

SUBJECT INDEX

- A. C. impedance study**
of Li in sulfur dioxide electrolytes, 37
- Ammoniates**
influence of water addition on structural and electrochemical behaviour of liquid; study of $\text{LiClO}_4 \cdot 4\text{NH}_3$ ammoniate/ H_2O mixtures, 305
- Anion behaviour**
in polyacetylene cathode for secondary Li battery, 231
- Anion diffusion process**
analysis of; application of electrochemically formed polypyrrole in Li secondary batteries, 237
- Anions**
as supporting electrolytes for rechargeable batteries, new, 287
- Battery(ies)**
Li
in China, research and development, 145
diffusion of Li in TiO_2 cathode of, 127
with fibrous carbon fluoride, discharge characteristics of, 99
future of; round table discussion, 345
stable electrolytes for, 19
testing techniques for materials used in, 75
Li foils for, study of surface layers on, 265
Li rechargeable
new anions as supporting electrolytes for, 287
development of, 3
electrochemical and structural characteristics of Nb(V) oxide in, 193
employing a porous thin film of $\text{Cu}_{3+\delta}\text{Mo}_6\text{S}_{7,9}$, 199
organic electrolyte solutions for, 273
Li secondary
anion behaviour in polyacetylene cathode for, 231
application of electrochemically formed polypyrrole in, analysis of anion diffusion process, 237
electrochemical behaviour of amorphous $\text{V}_2\text{O}_5(-\text{P}_2\text{O}_5)$ cathodes for, 173
ethylene carbonate/ether solvents for electrolytes in, 293
fibrous polyaniline as positive active material in, 249
Li-thionyl chloride, as memory backup power source, characteristics of, 47
materials testing package for, and energy conversion systems, 81
polyaniline/Li, 243
- Battery cathode**
Li, amorphous chromium oxide, new, 151
- Battery performance**
effects of additive material CuFeS_2 on Li/CuO, 119
- Carbon fluoride**
discharge characteristics of Li battery with fibrous, 99
- Cathode(s)**
amorphous $\text{V}_2\text{O}_5(-\text{P}_2\text{O}_5)$, for Li secondary batteries, electrochemical behaviour of, 173
InSe, electron and phonon aspects in Li intercalated, 213
polyacetylene for secondary Li battery, anion behaviour in, 231
 TiO_2 , of Li battery, diffusion of Li in, 127
- Cathode composition**
Li-graphitic oxide cells; influence of electrolyte and, 105
- Cell(s)**
Li, discharge reaction and overpotential of graphite fluoride cathode in nonaqueous, 87
Li/Ag vanadium oxide, heat dissipation from, during storage and low-rate discharge, 179

- Li-graphitic oxide, influence of electrolyte and cathode composition, 105
- Li-I, with additive in poly(2-vinylpyridine) iodide, long-term discharge characteristics of, 141
- Li rechargeable
 - solvent effects on, 279
 - vanadium oxides as electrode materials for, 165
 - vanadium oxides in electrodes for, 157
- Li/SOCl₂, *in situ* micro-Raman study of discharge products of, 69
- Chromium oxide
 - amorphous, new Li battery cathode, 151
- Conductivity
 - structure-, relationship in polymer electrolytes formed by network polymers from poly[dimethylsiloxane-g-poly(ethylene oxide)] and lithium perchlorate, 327
- Copper
 - effects of additive material CuFeS₂ on Li/CuO battery performance, 119
 - Li/Cu₄O(PO₄)₂ couple; new version for long-life low-rate applications, 111
 - rechargeable Li battery employing porous thin film of Cu_{3+δ}Mo₆S_{7,9}, 199
- Cyclability
 - of Li electrode, 9
- Cycling characteristics
 - of Li, effect of solvent blending on, 299
- Discharge characteristics
 - of graphite fluoride prepared via graphite oxide, 93
 - of Li battery with fibrous carbon fluoride, 99
 - of Li-I cells with additive in poly(2-vinylpyridine) iodide, long-term, 141
- Discharge products
 - of Li/SOCl₂ cells, *in situ* micro-Raman study of, 69
- Discharge reaction
 - and overpotential of graphite fluoride cathode in nonaqueous lithium cell, 87
- Diffusion
 - of Li in TiO₂ cathodes of Li battery, 127
- Electrochemical behaviour
 - of amorphous V₂O₅(-P₂O₅) cathodes for Li secondary batteries, 173
 - influence of water addition on structural and, of liquid ammoniates; study of LiClO₄·4NH₃ ammoniate/H₂O mixtures, 305
- Electrochemical characteristics
 - of Nb(V) oxide in rechargeable Li battery, 193
- Electrochemical properties
 - of double-metal nitrides containing Li, preparation and, 311
- Electrode(s)
 - Li, cyclability of, 9
 - vanadium oxides as, for rechargeable Li cells, 65
- Electrode kinetics
 - in poly(ethylene oxide)-based electrolytes, 333
- Electrode materials
 - vanadium oxides as, for rechargeable Li cells, 165
- Electrolyte(s)
 - new anions as supporting, for rechargeable Li batteries, 287
 - composite Li, effect of different internal surfaces in, 317
 - ethylene carbonate/ether solvents for, in Li secondary batteries, 293
 - Li-graphitic oxide cells; influence of, and cathode composition, 105
 - Li intercalation materials with organic solvents and molten salts as, at temperatures between 60 and 175 °C, investigation of, 221
 - poly(ethylene oxide)-based, electrode kinetics in, 333
 - stable, for lithium batteries, 19
 - structure-conductivity relationship in polymer, formed by network polymers from poly[dimethylsiloxane-g-poly(ethylene oxide)] and lithium perchlorate, 327
 - sulfur dioxide, a.c. impedance study of Li in, 37
- Electron
 - and phonon aspects in Li intercalated InSe cathode, 213

- Energy conversion systems**
materials testing package for batteries and, 81
- Ethylene carbonate**
/ether solvents for electrolytes in Li secondary batteries, 293
- Fluoride**
discharge reaction and overpotential of graphite fluoride cathode in non-aqueous Li cell, 87
- Graphite fluoride**
discharge characteristics of, prepared via graphite oxide, 93
- Graphite fluoride cathode**
in nonaqueous Li cell, discharge reaction and overpotential of, 87
- Graphitic oxide**
Li-, cells; influence of electrolyte and cathode composition, 105
- Heat dissipation**
from Li/Ag vanadium oxide cells during storage and low-rate discharge, 179
- Impedance analysis**
of lithium systems, 135
- Indium**
Li intercalated InSe cathode, electron and phonon aspects in, 213
- Intercalation materials**
investigation of Li, with organic solvents and molten salts as electrolytes at temperatures between 60 and 175 °C, 221
- Internal surfaces**
in composite Li electrolytes, effect of different, 317
- Iodine**
Li-, cells with additive in poly(2-vinylpyridine) iodide, long-term discharge characteristics of, 141
- Ionic conduction**
in polyether-polyurethane networks containing lithium perchlorate, mechanism of, 339
- Iron**
effects of additive material CuFeS₂ on Li/CuO battery performance, 119
nature of oxidizing centres in transition metal phosphorus trisulfides MPS₃ (M = Fe, Ni), 205
- Lithium**
/Ag vanadium oxide cells, heat dissipation from, during storage and low-rate discharge, 179
/CuO battery performance, effects of additive material CuFeS₂ on, 119
/Cu₄O(PO₄)₂ couple; new version for long-life low-rate applications, 111
cycling characteristics of, effect of solvent blending on, 299
double-metal nitrides containing, preparation and electrochemical properties of, 311
graphite fluoride cathode in non-aqueous Li cell, discharge reaction and overpotential of, 87
-graphitic oxide cells; influence of electrolyte and cathode composition, 105
-I cells with additive in poly(2-vinylpyridine) iodide, long-term discharge characteristics of, 141
influence of water addition on structural and electrochemical behaviour of liquid ammoniates; study of LiClO₄·4NH₃ ammoniate/H₂O mixtures, 305
insertion of, into vanadium molybdenum oxides, 187
intercalated InSe cathode, electron and phonon aspects in, 213
intercalation materials with organic solvents and molten salts as electrolytes at temperatures between 60 and 175 °C, investigation of, 221
properties of LiCl layers formed on Li in various SOCl₂ solutions, 53
reduction of voltage delay in Li/SOCl₂ system; study of polymers with chlorine substituent groups as delay reducing additives, 61
/SO₂ cells, studies of high reliability long-life, 27
/SOCl₂ cells, discharge products of, *in situ* micro-Raman study of, 69
in sulfur dioxide electrolytes, a.c. impedance study of, 37
-thionyl chloride battery as memory back-up power source, characteristics of, 47
- Lithium battery(ies)**
in China, research and development of, 145
diffusion of Li in TiO₂ cathode of, 127

- discharge characteristics of, with fibrous carbon fluoride, 99
- the future of, round table discussion, 345
- polyaniline/, 243
- rechargeable
 - new anions as supporting electrolytes for, 287
 - development of, 3
 - employing porous thin film of $\text{Cu}_{3+\delta}\text{Mo}_6\text{S}_{7.9}$, 199
 - Nb(V) oxide in, electrochemical and structural characteristics of, 193
 - organic electrolyte solutions for, 273
- secondary
 - anion behaviour in polyacetylene cathode for, 231
 - application of electrochemically formed polypyrrole in, analysis of anion diffusion process, 237
 - electrochemical behaviour of amorphous $\text{V}_2\text{O}_5(-\text{P}_2\text{O}_5)$ cathodes for, 173
 - ethylene carbonate/ether solvents for electrolytes in, 293
 - fibrous polyaniline as positive active material in, 249
 - stable electrolytes for, 19
 - testing techniques for materials used in, 75
- Lithium battery cathode
 - amorphous chromium oxide, new, 151
- Lithium cell(s)
 - solvent effects on rechargeable, 279
 - vanadium oxides for rechargeable as electrode materials, 165
 - in electrodes, 157
- Lithium electrode(s)
 - cyclability of, 9
 - properties of passivating film on surface of, 259
- Lithium electrolytes
 - effect of different internal surfaces in composite, 317
- Lithium foils
 - for batteries, study of surface layers on, 265
- Lithium perchlorate
 - polyether-polyurethane networks containing, mechanism of ionic conduction in, 339
 - structure-conductivity relationship
 - in polymer electrolytes formed by network polymers from poly[di-methylsiloxane-g-poly(ethylene oxide)] and, 327
- Lithium systems
 - impedance analysis of, 135
- Memory back-up power source
 - characteristics of Li-thionyl chloride battery as, 47
- Metal nitrides
 - double-, containing Li, preparation and electrochemical properties of, 311
- Molybdenum
 - insertion of Li into vanadium, oxides, 187
 - rechargeable Li battery employing porous thin film of $\text{Cu}_{3+\delta}\text{Mo}_6\text{S}_{7.9}$, 199
- Nickel
 - nature of oxidizing centres in transition metal phosphorus trisulfides MPS_3 (M = Fe, Ni), 205
- Niobium(V) oxide
 - in rechargeable Li battery, electrochemical and structural characteristics of, 193
- Nitrides
 - double-metal, containing Li, preparation and electrochemical properties of, 311
- Organic electrolyte solutions
 - for rechargeable Li batteries, 273
- Organic solvents
 - and molten salts as electrolytes at temperatures between 60 and 175 °C, investigation of Li intercalation materials with, 221
- Oxidizing centres
 - in transition metal phosphorus trisulfides MPS_3 (M = Fe, Ni), nature of, 205
- Passivating film
 - on surface of Li electrodes, properties of, 259
- Phosphorus
 - amorphous $\text{V}_2\text{O}_5(-\text{P}_2\text{O}_5)$ cathodes for Li secondary batteries, electrochemical behaviour of, 173

- Li/Cu₄O(PO₄)₂ couple; new version for long-life low-rate applications, 111
- Polyacetylene
cathode for secondary Li battery, anion behaviour in, 231
- Polyaniline
fibrous, as positive active material in Li secondary batteries, 249
/Li battery, 243
- Poly[dimethylsiloxane-g-poly(ethylene oxide)]
structure-conductivity relationship in polymer electrolytes formed by network polymers from, and lithium perchlorate, 327
- Polyether
-polyurethane networks containing lithium perchlorate, mechanism of ionic conduction in, 339
- Poly(ethylene oxide)
-based electrolytes, electrode kinetics in, 333
- Polypyrrole
application of electrochemically formed, in Li secondary batteries, analysis of anion diffusion process, 237
- Polyurethane
polyether-, networks containing lithium perchlorate, mechanism of ionic conduction in, 339
- Poly(2-vinylpyridine) iodide
Li-I cells with additive in, long-term discharge characteristics of, 141
- Positive active material
fibrous polyaniline as, in Li secondary batteries, 249
- Reliability
studies of high, long-life Li/SO₂ cells, 27
- Selenium
Li intercalated InSe cathode, electron and phonon aspects in, 213
- Silver
Li/Ag vanadium oxide cells, heat dissipation from, during storage and low-rate discharge, 179
- Solvent blending
effect of, on cycling characteristics of Li, 299
- Solvent effects
on rechargeable Li cells, 279
- Structural characteristics
of Nb(V) oxide in rechargeable Li battery, 193
- Structure
-conductivity relationship in polymer electrolytes formed by network polymers from poly[dimethylsiloxane-g-poly(ethylene oxide)] and lithium perchlorate, 327
- Sulfur
discharge products of Li/SOCl₂ cells, *in situ* micro-Raman study of, 69
effects of additive material CuFeS₂ on Li/CuO battery performance, 119
long-life Li/SO₂ cells, studies of high reliability, 27
properties of LiCl layers formed on Li in various SOCl₂ solutions, 53
rechargeable Li battery employing porous thin film of Cu_{3+δ}Mo₆S_{7.9}, 199
reduction of voltage delay in Li/SOCl₂ system; study of polymers with chlorine substituent groups as delay reducing additives, 61
- Sulfur dioxide
electrolytes, a.c. impedance study of Li in, 37
- Testing package
materials, for batteries and energy conversion systems, 81
- Testing techniques
for materials used in Li batteries, 75
- Thionyl chloride
characteristics of Li-, battery as memory back-up power source, 47
- Titanium
diffusion of Li in TiO₂ cathode of Li battery, 127
- Transition metal phosphorus trisulfides
nature of oxidizing centres in MPS₃ (M = Fe, Ni), 205
- Vanadium oxides
amorphous V₂O₅(-P₂O₅) cathodes for Li secondary batteries, electrochemical behaviour of, 173

- Li/Ag, cells, heat dissipation from, during storage and low-rate discharge, 179
- Mo, insertion of Li into, 187
- for rechargeable Li cells
 - as electrode materials, 165
 - in electrodes, 157
- Voltage delay
 - in Li/SOCl₂ system, reduction of; study of polymers with chlorine substituent groups as delay reducing additives, 61
- Water addition
 - influence of, on structural and electrochemical behaviour of liquid ammoniates; study of LiClO₄·4NH₃ ammoniate/H₂O mixtures, 305