



ELSEVIER

Journal of Power Sources 88 (2000) 287–297

JOURNAL OF
**POWER
SOURCES**

www.elsevier.com/locate/jpowsour

Patents ALERT

This section contains abstracts of recently issued patents in the United States and published patent applications filed from over 90 countries under the Patent Cooperation Treaty and compiled in accordance with interest profiles developed by the Editors.

Further information about complete patents can be obtained from:

REEDFAX Document Delivery System
275 Gibraltar Road, Horsham, PA 19044, USA

Phone: +1 215 441-4768
Fax: +1 215 441-5463
WWW: www.reedfax.com

Journal of Power Sources



REEDFAX The Patent Connection⁷
a division of Lexis-Nexis⁷
275 Gibraltar Road, Horsham, PA 19044-0962 USA

Phone: 1-800-422-1337 or +1.215.441.4768

FAX: 1-800-421-5585 or +1.215.441.5463

Email: email@reedfax.com

WWW: www.reedfax.com

FAX + 1-215-441-5463

Complete and return to confirm your personal 24-hour REEDFAX⁷
account number.

AUTHORIZED SIGNATURE _____

Name (please print) _____

Title _____

Company _____

Address _____

City _____ State _____ Zip _____

Phone _____ Fax _____

Email Address _____

Password (To use our electronic delivery services) _____

Name to appear on faxed patent documents. If same as above, check box:

Name (please print) _____

Check here if you plan to use Client Numbers (Client charge-back numbers)

Tax Exempt Number (For PA, FL and NY) _____

Name and address for billing. If same as above, check box:

LEAD ACID**5958623****ELECTROCHEMICAL CELL EMPLOYING A FINE CARBON ADDITIVE**

Kozawa Akiya; Mase Shunzo; Sato Atsushi; Ukino Chiaki-cho; Ichinomiya-shi, Aichi-ken, 491, Tobishimamura, Ama-gun, Aichi-ken, 490-14, Meitoku, Nagoya-shi, Aichi-ken, 465, JAPAN H01M 402

An electrochemical cell such as a lead acid cell, wherein fine carbon particles with or without an organic material is disposed in the electrolyte of the cell, deposited on the surface of the electrically active material of the cell and/or dispersed within the electrically active material of the cell.

5958625**POSITIVE LEAD-ACID BATTERY GRIDS AND CELLS AND BATTERIES USING SUCH GRIDS**

Rao Purushothama; Aurora, IL, UNITED STATES assigned to GNB Technologies H01M 468

Positive grids for lead-acid batteries for SLI, industrial battery, and electric vehicle batteries are disclosed in which the positive active material paste pellet openings have a reduced area and the number per square inch of the grid area are increased, the individual areas and the number of paste pellets varying with the intended application, and the preferred embodiments including reduced distances from the center of the paste pellet to the adjacent grid wires, as well as an optimized amount of positive active material per area of the grid wire surface area so as to allow enhanced electrical performance, if desired, or substantial savings in grid weight while achieving electrical performance commensurate with conventional lead-acid cells and batteries.

5962161**RECOMBINANT BATTERY SEPARATOR**

Zucker Jerry; Charleston, SC, UNITED STATES assigned to Daramic H01M 216

A recombinant battery separator pad is made from a mat of meltblown ultrafine polymer fibers, with the fibers being treated with an agent to render them permanently wettable. The fibers include at least 10% of less than 1 μm , with the majority less than 5 μm . The mat has a liquid porosity of at least 90% and a surface area of at least 1.0 m^2/g .

5962164**NATURAL OIL BATTERY ELECTROLYTE ADDITIVE**

Lajeunesse Yves; Palm Beach Gardens, FL, UNITED STATES assigned to Valany Import Export H01M 604

The instant invention is an electrolyte additive for use with lead acid batteries containing antimony. The electrolyte

additive consists of a mixture of natural oil such as white mineral oil or a hydrocracked and treated oil with naphthenic oil, a zinc-free rust and oxidation inhibitor and an ethylene-propylene copolymer. The electrolyte additive is placed above the plate cells in lead acid batteries having antimony to inhibit gassing and misting with an ancillary benefit of increasing performance and durability of the battery.

FUEL CELL**5958304****DOPED LANTHANUM CHROMITE MATERIAL FOR BIPOLAR INTERCONNECTS FOR SOLID OXIDE FUEL CELLS**

Khandkar Ashok C.; Milliken Christopher E.; Elangovan Singaravelu; Hartvigsen Joseph J.; Salt Lake City, Sandy, Kaysville, UT, UNITED STATES assigned to Gas Research Institute H01B 108, H01M 222

An improved ceramic interconnect component for a solid oxide fuel cell having good electrical conductivity and thermodynamic stability in the presence of fuel and a coefficient of thermal expansion matching closely that of zirconia electrolytes is disclosed. The interconnect is a lanthanum chromite material including strontium and magnesium as dopants.

5958613**POLYMER ELECTROLYTE FUEL CELL AND A POLYMER ELECTROLYTE FUEL CELL SYSTEM WHICH SUPPLY ANODE-SIDE CHANNELS WITH A GAS-LIQUID MIXTURE**

Hamada Akira; Matsubayashi Takaaki; Nakaoka Toru; Miyake Yasuo; Nakajima Toshikazu; Osaka, Fukui, JAPAN assigned to Sanyo Electric H01M 804

A polymer electrolyte fuel cell system with a polymer electrolyte fuel cell is made up of a cell main body, a mixture generator for generating a gas-liquid mixture by mixing fuel gas which has been supplied from a fuel gas supply with water, and a means for supplying the gas-liquid mixture to the anode-side channels. The gas-liquid mixture allows the solid-polymer film to be moistened without humidifying fuel gas and oxidant gas with a humidifier, and the cell main body to be cooled down without providing a cooling channel therein.

5958614**FUEL CELL GENERATING SET INCLUDING LYSHOLM COMPRESSOR**

Takei Noburo; Takabe Shigeru; Urayasu, Sagamihara, JAPAN assigned to Ishikawajima-Harima Heavy Industries H01M 804

There is provided a fuel cell generating set including (a) a fuel cell, (b) a Lysholm compressor, (c) a gas-liquid

separation apparatus condensing humidity generated in the fuel cell into water and retaining the thus-produced water therein, and (d) an injection pump for injecting the water to an intake port of the Lysholm compressor. The water exchanges heat with air under pressure in the Lysholm compressor to thereby cool air to be discharged from the Lysholm compressor by latent heat of vaporization. The water injected from the injection pump seals a leakage path in the Lysholm compressor. The above-mentioned generating set enhances volumetric efficiency and temperature efficiency of a Lysholm compressor, which ensures that the generating set can operate with less power and the generating set can be made smaller in size and lighter in weight. In addition, it is not necessary to supply water to the generating set, because the generating set is self-sufficient with respect to water.

5958616

MEMBRANE AND ELECTRODE STRUCTURE FOR METHANOL FUEL CELL

Salinas Carlos; Simpson Stanley F.; Murphy Oliver J.; Franaszczuk Krzysztof; Moaddel Homayoun; Weng Dacong; Bryan, College Station, TX, United States assigned to Lynntech H01M 486

The invention provides devices and techniques for reducing or eliminating fuel crossover from the anode to the cathode in fuel cells using organic fuels. The invention particularly provides proton exchange membranes having passages or channels with or without a catalyst layer active for the electrochemical oxidation of a fuel. The invention reduces fuel crossover by providing void spaces within the membrane where the fuel may be sequestered as it diffuses through the membrane from the anode to the cathode. The sequestered fuel may be removed physically and/or electrochemically. The invention provides for physical removal of the sequestered fuel by means of flowing a gas stream or a liquid stream through the passages thus evacuating the fuel before it diffuses to the cathode. Electrochemical removal of the fuel involves coating the inner walls of the passages with a catalyst, electronically connecting the catalyst with the anode, and electrooxidation of the crossover fuel sequestered in contact with the catalyst which is active for this oxidation process.

5962155

FUEL CELL SYSTEM

Kuranaka Sou; Gamou Takaharu; Morita Yoshio; Hatoh Kazuhito; Osaka, Fujiddera, Suita, Daito, JAPAN assigned to Matsushita Electric Industrial H01M 818

When a polymeric electrolyte type fuel cell operating at about 60°C is used, heating with exhaust gas becomes difficult. Therefore, a polymeric electrolyte type fuel cell

(PEM) is adopted as a fuel cell body, and a hydrogen storage vessel made of a metal containing hydrogen is connected to the PEM by a hydrogen supply piping via a humidifier for humidifying the electrolyte membrane of the PEM. The PEM and the hydrogen storage vessel are connected by a copper plate that is a conductor of heat. Heat generated in the PEM is transferred to the hydrogen storage vessel by this copper plate, and elevates the temperature and pressure in the vessel. By this, hydrogen is well supplied to the PEM.

5965010

ELECTROCHEMICAL AUTOTHERMAL REFORMER

Bloomfield David P.; Rabe Arthur N. Boston N. Quincy, MA, UNITED STATES assigned to Niagara Mohawk Power B01D 7102, B01D 5322

An electrochemical autothermal reformer (EATR) provides hydrogen. The EATR includes an autothermal reformer region, a reformer anode supply region, and a composite membrane layer separating the reformer anode from the autothermal reformer region. The composite membrane layer includes a mechanically stable porous ceramic support member with a thin gas permeable ceramic substrate layer overlaying the support member. Overlaying the substrate layer is a first thin metallic catalyst layer that promotes the dissociation of H_2 to $2H^+ + 2e^-$. Overlaying the first catalyst layer is a metallic oxide layer capable of conducting $2H^+ + 2e^-$ at elevated temperatures. Overlaying the metallic oxide layer is a second thin metallic catalyst layer that promotes the recombination of $2H^+ + 2e^-$ to H_2 .

BATTERY MATERIALS

5958281

LITHIUM ION-CONDUCTIVE SOLID ELECTROLYTE AND METHOD FOR PRODUCING THE SAME

Takada Kazunori; Iwamoto Kazuya; Kondo Shigeo; Ikeda Nobuhiko; Yamamoto Kazutomi; Uematsu Toshikatsu; Osaka, Sakai, Hirakata, Higashikurume, Kokubunji, JAPAN assigned to Matsushita Electric Industrial H01M 436

A method for producing an electrochemically advantageous lithium ion-conductive solid electrolyte with high ionic conductivity, low electronic conduction and electrochemical stability is disclosed. The method comprises the steps of synthesizing lithium sulfide by reacting lithium hydroxide with a gaseous sulfur source at a temperature of not less than 130°C and not more than 445°C, thermally melting plural compounds containing at least silicon sulfide and the synthesized lithium sulfide, and cooling the

molten mixture. The silicon sulfide is synthesized by the steps of adding a silicon powder to molten sulfur while stirring to disperse the silicon powder in the molten sulfur and heating the silicon powder-dispersed sulfur in a reaction chamber under reduced pressure.

5958362

METHOD OF PRODUCING ACTIVE MATERIAL POWDER FOR LITHIUM SECONDARY BATTERY

Takatori Kazumasa; Watanabe Naoyoshi; Tani Toshihiko; Sasaki Tsuyoshi; Takahashi Akio; Kato Masahiko; Murakami Akihiko; Nagoya, Aichi-ken, Tokai, JAPAN assigned to Kabushiki Kaisha Toyota Chuo Kenkyusho C01B 1314, C01G 4900, C01G 302, H01M 432

The aim of the present method is to produce an active material powder formed of a spinel oxide containing lithium or a layer-structured oxide containing lithium for a lithium secondary battery which is uniform in composition, fine in particle size and free of oxygen defects, and which is unlikely to cause capacity deterioration resulting from repetitive charge/discharge cycles at a high current density. A suspension 1 prepared by suspending an ingredient of the active material powder in a combustible liquid or an emulsion prepared by emulsifying a solution of the ingredient in the combustible liquid is sprayed in a droplet state 15 together with an oxygenic gas 2. The combustible liquid contained in the droplet 15 is burned to have the ingredient therein reacted and to evaporate the solvent. As a result, active material powder 4 formed of the spinel oxide containing lithium is obtained. An active material powder formed of the layer-structured oxide containing lithium is obtained by re-heating the oxide powder that has been generated by spraying and burning the droplet.

5958622

NEGATIVE ELECTRODE MATERIAL FOR LITHIUM SECONDARY BATTERIES

Kojima Yoshitsugu; Koiwai Akihiko; Suzuki Nobuaki; Yamamoto Satoru; Aichi, JAPAN assigned to Kabushiki Kaisha Toyota Chuo Kenkyusho H01M 458

A negative electrode material capable of absorbing and desorbing lithium is comprised of a mixture of coke and graphite. The amount of graphite in the mixture is near to that which induces percolation transition. Preferably, the amount of graphite in the mixture is 2–37 wt.% relative to the total amount of the coke and graphite. The coke may be prepared by heating raw coke from oil or coal at 500–900°C The coke may be 0.06 or more in the atomic ratio of hydrogen to carbon and 0.003 or more in the atomic ratio of oxygen to carbon. The graphite may be 0.5–30 μm in a mean particle size. Lithium secondary batteries comprising the negative electrodes have a large discharge capacity.

5961671

APPARATUS AND METHOD OF PREPARING ELECTROCHEMICAL CELLS

Guindy Wade; Cochran Steven D.; Richwine Carl; Adamson George; Mitchell Porter H.; Henderson, Las Vegas, NV, UNITED STATES assigned to Valence Technology H01M 1038

A method for removing plasticizers such as dibutyl phthalate from the anode, cathode, and polymeric matrix components of electrochemical cell precursors using carbon dioxide in the supercritical state is provided. The method forms porous polymeric structures that enhance the mass transport of ions in the cell, which results in improved electrochemical performance.

5961950

METHOD FOR PREPARING SOLID SOLUTION MATERIALS SUCH AS LITHIUM MANGANESE OXIDE

Dahn Jeffery Raymond; Rossen Erik; Reimers Jan N.; Fuller Eric Wayne; Surrey, North Vancouver, Maple Ridge, CANADA assigned to NEC Moli Energy (Canada) C01G 4500, C01D 1500

Lithiated manganese oxides are synthesized using a novel two-stage process. Using appropriate starting materials, lithiation is accomplished via low-temperature ion exchange in aqueous warm salt solution. A drying stage follows which completes the synthesis. Materials suitable for use as cathodes in lithium ion rechargeable batteries have been prepared in this way. Other solid solution transition metal materials might also be prepared using a similar low-temperature ion exchange process.

5962165

HYDROGEN-ABSORBING ALLOY, METHOD OF SURFACE MODIFICATION OF THE ALLOY, NEGATIVE ELECTRODE FOR BATTERY AND ALKALINE SECONDARY BATTERY

Tsuruta Shinji; Kohno Tatsuoki; Kanda Motoya; Yokohama, Kawasaki, JAPAN assigned to Kabushiki Kaisha Toshiba H01M 446

A hydrogen-absorbing alloy which is excellent in stability in an aqueous solution and in mechanical pulverizability is disclosed. This hydrogen-absorbing alloy contains an alloy represented by the following general formula (I): wherein M1 is at least one element selected (excluding Mg, elements which are capable of causing an exothermic reaction with hydrogen, Al and B) from elements which are incapable of causing an exothermic reaction with hydrogen; and y is defined as $1 < y \leq 1.5$.

5962168**POLYMER ELECTROLYTE SOLVENT FOR ELECTROCHEMICAL CELL**

Denton III Frank R.; Lawrenceville, GA, UNITED STATES assigned to Motorola H01M 1040

An electrochemical cell includes first and second electrodes with an electrolyte system disposed therebetween. The electrolyte system includes a polymeric support structure through which is dispersed an electrolyte active species in a solvent. The solvent comprises a poly(vinylidene fluoride) having a number average molecular weight of less than about 50,000 atomic mass units. Alternatively, the solvent may be a blend or copolymer of polyvinylidene fluoride and another solvent or polymer.

5962170**ELECTROCHEMICAL CELL**

Mitchell Porter H.; Las Vegas, NV, UNITED STATES assigned to Valence Technology H01M 1040

A method of preparing an electrochemical cell wherein the electrode material adheres to the current collector to create good electrical contact is provided. A critical aspect in the process of preparing the polymer mixture for both the anode and cathode slurries is that the polymer (or copolymer) not be subject to high shear so as to be degraded. Polymer degradation contributes to the creation of the polymer concentration gradient in the electrode film.

5962171**COMPOSITION USEFUL IN ELECTROLYTES OF SECONDARY BATTERY CELLS**

Boguslavsky Leonid I.; Mikhaylik Yuriy V.; Gavrilov Alexei B.; Skotheim Terje A.; Tucson, AZ, UNITED STATES assigned to Moltech H01M 1040

Provided is a nonaqueous electrolyte element for use in secondary battery cells which comprises an effective lithium stripping enhancing amount of one or more soluble materials, such as a lithium polysulfide, which increases the lithium stripping efficiency. Also provided is a secondary lithium battery cell comprising said nonaqueous electrolyte element. Such a nonaqueous electrolyte element can be advantageously used in the manufacture of secondary electric-current-producing cell elements, and provides many advantages in achieving extended cycle life and increased safety of secondary lithium batteries.

5962720**METHOD OF SYNTHESIZING UNSYMMETRIC ORGANIC CARBONATES AND PREPARING NONAQUEOUS ELECTROLYTES FOR ALKALI ION ELECTROCHEMICAL CELLS**

Gan Hong; Palazzo Marcus; Takeuchi Esther S.; East Amherst, Niagara Falls, East Amherst, NY, UNITED STATES assigned to Wilson Greatbatch C07C 6806

The present invention relates to an improved method of synthesizing unsymmetric linear organic carbonates comprising the reaction of two symmetric dialkyl carbonates, R^1 and R^2 , in the presence of a nucleophilic reagent or an electron-donating reductant as a catalyst, wherein R^1 and R^2 can be either saturated or unsaturated alkyl or aryl groups, is described. The present invention further provides a preparation method for a nonaqueous organic electrolyte having an unsymmetric linear organic carbonate as a co-solvent.

5964903**METHOD OF PREPARING ELECTROCHEMICAL CELLS**

Gao Feng; Mitchell Porter H.; Barker Jeremy; Henderson, Las Vegas, NV, UNITED STATES assigned to Valence Technology H01M 218, H01M 460

A method of fabricating electrochemical cells employing novel plasticizers that can be removed by evaporation under vacuum is provided thereby obviating the need for solvent extraction. The plasticizers comprise 2-(2-ethoxyethoxy) ethyl acetate, dimethyl adipate, dibutyl phthalate, propylene carbonate, and mixtures thereof.

5965054**NONAQUEOUS ELECTROLYTE FOR ELECTRICAL STORAGE DEVICES**

McEwen Alan B.; Yair Ein-Eli; Melrose, Waltham, MA, UNITED STATES assigned to Covalent Associates H01M 616, H01G 9022

Improved nonaqueous electrolytes for application in electrical storage devices such as electrochemical capacitors or batteries are disclosed. The electrolytes of the invention contain salts consisting of alkyl substituted, cyclic delocalized aromatic cations, and their perfluoro derivatives, and certain polyatomic anions having a van der Waals volume less than or equal to 100 \AA^3 , preferably inorganic perfluoride anions and most preferably PF_6^- , the salts being dissolved in organic liquids, and preferably alkyl carbonate solvents, or liquid sulfur dioxide or combinations thereof, at a concentration of greater than 0.5 M and preferably greater than 1.0 M. Exemplary electrolytes comprise 1-ethyl-3-methylimidazolium hexafluorophosphate dissolved in a cyclic or acyclic alkyl carbonate, or methyl formate, or a combination thereof. These improved electrolytes have useful characteristics such as higher conductivity, higher concentration, higher energy storage capabilities, and higher power characteristics compared to prior art electrolytes. Stacked capacitor cells using electrolytes of the invention permit high energy, high voltage storage.

5965289**SEPARATOR FOR BATTERIES**

Han Kyeng-ho; Chungchongnam-do, SOUTH KOREA assigned to Samsung Display Devices H01M 218

A separator for a battery includes a first separating layer for preventing a short circuit between a positive electrode and a negative electrode and a second separating layer having higher electrolyte retaining power than the first separating layer. The second separating layer is attached on the first separating layer. The second separating layer is made of polyethylene terephthalate, and the first separating layer is selected from the group consisting of nylon and polypropylene. Preferably, the first separating layer is attached on the second separating layer through a thermal fusing process.

5965299**COMPOSITE ELECTROLYTE CONTAINING SURFACE MODIFIED FUMED SILICA**

Khan Saad A.; Fedkiw Peter S.; Baker Gregory L.; Fan Jiang; Raghavan Srinivasa R.; Hou Jun; Cary, Raleigh, Haslett, Dublin, Berkeley, CA, UNITED STATES assigned to North Carolina State University, Michigan State University H01M 618, H01M 1008

A composite electrolyte comprises (a) surface modified fumed silica filler, wherein the surface modified fumed silica comprises polymerizable groups on the surface thereof, the polymerizable groups being bonded to each other such that the surface modified fumed silica filler is crosslinked in a three-dimensional structure; (b) a dissociable lithium salt; and (c) a bulk medium which contains the surface-modified fumed silica filler and the dissociable lithium salt. An electrochemical cell comprises an anode, a cathode, and a composite electrolyte dispersed between the anode and cathode.

5968681**POLYETHER COPOLYMER AND POLYMER SOLID ELECTROLYTE**

Miura Katsuhito; Yanagida Masanori; Higobashi Hiroki; Endo Takahiro; Sanda, Amagasaki, JAPAN assigned to Daiso H01M 600

A polyether copolymer prepared from 5% to 95% by mol of a monomer of the formula (I), 95–5% by mol of a monomer of the formula (II) and 0–15% by mol of a monomer of the formula (III) or (IV) as a crosslinking component; the copolymer having a weight-average molecular weight within the range from 10^3 to 10^7 : The copolymer of the present invention provides a polymer solid electrolyte having such a feature that it is superior in ionic conductivity and also superior in processability, moldability, mechanical strength and flexibility to a conventional solid electrolyte.

5968685**BATTERY ELECTRODE SUBSTRATE AND PROCESS FOR PRODUCING THE SAME**

Harada Keizo; Watanabe Kenichi; Yamanaka Shosaku; Hayashi Kiyoshi; Morishita Nobuyasu; Takeshima Hiroki; Kaiya Hideo; Ikoma Munehisa; Itami, Neyagawa, Fujidaira, Fujisawa, Chigasaki, Nara, JAPAN assigned to Sumitomo Electric Industries, Matsushita Electric Industrial H01M 470

A battery electrode substrate which is constituted of a porous metallic body structure having communicating pores at a porosity of at least 90% and an Fe/Ni multilayer structure wherein the skeletal portion of the porous metallic body is composed mainly of Fe and has a Ni covering layer on the surface thereof while pores communicating with the inside and outside of Fe skeletal portion exist in the Fe skeletal portion and the inside of the pores is covered with Ni. The electrode substrate is produced by applying an iron oxide powder of at most 20 μm in an average particle size on a porous resin core body; heat treating the core to remove an organic resin component while simultaneously sintering Fe to obtain a porous Fe body; and then covering the Fe skeletal portion with Ni by electroplating. In this process, the iron oxide can be used in combination with carbon powder. Further, a nickel porous sintered body can also be produced using nickel oxide in place of iron oxide.

LITHIUM BATTERIES**5961672****STABILIZED ANODE FOR LITHIUM-POLYMER BATTERIES**

Skotheim Terje A.; Soloveichik Grigorii L.; Gavrilov Alexei B.; Tucson, AZ, UNITED STATES assigned to Moltech H01M 1040

The invention relates to thin film solid state electrochemical cells consisting of a lithium metal anode, a polymer electrolyte and a cathode, where the lithium anode has been stabilized with a polymer film capable of transmitting lithium ions. Methods for making battery cells using the anode stabilizing films of the invention are disclosed.

5962162**LITHIUM ION POLYMER CELL SEPARATOR**

Barrella Joseph N.; Manna Michael E.; Irvington, Waterloo, NY, UNITED STATES assigned to Ultralife Batteries H01M 216

A lithium ion cell with a polymeric anode and cathode and a separator therebetween. The separator, such as of non-woven polymeric fibers is provided with its own discrete structure, without carrier substrate, and with structural integrity, apart from being laminated/compressed between the polymeric anode and cathode elements. Operable cells

are made thinner despite the self-supporting discrete structure, with obtained improved rate capacity and high temperature performance.

5962169

LITHIUM ION CONDUCTING ELECTROLYTES

Angell Charles Austen; Liu Changle; Xu Kang; Skotheim Terje A.; Mesa, Midland, Montgomery Village, Tucson, AZ, UNITED STATES assigned to Arizona Board of Regents H01M 1036, H01M 1040

The present invention relates generally to highly conductive alkali-metal ion non-crystalline electrolyte systems, and more particularly to novel and unique molten (liquid), rubbery, and solid electrolyte systems which are especially well suited for use with high current density electrolytic cells such as primary and secondary batteries.

5964902

USE OF B₂O₃ ADDITIVE IN NON-AQUEOUS RECHARGEABLE LITHIUM BATTERIES

Mao Huanyu; Reimers Jan Naess; Burnaby, Maple Ridge, CANADA assigned to NEC Moli Energy (Canada) H01M 616

The loss in delivered capacity upon cycling non-aqueous rechargeable lithium batteries can be reduced by incorporating a small amount of B₂O₃ additive in the electrolyte. The B₂O₃ additive is preferably dissolved in the electrolyte prior to assembling the battery. The invention is particularly suited to lithium ion rechargeable batteries.

5965296

NONAQUEOUS SECONDARY BATTERY AND A METHOD OF MANUFACTURING A NEGATIVE ELECTRODE ACTIVE MATERIAL

Nishimura Naoto; Yamada Kazuo; Tsukuda Yoshihiro; Mitate Takehito; Minato Kazuaki; Kitakatsuragi-gun, Yamatotakada, Osaka, JAPAN assigned to Sharp Kabushiki Kaisha H01M 438

A nonaqueous secondary battery comprising a negative electrode, a positive electrode in which a chalcogenated substance containing lithium is used as a positive electrode active material and a nonaqueous ion conductor, said negative electrode containing a negative electrode active material which is a carbon material where an amorphous carbon is adhered on the surface of graphite particles which are subjected to an oxidizing treatment.

5965300

POLYMER SOLID ELECTROLYTE, METHOD FOR MANUFACTURING POLYMER SOLID ELECTROLYTE, AND LITHIUM SECONDARY CELL ADOPTING POLYMER SOLID ELECTROLYTE

Lee Doo-yeon; Seong Sang-hyun; Lee Hyung-bok; Uiwang, Seoul, SOUTH KOREA assigned to Samsung Electronics H01M 1008

A polymer solid electrolyte, a method for manufacturing the polymer solid electrolyte, and a lithium secondary cell adopting the polymer solid electrolyte are provided. The polymer solid electrolyte includes a polymer electrolyte medium, at least one vinylidene fluoride resin and/or at least one *N,N*-diethylacrylamide. The polymer solid electrolyte provides excellent ion conductivity and mechanical strength.

NICKEL METAL HYDRIDE BATTERIES

5962156

NICKEL-METAL HYDRIDE STORAGE BATTERY AND ALLOY FOR CONFIGURING NEGATIVE ELECTRODE OF THE SAME

Izumi Yoichi; Moriwaki Yoshio; Yamashita Katsumi; Tokuhiro Takashi; Habikino, Hirakata, Fujisawa, Kamakura, JAPAN assigned to Matsushita Electric Industrial H01M 1030, H01M 438

A nickel-metal hydride storage battery having a high capacity and excellent cycle life is disclosed. The battery employs, as its material for the negative electrode, a hydrogen storage alloy powder having a composition represented by the general formula $Zr_{1-x}M_3Mn_aMo_bCr_cM_1_dM_2_eNi_f$, where M1 represents at least one element selected from the group consisting of V, Nb and rare earth elements, M2 represents at least one element selected from the group consisting of Fe, Co and Cu, and M3 represents at least one element selected from the group consisting of Ti and Hf, and where $0 \leq x \leq 0.3$, $0.3 \leq a \leq 0.7$, $0.01 \leq b \leq 0.2$, $0.05 \leq c \leq 0.3$, $0 \leq d \leq 0.1$, $0 \leq e \leq 0.2$, $0.8 \leq f \leq 1.3$, and $1.6 \leq a + b + c + d + e + f \leq 2.2$, and wherein said hydrogen storage alloy has at least one of a Laves phase having a crystal structure of the MgCu₂-type (C15) and a Laves phase having a crystal structure of the MgZn₂-type (C14), and wherein a sum of integrated intensities of diffraction peaks other than those attributed to the presence of said Laves phase is not more than 5% of a sum of integrated intensities of all diffraction peaks in a diffraction angle 2θ of 10° – 80° in a powder X-ray diffraction pattern by Cu K α radiation.

5964968

RARE EARTH METAL-NICKEL HYDROGEN STORAGE ALLOY, METHOD FOR PRODUCING THE SAME, AND ANODE FOR NICKEL-HYDROGEN RECHARGEABLE BATTERY

Kaneko Akihito; Kobe, JAPAN assigned to Santoku Metal Industry H01M 402

A rare earth metal-nickel hydrogen storage alloy having a composition represented by the formula (1) (R: La, Ce, Pr, Nd; L: Gd, Tb, Dy, Ho, Er, Tm, Yb, Lu, Y, Sc, Mg, Ca; M: Co, Al, Mn, Fe, Cu, Zr, Ti, Mo, Si, V, Cr, Nb, Hf, Ta,

W, B, C; $0.01 \leq x \leq 0.1$; $0 \leq y \leq 0.5$; $4.5 \leq z \leq 5.0$, the alloy including in an amount of not less than 10 vol.% and less than 95 vol.% thereof crystals each containing not less than 2 and less than 20 antiphase boundaries extending perpendicular to C-axis of a crystal grain of the alloy per 20 nm along the C-axis, not less than 60% and less than 95% of added amount of said element represented by L in the formula (1) being arranged in antiphase areas, a method for producing the same, and an anode for a nickel-hydrogen rechargeable battery. The anode for a nickel-hydrogen rechargeable battery can improve initial activity, battery capacity, and battery life all at the same time.

5968684

NICKEL POSITIVE ELECTRODE FOR ALKALINE RECHARGEABLE BATTERIES AND NICKEL METAL HYDRIDE CELLS

Hayashi Kiyoshi; Tomioka Katsuyuki; Morishita Nobuyasu; Ikeyama Masakazu; Ikoma Munehisa; Katano, Toyohashi, JAPAN assigned to Matsushita Electric Industrial H01M 432

In the paste type nickel positive electrode prepared by filling pores of a metal nickel plaque made of three-dimensional high porous sheet, or coating both sides or one side of a plaque made of either perforated nickel sheet or nickel-plated steel sheet, with a paste type active material mainly composed of nickel hydroxide, by adding particles of cobalt hydroxide having the specific surface area of at least $10 \text{ m}^2/\text{g}$, average particle size of $1.7 \text{ }\mu\text{m}$ or more, and content of fine particles with particle size of $1.0 \text{ }\mu\text{m}$ or less of 20% or less, the utilization of positive electrode active material is enhanced, and by using this nickel positive electrode, the alkaline rechargeable battery, in particular, the nickel-metal hydride alkaline battery is enhanced in capacity and extended in service life.

CHARGERS AND / OR COMPONENTS

5969506

APPARATUS AND METHOD FOR RAPID BULK CHARGING OF A LEAD ACID BATTERY

Neal Martin; Redditch, GREAT BRITAIN assigned to C & K Systems H02J 700

Apparatus to rapidly bulk charge a lead acid battery used in a "standby" power supply unit (PSU), or similar equipment containing said function, such as in an alarm panel system, fire panel (system) etc., without increasing the output capacity of the regulated PSU, significantly increasing its dissipation, size or cost, or causing an unacceptable recharge time of (often) several days. The apparatus comprises minimal additional components to provide a bulk charge of approximately 70% capacity to a 65 A h battery within 14 h, while only drawing an average current of approximately 0.4 A from the regulated PSU.

5969508

BATTERY CHARGING METHOD USING BATTERY CIRCUITRY IMPEDANCE MEASUREMENT TO DETERMINE OPTIMUM CHARGING VOLTAGE

Patino Joseph; Geren Michael D.; Dautre Barbara R.; Pembroke Pines, Suwanee, Plantation, FL, UNITED STATES assigned to Motorola H02N 700

A charging technique charges a battery pack by taking into account the additional internal circuit impedance of the battery pack. An optimum pack voltage value for the battery pack is calculated based on the rated internal cell voltage as well as the charge current and the internal battery pack circuitry impedance. The battery pack can now be charged such that the internal battery cell voltage is maintained at the rated voltage throughout the charging process. The optimum pack voltage is also updated to account for variations in the battery pack circuitry impedance over temperature as well as variations in charge current during the charging process.

OTHER BATTERIES

5958615

METAL-AIR CATHODE CAN, AND ELECTRO-CHEMICAL CELL MADE THEREWITH

McKenzie Rodney Stuart; Dopp Robert B.; Madison, WI, UNITED STATES assigned to Rayovac H01M 212

This invention pertains to metal-air electrochemical cells wherein one or more air entry ports is located in the bottom of the cathode can, to provide for entry of oxygen-rich air into the cathode can, where the oxygen participates in the chemical reaction whereby the cell produces electrical energy. In this invention, multiple small air entry ports are provided. Generally, the use of multiple ports distributed over the bottom of the cathode can, opposite the reaction surface of the cathode assembly, while not increasing the overall open area of the ports, results in an increase in the ratio of the cell limiting current to the rate at which moisture is lost from the cell. Accordingly, moisture loss as a function of electrical energy produced, is reduced. Preferred embodiments of the air entry ports have a stepped cross-sectional opening that provides a larger diffusion area controlling diffusion of air into and out of the cell through a covering tab prior to the cell being put into use, and a smaller untabbed diffusion area controlling diffusion of air into and out of the cell when the cell is in use.

5962160

SODIUM-SULFUR BATTERY, AND A BATTERY SYSTEM USING SAME

Oyama Tetsuo; Miyoshi Tadahiko; Madokoro Manabu; Hatoh Hisamitsu; Nishimura Shigeoki; Shiota Katsuhiko; Otaka Kiyoshi; Takahagi, Hitachi, Hitachinaka, Tokai-mura, Takahagi, JAPAN assigned to Hitachi H01M 1039

A highly reliable sodium–sulfur battery includes a cell container for the positive electrode, which is hardly deteriorated by corrosion. The cell container for the positive electrode is made of a Co base alloy containing Cr, Ni, and Mo, wherein carbide containing at least one of Cr, W, and Mo is precipitated, or the cell container for positive electrode is assembled by integrating plural members made of a high corrosion resistance alloy containing Cr by welding, and a readily deformable portion is provided to the cell container for positive electrode, whereby the reliability of the sodium–sulfur battery can be significantly improved.

5962167

**NON-AQUEOUS LIQUID ELECTROLYTE
SECONDARY CELL**

Nakai Kenji; Ochida Manabu; Tokyo, JAPAN assigned to Shin-Kobe Electric Machinery H01M 448

A non-aqueous liquid electrolyte secondary cell capable of preventing bursting or explosion thereof even when a current breaking device or a relief valve for pressure release fails in operation thereof due to any trouble or failure thereof. The cell includes a wound-up body formed by laminatedly spirally winding up a positive electrode and a negative electrode together while interposing a separator therebetween. The wound-up body thus formed is received in a cell can. The negative electrode is constructed by forming a negative active material layer containing amorphous carbon on each of both surfaces of a negative collector. The positive electrode is constructed by forming a positive active material layer containing Li_xCoO_2 on each of both surfaces of a positive collector. The negative electrode is electrically connected to the cell can through a negative electrode lead. The positive electrode is electrically connected to the cell lid through a positive electrode lead joined to a connection plate of the cell lid by welding.

5965290

NON-AQUEOUS ELECTROLYTE CELL

Shimizu Toshiyuki; Daio Fumio; Inui Takeshi; Sakai, Kitakatsuragi-gun, Yao, JAPAN assigned to Matsushita Electric Industrial H01M 400

A non-aqueous electrolyte cell has an electrode assembly including a negative electrode strip, a positive electrode strip having an active cathode material, and a separator. The positive electrode strip and the negative electrode strip are superposed with the separator therebetween and wound in a spiral. The negative electrode strip is disposed outside the positive electrode strip and has an outermost winding, a negative electrode strip winding end, and a penultimate winding. The positive electrode strip has an outermost winding terminating at a positive electrode strip-winding end. An anode current collector contacts the negative electrode strip on the penultimate winding and is radially aligned with a portion of the outermost winding of the positive electrode strip. Insulating tape is bonded to an

inside surface and an outside surface of the positive electrode strip extending from the positive electrode strip winding end and has an outer portion extending one of continuously and intermittently on the outer surface of the positive electrode strip a greater distance than an inner portion of the insulating tape covering the inner side of the positive electrode strip. In an embodiment, the outer portion of the insulating tape continuously extends from the positive electrode strip-winding end to a point radially aligned with the anode current collector. Alternatively, an auxiliary insulating tape is bonded to an inside surface of the outermost winding of the negative electrode strip in place of the above outer portion of the insulating tape.

5965293

NONAQUEOUS SECONDARY BATTERY

Idota Yoshio; Mishima Masayuki; Miyaki Yukio; Kubota Tadahiko; Miyasaka Tsutomu; Kanagawa, JAPAN assigned to Fuji Photo Film H01M 458

A nonaqueous secondary battery comprising a positive electrode active material, a negative electrode active material, and a lithium salt is disclosed, in which the negative electrode active material contains (1) a compound capable of intercalating and deintercalating lithium comprising an atom of the group IIIB, IVB or VB of the periodic table, (2) an amorphous compound containing at least two atoms selected from the elements of the groups IIIB, IVB, and VB of the periodic table, (3) a compound capable of intercalating and deintercalating lithium containing at least one of the atoms of the group IIIB, IVB, and VB of the periodic table and fluorine, or (4) a compound of the metal of the group IIIB, IVB or VB of the periodic table, Zn, or Mg which is capable of intercalating and deintercalating lithium. The nonaqueous secondary battery of the invention exhibits improved charge and discharge characteristics and improved safety.

5965295

**ALKALINE SECONDARY BATTERY, PASTE TYPE
POSITIVE ELECTRODE FOR ALKALINE
SECONDARY BATTERY, METHOD FOR
MANUFACTURING ALKALINE SECONDARY
BATTERY**

Bando Naomi; Yamane Tetsuya; Hiruma Masayoshi; Wakabayashi Makoto; Miyamoto Kunihiko; Fukuju Takeshi; Komiyama Ken; Kaneko Hiroshi; Kanno Ken-ichi; Kawasaki, Yokohama, Atsugi, Tokyo, Yokosuka, Yokohama, JAPAN assigned to Toshiba Battery H01M 432

An alkaline secondary battery comprising a positive electrode, a negative electrode, and an alkaline electrolyte, wherein the positive electrode comprises a conductive substrate and a mixture held by the conductive substrate, the mixture containing nickel hydroxide and a conductive cobalt compound, and the positive electrode has pores, substantially all of the pores each having a diameter with a range of 0.0001–10 μm .



REEDFAX™
The Patent Connection

REEDFAX The Patent Connection⁷
a division of Lexis-Nexis⁷
275 Gibraltar Road, Horsham, PA 19044-0962 USA

Phone: 1-800-422-1337 or +1.215.441.4768
FAX: 1-800-421-5585 or +1.215.441.5463
E-mail: E-mail@reedfax.com
WWW: www.reedfax.com

REEDFAX - The Patent Connection⁷ **Document Delivery System**

REEDFAX Products:

- US Patents (1971 to current issue on our automated delivery system)
- EP Patent Applications: (1990 to current on our automated delivery system)
- WO Patent Applications (1990 to current on our automated delivery system)
- US and Foreign File Histories / Wrappers
- US Trademarks
- Foreign patents
- Certified patents

Ordering Patents:

REEDFAX provides several ways for you to order patent documents:

- Patent Connection Software: Download from our WWW site at www.reedfax.com
- Internet Ordering System: Access at our WWW site www.reedfax.com. Order 24 hours / day.
- Voice Response System: Call 215-441-4768 to access our 24 hour voice response system to handle your US patent orders
- Customer Service: Fax your order to 215-441-5463, E-mail your order to E-mail@reedfax.com or call our Customer Service professionals at 215-441-4768. Our Customer Service hours are 8:30 am to 7:00 pm EST. (-5 hour GMT)

Delivery:

REEDFAX offers the following delivery options:

- Email or WWW page delivery: Available for any document on our automated system.
Electronic documents in Adobe⁷ Acrobat PDF format
- Fax Documents on our automated system usually fax within 15 minutes, other documents can take a couple of hours.
- Print: Laser printed copies shipped by courier or mail

No hidden charges at REEDFAX: no sign-on fees, no monthly fees and no minimum charges. You pay only for each patent delivered. Whatever your patent needs are – U.S. or foreign patents, trademarks, file histories/wrappers, printed, electronic delivery as Adobe PDF or faxed – we can fulfill them easily and promptly.

Fax, E-mail or visit our WWW page to request a free REEDFAX account number.