

## Subject Index of Volume 110, issue 1

- AC impedance**  
 Proton-conducting; Membrane; AMPS; Nafion®; Silica (Walker Jr., C.W. (110) 144)
- All solid polymer electrolyte aluminum corrosion**  
 Thermal safety; Four volts class; Capacity fade (Li, Q. (110) 38)
- Alternating current (ac) impedance**  
 Aluminium oxidation; Surface film; Lithium deposition; Cyclic voltammetry (Suresh, P. (110) 11)
- Aluminium oxidation**  
 Surface film; Lithium deposition; Cyclic voltammetry; Alternating current (ac) impedance (Suresh, P. (110) 11)
- Aluminum**  
 Anode; Primary batteries; Secondary batteries; Molten salt (Li, Q. (110) 1)
- m-Aminobenzoic acid**  
 Rechargeable battery; Polyaniline; Self-doped polyaniline (Rahmanifar, M.S. (110) 229)
- AMPS**  
 Proton-conducting; Membrane; AC impedance; Nafion®; Silica (Walker Jr., C.W. (110) 144)
- Anode**  
 Aluminum; Primary batteries; Secondary batteries; Molten salt (Li, Q. (110) 1)
- Batteries**  
 Ragone-plot; Supercapacitors; Economic optimization; Net present value (Christen, T. (110) 107)
- Bibliometric analysis**  
 Electrochemical power; Database tomography; Text mining; Information retrieval; Technical intelligence (Kostoff, R.N. (110) 163)
- Birnessite**  
 Manganese dioxide; Rechargeable lithium battery; Drying condition; Cyclability; Substitution (Tsuda, M. (110) 52)
- Br<sub>2</sub>/Br<sup>-</sup>-redox reaction**  
 Temperature difference; Thermocell; Thermoelectric power; Open-circuit voltage; Hysteresis (Shindo, K. (110) 46)
- Capacity fade**  
 All solid polymer electrolyte aluminum corrosion; Thermal safety; Four volts class (Li, Q. (110) 38)
- Capacity fading**  
 Li-ion battery; Spinel; Oxygen deficiency; Phase transition (Wang, X. (110) 19)
- Carbon composite electrode**  
 Electrochemical capacitor; Conductivity; Percolation; Pose diffusion resistance (Wu, N.L. (110) 233)
- Cathode**  
 MCFC; Mechanical strength; Lithiated nickel oxide; Single cell performance (Kim, S.-G. (110) 80)
- CO<sub>2</sub>-tolerance**  
 PEM fuel cell (PEMFC); Reformate; Reverse water-gas shift (de Bruijn, F.A. (110) 117)
- Composite electrolyte**  
 Low temperature SOFC; Sol-gel coating; YSZ thin film; Single cell performance (Kim, S.-G. (110) 222)
- Composite particle**  
 Spray pyrolysis; SOFCs; Ni-YSZ cermet anode; Long-term stability (Fukui, T. (110) 91)
- Composite polymer electrolyte**  
 Lithium battery; Thermoplastic polyurethane; Polyacrylonitrile (Kuo, H.-H. (110) 27)
- Conductivity**  
 Electrochemical capacitor; Carbon composite electrode; Percolation; Pose diffusion resistance (Wu, N.L. (110) 233)
- Coulometric gauge**  
 Lead-acid batteries; State of charge sensors (Blood, P.J. (110) 96)
- Crossover current**  
 1-Methoxy-2-propanol; Methanol; Direct liquid fuel cell (Qi, Z. (110) 65)
- Cyclability**  
 Manganese dioxide; Birnessite; Rechargeable lithium battery; Drying condition; Substitution (Tsuda, M. (110) 52)
- Cycle life**  
 Discharge capacity; X-ray absorption; Nickel-metal hydride battery (Ambrosio, R.C. (110) 73)
- Cyclic voltammetry**  
 Aluminium oxidation; Surface film; Lithium deposition; Alternating current (ac) impedance (Suresh, P. (110) 11)
- Database tomography**  
 Electrochemical power; Bibliometric analysis; Text mining; Information retrieval; Technical intelligence (Kostoff, R.N. (110) 163)
- Design of current collectors**  
 Lead-acid batteries; The structural parameters (Kamenev, Yu. (110) 133)
- Diffusion**  
 SOFC; SOFC modelling; Viscosity; Thermal conductivity; Gas mixture properties (Todd, B. (110) 186)
- Dimethoxyethane**  
 Electrospray ionization-mass spectroscopy; Solvation of lithium ion; Organic electrolyte solutions; Propylene carbonate (Fukushima, T. (110) 34)
- Direct liquid fuel cell**  
 1-Methoxy-2-propanol; Methanol; Crossover current (Qi, Z. (110) 65)
- Direct methanol fuel cell**  
 Open circuit voltage; Methanol crossover (Qi, Z. (110) 177)
- Discharge capacity**  
 Cycle life; X-ray absorption; Nickel-metal hydride battery (Ambrosio, R.C. (110) 73)
- Drying condition**  
 Manganese dioxide; Birnessite; Rechargeable lithium battery; Cyclability; Substitution (Tsuda, M. (110) 52)
- Economic optimization**  
 Ragone-plot; Batteries; Supercapacitors; Net present value (Christen, T. (110) 107)
- Electrochemical capacitor**  
 Carbon composite electrode; Conductivity; Percolation; Pose diffusion resistance (Wu, N.L. (110) 233)

- Electrochemical impedance  
LSM cathodes; Solid oxide fuel cell; Oxygen reduction (Jiang, S.P. (110) 201)
- Electrochemical power  
Database tomography; Bibliometric analysis; Text mining; Information retrieval; Technical intelligence (Kostoff, R.N. (110) 163)
- Electrolyte  
Li-ion cell; Propylene carbonate; Low temperature; Ionic conductivity (Zhang, S.S. (110) 216)
- Electrospray ionization-mass spectroscopy  
Solvation of lithium ion; Organic electrolyte solutions; Dimethoxyethane; Propylene carbonate (Fukushima, T. (110) 34)
- Four volts class  
All solid polymer electrolyte aluminum corrosion; Thermal safety; Capacity fade (Li, Q. (110) 38)
- Gas mixture properties  
SOFC; SOFC modelling; Viscosity; Thermal conductivity; Diffusion (Todd, B. (110) 186)
- Gel polymer electrolytes  
Lithium batteries; Polyvinylidene fluoride; Polyethyleneglycol diacrylate; UV-cured polymer blend; Miscibility (Song, M.-K. (110) 209)
- Hybrid capacitors  
Ruthenium oxide; Tantalum oxide (Chang, T.Y. (110) 138)
- Hybrid-electrode batteries  
Lithium battery; Pyrite battery (Ardel, G. (110) 152)
- Hydrous ruthenium oxide  
Transmission electron microscope; Selected area electron diffraction (Zheng, J.P. (110) 86)
- Hysteresis  
Temperature difference; Thermocell;  $\text{Br}_2/\text{Br}^-$ -redox reaction; Thermo-electric power; Open-circuit voltage (Shindo, K. (110) 46)
- Information retrieval  
Electrochemical power; Database tomography; Bibliometric analysis; Text mining; Technical intelligence (Kostoff, R.N. (110) 163)
- Ionic conductivity  
Li-ion cell; Propylene carbonate; Low temperature; Electrolyte (Zhang, S.S. (110) 216)
- Layered Li–Ni–Mn–O compounds  
Solid solutions; Phase transitions (Zhang, L. (110) 57)
- Lead-acid batteries  
Design of current collectors; The structural parameters (Kamenev, Yu. (110) 133)
- Lead–acid batteries  
State of charge sensors; Coulometric gauge (Blood, P.J. (110) 96)
- Li-ion battery  
Spinel; Capacity fading; Oxygen deficiency; Phase transition (Wang, X. (110) 19)
- Li-ion cell  
Propylene carbonate; Low temperature; Electrolyte; Ionic conductivity (Zhang, S.S. (110) 216)
- Lithiated nickel oxide  
MCFC; Cathode; Mechanical strength; Single cell performance (Kim, S.-G. (110) 80)
- Lithium batteries  
Gel polymer electrolytes; Polyvinylidene fluoride; Polyethyleneglycol diacrylate; UV-cured polymer blend; Miscibility (Song, M.-K. (110) 209)
- Lithium battery  
Hybrid-electrode batteries; Pyrite battery (Ardel, G. (110) 152)
- Lithium battery  
Thermoplastic polyurethane; Polyacrylonitrile; Composite polymer electrolyte (Kuo, H.-H. (110) 27)
- Lithium deposition  
Aluminium oxidation; Surface film; Cyclic voltammetry; Alternating current (ac) impedance (Suresh, P. (110) 11)
- Long-term stability  
Composite particle; Spray pyrolysis; SOFCs; Ni–YSZ cermet anode (Fukui, T. (110) 91)
- Low temperature SOFC  
Composite electrolyte; Sol-gel coating; YSZ thin film; Single cell performance (Kim, S.-G. (110) 222)
- Low temperature  
Li-ion cell; Propylene carbonate; Electrolyte; Ionic conductivity (Zhang, S.S. (110) 216)
- LSM cathodes  
Electrochemical impedance; Solid oxide fuel cell; Oxygen reduction (Jiang, S.P. (110) 201)
- Manganese dioxide  
Birnessite; Rechargeable lithium battery; Drying condition; Cyclability; Substitution (Tsuda, M. (110) 52)
- MCFC  
Cathode; Mechanical strength; Lithiated nickel oxide; Single cell performance (Kim, S.-G. (110) 80)
- Mechanical strength  
MCFC; Cathode; Lithiated nickel oxide; Single cell performance (Kim, S.-G. (110) 80)
- Membrane  
Proton-conducting; AC impedance; AMPS; Nafion<sup>®</sup>; Silica (Walker Jr., C.W. (110) 144)
- Methanol crossover  
Open circuit voltage; Direct methanol fuel cell (Qi, Z. (110) 177)
- Methanol  
1-Methoxy-2-propanol; Direct liquid fuel cell; Crossover current (Qi, Z. (110) 65)
- 1-Methoxy-2-propanol  
Methanol; Direct liquid fuel cell; Crossover current (Qi, Z. (110) 65)
- Miscibility  
Lithium batteries; Gel polymer electrolytes; Polyvinylidene fluoride; Polyethyleneglycol diacrylate; UV-cured polymer blend (Song, M.-K. (110) 209)
- Molten salt  
Aluminum; Anode; Primary batteries; Secondary batteries (Li, Q. (110) 1)
- Nafion<sup>®</sup>  
Proton-conducting; Membrane; AC impedance; AMPS; Silica (Walker Jr., C.W. (110) 144)
- Net present value  
Ragone-plot; Batteries; Supercapacitors; Economic optimization (Christen, T. (110) 107)
- Ni–YSZ cermet anode  
Composite particle; Spray pyrolysis; SOFCs; Long-term stability (Fukui, T. (110) 91)
- Nickel-metal hydride battery  
Cycle life; Discharge capacity; X-ray absorption (Ambrosio, R.C. (110) 73)
- Open circuit voltage  
Methanol crossover; Direct methanol fuel cell (Qi, Z. (110) 177)
- Open-circuit voltage  
Temperature difference; Thermocell;  $\text{Br}_2/\text{Br}^-$ -redox reaction; Thermo-electric power; Hysteresis (Shindo, K. (110) 46)
- Organic electrolyte solutions  
Electrospray ionization-mass spectroscopy; Solvation of lithium ion; Dimethoxyethane; Propylene carbonate (Fukushima, T. (110) 34)
- Oxygen deficiency  
Li-ion battery; Spinel; Capacity fading; Phase transition (Wang, X. (110) 19)

- Oxygen reduction  
Electrochemical impedance; LSM cathodes; Solid oxide fuel cell (Jiang, S.P. (110) 201)
- PEM fuel cell (PEMFC)  
Reformate; CO<sub>2</sub>-tolerance; Reverse water-gas shift (de Bruijn, F.A. (110) 117)
- Percolation  
Electrochemical capacitor; Carbon composite electrode; Conductivity; Pose diffusion resistance (Wu, N.L. (110) 233)
- Phase transition  
Li-ion battery; Spinel; Capacity fading; Oxygen deficiency (Wang, X. (110) 19)
- Phase transitions  
Layered Li-Ni-Mn-O compounds; Solid solutions (Zhang, L. (110) 57)
- Polyacrylonitrile  
Lithium battery; Thermoplastic polyurethane; Composite polymer electrolyte (Kuo, H.-H. (110) 27)
- Polyaniline  
Rechargeable battery; *m*-Aminobenzoic acid; Self-doped polyaniline (Rahmanifar, M.S. (110) 229)
- Polyethyleneglycol diacrylate  
Lithium batteries; Gel polymer electrolytes; Polyvinylidene fluoride; UV-cured polymer blend; Miscibility (Song, M.-K. (110) 209)
- Polyvinylidene fluoride  
Lithium batteries; Gel polymer electrolytes; Polyethyleneglycol diacrylate; UV-cured polymer blend; Miscibility (Song, M.-K. (110) 209)
- Pose diffusion resistance  
Electrochemical capacitor; Carbon composite electrode; Conductivity; Percolation (Wu, N.L. (110) 233)
- Positive active material  
VRLA; Soaking (Lawrence, E.L. (110) 125)
- Primary batteries  
Aluminum; Anode; Secondary batteries; Molten salt (Li, Q. (110) 1)
- Propylene carbonate  
Electrospray ionization-mass spectroscopy; Solvation of lithium ion; Organic electrolyte solutions; Dimethoxyethane (Fukushima, T. (110) 34)
- Propylene carbonate  
Li-ion cell; Low temperature; Electrolyte; Ionic conductivity (Zhang, S.S. (110) 216)
- Proton-conducting  
Membrane; AC impedance; AMPS; Nafion®; Silica (Walker Jr., C.W. (110) 144)
- Pyrite battery  
Lithium battery; Hybrid-electrode batteries (Ardel, G. (110) 152)
- Ragone-plot  
Batteries; Supercapacitors; Economic optimization; Net present value (Christen, T. (110) 107)
- Rechargeable battery  
Polyaniline; *m*-Aminobenzoic acid; Self-doped polyaniline (Rahmanifar, M.S. (110) 229)
- Rechargeable lithium battery  
Manganese dioxide; Birnessite; Drying condition; Cyclability; Substitution (Tsuda, M. (110) 52)
- Reformate  
PEM fuel cell (PEMFC); CO<sub>2</sub>-tolerance; Reverse water-gas shift (de Bruijn, F.A. (110) 117)
- Reverse water-gas shift  
PEM fuel cell (PEMFC); Reformate; CO<sub>2</sub>-tolerance (de Bruijn, F.A. (110) 117)
- Ruthenium oxide  
Hybrid capacitors; Tantalum oxide (Chang, T.Y. (110) 138)
- Secondary batteries  
Aluminum; Anode; Primary batteries; Molten salt (Li, Q. (110) 1)
- Selected area electron diffraction  
Hydrous ruthenium oxide; Transmission electron microscope (Zheng, J.P. (110) 86)
- Self-doped polyaniline  
Rechargeable battery; Polyaniline; *m*-Aminobenzoic acid (Rahmanifar, M.S. (110) 229)
- Silica  
Proton-conducting; Membrane; AC impedance; AMPS; Nafion® (Walker Jr., C.W. (110) 144)
- Single cell performance  
Low temperature SOFC; Composite electrolyte; Sol-gel coating; YSZ thin film (Kim, S.-G. (110) 222)
- Single cell performance  
MCFC; Cathode; Mechanical strength; Lithiated nickel oxide (Kim, S.-G. (110) 80)
- Soaking  
VRLA; Positive active material (Lawrence, E.L. (110) 125)
- SOFC modelling  
SOFC; Viscosity; Thermal conductivity; Diffusion; Gas mixture properties (Todd, B. (110) 186)
- SOFC  
SOFC modelling; Viscosity; Thermal conductivity; Diffusion; Gas mixture properties (Todd, B. (110) 186)
- SOFCs  
Composite particle; Spray pyrolysis; Ni-YSZ cermet anode; Long-term stability (Fukui, T. (110) 91)
- Sol-gel coating  
Low temperature SOFC; Composite electrolyte; YSZ thin film; Single cell performance (Kim, S.-G. (110) 222)
- Solid oxide fuel cell  
Electrochemical impedance; LSM cathodes; Oxygen reduction (Jiang, S.P. (110) 201)
- Solid solutions  
Layered Li-Ni-Mn-O compounds; Phase transitions (Zhang, L. (110) 57)
- Solvation of lithium ion  
Electrospray ionization-mass spectroscopy; Organic electrolyte solutions; Dimethoxyethane; Propylene carbonate (Fukushima, T. (110) 34)
- Spinel  
Li-ion battery; Capacity fading; Oxygen deficiency; Phase transition (Wang, X. (110) 19)
- Spray pyrolysis  
Composite particle; SOFCs; Ni-YSZ cermet anode; Long-term stability (Fukui, T. (110) 91)
- State of charge sensors  
Lead-acid batteries; Coulometric gauge (Blood, P.J. (110) 96)
- Substitution  
Manganese dioxide; Birnessite; Rechargeable lithium battery; Drying condition; Cyclability (Tsuda, M. (110) 52)
- Supercapacitors  
Ragone-plot; Batteries; Economic optimization; Net present value (Christen, T. (110) 107)
- Surface film  
Aluminium oxidation; Lithium deposition; Cyclic voltammetry; Alternating current (ac) impedance (Suresh, P. (110) 11)
- Tantalum oxide  
Hybrid capacitors; Ruthenium oxide (Chang, T.Y. (110) 138)
- Technical intelligence  
Electrochemical power; Database tomography; Bibliometric analysis; Text mining; Information retrieval (Kostoff, R.N. (110) 163)
- Temperature difference  
Thermocell; Br<sub>2</sub>/Br<sup>-</sup>-redox reaction; Thermoelectric power; Open-circuit voltage; Hysteresis (Shindo, K. (110) 46)

## Text mining

Electrochemical power; Database tomography; Bibliometric analysis;  
Information retrieval; Technical intelligence (Kostoff, R.N. (110)  
163)

## The structural parameters

Design of current collectors; Lead-acid batteries (Kamenev, Yu. (110)  
133)

## Thermal conductivity

SOFC; SOFC modelling; Viscosity; Diffusion; Gas mixture properties  
(Todd, B. (110) 186)

## Thermal safety

All solid polymer electrolyte aluminum corrosion; Four volts class;  
Capacity fade (Li, Q. (110) 38)

## Thermocell

Temperature difference; Br<sub>2</sub>/Br<sup>-</sup>-redox reaction; Thermoelectric  
power; Open-circuit voltage; Hysteresis (Shindo, K. (110) 46)

## Thermoelectric power

Temperature difference; Thermocell; Br<sub>2</sub>/Br<sup>-</sup>-redox reaction; Open-  
circuit voltage; Hysteresis (Shindo, K. (110) 46)

## Thermoplastic polyurethane

Lithium battery; Polyacrylonitrile; Composite polymer electrolyte  
(Kuo, H.-H. (110) 27)

## Transmission electron microscope

Hydrous ruthenium oxide; Selected area electron diffraction (Zheng, J.P.  
(110) 86)

## UV-cured polymer blend

Lithium batteries; Gel polymer electrolytes; Polyvinylidene fluoride;  
Polyethyleneglycol diacrylate; Miscibility (Song, M.-K. (110)  
209)

## Viscosity

SOFC; SOFC modelling; Thermal conductivity; Diffusion; Gas mixture  
properties (Todd, B. (110) 186)

## VRLA

Soaking; Positive active material (Lawrence, E.L. (110) 125)

## X-ray absorption

Cycle life; Discharge capacity; Nickel-metal hydride battery  
(Ambrosio, R.C. (110) 73)

## YSZ thin film

Low temperature SOFC; Composite electrolyte; Sol-gel coating; Single  
cell performance (Kim, S.-G. (110) 222)