

High open-circuit voltage single-layer polybithiophene-based photovoltaic devices

Elinton L. Leguenza · Rodolfo L. Patyk ·
Regina M. Q. Mello · Liliana Micaroni ·
Marlus Koehler · Ivo A. Hümmelgen

Received: 24 August 2007 / Accepted: 30 August 2007 / Published online: 19 September 2007
© Springer-Verlag 2007

J Solid State Electrochem (2007) 11:577–580

The correct potential in the 11th line of the Experimental section on page 578 is -200 mV vs Ag pseudoreference electrode and the correct unit for the current presented in Fig. 3 on page 579 is μA . We apologize any inconvenience this mistake may have caused.

The online version of the original article can be found at <http://dx.doi.org/10.1007/s10008-006-0200-5>.

E. L. Leguenza · R. L. Patyk · M. Koehler · I. A. Hümmelgen (✉)
Departamento de Física, Universidade Federal do Paraná,
Caixa Postal 19044, 81531 - 990 Curitiba PR, Brazil
e-mail: iah@fisica.ufpr.br

E. L. Leguenza
Núcleo de Ciências Exatas e Tecnologia,
Centro Universitário Positivo,
81280-330 Curitiba PR, Brazil

R. M. Q. Mello · L. Micaroni
Departamento de Química, Universidade Federal do Paraná,
Caixa Postal 19081, 81531-990 Curitiba PR, Brazil