



ELSEVIER

Available online at www.sciencedirect.com

SCIENCE @ DIRECT®

Journal of Sound and Vibration 280 (2005) 1157

JOURNAL OF
SOUND AND
VIBRATION

www.elsevier.com/locate/jsvi

Discussion

Author's reply[☆]

F. Bos^{a,*}, S. Bos Casagrande^b

^a*Laboratoire de Réologie du Bois de Bordeaux, Domaine de l'hermitage, 69 route d'Arcachon,
33612 Cestas Gazinet, France*

^b*XYLOMECA, Le Fouquet, 33490 Sainte-Foy La Longue, France*

Received 16 January 2004; accepted 28 January 2004

Available online 8 October 2004

We thank R.E. Rossi, D.V. Bambill and P.A.A. Laura for their interesting and enlightening comments concerning the approximations made in this paper about, in particular, the determination of the position of the “nodal points” for the two vibrating modes (2,0) and (0,2). In an industrial context, it is impossible to determine exactly the distances from the nodal points to the edges of the panel which depend, as it is clearly explained in the answer to the authors, on many parameters variable from one panel to another and sometimes inaccessible (Poisson's ratio for example). However, we think that, in spite of these approximations, the bending stiffness and strength estimated by the Vibrapann apparatus keep relevant within an industrial quality control procedure.

[☆] Reply to doi: 10.1016/j.jsv.2004.01.045

*Corresponding author.

E-mail address: bos@irbb.u-bordeaux.fr (F. Bos).