

the *d-cis*-carveol derivative, m.p. 92.5°, [α]_D 44.2° (CHCl₃, *c* 2).

In a similar manner the *p*-nitrobenzoate was prepared giving a mixture melting mainly at 27–28° and completely melted at 70–72°. Recrystallization gave a mixture of transparent plates, m.p. 26–28°, and a powder, m.p. 75–78°, after mechanical separation. This compares with the report¹ of the *d-cis* derivative m.p. 26.5–28° and the *d-trans* derivative, m.p. 77°.

Boiling 10.78 g. of the carveol mixture with 10 ml. of acetic anhydride and 1.0 g. of anhydrous sodium acetate for two hours gave on distillation 9.56 g. of carveol acetate, b.p. 110–113° (12 mm.), n_D^{20} 1.4760, $\alpha_D -33.2^\circ$.

Oxidation of 6.0 g. of the carveol mixture in 12.5 ml. of glacial acetic acid with 5.4 g. of chromic anhydride in 12.5 ml. of acetic anhydride at 13–17° gave carvone, $\alpha_D -54.6^\circ$, n_D^{20} 1.4959. This indicates that little isomerization of the ring structure occurred during the reduction and subsequent oxidation.^{4,5}

(4) This reaction was carried out by Mr. V. J. Baarman.

(5) Unless otherwise indicated all notations taken on homogeneous materials.

RESEARCH LABORATORY
A. M. TODD COMPANY
KALAMAZOO, MICHIGAN

The Vapor Pressures of Some Substituted Benzotrifluorides¹

BY SAMUEL KARDON AND JOHN H. SAYLOR

RECEIVED JANUARY 16, 1953

The measurements reported in this note resulted from a continuation of a general program in this Laboratory concerning the solubility and other physical properties of organic fluorine compounds.

740 mm. The data were fitted by the method of least squares to the equation

$$\log p = \frac{-B}{t + C} + A$$

where *p* is the pressure in mm. and *t* is the temperature in degrees centigrade.

The standard deviation between the observed pressures and those calculated from the equation ranged from 0.09 to 0.11 mm.

Table I gives the boiling points calculated from the vapor pressure equation, the freezing points, the freezing point depressions, the refractive indices (η), the dielectric constants (ϵ) and the values of the three constants in the above equation. The value given for the dielectric constant of *m*-nitrobenzotrifluoride is not considered as reliable as those for the other compounds.

DEPARTMENT OF CHEMISTRY
DUKE UNIVERSITY
DURHAM, NORTH CAROLINA

Polyalkylene Sulfides. XII.¹ Termination by Disulfide Formation²

BY C. S. MARVEL, C. W. HINMAN AND H. K. INSKIP

RECEIVED DECEMBER 18, 1952

It has been observed³ that 96–98% of the thiol groups have reacted in 8 to 16 minutes when hexamethylenedithiol and biallyl polymerize in a persulfate initiated reaction at 30°. The complete

TABLE I

Benzotrifluoride	B.p., °C.		F.p., °C.		η_D^{20}	η_D^{25}	ϵ^{20}	A	B	C
	Calcd.	Obsd.	Dep.							
<i>m</i> -Nitro	202.75	-1.32	0.06	1.4719	1.4675	17	7.18025	1710.60	195.12	
<i>m</i> -Amino	191.13	5.65	.01	1.4788	1.4750		7.17030	1650.21	193.58	
3-Nitro-4-chloro	222.58	-2.54	.04	1.4895	1.4853	12.8	7.15778	1738.71	183.95	
2-Chloro-5-nitro	231.88	21.7	.5		1.5043	9.8	7.15409	1779.91	184.64	

Experimental

Materials.—The compounds were supplied by the Hooker Electrochemical Company and were further purified by distillation at reduced pressure (controlled to ± 0.1 mm.) in a silvered vacuum-jacketed glass column packed with 1/8" glass helices. The fractions used were characterized by measuring refractive indices, dielectric constants and freezing points. The dielectric constants were measured by the heterodyne beat method. The apparatus was calibrated with benzene and chlorobenzene and has been found to give good results in measuring dielectric constants of highly purified materials with values up to approximately 15. The freezing points were determined as previously described.²

Vapor Pressures.—The apparatus which was previously used by Potter² was employed. It was a modification of the boiling point apparatus described by Rossini and co-workers.³

Results

Fifteen to twenty individual measurements were made on each compound from approximately 5 to

(1) Part of the work reported was carried out under Contract N6ori-107, T. O. II with the Office of Naval Research. Taken from the thesis submitted by Samuel Kardon to the Graduate School of Duke University in partial fulfillment of the requirements for the degree of Master of Arts, June 1952.

(2) J. C. Potter and J. H. Saylor, *THIS JOURNAL*, **73**, 90 (1951).

(3) C. B. Willingham, W. J. Taylor, J. M. Pignocco and F. D. Rossini, *J. Research Natl. Bur. Standards*, **55**, 219 (1945).

disappearance of thiol groups occurs only after many hours. The polymer formed in the first few minutes has an inherent viscosity of 0.4 to 0.7 and that obtained after a much longer reaction time has an inherent viscosity of about 1.0. Other dithiols and diolefins show a similar behavior. This has suggested to us that the slow reaction may be an oxidation of terminal thiol groups in the polymers first formed, to yield a disulfide which thus terminates further polymerization.

Evidence of the presence of disulfide links in the polymers of higher inherent viscosity produced in the above reaction has now been obtained. If one of the polymers produced in the long reaction time is reduced by amalgamated zinc and hydrochloric acid in hot xylene solution, it is cleaved to a polymer of lower inherent viscosity. This reduction product can be reoxidized with iodine to produce a poly-

(1) For the eleventh communication on this topic, see C. S. Marvel and H. N. Cripps, *J. Polymer Sci.*, **9**, 53 (1952).

(2) The work discussed herein was performed as a part of the research project sponsored by the Reconstruction Finance Corporation, Office of Synthetic Rubber, in connection with the Government Synthetic Rubber Program.

(3) C. S. Marvel and A. H. Markhart, Jr., *THIS JOURNAL*, **73**, 1064 (1951).