sorption and neotetrazolium reduction. That this mineralocorticoid possesses ultraviolet absorption and the one described by Tait, *et al.*,² did not is the only known differentiating feature between these strikingly similar compounds. A comparison of the two mineralocorticoids is shown in Table II.

A detailed description of this work, including the chromatographic characterization of the mineralocorticoid in numerous solvent systems developed in our laboratory and infrared data on the mineralocorticoid and its polyacetate, will be published soon.

The authors wish to thank Mr. Norbert E. Mayer for technical assistance.

THE RESEARCH LABORATORIES	R. E. KNAUFF
THE UPJOHN COMPANY	E. D. NIELSON
KALAMAZOO, MICHIGAN	W. J. HAINES
RECEIVED AUGUST 20, 1953	

ELECTRODES WITH CONVECTION CONTROLLED LIMITING CURRENTS ("CONVECTION ELEC-TRODES")

Sir:

Experimental conditions were found under which convection controlled limiting currents at the rotated platinum wire electrode are observed. In addition, a "convection" mercury microelectrode has been developed. In stirred solutions the thickness of the boundary layer at an electrode decreases with increasing rates of stirring and eventually reaches a limiting value of "molecular"dimensions. Under these conditions limiting currents no longer depend on the diffusion coefficient of the electroactive species but on the rate of convective transport to the electrode surface. Assuming that τ microliter of solution is transported per second to a unit area of the electrode, the convection controlled limiting current (corrected for residual currents and expressed in microamperes) is postulated to be:

$$i_{\rm conv.} = n Fa \tau C = knC \tag{1}$$

where nF represents the number of coulombs per mole involved in the electrode reaction, C is the bulk concentration of the electroactive species in moles per liter and A the area of the electrode expressed in sq. cm. $-\tau$ is called the "convection coefficient," expressed in cm. \times sec.⁻¹, and depends on the prevailing specific hydrodynamic conditions.

A platinum wire electrode, 0.5 mm. in diameter and 5 mm. in length, rotated at 600 to 900 r.p.m., yielded convection controlled limiting currents when the solution was stirred with the aid of a rectangular propeller with four blades ($13 \times 5 \times 1$ mm. each), mounted concentrically 2 cm. above the electrode and rotated at the same rate as the latter. Identical convection controlled limiting currents were obtained in equinormal solutions of iodide, triiodide and an ethylenediamine tetraacetate complex of thallium(III), the diffusion coefficient of the latter being about one-twentieth as large as that of iodide.

Well-defined limiting currents were obtained with a stationary mercury microelectrode which is being further studied and which consisted of 0.005 ml. of mercury in a 2-mm. bore capillary cuvette attached to the bottom of a 250-ml. electrolysis cell, the solution being stirred at 900–1200 r.p.m. In 0.1 M potassium chloride as supporting electrolyte the convection current of thallium(I) was proportional to concentration in the range between 5×10^{-6} and $5 \times 10^{-3} M$ and about twenty times as large as the corresponding diffusion current at the dropping mercury electrode. The half wave potential was independent of concentration at a given rate of change of applied voltage.

The value of the convection coefficient, τ , was estimated from convection currents at 900 r.p.m. for the rotated platinum wire electrode and the stationary mercury microelectrode as 19 and 18 cm. \times sec.⁻¹, respectively.

Most prominent advantages of convection electrodes are: (1) stationary electrodes can be used. (2) The limiting current is independent of the diffusion coefficient of the electroactive species. (3) The use of a synchronous motor is not necessary.

Acknowledgment is made to the Graduate School of the University of Minnesota for a grant in partial support of this work.

School of Chemistry University of Minnesota Minneapolis 14, Minn.		I. M. Kolthoff Joseph Jordan
	-	

RECEIVED AUGUST 27, 1953

PROPERTIES OF A SODIUM-RETAINING PRINCIPLE FROM BEEF ADRENAL EXTRACT

Sir:

Current interest in the amorphous fraction of adrenal extracts¹ makes it desirable to present results of a study of this fraction since further work must await processing of more material.

The extract (furnished by the Upjohn Co.) of 1200 lb. of beef glands was chromatographed on a column of silica gel with the propylene glycol-toluene system. The active fractions, assayed in rats using a method similar to that of Simpson and Tait² were combined and rechromatographed. The active fraction was acetylated and chromatographed successively in the formamide-benzene and formamide-benzene-cyclohexane systems. It was then chromatographed three times in the latter system on paper.

The acetate isolated weighed 13.2 mg. and assay for α -ketol with blue tetrazolium indicated 13.2 mg. in terms of cortisone. It could not be crystallized. Its biological activity in dog and rat assays was similar in type and approximately equal to that of desoxycorticosterone acetate. Absorption maxima at 239 m μ ($E_{1 \text{ cm.}}^{1\%}$ = 370, methanol) and at 1618 and 1671 cm.⁻¹ (chloroform) indicated the presence of a Δ^4 -3-keto group assuming the substance is a steroid. An acetylated α -ketol side chain was evidenced by absorption maxima at 1736 and 1750 cm.⁻¹ (chloroform). The absence of absorption maxima near 1710 (CS₂) and 3600 cm.⁻¹ denoted absence of an 11-keto and of unacetylated hydroxyl groups. A negative Porter-Silber³ reaction indicated absence of a 17-hydroxyl group, of a 16-17 double bond, and probably of a 16-acetoxy group.

⁽¹⁾ H. M. Grundy, S. A. Simpson, J. F. Tait and M. Woodford, Acta Endocrinologia, 11, 199 (1952).

S. A. Simpson and J. F. Tait, Endocrinology, **50**, 150 (1952).
C. C. Porter and R. H. Silber, J. Biol. Chem., **185**, 201 (1950).