

Published on Web 08/08/2006

Doubly Ortho-Linked Quinoxaline/Diphenylfluorene Hybrids as Bipolar, Fluorescent Chameleons for Optoelectronic Applications

Chien-Tien Chen,*,† Yi Wei,† Jin-Sheng Lin,† Murthy V. R. K. Moturu,† Wei-San Chao,† Yu-Tai Tao,‡ and Chin-Hsiung Chien‡

Department of Chemistry, National Taiwan Normal University, and Institute of Chemistry, Academia Sinica, Taipei, Taiwan

Received April 17, 2006; E-mail: chefv043@ntnu.edu.tw

There has been great interest in the development of new electroluminescent molecular materials for organic light emitting diodes (OLEDs) in flat-panel display. 1a.b In the aspect of advanced designs, integrating electron-transporting (ET) and hole-transporting (HT) segments into molecular materials may effectively improve the OLED device performance because of more balanced charge transports of both carriers. 1c Several linearly D-A conjugated templates based on this concept²⁻⁵ and attempts on single-layered devices⁶ have thus been examined with significant success. Recently, we unraveled the first attempt of using doubly ortholinked quinoxaline/triarylamine 1:1 hybrid as a bifunctional, dipolar electroluminescent clip for bluish green and orange OLED applications.⁷ As part of our ongoing program on the use of dibenzosuberene (DBE)-based triarylcarbenium ions and over-crowded triarylethenes in catalysis⁸ and LC optical switches,⁹ we thought to merge the DBE template with fused quinoxaline backbones of varying electronic attributes for optoelectronic applications. In addition, to improve the rigidity, redox stability, and morphology of the DBE template, spiro-fluorene¹⁰ is incorporated at the C5position of the DBE template. Conceptually, the new molecular design connects the individual ortho-position of two phenyl rings in a HT-type 9,9-diphenylfluorene framework to the C2-C3 edge of a functionalized ET-type quinoxaline. Therefore, the resultant 1:1 hybrid is potentially bipolar and may act as a central fluorescent chameleon unit with tunable emission colors by judicious choices of the C5- and C8-appendages. Herein, we report the preliminary results toward this end with good to excellent optoelectronic performance in OLED applications (Scheme 1).

The starting **2**, derived from DBE-**1**, was oxidized by benzene-seleninic anhydride (BSA) to give diketone-**3** in 87% yield. Condensation of **3** and 3,6-dibromo-1,2-diaminobenzene with catalytic *p*-TSA in refluxed CHCl₃ provided quinoxaline-fused DBE-**4** in 90% yield. Attachments of respective aryl and arylamino components to both the C5 and C8 positions of the quinoxaline backbone in **4** were achieved by Suzuki and Hartwig coupling reactions, leading to **5a**–**d**, respectively in 70–95% yields.

The structural features for **5a-d** were resolved by NMR spectroscopy and ultimately proven by X-ray crystallographic analyses. For the aryl-conjugated systems **5a-c**, they share common structural attributes. They exist as a dimmer in unit cell. The flanking aryl appendages at both the C5 and C8 positions in the quinoxaline backbone are turned by 45–56° to avoid epi-interaction with the quinoxaline nitrogen lone pairs and steric interaction with the spirofluorene unit in another molecule (Figure 1a). The spirofluorene prevents facile conformational flipping of the central seven-memberd ring in the DBE core. Conversely, only one flanking nitrogen lone pair of the methylphenylamino groups in **5d** is

‡ Academia Sinica.




Figure 1. ORTEP diagram for X-ray crystal structure (ellipsoids are shown at 20% probability level) of (a) **5b** (left) and (b) **5d** (right).

Scheme 1. Assembly Concept of the Quinoxaline/Diphenylfluorene Optoelectronic System




Table 1. Optical, Morphological, and CV Data for 5a-d and 6

compd	absorbance $\lambda_{\max}\left(\epsilon ight)^{a}$	$Em\lambda_{max}{}^{a,b}$ nm	$\Phi_{f}{}^a$ %	T _g /T _d °C	$E_{\rm red}/E_{ m ox}{}^a$ V
5a	276 (63.8), 367 (17.2)	482 (74)	41	181/395	-2.07/
5b	288 (60.6), 374 (15.7)	521 (89)	78	160/372	-2.07/
5c	323 (17.4), 441 (3.6)	599 (95)	34	186/412	-2.05/+0.46
5d	332 (23.0), 482 (2.7)	650 (110)	42	153/333	-2.11/+0.08, +0.27
6	284 (58.9), 365 (17.6)	497 (97)	57	74 /321	-2.07/

 $[^]a$ λ_{max} , in nm; $(\epsilon) \times 10^{-3}$; measured in CH₂Cl₂. b The data in parentheses correspond to full-width at half-maximum (fwhm).

somewhat coplanar (i.e., conjugated) with the quinoxaline backbone (Figure 1b). Nevertheless, resonance conjugations between the pendant aryl (or phenylamino) group and the quinoxaline backbone are prominent in solution, exerting progressive, bathochromic shifts in their UV and photoluminescence spectra, Table 1.

Upon UV excitation, these materials show different emission colors in solution varying from bluish, to green, to orange, to red. The full-width at half-maximum (fwhm) for each individual emission also increases progressively from 74, to 89, to 95, to 110 nm (Table 1), with quantum yields ranging from 34 to 78%. The increased molecular size and rigidity arising from the spiral framework of these materials are manifested in their increased thermal stability (T_d , 333–412 °C) and glassy transition temperature

[†] National Taiwan Normal University.

Table 2. Electroluminescence Data for 5a-d and 6

conf ^a	Em^b λ_max	V _{on} c V	$\eta_{ext}{}^c$	$\eta_{ extsf{c}}^{ extsf{c}}/\eta_{ extsf{p}}^{ extsf{c}}$	L ^c cd/m²
5a/A	490 (70)	4.5 (4.9)	0.45	0.82/0.52	5995 (205)
5b/A	520 (82)	2.5 (4.0)	1.92	6.35/5.02	35372 (1268)
5b/B	524 (88)	4.7 (7.4)	1.06	2.90/1.19	11733 (414)
6/A	502 (90)	2.7 (4.0)	1.75	5.07/3.95	20640 (1055)
Alq ₃ /A	516(104)	3.9 (5.6)	1.11	3.29/1.84	28911 (638)
5c/A	576 (95)	2.8 (3.9)	0.98	2.54/2.05	23716 (524)
5c/B	580 (97)	3.9 (6.5)	2.90	7.75/3.73	20683 (1542)
5c/C	578 (96)	4.4 (6.3)	4.92	13.10/6.54	69700 (2503)
5d/A	642(102)	3.7 (5.7)	0.81	0.85/0.47	3558 (167)
5d/B	644(101)	4.1 (5.8)	3.17	2.31/1.21	11484 (1102)

^a Configuration (conf) **A:** ITO/NPB (40 nm)/**5a-d** (40 nm)/LiF (1 nm)/Al; **B:** ITO/**5b-d** (40 nm)/BCP (10 nm)/Alq₃ (40 nm)/LiF (1 nm)/Al; **C:** ITO/NPB (40 nm)/**5c** (40 nm)/BCP (10 nm)/Alq₃ (40 nm)/LiF (1 nm)/Al. ^b The data in parentheses correspond to full-width a half-maximum (fwhm). ^c The data in parentheses for $V_{\rm on}$ and L and the data for $\eta_{\rm ext}$ (%), $\eta_{\rm c}$ (cd/A), and $\eta_{\rm p}$ (lm/W) were measured at 20 mA/cm².

($T_{\rm g}$, 153–186 °C). For example, the $T_{\rm d}$ and $T_{\rm g}$ (372 °C and 160 °C) for **5b** (C₄₇H₃₂N₂O₂, fw: 656.8) are 51 and 86 °C higher than those (321 °C and 74 °C) for the corresponding open-form system-**6** [i.e., 5,8-bis-(4-methoxyphenyl)-2,3-diphenyl-quinoxaline (C₃₄H₂₆-N₂O₂, fw: 494.6)].

The redox behaviors of $\mathbf{5a-d}$ were evaluated by cyclic voltammetry (CV) experiments at ambient temperature. They exhibit similar reduction potentials with reversible redox couples at -2.08 ± 0.03 V. No discernible oxidations were found in less than +1.5 V for $\mathbf{5a}$ and $\mathbf{5b}$. Nevertheless, reversible two-electron oxidation redox couples can be identified for triarylamino-containing $\mathbf{5c}$ and $\mathbf{5d}$. They show oxidation potential at +0.46 V for $\mathbf{5c}$ and a pair of +0.08 and +0.27 eV for $\mathbf{5d}$ owing to sequential oxidations of the two amino appendages. When compared with $\mathbf{Ar_3N/quinoxaline^{4a,b}}$ and spiro-fluorene-based dipolar hybrids, 5d the current new designs show slightly lower redox potentials, which may facilitate better charge injection from both carriers.

Their optoelectronic performances are evaluated as respective ET-type and HT-type emitting layers by fabricating bilayer or trilayer OLED devices with two different configurations. 1,4-Bis-(1-naphthylphenylamino)-biphenyl (α-NPB¹¹) and Alq₃ were employed (40 nm thickness each) as HT and ET layers, respectively. In the combination of respective 5a-d with Alq₃, 2,9-dimethyl-4,7-diphenyl-1,10-phenanthroline (BCP) was utilized as a hole blocking layer (10 nm) to completely suppress emission leakage from Alq3. When 5a, 5b, 5c, and 5d were examined as ET and emitting materials in device configuration A (Table 2), the resultant OLED devices exhibit maximum EL brightness (L_{max}) of 5995, 35372, 23716, and 3558 cd/m², respectively. Their operational brightness (L_{20}) at 20 mA/cm² can reach 205, 1268, 524, and 167 cd/m², respectively, with individual external quantum efficiency (η_{ext}) of 0.5, 1.9, 1.0, and 0.8%. Their luminance and power efficiencies (η_c/η_p) are 0.8/0.5, 6.4/5.0, 2.5/2.1, and 0.9/0.5 cd A⁻¹/ lm W^{−1}, respectively. Notably, **5b** acted more as a superior ET and emitting dipolar material than Alq3 in terms of operational voltage (4.0 vs 5.6 V), emission peak width (fwhm: 82 vs 104 nm), L_{20} (12688 vs 638 cd/m²), η_{ext} (1.9 vs 1.1%), and working efficiencies (6.4/5.0 vs 3.3/1.8 cd A^{-1}/lm W^{-1}) when both devices were fabricated simultaneously under the same conditions.

Conversely, when $\mathbf{5a-d}$ were examined as HT and emitting materials in device configuration B (Table 2), all the devices except that from $\mathbf{5a}$ showed promising results. The resultant OLED devices from $\mathbf{5b}$, $\mathbf{5c}$, and $\mathbf{5d}$ exhibit a maximum EL brightness (L_{max}) of 11773, 20683, and 11484 cd/m², respectively. Their operational brightness (L_{20}) at 20 mA/cm² can reach 414, 1542, and 1102 cd/m², respectively, with individual external quantum efficiency (η_{ext})

of 1.1, 2.9, and 3.2%. Their respective luminance and power efficiencies (η_c/η_p) are 2.9/1.2, 7.8/3.7, and 2.3/1.2 cd A⁻¹/lm W⁻¹.

Overall, the optoelectronic performance is 2 times better when 5b is utilized as an ET and emitting layer. On the contrary, the optoelectronic performances are 2-3 times better when 5c or 5d is employed as HT and emitting layers. Nevertheless, both the 5b and 5c can function as bipolar electroluminescent materials with more balanced charge transporting properties in view of the satisfactory OLED performances in complementary device configurations A and B. To further optimize the device efficiency, we have also fabricated a four-layered device with a configuration of α-NPB/5c (40 nm)/BCP/Alq₃ (configuration C). For this combination of using 5c as the sole emitting layer, the OLED device exhibits $L_{\rm max}$ and L_{20} of 69700 and 2503 cd/m² with $\eta_{\rm ext}$ of 4.9%. The luminance and power efficiencies (η_c/η_p) are 13.1/6.5 cd A⁻¹/lm W^{-1} . To our knowledge, green emitting **5b**, yellow-emitting **5c**, and red emitting 5d represent one of the best bipolar fluorescent materials to date.12

Acknowledgment. We thank the National Science Council of Taiwan for generous financial support of this research.

Supporting Information Available: Experimental, device, and spectra details of **2**–**6** and cif files for **5b** and **5d**. This material is available free of charge via the Internet at http://pubs.acs.org.

References

- (a) Hung, L. S.; Chen, C. H. Mater. Sci. Eng. Report 2002, 39, 143. (b) Burroughes, J. H.; Bradley, D. D. C.; Brown, A. R.; Marks, R. N.; Mackay, K.; Friend, R. H.; Burns, P. L.; Holmes, A. B. Nature 1990, 347, 539. (c) Mullen, K.; Scherf, U. Organic Light-Emitting Devices. Synthesis, Properties and Applications; Wiley: Weinheim, Germany, 2006.
- (2) (a) Mochizuki, H.; Hasui, T.; Kawamoto, M.; Shiono, T.; Ikeda, T.;
 Adachi, C.; Taniguchi, Y.; Shirota, Y. Chem. Commun. 2000, 1923. (b)
 Tamoto, N.; Adachi, C.; Nagai, K. Chem. Mater. 1997, 9, 1077. (c) Peng,
 Z. H.; Bao, Z. N.; Galvin, M. E. Chem. Mater. 1998, 10, 2086.
- (3) (a) Liu, Y.; Ma, H.; Jen, A. K.-Y. Chem. Commun. 1998, 2747. (b) Wang, Y. Z.; Epstein, A. J. Acc. Chem. Res. 1999, 32, 217. (c) Jenekhe, S. A.; Lu, L. D.; Alam, M. M. Macromolecules 2001, 34, 7315.
- (4) (a) Justin Thomas, K. R.; Lin, J. T.; Tao, Y.-T.; Chuen, C.-H. Chem. Mater. 2002, 14, 3852. (b) Kido, J.; Harada, G.; Nagai, K. Chem. Lett. 1996, 161. (c) Song, S.-Y.; Jang, M. S.; Shim, H.-K.; Hwang, D.-H.; Zyung, T. Macromolecules 1999, 32, 1482. (d) For quinoxaline-thiophene alternating polymers, see the following: Nurulla, I.; Yamaguchi, I.; Yamamoto, T. Polym. Bull. 2000, 44, 231. (e) Yamamoto, T.; Zhou, Z.-H.; Kanbara, T.; Shimura, M.; Kizu, K.; Maruyama, T.; Nakamura, Y.; Fukuda, T.; Lee, B.-L.; Ooba, N.; Tomaru, S.; Kurihara, T.; Kaino, T.; Kubota, K.; Sasaki, S. J. Am. Chem. Soc. 1996, 118, 10389.
- (5) (a) Geng, Y.; Katsis, D.; Culligan, S. W.; Ou, J. J.; Chen, S. H.; Rothberg, L. J. Chem. Mater. 2002, 14, 463. (b) Wong, K.-T.; Chien, Y.-Y.; Chen, R.-T.; Wang, C.-F.; Lin, Y.-T.; Chiang, H.-H.; Hsieh, P.-Y.; Wu, C.-C.; Chou, C. H.; Su, Y. O.; Lee, G.-H.; Peng, S.-M. J. Am. Chem. Soc. 2002, 124, 11576. (c) Wong, K.-T.; Hwu, T.-Y.; Balaiah, A.; Chao, T.-C.; Fang, F.-C.; Lee, C.-T.; Peng, Y.-C. Org. Lett. 2006, 8, 1415. (d) Fungo, F.; Wong, K.-T.; Ku, S.-Y.; Hung, Y.-Y.; Bard, A. J. J. Phys. Chem. B. 2005, 109, 3984.
- (6) (a) Zhu, W.; Hu, M.; Yao, R.; Tian, H. J. Photochem. Photobiol., A 2003, 154, 109. (b) Freudenmann, R.; Behnisch, B.; Hanack, M. J. Mater. Chem. 2001, 11, 1618. (c) Hassheider, T.; Benning, S. A.; Kitzerow, M. F.; Bock, A. H. Angew. Chem., Int. Ed. 2001, 40, 2060.
- (7) Chen, C.-T.; Lin, J.-S.; Moturu, M. V. R. K.; Lin, Y.-W.; Yi, W.; Tao, Y.-T.; Chien, C.-H. Chem. Commun. 2005, 3980.
- (8) Chen, C.-T.; Chao, S.-D.; Yen, K.-C.; Chen, C.-H.; Chou, I.-C.; Hon, S.-W. J. Am. Chem. Soc. 1997, 119, 11341.
- (9) Chen, C.-T.; Chou, Y.-C. J. Am. Chem. Soc. 2000, 122, 7662
- (10) (a) Chien, Y.-Y.; Wong, K.-T.; Chou, P.-T.; Cheng, Y.-M. Chem. Commun. 2002, 2874. (b) Wong, K.-T.; Chen, R.-T.; Fang, F.-C.; Wu, C.-C.; Lin, Y.-T. Org. Lett. 2005, 7, 1979.
- (11) (a) Koene, B. E.; Loy, D. E.; Thompson, M. E. *Chem. Mater.* **1998**, *10*, 2235. (b) O'Brien, D. F.; Burrows, P. E.; Forrest, S. R.; Koene, B. E.; Loy, D. E.; Thompson, M. E. *Adv. Mater.* **1998**, *10*, 1108.
- (12) (a) Huang, T.-H.; Lin, J.-T.; Chen, L.-Y.; Lin, Y.-T.; Wu, C.-C. Adv. Mater. 2006, 18, 602. (b) Justin Thomas, K. R.; Lin, J. T.; Tao, Y.-T.; Chuen, C.-H. Chem. Mater. 2002, 14, 2796. (b) Chen, C.-T. Chem. Mater. 2004, 16, 4389.

JA062660V