


Communication

Potentiometric Detection of DNA Hybridization

Apon Numnuam, Karin Y. Chumbimuni-Torres, Yun Xiang, Ralph Bash, Panote Thavarungkul, Proespichaya Kanatharana, Ern Pretsch, Joseph Wang, and Eric Bakker

J. Am. Chem. Soc., 2008, 130 (2), 410-411 • DOI: 10.1021/ja0775467

Downloaded from http://pubs.acs.org on February 8, 2009



More About This Article

Additional resources and features associated with this article are available within the HTML version:

- Supporting Information
- Links to the 1 articles that cite this article, as of the time of this article download
- Access to high resolution figures
- Links to articles and content related to this article
- Copyright permission to reproduce figures and/or text from this article

View the Full Text HTML





Published on Web 12/20/2007

Potentiometric Detection of DNA Hybridization

Apon Numnuam,^{†,‡,§} Karin Y. Chumbimuni-Torres,[†] Yun Xiang,[‡] Ralph Bash,[‡] Panote Thavarungkul,[§] Proespichaya Kanatharana,[§] Ernö Pretsch,^{*,II} Joseph Wang,^{*,‡} and Eric Bakker^{*,†,⊥}

Department of Chemistry, Purdue University, West Lafayette, Indiana 47907, The Biodesign Institute and Fulton School of Engineering, Arizona State University, Tempe, Arizona 85287, Faculty of Science, Prince of Songkla University, Hat Yai, Songkhla, 90112 Thailand, Institute of Biogeochemistry & Pollutant Dynamics ETH Zürich, CH-8092 Zürich, Switzerland, and Nanochemistry Research Institute, Department of Applied Chemistry, Curtin University of Technology, Perth, Western Australia 6845, Australia


Received October 1, 2007; E-mail: bakkere@purdue.edu; joseph.wang@asu.edu; pretsche@ethz.ch

Tremendous fundamental advances over the past decade have led to dramatic improvements in the performance of ion-selective electrodes (ISEs).¹ In particular, new insights into the principles dictating the limits of detection (LODs) of such potentiometric sensors have led to ISEs capable of convenient measurements down to the subnanomolar (parts per trillion) level.² Recent efforts have also demonstrated that potentiometric sensors with low LODs can be miniaturized to allow trace (subfemtomole) measurements in very small (microliter) sample volumes.³ Such major improvements in the performance of ISEs have facilitated new applications for which potentiometric sensors have not been used traditionally. For example, recent progress in our laboratories has led to highly sensitive immunoassays of proteins based on different ISE transducers.⁴

Here, we demonstrate for the first time the use of potentiometric microsensors for monitoring DNA hybridization. The detection of sequence-specific DNA is of central importance in the diagnosis and treatment of genetic diseases, detection of infectious agents, drug screening, and in forensic science.⁵ Various approaches have been successfully used to detect sequence-selective DNA hybridization, including optical,⁶ electrochemical,⁷ and piezoelectric methods.8 Electrochemical methods for detecting DNA hybridization have received considerable attention because of their high sensitivity, portability, low cost, minimal power requirement, and/or independence of sample turbidity or optical pathway.9 Various amperometric and voltammetric detection strategies¹⁰ have been used for transducing electronically DNA hybridization events based on oligonucleotide-bearing enzyme tags,¹¹ redox tracers,¹² or nanoparticle labels (i.e., gold nanoparticles, silver tags, and semiconductor nanocrystals).13

The new potentiometric nucleic acid measurements rely on a sandwich DNA hybridization for capturing a secondary oligonucleotide bearing CdS-nanocrystal tags. As illustrated in Scheme 1, the target DNA (60-mer) is hybridized (B) to the surface-anchored thiolated DNA probe (20-mer) on the gold substrate (A), followed by the capture of the secondary DNA probe (26-mer) conjugated to the CdS label (C). The nanocrystal is then dissolved in H_2O_2 to yield a dilute electrolyte background solution suitable for the potentiometric detection of the released Cd²⁺ with a polymer membrane Cd²⁺-selective microelectrode (D).

The assay was based on a recently developed miniaturized solidcontact Cd-ISE showing a lower LOD of 10^{-10} and 10^{-9} M Cd²⁺ in samples of 100 mL and 200 μ L (microwell plates), respectively.¹⁴ **Scheme 1.** Steps Involved in the Nanoparticle-Based Potentiometric Detection of DNA Hybridization^a



 a (A) Formation of a mixed monolayer of DNA probe on gold substrate; (B) hybridization with target DNA; (C) second hybridization with CdSlabeled probe; (D) dissolution of the CdS tag, followed by detection using a Cd²⁺-selective electrode.

It exhibits excellent selectivity for the relevant ions, with logarithmic selectivity coefficients of -7.04 (Ca²⁺), -3.88 (H⁺), and -4.59 (Na⁺). A miniaturized liquid-contact Ca-ISE was used as a pseudoreference electrode.¹⁴

The key parameters of the DNA sandwich hybridization assay were optimized as follows (cf. Supporting Information): The optimal concentration of the primary and secondary (CdS-nanocrystal-labeled) DNA probe was each 1 μ M, and the optimal time for both hybridization steps (cf. Scheme 1) was 60 min.

The high selectivity of the new DNA detection is illustrated in Figure 1 displaying the potentiometric responses of the Cd²⁺selective microelectrode to (a) control solution (zero target), (b) 500 nM of a noncomplementary DNA, (c) 500 µM of 2-base mismatch DNA, and to two significantly lower levels of the target DNA of (d) 10 nM and (e) 100 nM. The responses to the noncomplementary and the 2-base mismatch DNA are similar to those obtained with the control solution. Larger signals are observed for significantly lower (nanomolar) concentrations of the target DNA. Notice in particular the effective discrimination against the large excess (500 nM) of mismatch DNA (c) vs 10 nM target DNA (d). Such behavior confirms the good selectivity of the hybridization assay. Considering the logarithmic response of the Cd-ISE, the potential differences correspond to 2.8 nM for the 500 nM 2-base mismatch DNA (c) and 21 nM Cd2+ for the 10 nM target DNA (d), that is, to a \sim 8-fold lower amount of captured tags for a 50fold excess of the 2-base mismatch DNA.

The quantitative aspects are documented by a calibration experiment over a concentration range of 0.01-1000 nM target DNA. The resulting calibration plot in Figure 2 exhibits a well-defined concentration dependence suitable for DNA analysis, with

[†] Purdue University.

[‡] Arizona State University.

[§] Prince of Songkla University. ETH Zürich

[⊥] Curtin University of Technology.




Figure 1. Potentiometric responses of the Cd²⁺-selective electrode to: (a) control solution (10^{-4} M CaCl₂, zero target), (b) 500 nM noncomplementary DNA, (c) 500 nM 2-base mismatch DNA, (d) 10 nM target DNA, and (e) 100 nM target DNA (as complementary targets) after DNA hybridization. Potentiometric measurements were performed in 200 μ L of solutions with 10^{-4} M CaCl₂ as background (shown as baseline traces) with a Ca-ISE as pseudoreference electrode.




Figure 2. Calibration plot for the potentiometric monitoring of DNA with a sandwich array based on CdS quantum dot tags in $200-\mu$ L microwells (error bars: SD, N = 3). The dashed line corresponds to control signal (no target). Other conditions as in Figure 1.

a wide dynamic range of 0.01-300 nM target DNA. The EMF at the lowest measured concentration of 10 pM was 2.96 mV above that of the control, and the standard deviation of the noise of the control was 0.17 mV (N = 13, 1 min). Thus, the lower LOD is 10 pM or 37 pg (2 fmol) of the target DNA in the 200 μ L sample. These values compare favorably with those reported for other electrochemical DNA hybridization assays using similar nanoparticle labels.^{13a,b}

In conclusion, we have demonstrated for the first time the use of potentiometric transducers for detecting DNA hybridization. The use of Cd^{2+} -selective microelectrodes is particularly useful for a microplate operation in connection with CdS nanocrystal tags. The extremely high sensitivity and fmol detection limit of the microelectrode are coupled with a high selectivity of the bioassay, including effective discrimination against 2-base mismatched DNA. Note that the low detection limit was reached without a preconcentration step commonly used in other electrochemical transduction schemes. The new potentiometric detection route can be extended to a wide range of genetic tests in connection with different nanoparticle tags.

Acknowledgment. This work was supported by the grants from the National Institutes of Health (Grants R01 EB002189 and R01 1056047). A.N. acknowledges The Royal Golden Jubilee PhD Program (Thailand Research Fund). We thank Dr. D. Wegmann for careful reading of the manuscript.

Supporting Information Available: Optimization of the DNA sandwich hybridization assay, experimental details, instrumentation, and reagents. This material is available free of charge via the Internet at http://pubs.acs.org.

References

- (1) Pretsch, E. Trends Anal. Chem. 2007, 26, 46-51.
- (2) Ceresa, A.; Radu, A.; Bakker, E.; Pretsch, E. Anal. Chem. 2002, 74, 4027– 4036.
- (3) (a) Rubinova, N.; Chumbimuni-Torres, K.; Bakker, E. Sens. Actuators B 2007, 121, 135–141. (b) Malon, A.; Vigassy, T.; Bakker, E.; Pretsch, E. J. Am. Chem. Soc. 2006, 128, 8154–8155.
- (4) (a) Chumbimuni-Torres, K. Y.; Dai, Z.; Rubinova, N.; Xiang, Y.; Pretsch, E.; Wang, J.; Bakker, E. J. Am. Chem. Soc. 2006, 128, 13676–13677.
 (b) Thürer, R.; Vigassy, T.; Hirayama, M.; Wang, J.; Bakker, E.; Pretsch, E. Anal. Chem. 2007, 79, 5107–5110.
- (5) (a) Millan, K. M.; Mikkelsen, S. R. Anal. Chem. 1993, 65, 2317–2323.
 (b) Pinar, K.; Burcu, M.; Aysin, Z.; Mehmet, O. Anal. Chim. Acta 2004, 518, 69–76. (c) Ohmichi, T.; Kawamoto, Y.; Wu, P.; Miyoshi, D.; Karimata, H.; Sugimoto, N. Biochemistry 2005, 44, 7125–7130.
- (6) Taton, T. A.; Mirkin, C. A.; Litsinger, R. L. Science 2000, 289, 1757– 1760.
- (7) Wang, J. Anal. Chim. Acta 2003, 500, 247-257.
- (8) Wu, V. C. H.; Chen, S.-H.; Lin, C.-S. Biosens. Bioelectron. 2007, 22, 2967–2975.
- (9) (a) Wang, J. Anal. Chim. Acta 2002, 496, 63-71. (b) Wang, J.; Liu, G.; Mercoçi, A. J. Am. Chem. Soc. 2003, 125, 3214-3215. (c) Hansen, J. A.; Mukhopadhyay, R.; Hansen, J. O.; Gothelf, K. V. J. Am. Chem. Soc. 2006, 128, 3860-3861.
- (10) Wang, J. Stripping Analysis; VCH: New York, 1985.
- (11) (a) Kim, E.; Kim, K.; Yang, H.; Kim, Y. T.; Kwak, J. Anal. Chem. 2003, 75, 5665–5672. (b) Alfonta, L.; Singh, A. K.; Willner, I. Anal. Chem. 2001, 73, 91–102.
- (12) Ihara, T.; Nakayama, M.; Murata, M.; Nakano, K.; Maeda, M. Chem. Commun. 1997, 1609–1610.
- (13) (a) Wang, J.; Liu, G.; Polsky, R.; Merkoçi, A. *Electrochem. Commun.* 2002, 4, 722–726. (b) Kawde, A.-N.; Wang, J. *Electroanalysis* 2004, 16, 101–107. (c) Wang, J.; Rincón, O.; Polsky, R.; Dominguez, E. *Electrochem. Commun.* 2003, 5, 83–86.
- (14) Numnuam, A.; Chumbimuni-Torres, K. Y.; Xiang, Y.; Bash, R.; Thavarungkul, P.; Kanatharana, P.; Pretsch, E.; Wang, J.; Bakker, E. Anal. Chem., in press.

JA0775467