



Corrigendum

Corrigendum to “Wear mechanisms associated with the lubrication of zirconia ceramics in various aqueous solutions”
[J. Eur. Ceram. Soc. 26 (3) (2006) 223–232]

Mitjan Kalin^{a,*}, Goran Dražič^b, Saša Novak^b, Jože Vižintin^a

^a Center for Tribology and Technical Diagnostics, University of Ljubljana, Bogiščeva 8, 1000 Ljubljana, Slovenia

^b Department for Nanostructured Materials, Jožef Stefan Institute, Jamova 39, 1000 Ljubljana, Slovenia

Available online 26 January 2006

The sentence:

The materials used in our investigation were commercially available TZ-3Y zirconia balls (Tosoh USA Inc., Grove City, OH) and in-house prepared discs made from Alcoa A16.SG powder (Alcoa Cop., Pittsburg, PA).

should read:

The materials used in our investigation were commercially available TZ-3Y zirconia balls (Tosoh USA Inc., Grove City, OH) and in-house prepared discs made from Tosoh TZ-3Y powder (Tosoh USA Inc., Grove City, OH).

As seen, the powder used for discs was Tosoh zirconia powder, not Alcoa alumina powder. So, actual samples (balls and discs) were both from zirconia, not zirconia and alumina.

DOI of original article: [10.1016/j.jeurceramsoc.2004.10.026](https://doi.org/10.1016/j.jeurceramsoc.2004.10.026).

* Corresponding author. Tel.: +386 1 4771 462; fax: +386 1 4771 469.

E-mail address: mitjan.kalin@ctd.uni-lj.si (M. Kalin).