

This article was downloaded by:

On: 16 January 2011

Access details: *Access Details: Free Access*

Publisher *Taylor & Francis*

Informa Ltd Registered in England and Wales Registered Number: 1072954 Registered office: Mortimer House, 37-41 Mortimer Street, London W1T 3JH, UK



Journal of Energetic Materials

Publication details, including instructions for authors and subscription information:

<http://www.informaworld.com/smpp/title~content=t713770432>

Errata

To cite this Article (1992) 'Errata', Journal of Energetic Materials, 10: 1, 65

To link to this Article: DOI: 10.1080/07370659208018635

URL: <http://dx.doi.org/10.1080/07370659208018635>

PLEASE SCROLL DOWN FOR ARTICLE

Full terms and conditions of use: <http://www.informaworld.com/terms-and-conditions-of-access.pdf>

This article may be used for research, teaching and private study purposes. Any substantial or systematic reproduction, re-distribution, re-selling, loan or sub-licensing, systematic supply or distribution in any form to anyone is expressly forbidden.

The publisher does not give any warranty express or implied or make any representation that the contents will be complete or accurate or up to date. The accuracy of any instructions, formulae and drug doses should be independently verified with primary sources. The publisher shall not be liable for any loss, actions, claims, proceedings, demand or costs or damages whatsoever or howsoever caused arising directly or indirectly in connection with or arising out of the use of this material.

E R R A T A *

TABLE 4
Uniaxial Results T = 23°C

	COMP B	COMP B M1	COMP B M2	TNT
σ_m COMPRESSIVE STRENGTH (PSI)	3,260 ±150	4,020 (2,700 to 5,050)	4,240 (3,500 to 4,900)	1,850 ±180
E YOUNG'S MODULUS (X10⁶ PSI)	0.60 ±0.02	0.81 (0.59 to 0.92)	0.79 (0.61 to 0.88)	0.45 ±0.07

* Page 358 Volume 9 #5, December 1991