

# CONTENTS BY KEYWORD

|                                     |   |             |
|-------------------------------------|---|-------------|
| <b>Amorphous materials</b>          | Sensors development using its unusual properties of Fe/Co-based amorphous soft magnetic wire . . . . . M. Han <i>et al.</i>   | <b>5573</b> |
| <b>Ceramics</b>                     | Effect of sintering schedule on grain size of oxide ceramics . . . . . K. Maca <i>et al.</i>  | <b>5581</b> |
|                                     | Relation between grain growth, densification and surface diffusion in solid state sintering—a direct observation . . . . . J.-L. Shi <i>et al.</i>  | <b>5711</b> |
|                                     | Formation of strong ceramified ash from silicone-based compositions . . . . . J. Mansouri <i>et al.</i>   | <b>5741</b> |
| <b>Coatings</b>                     | Improved surface properties of D2 steel by laser surface alloying . . . . . E. Gemelli <i>et al.</i>  | <b>5649</b> |
|                                     | Improving the elevated temperature performance of Li/LiMn <sub>2</sub> O <sub>4</sub> cells by coating with ZnO . . . . . H. Liu <i>et al.</i>  | <b>5767</b> |
|                                     | A simple electrosynthesis route for preparation of nanocrystalline titanium sulphide film . . . . . C. D. Lokhande <i>et al.</i>  | <b>5771</b> |
|                                     | UV-absorption and thermal properties of Pb-doped glymo/damo-derived coating materials prepared by sol–gel process . . . . . F. Sayilkan <i>et al.</i>   | <b>5779</b> |
| <b>Composite materials</b>          | Fracture and failure behavior of basalt fiber mat-reinforced vinylester/epoxy hybrid resins as a function of resin composition and fiber surface treatment . . . . . T. Czigány <i>et al.</i> | <b>5609</b> |
| <b>Corrosion and oxidation</b>      | Improved surface properties of D2 steel by laser surface alloying . . . . . E. Gemelli <i>et al.</i>  | <b>5649</b> |
| <b>Diffusion</b>                    | Relation between grain growth, densification and surface diffusion in solid state sintering—a direct observation . . . . . J.-L. Shi <i>et al.</i>  | <b>5711</b> |
| <b>Deposition techniques</b>        | A simple electrosynthesis route for preparation of nanocrystalline titanium sulphide film . . . . . C. D. Lokhande <i>et al.</i>  | <b>5771</b> |
| <b>Electrical properties</b>        | New method of synthesizing In <sub>2</sub> O <sub>3</sub> nanoparticles for application in volatile organic compounds (VOCs) gas sensors . . . . . B. L. Zhu <i>et al.</i>                    | <b>5783</b> |
| <b>Electrochemistry</b>             | Improving the elevated temperature performance of Li/LiMn <sub>2</sub> O <sub>4</sub> cells by coating with ZnO . . . . . H. Liu <i>et al.</i>  | <b>5767</b> |
| <b>Electronic materials</b>         | Improving the elevated temperature performance of Li/LiMn <sub>2</sub> O <sub>4</sub> cells by coating with ZnO . . . . . H. Liu <i>et al.</i>  | <b>5767</b> |
| <b>Fracture</b>                     | Fracture and failure behavior of basalt fiber mat-reinforced vinylester/epoxy hybrid resins as a function of resin composition and fiber surface treatment . . . . . T. Czigány <i>et al.</i> | <b>5609</b> |
| <b>Heat treatment</b>               | UV-absorption and thermal properties of Pb-doped glymo/damo-derived coating materials prepared by sol–gel process . . . . . F. Sayilkan <i>et al.</i>   | <b>5779</b> |
| <b>Laser processing</b>             | Tribology of laser modified surface of stainless steel in physiological solution . . . . . R. Singh <i>et al.</i>   | <b>5619</b> |
|                                     | Improved surface properties of D2 steel by laser surface alloying . . . . . E. Gemelli <i>et al.</i>  | <b>5649</b> |
| <b>Magnetic materials</b>           | Sensors development using its unusual properties of Fe/Co-based amorphous soft magnetic wire . . . . . M. Han <i>et al.</i>   | <b>5573</b> |
| <b>Metals and alloys</b>            | Sensors development using its unusual properties of Fe/Co-based amorphous soft magnetic wire . . . . . M. Han <i>et al.</i>   | <b>5573</b> |
| <b>Microstructure</b>               | Effect of sintering schedule on grain size of oxide ceramics . . . . . K. Maca <i>et al.</i>  | <b>5581</b> |
|                                     | Tribology of laser modified surface of stainless steel in physiological solution . . . . . R. Singh <i>et al.</i>   | <b>5619</b> |
|                                     | Formation of strong ceramified ash from silicone-based compositions . . . . . J. Mansouri <i>et al.</i>   | <b>5741</b> |
| <b>Nanocomposites</b>               | A simple electrosynthesis route for preparation of nanocrystalline titanium sulphide film . . . . . C. D. Lokhande <i>et al.</i>  | <b>5771</b> |
| <b>Nanomaterials</b>                | New method of synthesizing In <sub>2</sub> O <sub>3</sub> nanoparticles for application in volatile organic compounds (VOCs) gas sensors . . . . . B. L. Zhu <i>et al.</i>                    | <b>5783</b> |
| <b>Polymers</b>                     | Fracture and failure behavior of basalt fiber mat-reinforced vinylester/epoxy hybrid resins as a function of resin composition and fiber surface treatment . . . . . T. Czigány <i>et al.</i> | <b>5609</b> |
|                                     | Formation of strong ceramified ash from silicone-based compositions . . . . . J. Mansouri <i>et al.</i>   | <b>5741</b> |
| <b>Sintering</b>                    | Effect of sintering schedule on grain size of oxide ceramics . . . . . K. Maca <i>et al.</i>  | <b>5581</b> |
|                                     | Relation between grain growth, densification and surface diffusion in solid state sintering—a direct observation . . . . . J.-L. Shi <i>et al.</i>  | <b>5711</b> |
| <b>Thermal properties</b>           | UV-absorption and thermal properties of Pb-doped glymo/damo-derived coating materials prepared by sol–gel process . . . . . F. Sayilkan <i>et al.</i>   | <b>5779</b> |
| <b>Thin and thick film coatings</b> | New method of synthesizing In <sub>2</sub> O <sub>3</sub> nanoparticles for application in volatile organic compounds (VOCs) gas sensors . . . . . B. L. Zhu <i>et al.</i>                    | <b>5783</b> |
| <b>Tribology</b>                    | Tribology of laser modified surface of stainless steel in physiological solution . . . . . R. Singh <i>et al.</i>   | <b>5619</b> |