

# CONTENTS BY KEYWORD

<b>Biomaterials</b>	Novel fabrication method of porous poly(L-lactic acid) scaffolds using liquid–solid extraction . . . . . C. Guo <i>et al.</i>	<b>1759</b>
	Effect of flowing speed on bone-like apatite formation in porous calcium phosphate in dynamic RSBF . . . . . C. Deng <i>et al.</i>	<b>1809</b>
<b>Blends</b>	HDPE/PA-6 blends: Influence of screw shear intensity and HDPE melt viscosity on phase morphology development . . . . . H.-X. Huang	<b>1777</b>
<b>Bonding</b>	Effect of surface roughness on the diffusion bonding of Incoloy MA 956 . . . . . Z. Guoge <i>et al.</i>	<b>1793</b>
<b>Ceramics</b>	Microstructure and mechanical properties of 3Y-TZP/Al <sub>2</sub> O <sub>3</sub> composites fabricated by liquid phase sintering . . . . . X. W. Huang <i>et al.</i>	<b>1693</b>
	Lamellar structure and twist boundary of NaV <sub>2</sub> O <sub>5</sub> grown by flux method . . . . . Y. G. Wang <i>et al.</i>	<b>1725</b>
	Preparation low dielectric constant material of cordierite with polyacrylamide gel method . . . . . B. Zhang <i>et al.</i>	<b>1781</b>
	Nanostructured titania membranes with improved thermal stability . . . . . J. Kim <i>et al.</i>	<b>1797</b>
	Microwave dielectric properties of (Zn <sub>1-x</sub> Mn <sub>x</sub> ) <sub>2</sub> P <sub>2</sub> O <sub>7</sub> . . . . . J. Bian <i>et al.</i>	<b>1801</b>
<b>Characterization methods</b>	Evaluation of the suitability of various glass sealant—alloy combinations under SOFC stack conditions . . . . . V. A. C. Haanappel <i>et al.</i>	<b>1583</b>
<b>Composite materials</b>	Tensile strength and fracture surface characterisation of sized and unsized glass fibers . . . . . S. Feih <i>et al.</i>	<b>1615</b>
	Use of artificial neural network for prediction of physical properties and tensile strengths in particle reinforced aluminum matrix composites . . . . . N. Altinkok <i>et al.</i>	<b>1767</b>
	Preparation and conductivity of decatungstomolybdovanadogermanic acid polyethylene glycol (PEG) hybrid material . . . . . Q. Wu <i>et al.</i>	<b>1771</b>
	<i>In-situ</i> Mg <sub>2</sub> Si/Al-Si-Cu composite modified by strontium . . . . . Y. G. Zhao <i>et al.</i>	<b>1831</b>
<b>Crystal growth</b>	Nanostructured titania membranes with improved thermal stability . . . . . J. Kim <i>et al.</i>	<b>1797</b>
<b>Defects</b>	Low-temperature damping behavior of cast iron with aluminum addition . . . . . X. Liu <i>et al.</i>	<b>1773</b>
<b>Deformation and fracture</b>	On Sneddon's boundary conditions used in the analysis of nanoindentation data . . . . . G. Fu <i>et al.</i>	<b>1789</b>
<b>Elastic properties</b>	Consistency checks on elastic properties of crystals . . . . . D. B. Sirdeshmukh <i>et al.</i>	<b>1553</b>
	On Sneddon's boundary conditions used in the analysis of nanoindentation data . . . . . G. Fu <i>et al.</i>	<b>1789</b>
<b>Electrical properties</b>	Preparation low dielectric constant material of cordierite with polyacrylamide gel method . . . . . B. Zhang <i>et al.</i>	<b>1781</b>
<b>Electrochemistry</b>	Preparation and conductivity of decatungstomolybdovanadogermanic acid polyethylene glycol (PEG) hybrid material . . . . . Q. Wu <i>et al.</i>	<b>1771</b>
<b>Electronic properties</b>	Microwave dielectric properties of (Zn <sub>1-x</sub> Mn <sub>x</sub> ) <sub>2</sub> P <sub>2</sub> O <sub>7</sub> . . . . . J. Bian <i>et al.</i>	<b>1801</b>
<b>Fiber technologies</b>	Tensile strength and fracture surface characterisation of sized and unsized glass fibers . . . . . S. Feih <i>et al.</i>	<b>1615</b>
<b>Fracture</b>	Tensile strength and fracture surface characterisation of sized and unsized glass fibers . . . . . S. Feih <i>et al.</i>	<b>1615</b>
<b>Glasses</b>	Evaluation of the suitability of various glass sealant—alloy combinations under SOFC stack conditions . . . . . V. A. C. Haanappel <i>et al.</i>	<b>1583</b>
<b>Grain boundaries</b>	Lamellar structure and twist boundary of NaV <sub>2</sub> O <sub>5</sub> grown by flux method . . . . . Y. G. Wang <i>et al.</i>	<b>1725</b>
<b>Hardness</b>	Comparison of hardness and XPS measurement on austenitic stainless steel irradiated by He <sup>+</sup> or Fe <sup>+</sup> high energy ions . . . . . L. Hongmei <i>et al.</i>	<b>1817</b>
<b>Heat treatment</b>	Low-temperature damping behavior of cast iron with aluminum addition . . . . . X. Liu <i>et al.</i>	<b>1773</b>
	Nanostructured titania membranes with improved thermal stability . . . . . J. Kim <i>et al.</i>	<b>1797</b>
<b>Infrared spectroscopy</b>	Preparation and conductivity of decatungstomolybdovanadogermanic acid polyethylene glycol (PEG) hybrid material . . . . . Q. Wu <i>et al.</i>	<b>1771</b>
<b>Mechanical properties</b>	High temperature compressive properties over a wide range of strain rates in an AZ31 magnesium alloy . . . . . K. Ishikawa <i>et al.</i>	<b>1577</b>
	Microstructure and mechanical properties of 3Y-TZP/Al <sub>2</sub> O <sub>3</sub> composites fabricated by liquid phase sintering . . . . . X. W. Huang <i>et al.</i>	<b>1693</b>
	Low-temperature damping behavior of cast iron with aluminum addition . . . . . X. Liu <i>et al.</i>	<b>1773</b>

(Continued)

<b>Metals and alloys</b>	High temperature compressive properties over a wide range of strain rates in an AZ31 magnesium alloy . . . . . K. Ishikawa <i>et al.</i>	<b>1577</b>
	Evaluation of the suitability of various glass sealant—alloy combinations under SOFC stack conditions . . . . . V. A. C. Haanappel <i>et al.</i>	<b>1583</b>
	Effect of surface roughness on the diffusion bonding of Incoloy MA 956 . . . . . Z. Guoge <i>et al.</i>	<b>1793</b>
<b>Microanalysis</b>	Comparison of hardness and XPS measurement on austenitic stainless steel irradiated by He <sup>+</sup> or Fe <sup>+</sup> high energy ions . . . . . L. Hongmei <i>et al.</i>	<b>1817</b>
<b>Microstructure</b>	High temperature compressive properties over a wide range of strain rates in an AZ31 magnesium alloy . . . . . K. Ishikawa <i>et al.</i>	<b>1577</b>
	Lamellar structure and twist boundary of NaV <sub>2</sub> O <sub>5</sub> grown by flux method . . . . . Y. G. Wang <i>et al.</i>	<b>1725</b>
	HDPE/PA-6 blends: Influence of screw shear intensity and HDPE melt viscosity on phase morphology development . . . . . H.-X. Huang	<b>1777</b>
	<i>In-situ</i> Mg <sub>2</sub> Si/Al-Si-Cu composite modified by strontium . . . . . Y. G. Zhao <i>et al.</i>	<b>1831</b>
<b>Mineralization</b>	Effect of flowing speed on bone-like apatite formation in porous calcium phosphate in dynamic RSBF . . . . . C. Deng <i>et al.</i>	<b>1809</b>
<b>Modelling</b>	Use of artificial neural network for prediction of physical properties and tensile strengths in particle reinforced aluminum matrix composites . . . . . N. Altinkok <i>et al.</i>	<b>1767</b>
	On Sneddon's boundary conditions used in the analysis of nanoindentation data . . . . . G. Fu <i>et al.</i>	<b>1789</b>
<b>Polymers</b>	Novel fabrication method of porous poly(L-lactic acid) scaffolds using liquid–solid extraction . . . . . C. Guo <i>et al.</i>	<b>1759</b>
	HDPE/PA-6 blends: Influence of screw shear intensity and HDPE melt viscosity on phase morphology development . . . . . H.-X. Huang	<b>1777</b>
	Wettability and soil friction of the wollastonite fiber filled UHMWPE composites . . . . . J. Tong <i>et al.</i>	<b>1823</b>
<b>Porosity</b>	Use of artificial neural network for prediction of physical properties and tensile strengths in particle reinforced aluminum matrix composites . . . . . N. Altinkok <i>et al.</i>	<b>1767</b>
<b>Sintering</b>	Microstructure and mechanical properties of 3Y-TZP/Al <sub>2</sub> O <sub>3</sub> composites fabricated by liquid phase sintering . . . . . X. W. Huang <i>et al.</i>	<b>1693</b>
<b>Sol-gel preparation</b>	Preparation low dielectric constant material of cordierite with polyacrylamide gel method . . . . . B. Zhang <i>et al.</i>	<b>1781</b>
	Nanostructured titania membranes with improved thermal stability . . . . . J. Kim <i>et al.</i>	<b>1797</b>
<b>Surfaces</b>	Effect of surface roughness on the diffusion bonding of Incoloy MA 956 . . . . . Z. Guoge <i>et al.</i>	<b>1793</b>
<b>Tribology</b>	Wettability and soil friction of the wollastonite fiber filled UHMWPE composites . . . . . J. Tong <i>et al.</i>	<b>1823</b>