

Under the conditions of the distillation no separation of the bromine isotopes is to be feared, as the constancy in composition of the fractionated material also indicates.

The analyses of titanium tetrachloride and titanium tetrabromide thus agree in yielding the value 47.90 for the atomic weight of titanium.

This research has been assisted by a grant from the Bache Fund of the National Academy of Sciences.

CAMBRIDGE, MASSACHUSETTS

NOTES

Alkali Earth Metals in Saccharate Solutions and their Use in Alkalimetry.—Theoretically it would be most desirable to find some substance the equivalent weight of which could be directly weighed out, put into solution and diluted to a given volume to yield a standard of predetermined normality that would not require standardization or adjustment. The writer has been carrying on some work in an attempt to realize, partially at least, this ideal.

To this end different materials that would yield calcium oxide have been converted to that substance or to calcium hydroxide and have been dissolved to form a standard solution in a 30% cane sugar. These attempts were successful in so far as the attainment of the final results were concerned, but so much time was consumed that the method was not considered practical. In the course of further investigations, it was found that samples of metallic calcium in the form of 0.05 inch wire and about 96% pure went into solution at the rate of 1 g. in about eight minutes, on the average. In the ten cases tried a solution of predetermined normality was obtained, employing, of course, a correction factor to allow for the impurities. The calcium was obtained from the General Electric Company and, though impure, was so uniform that samples from different parts of the lots were found to yield identical solutions. The chief impurity is metallic magnesium which, together with its oxide, is almost insoluble in 30% sucrose, a fact that might be employed in separating small amounts of magnesium from large percentages of calcium especially in the analysis of metallic calcium. It would seem easy to eliminate this impurity by employing pure calcium chloride as an electrolyte instead of that obtained as a by-product from magnesian bitters.

Another source of impurity is the rapid tarnishing of clean surfaces of metallic calcium when exposed to moist air, as reported in the literature. The film so formed is slow to appear in ordinary air and since it is very thin and consists of a high calcium compound, the error from this source seems negligible; however, it can easily be sandpapered off from the warm metal much as rust is removed from standard iron wire. The

warm calcium which does not tarnish readily can then be enclosed in a suitable weighing bottle, cooled and weighed. The metal used in the above experiments was weighed in the open air with excellent results.

Some doubts seem to exist as to whether it would be feasible to produce c. p. metallic calcium. The very recent notable success of Syracuse University in producing 99.9+% metallic barium, a more reactive metal than calcium, should satisfactorily answer this question. In addition, The American Magnesium Corporation in a letter to the writer stated that that company has produced metallic calcium analyzing 99.98% metal. Moreover, it is common knowledge that very pure metallic sodium, still more reactive than the alkali-earth metals, has been produced commercially for years in enormous quantities at a reasonable price.

The size of wire is an important factor in the production of metal suitable for analytical work. Half-inch sticks are too large, as solubility is too slow; 0.05 inch wire is rather small, as the length of a tenth-equivalent is too great for convenience. One-eighth inch sticks would probably be most suitable so that the length of a tenth-equivalent weight would be convenient.

To ascertain whether or not the solution of calcium saccharate so prepared was suitable for general analytical work, titrations of carbonic acid, acid potassium phthalate and succinic acid were carried out with satisfactory results, employing the common indicators. To further test out the solution in actual practice, samples were distributed to members of the chemical faculty for general use. These reported that the solutions were as satisfactory as the bases commonly employed.

The purpose of these notes is to interest, if possible, some producer of metallic calcium to furnish this element in sufficient purity to satisfy the requirements as outlined and at a non-prohibitive price. The successful accomplishment of this object seems attainable by attention to the exclusion of magnesium from the electrolyte employed in the method now used. The financial rewards of such a course seem to be assured because it would enable the chemist to prepare, with a single weighing, a standard alkali of predetermined normality, carbonate free and ready for use without previous standardization by an auxiliary substance.

CONTRIBUTION FROM THE
CHEMICAL LABORATORY
UNIVERSITY OF OKLAHOMA
NORMAN, OKLAHOMA

A. C. SHEAD

RECEIVED OCTOBER 10, 1927
PUBLISHED FEBRUARY 4, 1928