

**Erratum: Instantaneous frequency and amplitude identification using wavelets:  
Application to glass structure  
[Phys. Rev. E 66, 026703 (2002)]**

J. D. Harrop, S. N. Taraskin, and S. R. Elliott\*  
(Received 2 May 2003; published 23 July 2003)

DOI: 10.1103/PhysRevE.68.019904

PACS number(s): 02.70.Hm, 61.43.Fs, 02.30.Nw, 61.43.Bn, 99.10.Cd

We regret that it has come to our attention that some typographical errors appeared in the paper in the description of the new mother wavelet function and associated normalization expressions.

The correct expressions for the mother wavelet function are (the equation numbers refer to those in the original paper)

$$\psi(t; \sigma) = e^{-t^2/2} \{ p(\sigma) [\cos(\sigma t) - \kappa(\sigma)] + i q(\sigma) \sin(\sigma t) \}, \quad (5)$$

$$p(\sigma) = \pi^{-1/4} (1 + 3e^{-\sigma^2} - 4e^{-3\sigma^2/4})^{-1/2}, \quad (6a)$$

$$q(\sigma) = \pi^{-1/4} (1 - e^{-\sigma^2})^{-1/2}. \quad (6b)$$

The variance of the Gaussian approximation to the envelope of the mother wavelet is

$$\sigma_{\psi}^2(\sigma) = \frac{1}{4} \sqrt{\pi} \{ q^2 [1 + (2\sigma^2 - 1)e^{-\sigma^2}] + p^2 \{ [1 + (3 - 2\sigma^2)e^{-\sigma^2}] - 2(2 - \sigma^2)e^{-3\sigma^2/4} \} \}. \quad (11)$$

With this formulation, the remainder of the paper is correct and all results are unaffected.

We are grateful to Victor P. Ostanin for pointing out the mistake.

---

\*Electronic address: jdh30@cam.ac.uk; URL: <http://www.chem.pwf.cam.ac.uk/~jdh30>