




**AIRDROP OF SUPPLIES AND EQUIPMENT:
RIGGING DRAGON AND
JAVELIN MISSILES**



DISTRIBUTION RESTRICTION: Approved for public release; distribution is unlimited.

**HEADQUARTERS
DEPARTMENT OF THE ARMY
DEPARTMENT OF THE AIR FORCE**

**This Publication is available on the
General Dennis J. Reimer Training
And Doctrine Digital Library at
www.adtdl.army.mil**

CHANGE NO. 3

**HEADQUARTERS
DEPARTMENT OF THE ARMY
DEPARTMENT OF THE AIRFORCE
WASHINGTON, DC, 1 January 2001**

**AIRDROP OF SUPPLIES AND EQUIPMENT:
RIGGING DRAGON AND JAVELIN MISSILES**

This change replaces the procedures of the use of the 24-foot diameter, troop chest, reserve parachute on the Javelin missiles two-round bundle with the use of the T-10 cargo parachute procedures. It also adds the procedures for the use of the T-10 cargo parachute on the Javelin missiles four-round bundle.

FM 10-552/TO 13C7-22-61, 05 March 1982, is changed as follows:

1. New or changed material is identified by a vertical bar (■) in the margin opposite the changed material.
2. File this transmittal page in front of the publication.
3. Remove old pages and insert new pages as indicated below:

Remove old pages:

Cover
i-ii
v-vi
1-1
6-1 through 6-36

Insert new pages:

Cover
i-ii
v-vi
1-1
6-1 through 6-34

DISTRIBUTION RESTRICTION: Approved for public release; distribution is unlimited.

C3, FM 10-552/TO 13C7-22-61
1 JANUARY 2001

By Order of the Secretary of the Army and the Air Force:

ERIC K. SHINSEKI
General, United States Army
Chief of Staff

Official:



JOEL B. HUDSON
Administrative Assistant to the
Secretary of the Army
0033901

GEORGE T. BABBITT
General, USAF
Commander, AFMC

MICHAEL E. RYAN
General, USAF
Chief of Staff

DISTRIBUTION:

Active Army, Army National Guard, and U.S. Army Reserve: To be distributed in accordance with the initial distribution number 110933, requirements for FM 10-552.

**AIRDROP OF SUPPLIES AND EQUIPMENT:
 RIGGING DRAGON MISSILES**

TABLE OF CONTENTS

	Paragraph	Page
PREFACE		vii
CHAPTER 1. INTRODUCTION		
Description of Items.....	1-1	1-1
Special Considerations.....	1-2	1-1
CHAPTER 2. RIGGING AN A-22 CARGO BAG		
Section I. RIGGING NINE ONE-ROUND CONTAINERS		
Description of Load.....	2-1	2-1
Rigging Load.....	2-2	2-1
Closing Cargo Bag.....	2-3	2-1
Installing Parachutes.....	2-4	2-1
Equipment Required.....	2-5	2-1
Section II. RIGGING ONE 15-ROUND CONTAINER		
Description of Load.....	2-6	2-6
Rigging Load.....	2-7	2-6
Installing Parachutes.....	2-8	2-6
Equipment Required.....	2-9	2-7
CHAPTER 3. RIGGING CONTAINERS ON 8-FOOT PLATFORM FOR LOW-VELOCITY AIRDROP		
Section I. RIGGING THIRTY-SIX ONE-ROUND CONTAINERS		
Description of Load.....	3-1	3-1
Preparing Platform.....	3-2	3-1
Building and Placing Honeycomb Stacks.....	3-3	3-1
Positioning and Binding Container Groups.....	3-4	3-1
Lashing Containers.....	3-5	3-1
Safetying Suspension Slings.....	3-6	3-1
Installing Cargo Parachute.....	3-7	3-1
Installing Extraction System.....	3-8	3-10
Installing Release System.....	3-9	3-11
Placing Extraction Parachute.....	3-10	3-11
Marking Rigged Load.....	3-11	3-11
Equipment Required.....	3-12	3-11

DISTRIBUTION RESTRICTION: Approved for public release; distribution is unlimited.

Section II. RIGGING FOUR 15-ROUND CONTAINERS		Paragraph	Page
Description of Load.....			
Preparing Platform.....	3-13	3-14	
Building and Placing Honeycomb Stacks.....	3-14	3-14	
Positioning Load.....	3-15	3-14	
Lashing Load.....	3-16	3-14	
Safetying Suspension Slings.....	3-17	3-14	
Installing Cargo Parachute.....	3-18	3-14	
Installing Extraction System.....	3-19	3-14	
Installing Release System.....	3-20	3-15	
Placing Extraction Parachute.....	3-21	3-16	
Marking Rigged Load.....	3-22	3-16	
Equipment Required.....	3-23	3-16	
	3-24	3-16	
Section III. RIGGING FOUR A-22 CARGO BAGS WITH ONE-ROUND CONTAINERS			
Description of Load.....			
Preparing Platform.....	3-25	3-19	
Building and Placing Honeycomb Stacks.....	3-26	3-19	
Preparing Load.....	3-27	3-19	
Positioning Load.....	3-28	3-19	
Lashing Load.....	3-29	3-19	
Installing Suspension Slings.....	3-30	3-19	
Installing Cargo Parachute.....	3-31	3-19	
Installing Extraction System.....	3-32	3-19	
Installing Release System.....	3-33	3-24	
Placing Extraction Parachute.....	3-34	3-25	
Marking Rigged Load.....	3-35	3-25	
Equipment Required.....	3-36	3-25	
	3-37	3-25	
Section IV. RIGGING FOUR A-22 CARGO SLINGS WITH 15-ROUND CONTAINERS			
Description of Load.....			
Preparing Platform.....	3-38	3-28	
Building and Placing Honeycomb Stacks.....	3-39	3-28	
Preparing Load.....	3-40	3-28	
Positioning Load.....	3-41	3-28	
Rigging Load.....	3-42	3-28	
Marking Rigged Load.....	3-43	3-28	
Equipment Required.....	3-44	3-28	
	3-45	3-28	
CHAPTER 4. RIGGING CONTAINERS ON 12-FOOT PLATFORM FOR LAPES			
Section I. RIGGING THIRTY-SIX ONE-ROUND CONTAINERS			
Description of Load.....			
Preparing Platform.....	4-1	4-1	
Building and Placing Honeycomb Stacks.....	4-2	4-1	
Positioning Front Container Groups.....	4-3	4-1	
Lashing Front Container Groups.....	4-4	4-1	
Positioning Rear Container Groups.....	4-5	4-1	
	4-6	4-1	

Section IV. RIGGING FOUR A-22 CARGO SLINGS WITH FOUR 15-ROUND CONTAINERS

	Paragraph	Page
Description of Load.....	5-42	5-55
Preparing Platform.....	5-43	5-55
Building and Placing Honeycomb Stacks.....	5-44	5-57
Preparing the Load.....	5-45	5-58
Positioning the Load.....	5-46	5-60
Lashing Missile Containers.....	5-47	5-61
Installing Suspension Slings and Deadmans Tie.....	5-49	5-64
Stowing Cargo Parachute.....	5-49	5-65
Installing Extraction System.....	5-50	5-66
Installing Parachute Release.....	5-51	5-67
Placing Extraction Parachute.....	5-52	5-68
Installing Provisions for Emergency Restraints.....	5-53	5-68
Marking Rigged Load.....	5-54	5-68
Equipment Required.....	5-55	5-70

CHAPTER 6. RIGGING THE ADVANCED ANTITANK WEAPON SYSTEM-MEDIUM (JAVELIN) FOR LOW-VELOCITY AIRDROP**Section I. RIGGING TWO-ROUND A-7A DOOR BUNDLE**

Description of Load.....	6-1	6-1
Preparing Two-Round A-7A Door Bundle.....	6-2	6-1
Attaching Parachute to Load.....	6-3	6-10
Marking Rigged Load.....	6-4	6-11
Equipment Required.....	6-5	6-11

Section II. RIGGING FOUR-ROUND A-7A DOOR BUNDLE

Description of Load.....	6-6	6-13
Preparing Four-Round A-7A Door Bundle.....	6-7	6-13
Attaching Parachute to Load.....	6-8	6-23
Marking Rigged Load.....	6-9	6-24
Equipment Required.....	6-10	6-24

Section III. RIGGING NINE-ROUND CDS RIGGED IN AN A-22 STRETCH CONTAINER

Description of Load.....	6-11	6-26
Preparing Skid Board, Ties and Positioning Honeycomb.....	6-12	6-26
Positioning A-22 Sling Assemblies.....	6-13	6-28
Positioning Covers and A-7A Straps.....	6-14	6-29
Positioning and Securing Javelin Missiles.....	6-15	6-30
Securing the Lateral Straps and Installing Suspension Slings.....	6-16	6-31
Securing Skid Board Ties and Installing Parachute.....	6-17	6-32
Marking Rigged Load.....	6-18	6-33
Equipment Required.....	6-19	6-33

CHAPTER 7. RIGGING THIRTY-SIX JAVELIN ROUNDS AS A MASS SUPPLY LOAD ON A 12-FOOT, TYPE V AIRDROP PLATFORM FOR LOW-VELOCITY AIRDROP

	Paragraph	Page
Description of Load.....	7-1	7-1
Preparing Platform.....	7-2	7-1
Building and Positioning Honeycomb Stacks.....	7-3	7-3
Positioning and Securing Javelin Rounds	7-4	7-6
Lashing Load to Platform	7-5	7-13
Covering Load, Installing Suspension Slings and Deadman’s Tie.....	7-6	7-17
Stowing Cargo Parachutes and Installing Extraction System.....	7-7	7-19
Installing Parachute Release.....	7-8	7-20
Placing Extraction Parachute.....	7-9	7-21
Installing Provisions for Emergency Restraints.....	7-10	7-21
Marking Rigged Load.....	7-11	7-21
Equipment Required.....	7-12	7-21
GLOSSARY		Glossary-1
REFERENCES		References-1

PREFACE

SCOPE

This manual tells and shows how to prepare and rig the Dragon and Javelin antitank/assault missiles for low-velocity airdrop from C-130, C-141B, C-5, or C-17 aircraft. It is designed for use by all parachute riggers.

USER INFORMATION

The proponent of this publication is HQ TRADOC. You are encouraged to report any errors or omissions and to suggest ways for making this a better manual. Army personnel, send your comments on DA Form 2028 directly to:

Aerial Delivery and Field Services Department
USA Quartermaster Center and School
1010 Shop Road
Fort Lee, Virginia 23801-1502

Air Force personnel, send your reports on AFTO Form 22 through:

Headquarters
Air Mobility Command (AMC/DOTX)
402 Scott Drive, Unit 3A1
Scott AFB, Illinois 62225-5302

Air Force personnel in Special Operations Command, send your reports on AFTO Form 22 through:

HQ AFSOC/DOXT
100 Bartley St., Suite 260
Hurlburt Field, Florida 32544-5273

to:

Aerial Delivery and Field Services Department
USA Quartermaster Center and School
1010 Shop Road
Fort Lee, Virginia 23801-1502

Also send information copy of AFTO Form 22 to:

SA-ALC/TILD
485 Quentin Roosevelt Road
Kelly AFB, Texas 78241-6421

Unless this publication states otherwise, masculine nouns and pronouns do not refer exclusively to men.

CHAPTER 1

INTRODUCTION

1-1. Description of Items

This manual tells and shows how to rig Dragon and Javelin antitank/assault missiles for airdrop. The missile containers may be airdropped in the following ways:

a. Nine one-round containers are rigged in an A-22 cargo bag on a standard skid for a low-velocity airdrop from a C-130, C-141B, or C-17 aircraft.

b. One 15-round container is rigged in an A-22 cargo sling on a standard skid for a low-velocity airdrop from a C-130, C-141B, or C-17 aircraft.

c. Thirty-six one-round containers are rigged on an 8-foot modular type II platform for a low-velocity airdrop from a C-130 or C-141B aircraft.

d. Four 15-round containers are rigged on an 8-foot modular type II platform for a low-velocity airdrop from a C-130 or C-141B aircraft.

e. Four A-22 cargo bags with nine one-round containers in each A-22 cargo bag are rigged on an 8-foot modular type II platform for a low-velocity airdrop from a C-130 or C-141B aircraft.

f. Four A-22 cargo slings with four 15-round containers are rigged on an 8-foot modular type II platform for a low-velocity airdrop from a C-130 or C-141B aircraft.

g. Thirty-six one-round containers are rigged on a 12-foot LAPES/AD platform for a low-altitude parachute extraction system (LAPES) airdrop from a C-130 aircraft.

Note: LAPES loads weighing less than 6,700 pounds must be dropped as part of a tandem drop.

h. Four 15-round containers are rigged on a 12-foot LAPES/AD platform for a LAPES airdrop from a C-130 aircraft. (See note in g above.)

i. Four A-22 cargo bags with nine one-round containers in each A-22 cargo bag are rigged on a 12-foot LAPES/AD platform for a LAPES airdrop from a C-130 aircraft. (See note in g above.)

j. Four A-22 cargo slings with 15-round containers are rigged on a 12-foot LAPES/AD platform for a LAPES airdrop from a C-130 aircraft. (See note in g above.)

k. Thirty-six one-round containers are rigged on an 8-foot, type V airdrop platform for a low-velocity airdrop from a C-130 or C-141B aircraft.

l. Four 15-round containers are rigged on an 8-foot, type V airdrop platform for a low-velocity airdrop from a C-130, C-141B, or C-17 aircraft.

m. Four A-22 cargo bags with nine one-round containers in each A-22 cargo bag are rigged on an 8-foot, type V airdrop platform for a low-velocity airdrop from a C-130, C-141B, or C-17 aircraft.

n. Four A-22 cargo slings with four 15-round containers are rigged on an 8-foot, type V airdrop platform for a low-velocity airdrop from a C-130, C-141B, C-5, or C-17 aircraft.

Note: The following deals with Javelin rounds and containers.

o. Javelin two-round A-7A door bundle rigged for low-velocity airdrop from a C-130, C-141, or C-17 aircraft.

p. Javelin four-round A-7A door bundle rigged for low-velocity airdrop from a C-130, C-141 or C-17 aircraft.

q. Javelin six-round A-22 stretch container rigged for low-velocity airdrop from a C-130, C-141, or C-17 aircraft. Javelin thirty-six round mass supply load on a 12-foot, Type V, airdrop platform for low-velocity airdrop from a C-130, C-141, C-5, or C-17 aircraft.

1-2. Special Considerations

a. These loads contain dangerous explosives as defined by *AFJMAN 24-204/TM 38-250*.

b. A copy of this manual must be available for the joint airdrop inspectors to use during the before and after loading inspections.

CHAPTER 6

RIGGING THE ADVANCED ANTITANK WEAPON SYSTEM-MEDIUM (JAVELIN) FOR LOW-VELOCITY AIRDROP

Section I


RIGGING TWO-ROUND A-7A DOOR BUNDLE

6-1. Description of Load


The Javelin Missile System is a man-portable antitank weapon system made up of a tactical round in a disposable launch tube and a reusable Command Launch Unit (CLU). The Command Launch Unit is not rigged with the tactical rounds. The Javelin can be airdropped as a door bundle in two-round and four-round configurations. As a door bundle, the Javelin can be dropped only from C-130, C-141, C-5 and C-17 aircrafts. The Javelin two-round A-7A door bundle has an approximate rigged weight of 146 pounds. It has an approximate height of 65 1/2 inches, a width of 17 1/2 inches and a length of 30 1/4 inches. The two-round bundle uses the T-10 cargo parachute.

6-2. Preparing Two-Round A-7A Door Bundle

Prepare the two-round A-7A door bundle according to FM 10-500-3/TO 13C7-1-11 and as shown in Figure 6-1.



- 1 Cut two 17 1/2-inch by 30 1/4-inch pieces of 3/4-inch plywood with eight 1/2-inch by 2-inch cutouts. Pad and tape sharp edges of the cutouts.
- 2 Cut two 17 1/2-inch by 30 1/4-inch pieces of honeycomb.



- 3 Cut two 7-inch by 7-inch pieces of honeycomb.

Figure 6-1. Two-round A-7A door bundle prepared








Figure 6-1. Two-round A-7A door bundle prepared (continued)




- ⑦ Position four A-7A straps under one of the 17 1/2-inch by 30 1/4-inch pieces of plywood. Position each strap approximately 5 inches from each edge of the plywood.
- ⑧ Position and glue the two 7-inch by 7-inch pieces of honeycomb on top of the plywood. Each piece should be 5 1/4 inches from the right and left edges of the plywood. Each piece should also be 5 3/4 inches from the forward edge and 5 3/4 inches from the rear edge of the plywood.

Figure 6-1. Two-round A-7A door bundle prepared (continued)




- 9 Position and glue one of the 17 1/2-inch by 30 1/4-inch pieces of honeycomb centered on the plywood in step 8.
- 10 Position two A-7A straps, one in each set of cutouts on the 24 1/4-inch by 47-inch piece of plywood.

Figure 6-1. Two-round A-7A door bundle prepared (continued)




COMMAND
LAUNCH
UNIT CONNECTORS




- 11 Position and glue one of the matching pieces of honeycomb on the top of the plywood in step 10.
- 12 With the Command Launch Unit connectors on opposite ends, position two Javelin rounds on the honeycomb. Lay the rounds with the flat side of the protective foam down making sure the Battery Coolant Units (BCU) face inward.

Figure 6-1. Two-round A-7A door bundle prepared (continued)




- 13 Position the other piece of 24 1/4 inch by 47 inch honeycomb with the cutouts evenly on top of the launch tubes.
- 14 Position and glue the matching piece of plywood on top of the honeycomb.
- 15 Secure the A-7A straps. Fold and secure excess straps with one turn single type I, 1/4-inch cotton webbing.

Figure 6-1. Two-round A-7A door bundle prepared (continued)



- ① 16 Using the materials from steps 7 through 9 as a base, position the materials from steps 10 through 15 on one end centered on the base.
- ① 17 Position one of the 17 1/2-inch by 47-inch pieces of honeycomb flush with the front of the load and one flush with the rear of the load. Tape the edges of the honeycomb and secure it in place with two lengths of type III nylon cord.

Figure 6-1. Two round A-7A door bundle prepared (continued)



- ⑱ Position one 17 1/2-inch by 30 1/4-inch piece of honeycomb on top of the load.
- ⑲ Position and glue one 17 1/2-inch by 30 1/4-inch piece of plywood on the honeycomb.
- ⑳ Position two D-rings on top of the load. Place one in the left front corner and the other in the right rear corner of the load. Secure in place by passing the running ends of two of the A-7A straps in those corners through the D-rings. Secure all the A-7A straps.

Figure 6-1. Two-round A-7A door bundle prepared (continued)

6-3. Attaching Parachute to Load

Attach a T-10 cargo parachute as shown in Figure 6-2.




Figure 6-2. Parachute attached to load


6-4. Marking Rigged Load

Mark the rigged load according to FM 10-500-2/TO 13C7-1-5 and as shown in Figure 6-3. Complete Shipper's Declaration for Dangerous Goods and affix to load.

6-5. Equipment Required

Use the equipment listed in Table 6-1 to rig this load.

CAUTION
Mark the load "Door Bundle Only, Do Not Drop From AFT Ramp"



RIGGED LOAD DATA	
Rigged Weight	146 pounds
Height	65 1/2 inches
Width	17 1/2 inches
Length	30 1/4 inches
Parachute	T-10 cargo

Figure 6-3. Javelin two-round A-7A door bundle rigged

Table 6-1. Equipment required for rigging the Javelin two-round A-7A door bundle for low-velocity airdrop.

National Stock Number	Item	Quantity
8040-00-273-8713	Adhesive, paste, 1-gal	As required
4020-00-240-2146	Cord, nylon, type III, 550-lb	As required
1670-00-753-3928	Pad, energy-dissipating, honeycomb,	3 sheets
No NSN	Parachute: T-10 cargo	1
5530-00-128-4981	Plywood, 3/4- by 48- by 96-in	2 sheets
1670-00-251-1153	Sling assembly, cargo, airdrop, A-7A	6
8310-01-102-4478	Thread, cotton, ticket 8/7	As required
8305-00-268-2411	Webbing, cotton, 1/4-in, 80-lb	As required

Section II

RIGGING FOUR-ROUND A-7A DOOR BUNDLE


6-6. Description of Load

The Javelin Missile System is a man-portable antitank weapon system made up of a tactical round in a disposable launch tube and a reusable Command Launch Unit. The Command Launch Unit is not rigged with the tactical rounds. The Javelin four-round A-7A door bundle has an approximate rigged weight of 271 pounds. It has a height of 57 1/2 inches (G14) and 65 1/2 inches (T-10), a width of 37 1/2 inches and a length of 44 1/2 inches. The four-round bundle uses the G-14 or T-10 cargo parachute.


6-7. Preparing Four-Round A-7A Door Bundle

Prepare the four-round A-7A door bundle according to FM 10-500-3/TO 13C7-1-11 and as shown in Figure 6-4.

Note: This drawing is not to scale.




- ① Cut two 29 1/2-inch by 30 1/4-inch pieces of 3/4-inch plywood with eight 1/2-inch by 2-inch cutouts. Pad and tape the sharp edges of the cutouts.
- ② Cut two 29 1/2-inch by 30 1/4-inch pieces of honeycomb.



- ③ Cut four 4-inch by 9-inch pieces of honeycomb.

Figure 6-4. Four-round A-7A door bundle prepared


Note: This drawing is not to scale.



- ④ Cut three 24 1/4-inch by 47-inch pieces of 3/4-inch plywood with four 3-inch by 5 1/2-inch cutouts. Pad and tape the sharp edges of the cutouts.
- ⑤ Cut two pieces of honeycomb to match step 4.
- ⑥ Cut two 30-inch by 47-inch pieces of honeycomb.

Figure 6-4. Four-round A-7A door bundle prepared (continued)

Note: This drawing is not to scale.



- 7 Position four A-7A straps under one of the 29 1/2-inch by 30 1/4-inch pieces of plywood. Position each strap in each set of cutouts of the plywood.
- 8 Position and glue the four 4-inch by 9-inch pieces of honeycomb on top of the plywood. The pieces on the left side should be 6 3/4 inches from the left edge of the plywood and the right side pieces should be 6 3/4 inches from the right edge of the plywood. The forward pieces should be 4 inches from the forward edge of the plywood and the rear pieces should be 4 inches from the rear edge of the plywood.

Figure 6-4. Four-round A-7A door bundle prepared (continued)




Figure 6-4. Four-round A-7A door bundle prepared (continued)




Figure 6-4. Four-round A-7A door bundle prepared (continued)




Figure 6-4. Four-round A-7A door bundle prepared (continued)




Figure 6-4. Four-round A-7A door bundle prepared (continued)




Figure 6-4. Four-round A-7A door bundle prepared (continued)




Figure 6-4. Four-round A-7A door bundle prepared (continued)


6-9. Marking Rigged Load

Mark the rigged load according to FM 10-500-2/TO 13C7-1-5 and as shown in Figure 6-6. Complete Shipper's Declaration for Dangerous Goods and affix to load.

6-10. Equipment Required

Use the equipment listed in Table 6-2 to rig the load.

CAUTION
Mark the load "Door Bundle Only, Do Not Drop From AFT Ramp"



RIGGED LOAD DATA	
Rigged Weight	271 pounds
Height	57 1/2 inches (G-14) 65 1/2 inches (T-10)
Width	37 1/2 inches
Length	44 1/2 inches
Parachute	T-10 or G-14 cargo parachute

Figure 6-6. Javelin four-round A-7A door bundle rigged (G-14 shown)

Table 6-2. Equipment required for rigging the Javelin four-round A-7A door bundle for a low-velocity airdrop.

National Stock Number	Item	Quantity
8040-00-273-8713	Adhesive, paste, 1-gal	As required
4020-00-240-2146	Cord, nylon, type III, 550-lb	As required
1670-00-753-3928	Pad, energy-dissipating, honeycomb,	3 sheets
1670-00-999-2658	Parachute: G-14, cargo or	1
No NSN	Canopy, 35-ft diam., T-10 modified for cargo	1
5530-00-128-4981	Plywood, 3/4- by 48- by 96-in	2 sheets
1670-00-251-1153	Sling assembly, cargo, airdrop, A-7A	6
5340-00-360-0560	Suspension web	2
8310-01-102-4478	Thread, cotton, ticket number 8/7	As required
8305-00-268-2411	Webbing, cotton, 1/4-in, 80-lb	As required

Section III

RIGGING NINE-ROUND CDS RIGGED IN AN A-22 STRETCH CONTAINER

6-11. Description of Load

The Javelin Missile System is a man-portable antitank weapon system made up of a tactical round in a disposable launch tube and a reusable command launch unit. The command launch unit is not rigged with the launch tubes. The Javelin nine-round Javelin missile system rigged in an A-22 stretch container has an approximate rigged weight of 810 pounds. It has a height of 65 1/2 inches, a width of 48 inches and a length of 60 inches. The nine round Javelin missile system rigged in an A-22 stretch container uses the G-12E cargo parachute.

6-12. Preparing Skid Board, Ties and Positioning Honeycomb

Prepare the skid board, ties and position the honeycomb according to FM 10-500-3/TO 13C7-1-11 and as shown in Figure 6-7.




Figure 6-7. Skidboard, ties and honeycomb prepared and positioned

6-13. Positioning A-22 Sling Assemblies

Position two A-22 sling assemblies on the load according to FM 10-500-3/TO 13C7-1-11 and as shown in Figure 6-8.




Figure 6-8. A-22 sling assemblies positioned

6-14. Positioning Covers and A-7A Straps

Position two covers and two A-7A straps on top of the sling assemblies as shown in Figure 6-9.




Figure 6-9. Covers and A-7A straps positioned

6-15. Positioning and Securing Javelin Missiles

Position nine Javelin missiles and secure them as shown in Figure 6-10.




Figure 6-10. Javelin missiles positioned and secured

6-16. Securing the Lateral Straps and Installing Suspension Slings

Secure the lateral straps according to FM 10-500-3/TO 13C7-1-11 and install the suspension slings as shown in Figure 6-11.




Figure 6-11. Lateral straps secured and suspension slings installed

6-17. Securing Skid Board Ties and Installing Parachute

Secure the skid board ties according to FM 10-500-3/TO 13C7-1-11 and install a G-12E cargo parachute as shown in Figure 6-12.




Figure 6-12. Skid board ties secured and parachute installed

6-18. Marking Rigged Load

Mark the rigged load according to FM 10-500-2/TO 13C7-1-5 and as shown in Figure 6-13. Complete Shipper's Declaration for Dangerous Goods and affix to load.

6-19. Equipment Required

Use the equipment listed in Table 6-3 to rig the load.

**RIGGED LOAD DATA**

Rigged Weight	810 pounds
Height	65 1/2 inches
Width	48 inches
Length	60 inches
Parachute	G-12E cargo parachute

Figure 6-13. Javelin nine-round CDS in an A-22 stretch container rigged

Table 6-3. Equipment required for rigging the Javelin nine-round CDS in an A-22 stretch container for a low-velocity airdrop

National Stock Number	Item	Quantity
1670-00-587-3421	Bag, cargo, A-22	2
4030-00-678-8562	Clevis, suspension, 3/4-in (medium)	1
1670-01-162-2372	Clevis assembly (type V)	2
1670-00-753-3928	Pad, energy-dissipating, honeycomb	3 sheets
1670-01-065-3755	Parachute, cargo, G-12E	1
5530-00-128-4981	Plywood, 3/4- by 48- by 96-in	2 sheets
1670-01-062-6301	Sling, cargo, airdrop, 3-ft (2-loop)	4
7510-00-266-6710	Tape, masking, 2-in	As required
8305-00-268-2411	Webbing: Cotton, 1/4-in, type I	As required
8305-00-082-5752	Tubular, 1/2-in	As required
8305-00-263-3591	Type VIII	As required