OUTBOARD MOTOR, GASOLINE POWERED, OMC MODEL AM-40A, NSN 2805-01-089-0989


Intervals (on-condition or herd time) and the related manhour times are based on normal operation. The manhour time specified is the time you need to do all the services prescribed for a particular interval. On-condition (OC) oil sample intervals shall be applied unless changed by the Army Oil Analysis Program (AOAP) laboratory. Change the hard time interval if your lubricants are contaminated or if you are operating the equipment under adverse operating conditions, including longer-than-usual operating hours. The hard time interval may be extended during periods of low activity. If extended, adequate preservation precautions must be taken. Hard time intervals will be applied in the event AOAP laboratory support is not available.


'The time specified is the time required to perform all services at the particular interval.

Clean parts with dry cleaning solvent (SD), type II or equivalent. Dry before lubricating. The lowest level of maintenance authorized to lubricate a point is indicated by one of the following: (C) Operator/crew; or (O) Organizational Maintenance.

You can help improve this publication. If you find any mistake or if you know of a way to improve the procedures, please let us know. Your letter or DA Form 2028 Recommended Changes to Publications and Blank Forms) should be mailed directly to' Commander, U.S. Army Troop Support & Aviation Material Readiness Command, ATTN: DRSTS-MPSD, 4300 Goodfellow Blvd., St. Louis, MO 63120. A reply will be furnished to you.

*TOTAL TASK-H R		*TOTAL	TASK-H R
INTERVAL	TASK-HR	INTERVAL	TASK-HR
M Q	2.0 1.5	20 B	1.5 biannually





NOTES

*1. FUEL MIXTURE (C)

1 part approved lubricant to 50 parts gasoline. 8 fl. ozs. lubricant to 3 (three) gallons of gasoline. 16 fl. ozs. lubricant to 6 (six) gallons of gasoline. 20 milliliters lubricant to 1 liter gasoline.


CAUTION

Lubricant end gasoline must be properly mixed or serious damage will result to the engine.

CAUTION

Avoid the use of the following, they will contribute to deterioration of your engine and shorten spark plug life:





AVOID USE OF:

*2 GEARCASE (O)

Change after first 20 hours of operation and check after 50 hours of operation. Add lubricant if necessary.

Drain and refill every 100 hours of operation or every 6 months, whichever occurs first.

Automotive oils Premix fuel of unknown oil quality Premix fuel richer than 50/1 ratio Premix fuel leaner than 50/1 mixture ratio

- KEY -

		REFILL	EXPECTED TEMPERATURES		For		
		CAPACI	Above +32°F	+40°F to -10°F	0°F to -65°F	Arctic	
LUBRICANTS		TY (APP)	Above 0°C	+5°C to -23°C	-18°C to -50°C	Operation	INTERVALS
B/A Grade TCW 50/1 NSN 9150-	Lubricating Oil, Engine	6 gals. (Gas Tank)	TCW 50/1	TCW 50/1	TCW 50/1	Refer to TM 9- 207	M = Monthly
117-8791			GO	GO	GO		B = Biannually
GO MIL-L- 2015	Gearcase	413 cc					20 = Hours
GAA	Grease	O/C	GAA	GAA	GAA		
MIL-G- 2104GR30 (Oil Can Points)	General Purpose Oil						

DISTRIBUTION:

To be distributed in accordance with DA Form 12-25D, Operator naintenance requirements for Outboard Motors.

Copy of this Lubrication Order will remain with the equipment at all times; instructions contained herein are mandatory.

BY ORDER OF THE SECRETARY OF THE ARMY:

E.C. MEYER

General, United States Army Chief of Staff

OFFICIAL:

ROBERT M. JOYCE Brigadier General, United States Army The Adjutant General

Card 2 of 2

RECOMMENDED CHANGES TO EQUIPMENT TECHNICAL PUBLICATIONS							
SOMETHING WRONG WITH THIS PUBLICATION?							
THEN JOT DOWN THE DOPE ABOUT IT ON THIS FORM, CAREFULLY TEAR IT OUT, FOLD IT AND DROP IT IN THE MAIL! FROM: (PRINT YOUR UNIT'S COMPLETE ADDRESS) DATE SENT							
IN THE MAIL							
PUBLICATION NUMBER	PUBLICATION DATE	Publication title					
BE EXACTPIN-POINT WHERE IT IS	IN THIS SPACE TELL WHAT IS	WRONG					
PAGE GRAPH FIGURE NO.	AND WHAT SHOULD BE DON!						
PRINTED NAME, GRADE OR TITLE, AND TELEP	HONE NUMBER . SIGN HE	FRE:					

DA 15017 2028-2

PREVIOUS EDITIONS
• ARE OBSOLETE.

P.S.—IF YOUR OUTFIT WANTS TO KNOW ABOUT YOUR RECOMMENDATION MAKE A CARBON COPY OF THIS AND GIVE IT TO YOUR HEADQUARTERS.

PIN: 051468-000