17 APRIL 1962 (Supersedes L05-4310-221-15, 7 August 1961)

COMPRESSOR, ROTARY: AIR; SKID MTD; GASOLINE DRIVEN; 125 CFM 100 PSI (INGERSOLL-RAND MODEL GER-125) W/CONTINENTAL ENGINE MODEL FS-162

Reference: SM 10-1-C4-1

Intervals are based on normal operation. Reduce to compensate for abnormal operations and severe conditions. During inactive periods sufficient lubrication must be performed for adequate preservation.


Clean fittings before lubricating.

Relubricate after washing.

Clean parts with SOLVENT, dry-cleaning, or with OIL, fuel, Diesel. Dry before lubricating.

Dotted circle indicates drain below.

Drain crankcase only when hot after operation; replenish and check level when cool.



KEY

LUBRICANTS	CAPACITY	EXPECTED TEMPERATURES			INTERVALS
OE —OIL, Engine, Heavy Duty		Above +32°F	+40°F to 10°F	0°F to 65°F	
Engine Crankcase	4—1/2 qt	OE 30	OE 10	OES	
		or	or		
		9250	9110		
Oil Can Paints					
OES—OIL, Engine, Subzero					
2110TH-LUBRICATING OIL, General Purpose					Intervals
Compressor Air Receiver	20 qt				given are
Air Cleaner (See note 4)	1—3/4 qt	2110TH	2110TH	OES	in hours of
Air Cleaner (See note 5)	31/4 qt				normal
GAA—GREASE, Automotive and Artillery					operation

NOTES:

- 1. FOR OPERATION OF EQUIPMENT IN PROTRACTED COLD TEMPERATURES BELOW 10°F. Remove lubricants prescribed in the key for temperatures above -10°F. Clean parts with SOLVENT, drycleaning. Relubricate with lubricants specified in the key for 'temperatures below -10°F.
- 2. OIL FILTER. After installing new filter elements, fill crankcase, operate engine 5 minutes, check housings for leaks, check crankcase oil level and bring to full mark.
- 3. OIL CAN POINTS. Every 50 hours clean and lightly coat control linkages, exposed threads and pins with OE.

Copy of this Lubrication Order will remain with the equipment at all times; instructions contained herein are mandatory.

FOLD

FOLD

- 4. AIR CLEANER. Capacity shown is applicable to end items within serial number range 125CR22346 inclusive.
- 5. AIR CLEANER. Capacity shown is applicable to end items within serial number range 125CR24901 thru 125CR25400 inclusive.

BY ORDER OF THE SECRETARY OF THE ARMY:

G. H. DECKER, General, United States Army Chief of Staff

Official:

J. C. LAMBERT, Major General, Untied States Army, The Adjutant General.

LO 5-4310-221-15 DISTRIBUTION: Active Army USASA (2); DCSLOG (1); CNGB (1); Tech Stf, DA (1) except CofEngrs (3); Army Maint Bd (1); USCONARC (3); USAARTYBD (2); USAARTYBD (2); USABB (2); USARDB (2); USAABELCTBD (2); USAAVNBD (2); ARADCOM (2); ARADCOM Rgn (2); OS Maj Comd (5) except USASETAP (2). USARJ (10); MDW (1); Armies (2); Corp (2)1 Div (2); Engr Bde (1); Svc Colleges (2); Br Svc Sch (2) except USAES (100); USMA (2); GENDEP (2) except Schenectady GENDEP (4), Atlanta GENDEPP (4); Usah GENDEP (4); Memphis GENDEP (4); Sharpe GENDEP (4) Engr Sec GENDEP (10); except Granite City Engr Dep (14); USA Trans Tml Comd (2); Army Tml (1); OSA (2); Engr Dist (2) except Buffalo Engr Dist (1), Chicago Engr Dist (1), Detroit Engr Dist (1), Alaska Engr Dist (1); Los Angeles Engr Dist (1), New Orleans Engr Dist (1), New York Engr. Dist (1), Louisville Engr Dist (1), Pittsburgh Engr Dist (1), San Francisco Engr Dist (1). Omaha Engr Dist (1), Seattle Engr Dist (1), Kansas City Engr Dist (1), Baltimore Engr Dist (1), Ft Worth Engr Dist (1), Eastern Ocean Engr Dist (1), Philadelphia Engr Dist (1), Rock Island Engr Dist (1), St Louis Engr Dist (1), Philadelphia Engr Dist (1); Div Engr (2) except Lower Miss Valley Div (None); Engr Fld Maint Shops (2); Engr Dep Main Shops (2); USAERDL (3): Engr Cen (5); AMS (3); USA Engr Proc Ofc (10; EMC (10); Fld Comd, DASA (8); Def Log Sc Cen (10; USACOMZEUR (2): 5-114 (2); 5-237 (5); 5-267 (1); 5-278 (5); 5-279 (2); 6-627 (2); 8-187 (2); 9-377 (2); 9-510 (df, DG) (2); 39-51 (20: 55-225 (2); 55-227 (2); 55-227 (2); 55-247 (2); 55-500 (IE) (2). NG; State AG (3), USAR: Same as Active Army except allowance is one copy to each unit. For explanation of abbreviations used, see AR 320-50.

☆ U.S. GOVERNMENT PRINTNG OFFICE: 1986-490-998/40019