

DEPARTMENT OF THE ARMY TECHNICAL MANUAL

---

ORGANIZATIONAL MAINTENANCE REPAIR PARTS  
AND SPECIAL TOOLS LISTS  
TEST SET, TRANSISTOR TS-1836/U  
FSN 6625-893-2628

---

Headquarters, Department of the Army, Washington, D. C.  
29 June 1973

---

Current as of December 1972

	Paragraph	Page
Section I. INTRODUCTION		
Scope . . . . .	1-1	2
General . . . . .	1-2	2
Explanation of columns . . . . .	1-3	2
Special information . . . . .	1-4	4
Location of repair parts . . . . .	1-5	4
Abbreviations (Not applicable) . . . . .	1-6	4
Reporting of equipment publication improvements . . . . .	1-7	4
II. PRESCRIBED LOAD ALLOWANCE (Not applicable)		
III. REPAIR PARTS LIST . . . . .		6
IV. SPECIAL TOOLS, TEST AND SUPPORT EQUIPMENT ( Not applicable)		
V. INDEX -FEDERAL STOCK NUMBER AND REFERENCE NUMBER CROSS-REFERENCE TO FIGURE AND ITEM NUMBER . . . . .		7

---

\*This manual supersedes TM 11-6625-539-20P, 25 January 1963.

# SECTION I INTRODUCTION

## 1-1. Scope

This manual lists repair parts required for the performance of organizational maintenance of the TS-1836/U. The PCCN for the TS-1836/U is GTEACF for all models.

## 1-2. General

This repair parts list is divided into the following sections:

*a. Prescribed Load Allowance (PLA) — Section II.* Not applicable.

*b. Repair Parts List—Section III.* A list of repair parts authorized for the performance of maintenance at the organizational level. This repair parts list is arranged in alphabetical order.

*c. Special Tools, Test and Support Equipment — Section IV.* Not applicable.

*d. Index—Federal Stock Number and Reference Number Cross-Reference to Figure and Item Number — Section V.* A list, in ascending numerical sequence, of all Federal stock numbers appearing in the listings, followed by a list, in alphameric sequence, of all reference numbers appearing in the listings. Federal stock number and reference numbers are cross-referenced to each illustration figure and item number or reference designation appearance.

## 1-3. Explanation of Columns

The following provides an explanation of columns in the tabular lists—

*a. Source, Maintenance, and Recoverability Codes (SMR).*

(1) *Source code.* Indicates the manner of acquiring support items for maintenance, repair, or overhaul of end items. Source codes are—

Code	Explanation
------	-------------

PA	Item procured and stocked for anticipated or known usage.
----	---

PB	Item procured and stocked for insurance purposes because essentiality dictates that a minimum quantity be available in the supply systems.
----	--

PC	Item procured and stocked and which otherwise would be coded PA except that it is deteriorative in nature.
----	--

PD	Support item, excluding support equipment, procured for initial issue or outfitting and stocked only for subsequent or additional initial issues or outfitting. Not subject to automatic replenishment.
----	---

Code

Explanation

PE	— Support equipment procured and stocked for initial issue or outfitting to specified maintenance repair activities.
----	--

PF	– Support equipment which will not be stocked but which will be centrally procured on demand.
----	---

PG	Item procured and stocked to provide for sustained support for the life of the equipment. It is applied to an item peculiar to the equipment which because of probable discontinuance or shutdown of production facilities would prove uneconomical to reproduce at a later time.
----	---

KD	An item of depot overhaul/repair kit and not purchased separately. Depot kit defined as a kit that provides items required at the time of overhaul or repair.
----	---

KF	An item of a maintenance kit and not purchased separately. Maintenance kit defined as a kit that provides an item that can be replaced at organizational or direct support or general support levels of maintenance.
----	--

KB	– Item included in both a depot overhaul/repair kit and a maintenance kit.
----	--

MO	— Item to be manufactured or fabricated at organizational level.
----	--

MF	– Item to be manufactured or fabricated at direct support maintenance level.
----	--

MH	—Item to be manufactured or fabricated at general support maintenance level.
----	--

MD	— Item to be manufactured or fabricated at depot maintenance level.
----	---

AO	– Item to be assembled at organizational level.
----	---

AF	– Item to be assembled at direct support maintenance level.
----	---

AH	— Item to be assembled at general support maintenance level.
----	--

AD	— Item to be assembled at depot maintenance level.
----	--

XA	– Item is not procured or stocked because the requirements for the item will result in the replacement of the next higher assembly.
----	---

XB	— Item is not procured or stocked. If not available through salvage, requisition.
----	---

XC	– Installation drawing, diagram instruction sheet, field service drawing, that is identified by manufacturers' part number.
----	---

XD	– Support items can be requisitioned with justification.
----	--

**NOTE**

Cannibalization or salvage may be used as a source of supply for any items source coded above except those coded XA and aircraft support items as restricted by AR 700-42.

Code Explanation

(2) *Maintenance code.* Maintenance codes are assigned to indicate the levels of maintenance authorized to USE and REPAIR support items. The maintenance codes are entered in the third and fourth positions of the Uniform SMR Code Format as follows—

(a) *Use (third position).* The maintenance code entered in the third position indicates the lowest maintenance level authorized to remove, replace, and use the support item. The maintenance code entered in the third position indicates one of the following levels of maintenance.

Code Application/Explanation

O – Support item is removed, replaced, used at the organizational level of maintenance.

**NOTE**

A code “C” may be used in this position to denote crew or operator maintenance performed within organizational maintenance.

F – Support item is removed, replaced, used at the direct support maintenance level.

H – Support item is removed, replaced, used at the general support maintenance.

D – Support items that are removed, replaced, used at depot only.

(b) *Repair (fourth position).* The maintenance code entered in the fourth position indicates whether the item is to be repaired and identifies the lowest maintenance level with the capability to perform complete repair (i.e., all authorized maintenance functions). When a maintenance code is not used a dash (-) sign is entered. For multi-service equipment/systems or when a code is entered, this position will contain one of the following maintenance codes as assigned by the service(s) that require the code—

Code Application/explanation

O – The lowest maintenance level capable of complete repair of the support item is the organizational level.

F — The lowest maintenance level capable of complete repair of the support item is direct support.

H — The lowest maintenance level capable of complete repair of the support item is general support.

D — The lowest maintenance level capable of com -

plete repair of the support item is the depot level.

L – Repair restricted to designated Specialized Repair Activity.

Z – Non-repairable. No repair is authorized.

B – No repair is authorized. The item may be reconditioned by adjusting, lubricating, etc., at the user level. No parts or special tools are procured for the maintenance of this item.

(3) *Recoverability code.* Recoverability codes are assigned to support items to indicate the disposition action on unserviceable items. The recoverability code is entered in the fifth position of the uniform SMR Code Format as follows—

Code Explanation

Z – Nonrepairable item. When unserviceable, condemn and dispose at the level indicated in the first digit of the maintenance code.

O – Repairable item. When uneconomically repairable, condemn and dispose at organizational level.

F – Repairable item. When uneconomically repairable, condemn and dispose at the direct support level.

H – Repairable item. When uneconomically repairable, condemn and dispose at the general support level.

D – Repairable item. When beyond lower level repair capability, return to depot. Condemnation and disposal not authorized below depot level.

L – Repairable item. Repair, condemnation, and disposal not authorized below depot/Specialized Repair Activity level.

A — Item requires special handling or condemnation procedures because of specific reasons (i.e., precious metal content, high dollar value, critical material or hazardous material).

*b. Federal Stock Number.* Indicates the Federal stock number assigned to the item and will be used for requisitioning purposes.

*c. Description.* Indicates the Federal item name and a minimum description required to identify the item. The last line indicates the reference number followed by the applicable Federal Supply Code for Manufacturer (FSCM) in parentheses. The FSCM is used as an element in item identification to designate manufacturer or distributor or Government agency, etc., and is identified in SB 708-42.

*d. Unit of Measure (U/M).* Indicates the standard or basic quantity by which the listed item is used in performing the actual maintenance function. This

measure is expressed by a two-character alphabetical abbreviation; e.g., ea, in, pr, etc., and is the basis used to indicate quantities and allowances in subsequent columns. When the unit of measure differs from the unit of issue, the lowest unit of issue that will satisfy the required units of measure will be requisitioned.

*e. Quantity Incorporated in Unit.* This column indicates the quantity of the item used in the equipment.

*f. 15-Day Organizational Maintenance Allowance.*

(1) The repair parts indicated by an asterisk in the allowance column represent those authorized for use at the organizational category, and will be requisitioned on an "as required" basis, until stockage is based on demand in accordance with AR 710-2.

(2) Major Army commanders are authorized to approve reduction in the range of support items authorized for use in units within their commands. Recommendations for increase in range of items authorized for use will be forwarded to Commander, US Army Electronics Command, ATTN: AMSEL-MACRA, Fort Monmouth, N.J., 07703. Any changes approved will be reflected in a revision to the RPSTL.

(3) Allowance quantities are indicated in the special tools list section for special tools, TMDE, and other equipment.

*g. Illustration.* This column is divided as follows:

(1) *Figure number.* Indicates the figure number of the illustration on which the item is shown in TM 11-6625-539-15.

(2) *Item number.* Indicates the item number or reference designation used to reference the item in the illustration.

## 1-4. Special Information

*a.* Usable on codes are included in column 3. Uncoded items are applicable to all models. Identification of the usable on codes used in this publication are—

<i>Code</i>	<i>Used on</i>
AM7	TS-1836/U

*b.* The following publication pertains to the TS-1836/U and its components:

TM 11-6625-539-15 Operator, Organizational, Field and Depot Maintenance Manual: Transistor Test Set TS-1836/U.

## 1-5. Location of Repair Parts

*a.* This manual contains one cross-reference index (see V) to be used to locate a repair part when either the Federal stock number or reference number (manufacturer's part number) is known. The first column in the index is prepared in numerical or alphanumeric sequence in ascending order. The reference numbers (manufacturer's part numbers) are listed immediately following the last listed Federal stock number in the index of Federal stock numbers.

*b.* When the Federal stock number or reference number is known, follow the procedures given in (1) and (2) below.

(1) Refer to the index of Federal stock numbers (see V) and locate the Federal stock number or reference number. The FSN and reference number are cross-referenced to the applicable figure and item number or reference designation.

(2) Refer to the repair parts list (see III) and locate the figure number (col 7a) and item number or reference designation (col 7b) as noted in the FSN index.

*c.* When the figure and item number or reference designation are known, scrutinize columns 7a and 7b of the repair parts list (see III) until the item is located.

*d.* When the FSN, reference number, figure number, item number and reference designation are not known, scrutinize column 3 of the repair parts list (see III), which is arranged in alphabetical order.

## 1-6. Abbreviations

Not applicable.

## 1-7. Reporting of Equipment Publication Improvements

The reporting of errors, omissions, and recommendations for improving this publication by the individual user is encouraged. Reports should be submitted on DA Form 2028 (Recommended Changes to Publications) and forwarded direct to Commander, US Army Electronics Command, ATTN: AMSEL-MACRA, Fort Monmouth, N.J., 07703.

(Next printed page is 6.)



SECTION II

(1)	(2)	(3)		(4)	(5)	(6)				(7)	
SMR	FEDERAL STOCK	DESCRIPTION		UNIT OF MEAS	QTY INC	15-DAY ORGANIZATIONAL MAINTENANCE ALW				ILLUSTRATION	
CODE	NUMBER	REFERENCE NUMBER & MFR CODE	USABLE ON CODE		IN	(A)	(B)	(C)	(D)	FIGURE NO	(B) ITEM NO
PAOZZ	6625-329-2595	DATA BOOK NO-REF-DESIG TEST TABLES AND TRANSISTOR TEST OUTLINES 9501000003 (94668)		EA	1	*	*	*	*		
PAOZZ	5355-667-9099	KNOB NO-REF-DESIG POINTER SHAPE 70-5-2G (99687)		EA	3	*	*	*	*		
PAOZZ	5355-284-5514	KNOB NO-REF-DESIG RD SHAPE 70-2-2G (99687)		EA	1	*	*	*	*		
PAOZZ	6240-228-7130	LAMP, INCANDESCCENT 1.3V, 0.06 AMP 331 (08108)	DS1	EA	1	*	*	*	*	1-3	DS1
PAOZZ	6135-473-6278	BATTERY DRY MERCURY TYPE (SPECIAL) SB12459-2 (94668)	BT1	EA	1	*	*	*	*		
PAOZZ	6135-473-6279	BATTERY DRY MERCURY TYPE (SPECIAL) SB12460-2 (94668)	BT2	EA	1	*	*	*	*		
PAOZZ	5995-857-2830	CABLE ASSEMBLY, SPECIAL PURPOSE, ELECTRICAL SP13741-3-1 (94668)		EA	1	*	*	*	*		W1
PAOZZ	5995-857-2831	CABLE ASSEMBLY, SPECIAL PURPOSE, ELECTRICAL SP13741-3-2 (94668)		EA	1	*	*	*	*		W2

SECTION V

INDEX - FEDERAL STOCK NUMBER AND REFERENCE NUMBER  
 CROSS-REFERENCE TO FIGURE AND ITEM NUMBER

STOCK NUMBER	FIGURE NO.	ITEM NO.	STOCK NUMBER	FIGURE NO.	ITEM NO.
5355-284-5514			6135-473-6278		
5355-667-9099			6135-473-6279		
5995-857-2830		W1	6240-228-7130	1-3	DS1
5995-857-2831		W2	6625-329-2595		

REFERENCE NO.	MFR CODE	FIG. NO.	ITEM NO.	REFERENCE NO.	MFR CODE	FIG. NO.	ITEM NO.
SB12459-2	94668			331	08108	1-3	DS1
SB12460-2	94668			70-2-2G	99687		
SP13741-3-1	94668		W1	70-5-2G	99687		
SP13741-3-2	94668		W2	950100003	94668		

By Order of the Secretary of the Army:

**CREIGHTON W. ABRAMS**  
*General, United States Army*  
*Chief of Staff*

Official:

**VERNE L. BOWERS**

**Major General, United States Army**  
*The Adjutant General*

Distribution:

*Active Army:*

USASA (2)  
CNGB (1)  
ACSC-E (2)  
USAARENBD (2)  
USAMB (10)  
AMC (1)  
CONARC (5)  
ARADCOM (2)  
ARADCOM Rgn (2)  
OS Maj Cored (4)  
LOGCOMDS (5)  
MICOM (2)  
TECOM (2)  
USA STRATCOM (4)  
HISA (ECOM)(18)  
MDW (1)  
Armies(2)  
Corps(2)  
Svc Colleges (2)  
USASESS (5)  
USAADS (2)  
USAFAS (2)  
USAARMS (2)  
USAIS (2)  
USAES (2)  
USAINTS (3)

NG: State AG (3)

*USAR: None*

For explanation of abbreviations used, see AR 310-50.

USACDCEC (5)  
Instl (2) except  
Ft Gordon (10)  
Ft Huachuca(10)  
WSMR (2)  
Ft Carson (10)  
Army Dep (2) except  
LBAD (14)  
SAAD(30)  
TOAD (14)  
LEAD (7)  
ATAD (10)  
Gen Dep (2)  
Sig Sec Gen Dep (2)  
Sig Dep (5)  
Sig FLDMS (1)  
USAERDAA (1)  
USAERDAW (1)  
MAAG (1)  
USARMIS (1)  
Ft Richardson (ECOM Ofc) (2)  
WRAMC (1 )  
Units org under fol TOE:  
( 1 cy each)  
11-1.58  
29-134  
29-136



RECOMMENDED CHANGES TO EQUIPMENT TECHNICAL PUBLICATIONS



THEN...JOT DOWN THE  
DOPE ABOUT IT ON THIS FORM.  
CAREFULLY TEAR IT OUT, FOLD IT  
AND DROP IT IN THE MAIL.

SOMETHING WRONG WITH PUBLICATION

FROM: (PRINT YOUR UNIT'S COMPLETE ADDRESS)

DATE SENT

PUBLICATION NUMBER

PUBLICATION DATE

PUBLICATION TITLE

BE EXACT PIN-POINT WHERE IT IS

PAGE  
NO.

PARA-  
GRAPH

FIGURE  
NO.

TABLE  
NO.

IN THIS SPACE, TELL WHAT IS WRONG  
AND WHAT SHOULD BE DONE ABOUT IT.

TEAR ALONG PERFORATED LINE

PRINTED NAME, GRADE OR TITLE AND TELEPHONE NUMBER

SIGN HERE

# THE METRIC SYSTEM AND EQUIVALENTS

## WEIGHT MEASURE

1 Centimeter = 10 Millimeters = 0.01 Meters = 0.3937 Inches  
 1 Meter = 100 Centimeters = 1000 Millimeters = 39.37 Inches  
 1 Kilometer = 1000 Meters = 0.621 Miles

## WEIGHTS

1 Gram = 0.001 Kilograms = 1000 Milligrams = 0.035 Ounces  
 1 Kilogram = 1000 Grams = 2.2 lb.  
 1 Metric Ton = 1000 Kilograms = 1 Megagram = 1.1 Short Tons

## LIQUID MEASURE

1 Milliliter = 0.001 Liters = 0.0338 Fluid Ounces  
 1 Liter = 1000 Milliliters = 33.82 Fluid Ounces

## SQUARE MEASURE

1 Sq. Centimeter = 100 Sq. Millimeters = 0.155 Sq. Inches  
 1 Sq. Meter = 10,000 Sq. Centimeters = 10.76 Sq. Feet  
 1 Sq. Kilometer = 1,000,000 Sq. Meters = 0.386 Sq. Miles

## CUBIC MEASURE

1 Cu. Centimeter = 1000 Cu. Millimeters = 0.06 Cu. Inches  
 1 Cu. Meter = 1,000,000 Cu. Centimeters = 35.31 Cu. Feet

## TEMPERATURE

$5/9(^{\circ}\text{F} - 32) = ^{\circ}\text{C}$   
 212° Fahrenheit is equivalent to 100° Celsius  
 90° Fahrenheit is equivalent to 32.2° Celsius  
 32° Fahrenheit is equivalent to 0° Celsius  
 $9/5^{\circ}\text{C} + 32 = ^{\circ}\text{F}$

## APPROXIMATE CONVERSION FACTORS

TO CHANGE	TO	MULTIPLY BY
Inches	Centimeters	2.540
Feet	Meters	0.305
Yards	Meters	0.914
Miles	Kilometers	1.609
Square Inches	Square Centimeters	6.451
Square Feet	Square Meters	0.093
Square Yards	Square Meters	0.836
Square Miles	Square Kilometers	2.590
Acres	Square Hectometers	0.405
Cubic Feet	Cubic Meters	0.028
Cubic Yards	Cubic Meters	0.765
Fluid Ounces	Milliliters	29.573
its	Liters	0.473
arts	Liters	0.946
allons	Liters	3.785
Ounces	Grams	28.349
Pounds	Kilograms	0.454
Short Tons	Metric Tons	0.907
Pound-Feet	Newton-Meters	1.356
Pounds per Square Inch	Kilopascals	6.895
Miles per Gallon	Kilometers per Liter	0.425
Miles per Hour	Kilometers per Hour	1.609

TO CHANGE	TO	MULTIPLY BY
Centimeters	Inches	0.394
Meters	Feet	3.280
Meters	Yards	1.094
Kilometers	Miles	0.621
Square Centimeters	Square Inches	0.155
Square Meters	Square Feet	10.764
Square Meters	Square Yards	1.196
Square Kilometers	Square Miles	0.386
Square Hectometers	Acres	2.471
Cubic Meters	Cubic Feet	35.315
Cubic Meters	Cubic Yards	1.308
Milliliters	Fluid Ounces	0.034
Liters	Pints	2.113
Liters	Quarts	1.057
ers	Gallons	0.264
ms	Ounces	0.035
ograms	Pounds	2.205
Metric Tons	Short Tons	1.102
Newton-Meters	Pounds-Feet	0.738
Kilopascals	Pounds per Square Inch	0.145
ometers per Liter	Miles per Gallon	2.354
ometers per Hour	Miles per Hour	0.621



**PIN: 017256-000**