

AIR PUBLICATION 1086
BOOK 4 (i)

SECTION 10C

**RADIO CAPACITORS CHOKES
AND INDUCTANCES**

Items under Section 10C are covered by
VOTE 7 C. 1

EHA

George

*70.35
2.9
17.450*

- 2.9

9-6357

RESTRICTED

AMENDMENT LISTS CONCERNING SECTION 10G

The amendments promulgated in the undermentioned Amendment Lists have been inserted.

Amendment List		Inserted by	Date
No.	Date		
Amendment Lists No. 1-37 incorporated.			

RESTRICTED

RESTRICTED

AIR PUBLICATION 1086 BOOK 4 (i)

**VOCABULARY OF ROYAL AIR FORCE EQUIPMENT
RADIO CHOKES AND CONDENSERS**

SECTION 10C

(24th January, 1947)

VOTE 3 B. 4

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty
1	2	3	4	5	6	7
—	CHOKES:—		Army			
—	Aerial	ZA.3155/9	A	each	—
—	A.F.:—					
—	No. 106	2 henries at 0.35 amp. D.C.; open type, 4 in. × 3.75 in. × 5.75 in. high, with terminal block.	ZA. 14613	A	..	—
—	No. 107	40 henries at 0.5 amp. D.C.; open type, 4 in. × 3.75 in. × 5.75 in. high, with terminal block.	ZA. 14614	A	..	—
—	No. 117	ZA. 15378	A	..	—
—	H.F.:—					
—	200 μH	ZA. 15377	A	..	—
—	250 μH	Wire ends	Naval 53555	A	..	—
8482	Type 17	Cylindrical former, 2 in. diam., with three winding slots.		A	..	1
8483	Type 18	Cylindrical former, 2 in. diam., with three winding slots.		A	..	1
8484	Type 19	Cylindrical former, $\frac{3}{8}$ in. diam., with 10 winding slots.		A	..	2
8485	Type 20	Cylindrical former, 7 in. × 1½ in. H.T.		A	..	1
8486	Type 21	Cylindrical former, 4½ in. × ½ in. L.T.		A	..	1
8716	Type 22	Paxolin former pancake winding		A	..	1
8718	Type 24	Cylindrical former, wire wound, twin chokes		A	..	1
8682	Type 28	45,000 microhenries. Slotted former, with end caps.		A	..	1
9206	Type 34	Cylindrical former, 2½ in. × ½ in.		A	..	1
9514	Type 35	Cylindrical former, 1½ in. long × 1 in. diam., wire wound.		A	..	1
10117	Type 37		A	..	1
10504	Type 41	Cylindrical former, 2½ in. × 1 in. diam., with 14 slots.		A	..	1
10505	Type 42	Cylindrical former, 2½ in. × 1 in. diam., with 14 slots.		A	..	1
10986	Type 43	Spider former, air spaced winding		A	..	1
11393	Type 44	Crystal monitor, Type 2 ...		A	..	3
11341	Type 45	Attached to coil, master oscillator, range.		A	..	1
11601	Type 46	120 turns		A	..	1
11603	Type 47	110 turns		A	..	1
11604	Type 48	244 turns		A	..	1
11605	Type 49	64 turns		A	..	2
49	Type 50	50 turns		A	..	3
79	Type 53	1.5 millihenries, 4 banks, on ½ in. dia. × 1½ in. former.		A	..	2
80	Type 54	1.25 millihenries, 4 banks, on ½ in. dia. × 1½ in. former.		A	..	2
216	Type 56	L.T., half supporting		A	..	1
217	Type 57	H.T. former, wound		A	..	1

RADIO CHOKES AND CONDENSERS

Ref No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Wty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
285	Type 58		A	each	1
249	Type 60 ...	Inductance, 125 microhenries ...		A	"	1
384	Type 62		A	"	1
385	Type 63		A	"	1
386	Type 64		A	"	1
387	Type 65		A	"	1
401	Type 66 ...	Steatite, former 5 metres ...		A	"	2
447	Type 67 ...	210,000 microhenries, 330 ohms		A	"	1
482	Type 68 ...	210,000 microhenries, 330 ohms, with canister.		A	"	1
431	Type 69 ...	Wave wound, wax coated ...		A	"	1
578	Type 70 ...	8.8 microhenries ± 10 per cent. Bakelite moulding.		A	"	1
583	Type 71 ...	250 microhenries, 630 ohms, D.C.		A	"	1
717	Type 72		A	"	1
718	Type 73		A	"	1
719	Type 74		A	"	1
721	Type 76		A	"	1
845	Type 77 ...	200 microhenries ...		A	"	1
849	Type 78		A	"	1
850	Type 79		A	"	2
880	Type 80 ...	Winding in 5 sections. Inductance 3.8 microhenries, at 1,000 cycles, D.C., resistance 660 ohms. Paxolin former, $2\frac{1}{2}$ in. \times $\frac{1}{2}$ in. dia. Tag connections.		A	"	2
866	Type 81 ...	Heater Inductance 15 microhenries, approx. at 1,000 cycles, D.C. Resistance .02 ohms (approx.). Tufnol former 3 in. \times 1 in. dia.		A	"	2
902	Type 82 ...	Heater resistance 0.72 ohms. Inductance 7-8 millihenries at 1,000 cycles.		A	"	1
2019	Type 83 ...	6.7 mH, 135 ohms D.C. resistance; moulded former, $1\frac{1}{2}$ in. \times $\frac{3}{8}$ in. dia.; aluminium screening can, 1 in. dia. \times $1\frac{1}{2}$ in. high; tags through top of screen.		A	"	1
2087	Type 88 ...	8.8 millihenries ± 10 per cent.		A	"	1
836	Type 89 ...	Heater, .2 ohm ...		A	"	1
837	Type 90 ...	Heater, .1 ohm ...		A	"	1
2135	Type 91 ...	Anode connection, 6.8 microhenries $\pm 2\frac{1}{2}$ per cent., D.C. Resistance 1,100 ohms ± 5 per cent. Eight pancake windings on $2\frac{3}{4}$ in. \times $\frac{1}{2}$ in. diam. Paxolin former.		A	"	1
2185	Type 93 ...	5.6 mH, 1.3 ohms D.C. resistance, tubular wire end connections.	Army ZC.1033	A	"	2
2186	Type 94 ...	6.7 mH, 135 ohms D.C. resistance; moulded former, $1\frac{1}{2}$ in. \times $\frac{3}{8}$ in. dia. Aluminium screening can, $1\frac{1}{2}$ in. \times 1 in. dia. Tags through bottom of screen.		A	"	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
2232	Type 95 ...	Large tubular ...		A	each	1
2233	Type 96 ...	Large tubular ...		A	"	1
2234	Type 97 ...	Small tubular ...		A	"	2
2235	Type 98 ...	Spools, moulded bakelite ...		A	"	1
2236	Type 99 ...	With iron core cemented in ...		A	"	1
2299	Type 100 ...	Wound on porcelain tubular core, with terminal stud each end. Fitted with 2 nuts one end and 4 nuts the other end.		A	"	1
3804	Type 101 ...	Wound on porcelain tubular core, with terminal stud each end. Each fitted with 2 nuts.		A	"	1
3805	Type 102 ...	Wound on porcelain tubular core, with terminal stud each end. Fitted with 2 nuts one end and 1 nut the other end.		A	"	1
2360	Type 104 ...	1.25 microhenries, 22 ohms ...		A	"	1
2361	Type 105		A	"	1
2268	Type 106 ...	Air dielectric, 2 × 1,350 turns, double wound, 36 S.W.G. Fixing through centre of coil.		A	"	1
2269	Type 107 ...	Air dielectric, 1,000 turns. Centre top fixing through centre coil.		A	"	1
2378	Type 108 ...	Air dielectric, 2 × 600 turns. Centre top fixing through centre coil.		A	"	1
2585	Type 114 ...	2.5 millihenries. Variable iron dust core.		A	"	1
2593	Type 115 ...	Coiled electro-plated copper tube		A	"	1
2594	Type 116 ...	Coiled electro-plated copper tube		A	"	1
2270	Type 117 ...	S.W. Intermediate frequency		A	"	1
2701	Type 118		A	"	1
2736	Type 121 ...	Large tubular ...		A	"	1
2737	Type 122 ...	Large tubular ...		A	"	1
2762	Type 123 ...	Four microhenries, 1½ in. diam. × ⅝ in. Centre hole fixing.		A	"	2
2773	Type 124 ...	520 microhenries ± 5 per cent. Overall size ¾ in. × ½ in. diam.		A	"	2
2847	Type 126 ...	45 turns of 16 S.W.G. E. and S.C.C. wire. Wound on Tufnol former, 1½ in. × 1 in. diam.		A	"	1
2849	Type 127 ...	Heater, -130 ohms D.C. resistance (approx.). Tufnol former, 1½ in. × ½ in. × ½ in.		A	"	2
2850	Type 128 ...	Heater, -130 ohms D.C. resistance (approx.). Tufnol former, 1½ in. × ½ in. × ½ in.		A	"	2
2859	Type 129 ...	1.28 millihenries, 4 banks, Lessona wound, on ¼ in. former, 2 in. long.		A	"	1
2942	Type 132 ...	Less brackets (Detail 12, T.G. 17730).		A	"	2
2944	Type 133 ...	Anode ...		A	"	1
2953	Type 136 ...	105 microhenries ± 15 per cent.		A	"	1
2954	Type 137		A	"	1
3008	Type 138		A	"	1
3220	Type 150 ...	Filament choke ...		A	"	1
3221	Type 151		A	"	1
3223	Type 153		A	"	1
3224	Type 154 ...	Dust, iron core ...		A	"	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
3225	Type 155	... 2,940 microhenries, 2,360 microhenries, 1,300 microhenries, tapped.		A	each	1
3228	Type 158	... 17,000 microhenries, 110/230 volts, D.C., resistance 3 ohms. Impedance at 200 M=9,600 ohms. Impedance at 4,000 M=8,000 ohms. Self capacity .000011 mfd.		A	"	1
3425	Type 161	... I.F., 460 kc/s adjustable iron dust core.		A	"	1
10622	Type 162		A	"	—
10625	Type 164		A	"	—
3427	Type 181	... 1.5 millihenries, 10 ohms		A	"	—
3524	Type 183	... Wavewound dust iron core, 0.17 amp. D.C. Mult-section 5 m/H.		A	"	1
3570	Type 184	... L.T. filter, 1 $\frac{7}{8}$ in. \times $\frac{3}{4}$ in. diam., 30 turns 20 S.W.G. enamelled copper wire.		A	"	1
3590	Type 185	... 2 microhenries, 21 turns of 30 D.S.C. copper on bakelite former, $\frac{1}{4}$ in. diam.		A	"	1
3806	Type 197	... Cylindrical former wound with 16 turns of 23 S.W.G. enamelled copper wire.		A	"	2
3807	Type 198		A	"	1
3808	Type 199	... 1.25 \pm 10% millihenries, 22 ohms \pm 10%, D.C., resistance.		A	"	1
3809	Type 200	... 15.5 microhenries \pm 15%. Resistance 65-70 ohms.		A	"	1
3899	Type 202	... Heater choke, 0.17 ohms, approximately.		A	"	2
3977	Type 205	... 2,000 microhenries. Wound 4 slots on polystyrene former, $\frac{1}{2}$ in. diam. \times 1 $\frac{1}{8}$ in.		A	"	1
3979	Type 207	... Filament, choke, 1 millihenry ..		A	"	1
4064	Type 208		A	"	1
4065	Type 209		A	"	1
4066	Type 210		A	"	1
4067	Type 211		A	"	1
4068	Type 212		A	"	1
4069	Type 213		A	"	1
4070	Type 214		A	"	1
4092	Type 219	... 500 millihenries. Sectionalised, pile wound; 38 S.W.G. copper wire, D.C. resistance 9 ohms, loaded ebonite former.		A	"	1
4093	Type 220	... 8.4 millihenries. Sectionalised, pile wound; 26 S.W.G. copper wire, D.C. resistance .25 ohms, loaded ebonite.		A	"	1
4094	Type 221	... Heater, .2 ohms		A	"	1
4132	Type 225	... H.T. smoothing choke, 1,000 volts, 2,000 turns of 33 S.W.G.		A	"	1
4147	Type 226	... H.T. smoothing choke, 300 volts, laminated iron core, 2,800 turns of 35 S.W.G.		A	"	1
4150	Type 229	... Tuning; copper strip on paxolin former.		A	"	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
4152	Type 231 ...	Approx. 85 microhenries, 195 turns of 41 S.W.G. wire on bakelite former.		A	each	1
4153	Type 232 ...	3 windings of 40 turns of 22 S.W.G. wire on Tufnol former.		A	..	1
4160	Type 236 ...	Insulating rod, wound with 24 turns of 30 S.W.G. wire, pin connections.		A	..	1
4161	Type 237 ...	Eddystone 1010 modified by Ferranti Ltd.		A	..	1
4288	Type 24115 microhenries, 2 slab ...		A	..	1
4362	Type 248		A	..	1
4461	Type 251		A	..	1
4464	Type 254 ...	Mains		A	..	2
4517	Type 255 ...	Wound on Tufnol former, $\frac{3}{8}$ in. dia.; 30 turns approx. of 23 S.W.G. en. cu. wire, close wound.		A	..	2
4599	Type 263 ...	26 μ H, 21 turns 18 S.W.G. Choke windings, 4 layers single silk enamel C. wire, coated with varnish. 1 in. dia. \times 1 $\frac{1}{4}$ in. app. tags.		A	..	1
4848	Type 272 ...	Special		A	..	1
4849	Type 273 ...	Special		A	..	1
4851	Type 274		A	..	1
5015	Type 276 ...	Inductance, 1.5 m/H. Wire, 28 S.W.G. B.E.S.S.C. Wave-wound 4 sections on ceramic former, 6 ohms, D.C.		A	..	1
5017	Type 278 ...	2 coils, each 105 turns of .0075 in. diam. enamelled and silk-covered copper wire on $\frac{1}{2}$ in. diam. paxolin tube.		A	..	1
5065	Type 279		A	..	1
5066	Type 280		A	..	1
5069	Type 283 ...	Former, 1.25 in. \times .5 in., 3 sections, 200 turns each 40 S.W.G.		A	..	1
5070	Type 284 ...	R.F. plate, former 2 $\frac{1}{8}$ in. \times .5 in. 2 sections, 135 and 120 turns 40 S.W.G.		A	..	1
5072	Type 286 ...	Heater choke, 50 ohms approx. resistance.		A	..	1
5090	Type 287		A	..	1
5094	Type 292 ...	Resonant to 200 Mc./s paxolin rod, wound enamel wire, tags.		A	..	1
5277	Type 301 ...	Ringling		A	..	1
5285	Type 305 ...	24 turns of 26 S.W.G. enamelled wire, paxolin former, $\frac{1}{2}$ in. dia. \times 1 $\frac{1}{8}$ in.		A	..	2
5287	Type 306 ...	24 turns of 26 S.W.G. enamelled wire on Tufnol former, $\frac{1}{2}$ in. dia. \times 1 $\frac{1}{4}$ in., wire ends for connection mounting.		A	..	2
5343	Type 307 ...	Loaded ebonite rod, $\frac{3}{8}$ in. \times $\frac{1}{2}$ in., wound with 14 turns S.W.G. wire.		A	..	2
3592	Type 310 ...	Heater choke; 1.3 microhenries, 15 turns, 22 D.C.C. copper.		A	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
5615	Type 322 ...	12 slots, 36 S.W.G. enamelled Eureka wire. All wound in same direction.		A	each	1
5616	Type 323 ...	12 slots, 120 turns, 39 S.W.G. en. Eureka wire. All wound in same direction.		A	..	1
5619	Type 326 ...	100 microhenries at 50 mA. ...		A	..	1
5611	Type 328 ...	Moulded former, screwed internally for core.		A	..	1
5613	Type 329 ...	5 turns of .018 in. en. copper wire on 50 ohms $\frac{1}{2}$ watt resistance.		A	..	2
5614	Type 330 ...	9 turns of .018 in. en. copper wire on 50 ohms $\frac{1}{2}$ watt resistance.		A	..	2
5741	Type 332 ...	1.3 mH, 22 turns of 30 S.W.G., equally spaced between pins on $\frac{5}{8}$ in. dia. former; bakelite varnish over windings.		A	..	2
5743	Type 334 ...	20 turns of 20 S.W.G. D.S.C. wire on $\frac{5}{8}$ in. former.		A	..	2
5847	Type 335		A	..	1
5849	Type 336 ...	150 turns, 37 S.W.G. en. Lessona wound, 1 bank on former, $\frac{1}{4}$ in. dia. \times $1\frac{1}{4}$ in.		A	..	2
5910	Type 337 ...	296 turns of 38 S.W.G. en. and S.S.C. copper wire, wound in four sections; inductance, 270 millihenries \pm 5%.		A	..	1
5914	Type 341		A	..	1
11144	Type 348		A	..	1
11149	Type 350 ...	75 turns 30 S.W.G. en. cu. wire on $\frac{1}{2}$ in. former.		A	..	1
11227	Type 356 ...	30 S.W.G. en. cu. on bakelite former.		A	..	1
11236	Type 358 ...	20 turns in one inch on S.R.B.P. grooved former, $\frac{1}{4}$ in. dia. \times 1.25 in. long, with mounting clamp at end.		A	..	1
11326	Type 363 ...	Inductance, 2,600 μ H. Open. Air cooled, 6 wave-wound coils on silvonite former, with brackets.		A	..	1
11330	Type 367 ...	30 turns 24 S.W.G. en. cu. wire, $\frac{1}{4}$ in. dia. \times $1\frac{1}{2}$ in., end wires.		A	..	1
11331	Type 368 ...	800 mH, 20 mA, 3 windings, each 180 turns of 38 S.W.G. E S.S.C.		A	..	1
11298	Type 370 ...	130 mH		A	..	1
11314	Type 371 ...	Wire-wound, 14 turns 20 gauge E.C. on Tufnol former, 2 in. \times $\frac{1}{4}$ in. dia.		A	..	2
11336	Type 372 ...	25 turns 30 S.W.G. enamelled, close-wound, on 2.12 in. \times $\frac{1}{4}$ in. dia. Tufnol rod.		A	..	1
11345	Type 373 ...	Winding, 23 turns of 26 S.W.G. en. cu. wire on $\frac{5}{8}$ in. former.		A	..	2
11346	Type 374 ...	19 turns of 20 S.W.G. en. cu. wire, $\frac{1}{4}$ in. dia. \times 1 in. long.		A	..	2

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ret	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
11432	Type 375 ...	Spool, $\frac{11}{16}$ in. dia. \times $1\frac{1}{8}$ in. long, with 3 collars, $1\frac{1}{8}$ in. dia. \times $\frac{1}{8}$ in., spaced $\frac{1}{2}$ in. apart. Wound with 2,210 turns of 36 S.W.G. Inductance 67 mH \pm 10%.		A	each	1
11433	Type 376 ...	As "Type 375" but with 2,000 turns; inductance, 52 mH \pm 10%.		A	"	1
11435	Type 377 ...	18 turns of 38 S.W.G. en. cu. wire on $\frac{5}{16}$ in. former.		A	"	2
11436	Type 378 ...	40 turns of 30 S.W.G. en. cu. wire on $\frac{5}{16}$ in. former.		A	"	2
11440	Type 379 ...	24 turns of 32 S.W.G. en. wire on $\frac{1}{4}$ in. dia. ins. former \times $\frac{7}{8}$ in. long.		A	"	2
11447	Type 380 ...	Wave-wound, 5 sections, 400 turns each, 36 S.W.G. D.S.C. copper, on Tufnol rod, $3\frac{1}{4}$ in. \times $\frac{5}{8}$ in. dia.		A	"	1
11448	Type 381 ...	Wave-wound, 3 sections, 400 turns each, 36 S.W.G. D.S.C. copper, on Tufnol rod, $2\frac{11}{16}$ in. \times $\frac{5}{8}$ in. dia.		A	"	1
11452	Type 382 ...	Suppressor choke, $24\frac{1}{2}$ turns of 22 S.W.G. copper D.S.C. on loaded ebonite former, $2\frac{1}{8}$ in. long; wire ends.		A	"	1
11528	Type 383 ...	Copper strip, double right-angled, $\frac{3}{32}$ in. wide; length, $1\frac{1}{8}$ in.; length before winding, 2.735 in.		A	"	2
11529	Type 384 ...	U-shape copper strip, $\frac{1}{16}$ in. wide; length before bending, 2.735 in.		A	"	1
11530	Type 385 ...	10 turns 1 mm. en. cu. wire, $1\frac{1}{2}$ mm. pitch; internal dia., 8 mm.		A	"	1
11592	Type 386 ...	I.F. grid, 20 turns 37 S.W.G. S.S. enamelled, $\frac{1}{2}$ wave-wound. Moulded former, $\frac{3}{8}$ in. dia. \times $\frac{5}{8}$ in., flanged, tapped 6 B.A. for fixing screws.		A	"	2
11593	Type 387 ...	I.F. diode, 180 turns 37 S.W.G. S.S. en. cu wire, $\frac{1}{2}$ wave-wound; moulded former, $\frac{3}{8}$ in. dia. \times $\frac{5}{8}$ in., flanged; tapped 6 B.A. for fixing screws.		A	"	2
11594	Type 388 ...	100 turns 40 S.W.G. S.S. en. cu. wire on moulded former, 0.375 in. dia. \times $1\frac{1}{16}$ in. long, 4 B.A. insert at end.		A	"	2
11617	Type 389 ...	95 turns 37 S.W.G. S.S. en., $\frac{1}{2}$ wave-wound; moulded former, $\frac{3}{8}$ in. dia. \times $\frac{5}{8}$ in., with flange at each end.		A	"	2
11612	Type 390 ...	15 turns 1 mm. en. cu. wire, $1\frac{1}{2}$ mm. pitch; internal dia., 8 mm.		A	"	—
11639	Type 393 ...	I.F. filter, moulded former (C. 12098).		A	"	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ret	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
11738	Type 395 ...	Wound 170 turns per coil on former, 2.25 in. × 0.75 in. dia.; frequency, 10 kc/s.; inductance, 1,160 microH.		A	each	1
11793	Type 397 ...	$\frac{3}{16}$ in. dia. copper rod, 3 turns, $\frac{3}{8}$ in. pitch, $1\frac{1}{8}$ in. i/d, with tapping connection hole, tapped 4 B.A.		A	..	1
11794	Type 398 ...	$\frac{3}{16}$ in. dia. copper rod, 3 turns, $\frac{3}{8}$ in. pitch, $1\frac{1}{8}$ in. i/d, with tapping connection hole, 0.161 in. dia.		A	..	1
11821	Type 399 ...	70 turns 40 S.W.G. E.C. wire, $1\frac{1}{2}$ in. long × $\frac{3}{8}$ in. dia., end wires. (R.F.)		A	..	2
11822	Type 400 ...	40 S.W.G. en. Eureka wire, $\frac{1}{4}$ in. dia. bakelite former; 20 turns of 28 S.W.G. en. cu. wire.		A	..	2
11842	Type 404 ...	260 turns 36 S.W.G. S.C.C., wave-wound, $\frac{7}{16}$ in. former.		A	..	1
11844	Type 406 ...	20 microH., 74 turns of 16 S.W.G. en. wire, pile wound, $\frac{5}{16}$ in. former.		A	..	1
11848	Type 407 ...	$5\frac{1}{2}$ turns 16 S.W.G. wire. Left-hand. Bare T. cu wire, $\frac{3}{8}$ in. i/d, air spaced.		A	..	1
11850	Type 409 ...	172 turns of No. 30 S.W.G., close wound in $\frac{1}{2}$ in. dia. bakelite rod × 7 in. long tags.		A	..	1
11862	Type 410 ...	$\frac{3}{8}$ in. dia. ebonite former, with 23 turns of 22 S.W.G. en. cu. wire.		A	..	2
11871	Type 412 ...	1 coil, 15 turns 22 S.W.G. en. wire on former, loaded ebonite, $\frac{1}{4}$ in. × $3\frac{1}{8}$ in. long; ends tapped 6 B.A.		A	..	2
11872	Type 413 ...	2 coils, 15 turns 22 S.W.G. en. wire on former, loaded ebonite, $\frac{1}{4}$ in. dia. × $3\frac{1}{8}$ in. long; ends tapped 6 B.A.		A	..	2
11874	Type 414 ...	100 mA multi-section, wave-wound 1.4 to 6 Mc/s.		A	..	1
11875	Type 415 ...	D.C., 1.5 amp., multi-section wave-wound, 100 Kc/s., 1.2 Mc/s.; resistance, 2.2 ohms.		A	..	1
11897	Type 416 ...	Leesona wound coil, 374 turns of 38 S.W.G. D.W.S. cu. wire on S.R.B.P. tubular former (A.16635).		A	..	1
11962	Type 421 ...	74 turns 30 S.W.G. en. cu. wire on $1\frac{7}{16}$ in. × $\frac{3}{8}$ in. former.		A	..	1
11963	Type 422 ...	85 microH, 195 turns 41 S.W.G. Eureka en. wire, 3 slots, 65 turns each, on 1 in. × $\frac{1}{4}$ in. dia. former.		A	..	1
11964	Type 423 ...	8 tappings, 7 sections, 44 turns each, 20 S.W.G. en. cu. wire, on former, 15 in. long × $\frac{5}{16}$ in. dia.		A	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
11968	Type 424 ...	Tufnol former, $\frac{3}{8}$ in. \times 0.312 in. dia., 370 turns of 34 S.W.G. en. D.S.C. cu. wire; 1 mH \pm 5%.		A	each	1
11969	Type 425 ...	85 microH., 195 turns 41 S.W.G. en. cu., 3 slots of 65 turns each; 1 in. \times $\frac{1}{4}$ in. dia. former.		A	..	1
11970	Type 426 ...	34 turns 30 S.W.G. en. cu., ebonite former, $1\frac{7}{16}$ in. \times $\frac{5}{16}$ in.		A	..	1
11989	Type 427 ...	1.2 mH, 5 coils on tubular former, with fixing stud at one end. Impregnated.		A	..	1
11999	Type 429 ...	$19\frac{1}{2}$ turns 22 S.W.G. wire. Copper wire braided, on loaded ebonite former, 0.187 in. dia., 1.25 in.		A	..	1
12027	Type 433 ...	9 turns 12 S.W.G. cu. wire, air-spaced, 1 in. dia. \times 2 in. long, on S.R.B.P. panel, 2 in. \times 2 in. \times $\frac{1}{16}$ in. thick.		A	..	1
12051	Type 434 ...	17 in. of 28 S.W.G. Eureka wire, wound on moulded former, $\frac{3}{16}$ in. dia. \times 1 in., spaced 1 in. dia.		A	..	3
12056	Type 435 ...	17 in. of 20 S.W.G. cu. wire on moulded former, $\frac{3}{16}$ in. dia. \times $1\frac{1}{2}$ in., spaced 1 in. dia.		A	..	3
12067	Type 437 ...	130 turns 38 S.W.G. en. cu. wire, wound on $\frac{3}{8}$ in. dia. former.		A	..	1
12116	Type 439 ...	4 mH \pm 5%, 6 coils of 181 turns of 36 S.W.G. D.S.C. cu. wire.		A	..	1
12240	Type 445 ...	7.5 mH \pm 10%, with coupling winding on $\frac{1}{2}$ in. dia. \times 5 in. long former.		A	..	1
12251	Type 446 ...	60 turns 40 S.W.G. D.S.C. on moulded former, 0.5 in. o/d \times 0.375 in. i/d \times 1 in.		A	..	2
12268	Type 449 ...	30 in. of 18 S.W.G. tinned cu. wire, 28 turns, $\frac{1}{4}$ in. i/d \times $3\frac{1}{2}$ in. long.		A	..	2
12269	Type 450 ...	30 in. of 18 S.W.G. tinned cu. wire, 16 turns, $\frac{1}{2}$ in. dia.		A	..	2
12270	Type 451 ...	30 in. of 20 S.W.G. tinned cu. wire, 30 turns, $\frac{1}{4}$ in. dia.		A	..	2
12271	Type 452 ...	30 in. of $\frac{1}{4}$ in. o/d cu. tube, 8 turns, 1 in. i/d \times $3\frac{1}{2}$ in. long; complete with flexible connector and clamp. (Dim. X = $\frac{1}{2}$ in.)		A	..	1
12272	Type 453 ...	30 in. of $\frac{1}{4}$ in. o/d cu. tube, 8 turns, 1 in. i/d \times $3\frac{1}{2}$ in. long, complete with flexible connector and clamp. (Dim. X = $2\frac{1}{2}$ in.)		A	..	1
12273	Type 454 ...	30 in. of 18 S.W.G. tinned cu. wire, 28 turns, $\frac{1}{4}$ in. i/d, with ebonite sleeves.		A	..	1
12291	Type 456 ...	S.R.B.P. solid former, 0.62 in. dia. \times 2.81 in., 5 slots each wound 350 turns 34 S.W.G. en. and S.S.C. wire.		A	..	1
12434	Type 463 ...	$1\frac{1}{2}$ in. \times $\frac{1}{4}$ in. o/d (Dynatron)...		A	..	2

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
12442	Type 464	...		A	each	1
12455	Type 465	... 5 Leeson wound coils on ebonite former, 60 mH air core, 9 k. volt working.		A	"	1
12474	Type 467	... 23 turns of 22 S.W.G. en. cu., wound on loaded ebonite former; threaded $\frac{3}{8}$ in. Whit., wire ends.		A	"	1
12476	Type 468	... 4 mH \pm 5%, wound on $1\frac{1}{2}$ in. o/d former, $\frac{1}{2}$ in. long.		A	"	1
12559	Type 473	... 26 turns No. 22 S.W.G. E.C. wire on moulded tube, $\frac{1}{2}$ in. dia. \times 1 in. long.		A	"	2
12560	Type 474	... 40 turns No. 30 S.W.G. E.C. wire on moulded tube, $\frac{1}{2}$ in. dia. \times 1 in. long.		A	"	2
12571	Type 475	... 180 μ H + 2 per cent. Coil 110 turns of 0.0076 in. dia. en. and single silk-covered copper wire, wound clockwise; $1\frac{7}{8}$ in. long \times $\frac{3}{4}$ in. dia. overall.		A	"	2
12581	Type 476	... 14 turns of 30 S.W.G. enamelled copper wire on former, $\frac{3}{4}$ in. \times $\frac{9}{16}$ in. dia.		A	"	2
12592	Type 477	... 12 ft. approx. of 32 S.S.C. en. cu. wire and $3\frac{1}{2}$ in. of 18 S.W.G. tinned cu. wire, wound on Trolitol former.		A	"	1
12593	Type 478	... 12 ft. approx. of 32 S.W.G. en. cu. wire S.S.C. and $3\frac{1}{2}$ in. of 18 S.W.G. tinned cu. wire, wound on Trolitol former and mounted on 2 pillars.		A	"	1
12636	Type 481	... 57 turns 37 S.W.G. S.S. en. cu. wire, wave-wound on Keramot former.		A	"	1
12641	Type 483	... 33 turns (double spaced) of 28 S.W.G. D.S.C. copper wire on S.R.B.P. former, 0.25 in. dia. \times 1.25 in. long.		A	"	2
12644	Type 484	... Three 14 mH, 4 coils each, 250 turns of 35 S.W.G. D.S.C. copper wire, continuously wound on loaded ebonite former, 0.312 in. dia. \times 2.13 in. long; tapped one end 4 B.A.		A	"	1
12730	Type 487	... 17 turns of 22 S.W.G. silver-plated copper wire on moulded Steatite ribbed former, 0.734 in. dia.; vertical fixing; projecting wire ends for connection.		A	"	1
12755	Type 488	... 6 sections, wound on $\frac{1}{4}$ in. bakelite rod, $2\frac{3}{4}$ in. long; each section 190 turns of 38 S.W.G. en. S.C.C. 250 μ H \pm 5 per cent.		A	"	1
12760	Type 493	... 45 cms. of S.W.G. en. wire wound in 42 spaced turns on $\frac{1}{4}$ in. dia. Tufnol former.		A	"	1
12783	Type 494	... 10 turns of 22 S.W.G. tinned copper wire on former.		A	"	1

RADIO CHOKES AND CONDENSERS

Ref. No	NOMENCLATURE	DETAIL	Army or Navy Ref	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
12784	Type 495 ...	40 turns of 30 S.W.G. tinned copper wire on former.		A	each	1
12916	Type 502 ...	17 turns of No. 22 S.W.G. E.C. wire, close wound, tags, on $\frac{1}{2}$ in. dia. loaded ebonite rod, $1\frac{3}{8}$ in. long. Spigot mounting.		A	..	1
12917	Type 503 ...	23 turns of No. 28 S.W.G. E.C. wire, close wound, tags, on $\frac{3}{8}$ in. dia. loaded ebonite rod, $1\frac{3}{8}$ in. long. Spigot mounting.		A	..	1
12937	Type 504 ...	22 turns of 20 S.W.G., space wound, on bakelite former, $\frac{1}{4}$ in. dia. \times $1\frac{1}{2}$ in. long.		A	..	1
13023	Type 508 ...	480 turns approx. 26 S.W.G. D.S.C.C. wire; former, $\frac{7}{8}$ in. dia.		A	..	1
13045	Type 512 ...	Filament		A	..	1
13049	Type 513 ...	120 turns of 38 S.W.G. D.S.C. on fine D.C.C. wire, on former of Durex tape, wax dipped; $150 \mu\text{H} \pm 3 \mu\text{H}$.		A	..	2
13079	Type 516 ...	12 ft. approx of 32 S.W.G. S.S.C. en. cu. wire, wound on Kero-met former.		A	..	2
13089	Type 517 ...	26 S.W.G. en. copper wire, wound on former to cover whole area with one layer.		A	..	2
13097	Type 518 ...	28 in. 26 S.W.G. S.S.C., wound on $\frac{1}{4}$ in. Tufnol former, $2\frac{1}{2}$ mH at 100 mA.		A	..	2
13109	Type 520 ...	6 in. of 22 S.W.G., wound into $\frac{1}{8}$ in. dia. coil.		A	..	2
13110	Type 521 ...	12 in. of 22 S.W.G. on $\frac{1}{4}$ in. dia. Tufnol former.		A	..	2
13111	Type 522 ...	5,200 turns of 39 S.W.G. on Kraft paper former, 1-2 in. long.		A	..	1
13151	Type 523 ...	9 ft. 6 in. of 43 S.W.G. en. copper wire on former.		A	..	1
13157	Type 525 ...	Inductance, $470\mu\text{H}$ plus or minus 5 per cent. 17.3 ohms D.C. resistance.		A	..	1
13158	Type 526 ...	$18\frac{3}{4}$ in. of S.W.G. en. copper wire on former, adjustable core, $3\frac{3}{4}$ in. of sleeving.		A	..	1
13159	Type 527 ...	25 in. of 30 S.W.G. en. copper wire on former, adjustable core, $3\frac{3}{4}$ in. of sleeving.		A	..	1
13160	Type 528 ...	$23\frac{1}{2}$ in. of 30 S.W.G. en. copper wire on former, adjustable core, $3\frac{3}{4}$ in. of sleeving.		A	..	1
13162	Type 529 ...	$16\frac{1}{2}$ in. of 30 S.W.G. en. copper wire on former, adjustable core, $1\frac{1}{2}$ in. of sleeving.		A	..	1
13163	Type 530 ...	$16\frac{1}{2}$ in. of 30 S.W.G. en. copper wire on former, adjustable core, 1 in. of sleeving.		A	..	2
13173	Type 531 ...	30 in. of $\frac{1}{2}$ in. dia. copper wire; 8 turns, 1 in. i/d \times $3\frac{1}{2}$ in. long, complete with flexible connector and clamp.		A	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
13174	Type 532 ...	30 in. of $\frac{1}{4}$ in. dia. copper wire, 8 turns, 1 in. i/d \times $3\frac{1}{2}$ in. long, complete with flexible connector and clamp.		A	each	1
13226	Type 534 ...	6 turns 26 S.W.G. wire. Enamelled copper wire on former.		A	..	2
13269	Type 537 ...	Heater; red spot, 0.072 ohms; 50 turns 24 S.W.G. D.S.C.		A	..	1
13280	Type 538 ...	Winding—5 sections, each $\frac{3}{16}$ in. wide, Leeson wound. Former, moulded bakelite, $\frac{1}{2}$ in. dia. \times $1\frac{3}{4}$ in. long, with 4 B.A. studs, tags, and nuts each end.		A	..	1
13314	Type 540 ...	11 turns 30 S.W.G. wire. Enam. cu. on loaded ebonite former, 0.25 in. dia. \times 0.75 in., tapped 6 B.A. one end.		A	..	2
13315	Type 541 ...	13 turns 30 S.W.G. en. on loaded ebonite former, 0.25 in. dia. \times 1.22 in., one end tapped 6 B.A. hole.		A	..	1
14195	Type 544 ...	Inductance, 7 H. at 250 mA. D.C. resistance, 35 ohms approx.		A	..	1
13342	Type 546 ...	80 turns 40 S.W.G. Eureka wire wound in 4 sections on distrene former, $\frac{1}{2}$ in. dia. \times 2.14 in. long.		A	..	1
13399	Type 552 ...	25 turns 26 S.W.G. en. cu. wire on Trolitol former. (Former coil, Type 1.)		A	..	1
13441	Type 556 ...	13 turns 18 gauge tinned copper wire, $\frac{1}{4}$ in. i/d \times $1\frac{1}{2}$ in. overall length.		A	..	2
13442	Type 557 ...	10 turns 18 gauge tinned copper wire, $\frac{1}{4}$ in. i/d.		A	..	2
13474	Type 559		A	..	1
13482	Type 560 ...	12 in. of 30 S.W.G. en. copper wire on former, adjustable core, $1\frac{1}{4}$ in. of sleeving.		A	..	1
13498	Type 562 ...	30 in. of 18 S.W.G. tinned copper wire, 28 turns, $\frac{1}{4}$ in. i/d.		A	..	2
13561	Type 564 ...	25 turns 38 S.W.G., 2 windings.		A	..	1
13596	Type 568 ...	20 turns 22 S.W.G. wire. D.S.C. wire on insulating former, $1\frac{1}{2}$ in. \times $\frac{1}{4}$ in. dia. 2 Eureka spills. Screwed on 8 B.A.		A	..	1
13641	Type 570 ...	Inductance, 700 μ H. 700 μ H per section.		A	..	1
13642	Type 571 ...	4 μ H; 480 turns 36 S.W.G. D.S.C. copper wire; with moulded cover.		A	..	1
13656	Type 572 ...	25 μ H \pm 10 per cent. 60 turns 40 S.W.G. double en. copper on bakelite bobbin former, 1 in. \times $\frac{3}{8}$ in.		A	..	1
13658	Type 574 ...	2.75 μ H nominal. 13 turns 30 S.W.G. en. copper wire on moulded former, with dust iron core.		A	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
13659	Type 575 ...	3.95 μ H nominal. 18 turns 30 S.W.G. (tapped 4 turns) en. copper wire on moulded former, with core.		A	each	1
13660	Type 576 ...	3.83 μ H nominal. 18 turns + 4 turns over-wound 30 S.W.G. en. copper wire, moulded former, with dust iron core.		A	..	1
13661	Type 577 ...	1 to 1.55 μ H. 10½ turns 22 S.W.G. en. copper, moulded former, with dust iron core.		A	..	1
13662	Type 578 ...	47 mics. \pm 10 per cent. 34½ turns 22 S.W.G. en. copper wire, on 1½ in. \times ¼ in. former.		A	..	1
13721	Type 587 ...	25 μ H \pm 10 per cent. 60½ turns 40 S.W.G. double en. copper on former, 1 in. \times ⅜ in.		A	..	1
13739	Type 589 ...	23 turns 28 S.W.G. wire. ⅜ in. dia. former, 1½ in. long.		A	..	1
13742	Type 590 ...	Wire-wound, 26 S.W.G. E.C. wire on bakelite former, 1 in. \times ½ in.		A	..	2
13743	Type 591 ...	Wire-wound, 40 S.W.G. E.C. wire on bakelite former, 1½ in. \times ⅜ in. dia.		A	..	2
13744	Type 592 ...	Wire-wound, 11 turns 22 S.W.G. E.C. wire. ⅜ in. dia.		A	..	2
13745	Type 593 ...	Wire-wound, 20 turns 22 S.W.G. E.C. wire. ½ in. i/d.		A	..	2
13746	Type 594 ...	Wire-wound, 14 turns 20 S.W.G. E.C. wire. ⅜ in. i/d.		A	..	2
13747	Type 595 ...	Paxolin former, ½ in. o/d \times ⅜ in. i/d \times 1½ in. Wound 7½ turns 18 S.W.G. E.C. wire.		A	..	2
13774	Type 597 ...	30 mH former, ⅜ in. \times 2½ in., including end wires. 75 turns of 38 gauge D.S.C.		A	..	1
13776	Type 598 ...	22 SS.E. wound on ¾ in. \times 1½ in. former.		A	..	1
13789	Type 600 ...	185 μ H \pm 10 per cent. Wound 20 S.W.G. copper on former, with dust iron core.		A	..	1
13857	Type 601 ...	40 turns 24 S.W.G. T.C. ...		A	..	1
13894	Type 602 ...	Former, ⅝ in. dia. \times 1½ in. long, paxolin. 34 turns of 26 S.W.G. en. copper.		A	..	2
13907	Type 605 ...	Inductance, 2,600m/H, 310 turns per coil. 6 coils of 30 S.W.G. wire. Basket wound on Silvonite rod, 0.562 in. dia. \times 2.625 in. long. Similar to Type 363, but without brackets.		A	..	1
13911	Type 606 ...	240 mH. Approx. 450 yds. 26 S.W.G.		A	..	1
13919	Type 607 ...	2 sections, wave-wound single, 175 turns each section, continuous between windings; and 1 section, 350 turns, wave-wound single 0.006 in. cu. wire, on S.R.B.P. former, 0.25 in. dia. \times 2 in.		A	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
13954	Type 608 ...	24 turns 22 S.W.G. en. wire, paxolin former, $\frac{1}{4}$ in. dia. \times $1\frac{1}{8}$ in., 22 S.W.G. terminal wires, fitted with bracket.		A	each	2
13976	Type 610 ...	Inductance, 77 mH wire, 400 ± 10 per cent.		A	..	1
13977	Type 611 ...	Inductance, 1.3 mH, wound on 2 "E" cores.		A	..	1
13978	Type 612 ...	Wound on 2 "E" cores ...		A	..	1
14017	Type 614 ...	40-80 μ H		A	..	1
14049	Type 616 ...	585 turns 26 S.W.G. E. and S.S. copper wire. 0.25 A. nominal rating at 1,000 A. per sq. in., $\frac{1}{2}$ wave-wound, 8 mH ± 10 per cent. Bakelite moulded former.		A	..	1
14077	Type 620 ...	Used on T.1440 and T.1440A ...		A	..	1
14090	Type 622 ...	Loaded ebonite, $1\frac{1}{4}$ in. \times $\frac{3}{8}$ in. o/d. 55 turns of 48 S.W.G. D.S.C. copper wire, close-wound.		A	..	1
14103	Type 625 ...	35 turns 24 S.W.G. enamelled...		A	..	1
14104	Type 626 ...	Eddystone 1010 H.F. Choke has 4 sections of 0.25 μ H, each of the three interconnections are unwound one turn and taken down to tag panel.		A	..	1
14108	Type 627 ...	35 μ H ± 20 per cent. ...		A	..	1
14109	Type 628 ...	110 μ H ± 20 per cent. ...		A	..	1
14110	Type 629 ...	146 μ H ± 20 per cent. ...		A	..	1
14111	Type 630 ...	44 μ H ± 20 per cent. ...		A	..	1
14135	Type 633 ...	48 turns 24 gauge iron wire on former (Siemen's S.O.2351).		A	..	1
14136	Type 634 ...	7 turns of 18 S.W.G. en. cu. wire, air core, $\frac{5}{16}$ in. i/d \times $\frac{1}{2}$ in. long approx., ends $1\frac{1}{2}$ in. long.		A	..	2
14159	Type 636 ...	6 μ H ± 5 per cent. 25 turns of 24 S.W.G. D.S.C. copper wire.		A	..	1
14182	Type 639 ...	175 turns of 40 D.S.C. 230 μ H ± 5 per cent.		A	..	1
14221	Type 641 ...	4 mH ± 50 per cent, 20 mA. Wave-wound. Insulation 350 volts.		A	..	1
14231	Type 642 ...	Ebonite former, 0.375 in. dia. \times 1.0 in. long, wound 15 turns 36 S.W.G. en. copper wire.		A	..	2
14234	Type 643 ...	3.3 μ H. 23 turns 28 S.W.G. en. cu. wire, close-wound, on loaded ebonite former.		A	..	1
14278	Type 645 ...	3 coils, 67 turns 40 S.W.G. en. and S.S. copper wire, on former. 120 μ H ± 5 per cent.		A	..	1
14279	Type 646 ...	2 coils, 45 turns 40 S.W.G. en. and S.S. copper wire, on former. 35 μ H ± 5 per cent.		A	..	1
14309	Type 648 ...	24 turns of 24 S.W.G. en. copper wire on loaded ebonite former.		A	..	1
14310	Type 649 ...	2 windings, each 30 turns of 24 S.W.G. en. copper wire on loaded ebonite former.		A	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
14317	Type 650 ...	75 turns of 38 S.W.G. en. wire wound on former, Invicta, Type 55275.		A	each	1
14318	Type 651 ...	30 turns of 23 S.W.G. en. on $\frac{3}{8}$ in. paxolin former.		A	..	1
14330	Type 655 ...	265 turns of 44 S.W.G. en. copper wire close-wound. Inductance, 100 μ H \pm 10 per cent.		A	..	1
14362	Type 657 ...	Inductance, 2 H. Current, 80 mA.		A	..	1
14363	Type 658 ...	D.S.C. former, 4 in. long \times $\frac{1}{2}$ in. dia. W.T. 22 rod, 40 turns 26 S.W.G.		A	..	1
14425	Type 659 ...	Anode. 2 μ H. D.C. Resistance max., 60 ohms, 1.5 amps. D.C. $5\frac{1}{16}$ in. dia. \times $13\frac{1}{8}$ in. high.		A	..	1
14426	Type 660 ...	Inductance, 20 H. Current 60 mA.		A	..	1
14487	Type 664 ...	24 turns 23 S.W.G. enamelled, on paxolin strip.		A	..	1
14502	Type 665		A	..	1
14594	Type 678 ...	600 μ H. Mains filter ...		A	..	1
14595	Type 679 ...	120 μ H		A	..	1
14596	Type 680 ...	1,000 μ H		A	..	1
14653	Type 682 ...	Inductance, 1.1 henries at 120 mA, 5 volts, 50 cycles, D.C. Res., 130 ohms.		A	..	1
14733	Type 686 ...	Filament choke. 32 turns of 20 S.W.G. silk-covered wire, on S.R.B.P. tubular former. $1\frac{3}{8}$ in. long \times $\frac{3}{4}$ in o/d \times $\frac{1}{2}$ in i/d. Wire ends.		A	..	1
14769	Type 688 ...	500 mH. 200 turns 38 D.S.C. $\frac{5}{16}$ in. former.		A	..	1
14884	Type 691 ...	Inductance, 4 mH. 600 turns 0.0076 wire. Size: overall length, $1\frac{9}{16}$ in. Wave-wound on $\frac{3}{4}$ in. dia. former.		A	..	1
14976	Type 697 ...	7 turns 26 S.W.G. en. cu. wire...		A	..	1
15007	Type 699 ...	19 coils choke mounted on frame, with 2 mounting feet, $7\frac{3}{8}$ in. long \times $2\frac{3}{8}$ in. high \times $1\frac{3}{8}$ in. wide.		A	..	1
15028	Type 700		A	..	1
15031	Type 701 ...	Inductance, 6 μ H \pm 5 per cent. Number of turns, $100\frac{1}{2} \pm 1$, 0.018 in. D.S.C. copper wire. Loaded ebonite former, end wires.		A	..	1
15176	Type 709 ...	25 turns 22 S. W. G. wire. Enamelled copper wire on S.R.B.P. former, 0.187 in. dia. \times 2.12 in.		A	..	1
15179	Type 710 ...	Inductance, 3.46 mH. Number of turns, 5 sections each 150. 36 S.W.G. D.R.C. copper wire. Size: Former, $\frac{1}{2}$ in. dia. \times $2\frac{3}{4}$ in.		A	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
15177	Type 711 ...	Complete assembly on moulded base. Inductance, 21 microhenries at 1,000 c.p.s.		A	each	1
15178	Type 712 ...	As Type 711 but opposite hand		A	..	1
15218	Type 714 ...	4 in. of 24 S.W.G. wire, tight wound on $\frac{5}{16}$ in. former.		A	..	1
15279	Type 715 ...	17 in. of 28 S.W.G. enamelled wire, spaced one dia. on former, $1\frac{1}{8}$ in. long \times $\frac{3}{16}$ in.		A	..	1
15961	Type 722 ...	Inductance, 1.32 mH. Comprises 5 banks of 200 mH each.		A	..	1
15991	Type 729 ...	24 turns 22 S.W.G. en. cu. wire. Size, $\frac{17}{32}$ in. \times $\frac{1}{4}$ in. dia. on S.R.B.P. former. Drilled and tapped one end 6 B.A. for mounting.		A	..	1
15992	Type 730 ...	28 turns 18 S.W.G. "Bicelon" or Newmex wire. Size, 2 in. \times $\frac{3}{8}$ in. \times $\frac{1}{4}$ in., on S.R.B.P. former. One fixing hole, 6 B.A. clearance.		A	..	1
15993	Type 731 ...	24 turns 26 S.W.G. en. cu. wire. on S.R.B.P. former. One fixing hole, 6 B.A. clearance.		A	..	1
15994	Type 732 ...	24 turns 24 S.W.G. en. cu. wire. Size, $1\frac{7}{32}$ in. \times $\frac{1}{4}$ in. dia., on S.R.B.P. former. Drilled and tapped one end 6 B.A. for mounting.		A	..	1
16038	Type 735 ...	Inductance, 200 mH. 34 S.W.G. D.S.C. wire, wave-wound on $\frac{1}{4}$ in. dia. former. Dim. of winding, $\frac{1}{8}$ in. wide \times $\frac{3}{8}$ in. dia.		A	..	1
16057	Type 737 ...	Inductance, 2.2 μ H. 42 turns 23 S.W.G. copper D.C.C. wire. Overall dia., $\frac{5}{16}$ in.; length of end wires, 1 in. \times $\frac{3}{8}$ in. Resistance less than 1 ohm.		A	..	1
16162	Type 749 ...	Number of turns, 67 cms. \pm 1 cm. 24 S.W.G. en. cu. wire. Wound on S.R.B.P. former, 1.593 in. long \times 0.1875 in. dia.		A	..	1
16194	Type 752 ...	Inductance, 2.5 μ H \pm 5 per cent. at 1 mc/5. 39 turns 20 S.W.G. wire wound on former (Cossor, AB.3534).		A	..	1
16264	Type 761 ...	Inductance, 500 micro H. S.S.C. enam. wire, wound in 3 sections on $\frac{1}{4}$ in. Tufnol rod, each section 159 turns. Tropical.		A	..	1
16265	Type 762 ...	Inductance, 700 micro H. S.S.C. enam. wire, wound in 4 sections on $\frac{1}{4}$ in. dia. Tufnol rod, each section 163 turns.		A	..	1
16885	Type 775 ...	Inductance, 5.6 mH. D.C. resistance, 1.3 ohms.		A	..	—
16978	Type 780 ...	Inductance, 150 mH ...		A	..	—
16980	Type 781 ...	Inductance, 400 mH. 376 turns (4 sections, 94 turns per section) of 40 S.W.G. en. cu. wire.		A	..	—
17693	Type 806 ...	5 mH		A	..	—

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.:					
3345	Type A	Iron core choke, with paxolin bobbin. Overall dimensions, 2½ in. × 2½ in. × 1½ in.		A	each	1
7384	Type B	Iron core choke, with bakelite former. Overall dimensions, 2 in. × 1½ in. × 1½ in.		A	..	1
7512	Type C	Iron core power smoothing choke, with paxolin bobbin; air gap, 0.15 in. Overall dimensions, 8½ in. × 8½ in. × 6½ in.		A	..	1
7912	Type G	Iron core choke, with bakelite former. Overall dimensions, 2 in. × 1½ in. × 1½ in.		A	..	1
8634	Type J	Iron core, .009 henries, 15 amps.		A	..	1
9341	Type M	Iron core choke with moulded cover 2½ in. × 2½ in. × 2 in. overall, 4 henries, 150 milliamps.		A	..	1
9497	Type N	Iron core, .08 in. gap, 3½ in. × 3½ in. × 5 in. overall approximately. Fitted with mounting, Type 13.		A	..	1
		Ref. No. 10A/9882.				
9606	Type R	Iron core, 30/20 henries, 0–150 mA., 6½ in. × 4½ in. × 3½ in. overall.		A	..	1
9607	Type S	Iron core, 300 henries, metal cased, 3 in. × 3½ in. × 3½ in. overall.		A	..	1
9628	Type T	Iron core, 2½ in. × 2½ in. × 1½ in. overall.		A	..	1
1	Type V	Filter choke		A	..	1
42	Type W	Open type. 2½ in. × 1½ in. × 1½ in. high. Black varnish impregnated with tag panel at top.		A	..	1
—	5 H. 200 mA	Naval 2311	A	..	—
72	Type 26	Smoothing		A	..	1
74	Type 28	Mains		A	..	1
76	Type 30	Smoothing		A	..	1
77	Type 31		A	..	1
78	Type 32	4,500 turns of 0.0148 in. dia. en. cu. wire, open type.		A	..	1
81	Type 33	8,000 turns of 0.0048 in. en. copper wire, 1,440 ohms approx., open type, 2½ in. × 1½ in. × 2½ in., with tag panel at top.		A	..	1
11359	Type 36	Output		A	..	1
388	Type 37		A	..	1
400	Type 38		A	..	1
448	Type 39	30/7 henries, 100 mA., 215 ohms, 500 volts, D.C.		A	..	1
449	Type 40		A	..	1
571	Type 44	45 henries with 30 mA., D.C., and 20 volts, A.C., 1090 ohms, D.C.		A	..	1
572	Type 45	8 henries, with 80 mA., D.C., and 20 volts, A.C., 115 ohms, D.C.		A	..	1
579	Type 46	1.21–99 henries, 143–117 ohms		A	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
580	Type 4722 henries approx. at approx. 2.5 volts, 1,000 cycles.		A	each	1
581	Type 488 to .5 henries, 12.6 to 10.44 ohms.		A	"	1
582	Type 49 ...	1 henry approx. at approx. 1 volt, 1,000 cycles.		A	"	1
605	Type 50 ...	2.50 henries at 150 mA., 42.5 ohms. D.C. resistance.		A	"	1
658	Type 5135 henries ± 20 per cent., 400 mA. D.C. Resistance 4.1 ohms ± 20 per cent.		A	"	1
826	Type 52 ...	4 millihenries, 50 turns, 20 S.W.G. on $\frac{3}{8}$ in. former.		A	"	1
846	Type 55 ...	8 henries		A	"	1
2032	Type 56 ...	Inductance, 8 henries		A	"	1
2061	Type 57 ...	2 $\frac{1}{2}$ in. \times 1 $\frac{1}{2}$ in. \times 1 $\frac{1}{4}$ in. overall. Leads, mexphalte dipped.		A	"	1
2092	Type 58 ...	32 henries, 370 ohms		A	"	1
2093	Type 59 ...	20 henries, 180 ohms		A	"	1
2098	Type 60 ...	Inductance, 4 henries at 50 cycles at 30 mA.		A	"	1
2100	Type 61 ...	17 henries. Laminated stampings, with air gap. Overall size, 5 in. \times 5 in. \times 4 $\frac{1}{4}$ in.		A	"	1
2133	Type 62 ...	Inductance, 3 henries at 20 volts A.C., 60 mA. D.C. 200 ohms D.C. Resistance.		A	"	1
2142	Type 63 ...	1,400 ohms		A	"	1
2143	Type 64 ...	200 ohms		A	"	1
2184	Type 65 ...	Smoothing, 10 henries. Inductance at 100 mA. D.C., insulated for 1,000 volts D.C.		A	"	1
2187	Type 66 ...	Smoothing		A	"	1
2226	Type 67 ...	Smoothing		A	"	1
2273	Type 69 ...	10 henries, 200 mA. A.C. + 150 mA. D.C.		A	"	1
2279	Type 70 ...	100 henries, 5 mA.		A	"	1
2289	Type 71325 henries approx. at approx. 7 volts, 1,000 cycles.		A	"	2
2296	Type 72 ...	7 henries, 5 amps. D.C. 700 volts insulation.		A	"	1
2297	Type 73 ...	7 henries, 3 amps. 2,000 volts insulation.		A	"	1
2298	Type 74 ...	100 mA., 215 ohms, 500 volts ...		A	"	1
2367	Type 75 ...	D.C. working, 47.7 henries. Used in pairs with transformer, Type 210, Ref. No. 10KB/31.		A	"	1
2446	Type 76 ...	1,200 henries ± 20 per cent. ...		A	"	1
2376	Type 77		A	"	1
2552	Type 79 ...	Iron core		A	"	1
2556	Type 81 ...	Smoothing		A	"	1
2570	Type 82 ...	10 henries at 500 mA. D.C. ...		A	"	1
2576	Type 83 ...	Smoothing, 10 henries inductance at 50 mA., 3 $\frac{5}{8}$ in. \times 2 $\frac{3}{4}$ in. \times 4 in. overall, 2 $\frac{1}{2}$ in. \times 3 $\frac{1}{8}$ in. fixing centres, 3 lb. net.	Army ZC.1525	A	"	1
2580	Type 84 ...	1,000 cycles, smoothing, tropical		A	"	1
2582	Type 86 ...	Tapped smoothing, 5.2 henries, $\pm 5\%$ + 4 henries $\pm 5\%$. Open type, 3 in. \times 2 in. \times 3 $\frac{1}{2}$ in. high, with tag panel at base.		A	"	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
2595	Type 88 ...	Smoothing ...		A	each	1
2596	Type 89 ...	Smoothing ...		A	"	1
2601	Type 90 ...	Open type, 2½ in. × 1½ in. × 2 in. high, with tag panel; tropical, black varnish, impregnated.		A	"	1
2643	Type 91 ...	6 henries, 130 mA. D.C. Open type. 2½ in. × 2 in. × 3 in. high.		A	"	1
2692	Type 92 ...	Tapping switch reaction for use with transformer, Type 226 (10K/57). With choke, 7·7 volts at 2·5A. Not more than 10·8 volts at 5A.		A	"	1
2761	Type 94 ...	·001 mA., mica moulded, 1,000 volts.		A	"	1
2763	Type 95 ...	100 henries, 0·005 amps. ...		A	"	1
2764	Type 96 ...	10 volts at 7 amps. and 14 volts at 14 amps.		A	"	1
2765	Type 97 ...	1·7 volts at 7 amps. and 2·5 volts at 14 amps.		A	"	1
2866	Type 100 ...	3 henries at 60 mA. D.C. Resistances, 200 ohms, D.C. Enclosed in tank filled with Kingworth compound.		A	"	1
3019	Type 105 ...	20 henries ...		A	"	1
3145	Type 109 ...	20 henries ...		A	"	1
3146	Type 110		A	"	1
3147	Type 111 ...	50/30 henries, 0/50 mA., 600 ohms, 500 volts D.C.		A	"	1
10699	Type 114		A	"	1
3428	Type 117 ...	60 henries, 50 mA. ...		A	"	1
3429	Type 118 ...	6 henries, 1·2 amps, D.C., 30 henries, 12 amps.		A	"	1
3460	Type 119 ...	7 henries, 180 mA. ...		A	"	1
3520	Type 122 ...	40 henries, 20 mA., 10 henries, 180 mA.		A	"	1
3522	Type 124		A	"	1
3523	Type 125		A	"	1
3653	Type 130 ...	20 henries, laminated, 200 mA., 250 ohms max., 4½ in. × 3½ in. × 4 in. overall.		A	"	1
3680	Type 132		A	"	1
3682	Type 134 ...	15 henries, 330 mA., 100 ohms, swinging.		A	"	1
3684	Type 136 ...	25 henries, 150 mA., 1,100 ohms		A	"	1
3685	Type 137 ...	27 henries, 250 mA., 130 ohms		A	"	1
3687	Type 138 ...	Smoothing, terminal board on top.		A	"	1
3688	Type 139		A	"	1
3736	Type 144 ...	20 henries, 60 mA. ...		A	"	1
3742	Type 148 ...	10 henries, 250 mA., 11½ lb. net, 4½ in. × 2½ in. fixing centres, 2 B.A. terminals.	Army ZC.1524	A	"	1
3767	Type 155 ...	10 henries, 50 Mc./s, 1,000 volts, insulation.		A	"	1
3768	Type 156 ...	20 henries, 700 mA. ...		A	"	1
3770	Type 158 ...	3,500 turns on laminated former		A	"	1
3771	Type 159 ...	G.B., smoothing ...		A	"	1
3895	Type 160 ...	H.T., smoothing ...		A	"	1
3896	Type 161		A	"	1
3898	Type 162		A	"	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
3971	Type 163 ...	Double smoothing ...		A	each	1
3973	Type 165 ...	8 henries, 120 mA., 225 ohms		A	"	1
3974	Type 166		A	"	1
4073	Type 167 ...	5 henries, 3 amps., 27 ohms, D.C. resistance.		A	"	1
4074	Type 168		A	"	1
4075	Type 169		A	"	1
4076	Type 170		A	"	1
4081	Type 171 ...	13/20 henries, iron cored, smoothing, 350 ohms, D.C., 3 watts, max. dissipation, unshielded.		A	"	1
4084	Type 174		A	"	1
4086	Type 176 ...	Double smoothing in M.S. can		A	"	1
4087	Type 177 ...	Special R.F. ...		A	"	1
4088	Type 178		A	"	1
4089	Type 179		A	"	1
4280	Type 181 ...	Inductance, 25 H. Current, 110 mA. D.C. resistance, 100 ohms.		A	"	1
4523	Type 189 ...	1 henry, 140 mA., laminated iron core, 1,200 turns of 32 S.W.G. en. copper wire.		A	"	1
4524	Type 190 ...	1 henry, 40 mA., laminated iron core, 1,600 turns of 37 S.W.G. en. copper wire.		A	"	1
4525	Type 191 ...	3.2 henries, 40 mA., 360 ohms...		A	"	1
4592	Type 193 ...	Coil layer wound with enam. C. wire, paper interleaved. Test voltage, 1,000 volts A.C., etc. Open type, 1 $\frac{5}{16}$ in. \times 1 $\frac{3}{4}$ in. high, approx., with leads.		A	"	1
4593	Type 194 ...	Coil layer, wound with enam. C. wire, paper interleaved. Test voltage, 1,000 volts A.C. Open type, 2 in. \times 1 $\frac{7}{8}$ in. high, approx., with leads.		A	"	1
4595	Type 196 ...	Output, 2,000 ohms, centre tapped.		A	"	1
4710	Type 199 ...	0.01 in spacing ...		A	"	1
4711	Type 200		A	"	1
4712	Type 201 ...	12 henries at 25 volts, 50 cycles, ripple, 120 mA., D.C., 2,700 turns of 36 gauge En. and S.S.C. copper wire on former.		A	"	1
4713	Type 202 ...	Reactor ...	Army ZC.6676	A	"	1
4714	Type 203 ...	20 henries, 100 mA. ...		A	"	1
4715	Type 204 ...	200 henries, 6 mA., special ...		A	"	1
4842	Type 211 ...	20 henries at 180 mA. ...		A	"	1
4844	Type 213 ...	0.5 henries, 2 amps., D.C., 600 volts, R.M.S., 150 cycles per sec.; tropical.		A	"	1
4845	Type 214 ...	15 henries ...		A	"	1
4846	Type 215		A	"	1
5018	Type 218 ...	Smoothing, with 1 $\frac{1}{4}$ in. pack ...		A	"	1
5059	Type 219		A	"	1
5060	Type 220 ...	50 henries, 50 mA., D.C., 450 ohms.		A	"	1
5061	Type 221 ...	1,800 turns 0.0048 in. dia. en. S.S.C. copper wire, 1 $\frac{1}{4}$ in. \times 1 $\frac{3}{4}$ in. \times 2 in. overall.		A	"	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
5082	Type 227 ...	2½ in. × 1½ in. × 1½ in. metal case.		A	each	1
5085	Type 230 ...	10 henries at 500 mA. ...		A	..	1
5086	Type 231 ...	50 henries at 25 mA. ...		A	..	1
5087	Type 232 ...	80 henries at 5 mA. ...		A	..	1
5130	Type 239 ...	10 henries at 60 mA. ...		A	..	1
5134	Type 243 ...	50 mA. ...		A	..	1
5286	Type 244 ...	32 henries shrouded; 350 ohms, D.C. resistance.		A	..	1
5288	Type 245 ...	6 coils, each of 96 turns of 34 S.W.G. enamelled copper wire, wound on 1 in. dia. tubular former approx. 9 1/16 in. long.		A	..	1
5289	Type 246 ...	12½ henries, D.C. resistance 7,000 ohms, 46 mA., 2½ watts.		A	..	1
5290	Type 247 ...	88 henries, 60 henries at max. current of 8.7 mA. D.C. resistance, 1,460 ohms; 2½ watts.		A	..	1
5291	Type 248 ...	35 henries, max. current 20 mA. Resistance 1,800 ohms, 2½ watts.		A	..	1
5292	Type 249 ...	10 henries at 50 mA. Open type, 2½ in. × 2¼ in. × 3 in. high, with tag panel. Tropical.		A	..	1
5379	Type 255 ...	Anode valve 3, 2 in. × 1½ in. × 1½ in.		A	..	1
5399	Type 260 ...	20 henries, 150 mA., D.C. ...		A	..	1
5404	Type 261 ...	20 henries at 100 mA., D.C. ...		A	..	1
5405	Type 262 ...	12 henries, 200 mA. ...		A	..	1
5406	Type 263 ...	25 henries ...		A	..	1
5497	Type 270 ...	Inductance, 30 H ...		A	..	1
5623	Type 274 ...	Winding, 5,000 turns of 36 S.W.G. en. copper wire on 1/16 in. dia. former		A	..	1
5637	Type 279 ...	Intervalve, 5 henries, 60 mA...		A	..	1
5723	Type 282 ...	Coil, iron former, 3¼ in. × 2 in. × 1¾ in.; 2 fixing holes, 2¾ in. centres.		A	..	1
5724	Type 283 ...	154 millihenries ± 5%, 68 turns of 40 S.W.G., D.S.C. wire, coil approx. 5/8 in. dia × 1/8 in. with 1/2 in. dia. iron core; connections to side pins; complete with fixing panel, 1 in. × 1¼ in.; overall height, approx. 1½ in. not shrouded.		A	..	1
5725	Type 284 ...	154 millihenries ± 5%, 68 turns of 40 S.W.G., D.S.C. wire; coil approx. 5/8 in. dia. × 1/8 in., with 1/2 in. dia. iron core; connections to side tags; complete with fixing panel, 1 in. × 1¼ in.; overall height, approx. 1½ in.; not shrouded		A	..	1
587	CHOKES:— L.F. Type 266 ...	100 henries, 50 mA D.C., 1,090 megs., 20 v. A.C. Contained in tank filled with Kingsworth compound. 3½ in. × 3½ in. × 5 1/16 in.		A	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
5730	Type 285 ...	278 millihenries \pm 5%, 91 turns of 40 S.W.G., D.S.C. wire; coil approx. $\frac{5}{8}$ in. dia. \times $\frac{1}{2}$ in., with $\frac{1}{2}$ in. dia. iron core; connections to side pins; complete with fixing panel, 1 in. \times $1\frac{1}{4}$ in.; overall height, approx. $1\frac{1}{2}$ in.; not shrouded.		A	each	1
5735	Type 290 ...	Laminated iron core, 3,500 turns of 38 S.W.G. en. copper wire, 15 henries, 30 mA.		A	..	1
5845	Type 291 ...	10 henries at 110 mA., continuous air cooled, shell type, 6 in. \times $6\frac{3}{4}$ in. \times $5\frac{1}{2}$ in.		A	..	1
5906	Type 293 ...	60 volts, 50 megohms. Contained in tank, etc., o/a 4 in. \times 4 in. \times 5 in.		A	..	1
5906	Type 294 ...	10 volts, 50 megohms. Contained in tank, etc., o/a $4\frac{1}{2}$ in. \times $3\frac{3}{4}$ in. \times $5\frac{3}{16}$ in.				
5916	Type 298 ...	2 windings, 930 turns 34 S.W.G., tags; 256–264 henries; metal case, 2 in. high, $1\frac{1}{2}$ in. \times $\frac{3}{4}$ in.		A	..	1
11025	Type 305 ...	2 henries, current rates, 100 mA, ohmic resistance 100 ohms \pm 5%.		A	..	1
11043	Type 306 ...	20 henries, 100 mA, tropical ...		A	..	1
11167	Type 307		A	..	
11222	Type 310 ...	Smoothing		A	..	1
11234	Type 313 ...	10 henries, 4,250 turns of 28 S.W.G. en. cu. wire, $1\frac{1}{2}$ in. pack, No. 75 laminations.		A	..	1
11300	Type 314 ...	Inductance, 20 H. Current 70 mA. Choke, 25 A.		A	..	1
11301	Type 315 ...	20 henries, 75 mA		A	..	1
11302	Type 316 ...	3 henries, 100 mA, 92 ohms D.C., shrouded.		A	..	1
11304	Type 318 ...	3 henries, 100 ohms, open type, $2\frac{1}{2}$ in. \times $1\frac{1}{2}$ in. \times $1\frac{1}{2}$ in. high, black, impregnated.		A	..	1
11323	Type 320 ...	400 ohms approx., 20 henries, 6,500 turns 0.0084 in. S.S. en. cu. wire; dimensions, $3\frac{1}{2}$ in. \times $2\frac{3}{8}$ in. \times $2\frac{1}{2}$ in.		A	..	1
11324	Type 321 ...	3 henries, 200 mA		A	..	1
11325	Type 322 ...	2.5 H nominal value, 20 mA. To be not less than 2.4 H. 2,200 turns of 42 S.W.G. en. and S.S.C.		A	..	1
11332	Type 323 ...	2.5 henries \pm 5 percent. 120 mA. 2,000 turns of 34 S.W.G. E. S. S. C.; D. C. resistance, approx. 92.5 ohms.		A	..	1
11313	Type 324 ...	30–40 henries, 50 mA, $3\frac{1}{4}$ in. \times $1\frac{3}{4}$ in. \times $2\frac{1}{2}$ in., 4 fixing lugs.		A	..	1
11338	Type 326 ...	4 henries, 250 mA, L.F. ...		A	..	1
11339	Type 327 ...	9 henries, 125 mA, L. F., shrouded.		A	..	1
11340	Type 328 ...	15 henries, 50 mA, L. F., shrouded.		A	..	1

RADIO CHOKES AND CONDENSERS

Ref No	NOMENCLATURE	DETAIL	Army or Navy Ref	Class of Store	Denom of Qty	Carton Unit Qty
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont					
11429	Type 330 ...	Smoothing, impregnated, in metal case, 2½ K volts		A	each	1
11430	Type 331 ...	Smoothing, 200 mA ...		A	..	1
11442	Type 332 ...	11 henries, 80 mA ...		A	..	1
11445	Type 333 .	120 henries ± 20% at 80 mA peak, 26 mA mean current Peak voltage across choke, 13 K V, insulated to 21 K V		A	..	1
11446	Type 334 ..	Air insulated, 2 sections, 2 5 and 3 5 henries, variable 5 to 7 henries		A	..	1
11524	Type 336 ...	5 henries, 3,000 turns 34 S W G en cu wire, open type, 2½ in × 1½ in × 2¾ in high, with tag panel		A	..	1
11611	Type 338 ...	Smoothing choke, 10 henries, 30 mA		A	..	1
11609	Type 339 ..	2 henries at 200 mA, D C + 10 volts 50 cycles, A C, resistance, 77 ohms ± 20%, 1 800 turns of 34 S W G enamel, open type, 2¾ in × 1½ in × 2 in high approx, with tag panel		A	..	1
11610	Type 340 .	2 henries at 130 mA, D C + 10 volts A C 50 cycles, 2,400 turns of 34 S W G en cu wire, open type, 2½ in × 1¾ in × 1½ in high		A	..	1
11779	Type 344 .	Modulation . . .		A	..	1
11846	Type 347 ..	20 henries, 20 mA		A	..	1
11857	Type 348 .	Iron core, 2,200 turns of 34 S W G, tagboard		A	..	1
11873	Type 349 ...	350 turns quarter-wave-wound, 24 S W G D C C bound, former bakelised paper, 1 625 in long, 1½ in dia		A	..	1
11911	Type 350	6 henries at 2 3 amps, D C		A	..	1
11943	Type 351	12 henries		A	..	1
11971	Type 352 .	21 henries at 40 mA D C, 5 500 turns of 38 S W G, presspahn former, 1½ in square		A	..	1
11972	Type 353 ..	5 henries at 10 mA, 1¾ in × 1¾ in × 2½ in, 2 fixing holes, 3,200 turns of 37 S W G		A	..	1
11978	Type 354	8 henries with no D C flowing, 600 ohms ± 15%, open type 2 in × 2 in × 2 in, with tag panel		A	..	1
11981	Type 355 ...	10 henries 350 mA, to withstand 500 volts, R M S ripple, and 5 200 volts, peak inverse volts, D C resistance less than 1K		A	..	1
11994	Type 356 ...	Smoothing 15 mH at 0 5 amp .		A	..	1
12008	Type 357	25 henries, 25 mA, 1,000 ohms ± 15%		A	..	1
12018	Type 358	8 henries 200 ohms, D C resistance		A	..	1
12019	Type 359	100 henries, 3,500 ohms, D C. resistance		A	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
12021	Type 360 ...	0.5 henry, 250 mA, 2 K.V.A. insulation, approx. 3 in. × 2 in. × 2 in. high; tag panel.		A	each	1
12022	Type 361 ...	10 mH, 0.4 ohms approx., 3 in. × 2 in. × 2 in. high		A	..	1
12115	Type 363 ...	1 henry ± 15%; iron core, 2 $\frac{3}{8}$ in. × 1 $\frac{3}{8}$ in. × 1 $\frac{1}{4}$ in. overall.		A	..	1
12127	Type 365 ...	Coil, wound on former, 2 $\frac{7}{16}$ in. long × $\frac{1}{2}$ in. overall; 140 $\frac{1}{2}$ turns 0.0092 in. en. covered copper wire, close wound.		A	..	1
12129	Type 366 ...	10 turns tinned copper wire, 23 S.W.G., $\frac{1}{4}$ in. i/d.		A	..	1
12134	Type 367		A	..	1
12137	Type 370 ...	3.6 henries at 2 volts, 800 cycles, with 50 mA D.C., 260 ohms D.C., moulded former, tropical.		A	..	1
12154	Type 372 ...	1.7 henries at 100 mA D.C. ...		A	..	1
12190	Type 376 ...	5.5 henries at 50 mA, 400 ohms D.C. resistance.		A	..	1
12250	Type 379 ...	25 henries at 40 mA, D.C. resistance 200 ohms, 4,000 turns of 35 S.W.G. wire. Shrouded type.		A	..	1
12301	Type 383		A	..	1
12369	Type 388 ...	Smoothing, 0.86 henries, 180 mA, 1,000 cycles.		A	..	1
12375	Type 389 ...	0.33 henries, 120 mA, 1,500 cycles, 2 $\frac{1}{2}$ in. fixing centres.		A	..	1
12469	Type 394 ...	26 amps., D.C., 0.0023 henries...		A	..	1
12471	Type 395 ...	220 mA, D.C., 12 to 14 henries.		A	..	1
12472	Type 396 ...	Inductance, 0.004–0.006 H. Current, 14 amps. D.C.		A	..	1
12473	Type 397 ...	Inductance, 10–12 H. Current, 120 mA. Complete with two terminal boards.		A	..	1
12583	Type 398 ...	4 henries at 60 mA, flattened cheeks.		A	..	1
12584	Type 399 ...	0.17 henries at 450 mA ...		A	..	1
12606	Type 401 ...	20 henries, 250 mA ...		A	..	1
11993	Type 402 ...	Smoothing, 1 henry at 150 mA, iron core.		A	..	1
12656	Type 403 ...	20 henries, 60 mA ...		A	..	1
12661	Type 404 ...	18 henries, at 26 volts A.C., 60 mA D.C.; resistance, 435 ohms.		A	..	1
12688	Type 405 ...	3 henries, iron core, bakelite moulded case.		A	..	1
12691	Type 406 ...	2 henries, 100 mA. Metal can. For inverted chassis mounting.		A	..	1
12762	Type 409 ...	4,600 turns of 32 S.W.G. en. S.C.C. on bakelite former to be:— (a) Not less than 0.76 H at 1,000 c/s. (b) Not less than 22 H at 100 c/s.		A	..	1
12769	Type 411 ...	4–20 H, 2.3 amps., 120 mA. Oil immersed, contains swinging choke and one smoothing choke.		A	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
12770	Type 412 ...	5,300 turns 35 S.W.G. en. copper, 435 ohms; 18 henries at 60 mA D.C. plus 26 volts A.C.; open type; approx. 3.69 in. × 2.56 in. × 2.19 in. high. Tropical finish.		A	each	
12785	Type 413 ...	12 henries; 5,800 turns of 42 S.W.G. double en. copper; tapped at 1,950½ turns.		A	..	1
12840	Type 414 ...	1 H, 60 mA		A	..	1
12841	Type 415 ...	1 H, 70 mA		A	..	1
12842	Type 416 ...	1 H, 140 mA		A	..	1
12843	Type 417 ...	1 H, 120 mA		A	..	1
12844	Type 418 ...	10 henries, 120 mA, 100 ohms...		A	..	1
12899	Type 420 ...	2.6 henries at 200 mA, 1 K.V. insulation. Laminated iron core; 2,100 turns at 33 S.W.G.		A	..	1
12901	Type 421 ...	Inductance, 7 H. Current, 350 mA D.C. D.C. resistance, 35 ohms approx. (400 V. ripple, 10 c/s). Insulation, 1,500 V. to core.		A	..	1
12902	Type 422 ...	Inductance, 7 H. Current, 200 mA D.C. D.C. resistance, 50 ohms approx. (240 V. ripple, 100 c/s). Insulation, 1,000 V. to core.		A	..	1
12904	Type 424 ...	Inductance, 7 H. Current, 100 mA. D.C. resistance, 35 ohms approx.		A	..	1
12912	Type 425 ...	60 mH, smoothing		A	..	1
12959	Type 432 ...	4 henries		A	..	1
13037	Type 433 ...	Inductance, 10 H. Current, 150 mA.		A	..	1
13078	Type 436 ...	47/7 henries, 100 mA. 215 ohms D.C. resistance; 4 in. × 3 in. × 2½ in.		A	..	1
13101	Type 438 ...	10 henries at 1.2 amps., 300 ohms D.C. resistance.		A	..	1
13102	Type 439 ...	10 henries at 420 mA, 150 ohms D.C. resistance.		A	..	1
13103	Type 440 ...	20 henries at 100 mA, 300 ohms D.C. resistance.		A	..	1
13104	Type 441 ...	20 henries at 60 mA, 300 ohms D.C. resistance.		A	..	1
13105	Type 442 ...	10 henries at 0.8 amps, 30 ohms D.C. resistance.		A	..	1
13106	Type 443 ...	10 henries at 210 mA, 150 ohms D.C. resistance.		A	..	1
13161	Type 444 ...	Mains smoothing choke, 20 henries, 120 mA.		A	..	1
13180	Type 445 ...	8 henries, 200 ohms D.C. ...		A	..	1
13182	Type 446 ...	1.7 henries, 10 ohms, 200 mA, D.C.		A	..	1
13186	Type 447 ...	6 henries, ½ in. gap		A	..	1
13206	Type 448 ...	15–20 henries, 50 mA, 600 ohms, D.C. resistance; 2 in. × 2½ in. × 3¾ in high overall dimensions.		A	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
13224	Type 449 ...	20 henries, 120 mA, mains smoothing choke. Impregnated to W.T.1000.		A	each	1
13228	Type 450 ...	Smoothing, 20 henries at 100 mA.		A	"	1
13347	Type 454 ...	Inductance at 5 volts:— 10 mA—33 henries. 20 mA—31 henries. 30 mA—26 henries.		A	"	1
13350	Type 455 ...	230 volts, 50 cycles, for H. P. mercury vapour lamp.		A	"	1
13382	Type 456 ...	5 henries		A	"	1
13387	Type 458 ...	19 henries, 200 mA., 1,006 amp. turns.		A	"	1
13390	Type 459 ...	Wound 4,350 turns of 40 S.W.G. en. copper wire on silicon steel core. Approx. 20 henries.		A	"	1
13407	Type 460 ...	30 henries, 250 mA		A	"	1
13434	Type 461 ...	20 henries, 200 mA		A	"	1
13435	Type 462 ...	Assembly of choke coil in bitumen filled can.		A	"	1
13436	Type 463 ...	15 henries, 500 mA		A	"	1
13473	Type 464 ...	90 H \pm 10 per cent., 15 mA...		A	"	1
13531	Type 467 ...	Choke for use with mercury vapour lamp.		A	"	1
13532	Type 468 ...	Choke for use with mercury vapour lamp.		A	"	1
13533	Type 469 ...	8 henries, 200 ohms, D.C. resistance. Similar to Types 358 and 445, with special fixing position.		A	"	1
13555	Type 473 ...	1 H, 200 milliamps. D.C., 480 ohms. Shell type, with iron core.		A	"	1
13571	Type 474 ...	14 H, 70 milliamps. D.C., 480 ohms. Shell type, with iron core.		A	"	1
13587	Type 475 ...	20 H, 40 mA		A	"	1
13620	Type 477 ...	4.5 H at 75 mA. D.C. resistance, 190 ohms \pm 20 per cent.		A	"	1
13643	Type 478 ...	4,500 turns 32 S.W.G., using 72 crs. laminations M.E.A. No. 59A, 0.014 in. Silcor 11, 2 in. \times 2 $\frac{1}{8}$ in. fixing centres.		A	"	1
13645	Type 479 ...	875 turns 21 S.W.G. en. 80 Pos. M.E.A. laminations No. 4A. Silcor 11 four hole fixing, 2 $\frac{1}{4}$ in. \times 2 $\frac{1}{4}$ in.		A	"	1
13655	Type 480 ...	10 henries, 20 mA		A	"	1
13692	Type 482 ...	60 H at 50 mA D.C., 1 K.V.A., 350 cycles. Charging choke.		A	"	1
13693	Type 483 ...	75 H at 55 mA D.C., 1 K.V.A., 100 cycles. Smoothing choke.		A	"	1
13705	Type 491 ...	3 H, 125 mA D.C.		A	"	1
13737	Type 496 ...	Inductance at 25 volts, 50 cycles, to be greater than 15 henries after impregnation.		A	"	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
13760	Type 497 ...	200 ohms \pm 10 per cent. D.C. resistance; inductance, 16 henries \pm 20 per cent.		A	each	1
13775	Type 498 ...	2 H at 60 mA ...		A	"	1
13784	Type 500 ...	Part of Transmitter, Type T.1131.		A	"	1
13846	Type 502 ...	1 H at 2 mA D.C. ...		A	"	1
13856	Type 504 ...	27 H, 50 mA ...		A	"	1
13877	Type 507 ...	24 H, 95 mA ...		A	"	1
13878	Type 508 ...	27 H, 50 mA ...		A	"	1
13879	Type 509 ...	22 H, 80 mA ...		A	"	1
13880	Type 510 ...	25 H, 160 mA ...		A	"	1
13904	Type 512 ...	6,200 turns 28 S.W.G. en cu. D.C. resistance, 200 ohms. Approx. size, 4.5 in. \times 4.5 in. \times 3.0 in. overall, including vertical tag panel.		A	"	1
13909	Type 513 ...	12 H. D.C. resistance, 100 ohms. Continuous D.C. current, 200 mA. Ripple current, 0.14 A peak at 100 cycles.		A	"	1
13933	Type 514 ...	1,300 turns 0.0148 in. en. cu. wire. Open type, 2.5 in. \times 1.75 in. \times 2.25 in. high, with feet and tagboard at top.		A	"	1
13936	Type 515 ...	Inductance, 0.94 H at 1 K.S. Tapped. Ratio, 2 : 1.		A	"	1
13957	Type 518 ...	50 H, 65 mA. D.C. resistance, 500 ohms.		A	"	1
14008	Type 521 ...	Inductance, 10 H. Current, 100 mA.		A	"	1
14009	Type 522 ...	Inductance, 3 H. Current, 140 mA.		A	"	1
14014	Type 523 ...	20 H, 50 mA ...		A	"	1
14015	Type 524 ...	20 H, 200 mA ...		A	"	1
14016	Type 525 ...	40 H, 25 mA ...		A	"	1
14033	Type 526 ...	2 coil:—2.4 H. 2,000 turns 36 D.S.C. Former, 1 in. \times $\frac{9}{16}$ in.		A	"	—
14050	Type 527 ...	10 H, 120 mA. Maximum resistance, 100 ohms. $3\frac{3}{8}$ in. \times $3\frac{1}{2}$ in. \times $5\frac{1}{2}$ in. high.		A	"	1
14112	Type 530 ...	200 mH, 960 turns of 30 S.W.G. en. copper wire.		A	"	1
14130	Type 531 ...	L.T. smoothing. 7 H at 225 mA. 2 K.V. insulated earth screen.		A	"	1
14131	Type 532 ...	Inductance, 20 H. Current, 140 mA.		A	"	1
14132	Type 533 ...	250 μ H at 250 mA. $5\frac{1}{2}$ in. \times $4\frac{1}{4}$ in. \times 4 in.		A	"	1
14160	Type 535 ...	1 H \pm 15 per cent., 20 mA, iron-cored insulation to frame, 350 volts.		A	"	1
14161	Type 536 ...	Inductance, 100, 100 H \pm 10 per cent. Current, 70 mA. Iron core.		A	"	1
14162	Type 537 ...	Inductance, 4 mH \pm 10 per cent.		A	"	1
14180	Type 543 ...	6,500 turns 30 S.W.G. en. wire. Resistance, 275 ohms.		A	"	1
14198	Type 546		A	"	1
14252	Type 551 ...	8 H at 12 mA ...		A	"	1
14263	Type 552 ...	Smoothing. 11 H at 60 mA ...		A	"	1
14311	Type 555 ...	1.5 H, 130 mA, D.C., 10 volts at 2,000 cycles.		A	"	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
14325	Type 557 ...	400 μ H, 1,000 cycles per second. 376 turns in 4 sections of 34 turns of 40 S.W.G en. cu. wire.		A	each	1
14378	Type 558 ...	5 H \pm 2 per cent., coil tapped. 2 $\frac{3}{16}$ in. high \times 1 $\frac{7}{8}$ in. \times 1 $\frac{3}{8}$ in. Fixing centres, 1 $\frac{9}{16}$ in. \times 1 $\frac{3}{16}$ in.		A	..	1
14379	Type 559 ...	As Type 558 but single coil ...		A	..	1
14450	Type 560 ...	40 H, 50 mA, 500 volts D.C. working.		A	..	1
14451	Type 561 ...	40 H, 50 mA, 1,000 volts D.C. working.		A	..	1
14452	Type 562 ...	40 H, 250 mA, 500 volts D.C. working.		A	..	1
14477	Type 563 ...	Smoothing. 20 H, 40 mA ...		A	..	1
14519	Type 566 ...	Inductance, 5 H. Current, 130 mA. D.C. resistance, 130 ohms. Filter choke.		A	..	1
14592	Type 567 ...	2.5 H, smoothing ...		A	..	1
14593	Type 568 ...	10 H, smoothing ...		A	..	1
14618	Type 569 ...	4 H at 120–150 mA. D.C. Resistance, 150 ohms. 3 $\frac{1}{2}$ in. \times 2 $\frac{1}{8}$ in. \times 2 $\frac{1}{4}$ in. 3 $\frac{1}{2}$ in. fixing centres.		A	..	1
14658	Type 573 ...	15 H at 40 mA ...		A	..	1
14695	Type 575 ...	Inductance, 4 H. Current, 50 mA. Smoothing chokes.		A	..	1
14701	Type 577 ...	Inductance, 1 H. Current, 65 mA.		A	..	1
14729	Type 582 ...	10 H, 200 mA ...		A	..	1
14765	Type 585 ...	Inductance, 20 Henries. Current, 50 mA.		A	..	1
13717	Type 586 ...	Inductance, 10 mH \pm 5 per cent. inductance. Basket wound on ebonite former, $\frac{1}{2}$ in. dia. \times $\frac{3}{8}$ in. long, with centre hole for 6 B.A. screws.		A	..	—
14860	Type 590 ...	Inductance, 15 H. 4,250 turns of 36 S.W.G. enam. copper wire.		A	..	1
14885	Type 593 ...	Inductance, 20 H. Current, 20 mA. Size, 3 in. \times 2 in. \times 2 in. overall. 7,500 turns of 0.006 in. enam. copper wire, Fixing centres, 2 $\frac{3}{4}$ in.		A	..	1
14992	Type 596 ...	Inductance, 10 H. Current, 10 mA low capacity. Wave-wound.		A	..	1
15073	Type 600 ...	Inductance, 15 H. Current, 80 mA. Iron core.		A	..	1
15180	Type 605 ...	Inductance, 0.6 H \pm 20 per cent. D.C. resistance, 34 ohms \pm 10 per cent. Size, 1 $\frac{7}{8}$ in. \times 2 $\frac{3}{8}$ in. \times 1 $\frac{3}{8}$ in. approx.		A	..	1
15181	Type 606 ...	Inductance, 0.95H, D.C. resistance, 120 ohms \pm 10 per cent. Size, 1 $\frac{7}{8}$ \times 2 $\frac{3}{8}$ in. \times 1 $\frac{3}{8}$ in. approx.		A	..	1
15228	Type 611 ...	Inductance, 6 H, 150 mA. D.C. resistance, 140 ohms \pm 10 per cent. Dimensions, base 2 $\frac{1}{2}$ in. \times 2 $\frac{3}{8}$ in., 3 in. high.		A	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
15277	Type 620 ...	2,100 turns 32 S.W.G. enam. copper wire. Complete with fixing brackets and tag panel.		A	each	1
15278	Type 621 ...	5,300 turns 40 S.W.G. enam. copper wire, complete with fixing brackets and tag panel.		A	..	1
15904	Type 623 ...	Inductance, 15 H. Current, 20 mA. D.C. resistance, 700 ohms. Overall dimensions, $2\frac{5}{16}$ in. \times $3\frac{3}{8}$ in. \times $2\frac{3}{8}$ in., with $3\frac{1}{16}$ in. fixing centres.		A	..	1
15962	Type 630 ...	Inductance, 5 H. Current, 10 mA. 1,950 turns of 37 S.W.G. en. cu. wire. Bakelite bobbin. 1,000 volts A.C. test to Core. Overall dimensions, excluding mounting feet and tags, 1.89 in. \times 1.312 in. \times 1.609 in.		A	..	1
15996	Type 634 ...	Inductance, 5 H. Current, 10 mA. 1,950 turns of 37 S.W.G. en. cu. wire. Bakelite bobbin. 1,000 volts A.C. test to core. Overall dimensions, excluding mounting feet and tags, 1.89 in. \times 1.312 in. \times 1.609 in.		A	..	1
15998	Type 635 ...	Inductance, 1 H. Current, 75 mA.		A	..	1
16002	Type 637 ...	Inductance, 40 H. Current, 1,000 cycles. 4,000 turns 42 S.W.G. Dimensions, $1\frac{33}{64}$ in. \times $1\frac{3}{8}$ in. dia. Fixing centres, $1\frac{1}{8}$ in.		A	..	1
16058	Type 640 ...	Inductance, 25 H \pm 10 per cent. at 50 volts. Current, 50 cycles, 40 mA D.C. D.C. resistance, 50 ohms \pm 10 per cent.		A	..	1
16116	Type 642 ...	Inductance, 2 H. Current, 30 mA. Size, $3\frac{1}{4}$ in. high \times $2\frac{1}{8}$ in. \times $1\frac{1}{8}$ in. 4 fixing feet. Hole centres, $1\frac{3}{8}$ in. \times $1\frac{1}{8}$ in.		A	..	1
16152	Type 644 ...	Inductance, 2 H. Current, 200 mA.		A	..	1
16153	Type 645 ...	Inductance, 2 H. Current, 20 mA.		A	..	1
16188	Type 649 ...	Inductance, 20 H. Current, 200 mA.		A	..	1
16200	Type 654 ...	Inductance, 100 H. Current, 20 mA.		A	..	1
16201	Type 655 ...	Inductance, 20 H. Current, 120 mA.		A	..	1
16202	Type 656 ...	Inductance, 20 H. Current, 20 mA.		A	..	1
16208	Type 657 ...	Inductance, 2 H. Current, 80 mA.		A	..	1
16257	Type 660 ...	Inductance, 20 H. Current, 60 mA.		A	..	1
16270	Type 663 ...	Inductance, 4 H. Current, 130 mA. D.C. resistance, 140 ohms \pm 20 per cent. 5 volts, 50 cycles. A.C. (Inductance to be greater than 4 H.)		A	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
16271	Type 664 ...	Inductance, 7 H at 5 volts. Current, 30 mA D.C. D.C. resistance, 140 ohms \pm 20 per cent. Polarising current, 50 c/s A.C. (inductance to be greater than 7 H).		A	each	1
16272	Type 665 ...	Inductance, 4.2 H at 2 volts. Current, 10 mA D.C. D.C. resistance, 330 ohms \pm 20 per cent. 50 cycles A.C. polarising current.		A	..	1
16807	Type 693 ...	Inductance, 4.5 H. Current, 90 mA 5 volts A.C. D.C. 2 as one unit.		A	..	—
16887	Type 699 ...	Inductance, 0.65 H \pm 4 per cent. at 1 volt or less at 1,000 c.p.s.		A	..	—
16950	Type 721 ...	2 coils, each of 4.5 H, 90 mA, in sealed can.		A	..	—
16956	Type 723 ...	Current, 200 mA. Double coil choke, each 2 H \pm 20 per cent. 10 volts A.C., 50 ohms. Resistance, 77 ohms.		A	..	—
16967	Type 725 ...	5 per cent. wax impregnated sealed metal can. Inductance, 4 mH.		A	..	—
16972	Type 726 ...	Inductance, 20 H. Current, 150 mA.		A	..	—
16973	Type 727 ...	Inductance, 100 H. Current, 25 mA.		A	..	—
16974	Type 728 ...	Inductance 20 H. Current, 5 mA.		A	..	—
16976	Type 730 ...	Inductance, 20 H. Current, 60 mA.		A	..	—
16977	Type 731 ...	Inductance, 20 H. Current, 100 mA.		A	..	—
16979	Type 732 ...	Inductance, 20 H. Current, 20 mA.		A	..	—
16995	Type 737 ...	Inductance, 10 H. Current, 50 mA, 50 cycles, D.C. Resistance, 270 ohms.		A	..	—
17506	Type 738 ...	Inductance, 6–18 H. Current, 0.8 amp.		A	..	—
17516	Type 740 ...	Inductance, 9 H. Current, 128 mA.		A	..	—
17554	Type 747 ...	2 coils, each 1,800 turns 34 S.W.G., in sealed metal can.		A	..	—
17555	Type 748 ...	90 mA, D.C., 5 volts, 50 cycles. A.C. D.C. resistance, 15 ohms \pm 20 per cent.		A	..	—
17694	Type 762 ...	7,500 turns of 0.006 enamel copper wire. 2 M.		A	..	—
—	R.F. No. 56	Army ZC.15913	A	..	—
	CHOKE CONDENSER UNITS.					
14272	Type 2 ...	S.R.B.P. 1 $\frac{7}{16}$ in. \times 2 $\frac{1}{4}$ in. \times $\frac{1}{16}$ in. Used on Transmitter Unit, Type 53.		A	..	1
	CHOKE-UNITS:—					
8463	Type 1 ...	Filament		A	..	1
8464	Type 2 ...	H.T. key and microphone ...		A	..	1
2943	Type 8 ...	3 coils wound on paxolin tubular former.		A	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKE-UNITS					
	<i>—cont.</i>					
3615	Type 11 ...	Grid choke and grid lines (2), comprising 16 turns 30 S.W.G. D.S.C. wire on former.		A	each	1
3760	Type 14 ...	Supersedes choke-unit, Type 7, static drain.		A	"	1
4473	Type 18 ...	3 coils wound on S.R.P. tube ... <i>Coil 1.</i> 323½ turns of 29 D.S.C. wire. <i>Coil 2.</i> 462 turns of 36 D.S.C. wire. <i>Coil 3.</i> 300 turns of 37 D.S.C. wire.		A	"	1
5848	Type 22		A	"	1
11255	Type 25		A	"	1
11536	Type 29 ...	Screened assembly; complete with L.T. choke and "Condenser, Type 133", Ref. No. 10C/8010.		A	"	1
11537	Type 30 ...	Screened assembly; complete with H.T. choke and "Condenser, Type 133", Ref. No. 10C/8010.		A	"	1
12290	Type 35 ...	125 turns, 36 S.W.G. en. and S.S.C. Leeson, wound on S.R.B.P. former, 0.37 in. dia. × 1.25 in., with foot, 0.5 in. sq. × 1 in.		A	"	1
12622	Type 36 ...	Two chokes, wound on iron cores, 1½ in. × 2½ in. × ¾ in.:— 40 henries, 10mA, D.C. resistance approx. 760 ohms; 7 henries, 75mA, D.C. resistance approx. 170 ohms.		A	"	1
12643	Type 37 ...	S.R.B.P. sheet, 2.75 in. × 1.50 in. × 0.06 in.		A	"	1
12646	Type 38 ...	S.R.B.P. sheet, 3.25 in. × 1.63 in. × 0.06 in.		A	"	1
13153	Type 43 ...	3 chokes on mounting strip ...		A	"	1
13560	Type 45 ...	Crystal compensator unit. S.R.B. panel, 1.38 in. × 1.75 in. × 0.06 in.; 4 tags; 2 fixing holes, 0.120 in. dia. at 1.37 in. centres.		A	"	1
13667	Type 48 ...	Matched choke and condenser, iron core.		A	"	1
14233	Type 50 ...	M.S. bracket, 24 S.W.G., 3.25 in. × 1.12 in. wide, with feet 0.5 in.		A	"	1
	CONDENSER ASSEMBLIES:—					
11572	Type 1 ...	Comprises 2 variable condensers, complete with operating gear.		A	"	1
11587	Type 3 ...	Tuning, comprises 4 variable condensers with operating gear		A	"	—
12595	Base plate assembly	6¼ in. long × 2½ in. track:—1 ⅞ in. × ½ in. deep, 6 fixing holes, metal zinc-plated.		A	"	1
	CONDENSER-ASSEMBLY UNITS:—					
14847	Type 156 ...	For fitting to receiving units, Types 50 and 184.		A	"	1

CONDENSERS, FIXED AND VARIABLE**PREFACE**

1. The information previously given in the "Detail" column of A.P.1086 varied, and in many cases was insufficient to establish positive identification.

2. All condensers, fixed and variable, have now been classified into distinct groups; and will, in future, be shown in A.P.1086 in rising order of capacity within these groups. Other Services' reference numbers, where known, are also included.

3. Classification of the whole range of condensers has not been completed. This edition covers FIXED CONDENSERS in the revised form. Variable condensers and other headings are shown still with the emphasis on type numbers.

4. *Abbreviations.* (a) In "mounting" column: SUSP=suspension; UPRT=upright; INVT=inverted; CLMP=clamp; UP/SD=upright or side. (b) In "dimensions" column: M=millimeters.

5. Details of the grouping of fixed condensers are as follows:—

Type	Case or other details	Pages
CERAMIC DIELECTRIC	Solid, including cup, disc and bead ...	
" "	Transmitting type, flanged pot and disc	
" "	Tubular	
" "	Other types	
ELECTROLYTIC DIELECTRIC (DRY)	Cylindrical insulated	
" "	Cylindrical metal. (Aluminium tube, etc.)	
" "	Cylindrical moulded (pre-moulded plastic tube, usually bakelite) ...	
" "	Rectangular metal	
" "	Rectangular moulded	
" "	Rectangular waxed cardboard carton	
" "	Other types	
ELECTROLYTIC DIELECTRIC (WET)	All types	
ELECTROLYTIC DIELECTRIC	Other types, not classifiable under above headings	
MICA DIELECTRIC ...	Heavy rectangular steel or iron, e.g. High Voltage and Power Factor, correction types	
" "	Moulded in types, capacity less than 0.001 mfd. (including stacked foil, and metallized, but not protected, mica)	
" "	Moulded in types, capacity 0.001 mfd. and upwards (including stacked foil, and metallized, but not protected, mica)	
" "	Protected types, capacity less than 0.001 mfd.	
" "	Protected types, capacity 0.001 mfd. and upwards	
" "	Rectangular metal	
" "	Rectangular moulded (pre-moulded plastic cases, usually bakelite) ...	
" "	Other types, including open clamp...	
PAPER DIELECTRIC	Cylindrical insulated covering, baked paper or fibre, paxolin and similar materials	
" "	Cylindrical metal (metal tube is integral part of the construction) ...	
" "	Cylindrical plastic (pre-moulded bakelite or other plastic case)	
" "	Rectangular, capacity less than 1 mfd.	
" "	Rectangular, capacity 1 mfd. and upwards	
" "	Rectangular steel or other case (static power condensers)	
" "	Other types of highly specialised nature	<i>No entries to date</i>

SECTION 10G

FIXED CONDENSERS

VOTE 3 B. 4

1	2	3	4	5		7	8		9	10	11	12	13	14
				Working	Test		Length	Diameter						
3042	Type 1453	1	20	500	1,500	11	11	SUSP	—	—	—	B	each	3
11491	Type 542	1.5	15	500	1,500	11	11	SUSP	—	—	—	B	"	5
5661	Type 3086	2	20	500	1,500	11	11	SUSP	—	—	—	B	"	5
16399	Type 5597	2.2	.5 pf.	500	1,500	16	16	SUSP	52590	ZC.3259	—	B	"	3
14152	Type 4661	2.2	25	500	1,500	9	9	SUSP	—	—	—	B	"	3
4632	Type 2423	3	10	500	1,500	9	9	SUSP	—	ZC.12240	—	B	"	3
11711	Type 3558	3	10	500	1,500	9	9	SUSP	—	ZA.21167	—	B	"	6
5960	Type 3269	3	10	500	1,500	9	9	SUSP	—	—	—	B	"	5
14153	Type 4662	3.3	.5 pf.	500	1,500	9	9	SUSP	—	—	—	B	"	5
17004	Type —	4	.5 mmfd.	500	1,500	7	14	SUSP	W.4397	—	—	B	"	—
729	Type 815	4	.5 mmfd.	500	1,500	7	14	SUSP	W.3756	—	—	B	"	5
5810	Type 3197	4	20	500	1,500	4.5	5	SUSP	—	ZA.14849	—	B	"	3
2108	Type 982	5	5	500	1,500	11	11	SUSP	—	—	—	B	"	3
12147	Type 3796	5	10	500	1,500	11	13	SUSP	—	—	—	B	"	3
4768	Type 2500	5	20	500	1,500	13	13	SUSP	—	ZC.10675	—	B	"	3
3611	Type 1818	6	.5 mmfd.	500	1,500	11	13	SUSP	—	—	—	B	"	5
12188	Type 3821	6	5	500	1,500	9	11	SUSP	—	—	—	B	"	5
545	Type 759	6	10	500	1,500	13	13	SUSP	—	ZA.12513	—	B	"	3
12061	Type 3737	6	1 mmfd.	500	1,500	9	11	SUSP	—	—	—	B	"	3
14098	Type 4639	7	.5 mmfd.	500	1,500	9	11	SUSP	—	—	—	B	"	5
13275	Type 4292	7	10	500	1,500	13	13	SUSP	—	—	—	B	"	3
11579	Type 3543	7	1 mmfd.	500	1,500	9	11	SUSP	—	—	—	B	"	3
4240	Type 2185	7.5	5	500	1,500	9	13	SUSP	—	ZC.15641	—	B	"	3
11657	Type 3555	7.5	2 mmfd.	500	1,500	13	13	SUSP	—	—	—	B	"	5
3860	Type 1949	8	5	500	1,500	11	11	SUSP	—	—	—	B	"	5
5881	Type 3229	8	10	500	1,500	13	13	SUSP	—	—	—	B	"	5
5357	Type 2905	8	10	500	1,500	13	13	SUSP	—	—	—	B	"	5
13817	Type 4532	8	1 mmfd.	500	1,500	9	13.5	SUSP	—	—	—	B	"	3
12062	Type 3738	10	20	500	1,500	1	13	SUSP	—	ZA.17169	—	B	"	3
11569	Type 3538	11.5	.5 mmfd.	500	1,500	9	11	SUSP	—	—	—	B	"	3

SECTION 10C—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (mm.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	GERAMIC DIELECTRIC—cont. Solid—cont.												
4646	Type 2431	15	10	500	1,500	11	13	SUSP	—	ZC.3263	B	each	3
13138	Type 4230	15	20	500	1,500	11	13	SUSP	—	ZC.15640	B	"	3
728	Type 814	16	.2 mmfd	500	1,500	11	11	SUSP	—	—	B	"	5
15215	Type 5197	18	5	500	1,500	16	16	SUSP	52602	—	B	"	5
16413	Type 5611	18	10	500	1,500	16	16	SUSP	52601	—	B	"	3
11860	Type 3644	18-5	1 1	500	1,500	9	11	SUSP	—	ZC.18569	B	"	3
2707	Type 1300	20	2	500	1,500	9	11	SUSP	—	ZC.18439	B	"	3
3200	Type 1555	20	10	500	1,500	11	13	SUSP	W.2823	ZC.8985	B	"	3
12047	Type 3733	20	20	500	1,500	11	13	SUSP	—	ZC.2002	B	"	3
11920	Type 3667	22	10	500	1,500	9	11	SUSP	—	—	B	"	3
11920	Type 3126	22	10	500	1,500	9	11	SUSP	—	—	B	"	3
5701	Type 430	25	2	500	1,500	11	13	SUSP	—	ZC.11075	B	"	5
10975	Type 2760	25	5	500	1,500	11	11	SUSP	—	ZC.12995	B	"	3
5168	Type 1153	25	10	500	1,500	11	13	SUSP	W.3955	ZC.12008	B	"	3
2403	Type 1510	25	10	500	1,500	11	13	SUSP	—	ZC.1683	B	"	3
3110	Type 3130	25	10	500	1,500	11	13	SUSP	—	—	B	"	5
5705	Type 3074	25	20	500	1,500	11	16	SUSP	—	ZC.15639	B	"	5
5649	Type 5616	27	5	500	1,500	16	16	SUSP	52132	—	B	"	3
16418	Type 4663	27	10	500	1,500	9	11	SUSP	—	—	B	"	5
14154	Type 5490	27	10	500	1,500	16	16	SUSP	—	—	B	"	3
16287	Type 405	30	2	500	1,500	11	13	SUSP	—	—	B	"	3
10395	Type 3308	30	2	500	1,500	11	13	SUSP	—	—	B	"	5
5999	Type 1685	30	5	500	1,500	11	11	SUSP	—	—	B	"	3
3434	Type 1397	30	10	500	1,500	11	13	SUSP	—	—	B	"	3
2920	Type —	32	5	500	1,500	9	11	SUSP	W.3937	—	B	"	3
15786	Type 2734	32	10	500	1,500	11	13	SUSP	—	—	B	"	3
5142	Type 3781	35	5	500	1,500	11	11	SUSP	50107	—	B	"	5
12113	Type 2813	35	10	500	1,500	11	13	SUSP	—	—	B	"	5
5221	Type 5621	39	10	500	1,500	16	16	SUSP	52612	ZA.19008	B	"	3
16423	Type 3645	40	1	500	1,500	9	11	SUSP	—	—	B	"	3
11861	Type 1942	40	.5 mmfd.	500	1,500	11	13	SUSP	—	—	B	"	5
3853													

SECTION 100—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (mm.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1													
	CERAMIC DIELECTRIC—cont.												
	Solid—cont.												
14211	Type 4688	40	5	500	1,500	9	11	SUSP	—	—	B	each	5
2808	Type 1311	40	10	500	1,500	11	13	SUSP	W.4143	ZA.21379	B	"	5
13709	Type 4493	40	20	500	1,500	9	11	SUSP	—	—	B	"	5
14564	Type 4850	47	10	500	1,500	9	11	SUSP	—	—	B	"	5
15914	Type 5289	47	10	500	1,500	16	16	SUSP	52615	—	B	"	5
14141	Type 4652	47	20	500	1,500	9	11	SUSP	—	—	B	"	3
3854	Type 1943	50	1	500	1,500	9	11	SUSP	—	ZA.14667	B	"	5
14476	Type 4803	50	1	500	1,500	11.5	11	SUSP	—	—	B	"	5
10568	Type 410	50	2	500	1,500	13	13	SUSP	—	—	B	"	3
308	Type 656	50	5	500	1,500	11	13	SUSP	—	—	B	"	3
3043	Type 1454	50	10	500	1,500	13	13	SUSP	—	ZA.10188	B	"	3
5296	Type 2849	50	10	500	1,500	13	13	SUSP	W.2321	ZA.12996	B	"	3
4762	Type 2494	50	20	500	1,500	11	11	SUSP	—	ZC.3266	B	"	3
3560	Type 1775	60	2	500	1,500	11	11	SUSP	W.7928	ZC.12009	B	"	3
13261	Type 4281	75	5	500	1,500	13	13	SUSP	—	—	B	"	3
11851	Type 3636	75	10	500	1,500	13	13	SUSP	W.5239	ZC.8047	B	"	3
13	Type 569	80	5	500	1,500	11	11	SUSP	—	ZA.14802	B	"	3
16437	Type 5635	100	10	500	1,500	16	16	SUSP	W.5228	—	B	"	3
3436	Type 1687	100	5	500	1,500	11	11	SUSP	W.2572	ZA.19921	B	"	3
5956	Type 3265	100	10	500	1,500	13	13	SUSP	—	ZC.8983	B	"	3
4760	Type 2492	100	20	500	1,600	13	13	SUSP	—	—	B	"	3
14205	Type 4686	200	2	500	1,500	11.5	11	SUSP	—	—	B	"	6
13048	Type 4197	250	10	500	1,500	12	11	SUSP	—	—	B	"	3
	Transmitting Type, Flanged Pot and Disc—												
11853	Type 3638	20	5	4,000	7,500	80	33	UPRT	—	—	B	"	2
2668	Type 1278	20	20	7,500	15KV.	30	30	NONE	—	—	B	"	2
11852	Type 3637	25	5	4,000	7,500	80	33	UPRT	—	—	B	"	2
15122	Type 5124	35	40	4,000	7,500	57	3	NONE	—	—	B	"	1
5767	Type 3154	50	20	7,500	15KV	105	38	NONE	—	—	B	"	1

SECTION 100—*cont.*

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	Voltage		Overall Dimensions (mm.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom of Qty	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	CERAMIC DIELECTRIC— <i>cont.</i> Transmitting Type, Flanged Pot and Disc— <i>cont.</i>												
4989	Type 2679	100	5	7,500	15KV.	105	38	CLIP	—	—	B	each	1
14528	Type 4836	100	20	7,500	15KV.	63	30	UPRT	—	—	B	"	1
4506	Type 2332	500	5	1,000	5,000	77	33	NONE	—	—	B	"	1
13622	Type 4456	500	5	3,000	6,000	77	33	NONE	—	—	B	"	1
15095	Type 5108	500	10	15KV.	20KV.	98	38	NONE	—	—	B	"	1
2138	Type 991	600	10	5,000	10KV.	120	38	NONE	—	—	B	"	—
2366	Type 1148	.001	10	9,600	20KV.	105	57	NONE	—	—	B	"	1
12187	Type 3728	.001	10	10KV.	20KV.	98	78	NONE	—	—	B	"	1
12393	Type 3917	.001	20	5,000	10KV.	108	38	UPRT	—	—	B	"	3
14574	Type 4860	.001	20	7,500	15KV.	105	45	NONE	—	—	B	"	—
14529	Type 4837	.001	20	7,500	15KV.	115	45	NONE	—	—	B	"	1
4791	Type 2523	.0016	5	10KV.	20KV.	108	38	UPRT	—	—	B	"	3
	Tubular:—	mmfd.											
16053	Type 5345	.001	5	500	1,500	52	10	SUSP	—	—	B	"	3
16046	Type 5338	.001	10	500	1,500	52	10	SUSP	—	—	B	"	3
16147	Type 5405	.0015	20	300	—	22	6	SUSP	—	—	B	"	5
16094	Type 5368	.0047	20	300	—	32	9	SUSP	—	—	B	"	6
14453	Type 4785	1	.25 mmfd.	500	1,500	16	6	SUSP	—	—	B	"	5
5320	Type 2871	1	.5 mmfd.	500	1,500	15.5	6.5	SUSP	W.5070A	—	B	"	5
15862	Type 5251	1	.5 pf.	500	1,500	16	7	SUSP	—	—	B	"	5
15910	Type 5286	1	.5 pf.	500	1,500	16	7	SUSP	—	—	B	"	5
16291	Type 5494	1	.5 pf.	500	1,500	16	7	SUSP	—	—	B	"	3
12617	Type 4024	2	20	500	1,500	11	5	SUSP	—	—	B	"	5
5962	Type 3271	2	25	500	1,500	16	6	SUSP	—	—	B	"	5
5321	Type 2872	2	50	500	1,500	11	5	SUSP	—	—	B	"	5
16294	Type 5497	2.2	.5 pf.	500	1,500	16	7	SUSP	—	—	B	"	5
12895	Type 4120	2.5	10	500	1,500	11	5	SUSP	—	—	B	"	5
12894	Type 4119	3	.25 mmfd.	500	1,500	11	5	SUSP	—	—	B	"	5

SECTION 100—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (mm.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1													
	CERAMIC DIELECTRIC—cont.												
	Tubular—cont.												
5322	Type 2873	3	1 mmfd.	500	1,500	11	5	SUSP		ZA.11426	B	each	5
15873	Type 5262	3.3	.5 pf.	500	1,500	16	7	SUSP	52463		B	"	5
14464	Type 4796	3.3	.5 pf.	500	1,500	15	3	SUSP			B	"	5
3264	Type 1578	4	.25 mmfd.	500	1,500	15.5	6.5	SUSP			B	"	5
16290	Type 5493	4.7	.5 pf.	500	1,500	16	7	SUSP			B	"	5
15199	Type 5189	4.7	.5 pf.	500	1,500	16	7	SUSP.			B	"	5
15198	Type 5188	4.7	.5 pf.	500	1,500	16	7	SUSP			B	"	5
15838	Type 5228	5	.25 pf.	500	1,500	16	7	SUSP			B	"	2
15	Type 571	5	5	500	1,500	16	6	SUSP			B	"	2
3219	Type 1573	5	10	500	1,500	16	6	SUSP		ZC.0177	B	"	5
4622	Type 2413	5	10	500	1,500	15	3	SUSP			B	"	5
5323	Type 2874	5	20	500	1,500	11	5	SUSP			B	"	5
3563	Type 1778	5	2 mmfd.	500	1,500	11	5	SUSP			B	"	5
15101	Type 5114	5.6	.5 pf.	500	1,500	16	6	SUSP			B	"	2
16051	Type 5343	5.6	10	500	1,500	16	7	SUSP			B	"	3
15863	Type 5252	6	5	500	1,500	16	7	SUSP			B	"	5
15197	Type 5187	6.8	10	500	1,500	16	7	SUSP			B	"	5
13863	Type 4556	7	5	500	1,500	15	3	SUSP			B	"	5
5447	Type 2949	7	10	500	1,500	11	5	SUSP			B	"	5
5318	Type 2869	7	10	500	1,500	16	6	SUSP			B	"	5
4018	Type 2070	7	10	500	1,500	11	5	SUSP		ZA.11421	B	"	3
911	Type 877	8	1 mmfd.	500	1,500	11	5	SUSP			B	"	3
4254	Type 2199	8	.25 mmfd.	500	1,500	16	6	SUSP			B	"	3
15167	Type 5164	8.2	10	500	1,500	16	7	SUSP	52280		B	"	5
14465	Type 4797	9.5	5	500	1,500	15	3	SUSP			B	"	5
15196	Type 5186	10	.5 pf.	500	1,500	16	7	SUSP			B	"	5
16267	Type 5488	10	.5 pf.	500	1,500	16	7	SUSP			B	"	5
16043	Type 5335	10	10	500	1,500	16	7	SUSP			B	"	5
15168	Type 5165	10	10	500	1,500	16	7	SUSP			B	"	5
16293	Type 5496	10	10	500	1,500	16	7	SUSP			B	"	5
12234	Type 3833	10	1	500	1,500	16	6	SUSP			B	"	5

SECTION 10C—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (mm.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1													
2073	CERAMIC DIELECTRIC—cont.												
	Tubular—cont.												
	Type 963	10	2½	500	1,500	16	6	SUSP	—	—	B	each	3
3260	Type 1574	10	3	500	1,500	17	5.5	SUSP	—	—	B	"	3
5565	Type 3028	10	5	500	1,500	16	6	SUSP	—	—	B	"	5
3265	Type 1579	10	5	500	1,500	30	8	SUSP	—	ZC.2251	B	"	5
3036	Type 1447	10	.5 mmfd.	500	1,500	12	5	SUSP	—	—	B	"	5
5301	Type 2853	10	10	500	1,500	15	6	SUSP	—	—	B	"	3
4409	Type 2275	10	10	500	1,500	17	5.5	SUSP	—	—	B	"	5
13805	Type 4521	10	1 mmfd.	500	1,500	16	6	SUSP	51382	—	B	"	5
16255	Type 5485	12	.5 pf.	500	1,500	16	7	SUSP	—	—	B	"	5
15195	Type 5185	12	.5 pf.	500	1,500	25	7	SUSP	—	—	B	"	5
15174	Type 5171	12	10	500	1,500	16	7	SUSP	—	—	B	"	5
4493	Type 2319	15	.25 mmfd.	500	1,500	16	6	SUSP	—	—	B	"	5
13808	Type 4524	15	1 mmfd.	500	1,000	22	6	SUSP	—	—	B	"	5
16485	Type 5683	15	1	500	1,500	16	7	SUSP	—	—	B	"	3
4233	Type 2178	15	5	500	1,500	16	7	SUSP	—	—	B	"	3
3337	Type 1643	15	5	500	1,500	40	12	SUSP	—	—	B	"	5
16292	Type 5495	15	10	500	1,500	25	7	SUSP	—	—	B	"	3
15871	Type 5260	15	10	500	1,500	25	7	SUSP	—	—	B	"	5
15173	Type 5170	15	10	500	1,500	16	7	SUSP	—	—	B	"	5
713	Type 809	15	10	500	1,500	22	6	SUSP	—	ZC.0180	B	"	5
3261	Type 1575	15	10	500	1,500	16	6	SUSP	—	—	B	"	3
3567	Type 1782	15	2 mmfd.	500	1,500	40	12	SUSP	—	—	B	"	5
4251	Type 2196	16.4	.5 mmfd.	500	1,500	16	6	SUSP	—	—	B	"	3
862	Type 863	17	2	500	1,500	15	6	SUSP	—	—	B	"	5
15835	Type 5225	18	10	500	1,500	25	7	SUSP	—	—	B	"	5
12233	Type 3832	20	1	500	1,500	11	4	SUSP	—	—	B	"	1
3574	Type 1788	20	2	500	1,500	17	5	SUSP	—	—	B	"	5
15854	Type 5244	20	.2 pf.	500	1,500	16	7	SUSP	—	—	B	"	5
4486	Type 2312	20	.5 mmfd.	500	1,500	16	4	SUSP	—	—	B	"	5
5951	Type 3261	20	5	500	1,500	22	6	SUSP	—	—	B	"	5
14260	Type 4709	20	5	500	1,500	22	6	SUSP	—	ZA.1633	B	"	5

SECTION 10C—cont.

FIXED CONDENSERS

VOTE 3 B. 4

1	2	3	4	5		6	7		8	9	10	11	12	13	14
				Working	Test		Length	Diameter							
Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		Overall Dimensions (mm.)	Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit	Qty.		
				Working	Test										
1	CERAMIC DIELECTRIC—cont.														
	Tubular—cont.														
3927	Type 1996	20	10	500	1,500	11	4	SUSP					B	each	3
3451	Type 1702	20	10	500	1,500	30	8	SUSP					B	"	3
5560	Type 3023	20	10	500	1,500	40	12	SUSP					B	"	5
5319	Type 2870	20	15	500	1,500	16	6	SUSP					B	"	5
5450	Type 2952	20	15	500	1,500	40	12	SUSP					B	"	5
4794	Type 2525	20	25	500	1,500	17	5	SUSP					B	"	5
16137	Type 5395	22	.5	500	1,500	16	6	SUSP					B	"	5
15175	Type 5172	22	5	500	1,500	16	7	SUSP					B	"	5
15868	Type 5257	22	5	500	1,500	25	7	SUSP					B	"	5
15105	Type 5118	22	10	500	1,500	16	6	SUSP					B	"	3
4253	Type 2198	22	10	500	1,500	16	6	SUSP					B	"	3
13335	Type 4340	25	24.4	500	1,500	16	4	SUSP					B	"	5
3266	Type 1580	25	2	500	1,500	60	14	SUSP					B	"	5
3675	Type 1861	25	2 1/2	500	1,500	16	4	SUSP					B	"	2
672	Type 789	25	10	500	1,500	25	9	SUSP					B	"	5
16052	Type 5344	27	5	500	1,500	16	7	SUSP					B	"	3
15106	Type 5119	27	10	500	1,500	16	6	SUSP					B	"	3
15832	Type 5222	27	10	500	1,500	25	7	SUSP					B	"	5
16049	Type 5341	27	10	500	1,500	16	7	SUSP					B	"	3
4488	Type 2314	30	2	500	1,500	17	5	SUSP					B	"	5
2075	Type 965	30	5	500	1,500	16	6	SUSP					B	"	5
3262	Type 1576	30	5	500	1,500	16	6	SUSP					B	"	5
3566	Type 1781	30	2	500	1,500	29	7	SUSP					B	"	5
5541	Type 3004	30	10	500	1,500	20	8	SUSP					B	"	5
874	Type 868	30	10	500	1,500	29	7	SUSP					B	"	5
16130	Type 5388	33	.5 pf.	500	1,500	16	7	SUSP					B	"	5
16050	Type 5342	33	5	500	1,500	16	7	SUSP					B	"	5
15869	Type 5258	33	10	500	1,500	16	7	SUSP	52854				B	"	5
861	Type 862	35	2	500	1,500	30	7.5	SUSP					B	"	5
15833	Type 5223	39	.5 pf.	500	1,500	16	7	SUSP					B	"	1

SECTION 10C—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mmd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (mm.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty	Qty. Carton
				Working	Test	Length	Diameter						
1	CERAMIC DIELECTRIC—cont. Tubular—cont.												
16445	Type 5643	39	5	500	1,500	16	7	SUSP	52855	—	B	each	3
16149	Type 5407	39	10	500	1,500	16	7	SUSP	—	—	B	"	5
853	Type 858	40	2	500	1,500	29	7	SUSP	—	—	B	"	5
14259	Type 4708	40	5	500	1,500	22	6	SUSP	—	—	B	"	5
3089	Type 1495	40	10	500	1,500	15	3	SUSP	—	—	B	"	5
858	Type 860	45	2	500	1,500	45	9	SUSP	—	—	B	"	5
15834	Type 5224	47	.5 Pf.	500	1,500	16	7	SUSP	—	—	B	"	5
15226	Type 5205	47	5	500	1,500	35	10	SUSP	—	—	B	"	5
15147	Type 5145	47	5	500	1,500	16	7	SUSP	—	—	B	"	5
15170	Type 5167	47	10	500	1,500	16	7	SUSP	—	—	B	"	5
16289	Type 5492	47	10	500	1,500	35	10	SUSP	—	—	B	"	5
857	Type 859	48	2	500	1,500	16	6	SUSP	—	—	B	"	3
2079	Type 969	50	1	500	1,500	16	6	SUSP	—	—	B	"	5
4630	Type 2421	50	2	500	1,500	16	6	SUSP	—	—	B	"	5
3267	Type 1581	50	2	500	1,500	45	9	SUSP	—	—	B	"	5
14880	Type 5007	50	2	500	1,500	16	7	SUSP	—	—	B	"	5
13334	Type 4339	50	2	500	1,500	16	4	SUSP	—	—	B	"	5
2874	Type 1366	50	2 $\frac{1}{2}$	500	1,500	16	6	SUSP	—	—	B	"	5
3573	Type 1789	50	5	500	1,500	29	7	SUSP	—	—	B	"	3
2718	Type 1321	50	5	500	1,500	16	6	SUSP	—	—	B	"	5
13806	Type 4522	50	5	500	1,500	22	6	SUSP	—	—	B	"	5
13475	Type 4406	55	1	500	1,500	15	4	SUSP	—	—	B	"	5
16765	Type 5933	56	10	500	1,500	35	10	SUSP	—	—	B	"	5
16244	Type 5475	56	10	500	1,500	16	7	SUSP	—	—	B	"	5
2561	Type 1208	60	2	500	1,500	45	9	SUSP	—	—	B	"	3
2432	Type 1178	65	5	500	1,500	30	8	SUSP	—	—	B	"	3
15870	Type 5259	68	10	500	1,500	25	7	SUSP	—	—	B	"	5
859	Type 861	70	2	500	1,500	35	9	SUSP	—	—	B	"	5
15242	Type 5208	70	5	1,000	2,500	56	25	SUSP	—	—	B	"	5
2434	Type 1180	75	5	500	1,500	30	8	SUSP	—	—	B	"	3
3045	Type 1455	75	10	500	1,500	15	6	SUSP	—	—	B	"	3

SECTION 100—*cont.*

FIXED CONDENSERS

VOTE 3 B. 4

1	2	3	4	5		7	8		9	10	11	12	13	14
				Working	Test		Length	Diameter						
Ref. No.	NOMENCLATURE	Capacity mmfd	Tolerance ± %	VOLTAGE		Overall Dimensions (mm.)	Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Qty. Carton Unit		
	CERAMIC DIELECTRIC—<i>cont.</i>													
	Tubular—<i>cont.</i>													
3268	Type 1582	75	10	500	1,500	27	SUSP				B	each	5	
14258	Type 4707	80	2	500	1,500	22	SUSP				B	"	5	
18	Type 574	80	5	500	1,500	16	SUSP				B	"	5	
3263	Type 1577	80	10	500	1,500	16	SUSP				B	"	3	
3397	Type 1661	80	15	500	1,500	30	SUSP				B	"	3	
2435	Type 1181	85	5	500	1,500	30	SUSP				B	"	3	
3035	Type 1446	90	2	500	1,500	16	SUSP				B	"	5	
16138	Type 5396	91	2	500	1,500	39	SUSP				B	"	5	
12332	Type 3831	100	1	500	1,500	17	SUSP				B	"	5	
14257	Type 4706	100	2	500	1,500	22	SUSP				B	"	5	
15148	Type 5146	100	5	500	1,500	25	SUSP				B	"	5	
13807	Type 4523	100	5	500	1,500	22	SUSP				B	"	5	
5761	Type 3148	100	5	500	1,500	16	SUSP				B	"	5	
4951	Type 2641	100	5	500	1,500	16	SUSP				B	"	5	
3586	Type 1800	100	5	500	1,500	38	SUSP				B	"	5	
5663	Type 3088	100	10	500	1,500	39	SUSP				B	"	5	
714	Type 810	100	10	500	1,500	16	SUSP				B	"	5	
14515	Type 4828	100	15	500	1,500	22	SUSP				B	"	2	
667	Type 788	110	10	500	1,500	16	SUSP				B	"	5	
15839	Type 5229	115	1	750	1,500	32	SUSP				B	"	5	
16045	Type 5337	120	10	500	1,500	33	SUSP				B	"	5	
5872	Type 3220	150	10	500	1,500	33	SUSP				B	"	3	
15151	Type 5149	150	5	500	1,500	21	SUSP				B	"	3	
15974	Type 5314	150	10	500	1,500	33	SUSP				B	"	5	
15964	Type 5308	150	10	500	1,500	28	SUSP				B	"	5	
732	Type 818	160	5	500	1,500	38	SUSP				B	"	6	
16048	Type 5340	180	10	500	1,500	33	SUSP				B	"	3	
16742	Type 5910	180	10	500	1,500	52	SUSP				B	"	3	
3606	Type 1814	200	1	500	1,500	40	SUSP				B	"	3	
13890	Type 4562	200	2	500	1,500	22	SUSP				B	"	3	
5036	Type 2706	200	5	500	1,500	27	SUSP				B	"	5	

SECTION 100—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	Nomenclature	Capacity mfd.	Tolerance ±%	Voltage		Overall Dimensions (mm.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Qty. Unit
				Working	Test	Length	Diameter						
1													
	CERAMIC DIELECTRIC—cont.												
	Tubular—cont.												
4920	Type 2610	200	5	500	1,500	21	6	SUSP	—	ZA.21657	B	each	5
869	Type 865	200	10	500	1,500	40	12	SUSP	—	ZC.8634	B	"	5
2218	Type 1052	220	2	500	1,500	21	6	SUSP	—	—	B	"	3
16042	Type 5334	220	5	500	1,500	33	9	SUSP	—	—	B	"	3
16044	Type 5336	220	10	500	1,500	33	9	SUSP	—	ZA.29645	B	"	3
16288	Type 5491	220	10	500	1,500	33	9	SUSP	—	—	B	"	3
16146	Type 5404	220	20	300	900	16	6	SUSP	—	—	B	"	5
15975	Type 5315	270	10	500	1,500	33	9	SUSP	—	—	B	"	5
3216	Type 1570	300	10	500	1,500	27	6-5	SUSP	—	—	B	"	5
15840	Type 5230	330	1	500	1,500	33	9	SUSP	—	—	B	"	5
16532	Type 5730	330	5	500	1,500	33	9	SUSP	—	—	B	"	5
712	Type 808	350	10	500	1,500	30	7-5	SUSP	—	—	B	"	5
10510	Type 377	400	10	500	1,500	26.5	7	SUSP	—	ZA.11346	B	"	5
2213	Type 1051	450	2	500	1,500	27	8	SUSP	—	—	B	"	5
15149	Type 5147	470	5	500	1,500	35	10	SUSP	—	—	B	"	3
2401	Type 1151	500	5	500	1,500	27	8	SUSP	W.2571	—	B	"	5
3214	Type 1568	500	10	500	1,500	42	8	SUSP	51378	ZA.1557	B	"	5
15150	Type 5148	560	5	500	1,500	52	10	SUSP	—	—	B	"	5
3034	Type 1445	600	2	500	1,500	45	9	SUSP	—	—	B	"	3
13914	Type 4571	650	5	500	1,500	45	9	SUSP	—	—	B	"	5
		mfd.											
16047	Type 5339	680	5	500	1,500	52	10	SUSP	—	—	B	"	3
14572	Type 4858	750	5	500	1,500	45	9	SUSP	—	—	B	"	3
16249	Type 5480	820	10	500	1,500	52	10	SUSP	—	—	B	"	5
2209	Type 1048	1,001.2	1	500	1,500	53	9	SUSP	—	—	B	"	3

SECTION 100—cont.

FIXED CONDENSERS

NOTE 3 B. 4

1	2	3	4	5		6		7	8	9	10	11	12	13
				Working	Voltage	Length	Overall Dimensions (ins.) Diameter							
	ELECTROLYTIC DIELECTRIC:—													
	Dry:—													
	Cylindrical:—													
	Insulated:—													
382	Type 687	2	0 + 50	200	2	$\frac{3}{8}$	SUSP			ZA.2197	B	each	2	
2426	Type 1169	2	0 + 50	250	2	$\frac{1}{2}$	SUSP			ZC.2164	B	"	3	
4614	Type 2405	2	10 + 50	300	2	$\frac{1}{2}$	SUSP	W.2564		ZC.8440	B	"	2	
15771	Type —	2	20 + 50	350	2	$\frac{1}{2}$	SUSP			ZA.1936	B	"	2	
4950	Type 2640	4	0 + 50	350	2 $\frac{1}{2}$	$\frac{3}{8}$	SUSP				B	"	2	
11098	Type 3352	4	0 + 100	100	2	$\frac{1}{2}$	SUSP				B	"	2	
15780	Type —	4	20 + 50	12	2	$\frac{1}{2}$	SUSP			ZA.15388	B	"	2	
3317	Type 1623	8	0 + 50	150	2	$\frac{1}{2}$	SUSP			ZA.14846	B	"	2	
3781	Type 1911	8	0 + 50	200	2 $\frac{1}{2}$	$\frac{1}{2}$	SUSP				B	"	2	
11896	Type 3651	8	0 + 50	350	2 $\frac{1}{2}$	$\frac{1}{2}$	SUSP				B	"	2	
6892	Type 3209	8	10 + 50	450	2$\frac{1}{2}$	$\frac{1}{2}$	SUSP			ZC.9009	B	"	2	
3544	Type 1759	8	15 + 100	150	2 $\frac{1}{2}$	$\frac{1}{2}$	SUSP			ZA.1946	B	"	2	
16054	Type 5346	8	20 + 50	350	3	$\frac{1}{2}$	CLMP				B	"	1	
13222	Type 4271	10	0 + 50	100	2 $\frac{1}{2}$	$\frac{1}{2}$	SUSP				B	"	1	
4942	Type 2632	10	20 + 50	50	2	$\frac{1}{2}$	SUSP	W.2677		ZA.1625	B	"	2	
3474	Type 1717	12	0 + 100	200	2	$\frac{1}{2}$	SUSP			ZA.14389	B	"	2	
4095	Type 2097	20	0 + 50	50	2 $\frac{1}{2}$	$\frac{1}{2}$	SUSP				B	"	1	
2210	Type 1049	20	10 + 100	30	2 $\frac{1}{2}$	$\frac{1}{2}$	SUSP			ZC.10511	B	"	2	
5363	Type 3026	25	0 + 50	25	2 $\frac{1}{2}$	$\frac{1}{2}$	SUSP				B	"	1	
5349	Type 2897	25	0 + 50	50	2 $\frac{1}{2}$	$\frac{1}{2}$	SUSP			ZC.11482	B	"	1	
4980	Type 2670	25	10 + 100	25	3 $\frac{1}{2}$	$\frac{1}{2}$	SUSP				B	"	1	
3318	Type 1624	25	0 + 50	12	2	$\frac{1}{2}$	SUSP			ZA.20788	B	"	2	
4500	Type 2326	25	20 + 50	25	2	$\frac{1}{2}$	SUSP				B	"	2	
442	Type 710	40	20 + 50	15	2 $\frac{1}{2}$	$\frac{1}{2}$	SUSP			W.7062	B	"	2	
2965	Type 1420	50	0 + 50	12	2	$\frac{1}{2}$	SUSP				B	"	2	
3906	Type 1975	50	0 + 50	12	2	$\frac{1}{2}$	SUSP				B	"	1	
2148	Type 994	50	10 + 100	12	2 $\frac{1}{2}$	$\frac{1}{2}$	SUSP				B	"	2	
11770	Type 3593	50	20 + 50	12	2 $\frac{1}{2}$	$\frac{1}{2}$	SUSP				B	"	2	
5678	Type 3103	50	0 + 100	15	2	$\frac{1}{2}$	SUSP			W.3981	B	"	2	

SECTION 10C—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty	Carton Unit Qty.
				Working		Length	Diameter						
1	ELECTROLYTIC DIELECTRIC—cont.												
	Dry—cont.												
	Cylindrical—cont.												
	Insulated—cont.												
4413	Type 2279	50	- 0 + 50	25	2 1/2	3/8	SUSP	—	—	—	B	each	1
2653	Type 1269	50	- 20 + 50	25	2 1/2	1/2	SUSP	W.6951	ZA.11236	—	B	"	2
3794	Type 1924	50	- 0 + 50	50	2 1/2	1 1/2	SUSP	—	—	—	B	"	2
3218	Type 1572	75	- 0 + 50	12	2 1/2	1 1/2	SUSP	—	ZA.16119	—	B	"	5
2306	Type 1098	100	- 20 + 50	5	2	1 1/2	SUSP	—	—	—	B	"	2
15779	Type —	100	- 20 + 50	6	2	1 1/2	SUSP	—	ZA.11182	—	B	"	2
4703	Type 2474	100	- 0 + 100	20	2 1/2	1 1/2	SUSP	—	—	—	B	"	1
610	Type 775	160	- 20 + 50	15	2 1/2	1 1/2	SUSP	—	—	—	B	"	2
15778	Type —	200	- 20 + 50	12	2 1/2	1 1/2	SUSP	—	ZA.15386	—	B	"	2
844	Type 857	250	- 20 + 50	12	2 1/2	1 1/2	SUSP	—	—	—	B	"	2
3469	Type 1716	300	- 0 + 100	6	3	1 1/2	SUSP	—	—	—	B	"	2
5527	Type 2990	8-8-4-4	- 20 + 50	450	4	1 1/2	CLMP	—	—	—	B	"	1
	Metal:—												
10911	Type 501	2	10	25	2 1/2	3/8	STUD	—	—	—	B	"	2
13288	Type 4301	2	- 20 + 50	350	3 1/2	3/8	STUD	—	—	—	B	"	1
16212	Type 5446	2	- 20 + 100	150	2	2	SUSP	50727	ZA.27155	—	B	"	2
4779	Type 2511	4	- 0 + 50	200	2 1/2	3/8	STUD	—	—	—	B	"	2
15187	Type 5177	4	- 20 + 50	275	3 1/2	3/8	CLMP	50758	ZA.29812	—	B	"	2
16557	Type 5750	4	- 20 + 50	375	3 1/2	3/8	CLMP	—	—	—	B	"	1
5174	Type 2766	4	- 20 + 50	350	3 1/2	3/8	STUD	—	—	—	B	"	1
4780	Type 2512	4	10	500	3 1/2	3/8	STUD	—	—	—	B	"	2
4901	Type 2593	4	10	500	5 1/2	1 1/2	STUD	—	—	—	B	"	1
13286	Type 4299	4	- 20 + 50	250	3 1/2	3/8	STUD	—	—	—	B	"	1
13281	Type 4295	4	- 20 + 50	350	3 1/2	3/8	STUD	—	—	—	B	"	1
12657	Type 4036	4	- 20 + 50	350	2 1/2	3/8	STUD	—	—	—	B	"	2
11482	Type 3503	4	- 20 + 50	450	3 1/2	1 1/2	STUD	—	—	—	B	"	2
13211	Type 4260	4	- 20 + 50	500	3 1/2	1 1/2	CLMP	—	—	—	B	"	2
12663	Type 4041	4	- 20 + 50	550	5 1/2	1 1/2	STUD	—	—	—	B	"	1

SECTION 10G—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	Voltage		Overall Dimensions (Ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Qty. U
				Working		Length	Diameter						
1	ELECTROLYTIC DIELECTRIC—cont.	3	4	5	6	7	8	9	10	11	12	13	
	Dry—cont.												
	Cylindrical—cont.												
	Metal—cont.												
12429	Type 3936	8	- 0 + 50	500	3 3/4	1 1/2	STUD	W.1140		B	each	2	
4781	Type 2513	8	-10 + 50	250	2 1/4	1 1/4	STUD			B	"	1	
9610	Type 322	8	-10 + 50	500	5 1/4	1 1/4	STUD	W.5567		B	"	1	
11856	Type 3641	8	-15 + 50	450	3 3/4	1 1/4	STUD			B	"	2	
13194	Type 4232	8	20	500	5 1/4	1 1/4	STUD			B	"	1	
3639	Type 1830	8	20	500	3 1/4	1 1/4	CLMP			B	"	1	
4231	Type 2176	8	-20 + 50	120	3 1/4	1 1/4	STUD			B	"	2	
13287	Type 4300	8	-20 + 50	250	3 1/4	1 1/4	STUD			B	"	1	
4656	Type 2441	8	-20 + 50	150	3 3/8	1 1/4	STUD			B	"	1	
3138	Type 1534	8	-20 + 50	350	2 3/8	1 1/4	STUD		ZC.18810	B	"	1	
14469	Type 4801	8	-20 + 50	350	3 1/4	1 1/4	SUSP			B	"	1	
13289	Type 4302	8	-20 + 50	350	2 1/4	1 1/4	CLMP			B	"	2	
13377	Type 4362	8	-20 + 50	500	3 1/4	1 1/4	CLMP			B	"	1	
14893	Type 5011	8	-20 + 50	125	3 1/4	1 1/4	CLMP	50757		B	"	1	
14048	Type 4622	8	-20 + 50	275	2 3/4	1 1/4	SUSP			B	"	1	
13951	Type 4582	8	-20 + 50	450	3 1/4	1 1/4	STUD		ZC/AY/ 1140	B	"	1	
14020	Type 4611	8	-20 + 50	450	3	1 3/8	CLMP			B	"	1	
14070	Type 4629	8	-20 + 50	500	2 1/4	1 1/4	CLMP			B	"	1	
3779	Type 1909	8	-20 + 50	500	5 1/4	1 1/4	STUD		ZA.1751	B	"	1	
3485	Type 1719	8	-20 + 50	750	5 1/4	1 1/4	CLMP		ZA.14429	B	"	1	
16060	Type 5349	8	-20 + 50	500	5	1 1/4	CLMP		ZA.29300	B	"	2	
15735	Type —	8+8	-20 + 50	50	5	1 1/4	STUD		ZA.23743	B	"	1	
16198	Type 5439	10	- 0 + 50	50	2 3/4	1 1/4	SUSP	50723		B	"	1	
14100	Type 4641	10	-20 + 100	25	2	1 1/4	SUSP			B	"	2	
3787	Type 1917	12	-20 + 50	50	2 1/4	1 1/4	STUD			B	"	1	
13086	Type 4920	16	- 0 + 50	500	5 1/4	1 1/4	STUD			B	"	2	
4631	Type 2422	16	-10 + 50	450	4 3/4	1 1/4	CLMP			B	"	1	
	Type 2422	16	-10 + 50	475	5 1/4	1 1/4	CLMP		ZA.14433	B	"	1	

SECTION 100—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working		Length	Diameter						
1	ELECTROLYTIC DIELECTRIC—cont.	3	4	5	6	7	8	9	10	11	12	13	
	Dry—cont.												
	Cylindrical—cont.												
	Metal—cont.												
13674	Type 4482	16	-20 + 50	350	3 1/2	1 1/8	STUD	—	—	B	each	1	
5528	Type 2991	16	-20 + 50	450	3 1/8	1 1/8	CLMP	—	—	B	"	1	
14174	Type 4670	16	-20 + 50	500	4 1/8	1 1/8	CLMP	—	—	B	"	1	
13212	Type -4261	16	-20 + 50	500	5	1 1/8	CLMP	—	—	B	"	1	
4778	Type 2510	16	-20 + 50	500	5 1/2	1 1/8	STUD	—	ZC.3814	B	"	1	
15153	Type 5151	16	-20 + 50	375	5	1 1/8	CLMP	50762	ZA.28871	B	"	2	
5883	Type 3231	20	-20 + 50	50	3 1/8	1 1/8	STUD	—	—	B	"	1	
289	Type 653	20	-20 + 50	50	3 1/8	1 1/8	STUD	—	—	B	"	2	
13052	Type 4200	20	-20 + 50	150	2 7/8	1 1/8	STUD	—	—	B	"	1	
40222	Type 2074	24	-15 + 50	650	5 1/2	1 1/8	CLMP	—	—	B	"	1	
12568	Type 4013	25	20	50	3 1/8	1 1/8	STUD	—	—	B	"	2	
3531	Type 1751	25	0 + 50	25	3 1/8	1 1/8	CLMP	—	—	B	"	2	
5966	Type 3275	25	-10 + 50	200	3 1/8	1 1/8	CLMP	—	—	B	"	1	
2599	Type 1229	25	-10 + INF.	25	3 1/8	1 1/8	STUD	—	—	B	"	2	
12428	Type 3935	25	-10 + 50	25	2 5/8	1 1/8	STUD	—	—	B	"	2	
15969	Type 5311	25	-20 + 50	50	3 1/4	1 1/8	CLMP	50755	ZA.29811	B	"	1	
17022	—	25	-20 + 50	25	2 1/4	1 1/8	SUSP	—	ZC.18560	B	"	3	
10461	Type 408	25	-20 + 50	25	3 3/8	1 1/8	STUD	—	ZA.10189	B	"	3	
11977	Type 3703	25	-20 + 50	25	3 3/8	1 1/8	STUD	—	—	B	"	1	
13376	Type 4361	25	-20 + 50	25	3 3/8	1 1/8	STUD	—	—	B	"	1	
16559	Type 5752	25	-20 + 50	25	3	1 1/8	CLMP	—	—	B	"	3	
14302	Type 4715	25	-20 + 50	25	2 3/4	1 1/8	SUSP	—	—	B	"	2	
13283	Type 4296	25	-20 + 50	50	2 1/4	1 1/8	STUD	—	—	B	"	2	
13962	Type 4587	25	-20 + 50	50	2 3/8	1 1/8	SUSP	—	—	B	"	1	
12746	Type 4074	30	0 + 50	100	3 3/8	1 1/8	STUD	—	YB.04065	B	"	2	
12302	Type 3855	32	0 + 50	450	5	1 1/8	CLMP	—	—	B	"	1	
12433	Type 3938	32	-20 + 50	350	5 1/8	1 1/8	CLMP	—	—	B	"	1	
14846	Type 4991	32	-20 + 50	375	5	1 1/8	CLMP	—	—	B	"	1	
13290	Type 4303	32	-20 + 50	500	5	2	CLMP	—	—	B	"	1	

SECTION 100—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Qty. Carton Unit
				Working	Test	Length	Diameter						
1	ELECTROLYTIC DIELECTRIC—cont.	3	4	5	6	7	8	9	10	11	12	13	
	Dry—cont.												
	Cylindrical—cont.												
	Metal—cont.												
12390	Type 3914	40	- 0 + 100	12	2 1/8	1	STUD	—	—	B	each	2	
5946	Type 3256	40	- 20 + 50	12	3 1/8	1	STUD	—	—	B	"	2	
12389	Type 3913	45	- 20 + 50	15	2 1/8	1	STUD	—	—	B	"	2	
13764	Type 4508	50	0 + 50	25	3 1/8	1	STUD	—	—	B	"	2	
4501	Type 2327	50	- 10 + INF.	6	3 3/8	1	STUD	—	—	B	"	2	
13716	Type 4495	50	- 10 + 50	50	3 3/8	1	STUD	—	—	B	"	2	
9611	Type 323	50	10	12	2 7/8	1	STUD	—	—	B	"	2	
12683	Type 4046	50	- 10 + 100	12	2 1/8	1	STUD	—	—	B	"	2	
11927	Type 3670	50	- 10 + 100	60	4 1/8	1	CLMP	—	—	B	"	1	
11479	Type 3502	50	- 10 + INF.	12	3 3/8	1	STUD	—	—	B	"	2	
13193	Type 4251	50	20	12	3 1/8	1	STUD	—	—	B	"	1	
4526	Type 2339	50	20	60	3 3/8	1	SUSP	—	—	B	"	2	
14052	Type 4624	50	- 20 + 50	12	3 1/8	1	SUSP	—	—	B	"	2	
13375	Type 4360	50	- 20 + 50	12	3 1/8	1	STUD	—	—	B	"	1	
14303	Type 4716	50	- 20 + 50	50	2 1/8	1	SUSP	—	—	B	"	2	
3072	Type 1482	50	- 20 + 50	50	3 1/8	1	STUD	—	—	B	"	5	
15837	Type 5227	50	- 20 + 50	50	3 1/8	1	CLMP	50756	—	B	"	1	
16558	Type 5751	50	- 20 + 50	50	3 3/8	1	CLMP	—	—	B	"	3	
13284	Type 4297	50	- 20 + 50	75	3 3/8	1	CLMP	—	—	B	"	1	
15736	Type —	50	- 20 + 50	50	3 3/8	1	CLMP	—	—	B	"	1	
15190	Type 5180	80	- 20 + 50	100	5 1/8	1	CLMP	W.5938	ZA.23971	B	"	1	
4678	Type 2449	100	- 20 + 50	12	3 3/8	1	STUD	—	—	B	"	2	
12380	Type 3907	150	- 10 + 100	12	3 3/8	1	STUD	—	—	B	"	1	
13999	Type 4602	200	- 20 + 50	25	3 3/8	1	CLMP	—	—	B	"	2	
11995	Type 3708	250	- 20 + 50	20	3 1/8	1	CLMP	—	—	B	"	1	
11996	Type 3709	500	- 20 + 50	15	4 1/8	1	CLMP	—	—	B	"	1	
12950	Type 4139	8 + 4	20	350	3 3/8	1	CLIP	—	—	B	"	1	
5659	Type 3084	8-8	- 20 + 50	500	5 7/8	1	STUD	—	—	B	"	1	
14041	Type 4616	8-8	- 20 + 50	500	5 7/8	1	STUD	—	ZA.20663	B	"	1	

SECTION 100—*cont.*

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	Nomenclature	Capacity mfd.	Tolerance ± %	Voltage		Overall Dimensions (ins)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom of Qty.	Qty. Carton Unit
				Working		Length	Diameter						
1	ELECTROLYTIC DIELECTRIC—<i>cont.</i>												
	Dry—<i>cont.</i>												
	Cylindrical—<i>cont.</i>												
	Metal—<i>cont.</i>												
17009	Type —	8+8+8	-20 + 50	400	4 1/4	1 3/8	UPRT	—	—	ZA.20068	B	each	1
4017	Type 2069	8-8-8	-20 + 50	500	4 1/8	1 1/8	CLMP	—	—	—	B	"	2
13906	Type 4567	8+32	-20 + 50	450	4 1/8	1 1/8	CLMP	—	—	—	B	"	1
5655	Type 3080	8+32	-10 + 50	500	4 1/8	1 1/8	CLMP	—	—	—	B	"	1
4397	Type 2263	16-8	-20 + 50	350	5 1/4	1 1/4	STUD	—	—	—	B	"	1
13208	Type 4257	8-8-8	-20 + 50	400	4 1/4	1 3/4	5-pin base	—	—	—	B	"	1
	Moulded:—												
5538	Type 3001	4	10	200	2 3/8	1 1/8	SUSP	—	—	—	B	"	2
16695	Type 4597	8	20 + 50	150	2 1/8	1 1/8	SUSP	—	—	—	B	"	2
2677	Type 1281	25	-20 + 50	25	2 3/8	1 3/8	SUSP	—	—	—	B	"	2
534	Type 755	50	-20 + 50	12	2 3/8	1 1/8	SUSP	—	—	—	B	"	2
2710	Type 1303	50	-20 + 50	12	2 1/8	1 3/8	SUSP	—	—	—	B	"	2
13191	Type 4249	160	-20 + 50	15	2 3/8	1 1/4	SUSP	—	—	—	B	"	2

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Qty. per Unit
				Working		Height	Width	Depth						
1	ELECTROLYTIC DIELECTRIC—cont. Dry—cont. Rectangular:— Metal:—													
2936	Type 1414	4	-20 + 50	750	5 $\frac{1}{8}$	2 $\frac{1}{2}$	1 $\frac{1}{2}$	CLMP			B	each	1	
5434	Type 2936	8	- 0 + inf.	250	2 $\frac{1}{8}$	3 $\frac{1}{2}$	1	UPRT		ZA.1313	B	"	1	
2971	Type 1426	8	-20 + 50	450	5 $\frac{1}{8}$	2	1 $\frac{1}{8}$	CLMP			B	"	1	
11400	Type 34c3	8	-15 + 100	500	5 $\frac{1}{8}$	2 $\frac{3}{4}$	2 $\frac{3}{8}$	INVT			B	"	1	
5335	Type 2885	10	10	50	3 $\frac{1}{2}$	3	1 $\frac{1}{8}$	INVT			B	"	1	
5439	Type 2941	10	-15 + 50	450	3 $\frac{1}{2}$	2 $\frac{3}{4}$	1 $\frac{1}{8}$	UPRT			B	"	1	
3271	Type 1585	16	-10 + 30	400	5 $\frac{1}{8}$	3	2 $\frac{1}{4}$	INVT			B	"	1	
12607	Type 4021	16	-20 + 50	550	5 $\frac{1}{8}$	2 $\frac{1}{2}$	2 $\frac{1}{8}$	CLMP			B	"	1	
568	Type 768	16	-20 + 50	700	7 $\frac{1}{8}$	3 $\frac{1}{2}$	2 $\frac{1}{8}$	CLMP			B	"	1	
11399	Type 3468	16	-20 + 50	450	5 $\frac{1}{8}$	2 $\frac{3}{4}$	1 $\frac{1}{8}$	INVT			B	"	1	
532	Type 753	16	-20 + 50	250	3 $\frac{1}{8}$	2 $\frac{3}{4}$	2 $\frac{1}{8}$	INVT			B	"	2	
5592	Type 3055	16	-15 + 50	700	7 $\frac{1}{8}$	2 $\frac{1}{2}$	2 $\frac{1}{8}$	INVT			B	"	1	
2968	Type 1423	16	-20 + 50	450	5 $\frac{1}{8}$	2 $\frac{1}{2}$	2 $\frac{1}{8}$	CLMP			B	"	1	
11264	Type 3429	16	-25 + inf.	450	5 $\frac{1}{8}$	3 $\frac{1}{4}$	1 $\frac{1}{8}$	CLMP			B	"	1	
5333	Type 2883	25	-10 + 50	25	3 $\frac{1}{4}$	3	2 $\frac{1}{4}$	INVT			B	"	1	
10755	Type 464	25	- 0 + 100	25	1 $\frac{1}{8}$	2 $\frac{1}{2}$	1 $\frac{1}{8}$	FEET			B	"	5	
711	Type 807	26	-20 + 50	40	2 $\frac{3}{4}$	1 $\frac{1}{2}$	1 $\frac{1}{8}$	INVT			B	"	1	
565	Type 765	32	-20 + 50	300	5 $\frac{1}{8}$	2	1 $\frac{1}{8}$	CLMP			B	"	1	
3272	Type 1586	32	-10 + 30	400	5 $\frac{1}{8}$	3	1 $\frac{1}{8}$	CLMP			B	"	2	
2029	Type 939	32	-20 + 50	400	5 $\frac{1}{8}$	2 $\frac{3}{4}$	1 $\frac{1}{8}$	CLMP			B	"	2	
2440	Type 1186	32	-20 + 50	500	5 $\frac{1}{8}$	2 $\frac{3}{4}$	1 $\frac{1}{8}$	CLMP			B	"	1	
2605	Type 1231	32	-20 + 50	500	5 $\frac{1}{8}$	2 $\frac{1}{4}$	1 $\frac{1}{8}$	CLMP			B	"	1	
559	Type 761	32	-20 + 50	600	5 $\frac{1}{8}$	4	1 $\frac{1}{8}$	CLMP			B	"	1	
11204	Type 3407	50	25	50	3 $\frac{1}{4}$	2 $\frac{3}{4}$	1 $\frac{1}{8}$	FEET			B	"	1	
4654	Type 2439	50	-15 + 100	50	3	1 $\frac{1}{2}$	1	UPRT			B	"	1	
666	Type 837	60	-20 + 50	9	1 $\frac{1}{8}$	2 $\frac{1}{4}$	1 $\frac{1}{8}$	SIDE			B	"	1	
716	Type 812	60	-20 + 50	12	1 $\frac{1}{8}$	2 $\frac{1}{4}$	1 $\frac{1}{8}$	INVT			B	"	1	
531	Type 752	60	-20 + 50	200	5 $\frac{1}{8}$	2 $\frac{1}{4}$	1 $\frac{1}{8}$	CLMP			B	"	2	
2928	Type 1405	60	-20 + 50	600	5 $\frac{1}{8}$	5 $\frac{1}{8}$	2 $\frac{3}{4}$	CLMP			B	"	1	

SECTION 100—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	Voltage		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	ELECTROLYTIC DIELECTRIC—cont. Dry—cont. Rectangular—cont.													
5568	Type 3031	80	15	10	1 1/8	2 1/8	1 1/8	INVT				B	each	1
2606	Type 1232	160	-20 + 50	13	5 1/8	2 1/4	1 1/8	CLMP				B	"	1
2438	Type 1184	160	-20 + 50	13	2 1/8	2 1/4	1	INVT				B	"	1
652	Type 783	200	-20 + 50	35	5 1/8	2 1/4	1 1/4	INVT				B	"	1
11203	Type 3406	250	-20 + 50	12	5 1/4	3	2	UPRT				B	"	1
14430	Type 4768	250	-20 + 50	100	5 1/4	4	3	UPRT				B	"	1
5644	Type 3069	500	0 + 50	9	5 1/4	3	2	UPRT				B	"	1
653	Type 784	800	-20 + 50	12	5 1/8	2 1/4	1 1/4	INVT				B	"	1
654	Type 785	800	-20 + 50	12	5 1/8	2 1/4	1 1/4	INVT				B	"	1
13918	Type 4574	1,000	10	12	3 1/8	2 1/4	2 1/8	UPRT				B	"	1
8959	Type 234	2,000	-10 + 50	12	5 1/4	3	2	UPRT				B	"	2
13080	Type 4216	2,000	-20 + 50	25	5 1/4	3	3	UPRT		ZC.10652		B	"	1
16003	Type 5325	2,000	-20 + 50	25	5 1/4	3	3	UPRT		ZA.13418		B	"	1
9376	Type 301	4,000	-10 + 50	12	6 1/8	5	4	UPRT				B	"	1
11003	Type 3312	8-8	-10 + 30	450	5	2 1/4	1 1/8	INVT				B	"	1
11265	Type 3430	8+8	-25 + inf.	450	2	3 1/4	1 1/4	SIDE				B	"	1
4933	Type 2623	8+8+8	-20 + 50	550	2	3 1/4	1 1/4	UPRT				B	"	1
12927	Type 4132	8+8+8	8-10 + 30	850	4 1/8	3	2	UPRT				B	"	1
11979	Type 3704	8+16	{ 8-10 + 30 8+8-20 + 50 }	450)	4	3	2	UPRT		ZA.21759		B	"	1
5825	Type 3212	8+16	{ 16-15 + 50 -10 + 40 }	350)	5 1/4	3 1/8	1 1/8	INVT				B	"	1
5598	Type 3061	8+16	-20 + 50	550	5 1/4	3	2	INVT		WY/10C/ 5598		B	"	1
15781	Type —	8+24	-20 + 50	450	5 1/8	2	2 1/2	UPRT		ZA.15407		B	"	1
12838	Type 4092	16-16	-10 + 30	450	5 1/8	3 1/8	1 1/8	INVT				B	"	1
4351	Type 2256	16+16+16	-20 + 50	450	5 1/8	3	2	INVT				B	"	1
8638	Type 207	2,000 + 2,000	-20 + 50	12	5 1/4	3	3	UPRT		ZA.46345		B	"	1

SECTION 100—cont.

FIXED CONDENSERS

VOTE 3 B. 4

1 Ref. No.	2 NOMENCLATURE	3 Capacity mfd.	4 Tolerance ± %	5 VOLTAGE		6 OVERALL DIMENSIONS (ins.)			9 Mounting	10 Naval Ref.	11 Army Ref.	12 Class of Store	13 Denom. of Qty.	14 Carton Unit Qty.															
				Working		Height	Width	Depth																					
1	ELECTROLYTIC DIELECTRIC—cont. Dry—cont. Rectangular—cont. Moulded:—																												
															4876	Type 2568	15	-20 + 50	100	2 3/4	2 3/4	1 1/16	UPRT	—	—	B	each	1	
															3864	Type 1953	30	-20 + 50	100	2 3/4	2 3/4	1 1/16	UPRT	—	—	B	"	1	
															3188	Type 1543	30	-20 + 50	200	2 3/4	2 1/8	1 1/8	UPRT	9773	—	B	"	1	
															3408	Type 1670	50	-20 + 50	50	2 3/4	2 1/8	1 1/8	UPRT	—	—	B	"	2	
															2293	Type 1096	75	-20 + 50	50	2 3/4	2 1/8	1 1/8	UPRT	—	—	B	"	2	
															10802	Type 478	80	-20 + 50	100	3 1/8	2 3/4	2 1/8	UPRT	—	—	B	"	2	
															5662	Type 3087	80	-0 + 50	100	3 1/8	2 3/4	2 1/8	UPRT	—	—	B	"	1	
															2255	Type 1070	100	-0 + 50	50	2 3/4	2 1/8	1 1/8	UPRT	—	—	B	"	1	
															2729	Type 1332	250	-20 + 50	12	2 3/4	2 1/8	1 1/8	UPRT	—	—	B	"	2	
															4503	Type 2329	250	-20 + 50	12	2 3/4	2 1/8	1 1/8	UPRT	—	—	B	"	1	
															5801	Type 3188	250	-20 + 50	25	3	2 3/4	2 1/8	UPRT	—	—	B	"	1	
															3122	Waxed cardboard carton:—	8 + 8	10	450	3 1/2	2	1 3/8	CLMP	—	—	—	B	"	1
																Type 1517													
															13279	Other types:—	8	-20 + 50	440	5 3/8	4 1/2	3 3/4	UPRT	—	—	—	B	"	1
																Type 4294													

SECTION 100—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref	Army Ref	Class of Store	Denom of Qty.	Carton Unit Qty.
				Working		Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13	
	ELECTROLYTIC DIELECTRIC—cont.												
	Wet:—												
	All types:—												
4352	Type 2257	8	-20 +50	440	5 $\frac{1}{8}$	1 $\frac{1}{8}$	STUD	—	ZA.17568	B	each	1	
443	Type 711	8	-20 +50	500	5 $\frac{1}{8}$	1 $\frac{1}{8}$	STUD	—	ZA.1428	B	"	1	
2612	Type 1236	16	-0 +50	440	5 $\frac{1}{8}$	1 $\frac{1}{8}$	STUD	—	—	B	"	1	
3701	Type 1876	16	-20 +50	500	5 $\frac{1}{8}$	1 $\frac{1}{8}$	STUD	—	—	B	"	1	
3071	Type 1481	32	-0 +50	320	5 $\frac{1}{8}$	1 $\frac{1}{8}$	STUD	—	—	B	"	1	
4097	Type 2099	32	-20 +50	320	5 $\frac{1}{8}$	1 $\frac{1}{8}$	STUD	—	ZA.11348	B	"	2	
741	Type 827	32	-20 +50	320	5 $\frac{1}{8}$	1 $\frac{1}{8}$	STUD	—	—	B	"	2	
4401	Type 2267	32	15	320	5 $\frac{1}{8}$	1 $\frac{1}{8}$	STUD	—	—	B	"	1	
13085	Other types:— Type 4219	32-32	-10 +50	450	4 $\frac{1}{2}$	1 $\frac{1}{8}$	UPRT	—	—	B	"	1	

SECTION 10G—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mmd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC:— Heavy rectangular:— Steel or iron:—													
16815	Type 5962	900+900	5	—	—	22½	24½	22	UPRT	—	—	B	each	—
16812	Type 5959	6,000+ 3,000+ 1,000	5	—	—	37½	25	23	UPRT	—	—	B	"	—
16810	Type 5957	12,500+ 3,125	5	—	—	37½	25	13	UPRT	—	—	B	"	—
	Moulded:— Less than .001 mfd.:—													
15097	Type 5110	.001	10	350	1,000	11½	1½	22	SUSP	52456	—	B	"	3
16143	Type 5401	.002	10	350	1,000	11½	1½	22	SUSP	51203	ZA.28183	B	"	3
16224	Type 5455	.0027	10	350	1,000	11½	1½	22	SUSP	51104	—	B	"	5
16142	Type 5400	.005	10	350	1,000	11½	1½	22	SUSP	51209	ZC.27006	B	"	3
14710	Type 4935	.01	15	750	2,200	11½	1½	22	SUSP	—	ZA.1776	B	"	5
15008	Type 5073	.01	20	350	1,000	11½	1½	22	SUSP	—	ZA.11544	B	"	5
15098	Type 5111	.01	20	350	1,000	11½	1½	22	SUSP	—	—	B	"	3
4690	Type 2461	10	20	350	1,000	11½	1½	22	SUSP	51147	—	B	"	3
5640	Type 3065	15	15	350	750	11½	1½	22	SUSP	—	—	B	"	2
2406	Type 1155	15	15	350	1,000	11½	1½	22	SUSP	—	—	B	"	5
15864	Type 5253	20	5	350	1,000	11½	1½	22	SUSP	—	—	B	"	5
3939	Type 2008	20	2	350	1,000	11½	1½	22	SUSP	—	—	B	"	5
4688	Type 2459	20	10	350	1,000	11½	1½	22	SUSP	—	—	B	"	5
15155	Type 5153	22	10	350	1,000	11½	1½	22	SUSP	51039	—	B	"	5
15188	Type 5178	22	10	350	1,000	11½	1½	22	SUSP	—	—	B	"	5
5553	Type 3016	25	5	350	1,000	11½	1½	22	SUSP	51038	—	B	"	3
4699	Type 2470	25	15	350	1,000	11½	1½	22	SUSP	—	ZA.4655	B	"	5
3998	Type 2054	25	15	350	1,000	11½	1½	22	SUSP	—	ZA.21380	B	"	3
15874	Type 5263	25	20	350	1,000	11½	1½	22	SUSP	—	ZA.24157	B	"	5
15156	Type 5154	27	5	350	1,000	11½	1½	22	SUSP	51042	—	B	"	5
9184	Type 285	30	5	350	1,000	11½	1½	22	SUSP	—	—	B	"	5
8800	Type 228	30	10	350	1,000	11½	1½	22	SUSP	—	—	B	"	3

SECTION 100—cont.

FIXED CONDENSERS

VOTE 3 B. 4

1	2	3	4	5		6	7			9	10	11	12	13	14	15
				Working	Test		Height	Width	Depth							
16225	MICA DIELECTRIC—cont. Moulded—cont. Less than .001 mfd.—cont.	33	5	350	1,000	$\frac{1}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP	51045		B	each	5		
15191	Type 5156	33	10	350	1,000	$\frac{3}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP	51044		B	"	5		
16226	Type 5181	39	5	350	1,000	$\frac{1}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP	51037		B	"	5		
15988	Type 5457	39	10	350	1,000	$\frac{1}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP	51036		B	"	5		
39388	Type 5320	40	2	350	1,000	$\frac{7}{32}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	5		
3383	Type 2007	40	20+40	350	1,000	$\frac{7}{32}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	3		
682	Type 1648	45	5	350	1,000	$\frac{1}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	3		
14285	Type 794	50	2	350	1,000	$\frac{1}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	5		
7903	Type 4711	50	5	350	1,000	$\frac{3}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	2		
8659	Type 122	50	5	750	2,200	$\frac{1}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	5		
13534	Type 212	50	10	350	1,000	$\frac{1}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	3		
2039	Type 4426	50	10	750	2,200	$\frac{1}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	5		
4994	Type 944	50	15	350	1,000	$\frac{1}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	3		
4416	Type 2684	50	15	350	1,000	$\frac{1}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	5		
4687	Type 2282	50	15	350	1,000	$\frac{1}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	3		
8386	Type 2458	50	15	350	1,000	$\frac{1}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	5		
3273	Type 176	50	15	350	1,000	$\frac{1}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	5		
14501	Type 1587	50	15	350	1,000	$\frac{1}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	1		
5546	Type 4820	50	20	2,500	5,000	$\frac{3}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	3		
14995	Type 3009	50	+100	350	1,000	$\frac{3}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	5		
16131	Type 5068	56	2	350	1,000	$\frac{1}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	5		
16227	Type 5389	56	5	350	1,000	$\frac{1}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	5		
16132	Type 5458	60	2	350	1,000	$\frac{3}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	5		
16092	Type 5390	68	5	350	1,000	$\frac{3}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	3		
13133	Type 5366	75	10	350	1,000	$\frac{1}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	5		
3437	Type 1688	75	15	350	1,000	$\frac{3}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	5		
15875	Type 5264	80	1	350	1,000	$\frac{1}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	3		
2554	Type 1206	80	5	1,500	4,500	$\frac{3}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	3		
2416	Type 1165	80	10	350	1,000	$\frac{1}{16}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	3		
15876	Type 5265	93	2	350	1,000	$\frac{7}{32}$	$\frac{1}{16}$	$\frac{1}{16}$	SUSP			B	"	3		

SECTION 100—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	Nomenclature	Capacity mfd	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (Ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	MICA DIELECTRIC—cont. Moulded—cont. Less than .001 mfd.—cont.													
16135	Type 5393	100	2	350	1,000	$\frac{3}{16}$	$\frac{15}{16}$	$\frac{1}{32}$	SUSP	51061	—	B	each	5
3693	Type 1868	100	5	750	2,200	$\frac{3}{32}$	$\frac{27}{32}$	$\frac{3}{32}$	SUSP	—	—	B	"	3
4100	Type 2102	100	5	350	1,000	$\frac{1}{16}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP	—	ZA.22526	B	"	3
13185	Type 4244	100	5	350	1,000	$\frac{1}{16}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP	—	—	B	"	5
11034	Type 437	100	5	350	1,000	$\frac{1}{16}$	$\frac{23}{16}$	$\frac{11}{16}$	SUSP	—	—	B	"	3
2340	Type 1129	100	5	350	1,000	$\frac{3}{32}$	$\frac{13}{16}$	$\frac{1}{2}$	SUSP	51060	ZA.1439	B	"	3
38	Type 584	100	5	500	1,500	$\frac{3}{32}$	$\frac{27}{32}$	$\frac{1}{16}$	SUSP	—	—	B	"	5
11976	Type 3702	100	5	1,500	4,500	$\frac{3}{32}$	$\frac{27}{32}$	$\frac{1}{16}$	SUSP	—	—	B	"	5
5552	Type 3015	100	10	350	1,000	$\frac{3}{32}$	$\frac{13}{16}$	$\frac{1}{16}$	SUSP	—	WY.1219	B	"	3
4249	Type 2194	100	10	350	1,000	$\frac{3}{32}$	$\frac{23}{32}$	$\frac{1}{16}$	SUSP	—	ZC.0589	B	"	5
3389	Type 1654	100	10	350	1,000	$\frac{1}{16}$	$\frac{11}{16}$	$\frac{1}{16}$	SUSP	—	ZA.12992	B	"	5
963	Type 895	100	10	350	1,000	$\frac{1}{16}$	$\frac{11}{16}$	$\frac{1}{16}$	SUSP	—	—	B	"	3
5529	Type 2992	100	10	500	1,500	$\frac{1}{16}$	$\frac{11}{16}$	$\frac{1}{16}$	SUSP	—	—	B	"	5
4255	Type 2200	100	10	750	2,200	$\frac{1}{16}$	$\frac{27}{16}$	$\frac{1}{16}$	SUSP	—	—	B	"	5
12333	Type 3876	100	10	750	2,200	$\frac{3}{32}$	$\frac{23}{32}$	$\frac{1}{16}$	SUSP	—	—	B	"	5
12972	Type 4152	100	10	750	2,200	$\frac{3}{32}$	$\frac{23}{32}$	$\frac{1}{16}$	SUSP	—	—	B	"	3
13652	Type 4478	100	10	2,000	5,000	$\frac{3}{32}$	$\frac{27}{32}$	$\frac{1}{16}$	SUSP	—	—	B	"	3
5034	Type 2704	100	15	350	1,000	$\frac{3}{32}$	$\frac{27}{32}$	$\frac{1}{16}$	SUSP	—	—	B	"	3
4995	Type 2685	100	15	350	1,000	$\frac{3}{32}$	$\frac{27}{32}$	$\frac{1}{16}$	SUSP	—	—	B	"	3
96	Type 611	100	15	350	1,000	$\frac{1}{16}$	$\frac{11}{16}$	$\frac{1}{16}$	SUSP	—	ZC.9988	B	"	5
7902	Type 121	100	15	350	1,000	$\frac{1}{16}$	$\frac{11}{16}$	$\frac{1}{16}$	SUSP	—	—	B	"	1
7814	Type 112	100	15	350	1,000	$\frac{1}{16}$	$\frac{11}{16}$	$\frac{1}{16}$	SUSP	—	—	B	"	3
4698	Type 2469	100	15	350	1,000	$\frac{1}{16}$	$\frac{11}{16}$	$\frac{1}{16}$	SUSP	—	—	B	"	5
5315	Type 2866	100	15	500	1,500	$\frac{1}{16}$	$\frac{11}{16}$	$\frac{1}{16}$	SUSP	—	—	B	"	5
3414	Type 1675	100	15	1,000	2,200	$\frac{1}{16}$	$\frac{11}{16}$	$\frac{1}{16}$	SUSP	—	—	B	"	3
12347	Type 3890	100	15	1,000	2,200	$\frac{1}{16}$	$\frac{11}{16}$	$\frac{1}{16}$	SUSP	—	—	B	"	3
87	Type 602	100	15	2,500	5,000	$\frac{1}{16}$	$\frac{27}{16}$	$\frac{1}{16}$	SUSP	—	—	B	"	2
13791	Type 4514	100	20	350	1,000	$\frac{1}{16}$	$\frac{11}{16}$	$\frac{1}{16}$	SUSP	W.2815	—	B	"	5
15772	Type —	100	20	350	1,000	$\frac{1}{16}$	$\frac{11}{16}$	$\frac{1}{16}$	SUSP	W.2985	—	B	"	3

SECTION 10C—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	Voltage		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
<p>MICA DIELECTRIC—cont. Moulded—cont. Less than .001 mfd.—cont.</p>														
5871	Type 3219	300	10	500	1,500	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP	—	—	B	each	3
13678	Type 4486	300	10	750	2,200	$\frac{1}{16}$	$\frac{23}{32}$	$\frac{11}{16}$	SUSP	—	—	B	"	—
15844	Type 5234	300	10	750	2,200	$\frac{1}{16}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP	W.6246	ZC.12060	B	"	5
745	Type 831	300	15	350	1,000	$\frac{5}{32}$	$\frac{11}{16}$	$\frac{7}{16}$	SUSP	—	ZC.18445	B	"	3
2076	Type 966	300	15	350	1,000	$\frac{5}{32}$	$\frac{11}{16}$	$\frac{7}{16}$	SUSP	—	ZA.1452	B	"	3
3196	Type 1551	300	15	350	1,000	$\frac{5}{32}$	$\frac{11}{16}$	$\frac{7}{16}$	SUSP	—	ZC.8613	B	"	5
8383	Type 173	300	15	350	1,000	$\frac{1}{16}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP	W.2550	ZA.12661	B	"	5
5947	Type 3257	300	15	500	1,500	$\frac{1}{16}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP	—	—	B	"	3
8673	Type 222	300	15	750	2,200	$\frac{1}{16}$	$\frac{23}{32}$	$\frac{11}{16}$	SUSP	—	—	B	"	5
15744	Type —	300	15	750	2,200	$\frac{1}{16}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP	W.6422	—	B	"	1
2803	Type 1345	300	15	1,000	3,000	$\frac{1}{16}$	$\frac{23}{32}$	$\frac{11}{16}$	SUSP	—	—	B	"	3
12000	Type 3712	300	—0+100	350	1,000	$\frac{1}{16}$	$\frac{15}{16}$	$\frac{11}{16}$	SUSP	—	—	B	"	3
12381	Type 3908	300	—0+100	350	1,000	$\frac{1}{16}$	$\frac{15}{16}$	$\frac{11}{16}$	SUSP	—	—	B	"	3
12315	Type 3861	300	—0+100	350	1,000	$\frac{1}{16}$	$\frac{15}{16}$	$\frac{11}{16}$	SUSP	—	—	B	"	3
12337	Type 3880	300	—0+100	750	2,200	$\frac{1}{16}$	$\frac{23}{32}$	$\frac{11}{16}$	SUSP	—	—	B	"	3
3388	Type 1653	300	—15+0	350	1,000	$\frac{1}{16}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP	51155	—	B	"	3
3101	Type 1501	300	—15+inf.	350	1,000	$\frac{1}{16}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP	—	—	B	"	3
16300	Type 5502	330	2	350	1,000	$\frac{3}{32}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP	51079	—	B	"	5
15185	Type 5175	330	5	350	1,000	$\frac{3}{32}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP	51078	—	B	"	5
15093	Type 5106	330	10	350	1,000	$\frac{3}{32}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP	51077	—	B	"	3
15841	Type 5231	350	1	350	1,000	$\frac{3}{32}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP	—	—	B	"	5
14114	Type 4642	350	10	350	1,000	$\frac{1}{16}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP	—	—	B	"	3
4689	Type 2460	350	15	350	1,000	$\frac{1}{16}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP	—	—	B	"	5
15842	Type 5232	375	1	750	2,200	$\frac{11}{32}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP	—	—	B	"	3
13780	Type 4511	375	5	350	1,000	$\frac{11}{32}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP	—	—	B	"	3
16329	Type 5527	390	2	350	1,000	$\frac{1}{16}$	$\frac{23}{32}$	$\frac{11}{16}$	SUSP	51046	—	B	"	3
16229	Type 5460	390	5	350	1,000	$\frac{1}{16}$	$\frac{23}{32}$	$\frac{11}{16}$	SUSP	51043	—	B	"	5
15221	Type 5201	390	10	350	1,000	$\frac{1}{16}$	$\frac{23}{32}$	$\frac{11}{16}$	SUSP	51040	—	B	"	3
4546	Type 2356	400	5	350	1,000	$\frac{1}{16}$	$\frac{23}{32}$	$\frac{11}{16}$	SUSP	—	—	B	"	3
3602	Type 1810	400	5	350	1,000	$\frac{1}{16}$	$\frac{23}{32}$	$\frac{11}{16}$	SUSP	—	ZA.1631	B	"	5

SECTION 10C—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Moulded—cont.													
	Less than .001 mfd.—cont.													
104	Type 617	400	5	750	2,200	$\frac{3}{16}$	$2\frac{1}{8}$	$\frac{3}{8}$	SUSP	—	—	B	each	5
14485	Type 4807	400	15	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{1}{16}$	SUSP	—	—	B	"	3
2726	Type 1329	400	15	350	1,000	$\frac{3}{16}$	$2\frac{1}{8}$	$\frac{1}{16}$	SUSP	—	—	B	"	5
3525	Type 1746	400	15	350	1,000	$\frac{3}{16}$	$2\frac{1}{8}$	$\frac{1}{16}$	SUSP	—	—	B	"	3
5441	Type 2943	400	15	500	1,500	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{1}{16}$	SUSP	—	—	B	"	5
13469	Type 4402	420	10	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{1}{16}$	SUSP	—	—	B	"	3
14119	Type 4646	450	10	350	1,500	$\frac{3}{16}$	$2\frac{1}{8}$	$\frac{1}{16}$	SUSP	—	—	B	"	3
13471	Type 4404	460	5	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{1}{16}$	SUSP	—	—	B	"	3
16091	Type 5365	470	2	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{1}{16}$	SUSP	51081	—	B	"	3
3051	Type 1461	500	2	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{1}{16}$	SUSP	—	—	B	"	3
3935	Type 2004	500	2	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{1}{16}$	SUSP	—	—	B	"	3
11695	Type 549	500	2	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{1}{16}$	SUSP	—	ZC.2708	B	"	3
11490	Type 541	500	5	350	1,000	$\frac{3}{16}$	$2\frac{1}{8}$	$\frac{1}{16}$	SUSP	—	—	B	"	5
3587	Type 1801	500	5	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{1}{16}$	SUSP	—	—	B	"	5
5774	Type 3161	500	5	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{1}{16}$	SUSP	W.5214	—	B	"	3
4976	Type 2666	500	5	750	2,200	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{1}{16}$	SUSP	—	—	B	"	3
14118	Type 4645	500	5	750	2,200	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{1}{16}$	SUSP	—	—	B	"	3
15845	Type 5235	500	10	750	2,200	$\frac{3}{16}$	$2\frac{1}{8}$	$\frac{1}{16}$	SUSP	W.6247	—	B	"	5
3774	Type 1907	500	10	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{1}{16}$	SUSP	51197	ZA.28028	B	"	5
4248	Type 2193	500	10	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{1}{16}$	SUSP	51133	ZA.1441	B	"	5
13348	Type —	500	10	350	1,000	$\frac{3}{16}$	$2\frac{1}{8}$	$\frac{1}{16}$	SUSP	—	—	B	"	1
5656	Type 3081	500	10	350	1,000	$\frac{3}{16}$	$2\frac{1}{8}$	$\frac{1}{16}$	SUSP	W.4958	—	B	"	3
12324	Type 3870	500	10	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{1}{16}$	SUSP	—	—	B	"	3
12338	Type 3881	500	10	750	2,200	$\frac{3}{16}$	$2\frac{1}{8}$	$\frac{1}{16}$	SUSP	51160	—	B	"	3
4171	Type 2127	500	15	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{1}{16}$	SUSP	—	—	B	"	3
11775	Type 3598	500	15	350	1,000	$\frac{3}{16}$	$2\frac{1}{8}$	$\frac{1}{16}$	SUSP	W.5106	ZA.21384	B	"	5
8009	Type 132	500	15	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{1}{16}$	SUSP	—	—	B	"	5
3191	Type 1546	500	15	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{1}{16}$	SUSP	—	—	B	"	5
4869	Type 2561	500	15	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{1}{16}$	SUSP	W.2802	ZA.1392	B	"	3
13065	Type —	500	15	350	1,000	$\frac{3}{16}$	$2\frac{1}{8}$	$\frac{1}{16}$	SUSP	—	ZC.3192	B	"	3
											ZC.3268	B	"	—

SECTION 10C—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	Nomenclature	Capacity ind.	Tolerance ± %	Voltage		Overall Dimensions (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Qty. Unit
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont. Moulded—cont. .001 mfd. and upwards—cont.													
12317	Type 3863	.002	10	350	1,000	$3\frac{1}{2}$	$2\frac{3}{8}$	$3\frac{3}{8}$	SUSP	—	—	B	each	3
13884	Type 4560	.002	10	350	1,000	$3\frac{1}{8}$	$1\frac{1}{2}$	$3\frac{1}{2}$	SUSP	—	ZA.10832	B	"	3
5425	Type 2927	.002	10	350	1,000	$1\frac{1}{2}$	$2\frac{1}{4}$	$2\frac{1}{2}$	SUSP	—	—	B	"	3
11199	Type 3402	.002	10	750	2,200	$1\frac{1}{2}$	$2\frac{1}{8}$	$3\frac{1}{8}$	SUSP	—	—	B	"	3
4244	Type 2189	.002	10	750	2,220	$1\frac{1}{2}$	$2\frac{1}{8}$	$3\frac{1}{8}$	SUSP	W.5406	—	B	"	5
15847	Type 5237	.002	10	750	2,200	$1\frac{1}{2}$	$2\frac{1}{8}$	$3\frac{1}{8}$	SUSP	52495	—	B	"	5
14001	Type 4604	.002	15	350	700	$3\frac{1}{8}$	$1\frac{1}{8}$	$1\frac{3}{8}$	SUSP	—	—	B	"	5
12957	Type 4143	.002	15	350	1,000	$3\frac{1}{8}$	$1\frac{1}{8}$	$1\frac{3}{8}$	SUSP	—	ZA.22452	B	"	3
8010	Type 133	.002	15	350	1,000	$3\frac{1}{8}$	$1\frac{1}{8}$	$1\frac{3}{8}$	SUSP	W.2367	—	B	"	5
12318	Type 3864	.002	15	350	1,000	$3\frac{1}{8}$	$2\frac{1}{8}$	$2\frac{1}{8}$	SUSP	—	ZA.20472	B	"	3
7847	Type 114	.002	15	350	1,000	$3\frac{1}{8}$	$1\frac{1}{8}$	$1\frac{3}{8}$	SUSP	—	—	B	"	3
12475	Type 3957	.002	15	750	2,200	$1\frac{1}{2}$	$1\frac{1}{8}$	$1\frac{3}{8}$	SUSP	—	—	B	"	3
8656	Type 209	.002	15	750	2,200	$1\frac{1}{2}$	$1\frac{1}{8}$	$1\frac{3}{8}$	SUSP	—	—	B	"	5
4887	Type 2579	.002	15	2,000	5,000	$1\frac{1}{2}$	$2\frac{1}{8}$	$2\frac{1}{8}$	SUSP	W.2807	—	B	"	2
12371	Type 3903	.002	15	2,000	5,000	$1\frac{1}{2}$	$2\frac{1}{8}$	$2\frac{1}{8}$	SUSP	—	—	B	"	3
13589	Type 4448	.002	20	350	1,000	$3\frac{1}{8}$	$1\frac{1}{8}$	$1\frac{3}{8}$	SUSP	—	ZA.20318	B	"	3
13809	Type 4525	.002	20	350	1,000	$3\frac{1}{8}$	$1\frac{1}{8}$	$1\frac{3}{8}$	SUSP	—	—	B	"	3
15927	Type 5294	.002	20	350	1,000	$3\frac{1}{8}$	$1\frac{1}{8}$	$1\frac{3}{8}$	SUSP	—	—	B	"	5
12319	Type 3865	.002	—	2,000	6,000	$3\frac{1}{8}$	$2\frac{1}{8}$	$2\frac{1}{8}$	SUSP	51191	—	B	"	3
12341	Type 3884	.002	—	350	1,000	$3\frac{1}{8}$	$2\frac{1}{8}$	$2\frac{1}{8}$	SUSP	51137	—	B	"	3
14384	Type 4733	.0021	5	350	1,000	$3\frac{1}{8}$	$1\frac{1}{8}$	$1\frac{3}{8}$	SUSP	51164	—	B	"	3
4940	Type 2630	.0022	2	350	1,000	$3\frac{1}{8}$	$1\frac{1}{8}$	$1\frac{3}{8}$	SUSP	—	—	B	"	5
16339	Type 5537	.0022	2	350	1,000	$3\frac{1}{8}$	$1\frac{1}{8}$	$1\frac{3}{8}$	SUSP	51103	ZA.1728	B	"	3
15152	Type 5150	.0022	5	350	1,000	$3\frac{1}{8}$	$1\frac{1}{8}$	$1\frac{3}{8}$	SUSP	51102	ZC.23390	B	"	3
14417	Type 4759	.0022	10	350	1,000	$3\frac{1}{8}$	$1\frac{1}{8}$	$1\frac{3}{8}$	SUSP	51101	—	B	"	3
14388	Type 4737	.00225	2	350	1,000	$3\frac{1}{8}$	$1\frac{1}{8}$	$1\frac{3}{8}$	SUSP	—	—	B	"	3
4891	Type 2583	.0025	2	350	1,000	$3\frac{1}{8}$	$1\frac{1}{8}$	$1\frac{3}{8}$	SUSP	—	ZA.11668	B	"	3
11867	Type 3646	.0025	5	350	1,000	$3\frac{1}{8}$	$1\frac{1}{8}$	$1\frac{3}{8}$	SUSP	—	—	B	"	3
13420	Type 4375	.0025	10	750	2,200	$3\frac{1}{8}$	$1\frac{1}{8}$	$1\frac{3}{8}$	SUSP	—	—	B	"	1
14492	Type 4812	.0025	10	2,000	5,000	$3\frac{1}{8}$	$1\frac{1}{8}$	$1\frac{3}{8}$	SUSP	—	—	B	"	3

SECTION 10C—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	Nomenclature	Capacity mfd.	Tolerance ± %	Voltage		Overall Dimensions (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Moulded—cont. .001 mfd. and upwards—cont.													
4707	Type 2478	-.0025	15	350	100	$1\frac{1}{2}$	$1\frac{1}{2}$	$2\frac{3}{16}$	SUSP	—	ZA.1616	B	each	3
336	Type 663	-.0025	15	2,000	6,000	$1\frac{1}{2}$	$2\frac{1}{2}$	$2\frac{1}{8}$	SUSP	—	—	B	"	3
14555	Type 4845	-.0025	20	350	1,000	$1\frac{1}{2}$	$1\frac{1}{2}$	$2\frac{1}{8}$	SUSP	—	—	B	"	3
16340	Type 5538	-.0027	2	350	1,000	$1\frac{1}{2}$	$1\frac{1}{2}$	$2\frac{1}{8}$	SUSP	51106	ZA.11669	B	"	3
5952	Type 3262	-.0028	2	500	1,000	$1\frac{1}{2}$	$1\frac{1}{2}$	$2\frac{1}{8}$	SUSP	—	—	B	"	3
11694	Type 548	-.003	2	350	1,000	$1\frac{1}{2}$	$1\frac{1}{2}$	$2\frac{1}{8}$	SUSP	—	—	B	"	3
245	Type 636	-.003	5	750	2,200	$1\frac{1}{2}$	$1\frac{1}{2}$	$2\frac{1}{8}$	SUSP	—	—	B	"	3
5687	Type 3112	-.003	10	350	1,000	$1\frac{1}{2}$	$1\frac{1}{2}$	$2\frac{1}{8}$	SUSP	51206	ZA.1449	B	"	3
3502	Type 1728	-.003	10	350	1,000	$1\frac{1}{2}$	$1\frac{1}{2}$	$2\frac{1}{8}$	SUSP	51142	ZA.21166	B	"	3
16389	Type 5587	-.003	10	750	2,200	$1\frac{1}{2}$	$2\frac{1}{2}$	$2\frac{1}{8}$	SUSP	51169	—	B	"	3
15848	Type 5238	-.003	10	750	2,200	$1\frac{1}{2}$	$1\frac{1}{2}$	$2\frac{1}{8}$	SUSP	51229	—	B	"	5
4788	Type 2520	-.003	15	350	1,000	$1\frac{1}{2}$	$1\frac{1}{2}$	$2\frac{1}{8}$	SUSP	W.5529	ZA.10973	B	"	3
2342	Type 1131	-.003	15	350	1,000	$1\frac{1}{2}$	$1\frac{1}{2}$	$2\frac{1}{8}$	SUSP	—	—	B	"	3
5293	Type 2846	-.003	15	350	1,000	$1\frac{1}{2}$	$1\frac{1}{2}$	$2\frac{1}{8}$	SUSP	—	—	B	"	5
4267	Type 2211	-.003	15	500	1,500	$1\frac{1}{2}$	$1\frac{1}{2}$	$2\frac{1}{8}$	SUSP	—	—	B	"	5
3696	Type 1871	-.003	15	750	2,200	$1\frac{1}{2}$	$2\frac{1}{2}$	$2\frac{1}{8}$	SUSP	—	—	B	"	3
2798	Type 1340	-.003	15	750	5,000	$1\frac{1}{2}$	$2\frac{1}{2}$	$2\frac{1}{8}$	SUSP	—	—	B	"	3
16032	Type 5333	-.003	20	350	1,000	$1\frac{1}{2}$	$2\frac{1}{2}$	$2\frac{1}{8}$	SUSP	51141	—	B	"	3
16657	Type 5841	-.003	20	750	1,500	$1\frac{1}{2}$	$2\frac{3}{16}$	$2\frac{1}{8}$	SUSP	—	—	B	"	5
4889	Type 2581	-.0032	2	350	1,000	$1\frac{1}{2}$	$1\frac{1}{2}$	$2\frac{1}{8}$	SUSP	—	—	B	"	3
16342	Type 5540	-.0033	2	350	1,000	$1\frac{1}{2}$	$1\frac{1}{2}$	$2\frac{1}{8}$	SUSP	51109	—	B	"	5
16233	Type 5464	-.0033	10	350	1,000	$1\frac{1}{2}$	$1\frac{1}{2}$	$2\frac{1}{8}$	SUSP	51107	—	B	"	5
14381	Type 4730	-.00325	2	350	700	$1\frac{1}{2}$	$1\frac{1}{2}$	$2\frac{1}{8}$	SUSP	—	—	B	"	5
13467	Type 4400	-.0034	2	350	1,000	$1\frac{1}{2}$	$1\frac{1}{2}$	$2\frac{1}{8}$	SUSP	—	ZA.13189	B	"	3
3102	Type 1502	-.0034	—	350	1,000	$1\frac{1}{2}$	$2\frac{1}{2}$	$2\frac{1}{8}$	SUSP	—	—	B	"	5
14383	Type 1506	-.0035	—	750	2,200	$1\frac{1}{2}$	$2\frac{1}{2}$	$2\frac{1}{8}$	SUSP	—	—	B	"	3
5953	Type 4732	-.0035	15	350	1,000	$1\frac{1}{2}$	$1\frac{1}{2}$	$2\frac{1}{8}$	SUSP	—	—	B	"	3
16345	Type 3263	-.0035	2	350	1,000	$1\frac{1}{2}$	$1\frac{1}{2}$	$2\frac{1}{8}$	SUSP	51388	—	B	"	3
16343	Type 5543	-.0039	2	350	1,000	$1\frac{1}{2}$	$1\frac{1}{2}$	$2\frac{1}{8}$	SUSP	51049	—	B	"	3
	Type 5541	-.0039	10	350	1,000	$1\frac{1}{2}$	$1\frac{1}{2}$	$2\frac{1}{8}$	SUSP	—	—	B	"	3

SECTION 100-cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
MICA DIELECTRIC-cont.														
Moulded-cont.														
.001 mfd. and upwards-cont.														
4867	Type 2559	.004	5	350	1,000	^{1 1/8} _{3/8}	^{1 1/2} _{2 1/8}	^{5/8} _{1 1/8}	SUSP	—	—	B	each	3
5455	Type 2287	.004	5	350	1,000	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	—	ZA.25176	B	"	3
8670	Type 215	.004	5	750	2,200	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	—	—	B	"	5
2055	Type 956	.004	10	350	1,000	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	—	—	B	"	5
14021	Type 4612	.004	10	350	1,000	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	—	ZA.20828	B	"	3
3210	Type 1564	.004	10	500	1,500	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	—	—	B	"	3
8493	Type 185	.004	10	750	2,200	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	—	—	B	"	5
15769	Type —	.004	15	750	2,200	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	—	ZA.1706	B	"	3
15859	Type 5249	.00455	2	350	1,000	^{3/8} _{1 1/8}	^{1 1/8} _{1 3/8}	^{5/8} _{1 1/8}	SUSP	—	—	B	"	1
4943	Type 2633	.0046	15	350	1,000	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	—	—	B	"	5
16346	Type 5544	.0047	2	350	1,000	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	51112	—	B	"	3
15220	Type 5200	.0047	2	350	1,000	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	51111	—	B	"	3
15999	Type 5323	.0047	5	350	1,000	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	51110	—	B	"	3
11697	Type 551	.005	10	350	1,000	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	—	ZA.1363	B	"	3
4808	Type 2539	.005	5	350	1,000	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	—	—	B	"	3
10164	Type 385	.005	5	500	1,500	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	—	ZA.25175	B	"	3
12001	Type 3713	.005	10	350	1,000	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	51145	—	B	"	3
3788	Type 1918	.005	10	350	1,000	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	—	ZA.21127	B	"	3
15748	Type —	.005	10	500	1,500	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	—	ZA.1438	B	"	3
12342	Type 3885	.005	10	750	2,200	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	—	—	B	"	3
499	Type 737	.005	15	350	1,000	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	—	—	B	"	5
5352	Type 2900	.005	15	350	1,000	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	W.973	—	B	"	3
12230	Type 3830	.005	15	350	1,000	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	—	YB.01674	B	"	3
5564	Type 3027	.005	15	500	1,500	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	—	ZC.2692	B	"	3
964	Type 896	.005	15	500	1,500	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	—	—	B	"	2
5884	Type 3232	.005	15	750	2,200	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	—	—	B	"	3
11932	Type 3674	.005	15	750	2,200	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	—	—	B	"	3
15902	Type 5281	.005	20	350	1,000	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	—	ZA.21438	B	"	3
4256	Type 2201	.005	20	350	1,000	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	51144	—	B	"	5
15867	Type 5256	.005	20	750	2,200	^{3/8} _{1 1/8}	^{2 1/8} _{2 3/8}	^{5/8} _{1 1/8}	SUSP	51171	—	B	"	5

SECTION 10C—cont.

FIXED CONDENSERS

VOTE 3 B. 4

1	2	3	4	5		6	7			8	9	10	11	12	13	14	15
				Working	Test		Height	Width	Depth								
MICA DIELECTRIC—cont.																	
Moulded—cont.																	
14251	Type 4703	.005	20	750	1,500		³ / ₃₂	1 1/8	² / ₃₂	SUSP	—	—	B	each	3		
11554	Type 3523	.005	-0 + 100	750	2,200		³ / ₃₂	2 1/8	² / ₃₂	SUSP	51170	—	B	3			
2423	Type 1176	.005	-15 + 0	350	1,000		³ / ₃₂	1 1/8	² / ₃₂	SUSP	—	—	B	5			
16349	Type 5547	.0056	2	350	1,000		³ / ₃₂	1 1/8	² / ₃₂	SUSP	51115	—	B	3			
16348	Type 5546	.0056	5	350	1,000		³ / ₃₂	1 1/8	² / ₃₂	SUSP	51114	—	B	3			
4586	Type 2396	.006	2	350	1,000		³ / ₃₂	1 1/8	² / ₃₂	SUSP	—	ZA.2155	B	3			
4199	Type 2155	.006	5	350	1,000		³ / ₃₂	2 1/8	² / ₃₂	SUSP	W.6339	—	B	5			
15785	Type —	.006	10	350	1,000		³ / ₃₂	1 1/8	² / ₃₂	SUSP	—	ZA.15454 ZC.1670	B	3			
3270	Type 1584	.006	15	750	2,200		³ / ₃₂	1 1/8	² / ₃₂	SUSP	W.6421	—	B	2			
5889	Type 3237	.006	15	750	2,200		³ / ₃₂	2 1/8	² / ₃₂	SUSP	—	—	B	3			
2690	Type 1294	.006	15	1,200	2,500		³ / ₃₂	1 1/8	² / ₃₂	SUSP	—	ZC.15572	B	3			
14387	Type 4736	.0061	2	350	700		³ / ₃₂	1 1/8	² / ₃₂	SUSP	—	—	B	3			
16352	Type 5550	.0068	2	350	1,000		³ / ₃₂	1 1/8	² / ₃₂	SUSP	51118	—	B	3			
15860	Type 5250	.00617	2	350	1,000		³ / ₃₂	1 1/8	² / ₃₂	SUSP	—	—	B	5			
14382	Type 4731	.00625	2	350	700		³ / ₃₂	1 1/8	² / ₃₂	SUSP	—	—	B	3			
4103	Type 2104	.008	2	350	1,000		³ / ₃₂	1 1/8	² / ₃₂	SUSP	—	—	B	3			
16355	Type 5553	.0082	2	350	1,000		³ / ₃₂	1 1/8	² / ₃₂	SUSP	51121	—	B	3			
16353	Type 5551	.0082	2	350	1,000		³ / ₃₂	1 1/8	² / ₃₂	SUSP	51119	—	B	3			
14380	Type 4729	.01	10	350	1,000		³ / ₃₂	1 1/8	² / ₃₂	SUSP	—	—	B	3			
2875	Type 1367	.01	2	350	700		³ / ₃₂	1 1/8	² / ₃₂	SUSP	—	—	B	3			
11696	Type 550	.01	2	350	1,000		³ / ₃₂	1 1/8	² / ₃₂	SUSP	—	—	B	2			
11184	Type 3387	.01	2	350	1,000		³ / ₃₂	1 1/8	² / ₃₂	SUSP	51122	—	B	3			
13183	Type 4242	.01	5	350	1,000		³ / ₃₂	1 1/8	² / ₃₂	SUSP	—	ZC.21678	B	3			
16356	Type 5554	.01	5	350	1,000		³ / ₃₂	1 1/8	² / ₃₂	SUSP	—	—	B	3			
10562	Type 424	.01	5	750	2,200		³ / ₃₂	2 1/8	² / ₃₂	SUSP	—	ZA.1475	B	3			
14466	Type 4798	.01	5	350	2,200		³ / ₃₂	1 1/8	² / ₃₂	SUSP	51211	—	B	5			
838	Type 4798	.01	10	350	1,000		³ / ₃₂	1 1/8	² / ₃₂	SUSP	—	ZC.2168	B	3			
4246	Type 854	.01	10	350	1,000		³ / ₃₂	2 1/8	² / ₃₂	SUSP	—	—	B	3			
3448	Type 2191	.01	10	750	2,200		³ / ₃₂	2 1/8	² / ₃₂	SUSP	—	ZA.20308	B	3			
3448	Type 1699	.01	10	750	2,200		³ / ₃₂	2 1/8	² / ₃₂	SUSP	—	ZA.13421	B	3			

SECTION 10G—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (INS.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	MICA DIELECTRIC—cont. Moulded—cont. .001 mfd. and upwards—cont.													
3439	Type 1690	.01	10	750	2,200	$\frac{9}{32}$	$\frac{23}{32}$	$\frac{9}{32}$	SUSP	—	—	B	each	3
8496	Type 188	.01	15	350	1,000	$\frac{9}{32}$	$\frac{24}{32}$	$\frac{9}{32}$	SUSP	—	ZC.19973	B	"	3
16915	Type 6027	.01	15	350	1,000	$\frac{9}{32}$	$\frac{24}{32}$	$\frac{9}{32}$	SUSP	—	—	B	"	—
244	Type 635	.01	15	350	1,000	$\frac{9}{32}$	$\frac{24}{32}$	$\frac{9}{32}$	SUSP	W.1428	ZA.1560	B	"	3
10393	Type 403	.01	15	750	2,200	$\frac{9}{32}$	$\frac{24}{32}$	$\frac{9}{32}$	SUSP	—	—	B	"	5
8658	Type 211	.01	15	1,000	2,000	$\frac{9}{32}$	$\frac{27}{32}$	$\frac{1}{32}$	SUSP	W.2813	ZA.17052	B	"	2
10511	Type 378	.01	15	1,000	3,000	$\frac{9}{32}$	$\frac{27}{32}$	$\frac{1}{32}$	SUSP	—	—	B'	"	5
11210	Type 3413	.01	15	1,500	4,500	$\frac{9}{32}$	$\frac{27}{32}$	$\frac{1}{32}$	SUSP	—	—	B	"	3
13395	Type 4367	.01	15	2,000	5,000	$\frac{9}{32}$	$\frac{27}{32}$	$\frac{1}{32}$	SUSP	—	—	B	"	2
14582	Type 4861	.01	20	350	1,000	$\frac{9}{32}$	$\frac{21}{32}$	$\frac{1}{32}$	SUSP	51211	ZA.25338	B	"	1
13579	Type 4445	.01	20	450	1,350	$\frac{9}{32}$	$\frac{21}{32}$	$\frac{1}{32}$	SUSP	—	—	B	"	3
15255	Type 5212	.01	20	750	2,200	$\frac{9}{32}$	$\frac{24}{32}$	$\frac{1}{32}$	SUSP	51174	—	B	"	3
7906	Type 125	.01	0 + 15	350	1,000	$\frac{9}{32}$	$\frac{24}{32}$	$\frac{1}{32}$	SUSP	—	—	B	"	3
12407	Type 3927	.01	-0 + 100	350	1,000	$\frac{9}{32}$	$\frac{24}{32}$	$\frac{1}{32}$	SUSP	51146	—	B	"	3
12343	Type 3886	.01	-0 + 100	750	2,200	$\frac{9}{32}$	$\frac{24}{32}$	$\frac{1}{32}$	SUSP	51173	—	B	"	3
13472	Type 4405	.0119	2	350	1,000	$\frac{9}{32}$	$\frac{21}{32}$	$\frac{1}{32}$	SUSP	—	—	B	"	3
5689	Type 3114	.013	2	350	1,000	$\frac{9}{32}$	$\frac{21}{32}$	$\frac{1}{32}$	SUSP	—	—	B	"	5
12344	Type 3872	.02	10	750	2,200	$\frac{9}{32}$	$\frac{24}{32}$	$\frac{1}{32}$	SUSP	—	—	B	"	3
12326	Type 1046	.02	15	350	1,000	$\frac{9}{32}$	$\frac{21}{32}$	$\frac{1}{32}$	SUSP	W.5032	—	B	"	3
2207	Type 1272	.02	15	1,000	3,000	$\frac{9}{32}$	$\frac{24}{32}$	$\frac{1}{32}$	SUSP	—	—	B	"	3
2656	Type 1272	.02	2	350	1,000	$\frac{9}{32}$	$\frac{21}{32}$	$\frac{1}{32}$	SUSP	—	—	B	"	3
15866	Type 5255	.1	5	350	1,000	$\frac{9}{32}$	$\frac{21}{32}$	$\frac{1}{32}$	SUSP	—	—	B	"	5
13468	Type 4401	.1	10	350	1,000	$\frac{9}{32}$	$\frac{21}{32}$	$\frac{1}{32}$	SUSP	—	—	B	"	2
16150	Type 5408	.100	5	350	1,000	$\frac{9}{32}$	$\frac{21}{32}$	$\frac{1}{32}$	SUSP	—	—	B	"	5
15997	Type 5322	.25	15	750	2,250	$\frac{9}{32}$	$\frac{24}{32}$	$\frac{1}{32}$	SUSP	—	—	B	"	3
16673	Type 5851	.300	20	350	1,000	$\frac{9}{32}$	$\frac{21}{32}$	$\frac{1}{32}$	SUSP	—	—	B	"	—

SECTION 10G—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	Nomenclature	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins or mm.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
<p>MICA DIELECTRIC—cont. Protected:— Less than .001 mfd.—</p>														
11412	Type 3479	1	25	350	1,000	2M	15M	10M	SUSP	—	—	B	each	5
11411	Type 3478	2	25	350	1,000	2M	15M	10M	SUSP	—	—	B	"	5
15757	Type —	3	15	350	1,000	5M	20M	10M	SUSP	—	ZA.1598	B	"	3
12450	Type 3948	3	15	350	1,000	5M	15M	10M	SUSP	—	—	B	"	5
2123	Type 1005	5	15	750	2,250	$\frac{3}{16}$ 5M	$\frac{7}{8}$ 15M	$\frac{1}{2}$ 10M	SUSP	—	—	B	"	5
12070	Type 3743	5	20	350	1,000	5M	15M	10M	SUSP	—	—	B	"	5
15728	Type —	10	5	350	1,000	3M	15M	10M	SUSP	—	ZA.23726	B	"	1
14219	Type 4691	10	10	350	700	6M	15M	10M	SUSP	—	—	B	"	5
4478	Type 2304	10	10	350	1,000	5M	15M	10M	SUSP	—	—	B	"	5
15729	Type —	10	10	600	1,500	5M	31M	11M	SUSP	—	ZA.23655	B	"	1
4476	Type 2303	10	10	750	2,250	6M	15M	12M	SUSP	—	—	B	"	3
784	Type 835	10	10	750	2,250	6M	29M	12M	SUSP	—	—	B	"	5
12072	Type 3745	12	1	350	1,000	5M	15M	10M	SUSP	—	—	B	"	5
12155	Type 3802	15	1 mmfd.	350	1,000	5M	15M	10M	SUSP	—	—	B	"	5
2278	Type 1085	15	1 mmfd.	750	2,200	5M	30M	10M	SUSP	—	—	B	"	3
11558	Type 3527	15	10	350	1,000	5M	15M	10M	SUSP	—	ZC.16936	B	"	5
785	Type 836	15	10	750	2,250	5M	30M	10M	SUSP	—	—	B	"	5
2121	Type 1003	17	1 mmfd.	750	2,200	6M	30M	12M	SUSP	—	—	B	"	3
12073	Type 3746	20	5	350	1,000	5M	15M	10M	SUSP	—	—	B	"	5
2120	Type 1002	20	5	750	2,250	6M	29M	15M	SUSP	—	—	B	"	3
11408	Type 3476	20	10	350	1,000	5M	15M	10M	SUSP	—	—	B	"	3
786	Type 837	20	10	750	2,200	6M	30M	12M	SUSP	—	—	B	"	5
3913	Type 1982	20	15	350	1,000	6M	20M	10M	SUSP	—	—	B	"	5
15753	Type —	20	20	350	1,000	6M	20M	10M	SUSP	—	—	B	"	3
14467	Type 4799	22	10	350	700	6M	19M	16M	SUSP	—	—	B	"	5
5984	Type 3293	23	1 mmfd.	350	1,000	5M	15M	10M	SUSP	—	ZC/10C/ 5984	B	"	3
11895	Type 3650	23	10	350	1,000	5M	15M	10M	SUSP	—	—	B	"	5
13841	Type 4540	25	2	350	700	6M	15M	10M	SUSP	—	—	B	"	5

SECTION 10C—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	Nomenclature	Capacity mmfd.	Tolerance ± %	VOLTAGE		Test	OVERALL DIMENSIONS (ins or mm.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test		Height	Width	Depth						
1															
	MICA DIELECTRIC—cont. Protected—cont. Less than .001 mfd.—cont.														
10570	Type 426	25	4	350	1,000	6M	20M	10M	SUSP	—	—	—	B	each	5
12074	Type 3747	25	5	350	1,000	5M	15M	10M	SUSP	—	—	—	B	”	5
12075	Type 3748	25	10	350	1,000	5M	15M	10M	SUSP	—	—	—	B	”	5
15900	Type 5279	27	10	350	1,000	6M	19M	16M	SUSP	50918	—	—	B	”	5
49222	Type 2612	30	1 mmfd.	350	1,000	6M	20M	10M	SUSP	—	—	—	B	”	5
11560	Type 3529	30	5	350	1,000	5M	15M	10M	SUSP	—	—	—	B	”	5
11487	Type 538	30	5	350	1,000	6M	20M	10M	SUSP	—	—	—	B	”	5
13908	Type 4568	30	10	350	700	6M	30M	30M	SUSP	—	—	—	B	”	5
5585	Type 3048	30	10	350	1,000	6M	20M	10M	SUSP	W.6239	—	—	B	”	5
4274	Type 2218	30	10	750	2,200	6M	30M	12M	SUSP	—	—	—	B	”	3
15756	Type —	30	20	350	1,000	.025	.79	.39	SUSP	—	—	—	B	”	3
15730	Type —	32	10	350	1,000	3M	15M	10M	SUSP	—	—	—	B	”	1
14925	Type 5037	33	10	350	1,000	6M	19M	16M	SUSP	50921	—	—	B	”	5
5989	Type 3298	35	1	350	1,000	5M	15M	10M	SUSP	—	ZC 14597	—	B	”	3
5056	Type 2726	35	2	350	1,000	5M	15M	10M	SUSP	—	—	—	B	”	3
15776	Type —	35	5	350	1,000	.6M	20M	10M	SUSP	—	—	—	B	”	3
3921	Type 1990	35	10	350	1,000	6M	20M	10M	SUSP	—	ZA 13793	—	B	”	5
15040	Type 5082	39	5	350	1,000	6M	26M	14M	SUSP	50863	—	—	B	”	5
2146	Type 992	40	2	350	1,000	.6M	50.5M	10.5M	SUSP	—	—	—	B	”	5
4939	Type 2629	40	5	350	1,000	$\frac{7}{8}$ M	2 $\frac{3}{8}$ M	1 $\frac{1}{2}$ M	SUSP	—	—	—	B	”	3
11206	Type 3409	40	5	350	1,000	6M	20M	10M	SUSP	—	—	—	B	”	5
3723	Type 1898	40	5	350	1,000	6M	24M	16M	SUSP	—	—	—	B	”	5
787	Type 838	40	15	750	2,200	6M	30M	12M	SUSP	—	—	—	B	”	5
15754	Type —	45	2	350	1,000	.6M	20M	10M	SUSP	—	—	—	B	”	3
15777	Type —	45	5	350	1,000	$\frac{3}{8}$ M	$\frac{3}{8}$ M	$\frac{3}{8}$ M	SUSP	—	—	—	B	”	3
14031	Type 4614	47	2	350	700	6M	20M	10M	SUSP	—	—	—	B	”	5
11936	Type 3678	50	2	350	1,000	5M	15M	10M	SUSP	—	—	—	B	”	5
3981	Type 2037	50	2	350	1,000	6M	20M	10M	SUSP	—	—	—	B	”	3

SECTION 10C—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins or mm.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	MICA DIELECTRIC—cont. Protected—cont. Less than .001 mfd.—cont.													
11294	Type 3456	50	5	350	1,000	5M	15M	10M	SUSP	—	—	B	each	5
12778	Type 4081	50	5	2,500	7,000	$\frac{1}{2}$ 5M	$1\frac{1}{2}$ 15M	$\frac{11}{16}$ 10M	SUSP	—	—	B	"	1
5998	Type 3307	50	10	750	2,200	5M	15M	10M	SUSP	—	—	B	"	3
788	Type 839	50	15	750	2,200	6M	30M	12M	SUSP	—	—	B	"	5
13494	Type 4411	50	5	350	1,000	6M	20M	10M	SUSP	—	—	B	"	5
16163	Type 5414	56	2	350	1,000	6M	26M	14M	SUSP	50884	—	B	"	5
15041	Type 5083	56	5	350	1,000	6M	26M	14M	SUSP	50883	—	B	"	5
16378	Type 5576	56	10	350	1,000	6M	26M	14M	SUSP	50882	—	B	"	3
5586	Type 3049	60	10	350	1,000	6M	33M	17M	SUSP	—	—	B	"	5
3923	Type 1992	65	3	350	1,000	6M	20M	10M	SUSP	—	—	B	"	5
2649	Type 1265	65	10	350	1,000	6M	20M	10M	SUSP	—	—	B	"	6
2147	Type 993	70	2	350	1,000	6M	20M	10M	SUSP	—	—	B	"	5
11484	Type 535	70	5	350	1,000	6M	20M	10M	SUSP	—	—	B	"	5
5990	Type 3299	75	2	350	1,000	5M	15M	10M	SUSP	—	—	B	"	5
2648	Type 1264	75	2	350	1,000	6M	20M	10M	SUSP	—	—	B	"	6
16083	Type 5357	75	2	750	2,200	6M	19M	14M	SUSP	—	—	B	"	5
5596	Type 3059	75	5	350	1,000	6M	20M	10M	SUSP	—	—	B	"	5
13842	Type 4541	75	10	350	700	6M	15M	10M	SUSP	—	—	B	"	5
4959	Type 2649	75	10	350	1,000	6M	20M	10M	SUSP	—	—	B	"	3
15758	Type —	80	2	350	1,000	$\frac{3}{32}$ 6M	$\frac{3}{4}$ 20M	$\frac{3}{8}$ 10M	SUSP	—	—	B	"	3
16164	Type 5415	82	2	350	1,000	6M	26M	14M	SUSP	50890	ZA 1601	B	"	5
16217	Type 5450	82	5	350	1,000	6M	26M	14M	SUSP	50889	—	B	"	5
16368	Type 5566	82	10	350	1,000	6M	26M	14M	SUSP	50888	—	B	"	3
15759	Type —	90	2	350	1,000	$\frac{1}{4}$ 6M	$\frac{3}{4}$ 20M	$\frac{11}{16}$ 10M	SUSP	—	ZA 1602	B	"	3
14043	Type 4617	90	5	350	700	6M	20M	10M	SUSP	—	—	B	"	5
2012	Type 924	93	2	350	1,000	6M	25M	15M	SUSP	—	—	B	"	5
14403	Type 4752	100	1	750	1,500	6M	20M	10M	SUSP	—	—	B	"	2
13351	Type 4348	100	1	750	2,200	6M	20M	10M	SUSP	—	—	B	"	5
5983	Type 3292	100	2	350	1,000	5M	15M	10M	SUSP	—	—	B	"	5

SECTION 10G—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	Nomenclature	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins. or mm.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
<p>MICA DIELECTRIC—cont. Protected—cont. Less than .001 mfd.—cont.</p>														
5055	Type 2725	100	2	350	1,000	6M	20M	10M	SUSP	—	—	B	each	3
15731	Type —	100	5	350	1,000	.025	.73 dia.	14M	SUSP	—	ZA.1678	B	"	1
16084	Type 5358	100	5	750	2,200	6M	19M	15M	SUSP	—	—	B	"	5
14366	Type 4724	100	10	350	1,000	6M	18M	15M	SUSP	—	—	B	"	5
4271	Type 2215	100	10	350	1,000	6M	20M	10M	SUSP	—	—	B	"	3
5788	Type 3175	100	10	750	2,200	6M	20M	10M	SUSP	—	—	B	"	3
15775	Type —	100	15	350	1,000	.025	.79	.39	SUSP	—	ZA.11167	B	"	3
789	Type 840	100	15	750	2,250	5M	30M	12M	SUSP	—	—	B	"	5
15732	Type —	100	20	350	1,000	.6M	20.1M	9.9M	SUSP	—	{ZA.1592 ZA.1996 ZA.1639}	B	"	1
15764	Type —	110	2	350	1,000	$\frac{3}{8}$	$\frac{3}{8}$	$\frac{3}{4}$	SUSP	—	—	B	"	3
11944	Type 3684	115	2	350	1,000	6M	25M	15M	SUSP	—	—	B	"	5
12077	Type 3750	120	5	350	1,000	6M	25M	15M	SUSP	—	—	B	"	5
12069	Type 3742	120	5	750	2,200	6M	25M	15M	SUSP	—	—	B	"	5
12078	Type 3751	120	10	350	1,000	6M	25M	15M	SUSP	—	—	B	"	5
5903	Type 3251	125	5	350	1,000	6M	32M	16M	SUSP	—	—	B	"	5
12555	Type 4005	125	10	350	1,000	6M	25M	15M	SUSP	—	—	B	"	3
15760	Type —	130	2	350	1,000	.6M	20.1	9.9	SUSP	—	ZA.1603	B	"	3
15761	Type —	140	2	350	1,000	.6M	20.1	9.9	SUSP	—	ZA.1604	B	"	3
14498	Type 4817	150	2	350	1,000	4M	32M	24M	SUSP	—	—	B	"	5
3080	Type 1486	150	2	350	1,000	6M	20M	10M	SUSP	—	—	B	"	5
4798	Type 2529	150	2	350	1,000	6M	25M	15M	SUSP	—	—	B	"	5
3643	Type 1834	150	5	350	1,000	6M	20M	10M	SUSP	—	—	B	"	5
12079	Type 3752	150	5	350	1,000	6M	25M	15M	SUSP	—	—	B	"	3
4961	Type 2651	150	10	350	1,000	$\frac{3}{8}$	$\frac{3}{8}$	$\frac{3}{8}$	SUSP	—	ZA.11187	B	"	3
12080	Type 3753	150	10	350	1,000	6M	24M	16M	SUSP	—	—	B	"	3
5787	Type 3174	150	10	750	2,200	6M	30M	12M	SUSP	—	—	B	"	3
790	Type 841	150	10	750	2,200	6M	30M	12M	SUSP	—	—	B	"	3
10228	Type 417	160	2	350	1,000	6M	20M	10M	SUSP	—	—	B	"	5
4923	Type 2613	160	5	350	1,000	6M	25M	15M	SUSP	—	—	B	"	3

SECTION 104—cont.

FIXED CONDENSERS

VOTE 3 B. 4

1	2	3	4	5		6	7, 8, 9			10	11	12	13	14	15
				Working	Test		Height	Width	Depth						
Ref. No.	Nomenclature	Capacity mmfd	Tolerance ± %	VOLTAGE		Test	OVERALL DIMENSIONS (ins. or mm.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom of Qty.	Carton Unit Qty.
1	MICA DIELECTRIC—cont. Protected—cont. Less than .001 mfd.—cont.														
11916	Type 3663	175	5	350	1,000	6M	20M	10M	SUSP	—	—	—	B	each	5
5583	Type 3046	180	2	350	1,000	6M	32M	16M	SUSP	—	—	—	B	"	3
15042	Type 5084	180	5	350	1,000	6M	32M	20M	SUSP	50898	—	—	B	"	5
3919	Type 1988	190	5	350	1,000	6M	32M	16M	SUSP	—	—	—	B	"	5
14404	Type 4753	200	1	750	1,500	6M	20M	10M	SUSP	—	—	—	B	"	2
13352	Type 4349	200	1	750	2,250	6M	20M	10M	SUSP	—	—	—	B	"	3
3533	Type 1753	200	2	350	1,000	6M	20M	10M	SUSP	—	—	—	B	"	5
4184	Type 2140	200	2	350	1,000	6M	25M	15M	SUSP	—	—	—	B	"	3
4326	Type 2231	200	5	350	1,000	6M	20M	10M	SUSP	—	—	—	B	"	5
5708	Type 3133	200	5	350	1,000	6M	30M	12M	SUSP	—	—	—	B	"	5
15768	Type —	200	15	350	1,000	.025	.728 dia.	—	SUSP	—	—	—	B	"	3
4763	Type 2495	200	20	350	1,000	.6M	20-1	9-9M	SUSP	—	—	—	B	"	3
16375	Type 5573	220	2	350	1,000	6M	32M	20M	SUSP	50938	—	—	B	"	3
12157	Type 3804	225	5	350	1,000	6M	32M	16M	SUSP	—	—	—	B	"	3
4872	Type 2564	230	2	350	1,000	6M	24M	16M	SUSP	—	—	—	B	"	5
4238	Type 2183	230	5	350	1,000	6M	28M	16M	SUSP	—	—	—	B	"	3
14422	Type 4764	230	5	350	1,000	6M	18M	15M	SUSP	—	—	—	B	"	3
2008	Type p20	240	1	350	1,000	5M	33M	20M	SUSP	—	—	—	B	"	5
11368	Type \$20	241	1	350	1,000	1/2	2 3/4	12M	SUSP	—	—	—	B	"	5
11562	Type 3531	250	2	350	1,000	6M	30M	12M	SUSP	—	—	—	B	"	3
5484	Type 2985	250	5	350	1,000	6M	32M	16M	SUSP	—	—	—	B	"	3
14421	Type 4763	250	5	350	700	6M	18M	15M	SUSP	—	—	—	B	"	3
4960	Type 2650	250	10	350	1,000	2M	18M	15M	SUSP	—	—	—	B	"	3
3956	Type 2025	250	10	350	1,000	6M	32M	16M	SUSP	—	—	—	B	"	3
3433	Type 1684	250	15	350	1,000	6M	30M	12M	SUSP	—	—	—	B	"	3
14394	Type 4743	263	5	350	700	6M	18M	15M	SUSP	—	—	—	B	"	3
15986	Type 5318	270	10	350	1,000	6M	37M	24M	SUSP	50903	—	—	B	"	5
3594	Type 1804	275	5	350	1,000	6M	32M	16M	SUSP	—	—	—	B	"	3
5030	Type 2700	300	2	350	1,000	2M	18M	15M	SUSP	—	—	—	B	"	3
4797	Type 2528	300	2	350	1,000	6M	25M	15M	SUSP	—	—	—	B	"	5

SECTION 10C—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ret. No.	Nomenclature	Capacity mfd.	Tolerance ± %	VOLTAGE.		Overall Dimensions (ins. (F.F.M.))			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Cart. Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont. Protected—cont. Less than .001 mfd.—cont.													
2017	Type 929	300	2	350	1,000	6M	32M	16M	SUSP	—	—	B	each	5
13812	Type 4528	300	5	350	700	6M	28M	15M	SUSP	—	—	B	"	3
3064	Type 1474	300	5	350	1,000	6M	32M	16M	SUSP	—	—	B	"	3
13501	Type 4417	300	5	350	1,000	6M	20M	10M	SUSP	—	—	B	"	3
11563	Type 3532	300	5	350	1,000	6M	30M	12M	SUSP	—	—	B	"	3
14525	Type 4833	300	10	350	1,000	$\frac{3}{8}$ M	$\frac{3}{8}$ M	$\frac{1}{2}$ M	SUSP	—	—	B	"	3
3955	Type 2024	300	10	350	1,000	6M	32M	16M	SUSP	—	—	B	"	3
5802	Type 3189	300	10	750	2,200	6M	32M	16M	SUSP	—	—	B	"	5
791	Type 842	300	15	750	2,200	6M	30M	12M	SUSP	—	—	B	"	5
15959	Type 5305	330	2	350	1,000	—	—	—	—	—	—	B	"	3
14002	Type 4605	330	10	350	700	6M	30M	17M	SUSP	—	—	B	"	5
4201	Type 2157	350	2	350	1,000	6M	25M	15M	SUSP	—	—	B	"	5
5477	Type 2978	350	2	350	1,000	6M	32M	16M	SUSP	—	—	B	"	5
15800	Type —	350	10	350	1,000	5M	31M	18M	SUSP	—	ZA.23653	B	"	3
11269	Type 3434	382	3	350	1,000	6M	28M	16M	SUSP	—	—	B	"	3
3545	Type 1760	382	10	350	1,000	6M	28-2M	20-8M	SUSP	—	—	B	"	5
14877	Type 5004	390	5	350	1,000	6M	37M	24M	SUSP	50866	—	B	"	3
14405	Type 4754	400	1	750	1,500	6M	28M	15M	SUSP	—	—	B	"	5
13353	Type 4350	400	1	750	2,200	6M	2 M	16M	SUSP	—	—	B	"	3
4185	Type 2141	400	2	350	1,000	6M	28M	16M	SUSP	—	—	B	"	3
5456	Type 2957	400	2	350	1,000	6M	30M	12M	SUSP	—	—	B	"	1
5792	Type 3179	400	2	350	1,000	6M	32M	16M	SUSP	—	—	B	"	5
11263	Type 3428	400	5	350	1,000	6M	32M	16M	SUSP	—	—	B	"	3
12650	Type 4032	400	10	350	1,000	6M	32M	16M	SUSP	—	—	B	"	3
13891	Type 4563	410	2	750	1,500	6M	30M	17M	SUSP	—	—	B	"	3
3549	Type 1764	414	3	350	1,000	6M	30M	17M	SUSP	—	ZA.11988	B	"	6
11914	Type 3662	450	2	350	1,000	6M	1-11	.82	SUSP	—	—	B	"	3
14032	Type 4615	470	2	350	700	6M	30M	17M	SUSP	—	—	B	"	3
15050	Type 5091	470	2	350	1,000	6M	37M	24M	SUSP	50911	—	B	"	3
14834	Type 4987	470	5	350	1,000	6M	37M	24M	SUSP	50910	—	B	"	3

SECTION 10G—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref No.	Nomenclature	Capacity mfd.	Tolerance ± %	Voltage		Overall Dimensions (ins or mm.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Qty. per Carton
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Protected—cont.													
	Less than .001 mfd.—cont.													
14186	Type 4674	470	10	350	700	6M	32M	16M	SUSP	—	—	B	each	3
11797	Type 3609	475	2	350	1,000	6M	30M	12M	SUSP	—	—	B	"	3
14393	Type 4742	480	5	350	700	6M	18M	15M	SUSP	—	—	B	"	3
14400	Type 4749	491	2	350	700	4	1/8 dia.	15M	SUSP	—	—	B	"	2
15704	Type —	500	1	350	1,000	.6M	28M	15M	SUSP	W.4206	—	B	"	5
13354	Type 4351	500	1	750	2,200	6M	24M	16M	SUSP	—	—	B	"	5
4197	Type 2153	500	2	350	1,000	6M	28M	16M	SUSP	—	—	B	"	3
5144	Type 2736	500	2	350	1,000	6M	32M	16M	SUSP	W.8851	—	B	"	5
11564	Type 3533	500	2	350	1,000	6M	30M	12M	SUSP	—	—	B	"	3
5230	Type 2822	500	5	350	1,000	3-2M	26 9M dia.	15M	SUSP	—	—	B	"	5
4237	Type 2182	500	5	350	1,000	6M	25M	15M	SUSP	—	—	B	"	3
5483	Type 2984	500	5	350	1,000	6M	30M	12M	SUSP	—	—	B	"	3
12153	Type 3801	500	10	350	1,000	6M	30M	12M	SUSP	—	—	B	"	3
14291	Type 4712	500	10	750	1,500	6M	30M	10M	SUSP	—	—	B	"	3
11099	Type 3353	500	10	750	2,200	6M	32M	16M	SUSP	—	—	B	"	3
792	Type 843	500	15	750	2,200	6M	33M	17M	SUSP	—	—	B	"	5
16165	Type 5416	560	2	350	1,000	6M	80M	25M	SUSP	50914	—	B	"	5
16380	Type 5578	560	5	350	1,000	6M	80M	25M	SUSP	50913	—	B	"	5
15826	Type 5221	560	10	350	1,000	6M	32M	20M	SUSP	50948	—	B	"	3
16071	Type 5351	560	10	350	1,000	6M	80M	25M	SUSP	50912	—	B	"	3
14051	Type 4623	600	2	350	700	6M	20M	10M	SUSP	—	—	B	"	3
5971	Type 3280	600	2	350	1,000	6M	33M	17M	SUSP	—	—	B	"	5
5475	Type 2976	600	5	350	1,000	6M	33M	17M	SUSP	—	—	B	"	3
13843	Type 4542	600	10	350	700	6M	30M	17M	SUSP	—	—	B	"	3
5047	Type 2717	612	2	350	1,000	6M	33M	17M	SUSP	—	—	B	"	5
15154	Type 5152	680	2	350	1,000	6M	80M	25M	SUSP	50917	—	B	"	3
16218	Type 5451	680	5	350	1,000	6M	80M	25M	SUSP	50916	—	B	"	3
4424	Type 2290	700	2	350	1,000	6M	33M	17M	SUSP	—	—	B	"	5
3548	Type 1763	700	5	350	1,000	6M	33M	17M	SUSP	—	—	B	"	5
674	Type 791	700	20	350	1,000	.6M	28-2M	20-8M	SUSP	—	—	B	"	2

SECTION 10C—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins. or mm.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom of Qty.	Carton Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Protected—cont.													
	Less than .001 mfd—cont.													
3547	Type 1762	736	3	350	1,000	6M	33M	20M	SUSP	—	ZA.12807	B	each	6
5901	Type 3249	750	2	350	1,000	6M	33M	17M	SUSP	—	—	B	"	3
14499	Type 4818	750	2	350	1,000	6M	27.7M	15M	SUSP	—	—	B	"	3
13785	Type 4512	750	5	350	700	6M	30M	17M	SUSP	—	—	B	"	3
12084	Type 3757	750	5	350	1,000	6M	45M	21M	SUSP	—	—	B	"	3
13366	Type 4357	800	5	350	1,000	6M	33M	17M	SUSP	—	—	B	"	3
3530	Type 1750	800	10	350	1,000	6M	33M	17M	SUSP	—	—	B	"	5
12943	Type 4135	850	5	350	1,000	6M	45M	21M	SUSP	—	—	B	"	1
3046	Type 1456	850	10	350	1,000	6M	33M	17M	SUSP	—	—	B	"	3
14402	Type 4751	894	2	350	700	.312	1-625	dia.	SUSP	—	—	B	"	5
	.001 mfd. and upwards—	mfd.												
3954	Type 2023	.001	1	350	1,000	.6M	28.2M	20.8M	SUSP	—	—	B	"	1
14126	Type 4649	.001	1	350	1,000	.175	1-67	1-20	SUSP	—	—	B	"	3
13355	Type 4352	.001	1	750	2,250	6M	33M	20M	SUSP	—	—	B	"	3
13569	Type 4438	.001	2	350	1,000	5M	30M	30M	SUSP	—	—	B	"	1
12799	Type 4084	.001	2	350	1,000	6M	20M	10M	SUSP	—	—	B	"	3
3198	Type 1553	.001	2	350	1,000	6M	33M	17M	SUSP	—	—	B	"	5
12085	Type 3758	.001	2	350	1,000	6M	45M	21M	SUSP	—	—	B	"	3
12086	Type 3759	.001	2	350	1,000	6M	45M	21M	SUSP	—	—	B	"	3
3961	Type 2030	.001	5	350	1,000	6M	33M	20M	SUSP	—	—	B	"	3
14993	Type 5066	.001	10	750	2,200	6M	28M	20M	SUSP	—	—	B	"	3
4613	Type 2404	.001	10	350	1,000	6M	33M	20M	SUSP	—	—	B	"	3
15763	Type —	.001	10	350	1,000	.025	1-11	.82	SUSP	—	ZA.1638	B	"	3
12158	Type 3497	.001	10	350	1,000	6M	33M	20M	SUSP	—	—	B	"	3
12087	Type 3760	.001	10	350	1,000	6M	45M	21M	SUSP	—	—	B	"	3
14047	Type 4621	.001	20	3,000	6,000	6M	30M	30M	SUSP	—	—	B	"	3
10229	Type 412	.00105	2	350	1,000	6M	45M	21M	SUSP	—	—	B	"	5
14085	Type 4638	.00105	5	350	700	6M	30M	17M	SUSP	—	—	B	"	3
14084	Type 4637	.00106	2	350	700	6-5M	30M	17M	SUSP	—	—	B	"	3

SECTION 10G—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	Nomenclature	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins or mm)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom of Qty	Carton Unit Qty
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Protected—cont.													
	.001 mfd. and upwards—cont.													
5045	Type 2715	.0012	2	350	1,000	6M	33M	17M	SUSP	—	—	B	each	5
15747	Type —	.0012	3	350	1,000	6M	28.2M	20.8M	SUSP	W 9632	—	B	"	3
12089	Type 3762	.0012	5	350	1,000	6M	45M	21M	SUSP	—	—	B	"	3
12159	Type 3806	.0012	5	350	1,000	6M	45M	21M	SUSP	—	—	B	"	3
3983	Type 2039	.0013	2	350	1,000	5M	33M	20M	SUSP	—	—	B	"	3
14434	Type 4772	.00132	2	350	700	6.5M	30M	17M	SUSP	—	—	B	"	3
14083	Type 4636	.00138	2	350	700	6.5M	30M	17M	SUSP	—	—	B	"	3
14399	Type 4748	.0014	2	350	700	6.5M	30M	17M	SUSP	—	—	B	"	3
14125	Type 4648	.0015	1	350	1,000	.175	1.67	1.20	SUSP	—	—	B	"	3
4203	Type 2159	.0015	2	350	1,000	6M	45M	21M	SUSP	—	—	B	"	5
5782	Type 3169	.0015	5	350	1,000	6M	32M	16M	SUSP	—	—	B	"	5
11500	Type 3510	.0015	10	350	1,000	6M	32M	16M	SUSP	—	—	B	"	3
12092	Type 3765	.0015	10	350	1,000	6M	45M	21M	SUSP	—	—	B	"	3
15774	Type —	.0016	2	350	1,000	1 $\frac{1}{8}$	1 $\frac{1}{4}$	1 $\frac{3}{8}$	SUSP	—	ZA.11066	B	"	3
14398	Type 4747	.001691	2	350	700	1 $\frac{1}{8}$	1 $\frac{1}{4}$ dia.	10M	SUSP	—	—	B	"	3
14391	Type 4740	.0017	15	350	700	6M	20M	1.20	SUSP	—	—	B	"	3
14127	Type 4650	.00177	1	350	1,000	.175	1.67	1.20	SUSP	—	—	B	"	3
14140	Type 4651	.0018	2	350	700	6.5M	30M	17M	SUSP	—	—	B	"	3
15952	Type 5302	.0018	5	350	1,000	6M	37M	24M	SUSP	50971	—	B	"	3
15282	Type 5217	.0018	10	350	1,000	6M	80M	25M	SUSP	51000	—	B	"	3
13356	Type 4853	.002	1	750	2,200	6M	33M	17M	SUSP	—	—	B	"	3
14408	Type 4757	.002	1	750	1,500	6M	28M	20M	SUSP	—	—	B	"	3
2011	Type 923	.002	2	350	1,000	6M	33M	17M	SUSP	—	—	B	"	5
4242	Type 2187	.002	2	350	1,000	6M	45M	21M	SUSP	—	—	B	"	5
3957	Type 2026	.002	5	350	1,000	6M	33M	17M	SUSP	—	—	B	"	3
12093	Type 3766	.002	5	350	1,000	6M	45M	21M	SUSP	—	—	B	"	3
12160	Type 3807	.002	5	350	1,000	6M	45M	21M	SUSP	—	—	B	"	3
15733	Type —	.002	10	350	1,000	6M	45M	21M	SUSP	—	—	A	"	3
12094	Type 3767	.002	10	350	1,000	6M	45M	21M	SUSP	—	ZA 18576	A	"	3
12128	Type 3786	.002	10	750	2,200	5M	30M	30M	SUSP	—	—	B	"	3

SECTION 10C—cont.

FIXED CONDENSERS

NOTE 3 B. 4

1	2	3	4	5		6	7			9	10	11	12	13	14	15
				Working	Test		Height	Width	Depth							
Ref. No.	Nomenclature	Capacity mfd.	Tolerance ± %	Voltage		Overall Dimensions (ins or mm.)	Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.				
				Working	Test											
MICA DIELECTRIC—cont.																
Protected—cont.																
.001 mfd. and upwards—cont.																
3443	Type 1694	.002	15	750	2,200	6M	33M	17M	SUSP	—	—	—	B	each	5	
11912	Type 3661	.0021	2	350	1,000	6M	33M	17M	SUSP	—	—	—	B	"	3	
12554	Type 4004	.00225	10	350	1,000	6M	33M	17M	SUSP	—	—	—	B	"	5	
5798	Type 3185	.0023	2	350	1,000	6M	45M	21M	SUSP	—	—	—	B	"	3	
13893	Type 4564	.0023	2	750	1,500	6M	45M	21M	SUSP	—	—	—	B	"	3	
5046	Type 2716	.00236	2	350	1,000	6M	33M	17M	SUSP	—	—	—	B	"	5	
14401	Type 4750	.002484	2	350	700	$\frac{1}{4}$	$1\frac{1}{2}$ dia.	17M	SUSP	—	—	—	B	"	2	
5710	Type 3135	.0025	5	350	1,000	6M	33M	17M	SUSP	—	—	—	B	"	5	
12095	Type 3768	.0025	5	350	1,000	6M	45M	21M	SUSP	—	—	—	B	"	3	
12096	Type 3769	.0025	10	350	1,000	6M	45M	21M	SUSP	—	—	—	B	"	3	
14571	Type 4857	.0025	10	750	2,200	$\frac{1}{2}$	$1\frac{1}{2}$	$\frac{1}{2}$	SUSP	—	—	—	B	"	3	
5979	Type 3288	.003	2	350	1,000	6M	20M	20M	SUSP	—	—	—	B	"	3	
12400	Type 3920	.003	2	350	1,000	6M	33M	17M	SUSP	—	—	—	B	"	3	
12097	Type 3770	.003	5	350	1,000	6M	45M	21M	SUSP	—	—	—	B	"	3	
12161	Type 3808	.003	5	350	1,000	6M	45M	21M	SUSP	—	—	—	B	"	3	
3642	Type 1833	.003	10	350	1,000	6M	45M	21M	SUSP	—	—	—	B	"	5	
5786	Type 3173	.003	10	750	2,200	6M	33M	17M	SUSP	—	—	—	B	"	2	
14082	Type 4635	.00318	2	350	700	6M	30M	17M	SUSP	—	—	—	B	"	3	
4209	Type 2165	.0035	2	350	1,000	6M	45M	21M	SUSP	—	—	—	B	"	5	
13357	Type 4354	.004	1	750	2,200	6M	33M	17M	SUSP	—	—	—	B	"	3	
14099	Type 4640	.004	5	350	700	.6M	45M	20M	SUSP	—	—	—	B	"	3	
11193	Type 3396	.004	5	350	1,000	5M	30M	30M	SUSP	—	—	—	B	"	3	
11801	Type 3611	.004	5	350	1,000	6M	33M	17M	SUSP	—	—	—	B	"	3	
11942	Type 3683	.004	15	350	1,000	6M	33M	20M	SUSP	—	—	—	B	"	3	
2294	Type 1097	.005	2	350	1,000	6M	45M	21M	SUSP	—	—	—	B	"	3	
14526	Type 4834	.005	2	350	1,000	5M	30M	30M	SUSP	—	—	—	B	"	3	
5478	Type 2979	.005	5	350	1,000	6M	33M	17M	SUSP	—	—	—	B	"	3	
15734	Type —	.005	5	350	1,000	$\frac{1}{16}$	$1\frac{3}{8}$	$\frac{1}{8}$	SUSP	—	—	—	B	"	1	
11192	Type 3395	.005	5	350	1,000	$\frac{1}{16}$	33M	17M	SUSP	—	—	—	B	"	3	
4611	Type 2402	.005	10	350	1,000	6M	33M	17M	SUSP	—	—	—	B	"	3	

ZA.15409

SECTION 100—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	Voltage		OVERALL DIMENSIONS (ins. or mm.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
<p>MICA DIELECTRIC—cont. Protected—cont. .001 mfd. and upwards—cont.</p>														
12101	Type 3774	.005	10	350	1,000	6M	45M	21M	SUSP	—	—	B	each	3
12162	Type 3809	.005	10	350	1,000	6M	45M	21M	SUSP	—	—	B	"	3
14397	Type 4746	.005684	2	350	700	4	1 1/2	dia.	SUSP	—	—	B	"	2
794	Type 845	.006	15	750	2,250	6M	33M	20M	SUSP	51034	—	B	"	5
16166	Type 5417	.0068	2	350	1,000	6M	37M	24M	SUSP	—	—	B	"	5
5476	Type 2977	.0073	2	350	1,000	5M	30M	30M	SUSP	—	—	B	"	5
12102	Type 3775	.0075	2	350	1,000	6M	45M	21M	SUSP	—	—	B	"	3
12104	Type 3777	.0075	10	350	1,000	6M	45M	21M	SUSP	—	—	B	"	3
12401	Type 3921	.008	5	350	1,000	6M	45M	21M	SUSP	—	—	B	"	3
11935	Type 3677	.01	2	350	1,000	2M	42M	24M	SUSP	—	—	B	"	3
5479	Type 2980	.01	2	350	1,000	5M	30M	30M	SUSP	—	—	B	"	3
15746	Type —	.01	5	350	1,000	.6M	75M	20M	SUSP	W.7262	—	B	"	3
12106	Type 3779	.01	5	350	1,000	6M	45M	21M	SUSP	—	—	B	"	3
15745	Type —	.01	5	750	2,200	.6M	75M	20M	SUSP	W.6931	—	B	"	3
3446	Type 1697	.015	15	750	2,200	5M	30M	30M	SUSP	—	—	B	"	5
3447	Type 1698	.016	15	750	2,200	5M	30M	30M	SUSP	—	—	B	"	5
<p>Rectangular— Metal—</p>														
15725	Type —	mmfd.	10	5,000	15KV	7 1/2	7 1/2	4 1/2	UPRT	—	ZA.1628	B	"	1
10015	Type 352	500	10	2,400	7,200	6	7 1/2	4 1/2	UPRT	—	—	B	"	1
7204	Type 56	5,000	5	500	1,000	1 3/8	3	1 3/8	UPRT	—	—	B	"	2
7174	Type 57	10,000	5	500	1,000	1 3/8	3	1 3/8	UPRT	—	—	B	"	2
15792	Type —	10,704	1 1/2	250	500	3 3/8	2 3/4	1 3/8	UPRT	—	YB.01465	B	"	1
15793	Type —	13,285	1 1/2	250	500	3 3/8	2 3/4	1 3/8	UPRT	—	YB.01466	B	"	1
4113	Type 2112	18,000	1 1/2	250	500	3	2 3/4	1 3/8	UPRT	—	—	B	"	2
3991	Type 2047	34,770	1 1/2	250	500	3	2 3/4	1 3/8	UPRT	—	—	B	"	2
4112	Type 2111	50,000	1 1/2	250	500	3	2 3/4	1 3/8	UPRT	—	—	B	"	2
15727	Type —	.1 mfd.	10	350	1,000	2 1/8	2 3/4	1 3/8	UPRT	—	YB.03296	B	"	1

SECTION 10C—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mmd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Qty. Unit
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Rectangular—cont.													
	Metal—cont.													
15726	Type —	.1 mfd.	+250-0	250	500	2 1/8	2 3/8	1 1/8	UPRT	—	YB.03297	B	each	2
3990	Type 2046	.17043mfd	1/2	250	500	3	2 3/8	1 3/8	UPRT	—	—	B	"	2
15790	Type —	5.950 + 5093	1/2	250	500	3 3/8	2 3/4	3/4	UPRT	—	YB.01462	B	"	1
15791	Type —	7.345 + 6318	1/2	250	500	3 3/8	2 3/4	3/4	UPRT	—	YB.01463	B	"	1
15794	Type —	28.597 + 32.451	1/2	250	500	3 3/8	2 3/4	3/4	UPRT	—	YB.01467	B	"	1
15795	Type —	32.248 + 36.931	1/2	250	500	3 3/8	2 3/4	3/4	UPRT	—	YB.01468	B	"	1
15797	Type —	77.544 + 94.954	1/2	250	500	3 3/8	2 3/4	3/4	UPRT	—	YB.01470	B	"	1
16816	Moulded:—													
15119	Type 5963	50	—	3,500	7,000	3 1/8	2 11/8	1 11/8	UP/SD	—	—	B	"	—
8498	Type 5122	50	5	1,500	3,000	3 3/8	2 3/4	1 3/8	UP/SD	—	—	B	"	2
564	Type 190	75	6	1a at 100 Kc/s	12 Kc/s	3 1/8	2 7/8	1 3/8	UPRT	—	—	B	"	2
3354	Type 764	80	5 mmd.	6,000	12 Kc/s	3 5/8	3 1/4	1 1/4	UPRT	—	—	B	"	1
11826	Type 6	100	5	2,500	5,000	3 5/8	2 7/8	1 3/8	UPRT	—	—	B	"	2
14507	Type 3628	100	10	2,500	5,000	3 5/8	2 7/8	1 3/8	UPRT	—	—	B	"	1
3363	Type 4822	100	10	300	600	3 5/8	2 3/4	1 3/8	UP/SD	—	—	B	"	3
11823	Type 47	140	3-6	2,500	5,000	3 5/8	2 7/8	1 3/8	UPRT	—	—	B	"	2
3341	Type 3625	150	5	2,500	5,000	3 5/8	2 7/8	1 3/8	UPRT	—	—	B	"	1
2310	Type 9	200	10	500	1,000	4	2 7/8	—	UPRT	—	—	B	"	5
16912	Type 63	200	10	Inf. Meg.	1,000	4	2 7/8	—	UPRT	—	—	B	"	2
8507	Type 6024	250	10	7,500	—	4	2 7/8	—	STUD	—	—	B	"	—
8497	Type 198	260	7	1a at 100 Kc/s	—	4	2 7/8	—	UPRT	—	—	B	"	2
2933	Type 189	300	6	1/4 at 100 Kc/s	—	4	2 7/8	—	UPRT	—	—	B	"	3
11825	Type 1410	300	10	500	1,000	4	2 7/8	—	UPRT	—	—	B	"	3
	Type 3627	300	10	2.5a at 2.5 Mc/s	—	4	2 7/8	—	UPRT	—	—	B	"	1

SECTION 10C—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
MICA DIELECTRIC—cont.														
Rectangular—cont.														
Moulded—cont.														
15981	Type 5317	300	10	10KV	20KV	5 1/4	2 1/4	—	STUD	—	ZC.1536	B	each	1
14512	Type 4827	500	5	2,000	4,000	5 1/4	2 1/4	—	STUD	—	—	B	"	1
9294	Type 271	500	5	2,500	5,000	5 1/4	2 1/4	—	UPRT	—	—	B	"	1
9377	Type 302	500	15	1a at 3-15 Mc/s	—	3 1/8	2 1/8	1 1/8	UP/SD	—	—	B	"	2
13451	Type 4390	600	10	250	500	1 1/8	2 1/8	1 1/8	UPRT	—	—	B	"	2
13320	Type 4329	600	15	3a at 750 Kc/s	—	2 1/8	2 1/8	1 1/8	UPRT	—	—	B	"	2
16913	Type 4331	600	15	8a at 500 Kc/s	—	2 1/8	2 1/8	1 1/8	UPRT	—	—	B	"	1
13452	Type 4391	800	15	7,500	—	4 1/4	2 1/4	—	STUD	—	—	B	"	—
15889	Type 5275	850	5	500	1,000	4 1/4	3 1/8	—	UPRT	—	—	B	"	1
14509	Type 4824	1,000	5	1,800	3,600	7 1/2	2 1/2	—	UPRT	—	—	B	"	3
8048	Type 143	1,000	5	2,500	5,000	1 1/2	1 1/2	1 1/2	UPRT	—	—	B	"	2
5223	Type 2815	1,000	10	1,500	3,000	3 1/8	2 1/8	—	UP/SD	—	ZA.1705	B	"	1
7763	Type 108	1,090	10	10a at 250 Kc/s	—	3 1/8	3 1/8	1 1/8	UPRT	—	—	B	"	2
12735	Type 4070	1,111	5	6a at 300 Kc/s	—	4 1/4	4 1/4	—	UPRT	—	—	B	"	1
5193	Type 2785	1,250	10	2,500	5,000	3 1/8	2 1/8	—	UPRT	—	—	B	"	1
13453	Type 4392	1,300	15	6a at 400 Kc/s	—	4 1/4	4 1/4	—	UPRT	—	—	B	"	1
13448	Type 4387	1,500	10	500	1,000	—	2 1/8	1 1/8	UPRT	—	—	B	"	2
16914	Type 6026	1,600	10	7,500	—	4 1/4	2 1/4	—	STUD	—	—	B	"	1
8045	Type 140	2,000	5	2,500	5,000	3 1/8	3 1/8	1 1/8	UPRT	—	—	B	"	1
8499	Type 191	2,000	5	2,500	5,000	3 1/8	3 1/8	1 1/8	UPRT	—	—	B	"	2
9374	Type 298	2,000	5	2,500	5,000	3 1/8	3 1/8	1 1/8	UPRT	—	—	B	"	2
9297	Type 274	2,000	5	2,500	5,000	3 1/8	3 1/8	1 1/8	UPRT	—	—	B	"	2
7764	Type 109	2,000	5	5,000	10KV	1 1/4	2 1/4	—	UPRT	—	—	B	"	1
13454	Type 4393	2,110	15	6a at 250 Kc/s	—	4 1/4	4 1/4	—	UPRT	—	—	B	"	1
8164	Type 152	2,600	2	2,000	4,000	3 1/4	4 1/4	—	UPRT	—	—	B	"	1
394	Type 691	3,000	10	250	500	1 1/2	2 1/2	—	UP/SD	W.4115	—	B	"	5
13455	Type 4394	3,430	15	6a at 150 Kc/s	—	4 1/4	4 1/4	—	UPRT	—	—	B	"	1
13813	Type 4529	.001	5	500	1,000	7 1/2	1 1/2	—	SUSP	—	—	B	"	3

SECTION 10C—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont. Rectangular—cont. Moulded—cont.													
14510	Type 4825	.001	5	1,400	2,800	5 1/4	2 1/4	1 1/16	STUDD			B	each	1
3562	Type 1777	.004	10	500	1,000	2 3/8	1 3/8	1 1/16	UPRT			B	"	3
2043	Type 948	.004	10	850	1,700	3 3/8	2 1/4	1 1/16	UP/SD			B	"	1
3845	Type 1934	.0045	5	3,500	7,000	3 3/8	2 1/4	1 1/16	UP/SD			B	"	1
10049	Type 367	.005	10	250	500	1 5/8	2 3/8	1 3/8	UP/SD			B	"	5
3798	Type 1928	.005	10	2,500	5,000	3 3/8	4 1/8	2 3/8	UP/SD			B	"	1
2626	Type 1250	.005	20	2,500	5,000	3 3/8	2 1/4	2 3/8	UP/SD			B	"	2
2314	Type 33	.0089	10	Inf. Meg.	1,000	3 3/8	2 1/4	2 3/8	UPRT			B	"	2
3604	Type 1812	.01	1	250	1,000	1 7/8	2 7/8	1 3/8	UPRT			B	"	3
7039	Type 53	.01	5	2,500	5,000	3 3/8	2 7/8	2 3/8	UPRT			B	"	1
8044	Type 139	.01	5	2,500	5,000	3 3/8	2 7/8	2 3/8	UPRT			B	"	1
4034	Type 2086	.01	10	500	1,000	1 5/8	2 1/8	1 1/8	UP/SD			B	"	2
2934	Type 1411	.01	10	500	1,000	1 5/8	2 1/8	1 1/8	UP/SD			B	"	3
4042	Type 2094	.01	10	1,500	3,000	3 3/8	2 1/4	1 1/8	UP/SD			B	"	1
10008	Type 345	.01	10	2,000	4,000	3 3/8	2 1/4	1 1/8	UP/SD			B	"	2
4036	Type 2088	.01	10	2,500	5,000	3 3/8	2 1/4	1 1/8	UP/SD			B	"	2
8163	Type 151	.01	10	5,000	10KV	1 1/8	3 1/4	2 3/4	UPRT			B	"	2
4345	Type 2250	.025	10	1,000	2,000	2 1/8	2 1/8	1 1/8	UPRT			B	"	1
11011	Type 3320	.0295	1	300	600	2 1/8	2 1/8	1 1/8	UP/SD			B	"	2
11761	Type 3589	.05	5	350	1,200	3 3/8	2 1/4	2 3/8	UP/SD			B	"	2
11756	Type 3500	.05	5	350	1,200	3 3/8	2 1/4	2 3/8	UP/SD			B	"	2
3193	Type 1548	.05	10	500	1,000	3 3/8	2 1/4	2 3/8	UP/SD			B	"	2
10221	Type 414	.05	10	1,000	2,000	3 3/8	2 1/4	2 3/8	UP/SD			B	"	5
11012	Type 3321	.006	1	300	600	2 1/8	2 1/8	1 1/8	UPRT			B	"	1
9833	Type 341	.1	10	250	500	2 1/8	2 1/8	1 1/8	UPRT			B	"	2
4890	Type 2582	.1	10	350	1,000	2 3/8	2 3/8	1 1/8	UPRT			B	"	2
5137	Type 2729	.1	10	500	1,000	2 3/8	2 3/8	1 1/8	UP/SD			B	"	1
11010	Type 3319	.185	1	300	600	2 1/4	2 1/4	1 1/4	UP/SD			B	"	1
8567	Type 205	.2	10	250	500	3	2 1/8	1 1/8	UPRT			B	"	1
10010	Type 347	.25	10	250	500	3 1/4	2 1/4	1 1/4	UP/SD			B	"	2

A/K/11

SECTION 10G—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Other types:—													
8500	Type 192	100	5	2,500	5,000	$\frac{7}{16}$	$\frac{11}{16}$	—	UPRT	—	—	B	each	2
15743	Type —	160	5	28KV	35KV	$\frac{5}{4}$	$\frac{23}{32}$	—	STUD	W.5767	—	B	"	1
2178	Type 1025	200	10	5,000	10KV	$\frac{4}{4}$	$\frac{23}{32}$	—	STUD	—	ZC.0084	B	"	1
4191	Type 2147	230	20	500	1,500	$\frac{3}{32}$	$\frac{1}{16}$	—	SUSP	—	ZC.11445	B	"	3
2693	Type 12	300	5	1,500	3,000	$\frac{3}{4}$	2	$\frac{1}{2}$	UPRT	—	—	B	"	1
3796	Type 1926	500	5	25KV	50KV	$\frac{8}{8}$	$\frac{3}{16}$	—	STUD	—	—	B	"	1
2179	Type 1026	500	10	5,000	10KV	$\frac{4}{4}$	$\frac{23}{32}$	—	STUD	—	ZC.2175	B	"	1
4433	Type 2299	500	20	500	1,500	$\frac{3}{32}$	$\frac{1}{16}$	$\frac{1}{2}$	SUSP	—	ZC.11915	B	"	5
		mid.												
2337	Type 1127	.001	10	5,000	10KV	$\frac{4}{4}$	$\frac{23}{32}$	—	STUD	—	ZC.1534	B	"	1
2244	Type 1062	.001	10	15KV	30KV	$\frac{8}{8}$	$\frac{3}{16}$	—	STUD	—	—	B	"	1
2386	Type 1201	.001	10	25KV	51KV	$\frac{5}{16}$	$\frac{3}{16}$	—	UPRT	—	ZC.1707	B	"	1
2243	Type 1061	.001	10	28KV	56KV	$\frac{14}{4}$	$\frac{5}{16}$	—	CLMP	—	—	B	"	1
4190	Type 2146	.001	20	500	1,500	$\frac{7}{16}$	$\frac{1}{16}$	$\frac{1}{8}$	SUSP	—	ZC.11916	B	"	3
2181	Type 1028	.0015	10	25KV	50KV	$\frac{5}{16}$	$\frac{3}{16}$	—	UPRT	—	ZC.1535	B	"	1
14511	Type 4826	.002	5	600	1,200	$\frac{5}{16}$	$\frac{3}{16}$	—	STUD	—	—	B	"	1
4193	Type 2149	.0023	5	500	1,500	$\frac{3}{32}$	$\frac{1}{16}$	—	SUSP	—	—	B	"	3
4192	Type 2148	.0023	20	500	1,500	$\frac{3}{32}$	$\frac{1}{16}$	$\frac{1}{4}$	SUSP	—	—	B	"	3
14516	Type 4829	.0035	5	3,500	7,000	$\frac{5}{16}$	$\frac{2}{16}$	—	STUD	—	—	B	"	3
2182	Type 1029	.004	10	2,000	4,000	$\frac{1}{4}$	$\frac{2}{16}$	—	UPRT	—	—	B	"	1
3386	Type 1651	.005	10	5,000	10KV	$\frac{1}{4}$	$\frac{2}{16}$	—	STUD	—	—	B	"	1
15783	Type —	.005	20	1,000	2,000	$\frac{4}{16}$	$\frac{2}{16}$	—	UPRT	—	ZC.0538	B	"	3
5532	Type 2995	.006	5	250	500	$\frac{1}{16}$	$\frac{1}{16}$	—	STUD	—	—	B	"	2
2246	Type 1064	.01	10	5,000	10KV	$\frac{2}{16}$	$\frac{2}{16}$	—	STUD	—	—	B	"	1
2245	Type 1063	.01	20	15KV	30KV	$\frac{4}{16}$	$\frac{5}{16}$	—	CLMP	—	—	B	"	1
17019	Type —	.01	20	750	2,200	$\frac{14}{14}$	$\frac{5}{16}$	—	SUSP	—	ZC.11328	B	"	3
15887	Type 5273	.04	5	750	1,500	$\frac{1}{8}$	$\frac{1}{8}$	—	UPRT	—	—	B	"	5

SECTION 10G—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	PAPER DIELECTRIC:—												
	Cylindrical:—												
	Insulated:—												
13310	Type 4323	.001	15	600	1,500	1 1/8	1/8	SUSP	—	—	B	each	2
5811	Type 3198	.001	25	750	2,000	1 1/8	1/8	SUSP	—	—	B	"	2
11120	Type 3356	.001	25	1,000	2,000	1 1/8	3/16	SUSP	50000	ZA.24252	B	"	3
13238	Type 4273	.0015	10	450	900	1 1/8	1/16	SUSP	—	—	B	"	2
11134	Type 3370	.002	10	1,000	2,000	1 1/8	1/16	SUSP	—	—	B	"	3
12884	Type 4118	.002	15	450	1,500	1 1/8	1/16	SUSP	—	—	B	"	3
15789	Type —	.002	20	400	1,000	1 1/8	7/16	SUSP	—	—	B	"	3
11124	Type 3357	.002	25	1,000	2,000	1 1/8	1/8	SUSP	50001	ZA.24251	B	"	3
4774	Type 2506	.0022	20	400	800	1 1/8	1/8	SUSP	—	—	B	"	3
2173	Type 1020	.003	10	3,500	10,500	3 3/8	1/8	SUSP	—	ZC.0511	B	"	1
11139	Type 3375	.003	20	1,000	2,000	1 1/8	1/8	SUSP	—	—	B	"	3
11956	Type 3693	.0035	10	450	1,000	1 1/8	1/8	SUSP	—	—	B	"	3
4167	Type 2123	.0035	20	750	1,500	1 1/8	1/8	SUSP	—	—	B	"	2
11140	Type 3376	.004	20	1,000	2,000	1 1/8	1/8	SUSP	—	ZA.21760	B	"	3
4566	Type 2376	.005	2	450	1,500	1 1/8	1/8	SUSP	—	—	B	"	2
4925	Type 2615	.005	10	300	1,000	1 1/8	1/8	SUSP	—	—	B	"	2
5867	Type 3215	.005	10	500	1,000	1 1/8	1/8	SUSP	—	—	B	"	3
11125	Type 3974	.005	10	1,000	2,000	1 1/8	1/8	SUSP	—	—	B	"	3
4610	Type 2401	.005	10	30,000	50,000	2 3/4	2 3/8	CLMP	—	—	B	"	1
5807	Type 3194	.005	15	600	1,500	1 1/8	1/8	SUSP	—	—	B	"	3
11136	Type 3372	.005	20	375	750	1 1/8	1/8	SUSP	—	—	B	"	3
2973	Type 1103	.005	20	400	1,000	1 1/8	1/8	SUSP	—	—	B	"	2
4204	Type 2160	.005	20	750	2,200	1 1/8	1/8	SUSP	—	P&B.0669	B	"	2
11192	Type 3858	.005	25	1,000	2,000	1 1/8	1/8	SUSP	50002	ZC.17222	B	"	3
11141	Type 3377	.006	20	1,000	2,000	1 1/8	1/8	SUSP	—	ZA.24260	B	"	3
4205	Type 2161	.006	5	750	1,500	1 1/8	1/8	SUSP	—	—	B	"	2
13497	Type 4414	.01	10	250	700	1 1/8	1/8	SUSP	—	—	B	"	2
6000	Type 2860	.01	10	400	800	1 1/8	1/8	SUSP	—	—	B	"	2
3092	Type 1656	.01	10	500	900	1 1/8	1/8	SUSP	—	—	B	"	2
5868	Type 3216	.01	10	500	1,000	1 1/8	1/8	SUSP	—	—	B	"	3

SECTION 100—*cont.*

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Qty.
				Working	Test	Length	Diameter						
1													
	PAPER DIELECTRIC—<i>cont.</i>												
	Cylindrical—<i>cont.</i>												
	Insulated—<i>cont.</i>												
3507	Type 1733	.01	10	750	2,200	1 1/4	1 1/8	SUSP			B	each	2
11197	Type 9973	.01	10	1,000	2,000	1 1/4	1 1/8	SUSP			B	—	2
2590	Type 1228	.01	10	3,000	6,000	2 1/2	1 1/8	SUSP			B	"	2
15749	Type —	.01	15	250	700	1 1/8	1/8	SUSP			B	"	3
15705	Type —	.01	15	400	1,000	1 3/8	7/16	SUSP			B	"	5
12944	Type 4136	.01	15	600	1,200	1 3/8	1/8	SUSP			B	"	3
13309	Type 4322	.01	15	600	1,500	1 3/8	1/8	SUSP			B	"	2
2272	Type 1082	.01	15	750	2,000	1 3/8	1/8	SUSP			B	"	2
2715	Type 1318	.01	20	250	700	1 1/8	1/8	SUSP			B	"	2
11796	Type 3604	.01	20	350	1,000	1 1/8	1/8	SUSP			B	—	2
4766	Type 2498	.01	20	350	1,000	1 1/8	1/8	SUSP			B	"	3
11188	Type 9974	.01	20	375	750	1 1/8	1/8	SUSP			B	—	3
2811	Type 1314	.01	20	400	1,000	1 1/4	1/8	SUSP			B	"	2
684	Type 796	.01	20	450	1,000	1 1/4	1/8	SUSP			B	"	2
5077	Type 9286	.01	20	450	1,000	1 1/4	1/8	SUSP			B	—	2
4679	Type 2450	.01	20	450	1,500	1 1/4	1/8	SUSP			B	"	2
15762	Type —	.01	20	500	1,000	1 3/4	1/8	SUSP			B.	"	3
17021	Type —	.01	20	500	1,000	3 1/4	1/8	SUSP			B	"	3
11127	Type 9968	.01	20	500	1,000	2	1/8	SUSP			B	—	2
5310	Type 2861	.01	20	600	1,200	1 1/4	1/8	SUSP			B	—	2
4176	Type 2132	.01	20	750	1,500	1 1/8	1/8	SUSP			B	"	2
13004	Type 4172	.01	20	800	1,600	1 1/8	1/8	SUSP			B	"	2
2716	Type 1319	.01	20	800	2,000	1 1/8	1/8	SUSP			B	"	2
11960	Type 3697	.01	20	800	2,000	1 1/8	1/8	SUSP			B	"	2
785	Type 246	.01	20	1,000	2,000	1 1/8	1/8	SUSP			B	—	2
12772	Type 4075	.01	20	1,500	3,000	1 1/8	1/8	SUSP			B	"	2
13710	Type 4494	.01	20	2,000	4,000	1 1/8	1/8	SUSP			B	"	1
15078	Type 5098	.01	± 20	1,000	3,000	1 1/8	1/8	SUSP			B	"	2

SECTION 10G—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	PAPER DIELECTRIC—cont. Cylindrical—cont. Insulated—cont.												
16001	Type 5324	.01	25	250	500	1 5/8	5/16	SUSP	—	ZA.25930	B	each	—
15131	Type 5132	.01	25	500	1,500	1 3/4	7/16	SUSP	—	—	B	"	3
2812	Type 1315	.01	25	750	2,000	1 3/4	7/16	SUSP	—	—	B	"	3
11123	Type 3359	.01	25	1,000	2,000	1 1/2	1/2	SUSP	50003	ZA.24259	B	"	2
4549	Type 2859	.01	25	1,000	2,000	1 1/2	1/2	SUSP	—	—	B	"	3
15939	Type 5298	.01	25	1,000	3,000	1 1/2	1/16	SUSP	—	ZA.20915	B	"	3
9133	Type 1591	.015	20	450	1,500	1 1/2	1/16	SUSP	—	—	B	"	3
12978	Type 4158	.02	5	1,000	2,000	1 3/4	7/16	SUSP	—	—	B	"	2
11142	Type 3978	.02	10	750	1,500	1 1/2	1/8	SUSP	—	—	B	"	2
12986	Type 4166	.02	10	1,000	2,000	1 3/4	7/16	SUSP	—	—	B	"	2
13664	Type 4479	.02	+20-10	1,500	3,000	1 3/4	7/16	SUSP	—	—	B	"	2
5704	Type 8129	.02	15	450	1,000	1 1/2	5/16	SUSP	—	—	B	"	1
17005	Type —	.02	15	450	1,500	1 3/8	7/16	SUSP	W.2560	—	B	"	2
14475	Type 4802	.02	20	350	700	1	1/8	SUSP	—	—	B	"	2
14271	Type 512	.02	20	375	1,000	1 1/8	3/16	SUSP	—	—	B	"	2
5976	Type 3285	.02	20	450	1,500	1 1/4	1/16	SUSP	50004	ZA.24258	B	"	2
11124	Type 3860	.02	20	750	1,500	1 1/4	1/16	SUSP	—	—	B	"	2
11961	Type 3698	.02	20	2,000	4,000	1 3/4	1/16	SUSP	—	—	B	"	2
11957	Type 3694	.023	20	450	1,000	1 1/4	3/32	SUSP	—	—	B	"	2
4206	Type 2162	.023	20	750	1,500	1 1/4	1/16	SUSP	—	—	B	"	2
12981	Type 4161	.025	5	250	500	1 1/4	7/16	SUSP	—	—	B	"	3
12980	Type 4160	.025	5	1,000	2,000	1 1/4	7/16	SUSP	—	—	B	"	2
15755	Type —	.025	15	350	1,000	1 1/4	7/16	SUSP	—	ZA.1596	B	"	3
14437	Type 3695	.025	15	350	1,000	1 1/4	8/16	SUSP	—	—	B	"	3
20728	Type 938	.025	15	450	1,000	1 1/4	7/16	SUSP	—	ZA.14071	B	"	3
5149	Type 2741	.025	15	1,000	2,000	1 3/4	7/16	SUSP	—	—	B	"	2
6579	Type 3042	.025	15	350	1,000	1 1/4	1/16	SUSP	—	ZA.15035	B	"	2
11143	Type 3279	.03	20	500	1,000	1 1/2	1/2	SUSP	—	—	B	"	2
2791	Type 1333	.03	20	800	2,000	2	7/16	SUSP	—	—	B	"	2
13814	Type 4530	.035	5	350	700	1 1/2	1/8	SUSP	—	—	B	"	2

SECTION 100—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	Nomenclature	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	PAPER DIELECTRIC—cont. Cylindrical—cont. Insulated—cont.												
12960	Type 4145	.035	20	600	1,200	1 1/4	1 1/4	SUSP			B	each	2
4257	Type 2202	.04	15	350	1,000	1 1/4	1 1/4	SUSP			B	"	2
12430	Type 3937	.04	15	1,000	2,000	1 1/4	1 1/4	SUSP			B	"	2
12144	Type 3793	.04	15	1,500	3,000	2 1/4	1 1/4	SUSP			B	"	2
4234	Type 2179	.05	2	750	1,500	1 1/4	1 1/4	SUSP			B	"	2
5053	Type 2723	.05	5	400	1,000	1 1/4	1 1/4	SUSP			B	"	2
5961	Type 3270	.05	10	750	1,500	1 1/4	1 1/4	SUSP			B	"	2
2315	Type 1105	.05	15	350	700	1 1/4	1 1/4	SUSP			B	"	2
15770	Type —	.05	15	350	1,000	1 1/4	1 1/4	SUSP		ZA.1746	B	"	3
15751	Type —	.05	15	350	1,000	1 1/4	1 1/4	SUSP		ZA.1620	B	"	3
3010	Type 1620	.05	15	350	1,000	2 1/4	1 1/4	SUSP			B	"	2
2271	Type 1081	.05	15	750	2,000	2 1/4	1 1/4	SUSP			B	"	2
4998	Type 2688	.05	15	1,000	2,000	2 1/4	1 1/4	SUSP			B	"	2
4921	Type 2611	.05	15	1,500	3,000	2 1/4	1 1/4	SUSP			B	"	2
5975	Type 3284	.05	20	450	1,000	1 1/4	1 1/4	SUSP		ZC.15132	B	"	2
16690	Type 5865	.05	20	500	1,500	1 1/4	1 1/4	SUSP			B	"	2
17020	Type —	.05	20	500	1,000	1 1/4	1 1/4	SUSP		ZC.20752	B	"	3
11125	Type 8901	.05	20	500	1,000	1 1/4	1 1/4	SUSP		ZA.24287	B	"	3
11959	Type 3696	.05	20	1,000	2,000	1 1/4	1 1/4	SUSP			B	"	2
12707	Type 4062	.05	20	2,000	4,000	1 1/4	1 1/4	SUSP			B	"	2
15950	Type 5300	.05	25	250	375	2 1/4	1 1/4	SUSP		ZA.30403	B	"	3
15128	Type 5129	.05	25	350	525	2 1/4	1 1/4	SUSP			B	"	2
744	Type 830	.075	15	350	1,000	2 1/4	1 1/4	SUSP			B	"	2
12860	Type 4103	.09	20	3,000	6,000	3 1/4	1 1/4	CLMP			B	"	2
12979	Type 4159	.1	5	250	500	1 1/4	1 1/4	SUSP			B	"	2
2717	Type 1320	.1	5	350	700	1 1/4	1 1/4	SUSP			B	"	2
5356	Type 2904	.1	5	450	1,000	1 1/4	1 1/4	SUSP			B	"	3
4181	Type 2137	.1	5	750	1,500	1 1/4	1 1/4	SUSP			B	"	2
14527	Type 4835	.1	5	350	1,000	1 1/4	1 1/4	SUSP			B	"	2
13496	Type 4413	.1	10	250	700	1 1/4	1 1/4	SUSP			B	"	2

SECTION 10C—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Qty.
				Working	Test	Length	Diameter						
1	PAPER DIELECTRIC—cont. Cylindrical—cont. Insulated—cont.	3	4	5	6	7	8	9	10	11	12	13	14
9997	Type 1408	1	10	950	1,000	1 1/8	1 1/8	SUSP	—	—	B	each	2
4626	Type 2411	1	10	350	1,000	1 1/8	1 1/8	SUSP	—	—	B	"	2
12983	Type 4168	1	10	490	800	1 1/8	1 1/8	SUSP	—	—	B	"	2
12974	Type 4154	1	10	500	1,000	2 1/8	1 1/8	SUSP	—	—	B	"	2
3488	Type 1721	1	10	1,000	2,000	2 3/8	1 1/8	SUSP	—	—	B	"	2
12985	Type 4165	1	10	1,000	2,000	2 1/8	1 1/8	SUSP	—	—	B	"	2
11974	Type 3700	1	10	1,500	3,000	2 1/8	1 1/8	SUSP	—	—	B	"	2
12773	Type 4076	1	10	2,000	4,000	2 1/8	1 1/8	SUSP	—	—	B	"	2
2252	Type 1067	1	15	250	700	1 1/8	1 1/8	SUSP	W.6709	—	B	"	2
17006	Type —	1	15	250	1,000	1 1/8	1 1/8	SUSP	W.3612	—	B	"	2
15750	Type —	1	15	350	1,000	1 1/8	1 1/8	SUSP	—	—	B	"	3
4550	Type 2360	1	15	450	900	2	1 1/8	SUSP	—	—	B	"	2
683	Type 795	1	15	450	1,500	1 1/8	1 1/8	SUSP	—	—	B	"	2
800	Type 851	1	15	500	1,000	1 1/8	1 1/8	SUSP	—	—	B	"	2
4553	Type 2363	1	15	1,000	2,000	2 1/8	1 1/8	SUSP	—	—	B	"	2
798	Type 849	1	15	1,000	2,000	2 1/8	1 1/8	SUSP	—	—	B	"	2
5673	Type 3098	1	15	2,000	4,000	2 1/8	1 1/8	SUSP	W.4037	—	B	"	2
15722	Type —	1	20	350	1,000	1 1/8	1 1/8	SUSP	—	—	B	"	1
16055	Type 5347	1	20	350	1,000	1 1/8	1 1/8	STUD	—	—	B	"	2
15936	Type 5295	1	20	350	1,000	1 1/8	1 1/8	SUSP	—	—	B	"	2
14518	Type 4830	1	20	500	1,000	1 1/8	1 1/8	SUSP	—	—	B	"	3
12459	Type 3952	1	20	500	1,000	2 1/8	1 1/8	SUSP	—	—	B	"	2
4241	Type 2186	1	20	1,000	2,000	2 1/8	1 1/8	SUSP	50008	ZC.12642	B	"	1
4823	Type 2554	1	20	1,500	3,000	2 1/8	1 1/8	SUSP	—	—	B	"	2
16125	Type 5383	1	25	250	375	1 3/8	1 3/8	SUSP	—	—	B	"	3
2624	Type 1248	1	25	450	900	1 3/8	1 3/8	SUSP	—	—	B	"	3
15245	Type 5210	1	25	250	700	1 3/8	1 3/8	SUSP	—	—	B	"	5
11955	Type 3692	1	5	450	1,000	1 1/8	1 1/8	SUSP	—	—	B	"	2
12398	Type 3919	1	10	350	700	1 1/8	1 1/8	SUSP	—	—	B	"	2
11952	Type 3689	1	20	450	1,000	1 1/8	1 1/8	SUSP	—	—	B	"	2

SECTION 10C—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	Nomenclature	Capacity mfd.	Tolerance ± %	VOLTAGE		Test	OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom of Qty	Carton Unit Qty
				Working			Length	Diameter						
1	PAPER DIELECTRIC—cont. G. Cylindrical—cont. Insulated—cont.													
5641	Type 3066	.2	15	450	1,000	1 3/4	1	SUSP				B	each	2
3647	Type 1838	.2	15	650	1,300	2	1 3/8	SUSP				B	"	1
5973	Type 3282	.23	5	450	1,000	1 1/2	3/8	SUSP				B	"	2
5974	Type 3283	.23	20	450	1,000	1 1/2	3/8	SUSP	W.8069	ZC.11448		B	"	2
12987	Type 4167	.25	5	250	500	2 1/4	9/16	SUSP				B	"	2
13840	Type 4539	.25	10	250	700	2 1/4	1 1/8	SUSP				B	"	2
12988	Type 4168	.25	10	1,000	2,000	2 1/4	1 1/8	SUSP				B	"	2
15706	Type —	.25	15	250	700	2 1/4	1 1/8	SUSP	W.5662			B	"	5
2253	Type 1068	.25	15	350	1,000	2 1/4	1 1/8	SUSP				B	"	2
13006	Type 4175	.25	15	450	1,000	2 1/4	1 1/8	SUSP				B	"	2
4551	Type 2361	.25	15	450	900	1 3/4	1 1/8	SUSP				B	"	2
4543	Type 2353	.25	15	450	900	1 3/4	1 1/8	SUSP				B	"	2
5699	Type 3124	.25	15	450	1,000	2	1 1/8	SUSP				B	"	2
5162	Type 2754	.25	15	450	1,000	1 3/4	1 1/8	SUSP				B	"	2
11788	Type 3606	.25	15	750	1,500	2 1/4	1 1/8	SUSP				B	"	2
12145	Type 3794	.25	15	750	1,500	2 1/4	1 1/8	SUSP				B	"	2
2024	Type 934	.25	15	1,000	3,000	2 3/8	1 1/8	SUSP				B	"	2
11199	Type 2964	.25	20	250	700	2	1 1/8	SUSP	50009	ZA-15259		B	"	2
4803	Type 2534	.25	20	450	1,000	1 1/2	1 1/8	SUSP				B	"	3
11199	Type 2965	.25	20	500	1,000	2 1/4	1 1/8	SUSP	50010	ZA-91954		B	"	2
13005	Type 4174	.25	20	700	1,400	2 1/4	1 1/8	SUSP				B	"	2
15083	Type 5103	.25	+20-20	500	1,500	2 3/8	1 1/8	SUSP	52170			B	"	2
16124	Type 5382	.25	25	150	250	1 1/8	5/16	SUSP				B	"	3
16123	Type 5381	.3	25	350	525	1 1/2	5/16	SUSP				B	"	3
15130	Type 5131	.3	25	350	1,000	1 1/2	5/16	SUSP				B	"	2
5657	Type 3082	.4	15	450	1,000	2 1/8	1 1/8	SUSP				B	"	2
12989	Type 4169	.5	10	350	700	2 1/4	1 1/8	SUSP				B	"	2
5140	Type 2732	.5	15	400	1,000	2 3/8	1 1/8	SUSP	W.3642	ZC.13032		B	"	2
2711	Type 1304	.5	15	450	900	1 3/4	1 1/8	SUSP				B	"	1
4804	Type 2535	.5	15	450	1,500	2 1/8	1 1/8	SUSP				B	"	3

11199

SECTION 100—cont

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref	Army Ref.	Class of Store	Denom. of Qty	Carton Unit Qty
				Working	Test	Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13	14
PAPER DIELECTRIC—cont.													
Cylindrical—cont.													
Insulated—cont.													
19100	Type 4294	.5	15	450	1,500	2	1	SUSP	—	ZA 24291	B	each	2
4909	Type 2601	.5	15	450	1,500	1 1/2	1 1/2	SUSP	—	ZA 24291	B	"	1
11190	Type 3266	.5	20	350	700	2 1/4	1 1/2	SUSP	56011	ZA 24291	B	"	2
15723	Type —	.5	20	350	1,000	2 1/4	1	SUSP	—	ZA 1664	B	"	1
15724	Type —	.5	20	350	1,000	2 1/4	1 1/2	SUSP	—	ZA 19752	B	"	1
15129	Type 6180	.5	20	350	1,000	2 1/4	3/4	SUSP	56011	ZA 24291	B	"	2
5795	Type 3182	.5	20	450	1,000	2 1/4	3/4	SUSP	W 8073	ZC 11924	B	"	2
12379	Type 3906	.5	20	450	1,000	2 1/4	1 1/2	SUSP	—	—	B	"	2
15971	Type 5312	.5	25	150	250	1 1/2	7/8	SUSP	—	—	B	"	5
5139	Type 2731	.7	15	400	1,000	2 1/2	1 1/2	SUSP	—	—	B	"	2
11954	Type 3691	1	5	450	1,000	2 1/2	1 1/2	SUSP	—	—	B	"	2
12921	Type 4110	1	15	350	1,000	2 1/4	1 1/2	SUSP	—	—	B	"	1
4544	Type 2354	1	15	400	800	2 1/4	1 1/2	CLMP	—	—	B	"	2
4871	Type 2563	1	20	450	1,000	2 1/4	1 1/2	SUSP	W 8072	ZC 11186	B	"	2
12706	Type 4061	1	20	630	1,300	2 1/4	1 1/2	SUSP	—	—	B	"	2
15126	Type 5127	1	25	150	250	1 1/2	1 1/8	SUSP	—	—	B	"	2
15132	Type 5133	1	25	250	375	1 1/2	1 1/8	SUSP	—	—	B	"	2
608	Type 773	2	20	250	500	2 1/4	1 1/2	CLMP	—	—	B	"	1
12883	Type 4112	2	20	250	500	2 1/4	1 1/2	SUSP	—	—	B	"	1
15125	Type 5126	2	25	150	250	1 1/2	1 1/8	SUSP	—	—	B	"	2
15244	Type 5209	2	25	250	375	1 1/2	1 1/8	SUSP	—	—	B	"	5
Metal:—													
12809	Type 4087	.001	-5 + 10	375	1,000	3 1/4	1 1/2	STUD	—	—	B	"	3
16167	Type 5418	.001	20	1,000	3,000	1 1/2	1 1/2	SUSP	—	ZA 26708	B	"	3
15077	Type 5097	.002	± 20	1,000	3,000	1 1/2	1 1/2	SUSP	52161	ZA 26708	B	"	3
16168	Type 5419	.002	20	1,000	3,000	1 1/2	1 1/2	SUSP	—	ZA 29706	B	"	3
15953	Type 5301	.005	10	1,000	3,000	1 1/2	1 1/2	SUSP	—	—	B	"	3
16169	Type 5420	.005	20	1,000	3,000	1 1/2	1 1/2	SUSP	—	ZA 29707	B	"	3
16118	Type 5377	.005	25	350	1,000	1	1	SUSP	—	—	B	"	3

SECTION 10G—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Qty. Unit
				Working	Test	Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13	14
	PAPER DIELECTRIC—cont.												
	Cylindrical—cont.												
	Metal—cont.												
14346	Type 4721	.01	10	350	700	1 1/8	1 1/8	UPRT	—	—	B	each	2
16103	Type 5370	.01	10	350	1,000	1 3/8	1 3/8	STUD	—	—	B	—	3
4024	Type 2076	.01	15	350	1,000	2 1/8	2 1/8	STUD	W.9244	—	B	—	1
11753	Type 3583	.01	15	350	1,000	3 3/8	3 3/8	STUD	—	—	B	—	1
14072	Type 4631	.01	15	450	1,000	2 1/4	2 1/4	STUD	—	—	B	—	3
3276	Type 1590	.01	15	750	2,250	1 1/8	1 1/8	SUSP	—	—	B	—	2
16170	Type 5421	.01	20	1,000	3,000	1 3/8	1 3/8	SUSP	—	—	B	—	3
11747	Type 3578	.01	20	2,500	5,000	3 3/8	3 3/8	UPRT	—	—	B	—	1
2625	Type 1249	.01	20	2,500	5,000	3 3/8	3 3/8	UPRT	W.3715	—	B	—	2
16085	Type 5359	.01	25	350	1,000	1 1/8	1 1/8	SUSP	—	—	B	—	3
16129	Type 5387	.01	25	500	1,000	1 1/8	1 1/8	SUSP	—	—	B	—	3
17010	Type —	.02	10	350	1,000	2 1/8	2 1/8	UPRT	—	—	B	—	2
13209	Type 4258	.02	10	350	1,000	2 1/8	2 1/8	UPRT	—	—	B	—	1
2568	Type 1215	.02	10	450	1,500	1 5/8	1 5/8	STUD	—	—	B	—	2
16107	Type 5374	.02	10	750	1,500	1 5/8	1 5/8	SUSP	—	—	B	—	3
2157	Type 997	.02	15	8,000	16,000	6 1/8	6 1/8	CLMP	W.7913	ZC.3356	B	—	1
13578	Type 4444	.02	20	350	1,000	1 3/8	1 3/8	UPRT	—	—	B	—	1
16171	Type 5422	.02	20	750	2,200	1 1/8	1 1/8	SUSP	—	—	B	—	3
16567	Type 5759	.02	20	750	2,200	1 1/8	1 1/8	SUSP	—	—	B	—	3
15201	Type 5190	.02	25	350	700	1 1/8	1 1/8	STUD	—	—	B	—	3
3026	Type 1438	.02	25	450	1,500	1 1/8	1 1/8	STUD	—	—	B	—	2
11751	Type 3581	.025	15	350	8,000	2 3/8	2 3/8	UPRT	—	—	B	—	1
15973	Type 5313	.025	20	2,500	5,000	3 3/8	3 3/8	CLMP	—	—	B	—	5
16837	Type 5971	.04	10	350	1,000	1 1/8	1 1/8	SUSP	—	—	B	—	1
11388	Type 3460	.04	—	4,000	8,000	5	5	CLMP	—	—	B	—	1
15907	Type 5283	.05	5	500	1,500	1 1/8	1 1/8	SUSP	—	—	B	—	3
14371	Type 4725	.05	10	350	700	2 1/8	2 1/8	UPRT	—	—	B	—	3
14372	Type 4726	.05	10	350	700	2 1/8	2 1/8	UPRT	—	—	B	—	2
11754	Type 3584	.05	15	350	1,000	3 3/8	3 3/8	UPRT	—	—	B	—	1
16566	Type 5758	.05	20	450	1,500	1 5/8	1 5/8	SUSP	—	—	B	—	3

SECTION 10C—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	PAPER DIELECTRIC—cont. Cylindrical—cont. Metal—cont.												
16172	Type 5423	.05	20	500	1,500	1 1/8	1 1/8	SUSP	—	ZA.29591	B	each	3
15954	Type 5303	.1	5	350	1,000	1 1/8	1 1/8	SUSP	—	—	B	"	3
15909	Type 5285	.1	5	500	1,500	2 1/8	1 1/8	SUSP	—	—	B	"	3
13188	Type 4246	.1	10	350	1,000	1 1/8	1 1/8	UPRT	—	—	B	"	2
2567	Type 1214	.1	10	450	1,500	2 1/8	1 1/8	STUD	—	—	B	"	2
15908	Type 5284	.1	10	500	1,500	2 1/8	1 1/8	SUSP	—	ZA.29334	B	"	3
14071	Type 4630	.1	15	350	700	2 1/8	1 1/8	STUD	—	—	B	"	2
17008	Type —	.1	15	350	750	1 1/8	1 1/8	STUD	—	ZA.11422	B	"	2
4406	Type 2272	.1	15	350	1,000	1 1/8	1 1/8	STUD	—	—	B	"	2
4021	Type 2073	.1	15	350	1,000	1 1/8	1 1/8	STUD	—	—	B	"	5
4023	Type 2075	.1	15	350	1,000	1 1/8	1 1/8	STUD	—	—	B	"	1
967	Type 899	.1	15	350	1,000	2	1 1/8	STUD	—	—	B	"	2
13203	Type 4254	.1	15	350	1,500	1 1/8	1 1/8	SUSP	W.2983	—	B	"	1
13948	Type 4580	.1	15	1,000	2,000	2 1/8	1 1/8	STUD	—	—	B	"	2
13947	Type 4579	.1	15	1,000	2,000	2 1/8	1 1/8	STUD	—	—	B	"	1
16565	Type 5757	.1	20	250	10,000	4 1/8	1 1/8	CLMP	—	—	B	"	1
12945	Type 4137	.1	20	350	1,000	1 1/8	1 1/8	SUSP	—	—	B	"	3
14495	Type 4815	.1	20	350	700	1 1/8	1 1/8	SUSP	—	—	B	"	2
12694	Type 4054	.1	20	350	1,000	1 1/8	1 1/8	STUD	—	—	B	"	—
12693	Type 4053	.1	20	350	1,000	1 1/8	1 1/8	STUD	—	—	B	"	—
16173	Type 5424	.1	20	350	1,000	1 1/8	1 1/8	SUSP	—	ZA.26605	B	"	3
16564	Type 5756	.1	20	450	1,500	2 1/8	1 1/8	SUSP	—	—	B	"	3
16174	Type 5425	.1	20	500	1,500	2 1/8	1 1/8	SUSP	—	—	B	"	3
16175	Type 5426	.1	20	500	1,500	2 1/8	1 1/8	SUSP	—	ZA.29342	B	"	3
12332	Type 3875	.1	20	1,000	3,000	2 1/8	1 1/8	SUSP	—	ZA.29708	B	"	3
13998	Type 4601	.1	20	1,500	3,000	3 1/8	1 1/8	CLMP	—	—	B	"	—
16892	Type 6004	.1	25	150	5,000	4 1/8	1 1/8	SUSP	—	—	B	"	—
16122	Type 5380	.1	25	350	1,000	1 1/8	1 1/8	SUSP	—	—	B	"	3
12810	Type 4088	.1	-5 + 10	375	1,000	2 1/8	1 1/8	STUD	—	—	B	"	—
2565	Type 1212	.1	-10 + Inf	2,500	5,000	5 1/8	1 1/8	CLMP	—	—	B	"	—

SECTION 100—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	PAPER DIELECTRIC—cont. Cylindrical—cont. Metal—cont.												
11756	Type 3586	.25	15	350	700	4	3/16	STUD	—	—	B	each	—
12132	Type 3788	.25	15	375	750	2 1/4	3/16	SUSP	W.5168	—	B	"	—
16573	Type 5765	.25	20	250	1,000	2 1/4	3/16	SUSP	—	—	B	"	3
16176	Type 5427	.25	20	350	1,000	2 1/4	3/16	SUSP	—	ZA.29709	B	"	3
16563	Type 5755	.25	20	450	1,500	2 3/8	3/16	SUSP	—	ZA.28361	B	"	3
16177	Type 5428	.25	20	500	1,500	2 3/8	3/16	STUD	—	—	B	"	3
12633	Type 4028	.25	20	500	1,500	3 1/8	3/16	STUD	—	—	B	"	3
13959	Type 4584	.25	20	500	2,500	2 1/8	1/8	UPRT	—	—	B	"	1
11752	Type 3582	.36	10	350	700	2 3/8	3/16	STUD	—	—	B	"	—
3290	Type 1601	.5	10	250	500	2 1/2	1/8	STUD	—	—	B	"	—
13190	Type 4248	.5	10	350	700	2 1/2	3/16	STUD	—	—	B	"	—
17007	Type —	.5	15	350	700	2 1/2	3/16	STUD	—	—	B	"	—
8494	Type 186	.5	15	900	2,500	5 3/8	1 1/8	UPRT	—	ZA.20956	B	"	—
16360	Type 5558	.5	20	350	1,000	2 1/2	3/16	SUSP	—	—	B	"	3
16178	Type 5429	.5	20	350	1,000	2 1/2	3/16	SUSP	—	52171	B	"	3
16575	Type 5767	.5	20	450	1,500	2 3/8	3/16	SUSP	—	—	B	"	3
16359	Type 5557	.5	20	500	—	2 3/8	3/16	SUSP	—	—	B	"	3
16823	Type 5970	.5	25	250	—	1 1/2	1/8	SUSP	—	—	B	"	3
2654	Type 1270	.5	5+10	375	750	3 1/4	3/16	STUD	—	—	B	"	—
8671	Type 216	1.0	10	250	650	5 1/8	1 1/8	UPRT	—	—	B	"	—
14390	Type 4739	1.0	10	350	700	2 1/4	1/8	STUD	—	—	B	"	—
13189	Type 4247	1.0	10	350	750	2 1/4	1/8	SUSP	—	—	B	"	1
2890	Type 1382	1.0	10	450	1,000	3 1/4	1/8	STUD	—	—	B	"	—
8657	Type 210	1.0	15	650	1,500	5 1/4	1 1/8	UPRT	—	—	B	"	2
11132	Type 3368	1.0	20	350	700	2 1/4	1/8	SUSP	—	—	B	"	2
15086	Type 5105	1.0	20	350	1,000	2 1/4	1/8	SUSP	—	—	B	"	2
14255	Type 4704	1.0	20	400	800	5 1/4	1/8	STUD	51396	—	B	"	2
11133	Type 3369	1.0	20	500	1,000	5 1/4	1/8	STUD	—	—	B	"	2
11748	Type 3579	1.25	20	350	700	4 1/4	1/8	STUD	—	—	B	"	1
16779	Type 5947	.26	-20+inf. -0+10	230	—	10 3/8	3 1/4	U-shaped STRAP	—	—	B	"	1

SECTION 100—*cont.*

FIXED CONDENSERS

VOTE 3 B. 4

1	2	3	4	5		6	7		8	9	10	11	12	13	14
				Working	Test		Length	Diameter							
Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		Test	OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.	
1															
	PAPER DIELECTRIC—<i>cont.</i>														
	Cylindrical—<i>cont.</i>														
	Metal—<i>cont.</i>														
2083	Type 973	{ .05+ .05 .1+ }	15	350	500	3 $\frac{3}{4}$	3 $\frac{3}{4}$	STUD	—	—	B	each	2		
11838	Type 3631	{ .1+ .1 .1 }	15	350	700	3 $\frac{3}{4}$	3 $\frac{3}{4}$	STUD	—	—	B	”	2		
3399	Type 1662	{ .1+ .1 .1+ }	15	250	500	3 $\frac{3}{4}$	3 $\frac{3}{4}$	STUD	—	—	B	”	2		
4020	Type 2072	{ .1+ .1 .1+ }	15	750	2,250	2	1 $\frac{1}{2}$	STUD	—	—	B	”	2		
13706	Type 4490	{ .003+ .001+ .0004+ .0001 }	10	400	750	2 $\frac{3}{4}$	1 $\frac{1}{2}$	CLMP	—	—	B	”	1		
	Plastic—														
884	Type 870	.0005	20	350	700	2 $\frac{1}{2}$	1 $\frac{1}{2}$	STUD	—	—	B	”	2		
13018	Type 4187	.0005	20	350	700	1 $\frac{1}{2}$	1 $\frac{1}{2}$	SUSP	—	—	B	”	3		
2679	Type 1283	.0005	20	600	1,200	1 $\frac{1}{2}$	1 $\frac{1}{2}$	SUSP	—	—	B	”	3		
12687	Type 4050	.0005	20	2,000	5,000	2 $\frac{1}{2}$	1 $\frac{1}{2}$	SUSP	—	—	B	”	1		
13012	Type 4181	.001	20	350	700	1 $\frac{1}{2}$	1 $\frac{1}{2}$	SUSP	—	—	B	”	3		
13017	Type 4186	.001	20	350	700	1 $\frac{1}{2}$	1 $\frac{1}{2}$	SUSP	—	—	B	”	5		
12658	Type 4037	.001	20	2,000	5,000	2 $\frac{1}{2}$	1 $\frac{1}{2}$	STUD	—	—	B	”	3		
2891	Type 1383	.001	20	3,000	6,000	3 $\frac{1}{4}$	1 $\frac{1}{2}$	STUD	—	—	B	”	2		
13175	Type 4238	.001	20	5,000	10,000	2 $\frac{1}{2}$	1 $\frac{1}{2}$	SUSP	—	—	B	”	1		
12485	Type 3963	.001	20	5,000	10,000	3 $\frac{1}{4}$	1 $\frac{1}{2}$	STUD	—	—	B	”	2		
14172	Type 4669	.001	20	5,000	10,000	3 $\frac{1}{4}$	1 $\frac{1}{2}$	SUSP	50674	—	B	”	1		

SECTION 10C—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Determ. of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	PAPER DIELECTRIC—cont. Cylindrical—cont.												
2681	Type 1285	.002	20	500	1,000	1 1/8	3/8	SUSP	—	—	B	each	2
12514	Type 3991	.002	20	2,000	5,000	2 1/8	3/8	SUSP	—	—	B	"	3
2678	Type 1282	.003	20	600	1,200	1 1/8	3/8	SUSP	—	—	B	"	3
12486	Type 3964	.003	20	4,000	10,000	2 1/8	3/8	SUSP	—	—	B	"	2
5707	Type 3132	.005	15	3,000	6,000	2 1/8	1/2	SUSP	—	—	B	"	1
2683	Type 1287	.005	20	200	400	1 1/8	3/8	SUSP	—	—	B	"	1
13019	Type 4188	.005	20	350	700	1 1/8	3/8	SUSP	—	—	B	"	2
12539	Type 3998	.005	20	2,000	5,000	2 1/8	3/8	SUSP	—	—	B	"	3
12487	Type 3965	.005	20	4,000	10,000	2 1/8	3/8	SUSP	—	—	B	"	2
12540	Type 3999	.005	20	4,000	10,000	2 1/8	3/8	STUD	—	—	B	"	2
2963	Type 1418	.007	20	750	1,500	3 1/8	1 1/8	SUSP	—	—	B	"	3
2429	Type 1172	.01	10	1,500	3,000	1 1/8	2 1/8	SUSP	—	ZC.1666	B	"	1
3931	Type 2000	.01	15	200	400	3	1 1/8	STUD	—	—	B	"	1
13302	Type 4315	.01	15	300	600	1 1/8	3/8	UPRT	—	—	B	"	2
2722	Type 1325	.01	15	600	1,200	1 1/8	3/8	STUD	—	—	B	"	2
2020	Type 931	.01	15	600	1,200	1 1/8	3/8	SUSP	—	—	B	"	2
2709	Type 1302	.01	15	750	1,500	2	2 1/8	STUD	—	—	B	"	2
535	Type 756	.01	15	1,000	2,000	2 1/8	1 1/8	STUD	—	—	B	"	2
2686	Type 1290	.01	15	2,000	4,000	2 1/8	1 1/8	STUD	—	—	B	"	2
707	Type 805	.01	15	3,000	6,000	3 1/8	1 1/8	STUD	—	ZC.0172	B	"	1
12488	Type 3966	.01	20	1,200	3,000	2 1/8	7/8	SUSP	50663	—	B	"	3
12489	Type 3967	.01	20	1,200	3,000	2 1/8	7/8	SUSP	50685	—	B	"	3
12490	Type 3968	.01	20	4,000	10,000	2 1/8	7/8	STUD	—	—	B	"	3
12492	Type 3970	.01	20	6,000	12,000	2 1/8	1 1/8	STUD	—	—	B	"	1
4637	Type 2428	.02	15	350	700	2 1/8	1 1/8	STUD	—	—	B	"	1
11545	Type 3517	.02	15	2,000	4,000	2 1/8	1 1/8	STUD	—	—	B	"	2
13112	Type 4226	.02	15	5,000	10,000	2 1/8	1 1/8	SUSP	—	—	B	"	2
12493	Type 3971	.02	20	800	2,000	2 1/8	3/8	SUSP	—	—	B	"	2
12494	Type 3972	.02	20	800	2,000	2 1/8	3/8	STUD	—	—	B	"	2
13217	Type 4266	.02	20	3,000	7,500	2 1/8	1	SUSP	—	—	B	"	2

SECTION 100—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13	14
<p>PAPER DIELECTRIC—cont.</p> <p>Cylindrical—cont.</p> <p>Plastic—cont.</p>													
13826	Type 4534	.02	20	5,000	10,000	3 3/8	1 7/8	STUD	—	—	B	each	1
13218	Type 4267	.02	20	5,000	12,000	3 3/4	1 7/8	SUSP	—	—	B	"	1
12541	Type 4000	.02	20	5,000	12,000	3 3/4	1 3/8	STUD	—	—	B	"	2
2439	Type 1185	.03	15	500	1,000	2	1 3/8	SUSP	—	—	B	"	1
12496	Type 3974	.03	20	800	2,000	2 1/8	1 3/8	SUSP	—	—	B	"	3
12498	Type 3976	.03	20	2,500	6,000	3 3/8	1 1/2	STUD	—	—	B	"	2
12497	Type 3975	.03	20	2,500	6,000	2 1/2	1 1/2	SUSP	—	—	B	"	2
3963	Type 2032	.04	5	750	1,500	2 1/2	1 1/2	SUSP	—	—	B	"	2
4619	Type 2410	.05	10	750	1,500	2 1/2	1 1/2	SUSP	—	—	B	"	2
13975	Type 4594	.05	10	15,000	30,000	2 1/2	1 1/2	SUSP	—	—	B	"	1
868	Type 864	.05	15	600	1,200	2	1 1/2	SUSP	—	ZC.0166	B	"	2
2680	Type 1284	.05	15	600	1,200	2 1/2	1 1/2	STUD	—	—	B	"	2
12499	Type 3977	.05	20	800	2,000	2 1/2	1 1/2	SUSP	—	—	B	"	2
12500	Type 3978	.05	20	800	2,000	2 1/2	1 1/2	SUSP	—	—	B	"	2
13219	Type 4268	.05	20	2,000	5,000	2 1/2	1 1/2	STUD	—	—	B	"	3
12543	Type 4002	.05	20	2,000	5,000	3 3/8	1 1/2	STUD	—	—	B	"	2
12501	Type 3979	.05	20	3,500	8,500	3 3/8	1 7/8	SUSP	—	—	B	"	2
13220	Type 4269	.05	20	3,500	8,500	3 3/8	1 7/8	SUSP	—	—	B	"	2
2724	Type 1327	.075	10	350	700	2	1 1/2	SUSP	—	—	B	"	2
12140	Type 3791	.09	15	350	700	3 1/2	1 1/2	STUD	—	—	B	"	2
14396	Type 4745	.1	5	250	500	1 1/2	7/8	SUSP	—	—	B	"	2
3902	Type 1971	.1	10	350	700	2	1 1/2	SUSP	—	ZA.1744	B	"	2
4589	Type 2399	.1	10	500	1,000	2	1 1/2	SUSP	—	ZC.3059	B	"	3
2881	Type 1373	.1	15	300	600	2 1/2	1 1/2	STUD	—	—	B	"	2
2048	Type 953	.1	15	350	700	2 1/2	1 1/2	SUSP	—	—	B	"	3
886	Type 872	.1	15	750	1,500	2 1/2	1 1/2	STUD	—	ZC.1845	B	"	1
13015	Type 4184	.1	20	350	700	2 1/2	1 1/2	SUSP	—	—	B	"	2
13020	Type 4189	.1	20	375	750	3 1/8	1 1/2	STUD	—	—	B	"	1
12502	Type 3980	.1	20	600	1,500	3 1/8	1 1/2	SUSP	—	—	B	"	3
12503	Type 3981	.1	20	1,200	3,000	2 1/2	1 1/2	SUSP	—	ZC.15830	B	"	2

SECTION 10C—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		Test	OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test		Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	
	PAPER DIELECTRIC—cont.													
	Cylindrical—cont.													
	Metal—cont.													
12504	Type 3982	.1	20	1,200	3,000	3 1/4	1 1/4	STUD	—	—	B	"	2	
12505	Type 3983	.1	20	2,500	6,000	3 1/4	1 3/8	STUD	—	—	B	"	2	
13221	Type 4270	.1	20	2,500	6,000	3 3/8	1 3/8	SUSP	—	—	B	"	1	
16087	Type 5361	.1	25	150	250	3 1/8	1 1/8	SUSP	—	—	B	"	2	
16093	Type 5367	.1	25	350	525	1 1/8	1 1/8	SUSP	—	—	B	"	2	
2132	Type 988	.25	15	350	700	2 3/8	1 3/8	STUD	—	—	B	"	2	
552	Type 760	.25	15	350	700	2 7/8	1 3/8	SUSP	—	—	B	"	2	
13010	Type 4179	.25	20	350	700	3 1/8	1 3/8	STUD	—	—	B	"	2	
12507	Type 3985	.25	20	800	2,000	3 1/8	1 3/8	STUD	—	—	B	"	2	
12506	Type 3984	.25	20	800	2,000	3 1/8	1 3/8	SUSP	—	—	B	"	2	
16024	Type 5329	.25	20	1,500	4,500	2 1/8	1 1/8	STUD	50704	—	B	"	3	
16120	Type 5378	.25	20	1,500	4,500	4	1 1/8	SUSP	50681	—	B	"	3	
2578	Type 1223	.5	10	200	400	3 1/8	1 3/8	STUD	—	—	B	"	1	
3862	Type 1951	.5	10	350	700	2 7/8	1 3/8	SUSP	—	—	B	"	2	
13013	Type 4182	.5	20	350	700	3 1/8	1 3/8	STUD	—	—	B	"	2	
13007	Type 4176	.5	20	350	700	3	1 1/8	SUSP	—	—	B	"	2	
13008	Type 4177	.5	20	350	700	3	1 1/8	STUD	—	—	B	"	2	
12508	Type 3986	.5	20	400	1,000	2 7/8	1 1/8	SUSP	—	—	B	"	2	
12509	Type 3987	.5	20	400	1,000	2 7/8	1 1/8	SUSP	—	—	B	"	2	
13558	Type 4434	.5	20	400	2,000	3 1/8	1 1/8	STUD	—	—	B	"	2	
13559	Type 4435	.5	20	800	2,000	3 3/8	1 1/8	SUSP	—	—	B	"	1	
16088	Type 5362	.5	25	150	250	1 3/8	1 1/8	SUSP	—	—	B	"	2	
2346	Type 1135	.75	10	600	1,200	3 1/8	1 3/8	SUSP	—	—	B	"	1	
12511	Type 3989	1	20	400	1,000	3 1/8	1 3/8	STUD	—	—	B	"	2	
12510	Type 3988	1	20	400	1,000	3 1/8	1 3/8	SUSP	—	—	B	"	2	
16141	Type 5399	1	25	150	250	1 3/8	1 1/8	SUSP	—	—	B	"	2	
16144	Type 5402	1	25	250	375	1 3/8	1 1/8	SUSP	—	—	B	"	2	
16089	Type 5363	1	25	350	525	2 1/8	1 1/8	SUSP	—	—	B	"	2	
12512	Type 3990	2	20	160	400	2 3/8	1 3/8	SUSP	—	—	B	"	1	

SECTION 10C—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	PAPER DIELECTRIC—cont. Rectangular:— Less than 1 mfd.:—													
347	Type 668	.01	15	350	1,000	1 1/8	1 1/8	1 1/8	SUSP			B	each	5
5210	Type 2802	.01	15	350	1,000	2 1/8	1 1/8	2 1/8	UPRT			B	"	3
5157	Type 2749	.01	15	2,500	5,000	2 1/8	2 1/8	1	UPRT			B	"	1
686	Type 798	.02	10	6,000	15KV	6 3/4	5 1/4	3	CLMP			B	"	2
14463	Type 4795	.02	20	8,000	15KV	8 1/4	2 1/8	1 1/2	UPRT			B	"	1
12383	Type 3909	.025	+inf. -15	2,500	5,000	3 3/8	2 1/8	1 1/2	UPRT			B	"	1
3989	Type 2045	.025	10	600	1,500	2 3/8	2 1/8	2 1/8	UPRT			B	"	1
15784	Type —	.05	10	1,000	2,000	3 3/8	3	2 3/8	UPRT			B	"	3
13917	Type 4573	.05	10	2,000	4,000	5 1/2	2 3/8	2 3/8	UPRT		ZC.1667	B	"	1
2101	Type 980	.05	10	4,000	8,000	3 3/8	2 3/8	1 1/2	SIDE			B	"	2
5471	Type 2972	.05	10	7,000	17.5 KV	8 3/4	6 1/2	3	CLMP			B	"	1
5950	Type 3260	.05	15	2,000	4,000	3 1/8	3 3/4	1 1/8	INVT			B	"	1
4528	Type 2341	.05	20	2,000	5,000	2 3/4	3 3/4	1	SIDE			B	"	1
11013	Type 3322	.07	5	250	500	2 1/8	2 1/8	1 1/8	UPRT			B	"	1
3211	Type 1565	.06	15	250	500	2 1/8	2 1/8	1 1/8	UPRT			B	"	1
11292	Type 436	.1	10	250	500	1 1/8	1 1/4	1 1/8	CLMP			B	"	2
468	Type 717	.1	10	250	500	1 1/8	2 1/8	1 1/8	UPRT			B	"	2
13861	Type 4549	.1	10	250	500	3 1/8	1 1/2	1 1/8	UPRT			B	"	2
4534	Type 2347	.1	10	300	600	1 3/8	2 1/8	1 1/8	UPRT			B	"	1
10649	Type 447	.1	10	400	800	1 3/8	2 1/8	1 1/8	INVT			B	"	1
11005	Type 3314	.1	10	500	1,000	2 1/8	2 3/8	1 1/8	UPRT			B	"	3
333	Type 662	.1	10	500	1,000	2 1/8	2 3/8	1 1/8	UPRT			B	"	1
4786	Type 2518	.1	10	500	1,000	2 1/8	2 3/8	1 1/8	UPRT			B	"	2
533	Type 754	.1	10	550	1,100	3 1/8	2 3/8	1 1/8	INVT			B	"	2
10826	Type 485	.1	10	750	2,000	3 1/8	3	3	UPRT			B	"	1
5159	Type 2751	.1	10	900	1,800	3	2 3/8	1	UPRT			B	"	2
2175	Type 1022	.1	10	1,000	2,000	2 3/4	2 3/8	1 1/8	UPRT		ZC.0504	B	"	1
706	Type 804	.1	10	1,000	2,000	2 1/8	2 3/4	1 1/8	INVT			B	"	1
5145	Type 2737	.1	10	1,500	4,000	3 1/8	3 1/8	1 1/8	UPRT			B	"	1

SECTION 100—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1														
	PAPER DIELECTRIC—cont. Rectangular—cont. Less than 1 mfd.—cont.													
2177	Type 1024	.1	10	2,000	4,000	2 3/8	2 3/8	1 1/8	UPRT		ZC.0505	B	each	2
697	Type 801	.1	10	2,000	4,000	3 1/8	2 3/8	1 1/8	INVT			B	"	1
3499	Type 1725	.1	10	2,000	5,000	4 1/8	4 1/8	1 1/8	UPRT		ZC.1542	B	"	1
938	Type 883	.1	10	3,000	6,000	6 7/8	2 1/2	2	CLMP			B	"	1
939	Type 884	.1	10	4,000	8,000	6 7/8	2 1/2	2	CLMP			B	"	1
4213	Type 2169	.1	10	5,000	10KV	7 1/2	3 1/2	3 1/8	CLMP			B	"	1
5185	Type 2777	.1	10--20	750	2,000	3 1/8	3	3 3/8	UPRT			B	"	1
10833	Type 508	.1	15	400	1,000	2 5/8	2 3/8	2 3/8	UPRT			B	"	2
13449	Type 4388	.1	15	500	1,250	2 5/8	2 3/8	2 3/8	UPRT			B	"	1
15708	Type —	.1	15	1,000	1,000	2 5/8	2 3/8	2 3/8	UPRT			B	"	1
11899	Type 3653	.1	15	1,000	2,000	2 5/8	2 3/8	2 3/8	UPRT			B	"	1
2248	Type 1066	.1	15	1,000	2,000	2 5/8	2 3/8	2 3/8	UPRT			B	"	1
11290	Type 3454	.1	15	5,000	12KV	3	2 3/8	2 3/8	UPRT			B	"	1
12761	Type 4065	.1	15	7,500	15KV	3 1/8	4 1/8	3 3/8	INVT			B	"	1
13316	Type 4326	.1	20	1,200	2,500	2 7/8	2 3/8	2 3/8	STRP			B	"	1
14543	Type 4838	.1	20	1,500	3,000	3 1/8	2 3/8	2 3/8	INVT			B	"	1
16073	Type 5353	.1	20	15KV	30KV	3 1/8	2 3/8	2 3/8	UPRT			B	"	3
13707	Type 4491	.1	20	2,000	4,000	4	4 1/8	3 1/8	UPRT			B	"	1
13905	Type 4566	.1	20	2,000	4,000	4	4 1/8	3 1/8	UPRT			B	"	1
14462	Type 4794	.1	20	3,000	6,000	4	4 1/8	3 1/8	UPRT			B	"	1
13262	Type 4282	.1	20	3,000	6,000	4 1/8	4 1/8	3 1/8	UPRT			B	"	1
13855	Type 4545	.1	20	4,000	8,000	4	4 1/8	3 1/8	UPRT			B	"	1
2192	Type 1036	.1	25	4,000	8,000	4 1/8	4 1/8	3 1/8	UPRT		ZC.10476	B	"	1
5764	Type 3151	.1	+inf.-15	3,000	6,000	3 7/8	2 3/8	2 1/8	UPRT			B	"	2
5762	Type 3149	.1	+inf.-15	4,000	8,000	3 7/8	2 3/8	2 1/8	UPRT			B	"	1
10297	Type 389	.2	10	350	700	1 7/8	2	1 1/2	CLMP			B	"	2
2620	Type 1244	.2	10	600	1,250	1 1/8	2 1/8	1 1/8	UPRT			B	"	1
13691	Type 4489	.2	10	250	500	1 1/8	2 1/8	1 1/8	UPRT			B	"	1
13860	Type 4548	.25	10	250	500	3 1/8	2 1/8	1 1/8	UPRT			B	"	1
14256	Type 4705	.25	10	250	500	2 1/8	2 1/8	1 1/8	UPRT			B	"	1

SECTION 10C—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		Test	OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test		Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
	PAPER DIELECTRIC—cont. Rectangular—cont. Less than 1 mfd.—cont.														
2290	Type 1093	.25	10	250	500	3 ⁵ / ₁₆	2 ¹ / ₈	3 ¹ / ₈	UPRT	—	—	B	each	1	
11394	Type 524	.25	10	350	700	1 ¹ / ₁₆	2 ¹ / ₈	2 ¹ / ₈	CLMP	—	—	B	”	2	
3729	Type 1904	.25	10	400	800	2 ¹ / ₄	2 ³ / ₈	1	UPRT	—	—	B	”	2	
5891	Type 3239	.25	10	500	1,000	3	2 ³ / ₈	2 ¹ / ₈	UPRT	—	—	B	”	1	
2436	Type 1182	.25	10	750	2,000	2 ¹ / ₈	2 ² / ₈	3	INVT	—	—	B	”	2	
3509	Type 1735	.25	10	750	2,000	3 ¹ / ₁₆	3	3	UPRT	—	ZA.22001	B	”	2	
2040	Type 945	.25	10	1,000	3,000	3 ¹ / ₁₆	3	3	UPRT	—	—	B	”	5	
5711	Type 3136	.25	10	1,500	3,000	3 ¹ / ₁₆	3	3	UPRT	—	—	B	”	1	
11205	Type 3408	.25	10	2,000	5,000	4 ¹ / ₁₆	4 ¹ / ₈	2 ¹ / ₈	UPRT	—	—	B	”	1	
12708	Type 4063	.25	10	3,000	6,000	4 ¹ / ₁₆	3 ³ / ₈	1 ¹ / ₂	SIDE	—	—	B	”	1	
11214	Type 3417	.25	10	3,000	6,000	4 ¹ / ₁₆	3 ³ / ₈	2 ¹ / ₈	UPRT	—	—	B	”	1	
2351	Type 1140	.25	10	4,000	8,000	6 ¹ / ₁₆	3	3	UPRT	—	—	B	”	1	
2174	Type 1021	.25	10	4,000	8,000	6 ¹ / ₁₆	3	1 ¹ / ₂	UPRT	—	—	B	”	1	
3490	Type 1723	.25	10	4,000	8,000	8 ¹ / ₈	4 ³ / ₈	3 ¹ / ₈	UPRT	—	ZC.1540	B	”	1	
4884	Type 2576	.25	10	5,000	10KV	8 ¹ / ₈	4 ³ / ₈	3 ¹ / ₈	UPRT	—	—	B	”	1	
16187	Type 5435	.25	10	7,500	15KV	6	9 ¹ / ₈	11 ¹ / ₁₆	NONE	—	—	B	”	1	
4533	Type 2346	.25	15	300	600	3 ¹ / ₁₆	2 ¹ / ₁₆	3 ¹ / ₈	INVT	—	—	B	”	1	
15740	Type —	.25	15	1,500	4,000	3 ¹ / ₁₆	3 ¹ / ₈	1 ¹ / ₁₆	UPRT	W.2565	—	B	”	1	
11728	Type 3566	.25	15	1,500	4,000	3 ¹ / ₁₆	3 ¹ / ₈	1 ¹ / ₁₆	UPRT	—	—	B	”	2	
15707	Type —	.25	15	2,000	4,000	3 ¹ / ₁₆	3 ¹ / ₈	1 ¹ / ₁₆	UPRT	W.7817	—	B	”	1	
11900	Type 3654	.25	15	2,000	4,000	3 ¹ / ₁₆	3 ¹ / ₈	1 ¹ / ₁₆	UPRT	—	—	B	”	1	
14329	Type 4719	.25	15	2,000	5,000	3 ¹ / ₁₆	3 ¹ / ₈	1 ¹ / ₁₆	UPRT	—	—	B	”	1	
13648	Type 4474	.25	20	9,000	18KV	8 ¹ / ₈	7 ¹ / ₈	3 ¹ / ₈	UPRT	—	—	B	”	1	
13223	Type 4272	.25	20	250	750	2 ⁵ / ₈	2 ² / ₈	2 ² / ₈	UPRT	—	—	B	”	2	
12619	Type 4026	.25	20	400	800	3 ¹ / ₁₆	2 ² / ₈	2 ² / ₈	UPRT	—	—	B	”	1	
13272	Type 4289	.25	20	750	1,500	3 ¹ / ₁₆	2 ² / ₈	2 ² / ₈	UPRT	—	—	B	”	1	
13961	Type 4586	.25	20	1,000	3,000	3 ¹ / ₁₆	3 ¹ / ₈	1	UPRT	—	—	B	”	1	
13576	Type 4442	.25	20	1,500	3,000	4 ¹ / ₁₆	4 ¹ / ₈	1 ¹ / ₄	UPRT	—	—	B	”	1	
13971	Type 4590	.25	20	2,000	5,000	6 ¹ / ₁₆	4 ¹ / ₈	2 ¹ / ₈	UPRT	—	—	B	”	1	
13673	Type 4481	.25	20	3,000	6,000	6 ¹ / ₁₆	4 ¹ / ₈	2 ¹ / ₈	UPRT	—	—	B	”	1	
				4,000	8,000			3	UPRT	—	—				

SECTION 100—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (INS.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	?	3	4	5	6	7	8	9	10	11	12	13	14	15
	PAPER DIELECTRIC—cont. Rectangular—cont. Less than 1 mfd.—cont.													
13990	Type 4598	.25	20	4,000	10KV	8 1/4	4 1/4	3 1/4	UPRT			B	each	1
14158	Type 4665	.25	20	6,000	12KV	8 1/4	5 1/4	3	UPRT			B	"	1
14433	Type 4771	.25	20	10KV	20KV	7 1/4	7 1/4	5	UPRT			B	"	1
15709	Type —	.25	+20-10	2,750	10KV	8 1/4	4 3/4	3	UPRT			B	"	1
15737	Type —	.25	+20-10	2,750	10KV	8 1/4	4 3/4	3	UPRT			B	"	1
5217	Type 2809	.25	+mf.-15	450	1,000	2 3/4	2 1/4	1	UPRT			B	"	2
11940	Type 3682	.25	+mf.-15	450	1,500	2 3/4	2 1/4	1	UPRT			B	"	2
5440	Type 2942	.25	+mf.-15	1,500	3,000	2 3/4	2 1/4	1	UPRT			B	"	2
5216	Type 2808	.25	+mf.-15	2,000	4,000	2 3/4	2 1/4	1	UPRT			B	"	1
11859	Type 3643	.25	+mf.-15	2,000	4,000	2 3/4	2 1/4	1	UPRT			B	"	1
16159	Type 5413	.25	+mf.-15	250	500	5 1/4	4 1/4	2	UPRT			B	"	2
14203	Type 4684	.25	+mf.-15	4,000	8,000	2 3/4	2 1/4	1	UPRT			B	"	1
7593	Type 85	.5	5	1,000	2,000	2 3/4	2 1/4	1	UPRT			B	"	2
437	Type 705	.5	10	150	300	2 3/4	1 7/8	1	CLMP			B	"	1
2447	Type 1188	.5	10	250	500	2 3/4	2 1/4	1	UPRT			B	"	3
10342	Type 392	.5	10	250	500	2 3/4	2 1/4	1	UPRT		ZA.20307	B	"	3
434	Type 702	.5	10	350	700	2 3/4	2 1/4	1	UPRT			B	"	2
4930	Type 2620	.5	10	350	700	2 3/4	2 1/4	1	UPRT			B	"	3
2176	Type 1023	.5	10	350	700	2 3/4	2 1/4	1	UPRT		ZC.0506	B	"	1
4532	Type 2345	.5	10	350	700	2 3/4	2 1/4	1	UPRT		ZC.1543	B	"	2
3127	Type 1523	.5	10	400	800	2 3/4	2 1/4	1	UPRT			B	"	2
10801	Type 477	.5	10	400	1,000	2 3/4	2 1/4	1	UPRT			B	"	2
15738	Type —	.5	10	450	1,300	2 3/4	2 1/4	1	UPRT		YB.03298	B	"	1
561	Type 763	.5	10	550	1,100	2 3/4	2 1/4	1	INVT			B	"	2
2688	Type 1292	.5	10	1,000	2,000	2 3/4	2 1/4	1	UPRT			B	"	2
4214	Type 2170	.5	10	1,500	4,000	2 3/4	2 1/4	1	UPRT			B	"	1
9012	Type 257	.5	10	2,000	4,000	2 3/4	2 1/4	1	UPRT			B	"	1
4683	Type 2454	.5	10	2,000	5,000	2 3/4	2 1/4	1	UPRT			B	"	1
4805	Type 2536	.5	10	2,500	6,000	2 3/4	2 1/4	1	UPRT			B	"	1
3718	Type 1893	.5	15	250	500	6 1/4	3 1/4	1	UPRT			B	"	2

SECTION 10C—cont.

FIXED CONDENSERS

NOTE 3 B. 4

1	2	3	4	5		6	7			8	9	10	11	12	13	14	15
				Working	Test		Height	Width	Depth								
4570	PAPER DIELECTRIC—cont. Rectangular—cont. Less than 1 mfd.—cont.	.5	15	400	800	3 1/2	2 1/4	3 1/2	INVT UPRT	—	—	B	each	1			
13446	Type 2380	.5	15	500	1,250	2 1/2	2 1/4	1	UPRT	—	—	B	"	1			
9675	Type 4385	.5	15	1,500	3,000	3 1/2	3 3/8	3 1/2	UPRT	—	—	B	"	1			
13979	Type 533	.5	20	200	400	3 1/2	3 3/8	3 1/2	UPRT	—	—	B	"	1			
11543	Type 4595	.5	20	250	700	3 1/2	2 1/4	3 3/8	UPRT	50804	—	B	"	1			
12662	Type 3515	.5	20	400	1,000	3 1/2	2 1/4	3 3/8	UPRT	—	—	B	"	1			
14544	Type 4040	.5	20	500	1,000	3 1/2	2 1/4	3 3/8	UPRT	—	—	B	"	1			
13095	Type 4839	.5	20	600	1,200	3 1/2	2 1/4	3 3/8	UPRT	—	—	B	"	1			
13762	Type 4224	.5	20	750	1,500	3 1/2	2 1/4	3 3/8	UPRT	—	—	B	"	1			
16090	Type 4506	.5	20	800	2,000	3 3/8	2 1/4	3 3/8	UPRT	50839	—	B	"	1			
14994	Type 5364	.5	20	800	2,000	3 3/8	2 1/4	3 3/8	UPRT	—	—	B	"	1			
12635	Type 5067	.5	20	800	2,000	3 3/8	2 1/4	3 3/8	UPRT	50814	—	B	"	2			
14545	Type 4030	.5	20	800	2,000	3 3/8	2 1/4	3 3/8	UPRT	—	—	B	"	1			
16074	Type 4840	.5	20	1,000	2,500	3 1/2	2 1/4	3 3/8	UPRT	50085	—	B	"	1			
12524	Type 5354	.5	20	1,200	3,000	5 1/2	4 1/8	1 3/8	UPRT	—	ZA.29012	B	"	1			
13633	Type 3992	.5	20	2,000	4,000	8 1/2	7 1/8	1 3/8	UPRT	—	—	B	"	1			
9181	Type 4465	.5	20	7,000	14KV	1 1/2	1 1/8	1 3/8	UPRT	—	—	B	"	1			
15046	Type 282	.5	+20-10	250	500	1 1/2	2 1/8	1 1/8	UPRT	—	—	B	"	1			
15047	Type 5087	.5	+20-20	250	700	3 1/2	2 1/8	1 1/8	UPRT	—	—	B	"	1			
2635	Type 5088	.5	+20-20	400	1,000	3 1/2	2 1/8	1 1/8	UPRT	—	—	B	"	2			
5215	Type 1257	.5	+25-10	450	900	3 1/2	3	1 1/8	UPRT	—	—	B	"	2			
12448	Type 2807	.75	+25-10	450	900	2 1/2	2 1/8	1 1/8	UPRT	—	—	B	"	1			
13552	Type 3946	.75	10	450	900	5 1/8	3 1/2	1 1/8	UPRT	—	—	B	"	1			
5245	Type 4429	.75	10	450	900	5 1/8	3 1/2	1 1/8	UPRT	—	—	B	"	1			
1805	Type 2837	.75	15	400	800	5 1/8	3 1/2	1 1/8	UPRT	—	—	B	"	1			
2885	1 mfd. and upwards— Type 45	1	10	150	300	1 1/2	4 1/8	1 1/8	UPRT	—	—	B	"	1			
5597	Type 1377	1	10	150	300	3 1/4	2 1/8	1 1/8	UPRT	—	—	B	"	1			
14248	Type 3060	1	10	250	500	2 1/8	2 1/8	1 1/8	UPRT	—	ZA.0799	B	"	1			
10823	Type 4700	1	10	250	500	3 1/8	2 1/8	1 1/8	UPRT	—	ZA.0912	B	"	1			
	Type 482	1	10	250	500	3	2 1/8	1 1/8	UPRT	—	—	B	"	2			

SECTION 10C—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
<p>PAPER DIELECTRIC—cont. Rectangular—cont. 1 mfd. and upwards—cont.</p>														
13972	Type 4591	1	10	250	500	3 1/4	2	1 1/8	UPRT	—	—	B	each	1
4531	Type 2344	1	10	350	700	3 1/4	2 1/8	1 1/8	INVT	—	—	B	"	1
16881	Type 5996	1	10	350	1,000	3 1/4	3	1 1/8	UPRT	—	—	B	"	—
4905	Type 2597	1	10	400	800	3 1/8	2 3/4	1 1/8	UPRT	—	ZA.1754	B	"	2
5158	Type 2750	1	10	350	700	3 1/8	2 3/8	1 1/8	UPRT	—	—	B	"	2
2189	Type 1033	1	10	400	1,000	3 1/8	2 3/4	1 1/8	INVT	—	ZC.10391	B	"	2
2448	Type 1189	1	10	400	1,000	3 1/8	2 3/4	1 1/8	UPRT	—	ZC.3275	B	"	3
2969	Type 1424	1	10	450	1,000	5 1/8	2	3/4	UPRT	—	ZC.0165	B	"	2
2119	Type 985	1	10	450	1,000	2 1/4	2 1/4	1 1/8	UPRT	—	YB.1922	B	"	2
10937	Type 431	1	10	450	1,000	2 1/4	2 1/4	1 1/8	UPRT	—	—	B	"	2
5639	Type 3064	1	10	500	1,000	3 1/8	2 3/4	1 1/8	UPRT	—	ZA.1494	B	"	2
655	Type 786	1	10	500	1,000	3 1/8	2 3/4	1 1/8	INVT	—	—	B	"	2
2687	Type 1291	1	10	600	1,200	3 1/8	2 3/4	1 1/8	INVT	—	—	B	"	1
2922	Type 1399	1	10	750	2,000	3 1/8	3	1 1/8	UPRT	—	—	B	"	1
3123	Type 1518	1	10	1,000	2,000	3 1/8	3 1/4	1 1/8	UPRT	—	—	B	"	1
5480	Type 2981	1	10	1,000	3,000	5 1/8	3 1/4	1 1/8	INVT	—	—	B	"	1
5524	Type 2987	1	10	1,500	3,000	6 1/8	2 1/4	2 1/4	SIDE	—	—	B	"	1
9011	Type 256	1	10	2,000	4,000	9 1/8	4 1/4	2 1/4	UPRT	—	—	B	"	1
4044	Type 2096	1	10	2,000	5,000	6 1/8	4 1/4	2 1/4	UPRT	—	—	B	"	1
3900	Type 1969	1	10	2,500	6,000	6 1/8	4 1/4	2 1/4	UPRT	—	—	B	"	1
3049	Type 1459	1	10	5,000	10KV	6	3 1/2	3	CLMP	—	—	B	"	1
15710	Type —	1	15	200	600	2 1/2	8	1 1/8	UPRT	—	ZC.0151	B	"	2
4572	Type 2382	1	15	250	500	3	1 1/8	3/8	UPRT	W.7436	YA.2373	B	"	1
5244	Type 2836	1	15	400	800	5 7/8	2 1/2	3/8	UPRT	—	ZA.17540	B	"	1
2813	Type 1316	1	15	450	1,000	4 1/8	2 1/8	1 1/8	UPRT	—	—	B	"	2
5591	Type 3054	1	15	700	1,400	4 1/8	2 1/8	1 1/8	INVT	—	—	B	"	1
11727	Type 3565	1	15	750	1,500	3 1/8	3	1 1/8	UPRT	—	—	B	"	2
2810	Type 1313	1	15	800	1,600	4 1/8	3	1 1/8	UPRT	—	—	B	"	1
801	Type 852	1	15	1,000	2,000	4 1/8	2 1/4	1 1/8	UPRT	—	—	B	"	1
469	Type 718	1	15	1,000	2,000	3 1/2	3 1/2	1 1/8	UPRT	—	—	B	"	1

SECTION 100—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Qty. Units
				Working	Test	Height	Width	Depth						
1	PAPER DIELECTRIC—cont. Rectangular—cont. 1 mfd. and upwards—cont.													
5796	Type 3183	1	15	1,000	3,000	2 7/8	2 3/4	1 1/2	UPRT	—	—	B	each	1
14568	Type 4854	1	15	5,000	10KV	6	10	4 1/2	UPRT	—	—	B	"	1
14004	Type 4607	1	20	200	400	2 1/2	1 3/8	3/8	UPRT	—	—	B	"	1
14889	Type 5008	1	20	250	700	3 1/8	2 1/2	3/8	UPRT	50826	ZA.26570	B	"	1
11189	Type 3392	1	20	250	500	2 1/8	2 9/16	3/8	INVT	—	—	B	"	1
12660	Type 4039	1	20	350	700	2 1/8	2 3/8	1	INVT	—	—	B	"	2
12682	Type 4045	1	20	350	700	3 1/8	2 3/8	1	UPRT	—	—	B	"	2
9097	Type 316	1	20	400	800	3 1/8	2 3/4	3/8	INVT	—	ZC/PY. 67151	B	"	2
13263	Type 4283	1	20	400	800	3 1/8	2 3/4	3/8	UPRT	50805	—	B	"	1
15048	Type 5089	1	20	400	1,000	3 1/8	2 3/4	3/8	INVT	—	ZC.23398	B	"	1
15955	Type 5304	1	20	400	1,000	3 1/8	2 3/4	3/8	UPRT	50831	ZA.26506	B	"	3
13058	Type 4202	1	20	400	1,000	2 7/8	2 3/8	1	UPRT	—	—	B	"	1
13736	Type 4503	1	20	400	400	3	2 3/8	1 1/8	INVT	—	—	B	"	1
12634	Type 4029	1	20	400	1,000	3	2 3/8	1 1/8	UPRT	50809	—	B	"	1
13047	Type 4196	1	20	600	600	3	2 3/8	1 1/8	INVT	—	—	B	"	1
12775	Type 4078	1	20	600	1,200	3 1/8	2 3/8	1 1/8	UPRT	—	—	B	"	1
12567	Type 4012	1	20	600	1,500	3 1/8	2 3/8	1 1/8	INVT	—	—	B	"	1
4865	Type 2557	1	20	750	1,500	3 1/8	3	1 1/8	UPRT	—	—	B	"	2
16239	Type 5470	1	20	800	2,000	3	2 3/8	1 1/8	UPRT	50840	ZC.23294	B	"	3
13553	Type 4430	1	20	1,000	3,000	3 1/8	3 1/8	1 1/8	INVT	—	—	B	"	1
14461	Type 4793	1	20	1,500	3,000	5 7/16	3 1/8	1 1/8	UPRT	—	—	B	"	1
13274	Type 4291	1	20	1,500	3,000	5 7/16	3 3/8	1 1/8	UPRT	—	—	B	"	1
13178	Type 4240	1	20	2,000	4,000	5 7/16	3 3/8	1 1/8	UPRT	—	—	B	"	1
5337	Type 2887	1	+inf.-15	500	1,000	3 1/8	2 3/4	1 1/8	UPRT	—	—	B	"	1
5183	Type 2775	1	+10-20	750	2,000	3 1/8	3	1 1/8	UPRT	—	—	B	"	1
2400	Type 1150	1	10	250	500	9 1/4	4 1/8	1 3/8	CLAMP	—	—	B	"	1
10920	Type 428	1	10	4,000	10KV	9 1/4	4 1/8	1 3/8	CLAMP	—	—	B	"	2
13983	Type 4596	1	+20-10	1,200	2,400	5 1/2	2 3/8	1 1/8	INVT	—	—	B	"	1
4617	Type 2408	1	+40-15	250	500	5 1/2	4 1/8	1 1/8	SIDE	—	—	B	"	1

SECTION 100—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity ind.	Tolerance ± %	VOLTAGE		Test	OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Demom. of Qty.	Carton Unit Qty.
				Working	Test		Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
PAPER DIELECTRIC—cont.															
Rectangular—cont.															
1 mid. and upwards—cont.															
7391	Type 74	2	10	150	300	$2\frac{3}{4}$	2	1	CLMP	—	—	B	each	1	
8275	Type 164	2	10	150	300	$3\frac{1}{8}$	$2\frac{3}{4}$	1	UPRT	—	—	B	"	2	
3464	Type 1711	2	10	200	400	$2\frac{5}{8}$	$2\frac{3}{4}$	$1\frac{1}{2}$	UPRT	—	—	B	"	2	
2170	Type 1017	2	10	200	400	$2\frac{1}{2}$	$2\frac{1}{8}$	1	UPRT	ZC.0593	—	B	"	2	
2220	Type 1031	2	10	250	500	$2\frac{3}{8}$	$2\frac{1}{2}$	$1\frac{1}{2}$	UPRT	—	—	B	"	2	
15967	Type 5310	2	10	250	500	$3\frac{1}{8}$	$1\frac{1}{2}$	1	UPRT	—	—	B	"	1	
10343	Type 393	2	10	250	500	$2\frac{5}{8}$	$2\frac{1}{2}$	1	UPRT	—	—	B	"	2	
50	Type 590	2	10	250	500	$2\frac{3}{4}$	$2\frac{1}{2}$	1	UPRT	—	—	B	"	2	
380	Type 685	2	10	250	500	$2\frac{3}{4}$	$2\frac{1}{2}$	1	UPRT	—	—	B	"	2	
4341	Type 2246	2	10	250	500	$3\frac{1}{8}$	$2\frac{1}{2}$	1	UPRT	ZC.8442	—	B	"	2	
9382	Type 307	2	10	250	500	$3\frac{1}{8}$	$2\frac{1}{2}$	1	UPRT	—	—	B	"	2	
288	Type 652	2	10	250	500	$3\frac{1}{8}$	$2\frac{1}{2}$	1	UPRT	—	—	B	"	2	
5892	Type 3240	2	10	250	500	$3\frac{1}{8}$	$2\frac{1}{2}$	1	UPRT	—	—	B	"	2	
3277	Type 1591	2	10	250	500	$3\frac{1}{8}$	$1\frac{1}{2}$	1	UPRT	—	—	B	"	1	
13969	Type 4588	2	10	250	500	$3\frac{1}{8}$	2	1	UPRT	—	—	B	"	1	
11722	Type 557	2	10	250	500	$2\frac{3}{4}$	$4\frac{1}{8}$	1	CLMP	—	—	B	"	2	
10509	Type 376	2	10	300	600	$2\frac{5}{8}$	3	1	UPRT	—	—	B	"	3	
466	Type 715	2	10	350	700	$3\frac{1}{8}$	$2\frac{3}{4}$	1	UPRT	—	—	B	"	2	
12681	Type 4044	2	10	350	700	$3\frac{1}{8}$	$2\frac{3}{4}$	1	UPRT	—	—	B	"	2	
4904	Type 2596	2	10	350	700	$3\frac{1}{8}$	$2\frac{3}{4}$	1	UPRT	—	—	B	"	1	
560	Type 762	2	10	350	700	$3\frac{1}{8}$	$2\frac{3}{4}$	1	INVT	—	—	B	"	1	
5042	Type 2712	2	10	350	700	$4\frac{1}{8}$	$2\frac{3}{4}$	1	UPRT	—	—	B	"	1	
4977	Type 2667	2	10	350	800	$2\frac{5}{8}$	$2\frac{3}{4}$	1	UPRT	—	—	B	"	1	
2193	Type 1037	2	10	400	800	$3\frac{1}{8}$	3	1	UPRT	—	—	B	"	1	
12003	Type 3715	2	10	400	800	$3\frac{1}{8}$	3	1	UPRT	—	—	B	"	1	
4029	Type 2081	2	10	400	800	$3\frac{1}{8}$	3	1	INVT	—	—	B	"	2	
11958	Type 3695	2	10	400	800	$3\frac{1}{8}$	3	1	UPRT	—	—	B	"	1	
2970	Type 1425	2	10	450	900	$5\frac{1}{8}$	8	1	CLMP	ZC.01070	—	B	"	2	
2190	Type 1034	2	10	400	900	$3\frac{1}{8}$	3	1	INVT	ZC.10350	—	B	"	2	
3863	Type 1952	2	10	500	1,000	$3\frac{1}{8}$	2	1	CLMP	—	—	B	"	1	

SECTION 100—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	PAPER DIELECTRIC—cont. Rectangular—cont. 1 mfd. and upwards—cont.													
10822	Type 481	2	10	500	1,000	3 $\frac{1}{8}$	3	2	UPRT	—	ZC.1532	B	each	2
10546	Type 419	2	10	750	2,000	5 $\frac{7}{16}$	3	1 $\frac{1}{2}$	UPRT	—	ZC.0533	B	"	2
3459	Type 1708	2	10	1,000	2,000	3 $\frac{1}{4}$	3	2 $\frac{1}{2}$	UPRT	—	—	B	"	1
3069	Type 1479	2	10	1,000	3,000	5 $\frac{7}{16}$	4	1 $\frac{1}{4}$	UPRT	—	ZC.1529	B	"	1
3512	Type 1738	2	10	2,000	5,000	6 $\frac{7}{16}$	3 $\frac{1}{2}$	6	UPRT	—	—	B	"	1
2325	Type 1115	2	10	2,000	6,000	5 $\frac{7}{8}$	4 $\frac{1}{2}$	3	UPRT	—	—	B	"	1
3050	Type 1460	2	10	2,500	5,000	6	4	4	CLMP	—	—	B	"	1
3462	Type 1709	2	10	4,000	8,000	6 $\frac{1}{2}$	4	4 $\frac{5}{8}$	UPRT	—	—	B	"	3
3610	Type 1817	2	10	6,000	12KV	8 $\frac{3}{8}$	4 $\frac{1}{2}$	2 $\frac{3}{4}$	UPRT	—	—	B	"	2
13913	Type 4570	2	10	12KV	24KV	16	4 $\frac{1}{2}$	15 $\frac{1}{16}$	UPRT	—	—	B	"	1
14026	Type 4613	2	+10-20	1,500	3,000	5 $\frac{7}{16}$	3 $\frac{1}{2}$	14 $\frac{3}{4}$	UPRT	—	—	B	"	1
2239	Type 1057	2	15	100	300	2 $\frac{1}{8}$	2 $\frac{1}{2}$	1	UPRT	—	—	B	"	—
11268	Type 3433	2	15	250	500	3	2 $\frac{1}{2}$	1	UPRT	W.2797	—	B	"	—
2792	Type 1334	2	15	250	500	3	2 $\frac{1}{2}$	1	UPRT	—	—	B	"	2
11493	Type 3504	2	15	250	500	2 $\frac{3}{8}$	2 $\frac{1}{2}$	1	INVT	—	—	B	"	1
4568	Type 2378	2	15	250	500	3	2 $\frac{1}{2}$	1	INVT	—	—	B	"	1
5533	Type 2996	2	15	250	500	3 $\frac{1}{8}$	2 $\frac{1}{2}$	1	INVT	—	—	B	"	1
2257	Type 1072	2	15	350	700	2 $\frac{3}{4}$	2 $\frac{1}{2}$	1	UPRT	—	—	B	"	2
4510	Type 2336	2	15	400	800	3 $\frac{3}{8}$	2	1 $\frac{1}{8}$	SIDE	—	—	B	"	2
4418	Type 2284	2	15	400	800	5 $\frac{1}{4}$	2 $\frac{1}{2}$	1 $\frac{7}{8}$	UPRT	—	—	B	"	2
10885	Type 498	2	15	400	1,000	3 $\frac{1}{2}$	3	1 $\frac{1}{2}$	UPRT	W.2792	ZC/PV. 67154	B	"	2
11494	Type 3505	2	15	400	1,000	2 $\frac{3}{8}$	3	1 $\frac{1}{2}$	INVT	—	—	B	"	1
15788	Type —	2	15	500	1,000	2 $\frac{5}{8}$	2	2	CLMP	—	ZC.15409	B	"	2
13447	Type 4386	2	15	500	1,000	2 $\frac{3}{4}$	2	1	UPRT	—	—	B	"	1
467	Type 716	2	15	500	1,000	3 $\frac{1}{8}$	3	1	UPRT	—	—	B	"	1
5566	Type 3029	2	15	500	1,000	5 $\frac{5}{8}$	2 $\frac{1}{2}$	1 $\frac{1}{2}$	INVT	—	—	B	"	1
12655	Type 4035	2	15	700	1,400	4 $\frac{3}{8}$	2 $\frac{1}{2}$	1 $\frac{1}{8}$	INVT	—	—	B	"	1
9997	Type 534	2	15	750	1,300	3 $\frac{1}{8}$	3 $\frac{3}{8}$	7 $\frac{1}{8}$	UPRT	—	—	B	"	1
2322	Type 1112	2	15	800	1,600	5 $\frac{1}{4}$	3 $\frac{1}{2}$	1 $\frac{1}{2}$	UPRT	—	—	B	"	1

SECTION 10C—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (INS.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	PAPER DIELECTRIC—cont. Rectangular—cont. 1 mid. and upwards—cont.													
5338	Type 2888	2	15	1,000	2,000	5 1/16	3 3/16	1 1/8	UPRT	W.5610	—	B	each	1
13557	Type 4433	2	15	2,000	4,000	5 7/16	3 3/16	2 3/8	UPRT	—	—	B	"	1
13763	Type 4507	2	15	2,000	4,000	5 7/16	4 1/8	2 3/8	UPRT	50098	—	B	"	1
15004	Type 5071	2	15	3,000	8,000	6 1/16	7 7/16	2 4/8	UPRT	W.6455	—	B	"	1
13761	Type 4505	2	20	250	500	3	2 1/4	1 1/8	INVT	—	—	B	"	1
13059	Type 4203	2	20	250	500	3	2 1/4	1 1/8	UPRT	—	—	B	"	1
11544	Type 3516	2	20	250	700	3	2 1/4	1 1/8	UPRT	—	—	B	"	1
12659	Type 4038	2	20	350	700	3 3/8	3 3/8	1 1/8	INVT	—	—	B	"	1
5799	Type 3186	2	20	400	800	3 3/8	3 27/8	1 1/8	UPRT	—	—	B	"	1
15799	Type —	2	20	400	1,000	3	2 1/4	1 1/8	UPRT	50832	—	B	"	1
16297	Type 5500	2	20	400	400	3	2 1/4	1 1/8	UPRT	—	—	B	"	1
13307	Type 4320	2	20	450	900	2 1/8	2 1/8	2 1/8	UPRT	—	—	B	"	1
15926	Type 5293	2	20	600	1,500	3	2 1/4	1 1/8	UPRT	—	—	B	"	1
12573	Type 4017	2	20	600	600	3 3/16	3 3/8	2 1/8	UPRT	50835	—	B	"	1
4824	Type 2555	2	20	750	2,000	5 1/16	3 3/4	1 1/8	UPRT	—	—	B	"	1
13885	Type 4561	2	20	1,000	2,000	5 1/16	3 3/4	1 1/8	UPRT	—	—	B	"	1
13062	Type 4206	2	20	1,000	2,000	5 1/16	3 3/4	1 1/8	UPRT	—	—	B	"	1
14438	Type 4776	2	20	2,000	4,000	5 1/16	3 3/4	1 1/8	UPRT	—	—	B	"	1
9180	Type 281	2	+20—10	250	500	3 1/4	3 1/4	1 1/8	UPRT	—	—	B	"	2
5218	Type 2810	2	+inf—15	400	1,000	3 1/4	3 1/4	1 1/8	SIDE	—	—	B	"	1
5219	Type 2811	2	+inf—15	450	900	3 1/4	3 1/4	1 1/8	INVT	—	—	B	"	1
5759	Type 3146	2	+inf—15	1,000	2,000	3 1/4	2 1/4	2 1/4	UPRT	—	—	B	"	2
11576	Type 3540	2	15	2,000	4,000	5 1/16	5 1/4	2 1/4	UPRT	—	—	B	"	1
12007	Type 3716	3	10	380	760	4 1/8	5 1/4	2 1/4	UPRT	—	—	B	"	1
11215	Type 3418	3	5	600	1,200	4 1/8	4 3/4	2 1/4	SIDE	—	—	B	"	1
14202	Type 4683	4	10	2,000	4,000	6 1/8	5 3/4	2 1/4	UPRT	—	—	B	"	1
8378	Type 168	4	10	150	300	2 1/4	3	2	UPRT	—	—	B	"	1
251	Type 641	4	10	250	500	2 1/4	3 1/4	1 1/8	UPRT	—	—	B	"	2
979	Type 911	4	10	250	500	2 1/4	2 1/4	1 1/4	INVT	—	—	B	"	2
3664	Type 1850	4	10	350	700	2 3/4	3 1/4	1 1/4	UPRT	ZA.11373	—	B	"	1

SECTION 100—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	Nomenclature	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Qty. Unit
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
<p>PAPER DIELECTRIC—cont. Rectangular—cont. 1 mfd. and upwards—cont.</p>														
11498	Type 3509	4	10	350	700	2 15/16	2	1 5/8	UPRT	—	—	B	each	2
12680	Type 4043	4	10	350	700	3 11/16	4 1/2	1	UPRT	—	—	B	"	1
3726	Type 1901	4	10	400	800	2 1/4	2 1/4	2 1/2	UPRT	—	—	B	"	1
3943	Type 2012	4	10	400	800	3	3	2 1/4	UPRT	—	ZC.3530	B	"	1
9805	Type 338	4	10	400	1,000	3 1/8	3	2 1/4	UPRT	—	—	B	"	2
61	Type 593	4	10	450	900	2 1/2	2	2 1/4	INVT	—	—	B	"	2
3930	Type 1999	4	10	450	900	4 1/16	2 1/2	2	INVT	—	—	B	"	1
3048	Type 1458	4	10	450	900	5 1/16	2 1/2	1 13/16	CLMP	—	—	B	"	2
567	Type 767	4	10	450	900	5 1/16	2 1/2	1 1/2	CLMP	—	—	B	"	1
13319	Type 4328	4	10	500	1,000	5 1/16	3	2	CLMP	—	—	B	"	1
5297	Type 2850	4	10	500	1,000	5 1/8	3	2	CLMP	—	ZC.2565	B	"	1
2030	Type 940	4	10	600	600	5 1/8	2	2 1/8	INVT	—	—	B	"	1
2437	Type 1183	4	10	600	1,200	5 1/8	2 1/2	2 1/8	CLMP	—	—	B	"	1
569	Type 769	4	10	700	700	5 1/8	2 1/2	2 1/8	INVT	—	—	B	"	1
3638	Type 1829	4	10	700	1,400	5 1/8	2 1/2	2 1/8	CLMP	—	—	B	"	1
3491	Type 1724	4	10	750	1,500	5 1/8	3 1/4	2 1/8	UPRT	—	—	B	"	2
9608	Type 320	4	10	750	2,000	5 1/8	3	2 1/8	UPRT	—	—	B	"	2
2162	Type 1009	4	10	750	2,000	5 7/8	5	2 1/8	UPRT	—	ZC.0540	B	"	1
2937	Type 1415	4	10	800	1,500	6 7/8	3	1 1/8	CLMP	—	—	B	"	1
566	Type 766	4	10	800	1,600	5 1/8	4	2 1/8	CLMP	—	—	B	"	1
13910	Type 4569	4	10	1,000	2,000	5 1/8	3	1 1/8	UPRT	—	—	B	"	1
2222	Type 1039	4	10	1,000	3,000	5 7/8	5 1/2	2 1/2	UPRT	—	ZC.10602	B	"	1
2191	Type 1035	4	10	1,000	3,000	5 7/8	4	2 1/2	INVT	—	ZC.10480	B	"	1
11004	Type 3313	4	10	1,500	3,000	5 1/8	4 1/2	2 1/2	CLMP	—	—	B	"	1
2382	Type 1197	4	10	1,500	4,000	5 7/8	5 1/2	3	UPRT	—	—	B	"	1
13946	Type 4578	4	10	2,000	4,000	5 1/8	5 1/2	2 1/2	UPRT	—	—	B	"	1
11216	Type 3419	4	10	2,000	4,000	6	5 1/2	2 1/2	UPRT	—	—	B	"	1
10828	Type 509	4	10	2,000	5,000	6 1/8	5 1/2	2 1/2	UPRT	—	—	B	"	2
9385	Type 310	4	10	4,000	8,000	8 1/4	9 1/2	6	UPRT	—	—	B	"	1
2240	Type 1058	4	15	100	200	2 1/8	2 1/4	1	UPRT	—	—	B	"	1

SECTION 10C—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	PAPER DIELECTRIC—cont. Rectangular—cont. 1 mfd. and upwards—cont.													
10825	Type 484	4	15	250	500	3	2 1/8	1 3/8	UPRT	—	—	B	each	2
5567	Type 3030	4	15	250	500	3 1/8	2 1/8	1 7/8	INVT	—	—	B	"	1
2809	Type 1312	4	15	250	500	2 1/2	2 1/8	1 1/2	UPRT	—	—	B	"	1
3641	Type 1832	4	15	250	500	5 5/8	2 1/8	1 1/2	INVT	—	—	B	"	2
3608	Type 1815	4	15	400	800	5 1/4	2 1/4	1 1/8	UPRT	4060	ZA.24245	B	"	1
5147	Type 2739	4	15	400	1,000	3 3/4	3	2 1/4	UPRT	—	—	B	"	1
4482	Type 2308	4	15	450	900	2 1/2	2 1/8	1	UPRT	—	—	B	"	1
3121	Type 1516	4	15	450	900	2 1/8	3 1/4	2 1/2	INVT	—	—	B	"	1
13458	Type 4397	4	15	500	1,000	5 1/4	3 1/4	2 1/2	UPRT	—	—	B	"	1
5890	Type 3238	4	15	500	1,000	5 1/4	3	2 1/2	UPRT	—	—	B	"	1
44	Type 588	4	15	600	1,200	5 1/4	3	2	UPRT	A.1915	ZA.25739	B	"	3
12353	Type 3896	4	15	800	1,600	5 1/4	2 1/8	3 3/8	INVT	—	—	B	"	1
4535	Type 2348	4	15	800	1,600	5 1/4	2 1/8	3 3/8	UPRT	W.638	ZA.11472	B	"	1
13502	Type 4418	4	15	1,000	2,000	5 1/4	4 1/2	1 1/2	UPRT	—	—	B	"	1
12946	Type 4138	4	20	250	700	3	2 1/8	1 1/2	UPRT	50828	ZA.28238	B	"	1
14998	Type 5069	4	20	350	700	3	2 1/8	1 1/2	UPRT	—	—	B	"	1
13063	Type 4207	4	20	400	1,000	2 1/8	3	2 1/8	UPRT	50833	ZA.26508	B	"	1
15211	Type 5195	4	20	400	1,000	3	3	2 1/8	UPRT	—	ZC.8616	B	"	1
12776	Type 4079	4	20	400	1,000	3 1/8	3	2 1/8	INVT	—	—	B	"	1
13264	Type 4284	4	20	400	1,000	3 1/8	3	2 1/8	INVT	—	—	B	"	1
13192	Type 4250	4	20	400	1,000	4 1/8	1 1/2	1 1/2	INVT	—	—	B	"	1
13784	Type 4501	4	20	600	1,200	4 1/8	1 1/2	1 1/2	INVT	—	—	B	"	1
13179	Type 4241	4	20	800	2,000	5	2 1/8	3	UPRT	—	—	B	"	1
16310	Type 5508	4	20	800	2,000	5 1/8	3	3 1/8	UPRT	50842	—	B	"	1
13970	Type 4589	4	20	1,000	2,000	5 1/8	5	2 1/8	UPRT	—	—	B	"	1
13093	Type 4222	4	20	1,000	2,000	5 1/8	4	1 1/2	UPRT	—	—	B	"	1
13273	Type 4290	4	20	1,000	3,000	5 1/8	4	1 1/2	UPRT	—	—	B	"	1
13676	Type 4484	4	20	1,000	3,000	5 1/8	5	1 1/2	UPRT	—	—	B	"	1
13864	Type 4551	4	20	1,500	3,000	5 1/8	4	2 1/8	UPRT	—	—	B	"	1
14249	Type 4701	4	20	1,500	3,000	5 1/8	5 1/4	2 1/8	NONE	—	—	B	"	1

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (Ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	PAPER DIELECTRIC—cont. Rectangular—cont. 1 mfd. and upwards—cont.													
12847	Type 4095	4	20	1,500	4,000	5 1/16	5 1/8	2 1/2	UPRT	—	—	B	each	1
13915	Type 4572	4	20	2,000	4,000	6 1/4	5 1/8	6 1/8	UPRT	—	—	B	"	1
5758	Type 3145	4	+0-15	450	900	2 1/2	2 1/2	2 1/2	UPRT	—	ZA.22619	B	"	3
11415	Type 3482	5	10	500	1,000	5 1/8	4 1/8	2 1/2	UPRT	—	—	B	"	1
13872	Type 4552	5	20	750	1,500	5 1/8	3	2 1/8	UPRT	—	—	B	"	1
15711	Type —	6	10	150	300	3 1/8	2 1/8	3 1/4	UPRT	—	ZA.22096	B	"	1
2090	Type 977	6	10	600	1,500	4 1/8	3	3	UPRT	—	—	B	"	1
4028	Type 2080	6	10	750	2,000	5 1/8	5	3 1/2	UPRT	—	ZA.17051	B	"	1
4027	Type 2079	6	10	1,500	4,000	5 1/8	5 1/8	3 3/8	UPRT	—	—	B	"	1
13459	Type 4398	6	16	650	1,500	5 1/8	3 3/8	3 3/8	UPRT	—	—	B	"	1
13064	Type 4208	6	20	350	700	5 1/8	3 3/8	1 1/2	INVT	—	—	B	"	1
13873	Type 4553	6	20	350	700	3 1/8	3	1 1/2	UPRT	—	—	B	"	1
14490	Type 4811	6	20	600	1,200	5 1/8	3	3	UPRT	—	—	B	"	1
14201	Type 4682	8	5	1,000	2,000	4 1/8	4 1/8	4	INVT	—	—	B	"	1
4900	Type 2592	8	10	250	700	4 1/8	2 1/8	2 1/8	UPRT	—	ZA.1481	B	"	1
2161	Type 1008	8	10	350	700	5 1/8	4	2	UPRT	—	—	B	"	1
2326	Type 1116	8	10	400	800	2 1/8	3	1 1/2	UPRT	—	—	B	"	1
9806	Type 339	8	10	400	800	5 1/8	3	3	UPRT	—	ZC.1539	B	"	1
5559	Type 3022	8	10	450	900	5	2 1/2	3 3/4	UPRT	—	—	B	"	1
15712	Type —	8	10	565	1,500	5 1/8	2 3/8	2	UPRT	—	YB.03482	B	"	1
5665	Type 3090	8	10	600	1,500	5 1/8	3 3/8	4	CLAMP	—	—	B	"	1
8639	Type 208	8	10	700	2,000	2 1/8	3 1/8	4 1/4	UPRT	—	—	B	"	1
3513	Type 1739	8	10	750	2,000	5 1/8	5	2 3/8	UPRT	—	ZA.1480	B	"	1
2614	Type 1238	8	10	750	2,000	5 1/8	5	3	UPRT	—	—	B	"	1
2331	Type 1121	8	10	800	1,600	5 1/8	5	2 3/8	UPRT	—	—	B	"	1
12608	Type 4022	8	10	1,000	2,000	5 1/8	4 1/8	2	UPRT	—	—	B	"	1
3698	Type 1873	8	10	1,000	3,000	5 1/8	6	3	UPRT	—	ZA.21028	B	"	1
11934	Type 3676	8	10	2,000	5,000	6 1/8	7 1/8	8 1/2	UPRT	—	ZA.1479	B	"	1
2354	Type 1143	8	15	450	1,500	5 1/8	2 1/8	2 1/8	UPRT	—	—	B	"	1
13973	Type 4592	8	15	1,000	2,000	5 1/8	4 1/8	3 1/4	INVT	—	—	B	"	1

SECTION 100—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	Nomenclature	Capacity mfd.	Tolerance ± %	Voltage		Overall Dimensions (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Qty. per Carton
				Working	Test	Height	Width	Depth						
1	PAPER DIELECTRIC—cont. Rectangular—cont. 1 mfd. and upwards—cont.													
13858	Type 4546	8	20	400	1,000	5 1/8	2 3/8	3 1/2	UPPRT	50808	—	B	each	1
15713	Type —	8	20	400	1,000	5 1/8	3	1 1/2	UPPRT	—	ZA.23970	B	"	1
16312	Type 5510	8	20	1,200	3,000	5 1/8	4 1/2	5 1/2	UPPRT	50847	—	B	"	1
4895	Type 2587	10	5	2,500	5,000	7 1/8	3	1 3/4	UPPRT	—	—	B	"	1
10051	Type 369	10	10	250	700	5 1/8	2 1/2	3 3/8	UPPRT	—	ZA.13415	B	"	2
3416	Type 1677	10	10	400	800	5 1/8	3	2 1/4	UPPRT	—	—	B	"	1
9807	Type 340	10	10	400	800	5 1/8	3 1/4	3	UPPRT	—	ZA.22930	B	"	1
2224	Type 1041	10	10	400	1,000	5 1/8	3 1/4	3	UPPRT	—	ZC.10603	B	"	1
2165	Type 1012	10	10	1,000	2,000	5 1/8	5	4 1/2	UPPRT	—	ZC.0510	B	"	1
2194	Type 1038	10	10	400	1,000	5 1/8	3 1/4	3	INVT	—	ZC.7276	B	"	1
4886	Type 2578	10	10	600	600	5 1/8	2 1/2	3	UPPRT	—	—	B	"	1
10827	Type 486	10	10	600	1,500	5 1/8	8	5	UPPRT	—	ZC.0534	B	"	2
10832	Type 490	10	10	750	2,000	5 1/8	5	5	UPPRT	—	ZA.20298	B	"	1
15714	Type —	10	10	1,000	2,000	5 1/8	5	2 1/2	UPPRT	—	ZA.22094	B	"	1
2622	Type 1246	10	10	1,000	3,000	5 1/8	7 1/4	6 1/4	UPPRT	—	ZC.1527	B	"	1
2323	Type 1113	10	15	800	2,000	6 1/8	5	2 1/2	UPPRT	—	—	B	"	1
277	Type 647	10	15	250	500	2 1/8	1 3/4	1 1/2	UPPRT	—	—	B	"	1
276	Type 646	10	15	250	500	2 1/8	3 1/4	3	UPPRT	—	—	B	"	1
12848	Type 4096	10	20	400	1,000	5 3/8	3 1/4	3	UPPRT	—	—	B	"	1
14144	Type 4654	10	20	600	1,200	5 3/8	3	5 1/2	UPPRT	—	—	B	"	1
13974	Type 4593	10	20	600	1,200	4 1/4	4 1/2	4	INVT	—	—	B	"	1
13992	Type 4600	10	20	1,000	2,000	4 1/4	4 1/2	6 3/8	UPPRT	—	—	B	"	1
15715	Type —	16	+30-10	565	3,000	5 1/2	4 1/2	2	UPPRT	—	YB.03303	B	"	1
5805	Type 3192	100	10	150	1,200	6 3/8	4 1/2	6	SIDE	—	—	B	"	1
3953	Type 2022	.01 + .01	10	500	1,000	6 3/8	2 1/2	1	SIDE	W.7059	—	B	"	1
883	Type 869	.01 + .01	15	600	1,200	3 1/4	1 3/8	1 1/2	INVT	—	—	B	"	1
2713	Type 1306	.05 + .05	10	2,000	4,000	6 1/8	4	2	CLMP	—	—	B	"	1

SECTION 100—cont.

FIXED CONDENSERS

NOTE 3 B. 4

Ref. No.	Nomenclature	Capacity ind.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
PAPER DIELECTRIC—cont.														
Rectangular—cont.														
1 mfd. and upwards—cont.														
2712	Type 1305	.05+ .05	10	7,000 5,000	14KV 10KV	9	4	2	CLMP	—	—	B	each	1
696	Type 800	.05+ .1	10	5,000 3,000	10KV 6KV	7 $\frac{3}{4}$	4	3	CLMP	—	—	B	"	1
17011	Type —	.1+.1	10	600	1,250	1 $\frac{1}{8}$	2 $\frac{1}{2}$	1	UPRT	—	ZA, 11349	B	"	1
695	Type 799	.1+.1	10	2,000	4,000	4 $\frac{1}{2}$	2	1 $\frac{7}{8}$	CLMP	—	—	B	"	1
4212	Type 2168	.1+.1	10	3,000	6,000	7 $\frac{1}{2}$	3 $\frac{1}{2}$	2 $\frac{1}{2}$	CLMP	—	—	B	"	1
941	Type 886	.1+.1	10	8,000	16KV	8 $\frac{1}{2}$	5	5	CLMP	—	—	B	"	1
15718	Type —	.1+.1+ .1+.085	+15-10	450	1,100	1 $\frac{1}{8}$	7 $\frac{3}{8}$	2 $\frac{1}{2}$	UPRT	—	YB, 03293	B	"	1
		.01	+20-10											
		.1+.1												
15716	Type —	.1+.1 .1+.1	+30-10	450	1,100	1 $\frac{1}{8}$	5 $\frac{1}{8}$	2 $\frac{1}{2}$	UPRT	—	YB, 03294	B	"	1
15717	Type —	.1+.1+ .1+.1+ .1+.1+ .1+.1	+30-10	450	1,100	1 $\frac{1}{8}$	9 $\frac{3}{8}$	2 $\frac{1}{2}$	UPRT	—	YB, 03295	B	"	1
12287	Type 3853	.1 +.05 +.025	2	250	500	3 $\frac{1}{8}$	1 $\frac{3}{4}$	1 $\frac{7}{8}$	UPRT	—	—	B	"	1
2634	Type 1256	.25 +.18 +.10 +.10	10 10 20 20	124 70 500 500	—	3 $\frac{1}{8}$	4 $\frac{1}{8}$	2 $\frac{1}{4}$	SIDE	—	—	B	"	1
2046	Type 951	.25+.25	10	4,000	8,000	6 $\frac{1}{8}$	5	2	CLMP	—	—	B	"	1
12697	Type 4056	.25+.25	15	9,000	18KV	7 $\frac{1}{8}$	6 $\frac{1}{4}$	3 $\frac{1}{4}$	UPRT	—	—	B	"	1

SECTION 10C—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1														
	PAPER DIELECTRIC—cont. Rectangular—cont. 1 mfd. and upwards—cont.													
2053	Type 955	.25+	10	1,500	3,000	2 1/8	2	2 1/8	UPRT			B	each	2
15739	Type —	.4+.1	10+60-10	250	500	4 1/2	2	1 1/2	UPRT		YB.03442	B	"	1
9223	Type 291	.5+.5	10	125	1,000	2 1/4	2 1/4	1	UPRT			B	"	2
5525	Type 2988	.5+.5	10	150	300	2 1/4	1 1/2	1	CLMP			B	"	1
13050	Type 4198	.5+.5	10	500	1,000	2 1/4	3 1/2	1 1/4	UPRT			B	"	1
11281	Type 3445	.5+.5	10	1,500	3,000	5 1/8	5 1/8	2 1/2	CLMP			B	"	1
2389	Type 1556	.5+.5	10	4,400	8,800	5 1/8	5 1/8	10	CLMP			B	"	1
		+1.0		3,500	7,000	4 1/8	5 1/4		UPRT			B	"	1
3280	Type 1594	.5+	15	250	500	2 1/4	2 1/8	2	UP/SD			B	"	1
4616	Type 2407	.5+.5	+40-5	1,500	3,000	2 1/4	2 1/8	2 1/8	SIDE			B	"	1
3869	Type 1958	1+.1	10	100	200	2 1/8	2 3/4	2 3/8	CLMP			B	"	1
15719	Type —	1+.1	10	250	500	2 1/8	2 3/4	1 1/4	UPRT		YB.03300	B	"	1
2564	Type 1211	1+.1	10	350	1,000	3 3/8	2	1 1/4	SIDE			B	"	1
2563	Type 1210	1+.1	10	450	1,100	3 3/8	2	1 1/4	UPRT			B	"	1
2047	Type 952	1+.1	10	450	1,100	3 1/2	2	1 1/8	CLMP			B	"	1
11459	Type 3488	1+.1	10	1,000	2,000	5 1/8	2 1/2	1 1/8	CLMP			B	"	1
4615	Type 2406	1+.1	20	500	1,000	3 1/4	2	2	CLMP			B	"	1
710	Type 806	2+.1	+40-5	100	200	2 1/8	2 1/8	1 1/4	UPRT			B	"	1
15720	Type —	2+.1	10	350	600	3 1/8	2 1/8	2	CLMP			B	"	1
715	Type 811	2+.1	10	450	1,100	3 1/8	2 1/4	1 1/8	UPRT		YB.03301	B	"	1
3719	Type 1894	2+.1	10	600	1,200	3 1/8	2 1/8	2	CLMP			B	"	1
4618	Type 2409	2+.2	10	250	500	3 1/8	3 1/4	1 1/4	CLMP			B	"	1
		4	+40-5	400	800	2 1/8	3 1/4	3	UPRT			B	"	1
2332	Type 1122	.2+	10	800	1,600	4	5	3	UPRT			B	"	1
11575	Type 3539	2.25 +2.25	15	3,000	6,000	6 1/8	10 1/4	7	UPRT			B	"	1

SECTION 100—cont.

FIXED CONDENSERS

VOTE 3 B. 4

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	PAPER DIELECTRIC—cont.													
	Rectangular—cont.													
	1 mfd. and upwards—cont.													
962	Type 894	2.5+ 1.0	15	200	400	2 1/2	1 3/4	2 3/8	SIDE	—	—	B	each	1
960	Type 892	2.5+ 1.0	15	200	400	2 3/8	1 3/4	2 1/8	UPRT	—	—	B	"	1
4262	Type 2206	4+2	10	250	500	3 1/8	3	3 1/4	UPRT	—	—	B	"	1
2696	Type 1295	4+2	10	350	700	3 1/8	3	3 1/4	INVT	—	—	B	"	1
11577	Type 3541	4+2	10	3,000	9,000	7 3/8	10 1/4	12	UPRT	—	—	B	"	1
2381	Type 1196	4+4	10	2,000	4,000	6 1/8	10 1/4	7	UPRT	—	—	B	"	1
2380	Type 1195	4+4	10	3,000	9,000	6 1/8	10 1/4	7	UPRT	—	—	B	"	1
2383	Type 1198	4+4	10	4,500	11 1/4KV	6 1/8	10 1/4	12	UPRT	—	—	B	"	1
4263	Type 2207	8+	15	350	700	5 1/8	3 1/4	2	INVT	—	WY.1846	B	"	1
4932	Type 2622	4	20	500	1,000	4 3/8	4 1/2	2 3/8	UPRT	—	—	B	"	1
		8+	20	500	1,000	4 3/8	4 1/2	2 3/8	UPRT	—	—	B	"	1
		4	10	350	700	5	3	4 1/4	UPRT	—	—	B	"	1
3554	Type 1769	8+8	10	400	800	5	3	4 1/4	UPRT	—	—	B	"	1
13051	Type 4199	8+8	20	500	1,000	5	3 1/8	2 1/8	UPRT	—	—	B	"	1
15721	Type —	8+8	+30-10	565	1,500	3	9 3/8	2	SIDE	—	YB.03302	B	"	1
47	Type 589	10+10	10	250	500	3 1/8	8	2 1/4	UPRT	—	—	B	"	1
		+4+4	10	250	500	3 1/8	8	2 1/4	UPRT	—	—	B	"	1
	Steel or other case:—													
2379	Type 1194	.5	+20-5	25KV	51KV	15 1/8	15 1/8	16	UPRT	—	—	B	"	1
13677	Type 4485	.8	15	36KV	72KV	27	23	15	UPRT	—	—	B	"	1
2321	Type 1111	2	15	18KV	36KV	19 3/8	14 7/8	14 7/8	UPRT	—	—	B	"	1
3111	Type 1511	2-25	+20-5	25KV	51KV	15 1/8	36 1/4	29	UPRT	—	ZC.1526	B	"	1

N.B.—It should be noted that a few fixed condensers not yet classified in these tables appear in the following pages.

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
—	CONDENSERS:—		Army			
—	5-80 pfd. ...	5-80 pfd., trimmer ...	ZA. 2008	B	each	—
—	R2.L.02 mfd. \pm 20 per cent., 450 volts D.C. working, non-inductive, tubular, paper.	Army ZA.1591	B	"	—
3342	Type 100001 to .00005 mfd. Single vane, adjustable, mica dielectric, mounted on square base.	ZA. 3155/89	B	"	1
5954	Type 4000024 to .0003 mfd. \pm 5% Variable, air dielectric, vernier adjustment dial engraved "0-210". With remote control attachment.		B	"	3
2951	Type 7 ...	1 jar. Variable, air (or oil) dielectric, with glass container, handle, pointer, engraved scale and shorting switch.		B	"	1
3486	Type 800015 mfd. Fixed capacity, mica dielectric, clamped, with 2 clips for 1½-in. grid leak. 1,000 volts megger test.		B	"	2
3356	Type 1800075 mfd. Fixed capacity, mica dielectric, clamped. 5,000 volts D.C. and 500 volts, 100 kc./s test.		B	"	2
2263	Type 3601— .01— .002 mfd Fixed capacity, mica dielectric, with metal disc clamp, tapped. 5,000 volts D.C. and 500 volts, 100 kc./s test.		B	"	1
1804	Type 42 ...	0.3 mfd. Paper dielectric, in wax filled metal case, with soldering tabs. 300 volts D C. test.		B	"	1
5302	Type 43 ...	0.5 mfd. Paper dielectric, in wax filled metal case, with soldering tabs. 300 volts D C. test		B	"	2
7203	Type 540003 mfd. Variable, air dielectric.		B	"	1
7348	Type 6500003 mfd Tubular "Clip-in" type, 1½ in. long.		B	"	2
7423	Type 7500008 mfd. Fixed capacity, air dielectric, with duralumin vanes.		B	"	1
7424	Type 7600012 mfd. Fixed capacity, mica dielectric, in bakelite body with screwed clamping plug. 5,000 volts D C. test.		B	"	1
7425	Type 770011 mfd Fixed capacity, mica dielectric, in bakelite body, with screwed clamping plug. 5,000 volts D.C. test.		B	"	1
7427	Type 79005 mfd Two fixed capacity, mica dielectric, clamped condensers assembled as one unit. 5,000 volts D C and 5 amps at 500 kc /s test.		B	"	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
7469	Type 800005 mfd. Variable, air dielectric, without knob and dial		B	each	1
7594	Type 860003 mfd. Variable, air dielectric, without handle.		B	"	1
7762	Type 1070001 mfd. Fixed capacity, mica dielectric, with disc clamps. 5 amps. at 5,000 kc./s test.		B	"	3
7853	Type 111	0.125 mfd Fixed capacity. 28,000 volts test		B	"	1
7895	Type 118	0.5 mfd Paper dielectric, in wax-filled metal case. 2,500 volts D.C. test.		B	"	1
7904	Type 12300005 mfd. Variable, air dielectric.		B	"	1
7905	Type 1240002 mfd. Variable, air dielectric, slow motion.		B	"	1
8012	Type 135	200 μ F. Variable air ...		A	"	1
8116	Type 14700025 mfd. Fixed capacity, mica dielectric, clamped. 1,000 volts megger test.		B	"	1
8140	Type 149002 mfd. Fixed capacity, mica dielectric, clamped.		B	"	5
8166	Type 1540003 mfd. Mica dielectric, clamped.		B	"	1
8167	Type 155000192 mfd. Bank of 6 units with square micas and disc clamps.		B	"	1
8168	Type 15600103. Bank of 10 units with square micas and disc clamps.		B	"	1
8169	Type 1570002 mfd. 2 units with square micas and disc clamps.		B	"	1
8171	Type 159000032 mfd. With square micas and disc clamps.		B	"	1
8172	Type 160000106 mfd. With square micas and disc clamps.		B	"	1
8201	Type 161	4.5 pfd. Fixed capacity, mica dielectric screwed clamping plugs.		B	"	2
8206	Type 162000212 mfd. 2 units with square micas and disc clamp.		B	"	1
8286	Type 166	8 mfd. Paper dielectric, wax-filled, metal case. 400 volts D C test.		B	"	1
8380	Type 17000001 mfd. Variable, air dielectric.		B	"	1
8381	Type 1710005 mfd. Variable, air dielectric.		B	"	1
8384	Type 17400025 mfd. Pre-set type ...		B	"	2
8387	Type 17700001 mfd. Mica dielectric, clip-in type.		B	"	3
8490	Type 1820003 mfd. Variable, air dielectric, without handle.		B	"	1
8501	Type 19300003 mfd. Variable, air dielectric, screw controlled.		B	"	1
8502	Type 194000115 mfd. Fixed, air dielectric, rectangular plates.		B	"	1
8508	Type 19900002 mfd. Air dielectric, rectangular plates, adjustable.		B	"	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
8566	Type 20400025 mfd. Pre-set type (Modification of type 174).		B	each	1
8637	Type 206 ...	2 mfd. Metal case 5,000 volts D.C. working.		B	"	1
8720	Type 21800083 mfd. Maximum. Variable air dielectric. With double set of vanes.		B	"	1
8672	Type 221 ...	1 mfd. Cylindrical, paper dielectric, non-inductive. 450 volts working.		B	"	2
8804	Type 2300005 mfd. Variable, air dielectric. Without knob and dial.		B	"	1
9145	Type 261000415 mfd. Mica dielectric ...		B	"	1
9151	Type 26300085 mfd. Maximum. Variable, air dielectric, with double sets of vanes and vernier vane.		B	"	1
9152	Type 2640001 mfd. Maximum. Variable, air dielectric.		B	"	1
2229	Pillars, mounting		B	"	5
2227	Spindles, extension		B	"	1
9318	Type 265000135 mfd. Mica dielectric ...		B	"	1
9300	Type 277 ...	0.5 mfd. Paper dielectric, in wax-filled metal case.		B	"	2
9182	Type 283 ...	Miniature, variable, with screw adjustment.		B	"	2
9197	Type 287000048 mfd. Variable, 3 gang, air dielectric.		B	"	1
9198	Type 288 ...	12 pfd. min. to 233 pfd. max., variable air, complete with drive.		B	"	2
9186	Type 292 ...	2 mfd. Paper dielectric, in metal case.		B	"	1
9630	Type 325 ...	1,000 mfd. 25 volts, electrolytic.		B	"	1
9905	Type 333 ...	1 mfd. 1,000 volts D.C. test. Metal case.		B	"	2
9906	Type 334 ...	1 mfd 8,000 volts D.C. test. Metal case.		B	"	2
9907	Type 335 ...	1 mfd. 16,000 volts D.C. test. Metal case.		B	"	2
10082	Type 371 ...	0.5 mfd. Metal case 1,500 volts working		B	"	1
10507	Type 374 ...	10 pfd Variable, air ...		B	"	1
10513	Type 38000025 mfd. Variable, air. Series plate with shorting switch.		B	"	1
10317	Type 3910005 mfd. Variable, air ...		B	"	1
10344	Type 3940001 mfd Variable, air ...		B	"	1
10390	Type 400 ...	250 pfd. 1,250 volts D.C. test. Variable, air.		B	"	1
10460	Type 407 ...	10 + 6 + 4 mfd. Electrolytic block in cardboard case. 300 volts.		B	"	1
10476	Type 411 ...	30 pfd. Variable, air ...		B	"	1
10230	Type 413 ...	3-17 pfd. Variable, air, trimming condenser		B	"	1
10226	Type 4150005 mfd. Variable, air ...		B	"	1
10227	Type 416 ...	3-35 pfd. Variable, air, trimming condenser.		B	"	1
10938	Type 432 ...	100 pfd Variable, air dielectric; trimmer.		B	"	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
10644	Type 442 ...	0.0003 mfd. ...		B	each	1
10646	Type 444		A	"	5
10647	Type 445 ...	20 pfd. ...		B	"	5
10648	Type 446 ...	40 pfd. ...		B	"	5
10651	Type 449 ...	0.1 mfd. ...		B	"	3
10655	Type 450 ...	0.001 mfd. ...		B	"	5
10656	Type 451 ...	0.01 mfd. ...		B	"	5
10743	Type 457 ...	300 pfd. ...		B	"	3
10752	Type 461		A	"	1
10753	Type 462		A	"	5
10878	Type 495 ...	0.07 mfd. ...		B	"	3
10883	Type 496 ...	0.1 mfd. ...		B	"	2
11305	Type 513 ...	60 mfd., 25 volts working, electrolytic.		B	"	2
11365	Type 517 ...	25 pfd., pre-set trimmer ...		B	"	1
11455	Type 527 ...	65 pfd. Variable, air ...		B	"	1
11588	Type 544 ...	Variable series gap ...		B	"	1
3628	Type 545 ...	Min. not more than 1.3 pfd. Max. between 4.5 and 7.6 pfd. Trimmer ceramic.		B	"	3
11693	Type 547001 mfd. Silvered mica, moulded.		B	"	3
11708	Type 553002 mfd. Tubular, 350 volts, D.C.		B	"	2
11709	Type 554 ...	4.0 mfd. Paper metal case, 250 volts, D.C. working. Fixing centres, $2\frac{1}{8}$ in. \times $1\frac{1}{8}$ in.		B	"	2
11	Type 567 ...	50 μ F. 35 volts D.C. Silvered mica, protected.		A	"	5
21	Type 577 ...	50 mfd. 2 volts D.C. Electrolytic.		B	"	1
23	Type 579 ...	0.5 mfd. Tubular, paper. Wire ends at sides.		B	"	2
37	Type 583 ...	15 pfd., 10 per cent. ...		A	"	5
62	Type 594 ...	1 mfd. Tubular metal case ...		B	"	2
84	Type 598 ...	2 gang air variable, 6 pfd. min., 30 pfd. swing; ceramic base.		B	"	1
83	Type 599 ...	2 gang air variable, 5.5 pfd. min., 18 pfd. swing; ceramic base.		B	"	1
85	Type 600 ...	Air variable, neutralising, not greater than 3.2 pfd.; min. capacity not less than 1.5 pfd.		B	"	1
86	Type 601 ...	Air variable, neutralising, not greater than 3.2 pfd.; min. capacity not less than 1.5 pfd.		B	"	2
88	Type 603 ...	4-59.5 pfd., air variable, D.L.9 moulded base, spindle, $\frac{1}{4}$ in. dia., tropical.		B	"	1
90	Type 605 ...	3-65 pfd. air variable ...		B	"	1
223	Type 626 ...	5 mfd. \pm .2 mfd., ceramic disc		B	"	5
233	Type 630 ...	10 pfd. ...		B	"	5
234	Type 631 ...	40 pfd. ...		B	"	5
241	Type 6320275 mfd. \pm 1 per cent ...		B	"	5
242	Type 63306 mfd. \pm 1 per cent. ...		B	"	5
243	Type 634165 mfd. \pm 1 per cent. ...		B	"	5
274	Type 64425 mfd. tubular end connections		B	"	3
275	Type 645 ...	2.5 mfd., paper dielectric in metal case, 500 volts working without fixing feet.		B	"	2
279	Type 649 ...	2.5 mfd. paper dielectric in metal case, 500 volts working, with fixing lugs		B	"	2

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
312	Type 658 ...	4 mfd., 750 volts D.C. test, dry electrolytic.		B	each	1
339	Type 665 ...	4 mfd. electrolytic ...		B	"	2
344	Type 667 ...	14 pfd. minimum to 350 pfd. maximum; length of spindle, 0.74 in., with tapped hole.		B	"	3
351	Type 669 ...	40 pfd. ...		B	"	5
366	Type 671 ...	0.003 mfd., each half 2 gang ...		B	"	1
368	Type 673 ...	0.0005 mfd., each half 2 gang		B	"	1
369	Type 674 ...	Vernier condenser (slow motion)		B	"	1
370	Type 675 ...	0.01 mfd., paper ...		B	"	3
371	Type 676 ...	140-220 pfd., each section trimmer.		B	"	1
372	Type 677 ...	0.1 mfd., paper condenser ...		B	"	2
374	Type 679 ...	23½-30 pfd., variable ...		B	"	1
375	Type 680 ...	20.0001 mfd., each section variable.		B	"	1
377	Type 682 ...	0.005 mfd., moulded mica ...		B	"	5
378	Type 683 ...	25 pfd., trimmer ...		B	"	1
379	Type 684 ...	0.0001 mfd. ...		B	"	5
392	Type 689001 pfd. ...		B	"	5
395	Type 692004 pfd. ...		B	"	5
397	Type 69425 pfd. ...		B	"	5
398	Type 695 ...	50 pfd. ...		B	"	5
399	Type 696 ...	18 pfd., variable ...		B	"	1
436	Type 704 ...	1.0 mfd., 350 volts ...		B	"	2
445	Type 713 ...	4 mfd., 4,000 volts working ...		B	"	1
475	Type 724 ...	Trimmer ...		B	"	2
477	Type 726 ...	0.5 mfd., 4,000 volts working		B	"	1
481	Type 730 ...	0.0005 mfd. ...		B	"	1
497	Type 735003 mfd., mica moulded ...		B	"	2
504	Type 751 ...	1-30 pfd. ...		B	"	2
543	Type 757 ...	20 pfd., variable, air dielectric, ¾ in. spindle.		B	"	1
609	Type 774 ...	4 mfd., 150 volts, D.C. working, 1½ in. dia., tubular.		B	"	1
625	Type 776 ...	2 gang variable ...		B	"	1
634	Type 781 ...	5 pfd., silvered mica ...		B	"	5
730	Type 816 ...	Ceramic trimmer ...		B	"	3
731	Type 817 ...	2-30 pfd., variable ...		B	"	1
746	Type 8325 mfd., ± 15 per cent., tubular, paper, 350 volts, working.		B	"	2
769	Type 833 ...	100 + 100 pfd., ± 10 per cent., special short wave variable air dielectric, left hand.		B	"	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref	Class of Store	Denom. of Qty	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
770	Type 834 ...	As type 833, but right hand		B	each	1
843	Type 856 ...	16 mfd., electrolytic, 450 volts		B	"	1
2646	Nuts		C	"	12
872	Type 866 ...	130 pfd., 2 gang ...		B	"	1
894	Type 873 ...	100 + 100 pfd., ± 5%, split stator, variable air dielectric.		B	"	1
901	Type 875 ...	Mica, wax coated ...		B	"	5
910	Type 876 ...	·0001 mfd, variable air dielectric, tag connections Rotor tag, spaced 30° from stator tag.		B	"	1
915	Type 878 ...	60 pfd., variable air dielectric, tag connections. Rotor tag spaced 30° from stator tag.		B	"	1
916	Type 879 ...	60 pfd, variable air dielectric, tag connections. Rotor tag 90° from stator tag.		B	"	1
917	Type 880 ...	·0001 mfd., variable air dielectric, tag connections. Rotor tag spaced 90° from stator tag.		B	"	1
968	Type 900 ...	75 pfd., variable air trimmer ...		B	"	1
974	Type 906 ...	7-100 μμf., ceramic trimmer, centre adjusting screw.		B	"	2
976	Type 908 ...	5-40 pfd., ceramic trimmer, with tag connections.		B	"	3
2018	Type 942 ...	·00001 mfd., ± 10 per cent., fixed air, double spaced.		B	"	5
2069	Type 959 ...	3-18 pfd.		B	"	1
2070	Type 960 ...	3-20 pfd., tuning		B	"	1
2071	Type 961 ...	3-18 pfd.		B	"	1
2072	Type 962 ...	Trimmer, cylindrical, 2-8 pfd.		B	"	3
2089	Type 964 ...	300 pfd, mica, impregnated ...		B	"	1
2082	Type 972 ...	1·5 pfd, variable		B	"	1
2086	Type 976 ...	6 pfd, ± 10 per cent., fixed air, double spaced.		B	"	2
2103	Type 979 ...	15 pfd to 0·000197 mfd., 4 gang dielectric		B	"	1
2110	Type 984 ...	80 pfd., + 80 pfd. variable, left hand.		B	"	1
2124	Type 1006		B	"	1
2172	Type 1019 ...	·4 mfd., 500 volts, D.C. working, metal case (terminals at 1,000 volts, to earth).		B	"	1
2180	Type 1027 ...	3-18 pfd. Variable air dielectric		B	"	1
2223	Type 1040 ...	0·1 mfd., 450 volts, block metal case.		B	"	1
2258	Type 1073 ...	0·07 mfd., 350 volts, D.C. working, tubular.		B	"	2
2259	Type 1074 ...	0·1 mfd., 750 volts, D C working, tubular.		B	"	2
2262	Type 1077 ...	Neutradyne condenser assembly		B	"	1
2281	Type 1087 ...	0·0003 mfd., pre-set, variable		B	"	1
2282	Type 1088 ...	·0005 mfd., variable		B	"	1
2283	Type 1089 ...	0·0001 mfd., variable air dielectric.		B	"	1
2284	Type 1090 ...	0·1 mfd., 3,500 volts, tubular ...		B	"	2
2285	Type 1091 ...	0·0003 mfd., mica, moulded ...		B	"	2
2286	Type 1092 ...	0·003 mfd., mica, moulded ...		B	"	3

RADIO CHOKES AND CONDENSERS

Ref. No	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom of Qty.	Carton Unit Qty
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
2307	Type 109905 mfd., \pm 1 per cent., 450 volts, D.C. working, tubular, $\frac{7}{16}$ in. dia. \times $1\frac{1}{16}$ in., wire ends.		B	each	2
2311	Type 11011 mfd., \pm 15 per cent., 1,000 volts, D.C. working, tubular, $\frac{3}{4}$ in. dia. \times $2\frac{1}{2}$ in., wire ends.		B	"	—
3778	Type 1104003 mfd., \pm 15 per cent., 450 volts, D.C. working, tubular, $\frac{3}{8}$ in. dia. \times $1\frac{1}{2}$ in., wire ends.		B	"	—
2318	Type 1108004 mfd., mica, in copper flanged case, $2\frac{3}{4}$ in. dia \times $1\frac{1}{8}$ in. with 4 hole fixings.		B	"	1
2328	Type 1118 ...	Bushing type, 36 k. volts, D.C.		B	"	1
2334	Type 1124 ...	2 mfd., 2,000 volts D C + 30 per cent., 100 cycles, ripple working.		B	"	1
2352	Type 114102 mfd., 4,000 volts, D.C. working.		B	"	1
2353	Type 1142 ...	50 mfd., 50 volts, D.C. working		B	"	2
2431	Type 1177 ...	5-40 pfd., air variable trimmer		B	"	1
2387	Type 1202001 mfd. (approx.) ...		B	"	1
3201	Type 12045 + .5 + .1 + .1 mfd., \pm 10 per cent., 3.5 k. volts, rectangular metal case.		B	"	
2560	Type 1207 ...	10-65 pfd., trimmer ...		B	"	1
2572	Type 1217 ...	Tuning air dielectric, 2 sections		B	"	1
2574	Type 1220 ...	28 pfd., max., air, variable, ceramic insulation, metal frame. Spindle, $\frac{1}{4}$ in. dia \times .546 in.		B	"	2
2575	Type 1221 ...	Variable, twin section ...		B	"	1
2579	Type 1224 ...	5 mfd., 200 volts, tubular, with terminal sleeved wires sweated to ends, without sleeves.		B	"	1
2587	Type 1225		A	"	1
2615	Type 1239 ...	0.01 mfd. ...		B	"	3
2617	Type 1241 ...	1 μ F. ...		A	"	2
2638	Type 1260		B	"	1
2676	Type 1280 ...	2 \times 15 pfd., — 45 pfd., trimmer, ceramic.		B	"	2
2684	Type 1288 ...	0.1 + 0.1 μ F., 10 per cent. 3,000 volts D.C. Metal case, 6 in. \times 2 in. \times 7 in		A	"	1
2705	Type 1298 ...	23 pfd., max 2 gang, air, variable, ceramic insulation, metal frame, spindle $\frac{1}{4}$ in. dia. \times .562 in. at front and rear.		B	"	1
2706	Type 1299 ...	3.5 pfd.—42 pfd., ceramic trimmer.		B	"	1
2708	Type 1301 ...	70 pfd. (max.), double trimmer		B	"	2
2806	Type 1309001 mfd., variable air dielectric		B	"	1
2714	Type 1317 ...	0.1 mfd., 800 volts, tubular, wire end connections.		B	"	2
2725	Type 1328 ...	75 + 75 + 5 — 0 pfd., variable air dielectric.		B	"	1
2727	Type 1330 ...	100 + 100 pfd., + 5 — 0 pfd., variable air dielectric.		B	"	1
2796	Type 1338 ...	0.01 mfd, 400 volts, tubular, wire end connection.		B	"	5
2797	Type 1339 ...	0.1 mfd., 400 volts, tubular, wire end connection.		B	"	3

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
		<i>cont.</i>				
2799	Type 1341	... 11 mfd., 450 volts, working ...		B	each	2
2800	Type 1342	... H.T. feeder bushing ...		B	"	1
2801	Type 1343	... H.T., feeder bushing ...		B	"	1
2802	Type 1344	... 300 pfd., moulded, pre-set ...		B	"	1
2814	Type 1356	... 0.1 mfd., 3,500 volts, tubular, one end connections.		B	"	2
2819	Type 1361	... 2 mfd., 450 volts, working, tag connections.		B	"	1
2870	Type 1362	... 30-3 $\mu\mu\text{F}$. Trimmer ...		A	"	2
2873	Type 1365	... 0.001 mfd., ± 2 per cent., 1,300 volts, A.C., 60 cycles test, ceramic rod type, concentric wire ends, negative temperature coefficient.		B	"	3
2882	Type 1374	... 110 pfd., variable air dielectric, $2\frac{1}{2}$ in. dia., panel mounting, 1 hole fixing.		B	"	1
2896	Type 1388	... 0.00018 mfd., variable air ...		B	"	1
2930	Type 1407	... 2 \times 30 pfd., variable ...		B	"	1
2932	Type 140901 mfd., mica, 250 volts, D.C. working.		B	"	2
2935	Type 1413	... 10 pfd., max., air-spaced trimmer, with locking device.		B	"	1
2966	Type 1421	... 60-15 $\mu\mu\text{F}$. Trimmer, ceramic		A	"	3
2973	Type 14285 mfd., ± 15 per cent., tubular, paper, 450 volts, working		B	"	2
3023	Type 1435	... 25 μF . + 100 - 0 per cent. 50 D C Electrolyte.		A	"	2
3028	Type 1440	... Variable 3 gang, with tuning scale calibrated to suit Coil Unit, 10D/380.		B	"	1
3031	Type 1442	... 0.5 mfd., 750 volts, D.C. working, metal case, tags, tropical.		B	"	1
3039	Type 145005 mfd., 200 volts D.C. working, paper, tubular, with 2 leads, 12 in. long.		B	"	1
3047	Type 145700062 mfd., trimmer ...		B	"	3
3066	Type 14760001 mfd., variable air spaced, screwdriver adjustment, locking device.		B	"	2
3085	Type 1491	... 10-315 pfd., 2 gang, variable ...		B	"	1
3092	Type 1498	... 4-20 pfd., variable air, frequentite base.		B	"	1
3125	Type 1520	... Special, 2 ganged, variable, air dielectric, 2-15 pfd., each section.		B	"	1
3094	Type 1522	... 3.8 pfd. to 40 pfd., variable ...		B	"	1
3129	Type 1525	... 5-60 pfd., variable, air, trimmer		B	"	1
3180	Type 15360014 mfd., variable, air ...		B	"	1
3186	Type 1541	... 0.1 mfd., ± 15 per cent., paper dielectric, in moulded bakelite case, 250 volts, D.C. working, terminal connections.		B	"	2

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
		<i>cont</i>				
3194	Type 1549 ...	50 mfd., electrolytic, 12 volts, D.C. working, terminal connections.		B	each	2
3207	Type 1561 ...	0.0002 mfd., mica dielectric, in moulded case, 500 volts, D.C. working, tag connections.		B	"	2
3208	Type 1562 ...	25 mfd., electrolytic, 25 volts, D.C. working, terminal connections.		B	"	2
3217	Type 1571 ...	As Type 817, but without centre spring contact, and with modified tag positions.		B	"	1
3275	Type 1589 ...	8 μ F., 15 per cent., 250 volts D.C. Paper, metal case.		B	"	1
3293	Type 1604 ...	3-20 pfd., trimmer ...		B	"	1
3294	Type 1605 ...	25 pfd., air spaced trimmer, $\frac{1}{4}$ in. diam., extended spindle.		B	"	1
3298	Type 160700016 mfd., variable ceramic base, air dielectric.		B	"	1
3299	Type 1608 ...	3.5-25 pfd., air spaced trimmer		B	"	1
3304	Type 16100001 mfd., \pm 2 pfd., silvered mica.		B	"	5
3305	Type 16110002 mfd., \pm 2 pfd., silvered mica.		B	"	5
3308	Type 16140005 mfd., \pm 2 pfd., silvered mica.		B	"	5
3309	Type 16150006 mfd., \pm 3 pfd., silvered mica.		B	"	5
3313	Type 1619001 mfd., \pm 4 pfd., silvered mica.		B	"	5
3325	Type 1631 ...	0.00014 mfd., variable ...		B	"	1
3327	Type 1633002 mfd., \pm 0.4 per cent., silvered mica.		B	"	5
3330	Type 1636005 mfd., \pm 0.3 per cent., silvered mica.		B	"	5
3331	Type 1637006 mfd., \pm 0.3 per cent., silvered mica.		B	"	5
3332	Type 1638007 mfd., \pm 0.3 per cent., silvered mica.		B	"	5
3333	Type 1639008 mfd., \pm 0.3 per cent., silvered mica.		B	"	5
3334	Type 164001 mfd., \pm 0.3 per cent., silvered mica.		B	"	5
3336	Type 1642 ...	45 + 45 pfd., variable, air dielectric.		B	"	1
3394	Type 1658 ...	0.003 mfd., \pm 2 per cent., silvered mica.		B	"	5
3395	Type 1659 ...	3.5 to 25 pfd., air, variable, ceramic base, $\frac{1}{8}$ in. \times $1\frac{7}{32}$ in., short spindle, slotted.		B	"	5
3407	Type 1669 ...	45-15 pfd. Trimmer, ceramic ...		B	"	2
3452	Type 1703 ...	650 pf., 15 per cent., 750 volts D.C., silvered mica, protected.		B	"	5
3456	Type 1705 ...	90 pfd., variable, air, dielectric, with special locking nut.		B	"	1
3465	Type 1712 ...	50 pfd., air dielectric, variable, tropical, $1\frac{7}{32}$ in. \times $\frac{15}{16}$ in. \times $2\frac{1}{32}$ in.		B	"	1
3466	Type 1713 ...	25 pfd., air dielectric, variable, tropical, $1\frac{7}{32}$ in. \times $\frac{15}{16}$ in. \times $1\frac{3}{4}$ in. long.		B	"	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
3467	Type 1714 ...	25 mfd., 35 volts ...		B	each	2
3487	Type 1720 ...	$\frac{1}{2} + \frac{1}{2}$ mfd., 1,500 volts ...		B	"	2
3501	Type 1727 ...	0.000317 mfd., ± 15 per cent., variable, air spaced, 350 volts, D.C. working. Standard spacing shaft, $\frac{1}{4}$ in. \times $1\frac{1}{8}$ in.		B	"	1
3505	Type 1731 ...	20 pfd., variable ...		B	"	1
3517	Type 1743 ...	Variable air dielectric ...		B	"	1
3519	Type 1745 ...	10–11 pfd. min. to 166–172 pfd. max., precision variable, mid log line.		B	"	1
3535	Type 1755 ...	8 + 8 mfd., ± 50 per cent., — 0, 550 volts, D.C. working, waxed cardboard case.		B	"	1
3546	Type 1761 ...	0.0005 mfd., 3 gang, variable, 5 in. \times $1\frac{1}{8}$ in. \times 3 in.		B	"	1
3550	Type 1765 ...	0.0005 mfd., 3 gang, variable, $4\frac{1}{2}$ in. \times $1\frac{1}{8}$ in. \times 3 in.		B	"	1
3551	Type 1766 ...	Balanced, variable, fitted with switch attachment.		B	"	1
3575	Type 1789 ...	100 $\mu\mu$ F., 2 per cent., 500 volts D. C., silvered ceramic, tubular.		B	"	5
3576	Type 1790 ...	0.0005 mfd., ± 5 per cent., 350 volts, D.C. working, moulded mica.		B	"	3
3609	Type 18160001 mfd., space tuning ...		B	"	1
3634	Type 1825 ...	2 + 2 + 4 mfd. ...		B	"	1
3646	Type 1837 ...	0.1 mfd., 650 volts, D.C. working, waxed tubular, end wires.		B	"	2
3659	Type 1845 ...	100 $\mu\mu$ F., 50 K.V. test. H.F. Ceramic. Flanged pot.		B	"	1
3660	Type 1846 ...	250 mfd., electrolytic ...		B	"	1
3661	Type 1847 ...	8 mfd., electrolytic ...		B	"	1
3663	Type 1849 ...	8 + 8 mfd., electrolytic ...		B	"	1
3669	Type 1855 ...	10–3 pfd., variable split stator		B	"	1
3670	Type 1856 ...	2 to 8 pfd., air variable, trimmer		B	"	1
3676	Type 1862 ...	30–100 pfd., screwdriver adjustment.		B	"	2
3690	Type 1865 ...	20 mfd., 50 volts, D.C. working, ± 5 per cent., dry electrolytic, tubular.		B	"	2
3691	Type 1866 ...	1.73 pfd. to 9.8 pfd., trimmer		B	"	1
3694	Type 186905 mfd., ± 10 per cent., 1,000 volts, D.C. working, paper, petroleum jelly impregnated.		B	"	1
3695	Type 1870 ...	0.05 mfd., ± 10 per cent., 5,000 volts, D.C. test, bakelite, mica terminals.		B	"	1
3705	Type 1880 ...	0.001 mfd. ...		B	"	3
3710	Type 1885 ...	0.05 mfd., ± 10 per cent., mica, bakelite case, terminals, 500 volts, D.C. peak, working.		B	"	3
3715	Type 1890 ...	1 mfd. ...		B	"	2
3717	Type 1892 ...	25 pfd., 14,000 volts, working, vacuum type.		B	"	1
3728	Type 1903 ...	50 mfd. ...		B	"	1
3783	Type 1913 ...	0.0005 mfd., variable, with standard spindle.		B	"	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
3786	Type 1916 ...	8 mfd., 600 volts, D.C. peak working, 700 volts, surge, 4½ in. × 1½ in. diam., aluminium case, fixing nuts, and tags below chassis.		B	each	1
3790	Type 1920 ...	0.00016 mfd. variable, 1 gang		B	"	1
3791	Type 1921 ...	0.00016 mfd., variable, 2 gang		B	"	1
3793	Type 1923 ...	8 + 8 mfd., 600 volts, D.C. working, electrolytic, aluminium can, 3 leads.		B	"	1
3841	Type 1930 ...	40 pfd., ± 10 per cent., for 1,800 volts, r.m.s., at 100-600 kc./s + 100 per cent., 1M., 2,000 volts, D.C., 180° F.		B	"	1
3848	Type 1937 ...	4 — 0.0005 mfd., ganged ...		B	"	1
3850	Type 1939 ...	3 to 24 pfd., variable air, ceramic base.		B	"	1
3851	Type 1940 ...	3 to 12.5 pfd., variable air, ceramic base.		B	"	1
3852	Type 1941 ...	3 to 9 pfd., variable air, ceramic base.		B	"	1
3855	Type 1944 ...	2 pfd. min. to 10 pfd. max., variable air.		B	"	1
3856	Type 1945 ...	Each section 3.5 pfd. min. to 20 pfd. max., 3 gang, variable air.		B	"	1
3858	Type 1947 ...	Each section 3.5 pfd. min. to 21 pfd. max., 2 gang, variable air.		B	"	1
3865	Type 1954 ...	500 μμF., variable ...		B	"	1
3873	Type 1962 ...	0.1 μF. + 2 — 0 per cent., 250 volts D. C., mica, rect., bakelite case.		B	"	2
3878	Type 1967 ...	100 pfd., variable, trimmer, air dielectric.		B	"	1
3904	Type 1973 ...	5-35 pfd., air spaced trimmer on bakelite base, with tags.		B	"	1
3908	Type 1977 ...	4-21 pfd., + 5 per cent., trimmer.		B	"	3
3909	Type 1978 ...	45-15 μμF, Trimmer. Screw adjustment.		B	"	1
3940	Type 2009 ...	40 μμF., 2 per cent., 500 volts D.C., silvered ceramic, tubular.		B	"	5
3947	Type 2016 ...	Variable, air-spaced, min. capacity less than 10 pfd., max. capacity between 105 and 120 pfd.		B	"	1
3948	Type 2017 ...	50 pfd., air-spaced trimmer, frequentite base, variable.		B	"	1
3959	Type 2028 ...	30 pfd., max. trimmer ...		B	"	1
3960	Type 2029 ...	2 mfd., electrolytic ...		B	"	2
3994	Type 20500001 mfd., variable ...		B	"	1
3995	Type 2051 ...	50 pfd., variable ...		B	"	1
3996	Type 2052 ...	35 pfd., variable ...		B	"	1
3999	Type 2055 ...	Special series, gap type ...		B	"	1
4000	Type 2056 ...	50-5 μμF., trimmer ...		B	"	3
4010	Type 2062 ...	30 pfd., variable trimmer, ceramic base, ¾ in. × ⅝ in.		B	"	1
4014	Type 2066 ...	50 pfd., air variable, spindle ¼ in. diam. × ⅜ in.		B	"	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
4025	Type 207701 mfd., \pm 10 per cent., 500 volts, D.C. working, paper, moulded tags.		B	each	2
4032	Type 2084 ...	75 pfd. + 75 pfd., + 5 pfd., — 0, variable air dielectric, 2 gang.		B	"	1
4102	Type 21030005 mfd., variable, air dielectric (spring is removed, tension increased, and re-fixed).		B	"	1
4106	Type 21070001 mfd., aluminium vanes, square law transmitting condenser, variable, 1,500 volts, A.C. working, 4 $\frac{1}{4}$ in. \times 3 $\frac{3}{8}$ in. \times 3 in.		B	"	1
4107	Type 21080001 mfd., aluminium vanes, square law transmitting condenser, variable, 1,500 volts, A.C. working, 4 $\frac{1}{4}$ in. \times 3 $\frac{3}{8}$ in. \times 3 in.		B	"	1
4109	Type 2109 ...	35 pfd., variable, double spaced, ceramic base, brass construction.		B	"	1
4114	Type 2113 ...	34 pfd., variable		B	"	1
4265	Type 2209 ...	6.6 pfd., air spaced, 5 spaces, split stator.		B	"	1
4321	Type 2226 ...	75 pfd., \pm 10 per cent., variable air, ceramic base, panel mounting; spindle, $\frac{1}{4}$ in. dia. \times 2 in, knurled $\frac{3}{8}$ in at end, and screwdriver slot.		B	"	1
4334	Type 2239000426 mfd., variable		B	"	1
4340	Type 22451 + .1 mfd., block, rectangular, metal case.		B	"	1
4415	Type 2281 ...	50 mfd., variable, trimmer		B	"	1
4419	Type 2285 ...	16 mfd., 300 volts, D.C. working		B	"	1
4420	Type 22860001 mfd., variable, air, aluminium shield, 1 $\frac{1}{2}$ in. \times 1 $\frac{1}{4}$ in. diam.		B	"	1
4422	Type 2288 ...	50 mfd., \pm 20 per cent., 60 volts, D.C. working, tubular, aluminium case, electrolytic, tags, stud fixing.		B	"	1
4425	Type 2291 ...	4 gang, variable		B	"	1
4474	Type 2301 ...	0.15 μ F., 2 per cent., 375 volts D.C., paper, tubular, Bakelised waxed, 2 $\frac{1}{4}$ in. \times $\frac{9}{16}$ in. dia.		B	"	2
4483	Type 2309 ...	50 mfd., 20 volts, D.C. working, dry electrolytic, tubular, tropical type.		B	"	2
4499	Type 2325 ...	0.0005 mfd., 3 gang, variable		B	"	1
4507	Type 2333 ...	Variable, split stator, precision condenser, with integral induction loop.		B	"	1
4705	Type 2476 ...	Trimmer, 8 pfd., 120 — 200 pfd. max., preset compression.		B	"	1
4751	Type 248315 mfd., \pm 2 per cent., 700 volts, D.C. test, mica.		B	"	2
4772	Type 2504 ...	0.1 μ F., 400 volts D.C., tubular		B	"	2
4773	Type 2505 ...	0.27 mfd., \pm 20 per cent., 400 volts, D.C. working, tubular, end wires.		B	"	2

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
4775	Type 2507 ...	0.047 mfd., \pm 20 per cent., 400 volts, D.C. working, tubular.		B	each	2
4807	Type 2538 ...	Tuning, air dielectric, 1.8 pfd. — 4.8 pfd., spindle length, .812 in.		B	"	1
4810	Type 2541 ...	10 pfd., tubular, neutral shunt condenser.		B	"	2
4811	Type 2542 ...	25 pfd., ceramic, with two plugs fitted.		B	"	1
4812	Type 2543 ...	50 pfd., ceramic, with 2 plugs fitted.		B	"	1
4813	Type 2544 ...	65 pfd. ceramic, with 2 plugs fitted.		B	"	1
4814	Type 2545 ...	100 pfd., \pm 5 per cent., 10 k. volt test, 7.5 k. volt D.C. working, ceramic, flanged pot type, with 2 plugs fitted.		B	"	1
4821	Type 2552 ...	25 μ F., padding ...		B	"	1
4864	Type 2556 ...	0.5 mfd., \pm 20 per cent., 1,000 volts, D.C. working, paper, jelly impregnated, metal case.		B	"	1
4870	Type 2562 ...	50 pfd., variable, air spaced, with ball-bearings.		B	"	1
4875	Type 2567 ...	100 pfd., \pm 10 per cent., 500 volts, D.C. working, ceramic tubular, side wires.		B	"	5
4883	Type 257502 mfd., \pm 10 per cent., 1,000 volts, test, mica, bakelite case, terminals.		B	"	1
4888	Type 2580 ...	0.003 mfd., \pm 15 per cent., 350 volts, D.C. working, moulded mica, tags.		B	"	3
4893	Type 2585 ...	25 pfd., air-spaced, variable ...		B	"	1
4894	Type 2586 ...	5 mfd. + 10 mfd., block, 500 volts, D.C. working, paper, terminals. Overall size, 4 in. long \times 3 $\frac{1}{2}$ in. wide \times 4 $\frac{1}{4}$ in.		B	"	1
4896	Type 2588 ...	10 mfd. + 5 mfd., \pm 5 per cent., 1,500 volts, D.C. working, paper, oil or petroleum jelly filled, tropical.		B	"	1
4914	Type 2605 ...	25 pfd., ceramic, air dielectric...		B	"	1
4917	Type 2607 ...	3-30 pfd., trimmer, air dielectric, 75 volts working at 20° C.		B	"	1
4934	Type 2624 ...	15 — 45 pfd., trimmer ...		B	"	1
4944	Type 2634001 mfd., maximum variable		B	"	2
4947	Type 263700023 mfd., maximum variable		B	"	1
4965	Type 2655 ...	Reaction, variable; min. 9 pfd., \pm 1 pfd.; max. 100 pfd., \pm 5 per cent.; ceramic base.		B	"	1
4966	Type 2656 ...	Trimmer, min. 3 pfd., \pm 1 pfd.; max. 25 pfd., \pm 10 per cent.; ceramic base.		B	"	1
4967	Type 2657 ...	Trimmer, min. 3 pfd., \pm 1 pfd.; max. 25 pfd., \pm 10 per cent.; ceramic base.		B	"	1
4968	Type 2658 ...	Tuning, 3 gang, .00025 mfd. capacity, swing.		B	"	1
4973	Type 2663 ...	4 — 12 pfd., variable, air-spaced, spindle ball-bearing, mounted.		B	"	1

RADIO CHOKES AND CONDENSERS

Ref No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
4979	Type 2669	... Variable, air, tuning with switch, 2 gland washers (4 LU. 26, Dets. 105 and 106), and nuts (4 LU. 26, Det. 107).		B	each	1
5026	Type 2696	... 500 μ F., 10 per cent., 350 volts D.C., silvered mica, protected.		B	..	5
5027	Type 2697	... 0.0016 mfd., 15 per cent., 350 volts D.C., silvered mica, protected.		B	..	5
5028	Type 2698	... 20 — 100 pfd., ceramic trimmer, test voltage 500 at 50 cycles, single plate.		B	..	2
5043	Type 2713	... 100 pfd., variable, $\frac{1}{4}$ in. diam. shaft, slotted end, $\frac{3}{16}$ in. to base of bush.		B	..	1
5151	Type 2743	... 0.05 mfd., \pm 10 per cent., 500 volts, D.C. working, tubular, end wires.		B	..	2
5186	Type 2778	... Variable, air, rotary; fitted to motors, Type 13, Ref. No. 10K/224.		B	..	1
5220	Type 2812	... 3 — 23 pfd., trimmer, $\frac{3}{8}$ in. std. shaft, $\times \frac{1}{4}$ in. diam.		B	..	1
5222	Type 2814	... 0.025 mfd., 1,500 volts, D.C. working, black ebonite, oval section, $1\frac{3}{4}$ in. \times $1\frac{1}{4}$ in., $1\frac{5}{8}$ in. long, with 0 B.A. studs $\frac{3}{8}$ in. long at each end. Metal plate at one end, 5 amp. at 20 Mc./s.		B	..	1
5237	Type 2829	... 16 mfd., 600 volts, D.C. working, electrolytic, metal case, inverted lugs and pillar, solder connections for chassis mounting, tropical.		B	..	1
5238	Type 2830	... 32 mfd., 300 volts, D.C. working, electrolytic, metal case, inverted lugs and pillar, solder connections for chassis mounting, tropical.		B	..	1
5239	Type 2831	... 60 mfd., 200 volts, D.C. working, electrolytic, metal case, inverted lugs and pillar, solder connections for chassis mounting, tropical.		B	..	1
5241	Type 2833	... 0.001 mfd., 10 amp. M.U. R.F. at 500 kc./s.		B	..	1
5247	Type 2839	... 4 mfd., \pm 15 per cent., electrolytic, 500 volts, D.C. peak.		B	..	1
5304	Type 2855	... 2.5 pfd (min.), 5.2 pfd. (max), variable, split stator, air-spaced.		B	..	1
5325	Type 2876	... 0.5 mfd., \pm 10 per cent., 250 volts, D.C. working, tags; tin case, 1 in. \times $\frac{1}{2}$ in. \times $1\frac{1}{8}$ in.; side lugs.		B	..	2
5327	Type 2877	... 40 pfd., 10 per cent., 500 volts D.C., silvered mica, protected.		B	..	5
5329	Type 2879	... 9.5 pfd. max., variable, ceramic, end plates, 3 mounting pillars opposite to operating shaft; friction device at operating shaft.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
5342	Type 2892 ...	Double-ended spindle, ganged, 3½ to 25 pfd.		B	each	1
5414	Type 2920 ...	1 mfd., 500 volts, D.C. test, paper, metal case, 1.62 in. × 0.5 in. × 3.18 in. high; G.P.O. No. 101T.F.; tropical, 160°F.	Army YA.4694	B	..	1
5419	Type 2925 ...	4 mfd., ± 15 per cent., 500 volts, D.C. working, metal case, tags; 1½ in. × 2½ in. × 2½ in.		B	..	1
5420	Type 2926 ...	300 pfd. min.; ring decoupling on aerial and 1st R.F. stage, complete with screws and washers.		B	..	1
5432	Type 2934		B	..	1
5433	Type 2935 ...	0.006 μF., 15 per cent., 350 volts D.C., moulded mica, stacked foil.		B	..	3
5436	Type 2938 ...	0.02 mfd., ± 5 per cent, moulded mica, 750 volts, D.C. working, end wires.		B	..	3
5438	Type 2940		B	..	1
5443	Type 2945		B	..	1
5444	Type 2946 ...	Block, 0.5 + 2 + 2 + 4 mfd....		B	..	1
5467	Type 2968 ...	8 mfd., wet electrolytic ...		B	..	1
5526	Type 2989 ...	30 mfd., min.; max. D.C. peak working voltage, — 30; bake-lised paper tube, drilitic.		B	..	2
5539	Type 3002 ...	32 mfd., 600 volts, D.C. working, metal case, electrolytic, inverted terminals for chassis mounting, tropical finish		B	..	1
5543	Type 3006 ...	1-3 pfd. variable trimmer, air dielectric, spindle, 1½ in. × ¼ in. diam.		B	..	1
5544	Type 3007 ...	4 gang, variable, air - spaced, 9-223 pfd. one section, 7-157 pfd. other 3 sections.		B	..	1
5556	Type 3019 ...	5-35 pfd., ceramic trimmer, variable.		B	..	2
5576	Type 3039 ...	2 + 2 μF., 2,000 volts D.C. ...		B	..	1
5587	Type 3050 ...	Three 450 pfd. variable condensers, triple ganged, and mounted on bakelite base, 8 in. × 1½ in. × ¼ in.		B	..	1
5588	Type 3051 ...	4-12 pfd., variable, air-spaced, single bearing with locking device.		B	..	1
5593	Type 3056 ...	20 pfd., air-spaced, variable, with Hoffman ball-race, frequentite top and bottom plates.		B	..	1
5594	Type 3057 ...	40.8 pfd., air-spaced variable, split stator; spindle, ¾ in. × ¼ in. diam.; 10 spaces, 0.015 in. air gap.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMFNCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.*	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
		<i>cont.</i>				
5599	Type 3062	Variable, 0-0004 mfd., with ceramic mounting base.		B	each	1
5638	Type 3063	32.6 pfd., split stator, air spaced, variable; 8 spaces, 0.015 in. air gap.		B	"	1
5647	Type 3072	0.0001 mfd., variable, air spaced, $\frac{1}{16}$ in. shaft.		B	"	1
5651	Type 3076	0.1 mfd., ± 10 per cent., 5,000 volts, D.C. working, paper, tubular, in metal case, $1\frac{1}{2}$ in. diam. $\times 4\frac{1}{2}$ in., with ebonite cable entry.		B	"	3
5654	Type 3079	100 mfd., $+ 50$ per cent. — 10 per cent., 200 volts, D.C. working, sheet metal case, 3 in. \times 3 in. $\times 4\frac{1}{2}$ in. high, 2 B.A. terminal studs.		B	"	1
5706	Type 3131	Glass, 4 in. max. diam. $\times 4\frac{1}{2}$ in. high, with sheds; capacitance, 0.00035 to 0.000425 mfd.		B	"	1
5772	Type 3159	Trimmer, 4-40 pfd.		B	"	1
5790	Type 3177	25 μ F., 2 per cent., 500 volts D.C., silvered ceramic, tubular.		B	"	5
5800	Type 3187	0.05 mfd., $+ 10$ per cent. — 20 per cent., 1,000 volts, D.C. working, metal case, paper, terminals.		B	"	1
5806	Type 3193	0.0001 mfd., ± 15 per cent., ceramic cup, waxed.		B	"	3
5821	Type 3208	0.1 mfd., ± 20 per cent., 1,000 volts, D.C. working, paper, tubular.		B	"	2
5873	Type 3221	0.01 mfd., 600 volts, D.C. working, paper, tubular, screwed ends, tropical.		B	"	3
5875	Type 3223	Not greater than 4.5 pfd. min., to 7.5-8.5 pfd. max., trimmer with brackets.		B	"	1
5885	Type 3233	3-65 pfd., air variable, tropical finish.		B	"	1
5886	Type 3234	3.8-40 pfd., air variable, D.L.9 moulded base; spindle, $\frac{1}{4}$ in. diam., tropical finish.		B	"	1
5887	Type 3235	4-59.5 pfd., air variable, D.L.9 moulded base; spindle, $\frac{1}{4}$ in. diam., tropical.		B	"	1
5888	Type 3236	8 and 8-8 mfd., 500 volts, D.C. working, negative case.		B	"	1
5895	Type 3243	2 gang air variable; 6 pfd. min., 30 pfd. swing; ceramic base, tropical finish.		B	"	1
5958	Type 3267	0.1 mfd., ± 20 per cent., 1,500 volts, D.C. working, paper, tubular, end wires.		B	"	2
5967	Type 3276	3.5 to 15 pfd., variable air, frequentite base		B	"	1
5969	Type 3278	5-75 mfd., variable; spindle, $\frac{1}{4}$ in. long, including bush, screwdriver slot.			"	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
5980	Type 3289	5 pfd., - 15 pfd., variable air.		B	each	1
5985	Type 3294	23 pfd., ± 20 per cent., 350 volts, D.C. working, stacked foil, mica, foil tags, waxed.		B	"	5
5987	Type 3296	Spindle, $\frac{25}{32}$ in., 0.282 in. flat, 100 - 5.5 μF . per cent., volts D.C.		B	"	1
5991	Type 3300	0.25 mfd., ± 20 per cent., 400 volts, D.C. working, tubular, wire ends.		B	"	2
5997	Type 3306	2 gang, 130 pfd., total, tropical finish.		B	"	1
11006	Type 3315	15 pfd. approx., variable air, 4 moving, 5 fixed vanes; intermediate spacing, $\frac{3}{4}$ in. long spindle.		B	"	1
11061	Type 3332	22.5 pfd. to 346 pfd. total, ± 1 per cent., variable air, split stator, ceramic insulation.		B	"	1
11062	Type 3333	11 pfd. to 135 pfd., ± 1 per cent., variable air, ceramic insulation.		B	"	1
11066	Type 3337	8-8-8 mfd., 400 volts peak working, electrolytic, adjustable fixing clip.		B	"	1
11069	Type 3340	100 pfd., ± 15 per cent., 250 volts, D.C. working.		B	"	3
11071	Type 3341	5 pfd. min., 50 pfd. max., 1,500 volts A.C. test, 500 volts A.C. working, ceramic, variable, trimmer, single.		B	"	1
11097	Type 3351	3-25 pfd., air variable, series gap, ceramic, end plates $2\frac{1}{8}$ in. $\times 2\frac{1}{4}$ in., spindle $\frac{3}{8}$ in. diam. $\times \frac{5}{8}$ in.		B	"	1
11100	Type 3354	16-8 mfd., wet electrolytic, 450 volts, D.C. working.		B	"	1
11188	Type 3391	86 - 8 μF ., variable...		B	"	1
11195	Type 3398	8.8 mfd., 500 volts D.C., electrolytic; rectangular case, $4\frac{7}{16}$ in. $\times 1\frac{3}{8}$ in. $\times 1\frac{1}{8}$ in.		B	"	1
11196	Type 3399	1,000 mfd. ± 100 per cent. - 10 per cent., 8 volts D. C., electrolytic, rectangular case, $4\frac{7}{16}$ in. $\times 1\frac{3}{8}$ in. $\times 1\frac{1}{8}$ in.		B	"	1
11207	Type 3410	140 valve, 2 per cent., 500 volts D.C., silver, mica protected.		B	"	5
11208	Type 3411	425 pf., 2 per cent., 350 volts D.C., silvered mica, protected.		B	"	3
11211	Type 3414	3 pfd. to 10 pfd., air, variable, ceramic base; spindle, $\frac{1}{4}$ in. dia. $\times \frac{3}{4}$ in.		B	"	1
11219	Type 3422	0-540 pfd., variable, ball bearings, solid fixed feet.		B	"	1
11261	Type 3426	2 mfd., ± 25 per cent., 250 volts, D.C. working, tubular, paper, dielectric; 2 leads at one end, $2\frac{1}{2}$ in. long $\times 1\frac{3}{8}$ in. dia.		B	"	1
11277	Type 3441	60 mfd., ± 5 per cent., 350 volts, D.C. working, silvered mica, protected type.		B	"	5

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
11285	Type 3449 ...	125 pfd., 1 per cent, 500 volts D.C., ceramic, tubular.		B	each	6
11287	Type 3451 ...	2 pfd. to 5 pfd., air dielectric, 2 moving, 3 fixed vanes; spindle, 0.155 in. dia.		B	„	1
11288	Type 3452 ...	1.5 pfd. to 3 pfd., variable air, 2 fixed, 3 moving vanes; spindle, 0.155 in. dia. × 1½ in. long.		B	„	1
11397	Type 3466 ...	0.0025 mfd., ± 10 per cent., 350 volts, D.C. working, moulded, silvered mica, wire ends.		B	„	3
11409	Type 3477 ...	100 pfd., ± 20 per cent., 500 volts, D.C. working, mica, waxed.		B	„	5
11461	Type 3490 ...	16 – 16 µF., 350 volts D.C., dry, electrolyte.		B	„	1
11495	Type 3506 ...	3–20 pfd., air, variable ...		B	„	3
11540	Type 3512 ...	0.05 mfd., 9 k. volts, oil-filled, in metal case.		B	„	1
11541	Type 3513 ...	7.5 mfd. – 1.5 mfd. Air variable. Split stator.		B	„	1
11550	Type 3522 ...	4 to 50 pfd., variable, air dielectric, one spindle ⅜ in., other spindle ⅛ in.		B	„	1
11565	Type 3534 ...	500 pfd., ± 5 per cent., 350 volts, D.C. working, silvered mica, waxed, end wires.		B	„	3
11568	Type 3537 ...	13 to 541 pfd., air, variable, metal frame; spindle, ¼ in. dia. × ⅞ in.		B	„	1
11578	Type 3542 ...	4.50 pfd., variable, air-spaced, brass, with conical front bearing and single phosphor bronze ball at rear.		B	„	1
11620	Type 3544 ...	0.04 mfd., ± 15 per cent., 1,000 volts, D.C. working, paper, tubular, end wires.		B	„	2
11622	Type 3546 ...	8 + 8 mfd., 450 volts, dry electrolytic.		B	„	1
11631	Type 3548 ...	500 mfd., + 100 per cent. – 20 per cent., 15 volts D. C. working, cardboard box electrolytic.		B	„	1
11656	Type 3554 ...	0.01 mfd., ± 15 per cent., 3,000 volts, D.C. working, moulded case.		B	„	1
11715	Type 3562 ...	0.02 mfd., 15 per cent., 1,500 volts D.C., paper, tubular.		B	„	2
11718	Type 3564 ...	0.02 mfd., ± 15 per cent., 4,500 volts, D.C. working, 500 volts R.M.S. at 1,500 cycles, A.C. working, cylindrical, dome nut connection, 1½ in. dia. × 4½ in. high.		B	„	1
11744	Type 3575 ...	1.5 pfd. to 7.5 pfd., ceramic trimmer, centre adjusting screw.		B	„	2
11767	Type 3592 ...	0.01 mfd., ± 15 per cent., 3,000 volts, D.C. working, moulded case.		B	„	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
11771	Type 3594 ...	50 $\mu\mu\text{F.}$, ± 5 per cent., 350 volts.		B	each	3
11772	Type 3595 ...	25 pfd., ± 5 per cent., 350 volts D.C. silver, mica protected, size 4.		B	"	—
11780	Type 3601 ...	Variable, 200 pfd., 2,000 volts A.C. test, 20 S.W.G. spindle, $\frac{1}{4}$ in. dia.; $4\frac{1}{4}$ in. \times $3\frac{3}{8}$ in. \times 4 in.		B	"	1
11796	Type 3608 ...	50 mfd., metal case, 275 volts, A.C. working, with waterproof junction box; incorporates discharge resistance.		B	"	1
11804	Type 3614 ...	40 mfd., 40 volts, D.C. working, metal case, electrolytic, inverted terminals for chassis mounting, tropical finish.		B	"	1
11816	Type 3621 ...	8 mfd., 500 volts working, electrolytic, $2\frac{9}{16}$ in. \times 1 in. radius.		B	"	1
11819	Type 3624 ...	Variable special, unspecified ...		B	"	1
11824	Type 3626 ...	0-00025 mfd., ± 5 per cent., moulded, cylindrical, $1\frac{3}{4}$ in. dia. \times $3\frac{1}{2}$ in., with two 2 B.A. terminals; test, 1 amp. at 150 kc/s.		B	"	1
11858	Type 3642 ...	0-25 mfd. + unlimited — 0, 4,000 volts, D.C. working; metal case, $1\frac{3}{4}$ in. \times $3\frac{1}{2}$ in. \times 6 in. high over terminals; tropical.		B	"	1
11870	Type 3648 ...	0 to 40 mfd., variable air, ceramic pillars.		B	"	1
11906	Type 3656 ...	100 + 100 pfd., ± 5 per cent., split stator, variable air dielectric.		B	"	1
11910	Type 3660 ...	One set of rotor and four sets of stator plates, air dielectric, ball bearings, maximum capacity between rotor and any stator 100 pfd.		B	"	1
11921	Type 3668 ...	25 mfd., 50 — 0 per cent., 50 volts D.C., electrolytic, alum. can chassis, working lead connections, flex.		B	"	2
11922	Type 3669 ...	Electrolytic, 10 mfd., 50 volts		B	"	2
11929	Type 3671 ...	38 mfd., 100 volts, A.C. working, dry electrolytic, tubular, insulated case, $1\frac{1}{8}$ in. dia. \times $2\frac{15}{16}$ in.; side wires, $2\frac{11}{16}$ in. long.		B	"	1
11933	Type 3675 ...	150 max., 5 min., air variable		B	"	—
11988	Type 3706 ...	0-01 pfd., ± 15 per cent., 5,000 volts, D.C. working end stud terminals.		B	"	1
11992	Type 3707 ..	5 pfd. to 50 pfd., ceramic trimmer, centre screw adjustment.		B	"	3
12020	Type 3719 ...	16 + 16 mfd., 450 volts D.C., 4 terminals, dry electrolytic, surge proof, metal cased, rectangular.		B	"	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
12032	Type 3722 ...	6 pfd., variable, 1 fixed and 1 moving vane, micalex block, angle bracket fixing.		B	each	1
12040	Type 3727 ...	0.1 mfd., \pm 10 per cent., 10 k. volts D.C., metal-cased block, oil immersed, paper dielectric.		B	"	1
12055	Type 3736 ...	1 to 7 pfd., variable, preset, lockable, tubular, screw adjustment.		B	"	1
12065	Type 3741 ...	4.5 to 10 pfd., air variable, metal frame; spindle, $\frac{1}{4}$ in. dia. \times 0.7 in., with hole tapped for screw.		B	"	1
12114	Type 3782 ...	40 μ F \pm 5 per cent., 350 volts, D.C. Silvered mica. Protected.		B	"	5
12138	Type 3790 ...	3 to 30 mfd., trimmer with mounting plate, 75 volts D.C. working, air dielectric.		B	"	2
12176	Type 3813 ...	0.007 mfd. \pm 5 per cent. Silvered mica. Protected.		B	"	3
12177	Type 3814 ...	0.01 mfd., \pm 5 per cent. Silvered mica. Protected.		B	"	3
12180	Type 3817 ...	Variable, split stator, precision condenser with integral induction loop.		B	"	1
12182	Type 3818 ...	3.8 to approx. 35 pfd., air variable, frequentite base, $\frac{15}{16}$ in. \times $1\frac{1}{2}$ in., screwdriver adjustment.		B	"	1
12185	Type 3819 ...	0.25 + 0.25 mfd., 20 per cent., volts D.C. 3,000, paper, tubular, cardboard case, $2\frac{3}{8}$ in. dia. \times 5 in. terminals.		B	"	1
12204	Type 3823 ...	Variable air		B	"	1
12205	Type 3824 ...	Variable air		B	"	1
12226	Type 3826 ...	115 μ F., 2 per cent., 350 volts D.C., silvered mica, protected.		B	"	3
12229	Type 3829 ...	100 pfd., \pm 10 per cent., 500 volts, R.M.S. test, trimmer, air dielectric, ceramic base, screwdriver slot.		B	"	2
12246	Type 3839 ...	3 sections, each 7 pfd. to 23 pfd., variable, air dielectric, midget type vanes.		B	"	1
12265	Type 3846 ...	30 pfd., variable, air		B	"	1
12266	Type 3847 ...	20 pfd., fixed, air dielectric ...		B	"	1
12267	Type 3848 ...	100 pfd. + 100 pfd., circular metal plates and mica discs.		B	"	1
12296	Type 3852		B	"	1
12289	Type 3854 ...	40 pfd. + 40 pfd., variable ...		B	"	1
12308	Type 3856 ...	20—3.5 μ F., variable air, 3 gang.		B	"	1
12354	Type 3897 ...	1 mfd., \pm 15 per cent., 1,000 volts, D.C. working, 1,500 volts test; $2\frac{3}{8}$ in. \times 2 in. \times $1\frac{1}{4}$ in. rectangular metal; fixing feet, moulded, terminals		B	"	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
12384	Type 3910 ...	25 mfd., 50 volts, D.C. Electrolytic.		B	each	1
12392	Type 3916 ...	0.001 μ F., \pm 5 per cent., 500 volts, D.C. working, ceramic tube, protected type, 14 mm. \times 60 mm. long.		B	;	2
12394	Type 3918 ...	2-gang variable, 168 μ F. max. each section (6 μ F. min. each section).		B	..	1
12406	Type 3926 ...	0.5 mmF. to 8 mmF., variable, 2 plates, 1 fixed to micalex base, 1 suspended on flexible strip.		B	..	1
12425	Type 3939 ...	3 to 25 pfd., air, variable ...		B	..	1
12436	Type 3940 ...	100 pfd., air, variable ...		B	..	1
12443	Type 3944 ...	Variable, 0.0005 μ F. ...		B	..	1
12444	Type 3945 ...	2-gang, variable, 0.0005 μ F. ...		B	..	1
12449	Type 3947		B	..	1
12452	Type 3950 ...	0.1 μ F., \pm 10 per cent., in insulating tube, 500 volts working at 60° C., 400 volts at 70° C.		B	..	2
12462	Type 3953 ...	0.06 mfd., \pm 2 per cent., 1,000 volts test, silvered mica, metal case, screw tags.		B	..	2
12463	Type 3954 ...	0.03 mF., \pm 2 per cent., 1,000 volts test, silvered mica, metal case.		B	..	2
12468	Type 3955 ...	8 + 8 μ F., 450 volts, D.C. working, electrolytic.		B	..	1
12470	Type 3956 ...	40 + 16 + 8 mfd., 320 volts, A.C. working, paper, oil immersed.		B	..	1
12480	Type 3958 ...	0.01 + 0.01 μ F., \pm 10 per cent., 750 W. Block, tubular.		B	..	1
12525	Type 3993 ...	0.5 μ F. \pm 20 per cent., 1,000 W. Metal case.		B	..	1
12582	Type 4019 ...	10 mfd., \pm 20 per cent., 250 volts, D.C. working, in rectangular metal case; terminals.		B	..	1
12605	Type 4020 ...	100 μ F., variable air, spindle, 0.25 in. \times 0.64 in. dia.		B	..	1
12620	Type 4027 ...	1 μ F., 250 volts, D.C. working, paper, tubular, metal case, 0.62 in. dia. \times 1 in., self sealing, wires, tropical.		B	..	2
12649	Type 4031 ...	One set of rotor plates (2 per set) and 4 sets of stator plates (3 per set), air dielectric, ball bearings, maximum capacity between rotor and any stator 100 μ F.		B	..	1
12653	Type 4033 ...	5.7 μ F. min., 13.5 μ F. max., air variable, ceramic installation, single gang, in metal frame, approx. 1.53 in. \times 1.15 in. \times 1.06 in. Spindle, 0.92 in.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
12654	Type 4034 ...	2.5 $\mu\text{F.}$ min., 18.9 $\mu\text{F.}$ max., air variable, split stator, ceramic insulation, in metal frame, approx. 1.38 in. \times 1.61 in. \times 1.69 in. Spindle, 0.63 in.		B	each	1
12684	Type 4047 ...	8 $\mu\text{F.}$, 350 volts peak working, electrolytic, aluminium case, 3 $\frac{3}{8}$ in. \times 1 $\frac{1}{8}$ in. dia.		B	..	1
12690	Type 4052 ...	500 $\mu\text{F.}$, 20 per cent., 350 W., variable mica		B	..	1
12698	Type 4057 ...	0.25 $\mu\text{F.}$, \pm 15 per cent., rectangular metal case, base mounting, moulded terminals, oil impregnated and immersed paper dielectric, 9 kv., D. C. working.		B	..	1
12709	Type 4064 ...	150 pfd., 4,000 volts D.C., transmitter, 40 A. at 100 mc/s.		B	..	1
12731	Type 4066 ...	6.50 mmF., variable; spindle, $\frac{1}{4}$ in. dia. \times $\frac{5}{16}$ in. free length.		B	..	1
12732	Type 4067 ...	6.50 mmF., variable; spindle, $\frac{1}{4}$ in. dia. \times $\frac{5}{16}$ in. free length.		B	..	1
12733	Type 4068 ...	0.003-0.00053 $\mu\text{F.}$, trimmer, mica, screw adjustment, 1.06 in. \times 0.87 in.		B	..	2
12780	Type 4083 ...	50 $\mu\text{F.}$, + 50 per cent. - 20 per cent., 12 volts, dry electrolytic.		B	..	2
12811	Type 4089 ...	1 $\mu\text{F.}$, + 10 per cent. - 5 per cent., 375 volts, D.C. working, tubular, paper, one hole fixing, tags.		B	..	2
12836	Type 4090 ...	Variable, 2 section, 24.5 $\mu\text{F.}$ each section.		B	..	1
12845	Type 4094 ...	30 pfd., \pm 20 per cent., 500 volts, D.C., silvered ceramic disc.		B	..	5
12863	Type 4106 ...	0.02 $\mu\text{F.}$, 20 per cent., 5,000 W., paper, tubular.		B	..	2
12889	Type 4114 ...	Variable, 2-section, 40.8 $\mu\text{F.}$, each section.		B	..	1
12891	Type 4116 ...	7 $\mu\text{F.}$, trimmer		A	..	1
12892	Type 4117 ...	75 $\mu\text{F.}$, trimmer		A	..	1
12896	Type 4121 ...	5 $\mu\text{F.}$ max., single plate trimmer.		B	..	1
12897	Type 4122 ...	75 $\mu\text{F.}$, single plate trimmer.		B	..	1
12898	Type 4123 ...	75 $\mu\text{F.}$, single plate trimmer.		B	..	1
12915	Type 4131 ...	Split stator, 2-gang variable, 3.3 $\mu\text{F.}$ to 27.8 $\mu\text{F.}$ per section; 3 fixed, 4 moving plates per section; air gap, 0.015 in.		B	..	1
12964	Type 4148 ...	100 $\mu\text{F.}$, mica, circular ...		B	..	3
12992	Type 4170 ...	17 mfd. min., 510 mfd. max., 3-gang, variable, air spaced.		B	..	1
13038	Type 4191 ...	8 $\mu\text{F.}$, + 50 per cent. - 20 per cent., 500 volts working; electrolytic metal tubular case, 2 $\frac{3}{4}$ in. high \times 1 $\frac{1}{8}$ in. dia., tags.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
13039	Type 4192 ...	2 mfd., + 50 per cent. — 20 per cent., metal tubular case, 350 volts, D.C. working, tags, electrolytic.		B	each	2
13042	Type 4193 ...	0.004 μ F. + 0.004 μ F. + 0.004 μ F., H.F. oil filled, 8 in. long \times 6 in. wide \times 8 in. high approx.		B	..	1
13044	Type 4194 ...	1,000 μ F., rectangular, 7 $\frac{3}{16}$ in. \times 2 $\frac{1}{2}$ in. \times 2 $\frac{1}{2}$ in. overall, $\frac{3}{8}$ in. spindle.		B	..	1
13060	Type 4204 ...	4 μ F., + 50 per cent. — 20 per cent., aluminium cased, electrolytic, 350 volts, D.C. peak voltage, stud fixing. Dimensions, 2 $\frac{3}{4}$ in. \times 1 in.		B	..	2
13061	Type 4205 ...	25 μ F., + 50 per cent. — 20 per cent., 25 volts peak, D.C. working, aluminium cased electrolytic, stud fixing. Dimensions, 1 $\frac{3}{4}$ in. \times 1 in.		B	..	2
13066	Type 4210 ...	3 μ F.—10 μ F., air variable.		B	..	1
13083	Type 4218 ...	30 μ F. Variable air. Spindle tapped 6 B.A.		B	..	1
13088	Type 4221 ...	400 μ F., \pm 15 per cent., 750 volts working, stacked foil mica, tag ends.		B	..	1
13094	Type 4223 ...	8 mF., \pm 20 per cent., 1,000 volts, D.C. working (140° F.), paper, block metal case, upright mounting.		B	..	1
13149	Type 4231 ...	3.5 μ F.—25 μ F., 3 moving and 4 fixed valves; spindle, 0.25 in. dia. \times 2.1 in. long; variable, air.		B	..	1
13165	Type 4233 ...	2 mfd., + 50 per cent. — 20 per cent., 500 W. Dry electrolytic. Reversible. 2 $\frac{3}{8}$ in. \times 1 $\frac{3}{8}$ in. dia.		B	..	1
13187	Type 4245 ...	Variable, 1,450 μ F. to 2,000 μ F., mica on ceramic base, 1 $\frac{1}{2}$ in. \times 1 in.		B	..	1
13260	Type 4280 ...	4 mfd., + 50 per cent. — 20 per cent., 350 volts, D.C. working, dry electrolytic in aluminium can.		B	..	1
13285	Type 4298 ...	2 mfd, 50 — 20 per cent., 250 volts D.C., electrolytic, al. can.		B	..	1
13306	Type 4319 ...	5–75 μ F., variable; spindle, $\frac{1}{4}$ in. dia. \times $\frac{3}{8}$ in. free length.		B	..	1
13308	Type 4321 ...	450 μ F., ceramic, 100 volts R.M.S. H.F. at 20° C. zero temp. co-eff.		B	..	2
13324	Type 4333 ...	9.5 μ F., 0.5 μ F. per cent., 2,000 W., ceramic special, within castor oil filled neschrine bag clamped between bracket on flat mounting plate.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
13325	Type 4334 ...	19 $\mu\text{F.}$, — 5 $\mu\text{F.}$, 3,000 W. Ceramic. Special. In castor oil filled neocrine bag; clamped between bracket on flat mounting plate.		B	each	1
13326	Type 4335 ...	0.1 mfd., 20 per cent., 100 volts D.C., paper, rect., metal case.		B	„	1
13331	Type 4336 ...	7.5 $\mu\text{F.}$, 275 W., A.C. Metal case.		B	„	1
13333	Type 4338 ...	100 pfd. \pm 2 per cent., 500 volts D.C., ceramic, tubular, side wires. Similar to 10C/3988 but tropical waxed dipped.		B	„	5
13370	Type 4358 ...	3 to 20 p.f.d., air dielectric trimmer.		B	„	1
13374	Type 4359 ...	500 $\mu\text{F.}$, variable air dielectric		B	„	1
13392	Type 4366 ...	1½–4 $\mu\text{F.}$, split stator, variable. Air gap, 0.045 in; spindle, ¼ in. dia. \times 0.78 in.		B	„	1
13408	Type 4369 ...	4 $\mu\text{F.}$, + 50 per cent — 20 per cent., dry electrolytic, 350 volts, D.C. working. Tropical to K.110.		B	„	1
13409	Type 4370 ...	25 $\mu\text{F.}$, + 50 per cent. — 20 per cent., dry electrolytic, 25 volts, D.C. working. Tropical to K.110.		B	„	1
13433	Type 4382		B	„	1
13440	Type 4383 ...	6 to 16 $\mu\text{F.}$, single gang, variable; Tufnol spindle, 1½ in. dia., 2½ in. long between top and bottom plates. Shorted.		B	„	1
13456	Type 4395 ...	0.001 $\mu\text{F.}$, 8 amps., 550/1,500 Kc/s.		B	„	1
13457	Type 4396 ...	0.006 $\mu\text{F.}$ \pm 15 per cent. Paper jelly, rectangular bakelite case. 7 amps. at 650 Kc/s.		B	„	1
13493	Type 4410 ...	35 $\mu\text{F.}$ max., 13 $\mu\text{F.}$ min., variable air. Spindle, 1½ in. \times ¾ in. dia.		B	„	1
13499	Type 4415 ...	Variable air. 483 $\mu\text{F.}$ Swing, ganged.		B	„	1
13500	Type 4416 ...	Variable air. 483 $\mu\text{F.}$ Swing, ganged.		B	„	1
13506	Type 4420 ...	100 $\mu\text{F.}$ Ceramic transmitting. Negative temperature co-efficient.		B	„	3
13507	Type 4421 ...	50 $\mu\text{F.}$, transmitting — VE, temp. co-efficient.		B	„	3
13508	Type 4422 ...	20 $\mu\text{F.}$, transmitter		B	„	3
13529	Type 4424 ...	40 pfd. — 8 pfd. Variable air		B	„	1
13530	Type 4425 ...	8 $\mu\text{F.}$, \pm 10 per cent., tested at 1,000 volts, 50 cycles A.C.; silvered ceramic temperature co-efficient $750 \times 10^{-6} \pm 10$ per cent. Power factor better (less) than 8×10^{-4} . Wire ends.		B	„	5

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
13554	Type 4431 ...	8 μ F — 15 per cent. + 100 per cent., 450 volts, D.C. working, electrolytic; tropical; can, $2\frac{1}{2}$ in. \times 2 in.; base overall, $2\frac{3}{4}$ in. \times $1\frac{1}{8}$ in.		B	each	1
13556	Type 4432 ...	0.01 μ μ F — 10 μ μ F. Air variable. $2\frac{3}{32}$ in. square, bakelite dielectric spindle, 6 mm. dia.		B	..	1
13567	Type 4436 ...	8 mfd., + 50 per cent. — 20 per cent., 500 volts, D.C. Electrolytic. In screw type can, $1\frac{3}{8}$ in. dia. \times $3\frac{1}{2}$ in. long.		B	..	1
13570	Type 4439 ...	32 + 32 μ F., + 50 per cent. — 20 per cent., 35 volts, D. C. Sprayed gauge, non-tropical, on high ripple.		B	..	1
13577	Type 4443 ...	50 — 5 mfd. Air variable. Mica dielectric on ceramic base, $\frac{13}{16}$ in. \times $\frac{9}{16}$ in. \times 1 in.; full open, $1\frac{3}{16}$ in. long over connecting tag.		B	..	1
13590	Type 4449 ...	1 μ F., + 50 per cent. — 20 per cent., 150 volts working, dry electrolytic in aluminium can, $\frac{3}{4}$ in. dia., $2\frac{1}{4}$ in. long, with M.A. fixing stud one end.		B	..	1
13599	Type 4451 ...	Variable, max. 13.5 pfd., min. 3.5 pfd., trimmer, ceramic.		B	..	1
13600	Type 4452 ...	6.5 — 2.5 pfd. Variable air, ceramic brass, 2 fixed vanes, 2 moving vanes. Spindle, 0.2 in. dia. \times 0.838 in.		B	..	1
13601	Type 4453 ...	75 — 7 pfd. Variable air, 2 gang. Spindle, 0.25 in. dia. \times 0.465 in.		B	..	1
13602	Type 4454 ...	75 — 7 pfd. Variable air. Single gang. Spindle, 0.2 in. dia. \times 0.465 in. at each end.		B	..	1
13624	Type 4457 ...	2 μ F., 20 per cent. D.C. working, 350 volts at 10 per cent., 425 volts at 60 per cent. Electrolytic.		B	..	1
13625	Type 4458 ...	— 0.004 μ μ F. + 0.004 μ μ F. + 0.004 μ μ F. + 0.004 μ μ F. block. Oil filled. Height $8\frac{7}{8}$ in. \times $7\frac{1}{2}$ in. wide \times 11 in. long, base $9\frac{1}{2}$ in. long, top $4\frac{1}{2}$ in.; fixing centres, \times 10 in., $\frac{1}{4}$ in. Whitworth terminals, 1 in. high.		B	..	1
13626	Type 4459 ...	0.0005 + 0.0005 μ F. Variable ganged.		B	..	1
13646	Type 4472 ...	200 μ F. + 50 — 20 per cent., 100 volts, D.C. Dry electrolytic. In rectangular metal case.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
13647	Type 4473 ...	Variable air. 2 cylinder—1 fixed, 1 moving; preset variable inolex base centre screw adjustment, Ref. No. 10C/10009, modified to increase the capacity unspecified.		B	each	1
13649	Type 4475 ...	30 μ F., 100 volts D.C. Dry electrolytic.		B	..	1
13650	Type 4476 ...	25 μ F., + 50 — 0 per cent., 50 volts, D.C. Dry electrolytic.		B	..	2
13651	Type 4477 ...	50 μ F., + 50 — 0 per cent., 150 volts, D.C. Dry electrolytic.		B	..	1
13665	Type 4480 ...	0.1 mfd., \pm 20 per cent., 250 D.C. working, rect. metal inverted case.		B	..	1
13681	Type 4488 ...	38 max., 6.5 min., air variable, split stator.		B	..	1
13718	Type 4496 ...	4 + 10 mfd., 250 R.M.S., metal block.		B	..	1
13723	Type 4498 ...	14 + 15, 250 R.M.S., rect., metal cased, block.		B	..	1
13727	Type 4499 ...	46 μ μ F. Mica. Metal clamp, fixing centres, 4 $\frac{3}{8}$ in.		B	..	1
13733	Type 4500 ...	0.1 μ F., 20 per cent., 750 D.C. working, rect., metal cased.		B	..	1
13749	Type 4504 ...	30 pfd. — 6 pfd Air variable. 2 $\frac{1}{8}$ in. between top and bottom plates, $\frac{3}{8}$ in. dia. tufnol spindle.		B	..	1
13790	Type 4513 ...	500 mfd., 20 per cent., 500 D.C. working, cylindrical, alum.		B	..	1
13792	Type 4515 ...	0.1 mfd. 10,000 volts, D.C. Paper metal case.		B	..	1
13793	Type 4516 ...	2.25 mfd., + 20 per cent. — 0, 2,500 volts D.C. Paper metal case. Oil immersed, tank type, on four wheels.		B	..	1
13794	Type 4517 ...	50 — 6 pfd max., 50 — 6 pfd. min. Variable air, 6 — 50 μ μ F. Each section 2 gang.		B	..	1
13801	Type 4518 ...	170 max., 10 pfd. min., air variable.		B	..	1
13815	Type 4531 ...	450 + 450 pfd., variable air, 2 gang.		B	..	1
13818	Type 4533 ...	9.6 μ μ F. max., 3 μ μ F. min., variable air, split stator. Ceramic end plates.		B	..	1
13833	Type 4535 ..	500 μ μ F. Variable air ...		B	..	1
13839	Type 4538 ...	21 μ μ F. max., 3.5 μ μ F. min. Variable, 2 gang. Modification of Condenser 10C/3858 by new bearings and filling of spindle.		B	..	1
13844	Type 4543 ...	500 μ μ F. max. Variable, solid dielectric		B	..	1
13847	Type 4544 ...	50 μ μ F. — 3.8 μ μ F. Variable air. 6 fixed vanes, 7 moving. Air gap, 0.015 in. Steel end plate and bar. Brass shaft, with steel ball bearings. Silver plate finish. Low loss ceramic.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
13859	Type 4547 ...	50 $\mu\text{F.}$ — 6 $\mu\text{F.}$. Variable air, 2 gang. Fixed plate, 2 in. \times 6 in.; moving plate, 2 in. \times 7 in. Air gap, 0.015 in.		B	each	1
13874	Type 4554 ...	15 $\mu\text{F.}$, 380 volts. Continuous paper, oil immersed.		B	..	1
13876	Type 4556 ...	20 $\mu\text{F.}$, 380 volts. Intermittent. Paper, oil immersed.		B	..	1
13881	Type 4557 ...	22.5 $\mu\text{F.}$, 380 volts, intermittent. Paper, oil immersed.		B	..	1
13882	Type 4558 ...	27.8 $\mu\text{F.}$, 380 volts, intermittent. Paper, oil immersed.		B	..	1
13899	Type 4565 ...	8 $\mu\text{F.}$, 440 volts, A.C. Metal case		B	..	1
13929	Type 4575 ...	Air, variable, 2 gang		B	..	1
13930	Type 4576 ...	Air, variable, 3 gang		B	..	1
13931	Type 4577 ...	Air, variable, 3 gang		B	..	1
13950	Type 4581 ...	32 mfd. + 50 — 20 per cent., 320 volts. Dry electrolytic.		B	..	1
13953	Type 4583 ...	140 + 140 pfd. Ceramic trimmer. Dual mica trimming condenser on ceramic base.		B	..	1
13984	Type 4597 ...	Air, variable, 3 gang, including scale calibrated to suit R.F. unit.		B	..	1
14000	Type 4603 ...	500 $\mu\text{F.}$, \pm 15 per cent. Variable midget. Low loss, 1 $\frac{1}{2}$ in. dia. shaft, with one hole fixing.		B	..	1
14006	Type 4609 ...	7 mfd., 500 volts D.C. Power factor, wax.		B	..	1
14007	Type 4610 ...	0.05 mfd., 100 ohms. D.C. resistance in fuse fitted all in a brass tube, 1 $\frac{1}{2}$ in. \times $\frac{3}{16}$ in.		B	..	3
14044	Type 4618 ...	50 pfd. Air, variable		B	..	1
14045	Type 4619 ...	25 pfd. Air, variable		B	..	1
14046	Type 4620 ...	25 pfd. Air, variable		B	..	1
14068	Type 4627 ...	50 + 50 pfd. Air, variable. Twin gang, series gap.		B	..	1
14073	Type 4632 ...	520 pfd. Air, variable, 2 ganged		B	..	1
14078	Type 4633 ...	100 mfd., 50 D.C. working. Dry elect.		B	..	1
14079	Type 4634 ...	10mfd., 50 D.C. working. Dry elect.		B	..	2
14124	Type 4647 ...	0.0021 mfd., \pm 1 per cent., 1,000 volts, test. Silvered mica. In Calet case.		B	..	3
14204	Type 4685 ...	32 $\mu\text{F.}$, 500 volts D.C. Electrolytic.		B	..	1
14216	Type 4689 ...	20 pfd., 6,000 volts. Special condenser plate in polystyrene moulding, with 2 additional plates added externally, 1 each side and connected together. Overall dimensions, 2 in. \times 1 $\frac{1}{4}$ in. \times $\frac{3}{8}$ in., excluding connecting lug.		B	..	1
14220	Type 4692 ...	9.6 — 3 pfd. Air, variable ...		B	..	1.
14230	Type 4698 ...	50 + 50 mfd., 260 volts, R.M.S.; 550 volts, R.M.S. P.K. Paper block.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
14232	Type 4699 ...	320 pfd., ± 10 per cent. Air fixed. Special. Silvered ceramic tube complete with threaded bush and two $\frac{5}{16}$ in. B.S.F. (Fixed.)		B	each	1
14273	Type 4710 ...	750 $\mu\mu\text{F.}$, 10 per cent., 350 volts. Silvered, mica protected.		B	..	3
14301	Type 4714 ...	Variable, 2 gang. Air dielectric.		B	..	1
14389	Type 4738 ...	0.001 — 0.0005 mfd. Variable, mica. On ceramic case, $1\frac{1}{2}$ in. \times 1 in.		B	..	1
14392	Type 4741 ...	890 pfd. ± 10 per cent., 350 volts D.C. Silvered mica, protected.		B	..	3
14395	Type 4744 ...	30 mfd., 270 A.C. Electrolytic. Non-polarised electrolytic.		B	..	1
14428	Type 4766 ...	0.02 mfd., 500 D.C. working. Fixed mica.		B	..	2
14432	Type 4770 ...	950 $\mu\text{F.}$, 5 per cent., 10,000 D.C. working. 750 V.H.F. Silvered ceramic tag. Temp. co-efficient. 600 parts.		B	..	3
14444	Type 4779 ...	0.5 $\mu\text{F.}$, 20 per cent., 500 D.C. working. Tubular metal case, $2\frac{1}{4}$ in. long \times 1 in. dia. paper dielectric. Single fixing stud, 0 B.A. and $\frac{1}{2}$ in. long.		B	..	1
14446	Type 4781 ...	0.5 mfd. ± 20 per cent., 350 volts, D.C. Metal tube.		B	..	2
14447	Type 4782 ...	1 mfd. ± 20 per cent., 250 volts, D.C. Metal tube.		B	..	1
14448	Type 4783 ...	0.25 mfd. ± 20 per cent., 500 volts D.C. Metal tube.		B	..	2
14449	Type 4784 ...	2 mfd., 20 per cent., 250 D.C. working. Rect. metal case.		B	..	1
14454	Type 4786 ...	4 mfd., 20 per cent., 1,200 D.C. working. Paper, rect. Metal, $4\frac{1}{16}$ in. \times $3\frac{3}{8}$ in. \times $2\frac{3}{8}$ in.		B	..	1
14455	Type 4787 ...	2 mfd., 20 per cent., 800 D.C. working. Paper, rect. Metal, $4\frac{1}{16}$ in. \times $1\frac{7}{8}$ in. \times $1\frac{1}{2}$ in.		B	..	—
14460	Type 4792 ...	20 pfd., 500 D.C. working. Ceramic trimmer. Temperature co-efficient, 0–500 part. Size 34, 8 mm. \times 22.4 mm. \times 10 mm.		B	..	1
14468	Type 4800 ...	4 mfd. + 50 — 20 per cent., 375 volts, D.C. Electrolytic.		B	..	1
14481	Type 4804 ...	500 pfd. Air, variable ...		B	..	2
14483	Type 4805 ...	Variable thermal. Assembly of plate, $2\frac{1}{2}$ in. \times $1\frac{1}{2}$ in., and bi-metal strip.		B	..	1
14486	Type 4808 ...	15 pfd. Ceramic trimmer ...		B	..	1
14489	Type 4810 ...	100 pfd. Air, variable. Stator mounting.		B	..	1
14490	Type 4816 ...	0.25 mfd. ± 20 per cent., 350 volts, D.C. Tubular paper.		B		2
14508	Type 4823 ...	500 pfd., 5 per cent., 1,800 volts R.M.S. Mica, rect. moulded.		B	..	3
14523	Type 4831 ...	500 pfd. Variable, air, 4 gangs		B	..	1
14524	Type 4832 ...	50 pfd. Variable, air. Trimmer		B	..	1
14548	Type 4841 ...	27.8 — 3.3 pfd. Air, variable. Split stator.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
14549	Type 4842 ...	27.8 max., 3.3 min. Air, variable. Differential.		B	each	1
14550	Type 4843 ...	9.6 max., 3 min. Variable air. Differential type.		B	..	1
14554	Type 4844 ...	20 pfd. \pm 10 per cent., 750 volts, D.C. Silvered mica, protected.		B	..	5
14565	Type 4851 ...	470 pfd. \pm 10 per cent., 350 volts, D.C. Silvered mica, protected.		B	..	3
14566	Type 4852 ...	270 pfd. \pm 10 per cent., 350 volts, D.C. Silvered mica protected.		B	..	3
14567	Type 4853 ...	180 pfd. \pm 10 per cent., 350 volts, D.C. Silvered mica protected.		B	..	5
14569	Type 4855 ...	170 — 4.5 pfd., 1,000 volts. Variable, air. 12 fixed plates, 11 Rota plates, 22 positions between plates.		B	..	1
14570	Type 4856 ...	20–80 pfd. Ceramic. Screw adjustment. Base, 25 mm. \times 31.5 mm.		B	..	1
14590	Type 4867 ...	2 mfd. \pm 10 per cent., 1,500 volts. Paper. Rectangular metal case. Vaseline impregnated.		B	..	1
14601	Type 4869 ...	444 pfd. Air, variable, 2 gangs		B	..	1
14602	Type 4870 ...	500 pfd. Air, variable, 2 gangs		B	..	1
14603	Type 4871 ...	500 pfd. Air, variable, 3 gangs		B	..	1
14604	Type 4872 ...	0.01 mfd. \pm 20 per cent., 400 volts, D.C. Paper, tubular, moulded case.		B	..	3
14605	Type 4873 ...	1 mfd. \pm 20 per cent., 400 volts, D.C. Paper, tubular, moulded case.		B	..	1
14607	Type 4875 ...	200 pfd. \pm 20 per cent., 500 volts, D.C. Ceramic disc.		B	..	3
14623	Type 4885 ...	0.25 mfd. \pm 20 per cent., 1,200 volts, D.C. Paper, metal case, inverted, 2 $\frac{3}{8}$ in. \times 1 $\frac{3}{4}$ in. \times 1 $\frac{3}{4}$ in.; inverted tags.		B	..	1
14625	Type 4887 ...	1 mfd. \pm 20 per cent., 1,200 volts, D.C. Paper, metal case, inverted, 2 $\frac{3}{8}$ in. \times 1 $\frac{3}{4}$ in. \times 4 $\frac{1}{2}$ in.; inverted tags.		B	..	—
14626	Type 4888 ...	12 mfd. + 50 per cent. — 20 per cent., 50 volts, D.C. Electrolytic, dry.		B	..	2
14627	Type 4889 ...	0.5 mfd. \pm 20 per cent., 250 volts, D.C. Paper, metal case, upright, 2 $\frac{1}{2}$ in. \times 1 $\frac{3}{4}$ in. \times $\frac{3}{4}$ in.		B	..	1
14628	Type 4890 ...	0.5 mfd. \pm 20 per cent., 400 volts, D.C. Paper, metal case, upright, 2 $\frac{1}{2}$ in. \times 2 in. \times $\frac{3}{4}$ in.		B	..	1
14629	Type 4891 ...	1 mfd. \pm 20 per cent., 400 volts, D.C. Paper, metal case, upright, 2 $\frac{1}{2}$ in. \times 2 in. \times $\frac{3}{4}$ in.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
14630	Type 4892 ...	2 mfd. \pm 20 per cent., 400 volts, D.C. Paper, rectangular metal case, upright, $2\frac{1}{2}$ in. \times $2\frac{1}{8}$ in. \times $1\frac{1}{4}$ in.		B	each	1
14631	Type 4893 ...	4 mfd. \pm 20 per cent.; 600 volts, D.C. Paper, metal case, inverted. Inverted mounting.		B	..	1
14659	Type 4902 ...	2,000 pfd. \pm 20 per cent., 350 volts, D.C. Moulded mica, stacked foil.		B	..	5
14676	Type 4909 ...	16 mfd. + 50 — 20 per cent, 500 volts, D.C. Electrolytic, aluminium can, $4\frac{1}{2}$ in. \times $1\frac{3}{8}$ in. dia. Aluminium bush.		B	..	1
14678	Type 4911 ...	2,000 pfd. \pm 20 per cent., 350 volts, D.C. Moulded mica, stacked foil.		B	..	3
14692	Type 4922 ...	0.00105 valve, 10 per cent., 350 volts D.C. working. Silver mica, protected.		B	..	3
14693	Type 4923 ...	1,600 pfd., 5 per cent., 10,000 D. C. working. Ceramic flanged pot.		B	..	1
14696	Type 4924 ...	0.01 mfd. \pm 15 per cent., 350 volts, D.C. Silver mica, moulded.		B	..	3
14697	Type 4925 ...	25 mfd. + 50 — 20 per cent., 25 volts, D.C. Electrolytic.		B	..	2
14705	Type 4931 ...	8 mfd. + 50 — 20 per cent., 350 volts, D.C., at 60° C. Electrolytic. $2\frac{1}{4}$ in. \times $\frac{3}{4}$ in.		B	..	2
14706	Type 4932 ...	100 pfd. \pm 25 per cent., 500 volts, D.C. Ceramic cup.		B	..	5
14750	Type 4950 ...	0.02 mfd. \pm 20 per cent., 750 volts, D.C. Tubular paper. Non-ins.		B	..	2
14751	Type 4951 ...	0.005 mfd. \pm 20 per cent., 1,000 volts, D.C. Tubular paper, Non-ins.		B	..	2
14759	Type 4957 ...	8 mfd. + 50 — 20 per cent., 375 volts, D.C. Electrolytic. Spindle, $2\frac{3}{8}$ in. long \times $1\frac{3}{8}$ in. dia.		B	..	1
14844	Type 4989 ...	0.02 mfd., 10 per cent., 2,000 D.C. working. Paper. Rect. metal case, $2\frac{3}{8}$ in. \times 2 in. \times $1\frac{1}{4}$ in.		B	..	1
14845	Type 4990 ...	0.25 mfd., 20 per cent., 3,000 D.C. working. Paper. Rect. metal case, $3\frac{1}{16}$ in. \times $3\frac{3}{8}$ in. \times $1\frac{7}{8}$ in.		B	..	1
14852	Type 4993 ...	0.01 mf. \pm 10 per cent., 350 volts. Silver mica, protected.		B	..	3
14857	Type 4994 ...	68 pfd., 5 per cent., 750 D.C. working. Silvered mica, protected.		B	..	5
14858	Type 4995 ...	0.0025, 5 per cent., 750 D.C. working. Silvered mica, protected.		B	..	3
14869	Type 4997 ...	320 μ F., 5 per cent., 350 D.C. working. Silver mica, protected.		B	..	3

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom of Qty	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
14870	Type 4998 ...	0.0025 mfd. \pm 10 per cent., 750 volts, D.C. Silver mica, protected.		B	each	3
14871	Type 4999 ...	220 μ F., 2 per cent., 2,000 D.C. working. Silver mica, protected.		B	..	3
14872	Type 5000 ...	1,400 μ F., 20 per cent., 5 KV. Ceramic flange pot.		B	..	1
14875	Type 5002 ...	50 μ F. + 50 - 20 per cent., 50 D.C. working. Dry electrolytic. Dimensions, 2 $\frac{1}{2}$ in. long \times 1 $\frac{1}{8}$ in. dia.		B	..	2
14876	Type 5003 ...	70 pfd., 10 per cent., 1,000 D.C. working. Ceramic, tubular. 15 mm. \times 8 mm.		B	..	3
14878	Type 5005 ...	17 μ F., 5 per cent., 500 volts. Silver ceramic disc.		B	..	5
14892	Type 5010 ...	50 mfd., 50 D.C. working. Dry electrolytic, non-polarised.		B	..	—
14899	Type 5014 ...	250 μ F. + 15 - 20 per cent., 70 W. Electrolytic, metal rect. case. 100 volts peak working l.		B	..	1
14903	Type 5017 ...	0.006 mfd \pm 5 per cent, 350 watts. Silver mica, protected.		B	..	3
14904	Type 5018 ...	0.008 mfd. \pm 5 per cent., 350 watts. Silver mica, protected.		B	..	3
14905	Type 5019 ...	0.009 mfd. \pm 5 per cent., 350 watts. Silver mica, protected.		B	..	3
14907	Type 5021 ...	100 pfd. \pm 15 per cent., 350 volts, D.C. Silver mica, protected.		B	..	5
14908	Type 5022 ...	300 pfd. \pm 15 per cent., 350 volts, D.C. Silver mica, protected.		B	..	3
14909	Type 5023 ...	500 pfd. \pm 15 per cent., 350 volts, D.C. Silver mica, protected.		B	..	3
14910	Type 5024 ...	0.001 mfd. \pm 15 per cent., 350 watts. Silver mica, protected.		B	..	3
15037	Type 5079 ...	100 - 7.5 pfd. Variable air. Spindle, $\frac{3}{4}$ in., 0.465 in. at each end. Air gap, 0.012 in. Single gang.		B	..	1
15069	Type 5093 ...	Air, variable, 3 gauge. Transmitter.		B	..	1
15070	Type 5094 ...	Air, variable, 2 gauge. Transmitter.		B	..	1
15071	Type 5095 ...	500 pf., 10 per cent., 15 KV. H.F. Ceramic, flanged pot.		B	..	1
15102	Type 5114 ...	0.05 valve. Anti-interference...		B	..	2
15103	Type 5116 ...	Anti-interference		B	..	2
15104	Type 5117 ...	6.8 μ F., 10 per cent., 500 W. Silvered ceramic, tubular, tropical.		B	..	3
15107	Type 5120 ...	Air, variable		B	..	1
15123	Type 5125 ...	35 - 6 pfd. Variable. Split stator, 5 rotor, 6 stator plates per section, 0.058 in. spacing.		B	..	1
15134	Type 5135 ...	4 max., 2 min. Air, variable. Neutralising condenser.		B	..	1
15135	Type 5136 ...	30 max., 4.7 min. Air, variable		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
15136	Type 5137	18 max., 4.5 min. Air, variable		B	each	1
15137	Type 5138	36 max., 4.8 min. Air, variable		B	..	1
15138	Type 5139	11 max., 3 min. Air, variable		B	..	1
15140	Type 5140	11 max. Air, variable, NOT		B	..	1
15141	Type 5141	Air, variable		B	..	1
15142	Type 5142	Air, fixed		B	..	1
15223	Type 5203	Valve, 100. Air, variable. Spin- dle, $\frac{7}{8}$ in., with flat $\frac{3}{4}$ in. long.		B	..	1
15251	Type 5211	60 pfd., 5 per cent. On adjust- ment mica. Coupling, $5\frac{1}{4}$ in. $\times 3\frac{11}{16}$ in. overall.		B	..	1
15274	Type 5213	97-89 valve. Air, variable. Padding plug in $3\frac{7}{8}$ in.		B	..	1
15280	Type 5216	1-7 $\mu\mu\text{F}$. Concentric trimmer		B	..	1
15816	Type 5218	Air, copper, tubular, 1 ft. $\times 2\frac{3}{8}$ in. $\times 1\frac{1}{2}$ in. dia.		B	..	1
15818	Type 5219	Left-hand output circuit wave change.		B	..	1
15819	Type 5220	Right-hand output circuit wave change.		B	..	1
15849	Type 5239	10 pfd., 0.5 per cent., 500 W. Ceramic, tubular.		B	..	3
15850	Type 5240	27 pfd., 0.5 per cent., 500 W. Ceramic, tubular.		B	..	3
15851	Type 5241	51 pfd., 17 per cent. 500 W. Ceramic, tubular.		B	..	5
15852	Type 5242	100 pfd., 1 per cent., 500 W. Ceramic, tubular		B	..	5
15853	Type 5243	150 pfd., 1 per cent., 500 W. Ceramic, tubular.		B	..	5
15872	Type 5261	100 valve + 50 - 20 per cent., 50 W. Electrolytic.		B	..	—
15884	Type 5272	Used on S.W.B. 10		B	..	1
15892	Type 5277	Alum. tubular, 2-section end chains, and saddles 2 in.— 4 in. $\times 4\frac{3}{16}$ in. dia.		B	..	1
15894	Type 5278	Assembly of 2 copper straps and insulating strips, $8\frac{1}{2}$ in. \times $\frac{1}{2}$ in.		B	..	5
15901	Type 5280	0.01 μF ., 20 per cent., 350 W. Mild mica, stacked foil.		B	..	5
15913	Type 5288	6-100 $\mu\mu\text{F}$., 650 W. Air dielec- tric. Trimmer.		B	..	1
15915	Type 5290	554 pfd. Air, variable, 4 gang		B	..	1
15924	Type 5291	300 pfd. Variable, air... ..		B	..	1
15925	Type 5292	50 pfd. Variable, air		B	..	1
15938	Type 5297	0.05 mfd., 5 per cent., 500 W. Paper, tubular. $1\frac{1}{2}$ in. $\times 1\frac{3}{8}$ in. dia.		B	..	3
15943	Type 5299	315 pfd. Variable, air, 2 gang		B	..	1
15963	Type 5307	40 $\mu\mu\text{F}$. Ceramic trimmer ...		B	..	1
15989	Type 5321	0.1 μF., 20 per cent., 1,000 W. Paper, tubular, $2\frac{1}{2}$ in. $\times \frac{3}{4}$ in.		B	..	3
16016	Type 5327	50 max., 5 min. Air, variable		B	..	1
16023	Type 5328	75 max., 5 min. Air, variable		B	..	1
16029	Type 5330	0.0004. Air, variable. As Type 3062 but with additional vane.		B	..	1
16059	Type 5348	100 pfd. Air, variable		B	..	1
16081	Type 5355	47 pfd., 2 per cent., 500 volts D.C. Ceramic tube.		B	..	5
16082	Type 5356	47 pfd., 5 per cent., 500 volts D.C. Ceramic, tubular.		B	..	5

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSERS—					
	<i>cont.</i>					
16102	Type 5369 ...	8 + 16 mfd. + 50 — 10 per cent., 350 volts D.C. Paper block. Alum. can, 2½ in. × 1¾ in. dia.		B	each	1
16126	Type 5384 ...	0.1 mfd., 25 per cent., 150 volts D.C. Metallised paper. Nesprene sleeve, 0.687 in. × 0.37 in. dia.		B	..	3
16128	Type 5386 ...	0.05, 25 per cent., 250 volts D.C. Metallised paper. Nesprene sleeve, 0.687 in. × 0.37 in. dia.		B	..	3
16139	Type 5397 ...	110 pfd., 1 per cent., 500 volts D.C. Ceramic tube ...		B	..	5
16145	Type 5403 ...	47 pfd., 0.5 per cent., 500 volts D.C. Ceramic tube.		B	..	5
16155	Type 5409 ...	60–5. Variable. Mica ...		B	..	1
16156	Type 5410 ...	100–40. Variable. Mica ...		B	..	1
16157	Type 5411 ...	400–200. Variable. Mica ...		B	..	1
16158	Type 5412 ...	700–350. Variable. Mica ...		B	..	1
16197	Type 5438 ...	6.8 μF., 10 per cent., 500 volts D.C. Ceramic ...		B	..	5
16295	Type 5498 ...	50 + 50 pfd. Air, variable, 2 gauge. Overall size, 2.679 in. long × 1.532 in. × 1.26 in. Spindle, ¼ in.		B	..	3
16296	Type 5499 ...	0.01 μF., 20 per cent., 3,000 volts. Paper dielectric. ceramic tube. Spindle, 2½ in. × ¾ in.		B	..	3
16459	Type 5657 ...	270 pfd. ± 5 per cent., 500 volts D.C. Ceramic, tubular.		B	..	3
17043	Type W.5661 ...	Fixed paper, metal case. 0.25 mfd., 3 K.volts D.C.		B	..	—
16560	Type 5753 ...	20 pfd., 5 per cent., 350 volts D.C. Silvered mica, moulded.		B	..	3
16705	Type 5877 ...	7–61. Air, variable ...		B	..	—
17537	Type 6077 ...	Air, variable. 4 fixed, 3 moving vanes. Valve, 3.3–25.		B	..	—
	CONDENSER-UNITS:—					
10545	Type 4 ...	Aluminium plate, 4½ in. × 3 in., with feet, fitted with 3 condensers.		B	..	1
2031	Type 8		B	..	1
2392	Type 10 ...	Bracket assembly ...		B	..	1
2364	Type 13 ...	Tufnol panel, 2¼ in. × 1¾ in. × 1½ mm.		B	..	1
2365	Type 14 ...	Tufnol panel, 5½ in. × 3¾ in. × 2 mm.		B	..	1
2598	Type 15 ...	Base plate with valve base ...		B	..	1
2698	Type 17 ...	2 variable concentric tube condensers.		B	..	1
2829	Type 20 ...	11–21 pfd., split stator precision condenser, series, gap type, mounted in silver-plated screening box.		B	..	1
8473	Type 25 ...	Earth. Combined condenser and resistance.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSER-UNITS—cont.					
8474	Type 26	Listening through. Combined condenser and plug and socket connector.		B	each	1
3173	Type 34	Five 4-40 pfd. H.F ceramic trimmer condensers, mica dielectric, with screw adjustment, mounted on metal bracket.		B	"	1
3174	Type 35	Three 4-40 pfd. H.F. ceramic trimmer condensers, mica dielectric, with screw adjustment, mounted on metal bracket.		B	"	1
3376	Type 39	2 gang		B	"	1
3075	Type 40	25 k. volts, glass dielectric, with sheds and corona flange.		B	"	—
3378	Type 42	Tuning condenser, 2.3 — 11.3 pfd., rotor float, with shorting bar, inductance and valve caps.		B	"	2
3593	Type 44	Tufnol panel, 2½ in. × 1½ in. × 2 mm., and meter screen.		B	"	1
11607	Type 45	Moulded mounting block ...		B	"	1
3823	Type 50		B	"	1
3824	Type 51	4 gang condenser, complete with slow motion logging scale.		B	"	1
4061	Type 52	Tufnol panel, complete with pillars (6).		B	"	1
4062	Type 53	2½ in. × 1½ in. × 1½ mm., Tufnol panel.		B	"	1
4470	Type 57	Tag panel, insulating panel, nuts and screws.		B	"	1
4471	Type 58	Tag panel and oscillator tuning condenser coil.		B	"	1
5629	Type 68	Bushing condenser assembly ...		B	"	1
5727	Type 70		B	"	1
5729	Type 72		B	"	1
5750	Type 73	S.R.B.P. panel		B	"	1
11048	Type 82	Bracket mounted assembly, copper, 18 S.W.G., 1½ in. × 1½ in. base, with copper rod coil.		B	"	—
11337	Type 87	3 condensers, mounted on base, ⅜ in. × 1½ in. × 1½ in. × 15 in., common connector, ⅜ in. × ¼ in. × 10¼ in. copper.		B	"	1
11449	Type 88	Neutralizer plate, right hand; fitted with 2 brass sleeves, and 2 brass 6 B.A. screws, ⅜ in. long, countersunk heads.		B	"	1
11450	Type 89	Neutralizer plate, left hand; fitted with 2 brass sleeves, and 2 brass 6 B.A. screws, ⅜ in. long, countersunk heads.		B	"	1
11505	Type 90	M.S. bracket, 3½ in. × 2½ in. × 1½ in. C/W 4 condensers.		B	"	1
11571	Type 92	S.R.B.P. panel, 1½ in. × 1½ in., including 1 condenser 30 μμF, and 1 condenser 100 μμF.		B	"	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CONDENSER-UNITS—cont.					
11573	Type 93	S.R.B.P. panel, 2 $\frac{3}{8}$ in. \times 2 in. ...		B	each	1
11574	Type 94	S.R.B.P. panel, 2 $\frac{3}{8}$ in. \times 1 $\frac{1}{2}$ in.		B	..	1
11637	Type 95	S.R.B.P. panel		B	..	1
11798	Type 98	Assembly		B	..	1
12225	Type 103	Bakelised paper board, 2 $\frac{3}{8}$ in. \times 2 $\frac{1}{4}$ in.		B	..	1
12292	Type 104	S.R.B.P. panel, 1.5 in. \times 2.25 in.		B	..	1
12441	Type 105	2 mica presets, each 4 to 5 $\mu\mu\text{F}$. min., 12 $\mu\mu\text{F}$. max., on bakelite strip.		B	..	1
12564	Type 107		B	..	1
12626	Type 108	Right-hand mounting		B	..	1
12627	Type 109	Left-hand mounting		B	..	1
12965	Type 118	Ruby mica wafer, rectangular, 1 $\frac{1}{2}$ in. \times 1 in. \times 0.003 in. (app.), drilled 2 holes.		B	..	1
13176	Type 120	Insulated plate, 1 $\frac{1}{8}$ in. \times 4 $\frac{1}{8}$ in. \times $\frac{1}{8}$ in., with 2 M. steel brackets.		B	.	1
13313	Type 126		B	..	1
13391	Type 127	Variable condenser and drive, complete with anode coil and 2 valve clips.		B	..	1
13540	Type 130		B	..	1
13566	Type 131	Variable, 500 $\mu\mu\text{F}$., 4 gang. 2 condensers joined together and coupled to operate on common spindle.		B	..	1
13684	Type 133	S.R.B.P. tagboard, 2 $\frac{1}{16}$ in. \times 2 in.		B	..	1
13685	Type 134	M.S. zinc-plated bracket, 1.781 in. \times 0.813 in. \times 0.75 in., with clamping plate screwed to bracket.		B	..	1
13741	Type 136	32-90 $\mu\mu\text{F}$. Variable condenser (2 banks 180 in. apart in parallel). Condenser rotor on moving spindle at Desynon motor. Oil filled. 0.12 volt operation. For control by remote potentiometer.		B	..	1
13886	Type 138	S.R.B.P., $\frac{5}{8}$ in. \times 2 $\frac{9}{16}$ in. \times $\frac{1}{16}$ in.		B	..	1
13928	Type 139	Variable, air, 3.3-6.1 $\mu\mu\text{F}$. Ceramic end plates, complete with inductances, centre tapped.		B	..	1
13937	Type 140	S.R.B.P., 1.875 in. \times 0.75 in. \times 0.062 in.		B	..	1
13949	Type 141	Assembly of mounting with three 8 μF . and one 16 μF . condenser.		B	..	1
14087	Type 143	0.001 μF . + 0.0074 μF . Frequency tuning pair of 1. Complete, in moulded case, 1.687 in. dia., tap reduced to 1.234 in. dia. \times 2.687 in., with 4-pin base, using pins 1, 3, 5, and 6 of Brit. 7-valve base.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
14088	CONDENSER-UNITS—cont. Type 144 ...	0.0043 μ F. + 0.0032 μ F. Frequency tuning pair 2. All other details as Type 143.		B	each	1
14089	Type 145 ...	0.0024 μ F. + 0.00173 μ F. Frequency tuning pair 3. All other details as Type 143.		B	..	1
14261	Type 146 ...	S.R.B.P., 0.093 in. \times 0.4687 in. \times 1.5 in.		B	..	1
14271	Type 147 ...	S.R.B.P., 2 in. \times 0.75 in. ...		B	..	1
14340	Type 148 ...	4-gang, complete with calibration.		B	..	—
14367	Type 149 ...	Compensating condenser assembly of adjustable plate and trimmer on bracket.		B	..	1
14743	Type 151 ...	Right-hand. First used on Power Unit, Type 87.		B	..	1
14744	Type 152 ...	Left-hand. First used on Power Unit, Type 87.		B	..	1
14881	Type 157 ...	3 $\frac{1}{8}$ in. \times 2 $\frac{1}{16}$ in. S.R.B.P., $\frac{1}{16}$ in. thick, with 8 taps, complete with 2 condensers.		B	..	1
	CORES, IRON DUST:—					
5826	10 mm. dia. \times 17 mm. long.	Complete, with adjusting screw, 4 B.A. \times 30 mm. long. For use with inductances, Types 501, 502, 503, and 504.		B	..	2
12578	Type 1 ...	0.37 in. dia. \times 0.5 in., on brass spindle, 3.31 in. long.		B	..	1
12579	Type 2 ...	0.37 in. dia. \times 0.5 in., on brass spindle, 1.5 in. long.		B	..	1
12885	Type 3 ...	16 mm. \times 8 mm. dia., threaded 1.25 mm. pitch, slotted end. 10C/5722, cellulose varnished.		B	..	—
12938	Type 4 ...	Comprising H.F. core, $\frac{1}{2}$ in. long \times $\frac{3}{8}$ in. dia., on stem, 1.25 in. long over squared end, screwed 2 B.A.		B	..	2
13338	Type 6		B	..	1
13488	Type 7 ...	Primary, 3 turns 26 S.W.G. D.S.C. copper. Secondary, 2 turns 26 S.W.G. D.S.C. copper.		B	..	1
13489	Type 8 ...	Primary, 4 turns 26 S.W.G. D.S.C. copper. Secondary, 2 turns 26 S.W.G. D.S.C. copper.		B	..	1
13490	Type 9 ...	Primary, 6 turns 26 S.W.G. D.S.C. copper. Secondary, 3 turns 26 S.W.G. D.S.C. copper.		B	..	1
13491	Type 10 ...	Primary, 9 turns 26 S.W.G. D.S.C. copper. Secondary, 3 turns 26 S.W.G. D.S.C. copper.		B	..	1
13968	Type 11 ...	Screwed, screwdriver slot one end, $\frac{5}{8}$ in. long.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
17038	INDUCTANCE ASSEMBLIES:— I.F. No. 1	Used on R/RDF No. 7	Army ZC.12021	B	each	—
3476	INDUCTANCE CONDENSER-UNITS:— Type 1	2 wire-wound inductances, 0.423 microhenries each (6½ turns), mounted in international octal valve base, cover engraved 22–28 Mc./s, 45°.		B	..	1
3477	Type 2	2 wire-wound inductances, 1.06 microhenries each (12 turns), mounted in international octal valve base, cover engraved 22–28 Mc./s, 90°.		B	..	1
3478	Type 3	2 wire-wound inductances, 0.213 microhenries each (4 turns), mounted in international octal valve base, cover engraved 42–50 Mc./s, 45°.		B	..	1
3479	Type 4	3 + 3 turns No. 32 S.W.G., D.S.C. copper on bobbin, mounted in international octal valve base, cover engraved 42–55 Mc./s, 90°.		B	..	1
4640	Type 9	Delay network, comprising 11 "Leesona" wound coils, 10 condensers and 2 resistances, in sheet brass box, 5½ in. × 2¼ in. × 1¼ in.		B	..	1
5495	Type 11	Side chain (A.V.C.) unit		B	..	1
11335	Type 21	Delay network; 80 ohms, 1.0 microsecond.		B	..	1
11443	Type 22	Assembly of suppressor		B	..	1
11444	Type 23	Delay network, comprising six inductances, five of 42 mH and one of 84 mH; and five condensers, 670 pfd.		B	..	1
11451	Type 24		B	..	1
11521	Type 25	Marker unit in sheet brass screening case, 4 in × 1 in. × 1½ in. approx.		B	..	1
11502	Type 26		B	..	1
11915	Type 28		B	..	1
11965	Type 29	2 units on common mounting:— (1) Single transit delay of 1 microsecond, and characteristic impedance of 2,000 ohms. (2) Single transit delay of 0.5 microsecond, and characteristic impedance of 4,000 ohms.		B	..	1
11966	Type 30	Single transit delay of 2 microseconds, and characteristic impedance of 270 ohms.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCE CONDENSER-UNITS—cont.					
11967	Type 31	Single transit delay of 8 micro-seconds, and characteristic impedance of 1,000 ohms.		B	each	1
12926	Type 40	5 μ sec. delay. Includes 1 \times 100 $\mu\mu$ F. condensers, T.C.C., silvered mica, protection; 5 \times 10 $\mu\mu$ F. condensers, T.C.C., silvered ceramic disc; and 10 inductances, each 1 mH., wave-wound.		B	..	1
13358	Type 44	Comprises 1 tagboard, 2 \times 6.5 H., inductances and condensers.		B	..	1
13359	Type 45	Comprises 1 tagboard, 2 \times 0.45 H., chokes and condensers.		B	..	1
13360	Type 46	Comprises 1 tagboard, 1 \times 6.5 H., inductance and condensers.		B	..	1
13361	Type 47	Comprises 1 tagboard, 2 \times 6.5 H., inductance and condensers.		B	..	1
13411	Type 49	1 μ -sec., 75 ohms		B	..	1
13412	Type 50	$\frac{1}{2}$ μ -sec., 80 ohms impedance...		B	..	1
13439	Type 52		B	..	1
14018	Type 64	Delay network, comprising one 4.7 K. resistor, four 25 $\mu\mu$ F. condensers, and five inductances.		B	..	1
14019	Type 65	Delay network, comprising one 4.7 K. resistor, four 25 $\mu\mu$ F. condensers, and five inductances.		B	..	1
14113	Type 68	6 sections, inductance of each 307 μ H., 6 condensers 50 pF. \pm 5 per cent. Silvered mica waxed in as one unit.		B	..	1
14115	Type 69	Delay network		B	..	1
14175	Type 72	1 μ -sec., 75 ohms		B	..	1
14184	Type 73	Assembly of 17 coils, 18 condensers, 1 resistance, and 10 sockets, mounted between bars.		B	..	1
14269	Type 77	1 μ -sec delay. Impedance, 75 ohms.		B	..	1
14280	Type 78	Comprises 8 condensers and 1 inductance of 5 coils on former.		B	..	1
14281	Type 79	Comprises 7 condensers and 1 inductance of 5 coils on former.		B	..	1
14284	Type 82	Comprises 6 condensers and 1 inductance of 6 coils on former.		B	..	1
14730	Type 88	2 honeycomb coils and 1 condenser in cylindrical metal can, with 2 screened leads.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCE CONDENSER UNITS—cont.					
14919	Type 92	Comprises condenser, Type 5032, 4 coils of 300 mH. each, 2.47 K. \pm 20 per cent., 1 watt, carbon resistors, and 0.1 mf. \pm 10 per cent., 1,500 volts. paper tubular condenser, 20 coils of 200 mH. each.		B	each	1
14963	Type 93	Delay line and switch assembly, with 20 condensers and 3 resistances and switch.		B	„	1
15074	Type 95	Consists of 13 section coil. 2 end coils are each 0.75 mH. and 11 coils in between are 1.5 mH. Twelve 500 pf. silver mica condensers all mounted on base.		B	„	1
16872	Type 126	Delay network wax filled sealed can, 5 $\frac{3}{4}$ in. \times 3 in. \times 1 in. approx., containing 2 off resistances, 8 off condensers and coil assembly.		B	„	—
16873	Type 127	Delay network wax filled sealed can, 5 $\frac{3}{4}$ in. \times 3 in. \times 1 in. overall approx., containing 1 off resistance, 7 off condensers and coil assembly.		B	„	—
	INDUCTANCES:—					
404	Type 1	A.M. allocation only		B	„	1
405	Type 2		B	„	1
406	Type 3		B	„	1
407	Type 4		B	„	1
409	Type 6	A.M. allocation only		B	„	1
410	Type 7		B	„	1
411	Type 8		B	„	1
412	Type 9		B	„	1
413	Type 10		B	„	1
414	Type 11		B	„	1
415	Type 12		B	„	1
416	Type 13		B	„	1
417	Type 14	A.M. allocation only		B	„	1
418	Type 15		B	„	1
419	Type 16		B	„	1
420	Type 17		B	„	1
421	Type 18		B	„	1
422	Type 19		B	„	1
423	Type 20		B	„	1
424	Type 21	A.M. allocation only		B	„	1
425	Type 22		B	„	1
10790	Type 31	Aerial coil		B	„	1
11081	Type 32		B	„	1
11082	Type 33		B	„	1
11083	Type 34		B	„	1
11084	Type 35		B	„	1
10805	Type 43	Retard coil; 6 henries at 50 mA., D.C. Resistance, 150 ohms.		B	„	1
771	Type 50		B	„	1
772	Type 5165 microhenries		B	„	1
776	Type 53		B	„	1
829	Type 59		B	„	1
831	Type 60		B	„	1
834	Type 62		B	„	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCES—					
	<i>cont.</i>					
835	Type 63		B	each	1
891	Type 64	8 $\frac{5}{8}$ turns, centre tapped on bakelite former.		B	"	2
892	Type 65	0.42 M.H. 3 $\frac{5}{8}$ turns, centre tapped on bakelite former.		B	"	1
893	Type 66		B	"	1
897	Type 67		B	"	1
10658	Type 70	Choke coil		B	"	1
909	Type 101	0.33 microhenries		B	"	1
912	Type 102	0.59 millihenries approx., 7 turns 20 S.W.G. bare copper wire, wound anti-clockwise on grooved 4-rib ceramic former.		B	"	1
913	Type 103	0.29 millihenries, approx. 4 turns of 20 S. W. G. bare copper wire, wound clockwise on grooved 4-rib ceramic former.		B	"	1
2096	Type 106	I.F. coupling. Variable 97 millihenries ± 2 per cent.		B	"	1
2097	Type 107	I.F. coupling. Variable 97 millihenries ± 2 per cent., tapped at 39th turn.		B	"	1
2099	Type 108	68 microhenries ± 5 per cent., 1,000 cycles.		B	"	1
2111	Type 109	1.322 microhenries. With bakelite base. 10 turns of 10 S.W.G. bare copper wire. Length of coil, 2 in.		B	"	1
2112	Type 110	0.853 microhenries. With bakelite base. 8 turns of 10 S.W.G. bare copper wire. Length of coil, 1 $\frac{7}{8}$ in.		B	"	1
2113	Type 111	0.512 microhenries. With bakelite base. 6 turns of 10 S.W.G. bare copper wire. Length of coil, 1 $\frac{7}{8}$ in.		B	"	1
2114	Type 112	0.318 microhenries. With bakelite base. 4 turns of 10 S.W.G. bare copper wire. Length of coil, 1 $\frac{1}{8}$ in.		B	"	1
2115	Type 113	1.12 microhenries. With bakelite base 10 turns of 10 S.W.G. bare copper wire. Length of coil, 2 $\frac{1}{4}$ in.		B	"	1
2116	Type 114	0.9 microhenries. With bakelite base 8 turns of 10 S.W.G. bare copper wire. Length of coil, 1 $\frac{1}{8}$ in.		B	"	1
2117	Type 115	0.66 microhenries. With bakelite base 6 turns of 10 S.W.G. bare copper wire.		B	"	1
2118	Type 116	0.54 microhenries. With bakelite base. 6 turns of 10 S.W.G. bare copper wire. Length of coil, 1 $\frac{7}{8}$ in.		B	"	1
2140	Type 117	126 microhenries ± 20 per cent. Iron cored Overall size, 1 $\frac{1}{2}$ in. \times $\frac{5}{8}$ in. dia.		B	"	1
2151	Type 118	1.66 microhenries. With mounting base. 12 turns of 10 S.W.G. bare copper wire. Coil, 2 $\frac{1}{8}$ in. \times 1 $\frac{5}{8}$ in. dia.		B	"	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCES—					
	<i>cont.</i>					
2152	Type 119 ...	1.26 microhenries. With mounting base. 10 turns of 10 S.W.G. bare copper wire. Coil, 2 in. \times $1\frac{3}{16}$ in. dia.		B	each	1
2153	Type 120 ...	0.93 microhenries. With mounting base. 8 turns 10 S.W.G. bare copper wire. Coil, $1\frac{3}{8}$ in. \times $1\frac{3}{16}$ in. dia.		B	..	1
2154	Type 121 ...	0.79 microhenries. With mounting base. 8 turns of 10 S.W.G. bare copper wire. Coil, $2\frac{1}{8}$ in. \times $1\frac{3}{16}$ in. dia.		B	..	1
2200	Type 122 ...	Oscillator coil ...		B	..	1
2201	Type 123 ...	Oscillator coil ...		B	..	1
2202	Type 124 ...	Shaping coil ...		B	..	1
2266	Type 125 ...	S.W. Intermediate frequency coil. Centre tapped.		B	..	1
2267	Type 126		B	..	1
2602	Type 130 ...	68 microhenries \pm 5 per cent. at 1,000 cycles.		B	..	1
2608	Type 133 ...	Shift coil assembly; comprises 2 coils each on formers $4\frac{1}{2}$ in. long \times 1 in. dia., 1 coil mounted on each leg of U-shaped iron core $8\frac{1}{2}$ in. \times $5\frac{1}{2}$ in. \times $\frac{1}{2}$ in.		B	..	1
2609	Type 134 ...	Di-placer coil assembly; flat coil $2\frac{3}{8}$ in. diam. \times $\frac{1}{2}$ in. with mounting.		B	..	2
2632	Type 136 ...	Primary — 250 microhenries; secondary (tuned, centre tapped) 58 microhenries Iron core $\frac{3}{8}$ in. sq.; coil former cheeks $1\frac{1}{2}$ in. dia.		B	..	1
11107	Type 137		B	..	1
2754	Type 138 ...	140 microhenries \pm $2\frac{1}{2}$ per cent; coil, $1\frac{1}{2}$ in. dia. \times $\frac{3}{8}$ in.; former, tufnol, 1 in. \times $\frac{1}{2}$ in. dia.		B	..	1
11791	Type 139		B	..	1
2771	Type 140		B	..	1
2776	Type 141		B	..	1
2786	Type 148		B	..	1
2789	Type 151		B	..	1
2842	Type 153		B	..	1
2843	Type 154		B	..	1
2844	Type 155		B	..	1
2845	Type 156		B	..	1
2856	Type 161		B	..	1
2910	Type 163 ...	Aerial transformer, 20,000 kc./s to 1,500 kc./s.		B	..	1
2911	Type 164 ...	Amplifier 20,000 kc./s to 1,500 kc./s.		B	..	1
2912	Type 165 ...	First stage ...		B	..	1
2913	Type 166 ...	First stage ...		B	..	1
2914	Type 167 ...	Second stage ...		B	..	1
2915	Type 168 ...	Second stage ...		B	..	1
3650	Cases, transit ...	For inductances, Types 165-168		A	..	—

RADIO CHOKES AND CONDENSERS

Ref. No	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCES—					
	<i>cont.</i>					
2994	Type 183 ...	Wire wound on loaded ebonite former, Spec. K109 $\frac{7}{8}$ in. dia.		B	each	1
3151	Type 188 ...	Two windings (6 turns of 26 S.W.G. and 10 turns of 20 S.W.G. enamelled wire) on ribbed former with base and leads.		B	..	1
3153	Type 190 ...	No. of turns 6, 10 + $\frac{5}{16}$, 3 windings (6, 10 + $\frac{5}{16}$) turns 26 S.W.G. enam. wire on ribbed former, with case and leads.		B	..	1
3154	Type 197 ...	Used on R.1205		B	..	1
3156	Type 199 ...	Fixed		B	..	1
3159	Type 202 ...	Fixed		B	..	1
3166	Type 209 ...	Compensation coil		B	..	1
3167	Type 210 ...	I.F. coil grid		B	..	1
3168	Type 211 ...	I.F. coil anode		B	..	1
3169	Type 212 ...	I.F. coil diode		B	..	1
3230	Type 213 ...	3.73 millihenries, wound on moulded former.		B	..	1
3231	Type 214 ...	370 microhenries, wound on moulded former.		B	..	1
3232	Type 215 ...	190 millihenries, wound on moulded former.		B	..	1
3233	Type 216 ...	30 millihenries, wound on tubular tufnol former.		B	..	1
3234	Type 217 ...	1,000 microhenries, creed, Part No 2266/1.		B	..	1
3235	Type 218 ...	1,000 microhenries $1\frac{1}{2}$ in. dia. \times $\frac{7}{16}$ in.		B	..	1
3496	Type 234 ...	H.F. transformers, 4 sections, P :-60 turns, S :-133-133-133 No. 36, D S C copper.		B	..	1
3542	Type 237 ...	2nd stage 1.5 to 3 Mc/s		B	..	1
3541	Cases, transit			A	..	—
3619	Type 241 ...	I.F. iron dust core 298 microhenries between pins 1 and 6. 163 microhenries between pins 3 and 4.		B	..	1
3816	Type 250 ...	$\frac{7}{8}$ in. outside dia. tubular former wound with closely spaced enamelled copper wire.		B	..	1
3817	Type 251 ...	$\frac{7}{8}$ in. outside dia. tubular former wound with widely spaced enamelled copper wire.		B	..	1
3818	Type 252 ...	$1\frac{1}{2}$ in. dia. cylindrical former with 8 grooves—6 grooves wound with a total of 455 $\frac{1}{2}$ turns of 38 S.W.G. enamelled copper wire.		B	..	1
3819	Type 253 ...	$\frac{3}{4}$ in dia. cylindrical former wound with 86 $\frac{1}{2}$ turns of 38 S.W.G. enamelled copper wire.		B	..	1
3825	Type 254 ...	3 $\frac{1}{2}$ turns of $\frac{1}{8}$ in. dia. copper rod		B	..	1
3827	Type 256 ...	Helical coil, 2 turns of 14 S.W.G. copper wire, silver-plated.		B	..	1
3829	Type 258 ...	Helical coil, 3 turns, 14 S.W.G. copper wire, silver-plated		B	..	1
3967	Type 262 ...	1 mH., 90+90 turns, 36 S.W.G. Trolitol, large round bobbin.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCES—					
	<i>cont.</i>					
4045	Type 270 ...	Plug-in polystyrene former $1\frac{1}{8}$ in. dia. across ribs, \times 2 ins. with 4 pins on strip. Windings:—50 turns and 16 turns, close wound.		B	each	1
4051	Type 276 ...	$1\frac{1}{2}$ in. dia. former ...		B	..	1
4052	Type 277 ...	$1\frac{1}{2}$ in. dia. former ...		B	..	1
4053	Type 278 ...	$1\frac{1}{2}$ in. dia. former ...		B	..	1
4054	Type 279 ...	$1\frac{1}{2}$ in. dia. former ...		B	..	1
4077	Type 280 ...	$1\frac{1}{2}$ in. dia. former ...		B	..	1
4078	Type 281		B	..	1
4136	Type 288 ...	H.F. ...		B	..	1
4137	Type 289		B	..	1
4139	Type 290		B	..	1
4302	Type 311 ...	9.3–21.5 m/c. No. of turns 9, 18 enam. D.S.C. moulded former \times 262.		B	..	1
4303	Type 312 ...	Used on R.1273 ...		B	..	1
4304	Type 313		B	..	1
4314	Type 314		B	..	1
4315	Type 315		B	..	1
4316	Type 316 ...	2 range coil unit ...		B	..	1
4317	Type 317		B	..	1
4450	Type 365 ...	I.F. Coil grid ...		B	..	1
4451	Type 366 ...	I.F. Anode and diode ...		B	..	1
4453	Type 368 ...	1st R.F. Coil and bracket assembly.		B	..	1
4454	Type 369 ...	2nd R.F. Coil and bracket assembly.		B	..	1
4456	Type 371 ...	Keramot 5 flange bobbin, 42 S.W.G. 10 turns per slot		B	..	1
4459	Type 374 ...	46 turns, 24 enamelled copper wire.		B	..	1
4726	Type 376 ...	Dust iron core, screened; coil windings:— Primary 456 turns, 42 D.S.C. Secondary (1) 57 turns, 36 D.S.C. Secondary (2) 57 turns, 36 D.S.C.		B	..	1
4728	Type 378 ...	Wire-wound oscillator assembly, mounted on bakelite base, with brass core and distrene sleeve.		B	..	1
4729	Type 379 ...	Wire-wound, 1st R.F. assembly, mounted on bakelite base, with brass core and distrene sleeve.		B	..	1
4730	Type 380 ...	Wire-wound, 2nd R.F. assembly, mounted on bakelite base, with brass core and distrene sleeve.		B	..	1
4731	Type 381 ...	Wire-wound, aerial assembly, mounted on bakelite base, with brass core and distrene sleeve.		B	..	1
4733	Type 383 ...	22 turns of 36 gauge, enamelled S.S.C. copper wire on $\frac{1}{4}$ in. dia. former.		B	..	1
4734	Type 384 ...	18 turns of 36 gauge, enamelled S.S.C. copper wire on $\frac{1}{2}$ in. dia. former.		B	..	1
4833	Type 388		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCES—					
	<i>cont.</i>					
4834	Type 389		B	each	1
4835	Type 390		B	..	1
4838	Type 393	Cylindrical former, twin lug fixing, 3 section winding, 527.6 millihenries.		B	..	1
4839	Type 394	Cylindrical former, twin lug fixing, 3 section winding, 521.7 millihenries.		B	..	1
4858	Type 396	13 turns, 36 gauge enamelled S.S.C. copper wire on $\frac{1}{2}$ in. dia. former		B	..	1
5077	Type 422	35 millihenries, 10 mA, $1\frac{1}{8}$ in. max. diam. wave wound coil on tubular bakelite former $1\frac{1}{8}$ in. long, approx., complete with pins.		B	..	1
5122	Type 439	650 microhenries, wire wound on iron core, with upper and lower mountings		B	..	1
5258	Type 443	$16\frac{7}{8}$ turns of 22 S.W.G. tinned copper wire.		B	..	1
5381	Type 456	$\frac{3}{4}$ in. o/d \times $1\frac{1}{8}$ in.; 5 turns, $\frac{1}{4}$ in. diam. copper wire, silver-plated; 2 spills soldered one turn from each end.		B	..	1
5382	Type 457	Tuning coil assembly, comprising $4\frac{1}{2}$ turns of 24 S.W.G. D.S.C. copper wire, wound on bakelite former (A.16212). Complete with collet (A.16199), slug (A.16196), assembled on mounting plate, $2\frac{1}{2}$ in. \times $1\frac{1}{8}$ in. \times 0.064 in. thick M.S.		B	..	1
5385	Type 460	Windings:— <i>Primary</i> , 150 turns of 42 S.W.G. S.S. en. copper wire, centre tapped. <i>Secondary</i> , 450 turns (3 \times 150) of 42 S.W.G. S.S. en. copper wire; inductance, 7 millihenries, $Q = 70$.		B	..	1
5386	Type 461	Windings:— <i>Primary</i> , 450 turns (3 \times 150) of 42 S.W.G. S.S. en. copper wire; inductance, 7 millihenries, $Q = 70$. <i>Secondary</i> , 40 turns of 36 S.W.G. S.S. en. copper wire.		B	..	1
5388	Type 463	Windings:— <i>Primary</i> , 396 turns (3 \times 132) of 42 S.W.G. S.S. en. copper wire; inductance, 3.7 millihenries, $Q = 75$. <i>Secondary</i> , 44 turns of 36 S.W.G. S.S. en. copper wire; inductance, 0.09 millihenries. Fitted with dust iron core.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCES—					
	<i>cont.</i>					
5389	Type 464 ...	Windings:— <i>Primary</i> , 40 turns of 36 S.W.G. S.S. en. copper wire. <i>Secondary</i> , 450 turns (3 × 150), 42 S.W.G. S.S. en. copper wire; inductance, 7.0 millihenries, Q = 70. Fitted with dust iron core.		B	each	1
5500	Type 467 ...	H.T. S.R.B. paper tube, 2 $\frac{5}{16}$ in. long × $\frac{3}{4}$ in. diam.; spigot mounting; 55 turns of 24 S.W.G. en. copper wire, close wound; tags.		B	„	1
5501	Type 468 ...	L.T. S.R.B. paper tube, 2 $\frac{5}{16}$ in. long × $\frac{3}{4}$ in. diam.; spigot mounting; 16 turns of 16 S.W.G. en. copper wire, close wound; tags.		B	„	1
5520	Type 487 ...	No. of turns 22, $\frac{1}{2}$, 24 D.S.C., tapped at 14, $\frac{1}{2}$, and 7, $\frac{3}{4}$ turns. Iron core.		B	„	1
5606	Type 496 ...	Windings:—2 turns and 9 turns of 22 S.W.G. tinned copper wire, spaced $\frac{1}{8}$ in. apart. Coil of 9 turns, tapped 3 turns from bottom; 2 turns wound at “earthy” end of former.		B	„	1
5736	Type 498 ...	Tuned by dust iron cores, 380 turns of 9/46 Litz S.S. en. wire; 1,750 microhenries ± 5 per cent.		B	„	1
5737	Type 499 ...	0.9 millihenries, Tufnol tubular former (76/13/1), wave wound with 142 + 135 turns of 40 S.W.G. D.S.C. copper wire, air core.		B	„	1
5738	Type 500 ...	10 millihenries, Tufnol tubular former (76/13/1), wave wound with 435 + 405 turns of 40 S.W.G. D.S.C. copper wire, air core.		B	„	1
5828	Type 502 ...	2.74 millihenries (without core), Tufnol tubular former (76/12/1), wave wound with (125 + 125) + 250 turns of 38 S.W.G. D.S.C. copper wire.		B	„	1
—	Cores, iron dust...	See Ref. No. 10C/5826 (for Type 501).		—	—	—
5829	Type 503 ...	26 millihenries (without core), Tufnol tubular former (76/12/1), wave wound with (445 + 445) + 890 turns of 40 S.W.G. D.S.C. copper wire.		B	each	1
—	Cores, iron dust...	See Ref. No. 10C/5826 (for Type 501).		—	—	—

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCES—					
	<i>cont.</i>					
5830	Type 504	170 millihenries (without core), Tufnol tubular former (76/12/1), wave wound with (990 + 990) + 1980 turns of 40 S.W.G. D.S.C. copper wire.		B	each	1
—	Cores, iron dust...	See Ref. No. 10C/5826 (for Type 501).		—	—	—
5833	Type 505	10 turns of 20 S.W.G. copper wire wound on Trolitol former. Inductance, 0.58 mH.		B	each	1
5834	Type 506	15 turns of 23 S.W.G. D.S. copper wire on vulcanite former, $\frac{1}{2}$ in. diam. \times $\frac{3}{4}$ in.		B	..	1
5920	Type 507	Iron core, paper former, 120 turns; paxolin bracket; 29 B microhenries.		B	..	1
5922	Type 509	Assembly of 2 coils overwound on tubular former.		B	..	1
5923	Type 510	1.8 millihenries... ..		B	..	1
5936	Type 515	4 $\frac{1}{2}$ turns and 1 turn, Steatite former, oval foot, 1 $\frac{1}{16}$ in. fixing centres, 6 B.A. holes; hex. former, 2 $\frac{1}{8}$ in. high, threaded 10 t.p.i.; trimmer cap.		B	..	1
11045	Type 517	Moulded former, 1 $\frac{1}{2}$ in. diam. \times 2 $\frac{5}{8}$ in. long, air core, 16 $\frac{1}{2}$ turns, 5.6 microhenries.		B	..	1
11046	Type 518	Moulded former, 1 $\frac{1}{2}$ in. diam. \times 2 $\frac{5}{8}$ in. long, air core, 29 $\frac{1}{2}$ turns, 18.5 microhenries.		B	..	1
11047	Type 519	Moulded former, 1 $\frac{1}{2}$ in. dia. \times 2 $\frac{5}{8}$ in. long; air core, with terminal strip, 344 turns, 2,266 microhenries, 8 sections, tapped 3rd and 5th sections.		B	..	1
11108	Type 521	2.4 mH, 0.5 mH. No. of turns 313 $\frac{1}{2}$, 140, 36 S.W.G., 36 S.W.G. Tuning and reaction tapped at 7 $\frac{1}{2}$ turns. D.S.C. copper coupling coil, 3 in. \times $\frac{1}{2}$ in. paxolin former, etc.		B	..	1
11152	Type 525	9 turns, 24 en. copper wire, dust iron core.		B	..	1
11153	Type 526	3 $\frac{1}{2}$ turns, 24 en. copper wire, dust iron core.		B	..	1
11166	Type 528		B	..	1
11242	Type 541	Aerial coil and bracket assembly, 4 $\frac{3}{8}$ turns + $\frac{3}{8}$ coupling turn.		B	..	1
11244	Type 543	Coil tuning		B	..	1
11249	Type 546	Delay link, comprising—1 resistance, 510 ohms; 20 condensers, 200 pfd.; and 20 coils 90 turns, 38 S.W.G. enamelled, on former, all wax-dipped after assembly.		B	..	1
11318	Type 550	Brass, 1 in. \times $\frac{1}{2}$ in. \times 2 $\frac{1}{2}$ in. long, cut away 1 $\frac{1}{2}$ in. \times $\frac{3}{8}$ in.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCES—					
	<i>cont.</i>					
11438	Type 580	4 turns of 20 S.W.G. cu. wire on $\frac{1}{4}$ in. former.		B	each	1
11456	Type 583	No. of turns 6		B	..	1
11457	Type 584	1st and 2nd R.F.		B	..	1
11458	Type 585	Grid		B	..	1
11503	Type 587	4 turns		B	..	1
11518	Type 591	Range 1, wave-wound coils on moulded formers.		B	..	1
11519	Type 592	Range 2, wave-wound coils on moulded formers.		B	..	1
11520	Type 593	Beacon, wave-wound coils on moulded formers.		B	..	1
11531	Type 599	H.F. $1\frac{1}{2}$ turns of 1 mm. tinned copper wire, 2 mm. pitch; length before winding, 60 mm.; internal dia., 8 mm.		B	..	1
11532	Type 600	H.F. $1\frac{3}{4}$ turns of 2 mm. tinned copper wire, 4 mm. pitch; length before winding, 110 mm.; internal dia., 8 mm.		B	..	1
11533	Type 601	H.F. $2\frac{1}{2}$ turns of 1 mm. tinned copper wire; internal dia., 8 mm.; length, 14 mm.		B	..	1
11534	Type 602	H.F. 3 turns of 2 mm. tinned copper wire, 4 mm. pitch; length, 25 mm.; internal dia., 13 mm.		B	..	1
11535	Type 603	H.F. $2\frac{1}{4}$ turns of 2 mm. tinned copper wire; length, 23 mm.; internal dia., 13 mm.		B	..	1
11584	Type 606	Steatite former, $4\frac{1}{4}$ in. long, 2 in. dia., 6 ribs grooved, 10 turns centre tapped, spigot mounted.		B	..	1
11615	Type 611	Half loop, $\frac{1}{8}$ radius, 20 S.W.G.		B	..	1
11640	Type 615	10 coils, 11 condensers, and 1 resistance assembled on insulating rod, and the whole wax-coated, mounted on bracket (D.P.4472).		B	..	1
12373	Type 621	9 coils on tubular former, with two brackets and terminal strip.		B	..	1
11710	Type 622	1 turn of 20 S.W.G. $\times \frac{1}{4}$ in. wide, S.P. copper.		B	..	1
11735	Type 624	10 coils mounted on brackets, with terminal plate; includes cover.		B	..	1
11820	Type 628	36 to 54 Mc/s, ebonite former, $\frac{1}{2}$ in. \times 1 in. \times $2\frac{1}{2}$ in. long. Diagonally wound $2\frac{3}{4}$ turns of 20 S.W.G. en. cu. wire.		B	..	1
11876	Type 635	632 mH. No. of turns 286, 40 S.W.G., 32.2 ohms. Secondary: 317 turns 34 S.W.G., 600 μ F., 9.2 ohms, enamelled copper wire.		B	..	1
11877	Type 636	No. of turns, 600 prim., 687 sec., 40 S.W.G. 40 S.W.G. enamelled copper wire.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref	Class of Store	Denom. of Qty.	Carton Unit Qty
1	2	3	4	5	6	7
	INDUCTANCES—					
		<i>cont</i>				
11878	Type 637	Primary—80 turns of 40 S.W.G. 82 micro-H., 9·7 ohms. Secondary—101 turns of 24 S.W.G., 75 micro-H. 0·57 ohms. Enamelled copper wire.		B	each	1
11879	Type 638	No. of turns, 190 prim., 221 sec., 40 S.W.G., 30 S.W.G. enamelled copper wire.		B	..	1
11880	Type 639		B	..	1
11882	Type 641	600 microhenries		B	..	1
11883	Type 642	2,400 microhenries		B	..	1
11885	Type 644	122·8 microhenries. No. of turns 122, 28 S.W.G.		B	..	1
11886	Type 645	461 μ H. No. of turns 263, 34 S.W.G. copper wire.		B	..	1
11887	Type 646	1,832 μ H. No. of turns 563, 40 S.W.G. copper wire.		B	..	1
11904	Type 655	Delay network, fitted with 10 Leeson wound coils (L.1-6).		B	..	1
11905	Type 656	24 turns 11 S.W.G. electrolytic copper wire, 12·5 in. o/d \times 6 in. deep.		B	..	1
11913	Type 657	531 micro-H., wound with 27/46 S.W.G. en. S.S.C. cu. wire.		B	..	1
11924	Type 658	Moulded former, 1½ in. dia. \times 2½ in. long, 8·5 micro-H., air core, 21 turns, tapped at 7, 9, and 15 turns.		B	..	1
11925	Type 659	Moulded former, 1½ in. dia. \times 2½ in. long, 28·6 micro-H., air core, 40 turns, tapped at 17 and 28 turns.		B	..	1
11941	Type 661	8 mH.		B	..	1
12006	Type 663	Variable H.F. current, phasing coil assembly of wire-wound former, iron dust core, etc.		B	..	1
12009	Type 664	3,000 turns 40 S.W.G. C. and S.S.C., ¾ in. long, ½ in. former, 125 mH.		B	..	1
12010	Type 665	350 turns 34 S.W.G. C. and S.S.C., ⅜ in. long, ½ in. former, 2 mH., without core.		B	..	1
12011	Type 666	16 turns 36 S.W.G. enamelled, ½ in. former, centre tapped.		B	..	1
12028	Type 671	1½ turns 10 S.W.G. tinned copper wire, silver plated, 1¼ in. i/d.		B	..	1
12029	Type 672	¾ turn 10 S.W.G. tinned copper wire, silver plated, 2¼ in. i/d.		B	..	1
12030	Type 673	1 turn ¼ in. copper tube, silver-plated, 3½ in dia., with clip.		B	..	1
12045	Type 675	400 \pm 25 kc/s, 66 turns + 315 turns, tapped, 36 S.W.G. D.S.C., wound on moulded hexagonal former, ⅝ in across flats \times 1⅞ in.		B	..	1
12119	Type 678	Two windings, each 425/·0052 enamel and S.S.C. copper wire, in series, on bakelite former, ½ in. o/d., with adjustable iron dust core.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCES—					
	<i>cont.</i>					
12121	Type 680 ...	6 turns of 20 S.W.G. tapped at 2½ turns, on hollow dystrene former, ⅝ in. o/d, with adjustable brass slug.		B	each	1
12122	Type 681 ...	17 turns 0.0076 in. S.S.C., on bakelite former, ½ in. o/d, with adjustable iron dust core.		B	..	1
12123	Type 682 ...	4 turns of 20 S.W.G. bare tinned copper wire, tapped at 2 turns. Former, ⅝ in. o/d.		B	..	1
12163	Type 684 ...	25 micro-H., 55 turns of 22 S.W.G. en. cu. wire, spaced 0.02 in. tapped at 9½ turns; S.R.B.P. former, 4.37 in. × 1 in. dia.; complete with leads.		B	..	1
12169	Type 689 ...	19 turns of 24 S.W.G. en. wire on hollow trolitol former, ½ in. o/d × 1½ in. long.		B	..	1
12170	Type 690 ...	12 turns of 24 S.W.G. en. wire on hollow trolitol former, ½ in. o/d × 1½ in. long.		B	..	1
12199	Type 693 ...	2 windings, 6 + 11 turns of 30 S.W.G. copper wire on vulcanite former, with 3 soldering pins.		B	..	1
12200	Type 694 ...	86.5 turns of 38 S.W.G. copper wire on loaded ebonite former, 0.37 in. dia. × 2 in.		B	..	1
12201	Type 695		B	..	1
12209	Type 698 ...	17 turns of No. 22E/ copper wire on 0.5 in. dia. former, in metal screening can.		B	..	1
12280	Type 716 ...	Used on A.R.I.5513 ...		B	..	1
12297	Type 717 ...	Used on A.R.I.5194 ...		B	..	1
12298	Type 718 ...	H.F. coil. Used on A.R.I.5194		B	..	1
12299	Type 719 ...	Oscillator. Used on A.R.I.5194		B	..	1
12360	Type 723 ...	Former, W.T.16930/1A. Wound 6 turns 26 S.W.G. D.S.C. per slot, clamped between two brackets.		B	..	1
12364	Type 724 ...	No. of turns 18, 36 S.W.G. enamelled copper wire on former, ½ in. dia. × 1½ in. long, with tags.		B	..	1
12365	Type 725 ...	16 turns S.W.G. 36 enamelled copper wire, on former, ½ in. dia. × 1½ in. long, with 4 tags.		B	..	1
12367	Type 727 ...	100 turns 38 E.S.S. wire wound on ½ in. dia. former. Coil, ⅜ in. long, 13.5 mH.		B	..	1
12397	Type 732 ...	28½ turns of 20 S.W.G. en. cu. wire, tapped at 15½ turns from start; 1⅞ in. o/d × 1⅞ in. long former.		B	..	1
12445	Type 743		B	..	1
12446	Type 744		B	..	1
12447	Type 745		B	..	1
12515	Type 746 ...	Aerial coil and bracket assembly, 4½ turns + ½ coupling turn.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCES—					
	<i>cont.</i>					
12545	Type 749	12 turns S.W.G. 36 enamelled copper wire, on former, $\frac{1}{2}$ in. dia. \times $\frac{1}{4}$ in. long with 4 tags.		B	each	1
12547	Type 751	17 + 2 turns S.W.G. 36 enamelled copper wire, on former, $\frac{1}{2}$ in. dia. \times $1\frac{1}{4}$ in. long, with 4 tags.		B	..	1
12548	Type 752	Windings:—Primary, 75 turns No. 42 S.W.G. S.S. en. cu. wire. Secondary, 450 turns (3 \times 150) 42 S.W.G. S.S. en. cu. wire. Inductance, 7 mH. Q = 70.		B	..	1
12549	Type 753	Windings:—Primary, 90 turns (2 \times 45) 36 S.W.G. en. cu. wire. Secondary, 100 turns (2 \times 50) 36 S.W.G. en. cu. wire.		B	..	1
12550	Type 754	Windings:—120 turns 34 S.W.G. S.S. en. cu. wire. Inductance, 500 mH. \pm 5 per cent., 150 K/c.		B	..	1
12551	Type 755	Primary, 54 turns (18 \times 3) 32 S.W.G. S.S. en. cu. wire. Secondary, 6 turns (6 \times 1) 32 S.W.G. S.S. en. cu. wire.		B	..	1
12552	Type 756	Primary, 54 turns (18 \times 3) 32 S.W.G. S.S. en. cu. wire. No secondary.		B	..	1
12553	Type 757	Primary, 54 turns (18 \times 3) 32 S.W.G. S.S. en. cu. wire. Secondary, 6 turns (6 \times 1) 32 S.W.G. S.S. en. cu. wire. Centre tapped.		B	..	1
12566	Type 758	Coil, 1st winding, $2\frac{1}{4}$ turns of 0.0148 in. dia. S.S.C. en. cu. wire, close wound anti-clockwise. 2nd winding, $14\frac{1}{4}$ turns of 0.0148 in. dia. S.S.C. en. cu. wire, close wound clockwise.		B	..	1
12576	Type 759	3 turns 14 S.W.G. cu. wire, silver-plated, mounted on S.R.B.P. panel, 1.25 in. \times 0.69 in., with brass tag plates.		B	..	1
12577	Type 760	2.6 μ H., 6 + 11 turns of 30 S.W.G. cu. wire, on vulcanite former, mounted on S.R.B.P. panel, 1.25 in. \times 0.69 in., with brass tag plates.		B	..	1
12580	Type 761	2.77 μ H., 17 turns 0.0148 in. cu. wire, on former, 0.5 in. dia. \times 1.37 in.		B	..	1
12587	Type 762	9 $\frac{1}{2}$ turns of 20 S.W.G. tinned copper, wound on Buller ceramic former, No. E.A. 14039.		B	..	1
12604	Type 766	I.F. coil		B	..	1
12639	Type 772	16 turns of 26 S.W.G. enamelled copper wire, double spaced, on former 2 in. \times $\frac{5}{16}$ in. dia. complete with diode clip.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref	Class of Store	Denom. of Qty	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCES—					
	<i>cont.</i>					
12640	Type 773	1,000 turns of 40 S.W.G., on former, 1½ in. × ½ in. dia.		B	each	1
12647	Type 774	Delay link. Foil screened loaded ebonite former, 0.38 in. dia. × 7.56 in. long, tapped 4 B.A. at ends, containing 30 coils of 42 S.W.G. D.S.C. copper wire, each 0.11 in. wide at 0.22 in. spacing. Varnished and covered with cardboard.		B	..	1
12648	Type 775	Windings:—48 turns of No. 34 S.W.G. en. cu. wire. Inductance, 28.6 mH. ± 5 per cent. at 1 m/c.		B	..	1
12692	Type 776	600 μH. 200 turns of 34 gauge D.S.C. copper wire, on Tufnol former, 1½ in. × ½ in. dia., single pie, ¼ in. wide.		B	..	1
12695	Type 777	400 μH., 1,500 turns. 3 sections, wave-wound, ½ in. wide, ½ in. spacing, 1.4 in. dia. Former wound with 24 S.W.G. wire E. and S.S. covered.		B	..	1
12710	Type 778	Oscillator band 1. Main winding, 21¾ turns of 32 S.W.G. D.S.C. wire. Subsidiary winding, 5¾ turns of 32 S.W.G. D.S.C. wire.		B	..	1
12711	Type 779	1st and 2nd R.F. band 1. Main winding, 31¾ turns of 34 S.W.G. D.S.C. wire, tap at 2½ turns.		B	..	1
12712	Type 780	Aerial band 1. Main winding, 31¾ turns of 34 S.W.G. D.S.C. wire. Subsidiary winding, 2¾ turns of 34 S.W.G. D.S.C. wire.		B	..	1
12713	Type 781	Oscillator, band 2. Main winding, 11¾ turns of 30 S.W.G. D.S.C. wire. Subsidiary winding, 4¾ turns of 30 S.W.G. D.S.C. wire.		B	..	1
12714	Type 782	2nd R.F., band 2. Main winding, 15¾ turns of 32 S.W.G., D.S.C. wire. Tap at 2½ turns.		B	..	1
12715	Type 783	1st R.F., band 2. Main winding, 15¾ turns of 32 S.W.G. D.S.C. wire. Tap at 1½ turns.		B	..	1
12716	Type 784	Aerial, band 2. Main winding, 15¾ turns of 32 S.W.G. D.S.C. wire. Subsidiary winding, 1¾ turns of 32 S.W.G. D.S.C. wire.		B	..	1
12717	Type 785	Oscillator, band 3. Main winding, 6¾ turns of 26 S.W.G. D.S.C. wire. Tap at 1½ turns, twisted and soldered to main coil. Subsidiary winding, 3¾ turns of 30 S.W.G. D.S.C. wire.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCES—					
	<i>cont.</i>					
12718	Type 786	2nd R.F., band 3. Main winding, $9\frac{1}{4}$ turns of 26 S.W.G. D.S.C. wire. Tap at $2\frac{1}{2}$ turns.		B	each	1
12719	Type 787	1st R.F., band 3. Main winding, $9\frac{3}{4}$ turns of 26 S.W.G., D.S.C. wire. Tap at $1\frac{1}{2}$ turns twisted and soldered to main winding.		B	..	1
12720	Type 788	Aerial, band 3. Main winding, $9\frac{3}{4}$ turns of 26 S.W.G. D.S.C. wire.		B	..	1
12721	Type 789	Oscillator, band 4. Main winding, $3\frac{3}{4}$ turns of 22 S.W.G. enamelled copper wire. Tap at $1\frac{1}{2}$ turns and solder to main coil. Subsidiary winding, $3\frac{1}{4}$ turns of 26 S.W.G. D.S.C. wire, $1\frac{1}{2}$ turns to be interwound with main winding.		B	..	1
12722	Type 790	2nd R.F., band 4. Main winding, $5\frac{3}{4}$ turns of 22 S.W.G. enamelled copper wire. Overall length of main coil centre to centre of wire = $\frac{9}{16}$ in. Tap at $2\frac{1}{2}$ turns and solder to main coil.		B	..	1
12723	Type 791	1st R.F., band 4. Main winding, $5\frac{3}{4}$ turns of 22 S.W.G. enamelled copper wire. Overall length of main coil centre to centre of wires = $\frac{9}{16}$ in. Tap at $1\frac{1}{2}$ turns and solder to main coil.		B	..	1
12724	Type 792	Aerial, band 4. Main winding, $5\frac{3}{4}$ turns of 22 S.W.G. enamelled copper wire. Overall length of main coil centre to centre of wires = $\frac{9}{16}$ in. Subsidiary winding, $\frac{7}{8}$ of a turn 26 S.W.G. D.S.C. wire. To be interwound with beginning of main coil.		B	..	1
12725	Type 793	Oscillator, band 5. Main winding, $1\frac{3}{4}$ turns of 18 S.W.G. enamelled copper wire. Main coil length overall centre to centre of wires = $\frac{5}{16}$ in. Subsidiary winding, $3\frac{1}{4}$ turns of 26 S.W.G. D.S.C. wire ($1\frac{1}{2}$ turns interwound).		B	..	1
12726	Type 794	2nd R.F., band 5. Main winding, $3\frac{1}{4}$ turns of 18 S.W.G. tinned copper wire. Tap at $1\frac{1}{2}$ and $\frac{3}{4}$ of a turn. Overall length of main winding, centre to centre of wire = $\frac{9}{16}$ in.		B	..	1
12727	Type 795	1st R.F., band 5. Main winding, $3\frac{3}{4}$ turns of 18 S.W.G. tinned copper wire. Tap at $\frac{5}{8}$ of a turn and solder to main coil. Overall length of main winding, centre to centre of wires = $\frac{9}{16}$ in.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCES—					
	<i>cont.</i>					
12728	Type 796	Aerial, band 5. Main winding, $3\frac{1}{4}$ turns of 18 S.W.G. tinned copper wire. Tap at $\frac{2}{3}$ of a turn and solder to main coil. Overall length of main winding, centre to centre of wire = $\frac{7}{32}$ in.		B	each	1
12781	Type 801	Wire wound on former, 2 turns of 22 S.W.G., tinned copper.		B	..	1
12782	Type 802	1 turn of 28 S.W.G. $\times \frac{5}{32}$ in copper strip.		B	..	1
12786	Type 803	40 S. W. G., double cotton covered; 3 sections, $4\frac{1}{8}$, 5, and 5 turns.		B	..	1
12787	Type 804	30 S.W.G., double silk covered; 3 sections, 4, 5, and $4\frac{1}{2}$ turns.		B	..	1
12788	Type 805	30 S.W.G., double silk covered; 4 sections, $4\frac{1}{2}$, $4\frac{1}{8}$, 5, and 5 turns.		B	..	—
12789	Type 806	30 S.W.G., double silk covered; sections, $4\frac{1}{8}$, 5, and 5 turns on former.		B	..	1
12790	Type 807	30 S.W.G., double silk covered; 3 sections, 4, 5, and $4\frac{1}{2}$ turns. Tapped at $1\frac{7}{8}$ turns and 2nd section on former		B	..	1
12791	Type 808	Wire wound on former, 3 windings, $12\frac{1}{4}$ turns of 20 S.W.G. tinned copper, $2\frac{3}{4}$ turns of 28 S.W.G. double silk covered, 2 turns of 20 S.W.G. tinned copper.		B	..	1
12792	Type 809	Wire wound on former. 3 windings, $6\frac{1}{2}$ turns of 20 S.W.G. tinned copper, 1 turn of 20 S.W.G. tinned copper, $1\frac{3}{4}$ turns of 28 S.W.G. double silk covered		B	..	1
12793	Type 810	Wire wound on former. 3 windings, 3 turns of 20 S.W.G. tinned copper, 1 turn of 20 S.W.G. tinned copper, 1 turn of 28 S.W.G. double silk covered.		B	..	1
12794	Type 811	Wire wound on former. $12\frac{1}{2}$ turns of 20 S.W.G. tinned copper.		B	..	1
12795	Type 812	Wire wound on former. $6\frac{1}{2}$ turns of 20 S.W.G. tinned copper.		B	..	1
12796	Type 813	Wire wound on former. $3\frac{1}{4}$ turns of 20 S.W.G. tinned copper.		B	..	1
12797	Type 814	Wire wound on former. 4 turns of 22, S.W.G. tinned copper.		B	..	1
12886	Type 846	267 mH, 5/44 Litz; 3 sections, $29\frac{7}{8}$, 30, and 30 turns.		B	..	1
12887	Type 847	88 mH., 5/44 Litz; 3 sections, $17\frac{7}{8}$, 17, and 17 turns.		B	..	1
13054	Type 877	Copper wire coil, 14 S.W.G. silver-plated; 4 turns, $\frac{1}{8}$ in. pitch, $\frac{1}{2}$ in. dia. mandrel.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty
1	2	3	4	5	6	7
	INDUCTANCES—					
	<i>cont.</i>					
13055	Type 878 ...	Copper wire coil, 14 S.W.G. silver-plated; 3 turns, $\frac{1}{8}$ in. pitch, on $\frac{3}{8}$ in. dia. mandrel.		B	each	1
13056	Type 879 ...	Copper wire coil, 14 S.W.G. silver-plated; 2 turns, $\frac{1}{8}$ in. pitch on $\frac{3}{8}$ in. dia. mandrel.		B	..	1
13090	Type 881 ...	Aerial coupling, 3 turns 12 S.W.G. silver-plated copper wire, on 14 mm. dia mandrel, $2\frac{7}{16}$ in. \times $1\frac{3}{8}$ in. overall dimensions.		B	..	1
13091	Type 882 ...	Final anode. 6 turns $\frac{1}{8}$ in. dia. silver-plated copper tube on 23 mm. dia. mandrel, 2 in. long.		B	..	1
13092	Type 883 ...	Penultimate anode. $5\frac{1}{2}$ turns $\frac{1}{8}$ in. dia. silver-plated copper tube on 14 mm. mandrel, $\frac{1}{4}$ in. pitch, $1\frac{3}{4}$ in. long.		B	..	1
13108	Type 885 ...	$3\frac{1}{2}$ turns of 28 S.W.G., with variable iron dust core.		B	..	1
13147	Type 907 ...	A.G.S. coil. Used on A.R.I.5131		B	..	1
13246	Type 916 ...	Enamelled and cotton braided, 19 in. \times 11 in. dia. Tapped every 8 turns. 128 turns 243/0006 Litz wire.		B	..	1
13270	Type 917 ...	I.F. coupling, 142 microhenries, 67 turns 40 S.W.G. enamelled S.S.C.		B	..	1
13378	Type 921 ...	25 turns of wire on former, $\frac{1}{2}$ in. dia. \times $1\frac{1}{4}$ in. long.		B	..	1
13379	Type 922 ...	24 turns 23 S.W.G. on former, without bracket.		B	..	1
13380	Type 923 ...	24 turns 23 S.W.G. enam. cu. wire, with bracket.		B	..	1
13381	Type 924 ...	24 turns 23 S.W.G. enam. cu. wire.		B	..	1
13394	Type 925 ...	25 H., 30 mA. D.C. Resistance, 750 ohms.		B	..	1
13403	Type 926 ...	Secondary winding of I.F. transformer, Type 311. 20 ft. 30 S.W.G. D.S.C. 92 turns.		B	..	1
13404	Type 927 ...	Primary winding of I.F. transformer, Type 311. 16 ft. 30 S.W.G. D.S.C. 75 turns.		B	..	1
13405	Type 928 ...	Secondary winding of diode transformer, Type 349.		B	..	1
13406	Type 929 ...	Primary winding of diode transformer, Type 349.		B	..	1
13417	Type 932 ...	66.1 microhenries \pm 0.5 per cent. at 1,000 cycles, 14 ft., 38 S.W.G. D.S.C.		B	..	1
13418	Type 933 ...	I.F., 154 microhenries, 72 turns 40 S.W.G.		B	..	1
13419	Type 934 ...	I.F., 278 microhenries, 96 turns 40 S.W.G.		B	..	1
13428	Type 939 ...	16 μ H, 1,070 μ H, 5 per cent., 26 T. 1 per cent. 230 T. 40 DE. 40 DE. Rectangular screening can, slotted; fixing feet winding tags, 1-2, 3-4.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCES—					
	<i>cont.</i>					
13509	Type 945	Relay coil, wire wound on bobbin C.P.623, 4,160 turns of 0.2946 in. dia. bare enamelled copper. Nominal resistance, 50 ohms.		B	each	1
13514	Type 946	"A" winding, 19 turns 30/48 Litz wire; "B" winding, 4 turns 38 S.W.G. copper wire. Wound on former, complete with postage stamp trimmer.		B	..	1
13515	Type 947	Coil, 19 turns 30/48 Litz wire. Wound on former, complete with postage stamp trimmer.		B	..	1
13516	Type 948	Coil, with 2 windings. Complete with 300 $\mu\mu\text{F}$. and 200 $\mu\mu\text{F}$. condensers and resistances, 220,000 ohms, $\frac{1}{4}$ watt, in aluminium can.		B	..	1
13517	Type 949	"A" winding, 46 turns 9/45 Litz wire; "B" winding, 20 turns 38 S. W. G. copper wire. Wound on former, complete with postage stamp trimmer.		B	..	1
13518	Type 950		B	..	1
13519	Type 951		B	..	1
13520	Type 952		B	..	1
13521	Type 953		B	..	1
13522	Type 954		B	..	1
13523	Type 955		B	..	1
13524	Type 956		B	..	1
13525	Type 957		B	..	1
13526	Type 958	400 μH . Two sections of 155 turns, $\frac{3}{32}$ in. apart.		B	..	1
13527	Type 959	600 μH . Two sections of 180 turns, $\frac{3}{32}$ in. apart.		B	..	1
13528	Type 960	740 μH . Two sections of 250 turns, $\frac{1}{4}$ in. apart.		B	..	1
13536	Type 961	$5\frac{1}{4}$ turns of 18 S.W.G. copper wire and $\frac{5}{16}$ in. dia. distrene sleeve, on bakelite mounting, with brass adjustable core. Coil tapped at mid-point.		B	..	1
13537	Type 962	$3\frac{3}{4}$ turns of 18 S.W.G. copper wire and $\frac{5}{16}$ in. dia. distrene sleeve, on bakelite mounting, with brass adjustable core.		B	..	1
13538	Type 963	Coil of 4 turns and distrene sleeve on bakelite mounting, with brass adjustable core.		B	..	1
13539	Type 964	Coil of $2\frac{1}{2}$ turns and distrene sleeve on bakelite mounting, with brass adjustable ends.		B	..	1
13541	Type 965	$76\frac{1}{2}$ turns of 40 S.W.G. en. copper wire on former, $\frac{1}{2}$ in. dia., with bracket.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCES—					
	<i>cont.</i>					
13562	Type 968	Coil on former in can, $1\frac{1}{2}$ in. square \times $3\frac{3}{8}$ in. External lead, $3\frac{1}{2}$ in. long.		B	each	1
13563	Type 969	Coil on former in can, $1\frac{1}{2}$ in. square \times $3\frac{3}{8}$ in. External lead, $4\frac{1}{2}$ in. long.		B	..	1
13564	Type 970	2 coils on iron core, complete with two condensers in can, $1\frac{3}{4}$ in. square \times 3 in.		B	..	1
13565	Type 971	Voltmeter coil; 3 coils on former. Coils "A" and "C" each 170 turns of 3/44 Litz S.S.C. Coil "B" 15 turns of 38 S.W.G. en. S.S.C. copper wire wound between "A" and "C". The whole contained in can.		B	..	1
13572	Type 972	850 μ H \pm 1 per cent.		B	..	1
13573	Type 973	H.F. transformer, 150 kc/s., 20,000 ohms: 75 ohms. Rectangular screened, two hole base fixing, $2\frac{3}{8}$ in. centres.		B	..	1
13585	Type 977	No. of turns 7. 36 S. W. G. enamelled copper wire on $\frac{1}{2}$ in. diameter former.		B	..	1
13598	Type 979	300 turns 39 S.W.G. D.S.C. wire, tapped at 50 turns, on former, 1 in. \times $\frac{1}{2}$ in. dia. 4 tags, and stud screwed 4 B.A. \times $\frac{1}{16}$ in. long.		B	..	1
13618	Type 980	775 turns of 38 S.W.G. en. copper wire, wave-wound (10 μ H. approx.).		B	..	1
13639	Type 982	531 μ H. \pm 10 per cent., 155 turns of 27/46 wire, iron dust core in screening case. (Inductor.)		B	..	1
13640	Type 983	Primary, 200 μ H. \pm 5 per cent. Secondary, 1,330 μ H. \pm 5 per cent. Valence \pm 1 per cent. Iron dust core in screening case, two hole fixing.		B	..	1
13688	Type 984	2,700 turns 40 S.W.G. S. silk-covered copper wire. Former, $\frac{3}{4}$ in. \times $\frac{1}{2}$ in. dia., with dust core.		B	..	1
13696	Type 986	80 turns 38 S.W.G. en. copper wire, $\frac{1}{4}$ in. former.		B	..	1
13724	Type 992	Silver-plated assembly. Slotted brass bar, $2\frac{1}{2}$ in. \times $1\frac{1}{16}$ in. \times $\frac{1}{2}$ in., with spring clips. 150–300 mc/s.		B	..	1
13725	Type 993	Wire-wound assembly of ebonite block, 1 in. \times $\frac{1}{2}$ in. \times $2\frac{1}{2}$ in., with 2 sockets and spring clips. 35–58 mc/s.		B	..	1
13726	Type 994	Wire-wound assembly of ebonite block, 1 in. \times $\frac{1}{2}$ in. \times $2\frac{1}{2}$ in., with 2 sockets and spring clips. 10–18 mc/s.		B	..	1
13748	Type 997	70 turns 40 S.W.G. en. copper wire on Tufnol former, $1\frac{3}{16}$ in. \times $\frac{3}{8}$ in.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCES—					
	<i>cont.</i>					
13755	Type 999 ...	Aerial coil, 2 turns of 16 S.W.G. bare T/C wire, spaced 0.16 in.; i/d $\frac{5}{32}$ in.		B	each	1
13756	Type 1000 ...	T.R.F. coil, 3 turns of 16 S.W.G. bare T/C wire, spaced 0.125 in. i/d $\frac{5}{32}$ in.		B	..	1
13757	Type 1001 ...	T. R. F. coil, $3\frac{1}{2}$ turns of 16 S.W.G. bare T/C wire. Spaced 0.125 in.; i/d $\frac{5}{32}$ in.		B	..	1
13758	Type 1002 ...	I/F coil, 8 turns on Tufnol former. Dust-iron core, trimmed.		B	..	1
13759	Type 1003 ...	I/F transformer. Primary, 10 turns 26 S.W.G. en. wire. Secondary, 1 turn 26 S.W.G. en. wire. Dust iron-core, trimmed.		B	..	1
13799	Type 1009 ...	No. of turns, 23. 28 S.W.G. enamelled copper wire.		B	..	1
13800	Type 1010 ...	17 turns of 22 S.W.G. en. copper wire on $\frac{3}{8}$ in. dia. \times $1\frac{1}{4}$ in. long former.		B	..	—
13822	Type 1012 ...	$9\frac{1}{2}$ turns 26 S.W.G. en. copper on hollow trolitol former (Pye 55276). Dust-iron cored (10B/1336, Type 2, Neosid T.C. 8/1.25 MNX).		B	..	1
13824	Type 1014 ...	22 turns 26 S.W.G. en. copper wire on hollow trolitol former (Pye 55276). Dust-iron cored (10B/1336, Type 2, Neosid T.C. Q/1125 MNX).		B	..	1
13836	Type 1015 ...	No. of turns, 40. 28 D.C.C. 1 in. dia. former made of R.M. 70.		B	..	1
13920	Type 1024 ...	16 S.W.G. cu. wire, 3 turns, 0.345 in. i/d at 0.109 in. pitch, extended ends.		B	..	1
13921	Type 1025 ...	As Type 1024, but with additional connecting strip.		B	..	1
13922	Type 1026 ...	16 S.W.G. cu. wire, 3 turns, 0.290 in. i/d at 0.109 in. pitch, extended ends.		B	..	1
13923	Type 1027 ...	16 turns 0.0124 in. dia. en. cu. wire on vulcanite former, 0.5 in. dia. \times 1.37 in.		B	..	1
13924	Type 1028 ...	7 turns 16 S.W.G. tinned cu. wire, wound on grooved vulcanite former, 0.953 in. o/d \times 0.75 in. i/d \times 1.281 in.		B	..	1
13925	Type 1029 ...	11 turns 18 S.W.G. tinned cu. wire, wound on grooved vulcanite former, 0.95 in. o/d \times 0.75 in. i/d.		B	..	1
13926	Type 1030 ...	3 turns 16 S.W.G. 0.462 in. i/d at 0.25 in. pitch, extended ends.		B	..	1
13927	Type 1031		B	..	1
13942	Type 1032 ...	2 wave-wound coils on silvanite former, $\frac{5}{8}$ in. dia. \times $1\frac{1}{8}$ in. long.		B	..	1
13956	Type 1033 ...	Quench oscillation, 265 turns 34 S.W.G. D.S.C. Tapped at 230.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCES—					
	<i>cont.</i>					
13997	Type 1040 ...	Coil, $9\frac{1}{2}$ turns (7 turns per in.) of 0.048 in. dia. tinned copper wire on a bakelite former, $2\frac{1}{2}$ in. \times $\frac{3}{4}$ in. \times $\frac{1}{16}$ in. Fixing centres $2\frac{1}{8}$ in.		B	each	1
14011	Type 1042 ...	8 turns then 2 turns 26 S.W.G. en. cu. wire, wound clockwise on former (10A/14279), with variable iron-dust core (10B/1336).		B	..	1
14034	Type 1045 ...	L.W. Aerial coil		B	..	1
14035	Type 1046 ...	M.W. Aerial coil		B	..	1
14036	Type 1047 ...	L.W. Intervalve coil		B	..	1
14037	Type 1048 ...	M.W. Intervalve coil		B	..	1
14038	Type 1049 ...	L.W. Oscillator coil		B	..	1
14039	Type 1050 ...	M.W. Oscillator coil		B	..	1
14040	Type 1051 ...	B.F.O. coil		B	..	1
14042	Type 1052 ...	Loading coil		B	..	1
14081	Type 1058 ...	Oscillator coil		B	..	1
14093	Type 1059 ...	1.8 μ H. \pm 10 per cent.		B	..	1
14094	Type 1060 ...	330 μ H. \pm 2 per cent.		B	..	1
14095	Type 1061 ...	497 μ H. \pm 2 per cent.		B	..	1
14096	Type 1062 ...	0.72 μ H. \pm 15 per cent.		B	..	1
14097	Type 1063 ...	0.4 μ H. \pm 10 per cent.		B	..	1
14105	Type 1064 ...	Bakelite former, $2\frac{3}{16}$ in. \times 1 in. o/d, 2 windings:—(1) $14\frac{3}{4}$ turns 36 S.W.G. en. copper wire, wound 114 T.P.J. (2) $3\frac{1}{4}$ turns of 26 S.W.G. E.C. wire, close wound.		B	..	1
14106	Type 1065 ...	Bakelite former, $2\frac{3}{16}$ in. \times 1 in. o/d, 2 windings:—(1) $19\frac{1}{4}$ turns of 36 S.W.G. E.C. wire. (2) $14\frac{3}{4}$ turns of 36 S.W.G. E.C. wire.		B	..	1
14107	Type 1066 ...	Bakelite former, $2\frac{3}{16}$ in. \times 1 in. o/d, 4 windings:—(1) $11\frac{3}{4}$ turns 36 S.W.G. E.C. wire. (2) $18\frac{7}{8}$ turns 36 S.W.G. E.C. wire. (3) $18\frac{7}{8}$ turns 36 S.W.G. E.C. wire. (4) $9\frac{3}{4}$ turns 36 S.W.G. E.C. wire.		B	..	1
14120	Type 1067 ...	20.73 μ H.		B	..	1
14121	Type 1068 ...	17.69 μ H.		B	..	1
14122	Type 1069 ...	9.94 μ H.		B	..	1
14123	Type 1070 ...	458.1 μ H., 28 S.W.G. D.S.C., wound on colvern 5-flange bobbin.		B	..	1
14206	Type 1079 ...	26 turns of 18 S.W.G. en. copper wire on former, 3 in. \times 1 in. dia. 1st doubler coil.		B	..	1
14207	Type 1080 ...	9 turns of 18 S.W.G. en. copper wire on former, $1\frac{3}{8}$ in. \times 1 in. dia. 2nd doubler coil.		B	..	1
14214	Type 1081 ...	Copper, 2 turns, $2\frac{3}{8}$ in. mean dia., centre tapped, with 3 banana plugs sweated in position at $\frac{1}{2}$ in. spacing.		B	..	—
14215	Type 1082 ...	Copper, 1 turn, $2\frac{3}{8}$ in. mean dia., centre tapped, with 3 banana plugs sweated in position at $\frac{1}{2}$ in. spacing.		B	..	—

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCES—					
	<i>cont.</i>					
14236	Type 1083 ...	Second triplex anode coil ...		B	each	1
14237	Type 1084 ...	Oscillator anode coil ...		B	"	1
14238	Type 1085 ...	First triplex anode coil ...		B	"	1
14239	Type 1086 ...	Double grid coil ...		B	"	1
14240	Type 1087 ...	Double anode coil ...		B	"	1
14241	Type 1088 ...	Centre aerial amplifier grid coil		B	"	1
14242	Type 1089 ...	Centre aerial amplifier anode coil.		B	"	1
14243	Type 1090 ...	Outer aerial amplifier coil ...		B	"	1
14244	Type 1091 ...	Outer aerial amplifier coil ...		B	"	1
14245	Type 1092 ...	Outer aerial amplifier coil ...		B	"	1
14246	Type 1093 ...	Centre aerial coupling coil ...		B	"	1
14247	Type 1094 ...	Outer aerial coupling coil ...		B	"	1
14253	Type 1095 ...	2½ turns No. 22 S.W.G. T. cu. wire on hollow trolitol former, ½ in. o/d × 1½ in. long.		B	"	1
14254	Type 1096 ...	7 turns, tapped at 2½, 22 S.W.G. tinned copper, on hollow trolitol former, ½ in. o/d × 1½ in. long.		B	"	1
14262	Type 1097 ...	3 turns of 18 S.W.G. copper wire on moulded former.		B	"	1
14265	Type 1098 ...	9 turns of 20 S.W.G. copper wire on loaded ebonite former, ⅜ in. dia. × 1¼ in. long.		B	"	1
14275	Type 1100 ...	No. of turns, 1,250. 38 E.S.S., wound on ¼ in. dia. former.		B	"	1
14276	Type 1101 ...	No. of turns, 14. 36 S.W.G. enam. copper, on former, ½ in. dia. × 1¼ in. long.		B	"	1
14277	Type 1102 ...	No. of turns, 17. 36 S.W.G. enam. copper, on former, ½ in. dia. × 1¼ in. long.		B	"	1
14286	Type 1103 ...	5 coils, each 1 μH., wound on former, complete with brackets and dividing strips.		B	"	1
14288	Type 1105 ...	8 coils, each 62 μH., wound on former, complete with brackets and dividing strips.		B	"	1
14289	Type 1106 ...	6 coils, each 160 μH., wound on former, complete with brackets and dividing strips.		B	"	1
14290	Type 1107 ...	20¾ turns 34 S.W.G. en. copper wire on former, ⅜ in. o/d, 8.5 μH. ± ½ per cent.		B	"	1
14304	Type 1112 ...	12 turns of 20 S.W.G. tinned copper wire, centre tapped, on loaded ebonite former.		B	"	1
14305	Type 1113 ...	2 turns and 11 turns of 28 S.W.G. en. copper wire on Pye former (10A/14279).		B	"	1
14306	Type 1114 ...	9 turns of 28 S.W.G. en. copper wire on Pye former (10A/14279).		B	"	1
14307	Type 1115 ...	2 turns and 9 turns of 29 S.W.G. en. copper wire on Pye former (10A/14279).		B	"	1
14308	Type 1116 ...	22 turns of 20 S.W.G. en. copper wire on Pye former (10A/14279).		B	"	1
14312	Type 1117 ...	10 turns of 26 S.W.G. wire, en., on former (10A/14279).		B	"	1.

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCES—					
	<i>cont.</i>					
14313	Type 1118 ...	Primary, 8 turns. Secondary, 2 turns of 26 S.W.G. en. wire on former (10A/14279).		B	each	1
14314	Type 1119 ...	Primary, 8 turns. Secondary, 1½ turns of 26 S.W.G. en. wire on former (10A/14279).		B	..	1
14315	Type 1120 ...	9¾ turns 20 gauge tinned copper wire, wound on Buller former.		B	..	1
14316	Type 1121 ...	4½ turns 20 gauge tinned copper wire, wound on Buller former.		B	..	1
14323	Type 1122 ...	Primary, 9 turns. Secondary, 2 turns of 26 S.W.G. enamelled wire on former 10A/14279.		B	..	1
14339	Type 1123 ...	Assembly of winding and former		R	..	1
14344	Type 1124 ...	Coil I.F., 1st		B	..	1
14348	Type 1127 ...	Coil, short wave, 1.48 ohms. Inductance, 129 μH. 128 turns 28 S.W.G.		B	..	1
14352	Type 1128 ...	Coil, medium wave, enamelled, 295, 34 S.W.G.		B	..	1
14353	Type 1129 ...	Coil, short wave, enamelled, 630, 40 S.W.G.		B	..	1
14358	Type 1132 ...	No. of turns, 7. 20 S.W.G. Tapped at 2 points, 4 T. and 5¼ T. No core former, unglazed.		B	..	1
14359	Type 1133 ...	No. of turns, 9. 30 S.W.G. enam. copper. Tuning inductance, with dust core, coded blue.		B	..	1
14360	Type 1134 ...	No. of turns, 8. 30 S.W.G. enam. copper. Tuning inductance, with dust core, coded green.		B	..	1
14410	Type 1136 ...	No. of turns, 7½. 30 S.W.G. enam. copper. Tuning inductance, with dust core, coded red.		B	..	1
14411	Type 1137 ...	No. of turns, 7 and 11. 30 S.W.G. enam. copper, 2 parts. Tuning inductance, with dust core, coded black.		B	..	1
14412	Type 1138 ...	No. of turns, 2 and 12. 30 S.W.G. enam. copper. Tuning inductance, with dust core, 2 parts, coded yellow.		B	..	1
14413	Type 1139 ...	No. of turns, 230. 38 S.W.G. enam. and S.S.C. copper. Former, 3⅞ in. long, with 7 sections of 650 μH ± 10 per cent.		B	..	1
14414	Type 1140 ...	No. of turns, 165. 38 S.W.G. enam. and S.S.C. copper. 4 sections of 650 μH and 1 section of 325 μH ± 10 per cent. Small coil mounted at opposite end to white mark.		B	..	1
14415	Type 1141 ...	No. of turns, 165. 38 S.W.G. enam. and S.S.C. copper. 4 sections of 650 μH and 1 section of 325 μH ± 10 per cent. Small coil mounted at same end.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCES—					
	<i>cont.</i>					
14471	Type 1142		B	each	1
14472	Type 1143	... 0.5 μ H. \pm 1 per cent. ...		B	"	1
14473	Type 1144	... 5 μ H. \pm 1 per cent. ...		B	"	1
14474	Type 1145	... 2.46-3.41 μ H., variable ...		B	"	1
14478	Type 1146		B	"	1
14479	Type 1147		B	"	1
14480	Type 1148		B	"	1
14520	Type 1150	... Aerial coil ...		B	"	1
14521	Type 1151	... Intervalve coil ...		B	"	1
14522	Type 1152	... Oscillator coil ...		B	"	1
14597	Type 1171	... 290 μ H., complete with mounting.		B	"	1
14598	Type 1172	... 760 μ H., complete with mounting.		B	"	1
14599	Type 1173	... 1,985 μ H., complete with mounting.		B	"	1
14600	Type 1174	... 2,500 μ H., complete with mounting.		B	"	1
14636	Type 1178	... No. of turns, 67. 28 S.W.G. Single winding section wound 28 S.W.G. on moulded former.		B	"	1
14637	Type 1179	... No. of turns, 10. 28 S.W.G. Dust cored inductance, single winding.		B	"	1
14638	Type 1180	... No. of turns, 2. 28 S.W.G. Dust cored inductance. 1 winding of 2 turns 28 S.W.G.		B	"	1
14639	Type 1181	... No. of turns, 10. 28 S.W.G. Dust cored.		B	"	1
14640	Type 1182	... No. of turns, 15. 28 S.W.G. 2 windings, enamelled copper, on moulded former.		B	"	1
14641	Type 1183	... No. of turns, 48. 28 S.W.G. Single winding, enamelled copper wire, on moulded former.		B	"	1
14642	Type 1184	... No. of turns, 4 $\frac{1}{2}$. 28 S.W.G. Iron dust cored, enamelled copper wire, on moulded former.		B	"	1
14643	Type 1185	... No. of turns, 7 $\frac{1}{2}$, 1. 28 S.W.G. Iron dust cored.		B	"	1
14644	Type 1186	... No. of turns, 11 $\frac{1}{2}$, 1. 28 S.W.G. Tinned copper wire. $\frac{5}{16}$ in. i/d.		B	"	1
14645	Type 1187	... No. of turns, 6 $\frac{1}{2}$. 28 S.W.G. Iron dust cored. 1 winding.		B	"	1
14687	Type 1191	... Trimmer adjustable iron core in former, with wound coil, 2 $\frac{1}{2}$ turns.		B	"	1
14688	Type 1192	... Trimmer adjustable iron core in former, with wound coil, 2 turns.		B	"	1
14691	Type 1193	... 0.51 mH. No. of turns, 259. 36 S.W.G. Double silk covered copper wire.		B	"	1
14722	Type 1196	... Delay link foil screened ebonite former, 0.37 in. dia. \times 7.56 in., tapped 4 B.A. at ends and containing 30 coils of 208 turns No. 42 S.W.G. D.S.C. copper wire.		B	"	1
14764	Type 1204	... No. of turns, 1,000. 40 S.W.G. E. and S.S. wire.		B	"	1

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCES—					
	<i>cont.</i>					
14839	Type 1235 ...	Former, $\frac{37}{32}$ in. long. 4 coils, wave wound, 153 turns 38 S.W.G. enam. S.S.C. copper wire, $192 \mu\text{H} \pm 5$ per cent.; 2 coils, wave wound, 110 turns 38 S.W.G. enam. S.S.C. copper wire, $96 \mu\text{H} \pm 5$ per cent.		B	each	1
14855	Type 1240 ...	1 mH. No. of turns, 230. $\frac{9}{46}$ Litz wire.		B	..	1
14856	Type 1241 ...	25 μH . No. of turns, 1,300. $\frac{9}{46}$ Litz wire.		B	..	1
14902	Type 1249 ...	2 turns approx., 0.5 in. dia., No. 14 S.W.G. silver-plated copper wire.		B	..	1
14986	Type 1251 ...	No. of turns, 1. 26 S.W.G. enam. copper. 1.145 in. \times 1.025 in. long. Wound on bakelite former. Dia. of head, $\frac{1}{4}$ in.; dia. of base, $\frac{11}{32}$ in. 8 B.A. insert.		B	..	1
14987	Type 1252 ...	No. of turns, $6\frac{1}{2}$. 26 S.W.G. enam. copper. 1.145 in. \times 1.025 in. long. Wound on bakelite former. Dia. of head, $\frac{1}{4}$ in.; dia. of base, $\frac{11}{32}$ in. 8 B.A. insert.		B	..	1
14988	Type 1253 ...	No. of turns, $1\frac{1}{2}$. 26 S.W.G. enam. copper. 1.145 in. \times 1.025 in. Wound on bakelite former. Dia. of head, $\frac{1}{4}$ in.; dia. of base, $\frac{11}{32}$ in. 8 B.A. insert.		B	..	1
14989	Type 1254 ...	No. of turns, $8\frac{1}{4}$. 28 S.W.G. Wound clockwise on former fitted with core.		B	..	1
14990	Type 1255 ...	No. of turns: Coupling 1, grid coil 9. 28 S.W.G. 28 S.W.G. moulded former, fitted with core.		B	..	1
14991	Type 1256 ...	No. of turns: Coupling 1, anode coil $11\frac{3}{4}$. 28 S.W.G. 28 S.W.G. moulded former, fitted with coil.		B	..	1
15010	Type 1263		B	..	1
15011	Type 1264		B	..	1
15012	Type 1265		B	..	1
15033	Type 1277 ...	No. of turns, $2\frac{1}{4}$. 26 S.W.G. Dust iron core. Bakelite former (WD.15684).		B	..	1
15034	Type 1278 ...	No. of turns, $1\frac{1}{2}$. 26 S.W.G. Dust iron. Bakelite former (WD.15684).		B	..	1
15035	Type 1279 ...	No. of turns, 3. 26 S.W.G. Dust iron core. Bakelite former (WD.15684).		B	..	1
15044	Type 1281 ...	12.5 μH , 2.5 ohms, 28 turns full wave wound 0.0148 in. dia. D.C. enam. wire on vulcanite former, 0.5 in. dia. \times 1.37 in., complete with bushes and 4 B.A. \times 0.43 in. ch/hd. screw.		B	..	1
15075	Type 1295 ...	No. of turns, 1,200. Centre tapped coil on iron core.		B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCES—					
	<i>cont.</i>					
15076	Type 1296 ...	8 turns of 28 S.W.G., $\frac{1}{32}$ in. spacing, on K.S.90667 former.		B	each	1
15087	Type 1297 ...	8 $\mu\text{H} \pm 10$ per cent. No. of turns, 43. 22 S.W.G. D.S.C. on former.		B	..	1
15088	Type 1298 ...	1 $\mu\text{H} \pm 10$ per cent. No. of turns, 9. 22 S.W.G. D.C.S., on former.		B	..	1
15089	Type 1299 ...	500 $\mu\text{H} \pm 10$ per cent. No. of turns, 237. 36 S.W.G. S.S. enam. copper. Circular base, with 3 fixing holes.		B	..	1
15090	Type 1300 ...	8 $\mu\text{H} \pm 10$ per cent. No. of turns, 26. 22 S.W.G. S.S.C. enam. copper. Two short connectors, $\frac{3}{8}$ in. long, on one side.		B	..	1
15091	Type 1301 ...	4 $\mu\text{H} \pm 10$ per cent. No. of turns, 25. 22 S.W.G. S.S.C. enam. copper.		B	..	1
15139	Type 1310 ...	5.8 mH. Can dimensions, $2\frac{3}{4}$ in. $\times 1\frac{13}{16}$ in. $\times 1\frac{9}{16}$ in. Two studs, fixing, No. 4 B.A.		B	..	1
15146	Type 1311 ...	No. of turns, 8. 28 S.W.G. copper wire, wound on moulded former, tapped at 1.8 turn. Dust iron cube.		B	..	1
15253	Type 1317 ...	No. of turns, 18. 36 S.W.G. enam. copper. On bakelite, $1\frac{1}{4}$ in. $\times \frac{1}{2}$ in. dia., with tags.		B	..	1
15254	Type 1318 ...	No. of turns, 20. 36 S.W.G. enam. copper. On bakelite former, $1\frac{1}{4}$ in. $\times \frac{1}{2}$ in., with tags.		B	..	1
15906	Type 1323 ...	No. of turns, 8. 28 en. cu. wire. Wound on moulded former.		B	..	1
15957	Type 1335 ...	No. of turns, 24. 36 S.W.G. enam. copper. On former, $\frac{1}{2}$ in. dia. $\times 1\frac{1}{4}$ in. long, with 4 tags.		B	..	1
16111	Type 1353 ...	1.2 $\mu\text{H} \pm 5$ per cent. 4 sections of 180. 38 S.W.G. S.S.C. en. cu. wire. Size, $1\frac{1}{8}$ in. $\times \frac{1}{4}$ in. D.C. 22 ohms. Wave wound on hollow S.R.B.P. former, with connecting tags.		B	..	1
16112	Type 1354 ...	12 $\mu\text{H} \pm 5$ per cent. No. of turns, 830. 40 S.W.G. S.S.C. en. cu., $1\frac{1}{2}$ in. long. Overall dia., 1 in. D.C. Resistance, 83 ohms. Wave wound on hollow S.R.B.P. former.		B	..	1
16113	Type 1355 ...	No. of turns, 300. 40 S.W.G. S.S.C. en. cu. 1.1 mH. ± 5 per cent. Main portion, 5 $\mu\text{H} \pm 5$ per cent. Tapped portion, D.C. Resistance, 23 ohms. Tapped at 50 turns.		B	..	1
16274	Type 1358 ...	Tropicalisation version of coils		B	..	1
16870	Type 1401 ...	150 V.H., 150 T. ± 20 per cent. 34 S.W.G. D.S.C. wire, on former.		B	..	—

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navv Ref	Class of Store	Denom. of Qty.	Carton Unit Qty
1	2	3	4	5	6	7
	INDUCTANCES—					
	<i>cont.</i>					
16871	Type 1402 ...	On former (Ericsson's, Type P.49391), 25 ULL, 5 per cent. 60. 36 S.W.G.		B	each	—
16997	Type 1406 ...	25 millihenries. 1,016 turns 40 S.W.G. Dust core. Sealed can.		B	„	—
—	Variable, No. 17	Army ZA. 15372	B	„	—
	INDUCTANCE UNITS :—					
12594	Mounting assembly		B	„	1
11248	Type 12	Special variable condenser, with integral inductance loop		B	„	1
12518	Type 16		B	„	1
12585	Type 17	Coil assembly of 2 coils of 8 turns of 14 S.W.G. silver-plated wire.		B	„	1
12586	Type 18	Coil assembly of 2 coils of 12 turns of 14 S.W.G. silver-plated wire.		B	„	1
12664	Type 19	Coil assembly of 2 coils of 10 turns of 14 S.W.G. silver-plated wire.		B	„	1
12743	Type 20	Coil assembly of 2 coils of 7 turns of 14 S.W.G. silver-plated wire.		B	„	1
13437	Type 21	Coil assembly of 2 coils of 14 S.W.G., each 5 turns, 2½ in. dia. Coil turns spaced 0.3 in. Coils spaced 0.6 in.		B	„	1
13438	Type 22	2 coils of 14 S.W.G., 5 turns each, 2½ in. dia. Coil turn spaced 0.5 in. Coils spaced 0.75 in.		B	„	1
13444	Type 23	2 coils, 4 turns each of 14 S.W.G. Dia. coils 2½ in. Coil turns spaced 0.4 in. Coils spaced 0.6 in.		B	„	1
13795	Type 25	S.R.B.P. 1.25 in. × 5.125 in. × ½ in.		B	„	1
13796	Type 26	S.R.B.P. 1.25 in. × 5.125 in. × ½ in.		B	„	1
13848	Type 27	Metal can containing inductances and condensers. Marked "L 1A" and "L.2A".		B	„	1
13849	Type 28	Metal can containing inductances and condensers. Marked "L 3A" and "L 4A".		B	„	1
13850	Type 29	Metal can containing inductances and condensers. Marked "L.7A" and "L.8A".		B	„	1
13851	Type 30	Metal can containing inductances, condensers, and resistances. Marked "L.9A".		B	„	1
13938	Type 31	C.W. oscillator unit, marked "L.4C".		B	„	1
13939	Type 32		B	„	1
13940	Type 33		B	„	1
13941	Type 34		B	„	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL.	Army or Navy Ref.	Class of Store	Denom of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTANCE UNITS—cont.					
14024	Type 35	4 windings (wave-wound) of 250 μ H. each.		B	each	1
14025	Type 36	3 windings of 13, 6, and 13 turns on former SD.1770.		B	..	1
14177	Type 37	Trace separator coils, bobbin wound, mounted on ebonite or paxolin plate, fitted to adjustable bracket.		B	..	1
14264	Type 39	Inductance and condenser sub-assembly.		B	..	1
14266	Type 40	Metal can containing inductances and condensers, marked "L.1.B" and "L.2.B".		B	..	1
14267	Type 41	Metal can containing inductances and condensers, marked "L.3.B" and "L.4.B".		B	..	1
14268	Type 42	Metal can containing inductances and condensers, marked "L.7.B".		B	..	1
14332	Type 43	2nd oscillator assembly ...		B	..	1
14333	Type 44	3rd oscillator assembly ...		B	..	1
14334	Type 45	2nd I.F. assembly		B	..	1
14335	Type 46	3rd I.F. assembly		B	..	1
14336	Type 47	4th I.F. assembly		B	..	1
14337	Type 48	5th I.F. assembly		B	..	1
14338	Type 49	6th I.F. assembly		B	..	1
14341	Type 50	H.F.		B	..	1
14342	Type 51	Aerial		B	..	1
14343	Type 52	Mixer		B	..	1
14349	Type 53	Coil assembly. Buffer, 3 in. dia. $\times \frac{5}{8}$ in. long overall.		B	..	1
14350	Type 54	Coil assembly, driver, 3 in. dia. $\times \frac{5}{8}$ in. long overall.		B	..	1
14351	Type 55	Coil oscillator crystal assembly, 3 in. dia. $\times \frac{5}{8}$ in. long.		B	..	1
14354	Type 56	Coil buffer crystal assembly ...		B	..	1
14345	Type 60	Oscillator		B	..	1
15209	Type 76	Wooden box, 3 in. cable, containing 1 stator from Switch Unit, Type 35A.		B	..	1
4048	Type 273	Complete in screening unit with wave switch H.F. sub-assembly		B	..	1
4079	Type 282	1st I.F. Sub assembly ...		B	..	1
4080	Type 283	2nd I.F. Sub-assembly ...		B	..	1
4124	Type 284	3rd I.F. Sub-assembly ...		B	..	1
4125	Type 285	4th I.F. Sub-assembly ...		B	..	1
4126	Type 286	5th I.F. Sub-assembly ...		B	..	1
4134	Type 287	2nd oscillator, sub-assembly ...		B	..	1
—	R.F.7	Army	B	..	1

RADIO CHOKES AND CONDENSERS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
3746	MICA :— 2½ in. × 2½ in. × .003 in. thick.	For condenser assembly ...		B	each	1
3747	3½ in. × 2½ in. × .002 in. thick.	For condenser assembly ...		B	„	1
15030	PLATES :— Capitance ...	Back plate, 1½ in. × 1¼ in. × ¼ in. deep, rounded corners.		B	„	5
12598	Condenser :— D.B.3433 ...	Variable, silver-plated, 3 ⅞ in. 3.032 in. × 1.312 in.		B	„	1
13819	Fixed L.T. ...	Brass sheet, 8 in. × 8¾ in., with lugs.		B	„	1
11072	For Grid Condenser	2 in. diam. metal disc, with stud, holding block, and adjusting spindle.		B	„	1
3880	Neutralizing :— Type 1 ...	Left-hand, fixed connection to insulator and variable con- denser, brass sheet.		B	„	2
3881	Type 2 ...	Right-hand, otherwise as Type 1		B	„	2
3882	Type 3 ...	Left-hand, fixed connection to variable condenser, brass sheet.		B	„	2
3884	Type 5 ...	Movable, slotted steel plate ...		B	„	2
3743	Padding ...	2 in. dia., with clamping screw and locknut.		B	„	1
3765	Screening ...	Trimming condenser, vernier trimmer device.		B	„	1
955	SCALES CON- DENSER TUNING.	Manganese aluminium ...		B	„	1
13368	STRIPS, CONDENSER MOUNTING.	Mycalex, 5½ in. × 2 in. × ⅜ in. thick, with 8 inserts.		B	„	1

RADIO CHOKES AND CONDENSERS

INDEX TO REFERENCE NUMBERS

SECTION 10C

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
1	17	366	118	499	65	731	118	912	153
11	117	368	118	504	118	732	41	913	153
13	35	369	118	531	49	734	62	915	119
14	61	370	118	532	49	741	52	916	119
15	37	371	118	533	97	744	86	917	119
18	41	372	118	534	48	745	58	938	98
19	57	374	118	535	94	746	118	939	98
21	117	375	118	543	118	769	118	944	111
23	117	377	118	545	33	770	119	955	179
37	117	378	118	552	96	771	152	958	60
38	55	379	118	559	49	772	152	960	113
42	17	380	104	560	104	776	152	962	113
44	108	382	43	561	100	784	68	963	55
47	113	384	2	564	79	785	68	964	65
49	1	385	2	565	49	786	68	967	91
50	104	386	2	566	107	787	69	968	119
61	107	387	2	567	107	788	70	974	119
62	117	388	17	568	49	789	71	976	119
72	17	392	118	569	107	790	71	979	106
74	17	394	80	571	17	791	73	1804	114
76	17	395	118	572	17	792	74	1805	101
77	17	397	118	578	2	794	78	2008	72
78	17	398	118	579	17	795	84	2011	76
79	1	399	118	580	18	798	87	2012	70
80	1	400	17	581	18	800	87	2017	73
81	17	401	2	582	18	801	102	2018	119
82	62	404	152	583	2	826	18	2019	2
83	117	405	152	605	18	829	152	2020	94
84	117	406	152	608	89	831	152	2024	88
85	117	407	152	609	118	834	152	2028	85
86	117	409	152	610	44	835	153	2029	49
87	55	410	152	625	118	836	2	2030	107
88	117	411	152	634	118	837	2	2031	146
90	117	412	152	651	61	838	66	2032	18
96	55	413	152	652	50	843	119	2039	54
104	59	414	152	653	50	844	44	2040	99
214	61	415	152	654	50	845	2	2043	81
216	1	416	152	655	102	846	18	2046	111
217	1	417	152	658	18	849	2	2047	112
223	117	418	152	666	49	850	2	2048	95
233	117	419	152	667	41	853	40	2053	112
234	117	420	152	672	39	857	40	2055	65
241	117	421	152	674	74	858	40	2061	18
242	117	422	152	682	54	859	40	2069	119
243	117	423	152	689	87	861	39	2070	119
244	67	424	152	684	84	862	38	2071	119
245	64	425	152	686	97	866	2	2072	119
249	2	431	2	695	111	868	95	2073	38
251	106	434	100	696	111	869	42	2075	39
271	57	436	118	697	98	872	119	2076	58
274	117	437	100	706	97	873	62	2079	40
275	117	442	43	707	94	874	39	2082	119
276	110	443	52	710	112	880	2	2083	93
277	110	445	118	711	49	883	110	2086	119
279	117	447	2	712	42	884	93	2087	2
285	2	448	17	713	38	886	95	2089	119
288	104	449	17	714	41	891	153	2090	109
289	46	466	104	715	112	892	153	2092	18
308	35	467	105	716	49	893	153	2093	18
312	118	468	97	717	2	894	119	2096	153
333	97	469	102	718	2	897	153	2097	153
336	64	475	118	719	2	901	119	2098	18
339	118	477	118	721	2	902	2	2099	153
344	118	481	118	728	34	909	153	2100	18
347	97	482	2	729	33	910	119	2101	97
351	118	497	118	730	118	911	37	2103	119

RADIO CHOKES AND CONDENSERS

INDEX TO REFERENCE NUMBERS

SECTION 10C—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
2108	33	2224	110	2339	57	2582	18	2718	40
2110	119	2226	18	2340	55	2585	3	2722	94
2111	153	2227	116	2342	64	2587	120	2724	95
2112	153	2229	116	2346	96	2590	84	2725	120
2113	153	2232	3	2351	99	2593	3	2726	59
2114	153	2233	3	2352	120	2594	3	2727	120
2115	153	2234	3	2353	120	2595	19	2729	51
2116	153	2235	3	2354	109	2596	19	2736	3
2117	153	2236	3	2360	3	2598	146	2737	3
2118	153	2239	105	2361	3	2599	46	2754	154
2119	102	2240	107	2364	146	2601	19	2761	19
2120	68	2243	82	2365	146	2602	154	2762	3
2121	68	2244	82	2366	36	2605	49	2763	19
2123	68	2245	82	2367	18	2606	50	2764	19
2124	119	2246	82	2376	18	2608	154	2765	19
2132	96	2248	98	2378	3	2609	154	2771	154
2133	18	2252	87	2379	113	2612	52	2773	3
2135	2	2253	88	2380	113	2614	109	2776	154
2138	36	2255	51	2381	113	2615	120	2786	154
2140	153	2257	105	2382	107	2617	120	2789	154
2142	18	2258	119	2383	113	2620	98	2791	86
2143	18	2259	119	2386	82	2622	110	2792	105
2146	69	2262	119	2387	120	2624	87	2796	120
2147	70	2263	114	2388	61	2625	90	2797	120
2148	43	2266	154	2389	112	2626	81	2798	64
2151	153	2267	154	2392	146	2632	154	2799	121
2152	154	2268	3	2400	103	2634	111	2800	121
2153	154	2269	3	2401	42	2635	101	2801	121
2154	154	2270	3	2403	34	2638	120	2802	121
2157	90	2271	86	2406	53	2643	19	2803	58
2161	109	2272	84	2416	54	2648	70	2806	120
2162	107	2273	18	2417	56	2649	70	2808	35
2165	110	2278	68	2421	60	2653	44	2809	108
2170	104	2279	18	2423	66	2654	92	2810	102
2172	119	2281	119	2426	43	2656	67	2811	84
2173	83	2282	119	2429	94	2668	35	2812	85
2174	99	2283	119	2431	120	2676	120	2813	102
2175	97	2284	119	2432	40	2677	48	2814	121
2176	100	2285	119	2434	40	2678	94	2819	121
2177	88	2286	119	2435	41	2679	93	2829	146
2178	82	2289	18	2436	99	2680	95	2842	154
2179	82	2290	99	2437	107	2681	94	2843	154
2180	119	2293	51	2438	50	2683	94	2844	154
2181	82	2294	77	2439	95	2684	120	2845	154
2182	82	2296	18	2440	49	2686	94	2847	3
2184	18	2297	18	2446	18	2687	102	2849	3
2185	2	2298	18	2447	100	2688	100	2850	3
2186	2	2299	3	2448	102	2690	66	2856	154
2187	18	2306	44	2552	18	2692	19	2859	3
2189	102	2307	120	2554	54	2693	82	2866	19
2190	104	2310	79	2556	18	2696	113	2870	112
2191	107	2311	120	2560	120	2698	146	2873	121
2192	98	2310	83	2561	40	2701	3	2874	40
2193	104	2314	81	2563	112	2705	120	2875	66
2194	110	2315	86	2564	112	2706	120	2881	95
2200	154	2318	120	2565	91	2707	34	2882	121
2201	154	2321	113	2567	91	2708	120	2885	101
2202	154	2322	105	2568	90	2709	94	2890	92
2207	67	2323	110	2570	18	2710	48	2891	93
2209	42	2325	105	2572	120	2711	88	2896	121
2210	43	2326	109	2574	120	2712	111	2910	154
2213	42	2328	120	2575	120	2713	110	2911	154
2218	42	2331	109	2576	18	2714	120	2912	154
2220	104	2332	112	2578	96	2715	84	2913	154
2222	107	2334	120	2579	120	2716	84	2914	154
2223	119	2337	82	2580	18	2717	86	2915	154

RADIO CHOKES AND CONDENSERS
INDEX TO REFERENCE NUMBERS

SECTION 10C—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
2920	34	3123	102	3277	104	3459	105	3592	5
2922	102	3125	121	3280	112	3460	19	3593	147
2928	49	3127	100	3290	92	3462	105	3594	72
2930	121	3129	121	3293	122	3464	104	3602	58
2932	121	3135	85	3294	122	3465	122	3604	81
2933	79	3138	45	3298	122	3466	122	3606	41
2934	81	3145	19	3299	122	3467	123	3608	108
2935	121	3146	19	3304	122	3469	44	3609	123
2936	49	3147	19	3305	122	3474	43	3610	105
2937	107	3151	155	3308	122	3476	150	3611	33
2939	56	3153	155	3309	122	3477	150	3615	31
2942	3	3154	155	3313	122	3478	150	3619	155
2943	30	3156	155	3316	38	3479	150	3628	117
2944	3	3159	155	3317	43	3485	45	3634	123
2951	114	3166	155	3318	43	3486	114	3638	107
2953	3	3167	155	3325	122	3487	123	3639	45
2954	3	3168	155	3327	122	3488	87	3641	108
2963	94	3169	155	3330	122	3490	99	3642	77
2965	43	3173	147	3331	122	3491	107	3643	71
2966	121	3174	147	3332	122	3496	155	3646	123
2968	49	3180	121	3333	122	3499	98	3647	88
2969	102	3186	121	3334	122	3501	123	3650	154
2970	104	3188	51	3336	122	3502	64	3653	19
2971	49	3191	59	3337	38	3505	123	3659	123
2973	121	3193	81	3338	60	3507	84	3660	123
2994	155	3194	122	3341	79	3509	99	3661	123
3008	3	3196	58	3342	114	3512	105	3663	123
3019	19	3198	75	3345	17	3513	109	3664	106
3023	121	3200	34	3354	79	3516	57	3669	123
3026	90	3201	120	3356	114	3517	123	3670	123
3028	121	3207	122	3363	79	3519	123	3675	39
3031	121	3208	122	3376	147	3520	19	3676	123
3034	42	3210	65	3378	147	3522	19	3679	57
3035	41	3211	97	3380	56	3523	19	3680	19
3036	38	3214	42	3383	54	3524	4	3682	19
3039	121	3216	42	3386	82	3525	59	3684	19
3042	33	3217	122	3387	61	3530	75	3685	19
3043	35	3218	44	3388	58	3531	46	3687	19
3045	40	3219	37	3389	55	3533	72	3688	19
3046	76	3220	3	3392	83	3535	123	3690	123
3047	121	3221	3	3394	122	3541	155	3691	123
3048	107	3223	3	3395	122	3542	155	3693	55
3049	102	3224	3	3396	61	3544	43	3694	123
3050	105	3225	4	3397	41	3545	73	3695	123
3051	59	3228	4	3399	93	3546	123	3696	64
3064	73	3230	155	3407	122	3547	75	3698	109
3066	121	3231	155	3408	51	3548	74	3701	52
3068	60	3232	155	3414	55	3549	73	3705	123
3069	105	3233	155	3415	60	3550	123	3710	123
3071	52	3234	155	3416	110	3551	123	3715	123
3072	47	3235	155	3425	4	3554	113	3717	123
3075	147	3260	38	3427	4	3557	60	3718	100
3080	74	3261	38	3428	19	3560	35	3719	112
3085	121	3262	39	3429	19	3562	81	3723	69
3087	87	3263	41	3433	72	3563	37	3726	107
3089	40	3264	37	3434	34	3566	39	3728	123
3092	121	3265	38	3436	35	3567	38	3729	99
3093	62	3266	39	3437	54	3570	4	3736	19
3094	121	3267	40	3439	67	3573	40	3742	19
3101	58	3268	41	3443	77	3574	38	3743	179
3102	64	3270	66	3446	78	3575	123	3746	179
3106	64	3271	49	3447	78	3576	123	3747	179
3110	34	3272	49	3448	66	3586	41	3760	31
3111	73	3273	54	3451	39	3587	59	3765	179
3121	108	3275	122	3452	122	3589	61	3767	19
3122	51	3276	90	3456	122	3590	4		

RADIO CHOKES AND CONDENSERS

INDEX TO REFERENCE NUMBERS

SECTION 10C—cont.

Ref No	Page	Ref No.	Page	Ref No	Page	Ref No	Page	Ref No	Page
3768	19	3919	72	4065	4	4209	77	4454	156
3770	19	3921	69	4066	4	4212	111	4456	156
3771	19	3923	70	4067	4	4213	98	4459	156
3774	59	3927	39	4068	4	4214	100	4461	5
3778	120	3930	107	4069	4	4231	45	4464	5
3779	45	3931	94	4070	4	4233	38	4470	147
3781	43	3935	59	4073	20	4234	86	4471	147
3783	123	3938	54	4074	20	4237	14	4473	31
3786	124	3939	53	4075	20	4238	72	4474	125
3787	45	3940	124	4076	20	4240	33	4476	68
3788	65	3943	107	4077	156	4241	87	4478	68
3790	124	3947	124	4078	156	4242	76	4482	108
3791	124	3948	124	4079	178	4244	63	4483	125
3793	124	3953	110	4080	178	4245	61	4486	38
3794	44	3954	75	4081	20	4246	66	4488	39
3796	82	3955	73	4084	20	4248	59	4493	38
3798	81	3956	72	4086	20	4249	55	4499	125
3804	3	3957	76	4087	20	4250	61	4500	43
3805	3	3959	124	4088	20	4251	38	4501	47
3806	4	3960	124	4089	20	4253	39	4502	62
3807	4	3961	75	4092	4	4254	37	4503	51
3808	4	3963	95	4093	4	4255	55	4506	36
3809	4	3967	155	4094	4	4256	65	4507	125
3816	155	3971	20	4095	43	4257	86	4510	105
3817	155	3973	20	4097	52	4262	113	4517	5
3818	155	3974	20	4100	55	4263	113	4523	20
3819	155	3977	4	4102	125	4265	125	4524	20
3823	147	3979	4	4103	66	4267	64	4525	20
3824	147	3981	69	4106	125	4268	57	4526	47
3825	155	3983	76	4107	125	4271	71	4528	97
3827	155	3989	97	4109	125	4274	69	4531	102
3829	155	3990	79	4112	78	4280	20	4532	100
3841	124	3991	78	4113	78	4288	5	4533	99
3845	81	3994	124	4114	125	4302	156	4534	97
3848	124	3995	124	4124	178	4303	156	4535	108
3850	124	3996	124	4125	178	4304	156	4533	88
3851	124	3998	53	4126	178	4314	156	4544	89
3852	124	3999	124	4132	4	4315	156	4546	58
3853	34	4000	124	4134	178	4316	156	4549	85
3854	35	4010	124	4136	156	4317	156	4550	87
3855	124	4014	124	4137	156	4321	125	4551	88
3856	124	4017	48	4139	156	4326	72	4553	87
3858	124	4018	37	4147	4	4334	125	4566	83
3860	33	4020	93	4150	4	4340	125	4568	105
3862	86	4021	91	4152	5	4341	104	4570	101
3863	104	4022	46	4153	5	4345	81	4572	102
3864	51	4023	91	4160	5	4351	50	4586	66
3865	124	4024	90	4161	5	4352	52	4589	95
3869	112	4025	125	4167	83	4362	5	4592	20
3873	124	4027	109	4171	59	4397	48	4593	20
3878	124	4028	109	4176	84	4401	52	4595	20
3880	179	4029	104	4181	86	4406	91	4599	5
3881	179	4032	125	4184	72	4409	39	4610	83
3882	179	4034	81	4185	73	4413	44	4611	77
3884	179	4036	81	4188	57	4415	125	4613	75
3885	19	4042	81	4190	82	4416	54	4614	43
3896	19	4044	102	4191	82	4418	105	4615	112
3898	19	4045	156	4192	82	4419	125	4616	112
3899	4	4048	178	4193	82	4420	125	4617	103
3900	102	4051	156	4197	74	4422	125	4618	112
3902	95	4052	156	4199	66	4424	74	4619	95
3904	124	4053	156	4201	73	4425	125	4620	87
3906	43	4054	156	4203	76	4433	82	4622	37
3908	124	4061	147	4204	83	4450	156	4625	60
3909	124	4062	147	4205	83	4451	156	4630	40
3913	68	4064	4	4206	85	4453	156	4631	45

RADIO CHOKES AND CONDENSERS

INDEX TO REFERENCE NUMBERS

SECTION 10C—cont.

Ref. No	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
4632	33	4824	106	4967	126	5193	80	5404	21
4637	94	4833	156	4968	126	5210	97	5405	21
4640	150	4834	157	4970	62	5215	101	5406	21
4646	34	4835	157	4973	126	5216	100	5414	128
4654	49	4838	157	4976	59	5217	100	5419	128
4656	45	4839	157	4977	104	5218	106	5420	128
4678	47	4842	20	4979	127	5219	105	5425	63
4679	84	4844	20	4980	43	5220	127	5432	128
4683	100	4845	20	4989	36	5221	34	5433	128
4687	51	4846	20	4994	54	5222	127	5434	49
4688	53	4848	5	4995	55	5223	80	5436	128
4689	58	4849	5	4998	86	5230	74	5438	128
4690	53	4851	5	5015	5	5237	127	5439	49
4698	55	4858	157	5017	5	5238	127	5440	100
4699	53	4864	126	5018	20	5239	127	5441	59
4703	44	4865	103	5026	127	5241	127	5443	128
4705	125	4867	65	5027	127	5244	102	5444	128
4706	57	4868	57	5028	127	5245	101	5447	37
4707	64	4869	59	5030	72	5247	127	5450	39
4710	20	4870	126	5034	55	5258	157	5455	65
4711	20	4871	89	5036	47	5277	5	5456	73
4712	20	4872	72	5042	104	5285	5	5467	128
4713	20	4875	126	5043	127	5286	21	5471	97
4714	20	4876	51	5045	76	5287	5	5474	56
4715	20	4883	126	5046	77	5288	21	5475	74
4726	156	4884	99	5047	74	5289	21	5476	78
4728	156	4885	57	5053	86	5290	21	5477	73
4729	156	4886	110	5055	71	5291	21	5478	77
4730	156	4887	63	5056	69	5292	21	5479	78
4731	156	4888	126	5058	62	5293	64	5480	102
4733	156	4889	64	5059	20	5296	35	5483	74
4734	156	4890	81	5060	20	5297	108	5484	72
4751	125	4891	63	5061	20	5301	38	5495	150
4760	35	4893	126	5065	5	5302	114	5497	21
4762	35	4894	126	5066	5	5304	127	5500	158
4763	72	4895	110	5069	5	5309	82	5501	158
4764	57	4896	126	5070	5	5310	84	5520	158
4766	84	4900	109	5072	5	5313	61	5524	102
4768	33	4901	44	5077	157	5315	55	5525	112
4772	125	4904	104	5082	21	5318	37	5526	128
4773	125	4905	102	5085	21	5319	39	5527	44
4774	83	4909	89	5086	21	5320	36	5528	46
4775	126	4914	126	5087	21	5321	36	5529	55
4776	60	4917	126	5090	5	5322	37	5532	82
4778	46	4920	42	5094	5	5323	37	5533	105
4779	44	4921	86	5122	157	5325	127	5538	48
4780	44	4922	69	5130	21	5327	127	5539	128
4781	45	4923	71	5134	21	5329	127	5541	39
4786	97	4925	83	5137	81	5333	49	5543	128
4788	64	4930	100	5139	89	5335	49	5544	128
4791	36	4932	113	5140	88	5337	102	5545	56
4794	39	4933	50	5142	34	5338	106	5546	54
4797	72	4934	126	5144	74	5342	128	5548	56
4798	71	4939	69	5145	97	5343	5	5549	61
4803	88	4940	63	5147	108	5349	43	5552	55
4804	88	4942	43	5149	85	5352	65	5553	53
4805	100	4943	65	5151	127	5356	86	5556	128
4807	126	4944	126	5157	97	5357	23	5559	109
4808	65	4947	126	5158	102	5379	21	5560	39
4810	126	4950	43	5159	97	5381	157	5563	43
4811	126	4951	41	5162	88	5382	157	5564	65
4812	126	4959	70	5168	34	5385	157	5565	38
4813	126	4960	72	5174	44	5386	157	5566	105
4814	126	4961	71	5183	103	5388	157	5567	108
4821	126	4965	126	5185	98	5389	158	5568	50
4823	87	4966	126	5186	127	5399	21	5576	128

5487.-21

RADIO CHOKES AND CONDENSERS

INDEX TO REFERENCE NUMBERS

SECTION 10C—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
5579	85	5743	6	5910	6	7902	55	8670	65
5583	72	5750	147	5914	6	7903	54	8671	92
5585	69	5758	109	5916	22	7904	115	8672	116
5586	70	5759	106	5920	159	7905	115	8673	58
5587	128	5761	41	5922	159	7906	67	8682	1
5588	128	5762	98	5923	159	7912	17	8716	1
5591	102	5764	98	5936	159	8009	59	8718	1
5592	49	5766	61	5946	47	8010	63	8720	116
5593	128	5767	35	5947	58	8012	115	8800	53
5594	128	5772	129	5950	97	8044	81	8804	116
5596	70	5774	59	5951	38	8045	80	8959	50
5597	101	5779	56	5952	64	8048	80	9008	60
5598	50	5782	86	5953	64	8116	115	9011	102
5599	129	5786	77	5954	114	8140	115	9012	100
5606	158	5787	71	5956	35	8163	81	9097	103
5611	6	5788	71	5958	129	8164	80	9133	61
5613	6	5790	129	5960	33	8166	115	9145	116
5614	6	5792	73	5961	86	8167	115	9151	116
5615	6	5795	89	5962	36	8168	115	9152	116
5616	6	5796	103	5966	46	8169	115	9178	57
5619	6	5798	77	5967	129	8171	115	9179	61
5623	21	5799	106	5969	129	8172	115	9180	106
5629	147	5800	129	5971	74	8201	115	9181	101
5637	21	5801	51	5973	88	8206	115	9182	116
5638	129	5802	73	5974	88	8275	104	9184	53
5639	102	5805	110	5975	86	8286	115	9186	116
5640	53	5806	129	5976	85	8378	106	9197	116
5641	88	5807	83	5977	84	8380	115	9198	116
5644	50	5810	33	5979	77	8381	115	9206	1
5647	129	5811	83	5980	130	8383	58	9223	112
5649	34	5812	61	5983	70	8384	115	9294	80
5651	129	5821	129	5984	68	8386	54	9297	80
5654	129	5822	48	5985	130	8387	115	9300	116
5655	48	5825	50	5987	130	8463	30	9318	116
5656	59	5826	149	5989	69	8464	30	9341	17
5657	88	5828	158	5990	70	8473	146	9374	80
5659	47	5829	158	5991	130	8474	147	9376	50
5661	33	5830	159	5997	130	8482	1	9377	80
5662	51	5833	159	5998	70	8483	1	9382	104
5663	41	5834	159	5999	34	8484	1	9385	107
5665	109	5845	22	7039	81	8485	1	9497	17
5673	87	5847	6	7174	78	8486	1	9514	1
5678	43	5848	31	7203	114	8490	115	9606	17
5682	57	5849	6	7204	78	8493	65	9607	17
5687	64	5867	83	7348	114	8494	92	9608	107
5689	67	5868	83	7384	17	8496	67	9610	45
5699	88	5871	58	7386	57	8497	79	9611	47
5701	34	5872	41	7488	61	8498	79	9628	17
5704	85	5873	129	7491	104	8499	80	9630	116
5705	34	5875	129	7423	114	8500	82	9675	101
5706	129	5881	33	7424	114	8501	115	9805	107
5707	94	5883	46	7425	114	8502	115	9806	109
5708	72	5884	65	7427	114	8507	79	9807	110
5710	77	5885	129	7469	115	8508	115	9833	81
5711	99	5886	129	7512	17	8566	116	9905	116
5723	21	5887	129	7593	100	8567	81	9906	116
5724	21	5888	129	7594	115	8634	17	9907	116
5725	21	5889	66	7762	115	8637	116	9997	105
5727	147	5890	108	7763	80	8638	50	10008	81
5729	147	5891	99	7764	80	8639	109	10010	81
5730	22	5892	104	7814	55	8656	63	10015	78
5735	22	5995	129	7847	63	8657	92	10049	81
5736	158	5901	75	7853	115	8658	67	10051	110
5737	158	5903	71	7895	115	8659	54	10082	116
5738	158	5905	22	7901	61	8660	57	10117	1
5741	6	5906	22			8669	60	10164	65

RADIO CHOKES AND CONDENSERS
INDEX TO REFERENCE NUMBERS

SECTION 10C—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
10167	61	10975	34	11188	130	11341	1	11530	7
10221	81	10986	1	11189	103	11345	6	11531	160
10226	116	11003	50	11192	77	11346	6	11532	160
10227	116	11004	107	11193	77	11359	17	11533	160
10228	71	11005	97	11195	130	11365	117	11534	160
10229	75	11006	130	11196	130	11368	72	11535	160
10230	116	11010	81	11199	63	11388	90	11536	31
10297	98	11011	81	11203	60	11393	1	11537	31
10317	116	11012	81	11204	49	11394	99	11540	131
10342	100	11013	97	11205	99	11396	62	11541	131
10343	104	11025	22	11206	69	11397	131	11543	101
10344	116	11034	55	11207	130	11399	49	11544	106
10390	116	11043	22	11208	130	11400	49	11545	94
10392	57	11045	159	11210	67	11408	68	11550	131
10393	67	11046	159	11211	130	11409	131	11554	66
10395	34	11047	159	11214	99	11411	68	11558	68
10460	116	11048	147	11215	106	11412	68	11560	69
10461	46	11054	57	11216	107	11415	109	11562	72
10476	116	11061	130	11219	130	11429	23	11563	73
10504	1	11062	130	11222	22	11430	23	11564	74
10505	1	11065	61	11227	6	11432	7	11565	131
10507	116	11066	130	11234	22	11433	7	11568	131
10509	104	11067	62	11236	6	11435	7	11569	33
10510	42	11069	130	11242	159	11436	7	11571	147
10511	67	11071	130	11244	159	11438	160	11572	31
10513	116	11072	179	11248	177	11440	7	11573	148.
10545	146	11073	62	11249	159	11442	23	11574	148
10546	105	11081	152	11255	31	11443	150	11575	112
10562	66	11082	152	11261	130	11444	150	11576	106
10568	35	11083	152	11263	73	11445	23	11577	113
10570	69	11084	152	11264	49	11446	23	11578	131
10622	4	11097	130	11265	50	11447	7	11579	33
10625	4	11098	43	11268	105	11448	7	11584	160
10644	117	11099	74	11269	73	11449	147	11587	31
10646	117	11100	130	11271	85	11450	147	11588	117
10647	117	11107	154	11277	130	11451	150	11592	7
10648	117	11108	159	11281	112	11452	7	11593	7
10649	97	11120	83	11285	131	11455	117	11594	7
10651	117	11121	83	11286	60	11456	160	11601	1
10655	117	11122	83	11287	131	11457	160	11603	1
10656	117	11123	85	11288	131	11458	160	11604	1
10658	153	11124	85	11290	98	11459	112	11605	1
10699	19	11125	86	11292	97	11461	131	11607	147
10743	117	11127	84	11294	70	11475	81	11609	23
10752	117	11128	88	11298	6	11479	47	11610	23
10753	117	11129	88	11300	22	11481	56	11611	23
10755	49	11130	89	11301	22	11482	44	11612	7
10790	152	11132	92	11302	22	11484	70	11615	160
10801	100	11133	92	11304	22	11487	69	11617	7
10802	51	11134	83	11305	117	11490	59	11620	131
10805	152	11135	86	11313	22	11491	33	11622	131
10822	105	11136	83	11314	6	11493	105	11631	131
10823	101	11137	84	11318	149	11494	105	11637	148
10825	108	11138	84	11323	22	11495	131	11639	7
10826	97	11139	83	11324	22	11498	107	11640	160
10827	110	11140	83	11325	22	11500	76	11656	131
10828	107	11141	83	11326	6	11502	150	11657	133
10832	110	11142	85	11330	6	11503	160	11693	117
10833	98	11143	85	11331	6	11505	147	11694	64
10878	117	11144	6	11332	22	11518	160	11695	59
10883	117	11149	6	11335	150	11519	160	11696	66
10885	105	11152	159	11336	6	11520	160	11697	65
10911	44	11153	159	11337	147	11521	150	11698	61
10920	103	11166	159	11338	22	11524	23	11708	117
10937	102	11167	22	11339	22	11528	7	11709	117
10938	116	11184	66	11340	22	11529	7		

RADIO CHOKES AND CONDENSERS

INDEX TO REFERENCE NUMBERS

SECTION 10C—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
11710	160	11872	8	11974	87	12096	77	12268	9
11711	33	11873	23	11976	55	12097	77	12269	9
11715	131	11874	8	11977	46	12101	78	12270	9
11718	131	11875	8	11978	23	12102	78	12271	9
11722	104	11876	160	11979	50	12104	78	12272	9
11727	102	11877	160	11980	60	12106	78	12273	9
11728	99	11878	161	11981	23	12113	34	12280	162
11735	160	11879	161	11983	132	12114	133	12287	111
117 6	62	11880	161	11988	132	12115	24	12289	133
11738	8	11882	161	11989	9	12116	9	12290	31
11744	131	11883	161	11992	132	12119	161	12291	9
11747	90	11885	161	11993	24	12121	162	12292	148
11748	92	11886	161	11994	23	12122	162	12296	133
11751	90	11887	161	11995	47	12123	162	12297	162
11752	92	11895	68	11996	47	12127	24	12298	162
11753	90	11896	43	11999	9	12128	76	12299	162
11754	90	11897	8	12000	58	12129	24	12301	24
11756	92	11899	98	12001	65	12132	92	12302	46
11761	81	11900	99	12003	104	12134	24	12308	133
11767	131	11904	161	12006	161	12137	24	12311	56
11770	43	11905	161	12007	106	12138	133	12312	56
11771	132	11906	132	12008	23	12140	95	12313	57
11772	132	11910	132	12009	161	12144	86	12314	57
11775	59	11911	23	12010	161	12145	88	12315	58
11779	23	11912	77	12011	161	12147	33	12316	60
11780	132	11913	161	12018	23	12153	74	12317	63
11786	84	11914	73	12019	23	12154	24	12318	63
11787	85	11915	150	12020	132	12155	68	12319	63
11788	88	11916	72	12021	24	12157	72	12324	59
11791	154	11920	34	12022	24	12158	75	12326	67
11793	8	11921	132	12027	9	12159	76	12332	91
11794	8	11922	132	12028	161	12160	76	12333	55
11796	132	11924	161	12029	161	12161	77	12335	56
11797	74	11925	161	12030	161	12162	78	12337	58
11798	148	11927	47	12032	133	12163	162	12338	59
11801	77	11929	132	12040	133	12169	162	12340	62
11804	132	11932	65	12043	62	12170	162	12341	63
11816	132	11933	132	12045	161	12176	133	12342	65
11819	132	11934	109	12046	62	12177	133	12343	67
11820	160	11935	78	12047	34	12180	133	12344	67
11821	8	11936	69	12051	9	12182	133	12347	55
11822	8	11940	100	12055	133	12185	133	12348	57
11823	79	11941	161	12056	9	12187	36	12351	60
11824	132	11942	77	12061	33	12188	33	12353	108
11825	79	11943	23	12062	33	12190	24	12354	133
11826	79	11944	71	12065	133	12199	162	12360	162
11838	93	11952	88	12067	9	12200	162	12364	162
11842	8	11954	89	12069	71	12201	162	12365	162
11844	8	11955	87	12070	68	12204	133	12367	162
11846	23	11956	83	12072	68	12205	133	12369	24
11848	8	11957	83	12073	68	12209	162	12371	63
11850	8	11958	104	12074	69	12225	148	12373	160
11851	35	11959	86	12075	69	12226	133	12375	24
11852	35	11960	84	12077	71	12229	133	12379	89
11853	35	11961	85	12078	71	12230	65	12380	47
11856	45	11962	8	12079	71	12232	41	12381	58
11857	23	11963	8	12080	71	12233	38	12383	97
11858	132	11964	8	12084	75	12234	37	12384	134
11859	100	11965	150	12085	75	12240	9	12389	47
11860	34	11966	150	12086	75	12246	133	12390	47
11861	34	11967	151	12087	75	12250	24	12391	61
11862	8	11968	9	12089	76	12251	9	12392	134
11867	63	11969	9	12092	76	12265	133	12393	36
11868	60	11970	9	12093	76	12266	133	12394	134
11870	132	11971	23	12094	76	12267	133	12397	162
11871	8	11972	23	12095	77			12398	88

RADIO CHOKES AND CONDENSERS

INDEX TO REFERENCE NUMBERS

SECTION 10C—cont.

Ref No	Page	Ref. No.	Page	Ref. No	Page	Ref No	Page	Ref. No.	Page
12400	77	12515	162	12649	134	12773	87	12944	84
12401	78	12518	177	12650	73	12775	103	12945	91
12405	61	12524	101	12653	134	12776	108	12946	108
12406	134	12525	134	12654	135	12778	70	12950	47
12407	67	12539	94	12655	105	12780	135	12957	63
12428	46	12540	94	12656	24	12781	166	12959	25
12429	45	12541	95	12657	44	12782	166	12960	86
12430	86	12543	95	12658	93	12783	10	12964	135
12433	46	12545	163	12659	106	12784	11	12965	148
12434	9	12547	163	12660	103	12785	25	12972	55
12435	134	12548	163	12661	24	12786	166	12973	56
12436	134	12549	163	12662	101	12787	166	12974	87
12439	57	12550	163	12663	44	12788	166	12978	85
12440	56	12551	163	12664	177	12789	166	12979	86
12441	148	12552	163	12680	107	12790	166	12980	85
12442	10	12553	163	12681	104	12791	166	12981	85
12443	134	12554	77	12682	103	12792	166	12983	87
12444	134	12555	71	12683	47	12793	166	12985	87
12445	162	12559	10	12684	135	12794	166	12986	85
12446	162	12560	10	12687	93	12795	166	12987	88
12447	162	12564	148	12688	24	12796	166	12988	88
12448	101	12566	163	12690	135	12797	166	12989	88
12449	134	12567	103	12691	24	12799	75	12992	135
12450	68	12568	46	12692	164	12809	89	13004	84
12452	134	12571	10	12693	91	12810	91	13005	88
12455	10	12573	106	12694	91	12811	135	13006	88
12459	87	12576	163	12695	164	12836	135	13007	96
12462	134	12577	163	12697	111	12838	50	13008	96
12463	134	12578	149	12698	135	12840	25	13010	96
12468	134	12579	149	12706	89	12841	25	13012	93
12469	24	12580	163	12707	86	12842	25	13013	96
12470	134	12581	10	12708	99	12843	25	13015	95
12471	24	12582	134	12709	135	12844	25	13017	93
12472	24	12583	24	12710	164	12845	135	13018	93
12473	24	12584	24	12711	164	12847	109	13019	94
12474	10	12585	177	12712	164	12848	110	13020	95
12475	63	12586	177	12713	164	12860	86	13023	11
12476	10	12587	163	12714	164	12863	135	13037	25
12480	134	12592	10	12715	164	12881	89	13038	135
12485	93	12593	10	12716	164	12883	89	13039	136
12486	94	12594	177	12717	164	12884	83	13042	136
12487	94	12595	31	12718	165	12885	149	13044	136
12488	94	12598	179	12719	165	12886	166	13045	11
12489	94	12604	163	12720	165	12887	166	13047	103
12490	94	12605	134	12721	165	12889	135	13048	35
12492	94	12606	24	12722	165	12891	135	13049	11
12493	94	12607	49	12723	165	12892	135	13050	112
12494	94	12608	109	12724	165	12893	57	13051	113
12496	95	12617	36	12725	165	12894	36	13052	46
12497	95	12619	99	12726	165	12895	36	13054	166
12498	95	12620	134	12727	165	12896	135	13055	167
12499	95	12622	31	12728	166	12897	135	13056	167
12500	95	12626	148	12730	10	12898	135	13058	103
12501	95	12627	148	12731	135	12899	25	13059	106
12502	95	12633	92	12732	135	12901	25	13060	136
12503	95	12634	103	12733	135	12902	25	13061	136
12504	96	12635	101	12735	80	12904	25	13062	106
12505	96	12636	10	12743	177	12912	25	13063	108
12506	96	12639	163	12746	46	12915	135	13064	109
12507	96	12640	164	12755	10	12916	11	13065	59
12508	96	12641	10	12760	10	12917	11	13066	136
12509	96	12643	31	12761	93	12926	151	13078	25
12510	96	12644	10	12762	24	12927	50	13079	11
12511	96	12646	31	12769	24	12937	11	13080	50
12512	96	12647	164	12770	25	12938	149	13083	136
12514	94	12648	164	12772	84	12943	75	13085	52

RADIO CHOKES AND CONDENSERS

INDEX TO REFERENCE NUMBERS

SECTION 10C—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
13086	45	13219	95	13358	151	13473	26	13570	138
13088	136	13220	95	13359	151	13474	12	13571	26
13089	11	13221	96	13360	151	13475	40	13572	169
13090	167	13222	43	13361	151	13481	61	13573	169
13091	167	13223	99	13366	75	13482	12	13576	99
13092	167	13224	26	13368	179	13488	149	13577	139
13093	105	13226	12	13370	137	13489	149	13578	90
13094	136	13228	26	13374	137	13490	149	13579	67
13095	101	13238	83	13375	47	13491	149	13585	169
13097	11	13246	167	13376	46	13493	137	13586	56
13101	25	13260	136	13377	45	13494	70	13587	26
13102	25	13261	35	13378	167	13496	97	13589	63
13103	25	13262	98	13379	167	13497	83	13590	138
13104	25	13263	103	13380	167	13498	12	13596	12
13105	25	13264	108	13381	167	13499	137	13598	169
13106	25	13269	12	13382	26	13500	137	13599	138
13108	167	13270	167	13387	26	13501	73	13600	138
13109	11	13272	99	13390	26	13502	108	13601	138
13110	11	13273	108	13391	148	13506	137	13602	138
13111	11	13274	103	13392	137	13507	137	13618	169
13112	94	13275	33	13394	167	13508	137	13620	26
13113	60	13276	61	13395	67	13509	168	13622	36
13133	54	13279	61	13399	12	13514	168	13624	138
13138	34	13280	12	13403	167	13515	168	13625	138
13147	167	13281	44	13404	167	13516	168	13626	138
13149	136	13283	46	13405	167	13517	168	13633	101
13151	11	13284	47	13406	167	13518	168	13634	61
13153	31	13285	136	13407	26	13519	168	13635	57
13157	11	13286	44	13408	137	13520	168	13636	61
13158	11	13287	45	13409	137	13521	168	13639	169
13159	11	13288	44	13411	151	13522	168	13640	169
13160	11	13289	45	13412	151	13523	168	13641	12
13161	25	13290	46	13417	167	13524	168	13642	12
13162	11	13302	94	13418	167	13525	168	13643	26
13163	11	13306	136	13419	167	13526	168	13645	26
13165	136	13307	106	13420	63	13527	168	13646	138
13166	89	13308	136	13428	167	13528	168	13647	139
13172	60	13309	84	13433	137	13529	137	13648	99
13173	11	13310	83	13434	26	13530	137	13649	139
13174	12	13313	148	13435	26	13531	26	13650	139
13175	93	13314	12	13436	26	13532	26	13651	139
13176	148	13315	12	13437	177	13533	26	13652	55
13178	103	13316	98	13438	177	13534	54	13655	26
13179	108	13319	107	13439	151	13536	168	13656	12
13180	25	13320	80	13440	137	13537	168	13658	12
13182	25	13322	80	13441	12	13538	168	13659	13
13183	66	13324	136	13442	12	13539	168	13660	13
13185	55	13325	137	13444	177	13540	148	13651	13
13186	25	13326	137	13446	101	13541	168	13662	13
13187	136	13331	137	13447	105	13552	101	13664	85
13188	91	13333	137	13448	80	13553	103	13665	139
13189	92	13334	40	13449	98	13554	138	13667	31
13190	92	13335	39	13451	80	13555	26	13673	99
13191	48	13338	149	13452	80	13556	138	13674	46
13192	108	13342	12	13453	80	13557	103	13676	108
13193	47	13347	26	13454	80	13558	96	13677	113
13194	45	13348	59	13455	80	13559	96	13678	58
13203	91	13349	61	13456	137	13560	31	13681	139
13204	31	13350	26	13457	137	13561	12	13684	148
13206	25	13351	70	13458	108	13562	169	13685	148
13208	48	13352	72	13459	109	13563	169	13688	169
13209	90	13353	73	13467	64	13564	169	13691	98
13211	44	13354	74	13468	67	13565	169	13692	26
13212	46	13355	75	13469	59	13566	148	13693	26
13217	94	13356	76	13471	59	13567	133	13696	169
13218	95	13357	77	13472	67	13569	75	13705	26

RADIO CHOKES AND CONDENSERS

INDEX TO REFERENCE NUMBERS

SECTION 10C—cont.

Ref. No.	Page								
13706	93	13817	33	13924	170	14025	178	14120	171
13707	98	13818	139	13925	170	14026	105	14121	171
13709	35	13819	179	13926	170	14031	69	14122	171
13710	84	13822	170	13927	170	14032	73	14123	171
13716	47	13824	170	13928	148	14033	27	14124	140
13717	28	13826	95	13929	140	14034	171	14125	76
13718	139	13833	139	13930	140	14035	171	14126	75
13721	13	13835	78	13931	140	14036	171	14127	76
13723	139	13836	170	13933	27	14037	171	14130	27
13724	169	13839	139	13936	27	14038	171	14131	27
13725	169	13840	88	13937	148	14039	171	14132	27
13726	169	13841	68	13938	177	14040	171	14135	14
13727	139	13842	70	13939	177	14041	47	14136	14
13733	139	13843	74	13940	177	14042	171	14140	76
13734	108	13844	139	13941	177	14043	70	14141	35
13736	103	13846	27	13942	170	14044	140	14144	110
13737	26	13847	139	13946	107	14045	140	14152	33
13739	13	13848	177	13947	91	14046	140	14153	33
13741	148	13849	177	13948	91	14047	75	14154	34
13742	13	13850	177	13949	148	14048	45	14158	100
13743	13	13851	177	13950	140	14049	14	14159	14
13744	13	13855	98	13951	45	14050	27	14160	27
13745	13	13856	27	13953	140	14051	74	14161	27
13746	13	13857	13	13954	14	14052	47	14162	27
13747	13	13858	110	13956	170	14068	146	14172	93
13748	169	13859	140	13957	27	14070	45	14174	46
13749	139	13860	98	13959	92	14071	91	14175	151
13755	170	13861	97	13961	99	14072	90	14177	178
13756	170	13863	37	13962	46	14073	140	14180	27
13757	170	13864	108	13968	149	14077	14	14182	14
13758	170	13872	109	13969	104	14078	140	14184	151
13759	170	13873	109	13970	108	14079	140	14186	74
13760	27	13874	140	13971	99	14081	171	14190	56
13761	106	13876	140	13972	102	14082	77	14195	12
13762	101	13877	27	13973	109	14083	76	14198	27
13763	106	13878	27	13974	110	14084	75	14201	109
13764	47	13879	27	13975	95	14085	75	14202	106
13770	56	13880	27	13976	14	14087	148	14203	100
13774	13	13881	140	13977	14	14088	149	14204	140
13775	27	13882	140	13978	14	14089	149	14205	35
13776	13	13884	63	13979	101	14090	14	14206	171
13779	56	13885	106	13983	103	14093	171	14207	171
13780	58	13886	148	13984	140	14094	171	14211	35
13784	27	13890	41	13990	100	14095	171	14214	171
13785	75	13891	73	13992	110	14096	171	14215	171
13789	13	13893	77	13997	171	14097	171	14216	140
13790	139	13894	13	13998	91	14098	33	14219	68
13791	55	13899	140	13999	47	14099	77	14220	140
13792	139	13904	27	14000	140	14100	45	14221	14
13793	139	13905	98	14001	63	14103	14	14230	140
13794	139	13906	47	14002	73	14104	14	14231	14
13795	177	13907	13	14004	103	14105	171	14232	141
13796	177	13908	69	14006	140	14106	171	14233	31
13799	170	13909	27	14007	140	14107	171	14234	14
13800	170	13910	107	14008	27	14108	14	14236	172
13801	139	13911	13	14009	27	14109	14	14237	172
13805	38	13913	105	14011	171	14110	14	14238	172
13806	40	13914	42	14014	27	14111	14	14239	172
13807	41	13915	109	14015	27	14112	27	14240	172
13808	38	13917	97	14016	27	14113	151	14241	172
13809	63	13918	50	14017	14	14114	58	14242	172
13810	62	13919	13	14018	151	14115	151	14243	172
13812	73	13920	170	14019	151	14116	60	14244	172
13813	80	13921	170	14020	45	14117	60	14245	172
13814	86	13922	170	14021	65	14118	59	14246	172
13815	139	13923	170	14024	178	14119	59	14247	172

RADIO CHOKES AND CONDENSERS

INDEX TO REFERENCE NUMBERS

SECTION 10C—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
14248	101	14336	178	14426	15	14523	141	14687	174
14249	108	14337	178	14428	141	14524	141	14688	174
14250	62	14338	178	14430	50	14525	73	14691	174
14251	66	14339	173	14432	141	14526	77	14692	143
14252	27	14340	149	14433	100	14527	87	14693	143
14253	172	14341	178	14434	76	14528	36	14695	28
14254	172	14342	178	14438	106	14529	36	14696	143
14255	92	14343	178	14444	141	14543	98	14697	143
14256	98	14344	173	14446	141	14544	101	14701	28
14257	41	14345	178	14447	141	14545	101	14705	143
14258	41	14346	90	14448	141	14548	142	14706	143
14259	40	14348	173	14449	141	14549	142	14710	53
14260	38	14349	178	14450	28	14550	142	14722	174
14261	149	14350	178	14451	28	14554	142	14729	28
14262	172	14351	178	14452	28	14555	64	14730	151
14263	27	14352	173	14453	36	14564	35	14733	15
14264	178	14353	173	14454	141	14565	142	14743	149
14265	172	14354	178	14455	141	14566	142	14744	149
14266	178	14358	173	14460	141	14567	142	14750	143
14267	178	14359	173	14461	103	14568	103	14751	143
14268	178	14360	173	14462	98	14569	142	14759	143
14269	151	14362	15	14463	97	14570	142	14764	174
14271	149	14363	15	14464	37	14571	77	14765	28
14272	30	14366	71	14465	37	14572	42	14769	15
14273	141	14367	149	14466	66	14574	36	14834	73
14275	172	14371	90	14467	68	14582	67	14839	175
14276	172	14372	90	14468	141	14590	142	14844	143
14277	172	14378	28	14469	45	14592	28	14845	143
14278	14	14379	28	14471	174	14593	28	14846	46
14279	14	14380	66	14472	174	14594	15	14847	31
14280	151	14381	64	14473	174	14595	15	14852	143
14281	151	14382	66	14474	174	14596	15	14855	175
14284	151	14383	64	14475	85	14597	174	14856	175
14285	54	14384	63	14476	35	14598	174	14857	143
14286	172	14385	62	14477	28	14599	174	14858	143
14288	172	14386	60	14478	174	14600	174	14860	28
14289	172	14387	66	14479	174	14601	142	14869	143
14290	172	14388	63	14480	174	14602	142	14870	144
14291	74	14389	141	14481	141	14603	142	14871	144
14301	141	14390	92	14483	141	14604	142	14872	144
14302	46	14391	76	14485	59	14605	142	14875	144
14303	47	14392	141	14486	141	14607	142	14876	144
14304	172	14393	74	14487	15	14618	28	14877	73
14305	172	14394	72	14489	142	14623	142	14878	144
14306	172	14395	141	14490	109	14625	142	14880	40
14307	172	14396	95	14492	63	14626	142	14881	149
14308	172	14397	78	14495	91	14627	142	14884	15
14309	14	14398	76	14496	141	14628	142	14885	28
14310	14	14399	76	14498	71	14629	142	14889	103
14311	27	14400	74	14499	75	14630	143	14892	144
14312	172	14401	77	14500	62	14631	143	14893	45
14313	173	14402	75	14501	54	14636	174	14895	56
14314	173	14403	70	14502	15	14637	174	14899	144
14315	173	14404	72	14507	79	14638	174	14902	175
14316	173	14405	73	14508	141	14639	174	14903	144
14317	15	14408	76	14509	80	14640	174	14904	144
14318	15	14410	173	14510	81	14641	174	14905	144
14323	173	14411	173	14511	82	14642	174	14907	144
14325	28	14412	173	14512	80	14643	174	14908	144
14329	99	14413	173	14515	41			14909	144
14330	15	14414	173	14516	82			14910	144
14331	61	14415	173	14518	87	14645	174	14914	144
14332	178	14417	63	14519	28	14652	15	14919	152
14333	178	14421	72	14520	174	14658	28	14925	69
14334	178	14422	72	14521	174	14659	143	14963	152
14335	178	14425	15	14522	174	14676	143	14976	15
						14678	143	14986	175

RADIO CHOKES AND CONDENSERS

INDEX TO REFERENCE NUMBERS

SECTION 10C—cont.

Ref. No.	Page								
14987	175	15129	89	15255	67	15768	72	15867	45
14988	175	15130	88	15274	145	15769	65	15868	39
14989	175	15131	85	15277	29	15770	86	15869	39
14990	175	15132	89	15278	29	15771	43	15870	40
14991	175	15134	144	15279	16	15772	55	15871	38
14992	28	15135	144	15280	145	15773	60	15872	145
14993	75	15136	145	15282	76	15774	76	15873	37
14994	101	15137	145	15704	74	15775	71	15874	53
14995	54	15138	145	15705	84	15776	69	15875	54
14998	108	15139	176	15706	88	15777	69	15876	54
15004	106	15140	145	15707	99	15778	44	15877	56
15007	15	15141	145	15708	98	15779	44	15878	57
15008	53	15142	145	15709	100	15780	43	15879	57
15010	175	15146	176	15710	102	15781	50	15880	57
15011	175	15147	40	15711	109	15783	83	15881	60
15012	175	15148	41	15712	109	15784	97	15882	60
15028	15	15149	42	15713	110	15785	66	15884	145
15030	179	15150	42	15714	110	15786	34	15887	82
15031	15	15151	41	15715	110	15788	105	15889	80
15033	175	15152	63	15716	111	15789	83	15892	145
15034	175	15153	46	15717	111	15790	79	15894	145
15035	175	15154	74	15718	111	15791	79	15900	69
15037	144	15155	53	15719	112	15792	78	15901	145
15040	69	15156	53	15720	112	15793	78	15902	65
15041	70	15159	57	15721	113	15794	79	15904	29
15042	72	15167	37	15722	87	15795	79	15906	176
15044	175	15168	37	15723	89	15797	79	15907	90
15046	101	15170	40	15724	89	15799	106	15908	91
15047	101	15173	38	15725	78	15800	73	15909	91
15048	103	15174	38	15726	79	15816	145	15910	36
15050	73	15175	39	15727	78	15818	145	15913	145
15069	144	15176	15	15728	68	15819	145	15914	35
15070	144	15177	16	15729	68	15826	74	15915	145
15071	144	15178	16	15730	69	15832	39	15924	145
15073	28	15179	15	15731	71	15833	39	15925	145
15074	152	15180	28	15732	71	15834	40	15926	106
15075	175	15181	28	15733	76	15835	38	15927	63
15076	176	15185	58	15734	77	15836	57	15936	87
15077	89	15187	44	15735	45	15837	47	15938	145
15078	84	15188	53	15736	47	15838	37	15939	85
15083	88	15190	47	15737	100	15839	41	15943	145
15086	92	15191	54	15738	100	15840	42	15950	86
15087	176	15192	60	15739	112	15841	58	15952	76
15088	176	15193	62	15740	99	15842	58	15953	89
15089	176	15195	38	15742	62	15843	56	15954	91
15090	176	15196	37	15743	82	15844	58	15955	103
15091	176	15197	37	15744	58	15845	59	15957	176
15093	58	15198	37	15745	78	15846	61	15959	73
15095	36	15199	37	15746	78	15847	63	15960	60
15096	57	15201	90	15747	76	15848	64	15961	16
15097	53	15209	178	15748	65	15849	145	15962	129
15098	53	15211	108	15749	84	15850	145	15963	145
15099	56	15215	34	15750	87	15851	145	15964	41
15101	37	15218	16	15751	86	15852	145	15967	104
15102	144	15220	65	15753	68	15853	145	15969	46
15103	144	15221	58	15754	69	15854	38	15971	89
15104	144	15223	145	15755	85	15855	56	15973	90
15105	39	15226	40	15756	69	15856	62	15974	41
15106	39	15227	51	15757	68	15857	62	15975	42
15107	144	15228	51	15758	70	15858	62	15981	80
15119	79	15242	40	15759	70	15859	65	15986	72
15122	35	15244	89	15760	71	15860	66	15987	56
15123	144	15245	87	15761	71	15862	36	15988	54
15125	89	15251	45	15762	84	15863	37	15989	145
15126	89	15253	176	15763	75	15864	53	15991	16
15128	86	15254	176	15764	71	15866	67		