

Issued with A/L.21

**AIR PUBLICATION 1086
BOOK 4 (iii)**

SECTION 10W

**RADIO RESISTORS
AND
MISCELLANEOUS SPARES**

**Items under Section 10W are covered by
VOTE 7 C. I**

AMENDMENT LISTS CONCERNING SECTION 10W

The amendments promulgated in the undermentioned Amendment Lists have been inserted.

Amendment List		Inserted by	Date
No.	Date		
Amendment Lists 1 to 20 incorporated			18/1/50
A/L No.	5-1-57	C.W. King.	27-9-57

RESTRICTED

**AIR MINISTRY
AIR PUBLICATION 1086—BOOK 4 (iii)**

**VOCABULARY OF ROYAL AIR FORCE EQUIPMENT
RADIO RESISTORS**

SECTION 10W

(18th January, 1950)

PREFACE

RESISTORS have previously been shown in A.P.1086 in type-number sequence. In order to assist Service personnel in identification, and the selecting of suitable alternatives, resistors have been divided into the undermentioned categories.

Within each category resistors have been arranged in ascending order of ohmic value, tolerance, and wattage.

- | | <i>Pages</i> |
|--|--------------|
| 1. FIXED:— | |
| (a) Carbon rod, 3 watt and under | 1-22 |
| (b) Carbon rod, high stability type | 23-29 |
| (c) Carbon rod, protected, concentric wire ends ($\frac{1}{4}$, $\frac{1}{2}$, and 1 watt) | 29-30 |
| (d) Carbon rod/tube type, with metallised ends, for clip holders | 31-32 |
| (e) Metallised filament, in insulating bakelite tube, with concentric wire ends ($\frac{1}{4}$, $\frac{1}{2}$, $\frac{1}{2}$, and 1 watt) | 33-35 |
| (f) Wire-wound, non-vitreous | 36-39 |
| (g) Wire-wound, vitreous | 40-62 |
| 2. VARIABLE:— | |
| (a) Ganged potentiometer style | 63-65 |
| (b) Potentiometer style, carbon composition element | 66-89 |
| (c) Potentiometer style, wire-wound element | 90-111 |
| 3. MISCELLANEOUS:— | |
| Items not included in any of the above-mentioned categories ... | 112-162 |
| 4. This publication covers "RESISTORS" with R.A.F. Domestic Number ONLY. For Resistors bearing an Inter-service Number, reference should be made to the Inter-service Catalogue of Electronic Components. | |

Demands for resistors not shown in this vocabulary are to be supported by a written statement quoting the main item of equipment for which the resistor is required, and stating why alternatives given in the vocabulary cannot be accepted. A.M.O. N.726/45 refers.

SECTION 10W

RADIO RESISTORS

COLOUR CODE FOR IDENTIFICATION OF RESISTORS

The Radio Manufacturers' Association (R.M.A.) Colour Code is a system for the easy identification of resistors, but is to be used as a guide only. No guarantee is given that resistors in use in the Service conform to this system of identification.

All items so marked are classified into groups based on size and wattage:—

R.M.A. Code	Wattage	Max. Voltage	Body Length	Body Diameter
0	3	1,500	in. 2½	in. 9/16
1	2	1,000	2	3/8
2	1	1,000	1¾	¼
3	½	1,000	1	¼
4	¼	1,000	11/16	3/16
7B	1/10	500	3/8	1/8
8	1/2	1,000	11/16	1/8
9	¼	500	7/16	1/8

The colours on the resistors represent resistor value and tolerance as shown below:—

	Black (Bk)	Brown (Bn)	Red (Rd)	Orange (Or)	Yellow (Ye)	Green (Gn)	Blue (Bl)	Violet (Vi)	Grey (Gy)	White (Wh)
Body ...	0	1	2	3	4	5	6	7	8	9
End ...	0	1	2	3	4	5	6	7	8	9
Dot (or band)	·0	0	00	000	0,000	00,000	—	—	—	—
Tol'rance	Silver tip=10 per cent. Gold tip=5 per cent. All others=20 per cent.									

For example:—A resistor size 2 in. × 3/8 in. with a Brown body, Black end and a Brown dot, would be:—

- (a) R.M.A. Code, 1, 2 watts.
- (b) 100 ohms (Brown body = 1; Black end = 0; Brown dot = 0).
- (c) 20 per cent. tolerance.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Connection	Insulated or Non-insulated	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Body Length Inches	Overall Diameter Inches					
1											
	RESISTORS:--										
	Fixed:--										
	Carbon rod:--										
	3 watt and under:--										
6069	Type 6069	1	10	$\frac{1}{2}$	$\frac{7}{8}$	$\frac{1}{4}$	Axial Wires	Insulated	C	each	5
457	Type 775	1	10	$\frac{2}{3}$	$\frac{2}{3}$	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	5
1095	Type 1095	2	5	2	$\frac{2}{3}$	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	5
1677	Type 1677	3	5	$\frac{1}{2}$	1	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	5
7915	Type 7915	3-3	10	$\frac{1}{2}$	$\frac{11}{8}$	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	5
803	Type 909	4	10	$\frac{1}{2}$	$\frac{11}{8}$	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	10
1840	Type 1840	4	10	$\frac{1}{2}$	$\frac{11}{8}$	$\frac{1}{4}$	Axial Wires	Ceramic Ins.	C	"	5
16404	Type 4985	4.7	10	1	$\frac{7}{8}$	$\frac{1}{4}$	Axial Wires	Non-insulated	C	"	5
1834	Type 1834	5	10	$\frac{1}{2}$	$\frac{11}{8}$	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	10
1676	Type 1676	6	5	$\frac{1}{2}$	1	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	5
7025	Type 7025	6	10	$\frac{1}{2}$	1	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	5
7318	Type 7318	6	20	$\frac{1}{2}$	1	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	5
8816	Type 2253	7	10	$\frac{1}{2}$	$\frac{7}{8}$	$\frac{1}{4}$	Axial Wires	Non-insulated	C	"	5
9689	Type 2918	10	5	$\frac{1}{2}$	$\frac{7}{8}$	$\frac{1}{4}$	Axial Wires	Ceramic Ins.	C	"	5
9746	Type 2967	10	5	$\frac{1}{2}$	$\frac{13}{16}$	$\frac{3}{16}$	Side Wires	Non-insulated	C	"	5
1484	Type 1484	10	10	$\frac{1}{2}$	$\frac{13}{16}$	$\frac{3}{16}$	Side Wires	Non-insulated	C	"	10
6649	Type 6649	10	10	$\frac{1}{2}$	$\frac{13}{16}$	$\frac{3}{16}$	Side Wires	Non-insulated	C	"	10
10834	Type 3600	13	20	$\frac{1}{2}$	$\frac{13}{16}$	$\frac{3}{16}$	Side Wires	Non-insulated	C	"	10
10708	Type 3536	13.5	5	$\frac{1}{2}$	$\frac{7}{8}$	$\frac{1}{4}$	Axial Wires	Non-insulated	C	"	5
898	Type 952	15	5	$\frac{1}{2}$	$\frac{7}{8}$	$\frac{1}{4}$	Axial Wires	Ceramic Ins.	C	"	10
8725	Type 2180	16	10	$\frac{1}{2}$	$\frac{7}{8}$	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	5
6865	Type 6865	16	5	1	$\frac{13}{16}$	$\frac{3}{16}$	Axial Wires	Ceramic Ins.	C	"	5
15011	Type 3720	18	5	1	$\frac{13}{16}$	$\frac{3}{16}$	Side Wires	Non-insulated	C	"	5
1458	Type 1458	18	10	$\frac{1}{2}$	1	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	10
15895	Type 4576	18	20	$\frac{1}{2}$	$\frac{7}{8}$	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	10
980	Type 980	20	5	$\frac{1}{2}$	$\frac{7}{8}$	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	2
10894	Type 439	20	10	$\frac{1}{2}$	$\frac{7}{8}$	$\frac{1}{4}$	Axial Wires	Ceramic Ins.	C	"	10

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM BODY DIMENSIONS		Connection	Insulated or Non-insulated	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Body Length inches	Overall Diameter inches					
1	2	3	4	5	6	7	8	9	10	11	12
	RESISTORS—cont. Fixed—cont. Carbon rod—cont. 3 watt and under—cont.										
6497	Type 6497 ...	20	10	$\frac{1}{2}$	1 $\frac{11}{16}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	each	5
1548	Type 1548 ...	20	10	1	$\frac{11}{16}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	"	5
7252	Type 7252 ...	20	10	3	2 $\frac{11}{16}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	"	2
15702	Type 4397 ...	20-6	5	$\frac{1}{2}$	$\frac{11}{16}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	"	10
15896	Type 4577 ...	22	5	$\frac{1}{2}$	$\frac{11}{16}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	"	10
15504	Type 4213 ...	22	10	$\frac{1}{2}$	$\frac{11}{16}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	"	5
9466	Type 2722 ...	22	20	$\frac{1}{2}$	$\frac{11}{16}$	$\frac{3}{8}$	Axial Wires	Carbon Semi-ins.	C	"	10
6472	Type 6472 ...	25	3	$\frac{1}{2}$	$\frac{11}{16}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	"	5
6866	Type 6866 ...	25	5	1 $\frac{1}{2}$	$\frac{11}{16}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	"	5
1287	Type 1287 ...	25	10	$\frac{1}{2}$	$\frac{11}{16}$	$\frac{3}{8}$	Axial Wires	Non-insulated	C	"	5
461	Type 779 ...	25	10	2	$\frac{11}{16}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	"	5
1174	Type 1174 ...	30	10	$\frac{1}{2}$	$\frac{11}{16}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	"	5
1098	Type 1098 ...	30	10	$\frac{1}{2}$	$\frac{11}{16}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	"	10
1755	Type 1755 ...	30	10	$\frac{1}{2}$	$\frac{11}{16}$	$\frac{3}{8}$	Axial Wires	Ceramic Ins.	C	"	10
7609	Type 7609 ...	30	10	$\frac{1}{2}$	$\frac{11}{16}$	$\frac{3}{8}$	Axial Wires	Ceramic Ins.	C	"	5
6481	Type 6481 ...	30	10	1 $\frac{1}{2}$	$\frac{11}{16}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	"	5
1459	Type 1459 ...	33	2	$\frac{1}{2}$	$\frac{11}{16}$	$\frac{3}{8}$	Axial Wires	Non-insulated	C	"	10
665	Type 863 ...	33	10	$\frac{1}{2}$	$\frac{11}{16}$	$\frac{3}{8}$	Side Wires	Ceramic Ins.	C	"	10
1606	Type 1606 ...	33	10	$\frac{1}{2}$	$\frac{11}{16}$	$\frac{3}{8}$	Axial Wires	Ceramic Ins.	C	"	5
1679	Type 1679 ...	33	10	1.	$\frac{11}{16}$	$\frac{3}{8}$	Side Wires	Ceramic Ins.	C	"	5
9757	Type 2977 ...	33	10	$\frac{1}{2}$	$\frac{11}{16}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	"	5
10837	Type 3603 ...	33	10	3	2 $\frac{11}{16}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	"	2
8619	Type 2124 ...	33	20	$\frac{1}{2}$	$\frac{11}{16}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	"	10
7688	Type 7688 ...	36	10	$\frac{1}{2}$	$\frac{11}{16}$	$\frac{3}{8}$	Axial Wires	Ceramic Ins.	C	"	5
6340	Type 6340 ...	36	10	2	2 $\frac{11}{16}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	"	5
1311	Type 1311 ...	38	10	$\frac{1}{2}$	$\frac{11}{16}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	"	5
15568	Type 4275 ...	39	2	$\frac{1}{2}$	$\frac{11}{16}$	$\frac{3}{8}$	Axial Wires	Ceramic Ins.	C	"	10

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Connection	Insulated or Non-insulated	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Body Length inches	Overall Diameter inches					
1	RESISTORS—cont. Fixed—cont. Carbon rod—cont. 3 watt and under—cont.										
66	Type 566 ...	40	10	1/2	1/8	1/8	Axial Wires	Ceramic Ins.	C	each	5
750	Type 888 ...	42	1	1/2	1/8	1/8	Axial Wires	Ceramic Ins.	C	"	5
8297	Type 8297 ...	47	20	1/2	1/8	1/8	Side Wires	Non-insulated	C	"	10
9768	Type 2979 ...	47	20	2	1/8	1/8	Side Wires	Non-insulated	C	"	5
597	Type 832 ...	50	1	1/2	1/8	1/8	Axial Wires	Ceramic Ins.	C	"	5
15503	Type 4212 ...	50	10	1/2	1/8	1/8	—	Carbon rod Semi-ins.	C	"	5
6175	Type 6175 ...	50	2 1/2	1/2	1/8	1/8	Side Wires	Non-insulated	C	"	10
48	Type 559 ...	50	5	1/2	1/8	1/8	Axial Wires	Ceramic Ins.	C	"	10
121	Type 589 ...	50	5	1/2	1/8	1/8	Axial Wires	Ceramic Ins.	C	"	5
10845	Type 428 ...	50	5	2	1/8	1/8	Side Wires	Non-insulated	C	"	5
1703	Type 1703 ...	50	10	1/2	1/8	1/8	Side Wires	Non-insulated	C	"	10
8	Type 542 ...	50	10	1/2	1/8	1/8	Axial Wires	Ceramic Ins.	C	"	10
11685	Type 519 ...	50	10	1/2	1/8	1/8	Axial Wires	Ceramic Ins.	C	"	5
298	Type 724 ...	50	10	1/2	1/8	1/8	Side Wires	Non-insulated	C	"	5
530	Type 801 ...	50	10	1/2	1/8	1/8	Side Wires	Non-insulated	C	"	5
7580	Type 7580 ...	50	15	1/2	1/8	1/8	—	—	C	"	50
1857	Type 1857 ...	50	20	1/2	1/8	1/8	Axial Wires	Ceramic Ins.	C	"	10
6676	Type 6676 ...	50	20	1/2	1/8	1/8	Side Wires	Non-insulated	C	"	5
7214	Type 7214 ...	51	5	1/2	1/8	1/8	Side Wires	Non-insulated	C	"	10
15245	Type 3954 ...	51	10	1/2	1/8	1/8	—	—	C	"	50
1675	Type 1675 ...	60	5	1/2	1/8	1/8	Side Wires	Non-insulated	C	"	5
7029	Type 7029 ...	60	10	1/2	1/8	1/8	Side Wires	Non-insulated	C	"	10
7500	Type 7500 ...	60	10	1/2	1/8	1/8	—	—	C	"	5
1313	Type 1313 ...	60	10	1/2	1/8	1/8	Side Wires	Non-insulated	C	"	5
15567	Type 4274 ...	61.5	2	1/2	1/8	1/8	—	—	C	"	5
15590	Type 4295 ...	63.2	2	1/2	1/8	1/8	—	—	C	"	5
6073	Type 6073 ...	65	10	1/2	1/8	1/8	Side Wires	Non-insulated	C	"	10

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Connection	Insulated or Non-insulated	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Body Length inches	Overall Diameter inches					
1	2	3	4	5	6	7	8	9	10	11	12
	RESISTORS—cont.										
	Fixed—cont.										
	Carbon rod—cont.										
	3 watt and under—cont.										
8051	Type 8051 ...	66	5	1/2	1/8	1/8	Axial Wires	Ceramic Ins.	C	each	5
8724	Type 2179 ...	68	5	1/2	1/8	1/8	Axial Wires	Ceramic Ins.	C	"	5
9109	Type 2464 ...	68	5	1/2	1/8	1/8	Side Wires	Non-insulated	C	"	5
8194	Type 8194 ...	68	20	1/2	1/8	1/8	Side Wires	Non-insulated	C	"	10
15390	Type 4099 ...	68	20	1/2	1/8	1/8	Side Wires	Semi-insulated	C	"	5
7027	Type 7027 ...	70	10	1	1/8	1/8	Side Wires	Non-insulated	C	"	10
7035	Type 7035 ...	70	10	1	1/8	1/8	Side Wires	Non-insulated	C	"	5
7740	Type 7740 ...	70	10	1	1/8	1/8	Side Wires	Non-insulated	C	"	5
6978	Type 6978 ...	75	10	1	1/8	1/8	Side Wires	Non-insulated	C	"	5
7086	Type 7086 ...	75	10	1	1/8	1/8	Side Wires	Non-insulated	C	"	10
7433	Type 7433 ...	80	10	1	1/8	1/8	Side Wires	Ceramic Ins.	C	"	5
432	Type 767 ...	80	15	1	1/8	1/8	Axial Wires	Non-insulated	C	"	10
15110	Type 3819 ...	82	10	1	1/8	1/8	Side Wires	Non-insulated	C	"	10
10336	Type 3292 ...	82	10	1	1/8	1/8	Axial Wires	Ceramic Ins.	C	"	10
9687	Type 2917 ...	82	10	1	1/8	1/8	Axial Wires	Ceramic Ins.	C	"	5
10206	Type 3210 ...	82	10	1	1/8	1/8	Side Wires	Non-insulated	C	"	5
6131	Type 6131 ...	99	15	1	1/8	1/8	Side Wires	Non-insulated	C	"	5
1698	Type 1698 ...	100	10	1	1/8	1/8	Side Wires	Non-insulated	C	"	10
889	Type 949 ...	100	10	1	1/8	1/8	Side Wires	Non-insulated	C	"	50
6536	Type 6536 ...	100	15	1	1/8	1/8	Side Wires	Non-insulated	C	"	5
11309	Type 470 ...	100	15	1	1/8	1/8	Side Wires	Non-insulated	C	"	1
8684	Type 2158 ...	100	20	1	1/8	1/8	Side Wires	Non-insulated	C	"	10
15362	Type 4071 ...	100	20	1	1/8	1/8	Side Wires	Carbon Semi-ins.	C	"	5
15237	Type 3946 ...	110	5	1	1/8	1/8	Side Wires	Non-insulated	C	"	5
8774	Type 2224 ...	110	5	1	1/8	1/8	Axial Wires	Ceramic Ins.	C	"	10
107	Type 575 ...	125	10	1	1/8	1/8	Axial Wires	Ceramic Ins.	C	"	10
6300	Type 6300 ...	130	10	1	1/8	1/8	Axial Wires	Ceramic Ins.	C	"	10

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Connection	Insulated or Non-insulated	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Body Length inches	Overall Diameter inches					
1	RESISTORS—cont. Fixed—cont. Carbon rod—cont. 3 watt and under—cont.										
15112	Type 3821 ...	130	10	$\frac{1}{2}$	—	—	—	—	C	each	5
15047	Type 3756 ...	140	10	$\frac{1}{2}$	—	—	—	—	C	"	50
7254	Type 7254 ...	140	10	2	$\frac{1}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5
1460	Type 1460 ...	150	10	$\frac{1}{10}$	$\frac{1}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	10
807	Type 913 ...	150	10	$\frac{1}{10}$	1	$\frac{3}{16}$	Side Wires	Non-insulated	C	"	5
17521	Type 5976 ...	150	20	$\frac{1}{10}$	$\frac{1}{16}$	$\frac{3}{16}$	Side Wires	Non-insulated	C	"	10
1859	Type 1859 ...	160	20	$\frac{1}{10}$	—	—	—	—	C	"	10
9128	Type 2483 ...	180	10	$\frac{1}{10}$	$\frac{1}{16}$	$\frac{7}{16}$	Side Wires	Non-insulated	C	"	10
1013	Type 1013 ...	200	5	$\frac{1}{10}$	$\frac{1}{16}$	$\frac{7}{16}$	Side Wires	Non-insulated	C	"	10
15500	Type 4209 ...	200	5	$\frac{1}{10}$	$\frac{1}{16}$	$\frac{7}{16}$	Side Wires	Carbon rod Semi-ins.	C	"	5
6872	Type 6872 ...	200	10	$\frac{1}{10}$	$\frac{1}{16}$	$\frac{7}{16}$	Side Wires	Non-insulated	C	"	10
34	Type 551 ...	200	10	$\frac{1}{10}$	$\frac{1}{16}$	$\frac{7}{16}$	Side Wires	Non-insulated	C	"	10
239	Type 691 ...	200	10	$\frac{1}{10}$	$\frac{1}{16}$	$\frac{7}{16}$	Side Wires	Ceramic Ins.	C	"	10
11803	Type 536 ...	200	10	1	$\frac{1}{16}$	$\frac{1}{16}$	Axial Wires	Ceramic Ins.	C	"	5
1447	Type 1447 ...	200	10	$\frac{1}{10}$	$\frac{1}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5
6498	Type 6498 ...	200	10	2	$\frac{1}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5
6001	Type 6001 ...	200	10	3	2	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	2
10681	Type 3519 ...	200	20	3	$\frac{1}{16}$	$\frac{1}{16}$	—	—	C	"	10
7685	Type 7685 ...	200	20	$\frac{1}{10}$	$\frac{1}{8}$	$\frac{1}{8}$	Axial Wires	Ceramic Ins.	C	"	10
1939	Type 1939 ...	210	10	$\frac{1}{10}$	$\frac{1}{8}$	$\frac{1}{8}$	Side Wires	Non-insulated	C	"	5
9110	Type 2465 ...	220	5	$\frac{1}{10}$	1	$\frac{1}{8}$	Axial Wires	Ceramic Ins.	C	"	10
8195	Type 8195 ...	220	20	$\frac{1}{10}$	$\frac{1}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5
7409	Type 7409 ...	250	5	$\frac{1}{10}$	$\frac{1}{16}$	$\frac{1}{16}$	Axial Wires	Ceramic Ins.	C	"	5
10851	Type 434 ...	250	5	1	$\frac{1}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5
7357	Type 7357 ...	250	5	2	—	—	—	—	C	"	5
15049	Type 3758 ...	280	10	$\frac{1}{4}$	—	—	—	—	C	"	10
1862	Type 1862 ...	250	10	$\frac{1}{4}$	$\frac{1}{8}$	$\frac{1}{8}$	Axial Wires	Ceramic Ins.	C	"	10

SECTION 10W—cont.

RADIO RESISTORS

1 Ref. No.	2 NOMENCLATURE	3 Value in Ohms	4 Tolerance + or - %	5 Wattage	6 MAXIMUM DIMENSIONS		7 Overall Diameter inches	8 Connection	9 Insulated or Non-insulated	10 Class of Store	11 Denom. of Qty.	12 Carton Unit Qty.
					Body Length inches	Diameter inches						
	RESISTORS—cont.											
	Fixed—cont.											
	Carbon rod—cont.											
	3 watt and under—cont.											
123	Type 591 ...	250	10	$\frac{1}{2}$	$\frac{7}{8}$	$\frac{1}{8}$	$\frac{1}{8}$	Axial Wires	Ceramic Ins.	C	each	5
1188	Type 1188 ...	250	10	1	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	Side Wires	Non-insulated	C	"	5
1932	Type 1932 ...	250	10	2	$\frac{2}{8}$	$\frac{1}{2}$	$\frac{1}{2}$	Side Wires	Non-insulated	C	"	5
15465	Type 4174 ...	250	10	3	$\frac{2}{8}$	$\frac{1}{2}$	$\frac{1}{2}$	Side Wires	Non-insulated	C	"	2
7317	Type 7317 ...	250	20	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	Side Wires	Non-insulated	C	"	5
6482	Type 6482 ...	270	2	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	Axial Wires	Ceramic Ins.	C	"	10
15893	Type 4574 ...	270	5	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	Side Wires	Non-insulated	C	"	10
888	Type 948 ...	270	5	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	Axial Wires	Ceramic Ins.	C	"	10
10365	Type 3316 ...	270	10	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	Side Wires	Non-insulated	C	"	10
6200	Type 6200 ...	300	10	2	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	—	—	C	"	1
109	Type 577 ...	300	10	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	Axial Wires	Ceramic Ins.	C	"	10
7055	Type 7055 ...	300	10	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	Axial Wires	Ceramic Ins.	C	"	5
6890	Type 6890 ...	300	10	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	Side Wires	Non-insulated	C	"	5
10366	Type 3317 ...	330	20	1	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	Side Wires	Non-insulated	C	"	5
6439	Type 6439 ...	330	10	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	—	—	C	"	—
8168	Type 2218 ...	330	20	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	Side Wires	Non-insulated	C	"	10
111	Type 379 ...	350	5	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	—	—	C	"	5
1396	Type 1396 ...	350	10	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	—	—	C	"	10
7541	Type 7541 ...	350	10	2	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	Side Wires	Non-insulated	C	"	10
15466	Type 4175 ...	350	10	3	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	Side Wires	Non-insulated	C	"	5
6129	Type 6129 ...	350	15	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	—	—	C	"	1
6899	Type 6899 ...	390	5	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	Side Wires	Non-insulated	C	"	5
11666	Type 499 ...	400	10	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	Axial Wires	Ceramic Ins.	C	"	10
30	Type 547 ...	400	10	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	Axial Wires	Ceramic Ins.	C	"	5
224	Type 681 ...	400	15	1	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	Side Wires	Non-insulated	C	"	5
6816	Type 6816 ...	400	10	3	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	Side Wires	Non-insulated	C	"	2
1864	Type 1864 ...	400	20	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	Axial Wires	Ceramic Ins.	C	"	10

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Connection	Insulated or Non-insulated	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Body Length inches	Overall Diameter inches					
1	2	3	4	5	6	7	8	9	10	11	12
	RESISTORS—cont.										
	Fixed—cont.										
	Carbon rod—cont.										
	3 watt and under—cont.										
7708	Type 7708 ...	420	1	—	—	—	—	—	—	each	5
810	Type 916 ...	450	10	—	—	—	Side Wires	Non-insulated	C	"	10
809	Type 915 ...	450	10	—	—	—	Axial Wires	Ceramic Ins.	C	"	10
235	Type 687 ...	450	10	—	—	—	Axial Wires	Ceramic Ins.	C	"	5
15017	Type 3726 ...	470	1	20	—	—	—	—	C	"	1
6900	Type 6900 ...	470	5	—	—	—	Side Wires	Non-insulated	C	"	10
6851	Type 6851 ...	470	10	—	—	—	Side Wires	Non-insulated	C	"	10
875	Type 941 ...	470	10	—	—	—	Side Wires	Non-insulated	C	"	5
8621	Type 2126 ...	470	20	—	—	—	Side Wires	Non-insulated	C	"	10
1865	Type 1865 ...	500	5	—	—	—	Axial Wires	Ceramic Ins.	C	"	10
1843	Type 1843 ...	500	5	—	—	—	Axial Wires	Ceramic Ins.	C	"	10
1669	Type 1669 ...	500	5	2	—	—	Axial Wires	Non-insulated	C	"	5
1014	Type 1014 ...	500	10	—	—	—	Side Wires	Non-insulated	C	"	50
1838	Type 1838 ...	500	10	—	—	—	Side Wires	Non-insulated	C	"	10
6	Type 540 ...	500	10	—	—	—	—	—	C	"	10
311	Type 733 ...	500	10	—	—	—	Axial Wires	Ceramic Ins.	C	"	5
15501	Type 4210 ...	500	10	—	—	—	Axial Wires	Ceramic Ins.	C	"	5
1367	Type 1367 ...	500	10	2	—	—	—	Carbon Semi-ins.	C	"	5
295	Type 721 ...	500	10	3	—	—	Side Wires	Non-insulated	C	"	5
6215	Type 6215 ...	500	15	—	—	—	Side Wires	Non-insulated	C	"	2
7678	Type 7678 ...	500	20	—	—	—	Side Wires	Non-insulated	C	"	5
7314	Type 7314 ...	500	20	—	—	—	Axial Wires	Ceramic Ins.	C	"	10
6431	Type 6431 ...	560	5	2	—	—	Side Wires	Non-insulated	C	"	5
8685	Type 2159 ...	560	10	—	—	—	Side Wires	Non-insulated	C	"	10
5588	Type 4293 ...	569	2	—	—	—	Side Wires	Non-insulated	C	"	5
1963	Type 1963 ...	600	2½	—	—	—	Side Wires	Non-insulated	C	"	10
112	Type 580 ...	600	5	—	—	—	Axial Wires	Ceramic Ins.	C	"	10

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Connection	Insulated or Non-insulated	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Body Length inches	Overall Diameter inches					
1	2	3	4	5	6	7	8	9	10	11	12
	RESISTORS—cont.										
	Fixed—cont.										
	Carbon rod—cont.										
	3 watt and under—cont.										
1845	Type 1845 ...	600	5	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{7}{16}$ $\frac{7}{8}$	$\frac{1}{4}$ $\frac{1}{2}$	Axial Wires	Ceramic Ins.	C	each	5
6226	Type 6226 ...	600	10	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{7}{16}$ $\frac{7}{8}$	$\frac{1}{4}$ $\frac{1}{2}$	Axial Wires	Ceramic Ins.	C	"	10
28	Type 545 ...	600	10	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{7}{16}$ $\frac{7}{8}$	$\frac{1}{4}$ $\frac{1}{2}$	Axial Wires	Ceramic Ins.	C	"	5
6088	Type 6088 ...	600	10	1	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{1}{4}$ $\frac{1}{2}$	Axial Wires	Non-insulated	C	"	5
6530	Type 6530 ...	650	15	3	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{1}{4}$ $\frac{1}{2}$	Side Wires	—	C	"	1
15467	Type 4176 ...	680	10	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{7}{16}$ $\frac{7}{8}$	$\frac{1}{4}$ $\frac{1}{2}$	—	—	C	"	5
113	Type 581 ...	700	10	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{7}{16}$ $\frac{7}{8}$	$\frac{1}{4}$ $\frac{1}{2}$	—	Insulated	C	"	10
6876	Type 6876 ...	700	10	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{7}{16}$ $\frac{7}{8}$	$\frac{1}{4}$ $\frac{1}{2}$	Axial Wires	Ceramic Ins.	C	"	5
6247	Type 6247 ...	700	10	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{7}{16}$ $\frac{7}{8}$	$\frac{1}{4}$ $\frac{1}{2}$	—	—	C	"	5
1846	Type 1846 ...	800	5	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{7}{16}$ $\frac{7}{8}$	$\frac{1}{4}$ $\frac{1}{2}$	Axial Wires	Ceramic Ins.	C	"	5
7536	Type 7536 ...	800	10	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{7}{16}$ $\frac{7}{8}$	$\frac{1}{4}$ $\frac{1}{2}$	Axial Wires	Non-insulated	C	"	10
31	Type 548 ...	800	10	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{7}{16}$ $\frac{7}{8}$	$\frac{1}{4}$ $\frac{1}{2}$	Side Wires	Non-insulated	C	"	5
1338	Type 1338 ...	800	10	2	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{1}{4}$ $\frac{1}{2}$	Side Wires	Non-insulated	C	"	5
15585	Type 4290 ...	936.2	2	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{7}{16}$ $\frac{7}{8}$	$\frac{1}{4}$ $\frac{1}{2}$	Side Wires	Non-insulated	C	"	5
6856	Type 6856 ...	1K	5	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{7}{16}$ $\frac{7}{8}$	$\frac{1}{4}$ $\frac{1}{2}$	Side Wires	Non-insulated	C	"	10
1463	Type 1463 ...	1K	10	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{7}{16}$ $\frac{7}{8}$	$\frac{1}{4}$ $\frac{1}{2}$	Side Wires	Non-insulated	C	"	10
6334	Type 6334 ...	1K	15	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{7}{16}$ $\frac{7}{8}$	$\frac{1}{4}$ $\frac{1}{2}$	Side Wires	—	C	"	1
6654	Type 6654 ...	1K	20	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{7}{16}$ $\frac{7}{8}$	$\frac{1}{4}$ $\frac{1}{2}$	Side Wires	Non-insulated	C	"	10
755	Type 893 ...	1-25K	10	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{7}{16}$ $\frac{7}{8}$	$\frac{1}{4}$ $\frac{1}{2}$	Axial Wires	Non-insulated	C	"	10
15587	Type 4292 ...	1-328K	2	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{7}{16}$ $\frac{7}{8}$	$\frac{1}{4}$ $\frac{1}{2}$	Axial Wires	Ceramic Ins.	C	"	5
7922	Type 7922 ...	1.5K	5	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{7}{16}$ $\frac{7}{8}$	$\frac{1}{4}$ $\frac{1}{2}$	Side Wires	Non-insulated	C	"	5
10372	Type 3323 ...	1.5K	10	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{7}{16}$ $\frac{7}{8}$	$\frac{1}{4}$ $\frac{1}{2}$	Side Wires	Non-insulated	C	"	10
1975	Type 1975 ...	1.5K	15	2	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{7}{16}$ $\frac{7}{8}$	—	Carbon Rod in Ceramic Tube with capped ends	C	"	5
6655	Type 6655 ...	1.5K	20	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{7}{16}$ $\frac{7}{8}$	$\frac{1}{4}$ $\frac{1}{2}$	Side Wires	Non-insulated	C	"	10
1499	Type 1499 ...	1.6K	15	$\frac{1}{2}$ $\frac{1}{8}$	$\frac{7}{16}$ $\frac{7}{8}$	$\frac{1}{4}$ $\frac{1}{2}$	Side Wires	Non-insulated	C	"	5

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Connection	Insulated or Non-insulated	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Body Length Inches	Overall Diameter Inches					
1	RESISTORS—cont. Fixed—cont. Carbon rod—cont. 3 watt and under—cont.										
15584	Type 4289 ...	1.8K	2	$\frac{1}{2}$	—	—	—	—	C	each	5
9130	Type 2485 ...	1.8K	10	$\frac{1}{2}$	—	—	—	—	C	"	1
8629	Type 2134 ...	1.8K	10	$\frac{1}{2}$	—	—	—	—	C	"	1
16940	Type 5449 ...	1.9K	5	2	—	—	—	—	C	"	10
11668	Type 520 ...	2K	10	$\frac{1}{2}$	$\frac{5}{8}$	$\frac{1}{4}$	Axial Wires	Ceramic Ins.	C	"	5
11679	Type 513 ...	2K	10	$\frac{1}{2}$	$\frac{7}{8}$	$\frac{1}{4}$	Axial Wires	Ceramic Ins.	C	"	5
9158	Type 234 ...	2K	10	1	$\frac{1}{2}$	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	5
156	Type 624 ...	2K	10	2	$\frac{1}{2}$	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	5
11629	Type 496 ...	2K	10	3	2	$\frac{1}{8}$	Side Wires	Non-insulated	C	"	2
7966	Type 7966 ...	2K	20	$\frac{1}{2}$	8	$\frac{1}{4}$	Axial Wires	Ceramic Ins.	C	"	10
7319	Type 7319 ...	2K	20	$\frac{1}{2}$	1	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	5
6902	Type 6902 ...	2.2K	5	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	10
6850	Type 6850 ...	2.2K	10	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	10
8652	Type 2150 ...	2.2K	20	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	10
9600	Type 2851 ...	2.4K	5	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	10
10862	Type 3612 ...	2.4K	10	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	10
6182	Type 6182 ...	2.5K	5	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{4}$	Axial Wires	Ceramic Ins.	C	"	5
1497	Type 1497 ...	2.5K	5	2	$\frac{1}{2}$	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	5
7960	Type 7960 ...	2.5K	10	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	10
641	Type 852 ...	2.5K	10	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{4}$	Axial Wires	Ceramic Ins.	C	"	5
1829	Type 1829 ...	2.5K	10	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{4}$	Axial Wires	Non-insulated	C	"	5
157	Type 625 ...	2.5K	10	1	$\frac{1}{2}$	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	5
163	Type 631 ...	2.5K	10	2	$\frac{1}{2}$	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	2
15904	Type 4505 ...	2.7K	5	3	$\frac{1}{2}$	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	10
9129	Type 2484 ...	3K	5	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	10
830	Type 930 ...	3K	5	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{4}$	Side Wires	Non-insulated	C	"	5
310	Type 732 ...	3K	10	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{4}$	Axial Wires	Ceramic Ins.	C	"	10

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Connection	Insulated or Non-insulated	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Body Length inches	Overall Diameter inches					
1	RESISTORS—cont. Fixed—cont. Carbon rod—cont. 3 watt and under—cont.										
11680	Type 514 ...	3K	10	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{8}$	Axial Wires	Ceramic Ins.	C	each	5
1552	Type 1552 ...	3K	10	1	$\frac{11}{16}$	$\frac{1}{8}$	Side Wires	Non-insulated	C	"	5
1553	Type 1553 ...	3K	10	2	$\frac{1}{16}$	$\frac{1}{8}$	Side Wires	Non-insulated	C	"	5
164	Type 632 ...	3K	10	3	$\frac{2}{16}$	$\frac{1}{8}$	Side Wires	Non-insulated	C	"	2
6659	Type 6659 ...	3K	20	$\frac{10}{16}$	$\frac{7}{16}$	$\frac{1}{8}$	Side Wires	Non-insulated	C	"	10
8915	Type 2325 ...	3.3K	10	$\frac{10}{16}$	$\frac{7}{16}$	$\frac{1}{8}$	Side Wires	Non-insulated	C	"	10
10373	Type 3324 ...	3.3K	20	$\frac{10}{16}$	$\frac{7}{16}$	$\frac{1}{8}$	Side Wires	Non-insulated	C	"	10
15343	Type 4052 ...	3.3K	5	$\frac{1}{2}$	$\frac{8}{16}$	$\frac{3}{32}$	—	Carbon Semi-ins.	C	"	5
15228	Type 3937 ...	3.5K	10	$\frac{1}{2}$	$\frac{11}{16}$	$\frac{1}{8}$	Side Wires	Non-insulated	C	"	5
6252	Type 6252 ...	3.5K	10	2	$\frac{11}{16}$	$\frac{1}{8}$	Side Wires	Non-insulated	C	"	5
165	Type 633 ...	3.5K	10	3	$\frac{2}{16}$	$\frac{1}{8}$	Side Wires	Non-insulated	C	"	2
9136	Type 2488 ...	3.6K	5	$\frac{10}{16}$	$\frac{7}{16}$	$\frac{1}{8}$	Side Wires	Non-insulated	C	"	10
10864	Type 3614 ...	3.6K	10	$\frac{10}{16}$	$\frac{7}{16}$	$\frac{1}{8}$	Axial Wires	Ceramic Ins.	C	"	10
10588	Type 3465 ...	3.75K	5	$\frac{10}{16}$	$\frac{7}{16}$	$\frac{1}{8}$	Side Wires	Non-insulated	C	"	10
9550	Type 2801 ...	3.9K	10	$\frac{10}{16}$	$\frac{7}{16}$	$\frac{1}{8}$	Side Wires	Non-insulated	C	"	10
1096	Type 1096 ...	4K	2½	$\frac{10}{16}$	$\frac{7}{16}$	$\frac{1}{8}$	Side Wires	Non-insulated	C	"	10
1711	Type 1711 ...	4K	3	1	$\frac{11}{16}$	$\frac{1}{8}$	Side Wires	Non-insulated	C	"	5
1849	Type 1849 ...	4K	5	$\frac{1}{2}$	$\frac{11}{16}$	$\frac{1}{8}$	Axial Wires	Ceramic Ins.	C	"	5
6230	Type 6230 ...	4K	5	1	$\frac{7}{16}$	$\frac{1}{8}$	Side Wires	Non-insulated	C	"	5
11669	Type 503 ...	4K	10	1	$\frac{11}{16}$	$\frac{1}{8}$	Axial Wires	Non-insulated	C	"	10
11681	Type 515 ...	4K	10	$\frac{1}{2}$	$\frac{11}{16}$	$\frac{1}{8}$	Axial Wires	Ceramic Ins.	C	"	5
1090	Type 1090 ...	4K	10	$\frac{1}{2}$	$\frac{11}{16}$	$\frac{1}{8}$	Side Wires	Non-insulated	C	"	5
6889	Type 6889 ...	4K	10	1	$\frac{11}{16}$	$\frac{1}{8}$	Side Wires	Non-insulated	C	"	5
8121	Type 8121 ...	4K	10	1	$\frac{11}{16}$	$\frac{1}{8}$	—	Carbon Rod in Ceramic Tube with Capped Ends	C	"	5
1024	Type 1024 ...	4K	10	2	$\frac{11}{16}$	$\frac{1}{8}$	Side Wires	Non-insulated	C	"	5

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Connection	Insulated or Non-insulated	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Body Length inches	Overall Diameter inches					
1	RESISTORS—cont. Fixed—cont. Carbon rod—cont. 3 watt and under—cont.										
329	Type 747	4K	10	3	2 $\frac{1}{16}$	$\frac{11}{16}$	Side Wires	Non-insulated	C	each	2
15559	Type 4266	4.5K	5	3	—	—	—	—	C	"	10
6253	Type 6253	4.5K	10	3	—	—	Axial Wires	Ceramic Ins.	C	"	1
828	Type 929	4.7K	5	$\frac{1}{10}$	$\frac{7}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5
6433	Type 6433	4.7K	10	$\frac{1}{10}$	$\frac{7}{16}$	$\frac{3}{32}$	Side Wires	Non-insulated	C	"	10
8196	Type 8196	4.7K	20	$\frac{1}{10}$	$\frac{7}{16}$	$\frac{3}{32}$	Side Wires	Non-insulated	C	"	10
15351	Type 4060	4.7K	20	$\frac{1}{10}$	$\frac{7}{16}$	$\frac{3}{32}$	—	Carbon Semi-ins.	C	"	5
6858	Type 6858	5K	5	$\frac{1}{10}$	$\frac{7}{16}$	$\frac{3}{32}$	Side Wires	Non-insulated	C	"	10
1873	Type 1873	5K	5	$\frac{1}{10}$	$\frac{7}{16}$	$\frac{3}{32}$	Side Wires	Ceramic Ins.	C	"	10
907	Type 957	5K	5	1	$\frac{1}{16}$	$\frac{1}{16}$	Axial Wires	Non-insulated	C	"	5
1455	Type 1455	5K	10	$\frac{1}{10}$	$\frac{7}{16}$	$\frac{3}{32}$	Side Wires	Non-insulated	C	"	10
11670	Type 504	5K	10	$\frac{1}{10}$	$\frac{7}{16}$	$\frac{3}{32}$	Side Wires	Ceramic Ins.	C	"	5
11682	Type 516	5K	10	$\frac{1}{10}$	$\frac{7}{16}$	$\frac{3}{32}$	Side Wires	Non-insulated	C	"	5
9633	Type 271	5K	10	1	$\frac{1}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5
459	Type 777	5K	10	2	$\frac{1}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	2
620	Type 844	5K	10	3	$\frac{1}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5
1874	Type 1874	5K	20	1	$\frac{1}{16}$	$\frac{1}{16}$	Axial Wires	Ceramic Ins.	C	"	10
6843	Type 6843	5K	20	$\frac{1}{10}$	$\frac{7}{16}$	$\frac{3}{32}$	Side Wires	Non-insulated	C	"	5
8174	Type 8174	5K	20	$\frac{1}{10}$	$\frac{7}{16}$	$\frac{3}{32}$	Side Wires	Non-insulated	C	"	5
7215	Type 7215	5K	20	1	$\frac{1}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	10
15586	Type 4291	5.1K	5	$\frac{1}{10}$	$\frac{7}{16}$	$\frac{3}{32}$	Side Wires	Non-insulated	C	"	5
7001	Type 7001	5.123K	2	$\frac{1}{10}$	$\frac{7}{16}$	$\frac{3}{32}$	Side Wires	Non-insulated	C	"	2
287	Type 715	5.5K	5	3	$\frac{1}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5
9131	Type 2486	5.6K	10	1	$\frac{1}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5
1465	Type 1465	5.6K	5	$\frac{1}{10}$	$\frac{7}{16}$	$\frac{3}{32}$	Side Wires	Non-insulated	C	"	10
1876	Type 1876	6K	5	$\frac{1}{10}$	$\frac{7}{16}$	$\frac{3}{32}$	Side Wires	Non-insulated	C	"	10
1300	Type 1300	6K	5	2	$\frac{1}{16}$	$\frac{1}{16}$	Axial Wires	Ceramic Ins.	C	"	5

SECTION 10W—cont.

RADIO RESISTORS

1	2	3	4	5	6		7	8	9	10	11	12
					Body Length Inches	Overall Diameter Inches						
Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Connection	Insulated or Non-insulated	Class of Store	Denom. of Qty.	Carton Unit Qty.	
	RESISTORS—cont.											
	Fixed—cont.											
	Carbon rod—cont.											
	3 watt and under—cont.											
341	Type 753 ...	6K	10	$\frac{1}{2}$	$\frac{3}{8}$	$\frac{1}{16}$	Axial Wires	Ceramic Ins.	C	each	5	
1337	Type 1337 ...	6K	10	2	$\frac{1}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5	
6152	Type 6152 ...	6K	10	3	$\frac{1}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	2	
10865	Type 3615 ...	6-2K	10	$\frac{1}{2}$	$\frac{3}{8}$	$\frac{1}{16}$	Axial Wires	Ceramic Ins.	C	"	10	
10591	Type 3467 ...	6-6K	5	$\frac{1}{2}$	$\frac{3}{8}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	10	
15494	Type 4203 ...	6-6K	5	$\frac{1}{2}$	$\frac{3}{8}$	$\frac{1}{16}$	Axial Wires	Ceramic Ins.	C	"	2	
9927	Type 3091 ...	6-8K	10	3	$\frac{1}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	2	
9926	Type 3090 ...	6-8K	20	3	$\frac{1}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	2	
6389	Type 6389 ...	7K	5	1	$\frac{1}{16}$	$\frac{1}{16}$	Axial Wires	Non-insulated	C	"	1	
7432	Type 7432 ...	7K	10	$\frac{1}{2}$	$\frac{3}{8}$	$\frac{1}{16}$	Side Wires	Ceramic Ins.	C	"	10	
1851	Type 1851 ...	7K	10	$\frac{1}{2}$	$\frac{3}{8}$	$\frac{1}{16}$	Axial Wires	Ceramic Ins.	C	"	5	
1712	Type 1712 ...	7-5K	3	$\frac{1}{2}$	$\frac{3}{8}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	10	
832	Type 931 ...	7-5K	5	$\frac{1}{2}$	$\frac{3}{8}$	$\frac{1}{16}$	Axial Wires	Ceramic Ins.	C	"	5	
6244	Type 6244 ...	7-5K	10	$\frac{1}{2}$	$\frac{3}{8}$	$\frac{1}{16}$	Axial Wires	Ceramic Ins.	C	"	5	
10899	Type 444 ...	7-5K	10	2	$\frac{1}{16}$	$\frac{1}{16}$	—	—	C	"	5	
9443	Type 2699 ...	8K	5	$\frac{1}{2}$	$\frac{3}{8}$	$\frac{1}{16}$	Axial Wires	Ceramic Ins.	C	"	5	
1733	Type 1733 ...	8K	10	1	$\frac{1}{16}$	$\frac{1}{16}$	Axial Wires	Ceramic Ins.	C	"	5	
6886	Type 6886 ...	8K	10	1	$\frac{1}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5	
7253	Type 7253 ...	8K	10	2	$\frac{1}{16}$	$\frac{1}{16}$	—	—	C	"	—	
6884	Type 6884 ...	8K	10	3	$\frac{1}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	2	
15354	Type 4063 ...	8K	20	$\frac{1}{2}$	$\frac{3}{8}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5	
11626	Type 493 ...	8K	10	2	$\frac{1}{16}$	$\frac{1}{16}$	Axial Wires	Non-insulated	C	"	5	
316	Type 734 ...	9-9K	10	2	$\frac{1}{16}$	$\frac{1}{16}$	—	—	C	"	5	
6852	Type 6852 ...	10K	2 $\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{16}$	$\frac{1}{16}$	Side Wires	Ceramic Ins.	C	"	10	
1839	Type 7B/74 ...	10K	10	$\frac{1}{2}$	$\frac{1}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	10	
15357	Type 4066 ...	10K	10	$\frac{1}{2}$	$\frac{1}{16}$	$\frac{1}{16}$	—	—	C	"	5	
6660	Type 6660 ...	10K	20	$\frac{1}{2}$	$\frac{1}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	10	

SECTION 10W—cont.

RADIO RESISTORS

1	2	3	4	5	6		7	8	9	10	11	12
					Body Length inches	Overall Diameter inches						
Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Connection	Insulated or Non-insulated	Class of Store	Denom. of Qty.	Carton Qty. Unit	
6706	RESISTORS—cont. Fixed—cont. Carbon rod—cont. 3 watt and under—cont.	10K	20	$\frac{1}{4}$ W	$\frac{11}{16}$	$\frac{3}{32}$	Side Wires	Non-insulated	C	each	10	
15751	Type 6706 ...	11K	5	$\frac{1}{10}$ W	$\frac{11}{16}$	$\frac{7}{32}$	Side Wires	Non-insulated	C	"	1	
9357	Type 441 ...	11K	10	$\frac{1}{10}$ W	$\frac{7}{16}$	$\frac{11}{32}$	Side Wires	Non-insulated	C	"	5	
9549	Type 2648 ...	12K	10	$\frac{1}{10}$ W	$\frac{7}{16}$	$\frac{11}{32}$	Side Wires	Non-insulated	C	"	10	
1253	Type 2800 ...	12K	15	$\frac{3}{10}$ W	$\frac{2}{16}$	$\frac{11}{16}$	Side Wires	Non-insulated	C	"	2	
905	Type 1253 ...	12.5K	5	$\frac{2}{10}$ W	$\frac{2}{16}$	$\frac{11}{16}$	Side Wires	Non-insulated	C	"	5	
15502	Type 955 ...	15K	10	$\frac{1}{2}$ W	$\frac{3}{8}$	$\frac{3}{16}$	Side Wires	Carbon Semi-Ins.	C	"	5	
8266	Type 4211 ...	15K	20	$\frac{1}{2}$ W	$\frac{7}{16}$	$\frac{3}{16}$	Side Wires	Non-insulated	C	"	10	
15900	Type 8266 ...	16K	5	$\frac{1}{10}$ W	$\frac{7}{16}$	$\frac{3}{16}$	Side Wires	Non-insulated	C	"	10	
158	Type 4581 ...	16K	10	$\frac{1}{10}$ W	$\frac{7}{16}$	$\frac{3}{16}$	Side Wires	Non-insulated	C	"	5	
854	Type 626 ...	17K	2	$\frac{1}{4}$ W	$\frac{2}{16}$	$\frac{3}{16}$	Axial Wires	Ceramic Ins.	C	"	5	
6092	Type 935 ...	17K	10	$\frac{1}{4}$ W	$\frac{2}{16}$	$\frac{3}{16}$	Side Wires	Non-insulated	C	"	5	
1925	Type 6092 ...	18K	10	$\frac{1}{10}$ W	$\frac{1}{16}$	$\frac{7}{32}$	Side Wires	Non-insulated	C	"	10	
15788	Type 7B/77 ...	18K	10	$\frac{1}{10}$ W	$\frac{1}{16}$	$\frac{7}{32}$	Side Wires	Non-insulated	C	"	5	
8527	Type 4472 ...	18K	10	$\frac{1}{10}$ W	$\frac{1}{16}$	$\frac{7}{32}$	Side Wires	Non-insulated	C	"	5	
9762	Type 2043 ...	18K	2	$\frac{2}{10}$ W	$\frac{1}{16}$	$\frac{7}{32}$	Side Wires	Non-insulated	C	"	5	
9288	Type 283 ...	20K	5	$\frac{1}{2}$ W	$\frac{1}{16}$	$\frac{7}{32}$	Side Wires	Non-insulated	C	"	10	
11379	Type 2612 ...	20K	10	$\frac{1}{2}$ W	$\frac{1}{16}$	$\frac{7}{32}$	Side Wires	Non-insulated	C	"	10	
32	Type 475 ...	20K	10	$\frac{1}{2}$ W	$\frac{1}{16}$	$\frac{7}{32}$	Axial Wires	Ceramic Ins.	C	"	5	
455	Type 549 ...	20K	10	$\frac{1}{2}$ W	$\frac{1}{16}$	$\frac{7}{32}$	Axial Wires	Ceramic Ins.	C	"	5	
10139	Type 773 ...	20K	10	$\frac{1}{2}$ W	$\frac{2}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5	
1878	Type 367 ...	20K	10	$\frac{1}{2}$ W	$\frac{2}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5	
6095	Type 1878 ...	20K	20	$\frac{1}{2}$ W	$\frac{2}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	10	
15048	Type 6095 ...	21K	10	$\frac{1}{2}$ W	$\frac{2}{16}$	$\frac{1}{16}$	Axial Wires	Ceramic Ins.	C	"	5	
841	Type 3757 ...	22K	—	$\frac{1}{2}$ W	$\frac{2}{16}$	$\frac{1}{16}$	—	—	C	"	5	
1697	Type 933 ...	22K	10	$\frac{1}{2}$ W	$\frac{2}{16}$	$\frac{1}{16}$	—	—	C	"	10	
15359	Type 1697 ...	22K	10	$\frac{1}{2}$ W	$\frac{2}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5	
	Type 4068 ...	22K	—	$\frac{1}{2}$ W	$\frac{2}{16}$	$\frac{1}{16}$	—	Carbon Semi-ins.	C	"	5	

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Connection	Insulated or Non-insulated	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Body Length inches	Overall Diameter inches					
1	RESISTORS—cont. Fixed—cont. Carbon rod—cont. 3 watt and under—cont.										
8692	Type 2162 ...	22K	20	1/2	1 7/8	Side Wires	Non-insulated	C	each	10	
15352	Type 4061 ...	22K	20	1/2	1 7/8	Side Wires	Carbon Semi-ins.	C	"	5	
1880	Type 1880 ...	23K	5	1/2	1 7/8	Side Wires	Non-insulated	C	"	10	
159	Type 627 ...	23K	10	2	2 1/8	Side Wires	Non-insulated	C	"	5	
574	Type 821 ...	23K	15	3	2 1/8	Side Wires	Non-insulated	C	"	2	
15248	Type 3957 ...	25K	1	1/2	1 7/8	Side Wires	Non-insulated	C	"	1	
6184	Type 6184 ...	25K	5	1/2	1 7/8	Axial Wires	Ceramic Ins.	C	"	10	
1756	Type 1756 ...	25K	5	1/2	1 7/8	Axial Wires	Ceramic Ins.	C	"	5	
6404	Type 6404 ...	25K	5	1/2	1 7/8	Side Wires	Non-insulated	C	"	5	
1291	Type 1291 ...	25K	5	1/2	1 7/8	Side Wires	Non-insulated	C	"	5	
1500	Type 1500 ...	25K	5	2	2 1/8	Side Wires	Non-insulated	C	"	2	
11672	Type 506 ...	25K	10	3	2 1/8	Axial Wires	Ceramic Ins.	C	"	10	
11684	Type 518 ...	25K	10	1/2	1 7/8	Axial Wires	Ceramic Ins.	C	"	5	
1126	Type 1126 ...	25K	10	1/2	1 7/8	Side Wires	Non-insulated	C	"	1	
1141	Type 1141 ...	25K	10	2	2 1/8	Side Wires	Non-insulated	C	"	5	
10413	Type 383 ...	25K	10	3	2 1/8	Side Wires	Non-insulated	C	"	2	
1385	Type 1385 ...	25K	15	2	2 1/8	Side Wires	Non-insulated	C	"	1	
6846	Type 6846 ...	25K	20	1	1 1/8	Side Wires	Non-insulated	C	"	5	
527	Type 798 ...	27K	2	1	1 1/8	Side Wires	Non-insulated	C	"	5	
994	Type 994 ...	27K	2	1	1 1/8	Axial Wires	Ceramic Ins.	C	"	5	
10542	Type 3442 ...	27K	5	1	1 1/8	Side Wires	Non-insulated	C	"	5	
15353	Type 4062 ...	27K	10	1	1 1/8	Side Wires	Non-insulated	C	"	5	
7676	Type 7676 ...	27K	20	1	1 1/8	Axial Wires	Ceramic Ins.	C	"	5	
7693	Type 7693 ...	27K	20	1	1 1/8	Side Wires	Non-insulated	C	"	5	
116	Type 584 ...	30K	1	1	1 1/8	Side Wires	Non-insulated	C	"	10	
11492	Type 485 ...	30K	10	1	1 1/8	Side Wires	Non-insulated	C	"	10	
1189	Type 1189 ...	30K	10	1	1 1/8	Axial Wires	Ceramic Ins.	C	"	5	

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Connection	Insulated or Non-insulated	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Body Length inches	Overall Diameter inches					
1	2	3	4	5	6	7	8	9	10	11	12
	RESISTORS—cont.										
	Fixed—cont.										
	Carbon rod—cont.										
	3 watt and under—cont.										
9621	Type 268 ...	30K	10	2	2 1/16	1 1/16	Side Wires	Non-insulated	C	each	5
10414	Type 384 ...	30K	10	3	2 3/16	1 1/16	Side Wires	Non-insulated	C	"	2
6022	Type 6022 ...	30K	15	1	1 1/4	1 1/16	—	Carbon Rod in Ceramic Tube with Capped Ends	C	"	5
10680	Type 3518 ...	30K	20	1 1/2	1 1/8	1 1/8	Axial Wires	Ceramic Ins.	C	"	10
7273	Type 7273 ...	30K	20	1 1/2	1 1/8	1 1/8	Axial Wires	Ceramic Ins.	C	"	5
9306	Type 244 ...	30K	20	1	1 1/8	1 1/8	Side Wires	Non-insulated	C	"	5
16079	Type 4735 ...	33K	10	1 1/10	—	—	—	Carbon Rod in Ceramic Tube with Capped Ends	C	"	10
7994	Type 7994 ...	33K	10	2	2	1 3/8	—	—	C	"	5
15016	Type 375 ...	33K	20	1 1/2	—	—	Axial Wires	Ceramic Ins.	C	"	5
6245	Type 6245 ...	35K	10	1	7/8	1 1/8	Side Wires	Non-insulated	C	"	5
10306	Type 3270 ...	39K	10	1	1 1/8	1 1/8	Axial Wires	Non-insulated	C	"	10
855	Type 936 ...	40K	2	1	1 1/8	1 1/8	Axial Wires	Ceramic Ins.	C	"	10
1706	Type 1706 ...	40K	10	1	1 1/8	1 1/8	Side Wires	Non-insulated	C	"	10
117	Type 585 ...	40K	10	1	1 1/8	1 1/8	Axial Wires	Ceramic Ins.	C	"	10
11686	Type 520 ...	40K	10	1	1 1/8	1 1/8	Axial Wires	Ceramic Ins.	C	"	10
7601	Type 71 ...	40K	10	1	1 1/8	1 1/8	Side Wires	Non-insulated	C	"	5
160	Type 628 ...	40K	10	2	2 1/16	1 1/8	Side Wires	Non-insulated	C	"	5
9350	Type 250 ...	40K	10	3	2 9/16	1 1/8	Side Wires	Non-insulated	C	"	2
7914	Type 98 ...	45K	10	1	1 1/8	1 1/8	Side Wires	Non-insulated	C	"	5
9284	Type 2611 ...	47K	5	1	1 1/8	1 1/8	Side Wires	Non-insulated	C	"	10
6434	Type 6434 ...	47K	10	1	1 1/8	1 1/8	Side Wires	Non-insulated	C	"	10
15340	Type 4049 ...	47K	20	1	1 1/8	1 1/8	Side Wires	Non-insulated	C	"	10
8143	Type 8143 ...	47K	20	1 1/10	1 1/8	1 1/8	Side Wires	Carbon Semi-ins.	C	"	5

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Connection	Insulated or Non-insulated	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Body Length inches	Overall Diameter inches					
1	2	3	4	5	6	7	8	9	10	11	12
	RESISTORS—cont.										
	Fixed—cont.										
	Carbon rod—cont.										
	3 watt and under—cont.										
6242	Type 6242	50K	2	$\frac{1}{2}$	$\frac{7}{8}$	$\frac{1}{4}$	Axial Wires	Ceramic Ins.	C	each	5
6185	Type 6185	50K	5	$\frac{1}{2}$	$\frac{7}{8}$	$\frac{1}{4}$	Axial Wires	Ceramic Ins.	C	"	5
7829	Type 7829	50K	5	$\frac{1}{2}$	$\frac{7}{8}$	$\frac{1}{4}$	Axial Wires	Ceramic Ins.	C	"	10
6163	Type 6163	50K	5	$\frac{1}{2}$	$\frac{7}{8}$	$\frac{1}{4}$	—	—	C	"	5
6390	Type 6390	50K	5	$\frac{1}{2}$	$\frac{1 \frac{1}{8}}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	"	5
1821	Type 1821	50K	5	$\frac{1}{2}$	$\frac{1 \frac{1}{8}}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	"	5
1453	Type 1453	50K	10	$\frac{1}{2}$	$\frac{1 \frac{1}{8}}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	"	10
11381	Type 477	50K	10	$\frac{1}{2}$	$\frac{7}{8}$	$\frac{1}{4}$	Side Wires	Ceramic Ins.	C	"	10
11687	Type 521	50K	10	$\frac{1}{2}$	$\frac{7}{8}$	$\frac{1}{4}$	Axial Wires	Ceramic Ins.	C	"	5
9634	Type 272	50K	10	$\frac{1}{2}$	$\frac{1 \frac{1}{8}}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	"	5
161	Type 629	50K	10	$\frac{1}{2}$	$\frac{1 \frac{1}{8}}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	"	5
10698	Type 420	50K	10	$\frac{1}{2}$	$\frac{1 \frac{1}{8}}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	"	2
6507	Type 6507	50K	10	$\frac{1}{2}$	$\frac{1 \frac{1}{8}}$	$\frac{3}{8}$	Side Wires	—	C	"	1
6005	Type 6005	50K	15	$\frac{1}{2}$	$\frac{1 \frac{1}{8}}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	"	10
6221	Type 6221	50K	15	$\frac{1}{2}$	$\frac{1 \frac{1}{8}}$	$\frac{3}{8}$	Side Wires	Non-insulated	C	"	5
1974	Type 1974	50K	15	2	2	$\frac{13}{16}$	—	Carbon Rod in Ceramic Tube with Capped Ends	C	"	5
6056	Type 6056	50K	15	3	$2 \frac{1}{2}$	$\frac{3}{4}$	—	Carbon Rod in Ceramic Tube with Capped Ends	C	"	2
5138	Type 2490	51K	5	$\frac{1}{16}$	$\frac{7}{16}$	$\frac{7}{32}$	Side Wires	Non-insulated	C	"	10
52	Type 560	56K	—	$\frac{1}{8}$	$\frac{1}{8}$	$\frac{5}{32}$	—	Carbon Semi-ins.	C	"	5
15361	Type 4070	56K	10	$\frac{1}{8}$	$\frac{1}{8}$	$\frac{5}{32}$	—	Carbon Semi-ins.	C	"	5
10874	Type 3623	56K	20	$\frac{1}{8}$	$\frac{1}{8}$	$\frac{5}{32}$	—	Carbon Semi-ins.	C	"	5
1245	Type 1245	60K	1	$\frac{1}{4}$	$\frac{11}{16}$	$\frac{13}{32}$	Side Wires	Non-insulated	C	"	10

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Connection	Insulated or Non-insulated	Class of Store	Denom. of Qty.	Carton Unit Qty.	
					Body Length inches	Overall Diameter inches						
1	2	3	4	5	6	7	8	9	10	11	12	
	RESISTORS—cont.											
	Fixed—cont.											
	Carbon rod—cont.											
	3 watt and under—cont.											
1822	Type 1822	60K	5	2	2 1/8	1 1/8	Side Wires	Non-insulated	C	each	5	
118	Type 586	60K	10	1 1/2	1 1/8	1 1/8	Axial Wires	Ceramic Ins.	C	"	10	
11688	Type 522	60K	10	1 1/2	1 1/8	1 1/8	Axial Wires	Ceramic Ins.	C	"	5	
7393	Type 59	60K	10	1	1 1/8	1 1/8	Side Wires	Non-insulated	C	"	5	
296	Type 722	60K	10	3	2 1/8	1 1/8	Side Wires	Non-insulated	C	"	5	
1209	Type 1209	65K	10	1 1/2	1 1/8	1 1/8	Side Wires	Non-insulated	C	"	5	
6160	Type 6160	65K	10	1	1 1/8	1 1/8	Side Wires	Non-insulated	C	"	5	
10383	Type 3334	68K	20	1 1/2	1 1/8	1 1/8	—	—	C	"	—	
15015	Type 3724	68K	20	1 1/2	1 1/8	1 1/8	—	—	C	"	5	
11380	Type 476	70K	10	1 1/2	1 1/8	1 1/8	Axial Wires	Ceramic Ins.	C	"	10	
11689	Type 523	70K	10	1 1/2	1 1/8	1 1/8	Axial Wires	Ceramic Ins.	C	"	5	
297	Type 723	70K	10	3	2 1/8	1 1/8	Side Wires	Non-insulated	C	"	2	
7189	Type 7189	75K	10	1 1/2	1 1/8	1 1/8	Axial Wires	Ceramic Ins.	C	"	5	
7398	Type 7398	75K	10	1 1/2	1 1/8	1 1/8	Side Wires	Non-insulated	C	"	5	
10160	Type 372	80K	2	1	1 1/8	1 1/8	Side Wires	Non-insulated	C	"	5	
6186	Type 6186	80K	5	1 1/2	1 1/8	1 1/8	Side Wires	Non-insulated	C	"	10	
7431	Type 7431	80K	10	1 1/2	1 1/8	1 1/8	Axial Wires	—	C	"	10	
11690	Type 524	80K	10	1 1/2	1 1/8	1 1/8	Axial Wires	Ceramic Ins.	C	"	5	
6166	Type 6166	80K	10	1 1/2	1 1/8	1 1/8	Side Wires	Non-insulated	C	"	5	
126	Type 594	90K	10	2	2 1/8	1 1/8	Axial Wires	Non-insulated	C	"	5	
9119	Type 2474	91K	5	1 1/2	1 1/8	1 1/8	Side Wires	Non-insulated	C	"	5	
9761	Type 282	100K	2	1 1/2	1 1/8	1 1/8	Side Wires	Non-insulated	C	"	5	
840	Type 932	100K	2	2	2 1/8	1 1/8	Side Wires	Non-insulated	C	"	5	
6662	Type 6662	100K	10	2	2 1/8	1 1/8	Side Wires	Non-insulated	C	"	10	
6011	Type 6011	100K	15	1 1/2	1 1/8	1 1/8	Side Wires	—	C	"	5	
8197	Type 8197	100K	20	1 1/2	1 1/8	1 1/8	Side Wires	Non-insulated	C	"	10	
127	Type 595	115K	10	1 1/2	1 1/8	1 1/8	Axial Wires	Ceramic Ins.	C	"	5	

SECTION 10W—cont.

RADIO RESISTORS

1	2	3	4	5	6		7	8	9	10	11	12
					Value in Ohms	Tolerance + or - %						
Ref. No.	NOMENCLATURE					Body Length Inches	Overall Diameter Inches					
	RESISTORS—cont.											
	Fixed—cont.											
	Carbon rod—cont.											
	3 watt and under—cont.											
1513	Type 1513 ...	125K	10	$\frac{1}{2}$	$\frac{11}{16}$	$\frac{3}{16}$	Side Wires	Non-insulated	C	each	10	
1748	Type 1748 ...	125K	10	$\frac{2}{3}$	$\frac{2}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5	
6477	Type 6477 ...	130K	3	$\frac{2}{3}$	$\frac{2}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5	
7401	Type 7401 ...	140K	10	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	10	
6436	Type 6436 ...	150K	10	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	10	
8686	Type 2160 ...	150K	20	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	10	
9668	Type 2900 ...	150K	20	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	10	
1035	Type 1035 ...	175K	1	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Axial Wires	Ceramic Ins.	C	"	5	
1632	Type 1632 ...	200K	2	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Axial Wires	Ceramic Ins.	C	"	10	
11673	Type 507 ...	200K	10	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Axial Wires	Ceramic Ins.	C	"	10	
11692	Type 526 ...	200K	10	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Axial Wires	Ceramic Ins.	C	"	5	
7603	Type 73 ...	200K	10	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5	
1187	Type 1187 ...	200K	10	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5	
6418	Type 6418 ...	200K	10	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5	
6713	Type 6713 ...	200K	10	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5	
8156	Type 8156 ...	220K	20	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5	
15356	Type 8156 ...	220K	20	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5	
9954	Type 4065 ...	220K	10	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Side Wires	Carbon Semi-ins.	C	"	2	
15018	Type 3110 ...	220K	10	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	10	
15350	Type 3727 ...	220K	20	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Side Wires	Carbon Semi-ins.	C	"	5	
1716	Type 4059 ...	220K	20	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	10	
1116	Type 1716 ...	250K	2 $\frac{1}{2}$	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	10	
8091	Type 1116 ...	250K	5	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Axial Wires	Ceramic Ins.	C	"	10	
6171	Type 8091 ...	250K	5	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Axial Wires	Ceramic Ins.	C	"	10	
1295	Type 6171 ...	250K	5	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Axial Wires	Ceramic Ins.	C	"	10	
6871	Type 1295 ...	250K	10	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	5	
11383	Type 6871 ...	250K	10	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Side Wires	Non-insulated	C	"	10	
	Type 479 ...	250K	10	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{1}{16}$	Axial Wires	Ceramic Ins.	C	"	10	

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Connection	Insulated or Non-insulated	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Body Length inches	Overall Diameter inches					
1	RESISTORS—cont. Fixed—cont. Carbon rod—cont. 3 watt and under—cont.										
11477	Type 553	250K	10	$\frac{1}{2}$	$\frac{7}{16}$	AXIAL WIRES	Ceramic Ins.	C	each	5	
7267	Type 29	250K	10	$\frac{1}{2}$	$\frac{11}{16}$	Side Wires	Non-insulated	C	"	5	
162	Type 630	250K	10	2	$\frac{11}{16}$	Side Wires	Non-insulated	C	"	5	
7882	Type 7882	250K	10	3	$\frac{2}{8}$	Side Wires	Non-insulated	C	"	2	
1883	Type 1883	250K	20	$\frac{1}{2}$	$\frac{7}{16}$	Axial Wires	Ceramic Ins.	C	"	10	
6841	Type 6841	250K	20	$\frac{1}{2}$	$\frac{7}{16}$	Axial Wires	Ceramic Ins.	C	"	5	
8653	Type 2151	270K	10	$\frac{1}{2}$	$\frac{7}{16}$	Side Wires	Non-insulated	C	"	10	
10880	Type 3624	270K	20	$\frac{1}{2}$	$\frac{7}{16}$	Side Wires	Non-insulated	C	"	5	
1532	Type 1532	280K	5	1	$\frac{11}{16}$	Side Wires	Non-insulated	C	"	5	
6880	Type 6880	280K	5	1	$\frac{11}{16}$	Side Wires	Carbon Rod in Ceramic Tube with Capped Ends	C	"	5	
1023	Type 1023	300K	10	$\frac{1}{2}$	$\frac{7}{16}$	Axial Wires	Ceramic Ins.	C	"	10	
128	Type 596	300K	10	$\frac{1}{2}$	$\frac{7}{16}$	Axial Wires	Ceramic Ins.	C	"	5	
7075	Type 7075	300K	10	1	$\frac{11}{16}$	Side Wires	Non-insulated	C	"	5	
1102	Type 1102	300K	10	3	$\frac{2}{8}$	Side Wires	Non-insulated	C	"	2	
7715	Type 7715	300K	15	$\frac{1}{2}$	$\frac{7}{16}$	Axial Wires	Ceramic Ins.	C	"	5	
15270	Type 3979	350K	5	$\frac{1}{2}$	$\frac{7}{16}$	Axial Wires	Ceramic Ins.	C	"	5	
1402	Type 1402	350K	10	1	$\frac{11}{16}$	Side Wires	Non-insulated	C	"	5	
7823	Type 7823	350K	20	1	$\frac{11}{16}$	Side Wires	Ceramic Ins.	C	"	5	
1917	Type 1917	375K	2	1	$\frac{11}{16}$	Axial Wires	Carbon Rod in Ceramic Tube with Capped Ends	C	"	5	
600	Type 834	375K	15	1	$\frac{11}{16}$	Side Wires	Non-insulated	C	"	5	
9279	Type 2606	390K	5	$\frac{1}{2}$	$\frac{7}{16}$	Side Wires	Non-insulated	C	"	5	
7002	Type 7002	400K	5	$\frac{1}{2}$	$\frac{7}{16}$	Side Wires	Non-insulated	C	"	10	
7191	Type 7191	400K	10	$\frac{1}{2}$	$\frac{7}{16}$	Axial Wires	Ceramic Ins.	C	"	5	

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Connection	Insulated or Non-insulated	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Body Length Inches	Overall Diameter Inches					
1	2	3	4	5	6	7	8	9	10	11	12
	RESISTORS—cont.										
	Fixed—cont.										
	Carbon rod—cont.										
	3 watt and under—cont.										
7965	Type 7965 ...	400K	20	$\frac{1}{4}$	$\frac{5}{16}$ $1\frac{11}{16}$	$\frac{7}{16}$ $\frac{7}{16}$	Axial Wires Side Wires	Ceramic Ins. Non-insulated	C C	each "	10 5
9599	Type 2850 ...	430K	5	1	$1\frac{1}{2}$	$\frac{1}{8}$ $\frac{1}{8}$	—	Carbon Rod in Ceramic Tube with Capped Ends	C	"	5
6039	Type 6039 ...	470K	2	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{1}{8}$ $\frac{1}{8}$			C	"	5
9747	Type 2968 ...	470K	5	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{7}{16}$ $\frac{7}{16}$	Side Wires	Non-insulated	C	"	10
6437	Type 6437 ...	470K	10	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{7}{16}$ $\frac{7}{16}$	Side Wires	Non-insulated	C	"	10
8678	Type 2156 ...	470K	20	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{7}{16}$ $\frac{7}{16}$	Side Wires	Non-insulated	C	"	10
1059	Type 1059 ...	500K	2	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{7}{16}$ $\frac{7}{16}$	Axial Wires	Ceramic Ins.	C	"	5
1886	Type 1886 ...	500K	5	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{7}{16}$ $\frac{7}{16}$	Axial Wires	Ceramic Ins.	C	"	5
6085	Type 6085 ...	500K	5	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{7}{16}$ $\frac{7}{16}$	Axial Wires	Ceramic Ins.	C	"	10
1831	Type 1831 ...	500K	5	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{7}{16}$ $\frac{7}{16}$	Side Wires	Non-insulated	C	"	5
8870	Type 6870 ...	500K	10	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{7}{16}$ $\frac{7}{16}$	Side Wires	Non-insulated	C	"	10
1674	Type 508 ...	500K	10	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{7}{16}$ $\frac{7}{16}$	Axial Wires	Ceramic Ins.	C	"	10
129	Type 597 ...	500K	10	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{7}{16}$ $\frac{7}{16}$	Axial Wires	Ceramic Ins.	C	"	5
7602	Type 72 ...	500K	10	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{7}{16}$ $\frac{7}{16}$	Axial Wires	Ceramic Ins.	C	"	5
458	Type 776 ...	500K	10	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{7}{16}$ $\frac{7}{16}$	Side Wires	Non-insulated	C	"	5
6212	Type 6212 ...	500K	10	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{7}{16}$ $\frac{7}{16}$	Side Wires	Non-insulated	C	"	5
1885	Type 1885 ...	500K	20	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{7}{16}$ $\frac{7}{16}$	Side Wires	Non-insulated	C	"	2
7822	Type 7822 ...	500K	20	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{7}{16}$ $\frac{7}{16}$	Axial Wires	Ceramic Ins.	C	"	10
10711	Type 3539 ...	510K	10	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{7}{16}$ $\frac{7}{16}$	Axial Wires	Ceramic Ins.	C	"	5
5745	Type 4437 ...	510K	10	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{7}{16}$ $\frac{7}{16}$	Side Wires	Non-insulated	C	"	5
9643	Type 2876 ...	560K	5	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{7}{16}$ $\frac{7}{16}$	Axial Wires	Insulated	C	"	5
5752	Type 4442 ...	560K	10	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{7}{16}$ $\frac{7}{16}$	Side Wires	Ceramic Ins.	C	"	5
1671	Type 1671 ...	600K	5	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{7}{16}$ $\frac{7}{16}$	Side Wires	Non-insulated	C	"	10
7403	Type 7403 ...	600K	10	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{7}{16}$ $\frac{7}{16}$	—	—	C	"	5
11675	Type 509 ...	750K	10	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{7}{16}$ $\frac{7}{16}$	Axial Wires	Ceramic Ins.	C	"	10

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Connection	Insulated or Non-insulated	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Body Length inches	Overall Diameter inches					
1	2	3	4	5	6	7	8	9	10	11	12
	RESISTORS—cont.										
	Fixed—cont.										
	Carbon rod—cont.										
	3 watt and under—cont.										
9644	Type 274 ...	750K	10	1	1 13/16	3/8	Side Wires	Non-insulated	C	each	1
1169	Type 1169 ...	750K	10	2	2 1/8	1/2	Side Wires	Non-insulated	C	"	5
7003	Type 7003 ...	800K	5	1 2	1 1/8	3/16	Side Wires	Non-insulated	C	"	5
9759	Type 280 ...	1M	2	1 1/2	1 1/8	3/16	Side Wires	Non-insulated	C	"	10
6441	Type 6441 ...	1M	10	1 1/2	1 1/8	3/16	Side Wires	Non-insulated	C	"	10
8961	Type 2354 ...	1M	20	1 1/2	1 1/8	3/16	Side Wires	Non-insulated	C	"	5
1210	Type 1210 ...	1.1M	20	1 1/2	1 1/8	3/16	Side Wires	Non-insulated	C	"	5
7004	Type 7004 ...	1.6M	5	1 1/2	1 1/8	3/16	Side Wires	Non-insulated	C	"	10
7166	Type 7166 ...	1.8M	20	1 1/2	1 1/8	3/16	Axial Wires	Ceramic Ins.	C	"	10
11385	Type 481 ...	2M	10	1 1/2	1 1/8	3/16	Axial Wires	Ceramic Ins.	C	"	5
131	Type 599 ...	2M	10	1 1/2	1 1/8	3/16	Axial Wires	Non-insulated	C	"	5
153	Type 621 ...	2M	10	1 1/2	1 1/8	3/16	Side Wires	Non-insulated	C	"	5
463	Type 781 ...	2M	10	1 1/2	1 1/8	3/16	Side Wires	Non-insulated	C	"	5
7669	Type 7669 ...	2M	20	1 1/2	1 1/8	3/16	Axial Wires	Ceramic Ins.	C	"	5
1684	Type 1684 ...	2.1M	10	1 1/2	1 1/8	3/16	Side Wires	Non-insulated	C	"	5
6440	Type 6440 ...	2.2M	10	1 1/2	1 1/8	3/16	Side Wires	Non-insulated	C	"	10
8683	Type 2157 ...	2.2M	20	1 1/2	1 1/8	3/16	Side Wires	Non-insulated	C	"	10
15360	Type 4069 ...	2.2M	20	1 1/2	1 1/8	3/16	Side Wires	Non-insulated	C	"	5
7148	Type 7148 ...	2.5M	5	1 1/2	1 1/8	3/16	—	Carbon Semi-ins.	C	"	5
15227	Type 3936 ...	2.5M	5	1 1/2	1 1/8	3/16	—	Insulated	C	"	5
7690	Type 7690 ...	3M	10	1 1/2	1 1/8	3/16	Axial Wires	Ceramic Ins.	C	"	5
6907	Type 6907 ...	3M	1	1 1/2	1 1/8	3/16	Side Wires	Non-insulated	C	"	5
132	Type 600 ...	3M	1	1 1/2	1 1/8	3/16	Axial Wires	Non-insulated	C	"	5
460	Type 778 ...	3M	10	1 1/2	1 1/8	3/16	Side Wires	Non-insulated	C	"	5
7222	Type 7222 ...	3M	20	1 1/2	1 1/8	3/16	Axial Wires	Ceramic Ins.	C	"	10
11677	Type 511 ...	4M	10	1 1/2	1 1/8	3/16	Axial Wires	Ceramic Ins.	C	"	10
8913	Type 2323 ...	4.7M	20	1 1/2	1 1/8	3/16	Side Wires	Non-insulated	C	"	10

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Connection	Insulated or Non-insulated	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Body Length inches	Overall Diameter inches					
1	2	3	4	5	6	7	8	9	10	11	12
	RESISTORS—cont. Fixed—cont. Carbon rod—cont. 3 watt and under—cont.										
16858	Type 5368 ...	4.7M	20	1	1 1/8	1 1/8	—	—	C	each	1
7147	Type 7147 ...	5M	5	1	1 1/8	1 1/8	Side Wires	Non-insulated	C	"	10
7480	Type 7480 ...	5M	5	1	1 1/8	1 1/8	Axial Wires	Ceramic Ins.	C	"	5
6459	Type 6459 ...	5M	10	1	1 1/8	1 1/8	Axial Wires	Ceramic Ins.	C	"	10
1722	Type 1722 ...	5M	10	1	1 1/8	1 1/8	Side Wires	Non-insulated	C	"	6
8607	Type 153 ...	5M	10	1	1 1/8	1 1/8	Side Wires	Non-insulated	C	"	5
6607	Type 6607 ...	5M	20	1	1 1/8	1 1/8	Side Wires	Non-insulated	C	"	5
8093	Type 8093 ...	6M	20	1	1 1/8	1 1/8	Axial Wires	Ceramic Ins.	C	"	10
1511	Type 1511 ...	6M	20	1	1 1/8	1 1/8	Side Wires	Non-insulated	C	"	5
1211	Type 1211 ...	50M	10	1	1 1/8	1 1/8	Side Wires	Non-insulated	C	"	5
15209	Type 3918 ...	50M	10	2	2 1/8	2 1/8	—	Non-insulated	C	"	5
8888	Type 2308 ...	50M	20	3	2 1/8	2 1/8	Side Wires	Non-insulated	C	"	2
1113	Type 1113 ...	100M	10	3	2 1/8	2 1/8	Side Wires	Non-insulated	C	"	2
456	Type 774 ...	500M	10	2	2 1/8	2 1/8	Side Wires	Non-insulated	C	"	5

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Class of Store	Denom. of Qty.	Carton Unit Qty.	
					Length (inches)	Diameter (inches)				
1	2	3	4	5	6	7	8	9	10	
	RESISTORS—cont. Fixed—cont. Carbon rod—cont. High stability type, with capped ends and wire leads, non-insulated:—									
7127	Type 7127 ...	0.42	2	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{3}{8}$	C	each	5	
6968	Type 6968 ...	0.8	1	1	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	10	
15736	Type 4434 ...	40	2	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	5	
6690	Type 6690 ...	40	5	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	5	
7292	Type 7292 ...	50	2	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	5	
7302	Type 7302 ...	50	5	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	5	
6918	Type 6918 ...	50	5	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	5	
15026	Type 3735 ...	62	2	1	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	5	
13735	Type 4429 ...	100	1	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	5	
7529	Type 7529 ...	100	1	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	5	
15734	Type 4428 ...	110	1	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	10	
7107	Type 7107 ...	120	1	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	5	
7287	Type 7287 ...	200	2	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	5	
7526	Type 7526 ...	250	1	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	5	
8562	Type 8562 ...	250	2	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	5	
15240	Type 3949 ...	250	5	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	5	
17706	Type 5151 ...	470	1	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	5	
7060	Type 7060 ...	500	2	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	5	
7522	Type 7522 ...	500	5	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	5	
6681	Type 6681 ...	500	5	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	5	
7049	Type 7049 ...	520	2	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	5	
8264	Type 8264 ...	600	5	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	5	
6753	Type 6573 ...	700	2	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	10	
6612	Type 6612 ...	700	5	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	5	
10561	Type 3448 ...	820	5	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	5	
15732	Type 4426 ...	900	1	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{1}{16}$	C	"	10	

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Class of Store	Denom of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)			
1	2	3	4	5	6	7	8	9	10
	RESISTORS—cont.								
	Fixed—cont.								
	Carbon rod—cont.								
	High stability type, with capped ends and wire leads, non-insulated:—cont.								
15733	Type 4427 ...	900	1	2	—	—	C	each	5
7105	Type 7105 ...	1K	1	1	$1\frac{3}{4}$	$\frac{3}{16}$	C	"	5
6379	Type 6379 ...	1K	3	1	$1\frac{3}{8}$	$\frac{1}{16}$	C	"	5
7101	Type 7101 ...	1.4K	2	1	$1\frac{1}{2}$	$\frac{1}{16}$	C	"	5
7528	Type 7528 ...	2.3K	5	1	$1\frac{1}{2}$	$\frac{1}{16}$	C	"	5
6738	Type 6738 ...	3K	2	1	$1\frac{1}{2}$	$\frac{1}{16}$	C	"	5
7062	Type 7062 ...	3.5K	2	1	$1\frac{1}{2}$	$\frac{1}{16}$	C	"	10
15335	Type 4044 ...	3.5K	5	1	$1\frac{3}{8}$	$\frac{1}{16}$	C	"	5
6806	Type 6806 ...	4K	1	1	$1\frac{3}{8}$	$\frac{1}{16}$	C	"	5
7059	Type 7059 ...	4K	2	1	$1\frac{3}{8}$	$\frac{1}{16}$	C	"	5
6666	Type 6666 ...	4.7K	5	1	$1\frac{3}{8}$	$\frac{1}{16}$	C	"	5
15849	Type 4532 ...	4.7K	5	1	—	—	C	"	5
9080	Type 2440 ...	5K	2	1	—	—	C	"	5
6609	Type 6609 ...	5K	5	1	—	—	C	"	5
7051	Type 7051 ...	6K	2	1	$1\frac{3}{8}$	$\frac{1}{16}$	C	"	5
7124	Type 7124 ...	6K	2	1	$1\frac{3}{8}$	$\frac{1}{16}$	C	"	5
17682	Type 9127 ...	6-2K	1	1	$1\frac{3}{8}$	$\frac{1}{16}$	C	"	5
7117	Type 7117 ...	8K	2	1	$1\frac{3}{8}$	$\frac{1}{16}$	C	"	5
6667	Type 6667 ...	8K	2	1	$1\frac{3}{8}$	$\frac{1}{16}$	C	"	5
7271	Type 7271 ...	9K	5	1	$1\frac{3}{8}$	$\frac{1}{16}$	C	"	5
6721	Type 6721 ...	10K	1	1	$1\frac{3}{8}$	$\frac{1}{16}$	C	"	10
6373	Type 6373 ...	10K	3	1	$1\frac{3}{8}$	$\frac{1}{16}$	C	"	5
15087	Type 3796 ...	10K	10	1	$1\frac{3}{8}$	$\frac{1}{16}$	C	"	5
15349	Type 4058 ...	15K	5	1	$1\frac{3}{8}$	$\frac{1}{16}$	C	"	5
16219	Type 4846 ...	15K	10	1	—	—	C	"	10
15368	Type 4077 ...	15K	10	1	—	—	C	"	5

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Class of Store	Denom of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)			
1	2	3	4	5	6	7	8	9	10
<p>RESISTORS—cont. Fixed—cont. Carbon rod—cont. High stability type, with capped ends and wire leads, non-insulated—cont.</p>									
6371	Type 6371 ...	—	3	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	each	5
16123	Type 4771 ...	222K	5	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	5
15655	Type 4351 ...	222K	5	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	5
7064	Type 7064 ...	—	2	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	5
9063	Type 2425 ...	—	1	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	5
6756	Type 6756 ...	—	2	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	5
6374	Type 6374 ...	—	3	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	5
6593	Type 6593 ...	—	5	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	5
16220	Type 4847 ...	25K	5	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	5
9062	Type 2424 ...	—	1	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	5
9071	Type 2433 ...	—	2	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	5
16041	Type 4709 ...	35K	5	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	5
9648	Type 2880 ...	—	5	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	5
7572	Type 7572 ...	—	1	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	5
6590	Type 6590 ...	40K	1	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	5
7057	Type 7057 ...	40K	2	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	5
6377	Type 6377 ...	40K	3	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	5
16112	Type 4761 ...	40K	5	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	10
7272	Type 7272 ...	40K	5	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	5
7116	Type 7116 ...	40K	5	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	5
16612	Type 5172 ...	47K	5	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	10
7530	Type 7530 ...	50K	1	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	5
9245	Type 2572 ...	50K	1	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	5
6614	Type 6614 ...	50K	1	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	5
6617	Type 6617 ...	50K	2	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	5
6808	Type 6808 ...	50K	2	1	$1\frac{3}{32}$	$\frac{1}{16}$	C	"	5

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)			
1									
	RESISTORS—cont. Fixed—cont. Carbon rod—cont. High stability type, with capped ends and wire leads, non-insulated—cont.								
6729	Type 6729 ...	50K	5	1/2	1 3/32	1/16	C	each	10
9619	Type 2864 ...	55K	2	1/2	1 9/32	1/16	C	"	5
7141	Type 7141 ...	60K	1	1/2	1 9/32	1/16	C	"	5
6380	Type 6380 ...	60K	3	1/2	1 9/32	1/16	C	"	5
16042	Type 4710 ...	60K	5	1	1 3/8	3/16	C	"	5
6610	Type 6610 ...	60K	5	1	1 3/8	3/16	C	"	5
16114	Type 4763 ...	68K	5	1	1 3/8	3/16	C	"	5
16043	Type 4711 ...	70K	5	1	1 3/8	3/16	C	"	5
6805	Type 6805 ...	70K	5	1	1 3/8	3/16	C	"	5
7126	Type 7126 ...	80K	5	1	1 3/8	3/16	C	"	5
7043	Type 7043 ...	85K	2	1	1 3/8	3/16	C	"	5
15241	Type 3950 ...	90K	5	1	1 3/8	3/16	C	"	10
16408	Type 4989 ...	90K	5	1	1 3/8	3/16	C	"	5
6744	Type 6744 ...	100K	1	1	1 3/8	3/16	C	"	10
8428	Type 8428 ...	100K	10	1	1 3/8	3/16	C	"	5
9277	Type 2604 ...	130K	1	1	1 3/8	3/16	C	"	5
6720	Type 6720 ...	150K	1	1	1 3/8	3/16	C	"	5
15845	Type 4528 ...	180K	1	1	1 3/8	3/16	C	"	5
8851	Type 2280 ...	200K	1	1	1 3/8	3/16	C	"	5
15710	Type 4405 ...	220K	10	1	1 3/8	3/16	C	"	5
16045	Type 4713 ...	230K	5	1	1 3/8	3/16	C	"	5
8342	Type 8342 ...	250K	1	1	1 3/8	3/16	C	"	5
7285	Type 7285 ...	250K	2	1	1 3/8	3/16	C	"	5
9078	Type 2438 ...	250K	1	1	1 3/8	3/16	C	"	5
7282	Type 7282 ...	250K	2	1	1 3/8	3/16	C	"	5
6597	Type 6957 ...	250K	5	1	1 3/8	3/16	C	"	5

SECTION 10W—cont.

RADIO RESISTORS

Ref. No	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Class of Store	Denom of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)			
1	2	3	4	5	6	7	8	9	10
9276	Type 2603 ...	250K	5	1 1/2	1 3/4	3/8	C	each	5
16206	Type 4834 ...	260K	5	1	1 3/8	1/8	C	"	5
16519	Type 5089 ...	270K	2	1	1 3/8	1/8	C	"	5
9649	Type 2881 ...	300K	2	1	1 3/8	1/8	C	"	5
15372	Type 4081 ...	300K	10	1	1 3/8	1/8	C	"	5
6758	Type 6758 ...	350K	1	1	1 3/8	1/8	C	"	5
6800	Type 6800 ...	350K	2	1	1 3/8	1/8	C	"	5
7048	Type 7048 ...	400K	1	1	1 3/8	1/8	C	"	5
16550	Type 5120 ...	400K	2	1	1 3/8	1/8	C	"	5
9065	Type 2427 ...	400K	5	1	1 3/8	1/8	C	"	5
9068	Type 2430 ...	450K	2	1	1 3/8	1/8	C	"	5
6635	Type 6635 ...	450K	5	1	1 3/8	1/8	C	"	5
6589	Type 6589 ...	500K	2	1	1 3/8	1/8	C	"	5
6754	Type 6754 ...	500K	1	1	1 3/8	1/8	C	"	5
6375	Type 6375 ...	500K	3	1	1 3/8	1/8	C	"	5
7300	Type 7300 ...	500K	5	1	1 3/8	1/8	C	"	5
16516	Type 5086 ...	560K	1	1	1 3/8	1/8	C	"	10
16286	Type 4906 ...	600K	5	1	1 3/8	1/8	C	"	10
6634	Type 6634 ...	600K	5	1	1 3/8	1/8	C	"	5
16064	Type 4720 ...	600K	5	1	1 3/8	1/8	C	"	5
15737	Type 4431 ...	650K	5	1	1 3/8	1/8	C	"	5
16467	Type 5040 ...	750K	2	1	1 3/8	1/8	C	"	10
6759	Type 6759 ...	900K	2	1	1 3/8	1/8	C	"	5
16203	Type 4831 ...	900K	5	1	1 3/8	1/8	C	"	5
9079	Type 2439 ...	1M	1	1	1 3/8	1/8	C	"	10
6591	Type 6591 ...	1M	1	1	1 3/8	1/8	C	"	5

RESISTORS—cont.

Fixed—cont.
Carbon rod—cont.

High stability type,
with capped ends and wire leads, non-insulated—cont.

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)			
1	2	3	4	5	6	7	8	9	10
<p>RESISTORS—cont. Fixed—cont. Carbon rod—cont. High stability type, with capped ends and wire leads, non-insulated—cont.</p>									
6970	Type 6970 ...	1M	1	1	$1\frac{3}{4}$	$\frac{3}{16}$	C	each	5
6723	Type 6723 ...	1M	5	1	$1\frac{3}{32}$	$\frac{3}{16}$	C	"	10
15707	Type 4402 ...	1.1M	2	1	—	—	C	"	5
15706	Type 4401 ...	1.3M	2	1	—	—	C	"	5
16385	Type 4967 ...	1.4M	5	1	—	—	C	"	5
8263	Type 8263 ...	1.5M	1	1	—	—	C	"	5
9878	Type 2908 ...	1.5M	1	1	$1\frac{3}{4}$	$\frac{3}{16}$	C	"	5
9066	Type 2428 ...	1.5M	2	1	$1\frac{3}{32}$	$\frac{3}{16}$	C	"	5
6966	Type 6966 ...	1.6M	1	1	$1\frac{33}{32}$	$\frac{1}{16}$	C	"	5
16040	Type 4708 ...	1.8M	2	1	$1\frac{33}{32}$	$\frac{1}{16}$	C	"	5
9067	Type 2429 ...	2M	2	1	$1\frac{33}{32}$	$\frac{1}{16}$	C	"	5
15164	Type 3873 ...	2M	1	1	—	—	C	"	5
15412	Type 4121 ...	2.2M	2	1	$1\frac{33}{32}$	$\frac{1}{16}$	C	"	5
15373	Type 4082 ...	2.2M	2	1	$1\frac{33}{32}$	$\frac{1}{16}$	C	"	5
15370	Type 4079 ...	2.3M	10	1	$1\frac{33}{32}$	$\frac{1}{16}$	C	"	5
16204	Type 4832 ...	2.3M	5	1	$1\frac{33}{32}$	$\frac{1}{16}$	C	"	5
16677	Type 5201 ...	2.7M	10	1	$1\frac{33}{32}$	$\frac{1}{16}$	C	"	5
7574	Type 7574 ...	3M	1	1	$1\frac{33}{32}$	$\frac{1}{16}$	C	"	5
16287	Type 4908 ...	3M	5	1	$1\frac{33}{32}$	$\frac{1}{16}$	C	"	10
10409	Type 3338 ...	3.3M	20	1	—	—	C	"	5
6811	Type 6811 ...	3M	5	1	$1\frac{3}{4}$	$\frac{3}{8}$	C	"	5
16288	Type 4908 ...	4M	5	1	—	—	C	"	10
16406	Type 4987 ...	4M	5	1	—	—	C	"	5
6683	Type 6683 ...	4M	5	1	$1\frac{3}{4}$	$\frac{3}{8}$	C	"	5
16065	Type 4721 ...	4M	5	2	$1\frac{3}{4}$	$\frac{3}{8}$	C	"	5
15761	Type 4447 ...	4.7M	2	1	$1\frac{3}{4}$	$\frac{3}{8}$	C	"	5

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)			
1									
	RESISTORS—cont. Fixed—cont. Carbon rod—cont. High stability type, with capped ends and wire leads, non-insulated—cont.								
15242	Type 3951 ...	4.7M	5	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{1}{8}$	C	each	10
15371	Type 4080 ...	4.7M	10	$1\frac{1}{2}$	—	—	C	"	5
7301	Type 7301 ...	5M	5	1	—	—	C	"	5
6684	Type 6684 ...	5M	5	1	$1\frac{3}{4}$	$\frac{8}{70}$	C	"	5
16068	Type 4724 ...	5M	5	2	$2\frac{1}{2}$	$\frac{1}{16}$	C	"	5
16205	Type 4833 ...	5.7M	5	2	—	—	C	"	5
16410	Type 4991 ...	6M	2	2	—	—	C	"	5
16386	Type 4968 ...	6M	5	5	—	—	C	"	5
16289	Type 4909 ...	10M	5	5	—	—	C	"	5
16411	Type 4992 ...	12M	2	2	—	—	C	"	10
	Protected, concentric wire ends ($\frac{1}{4}$, $\frac{1}{2}$, and 1 watt):—								
7164	Type 7164 ...	27	20	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{1}{8}$	C	"	10
7175	Type 7175 ...	100	13	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{1}{8}$	C	"	10
7163	Type 7163 ...	180	13	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{1}{8}$	C	"	10
7167	Type 7167 ...	470	20	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{1}{8}$	C	"	10
7169	Type 7169 ...	1.5K	20	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{1}{8}$	C	"	10
7162	Type 7162 ...	2.2K	13	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{1}{8}$	C	"	10
7642	Type 7642 ...	4.7K	10	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{1}{8}$	C	"	10
7165	Type 7165 ...	4.7K	13	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{1}{8}$	C	"	10
7197	Type 7197 ...	4.7K	20	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{1}{8}$	C	"	5
8325	Type 8325 ...	5K	10	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{1}{8}$	C	"	10
7643	Type 7643 ...	10K	10	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{1}{8}$	C	"	10
7651	Type 7651 ...	10K	10	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{1}{8}$	C	"	5
7646	Type 7646 ...	27K	10	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{1}{8}$	C	"	5
7648	Type 7648 ...	27K	10	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{1}{8}$	C	"	5

RADIO RESISTORS

Ref. No	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	MAXIMUM DIMENSIONS		Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)			
1	2	3	4	5	6	7	8	9	10
	RESISTORS—cont.								
	Fixed—cont.								
	Carbon rod—cont.								
	Protected, concentric wire ends ($\frac{1}{2}$, $\frac{1}{4}$, and 1 watt)—cont.								
7650	Type 7650 ...	33K	10	1	$1\frac{13}{32}$	$\frac{13}{32}$	C	each	5
7649	Type 7649 ...	47K	10	1	$1\frac{13}{32}$	$\frac{13}{32}$	C	"	5
8322	Type 8322 ...	50K	10	$\frac{1}{4}$	$\frac{13}{32}$	$\frac{13}{32}$	C	"	10
7161	Type 7161 ...	68K	13	$\frac{1}{4}$	$\frac{13}{32}$	$\frac{13}{32}$	C	"	10
8323	Type 8323 ...	100K	10	$\frac{1}{4}$	$\frac{13}{32}$	$\frac{13}{32}$	C	"	10
7647	Type 7647 ...	100K	10	1	$\frac{13}{32}$	$\frac{13}{32}$	C	"	5
7674	Type 7674 ...	100K	20	$\frac{1}{2}$	$\frac{13}{32}$	$\frac{13}{32}$	C	"	5

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (mm.)	Diameter (mm.)	Bore (mm.)			
1	2	3	4	5	6	7	8	9	10	11
	RESISTORS—cont. Fixed—cont. Carbon rod/tube type, with metallised ends for chip holders:—									
7746	Type 7746	10	10	35	250	25	15	C	each	1
15807	Type 4490	10	15	10	150	18	15	C	"	1
10501	Type 3415	23	15	35	250	25	15	C	"	1
1384	Type 1384*	40	15	2	43	6	—	C	"	1
8688	Type 164	40	15	2	43	6	—	C	"	5
10066	Type 347†	50	15	2	43	6	—	C	"	5
7484	Type 7484	50	15	35	250	25	15	C	"	1
10502	Type 3416	80	15	35	250	25	15	C	"	1
6569	Type 6569	100	15	2	43	6	—	C	"	1
7748	Type 7748	100	15	35	250	25	15	C	"	1
1386	Type 1386	125	15	35	250	25	15	C	"	2
10030	Type 338	150	15	7	100	18	—	C	"	2
10442	Type 3364	150	20	1	—	—	—	C	"	2
6533	Type 6533	200	15	4	70	18	—	C	"	1
15815	Type 4498	200	15	7	200	18	—	C	"	1
6521	Type 6521	200	15	35	250	25	15	C	"	1
9493	Type 2748	220	20	1‡	—	—	—	C	"	—
16729	Type 5249	220	15	35	250	35	15	C	"	—
1715	Type 1715	350	5	1	—	—	—	C	"	5
15816	Type 4499	390	15	35	250	25	15	C	"	1
10503	Type 3417	500	15	35	250	25	15	C	"	1
15814	Type 4497	500	15	10	150	18	—	C	"	1
15114	Type 3823	700	15	20	75	10	—	C	"	2
6513	Type 6513	800	15	25	150	25	15	C	"	1
9414	Type 256	1K	15	2	43	6	—	C	"	5
8470	Type 2023	1K	15	25	150	25	15	C	"	2
6532	Type 6532	1K	15	35	250	25	15	C	"	1

* Special wire ends.

† Screwed ends.

SECTION 10W—cont.

RADIO RESISTORS

Ref. No	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (mm.)	Diameter (mm.)	Bore (mm.)			
1	RESISTORS—cont. Fixed—cont. Carbon rod/tube type, with metallised ends for clip holders—cont.									
10812	Type 3591 ...	1K	20	$\frac{1}{2}$	—	—	—	C	each	1
9415	Type 257 ...	2.5K	15	2	43	6	—	C	"	5
15648	Type 4344 ...	3.3K	5	1	—	—	—	C	"	5
9142	Type 2494 ...	4K	15	4	70	18	—	C	"	2
6550	Type 6550 ...	4K	15	35	250	25	15	C	"	1
10938	Type 3668 ...	5K	15	20	75	10	—	C	"	1
6202	Type 6202 ...	15K	10	1	—	—	—	C	"	5
9219	Type 2547 ...	22K	10	$\frac{1}{4}$	—	—	—	C	"	10
1914	Type 1914 ...	26K	15	35	250	25	15	C	"	1
10427	Type 3350 ...	33K	20	$\frac{1}{4}$	—	—	—	C	"	—
9220	Type 2548 ...	47K	10	$\frac{1}{4}$	—	—	—	C	"	—
9508	Type 2761 ...	47K	20	$\frac{1}{4}$	—	—	—	C	"	10
10096	Type 3143 ...	50K	5	1	—	—	—	C	"	5
10971	Type 3686 ...	68K	20	1	—	—	—	C	"	5
10429	Type 3352 ...	100K	5	1	—	—	—	C	"	10
10969	Type 3684 ...	220K	20	$\frac{1}{4}$	—	—	—	C	"	5
10433	Type 3356 ...	1M	15	35	250	25	15	C	"	5
10962	Type 367 ...	1.5M	20	$\frac{1}{4}$	—	—	—	C	"	—
9667	Type 2899 ...	2M	5	$\frac{1}{2}$	—	—	—	C	"	—
15035	Type 3744 ...									5

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS		Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)			
1									
	RESISTORS—cont.								
	Fixed—cont.								
	Metallised filament,								
	in insulating bakelite tube, with concentric wire ends								
	($\frac{1}{4}$, $\frac{1}{2}$, and 1 watt):—								
10954	Type 3669	4	10	1	—	—	C	each	1
8771	Type 2221	6.2	5	1	—	—	C	"	—
10581	Type 3451	40	10	1	—	—	C	"	—
9213	Type 2541	—	—	1	—	—	C	"	—
342	Type 708	75	15	1	1 $\frac{1}{2}$	—	C	"	5
133	Type 601	200	15	1	1 $\frac{1}{2}$	—	C	"	2
9214	Type 2542	220	10	1	1 $\frac{1}{2}$	—	C	"	5
9421	Type 261	300	15	1	—	—	C	"	—
9503	Type 2758	470	10	1	—	—	C	"	10
8749	Type 2199	470	20	1	1 $\frac{1}{2}$	—	C	"	5
7038	Type 7038	600	20	1	1 $\frac{1}{2}$	—	C	"	5
7867	Type 7867	1K	10	1	1 $\frac{1}{2}$	—	C	"	5
135	Type 603	1K	15	1	1 $\frac{1}{2}$	—	C	"	5
8746	Type 2196	1K	20	1	1 $\frac{1}{2}$	—	C	"	5
10450	Type 3372	1.5K	10	1	1 $\frac{1}{2}$	—	C	"	5
6934	Type 6934	2.0K	15	1	1 $\frac{1}{2}$	—	C	"	5
8738	Type 2188	2.2K	20	1	1 $\frac{1}{2}$	—	C	"	5
137	Type 605	2.5K	15	1	1 $\frac{1}{2}$	—	C	"	5
7806	Type 7806	3K	10	1	1 $\frac{1}{2}$	—	C	"	5
9215	Type 2543	4.7K	10	1	1 $\frac{1}{2}$	—	C	"	10
8737	Type 2187	4.7K	20	1	1 $\frac{1}{2}$	—	C	"	5
6946	Type 6946	5K	15	1	1 $\frac{1}{2}$	—	C	"	5
138	Type 606	5K	15	1	1 $\frac{1}{2}$	—	C	"	5
10592	Type 3468	5.5K	5	1	1 $\frac{1}{2}$	—	C	"	5
320	Type 738	5.5K	15	1	1 $\frac{1}{2}$	—	C	"	5
139	Type 607	7.5K	15	1	1 $\frac{1}{2}$	—	C	"	5

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS		Class of Store	Denom of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)			
1									
	RESISTORS—cont.								
	Fixed—cont.								
	Metallised filament,								
	in insulating bakelite tube, with concentric wire ends								
	($\frac{1}{2}$, $\frac{3}{4}$, and 1 watt)—cont.								
9216	Type 2544 ...	8.2K	10	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	each	10
9217	Type 2545 ...	10K	10	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	10
6201	Type 6201 ...	10K	10	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	5
140	Type 608 ...	10K	15	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	5
8736	Type 2186 ...	10K	20	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	5
9218	Type 2546 ...	15K	10	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	10
141	Type 609 ...	15K	15	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	5
8765	Type 2215 ...	15K	20	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	5
8348	Type 8348 ...	20K	5	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	5
144	Type 612 ...	30K	5	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	5
8347	Type 8347 ...	33K	5	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	5
8346	Type 8346 ...	33K	10	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	5
321	Type 739 ...	38K	15	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	5
6944	Type 6944 ...	50K	15	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	5
146	Type 614 ...	50K	15	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	5
322	Type 740 ...	55K	15	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	5
8735	Type 2185 ...	56K	10	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	5
147	Type 615 ...	75K	15	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	5
328	Type 746 ...	99K	15	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	5
6133	Type 6133 ...	99K	15	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	5
6132	Type 6132 ...	99K	15	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	5
8517	Type 2039 ...	100K	15	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	5
148	Type 616 ...	100K	15	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	5
318	Type 736 ...	220K	15	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	5
7804	Type 7804 ...	250K	10	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	5
6061	Type 6061 ...	250K	10	$\frac{1}{4}$	$\frac{3}{16}$	$\frac{1}{16}$	C	"	5

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS		Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)			
1									
	RESISTORS—cont.								
	Fixed—cont.								
	Metallised filament,								
	in insulating bakelite tube, with concentric wire ends								
	($\frac{1}{4}$, $\frac{1}{2}$, and 1 watt)—cont.								
8807	Type 2244 ...	560K	10	1	$1\frac{1}{2}$	$\frac{1}{16}$	C	each	5
6302	Type 6302 ...	750K	10	1	$1\frac{1}{2}$	$\frac{1}{16}$	C	"	5
7802	Type 7802 ...	1M	10	1	$1\frac{1}{2}$	$\frac{1}{16}$	C	"	5
152	Type 620 ...	1M	10	1	$1\frac{1}{2}$	$\frac{1}{16}$	C	"	5
7070	Type 7070 ...	1M	15	1	$1\frac{1}{2}$	$\frac{1}{16}$	C	"	5
9516	Type 2768 ...	1M	20	1	$1\frac{1}{2}$	$\frac{1}{16}$	C	"	5
10577	Type 3456 ...	1.8M	10	1	$1\frac{1}{2}$	$\frac{1}{16}$	C	"	5
154	Type 622 ...	3M	15	1	$1\frac{1}{2}$	$\frac{1}{16}$	C	"	5
155	Type 623 ...	5M	15	1	$1\frac{1}{2}$	$\frac{1}{16}$	C	"	5
9498	Type 2753 ...	47M	20	1	$1\frac{1}{2}$	$\frac{1}{16}$	C	"	5

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)	Bore (inches)			
1	RESISTORS—cont. Fixed—cont. Wire-wound: Non-vitreous: Ceramic tube, fixed/adjustable, protected by cement coating:—									
15135	Type 3844 ...	2	7½	50	6	1½	⅜	C	each	1
6191	Type 6191 ...	50	5	15	2	1½	⅜	C	"	1
15547	Type 4256 ...	65	5	7	1½	1½	⅜	C	"	2
6368	Type 6368 ...	300	10	10	1½	1½	⅜	C	"	1
6254	Type 6254 ...	400	5	6	10½	1½	⅜	C	"	2
1364	Type 1364 ...	430	5	180	—	1½	⅜	C	"	1
10863	Type 3613 ...	470	20	6	—	1½	⅜	C	"	10
15683	Type 4378 ...	500	10	6	—	1½	⅜	C	"	2
15885	Type 4567 ...	500	20	10	—	1½	⅜	C	"	1
10495	Type 3409 ...	800	5	10	—	1½	⅜	C	"	1
1180	Type 1180 ...	2.4K	5	180	—	1½	⅜	C	"	1
1332	Type 1332 ...	5K	5	30	—	1½	⅜	C	"	1
596	Type 831 ...	6.5K	5	30	—	1½	⅜	C	"	1
7337	Type 7337 ...	25K	5	15	—	1½	⅜	C	"	1
9866	Type 326 ...	40K to 45K	5	45	—	1½	⅜	C	"	1
7229	Type 7229 ...	50K	2	6	—	1½	⅜	C	"	2
15223	Double spiral solenoid: threaded tubular refractory former, with terminal bands. End brackets horizontal/vertical mounting:—	25	10	30	—	1½	⅜	C	"	1
1549	Type 3932 ...	100	10	10	—	1½	⅜	C	"	1
1544	Type 1549 ...	100	10	20	—	1½	⅜	C	"	1
9622	Type 1544 ...	100	10	20	—	1½	⅜	C	"	1
	Type 269 ...	250	10	20	—	1½	⅜	C	"	1

Ref. No.	Nomenclature	Value in Ohms	Tolerance + or - %	Wattage	Overall Dimensions			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)	Bore (inches)			
1	2	3	4	5	6	7	8	9	10	11
	RESISTORS—cont.									
	Fixed—cont.									
	Wire-wound—cont.									
	Non-vitreous—cont.									
	Double spiral solenoid; threaded tubular refractory former, with terminal bands. End brackets horizontal/vertical mounting—cont.									
10796	Type 3581 ...	300	10	20	3	1	$1\frac{2}{3}$	C	each	1
9623	Type 270 ...	500	10	20	3	1	$1\frac{1}{2}$	C	"	1
6151	Type 6151 ...	1K	10	20	3	1	$1\frac{1}{2}$	C	"	1
10974	Type 396 ...	1.5K	10	20	3	1	$1\frac{1}{2}$	C	"	1
10795	Type 3580 ...	5K	10	10	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{8}$	C	"	2
9518	Type 2770 ...	8.5K	10	20	3	1	$1\frac{1}{2}$	C	"	1
10946	Type 3662 ...	50K	10	10	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{8}$	C	"	1
	Glass or ceramic tube or rod, tropically protected with non-vitreous coating:—									
15388	Type 4097 ...	2	5	2	$1\frac{1}{2}$	$\frac{3}{16}$	—	C	"	2
15487	Type 4196 ...	2.5	1	1	$1\frac{1}{2}$	$\frac{3}{16}$	—	C	"	2
15486	Type 4195 ...	10	1	1	$1\frac{1}{2}$	$\frac{3}{16}$	—	C	"	2
9588	Type 2839 ...	10	10	1	$1\frac{1}{2}$	$\frac{3}{16}$	—	C	"	2
1704	Type 1704 ...	20	10	$1\frac{1}{2}$	$1\frac{1}{2}$	$\frac{3}{16}$	—	C	"	2
15846	Type 4529 ...	22	10	1	$1\frac{1}{2}$	$\frac{3}{16}$	—	C	"	2
9316	Type 2624 ...	27	10	1	$1\frac{1}{2}$	$\frac{3}{16}$	—	C	"	2
9587	Type 2838 ...	47	10	1	$1\frac{1}{2}$	$\frac{3}{16}$	—	C	"	2
10787	Type 3573 ...	47	10	1	$1\frac{1}{2}$	$\frac{3}{16}$	—	C	"	2
15870	Type 4553 ...	57	10	1	$1\frac{1}{2}$	$\frac{3}{16}$	—	C	"	2
15828	Type 4511 ...	60	10	1	$1\frac{1}{2}$	$\frac{3}{16}$	—	C	"	2
6974	Type 6974 ...	100	1	1	$1\frac{1}{2}$	$\frac{3}{16}$	—	C	"	2
9251	Type 2578 ...	140	2	$1\frac{1}{2}$	$1\frac{1}{2}$	$\frac{3}{16}$	—	C	"	5

SECTION 10W—cont.

RADIO RESISTORS

Rel. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Class of Store	Denom. of Qty.	Carton Unit Qty
					Length (inches)	Diameter (inches)	Bore (inches)			
1	RESISTORS—cont. Fixed—cont. Wire-wound—cont. Non-vitreous—cont. Glass or ceramic tube or rod, tropically protected with non-vitreous coating—cont.									
15829	Type 4512 ...	500	1	1 1/2	1 1/4	—	C	each	5	
1702	Type 1702 ...	2K	10	2	1 3/4	—	C	"	2	
9326	Type 2626 ...	2-2K	20	2	1 1/4	—	C	"	2	
8803	Type 2242 ...	4-7K	5	4	2 3/8	—	C	"	2	
1034	Type 1034 ...	5K	10	1	1 1/8	—	C	"	5	
9256	Type 2583 ...	6K	1	2	1 1/8	—	C	"	5	
8802	Type 2241 ...	10K	5	4	1 2/8	—	C	"	2	
15824	Type 4507 ...	12K	1	1	1 1/4	—	C	"	5	
15823	Type 4506 ...	15K	1	1	1 1/4	—	C	"	5	
15822	Type 4505 ...	20K	1	1	1 1/4	—	C	"	5	
10947	Type 3663 ...	25K	10	40	1 1/4	—	C	"	1	
15821	Type 4504 ...	30K	1	4	2 1/8	—	C	"	2	
15073	Type 3782 ...	30K	1	4	—	—	C	"	1	
7226	Type 7226 ...	40K	2	4	1 1/2	—	C	"	2	
15820	Type 4503 ...	60K	1	4	2 1/8	—	C	"	2	
15826	Type 4509 ...	80K	1	4	2 3/8	—	C	"	2	
15825	Type 4508 ...	100K	1	4	2 3/8	—	C	"	2	
10744	Small diam. core, enclosed in bakelite moulded tube:—	4-7	20	—	—	—	C	"	2	
9008	Type 3562 ...	5	10	—	—	—	C	"	5	
301	Type 2384 ...	25	10	—	—	—	C	"	5	
6947	Type 727 ...	75	10	—	—	—	C	"	5	
1727	Type 6947 ...	100	10	—	—	—	C	"	1	
1033	Type 1727 ...	250	10	—	—	—	C	"	5	
8759	Type 1033 ...	270	10	—	—	—	C	"	2	
	Type 2209 ...									

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)	Bore (inches)			
1										
	RESISTORS—cont.									
	Fixed—cont.									
	Wire-wound—cont.									
	Non-vitreous—cont.									
	10-watt, sectioned ceramic former, with metal ends for clip holder:—									
1382	Type 1382 ...	100	5	10	2 1/2	—	—	C	each	1
1381	Type 1381 ...	400	5	10	2 1/2	—	—	C	"	1
7501	Type 7501 ...	500	5	10	2 1/2	—	—	C	"	2
1379	Type 1379 ...	2K	5	10	2 1/2	—	—	C	"	1
7607	Type 7607 ...	2.5K	5	10	2 1/2	—	—	C	"	2
1417	Type 1417 ...	3K	5	10	2 1/2	—	—	C	"	2
1412	Type 1412 ...	4K	5	10	2 1/2	—	—	C	"	2
1413	Type 1413 ...	5K	5	10	2 1/2	—	—	C	"	2
7521	Type 7521 ...	7K	5	10	2 1/2	—	—	C	"	2
1411	Type 1411 ...	10K	5	10	2 1/2	—	—	C	"	2
1416	Type 1416 ...	20K	5	10	2 1/2	—	—	C	"	2
7504	Type 7504 ...	25K	5	10	2 1/2	—	—	C	"	2
1378	Type 1378 ...	30K	5	10	2 1/2	—	—	C	"	2
1415	Type 1415 ...	50K	5	10	2 1/2	—	—	C	"	1
7502	Type 7502 ...	80K	5	10	2 1/2	—	—	C	"	2
1376	Type 1376 ...	100K	5	10	2 1/2	—	—	C	"	2
6337	Type 6337 ...	250K	5	10	2 1/2	—	—	C	"	2

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Connection	Class of Store	Denom. of Qty.	Qty. per Carton
					Length (inches)	Diameter (inches)	Bore (inches)				
1	RESISTORS—cont. Fixed—cont. Wire-wound—cont. Vitreous:—										
6519	Type 6519	0.3	5	15	—	—	—	Bands	C	each	1
15064	Type 3773	0.5	1	6	Miniature	—	—	—	C	"	1
15925	Type 4606	0.6	5	3	—	—	—	—	C	"	5
15375	Type 4084	0.6	5	7½	Miniature	—	—	—	C	"	1
8453	Type 2008	0.75	10	6	1¾	—	—	Wire Ends	C	"	1
15477	Type 4186	1	—	80	—	—	—	—	C	"	1
15052	Type 3761	1	5	12	Miniature	—	—	Wire Ends	C	"	1
15570	Type 4277	1	10	6	1¾	—	—	Wire Ends	C	"	2
8586	Type 2094	1	5	3	1¾	—	—	Wire Ends	C	"	2
17836	Type 9277	1	5	5	1¾	—	—	Wire Ends	C	"	1
821	Type 927	1.1	5	15	2	—	—	To Pigtails	C	"	1
8208	Type 8208	1.5	5	6	1¾	—	—	Wire Ends	C	"	1
15407	Type 4116	1.5	10	6	1¾	—	—	Wire Ends	C	"	2
8578	Type 2086	1.6	5	6	1¾	—	—	Wire Ends	C	"	2
1389	Type 1389	2	5	6	1¾	—	—	Wire Ends	C	"	2
6622	Type 6622	2	5	15	3	—	—	To Ferrules	C	"	1
8343	Type 8343	2	5	6	1¾	—	—	Wire Ends	C	"	2
15206	Type 3915	2.1	10	6	1¾	—	—	Wire Ends	C	"	2
15963	Type 4644	2.3	5	25	4¾	—	—	Pigtails with Pig-tail Taps	C	"	1
15405	Type 4114	2.3	10	100	9¾	—	—	To Ferrules	C	"	1
15742	Type 4435	2.35	5	3	1¼	—	—	Wire Ends	C	"	2
8257	Type 8257	2.4	10	6	1¼	—	—	End Wires	C	"	2
9584	Type 2835	3	5	—	2½	—	—	Wire Ends	C	"	2
6820	Type 6820	3	5	6	Miniature	—	—	To Clamping Ring	C	"	2
7440	Type 7440	3	5	15	2	—	—	Bands	C	"	—
								To Ferrules	C	"	2

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Connection	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)	Bore (inches)				
1	RESISTORS—cont. Fixed—cont. Wire-wound—cont. Vitreous—cont.										
15841	Type 4524	3	5	3	1 1/4	1/4	—	Wire Ends	C	each	5
16955	Type 5464	3	10	7 1/2	—	—	—	—	C	"	—
17039	Type —	3-3	10	—	—	—	—	—	C	"	—
16217	Type 4844	3-3	10	6	—	—	—	—	C	"	—
7641	Type 7641	4	7 1/2	25	4 3/4	1 1/2	—	To Pigtaills To Ferrules	C	"	1
7991	Type 7991	4	5	15	3	1 1/2	—	Wire Ends	C	"	1
1029	Type 1029	4	10	6	1 1/4	1 1/2	—	Wire Ends	C	"	2
16017	Type 4692	4	10	6	1 1/4	1 1/2	—	Wire Ends	C	"	2
6426	Type 6426	4	5	3	1 1/4	1/4	—	Wire Ends To Band with Band Taps	C	"	1
6915	Type 6915	4-0.9	5	25	3 1/2	1/4	—	—	C	"	1
15071	Type 3780	4-5	1	6	Miniature	—	—	—	C	"	1
15512	Type 4221	4-5	5	120	1 1/4	1/16	—	To Ferrules	C	"	1
8579	Type 2087	5	5	6	Miniature	—	—	—	C	"	1
6205	Type 6205	5	5	25	4 3/4	1 1/2	—	To Ferrules	C	"	1
9842	Type 317	5	5	20	5	1 1/2	—	To ferrules	C	"	1
16130	Type 4778	5	10	12	—	1 1/2	—	—	C	"	1
9040	Type 2402	5	10	15	2g	5/8	—	To Pigtaills or to Wire Leads	C	"	2
10525	Type 3428	5	15	15	3	1 1/2	—	To Ferrules	C	"	2
15043	Type 3752	5	5	15	2	1 1/2	—	To Ferrules with Pigtail Taps	C	"	1
15191	Type 3900	5	5	15	2	1 1/2	—	To Pigtaills	C	"	2
1391	Type 1391	5	5	7 1/2	2 1/2	1 1/2	—	To Ferrules	C	"	1
15651	Type 4347	5	20	7 1/2	1 1/4	1 1/2	—	To Ferrules To Pigtaills	C	"	2
15964	Type 4645	5	10	4	—	.28	—	To Pigtaills	C	"	2
17010	Type —	5-2	5	3	—	—	—	Wire Ends	C	"	—

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Connection	Class of Store	D- ^{nom} of Qty.	Qty. Carton #
					Length (inches)	Diameter (inches)	Bore (inches)				
1	2	3	4	5	6	7	8	9	10	11	12
	RESISTORS—cont.										
	Fixed—cont.										
	Wire-wound—cont.										
	<i>Vitreous—cont.</i>										
7408	Type 7408	6	5	7½	1¼	½	—	To Clamping Ring Bands	C	each	2
15526	Type 4235	6	5	20	—	—	—	To Ferrules	C	"	1
15236	Type 3945	6	10	—	—	—	—	Wire Ends	C	"	1
8557	Type 2072	6	10	6	1¼	½	—	Wire Ends	C	"	1
16032	Type 4700	6	10	10-20	—	—	—	Wire Ends	C	"	1
7615	Type 7615	6-5	5	6	1¼	½	—	Wire Ends	C	"	1
15491	Type 4200	6-8	10	½	—	—	—	Wire Ends	C	"	1
16974	Type 5483	6-8	5	65	—	—	—	Wire Ends	C	"	1
15753	Type 4443	7	5	3	1¼	¼	—	Wire Ends	C	"	1
10934	Type 3653	7-4	—	10	—	—	—	To Ferrules	C	"	1
16227	Type 4853	7-5	5	60	—	—	—	To Ferrules	C	"	1
17017	Type —	8	5	15	—	—	—	To Ferrules	C	"	1
16671	Type 5196	9	5	25	—	—	—	To Ferrules	C	"	1
1028	Type 1028	9	5	15	2½	—	—	To Ferrules	C	"	1
15685	Type 4380	9	5	15	2½	—	—	Terminal Bands	C	"	1
1471	Type 1471	9	5	7½	2 1/16	—	—	To Ferrules	C	"	2
6423	Type 6423	9	5	3	2 1/16	—	—	Wire Ends	C	"	2
10619	Type 3493	10	5	15	1¼	—	—	To Pigtales with End Ferrules	C	"	2
6689	Type 6689	10	5	12	Miniature	—	—	Astatic Winding Bands	C	"	5
15303	Type 4012	10	5	7½	—	—	—	To Ferrules	C	"	1
8577	Type 2085	10	5	7½	2 1/16	—	—	Wire Ends	C	"	1
7684	Type 7684	10	2	6	1¼	—	—	Wire Ends	C	"	2
15219	Type 3928	10	—	12	Miniature	—	—	Terminal Bands	C	"	1
18040	Type 9512	10	5	50	—	—	—	Wire Leads	C	"	1
15687	Type 4382	12	10	10	2½	—	—	Wire Leads	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Connection	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)	Bore (inches)				
1	RESISTORS—cont. Fixed—cont. Wire-wound—cont. Vitreous—cont.										
16300	Type 4918	13.5	5	25	4 $\frac{3}{4}$	1 $\frac{1}{8}$	—	To Ferrules	C	each	1
8558	Type 2073	14	10	6	Miniature	—	—	—	C	"	1
16169	Type 4815	15	5	1	—	—	—	To Pigtail with Pigtail Tap	C	"	5
6833	Type 6833	10 + 6	10	15	2 or 1 $\frac{3}{4}$	$\frac{3}{4}$, $\frac{1}{8}$	—	Terminal Bands	C	"	1
350	Type 757	16	2	7 $\frac{1}{2}$	1 $\frac{1}{8}$	1 $\frac{1}{8}$	—	To Ferrules	C	"	1
9563	Type 2814	17.5	5	280	8 $\frac{3}{4}$	1 $\frac{1}{8}$	—	To Ferrules	C	"	1
15928	Type 4609	19	5	6	1 $\frac{3}{4}$	1 $\frac{1}{8}$	—	Wire Ends	C	"	2
6103	Type 6103	19.2	5	65	7 $\frac{1}{4}$	1 $\frac{1}{8}$	—	To Ferrules	C	"	1
17019	Type —	20	5	10	—	—	—	—	C	"	—
15650	Type 4346	20	20	7 $\frac{1}{2}$	1 $\frac{1}{4}$	1 $\frac{1}{8}$	—	To Pigtail Side Wire leads	C	"	2
10918	Type 3639	20	2	7 $\frac{1}{2}$	1 $\frac{1}{8}$	1 $\frac{1}{8}$	—	—	C	"	1
9199	Type 2729	20	5	2	Miniature	—	—	—	C	"	1
8283	Type 8283	20.7	5	25	3 $\frac{1}{2}$	$\frac{3}{4}$	—	To Clamping Ring Bands	C	"	1
15138	Type 3857	21	5	7 $\frac{1}{2}$	—	—	—	Ferrules	C	"	1
15387	Type 4096	21	5	12	Miniature	—	—	—	C	"	1
17040	Type —	22	5	—	—	—	—	—	C	"	—
15962	Type 4643	23	10	100	—	—	—	Termination Ferrules To Bands with Band	C	"	1
15205	Type 3914	23.9	5	25	3 $\frac{1}{4}$	$\frac{3}{4}$	—	—	C	"	1
15468	Type 4177	25	5	100	9 $\frac{3}{4}$	1 $\frac{1}{8}$	—	To Pigtail with Taps	C	"	1
6360	Type 6370	25	5	45	—	—	—	End Ferrules Termination Ferrules and Pigtails Wire Ends	C	"	1
9221	Type 2549	25	10	3	1 $\frac{3}{8}$	—	—	—	C	"	2
15391	Type 4100	25	10	6	Miniature	—	—	—	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Connection	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)	Bore (inches)				
1	2	3	4	5	6	7	8	9	10	11	12
	RESISTORS—cont.										
	Fixed—cont.										
	Wire-wound—cont.										
	Vitreous—cont.										
15688	Type 4383	26	10	10	2 $\frac{3}{8}$	$\frac{1}{8}$	—	Wire Leads	C	each	1
8072	Type 8072	26	5	6	—	$\frac{1}{16}$	—	Wire Ends	C	"	2
1094	Type 1094	27 (10 + 17)	5	15	2	$\frac{3}{4}$	—	To Pigtailed with Pigtail Tap	C	"	1
15414	Type 4123	28	5	7 $\frac{1}{2}$	Miniature	—	—	—	C	"	1
9369	Type 2660	30	5	45	4	$1\frac{1}{8}$	—	To Pigtailed	C	"	1
8548	Type 2063	30	10	3	1 $\frac{3}{8}$	$\frac{9}{32}$	—	Wire Ends	C	"	1
16393	Type 4974	30	20	—	—	—	—	Embedded	C	"	1
10062	Type 343	31	5	7 $\frac{1}{2}$	2 $\frac{5}{8}$	$\frac{1}{16}$	—	To Ferrules	C	"	2
15293	Type 4002	31	5	3	1 $\frac{1}{4}$	$\frac{1}{32}$	—	Side Wires	C	"	2
15439	Type 4148	31.5	10	1.5	—	—	—	—	C	"	1
15221	Type 3930	32	10	6	1 $\frac{3}{4}$	$\frac{3}{8}$	—	Wire Ends	C	"	2
15056	Type 3765	32	5	12	Miniature	—	—	—	C	"	1
15386	Type 4095	32	5	3	1 $\frac{3}{8}$	$\frac{9}{32}$	—	Wire Ends	C	"	2
15874	Type 4559	33	20	3	1 $\frac{3}{8}$	$\frac{9}{32}$	—	Wire Ends	C	"	2
9564	Type 2815	35	5	280	8 $\frac{1}{4}$	$\frac{3}{16}$	—	To Ferrules	C	"	1
1446	Type 1446	36	5	65	7 $\frac{1}{4}$	1 $\frac{1}{16}$	—	To Ferrules	C	"	1
1345	Type 1345	40	5	15	2	—	—	To Pigtailed	C	"	2
6427	Type 6427	40	5	6	2	$\frac{1}{4}$	—	Wire Ends	C	"	2
8075	Type 8075	40	5	6	Miniature	—	—	—	C	"	1
15249	Type 3935	40	10	—	Miniature	—	—	—	C	"	1
16129	Type 4777	40	10	6	—	—	—	—	C	"	1
15220	Type 3929	42	10	3	1 $\frac{3}{8}$	$\frac{9}{32}$	—	Wire Ends	C	"	2
15072	Type 3781	45	5	6	Miniature	—	—	—	C	"	1
10143	Type 371	45	1	100	9 $\frac{3}{4}$	1 $\frac{1}{16}$	—	To Ferrules	C	"	1
1370	Type 1370	45	5	65	7 $\frac{1}{4}$	1 $\frac{1}{16}$	—	To Ferrules	C	"	1
10659	Type 411	50	5	90	—	—	—	—	C	"	1
15066	Type 3775	50	1	6	Miniature	—	—	—	C	"	1

RADIO RESISTORS

SECTION 10W—cont.

C (P16315)

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Connection	Class of Store	Denom. of Qty.	Carton Unit Qty
					Length (inches)	Diameter (inches)	Bore (inches)				
1	RESISTORS—cont.										
	Fixed—cont.										
	Wire-wound—cont.										
	Vitreous—cont.										
15299	Type 4008	50	5	25	—	1 1/8	—	To Pigtaails To Ferrules with End Ferrules	C	each	1
15474	Type 4183	50	5	25	4 3/4	—	—	To Pigtaails To Ferrules with End Ferrules	C	"	1
8444	Type 8444	50	10	15	2 3/8	9/16	—	To Ferrules	C	"	1
11699	Type 527	50	2	7 1/2	1 1/8	11/16	—	Wire Ends	C	"	1
349	Type 756	50	2	7 1/2	1 1/8	11/16	—	Terminal Bands	C	"	1
7998	Type 7998	50	10	6	1 1/2	11/16	—	Wire Ends	C	"	2
7310	Type 7310	50	20	3	—	—	—	—	C	"	2
1330	Type 1330	60	—	—	—	—	—	—	C	"	1
15673	Type 4369	60	10	10	2 3/8	1/2	—	Wire Leads	C	"	1
17264	Type 5721	60	5	10	—	—	—	—	C	"	1
8074	Type 8074	60	5	6	—	—	—	End Wires	C	"	2
7843	Type 7843	60	10	3	1	1/4	—	End Wires	C	"	2
7419	Type 7419	60	5	3	1	1/4	—	End Wires	C	"	1
15065	Type 3774	61	1	6	—	—	—	—	C	"	1
848	Type 850	64	10	6	—	—	—	—	C	"	1
15128	Type 3837	65	5	3	—	—	—	—	C	"	1
1501	Type 1501	72	10	6	—	—	—	—	C	"	1
16853	Type 5366	75	5	75	7 3/4	7/16	—	—	C	"	1
15947	Type 4628	75	5	50	7 3/4	1 1/8	—	To Ferrules	C	"	1
15652	Type 4348	75	10	15	2	3/8	—	Clamping Ring Bands	C	"	2
8710	Type 2172	75	5	15	2 1/8	3/8	—	Terminal Bands	C	"	2
15541	Type 4250	75	10	3	1 3/8	11/16	—	Wire Ends	C	"	2
15548	Type 4257	80	5	100	9 3/4	1 1/8	—	To Ferrules	C	"	1
6419	Type 6419	80	5	50	7 3/4	1 1/8	—	To Ferrules	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Connection	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)	Bore (inches)				
1	2	3	4	5	6	7	8	9	10	11	12
	RESISTORS—cont.										
	Fixed—cont.										
	Wire-wound—cont.										
	Vitreous—cont.										
8203	Type 8203	80	5	45	—	—	—	—	C	each	—
6692	Type 6692	80	5	6	1 3/8	3/16	—	Termination Ferrules	C	—	2
7068	Type 7068	80	5	3	1 3/8	3/16	—	Astatic Winding	C	—	2
6869	Type 6869	82.5 (75 + 7.5)	5	—	—	—	—	Wire Ends	C	—	1
18019	Type 9397 (F)	90	10	100	9 3/4	1 1/8	—	Capped Ends	C	—	1
16363	Type 4953	100	20	—	—	—	—	To Ferrules	C	—	1
7493	Type 7493	100	5	50	7 3/4	1 1/8	—	To Ferrules	C	—	1
17266	Type 5723	100	5	50	—	—	—	—	C	—	1
352	Type 754	100	5	15	2	1 1/8	—	To Pigtails	C	—	1
11702	Type 530	100	5	15	1 1/8	1/16	—	Wire Ends	C	—	1
8213	Type 8213	100	2	6	—	—	—	Wire Ends	C	—	2
10541	Type 3441	100	10	4	1 1/8	3/8	—	—	C	—	2
15622	Type 4318	100	10	3	1 1/8	—	—	Wire Ends	C	—	2
8905	Type 2316	100	10	—	—	—	—	—	C	—	2
7570	Type 7570	110	5	15	—	—	—	—	C	—	1
1321	Type 1321	120	5	100	9 3/4	1 1/8	—	Bands	C	—	1
10854	Type 437	120	5	65	7 1/4	1 1/8	—	To Ferrules	C	—	1
1410	Type 1410	125	5	100	9 3/4	1 1/8	—	To Pigtails	C	—	1
15023	Type 3732	125	5	6	—	—	—	To Ferrules	C	—	1
17265	Type 5722	125	5	10	—	—	—	—	C	—	1
17265	Type 5722	125	5	10	—	—	—	—	C	—	1
17835	Type 9276	125	5	10	—	—	—	—	C	—	1
15440	Type 4149	126	10	1 1/2	—	—	—	Double Glazed Capped	C	—	1
15927	Type 4608	150	10	12	—	—	—	Ends Tropicalised	C	—	1
15946	Type 4627	150	5	50	7 3/4	1 1/8	—	To Ferrules	C	—	1
11700	Type 528	150	2	7 1/2	1 1/8	1/16	—	Wire Ends	C	—	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Connection	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)	Bore (inches)				
1	RESISTORS—cont. Fixed—cont. Wire-wound—cont. Vitreous—cont.										
15633	Type 4329	150	10	3	1 3/8	—	—	Wire Ends	C	each	2
6575	Type 6575	174	5	15	—	—	—	Bands	C	"	1
10078	Type 359	174	5	15	3	1/8	—	To Ferrules	C	"	2
1921	Type 1921	175	5	15	—	—	—	Bands	C	"	1
10641	Type 3498	190	5	65	7 1/4	1 1/8	—	To Ferrules	C	"	1
748	Type 886	195	10	3	1 3/8	—	—	Wire Ends	C	"	2
7244	Type 7244	200	5	25	4 1/2	1 1/8	—	To Pigtails	C	"	1
8397	Type 8397	200	10	—	6-8 1/3 o/a	3/4 Ferrules	—	—	C	"	1
15741	Type 4434	200	5	15	2	3/4	—	To Pigtails	C	"	2
8050	Type 8050	200	20	6	1 3/8	—	—	Wire Ends	C	"	2
15384	Type 4093	200	10	6	1 3/4	—	—	Wire Ends	C	"	2
15876	Type 4559	220	5	20	—	—	—	To Ferrules	C	"	1
6579	Type 6579	250	5	25	—	—	—	To Ferrules and Pigtails	C	"	1
10853	Type 456	250	5	15	—	—	—	To Ferrules and Pigtails	C	"	2
16392	Type 4973	250	20	12	—	—	—	—	C	"	1
11701	Type 529	250	2	7 1/2	1 1/8	1/8	—	Wire Ends	C	"	1
1581	Type 1581	250	5	6	2	—	—	Wire Ends	C	"	2
15125	Type 3834	250	10	6	1 3/4	—	—	Wire Ends	C	"	2
15834	Type 4517	250	5	3	1 3/8	3/8	—	Side Wires	C	"	2
7309	Type 7309	250	20	3	1 3/8	—	—	Wire Ends	C	"	2
9815	Type 301	255	5	15	3	1/8	—	To Ferrules	C	"	2
762	Type 900	270	10	6	Miniature	—	—	—	C	"	1
15944	Type 4625	300	5	50	7 1/2	1 3/8	—	To Ferrules	C	"	1
15854	Type 4537	300	5	7 1/2	—	—	—	Bands	C	"	1
15179	Type 3888	300	10	10	—	—	—	No End Fittings	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Connection	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)	Bore (inches)				
1	RESISTORS—cont. Fixed—cont. Wire-wound—cont. Vitreous—cont.										
6159	Type 6159	300	10	6	1 $\frac{3}{4}$	—	—	Wire Ends	C	each	2
15180	Type 3889	325	5	6	1 $\frac{1}{2}$	—	—	Wire Ends	C	"	2
1048	Type 1048	350	5	25	4 $\frac{3}{4}$	—	4 $\frac{3}{16}$ Fixing Centres	To Ferrules	C	"	1
9861	Type 322	119+119+119	5	20	4	—	—	To Pigtales with Pigtail Tap	C	"	—
15784	Type 4468	367	5	45	4 $\frac{1}{8}$	1 $\frac{1}{4}$	—	Terminal Bands	C	"	1
17852	Type 9293	400 Tapped every 50 ohms	100	5	9 $\frac{1}{2}$	1 $\frac{1}{8}$	—	To Ferrules	C	"	5
15945	Type 4626	400	5	50	7 $\frac{1}{2}$	1 $\frac{3}{16}$	—	To Ferrules	C	"	1
11703	Type 531	400	2	7 $\frac{1}{2}$	1 $\frac{1}{16}$	—	—	Wire Leads	C	"	1
10620	Type 3494	400	10	6	2	—	—	Wire Ends	C	"	2
1642	Type 1642	430	5	120	11 $\frac{3}{4}$	1 $\frac{1}{16}$	Fixing Centres	To Ferrules	C	"	1
9810	Type 314	434	5	65	7 $\frac{1}{2}$	11 $\frac{1}{16}$	—	To Ferrules	C	"	1
15139	Type 3848	440	5	7 $\frac{1}{2}$	2 $\frac{1}{8}$	1 $\frac{1}{16}$	—	To Ferrules	C	"	1
8845	Type 2274	450	5	100	9 $\frac{1}{2}$	1 $\frac{1}{16}$	—	To Ferrules	C	"	1
15875	Type 4558	470	5	20	—	—	—	To Ferrules	C	"	1
10072	Type 353	500	2	100	9 $\frac{1}{2}$	1 $\frac{1}{16}$	—	To Ferrules	C	"	1
8546	Type 2061	500	5	280	—	—	—	To Pigtales	C	"	—
1335	Type 1335	500	5	65	7 $\frac{1}{4}$	1 $\frac{1}{16}$	—	To Ferrules	C	"	1
15948	Type 4629	500	5	50	7 $\frac{1}{4}$	1 $\frac{1}{16}$	—	To Ferrules	C	"	1
15196	Type 3905	500 Tapped at 100 ohms 200 ohms 500	5	50	—	—	—	To Ferrules	C	"	1
6580	Type 6580	500	5	45	5 $\frac{1}{4}$	1 $\frac{1}{16}$	—	To Pigtales	C	"	1
6282	Type 6282	500	5	20	—	—	—	Termination Ferrules	C	"	2

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Connection	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)	Bore (inches)				
1	2	3	4	5	6	7	8	9	10	11	12
	RESISTORS—cont.										
	Fixed—cont.										
	Wire-wound—cont.										
	Vitreous—cont.										
15991	Type 4668	500	5	15	3	$\frac{3}{16}$	—	To Pigtails	C	each	2
10642	Type 3499	500	10	10	$2\frac{3}{8}$	$\frac{1}{8}$	—	Wire Leads	C	"	2
15010	Type 3719	500	5	10	$2\frac{3}{8}$	$\frac{1}{8}$	—	Wire Leads	C	"	2
15331	Type 4040	500	10	$7\frac{1}{2}$	—	—	—	Bands	C	"	1
8466	Type 2019	500	5	—	$2\frac{5}{8}$ o/a	$\frac{1}{8}$ Ferrules	—	To Ferrules	C	"	1
10797	Type 469	500	5	$7\frac{1}{2}$	$2\frac{1}{8}$	$\frac{1}{8}$	—	Wire Leads	C	"	1
11704	Type 532	500	2	$7\frac{1}{2}$	$1\frac{1}{8}$	$\frac{1}{8}$	—	To Ferrules	C	"	1
7448	Type 7448	500	5	6	2	—	—	Wire Ends	C	"	2
9163	Type 2506	500	5	6	$1\frac{3}{4}$	—	—	Wire Ends	C	"	2
9240	Type 2567	500	10	6	2	—	—	Wire Ends	C	"	2
9348	Type 2642	500	10	6	$1\frac{3}{4}$	—	—	Wire Ends	C	"	2
7305	Type 7305	500	20	6	$1\frac{3}{4}$	—	—	Wire Ends	C	"	2
15830	Type 4513	500	1	3	$1\frac{3}{4}$	—	—	Wire Ends	C	"	2
7445	Type 7445	500	10	3	$1\frac{3}{4}$	—	—	Wire Ends	C	"	2
8556	Type 2071	500	10	3	$1\frac{3}{4}$	—	—	Wire Ends	C	"	2
6511	Type 6511	600	5	6	$2\frac{1}{8}$	$\frac{1}{8}$	—	To Ferrules	C	"	1
15020	Type 3729	600	5	25	$2\frac{1}{8}$	$\frac{1}{8}$	—	To Pigtails	C	"	1
15717	Type 4412	600	5	25	$3\frac{1}{2}$	$\frac{1}{8}$	—	To Pigtails	C	"	1
10067	Type 348	600	5	15	—	—	—	Bands	C	"	1
15740	Type 4433	600	5	15	3	$\frac{1}{8}$	—	To Ferrules	C	"	2
15378	Type 4087	600	5	$7\frac{1}{2}$	2	$\frac{1}{8}$	—	To Pigtails	C	"	1
11705	Type 533	600	2	$7\frac{1}{2}$	1 $\frac{1}{8}$	$\frac{1}{8}$	—	Wire Leads	C	"	1
15328	Type 4037	600	10	6	2	$\frac{1}{8}$	—	Wire Leads	C	"	1
15653	Type 4349	650	10	10	—	—	—	Wire Ends	C	"	2
10077	Type 358	666	5	15	2	—	—	Pigtails Anchored	C	"	10
15173	Type 3882	680	5	$7\frac{1}{2}$	—	—	—	—	C	"	2
17961	Type 9345	680	5	$7\frac{1}{2}$	—	—	—	Metal Inserts	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	Nomenclature	Value in Ohms	Tolerance + or - %	Wattage	Overall Dimensions			Connection	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)	Bore (inches)				
1	RESISTORS—cont. Fixed—cont. Wire-wound—cont. Vitreous—cont.										
15021	Type 3730	750	5	15	2	$\frac{3}{4}$	—	To Pigtails	C	each	2
15177	Type 3886	770	5	10	$\frac{9}{32}$	$\frac{1}{16}$	—	To Ferrules	C	"	1
1408	Type 1408	800	5	100	$\frac{2}{8}$	$\frac{1}{4}$	—	To Ferrules Wire Leads	C	"	1
16240	Type 4866	800	10	10	$\frac{1}{4}$	$\frac{1}{16}$	—	To Bands	C	"	2
15953	Type 4634	800	5	$7\frac{1}{2}$	$\frac{1}{4}$	$\frac{1}{16}$	—	(Clamping Ring)	C	"	2
10540	Type 3440	800	+0-10	4	$\frac{5}{8}$	$\frac{5}{32}$	—	Bands	C	"	2
15689	Type 4384	820	5	25	—	$\frac{9}{32}$	—	To Ferrules	C	"	2
10079	Type 360	900	5	15	3	$\frac{1}{16}$	—	To Ferrules	C	"	2
6508	Type 6508	900	5	$7\frac{1}{2}$	$2\frac{1}{16}$	$\frac{1}{16}$	—	To Ferrules	C	"	2
9627	Type 2868	1 K	+0-5	280	$8\frac{3}{4}$	$1\frac{1}{8}$	—	To Ferrules	C	"	1
1328	Type 1328	1 K	5	100	$9\frac{3}{4}$	$1\frac{1}{16}$	—	To Ferrules with Pigtail Tap	C	"	1
67	Type 567	1 K	3	65	1 $\frac{13}{16}$ dia.	$\frac{5}{8}$	—	Wire Leads	C	"	1
9817	Type 303	1 K	5	50	$7\frac{3}{4}$	$1\frac{3}{16}$	—	To Ferrules	C	"	1
16012	Type 4689	1 K	10	30	$1.64 \times 1.72 \times 0.06$	—	—	Bands	C	"	1
6581	Type 6581	1 K	5	25	$4\frac{3}{4}$	$\frac{13}{16}$	—	To Pigtails	C	"	1
1220	Type 1220	1 K	5	15	2	$\frac{3}{4}$	—	To Pigtails	C	"	2
16394	Type 4975	1 K	10	20	—	—	—	—	C	"	1
15200	Type 3209	1 K	10	20	—	—	—	—	C	"	1
15059	Type 3768	1 K	10	$7\frac{1}{2}$	—	—	—	Wire Leads	C	"	1
16291	Type 4911	1 K	10	$7\frac{1}{2}$	—	—	—	Terminal	C	"	1
700	Type 881	1 K	5	6	$2\frac{1}{16}$ dia.	—	—	To Ferrules	C	"	1
9196	Type 2528	1 K	5	$7\frac{1}{2}$	$1\frac{5}{16}$	$\frac{1}{16}$	—	Wire Leads	C	"	1
1730	Type 1730	1 K	10	$7\frac{1}{2}$	$1\frac{5}{16}$	$\frac{1}{16}$	—	Wire Ends	C	"	2
6428	Type 6428	1 K	5	6	$1\frac{5}{16}$	—	—	Wire Ends	C	"	2
6496	Type 6496	1 K	5	6	2	—	—	Wire Ends	C	"	2

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Connection	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)	Bore (inches)				
1	RESISTORS—cont. Fixed—cont. Wire-wound—cont. Vitreous—cont.										
8539	Type 2054	1 K	15	6	1 3/8	—	—	—	C	each	2
7067	Type 7067	1 K	5	3	7/8	—	—	—	C	"	2
15403	Type 4112	1-125 K	5	7 1/2	Miniature	—	—	—	C	"	1
7443	Type 7443	1-2 K	5	100	9 3/4	1 1/8	—	To Ferrules	C	"	1
8443	Type 8443	1-2 K	5	—	2 5/8 o/a	1 1/8 Ferrules	—	To Ferrules	C	"	1
15386	Type 4568	1-2 K	10	10	—	—	—	Wire Leads	C	"	1
15298	Type 4007	1-2 K	20	7 1/4	—	—	—	To Ferrules	C	"	1
9049	Type 2411	1-2 K	5	20	—	—	—	To Ferrules	C	"	1
71	Type 571	600 + 700	3	65	1 13/8	5/8	—	Wire Leads	C	"	1
16493	Type 5064	1-3 K	10	10	—	—	—	—	C	"	1
6929	Type 6929	1-49 K	10	15	3	1 1/8	—	To Ferrules	C	"	2
10734	Type 3558	1-5 K	5	20	5 1/4	1 1/8	—	To Ferrules	C	"	1
1644	Type 1644	1-5 K	5	15	2	5/8	—	To Bands	C	"	2
15234	Type 3943	1-5 K	5	15	—	—	—	(Clamping Rings) To Bands	C	"	1
15493	Type 4202	1-5 K	10	—	—	—	—	—	C	"	1
9362	Type 2653	1-5 K	10	6	1 1/4	—	—	Wire Ends	C	"	1
15297	Type 4006	1-5 K	20	7 1/4	—	—	—	To Ferrules	C	"	2
16302	Type 4920	1-5 K	20	6	1 3/4	—	—	Wire Ends	C	"	1
1695	Type 1695	1-5 K	10	3	1 13/8	—	—	Wire Ends	C	"	2
15686	Type 4381	1-5 K	5	3	1 13/8	—	—	Wire Ends	C	"	2
15068	Type 3777	1-8 K	1	6	Miniature	—	—	—	C	"	1
15067	Type 3776	1-96 K	1	6	Miniature	—	—	—	C	"	1
1138	Type 1138	2 K	5	100	9 3/4	1 1/8	—	To Ferrules	C	"	1
8840	Type 2269	2 K	5	50	7 3/4	1 1/8	—	To Ferrules	C	"	1
15473	Type 4182	2 K	5	25	3 13/8	7/8	—	To Terminal Bands	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Connection	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)	Bore (inches)				
1	RESISTORS—cont. Fixed—cont. Wire-wound—cont. Vitreous—cont. Type 7241	2 K	5	7½	1½	⅝	—	To Bands (Clamping Ring)	C	each	2
1665	Type 1665	2 K	5	6	1¼	—	—	To Bands (Clamping Ring)	C	"	1
15301	Type 4010	2 K	10	20	—	—	—	Wire Ends	C	"	1
15381	Type 4090	2 K	10	6	Miniature	—	—	Wire Leads	C	"	1
7311	Type 7311	2 K	20	6	1¾	—	—	Wire Ends	C	"	2
1217	Type 1217	2 K	10	3	1⅝	—	—	Wire Ends	C	"	2
16454	Type 5032	2.2 K	10	30	—	—	—	—	C	"	1
15988	Type 4665	2.2 K	10	7½	Miniature	—	—	—	C	"	1
15718	Type 4413	2.2 K	10	3	1⅝	—	—	Wire Ends	C	"	2
6964	Type 6964	2.3 K	5	25	—	—	—	To Ferrules	C	"	1
15211	Type 3920	2.35 K	10	6	Miniature	—	—	—	C	"	1
15193	Type 3902	2,500, Tapped 500 ohms	5	100	—	—	—	To Ferrules	C	"	1
7940	Type 7940	1,000 ohms	5	15	3½	⅝	—	To Pigtails	C	"	1
15195	Type 3904	2,500 ohms	5	7½	—	—	—	To Pigtails	C	"	1
8893	Type 2313	2.5 K	10	15	3	⅝	—	To Pigtails	C	"	1
15382	Type 4091	2.5 K	10	12	Miniature	—	—	To Ferrules	C	"	2
9266	Type 2593	2.5 K	10	10	—	—	—	—	C	"	1
1241	Type 1241	2.5 K	5	15	2	¾	—	To Pigtails	C	"	2
15762	Type 4448	2.5 K	10	15	2	¾	—	To Pigtails (Anchored by 1 turn)	C	"	2
15765	Type 4451	2.5 K	10	15	2	¾	—	To Bands (Clamping Ring)	C	"	2
9734	Type 2956	2.5 K	5	10	2½	½	—	Wire Leads	C	"	2

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Connection	Class of Store	Denom. of Qty.	Carton Unit Qty
					Length (inches)	Diameter (inches)	Bore (inches)				
1	RESISTORS—cont. Fixed—cont. Wire-wound—cont. Vitreous—cont.										
15606	Type 4302	2.5 K	10	10	2 $\frac{3}{8}$	$\frac{1}{8}$	—	To Bands (Clamping Ring) Wire Ends	C	each	1
7303	Type 7303	2.5 K	20	6	1 $\frac{1}{2}$	—	—	Wire Ends	C	"	2
1583	Type 1583	2.5 K	5	6	2	—	—	Wire Ends	C	"	2
1518	Type 1518	2.6 K	5	15	3	$\frac{1}{16}$	—	To Ferrules	C	"	2
15070	Type 3779	2.7 K	1	6	Miniature	—	—	—	C	"	1
1768	Type 1768	3 K	5	25	4 $\frac{1}{2}$	$\frac{13}{16}$	—	To Ferrules	C	"	1
936	Type 969	3 K	5	20	5	$\frac{13}{16}$	—	To Ferrules	C	"	1
15749	Type 4439	3 K	5	15	3	$\frac{11}{16}$	—	To Bands	C	"	1
15793	Type 4477	3 K	5	10	—	—	—	—	C	"	1
15418	Type 4127	3 K	10	25	—	—	—	To Ferrules	C	"	1
16191	Type 4823	3 K	10	10	—	—	—	—	C	"	1
1701	Type 1701	3 K	10	6	1 $\frac{1}{2}$	—	—	Wire Ends	C	"	2
1213	Type 1213	3 K	10	3	1 $\frac{1}{2}$	—	—	Wire Ends	C	"	2
16391	Type 4972	3 K	20	10	1 $\frac{1}{2}$	—	—	—	C	"	1
15659	Type 4355	3.3 K	10	15	—	—	—	—	C	"	1
16069	Type 4725	3.3 K	10	4	$\frac{5}{16}$	$\frac{3}{16}$	—	Bands	C	"	1
15529	Type 4238	3.3 K	20	3	1 $\frac{1}{8}$	—	—	Wire Ends	C	"	2
1204	Type 1204	3.4 K	5	7 $\frac{1}{2}$	2 $\frac{1}{16}$	$\frac{1}{16}$	—	To Ferrules	C	"	2
9579	Type 2830	3.5 K	5	15	3	$\frac{1}{16}$	—	To Ferrules	C	"	1
15025	Type 3734	3.5 K	5	7 $\frac{1}{2}$	Miniature	—	—	—	C	"	1
16956	Type 5465	3.9 K	10	2 $\frac{1}{2}$	—	—	—	—	C	"	1
16395	Type 4976	3.9 K	10	12	—	—	—	—	C	"	1
1186	Type 1186	4 K	5	100	Miniature	1 $\frac{1}{16}$	—	To Ferrules	C	"	1
16126	Type 4774	4 K	5	100	9 $\frac{1}{4}$	—	—	Bands	C	"	1
1627	Type 1627	4 K	5	25	4 $\frac{1}{2}$	$\frac{13}{16}$	—	To Ferrules	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	Nomenclature	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Connection	Class of Store	Denom of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)	Bore (inches)				
1	RESISTORS—cont. Fixed—cont. Wire-wound—cont. Vitreous—cont.										
10080	Type 361	4 K	5	15	3	$\frac{1}{16}$	—	To Ferrules	C	each	2
15684	Type 4379	4 K	10	15	$2 \frac{1}{16}$	$\frac{1}{16}$	—	Terminal Bands	C	"	2
15226	Type 3935	4 K	10	10	$2 \frac{3}{8}$	$\frac{1}{16}$	—	Wire Leads	C	"	2
1086	Type 1086	4 K	5	$7 \frac{1}{2}$	$2 \frac{5}{16}$	$\frac{1}{16}$	—	To Ferrules	C	"	2
6425	Type 6425	4 K	5	6	2	$\frac{1}{16}$	—	Wire Ends	C	"	2
7741	Type 7741	4 K	10	3	1	—	—	Wire Ends	C	"	2
15421	Type 4130	4.5 K	5	200	$9 \frac{3}{4}$	—	—	To Ferrules	C	"	1
9000	Type 2376	4.5 K	10	65	$7 \frac{1}{4}$	$1 \frac{1}{16}$	—	To Ferrules	C	"	1
16339	Type 4865	4.5 K	10	$7 \frac{1}{2}$	—	—	—	To Ferrules	C	"	1
16452	Type 5030	4.7 K	30	10	—	—	—	To Ferrules	C	"	1
15593	Type 4298	4.7 K	5	6	—	—	—	Wire Ends	C	"	2
1646	Type 1646	4.7 K	10	3	2	—	—	Wire Ends	C	"	5
1047	Type 1047	5 K	5	25	$1 \frac{3}{8}$	—	—	To Ferrules	C	"	1
15763	Type 4449	5 K	5	25	$4 \frac{5}{8}$	$\frac{1}{16}$	—	To Bands	C	"	2
6542	Type 6542	5 K	5	15	$3 \frac{1}{8}$	—	—	To Bands	C	"	1
7382	Type 7382	5 K	5	15	3	$\frac{1}{16}$	—	To Pigtails	C	"	2
6500	Type 6500	5 K	5	15	2	$\frac{1}{16}$	—	To Bands	C	"	1
15443	Type 5152	5 K	10	—	2	—	—	To Ferrules	C	"	1
9370	Type 2661	5 K	10	15	2 $\frac{1}{16}$	—	—	To Ferrules (Anchored by 1 turn)	C	"	2
1687	Type 1687	5 K	10	6	$1 \frac{3}{4}$	$\frac{3}{16}$	—	Wire Ends	C	"	2
1745	Type 1745	5 K	10	6	2	$\frac{1}{16}$	—	Wire Ends	C	"	2
1212	Type 1212	5 K	10	3	$1 \frac{3}{8}$	$\frac{1}{16}$	—	Wire Ends	C	"	2
1405	Type 1405	5.5 K	5	25	$4 \frac{1}{2}$	$\frac{1}{16}$	—	To Ferrules	C	"	1
6270	Type 6270	5.5 K	5	15	3	$\frac{1}{16}$	—	To Ferrules	C	"	2
16290	Type 4910	5.6 K	10	6	—	—	—	—	C	"	1
10003	Type 327	6 K	5	45	5 $\frac{1}{4}$	$1 \frac{1}{16}$	—	To Ferrules	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Connection	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)	Bore (inches)				
1	RESISTORS—cont. Fixed—cont. Wire-wound—cont. Vitreous—cont.										
9841	Type 316	6 K	5	25	4 1/2	1 1/8	—	To Ferrules Ferrules and Pigtails	C	each	1
1540	Type 1540	6 K	5	100	—	—	—	Ferrules and Pigtails	C	"	1
7585	Type 7585	6 K	5	45	—	—	—	To Clamping Ring	C	"	2
15012	Type 3721	6 K	5	10	2 3/8	1/2	—	To Clamping Ring	C	"	2
7096	Type 7096	6 K	5	7 1/2	Miniature	—	—	—	C	"	—
7982	Type 7982	6 K	5	3	1	1/4	—	Wire Ends	C	"	2
7835	Type 7835	6 K	20	12	Miniature	—	—	—	C	"	1
16145	Type 4792	6-5 K	5	7 1/2	3	—	—	To Ferrules	C	"	1
15871	Type 4554	6-6 K	5	15	—	—	—	—	C	"	1
15977	Type 4654	6-6 K	5	7 1/2	—	—	—	—	C	"	1
15692	Type 4387	6-8 K	10	6	1 1/4	3/16	—	Wire Ends	C	"	2
15197	Type 3906	7 K	5	100	9 1/4	1 1/16	—	To Ferrules	C	"	1
6406	Type 6406	7 K	5	100	—	—	—	Ferrules and Pigtails	C	"	1
881	Type 945	7 K	5	25	3 1/2	7/8	—	To Clamping Ring	C	"	1
9865	Type 325	7 K	5	25	3 1/2	7/8	—	To Pigtails with Bands	C	"	2
15472	Type 4181	7 K	5	25	3 1/8	7/8	—	To Pigtails with Pigtail Tap	C	"	1
181	Type 649	7 K	—	—	2	7/8	—	Terminal Bands	C	"	1
15224	Type 3933	7 K	5	12	Miniature	—	—	To Clamping Ring	C	"	1
15777	Type 4461	7 K	5	3	Miniature	—	—	—	C	"	1
9363	Type 2654	7 K	10	6	1 1/4	3/8	—	Wire Ends	C	"	2
15607	Type 4303	7 K	20	6	—	—	—	—	C	"	1
1420	Type 1420	7-5 K	20	—	—	—	—	—	C	"	—
15634	Type 4330	7-5 K	10	20	—	—	—	To Ferrules	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Connection	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)	Bore (inches)				
1	2	3	4	5	6	7	8	9	10	11	12
RESISTORS—cont. Fixed—cont. Wire-wound—cont. Vitreous—cont.											
1957	Type 1957	7.5 K	5	15	2 1/16	3/4	—	Terminal Bands	C	each	1
1582	Type 1582	7.5 K	5	6	2	1/4	—	Wire Ends	C	"	2
15261	Type 3970	7.5 K	20	3	Miniature	—	—	Wire Ends	C	"	1
6906	Type 6906	7.5 K	10	3	1 3/8	3/8	—	To Ferrules	C	"	2
15943	Type 4624	8 K	5	15	—	—	—	Terminal Bands	C	"	1
15779	Type 4463	8 K	5	8	2 1/16	2 1/8	—	Clip Ends	C	"	2
1560	Type 1560	8 K	5	6	2 1/8	2 1/8	—	Wire Ends	C	"	1
757	Type 895	8 K	10	6	1 3/4	3/8	—	Wire Ends	C	"	2
6588	Type 6588	8 K	5	6	2	1/4	—	Wire Ends	C	"	2
16453	Type 5031	8.2 K	10	30	—	—	—	—	C	"	1
6558	Type 6558	8.9 K	—	—	—	—	—	—	C	"	1
		(2.2+6.7)	—	—	—	—	—	—	C	"	1
15671	Type 4367	8.9 K	20	45	4	1 1/4	—	To Pigtails with Pigtail Tap	C	"	1
		(6.7K+2.2K)	—	—	—	—	—	—	C	"	1
1039	Type 1039	9 K	5	15	3	3/8	—	To Ferrules	C	"	1
1590	Type 1590	9 K	5	6	2	1/8	—	Wire Ends	C	"	2
9544	Type 2795	10 K	+0-5	280	8 3/4	1 1/8	—	To Ferrules	C	"	1
9818	Type 304	10 K	5	100	9 3/4	1 1/8	—	To Ferrules	C	"	1
7520	Type 7520	10 K	5	65	7 1/4	1 1/8	—	To Ferrules	C	"	1
1119	Type 1119	10 K	5	50	6 1/4	1 1/8	—	Screw Base	C	"	1
1070	Type 1070	10 K	5	25	3 1/2	7/8	—	To Clamping Ring Bands	C	"	1
7247	Type 7247	10 K	5	25	4 3/4	1 1/8	—	To Pigtails	C	"	1
8899	Type 207	10 K	5	150	—	—	—	To Ferrules	C	"	1
1589	Type 1589	10 K	5	25	3 1/2	7/8	—	To Pigtails with Pigtail Tap	C	"	1
15508	Type 4217	(5K + 5K) 10 K	10	45	—	—	—	To Ferrules	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Connection	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)	Bore (inches)				
1	RESISTORS—cont.										
	Fixed—cont.										
	Wire-wound—cont.										
	Vitreous—cont.										
15780	Type 4464	10 K	5	20	4 1/8	1/8	—	Terminal Bands To Pigtails (Anchored by 1 Turn)	C	each	1
1218	Type 1218	10 K	10	20	—	1/8	—	Terminal Bands Pigtails Anchored To Pigtails with Pigtails Tap	C	"	2
15518	Type 4227	10 K	10	15	4 1/8	1/8	—	Terminal Bands Pigtails Anchored To Pigtails with Pigtails Tap	C	"	2
10579	Type 3457	10 K	10	15	—	1/8	—	Terminal Bands Pigtails Anchored To Pigtails with Pigtails Tap	C	"	2
7410	Type 7410	10 K	5	15	2	3/8	—	Terminal Bands Pigtails Anchored To Pigtails with Pigtails Tap	C	"	2
1355	Type 1355	10 K	5	15	2	3/8	—	Terminal Bands Pigtails Anchored To Pigtails with Pigtails Tap	C	"	2
6928	Type 6928	10 K	5	—	—	—	—	Terminal Bands Pigtails Anchored To Pigtails with Pigtails Tap	C	"	2
15609	Type 4305	10 K	10	10-20	—	—	—	Terminal Bands Pigtails Anchored To Pigtails with Pigtails Tap	C	"	1
15952	Type 4633	10 K	5	7 1/2	1 1/4	1/8	—	Terminal Bands Pigtails Anchored To Pigtails with Pigtails Tap	C	"	2
15495	Type 4204	10 K	5	7 1/2	—	—	—	Terminal Bands Pigtails Anchored To Pigtails with Pigtails Tap	C	"	1
6493	Type 6493	10 K	5	6	1 3/4	1/8	—	Terminal Bands Pigtails Anchored To Pigtails with Pigtails Tap	C	"	2
7970	Type 7970	10 K	10	6	2	1/4	—	Terminal Bands Pigtails Anchored To Pigtails with Pigtails Tap	C	"	2
15127	Type 3836	10 K	10	3	Miniature	—	—	Terminal Bands Pigtails Anchored To Pigtails with Pigtails Tap	C	"	1
1214	Type 1214	10 K	10	3	1 3/8	3/8	—	Terminal Bands Pigtails Anchored To Pigtails with Pigtails Tap	C	"	2
15720	Type 4415	10 K	—	—	—	—	—	Terminal Bands Pigtails Anchored To Pigtails with Pigtails Tap	C	"	1
182	Type 650	11 K	5	15	2	3/8	—	Terminal Bands Pigtails Anchored To Pigtails with Pigtails Tap	C	"	1
6670	Type 6670	12 K	2	12	Miniature	—	—	Terminal Bands Pigtails Anchored To Pigtails with Pigtails Tap	C	"	1
15277	Type 3986	12 K	10	6	1 1/2	3/8	—	Terminal Bands Pigtails Anchored To Pigtails with Pigtails Tap	C	"	2
15691	Type 4386	12 K	10	3	1 3/8	3/8	—	Terminal Bands Pigtails Anchored To Pigtails with Pigtails Tap	C	"	2
10794	Type 3579	12 K	5	3	1 3/4	3/8	—	Terminal Bands Pigtails Anchored To Pigtails with Pigtails Tap	C	"	2
8599	Type 2107	12 K	5	3	1 3/8	3/8	—	Terminal Bands Pigtails Anchored To Pigtails with Pigtails Tap	C	"	2
15192	Type 3901	12.5 K	5	100	—	—	—	Terminal Bands Pigtails Anchored To Pigtails with Pigtails Tap	C	"	1
575	Type 822	12.5 K	5	20	5	1/2	—	Terminal Bands Pigtails Anchored To Pigtails with Pigtails Tap	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Connection	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)	Bore (inches)				
1	RESISTORS—cont. Fixed—cont. Wire-wound—cont. Vitreous—cont.										
15530	Type 4239	12.5 K	10	7½	1	¼	—	To Ferrules Wire Ends	C	each	1
7984	Type 7984	12.5 K	5	3	5¼	1 1/16	—	To Bands or Ferrules with Band Tap	C	"	2
1046	Type 1046	14 K (12 K + 2 K)	5	45	—	—	—		C	"	1
16429	Type 5009	14 K	2	6	—	—	—	—	C	"	1
15527	Type 4236	15 K	5	25	—	—	—	To Ferrules	C	"	1
9863	Type 324	15 K	5	25	3½	¾	—	To Pigtails	C	"	1
15511	Type 4220	15 K	20	20	—	—	—	To Pigtails	C	"	1
15454	Type 4163	15 K	5	15	2 1/16	¾	—	Terminal Bands	C	"	1
15337	Type 4046	15 K	10	10	—	—	—	Wire Leads	C	"	2
7130	Type 7130	15 K	2	10	2 1/8	5/16	—	Wire Leads	C	"	2
8576	Type 2084	15 K	20	6	1 1/4	3/16	—	Wire Ends	C	"	2
8202	Type 8202	15 K	10	6	1 1/4	3/16	—	Wire Ends	C	"	2
1971	Type 1971	15 K	5	6	2	1/4	—	Wire Ends	C	"	2
1648	Type 1648	15 K	2½	6	2	1/4	—	—	C	"	2
16419	Type 4998	16 K	10	6	—	—	—	To Ferrules	C	"	1
1154	Type 1154	18 K	5	45	5¼	1 1/16	—	Wires	C	"	2
16521	Type 5091	18 K	5	3	—	—	—	To Pigtails	C	"	1
6366	Type 6366	20 K	5	100	9 3/4	1 1/16	—	To Ferrules	C	"	1
9001	Type 2377	20 K	10	25	4 1/4	5/16	—	To Ferrules	C	"	1
7519	Type 7519	20 K	5	15	2 1/8	5/16	—	To Pigtails (Anchored by 1 turn)	C	"	2
1323	Type 1323	20 K	5	10	2 1/8	5/16	—	Wire Leads	C	"	1
758	Type 896	20 K	10	6	1 3/4	3/16	—	Wire Ends	C	"	2
7892	Type 7892	20 K	15	6	2	1/4	—	Wire Ends	C	"	2
1718	Type 1718	20 K	5	6	2	1/4	—	Wire Ends	C	"	2

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Connection	Class of Store	Denom. of Qty.	Carton Unit Qty
					Length (inches)	Diameter (inches)	Bore (inches)				
1	RESISTORS—cont. Fixed—cont. Wire-wound—cont. Vitreous—cont.										
9448	Type 2704	20 K	10	3	1 3/8	3/8	—	Wire Ends To Ferrules and Pigtails	C	each	2
6577	Type 6577	21 K	5	100	—	—	—	—	C	"	1
6861	Type 6861	22 K	5	45	5 1/4	1 1/8	—	Wire Ends To Ferrules	C	"	1
16933	Type 5443	22 K	2	12	Miniature	—	—	—	C	"	1
8131	Type 8131	22 K	5	7 1/2	Miniature	—	—	—	C	"	1
8743	Type 2193	22 K	10	6	2	—	—	Wire Ends	C	"	2
15176	Type 3885	22 K	20	3	1	—	—	Wire Ends	C	"	2
16952	Type 5461	24 K	5	7 1/2	—	—	—	—	C	"	—
15222	Type 3931	24 K	5	6	1 1/4	—	—	Wire Ends	C	"	2
7537	Type 7537	24 K	10	6	1 1/4	3/32	—	Wire Ends	C	"	2
1372	Type 1372	25 K	5	100	—	—	—	To Ferrules	C	"	1
16254	Type 4879	25 K	5	65	7 1/4	1 1/8	—	To Ferrules	C	"	1
10535	Type 3436	25 K	5	50	7 3/4	1 7/8	—	To Ferrules	C	"	1
9862	Type 323	15 K + 10 K	5	25	3 1/2	7/8	—	To Pigtails with Pigtail Tap	C	"	—
1566	Type 1566	25 K	5	15	2 3/8	—	—	To Pigtails	C	"	2
15519	Type 4228	25 K	10	15	2 1/8	1/8	—	Terminal Bands	C	"	2
8753	Type 2203	25 K	10	12	Miniature	—	—	—	C	"	2
15198	Type 3907	25 K	5	10	2 3/8	—	—	To Pigtails	C	"	1
6830	Type 6830	25 K	10	6	2	—	—	Wire Ends	C	"	1
15483	Type 4192	25 K	10	6	—	—	—	—	C	"	2
1972	Type 1972	25 K	5	6	2	—	—	Wire Ends	C	"	1
15748	Type 4438	25 K	20	6	1 3/4	—	—	Wire Ends	C	"	2
10849	Type 3607	25 K	2	4	—	—	—	—	C	"	2
10855	Type 3608	25 K	2	4	—	—	—	—	C	"	2
15380	Type 4089	25 K	5	3	Miniature	—	—	—	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Connection	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)	Bore (inches)				
1	RESISTORS—cont. Fixed—cont. Wire-wound—cont. Vitreous—cont.										
1738	Type 1738	25 K	—	3	—	—	—	—	C	each	1
15115	Type 3824	25 K	10	3	1 3/8	1/8	—	Side Wires	C	"	2
15137	Type 3846	25 K	5	3	1 3/8	1/8	—	Wire Ends	C	"	2
15398	Type 4107	25 K	20	3	1 3/8	1/8	—	Wire Ends	C	"	2
15929	Type 4610	27 K	10	6	1 3/4	—	—	Wire Ends	C	"	2
1250	Type 1250	30 K	10	—	—	—	—	Cap Ends	C	"	1
1429	Type 1429	30 K	—	—	—	—	—	Cap Ends	C	"	1
9007	Type 2383	30 K	5	15	2	3/4	—	To Bands	C	"	2
7581	Type 7581	30 K	5	15	—	—	—	(Clamping Ring)	C	"	—
7737	Type 7737	30 K	10	10	2 3/8	1/2	—	To Pigtails	C	"	2
15199	Type 3908	30 K	5	10	2 3/8	1/2	—	Wire Leads	C	"	1
15463	Type 4172	30 K	5	7 1/2	—	—	—	To Pigtails	C	"	1
16077	Type 4733	30 K	10	7 1/2	—	—	—	Wire Ends	C	"	1
7891	Type 7891	30 K	15	6	2	1/4	—	Wire Ends	C	"	2
761	Type 899	32 K	10	15	2	3/4	—	To Pigtails (may be anchored by 1 turn)	C	"	2
15656	Type 4352	33 K	10	15	2	3/4	—	To Bands (Clamping Ring)	C	"	2
16401	Type 4982	33 K	10	12	Miniature	—	—	—	C	"	1
16455	Type 5033	33 K	10	12	—	—	—	—	C	"	1
16389	Type 5060	33 K	5	7 1/2	—	—	—	—	C	"	1
16388	Type 4970	33 K	10	6	—	—	—	—	C	"	1
8744	Type 2194	33 K	10	6	2	1/4	—	Wire Ends	C	"	2
10104	Type 363	34 K	5	100	9 1/4	1 1/8	—	To Ferrules	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Connection	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)	Bore (inches)				
1	RESISTORS—cont. Fixed—cont. Wire-wound—cont. Vitreous—cont.										
6365	Type 6365	35 K	5	100	—	—	—	To Ferrules and Pigtails	C	each	1
15610	Type 4306	35 K	10	10-20	—	—	—	Wire Leads	C	"	1
6674	Type 6674	35 K	5	10	2 1/4	1 1/2	—	Wire Leads	C	"	2
15104	Type 3813	39 K	5	10	2 1/4	1 1/2	—	Wire Leads	C	"	2
16563	Type 5131	39 K	5	7.5	—	—	—	Wire Leads	C	"	1
1599	Type 1599	40 K	5	100	9 1/4	1 1/8	—	To Ferrules	C	"	1
15194	Type 3903	40 K	5	100	—	—	—	To Ferrules	C	"	1
10069	Type 350	40 K	5	50	7 3/4	1 3/16	—	To Ferrules	C	"	1
15657	Type 4353	40 K	10	15	2	3/4	—	To Bands	C	"	2
759	Type 897	40 K	5	10	—	—	—	(Clamping Ring) Pigtails Anchored	C	"	1
8132	Type 8132	40 K	10	6	2	1/4	—	Wire Leads	C	"	2
16953	Type 5462	40 K	5	7 1/2	—	—	—	Wire Leads	C	"	1
16382	Type 4964	40 K	5	6	—	—	—	Wire Leads	C	"	1
15069	Type 3778	45 K	1	6	—	—	—	Wire Leads	C	"	1
15497	Type 4206	47 K	10	10	—	—	—	Wire Leads	C	"	1
15103	Type 3812	47 K	5	10	2 3/8	1 1/2	—	Wire Leads	C	"	2
15225	Type 3934	47 K	20	10	2 3/8	1 1/2	—	Wire Leads	C	"	2
16405	Type 4986	47 K	10	7 1/2	—	—	—	Wire Leads	C	"	1
16387	Type 4969	47 K	5	6	—	—	—	Wire Leads	C	"	1
15385	Type 4094	47 K	10	3	Miniature	—	—	Side Wires	C	"	2
15623	Type 4319	47 K	20	3	1 3/4	5/16	—	Wire Leads	C	"	2
6367	Type 6367	50 K	5	100	1 3/4	3/16	—	To Pigtails	C	"	1
338	Type 752	50 K	5	45	9 1/4	1 1/8	—	To Pigtails (may be anchored by 1 turn)	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value In Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Connection	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)	Bore (inches)				
1	RESISTORS—cont. Fixed—cont. Wire-wound—cont. Vitreous—cont.										
16425	Type 5005	50 K	10	25	—	—	—	—	C	each	1
8477	Type 2027	50 K	15	10	2 $\frac{3}{8}$	$\frac{1}{2}$	—	—	C	"	5
15374	Type 4083	50 K	10	7 $\frac{1}{2}$	Miniature	—	—	—	C	"	1
7890	Type 7890	50 K	15	6	2	$\frac{1}{4}$	—	—	C	"	2
1719	Type 1719	50 K	5	6	2	$\frac{1}{4}$	—	—	C	"	2
15729	Type 4423	56 K	20	$\frac{1}{2}$	—	—	—	—	C	"	1
15327	Type 4036	56 K	—	12/13	Miniature	—	—	—	C	"	2
15102	Type 3811	56 K	5	6	2 $\frac{3}{8}$	$\frac{1}{16}$	—	—	C	"	2
9367	Type 2658	60 K	5	65	7 $\frac{1}{4}$	$\frac{1}{16}$	—	—	C	"	1
6932	Type 6932	60 K	5	15	2 $\frac{1}{2}$	$\frac{3}{8}$	—	—	C	"	2
15658	Type 4354	60 K	10	15	2	$\frac{3}{4}$	—	—	C	"	2
6447	Type 6447	65 K	10	6	2	$\frac{1}{4}$	—	—	C	"	2
16074	Type 4730	70 K	5	7 $\frac{1}{2}$	2	$\frac{1}{4}$	—	—	C	"	2
1336	Type 1336	75 K	5	100	9 $\frac{3}{4}$	$\frac{1}{16}$	—	—	C	"	1
1045	Type 1045	75 K	5	25	4 $\frac{1}{2}$	$\frac{1}{16}$	—	—	C	"	1
15938	Type 4619	75 K	5	6	2	$\frac{1}{4}$	—	—	C	"	1
7442	Type 7442	79 K	5	100	9 $\frac{1}{4}$	$\frac{1}{16}$	—	—	C	"	1
16046	Type 4714	90 K	10	35-65	2	$\frac{1}{16}$	—	—	C	"	1
16088	Type 4744	90 K	10	15	—	—	—	—	C	"	1
16207	Type 4835	90 K	10	25	—	—	—	—	C	"	1
8200	Type 8200	100 K	5	100	—	—	—	—	C	"	1
9823	Type 309	100 K	5	100	—	—	—	—	C	"	1
15520	Type 4929	100 K	10	15	9 $\frac{3}{4}$	$\frac{1}{16}$	—	—	C	"	2
7889	Type 7889	100 K	15	6	2 $\frac{1}{8}$	$\frac{1}{16}$	—	—	C	"	2
8133	Type 8133	100 K	10	6	2	$\frac{1}{4}$	—	—	C	"	2

RADIO RESISTORS

Ref. No.	Nomenclature	Value in Ohms per Section			Wattage	Element	Grading	Diameter (inches)	Spindle Length (inches)	Class of Store	Denom. of Qty.	Carton Unit Qty.
		1	2	3								
1												
	RESISTORS—cont.											
	Variable ganged potentiometers:—											
18014	Type 9392	9.04	9.04	9.04	—	Wirewound	—	—	—	C	each	—
17083	Type 5540	13.4	13.4	—	—	Wirewound	—	—	—	C	—	1
18010	Type 9388	80	160	320	4.5	Wirewound	+2½% each tube	—	—	C	—	—
18011	Type 9389	80	160	320	4.5	Wirewound	+2½% each tube	—	—	C	—	—
18015	Type 9393	88	88	88	—	Carbon	Linear	—	—	C	—	—
10679	Type 3517	100	100	100	1½	Wirewound	±10%	¼	1	C	—	5
8942	Type 2346	100	1,000	—	3	Wirewound	—	¼	—	C	—	—
18016	Type 9394	120	120	—	—	Wirewound	—	—	—	C	—	—
15262	Type 3971	137	137	—	1.2	Wirewound	—	—	—	C	—	—
18017	Type 9395	195	195	—	—	Wirewound	—	—	—	C	—	—
8462	Type 2017	200	200	—	200	Wirewound	—	—	—	C	—	—
15705	Type 4400	200	200	—	100	Wirewound	—	—	—	C	—	—
16316	Type 4932	277	277	277	—	Wirewound	—	—	—	C	—	—
6878	Type 6878	400	50,000	—	—	—	—	—	—	C	—	—
16317	Type 4933	605	605	—	—	Wirewound	—	—	—	C	—	—
17916	Type 9400	787.7	1,002.6	—	4.5	Wirewound	+2½%	—	—	C	—	—
16792	Type 5308	900	500	—	—	Wirewound	—	—	—	C	—	—
9149	Type 2499	1,000	1,000	—	—	Wirewound	—	—	—	C	—	—
16359	Type 4949	2,000	2,000	—	30	Wirewound	+½%	—	—	C	—	—
15796	Type 4480	2,000	2,000	—	2	Carbon	—	—	—	C	—	—
10915	Type 3636	2,500	2,500	—	—	Wirewound	—	—	—	C	—	—
6122	Type 6122	2,500	2,500	—	—	Wirewound	—	—	—	C	—	—
16863	Type 5373	3,000	3,000	—	4	Wirewound	Linear	—	—	C	—	—
6164	Type 6164	3,000	100,000	—	1½	Carbon	Linear	—	—	C	—	—
16463	Type 5036	5,000	5,000	—	—	Wirewound	—	—	—	C	—	—
17811	Type 9254	5,000	5,000	—	15	Wirewound	±5%	—	—	C	—	—
16545	Type 5115	5,000	25,000	—	5	Wirewound	±5%	—	—	C	—	—
15578	Type 4283	10,000	100,000	—	15	Wirewound	—	—	—	C	—	—

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms per Section			Wattage	Element	Grading	Diameter (inches)	Spindle Length (inches)	Class of Store	Denom. of Qty.	Carton Unit Qty.
		1	2	3								
1	RESISTORS—cont. Variable ganged potentiometers —cont.											
16515	Type 5058	10,000	10,000	—	3-4	Wirewound	—	—	1	C	each	1
15831	Type 4514	25,000	25,000	—	2	Carbon	Linear	1/4	1	C	"	1
15215	Type 3924	25,000	25,000	—	5	Wirewound	—	—	1/8	C	"	1
16073	Type 4729	25,000	25,000	—	3	Wirewound	Linear	—	5/8 slotted	C	"	1
6126	Type 6126	35,000	250,000	—	1 1/2	Carbon	Linear	—	—	C	"	1
16084	Type 4740	50,000	50,000	—	1 1/2	Carbon	±20%	1/4	1 1/8	C	"	1
16806	Type 5322	50,000	50,000	—	1 1/2	Carbon	±20%	1/4	1 1/8	C	"	1
15124	Type 3833	50,000	50,000	—	2	Carbon	±20%	1/4	1/2	C	"	1
16619	Type 5178	50,000	50,000	—	4	—	±5%	—	—	C	"	—
16106	Type 4757	50,000	50,000	—	1 1/2	Carbon	—	1/4	3 1/8	C	"	1
16090	Type 4746	50,000	50,000	—	4	Wirewound	—	1/4	7/8	C	"	1
6897	Type 6897	50,000	50,000	—	—	—	—	—	—	C	"	1
1000	Type 1000	50,000	500,000	—	1 1/2	Wirewound	—	1/4	—	C	"	1
8312	Type 8312	100,000	100,000	—	5	Carbon	±10%	1/4	2 1/8	C	"	1
16262	Type 4883	100,000	100,000	—	2	—	±5%	—	—	C	"	1
15123	Type 2832	100,000	100,000	—	2	Carbon	±20%	1/4	1 1/2	C	"	1
15975	Type 4479	100,000	100,000	—	15	Carbon	±10%	1/4	1	C	"	1
8706	Type 2168	200,000	100,000	100000	2	Carbon	±10%	—	—	C	"	1
16428	Type 5008	500 K	500 K	—	—	—	—	—	—	C	"	1
16299	Type 4917	500 K	500 K	—	—	Carbon	Linear	—	3/16	C	"	1
7986	Type 7986	500,000	500,000	—	2	Carbon	±10%	1/4	1/16	C	"	1
6127	Type 6127	500,000	2 meg.	—	—	Carbon	±15%	—	—	C	"	1
1517	Type 1517	1 meg.	1 meg.	—	—	Carbon	Linear	—	7/16	C	"	1
986	Type 986	2 meg.	2 meg.	—	1 1/2	Carbon	—	—	1/8	C	"	1
1103	Type 1103	2 meg.	2 meg.	—	—	Carbon	—	—	—	C	"	1

SECTION 10W—*cont.*

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms per Section			Wattage	Element	Grading	Diameter (inches)	Spindle Length (inches)	Class of Store	Denom. of Qty.	Carton Unit Qty.
		1	2	3								
1	2	3	4	5	6	7	8	9	10	11	12	13
	RESISTORS—<i>cont.</i> Variable ganged potentiometers —<i>cont.</i>											
1357	Type 1357	2 meg.	2 meg.	—	1½	Carbon	—	—	¾	C	each	1
15877	Type 4560	2 meg.	2 meg.	—	2	Carbon	—	—	¾	C	"	1
6125	Type 6125	2 meg.	2 meg.	—	—	Carbon	—	—	¾	C	"	1
15540	Type 4249	2 M	2 M	—	—	Carbon	± 10%	—	1	C	"	1
1286	Type 1286	2 M	2 M	—	1½	Carbon	Linear	¾	1	C	"	—
17867	Type 9308	5 M	5 M	—	½	Carbon	Linear	¾	1	C	"	—

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ± %	Wattage	DIMENSIONS AND DETAILS OF BODY		Other Details	DIMENSIONS AND DETAILS OF SPINDLE		Class of Store	Denom. of Qty.	Carton Unit Qty.	
					Dia. (inches)	Depth (inches)		Dia. (inches)	Length (inches)				
1	2	3	4	5	6	7	8	9	10	11	12	13	14
	RESISTORS—cont. Variable potentiometers—cont. Carbon composition element:												
7405	Type 7405 ...	30	10	1½	1 11/16	31/16	—	1 1/4	1 1/8	Plain	C	each	1
15157	Type 3866 ...	200	20	2	1 11/16	31/16	3 tags	1 1/4	1 1/8	Slotted	C	"	1
16208	Type 4836 ...	200	20	2	—	—	—	1 1/4	1 1/8	Slotted	C	"	1
17043	Type — ...	220	20	—	—	—	—	—	—	—	C	"	—
15572	Type 4278 ...	300	—	—	—	—	—	—	—	—	C	"	—
15666	Type 4362 ...	500	—	—	—	—	—	—	—	—	C	"	—
348	Type 755 ...	500	20	—	—	—	3 tags	—	—	—	C	"	—
8077	Type 8077 ...	500	—	2	1 1/16	31/16	—	1 1/4	1 1/8	Slotted	C	"	1
7368	Type 7368 ...	500	20	1½	—	—	—	—	—	with 3/8 in. flat	C	"	1
15122	Type 3831 ...	500	20	1½	—	—	—	—	—	Plain	C	"	1
16155	Type 4802 ...	500	20	1½	—	—	—	—	—	Slotted	C	"	1
16762	Type 5279 ...	500	20	1½	—	—	—	—	—	Slotted	C	"	1
16756	Type 5273 ...	500	20	1½	—	—	—	—	—	Plain	C	"	1
8990	Type 2367 ...	500	20	1½	—	—	—	—	—	Slotted	C	"	1
1551	Type 1551 ...	500	10	—	1 3/16	7/16	3 tags	—	—	Slotted	C	"	1
10667	Type 3506 ...	500	20	—	—	—	3 tags	—	—	—	C	"	1
15009	Type 3718 ...	500	20	—	—	—	3 tags	—	—	—	C	"	1
16076	Type 4732 ...	500	20	—	—	—	3 tags	—	—	—	C	"	1
15956	Type 4637 ...	500	20	—	—	—	3 tags	—	—	—	C	"	1
15506	Type 4215 ...	500	20	—	—	—	3 tags	—	—	—	C	"	1
10098	Type 3145 ...	500	20	—	—	—	3 × 1/2 in. solder pins	—	—	—	C	"	1
16171	Type 4816 ...	1K	10	—	—	—	—	—	—	—	C	"	5
15113	Type 3822 ...	1,000	20	—	—	—	—	—	—	—	C	"	1
17563	Type 9018 ...	1,000	10	—	—	—	—	—	—	—	C	"	1
10960	Type 3675 ...	1,000	20	—	—	—	3 tags	—	—	—	C	"	3
16213	Type 4841 ...	1,000	20	—	—	—	3 tags	—	—	—	C	"	1
8991	Type 2368 ...	1,000	20	—	—	—	3 tags	—	—	—	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ± %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Dia. (inches)	Depth (inches)	Other Details	Dia. (inches)	Length (inches)	Other Details			
1	RESISTORS—cont. Variable potentiometers—cont. Carbon composition element —cont.												
7142	Type 7142 ...	1,000	10	$\frac{1}{2}$	$1\frac{11}{16}$	$\frac{1}{16}$	3 tags	$\frac{1}{4}$	$1\frac{11}{16}$	Plain	C	each	1
9560	Type 2811 ...	1,000	20	$\frac{1}{2}$	—	—	—	$\frac{1}{4}$	$\frac{11}{16}$	Slotted	C	"	1
15271	Type 3980 ...	1,000	20	$\frac{1}{2}$	—	—	—	$\frac{1}{4}$	$\frac{11}{16}$	Slotted	C	"	1
16424	Type 5004 ...	1,000	20	$\frac{1}{2}$	—	—	—	—	$\frac{11}{16}$	Plain	C	"	1
9336	Type 2637 ...	1,000	20	$\frac{1}{2}$	—	—	—	—	$\frac{11}{16}$	Standard	C	"	1
15097	Type 3806 ...	1,000	20	$\frac{1}{2}$	—	—	—	—	$2\frac{1}{2}$	Plain	C	"	1
6896	Type 6896 ...	1,000	20	$\frac{1}{2}$	—	—	—	—	$1\frac{1}{8}$	Slotted	C	"	1
8085	Type 8085 ...	1,000	10	$\frac{1}{2}$	$1\frac{1}{16}$	$\frac{31}{32}$	3 tags	$\frac{1}{4}$	$1\frac{1}{8}$	Slotted	C	"	1
6161	Type 6161 ...	1,000	10	$\frac{1}{2}$	$1\frac{1}{16}$	$\frac{31}{32}$	3 tags	$\frac{1}{4}$	$1\frac{1}{8}$	Slotted	C	"	1
6863	Type 6863 ...	1,000	20	$\frac{1}{2}$	$1\frac{1}{16}$	$\frac{31}{32}$	3 solder pins	$\frac{1}{4}$	$1\frac{1}{8}$	Plain	C	"	1
10612	Type 3486 ...	1,000	20	$\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	3 solder pins	$\frac{1}{4}$	$1\frac{1}{8}$	Slotted	C	"	1
10692	Type 3525 ...	1,000	20	$\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	3 solder pins	$\frac{1}{4}$	$1\frac{1}{8}$	Plain	C	"	1
10919	Type 3640 ...	1,000	20	$\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	3 solder pins	$\frac{1}{4}$	$1\frac{1}{8}$	Plain	C	"	1
15098	Type 3807 ...	1,000	20	$\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	3 solder pins	$\frac{1}{4}$	$1\frac{1}{8}$	Plain	C	"	1
9337	Type 2638 ...	1,000	20	$\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	3 solder pins	$\frac{1}{4}$	$1\frac{1}{8}$	Plain	C	"	1
9453	Type 2709 ...	1,500	20	$\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	3 tags	$\frac{1}{4}$	$1\frac{1}{8}$	Flattened with $\frac{3}{8}$ in. flat	C	"	1
6383	Type 6383 ...	1,500	10	$\frac{1}{2}$	—	—	—	$\frac{1}{4}$	$1\frac{1}{8}$	Slotted	C	"	1
8107	Type 8107 ...	1,500	20	$\frac{1}{2}$	—	—	—	$\frac{1}{4}$	$1\frac{1}{8}$	Slotted	C	"	1
17372	Type 5829 ...	1,500	20	$\frac{1}{2}$	—	—	—	$\frac{1}{4}$	$1\frac{1}{8}$	Plain	C	"	1
8026	Type 8026 ...	2 K	20	$\frac{1}{2}$	$1\frac{1}{32}$	$\frac{7}{16}$	3 tags $\frac{7}{16}$ in. long	$\frac{1}{4}$	$1\frac{1}{8}$	Slotted	C	"	1
16109	Type 4758 ...	2 K	20	$\frac{1}{2}$	$1\frac{1}{16}$	—	—	$\frac{1}{4}$	$1\frac{1}{8}$	Slotted	C	"	1
15430	Type 4139 ...	2 K	10	$\frac{1}{2}$	$1\frac{1}{16}$	$\frac{31}{32}$	3 tags	$\frac{1}{4}$	$1\frac{1}{8}$	Slotted	C	"	1
16080	Type 4736 ...	2 K	20	$\frac{1}{2}$	—	—	—	$\frac{1}{4}$	$1\frac{1}{8}$	—	C	"	1
16646	Type 5185 ...	2 K	20	$\frac{1}{2}$	—	—	—	$\frac{1}{4}$	$1\frac{1}{8}$	—	C	"	1
16599	Type 5157 ...	2 K	20	$\frac{1}{2}$	—	—	—	$\frac{1}{4}$	$1\frac{1}{8}$	—	C	"	1
16599	Type 5159 ...	2 K	20	$\frac{1}{2}$	—	—	—	$\frac{1}{4}$	$1\frac{1}{8}$	Plain	C	"	1

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ± %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Dia. (inches)	Depth (inches)	Other Details	Dia. (inches)	Length (inches)	Other Details			
1	RESISTORS—cont. Variable potentiometers—cont. Carbon composition element—cont.												
10836	Type 3602 ...	2 K	—	—	—	—	—	—	—	—	—	—	—
7941	Type 7941 ...	2 K	20	1 1/8	3/16	3 tags	—	—	1 3/4	Plain With 1/8 in. flat	C	each	1
8613	Type 2119 ...	2 K	20	1 1/8	3/16	3 tags	—	—	1 7/8	Slotted	C	"	1
8113	Type 8113 ...	2 K	20	1 1/8	3/16	3 tags	—	—	1 5/8	Slotted	C	"	1
15889	Type 4571 ...	2 K	20	1 1/8	3/16	3 tags	—	—	1 5/8	Slotted	C	"	1
15663	Type 4359 ...	2 K	20	1 1/8	3/16	3 solder pins 1/2 in. long	—	—	1	Plain	C	"	1
15413	Type 4122 ...	2 K	20	2	1/8	—	—	—	2 1/8	—	C	"	1
15842	Type 4525 ...	2 K	20	2	1/8	3 tags	—	—	2 1/8	Plain Slotted	C	"	1
15665	Type 4361 ...	2 K	20	2	1/8	—	—	—	2 1/8	—	C	"	1
6348	Type 6348 ...	2.5 K	20	1	—	—	—	—	1 1/8	—	C	"	1
9335	Type 2636 ...	2.5 K	10	1	3/16	3 tags	—	—	1 1/8	Plain	C	"	1
15041	Type 3750 ...	2.5 K	5	1	—	—	—	—	1 1/8	Slotted	C	"	5
16761	Type 5278 ...	2.5 K	20	1	—	—	—	—	1 1/8	Plain	C	"	1
846	Type 2016 ...	2.5 K	20	1	—	—	—	—	1 1/8	Slotted	C	"	1
16383	Type 4965 ...	2.5 K	20	1	—	—	—	—	1 1/8	Plain	C	"	1
16381	Type 4963 ...	2.5 K	20	1	—	—	—	—	1 1/8	Slotted	C	"	1
15338	Type 4047 ...	2.5 K	20	1	—	—	—	—	1 1/8	With 1/2 in. flat	C	"	1
15605	Type 4301 ...	3 K	20	1	—	—	—	—	1 1/8	1/2 in. × 7/8 in. flat	C	"	1
8285	Type 8285 ...	3 K	15	1	—	—	—	—	1 7/8	—	C	"	1
8832	Type 2263 ...	3 K	15	1	—	—	—	—	1 7/8	Plain	C	"	1
16471	Type 5044 ...	3 K	20	1	—	—	—	—	1 7/8	Plain	C	"	1
8357	Type 8357 ...	3 K	20	1	—	—	—	—	1 7/8	Slotted	C	"	1
6883	Type 6883 ...	5 K	20	1	—	—	—	—	1 7/8	Plain	C	"	1
8071	Type 8071 ...	5 K	20	1	—	—	—	—	1 7/8	1 1/2 in. × 5/8 in.	C	"	1
9645	Type 2877 ...	5 K	20	1	—	—	—	—	1 7/8	Slotted	C	"	1
9333	Type 2634 ...	5 K	10	1	—	—	—	—	1 7/8	Slotted	C	"	1

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ± %	Wattage	DIMENSIONS AND DETAILS OF BODY		Other Details	DIMENSIONS AND DETAILS OF SPINDLE		Class of Store	Denom. of Qty.	Carton Unit Qty.	
					Dia. (inches)	Depth (inches)		Dia. (inches)	Length (inches)				
1	2	3	4	5	6	7	8	9	10	11	12	13	14
RESISTORS—cont. Variable potentiometers—cont. Carbon composition element—cont.													
1643	Type 1643 ...	5 K	10	$\frac{1}{2}$	$1\frac{11}{16}$	$\frac{1}{16}$	3 tags	$\frac{1}{4}$	$\frac{3}{8}$	Slotted	C	each	1
17616	Type 9069 ...	5 K	20	$\frac{1}{2}$	$1\frac{11}{16}$	$\frac{1}{16}$	3 tags	$\frac{1}{4}$	$\frac{3}{8}$	Slotted	C	"	3
8996	Type 2372 ...	5 K	20	$\frac{1}{2}$	$1\frac{11}{16}$	$\frac{1}{16}$	3 tags	$\frac{1}{4}$	$\frac{3}{8}$	Flatted	C	"	1
15515	Type 4224 ...	5 K	20	$\frac{1}{2}$	$1\frac{11}{16}$	$\frac{1}{16}$	3 tags	$\frac{1}{4}$	$\frac{3}{8}$	Plain	C	"	1
16670	Type 5195 ...	5 K	10	$\frac{1}{2}$	$1\frac{11}{16}$	$\frac{1}{16}$	3 tags	$\frac{1}{4}$	$\frac{3}{8}$	With $\frac{3}{8}$ slot	C	"	1
16110	Type 4759 ...	5 K	20	$\frac{1}{2}$	$1\frac{11}{16}$	$\frac{1}{16}$	3 tags	$\frac{1}{4}$	$\frac{3}{8}$	With $\frac{3}{8}$ in. flat	C	"	1
15280	Type 3789 ...	5 K	20	$\frac{1}{2}$	$1\frac{11}{16}$	$\frac{1}{16}$	3 tags	$\frac{1}{4}$	$\frac{3}{8}$	—	C	"	1
15364	Type 4073 ...	5 K	20	$\frac{1}{2}$	$1\frac{11}{16}$	$\frac{1}{16}$	3 tags	$\frac{1}{4}$	$\frac{3}{8}$	—	C	"	1
15627	Type 4323 ...	5 K	20	$\frac{1}{2}$	$1\frac{11}{16}$	$\frac{1}{16}$	3 solder pins $\frac{1}{2}$ in.	$\frac{1}{4}$	$\frac{3}{8}$	Slotted	C	"	1
1230	Type 1230 ...	5 K	10	$\frac{1}{2}$	$1\frac{11}{16}$	$\frac{1}{16}$	3 tags	$\frac{1}{4}$	$\frac{3}{8}$	Plain	C	"	1
1229	Type 1229 ...	5 K	10	$\frac{1}{2}$	$1\frac{11}{16}$	$\frac{1}{16}$	3 tags	$\frac{1}{4}$	$\frac{3}{8}$	Slotted	C	"	1
8097	Type 8097 ...	5 K	10	$\frac{1}{2}$	$1\frac{11}{16}$	$\frac{1}{16}$	3 tags	$\frac{1}{4}$	$\frac{3}{8}$	Slotted	C	"	1
8778	Type 2228 ...	5 K	10	$\frac{1}{2}$	$1\frac{11}{16}$	$\frac{1}{16}$	3 solder pins $\frac{1}{2}$ in.	$\frac{1}{4}$	$\frac{3}{8}$	Plain	C	"	1
15121	Type 3830 ...	5 K	10	$\frac{1}{2}$	$1\frac{11}{16}$	$\frac{1}{16}$	3 solder pins $\frac{1}{2}$ in.	$\frac{1}{4}$	$\frac{3}{8}$	Slotted	C	"	1
16105	Type 4756 ...	5 K	20	$\frac{1}{2}$	$1\frac{11}{16}$	$\frac{1}{16}$	3 tags	$\frac{1}{4}$	$\frac{3}{8}$	Plain	C	"	1
16355	Type 4945 ...	5 K	20	$\frac{1}{2}$	$1\frac{11}{16}$	$\frac{1}{16}$	3 solder pins $\frac{1}{2}$ in.	$\frac{1}{4}$	$\frac{3}{8}$	Slotted	C	"	1
10663	Type 3505 ...	5 K	20	$\frac{1}{2}$	$1\frac{11}{16}$	$\frac{1}{16}$	3 tags	$\frac{1}{4}$	$\frac{3}{8}$	—	C	"	1
7313	Type 7313 ...	5 K	20	$\frac{1}{2}$	$1\frac{11}{16}$	$\frac{1}{16}$	3 tags	$\frac{1}{4}$	$\frac{3}{8}$	Slotted	C	"	1
1912	Type 1912 ...	5 K	20	$\frac{1}{2}$	$1\frac{11}{16}$	$\frac{1}{16}$	3 tags	$\frac{1}{4}$	$\frac{3}{8}$	Slotted	C	"	1
1083	Type 1083 ...	5 K	20	$\frac{1}{2}$	$1\frac{11}{16}$	$\frac{1}{16}$	3 tags	$\frac{1}{4}$	$\frac{3}{8}$	Plain	C	"	1
7942	Type 7942 ...	5 K	20	$\frac{1}{2}$	$1\frac{11}{16}$	$\frac{1}{16}$	3 tags	$\frac{1}{4}$	$\frac{3}{8}$	With $\frac{1}{8}$ in. flat	C	"	1
7963	Type 7963 ...	5 K	20	$\frac{1}{2}$	$1\frac{11}{16}$	$\frac{1}{16}$	3 tags	$\frac{1}{4}$	$\frac{3}{8}$	Plain	C	"	1

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ± %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty
					Dia. (inches)	Depth (inches)	Other Details	Dia (inches)	Length (inches)	Other Details			
1	RESISTORS—cont. Variable potentiometers—cont. Carbon composition element—cont.												
10789	Type 3575 ...	5 K	20	1 1/4	1 3/16	3 solder pins	1/8	1 1/8	Plain	C	each	1	
8907	Type 2318 ...	5 K	20	1 1/4	1 1/16	3 solder pins	1/8	1 1/8	Slotted	C	"	1	
9315	Type 2623 ...	5 K	20	1 1/4	1 1/16	3 solder pins	1/8	1 1/8	Slotted 1/2 in. flat	C	"	1	
9205	Type 2535 ...	5 K	20	1 1/4	1 1/16	3 solder pins	1/8	1 1/8	Slotted	C	"	1	
15243	Type 3952 ...	5 K	20	1 1/4	1 1/16	3 solder pins	1/8	1 1/8	Slotted	C	"	1	
15867	Type 4550 ...	5 K	20	1 1/4	1 1/16	3 solder pins	1/8	1 1/8	Slotted	C	"	1	
15931	Type 4612 ...	5 K	20	1 1/4	1 1/16	3 solder pins	1/8	1 1/8	Slotted	C	"	1	
15004	Type 3713 ...	5 K	—	—	—	—	—	—	Plain	C	"	1	
15030	Type 3739 ...	5 K	—	—	—	—	—	—	Slotted	C	"	1	
15681	Type 4377 ...	5 K	—	—	—	—	—	—	Slotted	C	"	1	
17033	Type — ...	10 K	—	—	—	—	—	—	Slotted	C	"	3	
17042	Type — ...	10 K	—	—	—	—	—	—	Slotted	C	"	3	
190	Type 658 ...	10 K	—	—	—	—	—	—	Slotted	C	"	1	
17617	Type 9070 ...	10 K	20	1 1/4	1 1/16	3 tags 1/8 in. long	1/8	1 1/8	Slotted	C	"	3	
7097	Type 7097 ...	10 K	10	1 1/4	1 1/16	3 tags 1/8 in. long	1/8	1 1/8	Slotted	C	"	1	
17034	Type — ...	10 K	—	—	—	—	—	—	Plain	C	"	1	
15096	Type 3805 ...	10 K	20	1 1/4	1 1/16	3 tags	1/8	1 1/8	Slotted	C	"	1	
15419	Type 4128 ...	10 K	15	1 1/4	1 1/16	3 tags	1/8	1 1/8	Slotted	C	"	1	
6860	Type 6860 ...	10 K	10	1 1/4	1 1/16	3 tags	1/8	1 1/8	Plain	C	"	1	
15431	Type 4140 ...	10 K	10	1 1/4	1 1/16	3 tags	1/8	1 1/8	Slotted	C	"	1	
15470	Type 4179 ...	10 K	10	1 1/4	1 1/16	3 tags	1/8	1 1/8	Slotted	C	"	1	
7366	Type 7366 ...	10 K	10	1 1/4	1 1/16	3 tags	1/8	1 1/8	Plain	C	"	1	
6137	Type 6137 ...	10 K	10	1 1/4	1 1/16	3 tags	1/8	1 1/8	Slotted	C	"	1	
9739	Type 2960 ...	10 K	10	1 1/4	1 1/16	3 tags	1/8	1 1/8	Slotted	C	"	1	
15542	Type 4251 ...	10 K	10	1 1/4	1 1/16	3 tags	1/8	1 1/8	Slotted	C	"	1	
9228	Type 2555 ...	10 K	10	1 1/4	1 1/16	3 solder pins 1/8 in.	1/8	1 1/8	Plain	C	"	1	
15120	Type 3829 ...	10 K	10	1 1/4	1 1/16	3 solder pins 1/8 in.	1/8	1 1/8	Slotted	C	"	1	

SECTION 10W—*cont.*

RADIO RESISTORS

Ref. No.	Nomenclature	Value in Ohms	Tolerance ± %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Dia. (inches)	Depth (inches)	Other Details	Dia. (inches)	Length (inches)	Other Details			
1	RESISTORS—<i>cont.</i> Variable potentiometers—<i>cont.</i> Carbon composition element—<i>cont.</i>												
1594	Type 1594 ...	10 K	15	1 1/2	1 1/8	3 tags	1	7/8	Slotted	C	each	1	
16600	Type 5160 ...	10 K	15	1 1/2	1 1/8	3 tags	1	1 1/2	Slotted	C	"	1	
8712	Type 2174 ...	10 K	15	1 1/2	1 1/8	3 solder pins 1/2 in.	1	1	Plain	C	"	1	
16678	Type 5302 ...	10 K	15	1 1/2	1 1/8	3 tags	1	.719	Slotted	C	"	1	
10631	Type 3495 ...	10 K	20	1 1/2	1 1/8	3 tags	1	1 1/8	Slotted with .063 in. hole	C	"	1	
895	Type 950 ...	10 K	20	1 1/2	1 1/8	3 tags	1	1 1/8	Slotted with .063 in. hole	C	"	1	
1811	Type 1811 ...	10 K	—	1 1/2	1 1/8	3 tags	1	—	—	C	"	1	
10617	Type 3491 ...	10 K	20	1 1/2	1 1/8	3 solder pins	1	1 1/8	—	C	"	1	
8375	Type 8375 ...	10 K	20	1 1/2	1 1/8	3 solder pins	1	1 1/8	Plain	C	"	1	
8650	Type 2148 ...	10 K	20	1 1/2	1 1/8	3 solder pins	1	1 1/8	Plain	C	"	1	
9452	Type 2708 ...	10 K	20	1 1/2	1 1/8	3 solder pins	1	1 1/8	Plain	C	"	1	
9257	Type 2584 ...	10 K	20	1 1/2	1 1/8	3 solder pins	1	1 1/8	Plain	C	"	1	
8214	Type 8214 ...	10 K	20	1 1/2	1 1/8	3 solder pins	1	1 1/8	Plain	C	"	1	
8867	Type 2296 ...	10 K	20	1 1/2	1 1/8	3 solder pins	1	1 1/8	Slotted	C	"	1	
15628	Type 4324 ...	10 K	20	1 1/2	1 1/8	3 solder pins	1	1 1/8	Slotted	C	"	1	
15785	Type 4469 ...	10 K	20	1 1/2	1 1/8	3 solder pins	1	1 1/8	Slotted	C	"	1	
16102	Type 4753 ...	10 K	20	1 1/2	1 1/8	3 solder pins	1	1 1/8	Slotted	C	"	1	
16309	Type 4925 ...	10 K	20	1 1/2	1 1/8	3 tags	1	1 1/8	With 1/2 in. flat 3/8 in. long	C	"	1	
16101	Type 4752 ...	10 K	20	1 1/2	1 1/8	—	1	1 1/8	Flat	C	"	1	
8614	Type 2120 ...	10 K	20	1 1/2	1 1/8	—	1	1 1/8	—	C	"	1	
15447	Type 4156 ...	10 K	20	1 1/2	1 1/8	—	1	1 1/8	—	C	"	1	
15324	Type 4033 ...	10 K	20	1 1/2	1 1/8	—	1	1 1/8	Slotted	C	"	1	
9043	Type 2405 ...	10 K	15	1 1/2	1 1/8	—	1	1 1/8	Slotted	C	"	1	
15287	Type 3996 ...	10 K	20	1 1/2	1 1/8	3 × 1/2 in. solder pins	1	1 1/8	Plain	C	"	1	

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ± %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty
					Dia. (inches)	Depth (inches)	Other Details	Dia. (inches)	Length (inches)	Other Details			
1	RESISTORS—cont. Variable potentiometers—cont. Carbon composition element—cont.												
6189	Type 6189 ...	10 K	20	2	1 7/8	1 13/16	3 × 1/2 in. solder pins	1 13/16	1 13/16	Plain	C	each	1
9209	Type 2537 ...	10 K	—	—	—	—	—	—	—	—	C	"	—
6882	Type 6882 ...	10 K	—	—	—	—	—	—	—	—	C	"	—
9332	Type 2633 ...	15 K	20	—	1 13/16	1 1/8	3 tags 1/16 in. long	1 1/8	1 1/8	Plain	C	"	—
7129	Type 7129 ...	15 K	10	—	1 13/16	1 1/8	3 tags	1 1/8	1 1/8	Slotted	C	"	—
15432	Type 4141 ...	15 K	10	—	1 13/16	1 1/8	3 tags	1 1/8	1 1/8	Plain	C	"	—
6074	Type 6074 ...	15 K	20	—	1 13/16	1 1/8	—	1 1/8	1 1/8	Slotted	C	"	—
9553	Type 2804 ...	15 K	20	—	1 13/16	1 1/8	3 solder pins 1/2 in.	1 1/8	1 1/8	Slotted	C	"	—
15958	Type 4639 ...	15 K	20	—	1 13/16	1 1/8	3 solder pins 1/2 in.	1 1/8	1 1/8	Slotted	C	"	—
8891	Type 2311 ...	20 K	20	—	1 13/16	1 1/8	3 tags 1/16 in. long	1 1/8	1 1/8	Plain	C	"	—
16138	Type 4785 ...	20 K	20	—	1 13/16	1 1/8	3 tags 1/16 in. long	1 1/8	1 1/8	Slotted	C	"	—
15629	Type 4325 ...	20 K	20	—	1 13/16	1 1/8	3 tags 1/16 in. long	1 1/8	1 1/8	Slotted	C	"	—
15535	Type 4244 ...	20 K	20	—	1 13/16	1 1/8	3 tags 1/16 in. long	1 1/8	1 1/8	—	C	"	—
15930	Type 4611 ...	20 K	20	—	1 13/16	1 1/8	3 tags	1 1/8	1 1/8	Plain	C	"	—
7128	Type 7128 ...	20 K	10	—	1 13/16	1 1/8	3 tags	1 1/8	1 1/8	Plain	C	"	—
8102	Type 8102 ...	20 K	15	—	1 1/2	1 1/2	3 tags	1 1/2	1 1/2	Slotted	C	"	—
15576	Type 4281 ...	20 K	20	—	—	—	—	—	—	Slotted	C	"	—
16669	Type 5194 ...	20 K	10	—	—	—	—	—	—	With 1/2 in. flat	C	"	—
16156	Type 4803 ...	20 K	10	—	—	—	—	—	—	With 3/8 in. slot	C	"	—
8099	Type 8099 ...	20 K	10	—	—	—	—	—	—	Slotted	C	"	—
11110	Type 455 ...	20 K	—	—	—	—	—	—	—	—	C	"	—
8029	Type 8029 ...	20 K	20	—	—	—	—	—	—	Plain	C	"	—
1800	Type 1800 ...	20 K	20	—	—	—	—	—	—	—	C	"	—
10677	Type 3515 ...	20 K	20	—	—	—	—	—	—	—	C	"	—
9258	Type 2585 ...	20 K	20	—	—	—	—	—	—	—	C	"	—
9409	Type 2673 ...	20 K	20	—	—	—	3 solder pins 1/2 in. 3 solder pins 1/2 in.	—	—	Plain	C	"	—

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ± %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty	Carton Unit Qty
					Di. (inches)	Depth (inches)	Other Details	Di. (inches)	Length (inches)	Other Details			
1	2	3	4	5	6	7	8	9	10	11	12	13	14
15726	Type 4420 ...	20 K	20	1 1/2	—	—	—	—	—	—	C	each	1
15061	Type 3770 ...	20 K	20	1 1/2	—	—	—	—	—	—	C	"	1
15857	Type 4540 ...	20 K	20	1 1/2	—	—	—	—	—	—	C	"	1
16190	Type 4822 ...	20 K	20	1 1/2	—	—	—	—	—	—	C	"	1
16565	Type 5133 ...	20 K	20	1 1/2	—	—	—	—	—	—	C	"	1
9721	Type 2949 ...	25 K	20	1 1/2	—	—	3 solder pins 1/2 in.	—	—	—	C	"	1
6485	Type 6485 ...	25 K	10	2	1 1/8	1 1/8	—	—	—	—	C	"	1
6998	Type 6998 ...	25 K	—	—	—	—	—	—	—	—	C	"	1
16906	Type 5416 ...	25 K	10	—	—	—	—	—	—	—	C	"	1
16673	Type 5197 ...	25 K	20	—	—	—	—	—	—	—	C	"	1
17618	Type 9070 ...	25 K	20	—	—	—	—	—	—	—	C	"	1
17960	Type 9344 ...	25 K	20	—	—	—	—	—	—	—	C	"	3
6350	Type 6350 ...	25 K	20	—	—	—	—	—	—	—	C	"	1
16732	Type 5250 ...	25 K	20	—	—	—	—	—	—	—	C	"	1
16283	Type 4903 ...	25 K	20	—	—	—	—	—	—	—	C	"	1
15170	Type 3879 ...	25 K	20	—	—	—	—	—	—	—	C	"	1
17822	Type 9263 ...	25 K	20	—	—	—	—	—	—	—	C	"	1
16760	Type 5277 ...	25 K	20	—	—	—	—	—	—	—	C	"	1
15496	Type 4205 ...	25 K	10	—	—	—	—	—	—	—	C	"	1
16153	Type 4800 ...	25 K	10	—	—	—	—	—	—	—	C	"	1
1232	Type 1232 ...	25 K	10	—	—	—	—	—	—	—	C	"	1
192	Type 660 ...	25 K	10	—	—	—	3 tags	—	—	—	C	"	1
9230	Type 2557 ...	25 K	10	—	—	—	3 solder pins 1/2 in.	—	—	—	C	"	1
15158	Type 3867 ...	25 K	10	—	—	—	3 solder pins 1/2 in.	—	—	—	C	"	1
16157	Type 4804 ...	25 K	10	—	—	—	3 solder pins 1/2 in.	—	—	—	C	"	1
16507	Type 5077 ...	25 K	15	—	—	—	—	—	—	—	C	"	1

RESISTORS—cont.
Variable potentiometers—cont.
Carbon composition element—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ± %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Dia. (inches)	Depth (inches)	Other Details	Dia. (inches)	Length (inches)	Other Details			
1	2	3	4	5	6	7	8	9	10	11	12	13	14
	RESISTORS—cont.												
	Variable potentiometers—cont.												
	Carbon composition element—cont.												
10923	Type 3643 ...	25 K	15	$1\frac{1}{2}$	—	—	—	$\frac{1}{2}$	1	Slotted	C	each	1
16506	Type 5076 ...	25 K	15	$1\frac{1}{2}$	—	—	—	$\frac{1}{2}$	1	Slotted	C	"	1
10662	Type 3504 ...	25 K	20	$1\frac{1}{2}$	$1\frac{9}{16}$	$1\frac{31}{32}$	—	$\frac{1}{2}$	1	—	C	"	1
16310	Type 4926 ...	25 K	20	$1\frac{1}{2}$	$1\frac{9}{16}$	$1\frac{31}{32}$	3 solder pins $\frac{1}{2}$ in.	$\frac{1}{2}$	$1\frac{1}{8}$	Fiat	C	"	1
16063	Type 4719 ...	25 K	20	$1\frac{1}{2}$	$1\frac{9}{16}$	$1\frac{31}{32}$	3 solder pins $\frac{1}{2}$ in.	$\frac{1}{2}$	$1\frac{1}{8}$	Plain	C	"	1
7510	Type 7510 ...	25 K	20	$1\frac{1}{2}$	$1\frac{9}{16}$	$1\frac{31}{32}$	3 tags	$\frac{1}{2}$	$1\frac{1}{8}$	Slotted	C	"	1
8059	Type 8059 ...	25 K	20	$1\frac{1}{2}$	$1\frac{9}{16}$	$1\frac{31}{32}$	3 tags	$\frac{1}{2}$	$1\frac{1}{8}$	Slotted	C	"	1
9720	Type 2948 ...	25 K	20	$1\frac{1}{2}$	$1\frac{9}{16}$	$1\frac{31}{32}$	3 solder pins $\frac{1}{2}$ in.	$\frac{1}{2}$	1	Slotted	C	"	1
9270	Type 2597 ...	25 K	20	$1\frac{1}{2}$	$1\frac{9}{16}$	$1\frac{31}{32}$	3 solder pins $\frac{1}{2}$ in.	$\frac{1}{2}$	2 $\frac{3}{8}$	Screwdriver slot with flat	C	"	1
9569	Type 2820 ...	25 K	20	$1\frac{1}{2}$	$1\frac{9}{16}$	$1\frac{31}{32}$	3 solder pins $\frac{1}{2}$ in.	$\frac{1}{2}$	1	Plain	C	"	1
15244	Type 3953 ...	25 K	20	$1\frac{1}{2}$	$1\frac{9}{16}$	$1\frac{31}{32}$	3 solder pins $\frac{1}{2}$ in.	$\frac{1}{2}$	$1\frac{1}{2}$	Slotted	C	"	1
15577	Type 4282 ...	25 K	20	$1\frac{1}{2}$	$1\frac{9}{16}$	$1\frac{31}{32}$	3 solder pins $\frac{1}{2}$ in.	$\frac{1}{2}$	$1\frac{3}{8}$	Flattened ($\frac{1}{2}$ in. flat)	C	"	1
15957	Type 4638 ...	25 K	20	$1\frac{1}{2}$	$1\frac{9}{16}$	$1\frac{31}{32}$	3 solder pins $\frac{1}{2}$ in.	$\frac{1}{2}$	$2\frac{1}{8}$	Slotted	C	"	1
15217	Type 3926 ...	25 K	20	2	$1\frac{7}{8}$	$1\frac{13}{16}$	3 $\times \frac{1}{2}$ in. solder pins	$\frac{1}{2}$	$1\frac{7}{8}$	Plain	C	"	1
15680	Type 4376 ...	25 K	20	2	$1\frac{11}{16}$	$1\frac{13}{16}$	3 tags	$\frac{1}{2}$	1	Slotted	C	"	1
15667	Type 4363 ...	25 K	20	2	—	—	—	$\frac{1}{2}$	$1\frac{3}{8}$	Screwdriver slot	C	"	1
16143	Type 4790 ...	25 K	5	5	—	—	—	$\frac{1}{2}$	$1\frac{3}{8}$	—	C	"	1
16146	Type 4793 ...	30 K	10	4	—	—	—	$\frac{1}{2}$	$1\frac{3}{8}$	—	C	"	1
8606	Type 2114 ...	30 K	20	4	$1\frac{1}{8}$	$1\frac{7}{16}$	3 tags $\frac{7}{16}$ in. long	$\frac{1}{2}$	$1\frac{3}{8}$	Slotted	C	"	1
16167	Type 4813 ...	30 K	20	4	$1\frac{1}{8}$	$1\frac{7}{16}$	3 tags $\frac{7}{16}$ in. long	$\frac{1}{2}$	$1\frac{3}{8}$	Slotted	C	"	1
15417	Type 4126 ...	30 K	20	$1\frac{1}{2}$	$1\frac{9}{16}$	$1\frac{31}{32}$	3 tags	$\frac{1}{2}$	$1\frac{3}{8}$	Slotted	C	"	1
16483	Type 5054 ...	33 K	$\frac{1}{2}$	30	Mini-ature	—	—	$\frac{1}{2}$	—	—	C	"	1
15105	Type 3814 ...	50 K	10	—	—	—	—	$\frac{1}{2}$	1	Plain	C	"	1
7564	Type 7564 ...	50 K	—	—	—	—	—	$\frac{1}{2}$	$1\frac{3}{8}$	Flattened	C	"	1
17894	Type 9335 ...	50 K	20	$\frac{1}{2}$	—	—	—	$\frac{1}{2}$	$1\frac{3}{8}$	Slotted	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ± %	Wattage	DIMENSIONS AND DETAILS OF BODY		Other Details	DIMENSIONS AND DETAILS OF SPRINDLE		Class of Store	Denom. of Qty.	Carton Unit Qty.	
					Dia. (inches)	Depth (inches)		Dia. (inches)	Length (inches)				Other Details
1	RESISTORS—cont. Variable potentiometers—cont. Carbon composition element—cont.												
9207	Type 2536 ...	50 K	15	1	1 3/8	3/16	3 tags 1/8 in. long	1/8	1 1/8	Slotted	C	each	1
16522	Type 5092 ...	50 K	20	1	1	—	—	1/8	1 1/8	Slotted	C	"	1
15416	Type 4125 ...	50 K	20	1	1	—	—	1/8	1 1/8	Standard	C	"	1
10956	Type 3671 ...	50 K	20	1	1 3/8	3/16	3 tags 1/8 in. long	1	1 3/8	Plain	C	"	1
9331	Type 2632 ...	50 K	20	1	1 3/8	3/16	3 tags 1/8 in. long	1	1 3/8	Slotted	C	"	1
9044	Type 2406 ...	50 K	15	1	1 1/2	3/16	3 tags	1	1 1/2	—	C	"	1
15003	Type 3712 ...	50 K	20	1	1 1/2	3/16	3 tags	1	1 1/2	Plain	C	"	1
7421	Type 7421 ...	50 K	20	1	1 1/2	3/16	3 tags	1	1 1/2	Slotted	C	"	1
8103	Type 8103 ...	50 K	15	1	1 1/2	3/16	3 tags	1	1 1/2	Plain	C	"	1
1149	Type 1149 ...	50 K	10	1	1 1/2	3/16	3 tags	1	1 1/2	Slotted	C	"	1
8105	Type 8105 ...	50 K	10	1	1 1/2	3/16	3 tags	1	1 1/2	Slotted	C	"	1
8251	Type 8251 ...	50 K	10	1	1 1/2	3/16	3 tags	1	1 1/2	Plain	C	"	1
9229	Type 2556 ...	50 K	10	1	1 1/2	3/16	3 solder pins 1/8 in.	1 1/2	1 1/2	Plain	C	"	1
15279	Type 3988 ...	50 K	10	1	1 1/2	3/16	3 solder pins 1/8 in.	1 1/2	1 1/2	Plain	C	"	1
10557	Type 3444 ...	50 K	15	1	1 1/2	3/16	3 tags	1 1/2	1 1/2	With 5 B.A. holes	C	"	1
8216	Type 8216 ...	50 K	15	1	1 1/2	3/16	3 tags	1 1/2	1 1/2	Slotted	C	"	1
1493	Type 1493 ...	50 K	15	1	1 1/2	3/16	3 tags	1 1/2	1 1/2	Plain	C	"	1
7855	Type 7855 ...	50 K	15	1	1 1/2	3/16	3 tags	1 1/2	1 1/2	Plain	C	"	1
8713	Type 2175 ...	50 K	15	1	1 1/2	3/16	3 solder pins 1/8 in.	1 1/2	1 1/2	Plain	C	"	1
8879	Type 2301 ...	50 K	15	1	1 1/2	3/16	3 solder pins 1/8 in.	1 1/2	1 1/2	Plain	C	"	1
17619	Type 9072 ...	50 K	20	1	1 1/2	3/16	3 solder pins 1/8 in.	1 1/2	1 1/2	Slotted	C	"	1
10654	Type 3501 ...	50 K	20	1	1 1/2	3/16	3 tags	1 1/2	1 1/2	—	C	"	1
8928	Type 2338 ...	50 K	20	1	1 1/2	3/16	3 tags	1 1/2	1 1/2	Slotted	C	"	1
1486	Type 1486 ...	50 K	20	1	1 1/2	3/16	3 tags	1 1/2	1 1/2	Plain	C	"	1
7321	Type 7321 ...	50 K	20	1	1 1/2	3/16	3 tags	1 1/2	1 1/2	Slotted	C	"	1
7414	Type 7414 ...	50 K	20	1	1 1/2	3/16	3 tags	1 1/2	1 1/2	With 1/2 in. flat.	C	"	1
16470	Type 5043 ...	50 K	20	1	1 1/2	3/16	3 solder pins 1/8 in.	1 1/2	1 1/2	Slotted	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ± %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Dia. (inches)	Depth (inches)	Other Details	Dia. (inches)	Length (inches)	Other Details			
1													
	RESISTORS—cont.												
	Variable potentiometers—cont.												
	Carbon composition element—cont.												
7818	Type 7818 ...	50 K	20	1 1/8	1 1/8	3 tags	1 1/8	1 1/8	Slotted	C	each	1	
193	Type 661 ...	50 K	20	1 1/8	1 1/8	3 solder pins	1 1/8	1 1/8	Slotted	C	"	1	
10791	Type 3576 ...	50 K	20	1 1/8	1 1/8	3 solder pins	1 1/8	1 1/8	Plain	C	"	1	
8741	Type 2191 ...	50 K	20	1 1/8	1 1/8	3 solder pins	1 1/8	1 1/8	Plain	C	"	1	
8835	Type 2266 ...	50 K	20	1 1/8	1 1/8	3 solder pins	1 1/8	1 1/8	Slotted	C	"	1	
9242	Type 2569 ...	50 K	20	1 1/8	1 1/8	3 solder pins	1 1/8	1 1/8	Slotted	C	"	1	
9439	Type 2695 ...	50 K	20	1 1/8	1 1/8	3 solder pins	1 1/8	1 1/8	Plain	C	"	1	
9451	Type 2707 ...	50 K	20	1 1/8	1 1/8	3 solder pins	1 1/8	1 1/8	Plain	C	"	1	
15119	Type 3828 ...	50 K	20	1 1/8	1 1/8	3 solder pins	1 1/8	1 1/8	Flatted	C	"	1	
15624	Type 4320 ...	50 K	20	1 1/8	1 1/8	3 solder pins	1 1/8	1 1/8	Flatted with 1/2 in. flat	C	"	1	
15625	Type 4321 ...	50 K	20	1 1/8	1 1/8	3 solder pins 1/2 in.	1 1/8	1 1/8	Slotted	C	"	1	
15631	Type 4327 ...	50 K	20	1 1/8	1 1/8	3 solder pins 1/2 in.	1 1/8	1 1/8	Slotted	C	"	1	
15856	Type 4539 ...	50 K	20	1 1/8	1 1/8	3 solder pins 1/2 in.	1 1/8	1 1/8	Slotted	C	"	1	
16803	Type 5319 ...	50 K	20	1 1/8	1 1/8	3 solder pins 1/2 in.	1 1/8	1 1/8	Slotted	C	"	1	
15151	Type 3860 ...	50 K	20	1 1/8	1 1/8	3 solder pins	1 1/8	1 1/8	Slotted	C	"	1	
8605	Type 2113 ...	50 K	20	1 1/8	1 1/8	3 solder pins	1 1/8	1 1/8	Slotted	C	"	1	
6094	Type 6094 ...	50 K	20	1 1/8	1 1/8	3 solder pins	1 1/8	1 1/8	Slotted	C	"	1	
8328	Type 8328 ...	50 K	20	1 1/8	1 1/8	3 solder pins	1 1/8	1 1/8	Slotted	C	"	1	
6156	Type 6156 ...	50 K	20	1 1/8	1 1/8	3 solder pins	1 1/8	1 1/8	Slotted	C	"	1	
7687	Type 7687 ...	50 K	20	1 1/8	1 1/8	3 solder pins	1 1/8	1 1/8	Slotted	C	"	1	
15510	Type 4219 ...	50 K	10	1 1/8	1 1/8	3 solder pins	1 1/8	1 1/8	Slotted	C	"	10	
15509	Type 4218 ...	50 K	10	1 1/8	1 1/8	3 solder pins	1 1/8	1 1/8	Slotted	C	"	1	
16154	Type 4801 ...	50 K	10	1 1/8	1 1/8	3 solder pins	1 1/8	1 1/8	Slotted	C	"	1	
17838	Type 9279 ...	50 K	15	1 1/8	1 1/8	3 solder pins	1 1/8	1 1/8	Slotted	C	"	1	
16680	Type 5204 ...	50 K	15	1 1/8	1 1/8	3 solder pins	1 1/8	1 1/8	Slotted	C	"	1	
6486	Type 6486 ...	50 K	10	1 1/8	1 1/8	3 tags	1 1/8	1 1/8	Slotted	C	"	1	

RADIO RESISTORS

SECTION 10W—cont.

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ± %	Wattage	DIMENSIONS AND DETAILS OF BODY		Other Details	DIMENSIONS AND DETAILS OF SPINDLE		Class of Store	Denom. of Qty.	Carton Unit Qty.
					Dia. (inches)	Depth (inches)		Dia. (inches)	Length (inches)			
1	RESISTORS—cont. Variable potentiometers—cont. Carbon composition element—cont.											
6190	Type 6190 ...	50 K	20	2	1 7/8	1 13/16	3 × 1/2 in. solder pins	1 1/4	1 3/4	C	each	1
15005	Type 3714 ...	50 K	20	2	1 7/8	1 13/16	3 × 1/2 in. solder pins	1 1/4	1 3/4	C	"	1
389	Type 762 ...	50 K	10	1 1/2	1 13/16	3 tags	—	1 1/4	1 1/4	C	"	1
1569	Type 1569 ...	60 K	20	1 1/2	1 13/16	—	—	1 1/4	1 1/4	C	"	1
6420	Type 6240 ...	60 K	20	1 1/2	1 13/16	—	—	1 1/4	1 1/4	C	"	1
7365	Type 7365 ...	75 K	20	1 1/2	1 13/16	—	—	1 1/4	1 1/4	C	"	1
16490	Type 5061 ...	75 K	20	1 1/2	1 13/16	—	—	1 1/4	1 1/4	C	"	1
8104	Type 8104 ...	75 K	15	2.5	1 1/2	3 tags	—	1 1/4	1 1/4	C	"	1
17581	Type 9036 ...	75 K	20	1 1/2	1 13/16	—	—	1 1/4	1 1/4	C	"	1
9408	Type 2672 ...	75 K	20	1 1/2	1 13/16	3 pins	—	1 1/4	1 1/4	C	"	1
15085	Type 3794 ...	75 K	20	2	1 7/8	—	—	1 1/4	1 1/4	C	"	1
15800	Type 4483 ...	75 K	20	2	1 7/8	3 × 1/2 in. solder pins	—	1 1/4	1 1/4	C	"	1
17893	Type 9334 ...	100 K	20	1 1/2	1 13/16	—	—	1 1/4	1 1/4	C	"	1
8185	Type 8185 ...	100 K	10	1	1 13/16	3 tags 7/16 in. long	—	1 1/4	1 1/4	C	"	1
8995	Type 2371 ...	100 K	10	1	1 13/16	3 tags 7/16 in. long	—	1 1/4	1 1/4	C	"	1
10714	Type 3542 ...	100 K	20	1	1 13/16	3 tags 7/16 in. long	—	1 1/4	1 1/4	C	"	1
6317	Type 6317 ...	100 K	20	1	1 13/16	3 tags 7/16 in. long	—	1 1/4	1 1/4	C	"	1
766	Type 904 ...	100 K	20	1	1 13/16	3 tags 7/16 in. long	—	1 1/4	1 1/4	C	"	1
15089	Type 3789 ...	100 K	20	1	1 13/16	3 tags 7/16 in. long	—	1 1/4	1 1/4	C	"	1
15415	Type 4124 ...	100 K	20	1	1 13/16	3 tags 7/16 in. long	—	1 1/4	1 1/4	C	"	1
9616	Type 2861 ...	100 K	20	1	1 13/16	3 tags 7/16 in. long	—	1 1/4	1 1/4	C	"	1
16491	Type 5063 ...	100 K	20	1	1 13/16	3 tags 7/16 in. long	—	1 1/4	1 1/4	C	"	1
15090	Type 3799 ...	100 K	20	1	1 13/16	3 tags 7/16 in. long	—	1 1/4	1 1/4	C	"	1
15046	Type 3755 ...	100 K	20	1	1 13/16	3 tags 7/16 in. long	—	1 1/4	1 1/4	C	"	1
6341	Type 6341 ...	100 K	20	1	1 13/16	3 tags 7/16 in. long	—	1 1/4	1 1/4	C	"	1
8997	Type 2373 ...	100 K	20	1	1 13/16	3 tags 7/16 in. long	—	1 1/4	1 1/4	C	"	1
8293	Type 8293 ...	100 K	20	1	1 13/16	3 tags 7/16 in. long	—	1 1/4	1 1/4	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ± %	Wattage	DIMENSIONS AND DETAILS OF BODY		Other Details	DIMENSIONS AND DETAILS OF SPINDLE		Class of Store	Denom. of Qty.	Carton Unit Qty.
					Dia. (inches)	Depth (inches)		Dia. (inches)	Length (inches)			
1	RESISTORS—cont. Variable potentiometers—cont. Carbon composition element—cont.											
15537	Type 4246 ...	100 K	20	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	each	1
8370	Type 8370 ...	100 K	20	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	"	1
6209	Type 6209 ...	100 K	20	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	"	1
1443	Type 1443 ...	100 K	10	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	"	1
6342	Type 6342 ...	100 K	10	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	"	1
7413	Type 7413 ...	100 K	10	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	"	1
8096	Type 8096 ...	100 K	10	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	"	1
8248	Type 8248 ...	100 K	10	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	"	1
8777	Type 2227 ...	100 K	10	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	"	1
8014	Type 8014 ...	100 K	10	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	"	1
8643	Type 2141 ...	100 K	10	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	"	1
8776	Type 2226 ...	100 K	10	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	"	1
15955	Type 4636 ...	100 K	10	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	"	1
10987	Type 3697 ...	100 K	10	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	"	1
15278	Type 3987 ...	100 K	10	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	"	1
10531	Type 3434 ...	100 K	15	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	"	1
1691	Type 1691 ...	100 K	15	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	"	1
10925	Type 3645 ...	100 K	15	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	"	1
16508	Type 5078 ...	100 K	15	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	"	1
16509	Type 5079 ...	100 K	15	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	"	1
1201	Type 1201 ...	100 K	15	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	"	1
8872	Type 2299 ...	100 K	15	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	"	1
10672	Type 3511 ...	100 K	20	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	"	1
6076	Type 6076 ...	100 K	20	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	"	1
8931	Type 2341 ...	100 K	20	$\frac{1}{2}$ W	1 $\frac{11}{16}$	1 $\frac{1}{16}$	—	$\frac{1}{4}$ × $\frac{1}{4}$	1	C	"	1

SECTION 10W—*cont.*

RADIORESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ± %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Dia. (inches)	Depth (inches)	Other Details	Dia. (inches)	Length (inches)	Other Details			
1	RESISTORS—<i>cont.</i> Variable potentiometers—<i>cont.</i> Carbon composition element—<i>cont.</i>												
6864	Type 6864 ...	100 K	20	1 1/2	1 1/8	3 tags	1 1/8	1 1/8	Plain	C	each	1	
7264	Type 7264 ...	100 K	20	1 1/2	1 1/8	3 tags	1 1/8	1 1/8	Flatted	C	"	1	
764	Type 902 ...	100 K	20	1 1/2	1 1/8	3 tags	1 1/8	1 1/8	Slotted	C	"	1	
7457	Type 7457 ...	100 K	20	1 1/2	1 1/8	3 tags	1 1/8	1 1/8	Slotted	C	"	1	
10967	Type 3682 ...	100 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Plain	C	"	1	
6697	Type 6697 ...	100 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Plain	C	"	1	
8308	Type 8308 ...	100 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Plain	C	"	1	
8654	Type 2152 ...	100 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Plain	C	"	1	
8740	Type 2190 ...	100 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Plain	C	"	1	
9314	Type 2622 ...	100 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Plain	C	"	1	
8655	Type 2153 ...	100 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Plain 5 B.A. hole	C	"	1	
15965	Type 4646 ...	100 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Slotted	C	"	1	
9660	Type 2892 ...	100 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Slotted	C	"	1	
10709	Type 3537 ...	100 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Flatted	C	"	1	
15630	Type 4326 ...	100 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	6 B.A. hole	C	"	1	
15858	Type 4541 ...	100 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Slotted	C	"	1	
15880	Type 4563 ...	100 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Slotted	C	"	1	
8329	Type 8329 ...	100 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Slotted	C	"	1	
7582	Type 7582 ...	100 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Plain	C	"	1	
10610	Type 3484 ...	100 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Plain	C	"	1	
16654	Type 5188 ...	100 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Slotted	C	"	1	
10921	Type 3641 ...	100 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Slotted	C	"	1	
8693	Type 2163 ...	100 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Plain	C	"	1	
6188	Type 6188 ...	100 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Plain	C	"	1	
6487	Type 6487 ...	100 K	10	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Plain	C	"	1	
10993	Type 3703 ...	100 K	10	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Slotted	C	"	1	
17779	Type 9224 ...	100 K	15	1.5	1 1/8	3 × 1/2 in. solder pins	0-872	1 1/8	Slotted	C	"	1	

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ± %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Net Qty.
					Dia. (inches)	Depth (inches)	Other Details	Dia. (inches)	Length (inches)	Other Details			
1	2	3	4	5	6	7	8	9	10	11	12	13	14
RESISTORS—cont.													
Variable potentiometers—cont.													
Carbon composition element—cont.													
9045	Type 2407 ...	100 K	15	2	1 11/16	1 9/16	3 pins 1/2 in. long	1 1/4	1 1/8	Slotted Plain	C	each	1
8512	Type 2034 ...	100 K	15	2	1 11/16	1 9/16	3 tags	1 1/4	1 1/8	Slotted Plain	C	"	1
17620	Type 9073 ...	100 K	20	4	1 11/16	1 9/16	—	1 1/4	1 1/8	Slotted Plain	C	"	1
17035	Type — ...	100 K	—	—	—	—	—	—	—	Slotted	C	"	3
15002	Type 3711 ...	100 K	—	—	—	—	—	—	—	Slotted	C	"	1
15027	Type 3736 ...	100 K	—	—	—	—	—	—	—	Slotted	C	"	1
15028	Type 3737 ...	100 K	—	—	—	—	—	—	—	Slotted	C	"	1
9259	Type 2586 ...	120 K	20	1 1/2	1 9/16	1 1/2	3 pins 1/2 in. long	1 1/4	1 1/8	Flatted 1/8 in. × 1/16 in. and tapped 5 B.A.	C	"	1
15153	Type 3862 ...	120 K	20	1 1/2	1 9/16	1 1/2	3 pins 1/2 in. long	1 1/4	1 1/8	Slotted	C	"	1
6421	Type 6421 ...	200 K	10	1 1/2	1 9/16	1 1/2	3 tags 1/2 in. long	1 1/4	1 1/8	—	C	"	5
15092	Type 3801 ...	200 K	20	1 1/2	1 9/16	1 1/2	3 tags 1/2 in. long	1 1/4	1 1/8	Slotted	C	"	1
765	Type 903 ...	200 K	20	1 1/2	1 9/16	1 1/2	3 tags 1/2 in. long	1 1/4	1 1/8	Slotted	C	"	1
9204	Type 2534 ...	200 K	20	1 1/2	1 9/16	1 1/2	3 tags 1/2 in. long	1 1/4	1 1/8	Slotted	C	"	1
15216	Type 3925 ...	200 K	20	1 1/2	1 9/16	1 1/2	3 tags 1/2 in. long	1 1/4	1 1/8	Slotted	C	"	1
16679	Type 5203 ...	200 K	15	1 1/2	1 9/16	1 1/2	—	1 1/4	0-7/19	Slotted	C	"	1
16601	Type 5161 ...	200 K	15	1 1/2	1 9/16	1 1/2	—	1 1/4	1 1/8	Slotted	C	"	1
7444	Type 7444 ...	200 K	20	1 1/2	1 9/16	1 1/2	—	1 1/4	1 1/8	Plain	C	"	1
16741	Type 5258 ...	200 K	20	1 1/2	1 9/16	1 1/2	—	1 1/4	1 1/8	Slotted	C	"	1
16260	Type 4881 ...	200 K	20	1 1/2	1 9/16	1 1/2	—	1 1/4	1 1/8	—	C	"	1
16246	Type 4871 ...	200 K	20	1 1/2	1 9/16	1 1/2	—	1 1/4	1 1/8	Plain	C	"	1
1195	Type 1195 ...	200 K	10	1 1/2	1 9/16	1 1/2	3 tags	1 1/4	1 1/8	—	C	"	1
1233	Type 1233 ...	200 K	10	1 1/2	1 9/16	1 1/2	3 tags	1 1/4	1 1/8	Slotted	C	"	1
1226	Type 1226 ...	200 K	10	1 1/2	1 9/16	1 1/2	3 tags	1 1/4	1 1/8	Slotted	C	"	1
1318	Type 1318 ...	200 K	10	1 1/2	1 9/16	1 1/2	3 pins 1/2 in. long	1 1/4	1 1/8	Slotted	C	"	1
10675	Type 3514 ...	200 K	20	1 1/2	1 9/16	1 1/2	3 tags	1 1/4	1 1/8	Plain	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ± %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Dia. (inches)	Depth (inches)	Other Details	Dia. (inches)	Length (inches)	Other Details			
1	RESISTORS—cont. Variable potentiometers—cont. Carbon composition element—cont.												
8938	Type 2344 ...	200 K	20	1 1/8	1 1/8	3 tags	1/8 in. long	1/8	1 1/8	Plain	C	each	1
9311	Type 2619 ...	200 K	20	1 1/8	1 1/8	3 pins	1/8 in. long	1/8	1 1/8	Tapped 5 B.A. Plain, 1/8 in. flat	C	"	1
9663	Type 2895 ...	200 K	20	1 1/8	1 1/8	3 pins	1/8 in. long	1/8	1 1/8	Flatted	C	"	1
15057	Type 3766 ...	200 K	20	1 1/8	1 1/8	3 pins	1/8 in. long	1/8	1 1/8	Slotted	C	"	1
15859	Type 4542 ...	200 K	20	1 1/8	1 1/8	3 pins	1/8 in. long	1/8	1 1/8	Slotted	C	"	1
15862	Type 4545 ...	200 K	20	1 1/8	1 1/8	3 pins	1/8 in. long	1/8	1 1/8	Slotted	C	"	1
15626	Type 4322 ...	200 K	20	1 1/8	1 1/8	3 pins	1/8 in. long	1/8	1 1/8	Slotted	C	"	1
15664	Type 4360 ...	200 K	20	1 1/8	1 1/8	3 pins	1/8 in. long	1/8	1 1/8	Slotted	C	"	1
17896	Type 9337 ...	250 K	20	1 1/8	1 1/8	—	—	—	1 1/8	—	C	"	1
17403	Type 5859 ...	250 K	5	1 1/8	1 1/8	—	—	—	1 1/8	Slotted	C	"	1
8974	Type 2363 ...	250 K	10	1 1/8	1 1/8	—	—	—	1 1/8	—	C	"	1
10959	Type 3674 ...	250 K	20	1 1/8	1 1/8	3 tags	1/8 in. long	1/8	1 1/8	Slotted	C	"	1
8604	Type 2112 ...	250 K	20	1 1/8	1 1/8	3 tags	1/8 in. long	1/8	1 1/8	Plain 5 B.A. hole	C	"	1
8728	Type 2183 ...	250 K	20	1 1/8	1 1/8	3 tags	1/8 in. long	1/8	1 1/8	Slotted	C	"	1
16492	Type 5063 ...	250 K	20	1 1/8	1 1/8	3 tags	1/8 in. long	1/8	1 1/8	Plain	C	"	1
6818	Type 6818 ...	250 K	15	1 1/8	1 1/8	3 tags	—	—	1 1/8	Flatted	C	"	1
8358	Type 8358 ...	250 K	15	1 1/8	1 1/8	3 tags	—	—	1 1/8	Slotted	C	"	1
15420	Type 4129 ...	250 K	15	1 1/8	1 1/8	—	—	—	1 1/8	—	C	"	1
9647	Type 2879 ...	250 K	20	1 1/8	1 1/8	—	—	—	1 1/8	Plain	C	"	1
7869	Type 7869 ...	250 K	20	1 1/8	1 1/8	3 tags	—	—	1 1/8	Flatted	C	"	1
8294	Type 8294 ...	250 K	20	1 1/8	1 1/8	3 tags	—	—	1 1/8	Plain	C	"	1
1442	Type 1442 ...	250 K	10	1 1/8	1 1/8	3 tags	—	—	1 1/8	Plain	C	"	1
9226	Type 2553 ...	250 K	10	1 1/8	1 1/8	3 pins	1/8 in. long	1/8	1 1/8	Slotted	C	"	1
10327	Type 374 ...	250 K	15	1 1/8	1 1/8	3 pins	1/8 in. long	1/8	1 1/8	—	C	"	1
7854	Type 7854 ...	250 K	15	1 1/8	1 1/8	3 pins	1/8 in. long	1/8	1 1/8	Plain	C	"	1
9010	Type 2386 ...	250 K	15	1 1/8	1 1/8	3 pins	1/8 in. long	1/8	1 1/8	Slotted	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	Nomenclature	Value in Ohms	Tolerance ± %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Dia. (inches)	Depth (inches)	Other Details	Dia. (inches)	Length (inches)	Other Details			
1	RESISTORS—cont. Variable potentiometers—cont. Carbon composition element —cont.												
10523	Type 3426 ...	250 K	15	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	3 pins $\frac{1}{2}$ in. long	$\frac{1}{8}$	$1\frac{1}{8}$	Slotted	C	each	1
6077	Type 6077 ...	250 K	20	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	3 tags	$\frac{1}{8}$	$1\frac{1}{8}$	Plain	C	"	1
7739	Type 7739 ...	250 K	20	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	3 tags	$\frac{1}{8}$	$1\frac{1}{8}$	Plain	C	"	1
6894	Type 6894 ...	250 K	20	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	3 tags	$\frac{1}{8}$	$1\frac{1}{8}$	Slotted	C	"	1
7813	Type 7813 ...	250 K	20	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	3 tags	$\frac{1}{8}$	$1\frac{1}{8}$	Slotted	C	"	1
462	Type 780 ...	250 K	20	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	3 tags	$\frac{1}{8}$	$1\frac{1}{8}$	Slotted	C	"	1
8309	Type 8309 ...	250 K	20	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	—	$\frac{1}{8}$	$1\frac{1}{8}$	Plain	C	"	1
8750	Type 2200 ...	250 K	20	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	3 pins $\frac{1}{2}$ in. long	$\frac{1}{8}$	$1\frac{1}{8}$	Plain	C	"	1
8751	Type 2201 ...	250 K	20	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	3 pins $\frac{1}{2}$ in. long	$\frac{1}{8}$	$1\frac{1}{8}$	Plain	C	"	1
9188	Type 2520 ...	250 K	20	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	3 pins $\frac{1}{2}$ in. long	$\frac{1}{8}$	$1\frac{1}{8}$	Plain	C	"	1
9193	Type 2525 ...	250 K	20	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	3 pins $\frac{1}{2}$ in. long	$\frac{1}{8}$	$1\frac{1}{8}$	Plain	C	"	1
15058	Type 3767 ...	250 K	20	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	—	$\frac{1}{8}$	$1\frac{1}{8}$	Slotted	C	"	1
15860	Type 4543 ...	250 K	20	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	3 pins $\frac{1}{2}$ in. long	$\frac{1}{8}$	$1\frac{1}{8}$	Slotted	C	"	1
15285	Type 3994 ...	250 K	20	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	3 pins $\frac{1}{2}$ in. long	$\frac{1}{8}$	$1\frac{1}{8}$	Slotted	C	"	1
15339	Type 4248 ...	250 K	20	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	3 pins $\frac{1}{2}$ in. long	$\frac{1}{8}$	$1\frac{1}{8}$	Slotted	C	"	1
16104	Type 4755 ...	250 K	20	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	3 pins $\frac{1}{2}$ in. long	$\frac{1}{8}$	$1\frac{1}{8}$	Slotted	C	"	1
9404	Type 2668 ...	250 K	20	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	3 pins $\frac{1}{2}$ in. long	$\frac{1}{8}$	$1\frac{1}{8}$	Slotted	C	"	1
15118	Type 3827 ...	250 K	20	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	—	$\frac{1}{8}$	$1\frac{1}{8}$	Plain	C	"	1
16505	Type 5075 ...	250 K	20	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	—	$\frac{1}{8}$	$1\frac{1}{8}$	Plain	C	"	1
15635	Type 4331 ...	250 K	20	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	—	$\frac{1}{8}$	$1\frac{1}{8}$	—	C	"	1
15499	Type 4208 ...	250 K	20	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	—	$\frac{1}{8}$	$1\frac{1}{8}$	Plain	C	"	1
15679	Type 4375 ...	250 K	20	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	3 × $\frac{1}{2}$ in. solder pins	$\frac{1}{8}$	$1\frac{1}{8}$	Slotted	C	"	1
15029	Type 3738 ...	250 K	—	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	3 tags	$\frac{1}{8}$	$1\frac{1}{8}$	Plain	C	"	1
15505	Type 4214 ...	250 K	—	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	—	$\frac{1}{8}$	$1\frac{1}{8}$	Slotted	C	"	1
16759	Type 5276 ...	330 K	30	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	—	$\frac{1}{8}$	$1\frac{1}{8}$	—	C	"	1
17897	Type 9338 ...	500 K	20	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	—	$\frac{1}{8}$	$1\frac{1}{8}$	—	C	"	1
15053	Type 3762 ...	500 K	10	$1\frac{1}{2}$	$1\frac{1}{16}$	$1\frac{1}{32}$	3 tags $\frac{1}{8}$ in. long	$\frac{1}{8}$	$1\frac{1}{8}$	Slotted	C	"	2

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ± %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty
					Dia. (inches)	Depth (inches)	Other Details	Dia. (inches)	Length (inches)	Other Details			
1	2	3	4	5	6	7	8	9	10	11	12	13	14
RESISTORS—cont.													
Variable potentiometers—cont.													
Carbon composition element—cont.													
15940	Type 4621 ...	500 K	10	1	—	—	—	1	$\frac{3}{16}$	Slotted	C	each	1
16703	Type 5225 ...	500 K	10	1	—	—	—	1	$\frac{3}{16}$	Plain	C	"	1
8875	Type 2297 ...	500 K	15	1	$1\frac{1}{32}$	$\frac{7}{16}$	$\frac{7}{16}$ in. long	1	$\frac{3}{16}$	Plain	C	"	1
8023	Type 8023 ...	500 K	20	1	$1\frac{3}{32}$	$\frac{7}{16}$	$\frac{7}{16}$ in. long	1	1	Slotted	C	"	1
8198	Type 8198 ...	500 K	20	1	$1\frac{3}{32}$	$\frac{7}{16}$	$\frac{7}{16}$ in. long	1	1	Slotted	C	"	1
500	Type 792 ...	500 K	—	1	—	—	—	1	$\frac{3}{16}$	—	C	"	5
8435	Type 8435 ...	500 K	20	1	$1\frac{3}{32}$	$\frac{7}{16}$	$\frac{7}{16}$ in. long	1	$\frac{3}{16}$	Slotted	C	"	1
9330	Type 2631 ...	500 K	20	1	—	—	—	1	$\frac{3}{16}$	Plain	C	"	1
15042	Type 3751 ...	500 K	20	1	—	—	—	1	$\frac{3}{16}$	Slotted	C	"	1
15108	Type 3817 ...	500 K	20	1	—	—	—	1	$\frac{3}{16}$	Slotted	C	"	1
15864	Type 4547 ...	500 K	20	1	—	—	—	1	$\frac{3}{16}$	Slotted	C	"	1
16166	Type 4812 ...	500 K	20	1	$1\frac{3}{32}$	$\frac{7}{16}$	$\frac{7}{16}$ in. long	1	$\frac{3}{16}$	Plain	C	"	1
17956	Type 9340 ...	500 K	20	1	—	—	—	1	$\frac{3}{16}$	With Flat $\frac{3}{8}$ in. long	C	"	1
10484	Type 3398 ...	500 K	15	1	$1\frac{1}{16}$	$\frac{9}{16}$	3 tags	1	$\frac{3}{16}$	Plain	C	"	1
9046	Type 2408 ...	500 K	15	1	$1\frac{1}{16}$	$\frac{9}{16}$	3 tags	1	$\frac{3}{16}$	Slotted	C	"	1
6488	Type 6488 ...	500 K	20	1	$1\frac{1}{16}$	$\frac{9}{16}$	3 tags	1	$\frac{3}{16}$	Slotted	C	"	1
7422	Type 7422 ...	500 K	20	1	$1\frac{1}{16}$	$\frac{9}{16}$	3 tags	1	$\frac{3}{16}$	Plain	C	"	1
6349	Type 6349 ...	500 K	20	1	$1\frac{1}{16}$	$\frac{9}{16}$	3 tags	1	$\frac{3}{16}$	Plain	C	"	1
1192	Type 1192 ...	500 K	10	1	$1\frac{1}{16}$	$\frac{9}{16}$	3 tags	1	$\frac{3}{16}$	Plain	C	"	1
1236	Type 1236 ...	500 K	10	1	$1\frac{1}{16}$	$\frac{9}{16}$	3 tags	1	$\frac{3}{16}$	Plain	C	"	1
1136	Type 1136 ...	500 K	10	1	$1\frac{1}{16}$	$\frac{9}{16}$	3 tags	1	$\frac{3}{16}$	Plain	C	"	1
1118	Type 1118 ...	500 K	10	1	$1\frac{1}{16}$	$\frac{9}{16}$	3 tags	1	$\frac{3}{16}$	Flattened	C	"	1
1324	Type 1324 ...	500 K	10	1	$1\frac{1}{16}$	$\frac{9}{16}$	3 tags	1	$\frac{3}{16}$	Slotted	C	"	1
8109	Type 8109 ...	500 K	10	1	$1\frac{1}{16}$	$\frac{9}{16}$	3 tags	1	$\frac{3}{16}$	Slotted	C	"	1
1319	Type 1319 ...	500 K	10	1	$1\frac{1}{16}$	$\frac{9}{16}$	3 tags	1	$\frac{3}{16}$	Slotted	C	"	1
8715	Type 2177 ...	500 K	15	1	$1\frac{1}{16}$	$\frac{9}{16}$	3 pins $\frac{1}{8}$ in. long	1	$\frac{3}{16}$	Plain	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ± %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Dia. (inches)	Depth (inches)	Other Details	Dia. (inches)	Length (inches)	Other Details			
1	RESISTORS—cont. Variable potentiometers—cont. Carbon composition element—cont.	3	4	5	6	7	8	9	10	11	12	13	14
10328	Type 375 ...	500 K	15	1 1/2	1 1/8	3/16	3 tags	1 1/2	1 1/8	Slotted	C	each	1
10936	Type 397 ...	500 K	15	1 1/2	1 1/8	3/16	3 tags	1 1/2	1 1/8	Plain	C	"	1
556	Type 818 ...	500 K	15	1 1/2	1 1/8	3/16	3 tags	1 1/2	1 1/8	Plain	C	"	1
8338	Type 8338 ...	500 K	15	1 1/2	1 1/8	3/16	3 tags	1 1/2	1 1/8	Plain	C	"	1
1063	Type 1063 ...	500 K	15	1 1/2	1 1/8	3/16	3 tags	1 1/2	1 1/8	Plain 5 B.A. hole	C	"	1
7856	Type 7856 ...	500 K	15	1 1/2	1 1/8	3/16	3 pins	1 1/2	1 1/8	Plain	C	"	1
8878	Type 2300 ...	500 K	15	1 1/2	1 1/8	3/16	3 pins	1 1/2	1 1/8	Plain	C	"	1
10928	Type 3647 ...	500 K	15	1 1/2	1 1/8	3/16	3 pins	1 1/2	1 1/8	Slotted	C	"	1
10924	Type 3644 ...	500 K	15	1 1/2	1 1/8	3/16	3 pins	1 1/2	1 1/8	Slotted	C	"	1
15032	Type 3741 ...	500 K	15	1 1/2	1 1/8	3/16	3 pins	1 1/2	1 1/8	Slotted	C	"	1
17839	Type 9280 ...	500 K	15	1 1/2	1 1/8	3/16	3 pins	1 1/2	1 1/8	Slotted	C	"	1
10608	Type 3483 ...	500 K	20	1 1/2	1 1/8	3/16	3 pins	1 1/2	1 1/8	Slotted	C	"	1
15126	Type 3835 ...	500 K	20	1 1/2	1 1/8	3/16	3 pins	1 1/2	1 1/8	Slotted	C	"	1
15435	Type 4144 ...	500 K	20	1 1/2	1 1/8	3/16	3 pins	1 1/2	1 1/8	Slotted	C	"	1
15855	Type 4538 ...	500 K	20	1 1/2	1 1/8	3/16	3 pins	1 1/2	1 1/8	Slotted	C	"	1
16103	Type 4754 ...	500 K	20	1 1/2	1 1/8	3/16	3 pins	1 1/2	1 1/8	Slotted	C	"	1
17529	Type 5984 ...	500 K	20	1 1/2	1 1/8	3/16	3 pins	1 1/2	1 1/8	Screwdriver slotted	C	"	1
16804	Type 5320 ...	500 K	20	1 1/2	1 1/8	3/16	3 pins	1 1/2	1 1/8	With 1/2 in. flat	C	"	1
16805	Type 5321 ...	500 K	20	1 1/2	1 1/8	3/16	3 pins	1 1/2	1 1/8	With 3/8 in. flat	C	"	1
16723	Type 5244 ...	500 K	20	1 1/2	1 1/8	3/16	3 pins	1 1/2	1 1/8	Plain	C	"	1
10660	Type 3502 ...	500 K	20	1 1/2	1 1/8	3/16	3 tags	1 1/2	1 1/8	Plain	C	"	1
8095	Type 8095 ...	500 K	20	1 1/2	1 1/8	3/16	3 tags	1 1/2	1 1/8	Plain	C	"	1
16314	Type 4930 ...	500 K	20	1 1/2	1 1/8	3/16	3 pins	1 1/2	1 1/8	Slotted	C	"	1
8061	Type 8061 ...	500 K	20	1 1/2	1 1/8	3/16	3 pins	1 1/2	1 1/8	Slotted	C	"	1
16117	Type 4766 ...	500 K	20	1 1/2	1 1/8	3/16	3 pins	1 1/2	1 1/8	Slotted	C	"	1
7978	Type 7978 ...	500 K	20	1 1/2	1 1/8	3/16	3 pins	1 1/2	1 1/8	Slotted	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ± %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Dia. (inches)	Depth (inches)	Other Details	Dia. (inches)	Length (inches)	Other Details			
1	RESISTORS—cont. Variable potentiometers—cont. Carbon composition element—cont.												
17225	Type 1725 ...	500 K	20	1 1/2	1 1/8	3 tags	1 1/8	1 1/8	Slotted	C	each	1	
15887	Type 4569 ...	500 K	20	1 1/2	1 1/8	3 tags	1 1/8	1 1/8	Slotted	C	"	1	
15888	Type 4570 ...	500 K	20	1 1/2	1 1/8	3 tags	1 1/8	1 1/8	Slotted	C	"	1	
7597	Type 7597 ...	500 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Plain	C	"	1	
195	Type 663 ...	500 K	20	1 1/2	1 1/8	3 tags	1 1/8	1 1/8	1/2 in. flat	C	"	1	
9313	Type 2621 ...	500 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	1/2 in. flat	C	"	1	
9328	Type 2630 ...	500 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Plain	C	"	1	
9406	Type 2670 ...	500 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Plain	C	"	1	
9407	Type 2671 ...	500 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Slotted	C	"	1	
9652	Type 2884 ...	500 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Slotted	C	"	1	
8598	Type 2106 ...	500 K	20	1 1/2	1 1/8	3 tags	1 1/8	1 1/8	Slotted	C	"	1	
15471	Type 4180 ...	500 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Slotted	C	"	1	
15230	Type 3939 ...	500 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Slotted	C	"	1	
15725	Type 4419 ...	500 K	20	1 1/2	1 1/8	3 pins	1 1/8	1 1/8	Slotted	C	"	1	
6587	Type 6587 ...	500 K	20	2	1 1/8	3 pins	1 1/8	1 1/8	Plain	C	"	1	
390	Type 763 ...	500 K	—	2	1 1/8	—	—	—	With hole	C	"	1	
11570	Type 488 ...	500 K	—	—	—	—	—	—	—	C	"	1	
8858	Type 2287 ...	500 K	20	2	—	—	—	—	Screwdriver slot	C	"	1	
15795	Type 4479 ...	500 K	20	2	—	—	—	—	—	C	"	1	
16417	Type 4997 ...	500 K	20	2	—	—	—	—	—	C	"	1	
16357	Type 4947 ...	500 K	10	2	—	—	—	—	Plain	C	"	1	
6147	Type 6147 ...	500 K	—	—	—	—	—	—	—	C	"	1	
7562	Type 7562 ...	500 K	—	—	—	—	—	—	Flat	C	"	1	
15255	Type 3964 ...	750 K	20	1 1/2	—	—	—	—	—	C	"	1	
17898	Type 9339 ...	1 M	20	1 1/2	—	—	—	—	Slotted	C	"	1	
8314	Type 8314 ...	1 M	10	1 1/2	—	—	—	—	Slotted	C	"	1	
8313	Type 8313 ...	1 M	10	1 1/2	—	3 tags	1 1/8	1 1/8	Slotted	C	"	1	
						3 tags	1 1/8	1 1/8	Plain 5 B.A. hole	C	"	1	

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ± %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Dia. (inches)	Depth (inches)	Other Details	Dia. (inches)	Length (inches)	Other Details			
1	RESISTORS—cont. Variable potentiometers—cont. Carbon composition element—cont.												
16158	Type 4805 ...	1 M	10	1/4	—	—	—	1/4	3 3/8	Screwdriver slot	C	each	1
15088	Type 3797 ...	1 M	20	1/4	—	—	—	1/4	3 3/8	Slotted	C	"	1
17621	Type 9074 ...	1 M	20	1/4	—	—	—	1/4	3 3/8	Slotted	C	"	3
15093	Type 3803 ...	1 M	20	1/4	—	—	—	1/4	3 3/8	Slotted	C	"	1
16214	Type 4843 ...	1 M	20	1/4	—	—	—	1/4	3 3/8	—	C	"	1
16674	Type 5198 ...	1 M	20	1/4	—	—	—	1/4	3 3/8	Slotted	C	"	1
10957	Type 3672 ...	1 M	20	1/4	—	—	—	1/4	3 3/8	Slotted	C	"	1
6318	Type 6318 ...	1 M	20	1/4	1 1/8	1/8	1/8	1/4	3 3/8	—	C	"	1
8992	Type 2369 ...	1 M	20	1/4	1 1/8	1/8	1/8	1/4	3 3/8	Plain	C	"	1
15091	Type 2533 ...	1 M	20	1/4	1 1/8	1/8	1/8	1/4	3 3/8	Slotted	C	"	1
7132	Type 3800 ...	1 M	10	1/4	1 1/8	1/8	1/8	1/4	3 3/8	Slotted	C	"	1
9047	Type 2409 ...	1 M	15	1/4	1 1/8	1/8	1/8	1/4	3 3/8	1/2 slot	C	"	1
15678	Type 4374 ...	1 M	20	1/4	1 1/8	1/8	1/8	1/4	3 3/8	Slotted	C	"	1
8330	Type 8330 ...	1 M	20	1/4	1 1/8	1/8	1/8	1/4	3 3/8	Slotted	C	"	1
15329	Type 4038 ...	1 M	20	1/4	1 1/8	1/8	1/8	1/4	3 3/8	Plain	C	"	1
8111	Type 8111 ...	1 M	10	1/4	1 1/8	1/8	1/8	1/4	3 3/8	Slotted	C	"	1
1441	Type 1441 ...	1 M	10	1/4	1 1/8	1/8	1/8	1/4	3 3/8	Slotted	C	"	1
8779	Type 2229 ...	1 M	10	1/4	1 1/8	1/8	1/8	1/4	3 3/8	Slotted	C	"	1
920	Type 958 ...	1 M	15	1/4	1 1/8	1/8	1/8	1/4	3 3/8	Plain	C	"	1
1521	Type 1521 ...	1 M	15	1/4	1 1/8	1/8	1/8	1/4	3 3/8	Plain 5 B.A. hole	C	"	1
8880	Type 2302 ...	1 M	15	1/4	1 1/8	1/8	1/8	1/4	3 3/8	Plain 5 B.A. hole	C	"	1
1689	Type 1689 ...	1 M	15	1/4	1 1/8	1/8	1/8	1/4	3 3/8	Slotted	C	"	1
7078	Type 7078 ...	1 M	15	1/4	1 1/8	1/8	1/8	1/4	3 3/8	Slotted	C	"	1
7852	Type 7852 ...	1 M	15	1/4	1 1/8	1/8	1/8	1/4	3 3/8	Plain	C	"	1
15233	Type 3942 ...	1 M	20	1/4	1 1/8	1/8	1/8	1/4	3 3/8	Plain	C	"	1
7332	Type 7332 ...	1 M	20	1/4	1 1/8	1/8	1/8	1/4	3 3/8	Slotted	C	"	1

SECTION 10W—*cont.*

RADIO RESISTORS

Ref. No.	Nomenclature	Value in Ohms	Tolerance ± %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Dia. (inches)	Depth (inches)	Other Details	Dia. (inches)	Length (inches)	Other Details			
1	2	3	4	5	6	7	8	9	10	11	12	13	14
RESISTORS—<i>cont.</i>													
Variable potentiometers—<i>cont.</i>													
Carbon composition element—<i>cont.</i>													
6464	Type 6464 ...	1 M	20	1 1/2	1 1/8	3/16	3 tags	1	1 1/8	Slotted Plain	C	each	1
8310	Type 8310 ...	1 M	20	1 1/2	1 1/8	—	—	1	1 1/8	—	C	"	1
16139	Type 4786 ...	1 M	20	1 1/2	1 1/8	—	—	1	1 1/8	—	C	"	1
16282	Type 4902 ...	1 M	20	1 1/2	1 1/8	—	—	1	1 1/8	Screwdriver slot	C	"	1
16261	Type 4882 ...	1 M	20	1 1/2	1 1/8	—	—	1	1 1/8	Slotted Plain	C	"	1
8250	Type 8250 ...	1 M	10	1 1/2	1 1/8	—	—	1	1 1/8	—	C	"	1
1563	Type 1563 ...	1 M	10	1 1/2	1 1/8	—	—	1	1 1/8	—	C	"	1
1913	Type 1913 ...	1 M	10	1 1/2	1 1/8	—	—	1	1 1/8	—	C	"	1
15411	Type 4120 ...	1 M	20	1 1/2	1 1/8	—	3 pins 1/2 in. long	1	1 1/8	Plain	C	"	1
7596	Type 7596 ...	1 M	20	1 1/2	1 1/8	—	3 pins 1/2 in. long	1	1 1/8	Plain	C	"	1
8676	Type 2154 ...	1 M	20	1 1/2	1 1/8	—	3 pins 1/2 in. long	1	1 1/8	Plain	C	"	1
8752	Type 2202 ...	1 M	20	1 1/2	1 1/8	—	3 pins 1/2 in. long	1	1 1/8	Plain	C	"	1
9291	Type 2615 ...	1 M	20	1 1/2	1 1/8	—	3 pins 1/2 in. long	1	1 1/8	Tapped 5 B.A. Plain 3/8 in. flat.	C	"	1
9303	Type 2616 ...	1 M	20	1 1/2	1 1/8	—	3 pins 1/2 in. long	1	1 1/8	Plain 3/8 in. flat, Tapped 5 B.A.	C	"	1
9304	Type 2617 ...	1 M	20	1 1/2	1 1/8	—	3 pins 1/2 in. long	1	1 1/8	Plain 3/8 in. flat	C	"	1
9310	Type 2618 ...	1 M	20	1 1/2	1 1/8	—	3 pins 1/2 in. long	1	1 1/8	Plain 3/8 in. flat	C	"	1
8694	Type 2164 ...	1 M	20	1 1/2	1 1/8	—	3 pins 1/2 in. long	1	1 1/8	Slotted	C	"	1
9513	Type 2766 ...	1 M	20	1 1/2	1 1/8	—	3 pins 1/2 in. long	1	1 1/8	Slotted	C	"	1
9653	Type 2885 ...	1 M	20	1 1/2	1 1/8	—	3 pins 1/2 in. long	1	1 1/8	Slotted	C	"	1
9664	Type 2896 ...	1 M	20	1 1/2	1 1/8	—	3 pins 1/2 in. long	1	1 1/8	Slotted	C	"	1
15150	Type 3859 ...	1 M	20	1 1/2	1 1/8	—	3 pins 1/2 in. long	1	1 1/8	Slotted	C	"	1
15165	Type 3874 ...	1 M	20	1 1/2	1 1/8	—	3 pins 1/2 in. long	1	1 1/8	Slotted	C	"	1
15231	Type 3940 ...	1 M	20	1 1/2	1 1/8	—	3 pins 1/2 in. long	1	1 1/8	Slotted	C	"	1
15989	Type 4666 ...	1 M	20	1 1/2	1 1/8	—	3 pins 1/2 in. long	1	1 1/8	Slotted	C	"	1
15801	Type 4484 ...	1 M	20	1 1/2	1 1/8	—	3 × 1/2 in. solder pins	1	1 1/8	Slotted	C	"	1

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ± %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Dia. (inches)	Depth (inches)	Other Details	Dia. (inches)	Length (inches)	Other Details			
1	RESISTORS—cont. Variable potentiometers—cont. Carbon composition element—cont.												
10961	Type 3676 ...	2 M	20	1/4	—	—	—	1 3/8	Standard	C	each	—	
16147	Type 4794 ...	2 M	20	1/4	—	—	—	1 3/8	Slotted	C	"	1	
16675	Type 5199 ...	2 M	10	1/4	—	—	—	1 3/8	Slotted	C	"	1	
15458	Type 4167 ...	2 M	20	1/4	1 1/2	—	—	1 3/8	Slotted	C	"	1	
8295	Type 8295 ...	2 M	20	1/4	1 1/2	—	—	1 3/8	Plain	C	"	1	
15422	Type 4131 ...	2 M	20	1/4	1 1/2	—	—	1 3/8	Plain	C	"	1	
921	Type 959 ...	2 M	5	1/4	1 1/2	—	—	1 3/8	Plain	C	"	1	
1305	Type 1305 ...	2 M	10	1/4	1 1/2	—	—	1 3/8	—	C	"	1	
1135	Type 1135 ...	2 M	10	1/4	1 1/2	—	—	1 3/8	Plain	C	"	1	
1512	Type 1512 ...	2 M	10	1/4	1 1/2	—	—	1 3/8	Slotted	C	"	1	
9227	Type 2554 ...	2 M	10	1/4	1 1/2	—	—	1 3/8	Plain	C	"	1	
6139	Type 6139 ...	2 M	10	1/4	1 1/2	—	—	1 3/8	Slotted	C	"	1	
1065	Type 1065 ...	2 M	15	1/4	1 1/2	—	—	1 3/8	Plain	C	"	1	
197	Type 665 ...	2 M	15	1/4	1 1/2	—	—	1 3/8	Plain	C	"	1	
945	Type 973 ...	2 M	15	1/4	1 1/2	—	—	1 3/8	Plain	C	"	1	
1994	Type 1994 ...	2 M	15	1/4	1 1/2	—	—	1 3/8	Plain	C	"	1	
1631	Type 1631 ...	2 M	15	1/4	1 1/2	—	—	1 3/8	Plain	C	"	1	
15033	Type 3742 ...	2 M	15	1/4	—	—	—	1 3/8	Slotted	C	"	1	
10678	Type 3516 ...	2 M	20	1/4	—	—	—	1 3/8	Plain	C	"	1	
7934	Type 7934 ...	2 M	20	1/4	—	—	—	1 3/8	Plain	C	"	1	
8278	Type 8278 ...	2 M	20	1/4	—	—	—	1 3/8	Slotted	C	"	1	
7518	Type 7518 ...	2 M	20	1/4	—	—	—	1 3/8	Slotted	C	"	1	
15724	Type 4418 ...	2 M	20	1/4	—	—	—	1 3/8	Plain	C	"	1	
16075	Type 4731 ...	2 M	20	1/4	—	—	—	1 3/8	Plain	C	"	1	
8376	Type 8376 ...	2 M	20	1/4	—	—	—	1 3/8	Plain	C	"	1	
8651	Type 2149 ...	2 M	20	1/4	—	—	—	1 3/8	Plain	C	"	1	

SECTION 10W—*cont.*

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ± %	Wattage	DIMENSIONS AND DETAILS OF BODY		Other Details	DIMENSIONS AND DETAILS OF SPINDLE		Class of Store	Denom. of Qty.	Carton Unit Qty.
					Dia. (inches)	Depth (inches)		Dia. (inches)	Length (inches)			
1	RESISTORS—<i>cont.</i> Variable potentiometers—<i>cont.</i> Carbon composition element—<i>cont.</i>											
9558	Type 2809 ...	2 M	20	1 1/2	1 1/2	3 solder pins } 1/2 in. long	1 1/2	7 3/8	Plain	C	each	1
15861	Type 4544 ...	2 M	20	1 1/2	1 1/2	3 solder pins } 1/2 in. long	1 1/2	7 3/8	Slotted	C	"	1
16033	Type 4701 ...	2 M	20	1 1/2	1 1/2	3 solder pins } 1/2 in. long	1 1/2	7 3/8	Slotted	C	"	1
15866	Type 4549 ...	2 M	20	1 1/2	1 1/2	3 solder pins } 1/2 in. long	1 1/2	7 3/8	Slotted	C	"	1
16259	Type 4880 ...	2 M	20	1 1/2	1 1/2	3 solder pins } 1/2 in. long	1 1/2	7 3/8	Slotted	C	"	1
8110	Type 8110 ...	2 M	20	1 1/2	1 1/2	3 tags	1 1/2	7 3/8	Plain	C	"	1
15498	Type 4207 ...	2 M	20	1 1/2	1 1/2	3 tags	1 1/2	7 3/8	Slotted	C	"	1
9189	Type 2521 ...	2.5 M	20	1 1/2	1 1/2	3 tags	1 1/2	7 3/8	Plain	C	"	1
16502	Type 5072 ...	2.5 M	20	1 1/2	1 1/2	3 tags	1 1/2	7 3/8	Slotted	C	"	1
17957	Type 9341 ...	5 M	15	1 1/2	1 1/2	3 tags	1 1/2	7 3/8	Slotted	C	"	1
16209	Type 4837 ...	5 M	20	1 1/2	1 1/2	3 tags	1 1/2	7 3/8	Screwdriver slot	C	"	1
17530	Type 5985 ...	5 M	20	1 1/2	1 1/2	3 tags	1 1/2	7 3/8	Plain	C	"	1
16303	Type 4921 ...	5 M	20	1 1/2	1 1/2	3 tags	1 1/2	7 3/8	Slotted	C	"	1
15574	Type 4279 ...	5 M	20	1 1/2	1 1/2	3 tags	1 1/2	7 3/8	Flattened 1/2 in. flat	C	"	1
16944	Type 5453 ...	5 M	20	1 1/2	1 1/2	3 tags	1 1/2	7 3/8	Flattened 1/2 in. flat	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom of Qty	Carton Unit Qty	
					Diam. (inches)	Depth (inches)	Other Details	Diam. (inches)	Length (inches)	Other Details				
1	RESISTORS—cont. Variable potentiometers—cont. Wire-wound element:—													
15967	Type 4648	$\frac{1}{2}$	10	2	—	—	—	0.187	$\frac{1}{16}$	—	—	C	each	1
16569	Type 5137	$\frac{1}{2}$	10	2 $\frac{1}{2}$	—	—	—	$\frac{1}{4}$	$\frac{1}{16}$	Plain	—	C	"	1
16120	Type 4679	1	20	2	—	—	—	$\frac{1}{16}$	$\frac{1}{16}$	Slotted	—	C	"	1
8788	Type 2234	1	10	2	$\frac{7}{16}$	—	—	$\frac{1}{16}$	$\frac{1}{4}$	Slotted	—	C	"	1
15783	Type 4467	1	5	3	$\frac{1}{16}$	$\frac{1}{16}$	Tags	$\frac{1}{4}$	$\frac{1}{4}$	Plain	—	C	"	1
1685	Type 1685	1	10	4	$\frac{1}{16}$	$\frac{1}{16}$	Terminals	$\frac{1}{4}$	$\frac{1}{4}$	Slotted	—	C	"	1
15488	Type 4197	1.3	10	—	—	—	—	—	—	—	—	C	"	1
1659	Type 1659	1.7	—	—	—	—	—	—	—	—	—	C	"	1
1093	Type 1093	1.9	—	—	—	—	—	—	—	—	—	C	"	1
9680	Type 2910	2.5	10	4	—	—	Terminals	$\frac{1}{4}$	$\frac{1}{8}$	Plain	—	C	"	1
15987	Type 4664	2.5	10	$\frac{1}{2}$	—	—	—	—	—	—	—	C	"	1
16352	Type 4942	2.6	—	—	—	—	—	—	—	—	—	C	"	1
7767	Type 82	4	—	10	—	—	—	—	—	Lead screw	—	C	"	1
15986	Type 4663	4	—	$\frac{1}{2}$	—	—	—	—	—	—	—	C	"	1
16948	Type 5457	5	10	—	—	—	—	—	—	—	—	C	"	1
16809	Type 5325	5	5	1	—	—	—	—	—	—	—	C	"	1
16932	Type 5442	5	10	2	—	—	—	—	—	—	—	C	"	1
16092	Type 4748	5	10	4	—	—	—	$\frac{1}{4}$	$\frac{1}{16}$	—	—	C	"	1
15636	Type 4332	5	5	4	—	—	Terminals	$\frac{1}{4}$	$\frac{3}{16}$	Slotted	—	C	"	1
15981	Type 4658	5	5	4	$\frac{1}{16}$	$\frac{1}{16}$	Terminals	$\frac{1}{4}$	$\frac{1}{4}$	$\frac{1}{2}$ flat	—	C	"	1
1027	Type 1027	5	—	—	—	—	—	—	—	—	—	C	"	1
1131	Type 1131	5.7	—	—	—	—	—	—	—	—	—	C	"	1
6908	Type 1131	8	10	—	—	—	—	—	—	—	—	C	"	1
1197	Type 6908	8	10	1 to 2	$\frac{11}{16}$	$\frac{11}{16}$	Tags	$\frac{1}{4}$	$\frac{3}{8}$	Slotted	—	C	"	1
15034	Type 1197	10	5	4	—	—	—	—	—	—	—	C	"	1
16168	Type 3743	10	10	1	—	—	—	—	—	Plain	—	C	"	1
16168	Type 4814	10	10	1	—	—	—	—	—	—	—	C	"	1
6819	Type 6819	10	10	3	—	—	—	—	—	With $\frac{3}{16}$ in. flat	—	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Diam. (inches)	Depth (inches)	Other Details	Diam. (inches)	Length (inches)	Other Details			
1	2	3	4	5	6	7	8	9	10	11	12	13	14
16787	Type 5303	10.5	—	—	—	—	—	—	—	—	C	each	1
16793	Type 5309	12	—	100	—	—	—	—	—	—	C	"	1
16683	Type 5207	16	—	—	—	—	—	—	—	—	C	"	1
1574	Type 1574	16	—	15/20	2 1/8	1 1/8	Terminals	—	—	—	C	"	1
1129	Type 1129	17.5	—	—	—	—	—	—	—	—	C	"	1
1130	Type 1130	17.5	—	—	—	—	—	—	—	—	C	"	1
18012	Type 9390	18.5	—	—	—	—	—	—	—	—	C	"	1
16621	Type 5180	20	—	—	—	—	—	—	—	—	C	"	1
558	Type 820	20	—	4	1 1/4	1 1/8	Terminals	—	1 1/8	—	C	"	1
16795	Type 5311	20	10	40	—	—	—	—	—	—	C	"	1
8106	Type 8106	20	5	50	3 1/4	2 1/8	Terminals	—	1	Slotted	C	"	1
16356	Type 4946	23.5	10	—	—	—	—	—	—	—	C	"	1
15932	Type 4613	25	—	1	—	—	—	—	—	—	C	"	1
8582	Type 2090	25	10	1 to 2	—	—	Tags	—	—	Slotted	C	"	1
10526	Type 3429	25	20	—	1 1/8	3 1/8	Tags	—	—	—	C	"	1
16682	Type 5206	25	10	2	1 1/8	1 1/8	—	—	—	—	C	"	1
10929	Type 3648	25.6	—	—	—	—	—	—	—	—	C	"	1
6291	Type 6291	30	20	1	—	—	—	—	—	—	C	"	1
8623	Type 2128	30	5	2 1/2	1 1/8	3/4	Terminals	—	—	With 3/8 in. flat	C	"	1
15117	Type 3826	30	10	3	—	—	—	—	—	—	C	"	1
9224	Type 2551	30	10	4	1 1/8	3/8	Terminals	—	—	—	C	"	1
16763	Type 5280	30	10	4	—	—	—	—	—	—	C	"	1
16319	Type 4935	30	—	5	—	—	—	—	—	—	C	"	1
1267	Type 1267	31	—	—	—	—	—	—	—	—	C	"	1
15476	Type 4185	32	10	50	3 1/4	2 1/8	Terminals	—	—	—	C	"	1
16784	Type 5301	35	—	—	10 1/8	3 3/8	Slider bar type; height 6 1/8, fixing centres 9 1/8	—	—	—	C	"	1
16784	Type 5301	40	7.5	4	—	—	—	—	—	—	C	"	1

RESISTORS—cont.
Variable potentiometers—cont.
Wire-wound element—cont.

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom of Qty.	Carton Unit Qty	
					Diam. (inches)	Depth (inches)	Other Details	Diam. (inches)	Length (inches)	Other Details				
1														
	RESISTORS—cont.													
	Variable potentiometers—cont.													
	Wire-wound element—cont.													
8429	Type 8429	50	—	1	—	—	—	—	—	—	—	—	—	1
15934	Type 4615	50	—	2	—	—	—	—	—	—	—	—	—	1
16250	Type 4875	50	10	2	—	—	—	—	—	—	—	—	—	1
9231	Type 2558	50	10	4	1 1/8	3/8	Terminals	1/4	1/8	1/8	—	—	—	1
7544	Type 7544	50	5	4	1 1/8	3/8	Terminals	1/4	1/8	1/8	—	—	—	1
8969	Type 2358	50	10	4	1 1/8	3/8	Terminals	1/4	1/8	1/8	—	—	—	1
8781	Type 2231	50	10	4	1 1/8	3/8	Terminals	1/4	1/8	1/8	—	—	—	1
16514	Type 5084	50	10	5	—	—	—	—	—	—	—	—	—	1
16714	Type 5235	50	5	50	—	—	—	—	—	—	—	—	—	1
15620	Type 4316	50	10	50	2 1/2	1 1/8	Terminals	1/4	1/8	1/8	—	—	—	1
10905	Type 3631	50	10	65	—	—	—	—	—	—	—	—	—	5
15086	Type 3795	55	10	1	—	—	—	—	—	—	—	—	—	1
15536	Type 4245	68	5	—	—	—	—	—	—	—	—	—	—	1
16022	Type 4694	75	5	—	—	—	—	—	—	—	—	—	—	1
15482	Type 4191	75	—	1	—	—	—	—	—	—	—	—	—	1
15959	Type 4640	75	10	1	—	—	—	—	—	—	—	—	—	1
17772	Type 9217	75	20	2	—	—	—	—	—	—	—	—	—	1
10931	Type 3650	80	—	3	—	—	—	—	—	—	—	—	—	1
15399	Type 4108	80	—	20	—	—	—	—	—	—	—	—	—	1
17526	Type 5981	100	—	1	—	—	—	—	—	—	—	—	—	1
16821	Type 5336	100	10	1	—	—	—	—	—	—	—	—	—	1
16571	Type 5138	100	10	1	—	—	—	—	—	—	—	—	—	1
16602	Type 5162	100	10	2	—	—	—	—	—	—	—	—	—	1
10690	Type 3523	100	10	3	—	—	—	—	—	—	—	—	—	1
9478	Type 2734	100	5	3	—	—	—	—	—	—	—	—	—	1
1600	Type 1600	100	—	3	—	—	—	—	—	—	—	—	—	1
7799	Type 7799	100	10	3	1 1/8	1 1/8	Tags Terminals	1/4	1/8	1/8	—	—	—	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Diam. (inches)	Depth (inches)	Other Details	Diam. (inches)	Length (inches)	Other Details			
1	2	3	4	5	6	7	8	9	10	11	12	13	14
	RESISTORS—cont. Variable potentiometers—cont. Wire-wound element—cont.												
8350	Type 8350	100	10	3	$1\frac{11}{16}$	$\frac{3}{16}$	Terminals	$1\frac{1}{4}$	$1\frac{1}{8}$	Slotted	C	each	1
1567	Type 1567	100	20	3	$1\frac{11}{16}$	$\frac{3}{16}$	Tags	$1\frac{1}{4}$	$1\frac{1}{8}$	Slotted, with locking bush	C	"	1
16245	Type 4870	100	—	4	—	—	—	—	$1\frac{1}{8}$	Plain	C	"	1
17420	Type 5876	100	5	4	—	—	—	—	$1\frac{1}{8}$	Plain	C	"	1
202	Type 670	100	10	4	$1\frac{3}{8}$	$1\frac{1}{8}$	Terminals	$1\frac{1}{4}$	$1\frac{1}{8}$	Slotted	C	"	1
611	Type 836	100	—	4	$1\frac{3}{8}$	$\frac{1}{8}$	Terminals	$1\frac{1}{4}$	$1\frac{1}{8}$	Plain	C	"	1
16886	Type 5396	100	10	5	—	—	—	—	$1\frac{1}{8}$	Plain	C	"	1
10721	Type 3549	100	5	5	—	—	—	—	$1\frac{1}{8}$	Plain	C	"	2
1356	Type 1356	100	10	5	—	—	—	—	$1\frac{1}{8}$	Plain	C	"	1
15273	Type 3982	100	5	5	$1\frac{7}{8}$	$\frac{1}{4}$	Tags	$1\frac{1}{4}$	$1\frac{1}{8}$	Slotted	C	"	1
15907	Type 4588	100	5	5	$1\frac{7}{8}$	$\frac{1}{4}$	Tags	$1\frac{1}{4}$	$1\frac{1}{8}$	Plain	C	"	1
17799	Type 9244	120	10	—	—	—	—	—	$1\frac{7}{8}$	Slotted	C	"	1
15713	Type 4408	150	3	—	—	—	—	—	$1\frac{7}{8}$	Plain	C	"	1
16713	Type 5234	150	5	—	—	—	—	—	$1\frac{7}{8}$	Plain	C	"	1
15781	Type 4465	150	10	1	—	—	—	—	$1\frac{7}{8}$	Plain	C	"	1
17837	Type 9278	150	10	1	—	—	—	—	$1\frac{7}{8}$	Slotted	C	"	1
1534	Type 1534	150	10	5	$1\frac{11}{16}$	$\frac{3}{16}$	Terminals	$1\frac{1}{4}$	$1\frac{1}{8}$	Plain	C	"	1
6445	Type 6445	150	10	5	$1\frac{11}{16}$	$\frac{3}{16}$	Tags	$1\frac{1}{4}$	$1\frac{1}{8}$	Plain	C	"	1
1263	Type 1263	150	5	20	$1\frac{11}{16}$	$\frac{3}{16}$	Terminals	$1\frac{1}{4}$	$1\frac{1}{8}$	Plain	C	"	1
8831	Type 2262	150	10	—	—	—	—	—	$1\frac{11}{16}$	Slotted	C	"	1
16689	Type 5212	150	—	100	—	—	—	—	$1\frac{11}{16}$	—	C	"	1
17401	Type 5857	200	10	1	—	—	—	—	$1\frac{7}{8}$	—	C	"	1
16426	Type 5006	200	10	2	$1\frac{11}{16}$	$\frac{1}{4}$	Tags	$1\frac{1}{4}$	$1\frac{1}{8}$	Slotted	C	"	1
10917	Type 3638	200	—	—	—	—	—	—	$1\frac{1}{2}$	—	C	"	1
15522	Type 4231	200	10	2	—	—	—	—	$1\frac{1}{2}$	Slotted	C	"	1
10253	Type 379	200	10	3	$1\frac{11}{16}$	$\frac{1}{4}$	—	$1\frac{1}{4}$	$1\frac{1}{8}$	Slotted	C	"	1
15950	Type 4631	200	10	3	$1\frac{11}{16}$	$\frac{1}{4}$	Terminals	$1\frac{1}{4}$	$1\frac{1}{8}$	Plain	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Score	Denom. of Qty.	Carton Unit Qty.
					Diam. (inches)	Depth (inches)	Other Details	Diam. (inches)	Length (inches)	Other Details			
1	2	3	4	5	6	7	8	9	10	11	12	13	14
	RESISTORS—cont. Variable potentiometers—cont. Wire-wound element—cont.												
7545	Type 7545	200	5	4	1 13/16	—	—	—	1 1/8	Slotted	C	each	1
15637	Type 4333	200	5	4	1 17/8	3/8	—	—	1 3/8	1/2 Flat	C	"	1
8398	Type 8398	200	5	5	1 7/8	3/8	—	—	1 3/8	Slotted	C	"	1
7809	Type 7809	200	10	10	2 1/2	1 1/2	—	—	3	Plain	C	"	1
16801	Type 5317	200	5	4	—	—	—	—	1 1/8	Slotted	C	"	1
15621	Type 4317	200	5	4	—	—	—	—	1 1/8	—	C	"	1
16802	Type 5318	200	5	4	—	—	—	—	1 1/8	Slotted	C	"	1
8227	Type 8227	200	10	15 to 20	3 3/8	2 3/8	—	—	1 1/8	Plain	C	"	1
16496	Type 5066	200	10	—	—	—	—	—	1 1/8	—	C	"	1
16433	Type 5012	250	10	1	—	—	—	—	1 1/8	6 B.A. 0.15 in. from end	C	"	1
15941	Type 4622	250	10	2	1 1/2	1 3/8	Tags	1/2	1 3/8	—	C	"	1
10685	Type 3520	250	10	2	—	—	—	—	1 3/8	Plain	C	"	1
6290	Type 6290	250	5	2 1/2	—	—	—	—	1 3/8	Slotted	C	"	1
1264	Type 1264	250	5	20	2 3/4	1 1/8	—	—	1 3/8	Plain	C	"	1
15365	Type 4074	300	10	1	1 3/8	3/8	—	—	1 3/8	Plain	C	"	1
8834	Type 2265	300	10	2 1/2	1 3/8	3/8	—	—	1 3/8	Slotted	C	"	1
15453	Type 4162	300	5	4	—	—	—	—	1 3/8	Plain	C	"	1
16501	Type 5071	300	5	—	—	—	—	—	1 3/8	—	C	"	1
11109	Type 454	400	5	3	1 1/2	5/8	—	—	1 3/8	Plain	C	"	1
17995	Type 9373	400	5	5	—	—	—	—	1 3/8	Plain	C	"	1
16252	Type 4877	400	5	3	—	—	—	—	1 3/8	Plain	C	"	1
16655	Type 5189	400	5	4	—	—	—	—	1 3/8	Plain	C	"	1
7076	Type 7076	400	10	4	1 13/16	11/16	—	—	1 3/8	Slotted	C	"	1
8534	Type 2050	400	10	5	1 1/2	2 1/16	—	—	1 3/8	Slotted	C	"	1
16497	Type 5067	400	10	—	—	—	—	—	1 3/8	—	C	"	1
1371	Type 1371	450	10	100	4 1/2	2 1/8	—	—	1 3/8	Mounting	C	"	1
15971	Type 4650	500	20	1	—	—	—	—	1 3/8	Slotted	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty
					Diam. (inches)	Depth (inches)	Other Details	Diam. (inches)	Length (inches)	Other Details			
1	RESISTORS—cont. Variable potentiometers—cont. Wire-wound element—cont.												
10614	Type 3488	500	20	1 to 2	$\frac{11}{16}$	$\frac{3}{16}$	Tags	$\frac{1}{4}$	$\frac{11}{16}$	Slotted	C	each	1
15516	Type 4225	500	10	2	$\frac{11}{16}$	$\frac{11}{16}$	Tags	$\frac{1}{16}$	$\frac{3}{16}$	Slotted	C	"	1
10840	Type 3606	500	10	2	$\frac{11}{16}$	$\frac{11}{16}$	Tags	$\frac{1}{16}$	$\frac{3}{16}$	Plain	C	"	1
16676	Type 5200	500	5	$2\frac{1}{2}$	—	—	—	—	$\frac{1}{16}$	Plain	C	"	1
9013	Type 2387	500	10	$2\frac{1}{2}$	—	—	—	—	$\frac{1}{16}$	Slotted	C	"	1
403	Type 765	500	5	3	$\frac{11}{16}$	$\frac{1}{16}$	Terminals	$\frac{1}{4}$	$\frac{1}{16}$	Slotted	C	"	1
15260	Type 3969	500	10	3	$\frac{11}{16}$	$\frac{1}{16}$	Terminals	$\frac{1}{4}$	$\frac{1}{16}$	Plain	C	"	1
7434	Type 7434	500	10	3	$\frac{11}{16}$	$\frac{1}{16}$	Terminals	$\frac{1}{4}$	$\frac{1}{16}$	Slotted	C	"	1
1740	Type 1740	500	10	3	$\frac{11}{16}$	$\frac{1}{16}$	Tags	$\frac{1}{4}$	$\frac{1}{16}$	Slotted	C	"	1
1742	Type 1742	500	10	3	$\frac{11}{16}$	$\frac{1}{16}$	Tags	$\frac{1}{4}$	$\frac{1}{16}$	Slotted	C	"	1
9003	Type 2379	500	10	3	$\frac{11}{16}$	$\frac{1}{16}$	Tags	$\frac{1}{4}$	$\frac{1}{16}$	Plain	C	"	1
15456	Type 4165	500	20	3	$\frac{11}{16}$	$\frac{1}{16}$	Terminals	$\frac{1}{4}$	$\frac{1}{16}$	Slotted	C	"	1
10518	Type 3422	500	20	3	$\frac{11}{16}$	$\frac{1}{16}$	Tags	$\frac{1}{4}$	$\frac{1}{16}$	Slotted	C	"	1
9014	Type 2388	500	10	3	$\frac{11}{16}$	$\frac{1}{16}$	Terminals	$\frac{1}{4}$	$\frac{1}{16}$	Plain	C	"	1
16783	Type 5300	500	5	3 to 4	$\frac{11}{16}$	$\frac{1}{16}$	—	$\frac{1}{4}$	$\frac{1}{16}$	—	C	"	1
8833	Type 2264	500	10	4	$\frac{11}{16}$	$\frac{1}{16}$	Terminals	$\frac{1}{4}$	$\frac{1}{16}$	Plain 360° rotation	C	"	1
10696	Type 3528	500	10	4	$\frac{11}{16}$	$\frac{1}{16}$	Terminals	$\frac{1}{4}$	$\frac{1}{16}$	Plain	C	"	1
7196	Type 7196	500	10	4	—	—	—	—	$\frac{1}{16}$	Plain	C	"	1
1202	Type 1202	500	15	4	—	—	—	—	$\frac{1}{16}$	Slotted	C	"	1
15081	Type 3790	500	1	5	—	—	—	—	$\frac{1}{16}$	Slotted	C	"	1
17958	Type 9342	500	5	5	—	—	—	—	$\frac{1}{8}$	Plain	C	"	1
15272	Type 3981	500	5	5	—	—	—	—	$\frac{1}{8}$	Slotted	C	"	1
15805	Type 4488	500	5	5	—	—	Tags	—	$\frac{1}{8}$	Slotted	C	"	1
628	Type 847	500	5	5	—	—	Tags	—	$\frac{1}{8}$	Slotted	C	"	1
6924	Type 6924	500	10	5	—	—	Tags	—	$\frac{1}{8}$	Tapped 6 B.A.	C	"	1
6939	Type 6939	500	15	5	—	—	Terminals	—	$\frac{1}{8}$	Plain	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom of Qty.	Carton Unit Qty	
					Diam. (inches)	Depth (inches)	Other Details	Diam. (inches)	Length (inches)	Other Details				
1														
	RESISTORS—cont.													
	Variable potentiometers—cont.													
	Wire-wound element—cont.													
10706	Type 3534	500	10	10	3	1 $\frac{1}{8}$	—	—	—	1 $\frac{1}{8}$	Plain 360° rotation	C	each	1
10548	Type 392	500	10	15 to 20	3 $\frac{3}{8}$	2 $\frac{3}{8}$	—	—	—	1 $\frac{1}{8}$	Plain Screwdriver slot	C	"	1
16128	Type 4776	500	10	50	—	—	—	—	—	1	Plain 360° rotation	C	"	1
15933	Type 4614	500	10	100	3 $\frac{1}{2}$	1 $\frac{1}{2}$	—	—	—	1 $\frac{1}{8}$	Plain 360° rotation	C	"	1
16549	Type 5119	500	1	—	—	—	—	—	—	1 $\frac{1}{8}$	—	C	"	1
16498	Type 5068	500	—	—	—	—	—	—	—	1 $\frac{1}{8}$	—	C	"	1
16789	Type 5305	590	0.29	50	—	—	—	—	—	—	—	C	"	1
15662	Type 4358	600	—	40	—	—	—	—	—	—	—	C	"	1
15171	Type 3880	600	—	15 to 20	—	—	—	—	—	—	—	C	"	1
17774	Type 9219	600	2	—	—	—	—	—	—	—	—	C	"	1
8211	Type 8211	600	5	—	—	—	—	—	—	—	—	C	"	—
8212	Type 8212	600	5	—	—	—	—	—	—	—	—	C	"	—
7362	Type 7362	600	10	4	—	—	—	—	—	—	—	C	"	1
16684	Type 5208	624	10	—	—	—	—	—	—	—	—	C	"	1
15080	Type 3289	650	10	5	—	—	—	—	—	—	Plain Quadrant arm	C	"	1
10997	Type 3707	660	10	100	—	—	—	—	—	—	Shield and knob	C	"	1
16820	Type 5335	750	10	100	—	—	—	—	—	—	Shield and knob	C	"	1
16733	Type 5251	1 K	10	1	—	—	—	—	—	—	Slotted, insulated	C	"	—
16511	Type 5081	1 K	10	1	—	—	—	—	—	—	Slotted	C	"	1
16228	Type 4854	1 K	10	1	—	—	—	—	—	—	Slotted	C	"	1
6287	Type 6287	1 K	5	2 $\frac{1}{2}$	—	—	—	—	—	—	Plain	C	"	1
8924	Type 2334	1 K	10	3	—	—	—	—	—	—	Slotted	C	"	1
17757	Type 9202	1 K	10	2	—	—	—	—	—	—	Slotted $\frac{1}{2}$ in. including brush	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Diam. (inches)	Depth (inches)	Other Details	Diam. (inches)	Length (inches)	Other Details			
1	RESISTORS—cont Variable potentiometers—cont. Wire-wound element—cont.												
8420	Type 8420	1 K	10	3	$\frac{1}{16}$	$\frac{3}{16}$	Terminals	$\frac{1}{4}$	1	Plain	C	each	1
7798	Type 7798	1 K	10	3	$\frac{1}{16}$	$\frac{3}{16}$	Terminals	$\frac{1}{4}$	$\frac{1}{2}$	Slotted	C	"	1
209	Type 677	1 K	10	3	$\frac{1}{16}$	$\frac{3}{16}$	Tags	$\frac{1}{4}$	1	Plain	C	"	1
8951	Type 2350	1 K	10	3	$\frac{1}{16}$	$\frac{3}{16}$	Tags	$\frac{1}{4}$	$\frac{7}{16}$	Slotted	C	"	1
9004	Type 2380	1 K	10	3	$\frac{1}{16}$	$\frac{3}{16}$	Tags	$\frac{1}{4}$	$\frac{11}{16}$	Slotted	C	"	1
9005	Type 2381	1 K	10	3	$\frac{1}{16}$	$\frac{3}{16}$	Tags	$\frac{1}{4}$	$\frac{11}{16}$	Slotted	C	"	1
16350	Type 4940	1 K	20	3	$\frac{1}{16}$	$\frac{3}{16}$	—	$\frac{1}{4}$	$\frac{11}{16}$	Slotted	C	"	1
17814	Type 9257	1 K	10	3	—	—	—	$\frac{1}{4}$	$\frac{11}{16}$	—	C	"	1
16072	Type 4728	1 K	10	3 to 4	—	—	—	—	1	Screwdriver slot	C	"	1
1203	Type 1203	1 K	—	4	—	—	—	—	$\frac{1}{16}$	Slotted	C	"	1
7549	Type 7549	1 K	5	4	—	—	—	—	$\frac{1}{16}$	Slotted	C	"	1
8028	Type 8028	1 K	10	4	—	—	—	—	1	Slotted	C	"	1
1221	Type 1221	1 K	20	4	—	—	—	—	1	Slotted	C	"	1
6004	Type 6004	1 K	1	5	$\frac{1}{16}$	$\frac{3}{16}$	Terminals	$\frac{1}{4}$	—	Slotted	C	"	1
7724	Type 7724	1 K	5	5	$\frac{1}{16}$	$\frac{3}{16}$	Terminals	$\frac{1}{4}$	—	—	C	"	1
8362	Type 8362	1 K	5	5	$\frac{1}{16}$	$\frac{3}{16}$	Tags	$\frac{1}{4}$	—	Plain	C	"	1
946	Type 974	1 K	10	5	$\frac{1}{16}$	$\frac{3}{16}$	Tags	$\frac{1}{4}$	—	Plain	C	"	1
1587	Type 1587	1 K	10	5	$\frac{1}{16}$	$\frac{3}{16}$	Terminals	$\frac{1}{4}$	—	Plain	C	"	1
1754	Type 1754	1 K	10	5	$\frac{1}{16}$	$\frac{3}{16}$	Terminals	$\frac{1}{4}$	—	Slotted	C	"	1
6919	Type 6919	1 K	10	5	$\frac{1}{16}$	$\frac{3}{16}$	Terminals	$\frac{1}{4}$	—	Plain	C	"	1
7579	Type 7579	1 K	10	5	$\frac{1}{16}$	$\frac{3}{16}$	Tags	$\frac{1}{4}$	—	Plain	C	"	1
6255	Type 6255	1 K	5	5	$\frac{1}{16}$	$\frac{3}{16}$	Terminals	$\frac{1}{4}$	—	Tapped 5 B.A.	C	"	1
7435	Type 7435	1 K	5	5	—	—	—	—	—	—	C	"	1
15060	Type 3769	1 K	5	5	—	—	—	—	—	With $\frac{1}{2}$ in. flat	C	"	1
17983	Type 9363	1 K	5	5	—	—	—	—	—	Slotted	C	"	1
9235	Type 2562	1 K	10	7 $\frac{1}{2}$	—	—	—	—	—	Plain	C	"	1
16722	Type 5243	1 K	5	20	—	—	—	—	—	Slotted	C	"	1
16263	Type 4884	1 K	—	25	—	—	—	—	—	Plain	C	"	1

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Diam. (inches)	Depth (inches)	Other Details	Diam. (inches)	Length (inches)	Other Details			
1	2	3	4	5	6	7	8	9	10	11	12	13	14
	RESISTORS—cont.												
	Variable potentiometers—cont.												
	Wire-wound element—cont.												
937	Type 970	1 K	—	175	—	—	—	—	—	—	—	each	1
10731	Type 3555	1 K	10	50	$3\frac{1}{4}$	$2\frac{1}{16}$	—	$1\frac{1}{4}$	$1\frac{1}{8}$	—	C	"	1
15484	Type 4193	1 K	10	50	$3\frac{1}{4}$	$2\frac{1}{16}$	—	$1\frac{1}{4}$	$1\frac{1}{8}$	—	C	"	1
7726	Type 7726	1 K	5	5	$1\frac{7}{8}$	$2\frac{3}{16}$	—	$1\frac{1}{4}$	$1\frac{1}{4}$	—	C	"	1
10732	Type 3556	1 K	10	100	$4\frac{1}{2}$	$2\frac{1}{8}$	—	$1\frac{1}{4}$	$1\frac{1}{4}$	—	C	"	1
16320	Type 4936	1.04 K	0-6	50	—	—	—	—	—	—	C	"	1
16939	Type 5448	1.2 K	—	50	—	—	—	—	—	—	C	"	1
16720	Type 5241	1.5 K	—	1	—	—	—	—	—	—	C	"	1
1568	Type 1568	2 K	10	—	—	—	—	—	—	—	C	"	1
16347	Type 4937	2 K	20	1	—	—	—	—	—	—	C	"	1
9552	Type 2803	2 K	10	—	—	—	—	—	—	—	C	"	1
9476	Type 2732	2 K	10	3	$1\frac{1}{8}$	$3\frac{1}{16}$	—	$1\frac{1}{4}$	$1\frac{1}{8}$	—	C	"	1
15802	Type 4485	2 K	10	3	—	—	—	—	—	—	C	"	1
16544	Type 5114	2 K	10	3	—	—	—	—	—	—	C	"	1
7924	Type 7924	2 K	10	3	$1\frac{9}{16}$	$2\frac{1}{16}$	—	$1\frac{1}{4}$	$1\frac{1}{8}$	—	C	"	1
1440	Type 1440	2 K	20	3	$1\frac{1}{16}$	$3\frac{1}{16}$	—	$1\frac{1}{4}$	$1\frac{1}{8}$	—	C	"	1
8843	Type 2272	2 K	20	3	$1\frac{1}{16}$	$3\frac{1}{16}$	—	$1\frac{1}{4}$	$1\frac{1}{8}$	—	C	"	1
17868	Type 9309	2 K	5	3 to 4	—	—	—	—	—	—	C	"	1
16151	Type 4798	2 K	5	4	$1\frac{1}{8}$	$2\frac{1}{16}$	—	$1\frac{1}{4}$	$1\frac{1}{8}$	—	C	"	1
1595	Type 1595	2 K	10	4	$1\frac{1}{8}$	$2\frac{1}{16}$	—	$1\frac{1}{4}$	$1\frac{1}{8}$	—	C	"	1
1760	Type 1760	2 K	5	4	$1\frac{1}{8}$	$2\frac{1}{16}$	—	$1\frac{1}{4}$	$1\frac{1}{8}$	—	C	"	1
6491	Type 6491	2 K	10	5	$1\frac{1}{8}$	$2\frac{1}{16}$	—	$1\frac{1}{4}$	$1\frac{1}{8}$	—	C	"	1
1200	Type 1200	2 K	15	5	$1\frac{1}{8}$	$2\frac{1}{16}$	—	$1\frac{1}{4}$	$1\frac{1}{8}$	—	C	"	1
16038	Type 4706	2 K	20	5	$1\frac{1}{8}$	$2\frac{1}{16}$	—	$1\frac{1}{4}$	$1\frac{1}{8}$	—	C	"	1
6940	Type 6940	2 K	10	10	—	—	—	—	—	—	C	"	1
16085	Type 4741	2 K	10	10	—	—	—	—	—	—	C	"	1
7085	Type 7085	2 K	20	10	$3\frac{1}{4}$	$2\frac{1}{16}$	Terminals	—	$1\frac{3}{8}$	Slotted	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.	
					Diam. (inches)	Depth (inches)	Other Details	Diam. (inches)	Length (inches)	Other Details				
1														
	RESISTORS—cont.													
	Variable potentiometers—cont.													
	Wire-wound element—cont.													
1223	Type 1223	2 K	—	—	—	—	—	—	—	—	—	C	each	1
16556	Type 5126	2 K	—	—	—	—	—	—	—	—	—	C	"	1
10922	Type 3642	2 K	15/61	—	—	—	—	—	—	—	—	C	"	1
1528	Type 1528	2 K	—	50	3 1/4	2 1/8	Terminals	1/4	4 1/8	Plain	—	C	"	1
10793	Type 3578	2.5 K	10	1	—	—	—	—	1 1/8	Slotted	—	C	"	1
16785	Type 5302	2.5 K	5	3 to 4	—	—	—	—	1	—	—	C	"	1
15037	Type 3746	2 K	10	4	1 1/8	—	Terminals	1/4	1 7/8	Plain	—	C	"	1
15367	Type 4076	2 K	10	4	1 1/8	—	Terminals	1/4	1 7/8	Plain	—	C	"	1
15832	Type 4515	2 K	10	5	1 1/2	—	Tags	1/4	1 7/8	Slotted	—	C	"	1
7776	Type 7776	2 K	10	5	1 1/2	2 1/8	Tags	1/4	1 7/8	Plain	—	C	"	1
16223	Type 4850	2.5 K	10	5	—	—	—	—	1 1/8	Plain	—	C	"	1
15019	Type 3728	2.5 K	5	10	—	—	—	—	1 1/8	Plain	—	C	"	1
8129	Type 8129	2.5 K	10	50	—	—	—	—	1 1/8	Slotted	—	C	"	1
10952	Type 3667	3 K	10	2 1/2	—	—	Terminals	1/4	1 1/8	Plain	—	C	"	1
10527	Type 3430	3 K	10	3	1 1/8	—	Terminals	1/4	1 1/8	Plain	—	C	"	1
9477	Type 2733	3 K	10	3	1 1/8	—	Terminals	1/4	1 1/8	Plain	—	C	"	1
6314	Type 6314	3 K	10	3	1 1/8	—	Terminals	1/4	1 1/8	Plain	—	C	"	1
1026	Type 1026	3 K	20	4	1 1/8	—	Terminals	1/4	1 1/8	Slotted	—	C	"	1
1622	Type 1622	3 K	10	20	3 3/8	2 3/8	Terminals	1/4	1 1/8	Slotted	—	C	"	1
692	Type 876	3 K	10	15 to 20	3 3/8	2 3/8	Terminals	1/4	1 1/8	Plain	—	C	"	1
16661	Type 5190	3 K	5	25	—	—	—	—	1 1/8	—	—	C	"	1
16938	Type 5447	4 K	—	50	—	—	—	—	1 1/8	—	—	C	"	1
15485	Type 4194	4 K	5	50	3 1/4	2 1/8	Terminals	1/4	1 1/8	Plain	—	C	"	1
1268	Type 1268	4 K	10	50	3 1/4	2 1/8	Terminals	1/4	1 1/8	Plain	—	C	"	1
15063	Type 3772	4 K	10	50	—	—	—	—	1 1/8	Plain	—	C	"	1
16160	Type 4807	4.7 K	10	15	—	—	—	—	1 1/8	Plain	—	C	"	1
17895	Type 9336	5 K	10	15	—	—	—	—	1 1/8	Plain	—	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Diam. (inches)	Depth (inches)	Other Details	Diam. (inches)	Length (inches)	Other Details			
1	RESISTORS—cont. Variable potentiometers—cont. Wire-wound element—cont.												
17371	Type 5828	5 K	20	1	$\frac{1}{16}$	$\frac{1}{16}$	—	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	each	1
9267	Type 2594	5 K	10	1 to 2	$\frac{1}{16}$	$\frac{1}{16}$	Tags	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1
17758	Type 9203	5 K	10	2	$\frac{7}{16}$	$\frac{1}{16}$	—	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1
10719	Type 3547	5 K	20	2	$\frac{1}{8}$	$\frac{1}{16}$	Tags	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1
6289	Type 6289	5 K	5	2 $\frac{1}{2}$	$\frac{1}{8}$	$\frac{1}{16}$	Terminals	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1
16423	Type 5003	5 K	10	2 $\frac{1}{2}$	—	—	—	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1
16721	Type 5242	5 K	—	2 $\frac{1}{2}$	—	—	—	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1
7796	Type 7796	5 K	—	3	$\frac{1}{16}$	$\frac{1}{16}$	Terminals	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1
7976	Type 7976	5 K	10	3	$\frac{1}{16}$	$\frac{1}{16}$	—	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1
8726	Type 2181	5 K	10	3	$\frac{1}{16}$	$\frac{1}{16}$	—	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1
8925	Type 2335	5 K	10	3	$\frac{1}{16}$	$\frac{1}{16}$	Terminals	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1
8929	Type 2339	5 K	10	3	$\frac{1}{16}$	$\frac{1}{16}$	Terminals	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1
15038	Type 3747	5 K	10	3	$\frac{1}{16}$	$\frac{1}{16}$	Terminals	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1
15397	Type 4106	5 K	20	3	—	—	—	$\frac{1}{16}$	$\frac{5}{16}$	—	C	"	1
15401	Type 4110	5 K	—	3	—	—	—	$\frac{1}{16}$	$\frac{5}{16}$	—	C	"	1
65	Type 565	5 K	10	3	$\frac{1}{16}$	$\frac{1}{16}$	—	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1
9006	Type 2382	5 K	10	3	$\frac{1}{16}$	$\frac{1}{16}$	Tags	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1
15960	Type 4641	5 K	10	3	$\frac{1}{16}$	$\frac{1}{16}$	Tags	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1
16081	Type 4737	5 K	10	3	—	—	—	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1
1807	Type 1807	5 K	20	3 to 4	—	—	—	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1
8423	Type 8423	5 K	20	3	$\frac{1}{16}$	$\frac{1}{16}$	Tags	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1
10538	Type 8438	5 K	20	3	$\frac{1}{16}$	$\frac{1}{16}$	Tags	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1
16152	Type 4799	5 K	5	3	$\frac{1}{16}$	$\frac{1}{16}$	Tags	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1
15803	Type 4486	5 K	5	4	$\frac{1}{16}$	$\frac{1}{16}$	Terminals	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1
16315	Type 4931	5 K	10	4	$\frac{1}{16}$	$\frac{1}{16}$	Terminals	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1
8541	Type 2056	5 K	10	4	$\frac{1}{16}$	$\frac{1}{16}$	Terminals	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1
612	Type 837	5 K	15	4	$\frac{1}{16}$	$\frac{1}{16}$	Terminals	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1
15868	Type 4551	5 K	20	4	$\frac{1}{16}$	$\frac{1}{16}$	Terminals	$\frac{1}{16}$	$\frac{5}{16}$	Slotted	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	Nomenclature	Value in Ohms	Tolerance + or - %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Diam. (inches)	Depth (inches)	Other Details	Diam. (inches)	Length (inches)	Other Details			
1	2	3	4	5	6	7	8	9	10	11	12	13	14
9571	Variable potentiometers—cont. Wire-wound element—cont.	5 K	5	5	1 7/8	3/8	Tags	1/4	1 7/8	1/2 Flat	C	each	1
7342	Type 2822	5 K	5	5	1 7/8	3/8	Tags	1/4	1 1/2	1/2 Flat	C	"	1
557	Type 7342	5 K	10	5	1 3/4	3/8	Terminals	1/4	1 1/2	Plain	C	"	1
15668	Type 819	5 K	10	5	1 3/4	3/8	Terminals	1/4	1 1/2	Plain	C	"	1
15833	Type 4364	5 K	10	5	1 3/4	3/8	Tags	1/4	1 1/2	Plain	C	"	1
15873	Type 4516	5 K	10	5	1 3/4	3/8	Tags	1/4	1 1/2	Slotted	C	"	1
15333	Type 4556	5 K	20	5	1 3/4	3/8	Tags	1/4	1 1/2	Slotted	C	"	1
6256	Type 4042	5 K	20	5	1 3/4	3/8	Tags	1/4	1 1/2	Slotted	C	"	1
1707	Type 6256	5 K	10	5	1 3/4	3/8	Tags	1/4	1 1/2	Plain	C	"	1
6070	Type 1707	5 K	10	5	1 3/4	3/8	Tags	1/4	1 1/2	Plain	C	"	1
15001	Type 6070	5 K	10	5	1 3/4	3/8	Tags	1/4	1 1/2	Slotted	C	"	1
15394	Type 3710	5 K	5	5	1 3/4	3/8	Tags	1/4	1 1/2	Slotted	C	"	1
16118	Type 4103	5 K	5	5	1 3/4	3/8	Tags	1/4	1 1/2	Slotted	C	"	1
16593	Type 4767	5 K	5	5	1 3/4	3/8	Tags	1/4	1 1/2	Slotted	C	"	1
16593	Type 5153	5 K	5	5	1 3/4	3/8	Tags	1/4	1 1/2	Slotted	C	"	1
16595	Type 5153	5 K	5	5	1 3/4	3/8	Tags	1/4	1 1/2	Slotted	C	"	1
16086	Type 5155	5 K	5	5	1 3/4	3/8	Tags	1/4	1 1/2	Slotted	C	"	1
15307	Type 4742	5 K	10	10	1 3/4	3/8	Terminals	1/4	1 1/2	Plain	C	"	2
7743	Type 4016	5 K	10	15	1 3/4	3/8	Terminals	1/4	1 1/2	Plain	C	"	1
1064	Type 7743	5 K	10	15 to 20	1 3/4	3/8	Terminals	1/4	1 1/2	Plain	C	"	1
16824	Type 1064	5 K	10	25	1 3/4	3/8	Terminals	1/4	1 1/2	Plain	C	"	1
16034	Type 5337	5 K	10	50	1 3/4	3/8	Terminals	1/4	1 1/2	Slotted	C	"	1
15647	Type 4702	5 K	10	50	1 3/4	3/8	Terminals	1/4	1 1/2	Slotted	C	"	1
16499	Type 4343	5 K	10	50	1 3/4	3/8	Terminals	1/4	1 1/2	Slotted	C	"	1
17261	Type 5069	5 K	10	2	1 3/4	3/8	Terminals	1/4	1 1/2	Slotted	C	"	1
8215	Type 5718	5 K	10	2	1 3/4	3/8	Terminals	1/4	1 1/2	Slotted	C	"	1
6301	Type 8215	5 K	10	50	1 3/4	3/8	Terminals	1/4	1 1/2	Slotted	C	"	1
16859	Type 6301	7 K	10	3	1 3/4	3/8	Terminals	1/4	1 1/2	Slotted	C	"	1
16856	Type 5369	9 K	5	3	1 3/4	3/8	Terminals	1/4	1 1/2	Slotted	C	"	1
	Type 5367	10 K	5	3	1 3/4	3/8	Terminals	1/4	1 1/2	Slotted	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Diam. (inches)	Depth (inches)	Other Details	Diam. (inches)	Length (inches)	Other Details			
1	2	3	4	5	6	7	8	9	10	11	12	13	14
	RESISTORS—cont.												
	Variable potentiometers—cont.												
	Wire-wound element—cont.												
15982	Type 4659	10 K	5	2½	—	—	—	½	¾	Slotted out knob	C	each	1
17870	Type 9311	10 K	5	3-4 DC	—	—	—	½	¾	Slotted out knob	C	"	1
6286	Type 6286	10 K	5	2½	1½	¾	Terminals	½	1 1/16	Slotted Plain	C	"	1
1762	Type 1762	10 K	5	5	—	—	—	½	1 1/16	Slotted Plain	C	"	1
7888	Type 7888	10 K	10	3	1 1/16	¾	Terminals	½	1 1/16	Slotted Plain	C	"	1
8086	Type 8086	10 K	10	3	1 1/16	¾	Terminals	½	1 1/16	Slotted Plain	C	"	1
8926	Type 2336	10 K	10	3	1 1/16	¾	Terminals	½	1 1/16	Slotted Plain	C	"	1
10935	Type 3654	10 K	10	3	1 1/16	¾	Terminals	½	1 1/16	Slotted Plain	C	"	1
15213	Type 3922	10 K	10	3	1 1/16	¾	—	½	1 1/16	Slotted Plain	C	"	1
16140	Type 4787	10 K	20	3	—	—	—	½	1 1/16	—	C	"	1
8229	Type 8229	10 K	10	3	—	—	—	½	1 1/16	Slotted	C	"	1
16543	Type 5113	10 K	10	3	—	—	—	½	1 1/16	Slotted	C	"	1
16082	Type 4738	10 K	10	3	—	—	—	½	1 1/16	Slotted	C	"	1
17869	Type 9310	10 K	5	3 to 4	—	—	—	½	1 1/16	Slotted	C	"	1
16149	Type 4796	10 K	5	4	—	—	—	½	1 1/16	Plain	C	"	1
15006	Type 3715	10 K	10	4	1 1/16	¾	Terminals	½	1 1/16	Plain 360° rotation	C	"	1
15007	Type 3716	10 K	10	4	1 1/16	¾	Terminals	½	¾	Plain 360° rotation	C	"	1
10693	Type 3526	10 K	10	4	1 1/16	¾	Terminals	½	1 1/16	Plain 360° rotation	C	"	1
8340	Type 8340	10 K	10	4	—	—	—	½	1	Plain	C	"	1
15452	Type 4161	10 K	5	4	—	—	—	½	1	Slotted	C	"	1
7548	Type 7548	10 K	5	4	—	—	—	½	1	Slotted	C	"	1
15062	Type 3771	10 K	5	5	—	—	—	½	1 1/16	Slotted	C	"	1
7725	Type 7725	10 K	5	5	1 1/16	¾	Tags	½	1 1/16	Slotted	C	"	1
1933	Type 1933	10 K	5	5	1 1/16	¾	Tags	½	1 1/16	Plain	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit
					Diam. (inches)	Depth (inches)	Other Details	Diam. (inches)	Length (inches)	Other Details			
1	2	3	4	5	6	7	8	9	10	11	12	13	14
RESISTORS—cont. Variable potentiometers—cont. Wire-wound element—cont.													
7420	Type 7420	10 K	5	5	1 7/8	3/8	Tags	1/4	7/8	Plain	C	each	1
16116	Type 4765	10 K	5	5	1 7/8	3/8	Tags	1/4	7/8	Slotted	C	"	1
987	Type 987	10 K	10	5	1 13/16	3/8	Terminals	1/4	1 1/8	Plain	C	"	1
1025	Type 1025	10 K	10	5	1 13/16	3/8	Terminals	1/4	1 1/8	Plain	C	"	1
1535	Type 1535	10 K	10	5	1 13/16	3/8	Terminals	1/4	1 1/8	Tapped 5 B.A.	C	"	1
8815	Type 2252	10 K	10	5	1 13/16	3/8	Terminals	1/4	1 1/8	Tapped 6 B.A.	C	"	1
6257	Type 6257	10 K	10	5	1 7/8	2 1/16	Tags	1/4	1 1/8	Slotted	C	"	1
16591	Type 5151	10 K	5	5	—	—	—	—	1 1/8	Slotted	C	"	1
16592	Type 5152	10 K	5	5	—	—	—	—	1 1/8	Slotted	C	"	1
17408	Type 5864	10 K	5	5	—	—	—	—	1 1/8	Slotted	C	"	1
16555	Type 5125	10 K	5	5	—	—	—	—	1 1/8	Slotted	C	"	1
15395	Type 4104	10 K	5	5	—	—	—	—	1 1/8	Slotted	C	"	1
1547	Type 1547	10 K	5	5	—	—	—	—	1 1/8	Slotted	C	"	1
18037	Type 9459	10 K	10	2	—	1 1/16	Terminals	0-187	0-406	Plain Including threaded portion, plain	C	"	—
6180	Type 6180	10 K	10	15 to 20	3 3/8	2 3/8	Terminals	1/4	1 3/8	Plain	C	"	1
16500	Type 5070	10 K	10	—	—	—	—	1/4	1 3/8	Plain	C	"	1
17824	Type 9265	14 K	10	25	—	—	—	1/4	1 3/8	Plain	C	"	1
9412	Type 2676	15 K	10	4	1 13/16	3/8	Terminals	1/4	1 1/8	Slotted	C	"	1
15490	Type 4199	15 K	10	5	—	—	—	1/4	1 1/8	Slotted	C	"	1
15799	Type 4482	15 K	5	5	—	—	—	1/4	1 1/8	Slotted	C	"	1
1457	Type 1457	15 K	10	5	—	—	—	1/4	1 1/8	Slotted	C	"	1
16862	Type 5372	15 K	10	6	—	—	—	1/4	1 1/8	Slotted	C	"	1
16091	Type 4747	15 K	10	10	—	—	—	1/4	1 1/8	Slotted	C	"	1
1265	Type 1265	15 K	5	20	2 3/4	—	Terminals	1/4	1 1/8	Slotted	C	"	1
7616	Type 7616	15 K	—	—	—	—	—	1/4	1 1/8	Slotted	C	"	1
15235	Type 3944	20 K	20	—	—	—	—	1/4	1 1/8	Slotted	C	"	1
16422	Type 5002	20 K	10	1 1/2	—	—	—	1/4	1 1/8	Slotted	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Diam. (inches)	Depth (inches)	Other Details	Diam. (inches)	Length (inches)	Other Details			
1	2	3	4	5	6	7	8	9	10	11	12	13	14
6285	RESISTOR—cont. Variable potentiometers—cont. Wire-wound element—cont.	20 K	5	2½	1 3/8	3/8	Terminals	1/4	1 1/8	Slotted	C	each	1
8645	Type 6285	20 K	10	3	1 3/8	3/8	Terminals	1/4	1 1/8	Slotted	C	"	1
8727	Type 2143	20 K	10	3	1 1/8	3/8	Terminals	1/4	1 1/8	Plain	C	"	1
9225	Type 2182	20 K	10	3	1 1/8	3/8	Terminals	1/4	1 1/8	Plain	C	"	1
15116	Type 2552	20 K	10	3	1 1/8	3/8	Terminals	1/4	1 1/8	Plain	C	"	1
1438	Type 3825	20 K	10	3	1 1/8	3/8	Terminals	1/4	1 1/8	Flat	C	"	1
1439	Type 1439	20 K	10	3	1 1/8	3/8	Tags	1/4	1 1/8	Slotted	C	"	1
1602	Type 1602	20 K	10	3	1 1/8	3/8	Tags	1/4	1 1/8	Plain	C	"	1
1808	Type 1808	20 K	10	3	1 1/8	3/8	Tags	1/4	1 1/8	Slotted	C	"	1
7780	Type 1602	20 K	10	3	1 1/8	3/8	Tags	1/4	1 1/8	Plain	C	"	1
16150	Type 1808	20 K	10	3	1 1/8	3/8	Tags	1/4	1 1/8	Plain	C	"	1
1224	Type 7780	20 K	5	4	1 1/8	3/8	Terminals	1/4	1 1/8	Slotted	C	"	1
9411	Type 4797	20 K	10	4	1 1/8	3/8	Terminals	1/4	1 1/8	Slotted	C	"	1
7359	Type 1224	20 K	10	4	1 1/8	3/8	Terminals	1/4	1 1/8	Slotted	C	"	1
16141	Type 2675	20 K	10	4	1 1/8	3/8	Terminals	1/4	1 1/8	Plain	C	"	1
6468	Type 7359	20 K	10	4	1 1/8	3/8	Terminals	1/4	1 1/8	Plain	C	"	1
6562	Type 4788	20 K	10	4	1 1/8	3/8	Terminals	1/4	1 1/8	Plain	C	"	1
8644	Type 6468	20 K	10	5	1 1/8	3/8	Tags	1/4	1 1/8	Plain	C	"	1
15130	Type 6562	20 K	10	5	1 1/8	3/8	Tags	1/4	1 1/8	Plain	C	"	1
16133	Type 2142	20 K	10	5	1 1/8	3/8	Tags	1/4	1 1/8	Slotted	C	"	1
16296	Type 3839	20 K	10	5	1 1/8	3/8	Tags	1/4	1 1/8	Slotted	C	"	1
16444	Type 4781	20 K	5	5	1 1/8	3/8	Tags	1/4	1 1/8	Slotted	C	"	1
16596	Type 4916	20 K	20	5	1 1/8	3/8	Tags	1/4	1 1/8	Slotted	C	"	1
17395	Type 5022	20 K	5	5	1 1/8	3/8	Tags	1/4	1 1/8	Plain	C	"	1
17405	Type 5156	20 K	5	5	1 1/8	3/8	Tags	1/4	1 1/8	Plain	C	"	1
1444	Type 5851	20 K	5	5	1 1/8	3/8	Tags	1/4	1 1/8	Slotted	C	"	1
6284	Type 5861	20 K	10	5	1 1/8	3/8	Tags	1/4	1 1/8	Plain	C	"	1
999	Type 1444	20 K	5	12	1 1/8	3/8	Terminals	1/4	1 1/8	Plain	C	"	1
	Type 6284	20 K	20	12	1 1/8	3/8	Terminals	1/4	1 1/8	Plain	C	"	1
	Type 999	20 K	20	12	1 1/8	3/8	Terminals	1/4	1 1/8	Plain	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Diam. (inches)	Depth (inches)	Other Details	Diam. (inches)	Length (inches)	Other Details			
1													
	RESISTORS—cont.												
	Variable potentiometers—cont.												
	Wire-wound element—cont.												
15172	Type 3881	20 K	10	20	—	—	—	—	—	—	C	each	1
16941	Type 5450	20 K	20	1	—	—	—	—	2 1/4	—	C	"	1
17262	Type 5719	25 K	—	2	—	—	—	—	1	—	C	"	1
17263	Type 5720	25 K	—	2	—	—	—	—	1 1/8	—	C	"	1
17826	Type 9267	25 K	5	2 1/2	—	—	—	—	1 1/8	—	C	"	1
17871	Type 9312	25 K	5	3 to 4	—	—	—	—	1 1/8	—	C	"	3
8574	Type 2082	25 K	10	3	—	—	—	—	1 1/8	—	C	"	1
10930	Type 3649	25 K	10	3	—	—	—	—	1 1/8	—	C	"	1
307	Type 731	25 K	10	3	—	—	—	—	1 1/8	—	C	"	1
15400	Type 4109	25 K	10	3	—	—	—	—	1 1/8	—	C	"	1
15457	Type 4166	25 K	20	3	—	—	—	—	1 1/8	—	C	"	1
16447	Type 5025	25 K	—	3	—	—	—	—	1 1/8	—	C	"	1
7797	Type 7797	25 K	10	3	—	—	—	—	1 1/8	—	C	"	1
7887	Type 7887	25 K	10	3	—	—	—	—	1 1/8	—	C	"	1
8147	Type 8147	25 K	10	3	—	—	—	—	1 1/8	—	C	"	1
8159	Type 8159	25 K	10	3	—	—	—	—	1 1/8	—	C	"	1
8573	Type 2081	25 K	10	3	—	—	—	—	1 1/8	—	C	"	1
8927	Type 2337	25 K	10	3	—	—	—	—	1 1/8	—	C	"	1
10536	Type 3437	25 K	10	3	—	—	—	—	1 1/8	—	C	"	1
15039	Type 3748	25 K	10	3	—	—	—	—	1 1/8	—	C	"	1
8209	Type 8209	25 K	10	4	—	—	—	—	1 1/8	—	C	"	1
16512	Type 5082	25 K	10	4	—	—	—	—	1 1/8	—	C	"	1
16647	Type 5186	25 K	—	4	—	—	—	—	1 1/8	—	C	"	1
15022	Type 3731	25 K	1	4	—	—	—	—	1 1/8	—	C	"	1
7542	Type 7542	25 K	5	4	—	—	—	—	1 1/8	—	C	"	1
8032	Type 8032	25 K	10	4	—	—	—	—	1 1/8	—	C	"	1
8083	Type 8083	25 K	10	4	—	—	—	—	1 1/8	—	C	"	1
1761	Type 1761	25 K	10	4	—	—	—	—	1 1/8	—	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.	
					Diam. (inches)	Depth (inches)	Other Details	Diam. (inches)	Length (inches)	Other Details				
1														
	RESISTORS—cont.													
	Variable potentiometers—cont.													
	Wire-wound element—cont.													
10695	Type 3527	25 K	10	4	1 1/8	1 3/8	Terminals	1/4	1 1/8	Plain 360° rotation	C	each	1	
15008	Type 3717	25 K	10	4	1 1/8	1 3/8	Terminals	1/4	1 1/8	Plain rotation	C	"	1	
16071	Type 4727	25 K	5	5	1 1/8	1 3/8	Tags	1/4	1 1/8	Plain	C	"	1	
16474	Type 5046	25 K	5	5	1 1/8	1 3/8	Tags	1/4	1 1/8	6 B.A. tapped	C	"	1	
7655	Type 7655	25 K	5	5	1 1/8	1 3/8	Tags	1/4	1 1/8	Plain	C	"	1	
16590	Type 5150	25 K	5	5	1 1/8	1 3/8	Tags	1/4	1 1/8	Slotted	C	"	1	
16115	Type 4764	25 K	5	5	1 1/8	1 3/8	Tags	1/4	1 1/8	Plain	C	"	1	
16589	Type 5149	25 K	5	5	1 1/8	1 3/8	Tags	1/4	1 1/8	Plain	C	"	1	
6469	Type 6469	25 K	10	5	2 1/8	2 1/8	Tags	1/4	2 1/8	Slotted	C	"	1	
7846	Type 7846	25 K	10	5	2 1/8	2 1/8	Tags	1/4	2 1/8	Plain	C	"	1	
8128	Type 8128	25 K	10	5	2 1/8	2 1/8	Tags	1/4	2 1/8	Plain	C	"	1	
8572	Type 2080	25 K	10	5	2 1/8	2 1/8	Tags	1/4	2 1/8	Plain	C	"	1	
1525	Type 1525	25 K	10	5	2 1/8	2 1/8	Terminals	1/4	2 1/8	Tapped 5 B.A.	C	"	1	
538	Type 804	25 K	10	5	2 1/8	2 1/8	Terminals	1/4	2 1/8	Plain	C	"	1	
6561	Type 6561	25 K	10	5	2 1/8	2 1/8	Terminals	1/4	2 1/8	Slotted	C	"	2	
16513	Type 5083	25 K	10	5	2 1/8	2 1/8	Terminals	1/4	2 1/8	Slotted	C	"	1	
16551	Type 5121	25 K	10	5	2 1/8	2 1/8	Terminals	1/4	2 1/8	Slotted	C	"	1	
16552	Type 5122	25 K	5	5	2 1/8	2 1/8	Terminals	1/4	2 1/8	Plain	C	"	1	
16588	Type 5148	25 K	10	5	2 1/8	2 1/8	Terminals	1/4	2 1/8	Plain	C	"	1	
17780	Type 9225	25 K	10	5	2 1/8	2 1/8	Terminals	1/4	2 1/8	Plain	C	"	1	
16568	Type 5136	25 K	10	5	2 1/8	2 1/8	Terminals	1/4	2 1/8	Plain	C	"	1	
8204	Type 8204	25 K	—	100	—	—	Terminals	—	—	Plain	C	"	1	
1196	Type 1196	25 K	15	5	—	—	Terminals	—	—	Plain	C	"	1	
8359	Type 8359	25 K	10	10	1 1/8	1 1/8	Terminals	1/4	1 1/8	Slotted	C	"	1	
15254	Type 3963	30 K	20	3	2 5/8	2 5/8	Terminals	1/4	2 5/8	Slotted	C	"	1	
16950	Type 5459	30 K	10	3	—	—	Terminals	—	—	Slotted	C	"	1	
15935	Type 4616	30 K	10	3	—	—	Terminals	—	—	Slotted	C	"	1	

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Diam. (inches)	Depth (inches)	Other Details	Diam. (inches)	Length (inches)	Other Details			
1	RESISTORS—cont. Variable potentiometers—cont. Wire-wound element—cont.												
15804	Type 4487	30 K	5	4	$1\frac{13}{16}$	$1\frac{33}{16}$	Terminals	$1\frac{1}{4}$	$1\frac{13}{16}$	Slotted	C	each	1
7416	Type 7416	30 K	10	4	$1\frac{13}{16}$	$1\frac{33}{16}$	Terminals	$1\frac{1}{4}$	$1\frac{13}{16}$	Plain	C	"	1
7727	Type 7727	30 K	5	5	$1\frac{13}{16}$	$1\frac{33}{16}$	Tags	$1\frac{1}{4}$	$1\frac{13}{16}$	Plain	C	"	1
15937	Type 4618	30 K	5	5	$1\frac{13}{16}$	$1\frac{33}{16}$	Tags	$1\frac{1}{4}$	$1\frac{13}{16}$	Plain	C	"	1
16754	Type 5271	30 K	10	5	$1\frac{13}{16}$	$1\frac{33}{16}$	—	$1\frac{1}{4}$	$1\frac{13}{16}$	Plain	C	"	1
15787	Type 4471	30 K	10	10	$1\frac{13}{16}$	$1\frac{33}{16}$	Terminals	$1\frac{1}{4}$	$1\frac{13}{16}$	Slotted	C	"	1
16142	Type 4789	30 K	5	15	$1\frac{13}{16}$	$1\frac{33}{16}$	Terminals	$1\frac{1}{4}$	$1\frac{13}{16}$	—	C	"	1
45	Type 557	40 K	5	5	$1\frac{13}{16}$	$1\frac{33}{16}$	—	$1\frac{1}{4}$	$1\frac{13}{16}$	Plain	C	"	1
1272	Type 1272	40 K	5	5	$1\frac{13}{16}$	$1\frac{33}{16}$	Tags	$1\frac{1}{4}$	$1\frac{13}{16}$	Plain = $\frac{3}{8}$ bush length	C	"	1
64	Type 564	50 K	—	3	2	$\frac{3}{8}$	Tags	$1\frac{1}{4}$	$1\frac{13}{16}$	—	C	"	1
16098	Type 4749	50 K	5	20 to 30	—	—	—	$1\frac{1}{4}$	$1\frac{13}{16}$	—	C	"	1
15670	Type 4366	50 K	—	3	—	—	—	$1\frac{1}{4}$	$1\frac{13}{16}$	—	C	"	1
16389	Type 4971	50 K	10	3	—	—	—	$1\frac{1}{4}$	$1\frac{13}{16}$	Slotted	C	"	1
16523	Type 5093	50 K	10	3	—	—	—	$1\frac{1}{4}$	$1\frac{13}{16}$	Slotted	C	"	1
16546	Type 5116	50 K	20	3	—	—	—	$1\frac{1}{4}$	$1\frac{13}{16}$	Plain	C	"	1
17396	Type 5852	50 K	—	3	—	—	—	$1\frac{1}{4}$	$1\frac{13}{16}$	—	C	"	1
8015	Type 107	50 K	—	3	$1\frac{13}{16}$	$1\frac{33}{16}$	Tags	$1\frac{1}{4}$	$1\frac{13}{16}$	Plain	C	"	1
6313	Type 6313	50 K	—	3	$1\frac{13}{16}$	$1\frac{33}{16}$	Tags	$1\frac{1}{4}$	$1\frac{13}{16}$	Plain	C	"	1
8417	Type 8417	50 K	—	3	$1\frac{13}{16}$	$1\frac{33}{16}$	Tags	$1\frac{1}{4}$	$1\frac{13}{16}$	Slotted	C	"	1
9148	Type 2498	50 K	—	3	$1\frac{13}{16}$	$1\frac{33}{16}$	Tags	$1\frac{1}{4}$	$1\frac{13}{16}$	Slotted	C	"	1
8087	Type 8087	50 K	—	3	$1\frac{13}{16}$	$1\frac{33}{16}$	Terminals	$1\frac{1}{4}$	$1\frac{13}{16}$	Slotted	C	"	1
9222	Type 2550	50 K	10	3	$1\frac{13}{16}$	$1\frac{33}{16}$	Terminals	$1\frac{1}{4}$	$1\frac{13}{16}$	Plain	C	"	1
15660	Type 4356	50 K	10	3	$1\frac{13}{16}$	$1\frac{33}{16}$	Terminals	$1\frac{1}{4}$	$1\frac{13}{16}$	Plain	C	"	1
15764	Type 4450	50 K	10	3	$1\frac{13}{16}$	$1\frac{33}{16}$	Terminals	$1\frac{1}{4}$	$1\frac{13}{16}$	Slotted	C	"	1
1753	Type 1753	50 K	15	3	$1\frac{13}{16}$	$1\frac{33}{16}$	—	$1\frac{1}{4}$	$1\frac{13}{16}$	Slotted	C	"	1
15865	Type 4548	50 K	20	3	$1\frac{13}{16}$	$1\frac{33}{16}$	Terminals	$1\frac{1}{4}$	$1\frac{13}{16}$	Plain	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom of Qty.	Carton Unit Qty
					Diam. (inches)	Depth (inches)	Other Details	Diam. (inches)	Length (inches)	Other Details			
1	2	3	4	5	6	7	8	9	10	11	12	13	14
	RESISTORS—cont. Variable potentiometers—cont. Wire-wound element—cont.												
8101	Type 8101	50 K	5	4	$1\frac{1}{8}$	$1\frac{1}{8}$	Terminals	$1\frac{1}{8}$	1	Slotted	C	each	1
7546	Type 7456	50 K	5	4	$1\frac{1}{8}$	$1\frac{1}{8}$	Terminals	$1\frac{1}{8}$	2	Slotted	C	"	1
15451	Type 4160	50 K	5	4	$1\frac{1}{8}$	$1\frac{1}{8}$	Terminals	$1\frac{1}{8}$	1	Slotted	C	"	1
16313	Type 4929	50 K	5	4	$1\frac{1}{8}$	$1\frac{1}{8}$	Terminals	$1\frac{1}{8}$	$\frac{1}{2}$	Plain	C	"	1
16174	Type 4819	50 K	5	4	$1\frac{1}{8}$	$1\frac{1}{8}$	Terminals	$1\frac{1}{8}$	$\frac{1}{2}$	Slotted	C	"	1
9410	Type 2674	50 K	10	4	$1\frac{1}{8}$	$1\frac{1}{8}$	Terminals	$1\frac{1}{8}$	$\frac{1}{2}$	Slotted	C	"	1
1222	Type 1222	50 K	20	4	$1\frac{1}{8}$	$1\frac{1}{8}$	Terminals	$1\frac{1}{8}$	1	Slotted	C	"	1
16039	Type 4707	50 K	5	5	$1\frac{1}{8}$	$1\frac{1}{8}$	Tags	$1\frac{1}{8}$	$1\frac{1}{8}$	Plain	C	"	1
10691	Type 3524	50 K	5	5	$1\frac{1}{8}$	$1\frac{1}{8}$	Tags	$1\frac{1}{8}$	$1\frac{1}{8}$	Plain	C	"	1
7668	Type 7668	50 K	5	5	$1\frac{1}{8}$	$1\frac{1}{8}$	Tags	$1\frac{1}{8}$	$1\frac{1}{8}$	Slotted	C	"	1
7728	Type 7728	50 K	5	5	$1\frac{1}{8}$	$1\frac{1}{8}$	Tags	$1\frac{1}{8}$	$1\frac{1}{8}$	Plain	C	"	1
9570	Type 2821	50 K	5	5	$1\frac{1}{8}$	$1\frac{1}{8}$	Tags	$1\frac{1}{8}$	$1\frac{1}{8}$	$\frac{1}{2}$ Flat	C	"	1
15283	Type 3992	50 K	5	5	$1\frac{1}{8}$	$1\frac{1}{8}$	Tags	$1\frac{1}{8}$	1	Plain	C	"	1
15313	Type 4022	50 K	5	5	$1\frac{1}{8}$	$1\frac{1}{8}$	Tags	$1\frac{1}{8}$	$1\frac{1}{8}$	Plain	C	"	1
16119	Type 4768	50 K	5	5	$1\frac{1}{8}$	$1\frac{1}{8}$	Tags	$1\frac{1}{8}$	$1\frac{1}{8}$	Slotted	C	"	1
16566	Type 5134	50 K	5	5	$1\frac{1}{8}$	$1\frac{1}{8}$	—	$1\frac{1}{8}$	$1\frac{1}{8}$	Slotted	C	"	1
16597	Type 5157	50 K	5	5	$1\frac{1}{8}$	$1\frac{1}{8}$	—	$1\frac{1}{8}$	$1\frac{1}{8}$	Slotted	C	"	1
16594	Type 5154	50 K	5	5	$1\frac{1}{8}$	$1\frac{1}{8}$	—	$1\frac{1}{8}$	$1\frac{1}{8}$	Slotted	C	"	1
17409	Type 5865	50 K	5	5	$1\frac{1}{8}$	$1\frac{1}{8}$	—	$1\frac{1}{8}$	$1\frac{1}{8}$	—	C	"	1
17803	Type 9248	50 K	5	5	$1\frac{1}{8}$	$1\frac{1}{8}$	—	$1\frac{1}{8}$	$1\frac{1}{8}$	—	C	"	1
15106	Type 3815	50 K	10	5	$1\frac{1}{8}$	$1\frac{1}{8}$	—	$1\frac{1}{8}$	$1\frac{1}{8}$	Slotted	C	"	1
1088	Type 1088	50 K	10	5	$1\frac{1}{8}$	$1\frac{1}{8}$	Terminals	$1\frac{1}{8}$	$1\frac{1}{8}$	—	C	"	1
1588	Type 1588	50 K	10	5	$1\frac{1}{8}$	$1\frac{1}{8}$	Terminals	$1\frac{1}{8}$	$1\frac{1}{8}$	Slotted	C	"	1
8137	Type 8137	50 K	10	5	$1\frac{1}{8}$	$1\frac{1}{8}$	Tags	$1\frac{1}{8}$	$1\frac{1}{8}$	Plain	C	"	1
9450	Type 2706	50 K	10	5	$1\frac{1}{8}$	$1\frac{1}{8}$	Tags	$1\frac{1}{8}$	$1\frac{1}{8}$	Plain	C	"	1
15669	Type 4365	50 K	10	5	$1\frac{1}{8}$	$1\frac{1}{8}$	Tags	$1\frac{1}{8}$	$1\frac{1}{8}$	Plain	C	"	1
1934	Type 1934	50 K	10	5	$1\frac{1}{8}$	$1\frac{1}{8}$	Tags	$1\frac{1}{8}$	$1\frac{1}{8}$	—	C	"	1
16132	Type 4780	50 K	5	15	$1\frac{1}{8}$	$1\frac{1}{8}$	Terminals	$1\frac{1}{8}$	$1\frac{1}{8}$	Plain	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	Nomenclature	Value in Ohms	Tolerance + or - %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Diam. (inches)	Depth (inches)	Other Details	Diam. (inches)	Length (inches)	Other Details			
1	RESISTORS—cont. Variable potentiometers—cont. Wire-wound element—cont.												
17812	Type 9255	50 K	5	15	—	—	—	1/4	0.937	—	C	each	1
17802	Type 9247	50 K	5	15	—	—	—	1/4	1	Plain	C	"	1
15312	Type 4021	50 K	5	15	—	—	—	1/4	1	—	C	"	1
15727	Type 4421	50 K	5	20	2 3/8	1 1/8	—	1/4	1 1/4	1/2 Flat	C	"	1
7654	Type 7654	50 K	5	20	1 3/4	1 1/8	—	1/4	1 1/2	Plain	C	"	1
1137	Type 1137	50 K	10	20	3 1/8	2 3/8	—	1/4	1 1/2	—	C	"	1
8205	Type 8205	50 K	—	—	—	—	—	1/4	1/2	Screwdriver slot	C	"	1
15306	Type 4015	50 K	—	—	—	—	—	1/4	1/2	—	C	"	1
16667	Type 5192	50 K	—	—	—	—	—	1/4	1/2	—	C	"	1
16611	Type 5171	50 K	—	—	—	—	—	1/4	1/2	—	C	"	1
6351	Type 6351	100 K	20	1	—	—	—	1/4	1 1/8	Plain	C	"	1
16942	Type 5451	100 K	20	1	—	—	—	1/4	1 1/8	—	C	"	1
16446	Type 5024	100 K	10	4	—	—	—	1/4	2 1/8	Plain	C	"	1
15393	Type 4102	100 K	5	5	—	—	—	1/4	1 1/8	—	C	"	1
17864	Type 9305	100 K	5	5	—	—	—	1/4	1 1/8	—	C	"	1
16567	Type 5135	100 K	5	5	—	—	—	1/4	1 1/8	Slotted	C	"	1
16476	Type 5047	100 K	5	5	—	—	—	1/4	1 1/8	Slotted	C	"	1
16951	Type 5460	100 K	5	5	—	—	—	1/4	1 1/8	Plain	C	"	1
17410	Type 5866	100 K	5	5	—	—	—	1/4	1 1/8	—	C	"	1
17892	Type 9333	100 K	5	5	—	—	—	1/4	1 1/8	—	C	"	1
16947	Type 5456	100 K	5	5	—	—	—	1/4	1 1/8	Plain	C	"	1
16305	Type 4923	100 K	5	5	—	—	—	1/4	1 1/8	Slotted	C	"	1
17729	Type 7729	100 K	5	5	—	—	—	1/4	1 1/8	Plain	C	"	1
15232	Type 3941	100 K	5	5	—	—	—	1/4	1 1/8	Slotted	C	"	1
9239	Type 2566	100 K	5	5	—	—	—	1/4	1 1/8	Tapped 6 B.A.	C	"	1
16415	Type 4995	100 K	10	5	—	—	—	1/4	1 1/8	Slotted	C	"	1
16416	Type 4996	100 K	5	5	—	—	—	1/4	1 1/8	Slotted	C	"	1
17801	Type 9246	100 K	5	15	—	—	—	1/4	1 1/8	Plain	C	"	1

B (P16315)

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	DIMENSIONS AND DETAILS OF BODY			DIMENSIONS AND DETAILS OF SPINDLE			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Diam. (inches)	Depth (inches)	Other Details	Diam. (inches)	Length (inches)	Other Details			
1													
	RESISTORS—cont.												
	Variable potentiometers—cont.												
	Wire-wound element—cont.												
1647	Type 1647	100 K	10	15 to 20	3 $\frac{3}{8}$	2 $\frac{1}{2}$	Terminals	$\frac{1}{4}$	1 $\frac{1}{8}$	Plain	C	each	1
525	Type 796	100 K	15	—	—	—	—	—	1 $\frac{1}{8}$	—	C	"	1
8136	Type 8136	100 K	—	—	—	—	—	—	—	—	C	"	1
1556	Type 1556	200 K	—	1	—	—	—	—	—	—	C	"	5
1266	Type 1266	200 K	10	5	1 $\frac{1}{2}$	$\frac{3}{4}$	Tags	—	—	—	C	"	1
15332	Type 4041	250 K	20	5	—	—	—	$\frac{1}{4}$	2 $\frac{3}{16}$	Plain	C	"	1
8130	Type 8130	250 K	5	20	—	—	—	—	—	Slotted	C	"	1
8361	Type 8361	250 K	5	20	2 $\frac{1}{4}$	1 $\frac{1}{16}$	Terminals	$\frac{1}{4}$	$\frac{3}{16}$	Slotted	C	"	1
1577	Type 1577	500 K	—	1	—	—	—	—	—	—	C	"	1
8000	Type 8000	500 K	5	5	1 $\frac{1}{2}$	$\frac{3}{4}$	Tags	—	2 $\frac{3}{16}$	—	C	"	1
16148	Type 4795	500 K	5	15	2 $\frac{1}{4}$	1 $\frac{1}{16}$	Terminals	$\frac{1}{4}$	1 $\frac{1}{16}$	—	C	"	1
922	Type 960	500 K	5	20	2 $\frac{1}{4}$	1 $\frac{1}{16}$	Terminals	$\frac{1}{4}$	1	Slotted	C	"	1
7193	Type 7193	1 M	—	1	—	—	—	—	—	—	C	"	1
15212	Type 3921	1 M	10	3	—	—	—	—	1 $\frac{1}{8}$	Plain	C	"	1

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance + or - %	Wattage	OVERALL DIMENSIONS			Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length (inches)	Diameter (inches)	Bore (inches)			
1										
	RESISTORS—cont. Wire-wound, open, on vitreous enamelled steel hex. tube, 2 hole fixing:—									
1334	Type 1334 ...	5.3	—	8 amps.	14	2	—	C	each	1
1448	Type 1448 ...	5.3	—	8 amps.	—	—	—	C	"	1
1449	Type 1449 ...	7.5	—	4 amps.	—	—	—	C	"	1
1616	Type 1616 ...	17.5	—	8 amps.	18	2 $\frac{1}{2}$	—	C	"	1
1333	Type 1333 ...	17.5	—	8 amps.	18	2 $\frac{1}{2}$	—	C	"	1
1269	Type 1269 ...	31	—	2.8 amps.	—	—	—	C	"	1
6293	Type 6293 ...	35	—	4 amps.	18	2 $\frac{1}{2}$	—	C	"	1
6292	Type 6292 ...	35	—	4 amps.	18	2 $\frac{1}{2}$	—	C	"	1
1322	Type 1322 ...	60	—	1.5 amps.	6	1 $\frac{1}{2}$	—	C	"	1
1110	Type 1110 ...	1,970	—	4 amps.	12	1 $\frac{1}{2}$	—	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance \pm % unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7	8	9	10
	RESISTORS—cont.								
	Miscellaneous:—								
	Ohmic values shown:—								
16581	Type 5147	.00625	100 amps.	—	Adjustable	6 $\frac{3}{4}$ in. \times 2 $\frac{3}{4}$ in. with 7 tapping positions Two looped elements of 8 S.W.G. \times 2 ft. Eureka, adjustable distance piece through 2 B.A. terminal. Filament discrimination	C	each	—
16946	Type 5455	0.22 + 0.22	—	—	—	32 amps. Special	C	"	1
8895	Type 203	.03	—	—	—	Enamelled	C	"	1
7461	Type 7461	.05	—	—	—	Wire wound with adjustable oxide-coated tapping band on former 1 in. d. \times 2.94 in.	C	"	10
16242	Type 4869	0.9	—	—	—	On asbestos covered brass tube 9 in. \times 1 in. end lug	C	"	2
6839	Type 6839	.1	10	3	—	On asbestos covered brass tube 13 in. \times 17 in. S.W.G. Eureka wire	C	"	2
8528	Type 2044	.1	10	3	—	On asbestos covered brass tube, 9 in. \times 1 in. end lug	C	"	2
15107	Type 3816	.125	5	—	—	Box type with winding on top bars, 4 $\frac{3}{8}$ in. \times $\frac{3}{8}$ in. \times 1 $\frac{1}{8}$ in. variable	C	"	1
15479	Type 4188	.15	—	6.8	—	On flat former	C	"	2
15147	Type 3856	.17	—	—	—	—	C	"	1
16125	Type 4773	.19	5	—	—	—	C	"	2
15146	Type 3855	.22	—	—	—	—	C	"	1
11723	Type 534	.24	—	—	—	—	C	"	2
9438	Type 2694	.25	—	—	—	—	C	"	1
8772	Type 2222	.28	—	—	—	—	C	"	2
15915	Type 4596	.294	1	—	—	—	C	"	5

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ± % unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7	8	9	10
	RESISTORS—cont.								
	Miscellaneous—cont.								
	Ohmic values shown—cont.								
16443	Type 5021	.3 min. .36 max.	0-36 amps. +10-0	—	Wire wound	Tapped at approx. 0-5 ohms intervals	C	each	1
6002	Type 6002	.3	—	7-5	Wire wound	—	C	"	2
16360	Type 4950	.32	—	—	Wire wound	On SRBP former 3.5 in. × 1.12 in. × 12 in. 2 fixing holes .149 in. dia.	C	"	1
15478	Type 4187	.37	15	1-48	Wire wound	—	C	"	2
		(.185 + .185)							
16776	Type 5293	.4	4	5	Wire wound	—	C	"	10
8733	Type 190	.4	—	—	Variable	25 amps.	C	"	1
8734	Type 191	.4	—	—	Variable	15 amps.	C	"	1
16798	Type 5314	.44	—	—	Wire wound	—	C	"	1
15560	Type 4267	.47	5	4	Wire wound	—	C	"	10
6585	Type 6585	.5	5	2	Wire wound	—	C	"	5
16124	Type 4772	.5	—	5	Wire wound, wire leads	—	C	"	1
9479	Type 252	.5	—	—	—	—	C	"	2
15145	Type 3854	.51	—	—	—	—	C	"	1
15916	Type 4597	.576	1	4	Wire wound	24 to 38 S.W.G. D.S.C. wire wound on Keramot former $\frac{1}{8}$ in. dia. and 2 in. long	C	"	5
16243	Type 4869	.65	—	—	—	—	C	"	2
15719	Type 4414	.66	—	—	Wire wound	Bobbin	C	"	1
8521	Type 147	.75	—	—	Wire wound	—	C	"	2
16769	Type 5286	.75	4	—	Wire wound	—	C	"	5
15442	Type 4151	.75	2	—	Wire wound	Woolcard type, .625 in. square	C	"	2
16970	Type 5479	.75	2	1	Wire wound	—	C	"	1
6467	Type 6467	.75	5	—	Wire wound	Bobbin	C	"	1
8452	Type 2007	.75	10	—	Wire wound	4 $\frac{1}{2}$ -turns 22 S.W.G. Eureka on paxolin panel, 2 $\frac{1}{2}$ in. × $\frac{1}{8}$ in. × 2 in. long	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	Nomenclature	Value in Ohms	Tolerance \pm % unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7	8	9	10
	RESISTORS—cont.								
	Miscellaneous—cont.								
	Ohmic values shown—cont.								
15716	Type 4411	.758	—	—	Wire wound	—	C	each	1
16837	Type 5350	.76	—	—	—	110W/2937 modified by Shellac imp.	C	"	5
15429	Type 4138	.8	5	10	Wire wound	—	C	"	2
8179	Type 130	.85	—	—	Wire wound slate	Former 10 amps.	C	"	2
10417	Type 387	.9	—	—	—	Non-insulated: shunt resistance 9 in. \times 1 $\frac{3}{4}$ in., with end clips	C	"	2
16036	Type 4704	.91	5	—	Wire wound	16 turns of 28 S.W.G. Eureka wire	C	"	1
16694	Type 5216	.92	—	—	Wire wound	Wound on natural Sindonyo former, fully wound 16 S.W.G.	C	"	5
15640	Type 4336	1.0	5	—	Wire wound	—	C	"	5
15881	Type 4564	1.0	1	—	Wire wound	—	C	"	5
15450	Type 4159	1.0	10	6	Wire wound minature	—	C	"	1
16028	Type 4696	1.0	5	10	Wire wound	Ceramic bobbin, 1 in. \times 1 in. dia.	C	"	1
16368	Type 4957	1.0	5	15	Wire wound	—	C	"	1
8729	Type 186	1.06	—	—	Wire wound	Special resistance. 4 $\frac{1}{2}$ -turns No. 28 S.W.G. S.S.C. wound non-inductively on paxolin tube on brass bracket	C	"	2
9557	Type 2808	1.1	—	—	Wire wound	2 turns of 36 S.W.G. Eureka resistance wire on former	C	"	1
15654	Type 4350	1.1	10	4	—	18 S.W.G. Eureka tapped resistance	C	"	10
767	Type 849	1.10	—	—	Wire wound	—	C	"	1
236	Type 688	1.13	—	1 $\frac{1}{4}$	—	—	C	"	1
15918	Type 4599	1.15	1	1 $\frac{1}{4}$	Wire wound	—	C	"	5

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance \pm % unless otherwise stated	Wattage	Type	Details	Class of Class	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7	8	9	10
	RESISTORS—cont. Miscellaneous—cont. Ohmic values shown—cont.								
15806	Type 4489	1.2	10	—	Wire wound	Non-inductive, woolcard type, 0.62 in. sq.	C	each	2
6213	Type 6213	1.4	—	—	Wire wound	—	C	"	2
15919	Type 4600	1.43	1	1/4	Wire wound	—	C	"	5
15561	Type 4268	1.5	5	1/4	Wire wound	—	C	"	10
15425	Type 4134	1.5	5	10	Wire wound on spool	—	C	"	2
16575	Type 5142	1.5	5	5	Wire wound	—	C	"	1
9596	Type 2847	1.5	5	—	Wire wound	Woolcard type 0.62 in. sq.	C	"	2
8817	Type 2254	1.5	—	—	Wire wound	Woolcard type	C	"	2
7751	Type 7751	1.5	—	96	—	Safety protected 12 V. open type sliding resistance with graded winding on slate former to dim load from full to blackout	C	"	1
7910	Type 97	1.5	—	—	Wire wound bobbin	—	C	"	2
7939	Type 7939	1.5	2	—	Wire wound	On cylindrical former	C	"	2
15920	Type 4601	1.73	1	1/4	Wire wound	—	C	"	5
16351	Type 4941	1.8	5	—	Wire wound, ferrules	—	C	"	1
187	Type 655	1.8	—	—	—	Adjusted for FSD of 200 m/A mounted wire wound on R type former	C	"	1
8089	Type 8089	1.8	—	—	Wire wound	Non-inductively wound 32 S.W.G. silk covered Eureka wire	C	"	5
16301	Type 4919	1.8	5	—	Wire wound	Adjusted for FSD of 200 m/A mounted wire wound on R type former	C	"	—
15133	Type 3842	1.8	7 1/2	50	—	Ceramic former, preset	C	"	1
15921	Type 4602	2	1	1/4	Wire wound	—	C	"	5
8394	Type 143	2	—	—	Wire wound bobbin	—	C	"	2

SECTION 10W—cont.

RADIO RESISTORS

Ref. No	NOMENCLATURE	Value in Ohms	Tolerance ± % unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7	8	9	10
	RESISTORS—cont. Miscellaneous—cont. Ohmic values shown—cont.								
15641	Type 4337	2	5	—	Wire wound	32 turns of 30 S.W.G. Eureka wire	C	each	—
8538	Type 2053	2	5	24	Wire wound	16 amps.	C	"	1
16610	Type 5170	2	10	1	—	7 turns of "Tophal C" resistance wire 32 S.W.G. wound on flat	C	"	—
17580	Type 9035	2	10	20	—	Mycalex, 2.4 in. × 1.24 in. × $\frac{1}{8}$ in. wire ends	C	"	1
7450	Type 63	2	—	—	—	Sliding contact fixing feet, 3 terminals	C	"	1
15961	Type 4642	2	—	100	Variable power type	Spindle $\frac{3}{8}$ in. × $\frac{1}{4}$ in. dia., screw-driver slotted, Toroidal wound, without knob	C	"	1
8176	Type 127	2	—	—	—	Flat mica former	C	"	2
15464	Type 4173	2.2	20	—	Wire wound	Enclosed in bakelite case	C	"	1
15922	Type 4603	2.31	1	—	Wire wound	—	C	"	1
15923	Type 4604	2.59	1	—	Wire wound	—	C	"	5
15701	Type 4296	2.6	—	—	Wire wound	—	C	"	5
16613	Type 5173	2.6	—	—	Wire wound	31 S.W.G. wound on Tufnol former	C	"	10
18000	Type 9378	2.7	5	1	Wire wound minia-ture	—	C	"	—
6658	Type 6658	2.75	—	—	—	7 amps.	C	"	1
6545	Type —	2.8	5	10	Wire wound	Spool	C	"	1
8449	Type 2004	2.8	5	20	—	Porcelain former 1 in. dia. × 1 in. high. 6 turns double wound	C	"	2
586	Type 825	2.84	1	—	—	20 S.W.G. Eureka Special	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	Nomenclature	Value in Ohms	Tolerance ±% unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7	8	9	10
	RESISTORS—cont.								
	Miscellaneous—cont.								
	Ohmic values shown—cont.								
15908	Type 4589	2.88	1	½	Wire wound	—	C	each	5
15642	Type 4338	3	5	—	Wire wound	—	C	"	1
1488	Type 1488	3	10	—	Wire wound	Wire wound on Tufool former 2½ in. × ⅞ in.	C	"	1
15550	Type 4259	3	2½	10	Wire wound	—	C	"	2
7507	Type 7057	3	10	4	Wire wound	—	C	"	1
15553	Type 4262	3	2½	2	Wire wound	—	C	"	2
16777	Type 5294	3	7.5	5	Wire wound	—	C	"	1
3344	Type 5	3	—	—	Rheostat	—	C	"	1
8698	Type 2166	3.02	—	—	Wire wound	Approx. 28 in. S.W.G. Eureka D.S.C. wire wound on moulded former	C	"	2
15251	Type 3960	3.125	1	—	Wire wound	—	C	"	2
15924	Type 4605	3.15	1	½	Wire wound	—	C	"	5
16199	Type 4827	3.15	—	2	Non-vitreous	—	C	"	1
9763	Type 284	3.151	—	—	—	—	C	"	1
		(2.63 + .521)							
15700	Type 4395	3.2	—	½	Wire wound	—	C	"	10
1572	Type 1572	3.2	—	—	Wire wound	—	C	"	1
16380	Type 4962	3.4	—	—	Wire wound	Ebonite former	C	"	1
10807	Type 3586	3.4	15	—	Wire wound	Wire wound non-inductive on bakelite strip 2½ in. × 1 in. with tags	C	"	2
8459	Type 139	3.4	—	—	—	Tubular rheostat. 12 amps.	C	"	1
7478	Type 7478	3.5	2	—	—	—	C	"	2
15612	Type 4308	3.5	2	—	Wire wound insl.	—	C	"	1
355	Type 713	3.6	—	—	—	—	C	"	1
7610	Type 7610	3.6	—	—	Wire wound variable	Slate box. Hand Preset	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance \pm % unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Qty.
1	RESISTORS—cont. Miscellaneous—cont.								
15423	Type 4132	3-75	5	10	Wire wound	Wire wound on spool	C	each	2
18001	Type 9379	3-9	5	1	Wire wound	Miniature	C	"	—
15643	Type 4339	4	5	—	Wire wound	25 turns 34 S.W.G. Eureka wire	C	"	—
16369	Type 4958	4	5	10	Wire wound	Bands	C	"	1
16615	Type 5175	4	15	25	Carbon rod	Tubular, 250 \times 25 mm. dia., 15 mm. i/d, with 2 windings wound in opposite directions, 33 turns 28 S.W.G. non-inductive	C	"	—
15208	Type 3917	4	—	—	Wire wound	—	C	"	—
16413	Type 4993	4	10	—	Wire wound	W.W. on Keramot former, 1 in. \times 1 $\frac{1}{4}$ in. dia.	C	"	2
16797	Type 5313	4	—	—	Wire wound	Wire wound on spool	C	"	1
15427	Type 4136	4-1	5	10	Wire wound	—	C	"	2
15699	Type 4394	4-2	—	$\frac{1}{4}$	Wire wound	—	C	"	10
9845	Type 320	4-5	—	—	Wire wound	—	C	"	2
15190	Type 3899	4-5	10	—	Wire wound	Tapped at 9 ohms, 18 S.W.G., Nichrome former	C	"	1
15562	Type 4269	4-75	5	$\frac{1}{4}$	Wire wound	—	C	"	10
16037	Type 4705	4-76	5	—	Wire wound	Non-inductive, shunt resistance, 32 S.W.G. silk covered Eureka wire	C	"	1
6068	Type 6068	5	—	10	—	—	C	"	1
16622	Type 5181	5	15	1	Carbon rod	Tubular, 150 \times 25 mm. o/d \times 15 mm. i/d. Silk covered Eureka wire	C	"	1
16709	Type 5231	5	5	1	Wire wound	—	C	"	1
15426	Type 4135	5	5	10	Wire wound	On spool	C	"	2

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance \pm % unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7	8	9	10
	RESISTORS—cont.								
	Miscellaneous—cont.								
	Ohmic values shown—cont.								
15808	Type 4491	5	5	45	Wire wound	Pigtails	C	each	1
953	Type 979	5	—	5	—	—	C	"	1
16211	Type 4839	5	10	6	Wire wound	Miniature Eureka wire wound on tubular micalex former	C	"	1
8811	Type 2248	5	10	—	Wire wound	10 amps. with sliding contact	C	"	2
7449	Type 62	5	—	—	—	—	C	"	1
15175	Type 3884	5	2	—	—	58 turns S.W.G. Eureka wire on bakelite former, $\frac{5}{8}$ in. \times $\frac{1}{4}$ in. dia, with 18 S.W.G. brass wire insert each end	C	"	—
8711	Type 2173	5	2	—	Wire wound	On cylindrical former and wired adjustable brass clip, fitted with 6 B.A. screw and nut	C	"	1
16435	Type 5013	5	10	—	Wire wound	Non-inductive winding on bakelite board with 2 end studs	C	"	1
15698	Type 4393	5-1	—	—	Wire wound	9 in. \times $1\frac{1}{4}$ in. with end clips	C	"	10
16693	Type 5215	5-2	5-9 amps	$\frac{1}{4}$	Wire wound	Open	C	"	1
16573	Type 5140	5-6	5	5	Wire wound	—	C	"	1
1635	Type 1635	5-7	10	10	Wire wound	—	C	"	1
15909	Type 4590	5-75	1	$\frac{1}{4}$	Wire wound	$\frac{1}{8}$ in. thick micaite; 34 turns of 26 S.W.G. en wire	C	"	5
7808	Type 7808	6	5	—	Wire wound	Special, 100 m/A	C	"	2
587	Type 826	6	1	—	Special	Wire wound on moulded former	C	"	1
7918	Type 7918	6-07	2 $\frac{1}{2}$	—	Wire wound	On cylindrical former	C	"	2
8355	Type 8355	6-25	1	—	Wire wound	6-5 amps. Tubular rheostat.	C	"	1
7868	Type 91	6-4	—	—	—	External spindle motion	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ± % unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7	8	9	10
	RESISTORS—cont.								
	Miscellaneous—cont.								
	Ohmic values shown—cont.								
15926	Type 4607	6.25	2½	—	—	Wire wound 32 S.W.G. Eureka wire	C	each	5
15697	Type 4392	6.5	—	—	Wire wound	Insulated	C	"	10
15646	Type 4342	6.8	5	¼	Wire wound	Miniature	C	"	5
16018	Type 4693	7	5	7.5	Wire wound	Attenuator panel, 2¼ in. × 1¾ in. × ½ in., bakelite	C	"	1
15214	Type 3923	7.35-1.5	—	—	—	Terminal bands each end	C	"	—
16241	Type 4867	7.35	—	—	Wire wound	—	C	"	2
15558	Type 4265	7.4	1	—	Wire wound	—	C	"	—
15132	Type 3841	7.4	7½	50	Wire wound	Ceramic former Preset	C	"	1
1132	Type 1132	7.5	—	—	Wire wound	8 amps.	C	"	1
15819	Type 4502	8	5	6	Wire wound	Miniature	C	"	1
8876	Type 2298	8	—	200	—	—	C	"	1
15134	Type 3843	8	7½	50	Wire wound	Ceramic former Preset	C	"	1
17754	Type 9199	8	4.3 amps	—	Wire wound	Asbestos and ferry wire 3½ in. × 1¼ in.	C	"	1
9536	Type 2787	8	—	—	Wire wound	—	C	"	2
9635	Type 273	8	—	—	—	—	C	"	2
17791	Type 9236	8	—	15	Wire wound	Slotted tube loop terminals, 2 in. × ⅝ in. dia.	C	"	1
16485	Type 5056	8.2	¼	5	Wire wound	Miniature	C	"	1
15696	Type 4391	8.2	—	¼	Wire wound	—	C	"	10
16576	Type 5143	8.3	2½	5	Wire wound	—	C	"	1
6315	Type 6315	8.3	—	—	—	Shunt with 2 point plug	C	"	1
15714	Type 4409	8.34	—	—	Wire wound	Meter shunt	C	"	1
15533	Type 4242	8.6	2	¼	Wire wound	—	C	"	10
17989	Type 9367	8.34 × 3 ohms at 10 amps. each	1	¼	Wire wound, variable	3 hexagonal tubes, 14 in. × 2½ in., tropical	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

1	2	3	4	5	6	7	8	9	10
Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance \pm % unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
15910	RESISTORS—cont. Miscellaneous—cont. Ohmic values shown—cont. Type 4591	8.65	1	$\frac{1}{4}$	Wire wound	—	C	each	5
15882	Type 4565	10	1	—	Wire wound	Moulded	C	"	1
15644	Type 4340	10	5	—	Wire wound	42 turns of 36 S.W.G. Eureka wire	C	"	—
16616	Type 5176	10	15	25	Carbon (rod)	250 \times 25 mm. dia. tube, 15 mm. i/d	C	"	—
15492	Type 4201	10	10	$\frac{1}{4}$	Wire wound	—	C	"	10
17397	Type 5853	10	2	—	Wire wound	60 turns of 32 S.W.G. Eureka wire, on bakelite former $1\frac{1}{8}$ in. \times $\frac{1}{4}$ in., brass wire insert each end	C	"	1
16788	Type 5304	10	—	200	Wire wound	Centre tapped nickel copper winding flat. Former $7\frac{3}{8}$ in. \times $1\frac{1}{8}$ in.	C	"	1
1489	Type 1489	9-3	—	—	—	—	C	"	1
5492	Type 4201	10	10	$\frac{1}{4}$	Wire wound	—	C	"	1
6294	Type 6294	10	10	1	Variable	—	C	"	2
18002	Type 9380	10	5	1	Wire wound	Miniature	C	"	—
15782	Type 4466	10	5	3	Wire wound	Miniature	C	"	—
1030	Type 1030	10	—	—	Variable	—	C	"	2
16010	Type 4687	10	10	—	—	Ceramic bobbin	C	"	—
16607	Type 5167	10	20	$\frac{1}{4}$	Wire wound	—	C	"	5
6955	Type 6955	10	—	—	—	Vitreous protected	C	"	—
7839	Type 7839	10	1	$\frac{1}{4}$	Wire wound	20 S.W.G. D.S.C. copper wire connector wound to former.	C	"	5
10530	Type 3433	10	10	—	Wire wound	Resistance coil $\frac{1}{4}$ in. long \times $\frac{7}{16}$ in. dia.	C	"	—
7858	Type 7858	10	—	—	—	Ceramic former $\frac{3}{8}$ in. dia. \times $\frac{1}{8}$ in.	C	"	2
8344	Type 8344	10	10	—	Wire wound	—	C	"	—
17657	Type 9106	10	5	15	Wire wound	—	C	"	—

RESTRICTED

RESTRICTED

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance \pm % unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1		3	4	5	6	7	8	9	10
1782	RESISTORS—cont. Miscellaneous—cont. Ohmic values shown—cont. Type 1782	10	5	10	Wire wound	Ceramic spool 1 in. dia. \times 1 in. wide	C	each	1
17855	Type 9296	10	10	2½	Wire wound, fixed	Ceramic bobbin, 1 in. \times 1 in. dia. approx., with 2 soldering tags	C	"	1
8393	Type 142	10	—	—	Wire wound	Bobbin	C	"	2
15809	Type 4492	10	2½	2	Wire wound	Moulded bobbin, 1 in. dia. \times ½ in. long, 2 soldering tags	C	"	1
16035	Type 4703	10.05	5	—	Wire wound	Non-inductive; shunt resistance 40 S.W.G.	C	"	1
15695	Type 4390	10.3	—	½	Wire wound	Ceramic bobbin, 1 in. \times 1 in. long, 2 soldering tags	C	"	10
15810	Type 4493	11	2½	10	Wire wound	Non-inductive	C	"	1
1247	Type 1247	11	—	—	No. 1 plate	Non-inductive	C	"	1
17998	Type 9376	11.2	1	2½	Wire wound	Tubular	C	"	—
18479	Type 9473	11.2	1	4-5	Wire wound	Non-inductive	C	"	1
15911	Type 4592	11.45	1	½	Wire wound	Non-inductive	C	"	5
16778	Type 5295	12	1	10	Wire wound	Bobbin	C	"	1
8392	Type 141	12.5	—	—	Wire wound	Variable. 2 hexagonal tubes, 8 in. \times 1½ in., 6.5 amps current rating. Tropical. 11¼ in. \times 3½ in. \times 2½ in.	C	"	2
16318	Type 4934	13 (total)	—	—	Wire wound	Bobbin	A	"	1
15694	Type 4389	13	—	½	Wire wound	50 m/A	C	"	10
536	Type 802	13.5	1	—	—	On porcelain, 1½ in. \times 9¼ in. long. Terminal and clips.	C	"	1
15912	Type 4593	14.3	1	½	Wire wound	(Replaces stripment resistors)	C	"	5
18018	Type 9396	14.5	—	—	Wire wound	Moulded former	C	"	—
17424	Type 5880	15	2½	5	Wire wound		C	"	—

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	Nomenclature	Value in Ohms	Tolerance ±% unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. Qty.	Carton Unit Qty.
1	2	3	4	5	6	7	8	9	10
16964	RESISTORS—cont. Miscellaneous—cont. Ohmic values shown—cont. Type 5473	15	10	4	Wire wound	Miniature fixed 150 × 25 mm. × 15 mm. i/d 1.6 amps. 5 amps Tubular 3 1/8 in. × 6 1/4 in. Flat paxolin strip. Wound with Eureka wire on porcelain former On moulded former Asbestos and Ferry wire, 3/8 in. × 2 3/8 in. On former 1 in. dia. × 1 in., 36T, 30 S.W.G. Wire wound, tubular Tubular, 10 in. × 2 in., max. element Non-vitreous On spool Non-vitreous, enamelled	C	each	—
16614	Type 5174	15	15	25	Carbon rod		C	"	1
18466	Type 9450	15	—	35-40	—		C	"	1
9846	Type 321	15	—	—	Variable		C	"	1
15149	Type 3838	15	10	12	—		C	"	1
17942	Type 9426	15	2 1/2	4-5	Wire wound		C	"	1
6097	Type 6097	15	5	25	Asbestos net		C	"	1
15563	Type 4270	15.2	5	1	Wire wound		C	"	10
6411	Type 6411	(10.72 + 1.92 + 1.92 + 0.76)	—	—	—		C	"	2
7919	Type 7919	15.32	2 1/2	—	Wire wound		C	"	2
17755	Type 9200	15.4	0.43	—	Wire wound	C	"	1	
8069	Type 8069	16	2 1/2	10	Wire wound	C	"	1	
17944	Type 9428	16	1	4-5	—	C	"	—	
15693	Type 4388	16.3	—	1 1/4	Wire wound	C	"	10	
15913	Type 4594	17.1	1	1 1/4	Wire wound	C	"	5	
16686	Type 5209	17.5	2.5	500	Variable	C	"	—	
16484	Type 5055	18	1/2	1	Wire wound minia- ture	C	"	—	
15094	Type 3803	18	1	10	Wire wound	C	"	1	
15148	Type 3857	18	10	12	—	C	"	1	
15428	Type 4137	18.5	2 1/2	10	Wire wound	C	"	2	
15256	Type 3965	18.75	0.5	—	—	C	"	—	
16734	Type 5252	19	5	1	Wire wound	C	"	1	
15914	Type 4595	19.9	1	1 1/4	Wire wound	C	"	5	

SECTION 10W—cont.

RADIO RESISTORS

1	2	3	4	5	6	7	8	9	10
Ref. No.	Nomenclature	Value in Ohms	Tolerance \pm % unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1									
15645	RESISTORS—cont. Miscellaneous—cont. Ohmic values shown—cont. Type 4341	20	5	—	Wire wound	39 turns of 39 S.W.G. Eureka wire	C	each	—
6586	Type 6586	20	10	—	Carbon	—	C	"	5
9533	Type 2784	20	20	$\frac{1}{2}$	Wire wound	—	C	"	1
7223	Type 7223	20	20	7.5	Wire wound	No. 34 S.W.G. Eureka wire wound on mica card, approx. 1 ft. 5 in. \times 1 ft. 0 in.	C	"	2
15677	Type 4373	20	—	—	Wire wound	—	C	"	1
10982	Type 398	20	—	—	—	24 gauge Eureka wire on mica former $1\frac{1}{8}$ in. \times $1\frac{1}{8}$ in. overall, tags. Special	C	"	5
9025	Type 2397	20	—	—	Wire wound	—	C	"	2
7498	Type 66	20	—	—	Wire wound	—	C	"	2
11319	Type 471	20	—	2	—	—	C	"	5
7840	Type 7840	20	1	$\frac{1}{2}$	Wire wound	NI	C	"	5
15580	Type 4285	20-2	2	—	Wire wound	Non-inductive	C	"	2
15437	Type 4146	21	5	3	Wire wound	Miniature	C	"	1
15992	Type 4669	21	5	6	Wire wound	Miniature	C	"	1
18003	Type 9381	22	5	1	Wire wound	Miniature	C	"	1
17276	Type 5733	22	10	1	Wire wound	Miniature	C	"	1
16982	Type 5491	22	5	2.5	Wire wound	Miniature	C	"	—
16962	Type 5471	22	10	2.5	Wire wound	Miniature	C	"	—
1040	Type 1040	25	—	—	Wire wound	Wire wound on paxolin strip 1 in. \times $\frac{1}{2}$ in. \times $\frac{1}{8}$ in. approx., tags On circular bobbin 1 in. dia. \times 1 in. (P.O. No. 9)	C	"	2
18465	Type 9449	25	—	5-10	Wire wound	Non-inductive on moulded bakelite former, wire and connections	C	"	—
16353	Type 4943	25	5	—	Wire wound	—	C	"	1

RESTRICTED

RESTRICTED

SECTION 10W—cont.

RADIO RESISTORS

1	2	3	4	5	6	7	8	9	10
Ref. No.	Nomenclature	Value in Ohms	Tolerance ±% unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1									
6100	RESISTORS—cont. Miscellaneous—cont. Ohmic values shown—cont. Type 6100	25	5	42	—	Asbestos woven resistance net 5 $\frac{3}{8}$ in. \times 7 $\frac{1}{2}$ in. Ceramic metal ends Close wound with 63 turns 30 S.W.G. enamelled Eureka wire wound on Marconi former SK48931	C	each	1
15185	Type 3984	25	5	10	Wire wound		C	"	2
7479	Type 7479	25	—	—	—		C	"	—
16608	Type 5186	26	10	$\frac{1}{2}$	Wire wound		C	"	5
15730	Type 4424	26	—	—	—		C	"	2
16772	Type 5289	27	1	5	Wire wound		C	"	1
8810	Type 2247	28 (14 + 14)	5	—	—		C	"	2
16623	Type 5182	30	15	25	Carbon rod		C	"	—
16448	Type 5026	30	5	37 $\frac{1}{2}$ —45	Wire wound		C	"	1
1428	Type 1428	30	—	40	—		C	"	—
15728	Type 4422	30	—	—	Wire wound		C	"	1
15546	Type 4255	30	10	—	Wire wound		C	"	1
15174	Type 3883	31.5	2	—	—		C	"	—
9597	Type 2848	31.5	$\frac{1}{2}$	—	Wire wound		C	"	2
16577	Type 5144	31.5	2 $\frac{1}{2}$	5	Wire wound		C	"	1
15583	Type 4288	32.51	2	—	Wire wound		C	"	2
16981	Type 5490	33	5	2.5	Wire wound		C	"	1
17041	Type —	33	—	15	—		C	"	3
16736	Type 5253	33	10	$\frac{1}{2}$	Wire wound		C	"	1
16963	Type 5472	33	10	2.5	Wire wound		C	"	—

RESTRICTED

RESTRICTED

125

Issued with A/L 41 to A.P. 1086—Book 4 (iii)

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	Nomenclature	Value in Ohms	Tolerance ±% unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1		3	4	5	6	7	8	9	10
	RESISTORS—cont. Miscellaneous—cont. Ohmic values shown—cont.								
17044	Type —	33	20	—	—	—	C	each	3
15545	Type 4254	35	3½	2	Wire wound	Wire wound on bakelite former	C	"	2
6948	Type 6948	35	10	½	Wire wound	Insulated bakelite tube	C	"	5
10979	Type 3691	37	10	10	Wire wound	Wire wound on ceramic bobbin 1 in. long × 1 in. dia. Wire ends	C	"	2
15840	Type 4523	40	5	3	Wire wound	Side wires. ¼ in. × ⅜ in. dia.	C	"	2
7608	Type 7608	40	5	4	Wire wound	Non-vitreous Spindles protected	C	"	1
6098	Type 6098	40	5	68	—	Asbestos woven resistance net 7¼ in × 8½ in.	C	"	1
7453	Type 7453	40	2½	2	Wire wound	44 turns S.W.G. Nickel chrome wire on mycalex former 1¼ in. × 4 in. × ¼ in.	C	"	2
16688	Type 5193	40	—	—	Wire wound	Adjustable lead (Ref. 10) end wires	C	"	—
15441	Type 4150	40	10	—	Wire wound	Wire on porcelain tube 1 in. × 1 in. dia.	C	"	1
1609	Type 1609	40	—	15	Wire wound	Flat	C	"	2
7786	Type 82 . .	40	—	—	Wire wound	—	C	"	2
16578	Type 5145	42	2½	5	Wire wound	—	C	"	—
6408	Type 6408	42	2	—	—	Eureka wire on flat porcelain former	C	"	2
17934	Type —	50	2½	4-5	Wire wound	Tubular	C	"	1
1167	Type 1167	46-25	—	—	Rheostat	6-5/3-3 amps.	C	"	1
16961	Type 5470	47	1	1	Wire wound	Miniature fixed	C	"	1
16773	Type 5290	47	1	5	Wire wound	—	C	"	1
8184	Type 8184	48-5	—	—	Wire wound	Wire wound plate 8½ in. × 3½ in. with slotted ends for term studs	C	"	1

RESTRICTED

RESTRICTED

SECTION 10W—cont.

RADIO RESISTORS

1	2	3	4	5	6	7	8	9	10
Ref. No.	Nomenclature	Value in Ohms	Tolerance $\pm\%$ unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1									
	RESISTORS—cont. Miscellaneous—cont. Ohmic values shown—cont.								
1056	Type 1056	49	1	—	Wire wound	Meter shunt. Tapped —0, 10, 29, 5, 49 20°C., 65 volts, 150×23/15 mm. $\frac{1}{4}$ in. dia. × $1\frac{1}{2}$ in. long	C	each	5
6269	Type 6269	50	—	—	—	2 amp. vitreous enamelled tubular	C	"	1
17037	Type —	50	—	2	—	N.1 Tubular, single screw fixing	C	"	1
15853	Type 4536	50	—	4	Variable pot	$1\frac{1}{8}$ in. × $\frac{81}{64}$ in. dia.	C	"	1
1279	Type 1279	50	—	—	Semi-variable	Tropical. WW. on former 1 in. dia. × 1 in. 58 turns 34 S.W.G. B.E.	C	"	2
7811	Type 7811	50	—	2	Wire wound		C	"	1
17940	Type 9424	50	1	4.5	Wire wound		C	"	1
8070	Type 8070	50	2 $\frac{1}{2}$	10	Wire wound		C	"	2
9050	Type 2412	50	—	30	Wire wound	WW. on mica 5 in. × $1\frac{1}{4}$ in. 2 fixing holes, $\frac{3}{8}$ in. dia., 5 in. centres	C	"	1
15210	Type 3919	50	—	40	Wire wound	Moulded bobbin with 2 soldering tags. Dims. overall × $\frac{5}{8}$ in.	C	"	1
17858	Type 9299	50	2	3	Wire wound, fixed	WW. and vitreous enamelled covered tags (Ericson)	C	"	1
10817	Type 3596	50	2 $\frac{1}{2}$	5	Wire wound	Suffix "A" denotes adjustable type	C	"	1
15247	Type 3956	50	5	10	Wire wound	Ceramic, metal ends	C	"	1
15186	Type 3895	50	5	10	Wire wound	Ceramic, tubular, 3 in. × $\frac{1}{8}$ in. o/d × $\frac{3}{8}$ in. 1/d	C	"	1
16794	Type 5310	50	5	10	Wire wound	Pigtails	C	"	1
16687	Type 5210	50	5	100	Wire wound	Miniature	C	"	1
15690	Type 4385	50	10	6	Wire wound	Tapped 50, 70, 80, 90, 150, 160, 170, 180, 190 ohms at 200 v. D.C.	C	"	5
17522	Type 5977	50-190	—	2.5	—		C	"	5
15649	Type 4345	51	5	1	Wire wound	Insulated. Tropical	C	"	5

RESTRICTED

RESTRICTED

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	Nomenclature	Value in Ohms	Tolerance ±% unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1									
708	RESISTORS—cont. Miscellaneous—cont. Ohmic values shown—cont.								
16137	Type 884	54	1	—	—	25 m/A	C	each	1
18013	Type 4784	56	10	2	Wire wound	—	C	"	1
16779	Type 9391	57	—	—	—	1/8 in. spindle. Sawcut	C	"	1
1248	Type 5296	60	1	—	Wire wound	—	C	"	1
7785	Type 1248	60	—	—	Wire wound	—	C	"	1
15517	Type 7785	60	2 1/2	10	Wire wound	1 in. × 1 in. dia.	C	"	2
15111	Type 4226	60	5	5	Wire wound	Non-inductive	C	"	2
18468	Type 3820	60	—	30	Wire wound	Variable tap	C	"	1
	Type 9462	60	2 1/2	—	Wire wound	N.1. Tubular 3/8 in. × 1 1/4 in., single screw fixing	C	"	1
16980	Type 5489	120	2 1/2	—	Wire wound	Miniature, fixed	C	"	—
15434	Type 4143	240	5	1	Wire wound	Woolcard type 0.625 in. sq.	C	"	2
17398	Type 5854	63	5	2	Wire wound	120 turns of 38 S.W.G. Eureka wire, bakelite former 1 1/8 in. × 1/4 in., brass wire insert each end	C	"	1
15438	Type 4147	63	5	3	Wire wound	250 × 25 mm.	C	"	1
16770	Type 5287	63	1	5	Wire wound	—	C	"	1
15184	Type 3893	65	25	35	Carbon rod	—	C	"	1
7454	Type 7454	65	2 1/2	2	Wire wound	Miniature	C	"	1
18004	Type 9382	68	5	1	Wire wound	Miniature, fixed	C	"	1
16960	Type 5469	68	10	1	Wire wound	44 S.W.G. Eureka	C	"	—
10733	Type 3357	69.6	—	—	Wire wound	—	C	"	5
7838	Type 7838	70	1	1	Wire wound	Meter shunt	C	"	1
15721	Type 4416	70	—	—	Wire wound	Non-inductive	C	"	1
15582	Type 4287	72	—	—	Wire wound	Asbestos former	C	"	2
10950	Type 3665	72.5	2	6	Wire wound	Insert tapped at 68 A.	C	"	1
10599	Type 3475	75	10	—	Wire wound	—	C	"	—
16975	Type 5484	75	15	50	Carbon rod	—	C	"	—

RESTRICTED

RESTRICTED

SECTION 10W—*cont.*

RADIO RESISTORS

1	2	3	4	5	6	7	8	9	10
Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance \pm % unless otherwise stated	Wattage	Type	Details	Class of Store	Denom of Qty.	Carton Unit Qty.
1559	RESISTORS—<i>cont.</i> Miscellaneous—<i>cont.</i> Ohmic values shown—<i>cont.</i> Type 1559	75	—	—	—			each	1
15766	Type 4452	75	1	1	Wire wound	Twin feeder (wire enclosed in rubber tube, sealed)	C	"	—
11789	Type 879	75	15	35	Carbon rod	On loaded ebonite former 250 X 25 mm., 15 mm. bore. Heavy duty	C	"	1
15579	Type 4284	81-82	2	—	Wire wound	Non-inductive	C	"	2
15433	Type 4142	83.3 (8.3 + 75)	.03 and 5	—	Wire wound	Wire wound on S.R.B.P. former 2.25 in. X 0.5 in. X 0.06 in. Miniature	C	"	5
16358	Type 4948	84	5	3	Wire wound	Vitreous rod 7 $\frac{1}{4}$ in. overall, $\frac{1}{16}$ in. ferrules	C	"	1
15917	Type 4598	85	1	$\frac{1}{2}$	Wire wound		C	"	5
17416	Type 5872	90	15	—	Wire wound		C	"	1
9268	Type 2595	90	5	—	—		C	"	2
8182	Type 8182	90	—	—	Wire wound	On plate 2 $\frac{3}{4}$ in. X 7 $\frac{1}{4}$ in., with slotted ends for terminal studs	C	"	1
15770	Type 4455	90	5	3	Wire wound	Miniature	C	"	1
1751	Type 1751	90 (45 + 45)	2	—	Wire wound		C	"	1
15838	Type 4521	96	5	3	Wire wound	Side wire. $\frac{3}{4}$ in. X $\frac{3}{8}$ in. Insulated. Bakelite tube	C	"	1
8515	Type 2037	100	15	$\frac{1}{2}$	Wire wound	Miniature	C	"	1
17278	Type 5735	100	10	1	Wire wound	Open coil. Varnished	C	"	1
7144	Type 7144	100	2 $\frac{1}{2}$	10	—		C	"	2
10976	Type 3688	100	10	4	Wire wound		C	"	1
10587	Type 3464	100	—	—	—		C	"	1
8701	Type 170	100	—	10	Wire wound	Cartridge type	C	"	1
1055	Type 1055	100	1	—	Wire wound	Meter shunt. Tapped 0, 10, 12.9, 18.2, 30.8, 100	C	"	1
6146	Type 6146	100	—	20	Variable		C	"	1
259	Type 699	100	—	—	—		C	"	1
15768	Type 4454	100	—	—	—	0.00028 lb. 38 S.W.G. Eureka wire wound on bobbin	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ±% unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.	
1		3	4	5	6	7	8	9	10	
17938	RESISTORS—cont. Miscellaneous—cont. Ohmic values shown—cont. Type 9422 Type 9410	100	1	4-5	Wire wound	Tubular Tubular 1 $\frac{1}{8}$ in. × $\frac{1}{16}$ in. Single screw fixing	C	each	—	
17926		100	2 $\frac{1}{2}$	4-5	Wire wound		C	"	1	
		200	2 $\frac{1}{2}$							
		400	2 $\frac{1}{2}$							
		102	—		—	Wire wound	Porcelain case. Cap ends	C	"	1
1271		Type 1271	103	—	—	—	0-55 amps.	C	"	1
10636		Type 408	103	—	—	Wire wound bobbin	Shunt for milliammeter	C	"	1
7083		Type 31	110	5	6	Wire wound	Special, 120 turns 32 S.W.G.	C	"	1
15972		Type 4651	110	5	6	—	Miniature	C	"	1
6087		Type 6087	120	10	6	Wire wound	Miniature	C	"	1
15936	Type 4617	120	10	12	Wire wound	Miniature	C	"	1	
16306	Type 4924	122	10	10	Wire wound on spool	Wound on spool	C	"	2	
15424	Type 4133	122	2 $\frac{1}{2}$	5	Wire wound	—	C	"	1	
16579	Type 5176	125	2 $\frac{1}{2}$	5	—	0-69 amp.	C	"	1	
8633	Type 162	125	—	—	—	Miniature	C	"	1	
15310	Type 4019	126	5	3	Wire wound	Lead screw	C	"	1	
9323	Type 240	135	—	—	Wire wound, variable	Variable potentiometer	C	"	1	
8390	Type 140	135	—	—	Wire wound	—	C	"	1	
15311	Type 4020	140	5	3	Wire wound	Miniature	C	"	1	
10666	Type 414	140	10	—	—	2 adjustable clips. Wound on tube 9 $\frac{1}{2}$ in. × 1 $\frac{1}{2}$ in. × 1 $\frac{1}{2}$ in. high. 0-5 amp.	C	"	1	
7451	Type 7451	140	—	—	—	Miniature	C	"	1	
16312	Type 4928	150	5	7-5	Wire wound	On porcelain tube, 1 in. × 1 in. dia. Tags	C	"	1	
1611	Type 1611	150	—	15	Wire wound	Stearite spool, 0-67 in. dia. × 1-94 in. Over terminal, wound with 36 S.W.G. B.E. S.S.C. wire	C	"	2	
1927	Type 1927	150	2 $\frac{1}{2}$	5	—	—	C	"	—	

100
100
200
400
} in series

RESTRICTED

RESTRICTED

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	Nomenclature	Value in Ohms	Tolerance \pm % unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1									
	RESISTORS—cont.								
	Miscellaneous—cont.								
	Ohmic values shown—cont.								
253	Type 694	150	—	2½	—	—	C	each	1
16249	Type 4874	150	10	—	Wire wound	Ceramic spool	C	"	1
8520	Type 146	150	—	—	+ 150 ohms. Wire wound	Bobbin	C	"	2
16971	Type 5480	150	—	50	Carbon rod	—	C	"	1
6813	Type 6813	150	10	35	Wire wound	—	C	"	1
8667	Type 160	152	—	—	Variable	2 amps. Double tube	C	"	1
15581	Type 4286	159.5	2	—	Wire wound	Non-inductive	C	"	2
16774	Type 5291	160	1	5	Wire wound	—	C	"	1
15836	Type 4518	169	5	3	—	—	C	"	2
8668	Type 161	173	—	—	Variable	Side wire, ¼ in. × ⅜ in. dia.	C	"	1
15835	Type 4519	179	5	3	—	Single tube. 1.0 amp.	C	"	2
15045	Type 3754	180	10	—	—	Side wire. ⅜ in. × ⅜ in. dia.	C	"	1
17890	Type 9331	180	—	—	F.S. fittings	—	C	"	1
7143	Type 7143	200	2½	10	WV. on ceramic spool	—	C	"	1
16574	Type 5140	200	—	—	—	—	C	"	1
16972	Type 5481	200	—	50	Carbon rod	Bobbin	C	"	1
9100	Type 264	200	—	—	—	—	C	"	2
9164	Type 2507	200	20	—	—	Enamelled, tubular	C	"	1
7810	Type 7810	200	—	6	Wire wound	Moulded bobbin with 2 soldering tags. Dims. 0/all. 1 in. × ⅝ in.	C	"	2
17862	Type 9303	200	2	3	Wire wound	1¼ in. × 6¼ in. Non-inductive	C	"	1
7777	Type 7777	200	10	—	—	—	C	"	2
17939	Type 9423	200	½	—	Wire wound tubular	—	C	"	1
16175	Type 4820	200	2½	—	Wire wound	—	C	"	1
16011	Type 4688	200	10	—	Wire wound	—	C	"	1
16861	Type 5731	200	20	3	Wire wound	Ceramic bobbin ¾ in. × ⅝ in. Dims. ⅝ in.; insulated sp. inc. bush	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

1	2	3	4	5	6	7	8	9	10	
Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance \pm % unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.	
	RESISTORS—cont.									
	Miscellaneous—cont.									
	Ohmic values shown—cont.									
15750	Type 4440	200	10	8	Variable	Continuous; 4 in. long; $\frac{5}{8}$ in. o/d collar fixing, $\frac{1}{4}$ in. wide 0-316 S.W.G. on former (5U/1028), two end caps and tappings Tubular. $1\frac{1}{8}$ in. \times $\frac{5}{8}$ in. dia. Single screw fixing	C	each	1	
15302	Type 4011	200	—	—	Wire wound		C	"	1	
17932	Type 9416	200 4000 in series	1	4-5	Wire wound		C	"	1	
16979	Type 5488	220	5	1	Wire wound	Miniature, fixed Former wound with 365 turns of 38 S.W.G. D.S.C. Eureka wire, $2\frac{1}{2}$ in. long, side wires Tubular, 3 windings "Y" form $\frac{5}{8}$ in.	C	"	—	
16237	Type 4863	230	1	—	Wire wound		C	"	1	
18480	Type 9474	244.06 244.06 615.5 245	1 1 1 1	—	Wire wound		C	"	1	
16696	Type 5218	250	—	—	Wire wound	230 turns on tube 1 in. dia., 6.6 in. overall, 6 in. fixing centres On circular bobbin 1 in. dia. \times 1 in. long (P.O. No. 9 type) Pigtails	C	"	1	
18471	Type 9465	250	2 $\frac{1}{2}$	10	Wire wound		C	"	1	
16212	Type 4840	250	5	—	Wire wound		C	"	1	
17985	Type 9365	250	5	3	Wire wound		C	"	—	
16609	Type 5169	250	20	$\frac{1}{2}$	Wire wound		C	"	5	
1584	Type 1584	250	10/15	20	Wire wound		C	"	2	
1100	Type 1100	250	10	4	—	Semi-variable Ceramic bobbin	C	"	5	
323	Type 741	250	—	—	—		C	"	2	
18458	Type 9222	258.4 567.7 258.4 260	2 $\frac{1}{2}$ 2 $\frac{1}{2}$ 2 $\frac{1}{2}$ 2	— — — 4.5	Wire wound, tubular	3 windings in Y form	C	"	1	
15619	Type 4315	260	2	100	Wire wound	Mica former. Dims. A = $3\frac{1}{2}$ in., B = $2\frac{1}{2}$ in.	C	"	1	
15141	Type 3850	262.5	2 $\frac{1}{2}$	—	Wire wound	Moulded former	C	"	1	

RESTRICTED

RESTRICTED

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	Nomenclature	Value in Ohms	Tolerance ±% unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	1	3	4	5	6	7	8	9	10
	RESISTORS—cont.								
	Miscellaneous—cont.								
	Ohmic values shown—cont.								
10639	Type 5496	270	—	—	Wire wound	Variable slide	C	each	—
16284	Type 4904	300	—	2	Wire wound	1 in. × $\frac{1}{8}$ in. dia.	C	"	1
17936	Type 9420	300	2½	4.5	Wire wound	Tubular	C	"	1
16704	Type 5226	300	5	1	Wire wound	—	C	"	1
17854	Type 9295	300	10	2½	Wire wound	Ceramic bobbin, 1 in. × 1 in. dia., approx., with 2 soldering tags	C	"	1
15320	Type 4029	300	—	—	Wire wound	36 S.W.G. D.S.C. en. wire on 2-slot midjet porcelain former, 0.562 in. o/d × $\frac{1}{8}$ in.	C	"	2
15083	Type 3792	330	1-5	—	—	Rheostat, back panel mounting, hand wheel operated from front of panel, $\frac{1}{2}$ in. sheet S.S. and enam. constantin wire wound on bobbin 0.70 in. long, checks 0.6 in. dia. × $\frac{1}{16}$ in. approx., shank 0.2 in. dia.	C	"	5
17991	Type 9369	350	10	—	—	Tubular	C	"	—
18455	Type 9439	350	2½	4.5	Wire wound	Mica slab	C	"	1
291	Type 717	350	—	—	—	Wire wound, variable	C	"	1
9534	Type 2785	350	—	—	Wire wound	On 3 sections bobbins, 2 in. × $\frac{3}{8}$ in., 6 B.A. shank for Aying	C	"	1
16775	Type 5292	360	1	5	Wire wound	40 S.W.G. D.C.C. Eureka wire	C	"	1
9154	Type 2502	363	1	—	Wire wound	—	C	"	1
16271	Type 4891	368	—	—	Wire wound	Ceramic bobbin 1 in. × 1 in.	C	"	1
16708	Type 5230	390	5	1	Wire wound	Tubular, 1 screw fixing. Size	C	"	1
15253	Type 3962	400	2½	10	Wire wound	$\frac{23}{32}$ in. × $1\frac{1}{4}$ in. long.	C	"	2
18473	Type 9467	400	2½	4-5	Wire wound	double turns	C	"	1

RESTRICTED

RESTRICTED

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	Nomenclature	Value in Ohms	Tolerance \pm % unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.	
1	2	3	4	5	6	7	8	9	10	
	RESISTORS—cont.									
	Miscellaneous—cont.									
	Ohmic values shown—cont.									
17856	Type 9297	400.	10	2½	Wire wound	Ceramic bobbin 1 in. \times 1 in. dia. approx., with 2 soldering tags	C	each	1	
7782	Type 7782	400	2½	2	Wire wound	Miniature	C	"	2	
15521	Type 4230	400	10	12	Wire wound	Cartridge type, 10 watts	C	"	1	
8696	Type 168	400	—	—	Wire wound	Tubular, 1 1/8 in. \times 5/8 in. dia. Single screw fixing	C	"	2	
17931	Type 9415	400	1	4-5	Wire wound		C	"	1	
		400								
		400								
17943	Type 9427	446 554 450 490	2½ in series	4-5 57 180	Wire wound Wire wound	Tubular	C	"	—	
1262	Type 1262	450	—	—	Wire wound	230 V. dimmer. Sliding resistance, with graded winding on slate former to dim lead from full to blackout. 0.8 amp. Moulded bobbin, 2 S. tags, 1 in. \times 5/8 in.	C	"	1	
7749	Type 7749	490	—	—	Wire wound		C	"	1	
16362	Type 4962	500	—	2½	—	Power type, toroidal wound Nickel copper, ferrite winding for 530uH. Ind. \pm 10% vitreous on double glazed copper ends. Tropicalised	C	"	1	
15966	Type 4647	500	5	50	Variable	Ceramic bobbin 1 in. dia. \times 1 in. wires	C	"	1	
17830	Type 9271	500	5	75-90	—		C	"	—	
10497	Type 3411	500	2½	10	—		C	"	2	
17984	Type 9364	500	5	5	—		C	"	—	
15162	Type 3871	500	20	—	Variable	1,100 turns 32 S.W.G. S.W.S. Eureka	C	"	1	
8433	Type 8433	500	—	—	—	With 2 adjustable lapping clips, nickel copper winding on flat mica former	C	"	1	
16791	Type 5307	500	10	40	Wire wound		C	"	1	

RESTRICTED

RESTRICTED

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	Nomenclature	Value in Ohms	Tolerance +% unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1		3	4	5	6	7	8	9	10
903	RESISTORS—cont. Miscellaneous—cont. Ohmic values shown—cont. Type 954	500	1	—	Wire wound	Former brass rod with Symrite sleeving. 10 mA shunt; wire ends	C	each	1
10634	Type 406	500	10	—	—	3 adjustable bands and clips. Winding insulated for 1,000V. to frame, fitted with feet and end brackets, wound on tube 13¼ in. × 3 in. × 3⅞ in. 0.6 amp.	C	"	1
1393	Type 1393	500	—	—	Variable	Tubular. Single screw fixing	C	"	1
18451	Type 9435	500	2½	4-5	Wire wound	130 double turns	C	"	1
		200	2½			140 double turns			
		500	2½			300 double turns			
18475	Type 9469	1000	2½	4-5	Wire wound	Tubular, 1 screw fixing. Size ⅜ in. × 1⅞ in.	C	"	1
		2000	2½						
18477	Type 9471	500	2½	4-5	Wire wound	Tubular. Used on Panel Type 674	C	"	1
		1000	2½						
		2000	2½						
18071	Type 9543	500 + 500 Pot.	5	5	Wire wound	Potentiometer. Spindle 1 in. long, ¼ in. dia., drilled 2 holes 0.116 in. dia. at right angles	C	"	1
						Non-inductive			
17999	Type 9377	500-1,000-2,000	2½	4-5	Wire wound	WW. on asbestos former	C	"	1
15140	Type 3849	549	2½	—	Wire wound	2 amps.	C	"	1
16695	Type 5217	550	—	50	—	Tubular, 1 screw fixing. Size ⅜ in. × 1⅞ in. long.	C	"	1
10910	Type 3634	600	—	—	Wire wound		C	"	2
9931	Type 291	600	—	—	—		C	"	1
18474	Type 9468	600	2½	4-5	Wire wound	double turns	C	"	1

Issued with A/L 41 to 1.P. 1086—Book 4 (iii)

135

RESTRICTED

RESTRICTED

SECTION 10W—cont.

RADIO RESISTORS

1	2	3	4	5	6	7	8	9	10
Ref. No.	Nomenclature	Value in Ohms	Tolerance $\pm\%$ unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1									
	RESISTORS—cont. Miscellaneous—cont. Ohmic values shown—cont.								
7995	Type 7995	600	3	2	—	Moulded bobbin with brass tube centre, 1 in. dia. \times $\frac{5}{8}$ in. tags Terminals at each end. 8 in. long \times $\frac{5}{8}$ in. dia. rod. 4 B.A. Miniature	C	each	—
10968	Type 3683	600	—	—	—	Non-inductive. Bobbin $1\frac{1}{4}$ in. dia. \times $1\frac{1}{8}$ in. o/d 0.6 amp. 4 adjustable band clips, winding insulated for 1,000 V. to frame fitted with feet and end brackets, wound on tube, $13\frac{1}{4}$ in. \times $3\frac{1}{8}$ in. \times $4\frac{1}{8}$ in. high Moulded bobbin with 2 soldering tags. Dims. o/all 1 in. \times $\frac{5}{8}$ in. Bobbin	C	"	1
16908	Type 5418	680	5	—	Wire wound		C	"	1
15739	Type 4432	700	3	2	—		C	"	5
16285	Type 4905	730	—	2	Wire wound		C	"	1
6338	Type 6338	750	—	—	—		C	"	2
10635	Type 407	750	10	—	—		C	"	1
17859	Type 9300	800	2	3	Wire wound		C	"	1
9803	Type 298	800	—	—	Wire wound		C	"	2
15264	Type 3973	800	2 $\frac{1}{2}$	—	Wire wound		C	"	—
17925	Type 9409	800	1	4-5	Wire wound		C	"	—
		1,600	1				C	"	1
		3,200	1				C	"	—
		in series							
15878	Type 4561	820	10	10	Wire leads		C	"	1
17945	Type 9429	826, 922, 826, 922	—	4-5	Wire wound		C	"	—
		in series							
18459	Type 9443	826, 922, 826, 922	1	4-5	Wire wound	Tubular, single screw fixing	C	"	1
16366	Type 4955	850	5	100	Wire wound		C	"	1
252	Type 693	960	—	—	—		C	"	1

RESTRICTED

RESTRICTED

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance \pm % unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1									
6277	RESISTORS—cont. Miscellaneous—cont. Ohmic values shown—cont. Type 6277	966	—	—	—	Woven asbestos net, 26 in. \times 16 in. Fixing centres 24 in. \times 14 in. Tapped as giving 3 equal Ohm sections. 0.74 amp. continuous rating Max. loading up to 8 watts open coil. Varnished ceramic	C	each	1
7145	Type 7145	1 K	2 $\frac{1}{2}$	8	Wire wound	—	C	"	—
17001	Type —	1 K	—	20	Wire wound	—	C	"	1
1360	Type 1360	1 K	+10—15	—	—	—	C	"	1
15611	Type 4307	1 K	5	4	Wire wound	—	C	"	1
18472	Type 9466	1 K	2 $\frac{1}{2}$	4-5	Wire wound	Tubular. 242 double turns. 1 screw fixing. Size $\frac{3}{16}$ in. \times 1 $\frac{1}{4}$ in. long Mica slab Ceramic, metal ends	C	"	1
294	Type 720	1 K	—	—	—	—	C	"	1
15187	Type 3896	1 K	5	10	Wire wound	—	C	"	1
15942	Type 4623	1 K	—	40	Wire wound	—	C	"	1
10633	Type 405	1 K	10	—	—	Adjustable band clips, on ceramic tube with end caps, 7 $\frac{1}{8}$ in. \times 1 $\frac{1}{2}$ in. \times 1 $\frac{1}{2}$ in. high. 2 amps.	C	"	1
9529	Type 2781	1 K	1	5	Wire wound	—	C	"	2
15286	Type 3995	1 K	20	3	Variable	Spindle 2 $\frac{1}{2}$ in. \times $\frac{1}{4}$ in. including bush	C	"	1
6474	Type 6474	1 K	—	60	—	Centre tapped. Vitreous. End mountings, 3 terminal bands. Size 3 $\frac{1}{8}$ in. \times $\frac{7}{8}$ in. dia.	C	"	1
18481	Type 9475	1 K	—	60	Wire wound	Spindle $\frac{3}{4}$ in. \times $\frac{1}{4}$ in. slotted moulded bobbin, 1 in. dia. \times $\frac{3}{8}$ in. with brass tube centre and soldered tags	C	"	1
16029	Type 4697	1 K	20	1.5	Variable linear	—	C	"	1
7800	Type 7800	1 K	3	2	Wire wound	—	C	"	2

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance \pm % unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7	8	9	10
15661	RESISTORS—cont. Miscellaneous—cont. Ohmic values shown—cont. Type 4357	1 K	—	40	Wire wound	Power type, spindle horizontal mounting	C	each	1
7198	Type 11	1 K	—	—	Variable resist	2 flat formers. Rubbing contact	C	"	1
9150	Type 2500	1 K + 1 K	—	10	Wire wound	Variable. Dual type	A	"	1
17928	Type 9412	1 K 1 K	1	4-5	Wire wound	Tubular. $1\frac{1}{8}$ in. \times $\frac{1}{4}$ in. Single screw fixing	C	"	1
7750	Type 7750	1.074 K in series	—	120	—	230 V. dimmer. Sliding resist. with grade winding on slate former to dim load form full to blackout. 0.5 amp. Safety protected Tubular	C	"	1
17948	Type 9932	1.394 K, .317 K, 1.394 K, .317 K in series	—	4.5	Wire wound	Bakelite former Bakelite former Double tube, 1.0 amp. Cap ends	C	"	1
15543	Type 4252	1.20 K	2 $\frac{1}{2}$	2	Wire wound	Bakelite former	C	"	1
1666	Type 5191	1.2 K	2 $\frac{1}{2}$	10	Wire wound	Bakelite former	C	"	1
8665	Type 158	1.23 K	—	—	Semi-variable	Double tube, 1.0 amp.	C	"	1
1251	Type 1251	1.50 K	10	—	Wire wound	Cap ends	C	"	1
15554	Type 4263	1.5 K	2 $\frac{1}{2}$	2	Wire wound	—	C	"	1
16278	Type 4898	1.54 K	—	—	Wire wound	42 S.W.G. D.S.C. Eureka wire	C	"	1
17819	Type 9260	1.6 K + 1 K + 1 K	—	50	—	Vit. embedded with wire ends. 3 $\frac{1}{4}$ in. \times $\frac{1}{8}$ in. dia. Tubular, 1 screw fixing	C	"	—
18452	Type 9436	1.6 K	2 $\frac{1}{2}$	405	Wire wound	3 $\frac{1}{4}$ in. \times $\frac{1}{8}$ in. dia. Tubular, 1 screw fixing	C	"	1
16272	Type 4892	1.70 K	—	—	Wire wound	42 S.W.G. D.S.C. Eureka wire	C	"	1
9340	Type 2791	1.75 K	15	7	Carbon rod	Heavy duty	C	"	1
9135	Type 232	1.79 K	—	—	Wire wound variable	8 steps	C	"	1
15265	Type 3974	1.8 K	2 $\frac{1}{2}$	—	Wire wound	On bakelite bobbin 0.95 in. \times 0.62 in.	C	"	1
16348	Type 4938	1.8 K	20	6	Wire wound	Miniature	C	"	1

SECTION 10W—*cont.*

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ±% unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.	
1										
	RESISTORS—<i>cont.</i>									
	Miscellaneous—<i>cont.</i>									
	Ohmic values shown—<i>cont.</i>									
15201	Type 3910	1.8 K	5	35	Wire wound		C	each	1	
7561	Type 7561	1.9 K	—	30	Wire wound	1 $\frac{3}{8}$ in. dia. former and stud fixing, side tag connections. 9 $\frac{1}{2}$ in. total length. Special	C	"	1	
16273	Type 4893	1.97 K	—	30	Wire wound	42 S.W.G. D.S.C. Eureka wire WW. on mica base with floaten band	C	"	1	
15109	Type 3818	2 K	—	30	—	Cartridge type, 10 watts Bakelite bobbin, 0.95 in. × 0.62 in.	C	"	2	
8690	Type 166	2 K	2 $\frac{1}{2}$	—	Wire wound	Glass tube, enclosed metallised rod	C	"	1	
15263	Type 3972	2 K	—	—	Wire wound	36 S.W.G. D.W.S. Eureka Ceramic former. Metal ends	C	"	1	
1326	Type 1326	2 K	—	—	—	$\frac{1}{8}$ in. × $\frac{1}{4}$ in. inc. bush, slotted Mica slab	C	"	1	
8434	Type 8434	2 K	—	—	—	Mica base with floaten band	C	"	1	
7977	Type 7977	2 K	5	10	Wire wound	Porcelain former	C	"	1	
198	Type 666	2 K	—	10	Wire wound.	Insulation ceramic former, wire ends—tropical	C	"	1	
16445	Type 5023	2 K	10	1	Wire wound.	0.015 amp. Adjustable band clips; wound on tube 4 $\frac{1}{8}$ in. × $\frac{1}{8}$ in. × 1 $\frac{3}{8}$ in.	C	"	1	
293	Type 719	2 K	—	150	—	—	C	"	1	
15000	Type 3709	2 K	—	20	Wire wound	—	C	"	1	
687	Type 871	2 K	10	20	Wire wound.	—	C	"	1	
6305	Type 6305	2 K	—	10	Wire wound	—	C	"	1	
10990	Type 3700	2 K	2 $\frac{1}{2}$	10	Wire wound	—	C	"	2	
10682	Type 415	2 K	10	45	—	—	C	"	1	
9416	Type 262	2 K	—	30	Variable	Graphite. 1 watt. 1 $\frac{1}{8}$ in. × $\frac{1}{4}$ in. dia.	C	"	1	
9260	Type 2587	2 K	20	—	—	—	C	"	1	
16572	Type 5139	2.2 K	5	—	Wire wound	—	C	"	1	
15592	Type 4297	2.2 K	5	7.5	Wire wound	—	C	"	1	

RESTRICTED

RESTRICTED

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ±% unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Qty. in Carton
1									
	RESISTORS—cont. Miscellaneous—cont. Ohmic values shown—cont.								
16504	Type 5074	2.35 K	5	150	Wire wound	Ferrules	C	each	1
8663	Type 156	2.35 K	—	12	Semi-variable	Single tube. 0.3 amp.	C	"	1
15449	Type 4158	2.35 K	5	25	Wire wound	Miniature	C	"	1
15202	Type 3911	2.4 K	5		Wire wound	1 1/2 in. dia. Ceramic former. End stud fixing, side tag connections. 9 1/2 in. total length.	C	"	1
						Special			
10665	Type 413	2.5 K	10	—	—	0.01 am. Adjustable band clip.	C	"	1
6448	Type 6448	2.5 K	20	—	—	4 1/2 in. × 7/8 in. × 1 1/2 in.	C	"	1
204	Type 672	2.5 K	—	10	Pot	Spindle 1 1/8 in. Hat	C	"	1
10977	Type 3689	2.5 K	10	10	Wire wound		C	"	1
17865	Type 9306	2.5 K	5	5	Wire wound.		C	"	1
						Pot			
17979	Type 9359	2.5 K	5	5	Wire wound.	Spindle 1 1/8 in. long, drilled 2 holes 0.113 in. at right angles; 1 at 3/8 in. from end, the other 1/8 in. from end	C	"	1
15544	Type 4253	2.5 K	2 1/2	2	Wire wound.	Slotted spindle, 5/8 in. long	C	"	2
177	Type 645	2.5 K	(+10—15)	5	—	Bakelite former	C	"	2
9169	Type 239	2.5 K	—	50	Vitreous	Non-insulated rod	C	"	1
15549	Type 4258	2.565 K	10	—	Wire wound		C	"	2
		(2,500 + 50 + 15)							
18453	Type 9437	2.5 K	2 1/2	4-5	Wire wound	Ceramic former 0.718 in. dia. × 1.718 in., with tags	C	"	1
		1.5 K	2 1/2			Tubular, single screw fixing			
1182	Type 1182	2.6 K	—	100	—		C	"	1
17947	Type 9431	2.650 K, .143 K, 2.650 K, .143 K in series	—	4.5	Wire wound	Tubular	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	Nomenclature	Value in Ohms	Tolerance ±% unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1									10
18461	RESISTORS—cont. Miscellaneous—cont. Ohmic values shown—cont. Type 9445	2.65 K, .143 K, 2.65 K, .143 K in series	1	4-5	Wire wound	Tubular. Single screw fixing	C	each	1
6278	Type 6278	2.69 K	—	—	—	0-041 amp. continuous rating; woven asbestos mat, 26 in. × 16 in. Fixing centres 26 in. × 16 in. 5 tapings giving 4 equal ohmic sections	C	"	1
10516	Type 3420	3 K	2½	2	Wire wound	Bakelite former, tap connections, 1 in. × ¾ in. 12 tags giving 4 equal ohmic sections	C	"	2
18478	Type 9472	3 K	2½	4-5	Wire wound	Tubular	C	"	1
15436	Type 4145	3 K	5	7	Wire wound	Miniature	C	"	1
7933	Type 7933	3 K	5	—	Wire wound	—	C	"	1
9192	Type 2524	3 K	—	—	Variable	—	C	"	1
15316	Type 4025	3 K	10	7.5	Wire wound	Miniature Ferrules	C	"	1
16700	Type 5222	3.36 K	5	100	Wire wound	"Keramot" former. Meter resistance	C	"	2
15891	Type 4572	3.44 K	—	—	Wire wound	—	C	"	1
16437	Type 5015	3.5 K	5	12	Wire wound	Miniature	C	"	1
15818	Type 4501	3.5 K	5	25	Wire wound	Pigtails (with taps)	C	"	1
9828	Type 315	3.5 K	—	—	Variable	—	C	"	1
16983	Type 5492	3.6 K	—	50	Carbon rod	Required for laboratory equipment	C	"	—
16771	Type 5238	3.9 K	2-5	10	Wire wound	—	C	"	1
18006	Type 9384	3.9 K	5	2½	Wire wound	Fixed	C	"	1
17861	Type 9302	4 K	2	3	Wire wound	Tubular, 1 ⅜ in. × ¾ in., single screw fixing	C	"	1
17933	Type 9417	4 K	1	4.5	Wire wound	—	C	"	1

RESTRICTED

RESTRICTED

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance \pm % unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1									10
	RESISTORS—cont. Miscellaneous—cont. Ohmic values shown—cont.								
18470	Type 9464	4 K	2½	4-5	Wire wound	Tubular, 490 double turns, ¾ in. dia. × 1½ in. long Non-vitreous protected	C	each	1
16487	Type 5058	4 K	5	1	Wire wound	On ceramic former. Non-vitreous coating	C	"	5
16657	Type 4264	4 K	10	4	Wire wound	Miniature 1½ in. × ¾ in. metal clamps, mica slab	C	"	1
6814	Type 6814	4 K	10	12	—	Semi-variable between 2,000-4,000 by adjustable band, with terminal	C	"	1
16218	Type 4845	4 K	15	12	Wire wound	Complete with knob graded 4-1 rate of charge, fully anti-clockwise when viewed from knob end	C	"	1
292	Type 718	4 K	—	4-5	Wire wound		C	"	1
16361	Type 4951	4 K	—	10	Wire wound		C	"	1
17992	Type 9370	4 K	10	—	Pot ¾ in. standard		C	"	—
17927	Type 9411	4 K, 4 K in series	1 : 1	4-5	Wire wound	Tubular. 1½ in. × ¾ in. Single screw fixing	C	"	1
17949	Type 9433	4.5 K	2½	4-5	Wire wound	Tubular, 1½ in. long × ¾ in. dia., single screw fixing	C	"	1
15321	Type 4030	4.7 K	10	20	Wire wound	Pigtails	C	"	1
16047	Type 4715	4.7 K	10	12	Wire wound	Miniature	C	"	1
16816	Type 5331	4.7 K	5	5	Wire wound	Miniature	C	"	1
17028	Type —	4.7 K	10	—	—	—	C	"	1
6387	Type 6387	5 K	—	—	Variable	—	C	"	1
15772	Type 4457	5 K	5	10-20	Wire wound	A static winding (for testing cathode ray tube)	C	"	1
15159	Type 3868	5 K	20	—	Variable	Linear, no switch. Spindle ½ in. × ¼ in. dia.	C	"	1

RESTRICTED

RESTRICTED

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance \pm % unless otherwise stated	Wattage	Type	Details	Class of Store	Denom of Qty.	Carton Unit Qty.
1									
15968	RESISTORS—cont. Miscellaneous—cont. Ohmic values shown—cont. Type 4649	5 K over 3° of Track	—	—	Wire wound	Plain Specially wound, Spindle $\frac{1}{8}$ in.	C	each	1
10515	Type 3419	5 K	2½	2	Wire wound	Insulated on moulded bakelite former, tap connectors, 1 in. \times $\frac{3}{8}$ in. moulded bobbin. 2 tags Coil type with ceramic bobbin, 1 in. \times 1 in. dia. Pigtails Tubular caps 1 amp. $7\frac{1}{4}$ in. \times 5 in. \times 2 in. high $2\frac{1}{2}$ in. long $7\frac{5}{8}$ \times 10 mm., ends coppered Spindle $\frac{1}{8}$ in. slotted. Inverse log Linearity is 10 parts in 9,000; and trimmer suitable for gauging by $\frac{1}{8}$ in. shaft, extending 1 in. at rear Control Miniature Tubular. Single screw fixing	C	"	1
15703	Type 4398	5 K	2½	8	Wire wound		C	"	1
15330	Type 4039	5 K	5	—	Wire wound		C	"	1
1277	Type 1277	5 K	—	—	Wire wound		C	"	1
10768	Type 421	5 K	+10—10	—	—		C	"	1
9935	Type 295	5 K	—	—	Cartridge		C	"	2
9340	Type 2641	5 K	15	—	—		C	"	2
18054	Type 9526	5 K Pot.	15	2	—		C	"	1
16225	Type 4851	5 K	10	5	Variable linear		C	"	1
8865	Type 2294	5 K	—	10	Wire wound	Control	C	"	2
15771	Type 4456	5.1 K	5	12	Wire wound	Miniature	C	"	—
18462	Type 9446	5.235 K, 69.7, 5.235 K, 69.7	1	4-5	Wire wound	Tubular. Single screw fixing	C	"	1
18463	Type 9447	5.8 K, .628 K, 5.8 K, .628 K in series	2½	4-5	Wire wound	Tubular. Single screw fixing	C	"	1
15404	Type 4113	6 K	3	2	G.P.O.		C	"	—
206	Type 674	6 K	—	—	Wire wound. Pot	Moulded bobbin, brass centre tube, 2 tags, 1 in. dia. \times $\frac{3}{8}$ in.	C	"	1
16557	Type 5127	6.3 K	5	—	Wire wound	Ferrules	C	"	1
16414	Type 4994	6.5 K	5	12	Wire wound	Miniature	C	"	1

RESTRICTED

RESTRICTED

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance $\pm\%$ unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1									
	RESISTORS—cont. Miscellaneous—cont. Ohmic values shown—cont.								
16274	Type 4894	8 K	— 3	— 2	Wire wound	Eureka wire, 46 S.W.G., D.S.C. Moulded bobbin with 2 soldering tags, O/all dims. 1 in. \times $\frac{1}{8}$ in. Pigtails	C	each	1
18042	Type 9514	8 K	— 3	— 2	—	Tubular Adjustable band clips and caps Miniature Spindle $\frac{1}{16}$ in., tapped at 4 B.A. 0-1 amp. 5 in. long Spindle $\frac{1}{8}$ in. \times $\frac{1}{4}$ in. dia. Tubular	C	"	1
15817	Type 4500	9 K	5	5	Wire wound		C	"	1
12935	Type 9419	9 K	5	4.5	Wire wound		C	"	1
10632	Type 404	10 K	10	—	—		C	"	1
16456	Type 5034	10 K	10	12	Wire wound		C	"	1
7054	Type 7054	10 K	2	—	Variable Vitreous		C	"	1
9932	Type 292	10 K	—	—	Variable		C	"	1
15160	Type 3869	10 K	20	—	Wire wound		C	"	1
18454	Type 9438	10 K	1	4.5	Cartridge		C	"	1
9168	Type 238	10 K	—	10	Variable		C	"	2
15188	Type 3897	10 K	—	15-20	Wire wound	Spindle $\frac{1}{8}$ in. \times $\frac{1}{4}$ in. dia., plain Vitreous enamel	C	"	1
7560	Type 7560	10 K	—	30	Wire wound anode	Feed resistance. Cylindrical	C	"	1
8057	Type 119	10 K	—	—	Wire wound	Tubular	C	"	1
17946	Type 9430	10 K	—	4.5	Wire wound		C	"	—
		10-450 K, 346 K, 10-450 K, 346 K							
		in series							
18460	Type 9444	10-45 K, 34.6, 10-45 K, 34.6	1	4-5	Wire wound	Tubular. Single screw fixing	C	"	1
		in series							
10584	Type 3462	12 K	—	—	Ball contact. Pot	Variable input with dial graduated 0-40 Ferrules	C	"	1
		12 K							
15631	Type 4240	12 K	20	15	Wire wound		C	"	1
16688	Type 5211	12.8 K	24	—	Wire wound		C	"	1
16279	Type 4899	14 K	—	—	Wire wound	Nickel chrome, 51 S.W.G.	C	"	1
7503	Type 7503	15 K	5	10	Wire wound	Ceramic former, metal ends	C	"	1
15250	Type 3959	15 K	10	20	Wire wound	Pigtails	C	"	1
17937	Type 9421	15 K	4	—	—	Nichram. Capped ends	C	"	1
9321	Type 2628	15 K	—	—	—	—	C	"	1

RESTRICTED

RESTRICTED

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	Nomenclature	Value in Ohms	Tolerance ±% unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Qty. Carton Unit
1									
18322	RESISTORS—cont. Miscellaneous—cont. Ohmic values shown—cont. Type 4031	15 K	10	20	Wire wound	Pigtails Shunt for A.C. voltmeter, 0-300 V.	C	each	1
7886	Type 7886	16 K	$\frac{1}{2}$	—	—	Fixed. Moulded bobbin with 2 soldering tags. Dims. overall 1 in. × $\frac{1}{8}$ in.	C	"	1
17860	Type 9301	16 K	2	3	Wire wound	Carbon filament wound rod. Slotted pin. Non-insulated. 2 in. × $\frac{1}{16}$ in. Terminal tags	C	"	—
10070	Type 351	17 K	4	2	—	Moulded bobbin with 3 soldering tags. Dims. overall 1 in. × $\frac{3}{8}$ in. Moulded bobbin, 1 in. dia. × $\frac{3}{8}$ in. Cartridge type, 10 watts 0-05 amp. Wire leads	C	"	2
1681	Type 1681	17 K	—	100	—	Spindle $\frac{1}{4}$ in. × $\frac{1}{8}$ in. slotted	C	"	1
17857	Type 9298	20 K	2	3	Wire wound, fixed	Linear. Spindle 1 $\frac{1}{16}$ in. Tubular. 1 $\frac{1}{16}$ in. × $\frac{3}{16}$ in. dia. Single screw fixing	C	"	1
15811	Type 4494	20 K	2 $\frac{1}{2}$	2	Wire wound	Spindle $\frac{1}{8}$ in. × $\frac{1}{4}$ in., slotted	C	"	1
8691	Type 167	20 K	—	—	Wire wound	Spindle $\frac{3}{8}$ in., slotted	C	"	1
9349	Type 249	20 K	—	—	Wire wound	Spindle $\frac{1}{4}$ in., slotted	C	"	1
16210	Type 4838	20 K	10	10-20	Wire wound	Spindle $\frac{1}{4}$ in. × $\frac{1}{2}$ in., plain	C	"	1
16400	Type 4981	20 K	20	1 $\frac{1}{2}$	Variable	Spindle $\frac{1}{4}$ in. × $\frac{1}{2}$ in., slotted	C	"	1
9726	Type 278	20 K	—	—	Variable	Spindle $\frac{1}{8}$ in. free length (slotted)	C	"	1
15314	Type 4023	20 K	5	5	Variable, plain	Tubular. 1 $\frac{1}{16}$ in. × $\frac{3}{16}$ in. dia. Single screw fixing	C	"	1
17929	Type 9413	20 K	1	4-5	Wire wound	Spindle $\frac{1}{8}$ in. × $\frac{1}{4}$ in., slotted	C	"	1
16439	Type 5017	20 K	10	25	Variable, linear	Spindle $\frac{1}{8}$ in., slotted	C	"	1
6264	Type 6264	20 K	—	—	Variable	Spindle $\frac{1}{8}$ in., slotted	C	"	1
6265	Type 6265	20 K	—	—	Variable	Spindle $\frac{1}{8}$ in., slotted	C	"	1
11616	Type 489	20 K	—	—	Variable	Spindle $\frac{1}{4}$ in. × $\frac{1}{2}$ in., plain	C	"	1
15183	Type 3892	20 K	—	—	Variable	Spindle $\frac{1}{4}$ in. × $\frac{1}{2}$ in., slotted	C	"	1
17848	Type 9289	25 K	5	5	Wire wound. Pot	Spindle $\frac{1}{8}$ in. free length (slotted)	C	"	1
17771	Type 9216	25 K	20	1.5	Carbon, variable	Tubular. 1 $\frac{1}{16}$ in. × $\frac{3}{16}$ in. dia. Single screw fixing	A	"	1
16251	Type 4876	25 K	20	2	Wire wound	Spindle $\frac{1}{8}$ in. × $\frac{1}{4}$ in., slotted	C	"	1
6385	Type 6385	25 K	—	—	—	Spindle 1 $\frac{1}{8}$ in. flat. Log grading	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

1	2	3	4	5	6	7	8	9	10
Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance \pm % unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
	RESISTORS—cont.								
	Miscellaneous—cont.								
	Ohmic values shown—cont.								
16275	Type 4895	30 K	—	—	Wire wound	Nickel chrome, 40 S.W.G. D.S.C.	C	each	1
17536	Type 5991	30 K	20	2	Variable	Spindle $1\frac{1}{4}$ in. \times $\frac{1}{2}$ in., plain	C	"	1
16440	Type 5018	30 K	5	5	Variable, linear	Spindle $\frac{7}{8}$ in. \times $\frac{1}{4}$ in., plain	C	"	1
2998	Type 19	30 K	—	—	Wire wound	Tapping socket panel and plug	C	"	1
15514	Type 4223	30 K	5	15	Wire wound	Vitreous. Pigtails	C	"	1
1394	Type 1394	30 K	—	—	Variable	—	C	"	1
8689	Type 165	30 K	—	—	Wire wound	Cartridge type, 10 watts	C	"	1
16226	Type 4852	33 K	10	10-20	Wire wound	Wire leads	C	"	1
10949	Type 3664	40 K	10	40	Wire wound	—	C	"	1
7958	Type 7958	40 K	5	50	Wire wound	Ceramic former	C	"	1
9933	Type 293	40 K	—	—	Vitreous	0.055 amp., 10 in. long	C	"	1
15551	Type 4260	45 K	5	7.5	Wire wound	Miniature	C	"	1
15507	Type 4216	47 K	20	2	Wire wound	—	C	"	2
10904	Type 3630	50 K	—	—	Wire wound	Igranic baseboard. Porcelain former. Spindle 5359/2 fitted by re-diffusion	C	"	1
16276	Type 4896	50 K	—	—	Wire wound	Nickel chrome, 40 S.W.G. D.S.C.	C	"	1
16743	Type 9094	50 K	1	1	Wire wound	—	C	"	1
7260	Type 7260	50 K	20	—	—	Spindle $1\frac{1}{8}$ in. flat	C	"	1
9505	Type 253	50 K	—	—	Pot	Graphite	C	"	1
1383	Type 1383	50 K	5	10	Wire wound	Ceramic former, metal ends	C	"	1
9506	Type 254	50 K	—	—	Wire wound.	—	C	"	1
15288	Type 3997	50 K	20	2	Variable	Spindle $2\frac{1}{2}$ in. \times $\frac{1}{4}$ in.	C	"	1
9738	Type 288	50 K	—	—	Pot	—	C	"	1
15773	Type 4458	50 K	20	1 $\frac{1}{2}$	Variable, linear	Spindle $\frac{11}{16}$ in. \times $\frac{1}{4}$ in. (standard)	C	"	1
15252	Type 3961	50 K	2 $\frac{1}{2}$	—	Wire wound	Bakelite bobbin, 0.95 in. \times 0.62 in.	C	"	2
1395	Type 1395	50 K	—	—	Variable	—	C	"	1
17813	Type 9256	50 K	10	10	—	Spindle $\frac{3}{4}$ in. long \times $\frac{1}{4}$ in. dia. Plain, fitted with metal rear	C	"	—

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Value in Ohms	Tolerance ±% unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7	8	9	10
1683	RESISTORS—cont. Miscellaneous—cont. Ohmic values shown—cont. Type 1683	50 K	—	18	—	—	C	each	2
1168	Type 1168	50 K	—	200	Wire wound	Non-vitreous, protected	C	"	—
7211	Type 7211	51 K	10	6	Wire wound	—	C	"	—
17016	Type —	51 K	2	$\frac{1}{2}$	Carbon film	High stability	C	"	—
6600	Type 6600	51 K	2	$\frac{1}{2}$	Wire wound	Nickel chrome 40 S.W.G. D.S.C.	C	"	—
16277	Type 4897	60 K	—	—	Wire wound	Miniature	C	"	—
16564	Type 5132	62 K	7	5	Wire wound	Carbon	C	"	—
8413	Type 8413	80 K	10	$\frac{1}{2}$	—	Rod type grid lead, 1 $\frac{1}{2}$ in.	C	"	—
7278	Type 28 . .	80 K	—	1	—	Miniature	C	"	—
15315	Type 4024	90 K	10	7.5	Wire wound	—	C	"	—
1579	Type 1579	90 K	1	$\frac{1}{2}$	—	Metallised filament, consolidated	C	"	—
9492	Type 2747	100 K	20	$\frac{1}{2}$	—	Cartridge	C	"	10
17889	Type 9330	100 K	1	10	Wire wound	Spindle 2 $\frac{1}{2}$ in. × $\frac{1}{4}$ in.	C	"	—
15289	Type 3998	100 K	20	2	Variable Cartridge	2 $\frac{1}{2}$ in. long	C	"	—
9930	Type 290	100 K	—	—	—	Special high precision linear 70 ± .03	C	"	2
16800	Type 5316	100 K	—	15	—	Ceramic former, metal ends	C	"	1
1414	Type 1414	100 K	5	10	Wire wound	Miniature	C	"	—
16818	Type 5333	100 K	5	5	Wire wound	—	C	"	—
1576	Type 1576	100 K	—	—	Pot. Variable	—	C	"	—
16269	Type 4889	148 K	—	—	Wire wound	—	C	"	—
15983	Type 4660	150 K	5	52.8	Wire wound	6 $\frac{1}{4}$ in. Fixing centre 1 $\frac{1}{4}$ in. o/d	C	"	—
16280	Type 4900	160 K	—	—	Wire wound	—	C	"	—
16266	Type 4886	160 K	—	—	Wire wound	Potentiometer 100 ohms, $\frac{1}{2}$ watt	C	"	—
11104	Type 449	200 K	10	—	—	—	C	"	—
15336	Type 4045	200 K	2	—	Wire wound	—	C	"	—
16281	Type 4901	220 K	—	—	Wire wound	Nickel chrome, 51 S.W.G.	C	"	—
18506	Type 9573	220 K	5	$\frac{1}{2}$	Fixed Composition, Grade 1	Silicon varnished. Army Ref. ZA37529	C	"	—
15290	Type 3999	250 K	20	2	Variable	Spindle 2 $\frac{1}{2}$ in. × $\frac{1}{4}$ in. including bush	C	"	1

RESTRICTED

SECTION 10W—cont.

RADIO RESISTORS

1	2	3	4	5	6	7	8	9	10
Ref. No.	Nomenclature	Value in Ohms	Tolerance \pm % unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1									
	RESISTORS—cont.								
	Miscellaneous—cont.								
	Ohmic values shown—cont.								
15218	Type 3927	250 K	—	1½	Variable, linear	Spindle 7/8 in. × 1/4 in., plain	C	each	1
7263	Type 7263	250 K	20	—	—	Spindle 1 1/8 in., plain	C	"	1
7825	Type 90 . . .	250 K	—	—	Variable	Variable potentiometer	C	"	1
15163	Type 3872	250 K	20	—	Variable	Spindle 1 1/8 in. × 1/4 in. dia.	C	"	1
6174	Type 6174	250 K	—	—	Variable	Spindle 1 1/8 in.	C	"	1
16270	Type 4890	298 K	—	—	Wire wound	—	C	"	1
6162	Type 6162	300 K	+0-5	1	Carbon rod	Special	C	"	5
8414	Type 8414	330 K	10	—	Carbon rod	Protected	C	"	5
18507	Type 9574	330 K	1	1/2	Fixed Composition, Grade 1	Silicon varnished	C	"	1
18508	Type 9575	350 K	5	1/2	Fixed Composition, Grade 1	Silicon varnished. Army Ref. ZA37513	C	"	1
18499	Type 9566	390 K	1	1/2	Fixed Composition, Grade 1	Silicon varnished	C	"	1
18510	Type 9577	470 K	5	1/2	Fixed Composition, Grade 1	Silicon varnished. Army Ref. ZA37513	C	"	1
16472	Type 6045	490 K	1	—	Wire wound	—	C	"	1
100	Type 572	500 K	—	—	Variable	Vol. control	C	"	1
7295	Type 40	500 K	—	—	Variable	Non-inductive graphic tube resistance, Centralab type	C	"	1
18502	Type 9569	510 K	1	1/2	Fixed Composition, Grade 1	Silicon varnished	C	"	1
18503	Type 9570	560 K	5	1/2	Fixed Composition, Grade 1	Silicon varnished	C	"	1
18511	Type 9578	620 K	5	1/2	Fixed Composition, Grade 1	Silicon varnished. Army Ref. ZA37518	C	"	1
7149	Type 7149	635 K	2½	1/2	Fixed Composition, Grade 1	Metallised ceramic rod, metal caps	C	"	5
16267	Type 4887	640 K	—	—	Wire wound	Comprises set of 3 resistors	C	"	1

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	Nomenclature	Value in Ohms	Tolerance \pm % unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. Qty.	Carton Unit Qty.	
1										
	RESISTORS—cont.									
	Miscellaneous—cont.									
	Ohmic values shown—cont.									
18500	Type 9567	650 K	1	$\frac{1}{2}$	Fixed Composition, Grade 1	Silicon varnished	C	each	1	
18501	Type 9568	680 K	1	$\frac{1}{2}$	Fixed Composition, Grade 1	Silicon varnished	C	"	1	
15024	Type 3733	700 K	—	—	Fixed Composition, Grade 1	Meter resistance, complete with baseplate and mounting brackets	C	"	1	
8005	Type 8005	(450 + 450) 900 K	1	—	Meter shunt	Silicon varnished	C	"	1	
18504	Type 9571	1 M	1	$\frac{1}{2}$	Fixed Composition, Grade 1	Silicon varnished	C	"	1	
18512	Type 9579	1 M	5	$\frac{1}{2}$	Fixed Composition, Grade 1	Silicon varnished. Army Ref. ZA37519	C	"	1	
15523	Type 4232	1 M	20	$1\frac{1}{2}$	Linear variable	Spindle $1\frac{1}{2}$ in. \times $\frac{1}{2}$ in., plain	C	"	1	
16606	Type 3166	1 M	20	$1\frac{1}{2}$	Linear variable	Spindle 1 in., slotted	C	"	1	
6060	Type 6060	1 M	—	—	—	Spindle flat	C	"	1	
6259	Type 6259	1 M	—	—	—	Spindle flat	C	"	1	
16420	Type 4999	1 M	5	25	Variable Special W.W.	Overall dims. $4\frac{1}{2}$ in. \times $4\frac{1}{2}$ in. \times $2\frac{1}{2}$ in. main body $4\frac{1}{2}$ in. dia. \times $1\frac{1}{2}$ in. Wiper can be lifted from track magnetically	C	"	1	
2526	Type 27	2 M	—	—	—	Grid leak rod $4\frac{1}{2}$ in. Comprising 40 C.M.S. 30 S.W.G. D.S.C. copper $\frac{1}{8}$ in. dia.	C	"	1	
8210	Type 8210	2 M	—	$\frac{1}{2}$	Wire wound	Tubular ceramic, wire wound.	C	"	—	
16790	Type 5306	2 M	10	500	Wire wound	Element $4\frac{1}{2}$ in. long \times $\frac{1}{2}$ in. o/d	C	"	1	
15292	Type 4001	2 M	20	2	Variable	Spindle $2\frac{1}{2}$ in. \times $\frac{1}{2}$ in.	C	"	1	
18505	Type 9572	2-4 M	1	$\frac{1}{2}$	Fixed Composition, Grade 1	Silicon varnished	C	"	1	
6306	Type 6306	3 M	15	10	—	10,000 V. D.C. max.	C	"	1	
16216	Type 4843	5 M	15	50	Wire wound	Ceramic tube	C	"	1	
1763	Type 1763	5 M	20	—	—	Spindle flat	C	"	1	

SECTION 10W—*cont.*

RADIO RESISTORS

Ref. No.	Nomenclature	Value in Ohms	Tolerance \pm % unless otherwise stated	Wattage	Type	Details	Class of Store	Denom. of Qty.	Carton Unit Qty.
1									
	RESISTORS—<i>cont.</i> Miscellaneous—<i>cont.</i> Ohmic values shown—<i>cont.</i>								
16367	Type 4956	—	—	—	—	Filament regulating. Wound Eureka wire for 6.3 V. on insulating boards, $2\frac{1}{8}$ in. \times 2 in. \times $\frac{1}{4}$ in. Discriminating Atomic. Spark quench, $\frac{3}{32}$ in. dia. \times $\frac{1}{8}$ in. thick 50 volts, 1,000 w. Heating element	C	each	1
16159	Type 4806	—	—	—	—	Variable resistor W.W. motor driven back of panel mounting of 20 %.	C	"	5
16618	Type 5177	—	—	—	—	Rheostat with hand-wheel	C	"	1
15082	Type 3791	—	—	—	—		C	"	5

SECTION 10W—cont.

RADIO RESISTORS

Ref. No.	NOMENCLATURE	Description	Class of Store.	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6
	RESISTORS—cont.				
	Miscellaneous—cont.				
	Ohmic values not shown :—				
7509	Type 7509	C	each	—
9322	Type 2629	C	"	1
1979	Type 1979	C	"	1
9338	Type 2639	C	"	5
15166	Type 3875	C	"	3
15167	Type 3876	C	"	3
15168	Type 3877	C	"	1
7689	Type 7689	C	"	2
7691	Type 7691	C	"	1
1542	Type 1542	C	"	2
1327	Type 1327	C	"	2
1314	Type 1314	C	"	1
598	Type 833	C	"	1
1640	Type 1640	C	"	1
1641	Type 1641	C	"	1
10356	Type 381	C	"	1
16265	Type —	C	"	2
16434	Type —	C	"	10
15084	Type 3793	C	"	5
17473	Type 5928	C	"	1
		Carbon rod. ± 5% 1 W. Experimental purposes			
		Atruite disc, ¾ in. dia. × 0-04 in. thick. 2 Tags. 50 V. working			
		Atruite disc 1½ in. dia. × 0-03 in. thick between 1 and 3 mA passed at 25 V. Ratio of currents at 50 V. and 25 V. 16 : 1 min.			
		Atruite disc 450. Silico carbon compound. 1 in. dia. × ½ in. thick between 1-2 and 3-6 mA passed at 150 V. and 100 V. 5 : 1 min.			
		Atruite disc 330. Silico carbon compound. 1 in. dia. × 0-09 in. thick between 1-2 and 3-6 mA passed at 70 V. Ratio of currents passed 100 V. and 70 V. C : 1 min.			
		Special. Wire wound, ceramic former. 1½ in. dia. × 2¼ in. 9 turns. . . .			
		Special. Wire wound, ceramic former. 1½ in. × 1½ in. elliptical × 2¼ in. 13 turns			
		Metrosil surge suppressor			
		Metrosil rod. 1¼ in. × ¼ in. × ¼ in. . . .			
		Metrosil disc. 1 in. dia. × ¾ in. . . .			
		Calibrated with voltmeter, Type D. Meter shunt			
		Ballast for switch, magnetic relay, Type C			
		Ballast for switch, magnetic relay, Type C			
		Aerial load resistance, including 8 resistances, Type 32, and four insulators, Type 12			
		Bobbin resistance			
		Clamp resistance			
		Ballast rheostat, back of panel mounting with slider bar and slider adjustment.			
		Variable			

RESTRICTED

152

RADIO RESISTORS

SECTION 10W—cont.

Ref. No.	NOMENCLATURE	DETAIL	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6
	RESISTOR CONDENSER UNITS :—				
644	Type 3	C	each	1
890	Type 3	C	"	1
2021	Type 12	Bakelite panel	C	"	1
2198	Type 30	Insulation plate assembly	C	"	1
2216	Type 33	Insulation plate	C	"	1
2217	Type 34	Bakelite panel assembly	C	"	1
2212	Type 35	Bakelite plate fitted with resistor and capacitor.	C	"	1
2597	Type 47	Bakelite panel fitted with capacitors : 2—T939, 4—T939, 4—T761, 1—T940, 2—T766. 1 resistor T641 and 1 resistor T1470.	C	"	1
2731	Type 51	Bakelite panel	C	"	1
2734	Type 54	Bakelite panel	C	"	1
2756	Type 62	29-way (resistances and condensers) assembled on bakelite plate.	C	"	1
2757	Type 63	14-way (resistances and condensers) assembled on bakelite plate.	C	"	1
2836	Type 66	C	"	1
2837	Type 67	C	"	1
2739	Type 75	17-way resistor assembly	A	"	1
2741	Type 77	14-way resistor assembly	C	"	1
3016	Type 87	C	"	1
2769	Type 100	C	"	1
2770	Type 101	Bakelite panel	C	"	1
3367	Type 102	2 in. × 1.75 in. bakelite panel ..	C	"	1
3372	Type 107	C	"	1
3627	Type 108	Bakelite panel, 4 $\frac{3}{8}$ in. × 2 $\frac{5}{8}$ in. × $\frac{1}{8}$ in. ; has 6 holes for wiring.	C	"	1
3744	Type 111	Paxolin panel, 5 $\frac{1}{4}$ in. × 2 $\frac{1}{8}$ in. × $\frac{1}{8}$ in.	C	"	1
3748	Type 112	Paxolin panel, $\frac{1}{8}$ in. × 2 $\frac{1}{4}$ in. × 2 in.	C	"	1
3749	Type 113	S.R.B.P. panel, 2.25 in. × 2 in. × 0.06 in., fitted with 4 resistances, 1 meg. ± 5 per cent., $\frac{1}{4}$ watt, specially selected (bridge network). In case of breakdown, complete unit, 10/W 3749, to be changed.	C	"	1
3750	Type 114	Paxolin panel, $\frac{1}{8}$ in. × 2 $\frac{1}{4}$ in. × 2 in.	C	"	1
3751	Type 115	Paxolin panel, $\frac{1}{8}$ in. × 2 $\frac{1}{4}$ in. × 2 in.	C	"	1
3752	Type 116	Paxolin panel, $\frac{1}{8}$ in. × 2 $\frac{1}{4}$ in. × 2 in.	C	"	1
4055	Type 121	$\frac{1}{8}$ in. thick bakelite panel and tags	C	"	1
4058	Type 124	$\frac{1}{8}$ in. thick bakelite panel and tags	C	"	1
4060	Type 126	Smoothing and filter unit for power supply of T.1451.	C	"	1
4127	Type 127	Tufnol board, 7 $\frac{1}{2}$ in. × 2 $\frac{1}{4}$ in. × 2 mm. (Drg. B.15288.)	C	"	1
4128	Type 128	C	"	1
4129	Type 129	$\frac{1}{8}$ in. thick bakelite panel and tags, L.H.	C	"	1
4130	Type 130	As Type 129, but R.H.	C	"	1
4311	Type 131	Bakelite panel, $\frac{1}{8}$ in. thick, 36 tags	C	"	1
4312	Type 132	C	"	1
4513	Type 133	Paxolin panel	C	"	1
4514	Type 134	Tufnol panel, $\frac{1}{8}$ in. thick	C	"	1
4515	Type 135	Tufnol panel fitted with capacitors ..	C	"	1
4660	Type 137	Tufnol panel, $\frac{1}{8}$ in. thick	C	"	1
4661	Type 138	Tufnol panel, $\frac{1}{8}$ in. thick	C	"	1

RESTRICTED

Issued with A/L 41 to A.P. 1086—Book 4 (iii)

RADIO RESISTORS
SECTION 10W—cont.

Ref. No.	NOMENCLATURE	DETAIL	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6
	RESISTOR CONDENSER-UNITS—cont.				
4662	Type 139	Tufnol panel, $\frac{1}{8}$ in. thick	C	each	1
4664	Type 141	Tufnol panel, $\frac{1}{16}$ in. thick	C	"	1
4665	Type 142	Tufnol panel, $\frac{1}{16}$ in. thick	C	"	1
4666	Type 143	Tufnol panel, $\frac{1}{16}$ in. thick	C	"	1
4669	Type 146	Paxolin T.I. panel, $\frac{1}{8}$ in. thick	C	"	1
4670	Type 147	Paxolin T.I. panel, $\frac{1}{8}$ in. thick	C	"	1
4825	Type 150	Bakelite sheet, $\frac{1}{16}$ in. thick, with 32 tags.	C	"	1
4826	Type 151	Bakelite sheet, $\frac{1}{16}$ in. thick, with 20 tags.	C	"	1
4827	Type 152	Bakelite sheet, $\frac{1}{16}$ in. thick, with 15 tags.	C	"	1
4828	Type 153	Bakelite sheet, $\frac{1}{16}$ in. thick, with 14 tags.	C	"	1
4832	Type 156	Tagboard assembly. 17-way coupling	C	"	1
5095	Type 157	Tagboard assembly. 20-way coupling	C	"	1
5096	Type 158	Tagboard assembly. 40-way coupling	C	"	1
5097	Type 159	Tagboard assembly. 10-way coupling	C	"	1
5390	Type 162	S.R.B.P. sheet, $3\frac{1}{8}$ in. \times $2\frac{3}{4}$ in. \times 1 mm., fitted with 20 tags. (Drg. P.4262.)	C	"	1
5612	Type 164	S.R.B.P. sheet, $2\frac{1}{4}$ in. \times $9\frac{1}{4}$ in., with brackets.	C	"	1
5747	Type 165	C	"	1
5748	Type 166	S.R.B.P. panel	C	"	1
5749	Type 167	C	"	1
5836	Type 169	S.R.P. board, $7\frac{1}{2}$ in. \times 2 in. \times $\frac{1}{16}$ in. 76/20/1.	C	"	1
5837	Type 170	S.R.P. board, $6\frac{1}{2}$ in. \times $2\frac{5}{8}$ in. \times 1.5 mm. or $\frac{1}{16}$ in. 10120/12/1.	C	"	1
11049	Type 177	Assembly	C	"	1
11158	Type 178	S.R.B.P. panel	C	"	1
11159	Type 179	S.R.B.P. panel	C	"	1
11160	Type 180	S.R.B.P. panel	C	"	1
11164	Type 181	S.R.B.P. panel	C	"	1
11165	Type 182	S.R.B.P. panel	C	"	1
11306	Type 184	C	"	1
11307	Type 185	C	"	1
11308	Type 186	C	"	1
11310	Type 187	C	"	1
11353	Type 190	S.R.B.P. panel	C	"	1
5729	Type 192	S.R.B.P. panel	C	"	1
11431	Type 193	S.R.B.P. panel	C	"	1
11454	Type 194	C	"	1
11506	Type 195	S.R.B.P. sheet, $2\frac{3}{4}$ in. \times $1\frac{7}{8}$ in. \times $1\frac{1}{2}$ mm., with 6 tags.	C	"	1
11507	Type 196	S.R.B.P. sheet, $1\frac{1}{2}$ in. \times 1 in. \times $1\frac{1}{2}$ mm., with 4 tags.	C	"	1
11508	Type 197	S.R.B.P. sheet, $6\frac{1}{2}$ in. \times $2\frac{3}{4}$ in. \times 2 mm., with 14 tags.	C	"	1
11509	Type 198	S.R.B.P. sheet, $6\frac{1}{8}$ in. \times $2\frac{3}{4}$ in. \times 2 mm., with 53 tags.	C	"	1
11510	Type 199	S.R.B.P. sheet, $6\frac{7}{8}$ in. \times $2\frac{1}{8}$ in. \times 2 mm., with 8 tags.	C	"	1
11513	Type 200	S.R.B.P. sheet, $9\frac{1}{2}$ in. \times $2\frac{1}{8}$ in. \times 2 mm., with 36 tags.	C	"	1

RESTRICTED

154

RADIO RESISTORS
SECTION 10W—cont.

Ref. No.	NOMENCLATURE	DETAIL	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6
	RESISTOR CONDENSER-UNITS—cont.				
11514	Type 201	S.R.B.P. sheet, 3 $\frac{5}{8}$ in. \times 2 $\frac{5}{8}$ in. \times 2 mm. (A.16787) riveted to two M.S. brackets (A.16791 and A.16789) with 8 tags.	C	each	1
11596	Type 203	S.R.B.P. panel, 2 $\frac{3}{8}$ in. \times 12 $\frac{1}{4}$ in. ..	C	"	1
11597	Type 204	S.R.B.P. panels, 2 $\frac{3}{8}$ in. \times 11 $\frac{1}{2}$ in. double, mounted back to back with feet.	C	"	1
11598	Type 205	S.R.B.P. panel, 2 $\frac{1}{4}$ in. \times 2 in. ..	C	"	1
11599	Type 206	S.R.B.P. panel, 1 $\frac{1}{2}$ in. \times 2 $\frac{3}{8}$ in. ..	C	"	1
11600	Type 207	S.R.B.P. panel, 1 $\frac{3}{8}$ in. \times $\frac{7}{8}$ in. ..	C	"	1
11602	Type 208	S.R.B.P. panel, 1-812 in. \times 1 in. ..	C	"	1
11606	Type 209	S.R.B.P. panel, 2 $\frac{1}{4}$ in. \times 16 $\frac{3}{4}$ in. with 4 mounting pillars and backing plate.	C	"	1
11608	Type 210	S.R.B.P. panel, 2 in. \times 4 $\frac{1}{2}$ in. ..	C	"	1
12005	Type 211	S.R.B.P. panel, 2 $\frac{1}{8}$ in. \times 2 in. ..	C	"	1
11645	Type 213	S.R.B.P. panel, 2 $\frac{1}{8}$ in. \times 1 $\frac{1}{8}$ in. and earthing bridge (D.P.4459).	C	"	1
11646	Type 214	S.R.B.P. panel, 2 $\frac{1}{8}$ in. \times 1 $\frac{1}{8}$ in., and earthing bridge (D.P.4460).	C	"	1
11647	Type 215	S.R.B.P. panels, 5 in. \times 3 $\frac{1}{8}$ in., 2 $\frac{1}{2}$ in. \times 3 $\frac{1}{8}$ in., with insulating sheet; assembled on connecting strip, 4 in. long \times $\frac{5}{8}$ in. \times $\frac{1}{4}$ in., and complete with two spacers, $\frac{5}{8}$ in. long \times $\frac{1}{4}$ in. dia., and 2 M.S. brackets.	C	"	1
11648	Type 216	S.R.B.P. panel, 2 $\frac{1}{8}$ in. \times 3 $\frac{1}{4}$ in. \times 2 mm. thick.	C	"	1
11649	Type 217	S.R.B.P. panel, 2 $\frac{1}{8}$ in. \times 1 $\frac{1}{8}$ in., and earthing bridge (D.P.4459).	C	"	1
12382	Type 218	C	"	1
11724	Type 219	Bakelite sheet	C	"	1
11741	Type 221	C	"	1
11768	Type 222	C	"	1
11769	Type 223	C	"	1
11807	Type 224	C	"	1
11808	Type 225	C	"	1
11809	Type 226	C	"	1
11864	Type 227	C	"	1
11865	Type 228	C	"	1
11866	Type 229	C	"	1
11869	Type 230	C	"	1
11928	Type 231	C	"	1
12038	Type 233	C	"	1
12048	Type 234	Complete	C	"	1
12049	Type 235	Complete	C	"	1
12050	Type 236	Complete	C	"	1
12052	Type 237	Complete	C	"	1
12059	Type 238	Complete	C	"	1
12111	Type 239	S.R.B.P. panel, 2 $\frac{3}{8}$ in. \times 1 $\frac{1}{8}$ in. ..	C	"	1
12112	Type 240	S.R.B.P. panel, 1 ft. 5 in. \times 1 $\frac{1}{4}$ in. ..	C	"	1
12191	Type 241	S.R.B.P. panel, 2-25 in. \times 2 in. \times 0-06 in.	C	"	1
12192	Type 242	S.R.B.P. panel	C	"	1
12193	Type 243	S.R.B.P. panel	C	"	1
12194	Type 244	S.R.B.P. panel, 5-75 in. \times 2-12 in. \times 0-06 in.	C	"	1

RESTRICTED

Issued with A/L 41 to A.P. 1086—Book 4 (iii)

155

RADIO RESISTORS

SECTION 10W—cont.

Ref. No.	NOMENCLATURE	DETAIL	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6
	RESISTOR CONDENSER-UNITS—cont.				
12195	Type 245	S.R.B.P. panel, 5.75 in. × 2.12 in. × 0.06 in.	C	each	1
12218	Type 247	Bakelised paper board, 2½ in. × 3½ in.	C	"	1
12219	Type 248	Bakelised paper board, L shaped ..	C	"	1
12362	Type 252	S.R.B.P. panel	C	"	1
12363	Type 253	S.R.B.P. panel	C	"	1
12460	Type 254	C	"	1
12464	Type 255	C	"	1
12527	Type 261	Tagboard	C	"	1
12528	Type 262	Tagboard	C	"	1
12529	Type 263	Tagboard	C	"	1
12531	Type 265	Tagboard	C	"	1
12532	Type 266	Tagboard	C	"	1
12533	Type 267	C	"	1
12534	Type 268	C	"	1
12535	Type 269	C	"	1
12603	Type 270	Panel assembly	C	"	1
12642	Type 274	S.R.B.P. sheet, 2.75 in. × 1.50 in. × 0.06 in.	C	"	1
12651	Type 275	C	"	1
12652	Type 276	S.R.B.P. sheet, 8.13 in. × 2.38 in. × 0.06 in., with brass brackets riveted on.	C	"	1
12700	Type 283	S.R.B.P. sheet, 6.00 in. × 2.00 in. × 0.13 in., with 2 brass fixing brackets.	C	"	1
12701	Type 284	S.R.B.P. sheet, 8.50 in. × 2.00 in. × 0.13 in.	C	"	1
12702	Type 285	S.R.B.P. sheet, 8.00 in. × 2.00 in. × 0.13 in.	C	"	1
12703	Type 286	S.R.B.P. sheet, 6.00 in. × 2.50 in. × 0.13 in.	C	"	1
12741	Type 287	S.R.B.P. panels, 1.69 in. × 1.8 in. × 0.06 in., fitted with 10 tags.	C	"	1
13000	Type 302	C	"	1
13127	Type 306	Tagboard, with 3 condensers, 4 resistances, and 1 valve-holder.	C	"	1
13128	Type 307	Tagboard, with 1 condenser, 1 coil, 9 resistances and 4 valve-holders.	C	"	1
13131	Type 310	Tagboard, with 1 condenser and 3 resistances.	C	"	1
13136	Type 314	Tagboard, with 3 condensers and 3 resistances.	C	"	1
13230	Type 318	S.R. laminated sheet, 5½ in. × 2½ in. × 2 mm., complete with 12 resistances and 3 condensers.	C	"	1
13231	Type 319	S.R. laminated sheet, 5½ in. × 2½ in. × 2 mm., complete with 15 resistances and 1 condenser.	C	"	1
13232	Type 320	S.R. laminated sheet, 5½ in. × 2½ in. × 2 mm., complete with 13 resistances and 5 condensers.	C	"	1
13465	Type 335	Bakelite tagboard, 8 in. × 3½ in., 30 tags, 6 fixing screws.	C	"	1
15756	Type 386	S.R.B.P., 2.187 in. × 2.375 in. × 0.62 in.	C	"	1
15798	Type 388	Used on Aerial system T.295	C	"	1
16096	Type 399	Tagboard, with 1 choke, 1 capacitor and 4 resistors.	C	"	1

RESTRICTED

156

RADIO RESISTORS
SECTION 10W—cont.

Ref. No.	NOMENCLATURE	DETAIL	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6
	RESISTOR CONDENSER-UNITS—cont.				
16364	Type 407	S.R.B.P. panel	C	each	1
16375	Type 413	S.R.B.P., 5 $\frac{7}{16}$ in. × 2 $\frac{3}{8}$ in., 2 fixing brackets, 2 capacitors and 10 resistors.	C	"	1
16475	Type 415	S.R.B.P. sheet, 6 $\frac{1}{4}$ in. × 2 $\frac{3}{4}$ in. × 2 mm. complete, with resistors (14 tags).	C	"	1
16494	Type 416	Consists of 3 variable capacitors, 3 potentiometers, 1 drive. Slow motion and flexible coupling, together with fixed resistors and capacitors mounted in a bakelite case.	C	"	1
	RESISTOR MATS :—				
1426	Type 1426 .. 2·7	6 in. × 8 in. mat with centre tapped for equal resistance.	C	"	—
18024	Type — .. 10	Rectangular, 5·9 amps. rating, asbestos fabric, threaded with resistance wire approx. 2 ft. 4 in. × 1 ft. 10 in.	C	"	—
18025	Type — .. 50	Rectangular, 5·0 amps. rating, asbestos fabric, threaded with resistance wire approx. 2 ft. 4 in. × 1 ft. 10 in.	C	"	—
15744	Type 4436 .. 60	± 5 per cent., centre tapped, asbestos woven wire mat, 2 $\frac{3}{8}$ in. × 5 $\frac{1}{8}$ in.	C	"	1
16692	Type — .. 966	0·74 amp. 30 S.W.G. end tappings only. Continuously wire wound.	C	"	—
16685	Type — .. —	3 bands, each 3·3, to dissipate 1 KW intermittent, 250 volts, 3 phase, 50 cycles A.C. working stripment pattern, 13 in. × 7 $\frac{1}{2}$ in. overall, with frame, studs, and insulators.	C	"	1
16244	Type 12/33 .. 1,100	0·54 amp., with 10 taps	C	"	1
16711	Type — .. 1·750	± 5 per cent., asbestos woven wire mat, 3 $\frac{1}{2}$ in. × 2 $\frac{3}{4}$ in., 30 watts and 4 amps.	C	"	1
16337	RESISTOR TUBES ..	6·5 ohms, 6·5 amps. Steel, vitreous enamelled hexagonal wire band terminals, 8 in. long × 1 $\frac{1}{2}$ in. A.F.	C	"	50
17965	RESISTOR TUBES ..	25·6 ohms, 8·5 amps. Vitreous steel tube W.W. with brass end bands, 14 in. × 2 $\frac{1}{2}$ in. A.F.	C	"	3
17966	RESISTOR TUBES ..	15·1 ohms, 4 amps. Steel vitreous enamelled hexagonal tube, W.W. end band terminals, 8 in. × $\frac{1}{2}$ in. A.F.	C	"	3
17967	RESISTOR TUBES ..	3·12 ohms, 1·5 amps. Vitreous steel tube with brass end bands, 16 in. × 2 $\frac{1}{2}$ in. A.F.	C	"	3
17908	RESISTOR TUBES ..	84·3 ohms, 10 amps. Vitreous enamel. Steel hexagonal tube, 14 in. × 2 $\frac{1}{2}$ in. A.F., wire wound. End band terminal.	C	"	1
17905	RESISTOR TUBES	C	"	1

RESTRICTED

Issued with A/L 41 to A.P. 1086—Book 4 (iii)

157

RADIO RESISTORS

SECTION 10W—cont.

Ref. No.	NOMENCLATURE	DETAIL	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6
	RESISTOR-UNITS :—				
10547	Type 1	Paxolin panel, 4½ in. × 4.3 in. × ⅜ in., mounted on 3 brass pillars 5½ in. high.	C	each	1
10589	Type 2	C	"	1
10295	Type 4	5 ohms	C	"	10
10549	Type 5	C	"	1
588	Type 16	C	"	1
595	Type 19	C	"	1
662	Type 22	C	"	1
774	Type 28	Fitted with 2 resistors T.420 and 2 resistors T.866.	C	"	1
823	Type 29 .. .	Bakelite panel, with pin clip and valve top cap.	C	"	1
824	Type 30	Bakelite panel with diode pin clip ..	C	"	1
825	Type 31	Bakelite panel	C	"	1
871	Type 32	Consists of 2 capacitors T.16 and 2 chokes H.F.T.80.	C	"	1
904	Type 33	C	"	2
925	Type 34	C	"	1
926	Type 35	C	"	1
933	Type 36	C	"	1
2066	Type 44	As Type 29	C	"	1
2067	Type 45	Bakelite panel	C	"	1
2221	Type 47	12 volt supply	C	"	1
16024	Type 52A	C	"	—
2338	Type 54	W.W. flat resistor with 37 tappings ..	C	"	1
2369	Type 56	Tufnol panel, 5½ in. × 3½ in. × 2 mm.	C	"	1
2370	Type 57	Tufnol mat, 7½ in. × 3 in. × 2 mm.	C	"	1
2444	Type 60	Bakelite panel, 4⅜ in. × 3¼ in. ..	C	"	—
2445	Type 61	C	"	—
2551	Type 63	Insulation panel	C	"	1
2559	Type 64	Bakelite panel	C	"	1
2571	Type 65	Ebonite base assembly	C	"	1
2735	Type 77	Fitted with one each of resistor T.761, 400, 1239, 101, and 124.	C	"	1
2742	Type 78	Bakelite panel, 7¼ in. × 3¼ in. ..	C	"	1
2767	Type 87	For C.G. voltmeter	C	"	1
2768	Type 88	For C.G. supply	C	"	1
2790	Type 91	C	"	1
2838	Type 99	Bakelite panel with one resistor T.1579	C	"	1
2783	Type 103	Bakelite panel with various resistors	C	"	1
2903	Type 104	Bakelite panel with various resistors	C	"	1
2946	Type 105	Tufnol panel	C	"	1
3244	Type 126	C	"	1
3831	Type 138	C	"	1
3832	Type 139	2-way	C	"	1
3892	Type 150	Panel insulator, 5½ in. × 1¼ in., fitted with various resistors.	C	"	1
3894	Type 152	Fitted with 10 resistors R22-31 ..	A	"	1
4220	Type 153	Panel, with tags and leads	C	"	1
4222	Type 154	Strips assembly, with potentiometer and retaining clip ring.	C	"	1
4468	Type 161	C	"	1
4469	Type 162	C	"	1
4606	Type 164	Bakelite panel, 4 tags	C	"	1
4607	Type 165	5 leads wired to 2 connecting plates, 10 resistors T.209 arranged in 2 parallel rows of 5 each wired to 2 plates, slotted to take connection bolts.	C	"	1

RESTRICTED

158

RADIO RESISTORS

SECTION 10W—cont.

Ref. No.	NOMENCLATURE	DETAIL	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6
RESISTOR UNITS					
		<i>—cont.</i>			
4608	Type 166	25 ohms \pm 10 per cent., wire-wound variable, in metal case, $1\frac{1}{16}$ in. \times $2\frac{1}{2}$ in. dia., complete with metal braided lead; spindle, $\frac{3}{4}$ in. \times $\frac{1}{4}$ in. with flat.	C	each	1
4668	Type 172	Paxolin T.I. panel, $\frac{1}{8}$ in. thick ..	C	"	1
4671	Type 173	Paxolin T.I. panel, $\frac{3}{16}$ in. thick ..	C	"	1
4672	Type 174	Panel assembly	C	"	1
5627	Type 190	Panel, complete with resistances ..	C	"	1
5746	Type 194	Bakelised paper panel	C	"	1
5751	Type 195	S.R.B.P. panel	C	"	1
5840	Type 196	S.R.P. board, $2\frac{3}{4}$ in. \times $1\frac{1}{8}$ in. \times $\frac{1}{16}$ in. (A.13211.)	C	"	1
11042	Type 201	7 ohms, approximately 7 to 8 amps.	C	"	1
11044	Type 202	Three sets of resistance grids, 1-36, 0-936, 4-124 ohms, fitted between two end mountings, $11\frac{5}{8}$ in. \times $3\frac{5}{8}$ in. \times $\frac{7}{8}$ in., $16\frac{1}{2}$ in. between mountings.	C	"	1
11539	Type 212	S.R.B.P. sheet, $4\frac{1}{2}$ in. \times $\frac{13}{16}$ in. \times 3 mm., with 2 clips.	C	"	1
11581	Type 213	Strip assembly, with potentiometers and retaining click ring.	C	"	1
11585	Type 214	Variable focus and brilliance control, with gearing and extension shafts.	C	"	1
11586	Type 215	Potentiometer panel, M.S., 8 in. \times $6\frac{1}{2}$ in., flanged, with pivot plate.	C	"	1
11589	Type 216	S.R.B.P. panel, $4\frac{1}{2}$ in. \times 2 in. ..	C	"	1
11590	Type 217	S.R.B.P. panel, $1\frac{1}{2}$ in. sq.	C	"	1
11591	Type 218	S.R.B.P. panel, $1\frac{3}{8}$ in. \times $1\frac{1}{4}$ in. ..	C	"	1
11614	Type 219	S.R.B.P. panel	C	"	1
11651	Type 221	S.R.B.P. panel, $2\frac{1}{8}$ in. \times $1\frac{1}{8}$ in., and earthing bridge (D.P.4459).	C	"	1
11720	Type 224	Bakelite base, $2\frac{3}{8}$ in. \times $2\frac{3}{8}$ in. ..	C	"	1
11721	Type 225	Bakelite sheet, $4\frac{7}{8}$ in. \times $6\frac{1}{4}$ in., fitted with resistances each side.	C	"	1
11983	Type 227	C	"	1
11984	Type 228	92 ohms, four 23 ohms, 35 watts, carbon resistances in series. Part of A.R.I.5119.	C	"	1
11985	Type 229	Used for testing A.R.I.5093 and 5153	C	"	1
11986	Type 230	2,000 ohms (four 500 ohms), 35 watts, carbon resistors in series.	C	"	1
11987	Type 231	Twelve 80 ohms, 35 watts, carbon resistors in parallel, in banks of six.	C	"	1
11991	Type 232	Insulating plate, fitted with one fixed and one variable resistance.	C	"	1
12110	Type 235	S.R.B.P. panel, $1\frac{1}{2}$ in. \times $\frac{7}{8}$ in. ..	C	"	1
12198	Type 238	C	"	1
12217	Type 239	Bakelite strips, with two metal end brackets.	C	"	1
12220	Type 240	Bakelised paper board, $2\frac{3}{8}$ in. \times $2\frac{1}{4}$ in.	C	"	1
12221	Type 241	Bakelised paper board, $1\frac{3}{8}$ in. \times $2\frac{3}{8}$ in.	C	"	1
12453	Type 247	C	"	1
12454	Type 248	S.R.B.P. sheet, $4\frac{3}{16}$ in. \times $3\frac{11}{16}$ in., with two fixing brackets.	C	"	1
12465	Type 249	Tagboard, with resistances	C	"	1
12466	Type 250	Tagboard, with resistances	C	"	1
12467	Type 251	Tagboard, with resistances	C	"	1

RESTRICTED

Issued with A/L 41 to A.P. 1086—Book 4 (iii)

159

RADIO RESISTORS
SECTION 10W—cont.

Ref. No.	NOMENCLATURE	DETAIL	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6
RESISTOR UNITS					
<i>—cont.</i>					
12575	Type 252	S.R.B.P. panel, 1.87 in. × 1.44 in. × 0.06 in., with angle bracket fixing.	C	each	1
12602	Type 253	Panel assembly	C	"	1
12624	Type 256	Panel and bracket, mounted with potentiometer and fixed resistance.	C	"	1
12625	Type 257	1½ in. × ¾ in. × ⅙ in. S.R.B.P., with 4 tags.	C	"	1
12632	Type 260	C	"	1
13053	Type 277	Assembly in paxolin tube, 5½ in. × ¾ in. o/d × ⅝ in. i/d, with brass caps.	C	"	1
13096	Type 281	Tag panel assembly	C	"	1
13365	Type 287	S.R.B.P. sheet, ¾ in. × 1 in. × ⅙ in. thick.	C	"	1
13402	Type 289	Modulator dummy load for T.3501 ..	C	"	1
13510	Type 292	Assembly in metal container, 11 in. × 3½ in. approx.	C	"	1
13511	Type 293	Mycalex, ⅙ in. thick, 3 in. × 3⅝ in., with 6 resistances, Type 1730, and with fixing brackets.	C	"	1
13512	Type 294	⅙ in. thick, WT.22, 10½ in. × 4½ in., with fixing brackets and 10 resistances.	C	"	1
13686	Type 306	Tagboard, with 11 resistances ..	C	"	1
13687	Type 307	Box, 8 in. × 3 in. × 3 in. inside, 30 watt resistor, W plug one end, other end a length of Sextomet cable, with no socket one end.	C	"	1
13888	Type 319	S.R.B.P., ⅝ in. × 2.562 in. × ⅙ in.	C	"	1
13889	Type 320	S.R.B.P., 3.75 in. × 2.63 in. × ⅙ in.	C	"	1
13898	Type 322	Modification of Resistance Unit, Type 228. Instead of four 23 ohms resistors in series, there are four 62-ohms resistors in series parallel. Plug, Type W354, is superseded by American plug, Amphenol type 97/3108/795/S.	C	"	1
13932	Type 323	S.R.B.P., 7.37 in. × 1.25 in., open frame, with bracket each end. Fitted with 17 pairs of tags.	C	"	1
13981	Type 327	⅙ in. bakelite sheet, 8 in. × 3⅞ in., with fixing tags and 6 resistances, Type 0/98.	C	"	1
13982	Type 328	Complete. Used with TR.3182 ..	C	"	1
13989	Type 329	Complete	C	"	1
14028	Type 331	Tagboard, with 2 resistances ..	C	"	1
14029	Type 332	Tagboard, with 5 resistances ..	C	"	1
15722	Type 334	Tagboard, with 3 resistors ..	C	"	1
15883	Type 339	S.R.B.P. panel, with various resistors	C	"	1
16013	Type 341	S.R.B.P., 1.64 in. × 1.72 in. × 0.06 in., fitted with two brackets, one resistance, one plug, and DuceL 4, 6 in.	C	"	1
16019	Type 342	S.R.B.P., ⅙ in. × ¾ in. × 2½ in. ..	C	"	1
16164	Type 348	Single spool, 600 ohms. Impedance with shunt coil 3,510 ohms 2 per cent., and series coil 105.7 ohms 2 per cent.	C	"	1
16297	Type 352	Assembly of 2 resistances, 25,000 ohms, K5-VS, 2 end caps.	C	"	1
16298	Type 353	Assembly of 2 resistances, 25,000 ohms, intermediate coupling.	C	"	1

RESTRICTED

160

RADIO RESISTORS
SECTION 10W—cont.

Ref. No.	NOMENCLATURE	DETAIL	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6
RESISTOR UNITS					
		—cont.			
16376	Type 354	S.R.B.P., 3½ in. × 1½ in., with 2 resistances.	C	each	1
16418	Type 356	Consists of 4 resistors in parallel each of 220 ohms to give 55 ohms altogether.	C	"	1
16432	Type 357	4 K ± 5 per cent., 7½ watts, embedded capped ends.	C	"	1
12058	Type 358	C	"	1
16458	Type 359	Shift potentiometer, 6 in. × 6 in. × 3¼ in. overall, complete with relay, 40 resistors wound on bobbins, slider assembly and contact studs.	C	"	1
16459	Type 360	Wind rate potentiometer, 5¼ in. × 5¼ in. × 3 in. overall (approx.), complete with 38 resistors wound on bobbins, arranged in a circle, slider assembly and contact studs.	C	"	1
16460	Type 361	Potentiometer assembly, 6 in. × 6 in. × 3¼ in. overall (approx.), complete with 40 resistors wound on bobbins, contact studs and wipe assembly.	C	"	1
16461	Type 362	Potentiometer assembly, 6 in. × 6 in. × 3¼ in. overall (approx.), complete with 40 resistors wound on bobbins, contact studs and wipe assembly (as Type 361 but different stud connections).	C	"	1
12060	Type 363	C	"	1
14022	Type 364	Tagboard, with 1 choke, 1 condenser, and 5 resistances.	C	"	1
14023	Type 365	Tagboard, with 3 condensers and 12 resistances.	C	"	1
16617	Type 367	M.S. cover and bracket, 1 heating element, 1,000 w. 250 v. Belling A/1, a switch 5C/622 for low power.	C	"	1
15555	Type 369	Complete, S.R.B.P., 7.87 in. × 2.37 in. × 0.06 in., fitted with 18 pairs of tags.	C	"	1
16645	Type 370	C	"	1
17429	Type 377	Including W.W. plug T.609, 20,000 ohms resistor.	C	"	1
17651	Type 378	Assembly of 5 resistors T.187 each, 100,000 ohms ± 5 per cent. (BERCO K6-VS to P.13282/AV), but the total resistor to be ½ meg. ± 1 per cent. 20 mA and individual item coded.	C	"	1
17807	Type 379	Assembly in metal case with extension connectors.	C	"	1
17815	Type 381	C	"	1
17901	Type 383	W.W. H. Pad. 3 sets of resistance grids, 245 + 245 ohms, 121 ohms, and 245 + 245 ohms, mounted between 2 zinc plated brackets. Dims. 2⅞ in. × 2⅜ in.	C	"	1
17899	Type 384	2 bobbins per unit. W.W. overall resistance 25 K. ohms, 1 watt.	C	"	1
17900	Type 385	Single bobbin, W.W., 12.5 K. ohms, 1 watt.	C	"	1

RESTRICTED

Issued with A/L 41 to A.P. 1086—Book 4 (iii)

161

RADIO RESISTORS

SECTION 10W—cont.

Ref. No.	NOMENCLATURE	DETAIL	Class of Store	Denom of Qty.	Carton Unit Qty.
1	2	3	4	5	6
RESISTOR UNITS					
<i>—cont.</i>					
17951	Type 386	3 bobbins per unit, W.W., overall resistance 37 K. ohms, 1 watt.	C	each	1
17952	Type 387	Single bobbin W.W., 10 K. ohms, 1 watt.	C	"	1
17953	Type 388	3 bobbins per unit, W.W. overall resistance 30 K. ohms, 1 watt.	C	"	1
17954	Type 389	Single bobbin, W.W. 14.8 K. ohms, 1 watt.	C	"	1
17955	Type 390	Single bobbin, W.W. 13 K. ohms, 1 watt.	C	"	1
17987	Type 391	Assembly of 10 resistors on both sides of 12 copper strips mounted on frame, 5 $\frac{5}{16}$ in. \times 3 in.	C	"	1
16014	Type 393	C	"	1
18020	Type 396	12 resistors, 14.5 ohms each, on metal frame, with ceramic spacers, 24 in. \times 12 in.	C	"	1
18022	Type 397	16 mats of 10 ohms each, mounted in M. steel frame, 2 ft. 10 ins. wide \times 2 ft. 4 $\frac{5}{8}$ in. sq. Connections made to terminal busbars on top of 3 brick type insulators, 4 in. high, and frame mounted on 9 in. box type insulators.	C	"	1
18023	Type 398	16 mats at 50 ohms each, mounted in M. steel, 2 ft. 10 in. \times 2 ft. 4 $\frac{5}{8}$ in. sq. Connections made to terminal busbars on top of 3 brick-type insulators, 4 in., and frame mounted on 9 in. box-type insulators.	C	"	1
18026	Type 399	Potentiometer assembly, with 16 bobbin wound resistors on panel, 3 in. \times 3 in. \times $\frac{1}{4}$ in. thick. Complete with contact studs and blades and worm-wheel. Similar to Resistor Unit T.358 (Ref. No. 10W/16457), but wound to different specification.	C	"	1
16307	Type 405	S.R.B.P. strip, $\frac{1}{16}$ in. \times 2 $\frac{1}{8}$ in. \times 5 $\frac{1}{4}$ in., fitted with 4 condensers and 7 resistances.	C	"	1
16308	Type 406	S.R.B.P. strip, $\frac{1}{16}$ in. \times 2 $\frac{1}{8}$ in. \times 3 $\frac{3}{4}$ in., fitted with 1 condenser and 4 resistances.	C	"	1
16390	Type 414	2 ft. 10 in. \times 1 ft. 10 in. \times $\frac{15}{16}$ in. deep, with two-way terminal block, 200 $\mu\mu$ F condenser and 1 resistance connected in series.	C	"	1
16582	Supports, top ..	Mycalex, $\frac{1}{8}$ in. \times $\frac{1}{2}$ in. \times 12 $\frac{1}{2}$ in. ..	C	"	—
16583	Supports, bottom ..	Mycalex, $\frac{1}{8}$ in. \times $\frac{1}{2}$ in. \times 12 $\frac{1}{2}$ in. ..	C	"	—
16584	Supports, centre ..	Mycalex, 2 $\frac{1}{4}$ in. \times $\frac{3}{16}$ in. \times 10 in. Copper inserts.	C	"	—
16585	Supports, side ..	Mycalex, 4 $\frac{7}{8}$ in. \times 1 $\frac{5}{8}$ in. \times $\frac{3}{16}$ in. ..	C	"	—
16586	Supports, side ..	Mycalex, 4 $\frac{7}{8}$ in. \times 1 $\frac{5}{8}$ in. \times $\frac{3}{16}$ in. ..	C	"	—
16587	Supports, mounting ..	Mycalex, 11 $\frac{1}{2}$ in. \times $\frac{3}{8}$ in. dia. ..	C	"	—
THERMISTORS:—					
17655	Type 1	1 amp., $\frac{5}{8}$ in. \times $\frac{1}{16}$ in. dia., with 23 S.W.G. copper wire terminations 3 $\frac{1}{2}$ in. long.	C	"	1
18072	Type 2	C	"	1

RESTRICTED

162

MISCELLANEOUS SPARES

SECTION 10W—cont.

Ref. No.	NOMENCLATURE	DETAIL	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6
16346	WIRES , lead screw ..	Phosphor bronze, 0.080 in. dia. Spiralex 14 S.W.G.	C	each	10
16321	BUSHES , insulating ..	Black bakelite, round, flanged, 2 B.A. clear i/d. Ends of sliders rod (MOU 16).	C	"	—
16322	BUSHES , insulating ..	Black bakelite, round, flanged, 2 B.A. clear, drive end of slide rod.	C	"	10
16323	CASTINGS , end ..	Casting No. 51. Brass, hexagonal, black finish, 1½ in. A.F. tube (drive end).	C	"	—
16324	CASTINGS , end ..	Casting No. 35. Hexagonal, black finish, 1½ in. A.F. tube. (Free end lead screw.)	C	"	—
16325	CASTINGS , end ..	Casting No. 1. Brass, hexagonal, black finish, 1½ in. A.F., plain end.	C	"	—
16326	CASTINGS , end ..	Casting No. 19. Brass, for 2 hexagonal tubes, black finish, plain ends.	C	"	—
16580	CLIPS , tapping ..	2 Sections, 2¼ in. × 1 in. × ½ in., with pin and screw.	C	"	1
16333	CUPS , insulating ..	Mica hexagonal, 1½ in. A.F.	C	"	1
16334	GEAR WHEELS ..	Hard brass, 2:1 ratio, 34 and 17 teeth respectively.	C	"	—
16335	LEAD SCREWS ..	Steel, cadmium plated, spiral groove drive and bearing extensions 7/16 in. × 8 in. × 5/8 in., pitch R.H.	C	"	—
16336	LEAD SCREWS ..	Steel, cadmium plated, spiral groove drive and bearing extensions, 7/16 in. × 8 in. × 5/8 in., L.H.	C	"	—

RESTRICTED

Issued with A/L 41 to A.P. 1086—Book 4 (m)

RADIO RESISTORS AND MISCELLANEOUS SPARES

INDEX TO REFERENCE NUMBERS

SECTION 10W—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
6	7	192	73	530	3	889	4	1110	111
8	3	193	76	536	122	890	152	1113	22
28	8	195	85	538	106	895	71	1116	18
30	6	197	88	556	84	898	1	1118	83
31	8	198	139	557	101	903	135	1119	56
32	13	202	93	558	91	904	157	1126	14
34	5	204	140	574	14	905	13	1129	91
45	107	206	143	575	57	907	11	1130	91
48	3	209	97	586	116	920	86	1131	90
52	16	224	6	587	119	921	88	1132	120
64	107	235	7	588	157	922	110	1135	88
65	100	236	114	595	157	925	157	1136	83
66	3	239	5	596	36	926	157	1137	109
67	50	252	136	597	3	933	157	1138	51
71	51	253	131	598	151	936	53	1141	14
100	148	259	129	600	19	937	98	1149	75
107	4	287	11	611	93	945	88	1154	58
109	6	291	133	612	100	946	97	1167	126
111	6	292	142	620	11	953	119	1168	147
112	7	293	139	628	95	980	1	1169	21
113	8	294	137	641	9	986	64	1174	2
116	14	295	7	644	152	987	103	1180	36
117	15	296	17	662	157	994	14	1182	140
118	17	297	17	665	2	999	104	1186	53
121	3	298	3	687	139	1000	64	1187	18
123	6	301	38	692	99	1013	5	1188	6
126	17	307	105	700	50	1014	7	1189	14
127	17	310	10	708	128	1023	19	1192	83
128	19	311	7	748	47	1024	10	1195	80
129	20	316	12	750	3	1025	103	1196	106
131	21	318	34	755	8	1026	99	1197	90
132	21	320	33	757	56	1027	90	1200	98
133	33	321	34	758	58	1028	42	1201	78
135	33	322	34	759	61	1029	41	1202	95
137	33	323	132	761	60	1030	121	1203	97
138	33	328	34	762	47	1033	38	1204	53
139	33	329	11	764	79	1034	38	1209	17
140	34	338	61	765	80	1035	18	1210	21
141	34	341	12	766	77	1039	56	1211	22
144	34	342	33	767	114	1040	124	1212	54
146	34	348	66	774	157	1045	62	1213	53
147	34	349	45	803	1	1046	58	1214	57
148	34	350	43	807	5	1047	54	1217	52
152	35	352	46	809	7	1048	48	1218	57
153	21	355	117	810	7	1055	129	1220	50
154	35	389	77	821	40	1056	127	1221	97
155	35	390	85	823	157	1059	20	1222	108
156	9	403	95	824	157	1063	84	1223	99
157	9	432	4	825	157	1064	101	1224	104
158	13	455	13	828	11	1065	88	1226	80
159	14	456	22	830	9	1070	56	1229	69
160	15	457	1	832	12	1083	69	1230	69
161	16	458	20	840	17	1086	54	1232	73
162	19	459	11	841	13	1088	108	1233	80
163	9	460	21	846	68	1093	90	1236	83
164	10	461	2	848	45	1094	44	1241	52
165	10	462	82	854	13	1095	1	1245	16
177	140	463	21	855	15	1096	10	1247	122
181	55	464	56	871	157	1098	2	1248	128
182	57	500	83	875	7	1100	132	1250	60
187	115	525	110	881	55	1102	19	1251	138
190	70	527	14	888	6	1103	64	1253	13

RESTRICTED

164

RADIO RESISTORS AND MISCELLANEOUS SPARES

INDEX TO REFERENCE NUMBERS

SECTION 10W—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
1262	134	1396	6	1551	66	1691	78	1878	13
1263	93	1402	19	1552	10	1695	51	1880	14
1264	94	1405	54	1553	10	1697	13	1883	19
1265	103	1408	50	1556	80	1698	4	1885	20
1266	80	1410	46	1559	129	1701	53	1886	20
1267	91	1411	39	1560	56	1702	38	1912	69
1268	99	1412	39	1563	87	1703	3	1913	87
1269	111	1413	39	1566	59	1704	37	1914	32
1271	130	1414	147	1567	93	1706	15	1917	19
1272	107	1415	39	1568	98	1707	101	1921	47
1277	143	1416	39	1569	77	1711	10	1925	13
1279	127	1417	39	1572	117	1712	12	1927	130
1286	65	1420	55	1574	91	1715	31	1932	6
1287	2	1426	156	1576	147	1716	18	1933	102
1291	14	1428	125	1577	83	1718	58	1934	108
1295	18	1429	60	1579	147	1719	62	1939	5
1300	11	1439	104	1581	47	1722	22	1957	56
1305	88	1439	104	1582	56	1725	85	1963	7
1311	2	1440	98	1583	53	1727	38	1971	58
1313	3	1441	86	1584	132	1730	50	1972	59
1314	151	1442	81	1587	97	1733	12	1973	67
1318	80	1443	78	1588	108	1738	60	1974	16
1319	83	1444	104	1589	56	1740	95	1975	8
1321	46	1446	44	1590	56	1742	95	1979	151
1322	111	1447	5	1594	71	1745	54	1994	88
1323	58	1448	111	1595	98	1748	18	2021	152
1324	83	1449	111	1599	61	1751	129	2066	157
1326	139	1453	16	1600	92	1753	107	2067	157
1327	151	1455	1	1602	104	1754	97	2198	152
1328	50	1457	103	1606	2	1755	2	2212	152
1330	45	1458	1	1609	126	1756	14	2216	152
1332	36	1459	2	1611	130	1760	98	2217	152
1333	111	1460	5	1616	111	1761	105	2221	157
1334	111	1463	8	1622	99	1762	102	2338	157
1335	48	1465	11	1627	53	1763	149	2369	157
1336	62	1471	42	1631	88	1768	53	2370	157
1337	12	1484	1	1632	18	1782	122	2444	157
1338	8	1486	75	1635	119	1800	72	2445	157
1345	44	1488	117	1640	151	1807	100	2526	149
1355	57	1489	121	1641	151	1808	104	2551	157
1356	93	1493	75	1642	48	1811	71	2559	157
1357	65	1497	9	1643	69	1821	16	2571	157
1360	137	1499	8	1644	51	1822	17	2597	152
1364	36	1500	14	1646	54	1829	9	2731	152
1367	7	1501	45	1647	110	1831	20	2734	152
1370	44	1511	22	1648	58	1834	1	2735	157
1371	94	1512	88	1659	90	1838	7	2739	152
1372	59	1513	18	1665	52	1839	12	2741	152
1376	39	1517	64	1666	138	1840	1	2742	157
1378	39	1518	53	1669	7	1843	7	2756	152
1379	39	1521	86	1671	20	1845	8	2757	152
1381	39	1525	106	1674	20	1846	8	2767	157
1382	39	1528	99	1675	3	1849	10	2768	157
1383	146	1532	19	1676	1	1851	12	2769	152
1384	31	1534	93	1677	1	1857	3	2770	152
1385	14	1535	103	1679	2	1859	5	2783	157
1386	31	1540	55	1681	145	1862	5	2790	157
1389	40	1542	151	1683	147	1864	6	2836	152
1391	41	1544	36	1684	21	1865	7	2837	152
1393	135	1547	103	1685	90	1873	11	2838	157
1394	146	1548	2	1687	54	1874	11	2903	157
1395	146	1549	36	1689	86	1876	11	2946	157

RESTRICTED

RESTRICTED

Issued with A/L 41 to A.P. 1086—Book 4 (iii)

165

RADIO RESISTORS AND MISCELLANEOUS SPARES

INDEX TO REFERENCE NUMBERS

SECTION 10W—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
2998	146	5745	20	6175	3	6341	77	6493	57
3016	152	5746	158	6180	103	6342	78	6496	50
3244	157	5747	153	6182	9	6348	68	6497	2
3344	117	5748	153	6184	14	6349	83	6498	5
3367	152	5749	153	6185	16	6350	73	6500	54
3372	152	5751	158	6186	17	6351	109	6507	16
3627	152	5752	20	6188	79	6360	43	6508	50
3744	152	5836	153	6189	72	6365	61	6511	49
3748	152	5837	153	6190	77	6366	58	6513	31
3749	152	5840	158	6191	36	6367	61	6519	40
3750	152	6001	5	6200	6	6368	36	6521	31
3751	152	6002	113	6201	34	6371	25	6530	8
3752	152	6004	97	6202	32	6373	24	6532	31
3831	157	6005	16	6205	41	6374	25	6533	31
3832	157	6011	17	6209	78	6375	27	6536	4
3892	157	6022	15	6212	20	6377	25	6542	54
3894	157	6039	20	6213	115	6379	24	6545	116
4055	152	6056	16	6215	7	6380	26	6550	32
4058	152	6060	149	6221	16	6383	67	6558	56
4060	152	6061	34	6230	10	6385	145	6516	106
4127	152	6068	118	6242	16	6387	142	6562	104
4128	152	6069	1	6244	12	6389	12	6569	31
4129	152	6070	101	6245	15	6390	16	6575	47
4130	152	6073	3	6247	8	6404	14	6577	59
4220	157	6074	72	6252	10	6406	55	6579	47
4222	157	6076	78	6253	11	6408	126	6580	48
4311	152	6077	82	6254	36	6411	123	6581	50
4312	152	6085	20	6255	97	6418	18	6585	113
4468	157	6087	130	6256	101	6419	45	6586	124
4469	157	6088	8	6257	103	6420	77	6587	85
4513	152	6092	13	6259	149	6421	80	6588	56
4514	152	6094	76	6264	145	6423	42	6589	27
4515	152	6095	13	6265	145	6425	54	6590	25
4606	157	6097	123	6269	127	6426	41	6591	27
4607	157	6098	126	6270	54	6427	44	6593	25
4608	158	6100	125	6277	137	6428	50	6597	26
4660	152	6103	43	6278	141	6431	7	6600	147
4661	152	6122	63	6282	48	6433	11	6607	22
4662	153	6125	65	6284	104	6434	15	6609	24
4664	153	6126	64	6285	104	6436	18	6610	26
4665	153	6127	64	6286	102	6437	20	6612	23
4666	153	6129	6	6287	96	6439	6	6614	25
4668	158	6131	4	6289	100	6440	21	6617	25
4669	153	6132	34	6290	94	6441	21	6622	40
4670	153	6133	34	6291	91	6445	93	6634	27
4671	158	6137	70	6292	111	6447	62	6635	27
4672	158	6139	88	6293	111	6448	140	6649	1
4825	153	6146	129	6294	121	6459	22	6654	8
4826	153	6147	85	6300	4	6464	87	6655	8
4827	153	6151	37	6301	101	6467	113	6658	116
4828	153	6152	12	6302	35	6468	104	6659	10
4832	153	6156	76	6305	139	6469	106	6660	12
5095	153	6157	67	6306	149	6472	2	6662	17
5096	153	6159	48	6313	107	6474	137	6666	24
5097	153	6160	17	6314	99	6477	18	6667	24
5138	16	6161	67	6315	120	6481	2	6670	57
5390	153	6162	148	6317	77	6482	6	6674	61
5492	121	6163	16	6318	86	6485	73	6676	3
5588	7	6164	63	6334	8	6486	76	6681	23
5612	153	6166	17	6337	39	6487	79	6683	28
5627	158	6171	18	6338	136	6488	83	6684	29
5729	153	6174	148	6340	2	6491	98	6689	42

RESTRICTED

166

RADIO RESISTORS AND MISCELLANEOUS SPARES

INDEX TO REFERENCE NUMBERS

SECTION 10W—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
6690	23	6902	9	7126	26	7313	69	7507	117
6692	46	6906	56	7127	23	7314	7	7509	151
6697	79	6907	21	7128	72	7317	6	7510	74
6706	13	6908	90	7129	72	7318	1	7518	88
6713	18	6915	41	7130	58	7319	9	7519	58
6720	26	6918	23	7132	86	7321	75	7520	56
6721	24	6919	97	7141	26	7332	86	7521	39
6723	28	6924	95	7142	67	7337	36	7522	23
6729	26	6928	57	7143	131	7342	101	7526	23
6738	24	6929	51	7144	129	7356	9	7528	24
6744	26	6932	62	7145	137	7357	5	7529	23
6753	23	6934	33	7147	22	7359	104	7530	25
6754	27	6939	95	7148	21	7362	96	7536	8
6756	25	6940	98	7149	148	7365	77	7537	59
6758	27	6944	34	7161	30	7366	70	7541	6
6759	27	6946	33	7162	29	7368	66	7542	105
6800	27	6947	38	7163	29	7382	54	7544	92
6805	26	6948	126	7164	29	7393	17	7545	94
6806	24	6955	121	7165	29	7397	17	7546	108
6808	25	6964	52	7166	21	7398	17	7548	102
6811	28	6966	28	7167	29	7401	18	7549	97
6813	131	6968	23	7169	29	7403	20	7557	70
6814	142	6970	28	7175	29	7405	66	7560	144
6816	6	6974	37	7189	17	7408	42	7561	136
6818	81	6978	4	7191	19	7409	5	7562	85
6819	90	6998	73	7193	86	7410	57	7564	74
6820	40	7001	11	7196	95	7413	78	7570	46
6830	59	7002	19	7197	29	7414	75	7572	25
6833	43	7004	21	7198	138	7416	107	7574	28
6839	112	7025	1	7211	147	7419	45	7577	114
6841	19	7027	4	7215	11	7420	103	7579	97
6843	11	7029	3	7222	21	7421	75	7580	3
6846	14	7035	4	7223	124	7422	83	7581	60
6850	9	7038	33	7226	38	7431	17	7582	79
6851	7	7043	26	7229	36	7432	12	7585	55
6852	12	7048	27	7241	52	7433	4	7596	87
6856	8	7049	23	7244	47	7434	95	7597	85
6858	11	7051	24	7247	56	7435	97	7601	15
6860	70	7054	144	7252	2	7440	40	7602	20
6861	59	7055	6	7253	12	7442	62	7603	18
6863	67	7057	25	7254	5	7443	51	7607	39
6864	79	7059	24	7260	146	7444	80	7608	126
6865	1	7060	23	7263	148	7445	49	7609	2
6866	2	7062	24	7264	79	7448	49	7610	117
6869	46	7064	25	7267	19	7449	119	7615	42
6870	20	7067	51	7271	24	7450	116	7616	103
6871	18	7068	46	7272	25	7451	130	7641	41
6872	5	7070	35	7273	15	7453	126	7642	29
6876	8	7075	19	7278	148	7454	128	7643	29
6878	63	7076	94	7282	26	7457	79	7646	29
6880	19	7078	86	7285	26	7461	112	7647	30
6882	72	7083	130	7287	23	7478	117	7648	29
6883	63	7085	98	7292	23	7479	125	7650	30
6884	12	7086	4	7295	148	7480	22	7651	29
6886	12	7096	55	7300	27	7484	31	7654	109
6889	10	7097	70	7301	29	7493	46	7655	106
6890	6	7101	24	7302	23	7498	124	7668	108
6894	82	7105	24	7303	53	7500	3	7669	21
6896	67	7107	23	7305	49	7501	39	7674	30
6897	64	7116	25	7309	47	7502	39	7676	14
6899	6	7117	24	7310	45	7503	144	7678	7
6900	7	7124	24	7311	52	7504	39	7684	42

RESTRICTED

Issued with A/L 41 to A.P. 1086—Book 4 (iii)

167

RADIO RESISTORS AND MISCELLANEOUS SPARES

INDEX TO REFERENCE NUMBERS

SECTION 10W—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
7685	5	7868	119	8077	66	8227	94	8434	139
7687	76	7869	81	8083	105	8229	102	8435	83
7688	2	7882	19	8085	67	8248	78	8443	51
7689	151	7886	145	8086	102	8250	87	8444	45
7690	21	7887	105	8087	107	8251	75	8449	116
7691	151	7888	102	8089	115	8257	40	8452	113
7693	14	7889	62	8091	18	8259	117	8453	40
7708	7	7890	62	8093	22	8263	28	8462	63
7715	19	7891	60	8095	84	8264	23	8466	49
7724	97	7892	58	8096	78	8266	13	8470	31
7725	102	7910	115	8097	69	8278	88	8477	62
7726	98	7914	15	8099	72	8283	43	8512	80
7727	107	7915	1	8101	108	8285	68	8515	129
7728	108	7918	119	8102	72	8293	77	8517	34
7729	109	7919	123	8103	75	8294	81	8520	131
7737	60	7922	8	8104	77	8295	88	8521	113
7739	82	7924	98	8105	75	8297	3	8527	13
7740	4	7933	141	8106	91	8308	79	8528	112
7741	54	7934	88	8107	67	8309	82	8534	94
7743	101	7939	115	8109	83	8310	87	8538	116
7746	31	7940	52	8110	89	8312	64	8539	51
7748	31	7941	68	8111	86	8313	85	8541	100
7749	134	7942	69	8113	68	8314	85	8546	48
7750	138	7949	110	8125	78	8322	30	8548	44
7751	115	7958	146	8128	106	8323	30	8556	49
7766	126	7960	9	8129	99	8325	29	8557	42
7767	90	7963	69	8130	110	8328	76	8558	43
7776	99	7964	16	8131	59	8329	79	8562	23
7777	131	7965	20	8132	61	8330	86	8571	51
7780	104	7966	9	8133	62	8333	73	8572	106
7782	134	7960	57	8136	110	8338	84	8573	105
7785	128	7976	100	8137	108	8340	102	8574	105
7796	100	7977	139	8143	15	8342	26	8576	58
7797	105	7978	84	8147	105	8343	40	8577	42
7798	97	7982	55	8156	18	8344	121	8578	40
7799	92	7984	58	8159	105	8346	34	8579	41
7800	137	7986	64	8168	6	8347	34	8582	91
7802	35	7991	41	8174	11	8348	34	8586	40
7804	34	7993	53	8176	116	8350	93	8598	85
7806	33	7994	15	8179	114	8355	119	8599	57
7808	119	7995	136	8182	129	8357	68	8604	81
7809	94	7998	45	8184	126	8358	81	8605	76
7810	131	8000	85	8185	77	8359	106	8606	74
7811	127	8005	149	8194	4	8361	110	8607	22
7813	82	8014	78	8195	5	8362	97	8613	68
7818	76	8015	107	8196	11	8370	78	8614	71
7822	20	8023	83	8197	17	8375	71	8621	7
7823	19	8026	67	8198	83	8376	88	8623	91
7825	148	8028	97	8200	62	8390	130	8629	9
7829	16	8029	72	8202	58	8392	122	8633	130
7835	55	8032	105	8203	46	8393	122	8643	78
7838	128	8050	47	8204	106	8394	115	8644	104
7839	121	8051	4	8205	109	8397	47	8645	104
7840	124	8057	144	8208	40	8398	94	8650	71
7843	45	8059	74	8209	105	8413	147	8651	88
7846	106	8061	84	8210	149	8414	148	8652	9
7852	86	8069	123	8211	96	8417	107	8653	19
7854	81	8070	127	8212	96	8420	97	8654	79
7855	75	8071	68	8213	46	8423	100	8655	79
7856	84	8072	44	8214	71	8428	26	8663	140
7858	121	8074	45	8215	101	8429	92	8665	138
7867	33	8075	44	8216	75	8433	134	8667	131

RESTRICTED

RESTRICTED

168

RADIO RESISTORS AND MISCELLANEOUS SPARES

INDEX TO REFERENCE NUMBERS

SECTION 10W—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
8668	131	8817	115	9044	75	9228	70	9410	108
8676	87	8831	93	9045	80	9229	75	9411	104
8678	20	8832	68	9046	83	9230	73	9412	103
8683	21	8833	95	9047	86	9231	92	9414	31
8685	7	8834	94	9049	51	9235	97	9415	32
8686	18	8835	76	9050	127	9239	109	9416	139
8688	31	8840	51	9062	25	9240	49	9421	33
8689	146	8843	98	9063	25	9242	76	9438	112
8690	139	8845	48	9065	27	9245	25	9439	76
8691	145	8851	26	9066	28	9251	37	9443	12
8692	14	8858	85	9067	28	9256	38	9448	59
8693	79	8865	143	9068	27	9257	71	9450	108
8694	87	8867	71	9071	25	9258	72	9451	76
8696	134	8875	83	9078	26	9259	80	9452	71
8698	117	8876	120	9079	27	9260	139	9453	67
8701	129	8877	78	9080	24	9266	52	9466	2
8706	64	8878	84	9100	131	9267	100	9476	89
8710	45	8879	75	9109	4	9268	129	9477	99
8711	119	8880	86	9110	5	9270	74	9478	92
8712	71	8888	22	9119	17	9276	27	9479	113
8713	75	8891	72	9128	5	9277	26	9492	147
8715	83	8893	52	9129	9	9279	19	9493	31
8724	4	8895	112	9130	9	9284	15	9498	35
8725	1	8899	56	9131	11	9288	13	9503	33
8726	100	8905	46	9135	138	9291	87	9505	146
8727	104	8907	70	9136	10	9303	87	9506	146
8728	81	8913	21	9142	32	9304	87	9508	32
8729	114	8915	10	9148	107	9306	15	9513	87
8733	113	8924	96	9149	63	9310	87	9516	35
8734	113	8925	100	9150	138	9311	81	9518	37
8735	34	8926	102	9154	133	9313	85	9529	137
8736	34	8927	105	9158	9	9314	79	9533	124
8737	33	8928	75	9163	49	9315	70	9534	133
8738	33	8929	100	9164	131	9316	37	9536	120
8740	79	8931	78	9168	144	9321	144	9540	138
8741	76	8938	81	9169	140	9322	151	9544	56
8743	59	8942	63	9188	82	9323	130	9549	13
8744	60	8951	97	9189	89	9326	38	9550	10
8746	33	8961	21	9192	141	9328	85	9552	98
8749	33	8969	92	9193	82	9330	83	9553	72
8750	82	8974	81	9196	50	9331	75	9558	89
8751	82	8990	66	9199	43	9332	72	9560	67
8752	87	8991	66	9203	86	9333	68	9563	43
8753	59	8992	86	9204	80	9335	68	9564	44
8759	38	8995	77	9205	70	9336	67	9569	74
8765	34	8996	69	9207	75	9337	67	9570	108
8771	33	8997	77	9209	72	9338	151	9571	101
8772	112	9000	54	9212	17	9340	143	9579	53
8774	4	9001	58	9213	33	9348	49	9584	40
8776	78	9002	54	9214	33	9349	145	9587	37
8777	78	9003	95	9215	33	9350	15	9588	37
8778	69	9004	97	9216	34	9357	13	9596	115
8779	86	9005	97	9217	34	9362	51	9597	125
8781	92	9006	100	9218	34	9363	55	9599	20
8788	90	9007	60	9219	32	9367	62	9600	9
8802	38	9008	38	9220	32	9369	44	9616	77
8803	38	9010	81	9221	43	9370	54	9619	26
8807	35	9013	95	9222	107	9404	82	9621	15
8810	125	9014	95	9224	91	9406	85	9622	36
8811	119	9025	124	9225	104	9407	85	9623	37
8815	103	9040	41	9226	81	9408	77	9627	50
8816	1	9043	71	9227	88	9409	72	9633	11

RESTRICTED

RESTRICTED

Issued with A/L 41 to A.P. 1080—Book 4 (iii)

169

RADIO RESISTORS AND MISCELLANEOUS SPARES

INDEX TO REFERENCE NUMBERS

SECTION 10W—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
9635	120	10069	61	10577	35	10744	38	10962	32
9643	20	10070	145	10579	57	10768	143	10967	79
9644	21	10072	48	10581	33	10787	37	10968	136
9645	68	10077	49	10584	144	10789	70	10969	32
9647	81	10078	47	10587	129	10791	76	10971	32
9648	25	10079	50	10588	10	10793	99	10974	37
9649	27	10080	54	10589	157	10794	57	10976	129
9652	85	10096	32	10591	12	10795	37	10977	140
9653	87	10098	66	10592	33	10796	37	10979	126
9660	79	10104	60	10599	128	10797	49	10982	124
9663	81	10139	13	10608	84	10807	117	10987	78
9664	87	10143	44	10610	79	10812	32	10990	139
9667	32	10160	17	10612	67	10817	127	10993	79
9668	18	10206	4	10614	95	10834	1	10997	96
9680	90	10253	93	10617	71	10836	68	11042	158
9687	4	10295	157	10619	42	10837	2	11044	158
9689	1	10306	15	10620	48	10840	95	11049	153
9720	74	10327	81	10631	71	10845	3	11104	147
9721	73	10328	84	10632	144	10849	59	11109	94
9726	145	10336	4	10633	137	10851	5	11110	72
9734	52	10356	151	10634	135	10853	47	11158	153
9738	146	10365	6	10635	136	10854	46	11159	153
9739	70	10366	6	10636	130	10855	59	11160	153
9742	17	10372	8	10639	133	10862	9	11164	153
9746	1	10373	10	10640	112	10863	36	11165	153
9747	20	10383	17	10641	47	10864	10	11306	153
9757	2	10409	28	10642	49	10865	12	11307	153
9759	21	10413	14	10654	75	10874	16	11308	153
9761	17	10414	15	10659	44	10880	19	11309	4
9762	13	10417	114	10660	84	10894	1	11310	153
9763	117	10427	32	10662	74	10899	12	11319	124
9768	3	10429	32	10663	69	10904	146	11353	153
9803	136	10433	32	10665	140	10905	92	11379	13
9810	48	10442	31	10666	130	10910	135	11380	17
9815	47	10450	33	10667	66	10915	63	11381	16
9817	50	10454	33	10672	78	10917	93	11383	18
9818	56	10484	83	10675	80	10918	43	11385	21
9823	62	10495	36	10677	72	10919	67	11431	153
9828	141	10497	134	10678	88	10921	79	11454	153
9841	55	10501	31	10679	63	10922	99	11477	19
9842	41	10502	31	10680	15	10923	74	11492	14
9845	118	10503	31	10681	5	10924	84	11506	153
9846	123	10515	143	10682	139	10925	78	11507	153
9861	48	10516	141	10685	94	10928	84	11508	153
9862	59	10518	95	10690	92	10929	91	11509	153
9863	58	10523	82	10691	108	10930	105	11510	153
9865	55	10525	41	10692	67	10931	92	11513	153
9866	36	10526	91	10693	102	10934	42	11514	154
9878	28	10527	99	10695	106	10935	102	11539	158
9926	12	10530	121	10696	95	10936	84	11570	85
9927	12	10531	78	10698	16	10938	32	11581	158
9930	147	10535	59	10706	96	10946	37	11585	158
9931	135	10536	105	10708	1	10947	38	11586	158
9932	144	10538	100	10709	79	10949	146	11589	158
9933	146	10540	50	10711	20	10950	128	11590	158
9935	143	10541	46	10714	77	10952	99	11591	158
9954	18	10542	14	10719	100	10954	33	11596	154
10003	54	10547	157	10721	93	10956	75	11597	154
10030	31	10548	96	10731	98	10957	86	11598	154
10062	44	10549	157	10732	98	10959	81	11599	154
10066	31	10557	75	10733	128	10960	66	11600	154
10067	49	10561	23	10734	51	10961	88	11602	154

RESTRICTED

170

RADIO RESISTORS AND MISCELLANEOUS SPARES

INDEX TO REFERENCE NUMBERS

SECTION 10W—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
11606	154	12005	154	13136	155	15043	41	15120	70
11608	154	12038	154	13230	155	15045	131	15121	69
11614	158	12048	154	13231	155	15046	77	15122	66
11616	145	12049	154	13232	155	15047	5	15123	64
11626	12	12050	154	13365	159	15048	13	15124	64
11629	9	12052	154	13402	159	15049	5	15125	47
11645	154	12058	160	13465	155	15052	40	15126	84
11646	154	12059	154	13510	159	15053	82	15127	57
11647	154	12060	160	13511	159	15056	44	15128	45
11648	154	12110	158	13512	159	15057	81	15130	104
11649	154	12111	154	13686	159	15058	82	15132	120
11651	158	12112	154	13687	159	15059	50	15133	115
11666	6	12191	154	13735	23	15060	97	15134	120
11668	9	12192	154	13888	159	15061	73	15135	36
11669	10	12193	154	13889	159	15062	102	15137	60
11670	11	12194	154	13898	159	15063	99	15138	43
11672	14	12195	155	13932	159	15064	40	15139	48
11673	18	12198	158	13981	159	15065	45	15140	135
11675	20	12217	158	13982	159	15066	44	15141	132
11677	21	12218	155	13989	159	15067	51	15145	113
11679	9	12219	155	14022	160	15068	51	15146	112
11680	10	12220	158	14023	160	15069	61	15147	112
11681	10	12221	158	14028	159	15070	53	15148	123
11682	11	12362	155	14029	159	15071	41	15149	123
11684	14	12363	155	15000	139	15072	44	15150	87
11685	3	12382	154	15001	101	15073	38	15151	76
11686	15	12453	158	15002	80	15080	96	15153	80
11687	16	12454	158	15003	75	15081	95	15157	66
11688	17	12460	155	15004	70	15082	150	15158	73
11689	17	12464	155	15005	77	15083	133	15159	142
11690	17	12465	158	15006	102	15084	151	15160	144
11692	18	12466	158	15007	102	15085	77	15162	134
11699	45	12467	158	15008	106	15086	92	15163	148
11700	46	12527	155	15009	66	15087	24	15164	28
11701	47	12528	155	15010	49	15088	86	15165	87
11702	46	12529	155	15011	1	15089	77	15166	151
11703	48	12531	155	15012	55	15090	77	15167	151
11704	49	12532	155	15015	17	15091	86	15168	151
11705	49	12533	155	15016	15	15092	80	15170	73
11720	158	12534	155	15017	7	15093	86	15171	96
11721	158	12535	155	15018	18	15094	123	15172	105
11723	112	12575	159	15019	99	15096	70	15173	49
11724	154	12602	159	15020	49	15097	67	15174	125
11741	154	12603	155	15021	50	15098	67	15175	119
11768	154	12624	159	15022	105	15192	62	15176	59
11769	154	12625	159	15023	46	15103	61	15177	50
11789	129	12632	159	15024	149	15104	61	15179	47
11803	5	12642	155	15025	53	15105	74	15180	48
11807	154	12651	155	15026	23	15106	108	15183	145
11808	154	12652	155	15027	80	15107	112	15184	128
11809	154	12700	155	15028	80	15108	83	15185	125
11864	154	12701	155	15029	82	15109	139	15186	127
11865	154	12702	155	15030	70	15110	4	15187	137
11866	154	12703	155	15032	84	15111	128	15188	144
11869	154	12741	155	15033	88	15112	5	15190	118
11928	154	12935	144	15034	90	15113	66	15191	41
11983	158	13000	155	15035	32	15114	31	15192	57
11984	158	13053	159	15037	99	15115	60	15193	52
11985	158	13096	159	15038	100	15116	104	15194	61
11986	158	13127	155	15039	105	15117	91	15195	52
11987	158	13128	155	15041	68	15118	82	15196	48
11991	158	13131	155	15042	83	15119	76	15197	55

RESTRICTED

Issued with A/L 41 to A.P. 1086—Book 4 (iii)

171

RADIO RESISTORS AND MISCELLANEOUS SPARES

INDEX TO REFERENCE NUMBERS

SECTION 10W—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
15198	59	15277	57	15372	27	15450	114	15523	149
15199	60	15278	78	15373	28	15451	108	15526	42
15200	50	15279	75	15374	62	15452	102	15527	58
15201	139	15280	69	15375	40	15453	94	15529	53
15202	140	15283	108	15378	49	15454	58	15530	58
15205	43	15285	82	15380	59	15456	95	15531	144
15206	40	15286	137	15381	52	15457	105	15533	120
15208	118	15287	71	15382	52	15458	88	15535	72
15209	22	15288	146	15384	47	15463	60	15536	92
15210	127	15289	147	15385	61	15464	116	15537	78
15211	52	15290	147	15386	44	15465	6	15539	82
15212	110	15292	149	15387	43	15466	6	15540	65
15213	102	15293	44	15388	37	15467	8	15541	45
15214	120	15297	51	15390	4	15468	43	15542	70
15215	64	15298	51	15391	43	15470	70	15543	138
15216	80	15299	45	15393	109	15471	85	15544	140
15217	74	15301	52	15394	101	15472	55	15545	126
15218	148	15302	132	15395	103	15473	51	15546	125
15219	42	15303	42	15397	100	15474	45	15547	36
15220	44	15306	109	15398	60	15476	91	15548	45
15221	44	15307	101	15399	92	15477	40	15549	140
15222	59	15310	130	15400	105	15478	113	15550	117
15223	36	15311	130	15401	100	15479	112	15551	146
15224	55	15312	109	15403	51	15482	92	15553	117
15225	61	15313	108	15404	143	15483	59	15554	138
15226	54	15314	145	15405	40	15484	98	15555	160
15227	21	15315	147	15407	40	15485	99	15558	120
15228	10	15316	141	15411	87	15486	37	15559	11
15230	85	15320	133	15412	28	15487	37	15560	113
15231	87	15321	142	15413	68	15488	90	15561	115
15232	109	15324	71	15414	44	15490	103	15562	118
15233	86	15327	62	15415	77	15491	42	15563	123
15234	51	15328	49	15416	75	15492	121	15567	3
15235	103	15329	86	15417	74	15493	51	15568	2
15236	42	15330	143	15418	53	15494	12	15570	40
15237	4	15331	49	15419	70	15495	57	15572	66
15240	23	15332	110	15420	81	15496	73	15574	89
15241	26	15333	101	15421	54	15497	61	15577	74
15242	29	15335	24	15422	88	15498	89	15578	63
15243	70	15336	147	15423	118	15499	82	15579	129
15244	74	15337	58	15424	130	15500	5	15580	124
15245	3	15338	68	15425	115	15501	7	15581	131
15247	127	15340	15	15426	118	15502	13	15582	128
15248	14	15343	10	15427	118	15503	3	15583	125
15249	44	15349	24	15428	123	15504	2	15584	9
15250	144	15350	18	15429	114	15505	82	15585	8
15251	117	15351	11	15430	67	15506	6	15586	11
15252	146	15352	14	15431	70	15507	146	15587	8
15253	133	15353	14	15432	72	15508	56	15590	3
15254	106	15354	12	15433	129	15509	76	15592	139
15255	85	15356	18	15434	128	15510	76	15593	54
15256	123	15357	12	15435	84	15511	58	15605	68
15260	95	15359	13	15436	141	15512	41	15606	53
15261	56	15360	21	15437	124	15514	146	15607	55
15262	63	15361	16	15438	128	15515	69	15609	57
15263	139	15362	4	15439	44	15516	95	15610	61
15264	136	15364	69	15440	46	15517	128	15611	137
15265	138	15365	94	15441	126	15518	57	15612	117
15270	19	15367	99	15442	113	15519	59	15619	132
15271	67	15368	24	15443	54	15520	62	15620	92
15272	95	15370	28	15447	71	15521	134	15621	94
15273	93	15371	29	15449	140	15522	93	15622	46

RESTRICTED

RESTRICTED

RADIO RESISTORS AND MISCELLANEOUS SPARES

INDEX TO REFERENCE NUMBERS

SECTION 10W—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
15623	61	15693	123	15782	121	15864	83	15942	137
15624	76	15694	122	15783	90	15865	107	15943	56
15625	76	15695	122	15784	48	15866	89	15944	47
15626	81	15696	120	15785	71	15867	70	15945	48
15627	69	15697	120	15787	107	15868	100	15946	46
15628	71	15698	110	15788	13	15870	37	15947	45
15629	72	15699	118	15793	53	15871	55	15948	48
15630	79	15700	117	15795	85	15873	101	15950	93
15631	76	15701	116	15796	63	15874	44	15952	57
15633	47	15702	2	15798	155	15875	48	15953	50
15634	55	15703	143	15799	103	15876	47	15955	78
15635	82	15705	63	15800	77	15877	65	15956	66
15636	90	15706	28	15801	87	15878	136	15957	74
15637	94	15707	28	15802	98	15880	79	15958	72
15640	114	15710	26	15803	100	15881	114	15959	92
15641	116	15713	93	15804	107	15882	121	15960	100
15642	117	15714	120	15805	95	15883	159	15961	116
15643	118	15716	114	15806	115	15885	36	15962	43
15644	121	15717	49	15807	31	15886	51	15963	40
15645	124	15718	52	15808	119	15887	85	15964	41
15646	120	15719	113	15809	122	15888	85	15965	79
15647	101	15720	57	15810	122	15889	68	15966	134
15648	32	15721	128	15811	145	15891	141	15967	90
15649	127	15722	159	15814	31	15893	6	15968	143
15650	43	15724	88	15815	31	15895	1	15971	94
15651	41	15725	85	15816	31	15896	2	15972	130
15652	45	15726	73	15817	144	15900	13	15975	64
15653	49	15727	109	15818	141	15904	9	15977	55
15654	114	15728	125	15819	120	15907	93	15981	90
15655	25	15729	62	15820	38	15908	117	15982	102
15656	60	15730	125	15821	38	15909	119	15983	147
15657	61	15732	23	15822	38	15910	121	15986	90
15658	62	15733	24	15823	38	15911	122	15987	90
15659	53	15734	23	15824	38	15912	122	15988	52
15660	107	15736	23	15825	38	15913	123	15989	87
15661	138	15737	27	15826	38	15914	123	15991	49
15662	96	15739	136	15828	37	15915	112	15992	124
15663	68	15740	49	15829	38	15916	113	16010	121
15664	81	15741	47	15830	49	15917	129	16011	131
15665	68	15742	40	15831	64	15918	114	16012	50
15666	66	15744	156	15832	99	15919	115	16013	159
15667	74	15748	59	15833	101	15920	115	16014	161
15668	101	15749	53	15834	47	15921	115	16017	41
15669	108	15750	132	15835	131	15922	116	16018	120
15670	107	15751	13	15836	131	15923	116	16019	159
15671	56	15753	42	15838	129	15924	117	16022	92
15673	45	15756	155	15840	126	15925	40	16024	157
15677	124	15761	28	15841	41	15926	120	16028	114
15678	86	15762	52	15842	68	15927	46	16029	137
15679	82	15763	54	15845	26	15928	43	16032	42
15680	74	15764	107	15846	37	15929	60	16033	89
15681	70	15765	52	15849	24	15930	72	16034	101
15683	36	15766	129	15853	127	15931	70	16035	122
15684	54	15768	129	15854	47	15932	91	16036	114
15685	42	15770	129	15855	84	15933	96	16037	118
15686	51	15771	143	15856	76	15934	92	16038	98
15687	42	15772	142	15857	73	15935	106	16039	108
15688	44	15773	146	15858	79	15936	130	16040	28
15689	50	15777	55	15859	81	15937	107	16041	25
15690	127	15779	56	15860	62	15938	62	16042	26
15691	57	15780	57	15861	89	15940	83	16043	26
15692	55	15781	93	15862	81	15941	94	16045	26