




T. DOLAN.
Wheelbarrow.

No. 217,864.

Patented July 29, 1879.



Witnesses

Attest, I think
Charles Secknick.

Thomas Dolan
Inventor.

UNITED STATES PATENT OFFICE.

THOMAS DOLAN, OF ALBANY, NEW YORK.

IMPROVEMENT IN WHEELBARROWS.

Specification forming part of Letters Patent No. **217,864**, dated July 29, 1879; application filed September 20, 1878.

To all whom it may concern:

Be it known that I, THOMAS DOLAN, of the city and county of Albany, in the State of New York, have invented certain new and useful Improvements in Wheelbarrows, which improvements are fully described in the following specification and the accompanying drawings, in which—

Figure 1 represents a side elevation of a wheelbarrow embodying the improvements in this invention. Fig. 2 is a sectional elevation of the improved parts of the wheelbarrow, illustrating one form of the construction of the same; and Fig. 3 is a sectional elevation illustrating another form of construction of the improved parts.

My invention relates to wheelbarrows having pivoted or hinged legs; and consists in combining with the side bars, rails, or handle-bars of the wheelbarrow a pair of swinging or hinged or pivoted legs in such a manner that when the side handle-bars are raised the said hinged legs will hang vertically from the same, and will be made to operate as fulcrums, by which the wheel end of the barrow may be elevated, and at the same time permit the operator to project the entire body of the barrow forward with its wheel elevated, so as to readily surmount a sudden elevation, as, for instance, the curb-stone of a sidewalk of a street.

In the drawings, A represents a side bar or handle-bar of the wheelbarrow. B is the wheel, and C is one of the legs.

The said legs are pivoted or hinged to the handle-bars A, as shown in Fig. 1 by full lines, each leg being pivoted or hinged to its side handle-bar at a point back from the wheel equal to about one-half of the length of the said bars, or more or less, as selected.

The exact form of the construction of the hinge or device for pivoting the legs to the bar is not essential, as it may be variously constructed. In cheap barrows the legs C may be made to have a hinge connection with the bars by forming in the lower side of the handle-bars mortises, in which the upper ends of the legs may enter, and be secured by pins or bolts *a*, as shown in Fig. 1.

If desired, the said mortises may be made to consist of metal sockets D, Fig. 2, which sockets

may be let into the lower sides of the handle-bars, as shown in said figure by full lines, or be secured to the lower sides of said bars, as shown by dotted lines in said figure; and in either case the legs, which may be made of either iron or wood, are to have their upper ends inserted in the said sockets, and secured by the pivot *a*, as shown. This mode of construction is simple, and permits the legs to readily swing from the inclined position (shown by full lines) to a vertical position (shown by dotted lines in the same figure,) while at the same time the legs are prevented from folding under and toward the handle ends of the bars by the rear portion, *b*, of the sockets bearing against the rear portion of the legs, as at *c*.

Another form of construction that may be used is shown in Fig. 3, which consists of a hinge, E, having one part secured to the side handle-bar A, and the other portion to the upper end of the leg, while the end of the leg is made with a bevel to bear against the lower side of the handle-bar A, and cause the leg to incline outward and downward, as shown, to prevent folding under or back.

The manner in which my invention is to be operated is as follows: The operator will hold the barrow by its handles the same as with barrows of ordinary construction, and will lift the handled end until the lower ends of the legs are clear from the ground, as shown by leg C¹ in dotted lines in Fig. 1, when the said leg will swing from the inclined position shown by full lines in Fig. 1 to that of dotted lines C¹ in the same figure. When the wheel B meets an obstacle, such as a stone, S, the operator will lower the handled end of the barrow from position of A¹ to that of A², when the lower end of the leg will bear on the ground, and at the same time stand vertical as leg C². (Shown by dotted lines in Fig. 1.) When the barrow is in this position, with its wheel against the obstacle S, and the leg standing vertically and bearing on the ground, the operator will bear down on the handles of the barrow, and throw the same down from dotted lines A² to that of A³, and at the same time push the barrow forward to the position of dotted lines A³ and B', when the wheel B will be at once elevated and landed forward to the top

of the obstacle S, as shown, the leg acting as a fulcrum, and also as a lever to aid to carry the barrow forward. The lower ends of the legs I would, in all cases, connect by a bar, e, running across from one leg to the other, which connection of the legs will cause both to swing uniformly as well as brace each other.

I do not claim a wheelbarrow provided with folding sides and a dropping tail-board, and having a pair of pivoted supports for said tail-board, said supports being connected by brace-bars to notched bars, as shown in the patent of H. Lawrence, July 18, 1871, No. 117,085; but

What I do claim is—

In a wheelbarrow, the combination of the side bars with the legs pivoted thereto, and capable of a limited motion forward and backward, whereby the wheel may be raised and forced forward over an obstacle by pressure on the handles.

THOMAS DOLAN.

Witnesses:

ALEX. SELKIRK,
CHARLES SELKIRK.