

J. HAUX.

HANGER FOR CURTAINS AND SHADES.

No. 301,120.

Patented July 1, 1884.





 \mathcal{B}

Witnesses: Roft H. Roy. Sermann States Inventor: Johannes Haux by his attorney Dankstrilen

United States Patent C

JOHANNES HAUX, OF MUNICH, BAVARIA, GERMANY.

HANGER FOR CURTAINS AND SHADES.

SPECIFICATION forming part of Letters Patent No. 301,120, dated July 1, 1884.

Application filed December 17, 1883. (No model.)

To all whom it may concern:

Be it known that I, JOHANNES HAUX, of Munich, Germany, have invented a new and Improved Hanger for Curtain and Shade 5 Rods, of which the following specification is a full, clear, and exact description.

This invention relates to an adjustable hanger for window-shades and curtain-rods, which, once in place, will allow rods of different 10 lengths to be attached to the window.

The invention consists, principally, in the combination of a window-frame and curtainmolding with hangers adapted to be fastened thereto, and perforated to receive a rod that 15 carries adjustable brackets for supporting the shade-roller.

The invention also consists in the details of construction, hereinafter more fully pointed

In the accompanying drawings, Figure 1 is 20 a front view of my improved hanger with the curtain-rod removed. Fig. 2 is a bottom view of the same, showing it broken off to show one side of the window only. Fig. 3 is a side 25 view of one of the hangers.

Similar letters of reference indicate corre-

sponding parts in all the figures.

The letter A represents the upper portion of a window-frame, and B the wooden mold-30 ing usually attached to the same for holding the curtain. The molding B is situated, as customary, a considerable distance in front of

C Care the hangers proper, for supporting the 35 curtain and shade rods $a\ b$. The hangers are situated, one near the right and one near the left side of the window-frame. They are each provided with one downwardly - projecting lug, fitting into an eye, d, on frame A, and 40 with one upwardly-projecting lug, e, which may be clamped between back of molding B and a plate, \dot{f} . This plate travels on pins gg, and may be tightened or loosened by nuts h.

The hangers C are perforated to permit the insertion of the rod \hat{a} , to which the curtain is 45 to be affixed directly by sliding rings, or otherwise, in place of being affixed to the molding B. The rod b likewise rests in hangers C, and upon it slide brackets i, which sustain the shade-roller. These brackets may be clamped 50 to rod b, and held at any suitable distance from each other. The brackets i are preferably made knee-shaped, as shown in Fig. 3. At or near their bend they are perforated to receive the axle of a spring shade-roller, j. 55 If an ordinary roller is to be used in place of the spring shade-roller, the same is attached to a plate, k, fastened to the end of bracket i. The plate k is perforated at l, to allow the string that operates the shade to pass through.

I claim as my invention— 1. The combination of window-frame A and molding B with the hangers C, adapted to be fastened thereto, and perforated to receive the rod b, carrying adjustable brackets i, substan- 65

tially as specified.

2. The combination of window frame A, having eye d, with the molding B, having pins g, plate f, and nuts h, and with the brackets C, having lugs for attachment to said frame 70 and molding, substantially as specified.

3. The combination of hangers C, having means for attachment to a window-frame, with the rod b, supported in said hangers, and carrying perforated brackets i, having plates k, 75

substantially as specified.

4. The combination of hangers C, adapted to be fastened to a window-frame, with the rods a b and sliding knee - shaped brackets i, having perforated plate k, substantially as and 80 for the purpose specified.

JOHANNES HAUX. [L. S.]

In presence of— Jos. W. HARPER, EMIL HENZEL.