

F. W. MIX.
Hasp for Trunk-Locks.

No. 163,230.

Patented May 11, 1875.

Fig. 1.





Fig. 2.



Witnesses.
Henry A. Mitchell
Henry B. Cook

Inventor.
Frank W. Mix.
By James Shepard Atty.

UNITED STATES PATENT OFFICE.

FRANK W. MIX, OF TERRYVILLE, CONNECTICUT, ASSIGNOR TO THE EAGLE LOCK COMPANY, OF SAME PLACE.

IMPROVEMENT IN HASPS FOR TRUNK-LOCKS.

Specification forming part of Letters Patent No. **163,230**, dated May 11, 1875; application filed April 20, 1875.

CASE A.

To all whom it may concern:

Be it known that I, FRANK W. MIX, of Terryville, in the county of Litchfield and State of Connecticut, have invented certain new and useful Improvements in Trunk-Hasps, of which the following is a specification:

The nature of my invention consists of the peculiar construction of the parts which form the joint, all as hereinafter described.

In the accompanying drawing, Figure 1 is an elevation of the rear side of a trunk-hasp which embodies my invention, and Fig. 2 is a similar view of two parts of the same detached from each other.

A designates the upper portion, to which the hasp B is hinged. This portion A is provided with recesses *a a*, sunk upon its inner face, as shown in Fig. 2. The hasp B is formed of cast metal, and its hub *b* is cast hollow, except a small portion at each end, which portions I term ears *c c*, the hollow in the hub being of such size as to allow ample room for the pintle *d*. The ears *c c* are drilled out at their centers, the holes therein being of such size that the pintle *d* fits easily, so as to allow the hasp to turn on it. The pintle *d* is of such length as to project a short distance at each

end of the hub *b*, and when inserted therein, as shown in Fig. 2, it is placed with its ends within the recesses *a a* of the upper portion A, and a sheet-metal plate, C, slotted, so as to allow free play of the ears *c c*, is riveted firmly to the upper portion A, to hold said portion and the hasp B together. The recesses *a a* should be so shallow that the plate C may come close to or bear upon the pintle *d*, and hold it so firmly that it will not rattle, and, preferably, so as to hold the pintle *d* so tight that it will not revolve, in which case the hasp B will turn upon it.

This construction is not only cheap and substantial, but it makes a snug joint that always works freely.

I claim as my invention—

In a trunk-hasp, the hasp B, provided with the hub formed of the parts *c b c*, as shown and described, in combination with the pintle *d*, upper portion A *a a*, and the plate C, all substantially in the manner specified.

FRANK W. MIX.

Witnesses:

ELISHA MIX,
WM. B. ELLS.