
J. P. HILL. Clothes-Drier.

No. 165,674.

Patented July 20, 1875.



Mitriesses:

A. Stimson Chaswooder.

Inventor: Joseph P. Hill Per T. J. Deavett Atty.

UNITED STATES PATENT OFFICE

JOSEPH P. HILL, OF BARRE, VERMONT.

IMPROVEMENT IN CLOTHES-DRIERS.

Specification forming part of Letters Patent No. 165,674, dated July 20, 1875; application filed January 4, 1875.

To all whom it may concern:

Be it known that I, JOSEPH P. HILL, of Barre, in the county of Washington and State of Vermont, have invented a new and useful Improvement in Clothes-Driers, of which the following is a specification:

In the accompanying drawing, which forms a part of this specification, Figure 1 is a perspective view of my improved clothes drier expanded. Fig. 2 represents my clothes drier folded and detached from the upright post. Fig. 3 shows the construction of the head C.

Similar letters of reference indicate corre-

sponding parts.

The object of my invention is to furnish an improved clothes drier, simple in its construction, and convenient in use, and which may be securely held when expanded to any designed extent; and it consists in the construction and combination of various parts, as hereinafter more fully described.

A represents an upright post, surmounted by a revolving hub, B, to which are pivoted the lower end of arms a a a, through which are passed cords e e, upon which the clothes are hung. C represents a head, having radial arr a' a', open-slotted to receive the inner ends the stretcher-rods b b, while the outer ends said rods are attached to arms a a, as show in the drawings. D is an arched stop, place between the pivoted points in such a mann that by the mutual pressure of the stretcher ods b b upon the head C, while resting uparched stop D, serves to lock and firmly ho the drier expanded for use.

By raising head C the drier is thereby easi and quickly folded, as is shown in Fig. 2 of t

drawing.

Having thus described my invention, Iclai as new and desire to secure by Letters Pa ent—

The head C, having radial arms a', ope slotted to receive the ends of stretcher-rods and provided with arched stops, placed t tween the pivotal points, all as and for tl purpose described.

JOSEPH P. HILL.

Witnesses:

THOMAS J. DEAVITT, LAFAYETTE RICHARDSON.