


EMMA C. McCUTCHINS.

DOLL SUPPORTER.

No. 180,613.

Patented Aug. 1, 1876.



WITNESSES:

*John Kemou*  
*J. W. Hart*

INVENTOR:

*Emma C. McCutchins*

BY

*Wm. T. E.*

ATTORNEYS.

# UNITED STATES PATENT OFFICE.

EMMA C. McCUTCHINS, OF WASHINGTON, DISTRICT OF COLUMBIA.

## IMPROVEMENT IN DOLL-SUPPORTERS.

Specification forming part of Letters Patent No. **180,613**, dated August 1, 1876; application filed June 15, 1876.

*To all whom it may concern:*

Be it known that I, EMMA C. McCUTCHINS, of Washington city, District of Columbia, have invented a new and Improved Doll-Supporter; and I do hereby declare that the following is a full, clear, and exact description of the same, reference being had to the accompanying drawing, forming part of this specification, in which—

The object of my invention is the construction of a device for holding dolls in an upright or standing position; and it consists of a metallic ring or girdle, to surround the waist of the doll, attached to legs made of stout wire, with their lower ends bent outward, and flattened to form feet. The girdle is closed upon the waist of the doll by means of a string or pin passing through opposing holes in its ends, which are free. By means of these holes, the device is rendered adjustable to dolls of different sizes. Attached to the rear of the girdle is an upright back piece or support, provided with holes through which strings are passed, and tied over the breast of the doll. In place of these strings rubber bands may be slipped over both the doll and back-support.

In the drawing, A represents my invention, of which B B are the wire legs fixed above to the waist ring or girdle C, and having their lower ends bent outward, and flattened to form feet. The metallic ring or girdle C surrounds the waist of the doll, and has its ends free and provided with various holes *c c*, through

any two opposing ones of which a string is passed and tied on the outer side, thus making the device adjustable to dolls of different sizes. In place of the string, a securing-pin may be passed through any two opposing holes. D is the back piece or support fixed to the rear of the girdle, and provided with the holes *d d*, through which pass strings E E, that are tied over the breast of the doll. These strings secure the doll in place in the device, with its back resting against the support D. In place of the strings E E, rubber bands may be slipped over both the doll and back support, or the strings themselves may be of rubber.

Having thus described my invention, what I claim as new is—

1. In a device for holding dolls, the metallic waist band or girdle C, provided with holes *c c* near its ends, for attachment of a string or securing-pin, and combined with the legs B B, substantially as and for the purpose herein set forth.

2. In a device for holding dolls, the back pieces or supports D, provided with the holes *d d*, and combined with the girdle C and legs B B, substantially as and for the purpose herein set forth.

The above specification of my invention, signed by me this 10th day of June, 1876.

EMMA C. McCUTCHINS.

Witnesses:

SOLON C. KEMON,  
CHAS. A. PETTIT.