
G. W. LASCELL.

FASTENINGS FOR SHOES, GLOVES, &c.

No. 181,187.

Patented Aug. 15, 1876.



Witnesses

Charles Singles Harold Terrell Inventor

George W. Scuscell Ger Lemmel W. Gerrell

N. PETERS, PHOTO-LITHOGRAPHER, WASHINGTON D. C.

UNITED STATES PATENT OFFICE.

GEORGE W. LASCELL, OF SYRACUSE, NEW YORK.

IMPROVEMENT IN FASTENINGS FOR SHOES, GLOVES, &c.

Specification forming part of Letters Patent No. 181,187, dated August 15, 1876; application filed April 6, 1876.

To all whom it may concern:

Be it known that I, GEORGE W. LASCELL, of Syracuse, in the county of Onondaga and State of New York, have invented an Improvement in Fastenings for Shoes, Gloves, and Clothing, of which the following is a

specification:

I make use of a metallic link, connected removably at one end to one part of the shoe or garment, and having at the other end a stud that passes through an eccentric slot in a plate that is fastened to the other part of the garment, so that the fastening is drawn up or tightened by moving the pin in the eccentric slot. This fastening is very strong, and can be made highly ornamental, either in

The link a is connected at one end to the part b of the shoe or garment, and at the other end is a pin, c, that passes into the eccentric slot d in the plate e, which is extended as a tongue, f, that is secured to the opposite part h of the shoe or garment. The pin c is formed with a head that can easily be grasped, so as to move the pin in the eccentric slot d_1 to tighten the fastening and draw the parts of the shoe together.

The link a is connected to the part b of the shoe by a stud, l, upon a base-plate that is permanently fastened to the shoe, and there is a slot in the link, a, enlarged at one end, so that the link can be lifted off the stud l when the shoe is to be opened.

The end of the link a may be made with a hook passing into an eyelet in the part b of the shoe or garment, instead of being attached

by the stud l.

This fastening is durable, strong, and cheap. The expense of button-holes is avoided, and the fastening can be drawn together more or less, as required, so as to accommodate the desires of the wearer.

I claim as my invention—

metal, rubber, horn, or other material.

In the drawing, Figure 1 is an elevation of the fastening. Fig. 2 is an edge view.

The link a, removably connected at one end to the part b of the shoe or garment, and prother fastening. Fig. 2 is an edge view. combination with the plate e, having a connecting-tongue, f, extending out from one side and containing an eccentric slot, d, for the stud c, substantially as set forth.

Signed by me this 3d day of April, A. D.

1876.

G. W. LASCELL.

Witnesses:

HAROLD SERRELL, CHAS. H. SMITH.