
## J. GILBERDS.

BUTTER PAIL.

No. 189,212.

Patented April 3, 1877.



## UNITED STATES PATENT OFFICE.

JAMES GILBERDS, OF JAMESTOWN, NEW YORK.

## IMPROVEMENT IN BUTTER-PAILS.

Specification forming part of Letters Patent No. 189,212, dated April 3, 1877; application filed January 13, 1877.

To all whom it may concern:

Be it known that I, JAMES GILBERDS, of Jamestown, in the county of Chautauqua and State of New York, have invented a new and Improved Butter-Pail, of which the following is a specification:

Figure 1 is a top view. Fig. 2 is a vertical section on line x x in Fig. 1.

Similar letters of reference indicate corresponding parts.

The invention will first be described in connection with the drawing, and then pointed out in the claim.

Referring to the drawing, A is a butter-pail, made in the ordinary way, except that a rabbet, a, is made at the inner side of the upper edge of the pail, to receive the cover B.

O is an L-shaped clip attached to the side of the pail, and extending over the cover a sufficient distance to retain it in the rabbet a. This clip may be formed of wrought or east iron, and it may be attached to the pail by nails, rivets, or screws.

D is a hasp, consisting of a piece of sheet metal, attached to the cover B, and bent downward at nearly a right angle, and provided with a slot, b, which slips over a hook or button, c, screwed into the side of the pail at a point opposite the clip C.

The edge of the cover B opposite the hasp D is placed in the rabbet a under the projecting portion of the clip C. The cover is then placed wholly in the rabbet, and at the same time the hasp D is sprung over the button c, and the button c is turned downward over the lower portion of the hasp.

To prevent the cover from swelling, I saturate it with paraffine or other waterproofing material.

Having thus described my invention, I claim as new and desire to secure by Letters Patent—

The combination of the pail A, having rabbet a and angular metallic clip C, and rotating button c, with the cover B, resting on the rabbet, with its top flush with the top of the pail, and having the angular and slotted springhasp D rigidly attached, all as set forth.

JAMES GILBERDS.

Witnesses:

BYRON A. BARLOW, JOHN LANGFORD.