

F. G. & W. F. NIEDRINGHAUS.

HINGES OF VESSELS OF ENAMELED IRON WARE.

No. 189,639.

Patented April 17, 1877.

FIG. 1.





FIG. 2.



ATTEST.

Paul Bakewell

Amos S. Boyd

INVENTORS.

Frederick G. Niedringhaus,
William F. Niedringhaus
by *Chas. S. Moody,*
their atty.

UNITED STATES PATENT OFFICE.

FREDERICK G. NIEDRINGHAUS AND WILLIAM F. NIEDRINGHAUS, OF
ST. LOUIS, MISSOURI.

IMPROVEMENT IN HINGES OF VESSELS OF ENAMELED IRON-WARE.

Specification forming part of Letters Patent No. **189,639**, dated April 17, 1877; application filed
April 2, 1877.

To all whom it may concern :

Be it known that we, FREDERICK G. NIEDRINGHAUS and WILLIAM F. NIEDRINGHAUS, residents of St. Louis, Missouri, have made a new and useful Improvement in Hinges of Vessels of Enameled Iron-Ware, of which the following is a full, clear, and exact description, reference being had to the annexed drawing, making part of this specification, in which—

Figure 1 is a perspective of the hinge, showing it as before attached; and Fig. 2, a vertical section of the hinge as attached, and showing that portion of the vessel immediately therewith connected.

Similar letters denote similar parts.

Our aim is to provide a neat, inexpensive, and durable hinge for vessels of enameled sheet-iron ware.

Referring to the annexed drawing, A represents the body of the vessel, and B its cover. These parts are coated with an enamel.

C represents the strap of the hinge. It is folded at its center around the wire *a*, (that usually encircles the top of the body of the vessel,) and its ends *c c* are then passed through a slot, *b*, in the cover, and then opened apart, as shown, and turned down upon the upper side of the cover. Solder D is then applied to and between the ends *c c*, as shown in Fig. 2, which serves, by becoming attached to the ends, to form a head on the strap, and to prevent its being withdrawn through the slot *b*. The strap is of a material to which solder attaches.

What we claim is—

The combination of the vessel A, wire *a*, cover B, having the slot *b*, strap C, and solder D, substantially as described and shown.

F. G. NIEDRINGHAUS.

WM. F. NIEDRINGHAUS.

Witnesses:

CHAS. D. MOODY,

SAML. S. BOYD.