

W. P. FERGUSON.
SHAWL-STRAP.

No. 192,246.

Patented June 19, 1877.





Fig. 1.

Fig. 2.



Witnesses:
William Hughes
Edward A. Woyle

Inventor:
W. P. Ferguson

UNITED STATES PATENT OFFICE.

WILLIAM P. FERGUSON, OF BROOKLYN, NEW YORK.

IMPROVEMENT IN SHAWL-STRAPS.

Specification forming part of Letters Patent No. **192,216**, dated June 19, 1877; application filed November 1, 1876.

To all whom it may concern:

Be it known that I, WM. P. FERGUSON, of Brooklyn, county of Kings, State of New York, have invented certain new and useful Improvements in Shawl-Straps, of which the following is a specification:

This invention relates to an improved retaining device for shawl straps, whereby a strap of leather, webbing, or embroidery may be used without perforating the same; and consists of a bar curved to form a handle, or a bar having a handle attached, bearing on each end of said bar, a flat plate of metal, having a longitudinal slot, to permit a right-angled lever to turn into the same, held in place by two raised ears attached to the ends of the plate, and by such operation describing a half-circle, forcing a strap at right angles against a serrated side of said longitudinal slot, to prevent slipping. To release the strap, the upper or longer part of said right-angled lever is raised by the fingers or an upward motion of the loose end of strap.

But, to describe my invention more particu-

larly, I will refer to the accompanying drawing, forming part of this specification, which shows the operation more in detail.

Figure 1 shows the plates in position, fastened to a flat bar. Fig. 2 is a transverse section cut through the line F F.

a is the flat plate, slotted longitudinally, having the raised ears *b b* attached thereto, holding the right-angled lever *c c*, which describes a half-circle, assuming the position *D*, to force a strap against the serrated side *e*.

What I claim, and desire to secure by Letters Patent, is—

A shawl-strap, consisting of a handled bar in combination with a right-angled lever, *c c*, revolving in raised ears *b b*, and the longitudinal slot having the serrated side *e*, all constructed to operate substantially as hereinbefore set forth.

WM. P. FERGUSON.

Witnesses:

WILLIAM HUGHES,
EDWARD A. DOYLE.