

M. B. MILLS.  
FEED-COOKERS.

No. 194,164.

Patented Aug. 14, 1877.





Fig. 2



WITNESSES:

*A. W. Almqvist*  
*Alex F. Roberts*

INVENTOR:

*M. B. Mills*  
BY *Munn & Co.*

ATTORNEYS.

# UNITED STATES PATENT OFFICE.

MORTIMER B. MILLS, OF DE WITT, IOWA.

## IMPROVEMENT IN FEED-COOKERS.

Specification forming part of Letters Patent No. **194,164**, dated August 14, 1877; application filed July 9, 1877.

*To all whom it may concern:*

Be it known that I, MORTIMER B. MILLS, of De Witt, in the county of Clinton and State of Iowa, have invented a new and Improved Feed-Cooker, of which the following is a specification:

This invention has relation to boilers for cooking feed for beasts; and the nature of my invention consists in the combination of a wooden barrel with a furnace, the fire-chamber of which is extended well up in the barrel and surrounded by the water therein, and the smoke-pipe is carried directly up through the top of the barrel.

My object is to have a shell which is a poor conductor of heat, and to obtain as large an amount of heating-surface in a given space as possible.

In the annexed drawings, Figure 1 is a vertical section through my improved feed-cooker. Fig. 2 is a section taken horizontally through the boiler.

Similar letters of reference indicate corresponding parts.

The letter B designates a barrel, which is strongly made, and constructed with openings *a a* through its head, for the purpose of introducing water and conducting off the steam. This barrel is mounted on a cylindrical furnace, A, in which is a grate, A', raised somewhat to allow the removal of ashes from beneath it.

This furnace A is provided with a door, N, to which a register may be applied for regulating the draft.

C designates a fire-chamber, which is a continuation of the furnace, and which is constructed within the barrel B, as shown in Fig. 1. This fire-chamber is cylindrical, and it extends up about half-way of the length of the barrel. From its crown rises a chimney, C', which is carried up through the head of the barrel.

For the purpose of creating a very rapid circulation of water in the barrel, and also to obtain a large heating-surface, the fire-chamber is of less diameter than the interior of the barrel, so that a water circulating and heating space, *g*, is left.

From this space *g* pipes D are carried into the fire-chamber and out of its crown, which pipes are of an angular shape, as shown.

Having thus described my invention, I claim as new and desire to secure by Letters Patent—

In combination with a wooden barrel, B, the furnace A, fire-chamber C, pipes D, and chimney C', constructed and arranged substantially in the manner described.

MORTIMER B. MILLS.

Witnesses:

N. A. MERRELL,  
ROBERT HOWAT.