

B. ELLIOTT. String-Holder.

No. 207,857.

Patented Sept. 10, 1878.







WITNESSES

Francis Molerate.

INVENTOR

13. Elliott

ATTORNEYS.

UNITED STATES PATENT OFFICE.

BENTON ELLIOTT, OF ELLSWORTH, WISCONSIN.

IMPROVEMENT IN STRING-HOLDERS.

Specification forming part of Letters Patent No. 207,857, dated September 10, 1878; application filed February 25, 1878.

To all whom it may concern:

Be it known that I, Benton Elliott, of Ellsworth, in the county of Pierce and State of Wisconsin, have invented a new and Improved String-Holder, of which the following is a specification:

In the accompanying drawings, forming part hereof, Figure 1 is a longitudinal section of my improved string-holder, taken on line x x in Fig. 2. Fig. 2 is a plan view, and Fig. 3 is an end elevation.

Similar letters of reference indicate corre-

sponding parts.

The object of my invention is to provide a holder for strings used in tying packages or bags, and for holding shoe-strings, so that one at a time may be removed from a bunch without snarling those that remain.

In the drawings, A is a base-plate, having a square boss, b, to opposite sides of which two springs, c, are secured by a rivet. The free ends of the springs, which are made convex, are in contact with each other. A square sleeve, d, is loosely fitted to the springs, and is provided with thumb-pieces d' d', which en-

gage the spiral spring e, that surrounds the springs e, and rests against the base-plate A.

A wedge-shaped block, f, is fitted between the spring c and secured to the sleeve d, and slides with it along the springs c. The base-plate A is secured to some solid object, and the strings are placed between the springs c by drawing back the sleeve d and introducing the strings between the free ends of the springs c. The sleeve is then allowed to press against the strings, and the strings may be drawn one by one from between the springs c without snarling those that remain.

Having thus described my invention, Iclaim as new and desire to secure by Letters Pat-

ent-

A string-holder consisting of a base-plate, A, the springs c, having convex ends, and a spring-acted sleeve, d, combined substantially as herein shown and described.

BENTON ELLIOTT.

Witnesses:

C. W. BROWN, DAVID MCNOAH,