D23-346

ΩE

D 9,320

DESIGN.

W. W. STANARD.

N.o. 9,320.

PARLOR STOVE.
Patented May 30, 1876.



Netwers. J. H Rook Ela Withelia

Walter W. Stanard atty, Edw. Wilhelm!

UNITED STATES PATENT OFFICE.

WALTER W. STANARD, OF BUFFALO, NEW YORK, ASSIGNOR TO JEWETT & ROOT, OF SAME PLACE.

DESIGN FOR PARLOR-STOVE.

Specification forming part of Design No. 9,320, dated May 30, 1876; application filed May 10, 1876. [Term of Patent 7 years.]

To all whom it may concern:

Be it known that I, WALTER W. STANARD, of the city of Buffalo, in the county of Erie and State of New York, have invented and produced a new and original Design for Parlor-Stoves, of which the following is a full, clear, and exact description, reference being had to the accompanying photographic illustration, making part of this specification.

My invention relates to a design for the general configuration and ornamentation of a

parlor-stove of cast-iron.

The nature of my design is fully represented in the accompanying photographic illustration, to which reference is here made.

A represents the top cover; B, the top ring; C, the ring connecting the latter with the case D surrounding the magazine; E, the frame of the combustion-chamber; F, the mica windows arranged in the doors thereof; G, the frame surrounding the fire-pot, and H the mica doors thereof; I, the top plate of the ash-pit; K, the case of the latter; L, the door thereof; M, the base-plate, and N the legs of the stove.

The top cover of A is provided with an ornamental hexagonal urn or vase, a, having handles a', the lower parts of which are made perpendicular, while their upper portions are drawn inward over the top of the vase, as

clearly shown.

The top ring B is formed with a plain edge or face, and provided on the adjacent convex portion with a circular band of ornaments, b.

The connecting-ring C is made in the form of an ogee molding, and provided with a nar-

row band of ornaments, c.

The case D is divided into several panels or fields by vertical bands d, provided with inclined parallel corrugations or ribs. Each field is provided with three columns in bassrelief, connected at the top by ornamented double arches, the space between each pair of columns being embellished with a sunk ornament, d', as clearly represented. A narrow band of arrow-shaped ornaments is arranged around the upper and lower edge of the case D. The ring D' at the lower edge of | nament, arranged in a circular field, sur-

the case D is ornamented in the same manner

as the top ring B.

The frame E of the combustion chamber and the frame G surrounding the fire-pot are divided into the same number of panels as the case D by vertical corrugated bands corresponding with the bands of the case D, and the ring E', arranged at the lower edge of the frame E, and the top plate I of the ash-pit, are ornamented substantially in the same manner as the top ring B. Each of the panels of the frame E is provided with a door having two mica windows, F F, the tops of which are made semicircular, while their bases are straight, with a small circular arch in the center thereof. A narrow band of ornaments is appraised at the investigation of the minutes. ments is arrranged at the junction of the windows F with the frame E, and at the top the windows are provided with ornaments resembling clusters of grapes.

Each of the fields of the lower frame G is provided with a door, composed of two mica windows, the lower corners of which are made rectangular, while their upper corners are broken or beveled, as clearly shown. The faces of the window-frames are provided with parallel inclined ribs or corrugations and a narrow band of ornaments is arranged around the outer edge of the window-frames.

The case K of the ash-pit is made of a concave cylindrical form, and provided with several panels, R, the top of which is formed by a number of intersecting arches, and which are provided on their plain surface with a sunk ornament, as clearly shown. The space between the panels k is embellished with checkered work, the squares being alternately smooth and ribbed. Below the top-plate I of the ash-pit is arranged a band of pendent ornaments, resembling clusters of grapes.

The base-plate M is provided with three bands of ornaments of different width, the lower one being the widest, the next higher one of less width, and the upper band the

narrowest. The legs N are provided with a sunk orrounded by ribs radiating therefrom, as clearly shown.

I claim as my invention, and desire to se-

cure by Letters Patent-

The design for the general configuration of the stove, and the ornamentation of the top cover A, top-ring B, connecting-ring C, case D, combustion-chamber E, mica windows F,

fire-pot frame G, mica doors H, plate I, ashpit case K, base-plate M, and legs N, substantially as shown and described.

WALTER W. STANARD.

Witnesses:

F. H. ROOT, EDWARD WILHELM.