D 10.424

() F



UNITED STATES PATENT OFFICE.

WILLIAM BURROWS, OF BROOKLYN, ASSIGNOR TO J. L. MOTT IRON WORKS, OF NEW YORK, N. Y.

DESIGN FOR FIRE-PLACE HEATERS.

Specification forming part of Design No. **10,424**, dated January 29, 1878; application filed January 3, 1878. [Term of patent 14 years.]

To all whom it may concern:

Be it known that I, WILLIAM BURROWS, of Brooklyn, Kings county, New York, have originated a Design for Fire-Place Heaters, of which the following is a full, clear, and exact description, reference being had to the accompanying engraved illustration, to which reference is made.

The design of the base of the middle or illuminated section, and also of the base of the top section of the front, consists of the sloping course h, convex course i, concave course j, with upright points, and the top convex course k.

The design of the illuminated front section consists of the ornamental raised projecting bars l at the bottom of the windows, the bars m and n at the top of the same, and the side plates o and p, with raised and figured bars, as shown.

The design for the front of the top section consists of the flaring or concave form of the lower margin of the front plate q, the scalloped beads r, and vertical ribs s, together with the figured side plates t, as shown.

The design of the reticulated cover consists of the plain base v, zigzag bars w, plain bar x,

serolls y, plain bar z, serolls a', and beaded bar b'.

I claim as my design for a fire-place heater—

1. The sloping course h, convex course i, concave course j, with upright points, and the top convex course k of the base of the middle and top sections of the front, as shown and described.

2. The ornamental raised projecting bars l at the bottom of the windows, bars m and n at the top of the same, and the side plates o and p, with raised and figured bars, of the front of the illuminated section, as shown and described.

3. The flaring or concave form of the lower margin of the front plate q, scalloped beads r, and vertical ribs s, and the figured side plates t of the front of the top section, as shown and described.

4. The plain base v, zigzag bars w, plain bar x, seroll y, plain bar z, serolls a', and beaded bar b', of the reticulated cover, as shown and described.

WILLIAM BURROWS.

Witnesses:

F. A. THAYER, Wm. J. Morgan.