

No. 10,511

March 5, 1878



UNITED STATES PATENT OFFICE.

SIEGFRIED WILLERSHAUSEN AND FRANK RHONER, OF NEW YORK, N. Y.,
ASSIGNORS TO SAID RHONER.

DESIGN FOR ROCKING-CHAIR FRAMES.

Specification forming part of Design No. **10,511**, dated March 5, 1878; application filed February 2, 1878.
[Term of patent 7 years.]

To all whom it may concern:

Be it known that we, SIEGFRIED WILLERSHAUSEN and FRANK RHONER, both of the city, county, and State of New York, have originated and designed a Pattern for Rocking-Chair Frame, of which the following is a full, clear, and exact description, reference being had to the accompanying photographic illustration, making part of this specification.

This photographic illustration represents a perspective view of our design.

Our invention relates to a novel and ornamental design for a rocking-chair frame, in which the rocker-frame is made in the form of an anchor, the arms of which curve up and are firmly secured to the seat-frame. The shank of said anchor forms a support for the arm-piece, which appears to pass through the stock of the anchor. The arm-piece is ornamented by a scroll, a band, and button, and an oblique brace.

In the drawing, the letter A designates the seat-frame, and the letter B the rocker-frame, which is made in the form of an anchor, the arms *a a* of which form the support of the seat-frame, while its shank *b* extends up and forms the support for the arm-piece D. Said shank is ornamented by a rosette, *c*, and beads *d d*. The stock *e* of the anchor has the appearance of a sleeve which embraces the arm-piece.

The arm-piece is ornamented by a scroll, *f*, a band, *g*, and a button, *h*, and also by an oblique brace, *i*, the head *j* of which is ornamented by a scroll, *k*.

What we claim as new, and desire to secure by Letters Patent, is—

1. The design for a rocking-chair frame, composed of a seat-frame, A, and a rocker-frame, B, made in the form of an anchor, the arms of which are curved up and support the seat-frame, as shown and described.

2. The design for a rocking-chair frame, composed of a seat-frame, A, and a rocker-frame, B, made in the form of an anchor, the arms of which are curved up and support the seat-frame, while its shank extends up and supports the arm-piece D, as shown and described.

3. The design for a rocking-chair frame, composed of a seat-frame, A, and a rocker-frame, B, made in the form of an anchor, the arms of which are secured to and support the seat-frame, while its stock has the appearance of a sleeve, which embraces the arm-piece D, as shown and described.

4. The design for the arm-piece D of a rocking-chair frame, composed of a scroll, *f*, band *g*, button *h*, oblique brace *i*, head *j*, and scroll *k*, as shown and described.

In testimony that we claim the foregoing we have hereunto set our hands and seals this 22d day of January, 1878.

SIEGFRIED WILLERSHAUSEN. [L. S.]
FRANK RHONER. [L. S.]

Witnesses:

W. HAUFF,
W. C. HAUFF.