

UNITED STATES PATENT OFFICE.

WILLIAM S. KREPS, OF BROOKLYN, NEW YORK, ASSIGNOR TO WIHTE, POTTER & PAIGE MANUFACTURING COMPANY, OF SAME PLACE.

DESIGN FOR A MIRROR-FRAME.

Specification forming part of Design No. 10,749, dated July 9, 1878; application filed June 27, 1878. [Term of patent 7 years.]

To all whom it may concern:

Be it known that I, WILLIAM S. KREPS, of Brooklyn, in the county of Kings, and the State of New York, have originated and designed a Design for Mirror Frame and Cornice; and I do hereby declare that the following is a full, clear, and exact description of the same, reference being had to the accompanying photographic illustration, making

part of this specification.

The photographic illustration herewith appended represents the entire front of the mirror-frame and one of the window-cornices extending laterally therefrom, there being generally two window-cornices, one on each side of such frame. The said window-cornices being alike, it is necessary to show and describe only one of said cornices. The cornice of the mirror-frame and the window-cornices are, moreover, alike, except in the one particular of dimension, so that a description of the mirrorcornice will suffice for the description of the window-cornices.

The mirror-frame is composed of a base, two side rails, and a cornice, ornamented as here-inafter described. The base of the said frame is composed of a center panel, A, two side panels, BB, and two intermediate panels, CC. The said side panels are ornamented with central leaf and flower ornaments in relief, as shown at c, and with moldings c' and c", respectively, at the top and at the bottom of the said panels. The said center panel is ornamented in relief with a central shield, a, between two smaller shields, a' a', a rosette, a'', above the central shield a, and moldings a''' a'''', respectively, at the top and at the bottom of the said panel.

The intermediate panels C are ornamented each with a rosette in the center of a group of leaves, said ornamentation being in relief, as shown at d. The said intermediate panels are, moreover, ornamented with top and bottom moldings d' and d'', and a molding, d''', surrounding the aforesaid rosette and leaves. The side rails, shown at E, are each ornamented with a truss, f, a panel, f', and a bracket, f'', each of which is ornamented in relief as follows: The truss f has its lower part or

upper part ornamented with corbel, molding, and finial work, as shown at g'. The panel f' has two end pieces, h, ornamented in relief with corbel, molding, and finial work, a center piece ornamented in relief with rosette, pendant, and scroll-work, flanked by spiral ornaments in relief, as shown at i. The brackets f'' are each ornámented in relief with a central rosette and pendant leaves, as shown at j, and a downwardly-projecting finial, j'. The said bracket is flanked on one or both sides by a panel-arch or spandrel, ornamented in relief with leaf, vine, and scroll work, as shown at k.

The cornice is shown at D, and is ornamented by end pieces l, a center piece, m, wings n, and ornaments o, intermediate between the said center piece and the said end pieces, the said ornaments o being corbels, as shown. The said cornice is, moreover, ornamented with an upper molding, p. Each of the said end pieces is ornamented in relief with a cap, l', and scroll-work pieces, the said scroll-work pieces being separated by a central molding, The center piece m is also ornamented in relief as follows: It has at the bottom corbels s s, supporting a molding, s' s', between an upper scroll-work piece and a lower scrollwork piece, s'' s'', and between the corbels s sis a piece of leaf and pendent work, s", also in relief.

The window-cornice is ornamented in precisely the same style, and has upon it all and the same ornaments, to wit: End pieces and center piece, wings, and intermediate moldings, all ornamented in the same manner as the like pieces of the mirror-frame cornice: hence, the design of the said window-cornice is identical with that of the mirror-frame cornice.

I claim-

1. The design for the base of a mirror-frame, consisting of side panels B, ornamented in relief, a center panel, A, and intermediate panels C, each ornamented substantially as described, and shown in the accompanying illustration.

2. The design for the side rails of the mirroras follows: The truss f has its lower part or large, consisting of the trusses f, center panel namented with scroll and leaf work g, and its large, consisting of the trusses f, center panel f', and brackets f'', flanked by the arch-panel. els or spandrels k, each of the said ornamental |parts being itself ornamented, substantially as described, and shown in the accompanying illustration.

3. The design for the mirror-frame cornice or window-cornice, composed of the end pieces t and the center piece m, with intermediate moldings p and corbel-work, the said end pieces and center piece being ornamented in relief, substantially as described, and shown in the accompanying illustration.

4. The design for a mirror-frame and window-cornice, consisting of base ornaments, side rail ornaments, and cornice ornaments in re-

lief, and arranged substantially as described, and shown in the accompanying illustration.

5. The design for the center piece of the cornice, consisting of the relief ornaments, namely: The bottom corbels s, supporting a molding, s', between an upper scroll-work piece and a lower scroll-work piece, and a piece of leaf and pendant work between the bottom corbels s, substantially as described, and shown in the accompanying illustration.
WILLIAM S. KREPS.

Witnesses:

ALFRED BURILORN, FRED. HAYNES.