

InterBase Master Index

Disclaimer

Borland International, Inc. (henceforth, Borland) reserves the right to make changes in specifications and other information contained in this publication without prior notice. The reader should, in all cases, consult Borland to determine whether or not any such changes have been made.

The terms and conditions governing the licensing of InterBase software consist solely of those set forth in the written contracts between Borland and its customers. No representation or other affirmation of fact contained in this publication including, but not limited to, statements regarding capacity, response-time performance, suitability for use, or performance of products described herein shall be deemed to be a warranty by Borland for any purpose, or give rise to any liability by Borland whatsoever.

In no event shall Borland be liable for any incidental, indirect, special, or consequential damages whatsoever (including but not limited to lost profits) arising out of or relating to this publication or the information contained in it, even if Borland has been advised, knew, or should have known of the possibility of such damages.

The software programs described in this document are confidential information and proprietary products of Borland.

Restricted Rights Legend. Use, duplication, or disclosure by the U.S. Government is subject to restrictions as set forth in subdivision (b) (3) (ii) of the Rights in Technical Data and Computer Software clause at 52.227-7013.

© **Copyright 1993** by Borland International, Inc. All Rights Reserved. InterBase, GDML, and Pictor are trademarks of Borland International, Inc. All other trademarks are the property of their respective owners.

Corporate Headquarters: Borland International Inc., 100 Borland Way, P. O. Box 660001, Scotts Valley, CA 95067-0001, (408) 438-5300. Offices in: Australia, Belgium, Canada, Denmark, France, Germany, Hong Kong, Italy, Japan, Korea, Latin America, Malaysia, Netherlands, New Zealand, Singapore, Spain, Sweden, Taiwan, and United Kingdom.

Software Version: V3.0

Current Printing: October 1993

Documentation Version: v3.0.1

Reprint note

This documentation is a reprint of InterBase V3.0 documentation. It contains most of the information from *InterBase Previous Versions Documentation Corrections* and *InterBase Version 3.2 Documentation Corrections* and a new index. For information on features added since InterBase Version V3.0, consult the appropriate release notes.

Preface

This document includes index entries for the entire InterBase documentation set, release notes, and installation guides up to and including InterBase V3.2. We recommend that you use the *InterBase Master Index* as a supplement to the index provided in each document.

Index conventions:

- At the bottom of each page is a key to the abbreviations used in the index.
- Commands and reserved words appear in bold typeface.

InterBase Documentation

The InterBase Version 3.0 documentation set contains the following books:

Getting Started with InterBase (INT0032WW2179A) provides an overview of InterBase components and interfaces.

Database Operations (INT0032WW2178D) describes how to use InterBase utilities to maintain databases.

Data Definition Guide (INT0032WW2178F) describes how to create and modify InterBase databases.

DDL Reference (INT0032WW2178E) describes the function and syntax for each of the data definition language clauses and statements. It also lists the standard error messages for **gdef**.

DSQL Programmer's Guide (INT0032WW2179C) describes how to program with DSQL, a capability for accepting or generating SQL statements at runtime.

Forms Guide (INT0032WW2178A) describes how to create forms using the InterBase forms editor, **fred**, and how to use forms in **qli** and GDML applications.

Programmer's Guide (INT0032WW2178I) describes how to program with GDML, a relational data manipulation language, and SQL, an industry standard language.

Programmer's Reference (INT0032WW2178H) describes the function and syntax for each of the GDML and InterBase supported SQL clauses and statements. It also lists the standard error messages for **gpre**.

Qli Guide (INT0032WW2178C) describes the use of **qli**, the InterBase query language interpreter that allows you to read to and write from the database using interactive GDML or SQL statements.

Qli Reference (INT0032WW2178B) describes the function and syntax for each of the data definition, GDML, and SQL clauses and statements that you can use in **qli**.

Sample Programs (INT0032WW2178G) contains sample programs that show the use of InterBase features.

Master Index (INT0032WW2179B) contains index entries for the entire InterBase Version 3.0 documentation set.

In addition, platform-specific installation instructions are available for all supported platforms.

A**abort**

QLI QR:3-3

accept QR:3-4

Access control list (ACL), see Security

Access privileges, see Security

Accessing

blob fields DS:3-1

date field with DSQL DS:3-1, DS:3-6

remote databases DO:2-6

ACL (Access control list), see Security

active DR:5-29

Ada

compiling considerations PG:19-2

DSQL example DS:4-7, SP:4-3

DYN example DG:11-9–DG:11-10,
DG:11-12

GDML considerations PG:3-2

GDML example SP:2-3

SQL considerations PG:3-2

SQL example SP:3-3

SQLDA setup DS:4-6

add field QR:3-6, QR:3-89

After-image journaling

components DO:4-2

enabling with **gfix** DO:3-6

overview DO:3-6

see also Journaling

Aggregate expression

any, unique, first, from QG:3-21

GDML DR:4-19

QLI QG:2-17

Aggregate function QR:2-22, QR:2-25

SQL PG:14-21

Aliases PG:14-17, QG:4-13, QR:2-20,

QR:3-39

all**grant** privilege QR:3-69

QLI QR:3-125

SQL PG:14-11, QG:4-4

ALSYS Ada support, see V3.1 Release

Notes

alter index PG:16-3**alter table** QG:6-16

QLI QR:3-6

SQL PG:13-6, PR:6-2

Alternate field name DG:4-20

and

GDML PG:5-13

order in compound boolean PR:3-2

SQL PG:14-7

any

compared with joining PR:3-3

DDL DR:4-4

GDML PG:5-16, PR:3-3

QLI QG:3-11, QR:2-2

SQL PG:14-11, QG:4-4

anycase PG:5-18, QG:3-15

Apollo

access privileges DG:8-5

Ada DYN example DG:11-9–DG:11-10

filter library PG:9-12

FORTRAN DYN example DG:11-10

fred implementation FO:A-1**fred** keyboard diagram FO:A-10

functions DG:9-5, DG:9-7, DG:9-9

gpre syntax PG:18-2

installing, see Apollo Installation Guide

journaling DO:4-5

licensing, see Apollo Installation Guide

linking considerations PG:19-3

multi-file databases DG:3-6

network servers, see Apollo Installation
Guide

OSRI database creation PG:12-10

Pascal DYN example DG:11-11

pause, see Apollo Installation Guide

registering, see Apollo Installation Guide

remote database DG:3-4

restoring a database DO:2-7

shadow DO:5-3, DO:5-11

shell QR:3-124system requirements, see Apollo Instal-
lation Guide

WBAK DO:2-3

Application development overview GS:4-1

DG: Data Definition Guide

DO: Database Operations

DR: DDL Reference

DS: DSQL Guide

FO: Forms Guide

GS: Getting Started

PG: Programmer's Guide

PR: Programmer's Reference

QG: QLI Guide

QR: QLI Reference

SP: Sample Programs

Application integrity DG:7-3
Arithmetic expression
 DDL DR:4-2
 GDML PG:5-7, PR:3-18
 QLI QG:2-15, QR:2-27
Array
 base PG:7-3
 bounds PG:7-3
 cell PG:7-3
 characteristics PG:7-9
 components PG:7-3
 datatypes PG:7-9
 defining PG:7-10
 dynamic access, see V3.2 Release Notes
 elements in database queries, see V3.1
 Release Notes
 examples PG:7-11, PG:7-22
 fields PG:7-9
 get_slice, see V3.1 Release Notes
 gpre processing PG:7-15
 host language references to cells PG:7-4
 see also V3.1 Release Notes
 host language statements PG:7-16
 overview PG:7-1
 Pascal example PG:7-23
 put_slice, see V3.1 Release Notes
 QLI examples QG:3-27
 reference errors PG:7-21
 referencing a particular cell PG:7-17
 referencing an entire PG:7-18
 retrieving from column PG:14-25
 retrieving, see V3.1 Release Notes
 subscripts PG:7-3
 syntax in host language PG:7-17
 syntax in RSEs PG:7-14
 using in souce code PG:7-13
 using static runtime storage PG:7-12
 using UDFs with, see V3.1 Release Notes
asc (ascending) sort order PG:5-18,
 QG:3-14, QR:3-118
ascending index DG:6-9, QR:3-17
ASCII printing characters DR:4-13, DR:5-4
Assignment statements
 size and precision of datatype QG:5-9

 troubleshooting in QLI QG:5-15
 using QG:5-2, QG:5-5, QR:3-7
Asterisk
 edit all QR:3-49
 print QR:2-20, QR:3-94
 wildcard QR:2-5
ASTs, see VMS Installation Guide
atlas.gdb database DG:B-1, FO:B-1,
 GS:2-5, PG:A-1, QG:B-1
Attaching database, see **ready**
Attribute, see Field
avg (average) PG:14-21, QG:2-17

B

Backup database, see **gbak**
BACKUP, VMS back up utility DO:2-3
based_on PR:4-3, QG:6-7
BASIC
 DSQL considerations DS:1-8
 DSQL example SP:4-6
 DYN example DG:11-13
 GDML considerations PG:3-4
 GDML example SP:2-8
 SQL considerations PG:3-4
 SQL example SP:3-7
 SQLDA setup DS:4-10
begin-end block
 definition QG:5-6, QR:3-10
between
 DDL DR:4-4
 GDML PR:3-3
 QLI QR:2-3, QR:2-9
 SQL PR:5-3
Binary datatype DG:4-4
Blob
 accessing DS:3-1, PG:8-3
 accessing in SQL PG:17-6
 C routine example PG:8-13
 C routines PG:8-12
 call example PG:8-20
 checking open PG:12-28
 close_blob PG:8-5
 closing PR:4-9
 create_blob PG:8-5, PR:4-15

creating PR:4-15
 creating context for storing PG:8-17
 creating using OSRI PG:12-33
 datatype DR:5-9, DG:4-10, DG:4-23
 definition DG:4-10, QG:5-10
 dumping PG:8-10
 feature summary DG:4-10
for blob PR:4-46
for loop PG:8-3
gds DR:5-9
gds calls PG:8-15
gds statements PG:17-6
gds_squad DR:5-9
get_segment PG:8-5, PR:4-57
input_type DR:5-23
 library routines PG:8-9, PG:17-6
 loading a field PG:8-10
 moving data between file systems PG:8-9
open_blob PG:8-5
 opening PR:4-67
 opening a stream PG:8-12
 opening using OSRI PG:12-32
output_type DR:5-23
 overview DG:4-10, GS:1-4, PG:8-1
 parameter blocks PG:12-32
 preparing for retrieval PG:8-18
 processing PG:8-5
put_segment PG:8-5, PR:4-74
 reading DG:8-11, PG:8-5, PG:8-10,
 PR:4-57
 reading segment PG:8-18
 release internal storage PR:4-4
 releasing internal storage PG:8-16
 releasing system resources PG:8-17
 restrictions PG:8-3
 retrieving from column PG:14-25
 searching DR:4-6, QR:2-4
 segment lengths DG:4-10
 storage PR:4-103
 subtypes DR:5-10, DG:4-10–DG:4-12
 using UDF's with, see V3.1 Release Notes
 using with forms FO:8-1
 writing PG:8-10

writing segment PG:8-19
 writing to PR:4-74
Blob filter
 accessing PG:9-18
 ACTION macros PG:9-7
 compiling PG:9-10
 control structure code PG:9-4
 defining to database DR:5-22, PG:9-11
 example PG:9-19
 library PG:9-12
 nroff filter example PG:9-8
 overview DG:4-12, GS:1-4, PG:9-1
 programming steps PG:9-3
 showing QR:3-126
 writing and compiling PG:9-4
blob_display PG:8-10
blob_dump PG:8-10
blob_edit PG:8-10
blob_load PG:8-10
 Block assignments, see **begin-end**
blr
 see also OSRI Manual
 setting in QLI QR:3-121
 Boolean expression DG:4-15
 conditions PR:3-2
 DDL DR:4-3
 GDML PR:3-2
 operator precedence DR:4-3
 QLI QG:3-6, QR:2-2
bopen PG:8-12
 BPB options, see Blob parameter block
 Bridge, see V3.0 Release Notes
bt, see **between**
 Buffer size
 QLI QG:1-9
C
C
 Apollo transaction example PG:12-22
 array consideration PG:7-23
 array example PG:7-22
 blob filter example PG:9-19
 blob routine example PG:8-13

- blob routines PG:8-12
- bopen** PG:8-12
- compiling considerations PG:19-2
- considerations for GDML PG:3-5
- considerations for SQL PG:3-5
- database attachment PG:12-16
- database creation using OSRI PG:12-10
- date field example PG:10-6
- DSQL considerations DS:1-8
- DSQL examples SP:4-8
- DYN example DG:11-13–DG:11-14
- fopen** PG:8-12
- GDML example SP:2-13
- getb** PG:8-12
- missing values in DSQL DS:2-53
- null indicator, setting up local storage for
 - DSQL in DS:2-53
- null values in DSQL DS:2-53
- OSRI database attachment PG:12-14
- putb** PG:8-12
- sample synchronous event program
 - PG:11-17
- setting up the SQLDA DS:2-6, DS:2-13,
 - DS:2-21, DS:2-30, DS:4-2
- SQL example SP:3-10
- SQLDA setup DS:4-2
- store and retrieve date field PG:10-4
- VAX transaction example PG:12-20
- C++
 - on Apollo HP-UX, see V3.2 Release Notes
 - on Apollo, see V3.1 Release Notes
 - on Sun, see V3.2 Release Notes
- Cache size, see V3.2 Release Notes
- Call interface names, see V3.1 Release Notes
- cancel_blob** PR:4-4
- Case sensitivity
 - containing** DR:4-6, QR:2-4
 - matching** DR:4-6, QR:2-5
 - QLI QG:1-5
 - sorting records QG:3-15
 - starting with** DR:4-7, QR:2-7
- case_menu** FO:7-10, FO:9-2, PR:4-6
- Casting
 - date fields DS:3-6
 - overview PG:6-13, PG:10-2
 - restrictions PG:6-14
 - supported conversions PG:6-13
- Central server, see appropriate platform
 - Installation Guide
- change** FO:3-12
- Changing values, see **modify**, **update**
- Char datatype DR:5-11
- Character datatype DG:4-7
- Checkpoint, recreating database from
 - DO:4-23
- close** PR:6-4
- close_blob** PG:8-5, PR:4-9
- COBOL
 - DSQL considerations DS:1-8
 - DSQL example SP:4-20
 - DYN example DG:11-14–DG:11-15
 - GDML considerations PG:3-7
 - GDML example SP:2-35
 - SQL considerations PG:3-7
 - SQL example SP:3-13
 - SQLDA setup DS:4-11
- col** QR:3-94
- Column
 - alternate name DR:5-17, DG:4-21
 - assigning values PG:15-2
 - headings QR:3-94, QR:3-110
 - modifying array data in PG:15-13
 - modifying blob data in PG:15-12
 - print width QR:3-121
 - projecting PG:14-15
 - retrieving array data from PG:14-25
 - retrieving blob data from PG:14-25
 - storing array data in PG:15-7
 - storing blob data in PG:15-7
- column_header** QR:3-110
- Command line options, see Switches
- Commands
 - defined in QLI QG:1-6
 - distinction from statements PG:1-4
 - gpre** PG:1-4

- comment on** PG:16-3
- Comments DR:5-12, DR:5-29, DG:4-17
- commit**
 - GDML PG:4-13, PR:4-11
 - gfix** DO:3-8
 - QLI QG:1-16, QG:10-5, QR:3-12
 - SQL PG:13-11, PR:6-6
 - two-phase DG:3-2, QR:3-91
- Communication area
 - SQL PG:13-3
- compare**
 - SQL PR:5-2
- comparison**
 - DDL DR:4-5
 - GDML PR:3-4, QR:2-3, QR:2-10
- Compiling programs
 - Ada considerations PG:19-2
 - C considerations PG:19-2
 - linking PG:19-1
 - overview PG:19-1
- computed by** DR:5-33
- Computed field
 - example DG:6-5, DG:9-16
 - modifying DG:4-23, DG:5-13
 - overview DG:5-5, GS:3-4
- Concatenated key DG:2-3
- Concatenation operator QR:2-28
- Concurrency model
 - comparing with consistency PG:2-20
 - definition GS:4-2, PG:2-2
 - example PG:2-17
- Consistency model
 - comparing with concurrency PG:2-20
 - definition GS:4-2, PG:2-2
- console.addr* DO:4-5
- Constant expression
 - QLI QR:2-21
 - SQL PR:5-9
- cont**, see **containing**
- containing**
 - DDL DR:4-6
 - GDML PG:5-15, PR:3-5
 - QLI QG:3-8, QR:2-4
 - quoted string search in blob PR:3-5
- Context variable
 - QLI QG:2-9, QG:3-3, QR:2-14, QR:2-28
- Continuation prompt in QLI QR:3-121
- copy procedure** QG:7-7, QR:3-14
- Corrupt database repair DO:3-4
- count** PG:14-21, QG:2-17
- create database**
 - QLI QR:3-15
 - SQL GS:3-3, PG:13-6, PG:16-4, PR:6-10, QG:6-15
- create index**
 - QLI QG:6-17, QR:3-17
 - SQL PG:13-6, PR:6-12
- create synonym** PG:16-3
- create table**
 - QLI QR:3-19
 - SQL PG:13-6, PG:16-5, PR:6-14, QG:6-16
- create view**
 - QLI QR:3-21
 - SQL PG:13-6, PG:16-7, PR:6-17
- create_blob** PG:8-5, PR:4-15
- create_window** FO:7-4
- Creating a remote database DG:3-4
- cross**
 - DDL DR:4-14–DR:4-15
 - GDML PG:5-11, PR:3-13
- ct**, see **containing**
- Cursor
 - activating in SQL PR:6-54
 - closing PG:14-5
 - declaring PG:14-3, PR:6-19
 - fetching rows with PG:14-4
 - opening PG:14-4
- Customer support information DO:3-5, DO:6-19, DR:A-2

D

D_FLOAT, see V3.1 Release Notes

Data

- converting GS:5-2
- copying between databases QG:6-9
- copying from external file QG:6-9

- deleting in SQL PG:15-14
- deleting through a view in SQL PG:15-16
- erasing GS:4-11
- formatting DG:4-19
- modifying GS:4-8
- modifying array data in column PG:15-13
- modifying blob data in column PG:15-12
- modifying through view in SQL PG:15-13
- modifying with forms QG:9-7
- moving between relations QG:6-8
- moving blob between file systems PG:8-9
- retrieving GS:4-4
- retrieving array from column PG:14-25
- retrieving blob from column PG:14-25
- retrieving from joined relations PG:5-11
- security, see Security
- storing GS:4-6
- storing array data in column PG:15-7
- storing blob data in column PG:15-7
- storing through view using SQL PG:15-7
- storing using forms QG:9-6
- writing in QLI overview QG:5-1
- writing in SQL PG:15-1
- writing using GDML PG:6-1
- Data definition
 - calls to **gds** routines DG:12-2
 - embedded DYN DG:12-2
 - embedded SQL DG:12-2, DG:12-5
 - gdef** DG:3-3
 - modifying with DYN DG:11-7
 - overview DG:1-1, DG:12-1
 - QLI DG:12-3–DG:12-5
 - summary DG:12-1
- Data definition language, see DDL
- Data dictionary GS:3-3
- Data identifier, see Primary key
- Data integrity
 - application DG:7-3
 - domain DG:7-2, DG:7-3
 - entity DG:7-2
 - overview DO:3-3, DG:7-1, GS:1-3
 - referential DG:7-2
- Data manipulation languages GS:1-8, GS:C-1
- Data security, see Security
- Database
 - administration overview DO:1-1
 - attaching using OSRI PG:12-11
 - backup, see **gbak**
 - changing page size DO:2-9
 - cleaning up PG:2-19
 - closing PG:4-15, PR:4-39, QR:3-63
 - components GS:3-1
 - converting version 2 to version 3, see appropriate Installation Guide
 - creating DG:3-3, GS:3-3, PR:6-10, QR:3-15
 - creating in SQL PG:16-4
 - creating using OSRI PG:12-8
 - declaring PG:4-3, PR:4-18
 - declaring in DSQL DS:1-8
 - declaring multiple PG:4-3
 - defining DR:5-2, DG:3-9
 - defining on UNIX DG:3-3
 - defining on VMS DG:3-3
 - defining using SQL QG:6-15
 - defining with QLI QR:3-26
 - defining, see also **gdef**
 - deleting using SQL QG:6-15
 - designing and planning DG:2-1–DG:2-10
 - detachment using OSRI PG:12-17
 - dropping PR:6-33, QR:3-45
 - extracting metadata DG:3-14
 - field expression DR:4-9, QR:2-28
 - file length DG:3-5
 - file specifications DO:6-5, PR:4-19, PR:4-78
 - handle PG:5-10, QG:3-4, QG:3-5, QG:6-3, QR:3-12, QR:3-91, QR:3-116
 - local QR:3-101
 - maintaining DO:3-1, DO:6-18–DO:6-22, DG:3-15
 - multi-file DG:3-5
 - multi-file, see also Multi-file database
 - naming in SQL PG:13-5
 - networks DG:3-2

DG: Data Definition Guide
 DO: Database Operations
 DR: DDL Reference
 DS: DSQL Guide

FO: Forms Guide
 GS: Getting Started
 PG: Programmer's Guide
 PR: Programmer's Reference

QG: QLI Guide
 QR: QLI Reference
 SP: Sample Programs

- NFS format information DG:3-5
- opening PG:4-4, PR:4-77
- operations overview DO:1-1
- options PR:4-18
- page range DG:3-5
- page size DO:2-9, DR:5-3, DG:3-5
- pathname PR:4-19
- planning and designing DG:2-1–DG:2-10
- reading QR:3-100
- recovery overview DO:2-1
- recreating from checkpoint DO:4-23
- remote DO:2-6, DG:3-4, PR:4-78, QR:3-101
- repairing corrupt DO:3-4
- runtime PR:4-18
- sample (*atlas.gdb*) PG:A-1
- sample definition DG:B-1
- securing in SQL PG:16-10
- shadow file DG:3-7
- showing open QR:3-125
- single-file DG:3-3
- using **show** with handle QG:3-5, QG:6-3
- database** PG:4-3, PR:4-18
- Database field expression
 - GDML PR:3-19
- Database handle
 - assigning QG:3-4
- Database parameter blocks PG:12-7
- Datatype
 - array PG:7-9
 - binary DG:4-4
 - blob DG:4-10, DG:4-23
 - character DG:4-7
 - date DG:4-9, QG:5-9
 - double DG:4-7
 - external relation DG:5-6
 - fixed DR:5-11
 - float DG:4-7
 - integer, see Short datatype, Long datatype
 - long DG:4-4
 - multi-dimensional array DG:4-13
 - options DR:5-10
 - overview DR:5-7, DG:4-4, QR:3-56
 - scale QR:3-57
 - scale factor DG:4-4
 - short DG:4-4
 - size and precision of DR:5-10, QG:5-9, QR:3-24
 - SQLDA DS:1-4
 - SQLTYPE fields DS:1-7
 - string DG:4-7
 - syntax DR:5-7
 - text DG:4-7
 - varying text DG:4-7
- Datatype conversion
 - see casting
- Date datatype DG:4-9
- Date field
 - accessing in SQL PG:17-10
 - accessing with DSQL DS:3-1, DS:3-6
 - accessing with **gds** date routines DS:3-10
 - C example PG:10-6
 - casting DS:3-6, PG:10-2
 - converting PG:10-4
 - converting to/from UNIX time structure PG:14-25, PG:15-7, PG:15-12
 - edit string characters DR:5-14
 - formats QG:5-9
 - overview PG:10-1, QG:5-9
 - Pascal example PG:10-7
 - relative QG:5-10
 - retrieving from casted PG:10-3
 - writing to casted PG:10-2
- date timestamp* DO:4-12
- DDL
 - conventions DG:3-10
 - first** DR:4-10
 - input rules DG:3-10
 - interactive DG:3-12
 - list of statements DR:5-1
 - source files DG:11-4
- Debug, see **gltj**
- declare** QR:3-23
- declare cursor** PG:14-3, PR:6-19, DS:2-2
- declare statement** PR:6-23

- declare table** PR:6-24
 Declaring a database in DSQL DS:1-8
 DECnet
 remote database filenames DG:3-4
- define database**
 DDL DR:5-2
 gdef DG:3-9
 GDML GS:3-3
 QLI QG:6-3, QR:3-26
- define field**
 DDL DR:5-6–DR:5-11, DG:5-3
 DLL DG:4-1
 QLI QG:6-4, QR:3-28
 valid_if DG:7-5
- define filter** DR:5-22
- define function** DR:5-25–DR:5-27, DG:9-7
- define generator** DG:4-18
- define index**
 DDL DR:5-28–DR:5-30
 overview DG:6-8
 QLI QR:3-30
 unique DG:6-8, DG:7-4
- define procedure** QG:7-3, QG:7-4, QR:3-33
- define relation**
 adding field DG:4-1
 DDL DR:5-31–DR:5-36, DG:3-10
 overview DG:5-1
 QLI QG:6-6, QR:3-36
- define security_class** DR:5-37–DR:5-40, DG:8-4
- define shadow** DO:5-4, DO:5-6, DR:5-41–DR:5-42, DG:3-7
- define trigger** DR:5-43–DR:5-48, DG:7-6
- define view** DR:5-49–DR:5-53, DG:6-3–DG:6-6, QG:6-18
- Defining data, see Data definition
- delete**
 GDML QG:6-11
 overview DR:5-54
 SQL GS:4-11, PG:13-6, PG:15-14, PR:6-28
- delete field** DR:5-54, DG:4-24, QG:6-5
- delete function** DG:9-8
- delete index** DG:6-11
 see also **drop index** DG:6-11
- delete metadata** QR:3-41
- delete procedure** QG:7-8, QR:3-43
- delete relation** DG:5-14, QR:3-39, QR:3-42
- delete shadow** DO:5-9, DR:5-58
- delete trigger** DG:7-12
- delete view** DR:5-56, DG:6-7
- delete_window** FO:7-5
- Deleting records
 QLI QR:3-39
- desc** (descending) sort order PG:5-18, QG:3-14, QR:3-118
- descending index** DG:6-9, PG:16-6, QR:3-17
- describe** PR:6-31
 DSQL DS:2-2
- Detaching database, see **finish**
- Disabling journaling DO:4-8, DO:4-19
- Disaster recovery, see Shadowing, Journaling
- Disk shadowing, see Shadowing
- Display
 changing in QLI QG:1-13
- display**
 forms FO:9-5
 GDML PR:4-23
- distinct**
 erase caution QG:5-18
 QLI QG:3-18
 select option QR:2-23
 SQL PG:14-15, QG:4-12
- Dollar sign (\$), see V3.1 Release Notes
- Domain integrity DG:7-2, DG:7-3
- Double datatype DG:4-7
- drop database**
 caution QG:6-15
 QLI QG:6-15, QR:3-45
 SQL PR:6-33
- drop field** DG:4-24, QR:3-89

drop index

QLI QG:6-13, QG:6-17
 SQL PG:13-6, PG:16-6, PR:6-34

drop synonym PG:16-3**drop table**

QLI QG:6-16, QR:3-47
 SQL PG:13-6, PG:16-5, PR:6-35

drop view PG:16-7, PR:6-36, QG:6-18

SQL PG:13-6

DSQL

Ada example DS:4-7
 Ada program SP:4-3
alter table PR:6-2
 BASIC program SP:4-6
 BASIC programming considerations
 DS:1-8
 C program examples SP:4-8
 C programming considerations DS:1-8
 casting date fields DS:3-6
close PR:6-4
 COBOL program SP:4-20
 COBOL programming considerations
 DS:1-8
 column aliases, see V3.2 Release Notes

commit PR:6-6

compared to embedded SQL DS:1-3

create index PR:6-12**create table** PR:6-14**create view** PR:6-17

date fields DS:3-6

declare cursor DS:2-2**declare statement** PR:6-23

declaring a database in DS:1-8

describe DS:2-2, PR:6-31**drop index**

SQL PR:6-34

drop table PR:6-35**drop view** PR:6-36

error codes PR:A-25

execute DS:2-2, PR:6-37**execute immediate** DS:2-2, PR:6-39**fetch** DS:2-2, PR:6-41

FORTRAN program SP:4-23

FORTRAN programming considerations

DS:1-8–DS:1-9

gds date routines DS:3-10

general information DS:1-1

grant PR:6-46

invalid statements DS:1-2

missing values DS:2-53

multiple databases DS:1-8

null values DS:2-53

open DS:2-2, PR:6-54**open cursor** DS:2-2

overview DS:1-1

Pascal program examples SP:4-27

PL/1 program SP:4-39

prepare DS:2-2, PR:6-57

processing non-select statements DS:2-3–DS:2-12

processing **select** statements with the
 SQLDA DS:2-13–DS:2-29

processing statements with parameters
 DS:2-6–DS:2-12

processing unknown statements DS:2-30–DS:2-52

revoke PR:6-59**rollback** PR:6-61

statement definition DS:1-2

statements DS:1-2, DS:2-2

summary of functions DG:1-2

valid statements DS:1-2

Duplicate eliminating in indexes DG:6-8

DYN

Ada example DG:11-9–DG:11-10,
 DG:11-12

compiling commands DG:11-7

compiling source file DG:11-4

creating commands DG:11-3

DDL source file DG:11-3

dynamic DG:11-4

FORTRAN example DG:11-10, DG:11-15–DG:11-16

including in program DG:11-6

language options DR:2-3

modifying data definitions DG:11-7

modifying metadata DG:11-1
 overview DG:11-1
 Pascal example DG:11-11–DG:11-12,
 DG:11-16–DG:11-17
 PL/1 example DG:11-17–DG:11-18
 relation to **gdef** DR:2-2, DG:11-1–DG:11-
 2
 summary of functions DG:1-2
 using DG:11-3–DG:11-8
 Dynamic DDL, see DYN
 Dynamic menus FO:7-12, PR:4-54
 Dynamic SQL, see DSQL

E

echo QR:3-121
edit QR:3-49
edit form QG:9-9
edit procedure QR:3-51
edit_string DR:5-13–DR:5-16, QR:3-58
 Editing string DG:4-19
 Embedded SQL
 advantage of using instead of DSQL
 DS:1-1
 compared to DSQL DS:1-3
 summary of functions DG:1-2
end_item FO:9-17
 End-of-file characters QR:3-55
 Entity integrity DG:7-2
 Equijoin QG:2-8
erase GS:4-11, GS:4-12, PG:6-12, PR:4-27,
 QG:5-18, QR:3-53
 Errors
 DDL, App. A
 DSQL code list PR:A-25
gbak DO:6-7–DO:6-9
gcon DO:6-11–DO:6-13
gcsu DO:6-16–DO:6-17
gdef DG:3-16
gfix DO:6-21–DO:6-22
gl tj DO:6-24–DO:6-25
gpre PG:4-9
grst DO:6-26
 messages, App. A

on_error PR:4-61
 printing SQLCODE, see V3.2 Release
 Notes
 reporting in QLI QG:1-12
 reporting to program PR:A-2
 sample program PG:4-11
 shadow DO:5-12
 SQL PG:13-7
 SQL codes list PR:A-4
 status vector PG:4-9
 using **abort** in QR:3-3
 Event
 alerter GS:1-2, GS:5-12
 allocating block PG:11-15
 analyzing PG:11-10
 asynchronous PG:11-13
 asynchronous trap PG:11-14
 counts PG:11-16
 defining PG:11-9
 definition DG:10-1
 example PG:11-11
 manager DG:10-3
 overview GS:1-2, PG:11-1, PG:11-3
 parameter blocks PG:11-15
 posting DG:10-3
 processing PG:11-3
 programming using GDML PG:11-9
 programming using OSRI PG:11-13
 relation to event alerters DG:10-1
 sample asynchronous program PG:11-18
 sample synchronous program PG:11-17
 setup PG:11-4
 syntax PG:11-9
 table DG:10-3
 transaction control DG:10-6, PG:11-11
 uses PG:11-2
 wait types DG:10-4
 waiting for PG:11-10
 when to use PG:11-8
event_init DG:10-4, PG:11-10, PR:4-29
event_wait DG:10-4, PG:11-10, PR:4-33
exactcase PG:5-18
 Examples directory SP:1-2

execute

DSQL DS:2-2

SQL PR:6-37

execute immediate

DSQL DS:2-2

non-select statements DS:2-3

SQL PR:6-39

exists

QLI QR:2-10

see also **any**

SQL PG:14-10, PR:5-6, QG:4-5

exit

QLI QG:1-16, QG:10-7, QR:3-55

Expressions

Arithmetic expression PG:5-7

database field PG:5-5

numeric literal expression PG:5-6

quoted string PG:5-6

External command procedures in QLI

QG:7-14

External relation

changing datatype DG:5-8

converting data DG:5-9

copying data from QG:6-9

data access DG:5-6

data transfer DG:5-7

defined QG:6-9

definition DG:5-6

using DG:5-6–DG:5-11

Extracting metadata DG:3-14**F****Fax number for InterBase DO:3-5,**

DO:6-19, DR:A-2

fetch

DSQL DS:2-2

GDML PG:5-4, PR:4-36

SQL PG:14-4, PR:6-41

Fieldadding with **define relation** DG:5-2adding with **modify relation** QR:3-89

alternate names DR:5-18, DG:4-20

array PG:7-9

assigning name DG:5-4

attributes DG:4-2, DG:5-3, GS:3-4,

QR:3-56

automatic prompting for values QG:5-2

blob PG:8-1

changing attributes DG:5-3

column names DG:4-21

comments DG:4-17

computed DG:5-5, DG:5-13, GS:3-4

datatypes DG:4-4

date PG:10-1

defining DR:5-6–DR:5-11, DG:4-1,

GS:3-4, QR:3-28

deleting DG:4-24, QR:3-41

dropping DG:4-24, QR:3-89

edit strings DG:4-19

explained in QLI QG:2-3

global DG:4-2, DG:5-13, GS:3-4

including in relation DG:5-3

local GS:3-4

missing values DG:4-16

modifying PG:6-10

modifying with **modify field** DG:4-22,

DG:5-13, QR:3-86

modifying with **modify relation**

DG:4-22, QR:3-89

projecting on PG:5-20

query header DG:4-21

query name DG:4-21, QR:3-61

referencing in **for** loop PG:4-5

retrieving blob data from PR:4-46

selecting using SQL QG:4-2

selecting with SQL PR:5-13

sequential number generator DG:4-18

showing QR:3-126

updating PR:4-59, PR:6-67, QR:3-134

using in QLI QR:2-19

using values to create record stream

PG:6-3

validation criteria DG:4-15, DG:7-5

values QR:3-7, QR:3-134

Field comma list QG:3-2

Field expressions PR:5-8

DG: Data Definition Guide

DO: Database Operations

DR: DDL Reference

DS: DSQL Guide

FO: Forms Guide

GS: Getting Started

PG: Programmer's Guide

PR: Programmer's Reference

QG: QLI Guide

QR: QLI Reference

SP: Sample Programs

Fields

- SQLDA DS:1-5
- File extensions PG:18-3
 - definition SP:1-2
- File length DG:3-5
- File specifications
 - database DO:6-5, QR:3-26
- Files installed by InterBase, see
 - appropriate platform Installation Guide
- Filter, see Blob filter

finish

- GDML PG:4-15, PR:4-39
- QLI QG:1-16, QG:10-7, QR:3-63

first

- DDL DR:4-10
- GDML PG:5-19, PR:3-12, QG:3-21, QR:2-13, QR:2-29
- QLI QR:2-13, QR:2-29

Float datatype DG:4-7

Floating point numbers, see V3.2 Release Notes

Footer QR:3-109

fopen PG:8-12

for

- creating record stream PG:5-2
- data manipulation statements PG:4-8
- GDML PG:4-7, PR:4-41
- QLI QR:3-65
- retrieving and displaying records using QG:3-3
- storing records using QG:5-7
- using for outer join PG:5-12
- using with blobs PG:8-3

for blob PR:4-46

for_form FO:7-2, FO:9-9, PR:4-49, QG:9-3, QG:9-8, QR:3-67

for_item FO:9-12, PR:4-52

for_menu FO:9-14, PR:4-54

Foreign key DG:2-8, DG:7-2, DG:7-15

format using QR:2-29

Formatting

- data with edit strings DG:4-19

Forms

- accessing data through QG:9-2
- adding database fields FO:3-9
- adding external fields FO:3-7
- adding text FO:3-6
- attributes FO:7-6
- changing text FO:3-11
- creating a form FO:2-1
- creating menus FO:7-10
- creating windows FO:7-4
- datatypes valid FO:2-3
- default elements FO:2-3
- defining static menus FO:7-10
- deleting a window FO:7-5
- deleting elements FO:1-8, FO:3-13
- displaying FO:7-2, PR:4-23, QG:9-4
- editing FO:3-1, QG:9-9
- editing a blob FO:8-1
- editing fields in FO:2-5
- elements in FO:1-2
- exiting FO:3-15
- field values limiting FO:3-12
- fields on FO:2-3
- formatting in QLI FO:5-3
- horizontal FO:9-2, FO:9-7
- introduction FO:1-1
- invoking FO:1-7
- invoking automatically QG:9-2
- invoking explicitly QG:9-3
- invoking in QLI FO:6-3
- keyboard maps FO:A-5
- menus FO:1-7, FO:7-10
- modifying data with FO:6-5, QG:9-7, QR:3-84
- moving elements FO:3-4
- navigating in FO:2-4
- options for defining fields FO:3-8
- overview FO:1-1, GS:6-1, QG:9-1
- platform specific instructions QG:9-2
- printing QR:3-93
- reformat FO:2-7
- renaming FO:2-8
- repeating groups FO:3-10

resizing FO:2-7
 reversing FO:3-12
 rolling back FO:1-8
 sample application FO:7-13
 sample programs FO:C-1
 saving FO:2-8, FO:3-14
 saving to external file FO:2-9
 selecting fields FO:3-4
 setting attributes with GDML FO:7-6
 setting in QLI QR:3-121
 size FO:2-7
 starting FO:1-7
 storing data using FO:6-5, QG:9-6,
 QR:3-131
 tag line FO:2-3
 terminating key FO:7-9
 tutorial FO:5-2
 using in **for** loops QG:9-8
 using in programs FO:7-1
 using subforms in GDML FO:7-13
 using with GDML FO:7-1
 using with QLI FO:6-1, QG:9-1
 using with SQL FO:7-1
 valid field datatypes FO:2-3
 vertical FO:9-2, FO:9-7
 window FO:7-4

FORTRAN

DSQL considerations DS:1-8–DS:1-9
 DSQL example SP:4-23
 DYN example DG:11-10, DG:11-15
 GDML considerations PG:3-8
 GDML example SP:2-41
 setting up the SQLDA in DS:1-8, DS:4-12
 SQL considerations PG:3-8
 SQL example SP:3-16
 SQLDA setup DS:4-12
 using on SUN, see Sun Installation
 Guide
 using on Ultrix or SGI, see UNIX Instal-
 lation Guide

fred, see Forms

Function

accessing from **gdef** DG:9-1, DG:9-16

accessing from programs DG:9-15
 accessing from QLI DG:9-15
 defining DR:5-25–DR:5-27, DG:9-6–
 DG:9-8, GS:5-4
 deleting DG:9-8
 showing QR:3-125
 Function library, creating DG:9-9–DG:9-14

G

Garbage collection, see **gfix**

gbak

advantages DO:2-3
 blocking factor, see V3.2 Release Notes
 default device DO:2-5
 effect on security DG:8-6
 errors DO:6-7–DO:6-9
 examples DO:6-5–DO:6-7
 heterogeneous networks DO:2-5
no_validity option DO:2-8
 options DO:6-2–DO:6-5
 overview DO:2-1, DO:6-2, GS:1-11
 summary DG:3-15
 tape DO:2-5
 troubleshooting DO:6-7–DO:6-9
 user defined functions DO:2-8
 XDR (transportable) format DO:2-5

gcon

definition DO:4-2
 errors DO:6-11–DO:6-13
 options DO:4-8, DO:6-10
 overview DO:6-10
 troubleshooting DO:6-11–DO:6-13

gcsu

errors DO:6-16–DO:6-17
 options DO:6-14–DO:6-15
 overview DO:6-14, GS:1-11
 troubleshooting DO:6-16–DO:6-17

gdef

accessing functions from DG:9-16
 advantages of using DG:1-3
 creating database files DG:3-3
define generator DG:4-18
 defining databases DG:3-9

DG: Data Definition Guide
 DO: Database Operations
 DR: DDL Reference
 DS: DSQL Guide

FO: Forms Guide
 GS: Getting Started
 PG: Programmer's Guide
 PR: Programmer's Reference

QG: QLI Guide
 QR: QLI Reference
 SP: Sample Programs

- defining fields DG:4-1
- effect on security DG:8-6
- errors DG:3-16
- example DR:2-3
- extracting metadata DG:3-14
- interactive DG:3-12
- modifying databases DR:5-60, DG:1-4, DG:3-9
- overview DR:2-2, DG:1-1, GS:1-10
- relation to DYN DG:11-1–DG:11-2
- relation to QLI DG:1-2
- relationship to DYN DR:2-2
- reserved words DR:3-2
- sample database file DG:1-4
- sample interactive use DG:1-4
- source files DG:1-3, DG:3-10
- summary of functions DG:1-1
- summary of use DG:3-9–DG:3-10
- syntax DR:2-2
- troubleshooting DR:2-4
- GDML
 - accessing functions DG:9-15
 - accessing user defined functions DG:9-15
 - Ada considerations PG:3-2
 - Ada program SP:2-3
 - any** PR:3-3
 - arithmetic expression PG:5-7, PR:3-18
 - automatic value prompting in QLI QG:5-2
 - based_on** PR:4-3
 - BASIC considerations PG:3-4
 - BASIC program SP:2-8
 - between** PR:3-3
 - boolean syntax PR:3-2
 - C considerations PG:3-5
 - C program SP:2-13
 - cancel_blob** PR:4-4
 - case_menu** PR:4-6
 - clause list PR:4-1
 - close_blob** PR:4-9
 - COBOL considerations PG:3-7
 - COBOL program SP:2-35
 - commands list PR:4-1
 - commit** PR:4-11, PR:4-18
 - compared to SQL GS:1-8, GS:C-1
 - comparison** PR:3-4
 - containing** PR:3-5
 - converting from QLI QG:11-2
 - create_blob** PR:4-15
 - cross** PR:3-13
 - database components definable by GS:3-3
 - database field expression PG:5-5, PR:3-19
 - declarations list PR:4-1
 - definition PG:1-1
 - display** PR:4-23
 - embedded program requirements PG:4-1
 - embedding statements PG:4-7
 - erase** PR:4-27
 - event_wait** PR:4-33
 - events DG:10-4, PG:11-3
 - fetch** PR:4-36
 - finish** PR:4-39
 - first** PR:3-12
 - for** PR:4-41
 - for_blob** PR:4-46
 - for** loop PG:4-7
 - for_form** PR:4-49
 - for_item** PR:4-52
 - for_menu** PR:4-54
 - FORTRAN considerations PG:3-8
 - FORTRAN program SP:2-41
 - get_segment** PR:4-57
 - global field QG:6-4
 - implementing features in QLI QG:A-2
 - matching** PR:3-6
 - matching using** PR:3-7
 - missing** PR:3-8
 - missing values PG:5-17
 - mixing with host language programs PG:4-1
 - modify** PR:4-59
 - not** PR:3-9
 - numeric literal expression PG:5-6, PR:3-20

- on_error** PR:4-61
- open_blob** PR:4-67
- operators PG:5-13
- overview PG:4-1
- Pascal considerations PG:3-11
- Pascal program SP:2-51
- PL/1 considerations PG:3-13
- PL/1 program SP:2-79
- prepare** PR:4-69
- preprocessing programs PG:4-16
- programming events PG:11-9
- put_item** PR:4-71
- put_segment** PR:4-74
- QLI subset PG:4-17
- quotation marks GS:4-9
- quoted string expression PG:5-6, PR:3-20
- ready** PR:4-77
- record selection PG:5-5
- record selection expression PR:3-11
- reduced to** PR:3-15
- referencing fields in **for** loop PG:4-5
- relation clause PR:3-12
- release_requests** PR:4-81
- retrieving data PG:5-1
- rollback** PR:4-88
- save** PR:4-90
- search conditions in QLI QG:3-6
- sorted by** PR:3-16
- start_stream** PG:4-8, PR:4-92
- start_transaction** PR:4-95
- starting with** PR:3-9
- statements list PR:4-1
- store** GS:4-6, PR:4-99
- store_blob** PR:4-103
- summary of features GS:C-1
- supported variants PG:1-2
- transaction handle PR:4-105
- trigger language extensions DG:7-6
- unique** PR:3-10
- username expression PR:3-21
- using in QLI QG:3-1
- using with SQL PG:17-1
- value expressions PG:5-5, PR:3-18
- with** PR:3-15
- writing data PG:6-1
- gds**
 - blob calls PG:8-15
 - call parameters PG:12-4
 - date routines DR:5-9, DG:4-9, DS:3-10
 - status codes list PR:A-4
 - gds.authorize*, see appropriate platform Installation Guide
 - gds_\$attach_database** DO:3-10, PG:12-4, PG:12-7, PG:12-11
 - gds_\$blob_info** PG:12-28
 - gds_\$cancel_blob** PG:8-15, PG:8-16
 - gds_\$cancel_events**, see V3.1 Release Notes
 - gds_\$close_blob** PG:8-15, PG:8-17
 - gds_\$create_blob** PG:8-15, PG:8-17
 - gds_\$create_blob2** PG:12-4, PG:12-32, PG:12-33
 - gds_\$create_database** PG:12-4, PG:12-7, PG:12-8
 - gds_\$database_info** PG:12-26
 - gds_\$decode_date** DR:5-9, DG:4-9, DS:3-11, PG:14-25, PG:15-7
 - gds_\$detach_database** PG:12-17
 - gds_\$dpg_dbkey_scope** PG:12-8
 - gds_\$dpg_disable_journal** PG:12-13
 - gds_\$dpg_enable_journal** PG:12-13, PG:12-15
 - gds_\$dpg_num_buffers** PG:12-8
 - gds_\$dpg_page_size** PG:12-8
 - gds_\$dpg_verify** PG:12-13
 - gds_\$encode_date** DR:5-9, DG:4-9, DS:3-11, PG:14-25, PG:15-7
 - gds_\$event_block** PG:11-15
 - parameters PG:11-15
 - gds_\$event_counts** PG:11-16
 - parameters PG:11-16
 - gds_\$event_wait** PG:11-13
 - parameters PG:11-13
 - gds_\$events** DG:10-4
 - gds_\$get_segment** PG:8-15, PG:8-18
 - gds_\$open_blob** PG:8-15

- gds_\$open_blob2** PG:12-4, PG:12-32
- gds_\$print_status** DG:7-7, PG:12-3, PR:A-3
- gds_\$put_segment** PG:8-15, PG:8-19
- gds_\$squad** DS:3-11
- gds_\$sque_events** PG:11-13
parameters PG:11-14
- gds_\$reconnect_transaction** DO:3-10
- gds_\$start_multiple** PG:12-4, PG:12-18, PG:12-20
- gds_\$start_transaction** PG:12-18, PG:12-20
- gds_\$tpb_concurrency** PG:12-19
- gds_\$tpb_consistency** PG:12-19
- gds_\$tpb_ignore_limbo** PG:12-19
- gds_\$tpb_lock_level** PG:12-19
- gds_\$tpb_nowait** PG:12-19
- gds_\$tpb_read** PG:12-19
- gds_\$tpb_wait** PG:12-19
- gds_\$tpb_write** PG:12-19
- gds_\$strans** PG:2-4
- gds_\$transaction_info** DO:3-10, PG:12-30
- gds_cserver**, see appropriate platform Installation Guide
- gds_dnet_server**, see VMS Installation Guide
- gds_drop**, see appropriate platform Installation Guide
- gds_g.a.**, see Sun Installation Guide
- gds_inet_server**, see appropriate platform Installation Guide
- gds_server**, see Apollo Installation Guide
- get_segment** PG:8-5, PR:4-57
- get_slice**, see V3.1 Release Notes
- gfix**
activating DO:5-11
committing DO:3-8
errors DO:6-21–DO:6-22
examples DO:6-20–DO:6-21
housekeeping option DO:3-2
limbo transactions DO:3-7–DO:3-9
options DO:3-2, DO:3-8, DO:6-18
overview DO:3-1, DO:6-18, GS:1-11
sweep option DO:3-2
transaction recovery DO:3-7
troubleshooting DO:6-21–DO:6-22
two-phase commit DO:3-7
- Global field**
advantages DG:4-2
attributes DG:4-2
defining with GDML QG:6-4
deleting QG:6-5
modifying DR:5-62
overview GS:3-4
showing QR:3-126
- Global variables**
declaring in QLI QG:5-16
- gltj**
-debug option DO:4-5
debugging DO:4-5
definition DO:4-2
errors DO:6-24–DO:6-25
options DO:6-24
overview DO:6-24
starting on UNIX DO:4-5
starting on VMS DO:4-15
troubleshooting DO:6-24–DO:6-25
- gpre**
array processing PG:7-15
cache size, see V3.2 Release Notes
d_float flag, see V3.1 Release Notes
database option PG:18-6
date field PG:10-1
definition PG:1-2
errors PG:4-9
examples PG:18-8
file extensions PG:18-3
language options PG:18-3
language specification PG:18-2
language support PG:1-3
manual option PG:2-4, PG:18-7, PR:4-77
options PG:18-6
output option PG:18-7
overview PG:18-1, GS:1-10
preprocessing programs PG:4-16, PG:13-

DG: Data Definition Guide
DO: Database Operations
DR: DDL Reference
DS: DSQL Guide

FO: Forms Guide
GS: Getting Started
PG: Programmer's Guide
PR: Programmer's Reference

QG: QLI Guide
QR: QLI Reference
SP: Sample Programs

12, PG:18-1
raw option PG:18-7
 requests PG:1-4
 reserved words PR:2-3
 symbols PR:2-2
 syntax platform PG:18-2
 using PG:18-2
grant GS:3-8, PG:13-6, PG:16-8, PR:6-46,
 QG:6-19, QR:3-69, see V3.2 Release Notes
group by PR:5-18, QG:4-7, QR:2-25
 SQL PG:14-11
grst
date timestamp DO:4-12
 definition DO:4-2
 errors DO:6-26
 example DO:6-26
 option DO:6-26
 overview DO:6-26, GS:1-11
 troubleshooting DO:6-26

H

having PG:14-12, PR:5-19, QG:4-8, QR:2-26
 Headers for QLI field display DG:4-21
help QR:3-71
 Help in QLI QR:3-71
 Heterogeneous networks
 overview DG:3-2
 using **gbak** on DO:2-5
 Homogeneous networks DG:3-2
 Host language
 array base differences PG:7-4
 array delimiter differences PG:7-4
 array dimension differences PG:7-6
 array subscript order differences PG:7-6
 consideration overview PG:3-1
 subscript value differences PG:7-5
 using GDML with PG:4-1
 Host language variable
 assigning in GDML PG:6-3
 assigning in SQL PG:13-4
 assigning values to row PG:15-2
 Host language variables

SQL PR:5-10
housekeeping, gfix option DO:3-2
 HP cluster configuration, see V3.1 Release Notes
 HP-UX, see UNIX
 Hyphen QR:3-95

I

if-else QR:3-74
in
 DDL DR:4-16
 SQL PG:14-10, PR:5-5, QG:4-6, QR:2-11,
 QR:2-14
inactive DR:5-29
include sqlca in Ada DS:4-6
 Index
active/inactive DR:5-29
 ascending DR:5-29, DG:6-9
 considerations DG:6-10
 creating PR:6-12, QR:3-17
 defining DR:5-28, DG:6-8, DG:7-4,
 GS:3-7, QR:3-30
 defining in QLI QG:6-12, QG:6-17
 definition DG:6-1
 deleting DG:6-11, PG:16-6, QG:6-13,
 QR:3-41
 descending DR:5-29, DG:6-9
 descending sort PG:16-6
 dropping PR:6-34, QR:3-46
 duplicates DR:5-29, PG:16-6
 examples DG:6-8
 modifying DG:6-10, QG:6-13, QR:3-87
 multi-segment DG:6-9, QR:3-30
 navigating QG:6-12, QG:6-17
 nulls DG:7-4
 overview DG:6-1
 performance, see **unique**
 restrictions QR:3-30
 retrieval PG:16-6
 showing QR:3-126
 single-segment QR:3-31
unique DR:5-28–DR:5-29, DG:6-8,
 DG:7-4, QR:3-30

DG: Data Definition Guide
 DO: Database Operations
 DR: DDL Reference
 DS: DSQL Guide

FO: Forms Guide
 GS: Getting Started
 PG: Programmer's Guide
 PR: Programmer's Reference

QG: QLI Guide
 QR: QLI Reference
 SP: Sample Programs

- when to define DG:6-8
 - Indicator parameters PG:15-6
 - input_type** DR:5-23
 - insert**
 - QLI QG:5-8, QR:3-79
 - SQL GS:4-7, PG:13-6, PG:15-2, PR:6-49
 - Insert privilege QR:3-69
 - Installing InterBase, see appropriate platform Installation Guide
 - Integer, see Short datatype, Long datatype
 - Integrity of data, see Data integrity
 - Interactive **gdef** DG:3-12
 - interbas.jrn* DO:4-2
 - InterBase
 - architecture GS:1-5
 - components GS:1-8
 - fax number DO:3-5, DO:6-19, DR:A-2
 - optional modules GS:6-6
 - specifications GS:B-1
 - utilities list GS:1-10
 - isc** entry point, see V3.1 Release Notes
 - isc_functions** table DG:9-10
 - iscinstall**, see appropriate platform Installation Guide
 - isconvert**, see appropriate platform Installation Guide
 - Item list buffer PG:12-24
- J**
- Joining relations
 - cross**, PR:3-13
 - deleting QR:3-39, QR:3-53
 - for** loop for outer join QG:3-20
 - from two databases QG:3-21
 - modifying QR:3-134
 - more than two relations QG:3-19
 - overview DR:4-14
 - Joining tables PG:14-16
 - journal.addr* DO:4-5
 - journal.gbak* DO:4-6
 - journal.gdb* DO:4-6
 - journal.log* DO:4-5
- Journaling
- advantages and disadvantages DO:4-4
 - components DO:4-2
 - diagram DO:4-3
 - disaster recovery DO:4-10
 - files used DO:4-5
 - monitoring status DO:4-16
 - overview DO:4-1, GS:7-2
 - permanent journal file DO:4-2
 - restoring to time and date DO:4-12
 - UNIX DO:4-5–DO:4-13, see also UNIX Installation Guide
 - VMS DO:4-14–DO:4-25, see also **gljtj**, After image journaling
- K**
- Key, see Foreign key, Primary key
- L**
- Language
- DDL options DR:2-3
 - gpre** options PG:18-3
 - specifying in programs PG:18-2
 - support PG:3-1
- Licensing InterBase, see appropriate platform Installation Guide
- like**
- QLI QR:2-11
 - SQL PG:14-9, PR:5-4, QG:4-5
- Limbo transactions DO:3-7–DO:3-9
- Limbo transactions, see V3.2 Release Notes
- Line
- continuation in QLI QG:1-7, QR:3-122
 - length QR:3-109
 - number of QR:3-121
- Linking programs
- Apollo PG:19-3
 - overview PG:19-1
 - UNIX PG:19-3
 - VMS PG:19-3
- list**, **gfix** option DO:3-8
- Local field GS:3-4

DG: Data Definition Guide
 DO: Database Operations
 DR: DDL Reference
 DS: DSQL Guide

FO: Forms Guide
 GS: Getting Started
 PG: Programmer's Guide
 PR: Programmer's Reference

QG: QLI Guide
 QR: QLI Reference
 SP: Sample Programs

- Local variables
 - declaring PG:4-5
 - declaring in QLI QG:5-17
 - uses PG:4-5
- Lock header, see appropriate platform
 - Installation Guide
- Lock manager, see appropriate platform
 - Installation Guide
- lock table** PG:16-3
- Long datatype DG:4-4
- Long-term journaling, see After image journaling
- Loop, see **for**

- M**
- Major codes in **gds** PR:A-2, PR:A-4
- matching**
 - DDL DR:4-6
 - GDML PG:5-16, PR:3-6, QR:2-5
 - QLI QG:3-8
- matching using**
 - GDML PG:5-16, PR:3-7
- matching_language** QR:3-127
- max** (maximum) DR:4-19, PG:14-21, QG:2-17
- Menu FO:1-7, FO:7-10
- Metadata
 - changing in host language program DG:12-5
 - copying QR:3-113
 - defining a view QG:6-18
 - defining an index QG:6-17
 - defining in host language program DG:12-5
 - defining in QLI DG:12-3–DG:12-5, QG:6-1
 - defining using SQL PG:16-1, QG:6-14
 - deleting an index QG:6-17
 - extracting DG:3-14
 - modifying with DYN DG:11-1
 - overview GS:3-2
 - QLI caution QG:6-1
 - restructuring QR:3-113
 - rollback exclusion QR:3-116
 - sample database definition DG:B-1
 - transaction control DG:12-3–DG:12-5
 - unsupported SQL statements/commands PG:16-3
 - user defined function DG:9-1
- min** (minimum) DR:4-19, PG:14-21, QG:2-17
- Minor codes in **gds** PR:A-2, PR:A-19
- missing**
 - DDL DR:4-7
 - GDML PG:5-16, PR:3-8
 - QLI QG:3-11
- Missing values
 - assigning DR:5-16, PG:6-7, QG:5-13
 - assigning to column PG:15-5
 - characteristics QG:3-12
 - checking for PG:15-6
 - checking for in DSQL DS:2-53
 - DDL DR:4-7
 - DSQL DS:2-53
 - GDML PR:3-8, QR:2-7
 - GDML considerations PG:5-17
 - in fields DG:4-16
 - modifying rows with PG:15-11
 - overview QG:3-12
 - selecting rows in SQL PG:14-12
 - SQL PG:14-12, QG:4-8
 - storing records with PG:6-6
- modify** PR:4-59, QG:2-19, QG:5-4, QR:3-84
- modify database**
 - DDL DR:5-59–DR:5-61
 - gdef** DG:3-9
- modify field**
 - DDL DR:5-62–DR:5-64, DG:4-22
 - QLI QR:3-86
- modify index**
 - DDL DR:5-65–DR:5-66
 - QLI QG:6-13, QR:3-87
 - using DG:6-10
- modify relation**
 - adding field DG:4-1

DDL DR:5-67–DR:5-70, DG:4-22
 modifying field DG:4-1, DG:4-24
 QLI QG:6-10, QR:3-89

modify trigger

DDL DR:5-71–DR:5-73
 using DG:7-11

modify view

DDL DR:5-74–DR:5-75

Modifying data

overview GS:4-8
 QLI QR:3-7, QR:3-113, QR:3-134
 SQL DG:6-7

Modifying data definitions with DYN
 DG:11-7

Mouse support on Apollo FO:A-1

Moving a database DO:2-5

Multi-database access GS:4-3

Multi-dimensional array, see Array

Multi-file database

accessing DO:6-5
 creating DO:2-10, DG:3-5
 primary file DO:6-5, DR:5-2, DG:3-5
 secondary file DO:6-5, DR:5-2, DG:3-5
 writing to InterBase database DG:3-6

**Multi-generational architecture GS:1-2,
 GS:1-3, GS:4-2**

Multiple databases

accessing GS:4-3
 DSQL DS:1-8

Multiple databases, accessing DG:3-2

Multiple triggers DG:7-8

Multi-segment index DG:6-9, QR:3-30

N

nested for loops GS:5-2

Network

accessing databases on DO:6-5
 defining databases on DG:3-2
 heterogeneous DG:3-2
 homogeneous DG:3-2
 node name formats DG:3-4
 using InterBase on GS:1-5

Network servers, see appropriate platform

Installation Guide

new_page

print option QR:3-94
 report option QR:3-110

NFS

database format information DG:3-5

no_validity DO:2-8

no_wait PG:2-5

Nodes QR:3-101

Non-select statement processing in DSQL
 DS:2-3

Normalization DG:2-5

not

DDL DR:4-3
 GDML PG:5-13, PR:3-9
 order in compound boolean PR:3-2
 SQL PG:14-7

not null QR:3-20

null

DDL DR:4-11
 SQL PG:14-10, QG:4-7

Null flag

GDML PG:6-7

Null values

checking for in DSQL DS:2-53
 DDL DR:4-11
 DSQL DS:2-53
 indexes DG:7-4

Numeric field characters DR:5-15

numeric literal

DDL DR:4-12

Numeric literal expression

DDL DR:4-12
 GDML PR:3-20
 QLI QG:2-14, QR:2-30

O

Object

defined DG:8-1
 in security scheme DG:8-1

ODS, see On-disk structure

OLCP

characteristics GS:1-2

- using InterBase utilities in GS:1-7
- On Disk Structure changes, see V3.0 Release Notes
- on_error** FO:7-17, PR:4-61
- On-disk structure (ODS) DO:2-11
- Online help
 - QLI QG:1-14
- opaque** FO:9-7
- open**
 - SQL PR:6-54
- open cursor**, DSQL DS:2-2
- Open System Relation Interface, see OSRI
- open**, DSQL DS:2-2
- open_blob**
 - definition PG:8-5
 - GDML PR:4-67
- Opening a database, see **ready**
- Operators
 - all** in SQL PG:14-11, QG:4-4
 - and** in GDML PG:5-13
 - and** in SQL PG:14-7
 - any** in GDML PG:5-16
 - any** in SQL PG:14-11, QG:4-4
 - containing** in GDML PG:5-15
 - exists** in SQL PG:14-10, QG:4-5
 - in** in SQL PG:14-10, QG:4-6
 - like** in SQL PG:14-9, QG:4-5
 - matching** in GDML PG:5-16
 - matching using** in GDML PG:5-16
 - missing** in GDML PG:5-16
 - not** in GDML PG:5-13
 - not** in SQL PG:14-7
 - null** in SQL PG:14-10, QG:4-7
 - or** in GDML PG:5-13
 - or** in SQL PG:14-7
 - some** in SQL PG:14-11
 - starting with** in GDML PG:5-15
 - unique** in GDML PG:5-16
- Options, see Switches
- or**
 - DDL DR:4-3
 - GDML PG:5-13
 - order in compound boolean PR:3-2
 - SQL PG:14-7
- order by** PG:16-6
 - SQL QG:4-10
- Orphan pages DO:3-3
- OSRI
 - Apollo C database attachment example PG:12-16
 - Apollo C transaction example PG:12-22
 - Apollo database creation example PG:12-10
 - attaching a database PG:12-11
 - blob calls PG:8-15
 - blob creating PG:12-33
 - blob opening PG:12-32
 - blob parameter blocks PG:12-32
 - C database creating example PG:12-10
 - checking active transactions PG:12-30
 - checking open blobs PG:12-28
 - components PG:12-3
 - creating/attaching a database PG:12-7
 - database creating PG:12-8
 - database detachment PG:12-17
 - database info checking calls PG:12-26
 - database parameter blocks PG:12-7
 - gds** call parameters PG:12-4
 - item list buffer PG:12-24
 - journaling option PG:12-15
 - numeric values PG:12-5
 - overview PG:12-1
 - parameter blocks PG:12-4
 - programming events PG:11-13
 - result buffer PG:12-25
 - starting/stopping transactions PG:12-18
 - status information calls PG:12-24
 - status vector PG:12-3
 - transaction parameter blocks PG:12-18
 - VAC C transaction example PG:12-20
 - VAX C database attachment example PG:12-14
- Outer join
 - using nested **for** loop PG:5-12
- output_type** DR:5-23
- overriding** FO:9-6

Overview

- database operations DO:1-1
- database recovery DO:2-1
- Overview of InterBase GS:1-1

P

Page range

- in database files DG:3-5

Page size

- changing DO:2-9
- examples DO:2-9
- guidelines DO:2-9
- overriding default DR:5-3, DG:3-7, QR:3-15
- when printing report QR:3-109
- when to increase DG:3-7

Parameter blocks

- event PG:11-15
- OSRI PG:12-4, PG:12-7
- transaction PG:12-18

Partial-key dependency DG:2-6

Pascal

- array considerations PG:7-24
- array example PG:7-23
- date field example PG:10-7
- DSQL program examples SP:4-27
- DYN example DG:11-11–DG:11-12, DG:11-16–DG:11-17
- GDML considerations PG:3-11
- GDML program example SP:2-51
- missing values in DSQL DS:2-57
- null indicator, setting up local storage for DSQL in DS:2-57
- null values in DSQL DS:2-57
- setting up the SQLDA DS:2-9, DS:2-17, DS:2-26, DS:2-42, DS:4-4
- SQL considerations PG:3-11
- SQL example SP:3-20
- SQLDA setup DS:4-4

Percent sign QR:2-11

Performance

- changing page size to improve DO:2-9
- improvement DO:2-3

Pictor GS:6-6

PL/1

- DSQL example SP:4-39
- DYN example DG:11-17–DG:11-18
- GDML considerations PG:3-13
- GDML example SP:2-79
- SQL considerations PG:3-13
- SQL example SP:3-23
- SQLDA setup DS:4-5

Post-trigger indicator DG:7-6

Predicate expressions QR:2-9

Predicate expressions in SQL PR:5-2

prepare

- DSQL DS:2-2
- GDML PR:4-69
- QLI QR:3-91
- SQL PR:6-57

Preprocessing programs GS:4-13

Pre-trigger indicator DG:7-6

Primary file, see Multi-file database

Primary key DR:5-28, DG:2-3, DG:7-2

print QG:3-2, QR:3-93

print then modify QG:5-3

Privileges on VMS, see VMS Installation Guide

Privileges, see Security

Procedures in QLI

- aborting QR:3-3
- conditional branching QG:7-11
- copying QG:7-7, QR:3-14
- database handles in QG:7-9
- defining QG:7-3, QR:3-33
- deleting QG:7-8, QR:3-39
- echoing QR:3-121
- editing QR:3-51
- external command QG:7-14
- modifying QG:7-7
- overview QG:7-1
- renaming QG:7-7, QR:3-104
- running QG:7-6
- showing QR:3-125
- storing QG:7-9
- using default editor QG:7-3

Processes, see VMS Installation Guide
 Processing non-select statements
 DSQL DS:2-3–DS:2-12
 Processing **select** statements with the
 SQLDA, DSQL DS:2-13–DS:2-29
 Projecting QR:2-17
 see also **reduced to**
prompt, **gfix** option DO:3-8
 Prompting expressions PG:6-2
 Prompts in QLI GS:2-4, QR:3-122
 Prototyping applications GS:2-1
 Proxy accounts, see V3.1 Release Notes
public PG:16-8
put_item
 described FO:9-17
 GDML PR:4-71
put_segment PG:8-5, PG:8-6, PR:4-74
put_slice, see V3.1 Release Notes
 Pyxis
 relation to forms FO:1-3

Q

QLI

accessing user defined functions DG:9-15
 aggregate expressions list QG:2-17
 alternate column names DG:4-21
 alternate field names DG:4-20
 arithmetic expression QG:2-15
 array examples QG:3-27
 assessing data using SQL QG:4-1
 assigning values QG:5-2, QG:5-5
 blob fields QG:5-10
 blob filters DG:4-12
 blob segment length DG:4-10
 buffer size QG:1-9
 case sensitivity QG:1-5
 changing display QG:1-13
 closing database QG:1-16
 commands defined QG:1-6
 converting to GDML QG:11-2
 converting to SQL QG:11-3
 correcting mistakes GS:2-4, QG:1-5
 database definition QG:6-3

defining data DG:12-3
 direct assignments QG:2-20
 edit strings DG:4-19
 ending session QG:1-16
 erasing records QG:5-18
 error reporting QG:1-12
 example format QG:1-13
exists QR:2-10
exit QG:1-16, QG:10-7
 expressions QR:2-1
 external command procedures QG:7-14
finish QR:3-63
first QR:2-13, QR:2-29
for QR:3-65
 formatting dates QG:3-24
 forms using QG:9-1
 functions DG:9-15
grant QR:3-69
group by QR:2-25
having QR:2-26
help QR:3-71
in QR:2-11, QR:2-14
 joining records QG:2-8
like QR:2-11
 line continuation QG:1-7
 metadata caution QG:6-1
 metadata overview QG:6-1
 metadata updating DG:12-3
 modifying a record QG:2-19, QG:5-4
 non-interactive QLI QG:1-10
 numeric literal expression QG:2-14
 online help QG:1-14
 overview GS:1-11, GS:2-1, QG:1-1
print QG:3-2
 procedures QG:7-1
 prompts QG:1-5
 quoted string QG:2-14
 record selection formation QG:2-4,
 QG:3-2
 relation copying QG:6-7
 relation to **gdef** DG:1-2
restructure DG:5-8, DG:5-9
 retrieving data QG:2-3

saving changes QG:1-16
 search conditions QG:3-6
set no semicolon QG:1-7
set semicolon QG:1-7
show GS:3-3
show function DG:9-8
 show open databases QG:1-16
 special purpose transactions QG:10-9
 specifying column headers QG:3-24
 SQL search conditions QG:4-3
 starting QG:1-5
 startup files QG:1-8
 statements defined QG:1-6
 storing data QG:2-19, QG:5-5
 summary of functions DG:1-2
 supported features GDML/SQL QG:A-2
 transaction model QG:10-4
 transactions DG:12-3, QG:1-16
 transferring data DG:5-7
 trigger messages DG:7-7
 user-defined function support QG:2-18
 uses QG:1-2
 using GDML QG:3-1
 value expressions QG:2-3, QG:2-13,
 QG:5-3
 writing data QG:5-1
 writing SQL select expression QG:4-2
 Query header DG:4-21
 Query name DG:4-21
query_header DR:5-17, DG:4-21
query_name DR:5-18, DG:4-20, QR:3-61
 Question mark QR:2-5
quit QR:3-98
 QLI QG:10-7
 Quotas, see VMS Installation Guide
 Quotation marks GS:4-9
 Quoted string
 GDML PG:5-6, PR:3-20
 QLI QG:2-14, QR:2-30
 DDL DR:4-13

R

rdb\$, see System relations/variables
rdb\$files DO:5-4–DO:5-5
rdb\$user_name DG:8-11
 Rdb/VMS, see VMS Installation Guide
read_only PG:2-5
read_write PG:2-5
ready
 GDML PG:4-4, PR:4-77
 QLI QR:3-100
 remote databases QR:3-26
 showing QR:3-127
 Record
 definition GS:2-2
 deleting in GDML PG:6-12, PR:4-27
 deleting in QLI QG:5-18
 displaying, see **print**
 grouping by value QG:4-7
 limiting retrieval PG:5-19
 modifying in QLI QG:2-19, QG:5-4
 removing from stream PR:4-27
 retrieving limited number QG:3-17
 retrieving unique values QG:3-17
 selecting in GDML PG:5-5
 selecting in QLI QG:2-5, QR:3-118
 selecting in SQL PR:6-63
 sorting in GDML PG:5-18, QG:3-14
 sorting in SQL QG:4-10
 storing in GDML PG:6-2, PR:4-99
 storing in QLI QG:5-7
 storing in SQL PR:6-49
 storing multiple QG:5-5
 storing using **for** loop QG:5-7
 Record selection expression
 DDL DR:4-14
 formatting dates QG:3-24
 formatting output QG:3-23
 GDML PR:3-11
 QLI QG:2-4, QG:3-2, QR:2-13
 retrieving unique values QG:4-12
 specifying column headers QG:3-24
 Record stream
 creating PG:5-2, PR:4-92

DG: Data Definition Guide
 DO: Database Operations
 DR: DDL Reference
 DS: DSQL Guide

FO: Forms Guide
 GS: Getting Started
 PG: Programmer's Guide
 PR: Programmer's Reference

QG: QLI Guide
 QR: QLI Reference
 SP: Sample Programs

- sorting PG:5-18
- start_stream** PG:5-2
- using **for** loop PG:5-2
- Recovery
 - automatic DO:3-7, GS:7-2
 - database DO:2-1
 - gfix** DO:3-7
 - overview GS:1-3
 - repairing corrupt database DO:3-4
 - see also Journaling, Shadowing, Two-phase commit
 - transaction DO:3-7
 - UNIX DO:4-10–DO:4-13
 - VMS DO:4-21–DO:4-23
- Recursive query GS:5-3
- reduced to**
 - DDL DR:4-15–DR:4-16
 - erase caution QG:5-18
 - GDML PG:5-20, PR:3-15, QR:2-17
- Referential integrity DG:7-2, DG:7-15
- Reflexive join
 - QLI QG:2-11
- Registering InterBase, see appropriate platform Installation Guide
- Relation
 - adding a new field DG:5-2
 - adding existing field DG:5-3, QR:3-89
 - adding new field QR:3-89
 - computed field DG:5-5, DG:5-13
 - copying in QLI QG:6-7
 - defining in DDL DR:5-31–DR:5-36, DG:5-1, GS:3-5, QR:3-33
 - defining in QLI QG:6-6
 - defining using SQL QG:6-16
 - deleting in GDML DG:5-14
 - deleting in QLI QG:6-11, QR:3-39
 - deleting using SQL QG:6-16
 - external DG:5-6
 - joining overview GS:2-3
 - joining to itself using SQL QG:4-14
 - joining two relations using SQL QG:4-14
 - joining using GDML QG:3-19
 - joining using SQL QG:4-13
 - modifying in GDML DG:5-12
 - modifying in QLI QG:6-10
 - modifying using SQL QG:6-16
 - moving data between QG:6-8
 - overview DG:5-1
 - selecting in GDML PG:5-10
 - selecting using SQL QG:4-2
 - showing QR:3-125
 - system DG:A-1
- Relation clause DR:4-16, PG:5-10, QG:3-3, QR:2-14
- Relation clause in GDML PR:3-12
- Relational database theory GS:2-2
- Relational model QG:2-1
- Relational terminology QG:2-2
- release**
 - SQL PG:13-11
- release_requests** PR:4-81
- Remote database
 - accessing DO:2-6, DR:5-3
 - accessing, see also V3.1 Release Notes
 - backing up DO:2-6
 - creating DG:3-4
 - file specification QR:3-100
- rename procedure** QG:7-7
- Repairing corrupt database DO:3-4
- repeat**
 - QLI QG:2-19, QG:5-5, QR:3-106
- Repeating group DG:2-5
- Report
 - at bottom of** QG:8-6
 - at top of** QG:8-4
 - components QG:8-2
 - control breaks QG:8-4, QG:8-6
 - formatting QG:8-5
 - generating QG:8-3
 - running count** QG:8-6
 - running total** QG:8-6
 - running with procedures QG:8-4
- report**
 - QLI QG:8-3
 - QLI statement QR:3-108

DG: Data Definition Guide
 DO: Database Operations
 DR: DDL Reference
 DS: DSQL Guide

FO: Forms Guide
 GS: Getting Started
 PG: Programmer's Guide
 PR: Programmer's Reference

QG: QLI Guide
 QR: QLI Reference
 SP: Sample Programs

Report writer
 overview GS:6-4, QG:8-1, QR:3-108
report_header QR:3-110
report_name QG:8-5
 Reserved words list PR:2-3
 Reserved words, **gdef** DR:3-2
reserving
 definition PG:2-6
 options PG:2-6
 Restoring a database
 Apollo DO:2-7
 see also **gbak**
 summary DG:3-15
 UNIX DO:2-7
 VMS DO:2-7
 without **valid_if** DO:2-8
 Restoring journal files, see **grst**
restructure QG:6-8, QR:3-113
 Result buffer PG:12-25
 Retrieving data overview GS:4-4
revoke PG:13-6, PG:16-9, PR:6-59,
 QG:6-19, QG:6-22, QR:3-114
rollback
 GDML PG:4-13, PR:4-88
 QLI QG:1-16, QG:10-6, QR:3-116
 SQL PG:13-11, PR:6-61
 RSE, see Record selection expression
running count QG:8-6, QR:2-31
running total QG:8-6, QR:2-31

S

Sample database
 accessing GS:2-5, QG:1-4
 definition PG:A-1, QG:1-3
 Sample forms programs FO:C-1
 Sample programs SP:1-2
save PG:4-13, PR:4-90
 Scalar expressions PG:15-2, PR:5-7,
 QR:2-19
 Scale factor DG:4-4
 Scale of numerics DR:5-9, DG:4-4
 Search
 GDML PG:5-13

SQL PG:14-7, PG:14-11, QG:4-3
 Secondary file, see also Multi-file database
 DO:6-5
 Security
 access control list (ACL) DG:8-4, DG:8-6
 access privileges DR:5-38, DG:8-2
 ACL (access control list) DG:8-4, DG:8-6
 assigning to an object DR:5-19, DG:8-7
 changing DG:8-14
 considerations for defining classes
 DG:8-6
 creating tables and QR:3-20
 database PG:16-10
 defining DR:5-37, DG:8-4, GS:3-8
 designing the scheme DG:8-8
 displaying privileges QG:6-21
 examples DG:8-4–DG:8-6, DG:8-11–
 DG:8-13
gbak effect on DG:8-6
gdef effect on DG:8-6
 granting privileges PG:16-8, PR:6-46,
 QG:6-19
 hierarchy DR:5-38, DG:8-3
 modifying DG:8-14
 modifying class QG:6-6
 object DG:8-1
 order of access definitions DG:8-8
 overview DG:8-1
public PG:16-8
 revoking privileges PG:16-9, PR:6-59,
 QG:6-19, QG:6-22
 see also **grant**, **revoke** DG:8-1, QR:3-20
 views DG:8-9
with grant option PG:16-9
security_class
 DDL DR:5-19–DR:5-20, DR:5-32
 showing QR:3-127
select
 SQL GS:4-4, PG:13-6, PG:14-2, PR:5-13,
 PR:6-63, QG:4-2, QR:3-118
 Select expression
all QG:4-4
any QG:4-4

- exists** QG:4-5
- having** QG:4-8
- in** QG:4-6
- like** QG:4-5
- null** QG:4-7
- subquery QG:4-16
- writing using SQL QG:4-2
- Self join
 - QLI QG:2-11
- Semicolon QR:3-122
- set** PG:15-9, QR:3-121
- set columns** QG:8-7, QR:3-109
- set form** FO:6-3, QG:9-2
- set generator**, see V3.2 Release Notes
- set lines** QR:3-109
- set matching_language**
 - QLI QG:3-10
- set no semicolon** QG:1-7
- set semicolon** QG:1-7, QR:3-122
- Shadow file, see Shadowing, defining
- Shadow set, see Shadowing, multi-file
- Shadowing
 - activating DO:5-11
 - adding file DO:5-7
 - advantages and disadvantages DO:5-3
 - components DO:5-2
 - defining DO:5-4, DR:5-41–DR:5-42, DG:3-7
 - deleting DO:5-9
 - errors DO:5-12
 - multi-file DO:5-6–DO:5-7, DR:5-41
 - overview DO:5-1, DO:5-3, GS:7-3
 - transaction considerations DO:5-10
 - troubleshooting DO:5-12
- Sharing data across networks DG:3-2
- shell** QR:3-124
- Short datatype DG:4-4
- show**
 - overview GS:3-3
 - QLI QG:1-14, QR:3-125
- show databases** QG:1-16
- Single-file database DG:3-3
- Single-segment index QR:3-31
- skip** QR:3-94
- some**
 - SQL PG:14-11
- sorted by**
 - GDML PG:5-18, PR:3-16, QR:2-17
- Sorting records
 - case sensitivity QG:3-15
 - GDML PG:5-18, QG:3-14
 - SQL QG:4-10, QR:3-118
- Source files DG:1-3, DG:11-3
- space**
 - print option QR:3-94
 - report option QR:3-110
- SQL
 - accessing multiple databases PG:17-3
 - Ada considerations PG:3-2
 - Ada example program SP:3-3
 - aggregate functions PG:14-21
 - aliases PG:14-17, QG:4-13
 - all** QG:4-4
 - alter table** PR:6-2
 - any** QG:4-4, QG:4-5
 - assessing data in QLI QG:4-1
 - BASIC considerations PG:3-4
 - BASIC example program SP:3-7
 - between** PR:5-3
 - blob accessing PG:17-6
 - C considerations PG:3-5
 - C example program SP:3-10
 - close** PR:6-4
 - COBOL considerations PG:3-7
 - COBOL example program SP:3-13
 - column projecting PG:14-15
 - column values assigning PG:15-2
 - commit** PR:6-6
 - communication area PG:13-3
 - compare** PR:5-2
 - compared to GDML GS:C-1
 - constant expression PR:5-9
 - converting from QLI QG:11-3
 - create index** PR:6-12
 - create table** PR:6-14
 - create view** PR:6-17

- creating a table QG:6-16
- cursor closing PG:14-5, PR:6-61
- cursor declaration GS:4-5, PG:14-3, PR:6-19
- cursor opening PG:14-4, PR:6-54
- data defining DG:12-5
- data deleting GS:4-11
- database components definable by GS:3-2
- database creating PG:16-4
- database definition QG:6-15
- database dropping PR:6-33
- database naming PG:13-5
- dates accessing PG:17-10
- defining metadata QG:6-14
- definition PG:1-2
- delete** PR:6-28
- deleting a database QG:6-15
- deleting data PG:15-14
- deleting data through a view PG:15-16
- drop view** PR:6-36
- embedded statements PG:13-6
- error handling PG:13-7
- error recovery PG:13-7
- execute** PR:6-37
- exists** PR:5-6
- fetch** PR:6-41
- field expressions PR:5-8
- FORTTRAN considerations PG:3-8
- FORTTRAN example program SP:3-16
- GDML comparison GS:1-8, GS:C-1
- getting started with PG:13-1
- grant** GS:3-8, PR:6-46
- granting privileges QG:6-19
- group by** PR:5-18
- having** PR:5-19, QG:4-8
- host variables PG:13-4, PR:5-10
- implementing features in QLI QG:A-2
- in** PR:5-5, QG:4-6
- inner join PG:14-16
- insert** PR:6-49, QG:5-8
- like** PR:5-4, QG:4-5
- metadata considerations PG:16-2
- metadata definition PG:16-1
- missing values PG:14-12, QG:4-8
- mixing with other interfaces PG:17-1
- modifying a table QG:6-16
- modifying data through a view PG:15-13
- modifying data, see **update**
- null** QG:4-7
- Pascal considerations PG:3-11
- Pascal example program SP:3-20
- PL/1 considerations PG:3-13
- PL/1 example program SP:3-23
- preprocessing program PG:13-12
- privilege revoking PR:6-59
- program portability PR:A-20
- programming example PG:13-13
- quotation marks GS:4-9
- retrieving data overview PG:14-1
- revoking privileges QG:6-19, QG:6-22
- sample database definition PG:16-11
- scalar expressions PG:15-2, PR:5-7
- search conditions QG:4-3
- searching PG:14-7, PG:14-11
- security DG:8-2, PG:16-8
- select expression PR:5-13
- selecting data GS:4-4, PG:14-2, PR:6-63
- selecting rows PG:14-2
- sorting records QG:4-10
- statements list PR:6-1
- statistical functions PG:14-21
- statistical functions PR:5-11
- storing data through a view PG:15-7
- storing data, see **insert**
- subqueries PG:14-24
- summary of features GS:C-1
- supported variants PG:1-2
- table PG:14-20
- table creating PG:16-5
- table deleting PG:16-5
- transaction PG:2-15
- transaction closing default PG:13-11
- transaction control PG:17-5
- update** GS:4-8, PR:6-67, QG:5-8
- using with GDML PG:17-1

DG: Data Definition Guide
 DO: Database Operations
 DR: DDL Reference
 DS: DSQL Guide

FO: Forms Guide
 GS: Getting Started
 PG: Programmer's Guide
 PR: Programmer's Reference

QG: QLI Guide
 QR: QLI Reference
 SP: Sample Programs

- view defining PG:16-7
- view deleting PG:16-7
- whenever** PG:13-7, PR:6-70, PR:A-20
- writing data PG:15-1
- writing select expression in QLI QG:4-2
- SQL descriptor area, see SQLDA
- SQL, dynamic, see DSQL
- SQLABC field DS:1-5
- SQLAID field DS:1-5
- SQLCA
 - see SQL communication area
- SQLCODE
 - correspondence with InterBase PR:A-21
 - errors PR:A-21
 - messages PG:13-7
 - printing, see V3.2 Release Notes
 - testing PG:13-8
 - using PG:13-3
- SQLD
 - field DS:1-5
 - setting up in Pascal DS:2-26
- SQLDA
 - fields DS:1-4
 - function of DS:1-4
 - introduction DS:1-4
 - overview DS:1-4
 - purpose of DS:1-4
 - retrieving contents PR:6-31
 - see also **describe**
 - setting up in Ada DS:4-6
 - setting up in BASIC DS:4-10
 - setting up in C DS:2-6, DS:2-13, DS:2-21, DS:2-30, DS:4-2
 - setting up in COBOL DS:4-11
 - setting up in FORTRAN DS:1-8, DS:4-12
 - setting up in Pascal DS:2-9, DS:2-17, DS:2-42, DS:4-4
 - setting up in PL/1 DS:4-5
 - SQLABC field DS:1-5
 - SQLAID field DS:1-5
 - SQLD field DS:1-5
 - SQLN field DS:1-5
 - SQLVAR field DS:1-5
 - SQLVAR subfields DS:1-6
 - subfields DS:1-4
 - valid datatypes DS:1-4
- SQLDATA subfield DS:1-6
- SQLIND subfield DS:1-6
- SQLLEN subfield DS:1-6
- SQLN field DS:1-5
- SQLNAME subfield DS:1-6
- SQLTYPE
 - subfield DS:1-6
 - subfield datatypes DS:1-7
 - valid datatypes DS:1-7
- SQLVAR
 - field DS:1-5
 - SQLDATA subfield DS:1-6
 - SQLIND subfield DS:1-6
 - SQLLEN subfield DS:1-6
 - SQLNAME subfield DS:1-6
 - SQLTYPE subfield DS:1-6
 - subfields DS:1-6
- start_stream** PG:4-8, PG:5-2, PR:4-92
- start_transaction** PG:2-4, PG:4-6, PR:4-95
- start_transaction using**, see V3.2 Release Notes
- starting with**
 - DDL DR:4-7
 - GDML PG:5-15, PR:3-9, QR:2-7
 - QLI QG:3-8
- Statements
 - defined in QLI QG:1-6
 - distinction from commands PG:1-4
 - gpre** PG:1-4
- Static menus FO:7-10
- Statistical expressions DR:4-19, QG:2-17, QR:2-31
- Statistical functions
 - DDL DR:4-19
 - QLI QR:2-22
 - SQL PG:14-21, PR:5-11
- Statistics of database QR:3-125
- Status vector
 - definition PG:4-9, PG:12-3

DG: Data Definition Guide
 DO: Database Operations
 DR: DDL Reference
 DS: DSQL Guide

FO: Forms Guide
 GS: Getting Started
 PG: Programmer's Guide
 PR: Programmer's Reference

QG: QLI Guide
 QR: QLI Reference
 SP: Sample Programs

error reporting PR:A-1
 printing contents PG:12-3
storage groups PG:16-3
store
 defining in programs PG:6-2, PR:4-99
 defining in QLI QG:2-19, QR:3-131
 using FO:6-5
store blob in GDML PR:4-103
 Storing data
 direct assignments in QLI QG:2-20
 GDML PR:4-99
 overview GS:4-6
 QLI QG:2-19, QR:3-7
 using forms QR:3-131
 String datatype
 see Character datatype, Varying
 datatype
 Subforms
 changing FO:4-4
 characteristics FO:4-4
 editing FO:4-1
 exiting FO:4-6
 GDML FO:7-13
 region FO:4-4
 selecting FO:4-3
 size FO:4-5
sub_item FO:4-5
 Subqueries
 assigning values to row PG:15-3
 overview GS:5-2, QG:4-16
 SQL QG:4-16
 using in SQL PG:14-24
 Substring DR:4-6, QR:2-5, QR:2-11
 Subtransaction DO:3-7
 Subtype DR:5-10, GS:5-6
sum PG:14-21, QG:2-17
 Summary of functions
 DSQL DG:1-2
 DYN DG:1-2
 Embedded SQL DG:1-2
gdef DG:1-1
 QLI DG:1-2

Sun
 file specifications DO:6-5
 filter library PG:9-12
fred implementation FO:A-4
fred keyboard diagrams FO:A-8
 functions DG:9-5, DG:9-10–DG:9-11
 journaling DO:4-2
 Supported datatypes DR:5-8
sweep, gfix option DO:3-2
 Switches
gbak DO:6-2–DO:6-5
gcon DO:6-10
gcsu DO:6-14–DO:6-15
gdef DG:3-14
gfix DO:6-18–DO:6-20
gltj DO:4-5, DO:6-24
grst DO:6-26
 System relations/variables
 changing DG:12-3
 definition DG:3-9, GS:3-3
 displaying GS:3-3, QR:3-125
 list DG:A-1
rdb\$database DG:A-2
rdb\$dependencies DG:A-3
rdb\$field_dimensions DG:A-9
rdb\$field_position DG:12-3
rdb\$fields DG:4-3, DG:4-22, DG:5-2,
 DG:5-5, DG:A-4–DG:A-8
rdb\$files DG:A-10
rdb\$filters DG:A-11
rdb\$formats DG:A-12
rdb\$function_arguments DG:A-14–
 DG:A-15
rdb\$functions DG:A-13
rdb\$generators DG:A-16
rdb\$index_segments DG:12-6,
 DG:A-17
rdb\$indices DG:12-6, DG:A-18–DG:A-
 19
rdb\$pages DG:A-20
rdb\$relation_fields DG:4-3, DG:5-2,
 DG:5-4, DG:12-3, DG:A-24–DG:A-26
rdb\$relations DG:A-21–DG:A-23

rdb\$security_classes DG:8-4, DG:8-8,
 DG:A-27
rdb\$transactions DG:A-28
rdb\$trigger_messages DG:A-31
rdb\$triggers DG:A-29–DG:A-30
rdb\$types DG:A-32
rdb\$user_name QR:2-32
rdb\$user_privileges DG:A-33
rdb\$view_relations DG:A-34
 showing QR:3-125
 System variables
 see System relations/variables

T

tab

print option QR:3-94
 report option QR:3-110

Table

appending PG:14-20
 creating PR:6-14, QR:3-19
 declaring PR:6-24
 defining in QLI QG:6-16
 defining using SQL PG:16-5
 deleting QG:6-16
 deleting using SQL PG:16-5
 dropping QR:3-47
 dropping in SQL PR:6-35
 joining PG:14-16
 joining examples PG:14-18
 modifying PG:15-9
 modifying in QLI QG:6-16
 securing PG:16-8

tablespaces PG:16-3

Tape backup DO:2-5

tar DO:2-3

TCP/IP

journal files DO:4-5
 remote nodes DG:3-4

Text datatype

see Char datatype, Varying datatype

then QR:3-74, QR:3-133

Title of reports QR:3-109

Transaction

automatic recovery restrictions, see **gfix**
 checking active using OSRI PG:12-30
 closing default in SQL PG:13-11
 committing PR:4-11, QG:10-5
 committing without updating QG:10-6
 concurrency model GS:4-2, PG:2-2,
 PG:2-17, PR:4-95, QG:10-3
 consistency model GS:4-2, PG:2-2, PR:4-
 96, QG:10-3
 control in SQL PG:17-5
 database access PG:2-8–PG:2-13
 default PR:4-95
 default options GS:4-4
 definition GS:4-1, QG:10-1
 dirty reads PG:2-21
 ending PG:4-13, PR:4-11
 error recovery PG:2-16
 event control DG:10-6
 examples PG:2-7
 handle PG:2-5, PR:4-105
 lock compatibilities PG:2-6
 lost updates PG:2-20
 metadata changes in DG:12-3
 model in **gpre** PG:2-2
 model in QLI QG:10-4
 multi-generational GS:1-2, GS:1-3
 multiple GS:4-4
no_wait caution PG:2-5
no_wait option PR:4-96
 non-reproducible reads PG:2-21
 options PG:2-5, PR:4-95
 overview GS:1-2, GS:4-1, PG:2-1
 phantom records PG:2-21
 preparing QR:3-91
 quitting QR:3-98
read_only PG:2-5
read_write PG:2-5
 readying QR:3-100
 recovery DO:3-7
 recovery restrictions, see also **gfix**
 reserving PG:2-6, PR:4-96
 rolling back QG:10-6, QR:3-116

rolling back in GDML PR:4-88
 rolling back in SQL PR:6-61
 saving PR:4-90
 special purpose in QLI QG:10-9
 SQL environment PG:2-15
 starting in GDML program PG:2-4
 starting/stopping PG:2-4, PG:4-6,
 PR:4-95, QG:10-5, QR:3-55, QR:3-98
 starting/stopping using OSRI PG:12-18
 syntax PG:2-4
 triggers in DG:7-12–DG:7-15
 two-phase commit GS:4-3
 update side effects PG:2-22
wait PG:2-5
 Transitive dependency DG:2-7
 Transportable backup (XDR format)
 DO:2-5
 Trigger
 aborting DG:7-7
 accessing user defined functions DG:9-16
 action indicator DG:7-6
 activity indicator DG:7-6
 components DG:7-7
 deactivating DG:7-12
 defining DR:5-43–DR:5-48,
 DG:7-6–DG:7-9
 definition GS:1-3
 deleting DG:7-12
 examples DG:7-10, DG:7-15–DG:7-19
 language usage DR:5-45–DR:5-46
 message statement DG:7-7
 modifying DG:7-11
 multiple DG:7-8
 overview DG:7-6, GS:5-11
 posting events with DG:10-3
 relationship to other triggers DG:7-14
 sequence indicator DG:7-6
 showing QR:3-127
 time indicators DG:7-6
 transactions DG:7-13
 undoing DG:7-13
 updating DG:7-11
 views DG:7-10, QR:3-53, QR:3-79

Trigger (cont.)
 views DG:6-6
 Troubleshooting
gbak DO:6-7–DO:6-9
gcon DO:6-11–DO:6-13
gcsu DO:6-16–DO:6-17
gfix DO:6-21–DO:6-22
gl tj DO:6-24–DO:6-25
grst DO:6-26
 shadow DO:5-12
 Two-phase commit DO:3-7, DG:3-2,
 GS:4-3, QR:3-12, QR:3-91

U

UDF
 see User defined function DG:9-1
 Underscore QR:2-11
union PG:14-20
unique
 DDL DR:4-8
 GDML PG:5-16, PR:3-10
 index option DG:6-8, DG:7-4, DR:5-28,
 QR:3-30
 QLI QG:3-11, QR:2-8
 SQL PG:16-6
 Unique value retrieving
 SQL QG:4-12
 Uniqueness of relations DG:7-2
 UNIX
 backing up to tape DO:2-4
 creating databases DG:3-3
 filter library PG:9-14
 functions DG:9-5, DG:9-11–DG:9-13
gpre syntax PG:18-2
 journaling DO:4-5–DO:4-13
 linking considerations PG:19-3
 multi-file databases DG:3-6
 remote database access DO:2-6
 restoring a database DO:2-7
 security DG:8-5
 shadow DO:5-4, DO:5-11
 shell QR:3-124
tar DO:2-3

update

QLI QG:5-8, QR:3-134
 SQL GS:4-8, PG:13-6, PG:15-9, PR:6-67

User defined function

accessing DG:9-15
 accessing from **gdef** DG:9-16
 accessing from host language DG:9-15
 accessing from QLI DG:9-15, QG:2-18
 calling in program PG:5-8
 compiling DG:9-5
 creating function libraries DG:9-9
 defining DR:5-25–DR:5-27, DG:9-6–
 DG:9-8, PG:5-7, PG:5-8
 deleting DG:9-8
 function libraries DG:9-9–DG:9-14
 library PG:5-7
 overview DG:9-1, GS:1-5, GS:5-3
 using **gbak** with DO:2-8
valid_if DG:9-7
 writing and compiling DG:9-3–DG:9-5

Username expression

GDML PR:3-21, QR:2-32

using

in begin end block QG:5-6

using forms QG:9-3**Utilities**

list DO:1-3
 see **gbak**, **gcon**, **gcsu**, **gdef**, **gfix**,
 see **gltj**, **gpre**, **grst**
 summary GS:1-10, GS:7-1

V**valid_if**

DDL DR:5-20–DR:5-21
 missing values DG:4-16
 user defined function DG:9-7
 using for validation DG:7-5

Validating a database DO:3-3, DG:7-2,
 DG:7-5

Validating fields DG:4-15

value

DDL DR:4-21

Value expressions DR:4-21

arithmetic expression DR:4-2, PG:5-7

between condition DR:4-4

boolean expression DR:4-3

comparison condition DR:4-5

containing condition DR:4-6

database field PG:5-5

GDML PG:5-5, PG:6-2, PR:3-18

matching condition DR:4-6

numeric literal expressions PG:5-6

QLI QG:2-3, QG:2-13, QG:5-3, QR:2-27

quoted string PG:5-6

starting with condition DR:4-7

statistical expression DR:4-19

username expression DR:4-20

Variables

declaring global in QLI QG:5-16

declaring local in GDML PG:4-5

declaring local in QLI QG:5-17

Varying datatype DR:5-11, DG:4-7

VAX

Ada DYN example DG:11-12

BASIC DYN example DG:11-13

C DYN example DG:11-13–DG:11-14

COBOL DYN example DG:11-14–DG:11-
 15

FORTRAN DYN example DG:11-15–
 DG:11-16

Pascal DYN example DG:11-16–DG:11-
 17

PL/1 DYN example DG:11-17–DG:11-18

version QR:3-128

View

accessing multiple relations DG:6-4

defining in DDL DR:5-49–DR:5-53

defining in GDML DG:6-1, DG:6-3

defining in SQL PR:6-17

defining using SQL PG:16-7, QG:6-18

deleting DG:6-7, QR:3-53

deleting data through in SQL PG:15-16

deleting using SQL PG:16-7

dropping QR:3-48

dropping in SQL PR:6-36

examples DG:6-3–DG:6-4

limiting fields/records DG:6-3–DG:6-4
modifying DR:5-74–DR:5-75, PG:6-11,
QR:3-84, QR:3-134
modifying data through in SQL PG:15-13
overview GS:3-6
retrieving data from PG:5-10
security DG:8-9–DG:8-10
showing QR:3-128
storing data through QR:3-79
storing data through SQL PG:15-7
trigger DG:7-10

GDML PR:3-15
QLI QR:2-16
with grant option PG:16-9

VMS

backing up DO:2-4
backing up database files DO:2-3
BACKUP DO:2-3
database creating DG:3-3
database security DG:8-6
DCL QR:3-130
disaster recovery DO:4-21
filter library PG:9-16
fred keyboard diagrams FO:A-6
function DG:9-5, DG:9-13–DG:9-14
grpe syntax PG:18-2
journal files DO:4-17
journaling DO:4-2, DO:4-14–DO:4-25
linking considerations PG:19-3
multi-file database DO:6-5, DG:3-6
remote database access DO:2-6, DO:6-5
restoring a database DO:2-7
security DG:8-5
shadow DO:5-4, DO:5-11

W

wait PG:2-5
whenever PG:13-7, PR:6-70
where PG:14-12
QLI QR:2-24
Wildcard characters DR:4-6, QG:3-9,
QR:2-5, QR:2-11
Window
delete FO:7-5
with
DDL DR:4-17–DR:4-18

DG: Data Definition Guide
DO: Database Operations
DR: DDL Reference
DS: DSQL Guide

FO: Forms Guide
GS: Getting Started
PG: Programmer's Guide
PR: Programmer's Reference

QG: QLI Guide
QR: QLI Reference
SP: Sample Programs