

Fixed-Point Toolbox™

Release Notes

Summary by Version	1
Version 2.2 (R2008a) Fixed-Point Toolbox™ Software ..	4
Version 2.1 (R2007b) Fixed-Point Toolbox™ Software ..	7
Version 2.0 (R2007a) Fixed-Point Toolbox™ Software ..	10
Version 1.5 (R2006b) Fixed-Point Toolbox™ Software ..	13
Version 1.4 (R2006a) Fixed-Point Toolbox™ Software ..	15
Version 1.3 (R14SP3) Fixed-Point Toolbox™ Software	22
Version 1.2 (R14SP2) Fixed-Point Toolbox™ Software	25
Version 1.1 (R14SP1) Fixed-Point Toolbox™ Software	27
Version 1.0 (R14) Fixed-Point Toolbox™ Software	28
Compatibility Summary for Fixed-Point Toolbox™ Software	31

Summary by Version

This table provides quick access to what's new in each version. For clarification, see “Using Release Notes” on page 1.

Version (Release)	New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Latest Version V2.2 (R2008a)	Yes Details	No	Bug Reports Includes fixes	Printable Release Notes: PDF Current product documentation
V2.1 (R2007b)	Yes Details	Yes Summary	Bug Reports Includes fixes	No
V2.0 (R2007a)	Yes Details	Yes Summary	Bug Reports Includes fixes	No
V1.5 (R2006b)	Yes Details	No	Bug Reports Includes fixes	No
V1.4 (R2006a)	Yes Details	Yes Summary	Bug Reports Includes fixes	No
V1.3 (R14SP3)	Yes Details	Yes Summary	Bug Reports Includes fixes	No
V1.2 (R14SP2)	Yes Details	No	Bug Reports	No
V1.1 (R14SP1)	No	No	Yes Details	No
V1.0 (R14)	Yes Details	Not applicable	No bug fixes	No

Using Release Notes

Use release notes when upgrading to a newer version to learn about:

- New features
- Changes
- Potential impact on your existing files and practices

Review the release notes for other MathWorks™ products required for this product (for example, MATLAB® or Simulink®) for enhancements, bugs, and compatibility considerations that also might impact you.

If you are upgrading from a software version other than the most recent one, review the release notes for all interim versions, not just for the version you are installing. For example, when upgrading from V1.0 to V1.2, review the release notes for V1.1 and V1.2.

What's in the Release Notes

New Features and Changes

- New functionality
- Changes to existing functionality

Version Compatibility Considerations

When a new feature or change introduces a reported incompatibility between versions, the **Compatibility Considerations** subsection explains the impact.

Compatibility issues reported after the product is released appear under Bug Reports at the MathWorks Web site. Bug fixes can sometimes result in incompatibilities, so you should also review the fixed bugs in Bug Reports for any compatibility impact.

Fixed Bugs and Known Problems

The MathWorks offers a user-searchable Bug Reports database so you can view Bug Reports. The development team updates this database at release time and as more information becomes available. This includes provisions for any known workarounds or file replacements. Information is available for bugs existing in or fixed in Release 14SP2 or later. Information is not available for all bugs in earlier releases.

Access Bug Reports using your MathWorks Account.

Version 2.2 (R2008a) Fixed-Point Toolbox™ Software

This table summarizes what's new in Version 2.2 (R2008a):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	No	Bug Reports Includes fixes	Printable Release Notes: PDF Current product documentation

New features and changes introduced in this version are:

- “Enhanced Memory Management” on page 4
- “New Rounding Functions for fi Objects” on page 5
- “New Bitwise Operator bitreplicate” on page 5
- “New Syntax for Bitwise Operator bitconcat” on page 5
- “ndgrid Function Support for Fixed-Point Inputs” on page 6
- “New fi Constructor Syntax” on page 6

Enhanced Memory Management

The memory management of the `fi` object has been improved, and generating large multidimensional arrays should no longer hang the MATLAB® environment.

When performing computations with `fi` objects from the MATLAB command line, the memory usage in bits for the `fi` variable a is on the order of

$$\max(64, a.\text{wordlength}) * \text{numberofelements}(a)$$

The formula computes the number of bits used to store each element of an array, but does not include the overhead for each instance of the object. Similar to built-in `mxArrays`, there is additional overhead for each array. This

overhead is used to store information about data type, `fi`math properties, and other settings that do not depend on the size of the array.

If you are concerned with memory usage, try compiling with `emlmex` or `emlc`. The compiled code uses the smallest C integer type that contains the word length of the variables. For example, if the `fi` variable `a` is 8-bit, then the compiled code will use approximately $8 * \text{numberofelements}(a)$ bits of memory. The current maximum fixed-point word length in the Embedded MATLAB™ subset is 32 bits.

New Rounding Functions for `fi` Objects

Fixed-Point Toolbox™ software now provides the following `fi` object functions:

- `ceil` — Round toward positive infinity
- `convergent` — Apply convergent rounding
- `fix` — Round toward zero
- `floor` — Round toward negative infinity
- `nearest` — Round toward nearest integer with ties rounding toward positive infinity
- `round` — Round `fi` object toward nearest integer or round input data using quantizer object

These functions are also supported by the Embedded MATLAB subset.

New Bitwise Operator `bitreplicate`

Fixed-Point Toolbox software now provides the `bitreplicate` function to replicate and concatenate the bits of a `fi` object.

`bitreplicate` is also supported by the Embedded MATLAB subset.

New Syntax for Bitwise Operator `bitconcat`

The Fixed-Point Toolbox function `bitconcat` has new syntax.

For more information see the `bitconcat` reference page.

ndgrid Function Support for Fixed-Point Inputs

Fixed-Point Toolbox software now provides support for the `ndgrid` function.

New fi Constructor Syntax

Fixed-Point Toolbox software has added a new syntax for the `fi` constructor. The syntax `a = fi(V, F, T)` is now defined, and is equivalent to the existing syntax `a = fi(V, T, F)`.

See the `fi` function reference page for more information.

Version 2.1 (R2007b) Fixed-Point Toolbox™ Software

This table summarizes what's new in Version 2.1 (R2007b):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	Yes—Details labeled as Compatibility Considerations , below. See also Summary.	Bug Reports Includes fixes	Printable Release Notes: PDF Current product documentation

New features and changes introduced in this version are:

- “Support for Data Type Override” on page 7
- “New Bitwise Operator Functions” on page 7
- “bitget Function Updated” on page 8
- “abs Function Supports Complex Inputs” on page 8
- “divide Function Updated” on page 9
- “fi Constructor Applies Property/Value Pairs After Numeric Value” on page 9

Support for Data Type Override

Fixed-Point Toolbox™ software now supports data type override in Embedded MATLAB™ subset. This facilitates fixed-point design and enables a single source for fixed- and floating-point code generation.

New Bitwise Operator Functions

Fixed-Point Toolbox software now provides the following functions:

- `bitandreduce` — Bitwise AND of consecutive range of bits
- `bitconcat` — Concatenate bits of two `fi` objects
- `bitorreduce` — Bitwise OR of consecutive range of bits

- `bitrol` — Bitwise rotate left
- `bitror` — Bitwise rotate right
- `bitsliceget` — Consecutive slice of bits
- `bitsll` — Bit shift left logical
- `bitsra` — Bit shift right arithmetic
- `bitsrl` — Bit shift right logical
- `bitxorreduce` — Bitwise exclusive OR of consecutive range of bits
- `getlsb` — Least significant bit
- `getmsb` — Most significant bit

Embedded MATLAB subset also supports these functions.

bitget Function Updated

The `bitget` function now behaves as follows:

- `bitget` returns a `u1,0`.
- `bitget` supports variable indexing. This means that the position of the bit to get can be a variable instead of a constant.
- The input `fi` object and the position of the bit to get can be vectors or scalars.

For more information, see the `bitget` reference page.

Compatibility Consideration

In prior releases, this function returned a `uint8`. The function now returns a `u1,0`. To get a `uint8`, use the `uint8` function on the `bitget` output.

abs Function Supports Complex Inputs

You can now use the `abs` function to compute the absolute value of a complex `fi` object.

For more information, see the `abs` reference page.

divide Function Updated

The `divide` function now obeys the `DataTypeOverride` settings of the `fipref` object.

For more information, see the `divide` reference page.

Compatibility Consideration

In prior releases, this function did not obey the `DataTypeOverride` settings of the `fipref` object. For example, if the input was `fi ScaledDouble`, but the input `numericType` object was `fi Fixed`, the output was `fi Fixed`. The output is now `fi ScaledDouble`.

fi Constructor Applies Property/Value Pairs After Numeric Value

When you call the `fi` constructor with both a numeric value and one or more property/value pairs that change the numeric value of the `fi` object, the `fi` constructor applies the property/value pairs after it sets the numeric value of the `fi` object.

For more information, see the `fi` reference page.

Compatibility Consideration

In prior releases, the `fi` constructor applied the property/value pairs before it set the numeric value. For example, the following code used to produce a `fi` object with a value of 0:

```
a = fi(0,1,16,13,'hex','6488')
```

This code now produces a `fi` object with a value of `pi`.

Version 2.0 (R2007a) Fixed-Point Toolbox™ Software

This table summarizes what's new in Version 2.0 (R2007a):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	Yes—Details labeled as Compatibility Considerations , below. See also Summary.	Bug Reports Includes fixes	No

New features and changes introduced in this version are

- “Fast Execution for Fixed-Point Algorithms in MATLAB®” on page 10
- “New fi Syntaxes that Have fimath as an Argument” on page 11
- “Increased Support for Fixed-Point Toolbox™ Software Features in the Embedded MATLAB™ Subset” on page 11
- “Embedded MATLAB™ Subset Enhanced to Support N-Dimensional Arrays and Function Handles” on page 11
- “get Function Must be Declared Extrinsic in Embedded MATLAB™ Subset” on page 12
- “Embedded MATLAB™ Subset Does Not Support & and | Operators” on page 12
- “New Demo” on page 12

Fast Execution for Fixed-Point Algorithms in MATLAB®

The new Embedded MATLAB™ MEX functionality converts M-code to C-MEX functions. These C-MEX functions contain Embedded MATLAB subset optimizations for automatically accelerating fixed-point algorithms to compiled C code speed in MATLAB®. For more information, refer to “Working with Embedded MATLAB MEX” in the Embedded MATLAB subset documentation.

New `fi` Syntaxes that Have `fimath` as an Argument

The following syntaxes have been added to the `fi` object:

- `a = fi(v,F)`
- `a = fi(v,s,F)`
- `a = fi(v,s,w,F)`
- `a = fi(v,s,w,f,F)`
- `a = fi(v,s,w,slope,bias,F)`
- `a = fi(v,s,w,slopeadjustmentfactor,fixedexponent,bias,F)`

where `v` is value, `s` is signedness, `w` is word length, `f` is fraction length, and `F` is a `fimath` object. Refer to “Working with `fi` Objects” or the `fi` reference page for more information.

Increased Support for Fixed-Point Toolbox™ Software Features in the Embedded MATLAB™ Subset

The following Fixed-Point Toolbox™ software features are now supported by the Embedded MATLAB subset:

- Dot notation for getting the values of `fimath` properties
- `get` function for `fi` and `fimath` objects
- `diag`, `permute`, `tril`, and `triu` functions

For a complete list of the Fixed-Point Toolbox features supported by the Embedded MATLAB subset, refer to “Supported Functions and Limitations of Fixed-Point Embedded MATLAB Subset”.

Embedded MATLAB™ Subset Enhanced to Support N-Dimensional Arrays and Function Handles

Embedded MATLAB subset now supports N-dimensional arrays and function handles.

get Function Must be Declared Extrinsic in Embedded MATLAB™ Subset

There is a change to how you must use the `get` function in Embedded MATLAB subset to call properties of any object other than `fi` objects.

Compatibility Consideration

To get properties of non-`fi` objects in Embedded MATLAB subset, you must first declare `get` to be an extrinsic function. As of this release, if you do not do so, your code will error. For more information, refer to “Calling MATLAB Functions” in the Embedded MATLAB subset documentation.

Embedded MATLAB™ Subset Does Not Support & and | Operators

Embedded MATLAB subset no longer supports `&` and `|` operators in `if` and `while` conditional statements.

Compatibility Consideration

In prior releases, these operators compiled without error, but their short-circuiting behavior was not implemented correctly. Substitute `&&` and `||` operators instead.

New Demo

The “Fixed-Point Lowpass Filtering Using Embedded MATLAB MEX” demo is new in this release. This demo steps you through generating a C-MEX function from M-code, running the generated C-MEX function, and displaying the results.

Version 1.5 (R2006b) Fixed-Point Toolbox™ Software

This table summarizes what's new in Version 1.5 (R2006b):

New Features and Changes	Version Compatibility	Fixed Bugs and Known Problems	Related Documentation at
Yes Details below	No	Bug Reports Includes fixes	No

New features and changes introduced in this version are

- “Licensing Changes” on page 13
- “Fixed-Point Square Root Support” on page 13
- “Limited Dot Notation Support Added to Fixed-Point Embedded MATLAB™ Subset” on page 14
- “get Function Support Added to Fixed-Point Embedded MATLAB™ Subset” on page 14
- “New Default Syntax for fi Object” on page 14

Licensing Changes

You now can use `fi` objects with the `DataType` property set to `double` *without* a Fixed-Point Toolbox™ license when the `fipref` `LoggingMode` property is set to `off`. For details about the Fixed-Point Toolbox licensing model, refer to “Licensing” in the product documentation.

Fixed-Point Square Root Support

In this release, fixed-point square root support has been added to

- Fixed-Point Toolbox software, via the `sqrt` function
- Embedded MATLAB™ subset, via support for the Fixed-Point Toolbox `sqrt` function
- Simulink®, via fixed-point support for the `sqrt` mode of the Math Function block

These products use the same bisection algorithm to implement their fixed-point square root functionality and yield identical results.

Limited Dot Notation Support Added to Fixed-Point Embedded MATLAB™ Subset

Dot notation is now supported in Embedded MATLAB subset for getting the values of `numericType` object properties. Dot notation is not supported for `fi` or `fiMath` objects, and it is not supported for setting properties.

get Function Support Added to Fixed-Point Embedded MATLAB™ Subset

The Fixed-Point Toolbox `get` function is now supported for use with Embedded MATLAB subset with the following limitations:

- Only supported for use with `numericType` objects
- The syntax `structure = get(o)` is not supported

New Default Syntax for fi Object

You can now use the syntax `fi` without any input arguments to return a default `fi` object with no value, 16-bit word length, and 15-bit fraction length.

Version 1.4 (R2006a) Fixed-Point Toolbox™ Software

This table summarizes what's new in Version 1.4 (R2006a):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	Yes—Details labeled as Compatibility Considerations , below. See also Summary.	Bug Reports Includes fixes	No

New features and changes introduced in this version are

- “[Slope Bias] Math Support Added” on page 15
- “Scaled Double Data Type Support Added to the fi Object” on page 16
- “Global DataTypeOverride Property Added to the fipref Object” on page 16
- “Embedded MATLAB™ Subset Supports More Fixed-Point Toolbox™ Functions” on page 17
- “Embedded MATLAB™ Subset Does Not Support a CastBeforeSum Value of 'false'” on page 17
- “'round' Value Added to the fimath Object RoundMode Property” on page 18
- “numericType Object Syntax Change” on page 18
- “Minimums and Maximums Now Logged After Quantization” on page 19

[Slope Bias] Math Support Added

Arithmetic using the +, -, .*, and * operators is now supported for objects with [Slope Bias] scaling. Refer to “[Slope Bias] Arithmetic” in the product documentation for more information.

In support of this feature, the following properties have been added to the fimath object:

- `ProductBias` — Bias of the product data type
- `ProductFixedExponent` — Fixed exponent of the product data type
- `ProductSlope` — Slope of the product data type
- `ProductSlopeAdjustmentFactor` — Slope adjustment factor of the product data type
- `SumBias` — Bias of the sum data type
- `SumFixedExponent` — Fixed exponent of the sum data type
- `SumSlope` — Slope of the sum data type
- `SumSlopeAdjustmentFactor` — Slope adjustment factor of the sum data type

Refer to “Property Reference” in the product reference documentation for more information.

Scaled Double Data Type Support Added to the `fi` Object

The `fi` object now supports the scaled double data type. The value `ScaledDouble` has been added to the `DataType` property of the `numericType` object. The following values have also been added to the `DataTypeMode` property of the `numericType` object:

- Scaled double: binary point scaling
- Scaled double: slope and bias scaling
- Scaled double: unspecified scaling

Math operations are supported for `fi` objects with data type `ScaledDouble`.

Global `DataTypeOverride` Property Added to the `fi` Object

The `fi` object now has the property `DataTypeOverride`, which allows you to override `fi` objects with scaled doubles, singles, or doubles. Refer to “Using `fi` Objects to Set Data Type Override Preferences” in the product documentation for more information.

Embedded MATLAB™ Subset Supports More Fixed-Point Toolbox™ Functions

The following Fixed-Point Toolbox™ functions are now supported by Embedded MATLAB™ subset:

- bitand
- bitcmp
- bitget
- bitor
- bitset
- bitshift
- bitxor
- rescale

Refer to “Supported Functions and Limitations of Fixed-Point Embedded MATLAB Subset” in the product documentation for more information.

Embedded MATLAB™ Subset Does Not Support a CastBeforeSum Value of false

You can no longer set the fimath object property CastBeforeSum to false or 0 in Embedded MATLAB Function blocks. The reason for this restriction is that Embedded MATLAB subset does not produce the same numerical results as MATLAB® when CastBeforeSum is false.

Compatibility Considerations

In the previous release, CastBeforeSum was set to false for default fimath objects in Embedded MATLAB subset. If you have existing models that contain Embedded MATLAB Function blocks in which CastBeforeSum is false, you will now get an error when you compile or update your model. To correct this issue, you must set CastBeforeSum to true. To automate this process, you can run the utility slupdate either from the Model Advisor or by typing the following command at the MATLAB command line:

```
slupdate ('modelName')
```

where `'modelName'` is the name of the model containing the Embedded MATLAB Function block that generates the error. `slupdate` prompts you to update this property by selecting one of these options:

Option	Action
Yes	Updates the first occurrence of <code>CastBeforeSum=false</code> in Embedded MATLAB Function blocks in the model and then prompts you for each subsequent instance found in the model.
No	Does not update any occurrences of <code>CastBeforeSum=false</code> in the model.
All	Updates all occurrences of <code>CastBeforeSum=false</code> in the model.

Note `slupdate` detects `CastBeforeSum=false` only in *default* `fimath` objects defined for Simulink® signals in Embedded MATLAB Function blocks. If you modified the `fimath` object in an Embedded MATLAB Function block, update `CastBeforeSum` manually in your model and fix the errors as they are reported.

round Value Added to the fimath Object RoundMode Property

The `RoundMode` property value `round` has been added to the `fimath` object. The behavior of this rounding mode is identical to the MATLAB `round` function. For more information refer to “RoundMode” in the product documentation.

numerictype Object Syntax Change

Previously, if you created a `numerictype` object without specifying a value for the `FractionLength` property, the fraction length would be automatically set to 15. Now however, if you do not set the `FractionLength` property when creating a `numerictype` object, the scaling will remain unspecified. For example:

```
T = numerictype(1, 16)
```

```
T =
```

```

        DataTypeMode: Fixed-point: unspecified scaling
                Signed: true
                WordLength: 16

```

```
T.scaling
```

```
ans =
```

```
Unspecified
```

```
T.FractionLength
```

```
ans =
```

```
0
```

Compatibility Considerations

Any instances of this syntax in your existing code will now return a different result.

Minimums and Maximums Now Logged After Quantization

Previously, the `fi` and `quantizer` objects logged minimums and maximums before quantization. They now log after quantization.

Compatibility Considerations

If your fixed-point data overflows and you want to log minimums and maximums for the full floating-point range, use the `'ScaledDoubles'` or `'TrueDoubles'` values of the `fipref` object `DataTypeOverride` property. For example, the following fixed-point variable overflows. The saturated minimum and maximum values are logged:

```

p = fipref;
p.LoggingMode = 'On';
p.DataTypeOverride = 'ForceOff';

```

```

a = fi(-2:2, true, 16, 15)
Warning: 3 overflows occurred in the fi assignment operation.

a =

    -1    -1     0    0.99997    0.99997

    DataTypeMode: Fixed-point: binary point scaling
        Signed: true
        WordLength: 16
    FractionLength: 15

        RoundMode: nearest
    OverflowMode: saturate
        ProductMode: FullPrecision
    MaxProductWordLength: 128
        SumMode: FullPrecision
    MaxSumWordLength: 128
    CastBeforeSum: true

logreport(a)

    minlog    maxlog    lowerbound    upperbound    noverflows    nunderflows
a         -1    0.9999695         -1    0.9999695         3         0

```

Now set `DataTypeOverride` to `'ScaledDoubles'`. Note that overflows are reported, but the data is not quantized. The minimum and maximum logs show the full possible range of the data without quantization:

```

p = fipref;
p.LoggingMode = 'On';
p.DataTypeOverride = 'ScaledDoubles';

b = fi(-2:2, true, 16, 15)
Warning: 3 overflows occurred in the fi assignment operation.

b =

    -2    -1     0     1     2

```



```
DataTypeMode: Scaled double: binary point scaling
Signed: true
WordLength: 16
FractionLength: 15
```

```
RoundMode: nearest
OverflowMode: saturate
ProductMode: FullPrecision
MaxProductWordLength: 128
SumMode: FullPrecision
MaxSumWordLength: 128
CastBeforeSum: true
```

```
logreport(b)
```

	minlog	maxlog	lowerbound	upperbound	noverflows	nunderflows
b	-2	2	-1	0.9999695	3	0

For an in-depth example of using logging and data type override to help set appropriate scalings for fixed-point quantities, see the Fixed-Point Toolbox demo “Fixed-Point Data Type Override, Min/Max Logging, and Scaling”.

Version 1.3 (R14SP3) Fixed-Point Toolbox™ Software

This table summarizes what's new in Version 1.3 (R14SP3):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	Yes—Details labeled as Compatibility Considerations , below. See also Summary.	Bug Reports Includes fixes	No

New features and changes introduced in this version are

- “Fixed-Point Toolbox™ Function Support Added to Embedded MATLAB™ Subset” on page 22
- “Double, Single, and Boolean Data Type Support Added to the fi Object” on page 23
- “Fixed-Point Doubles Override, Min/Max Logging, and Scaling Demo” on page 23
- “Helper Functions Added for Accessing Logged Information” on page 24
- “RoundMode Property Value 'round' Now Called 'nearest'” on page 24

Fixed-Point Toolbox™ Function Support Added to Embedded MATLAB™ Subset

The Embedded MATLAB Function block lets you compose a MATLAB® language function in a Simulink® model that generates embeddable code using the Embedded MATLAB™ subset. When you simulate the model or generate code for a target environment, a function in an Embedded MATLAB Function block generates efficient C code. This code meets the strict memory and data type requirements of embedded target environments. In this way, Embedded MATLAB Function blocks bring the power of MATLAB for the embedded environment into Simulink.

For more information about the Embedded MATLAB Function block and the Embedded MATLAB subset, refer to the following documentation:

- Embedded MATLAB Function block reference page in the Simulink documentation
- “Using the Embedded MATLAB Function Block” in the Simulink documentation
- “Working with the Embedded MATLAB Subset” in the Embedded MATLAB subset documentation

You can now use a significant number of Fixed-Point Toolbox™ functions with Embedded MATLAB subset. Refer to “Supported Functions and Limitations of Fixed-Point Embedded MATLAB Subset” in the Using Fixed-Point Toolbox documentation.

Note To simulate models using fixed-point data types in Simulink, including when using the Embedded MATLAB Function block, you must have a Simulink® Fixed Point™ license.

Double, Single, and Boolean Data Type Support Added to the fi Object

The `fi` object now supports double, single, and boolean data types. The values double, single, and boolean have been added to the `DataType` and `DataTypeMode` properties of the `numericType` object. Math operations are supported for `fi` objects with data type single or double, but not boolean.

Fixed-Point Doubles Override, Min/Max Logging, and Scaling Demo

Since floating-point data types are now supported in Fixed-Point Toolbox software, it is possible to use doubles override and min/max scaling to help you choose the appropriate scalings for fixed-point variables in your algorithms. This is especially helpful when converting a floating-point algorithm to fixed point. A new demo “Fixed-Point Doubles Override, Min/Max Logging, and Scaling” leads you through an example of this process. You can access

this demo from the **Demos** pane of the Help browser under Toolboxes > Fixed-Point.

Helper Functions Added for Accessing Logged Information

In the previous release it became possible to log overflows and underflows as warnings for all assignment, plus, minus, and multiplication operations when the `fipref` `LoggingMode` property is set to on. Now when `LoggingMode` is on, you can also use the following helper functions to return logged information to you at the MATLAB command line:

- `maxlog` — Returns the maximum real-world value
- `minlog` — Returns the minimum real-world value
- `noperations` — Returns the number of quantized operations
- `noverflows` — Returns the number of overflows
- `nunderflows` — Returns the number of underflows

To clear the log, use the function `resetlog`.

RoundMode Property Value 'round' Now Called 'nearest'

The `RoundMode` property value `round` is now `nearest`. This is a reflection of the fact that this rounding mode is identical to the Simulink rounding mode `round toward nearest`, and different from the behavior of the MATLAB `round` function.

Compatibility Considerations

For this release, any code using the `RoundMode` property value `round` will still work as it did in previous releases. However, you should update each instance of the property value `round` to `nearest` because in a later release, the property value `round` will give a different answer.

Version 1.2 (R14SP2) Fixed-Point Toolbox™ Software

This table summarizes what's new in Version 1.2 (R14SP2):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	No	Bug Reports	No

New features and changes introduced in this version are

- “Overflow and Underflow Logging” on page 25
- “New Functions” on page 25

Overflow and Underflow Logging

Fixed-Point Toolbox™ software now allows you to log overflows and underflows as warnings for all assignment, plus, minus, and multiplication operations. Refer to “Using fipref Objects to Set Logging Preferences” in the Fixed-Point Toolbox documentation for more information.

New Functions

The following functions are new in version 1.2 of Fixed-Point Toolbox software:

abs	all	and	any	area
bar	barh	buffer	clabel	comet
comet3	compass	coneplot	contour	contour3
contourc	contourf	diag	end	errorbar
etreeplot	ezcontour	ezcontourf	ezmesh	ezplot
ezplot3	ezpolar	ezsurf	ezsurfc	feather
fplot	gplot	hankel	hist	histc
intmin	ipermute	isnumeric	isobject	line
logical	lowerbound	mesh	meshc	meshz

not	numberofelements	or	patch	pcolor
permute	plot3	plotmatrix	plotyy	polar
pow2	quiver	quiver3	rgbplot	ribbon
rose	scatter	scatter3	sdec	sign
slice	spy	stairs	stem	stem3
streamribbon	streamslice	streamtube	sum	surf
surfc	surfl	surfnorm	text	toeplitz
treeplot	tril	trimesh	triplot	trisurf
triu	uplus	upperbound	voronoi	voronoin
waterfall	xlim	ylim	zlim	

Version 1.1 (R14SP1) Fixed-Point Toolbox™ Software

This table summarizes what's new in Version 1.1 (R14SP1):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
No	No	Yes Details below	No

The particularly important bug fixes in this version are

Bitwise Operators Return Correct Answers for [Slope Bias] Signals

In the previous release, bitwise functions such as `bitshift` might have given wrong answers for [Slope Bias] fixed-point signals. This has been corrected in this release.

fi Object Operations with an Empty Array Work Properly

In the previous release, a segmentation violation occurred for any operation with the format

`a op e`

where `a` is a `fi` object, `e` is an empty array, and `op` is any operator such as `+`, `-`, `*`, `.*`, `<`, `>`, etc. This has been corrected in this release.

ispropequal Returns Correct Answers for fimath Objects

The `ispropequal` function has been updated to work properly in this release.

Version 1.0 (R14) Fixed-Point Toolbox™ Software

This table summarizes what's new in Version 1.0 (R14):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	No	No bug fixes	No

Fixed-Point Toolbox™ software provides fixed-point data types in MATLAB® and enables algorithm development by providing fixed-point arithmetic. The toolbox enables you to create the following types of objects:

- `fi` — Defines a fixed-point numeric object in the MATLAB workspace. Each `fi` object is composed of value data, a `fiarith` object, and a `numericity` object
- `fiarith` — Governs how overloaded arithmetic operators work with `fi` objects
- `fiarith` — Defines the display attributes for `fi` objects
- `numericity` — Defines the data type and scaling attributes of `fi` objects
- `quantizer` — Quantizes data sets

Features

Fixed-Point Toolbox software provides you with

- The ability to define fixed-point data types, scaling, and rounding and overflow methods in the MATLAB workspace
- Bit-true real and complex simulation
- Basic fixed-point arithmetic with binary point-only signals
 - Arithmetic operators `+`, `-`, `*`, `.*`
 - Division using the `divide` function
- Arbitrary word length up to `intmax('uint16')`

- Relational, logical, and bitwise operators
- Data visualization via the `plot` function
- Statistics functions such as `abs`, `max`, and `min`
- Conversions between binary, hex, double, and built-in integers
- Interoperability with Simulink®, Signal Processing Blockset™ software, and Filter Design Toolbox™ software
- Compatibility with the Simulink To Workspace and From Workspace blocks

Getting Help

This section tells you how to get help for Fixed-Point Toolbox software in this document and at the MATLAB command line.

Getting Help in the Fixed-Point Toolbox™ User's Guide

Fixed-Point Toolbox objects are discussed in the following chapters:

- “Working with `fi` Objects”
- “Working with `fimath` Objects”
- “Working with `fipref` Objects”
- “Working with `numerictype` Objects”
- “Working with `quantizer` Objects”

To get in-depth information about the properties of these objects, refer to “Property Reference”.

To get in-depth information about the functions of these objects, refer to Function Reference.

Getting Help at the MATLAB® Command Line

To get command-line help for Fixed-Point Toolbox objects, type

```
help objectname
```

For example:

```
help fi
help fimath
help fipref
help numericity
help quantizer
```

To invoke Help Browser documentation for Fixed-Point Toolbox functions from the MATLAB command line, type

```
doc fixedpoint/functionname
```

For example:

```
doc fixedpoint/int
doc fixedpoint/add
doc fixedpoint/savefipref
doc fixedpoint/quantize
```

Compatibility Summary for Fixed-Point Toolbox™ Software

This table summarizes new features and changes that might cause incompatibilities when you upgrade from an earlier version, or when you use files on multiple versions. Details are provided in the description of the new feature or change.

Version (Release)	New Features and Changes with Version Compatibility Impact
Latest Version V2.2 (R2008a)	None
V2.1 (R2007b)	See the Compatibility Considerations subheading for each of these new features or changes: <ul style="list-style-type: none"> • “bitget Function Updated” on page 8 • “divide Function Updated” on page 9 • “fi Constructor Applies Property/Value Pairs After Numeric Value” on page 9
V2.0 (R2007a)	See the Compatibility Considerations subheading for each of these new features or changes: <ul style="list-style-type: none"> • “get Function Must be Declared Extrinsic in Embedded MATLAB™ Subset” on page 12 • “Embedded MATLAB™ Subset Does Not Support & and Operators” on page 12

Version (Release)	New Features and Changes with Version Compatibility Impact
V1.5 (R2006b)	None
V1.4 (R2006a)	<p>See the Compatibility Considerations subheading for each of these new features or changes:</p> <ul style="list-style-type: none"> • “Embedded MATLAB™ Subset Does Not Support a CastBeforeSum Value of 'false'” on page 17 • “numericType Object Syntax Change” on page 18 • “Minimums and Maximums Now Logged After Quantization” on page 19
V1.3 (R14SP3)	<p>See the Compatibility Considerations subheading for this new feature or change:</p> <ul style="list-style-type: none"> • “RoundMode Property Value 'round' Now Called 'nearest’” on page 24
V1.2 (R14SP2)	None
V1.1 (R14SP1)	None
V1.0 (R14)	Not applicable