


MATLAB® 7

C and Fortran API Reference



MATLAB®

How to Contact The MathWorks



www.mathworks.com Web
comp.soft-sys.matlab Newsgroup
www.mathworks.com/contact_TS.html Technical Support



suggest@mathworks.com Product enhancement suggestions
bugs@mathworks.com Bug reports
doc@mathworks.com Documentation error reports
service@mathworks.com Order status, license renewals, passcodes
info@mathworks.com Sales, pricing, and general information



508-647-7000 (Phone)



508-647-7001 (Fax)



The MathWorks, Inc.
3 Apple Hill Drive
Natick, MA 01760-2098

For contact information about worldwide offices, see the MathWorks Web site.

MATLAB® C and Fortran API Reference

© COPYRIGHT 1984–2008 by The MathWorks, Inc.

The software described in this document is furnished under a license agreement. The software may be used or copied only under the terms of the license agreement. No part of this manual may be photocopied or reproduced in any form without prior written consent from The MathWorks, Inc.

FEDERAL ACQUISITION: This provision applies to all acquisitions of the Program and Documentation by, for, or through the federal government of the United States. By accepting delivery of the Program or Documentation, the government hereby agrees that this software or documentation qualifies as commercial computer software or commercial computer software documentation as such terms are used or defined in FAR 12.212, DFARS Part 227.72, and DFARS 252.227-7014. Accordingly, the terms and conditions of this Agreement and only those rights specified in this Agreement, shall pertain to and govern the use, modification, reproduction, release, performance, display, and disclosure of the Program and Documentation by the federal government (or other entity acquiring for or through the federal government) and shall supersede any conflicting contractual terms or conditions. If this License fails to meet the government's needs or is inconsistent in any respect with federal procurement law, the government agrees to return the Program and Documentation, unused, to The MathWorks, Inc.

Trademarks

MATLAB and Simulink are registered trademarks of The MathWorks, Inc. See www.mathworks.com/trademarks for a list of additional trademarks. Other product or brand names may be trademarks or registered trademarks of their respective holders.

Patents

The MathWorks products are protected by one or more U.S. patents. Please see www.mathworks.com/patents for more information.

Revision History

December 1996	First Printing	New for MATLAB 5 (Release 8)
May 1997	Online only	Revised for MATLAB 5.1 (Release 9)
January 1998	Online Only	Revised for MATLAB 5.2 (Release 10)
January 1999	Online Only	Revised for MATLAB 5.3 (Release 11)
September 2000	Online Only	Revised for MATLAB 6.0 (Release 12)
June 2001	Online only	Revised for MATLAB 6.1 (Release 12.1)
July 2002	Online only	Revised for MATLAB 6.5 (Release 13)
January 2003	Online only	Revised for MATLAB 6.5.1 (Release 13SP1)
June 2004	Online only	Revised for MATLAB 7.0 (Release 14)
October 2004	Online only	Revised for MATLAB 7.0.1 (Release 14SP1)
March 2005	Online only	Revised for MATLAB 7.0.4 (Release 14SP2)
September 2005	Online only	Revised for MATLAB 7.1 (Release 14SP3)
March 2006	Online only	Revised for MATLAB 7.2 (Release 2006a)
September 2006	Online only	Revised for MATLAB 7.3 (Release 2006b)
March 2007	Online only	Revised and renamed for MATLAB 7.4 (Release 2007a)
September 2007	Online only	Revised and renamed for MATLAB 7.5 (Release 2007b)
March 2008	Online only	Revised and renamed for MATLAB 7.6 (Release 2008a)
October 2008	Online only	Revised and renamed for MATLAB 7.7 (Release 2008b)

API Reference

1

MAT-File Access	1-2
MX Array Manipulation	1-2
MEX-Files	1-10
MATLAB Engine	1-11

API Reference

2

Index

API Reference

MAT-File Access (p. 1-2)

Incorporate and use MATLAB® data in C and Fortran programs

MX Array Manipulation (p. 1-2)

Create and manipulate MATLAB arrays from C and Fortran MEX and engine routines

MEX-Files (p. 1-10)

Perform operations in MATLAB environment from C and Fortran MEX-files

MATLAB Engine (p. 1-11)

Call MATLAB software from C and Fortran programs

See also “External Interfaces” in the MATLAB Function Reference for interfaces to DLLs, Sun™ Java™ programming language, Microsoft® Component Object Model (COM) and Microsoft® ActiveX® technologies, Web services, and serial port devices.

MAT-File Access

<code>matClose</code> (C and Fortran)	Close MAT-file
<code>matDeleteVariable</code> (C and Fortran)	Delete named mxArray from MAT-file
<code>MATFile</code> (C and Fortran)	Type for a MAT-file
<code>matGetDir</code> (C and Fortran)	Get directory of mxArrays in MAT-file
<code>matGetFp</code> (C)	Get file pointer to MAT-file
<code>matGetNextVariable</code> (C and Fortran)	Read next mxArray from MAT-file
<code>matGetNextVariableInfo</code> (C and Fortran)	Load array header information only
<code>matGetVariable</code> (C and Fortran)	Read mxArray from MAT-files
<code>matGetVariableInfo</code> (C and Fortran)	Load array header information only
<code>matOpen</code> (C and Fortran)	Open MAT-file
<code>matPutVariable</code> (C and Fortran)	Write mxArrays to MAT-files
<code>matPutVariableAsGlobal</code> (C and Fortran)	Put mxArrays into MAT-files as originating from global workspace

MX Array Manipulation

<code>mwIndex</code> (C and Fortran)	Type for index values
<code>mwPointer</code> (Fortran)	Declare appropriate pointer type for platform
<code>mwSize</code> (C and Fortran)	Type for size values
<code>mxAddField</code> (C and Fortran)	Add field to structure array
<code>mxArray</code> (C and Fortran)	Type for a MATLAB array

<code>mxArrayToString (C)</code>	Convert array to string
<code>mxAssert (C)</code>	Check assertion value for debugging purposes
<code>mxAssertS (C)</code>	Check assertion value without printing assertion text
<code>mxCalcSingleSubscript (C and Fortran)</code>	Offset from first element to desired element
<code>mxCalloc (C and Fortran)</code>	Allocate dynamic memory for array using MATLAB memory manager
<code>mxChar (C)</code>	Type for string <code>mxArray</code>
<code>mxClassID (C)</code>	Enumerated value identifying class of <code>mxArray</code>
<code>mxClassIDFromClassName (Fortran)</code>	Identifier corresponding to class
<code>mxComplexity (C)</code>	Flag specifying whether <code>mxArray</code> has imaginary components
<code>mxCopyCharacterToPtr (Fortran)</code>	Copy character values from Fortran array to pointer array
<code>mxCopyComplex16ToPtr (Fortran)</code>	Copy <code>COMPLEX*16</code> values from Fortran array to pointer array
<code>mxCopyComplex8ToPtr (Fortran)</code>	Copy <code>COMPLEX*8</code> values from Fortran array to pointer array
<code>mxCopyInteger1ToPtr (Fortran)</code>	Copy <code>INTEGER*1</code> values from Fortran array to pointer array
<code>mxCopyInteger2ToPtr (Fortran)</code>	Copy <code>INTEGER*2</code> values from Fortran array to pointer array
<code>mxCopyInteger4ToPtr (Fortran)</code>	Copy <code>INTEGER*4</code> values from Fortran array to pointer array
<code>mxCopyPtrToCharacter (Fortran)</code>	Copy character values from pointer array to Fortran array
<code>mxCopyPtrToComplex16 (Fortran)</code>	Copy <code>COMPLEX*16</code> values from pointer array to Fortran array

<code>mxCopyPtrToComplex8</code> (Fortran)	Copy <code>COMPLEX*8</code> values from pointer array to Fortran array
<code>mxCopyPtrToInteger1</code> (Fortran)	Copy <code>INTEGER*1</code> values from pointer array to Fortran array
<code>mxCopyPtrToInteger2</code> (Fortran)	Copy <code>INTEGER*2</code> values from pointer array to Fortran array
<code>mxCopyPtrToInteger4</code> (Fortran)	Copy <code>INTEGER*4</code> values from pointer array to Fortran array
<code>mxCopyPtrToPtrArray</code> (Fortran)	Copy pointer values from pointer array to Fortran array
<code>mxCopyPtrToReal4</code> (Fortran)	Copy <code>REAL*4</code> values from pointer array to Fortran array
<code>mxCopyPtrToReal8</code> (Fortran)	Copy <code>REAL*8</code> values from pointer array to Fortran array
<code>mxCopyReal4ToPtr</code> (Fortran)	Copy <code>REAL*4</code> values from Fortran array to pointer array
<code>mxCopyReal8ToPtr</code> (Fortran)	Copy <code>REAL*8</code> values from Fortran array to pointer array
<code>mxCreateCellArray</code> (C and Fortran)	Create unpopulated N-D cell <code>mxArray</code>
<code>mxCreateCellMatrix</code> (C and Fortran)	Create unpopulated 2-D cell <code>mxArray</code>
<code>mxCreateCharArray</code> (C and Fortran)	Create unpopulated N-D string <code>mxArray</code>
<code>mxCreateCharMatrixFromStrings</code> (C and Fortran)	Create populated 2-D string <code>mxArray</code>
<code>mxCreateDoubleMatrix</code> (C and Fortran)	Create 2-D, double-precision, floating-point <code>mxArray</code> initialized to 0
<code>mxCreateDoubleScalar</code> (C and Fortran)	Create scalar, double-precision array initialized to specified value
<code>mxCreateLogicalArray</code> (C)	Create N-D logical <code>mxArray</code> initialized to false

<code>mxCreateLogicalMatrix (C)</code>	Create 2-D, logical mxArray initialized to false
<code>mxCreateLogicalScalar (C)</code>	Create scalar, logical mxArray
<code>mxCreateNumericArray (C and Fortran)</code>	Create unpopulated N-D numeric mxArray
<code>mxCreateNumericMatrix (C and Fortran)</code>	Create numeric matrix and initialize data elements to 0
<code>mxCreateSparse (C and Fortran)</code>	Create 2-D unpopulated sparse mxArray
<code>mxCreateSparseLogicalMatrix (C)</code>	Create unpopulated 2-D, sparse, logical mxArray
<code>mxCreateString (C and Fortran)</code>	Create 1-by-N string mxArray initialized to specified string
<code>mxCreateStructArray (C and Fortran)</code>	Create unpopulated N-D structure mxArray
<code>mxCreateStructMatrix (C and Fortran)</code>	Create unpopulated 2-D structure mxArray
<code>mxDestroyArray (C and Fortran)</code>	Free dynamic memory allocated by <code>mxCreate*</code> functions
<code>mxDuplicateArray (C and Fortran)</code>	Make deep copy of array
<code>mxFree (C and Fortran)</code>	Free dynamic memory allocated by <code>mxCalloc</code> , <code>mxMalloc</code> , or <code>mxRealloc</code>
<code>mxGetCell (C and Fortran)</code>	Get contents of mxArray cell
<code>mxGetChars (C)</code>	Get pointer to character array data
<code>mxGetClassID (C and Fortran)</code>	Get class of mxArray
<code>mxGetClassName (C and Fortran)</code>	Get class of mxArray as string
<code>mxGetData (C and Fortran)</code>	Get pointer to data
<code>mxGetDimensions (C and Fortran)</code>	Get pointer to dimensions array

<code>mxGetElementSize</code> (C and Fortran)	Get number of bytes required to store each data element
<code>mxGetEps</code> (C and Fortran)	Get value of eps
<code>mxGetField</code> (C and Fortran)	Get field value, given field name and index into structure array
<code>mxGetFieldByNumber</code> (C and Fortran)	Get field value, given field number and index into structure array
<code>mxGetFieldNameByNumber</code> (C and Fortran)	Get field name, given field number in structure array
<code>mxGetFieldNumber</code> (C and Fortran)	Get field number, given field name in structure array
<code>mxGetImagData</code> (C and Fortran)	Get pointer to imaginary data of <code>mxArray</code>
<code>mxGetInf</code> (C and Fortran)	Get value of infinity
<code>mxGetIr</code> (C and Fortran)	Get <code>ir</code> array of sparse matrix
<code>mxGetJc</code> (C and Fortran)	Get <code>jc</code> array of sparse matrix
<code>mxGetLogicals</code> (C)	Get pointer to logical array data
<code>mxGetM</code> (C and Fortran)	Get number of rows in <code>mxArray</code>
<code>mxGetN</code> (C and Fortran)	Get number of columns in <code>mxArray</code>
<code>mxGetNaN</code> (C and Fortran)	Get value of NaN (Not-a-Number)
<code>mxGetNumberOfDimensions</code> (C and Fortran)	Get number of dimensions in <code>mxArray</code>
<code>mxGetNumberOfElements</code> (C and Fortran)	Get number of elements in <code>mxArray</code>
<code>mxGetNumberOfFields</code> (C and Fortran)	Get number of fields in structure <code>mxArray</code>
<code>mxGetNzmax</code> (C and Fortran)	Get number of elements in <code>ir</code> , <code>pr</code> , and <code>pi</code> arrays
<code>mxGetPi</code> (C and Fortran)	Get imaginary data elements in <code>mxArray</code>
<code>mxGetPr</code> (C and Fortran)	Get real data elements in <code>mxArray</code>

<code>mxGetProperty</code> (C and Fortran)	Get property value of MATLAB class object
<code>mxGetScalar</code> (C and Fortran)	Get real component of first data element in <code>mxArray</code>
<code>mxGetString</code> (C and Fortran)	Copy string <code>mxArray</code> to C-style string
<code>mxIsCell</code> (C and Fortran)	Determine whether input is cell <code>mxArray</code>
<code>mxIsChar</code> (C and Fortran)	Determine whether input is string <code>mxArray</code>
<code>mxIsClass</code> (C and Fortran)	Determine whether <code>mxArray</code> is member of specified class
<code>mxIsComplex</code> (C and Fortran)	Determine whether data is complex
<code>mxIsDouble</code> (C and Fortran)	Determine whether <code>mxArray</code> represents data as double-precision, floating-point numbers
<code>mxIsEmpty</code> (C and Fortran)	Determine whether <code>mxArray</code> is empty
<code>mxIsFinite</code> (C and Fortran)	Determine whether input is finite
<code>mxIsFromGlobalWS</code> (C and Fortran)	Determine whether <code>mxArray</code> was copied from MATLAB global workspace
<code>mxIsInf</code> (C and Fortran)	Determine whether input is infinite
<code>mxIsInt16</code> (C and Fortran)	Determine whether <code>mxArray</code> represents data as signed 16-bit integers
<code>mxIsInt32</code> (C and Fortran)	Determine whether <code>mxArray</code> represents data as signed 32-bit integers
<code>mxIsInt64</code> (C and Fortran)	Determine whether <code>mxArray</code> represents data as signed 64-bit integers

<code>mxIsInt8</code> (C and Fortran)	Determine whether <code>mxArray</code> represents data as signed 8-bit integers
<code>mxIsLogical</code> (C and Fortran)	Determine whether <code>mxArray</code> is of type <code>mxLogical</code>
<code>mxIsLogicalScalar</code> (C)	Determine whether scalar <code>mxArray</code> is of type <code>mxLogical</code>
<code>mxIsLogicalScalarTrue</code> (C)	Determine whether scalar <code>mxArray</code> of type <code>mxLogical</code> is true
<code>mxIsNaN</code> (C and Fortran)	Determine whether input is NaN (Not-a-Number)
<code>mxIsNumeric</code> (C and Fortran)	Determine whether <code>mxArray</code> is numeric
<code>mxIsSingle</code> (C and Fortran)	Determine whether <code>mxArray</code> represents data as single-precision, floating-point numbers
<code>mxIsSparse</code> (C and Fortran)	Determine whether input is sparse <code>mxArray</code>
<code>mxIsStruct</code> (C and Fortran)	Determine whether input is structure <code>mxArray</code>
<code>mxIsUint16</code> (C and Fortran)	Determine whether <code>mxArray</code> represents data as unsigned 16-bit integers
<code>mxIsUint32</code> (C and Fortran)	Determine whether <code>mxArray</code> represents data as unsigned 32-bit integers
<code>mxIsUint64</code> (C and Fortran)	Determine whether <code>mxArray</code> represents data as unsigned 64-bit integers
<code>mxIsUint8</code> (C and Fortran)	Determine whether <code>mxArray</code> represents data as unsigned 8-bit integers
<code>mxLogical</code> (C)	Type for logical <code>mxArray</code>

<code>mxMalloc</code> (C and Fortran)	Allocate dynamic memory using MATLAB memory manager
<code>mxRealloc</code> (C and Fortran)	Reallocate memory
<code>mxRemoveField</code> (C and Fortran)	Remove field from structure array
<code>mxSetCell</code> (C and Fortran)	Set value of one cell of <code>mxArray</code>
<code>mxSetClassName</code> (C)	Convert structure array to MATLAB object array
<code>mxSetData</code> (C and Fortran)	Set pointer to data
<code>mxSetDimensions</code> (C and Fortran)	Modify number of dimensions and size of each dimension
<code>mxSetField</code> (C and Fortran)	Set structure array field, given field name and index
<code>mxSetFieldByNumber</code> (C and Fortran)	Set structure array field, given field number and index
<code>mxSetImagData</code> (C and Fortran)	Set imaginary data pointer for <code>mxArray</code>
<code>mxSetIr</code> (C and Fortran)	Set <code>ir</code> array of sparse <code>mxArray</code>
<code>mxSetJc</code> (C and Fortran)	Set <code>jc</code> array of sparse <code>mxArray</code>
<code>mxSetM</code> (C and Fortran)	Set number of rows in <code>mxArray</code>
<code>mxSetN</code> (C and Fortran)	Set number of columns in <code>mxArray</code>
<code>mxSetNzmax</code> (C and Fortran)	Set storage space for nonzero elements
<code>mxSetPi</code> (C and Fortran)	Set new imaginary data for <code>mxArray</code>
<code>mxSetPr</code> (C and Fortran)	Set new real data for <code>mxArray</code>
<code>mxSetProperty</code> (C and Fortran)	Set value of property of MATLAB class object

MEX-Files

<code>mexAtExit</code> (C and Fortran)	Register function to call when MEX-function is cleared or MATLAB software terminates
<code>mexCallMATLAB</code> (C and Fortran)	Call MATLAB function or user-defined M-file or MEX-file
<code>mexCallMATLABWithTrap</code> (C and Fortran)	Call MATLAB function, user-defined M-file, or MEX-file and capture error information
<code>mexErrMsgIdAndTxt</code> (C and Fortran)	Issue error message with identifier and return to MATLAB prompt
<code>mexErrMsgTxt</code> (C and Fortran)	Issue error message and return to MATLAB prompt
<code>mexEvalString</code> (C and Fortran)	Execute MATLAB command in caller's workspace
<code>mexEvalStringWithTrap</code> (C and Fortran)	Execute MATLAB command in caller's workspace and capture error information
<code>mexFunction</code> (C and Fortran)	Entry point to C MEX-file
<code>mexFunctionName</code> (C and Fortran)	Name of current MEX-function
<code>mexGet</code> (C)	Get value of specified Handle Graphics® property
<code>mexGetVariable</code> (C and Fortran)	Get copy of variable from specified workspace
<code>mexGetVariablePtr</code> (C and Fortran)	Get read-only pointer to variable from another workspace
<code>mexIsGlobal</code> (C and Fortran)	Determine whether <code>mxArray</code> has global scope
<code>mexIsLocked</code> (C and Fortran)	Determine whether MEX-file is locked

mexLock (C and Fortran)	Prevent MEX-file from being cleared from memory
mexMakeArrayPersistent (C and Fortran)	Make mxArray persist after MEX-file completes
mexMakeMemoryPersistent (C and Fortran)	Make memory allocated by MATLAB software persist after MEX-function completes
mexPrintf (C and Fortran)	ANSI® C printf-style output routine
mexPutVariable (C and Fortran)	Copy mxArray from MEX-function into specified workspace
mexSet (C)	Set value of specified Handle Graphics property
mexSetTrapFlag (C and Fortran)	Control response of mexCallMATLAB to errors
mexUnlock (C and Fortran)	Allow MEX-file to be cleared from memory
mexWarnMsgIdAndTxt (C and Fortran)	Issue warning message with identifier
mexWarnMsgTxt (C and Fortran)	Issue warning message

MATLAB Engine

engClose (C and Fortran)	Quit MATLAB engine session
engEvalString (C and Fortran)	Evaluate expression in string
engGetVariable (C and Fortran)	Copy variable from MATLAB engine workspace
engGetVisible (C)	Determine visibility of MATLAB engine session
Engine (C)	Type for a MATLAB engine
engOpen (C and Fortran)	Start MATLAB engine session

<code>engOpenSingleUse (C)</code>	Start MATLAB engine session for single, nonshared use
<code>engOutputBuffer (C and Fortran)</code>	Specify buffer for MATLAB output
<code>engPutVariable (C and Fortran)</code>	Put variables into MATLAB engine workspace
<code>engSetVisible (C)</code>	Show or hide MATLAB engine session

API Reference

engClose (C and Fortran)

Purpose	Quit MATLAB engine session
C Syntax	<pre>#include "engine.h" int engClose(Engine *ep);</pre>
Fortran Syntax	<pre>integer*4 engClose(ep) mwPointer ep</pre>
Arguments	ep Engine pointer
Returns	0 on success, and 1 otherwise. Possible failure includes attempting to terminate a MATLAB engine session that was already terminated.
Description	This routine sends a quit command to the MATLAB engine session and closes the connection.
C Examples	<p>UNIX^{®1} Operating Systems</p> <p>See <code>engdemo.c</code> in the <code>eng_mat</code> subdirectory of the <code>examples</code> directory for a sample program that illustrates how to call the MATLAB engine functions from a C program.</p> <p>Microsoft Windows[®] Operating Systems</p> <p>See <code>engwindemo.c</code> in the <code>eng_mat</code> subdirectory of the <code>examples</code> directory for a sample program that illustrates how to call the MATLAB engine functions from a C program for Windows systems.</p>
Fortran Examples	See <code>fengdemo.F</code> in the <code>eng_mat</code> subdirectory of the <code>examples</code> directory for a sample program that illustrates how to call the MATLAB engine functions from a Fortran program.
See Also	<code>engOpen</code>

1. UNIX is a registered trademark of The Open Group in the United States and other countries.

Purpose	Evaluate expression in string
C Syntax	<pre>#include "engine.h" int engEvalString(Engine *ep,const char *string);</pre>
Fortran Syntax	<pre>integer*4 engEvalString(ep, string) mwPointer ep character*(*) string</pre>
Arguments	<p>ep Engine pointer</p> <p>string String to execute</p>
Returns	0 if the command was evaluated by the MATLAB engine session, and a nonzero value if unsuccessful. Possible reasons for failure include the engine session is no longer running or the engine pointer is invalid or NULL.
Error Handling	If string detects an error, MATLAB terminates and returns control to the MATLAB prompt.
Description	engEvalString evaluates the expression contained in string for the MATLAB engine session, ep, previously started by engOpen.

engEvalString (C and Fortran)

UNIX² Operating Systems

On UNIX systems, `engEvalString` sends commands to the MATLAB workspace by writing down a pipe connected to the MATLAB *stdin* process. Any output resulting from the command that ordinarily appears on the screen is read back from *stdout* into the buffer defined by `engOutputBuffer`.

To turn off output buffering in C, use:

```
engOutputBuffer(ep, NULL, 0);
```

To turn off output buffering in Fortran, use:

```
engOutputBuffer(ep, '')
```

Microsoft Windows Operating Systems

On a Windows system, `engEvalString` communicates with MATLAB software using a Component Object Model (COM) interface.

C Examples

UNIX Operating Systems

See `engdemo.c` in the `eng_mat` subdirectory of the `examples` directory for a sample program that illustrates how to call the MATLAB engine functions from a C program.

Windows Operating Systems

See `engwindemo.c` in the `eng_mat` subdirectory of the `examples` directory for a sample program that illustrates how to call the MATLAB engine functions from a C program for Windows systems.

Fortran Examples

See `fengdemo.F` in the `eng_mat` subdirectory of the `examples` directory for a sample program that illustrates how to call the MATLAB engine functions from a Fortran program.

See Also

`engOpen`, `engOutputBuffer`

2. UNIX is a registered trademark of The Open Group in the United States and other countries.

engGetVariable (C and Fortran)

Purpose	Copy variable from MATLAB engine workspace
C Syntax	<pre>#include "engine.h" mxAarray *engGetVariable(Engine *ep, const char *name);</pre>
Fortran Syntax	<pre>mwPointer engGetVariable(ep, name) mwPointer ep character*(*) name</pre>
Arguments	<p>ep Engine pointer</p> <p>name Name of mxArray to get from MATLAB workspace</p>
Returns	A pointer to a newly allocated mxArray structure, or NULL if the attempt fails. <code>engGetVariable</code> fails if the named variable does not exist.
Description	<p><code>engGetVariable</code> reads the named mxArray from the MATLAB engine session associated with <code>ep</code>.</p> <p>Use <code>mxDestroyArray</code> to destroy the mxArray created by this routine when you are finished with it.</p>

engGetVariable (C and Fortran)

C Examples

UNIX³ Operating Systems

See `engdemo.c` in the `eng_mat` subdirectory of the `examples` directory for a sample program that illustrates how to call the MATLAB engine functions from a C program.

Microsoft Windows Operating Systems

See `engwindemo.c` in the `eng_mat` subdirectory of the `examples` directory for a sample program that illustrates how to call the MATLAB engine functions from a C program for Windows systems.

See Also

`engPutVariable`, `mxDestroyArray`

3. UNIX is a registered trademark of The Open Group in the United States and other countries.

Purpose Determine visibility of MATLAB engine session

C Syntax

```
#include "engine.h"
int engGetVisible(Engine *ep, bool *value);
```

Arguments

ep
Engine pointer

value
Pointer to value returned from engGetVisible

Returns **Microsoft Windows Operating Systems Only**
0 on success, and 1 otherwise.

Description engGetVisible returns the current visibility setting for MATLAB engine session, ep. A *visible* engine session runs in a window on the Windows desktop, thus making the engine available for user interaction. An invisible session is hidden from the user by removing it from the desktop.

Examples The following code opens engine session ep and disables its visibility.

```
Engine *ep;
bool vis;

ep = engOpen(NULL);
engSetVisible(ep, 0);
```

To determine the current visibility setting, use:

```
engGetVisible(ep, &vis);
```

See Also engSetVisible

Engine (C)

Purpose Type for a MATLAB engine

Description A handle to a MATLAB engine object.
Engine is a C language opaque type.

You can call MATLAB software as a computational engine by writing C and Fortran programs that use the MATLAB engine library, described in “MATLAB Engine” on page 1-11. Engine is the link between your program and the separate MATLAB engine process.

The header file containing this type is:

```
#include "engine.h"
```

Examples

The example `engwindemo.c` (in your `matlabroot/extern/examples/eng_mat` directory) shows how to plot position versus time for a falling object in a MATLAB figure window.

The `engOpen` function starts the MATLAB process, returning an Engine variable. You use this handle for all calls to the MATLAB workspace.

The `mxCreateDoubleMatrix` function creates an `mxAarray` named `T`. The C function `memcpy` copies your time data (initialized in `engwindemo.c`) into `T`.

The `engPutVariable` function puts `T` into the MATLAB workspace. Now you can use this variable to calculate distance `D`. The `engEvalString` function evaluates the expression `D = .5.*(-9.8).*T.^2`.

Next, various MATLAB plot functions, like `plot(T,D)`, display the graph.

Calls to the `engClose` and `mxDestroyArray` functions complete the procedure.

Other sample programs, also found in your `matlabroot\extern\examples\eng_mat` directory, that show you how to use Engine are:

- `engdemo.c` shows how to call the MATLAB engine functions from a C program.
- `engwindemo.c` show how to call the MATLAB engine functions from a C program for Windows systems.
- `fengdemo.F` shows how to call the MATLAB engine functions from a Fortran program.

See Also

`engOpen`

engOpen (C and Fortran)

Purpose	Start MATLAB engine session
C Syntax	<pre>#include "engine.h" Engine *engOpen(const char *startcmd);</pre>
Fortran Syntax	<pre>mwPointer engOpen(startcmd) character*(*) startcmd</pre>
Arguments	<p><code>startcmd</code> String to start the MATLAB process. On Windows systems, the <code>startcmd</code> string must be NULL.</p>
Returns	A pointer to an engine handle or NULL if the open fails.
Description	<p>This routine allows you to start a MATLAB process for the purpose of using MATLAB software as a computational engine.</p> <p><code>engOpen</code> starts a MATLAB process using the command specified in the string <code>startcmd</code>, establishes a connection, and returns a unique engine identifier, or NULL if the open fails.</p> <p>On UNIX⁴ systems, if <code>startcmd</code> is NULL or the empty string, <code>engOpen</code> starts a MATLAB process on the current host using the command <code>matlab</code>. If <code>startcmd</code> is a hostname, <code>engOpen</code> starts a MATLAB process on the designated host by embedding the specified hostname string into the larger string:</p> <pre>"rsh hostname \"/bin/csh -c 'setenv DISPLAY\ hostname:0; matlab'\\""</pre> <p>If <code>startcmd</code> is any other string (has white space in it, or nonalphanumeric characters), the string is executed literally to start a MATLAB process.</p> <p>On UNIX systems, <code>engOpen</code> performs the following steps:</p> <ol style="list-style-type: none">4. UNIX is a registered trademark of The Open Group in the United States and other countries.

- 1 Creates two pipes.
- 2 Forks a new process and sets up the pipes to pass *stdin* and *stdout* from MATLAB (parent) software to two file descriptors in the engine program (child).
- 3 Executes a command to run MATLAB software (*rsh* for remote execution).

On Windows systems, `engOpen` opens a COM channel to MATLAB. This starts the MATLAB software that was registered during installation. If you did not register during installation, on the command line you can enter the command:

```
matlab /regserver
```

See “Introducing MATLAB COM Integration” for additional details.

C Examples

UNIX Operating Systems

See `engdemo.c` in the `eng_mat` subdirectory of the `examples` directory for a sample program that illustrates how to call the MATLAB engine functions from a C program.

Microsoft Windows Operating Systems

See `engwindemo.c` in the `eng_mat` subdirectory of the `examples` directory for a sample program that illustrates how to call the MATLAB engine functions from a C program for Windows systems.

Fortran Examples

See `fengdemo.F` in the `eng_mat` subdirectory of the `examples` directory for a sample program that illustrates how to call the MATLAB engine functions from a Fortran program.

engOpenSingleUse (C)

Purpose Start MATLAB engine session for single, nonshared use

C Syntax

```
#include "engine.h"
Engine *engOpenSingleUse(const char *startcmd, void *dcom,
    int *retstatus);
```

Arguments

startcmd
String to start MATLAB process. On Microsoft Windows systems, the startcmd string must be NULL.

dcom
Reserved for future use; must be NULL.

retstatus
Return status; possible cause of failure.

Returns **Microsoft Windows Operating Systems Only**
A pointer to an engine handle or NULL if the open fails.

UNIX⁵ Operating Systems

This routine is not supported on UNIX systems and simply returns.

Description This routine allows you to start multiple MATLAB processes for the purpose of using MATLAB software as a computational engine. engOpenSingleUse starts a MATLAB process, establishes a connection, and returns a unique engine identifier, or NULL if the open fails. engOpenSingleUse starts a new MATLAB process each time it is called. engOpenSingleUse opens a COM channel to MATLAB. This starts the MATLAB software that was registered during installation. If you did not register during installation, on the command line you can enter the command:

```
matlab /regserver
```

5. UNIX is a registered trademark of The Open Group in the United States and other countries.

`engOpenSingleUse` allows single-use instances of a engine server. `engOpenSingleUse` differs from `engOpen`, which allows multiple users to use the same engine server.

See “Introducing MATLAB COM Integration” for additional details.

engOutputBuffer (C and Fortran)

Purpose Specify buffer for MATLAB output

C Syntax

```
#include "engine.h"
int engOutputBuffer(Engine *ep, char *p, int n);
```

Fortran Syntax

```
integer*4 engOutputBuffer(ep, p)
mwPointer ep
character*n p
```

Arguments

ep Engine pointer

p Pointer to character buffer

n Length of buffer p

Returns 1 if you pass it a NULL engine pointer. Otherwise, it returns 0.

Description engOutputBuffer defines a character buffer for engEvalString to return any output that ordinarily appears on the screen.

The default behavior of engEvalString is to discard any standard output caused by the command it is executing. A call to engOutputBuffer with a buffer of nonzero length tells any subsequent calls to engEvalString to save output in the character buffer pointed to by p.

To turn off output buffering in C, use:

```
engOutputBuffer(ep, NULL, 0);
```

To turn off output buffering in Fortran, use:

```
engOutputBuffer(ep, '')
```


engOutputBuffer (C and Fortran)

Note The buffer returned by `engEvalString` is not guaranteed to be NULL terminated.

engOutputBuffer (C and Fortran)

C Examples

UNIX⁶ Operating Systems

See `engdemo.c` in the `eng_mat` subdirectory of the `examples` directory for a sample program that illustrates how to call the MATLAB engine functions from a C program.

Microsoft Windows Operating Systems

See `engwindemo.c` in the `eng_mat` subdirectory of the `examples` directory for a sample program that illustrates how to call the MATLAB engine functions from a C program for Windows systems.

Fortran Examples

See `fengdemo.F` in the `eng_mat` subdirectory of the `examples` directory for a sample program that illustrates how to call the MATLAB engine functions from a Fortran program.

See Also

`engOpen`, `engEvalString`

6. UNIX is a registered trademark of The Open Group in the United States and other countries.

engPutVariable (C and Fortran)

Purpose

Put variables into MATLAB engine workspace

C Syntax

```
#include "engine.h"
int engPutVariable(Engine *ep, const char *name, const mxArray
    *pm);
```

Fortran Syntax

```
integer*4 engPutVariable(ep, name, pm)
mwPointer ep, pm
character*(*) name
```

Arguments

ep
Engine pointer

name
Name given to the mxArray in the engine's workspace

pm
mxArray pointer

Returns

0 if successful and 1 if an error occurs.

Description

engPutVariable writes mxArray pm to the engine ep, giving it the variable name name. If the mxArray does not exist in the workspace, it is created. If an mxArray with the same name already exists in the workspace, the existing mxArray is replaced with the new mxArray.

engPutVariable (C and Fortran)

C Examples

UNIX⁷ Operating Systems

See `engdemo.c` in the `eng_mat` subdirectory of the `examples` directory for a sample program that illustrates how to call the MATLAB engine functions from a C program.

Microsoft Windows Operating Systems

See `engwindemo.c` in the `eng_mat` subdirectory of the `examples` directory for a sample program that illustrates how to call the MATLAB engine functions from a C program for Windows systems.

See Also

`engGetVariable`

7. UNIX is a registered trademark of The Open Group in the United States and other countries.

Purpose	Show or hide MATLAB engine session
C Syntax	<pre>#include "engine.h" int engSetVisible(Engine *ep, bool value);</pre>
Arguments	<p>ep Engine pointer</p> <p>value Value to set the <code>Visible</code> property to. Set value to 1 to make the engine window visible, or to 0 to make it invisible.</p>
Returns	Microsoft Windows Operating Systems Only 0 on success, and 1 otherwise.
Description	<code>engSetVisible</code> makes the window for the MATLAB engine session, <code>ep</code> , either visible or invisible on the Windows desktop. You can use this function to enable or disable user interaction with the MATLAB engine session.
Examples	<p>The following code opens engine session <code>ep</code> and disables its visibility.</p> <pre>Engine *ep; bool vis; ep = engOpen(NULL); engSetVisible(ep, 0);</pre> <p>To determine the current visibility setting, use:</p> <pre>engGetVisible(ep, &vis);</pre>
See Also	<code>engGetVisible</code>

matClose (C and Fortran)

Purpose	Close MAT-file
C Syntax	<pre>#include "mat.h" int matClose(MATFile *mfp);</pre>
Fortran Syntax	<pre>integer*4 matClose(mfp) mwPointer mfp</pre>
Arguments	<p>mfp Pointer to MAT-file information</p>
Returns	EOF in C (-1 in Fortran) for a write error, and 0 if successful.
Description	matClose closes the MAT-file associated with mfp.
C Examples	See matcreat.c and matdgn.c in the eng_mat subdirectory of the examples directory for sample programs that illustrate how to use the MATLAB MAT-file routines in a C program.
Fortran Examples	See matdemo1.F and matdemo2.F in the eng_mat subdirectory of the examples directory for sample programs that illustrate how to use this MAT-file routine in a Fortran program.

matDeleteVariable (C and Fortran)

Purpose

Delete named mxArray from MAT-file

C Syntax

```
#include "mat.h"  
int matDeleteVariable(MATFile *mfp, const char *name);
```

**Fortran
Syntax**

```
integer*4 matDeleteVariable(mfp, name)  
mwPointer mfp  
character*(*) name
```

Arguments

mfp
 Pointer to MAT-file information

name
 Name of mxArray to delete

Returns

0 if successful, and nonzero otherwise.

Description

matDeleteVariable deletes the named mxArray from the MAT-file pointed to by mfp.

**C
Examples**

See matcreat.c and matdgn.c in the eng_mat subdirectory of the examples directory for sample programs that illustrate how to use the MATLAB MAT-file routines in a C program.

MATFile (C and Fortran)

Purpose

Type for a MAT-file

Description

A handle to a MAT-file object. A MAT-file is the data file format MATLAB software uses for saving data to your disk.

MATFile is a C language opaque type.

The MAT-file interface library contains routines for reading and writing MAT-files. These routines are listed in “MAT-File Access” on page 1-2. You call these routines from your own C and Fortran programs, using MATFile to access your data file.

The header file containing this type is:

```
#include "mat.h"
```

Examples

The example `matcreat.c` in your `matlabroot/extern/examples/eng_mat` directory shows how to create and use a MAT-file.

The `matOpen` function creates the file `mattest.mat`.

The `mxCreateDoubleMatrix` and `mxCreateString` functions create `mxArrays` `pa1`, `pa2`, and `pa3`. `mxCreateString` also initializes `pa3` using the literal string "MATLAB: the language of technical computing". The C function `memcpy` copies data (initialized in `matcreat.c`) into `pa2`.

The `matPutVariable` and `matPutVariableAsGlobal` functions write the data to `mattest.mat`.

Calls to the `matClose` and `mxDestroyArray` functions complete the procedure.

Other examples, also found in your `matlabroot\extern\examples\eng_mat` directory, that show you how to use MATFile are:

- `matdgns.c` shows how to use MAT-file routines in a C program.
- `matdemo1.F` and `matdemo2.F` show how to use MAT-file routines in a Fortran program.

See Also

`matOpen`, `matClose`, `matPutVariable`, `matGetVariable`,
`mxDestroyArray`

matGetDir (C and Fortran)

Purpose	Get directory of mxArray's in MAT-file
C Syntax	<pre>#include "mat.h" char **matGetDir(MATFile *mfp, int *num);</pre>
Fortran Syntax	<pre>mwPointer matGetDir(mfp, num) mwPointer mfp integer*4 num</pre>
Arguments	<p>mfp Pointer to MAT-file information</p> <p>num Address of the variable to contain the number of mxArray's in the MAT-file</p>
Returns	<p>A pointer to an internal array containing pointers to the names of the mxArray's in the MAT-file pointed to by mfp. In C, each name is a NULL-terminated string. The length of the internal array (number of mxArray's in the MAT-file) is placed into num. If num is zero, mfp contains no arrays.</p> <p>matGetDir returns NULL in C (0 in Fortran) and sets num to a negative number if it fails.</p>
Description	<p>This routine allows you to get a list of the names of the mxArray's contained within a MAT-file.</p> <p>The internal array of strings that matGetDir returns is allocated using a single mxCalloc and must be freed using mxFree when you are finished with it.</p> <p>MATLAB variable names can be up to length mxMAXNAM, where mxMAXNAM is defined in the C header file matrix.h.</p>
C Examples	See matcreat.c and matdgn.c in the eng_mat subdirectory of the examples directory for sample programs that illustrate how to use the MATLAB MAT-file routines in a C program.

Fortran Examples

See `matdemo2.F` in the `eng_mat` subdirectory of the `examples` directory for a sample program that illustrates how to use this MAT-file routine in a Fortran program.

matGetFp (C)

Purpose	Get file pointer to MAT-file
C Syntax	<pre>#include "mat.h" FILE *matGetFp(MATFile *mfp);</pre>
Arguments	mfp Pointer to MAT-file information
Returns	A C file handle to the MAT-file with handle mfp. Returns NULL if mfp is a handle to a MAT-file in HDF5-based format.
Description	Use matGetFp to obtain a C file handle to a MAT-file. This can be useful for using standard C library routines like ferror and feof to investigate error situations.
Examples	See matcreat.c and matdgn.c in the eng_mat subdirectory of the examples directory for sample programs that illustrate how to use the MATLAB MAT-file routines in a C program.

matGetNextVariable (C and Fortran)

Purpose	Read next mxArray from MAT-file
C Syntax	<pre>#include "mat.h" mxArray *matGetNextVariable(MATFile *mfp, const char **name);</pre>
Fortran Syntax	<pre>mwPointer matGetNextVariable(mfp, name) mwPointer mfp character*(*) name</pre>
Arguments	<p>mfp Pointer to MAT-file information</p> <p>name Address of the variable to contain the mxArray name</p>
Returns	<p>A pointer to a newly allocated mxArray structure representing the next mxArray from the MAT-file pointed to by mfp. The function returns the name of the mxArray in name.</p> <p>matGetNextVariable returns NULL in C (0 in Fortran) when the end-of-file is reached or if there is an error condition. In C, use feof and ferror from the Standard C Library to determine status.</p>
Description	<p>matGetNextVariable allows you to step sequentially through a MAT-file and read all the mxArrays in a single pass. The function reads and returns the next mxArray from the MAT-file pointed to by mfp.</p> <p>Use matGetNextVariable immediately after opening the MAT-file with matOpen and not in conjunction with other MAT-file routines. Otherwise, the concept of the <i>next</i> mxArray is undefined.</p> <p>Use mxDestroyArray to destroy the mxArray created by this routine when you are finished with it.</p> <p>The order of variables returned from successive calls to matGetNextVariable is not guaranteed to be the same order in which the variables were written.</p>

matGetNextVariable (C and Fortran)

C Examples

See `matdgn.c` in the `eng_mat` subdirectory of the `examples` directory for a sample program that illustrates how to use the MATLAB MAT-file routines in a C program.

See Also

`matGetNextVariableInfo`, `matGetVariable`, `mxDestroyArray`

matGetNextVariableInfo (C and Fortran)

Purpose	Load array header information only
C Syntax	<pre>#include "mat.h" mxArray *matGetNextVariableInfo(MATFile *mfp, const char **name);</pre>
Fortran Syntax	<pre>mwPointer matGetNextVariableInfo(mfp, name) mwPointer mfp character*(*) name</pre>
Arguments	<p>mfp Pointer to MAT-file information</p> <p>name Address of the variable to contain the mxArray name</p>
Returns	<p>A pointer to a newly allocated mxArray structure representing header information for the next mxArray from the MAT-file pointed to by mfp. The function returns the name of the mxArray in name.</p> <p>matGetNextVariableInfo returns NULL in C (0 in Fortran) when the end-of-file is reached or if there is an error condition. In C, use feof and ferror from the Standard C Library to determine status.</p>
Description	<p>matGetNextVariableInfo loads only the array header information, including everything except pr, pi, ir, and jc, from the file's current file offset.</p> <p>If pr, pi, ir, and jc are set to nonzero values when loaded with matGetVariable, matGetNextVariableInfo sets them to -1 instead. These headers are for informational use only and should <i>never</i> be passed back to the MATLAB workspace or saved to MAT-files.</p> <p>Use mxDestroyArray to destroy the mxArray created by this routine when you are finished with it.</p> <p>The order of variables returned from successive calls to matGetNextVariableInfo is not guaranteed to be the same order in which the variables were written.</p>

matGetNextVariableInfo (C and Fortran)

C Examples

See `matdgn.c` in the `eng_mat` subdirectory of the `examples` directory for a sample program that illustrates how to use the MATLAB MAT-file routines in a C program.

See Also

`matGetNextVariable`, `matGetVariableInfo`

Purpose	Read mxArray from MAT-files
C Syntax	<pre>#include "mat.h" mxArray *matGetVariable(MATFile *mfp, const char *name);</pre>
Fortran Syntax	<pre>mwPointer matGetVariable(mfp, name) mwPointer mfp character*(*) name</pre>
Arguments	<p>mfp Pointer to MAT-file information</p> <p>name Name of mxArray to get from MAT-file</p>
Returns	<p>A pointer to a newly allocated mxArray structure representing the mxArray named by name from the MAT-file pointed to by mfp.</p> <p>matGetVariable returns NULL in C (0 in Fortran) if the attempt to return the mxArray named by name fails.</p>
Description	<p>This routine allows you to copy an mxArray out of a MAT-file.</p> <p>Use mxDestroyArray to destroy the mxArray created by this routine when you are finished with it.</p>
C Examples	See matcreat.c and matdgn.c in the eng_mat subdirectory of the examples directory for sample programs that illustrate how to use the MATLAB MAT-file routines in a C program.
See Also	matPutVariable, mxDestroyArray

matGetVariableInfo (C and Fortran)

Purpose	Load array header information only
C Syntax	<pre>#include "mat.h" mxArray *matGetVariableInfo(MATFile *mfp, const char *name);</pre>
Fortran Syntax	<pre>mwPointer matGetVariableInfo(mfp, name); mwPointer mfp character*(*) name</pre>
Arguments	<p>mfp Pointer to MAT-file information</p> <p>name Name of mxArray to get from MAT-file</p>
Returns	<p>A pointer to a newly allocated mxArray structure representing header information for the mxArray named by name from the MAT-file pointed to by mfp.</p> <p>matGetVariableInfo returns NULL in C (0 in Fortran) if the attempt to return header information for the mxArray named by name fails.</p>
Description	<p>matGetVariableInfo loads only the array header information, including everything except pr, pi, ir, and jc. It recursively creates the cells and structures through their leaf elements, but does not include pr, pi, ir, and jc.</p> <p>If pr, pi, ir, and jc are set to nonzero values when loaded with matGetVariable, matGetVariableInfo sets them to -1 instead. These headers are for informational use only and should <i>never</i> be passed back to the MATLAB workspace or saved to MAT-files.</p> <p>Use mxDestroyArray to destroy the mxArray created by this routine when you are finished with it.</p>
C Examples	See matcreat.c and matdgns.c in the eng_mat subdirectory of the examples directory for sample programs that illustrate how to use the MATLAB MAT-file routines in a C program.

matGetVariableInfo (C and Fortran)

See Also `matGetVariable`

matOpen (C and Fortran)

Purpose Open MAT-file

C Syntax

```
#include "mat.h"
MATFile *matOpen(const char *filename, const char *mode);
```

Fortran Syntax

```
mwPointer matOpen(filename, mode)
character*(*) filename, mode
```

Arguments

`filename`
Name of file to open

`mode`
File opening mode. Valid values for `mode` are listed in the following table.

r	Opens file for reading only; determines the current version of the MAT-file by inspecting the files and preserves the current version.
u	Opens file for update, both reading and writing, but does not create the file if the file does not exist (equivalent to the r+ mode of <code>fopen</code>); determines the current version of the MAT-file by inspecting the files and preserves the current version.
w	Opens file for writing only; deletes previous contents, if any.
w4	Creates a Level 4 MAT-file, compatible with MATLAB Versions 4 software and earlier.
wL	Opens file for writing character data using the default character set for your system. The resulting MAT-file can be read with MATLAB Version 6 or 6.5 software. If you do not use the wL mode switch, MATLAB writes character data to the MAT-file using Unicode® character encoding by default.

wz	Opens file for writing compressed data.
w7.3	Creates a MAT-file in an HDF5-based format that can store objects occupy more than 2 GB.

Returns A file handle, or NULL in C (0 in Fortran) if the open fails.

Description This routine opens a MAT-file for reading and writing.
See “Writing Character Data” in the External Interfaces documentation for more information on how MATLAB uses character encodings.

C Examples See `matcreat.c` and `matdgns.c` in the `eng_mat` subdirectory of the `examples` directory for sample programs that illustrate how to use the MATLAB MAT-file routines in a C program.

Fortran Examples See `matdemo1.F` and `matdemo2.F` in the `eng_mat` subdirectory of the `examples` directory for sample programs that illustrate how to use the MATLAB MAT-file routines in a Fortran program.

matPutVariable (C and Fortran)

Purpose Write mxArray to MAT-files

C Syntax

```
#include "mat.h"
int matPutVariable(MATFile *mfp, const char *name, const mxArray
    *pm);
```

Fortran Syntax

```
integer*4 matPutVariable(mfp, name, pm)
mwPointer mfp, pm
character*(*) name
```

Arguments

mfp
Pointer to MAT-file information

name
Name of mxArray to put into MAT-file

pm
mxArray pointer

Returns 0 if successful and nonzero if an error occurs. In C, use feof and ferror from the Standard C Library along with matGetFp to determine status.

Description This routine allows you to put an mxArray into a MAT-file. matPutVariable writes mxArray pm to the MAT-file mfp. If the mxArray does not exist in the MAT-file, it is appended to the end. If an mxArray with the same name already exists in the file, the existing mxArray is replaced with the new mxArray by rewriting the file. The size of the new mxArray can be different from the existing mxArray.

C Examples See matcreat.c and matdgn.c in the eng_mat subdirectory of the examples directory for sample programs that illustrate how to use the MATLAB MAT-file routines in a C program.

See Also matGetVariable

matPutVariableAsGlobal (C and Fortran)

Purpose	Put mxArray into MAT-files as originating from global workspace
C Syntax	<pre>#include "mat.h" int matPutVariableAsGlobal(MATFile *mfp, const char *name, const mxArray *pm);</pre>
Fortran Syntax	<pre>integer*4 matPutVariableAsGlobal(mfp, name, pm) mwPointer mfp, pm character*(*) name</pre>
Arguments	<p>mfp Pointer to MAT-file information</p> <p>name Name of mxArray to put into MAT-file</p> <p>pm mxArray pointer</p>
Returns	0 if successful and nonzero if an error occurs. In C, use feof and ferrord from the Standard C Library with matGetFp to determine status.
Description	<p>This routine puts an mxArray into a MAT-file. matPutVariableAsGlobal is similar to matPutVariable, except that the array, when loaded by MATLAB software, is placed into the global workspace and a reference to it is set in the local workspace. If you write to a MATLAB 4 format file, matPutVariableAsGlobal does not load it as global and has the same effect as matPutVariable.</p> <p>matPutVariableAsGlobal writes mxArray pm to the MAT-file mfp. If the mxArray does not exist in the MAT-file, it is appended to the end. If an mxArray with the same name already exists in the file, the existing mxArray is replaced with the new mxArray by rewriting the file. The size of the new mxArray can be different from the existing mxArray.</p>

matPutVariableAsGlobal (C and Fortran)

C Examples

See `matcreat.c` and `matdgn.c` in the `eng_mat` subdirectory of the `examples` directory for sample programs that illustrate how to use the MATLAB MAT-file routines in a C program.

Purpose	Register function to call when MEX-function is cleared or MATLAB software terminates
C Syntax	<pre>#include "mex.h" int mexAtExit(void (*ExitFcn)(void));</pre>
Fortran Syntax	<pre>integer*4 mexAtExit(ExitFcn) subroutine ExitFcn()</pre>
Arguments	ExitFcn Pointer to function you want to run on exit
Returns	Always returns 0.
Description	<p>Use <code>mexAtExit</code> to register a function to be called just before the MEX-function is cleared or MATLAB software is terminated. <code>mexAtExit</code> gives your MEX-function a chance to perform tasks such as freeing persistent memory and closing files. Typically, the named <code>ExitFcn</code> performs tasks like closing streams or sockets.</p> <p>Each MEX-function can register only one active exit function at a time. If you call <code>mexAtExit</code> more than once, MATLAB uses the <code>ExitFcn</code> from the more recent <code>mexAtExit</code> call as the exit function.</p> <p>If a MEX-function is locked, all attempts to clear the MEX-file will fail. Consequently, if a user attempts to clear a locked MEX-file, MATLAB does not call the <code>ExitFcn</code>.</p> <p>In Fortran, you must declare the <code>ExitFcn</code> as <code>external</code> in the Fortran routine that calls <code>mexAtExit</code> if it is not within the scope of the file.</p>
C Examples	See <code>mexatexit.c</code> in the <code>mex</code> subdirectory of the <code>examples</code> directory.
See Also	<code>mexLock</code> , <code>mexUnlock</code> , <code>mexSetTrapFlag</code>

mexCallMATLAB (C and Fortran)

Purpose Call MATLAB function or user-defined M-file or MEX-file

C Syntax

```
#include "mex.h"
int mexCallMATLAB(int nlhs, mxArray *plhs[], int nrhs,
    mxArray *prhs[], const char *functionName);
```

Fortran Syntax

```
integer*4 mexCallMATLAB(nlhs, plhs, nrhs, prhs, functionName)
integer*4 nlhs, nrhs
mwPointer plhs(*), prhs(*)
character*(*) functionName
```

Arguments

`nlhs` Number of desired output arguments.

`plhs` Array of pointers to output arguments.

`nrhs` Number of input arguments.

`prhs` Array of pointers to input arguments.

`functionName` Character string containing the `functionName` of the MATLAB built-in, operator, M-file, or MEX-file that you are calling.

Returns 0 if successful, and a nonzero value if unsuccessful.

Description Call `mexCallMATLAB` to invoke internal MATLAB numeric functions, MATLAB operators, M-files, or other MEX-files. Both `mexCallMATLAB` and `mexEvalString` execute MATLAB commands. However, `mexCallMATLAB` provides a mechanism for returning results (left-hand side arguments) back to the MEX-file; `mexEvalString` provides no way for return values to be passed back to the MEX-file.

For a complete description of the input and output arguments passed to `functionName`, see `mexFunction`. When calling the `mexCallMATLAB`

function, the number of output arguments `nlhs` and input arguments `nrhs` must be less than or equal to 50.

MATLAB allocates dynamic memory to store the `mxArrays` in `plhs`. MATLAB automatically deallocates the dynamic memory when you clear the MEX-file. However, if heap space is at a premium, you may want to call `mxDestroyArray` when you are finished with the `mxArrays` `plhs` points to.

If `functionName` is an operator, place the operator inside a pair of single quotes, for example, `'+'`.

It is possible to generate an object of type `mxUNKNOWN_CLASS` using `mexCallMATLAB`. For example, if you create an M-file that returns two variables but assigns only one of them a value:

```
function [a,b]=foo(c)
a=2*c;
```

you get this warning message in MATLAB:

```
Warning: One or more output arguments not assigned
during call to 'foo'.
```

MATLAB assigns output `b` to an empty matrix. If you then call `foo` using `mexCallMATLAB`, the unassigned output variable is given type `mxUNKNOWN_CLASS`.

Error Handling

If `functionName` detects an error, MATLAB terminates the MEX-file and returns control to the MATLAB prompt. If you want to trap errors, use the `mexCallMATLABWithTrap` function.

C Examples

See `mexcallmatlab.c` in the `mex` subdirectory of the `examples` directory.

Additional examples:

- `sincall.c` in the `refbook` subdirectory of the `examples` directory

mexCallMATLAB (C and Fortran)

- `mexevalstring.c` and `mexsettrapflag.c` in the `mex` subdirectory of the `examples` directory
- `mxcreatecellmatrix.c` and `mxisclass.c` in the `mx` subdirectory of the `examples` directory

See Also

`mexFunction`, `mexCallMATLABWithTrap`, `mexEvalString`,
`mxDestroyArray`

mexCallMATLABWithTrap (C and Fortran)

Purpose

Call MATLAB function, user-defined M-file, or MEX-file and capture error information

C Syntax

```
#include "mex.h"
mxArray *mexCallMATLABWithTrap(int nlhs, mxArray *plhs[], int nrhs,
    const mxArray *prhs[], const char *functionName);
```

Fortran Syntax

```
mwPointer mexCallMATLABWithTrap(nlhs, plhs, nrhs, prhs, functionName)
integer*4 nlhs, nrhs
mwPointer plhs(*), prhs(*)
character*(*) functionName
```

Arguments

For more information about arguments, see `mexCallMATLAB`.

`nlhs`

Number of desired output arguments.

`plhs`

Array of pointers to output arguments.

`nrhs`

Number of input arguments.

`prhs`

Array of pointers to input arguments.

`functionName`

Character string containing the `functionName` of the MATLAB built-in, operator, M-file, or MEX-file that you are calling.

Returns

NULL if no error occurred; otherwise, a pointer to an `mxArray` of class `MException`.

Description

The `mexCallMATLABWithTrap` function performs the same function as `mexCallMATLAB`. However, if MATLAB detects an error when executing `functionName`, MATLAB returns control to the line in the MEX-file immediately following the call to `mexCallMATLABWithTrap`. For information about `MException`, see “Responding to an Exception”

mexCallMATLABWithTrap (C and Fortran)

See Also `mexCallMATLAB`, `MException`

mexErrMsgIdAndTxt (C and Fortran)

Purpose	Issue error message with identifier and return to MATLAB prompt
C Syntax	<pre>#include "mex.h" void mexErrMsgIdAndTxt(const char *errorid, const char *errmsg, ...);</pre>
Fortran Syntax	<pre>mexErrMsgIdAndTxt(errorid, errmsg) character*(*) errorid, errmsg</pre>
Arguments	<p>errorid String containing a MATLAB message identifier. For information on creating identifiers, see “Message Identifiers” in the MATLAB Programming Fundamentals documentation.</p> <p>errmsg String containing the error message to be displayed. In C, the string may include formatting conversion characters, such as those used with the ANSI C <code>sprintf</code> function.</p> <p>...</p> <p>In C, any additional arguments needed to translate formatting conversion characters used in <code>errmsg</code>. Each conversion character in <code>errmsg</code> is converted to one of these values.</p>
Description	<p>Call <code>mexErrMsgIdAndTxt</code> to write an error message and its corresponding identifier to the MATLAB window. After the error message prints, MATLAB terminates the MEX-file and returns control to the MATLAB prompt.</p> <p>Calling <code>mexErrMsgIdAndTxt</code> does not clear the MEX-file from memory. Consequently, <code>mexErrMsgIdAndTxt</code> does not invoke the function registered through <code>mexAtExit</code>.</p> <p>If your application called <code>mxCalloc</code> or one of the <code>mxCreat*</code> routines to allocate memory, <code>mexErrMsgIdAndTxt</code> automatically frees the allocated memory.</p>

mexErrMsgIdAndTxt (C and Fortran)

Note If you get warnings when using `mexErrMsgIdAndTxt`, you may have a memory management compatibility problem. For more information, see “Memory Management Issues” in the External Interfaces documentation.

Remarks

In addition to the `errorid` and `errmsg`, the `mexerrmsgtxt` function determines where the error occurred, and displays the following information. For example, in the function `foo`, `mexerrmsgtxt` displays:

```
??? Error using ==> foo
```

See Also

`mexErrMsgTxt`, `mexWarnMsgIdAndTxt`, `mexWarnMsgTxt`

Purpose	Issue error message and return to MATLAB prompt
C Syntax	<pre>#include "mex.h" void mexErrMsgTxt(const char *errmsg);</pre>
Fortran Syntax	<pre>mexErrMsgTxt(errormsg) character*(*) errmsg</pre>
Arguments	<p>errmsg String containing the error message to be displayed</p>
Description	<p>Call <code>mexErrMsgTxt</code> to write an error message to the MATLAB window. After the error message prints, MATLAB terminates the MEX-file and returns control to the MATLAB prompt.</p> <p>Calling <code>mexErrMsgTxt</code> does not clear the MEX-file from memory. Consequently, <code>mexErrMsgTxt</code> does not invoke the function registered through <code>mexAtExit</code>.</p> <p>If your application called <code>mxCalloc</code> or one of the <code>mxCreat*</code> routines to allocate memory, <code>mexErrMsgTxt</code> automatically frees the allocated memory.</p> <hr/> <p>Note If you get warnings when using <code>mexErrMsgTxt</code>, you may have a memory management compatibility problem. For more information, see “Memory Management Issues”.</p> <hr/>
Remarks	<p>In addition to the <code>errmsg</code>, the <code>mexerrmsgtxt</code> function determines where the error occurred, and displays the following information. If an error labeled <code>Print my error message</code> occurs in the function <code>foo</code>, <code>mexerrmsgtxt</code> displays:</p> <pre>??? Error using ==> foo Print my error message</pre>

mexErrMsgTxt (C and Fortran)

C Examples

See `xtimesy.c` in the `refbook` subdirectory of the `examples` directory.

For additional examples, see `convec.c`, `findnz.c`, `fulltosparse.c`, `phonebook.c`, `revord.c`, and `timestwo.c` in the `refbook` subdirectory of the `examples` directory.

See Also

`mexErrMsgIdAndTxt`, `mexWarnMsgIdAndTxt`, `mexWarnMsgTxt`

Purpose	Execute MATLAB command in caller's workspace
C Syntax	<pre>#include "mex.h" int mexEvalString(const char *command);</pre>
Fortran Syntax	<pre>integer*4 mexEvalString(command) character*(*) command</pre>
Arguments	command A string containing the MATLAB command to execute
Returns	0 if successful, and a nonzero value if unsuccessful.
Description	<p>Call <code>mexEvalString</code> to invoke a MATLAB command in the workspace of the caller.</p> <p><code>mexEvalString</code> and <code>mexCallMATLAB</code> both execute MATLAB commands. However, <code>mexCallMATLAB</code> provides a mechanism for returning results (left-hand side arguments) back to the MEX-file; <code>mexEvalString</code> provides no way for return values to be passed back to the MEX-file.</p> <p>All arguments that appear to the right of an equal sign in the command string must already be current variables of the caller's workspace.</p>
Error Handling	If command detects an error, MATLAB terminates the MEX-file and returns control to the MATLAB prompt. If you want to trap errors, use the <code>mexEvalStringWithTrap</code> function.
Examples	See <code>mexevalstring.c</code> in the <code>mex</code> subdirectory of the <code>examples</code> directory.
See Also	<code>mexCallMATLAB</code> , <code>mexEvalStringWithTrap</code>

mexEvalStringWithTrap (C and Fortran)

Purpose	Execute MATLAB command in caller's workspace and capture error information
C Syntax	<pre>#include "mex.h" mxAArray *mexEvalStringWithTrap(const char *command);</pre>
Fortran Syntax	<pre>mwPointer mexEvalStringWithTrap(command) character*(*) command</pre>
Arguments	command A string containing the MATLAB command to execute
Returns	an object ME of class MException
Description	The mexEvalStringWithTrap function performs the same function as mexEvalString. However, if MATLAB detects an error when executing command, MATLAB returns control to the line in the MEX-file immediately following the call to mexEvalStringWithTrap.
See Also	mexEvalString, MException, mexCallMATLAB

Purpose	Entry point to C MEX-file
C Syntax	<pre>#include "mex.h" void mexFunction(int nlhs, mxArray *plhs[], int nrhs, const mxArray *prhs[]);</pre>
Fortran Syntax	<pre>mexFunction(nlhs, plhs, nrhs, prhs) integer*4 nlhs, nrhs mwPointer plhs(*), prhs(*)</pre>
Arguments	<p>nlhs The number of expected output mxArrays</p> <p>plhs Array of pointers to the expected output mxArrays</p> <p>nrhs The number of input mxArrays</p> <p>prhs Array of pointers to the input mxArrays. These mxArrays are read only and should not be modified by your MEX-file. Changing the data in these mxArrays may produce undesired side effects.</p>
Description	<p>mexFunction is not a routine you call. Rather, mexFunction is the name of a function in C (subroutine in Fortran) that you must write in every MEX-file. When you invoke a MEX-function, MATLAB software finds and loads the corresponding MEX-file of the same name. MATLAB then searches for a symbol named mexFunction within the MEX-file. If it finds one, it calls the MEX-function using the address of the mexFunction symbol. If MATLAB cannot find a routine named mexFunction inside the MEX-file, it issues an error message.</p> <p>When you invoke a MEX-file, MATLAB automatically seeds nlhs, plhs, nrhs, and prhs with the caller's information. In the syntax of the MATLAB language, functions have the general form:</p> $[a,b,c,\dots] = \text{fun}(d,e,f,\dots)$

mexFunction (C and Fortran)

where the ... denotes more items of the same format. The `a,b,c...` are left-hand side arguments, and the `d,e,f...` are right-hand side arguments. The arguments `nlhs` and `nrhs` contain the number of left-hand side and right-hand side arguments, respectively, with which the MEX-function is called. `prhs` is an array of `mxAarray` pointers whose length is `nrhs`. `plhs` is an array whose length is `nlhs`, where your function must set pointers for the returned left-hand side `mxAarrays`.

C **Examples**

See `mexfunction.c` in the `mex` subdirectory of the `examples` directory.

mexFunctionName (C and Fortran)

Purpose Name of current MEX-function

C Syntax

```
#include "mex.h"
const char *mexFunctionName(void);
```

Fortran Syntax

```
character*(*) mexFunctionName()
```

Returns The name of the current MEX-function.

Description mexFunctionName returns the name of the current MEX-function.

C Examples See mexgetarray.c in the mex subdirectory of the examples directory.

mexGet (C)

Purpose	Get value of specified Handle Graphics property
C Syntax	<pre>#include "mex.h" const mxArray *mexGet(double handle, const char *property);</pre>
Arguments	<p>handle Handle to a particular graphics object</p> <p>property A Handle Graphics property</p>
Returns	The value of the specified property in the specified graphics object on success. Returns NULL on failure. The return argument from <code>mexGet</code> is declared as <code>constant</code> , meaning that it is read only and should not be modified. Changing the data in these <code>mxArrays</code> may produce undesired side effects.
Description	Call <code>mexGet</code> to get the value of the property of a certain graphics object. <code>mexGet</code> is the API equivalent of the MATLAB <code>get</code> function. To set a graphics property value, call <code>mexSet</code> .
Examples	See <code>mexget.c</code> in the <code>mex</code> subdirectory of the <code>examples</code> directory.
See Also	<code>mexSet</code>

Purpose	Get copy of variable from specified workspace						
C Syntax	<pre>#include "mex.h" mxAArray *mexGetVariable(const char *workspace, const char *varname);</pre>						
Fortran Syntax	<pre>mwPointer mexGetVariable(workspace, varname) character*(*) workspace, varname</pre>						
Arguments	<p>workspace Specifies where <code>mexGetVariable</code> should search in order to find array <code>varname</code>. The possible values are</p> <table><tr><td><code>base</code></td><td>Search for the variable in the base workspace.</td></tr><tr><td><code>caller</code></td><td>Search for the variable in the caller's workspace.</td></tr><tr><td><code>global</code></td><td>Search for the variable in the global workspace.</td></tr></table> <p>varname Name of the variable to copy</p>	<code>base</code>	Search for the variable in the base workspace.	<code>caller</code>	Search for the variable in the caller's workspace.	<code>global</code>	Search for the variable in the global workspace.
<code>base</code>	Search for the variable in the base workspace.						
<code>caller</code>	Search for the variable in the caller's workspace.						
<code>global</code>	Search for the variable in the global workspace.						
Returns	A copy of the variable on success. Returns NULL in C (0 on Fortran) on failure. A common cause of failure is specifying a variable that is not currently in the workspace. Perhaps the variable was in the workspace at one time but has since been cleared.						
Description	<p>Call <code>mexGetVariable</code> to get a copy of the specified variable. The returned <code>mxAArray</code> contains a copy of all the data and characteristics that the variable had in the other workspace. Modifications to the returned <code>mxAArray</code> do not affect the variable in the workspace unless you write the copy back to the workspace with <code>mexPutVariable</code>.</p> <p>Use <code>mxDestroyArray</code> to destroy the <code>mxAArray</code> created by this routine when you are finished with it.</p>						

mexGetVariable (C and Fortran)

C Examples

See `mexgetarray.c` in the `mex` subdirectory of the `examples` directory.

See Also

`mexGetVariablePtr`, `mexPutVariable`, `mxDestroyArray`

mexGetVariablePtr (C and Fortran)

Purpose	Get read-only pointer to variable from another workspace						
C Syntax	<pre>#include "mex.h" const mxArray *mexGetVariablePtr(const char *workspace, const char *varname);</pre>						
Fortran Syntax	<pre>mwPointer mexGetVariablePtr(workspace, varname) character*(*) workspace, varname</pre>						
Arguments	<p>workspace Specifies which workspace you want <code>mexGetVariablePtr</code> to search. The possible values are</p> <table><tr><td><code>base</code></td><td>Search for the variable in the base workspace.</td></tr><tr><td><code>caller</code></td><td>Search for the variable in the caller's workspace.</td></tr><tr><td><code>global</code></td><td>Search for the variable in the global workspace.</td></tr></table> <p>varname Name of a variable in another workspace. This is a variable name, not an <code>mxArray</code> pointer.</p>	<code>base</code>	Search for the variable in the base workspace.	<code>caller</code>	Search for the variable in the caller's workspace.	<code>global</code>	Search for the variable in the global workspace.
<code>base</code>	Search for the variable in the base workspace.						
<code>caller</code>	Search for the variable in the caller's workspace.						
<code>global</code>	Search for the variable in the global workspace.						
Returns	A read-only pointer to the <code>mxArray</code> on success. Returns <code>NULL</code> in C (0 in Fortran) on failure.						
Description	<p>Call <code>mexGetVariablePtr</code> to get a read-only pointer to the specified variable, <code>varname</code>, into your MEX-file's workspace. This command is useful for examining an <code>mxArray</code>'s data and characteristics. If you need to change data or characteristics, use <code>mexGetVariable</code> (along with <code>mexPutVariable</code>) instead of <code>mexGetVariablePtr</code>.</p> <p>If you simply need to examine data or characteristics, <code>mexGetVariablePtr</code> offers superior performance because the caller needs to pass only a pointer to the array.</p>						

mexGetVariablePtr (C and Fortran)

C Examples

See `mxislogical.c` in the `mx` subdirectory of the `examples` directory.

See Also

`mexGetVariable`

Purpose	Determine whether mxArray has global scope
C Syntax	<pre>#include "matrix.h" bool mexIsGlobal(const mxArray *pm);</pre>
Fortran Syntax	<pre>integer*4 mexIsGlobal(pm) mwPointer pm</pre>
Arguments	pm Pointer to an mxArray
Returns	Logical 1 (true) if the mxArray has global scope, and logical 0 (false) otherwise.
Description	Use mexIsGlobal to determine whether the specified mxArray has global scope.
C Examples	See mxislogical.c in the mx subdirectory of the examples directory.
See Also	mexGetVariable, mexGetVariablePtr, mexPutVariable, global

mexIsLocked (C and Fortran)

Purpose	Determine whether MEX-file is locked
C Syntax	<pre>#include "mex.h" bool mexIsLocked(void);</pre>
Fortran Syntax	<pre>integer*4 mexIsLocked()</pre>
Returns	Logical 1 (true) if the MEX-file is locked; logical 0 (false) if the file is unlocked.
Description	<p>Call <code>mexIsLocked</code> to determine whether the MEX-file is locked. By default, MEX-files are unlocked, meaning that users can clear the MEX-file at any time.</p> <p>To unlock a MEX-file, call <code>mexUnlock</code>.</p>
C Examples	See <code>mexlock.c</code> in the <code>mex</code> subdirectory of the <code>examples</code> directory.
See Also	<code>mexLock</code> , <code>mexMakeArrayPersistent</code> , <code>mexMakeMemoryPersistent</code> , <code>mexUnlock</code>

Purpose	Prevent MEX-file from being cleared from memory
C Syntax	<pre>#include "mex.h" void mexLock(void);</pre>
Fortran Syntax	<pre>mexLock()</pre>
Description	<p>By default, MEX-files are unlocked, meaning that a user can clear them at any time. Call <code>mexLock</code> to prohibit a MEX-file from being cleared.</p> <p>To unlock a MEX-file, you must call <code>mexUnlock</code>. Do not use the <code>munlock</code> function.</p> <p><code>mexLock</code> increments a lock count. If you call <code>mexLock</code> <code>n</code> times, you must call <code>mexUnlock</code> <code>n</code> times to unlock your MEX-file.</p>
C Examples	See <code>mexlock.c</code> in the <code>mex</code> subdirectory of the <code>examples</code> directory.
See Also	<code>mexIsLocked</code> , <code>mexMakeArrayPersistent</code> , <code>mexMakeMemoryPersistent</code> , <code>mexUnlock</code>

mexMakeArrayPersistent (C and Fortran)

Purpose Make mxArray persist after MEX-file completes

C Syntax

```
#include "mex.h"
void mexMakeArrayPersistent(mxArray *pm);
```

Fortran Syntax

```
mexMakeArrayPersistent(pm)
mwPointer pm
```

Arguments pm
Pointer to an mxArray created by an mxCreate* function

Description By default, an mxArray allocated by an mxCreate* function is not persistent. The MATLAB memory management facility automatically frees a nonpersistent mxArray when the MEX-function finishes. If you want the mxArray to persist through multiple invocations of the MEX-function, you must call the mexMakeArrayPersistent function.

Note If you create a persistent mxArray, you are responsible for destroying it using mxDestroyArray when the MEX-file is cleared. If you do not destroy a persistent mxArray, MATLAB leaks memory. See mexAtExit to see how to register a function that gets called when the MEX-file is cleared. See mexLock to see how to lock your MEX-file so that it is never cleared.

See Also mexAtExit, mxDestroyArray, mexLock, mexMakeMemoryPersistent, and the mxCreate* functions

mexMakeMemoryPersistent (C and Fortran)

Purpose	Make memory allocated by MATLAB software persist after MEX-function completes
C Syntax	<pre>#include "mex.h" void mexMakeMemoryPersistent(void *ptr);</pre>
Fortran Syntax	<pre>mexMakeMemoryPersistent(ptr) mwPointer ptr</pre>
Arguments	<p><code>ptr</code></p> <p>Pointer to the beginning of memory allocated by one of the MATLAB memory allocation routines</p>
Description	<p>By default, memory allocated by MATLAB software is nonpersistent, so it is freed automatically when the MEX-function finishes. If you want the memory to persist, you must call <code>mexMakeMemoryPersistent</code>.</p> <hr/> <p>Note If you create persistent memory, you are responsible for freeing it when the MEX-function is cleared. If you do not free the memory, MATLAB leaks memory. To free memory, use <code>mxFree</code>. See <code>mexAtExit</code> to see how to register a function that gets called when the MEX-function is cleared. See <code>mexLock</code> to see how to lock your MEX-function so that it is never cleared.</p> <hr/>
See Also	<code>mexAtExit</code> , <code>mexLock</code> , <code>mexMakeArrayPersistent</code> , <code>mxMalloc</code> , <code>mxFree</code> , <code>mxMalloc</code> , <code>mxRealloc</code>

mexPrintf (C and Fortran)

Purpose ANSI C printf-style output routine

C Syntax

```
#include "mex.h"
int mexPrintf(const char *message, ...);
```

Fortran Syntax

```
integer*4 mexPrintf(message)
character*(*) message
```

Arguments

message
String to be displayed. In C, the string may include formatting conversion characters, such as those used with the ANSI C printf function.

...
In C, any additional arguments needed to translate formatting conversion characters used in message. Each conversion character in message is converted to one of these values.

Returns The number of characters printed. This includes characters specified with backslash codes, such as \n and \b.

Description This routine prints a string on the screen and in the diary (if the diary is in use). It provides a callback to the standard C printf routine already linked inside MATLAB software, and avoids linking the entire stdio library into your MEX-file.

In a C MEX-file, you must call mexPrintf instead of printf to display a string.

Note If you want the literal % in your message, you must use %% in your message string since % has special meaning to mexPrintf. Failing to do so causes unpredictable results.

C Examples

See

- `mexfunction.c` in the `mex` subdirectory of the `examples` directory
- `phonebook.c` in the `refbook` subdirectory of the `examples` directory.

See Also

`mexErrMsgIdAndTxt`, `mexErrMsgTxt`, `mexWarnMsgIdAndTxt`,
`mexWarnMsgTxt`

mexPutVariable (C and Fortran)

Purpose	Copy mxArray from MEX-function into specified workspace
C Syntax	<pre>#include "mex.h" int mexPutVariable(const char *workspace, const char *varname, const mxArray *pm);</pre>
Fortran Syntax	<pre>integer*4 mexPutVariable(workspace, varname, pm) character*(*) workspace, varname mwPointer pm</pre>
Arguments	<p>workspace Specifies the scope of the array that you are copying. The possible values are</p> <ul style="list-style-type: none">base Copy mxArray to the base workspace.caller Copy mxArray to the caller's workspace.global Copy mxArray to the list of global variables. <p>varname Name given to the mxArray in the workspace</p> <p>pm Pointer to the mxArray</p>
Returns	0 on success; 1 on failure. A possible cause of failure is that pm is NULL in C (0 in Fortran).
Description	<p>Call mexPutVariable to copy the mxArray, at pointer pm, from your MEX-function into the specified workspace. MATLAB software gives the name, varname, to the copied mxArray in the receiving workspace.</p> <p>mexPutVariable makes the array accessible to other entities, such as MATLAB, M-files, or other MEX-functions.</p> <p>If a variable of the same name already exists in the specified workspace, mexPutVariable overwrites the previous contents of the variable with</p>

the contents of the new mxArray. For example, suppose the MATLAB workspace defines variable `Peaches` as:

```
Peaches
1      2      3      4
```

and you call `mexPutVariable` to copy `Peaches` into the same workspace:

```
mexPutVariable("base", "Peaches", pm)
```

Then the old value of `Peaches` disappears and is replaced by the value passed in by `mexPutVariable`.

C **Examples**

See `mexgetarray.c` in the `mex` subdirectory of the `examples` directory.

See Also

`mexGetVariable`

mexSet (C)

Purpose Set value of specified Handle Graphics property

C Syntax

```
#include "mex.h"
int mexSet(double handle, const char *property,
           mxArray *value);
```

Arguments

handle
Handle to a particular graphics object

property
String naming a Handle Graphics property

value
Pointer to an mxArray holding the new value to assign to the property

Returns 0 on success; 1 on failure. Possible causes of failure include:

- Specifying a nonexistent property.
- Specifying an illegal value for that property, for example, specifying a string value for a numerical property.

Description Call mexSet to set the value of the property of a certain graphics object. mexSet is the API equivalent of the MATLAB set function. To get the value of a graphics property, call mexGet.

Examples See mexget.c in the mex subdirectory of the examples directory.

See Also mexGet

Purpose Control response of mexCallMATLAB to errors

C Syntax

```
#include "mex.h"
void mexSetTrapFlag(int trapflag);
```

Note The mexsettrapflag function will be removed in a future version of MATLAB software.

Fortran Syntax

```
mexSetTrapFlag(trapflag)
integer*4 trapflag
```

Arguments

trapflag
Control flag. Possible values are:

0	On error, control returns to the MATLAB prompt.
1	On error, control returns to your MEX-file.

Description Call mexSetTrapFlag to control the MATLAB response to errors in mexCallMATLAB.

If you do not call mexSetTrapFlag, then whenever MATLAB detects an error in a call to mexCallMATLAB, MATLAB automatically terminates the MEX-file and returns control to the MATLAB prompt. Calling mexSetTrapFlag with trapflag set to 0 is equivalent to not calling mexSetTrapFlag at all.

If you call mexSetTrapFlag and set the trapflag to 1, then whenever MATLAB detects an error in a call to mexCallMATLAB, MATLAB does not automatically terminate the MEX-file. Rather, MATLAB returns control to the line in the MEX-file immediately following the call to mexCallMATLAB. The MEX-file is then responsible for taking an appropriate response to the error.

If you call mexSetTrapFlag, the value of the trapflag you set remains in effect until the next call to mexSetTrapFlag within that MEX-file or,

mexSetTrapFlag (C and Fortran)

if there are no more calls to `mexSetTrapFlag`, until the MEX-file exits. If a routine defined in a MEX-file calls another MEX-file,

- 1 The current value of the `trapflag` in the first MEX-file is saved.
- 2 The second MEX-file is called with the `trapflag` initialized to 0 within that file.
- 3 When the second MEX-file exits, the saved value of the `trapflag` in the first MEX-file is restored within that file.

C Examples

See `mexsettrapflag.c` in the `mex` subdirectory of the `examples` directory.

See Also

`mexCallMATLAB`, `mexCallMATLABWithTrap`, `mexAtExit`, `mexErrMsgTxt`

Purpose Allow MEX-file to be cleared from memory

C Syntax

```
#include "mex.h"
void mexUnlock(void);
```

**Fortran
Syntax**

```
mexUnlock()
```

Description By default, MEX-files are unlocked, meaning that a user can clear them at any time. Calling `mexLock` locks a MEX-file so that it cannot be cleared. Calling `mexUnlock` removes the lock so that the MEX-file can be cleared.

`mexLock` increments a lock count. If you called `mexLock` `n` times, you must call `mexUnlock` `n` times to unlock your MEX-file.

**C
Examples** See `mexlock.c` in the `mex` subdirectory of the `examples` directory.

See Also `mexIsLocked`, `mexLock`, `mexMakeArrayPersistent`,
`mexMakeMemoryPersistent`

mexWarnMsgIdAndTxt (C and Fortran)

Purpose	Issue warning message with identifier
C Syntax	<pre>#include "mex.h" void mexWarnMsgIdAndTxt(const char *warningid, const char *warningmsg, ...);</pre>
Fortran Syntax	<pre>mexWarnMsgIdAndTxt(warningid, warningmsg) character*(*) warningid, warningmsg</pre>
Arguments	<p><code>warningid</code> String containing a MATLAB message identifier. For information on creating identifiers, see “Message Identifiers” in the MATLAB Programming Fundamentals documentation.</p> <p><code>warningmsg</code> String containing the warning message to be displayed. In C, the string may include formatting conversion characters, such as those used with the ANSI C <code>sprintf</code> function.</p> <p>...</p> <p>In C, any additional arguments needed to translate formatting conversion characters used in <code>warningmsg</code>. Each conversion character in <code>warningmsg</code> is converted to one of these values.</p>
Description	<p>Call <code>mexWarnMsgIdAndTxt</code> to write a warning message and its corresponding identifier to the MATLAB window.</p> <p>Unlike <code>mexErrMsgIdAndTxt</code>, <code>mexWarnMsgIdAndTxt</code> does not cause the MEX-file to terminate.</p>
See Also	<code>mexErrMsgTxt</code> , <code>mexErrMsgIdAndTxt</code> , <code>mexWarnMsgTxt</code>

mexWarnMsgTxt (C and Fortran)

Purpose	Issue warning message
C Syntax	<pre>#include "mex.h" void mexWarnMsgTxt(const char *warningmsg);</pre>
Fortran Syntax	<pre>mexWarnMsgTxt(warningmsg) character*(*) warningmsg</pre>
Arguments	<p>warningmsg String containing the warning message to be displayed</p>
Description	<p>mexWarnMsgTxt causes MATLAB software to display the contents of warningmsg.</p> <p>Unlike mexErrMsgTxt, mexWarnMsgTxt does not cause the MEX-file to terminate.</p>
C Examples	<p>See yprime.c in the mex subdirectory of the examples directory.</p> <p>Additional examples:</p> <ul style="list-style-type: none">• explore.c in the mex subdirectory of the examples directory• fulltosparse.c in the refbook subdirectory of the examples directory• mxisfinite.c and mxsetnzmax.c in the mx subdirectory of the examples directory
See Also	mexErrMsgTxt, mexErrMsgIdAndTxt, mexWarnMsgIdAndTxt

mwIndex (C and Fortran)

Purpose Type for index values

Description `mwIndex` is a type that represents index values, such as indices into arrays. This function is provided for purposes of cross-platform flexibility. By default, `mwIndex` is equivalent to `int` in C. When using the `mex -largeArrayDims` switch, `mwIndex` is equivalent to `size_t` in C. `mwIndex` is equivalent to `INTEGER*4` in Fortran. The C header file containing this type is:

```
#include "matrix.h"
```

In Fortran, `mwIndex` is implemented as a preprocessor macro. The Fortran header file containing this type is:

```
#include "fintrf.h"
```

See Also `mex`, `mwSize`

Purpose Declare appropriate pointer type for platform

Description `mwPointer` is a preprocessor macro that declares the appropriate Fortran type representing a pointer to an `mxAarray` or to other data that is not of a native Fortran type, such as memory allocated by `mxFmalloc`. On 32-bit platforms, the Fortran type that represents a pointer is `INTEGER*4`; on 64-bit platforms, it is `INTEGER*8`. The Fortran preprocessor translates `mwPointer` to the Fortran declaration that is appropriate for the platform on which you compile your file.

If your Fortran compiler supports preprocessing, you can use `mwPointer` to declare functions, arguments, and variables that represent pointers. If you cannot use `mwPointer`, you must ensure that your declarations have the correct size for the platform on which you are compiling Fortran code.

The Fortran header file containing this type is:

```
#include "finturf.h"
```

Examples This example declares the arguments for `mexFunction` in a Fortran MEX-file:

```
SUBROUTINE MEXFUNCTION(NLHS, PLHS, NRHS, PRHS)
  MWPOINTER PLHS(*), PRHS(*)
  INTEGER NLHS, NRHS
```

For additional examples, see the Fortran files with names ending in `.F` in the `matlabroot/extern/examples` directory.

mwSize (C and Fortran)

Purpose Type for size values

Description `mwSize` is a type that represents size values, such as array dimensions. This function is provided for purposes of cross-platform flexibility. By default, `mwSize` is equivalent to `int` in C. When using the `mex -largeArrayDims` switch, `mwSize` is equivalent to `size_t` in C. `mwSize` is equivalent to `INTEGER*4` in Fortran.

In Fortran, `mwSize` is implemented as a preprocessor macro.

The C header file containing this type is:

```
#include "matrix.h"
```

The Fortran header file containing this type is:

```
#include "fintrf.h"
```

See Also `mex`, `mwIndex`

mxAddField (C and Fortran)

Purpose	Add field to structure array
C Syntax	<pre>#include "matrix.h" extern int mxAddField(mxArray *pm, const char *fieldname);</pre>
Fortran Syntax	<pre>integer*4 mxAddField(pm, fieldname) mwPointer pm character*(*) fieldname</pre>
Arguments	<p>pm Pointer to a structure mxArray</p> <p>fieldname Name of the field you want to add</p>
Returns	Field number on success or -1 if inputs are invalid or an out-of-memory condition occurs.
Description	Call mxAddField to add a field to a structure array. You must then create the values with the mxCreate* functions and use mxSetFieldByNumber to set the individual values for the field.
See Also	mxRemoveField, mxSetFieldByNumber

mxArray (C and Fortran)

Purpose Type for a MATLAB array

Description The fundamental type underlying MATLAB data. For information on how the MATLAB array works with MATLAB-supported variables, see “MATLAB Data” in the External Interfaces documentation.

mxArray is a C language opaque type.

All C and Fortran MEX-files start with a gateway routine, called `mexFunction`, which requires mxArray for both input and output parameters. A C MEX-file gateway routine is described in “C Source MEX-Files”. The Fortran version is described in “Fortran Source MEX-Files”.

Once you have MATLAB data in your MEX-file, you can use the array access library routines (listed in “MX Array Manipulation” on page 1-2) to manipulate the data, and the MEX library routines (listed in “MEX-Files” on page 1-10) to perform operations in the MATLAB environment. You use mxArray to pass data to and from these functions.

Use any of the `mxCreate*` functions when you need to create data, and the corresponding `mxDestroyArray` function to free memory.

The header file containing this type is:

```
#include "matrix.h"
```

Example See `mxcreatecharmatrixfromstr.c` in your `matlabroot/extern/examples/mx` directory.

The input argument `prhs` contains two or more strings, defined as mxArray. Use the `mxIsChar` function to validate the input. Create a C variable `str` of type `char` using the `mxArrayToString` function. Now you can manipulate your data in C.

To set the return values in `plhs`, use the `mxCreateCharMatrixFromStrings` function.

Before you exit your routine, be sure to free memory using the `mxFree` function on `str`.

See Also

`mexFunction`, `mxClassID`, `mxCreateDoubleMatrix`,
`mxCreateNumericArray`, `mxCreateString`, `mxDestroyArray`,
`mxGetData`, `mxSetData`

mxArrayToString (C)

Purpose Convert array to string

C Syntax

```
#include "matrix.h"
char *mxArrayToString(const mxArray *array_ptr);
```

Arguments array_ptr
Pointer to a string mxArray; that is, a pointer to an mxArray having the mxCHAR_CLASS class.

Returns A C-style string. Returns NULL on failure. Possible reasons for failure include out of memory and specifying an mxArray that is not a string mxArray.

Description Call mxArrayToString to copy the character data of a string mxArray into a C-style string. The C-style string is always terminated with a NULL character.

If the string array contains several rows, they are copied, one column at a time, into one long string array. This function is similar to mxGetString, except that

- It does not require the length of the string as an input.
- It supports multibyte character sets.

mxArrayToString does not free the dynamic memory that the char pointer points to. Consequently, you should typically free the string (using mxFree) immediately after you have finished using it.

Examples See mexatexit.c in the mex subdirectory of the examples directory.

For additional examples, see mxcreatecharmatrixfromstr.c and mxislogical.c in the mx subdirectory of the examples directory.

See Also mxCreateCharArray, mxCreateCharMatrixFromStrings, mxCreateString, mxGetString

Purpose	Check assertion value for debugging purposes
C Syntax	<pre>#include "matrix.h" void mxAssert(int expr, char *error_message);</pre>
Arguments	<p><code>expr</code> Value of assertion</p> <p><code>error_message</code> Description of why assertion failed</p>
Description	<p>Similar to the ANSI C <code>assert</code> macro, <code>mxAssert</code> checks the value of an assertion, and continues execution only if the assertion holds. If <code>expr</code> evaluates to logical 1 (true), <code>mxAssert</code> does nothing. If <code>expr</code> evaluates to logical 0 (false), <code>mxAssert</code> prints an error to the MATLAB command window consisting of the failed assertion's expression, the filename and line number where the failed assertion occurred, and the <code>error_message</code> string. The <code>error_message</code> string allows you to specify a better description of why the assertion failed. Use an empty string if you don't want a description to follow the failed assertion message.</p> <p>For information about MATLAB behavior after a failed assertion, see "Abnormal Termination" in the Desktop Tools and Development Environment documentation.</p> <p>The <code>mex</code> script turns off these assertions when building optimized MEX-functions, so use this for debugging purposes only. Build the MEX-file using the syntax <code>mex -g filename</code> in order to use <code>mxAssert</code>.</p> <p>Assertions are a way of maintaining internal consistency of logic. Use them to keep yourself from misusing your own code and to prevent logical errors from propagating before they are caught; do not use assertions to prevent users of your code from misusing it.</p> <p>Assertions can be taken out of your code by the C preprocessor. You can use these checks during development and then remove them when the code works properly, letting you use them for troubleshooting during development without slowing down the final product.</p>

mxAssertS (C)

Purpose	Check assertion value without printing assertion text
C Syntax	<pre>#include "matrix.h" void mxAssertS(int expr, char *error_message);</pre>
Arguments	<p>expr Value of assertion</p> <p>error_message Description of why assertion failed</p>
Description	mxAssertS is similar to mxAssert, except mxAssertS does not print the text of the failed assertion.

mxCalcSingleSubscript (C and Fortran)

Purpose

Offset from first element to desired element

C Syntax

```
#include "matrix.h"
mwIndex mxCalcSingleSubscript(const mxArray *pm, mwSize nsubs,
                               mwIndex *subs);
```

Fortran Syntax

```
mwIndex mxCalcSingleSubscript(pm, nsubs, subs)
mwPointer pm
mwSize nsubs
mwIndex subs
```

Arguments

pm

Pointer to an mxArray

nsubs

The number of elements in the subs array. Typically, you set nsubs equal to the number of dimensions in the mxArray that pm points to.

subs

An array of integers. Each value in the array should specify that dimension's subscript. In C syntax, the value in subs[0] specifies the row subscript, and the value in subs[1] specifies the column subscript. Use zero-based indexing for subscripts. For example, to express the starting element of a two-dimensional mxArray in subs, set subs[0] to 0 and subs[1] to 0.

In Fortran syntax, the value in subs(1) specifies the row subscript, and the value in subs(2) specifies the column subscript. Use 1-based indexing for subscripts. For example, to express the starting element of a two-dimensional mxArray in subs, set subs(1) to 1 and subs(2) to 1.

Returns

The number of elements between the start of the mxArray and the specified subscript. This returned number is called an *index*; many mx routines (for example, mxGetField) require an index as an argument.

mxCalcSingleSubscript (C and Fortran)

If `subs` describes the starting element of an `mxAarray`, `mxCalcSingleSubscript` returns 0. If `subs` describes the final element of an `mxAarray`, `mxCalcSingleSubscript` returns `N-1` (where `N` is the total number of elements).

Description

Call `mxCalcSingleSubscript` to determine how many elements there are between the beginning of the `mxAarray` and a given element of that `mxAarray`. For example, given a subscript like `(5,7)`, `mxCalcSingleSubscript` returns the distance from the first element of the array to the `(5,7)` element. Remember that the `mxAarray` data type internally represents all data elements in a one-dimensional array no matter how many dimensions the MATLAB `mxAarray` appears to have.

MATLAB uses a column-major numbering scheme to represent data elements internally. That means that MATLAB internally stores data elements from the first column first, then data elements from the second column second, and so on through the last column. For example, suppose you create a 4-by-2 variable. It is helpful to visualize the data as follows.


A	E
B	F
C	G
D	H

In fact, though, MATLAB internally represents the data as the following:

A	B	C	D	E	F	G	H
Index 0	Index 1	Index 2	Index 3	Index 4	Index 5	Index 6	Index 7

If an `mxAarray` is `N`-dimensional, MATLAB represents the data in `N`-major order. For example, consider a three-dimensional array having dimensions 4-by-2-by-3. Although you can visualize the data as

mxCalcSingleSubscript (C and Fortran)



MATLAB internally represents the data for this three-dimensional array in the following order:

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X
0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23

Avoid using `mxCalcSingleSubscript` to traverse the elements of an array. In C, it is more efficient to do this by finding the array's starting address and then using pointer autoincrementing to access successive elements. For example, to find the starting address of a numerical array, call `mxGetPr` or `mxGetPi`.

C Examples

See `mxcalcsinglesubscript.c` in the `mx` subdirectory of the examples directory.

See Also

`mxGetCell`, `mxSetCell`

mxCalloc (C and Fortran)

Purpose Allocate dynamic memory for array using MATLAB memory manager

C Syntax

```
#include "matrix.h"
#include <stdlib.h>
void *mxCalloc(mwSize n, mwSize size);
```

Fortran Syntax

```
mwPointer mxCalloc(n, size)
mwSize n, size
```

Arguments

n Number of elements to allocate. This must be a nonnegative number.

size Number of bytes per element. (The C `sizeof` operator calculates the number of bytes per element.)

Returns A pointer to the start of the allocated dynamic memory, if successful. If unsuccessful in a stand alone (non-MEX-file) application, `mxCalloc` returns NULL in C (0 in Fortran). If unsuccessful in a MEX-file, the MEX-file terminates and control returns to the MATLAB prompt.

`mxCalloc` is unsuccessful when there is insufficient free heap space.

Description MATLAB applications should always call `mxCalloc` rather than `calloc` to allocate memory. The `mxCalloc` function works differently in MEX-files than in stand alone MATLAB applications.

In MEX-files, `mxCalloc` automatically

- Allocates enough contiguous heap space to hold `n` elements.
- Initializes all `n` elements to 0.
- Registers the returned heap space with the MATLAB memory manager.

The memory manager maintains a list of all memory allocated by `mxCalloc`. The memory manager automatically frees (deallocates) all MEX-file parcels when control returns to the MATLAB prompt.

In stand alone MATLAB C applications, `mxCalloc` calls the ANSI C `calloc` function.

By default, in a MEX-file, `mxCalloc` generates nonpersistent `mxCalloc` data. In other words, the memory manager automatically deallocates the memory as soon as the MEX-file ends. If you want the memory to persist after the MEX-file completes, call `mexMakeMemoryPersistent` after calling `mxCalloc`. If you write a MEX-file with persistent memory, be sure to register a `mexAtExit` function to free allocated memory in the event your MEX-file is cleared.

When you finish using the memory allocated by `mxCalloc`, call `mxFree` to deallocate the memory.

C Examples

See

- `explore.c` in the `mex` subdirectory of the `examples` directory
- `phonebook.c` and `revord.c` in the `refbook` subdirectory of the `examples` directory

For additional examples, see `mxcalcsinglesubscript.c` and `mxsetdimensions.c` in the `mx` subdirectory of the `examples` directory.

See Also

`mexAtExit`, `mexMakeArrayPersistent`, `mexMakeMemoryPersistent`, `mxDestroyArray`, `mxFree`, `mxCalloc`, `mxCRealloc`

mxChar (C)

Purpose Type for string mxArray

Description A string mxArray stores its data elements as mxChar rather than as char.

The header file containing this type is:

```
#include "matrix.h"
```

Examples See mxmalloc.c in the mx subdirectory of the examples directory.

Additional examples:

- explore.c in the mex subdirectory of the examples directory
- mxcreatecharmatrixfromstr.c in the mx subdirectory of the examples directory

See Also mxCreateCharArray

Purpose Enumerated value identifying class of mxArray

C Syntax

```
typedef enum {  
    mxUNKNOWN_CLASS,  
    mxCELL_CLASS,  
    mxSTRUCT_CLASS,  
    mxLOGICAL_CLASS,  
    mxCHAR_CLASS,  
    mxDOUBLE_CLASS,  
    mxSINGLE_CLASS,  
    mxINT8_CLASS,  
    mxUINT8_CLASS,  
    mxINT16_CLASS,  
    mxUINT16_CLASS,  
    mxINT32_CLASS,  
    mxUINT32_CLASS,  
    mxINT64_CLASS,  
    mxUINT64_CLASS,  
    mxFUNCTION_CLASS  
} mxClassID;
```

Constants

mxUNKNOWN_CLASS

The class cannot be determined. You cannot specify this category for an mxArray; however, mxGetClassID can return this value if it cannot identify the class.

mxCELL_CLASS

Identifies a cell mxArray.

mxSTRUCT_CLASS

Identifies a structure mxArray.

mxLOGICAL_CLASS

Identifies a logical mxArray, an mxArray whose data is represented as mxLogical.

mxCHAR_CLASS

Identifies a string mxArray, an mxArray whose data is represented as mxChar.

mxClassID (C)

mxDOUBLE_CLASS

Identifies a numeric mxArray whose data is stored as double-precision, floating-point numbers.

mxSINGLE_CLASS

Identifies a numeric mxArray whose data is stored as single-precision, floating-point numbers.

mxINT8_CLASS

Identifies a numeric mxArray whose data is stored as signed 8-bit integers.

mxUINT8_CLASS

Identifies a numeric mxArray whose data is stored as unsigned 8-bit integers.

mxINT16_CLASS

Identifies a numeric mxArray whose data is stored as signed 16-bit integers.

mxUINT16_CLASS

Identifies a numeric mxArray whose data is stored as unsigned 16-bit integers.

mxINT32_CLASS

Identifies a numeric mxArray whose data is stored as signed 32-bit integers.

mxUINT32_CLASS

Identifies a numeric mxArray whose data is stored as unsigned 32-bit integers.

mxINT64_CLASS

Identifies a numeric mxArray whose data is stored as signed 64-bit integers.

mxUINT64_CLASS

Identifies a numeric mxArray whose data is stored as unsigned 64-bit integers.

mxFUNCTION_CLASS

Identifies a function handle mxArray.

Description Various `mx*` calls require or return an `mxClassID` argument. `mxClassID` identifies the way in which the `mxArray` represents its data elements.

Examples See `explore.c` in the `mex` subdirectory of the `examples` directory.

See Also `mxGetClassID` , `mxCreateNumericArray`

mxClassIDFromClassName (Fortran)

Purpose	Identifier corresponding to class
Fortran Syntax	<pre>integer*4 mxClassIDFromClassName(classname) character*(*) classname</pre>
Arguments	<p>classname</p> <p>A character array specifying a MATLAB class name. Use one of the strings from the following table.</p>
Returns	A numeric identifier used internally by MATLAB software to represent the MATLAB class, classname. Returns unknown if classname is not a recognized MATLAB class.
Description	<p>Use mxClassIDFromClassName to obtain an identifier for any class that is recognized by MATLAB software. This function is most commonly used to provide a classid argument to mxCreateNumericArray and mxCreateNumericMatrix.</p> <p>Valid choices for classname are listed in the mxIsClass reference page.</p>
See Also	<code>mxGetClassName</code> , <code>mxCreateNumericArray</code> , <code>mxCreateNumericMatrix</code> , <code>mxIsClass</code>

Purpose	Flag specifying whether mxArray has imaginary components
C Syntax	<pre>typedef enum mxComplexity {mxREAL=0, mxCOMPLEX};</pre>
Constants	<p>mxREAL Identifies an mxArray with no imaginary components.</p> <p>mxCOMPLEX Identifies an mxArray with imaginary components.</p>
Description	Various mx* calls require an mxComplexity argument. You can set an mxComplex argument to either mxREAL or mxCOMPLEX.
Examples	See mxcalcsinglesubscript.c in the mx subdirectory of the examples directory.
See Also	mxCreateNumericArray, mxCreateDoubleMatrix, mxCreateSparse

mxCopyCharacterToPtr (Fortran)

Purpose Copy character values from Fortran array to pointer array

Fortran Syntax `mxCopyCharacterToPtr(y, px, n)`
character*(*) y
mwPointer px
mwSize n

Arguments

y	character Fortran array
px	Pointer to character or name array
n	Number of elements to copy

Description `mxCopyCharacterToPtr` copies n character values from the Fortran character array y into the MATLAB string array pointed to by px. This subroutine is essential for copying character data between MATLAB pointer arrays and ordinary Fortran character arrays.

See Also `mxCopyPtrToCharacter`, `mxCreateCharArray`, `mxCreateString`, `mxCreateCharMatrixFromStrings`

mxCopyComplex16ToPtr (Fortran)

Purpose	Copy COMPLEX*16 values from Fortran array to pointer array
Fortran Syntax	<pre>mxCopyComplex16ToPtr(y, pr, pi, n) complex*16 y(n) mwPointer pr, pi mwSize n</pre>
Arguments	<p>y COMPLEX*16 Fortran array</p> <p>pr Pointer to the real data of a double-precision MATLAB array</p> <p>pi Pointer to the imaginary data of a double-precision MATLAB array</p> <p>n Number of elements to copy</p>
Description	<p>mxCopyComplex16ToPtr copies n COMPLEX*16 values from the Fortran COMPLEX*16 array y into the MATLAB arrays pointed to by pr and pi. This subroutine is essential for use with Fortran compilers that do not support the %VAL construct in order to set up standard Fortran arrays for passing as arguments to the computation routine of a MEX-file.</p>
See Also	<p>mxCopyPtrToComplex16, mxCreateNumericArray, mxCreateNumericMatrix, mxGetData, mxGetImagData</p>

mxCopyComplex8ToPtr (Fortran)

Purpose	Copy COMPLEX*8 values from Fortran array to pointer array
Fortran Syntax	<pre>mxCopyComplex8ToPtr(y, pr, pi, n) complex*8 y(n) mwPointer pr, pi mwSize n</pre>
Arguments	<p>y COMPLEX*8 Fortran array</p> <p>pr Pointer to the real data of a single-precision MATLAB array</p> <p>pi Pointer to the imaginary data of a single-precision MATLAB array</p> <p>n Number of elements to copy</p>
Description	<p>mxCopyComplex8ToPtr copies n COMPLEX*8 values from the Fortran COMPLEX*8 array y into the MATLAB arrays pointed to by pr and pi. This subroutine is essential for use with Fortran compilers that do not support the %VAL construct in order to set up standard Fortran arrays for passing as arguments to the computation routine of a MEX-file.</p>
See Also	<p>mxCopyPtrToComplex8, mxCreateNumericArray, mxCreateNumericMatrix, mxGetData, mxGetImagData</p>

Purpose Copy INTEGER*1 values from Fortran array to pointer array

Fortran Syntax

```
mxCopyInteger1ToPtr(y, px, n)
integer*1 y(n)
mwPointer px
mwSize n
```

Arguments

y
INTEGER*1 Fortran array

px
Pointer to the real or imaginary data of the array

n
Number of elements to copy

Description mxCopyInteger1ToPtr copies n INTEGER*1 values from the Fortran INTEGER*1 array y into the MATLAB array pointed to by px, either a real or an imaginary array. This subroutine is essential for use with Fortran compilers that do not support the %VAL construct in order to set up standard Fortran arrays for passing as arguments to the computation routine of a MEX-file.

See Also mxCopyPtrToInteger1, mxCreateNumericArray, mxCreateNumericMatrix

mxCopyInteger2ToPtr (Fortran)

Purpose Copy INTEGER*2 values from Fortran array to pointer array

Fortran Syntax
mxCopyInteger2ToPtr(y, px, n)
integer*2 y(n)
mwPointer px
mwSize n

Arguments

y	INTEGER*2 Fortran array
px	Pointer to the real or imaginary data of the array
n	Number of elements to copy

Description mxCopyInteger2ToPtr copies n INTEGER*2 values from the Fortran INTEGER*2 array y into the MATLAB array pointed to by px, either a real or an imaginary array. This subroutine is essential for use with Fortran compilers that do not support the %VAL construct in order to set up standard Fortran arrays for passing as arguments to the computation routine of a MEX-file.

See Also mxCopyPtrToInteger2, mxCreateNumericArray, mxCreateNumericMatrix

Purpose Copy INTEGER*4 values from Fortran array to pointer array

Fortran Syntax

```
mxCopyInteger4ToPtr(y, px, n)
integer*4 y(n)
mwPointer px
mwSize n
```

Arguments

y
INTEGER*4 Fortran array

px
Pointer to the real or imaginary data of the array

n
Number of elements to copy

Description mxCopyInteger4ToPtr copies n INTEGER*4 values from the Fortran INTEGER*4 array y into the MATLAB array pointed to by px, either a real or an imaginary array. This subroutine is essential for use with Fortran compilers that do not support the %VAL construct in order to set up standard Fortran arrays for passing as arguments to the computation routine of a MEX-file.

See Also mxCopyPtrToInteger4, mxCreateNumericArray, mxCreateNumericMatrix

mxCopyPtrToCharacter (Fortran)

Purpose Copy character values from pointer array to Fortran array

Fortran Syntax `mxCopyPtrToCharacter(px, y, n)`
mwPointer px
character*(*) y
mwSize n

Arguments

px	Pointer to character or name array
y	character Fortran array
n	Number of elements to copy

Description `mxCopyPtrToCharacter` copies `n` character values from the MATLAB array pointed to by `px` into the Fortran character array `y`. This subroutine is essential for copying character data from MATLAB pointer arrays into ordinary Fortran character arrays.

Examples See `matdemo2.F` in the `eng_mat` subdirectory of the `examples` directory for a sample program that illustrates how to use this routine in a Fortran program.

See Also `mxCopyCharacterToPtr`, `mxCreateCharArray`, `mxCreateString`, `mxCreateCharMatrixFromStrings`

mxCopyPtrToComplex16 (Fortran)

Purpose	Copy COMPLEX*16 values from pointer array to Fortran array
Fortran Syntax	<pre>mxCopyPtrToComplex16(pr, pi, y, n) mwPointer pr, pi complex*16 y(n) mwSize n</pre>
Arguments	<p>pr Pointer to the real data of a double-precision MATLAB array</p> <p>pi Pointer to the imaginary data of a double-precision MATLAB array</p> <p>y COMPLEX*16 Fortran array</p> <p>n Number of elements to copy</p>
Description	<p>mxCopyPtrToComplex16 copies n COMPLEX*16 values from the MATLAB arrays pointed to by pr and pi into the Fortran COMPLEX*16 array y. This subroutine is essential for use with Fortran compilers that do not support the %VAL construct in order to set up standard Fortran arrays for passing as arguments to the computation routine of a MEX-file.</p>
See Also	<p>mxCopyComplex16ToPtr, mxCreateNumericArray, mxCreateNumericMatrix, mxGetData, mxGetImagData</p>

mxCopyPtrToComplex8 (Fortran)

Purpose	Copy COMPLEX*8 values from pointer array to Fortran array
Fortran Syntax	<pre>mxCopyPtrToComplex8(pr, pi, y, n) mwPointer pr, pi complex*8 y(n) mwSize n</pre>
Arguments	<p><code>pr</code> Pointer to the real data of a single-precision MATLAB array</p> <p><code>pi</code> Pointer to the imaginary data of a single-precision MATLAB array</p> <p><code>y</code> COMPLEX*8 Fortran array</p> <p><code>n</code> Number of elements to copy</p>
Description	<p><code>mxCopyPtrToComplex8</code> copies <code>n</code> COMPLEX*8 values from the MATLAB arrays pointed to by <code>pr</code> and <code>pi</code> into the Fortran COMPLEX*8 array <code>y</code>. This subroutine is essential for use with Fortran compilers that do not support the %VAL construct in order to set up standard Fortran arrays for passing as arguments to the computation routine of a MEX-file.</p>
See Also	<code>mxCopyComplex8ToPtr</code> , <code>mxCreateNumericArray</code> , <code>mxCreateNumericMatrix</code> , <code>mxGetData</code> , <code>mxGetImagData</code>

Purpose Copy INTEGER*1 values from pointer array to Fortran array

Fortran Syntax

```
mxCopyPtrToInteger1(px, y, n)
mwPointer px
integer*1 y(n)
mwSize n
```

Arguments

px
Pointer to the real or imaginary data of the array

y
INTEGER*1 Fortran array

n
Number of elements to copy

Description mxCopyPtrToInteger1 copies n INTEGER*1 values from the MATLAB array pointed to by px, either a real or imaginary array, into the Fortran INTEGER*1 array y. This subroutine is essential for use with Fortran compilers that do not support the %VAL construct in order to set up standard Fortran arrays for passing as arguments to the computation routine of a MEX-file.

See Also mxCopyInteger1ToPtr, mxCreateNumericArray, mxCreateNumericMatrix

mxCopyPtrToInteger2 (Fortran)

Purpose Copy INTEGER*2 values from pointer array to Fortran array

Fortran Syntax

```
mxCopyPtrToInteger2(px, y, n)
mwPointer px
integer*2 y(n)
mwSize n
```

Arguments

px	Pointer to the real or imaginary data of the array
y	INTEGER*2 Fortran array
n	Number of elements to copy

Description mxCopyPtrToInteger2 copies n INTEGER*2 values from the MATLAB array pointed to by px, either a real or an imaginary array, into the Fortran INTEGER*2 array y. This subroutine is essential for use with Fortran compilers that do not support the %VAL construct in order to set up standard Fortran arrays for passing as arguments to the computation routine of a MEX-file.

See Also mxCopyInteger2ToPtr, mxCreateNumericArray, mxCreateNumericMatrix

Purpose Copy INTEGER*4 values from pointer array to Fortran array

Fortran Syntax

```
mxCopyPtrToInteger4(px, y, n)
mwPointer px
integer*4 y(n)
mwSize n
```

Arguments

px Pointer to the real or imaginary data of the array

y INTEGER*4 Fortran array

n Number of elements to copy

Description mxCopyPtrToInteger4 copies n INTEGER*4 values from the MATLAB array pointed to by px, either a real or an imaginary array, into the Fortran INTEGER*4 array y. This subroutine is essential for use with Fortran compilers that do not support the %VAL construct in order to set up standard Fortran arrays for passing as arguments to the computation routine of a MEX-file.

See Also mxCopyInteger4ToPtr, mxCreateNumericArray, mxCreateNumericMatrix

mxCopyPtrToPtrArray (Fortran)

Purpose Copy pointer values from pointer array to Fortran array

Fortran Syntax
`mxCopyPtrToPtrArray(px, y, n)`
`mwPointer px`
`mwPointer y(n)`
`mwSize n`

Arguments

<code>px</code>	Pointer to pointer array
<code>y</code>	Fortran array of <code>mwPointer</code> values
<code>n</code>	Number of pointers to copy

Description `mxCopyPtrToPtrArray` copies `n` pointers from the MATLAB array pointed to by `px` into the Fortran array `y`. This subroutine is essential for copying the output of `matGetDir` into an array of pointers. After calling this function, each element of `y` contains a pointer to a string. You can convert these strings to Fortran character arrays by passing each element of `y` as the first argument to `mxCopyPtrToCharacter`.

Examples See `matdemo2.F` in the `eng_mat` subdirectory of the `examples` directory for a sample program that illustrates how to use this routine in a Fortran program.

See Also `matGetDir`, `mxCopyPtrToCharacter`

Purpose	Copy REAL*4 values from pointer array to Fortran array
Fortran Syntax	<pre>mxCopyPtrToReal4(px, y, n) mwPointer px real*4 y(n) mwSize n</pre>
Arguments	<p>px Pointer to the real or imaginary data of a single-precision MATLAB array</p> <p>y REAL*4 Fortran array</p> <p>n Number of elements to copy</p>
Description	<p>mxCopyPtrToReal4 copies n REAL*4 values from the MATLAB array pointed to by px, either a pr or pi array, into the Fortran REAL*4 array y. This subroutine is essential for use with Fortran compilers that do not support the %VAL construct in order to set up standard Fortran arrays for passing as arguments to the computation routine of a MEX-file.</p>
See Also	<p>mxCopyReal4ToPtr, mxCreateNumericArray, mxCreateNumericMatrix, mxGetData, mxGetImagData</p>

mxCopyPtrToReal8 (Fortran)

Purpose	Copy REAL*8 values from pointer array to Fortran array
Fortran Syntax	<pre>mxCopyPtrToReal8(px, y, n) mwPointer px real*8 y(n) mwSize n</pre>
Arguments	<p>px Pointer to the real or imaginary data of a double-precision MATLAB array</p> <p>y REAL*8 Fortran array</p> <p>n Number of elements to copy</p>
Description	mxCopyPtrToReal8 copies n REAL*8 values from the MATLAB array pointed to by px, either a pr or pi array, into the Fortran REAL*8 array y. This subroutine is essential for use with Fortran compilers that do not support the %VAL construct in order to set up standard Fortran arrays for passing as arguments to the computation routine of a MEX-file.
Examples	See fengdemo.F in the eng_mat subdirectory of the examples directory for a sample program that illustrates how to use this routine in a Fortran program.
See Also	mxCopyReal8ToPtr, mxCreateNumericArray, mxCreateNumericMatrix, mxGetData, mxGetImagData

Purpose	Copy REAL*4 values from Fortran array to pointer array
Fortran Syntax	<pre>mxCopyReal4ToPtr(y, px, n) real*4 y(n) mwPointer px mwSize n</pre>
Arguments	<p>y REAL*4 Fortran array</p> <p>px Pointer to the real or imaginary data of a single-precision MATLAB array</p> <p>n Number of elements to copy</p>
Description	mxCopyReal4ToPtr copies n REAL*4 values from the Fortran REAL*4 array y into the MATLAB array pointed to by px, either a pr or pi array. This subroutine is essential for use with Fortran compilers that do not support the %VAL construct in order to set up standard Fortran arrays for passing as arguments to the computation routine of a MEX-file.
See Also	mxCopyPtrToReal4, mxCreateNumericArray, mxCreateNumericMatrix, mxGetData, mxGetImagData

mxCopyReal8ToPtr (Fortran)

Purpose Copy REAL*8 values from Fortran array to pointer array

Fortran Syntax
mxCopyReal8ToPtr(y, px, n)
real*8 y(n)
mwPointer px
mwSize n

Arguments

y	REAL*8 Fortran array
px	Pointer to the real or imaginary data of a double-precision MATLAB array
n	Number of elements to copy

Description mxCopyReal8ToPtr copies n REAL*8 values from the Fortran REAL*8 array y into the MATLAB array pointed to by px, either a pr or pi array. This subroutine is essential for use with Fortran compilers that do not support the %VAL construct in order to set up standard Fortran arrays for passing as arguments to the computation routine of a MEX-file.

Examples See matdemo1.F and fengdemo.F in the eng_mat subdirectory of the examples directory for a sample program that illustrates how to use this routine in a Fortran program.

See Also mxCopyPtrToReal8, mxCreateNumericArray, mxCreateNumericMatrix, mxGetData, mxGetImagData

mxCreateCellArray (C and Fortran)

Purpose	Create unpopulated N-D cell mxArray
C Syntax	<pre>#include "matrix.h" mxArray *mxCreateCellArray(mwSize ndim, const mwSize *dims);</pre>
Fortran Syntax	<pre>mwPointer mxCreateCellArray(ndim, dims) mwSize ndim, dims</pre>
Arguments	<p><code>ndim</code> The desired number of dimensions in the created cell. For example, to create a three-dimensional cell mxArray, set <code>ndim</code> to 3.</p> <p><code>dims</code> The dimensions array. Each element in the dimensions array contains the size of the mxArray in that dimension. For example, in C, setting <code>dims[0]</code> to 5 and <code>dims[1]</code> to 7 establishes a 5-by-7 mxArray. In Fortran, setting <code>dims(1)</code> to 5 and <code>dims(2)</code> to 7 establishes a 5-by-7 mxArray. In most cases, there should be <code>ndim</code> elements in the <code>dims</code> array.</p>
Returns	A pointer to the created cell mxArray, if successful. If unsuccessful in a stand alone (non-MEX-file) application, <code>mxCreateCellArray</code> returns NULL in C (0 in Fortran). If unsuccessful in a MEX-file, the MEX-file terminates and control returns to the MATLAB prompt. The most common cause of failure is insufficient free heap space.
Description	<p>Use <code>mxCreateCellArray</code> to create a cell mxArray whose size is defined by <code>ndim</code> and <code>dims</code>. For example, in C, to establish a three-dimensional cell mxArray having dimensions 4-by-8-by-7, set:</p> <pre>ndim = 3; dims[0] = 4; dims[1] = 8; dims[2] = 7;</pre> <p>In Fortran, to establish a three-dimensional cell mxArray having dimensions 4-by-8-by-7, set:</p> <pre>ndim = 3;</pre>

mxCreateCellArray (C and Fortran)

```
dims(1) = 4; dims(2) = 8; dims(3) = 7;
```

The created cell mxArray is unpopulated; mxCreateCellArray initializes each cell to NULL. To put data into a cell, call mxSetCell.

Any trailing singleton dimensions specified in the dims argument are automatically removed from the resulting array. For example, if ndim equals 5 and dims equals [4 1 7 1 1], the resulting array is given the dimensions 4-by-1-by-7.

C Examples

See phonebook.c in the refbook subdirectory of the examples directory.

See Also

mxCreateCellMatrix, mxGetCell, mxSetCell, mxIsCell

mxCreateCellMatrix (C and Fortran)

Purpose	Create unpopulated 2-D cell mxArray
C Syntax	<pre>#include "matrix.h" mxArray *mxCreateCellMatrix(mwSize m, mwSize n);</pre>
Fortran Syntax	<pre>mwPointer mxCreateCellMatrix(m, n) mwSize m, n</pre>
Arguments	<p>m The desired number of rows</p> <p>n The desired number of columns</p>
Returns	A pointer to the created cell mxArray, if successful. If unsuccessful in a stand alone (non-MEX-file) application, mxCreateCellMatrix returns NULL in C (0 in Fortran). If unsuccessful in a MEX-file, the MEX-file terminates and control returns to the MATLAB prompt. Insufficient free heap space is the only reason for mxCreateCellMatrix to be unsuccessful.
Description	<p>Use mxCreateCellMatrix to create an m-by-n two-dimensional cell mxArray. The created cell mxArray is unpopulated; mxCreateCellMatrix initializes each cell to NULL in C (0 in Fortran). To put data into cells, call mxSetCell.</p> <p>mxCreateCellMatrix is identical to mxCreateCellArray except that mxCreateCellMatrix can create two-dimensional mxArrays only, but mxCreateCellArray can create mxArrays having any number of dimensions greater than 1.</p>
C Examples	See mxcreatecellmatrix.c in the mx subdirectory of the examples directory.
See Also	mxCreateCellArray

mxCreateCharArray (C and Fortran)

Purpose	Create unpopulated N-D string mxArray
C Syntax	<pre>#include "matrix.h" mxArray *mxCreateCharArray(mwSize ndim, const mwSize *dims);</pre>
Fortran Syntax	<pre>mwPointer mxCreateCharArray(ndim, dims) mwSize ndim, dims</pre>
Arguments	<p>ndim The desired number of dimensions in the string mxArray. You must specify a positive number. If you specify 0, 1, or 2, mxCreateCharArray creates a two-dimensional mxArray.</p> <p>dims The dimensions array. Each element in the dimensions array contains the size of the array in that dimension. For example, in C, setting <code>dims[0]</code> to 5 and <code>dims[1]</code> to 7 establishes a 5-by-7 mxArray. In Fortran, setting <code>dims(1)</code> to 5 and <code>dims(2)</code> to 7 establishes a 5-by-7 character mxArray. The <code>dims</code> array must have at least <code>ndim</code> elements.</p>
Returns	A pointer to the created string mxArray, if successful. If unsuccessful in a stand alone (non-MEX-file) application, mxCreateCharArray returns NULL in C (0 in Fortran). If unsuccessful in a MEX-file, the MEX-file terminates and control returns to the MATLAB prompt. Insufficient free heap space is the only reason for mxCreateCharArray to be unsuccessful.
Description	<p>Call mxCreateCharArray to create an N-dimensional string mxArray. The created mxArray is unpopulated; that is, mxCreateCharArray initializes each cell to NULL in C (0 in Fortran).</p> <p>Any trailing singleton dimensions specified in the <code>dims</code> argument are automatically removed from the resulting array. For example, if <code>ndim</code> equals 5 and <code>dims</code> equals [4 1 7 1 1], the resulting array is given the dimensions 4-by-1-by-7.</p>

mxCreateCharArray (C and Fortran)

C Examples

See `mxcreatecharmatrixfromstr.c` in the `mx` subdirectory of the `examples` directory.

See Also

`mxCreateCharMatrixFromStrings`, `mxCreateString`

mxCreateCharMatrixFromStrings (C and Fortran)

Purpose	Create populated 2-D string mxArray
C Syntax	<pre>#include "matrix.h" mxArray *mxCreateCharMatrixFromStrings(mwSize m, const char **str);</pre>
Fortran Syntax	<pre>mwPointer mxCreateCharMatrixFromStrings(m, str) mwSize m character*(*) str(m)</pre>
Arguments	<p>m The desired number of rows in the created string mxArray. The value you specify for m should equal the number of strings in str.</p> <p>str In C, an array of strings containing at least m strings. In Fortran, a character*n array of size m, where each element of the array is n bytes.</p>
Returns	A pointer to the created string mxArray, if successful. If unsuccessful in a stand alone (non-MEX-file) application, mxCreateCharMatrixFromStrings returns NULL in C (0 in Fortran). If unsuccessful in a MEX-file, the MEX-file terminates and control returns to the MATLAB prompt. Insufficient free heap space is the primary reason for mxCreateCharMatrixFromStrings to be unsuccessful. Another possible reason for failure is that str contains fewer than m strings.
Description	<p>Use mxCreateCharMatrixFromStrings to create a two-dimensional string mxArray, where each row is initialized to a string from str. In C, the created mxArray has dimensions m-by-max, where max is the length of the longest string in str. In Fortran, the created mxArray has dimensions m-by-n, where n is the number of characters in str(i).</p> <p>Note that string mxArrays represent their data elements as mxChar rather than as C char.</p>

mxCreateCharMatrixFromStrings (C and Fortran)

C Examples

See `mxcreatecharmatrixfromstr.c` in the `mx` subdirectory of the `examples` directory.

See Also

`mxCreateCharArray`, `mxCreateString`, `mxGetString`

mxCreateDoubleMatrix (C and Fortran)

Purpose	Create 2-D, double-precision, floating-point mxArray initialized to 0
C Syntax	<pre>#include "matrix.h" mxArray *mxCreateDoubleMatrix(mwSize m, mwSize n, mxComplexity ComplexFlag);</pre>
Fortran Syntax	<pre>mwPointer mxCreateDoubleMatrix(m, n, ComplexFlag) mwSize m, n integer*4 ComplexFlag</pre>
Arguments	<p>m The desired number of rows</p> <p>n The desired number of columns</p> <p>ComplexFlag Specify either mxREAL or mxCOMPLEX. If the data you plan to put into the mxArray has no imaginary components, specify mxREAL in C (0 in Fortran). If the data has some imaginary components, specify mxCOMPLEX in C (1 in Fortran).</p>
Returns	A pointer to the created mxArray, if successful. If unsuccessful in a stand alone (non-MEX-file) application, mxCreateDoubleMatrix returns NULL in C (0 in Fortran). If unsuccessful in a MEX-file, the MEX-file terminates and control returns to the MATLAB prompt. mxCreateDoubleMatrix is unsuccessful when there is not enough free heap space to create the mxArray.
Description	<p>Use mxCreateDoubleMatrix to create an m-by-n mxArray. mxCreateDoubleMatrix initializes each element in the pr array to 0. If you set ComplexFlag to mxCOMPLEX in C (1 in Fortran), mxCreateDoubleMatrix also initializes each element in the pi array to 0.</p> <p>If you set ComplexFlag to mxREAL in C (0 in Fortran), mxCreateDoubleMatrix allocates enough memory to hold m-by-n real elements. If you set ComplexFlag to mxCOMPLEX in C (1 in Fortran),</p>

mxCreateDoubleMatrix (C and Fortran)

`mxCreateDoubleMatrix` allocates enough memory to hold m-by-n real elements and m-by-n imaginary elements.

Call `mxDestroyArray` when you finish using the `mxArray`.

`mxDestroyArray` deallocates the `mxArray` and its associated real and complex elements.

C Examples

See `convec.c`, `findnz.c`, `sincall.c`, `timestwo.c`, `timestwoalt.c`, and `xtimesy.c` in the `refbook` subdirectory of the `examples` directory.

See Also

`mxCreateNumericArray`

mxCreateDoubleScalar (C and Fortran)

Purpose Create scalar, double-precision array initialized to specified value

C Syntax

```
#include "matrix.h"
mxArray *mxCreateDoubleScalar(double value);
```

Fortran Syntax

```
mwPointer mxCreateDoubleScalar(value)
real*8 value
```

Arguments value
The desired value to which you want to initialize the array

Returns A pointer to the created mxArray, if successful. mxCreateDoubleScalar is unsuccessful if there is not enough free heap space to create the mxArray. If mxCreateDoubleScalar is unsuccessful in a MEX-file, the MEX-file prints an “Out of Memory” message, terminates, and control returns to the MATLAB prompt. If mxCreateDoubleScalar is unsuccessful in a stand alone (non-MEX-file) application, mxCreateDoubleScalar returns NULL in C (0 in Fortran).

Description Call mxCreateDoubleScalar to create a scalar double mxArray. mxCreateDoubleScalar is a convenience function that can be used in place of the following C code:

```
pa = mxCreateDoubleMatrix(1, 1, mxREAL);
*mxGetPr(pa) = value;
```

mxCreateDoubleScalar can be used in place of the following Fortran code:

```
pm = mxCreateDoubleMatrix(1, 1, 0)
mxCopyReal8ToPtr(value, mxGetPr(pm), 1)
```

When you finish using the mxArray, call mxDestroyArray to destroy it.

See Also mxGetPr, mxCreateDoubleMatrix

Purpose	Create N-D logical mxArray initialized to false
C Syntax	<pre>#include "matrix.h" mxArray *mxCreateLogicalArray(mwSize ndim, const mwSize *dims);</pre>
Arguments	<p>ndim Number of dimensions. If you specify a value for <code>ndim</code> that is less than 2, <code>mxCreateLogicalArray</code> automatically sets the number of dimensions to 2.</p> <p>dims The dimensions array. Each element in the dimensions array contains the size of the array in that dimension. For example, setting <code>dims[0]</code> to 5 and <code>dims[1]</code> to 7 establishes a 5-by-7 mxArray. There should be <code>ndim</code> elements in the <code>dims</code> array.</p>
Returns	A pointer to the created mxArray, if successful. If unsuccessful in a stand alone (non-MEX-file) application, <code>mxCreateLogicalArray</code> returns NULL. If unsuccessful in a MEX-file, the MEX-file terminates and control returns to the MATLAB prompt. <code>mxCreateLogicalArray</code> is unsuccessful when there is not enough free heap space to create the mxArray.
Description	<p>Call <code>mxCreateLogicalArray</code> to create an N-dimensional mxArray of <code>mxLogical</code> elements. After creating the mxArray, <code>mxCreateLogicalArray</code> initializes all its elements to logical 0. <code>mxCreateLogicalArray</code> differs from <code>mxCreateLogicalMatrix</code> in that the latter can create two-dimensional arrays only.</p> <p><code>mxCreateLogicalArray</code> allocates dynamic memory to store the created mxArray. When you finish with the created mxArray, call <code>mxDestroyArray</code> to deallocate its memory.</p> <p>Any trailing singleton dimensions specified in the <code>dims</code> argument are automatically removed from the resulting array. For example, if <code>ndim</code> equals 5 and <code>dims</code> equals [4 1 7 1 1], the resulting array is given the dimensions 4-by-1-by-7.</p>

mxCreateLogicalArray (C)

See Also

`mxCreateLogicalMatrix`, `mxCreateSparseLogicalMatrix`,
`mxCreateLogicalScalar`

Purpose	Create 2-D, logical mxArray initialized to false
C Syntax	<pre>#include "matrix.h" mxArray *mxCreateLogicalMatrix(mwSize m, mwSize n);</pre>
Arguments	<p>m The desired number of rows</p> <p>n The desired number of columns</p>
Returns	A pointer to the created mxArray, if successful. If unsuccessful in a stand alone (non-MEX-file) application, mxCreateLogicalMatrix returns NULL. If unsuccessful in a MEX-file, the MEX-file terminates and control returns to the MATLAB prompt. mxCreateLogicalMatrix is unsuccessful when there is not enough free heap space to create the mxArray.
Description	<p>Use mxCreateLogicalMatrix to create an m-by-n mxArray of mxLogical elements. mxCreateLogicalMatrix initializes each element in the array to logical 0.</p> <p>Call mxDestroyArray when you finish using the mxArray. mxDestroyArray deallocates the mxArray.</p>
See Also	mxCreateLogicalArray, mxCreateSparseLogicalMatrix, mxCreateLogicalScalar

mxCreateLogicalScalar (C)

Purpose Create scalar, logical mxArray

C Syntax

```
#include "matrix.h"
mxArray *mxCreateLogicalScalar(mxLogical value);
```

Arguments value
The desired logical value to which you want to initialize the array

Returns A pointer to the created mxArray, if successful. mxCreateLogicalScalar is unsuccessful if there is not enough free heap space to create the mxArray. If mxCreateLogicalScalar is unsuccessful in a MEX-file, the MEX-file prints an “Out of Memory” message, terminates, and returns control to the MATLAB prompt. If mxCreateLogicalScalar is unsuccessful in a stand alone (non-MEX-file) application, the function returns NULL.

Description Call mxCreateLogicalScalar to create a scalar logical mxArray. mxCreateLogicalScalar is a convenience function that can be used in place of the following code:

```
pa = mxCreateLogicalMatrix(1, 1);
*mxGetLogicals(pa) = value;
```

When you finish using the mxArray, call mxDestroyArray to destroy it.

See Also mxCreateLogicalArray, mxCreateLogicalMatrix, mxIsLogicalScalar, mxIsLogicalScalarTrue, mxGetLogicals, mxDestroyArray

mxCreateNumericArray (C and Fortran)

Purpose	Create unpopulated N-D numeric mxArray
C Syntax	<pre>#include "matrix.h" mxArray *mxCreateNumericArray(mwSize ndim, const mwSize *dims, mxClassID classid, mxComplexity ComplexFlag);</pre>
Fortran Syntax	<pre>mwPointer mxCreateNumericArray(ndim, dims, classid, ComplexFlag) mwSize ndim, dims integer*4 classid, ComplexFlag</pre>
Arguments	<p>ndim Number of dimensions. If you specify a value for <code>ndim</code> that is less than 2, <code>mxCreateNumericArray</code> automatically sets the number of dimensions to 2.</p> <p>dims The dimensions array. Each element in the dimensions array contains the size of the array in that dimension. For example, in C, setting <code>dims[0]</code> to 5 and <code>dims[1]</code> to 7 establishes a 5-by-7 mxArray. In Fortran, setting <code>dims(1)</code> to 5 and <code>dims(2)</code> to 7 establishes a 5-by-7 mxArray. In most cases, there should be <code>ndim</code> elements in the <code>dims</code> array.</p> <p>classid An identifier for the class of the array, which determines the way the numerical data is represented in memory. For example, specifying <code>mxINT16_CLASS</code> in C causes each piece of numerical data in the mxArray to be represented as a 16-bit signed integer. In Fortran, use the function <code>mxClassIDFromClassname</code> to derive the <code>classid</code> value from a MATLAB class name. See the Description section for more information.</p> <p>ComplexFlag If the data you plan to put into the mxArray has no imaginary components, specify <code>mxREAL</code> in C (0 in Fortran). If the data has some imaginary components, specify <code>mxCOMPLEX</code> in C (1 in Fortran).</p>

mxCreateNumericArray (C and Fortran)

Returns

A pointer to the created `mxArray`, if successful. If unsuccessful in a stand alone (non-MEX-file) application, `mxCreateNumericArray` returns NULL in C (0 in Fortran). If unsuccessful in a MEX-file, the MEX-file terminates and control returns to the MATLAB prompt. `mxCreateNumericArray` is unsuccessful when there is not enough free heap space to create the `mxArray`.

Description

Call `mxCreateNumericArray` to create an N-dimensional `mxArray` in which all data elements have the numeric data type specified by `classid`. After creating the `mxArray`, `mxCreateNumericArray` initializes all its real data elements to 0. If `ComplexFlag` equals `mxCOMPLEX` in C (1 in Fortran), `mxCreateNumericArray` also initializes all its imaginary data elements to 0. `mxCreateNumericArray` differs from `mxCreateDoubleMatrix` in two important respects:

- All data elements in `mxCreateDoubleMatrix` are double-precision, floating-point numbers. The data elements in `mxCreateNumericArray` could be any numerical type, including different integer precisions.
- `mxCreateDoubleMatrix` can create two-dimensional arrays only; `mxCreateNumericArray` can create arrays of two or more dimensions.

`mxCreateNumericArray` allocates dynamic memory to store the created `mxArray`. When you finish with the created `mxArray`, call `mxDestroyArray` to deallocate its memory.

Any trailing singleton dimensions specified in the `dims` argument are automatically removed from the resulting array. For example, if `ndim` equals 5 and `dims` equals [4 1 7 1 1], the resulting array is given the dimensions 4-by-1-by-7.

The following table shows the C `classid` values and the Fortran data types that are equivalent to MATLAB classes.

MATLAB Class Name	C classid Value	Fortran Type
int8	mxINT8_CLASS	BYTE

mxCreateNumericArray (C and Fortran)

MATLAB Class Name	C classid Value	Fortran Type
uint8	mxUINT8_CLASS	
int16	mxINT16_CLASS	INTEGER*2
uint16	mxUINT16_CLASS	
int32	mxINT32_CLASS	INTEGER*4
uint32	mxUINT32_CLASS	
int64	mxINT64_CLASS	INTEGER*8
uint64	mxUINT64_CLASS	
single	mxSINGLE_CLASS	REAL*4
double	mxDOUBLE_CLASS	REAL*8
single, with imaginary components	mxSINGLE_CLASS	COMPLEX*8
double, with imaginary components	mxDOUBLE_CLASS	COMPLEX*16

C Examples

See `phonebook.c` and `doubleelement.c` in the `refbook` subdirectory of the `examples` directory. For an additional example, see `mxisfinite.c` in the `mx` subdirectory of the `examples` directory.

Fortran Examples

To create a 4-by-4-by-2 array of REAL*8 elements having no imaginary components, use:

```
C      Create 4x4x2 mxArray of REAL*8
      data dims / 4, 4, 2 /
      mxCreateNumericArray(3, dims,
+                          mxClassIDFromClassName('double'), 0)
```

See Also

`mxClassId`, `mxClassIdFromClassName`, `mxComplexity`,
`mxCreateNumericMatrix`

mxCreateNumericMatrix (C and Fortran)

Purpose Create numeric matrix and initialize data elements to 0

C Syntax

```
#include "matrix.h"
mxArray *mxCreateNumericMatrix(mwSize m, mwSize n,
    mxClassID classid, mxComplexity ComplexFlag);
```

Fortran Syntax

```
mwPointer mxCreateNumericMatrix(m, n, classid,
    ComplexFlag)
mwSize m, n
integer*4 classid, ComplexFlag
```

Arguments

m
The desired number of rows.

n
The desired number of columns.

classid
An identifier for the class of the array, which determines the way the numerical data is represented in memory. For example, specifying `mxINT16_CLASS` in C causes each piece of numerical data in the `mxArray` to be represented as a 16-bit signed integer. In Fortran, use the function `mxClassIDFromClassname` to derive the `classid` value from a MATLAB class name. See the Description section for more information.

ComplexFlag
If the data you plan to put into the `mxArray` has no imaginary components, specify `mxREAL` in C (0 in Fortran). If the data has some imaginary components, specify `mxCOMPLEX` in C (1 in Fortran).

Returns A pointer to the created `mxArray`, if successful. `mxCreateNumericMatrix` is unsuccessful if there is not enough free heap space to create the `mxArray`. If `mxCreateNumericMatrix` is unsuccessful in a MEX-file, the MEX-file prints an “Out of Memory” message, terminates, and control returns to the MATLAB prompt. If `mxCreateNumericMatrix`

mxCreateNumericMatrix (C and Fortran)

is unsuccessful in a stand alone (non-MEX-file) application, mxCreateNumericMatrix returns NULL in C (0 in Fortran).

Description

Call mxCreateNumericMatrix to create a 2-D mxArray in which all data elements have the numeric data type specified by classid. After creating the mxArray, mxCreateNumericMatrix initializes all its real data elements to 0. If ComplexFlag equals mxCOMPLEX in C (1 in Fortran), mxCreateNumericMatrix also initializes all its imaginary data elements to 0. mxCreateNumericMatrix allocates dynamic memory to store the created mxArray. When you finish using the mxArray, call mxDestroyArray to destroy it.

The following table shows the C classid values and the Fortran data types that are equivalent to MATLAB classes.

MATLAB Class Name	C classid Value	Fortran Type
int8	mxINT8_CLASS	BYTE
uint8	mxUINT8_CLASS	
int16	mxINT16_CLASS	INTEGER*2
uint16	mxUINT16_CLASS	
int32	mxINT32_CLASS	INTEGER*4
uint32	mxUINT32_CLASS	
int64	mxINT64_CLASS	INTEGER*8
uint64	mxUINT64_CLASS	
single	mxSINGLE_CLASS	REAL*4
double	mxDOUBLE_CLASS	REAL*8

mxCreateNumericMatrix (C and Fortran)

MATLAB Class Name	C classid Value	Fortran Type
single, with imaginary components	mxSINGLE_CLASS	COMPLEX*8
double, with imaginary components	mxDOUBLE_CLASS	COMPLEX*16

Fortran Examples

To create a 4-by-3 matrix of REAL*4 elements having no imaginary components, use:

```
C      Create 4x3 mxArray of REAL*4
      mxCreateNumericMatrix(4, 3,
+                          mxClassIDFromClassName('single'), 0)
```

See Also

`mxClassId`, `mxClassIdFromClassName`, `mxComplexity`,
`mxCreateNumericArray`

mxCreateSparse (C and Fortran)

Purpose	Create 2-D unpopulated sparse mxArray
C Syntax	<pre>#include "matrix.h" mxArray *mxCreateSparse(mwSize m, mwSize n, mwSize nzmax, mxComplexity ComplexFlag);</pre>
Fortran Syntax	<pre>mwPointer mxCreateSparse(m, n, nzmax, ComplexFlag) mwSize m, n, nzmax integer*4 ComplexFlag</pre>
Arguments	<p>m The desired number of rows</p> <p>n The desired number of columns</p> <p>nzmax The number of elements that mxCreateSparse should allocate to hold the pr, ir, and, if ComplexFlag is mxCOMPLEX in C (1 in Fortran), pi arrays. Set the value of nzmax to be greater than or equal to the number of nonzero elements you plan to put into the mxArray, but make sure that nzmax is less than or equal to m*n.</p> <p>ComplexFlag If the mxArray you are creating is to contain imaginary data, set ComplexFlag to mxCOMPLEX in C (1 in Fortran). Otherwise, set ComplexFlag to mxREAL in C (0 in Fortran).</p>
Returns	A pointer to the created sparse double mxArray if successful, and NULL in C (0 in Fortran) otherwise. The most likely reason for failure is insufficient free heap space. If that happens, try reducing nzmax, m, or n.
Description	Call mxCreateSparse to create an unpopulated sparse double mxArray. The returned sparse mxArray contains no sparse information and cannot be passed as an argument to any MATLAB sparse functions. To make the returned sparse mxArray useful, you must initialize the pr, ir, jc, and (if it exists) pi arrays.

mxCreateSparse (C and Fortran)

mxCreateSparse allocates space for

- A `pr` array of length `nzmax`.
- A `pi` array of length `nzmax`, but only if `ComplexFlag` is `mxCOMPLEX` in C (1 in Fortran).
- An `ir` array of length `nzmax`.
- A `jc` array of length `n+1`.

When you finish using the sparse `mxArray`, call `mxDestroyArray` to reclaim all its heap space.

C Examples

See `fulltosparse.c` in the `refbook` subdirectory of the `examples` directory.

See Also

`mxDestroyArray`, `mxSetNzmax`, `mxSetPr`, `mxSetPi`, `mxSetIr`, `mxSetJc`, `mxComplexity`

Purpose	Create unpopulated 2-D, sparse, logical mxArray
C Syntax	<pre>#include "matrix.h" mxArray *mxCreateSparseLogicalMatrix(mwSize m, mwSize n, mwSize nzmax);</pre>
Arguments	<p>m The desired number of rows</p> <p>n The desired number of columns</p> <p>nzmax The number of elements that mxCreateSparseLogicalMatrix should allocate to hold the data. Set the value of nzmax to be greater than or equal to the number of nonzero elements you plan to put into the mxArray, but make sure that nzmax is less than or equal to m*n.</p>
Returns	A pointer to the created mxArray, if successful. If unsuccessful in a stand alone (non-MEX-file) application, mxCreateSparseLogicalMatrix returns NULL. If unsuccessful in a MEX-file, the MEX-file terminates and control returns to the MATLAB prompt. mxCreateSparseLogicalMatrix is unsuccessful when there is not enough free heap space to create the mxArray.
Description	<p>Use mxCreateSparseLogicalMatrix to create an m-by-n mxArray of mxLogical elements. mxCreateSparseLogicalMatrix initializes each element in the array to logical 0.</p> <p>Call mxDestroyArray when you finish using the mxArray. mxDestroyArray deallocates the mxArray and its elements.</p>
See Also	<code>mxCreateLogicalArray</code> , <code>mxCreateLogicalMatrix</code> , <code>mxCreateLogicalScalar</code> , <code>mxCreateSparse</code> , <code>mxIsLogical</code>

mxCreateString (C and Fortran)

Purpose	Create 1-by-N string mxArray initialized to specified string
C Syntax	<pre>#include "matrix.h" mxArray *mxCreateString(const char *str);</pre>
Fortran Syntax	<pre>mwPointer mxCreateString(str) character*(*) str</pre>
Arguments	<p>str</p> <p>The string that is to serve as the mxArray's initial data</p>
Returns	A pointer to the created string mxArray if successful, and NULL in C (0 in Fortran) otherwise. The most likely cause of failure is insufficient free heap space.
Description	<p>Use mxCreateString to create a string mxArray initialized to str. Many MATLAB functions (for example, strcmp and upper) require string array inputs.</p> <p>Free the string mxArray when you are finished using it. To free a string mxArray, call mxDestroyArray.</p>
C Examples	<p>See revord.c in the refbook subdirectory of the examples directory.</p> <p>For additional examples, see mxcreatestructarray.c and mxisclass.c in the mx subdirectory of the examples directory.</p>
Fortran Examples	See matdemo1.F in the eng_mat subdirectory of the examples directory for a sample program that illustrates how to use this routine in a Fortran program.
See Also	mxCreateCharMatrixFromStrings, mxCreateCharArray

mxCreateStructArray (C and Fortran)

Purpose

Create unpopulated N-D structure mxArray

C Syntax

```
#include "matrix.h"
mxArray *mxCreateStructArray(mwSize ndim, const mwSize *dims,
    int nfields, const char **fieldnames);
```

Fortran Syntax

```
mwPointer mxCreateStructArray(ndim, dims, nfields,
    fieldnames)
mwSize ndim, dims
integer*4 nfields
character*(*) fieldnames(nfields)
```

Arguments

`ndim`

Number of dimensions. If you set `ndim` to be less than 2, `mxCreateStructArray` creates a two-dimensional mxArray.

`dims`

The dimensions array. Each element in the dimensions array contains the size of the array in that dimension. For example, in C, setting `dims[0]` to 5 and `dims[1]` to 7 establishes a 5-by-7 mxArray. In Fortran, setting `dims(1)` to 5 and `dims(2)` to 7 establishes a 5-by-7 mxArray. Typically, the `dims` array should have `ndim` elements.

`nfields`

The desired number of fields in each element

`fieldnames`

The desired list of field names

Each structure field name must begin with a letter and is case sensitive. The rest of the name may contain letters, numerals, and underscore characters. Use the `namelengthmax` function to determine the maximum length of a field name.

mxCreateStructArray (C and Fortran)

Returns

A pointer to the created structure `mxAArray` if successful, and `NULL` in C (0 in Fortran) otherwise. The most likely cause of failure is insufficient heap space to hold the returned `mxAArray`.

Description

Call `mxCreateStructArray` to create an unpopulated structure `mxAArray`. Each element of a structure `mxAArray` contains the same number of fields (specified in `nfields`). Each field has a name; the list of names is specified in `fieldnames`. A MATLAB structure `mxAArray` is conceptually identical to an array of `structs` in the C language.

Each field holds one `mxAArray` pointer. `mxCreateStructArray` initializes each field to `NULL` in C (0 in Fortran). Call `mxSetField` or `mxSetFieldByNumber` to place a non-`NULL` `mxAArray` pointer in a field.

When you finish using the returned structure `mxAArray`, call `mxDestroyArray` to reclaim its space.

Any trailing singleton dimensions specified in the `dims` argument are automatically removed from the resulting array. For example, if `ndim` equals 5 and `dims` equals [4 1 7 1 1], the resulting array is given the dimensions 4-by-1-by-7.

C Examples

See `mxcreatestructarray.c` in the `mx` subdirectory of the `examples` directory.

See Also

`mxDestroyArray`, `mxAddField`, `mxRemoveField`, `mxSetField`, `mxSetFieldByNumber`

mxCreateStructMatrix (C and Fortran)

Purpose	Create unpopulated 2-D structure mxArray
C Syntax	<pre>#include "matrix.h" mxArray *mxCreateStructMatrix(mwSize m, mwSize n, int nfields, const char **fieldnames);</pre>
Fortran Syntax	<pre>mwPointer mxCreateStructMatrix(m, n, nfields, fieldnames) mwSize m, n integer*4 nfields character*(*) fieldnames(nfields)</pre>
Arguments	<p>m The desired number of rows. This must be a positive integer.</p> <p>n The desired number of columns. This must be a positive integer.</p> <p>nfields The desired number of fields in each element.</p> <p>fieldnames The desired list of field names.</p> <p>Each structure field name must begin with a letter and is case sensitive. The rest of the name may contain letters, numerals, and underscore characters. Use the <code>namelengthmax</code> function to determine the maximum length of a field name.</p>
Returns	A pointer to the created structure mxArray if successful, and NULL in C (0 in Fortran) otherwise. The most likely cause of failure is insufficient heap space to hold the returned mxArray.
Description	<code>mxCreateStructMatrix</code> and <code>mxCreateStructArray</code> are almost identical. The only difference is that <code>mxCreateStructMatrix</code> can create only two-dimensional mxArrays, while <code>mxCreateStructArray</code> can create mxArrays having two or more dimensions.

mxCreateStructMatrix (C and Fortran)

C Examples

See `phonebook.c` in the `refbook` subdirectory of the `examples` directory.

See Also

`mxCreateStructArray`

mxDestroyArray (C and Fortran)

Purpose	Free dynamic memory allocated by mxCreate* functions
C Syntax	<pre>#include "matrix.h" void mxDestroyArray(mxArray *pm);</pre>
Fortran Syntax	<pre>mxDestroyArray(pm) mwPointer pm</pre>
Arguments	<p>pm</p> <p>Pointer to the mxArray you want to free</p>
Description	<p>mxDestroyArray deallocates the memory occupied by the specified mxArray. mxDestroyArray not only deallocates the memory occupied by the mxArray's characteristics fields (such as m and n), but also deallocates all the mxArray's associated data arrays, such as pr and pi for complex arrays, ir and jc for sparse arrays, fields of structure arrays, and cells of cell arrays. Do not call mxDestroyArray on an mxArray you are returning on the left-hand side.</p>
C Examples	<p>See sincall.c in the refbook subdirectory of the examples directory.</p> <p>Additional examples:</p> <ul style="list-style-type: none">• mexcallmatlab.c and mexgetarray.c in the mex subdirectory of the examples directory• mxisclass.c in the mx subdirectory of the examples directory
See Also	<p>mxCalloc, mxMalloc, mxFree, mexMakeArrayPersistent, mexMakeMemoryPersistent</p>

mxDuplicateArray (C and Fortran)

Purpose Make deep copy of array

C Syntax

```
#include "matrix.h"
mxArray *mxDuplicateArray(const mxArray *in);
```

Fortran Syntax

```
mwPointer mxDuplicateArray(in)
mwPointer in
```

Arguments `in`
Pointer to the mxArray you want to copy

Returns Pointer to a copy of the array.

Description `mxDuplicateArray` makes a deep copy of an array, and returns a pointer to the copy. A deep copy refers to a copy in which all levels of data are copied. For example, a deep copy of a cell array copies each cell and the contents of each cell (if any), and so on.

C Examples See

- `mexget.c` in the `mex` subdirectory of the `examples` directory
- `phonebook.c` in the `refbook` subdirectory of the `examples` directory

For additional examples, see `mxcreatecellmatrix.c`, `mxgetinf.c`, and `mxsetnzmax.c` in the `mx` subdirectory of the `examples` directory.

Purpose	Free dynamic memory allocated by <code>mxMalloc</code> , <code>mxMalloc</code> , or <code>mxRealloc</code>
C Syntax	<pre>#include "matrix.h" void mxFree(void *ptr);</pre>
Fortran Syntax	<pre>mxFree(ptr) mwPointer ptr</pre>
Arguments	<p><code>ptr</code></p> <p>Pointer to the beginning of any memory parcel allocated by <code>mxMalloc</code>, <code>mxMalloc</code>, or <code>mxRealloc</code>.</p>
Description	<p><code>mxFree</code> deallocates heap space using the MATLAB memory management facility. This ensures correct memory management in error and abort (Ctrl+C) conditions.</p> <p>To deallocate heap space, MATLAB applications in C should always call <code>mxFree</code> rather than the ANSI C <code>free</code> function.</p> <p>The memory management facility maintains a list of all memory allocated by <code>mxMalloc</code>, <code>mxMalloc</code>, and <code>mxRealloc</code>. The memory management facility automatically deallocates all of a MEX-file's managed parcels when the MEX-file completes and control returns to the MATLAB prompt.</p> <p>When <code>mxFree</code> appears in a stand alone MATLAB application, <code>mxFree</code> simply deallocates the contiguous heap space that begins at address <code>ptr</code>. In a MEX-file, <code>mxFree</code> also removes the memory parcel from the memory management facility's list of memory parcels.</p> <p>In a MEX-file, your use of <code>mxFree</code> depends on whether the specified memory parcel is persistent or nonpersistent. By default, memory parcels created by <code>mxMalloc</code>, <code>mxMalloc</code>, and <code>mxRealloc</code> are nonpersistent. The memory management facility automatically frees all nonpersistent memory whenever a MEX-file completes. Thus, even if you do not call <code>mxFree</code>, MATLAB takes care of freeing the memory for you. Nevertheless, it is good programming practice to deallocate</p>

mxFree (C and Fortran)

memory as soon as you are through using it. Doing so generally makes the entire system run more efficiently.

If an application calls `mexMakeMemoryPersistent`, the specified memory parcel becomes persistent. When a MEX-file completes, the memory management facility does not free persistent memory parcels. Therefore, the only way to free a persistent memory parcel is to call `mxFree`. Typically, MEX-files call `mexAtExit` to register a cleanup handler. The cleanup handler calls `mxFree`.

C Examples

See `mxcalcsinglesubscript.c` in the `mx` subdirectory of the examples directory.

Additional examples:

- `phonebook.c` in the `refbook` subdirectory of the examples directory
- `explore.c` and `mexatexit.c` in the `mex` subdirectory of the examples directory
- `mxcreatecharmatrixfromstr.c`, `mxisfinite.c`, `mxmalloc.c`, and `mxsetdimensions.c` in the `mx` subdirectory of the examples directory

See Also

`mexAtExit`, `mexMakeArrayPersistent`, `mexMakeMemoryPersistent`, `mxCalloc`, `mxDestroyArray`, `mxMalloc`, `mxRealloc`

Purpose Get contents of mxArray cell

C Syntax

```
#include "matrix.h"
mxArray *mxGetCell(const mxArray *pm, mwIndex index);
```

Fortran Syntax

```
mwPointer mxGetCell(pm, index)
mwPointer pm
mwIndex index
```

Arguments

pm
Pointer to a cell mxArray

index
The number of elements in the cell mxArray between the first element and the desired one. See `mxCalcSingleSubscript` for details on calculating an index in a multidimensional cell array.

Returns A pointer to the *i*th cell mxArray if successful, and NULL in C (0 in Fortran) otherwise. Causes of failure include

- Specifying the index of a cell array element that has not been populated.
- Specifying a pm that does not point to a cell mxArray.
- Specifying an index greater than the number of elements in the cell.
- Insufficient free heap space to hold the returned cell mxArray.

Description Call `mxGetCell` to get a pointer to the mxArray held in the indexed element of the cell mxArray.

Note Inputs to a MEX-file are constant read-only mxArrays and should not be modified. Using `mxSetCell*` or `mxSetField*` to modify the cells or fields of a MATLAB argument causes unpredictable results.

mxGetCell (C and Fortran)

C Examples

See `explore.c` in the `mex` subdirectory of the `examples` directory.

See Also

`mxCreateCellArray`, `mxIsCell`, `mxSetCell`

Purpose	Get pointer to character array data
C Syntax	<pre>#include "matrix.h" mxChar *mxGetChars(const mxArray *array_ptr);</pre>
Arguments	<pre>array_ptr Pointer to an mxArray</pre>
Returns	The address of the first character in the mxArray. Returns NULL if the specified array is not a character array.
Description	Call mxGetChars to determine the address of the first character in the mxArray that array_ptr points to. Once you have the starting address, you can access any other element in the mxArray.
See Also	<pre>mxGetString</pre>

mxGetClassID (C and Fortran)

Purpose	Get class of mxArray
C Syntax	<pre>#include "matrix.h" mxClassID mxGetClassID(const mxArray *pm);</pre>
Fortran Syntax	<pre>integer*4 mxGetClassID(pm) mwPointer pm</pre>
Arguments	pm Pointer to an mxArray
Returns	A numeric identifier of the class (category) of the mxArray that pm points to. The C-language class identifiers are listed in the mxClassID reference page.
Description	<p>Use mxGetClassId to determine the class of an mxArray. The class of an mxArray identifies the kind of data the mxArray is holding. For example, if pm points to a logical mxArray, then mxGetClassId returns mxLOGICAL_CLASS (in C).</p> <p>mxGetClassId is similar to mxGetClassName, except that the former returns the class as an integer identifier and the latter returns the class as a string.</p>
C Examples	See <ul style="list-style-type: none">• phonebook.c in the refbook subdirectory of the examples directory• explore.c in the mex subdirectory of the examples directory
See Also	mxClassID, mxGetClassName

mxGetClassName (C and Fortran)

Purpose	Get class of mxArray as string
C Syntax	<pre>#include "matrix.h" const char *mxGetClassName(const mxArray *pm);</pre>
Fortran Syntax	<pre>character*(*) mxGetClassName(pm) mwPointer pm</pre>
Arguments	<p>pm Pointer to an mxArray</p>
Returns	The class (as a string) of the mxArray pointed to by pm.
Description	<p>Call mxGetClassName to determine the class of an mxArray. The class of an mxArray identifies the kind of data the mxArray is holding. For example, if pm points to a logical mxArray, mxGetClassName returns logical.</p> <p>mxGetClassID is similar to mxGetClassName, except that the former returns the class as an integer identifier, as listed in the mxClassID reference page, and the latter returns the class as a string, as listed in the mxIsClass reference page.</p>
C Examples	<p>See mexfunction.c in the mex subdirectory of the examples directory. For an additional example, see mxisclass.c in the mx subdirectory of the examples directory.</p>
See Also	mxGetClassID, mxIsClass

mxGetData (C and Fortran)

Purpose	Get pointer to data
C Syntax	<pre>#include "matrix.h" void *mxGetData(const mxArray *pm);</pre>
Fortran Syntax	<pre>mwPointer mxGetData(pm) mwPointer pm</pre>
Arguments	pm Pointer to an mxArray
Returns	The address of the first element of the real data. Returns NULL in C (0 in Fortran) if there is no real data.
Description	Similar to mxGetPr, except that in C, mxGetData returns a void *. To copy values from the returned pointer to Fortran, use one of the mxCopyPtrTo* functions in the following manner: <pre>C Get the data in mxArray, pm mxCopyPtrToReal8(mxGetData(pm), data, + mxGetNumberOfElements(pm))</pre>
C Examples	See phonebook.c in the refbook subdirectory of the examples directory. For additional examples, see mxcreatecharmatrixfromstr.c and mxisfinite.c in the mx subdirectory of the examples directory.
See Also	mxGetImagData, mxGetPr

mxGetDimensions (C and Fortran)

Purpose Get pointer to dimensions array

C Syntax

```
#include "matrix.h"
const mwSize *mxGetDimensions(const mxArray *pm);
```

Fortran Syntax

```
mwPointer mxGetDimensions(pm)
mwPointer pm
```

Arguments

pm
Pointer to an mxArray.

Returns The address of the first element in the dimensions array. Each integer in the dimensions array represents the number of elements in a particular dimension. The array is not NULL terminated.

Description Use mxGetDimensions to determine how many elements are in each dimension of the mxArray that pm points to. Call mxGetNumberOfDimensions to get the number of dimensions in the mxArray.

To copy the values to Fortran, use mxCopyPtrToInteger4 in the following manner:

```
C      Get dimensions of mxArray, pm
      mxCopyPtrToInteger4(mxGetDimensions(pm), dims,
+                          mxGetNumberOfDimensions(pm))
```

C Examples See mxcalcsinglesubscript.c in the mx subdirectory of the examples directory.

Additional examples:

- findnz.c and phonebook.c in the refbook subdirectory of the examples directory
- explore.c in the mex subdirectory of the examples directory

mxGetDimensions (C and Fortran)

- `mxgeteps.c` and `mxisfinite.c` in the `mx` subdirectory of the `examples` directory

See Also

`mxGetNumberOfDimensions`

mxGetElementSize (C and Fortran)

Purpose	Get number of bytes required to store each data element
C Syntax	<pre>#include "matrix.h" mwSize mxGetElementSize(const mxArray *pm);</pre>
Fortran Syntax	<pre>mwSize mxGetElementSize(pm) mwPointer pm</pre>
Arguments	<p>pm Pointer to an mxArray</p>
Returns	The number of bytes required to store one element of the specified mxArray, if successful. Returns 0 on failure. The primary reason for failure is that pm points to an mxArray having an unrecognized class. If pm points to a cell mxArray or a structure mxArray, mxGetElementSize returns the size of a pointer (not the size of all the elements in each cell or structure field).
Description	<p>Call mxGetElementSize to determine the number of bytes in each data element of the mxArray. For example, if the MATLAB class of an mxArray is int16, the mxArray stores each data element as a 16-bit (2-byte) signed integer. Thus, mxGetElementSize returns 2.</p> <p>mxGetElementSize is particularly helpful when using a non-MATLAB routine to manipulate data elements. For example, the C function memcpy requires (for its third argument) the size of the elements you intend to copy.</p>
C Examples	See doubleelement.c and phonebook.c in the refbook subdirectory of the examples directory.
See Also	mxGetM, mxGetN

mxGetEps (C and Fortran)

Purpose	Get value of eps
C Syntax	<pre>#include "matrix.h" double mxGetEps(void);</pre>
Fortran Syntax	<pre>real*8 mxGetEps</pre>
Returns	The value of the MATLAB eps variable
Description	Call mxGetEps to return the value of the MATLAB eps variable. This variable holds the distance from 1.0 to the next largest floating-point number. As such, it is a measure of floating-point accuracy. The MATLAB pinv and rank functions use eps as a default tolerance.
C Examples	See mxgeteps.c in the mx subdirectory of the examples directory.
See Also	mxGetInf, mxGetNan

Purpose Get field value, given field name and index into structure array

C Syntax

```
#include "matrix.h"
mxArray *mxGetField(const mxArray *pm, mwIndex index,
                    const char *fieldname);
```

Fortran Syntax

```
mwPointer mxGetField(pm, index, fieldname)
mwPointer pm
mwIndex index
character*(*) fieldname
```

Arguments

`pm` Pointer to a structure mxArray

`index` Index of the desired element.

In C, the first element of an mxArray has an index of 0, the second element has an index of 1, and the last element has an index of N-1, where N is the total number of elements in the mxArray.

In Fortran, the first element of an mxArray has an index of 1, the second element has an index of 2, and the last element has an index of N, where N is the total number of elements in the mxArray.

`fieldname` The name of the field whose value you want to extract.

Returns A pointer to the mxArray in the specified field at the specified `fieldname`, on success. Returns NULL in C (0 in Fortran) if passed an invalid argument or if there is no value assigned to the specified field. Common causes of failure include:

- Specifying an array pointer `pm` that does not point to a structure mxArray. To determine whether `pm` points to a structure mxArray, call `mxIsStruct`.

mxGetField (C and Fortran)

- Specifying an `index` to an element outside the bounds of the `mxArray`. For example, given a structure `mxArray` that contains 10 elements, you cannot specify an `index` greater than 9 in C (10 in Fortran).
- Specifying a nonexistent `fieldname`. Call `mxGetFieldNameByNumber` or `mxGetFieldNumber` to get existing field names.
- Insufficient heap space to hold the returned `mxArray`.

Description

Call `mxGetField` to get the value held in the specified element of the specified field. In pseudo-C terminology, `mxGetField` returns the value at:

```
pm[index].fieldname
```

`mxGetFieldByNumber` is similar to `mxGetField`. Both functions return the same value. The only difference is in the way you specify the field. `mxGetFieldByNumber` takes a field number as its third argument, and `mxGetField` takes a field name as its third argument.

Note Inputs to a MEX-file are constant read-only `mxArrays` and should not be modified. Using `mxSetCell*` or `mxSetField*` to modify the cells or fields of a MATLAB argument causes unpredictable results.

In C, calling:

```
mxGetField(pa, index, "field_name");
```

is equivalent to calling:

```
field_num = mxGetFieldNumber(pa, "field_name");  
mxGetFieldByNumber(pa, index, field_num);
```

where `index` is 0 if you have a 1-by-1 structure.

In Fortran, calling:

```
mxGetField(pm, index, 'fieldname')
```

is equivalent to calling:

```
fieldnum = mxGetFieldNumber(pm, 'fieldname')
mxGetFieldByNumber(pm, index, fieldnum)
```

where `index` is 1 if you have a 1-by-1 structure.

See Also

`mxGetFieldByNumber`, `mxGetFieldNameByNumber`, `mxGetFieldNumber`,
`mxGetNumberOfFields`, `mxIsStruct`, `mxSetField`, `mxSetFieldByNumber`

mxGetFieldByNumber (C and Fortran)

Purpose Get field value, given field number and index into structure array

C Syntax

```
#include "matrix.h"
mxArray *mxGetFieldByNumber(const mxArray *pm, mwIndex index,
                             int fieldnumber);
```

Fortran Syntax

```
mwPointer mxGetFieldByNumber(pm, index, fieldnumber)
mwPointer pm
mwIndex index
integer*4 fieldnumber
```

Arguments

pm
Pointer to a structure mxArray

index
Index of the desired element.

In C, the first element of an mxArray has an index of 0, the second element has an index of 1, and the last element has an index of N-1, where N is the total number of elements in the mxArray.

In Fortran, the first element of an mxArray has an index of 1, the second element has an index of 2, and the last element has an index of N, where N is the total number of elements in the mxArray.

See mxCalcSingleSubscript for more details on calculating an index.

fieldnumber
The position of the field whose value you want to extract

In C, the first field within each element has a field number of 0, the second field has a field number of 1, and so on. The last field has a field number of N-1, where N is the number of fields.

mxGetFieldByNumber (C and Fortran)

In Fortran, the first field within each element has a field number of 1, the second field has a field number of 2, and so on. The last field has a field number of N, where N is the number of fields.

Returns

A pointer to the mxArray in the specified field for the desired element, on success. Returns NULL in C (0 in Fortran) if passed an invalid argument or if there is no value assigned to the specified field. Common causes of failure include:

- Specifying an array pointer `pm` that does not point to a structure mxArray. Call `mxIsStruct` to determine whether `pm` points to a structure mxArray.
- Specifying an index to an element outside the bounds of the mxArray. For example, given a structure mxArray that contains 10 elements, you cannot specify an index greater than 9 in C (10 in Fortran).
- Specifying a nonexistent field number. Call `mxGetFieldNumber` to determine the field number that corresponds to a given field name.

Description

Call `mxGetFieldByNumber` to get the value held in the specified `fieldnumber` at the indexed element.

Note Inputs to a MEX-file are constant read-only mxArrays and should not be modified. Using `mxSetCell*` or `mxSetField*` to modify the cells or fields of a MATLAB argument causes unpredictable results.

In C, calling:

```
mxGetField(pa, index, "field_name");
```

is equivalent to calling:

```
field_num = mxGetFieldNumber(pa, "field_name");  
mxGetFieldByNumber(pa, index, field_num);
```

mxGetFieldByNumber (C and Fortran)

where `index` is 0 if you have a 1-by-1 structure.

In Fortran, calling:

```
mxGetField(pm, index, 'fieldname')
```

is equivalent to calling:

```
fieldnum = mxGetFieldNumber(pm, 'fieldname')
mxGetFieldByNumber(pm, index, fieldnum)
```

where `index` is 1 if you have a 1-by-1 structure.

C Examples

See `phonebook.c` in the `refbook` subdirectory of the `examples` directory.

Additional examples:

- `mxiclass.c` in the `mx` subdirectory of the `examples` directory
- `explore.c` in the `mex` subdirectory of the `examples` directory

See Also

`mxGetField`, `mxGetFieldNameByNumber`, `mxGetFieldNumber`,
`mxGetNumberOfFields`, `mxIsStruct`, `mxSetField`, `mxSetFieldByNumber`

mxGetFieldNameByNumber (C and Fortran)

Purpose

Get field name, given field number in structure array

C Syntax

```
#include "matrix.h"
const char *mxGetFieldNameByNumber(const mxArray *pm,
    int fieldnumber);
```

Fortran Syntax

```
character*(*) mxGetFieldNameByNumber(pm, fieldnumber)
mwPointer pm
integer*4 fieldnumber
```

Arguments

pm

Pointer to a structure mxArray

fieldnumber

The position of the desired field. For instance, in C, to get the name of the first field, set `fieldnumber` to 0; to get the name of the second field, set `fieldnumber` to 1; and so on. In Fortran, to get the name of the first field, set `fieldnumber` to 1; to get the name of the second field, set `fieldnumber` to 2; and so on.

Returns

A pointer to the *n*th field name, on success. Returns NULL in C (0 in Fortran) on failure. Common causes of failure include

- Specifying an array pointer `pm` that does not point to a structure mxArray. Call `mxIsStruct` to determine whether `pm` points to a structure mxArray.
- Specifying a value of `fieldnumber` outside the bounds of the number of fields in the structure mxArray. In C, `fieldnumber` 0 represents the first field, and `fieldnumber` *N*-1 represents the last field, where *N* is the number of fields in the structure mxArray. In Fortran, `fieldnumber` 1 represents the first field, and `fieldnumber` *N* represents the last field.

Description

Call `mxGetFieldNameByNumber` to get the name of a field in the given structure mxArray. A typical use of `mxGetFieldNameByNumber` is to

mxGetFieldNameByNumber (C and Fortran)

call it inside a loop in order to get the names of all the fields in a given mxArray.

Consider a MATLAB structure initialized to:

```
patient.name = 'John Doe';  
patient.billing = 127.00;  
patient.test = [79 75 73; 180 178 177.5; 220 210 205];
```

In C, the field number 0 represents the field name; field number 1 represents field `billing`; field number 2 represents field `test`. A field number other than 0, 1, or 2 causes `mxGetFieldNameByNumber` to return `NULL`.

In Fortran, the field number 1 represents the field name; field number 2 represents field `billing`; field number 3 represents field `test`. A field number other than 1, 2, or 3 causes `mxGetFieldNameByNumber` to return 0.

C Examples

See `phonebook.c` in the `refbook` subdirectory of the `examples` directory.

Additional examples:

- `mxisclass.c` in the `mx` subdirectory of the `examples` directory
- `explore.c` in the `mex` subdirectory of the `examples` directory

See Also

`mxGetField`, `mxGetFieldByNumber`, `mxGetFieldNumber`,
`mxGetNumberOfFields`, `mxIsStruct`, `mxSetField`, `mxSetFieldByNumber`

mxGetFieldName (C and Fortran)

Purpose Get field number, given field name in structure array

C Syntax

```
#include "matrix.h"
int mxGetFieldName(const mxArray *pm,
                  const char *fieldname);
```

Fortran Syntax

```
integer*4 mxGetFieldName(pm, fieldname)
mwPointer pm
character*(*) fieldname
```

Arguments

`pm`
Pointer to a structure mxArray.

`fieldname`
The name of a field in the structure mxArray.

Returns The field number of the specified `fieldname`, on success. In C, the first field has a field number of 0, the second field has a field number of 1, and so on. In Fortran, the first field has a field number of 1, the second field has a field number of 2, and so on. Returns -1 in C (0 in Fortran) on failure. Common causes of failure include

- Specifying an array pointer `pm` that does not point to a structure mxArray. Call `mxIsStruct` to determine whether `pm` points to a structure mxArray.
- Specifying the `fieldname` of a nonexistent field.

Description If you know the name of a field but do not know its field number, call `mxGetFieldName`. Conversely, if you know the field number but do not know its field name, call `mxGetFieldNameByNumber`.

For example, consider a MATLAB structure initialized to:

```
patient.name = 'John Doe';
patient.billing = 127.00;
patient.test = [79 75 73; 180 178 177.5; 220 210 205];
```

mxGetFieldName (C and Fortran)

In C, the field `name` has a field number of 0; the field `billing` has a field number of 1; and the field `test` has a field number of 2. If you call `mxGetFieldName` and specify a field name of anything other than `name`, `billing`, or `test`, `mxGetFieldName` returns -1.

Calling:

```
mxGetField(pa, index, "field_name");
```

is equivalent to calling:

```
field_num = mxGetFieldName(pa, "field_name");  
mxGetFieldByNumber(pa, index, field_num);
```

where `index` is 0 if you have a 1-by-1 structure.

In Fortran, the field `name` has a field number of 1; the field `billing` has a field number of 2; and the field `test` has a field number of 3. If you call `mxGetFieldName` and specify a field name of anything other than `name`, `billing`, or `test`, `mxGetFieldName` returns 0.

Calling:

```
mxGetField(pm, index, 'fieldname');
```

is equivalent to calling:

```
fieldnum = mxGetFieldName(pm, 'fieldname');  
mxGetFieldByNumber(pm, index, fieldnum);
```

where `index` is 1 if you have a 1-by-1 structure.

C **Examples**

See `mxcreatestructarray.c` in the `mx` subdirectory of the examples directory.

See Also

`mxGetField`, `mxGetFieldByNumber`, `mxGetFieldNameByNumber`,
`mxGetNumberOfFields`, `mxIsStruct`, `mxSetField`, `mxSetFieldByNumber`

mxGetImagData (C and Fortran)

Purpose	Get pointer to imaginary data of mxArray
C Syntax	<pre>#include "matrix.h" void *mxGetImagData(const mxArray *pm);</pre>
Fortran Syntax	<pre>mwPointer mxGetImagData(pm) mwPointer pm</pre>
Arguments	<p>pm Pointer to an mxArray</p>
Returns	The address of the first element of the imaginary data, on success. Returns NULL in C (0 in Fortran) if there is no imaginary data or if there is an error.
Description	This function is similar to mxGetPi, except that in C it returns a void *.
C Examples	See mxisfinite.c in the mx subdirectory of the examples directory.
See Also	mxGetData, mxGetPi

mxGetInf (C and Fortran)

Purpose	Get value of infinity
C Syntax	<pre>#include "matrix.h" double mxGetInf(void);</pre>
Fortran Syntax	<pre>real*8 mxGetInf</pre>
Returns	The value of infinity on your system.
Description	<p>Call <code>mxGetInf</code> to return the value of the MATLAB internal <code>inf</code> variable. <code>inf</code> is a permanent variable representing IEEE® arithmetic positive infinity. The value of <code>inf</code> is built into the system; you cannot modify it.</p> <p>Operations that return infinity include</p> <ul style="list-style-type: none">• Division by 0. For example, <code>5/0</code> returns infinity.• Operations resulting in overflow. For example, <code>exp(10000)</code> returns infinity because the result is too large to be represented on your machine.
C Examples	See <code>mxgetinf.c</code> in the <code>mx</code> subdirectory of the <code>examples</code> directory.
See Also	<code>mxGetEps</code> , <code>mxGetNaN</code>

Purpose	Get <code>ir</code> array of sparse matrix
C Syntax	<pre>#include "matrix.h" mwIndex *mxGetIr(const mxArray *pm);</pre>
Fortran Syntax	<pre>mwPointer mxGetIr(pm) mwPointer pm</pre>
Arguments	<p><code>pm</code> Pointer to a sparse <code>mxArray</code></p>
Returns	<p>A pointer to the first element in the <code>ir</code> array, if successful, and NULL in C (0 in Fortran) otherwise. Possible causes of failure include</p> <ul style="list-style-type: none">• Specifying a full (nonsparse) <code>mxArray</code>.• Specifying a value for <code>pm</code> that is NULL in C (0 in Fortran). This usually means that an earlier call to <code>mxCreateSparse</code> failed.
Description	<p>Use <code>mxGetIr</code> to obtain the starting address of the <code>ir</code> array. The <code>ir</code> array is an array of integers; the length of the <code>ir</code> array is typically <code>nzmax</code> values. For example, if <code>nzmax</code> equals 100, the <code>ir</code> array should contain 100 integers.</p> <p>Each value in an <code>ir</code> array indicates a row (offset by 1) at which a nonzero element can be found. (The <code>jc</code> array is an index that indirectly specifies a column where nonzero elements can be found.)</p> <p>For details on the <code>ir</code> and <code>jc</code> arrays, see <code>mxSetIr</code> and <code>mxSetJc</code>.</p>
C Examples	<p>See <code>fulltosparse.c</code> in the <code>refbook</code> subdirectory of the <code>examples</code> directory.</p> <p>Additional examples:</p> <ul style="list-style-type: none">• <code>explore.c</code> in the <code>mex</code> subdirectory of the <code>examples</code> directory

mxGetlr (C and Fortran)

- `mxsetdimensions.c` and `mxsetnzmax.c` in the `mx` subdirectory of the `examples` directory

See Also

`mxGetJc`, `mxGetNzmax`, `mxSetIr`, `mxSetJc`, `mxSetNzmax`

Purpose	Get jc array of sparse matrix
C Syntax	<pre>#include "matrix.h" mwIndex *mxGetJc(const mxArray *pm);</pre>
Fortran Syntax	<pre>mwPointer mxGetJc(pm) mwPointer pm</pre>
Arguments	<p>pm</p> <p>Pointer to a sparse mxArray</p>
Returns	<p>A pointer to the first element in the jc array, if successful, and NULL in C (0 in Fortran) otherwise. Possible causes of failure include</p> <ul style="list-style-type: none">• Specifying a full (nonsparse) mxArray.• Specifying a value for pm that is NULL in C (0 in Fortran). This usually means that an earlier call to mxCreateSparse failed.
Description	<p>Use mxGetJc to obtain the starting address of the jc array. The jc array is an integer array having n+1 elements, where n is the number of columns in the sparse mxArray. The values in the jc array indirectly indicate columns containing nonzero elements. For a detailed explanation of the jc array, see mxSetJc.</p>
C Examples	<p>See fulltosparse.c in the refbook subdirectory of the examples directory.</p> <p>Additional examples:</p> <ul style="list-style-type: none">• explore.c in the mex subdirectory of the examples directory• mxgetnzmax.c, mxsetdimensions.c, and mxsetnzmax.c in the mx subdirectory of the examples directory
See Also	<p>mxGetIr, mxGetNzmax, mxSetIr, mxSetJc, mxSetNzmax</p>

mxGetLogicals (C)

Purpose Get pointer to logical array data

C Syntax

```
#include "matrix.h"
mxLogical *mxGetLogicals(const mxArray *array_ptr);
```

Arguments `array_ptr`
Pointer to an mxArray

Returns The address of the first logical element in the mxArray. The result is unspecified if the mxArray is not a logical array.

Description Call `mxGetLogicals` to determine the address of the first logical element in the mxArray that `array_ptr` points to. Once you have the starting address, you can access any other element in the mxArray.

See Also `mxCreateLogicalArray`, `mxCreateLogicalMatrix`,
`mxCreateLogicalScalar`, `mxIsLogical`, `mxIsLogicalScalar`,
`mxIsLogicalScalarTrue`

Purpose Get number of rows in mxArray

C Syntax

```
#include "matrix.h"
size_t mxGetM(const mxArray *pm);
```

Fortran Syntax

```
mwPointer mxGetM(pm)
mwPointer pm
```

Arguments

pm
 Pointer to an mxArray

Returns The number of rows in the mxArray to which pm points.

Description mxGetM returns the number of rows in the specified array. The term *rows* always means the first dimension of the array, no matter how many dimensions the array has. For example, if pm points to a four-dimensional array having dimensions 8-by-9-by-5-by-3, mxGetM returns 8.

Note Fortran does not have an equivalent of `size_t`. `mwPointer` is a preprocessor macro that provides the appropriate Fortran type. The value returned by this function, however, is not a pointer.

C Examples See `convec.c` in the `refbook` subdirectory of the `examples` directory. Additional examples:

- `fulltosparse.c`, `revord.c`, `timestwo.c`, and `xtimesy.c` in the `refbook` subdirectory of the `examples` directory
- `explore.c`, `mexget.c`, `mexlock.c`, `mexsettrapflag.c` and `yprime.c` in the `mex` subdirectory of the `examples` directory
- `mxmalloc.c`, `mxsetdimensions.c`, `mxgetnzmax.c`, and `mxsetnzmax.c` in the `mx` subdirectory of the `examples` directory

mxGetM (C and Fortran)

Fortran Examples

See `matdemo2.F` in the `eng_mat` subdirectory of the `examples` directory for a sample program that illustrates how to use this routine in a Fortran program.

See Also

`mxGetN`, `mxSetM`, `mxSetN`

Purpose	Get number of columns in mxArray
C Syntax	<pre>#include "matrix.h" size_t mxGetN(const mxArray *pm);</pre>
Fortran Syntax	<pre>mwPointer mxGetN(pm) mwPointer pm</pre>
Arguments	<p>pm Pointer to an mxArray</p>
Returns	The number of columns in the mxArray.
Description	<p>Call mxGetN to determine the number of columns in the specified mxArray.</p> <p>If pm is an N-dimensional mxArray, mxGetN is the product of dimensions 2 through N. For example, if pm points to a four-dimensional mxArray having dimensions 13-by-5-by-4-by-6, mxGetN returns the value 120 ($5 \times 4 \times 6$). If the specified mxArray has more than two dimensions and you need to know exactly how many elements are in each dimension, call mxGetDimensions.</p> <p>If pm points to a sparse mxArray, mxGetN still returns the number of columns, not the number of occupied columns.</p> <hr/> <p>Note Fortran does not have an equivalent of size_t. mwPointer is a preprocessor macro that provides the appropriate Fortran type. The value returned by this function, however, is not a pointer.</p> <hr/>
C Examples	<p>See convec.c in the refbook subdirectory of the examples directory.</p> <p>Additional examples:</p>

mxGetN (C and Fortran)

- `fulltospase.c`, `revord.c`, `timestwo.c`, and `xtimesy.c` in the `refbook` subdirectory of the `examples` directory
- `explore.c`, `mexget.c`, `mexlock.c`, `mexsettrapflag.c` and `yprime.c` in the `mex` subdirectory of the `examples` directory
- `mxmalloc.c`, `mxsetdimensions.c`, `mxgetnzmax.c`, and `mxsetnzmax.c` in the `mx` subdirectory of the `examples` directory

Fortran Examples

See `matdemo2.F` in the `eng_mat` subdirectory of the `examples` directory for a sample program that illustrates how to use this routine in a Fortran program.

See Also

`mxGetM`, `mxGetDimensions`, `mxSetM`, `mxSetN`

Purpose Get value of NaN (Not-a-Number)

C Syntax

```
#include "matrix.h"
double mxGetNaN(void);
```

Fortran Syntax

```
real*8 mxGetNaN
```

Returns The value of NaN (Not-a-Number) on your system

Description Call mxGetNaN to return the value of NaN for your system. NaN is the IEEE arithmetic representation for Not-a-Number. Certain mathematical operations return NaN as a result, for example,

- 0.0/0.0
- Inf-Inf

The value of Not-a-Number is built in to the system. You cannot modify it.

C Examples See mxgetinf.c in the mx subdirectory of the examples directory.

See Also mxGetEps, mxGetInf

mxGetNumberOfDimensions (C and Fortran)

Purpose	Get number of dimensions in mxArray
C Syntax	<pre>#include "matrix.h" mwSize mxGetNumberOfDimensions(const mxArray *pm);</pre>
Fortran Syntax	<pre>mwSize mxGetNumberOfDimensions(pm) mwPointer pm</pre>
Arguments	pm Pointer to an mxArray
Returns	The number of dimensions in the specified mxArray. The returned value is always 2 or greater.
Description	Use <code>mxGetNumberOfDimensions</code> to determine how many dimensions are in the specified array. To determine how many elements are in each dimension, call <code>mxGetDimensions</code> .
C Examples	See <code>explore.c</code> in the <code>mex</code> subdirectory of the <code>examples</code> directory. Additional examples: <ul style="list-style-type: none">• <code>findnz.c</code>, <code>fulltosparse.c</code>, and <code>phonebook.c</code> in the <code>refbook</code> subdirectory of the <code>examples</code> directory• <code>mxcalcsinglesubscript.c</code>, <code>mxgeteps.c</code>, and <code>mxisfinite.c</code> in the <code>mx</code> subdirectory of the <code>examples</code> directory.
See Also	<code>mxSetM</code> , <code>mxSetN</code> , <code>mxGetDimensions</code>

mxGetNumberOfElements (C and Fortran)

Purpose	Get number of elements in mxArray
C Syntax	<pre>#include "matrix.h" mwSize mxGetNumberOfElements(const mxArray *pm);</pre>
Fortran Syntax	<pre>mwSize mxGetNumberOfElements(pm) mwPointer pm</pre>
Arguments	pm Pointer to an mxArray
Returns	Number of elements in the specified mxArray
Description	mxGetNumberOfElements tells you how many elements an array has. For example, if the dimensions of an array are 3-by-5-by-10, mxGetNumberOfElements returns the number 150.
C Examples	See findnz.c and phonebook.c in the refbook subdirectory of the examples directory. Additional examples: <ul style="list-style-type: none">• explore.c in the mex subdirectory of the examples directory• mxcalcsinglesubscript.c, mxgeteps.c, mxgetinf.c, mxisfinite.c, and mxsetdimensions.c in the mx subdirectory of the examples directory
See Also	mxGetDimensions, mxGetM, mxGetN, mxGetClassID, mxGetClassName

mxGetNumberOfFields (C and Fortran)

Purpose	Get number of fields in structure mxArray
C Syntax	<pre>#include "matrix.h" int mxGetNumberOfFields(const mxArray *pm);</pre>
Fortran Syntax	<pre>integer*4 mxGetNumberOfFields(pm) mwPointer pm</pre>
Arguments	pm Pointer to a structure mxArray
Returns	The number of fields, on success. Returns 0 on failure. The most common cause of failure is that pm is not a structure mxArray. Call mxIsStruct to determine whether pm is a structure.
Description	Call mxGetNumberOfFields to determine how many fields are in the specified structure mxArray. Once you know the number of fields in a structure, you can loop through every field in order to set or to get field values.
C Examples	See phonebook.c in the refbook subdirectory of the examples directory. Additional examples: <ul style="list-style-type: none">• mxisclass.c in the mx subdirectory of the examples directory• explore.c in the mex subdirectory of the examples directory.
See Also	mxGetField, mxIsStruct, mxSetField

Purpose	Get number of elements in <i>ir</i> , <i>pr</i> , and <i>pi</i> arrays
C Syntax	<pre>#include "matrix.h" mwSize mxGetNzmax(const mxArray *pm);</pre>
Fortran Syntax	<pre>mwSize mxGetNzmax(pm) mwPointer pm</pre>
Arguments	<p><i>pm</i></p> <p>Pointer to a sparse mxArray</p>
Returns	The number of elements allocated to hold nonzero entries in the specified sparse mxArray, on success. Returns an indeterminate value on error. The most likely cause of failure is that <i>pm</i> points to a full (nonsparse) mxArray.
Description	<p>Use <code>mxGetNzmax</code> to get the value of the <code>nzmax</code> field. The <code>nzmax</code> field holds an integer value that signifies the number of elements in the <i>ir</i>, <i>pr</i>, and, if it exists, the <i>pi</i> arrays. The value of <code>nzmax</code> is always greater than or equal to the number of nonzero elements in a sparse mxArray. In addition, the value of <code>nzmax</code> is always less than or equal to the number of rows times the number of columns.</p> <p>As you adjust the number of nonzero elements in a sparse mxArray, MATLAB software often adjusts the value of the <code>nzmax</code> field. MATLAB adjusts <code>nzmax</code> in order to reduce the number of costly reallocations and in order to optimize its use of heap space.</p>
C Examples	See <code>mxgetnzmax.c</code> and <code>mxsetnzmax.c</code> in the <code>mx</code> subdirectory of the <code>examples</code> directory.
See Also	<code>mxSetNzmax</code>

mxGetPi (C and Fortran)

Purpose	Get imaginary data elements in mxArray
C Syntax	<pre>#include "matrix.h" double *mxGetPi(const mxArray *pm);</pre>
Fortran Syntax	<pre>mwPointer mxGetPi(pm) mwPointer pm</pre>
Arguments	pm Pointer to an mxArray
Returns	The imaginary data elements of the specified mxArray, on success. Returns NULL in C (0 in Fortran) if there is no imaginary data or if there is an error.
Description	<p>The pi field points to an array containing the imaginary data of the mxArray. Call mxGetPi to get the contents of the pi field, that is, to get the starting address of this imaginary data.</p> <p>The best way to determine whether an mxArray is purely real is to call mxIsComplex.</p> <p>The imaginary parts of all input matrices to a MATLAB function are allocated if any of the input matrices are complex.</p>
C Examples	<p>See convec.c, findnz.c, and fulltosparse.c in the refbook subdirectory of the examples directory.</p> <p>Additional examples:</p> <ul style="list-style-type: none">• explore.c and mexcallmatlab.c in the mex subdirectory of the examples directory• mxcalcsinglesubscript.c, mxgetinf.c, mxisfinite.c, and mxsetnzmax.c in the mx subdirectory of the examples directory
See Also	mxGetPr, mxSetPi, mxSetPr

Purpose	Get real data elements in mxArray
C Syntax	<pre>#include "matrix.h" double *mxGetPr(const mxArray *pm);</pre>
Fortran Syntax	<pre>mwPointer mxGetPr(pm) mwPointer pm</pre>
Arguments	<p>pm Pointer to an mxArray</p>
Returns	The address of the first element of the real data. Returns NULL in C (0 in Fortran) if there is no real data.
Description	Call mxGetPr to determine the starting address of the real data in the mxArray that pm points to. Once you have the starting address, you can access any other element in the mxArray.
C Examples	See convec.c, doubleelement.c, findnz.c, fulltosparse.c, sincall.c, timestwo.c, timestwoalt.c, and xtimesy.c in the refbook subdirectory of the examples directory.
See Also	mxGetPi, mxSetPi, mxSetPr

mxGetProperty (C and Fortran)

Purpose Get property value of MATLAB class object

C Syntax

```
#include "matrix.h"
mxArray *mxGetProperty(const mxArray *pa, mwIndex index,
                      const char *proprname);
```

Fortran Syntax

```
mwPointer mxGetProperty(pa, index, proprname)
mwPointer pa
mwIndex index
character*(*) proprname
```

Arguments

pa
Pointer to an mxArray which is a class object.

index
Index of the desired element of the object array.

In C, the first element of an mxArray has an index of 0, the second element has an index of 1, and the last element has an index of N-1, where N is the total number of elements in the mxArray.

In Fortran, the first element of an mxArray has an index of 1, the second element has an index of 2, and the last element has an index of N, where N is the total number of elements in the mxArray.

proprname
Name of the property whose value you want to extract.

Returns A pointer to the mxArray of the specified proprname on success.

Common causes of failure include:

- Specifying an index to an element outside the bounds of the mxArray. Use `mxGetNumberOfElements` or `mxGetM` and `mxGetN` to test the index value.
- Specifying a nonexistent proprname.

mxGetProperty (C and Fortran)

- Specifying a propname with an attribute setting that restricts access to its value.
- Insufficient memory (in the heap) to hold the returned mxArray.

Description

Call `mxGetProperty` to get the value held in the specified element. In pseudo-C terminology, `mxGetProperty` returns the value at:

```
pa[index].propname
```

See Also

`mxSetProperty`, `mxGetNumberOfElements`, `mxGetM`, `mxGetN`

mxGetScalar (C and Fortran)

Purpose	Get real component of first data element in mxArray
C Syntax	<pre>#include "matrix.h" double mxGetScalar(const mxArray *pm);</pre>
Fortran Syntax	<pre>real*8 mxGetScalar(pm) mwPointer pm</pre>
Arguments	<p>pm</p> <p>Pointer to an mxArray; cannot be a cell mxArray, a structure mxArray, or an empty mxArray.</p>
Returns	<p>The value of the first real (nonimaginary) element of the mxArray. Notice that in C, mxGetScalar returns a double. Therefore, if real elements in the mxArray are stored as something other than double, mxGetScalar automatically converts the scalar value into a double. To preserve the original data representation of the scalar, you must cast the return value to the desired data type.</p> <p>mxGetScalar should only be called when pm points to a nonempty numeric, logical, or char mxArray. Use mx functions such as mxIsEmpty, mxIsLogical, mxIsNumeric, or mxIsChar to test for this condition before calling mxGetScalar.</p> <p>If pm points to a sparse mxArray, mxGetScalar returns the value of the first nonzero real element in the mxArray.</p>
Description	<p>Call mxGetScalar to get the value of the first real (nonimaginary) element of the mxArray.</p> <p>In most cases, you call mxGetScalar when pm points to an mxArray containing only one element (a scalar). However, pm can point to an mxArray containing many elements. If pm points to an mxArray containing multiple elements, mxGetScalar returns the value of the first real element. If pm points to a two-dimensional mxArray, mxGetScalar returns the value of the (1,1) element; if pm points to</p>

a three-dimensional mxArray, mxGetScalar returns the value of the (1,1,1) element; and so on.

C Examples

See `timestwoalt.c` and `xtimesy.c` in the `refbook` subdirectory of the `examples` directory.

Additional examples:

- `mxsetdimensions.c` in the `mx` subdirectory of the `examples` directory
- `mexlock.c` and `mexsettrapflag.c` in the `mex` subdirectory of the `examples` directory

See Also

`mxGetM`, `mxGetN`

mxGetString (C and Fortran)

Purpose	Copy string mxArray to C-style string
C Syntax	<pre>#include "matrix.h" int mxGetString(const mxArray *pm, char *str, mwSize strlen);</pre>
Fortran Syntax	<pre>integer*4 mxGetString(pm, str, strlen) mwPointer pm character*(*) str mwSize strlen</pre>
Arguments	<p>pm Pointer to a string mxArray; that is, a pointer to an mxArray having the mxCHAR_CLASS class.</p> <p>str The starting location into which the string should be written. mxGetString writes the character data into str and then, in C, terminates the string with a NULL character (in the manner of C strings). str can point to either dynamic or static memory.</p> <p>strlen Maximum number of characters to read into str. Typically, in C, you set strlen to 1 plus the number of elements in the string mxArray to which pm points. See the mxGetM and mxGetN reference pages to find out how to get the number of elements.</p>
Returns	<p>0 on success, and 1 on failure. Possible reasons for failure include</p> <ul style="list-style-type: none">• Specifying an mxArray that is not a string mxArray.• Specifying strlen with less than the number of characters needed to store the entire mxArray pointed to by pm. If this is the case, 1 is returned and the string is truncated.
Description	Call mxGetString to copy the character data of a string mxArray into a C-style string in C or a character array in Fortran. The copied string starts at str and contains no more than strlen-1 characters in C (no

more than `strlen` characters in Fortran). In C, the C-style string is always terminated with a NULL character.

If the string array contains several rows, they are copied—one column at a time—into one long string array.

Multibyte Character Sets

This function is for use only with strings that represent single-byte character sets. For strings that represent multibyte character sets, use the C function `mxArrayToString`. Fortran users must allocate sufficient space for the return string to avoid possible truncation.

```
strlen = (mxGetM(prhs[0]) * mxGetN(prhs[0]) * sizeof(mxChar)) + 1
```

C Examples

Examples:

- `explore.c` in the `mex` subdirectory of the `examples` directory
- `mxmalloc.c` in the `mx` subdirectory of the `examples` directory

See Also

`mxArrayToString`, `mxCreateCharArray`,
`mxCreateCharMatrixFromStrings`, `mxCreateString`

mxIsCell (C and Fortran)

Purpose	Determine whether input is cell mxArray
C Syntax	<pre>#include "matrix.h" bool mxIsCell(const mxArray *pm);</pre>
Fortran Syntax	<pre>integer*4 mxIsCell(pm) mwPointer pm</pre>
Arguments	pm Pointer to an mxArray
Returns	Logical 1 (true) if pm points to an array having the class mxCELL_CLASS, and logical 0 (false) otherwise.
Description	Use mxIsCell to determine whether the specified array is a cell array. In C, calling mxIsCell is equivalent to calling: <pre>mxGetClassID(pm) == mxCELL_CLASS</pre> In Fortran, calling mxIsCell is equivalent to calling: <pre>mxGetClassName(pm) .eq. 'cell'</pre>
	<hr/> Note mxIsCell does not answer the question “Is this mxArray a cell of a cell array?” An individual cell of a cell array can be of any type. <hr/>
See Also	mxIsClass

Purpose	Determine whether input is string mxArray
C Syntax	<pre>#include "matrix.h" bool mxIsChar(const mxArray *pm);</pre>
Fortran Syntax	<pre>integer*4 mxIsChar(pm) mwPointer pm</pre>
Arguments	pm Pointer to an mxArray
Returns	Logical 1 (true) if pm points to an array having the class mxCHAR_CLASS, and logical 0 (false) otherwise.
Description	<p>Use mxIsChar to determine whether pm points to string mxArray.</p> <p>In C, calling mxIsChar is equivalent to calling:</p> <pre>mxGetClassID(pm) == mxCHAR_CLASS</pre> <p>In Fortran, calling mxIsChar is equivalent to calling:</p> <pre>mxGetClassName(pm) .eq. 'char'</pre>
C Examples	<p>See phonebook.c and revord.c in the refbook subdirectory of the examples directory.</p> <p>For additional examples, see mxcreatecharmatrixfromstr.c, mxislogical.c, and mxmalloc.c in the mx subdirectory of the examples directory.</p>
See Also	mxIsClass, mxGetClassID

mxIsClass (C and Fortran)

Purpose Determine whether mxArray is member of specified class

C Syntax

```
#include "matrix.h"
bool mxIsClass(const mxArray *pm, const char *classname);
```

Fortran Syntax

```
integer*4 mxIsClass(pm, classname)
mwPointer pm
character*(*) classname
```

Arguments

pm
Pointer to an mxArray

classname
The array category that you are testing. Specify classname as a string (not as an integer identifier). You can specify any one of the following predefined constants:

Value of classname	Corresponding Class
cell	mxCELL_CLASS
char	mxCHAR_CLASS
double	mxDOUBLE_CLASS
function_handle	mxFUNCTION_CLASS
int8	mxINT8_CLASS
int16	mxINT16_CLASS
int32	mxINT32_CLASS
int64	mxINT64_CLASS
logical	mxLOGICAL_CLASS
single	mxSINGLE_CLASS
struct	mxSTRUCT_CLASS
uint8	mxUINT8_CLASS

Value of classname	Corresponding Class
uint16	mxUINT16_CLASS
uint32	mxUINT32_CLASS
uint64	mxUINT64_CLASS
<class_name>	<class_id>
unknown	mxUNKNOWN_CLASS

In the table, <class_name> represents the name of a specific MATLAB custom object. You can also specify one of your own class names.

Returns

Logical 1 (true) if `pm` points to an array having category `classname`, and logical 0 (false) otherwise.

Description

Each `mxArray` is tagged as being a certain type. Call `mxIsClass` to determine whether the specified `mxArray` has this type.

In C:

```
mxIsClass(pm, "double");
```

is equivalent to calling either of these forms:

```
mxIsDouble(pm);
```

```
strcmp(mxGetClassName(pm), "double");
```

In Fortran:

```
mxIsClass(pm, 'double')
```

is equivalent to calling either one of the following:

```
mxIsDouble(pm)
```

```
mxGetClassName(pm) .eq. 'double'
```

mxIsClass (C and Fortran)

It is most efficient to use the `mxIsDouble` form.

C Examples

See `mxisclass.c` in the `mx` subdirectory of the `examples` directory.

See Also

`mxClassID`, `mxGetClassID`, `mxIsEmpty`, `mxGetClassName`

Purpose	Determine whether data is complex
C Syntax	<pre>#include "matrix.h" bool mxIsComplex(const mxArray *pm);</pre>
Fortran Syntax	<pre>integer*4 mxIsComplex(pm) mwPointer pm</pre>
Arguments	pm Pointer to an mxArray
Returns	Logical 1 (true) if pm is a numeric array containing complex data, and logical 0 (false) otherwise. If pm points to a cell array or a structure array, mxIsComplex returns false.
Description	Use mxIsComplex to determine whether or not an imaginary part is allocated for an mxArray. The imaginary pointer pi is NULL in C (0 in Fortran) if an mxArray is purely real and does not have any imaginary data. If an mxArray is complex, pi points to an array of numbers.
C Examples	See mxisfinite.c in the mx subdirectory of the examples directory. Additional examples: <ul style="list-style-type: none">• convec.c, phonebook.c, timestwo.c, and xtimesy.c in the refbook subdirectory of the examples directory• explore.c, yprime.c, mexlock.c, and mexsettrapflag.c in the mex subdirectory of the examples directory• mxcalcsinglesubscript.c, mxgeteps.c, and mxgetinf.c in the mx subdirectory of the examples directory
See Also	mxIsNumeric

mxIsDouble (C and Fortran)

Purpose	Determine whether mxArray represents data as double-precision, floating-point numbers
C Syntax	<pre>#include "matrix.h" bool mxIsDouble(const mxArray *pm);</pre>
Fortran Syntax	<pre>integer*4 mxIsDouble(pm) mwPointer pm</pre>
Arguments	pm Pointer to an mxArray
Returns	Logical 1 (true) if the mxArray stores its data as double-precision, floating-point numbers, and logical 0 (false) otherwise.
Description	<p>Call mxIsDouble to determine whether or not the specified mxArray represents its real and imaginary data as double-precision, floating-point numbers.</p> <p>Older versions of MATLAB software store all mxArray data as double-precision, floating-point numbers. However, starting with MATLAB Version 5 software, MATLAB can store real and imaginary data in a variety of numerical formats.</p> <p>In C, calling mxIsDouble is equivalent to calling:</p> <pre>mxGetClassID(pm) == mxDOUBLE_CLASS</pre> <p>In Fortran, calling mxIsDouble is equivalent to calling:</p> <pre>mxGetClassName(pm) .eq. 'double'</pre>
C Examples	See findnz.c, fulltosparse.c, timestwo.c, and xtimesy.c in the refbook subdirectory of the examples directory. Additional examples:

- `mexget.c`, `mexlock.c`, `mexsettrapflag.c`, and `yprime.c` in the `mex` subdirectory of the `examples` directory
- `mxcalcsinglesubscript.c`, `mxgeteps.c`, `mxgetinf.c`, and `mxisfinite.c` in the `mx` subdirectory of the `examples` directory

See Also

`mxIsClass`, `mxGetClassID`

mxIsEmpty (C and Fortran)

Purpose	Determine whether mxArray is empty
C Syntax	<pre>#include "matrix.h" bool mxIsEmpty(const mxArray *pm);</pre>
Fortran Syntax	<pre>integer*4 mxIsEmpty(pm) mwPointer pm</pre>
Arguments	pm Pointer to an mxArray
Returns	Logical 1 (true) if the mxArray is empty, and logical 0 (false) otherwise.
Description	Use mxIsEmpty to determine whether an mxArray contains no data. An mxArray is empty if the size of any of its dimensions is 0.
C Examples	See mxisfinite.c in the mx subdirectory of the examples directory.
See Also	mxIsClass

Purpose	Determine whether input is finite
C Syntax	<pre>#include "matrix.h" bool mxIsFinite(double value);</pre>
Fortran Syntax	<pre>integer*4 mxIsFinite(value) real*8 value</pre>
Arguments	value The double-precision, floating-point number that you are testing
Returns	Logical 1 (true) if value is finite, and logical 0 (false) otherwise.
Description	Call <code>mxIsFinite</code> to determine whether or not value is finite. A number is finite if it is greater than <code>-Inf</code> and less than <code>Inf</code> .
C Examples	See <code>mxisfinite.c</code> in the <code>mx</code> subdirectory of the <code>examples</code> directory.
See Also	<code>mxIsInf</code> , <code>mxIsNan</code>

mxIsFromGlobalWS (C and Fortran)

Purpose	Determine whether mxArray was copied from MATLAB global workspace
C Syntax	<pre>#include "matrix.h" bool mxIsFromGlobalWS(const mxArray *pm);</pre>
Fortran Syntax	<pre>integer*4 mxIsFromGlobalWS(pm) mwPointer pm</pre>
Arguments	pm Pointer to an mxArray
Returns	Logical 1 (true) if the array was copied out of the global workspace, and logical 0 (false) otherwise.
Description	mxIsFromGlobalWS is useful for stand alone MAT programs. mexIsGlobal tells you whether the pointer you pass actually points into the global workspace.
C Examples	See matdgn.c and matcreat.c in the eng_mat subdirectory of the examples directory.
See Also	mexIsGlobal

Purpose	Determine whether input is infinite
C Syntax	<pre>#include "matrix.h" bool mxIsInf(double value);</pre>
Fortran Syntax	<pre>integer*4 mxIsInf(value) real*8 value</pre>
Arguments	<p>value</p> <p>The double-precision, floating-point number that you are testing</p>
Returns	Logical 1 (true) if value is infinite, and logical 0 (false) otherwise.
Description	<p>Call <code>mxIsInf</code> to determine whether or not <code>value</code> is equal to infinity or minus infinity. MATLAB software stores the value of infinity in a permanent variable named <code>Inf</code>, which represents IEEE arithmetic positive infinity. The value of the variable <code>Inf</code> is built into the system; you cannot modify it.</p> <p>Operations that return infinity include</p> <ul style="list-style-type: none">• Division by 0. For example, <code>5/0</code> returns infinity.• Operations resulting in overflow. For example, <code>exp(10000)</code> returns infinity because the result is too large to be represented on your machine. <p>If <code>value</code> equals NaN (Not-a-Number), <code>mxIsInf</code> returns false. In other words, NaN is not equal to infinity.</p>
C Examples	See <code>mxisfinite.c</code> in the <code>mx</code> subdirectory of the <code>examples</code> directory.
See Also	<code>mxIsFinite</code> , <code>mxIsNaN</code>

mxIsInt16 (C and Fortran)

Purpose Determine whether mxArray represents data as signed 16-bit integers

C Syntax

```
#include "matrix.h"
bool mxIsInt16(const mxArray *pm);
```

Fortran Syntax

```
integer*4 mxIsInt16(pm)
mwPointer pm
```

Arguments

pm
 Pointer to an mxArray

Returns Logical 1 (true) if the array stores its data as signed 16-bit integers, and logical 0 (false) otherwise.

Description Use mxIsInt16 to determine whether or not the specified array represents its real and imaginary data as 16-bit signed integers.

In C, calling mxIsInt16 is equivalent to calling:

```
mxGetClassID(pm) == mxINT16_CLASS
```

In Fortran, calling mxIsInt16 is equivalent to calling:

```
mxGetClassName(pm) == 'int16'
```

See Also mxIsClass, mxGetClassID, mxIsInt8, mxIsInt32, mxIsInt64, mxIsUInt8, mxIsUInt16, mxIsUInt32, mxIsUInt64

Purpose Determine whether mxArray represents data as signed 32-bit integers

C Syntax

```
#include "matrix.h"
bool mxIsInt32(const mxArray *pm);
```

Fortran Syntax

```
integer*4 mxIsInt32(pm)
mwPointer pm
```

Arguments

pm
 Pointer to an mxArray

Returns Logical 1 (true) if the array stores its data as signed 32-bit integers, and logical 0 (false) otherwise.

Description Use mxIsInt32 to determine whether or not the specified array represents its real and imaginary data as 32-bit signed integers.

In C, calling mxIsInt32 is equivalent to calling:

```
mxGetClassID(pm) == mxINT32_CLASS
```

In Fortran, calling mxIsInt32 is equivalent to calling:

```
mxGetClassName(pm) == 'int32'
```

See Also mxIsClass, mxGetClassID, mxIsInt8, mxIsInt16, mxIsInt64, mxIsUint8, mxIsUint16, mxIsUint32, mxIsUint64

mxIsInt64 (C and Fortran)

Purpose Determine whether mxArray represents data as signed 64-bit integers

C Syntax

```
#include "matrix.h"
bool mxIsInt64(const mxArray *pm);
```

Fortran Syntax

```
integer*4 mxIsInt64(pm)
mwPointer pm
```

Arguments pm
Pointer to an mxArray

Returns Logical 1 (true) if the array stores its data as signed 64-bit integers, and logical 0 (false) otherwise.

Description Use mxIsInt64 to determine whether or not the specified array represents its real and imaginary data as 64-bit signed integers.

In C, calling mxIsInt64 is equivalent to calling:

```
mxGetClassID(pm) == mxINT64_CLASS
```

In Fortran, calling mxIsInt64 is equivalent to calling:

```
mxGetClassName(pm) == 'int64'
```

See Also mxIsClass, mxGetClassID, mxIsInt8, mxIsInt16, mxIsInt32, mxIsUint8, mxIsUint16, mxIsUint32, mxIsUint64

Purpose Determine whether mxArray represents data as signed 8-bit integers

C Syntax

```
#include "matrix.h"
bool mxIsInt8(const mxArray *pm);
```

Fortran Syntax

```
integer*4 mxIsInt8(pm)
mwPointer pm
```

Arguments

pm
 Pointer to an mxArray

Returns Logical 1 (true) if the array stores its data as signed 8-bit integers, and logical 0 (false) otherwise.

Description Use mxIsInt8 to determine whether or not the specified array represents its real and imaginary data as 8-bit signed integers.

In C, calling mxIsInt8 is equivalent to calling:

```
mxGetClassID(pm) == mxINT8_CLASS
```

In Fortran, calling mxIsInt8 is equivalent to calling:

```
mxGetClassName(pm) .eq. 'int8'
```

See Also mxIsClass, mxGetClassID, mxIsInt16, mxIsInt32, mxIsInt64, mxIsUInt8, mxIsUInt16, mxIsUInt32, mxIsUInt64

mxIsLogical (C and Fortran)

Purpose	Determine whether mxArray is of type mxLogical
C Syntax	<pre>#include "matrix.h" bool mxIsLogical(const mxArray *pm);</pre>
Fortran Syntax	<pre>integer*4 mxIsLogical(pm) mwPointer pm</pre>
Arguments	pm Pointer to an mxArray
Returns	Logical 1 (true) if pm points to a logical mxArray, and logical 0 (false) otherwise.
Description	Use mxIsLogical to determine whether MATLAB software treats the data in the mxArray as Boolean (logical). If an mxArray is logical, MATLAB treats all zeros as meaning false and all nonzero values as meaning true. For additional information on the use of logical variables in MATLAB software, type help logical at the MATLAB prompt.
C Examples	See mxislogical.c in the mx subdirectory of the examples directory.
See Also	mxIsClass

Purpose	Determine whether scalar mxArray is of type mxLogical
C Syntax	<pre>#include "matrix.h" bool mxIsLogicalScalar(const mxArray *array_ptr);</pre>
Arguments	array_ptr Pointer to an mxArray
Returns	Logical 1 (true) if the mxArray is of class mxLogical and has 1-by-1 dimensions, and logical 0 (false) otherwise.
Description	<p>Use mxIsLogicalScalar to determine whether MATLAB software treats the scalar data in the mxArray as logical or numerical. For additional information on the use of logical variables in MATLAB software, type <code>help logical</code> at the MATLAB prompt.</p> <p>mxIsLogicalScalar(pa) is equivalent to:</p> <pre>mxIsLogical(pa) && mxGetNumberOfElements(pa) == 1</pre>
See Also	mxIsLogical, mxIsLogicalScalarTrue, mxGetLogicals, mxGetScalar

mxIsLogicalScalarTrue (C)

Purpose	Determine whether scalar mxArray of type mxLogical is true
C Syntax	<pre>#include "matrix.h" bool mxIsLogicalScalarTrue(const mxArray *array_ptr);</pre>
Arguments	array_ptr Pointer to an mxArray
Returns	Logical 1 (true) if the value of the mxArray's logical, scalar element is true, and logical 0 (false) otherwise.
Description	<p>Use mxIsLogicalScalarTrue to determine whether the value of a scalar mxArray is true or false. For additional information on the use of logical variables in MATLAB software, type <code>help logical</code> at the MATLAB prompt.</p> <p>mxIsLogicalScalarTrue(pa) is equivalent to:</p> <pre>mxIsLogical(pa) && mxGetNumberOfElements(pa) == 1 && mxGetLogicals(pa)[0] == true</pre>
See Also	mxIsLogical, mxIsLogicalScalar, mxGetLogicals, mxGetScalar

Purpose	Determine whether input is NaN (Not-a-Number)
C Syntax	<pre>#include "matrix.h" bool mxIsNaN(double value);</pre>
Fortran Syntax	<pre>integer*4 mxIsNaN(value) real*8 value</pre>
Arguments	<p>value</p> <p>The double-precision, floating-point number that you are testing</p>
Returns	Logical 1 (true) if value is NaN (Not-a-Number), and logical 0 (false) otherwise.
Description	<p>Call <code>mxIsNaN</code> to determine whether or not <code>value</code> is NaN. NaN is the IEEE arithmetic representation for Not-a-Number. A NaN is obtained as a result of mathematically undefined operations such as</p> <ul style="list-style-type: none">• <code>0.0/0.0</code>• <code>Inf - Inf</code> <p>The system understands a family of bit patterns as representing NaN. In other words, NaN is not a single value; rather, it is a family of numbers that MATLAB software (and other IEEE-compliant applications) uses to represent an error condition or missing data.</p>
C Examples	<p>See <code>mxIsFinite.c</code> in the <code>mx</code> subdirectory of the <code>examples</code> directory.</p> <p>For additional examples, see <code>findnz.c</code> and <code>fulltosparse.c</code> in the <code>refbook</code> subdirectory of the <code>examples</code> directory.</p>
See Also	<code>mxIsFinite</code> , <code>mxIsInf</code>

mxIsNumeric (C and Fortran)

Purpose	Determine whether mxArray is numeric
C Syntax	<pre>#include "matrix.h" bool mxIsNumeric(const mxArray *pm);</pre>
Fortran Syntax	<pre>integer*4 mxIsNumeric(pm) mwPointer pm</pre>
Arguments	pm Pointer to an mxArray
Returns	Logical 1 (true) if the array can contain numeric data. The following class IDs represent storage types for arrays that can contain numeric data: <ul style="list-style-type: none">• mxDOUBLE_CLASS• mxSINGLE_CLASS• mxINT8_CLASS• mxUINT8_CLASS• mxINT16_CLASS• mxUINT16_CLASS• mxINT32_CLASS• mxUINT32_CLASS• mxINT64_CLASS• mxUINT64_CLASS Logical 0 (false) if the array cannot contain numeric data.
Description	Call mxIsNumeric to determine whether the specified array contains numeric data. If the specified array has a storage type that represents

numeric data, `mxIsNumeric` returns logical 1 (true). Otherwise, `mxIsNumeric` returns logical 0 (false).

Call `mxGetClassID` to determine the exact storage type.

C Examples

See `phonebook.c` in the `refbook` subdirectory of the `examples` directory.

Fortran Examples

See `matdemo1.F` in the `eng_mat` subdirectory of the `examples` directory.

See Also

`mxGetClassID`

mxIsSingle (C and Fortran)

Purpose	Determine whether mxArray represents data as single-precision, floating-point numbers
C Syntax	<pre>#include "matrix.h" bool mxIsSingle(const mxArray *pm);</pre>
Fortran Syntax	<pre>integer*4 mxIsSingle(pm) mwPointer pm</pre>
Arguments	pm Pointer to an mxArray
Returns	Logical 1 (true) if the array stores its data as single-precision, floating-point numbers, and logical 0 (false) otherwise.
Description	<p>Use <code>mxIsSingle</code> to determine whether or not the specified array represents its real and imaginary data as single-precision, floating-point numbers.</p> <p>In C, calling <code>mxIsSingle</code> is equivalent to calling:</p> <pre>mxGetClassID(pm) == mxSINGLE_CLASS</pre> <p>In Fortran, calling <code>mxIsSingle</code> is equivalent to calling:</p> <pre>mxGetClassName(pm) .eq. 'single'</pre>
See Also	<code>mxIsClass</code> , <code>mxGetClassID</code>

Purpose	Determine whether input is sparse mxArray
C Syntax	<pre>#include "matrix.h" bool mxIsSparse(const mxArray *pm);</pre>
Fortran Syntax	<pre>integer*4 mxIsSparse(pm) mwPointer pm</pre>
Arguments	<p>pm Pointer to an mxArray</p>
Returns	Logical 1 (true) if pm points to a sparse mxArray, and logical 0 (false) otherwise. A false return value means that pm points to a full mxArray or that pm does not point to a legal mxArray.
Description	Use mxIsSparse to determine whether pm points to a sparse mxArray. Many routines (for example, mxGetIr and mxGetJc) require a sparse mxArray as input.
C Examples	See phonebook.c in the refbook subdirectory of the examples directory. For additional examples, see mxgetnzmax.c, mxsetdimensions.c, and mxsetnzmax.c in the mx subdirectory of the examples directory.
See Also	mxGetIr, mxGetJc, mxCreateSparse

mxIsStruct (C and Fortran)

Purpose	Determine whether input is structure mxArray
C Syntax	<pre>#include "matrix.h" bool mxIsStruct(const mxArray *pm);</pre>
Fortran Syntax	<pre>integer*4 mxIsStruct(pm) mwPointer pm</pre>
Arguments	pm Pointer to an mxArray
Returns	Logical 1 (true) if pm points to a structure mxArray, and logical 0 (false) otherwise.
Description	Use mxIsStruct to determine whether pm points to a structure mxArray. Many routines (for example, mxGetFieldName and mxSetField) require a structure mxArray as an argument.
C Examples	See phonebook.c in the refbook subdirectory of the examples directory.
See Also	mxCreateStructArray, mxCreateStructMatrix, mxGetNumberOfFields, mxGetField, mxSetField

Purpose Determine whether mxArray represents data as unsigned 16-bit integers

C Syntax

```
#include "matrix.h"
bool mxIsUint16(const mxArray *pm);
```

Fortran Syntax

```
integer*4 mxIsUint16(pm)
mwPointer pm
```

Arguments

pm
 Pointer to an mxArray

Returns Logical 1 (true) if the mxArray stores its data as unsigned 16-bit integers, and logical 0 (false) otherwise.

Description Use mxIsUint16 to determine whether or not the specified mxArray represents its real and imaginary data as 16-bit unsigned integers.

In C, calling mxIsUint16 is equivalent to calling:

```
mxGetClassID(pm) == mxUINT16_CLASS
```

In Fortran, calling mxIsUint16 is equivalent to calling:

```
mxGetClassName(pm) .eq. 'uint16'
```

See Also mxIsClass, mxGetClassID, mxIsInt8, mxIsInt16, mxIsInt32, mxIsInt64, mxIsUint8, mxIsUint32, mxIsUint64

mxIsUint32 (C and Fortran)

Purpose Determine whether mxArray represents data as unsigned 32-bit integers

C Syntax

```
#include "matrix.h"
bool mxIsUint32(const mxArray *pm);
```

Fortran Syntax

```
integer*4 mxIsUint32(pm)
mwPointer pm
```

Arguments

pm
 Pointer to an mxArray

Returns Logical 1 (true) if the mxArray stores its data as unsigned 32-bit integers, and logical 0 (false) otherwise.

Description Use mxIsUint32 to determine whether or not the specified mxArray represents its real and imaginary data as 32-bit unsigned integers.

In C, calling mxIsUint32 is equivalent to calling:

```
mxGetClassID(pm) == mxUINT32_CLASS
```

In Fortran, calling mxIsUint32 is equivalent to calling:

```
mxGetClassName(pm) .eq. 'uint32'
```

See Also mxIsClass, mxGetClassID, mxIsInt8, mxIsInt16, mxIsInt32, mxIsInt64, mxIsUint8, mxIsUint16, mxIsUint64

Purpose Determine whether mxArray represents data as unsigned 64-bit integers

C Syntax

```
#include "matrix.h"
bool mxIsUint64(const mxArray *pm);
```

Fortran Syntax

```
integer*4 mxIsUint64(pm)
mwPointer pm
```

Arguments

pm
 Pointer to an mxArray

Returns Logical 1 (true) if the mxArray stores its data as unsigned 64-bit integers, and logical 0 (false) otherwise.

Description Use mxIsUint64 to determine whether or not the specified mxArray represents its real and imaginary data as 64-bit unsigned integers.

In C, calling mxIsUint64 is equivalent to calling:

```
mxGetClassID(pm) == mxUINT64_CLASS
```

In Fortran, calling mxIsUint64 is equivalent to calling:

```
mxGetClassName(pm) .eq. 'uint64'
```

See Also mxIsClass, mxGetClassID, mxIsInt8, mxIsInt16, mxIsInt32, mxIsInt64, mxIsUint8, mxIsUint16, mxIsUint32

mxIsUint8 (C and Fortran)

Purpose Determine whether mxArray represents data as unsigned 8-bit integers

C Syntax

```
#include "matrix.h"
bool mxIsUint8(const mxArray *pm);
```

Fortran Syntax

```
integer*4 mxIsUint8(pm)
mwPointer pm
```

Arguments

pm
 Pointer to an mxArray

Returns Logical 1 (true) if the mxArray stores its data as unsigned 8-bit integers, and logical 0 (false) otherwise.

Description Use mxIsUint8 to determine whether or not the specified mxArray represents its real and imaginary data as 8-bit unsigned integers.

In C, calling mxIsUint8 is equivalent to calling:

```
mxGetClassID(pm) == mxUINT8_CLASS
```

In Fortran, calling mxIsUint8 is equivalent to calling:

```
mxGetClassName(pm) .eq. 'uint8'
```

See Also mxIsClass, mxGetClassID, mxIsInt8, mxIsInt16, mxIsInt32, mxIsInt64, mxIsUint16, mxIsUint32, mxIsUint64

Purpose Type for logical mxArray

Description All logical mxArrays store their data elements as mxLogical rather than as bool.

The header file containing this type is:

```
#include "matrix.h"
```

Examples See mxislogical.c in the mx subdirectory of the examples directory.

See Also mxCreateLogicalArray

mxMalloc (C and Fortran)

Purpose	Allocate dynamic memory using MATLAB memory manager
C Syntax	<pre>#include "matrix.h" #include <stdlib.h> void *mxMalloc(mwSize n);</pre>
Fortran Syntax	<pre>mwPointer mxMalloc(n) mwSize n</pre>
Arguments	n Number of bytes to allocate
Returns	A pointer to the start of the allocated dynamic memory, if successful. If unsuccessful in a stand alone (non-MEX-file) application, <code>mxMalloc</code> returns NULL in C (0 in Fortran). If unsuccessful in a MEX-file, the MEX-file terminates and control returns to the MATLAB prompt. <code>mxMalloc</code> is unsuccessful when there is insufficient free heap space.
Description	<p>MATLAB applications should always call <code>mxMalloc</code> rather than <code>malloc</code> to allocate memory.</p> <p><code>mxMalloc</code> works differently in MEX-files than in stand alone MATLAB applications. In MEX-files, <code>mxMalloc</code> automatically</p> <ul style="list-style-type: none">• Allocates enough contiguous heap space to hold <code>n</code> bytes.• Registers the returned heap space with the MATLAB memory manager. <p>The MATLAB memory manager maintains a list of all memory allocated by <code>mxMalloc</code>. The MATLAB memory manager automatically frees (deallocates) all MEX-file parcels when control returns to the MATLAB prompt.</p> <p>In stand alone MATLAB C applications, <code>mxMalloc</code> calls the ANSI C <code>malloc</code> function.</p>

By default, in a MEX-file, `mxMalloc` generates nonpersistent `mxMalloc` data. In other words, the memory manager automatically deallocates the memory as soon as the MEX-file ends. If you want the memory to persist after the MEX-file completes, call `mexMakeMemoryPersistent` after calling `mxMalloc`. If you write a MEX-file with persistent memory, be sure to register a `mexAtExit` function to free allocated memory in the event your MEX-file is cleared.

When you finish using the memory allocated by `mxMalloc`, call `mxFree` to deallocate the memory.

C Examples

See `mxmalloc.c` in the `mx` subdirectory of the `examples` directory. For an additional example, see `mxsetdimensions.c` in the `mx` subdirectory of the `examples` directory.

See Also

`mexAtExit`, `mexMakeArrayPersistent`, `mexMakeMemoryPersistent`, `mxCalloc`, `mxDestroyArray`, `mxFree`, `mxRealloc`

mxRealloc (C and Fortran)

Purpose	Reallocate memory
C Syntax	<pre>#include "matrix.h" #include <stdlib.h> void *mxRealloc(void *ptr, mwSize size);</pre>
Fortran Syntax	<pre>mwPointer mxRealloc(ptr, size) mwPointer ptr mwSize size</pre>
Arguments	<p>ptr Pointer to a block of memory allocated by <code>mxMalloc</code>, <code>mxRealloc</code>, or <code>mxRealloc</code></p> <p>size New size of allocated memory, in bytes</p>
Returns	A pointer to the reallocated block of memory, or NULL in C (0 in Fortran) if <code>size</code> is 0. In a stand alone (non-MEX-file) application, if not enough memory is available to expand the block to the given size, <code>mxRealloc</code> returns NULL in C (0 in Fortran). In a MEX-file, if not enough memory is available to expand the block to the given size, the MEX-file terminates and control returns to the MATLAB prompt.
Description	<p><code>mxRealloc</code> changes the size of a memory block that has been allocated with <code>mxMalloc</code>, <code>mxRealloc</code>, or <code>mxRealloc</code>.</p> <p>If <code>size</code> is 0 and <code>ptr</code> is not NULL in C (0 in Fortran), <code>mxRealloc</code> frees the memory pointed to by <code>ptr</code> and returns NULL in C (0 in Fortran).</p> <p>If <code>size</code> is greater than 0 and <code>ptr</code> is NULL in C (0 in Fortran), <code>mxRealloc</code> behaves like <code>mxMalloc</code>, allocating a new block of memory of <code>size</code> bytes and returning a pointer to the new block.</p> <p>Otherwise, <code>mxRealloc</code> changes the size of the memory block pointed to by <code>ptr</code> to <code>size</code> bytes. The contents of the reallocated memory are unchanged up to the smaller of the new and old sizes. The reallocated memory may be in a different location from the original memory, so</p>

the returned pointer can be different from `ptr`. If the memory location changes, `mxRealloc` frees the original memory block pointed to by `ptr`.

In a stand alone (non-MEX-file) application, if not enough memory is available to expand the block to the given size, `mxRealloc` returns `NULL` in C (0 in Fortran) and leaves the original memory block unchanged. You must use `mxFree` to free the original memory block.

MATLAB maintains a list of all memory allocated by `mxRealloc`. By default, in a MEX-file, `mxRealloc` generates nonpersistent `mxRealloc` data. The memory management facility automatically deallocates the memory as soon as the MEX-file ends.

If you want the memory to persist after a MEX-file completes, call `mexMakeMemoryPersistent` after calling `mxRealloc`. If you write a MEX-file with persistent memory, be sure to register a `mexAtExit` function to free allocated memory when your MEX-file is cleared.

When you finish using the memory allocated by `mxRealloc`, call `mxFree`. `mxFree` deallocates the memory.

C **Examples**

See `mxsetnzmax.c` in the `mx` subdirectory of the `examples` directory.

See Also

`mexAtExit`, `mexMakeArrayPersistent`, `mexMakeMemoryPersistent`, `mxCalloc`, `mxDestroyArray`, `mxFree`, `mxMalloc`

mxRemoveField (C and Fortran)

Purpose Remove field from structure array

C Syntax

```
#include "matrix.h"
void mxRemoveField(mxArray *pm, int fieldnumber);
```

Fortran Syntax

```
subroutine mxRemoveField(pm, fieldnumber)
mwPointer pm
integer*4 fieldnumber
```

Arguments

pm
Pointer to a structure mxArray

fieldnumber
Number of the field you want to remove. In C, to remove the first field, set `fieldnumber` to 0; to remove the second field, set `fieldnumber` to 1; and so on. In Fortran, to remove the first field, set `fieldnumber` to 1; to remove the second field, set `fieldnumber` to 2; and so on.

Description Call `mxRemoveField` to remove a field from a structure array. If the field does not exist, nothing happens. This function does not destroy the field values. Use `mxDestroyArray` to destroy the actual field values.

Consider a MATLAB structure initialized to:

```
patient.name = 'John Doe';
patient.billing = 127.00;
patient.test = [79 75 73; 180 178 177.5; 220 210 205];
```

In C, the field number 0 represents the field name; field number 1 represents field `billing`; field number 2 represents field `test`. In Fortran, the field number 1 represents the field name; field number 2 represents field `billing`; field number 3 represents field `test`.

See Also `mxAddField`, `mxDestroyArray`, `mxGetFieldByNumber`

Purpose Set value of one cell of mxArray

C Syntax

```
#include "matrix.h"
void mxSetCell(mxArray *pm, mwIndex index, mxArray *value);
```

Fortran Syntax

```
mxSetCell(pm, index, value)
mwPointer pm, value
mwIndex index
```

Arguments

pm
Pointer to a cell mxArray

index
Index from the beginning of the mxArray. Specify the number of elements between the first cell of the mxArray and the cell you want to set. The easiest way to calculate index in a multidimensional cell array is to call mxCalcSingleSubscript.

value
The new value of the cell. You can put any kind of mxArray into a cell. In fact, you can even put another cell mxArray into a cell.

Description Call mxSetCell to put the designated value into a particular cell of a cell mxArray.

Note Inputs to a MEX-file are constant read-only mxArrays and should not be modified. Using mxSetCell* or mxSetField* to modify the cells or fields of a MATLAB argument causes unpredictable results.

This function does not free any memory allocated for existing data that it displaces. To free existing memory, call mxDestroyArray on the pointer returned by mxGetCell before you call mxSetCell.

mxSetCell (C and Fortran)

C Examples

See `phonebook.c` in the `refbook` subdirectory of the `examples` directory. For an additional example, see `mxcreatecellmatrix.c` in the `mx` subdirectory of the `examples` directory.

See Also

`mxCreateCellArray`, `mxCreateCellMatrix`, `mxGetCell`, `mxIsCell`, `mxDestroyArray`

Purpose	Convert structure array to MATLAB object array
C Syntax	<pre>#include "matrix.h" int mxSetClassName(mxArray *array_ptr, const char *classname);</pre>
Arguments	<p><code>array_ptr</code> Pointer to an mxArray of class mxSTRUCT_CLASS</p> <p><code>classname</code> The object class to which to convert array_ptr</p>
Returns	0 if successful, and nonzero otherwise. One cause of failure is that array_ptr is not a structure mxArray. Call mxIsStruct to determine whether array_ptr is a structure.
Description	mxSetClassName converts a structure array to an object array, to be saved subsequently to a MAT-file. The object is not registered or validated by MATLAB software until it is loaded via the LOAD command. If the specified classname is an undefined class within MATLAB, LOAD converts the object back to a simple structure array.
See Also	mxIsClass, mxGetClassID

mxSetData (C and Fortran)

Purpose Set pointer to data

C Syntax

```
#include "matrix.h"  
void mxSetData(mxArray *pm, void *pr);
```

Fortran Syntax

```
mxSetData(pm, pr)  
mwPointer pm, pr
```

Arguments

pm
Pointer to an mxArray

pr
Pointer to an array. Each element in the array contains the real component of a value. The array must be in dynamic memory; call mxCalloc to allocate this memory.

Description mxSetData is similar to mxSetPr, except that in C, its second argument is a void *. Use this on numeric arrays with contents other than double.

This function does not free any memory allocated for existing data that it displaces. To free existing memory, call mxFree on the pointer returned by mxGetData before you call mxSetData.

See Also mxCalloc, mxFree, mxGetData, mxSetPr

mxSetDimensions (C and Fortran)

Purpose	Modify number of dimensions and size of each dimension
C Syntax	<pre>#include "matrix.h" int mxSetDimensions(mxArray *pm, const mwSize *dims, mwSize ndim);</pre>
Fortran Syntax	<pre>integer*4 mxSetDimensions(pm, dims, ndim) mwPointer pm mwSize dims, ndim</pre>
Arguments	<p><code>pm</code> Pointer to an mxArray</p> <p><code>dims</code> The dimensions array. Each element in the dimensions array contains the size of the array in that dimension. For example, in C, setting <code>dims[0]</code> to 5 and <code>dims[1]</code> to 7 establishes a 5-by-7 mxArray. In Fortran, setting <code>dims(1)</code> to 5 and <code>dims(2)</code> to 7 establishes a 5-by-7 mxArray. In most cases, there should be <code>ndim</code> elements in the <code>dims</code> array.</p> <p><code>ndim</code> The desired number of dimensions</p>
Returns	0 on success, and 1 on failure. <code>mxSetDimensions</code> allocates heap space to hold the input size array. So it is possible (though extremely unlikely) that increasing the number of dimensions can cause the system to run out of heap space.
Description	<p>Call <code>mxSetDimensions</code> to reshape an existing mxArray. <code>mxSetDimensions</code> is similar to <code>mxSetM</code> and <code>mxSetN</code>; however, <code>mxSetDimensions</code> provides greater control for reshaping mxArrays that have more than two dimensions.</p> <p><code>mxSetDimensions</code> does not allocate or deallocate any space for the <code>pr</code> or <code>pi</code> arrays. Consequently, if your call to <code>mxSetDimensions</code> increases the number of elements in the mxArray, you must enlarge the <code>pr</code> (and <code>pi</code>, if it exists) arrays accordingly.</p>

mxSetDimensions (C and Fortran)

If your call to `mxSetDimensions` reduces the number of elements in the `mxArray`, you can optionally reduce the size of the `pr` and `pi` arrays using `mxRealloc`.

Any trailing singleton dimensions specified in the `dims` argument are automatically removed from the resulting array. For example, if `ndim` equals 5 and `dims` equals `[4 1 7 1 1]`, the resulting array is given the dimensions 4-by-1-by-7.

C Examples

See `mxsetdimensions.c` in the `mx` subdirectory of the `examples` directory.

See Also

`mxGetNumberOfDimensions`, `mxSetM`, `mxSetN`, `mxRealloc`

Purpose

Set structure array field, given field name and index

C Syntax

```
#include "matrix.h"
void mxSetField(mxArray *pm, mwIndex index,
    const char *fieldname, mxArray *value);
```

**Fortran
Syntax**

```
mxSetField(pm, index, fieldname, value)
mwPointer pm, value
mwIndex index
character*(*) fieldname
```

Arguments

pm

Pointer to a structure mxArray. Call `mxIsStruct` to determine whether pm points to a structure mxArray.

index

Index of the desired element.

In C, the first element of an mxArray has an index of 0, the second element has an index of 1, and the last element has an index of N-1, where N is the total number of elements in the mxArray.

In Fortran, the first element of an mxArray has an index of 1, the second element has an index of 2, and the last element has an index of N, where N is the total number of elements in the mxArray.

See `mxCalcSingleSubscript` for details on calculating an index.

fieldname

The name of the field whose value you are assigning. Call `mxGetFieldNameByNumber` or `mxGetFieldNumber` to determine existing field names.

value

Pointer to the mxArray you are assigning.

mxSetField (C and Fortran)

Description

Use `mxSetField` to assign a value to the specified element of the specified field. In pseudo-C terminology, `mxSetField` performs the assignment:

```
pm[index].fieldname = value;
```

Note Inputs to a MEX-file are constant read-only `mxArrays` and should not be modified. Using `mxSetCell*` or `mxSetField*` to modify the cells or fields of a MATLAB argument causes unpredictable results.

In C, calling:

```
mxSetField(pa, index, "fieldname", new_value_pa);
```

is equivalent to calling:

```
field_num = mxGetFieldNumber(pa, "fieldname");  
mxSetFieldByNumber(pa, index, field_num, new_value_pa);
```

In Fortran, calling:

```
mxSetField(pm, index, 'fieldname', newvalue)
```

is equivalent to calling:

```
fieldnum = mxGetFieldNumber(pm, 'fieldname')  
mxSetFieldByNumber(pm, index, fieldnum, newvalue)
```

This function does not free any memory allocated for existing data that it displaces. To free existing memory, call `mxDestroyArray` on the pointer returned by `mxGetField` before you call `mxSetField`.

To free memory for structures created using `mxSetField`, call `mxDestroyArray` only on the structure array, not the array used by `mxSetField`. If you also call `mxDestroyArray` on the `mxArray` value points to, the same memory is freed twice and this can corrupt memory.

C Examples

See `mxcreatestructarray.c` in the `mx` subdirectory of the examples directory.

See Also

`mxCreateStructArray`, `mxCreateStructMatrix`, `mxGetField`,
`mxGetFieldByNumber`, `mxGetFieldNameByNumber`, `mxGetFieldNumber`,
`mxGetNumberOfFields`, `mxIsStruct`, `mxSetFieldByNumber`,
`mxDestroyArray`

mxSetFieldByNumber (C and Fortran)

Purpose Set structure array field, given field number and index

C Syntax

```
#include "matrix.h"
void mxSetFieldByNumber(mxArray *pm, mwIndex index,
    int fieldnumber, mxArray *value);
```

Fortran Syntax

```
mxSetFieldByNumber(pm, index, fieldnumber, value)
mwPointer pm, value
mwIndex index
integer*4 fieldnumber
```

Arguments

pm
Pointer to a structure mxArray. Call `mxIsStruct` to determine whether `pm` points to a structure mxArray.

index
Index of the desired element.

In C, the first element of an mxArray has an index of 0, the second element has an index of 1, and the last element has an index of N-1, where N is the total number of elements in the mxArray.

In Fortran, the first element of an mxArray has an index of 1, the second element has an index of 2, and the last element has an index of N, where N is the total number of elements in the mxArray.

See `mxCalcSingleSubscript` for details on calculating an index.

fieldnumber
Position of the field whose value you want to set.

In C, the first field within each element has a `fieldnumber` of 0, the second field has a `fieldnumber` of 1, and so on. The last field has a `fieldnumber` of N-1, where N is the number of fields.

mxSetFieldByNumber (C and Fortran)

In Fortran, the first field within each element has a `fieldnumber` of 1, the second field has a `fieldnumber` of 2, and so on. The last field has a `fieldnumber` of N.

`value`

Pointer to the `mxArray` you are assigning.

Description

Use `mxSetFieldByNumber` to assign a `value` to the specified element of the specified field. `mxSetFieldByNumber` is almost identical to `mxSetField`; however, the former takes a field number as its third argument and the latter takes a field name as its third argument.

Note Inputs to a MEX-file are constant read-only `mxArrays` and should not be modified. Using `mxSetCell*` or `mxSetField*` to modify the cells or fields of a MATLAB argument causes unpredictable results.

In C, calling:

```
mxSetField(pa, index, "field_name", new_value_pa);
```

is equivalent to calling:

```
field_num = mxGetFieldNumber(pa, "field_name");
mxSetFieldByNumber(pa, index, field_num, new_value_pa);
```

In Fortran, calling:

```
mxSetField(pm, index, 'fieldname', newvalue)
```

is equivalent to calling:

```
fieldnum = mxGetFieldNumber(pm, 'fieldname')
mxSetFieldByNumber(pm, index, fieldnum, newvalue)
```

This function does not free any memory allocated for existing data that it displaces. To free existing memory, call `mxDestroyArray` on the pointer returned by `mxGetFieldByNumber` before you call `mxSetFieldByNumber`.

mxSetFieldByNumber (C and Fortran)

To free memory for structures created using `mxSetFieldByNumber`, call `mxDestroyArray` only on the structure array, not the array used by `mxSetFieldByNumber`. If you also call `mxDestroyArray` on the `mxArray` value points to, the same memory is freed twice and this can corrupt memory.

C Examples

See `mxcreatestructarray.c` in the `mx` subdirectory of the `examples` directory. For an additional example, see `phonebook.c` in the `refbook` subdirectory of the `examples` directory.

See Also

`mxCreateStructArray`, `mxCreateStructMatrix`, `mxGetField`,
`mxGetFieldByNumber`, `mxGetFieldNameByNumber`, `mxGetFieldNumber`,
`mxGetNumberOfFields`, `mxIsStruct`, `mxSetField`, `mxDestroyArray`

Purpose	Set imaginary data pointer for mxArray
C Syntax	<pre>#include "matrix.h" void mxSetImagData(mxArray *pm, void *pi);</pre>
Fortran Syntax	<pre>mxSetImagData(pm, pi) mwPointer pm, pi</pre>
Arguments	<p>pm Pointer to an mxArray</p> <p>pi Pointer to the first element of an array. Each element in the array contains the imaginary component of a value. The array must be in dynamic memory; call <code>mxMalloc</code> to allocate this dynamic memory. If <code>pi</code> points to static memory, memory errors will result when the array is destroyed.</p>
Description	<p><code>mxSetImagData</code> is similar to <code>mxSetPi</code>, except that in C, its <code>pi</code> argument is a <code>void *</code>. Use this on numeric arrays with contents other than <code>double</code>.</p> <p>This function does not free any memory allocated for existing data that it displaces. To free existing memory, call <code>mxFree</code> on the pointer returned by <code>mxGetImagData</code> before you call <code>mxSetImagData</code>.</p>
C Examples	See <code>mxisfinite.c</code> in the <code>mx</code> subdirectory of the <code>examples</code> directory.
See Also	<code>mxMalloc</code> , <code>mxFree</code> , <code>mxGetImagData</code> , <code>mxSetPi</code>

mxSetIr (C and Fortran)

Purpose	Set <code>ir</code> array of sparse <code>mxArray</code>
C Syntax	<pre>#include "matrix.h" void mxSetIr(mxArray *pm, mwIndex *ir);</pre>
Fortran Syntax	<pre>mxSetIr(pm, ir) mwPointer pm, ir</pre>
Arguments	<p><code>pm</code> Pointer to a sparse <code>mxArray</code></p> <p><code>ir</code> Pointer to the <code>ir</code> array. The <code>ir</code> array must be sorted in column-major order.</p>
Description	<p>Use <code>mxSetIr</code> to specify the <code>ir</code> array of a sparse <code>mxArray</code>. The <code>ir</code> array is an array of integers; the length of the <code>ir</code> array should equal the value of <code>nzmax</code>.</p> <p>Each element in the <code>ir</code> array indicates a row (offset by 1) at which a nonzero element can be found. (The <code>jc</code> array is an index that indirectly specifies a column where nonzero elements can be found. See <code>mxSetJc</code> for more details on <code>jc</code>.)</p> <p>For example, suppose you create a 7-by-3 sparse <code>mxArray</code> named <code>Sparrow</code> containing six nonzero elements by typing:</p> <pre>Sparrow = zeros(7,3); Sparrow(2,1) = 1; Sparrow(5,1) = 1; Sparrow(3,2) = 1; Sparrow(2,3) = 2; Sparrow(5,3) = 1; Sparrow(6,3) = 1; Sparrow = sparse(Sparrow);</pre>

The `pr` array holds the real data for the sparse matrix, which in Sparrow is the five 1s and the one 2. If there is any nonzero imaginary data, it is in a `pi` array.

Subscript	ir	pr	jc	Comments
(2,1)	1	1	0	Column 1; ir is 1 because row is 2.
(5,1)	4	1	2	Column 1; ir is 4 because row is 5.
(3,2)	2	1	3	Column 2; ir is 2 because row is 3.
(2,3)	1	2	6	Column 3; ir is 1 because row is 2.
(5,3)	4	1		Column 3; ir is 4 because row is 5.
(6,3)	5	1		Column 3; ir is 5 because row is 6.

Notice how each element of the `ir` array is always 1 less than the row of the corresponding nonzero element. For instance, the first nonzero element is in row 2; therefore, the first element in `ir` is 1 (that is, $2 - 1$). The second nonzero element is in row 5; therefore, the second element in `ir` is 4 ($5 - 1$).

The `ir` array must be in column-major order. That means that the `ir` array must define the row positions in column 1 (if any) first, then the row positions in column 2 (if any) second, and so on through column N . Within each column, row position 1 must appear prior to row position 2, and so on.

`mxSetIr` does not sort the `ir` array for you; you must specify an `ir` array that is already sorted.

This function does not free any memory allocated for existing data that it displaces. To free existing memory, call `mxFree` on the pointer returned by `mxGetIr` before you call `mxSetIr`.

C Examples

See `mxsetnzmax.c` in the `mx` subdirectory of the `examples` directory. For an additional example, see `explore.c` in the `mex` subdirectory of the `examples` directory.

mxSetIr (C and Fortran)

See Also

`mxCreateSparse`, `mxGetIr`, `mxGetJc`, `mxSetJc`, `mxFree`

Purpose Set jc array of sparse mxArray

C Syntax

```
#include "matrix.h"
void mxSetJc(mxArray *pm, mwIndex *jc);
```

Fortran Syntax

```
mxSetJc(pm, jc)
mwPointer pm, jc
```

Arguments

pm
 Pointer to a sparse mxArray

jc
 Pointer to the jc array

Description Use mxSetJc to specify a new jc array for a sparse mxArray. The jc array is an integer array having n+1 elements, where n is the number of columns in the sparse mxArray.

If the jth column of the sparse mxArray has any nonzero elements:

- jc[j] is the index in ir, pr, and pi (if it exists) of the first nonzero element in the jth column.
- jc[j+1]-1 is the index of the last nonzero element in the jth column.

The number of nonzero elements in the jth column of the sparse mxArray is:

```
jc[j+1] - jc[j];
```

For the jth column of the sparse mxArray, jc[j] is the total number of nonzero elements in all preceding columns. The last element of the jc array, jc[number of columns], is equal to nnz, which is the number of nonzero elements in the entire sparse mxArray.

For example, consider a 7-by-3 sparse mxArray named Sparrow containing six nonzero elements, created by typing:

```
Sparrow = zeros(7,3);
```

mxSetJc (C and Fortran)

```
Sparrow(2,1) = 1;  
Sparrow(5,1) = 1;  
Sparrow(3,2) = 1;  
Sparrow(2,3) = 2;  
Sparrow(5,3) = 1;  
Sparrow(6,3) = 1;  
Sparrow = sparse(Sparrow);
```

The contents of the `ir`, `jc`, and `pr` arrays are listed in this table.

Subscript	ir	pr	jc	Comment
(2,1)	1	1	0	Column 1 contains two nonzero elements, with rows designated by <code>ir[0]</code> and <code>ir[1]</code>
(5,1)	4	1	2	Column 2 contains one nonzero element, with row designated by <code>ir[2]</code>
(3,2)	2	1	3	Column 3 contains three nonzero elements, with rows designated by <code>ir[3]</code> , <code>ir[4]</code> , and <code>ir[5]</code>
(2,3)	1	2	6	There are six nonzero elements in all.
(5,3)	4	1		
(6,3)	5	1		

As an example of a much sparser `mxArray`, consider a 1000-by-8 sparse `mxArray` named `Spacious` containing only three nonzero elements. The `ir`, `pr`, and `jc` arrays contain the values listed in this table.

Subscript	ir	pr	jc	Comment
(73,2)	72	1	0	Column 1 contains no nonzero elements.

Subscript	ir	pr	jc	Comment
(50,3)	49	1	0	Column 2 contains one nonzero element, with row designated by ir[0].
(64,5)	63	1	1	Column 3 contains one nonzero element, with row designated by ir[1].
			2	Column 4 contains no nonzero elements.
			2	Column 5 contains one nonzero element, with row designated by ir[2].
			3	Column 6 contains no nonzero elements.
			3	Column 7 contains no nonzero elements.
			3	Column 8 contains no nonzero elements.
			3	There are three nonzero elements in all.

This function does not free any memory allocated for existing data that it displaces. To free existing memory, call `mxFree` on the pointer returned by `mxGetJc` before you call `mxSetJc`.

C Examples

See `mxsetdimensions.c` in the `mx` subdirectory of the `examples` directory. For an additional example, see `explore.c` in the `mex` subdirectory of the `examples` directory.

See Also

`mxCreateSparse`, `mxGetIr`, `mxGetJc`, `mxSetIr`, `mxFree`

mxSetM (C and Fortran)

Purpose Set number of rows in mxArray

C Syntax

```
#include "matrix.h"
void mxSetM(mxArray *pm, mwSize m);
```

Fortran Syntax

```
mxSetM(pm, m)
mwPointer pm
mwSize m
```

Arguments

pm
 Pointer to an mxArray

m
 The desired number of rows

Description Call `mxSetM` to set the number of rows in the specified mxArray. The term *rows* means the first dimension of an mxArray, regardless of the number of dimensions. Call `mxSetN` to set the number of columns.

You typically use `mxSetM` to change the shape of an existing mxArray. Note that `mxSetM` does not allocate or deallocate any space for the `pr`, `pi`, `ir`, or `jc` arrays. Consequently, if your calls to `mxSetM` and `mxSetN` increase the number of elements in the mxArray, you must enlarge the `pr`, `pi`, `ir`, and/or `jc` arrays. Call `mxRealloc` to enlarge them.

If your calls to `mxSetM` and `mxSetN` end up reducing the number of elements in the mxArray, you may want to reduce the sizes of the `pr`, `pi`, `ir`, and/or `jc` arrays in order to use heap space more efficiently. However, reducing the size is not mandatory.

C Examples See `mxsetdimensions.c` in the `mx` subdirectory of the `examples` directory. For an additional example, see `sincall.c` in the `refbook` subdirectory of the `examples` directory.

See Also `mxGetM`, `mxGetN`, `mxSetN`

Purpose	Set number of columns in mxArray
C Syntax	<pre>#include "matrix.h" void mxSetN(mxArray *pm, mwSize n);</pre>
Fortran Syntax	<pre>mxSetN(pm, n) mwPointer pm mwSize n</pre>
Arguments	<p>pm Pointer to an mxArray</p> <p>n The desired number of columns</p>
Description	<p>Call <code>mxSetN</code> to set the number of columns in the specified mxArray. The term <i>columns</i> always means the second dimension of a matrix. Calling <code>mxSetN</code> forces an mxArray to have two dimensions. For example, if pm points to an mxArray having three dimensions, calling <code>mxSetN</code> reduces the mxArray to two dimensions.</p> <p>You typically use <code>mxSetN</code> to change the shape of an existing mxArray. Note that <code>mxSetN</code> does not allocate or deallocate any space for the pr, pi, ir, or jc arrays. Consequently, if your calls to <code>mxSetN</code> and <code>mxSetM</code> increase the number of elements in the mxArray, you must enlarge the pr, pi, ir, and/or jc arrays.</p> <p>If your calls to <code>mxSetM</code> and <code>mxSetN</code> end up reducing the number of elements in the mxArray, you may want to reduce the sizes of the pr, pi, ir, and/or jc arrays in order to use heap space more efficiently. However, reducing the size is not mandatory.</p>
C Examples	See <code>mxsetdimensions.c</code> in the mx subdirectory of the examples directory. For an additional example, see <code>sincall.c</code> in the refbook subdirectory of the examples directory.
See Also	<code>mxGetM</code> , <code>mxGetN</code> , <code>mxSetM</code>

mxSetNzmax (C and Fortran)

Purpose Set storage space for nonzero elements

C Syntax

```
#include "matrix.h"
void mxSetNzmax(mxArray *pm, mwSize nzmax);
```

Fortran Syntax

```
mxSetNzmax(pm, nzmax)
mwPointer pm
mwSize nzmax
```

Arguments

pm Pointer to a sparse mxArray.

nzmax The number of elements that mxCreateSparse should allocate to hold the arrays pointed to by *ir*, *pr*, and *pi* (if it exists). Set *nzmax* greater than or equal to the number of nonzero elements in the mxArray, but set it to be less than or equal to the number of rows times the number of columns. If you specify an *nzmax* value of 0, mxSetNzmax sets the value of *nzmax* to 1.

Description Use mxSetNzmax to assign a new value to the *nzmax* field of the specified sparse mxArray. The *nzmax* field holds the maximum possible number of nonzero elements in the sparse mxArray.

The number of elements in the *ir*, *pr*, and *pi* (if it exists) arrays must be equal to *nzmax*. Therefore, after calling mxSetNzmax, you must change the size of the *ir*, *pr*, and *pi* arrays. To change the size of one of these arrays:

- 1 Call mxRealloc with a pointer to the array, setting the size to the new value of *nzmax*.
- 2 Call the appropriate mxSet routine (mxSetIr, mxSetPr, or mxSetPi) to establish the new memory area as the current one.

Two ways of determining how big you should make *nzmax* are

- Set `nzmax` equal to or slightly greater than the number of nonzero elements in a sparse `mxArray`. This approach conserves precious heap space.
- Make `nzmax` equal to the total number of elements in an `mxArray`. This approach eliminates (or, at least reduces) expensive reallocations.

C Examples

See `mxsetnzmax.c` in the `mx` subdirectory of the `examples` directory.

See Also

`mxGetNzmax`, `mxRealloc`

mxSetPi (C and Fortran)

Purpose	Set new imaginary data for mxArray
C Syntax	<pre>#include "matrix.h" void mxSetPi(mxArray *pm, double *pi);</pre>
Fortran Syntax	<pre>mxSetPi(pm, pi) mwPointer pm, pi</pre>
Arguments	<p>pm Pointer to a full (nonsparse) mxArray</p> <p>pi Pointer to the first element of an array. Each element in the array contains the imaginary component of a value. The array must be in dynamic memory; call <code>mxMalloc</code> to allocate this dynamic memory. If <code>pi</code> points to static memory, memory leaks and other memory errors may result.</p>
Description	<p>Use <code>mxSetPi</code> to set the imaginary data of the specified mxArray.</p> <p>Most <code>mxCreate*</code> functions optionally allocate heap space to hold imaginary data. If you tell an <code>mxCreate*</code> function to allocate heap space—for example, by setting the <code>ComplexFlag</code> to <code>mxCOMPLEX</code> in C (1 in Fortran) or by setting <code>pi</code> to a non-NULL value in C (a nonzero value in Fortran)—you do not ordinarily use <code>mxSetPi</code> to initialize the created mxArray's imaginary elements. Rather, you call <code>mxSetPi</code> to replace the initial imaginary values with new ones.</p> <p>This function does not free any memory allocated for existing data that it displaces. To free existing memory, call <code>mxFree</code> on the pointer returned by <code>mxGetPi</code> before you call <code>mxSetPi</code>.</p>
C Examples	See <code>mxisfinite.c</code> and <code>mxsetnzmax.c</code> in the <code>mx</code> subdirectory of the <code>examples</code> directory.
See Also	<code>mxGetPi</code> , <code>mxGetPr</code> , <code>mxSetImagData</code> , <code>mxSetPr</code> , <code>mxFree</code>

Purpose	Set new real data for mxArray
C Syntax	<pre>#include "matrix.h" void mxSetPr(mxArray *pm, double *pr);</pre>
Fortran Syntax	<pre>mxSetPr(pm, pr) mwPointer pm, pr</pre>
Arguments	<p>pm Pointer to a full (nonsparse) mxArray</p> <p>pr Pointer to the first element of an array. Each element in the array contains the real component of a value. The array must be in dynamic memory; call <code>mxMalloc</code> to allocate this dynamic memory. If <code>pr</code> points to static memory, memory leaks and other memory errors can result.</p>
Description	<p>Use <code>mxSetPr</code> to set the real data of the specified mxArray.</p> <p>All <code>mxCreate*</code> calls allocate heap space to hold real data. Therefore, you do not ordinarily use <code>mxSetPr</code> to initialize the real elements of a freshly created mxArray. Rather, you call <code>mxSetPr</code> to replace the initial real values with new ones.</p> <p>This function does not free any memory allocated for existing data that it displaces. To free existing memory, call <code>mxFree</code> on the pointer returned by <code>mxGetPr</code> before you call <code>mxSetPr</code>.</p>
C Examples	See <code>mxsetnzmax.c</code> in the <code>mx</code> subdirectory of the <code>examples</code> directory.
See Also	<code>mxGetPi</code> , <code>mxGetPr</code> , <code>mxSetData</code> , <code>mxSetPi</code> , <code>mxFree</code>

mxSetProperty (C and Fortran)

Purpose Set value of property of MATLAB class object

C Syntax

```
#include "matrix.h"
void mxSetProperty(mxArray *pa, mwIndex index,
    const char *propname, const mxArray *value);
```

Fortran Syntax

```
mwPointer mxSetProperty(pa, index, propname, value)
mwPointer pa, value
mwIndex index
character*(*) propname
```

Arguments

pa
Pointer to an mxArray which is a class object.

index
Index of the desired element of the object array.

In C, the first element of an mxArray has an index of 0, the second element has an index of 1, and the last element has an index of N-1, where N is the total number of elements in the mxArray.

In Fortran, the first element of an mxArray has an index of 1, the second element has an index of 2, and the last element has an index of N, where N is the total number of elements in the mxArray.

propname
Name of the property whose value you are assigning.

value
Pointer to the mxArray you are assigning.

Description Use mxSetProperty to assign a value to the specified property. In pseudo-C terminology, mxSetProperty performs the assignment:

```
pa[index].propname = value;
```


mxSetProperty (C and Fortran)

`mxSetProperty` makes a copy of the value before assigning it as the new property value. This may be a concern if the property uses a large amount of memory.

See Also

`mxGetProperty`

mx SetProperty (C and Fortran)

A

allocating memory 2-83

B

buffer
 defining output 2-14

D

deleting
 named matrix from MAT-file 2-21
directory
 getting 2-24

E

engClose 2-2
engEvalString 2-3
engGetVariable 2-5
engGetVisible 2-7
engine
 data type 2-8
engines
 getting and putting matrices into 2-5 2-17
 starting 2-2
engOpen 2-10
engPutVariable 2-17
engSetVisible 2-19
errors
 control response to 2-69
 issuing messages 2-45 2-47

G

getting
 directory 2-24

M

MAT-files
 deleting named matrix from 2-21
 getting and putting matrices into 2-31 2-36
 to 2-37
 getting next matrix from 2-27
 getting pointer to 2-26
 opening and closing 2-20 2-34
matClose 2-34
matDeleteMatrix 2-21
matfile
 data type 2-22
matGetDir 2-24
matGetFp 2-26
matGetNextVariable 2-27
matGetNextVariableInfo 2-29
matGetVariable 2-31
matGetVariableInfo 2-32
MATLAB engines
 starting 2-2
matOpen 2-20
matPutVariable 2-36
matPutVariableAsGlobal 2-37
matrices
 putting into engine's workspace 2-17
 putting into MAT-files 2-37
MEX-files
 entry point to 2-51
mexCallMATLAB 2-40
mexCallMATLABWithTrap 2-43
mexErrMsgIdAndTxt 2-45 2-72
mexErrMsgTxt 2-47 2-73
mexEvalString 2-49
mexEvalStringWithTrap 2-50
mexFunction 2-51
mexGetVariable 2-55
mexPrintf 2-64
mexSetTrapFlag 2-69
mwIndex 2-74
mwpointer 2-75

- mwSize 2-76
- mxaddfield 2-77
- mxarray
 - data type 2-78
- mxarraytostring 2-80
- mxassert 2-81
- mxasserts 2-82
- mxcalcsinglesubscript 2-83
- mxcalloc 2-86
- mxchar 2-88
- mxclassid 2-89
- mxclassidfromclassname 2-92
- mxcomplexity 2-93
- mxcopycharacterptr 2-94
- mxcopycomplex16toptr 2-95
- mxcopycomplex8toptr 2-96
- mxcopyinteger1toptr 2-97
- mxcopyinteger2toptr 2-98
- mxcopyinteger4toptr 2-99
- mxcopyptrtocharacter 2-100
- mxcopyptrtocomplex16 2-101
- mxcopyptrtocomplex8 2-102
- mxcopyptrtointeger1 2-103
- mxcopyptrtointeger2 2-104
- mxcopyptrtointeger4 2-105
- mxcopyptrtoptrarray 2-106
- mxCopyPtrToReal4 2-107
- mxcopyptrtoREAL8 2-108
- mxcopyreal4toptr 2-109
- mxcopyreal8toptr 2-110
- mxcreatecellarray 2-111
- mxcreatecellmatrix 2-113
- mxcreatechararray 2-114
- mxcreatecharmatrixfromstrings 2-116
- mxcreatedoublematrix 2-118
- mxcreatedoublescalar 2-120
- mxcreatelogicalarray 2-121
- mxcreatelogicalmatrix 2-123
- mxcreatelogicalscalar 2-124
- mxcreatenumericarray 2-125
- mxcreatenumericmatrix 2-128
- mxcreatesparse 2-131
- mxcreatesparselogicalmatrix 2-133
- mxcreatestring 2-134
- mxcreatestructarray 2-135
- mxcreatestructmatrix 2-137
- mxdestroyarray 2-139
- mxduplicatearray 2-140
- mxfree 2-141
- mxgetcell 2-143
- mxgetchars 2-145
- mxgetclassid 2-146
- mxgetclassname 2-147
- mxgetdata 2-148
- mxgetdimensions 2-149
- mxgetelementsize 2-151
- mxgeteps 2-152
- mxgetfield 2-153
- mxgetfieldbynumber 2-156
- mxgetfieldnamebynumber 2-159
- mxgetfieldnumber 2-161
- mxgetimagdata 2-163
- mxgetinf 2-164
- mxgetir 2-165
- mxgetjc 2-167
- mxgetlogicals 2-168
- mxgetm 2-169
- mxgetn 2-171
- mxgetnan 2-173
- mxgetnumberofdimensions 2-174
- mxgetnumberofelements 2-175
- mxgetnumberoffields 2-176
- mxgetnzmax 2-177
- mxgetpi 2-178
- mxgetpr 2-179
- mxGetProperty 2-180
- mxgetscalar 2-182
- mxgetstring 2-184
- mxiscell 2-186
- mxischar 2-187

mxisclass 2-188
mxiscomplex 2-191
mxisdouble 2-192
mxisempty 2-194
mxisfinite 2-195
mxisfromglobalws 2-196
mxisinf 2-197
mxisint16 2-198
mxisint32 2-199
mxisint8 2-201
mxislogical 2-202
mxislogicalscalar 2-203
mxislogicalscalartrue 2-204
mxisnan 2-205
mxisnumeric 2-206
mxissingle 2-208
mxissparse 2-209
mxisstruct 2-210
mxisuint16 2-211
mxisuint32 2-212
mxisuint64 2-213
mxisuint8 2-214
mxlogical 2-215
mxmalloc 2-216
mxrealloc 2-218
mxremovefield 2-220
mxsetcell 2-221
mxsetclassname 2-223
mxsetdata 2-224

mxsetdimensions 2-225
mxsetfield 2-227
mxsetfieldbynumber 2-230
mxsetimagdata 2-233
mxsetir 2-234
mxsetjc 2-237
mxsetm 2-240
mxsetn 2-241
mxsetnzmax 2-242
mxsetpi 2-244
mxsetpr 2-245
mxSetProperty 2-246

O

opening MAT-files 2-20 2-34

P

pointer
 to MAT-file 2-26
printing 2-61 2-63

S

starting
 MATLAB engines 2-2
string
 executing statement 2-3