

Target Support Package™ IC1 Release Notes

How to Contact The MathWorks



www.mathworks.com Web
comp.soft-sys.matlab Newsgroup
www.mathworks.com/contact_TS.html Technical Support



suggest@mathworks.com Product enhancement suggestions
bugs@mathworks.com Bug reports
doc@mathworks.com Documentation error reports
service@mathworks.com Order status, license renewals, passcodes
info@mathworks.com Sales, pricing, and general information



508-647-7000 (Phone)



508-647-7001 (Fax)



The MathWorks, Inc.
3 Apple Hill Drive
Natick, MA 01760-2098

For contact information about worldwide offices, see the MathWorks Web site.

Target Support Package™ IC1 Release Notes

© COPYRIGHT 2004–2009 by The MathWorks, Inc.

The software described in this document is furnished under a license agreement. The software may be used or copied only under the terms of the license agreement. No part of this manual may be photocopied or reproduced in any form without prior written consent from The MathWorks, Inc.

FEDERAL ACQUISITION: This provision applies to all acquisitions of the Program and Documentation by, for, or through the federal government of the United States. By accepting delivery of the Program or Documentation, the government hereby agrees that this software or documentation qualifies as commercial computer software or commercial computer software documentation as such terms are used or defined in FAR 12.212, DFARS Part 227.72, and DFARS 252.227-7014. Accordingly, the terms and conditions of this Agreement and only those rights specified in this Agreement, shall pertain to and govern the use, modification, reproduction, release, performance, display, and disclosure of the Program and Documentation by the federal government (or other entity acquiring for or through the federal government) and shall supersede any conflicting contractual terms or conditions. If this License fails to meet the government's needs or is inconsistent in any respect with federal procurement law, the government agrees to return the Program and Documentation, unused, to The MathWorks, Inc.

Trademarks

MATLAB and Simulink are registered trademarks of The MathWorks, Inc. See www.mathworks.com/trademarks for a list of additional trademarks. Other product or brand names may be trademarks or registered trademarks of their respective holders.

Patents

The MathWorks products are protected by one or more U.S. patents. Please see www.mathworks.com/patents for more information.

Summary by Version	1
Version 1.5.3 (R2009a) Target Support Package IC1 Product	4
Version 1.5.2 (R2008b) Target Support Package IC1 Product	6
Version 1.5.1 (R2008a) Target Support Package IC1 Product	7
Version 1.5 (R2007b) Target for Infineon C166 Product	8
Version 1.4 (R2007a) Target for Infineon C166 Product	10
Version 1.3 (R2006b) Embedded Target for Infineon C166 Microcontrollers	12
Version 1.2.2 (R2006a) Embedded Target for Infineon C166 Microcontrollers	14
Version 1.2.1 (R14SP3) Embedded Target for Infineon C166 Microcontrollers	15
Version 1.2 (R14SP2) Embedded Target for Infineon C166 Microcontrollers	16
Version 1.1.1 (R14SP1) Embedded Target for Infineon C166 Microcontrollers	17
Version 1.1 (R14) Embedded Target for Infineon C166 Microcontrollers	19

Compatibility Summary for the Target Support	
Package IC1 Product	21

Summary by Version

This table provides quick access to what's new in each version. For clarification, see "Using Release Notes" on page 2.

Version (Release)	New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Latest Version V1.5.3 (R2009a)	Yes Details	Yes Summary	Bug Reports Includes fixes	Printable Release Notes: PDF Current product documentation
V1.5.2 (R2008b)	No	No	Bug Reports Includes fixes	No
V1.5.1 (R2008a)	Yes Details	No	Bug Reports Includes fixes	No
V1.5 (R2007b)	Yes Details	Yes Summary	Bug Reports Includes fixes	No
V1.4 (R2007a)	Yes Details	No	Bug Reports Includes fixes	No
V1.3 (R2006b)	Yes Details	Yes Summary	Bug Reports Includes fixes	No
V1.2.2 (R2006a)	No	No	Bug Reports at Web site	No
V1.2.1 (R14SP3)	No	No	Bug Reports at Web site	No
V1.2 (R14SP2)	Yes Details	No	Bug Reports at Web site	No
V1.1.1 (R14SP1)	Yes Details	No	Fixed bugs	No
V1.1 (R14)	Yes Details	No	No bug fixes	No

Using Release Notes

Use release notes when upgrading to a newer version to learn about:

- New features
- Changes
- Potential impact on your existing files and practices

Review the release notes for other MathWorks™ products required for this product (for example, MATLAB® or Simulink®) for enhancements, bugs, and compatibility considerations that also might impact you.

If you are upgrading from a software version other than the most recent one, review the release notes for all interim versions, not just for the version you are installing. For example, when upgrading from V1.0 to V1.2, review the release notes for V1.1 and V1.2.

What's in the Release Notes

New Features and Changes

- New functionality
- Changes to existing functionality

Version Compatibility Considerations

When a new feature or change introduces a reported incompatibility between versions, the **Compatibility Considerations** subsection explains the impact.

Compatibility issues reported after the product is released appear under Bug Reports at the MathWorks Web site. Bug fixes can sometimes result in incompatibilities, so you should also review the fixed bugs in Bug Reports for any compatibility impact.

Fixed Bugs and Known Problems

The MathWorks offers a user-searchable Bug Reports database so you can view Bug Reports. The development team updates this database at release time and as more information becomes available. This includes provisions for any known workarounds or file replacements. Information is available for bugs existing in or fixed in Release 14SP2 or later. Information is not available for all bugs in earlier releases.

Access Bug Reports using your MathWorks Account.

Version 1.5.3 (R2009a) Target Support Package IC1 Product

This table summarizes what's new in Version 1.5.3 (R2009a) :

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	Yes — Details labeled as Compatibility Considerations within descriptions of new features and changes, below. See also Summary.	Bug Reports at Web site	Printable Release Notes: PDF Current product documentation

New features and changes introduced in this version are described here.

CAN Support by the Vehicle Network Toolbox

The new Vehicle Network Toolbox provides host-side CAN blocks. These are replacements for previous blocks, which are now marked obsolete. Although you can continue to use these obsolete blocks, there are advantages in using the new blocks. They include the following:

- A reduced block set that uses the same packing and unpacking blocks to handle any type of message (raw data, raw signals, or CANdb signals).
- Support for the new Vector-Informatik XL driver and device line.
- Better compatibility with CANdb files (as these files are now read using the Vector-Informatik library).

Compatibility Considerations

The Vehicle Network Toolbox is required for host-side CAN blocks. The following blocks are available from the Vehicle Network Toolbox :

- CAN Configuration

- CAN Receive
- CAN Transmit

CAN Pack and CAN Unpack blocks are available with Target Support Package™ IC1.

The Vehicle Network Toolbox is not required if you are using target-side CAN blocks.

The following blocks are now obsolete:

- CAN Message Filter
- CAN Message Packing
- CAN Message Packing (CANdb)
- CAN Message Unpacking
- CAN Message Unpacking (CANdb)
- Vector CAN Configuration
- Vector CAN Receive
- Vector CAN Transmit

For information on how you can identify obsolete blocks and transition to the new blocks, see [CAN Blocks Transition](#).

Version 1.5.2 (R2008b) Target Support Package IC1 Product

This table summarizes what's new in Version 1.5.2 (R2008b) :

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
No	No	Bug Reports at Web site	Printable Release Notes: PDF Current product documentation

Version 1.5.1 (R2008a) Target Support Package IC1 Product

This table summarizes what's new in Version 1.5.1 (R2008a) :

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	No	Bug Reports at Web site	No

New features and changes introduced in this version are described here.


“What’s This?” Context-Sensitive Help Available for Simulink Configuration Parameters Dialog

R2008a introduces “What’s This?” context-sensitive help for parameters that appear in the Simulink Configuration Parameters dialog. This feature provides quick access to a detailed description of the parameters, saving you the time it would take to find the information in the Help browser.

To use the "What’s This?" help, do the following:

- 1 Place your cursor over the label of a parameter.
- 2 Right-click. A **What’s This?** context menu appears.

For example, the following figure shows the **What’s This?** context menu appearing after a right-click on the **Start time** parameter in the **Solver** pane.



- 3 Click **What’s This?** A context-sensitive help window appears showing a description of the parameter.

Version 1.5 (R2007b) Target for Infineon C166 Product

This table summarizes what's new in Version 1.5 (R2007b) :

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	Yes — Details labeled as Compatibility Considerations within descriptions of new features and changes, below. See also Summary.	Bug Reports at Web site	No

New features and changes introduced in this version are described here.

C-CAN Device Driver Blocks for ST10 Processors

Newer ST10 derivatives use C-CAN modules that require different device drivers. Now, four new C-CAN blocks support these ST10 derivatives:

- C-CAN Transmit
- C-CAN Receive
- C-CAN CAN Calibration Protocol.
- C166 Execution Profiling via C-CAN 1

The Target for Infineon C166® product now supports the full range of CAN peripheral hardware used on C166 derivative (CAN, TwinCAN, and C-CAN).

USB XC164CM Support

Support for compact USB stick evaluation hardware, with a new demo, `c166_usb_stick`, preconfigured for XC164CM U CAN hardware. This demo features device driver blocks configured for this hardware to demonstrate its capabilities.

New TASKING Toolset Support

TASKING® Tools for C166/ST10 v8.6 r3 is now supported.

Link and Target Products Regrouped in New Start, Help, and Demos Category

A new product category, Links and Targets, now contains all MathWorks software products that link, target, or cosimulate code.

Compatibility Considerations

This change impacts you in the following ways:

- Finding and viewing these products through the MATLAB Desktop **Start** button and in the Help browser **Contents** and **Demos** panes.
- Using the `demo` command to access the product demos.

For more about this new product category, see “Demos and Help Browser Contents Now Include New Category for Links and Targets”, in the *MATLAB Release Notes*.

Version 1.4 (R2007a) Target for Infineon C166 Product

This table summarizes what's new in Version 1.4 (R2007a) :

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	Yes — Details labeled as Compatibility Considerations within descriptions of new features and changes, below. See also Summary.	Bug Reports at Web site	No

New features and changes introduced in this version are described here.

External Mode

External mode is now supported via CAN. You can use either external mode or a third party calibration tool to interact with the real-time application running on the target processor. The CAN Calibration Protocol block provides a means of monitoring signals and altering the parameter values in the application code running on the target.

See “Using External Mode” for details.

Real-Time Workshop GRT Target Support

Real-Time Workshop GRT target is supported for build and download, so Real-Time Workshop Embedded Coder is optional.

However Real-Time Workshop Embedded Coder ERT target is required for PIL, the use of the bit-addressable memory feature, and the CCP Data Acquisition (DAQ) List mode of operation. The CCP Polling mode of operation can be used both with or without Real-Time Workshop Embedded Coder.

Model Reference Support

Model reference is supported.

Host Side Profiling Via CAN Uses Vector "Application Channel"

You can now specify the CAN Application Channel to use with the execution profiling command, and run the Vector Informatik configuration utility to configure the bit rate of the channel. In previous versions, CAN channels other than CANCardX 1 and CAN AC2 PCI 1 were inaccessible. The syntax to use this new argument is:

```
profile_c166('can','CANChannel','MATLAB 1')
```

The default is 'MATLAB 1' if no Application Channel is specified.

Compatibility Considerations

It is no longer possible to specify the CAN bit rate as an argument to `profile_c166`. The old syntax for specifying the bit rate, e.g.,

```
profile_c166('can','bitrate',1000000)
```

or

```
profile_c166('can','modelName','mymodel')  
% Calculates required bit-rate by inspecting mymodel
```

now returns an error. The error describes the new approach for setting the CAN bit rate.

Version 1.3 (R2006b) Embedded Target for Infineon C166 Microcontrollers

This table summarizes what's new in Version 1.3 (R2006b) :

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	Yes — Details labeled as Compatibility Considerations within descriptions of new features and changes, below. See also Summary.	Bug Reports at Web site	No

New features and changes introduced in this version are described here.

Compatibility with the Link for TASKING Product

Embedded Target for Infineon C166 Microcontrollers is integrated with (and dependent on) the Link for TASKING® product. This integration provides new capabilities to the Embedded Target including:

- A flexible build process, which allows you to automatically create and build projects in the TASKING EDE using code generated by Real-Time Workshop Embedded Coder.
- Customizable project templates for targeting embedded hardware or instruction set simulator.
- Processor-in-the-Loop (PIL) cosimulation techniques to verify generated code running in an instruction set simulator or real embedded hardware environment. You can set breakpoints, step through the code, and watch variables during cosimulation.
- MATLAB commands to rapidly and easily interact with projects in the TASKING EDE or debug generated code in the CrossView Pro debugger.

- Execution profiling and code coverage reports are returned from the TASKING EDE to MATLAB for your review.

Compatibility Considerations

The Link for TASKING build process requires changes to existing models for C166 from previous releases. When you open a model created in a previous release, the Link for TASKING component is automatically added to your configuration set. Your model is ready to use with the Link for TASKING build process and all the existing Embedded Target for Infineon C166 Microcontrollers features such as real-time execution, device drivers, and real-time execution profiling.

See also the 2006b Transition Web page.

Note Model Reference is no longer supported due to the dependency on the Link for TASKING product.

Version 1.2.2 (R2006a) Embedded Target for Infineon C166 Microcontrollers

This table summarizes what's new in V1.2.2 (R2006a) :

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
No	No	Bug Reports at Web site	No

Version 1.2.1 (R14SP3) Embedded Target for Infineon C166 Microcontrollers

This table summarizes what's new in V1.2.1 (R14SP3) :

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
No	No	Bug Reports at Web site	No

Version 1.2 (R14SP2) Embedded Target for Infineon C166 Microcontrollers

This table summarizes what's new in V1.2 (R14SP2) :

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	No	Bug Reports at Web site	No

New features and changes introduced in this version are

Switch Target Configuration Block

This new block runs a convenience function that configures your model and Target Preferences to one of a set of pre-defined hardware configurations. The function can also be used as a template for setting up your own customized configurations.

Fast External Interrupt Block

This new block generates an asynchronous function-call trigger when an interrupt occurs. You can use this block to execute a function-call triggered subsystem in the context of the service routine for a fast external interrupt.

Digital Input/Output Blocks

You can use the new digital input/output device driver blocks to read and set the logical state of a specified port/pin number.

Version 1.1.1 (R14SP1) Embedded Target for Infineon C166 Microcontrollers

This table summarizes what's new in V1.1.1 (R14SP1) :

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	No	Fixed bugs	No

New features and changes introduced in this version are

Support for Model Reference

Model reference is now supported by the Embedded Target for Infineon C166 Microcontrollers.

Fixed Bugs

Correct Value for Number of Concurrent Overruns

In Version 1.1 (Release 14) an incorrect value was used for the maximum allowed number of concurrent base rate overruns. The effective value for this setting was one minus the value actually entered in the dialog under **Tools** -> **Real-Time Workshop** -> **Options**-> **C166 Options(1)**. For example, if a value of 2 is entered for **Maximum number of concurrent base-rate overruns** then the maximum number of concurrent base rate overruns is actually 1. In particular, if a value of 0 is entered the application would fail.

This problem is fixed in Version 1.1.1 (Release 14 Service Pack 1).

Overruns No Longer Stop Further Execution of Sub-rates

Previously, when an overrun occurred in sub-rate 1 the following could happen: consider the case when sub-rate 1 is currently executing and another instance of sub-rate 1 is scheduled to run (i.e. a task overrun has occurred). When the current instance of sub-rate 1 completes, the function does not

execute further instances of sub-rate 1. Instead the execution of sub-rate 1 can be delayed and the processor may be idle. The pending instance of sub-rate 1 will only be invoked on completion of the next base rate task.

This problem is fixed in version 1.1.1

Version 1.1 (R14) Embedded Target for Infineon C166 Microcontrollers

This table summarizes what's new in V1.1 (R14) :

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	No	No bug fixes	No

New features and changes introduced in this version are

CAN Support

There are new driver blocks for transmitting and receiving messages using the CAN module on the Infineon® C166® microprocessor. There are blocks for packing, unpacking and filtering CAN messages, outputting the bus status or resetting a CAN module. There is also an implementation of the CAN Calibration Protocol (CCP) standard for host-target communication over CAN, so you can use a calibration tool (such as Vector CANape or ATI Vision) for remote signal monitoring and parameter tuning.

Support for XC16x Processor Variants

There is now support for XC16x variants of the Infineon C166 microprocessor. There is a new sublibrary of TwinCAN blocks providing CAN support (including CCP) for the TwinCAN nodes of XC16x processor variants.

Task Execution Profiling

This is a new feature that allows execution profiling data to be recorded, uploaded and displayed in the form of a MATLAB graphic and as an HTML report. Execution profiling data can be collected over serial, CAN or TwinCAN. See the demo model `c166_multitasking`.

Temporary Task Overruns Now Permitted by the Scheduler

It is now possible for task overruns in the base rate or one of the sub- rates to occur without causing a failure. The benefit is that if it occasionally it takes longer than the normally allowed time to complete a task, this is now possible without having to increase the sample time. The overrun behavior is configurable and is illustrated by the new demo model `c166_multitasking`.

Use of Real Time Clock as System Timer

It is now possible to select the Real Time Clock (RTC) for use as the system timer. This allows the timers T2 ... T6 to be used for other purposes. This parameter is found in the C166 Resource Configuration block. Note that the RTC is not available on all hardware variants of the C166; please consult your hardware documentation.

Compatibility Summary for the Target Support Package IC1 Product

This table summarizes new features and changes that might cause incompatibilities when you upgrade from an earlier version, or when you use files on multiple versions. Details are provided in the description of the new feature or change.

Version (Release)	New Features and Changes with Version Compatibility Impact
Latest Version V1.5.3 (R2009a)	See the Compatibility Considerations subheading for this new feature or change: “CAN Support by the Vehicle Network Toolbox” on page 4
V1.5.2 (R2008b)	None
V1.5.1 (R2008a)	None
V1.5 (R2007b)	See the Compatibility Considerations subheading for this new feature or change: “Link and Target Products Regrouped in New Start, Help, and Demos Category” on page 9
V1.4 (R2007a)	See the Compatibility Considerations subheading for this new feature or change: “Host Side Profiling Via CAN Uses Vector "Application Channel"” on page 11
V1.3 (R2006b)	See the Compatibility Considerations subheading for this new feature or change: “Compatibility with the Link for TASKING Product ” on page 12
V1.2.2 (R2006a)	None
V1.2.1 (R14SP3)	None

Version (Release)	New Features and Changes with Version Compatibility Impact
V1.2 (R14SP2)	None
V1.1.1 (R14SP1)	None
V1.1 (R14)	None