

Bioinformatics Toolbox™

Release Notes

How to Contact The MathWorks



www.mathworks.com
comp.soft-sys.matlab
www.mathworks.com/contact_TS.html

Web
Newsgroup
Technical Support



suggest@mathworks.com
bugs@mathworks.com
doc@mathworks.com
service@mathworks.com
info@mathworks.com

Product enhancement suggestions
Bug reports
Documentation error reports
Order status, license renewals, passcodes
Sales, pricing, and general information



508-647-7000 (Phone)



508-647-7001 (Fax)



The MathWorks, Inc.
3 Apple Hill Drive
Natick, MA 01760-2098

For contact information about worldwide offices, see the MathWorks Web site.

Bioinformatics Toolbox™ Release Notes

© COPYRIGHT 2003–2009 by The MathWorks, Inc.

The software described in this document is furnished under a license agreement. The software may be used or copied only under the terms of the license agreement. No part of this manual may be photocopied or reproduced in any form without prior written consent from The MathWorks, Inc.

FEDERAL ACQUISITION: This provision applies to all acquisitions of the Program and Documentation by, for, or through the federal government of the United States. By accepting delivery of the Program or Documentation, the government hereby agrees that this software or documentation qualifies as commercial computer software or commercial computer software documentation as such terms are used or defined in FAR 12.212, DFARS Part 227.72, and DFARS 252.227-7014. Accordingly, the terms and conditions of this Agreement and only those rights specified in this Agreement, shall pertain to and govern the use, modification, reproduction, release, performance, display, and disclosure of the Program and Documentation by the federal government (or other entity acquiring for or through the federal government) and shall supersede any conflicting contractual terms or conditions. If this License fails to meet the government's needs or is inconsistent in any respect with federal procurement law, the government agrees to return the Program and Documentation, unused, to The MathWorks, Inc.

Trademarks

MATLAB and Simulink are registered trademarks of The MathWorks, Inc. See www.mathworks.com/trademarks for a list of additional trademarks. Other product or brand names may be trademarks or registered trademarks of their respective holders.

Patents

The MathWorks products are protected by one or more U.S. patents. Please see www.mathworks.com/patents for more information.

Summary by Version	1
Version 3.4 (R2009b) Bioinformatics Toolbox	
Software	4
Version 3.3 (R2009a) Bioinformatics Toolbox	
Software	13
Version 3.2 (R2008b) Bioinformatics Toolbox	
Software	16
Version 3.1 (R2008a) Bioinformatics Toolbox	
Software	23
Version 3.0 (R2007b) Bioinformatics Toolbox	
Software	30
Version 2.6 (R2007a+) Bioinformatics Toolbox	
Software	35
Version 2.5 (R2007a) Bioinformatics Toolbox	
Software	38
Version 2.4 (R2006b) Bioinformatics Toolbox	
Software	46
Version 2.3 (R2006a+) Bioinformatics Toolbox	
Software	50
Version 2.2.1 (R2006a) Bioinformatics Toolbox	
Software	53
Version 2.2 (R14SP3+) Bioinformatics Toolbox	
Software	54

Version 2.1.1 (R14SP3) Bioinformatics Toolbox	
Software	56
Version 2.1 (R14SP2+) Bioinformatics Toolbox	
Software	57
Version 2.0.1 (R14SP2) Bioinformatics Toolbox	
Software	59
Version 2.0 (R14SP1+) Bioinformatics Toolbox	
Software	60
Version 1.1.1 (R14SP1) Bioinformatics Toolbox	
Software	64
Version 1.1 (R14) Bioinformatics Toolbox Software ...	65
Version 1.0 (R13+) Bioinformatics Toolbox Software ..	69
Compatibility Summary for Bioinformatics Toolbox	
Software	72

Summary by Version

This table provides quick access to what's new in each version. For clarification, see "Using Release Notes" on page 2.

Version (Release)	New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Latest Version V3.4 (R2009b)	Yes Details	Yes Summary	Bug Reports Includes fixes	Printable Release Notes: PDF Current product documentation
V3.3 (R2009a)	Yes Details	Yes Summary	Bug Reports Includes fixes	No
V3.2 (R2008b)	Yes Details	Yes Summary	Bug Reports Includes fixes	No
V3.1 (R2008a)	Yes Details	Yes Summary	Bug Reports Includes fixes	No
V3.0 (R2007b)	Yes Details	Yes Summary	Bug Reports Includes fixes	No
V2.6 (R2007a+)	Yes Details	Yes Summary	Bug Reports Includes fixes	No
V2.5 (R2007a)	Yes Details	Yes Summary	Bug Reports Includes fixes	No
V2.4 (R2006b)	Yes Details	No	Bug Reports Includes fixes	No
V2.3 (R2006a+)	Yes Details	No	Bug Reports Includes fixes	No
V2.2.1 (R2006a)	No	No	Bug Reports Includes fixes	No
V2.2 (R14SP3+)	Yes Details	No	Bug Reports Includes fixes	No

Version (Release)	New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
V2.1.1 (R14SP3)	No	No	Bug Reports Includes fixes	No
V2.1 (R14SP2+)	Yes Details	No	Bug Reports Includes fixes	No
V2.0.1 (R14SP2)	Yes Details	No	Bug Reports Includes fixes	No
V2.0 (R14SP1+)	Yes Details	No	No bug fixes	No
V1.1.1 (R14SP1)	No	No	No bug fixes	No
V1.1 (R14)	Yes Details	No	No bug fixes	No
V1.0 (R13+)	Yes Details	No	No bug fixes	V1.0 product documentation

Using Release Notes

Use release notes when upgrading to a newer version to learn about:

- New features
- Changes
- Potential impact on your existing files and practices

Review the release notes for other MathWorks™ products required for this product (for example, MATLAB® or Simulink®). Determine if enhancements, bugs, or compatibility considerations in other products impact you.

If you are upgrading from a software version other than the most recent one, review the current release notes and all interim versions. For example, when you upgrade from V1.0 to V1.2, review the release notes for V1.1 and V1.2.

What Is in the Release Notes

New Features and Changes

- New functionality
- Changes to existing functionality

Version Compatibility Considerations

When a new feature or change introduces a reported incompatibility between versions, the **Compatibility Considerations** subsection explains the impact.

Compatibility issues reported after the product release appear under Bug Reports at The MathWorks™ Web site. Bug fixes can sometimes result in incompatibilities, so review the fixed bugs in Bug Reports for any compatibility impact.

Fixed Bugs and Known Problems

The MathWorks offers a user-searchable Bug Reports database so you can view Bug Reports. The development team updates this database at release time and as more information becomes available. Bug Reports include provisions for any known workarounds or file replacements. Information is available for bugs existing in or fixed in Release 14SP2 or later. Information is not available for all bugs in earlier releases.

Access Bug Reports using your MathWorks Account.

Version 3.4 (R2009b) Bioinformatics Toolbox Software

This table summarizes what's new in Version 3.4 (R2009b):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	Yes—Details labeled as Compatibility Considerations , below. See also Summary.	Bug Reports Includes fixes	Printable Release Notes: PDF Current product documentation

New and updated features in this version include:

- “Data Format and Database Functions” on page 5
- “Protein Analysis Functions” on page 5
- “Data Visualization Functions” on page 6
- “Sequence Statistics Functions” on page 6
- “Sequence Utility Functions” on page 6
- “Sequence Visualization Functions” on page 7
- “Pairwise Sequence Alignment Functions” on page 7
- “Multiple Sequence Alignment Functions” on page 7
- “Phylogenetic Tree Tools and Methods” on page 8
- “Clustergram Window” on page 9
- “Clustergram Methods and Properties” on page 9
- “HeatMap Object, Methods, and Properties” on page 11
- “DataMatrix Methods” on page 11
- “Microarray Functions, Objects, Methods, and Properties” on page 11
- “Mass Spectrometry Functions” on page 12
- “Demos for Sequence Analysis” on page 12

- “Demos for Microarray Analysis” on page 12

Data Format and Database Functions

Following are new functions:

- `fastainfo` — Return information about FASTA file.
- `fastqinfo` — Return information about FASTQ file.
- `fastqread` — Read data from FASTQ file.
- `fastqwrite` — Write to file using FASTQ format.
- `sffinfo` — Return information about SFF file.
- `sffread` — Read data from SFF file.
- `tgspcinfo` — Return information about SPC file.
- `tgspcread` — Read data from SPC file.

The following functions are updated:

- `affyread` — Read microarray data from Affymetrix® GeneChip® file. Updated to read cell layout files (CLF) and background probe (BGP) files.
- `multialignwrite` — Write multiple alignment to file. Updated to write a file in either ClustalW ALN format (default) or MSF format.

Protein Analysis Functions

Following is a new function:

- `isotopicdist` — Calculate high-resolution isotope mass distribution and density function.

The following function is updated:

- `cleave` — Cleave amino acid sequence with enzyme. Updated to let you specify an exception to the enzyme’s cleavage rule and to let you specify a maximum number of missed cleavage sites. Also updated to return the number of missed cleavage sites per peptide fragment.

Data Visualization Functions

The following functions are updated:

- `microplateplot` — Display visualization of microtiter plate. Display updated so that first row of input matrix appears at the top and is labeled row A. Updated to return the handle to the axes of the plot, which lets you reverse the order of the rows or columns in the display. Updated to include a new property, 'TextFontSize', which lets you control the font size of text labels.
- `multialignviewer` — Display and interactively adjust multiple sequence alignment. Updated to accept a list of names to label the sequences in the Multiple Sequence Alignment Viewer window.
- `showalignment` — Display color-coded sequence alignment. Updated to control the inclusion or exclusion of terminal gaps from the count of matches and similar residues when displaying a pairwise alignment.

Compatibility Considerations

In Bioinformatics Toolbox™ Version 3.3, the default layout for the plot returned by `microplateplot` displayed the first row of the input matrix at the bottom.

In Bioinformatics Toolbox Version 3.4, the plot displays the first row of the input matrix at the top.

Sequence Statistics Functions

The following function is updated:

- `seqshowwords` — Graphically display words in sequence. Updated to search for multiple words in a sequence.

Sequence Utility Functions

The following functions are updated:

- `cleave` — Cleave amino acid sequence with enzyme. Updated to let you specify an exception to the enzyme's cleavage rule and to let you specify

a maximum number of missed cleavage sites. Also updated to return the number of missed cleavage sites per peptide fragment.

- `rebasecuts` — Find restriction enzymes that cut nucleotide sequence. Updated to use Version 904 of REBASE®, the Restriction Enzyme Database.
- `restrict` — Split nucleotide sequence at restriction site. Updated to use Version 904 of REBASE, the Restriction Enzyme Database.

Sequence Visualization Functions

The following functions are updated:

- `multialignviewer` — Display and interactively adjust multiple sequence alignment. Updated to accept a list of names to label the sequences in the Multiple Sequence Alignment Viewer window.
- `showalignment` — Display color-coded sequence alignment. Updated to control the inclusion or exclusion of terminal gaps from the count of matches and similar residues when displaying a pairwise alignment.

Pairwise Sequence Alignment Functions

Following is a new function:

- `localalign` — Return local optimal and suboptimal alignments between two sequences.

The following functions are updated:

- `multialignviewer` — Display and interactively adjust multiple sequence alignment. Updated to accept a list of names to label the sequences in the Multiple Sequence Alignment Viewer window.
- `showalignment` — Display color-coded sequence alignment. Updated to control the inclusion or exclusion of terminal gaps from the count of matches and similar residues when displaying a pairwise alignment.

Multiple Sequence Alignment Functions

The following functions are updated:

- `multialignviewer` — Display and interactively adjust multiple sequence alignment. Updated to accept a list of names to label the sequences in the Multiple Sequence Alignment Viewer window.
- `multialignwrite` — Write multiple alignment to file. Updated to write a file in either ClustalW ALN format (default) or MSF format.
- `showalignment` — Display color-coded sequence alignment. Updated to control the inclusion or exclusion of terminal gaps from the count of matches and similar residues when displaying a pairwise alignment.

Phylogenetic Tree Tools and Methods

The Phylogenetic Tree Tool includes the following updates:

- Includes two new circular print renderings: equal angle and equal daylight
- Updates to **Tools** menu, including commands to select specific branch and leaf nodes based on different criteria, such as distance, common ancestors, leaves only, and descendants.

Following is a new method:

- `cluster` — Validate clusters in phylogenetic tree.

The following method is updated:

- `plot` — Draw phylogenetic tree. Updated to include two new algorithms for circular layouts: equal angle and equal daylight. Updated to let you rotate circular trees from 0 through 360 degrees and to rotate leaf labels of circular trees so that the text is aligned to the root node. Updated the 'LeafLabels' property so that it defaults to `true` for circular layouts and to `false` for square and angular layouts.



Compatibility Considerations

In Bioinformatics Toolbox Version 3.3, the 'LeafLabels' property defaulted to `true` when the 'Type' property was 'square' or 'angular', and to `false` when the 'Type' property was 'radial'.

In Bioinformatics Toolbox Version 3.4, the 'LeafLabels' property defaults to false when the 'Type' property is 'square' or 'angular', and to true when the 'Type' property is 'radial'.

Clustergram Window

The Clustergram window has two new toolbar buttons:

- Annotate  button — Shows and hides intensity values for each area of the heat map.
- Show Dendrogram  button — Shows and hides the dendrograms.

Clustergram Methods and Properties

The following are new methods of a clustergram object:

- `addTitle` — Add title to clustergram.
- `addXLabel` — Label *x*-axis of clustergram.
- `addYLabel` — Label *y*-axis of clustergram.
- `clusterGroup` — Select cluster group.

The following properties of a clustergram object are renamed:

- `ColumnMarker` is now `ColumnGroupMarker`.
- `Impute` is now `ImputeFun`.
- `Ratio` is now `DisplayRatio`.
- `RowMarker` is now `RowGroupMarker`.
- `SymmetricRange` is now `Symmetric`.

Note The former property names are still valid.

Following is a new property related to the display of dendrogram tree diagrams in a clustergram object:

- ShowDendrogram

The following are new properties related to the display of row and column labels of a clustergram object:

- RowLabels
- ColumnLabels
- RowLabelsLocation
- ColumnLabelsLocation
- RowLabelsColor
- ColumnLabelsColor
- LabelsWithMarkers
- RowLabelsRotate
- ColumnLabelsRotate

The following are new properties related to annotating data in a clustergram object:

- Annotate
- AnnotColor
- AnnotPrecision

When using clustergram properties with the `get` and `set` methods, the property names are now case sensitive.

Compatibility Considerations

In Bioinformatics Toolbox Version 3.3, the property names of a clustergram object were not case sensitive when used with the `get` and `set` methods.

In Bioinformatics Toolbox Version 3.4, property names of a clustergram object are case sensitive.

HeatMap Object, Methods, and Properties

Following is a new object:

- `HeatMap` object — Object containing matrix and heat map display properties.

The following are methods of a `HeatMap` object:

- `addTitle` — Add title to heat map.
- `addXLabel` — Label x -axis of heat map.
- `addYLabel` — Label y -axis of heat map.
- `plot` — Render heat map for object.
- `view` — Render heat map for object.

A `HeatMap` object includes many properties that control the creation of the heat map, row and column labels, axes labels, title, and data annotation.

DataMatrix Methods

Following is a new method of a `DataMatrix` object:

- `dmwrite` — Write `DataMatrix` object to text file.

Microarray Functions, Objects, Methods, and Properties

Following are new functions to create objects containing data from a microarray gene expression experiment:

- `bioma.ExpressionSet` — Contain data from microarray gene expression experiment.
- `bioma.data.ExptData` — Contain expression data from microarray gene expression experiment.
- `bioma.data.MetaData` — Contain sample or feature metadata from microarray gene expression experiment.

- `bioma.data.MIAME` — Contain experiment information from microarray gene expression experiment.

These objects have properties and methods that are useful for viewing and analyzing the data or a subset of the data.

Mass Spectrometry Functions

Following are new functions:

- `isotopicdist` — Calculate high-resolution isotope mass distribution and density function.
- `tgspcinfo` — Return information about SPC file.
- `tgspcread` — Read data from SPC file.

The following function is updated:

- `mspeaks` — Convert raw peak data to peak list (centroided data). Updated to include a new property, 'Style', which lets you specify the style for marking the peaks in the plot.

Demos for Sequence Analysis

Following are two new sequence analysis demos:

- Working with SFF Files from the 454 Genome Sequencer FLX System
- Working with Illumina/Solexa Next-Generation Sequencing Data

Demos for Microarray Analysis

Following are two new microarray analysis demos:

- Working with Objects for Microarray Experiment Data
- Analyzing Illumina Bead Summary Gene Expression Data

Version 3.3 (R2009a) Bioinformatics Toolbox Software

This table summarizes what's new in Version 3.3 (R2009a):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	Yes—Details labeled as Compatibility Considerations , below. See also Summary.	Bug Reports Includes fixes	No

New and updated features in this version include:

- “Data Visualization Functions” on page 13
- “Sequence Utility Functions” on page 13
- “Sequence Conversion Functions” on page 14
- “Bioanalytic and Mass Spectrometry Functions” on page 14
- “Microarray Functions” on page 14
- “Demo for Sequence Analysis” on page 15

Data Visualization Functions

Following is a new function:

- `microplateplot` — Display visualization of microtiter plate.

Sequence Utility Functions

The following functions are updated:

- `rebasecuts` — Find restriction enzymes that cut nucleotide sequence. Updated to use Version 811 of REBASE, the Restriction Enzyme Database.
- `restrict` — Split nucleotide sequence at restriction site. Updated to use Version 811 of REBASE, the Restriction Enzyme Database.

Sequence Conversion Functions

The following function is updated:

- `nt2aa` — Convert nucleotide sequence to amino acid sequence. Updated to include a new property, 'ACGTOnly', to support ambiguous and unknown nucleotide characters.

Bioanalytic and Mass Spectrometry Functions

The following functions are updated to use with data from any separation technique, including mass spectrometry:

- `msalign` — Align peaks in signal to reference peaks.
- `msbackadj` — Correct baseline of signal with peaks.
- `mslowess` — Smooth signal with peaks using nonparametric method.
- `msnorm` — Normalize set of signals with peaks.
- `mspeaks` — Convert raw peak data to peak list (centroided data).
- `msppresample` — Resample signal with peaks while preserving peaks.
- `msresample` — Resample signal with peaks.
- `mssgolay` — Smooth signal with peaks using least-squares polynomial.

Microarray Functions

The following functions are updated:

- `cghcbs` — Perform circular binary segmentation (CBS) on array-based comparative genomic hybridization (aCGH) data. Updated to include an optional heuristic stopping rule to improve performance.
- `illumbslookup` — Look up Illumina® BeadStudio™ target (probe) sequence and annotation information. Updated to read Illumina microRNA array annotation files.
- `illumbsread` — Read gene expression data exported from Illumina BeadStudio software. Updated to read Illumina microRNA array data files.
- `mattest` — Perform two-sample t-test to evaluate differential expression of genes from two experimental conditions or phenotypes. Updated with

new property, 'VarType', which lets you specify equal or unequal (default) variance for the test.

Compatibility Considerations

A compatibility consideration related to the `matstest` function was introduced in Bioinformatics Toolbox Version 3.2, but not reported in the Release Notes for Version 3.2 (R2008b). Specifically, in Bioinformatics Toolbox Version 3.1 and earlier, the `matstest` function used equal variance for the test. In Bioinformatics Toolbox Version 3.2, the `matstest` function starting using unequal variance for the test.

Demo for Sequence Analysis

The following is a new sequence analysis demo:

Predicting Protein Secondary Structure Using a Neural Network

Version 3.2 (R2008b) Bioinformatics Toolbox Software

This table summarizes what's new in Version 3.2 (R2008b):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	Yes—Details labeled as Compatibility Considerations , below. See also Summary.	Bug Reports Includes fixes	No

New and updated features in this version include:

- “Data Format and Database Functions” on page 16
- “Sequence Utility Functions” on page 18
- “Multiple Sequence Alignment Functions” on page 18
- “Gene Ontology Functions” on page 19
- “Protein Analysis Functions” on page 19
- “Mass Spectrometry Functions” on page 19
- “Microarray File Format Functions” on page 20
- “Microarray Functions” on page 21
- “DataMatrix Object” on page 21
- “DataMatrix Methods” on page 22
- “Demo for Visualization Tools” on page 22
- “Demo for Sequence Analysis” on page 22
- “Demos for Microarray Data Analysis” on page 22

Data Format and Database Functions

Following are new functions:

- `affygcma` — Perform GC Robust Multi-array Average (GCRMA) procedure on Affymetrix microarray probe-level data.
- `affyrma` — Perform Robust Multi-array Average (RMA) procedure on Affymetrix microarray probe-level data.
- `affysnannotread` — Read Affymetrix Mapping DNA array data from CSV-formatted annotation file.
- `geoseriesread` — Read Gene Expression Omnibus (GEO) Series (GSE) format data.
- `multialignwrite` — Write multiple-alignment to file using ClustalW ALN format.
- `mzcdfread` — Read mass spectrometry data from netCDF file.

The following functions are updated:

- `affyread` — Read microarray data from Affymetrix GeneChip file. Updated so that `Probes` field in the return structure is now a `single`, which reduces memory usage.
- `celintensityread` — Read probe intensities from Affymetrix CEL files. Updated so that `PMIntensities` and `MMIntensities` fields in the return structure are now `singles`, which reduces memory usage.
- `geosoftread` — Read Gene Expression Omnibus (GEO) SOFT format data. Updated to support Platform (GPL) records.
- `getgeodata` — Retrieve Gene Expression Omnibus (GEO) format data. Updated to support Platform (GPL) and Series (GSE) records.
- `goannotread` — Read annotations from Gene Ontology annotated file. Updated to include two new properties, `'Fields'` and `'Aspect'`, which let you read a subset of the data in the annotated file.
- `multialignread` — Read multiple sequence alignment file. Updated to support PHYLIP (Phylogeny Inference Package) multiple-sequence alignment files.
- `mzxmlread` — Read data from mzXML file. Improved to read larger files, faster and without running out of memory. Updated with three new properties, `'Levels'`, `'TimeRange'`, and `'ScanIndices'`, which let you

filter and read a subset of the data. Updated with a 'Verbose' property to control the progress display while reading the file.

Compatibility Considerations

In Bioinformatics Toolbox Version 3.1 and earlier, the `Probes` field, in the structure returned by `affyread`, and the `PMIntensities` and `MMIntensities` fields, in the structure returned by `celintensityread`, were doubles. In Bioinformatics Toolbox Version 3.2, these fields are singles.

Sequence Utility Functions

Following is a new function:

- `cleavelookup` — Find cleavage rule for enzyme or compound.

The following functions are updated:

- `blastncbi` — Create remote NCBI BLAST report request ID or link to NCBI BLAST report. Updated to include a 'GapCosts' property, which lets you specify penalties for both opening and extending gaps, and an 'Entrez' property, which lets you limit searches using Entrez query syntax.
- `cleave` — Cleave amino acid sequence with enzyme. Includes a new input argument that specifies the name of an enzyme or compound for which a cleavage rule is specified in the literature.
- `rebasecuts` — Find restriction enzymes that cut nucleotide sequence. Updated to use Version 806 of REBASE, the Restriction Enzyme Database.
- `restrict` — Split nucleotide sequence at restriction site. Updated to use Version 806 of REBASE, the Restriction Enzyme Database.
- `seqlogo` — Display sequence logo for nucleotide or amino acid sequences. Updated to return a figure handle to the sequence logo.

Multiple Sequence Alignment Functions

Following is a new function:

- `multialignwrite` — Write multiple alignment to file using ClustalW ALN format.

The following function is updated:

- `multialignread` — Read multiple sequence alignment file. Updated to support PHYLIP (Phylogeny Inference Package) multiple sequence alignment files.

Gene Ontology Functions

The following function is updated:

- `goannotread` — Read annotations from Gene Ontology annotated file. Updated to include two new properties, 'Fields' and 'Aspect', which let you read a subset of the data in the annotated file.

Protein Analysis Functions

Following are new functions:

- `cleavelookup` — Find cleavage rule for enzyme or compound.
- `pdbsuperpose` — Superpose 3-D structures of two proteins.
- `pdbtransform` — Apply linear transformation to 3-D structure of molecule.

The following function is updated:

- `cleave` — Cleave amino acid sequence with enzyme. Includes a new input argument that specifies the name of an enzyme or compound for which a cleavage rule is specified in the literature.

Mass Spectrometry Functions

Following are new functions:

- `mzcdf2peaks` — Convert mzCDF structure to peak list.
- `mzcdfinfo` — Return information about netCDF file containing mass spectrometry data.
- `mzcdfread` — Read mass spectrometry data from netCDF file.
- `mzxmlinfo` — Return information about mzXML file.

The following function is updated:

- `mzxmlread` — Read data from mzXML file. Improved to read larger files, faster and without running out of memory. Updated with three new properties, 'Levels', 'TimeRange', and 'ScanIndices', which let you filter and read a subset of the data. Updated with a 'Verbose' property to control the progress display while reading the file.

Microarray File Format Functions

Following are new functions:

- `affygcma` — Perform GC Robust Multi-array Average (GCRMA) procedure on Affymetrix microarray probe-level data.
- `affyrma` — Perform Robust Multi-array Average (RMA) procedure on Affymetrix microarray probe-level data.
- `affysnpannotread` — Read Affymetrix Mapping DNA array data from CSV-formatted annotation file.
- `geoseriesread` — Read Gene Expression Omnibus (GEO) Series (GSE) format data.

The following functions are updated:

- `affyread` — Read microarray data from Affymetrix GeneChip file. Updated so that `Probes` field in the return structure is now a `single`, which reduces memory usage.
- `celintensityread` — Read probe intensities from Affymetrix CEL files. Updated so that `PMIntensities` and `MMIntensities` fields in the return structure are now `singles`, which reduces memory usage.
- `geosoftread` — Read Gene Expression Omnibus (GEO) SOFT format data. Updated to support Platform (GPL) records.
- `getgeodata` — Retrieve Gene Expression Omnibus (GEO) format data. Updated to support Platform (GPL) and Series (GSE) records.

Compatibility Considerations

In Bioinformatics Toolbox Version 3.1 and earlier, the `Probes` field, in the structure returned by `affyread`, and the `PMIntensities` and `MMIntensities` fields, in the structure returned by `celintensityread`, were `doubles`. In Bioinformatics Toolbox Version 3.2, these fields are `singles`.

Microarray Functions

Following are new functions:

- `affysnpintensitysplit` — Split Affymetrix SNP probe intensity information for alleles A and B.
- `affygcrrma` — Perform GC Robust Multi-array Average (GCRMA) procedure on Affymetrix microarray probe-level data.
- `affyrma` — Perform Robust Multi-array Average (RMA) procedure on Affymetrix microarray probe-level data.
- `DataMatrix` — Create `DataMatrix` object.

The following functions are updated:

- `ilmnbslookup` — Look up Illumina BeadStudio target (probe) sequence and annotation information. Updated to support BGX and TXT annotation files.
- `mattest` — Perform two-sample t-test to evaluate differential expression of genes from two experimental conditions or phenotypes. Updated to use unequal variance instead of equal variance for the test.
- `probesetlookup` — Look up information for Affymetrix probe set. Updated to accept multiple probe set IDs/names or gene IDs.

Compatibility Considerations

In Bioinformatics Toolbox Version 3.1 and earlier, the `mattest` function used equal variance for the test. In Bioinformatics Toolbox Version 3.2, the `mattest` function uses unequal variance for the test.

DataMatrix Object

Following is a new object:

- `DataMatrix` object — Data structure encapsulating data and metadata from microarray experiment so that it can be indexed by gene or probe identifiers and by sample identifiers.

DataMatrix Methods

There are many methods that let you create, index into, modify, create subsets, sort, perform operations on, analyze, and plot a DataMatrix object.

Demo for Visualization Tools

The Visualizing the Three-Dimensional Structure of a Molecule demo is updated to use the new `pdbsuperpose` function.

Demo for Sequence Analysis

The following is a new sequence analysis demo:

- Analyzing the Human Distal Gut Microbiome

Demos for Microarray Data Analysis

Following is a new microarray data analysis demo:

- Working with GEO Series Data

The Exploring Gene Expression Data demo is updated to use the new DataMatrix object.

The Analyzing Affymetrix SNP Arrays for DNA Copy Number Variants demo is updated to use two new functions: `affysnpannotread` and `affysnpintensitiesplit`.

The Preprocessing Affymetrix Microarray Data at the Probe Level demo is updated to use two new functions: `affygcrrma` and `affyrma`.

Version 3.1 (R2008a) Bioinformatics Toolbox Software

This table summarizes what's new in Version 3.1 (R2008a):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	Yes—Details labeled as Compatibility Considerations , below. See also Summary.	Bug Reports Includes fixes	No

New and updated features in this version include:

- “Data Format and Database Functions” on page 23
- “Sequence Utility Functions” on page 24
- “Pairwise Sequence Alignment Functions” on page 25
- “Phylogenetic Tree Tools Function” on page 25
- “Protein Analysis Functions” on page 25
- “Microarray File Format Functions” on page 26
- “Microarray Functions” on page 26
- “Object” on page 28
- “Clustergram Methods” on page 28
- “Demo for Sequence Analysis” on page 29
- “Demo for Microarray Data Analysis” on page 29
- “Demo for Visualization Tools” on page 29
- “Demos for Mass Spectrometry Data Analysis” on page 29

Data Format and Database Functions

Following is a new function:

- `ilmnbsread` — Read microarray data exported from Illumina BeadStudio software.

The following functions are updated:

- `celintensityread` — Read probe intensities from Affymetrix CEL files. Updated output structure to include a new field, `GroupNumbers`, which contains group numbers of probes.
- `fastawrite` — Write to file using FASTA format. Updated such that if you specify an existing file, new data is appended to the file instead of overwriting it.
- `getgenbank` — Retrieve sequence information from GenBank® database. Updated such that if you use the `'ToFile'` property and specify an existing file, new data is appended to the file instead of overwriting it. Updated to allow you to access a partial sequence by adding new property `'PartialSeq'`.
- `getgenpept` — Retrieve sequence information from GenPept database. Updated such that if you use the `'ToFile'` property and specify an existing file, new data is appended to the file instead of overwriting it. Updated to allow you to access a partial sequence by adding new property `'PartialSeq'`.
- `getgeodata` — Retrieve Gene Expression Omnibus (GEO) SOFT format data. Updated to retrieve both Sample (GSM) and Data Set (GDS) data.

Compatibility Considerations

In Bioinformatics Toolbox Version 3.0 and earlier, when writing to files using the `fastawrite` function or the `getgenbank` or `getgenpept` functions with the `'ToFile'` property, if you specified an existing file, the file was overwritten. In Bioinformatics Toolbox Version 3.1, if you specify an existing file, new data is appended to the file instead of overwriting it.

Sequence Utility Functions

The following functions are updated:

- `evalrasmolscript` — Send RasMol script commands to Molecule Viewer window. Updated to use Version 11.4 of the Jmol molecule viewer.

- `molviewer` — Display and manipulate 3-D molecule structure. Updated to use Version 11.4 of the Jmol molecule viewer.
- `ramachandran` — Draw Ramachandran plot for Protein Data Bank (PDB) data. Updated to handle PDB files with multiple chains and models by adding three properties: 'Chain', 'Plot', and 'Model'. Updated Ramachandran plot to mark glycine residues and display reference regions by adding three properties: 'Glycine', 'Regions', and 'RegionDef'. Updated Ramachandran plot to display amino acid information in ToolTip. Updated to easily determine the names and sequence positions of amino acids corresponding to torsion angles by creating an output structure.
- `rebasecuts` — Find restriction enzymes that cut nucleotide sequence. Updated to use Version 710 of REBASE, the Restriction Enzyme Database.
- `restrict` — Split nucleotide sequence at restriction site. Updated to use Version 710 of REBASE, the Restriction Enzyme Database.

Pairwise Sequence Alignment Functions

The following functions are updated:

- `nwalign` — Globally align two sequences using Needleman-Wunsch algorithm. Updated to improve pairwise sequence performance.
- `swalign` — Locally align two sequences using Smith-Waterman algorithm. Updated to improve pairwise sequence performance.

Phylogenetic Tree Tools Function

The following function is updated:

- `dnds` — Estimate synonymous and nonsynonymous substitution rates. Updated by adding 'AdjustStops' property to control whether stop codons are excluded from calculations.

Protein Analysis Functions

The following functions are updated:

- `evalrasmolscript` — Send RasMol script commands to Molecule Viewer window. Updated to use Version 11.4 of the Jmol molecule viewer.

- `molviewer` — Display and manipulate 3-D molecule structure. Updated to use Version 11.4 of the Jmol molecule viewer.
- `ramachandran` — Draw Ramachandran plot for Protein Data Bank (PDB) data. Updated to handle PDB files with multiple chains and models by adding three properties: 'Chain', 'Plot', and 'Model'. Updated Ramachandran plot to mark glycine residues and display reference regions by adding three properties: 'Glycine', 'Regions', and 'RegionDef'. Updated Ramachandran plot to display amino acid information in ToolTip. Updated to easily determine the names and sequence positions of amino acids by creating an output structure.

Microarray File Format Functions

Following is a new function:

- `ilmnbsread` — Read microarray data exported from Illumina BeadStudio software.

The following functions are updated:

- `celintensityread` — Read probe intensities from Affymetrix CEL files. Updated output structure to include a new field, `GroupNumbers`, which contains group numbers of probes.
- `getgeodata` — Retrieve Gene Expression Omnibus (GEO) SOFT format data. Updated to retrieve both Sample (GSM) and Data Set (GDS) data.

Microarray Functions

Following are new functions:

- `affysnpquartets` — Create table of SNP probe quartet results for Affymetrix probe set.
- `cghfreqplot` — Display frequency of DNA copy number alterations across multiple samples.
- `ilmnbslookup` — Look up Illumina BeadStudio target (probe) sequence and annotation information.
- `redbluecmap` — Create red and blue color map.

The following functions are updated:

- `clustergram` — Compute hierarchical clustering, display dendrogram and heat map, and create clustergram object.

Updated properties include:

- `'Linkage'` — Can specify linkage method separately for rows and columns.
- `'Dendrogram'` — Can specify color threshold separately for rows and columns.

Replaced properties include:

- `'Dimension'` — Replaced by the `'Cluster'` property, which lets you cluster along the columns, rows, or both.
- `'Pdist'` — Replaced by `'RowPdist'` and `'ColumnPdist'` properties.

New properties include:

- `'Standardize'` — Specifies the dimension for standardizing the data.
- `'DisplayRange'` — Specifies the display range of standardized values.
- `'LogTrans'` — Controls the \log_2 transform of the data.
- `'Impute'` — Specifies a function and properties to impute missing data.
- `'RowMarker'` — Adds color and text marker to a group of rows.
- `'ColumnMarker'` — Adds color and text marker to a group of columns.

The interactivity of the clustergram figure is enhanced with the following features:

- Select a group of rows or columns and display the group number and genes or samples within.
 - Create a new clustergram of only a group of the data.
 - Export data as a clustergram object or structure in the MATLAB Workspace.
- `maboxplot` — Create box plot for microarray data. Updated by adding `'BoxPlot'` property, which lets you specify arguments to pass to the `boxplot` function, which creates the box plot.

- `mairplot` — Create intensity versus ratio scatter plot of microarray data. Updated by adding 'PlotOnly' property, which lets you display the scatter plot without user interface components.
- `mattest` — Perform two-sample t-test to evaluate differential expression of genes from two experimental conditions or phenotypes. Updated by adding 'Bootstrap' property to run bootstrap tests.
- `mavolcanoplot` — Create significance versus gene expression ratio (fold change) scatter plot of microarray data. Updated by adding 'PlotOnly' property, which lets you display the volcano plot without user interface components.
- `probesetvalues` — Create table of Affymetrix probe set intensity values. Updated by adding 'Background' property to control the background correction.
- `zonebackadj` — Perform background adjustment on Affymetrix microarray probe-level data using zone-based method. Updated to return a third output containing the estimated background values for each probe.

Compatibility Considerations

In Bioinformatics Toolbox Version 3.0 and earlier, the `clustergram` function included 'Dimension' and 'Pdist' properties. In Bioinformatics Toolbox Version 3.1, the 'Dimension' property is replaced by the 'Cluster' property, and the 'Pdist' property is replaced by the 'RowPdist' and 'ColumnPdist' properties.

Object

Following is a new object:

- `clustergram` object — Object containing hierarchical clustering analysis data.

Clustergram Methods

The following are new methods of a `clustergram` object:

- `get` — Retrieve information about `clustergram` object.

- `plot` — Render clustergram heat map and dendrograms for clustergram object.
- `set` — Set property of clustergram object.
- `view` — View clustergram heat map and dendrograms for clustergram object.

Demo for Sequence Analysis

The following is a new sequence analysis demo:

- Performing a Metagenomic Analysis of a Sargasso Sea Sample

Demo for Microarray Data Analysis

The following is a new microarray data analysis demo:

- Analyzing Affymetrix SNP Arrays for DNA Copy Number Variants

Demo for Visualization Tools

The following is a new visualization tool demo:

- Working with the Clustergram Function

Demos for Mass Spectrometry Data Analysis

- The Batch Processing of Spectra Using Distributed Computing demo is updated to use the latest features of the Parallel Computing Toolbox™ version 3.3, and is now called Batch Processing of Spectra Using Sequential and Parallel Computing
- The Preprocessing Raw Mass Spectrometry Data demo is updated with state-of-the-art examples for peak detection using wavelets denoising, binning by hierarchical clustering, and binning by dynamic programming.

Version 3.0 (R2007b) Bioinformatics Toolbox Software

This table summarizes what's new in Version 3.0 (R2007b):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	Yes—Details labeled as Compatibility Considerations , below. See also Summary.	Bug Reports Includes fixes	No

New and updated features in this version include:

- “Data Format and Database Functions” on page 30
- “Microarray File Format Functions” on page 31
- “Microarray Functions” on page 31
- “Sequence Conversion, Utility, and Visualization Functions” on page 31
- “Mass Spectrometry Functions” on page 32
- “Statistical Learning Functions” on page 32
- “Gene Ontology Methods” on page 32
- “Demos for Microarray Data Analysis” on page 33
- “Demos for Sequence Analysis” on page 33
- “Demo for Graph Theory Analysis” on page 34

Data Format and Database Functions

Following are new functions:

- `blastformat` — Create local BLAST database.
- `blastreadlocal` — Read data from local BLAST report.
- `cytobandread` — Read cytogenetic banding information.

The following function was updated:

- `affyread` — Read microarray data from Affymetrix GeneChip file. Updated the structure returned when reading a CDF library file. The structure contains three new subfields: `GroupNumber`, `Direction`, and `GroupName`.

Microarray File Format Functions

Following is a new function:

- `cytobandread` — Read cytogenetic banding information.

The following function was updated:

- `affyread` — Read microarray data from Affymetrix GeneChip file. Updated the structure returned when reading a CDF library file. The structure contains three new subfields: `GroupNumber`, `Direction`, and `GroupName`.

Microarray Functions

Following are new functions:

- `chromosomeplot` — Plot chromosome ideogram with G-banding pattern.
- `cghcbs` — Perform circular binary segmentation (CBS) on array-based comparative genomic hybridization (aCGH) data.

The following function is updated:

- `probesetvalues` — Create table of Affymetrix probe set intensity values. Updated return matrix, which contains intensity values for probe-level data, to include two new fields: `GroupNumber` and `Direction`. Updated to return a second output containing the column names for the return matrix, which contains intensity values for probe-level data.

Sequence Conversion, Utility, and Visualization Functions

Following are new functions:

- `blastlocal` — Perform search on local BLAST database to create BLAST report.

- `rnaconvert` — Convert secondary structure of RNA sequence between bracket and matrix notations.
- `rnafold` — Predict minimum free-energy secondary structure of RNA sequence.
- `rnaplot` — Draw secondary structure of RNA sequence.

Mass Spectrometry Functions

The following function is updated:

- `mssalign` — Align mass spectra from multiple peak lists from LC/MS or GC/MS data set. Updated to include a new property, `ShowEstimation`, which controls the display of an assessment plot relative to the estimation method and the vector of common mass/charge (m/z) values.

Statistical Learning Functions

The following function is updated:

- `svmsmoset` — Create or edit Sequential Minimal Optimization (SMO) options structure. Updated default values for the `MaxIter` and `KernelCacheLimit` properties. Changed the `Display` property so that when set to `iter`, a report displays every 500 iterations instead of 10.

Compatibility Considerations

In Bioinformatics Toolbox Version 2.6 and earlier, the `svmsmoset` function used a `MaxIter` property with a default of 1500 and a `KernelCacheLimit` property with a default of 7500. In Bioinformatics Toolbox Version 3.0, the defaults are 15000 and 5000, respectively. Also, when you set the `Display` property to `iter`, a report displays every 500 iterations instead of 10.

Gene Ontology Methods

The following methods of a gene ontology object are updated:

- `geneont.getancestors` — Find terms that are ancestors of specified Gene Ontology term. Updated to also return the number of times each ancestor is found. Updated to include two new properties, `Relationtype`, which specifies a relationship type to search for in the gene ontology, and

'Exclude', which controls excluding the original queried term(s) from the output, unless the term was reached while searching the gene ontology.

- `geneont.getdescendants` — Find terms that are descendants of specified Gene Ontology term. Updated to also return the number of times each descendant is found. Updated to include two new properties, 'Relationtype', which specifies a relationship type to search for in the gene ontology, and 'Exclude', which controls excluding the original queried term(s) from the output, unless the term was reached while searching the gene ontology.
- `geneont.getrelatives` — Find terms that are relatives of specified Gene Ontology term. Updated to also return the number of times each relative is found. Updated to include three new properties, 'Levels', which specifies the number of levels up and down to search in the gene ontology, 'Relationtype', which specifies a relationship type to search for in the gene ontology, and 'Exclude', which controls excluding the original queried term(s) from the output, unless the term was reached while searching the gene ontology.

Demos for Microarray Data Analysis

The following are two new microarray data analysis demos:

- Detecting DNA Copy Number Alteration in Array-Based CGH Data
- Analyzing Array-Based CGH Data Using Bayesian Hidden Markov Modeling

Demos for Sequence Analysis

The following are two new sequence analysis demos:

- Predicting and Visualizing the Secondary Structure of RNA Sequences
- Identifying Over-Represented Regulatory Motifs

The Investigating the Bird Flu Virus demo was updated to demonstrate how to write KML-formatted files, which can be used by Google™ Earth to display geospatial data.

Demo for Graph Theory Analysis

The following is a new graph theory demo:

- Working with Graph Theory Functions

Version 2.6 (R2007a+) Bioinformatics Toolbox Software

This table summarizes what's new in Version 2.6 (Release 2007a+):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	Yes—Details labeled as Compatibility Considerations , below. See also Summary.	Bug Reports Includes fixes	No

New and updated functions in this version include:

- “Data Formats and Databases Functions” on page 35
- “Microarray File Formats Functions” on page 36
- “Microarray Utility Functions” on page 36
- “Microarray Normalization and Filtering Functions” on page 37
- “Mass Spectrometry Functions” on page 37
- “Demos for Mass Spectrometry Functions” on page 37

Data Formats and Databases Functions

The following functions are updated:

- `affyread` — Read microarray data from Affymetrix GeneChip file. Updated to read Affymetrix files from expression, genotyping, or resequencing assays on all platforms, except Solaris™.
- `celintensityread` — Read probe intensities from Affymetrix CEL files. Updated to read Affymetrix CEL and CDF files from expression or genotyping assays on all platforms, except Solaris.
- `mzxmlread` — Read mzXML file into MATLAB as structure. Updated to read mzXML files that conform to the mzXML 2.1 specification or earlier specifications.

Compatibility Considerations

In Bioinformatics Toolbox Version 2.6, the structure returned by `affyread` when reading a CHP file from an expression assay no longer contains a `ProbePairs` field. The `ProbePairs` field still exists in the structure returned by `affyread` when reading a CDF file.

Microarray File Formats Functions

The following functions are updated:

- `affyread` — Read microarray data from Affymetrix GeneChip file. Updated to read Affymetrix files from expression, genotyping, or resequencing assays on all platforms, except Solaris.
- `celintensityread` — Read probe intensities from Affymetrix CEL files. Updated to read Affymetrix CEL and CDF files from expression or genotyping assays on all platforms, except Solaris.

Compatibility Considerations

In Bioinformatics Toolbox Version 2.6, the structure returned by `affyread` when reading a CHP file from an expression assay no longer contains a `ProbePairs` field. The `ProbePairs` field still exists in the structure returned by `affyread` when reading a CDF file.

Microarray Utility Functions

The following function is updated:

- `probesetplot` — Plot Affymetrix probe set intensity values. Updated to accept structures created from CEL and CDF files, instead of a structure created from a CHP file.

Compatibility Considerations

In Bioinformatics Toolbox Version 2.5 and earlier, the `probesetplot` function accepted a structure created from a CHP file as input. Currently it requires two structures: one created from a CEL file and one created from a CDF library file. If you have any scripts that call the `probesetplot` function, you need to update them to provide the correct input arguments.

Microarray Normalization and Filtering Functions

Following is a new function:

- `zonebackadj` — Perform background adjustment on Affymetrix microarray probe-level data using zone-based method.

Mass Spectrometry Functions

The following function is updated:

- `mzxmlread` — Read mzXML file into MATLAB as structure. Updated to read mzXML files that conform to the mzXML 2.1 specification or earlier specifications.

Following is a new function you can use to calibrate and/or synchronize multidimensional mass spectrometry data:

- `samplealign` — Align two data sets containing sequential observations by introducing gaps.

Demos for Mass Spectrometry Functions

The following are two new mass spectrometry demos:

- Visualizing and Preprocessing Hyphenated Mass-Spectrometry Data Sets for Metabolite and Protein/Peptide Profiling
- Differential Analysis of Complex Protein and Metabolic Mixtures Using Liquid Chromatography/Mass Spectrometry (LC/MS)

Version 2.5 (R2007a) Bioinformatics Toolbox Software

This table summarizes what's new in Version 2.5 (Release 2007a):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	Yes—Details labeled as Compatibility Considerations , below. See also Summary.	Bug Reports Includes fixes	No

New, updated, and deprecated functions in this version include:

- “Data Formats and Database Functions” on page 39
- “Demo for Data Formats and Database Functions” on page 39
- “Statistical Learning Functions” on page 40
- “Protein Analysis and Sequence Utilities Functions” on page 40
- “Demo for Protein Analysis and Sequence Utilities Functions” on page 41
- “Sequence Alignment Functions” on page 41
- “Demo for Sequence Alignment Functions” on page 42
- “Microarray File Formats Functions” on page 42
- “Microarray Normalization and Filtering Functions” on page 42
- “Demo for Microarray File Formats, Normalization, and Filtering Functions” on page 43
- “Microarray Data Analysis and Visualization Functions” on page 43
- “Demo for Microarray Data Analysis and Visualization Functions” on page 43
- “Mass Spectrometry Functions” on page 43
- “Phylogenetic Tree Tools Functions” on page 44
- “Demos for Phylogenetic Tree Tools Functions” on page 44

- “Phylogenetic Tree Methods” on page 45

Data Formats and Database Functions

Following are new functions for reading and creating files:

- `affyprobeseqread` — Read data file containing probe sequence information for Affymetrix GeneChip array.
- `pdbwrite` — Write to file using Protein Data Bank (PDB) format.

The following functions were updated:

- `celintensityread` — Read probe intensities from Affymetrix CEL files (Windows® 32). Updated so that the order of columns (CEL files) in return matrices `PMIntensities` and `MMIntensities` matches the order of CEL files in the `CELFiles` input argument.
- `pdbread` — Read data from Protein Data Bank (PDB) file. Updated so that the six fields containing coordinate information (`Atom`, `AtomSD`, `AnisotropicTemp`, `AnisotropicTempSD`, `Terminal`, and `HeterogenAtom`) are now subfields within the `Model` field of the MATLAB structure. Updated to include a new property, `ModelNum`, which reads only the specified model from a PDB-formatted text file.

Compatibility Considerations

In Bioinformatics Toolbox Version 2.4 and earlier, the `celintensityread` function ordered the columns (CEL files) of return matrices `PMIntensities` and `MMIntensities` alphabetically.

In Bioinformatics Toolbox Version 2.4 and earlier, the `pdbread` function stored coordinate information in six fields (`Atom`, `AtomSD`, `AnisotropicTemp`, `AnisotropicTempSD`, `Terminal`, and `HeterogenAtom`) within the MATLAB structure. These six fields are now subfields within the `Model` field of the MATLAB structure.

Demo for Data Formats and Database Functions

The Accessing NCBI Entrez Databases with E-Utilities demo illustrates how to programatically search and retrieve data.

Statistical Learning Functions

Following are new functions:

- `optimalleaforder` — Determine optimal leaf ordering for hierarchical binary cluster tree.
- `svmsmoset` — Create or edit Sequential Minimal Optimization (SMO) options structure.

The following function was updated:

- `svmtrain` — Train support vector machine classifier. Updated to include a new SMO method and a new property, `SMO_Opts`, which provides options for the SMO method. The `BoxConstraint` property has changed, including a new default value.

Compatibility Considerations

In Bioinformatics Toolbox Version 2.4 and earlier, the `svmtrain` function used

a `BoxConstraint` property with a default of $\frac{1}{\sqrt{\epsilon}}$. In Bioinformatics Toolbox Version 2.5, the default is 1, which can lead to slightly different results.

Protein Analysis and Sequence Utilities Functions

Following are new functions:

- `evalrasmolscript` — Send RasMol script commands to molecule viewer.
- `molviewer` — Display and manipulate 3-D molecule structure.
- `proteinpropplot` — Plot properties of amino acid sequence.
- `seqinsertgaps` — Insert gaps into nucleotide or amino acid sequence.

The following functions were updated:

- `featuresparse` — Parse features from GenBank, GenPept, or EMBL data. Updated to include a new property, `Sequence`, which controls the extraction, when possible, of the sequences.

- `oligoprop` — Calculate sequence properties of DNA oligonucleotide. Updated to handle ambiguous N characters in a sequence.

The following function is obsolete:

- `pdbplot` — Plot 3-D protein structure. This function was replaced by the `molviewer` function.

Compatibility Considerations

In Bioinformatics Toolbox Version 2.5, the `pdbplot` function was replaced by the `molviewer` function. If you have any scripts that call the `pdbplot` function, you need to update them to call the `molviewer` function.

Demo for Protein Analysis and Sequence Utilities Functions

The Visualizing the Three-dimensional Structure of a Molecule demo illustrates the `molviewer` function.

Sequence Alignment Functions

The following function was updated:

- `seqpdist` — Calculate pairwise distance between sequences. Updated to assume that all input sequences are aligned if they have the same length, regardless of the presence of gaps. If you know your input sequences are not aligned, you can align them before passing them to `seqpdist` (for example, using `multialign`), or set `PairwiseAlignment` to `true` when using `seqpdist`.

Compatibility Considerations

In Bioinformatics Toolbox Version 2.4 and earlier, the `seqpdist` function assumed all input sequences were aligned if they had the same length and at least one gap.

Demo for Sequence Alignment Functions

The Comparing Whole Genomes demo illustrates how to compare features of organisms on a genomic evolution scale.

Microarray File Formats Functions

Following is a new function:

- `affyprobeseqread` — Read data file containing probe sequence information for Affymetrix GeneChip array.

The following function was updated:

- `celintensityread` — Read probe intensities from Affymetrix CEL files (Windows 32). Updated so that the order of columns (CEL files) in return matrices `PMIntensities` and `MMIntensities` matches the order of CEL files in the `CELFiles` input argument.

Compatibility Considerations

In Bioinformatics Toolbox Version 2.4 and earlier, the `celintensityread` function ordered the columns (CEL files) of return matrices `PMIntensities` and `MMIntensities` alphabetically.

Microarray Normalization and Filtering Functions

Following are new functions:

- `affyprobeaffinities` — Compute Affymetrix probe affinities from their sequences and MM probe intensities.
- `gcrmabackadj` — Perform GC Robust Multi-array Average (GCRMA) background adjustment on Affymetrix microarray probe-level data using sequence information.
- `gcrma` — Perform GC Robust Multi-array Average (GCRMA) background adjustment, quantile normalization, and median-polish summarization on Affymetrix microarray probe-level data.

Demo for Microarray File Formats, Normalization, and Filtering Functions

The Preprocessing Affymetrix Microarray Data at the Probe Level demo illustrates the `affyprobeseqread`, `affyprobeaffinities`, `gcrmabackadj`, and `gcrma` functions.

Microarray Data Analysis and Visualization Functions

Following is a new function:

- `mafdr` — Estimate false discovery rate (FDR) of differentially expressed genes from two experimental conditions or phenotypes.

The following function was updated:

- `mattest` — Perform two-tailed t-test to evaluate differential expression of genes from two experimental conditions or phenotypes. Updated to include a new property, `Permute`, which controls whether permutation tests are run.

Demo for Microarray Data Analysis and Visualization Functions

The Exploring Gene Expression Data demo illustrates the `mattest` and `mafdr` functions.

Mass Spectrometry Functions

Following are new functions:

- `msdotplot` — Plot set of peak lists from LC/MS or GC/MS data set.
- `mssalign` — Align mass spectra from multiple peak lists from LC/MS or GC/MS data set.
- `mspeaks` — Convert raw mass spectrometry data to peak list (centroided data).
- `msppresample` — Resample mass spectrometry signal while preserving peaks.
- `mzxml2peaks` — Convert mzXML structure to peak list.

The following function was updated:

- `msheatmap` — Create pseudocolor image of set of mass spectra. Updated to handle LC/MS and GC/MS data.

Phylogenetic Tree Tools Functions

Following is a new function:

- `seqinsertgaps` — Insert gaps into nucleotide or amino acid sequence.

The following functions were updated:

- `dnds` — Estimate synonymous and nonsynonymous substitution rates. Updated to include two new properties, `Verbose`, which controls the display of the codons considered in the computations and their amino acid translations, and `Window`, which performs the calculations over a sliding window.
- `dndsm1` — Estimate synonymous and nonsynonymous substitution rates using maximum likelihood method. Updated to include a new property, `Verbose`, which controls the display of the codons considered in the computations and their amino acid translations.
- `seqpdist` — Calculate pairwise distance between sequences. Updated to assume that all input sequences are aligned if they have the same length, regardless of the presence of gaps. If you know your input sequences are not aligned, you can align them before passing them to `seqpdist` (for example, using `multialign`), or set `PairwiseAlignment` to `true` when using `seqpdist`.

Compatibility Considerations

In Bioinformatics Toolbox Version 2.4 and earlier, the `seqpdist` function assumed all input sequences were aligned if they had the same length and at least one gap.

Demos for Phylogenetic Tree Tools Functions

The following demos illustrate the `nwalign`, `seqinsertgaps`, `dnds`, and `multialign` functions:

- Analyzing Synonymous and Nonsynonymous Substitution Rates
- Investigating the Bird Flu Virus

The Reconstructing the Origin and the Diffusion of the SARS Epidemic demo presents an analysis of the SARS epidemic.

Phylogenetic Tree Methods

Following is a new method of a phytree object:

- `reorder` — Reorder leaves of phylogenetic tree.

Version 2.4 (R2006b) Bioinformatics Toolbox Software

This table summarizes what's new in Version 2.4 (Release 2006b):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	Yes Summary	Bug Reports Includes fixes	No

New functions, obsoleted functions, and changes introduced in this version are

- “Data Formats and Database Functions” on page 46
- “Sequence Utilities Functions” on page 47
- “Sequence Visualization Functions” on page 47
- “Multiple Sequence Alignment Functions” on page 47
- “Microarray File Formats” on page 47
- “Microarray Data Analysis and Visualization Functions” on page 48
- “Graph Theory Functions” on page 48
- “Graph Visualization Methods” on page 49
- “Phylogenetic Tree Methods” on page 49

Data Formats and Database Functions

Following is a new function for getting data into the MATLAB environment:

- `mzxmlread` — Read mzXML file into the MATLAB software as structure.

The following functions were updated:

- `celintensityread` — Read probe intensities from Affymetrix CEL files (Windows 32). Updated to include a new property, `Verbose`, which controls the display of a progress report showing the name of each CEL file as it is read.

- `fastaread` — Read data from FASTA file. Updated to include a new property, `Blockread`, which controls reading a single entry or block of entries from a file.
- `geosoftread` — Read Gene Expression Omnibus (GEO) SOFT format data. Updated to read Data Set (GDS) files as well as Sample (GSM) files.
- `getblast` — BLAST report from NCBI Web site. Updated to include a new property, `WaitTilReady`, which pauses the MATLAB software and waits a specified time (minutes) for a report from the NCBI Web site.
- `scfread` — Read trace data from SCF file. Updated to include more output options.

Sequence Utilities Functions

Following is a new function for parsing sequence data:

- `featuresparse` — Parse features from GenBank, GenPept, or EMBL data.

Sequence Visualization Functions

The following function was updated:

- `seqtool` — Open tool to interactively explore biological sequences. Updated to download sequences from the EMBL database, interactively move the viewing frame in the Sequence Viewer by pressing and holding **Ctrl** while click-dragging, and export an amino acid translation as a FASTA file or to the MATLAB Workspace.

Multiple Sequence Alignment Functions

The following function was updated:

- `multialignviewer` — Open viewer for multiple sequence alignments. Updated to export consensus sequences.

Microarray File Formats

The following function was updated:

- `celintensityread` — Read probe intensities from Affymetrix CEL files (Windows 32). Updated to include a new property, `Verbose`, which controls

the display of a progress report showing the name of each CEL file as it is read.

Microarray Data Analysis and Visualization Functions

The following functions were updated:

- `clustergram` — Create dendrogram and heat map. Updated to include a new property, `OptimalLeafOrder`, which enables or disables the optimal leaf ordering calculation, which determines the leaf order that maximizes the similarity between neighboring leaves.
- `mairplot` — Create intensity versus ratio scatter plot for microarray signals. Updated to include a new property, `Type`, which creates either an IR plot or MA plot, changing the plot axes to log scale, and adding plot interactive features such as displaying gene labels, changing factor lines, normalizing data, and exporting data.
- `mapcaplot` — Create Principal Component plot of expression profile data. Updated by adding an export feature.
- `redgreenmap` — Create red and green colormap. Updated to include a new property, `Interpolation`, which sets the method for color interpolation.

Graph Theory Functions

Following are new functions for applying basic graph theory algorithms to sparse matrices:

- `graphallshortestpaths` — Find all shortest paths in graph.
- `graphconncomp` — Find strongly or weakly connected components in graph.
- `graphisdag` — Test for cycles in directed graph.
- `graphisomorphism` — Find isomorphism between two graphs.
- `graphisspantree` — Determine if tree is spanning tree.
- `graphmaxflow` — Calculate maximum flow and minimum cut in directed graph.
- `graphminspantree` — Find minimal spanning tree in graph.
- `graphpred2path` — Convert predecessor indices to paths.

- `graphshortestpath` — Solve shortest path problem in graph.
- `graphtopoorder` — Perform topological sort of directed acyclic graph.
- `graphtraverse` — Traverse graph by following adjacent nodes.

Graph Visualization Methods

Following are new methods for applying basic graph theory algorithms to a `biograph` object:

- `allshortestpaths` — Find all shortest paths in `biograph` object.
- `conncomp` — Find strongly or weakly connected components in `biograph` object.
- `getmatrix` — Get connection matrix from `biograph` object.
- `isdag` — Test for cycles in `biograph` object.
- `isomorphism` — Find isomorphism between two `biograph` objects.
- `isspantree` — Determine if tree created from `biograph` object is spanning tree.
- `maxflow` — Calculate maximum flow and minimum cut in `biograph` object.
- `minspantree` — Find minimal spanning tree in `biograph` object.
- `shortestpath` — Solve shortest path problem in `biograph` object.
- `topoorder` — Perform topological sort of directed acyclic graph extracted from `biograph` object.
- `traverse` — Traverse `biograph` object by following adjacent nodes.

Phylogenetic Tree Methods

Following is a new method for the `phytree` object:

- `getmatrix` — Convert `phytree` object into a relationship matrix.

Version 2.3 (R2006a+) Bioinformatics Toolbox Software

This table summarizes what's new in Version 2.3 (Release 2006a+):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	No	Bug Reports	No

New functions, obsoleted functions, and changes introduced in this version are

- “Data Formats and Databases Functions” on page 50
- “Sequence Utilities Functions” on page 51
- “Sequence Visualization Functions” on page 51
- “Statistical Learning Functions” on page 51
- “Microarray Functions” on page 51
- “Demo for Microarray Functions” on page 52

Data Formats and Databases Functions

The following functions are obsolete:

- `getpir` — Sequence data from PIR-PSD database. This function retrieved data from the PIR-PSD database. This database has been discontinued and this function no longer retrieves data. See <http://pir.georgetown.edu/pirwww/dbinfo/nref.shtml> for more details.
- `pirread` — Read data from Protein Information Resource (PIR) file. This function supported the data format of the PIR-PSD database. This database has been discontinued. See <http://pir.georgetown.edu/pirwww/dbinfo/nref.shtml> for more details.

Sequence Utilities Functions

The following function was updated to include five new databases, including `refseq_rna`, `refseq_genomic`, `env_nt`, `refseq_protein`, and `env_nr`:

- `blastncbi` — Generate remote BLAST request.

Sequence Visualization Functions

Following is a new function for visualizing sequence data:

- `featuresmap` — Draw linear or circular map of features from GenBank structure.

Statistical Learning Functions

The following function was updated to include three new properties, including `RBF_Sigma`, `BoxConstraint`, and `Autoscale`:

- `svmtrain` — Train support vector machine classifier.

Microarray Functions

The following function is supported on the Windows 32 platform only:

- `affyread` — Read microarray data from Affymetrix GeneChip file (Windows 32).

Following are new functions for preprocessing Affymetrix probe-level microarray data:

- `celintensityread` — Read probe intensities from Affymetrix CEL files (Windows 32).
- `rmabackadj` — Perform background adjustment on Affymetrix microarray probe-level data using Robust Multi-array Average (RMA) procedure.
- `rmasummary` — Calculate gene (probe set) expression values from Affymetrix microarray probe-level data using Robust Multi-array Average (RMA) procedure.
- `affyinvarsetnorm` — Perform rank invariant set normalization on probe intensities from multiple Affymetrix CEL or DAT files.

Following is a new function for two-color microarray normalization:

- `mainvarsetnorm` — Perform rank invariant set normalization on gene expression values from two experimental conditions or phenotypes.

Following are new functions for microarray differential expression analysis:

- `mattest` — Perform two-sample, two-tailed t-test to evaluate differential expression of genes from two experimental conditions or phenotypes.
- `mavolcanoplot` — Create significance versus gene expression ratio (fold change) scatter plot of microarray data.

Demo for Microarray Functions

New demo of the new microarray functions (Analyzing Affymetrix Microarray Gene Expression Data).

Version 2.2.1 (R2006a) Bioinformatics Toolbox Software

This table summarizes what's new in Version 2.2.1 (Release 2006a):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
No	No	Bug Reports	No

Version 2.2 (R14SP3+) Bioinformatics Toolbox Software

This table summarizes what's new in Version 2.2 (Release 14SP3+):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	No	Bug Reports	No

New features and changes introduced in this version are

- “Multiple Sequence Alignment Viewer” on page 54
- “Microarray Functions for Agilent Software” on page 54
- “Gene Ontology Database Functions” on page 54
- “Demo for Gene Ontology Functions” on page 55

Multiple Sequence Alignment Viewer

- `multialignviewer` — Interactively view, explore alignments, and make manual modifications.

Microarray Functions for Agilent Software

- `agferead` — Read an Agilent® Feature Extraction Software file.
- `magetfield` — Utility function to extract data from a microarray.

Gene Ontology Database Functions

- `geneont.geneont` — Import the Gene Ontology database from the Web.
- `geneont.getancestors`, `geneont.getdescendants`, `geneont.getrelatives` — Get a subset of the ontology.
- `goannotread` — Parse Gene Ontology Annotated files.
- `num2goid` — Convert numbers to Gene Ontology IDs.

Demo for Gene Ontology Functions

New demo for the new Gene Ontology functions (`geneontologydemo`) and working with whole genomes (`biomemorymapdemo`).

Version 2.1.1 (R14SP3) Bioinformatics Toolbox Software

This table summarizes what's new in Version 2.1.1 (Release 14SP3):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
No	No	Bug Reports	No

Version 2.1 (R14SP2+) Bioinformatics Toolbox Software

This table summarizes what's new in Version 2.1 (Release 14SP2+)

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	No	Bug Reports	No

New features and changes introduced in this version are:

- “Sequence Alignment Functions” on page 57
- “Sequence Statistics Functions” on page 58
- “Sequence Utilities Functions” on page 58
- “Phylogenetic Tree Functions” on page 58
- “Phylogenetic Tree Methods” on page 58
- “Microarray Functions” on page 58
- “Statistics Functions” on page 58

Sequence Alignment Functions

- `multialign` — Align multiple sequences using a progressive method with Distributed Computing Toolbox™ support.
- `multialignread` — Read multiple sequence alignment file.
- `profalign` — Align two profiles using Needleman-Wunsch global alignment.
- `showalignment` — Updated to show multiply aligned sequences.
- `seqpdist` — Updated to calculate pairwise distances between observations with Distributed Computing Toolbox support.

Sequence Statistics Functions

- `codonbias` — Calculate codon frequency for each amino acid in a DNA sequence.
- `cpgisland` — Locate CpG islands in a DNA sequence.

Sequence Utilities Functions

- `rebasecuts` — Find restriction enzymes that cut a protein sequence.
- `seqtool` — Graphical User Interface (GUI) for single sequence analysis.

Phylogenetic Tree Functions

- `dnds`, `dndsml` — Estimate synonymous and nonsynonymous substitutions rates.
- `seqneighjoin` — Reconstruct a phylogenetic tree with a Neighbor-joining method.

Phylogenetic Tree Methods

- `getcanonical` — Calculate the canonical form of a phylogenetic tree.
- `getnewickstr` — Create a Newick formatted string.
- `reroot` — Change the root of a phylogenetic tree.
- `subtree` — Extract a subtree.
- `weights` — Calculate weights for a phylogenetic tree.

Microarray Functions

`probesetplot` — Plot values for an Affymetrix CHP file probe set.

Statistics Functions

`rankfeatures` — Renamed function. The previous name was `sqlfeatures`.

Version 2.0.1 (R14SP2) Bioinformatics Toolbox Software

This table summarizes what's new in Version 2.0.1 (Release 14SP2):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	No	Bug Reports	No

New features and changes introduced in this version are

- “Updated RBASE Table” on page 59
- “Expanded Bioperl Demonstration” on page 59

Updated RBASE Table

RBASE is the enzyme table that the function `restrict` uses to locate sequence patterns.

Expanded Bioperl Demonstration

Example of calling the MATLAB software from Perl scripts now includes several examples of passing various types of data (both directly and by variant variable) back and forth between Perl and a MATLAB Automation Server. To view the demo, type `bioperldemo`.

Version 2.0 (R14SP1+) Bioinformatics Toolbox Software

This table summarizes what's new in Version 2.0 (Release 14SP1+):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	No	No bug fixes	No

New features and changes introduced in this version are

- “Mass Spectrometry Data Analysis” on page 60
- “Graph Visualization Object and Methods” on page 61
- “Statistical Learning” on page 61
- “Sequence Analysis” on page 61
- “Protein Analysis” on page 62
- “Microarray Analysis” on page 62
- “Updated Web Connectivity Function” on page 63

Mass Spectrometry Data Analysis

Following are new functions designed for preprocessing and classification of raw mass spectrometry data from SELDI-TOF and MALDI-TOF spectrometers.

- `msresample` — Resample with antialias filtering.
- `msbackadj` — Correct a baseline by estimation.
- `msalign` — Align a spectrum to a set of candidate peaks.
- `msheatmap` — Draw a heat map image for a set of spectra and check alignments.
- `msnorm` — Normalize a set of spectra.
- `mslowess` — Nonparametric smoothing using the Lowess method.

- `mssgolay` — Least-squares polynomial smoothing.
- `msviewer` — Plot a spectrum or a set of spectra.

Graph Visualization Object and Methods

New object and set of methods to view relationships between data with interactive maps.

- `biograph` — Function to create a biograph object.
- `dolayout` — Calculate node and edge positions.
- `getnodesbyid` — Get handles to nodes.
- `getedgesbynodeid` — Get handles to edges.
- `view` — Render a graph in its viewer.
- `getancestors` — Find ancestors.
- `getdescendants` — Find descendants.
- `getrelatives` — Find neighbors.

Statistical Learning

New set of functions to classify data and identify features in the data.

- `classperf` — Evaluate the performance of a classifier.
- `crossvalind` — Cross-validation index generation.
- `knnclassify` — K-Nearest neighbor classifier.
- `knnimpute` — Impute missing data using the nearest neighbor method.
- `randfeatures` — Randomized subset feature selection.
- `sqt1features` — Sequential forward feature selection. This function will be renamed to `rankfeatures` in Version 2.1.
- `svmclassify` — Classify using a support vector machine classifier.
- `svmtrain` — Train a support vector machine classifier.

Sequence Analysis

New functions for analysis and visualization of multiple sequences.

- `seqconsensus` — Computes the consensus sequence for a set of sequences.
- `seqlogo` — Displays sequence logos for DNA and protein sequences.
- `seqprofile` — Computes the sequence profile of a multiple alignment.

Updated functions.

- `palindromes` — Updated to allow for gaps in the palindrome.
- `seqshoworfs`, `seqshowwords`, `showalignment` — Updated to display the results in a Figure window. (This may cause problems on the Mac®.)

In Bioinformatics Toolbox 2.0 the functions `seqlogo`, `seqshowwords`, `seqshoworfs`, and `showalignment` use Java™ based figures. Currently on the Macintosh®, Java figures are not enabled by default. If you use these functions on a Macintosh, you should start the MATLAB software with

```
matlab -useJavaFigures
```

Protein Analysis

- `pdbplot` — Plots 3-D backbone structure of proteins in a PDB file.

Microarray Analysis

- `quantilenorm` — Quantile normalization.

New set of functions for working with Affymetrix GeneChip data sets.

- `probelibraryinfo` — Get library information for a probe.
- `probesetlink` — Show probe set information from NetAffx™.
- `probesetlookup` — Get gene information for a probe set.
- `probesetplot` — Plot probe set values.
- `probesetvalues` — Get probe set values from CEL and CDF information.
- `manorm` — Normalization by scaling and centering replaces the functions `mamadnorm` and `mameannorm`.

- `affyread` — Updated with output structures that have changed slightly. Some redundant fields have been removed from CDF and CHP structure. GIN database files are now supported. Version 4 of the Affymetrix GDAC File Access Runtime Libraries is provided.

Note If you use `mamadnorm` or `mameannorm` in any of your personal M-files, please update your files with the new function `manorm`. These functions are now obsolete and may be removed from future releases of the Bioinformatics Toolbox software.

- `geosoftread` — Updated with supports Gene Expression Omnibus Database records (GDS files).
- `maimage` — Updated with supports Affymetrix CEL data.
- `maboxplot` — Now supports Affymetrix CHP data.

Updated Web Connectivity Function

`getgenbank` — Now returns CDS information for a gene in a structure allowing direct access to the transcribed sequence.

Version 1.1.1 (R14SP1) Bioinformatics Toolbox Software

This table summarizes what's new in Version 1.1.1 (Release 14SP1):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
No	No	No bug fixes	No

Version 1.1 (R14) Bioinformatics Toolbox Software

This table summarizes what's new in Version 1.1 (Release 14)

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	No	No bug fixes	No

New features and changes introduced in this version are

- “Phylogenetic Analysis Functions” on page 65
- “Phylogenetic Tree Object and Methods” on page 66
- “Hidden Markov Model (HMM) Profiles” on page 66
- “BLAST Functions” on page 67
- “Microarray Functions” on page 67
- “Protein Analysis Function” on page 67
- “Sequence Alignment Functions” on page 67
- “New Demos” on page 67

Phylogenetic Analysis Functions

New functions for phylogenetic tree creation and analysis.

- `phytreeread` — Read a Newick-formatted tree file into the MATLAB workspace and return a `phytree` object with data from the file. Data in the file uses the Newick (New Hampshire) format for describing trees.
- `phytreewrite` — Copy the contents of a `phytree` object from the MATLAB workspace to a file.
- `phytreetool` — Interactive GUI that allows you to view, edit, and explore phylogenetic tree data. This GUI allows branch pruning, reordering, renaming, and distance exploring. It can also open or save Newick-formatted files.

- `seqlinkage` — Construct a phylogenetic tree from pairwise distances.
- `seqpdist` — Calculate the pairwise distance between biological sequences.

Phylogenetic Tree Object and Methods

New object for manipulating phylogenetic tree data.

- `phytree` — Function to create a `phytree` object.
- `get` — Get property values from a `phytree` object
- `getbyname` — Get node names from a `phytree` object.
- `pdist` — Calculate the patristic distances between pairs of leaf nodes.
- `plot` — Draw a phylogenetic tree object in a MATLAB Figure window as a phylogram, cladogram, or radial tree.
- `prune` — Remove nodes from a phylogenetic tree.
- `select` — Select branches and leaves from a phylogenetic tree using a specified criteria.
- `view` — Open a phylogenetic tree in a `phytreetool` window.

Hidden Markov Model (HMM) Profiles

Updated Hidden Markov Model profile functions.

- The model structure that HMM functions use now includes loop and null transition probabilities. You can read null and loop probabilities from PFAM files using `pfamhmmread`, and, from PFAM Web databases, using `gethmmprof`.
- When the function `hmmprofstruct` builds an HMM model, the loop and null transition probabilities default to predefined values. If necessary, you can later modify the probabilities using the same function.
- `hmmprofalign` includes two new properties to control the scoring of flanking states and null transition probabilities. In addition, a third output argument with indices pointing to the respective symbols of the query sequence was added.

BLAST Functions

`blastncbi`, `blastread`, `getblast` — BLAST sequences and view results from within the MATLAB software.

Microarray Functions

- `imageneread` — Read microarray data from an ImaGene® Results file.
- `affyread` — Read microarray data from Affymetrix GeneChip files.
- `gprread` — Read microarray data from GenePix® Results (GPR) files.
- `mapcaplot` — Create a Principal Component plot of expression profile data.
- `clustergram` — Updated function to do two way bi-clustering.

Protein Analysis Function

`isoelectric` — Estimate the isoelectric point (the pH at which the protein has a net charge of zero) for an amino acid sequence and estimate the charge for a given pH.

Sequence Alignment Functions

- `seqdisp` — Formats sequence output for easy viewing.
- `seqmatch` — Find matches for every string in a library.
- `seqdotplot` — Updated function now returns a second output (the matrix of matches as a sparse matrix).
- `aminolookup` , `baselookup` — Updated functions to get IUB/UPAC character codes, integer codes, and names for nucleotides and amino acids.

New Demos

- **Bicluster demo** — Demonstrates some of the options of the `clustergram` function.
- **Bioperl demo** — Illustrates the interoperability between the MATLAB software and Bioperl, passing arguments from the MATLAB software to Perl scripts and pulling BLAST search data back to the MATLAB software.

- **Phytree demo for Hominidae species**— A phylogenetic tree is constructed from mtDNA sequences for the Hominidae taxa (also known as pongidae). This family embraces the gorillas, chimpanzees, orangutans and the humans.
- **Phytree demo for HIV/SIV** — Analyzes the reconstruction of phylogenetic trees from infected HIV/SIV organisms.

Version 1.0 (R13+) Bioinformatics Toolbox Software

This table summarizes what's new in Version 1.0 (Release 13+):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	No	No bug fixes	V1.0 product documentation

New features and changes introduced in this version are

- “Introduction to Bioinformatics Toolbox” on page 69
- “Databases and Data Formats” on page 70
- “Sequence Alignment” on page 70
- “Sequence Utilities and Statistics” on page 70
- “Microarray Normalization and Visualization” on page 70
- “Protein Structure Analysis” on page 71

Introduction to Bioinformatics Toolbox

Bioinformatics Toolbox Version 1.0 (Web Release R13 SP1+) extends the MATLAB software with basic sequence analysis and gene expression analysis functions. Bioinformatics Toolbox is a collection of tools built on the MATLAB numeric computing environment. The toolbox supports a wide range of common sequence analysis and expression analysis tasks, from accessing Web-based databases, to sequence alignment, to microarray normalization and visualization.

Bioinformatics Toolbox is dependent on many functions from the Statistics Toolbox™ software, including some functions available only in the latest version of Statistics Toolbox 4.1. We recommend that you install the latest version of the Statistics Toolbox software before running the Bioinformatics Toolbox software.

Bioinformatics Toolbox 1.0 has more than 100 functions implemented using M-files. For a complete list of functions, in the MATLAB Command Window, type

```
help bioinfo
```

Databases and Data Formats

The toolbox provides functions to directly access many standard Web-based databases such as GenBank, EMBL, PIR, and PDB. There are also functions to read many standard file formats, including FASTA and PDB. For microarray data, there are functions to read Affymetrix, GenePix, SPOT format data, and a function to access data directly from the NCBI Gene Expression Omnibus Web site.

Sequence Alignment

The toolbox has functions for pairwise sequence alignment and for hidden Markov model sequence profile alignment, including efficient MATLAB implementations of the Needleman-Wunsch and Smith-Waterman algorithms. In addition to the alignment functions there are several tools for visualizing sequence alignments. The toolbox provides many standard scoring matrices, including the PAM and BLOSUM families.

Sequence Utilities and Statistics

The toolbox contains many functions for working with sequences. There are functions for converting DNA sequences to RNA or amino acid sequences; there are functions that report various statistics about sequences, and functions to search for patterns within the sequence; there are functions for creating random sequences, and there are functions to perform in-silico digestion of sequences with restriction enzymes and proteases.

Microarray Normalization and Visualization

The toolbox contains a number of functions for normalizing microarray data including lowess normalization, global mean normalization, and MAD normalization. The toolbox provides several functions for visualizing microarray data, including spatial heat maps, box plots, loglog, and I-R plots. The toolbox also uses functions from the Statistics Toolbox software to perform cluster analysis and to visualize the results.

Protein Structure Analysis

In addition to standard sequence analysis functions, there is also a graphical user interface (GUI), `proteinplot`, for visualizing properties of protein sequences.

Compatibility Summary for Bioinformatics Toolbox Software

This table summarizes new features and changes that might cause incompatibilities when you upgrade from an earlier version, or when you use files on multiple versions. Details are provided in the description of the new feature or change.

Version (Release)	New Features and Changes with Version Compatibility Impact
Latest Version V3.4 (R2009b)	See the Compatibility Considerations subheading for this change: <ul style="list-style-type: none"> • “Data Visualization Functions” on page 6 • “Phylogenetic Tree Tools and Methods” on page 8 • “Clustergram Methods and Properties” on page 9
V3.3 (R2009a)	See the Compatibility Considerations subheading for this change: “Microarray Functions” on page 14
V3.2 (R2008b)	See the Compatibility Considerations subheading for these changes: <ul style="list-style-type: none"> • “Data Format and Database Functions” on page 16 • “Microarray File Format Functions” on page 20 • “Microarray Functions” on page 21
V3.1 (R2008a)	See the Compatibility Considerations subheading for these changes: <ul style="list-style-type: none"> • “Data Format and Database Functions” on page 23 • “Microarray Functions” on page 26

Version (Release)	New Features and Changes with Version Compatibility Impact
V3.0 (R2007b)	See the Compatibility Considerations subheading for these changes: <ul style="list-style-type: none"> • “Statistical Learning Functions” on page 32
V2.6 (R2007a+)	See the Compatibility Considerations subheadings for these changes: <ul style="list-style-type: none"> • “Data Formats and Databases Functions” on page 35 • “Microarray File Formats Functions” on page 36 • “Microarray Utility Functions” on page 36
V2.5 (R2007a)	See the Compatibility Considerations subheadings for these changes: <ul style="list-style-type: none"> • “Data Formats and Database Functions” on page 39 • “Statistical Learning Functions” on page 40 • “Protein Analysis and Sequence Utilities Functions” on page 40 • “Sequence Alignment Functions” on page 41 • “Microarray File Formats Functions” on page 42 • “Phylogenetic Tree Tools Functions” on page 44
V2.4 (R2006b)	None
V2.3 (R2006a+)	None
V2.2.1 (R2006a)	None
V2.2 (R14SP3+)	None
V2.1.1 (R14SP3)	None
V2.1 (R14SP2+)	None
V2.0.1 (R14SP2)	None
V2.0 (R14SP1+)	None

Version (Release)	New Features and Changes with Version Compatibility Impact
V1.1.1 (R14SP1)	None
V1.1 (R14)	None
V1.0 (R13+)	None