

Fixed-Point Toolbox™ Release Notes

How to Contact MathWorks



www.mathworks.com Web
comp.soft-sys.matlab Newsgroup
www.mathworks.com/contact_TS.html Technical Support



suggest@mathworks.com Product enhancement suggestions
bugs@mathworks.com Bug reports
doc@mathworks.com Documentation error reports
service@mathworks.com Order status, license renewals, passcodes
info@mathworks.com Sales, pricing, and general information



508-647-7000 (Phone)



508-647-7001 (Fax)



The MathWorks, Inc.
3 Apple Hill Drive
Natick, MA 01760-2098

For contact information about worldwide offices, see the MathWorks Web site.

Fixed-Point Toolbox™ Release Notes

© COPYRIGHT 2004–2010 by The MathWorks, Inc.

The software described in this document is furnished under a license agreement. The software may be used or copied only under the terms of the license agreement. No part of this manual may be photocopied or reproduced in any form without prior written consent from The MathWorks, Inc.

FEDERAL ACQUISITION: This provision applies to all acquisitions of the Program and Documentation by, for, or through the federal government of the United States. By accepting delivery of the Program or Documentation, the government hereby agrees that this software or documentation qualifies as commercial computer software or commercial computer software documentation as such terms are used or defined in FAR 12.212, DFARS Part 227.72, and DFARS 252.227-7014. Accordingly, the terms and conditions of this Agreement and only those rights specified in this Agreement, shall pertain to and govern the use, modification, reproduction, release, performance, display, and disclosure of the Program and Documentation by the federal government (or other entity acquiring for or through the federal government) and shall supersede any conflicting contractual terms or conditions. If this License fails to meet the government's needs or is inconsistent in any respect with federal procurement law, the government agrees to return the Program and Documentation, unused, to The MathWorks, Inc.

Trademarks

MATLAB and Simulink are registered trademarks of The MathWorks, Inc. See www.mathworks.com/trademarks for a list of additional trademarks. Other product or brand names may be trademarks or registered trademarks of their respective holders.

Patents

MathWorks products are protected by one or more U.S. patents. Please see www.mathworks.com/patents for more information.

Summary by Version	1
Version 3.2 (R2010b) Fixed-Point Toolbox Software ...	4
Version 3.1 (R2010a) Fixed-Point Toolbox Software ...	9
Version 3.0 (R2009b) Fixed-Point Toolbox Software ...	13
Version 2.4 (R2009a) Fixed-Point Toolbox Software ...	19
Version 2.3 (R2008b) Fixed-Point Toolbox Software ...	23
Version 2.2.1 (R2008a+) Fixed-Point Toolbox Software	25
Version 2.2 (R2008a) Fixed-Point Toolbox Software ...	26
Version 2.1.1 (R2007b+) Fixed-Point Toolbox Software	29
Version 2.1 (R2007b) Fixed-Point Toolbox Software ...	30
Version 2.0 (R2007a) Fixed-Point Toolbox Software ...	33
Version 1.5 (R2006b) Fixed-Point Toolbox Software ...	36
Version 1.4 (R2006a) Fixed-Point Toolbox Software ...	38
Version 1.3 (R14SP3) Fixed-Point Toolbox Software ..	45
Version 1.2 (R14SP2) Fixed-Point Toolbox Software ..	48

Version 1.1 (R14SP1) Fixed-Point Toolbox Software .. 50

Version 1.0 (R14) Fixed-Point Toolbox Software 51

**Compatibility Summary for Fixed-Point Toolbox
Software 54**

Summary by Version

This table provides quick access to what's new in each version. For clarification, see "Using Release Notes" on page 2.

Version (Release)	New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Latest Version V3.2 (R2010b)	Yes Details	Yes Summary	Bug Reports Includes fixes	Printable Release Notes: PDF Current product documentation
V3.1 (R2010a)	Yes Details	Yes Summary	Bug Reports Includes fixes	No
V3.0 (R2009b)	Yes Details	Yes Summary	Bug Reports Includes fixes	No
V2.4 (R2009a)	Yes Details	Yes Summary	Bug Reports Includes fixes	No
V2.3 (R2008b)	Yes Details	No	Bug Reports Includes fixes	No
V2.2.1 (R2008a+)	No	No	Bug Reports Includes fixes	No
V2.2 (R2008a)	Yes Details	No	Bug Reports Includes fixes	No
V2.1.1 (R2007b+)	No	No	Bug Reports Includes fixes	No
V2.1 (R2007b)	Yes Details	Yes Summary	Bug Reports Includes fixes	No

Version (Release)	New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
V2.0 (R2007a)	Yes Details	Yes Summary	Bug Reports Includes fixes	No
V1.5 (R2006b)	Yes Details	No	Bug Reports Includes fixes	No
V1.4 (R2006a)	Yes Details	Yes Summary	Bug Reports Includes fixes	No
V1.3 (R14SP3)	Yes Details	Yes Summary	Bug Reports Includes fixes	No
V1.2 (R14SP2)	Yes Details	No	Bug Reports	No
V1.1 (R14SP1)	No	No	Yes Details	No
V1.0 (R14)	Yes Details	Not applicable	No bug fixes	No

Using Release Notes

Use release notes when upgrading to a newer version to learn about:

- New features
- Changes
- Potential impact on your existing files and practices

Review the release notes for other MathWorks® products required for this product (for example, MATLAB® or Simulink®). Determine if enhancements, bugs, or compatibility considerations in other products impact you.

If you are upgrading from a software version other than the most recent one, review the current release notes and all interim versions. For example, when you upgrade from V1.0 to V1.2, review the release notes for V1.1 and V1.2.

What Is in the Release Notes

New Features and Changes

- New functionality
- Changes to existing functionality

Version Compatibility Considerations

When a new feature or change introduces a reported incompatibility between versions, the **Compatibility Considerations** subsection explains the impact.

Compatibility issues reported after the product release appear under Bug Reports at the MathWorks Web site. Bug fixes can sometimes result in incompatibilities, so review the fixed bugs in Bug Reports for any compatibility impact.

Fixed Bugs and Known Problems

MathWorks offers a user-searchable Bug Reports database so you can view Bug Reports. The development team updates this database at release time and as more information becomes available. Bug Reports include provisions for any known workarounds or file replacements. Information is available for bugs existing in or fixed in Release 14SP2 or later. Information is not available for all bugs in earlier releases.

Access Bug Reports using your MathWorks Account.

Version 3.2 (R2010b) Fixed-Point Toolbox Software

This table summarizes what's new in Version 3.2 (R2010b):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	Yes Summary	Bug Reports Includes fixes	Printable Release Notes: PDF Current product documentation

New features and changes introduced in this version are:

- “Enhanced NumericTypeScope for Selecting Fixed-Point Data Types” on page 4
- “Input Angle Range Extended for CORDIC Trigonometric Functions” on page 5
- “Floating-Point Support Added for bitsll Function” on page 5
- “Enhanced Compilation Report for emlc and emlhex” on page 5
- “Changes to the DataTypeMode Property of the numericType Object” on page 5
- “New fi and numericType Object Functions” on page 6
- “New and Updated Demos” on page 7
- “fi Objects with Boolean Data Type No Longer Obey Data Type Override” on page 7
- “Functions Being Removed” on page 7

Enhanced NumericTypeScope for Selecting Fixed-Point Data Types

The Fixed-Point Toolbox™ NumericTypeScope has been enhanced for R2010b. The scope now recommends data types based on the criteria you specify in the tool. The scope also allows you to switch into an interactive mode where

you can adjust the word and fraction lengths of the data type. When you are working in the interactive mode, you can drag the vertical bars that indicate the representable range of the data type.

Input Angle Range Extended for CORDIC Trigonometric Functions

The following CORDIC trigonometric functions now accept input angles in the range $[-2\pi, 2\pi]$:

- `cordicexp`
- `cordiccos`
- `cordicsin`
- `cordicsincos`

Floating-Point Support Added for bitsll Function

The Fixed-Point Toolbox `bitsll` function now supports floating-point inputs. You can now use the `bitsll` function with fixed-point, built-in or floating-point data types.

Enhanced Compilation Report for emlc and emlhex

The **Variables** tab of the compilation report now has an **Order** column. This new column allows you to sort the display of the variables according to the order in which they appear in your code.

Changes to the DataTypeMode Property of the numericType Object

The capitalization of the following `DataTypeMode` property values has changed for R2010b:

R2010a Property Value	R2010b Property Value
<code>boolean</code>	<code>Boolean</code>
<code>double</code>	<code>Double</code>
<code>single</code>	<code>Single</code>

Compatibility Consideration

As of R2010b, the `DataTypeMode` property of the `numericType` object returns the property values `Boolean`, `Double` and `Single` with the first letter capitalized. If your code performs any case-sensitive operations on the `DataTypeMode` property of a `numericType` object, you must update that code.

If you query the `DataTypeMode` property of a `numericType` object in R2010b, MATLAB throws a warning. To workaroud this warning, try using one or more of the following `numericType` object functions:

- `isboolean`
- `isdouble`
- `isfixed`
- `isscaleddouble`
- `isscalingbinarypoint`
- `isscalingslopebias`
- `isscalingunspecified`
- `issingle`

New `fi` and `numericType` Object Functions

R2010b adds the following `fi` and `numericType` object functions:

- `isscalingbinarypoint` — Determine whether input has binary point scaling
- `isscalingslopebias` — Determine whether input has nontrivial slope and bias scaling
- `isscalingunspecified` — Determine whether input has unspecified scaling

These functions provide you with the ability to query the scaling of a `fi` or `numericType` object.

New and Updated Demos

This release adds the Data Type Independent Code for CORDIC QR Factorization demo. The demo provides an example of how to write your algorithms using data type independent code. By writing your algorithms using data type independent code, you can run both floating- and fixed-point simulations using the same algorithm.

The Fixed-Point Algorithm Development demo has been updated to use the enhanced `NumericTypeScope` object.

fi Objects with Boolean Data Type No Longer Obey Data Type Override

In previous releases, `fi` objects with a boolean data type participated in data type override. When you set the `DataTypeOverride` property of the `fi` object to `ScaledDoubles`, `TrueDoubles`, or `TrueSingles`, `fi` objects with a boolean data type were overridden with the specified data type.

As of R2010b, `fi` objects with a boolean data type no longer participate in data type override. `fi` objects with a `DataType` of `boolean` (or a `DataTypeMode` of `Boolean`) now remain boolean `fi` objects, regardless of the current `DataTypeOverride` setting.

Functions Being Removed

Function Name	What Happens When You Use the Function?	Use This Instead	Compatibility Considerations
<code>removedefaultfimathpref</code>	Still runs	<code>removeglobalfimathpref</code>	Replace all instances of <code>removedefaultfimathpref</code> with <code>removeglobalfimathpref</code> .

Function Name	What Happens When You Use the Function?	Use This Instead	Compatibility Considerations
resetdefaultfimath	Still runs	resetglobalfimath	Replace all instances of resetdefaultfimath with resetglobalfimath.
savedefaultfimathpref	Still runs	saveglobalfimathpref	Replace all instances of savedefaultfimathpref with saveglobalfimathpref.
setdefaultfimath	Still runs	globalfimath	Replace all instances of setdefaultfimath with globalfimath.

Version 3.1 (R2010a) Fixed-Point Toolbox Software

This table summarizes what's new in Version 3.1 (R2010a):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	Yes Summary	Bug Reports Includes fixes	No

New features and changes introduced in this version are:

- “New Handle Object for the Global fimath” on page 9
- “New Global fimath Functions” on page 9
- “New NumericTypeScope for Selecting Fixed-Point Data Types” on page 10
- “New CORDIC Trigonometric Functions” on page 10
- “Fixed-Point Support Added for filter, mean, and median Functions” on page 10
- “Fixed-Point Support Added for mpower (^) and power (.^) Functions” on page 11
- “CastBeforeSum Property Hidden on fimath Objects with a SumMode of FullPrecision” on page 11
- “New and Updated Demos” on page 11
- “Functions Being Removed” on page 12

New Handle Object for the Global fimath

You can now configure the global fimath and return a handle object to it using the `globalfimath` function. Doing so makes it easier to change the properties of the global fimath, whether you are working at the MATLAB command line or in a file. See the “Functions Being Removed” on page 12 release note for information about the function that `globalfimath` replaces.

New Global fimath Functions

The following global fimath functions are new in R2010a:

- `removeglobalfimathpref`
- `resetglobalfimath`
- `saveglobalfimathpref`

For information about the functions they replace, see the “Functions Being Removed” on page 12 release note.

New NumericTypeScope for Selecting Fixed-Point Data Types

Fixed-Point Toolbox software now offers a `NumericTypeScope` object that can perform a dynamic range analysis on your data. You can use the results of the dynamic range analysis to help you select appropriate `numerictype` properties for your data.

New CORDIC Trigonometric Functions

Fixed-Point Toolbox software now offers the following CORDIC-based approximation functions:

- `cordicexp`
- `cordiccos`
- `cordicsin`
- `cordicsincos`

These functions allow you to compute the sine, cosine, and complex exponential of fixed-point data using the CORDIC approximation method.

Fixed-Point Support Added for filter, mean, and median Functions

Fixed-Point Toolbox software now provides support for the following functions:

- `filter`
- `mean`
- `median`

Fixed-Point Support Added for `mpower (^)` and `power (.^)` Functions

Fixed-Point Toolbox software now provides support for the `mpower (^)` and `power (.^)` functions.

CastBeforeSum Property Hidden on `fimath` Objects with a `SumMode` of `FullPrecision`

The setting of the `CastBeforeSum` property does not affect full-precision sums, so effective this release, it is hidden for `fimath` objects that have a `SumMode` of `FullPrecision`. In previous releases, you could not generate code with the Embedded MATLAB® subset when the `CastBeforeSum` property of a `fimath` object was set to `False`, even if you were only computing full-precision sums.

This change ensures that you can always generate code for full-precision sums using `emlmex`, `emlc`, or the Embedded MATLAB Function block. A `CastBeforeSum` property setting of `False` no longer causes an error if you are working with full-precision sums.

New and Updated Demos

This release adds the Fixed-Point Sine and Cosine Calculation demo. This demo shows you how to compute the sine and cosine of fixed-point data using the new CORDIC-based approximation functions.

Demos with significant updates this release include the following:

- Fixed-Point Basics — This demo now highlights the functionality of recently added features, including the new handle object for the global `fimath`.
- Fixed-Point Algorithm Development — This demo now uses the `NumericTypeScope` object to help select appropriate fixed-point data types.

Functions Being Removed

Function Name	What Happens When You Use the Function?	Use This Instead	Compatibility Considerations
<code>removedefaultfimathpref</code>	Still runs	<code>removeglobalfimathpref</code>	Replace all instances of <code>removedefaultfimathpref</code> with <code>removeglobalfimathpref</code> .
<code>resetdefaultfimath</code>	Still runs	<code>resetglobalfimath</code>	Replace all instances of <code>resetdefaultfimath</code> with <code>resetglobalfimath</code> .
<code>savedefaultfimathpref</code>	Still runs	<code>saveglobalfimathpref</code>	Replace all instances of <code>savedefaultfimathpref</code> with <code>saveglobalfimathpref</code> .
<code>setdefaultfimath</code>	Still runs	<code>globalfimath</code>	Replace all instances of <code>setdefaultfimath</code> with <code>globalfimath</code> .

Version 3.0 (R2009b) Fixed-Point Toolbox Software

This table summarizes what's new in Version 3.0 (R2009b):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	Yes Summary	Bug Reports Includes fixes	No

New features and changes introduced in this version are:

- “New Relationship Between `fi` Objects and a Global `fimath` Simplifies Fixed-Point Arithmetic” on page 13
- “New `sfi` and `ufi` Constructors for Creating `fi` Objects” on page 16
- “New `conv` Function for Fixed-Point Inputs” on page 17
- “Built-in Integer and Floating-Point Support Added for Bitshift Operations” on page 17
- “Embedded MATLAB Support for Variable-Size Arrays and Matrices” on page 17
- “New Compilation Report for Embedded MATLAB Function Blocks” on page 18

New Relationship Between `fi` Objects and a Global `fimath` Simplifies Fixed-Point Arithmetic

In previous versions of Fixed-Point Toolbox software, all `fi` objects had an attached `fimath` object property. The attached `fimath` object determined how the `fi` object performed fixed-point arithmetic operations. This format made it more cumbersome to create `fi` objects, sometimes resulting in “mismatched `fimath`” errors.

In R2009b, the behavior of the `fi` object has been changed. A `fi` object no longer needs to have its own attached `fimath` object property. Rather than each `fi` object having its own set of `fimath` object properties, you can now associate `fi` objects with the global `fimath`. See “Working with the Global `fimath`” for more information.

When you create a `fi` object in R2009b without specifying any `fimath` object properties in the constructor, MATLAB returns a `fi` object that associates itself with the global `fimath`. If you change the global `fimath`, all `fi` objects that are associated with the global `fimath` automatically pick up the new `fimath` properties.

You can still use the `fi` object constructor function to specify a particular `fimath` object for a `fi` object.

In general, fixed-point arithmetic operations use the following rules:

- If either `fi` object in a binary operation has its own `fimath` object, the operation uses that `fimath` object.
- If both `fi` objects in a binary operation use the global `fimath`, the operation uses the global `fimath`.

For more information on fixed-point arithmetic rules, see “`fimath` Rules for Fixed-Point Arithmetic”.

This feature also includes several new functions:

- `isfimathlocal` — Use this function to find out whether a `fi` object has its own explicitly attached `fimath` object. Any `fi` object that does not have its own `fimath` object is instead associated with the global `fimath`.
- `sfi`, `ufi` — Use these constructors to create signed and unsigned `fi` objects that associate themselves with the global `fimath`. See “New `sfi` and `ufi` Constructors for Creating `fi` Objects” on page 16 for more information.
- `removedefaultfimathpref` — Use this function to remove a user-configured global `fimath` from your MATLAB preferences. See “Working with the Global `fimath`” in the *Fixed-Point Toolbox User’s Guide* for more information.

Compatibility Consideration

The new relationship between `fi` objects and the global `fimath` results in the following incompatibilities:

Construction of fi Objects. To create `fi` objects with Fixed-Point Toolbox software, the `fi` constructor must know which `RoundMode` and `OverflowMode` properties to use. You can specify these `fimath` object properties in a `fi` object constructor. In this case, the constructor uses the `RoundMode` and `OverflowMode` properties you specify to create the `fi` object.

The new relationship between `fi` objects and the global `fimath` state introduces a compatibility consideration. This compatibility issue relates to the construction of `fi` objects from a floating-point value when you do not specify any `fimath` object properties in the `fi` object constructor. When you constructed `fi` objects in such a way in R2008b and R2009a, the `fi` constructor used the `RoundMode` and `OverflowMode` properties of the old default `fimath` object.

When you create a `fi` object in this way in R2009b, you may get different results. As of this release, the `fi` constructor creates the `fi` object using a `RoundMode` of nearest and an `OverflowMode` of saturate. Thus, the setting of the `RoundMode` and `OverflowMode` properties of the global `fimath` are not used to create `fi` objects from floating-point values.

You can still create a `fi` object from a floating-point value in R2009b with a `RoundMode` and `OverflowMode` other than nearest and saturate. To do so, specify your desired `RoundMode` and `OverflowMode` properties in the `fi` constructor.

Behavior change for `add`, `mpy` and `sub` Functions. In previous releases, the output of the `fimath` object functions `add`, `mpy` and `sub` was assigned the `fimath` object specified in the function call. For example, the syntax `c = add(F, a, b)` where `F` is a `fimath` object, resulted in a `fi` object `c` being created and assigned the `fimath` object `F`.

In R2009b, the output `fi` object `c` is always associated with the global `fimath`. It no longer gets assigned the `fimath` object `F`.

Specifying `fimath` Properties in the Embedded MATLAB Function Block. This release removes the `FIMATH for fixed-point input signals` and `FIMATH for fi and fimath constructors` parameters from the Embedded MATLAB Function Block. You now use the **Embedded MATLAB function block `fimath`** radio buttons to set the following:

- The `fimath` properties to be associated with fixed-point inputs
- The `fimath` properties to be associated with all `fi` and `fimath` objects constructed in the block

You can choose one of the following options for the **Embedded MATLAB function block `fimath`** parameter:

- **Same as MATLAB** — When you select this option, the block uses the same `fimath` properties as the current global `fimath`.
- **Specify other** — When you select this option, you can specify your own set of `fimath` object properties. These properties get associated with all fixed-point block inputs and all `fi` and `fimath` objects constructed in the block.

Run a model that had the **FIMATH for `fi` and `fimath` constructors** parameter set to `Same as MATLAB` factory default in R2009b. You may notice different results. This difference occurs because all `fi` and `fimath` objects constructed in the Embedded MATLAB function block now use the **Embedded MATLAB function block `fimath`**.

To achieve the same results as previous releases, set the **Embedded MATLAB function block `fimath`** to the MATLAB factory default when you run your model in R2009b. Otherwise, all `fi` and `fimath` objects constructed within your Embedded MATLAB function blocks may be associated with different `fimath` object properties.

To inform you of this change in behavior, the block issues a warning at the MATLAB command line. To turn off the warning, run `slupdate` on your model.

New `sfi` and `ufi` Constructors for Creating `fi` Objects

Fixed-Point Toolbox software now supports two new `fi` object constructor functions:

- `sfi` — Construct signed fixed-point numeric object
- `ufi` — Construct unsigned fixed-point numeric object

These new constructors simplify the construction of `fi` objects. You no longer need to specify the signedness and `fimath` object properties of the `fi` object in the constructor. All `fi` objects you construct with one of these functions are automatically associated with the global `fimath`. They do not have a `fimath` object of their own. For more information on the global `fimath` and how it can help you simplify arithmetic with `fi` objects, see:

“New Relationship Between `fi` Objects and a Global `fimath` Simplifies Fixed-Point Arithmetic” on page 13

New `conv` Function for Fixed-Point Inputs

Fixed-Point Toolbox software now provides support for the `conv` function.

Built-in Integer and Floating-Point Support Added for Bitshift Operations

The following Fixed-Point Toolbox functions now support built-in integers:

- `bits11`
- `bitsr1`
- `reinterpretcast`

The following Fixed-Point Toolbox function now supports both built-in integers and floating-point data types:

- `bitsra`

Embedded MATLAB Support for Variable-Size Arrays and Matrices

The Embedded MATLAB subset now supports variable-size arrays and matrices with known upper bounds. With this feature, you can define inputs, outputs, and local variables in Embedded MATLAB functions to represent data that varies in size at runtime. You can use variable-size data in:

- Embedded MATLAB Function blocks in Simulink
- Embedded MATLAB functions in Stateflow® charts

- Embedded MATLAB compliant M functions, from which you can generate MEX code with `emlmex` and C code with `emlc` (requires Real-Time Workshop® software)

For more information, see “Working with Variable-Size Data” in the *Embedded MATLAB User’s Guide*.

New Compilation Report for Embedded MATLAB Function Blocks

The new compilation report provides compile-time type information for the variables and expressions in your Embedded MATLAB functions. This information helps you find the sources of error messages and understand type propagation issues, particularly for fixed-point data types.

Compatibility Consideration

The new compilation report is not supported by the MATLAB internal browser on Sun™ Solaris™ 64-bit platforms. To view the compilation report, you must have your MATLAB Web preferences configured to use an external browser, for example, Mozilla® Firefox. To learn how to configure your MATLAB Web preferences, see “Web Preferences” in the MATLAB documentation.

Version 2.4 (R2009a) Fixed-Point Toolbox Software

This table summarizes what's new in Version 2.4 (R2009a):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	Yes Summary	NoBug Reports Includes fixes	No

New features and changes introduced in this version are:

- “Support Added for numerictype Objects with Unspecified Sign” on page 19
- “New Fixed-Point Menu Options in the MATLAB Editor” on page 20
- “New mrdivide and rdivide Functions for Fixed-Point Inputs” on page 20
- “New Compilation Report for emlc and emlhex” on page 20
- “New and Updated Demos” on page 21
- “Complex fi Objects with Nontrivial Slope and Bias Scaling Are No Longer Supported” on page 22

Support Added for numerictype Objects with Unspecified Sign

A new Signedness property has been added to the numerictype object. This new Signedness property allows you to set the Signedness of a numerictype object to Signed, Unsigned, or Auto. By setting the Signedness property to Auto, you can create numerictype objects that have an unspecified sign.

Although you can create numerictype objects with an unspecified sign (Signedness: Auto), all fi objects must have a Signedness of Signed or Unsigned. If you use a numerictype object with Signedness: Auto to construct a fi object, the Signedness property defaults to Signed at fi object creation.

The toolbox still supports the `Signed` property of the `numericity` object. For more information about the `Signedness` property, see “`numericity` Object Properties” in the Fixed-Point Toolbox documentation.

New Fixed-Point Menu Options in the MATLAB Editor

A new **Tools > Fixed-Point Toolbox** menu option in the MATLAB Editor allows you to build `fi`, `fimath`, and `numericity` object constructors in a GUI and insert them directly into your file. For more information, see the following sections:

- “Constructing `fi` Objects”
- “Constructing `fimath` Objects”
- “Constructing `numericity` Objects”

New `mrdivide` and `rdivide` Functions for Fixed-Point Inputs

Fixed-Point Toolbox software now provides the following `fi` object functions for division:

- `mrdivide` — Forward slash (`/`) or right-matrix division
- `rdivide` — Right-array division (`./`)

New Compilation Report for `emlc` and `emlmex`

A new compilation report is now available for `emlc` and `emlmex`. The new report provides compile-time type information for the variables and expressions in your MATLAB code. This information simplifies finding sources of error messages and aids understanding of type propagation rules, particularly for fixed-point data types. To generate the report, you must specify the `-report` option after the `emlc` or `emlmex` command. To learn more about the compilation report, see the following sections:

- For information about using the report to view fixed-point data types, see “Working with Fixed-Point Compilation Reports” in the Fixed-Point Toolbox documentation.

- For more information about using the report with `emlmex`, see “Working with Compilation Reports” in the Embedded MATLAB subset documentation.
- For more information about using the report with `emlc`, see “Working with Compilation Reports” in the Real-Time Workshop documentation.

Compatibility Consideration

The following internal and external browsers do not support the new compilation report:

- MATLAB internal browser (on 64-bit UNIX® platforms only)
- MACI internal browser
- Microsoft Internet Explorer® 6

To view the new compilation report when your internal browser does not support it, you must configure your MATLAB Web preferences to use an external browser, for example, Mozilla Firefox. To learn how to configure your MATLAB Web preferences, see “Specifying the System Browser for UNIX Platforms” in the MATLAB documentation.

New and Updated Demos

The Fixed-Point ATAN2 Calculation demo is new for this release. This new demo uses the CORDIC algorithm and polynomial approximation to perform a fixed-point calculation of the four quadrant inverse tangent. To run this demo, type `fixpt_atan2_demo` at the MATLAB command line.

The Fixed-Point Data Type Override, Min/Max Logging, and Scaling demo has been updated for this release. The updated demo uses the `emlc` and `emlmex` functions to generate code and demonstrates the Embedded MATLAB subset’s ability to generate code beyond 32-bits. To run this demo type `fi_datatype_override_demo` at the MATLAB command line.

Complex `fi` Objects with Nontrivial Slope and Bias Scaling Are No Longer Supported

Fixed-Point Toolbox operations that result in the creation of a complex `fi` object with nontrivial slope and bias scaling are no longer supported. All complex `fi` objects must now have an integer power-of-two slope and a bias of 0 (binary-point scaling).

Compatibility Consideration

In prior releases, Fixed-Point Toolbox software supported complex `fi` objects with nontrivial slope and bias scaling. As of R2009a, all complex `fi` objects must have an integer power-of-two slope and a bias of 0. Operations that result in the creation of a `fi` object with nontrivial slope and bias scaling will error out.

Version 2.3 (R2008b) Fixed-Point Toolbox Software

This table summarizes what's new in Version 2.3 (R2008b):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	No	Bug Reports Includes fixes	No

New features and changes introduced in this version are:

- “The Default fimath Object is Now User-Configurable” on page 23
- “Embedded MATLAB Subset Support for Data up to 128 Bits” on page 23
- “round and convergent Rounding Mode Support Added to the Embedded MATLAB Subset” on page 24
- “New reinterpretcast Function” on page 24
- “New sort Function for Fixed-Point Inputs” on page 24

The Default fimath Object is Now User-Configurable

When you create a `fi` object in MATLAB code or the Embedded MATLAB Function block without providing any `fimath` attributes in the constructor call, a default `fimath` object is assigned to the `fi` object you create. Previously, this default `fimath` object could not be user-configured, and the only way to assign a different `fimath` to your `fi` objects was to specify the desired `fimath` object in every constructor call.

In R2008b, the default `fimath` object used in the `fi` and `fimath` constructors can be user-configured. For more information, see “Working with the Global `fimath`” in the *Fixed-Point Toolbox User's Guide*.

Embedded MATLAB Subset Support for Data up to 128 Bits

The Embedded MATLAB subset now supports fixed-point word lengths up to 128 bits. This includes:

- Acceleration of fixed-point algorithm execution with the `emlmex` function.
- C code production with the `emlc` function.
- Model simulation and C code production with the Embedded MATLAB Function block.

round and convergent Rounding Mode Support Added to the Embedded MATLAB Subset

The Embedded MATLAB subset now supports two additional rounding modes:

- `round` — Rounds to the closest representable number. In the case of a tie, the `round` method rounds positive numbers to the closest representable number in the direction of positive infinity, and rounds negative numbers to the closest representable number in the direction of negative infinity.
- `convergent` — Rounds to the closest representable number. In the case of a tie, `convergent` rounds to the nearest even number.

New reinterpretcast Function

Fixed-Point Toolbox software now provides a `reinterpretcast` function to convert fixed-point data types without changing the underlying data.

New sort Function for Fixed-Point Inputs

Fixed-Point Toolbox software now provides support for the MATLAB `sort` function.

Version 2.2.1 (R2008a+) Fixed-Point Toolbox Software

This table summarizes what's new in Version 2.2.1 (R2008a+)

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
No	No	Bug Reports Includes fixes	No

There were no new features or changes in this version.

Version 2.2 (R2008a) Fixed-Point Toolbox Software

This table summarizes what's new in Version 2.2 (R2008a):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	No	Bug Reports Includes fixes	No

New features and changes introduced in this version are:

- “Enhanced Memory Management” on page 26
- “New Rounding Functions for fi Objects” on page 27
- “New Bitwise Operator bitreplicate” on page 27
- “New Syntax for Bitwise Operator bitconcat” on page 27
- “ndgrid Function Support for Fixed-Point Inputs” on page 28
- “New fi Constructor Syntax” on page 28

Enhanced Memory Management

The memory management of the `fi` object has been improved, and generating large multidimensional arrays should no longer hang the MATLAB environment.

When performing computations with `fi` objects from the MATLAB command line, the memory usage in bits for the `fi` variable a is on the order of

$$\max(64, a.\text{wordlength}) * \text{numberofelements}(a)$$

The formula computes the number of bits used to store each element of an array, but does not include the overhead for each instance of the object. Similar to built-in `mxArrays`, there is additional overhead for each array. This overhead is used to store information about data type, `fi`math properties, and other settings that do not depend on the size of the array.

If you are concerned with memory usage, try compiling with `emlmex` or `emlc`. The compiled code uses the smallest C integer type that contains the word length of the variables. For example, if the `fi` variable a is 8-bit, then the compiled code will use approximately $8 * \text{numberofelements}(a)$ bits of memory. The current maximum fixed-point word length in the Embedded MATLAB subset is 32 bits.

New Rounding Functions for `fi` Objects

Fixed-Point Toolbox software now provides the following `fi` object functions:

- `ceil` — Round toward positive infinity
- `convergent` — Round toward nearest integer with ties rounding to nearest even integer
- `fix` — Round toward zero
- `floor` — Round toward negative infinity
- `nearest` — Round toward nearest integer with ties rounding toward positive infinity
- `round` — Round toward nearest integer with ties rounding to nearest integer with greater absolute value

These functions are also supported by the Embedded MATLAB subset.

New Bitwise Operator `bitreplicate`

Fixed-Point Toolbox software now provides the `bitreplicate` function to replicate and concatenate the bits of a `fi` object.

`bitreplicate` is also supported by the Embedded MATLAB subset.

New Syntax for Bitwise Operator `bitconcat`

The Fixed-Point Toolbox function `bitconcat` has new syntax.

For more information see the `bitconcat` reference page.

ndgrid Function Support for Fixed-Point Inputs

Fixed-Point Toolbox software now provides support for the `ndgrid` function.

New fi Constructor Syntax

Fixed-Point Toolbox software has added a new syntax for the `fi` constructor. The syntax `a = fi(V, F, T)` is now defined, and is equivalent to the existing syntax `a = fi(V, T, F)`.

See the `fi` function reference page for more information.

Version 2.1.1 (R2007b+) Fixed-Point Toolbox Software

This table summarizes what's new in Version 2.1.1 (R2007b+)

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
No	No	Bug Reports Includes fixes	No

There were no new features or changes in this version.

Version 2.1 (R2007b) Fixed-Point Toolbox Software

This table summarizes what's new in Version 2.1 (R2007b):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	Yes—Details labeled as Compatibility Considerations , below. See also Summary.	Bug Reports Includes fixes	No

New features and changes introduced in this version are:

- “Support for Data Type Override” on page 30
- “New Bitwise Operator Functions” on page 30
- “bitget Function Updated” on page 31
- “abs Function Supports Complex Inputs” on page 31
- “divide Function Updated” on page 32
- “fi Constructor Applies Property/Value Pairs After Numeric Value” on page 32

Support for Data Type Override

Fixed-Point Toolbox software now supports data type override in Embedded MATLAB subset. This facilitates fixed-point design and enables a single source for fixed- and floating-point code generation.

New Bitwise Operator Functions

Fixed-Point Toolbox software now provides the following functions:

- `bitandreduce` — Bitwise AND of consecutive range of bits
- `bitconcat` — Concatenate bits of two `fi` objects
- `bitorreduce` — Bitwise OR of consecutive range of bits

- `bitrol` — Bitwise rotate left
- `bitror` — Bitwise rotate right
- `bitsliceget` — Consecutive slice of bits
- `bitsll` — Bit shift left logical
- `bitsra` — Bit shift right arithmetic
- `bitsrl` — Bit shift right logical
- `bitxorreduce` — Bitwise exclusive OR of consecutive range of bits
- `getlsb` — Least significant bit
- `getmsb` — Most significant bit

Embedded MATLAB subset also supports these functions.

bitget Function Updated

The `bitget` function now behaves as follows:

- `bitget` returns a `u1,0`.
- `bitget` supports variable indexing. This means that the position of the bit to get can be a variable instead of a constant.
- The input `fi` object and the position of the bit to get can be vectors or scalars.

For more information, see the `bitget` reference page.

Compatibility Consideration

In prior releases, this function returned a `uint8`. The function now returns a `u1,0`. To get a `uint8`, use the `uint8` function on the `bitget` output.

abs Function Supports Complex Inputs

You can now use the `abs` function to compute the absolute value of a complex `fi` object.

For more information, see the `abs` reference page.

divide Function Updated

The `divide` function now obeys the `DataTypeOverride` settings of the `fipref` object.

For more information, see the `divide` reference page.

Compatibility Consideration

In prior releases, this function did not obey the `DataTypeOverride` settings of the `fipref` object. For example, if the input was `fi ScaledDouble`, but the input `numericType` object was `fi Fixed`, the output was `fi Fixed`. The output is now `fi ScaledDouble`.

fi Constructor Applies Property/Value Pairs After Numeric Value

When you call the `fi` constructor with both a numeric value and one or more property/value pairs that change the numeric value of the `fi` object, the `fi` constructor applies the property/value pairs after it sets the numeric value of the `fi` object.

For more information, see the `fi` reference page.

Compatibility Consideration

In prior releases, the `fi` constructor applied the property/value pairs before it set the numeric value. For example, the following code used to produce a `fi` object with a value of 0:

```
a = fi(0,1,16,13,'hex','6488')
```

This code now produces a `fi` object with a value of `pi`.

Version 2.0 (R2007a) Fixed-Point Toolbox Software

This table summarizes what's new in Version 2.0 (R2007a):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	Yes—Details labeled as Compatibility Considerations , below. See also Summary.	Bug Reports Includes fixes	No

New features and changes introduced in this version are

- “Fast Execution for Fixed-Point Algorithms in MATLAB” on page 33
- “New fi Syntaxes that Have fimath as an Argument” on page 34
- “Increased Support for Fixed-Point Toolbox Software Features in the Embedded MATLAB Subset” on page 34
- “Embedded MATLAB Subset Enhanced to Support N-Dimensional Arrays and Function Handles” on page 34
- “get Function Must be Declared Extrinsic in Embedded MATLAB Subset” on page 35
- “Embedded MATLAB Subset Does Not Support & and | Operators” on page 35
- “New Demo” on page 35

Fast Execution for Fixed-Point Algorithms in MATLAB

The new Embedded MATLAB MEX functionality converts MATLAB code to C-MEX functions. These C-MEX functions contain Embedded MATLAB subset optimizations for automatically accelerating fixed-point algorithms to compiled C code speed in MATLAB. For more information, refer to “Working with Embedded MATLAB MEX” in the Embedded MATLAB subset documentation.

New `fi` Syntaxes that Have `fimath` as an Argument

The following syntaxes have been added to the `fi` object:

- `a = fi(v,F)`
- `a = fi(v,s,F)`
- `a = fi(v,s,w,F)`
- `a = fi(v,s,w,f,F)`
- `a = fi(v,s,w,slope,bias,F)`
- `a = fi(v,s,w,slopeadjustmentfactor,fixedexponent,bias,F)`

where `v` is value, `s` is signedness, `w` is word length, `f` is fraction length, and `F` is a `fimath` object. Refer to “Working with `fi` Objects” or the `fi` reference page for more information.

Increased Support for Fixed-Point Toolbox Software Features in the Embedded MATLAB Subset

The following Fixed-Point Toolbox software features are now supported by the Embedded MATLAB subset:

- Dot notation for getting the values of `fimath` properties
- `get` function for `fi` and `fimath` objects
- `diag`, `permute`, `tril`, and `triu` functions

For a complete list of the Fixed-Point Toolbox features supported by the Embedded MATLAB subset, refer to “Supported Functions and Limitations of the Fixed-Point Embedded MATLAB Subset”.

Embedded MATLAB Subset Enhanced to Support N-Dimensional Arrays and Function Handles

Embedded MATLAB subset now supports N-dimensional arrays and function handles.

get Function Must be Declared Extrinsic in Embedded MATLAB Subset

There is a change to how you must use the `get` function in Embedded MATLAB subset to call properties of any object other than `fi` objects.

Compatibility Consideration

To get properties of non-`fi` objects in Embedded MATLAB subset, you must first declare `get` to be an extrinsic function. As of this release, if you do not do so, your code will error. For more information, refer to “Calling MATLAB Functions” in the Embedded MATLAB subset documentation.

Embedded MATLAB Subset Does Not Support & and | Operators

Embedded MATLAB subset no longer supports `&` and `|` operators in `if` and `while` conditional statements.

Compatibility Consideration

In prior releases, these operators compiled without error, but their short-circuiting behavior was not implemented correctly. Substitute `&&` and `||` operators instead.

New Demo

The “Fixed-Point Lowpass Filtering Using Embedded MATLAB MEX” demo is new in this release. This demo steps you through generating a C-MEX function from MATLAB code, running the generated C-MEX function, and displaying the results.

Version 1.5 (R2006b) Fixed-Point Toolbox Software

This table summarizes what's new in Version 1.5 (R2006b):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	No	Bug Reports Includes fixes	No

New features and changes introduced in this version are

- “Licensing Changes” on page 36
- “Fixed-Point Square Root Support” on page 36
- “Limited Dot Notation Support Added to Fixed-Point Embedded MATLAB Subset” on page 37
- “get Function Support Added to Fixed-Point Embedded MATLAB Subset” on page 37
- “New Default Syntax for fi Object” on page 37

Licensing Changes

You now can use `fi` objects with the `DataType` property set to `double` *without* a Fixed-Point Toolbox license when the `fipref LoggingMode` property is set to `off`. For details about the Fixed-Point Toolbox licensing model, refer to “Licensing” in the product documentation.

Fixed-Point Square Root Support

In this release, fixed-point square root support has been added to

- Fixed-Point Toolbox software, via the `sqrt` function
- Embedded MATLAB subset, via support for the Fixed-Point Toolbox `sqrt` function
- Simulink, via fixed-point support for the `sqrt` mode of the Math Function block

These products use the same bisection algorithm to implement their fixed-point square root functionality and yield identical results.

Limited Dot Notation Support Added to Fixed-Point Embedded MATLAB Subset

Dot notation is now supported in Embedded MATLAB subset for getting the values of `numericType` object properties. Dot notation is not supported for `fi` or `fiMath` objects, and it is not supported for setting properties.

get Function Support Added to Fixed-Point Embedded MATLAB Subset

The Fixed-Point Toolbox `get` function is now supported for use with Embedded MATLAB subset with the following limitations:

- Only supported for use with `numericType` objects
- The syntax `structure = get(o)` is not supported

New Default Syntax for fi Object

You can now use the syntax `fi` without any input arguments to return a default `fi` object with no value, 16-bit word length, and 15-bit fraction length.

Version 1.4 (R2006a) Fixed-Point Toolbox Software

This table summarizes what's new in Version 1.4 (R2006a):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	Yes—Details labeled as Compatibility Considerations , below. See also Summary.	Bug Reports Includes fixes	No

New features and changes introduced in this version are

- “[Slope Bias] Math Support Added” on page 38
- “Scaled Double Data Type Support Added to the fi Object” on page 39
- “Global DataTypeOverride Property Added to the fipref Object” on page 39
- “Embedded MATLAB Subset Supports More Fixed-Point Toolbox Functions” on page 40
- “Embedded MATLAB Subset Does Not Support a CastBeforeSum Value of 'false'” on page 40
- “'round' Value Added to the fimath Object RoundMode Property” on page 41
- “numericType Object Syntax Change” on page 41
- “Minimums and Maximums Now Logged After Quantization” on page 42

[Slope Bias] Math Support Added

Arithmetic using the +, -, .*, and * operators is now supported for objects with [Slope Bias] scaling. Refer to “[Slope Bias] Arithmetic” in the product documentation for more information.

In support of this feature, the following properties have been added to the fimath object:

- `ProductBias` — Bias of the product data type
- `ProductFixedExponent` — Fixed exponent of the product data type
- `ProductSlope` — Slope of the product data type
- `ProductSlopeAdjustmentFactor` — Slope adjustment factor of the product data type
- `SumBias` — Bias of the sum data type
- `SumFixedExponent` — Fixed exponent of the sum data type
- `SumSlope` — Slope of the sum data type
- `SumSlopeAdjustmentFactor` — Slope adjustment factor of the sum data type

Refer to “Property Reference” in the product reference documentation for more information.

Scaled Double Data Type Support Added to the `fi` Object

The `fi` object now supports the scaled double data type. The value `ScaledDouble` has been added to the `DataType` property of the `numericType` object. The following values have also been added to the `DataTypeMode` property of the `numericType` object:

- Scaled double: binary point scaling
- Scaled double: slope and bias scaling
- Scaled double: unspecified scaling

Math operations are supported for `fi` objects with data type `ScaledDouble`.

Global `DataTypeOverride` Property Added to the `fipref` Object

The `fipref` object now has the property `DataTypeOverride`, which allows you to override `fi` objects with scaled doubles, singles, or doubles. Refer to “Using `fipref` Objects to Set Data Type Override Preferences” in the product documentation for more information.

Embedded MATLAB Subset Supports More Fixed-Point Toolbox Functions

The following Fixed-Point Toolbox functions are now supported by Embedded MATLAB subset:

- `bitand`
- `bitcmp`
- `bitget`
- `bitor`
- `bitset`
- `bitshift`
- `bitxor`
- `rescale`

Refer to “Supported Functions and Limitations of the Fixed-Point Embedded MATLAB Subset” in the product documentation for more information.

Embedded MATLAB Subset Does Not Support a `CastBeforeSum` Value of `false`

You can no longer set the `fimath` object property `CastBeforeSum` to `false` or `0` in Embedded MATLAB Function blocks. The reason for this restriction is that Embedded MATLAB subset does not produce the same numerical results as MATLAB when `CastBeforeSum` is `false`.

Compatibility Considerations

In the previous release, `CastBeforeSum` was set to `false` for default `fimath` objects in Embedded MATLAB subset. If you have existing models that contain Embedded MATLAB Function blocks in which `CastBeforeSum` is `false`, you will now get an error when you compile or update your model. To correct this issue, you must set `CastBeforeSum` to `true`. To automate this process, you can run the utility `slupdate` either from the Model Advisor or by typing the following command at the MATLAB command line:

```
slupdate ('modelName')
```

where `modelName` is the name of the model containing the Embedded MATLAB Function block that generates the error. `slupdate` prompts you to update this property by selecting one of these options:

Option	Action
Yes	Updates the first occurrence of <code>CastBeforeSum=false</code> in Embedded MATLAB Function blocks in the model and then prompts you for each subsequent instance found in the model.
No	Does not update any occurrences of <code>CastBeforeSum=false</code> in the model.
All	Updates all occurrences of <code>CastBeforeSum=false</code> in the model.

Note `slupdate` detects `CastBeforeSum=false` only in *default* `fimath` objects defined for Simulink signals in Embedded MATLAB Function blocks. If you modified the `fimath` object in an Embedded MATLAB Function block, update `CastBeforeSum` manually in your model and fix the errors as they are reported.

round Value Added to the fimath Object RoundMode Property

The `RoundMode` property value `round` has been added to the `fimath` object. The behavior of this rounding mode is identical to the MATLAB `round` function. For more information refer to “`RoundMode`” in the product documentation.

numericType Object Syntax Change

Previously, if you created a `numericType` object without specifying a value for the `FractionLength` property, the fraction length would be automatically set to 15. Now however, if you do not set the `FractionLength` property when creating a `numericType` object, the scaling will remain unspecified. For example:

```
T = numericType(1, 16)
```

```
T =
```

```
DataTypeMode: Fixed-point: unspecified scaling
Signed: true
WordLength: 16
```

```
T.scaling
```

```
ans =
```

```
Unspecified
```

```
T.FractionLength
```

```
ans =
```

```
0
```

Compatibility Considerations

Any instances of this syntax in your existing code will now return a different result.

Minimums and Maximums Now Logged After Quantization

Previously, the `fi` and `quantizer` objects logged minimums and maximums before quantization. They now log after quantization.

Compatibility Considerations

If your fixed-point data overflows and you want to log minimums and maximums for the full floating-point range, use the `'ScaledDoubles'` or `'TrueDoubles'` values of the `fipref` object `DataTypeOverride` property. For example, the following fixed-point variable overflows. The saturated minimum and maximum values are logged:

```
p = fipref;
p.LoggingMode = 'On';
p.DataTypeOverride = 'ForceOff';
```

```

a = fi(-2:2, true, 16, 15)
Warning: 3 overflows occurred in the fi assignment operation.

a =

    -1    -1     0    0.99997    0.99997

    DataTypeMode: Fixed-point: binary point scaling
        Signed: true
        WordLength: 16
    FractionLength: 15

        RoundMode: nearest
        OverflowMode: saturate
        ProductMode: FullPrecision
    MaxProductWordLength: 128
        SumMode: FullPrecision
    MaxSumWordLength: 128
    CastBeforeSum: true

logreport(a)

    minlog    maxlog    lowerbound    upperbound    noverflows    nunderflows
a         -1    0.9999695         -1    0.9999695         3         0

```

Now set `DataTypeOverride` to `'ScaledDoubles'`. Note that overflows are reported, but the data is not quantized. The minimum and maximum logs show the full possible range of the data without quantization:

```

p = fipref;
p.LoggingMode = 'On';
p.DataTypeOverride = 'ScaledDoubles';

b = fi(-2:2, true, 16, 15)
Warning: 3 overflows occurred in the fi assignment operation.

b =

    -2    -1     0     1     2

```

```
DataTypeMode: Scaled double: binary point scaling
Signed: true
WordLength: 16
FractionLength: 15
```

```
RoundMode: nearest
OverflowMode: saturate
ProductMode: FullPrecision
MaxProductWordLength: 128
SumMode: FullPrecision
MaxSumWordLength: 128
CastBeforeSum: true
```

```
logreport(b)
```

```
minlog  maxlog  lowerbound  upperbound  noverflows  nunderflows
b       -2      2           -1      0.9999695      3           0
```

For an in-depth example of using logging and data type override to help set appropriate scalings for fixed-point quantities, see the Fixed-Point Toolbox demo “Fixed-Point Data Type Override, Min/Max Logging, and Scaling”.

Version 1.3 (R14SP3) Fixed-Point Toolbox Software

This table summarizes what's new in Version 1.3 (R14SP3):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	Yes—Details labeled as Compatibility Considerations , below. See also Summary.	Bug Reports Includes fixes	No

New features and changes introduced in this version are

- “Fixed-Point Toolbox Function Support Added to Embedded MATLAB Subset” on page 45
- “Double, Single, and Boolean Data Type Support Added to the fi Object” on page 46
- “Fixed-Point Doubles Override, Min/Max Logging, and Scaling Demo” on page 46
- “Helper Functions Added for Accessing Logged Information” on page 47
- “RoundMode Property Value 'round' Now Called 'nearest'” on page 47

Fixed-Point Toolbox Function Support Added to Embedded MATLAB Subset

The Embedded MATLAB Function block lets you compose a MATLAB language function in a Simulink model that generates embeddable code using the Embedded MATLAB subset. When you simulate the model or generate code for a target environment, a function in an Embedded MATLAB Function block generates efficient C code. This code meets the strict memory and data type requirements of embedded target environments. In this way, Embedded MATLAB Function blocks bring the power of MATLAB for the embedded environment into Simulink.

For more information about the Embedded MATLAB Function block and the Embedded MATLAB subset, refer to the following documentation:

- Embedded MATLAB Function block reference page in the Simulink documentation
- “Using the Embedded MATLAB Function Block” in the Simulink documentation
- “Working with the Embedded MATLAB Subset” in the Embedded MATLAB subset documentation

You can now use a significant number of Fixed-Point Toolbox functions with Embedded MATLAB subset. Refer to “Supported Functions and Limitations of the Fixed-Point Embedded MATLAB Subset” in the Using Fixed-Point Toolbox documentation.

Note To simulate models using fixed-point data types in Simulink, including when using the Embedded MATLAB Function block, you must have a Simulink® Fixed Point™ license.

Double, Single, and Boolean Data Type Support Added to the fi Object

The `fi` object now supports double, single, and boolean data types. The values `double`, `single`, and `boolean` have been added to the `DataType` and `DataTypeMode` properties of the `numericType` object. Math operations are supported for `fi` objects with data type `single` or `double`, but not `boolean`.

Fixed-Point Doubles Override, Min/Max Logging, and Scaling Demo

Since floating-point data types are now supported in Fixed-Point Toolbox software, it is possible to use doubles override and min/max scaling to help you choose the appropriate scalings for fixed-point variables in your algorithms. This is especially helpful when converting a floating-point algorithm to fixed point. A new demo “Fixed-Point Doubles Override, Min/Max Logging, and Scaling” leads you through an example of this process. You can access

this demo from the **Demos** pane of the Help browser under Toolboxes > Fixed-Point.

Helper Functions Added for Accessing Logged Information

In the previous release it became possible to log overflows and underflows as warnings for all assignment, plus, minus, and multiplication operations when the `fipref LoggingMode` property is set to on. Now when `LoggingMode` is on, you can also use the following helper functions to return logged information to you at the MATLAB command line:

- `maxlog` — Returns the maximum real-world value
- `minlog` — Returns the minimum real-world value
- `noperations` — Returns the number of quantized operations
- `noverflows` — Returns the number of overflows
- `nunderflows` — Returns the number of underflows

To clear the log, use the function `resetlog`.

RoundMode Property Value 'round' Now Called 'nearest'

The `RoundMode` property value `round` is now `nearest`. This is a reflection of the fact that this rounding mode is identical to the Simulink rounding mode `round toward nearest`, and different from the behavior of the MATLAB `round` function.

Compatibility Considerations

For this release, any code using the `RoundMode` property value `round` will still work as it did in previous releases. However, you should update each instance of the property value `round` to `nearest` because in a later release, the property value `round` will give a different answer.

Version 1.2 (R14SP2) Fixed-Point Toolbox Software

This table summarizes what's new in Version 1.2 (R14SP2):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	No	Bug Reports	No

New features and changes introduced in this version are

- “Overflow and Underflow Logging” on page 48
- “New Functions” on page 48

Overflow and Underflow Logging

Fixed-Point Toolbox software now allows you to log overflows and underflows as warnings for all assignment, plus, minus, and multiplication operations. Refer to “Using fipref Objects to Set Logging Preferences” in the Fixed-Point Toolbox documentation for more information.

New Functions

The following functions are new in version 1.2 of Fixed-Point Toolbox software:

abs	all	and	any	area
bar	barh	buffer	clabel	comet
comet3	compass	coneplot	contour	contour3
contourc	contourf	diag	end	errorbar
etreeplot	ezcontour	ezcontourf	ezmesh	ezplot
ezplot3	ezpolar	ezsurf	ezsurfc	feather
fplot	gplot	hankel	hist	histc
intmin	ipermute	isnumeric	isobject	line
logical	lowerbound	mesh	meshc	meshz

not	numberofelements	or	patch	pcolor
permute	plot3	plotmatrix	plotyy	polar
pow2	quiver	quiver3	rgbplot	ribbon
rose	scatter	scatter3	sdec	sign
slice	spy	stairs	stem	stem3
streamribbon	streamslice	streamtube	sum	surf
surfc	surfl	surfnorm	text	toeplitz
treeplot	tril	trimesh	triplot	trisurf
triu	uplus	upperbound	voronoi	voronoin
waterfall	xlim	ylim	zlim	

Version 1.1 (R14SP1) Fixed-Point Toolbox Software

This table summarizes what's new in Version 1.1 (R14SP1):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
No	No	Yes Details below	No

The particularly important bug fixes in this version are

Bitwise Operators Return Correct Answers for [Slope Bias] Signals

In the previous release, bitwise functions such as `bitshift` might have given wrong answers for [Slope Bias] fixed-point signals. This has been corrected in this release.

fi Object Operations with an Empty Array Work Properly

In the previous release, a segmentation violation occurred for any operation with the format

`a op e`

where `a` is a `fi` object, `e` is an empty array, and `op` is any operator such as `+`, `-`, `*`, `.*`, `<`, `>`, etc. This has been corrected in this release.

ispropequal Returns Correct Answers for fimath Objects

The `ispropequal` function has been updated to work properly in this release.

Version 1.0 (R14) Fixed-Point Toolbox Software

This table summarizes what's new in Version 1.0 (R14):

New Features and Changes	Version Compatibility Considerations	Fixed Bugs and Known Problems	Related Documentation at Web Site
Yes Details below	No	No bug fixes	No

Fixed-Point Toolbox software provides fixed-point data types in MATLAB and enables algorithm development by providing fixed-point arithmetic. The toolbox enables you to create the following types of objects:

- `fi` — Defines a fixed-point numeric object in the MATLAB workspace. Each `fi` object is composed of value data, a `fiarith` object, and a `numericity` object
- `fiarith` — Governs how overloaded arithmetic operators work with `fi` objects
- `fipref` — Defines the display attributes for `fi` objects
- `numericity` — Defines the data type and scaling attributes of `fi` objects
- `quantizer` — Quantizes data sets

Features

Fixed-Point Toolbox software provides you with

- The ability to define fixed-point data types, scaling, and rounding and overflow methods in the MATLAB workspace
- Bit-true real and complex simulation
- Basic fixed-point arithmetic with binary point-only signals
 - Arithmetic operators `+`, `-`, `*`, `.*`
 - Division using the `divide` function
- Arbitrary word length up to `intmax('uint16')`

- Relational, logical, and bitwise operators
- Data visualization via the `plot` function
- Statistics functions such as `abs`, `max`, and `min`
- Conversions between binary, hex, double, and built-in integers
- Interoperability with Simulink, Signal Processing Blockset™ software, and Filter Design Toolbox™ software
- Compatibility with the Simulink To Workspace and From Workspace blocks

Getting Help

This section tells you how to get help for Fixed-Point Toolbox software in this document and at the MATLAB command line.

Getting Help in the Fixed-Point Toolbox User's Guide

Fixed-Point Toolbox objects are discussed in the following chapters:

- “Working with `fi` Objects”
- “Working with `fi`math Objects”
- “Working with `fi`pref Objects”
- “Working with `numeric`type Objects”
- “Working with quantizer Objects”

To get in-depth information about the properties of these objects, refer to “Property Reference”.

To get in-depth information about the functions of these objects, refer to Function Reference.

Getting Help at the MATLAB Command Line

To get command-line help for Fixed-Point Toolbox objects, type

```
help objectname
```

For example:


```
help fi
help fimath
help fipref
help numericity
help quantizer
```

To invoke Help Browser documentation for Fixed-Point Toolbox functions from the MATLAB command line, type

```
doc fixedpoint/functionname
```

For example:

```
doc fixedpoint/int
doc fixedpoint/add
doc fixedpoint/savefipref
doc fixedpoint/quantize
```

Compatibility Summary for Fixed-Point Toolbox Software

This table summarizes new features and changes that might cause incompatibilities when you upgrade from an earlier version, or when you use files on multiple versions. Details are provided in the description of the new feature or change.

Version (Release)	New Features and Changes with Version Compatibility Impact
Latest Version V3.2 (R2010b)	See the Compatibility Considerations subheading for this new feature or change: <ul style="list-style-type: none"> • “Changes to the DataTypeMode Property of the numerictype Object” on page 5 • “Functions Being Removed” on page 7
V3.1 (R2010a)	See the Compatibility Considerations subheading for this new feature or change: <ul style="list-style-type: none"> • “Functions Being Removed” on page 12
V3.0 (R2009b)	See the Compatibility Considerations subheading for this new feature or change: <ul style="list-style-type: none"> • “New Relationship Between fi Objects and a Global fimath Simplifies Fixed-Point Arithmetic” on page 13 • “New Compilation Report for Embedded MATLAB Function Blocks” on page 18

Version (Release)	New Features and Changes with Version Compatibility Impact
V2.4 (R2009a)	<p>See the Compatibility Considerations subheading for this new feature or change:</p> <ul style="list-style-type: none"> • “New Compilation Report for emlc and emlhex” on page 20 • “Complex fi Objects with Nontrivial Slope and Bias Scaling Are No Longer Supported” on page 22
V2.3 (R2008b)	None
V2.2 (R2008a)	None
V2.1.1 (R2007b+)	None
V2.1 (R2007b)	<p>See the Compatibility Considerations subheading for each of these new features or changes:</p> <ul style="list-style-type: none"> • “bitget Function Updated” on page 31 • “divide Function Updated” on page 32 • “fi Constructor Applies Property/Value Pairs After Numeric Value” on page 32

Version (Release)	New Features and Changes with Version Compatibility Impact
V2.0 (R2007a)	<p>See the Compatibility Considerations subheading for each of these new features or changes:</p> <ul style="list-style-type: none"> • “get Function Must be Declared Extrinsic in Embedded MATLAB Subset” on page 35 • “Embedded MATLAB Subset Does Not Support & and Operators” on page 35
V1.5 (R2006b)	None
V1.4 (R2006a)	<p>See the Compatibility Considerations subheading for each of these new features or changes:</p> <ul style="list-style-type: none"> • “Embedded MATLAB Subset Does Not Support a CastBeforeSum Value of 'false'” on page 40 • “numericType Object Syntax Change” on page 41 • “Minimums and Maximums Now Logged After Quantization” on page 42
V1.3 (R14SP3)	<p>See the Compatibility Considerations subheading for this new feature or change:</p> <ul style="list-style-type: none"> • “RoundMode Property Value 'round' Now Called 'nearest’” on page 47
V1.2 (R14SP2)	None

Version (Release)	New Features and Changes with Version Compatibility Impact
V1.1 (R14SP1)	None
V1.0 (R14)	Not applicable