

# DSP System Toolbox™

Reference

R2012b

MATLAB®  
& SIMULINK®

## How to Contact MathWorks



[www.mathworks.com](http://www.mathworks.com) Web  
[comp.soft-sys.matlab](mailto:comp.soft-sys.matlab) Newsgroup  
[www.mathworks.com/contact\\_TS.html](http://www.mathworks.com/contact_TS.html) Technical Support



[suggest@mathworks.com](mailto:suggest@mathworks.com) Product enhancement suggestions  
[bugs@mathworks.com](mailto:bugs@mathworks.com) Bug reports  
[doc@mathworks.com](mailto:doc@mathworks.com) Documentation error reports  
[service@mathworks.com](mailto:service@mathworks.com) Order status, license renewals, passcodes  
[info@mathworks.com](mailto:info@mathworks.com) Sales, pricing, and general information



508-647-7000 (Phone)



508-647-7001 (Fax)



The MathWorks, Inc.  
3 Apple Hill Drive  
Natick, MA 01760-2098

For contact information about worldwide offices, see the MathWorks Web site.

*DSP System Toolbox™ Reference*

© COPYRIGHT 2011–2012 by MathWorks, Inc.

The software described in this document is furnished under a license agreement. The software may be used or copied only under the terms of the license agreement. No part of this manual may be photocopied or reproduced in any form without prior written consent from The MathWorks, Inc.

FEDERAL ACQUISITION: This provision applies to all acquisitions of the Program and Documentation by, for, or through the federal government of the United States. By accepting delivery of the Program or Documentation, the government hereby agrees that this software or documentation qualifies as commercial computer software or commercial computer software documentation as such terms are used or defined in FAR 12.212, DFARS Part 227.72, and DFARS 252.227-7014. Accordingly, the terms and conditions of this Agreement and only those rights specified in this Agreement, shall pertain to and govern the use, modification, reproduction, release, performance, display, and disclosure of the Program and Documentation by the federal government (or other entity acquiring for or through the federal government) and shall supersede any conflicting contractual terms or conditions. If this License fails to meet the government's needs or is inconsistent in any respect with federal procurement law, the government agrees to return the Program and Documentation, unused, to The MathWorks, Inc.

### Trademarks

MATLAB and Simulink are registered trademarks of The MathWorks, Inc. See [www.mathworks.com/trademarks](http://www.mathworks.com/trademarks) for a list of additional trademarks. Other product or brand names may be trademarks or registered trademarks of their respective holders.

### Patents

MathWorks products are protected by one or more U.S. patents. Please see [www.mathworks.com/patents](http://www.mathworks.com/patents) for more information.

### Revision History

April 2011	Online only	Revised for Version 8.0 (R2011a)
September 2011	Online only	Revised for Version 8.1 (R2011b)
March 2012	Online only	Revised for Version 8.2 (R2012a)
September 2012	Online only	Revised for Version 8.3 (R2012b)

## Block Reference

**1**

<b>Estimation</b> .....	1-2
Linear Prediction .....	1-2
Parametric Estimation .....	1-3
Power Spectrum Estimation .....	1-3
<b>Filtering</b> .....	1-4
Adaptive Filters .....	1-4
Filter Designs .....	1-4
Filter Implementations .....	1-5
Multirate Filters .....	1-6
<b>Math Functions</b> .....	1-7
Math Operations .....	1-7
Matrices and Linear Algebra .....	1-7
Polynomial Functions .....	1-10
<b>Quantizers</b> .....	1-11
<b>Signal Management</b> .....	1-12
Buffers .....	1-12
Indexing .....	1-12
Signal Attributes .....	1-13
Switches and Counters .....	1-13
<b>Signal Operations</b> .....	1-15
<b>Sinks</b> .....	1-17
<b>Sources</b> .....	1-18
<b>Statistics</b> .....	1-19

Transforms .....	1-20
------------------	------

## Blocks — Alphabetical List

**2**

## System object Reference

**3**

Define New System Objects .....	3-2
Estimation .....	3-3
Filtering .....	3-4
Math Functions .....	3-5
Quantizers .....	3-6
Signal Management .....	3-7
Signal Operations .....	3-8
Sinks .....	3-9
Sources .....	3-10
Measurements and Statistics .....	3-11
Transforms .....	3-12

## Analysis Methods for Filter System Objects

4

Analysis Methods for Filter System Objects .....	4-2
--	-----

## Alphabetical List

5

## Function Reference

6

<b>Adaptive Filters</b> .....	6-2
Least Mean Squares .....	6-2
Recursive Least Squares .....	6-3
Affine Projection .....	6-3
Frequency Domain .....	6-3
Lattice .....	6-4
<b>Discrete-Time Filters</b> .....	6-5
<b>Filter Specifications — Response Types</b> .....	6-7
<b>Filter Specifications — Design Methods</b> .....	6-9
<b>Multirate Filters</b> .....	6-10
<b>GUIs</b> .....	6-11
<b>Filter Analysis</b> .....	6-12
<b>Fixed-Point Filters</b> .....	6-15
<b>Quantized Filter Analysis</b> .....	6-16

<b>SOS Conversion</b> .....	<b>6-17</b>
<b>Filter Design</b> .....	<b>6-18</b>
<b>Filter Conversion</b> .....	<b>6-19</b>
<b>Signal Logging</b> .....	<b>6-20</b>
<b>Simulink Signal Processing Functions</b> .....	<b>6-21</b>

## Functions — Alphabetical List

# 7

## Reference for the Properties of Filter Objects

# 8

<b>Fixed-Point Filter Properties</b> .....	<b>8-2</b>
Overview of Fixed-Point Filters .....	<b>8-2</b>
Fixed-Point Objects and Filters .....	<b>8-2</b>
Summary — Fixed-Point Filter Properties .....	<b>8-5</b>
Property Details for Fixed-Point Filters .....	<b>8-18</b>
<b>Adaptive Filter Properties</b> .....	<b>8-102</b>
Property Summaries .....	<b>8-102</b>
Property Details for Adaptive Filter Properties .....	<b>8-107</b>
References for Adaptive Filters .....	<b>8-114</b>
<b>Multirate Filter Properties</b> .....	<b>8-115</b>
Property Summaries .....	<b>8-115</b>
Property Details for Multirate Filter Properties .....	<b>8-120</b>
References for Multirate Filters .....	<b>8-130</b>

**Glossary**

---

**Index**

---



# Block Reference

---

Estimation (p. 1-2)	Perform spectrum estimates and autoregressive modeling
Filtering (p. 1-4)	Design, create, and work with filters
Math Functions (p. 1-7)	Perform linear algebra and basic math calculations
Quantizers (p. 1-11)	Design and implement quantization schemes
Signal Management (p. 1-12)	Perform basic signal processing operations
Signal Operations (p. 1-15)	Control signal attributes, buffer signals, and index signals
Sinks (p. 1-17)	View or log signals
Sources (p. 1-18)	Generate discrete-time signals
Statistics (p. 1-19)	Perform statistical computations on signals
Transforms (p. 1-20)	Compute transforms

## Estimation

Linear Prediction (p. 1-2)	Compute or work with linear predictive representations
Parametric Estimation (p. 1-3)	Compute estimates of autoregressive model parameters
Power Spectrum Estimation (p. 1-3)	Compute parametric and nonparametric spectral estimates

## Linear Prediction

Autocorrelation LPC	Determine coefficients of Nth-order forward linear predictors
Levinson-Durbin	Solve linear system of equations using Levinson-Durbin recursion
LPC to LSF/LSP Conversion	Convert linear prediction coefficients to line spectral pairs or line spectral frequencies
LPC to/from Cepstral Coefficients	Convert linear prediction coefficients to cepstral coefficients or cepstral coefficients to linear prediction coefficients
LPC to/from RC	Convert linear prediction coefficients to reflection coefficients or reflection coefficients to linear prediction coefficients
LPC/RC to Autocorrelation	Convert linear prediction coefficients or reflection coefficients to autocorrelation coefficients
LSF/LSP to LPC Conversion	Convert line spectral frequencies or line spectral pairs to linear prediction coefficients

## Parametric Estimation

Burg AR Estimator	Compute estimate of autoregressive (AR) model parameters using Burg method
Covariance AR Estimator	Compute estimate of autoregressive (AR) model parameters using covariance method
Modified Covariance AR Estimator	Compute estimate of autoregressive (AR) model parameters using modified covariance method
Yule-Walker AR Estimator	Compute estimate of autoregressive (AR) model parameters using Yule-Walker method

## Power Spectrum Estimation

Burg Method	Power spectral density estimate using Burg method
Covariance Method	Power spectral density estimate using covariance method
Magnitude FFT	Compute nonparametric estimate of spectrum using periodogram method
Modified Covariance Method	Power spectral density estimate using modified covariance method
Periodogram	Power spectral density or mean-square spectrum estimate using periodogram method
Yule-Walker Method	Power spectral density estimate using Yule-Walker method

## Filtering

Adaptive Filters (p. 1-4)	Use adaptive filter algorithms
Filter Designs (p. 1-4)	Design and implement single- and multirate FIR and IIR filters
Filter Implementations (p. 1-5)	Design and implement filters
Multirate Filters (p. 1-6)	Implement multirate filters

### Adaptive Filters

Block LMS Filter	Compute output, error, and weights using LMS adaptive algorithm
Fast Block LMS Filter	Compute output, error, and weights using LMS adaptive algorithm
Kalman Filter	Predict or estimate states of dynamic systems
LMS Filter	Compute output, error, and weights using LMS adaptive algorithm
RLS Filter	Compute filtered output, filter error, and filter weights for given input and desired signal using RLS adaptive filter algorithm

### Filter Designs

Arbitrary Response Filter	Design arbitrary response filter
Audio Weighting Filter	Design audio weighting filter
Bandpass Filter	Design bandpass filter
Bandstop Filter	Design bandstop filter
CIC Compensator	Design CIC compensator

CIC Filter	Design Cascaded Integrator-Comb (CIC) Filter
Comb Filter	Design comb Filter
Differentiator Filter	Design differentiator filter
Halfband Filter	Design halfband filter
Highpass Filter	Design highpass filter
Hilbert Filter	Design Hilbert filter
Inverse Sinc Filter	Design inverse sinc filter
Lowpass Filter	Design lowpass filter
Nyquist Filter	Design Nyquist filter
Octave Filter	Design octave filter
Parametric Equalizer	Design parametric equalizer
Peak-Notch Filter	Design peak or notch filter
Pulse Shaping Filter	Design pulse shaping filter

## Filter Implementations

Allpole Filter	Model allpole filters
Analog Filter Design	Design and implement analog filters
Biquad Filter	Model biquadratic IIR (SOS) filters
Digital Filter	Filter each channel of input over time using static or time-varying digital filter implementations
Digital Filter Design	Design and implement digital FIR and IIR filters
Discrete FIR Filter	Model FIR filters
Filter Realization Wizard	Construct filter realizations using Digital Filter block or Sum, Gain, and Delay blocks

Overlap-Add FFT Filter

Implement overlap-add method of frequency-domain filtering

Overlap-Save FFT Filter

Implement overlap-save method of frequency-domain filtering

## **Multirate Filters**

CIC Decimation

Decimate signal using Cascaded Integrator-Comb filter

CIC Interpolation

Interpolate signal using Cascaded Integrator-Comb filter

Dyadic Analysis Filter Bank

Decompose signals into subbands with smaller bandwidths and slower sample rates or compute discrete wavelet transform (DWT)

Dyadic Synthesis Filter Bank

Reconstruct signals from subbands with smaller bandwidths and slower sample rates or compute inverse discrete wavelet transform (IDWT)

FIR Decimation

Filter and downsample input signals

FIR Interpolation

Upsample and filter input signals

FIR Rate Conversion

Upsample, filter, and downsample input signals

Two-Channel Analysis Subband Filter

Decompose signal into high-frequency and low-frequency subbands

Two-Channel Synthesis Subband Filter

Reconstruct signal from high-frequency and low-frequency subbands

## Math Functions

Math Operations (p. 1-7)	Use specialized math operations for signal processing applications
Matrices and Linear Algebra (p. 1-7)	Work with matrices
Polynomial Functions (p. 1-10)	Work with polynomials

### Math Operations

Complex Exponential	Compute complex exponential function
Cumulative Product	Cumulative product of channel, column, or row elements
Cumulative Sum	Cumulative sum of channel, column, or row elements
dB Conversion	Convert magnitude data to decibels (dB or dBm)
dB Gain	Apply decibel gain
Difference	Compute element-to-element difference along specified dimension of input
Normalization	Perform vector normalization along rows, columns, or specified dimension

### Matrices and Linear Algebra

Linear System Solvers (p. 1-8)	Solve matrix equation $AX = B$ for $X$
Matrix Factorizations (p. 1-8)	Factor matrices
Matrix Inverses (p. 1-9)	Invert matrices
Matrix Operations (p. 1-9)	Perform basic matrix operations

## **Linear System Solvers**

Backward Substitution	Solve $UX=B$ for $X$ when $U$ is upper triangular matrix
Cholesky Solver	Solve $SX=B$ for $X$ when $S$ is square Hermitian positive definite matrix
Forward Substitution	Solve $LX=B$ for $X$ when $L$ is lower triangular matrix
LDL Solver	Solve $SX=B$ for $X$ when $S$ is square Hermitian positive definite matrix
Levinson-Durbin	Solve linear system of equations using Levinson-Durbin recursion
LU Solver	Solve $AX=B$ for $X$ when $A$ is square matrix
QR Solver	Find minimum-norm-residual solution to $AX=B$
SVD Solver	Solve $AX=B$ using singular value decomposition

## **Matrix Factorizations**

Cholesky Factorization	Factor square Hermitian positive definite matrix into triangular components
LDL Factorization	Factor square Hermitian positive definite matrices into lower, upper, and diagonal components
LU Factorization	Factor square matrix into lower and upper triangular components
QR Factorization	Factor arbitrary matrix into unitary and upper triangular components
Singular Value Decomposition	Factor matrix using singular value decomposition

## Matrix Inverses

Cholesky Inverse	Compute inverse of Hermitian positive definite matrix using Cholesky factorization
LDL Inverse	Compute inverse of Hermitian positive definite matrix using LDL factorization
LU Inverse	Compute inverse of square matrix using LU factorization
Pseudoinverse	Compute Moore-Penrose pseudoinverse of matrix

## Matrix Operations

Array-Vector Add	Add vector to array along specified dimension
Array-Vector Divide	Divide array by vector along specified dimension
Array-Vector Multiply	Multiply array by vector along specified dimension
Array-Vector Subtract	Subtract vector from array along specified dimension
Constant Diagonal Matrix	Generate square, diagonal matrix
Create Diagonal Matrix	Create square diagonal matrix from diagonal elements
Extract Diagonal	Extract main diagonal of input matrix
Extract Triangular Matrix	Extract lower or upper triangle from input matrices
Identity Matrix	Generate matrix with ones on main diagonal and zeros elsewhere
Matrix 1-Norm	Compute 1-norm of matrix

Matrix Concatenate	Concatenate input signals of same data type to create contiguous output signal
Matrix Exponential	Compute matrix exponential
Matrix Multiply	Multiply or divide inputs
Matrix Product	Multiply matrix elements along rows, columns, or entire input
Matrix Square	Compute square of input matrix
Matrix Sum	Sum matrix elements along rows, columns, or entire input
Matrix Sum (Obsolete)	Sum matrix elements along rows, columns, or entire input
Overwrite Values	Overwrite submatrix or subdiagonal of input
Permute Matrix	Reorder matrix rows or columns
Reciprocal Condition	Compute reciprocal condition of square matrix in 1-norm
Submatrix	Select subset of elements (submatrix) from matrix input
Toeplitz	Generate matrix with Toeplitz symmetry
Transpose	Transpose matrix

## **Polynomial Functions**

Least Squares Polynomial Fit	Compute polynomial coefficients that best fit input data in least-squares sense
Polynomial Evaluation	Evaluate polynomial expression
Polynomial Stability Test	Use Schur-Cohn algorithm to determine whether all roots of input polynomial are inside unit circle

## Quantizers

G711 Codec	Quantize narrowband speech input signals
Quantizer	Discretize input at specified interval
Scalar Quantizer Decoder	Convert each index value into quantized output value
Scalar Quantizer Design	Start Scalar Quantizer Design Tool (SQDTool) to design scalar quantizer using Lloyd algorithm
Scalar Quantizer Encoder	Encode each input value by associating it with index value of quantization region
Uniform Decoder	Decode integer input into floating-point output
Uniform Encoder	Quantize and encode floating-point input into integer output
Vector Quantizer Decoder	Find vector quantizer codeword that corresponds to given, zero-based index value
Vector Quantizer Design	Design vector quantizer using Vector Quantizer Design Tool (VQDTool)
Vector Quantizer Encoder	For given input, find index of nearest codeword based on Euclidean or weighted Euclidean distance measure

## Signal Management

Buffers (p. 1-12)	Change sample rate or frame rate of signals by buffering or unbuffering
Indexing (p. 1-12)	Manipulate ordering of signals
Signal Attributes (p. 1-13)	Inspect or modify signal attributes
Switches and Counters (p. 1-13)	Perform actions when events occur

### Buffers

Buffer	Buffer input sequence to smaller or larger frame size
Delay Line	Rebuffer sequence of inputs
Queue	Store inputs in FIFO register
Stack	Store inputs into LIFO register
Unbuffer	Unbuffer input frame into sequence of scalar outputs

### Indexing

Flip	Flip input vertically or horizontally
Multipoint Selector	Distribute arbitrary subsets of input rows or columns to multiple output ports
Overwrite Values	Overwrite submatrix or subdiagonal of input
Selector	Select input elements from vector, matrix, or multidimensional signal

Submatrix	Select subset of elements (submatrix) from matrix input
Variable Selector	Select subset of rows or columns from input

## Signal Attributes

Check Signal Attributes	Error when input signal does or does not match selected attributes exactly
Convert 1-D to 2-D	Reshape 1-D or 2-D input to 2-D matrix with specified dimensions
Convert 2-D to 1-D	Convert 2-D matrix input to 1-D vector
Data Type Conversion	Convert input signal to specified data type
Frame Conversion	Specify sampling mode of output signal
Inherit Complexity	Change complexity of input to match reference signal

## Switches and Counters

Counter	Count up or down through specified range of numbers
Edge Detector	Detect transition from zero to nonzero value
Event-Count Comparator	Detect threshold crossing of accumulated nonzero inputs
Multiphase Clock	Generate multiple binary clock signals

N-Sample Enable

Output ones or zeros for specified number of sample times

N-Sample Switch

Switch between two inputs after specified number of sample periods

## Signal Operations

Constant Ramp	Generate ramp signal with length based on input dimensions
Convolution	Convolution of two inputs
Delay	Delay discrete-time input by specified number of samples or frames
Downsample	Resample input at lower rate by deleting samples
Interpolation	Interpolate values of real input samples
NCO	Generate real or complex sinusoidal signals
Offset	Truncate vectors by removing or keeping beginning or ending values
Pad	Pad or truncate specified dimension(s)
Peak Finder	Determine whether each value of input signal is local minimum or maximum
Repeat	Resample input at higher rate by repeating values
Sample and Hold	Sample and hold input signal
Triggered Signal From Workspace	Import signal samples from MATLAB <sup>®</sup> workspace when triggered
Unwrap	Unwrap signal phase
Upsample	Resample input at higher rate by inserting zeros
Variable Fractional Delay	Delay input by time-varying fractional number of sample periods

Variable Integer Delay

Delay input by time-varying integer number of sample periods

Window Function

Compute and/or apply window to input signal

Zero Crossing

Count number of times signal crosses zero in single time step

## Sinks

Display	Show value of input
Matrix Viewer	Display matrices as color images
Signal To Workspace	Write data to MATLAB workspace
Spectrum Scope	Display mean-square spectrum or power spectral density of each input signal
Time Scope	Display time-domain signals
To Audio Device	Write audio data to computer's audio device
To Multimedia File	Write video frames and audio samples to multimedia file
Triggered To Workspace	Write input sample to MATLAB workspace when triggered
UDP Send	Send UDP message
Vector Scope	Display vector or matrix of time-domain, frequency-domain, or user-defined data
Waterfall	View vectors of data over time

## Sources

Chirp	Generate swept-frequency cosine (chirp) signal
Constant	Generate constant value
Constant Diagonal Matrix	Generate square, diagonal matrix
Discrete Impulse	Generate discrete impulse
DSP Constant (Obsolete)	Generate discrete- or continuous-time constant signal
From Audio Device	Read audio data from computer's audio device
From Multimedia File	Read multimedia file
Identity Matrix	Generate matrix with ones on main diagonal and zeros elsewhere
MIDI Controls	Output values from controls on MIDI control surface
Multiphase Clock	Generate multiple binary clock signals
N-Sample Enable	Output ones or zeros for specified number of sample times
Random Source	Generate randomly distributed values
Signal From Workspace	Import signal from MATLAB workspace
Sine Wave	Generate continuous or discrete sine wave
UDP Receive	Receive <code>uint8</code> vector as UDP message

## Statistics

Autocorrelation	Autocorrelation of vector or matrix input
Correlation	Cross-correlation of two inputs
Detrend	Remove linear trend from vectors
Histogram	Generate histogram of input or sequence of inputs
Maximum	Find maximum values in input or sequence of inputs
Mean	Find mean value of input or sequence of inputs
Median	Find median value of input
Minimum	Find minimum values in input or sequence of inputs
RMS	Compute root-mean-square value of input or sequence of inputs
Sort	Sort input elements by value
Standard Deviation	Find standard deviation of input or sequence of inputs
Variance	Compute variance of input or sequence of inputs

## Transforms

Analytic Signal	Compute analytic signals of discrete-time inputs
Complex Cepstrum	Compute complex cepstrum of input
DCT	Discrete cosine transform (DCT) of input
DWT	Discrete wavelet transform (DWT) of input or decompose signals into subbands with smaller bandwidths and slower sample rates
FFT	Fast Fourier transform (FFT) of input
IDCT	Inverse discrete cosine transform (IDCT) of input
IDWT	Inverse discrete wavelet transform (IDWT) of input or reconstruct signals from subbands with smaller bandwidths and slower sample rates
IFFT	Inverse fast Fourier transform (IFFT) of input
Inverse Short-Time FFT	Recover time-domain signals by performing inverse short-time, fast Fourier transform (FFT)
Magnitude FFT	Compute nonparametric estimate of spectrum using periodogram method
Real Cepstrum	Compute real cepstrum of input
Short-Time FFT	Nonparametric estimate of spectrum using short-time, fast Fourier transform (FFT) method

# Blocks — Alphabetical List

---

# Allpole Filter

---

## Purpose


Model allpole filters

## Library

Filtering / Filter Implementations

dsparch4

## Description



The Allpole Filter block independently filters each channel of the input signal with the specified allpole filter. The block can implement static filters with fixed coefficients, as well as time-varying filters with coefficients that change over time. You can tune the coefficients of a static filter during simulation.

This block filters each channel of the input signal independently over time. The **Input processing** parameter allows you to specify whether the block treats each element of the input as an independent channel (sample-based processing), or each column of the input as an independent channel (frame-based processing).

The outputs of this block numerically match the outputs of the DSP System Toolbox™ Digital Filter block.

This block supports the Simulink® state logging feature. See “States” in the *Simulink User’s Guide* for more information.

### Filter Structure Support

You can change the filter structure implemented with the Allpole Filter block by selecting one of the following from the **Filter structure** parameter:

- Direct form
- Direct form transposed
- Lattice AR

### Specifying Initial States

The Allpole Filter block initializes the internal filter states to zero by default, which has the same effect as assuming that past inputs and outputs are zero. You can optionally use the **Initial states** parameter to specify nonzero initial conditions for the filter delays.

To determine the number of initial states you must specify and how to specify them, see the table on valid initial states. The **Initial states** parameter can take one of the forms described in the next table.

## Valid Initial States

Initial Condition	Description
Scalar	The block initializes all delay elements in the filter to the scalar value.
Vector or matrix (for applying different delay elements to each channel)	Each vector or matrix element specifies a unique initial condition for a corresponding delay element in a corresponding channel: <ul style="list-style-type: none"><li>• The vector length equals the product of the number of input channels and the number of delay elements in the filter, <code>#_of_filter_coeffs-1</code> (or <code>#_of_reflection_coeffs</code> for Lattice AR).</li><li>• The matrix must have the same number of rows as the number of delay elements in the filter, <code>#_of_filter_coeffs-1</code> (<code>#_of_reflection_coeffs</code> for Lattice AR), and must have one column for each channel of the input signal.</li></ul>

## Data Type Support


The Allpole Filter block accepts and outputs real and complex signals of any numeric data type supported by Simulink. The block supports the same types for the coefficients.

The following diagrams show the filter structure and the data types used within the Allpole Filter block for fixed-point signals.


### Direct Form

You cannot specify the state data type on the block mask for this structure because the output states have the same data types as the output.

# Allpole Filter



# Allpole Filter




# Allpole Filter

---


## **Direct Form Transposed**

States are complex when either the inputs or the coefficients are complex.

# Allpole Filter





# Allpole Filter



# Allpole Filter

## Lattice AR






## Parameters and Dialog Box

The Main pane of the Allpole Filter block dialog box appears as follows.

# Allpole Filter



## Coefficient source

Select whether you want to specify the filter coefficients on the block mask or through an input port.

## Filter structure

Select the filter structure you want the block to implement. You can select `Direct form`, `Direct form transposed`, or `Lattice AR`.

## Coefficients

Specify the row vector of coefficients of the filter's transfer function.

This parameter is visible only when you set the **Coefficient source** to `Dialog parameters`.

## Input processing

Specify whether the block performs sample- or frame-based processing. You can select one of the following options:


- `Elements as channels (sample based)` — Treat each element of the input as an independent channel (sample-based processing).
- `Columns as channels (frame based)` — Treat each column of the input as an independent channel (frame-based processing).

## Initial states

Specify the initial conditions of the filter states. To learn how to specify initial states, see “Specifying Initial States” on page 2-2.

The **Data Types** pane of the Allpole Filter block dialog box appears as follows.

# Allpole Filter



## Coefficients

Specify the coefficient data type. You can set it to:

- A rule that inherits a data type, for example, Inherit: Same word length as input

- A built-in integer, for example, `int8`
- A data type object, for example, a `Simulink.NumericType` object
- An expression that evaluates to a data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Coefficient** parameter.

See “Specify Data Types Using Data Type Assistant” for more information.

### **Coefficients minimum**

Specify the minimum value that a filter coefficient should have. The default value is `[]` (unspecified). Simulink software uses this value to perform:

- Parameter range checking (see “Check Parameter Values”)
- Automatic scaling of fixed-point data types

### **Coefficients maximum**

Specify the maximum value that a filter coefficient should have. The default value is `[]` (unspecified). Simulink software uses this value to perform:

- Parameter range checking (see “Check Parameter Values”)
- Automatic scaling of fixed-point data types

### **Product output**

Specify the product output data type. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- A built-in data type, for example, `int8`

# Allpole Filter

---

- A data type object, for example, a `Simulink.NumericType` object
- An expression that evaluates to a data type, for example, `fixdt(1,16,0)`


Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output** parameter.

See “Specify Data Types Using Data Type Assistant” for more information.

## Accumulator

Specify the accumulator data type. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- A built-in data type, for example, `int8`
- A data type object, for example, a `Simulink.NumericType` object
- An expression that evaluates to a data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator** parameter.

See “Specify Data Types Using Data Type Assistant” for more information.

## State

Specify the state data type. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as accumulator`

- A built-in integer, for example, `int8`
- A data type object, for example, a `Simulink.NumericType` object
- An expression that evaluates to a data type, for example, `fixdt(1,16,0)`

This parameter is only visible when the selected filter structure is `Lattice MA`.

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **State** parameter.

See “Specify Data Types Using Data Type Assistant” for more information.

## Output

Specify the output data type. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as accumulator`
- A built-in data type, for example, `int8`
- A data type object, for example, a `Simulink.NumericType` object
- An expression that evaluates to a data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output** parameter.

See “Specify Block Output Data Types” in the *Simulink User’s Guide* for more information.

# Allpole Filter

---

## Output minimum

Specify the minimum value that the block should output. The default value is [ ] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Output maximum

Specify the maximum value that the block should output. The default value is [ ] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## Integer rounding mode

Specify the rounding mode for fixed-point operations. For more information, see “Rounding” in the Simulink Fixed Point™ documentation.

## Saturate on integer overflow

Action	Reasons for Taking This Action	What Happens for Overflows	Example
Select this check box.	Your model has possible overflow and you want explicit	Overflows saturate to either the minimum or maximum value	An overflow associated with a signed 8-bit

Action	Reasons for Taking This Action	What Happens for Overflows	Example
	saturation protection in the generated code.	that the data type can represent.	integer can saturate to -128 or 127.
Do not select this check box.	<p>You want to optimize efficiency of your generated code.</p> <p>You want to avoid overspecifying how a block handles out-of-range signals. For more information, see “Checking for Signal Range Errors”.</p>	Overflows wrap to the appropriate value that is representable by the data type.	The number 130 does not fit in a signed 8-bit integer and wraps to -126.

When you select this check box, saturation applies to every internal operation on the block, not just the output or result. In general, the code generation process can detect when overflow is not possible. In this case, the code generator does not produce saturation code.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point
- Fixed point
- 8-, 16-, and 32-bit integers

## See Also

Digital Filter	DSP System Toolbox
Filter Realization Wizard	DSP System Toolbox

# Allpole Filter

---

`fdatool`

DSP System Toolbox


`fvtool`

Signal Processing Toolbox

**Purpose** Design and implement analog filters

**Library** Filtering / Filter Implementations  
dsparch4

## Description



The Analog Filter Design block designs and implements a Butterworth, Chebyshev type I, Chebyshev type II, or elliptic filter in a highpass, lowpass, bandpass, or bandstop configuration.

The input must be a sample-based, continuous-time, real-valued, scalar signal.

The design and band configuration of the filter are selected from the **Design method** and **Filter type** pop-up menus in the dialog box. For each combination of design method and band configuration, an appropriate set of secondary parameters is displayed.

Filter Design	Description
Butterworth	The magnitude response of a Butterworth filter is maximally flat in the passband and monotonic overall.
Chebyshev type I	The magnitude response of a Chebyshev type I filter is equiripple in the passband and monotonic in the stopband.
Chebyshev type II	The magnitude response of a Chebyshev type II filter is monotonic in the passband and equiripple in the stopband.
Elliptic	The magnitude response of an elliptic filter is equiripple in both the passband and the stopband.

The following table lists the available parameters for each design/band combination. For lowpass and highpass band configurations, these parameters include the passband edge frequency  $\Omega_p$ , the stopband edge frequency  $\Omega_s$ , the passband ripple  $R_p$ , and the stopband attenuation  $R_s$ . For bandpass and bandstop configurations, the parameters include the


# Analog Filter Design

lower and upper passband edge frequencies,  $\Omega_{p1}$  and  $\Omega_{p2}$ , the lower and upper stopband edge frequencies,  $\Omega_{s1}$  and  $\Omega_{s2}$ , the passband ripple  $R_p$ , and the stopband attenuation  $R_s$ . Frequency values are in rad/s, and ripple and attenuation values are in dB.

	<b>Lowpass</b>	<b>Highpass</b>	<b>Bandpass</b>	<b>Bandstop</b>
<b>Butterworth</b>	Order, $\Omega_p$	Order, $\Omega_p$	Order, $\Omega_{p1}$ , $\Omega_{p2}$	Order, $\Omega_{p1}$ , $\Omega_{p2}$
<b>Chebyshev Type I</b>	Order, $\Omega_p$ , $R_p$	Order, $\Omega_p$ , $R_p$	Order, $\Omega_{p1}$ , $\Omega_{p2}$ , $R_p$	Order, $\Omega_{p1}$ , $\Omega_{p2}$ , $R_p$
<b>Chebyshev Type II</b>	Order, $\Omega_s$ , $R_s$	Order, $\Omega_s$ , $R_s$	Order, $\Omega_{s1}$ , $\Omega_{s2}$ , $R_s$	Order, $\Omega_{s1}$ , $\Omega_{s2}$ , $R_s$
<b>Elliptic</b>	Order, $\Omega_p$ , $R_p$ , $R_s$	Order, $\Omega_p$ , $R_p$ , $R_s$	Order, $\Omega_{p1}$ , $\Omega_{p2}$ , $R_p$ , $R_s$	Order, $\Omega_{p1}$ , $\Omega_{p2}$ , $R_p$ , $R_s$

The analog filters are designed using the filter design commands in Signal Processing Toolbox™ software's `buttap`, `cheb1ap`, `cheb2ap`, and `ellipap` functions, and are implemented in state-space form. Filters of order 8 or less are implemented in controller canonical form for improved efficiency.

## Dialog Box



The parameters displayed in the dialog box vary for different design/band combinations. Only some of the parameters listed below are visible in the dialog box at any one time.

### Design method

The filter design method: Butterworth, Chebyshev type I, Chebyshev type II, or Elliptic. Tunable.

### Filter type

The type of filter to design: Lowpass, Highpass, Bandpass, or Bandstop. Tunable.

### Filter order

The order of the filter, for lowpass and highpass configurations. For bandpass and bandstop configurations, the order of the final filter is *twice* this value.

# Analog Filter Design

---

## **Passband edge frequency**

The passband edge frequency, in rad/s, for the highpass and lowpass configurations of the Butterworth, Chebyshev type I, and elliptic designs. Tunable.

## **Lower passband edge frequency**

The lower passband frequency, in rad/s, for the bandpass and bandstop configurations of the Butterworth, Chebyshev type I, and elliptic designs. Tunable.

## **Upper passband edge frequency**

The upper passband frequency, in rad/s, for the bandpass and bandstop configurations of the Butterworth, Chebyshev type I, or elliptic designs. Tunable.

## **Stopband edge frequency**

The stopband edge frequency, in rad/s, for the highpass and lowpass band configurations of the Chebyshev type II design. Tunable.

## **Lower stopband edge frequency**

The lower stopband edge frequency, in rad/s, for the bandpass and bandstop configurations of the Chebyshev type II design. Tunable.

## **Upper stopband edge frequency**

The upper stopband edge frequency, in rad/s, for the bandpass and bandstop filter configurations of the Chebyshev type II design. Tunable.

## **Passband ripple in dB**

The passband ripple, in dB, for the Chebyshev Type I and elliptic designs. Tunable.

## **Stopband attenuation in dB**

The stopband attenuation, in dB, for the Chebyshev Type II and elliptic designs. Tunable.

## **References**

Antoniou, A. *Digital Filters: Analysis, Design, and Applications*. 2nd ed. New York, NY: McGraw-Hill, 1993.

## Supported Data Types

- Double-precision floating point

## See Also

Digital Filter Design	DSP System Toolbox
buttap	Signal Processing Toolbox
cheb1ap	Signal Processing Toolbox
cheb2ap	Signal Processing Toolbox
ellipap	Signal Processing Toolbox

See the following sections for related information:

- “Filter Design”
- “Filter Analysis”
- “Analog Filter Design Block”


# Analytic Signal

---

**Purpose** Compute analytic signals of discrete-time inputs

**Library** Transforms  
dspxfm3

## Description



The Analytic Signal block computes the complex analytic signal corresponding to each channel of the real  $M$ -by- $N$  input,  $u$

$$y = u + jH\{u\}$$

where  $j = \sqrt{-1}$  and  $H\{\}$  denotes the Hilbert transform. The real part of the output in each channel is a replica of the real input in that channel; the imaginary part is the Hilbert transform of the input. In the frequency domain, the Fourier transform of the analytic signal doubles the positive frequency content of the original signal while zeroing-out negative frequencies and retaining the DC component.

The block computes the Hilbert transform using an equiripple FIR filter with the order specified by the **Filter order** parameter,  $n$ . The linear phase filter is designed using the Remez exchange algorithm, and imposes a delay of  $n/2$  on the input samples.

The output has the same dimensions as the input.


### Frame-Based Processing

When you set the **Input processing** parameter to **Columns as channels (frame based)**, the block performs frame-based processing. In this mode, the block treats an  $M$ -by- $N$  matrix input as  $N$  independent channels containing  $M$  sequential time samples. The block computes the analytic signal for each channel over time.

### Sample-Based Processing

When you set the **Input processing** parameter to **Elements as channels (sample based)**, the block performs sample-based processing. In this mode, the block treats an  $M$ -by- $N$  matrix input as

$M \times N$  independent channels and computes the analytic signal for each channel (matrix element) over time.



## Dialog Box

### Filter order

The length of the FIR filter used to compute the Hilbert transform.

### Input processing

Specify how the block should process the input. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

# Analytic Signal

---

---

**Note** The Inherited (this choice will be removed - see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Supported Data Types

- Double-precision floating point
- Single-precision floating point


# Arbitrary Response Filter

---

**Purpose** Design arbitrary response filter

**Library** Filtering / Filter Designs  
dspfdesign

**Description** This block brings the filter design capabilities of the `filterbuilder` function to the Simulink environment.



**Dialog Box** See “Arbitrary Response Filter Design Dialog Box — Main Pane” on page 7-666 for more information about the parameters of this block. The **Data Types** and **Code Generation** panes are not available for blocks in the DSP System Toolbox Filter Designs library.

# Arbitrary Response Filter

Function Block Parameters: Arbitrary Response Filter

Arbitrary Response Filter

Design an arbitrary response filter. The constraint can be on the magnitude only, or on the magnitude and the phase.

[View Filter Response](#)

Filter specifications

Impulse response: FIR

Order mode: Specify

Order: 20

Filter Type: Single-rate

Response specifications

Number of bands: 1

Specify response as: Amplitudes

Frequency units: Normalized (0 to 1) Input Fs: 2

Band properties

	Frequencies	Amplitudes
1	<code>linspace(0, 1, 30)</code>	<code>[ones(1, 7) zeros(1,8) ones(1,8) zero</code>

Algorithm

Design method: Frequency Sampling

► Design options

Filter Implementation

Structure: Direct-form FIR

Use basic elements to enable filter customization

Input processing: Columns as channels (frame based)

## View filter response

This button opens the Filter Visualization Tool (fvtool) from the Signal Processing Toolbox product. You can use the tool to display:

- Magnitude response, phase response, and group delay in the frequency domain.
- Impulse response and step response in the time domain.
- Pole-zero information.

The tool also helps you evaluate filter performance by providing information about filter order, stability, and phase linearity. For more information on FVTool, see the Signal Processing Toolbox documentation.

## Filter Specifications

In this group, you specify your filter format, such as the impulse response and the filter order.

### Impulse response

Select either FIR or IIR from the drop down list, where FIR is the default. When you choose an impulse response, the design methods and structures you can use to implement your filter change accordingly.

### Order mode

Select Minimum or Specify from the drop-down list. Selecting Specify enables the **Order** option so you can enter the filter order. When you set the **Impulse response** to IIR, you can specify different numerator and denominator orders. To specify a different denominator order, you must select the **Denominator order** check box.

### Order

Enter the order for FIR filter, or the order of the numerator for the IIR filter.

### Denominator order

Select the check box and enter the denominator order. This option is enabled only if IIR is selected for **Impulse response**.

# Arbitrary Response Filter

---

## Filter type

This option is available for FIR filters only. Select **Single-rate**, **Decimator**, **Interpolator**, or **Sample-rate converter**. Your choice determines the type of filter as well as the design methods and structures that are available to implement your filter. By default, the block specifies a single-rate filter.

- Selecting **Decimator** or **Interpolator** activates the **Decimation Factor** or the **Interpolation Factor** options respectively.
- Selecting **Sample-rate converter** activates both factors.

## Decimation Factor

Enter the decimation factor. This option is enabled only if the **Filter type** is set to **Decimator** or **Sample-rate converter**. The default value is 2.

## Interpolation Factor

Enter the interpolation factor. This option is enabled only if the **Filter type** is set to **Interpolator** or **Sample-rate converter**. The default value is 2.

## Response Specification

### Number of Bands

Select the number of bands in the filter. Multiband design is available for both FIR and IIR filters.

### Specify response as

Specify the response as **Amplitudes**, **Magnitudes and phases**, **Frequency response**, or **Group delay**. **Group delay** is only available for IIR designs.

### Frequency units

Specify frequency units as either **Normalized**, which means normalized by the input sampling frequency, or select from **Hz**, **kHz**, **MHz**, or **GHz**.

## Input Fs

Enter the input sampling frequency in the units specified in the **Frequency units** drop-down list. When you select the frequency units, this option is available.

## Band Properties

These properties are modified automatically depending on the response chosen in the **Specify response as** drop-down list. Two or three columns are presented for input. The first column is always **Frequencies**. The other columns are **Amplitudes**, **Magnitudes**, **Phases**, or **Frequency Response**. Enter the corresponding vectors of values for each column.

- **Frequencies** and **Amplitudes** — These columns are presented for input if the response chosen in the **Specify response as** drop-down list is **Amplitudes**.
- **Frequencies**, **Magnitudes**, and **Phases** — These columns are presented for input if the response chosen in the **Specify response as** drop-down list is **Magnitudes** and **phases**.
- **Frequencies** and **Frequency response** — These columns are presented for input if the response chosen in the **Specify response as** drop-down list is **Frequency response**.

## Algorithm

### Design Method

Select the design method for the filter. Different methods are enabled depending on the defining parameters entered in the previous sections.

### Design Options

The options for each design are specific for each design method. This section does not present all of the available options for all designs and design methods. There are many more that you encounter as you select different design methods and filter specifications.

# Arbitrary Response Filter

---

- **Window** — Replace the square brackets with the name of a window function or function handle. For example, `hamming` or `@hamming`. If the window function takes parameters other than the length, use a cell array. For example, `{'kaiser',3.5}` or `{@chebwin,60}`.
- **Density factor** — Valid when the **Design method** is `Equiripple`. Density factor controls the density of the frequency grid over which the design method optimization evaluates your filter response function. The number of equally spaced points in the grid is the value you enter for **Density factor** times (filter order + 1).

Increasing the value creates a filter that more closely approximates an ideal equiripple filter but increases the time required to design the filter. The default value of 16 represents a reasonable trade-off between the accurate approximation to the ideal filter and the time to design the filter.

- **Phase constraint** — Valid when the **Design method** is `Equiripple`, you have the DSP System Toolbox installed, and **Specify response as** is set to `Amplitudes`. Choose one of `Linear`, `Minimum`, or `Maximum`.
- **Weights** — Valid when the **Design method** is `Equiripple`. Uses the weights in **Weights** to weight the error for a single-band design. If you have multiple frequency bands, the **Weights** design option changes to **B1 Weights**, **B2 Weights** to designate the separate bands.

## Filter Implementation

### Structure

Select the structure for the filter, available for the corresponding design method.

### Use basic elements to enable filter customization

Select this check box to implement the filter as a subsystem of basic Simulink blocks. Clear the check box to implement the filter as a high-level subsystem. By default, this check box is cleared.

The high-level implementation provides better compatibility across various filter structures, especially filters that would contain algebraic loops when constructed using basic elements. On the other hand, using basic elements enables the following optimization parameters:

- **Optimize for zero gains** — Terminate chains that contain Gain blocks with a gain of zero.
- **Optimize for unit gains** — Remove Gain blocks that scale by a factor of one.
- **Optimize for delay chains** — Substitute delay chains made up of  $n$  unit delays with a single delay by  $n$ .
- **Optimize for negative gains** — Use subtraction in Sum blocks instead of negative gains in Gain blocks.

### Optimize for unit-scale values

Select this check box to scale unit gains between sections in SOS filters. This parameter is available only for SOS filters.

### Input processing

Specify how the block should process the input. The available options may vary depending on the settings of the **Filter Structure** and **Use basic elements for filter customization** parameters. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

# Arbitrary Response Filter

---

---

**Note** The Inherited (this choice will be removed see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Rate options

When the **Filter type** parameter specifies a multirate filter, select the rate processing rule for the block from following options:

- Enforce single-rate processing — When you select this option, the block maintains the sample rate of the input.
- Allow multirate processing — When you select this option, the block adjusts the rate at the output to accommodate an increased or reduced number of samples. To select this option, you must set the **Input processing** parameter to Elements as channels (sample based).

## Use symbolic names for coefficients

Select this check box to enable the specification of coefficients using MATLAB variables. The available coefficient names differ depending on the filter structure. Using symbolic names allows tuning of filter coefficients in generated code. By default, this check box is cleared.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>


## Purpose

Add vector to array along specified dimension

## Library

Math Functions / Matrices and Linear Algebra / Matrix Operations  
dspmtx3

## Description



The Array-Vector Add block adds the values in the specified dimension of the  $N$ -dimensional input array  $A$  to the values in the input vector  $V$ .

The length of the input  $V$  must be the same as the length of the specified dimension of  $A$ . The Array-Vector Add block adds each element of  $V$  to the corresponding element along that dimension of  $A$ .

Consider a 3-dimensional  $M$ -by- $N$ -by- $P$  input array  $A(i,j,k)$  and a  $N$ -by-1 input vector  $V$ . When the **Add along dimension** parameter is set to 2, the output of the block  $Y(i,j,k)$  is

$$Y(i,j,k) = A(i,j,k) + V(j)$$

where

$$1 \leq i \leq M$$

$$1 \leq j \leq N$$

$$1 \leq k \leq P$$


The output of the Array-Vector Add block is the same size as the input array,  $A$ . This block accepts real and complex floating-point and fixed-point inputs.

## Fixed-Point Data Types

The following diagram shows the data types used within the Array-Vector Add block for fixed-point signals.

# Array-Vector Add

---




When you specify the vector  $V$  on the **Main** pane of the block mask, you must specify the data type and scaling properties of its elements in the **Vector (V)** parameter on the **Data Types** tab. When the vector comes in through the block port, its elements inherit their data type and scaling from the driving block.

You can set the vector, accumulator, and output data types in the block dialog as discussed below.

## Dialog Box

The **Main** pane of the Array-Vector Add block dialog appears as follows.



### Add along dimension

Specify the dimension along which to add the input array  $A$  to the elements of vector  $V$ .

# Array-Vector Add

---


## **Vector (V) source**

Specify the source of the vector,  $V$ . The vector can come from the `Input port` or from a `Dialog parameter`.

## **Vector (V)**

Specify the vector,  $V$ . This parameter is visible only when you select `Dialog parameter` for the **Vector (V) source** parameter.

The **Data Types** pane of the Array-Vector Add block dialog appears as follows.



**Note** Floating-point inheritance takes precedence over the data type settings defined on this pane. When inputs are floating point, the block ignores these settings, and all internal data types are floating point.

# Array-Vector Add

---

## Rounding mode

Select the rounding mode for fixed-point operations. If Accumulator Data Type is Inherit: Inherit via internal rule and Output Data Type is Inherit: Same as accumulator, the value of Rounding mode does not affect the numerical results.

---

**Note** The **Rounding mode** and **Overflow mode** settings have no effect on numerical results when both of the following conditions exist:

- **Accumulator data type** is Inherit: Inherit via internal rule
  - **Output data type** is Inherit: Same as accumulator
- With these data type settings, the block is effectively operating in full precision mode.
- 

## Overflow mode

Select the overflow mode for fixed-point operations.

## Vector (V)

Use this parameter to specify the word and fraction lengths for the elements of the vector, *V*. You can set this parameter to:

- A rule that inherits a data type, for example, Inherit: Same word length as input
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

---

**Note** The **Vector (V)** parameter on the **Data Types** pane is only visible when you select **Dialog** parameter for the **Vector (V)** **source** parameter on the **Main** pane of the block mask. When the vector comes in through the block's input port, the data type and scaling of its elements are inherited from the driving block.

---

## Accumulator data type

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-37 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, **Inherit: Inherit via internal rule**
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User's Guide* for more information.

## Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-37 for illustrations depicting the use of the output data type in this block. You can set it to:

- A rule that inherits a data type, for example, **Inherit: Same as accumulator**
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

# Array-Vector Add

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

## Minimum

Specify the minimum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Maximum

Specify the maximum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## Supported Data Types

Port	Supported Data Types
A	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
V	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

Port	Supported Data Types
	<ul style="list-style-type: none"><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>

## See Also

Array-Vector Divide	DSP System Toolbox
Array-Vector Multiply	DSP System Toolbox
Array-Vector Subtract	DSP System Toolbox

# Array-Vector Divide

---


## Purpose

Divide array by vector along specified dimension

## Library

Math Functions / Matrices and Linear Algebra / Matrix Operations  
dspmtx3

## Description



The Array-Vector Divide block divides the values in the specified dimension of the  $N$ -dimensional input array  $A$  by the values in the input vector  $V$ .

The length of the input  $V$  must be the same as the length of the specified dimension of  $A$ . The Array-Vector Divide block divides each element of  $V$  by the corresponding element along that dimension of  $A$ .

Consider a 3-dimensional  $M$ -by- $N$ -by- $P$  input array  $A(i,j,k)$  and a  $N$ -by-1 input vector  $V$ . When the **Divide along dimension** parameter is set to 2, the output of the block  $Y(i,j,k)$  is

$$Y(i,j,k) = \frac{A(i,j,k)}{V(j)}$$

where

$$1 \leq i \leq M$$


$$1 \leq j \leq N$$

$$1 \leq k \leq P$$

The output of the Array-Vector Divide block is the same size as the input array,  $A$ . This block accepts real and complex floating-point and fixed-point input arrays, and real floating-point and fixed-point input vectors.

## Fixed-Point Data Types

The following diagram shows the data types used within the Array-Vector Divide block for fixed-point signals.




When you specify the vector  $V$  on the **Main** pane of the block mask, you must specify the data type and scaling properties of its elements in the **Vector (V)** parameter on the **Data Types** tab. When the vector comes in through the block port, its elements inherit their data type and scaling from the driving block.

You can set the vector and output data types in the block dialog as discussed below.

## Dialog Box

The **Main** pane of the Array-Vector Divide block dialog appears as follows.

# Array-Vector Divide



## **Divide along dimension**

Specify the dimension along which to divide the input array  $A$  by the elements of vector  $V$ .


## **Vector (V) source**

Specify the source of the vector,  $V$ . The vector can come from the Input port or from a Dialog parameter.

## Vector (V)

Specify the vector,  $V$ . This parameter is visible only when you select Dialog parameter for the **Vector (V) source** parameter.

The **Data Types** pane of the Array-Vector Divide block dialog appears as follows.



# Array-Vector Divide

---

---

**Note** Floating-point inheritance takes precedence over the data type settings defined on this pane. When inputs are floating point, the block ignores these settings, and all internal data types are floating point.

---

## **Rounding mode**

Select the rounding mode for fixed-point operations.

## **Overflow mode**

Select the overflow mode for fixed-point operations.

## **Vector (V)**

Use this parameter to specify the word and fraction lengths for the elements of the vector, *V*. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Same word length as input`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

---


**Note** The **Vector (V)** parameter on the **Data Types** pane is only visible when you select **Dialog** parameter for the **Vector (V)** **source** parameter on the **Main** pane of the block mask. When the vector comes in through the block’s input port, the data type and scaling of its elements are inherited from the driving block.

---

## Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-46 for illustrations depicting the use of the output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as first input`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

## Minimum

Specify the minimum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Maximum

Specify the maximum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

# Array-Vector Divide

---

## Supported Data Types

Port	Supported Data Types
A	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
V	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>

## See Also

Array-Vector Add	DSP System Toolbox
Array-Vector Multiply	DSP System Toolbox
Array-Vector Subtract	DSP System Toolbox


## Purpose

Multiply array by vector along specified dimension

## Library

Math Functions / Matrices and Linear Algebra / Matrix Operations  
dspmtx3

## Description



The Array-Vector Multiply block multiplies the values in the specified dimension of the  $N$ -dimensional input array  $A$  by the values in the input vector  $V$ .

The length of the input  $V$  must be the same as the length of the specified dimension of  $A$ . The Array-Vector Multiply block multiplies each element of  $V$  by the corresponding element along that dimension of  $A$ .

Consider a 3-dimensional  $M$ -by- $N$ -by- $P$  input array  $A(i,j,k)$  and a  $N$ -by-1 input vector  $V$ . When the **Multiply along dimension** parameter is set to 2, the output of the block  $Y(i,j,k)$  is

$$Y(i,j,k) = A(i,j,k) * V(j)$$

where

$$1 \leq i \leq M$$

$$1 \leq j \leq N$$

$$1 \leq k \leq P$$


The output of the Array-Vector Multiply block is the same size as the input array,  $A$ . This block accepts real and complex floating-point and fixed-point inputs.

## Fixed-Point Data Types

The following diagram shows the data types used within the Array-Vector Multiply block for fixed-point signals.

# Array-Vector Multiply

---




When you specify the vector  $V$  on the **Main** pane of the block mask, you must specify the data type and scaling properties of its elements in the **Vector (V)** parameter on the **Data Types** tab. When the vector comes in through the block port, its elements inherit their data type and scaling from the driving block.

The output of the multiplier is in the product output data type when at least one of the inputs to the multiplier is real. When both of the inputs to the multiplier are complex, the result of the multiplication is in the accumulator data type. For details on the complex multiplication performed, see “Multiplication Data Types”.

You can set the vector, accumulator, product output, and output data types in the block dialog as discussed below.

## Dialog Box

The **Main** pane of the Array-Vector Multiply block dialog appears as follows.



### **Multiply along dimension**

Specify the dimension along which to multiply the input array  $A$  by the elements of vector  $V$ .

# Array-Vector Multiply

---

## **Vector (V) source**

Specify the source of the vector,  $V$ . The vector can come from the Input port or from a Dialog parameter.

## **Vector (V)**

Specify the vector,  $V$ . This parameter is visible only when you select Dialog parameter for the **Vector (V) source** parameter.

The **Data Types** pane of the Array-Vector Multiply block dialog appears as follows.

# Array-Vector Multiply

**Function Block Parameters: Array-Vector Multiply**

Array-Vector Multiply

Multiply the input array  $A$  by the elements of vector  $V$  along the specified dimension. In the two-dimensional case, this is equivalent to multiplying a full matrix ( $A$ ) by a diagonal ( $V$ ). Note that unoriented input signals are treated as oriented column vectors. The output of this block is always oriented.

When you specify the vector  $V$  on the block dialog and the fixed-point data type mode is set to "Specify word length," the fixed-point scaling is automatically set for you. In these cases, the scaling is set to the best possible precision given the real-world values and word length of  $V$ . This is equivalent to the "Best Precision: Matrix-wise" scaling option used in some fixed-point Simulink blocks.

Main | **Data Types**

Fixed-point operational parameters

Rounding mode:  Overflow mode:

Floating-point inheritance takes precedence over the settings in the 'Data Type' column below. When the block input is floating point, all block data types match the input. In addition, fixed-point accumulator attributes only apply when fixed-point block inputs are complex.

	Data Type	Assistant	Minimum	Maximum
Product output:	<input type="text" value="Inherit: Inherit via internal rule"/>	<input type="text" value="&gt;&gt;"/>		
Accumulator:	<input type="text" value="Inherit: Inherit via internal rule"/>	<input type="text" value="&gt;&gt;"/>		
Output:	<input type="text" value="Inherit: Same as product output"/>	<input type="text" value="&gt;&gt;"/>	<input type="text" value=""/>	<input type="text" value=""/>

Lock data type settings against changes by the fixed-point tools

? OK Cancel Help Apply

# Array-Vector Multiply

---

---

**Note** Floating-point inheritance takes precedence over the data type settings defined on this pane. When inputs are floating point, the block ignores these settings, and all internal data types are floating point.

---

## **Rounding mode**

Select the rounding mode for fixed-point operations.

## **Overflow mode**

Select the overflow mode for fixed-point operations.

## **Vector (V)**

Use this parameter to specify the word and fraction lengths for the elements of the vector,  $V$ . You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Same word length as input`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

---

**Note** The **Vector (V)** parameter on the **Data Types** pane is only visible when you select **Dialog** parameter for the **Vector (V)** **source** parameter on the **Main** pane of the block mask. When the vector comes in through the block’s input port, the data type and scaling of its elements are inherited from the driving block.

---

## Product output data type

Specify the product output data type. See “Fixed-Point Data Types” on page 2-53 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Accumulator data type

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-53 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

# Array-Vector Multiply

---

## Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-53 for illustrations depicting the use of the output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as product output`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

## Minimum

Specify the minimum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Maximum

Specify the maximum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## Supported Data Types

Port	Supported Data Types
A	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
V	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>

## See Also

Array-Vector Add	DSP System Toolbox
Array-Vector Divide	DSP System Toolbox
Array-Vector Subtract	DSP System Toolbox

# Array-Vector Subtract

---


## Purpose

Subtract vector from array along specified dimension

## Library

Math Functions / Matrices and Linear Algebra / Matrix Operations  
dspmtx3

## Description



The Array-Vector Subtract block subtracts the values in the input vector  $V$  from the values in the specified dimension of the  $N$ -dimensional input array  $A$ .

The length of the input  $V$  must be the same as the length of the specified dimension of  $A$ . The Array-Vector Subtract block subtracts each element of  $V$  from the corresponding element along that dimension of  $A$ .

Consider a 3-dimensional  $M$ -by- $N$ -by- $P$  input array  $A(i,j,k)$  and a  $N$ -by-1 input vector  $V$ . When the **Subtract along dimension** parameter is set to 2, the output of the block  $Y(i,j,k)$  is

$$Y(i,j,k) = A(i,j,k) - V(j)$$

where

$$1 \leq i \leq M$$


$$1 \leq j \leq N$$

$$1 \leq k \leq P$$

The output of the Array-Vector Subtract block is the same size as the input array,  $A$ . This block accepts real and complex floating-point and fixed-point inputs.

## Fixed-Point Data Types

The following diagram shows the data types used within the Array-Vector Subtract block for fixed-point signals.



When you specify the vector  $V$  on the **Main** pane of the block mask, you must specify the data type and scaling properties of its elements in the **Vector (V)** parameter on the **Data Types** tab. When the vector comes in through the block port, its elements inherit their data type and scaling from the driving block.


The output of the subtractor is in the accumulator data type.

You can set the vector, accumulator, and output data types in the block dialog as discussed below.

## Dialog Box

The **Main** pane of the Array-Vector Subtract block dialog appears as follows.

# Array-Vector Subtract



## Subtract along dimension

Specify the dimension along which to subtract the elements of vector  $V$  from the input array  $A$ .

**Vector (V) source**


Specify the source of the vector,  $V$ . The vector can come from the Input port or from a Dialog parameter.

**Vector (V)**

Specify the vector,  $V$ . This parameter is visible only when you select Dialog parameter for the **Vector (V) source** parameter.

The **Data Types** pane of the Array-Vector Subtract block dialog appears as follows.

# Array-Vector Subtract



**Note** Floating-point inheritance takes precedence over the data type settings defined on this pane. When inputs are floating point, the block ignores these settings, and all internal data types are floating point.

## Rounding mode

Select the rounding mode for fixed-point operations.

---

**Note** The **Rounding mode** and **Overflow mode** settings have no effect on numerical results when both of the following conditions exist:

- **Accumulator data type** is **Inherit**: Inherit via internal rule
  - **Output data type** is **Inherit**: Same as accumulator
- With these data type settings, the block is effectively operating in full precision mode.
- 

## Overflow mode

Select the overflow mode for fixed-point operations.

## Vector (V)

Use this parameter to specify the word and fraction lengths for the elements of the vector, *V*. You can set this parameter to:

- A rule that inherits a data type, for example, **Inherit: Same word length as input**
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

# Array-Vector Subtract

---

---

**Note** The **Vector (V)** parameter on the **Data Types** pane is only visible when you select **Dialog** parameter for the **Vector (V) source** parameter on the **Main** pane of the block mask. When the vector comes in through the block's input port, the data type and scaling of its elements are inherited from the driving block.

---

## Accumulator data type

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-62 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, **Inherit: Inherit via internal rule**
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User's Guide* for more information.

## Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-62 for illustrations depicting the use of the output data type in this block. You can set it to:

- A rule that inherits a data type, for example, **Inherit: Same as accumulator**
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

## Minimum

Specify the minimum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Maximum

Specify the maximum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## Supported Data Types

Port	Supported Data Types
A	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
V	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

# Array-Vector Subtract

---

Port	Supported Data Types
	<ul style="list-style-type: none"><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>

## See Also

Array-Vector Add	DSP System Toolbox
Array-Vector Divide	DSP System Toolbox
Array-Vector Multiply	DSP System Toolbox

**Purpose** Design audio weighting filter


**Library** Filtering / Filter Designs  
dspfdesign

**Description** This block brings the filter design capabilities of the `filterbuilder` function to the Simulink environment.



**Dialog Box** See “Audio Weighting Filter Design Dialog Box — Main Pane” on page 7-672 for more information about the parameters of this block. The **Data Types** and **Code** panes are not available for blocks in the DSP System Toolbox Filter Designs library.

# Audio Weighting Filter



## View Filter Response

This button opens the Filter Visualization Tool (`fvtool`) from the Signal Processing Toolbox product. You can use the tool to display:

- Magnitude response, phase response, and group delay in the frequency domain.
- Impulse response and step response in the time domain.
- Pole-zero information.

The tool also helps you evaluate filter performance by providing information about filter order, stability, and phase linearity. For more information on FVTool, see the Signal Processing Toolbox documentation.

## Filter Specifications

In this group, you specify your filter format, such as the impulse response and the filter order.

### Weighting type

The weighting type defines the frequency response of the filter.

The valid weighting types for this filter are A, C, C-message, ITU-R 468 4, and ITU-T 0.41. For definitions of the available weighting types, see the `fdesign.audioweighting` reference page.

### Class

The filter class describes the frequency-dependent tolerances specified in the relevant standards [1], [2]. There are two possible class values: 1 and 2. Class 1 weighting filters have stricter tolerances than class 2 filters. The filter class value does not affect the design. The class value is only used to provide a specification mask in `fvtool` for the analysis of the filter design. The default value of this parameter is 1.

The filter class is only applicable for A weighting and C weighting filters.

# Audio Weighting Filter

---

## **Impulse response**

Specify the impulse response type as one of **IIR** or **FIR**. For **A**, **C**, **C-message**, and **ITU-R 468–4** filter, **IIR** is the only option. For a **ITU-T 0.41** weighting filter, **FIR** is the only option.

## **Frequency units**

Specify the frequency units as **Hertz (Hz)**, **kilohertz (kHz)**, **megahertz (MHz)**, or **gigahertz (GHz)**. Normalized frequency designs are not supported for audio weighting filters. The default value of this parameter is **Hz**.

## **Input Fs**

Specify the input sampling frequency. The units correspond to the setting of the **Frequency units** parameter.

## **Algorithm**

### **Design Method**

Valid design methods depend on the weighting type. For type **A** and **C** weighting filters, the only valid design type is **ANSI S1.42**. This is an **IIR** design method that follows ANSI standard **S1.42–2001**. For a **C** message filter, the only valid design method is **Bell 41009**, which is an **IIR** design method following the Bell System Technical Reference **PUB 41009**. For a **ITU-R 468–4** weighting filter, you can design an **IIR** or **FIR** filter. If you choose an **IIR** design, the design method is **IIR least p-norm**. If you choose an **FIR** design, the design method choices are **Equiripple** or **Frequency Sampling**. For an **ITU-T 0.41** weighting filter, the available **FIR** design methods are **Equiripple** or **Frequency Sampling**.

### **Scale SOS filter coefficients to reduce chance of overflow**

Selecting this parameter directs the design to scale the filter coefficients to reduce the chances that the inputs or calculations in the filter overflow and exceed the representable range of the filter. Clearing this option removes the scaling. This parameter applies only to **IIR** filters.

## Filter Implementation

### Structure

For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter. For audio weighting IIR filter designs, you can choose direct form I or II biquad (SOS). You can also choose to implement these structures in transposed form.

For FIR designs, you can choose a direct form, direct-form transposed, direct-form symmetric, or direct-form asymmetric structure.

### Use basic elements to enable filter customization

Select this check box to implement the filter as a subsystem of basic Simulink blocks. Clear the check box to implement the filter as a high-level subsystem. By default, this check box is cleared.

The high-level implementation provides better compatibility across various filter structures, especially filters that would contain algebraic loops when constructed using basic elements. On the other hand, using basic elements enables the following optimization parameters:

- **Optimize for zero gains** — Terminate chains that contain Gain blocks with a gain of zero.
- **Optimize for unit gains** — Remove Gain blocks that scale by a factor of one.
- **Optimize for delay chains** — Substitute delay chains made up of  $n$  unit delays with a single delay by  $n$ .
- **Optimize for negative gains** — Use subtraction in Sum blocks instead of negative gains in Gain blocks.

### Optimize for unit-scale values

Select this check box to scale unit gains between sections in SOS filters. This parameter is available only for SOS filters.

# Audio Weighting Filter

---

## Input processing

Specify how the block should process the input. The available options may vary depending on the settings of the **Filter Structure** and **Use basic elements for filter customization** parameters. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

For more information about sample- and frame-based processing, see “Sample- and Frame-Based Concepts”.

## Use symbolic names for coefficients

Select this check box to enable the specification of coefficients using MATLAB variables. The available coefficient names differ depending on the filter structure. Using symbolic names allows tuning of filter coefficients in generated code. By default, this check box is cleared.

## References

- [1] *American National Standard Design Response of Weighting Networks for Acoustical Measurements*, ANSI S1.42-2001, Acoustical Society of America, New York, NY, 2001.
- [2] *Electroacoustics Sound Level Meters Part 1: Specifications*, IEC 61672-1, First Edition 2002-05.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

## See Also

`fdesign.audioweighting` | `filterbuilder` | `fvtool`

## How To

- [Audio Weighting Filters Example](#)

# Autocorrelation

---

**Purpose** Autocorrelation of vector or matrix input

**Library** Statistics  
dspstat3

## Description



The Autocorrelation block computes the autocorrelation along the first dimension of an N-D input array. The block accepts fixed-point signals when you set the **Computation domain** to Time.

When the input to the Autocorrelation block is an  $M$ -by- $N$  matrix  $u$ , the output,  $y$ , is an  $(l+1)$ -by- $N$  matrix whose  $j$ th column has elements

$$y_{i,j} = \sum_{k=0}^{M-l-1} u_{k,j}^* u_{(k+i),j} \quad 0 \leq i \leq l$$


where  $*$  denotes the complex conjugate, and  $l$  represents the maximum lag.  $y_{0,j}$  is the zero-lag element in the  $j$ th column. When you select **Compute all non-negative lags**,  $l=M-1$ . Otherwise,  $l$  is the nonnegative integer value you specify for the **Maximum non-negative lag (less than input length)** parameter.

Similarly, for an N-D input array, the block outputs an N-D array, where the size of the first dimension is  $l+1$ , and the sizes of all other dimensions match those of the input array. For example, when the input is an  $M$ -by- $N$ -by- $P$  array, the Autocorrelation block outputs an  $(l+1)$ -by- $N$ -by- $P$  array.


### Fixed-Point Data Types

The following diagrams show the data types used within the Autocorrelation block for fixed-point signals (time domain only).

## Signal flow when Scaling is "None"



## Signal flow when Scaling is other than "None"



# Autocorrelation


---

You can set the product output, accumulator, and output data types on the **Data Types** pane of the block dialog as discussed in the next section.

The output of the multiplier is in the product output data type when the input is real. When the input is complex, the result of the multiplication is in the accumulator data type. For details on the complex multiplication performed, see “Multiplication Data Types”.

## **Dialog Box**

The **Main** pane of the Autocorrelation block dialog appears as follows.



### Compute all non-negative lags

When you select this check box, the block computes the autocorrelation over all nonnegative lags in the range  $[0, \text{length}(\text{input}) - 1]$ . When you clear the check box, the block computes the autocorrelation using lags in the range  $[0, l]$ , where  $l$  is the value you specify for the **Maximum non-negative lag (less than input length)** parameter.

# Autocorrelation

---

## Maximum non-negative lag (less than input length)

Specify the maximum positive lag,  $l$ , for the autocorrelation. This parameter is available only when you clear the **Compute all non-negative lags** check box.

## Scaling

This parameter controls the scaling that the block applies to the output. The following options are available:

- **None** — Generates the raw autocorrelation  $y_{i,j}$  without normalization.
- **Biased** — Generates the biased estimate of the autocorrelation.

$$y_{i,j}^{biased} = \frac{y_{i,j}}{M}$$

- **Unbiased** — Generates the unbiased estimate of the autocorrelation.

$$y_{i,j}^{unbiased} = \frac{y_{i,j}}{M-i}$$

- **Unity at zero-lag** — Normalizes the estimate of the autocorrelation for each channel so that the zero-lag sum is identically 1.

$$y_{0,j} = 1$$


## Computation domain

This parameter sets the domain in which the block computes convolutions to one of the following settings:

- **Time** — Computes in the time domain, which minimizes memory use
- **Frequency** — Computes in the frequency domain, which might require fewer computations than computing in the time domain, depending on the input length

**Note** This parameter must be set to Time for fixed-point signals.

The **Data Types** pane of the Autocorrelation block dialog appears as follows.



# Autocorrelation

---

---

**Note** Fixed-point signals are only supported for the time domain. To use the parameters on this pane, make sure Time is selected for the **Computation domain** parameter on the **Main** pane.

---

## Rounding mode

Select the rounding mode for fixed-point operations.

---

**Note** The **Rounding mode** and **Overflow mode** settings have no effect on numerical results when all the following conditions exist:

- **Product output data type** is Inherit: Inherit via internal rule
- **Accumulator data type** is Inherit: Inherit via internal rule
- **Output data type** is Inherit: Same as accumulator

With these data type settings, the block is effectively operating in full precision mode.

---

## Overflow mode

Select the overflow mode for fixed-point operations.

## Product output data type

Specify the product output data type. See “Fixed-Point Data Types” on page 2-78 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set it to:

- A rule that inherits a data type, for example, Inherit: Inherit via internal rule
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Accumulator data type

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-78 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-78 for illustrations depicting the use of the output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as accumulator`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

# Autocorrelation

---

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

## Minimum

Specify the minimum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Maximum

Specify the maximum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>

Port	Supported Data Types
	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

## See Also

Correlation

DSP System Toolbox

`xcorr`

Signal Processing Toolbox



# Autocorrelation LPC

**Purpose** Determine coefficients of Nth-order forward linear predictors

**Library** Estimation / Linear Prediction

dsp1p

## Description



The Autocorrelation LPC block determines the coefficients of an *N-step forward linear predictor* for the time-series in each length-*M* input channel, *u*, by minimizing the prediction error in the least squares sense. A linear predictor is an FIR filter that predicts the next value in a sequence from the present and past inputs. This technique has applications in filter design, speech coding, spectral analysis, and system identification.

The Autocorrelation LPC block can output the prediction error for each channel as polynomial coefficients, reflection coefficients, or both. It can also output the prediction error power for each channel. The input *u* can be a scalar, unoriented vector, column vector, sample-based row vector, or a matrix. Frame-based row vectors are not valid inputs. The block treats all *M*-by-*N* matrix inputs as *N* channels of length *M*.

When you select **Inherit prediction order from input dimensions**, the prediction order, *N*, is inherited from the input dimensions. Otherwise, you can use the **Prediction order** parameter to specify the value of *N*. Note that *N* must be a scalar with a value less than the length of the input channels or the block produces an error.

When **Output(s)** is set to A, port A is enabled. For each channel, port A outputs an (*N*+1)-by-1 column vector,  $\alpha = [1 \ a_2 \ a_3 \ \dots \ a_{N+1}]^T$ , containing the coefficients of an Nth-order moving average (MA) linear process that predicts the next value,  $\hat{u}_{M+1}$ , in the input time-series.

$$\hat{u}_{M+1} = -(a_2 u_M) - (a_3 u_{M-1}) - \dots - (a_{N+1} u_{M-N+1})$$

When **Output(s)** is set to K, port K is enabled. For each channel, port K outputs a length-*N* column vector whose elements are the prediction error reflection coefficients. When **Output(s)** is set to A and K, both

port A and K are enabled, and each port outputs its respective set of prediction coefficients for each channel.

When you select **Output prediction error power (P)**, port P is enabled. The prediction error power is output at port P as a vector whose length is the number of input channels.

## Algorithm

The Autocorrelation LPC block computes the least squares solution to

$$\min_{i \in \mathcal{R}^n} \|U\tilde{a} - b\|$$

where  $\|\cdot\|$  indicates the 2-norm and

$$U = \begin{bmatrix} u_1 & 0 & \cdots & 0 \\ u_2 & u_1 & \ddots & \vdots \\ \vdots & u_2 & \ddots & 0 \\ \vdots & \vdots & \ddots & u_1 \\ \vdots & \vdots & \vdots & u_2 \\ \vdots & \vdots & \vdots & \vdots \\ u_M & \vdots & \vdots & \vdots \\ 0 & \ddots & \vdots & \vdots \\ \vdots & \ddots & \ddots & \vdots \\ 0 & \cdots & 0 & u_M \end{bmatrix}, \tilde{a} = \begin{bmatrix} a_2 \\ \vdots \\ a_n + 1 \end{bmatrix}, b = \begin{bmatrix} u_2 \\ u_3 \\ \vdots \\ u_M \\ 0 \\ \vdots \\ 0 \end{bmatrix}$$

Solving the least squares problem via the normal equations

$$U^*U\tilde{a} = U^*b$$

leads to the system of equations


# Autocorrelation LPC

---

$$\begin{bmatrix} r_1 & r_2^* & \cdots & r_n^* \\ r_2 & r_1 & \ddots & \vdots \\ \vdots & \ddots & \ddots & r_2^* \\ r_n & \cdots & r_2 & r_1 \end{bmatrix} \begin{bmatrix} a_2 \\ a_3 \\ \vdots \\ a_{n+1} \end{bmatrix} = \begin{bmatrix} -r_2 \\ -r_3 \\ \vdots \\ -r_{n+1} \end{bmatrix}$$

where  $r = [r_1 \ r_2 \ r_3 \ \dots \ r_{n+1}]^T$  is an autocorrelation estimate for  $u$  computed using the Autocorrelation block, and \* indicates the complex conjugate transpose. The normal equations are solved in  $O(n^2)$  operations by the Levinson-Durbin block.

Note that the solution to the LPC problem is very closely related to the Yule-Walker AR method of spectral estimation. In that context, the normal equations above are referred to as the Yule-Walker AR equations.



## Dialog Box

### Output(s)

The type of prediction coefficients output by the block. The block can output polynomial coefficients (A), reflection coefficients (K), or both (A and K).

### Output prediction error power (P)

When selected, enables port P, which outputs the output prediction error power.

### Inherit prediction order from input dimensions

When selected, the block inherits the prediction order from the input dimensions.

# Autocorrelation LPC

---

## Prediction order (N)

Specify the prediction order,  $N$ , which must be a scalar. This parameter is disabled when you select the **Inherit prediction order from input dimensions** parameter.

## References

Haykin, S. *Adaptive Filter Theory*. 3rd ed. Englewood Cliffs, NJ: Prentice Hall, 1996.

Ljung, L. *System Identification: Theory for the User*. Englewood Cliffs, NJ: Prentice Hall, 1987. Pgs. 278-280.

Proakis, J. and D. Manolakis. *Digital Signal Processing*. 3rd ed. Englewood Cliffs, NJ: Prentice-Hall, 1996.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point

## See Also

Autocorrelation	DSP System Toolbox
Levinson-Durbin	DSP System Toolbox
Yule-Walker Method	DSP System Toolbox
lpc	Signal Processing Toolbox


## Purpose

Solve  $UX=B$  for  $X$  when  $U$  is upper triangular matrix

## Library

Math Functions / Matrices and Linear Algebra / Linear System Solvers  
dspsolvers

## Description



The Backward Substitution block solves the linear system  $UX=B$  by simple backward substitution of variables, where:

- $U$  is the upper triangular  $M$ -by- $M$  matrix input to the U port.
- $B$  is the  $M$ -by- $N$  matrix input to the B port.

The  $M$ -by- $N$  output matrix  $X$  is the solution of the equations. The block does not check the rank of the inputs.

The block uses only the elements in the *upper triangle* of input  $U$  and ignores the lower elements. When you select the **Input U is unit-upper triangular** check box, the block assumes the elements on the diagonal of  $U$  are 1s. This is useful when matrix  $U$  is the result of another operation, such as an LDL decomposition, that uses the diagonal elements to represent the  $D$  matrix.


The block treats a length- $M$  vector input at port B as an  $M$ -by-1 matrix.

## Fixed-Point Data Types


The following diagram shows the data types used within the Backward Substitution block for fixed-point signals.

# Backward Substitution

When input  $U$  is not unit-upper triangular:



When input U is unit-upper triangular:




You can set the product output, accumulator, and output data types in the block dialog as discussed in the following section.

The output of the multiplier is in the product output data type when the input is real. When the input is complex, the result of the multiplication is in the accumulator data type. For details on the complex multiplication performed, see “Multiplication Data Types”.

## Dialog Box

The **Main** pane of the Backward Substitution block dialog box appears as follows.

# Backward Substitution



## Input $U$ is unit-upper triangular

Select this check box only when all elements on the diagonal of  $U$  have a value of 1. When you do so, the block optimizes its behavior by skipping an unnecessary divide operation.

Do not select this check box if there are any elements on the diagonal of  $U$  that do not have a value of 1. When you clear the **Input  $U$  is unit-upper triangular** check box, the block always performs the necessary divide operation.

## **Diagonal of complex input U is real**

Select to optimize simulation speed when the diagonal elements of complex input U are real. This parameter is only visible when **Input U is unit-upper triangular** is not selected.


---

**Note** When U is a complex fixed-point signal, you must select either **Input U is unit-upper triangular** or **Diagonal of complex input U is real**. In such a case, any imaginary part of the diagonal of U is ignored.

---

The **Data Types** pane of the Backward Substitution block dialog appears as follows.

# Backward Substitution



---

**Note** Floating-point inheritance takes precedence over the data type settings defined on this pane. When inputs are floating point, the block ignores these settings, and all internal data types are floating point.

---

## Rounding mode

Select the rounding mode for fixed-point operations.

## Overflow mode

Select the overflow mode for fixed-point operations.

## Product output data type

Specify the product output data type. See “Fixed-Point Data Types” on page 2-93 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Accumulator data type

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-93 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

# Backward Substitution

---

## Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-93 for illustrations depicting the use of the output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as first input`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

## Minimum

Specify the minimum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Maximum

Specify the maximum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## Supported Data Types

Port	Supported Data Types
U	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
B	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
X	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>

## See Also

Cholesky Solver	DSP System Toolbox
Forward Substitution	DSP System Toolbox
LDL Solver	DSP System Toolbox
Levinson-Durbin	DSP System Toolbox
LU Solver	DSP System Toolbox
QR Solver	DSP System Toolbox

See “Linear System Solvers” for related information.

# Bandpass Filter

---

**Purpose** Design bandpass filter

**Library** Filtering / Filter Designs  
dspfdesign

**Description** This block brings the filter design capabilities of the `filterbuilder` function to the Simulink environment.



**Dialog Box** See “Bandpass Filter Design Dialog Box — Main Pane” on page 7-675 for more information about the parameters of this block. The **Data Types** and **Code Generation** panes are not available for blocks in the DSP System Toolbox Filter Designs library.

# Bandpass Filter

Function Block Parameters: Bandpass Filter

Bandpass Filter  
Design a bandpass filter.

[View Filter Response](#)

Filter specifications

Impulse response: FIR

Order mode: Minimum

Filter Type: Single-rate

Frequency specifications

Frequency units: Normalized (0 to 1) Input Fs: 2

Fstop1: .35 Fpass1: .45

Fpass2: .55 Fstop2: .65

Magnitude specifications

Magnitude units: dB

Astop1: 60 Apass: 1

Astop2: 60

Algorithm

Design method: Equiripple

► Design options

Filter Implementation

Structure: Direct-form symmetric FIR

Use basic elements to enable filter customization

Input processing: Columns as channels (frame based)

Use symbolic names for coefficients

# Bandpass Filter

---

- Magnitude response, phase response, and group delay in the frequency domain.
- Impulse response and step response in the time domain.
- Pole-zero information.

The tool also helps you evaluate filter performance by providing information about filter order, stability, and phase linearity. For more information on FVTool, see the Signal Processing Toolbox documentation.

## Filter Specifications

In this group, you specify your filter format, such as the impulse response and the filter order.

### Impulse response

Select either **FIR** or **IIR** from the drop-down list. **FIR** is the default. When you choose an impulse response, the design methods and structures you can use to implement your filter change accordingly.

---

**Note** The design methods and structures for **FIR** filters are not the same as the methods and structures for **IIR** filters.

---

### Order mode

Select **Minimum** (the default) or **Specify**. Selecting **Specify** enables the **Order** option so you can enter the filter order. When you set the **Impulse response** to **IIR**, you can specify different numerator and denominator orders. To specify a different denominator order, you must select the **Denominator order** check box.

### Order

Enter the filter order. This option is enabled only if you set the **Order mode** to **Specify**.

## Denominator order

Select this check box to specify a different denominator order. This option is enabled only if you set the **Impulse response** to IIR and the **Order mode** to Specify.

## Filter type

Select Single-rate, Decimator, Interpolator, or Sample-rate converter. Your choice determines the type of filter as well as the design methods and structures that are available to implement your filter. By default, the block specifies a single-rate filter.

- Selecting Decimator or Interpolator activates the **Decimation Factor** or the **Interpolation Factor** options respectively.
- Selecting Sample-rate converter activates both factors.

## Decimation Factor

Enter the decimation factor. This option is enabled only if the **Filter type** is set to Decimator or Sample-rate converter. The default value is 2.


## Interpolation Factor

Enter the interpolation factor. This option is enabled only if the **Filter type** is set to Interpolator or Sample-rate converter. The default value is 2.

## Frequency Specifications

The parameters in this group allow you to specify your filter response curve. Graphically, the filter specifications look similar to those shown in the following figure.

# Bandpass Filter



In the figure, regions between specification values such as  $F_{stop1}$  and  $F_{pass1}$  represent transition regions where the filter response is not constrained.

## Frequency constraints

When **Order mode** is **Specify**, select the filter features that the block uses to define the frequency response characteristics. The list contains the following options, when available for the filter specifications.

- **Passband and stopband edges** — Define the filter by specifying the frequencies for the edges for the stop- and passbands.
- **Passband edges** — For IIR filters, define the filter by specifying frequencies for the edges of the passband.
- **Stopband edges** — For IIR filters, define the filter by specifying frequencies for the edges of the stopbands.
- **3 dB points** — For IIR filters, define the filter response by specifying the locations of the 3 dB points. The 3 dB point is the frequency for the point three decibels below the passband value.
- **3 dB points and passband width** — For IIR filters, define the filter by specifying frequencies for the 3 dB points in the filter response and the width of the passband.

- **3 dB points and stopband widths** — For IIR filters, define the filter by specifying frequencies for the 3 dB points in the filter response and the width of the stopband.
- **6 dB points** — For FIR filters, define the filter response by specifying the locations of the 6 dB points. The 6 dB point is the frequency for the point six decibels below the passband value.

## **Frequency units**

Use this parameter to specify whether your frequency settings are normalized or in absolute frequency. Select **Normalized (0 1)** to enter frequencies in normalized form. This behavior is the default. To enter frequencies in absolute values, select one of the frequency units from the drop-down list—Hz, kHz, MHz, or GHz. Selecting one of the unit options enables the **Input Fs** parameter.

## **Input Fs**

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter input. When you provide an input sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is available when you select one of the frequency options from the **Frequency units** list.

## **Fstop1**

Enter the frequency at the edge of the end of the first stopband. Specify the value in either normalized frequency units or the absolute units you select in **Frequency units**.

## **Fpass1**

Enter the frequency at the edge of the start of the passband. Specify the value in either normalized frequency units or the absolute units you selected for **Frequency units**.

## **Fpass2**

Enter the frequency at the edge of the end of the passband. Specify the value in either normalized frequency units or the absolute units you select in **Frequency units**.

# Bandpass Filter

---

## **Fstop2**

Enter the frequency at the edge of the start of the second stopband. Specify the value in either normalized frequency units or the absolute units you select in **Frequency units**.

## **F3dB1**

When **Frequency constraints** is 3 dB points, 3 dB points and passband width, or 3 dB points and stopband width, specify the lower-frequency 3 dB point.

## **F3dB2**

When **Frequency constraints** is 3 dB points, 3 dB points and passband width, or 3 dB points and stopband width, specify the higher-frequency 3 dB point.

## **F6dB1**

When **Frequency constraints** is 6 dB points, specify the lower-frequency 6 dB point.

## **F6dB2**

When **Frequency constraints** is 6 dB points, specify the higher-frequency 6 dB point.

## **Passband width**

When **Frequency constraints** is 3 dB points and passband width, specify the width of the passband, in units corresponding to the **Frequency units** parameter.

## **Stopband width**

When **Frequency constraints** is 3 dB points and stopband width, specify the width of the stopband, in units corresponding to the **Frequency units** parameter.

## **Magnitude Specifications**

Parameters in this group specify the filter response in the passbands and stopbands.

### **Magnitude constraints**

This option is only available when you specify the order of your filter design. The options for **Magnitude constraints** depend

on the value of the **Frequency constraints**. When you set the **Frequency constraints** parameter to Unconstrained, **Magnitude constraints** must also be set to Unconstrained. When **Frequency constraints** is not set to Unconstrained, some combination of the following options will be available for the **Magnitude constraints** parameter: Unconstrained, Passband ripple, Passband ripple and stopband attenuation or Stopband attenuation.

## **Magnitude units**

Specify the units for any parameter you provide in magnitude specifications.

From the drop-down list, select one of the following options:

- Linear — Specify the magnitude in linear units.
- dB — Specify the magnitude in dB (decibels). This is the default setting.
- Squared — Specify the magnitude in squared units.

## **Astop1**

Enter the filter attenuation in the first stopband in the units you choose for **Magnitude units**, either linear or decibels.

## **Apass**

Enter the filter ripple allowed in the passband in the units you choose for **Magnitude units**, either linear or decibels.

## **Astop2**

Enter the filter attenuation in the second stopband in the units you choose for **Magnitude units**, either linear or decibels.

## **Algorithm**

The parameters in this group allow you to specify the design method and structure of your filter.

# Bandpass Filter

---

## Design Method

Lists the design methods available for the frequency and magnitude specifications you entered. When you change the specifications for a filter, such as changing the impulse response, the methods available to design filters changes as well. The default IIR design method is usually Butterworth, and the default FIR method is Equiripple.

## Scale SOS filter coefficients to reduce chance of overflow

Selecting this parameter directs the design to scale the filter coefficients to reduce the chances that the inputs or calculations in the filter overflow and exceed the representable range of the filter. Clearing this option removes the scaling. This parameter applies only to IIR filters.

## Design Options

The options for each design are specific for each design method. This section does not present all of the available options for all designs and design methods. There are many more that you encounter as you select different design methods and filter specifications. The following options represent some of the most common ones available.

## Density factor

Density factor controls the density of the frequency grid over which the design method optimization evaluates your filter response function. The number of equally spaced points in the grid is the value you enter for **Density factor** times (filter order + 1).

Increasing the value creates a filter that more closely approximates an ideal equiripple filter but increases the time required to design the filter. The default value of 20 represents a reasonable trade between the accurate approximation to the ideal filter and the time to design the filter.

## Phase constraint

Specify the phase constraint of the filter as Linear, Maximum, or Minimum.

## Minimum order

When you select this parameter, the design method determines and design the minimum order filter to meet your specifications. Some filters do not provide this parameter. Select Any, Even, or Odd from the drop-down list to direct the design to be any minimum order, or minimum even order, or minimum odd order.

## Match Exactly

Specifies that the resulting filter design matches either the passband or stopband or both bands when you select passband or stopband or both from the drop-down list.

## Minimum order

When you select this parameter, the design method determines and design the minimum order filter to meet your specifications. Some filters do not provide this parameter. Select Any, Even, or Odd from the drop-down list to direct the design to be any minimum order, or minimum even order, or minimum odd order.

---

**Note** Generally, **Minimum order** designs are not available for IIR filters.

---

## Filter Implementation

### Structure

For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter. By default, FIR filters use direct-form structure, and IIR filters use direct-form II filters with SOS.

# Bandpass Filter

---

## Use basic elements to enable filter customization

Select this check box to implement the filter as a subsystem of basic Simulink blocks. Clear the check box to implement the filter as a high-level subsystem. By default, this check box is cleared.

The high-level implementation provides better compatibility across various filter structures, especially filters that would contain algebraic loops when constructed using basic elements. On the other hand, using basic elements enables the following optimization parameters:

- **Optimize for zero gains** — Terminate chains that contain Gain blocks with a gain of zero.
- **Optimize for unit gains** — Remove Gain blocks that scale by a factor of one.
- **Optimize for delay chains** — Substitute delay chains made up of  $n$  unit delays with a single delay by  $n$ .
- **Optimize for negative gains** — Use subtraction in Sum blocks instead of negative gains in Gain blocks.

## Optimize for unit-scale values

Select this check box to scale unit gains between sections in SOS filters. This parameter is available only for SOS filters.

## Input processing

Specify how the block should process the input. The available options may vary depending on the settings of the **Filter Structure** and **Use basic elements for filter customization** parameters. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The Inherited (this choice will be removed see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Rate options

When the **Filter type** parameter specifies a multirate filter, select the rate processing rule for the block from following options:

- **Enforce single-rate processing** — When you select this option, the block maintains the sample rate of the input.
- **Allow multirate processing** — When you select this option, the block adjusts the rate at the output to accommodate an increased or reduced number of samples. To select this option, you must set the **Input processing** parameter to **Elements as channels (sample based)**.

## Use symbolic names for coefficients

Select this check box to enable the specification of coefficients using MATLAB variables. The available coefficient names differ depending on the filter structure. Using symbolic names allows tuning of filter coefficients in generated code. By default, this check box is cleared.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

# Bandstop Filter

---

**Purpose** Design bandstop filter

**Library** Filtering / Filter Designs  
dspfdesign

**Description** This block brings the filter design capabilities of the `filterbuilder` function to the Simulink environment.



**Dialog Box** See “Bandstop Filter Design Dialog Box — Main Pane” on page 7-683 for more information about the parameters of this block. The **Data Types** and **Code Generation** panes are not available for blocks in the DSP System Toolbox Filter Designs library.

# Bandstop Filter

Function Block Parameters: Bandstop Filter

Bandstop Filter

Design a bandstop filter.

[View Filter Response](#)

Filter specifications

Impulse response: FIR

Order mode: Minimum

Filter Type: Single-rate

Frequency specifications

Frequency units: Normalized (0 to 1) Input Fs: 2

Fpass1: .35 Fstop1: .45

Fstop2: .55 Fpass2: .65

Magnitude specifications

Magnitude units: dB

Apass1: 1 Astop: 60

Apass2: 1

Algorithm

Design method: Equiripple

► Design options

Filter Implementation

Structure: Direct-form FIR

Use basic elements to enable filter customization

Input processing: Columns as channels (frame based)

Use symbolic names for coefficients

# Bandstop Filter

---

- Magnitude response, phase response, and group delay in the frequency domain.
- Impulse response and step response in the time domain.
- Pole-zero information.

The tool also helps you evaluate filter performance by providing information about filter order, stability, and phase linearity. For more information on FVTool, see the Signal Processing Toolbox documentation.

## Filter Specifications

In this group, you specify your filter format, such as the impulse response and the filter order.

### Impulse response

Select either **FIR** or **IIR** from the drop-down list. **FIR** is the default. When you choose an impulse response, the design methods and structures you can use to implement your filter change accordingly.

---

**Note** The design methods and structures for **FIR** filters are not the same as the methods and structures for **IIR** filters.

---

### Order mode

Select **Minimum** (the default) or **Specify**. Selecting **Specify** enables the **Order** option so you can enter the filter order. When you set the **Impulse response** to **IIR**, you can specify different numerator and denominator orders. To specify a different denominator order, you must select the **Denominator order** check box.

### Order

Enter the filter order. This option is enabled only if you set the **Order mode** to **Specify**.

## Denominator order

Select this check box to specify a different denominator order. This option is enabled only if you set the **Impulse response** to IIR and the **Order mode** to Specify.

## Filter type

Select Single-rate, Decimator, Interpolator, or Sample-rate converter. Your choice determines the type of filter as well as the design methods and structures that are available to implement your filter. By default, the block specifies a single-rate filter.

- Selecting Decimator or Interpolator activates the **Decimation Factor** or the **Interpolation Factor** options respectively.
- Selecting Sample-rate converter activates both factors.

## Decimation Factor

Enter the decimation factor. This option is enabled only if the **Filter type** is set to Decimator or Sample-rate converter. The default value is 2.


## Interpolation Factor

Enter the interpolation factor. This option is enabled only if the **Filter type** is set to Interpolator or Sample-rate converter. The default value is 2.

## Frequency Specifications

The parameters in this group allow you to specify your filter response curve. Graphically, the filter specifications look similar to those shown in the following figure.

# Bandstop Filter



## Frequency constraints

When **Order mode** is **Specify**, select the filter features that the block uses to define the frequency response characteristics. The list contains the following options, when available for the filter specifications.

- **Passband and stopband edges** — Define the filter by specifying the frequencies for the edges for the stop- and passbands.
- **Passband edges** — For IIR filters, define the filter by specifying frequencies for the edges of the passband.
- **Stopband edges** — For IIR filters, define the filter by specifying frequencies for the edges of the stopbands.
- **3 dB points** — For IIR filters, define the filter response by specifying the locations of the 3 dB points. The 3 dB point is the frequency for the point three decibels below the passband value.
- **3 dB points and passband width** — For IIR filters, define the filter by specifying frequencies for the 3 dB points in the filter response and the width of the passband.
- **3 dB points and stopband widths** — For IIR filters, define the filter by specifying frequencies for the 3 dB points in the filter response and the width of the stopband.

- **6 dB points** — For FIR filters, define the filter response by specifying the locations of the 6 dB points. The 6 dB point is the frequency for the point six decibels below the passband value.

## Frequency units

Use this parameter to specify whether your frequency settings are normalized or in absolute frequency. Select **Normalized (0 1)** to enter frequencies in normalized form. This behavior is the default. To enter frequencies in absolute values, select one of the frequency units from the drop-down list—Hz, kHz, MHz, or GHz. Selecting one of the unit options enables the **Input Fs** parameter.

## Input Fs

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter input. When you provide an input sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is available when you select one of the frequency options from the **Frequency units** list.

## Output Fs

When you design an interpolator, Fs represents the sampling frequency at the filter output rather than the filter input. This option is available only when you set **Filter type** is interpolator.

## Fpass1

Enter the frequency at the edge of the end of the first passband. Specify the value in either normalized frequency units or the absolute units you select in **Frequency units**.

## Fstop1

Enter the frequency at the edge of the start of the stopband. Specify the value in either normalized frequency units or the absolute units you select in **Frequency units**.

## Fstop2

Enter the frequency at the edge of the end of the stopband. Specify the value in either normalized frequency units or the absolute units you select in **Frequency units**.

# Bandstop Filter

---

## **Fpass2**

Enter the frequency at the edge of the start of the second passband. Specify the value in either normalized frequency units or the absolute units you select in **Frequency units**.

## **F3dB1**

When **Frequency constraints** is 3 dB points, 3 dB points and passband width, or 3 dB points and stopband width, specify the lower-frequency 3 dB point.

## **F3dB2**

When **Frequency constraints** is 3 dB points, 3 dB points and passband width, or 3 dB points and stopband width, specify the higher-frequency 3 dB point.

## **F6dB1**

When **Frequency constraints** is 6 dB points, specify the lower-frequency 6 dB point.

## **F6dB2**

When **Frequency constraints** is 6 dB points, specify the higher-frequency 6 dB point.

## **Passband width**

When **Frequency constraints** is 3 dB points and passband width, specify the width of the passband, in units corresponding to the **Frequency units** parameter.

## **Stopband width**

When **Frequency constraints** is 3 dB points and stopband width, specify the width of the stopband, in units corresponding to the **Frequency units** parameter.

## **Magnitude Specifications**

Parameters in this group specify the filter response in the passbands and stopbands.

### **Magnitude constraints**

This option is only available when you specify the order of your filter design. The options for **Magnitude constraints** depend on

the value of the **Frequency constraints**. Depending on the value of the **Frequency constraints** parameter, some combination of the following options will be available for the **Magnitude constraints** parameter: Unconstrained, Passband ripple and stopband attenuation, or Constrained bands.

## **Magnitude units**

Specify the units for any parameter you provide in magnitude specifications. From the drop-down list, select one of the following options:

- Linear — Specify the magnitude in linear units.
- dB — Specify the magnitude in decibels (default).
- Squared — Specify the magnitude in squared units.

## **Apass1**

Enter the filter ripple allowed in the first passband in the units you choose for **Magnitude units**, either linear or decibels.

## **Astop**

Enter the filter attenuation in the stopband in the units you choose for **Magnitude units**, either linear or decibels.

## **Apass2**

Enter the filter ripple allowed in the second passband in the units you choose for **Magnitude units**, either linear or decibels.

## **Algorithm**

The parameters in this group allow you to specify the design method and structure of your filter.

## **Design Method**

Lists the design methods available for the frequency and magnitude specifications you entered. When you change the specifications for a filter, such as changing the impulse response, the methods available to design filters changes as well. The default IIR design method is usually Butterworth, and the default FIR method is Equiripple.

# Bandstop Filter

---

## **Scale SOS filter coefficients to reduce chance of overflow**

Selecting this parameter directs the design to scale the filter coefficients to reduce the chances that the inputs or calculations in the filter overflow and exceed the representable range of the filter. Clearing this option removes the scaling. This parameter applies only to IIR filters.

## **Design Options**

The options for each design are specific for each design method. This section does not present all of the available options for all designs and design methods. There are many more that you encounter as you select different design methods and filter specifications. The following options represent some of the most common ones available.

### **Density factor**

Density factor controls the density of the frequency grid over which the design method optimization evaluates your filter response function. The number of equally spaced points in the grid is the value you enter for **Density factor** times (filter order + 1).

Increasing the value creates a filter that more closely approximates an ideal equiripple filter but increases the time required to design the filter. The default value of 20 represents a reasonable trade between the accurate approximation to the ideal filter and the time to design the filter.

### **Phase constraint**

Specify the phase constraint of the filter as **Linear**, **Maximum**, or **Minimum**.

### **Minimum order**

When you select this parameter, the design method determines and design the minimum order filter to meet your specifications. Some filters do not provide this parameter. Select **Any**, **Even**, or **Odd** from the drop-down list

to direct the design to be any minimum order, or minimum even order, or minimum odd order.

## Match Exactly

Specifies that the resulting filter design matches either the passband or stopband or both bands when you select passband or stopband or both from the drop-down list.

## Filter Implementation

### Structure

For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter. By default, FIR filters use direct-form structure, and IIR filters use direct-form II filters with SOS.

### Use basic elements to enable filter customization

Select this check box to implement the filter as a subsystem of basic Simulink blocks. Clear the check box to implement the filter as a high-level subsystem. By default, this check box is cleared.

The high-level implementation provides better compatibility across various filter structures, especially filters that would contain algebraic loops when constructed using basic elements. On the other hand, using basic elements enables the following optimization parameters:

- **Optimize for zero gains** — Terminate chains that contain Gain blocks with a gain of zero.
- **Optimize for unit gains** — Remove Gain blocks that scale by a factor of one.
- **Optimize for delay chains** — Substitute delay chains made up of  $n$  unit delays with a single delay by  $n$ .
- **Optimize for negative gains** — Use subtraction in Sum blocks instead of negative gains in Gain blocks.

# Bandstop Filter

---

## Optimize for unit-scale values

Select this check box to scale unit gains between sections in SOS filters. This parameter is available only for SOS filters.

## Input processing

Specify how the block should process the input. The available options may vary depending on the settings of the **Filter Structure** and **Use basic elements for filter customization** parameters. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The **Inherited** (this choice will be removed see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Rate options

When the **Filter type** parameter specifies a multirate filter, select the rate processing rule for the block from following options:

- **Enforce single-rate processing** — When you select this option, the block maintains the sample rate of the input.
- **Allow multirate processing** — When you select this option, the block adjusts the rate at the output to accommodate an increased or reduced number of samples. To select this option, you must set the **Input processing** parameter to **Elements as channels (sample based)**.

## Use symbolic names for coefficients

Select this check box to enable the specification of coefficients using MATLAB variables. The available coefficient names differ depending on the filter structure. Using symbolic names allows tuning of filter coefficients in generated code. By default, this check box is cleared.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

# Biquad Filter

---

**Purpose** Model biquadratic IIR (SOS) filters

**Library** Filtering / Filter Implementations  
dsparch4

## Description



The Biquad Filter block independently filters each channel of the input signal with the specified biquadratic IIR filter. When you specify the filter coefficients in the dialog box, the block implements static filters with fixed coefficients. When you provide the filter coefficients through an input port, you can tune the coefficients during simulation.

The block filters an  $M$ -by- $N$  input matrix as follows:

- When you set the **Input processing** parameter to **Columns as channels (frame based)**, the block treats each column as a separate channel. In this mode, the block creates  $M$  instances of the same filter, each with its own independent state buffer. Each of the  $M$  filters process  $N$  input samples at every Simulink time step.
- When you set the **Input processing** parameter to **Elements as channels (sample based)**, the block treats each element as a separate channel. In this mode, the block creates  $M*N$  instances of the same filter, each with its own independent state buffer. Each filter processes one input sample at every Simulink time step.

The output dimensions always equal those of the input signal. The outputs of this block numerically match the outputs of the `dfilt` object.

The Biquad Filter block supports the Simulink state logging feature. See “States” in the *Simulink User’s Guide* for more information.

## Coefficient Source and Filter Structures

The Biquad Filter block can operate in three different modes. Select the mode in the **Coefficient source** group box.

- If you select **Dialog parameters**, you enter information about the filter such as structure and coefficients in the block mask. In this

mode, you can choose the following filter structures in the **Filter structure** parameter:

- Direct form I
- Direct form I transposed
- Direct form II
- Direct form II transposed
- If you select **Input port(s)**, you enter information about the filter structure in the block mask using the **Filter structure** parameter, but the filter coefficients come into the block via input ports. The following additional ports appear on the block icon:
  - Num — numerator coefficients
  - Den — denominator coefficients
  - g — scale values
- If you select **Discrete-time filter object (DFILT)**, you specify the filter using a `dfilt` object. This block supports the following `dfilt` structures:
  - `dfilt.df1sos`
  - `dfilt.df1tsos`
  - `dfilt.df2sos`
  - `dfilt.df2tsos`

## Specifying the SOS Matrix and Scale Values

The **SOS matrix (Mx6)** is an  $M$ -by-6 matrix, where  $M$  is the number of sections in the second-order section filter. Each row of the SOS matrix contains the numerator and denominator coefficients ( $b_{ik}$  and  $\alpha_{ik}$ ) of the corresponding section in the filter.


# Biquad Filter

$$\begin{bmatrix} b_{01} & b_{11} & b_{21} & a_{01} & a_{11} & a_{21} \\ b_{02} & b_{12} & b_{22} & a_{02} & a_{12} & a_{22} \\ \vdots & \vdots & \vdots & \vdots & \vdots & \vdots \\ b_{0M} & b_{1M} & b_{2M} & a_{0M} & a_{1M} & a_{2M} \end{bmatrix}$$

You can use the `ss2sos` and `tf2sos` functions from Signal Processing Toolbox software to convert a state-space or transfer function description of your filter into the second-order section description used by this block.

The **Scale values** parameter specifies the scale values the block uses between each SOS section. You can specify a real-valued scalar or a vector of length  $M+1$ .

- If you enter a scalar, the value specifies the gain value before the first section of the second-order filter. The rest of the gain values default to 1.
- If you enter a vector of  $M+1$  values, each value specifies a separate section of the filter. For example, the first element is the first gain value, the second element is the second gain value, and so on.



Select the **Optimize unity scale values** check box to optimize your simulation when one or more scale values equal 1. Selecting this option removes the unity gains so that the values are treated like Simulink lines or wires. In some fixed-point cases when there are unity scale values, selecting this parameter also omits certain casts. Refer to “Filter Structure Diagrams” on page 2-148 for more information.

## Specifying Initial Conditions

The Biquad Filter block initializes the internal filter states to zero by default. You can optionally use the **Initial conditions** or **Initial conditions on zeros side** and **Initial conditions on poles side** parameters to specify nonzero initial states for the filter delays.

To determine the number of initial conditions you must specify and how to specify them, see the following table on valid initial conditions.

## Valid Initial Conditions

Initial Condition	Description
Scalar	The block initializes all delay elements in the filter to the scalar value.
Vector or matrix (for applying different delay elements to each channel)	Each vector or matrix element specifies a unique initial condition for a corresponding delay element in a corresponding channel. Where $M$ is the number of sections and $N$ is the number of input channels: <ul style="list-style-type: none"><li>• The vector length must equal the number of delay elements in the filter, <math>M*2</math>.</li><li>• The matrix must have the same number of rows as the number of delay elements in the filter, <math>(M*2)*N</math>. The matrix must also have one column for each channel of the input signal.</li></ul>

## Fixed-Point Data Types

See the “Filter Structure Diagrams” on page 2-148 section for diagrams showing the data types the biquad filter block uses when processing fixed-point signals.

## Examples

Open an example model by typing `ex_biquad_filter_ref` at the MATLAB command line.

## Dialog Box

### Coefficient Source

The Biquad Filter block can operate in three different modes. Select the mode in the **Coefficient source** group box.

- If you select **Dialog parameters**, you enter information about the filter such as structure and coefficients in the block mask. In this

# Biquad Filter


---

mode, you can choose the following filter structures in the **Filter structure** parameter:

- Direct form I
- Direct form I transposed
- Direct form II
- Direct form II transposed
- If you select **Input port(s)**, you enter information about the filter structure in the block mask using the **Filter structure** parameter, but the filter coefficients come into the block via input ports. The following additional ports appear on the block icon:
  - Num — numerator coefficients
  - Den — denominator coefficients
  - g — scale values
- If you select **Discrete-time filter object (DFILT)**, you specify the filter using a `dfilt` object. This block supports the following `dfilt` structures:
  - `dfilt.df1sos`
  - `dfilt.df1tsos`
  - `dfilt.df2sos`
  - `dfilt.df2tsos`

## Specify Filter Characteristics in Dialog

The **Main** pane of the Biquad Filter block dialog appears as follows when **Dialog parameters** is selected in the **Coefficient source** group box.



# Biquad Filter

---

## Filter structure

Select the filter structure.

This parameter is only visible when **Dialog parameters** or **Input port(s)** is selected.

## SOS Matrix

Specify an  $M$ -by-6 matrix, where  $M$  is the number of sections in the second-order section filter. Each row of the SOS matrix contains the numerator and denominator coefficients ( $b_{ik}$  and  $a_{ik}$ ) of the corresponding section in the filter.

$$\begin{bmatrix} b_{01} & b_{11} & b_{21} & a_{01} & a_{11} & a_{21} \\ b_{02} & b_{12} & b_{22} & a_{02} & a_{12} & a_{22} \\ \vdots & \vdots & \vdots & \vdots & \vdots & \vdots \\ b_{0M} & b_{1M} & b_{2M} & a_{0M} & a_{1M} & a_{2M} \end{bmatrix}$$

This parameter is only visible when **Dialog parameters** is selected.

## Scale values

The **Scale values** parameter specifies the scalar or vector of  $M+1$  scale values to be used between SOS sections.

- When you enter a scalar, the value specifies the gain value before the first section of the second-order filter. The rest of the gain values default to 1.
- When you enter a vector of  $M+1$  values, each value specifies a separate section of the filter. For example, the first element is the first gain value, the second element is the second gain value, and so on.

This parameter is only visible when **Dialog parameters** is selected.

## **Initial conditions**

Specify the initial conditions of the filter states. To learn how to specify initial conditions, see “Specifying Initial Conditions” on page 2-128.

This parameter is only visible when **Dialog parameters** or **Input port(s)** is selected and the filter structure is Direct form II or Direct form II transposed.

## **Initial conditions on zeros side**

Specify the initial conditions for the filter states on the side of the filter structure with the zeros ( $b_0, b_1, b_2, \dots$ ); see the next diagram.


This parameter is only visible when **Dialog parameters** or **Input port(s)** is selected and the filter structure is Direct form I or Direct form I transposed. To learn how to specify initial conditions, see “Specifying Initial Conditions” on page 2-128.

## **Initial conditions on poles side**

Specify the initial conditions for the filter states on the side of the filter structure with the poles ( $a_0, a_1, a_2, \dots$ ); see the next diagram.

This parameter is only visible when **Dialog parameters** or **Input port(s)** is selected and the filter structure is Direct form I or Direct form I transposed. To learn how to specify initial conditions, see “Specifying Initial Conditions” on page 2-128.

# Biquad Filter



## Action when the $a_0$ values of the SOS matrix are not one

Specify the action the block should perform when the SOS matrix  $a_{0j}$  values do not equal one; None, Error, or Warn.

This parameter is only visible when **Dialog parameters** is selected.

## Optimize unity scale values

Select this check box to optimize your simulation when one or more scale values equal 1. Selecting this option removes the unity gains so that the values are treated like Simulink lines or wires. In some fixed-point cases when there are unity scale values, selecting this parameter also omits certain casts. Refer to “Filter Structure Diagrams” on page 2-148 for more information.

This parameter is only visible when **Dialog parameters** is selected.

## Input processing

Specify how the block should process the input. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.

- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---


**Note** The **Inherited** (this choice will be removed - see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Specify Filter Characteristics via Input Port

The **Main** pane of the Biquad Filter block dialog appears as follows when **Input port(s)** is selected in the **Coefficient source** group box.

# Biquad Filter



## Filter structure

Select the filter structure.

This parameter is only visible when **Dialog parameters** or **Input port(s)** is selected.

## Initial conditions

Specify the initial conditions of the filter states. To learn how to specify initial conditions, see “Specifying Initial Conditions” on page 2-128.

This parameter is only visible when **Dialog parameters** or **Input port(s)** is selected and the filter structure is Direct form II or Direct form II transposed.

## Initial conditions on zeros side

Specify the initial conditions for the filter states on the side of the filter structure with the zeros ( $b_0, b_1, b_2, \dots$ ); see the next diagram.


This parameter is only visible when **Dialog parameters** or **Input port(s)** is selected and the filter structure is Direct form I or Direct form I transposed. To learn how to specify initial conditions, see “Specifying Initial Conditions” on page 2-128.

## Initial conditions on poles side

Specify the initial conditions for the filter states on the side of the filter structure with the poles ( $a_0, a_1, a_2, \dots$ ); see the next diagram.

This parameter is only visible when **Dialog parameters** or **Input port(s)** is selected and the filter structure is Direct form I or Direct form I transposed. To learn how to specify initial conditions, see “Specifying Initial Conditions” on page 2-128.

# Biquad Filter



## Scale values mode

Choose how to specify the scale values to use between filter sections. When you select **Specify via input port (g)**, you enter the scale values as a 2-D vector at port **g**. When you select **Assume all are unity and optimize**, all scale values are removed and treated like Simulink lines or wires.

This parameter is only visible when **Input port(s)** is selected.

## Input processing

Specify how the block should process the input. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---


**Note** The Inherited (this choice will be removed - see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## **Specify Discrete-Time Filter Object**

The **Main** pane of the Biquad Filter block dialog appears as follows when **Discrete-time filter object (DFILT)** is selected in the **Coefficient source** group box.

# Biquad Filter



## Filter

Specify the discrete-time filter object (`dfilt`) that you would like the block to implement. You can do so in one of three ways:

- You can fully specify the `dfilt` object in the block mask.
- You can enter the variable name of a `dfilt` object that is defined in any workspace.
- You can enter a variable name for a `dfilt` object that is not yet defined.

For more information on creating `dfilt` objects, see the `dfilt` reference page.

## View filter response

This button opens the Filter Visualization Tool (`fvtool`) from the Signal Processing Toolbox product and displays the filter response of the `dfilt` object specified in the **Discrete-time filter object (DFILT)** parameter. For more information on FVTool, see the Signal Processing Toolbox documentation.

---

**Note** If you specify a filter in the **Discrete-time filter object (DFILT)** parameter, you must click the **Apply** button to apply the filter before using the **View filter response** button.

---

## Input processing

Specify how the block should process the input. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

# Biquad Filter

---


---

**Note** The Inherited (this choice will be removed - see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Specify Fixed-Point Parameters

The **Data Types** pane of the Biquad Filter block dialog appears as follows. This pane only appears when **Dialog parameters** or **Input port(s)** is selected in the **Coefficient source** group box.



**Function Block Parameters: Biquad Filter**

Biquad Filter

Implement a general IIR filter using biquad structures. Biquad implementations of general IIR filters are often preferred due to their desirable numeric properties.

Coefficient source

- Dialog parameters
- Input port(s)
- Discrete-time filter object (DFILT)

Main | Data Types

Floating-point inheritance takes precedence over the settings in the 'Data Type' column below. When the block input is floating point, all block data types match the input.

Fixed-point operational parameters

Rounding mode:  Overflow mode:

Fixed-point data types

	Data Type
Section input	<input type="text" value="Same as input"/>
Section output	<input type="text" value="Same as section input"/>
Coefficients	<input type="text" value="Same word length as input"/>
Product output	<input type="text" value="Same as input"/>
Accumulator	<input type="text" value="Same as product output"/>
State	<input type="text" value="Same as accumulator"/>
Output	<input type="text" value="Same as accumulator"/>

Lock data type settings against changes by the fixed-point tools

? OK Cancel Help Apply

# Biquad Filter

---

## **Rounding mode**

Select the rounding mode for fixed-point operations. The filter coefficients do not obey this parameter; instead, they always round to Nearest.

## **Overflow mode**

Select the overflow mode for fixed-point operations. The filter coefficients do not obey this parameter; instead, they are always saturated.

## **Multiplicand**

Choose how you specify the word length and the fraction length of the multiplicand data type of a **Direct form I transposed** filter structure. See “Fixed-Point Data Types” on page 2-129 and the “Direct Form I Transposed” on page 2-151 filter structure diagram for illustrations depicting the use of the multiplicand data type in this block.

This parameter is only visible when the **Filter structure** parameter is set to **Direct form I transposed**.

- When you select **Same as output**, these characteristics match those of the output of the block.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the product output, in bits.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the product output. This block requires power-of-two slope and a bias of zero.

## **Section input**

Choose how you specify the word length and the fraction length of the fixed-point data type going into each section of a biquadratic filter. See “Fixed-Point Data Types” on page 2-129 for illustrations depicting the use of the section input data type in this block.

- When you select **Same as input**, these characteristics match those of the input to the block.

- When you select **Binary point scaling**, you can enter the word and fraction lengths of the section input and output, in bits.
- When you select **Slope and bias scaling**, you can enter the word lengths, in bits, and the slopes of the section input and output. This block requires power-of-two slope and a bias of zero.

## Section output

Choose how you specify the word length and the fraction length of the fixed-point data type coming out of each section of a biquadratic filter. See “Fixed-Point Data Types” on page 2-129 for illustrations depicting the use of the section input data type in this block.

- When you select **Same as input**, these characteristics match those of the input to the block.
- When you select **Binary point scaling**, you can enter the word and fraction lengths of the section input and output, in bits.
- When you select **Slope and bias scaling**, you can enter the word lengths, in bits, and the slopes of the section input and output. This block requires power-of-two slope and a bias of zero.

## Coefficients

Choose how you specify the word length and the fraction length of the filter coefficients (numerator, denominator, and scale value) when **Dialog parameters** is selected in the **Coefficient source** group box. See “Fixed-Point Data Types” on page 2-129 for illustrations depicting the use of the coefficient data types in this block:

- When you select **Same word length as input**, the word length of the filter coefficients match that of the input to the block. In this mode, the block automatically sets the fraction length of the coefficients to the binary-point only scaling that

# Biquad Filter

---

provides you with the best precision possible given the value and word length of the coefficients.

- When you select **Specify word length**, you can enter the word length of the coefficients, in bits. In this mode, the block automatically sets the fraction length of the coefficients to the binary-point only scaling that provides you with the best precision possible given the value and word length of the coefficients.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the coefficients, in bits. If applicable, you can enter separate fraction lengths for the numerator and denominator coefficients.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the coefficients. If applicable, you can enter separate slopes for the numerator and denominator coefficients. This block requires power-of-two slope and a bias of zero.
- The filter coefficients do not obey the **Rounding mode** and the **Overflow mode** parameters; instead, they are always saturated and rounded to Nearest.

## Product output

Use this parameter to specify how you would like to designate the product output word and fraction lengths. See “Fixed-Point Data Types” on page 2-129 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block:

- When you select **Same as input**, these characteristics match those of the input to the block.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the product output, in bits.

- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the product output. This block requires power-of-two slope and a bias of zero.

## Accumulator

Use this parameter to specify how you would like to designate the accumulator word and fraction lengths. See “Fixed-Point Data Types” on page 2-129 and “Multiplication Data Types” for illustrations depicting the use of the accumulator data type in this block:

- When you select **Same as input**, these characteristics match those of the input to the block.
- When you select **Same as product output**, these characteristics match those of the product output.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the accumulator, in bits.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the accumulator. This block requires power-of-two slope and a bias of zero.

## State

Use this parameter to specify how you would like to designate the state word and fraction lengths when **Dialog parameters** is selected in the **Coefficient source** group box. See “Fixed-Point Data Types” on page 2-129 for illustrations depicting the use of the state data type in this block.

This parameter is not visible for **Direct form I** and **Direct form I transposed filter** structures.

- When you select **Same as input**, these characteristics match those of the input to the block.
- When you select **Same as accumulator**, these characteristics match those of the accumulator.

# Biquad Filter

---

- When you select **Binary point scaling**, you can enter the word length and the fraction length of the accumulator, in bits.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the accumulator. This block requires power-of-two slope and a bias of zero.

## Output

Choose how you specify the output word length and fraction length. See “Fixed-Point Data Types” on page 2-129 for illustrations depicting the use of the output data type in this block.

- When you select **Same as input**, these characteristics match those of the input to the block.
- When you select **Same as accumulator**, these characteristics match those of the accumulator.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the output, in bits.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the output. This block requires power-of-two slope and a bias of zero.

## Lock data type settings against changes by the fixed-point tools


Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## Filter Structure Diagrams

The diagrams in the following sections show the filter structures supported by the Biquad Filter block. They also show the data types used in the filter structures for fixed-point signals. You can set the data types shown in these diagrams in the block dialog box. This is discussed in “Dialog Box” on page 2-129.


- “Direct Form I” on page 2-149
- “Direct Form I Transposed” on page 2-151
- “Direct Form II” on page 2-154
- “Direct Form II Transposed” on page 2-157

## Direct Form I




# Biquad Filter

The following diagram shows the data types for one section of the filter for fixed-point signals.




The following diagrams show the fixed-point data types between filter sections.


When the data is not optimized:



When you select **Optimize unity scale values** and scale values equal 1:




## Direct Form I Transposed



# Biquad Filter


The following diagram shows the data types for one section of the filter for fixed-point signals.




The dashed casts are omitted when **Optimize unity scale values** is selected and scale values equal one.

The following diagrams show the fixed-point data types between filter sections.

When the data is not optimized:





When you select **Optimize unity scale values** and scale values equal 1:




# Biquad Filter

## Direct Form II



The following diagram shows the data types for one section of the filter for fixed-point signals.




The dashed casts are omitted when **Optimize unity scale values** is selected and scale values equal one.


# Biquad Filter

The following diagrams show the fixed-point data types between filter sections.


When the data is not optimized:



When you select **Optimize unity scale values** and scale values equal 1:




## Direct Form II Transposed




# Biquad Filter

The following diagram shows the data types for one section of the filter for fixed-point signals.




The following diagrams show the fixed-point data types between filter sections.

When the data is not optimized:



When you select **Optimize unity scale values** and scale values equal 1:



## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed only)</li> <li>• 8-, 16-, and 32-bit signed integers</li> </ul>
Output	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed only)</li> <li>• 8-, 16-, and 32-bit signed integers</li> </ul>

## See Also

`dfilt.df1sos`  
`dfilt.df1tsos`

DSP System Toolbox  
 DSP System Toolbox

# Biquad Filter

---

`dfilt.df2sos`

DSP System Toolbox


`dfilt.df2tsos`

DSP System Toolbox

**Purpose** Compute output, error, and weights using LMS adaptive algorithm

**Library** Filtering / Adaptive Filters  
dspadpt3

## Description



The Block LMS Filter block implements an adaptive least mean-square (LMS) filter, where the adaptation of filter weights occurs once for every block of samples. The block estimates the filter weights, or coefficients, needed to minimize the error,  $e(n)$ , between the output signal,  $y(n)$ , and the desired signal,  $d(n)$ . Connect the signal you want to filter to the Input port. The input signal can be a scalar or a column vector. Connect the signal you want to model to the Desired port. The desired signal must have the same data type, complexity, and dimensions as the input signal. The Output port outputs the filtered input signal. The Error port outputs the result of subtracting the output signal from the desired signal.

The block calculates the filter weights using the Block LMS adaptive filter algorithm. This algorithm is defined by the following equations.

$$n = kN + i$$

$$y(n) = \mathbf{w}^T(k-1)\mathbf{u}(n)$$

$$e(n) = d(n) - y(n)$$

$$\mathbf{w}(k) = \mathbf{w}(k-1) + f(\mathbf{u}(n), e(n), \mu)$$

The weight update function for the Block LMS adaptive filter algorithm is defined as

$$f(\mathbf{u}(n), e(n), \mu) = \mu \sum_{i=0}^{N-1} \mathbf{u}^*(kN + i)e(kN + i)$$

The variables are as follows.

# Block LMS Filter

---

Variable	Description
$n$	The current time index
$i$	The iteration variable in each block, $0 \leq i \leq N - 1$
$k$	The block number
$N$	The block size
$\mathbf{u}(n)$	The vector of buffered input samples at step $n$
$\mathbf{w}(n)$	The vector of filter-tap estimates at step $n$
$y(n)$	The filtered output at step $n$
$e(n)$	The estimation error at time $n$
$d(n)$	The desired response at time $n$
$\mu$	The adaptation step size

Use the **Filter length** parameter to specify the length of the filter weights vector.

The **Block size** parameter determines how many samples of the input signal are acquired before the filter weights are updated. The number of rows in the input must be an integer multiple of the **Block size** parameter.

The adaptation **Step-size (mu)** parameter corresponds to  $\mu$  in the equations. You can either specify a step-size using the input port, Step-size, or enter a value in the Block Parameters: Block LMS Filter dialog box.

Use the **Leakage factor (0 to 1)** parameter to specify the leakage factor,  $0 < 1 - \mu\alpha \leq 1$ , in the leaky LMS algorithm shown below.

$$\mathbf{w}(k) = (1 - \mu\alpha)\mathbf{w}(k-1) + f(\mathbf{u}(n), e(n), \mu)$$

Enter the initial filter weights as a vector or a scalar in the **Initial value of filter weights** text box. When you enter a scalar, the block uses the scalar value to create a vector of filter weights. This vector


has length equal to the filter length and all of its values are equal to the scalar value

When you select the **Adapt port** check box, an Adapt port appears on the block. When the input to this port is greater than zero, the block continuously updates the filter weights. When the input to this port is zero, the filter weights remain at their current values.

When you want to reset the value of the filter weights to their initial values, use the **Reset input** parameter. The block resets the filter weights whenever a reset event is detected at the Reset port. The reset signal rate must be the same rate as the data signal input.


From the **Reset input** list, select **None** to disable the Reset port. To enable the Reset port, select one of the following from the **Reset input** list:

- **Rising edge** — Triggers a reset operation when the Reset input does one of the following:
  - Rises from a negative value to a positive value or zero
  - Rises from zero to a positive value, where the rise is not a continuation of a rise from a negative value to zero (see the following figure).




# Block LMS Filter

- **Falling edge** — Triggers a reset operation when the Reset input does one of the following:
  - Falls from a positive value to a negative value or zero
  - Falls from zero to a negative value, where the fall is not a continuation of a fall from a positive value to zero (see the following figure)



- **Either edge** — Triggers a reset operation when the Reset input is a Rising edge or Falling edge (as described above)
- **Non-zero sample** — Triggers a reset operation at each sample time that the Reset input is not zero

Select the **Output filter weights** check box to create a **Wts** port on the block. For each iteration, the block outputs the current updated filter weights from this port.



## Dialog Box

### Filter length

Enter the length of the FIR filter weights vector.

# Block LMS Filter

---

## Block size

Enter the number of samples to acquire before the filter weights are updated. The number of rows in the input must be an integer multiple of the **Block size**.

## Specify step-size via

Select Dialog to enter a value for  $\mu$  in the Block parameters: LMS Filter dialog box. Select Input port to specify  $\mu$  using the Step-size input port.

## Step-size ( $\mu$ )

Enter the step-size. Tunable.

## Leakage factor (0 to 1)

Enter the leakage factor,  $0 < 1 - \mu\alpha \leq 1$ . Tunable.

## Initial value of filter weights

Specify the initial values of the FIR filter weights.

## Adapt port

Select this check box to enable the Adapt input port.

## Reset port

Select this check box to enable the Reset input port.

## Output filter weights

Select this check box to export the filter weights from the Wts port.

## References

Hayes, M. H. *Statistical Digital Signal Processing and Modeling*. New York: John Wiley & Sons, 1996.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Desired	<ul style="list-style-type: none"><li>• Must be the same as Input</li></ul>
Step-size	<ul style="list-style-type: none"><li>• Must be the same as Input</li></ul>

Port	Supported Data Types
Adapt	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Reset	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Same as Input</li></ul>
Error	<ul style="list-style-type: none"><li>• Same as Input</li></ul>
Wts	<ul style="list-style-type: none"><li>• Same as Input</li></ul>

## See Also

Fast Block LMS Filter	DSP System Toolbox
Kalman Adaptive Filter (Obsolete)	DSP System Toolbox
LMS Filter	DSP System Toolbox
RLS Filter	DSP System Toolbox


See “Adaptive Filters in Simulink” for related information.

# Buffer


**Purpose** Buffer input sequence to smaller or larger frame size

**Library** Signal Management / Buffers  
dspbuff3


## Description



The Buffer block always performs frame-based processing. The block redistributes the data in each column of the input to produce an output with a different frame size. Buffering a signal to a larger frame size yields an output with a *slower* frame rate than the input. For example, consider the following illustration for scalar input.



Buffering a signal to a smaller frame size yields an output with a *faster* frame rate than the input. For example, consider the following illustration of scalar output.



The block coordinates the output *frame size* and *frame rate* of nonoverlapping buffers such that the sample period of the signal is the same at both the input and output:  $T_{so} = T_{si}$ .

This block supports triggered subsystems when the block input and output rates are the same.

### Buffering Single Channel Signals

The following table shows the output dimensions of the Buffer block when the input is a single-channel signal.  $M_o$  is the value of the **Output buffer size** parameter.

Input Dimensions	Output Dimensions
1-by-1 (scalar)	$M_o$ -by-1
$M_i$ -by-1 (column vector)	$M_o$ -by-1

The input frame period is  $M_i \cdot T_{si}$ , where  $M_i$  is the input frame size and  $T_{si}$  is the input sample period. The output frame period is  $(M_o - L)T_{si}$ , where  $L$  is the value of the **Buffer overlap** parameter and  $T_{si}$  is the input sample period. When you set the **Buffer overlap** parameter to  $M_o - 1$ , the output frame period equals the input sample period.

### Buffering Multichannel Signals

The following table shows the output dimensions of the Buffer block when the input is a multichannel signal.  $M_o$  is the value of the **Output buffer size** parameter and can be greater or less than the input frame size,  $M_i$ . The block buffers each of the  $N$  input channels independently.

Input Dimensions	Output Dimensions
1-by- $N$ (row vector)	$M_o$ -by- $N$
$M_i$ -by- $N$ (matrix)	$M_o$ -by- $N$

The input frame period is  $M_i \cdot T_{si}$ , where  $M_i$  is the input frame size and  $T_{si}$  is the input sample period. The output frame period is  $(M_o - L)T_{si}$ , which equals the sequence sample period when the **Buffer overlap** is  $M_o - 1$ . Thus, the output sample period is related to the input sample period by

$$T_{so} = \frac{(M_o - L)T_{si}}{M_i}$$

## Buffering with Overlap or Underlap

The **Buffer overlap** parameter,  $L$ , specifies the amount of overlap or underlap in each successive output frame. To overlap the data in the buffer, specify a value of  $L$  in the range  $0 \leq L < M_o$ , where  $M_o$  is the value of the **Output buffer size** parameter. The block takes  $L$  samples (rows) from the current output and repeats them in the next output. In cases of overlap, the block acquires  $M_o - L$  new input samples before propagating the buffered data to the output.

When  $L < 0$ , you are buffering the signal with underlap. The block discards  $L$  input samples after the buffer fills and outputs the buffer with period  $(M_o - L)T_{si}$ , which is longer than in the zero-overlap case.

The output frame period is  $(M_o - L)T_{si}$ , which equals the input sequence sample period,  $T_{si}$ , when the **Buffer overlap** is  $M_o - 1$ .

## Latency

*Zero-tasking latency* means that the first input sample, received at  $t = 0$ , appears as the first output sample. In the Simulink single-tasking mode, the Buffer block has zero-tasking latency for the following special cases:

- Scalar input and output ( $M_o = M_i = 1$ ) with zero or negative **Buffer overlap** ( $L \leq 0$ )
- Input frame size is an integer multiple of the output frame size

$$M_i = kM_o$$

where  $k$  is an integer with zero **Buffer overlap** ( $L = 0$ ); notable cases of this include

- Any input frame size  $M_i$  with scalar output ( $M_o = 1$ ) and zero **Buffer overlap** ( $L = 0$ )
- Equal input and output frame sizes ( $M_o = M_i$ ) with zero **Buffer overlap** ( $L = 0$ )

For all cases of single-tasking operation other than those listed above, the Buffer block's buffer is initialized to the value(s) specified by the **Initial conditions** parameter. The block reads from this buffer to generate the first  $D$  output samples, where

$$D = \begin{cases} M_o + L & (L \geq 0) \\ M_o & (L < 0) \end{cases}$$

The dimensions of the **Initial conditions** parameter depend on the **Buffer overlap**,  $L$ , and whether the input is single-channel or multichannel:

- When  $L \neq 0$ , the **Initial conditions** parameter must be a scalar.
- When  $L = 0$ , the **Initial conditions** parameter can be a scalar, or it can be a vector with the following constraints:
  - For single-channel inputs, the **Initial conditions** parameter can be a vector of length  $M_o$  if  $M_i$  is 1, or a vector of length  $M_i$  if  $M_o$  is 1.
  - For multichannel inputs, the **Initial conditions** parameter can be a vector of length  $M_o * N$  if  $M_i$  is 1, or a vector of length  $M_i * N$  if  $M_o$  is 1.

For all *multitasking* operations, use the `rebuffer_delay` function to compute the exact delay, in samples, that the Buffer block introduces for a given combination of buffer size and buffer overlap.

For general buffering between arbitrary frame sizes, the **Initial conditions** parameter must be a scalar value, which is then repeated across all elements of the initial output(s). However, in the special case

where the input is a 1-by- $N$  row vector, and the output of the block is an  $M_o$ -by- $N$  matrix, **Initial conditions** can be

- An  $M_o$ -by- $N$  matrix
- A length- $M_o$  vector to be repeated across all columns of the initial output(s)
- A scalar to be repeated across all elements of the initial output(s)

In the special case where the output is a 1-by- $N$  row vector, which is the result of unbuffering an  $M_i$ -by- $N$  matrix, the **Initial conditions** can be

- A vector containing  $M_i$  samples to output sequentially for each channel during the first  $M_i$  sample times
- A scalar to be repeated across all elements of the initial output(s)

---

**Note** For more information on latency and the Simulink tasking modes, see “Excess Algorithmic Delay (Tasking Latency)” and “Scheduling” in the *Simulink Coder™ User’s Guide*.

---

## Behavior in Enabled Subsystems

The Buffer block cannot be used in an enabled subsystem under the following conditions:

- In a multirate multitasking environment
- When the **Buffer overlap** parameter is set to a negative value

The Buffer block has an internal reservoir that temporarily stores data. When the Buffer block is used in an enabled subsystem, there is the possibility that the reservoir can overrun or underrun. The block implements safeguards against these occurrences.

Overrun occurs when more data enters into the buffer than it can hold. For example, consider buffering a scalar input to a frame of size three

with a buffer that accepts input every second and outputs every three seconds. If you place this buffer inside an enabled subsystem that is disabled every three seconds at  $t = 3\text{s}$ ,  $t = 6\text{s}$ , and so on, the buffer accumulates data in its internal reservoir without being able to empty it. This condition results in overrun.

Underrun occurs when the buffer runs out of data to output. For example, again consider buffering a scalar input to a frame size of three with a buffer that accepts input every second and outputs every three seconds. If you place this buffer inside an enabled subsystem that is disabled at  $t = 10\text{s}$ ,  $t = 11\text{s}$ ,  $t = 13\text{s}$ ,  $t = 14\text{s}$ ,  $t = 16\text{s}$ , and  $t = 17\text{s}$ , its internal reservoir becomes drained, and there is no data to output at  $t = 18\text{s}$ . This condition results in underrun.


To protect from overrun and underrun, the Buffer block keeps a record of the amount of data in its internal reservoir. When the Buffer block reads data, the amount of data in its reservoir goes up. When data is output from the Buffer block, the amount of data in its reservoir goes down. To protect from overrun, the oldest samples in the reservoir are discarded whenever amount of data in the reservoir is larger than the actual buffer size. To protect from underrun, the most recent samples are repeated whenever an output is due and there is no data in the reservoir.

## Examples

### Buffering a two-channel input with overlap

The `ex_buffer_tut4` model buffers a two-channel input using an **Output buffer size** of three and a **Buffer overlap** of one. The following diagram illustrates the inputs and outputs of the Buffer block.


# Buffer



Notice that the output is delayed by eight samples. This is latency occurs because of the parameter settings in this model, and because the model is running in Simulink multitasking mode. The first eight output samples therefore adopt the value specified for the **Initial conditions** parameter, which in this case is set to zero. You can use the `rebuffer_delay` function to determine the latency of the Buffer block for any combination of frame size and overlap values.

## Buffering a four-channel input with overlap

The `ex_buffer_tut3` buffers a four-channel input using a **Output buffer size** of three and a **Buffer overlap** of one. The following diagram illustrates the inputs and outputs of the Buffer block.




Notice that the input vectors do not begin appearing at the output until the second row of the second matrix. This is due to latency in the Buffer block. The first output matrix (all zeros in this example) reflects the value of the **Initial conditions** parameter, while the first row of zeros in the second output is a result of the one-sample overlap between consecutive output frames.

You can use the `rebuffer_delay` function with a frame size of 1 to precisely compute the delay (in samples). For the previous example,

```
d = rebuffer_delay(1,3,1)
d =
    4
```

This agrees with the four samples of delay (zeros) per channel shown in the previous figure.

# Buffer



## Dialog Box

### Output buffer size

Specify the number of consecutive samples,  $M_o$ , from each channel to buffer into the output frame.

### Buffer overlap

Specify the number of samples,  $L$ , by which consecutive output frames overlap.

### Initial conditions

Specify the value of the block's initial output for cases of nonzero latency; a scalar, vector, or matrix.

**Treat  $M \times 1$  and unoriented sample-based signals as**

Specify how the block treats sample-based  $M$ -by-1 column vectors and unoriented sample-based vectors of length  $M$ . You can select one of the following options:

- **One channel** — When you select this option, the block treats  $M$ -by-1 and unoriented sample-based inputs as a column vector (one channel). In this mode, the output of the block is an  $M_o$ -by-1 column vector, where  $M_o$  is the **Output buffer size**.
- **$M$  channels** (this choice will be removed see release notes) — When you select this option, the block treats  $M$ -by-1 and unoriented sample-based inputs as a 1-by- $M$  row vector. Because the block always does frame-based processing, the block interprets the 1-by- $M$  row vector as  $M$  individual channels. In this mode, the output of the block is an  $M_o$ -by- $M$  matrix, where  $M_o$  is the **Output buffer size**, and  $M$  is the length of the sample-based input vector.

---

**Note** This parameter will be removed in a future release. At that time, the Buffer block will always perform frame-based processing.

---

**Supported Data Types**

Port	Supported Data Types
Input	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> </ul>

# Buffer

---

Port	Supported Data Types
	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

## See Also


Delay Line	DSP System Toolbox
Unbuffer	DSP System Toolbox
rebuffer_delay	DSP System Toolbox

See “Convert Sample and Frame Rates in Simulink” and “Buffering and Frame-Based Processing” for more information.

**Purpose** Compute estimate of autoregressive (AR) model parameters using Burg method

**Library** Estimation / Parametric Estimation  
dspparest3

## Description



The Burg AR Estimator block uses the Burg method to fit an autoregressive (AR) model to the input data by minimizing (least squares) the forward and backward prediction errors while constraining the AR parameters to satisfy the Levinson-Durbin recursion.

The input is a sample-based vector (row, column, or 1-D) or frame-based vector (column only) representing a frame of consecutive time samples from a single-channel signal, which is assumed to be the output of an AR system driven by white noise. The block computes the normalized estimate of the AR system parameters,  $A(z)$ , independently for each successive input frame.

$$H(z) = \frac{G}{A(z)} = \frac{G}{1 + a(2)z^{-1} + \dots + a(p+1)z^{-p}}$$

When you select the **Inherit estimation order from input dimensions** parameter, the order,  $p$ , of the all-pole model is one less than the length of the input vector. Otherwise, the order is the value specified by the **Estimation order** parameter.

The **Output(s)** parameter allows you to select between two realizations of the AR process:

- A — The top output,  $A$ , is a column vector of length  $p+1$  with the same frame status as the input, and contains the normalized estimate of the AR model polynomial coefficients in descending powers of  $z$ .

$$[1 \ a(2) \ \dots \ a(p+1)]$$

# Burg AR Estimator

- $K$  — The top output,  $K$ , is a column vector of length  $p$  with the same frame status as the input, and contains the reflection coefficients (which are a secondary result of the Levinson recursion).
- $A$  and  $K$  — The block outputs both realizations.

The scalar gain,  $G$ , is provided at the bottom output ( $G$ ).

The following table compares the features of the Burg AR Estimator block to the Covariance AR Estimator, Modified Covariance AR Estimator, and Yule-Walker AR Estimator blocks.


	<b>Burg AR Estimator</b>	<b>Covariance AR Estimator</b>	<b>Modified Covariance AR Estimator</b>	<b>Yule-Walker AR Estimator</b>
<b>Characteristics</b>	Does not apply window to data	Does not apply window to data	Does not apply window to data	Applies window to data
	Minimizes the forward and backward prediction errors in the least squares sense, with the AR coefficients constrained to satisfy the L-D recursion	Minimizes the forward prediction error in the least squares sense	Minimizes the forward and backward prediction errors in the least squares sense	Minimizes the forward prediction error in the least squares sense (also called “autocorrelation method”)
<b>Advantages</b>	Always produces a stable model			Always produces a stable model

# Burg AR Estimator

	<b>Burg AR Estimator</b>	<b>Covariance AR Estimator</b>	<b>Modified Covariance AR Estimator</b>	<b>Yule-Walker AR Estimator</b>
<b>Disadvantages</b>		May produce unstable models	May produce unstable models	Performs relatively poorly for short data records
<b>Conditions for Nonsingularity</b>		Order must be less than or equal to half the input frame size	Order must be less than or equal to 2/3 the input frame size	Because of the biased estimate, the autocorrelation matrix is guaranteed to positive-definite, hence nonsingular

# Burg AR Estimator

---



## Dialog Box

### Output(s)

The realization to output, model coefficients, reflection coefficients, or both.

### Inherit estimation order from input dimensions

When selected, sets the estimation order  $p$  to one less than the length of the input vector.

### Estimation order

The order of the AR model,  $p$ . This parameter is enabled when you do not select **Inherit estimation order from input dimensions**.

## References

Kay, S. M. *Modern Spectral Estimation: Theory and Application*. Englewood Cliffs, NJ: Prentice-Hall, 1988.

Marple, S. L., Jr., *Digital Spectral Analysis with Applications*. Englewood Cliffs, NJ: Prentice-Hall, 1987.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
A	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
G	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

## See Also

Burg Method	DSP System Toolbox
Covariance AR Estimator	DSP System Toolbox
Modified Covariance AR Estimator	DSP System Toolbox
Yule-Walker AR Estimator	DSP System Toolbox
arburg	Signal Processing Toolbox


# Burg Method

---

**Purpose** Power spectral density estimate using Burg method

**Library** Estimation / Power Spectrum Estimation  
dspsect3

## Description



The Burg Method block estimates the power spectral density (PSD) of the input frame using the Burg method. This method fits an autoregressive (AR) model to the signal by minimizing (least squares) the forward and backward prediction errors. Such minimization occurs with the AR parameters constrained to satisfy the Levinson-Durbin recursion.

The input is a sample-based vector (row, column, or 1-D) or frame-based vector (column only). This input represents a frame of consecutive time samples from a single-channel signal. The block outputs a column vector containing the estimate of the power spectral density of the signal at  $N_{fft}$  equally spaced frequency points. The frequency points are in the range  $[0, F_s)$ , where  $F_s$  is the sampling frequency of the signal.

When you select the **Inherit estimation order from input dimensions** parameter, the order of the all-pole model is one less than the input frame size. Otherwise, the **Estimation order** parameter specifies the order. The block computes the spectrum from the FFT of the estimated AR model parameters.

Selecting the **Inherit FFT length from estimation order** parameter specifies that  $N_{fft}$  is one greater than the estimation order. Clearing the **Inherit FFT length from estimation order** check box, allows you to use the **FFT length** parameter to specify  $N_{fft}$  as a power of 2. The block zero-pads or wraps the input to  $N_{fft}$  before computing the FFT. The output is always sample based.

When you select the **Inherit sample time from input** check box, the block computes the frequency data from the sample period of the input signal. For the block to produce valid output, the following conditions must hold:

- The input to the block is the original signal, with no samples added or deleted (by insertion of zeros, for example).
- The sample period of the time-domain signal in the simulation equals the sample period of the original time series.

If these conditions do not hold, clear the **Inherit sample time from input** check box. You can then specify a sample time using the **Sample time of original time series** parameter.

The Burg Method and Yule-Walker Method blocks return similar results for large frame sizes. The following table compares the features of the Burg Method block to the Covariance Method, Modified Covariance Method, and Yule-Walker Method blocks.

	<b>Burg</b>	<b>Covariance</b>	<b>Modified Covariance</b>	<b>Yule-Walker</b>
<b>Characteristics</b>	Does not apply window to data	Does not apply window to data	Does not apply window to data	Applies window to data
	Minimizes the forward and backward prediction errors in the least squares sense, with the AR coefficients constrained to satisfy the L-D recursion	Minimizes the forward prediction error in the least squares sense	Minimizes the forward and backward prediction errors in the least squares sense	Minimizes the forward prediction error in the least squares sense (also called <i>autocorrelation method</i> )

# Burg Method


	<b>Burg</b>	<b>Covariance</b>	<b>Modified Covariance</b>	<b>Yule-Walker</b>
<b>Advantages</b>	High resolution for short data records	Better resolution than Y-W for short data records (more accurate estimates)	High resolution for short data records	Performs as well as other methods for large data records
	Always produces a stable model	Able to extract frequencies from data consisting of p or more pure sinusoids	Able to extract frequencies from data consisting of p or more pure sinusoids Does not suffer spectral line-splitting	Always produces a stable model
<b>Disadvantages</b>	Peak locations highly dependent on initial phase	May produce unstable models	May produce unstable models	Performs relatively poorly for short data records
	May suffer spectral line-splitting for sinusoids in noise, or when order is very large	Frequency bias for estimates of sinusoids in noise	Peak locations slightly dependent on initial phase	Frequency bias for estimates of sinusoids in noise

	<b>Burg</b>	<b>Covariance</b>	<b>Modified Covariance</b>	<b>Yule-Walker</b>
	Frequency bias for estimates of sinusoids in noise		Minor frequency bias for estimates of sinusoids in noise	
<b>Conditions for Nonsingularity</b>		Order must be less than or equal to half the input frame size	Order must be less than or equal to 2/3 the input frame size	Because of the biased estimate, the autocorrelation matrix is guaranteed to be positive-definite, hence nonsingular

## Examples

The `dspsacomp` example compares the Burg method with several other spectral estimation methods.

# Burg Method



## Dialog Box

### **Inherit estimation order from input dimensions**

Selecting this check box sets the estimation order to one less than the length of the input vector.

### **Estimation order**

The order of the AR model. This parameter becomes visible only when you clear the **Inherit estimation order from input dimensions** check box.

### **Inherit FFT length from estimation order**

When selected, the FFT length is one greater than the estimation order. To specify the number of points on which to perform the FFT, clear the **Inherit FFT length from estimation order** check box. You can then specify a power-of-two FFT length using the **FFT length** parameter.

## FFT length

Enter the number of data points on which to perform the FFT,  $N_{fft}$ . When  $N_{fft}$  is larger than the input frame size, the block zero-pads each frame as needed. When  $N_{fft}$  is smaller than the input frame size, the block wraps each frame as needed. This parameter becomes visible only when you clear the **Inherit FFT length from input dimensions** check box.

## Inherit sample time from input

If you select the **Inherit sample time from input** check box, the block computes the frequency data from the sample period of the input signal. For the block to produce valid output, the following conditions must hold:

- The input to the block is the original signal, with no samples added or deleted (by insertion of zeros, for example).
- The sample period of the time-domain signal in the simulation equals the sample period of the original time series.

If these conditions do not hold, clear the **Inherit sample time from input** check box. You can then specify a sample time using the **Sample time of original time series** parameter.

## Sample time of original time series

Specify the sample time of the original time-domain signal. This parameter becomes visible only when you clear the **Inherit sample time from input** check box.

## References

Kay, S. M. *Modern Spectral Estimation: Theory and Application*. Englewood Cliffs, NJ: Prentice-Hall, 1988.

Orfanidis, S. J. *Introduction to Signal Processing*. Englewood Cliffs, NJ: Prentice-Hall, 1995.

Orfanidis, S. J. *Optimum Signal Processing: An Introduction*. 2nd ed. New York, NY: Macmillan, 1985.

# Burg Method

---

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

## See Also

Burg AR Estimator	DSP System Toolbox
Covariance Method	DSP System Toolbox
Modified Covariance Method	DSP System Toolbox
Short-Time FFT	DSP System Toolbox
Yule-Walker Method	DSP System Toolbox
spectrum.burg	Signal Processing Toolbox

See “Spectral Analysis” for related information.

## Purpose

Error when input signal does or does not match selected attributes exactly

## Library

Signal Management / Signal Attributes  
dspsigattribs

## Description



The Check Signal Attributes block terminates the simulation with an error when the input characteristics differ from the characteristics you specify in the block parameters.

When you set **Error when input** to `Does not match attributes exactly`, the block generates an error when the input fails to match *any* of the specified attributes. Only signals that possess *all* of the specified attributes propagate to the output unaltered and do not cause the block to generate an error.

When you set **Error when input** to `Matches attributes exactly`, the block generates an error only when the input possesses *all* specified attributes. Signals that do not possess *all* of the specified attributes propagate to the output unaltered, and do not cause the block to generate an error.

### Signal Attributes

The Check Signal Attributes block can test for up to five different signal attributes, as specified by the following parameters. When you select `Ignore` for any parameter, the block does not check the signal for the corresponding attribute. For example, when you set **Complexity** to `Ignore`, neither real nor complex inputs cause the block to generate an error. The attributes are:

- **Complexity**

Check whether the input is real or complex. You can display this information in a model by attaching a Probe block with **Probe complex signal** selected. Alternatively, you can select **Port Data Types** from the **Format > Port/Signal Displays** menu.

- **Frame status**

# Check Signal Attributes

Check whether the signal is frame based or sample based. The Simulink environment displays sample-based signals using a single line and frame-based signals using a double line.

- **Dimensionality**

Check the dimensionality of the input for compliance or noncompliance with the attributes in the subordinate **Dimension** menu. See the following table.  $M$  and  $N$  are positive integers unless otherwise indicated.

<b>Dimensions</b>	<b>Is...</b>	<b>Is not...</b>
1-D	1-D vector, 1-D scalar	$M$ -by- $N$ matrix, 1-by- $N$ matrix (row vector), $M$ -by-1 matrix (column vector), 1-by-1 matrix (2-D scalar)
2-D	$M$ -by- $N$ matrix, 1-by- $N$ matrix (row vector), $M$ -by-1 matrix (column vector), 1-by-1 matrix (2-D scalar)	1-D vector, 1-D scalar
Scalar (1-D or 2-D)	1-D scalar, 1-by-1 matrix (2-D scalar)	1-D vector with length $>1$ , $M$ -by- $N$ matrix with $M>1$ and/or $N>1$
Vector (1-D or 2-D)	1-D vector, 1-D scalar, 1-by- $N$ matrix (row vector), $M$ -by-1 matrix (column vector), 1-by-1 matrix (2-D scalar) Vector (1-D or 2-D) or scalar	$M$ -by- $N$ matrix with $M>1$ and $N>1$
Row Vector (2-D)	1-by- $N$ matrix (row vector), 1-by-1 matrix (2-D scalar) Row vector (2-D) or scalar	1-D vector, 1-D scalar, $M$ -by- $N$ matrix with $M>1$
Column Vector (2-D)	$M$ -by-1 matrix (column vector), 1-by-1 matrix (2-D scalar) Column vector (2-D) or scalar	1-D vector, 1-D scalar, $M$ -by- $N$ matrix with $N>1$

Dimensions	Is...	Is not...
Full matrix	$M$ -by- $N$ matrix with $M > 1$ and $N > 1$	1-D vector, 1-D scalar, 1-by- $N$ matrix (row vector), $M$ -by-1 matrix (column vector), 1-by-1 matrix (2-D scalar)
Square matrix	$M$ -by- $N$ matrix with $M = N$ , 1-D scalar, 1-by-1 matrix (2-D scalar)	$M$ -by- $N$ matrix with $M \neq N$ , 1-D vector, 1-by- $N$ matrix (row vector), $M$ -by-1 matrix (column vector)

When you select **Signal Dimensions** from the **Format > Port/Signal Displays** menu, Simulink displays the size of a 1-D vector signal as an unbracketed integer, and displays the dimension of a 2-D signal as a pair of bracketed integers, [MxN]. Simulink *does not display* any size information for a 1-D or 2-D scalar signal. You can also display dimension information for a signal in a model by attaching a Probe block with **Probe signal dimensions** selected.

- **Data type**

Check the signal data type for compliance (Is . . .) or noncompliance (Is not . . .) with the attributes in the subordinate **General data type** menu. See the following table. You can individually select any of the specific data types listed in the Is . . . column from the subordinate **Specific data type** menu.

## Check Signal Attributes

General Data Type	Is...	Is not...
Boolean	boolean	single, double, uint8, int8, uint16, int16, uint32, int32, fixed point, enumerated
Enumerated	A user-defined enumerated data type. See “Data Types” in the Simulink documentation.	boolean, single, double, uint8, int8, uint16, int16, uint32, int32, fixed point
Floating point	single, double	boolean, uint8, int8, uint16, int16, uint32, int32, fixed point, enumerated
Floating point or Boolean	single, double, boolean	uint8, int8, uint16, int16, uint32, int32, fixed point, enumerated
Fixed point	fixed point, uint8, int8, uint16, int16, uint32, int32	boolean, single, double, enumerated
Integer	Signed integer int8, int16, int32 Unsigned integer uint8, uint16, uint32	boolean, single, double, fixed point, enumerated

To display data type information, in your model window, from the **Format** menu, point to **Port/Signal Displays** and select **Port Data Types**.


- **Sample time**

Check whether the signal is discrete time or continuous time. When you select **Colors** from the **Format > Sample Time Display** menu, Simulink displays continuous-time signal lines in black or grey and discrete-time signal lines in colors corresponding to the relative rate.

When you attach a Probe block with **Probe sample time** enabled to a continuous-time signal, the block icon displays the string **Ts: [0 To]**, where **To** is the sample time offset. Valid values of **To** for continuous-time signals are 0 and 1. When **To** is 0, updates occur at every major and minor time step. When **To** is 1, updates occur only at major time steps and the sample time is *fixed in minor time step*.

When you attach a Probe block with **Probe sample time** enabled to a discrete-time signal, the block icon displays the string **Ts: [Ts To]** for sample-based signals, and **Tf: [Tf To]** for frame-based signals. **Ts** and **Tf** are the positive sample period and frame period, respectively. **To** is the offset, such that  $0 \leq \text{offset} < \text{period}$ . Frame-based signals are almost always discrete time.

# Check Signal Attributes



## Dialog Box

### Error when input

Specify whether the block generates an error when the input *does* or *does not* possess *all* of the required attributes.

### Complexity

Specify the complexity for which you want to check the input, Real or Complex. When you select Ignore from the list, the block does not check the complexity of the input.

### Frame status

Specify the frame status for which you want to check the input, Sample-based or Frame-based. When you select Ignore from the list, the block does not check the frame status of the input.

## **Dimensionality**

Specify whether you want to check the input for compliance or noncompliance with the attributes in the subordinate **Dimensions** menu. When you select Ignore from the list, the block does not check the dimensionality of the input.

## **Dimensions**

Specify the dimensions for which you want to check the input. This parameter is only visible when you set the **Dimensionality** parameter to Is... or Is not....

## **Data type**

Specifies whether you want to check the input for compliance or noncompliance with the attributes in the subordinate **General data type** menu. When you select Ignore from the list, the block does not check the input data type.

## **General data type**

Specify the general data type for which you want to check the input. This parameter is only visible when you set the **Data type** to Is... or Is not....

## **Specific floating-point**

Specify the floating-point data type for which you want to check the input. This parameter is only visible when you set the **General data type** to Floating-point or Floating-point or boolean.

## **Specific fixed-point**

Specify the fixed-point data type for which you want to check the input. This parameter is only visible when you set the **General data type** to Fixed-point.

## **Specific integer**

Specify the integer data type for which you want to check the input. This parameter is only visible when you set the **General data type** to Integer.

# Check Signal Attributes

---

## Sample time

Specify the sample time for which you want to check the input, Discrete or Continuous. When you select Ignore from the list, the block does not check the sample time of the input.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8, 16, and 32-bit signed integers</li><li>• 8, 16, and 32-bit unsigned integers</li><li>• Enumerated</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8, 16, and 32-bit signed integers</li><li>• 8, 16, and 32-bit unsigned integers</li><li>• Enumerated</li></ul>

## See Also

Buffer	DSP System Toolbox
Convert 1-D to 2-D	DSP System Toolbox
Convert 2-D to 1-D	DSP System Toolbox
Data Type Conversion	Simulink

Frame Status Conversion  
(Obsolete)

DSP System Toolbox

Inherit Complexity

DSP System Toolbox

Probe

Simulink

Reshape

Simulink

Submatrix

DSP System Toolbox


# Chirp

---

**Purpose** Generate swept-frequency cosine (chirp) signal

**Library** Sources  
dspsrcs4

## Description



The Chirp block outputs a swept-frequency cosine (chirp) signal with unity amplitude and continuous phase. To specify the desired output chirp signal, you must define its instantaneous frequency function, also known as the output frequency sweep. The frequency sweep can be linear, quadratic, or logarithmic, and repeats once every **Sweep time** by default. See other sections of this reference page for more details about the block.

## Sections of This Reference Page

- Variables Used in This Reference Page on page 2-201
- “Setting the Output Frame Status” on page 2-201
- “Shaping the Frequency Sweep by Setting Frequency Sweep and Sweep Mode” on page 2-202
- “Unidirectional and Bidirectional Sweep Modes” on page 2-203
- “Setting Instantaneous Frequency Sweep Values” on page 2-204
- “Block Computation Methods” on page 2-205
- “Cautions Regarding the Swept Cosine Sweep” on page 2-208
- “Dialog Box” on page 2-210
- “Examples” on page 2-212
- “Supported Data Types” on page 2-223
- “See Also” on page 2-223

### Variables Used in This Reference Page

$f_0$	<b>Initial frequency</b> parameter (Hz)
$f_i(t_g)$	<b>Target frequency</b> parameter (Hz)
$t_g$	<b>Target time</b> parameter (seconds)
$T_{sw}$	<b>Sweep time</b> parameter (seconds)
$\phi_0$	<b>Initial phase</b> parameter (radians)
$\psi(t)$	Phase of the chirp signal (radians)
$f_i(t)$	User-specified output instantaneous frequency function (Hz); user-specified sweep
$f_{i(actual)}(t)$	Actual output instantaneous frequency function (Hz); actual output sweep
$y_{chirp}(t)$	Output chirp function

### Setting the Output Frame Status

Use **Samples per frame** parameter to set the block's output frame status, as summarized in the following table. The **Sample time** parameter sets the sample time of both sample- and frame-based outputs.

<b>Setting of Samples Per Frame Parameter</b>	<b>Output Frame Status</b>
1	Sample based
n (any integer greater than 1)	Frame based, frame size n

## Shaping the Frequency Sweep by Setting Frequency Sweep and Sweep Mode

The basic shape of the output instantaneous frequency sweep,  $f_i(t)$ , is set by the **Frequency sweep** and **Sweep mode** parameters, described in the following table.


Parameters for Setting Sweep Shape	Possible Setting	Parameter Description
Frequency sweep	Linear Quadratic Logarithmic Swept cosine	Determines whether the sweep frequencies vary linearly, quadratically, or logarithmically. Linear and swept cosine sweeps both vary linearly.
Sweep mode	Unidirectional Bidirectional	Determines whether the sweep is unidirectional or bidirectional. For details, see “Unidirectional and Bidirectional Sweep Modes” on page 2-203

The following diagram illustrates the possible shapes of the frequency sweep that you can obtain by setting the **Frequency sweep** and **Sweep mode** parameters.

## Possible Shapes of the Output Instantaneous Frequency Sweep

### Swept Cosine and Linear Sweeps

### Quadratic and Logarithmic Sweeps Logarithmic sweeps cannot be negative.



For information on how to set the frequency values in your sweep, see “Setting Instantaneous Frequency Sweep Values” on page 2-204.

### Unidirectional and Bidirectional Sweep Modes


The **Sweep mode** parameter determines whether your sweep is unidirectional or bidirectional, which affects the shape of your output frequency sweep (see “Shaping the Frequency Sweep by Setting Frequency Sweep and Sweep Mode” on page 2-202). The following table describes the characteristics of unidirectional and bidirectional sweeps.

# Chirp


Sweep Mode Parameter Settings	Sweep Characteristics
Unidirectional	<ul style="list-style-type: none"> <li>• Lasts for one <b>Sweep time</b>, <math>T_{sw}</math></li> <li>• Repeats once every <math>T_{sw}</math></li> </ul>
Bidirectional	<ul style="list-style-type: none"> <li>• Lasts for twice the <b>Sweep time</b>, <math>2 * T_{sw}</math></li> <li>• Repeats once every <math>2 * T_{sw}</math></li> <li>• First half is identical to its unidirectional counterpart.</li> <li>• Second half is a mirror image of the first half.</li> </ul>

The following diagram illustrates a linear sweep in both sweep modes. For information on setting the frequency values in your sweep, see “Setting Instantaneous Frequency Sweep Values” on page 2-204.

**Unidirectional Linear Sweep**



**Bidirectional Linear Sweep**



## Setting Instantaneous Frequency Sweep Values

Set the following parameters to tune the frequency values of your output frequency sweep.

- **Initial frequency** (Hz),  $f_0$
- **Target frequency** (Hz),  $f_i(t_g)$
- **Target time** (seconds),  $t_g$

The following table summarizes the sweep values at specific times for all **Frequency sweep** settings. For information on the formulas used to compute sweep values at other times, see “Block Computation Methods” on page 2-205.

**Instantaneous Frequency Sweep Values**

<b>Frequency Sweep</b>	<b>Sweep Value at <math>t = 0</math></b>	<b>Sweep Value at <math>t = t_g</math></b>	<b>Time when Sweep Value Is Target Frequency, <math>f_i(t_g)</math></b>
Linear	$f_0$	$f_i(t_g)$	$t_g$
Quadratic	$f_0$	$f_i(t_g)$	$t_g$
Logarithmic	$f_0$	$f_i(t_g)$	$t_g$
Swept cosine	$f_0$	$2f_i(t_g) - f_0$	$t_g/2$

**Block Computation Methods**

The Chirp block uses one of two formulas to compute the block output, depending on the **Frequency Sweep** parameter setting. For details, see the following sections:

- “Equations for Output Computation” on page 2-206
- “Output Computation Method for Linear, Quadratic, and Logarithmic Frequency Sweeps” on page 2-207
- “Output Computation Method for Swept Cosine Frequency Sweep” on page 2-208

## Equations for Output Computation

The following table shows the equations used by the block to compute the user-specified output frequency sweep,  $f_i(t)$ , the block output,  $y_{chirp}(t)$ , and the actual output frequency sweep,  $f_{i(actual)}(t)$ . The only time the user-specified sweep is not the actual output sweep is when the **Frequency sweep** parameter is set to Swept cosine.

---

**Note** The following equations apply only to unidirectional sweeps in which  $f_i(0) < f_i(t_g)$ . To derive equations for other cases, you might find it helpful to examine the following table and the diagram in “Shaping the Frequency Sweep by Setting Frequency Sweep and Sweep Mode” on page 2-202.

---

The table below contains the following variables:

- $f_i(t)$  — the user-specified frequency sweep
- $f_{i(actual)}(t)$  — the actual output frequency sweep, usually equal to  $f_i(t)$
- $y(t)$  — the Chirp block output
- $\psi(t)$  — the phase of the chirp signal, where  $\psi(0) = 0$ , and  $2\pi f_i(t)$  is the derivative of the phase

$$f_i(t) = \frac{1}{2\pi} \cdot \frac{d\psi(t)}{dt}$$

- $\phi_0$  — the **Initial phase** parameter value, where  $y_{chirp}(0) = \cos(\phi_0)$

## Equations Used by the Chirp Block for Unidirectional Positive Sweeps

Frequency Sweep	Block Output Chirp Signal	User-Specified Frequency Sweep, $f_i(t)$	$\beta$	Actual Frequency Sweep, $f_{i(actual)}(t)$
Linear	$y(t) = \cos(\psi(t) + \phi_0)$	$f_i(t) = f_0 + \beta t$	$\beta = \frac{f_i(t_g) - f_0}{t_g}$	$f_{i(actual)}(t) = f_i(t)$
Quadratic	Same as Linear	$f_i(t) = f_0 + \beta t^2$	$\beta = \frac{f_i(t_g) - f_0}{t_g^2}$	$f_{i(actual)}(t) = f_i(t)$
Logarithmic	Same as Linear	$F_i(t) = f_0 \left( \frac{f_i(t_g)}{f_0} \right)^{\frac{t}{t_g}}$ Where $f_i(t_g) > f_0 > 0$	N/A	$f_{i(actual)}(t) = f_i(t)$
Swept cosine	$y(t) = \cos(2\pi f_i(t)t + \phi_0)$	Same as Linear	Same as Linear	$f_{i(actual)}(t) = f_i(t) + \beta t$

### Output Computation Method for Linear, Quadratic, and Logarithmic Frequency Sweeps

The derivative of the phase of a chirp function gives the instantaneous frequency of the chirp function. The Chirp block uses this principle to calculate the chirp output when the **Frequency Sweep** parameter is set to Linear, Quadratic, or Logarithmic.

$$y_{chirp}(t) = \cos(\psi(t) + \phi_0)$$

Linear, quadratic, or logarithmic chirp signal with phase  $\psi(t)$

$$f_i(t) = \frac{1}{2\pi} \cdot \frac{d\psi(t)}{dt}$$

Phase derivative is instantaneous frequency

For instance, if you want a chirp signal with a linear instantaneous frequency sweep, you should set the **Frequency Sweep** parameter to

Linear, and tune the linear sweep values by setting other parameters appropriately. The block outputs a chirp signal, the phase derivative of which is the specified linear sweep. This ensures that the instantaneous frequency of the output is the linear sweep you desired. For equations describing the linear, quadratic, and logarithmic sweeps, see “Equations for Output Computation” on page 2-206.

## Output Computation Method for Swept Cosine Frequency Sweep

To generate the swept cosine chirp signal, the block sets the swept cosine chirp output as follows.

$$y_{chirp}(t) = \cos(\psi(t) + \phi_0) = \cos(2\pi f_i(t)t + \phi_0)$$

Swept cosine chirp output (Instantaneous frequency equation, shown above, does not hold.)

Note that the instantaneous frequency equation, shown above, does not hold for the swept cosine chirp, so the user-defined frequency sweep,  $f_i(t)$ , is not the actual output frequency sweep,  $f_{i(actual)}(t)$ , of the swept cosine chirp. Thus, the swept cosine output might not behave as you expect. To learn more about swept cosine chirp behavior, see “Cautions Regarding the Swept Cosine Sweep” on page 2-208 and “Equations for Output Computation” on page 2-206.

## Cautions Regarding the Swept Cosine Sweep

When you want a linearly swept chirp signal, we recommend you use a linear frequency sweep. Though a swept cosine frequency sweep also yields a linearly swept chirp signal, the output might have unexpected frequency content. For details, see the following two sections.

## Swept Cosine Instantaneous Output Frequency at the Target Time is not the Target Frequency


The swept cosine sweep value at the **Target time** is not necessarily the **Target frequency**. This is because the user-specified sweep is not the

actual frequency sweep of the swept cosine output, as noted in “Output Computation Method for Swept Cosine Frequency Sweep” on page 2-208. See the table Instantaneous Frequency Sweep Values on page 2-205 for the actual value of the swept cosine sweep at the **Target time**.

### **Swept Cosine Output Frequency Content May Greatly Exceed Frequencies in the Sweep**

In **Swept cosine** mode, you should not set the parameters so that  $1/T_{sw}$  is very large compared to the values of the **Initial frequency** and **Target frequency** parameters. In such cases, the actual frequency content of the swept cosine sweep might be closer to  $1/T_{sw}$ , far exceeding the **Initial frequency** and **Target frequency** parameter values.

# Chirp



## Dialog Box

### Frequency sweep

The type of output instantaneous frequency sweep,  $f_i(t)$ : Linear, Logarithmic, Quadratic, or Swept cosine.

**Sweep mode**

The directionality of the chirp signal: Unidirectional or Bidirectional.

**Initial frequency (Hz)**

For Linear, Quadratic, and Swept cosine sweeps, the initial frequency,  $f_0$ , of the output chirp signal. For Logarithmic sweeps, **Initial frequency** is one less than the actual initial frequency of the sweep. Also, when the sweep is Logarithmic, you must set the **Initial frequency** to be less than the **Target frequency**. Tunable.

**Target frequency (Hz)**

For Linear, Quadratic, and Logarithmic sweeps, the instantaneous frequency,  $f_i(t_g)$ , of the output at the **Target time**,  $t_g$ . For a Swept cosine sweep, **Target frequency** is the instantaneous frequency of the output at half the **Target time**,  $t_g/2$ . When **Frequency sweep** is Logarithmic, you must set the **Target frequency** to be greater than the **Initial frequency**. Tunable.

**Target time (s)**

For Linear, Quadratic, and Logarithmic sweeps, the time,  $t_g$ , at which the **Target frequency**,  $f_i(t_g)$ , is reached by the sweep. For a Swept cosine sweep, **Target time** is the time at which the sweep reaches  $2f_i(t_g) - f_0$ . You must set **Target time** to be *no greater than Sweep time*,  $T_{sw} \geq t_g$ . Tunable.

**Sweep time (s)**

In Unidirectional **Sweep mode**, the **Sweep time**,  $T_{sw}$ , is the period of the output frequency sweep. In Bidirectional **Sweep mode**, the **Sweep time** is half the period of the output frequency sweep. You must set **Sweep time** to be no less than **Target time**,  $T_{sw} \geq t_g$ . Tunable.

**Initial phase (rad)**

The phase,  $\phi_0$ , of the cosine output at  $t=0$ ;  $y_{chirp}(t) = \cos(\phi_0)$ . Tunable.

## Sample time

The sample period,  $T_s$ , of the output. The output frame period is  $M_o * T_s$ .

## Samples per frame

The number of samples,  $M_o$ , to buffer into each output frame. When the value of this parameter is 1, the block outputs a sample-based signal.

## Output data type

The data type of the output, single-precision or double-precision.

## Examples

The first few examples demonstrate how to use the Chirp block's main parameters, how to view the output in the time domain, and how to view the output spectrogram:

- “Example 1: Setting a Final Frequency Value for Unidirectional Sweeps” on page 2-212
- “Example 2: Bidirectional Sweeps” on page 2-216
- “Example 3: When Sweep Time is Greater Than Target Time” on page 2-218

Examples 4 and 5 illustrate Chirp block settings that might produce unexpected outputs:


- “Example 4: Output Sweep with Negative Frequencies” on page 2-220
- “Example 5: Output Sweep with Frequencies Greater Than Half the Sampling Frequency” on page 2-221

### **Example 1: Setting a Final Frequency Value for Unidirectional Sweeps**

Often times, you might want a unidirectional sweep for which you know the initial and final frequency values. You can specify the final frequency of a unidirectional sweep by setting **Target time** equal to **Sweep time**, in which case the **Target frequency** becomes the final frequency in the sweep. The following model demonstrates this method.


This technique might not work for swept cosine sweeps. For details, see “Cautions Regarding the Swept Cosine Sweep” on page 2-208.

Open the Example 1 model by typing `ex_chirp_ref` at the MATLAB command line. You can also rebuild the model yourself; see the following list for model parameter settings (leave unlisted parameters in their default states).




Since **Target time** is set to equal **Sweep time** (1 second), the **Target frequency** (25 Hz) is the final frequency of the unidirectional sweep. Run your model to see the time domain output:

# Chirp



Type the following command to view the chirp output spectrogram:

```
spectrogram(dsp_examples_yout,hamming(128),...  
            110,[0:.01:40],400)
```



### Chirp Block Parameters for Example 1

<b>Frequency sweep</b>	Linear
<b>Sweep mode</b>	Unidirectional
<b>Initial frequency</b>	0
<b>Target frequency</b>	25
<b>Target time</b>	1
<b>Sweep time</b>	1


<b>Initial phase</b>	0
<b>Sample time</b>	1/400
<b>Samples per frame</b>	400
<b>Vector Scope Block Parameters for Example 1</b>	
<b>Input domain</b>	Time
<b>Time display span</b>	6
<b>Signal To Workspace Block Parameters for Example 1</b>	
<b>Variable name</b>	dsp_examples_yout
<b>Configuration Dialog Parameters for Example 1</b>	
<b>Stop time</b>	5

## Example 2: Bidirectional Sweeps

Change the **Sweep mode** parameter in the Example 1 model to **Bidirectional**, and leave all other parameters the same to view the following bidirectional chirp. Note that in the bidirectional sweep, the period of the sweep is twice the **Sweep time** (2 seconds), whereas it was one **Sweep time** (1 second) for the unidirectional sweep in Example 1.

Open the Example 2 model by typing `ex_chirp_ref2` at the MATLAB command line.


Run your model to see the time domain output:



Type the following command to view the chirp output spectrogram:

```
spectrogram(dsp_examples_yout,hamming(128),...  
            110,[0:.01:40],400)
```

# Chirp




### Example 3: When Sweep Time is Greater Than Target Time

Setting **Sweep time** to 1.5 and leaving the rest of the parameters as in the Example 1 model gives the following output. The sweep still reaches the **Target frequency** (25 Hz) at the **Target time** (1 second), but since **Sweep time** is greater than **Target time**, the sweep continues on its linear path until one **Sweep time** (1.5 seconds) is traversed.

Unexpected behavior might arise when you set **Sweep time** greater than **Target time**; see “Example 4: Output Sweep with Negative Frequencies” on page 2-220 for details.

Open the Example 3 model by typing `ex_chirp_ref3` at the MATLAB command line.


Run your model to see the time domain output:



Type the following command to view the chirp output spectrogram:

```
spectrogram(dsp_examples_yout,hamming(128),...  
            110,[0:.01:40],400)
```

# Chirp




## Example 4: Output Sweep with Negative Frequencies

Modify the Example 1 model by changing **Sweep time** to 1.5, **Initial frequency** to 25, and **Target frequency** to 0. *The output chirp of this example might not behave as you expect* because the sweep contains negative frequencies between 1 and 1.5 seconds. The sweep reaches the **Target frequency** of 0 Hz at one second, then continues on its negative slope, taking on negative frequency values until it traverses one **Sweep time** (1.5 seconds).

Open the Example 4 model by typing `ex_chirp_ref4` at the MATLAB command line.

Run your model to see the time domain output:



### Example 5: Output Sweep with Frequencies Greater Than Half the Sampling Frequency


Modify the Example 1 model by changing the **Target frequency** parameter to 275. *The output chirp of this model might not behave as you expect* because the sweep contains frequencies greater than half the sampling frequency (200 Hz), which causes aliasing. If you unexpectedly get a chirp output with a spectrogram resembling the one following, your chirp's sweep might contain frequencies greater than half the sampling frequency.

Open the Example 5 model by typing `ex_chirp_ref5` at the MATLAB command line.

Run your model to see the time domain output:


# Chirp

---



Type the following command to view the chirp output spectrogram:

```
spectrogram(dsp_examples_yout,hamming(64),...  
            60,256,400)
```



## Supported Data Types

- Double-precision floating point
- Single-precision floating point

## See Also

Signal From Workspace	DSP System Toolbox
Signal Generator	Simulink

# Chirp

---

Sine Wave

chirp

spectrogram

DSP System Toolbox

Signal Processing Toolbox

Signal Processing Toolbox


## Purpose

Factor square Hermitian positive definite matrix into triangular components

## Library

Math Functions / Matrices and Linear Algebra / Matrix Factorizations  
dspfactors

## Description



The Cholesky Factorization block uniquely factors the square Hermitian positive definite input matrix  $S$  as


$$S = LL^*$$

where  $L$  is a lower triangular square matrix with positive diagonal elements and  $L^*$  is the Hermitian (complex conjugate) transpose of  $L$ . The block outputs a matrix with lower triangle elements from  $L$  and upper triangle elements from  $L^*$ . The output is not in the same form as the output of the MATLAB `chol` function. In order to convert the output of the Cholesky Factorization block to the MATLAB form, use the following equation:

$$R = \text{triu}(LL');$$

Here,  $LL'$  is the output of the Cholesky Factorization block. Due to roundoff error, these equations do not produce a result that is exactly the same as the MATLAB result.

# Cholesky Factorization



## Block Output Composed of $L$ and $L'$

### Input Requirements for Valid Output

The block output is valid only when its input has the following characteristics:

- Hermitian — The block does *not* check whether the input is Hermitian; it uses only the diagonal and upper triangle of the input to compute the output.
- Real-valued diagonal entries — The block disregards any imaginary component of the input's diagonal entries.
- Positive definite — Set the block to notify you when the input is not positive definite as described in “Response to Nonpositive Definite Input” on page 2-226.

### Response to Nonpositive Definite Input

To generate a valid output, the block algorithm requires a positive definite input (see “Input Requirements for Valid Output” on page 2-226). Set the **Non-positive definite input** parameter to determine how the block responds to a nonpositive definite input:

- Ignore — Proceed with the computation and *do not* issue an alert. The output is *not* a valid factorization. A partial factorization will be present in the upper left corner of the output.

- **Warning** — Display a warning message in the MATLAB Command Window, and continue the simulation. The output is *not* a valid factorization. A partial factorization will be present in the upper left corner of the output.
- **Error** — Display an error dialog and terminate the simulation.


---

**Note** The **Non-positive definite input** parameter is a diagnostic parameter. Like all diagnostic parameters on the Configuration Parameters dialog box, it is set to **Ignore** in the code generated for this block by Simulink Coder code generation software.

---

## Performance Comparisons with Other Blocks

Note that  $L$  and  $L^*$  share the same diagonal in the output matrix. Cholesky factorization requires half the computation of Gaussian elimination (LU decomposition), and is always stable.



## Dialog Box

### Non-positive definite input

Response to nonpositive definite matrix inputs: **Ignore**, **Warning**, or **Error**. See “Response to Nonpositive Definite Input” on page 2-226.

# Cholesky Factorization

---

## References

Golub, G. H., and C. F. Van Loan. *Matrix Computations*. 3rd ed. Baltimore, MD: Johns Hopkins University Press, 1996.

## Supported Data Types

Port	Supported Data Types
S	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
LL'	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

## See Also


Autocorrelation LPC	DSP System Toolbox
Cholesky Inverse	DSP System Toolbox
Cholesky Solver	DSP System Toolbox
LDL Factorization	DSP System Toolbox
LU Factorization	DSP System Toolbox
QR Factorization	DSP System Toolbox
chol	MATLAB

See “Matrix Factorizations” for related information.

**Purpose** Compute inverse of Hermitian positive definite matrix using Cholesky factorization

**Library** Math Functions / Matrices and Linear Algebra / Matrix Inverses  
dspinverses

## Description



The Cholesky Inverse block computes the inverse of the Hermitian positive definite input matrix  $S$  by performing Cholesky factorization.

$$S^{-1} = (LL^*)^{-1}$$

$L$  is a lower triangular square matrix with positive diagonal elements and  $L^*$  is the Hermitian (complex conjugate) transpose of  $L$ . Only the diagonal and upper triangle of the input matrix are used, and any imaginary component of the diagonal entries is disregarded. Cholesky factorization requires half the computation of Gaussian elimination (LU decomposition), and is always stable.

## Response to Nonpositive Definite Input

The algorithm requires that the input be Hermitian positive definite. When the input is not positive definite, the block reacts with the behavior specified by the **Non-positive definite input** parameter. The following options are available:


- **Ignore** — Proceed with the computation and *do not* issue an alert. The output is *not* a valid inverse.
- **Warning** — Display a warning message in the MATLAB Command Window, and continue the simulation. The output is *not* a valid inverse.
- **Error** — Display an error dialog box and terminate the simulation.

# Cholesky Inverse

---

**Note** The **Non-positive definite input** parameter is a diagnostic parameter. Like all diagnostic parameters on the Configuration Parameters dialog box, it is set to **Ignore** in the code generated for this block by Simulink Coder code generation software.

---



## Dialog Box

### Non-positive definite input

Response to nonpositive definite matrix inputs: **Ignore**, **Warning**, or **Error**. See “Response to Nonpositive Definite Input” on page 2-229.

## References

Golub, G. H., and C. F. Van Loan. *Matrix Computations*. 3rd ed. Baltimore, MD: Johns Hopkins University Press, 1996.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point

## See Also

Cholesky Factorization	DSP System Toolbox
Cholesky Solver	DSP System Toolbox
LDL Inverse	DSP System Toolbox

LU Inverse	DSP System Toolbox
Pseudoinverse	DSP System Toolbox
inv	MATLAB

See “Matrix Inverses” for related information.

# Cholesky Solver

---


## Purpose

Solve  $SX=B$  for  $X$  when  $S$  is square Hermitian positive definite matrix

## Library

Math Functions / Matrices and Linear Algebra / Linear System Solvers  
dspsolvers

## Description



The Cholesky Solver block solves the linear system  $SX=B$  by applying Cholesky factorization to input matrix at the  $S$  port, which must be square ( $M$ -by- $M$ ) and Hermitian positive definite. Only the diagonal and upper triangle of the matrix are used, and any imaginary component of the diagonal entries is disregarded. The input to the  $B$  port is the right side  $M$ -by- $N$  matrix,  $B$ . The  $M$ -by- $N$  output matrix  $X$  is the unique solution of the equations.

A length- $M$  vector input for right side  $B$  is treated as an  $M$ -by-1 matrix.

## Response to Nonpositive Definite Input

When the input is not positive definite, the block reacts with the behavior specified by the **Non-positive definite input** parameter. The following options are available:

- **Ignore** — Proceed with the computation and *do not* issue an alert. The output is *not* a valid solution.
- **Warning** — Proceed with the computation and display a warning message in the MATLAB Command Window. The output is *not* a valid solution.
- **Error** — Display an error dialog box and terminate the simulation.

---

**Note** The **Non-positive definite input** parameter is a diagnostic parameter. Like all diagnostic parameters on the Configuration Parameters dialog box, it is set to **Ignore** in the code generated for this block by Simulink Coder code generation software.

---

## Algorithm

Cholesky factorization uniquely factors the Hermitian positive definite input matrix  $S$  as

$$S = LL^*$$

where  $L$  is a lower triangular square matrix with positive diagonal elements.

The equation  $SX=B$  then becomes


$$LL^*X = B$$

which is solved for  $X$  by making the substitution  $Y = L^*X$ , and solving the following two triangular systems by forward and backward substitution, respectively.

$$LY = B$$

$$L^*X = Y$$

## Dialog Box



### Non-positive definite input

Response to nonpositive definite matrix inputs: Ignore, Warning, or Error. See “Response to Nonpositive Definite Input” on page 2-232.

# Cholesky Solver

---

## Supported Data Types

- Double-precision floating point
- Single-precision floating point

## See Also

Autocorrelation LPC	DSP System Toolbox
Cholesky Factorization	DSP System Toolbox
Cholesky Inverse	DSP System Toolbox
LDL Solver	DSP System Toolbox
LU Solver	DSP System Toolbox
QR Solver	DSP System Toolbox

`chol`                      MATLAB

See “Linear System Solvers” for related information.

**Purpose** Design CIC compensator

**Library** Filtering / Filter Designs  
dspfdesign

**Description** This block brings the filter design capabilities of the `filterbuilder` function to the Simulink environment.



**Dialog Box** See “CIC Compensator Filter Design Dialog Box — Main Pane” on page 7-696 for more information about the parameters of this block. The **Data Types** and **Code Generation** panes are not available for blocks in the DSP System Toolbox Filter Designs library.

# CIC Compensator

Function Block Parameters: CIC Compensator

CIC Compensator

Design a CIC compensating filter.

[View Filter Re](#)

Filter specifications

Order mode:  Order:

Filter Type:

Number of CIC sections:  Differential delay:

Frequency specifications

Frequency units:  Input Fs:

Fpass:  Fstop:

Magnitude specifications

Magnitude units:

Apass:  Astop:

Algorithm

Design method:

► Design options

Filter Implementation

Structure:

Use basic elements to enable filter customization

Input processing:

Use symbolic names for coefficients

2-236

- Magnitude response, phase response, and group delay in the frequency domain.
- Impulse response and step response in the time domain.
- Pole-zero information.

The tool also helps you evaluate filter performance by providing information about filter order, stability, and phase linearity. For more information on FVTool, see the Signal Processing Toolbox documentation.

## Filter Specifications

In this group, you specify your filter format, such as the filter order mode and the filter type.

### Filter order mode

Select either **Minimum** (the default) or **Specify** from the drop-down list. Selecting **Specify** enables the **Order** option (see the following sections) so you can enter the filter order.

### Filter type

Select **Single-rate**, **Decimator**, **Interpolator**, or **Sample-rate converter**. Your choice determines the type of filter as well as the design methods and structures that are available to implement your filter. By default, the block specifies a single-rate filter.

- Selecting **Decimator** or **Interpolator** activates the **Decimation Factor** or the **Interpolation Factor** options respectively.
- Selecting **Sample-rate converter** activates both factors.

### Order

Enter the filter order. This option is enabled only if **Specify** was selected for **Filter order mode**.

### Decimation Factor

Enter the decimation factor. This option is enabled only if the **Filter type** is set to **Decimator** or **Sample-rate converter**. The default value is 2.

# CIC Compensator

---

## Interpolation Factor

Enter the interpolation factor. This option is enabled only if the **Filter type** is set to Interpolator or Sample-rate converter. The default value is 2.

## Number of CIC sections

Specify the number of sections in the CIC filter for which you are designing this compensator. Select the number of sections from the drop-down list or enter the number.

## Differential Delay

Specify the differential delay of your target CIC filter. The default value is 1. Most CIC filters use 1 or 2.

## Frequency Specifications

The parameters in this group allow you to specify your filter response curve.

### Frequency Specifications

#### Frequency units

Use this parameter to specify whether your frequency settings are normalized or in absolute frequency. Select **Normalized (0 1)** to enter frequencies in normalized form. This behavior is the default. To enter frequencies in absolute values, select one of the frequency units from the drop-down list—Hz, kHz, MHz, or GHz. Selecting one of the unit options enables the **Input Fs** parameter.

#### Input Fs

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter input. When you provide an input sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is available when you select one of the frequency options from the **Frequency units** list.

#### Output Fs

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter output. When you

provide an output sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is available only when you design interpolators.

## **Fpass**

Enter the frequency at the end of the passband. Specify the value in either normalized frequency units or the absolute units you select in **Frequency units**.

## **Fstop**

Enter the frequency at the start of the stopband. Specify the value in either normalized frequency units or the absolute units you select in **Frequency units**.

## **Magnitude Specifications**

Parameters in this group specify the filter response in the passbands and stopbands.

### **Magnitude units**

Specify the units for any parameter you provide in magnitude specifications. From the drop-down list, select one of the following options:

- **Linear** — Specify the magnitude in linear units.
- **dB** — Specify the magnitude in decibels (default).
- **Squared** — Specify the magnitude in squared units.

### **Apass**

Enter the filter ripple allowed in the passband in the units you choose for **Magnitude units**, either linear or decibels

## **Algorithm**

The parameters in this group allow you to specify the design method and structure of your filter.

### **Design Method**

Lists the design methods available for the frequency and magnitude specifications you entered. When you change the

specifications for a filter, such as changing the impulse response, the methods available to design filters changes as well. The default method is Equiripple.

## Design Options

The options for each design are specific for each design method. This section does not present all of the available options for all designs and design methods. There are many more that you encounter as you select different design methods and filter specifications. The following options represent some of the most common ones available.

### Density factor

Density factor controls the density of the frequency grid over which the design method optimization evaluates your filter response function. The number of equally spaced points in the grid is the value you enter for **Density factor** times (filter order + 1).

Increasing the value creates a filter that more closely approximates an ideal equiripple filter but increases the time required to design the filter. The default value of 20 represents a reasonable trade between the accurate approximation to the ideal filter and the time to design the filter.

### Phase constraint

Specify the phase constraint of the filter as Linear, Maximum, or Minimum.

### Minimum order

When you select this parameter, the design method determines and design the minimum order filter to meet your specifications. Some filters do not provide this parameter. Select Any, Even, or Odd from the drop-down list to direct the design to be any minimum order, or minimum even order, or minimum odd order.

## Match Exactly

Specifies that the resulting filter design matches either the passband or stopband or both bands when you select passband or stopband or both from the drop-down list.

## Stopband Shape

Stopband shape lets you specify how the stopband changes with increasing frequency. Choose one of the following options:

- **Flat** — Specifies that the stopband is flat. The attenuation does not change as the frequency increases.
- **Linear** — Specifies that the stopband attenuation changes linearly as the frequency increases. Change the slope of the stopband by setting **Stopband decay**.
- **1/f** — Specifies that the stopband attenuation changes exponentially as the frequency increases, where  $f$  is the frequency. Set the power (exponent) for the decay in **Stopband decay**.

## Stopband Decay

When you set Stopband shape, Stopband decay specifies the amount of decay applied to the stopband. the following conditions apply to Stopband decay based on the value of Stopband Shape:

- When you set **Stopband shape** to **Flat**, **Stopband decay** has no affect on the stopband.
- When you set **Stopband shape** to **Linear**, enter the slope of the stopband in units of dB/rad/s. The block applies that slope to the stopband.
- When you set **Stopband shape** to **1/f**, enter a value for the exponent  $n$  in the relation  $(1/f)^n$  to define the stopband decay. The block applies the  $(1/f)^n$  relation to the stopband to result in an exponentially decreasing stopband attenuation.

## Filter Implementation

### Structure

For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter. By default, the filter uses direct-form structure.

### Use basic elements to enable filter customization

Select this check box to implement the filter as a subsystem of basic Simulink blocks. Clear the check box to implement the filter as a high-level subsystem. By default, this check box is cleared.

The high-level implementation provides better compatibility across various filter structures, especially filters that would contain algebraic loops when constructed using basic elements. On the other hand, using basic elements enables the following optimization parameters:

- **Optimize for zero gains** — Terminate chains that contain Gain blocks with a gain of zero.
- **Optimize for unit gains** — Remove Gain blocks that scale by a factor of one.
- **Optimize for delay chains** — Substitute delay chains made up of  $n$  unit delays with a single delay by  $n$ .
- **Optimize for negative gains** — Use subtraction in Sum blocks instead of negative gains in Gain blocks.

### Input processing

Specify how the block should process the input. The available options may vary depending on the settings of the **Filter Structure** and **Use basic elements for filter customization** parameters. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.

- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The Inherited (this choice will be removed see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

### Rate options

When the **Filter type** parameter specifies a multirate filter, select the rate processing rule for the block from following options:

- **Enforce single-rate processing** — When you select this option, the block maintains the sample rate of the input.
- **Allow multirate processing** — When you select this option, the block adjusts the rate at the output to accommodate an increased or reduced number of samples. To select this option, you must set the **Input processing** parameter to **Elements as channels (sample based)**.

### Use symbolic names for coefficients

Select this check box to enable the specification of coefficients using MATLAB variables. The available coefficient names differ depending on the filter structure. Using symbolic names allows tuning of filter coefficients in generated code. By default, this check box is cleared.

## Supported Data Types


Port	Supported Data Types
Input	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> </ul>
Output	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> </ul>

# CIC Decimation

**Purpose** Decimate signal using Cascaded Integrator-Comb filter

**Library** Filtering / Multirate Filters  
dspmlti4

## Description



The CIC Decimation block performs a sample rate decrease (decimation) on an input signal by an integer factor. Cascaded Integrator-Comb (CIC) filters are a class of linear phase FIR filters comprised of a comb part and an integrator part.

The transfer function of a CIC decimator filter is

$$H(z) = H_I^N(z)H_c^N(z) = \frac{(1 - z^{-RM})^N}{(1 - z^{-1})^N} = \left[ \sum_{k=0}^{RM-1} z^{-k} \right]^N$$

where

- $H_I$  is the transfer function of the integrator part of the filter.
- $H_C$  is the transfer function of the comb part of the filter.
- $N$  is the number of sections. The number of sections in a CIC filter is defined as the number of sections in either the comb part *or* the integrator part of the filter. This value does not represent the total number of sections throughout the entire filter.
- $R$  is the decimation factor.
- $M$  is the differential delay.


The CIC Decimation block requires a Simulink Fixed Point license. The block supports real and complex fixed-point inputs and treats each channel of a complex input as two real input channels.

## CIC Filter Structure

The filter structures supported by the CIC Decimation and CIC Interpolation blocks exactly match those created by the `mfilt.cicdecim`

and `mfilt.cicinterp` objects. You can create an `mfilt` object in any workspace and specify that object in the **Multirate filter variable** parameter of this block. Alternatively, you can set the **Coefficient source** to **Dialog parameters** and specify information about the CIC filter using the available block dialog parameters.

You can use this block to create the following CIC filter structure. This decimator has a latency of  $N$ , where  $N$  is the number of sections in either the comb or the integrator part of the filter.



## Examples

See GSM Digital Down Converter for an example using the CIC Decimation block.

## Dialog Box

### Coefficient Source

The CIC Decimation block can operate in two different modes. Select the mode in the **Coefficient source** group box. If you select

- **Dialog parameters**, you enter information about the filter such as structure and coefficients in the block mask.
- **Multirate filter object (MFILT)**, you specify the filter using an `mfilt` object.


Different items appear on the CIC Decimation block dialog depending on whether you select **Dialog parameters** or **Multirate filter object (MFILT)** in the **Coefficient source** group box. See the following sections for details:

- “Specify Filter Characteristics in Dialog” on page 2-246
- “Specify Multirate Filter Object” on page 2-250

# CIC Decimation

## Specify Filter Characteristics in Dialog

The **Main** pane of the CIC Decimation block dialog appears as follows when you select **Dialog parameters** in the **Coefficient source** group box.



## Decimation factor (R)

Specify the decimation factor of the filter.

## Differential delay (M)

Specify the differential delay of the comb part of the filter, M, as shown in the diagram in “CIC Filter Structure” on page 2-244.

## Number of sections (N)

Specify the number of filter sections. The number you specify determines the number of sections in either the comb part of the filter or the integrator part of the filter. This value does not represent the total number of sections in the comb and integrator parts combined.

## Data type specification mode

Choose how you specify the fixed-point word length and fraction length of the filter sections and/or output.

- **Full precision** — In this mode, the word and fraction lengths of the filter sections and outputs are automatically selected for you. All word lengths are set to

$$\text{word length} = \text{ceil}(N * \log_2(M * R)) + I$$

where

- I = input word length
- M = differential delay
- N = number of sections
- R = decimation factor

All fraction lengths are set to the input fraction length.

- **Minimum section word lengths** — In this mode, you specify the word length of the filter output in the **Output word length** parameter. The block automatically selects the word lengths of the filter sections and all fraction lengths such that each of the section word lengths is as small as possible. The

precision of each filter section is less than in Full precision mode, but the range of each section is preserved.

- **Specify word lengths** — In this mode you specify the word lengths of the filter sections and output in the **Section word lengths** and **Output word length** parameters. The block automatically selects fraction lengths for the filter sections and output such that the range of each section is preserved when the least significant bits are discarded.
- **Binary point scaling** — In this mode you fully specify the word and fraction lengths of the filter sections and output in the **Section word lengths**, **Section fraction lengths**, **Output word length**, and **Output fraction length** parameters.

## **Section word lengths**

Specify the word length, in bits, of the filter sections.

This parameter is only visible if **Specify word lengths** or **Binary point scaling** is selected for the **Data type specification mode** parameter.

## **Section fraction lengths**

Specify the fraction length of the filter sections.

This parameter is only visible if **Binary point scaling** is selected for the **Data type specification mode** parameter.

## **Output word length**

Specify the word length, in bits, of the filter output.

This parameter is only visible if you select **Minimum section word lengths**, **Specify word lengths**, or **Binary point scaling** for the **Data type specification mode** parameter.

## **Output fraction length**

Specify the fraction length of the filter output.

This parameter is only visible if **Binary point scaling** is selected for the **Data type specification mode** parameter.

## Rate options

Specify the rate processing rule for the block. You can select one of the following options:

- **Enforce single-rate processing** — When you select this option, the block performs frame-based processing and produces an output that has the same sample rate as the input. To decimate the signal while maintaining the input sample rate, the block decreases the output frame size. In this mode, the input column size must be a multiple of the decimation factor,  $R$ .
- **Allow multirate processing** — When you select this option, the block performs sample-based processing. In this mode, the block produces an output with a sample rate that is  $R$  times slower than the input sample rate.

---

**Note** The option `Inherit from input` (this choice will be removed - see release notes) will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## View filter response

This button opens the Filter Visualization Tool (`fvtool`) from the Signal Processing Toolbox product and displays the filter response of the filter defined in the block. For more information on FVTool, see the Signal Processing Toolbox documentation.

---


**Note** If you specify an `mfilt` object in the **Multirate filter variable** parameter, you must click the **Apply** button to apply the filter before using the **View filter response** button.

---

# CIC Decimation

## Specify Multirate Filter Object

The **Main** pane of the CIC Decimation block dialog appears as follows when you select **Multirate filter object (MFILT)** in the **Coefficient source** group box.



## Multirate filter variable

Specify the multirate filter object (`mfilt`) that you would like the block to implement. You can specify the `mfilt` object in one of three ways:

- You can fully specify the `mfilt` object in the block mask.
- You can enter the variable name of a `mfilt` object that is defined in any workspace.
- You can enter a variable name for a `mfilt` object that is not yet defined, as shown in the default value.

For more information on creating `mfilt` objects, see the `mfilt` function reference page.

## Rate options

Specify the rate processing rule for the block. You can select one of the following options:

- **Enforce single-rate processing** — When you select this option, the block performs frame-based processing and produces an output that has the same sample rate as the input. To decimate the signal while maintaining the input sample rate, the block decreases the output frame size. In this mode, the input column size must be a multiple of the decimation factor,  $R$ .
- **Allow multirate processing** — When you select this option, the block performs sample-based processing and produces an output with a sample rate that is  $R$  times slower than the input sample rate.

---

**Note** The option `Inherit from input` (this choice will be removed - see release notes) will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

# CIC Decimation

---

## View filter response

This button opens the Filter Visualization Tool (fvtool) from the Signal Processing Toolbox product and displays the filter response of the `mfilt` object specified in the **Multirate filter variable** parameter. For more information on FVTool, see the Signal Processing Toolbox documentation.

---

**Note** If you specify an `mfilt` object in the **Multirate filter variable** parameter, you must click the **Apply** button to apply the filter before using the **View filter response** button.

---

## References

- [1] Hogenauer, E.B., “An Economical Class of Digital Filters for Decimation and Interpolation,” *IEEE Transactions on Acoustics, Speech and Signal Processing*, ASSP-29(2): pp. 155–162, 1981.
- [2] Meyer-Baese, U., *Digital Signal Processing with Field Programmable Gate Arrays*, Springer Verlag, 2001.
- [3] Harris, Fredric J., *Multirate Signal Processing for Communication Systems*, Prentice Hall PTR, 2004.

## Supported Data Types

- Fixed point (signed only)
- 8-, 16-, and 32-bit signed integers

## See Also

CIC Interpolation	DSP System Toolbox
FIR Decimation	DSP System Toolbox
FIR Interpolation	DSP System Toolbox
filter	DSP System Toolbox

`mfilt.cicdecim`

DSP System Toolbox

`mfilt.cicinterp`

DSP System Toolbox


# CIC Filter

---

**Purpose** Design Cascaded Integrator-Comb (CIC) Filter

**Library** Filtering / Filter Designs  
dspfdesign

**Description** This block brings the filter design capabilities of the `filterbuilder` function to the Simulink environment.



**Dialog Box**

## Main Pane

See “CIC Filter Design Dialog Box — Main Pane” on page 7-692 for more information about the parameters of this block. The **Data Types** and **Code Generation** panes are not available for blocks in the DSP System Toolbox Filter Designs library.

Function Block Parameters: CIC Filter

CIC Filter

Design a Cascaded Integrator-Comb filter.

Main Data Types

Filter specifications

Filter Type: Decimator Factor: 2

Differential delay: 1

Frequency specifications

Frequency units: Normalized (0 to 1) Input Fs: 2

Fpass: .01

Magnitude specifications

Magnitude units: dB

Astop: 60

Filter Implementation

Use basic elements to enable filter customization

Rate options: Enforce single-rate processing

OK Cancel Help

## View filter response

This button opens the Filter Visualization Tool (fvtool) from the Signal Processing Toolbox product. You can use the tool to display:

- Magnitude response, phase response, and group delay in the frequency domain.
- Impulse response and step response in the time domain.
- Pole-zero information.

The tool also helps you evaluate filter performance by providing information about filter order, stability, and phase linearity. For more information on FVTool, see the Signal Processing Toolbox documentation.

## Filter Specifications

In this group, you specify your CIC filter format, such as the filter type and the differential delay.

### Filter type

Select whether your filter will be a decimator or an interpolator. Your choice determines the type of filter and the design methods and structures that are available to implement your filter. Selecting decimator or interpolator activates the **Factor** option. When you design an interpolator, you enable the **Output Fs** parameter.

When you design either a decimator or interpolator, the resulting filter is a CIC filter that decimates or interpolates your input signal.

### Differential delay

Specify the differential delay of your CIC filter as an integer value greater than or equal to 1. The default value is 1. The differential delay changes the shape, number, and location of nulls in the filter response. Increasing the differential delay increases the sharpness of the nulls and the response between the nulls. In practice, differential delay values of 1 or 2 are the most common.

**Factor**

Specify the decimation or interpolation factor for your filter as an integer value greater than or equal to 1. The default value is 2.

**Frequency units**

Use this parameter to specify whether your frequency settings are normalized or in absolute frequency. Select **Normalized (0 1)** to enter frequencies in normalized form. This behavior is the default. To enter frequencies in absolute values, select one of the frequency units from the drop-down list—Hz, kHz, MHz, or GHz. Selecting one of the unit options enables the **Input Fs** parameter.

**Input Fs**

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter input. When you provide an input sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is available when you select one of the frequency options from the **Frequency units** list.

**Output Fs**

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter output. When you provide an output sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is available only when you design interpolators.

**Fpass**

Enter the frequency at the end of the passband. Specify the value in either normalized frequency units or the absolute units you select in **Frequency units**.

**Magnitude units**

Specify the units for any parameter you provide in magnitude specifications. From the drop-down list, select one of the following options:

- **Linear** — Specify the magnitude in linear units.

- dB — Specify the magnitude in decibels (default).
- Squared — Specify the magnitude in squared units.

## Astop

Enter the filter attenuation in the stopband in the units you choose for **Magnitude units**, either linear or decibels.

## Filter Implementation

### Use basic elements to enable filter customization

Select this check box to implement the filter as a subsystem of basic Simulink blocks. Clear the check box to implement the filter as a high-level subsystem. By default, this check box is cleared.


The high-level implementation provides better compatibility across various filter structures, especially filters that would contain algebraic loops when constructed using basic elements.

## Rate options

When the **Filter type** parameter specifies a multirate filter, select the rate processing rule for the block from following options:

- Enforce single-rate processing — When you select this option, the block maintains the sample rate of the input.
- Allow multirate processing — When you select this option, the block adjusts the rate at the output to accommodate an increased or reduced number of samples. To select this option, you must set the **Input processing** parameter to Elements as channels (sample based).

## Data Types Pane



See the Data Types Pane subsection of the `filterbuilder` function reference page for more information about specifying data type parameters.

# CIC Filter

---


## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Fixed point</li></ul>

**Purpose** Interpolate signal using Cascaded Integrator-Comb filter

**Library** Filtering / Multirate Filters  
dspmlti4

## Description



The CIC Interpolation block performs a sample rate increase (interpolation) on an input signal by an integer factor. Cascaded Integrator-Comb (CIC) filters are a class of linear phase FIR filters that consist of a comb part and an integrator part.

The transfer function of a CIC interpolator filter is

$$H(z) = H_I^N(z)H_C^N(z) = \frac{(1 - z^{-RM})^N}{(1 - z^{-1})^N} = \left[ \sum_{k=0}^{RM-1} z^{-k} \right]^N$$

where

- $H_I$  is the transfer function of the integrator part of the filter.
- $H_C$  is the transfer function of the comb part of the filter.
- $N$  is the number of sections. The number of sections in a CIC filter is defined as the number of sections in either the comb part *or* the integrator part of the filter. This value does not represent the total number of sections throughout the entire filter.
- $R$  is the interpolation factor.
- $M$  is the differential delay.

The CIC Interpolation block requires a Simulink Fixed Point license. The block supports real and complex fixed-point inputs and treats each channel of a complex input as two real input channels.


## CIC Filter Structure

The filter structures supported by the CIC Interpolation and CIC Decimation blocks exactly match those created by the `mfilt.cicinterp` and `mfilt.cicdecim` objects. You can create an `mfilt` object in any

# CIC Interpolation

workspace and specify that object in the **Multirate filter variable** parameter of this block. Alternatively, you can set the **Coefficient source** to **Dialog parameters** and specify information about the CIC filter using the available block dialog parameters.

You can use this block to create the following CIC filter structure. This interpolator has a latency of  $N$ , where  $N$  is the number of sections in either the comb or the integrator part of the filter.



## Dialog Box

### Coefficient Source

The CIC Interpolation block can operate in two different modes. Select the mode in the **Coefficient source** group box. If you select:


- **Dialog parameters**, you enter information about the filter such as structure and coefficients in the block mask
- **Multirate filter object (MFILT)**, you specify the filter using an `mfilt` object.

Different items appear on the CIC Interpolation block dialog depending on whether you select **Dialog parameters** or **Multirate filter object (MFILT)** in the **Coefficient source** group box. See the following sections for details:

- “Specify Filter Characteristics in Dialog” on page 2-262
- “Specify Multirate Filter Object” on page 2-267

### Specify Filter Characteristics in Dialog

The **Main** pane of the CIC Interpolation block dialog appears as follows when you select **Dialog parameters** in the **Coefficient source** group box.



### **Interpolation factor (R)**

Specify the interpolation factor of the filter.

### **Differential delay (M)**

Specify the differential delay of the comb portion of the filter,  $M$ , as shown in the diagram in “CIC Filter Structure” on page 2-261.

# CIC Interpolation

---

## Number of sections (N)

Specify the number of filter sections. The number you specify determines the number of sections in either the comb part of the filter or in the integrator part of the filter. This value does not represent the total number of sections in the comb and integrator parts combined.

## Data type specification mode

Choose how you specify the fixed-point word length and fraction length of the filter sections and/or output.

- **Full precision** — In this mode, the word and fraction lengths of the filter sections and outputs are automatically selected for you. The output and last section word lengths are set to

$$\text{word length} = \text{ceil}(\log_2(\frac{(R * M)^N}{R})) + I$$

where

- I = input word length
- M = differential delay
- N = number of sections
- R = interpolation factor

The other section word lengths are set in such a way as to accommodate the bit growth, as described in Hogenauer's paper [1]. All fraction lengths are set to the input fraction length.

- **Minimum section word lengths** — In this mode, you specify the word length of the filter output in the **Output word length** parameter. The word lengths of the filter sections are set in the same way as in **Full precision** mode.

The section fraction lengths are set to the input fraction length. The output fraction length is set to the input fraction length minus the difference between the last section and output word lengths.

- **Specify word lengths** — In this mode you specify the word lengths of the filter sections and output in the **Section word lengths** and **Output word length** parameters. The fraction lengths of the filter sections are set such that the spread between word length and fraction length is the same as in full-precision mode. The output fraction length is set to the input fraction length minus the difference between the last section and output word lengths.
- **Binary point scaling** — In this mode you fully specify the word and fraction lengths of the filter sections and output in the **Section word lengths**, **Section fraction lengths**, **Output word length**, and **Output fraction length** parameters.

### **Section word lengths**

Specify the word length, in bits, of the filter sections.

This parameter is only visible if you select **Specify word lengths** or **Binary point scaling** for the **Data type specification mode** parameter.

### **Section fraction lengths**

Specify the fraction length of the filter sections.

This parameter is only visible if you select **Binary point scaling** for the **Data type specification mode** parameter.

### **Output word length**

Specify the word length, in bits, of the filter output.

This parameter is only visible if you select **Minimum section word lengths**, **Specify word lengths** or **Binary point scaling** for the **Data type specification mode** parameter.

### **Output fraction length**

Specify the fraction length of the filter output.

This parameter is only visible if you select **Binary point scaling** for the **Data type specification mode** parameter.

## Input processing

Specify how the block should process the input. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel. In this mode, the block always performs single-rate processing.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel. In this mode, the input to the block must be a scalar or a vector. You can use the **Rate options** parameter to specify whether the block performs single-rate or multirate processing.

---

**Note** The option *Inherit from input* (this choice will be removed - see release notes) will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Rate options

Specify the rate processing rule for the block. You can select one of the following options:

- **Enforce single-rate processing** — When you select this option, the block maintains the sample rate of the input.
- **Allow multirate processing** — When you select this option, the block produces an output with a sample rate that is  $R$  times faster than the input sample rate. To select this option, you must set the **Input processing** parameter to **Elements as channels (sample based)**.

## View filter response

This button opens the Filter Visualization Tool (fvtool) from the Signal Processing Toolbox product. The tool then displays

the filter response of the `mfilt` object specified in the **Multirate filter variable** parameter. For more information on FVTool, see the Signal Processing Toolbox documentation.

---


**Note** If you specify an `mfilt` object in the **Multirate filter variable** parameter, you must click the **Apply** button to apply the filter before using the **View filter response** button.

---

## Specify Multirate Filter Object

The **Main** pane of the CIC Interpolation block dialog appears as follows when you specify **Multirate filter object (MFILT)** in the **Coefficient source** group box.

# CIC Interpolation



## Multirate filter variable

Specify the multirate filter object (`mfilt`) that you want the block to implement. You can specify the `mfilt` object in one of three ways:

- You can fully specify the `mfilt` object in the block mask.

- You can enter the variable name of a `mfilt` object that is defined in any workspace.
- You can enter a variable name for a `mfilt` object that is not yet defined, as shown in the default value.

For more information on creating `mfilt` objects, see the `mfilt` function reference page.

## Input processing

Specify how the block should process the input. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel. In this mode, the block always performs single-rate processing.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel. In this mode, the input to the block must be a scalar or a vector. You can use the **Rate options** parameter to specify whether the block performs single-rate or multirate processing.

---

**Note** The option `Inherit from input` (this choice will be removed - see release notes) will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Rate options

Specify the rate processing rule for the block. You can select one of the following options:

- **Enforce single-rate processing** — When you select this option, the block maintains the sample rate of the input.

# CIC Interpolation

---

- Allow multirate processing — When you select this option, the block produces an output with a sample rate that is  $R$  times faster than the input sample rate. To select this option, you must set the **Input processing** parameter to `Elements as channels (sample based)`.

## View filter response

This button opens the Filter Visualization Tool (fvtool) from the Signal Processing Toolbox product. The tool then displays the filter response of the `mfilt` object specified in the **Multirate filter variable** parameter. For more information on FVTool, see the Signal Processing Toolbox documentation.

---

**Note** If you specify an `mfilt` object in the **Multirate filter variable** parameter, you must click the **Apply** button to apply the filter before using the **View filter response** button.

---

## References

- [1] Hogenauer, E.B., “An Economical Class of Digital Filters for Decimation and Interpolation,” *IEEE Transactions on Acoustics, Speech and Signal Processing*, ASSP-29(2): pp. 155–162, 1981.
- [2] Meyer-Baese, U., *Digital Signal Processing with Field Programmable Gate Arrays*, Springer Verlag, 2001.
- [3] Harris, Fredric J., *Multirate Signal Processing for Communication Systems*, Prentice Hall PTR, 2004.

## Supported Data Types

- Fixed point (signed only)
- 8-, 16-, and 32-bit signed integers

## See Also

CIC Decimation	DSP System Toolbox
FIR Decimation	DSP System Toolbox

FIR Interpolation	DSP System Toolbox
<code>filter</code>	DSP System Toolbox
<code>mfilt.cicdecim</code>	DSP System Toolbox
<code>mfilt.cicinterp</code>	DSP System Toolbox

# Comb Filter

---

**Purpose** Design comb Filter

**Library** Filtering / Filter Designs  
dspfdesign

**Description** This block brings the filter design capabilities of the `filterbuilder` function to the Simulink environment.



**Dialog Box** See “Comb Filter Design Dialog Box—Main Pane” on page 7-703 for more information about the parameters of this block. The **Data Types** and **Code Generation** panes are not available for blocks in the DSP System Toolbox Filter Designs library.

Function Block Parameters: Comb Filter

Comb Filter

Design a comb filter.

[View Filter Response](#)

Filter specifications

Comb Type:

Order mode:  Order:

Frequency specifications

Frequency constraints:

Quality factor:

Frequency units:  Input Fs:

Notch Frequencies:

Magnitude specifications

No magnitude constraints can be specified when specifying a filter order.

Algorithm

Design method:

Filter Implementation

Structure:

Use basic elements to enable filter customization

Input processing:

Use symbolic names for coefficients

# Comb Filter

---

## View filter response

This button opens the Filter Visualization Tool (fvtool) from the Signal Processing Toolbox product. You can use the tool to display:

- Magnitude response, phase response, and group delay in the frequency domain.
- Impulse response and step response in the time domain.
- Pole-zero information.

The tool also helps you evaluate filter performance by providing information about filter order, stability, and phase linearity. For more information on FVTool, see the Signal Processing Toolbox documentation.

## Filter Specifications

In this group, you specify the type of comb filter and the number of peaks or notches.

### Comb Type


Select either **Notch** or **Peak** from the drop-down list. **Notch** creates a comb filter that attenuates a set of harmonically related frequencies. **Peak** creates a comb filter that amplifies a set of harmonically related frequencies.

### Order mode

Select either **Order** or **Number of Peaks/Notches** from the drop-down menu.

Select **Order** to enter the desired filter order in the dialog box. The comb filter has notches or peaks at increments of  $2/\text{Order}$  in normalized frequency units.

Select **Number of Peaks** or **Number of Notches** to specify the number of peaks or notches and the Shelving filter order



## Shelving filter order

The Shelving filter order is a positive integer that determines the sharpness of the peaks or notches. Larger values result in sharper peaks or notches.

## Frequency specifications

In this group, you specify the frequency constraints and frequency units.

### Frequency specifications

Select either Quality factor or Bandwidth.

Quality factor is the ratio of the center frequency of the peak or notch to the bandwidth calculated at the  $-3$  dB point.

Bandwidth specifies the bandwidth of the peak or notch. By default the bandwidth is measured at the  $-3$  dB point. For example, setting the bandwidth equal to 0.1 results in 3 dB frequencies at normalized frequencies 0.05 above and below the center frequency of the peak or notch.

### Frequency Units

Specify the frequency units. The default is normalized frequency. Choosing an option in Hz enables the **Input Fs** dialog box.

## Magnitude specifications

Specify the units for the magnitude specification and the gain at which the bandwidth is measured. This menu is disabled if you specify a filter order. Select one of the following magnitude units from the drop down list:

# Comb Filter

---

- dB — Specify the magnitude in decibels (default).
- Squared — Specify the magnitude in squared units.

**Bandwidth gain** — Specify the gain at which the bandwidth is measured. The default is  $-3$  dB.

## Algorithm

The parameters in this group allow you to specify the design method and structure of your filter.

### Design Method

The IIR Butterworth design is the only option for peaking or notching comb filters.

## Filter Implementation

### Structure

For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter.

### Use basic elements to enable filter customization

Select this check box to implement the filter as a subsystem of basic Simulink blocks. Clear the check box to implement the filter as a high-level subsystem. By default, this check box is cleared.

The high-level implementation provides better compatibility across various filter structures, especially filters that would contain algebraic loops when constructed using basic elements. On the other hand, using basic elements enables the following optimization parameters:

- **Optimize for zero gains** — Terminate chains that contain Gain blocks with a gain of zero.
- **Optimize for unit gains** — Remove Gain blocks that scale by a factor of one.

- **Optimize for delay chains** — Substitute delay chains made up of  $n$  unit delays with a single delay by  $n$ .
- **Optimize for negative gains** — Use subtraction in Sum blocks instead of negative gains in Gain blocks.

### Optimize for unit-scale values

Select this check box to scale unit gains between sections in SOS filters. This parameter is available only for SOS filters.

### Input processing

Specify how the block should process the input. The available options may vary depending on the settings of the **Filter Structure** and **Use basic elements for filter customization** parameters. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The Inherited (this choice will be removed see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

### Rate options

When the **Filter type** parameter specifies a multirate filter, select the rate processing rule for the block from following options:

- **Enforce single-rate processing** — When you select this option, the block maintains the sample rate of the input.

# Comb Filter

---

- **Allow multirate processing** — When you select this option, the block adjusts the rate at the output to accommodate an increased or reduced number of samples. To select this option, you must set the **Input processing** parameter to **Elements as channels** (sample based).

## Use symbolic names for coefficients

Select this check box to enable the specification of coefficients using MATLAB variables. The available coefficient names differ depending on the filter structure. Using symbolic names allows tuning of filter coefficients in generated code. By default, this check box is cleared.


## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

**Purpose** Compute complex cepstrum of input

**Library** Transforms  
dspxfm3

## Description



The Complex Cepstrum block computes the complex cepstrum of each column in the real-valued  $M$ -by- $N$  input matrix,  $u$ . The block treats each column of the input as an independent channel containing  $M$  consecutive samples. The block does not accept complex-valued inputs.

The input is altered by the application of a linear phase term so that there is no phase discontinuity at  $\pm\pi$  radians. That is, each input channel is independently zero padded and circularly shifted to have zero phase at  $\pi$  radians.


The output is a real  $M_o$ -by- $N$  matrix, where  $M_o$  is specified by the **FFT length** parameter. Each output column contains the length- $M_o$  complex cepstrum of the corresponding input column.

```
y = cceps(u,Mo)    % Equivalent MATLAB code
```

When you select the **Inherit FFT length from input port dimensions** check box, the output frame size matches the input frame size ( $M_o=M$ ). In this case, the block processes *sample-based* length- $M$  row vector inputs as a single channel (that is, as an  $M$ -by-1 column vector), and returns the result as a length- $M$  column vector. The block *always* processes unoriented vector inputs as a single channel, and returns the result as a length- $M$  column vector.

The output port rate is the same as the input port rate.

# Complex Cepstrum



## Dialog Box

### Inherit FFT length from input port dimensions

When you select this check box, the output frame size matches the input frame size.

### FFT length

The number of frequency points at which to compute the FFT, which is also the output frame size,  $M_o$ . This parameter is visible only when you clear the **Inherit FFT length from input port dimensions** check box.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point


## See Also

DCT	DSP System Toolbox
FFT	DSP System Toolbox
Real Cepstrum	DSP System Toolbox
cceps	Signal Processing Toolbox

**Purpose** Compute complex exponential function


**Library** Math Functions / Math Operations  
dspmathops

**Description** The Complex Exponential block computes the complex exponential function for each element of the real input,  $u$ .



$$y = e^{ju} = \cos u + j \sin u$$

where  $j = \sqrt{-1}$ . The output is complex and the same size as the input.



**Dialog Box**

**Supported Data Types**

- Double-precision floating point
- Single-precision floating point

**See Also**

Math Function	Simulink
Sine Wave	DSP System Toolbox
exp	MATLAB

# Constant

---

<b>Purpose</b>	Generate constant value
<b>Library</b>	Sources dspsrcs4
<b>Description</b>	The Constant block is an implementation of the Simulink Constant block. See Constant for more information.


## Purpose

Generate square, diagonal matrix

## Library

- Sources  
dpsrcs4
- Math Functions / Matrices and Linear Algebra / Matrix Operations  
dspmtrx3

## Description




The Constant Diagonal Matrix block outputs a square diagonal matrix constant. The **Constant along diagonal** parameter determines the values along the matrix diagonal. This parameter can be a scalar to be repeated for all elements along the diagonal, or a vector containing the values of the diagonal elements. To generate the identity matrix, set the **Constant along diagonal** to 1, or use the Identity Matrix block.

The output is frame based when you select the **Frame-based output** check box; otherwise, the output is sample based.

## Dialog Box

The **Main** pane of the Constant Diagonal Matrix block dialog appears as follows.



# Constant Diagonal Matrix

---

## Constant(s) along diagonal


Specify the values of the elements along the diagonal. You can input a scalar or a vector. Tunable.

When you specify any data type information in this field, it is overridden by the value of the **Output data type** parameter on the **Data Types** pane, unless you select **Inherit** from 'Constant(s) along diagonal'.

## Frame-based output

Select to cause the output of the block to be frame based. Otherwise, the output is sample based.

The **Data Types** pane of the Constant Diagonal Matrix block dialog appears as follows.



## Output data type

Specify the output data type in one of the following ways:

- Choose one of the built-in data types from the list.

- Choose **Fixed-point** to specify the output data type and scaling in the **Signed**, **Word length**, **Set fraction length in output to**, and **Fraction length** parameters.
- Choose **User-defined** to specify the output data type and scaling in the **User-defined data type**, **Set fraction length in output to**, and **Fraction length** parameters.
- Choose **Inherit** from 'Constant(s) along diagonal' to set the output data type and scaling to match the values of the **Constant(s) along diagonal** parameter on the **Main** pane.
- Choose **Inherit via back propagation** to set the output data type and scaling to match the next block downstream.

The value of this parameter overrides any data type information specified in the **Constant(s) along diagonal** parameter on the **Main** pane, except when you select **Inherit** from 'Constant(s) along diagonal'.

## **Signed**

Select to output a signed fixed-point signal. Otherwise, the signal is unsigned. This parameter is only visible when you select **Fixed-point** for the **Output data type** parameter.

## **Word length**

Specify the word length, in bits, of the fixed-point output data type. This parameter is only visible when you select **Fixed-point** for the **Output data type** parameter.

## **User-defined data type**

Specify any built-in or fixed-point data type. You can specify fixed-point data types using the following Simulink Fixed Point functions: `sfix`, `ufix`, `sint`, `uint`, `sfrac`, and `ufrac`. This parameter is only visible when you select **User-defined** for the **Output data type** parameter.

## **Set fraction length in output to**

Specify the scaling of the fixed-point output by either of the following two methods:

# Constant Diagonal Matrix

---

- Choose **Best precision** to have the output scaling automatically set such that the output signal has the best possible precision.
- Choose **User-defined** to specify the output scaling in the **Fraction length** parameter.

This parameter is only visible when you select **Fixed-point** for the **Output data type** parameter, or when you select **User-defined** and the specified output data type is a fixed-point data type.

## Fraction length

For fixed-point output data types, specify the number of fractional bits, or bits to the right of the binary point. This parameter is only visible when you select **Fixed-point** or **User-defined** for the **Output data type** parameter and **User-defined** for the **Set fraction length in output to** parameter.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point
- Fixed point
- 8-, 16-, and 32-bit signed integers
- 8-, 16-, and 32-bit unsigned integers

## See Also

Create Diagonal Matrix	DSP System Toolbox
Constant	Simulink
Identity Matrix	DSP System Toolbox
diag	MATLAB

**Purpose** Generate ramp signal with length based on input dimensions

**Library** Signal Operations  
dspSigOps

**Description** The Constant Ramp block generates the constant ramp signal



$$y = (0:L-1)*m + b$$


where  $m$  is the slope specified by the scalar **Slope** parameter, and  $b$  is the  $y$ -intercept specified by the scalar **Offset** parameter.

For an unoriented vector input,  $L$  is equal to the length of the input vector. For an N-D input array, the length  $L$  of the output ramp is equal to the length of the input in the dimension specified by the **Ramp length equals number of** or **Dimension** parameter. The output,  $y$ , is always an unoriented vector.

# Constant Ramp

## Dialog Box

The **Main** pane of the Constant Ramp block dialog appears as follows.



### Ramp length equals number of

Specify whether the length of the output ramp is the number of rows, number of columns, or the length of the specified dimension of the input.

### Dimension

Specify the one-based dimension of the input array that determines the length of the output ramp.

This parameter is only visible when you select **Elements in specified dimension** for the **Ramp length equals number of** parameter.


### Slope

Specify the scalar slope of the ramp.

## Offset

Specify the scalar  $y$ -intercept of the ramp.

The **Data Types** pane of the Constant Ramp block dialog appears as follows.



## Output data type

Specify the output data type for this block. You can select one of the following:

- A rule that inherits a data type, for example, `Inherit: Same as input`.
- A built in data type, such as `double`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16)`

# Constant Ramp

---

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point
- Fixed point
- 8-, 16-, and 32-bit signed integers
- 8-, 16-, and 32-bit unsigned integers

This block differs from other DSP System Toolbox blocks in that unless you choose **Same as input** for the **Output data type** parameter, the data types of the input and the output do not need to be the same.

## See Also

Create Diagonal Matrix	DSP System Toolbox
Constant	Simulink
Ramp	Simulink
Identity Matrix	DSP System Toolbox


## Purpose

Create discontinuous input in contiguous block of memory

## Library

dspobslib

## Description



---

**Note** The Contiguous Copy block is still supported but is likely to be obsoleted in a future release.


---

The Contiguous Copy block copies the input to a contiguous block of memory, and passes this new copy to the output. The output is identical to the input, but is guaranteed to reside in a contiguous section of memory.

Because Simulink software employs an efficient copy-by-reference method for propagating data in a model, some operations produce outputs with discontinuous memory locations.

Although this does not present a problem during simulation, blocks linked to versions of DSP Blockset prior to 4.0 may require contiguous inputs for code generation with the Simulink Coder product. When such blocks are used in a model intended for code generation, they should be preceded by the Contiguous Copy block to ensure that their inputs are contiguous.

## Dialog Box



# Contiguous Copy (Obsolete)

---

## **Supported Data Types**

- Double-precision floating point
- Single-precision floating point
- Fixed point
- Boolean
- 8-, 16-, and 32-bit signed integers
- 8-, 16-, and 32-bit unsigned integers

## Purpose

Reshape 1-D or 2-D input to 2-D matrix with specified dimensions

## Library

Signal Management / Signal Attributes

dspsigattribs


## Description



The Convert 1-D to 2-D block reshapes a length- $M_i$  1-D vector or an  $M_i$ -by- $N_i$  matrix to an  $M_o$ -by- $N_o$  matrix, where  $M_o$  is specified by the **Number of output rows** parameter, and  $N_o$  is specified by the **Number of output columns** parameter.

`y = reshape(u,Mo,No)`      % Equivalent MATLAB code


The input is reshaped *columnwise*, as shown in the two cases below. The length-6 vector and the 2-by-3 matrix are both reshaped to the same 3-by-2 output matrix.



An error is generated when  $(M_o * N_o) \neq (M_i * N_i)$ . That is, the total number of input elements must be conserved in the output.

The output is frame based when you select the **Frame-based output** check box; otherwise, the output is sample based.

# Convert 1-D to 2-D



## Dialog Box

### Number of output rows

The number of rows,  $M_o$ , in the output matrix.

### Number of output columns

The number of rows,  $N_o$ , in the output matrix.

### Frame-based output

Creates a frame-based output when selected.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>

Port	Supported Data Types
	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

## See Also

Buffer	DSP System Toolbox
Convert 2-D to 1-D	DSP System Toolbox
Frame Conversion	DSP System Toolbox
Reshape	Simulink
Submatrix	DSP System Toolbox

# Convert 2-D to 1-D

**Purpose** Convert 2-D matrix input to 1-D vector


**Library** Signal Management / Signal Attributes  
dspattributes

**Description** The Convert 2-D to 1-D block reshapes an  $M$ -by- $N$  matrix input to a 1-D vector with length  $M*N$ .




`y = u(:)` % Equivalent MATLAB code

The input is reshaped *columnwise*, as shown below for a 3-by-2 matrix.



**Dialog Box**



## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed and unsigned)</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> <li>• Enumerated</li> </ul>
Output	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed and unsigned)</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> <li>• Enumerated</li> </ul>

## See Also

Buffer	DSP System Toolbox
Convert 1-D to 2-D	DSP System Toolbox
Frame Status Conversion (Obsolete)	DSP System Toolbox
Reshape	Simulink
Submatrix	DSP System Toolbox

# Convolution

---

**Purpose** Convolution of two inputs

**Library** Signal Operations  
dsp\_sigops

**Description**



The Convolution block convolves the first dimension of an N-D input array  $u$ , with the first dimension of an N-D input array  $v$ . The block can also independently convolve a column vector with the first-dimension of an N-D input array.

## Convolution with DSP System Toolbox Blocks

The general equation for convolution is

$$y(k) = \sum_n u(n-k) * h(k)$$

There are two DSP System Toolbox blocks that can be used for this purpose:

- Convolution
- Digital Filter

The Convolution block assumes that all of  $u$  and  $h$  are available at each Simulink time step, and computes the entire convolution at every one.

The Digital Filter block can be used for convolving signals in situations where all of  $h$  is available at each time step, but  $u$  is a sequence that comes in over the life of the simulation. When you use the Digital Filter block, the convolution is computed only once. To convolve inputs with the Digital Filter block, you must set the **Transfer function type** to FIR (all zeros).

Use the following questions to help you determine which block best fits your needs:

Question	Answer	Recommended Block(s)
How many convolutions do you intend to perform?	Many convolutions, one at each time step	<ul style="list-style-type: none"> <li>Convolution block</li> </ul>
	One convolution over the life of the simulation	<ul style="list-style-type: none"> <li>Convolution block</li> <li>Digital Filter block (in FIR mode)</li> </ul>
How long are your input sequences?	Both sequences have a finite length	<ul style="list-style-type: none"> <li>Convolution block</li> <li>Digital Filter block (in FIR mode)</li> </ul>
	One sequence has an infinite (not predetermined) length	<ul style="list-style-type: none"> <li>Digital Filter block (in FIR mode)</li> </ul>
How many of the inputs are scalar streams?	None	<ul style="list-style-type: none"> <li>Convolution block</li> <li>Digital Filter block (in FIR mode)</li> </ul>
	One or both	<ul style="list-style-type: none"> <li>Buffer block followed by the Convolution block</li> <li>Digital Filter block (in FIR mode)</li> </ul>

## Convoluting Two N-D Arrays

The block always computes the convolution of two N-D input arrays along the first dimension. When both inputs are N-D arrays, the size of their first dimension can differ, but the size of all other dimensions must be equal. For example, when  $u$  is an  $M_u$ -by- $N$ -by- $P$  array, and  $v$  is an  $M_v$ -by- $N$ -by- $P$  array, the output is an  $(M_u + M_v - 1)$ -by- $N$ -by- $P$  array.

When the input to the Convolution block is a  $M_u$ -by- $N$  matrix  $u$  and an  $M_v$ -by- $N$  matrix  $v$ , the output,  $y$ , is a  $(M_u + M_v - 1)$ -by- $N$  matrix whose  $j$ th column has the following elements

# Convolution

---

$$y_{i,j} = \sum_{k=0}^{\max(M_u, M_v)-1} u_{k,j} v_{(i-k),j} \quad 0 \leq i \leq (M_u + M_v - 2)$$

Inputs  $u$  and  $v$  are zero when indexed outside of their valid ranges. When both inputs are real, the output is real; when one or both inputs are complex, the output is complex.

## Convoluting a Column Vector with an N-D Array

When one input is a column vector and the other is an N-D array, the block independently convolves the vector with the first dimension of the N-D input array. For example, when  $u$  is a  $M_u$ -by-1 column vector and  $v$  is an  $M_v$ -by- $N$  matrix, the output is an  $(M_u + M_v - 1)$ -by- $N$  matrix whose  $j$ th column has the following elements

$$y_{i,j} = \sum_{k=0}^{\max(M_u, M_v)-1} u_k v_{(i-k),j} \quad 0 \leq i \leq (M_u + M_v - 2)$$

## Convoluting Two Column Vectors


The Convolution block also accepts two column vector inputs. When  $u$  and  $v$  are column vectors with lengths  $M_u$  and  $M_v$ , the Convolution block performs the vector convolution

$$y_i = \sum_{k=0}^{\max(M_u, M_v)-1} u_k v_{(i-k)} \quad 0 \leq i \leq (M_u + M_v - 2)$$

The output is a  $(M_u + M_v - 1)$ -by-1 column vector.

## Fixed-Point Data Types

The following diagram shows the data types used within the Convolution block for fixed-point signals (time domain only).



You can set the product output, accumulator, and output data types in the block dialog as discussed in the next section.

The output of the multiplier is in the product output data type when the input is real. When the input is complex, the result of the multiplication is in the accumulator data type. For details on the complex multiplication performed, see "Multiplication Data Types".

---


**Note** When one or both of the inputs are signed fixed-point signals, all internal block data types are signed fixed point. The internal block data types are unsigned fixed point only when *both* inputs are unsigned fixed-point signals.

---

## Dialog Box

The **Main** pane of the Convolution block dialog appears as follows.

# Convolution



## Computation domain


Set the domain in which the block computes convolutions:

- **Time** — The block computes in the time domain, which minimizes memory use.

- **Frequency** — The block computes in the frequency domain, which might require fewer computations than computing in the time domain, depending on the input length.
- **Fastest** — The block computes in the domain, which minimizes the number of computations.

The **Data Types** pane of the Convolution block dialog appears as follows.

# Convolution



---

**Note** Fixed-point signals are only supported for the time domain. To use the parameters on this pane, make sure Time is selected for the **Computation domain** parameter on the **Main** pane.

---

## Rounding mode

Select the rounding mode for fixed-point operations.

---

**Note** The **Rounding mode** and **Overflow mode** settings have no effect on numerical results when all the following conditions exist:

- **Product output data type** is Inherit: Inherit via internal rule
- **Accumulator data type** is Inherit: Inherit via internal rule
- **Output data type** is Inherit: Same as accumulator

With these data type settings, the block is effectively operating in full precision mode.

---


## Overflow mode

Select the overflow mode for fixed-point operations.

### Product output data type

Specify the product output data type. See “Fixed-Point Data Types” on page 2-300 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set it to:

- A rule that inherits a data type, for example, Inherit: Inherit via internal rule
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Accumulator data type

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-300 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`


Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-300 for illustrations depicting the use of the output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as accumulator`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

## Minimum

Specify the minimum value that the block should output. The default value is [ ] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Maximum

Specify the maximum value that the block should output. The default value is [ ] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed and unsigned)</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>
Output	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed and unsigned)</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>

# Convolution

---

## See Also

Correlation

Digital Filter

conv

DSP System Toolbox

DSP System Toolbox

MATLAB

**Purpose** Cross-correlation of two inputs

**Library** Statistics  
dspstat3

## Description



The Correlation block computes the cross-correlation of two N-D input arrays. The block computes the correlation column-wise, so both inputs must have the same number of columns. If one input is a column vector and the other is an N-D array, the Correlation block computes the cross-correlation of the vector with each column of the N-D array.

### Correlating Two N-D Arrays

When the input to the Correlation block is an  $M_u$ -by- $N$  input matrix  $u$  and an  $M_v$ -by- $N$  matrix  $v$ , the output,  $y$ , is a  $(M_u+M_v-1)$ -by- $N$  matrix whose  $j$ th column has elements

$$y_{uv(i,j)} = \sum_{k=0}^{\max(M_u, M_v)-1} u_{k,j} v_{(k-i),j}^* \quad 0 \leq i < M_v$$

$$y_{uv(i,j)} = y_{vu(-i,j)}^* \quad -M_u < i < 0$$

where \* denotes the complex conjugate. Inputs  $u$  and  $v$  are zero when indexed outside of their valid ranges. When both inputs are real, the output is real; when one or both inputs are complex, the output is complex.

### Correlating a Column Vector with an N-D Array

When one input is a column vector and the other is an N-D array, the Correlation block independently cross-correlates the input vector with each column of the N-D array. For example, when  $u$  is a  $M_u$ -by-1 column vector and  $v$  is an  $M_v$ -by- $N$  matrix, the output is an  $(M_u+M_v-1)$ -by- $N$  matrix whose  $j$ th column has elements

# Correlation

---

$$y_{uv}(i,j) = \sum_{k=0}^{\max(M_u, M_v)-1} u_k v_{(k-i),j}^* \quad 0 \leq i < M_v$$

$$y_{uv}(i,j) = y_{vu}^*(-i,j) \quad -M_u < i < 0$$

## Correlating Two Column Vectors

The Correlation block also accepts two column vector inputs. When  $u$  and  $v$  are column vectors with lengths  $M_u$  and  $M_v$ , the Correlation block performs the vector cross-correlation according to the following equation:


$$y_{uv}(i) = \sum_{k=0}^{\max(M_u, M_v)-1} u_k v_{(k-i)}^* \quad 0 \leq i < M_v$$

$$y_{uv}(i) = y_{vu}^*(-i) \quad -M_u < i < 0$$

The output is a  $(M_u + M_v - 1)$ -by-1 column vector.

## Fixed-Point Data Types

The following diagram shows the data types used within the Correlation block for fixed-point signals (time domain only).



You can set the product output, accumulator, and output data types in the block dialog as discussed in the next section.

The output of the multiplier is in the product output data type when the input is real. When the input is complex, the result of the multiplication is in the accumulator data type. For details on the complex multiplication performed, see “Multiplication Data Types”.

---


**Note** When one or both of the inputs are signed fixed-point signals, all internal block data types are signed fixed point. The internal block data types are unsigned fixed point only when *both* inputs are unsigned fixed-point signals.

---

## Dialog Box

The **Main** pane of the Correlation block dialog appears as follows.

# Correlation



## Computation domain


Set the domain in which the block computes correlations:

- **Time** — The block computes in the time domain, which minimizes memory use.

- **Frequency** — The block computes in the frequency domain, which might require fewer computations than computing in the time domain, depending on the input length.
- **Fastest** — The block computes in the domain, which minimizes the number of computations.

The **Data Types** pane of the Correlation block dialog appears as follows.

# Correlation



---

**Note** Fixed-point signals are only supported for the time domain. To use the parameters on this pane, make sure Time is selected for the **Computation domain** parameter on the **Main** pane.

---

## Rounding mode

Select the rounding mode for fixed-point operations.

---

**Note** The **Rounding mode** and **Overflow mode** settings have no effect on numerical results when all the following conditions exist:

- **Product output data type** is Inherit: Inherit via internal rule
- **Accumulator data type** is Inherit: Inherit via internal rule
- **Output data type** is Inherit: Same as accumulator

With these data type settings, the block is effectively operating in full precision mode.

---

## Overflow mode

Select the overflow mode for fixed-point operations.

### Product output data type

Specify the product output data type. See “Fixed-Point Data Types” on page 2-310 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set it to:

- A rule that inherits a data type, for example, Inherit: Inherit via internal rule
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Accumulator data type

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-310 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`


Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-310 for illustrations depicting the use of the output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as accumulator`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

## Minimum

Specify the minimum value that the block should output. The default value is [ ] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Maximum

Specify the maximum value that the block should output. The default value is [ ] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed and unsigned)</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>
Output	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed and unsigned)</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>

# Correlation

---

## See Also

Autocorrelation

DSP System Toolbox

Convolution

DSP System Toolbox


`xcorr`

Signal Processing Toolbox

**Purpose** Count up or down through specified range of numbers

**Library** Signal Management / Switches and Counters  
dspswit3

## Description



The Counter block counts up or down through a specified range of numbers. The block enables the Inc (increment) port when you set the **Count direction** parameter to Up. When you set the **Count direction** parameter to Down, the block enables the Dec (decrement) port. If you set the **Count event** parameter to Free running, the block disables the Inc or Dec port, and counts at a constant time interval. For all other settings of the **Count event** parameter, the block increments or decrements the counter each time a trigger event occurs at the Inc or Dec input port. When a trigger event occurs at the optional Rst port, the block resets the counter to its initial state.

The Counter block accepts single-channel inputs. The Inc and Dec ports accept real-valued scalars or vectors. If the input to the Inc or Dec port is a vector, the block treats the vector as a frame. The Rst port only accepts real-valued scalars. The Rst port must have the same port sample time as the Inc or Dec input port. If you enable the optional Max input port, you must provide an unsigned integer input that the **Count data type** can represent.


See the following topics for more information:

- “Setting the Count Event Parameter” on page 2-320
- “Setting the Counter Size and Initial Count Parameters” on page 2-321
- “Scalar Input Operation” on page 2-322
- “Vector Input Operation” on page 2-323
- “Free-Running Operation” on page 2-324


## Setting the Count Event Parameter

Specify the trigger event for the Inc/Dec and Rst ports by setting the **Count event** parameter to one of the following values:

- **Rising edge** — Triggers a count or reset operation when the input to the Inc/Dec or Rst port behaves in one of the following ways:
  - Rises from a negative value to a positive value or zero.
  - Rises from zero to a positive value, where the rise is not a continuation of a rise from a negative value to zero (see the following figure).



- **Falling edge** — Triggers a count or reset operation when the input to the Inc/Dec or Rst port behaves in one of the following ways:
  - Falls from a positive value to a negative value or zero.
  - Falls from zero to a negative value, where the fall is not a continuation of a fall from a positive value to zero (see the following figure).



- **Either edge** — Triggers a count or reset operation when the input to the Inc/Dec or Rst port is a **Rising edge** or **Falling edge**.
- **Non-zero sample** — Triggers a count or reset operation at each sample time when the input to the Inc/Dec or Rst port is not zero.
- **Free running** — Disables the Inc/Dec port and enables the **Samples per output frame** and **Sample time** block parameters. The block increments or decrements the counter at a constant interval,  $T_s$ , which you specify using the **Sample time** parameter. For more information, see “Free-Running Operation” on page 2-324. In this mode, the block resets the counter whenever it receives a non-zero sample at the Rst port.

### Setting the Counter Size and Initial Count Parameters

At the start of the simulation, the block sets the counter to the value you specify in the **Initial count** parameter. The **Initial count** can be any unsigned integer in the range defined by the **Counter size** parameter.

The **Counter size** parameter allows you to specify the range of integer values the block counts through. When the block counts through the entire counter range, the next time a trigger event occurs at the Inc/Dec port, the block resets the counter as follows:

- When you set the **Count direction** parameter to Up and the counter reaches the upper-limit of the counter range, the block restarts the counter at zero.

- When you set the **Count direction** parameter to Down and the counter reaches zero, the block restarts the counter at the upper-limit of the counter range.

You can set the **Counter size** parameter to one of the following options:

- **8 bits** — Specifies a counter with a range of 0 to 255.
- **16 bits** — Specifies a counter with a range of 0 to 65535.
- **32 bits** — Specifies a counter with a range of 0 to  $2^{32}-1$ .
- **User defined** — Enables the **Maximum count** parameter, which allows you to specify the upper-count limit as any arbitrary unsigned integer that the **Count data type** can represent. The counter values range from 0 to the value of the **Maximum count** parameter.
- **Specify via input port** — Enables the Max input port, which allows you to specify the upper-count limit as any arbitrary unsigned integer that the **Count data type** can represent. The counter values range from 0 to the value you specify as an input to the Max port.

## Scalar Input Operation

When you set the **Count direction** parameter to Up, a trigger event at the Inc (increment) input port causes the block to increase the counter by one. Assuming no reset events occur, the block continues increasing the counter value when triggered, until the counter value reaches the upper-count limit. The next time a trigger event occurs at the Inc port, the block restarts the counter at 0 and resumes increasing the counter by one for each subsequent trigger event at the Inc port.

When you set the **Count direction** parameter to Down, a trigger event at the Dec (decrement) input port causes the block to decrease the counter by one. Assuming no reset events occur, the block continues decreasing the counter value when triggered until the counter value reaches zero. The next time a trigger event occurs at the Dec port, the block restarts the counter at the upper-count limit and resumes decreasing the counter by one for each subsequent trigger event at the Dec port.

Between triggering events, the block holds the output at its most recent value. The block resets the counter to its initial state when the trigger event specified by the **Count event** parameter occurs at the optional Rst input port. When the Inc/Dec and Rst ports receive trigger events simultaneously, the block first resets the counter, and then increments or decrements the counter appropriately. If you do not need to reset the counter during simulation, you can disable the Rst port by clearing the **Reset input** check box.

The **Output** parameter allows you to specify which values the block outputs.

- **Count** enables a Cnt output port on the block, which provides the current value of the counter as a scalar value. The Cnt output port has the same port sample time as the Inc/Dec input port.
- **Hit** enables a Hit output port on the block. The Hit port produces zeros while the value of the counter does not equal any of the integers you specify for the **Hit values** parameter. You can specify an integer or a vector of integers for the **Hit values** parameter. When the counter value does equal one or more of the values you specify for the **Hit values** parameter, the block outputs a value of 1 at the Hit output port. The Hit output port has the same port sample time as the Inc/Dec input port.
- **Count** and **Hit** enables both the Cnt and Hit output ports.

## Vector Input Operation

The block treats vector inputs to the Inc/Dec port as a frame. Vector operation is the same as scalar operation, except that the block increments or decrements the counter by the total number of trigger events contained in the Inc/Dec input vector. Thus, the counter may change multiple times during the processing of a single Inc/Dec input vector.

When the block has a Hit port, the block outputs a value of 1 if any of the **Hit values** match any of the counter values during the processing of the Inc/Dec input vector.

When a trigger event splits across two consecutive vectors, that event is counted in the vector that contains the conclusion of the event. When the Rst port receives a trigger event at the same time as the Inc/Dec port, the block first resets the counter. The block then increments or decrements the counter by the number of trigger events contained in the Inc/Dec input vector.

When the input to the Inc/Dec port is a length  $N$  vector, the port sample time of the Inc/Dec input port is equal to the frame period of the input, or  $N$  times the sample time of the input signal. The port sample time of the Cnt and Hit output ports equals that of the Inc/Dec input port.

## Free-Running Operation

The block operates in free-running mode when you select `Free running` for the **Count event** parameter.


The Inc/Dec input port is disabled in this mode, and the block simply increments or decrements the counter at the constant interval,  $T_s$ , which you specify using the **Sample time** parameter.

In this mode, the Rst port always behaves as if the **Count event** parameter were set to `Non-zero sample`. Thus, the block triggers a reset event at each sample time that the Rst input is not zero.

In this mode, the Cnt output is an  $M$ -by-1 vector containing the count value at each of  $M$  consecutive sample times, where  $M$  is the value you specify for the **Samples per output frame** parameter. The Hit output is an  $M$ -by-1 vector containing the hit status (0 or 1) at each of those  $M$  consecutive sample times. Both the Cnt and Hit output ports have a port sample time of  $M * T_s$ .


## Examples

In the following model, `ex_counter_ref`, the Simulink Pulse Generator block drives the Dec port of the Counter block, and the N-Sample Enable block triggers the Rst port. All inputs to and outputs from the Counter block are multiplexed into a single To Workspace block using a 4-port Mux block.



The following figure shows the first 22 samples of the model's four-column output, `yout`.





The image shows a dialog box titled "Function Block Parameters: Counter". It contains a description of the counter's function, a "Parameters" section with several dropdown menus and text boxes, and a "Hit values" section with a text box and a checked checkbox. At the bottom are buttons for "?", "OK", "Cancel", "Help", and "Apply".

Counter (mask) (link)

Count up or down through a specified range of numbers. If you set the 'Count event' parameter to 'Free running', the block counts at a constant time interval. Otherwise, the block increments or decrements the counter each time a trigger event occurs at the Inc/Dec input port.

Parameters

Count direction: Up

Count event: Rising edge

Counter size: User defined

Maximum count: 255

Initial count: 0

Output: Count and Hit

Hit values: 32

Reset input

Count data type: double

Hit data type: Logical

? OK Cancel Help Apply

## Dialog Box

### Count direction

Specify whether to count Up or Down. The port label on the block icon changes to Inc (increment) or Dec (decrement) based on the value of this parameter.

- When you set the **Count direction** parameter to Up and the counter reaches the upper-limit of the counter range, the block

restarts the counter at zero the next time a trigger event occurs at the Inc port.

- When you set the **Count direction** parameter to Down and the counter reaches zero, the block restarts the counter at the upper-limit of the counter range the next time a trigger event occurs at the Dec port.

This parameter is tunable in Simulink Normal mode.

## Count event

Specify the type of event that triggers the block to increment, decrement, or reset the counter when received at the Inc/Dec or Rst ports. When you set this parameter to **Free running**, the block disables the Inc/Dec port and counts at the constant interval specified by the **Sample time** parameter. For more information on all the possible settings of this parameter, see “Setting the Count Event Parameter” on page 2-320.

## Counter size

Specify the range of integer values the block counts through. For more information about the valid values of this parameter, see “Setting the Counter Size and Initial Count Parameters” on page 2-321.

## Maximum count

Specify the maximum value of the counter as any unsigned integer representable by the data type you specify for the **Counter data type** parameter. This parameter appears only when you set the **Counter size** parameter to **User defined**. Tunable in Simulink Normal mode.

## Initial count

Specify the initial value of the counter. The block uses the initial value of the counter at the start of simulation and resets the counter back to that initial value each time a trigger event occurs at the Rst port. Tunable.

## Output

Select the output ports to enable. You can choose to enable the Count, Hit, or Count and Hit ports.

## Hit values

Specify an integer or vector of integers whose occurrence in the count should be flagged by a 1 at the (optional) Hit output port. This parameter appears only when you set the **Output** parameter to Hit or Count and Hit. Tunable.

## Reset input

Select this check box to enable the Rst input port. When you enable the Rst port, the block resets the counter to its initial value each time a trigger event occurs at the Rst port. To specify the type of event that triggers a reset of the counter, set the **Count event** parameter. When you clear the **Reset input** check box, you cannot reset the counter during simulation.

## Samples per output frame

Specify the number of samples,  $M$ , in each output vector. This parameter appears only when you set the **Count event** parameter to Free running.

## Sample time

Specify the constant interval,  $T_s$ , at which the block increments or decrements the counter when in free-running mode. For example, to have the block increment the counter every 5 seconds, set the **Count direction** parameter to Up, the **Count event** parameter to Free running, and specify a value of 5 for the **Sample time** parameter. In free running mode, the sample time of the output ports is always  $M * T_s$ .

This parameter appears only when you set the **Count event** parameter to Free running.

## Count data type

Specify the data type of the output at the Cnt port. This parameter appears only when you set the **Output** parameter to Count or Count and Hit.

# Counter

---

## Hit data type

Specify the data type of the output at the Hit port. This parameter appears only when you set the **Output** parameter to Hit or set it to Count and Hit with the **Count data type** parameter set to Double.

## Supported Data Types

Port	Supported Data Types
Inc/Dec	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Rst	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Max	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Cnt	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Hit	<ul style="list-style-type: none"><li>• Logical</li><li>• Boolean — The block might output Boolean values from the Hit output port depending on the setting of the <b>Hit data type</b> parameter.</li></ul>

## See Also


Edge Detector	DSP System Toolbox
N-Sample Enable	DSP System Toolbox
N-Sample Switch	DSP System Toolbox

# Covariance AR Estimator

**Purpose** Compute estimate of autoregressive (AR) model parameters using covariance method

**Library** Estimation / Parametric Estimation  
dspparest3

## Description



The Covariance AR Estimator block uses the covariance method to fit an autoregressive (AR) model to the input data. This method minimizes the forward prediction error in the least squares sense.

The input is a sample-based vector (row, column, or 1-D) or frame-based vector (column only) representing a frame of consecutive time samples from a single-channel signal, which is assumed to be the output of an AR system driven by white noise. The block computes the normalized estimate of the AR system parameters,  $A(z)$ , independently for each successive input frame.

$$H(z) = \frac{G}{A(z)} = \frac{G}{1 + a(2)z^{-1} + \dots + a(p+1)z^{-p}}$$


The order,  $p$ , of the all-pole model is specified by the **Estimation order** parameter. To guarantee a valid output, you must set the **Estimation order** parameter to be less than or equal to half the input vector length.

The top output,  $A$ , is a column vector of length  $p+1$  with the same frame status as the input, and contains the normalized estimate of the AR model coefficients in descending powers of  $z$ .

$$[1 \ a(2) \ \dots \ a(p+1)]$$

The scalar gain,  $G$ , is provided at the bottom output ( $G$ ).

See the Burg AR Estimator block reference page for a comparison of the Burg AR Estimator, Covariance AR Estimator, Modified Covariance AR Estimator, and Yule-Walker AR Estimator blocks.



## Dialog Box

### Estimation order

The order of the AR model,  $p$ . To guarantee a nonsingular output, you must set  $p$  to be less than or equal to half the input length. Otherwise, the output might be singular.

## References

Kay, S. M. *Modern Spectral Estimation: Theory and Application*. Englewood Cliffs, NJ: Prentice-Hall, 1988.

Marple, S. L., Jr., *Digital Spectral Analysis with Applications*. Englewood Cliffs, NJ: Prentice-Hall, 1987.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
A	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
G	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

# Covariance AR Estimator

---

## See Also

Burg AR Estimator

DSP System Toolbox

Covariance Method

DSP System Toolbox

Modified Covariance AR  
Estimator

DSP System Toolbox

Yule-Walker AR Estimator

DSP System Toolbox

arconv

Signal Processing Toolbox

## Purpose


Power spectral density estimate using covariance method

## Library

Estimation / Power Spectrum Estimation

dspsect3

## Description



The Covariance Method block estimates the power spectral density (PSD) of the input using the covariance method. This method fits an autoregressive (AR) model to the signal by minimizing the forward prediction error in the least squares sense. The **Estimation order** parameter specifies the order of the all-pole model. The block computes the spectrum from the FFT of the estimated AR model parameters. To guarantee a valid output, the **Estimation order** parameter must be less than or equal to half the input vector length.

The input is a sample-based vector (row, column, or 1-D) or frame-based vector (column only). It represents a frame of consecutive time samples from a single-channel signal. The block outputs a column vector containing the estimate of the power spectral density of the signal at  $N_{fft}$  equally spaced frequency points. The frequency points are in the range  $[0, F_s)$ , where  $F_s$  is the sampling frequency of the signal.

Selecting **Inherit FFT length from estimation order**, specifies that  $N_{fft}$  is one greater than the estimation order. Clearing the **Inherit FFT length from estimation order** check box allows you to use the **FFT length** parameter to specify  $N_{fft}$  as a power of 2. The block zero-pads or wraps the input to  $N_{fft}$  before computing the FFT. The output is always sample based.


When you select the **Inherit sample time from input** check box, the block computes the frequency data from the sample period of the input signal. For the block to produce valid output, the following conditions must hold:

- The input to the block is the original signal, with no samples added or deleted (by insertion of zeros, for example).
- The sample period of the time-domain signal in the simulation equals the sample period of the original time series.

# Covariance Method

If these conditions do not hold, clear the **Inherit sample time from input** check box. You can then specify a sample time using the **Sample time of original time series** parameter.

See the Burg Method block reference for a comparison of the Burg Method, Covariance Method, Modified Covariance Method, and Yule-Walker Method blocks.



## Dialog Box

### Estimation order

The order of the AR model. To guarantee a nonsingular output, the value of this parameter must be less than or equal to half the input length.

### Inherit FFT length from estimation order

When selected, this option specifies that the FFT length is one greater than the estimation order.

## FFT length

Enter the number of data points on which to perform the FFT,  $N_{fft}$ . When  $N_{fft}$  is larger than the input frame size, the block zero-pads each frame as needed. When  $N_{fft}$  is smaller than the input frame size, the block wraps each frame as needed. This parameter becomes visible only when you clear the **Inherit FFT length from estimation order** check box.

## Inherit sample time from input

When you select the **Inherit sample time from input** check box, the block computes the frequency data from the sample period of the input signal. For the block to produce valid output, the following conditions must hold:

- The input to the block is the original signal, with no samples added or deleted (by insertion of zeros, for example).
- The sample period of the time-domain signal in the simulation equals the sample period of the original time series.

If these conditions do not hold, clear the **Inherit sample time from input** check box. You can then specify a sample time using the **Sample time of original time series** parameter.

## Sample time of original time series

Specify the sample time of the original time-domain signal. This parameter becomes visible only when you clear the **Inherit sample time from input** check box.

## References

Kay, S. M. *Modern Spectral Estimation: Theory and Application*. Englewood Cliffs, NJ: Prentice-Hall, 1988.

Marple, S. L. Jr., *Digital Spectral Analysis with Applications*. Englewood Cliffs, NJ: Prentice-Hall, 1987.

Orfanidis, S. J. *Introduction to Signal Processing*. Englewood Cliffs, NJ: Prentice-Hall, 1995.

# Covariance Method

---

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

## See Also

Burg Method	DSP System Toolbox
Covariance AR Estimator	DSP System Toolbox
Modified Covariance Method	DSP System Toolbox
Short-Time FFT	DSP System Toolbox
Yule-Walker Method	DSP System Toolbox
spectrum.cov	Signal Processing Toolbox

See “Spectral Analysis” for related information.

# Create Diagonal Matrix


## Purpose

Create square diagonal matrix from diagonal elements

## Library

Math Functions / Matrices and Linear Algebra / Matrix Operations  
dspmtx3


## Description



The Create Diagonal Matrix block populates the diagonal of the  $M$ -by- $M$  matrix output with the elements contained in the length- $M$  vector input,  $D$ . The elements off the diagonal are zero.

$A = \text{diag}(D)$       Equivalent MATLAB code

## Dialog Box



## Supported Data Types

Port	Supported Data Types
D	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

# Create Diagonal Matrix

---

Port	Supported Data Types
A	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

## See Also

Constant Diagonal Matrix	DSP System Toolbox
Extract Diagonal	DSP System Toolbox
diag	MATLAB

## Purpose


Cumulative product of channel, column, or row elements

## Library

Math Functions / Math Operations

dspmathops

## Description



The Cumulative Product block computes the cumulative product along the specified dimension of the input or across time (running product).

The input can be a vector or matrix. The output always has the same dimensions, rate, data type, and complexity as the input.

## Input and Output Characteristics

### Valid Input

The Cumulative Product block accepts vector or matrix inputs containing real or complex values.

### Valid Reset Signal

The optional reset port, **Rst**, accepts scalar values, which can be any built-in Simulink data type including `boolean`. The rate of the input to the **Rst** port must be the same or slower than that of the input data signal. The sample time of the input to the **Rst** port must be a positive integer multiple of the input sample time.

### Output Characteristics

The output always has the same dimensions, rate, data type, and complexity as the data signal input.

## Computing the Running Product Along Channels of the Input

When you set the **Multiply input along** parameter to `Channels` (running product), the block computes the cumulative product of the elements in each input channel. The running product of the current input takes into account the running product of all previous inputs. In this mode, you must also specify a value for the **Input processing** parameter. When you set the **Input processing** parameter to `Columns as channels (frame based)`, the block computes the running product along each column of the current input. When you set the **Input processing** parameter to `Elements as channels (sample based)`,

# Cumulative Product

---

the block computes a running product for each element of the input across time. See the following sections for more information:

- Computing the Running Product for Each Column of the Input on page 342
- Computing the Running Product for Each Element of the Input on page 343
- Resetting the Running Product on page 344

## Computing the Running Product for Each Column of the Input

When you set the **Input processing** parameter to **Columns as channels** (frame based), the block treats each input column as an independent channel. As the following figure and equation illustrate, the output has the following characteristics:


- The first row of the first output is the same as the first row of the first input.
- The first row of each subsequent output is the element-wise product of the first row of the current input (time  $t$ ), and the last row of the previous output (time  $t - T_f$ , where  $T_f$  is the frame period).
- The output has the same size, dimension, data type, and complexity as the input.

Given an  $M$ -by- $N$  matrix input,  $u$ , the output,  $y$ , is an  $M$ -by- $N$  matrix whose first row has elements

$$y_{1,j}(t) = u_{1,j}(t) \cdot y_{M,j}(t - T_f)$$

# Cumulative Product

## Running Product for Each Column of the Input



## Computing the Running Product for Each Element of the Input

When you set the **Input processing** parameter to **Elements as channels (sample based)**, the block treats each element of the input matrix as an independent channel. As the following figure and equation illustrate, the output has the following characteristics:


- The first output is the same as the first input.
- Each subsequent output is the element-wise product of the current input (time  $t$ ) and the previous output (time  $t - T_s$ , where  $T_s$  is the sample period).
- The output has the same size, dimension, data type, and complexity as the input.

Given an  $M$ -by- $N$  matrix input,  $u$ , the output,  $y$ , is an  $M$ -by- $N$  matrix with the elements

$$y_{i,j}(t) = u_{i,j}(t) \cdot y_{i,j}(t - T_s) \quad \begin{matrix} 1 \leq i \leq M \\ 1 \leq j \leq N \end{matrix}$$

# Cumulative Product

For convenience, the block treats length- $M$  unoriented vector inputs as  $M$ -by-1 column vectors when multiplying along channels. In such cases, the output is a length- $M$  unoriented vector.



## Resetting the Running Product



When you are computing the running product, you can configure the block to reset the running product whenever it detects a reset event at the optional Rst port. The rate of the input to the Rst port must be the same or slower than that of the input data signal. The sample time of the input to the Rst port must be a positive integer multiple of the input sample time. The input to the Rst port can be of the Boolean data type.

If a reset event occurs while the block is performing sample-based processing, the block initializes the current output to the values of the current input. If a reset event occurs while the block is performing frame-based processing, the block initializes the first row of the current output to the values in the first row of the current input.

The **Reset port** parameter specifies the reset event, which can be one of the following:

- None disables the Rst port.


- **Rising edge** — Triggers a reset operation when the Rst input does one of the following:
  - Rises from a negative value to a positive value or zero
  - Rises from zero to a positive value, where the rise is not a continuation of a rise from a negative value to zero (see the following figure)



- **Falling edge** — Triggers a reset operation when the Rst input does one of the following:
  - Falls from a positive value to a negative value or zero
  - Falls from zero to a negative value, where the fall is not a continuation of a fall from a positive value to zero (see the following figure)

# Cumulative Product

---



- Either edge — Triggers a reset operation when the Rst input is a Rising edge or Falling edge (as described above)
- Non-zero sample — Triggers a reset operation at each sample time that the Rst input is not zero

---

**Note** When you run simulations in Simulink MultiTasking mode, reset signals have a one-sample latency. Thus, when the block detects a reset event, a one-sample delay occurs at the reset port rate before the block applies the reset. For more information on latency and the Simulink tasking modes, see “Excess Algorithmic Delay (Tasking Latency)” and “Scheduling” in the *Simulink Coder User’s Guide*.

---

## Multiplying Along Columns

When you set the **Multiply input along** parameter to **Columns**, the block computes the cumulative product of each column of the input. In this mode, the current cumulative product is independent of the cumulative products of previous inputs.

```
y = cumprod(u)      % Equivalent MATLAB code
```


The output has the same size, dimension, data type, and complexity as the input. The  $m$ th output row is the element-wise product of the first  $m$  input rows.

Given an  $M$ -by- $N$  input,  $u$ , the output,  $y$ , is an  $M$ -by- $N$  matrix whose  $j$ th column has elements

$$y_{i,j} = \prod_{k=1}^j u_{k,j} \quad 1 \leq i \leq M$$

When multiplying along columns, the block treats length- $M$  unoriented vector inputs as  $M$ -by-1 column vectors.

## Product Along Columns



## Multiplying Along Rows

When you set the **Multiply input along** parameter to Rows, the block computes the cumulative product of the row elements. In this mode, the current cumulative product is independent of the cumulative products of previous inputs.

```
y = cumprod(u,2) % Equivalent MATLAB code
```

The output has the same size, dimension, and data type as the input. The  $n$ th output column is the element-wise product of the first  $n$  input columns.


Given an  $M$ -by- $N$  matrix input,  $u$ , the output,  $y$ , is an  $M$ -by- $N$  matrix whose  $i$ th row has elements

# Cumulative Product

$$y_{i,j} = \prod_{k=1}^j u_{i,k} \quad 1 \leq j \leq N$$


When you multiply along rows, the block treats length- $N$  unoriented vector inputs as 1-by- $N$  row vectors.

## Product Along Rows



## Fixed-Point Data Types

The following diagram shows the data types used within the Cumulative Product block for fixed-point signals.




The output of the multiplier is in the product output data type when at least one of the inputs to the multiplier is real. When both of the inputs to the multiplier are complex, the result of the multiplication is

# Cumulative Product

in the accumulator data type. For details on the complex multiplication performed, see “Multiplication Data Types”. You can set the accumulator, product output, intermediate product, and output data types in the block dialog as discussed in “Dialog Box” on page 2-349.

## Dialog Box

The **Main** pane of the Cumulative Product block dialog appears as follows.



# Cumulative Product

---

## Multiply input along

Specify the dimension along which to compute the cumulative product. You can choose to multiply along Channels (running product), Columns, or Rows. For more information, see the following sections:

- “Computing the Running Product Along Channels of the Input” on page 2-341
- “Multiplying Along Columns” on page 2-346
- “Multiplying Along Rows” on page 2-347

## Input processing

Specify how the block should process the input when computing the running product along the channels of the input. You can set this parameter to one of the following options:

- Columns as channels (frame based) — When you select this option, the block treats each column of the input as a separate channel.
- Elements as channels (sample based) — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The option *Inherit from input* (this choice will be removed - see release notes) will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

This parameter is available only when you set the **Multiply input along** parameter to Channels (running product).


## Reset port

Determines the reset event that causes the block to reset the product along channels. The rate of the input to the Rst port must be the same or slower than that of the input data signal. The

# Cumulative Product

sample time of the input to the Rst port must be a positive integer multiple of the input sample time. This parameter appears only when you set the **Multiply input along** parameter to Channels (running product). For more information, see Resetting the Running Product on page 344.

The **Data Types** pane of the Cumulative Product block dialog appears as follows.



# Cumulative Product

---

---

**Note** Floating-point inheritance takes precedence over the data type settings defined on this pane. When inputs are floating point, the block ignores these settings, and all internal data types are floating point.

---

## Rounding mode

Select the rounding mode for fixed-point operations.

## Overflow mode

Select the overflow mode for fixed-point operations.

## Intermediate product

Specify the intermediate product data type. As shown in “Fixed-Point Data Types” on page 2-348, the output of the multiplier is cast to the intermediate product data type before the next element of the input is multiplied into it. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as input`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Product output data type

Specify the product output data type. See “Fixed-Point Data Types” on page 2-348 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as input`

- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`


Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

### Accumulator data type

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-348 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Same as input`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

### Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-348 for illustrations depicting the use of the output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as input`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

# Cumulative Product

---

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

## Minimum

Specify the minimum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Maximum

Specify the maximum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## Supported Data Types

Input and Output Ports	Supported Data Types
Data input port, In	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>

Input and Output Ports	Supported Data Types
	<ul style="list-style-type: none"> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>
Reset input port, Rst	All built-in Simulink data types: <ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>
Output port	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>

## See Also

Cumulative Sum	DSP System Toolbox
Matrix Product	DSP System Toolbox
cumprod	MATLAB

# Cumulative Sum

---

## Purpose

Cumulative sum of channel, column, or row elements

## Library

Math Functions / Math Operations

dspmathops

## Description



The Cumulative Sum block computes the cumulative sum along the specified dimension of the input or across time (running sum).

The inputs can be a vector or a matrix. The output always has the same dimensions, rate, data type, and complexity as the input.

## Input and Output Characteristics

### Valid Input

The Cumulative Sum block accepts vector or matrix inputs containing real or complex values.

### Valid Reset Signal

The optional reset port, **Rst**, accepts scalar values, which can be any built-in Simulink data type including `boolean`. The rate of the input to the **Rst** port must be the same or slower than that of the input data signal. The sample time of the input to the **Rst** port must be a positive integer multiple of the input sample time.

### Output Characteristics

The output always has the same dimensions, rate, data type, and complexity as the data signal input.

## Computing the Running Sum Along Channels of the Input

When you set the **Sum input along** parameter to `Channels` (running sum), the block computes the cumulative sum of the elements in each input channel. The running sum of the current input takes into account the running sum of all previous inputs. In this mode, you must also specify a value for the **Input processing** parameter. When you set the **Input processing** parameter to `Columns` as channels (frame based), the block computes the running sum along each column of the current input. When you set the **Input processing** parameter to `Elements` as channels (sample based), the block computes

a running sum for each element of the input across time. See the following sections for more information:

- Computing the Running Sum for Each Column of the Input on page 357
- Computing the Running Sum for Each Element of the Input on page 358
- Resetting the Running Sum on page 359

### Computing the Running Sum for Each Column of the Input

When you set the **Input processing** parameter to `Columns as channels (frame based)`, the block treats each input column as an independent channel. As the following figure and equation illustrate, the output has the following characteristics:


- The first row of the first output is the same as the first row of the first input.
- The first row of each subsequent output is the sum of the first row of the current input (time  $t$ ), and the last row of the previous output (time  $t - T_f$  where  $T_f$  is the frame period).
- The output has the same size, dimension, data type, and complexity as the input.

Given an  $M$ -by- $N$  matrix input,  $u$ , the output,  $y$ , is an  $M$ -by- $N$  matrix whose first row has elements

$$y_{1,j}(t) = u_{1,j}(t) + y_{M,j}(t - T_f)$$

# Cumulative Sum

Running Sum for Each Column of the Input



## Computing the Running Sum for Each Element of the Input


When you set the **Input processing** parameter to **Elements** as **channels** (sample based), the block treats each element of the input matrix as an independent channel. As the following figure and equation illustrate, the output has the following characteristics:

- The first output is the same as the first input.
- Each subsequent output is the sum of the current input (time  $t$ ) and the previous output (time  $t - T_s$ , where  $T_s$  is the sample period).
- The output has the same size, dimension, data type, and complexity as the input.

Given an  $M$ -by- $N$  matrix input,  $u$ , the output,  $y$ , is an  $M$ -by- $N$  matrix with the elements

$$y_{i,j}(t) = u_{i,j}(t) + y_{i,j}(t - T_s) \quad \begin{matrix} 1 \leq i \leq M \\ 1 \leq j \leq N \end{matrix}$$

## Running Sum for Each Element of the Input



### Resetting the Running Sum

When you are computing the running sum, you can configure the block to reset the running sum whenever it detects a reset event at the optional Rst port. The rate of the input to the Rst port must be the same or slower than that of the input data signal. The sample time of the input to the Rst port must be a positive integer multiple of the input sample time. The reset sample time must be a positive integer multiple of the input sample time. The input to the Rst port can be of the boolean data type.

If a reset event occurs while the block is performing sample-based processing, the block initializes the current output to the values of the current input. If a reset event occurs while the block is performing frame-based processing, the block initializes the first row of the current output to the values in the first row of the current input.


The **Reset port** parameter specifies the reset event, which can be one of the following:

- None disables the Rst port.


# Cumulative Sum

---

- **Rising edge** — Triggers a reset operation when the Rst input does one of the following:
  - Rises from a negative value to a positive value or zero
  - Rises from zero to a positive value, where the rise is not a continuation of a rise from a negative value to zero (see the following figure)



- **Falling edge** — Triggers a reset operation when the Rst input does one of the following:
  - Falls from a positive value to a negative value or zero
  - Falls from zero to a negative value, where the fall is not a continuation of a fall from a positive value to zero (see the following figure)



- **Either edge** — Triggers a reset operation when the Rst input is a Rising edge or Falling edge (as described above)
- **Non-zero sample** — Triggers a reset operation at each sample time that the Rst input is not zero

---

**Note** When you run simulations in the Simulink MultiTasking mode, reset signals have a one-sample latency. Thus, when the block detects a reset event, a one-sample delay occurs at the reset port rate before the block applies the reset. For more information on latency and the Simulink tasking modes, see “Excess Algorithmic Delay (Tasking Latency)” and the topic on models with multiple sample rates in the Simulink Coder documentation.

---

## Summing Along Columns

When you set the **Sum input along** parameter to **Columns**, the block computes the cumulative sum of each column of the input. In this mode, the current cumulative sum is independent of the cumulative sums of previous inputs.

```
y = cumsum(u)           % Equivalent MATLAB code
```

The output has the same size, dimension, data type, and complexity as the input. The  $m$ th output row is the sum of the first  $m$  input rows.


# Cumulative Sum

Given an  $M$ -by- $N$  input,  $u$ , the output,  $y$ , is an  $M$ -by- $N$  matrix whose  $j$ th column has elements

$$y_{i,j} = \sum_{k=1}^j u_{k,j} \quad 1 \leq i \leq M$$

The block treats length- $M$  unoriented vector inputs as  $M$ -by-1 column vectors when summing along columns.

## Sum Along Columns



## Summing Along Rows

When you set the **Sum input along** parameter to Rows, the block computes the cumulative sum of the row elements. In this mode, the current cumulative sum is independent of the cumulative sums of previous inputs.

`y = cumsum(u,2)`      % Equivalent MATLAB code


The output has the same size, dimension, and data type as the input. The  $n$ th output column is the sum of the first  $n$  input columns.

Given an  $M$ -by- $N$  input,  $u$ , the output,  $y$ , is an  $M$ -by- $N$  matrix whose  $i$ th row has elements

$$y_{i,j} = \sum_{k=1}^j u_{i,k} \quad 1 \leq j \leq N$$


When you sum along rows, the block treats length- $N$  unoriented vector inputs as 1-by- $N$  row vectors.

## Sum Along Rows



## Fixed-Point Data Types

The following diagram shows the data types used within the Cumulative Sum block for fixed-point signals.




You can set the accumulator and output data types in the block dialog as discussed in “Dialog Box” on page 2-363.

## Dialog Box

The **Main** pane of the Cumulative Sum block dialog appears as follows.

# Cumulative Sum



## Sum input along

Specify the dimension along which to compute the cumulative summations. You can choose to sum along **Channels** (running sum), **Columns**, or **Rows**. For more information, see the following sections:

- “Computing the Running Sum Along Channels of the Input” on page 2-356
- “Summing Along Columns” on page 2-361
- “Summing Along Rows” on page 2-362

## Input processing

Specify how the block should process the input when computing the running sum along the channels of the input. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The option **Inherit from input** (this choice will be removed - see release notes) will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---


This parameter is available only when you set the **Sum input along** parameter to **Channels (running sum)**.

## Reset port

Determines the reset event that causes the block to reset the sum along channels. The rate of the input to the Rst port must be the same or slower than that of the input data signal. The sample time of the input to the Rst port must be a positive integer multiple of the input sample time. This parameter appears only when you set the **Sum input along** parameter to **Channels (running sum)**. For more information, see *Resetting the Running Sum* on page 359.

The **Data Types** pane of the Cumulative Sum block dialog appears as follows.

# Cumulative Sum



---

**Note** Floating-point inheritance takes precedence over the data type settings defined on this pane. When inputs are floating point, the block ignores these settings, and all internal data types are floating point.

---

## **Rounding mode**

Select the rounding mode for fixed-point operations.

## **Overflow mode**

Select the overflow mode for fixed-point operations.

## Accumulator data type

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-363 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Same as input`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-363 for illustrations depicting the use of the output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as accumulator`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

# Cumulative Sum

---

## Minimum

Specify the minimum value that the block should output. The default value is [ ] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Maximum

Specify the maximum value that the block should output. The default value is [ ] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## Supported Data Types

Input and Output Ports	Supported Data Types
Data input port, In	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Reset input port, Rst	All built-in Simulink data types: <ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Boolean</li></ul>

Input and Output Ports	Supported Data Types
	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Output port	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

## See Also

Cumulative Product	DSP System Toolbox
Difference	DSP System Toolbox
Matrix Sum	DSP System Toolbox
cumsum	MATLAB

# Data Type Conversion


---

<b>Purpose</b>	Convert input signal to specified data type
<b>Library</b>	Signal Management / Signal Attributes dspattributes
<b>Description</b>	The Data Type Conversion block is an implementation of the Simulink Data Type Conversion block. See Data Type Conversion for more information.

**Purpose** Convert magnitude data to decibels (dB or dBm)

**Library** Math Functions / Math Operations  
dspmathops

## Description



The dB Conversion block converts a linearly scaled power or amplitude input to dB or dBm. The reference power is 1 Watt for conversions to dB and 1 mWatt for conversions to dBm. The **Input signal** parameter specifies whether the input is a power signal or a voltage signal, and the **Convert to** parameter controls the scaling of the output. When selected, the **Add eps to input to protect against “log(0) = -inf”** parameter adds a value of `eps` to all power and voltage inputs. When this option is not enabled, zero-valued inputs produce `-inf` at the output.

The output is the same size as the input.

### Power Inputs

Select **Power** as the **Input signal** parameter when the input, `u`, is a real, nonnegative, power signal (units of watts). When the **Convert to** parameter is set to **dB**, the block performs the dB conversion

$$y = 10 \cdot \log_{10}(u) \quad \% \text{ Equivalent MATLAB code}$$

When the **Convert to** parameter is set to **dBm**, the block performs the dBm conversion

$$y = 10 \cdot \log_{10}(u) + 30$$

The dBm conversion is equivalent to performing the dB operation *after* converting the input to milliwatts.

### Voltage Inputs

Select **Amplitude** as the **Input signal** parameter when the input, `u`, is a real voltage signal (units of volts). The block uses the scale factor specified in ohms by the **Load resistance** parameter, `R`, to convert the voltage input to units of power (watts) before converting to dB or dBm.

## dB Conversion

---

When the **Convert to** parameter is set to dB, the block performs the dB conversion


$$y = 10 \cdot \log_{10}(\text{abs}(u)^2/R)$$

When the **Convert to** parameter is set to dBm, the block performs the dBm conversion

$$y = 10 \cdot \log_{10}(\text{abs}(u)^2/R) + 30$$

The dBm conversion is equivalent to performing the dB operation *after* converting the  $(\text{abs}(u)^2/R)$  result to milliwatts.

## Dialog Box



### Convert to

The logarithmic scaling to which the input is converted, dB or dBm. The reference power is 1 W for conversions to dB and 1 mW for conversions to dBm. Tunable.

### Input signal

The type of input signal, Power or Amplitude.

### Load resistance

The scale factor used to convert voltage inputs to units of power. Tunable.

### Add eps to input to protect against “log(0) = -inf”

When selected, adds eps to all input values (power or voltage). Tunable.

# dB Conversion

---

## Supported Data Types

- Double-precision floating point
- Single-precision floating point

## See Also

dB Gain	DSP System Toolbox
Math Function	Simulink
log10	MATLAB

## Purpose


Apply decibel gain

## Library

Math Functions / Math Operations

dspmathops

## Description



The dB Gain block multiplies the input by the decibel values specified in the **Gain** parameter. For an  $M$ -by- $N$  input matrix  $u$  with elements  $u_{ij}$ , the **Gain** parameter can be a real  $M$ -by- $N$  matrix with elements  $g_{ij}$  to be multiplied element-wise with the input, or a real scalar.

$$y_{ij} = 10u_{ij}^{(g_{ij}/k)}$$

The value of  $k$  is 10 for power signals (select **Power** as the **Input signal** parameter) and 20 for voltage signals (select **Amplitude** as the **Input signal** parameter).

The value of the equivalent linear gain


$$g_{ij}^{lin} = 10^{(g_{ij}/k)}$$

is displayed in the block icon below the dB gain value. The output is the same size as the input.

The dB Gain block supports real and complex floating-point and fixed-point data types.

### Fixed-Point Data Types

The following diagram shows the data types used within the dB Gain subsystem block for fixed-point signals.




The settings for the fixed-point parameters of the Gain block in the diagram above are as follows:

# dB Gain

---

- Integer rounding mode: Floor
- Saturate on integer overflow — unselected
- Parameter data type mode — Inherit via internal rule
- Output data type mode — Inherit via internal rule

See the Gain reference page for more information.



## Dialog Box

### Gain

The dB gain to apply to the input, a scalar or a real  $M$ -by- $N$  matrix. Tunable.

### Input signal

The type of input signal: Power or Amplitude. Tunable.

---

**Note** This block does not support tunability in generated code.

---

## Supported Data Types

- Double-precision floating point
- Single-precision floating point
- Fixed point (signed and unsigned)

- 8-, 16-, and 32-bit signed integers
- 8-, 16-, and 32-bit unsigned integers

## See Also

dB Conversion

DSP System Toolbox

Math Function

Simulink


log10

MATLAB

**Purpose** Discrete cosine transform (DCT) of input

**Library** Transforms  
dspxfm3

## Description



The DCT block computes the unitary discrete cosine transform (DCT) of each channel in the  $M$ -by- $N$  input matrix,  $u$ .

```
y = dct(u) % Equivalent MATLAB code
```

When the input is a sample-based row vector, the DCT block computes the discrete cosine transform across the vector dimension of the input. For all other N-D input arrays, the block computes the DCT across the first dimension. The size of the first dimension (frame size), must be a power of two. To work with other frame sizes, use the Pad block to pad or truncate the frame size to a power-of-two length.

When the input to the DCT block is an  $M$ -by- $N$  matrix, the block treats each input column as an independent channel containing  $M$  consecutive samples. The block outputs an  $M$ -by- $N$  matrix whose  $l$ th column contains the length- $M$  DCT of the corresponding input column.

$$y(k,l) = w(k) \sum_{m=1}^M u(m,l) \cos \frac{\pi(2m-1)(k-1)}{2M}, \quad k = 1, \dots, M$$

where

$$w(k) = \begin{cases} \frac{1}{\sqrt{M}}, & k = 1 \\ \sqrt{\frac{2}{M}}, & 2 \leq k \leq M \end{cases}$$

The **Sine and cosine computation** parameter determines how the block computes the necessary sine and cosine values. This parameter has two settings, each with its advantages and disadvantages, as described in the following table.

Sine and Cosine Computation Parameter Setting	Sine and Cosine Computation Method	Effect on Block Performance
Table lookup	The block computes and stores the trigonometric values before the simulation starts, and retrieves them during the simulation. When you generate code from the block, the processor running the generated code stores the trigonometric values computed by the block in a speed-optimized table, and retrieves the values during code execution.	The block usually runs much more quickly, but requires extra memory for storing the precomputed trigonometric values.
Trigonometric fcn	The block computes sine and cosine values during the simulation. When you generate code from the block, the processor running the generated code computes the sine and cosine values while the code runs.	The block usually runs more slowly, but does not need extra data memory. For code generation, the block requires a support library to emulate the trigonometric functions, increasing the size of the generated code.




This block supports Simulink virtual buses.

### Fixed-Point Data Types


The following diagrams show the data types used within the DCT block for fixed-point signals. You can set the sine table, accumulator, product output, and output data types displayed in the diagrams in the DCT block dialog as discussed in “Dialog Box” on page 2-382.

Inputs to the DCT block are first cast to the output data type and stored in the output buffer. Each butterfly stage processes signals in the accumulator data type, with the final output of the butterfly being cast back into the output data type.


# DCT



## Butterfly Stage Data Types



## Twiddle Multiplication Data Types



The output of the multiplier is in the product output data type when at least one of the inputs to the multiplier is real. When both of the

---

inputs to the multiplier are complex, the result of the multiplication is in the accumulator data type. For details on the complex multiplication performed, see “Multiplication Data Types”.

---

**Note** When the block input is fixed point, all internal data types are signed fixed point.


---

# DCT

---

## Dialog Box

The **Main** pane of the DCT block dialog appears as follows.




### Sine and cosine computation

Sets the block to compute sines and cosines by either looking up sine and cosine values in a speed-optimized table (**Table lookup**),

or by making sine and cosine function calls (Trigonometric fcn).

See the table in the “Description ” on page 2-378 section.

The **Data Types** pane of the DCT block dialog appears as follows.



## **Rounding mode**

Select the rounding mode for fixed-point operations. The sine table values do not obey this parameter; they always round to Nearest.

## **Overflow mode**

Select the overflow mode for fixed-point operations. The sine table values do not obey this parameter; instead, they are always saturated.

## **Sine table data type**

Choose how you specify the word length of the values of the sine table. The fraction length of the sine table values always equals the word length minus one. You can set this parameter to:


- A rule that inherits a data type, for example, `Inherit: Same word length as input`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16)`

The sine table values do not obey the **Rounding mode** and **Overflow mode** parameters; instead, they are always saturated and rounded to Nearest.

## **Product output data type**

Specify the product output data type. See “Fixed-Point Data Types” on page 2-379 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

### Accumulator data type

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-379 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

### Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-379 for illustrations depicting the use of the output data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule.`


When you select `Inherit: Inherit via internal rule`, the block calculates the output word length and fraction length automatically. The internal rule first calculates an ideal output word length and fraction length using the following equations:

$$WL_{ideal\ output} = WL_{input} + \text{floor}(\log_2(DCT\ length - 1)) + 1$$

$$FL_{ideal\ output} = FL_{input}$$

Using these ideal results, the internal rule then selects word lengths and fraction lengths that are appropriate for your hardware. For more information, see “Inherit via Internal Rule”.

- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

### Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed and unsigned)</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>
Output	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed only)</li> <li>• 8-, 16-, and 32-bit signed integers</li> </ul>

**See Also**

Complex Cepstrum	DSP System Toolbox
FFT	DSP System Toolbox
IDCT	DSP System Toolbox
Real Cepstrum	DSP System Toolbox
dct	Signal Processing Toolbox


# Delay

---

**Purpose** Delay discrete-time input by specified number of samples or frames

**Library** Signal Operations  
dsp\_sigops

## Description



The Delay block delays a discrete-time input by the number of samples or frames specified in the **Delay units** and **Delay** parameters. The **Delay** value must be an integer value greater than or equal to zero. When you enter a value of zero for the **Delay** parameter, any initial conditions you might have entered have no effect on the output.

The Delay block allows you to set the initial conditions of the signal that is being delayed. The initial conditions must be numeric.

### Frame-Based Processing

When you set the **Input processing** parameter to **Columns as channels (frame based)**, the block treats each column of the  $M$ -by- $N$  input matrix as an independent channel. The block delays each channel of the input as specified by the **Delay** parameter.

The **Delay** parameter can be a scalar integer by which the block equally delays all channels or a vector whose length is equal to the number of channels.

There are four different choices for initial conditions. The initial conditions can be the same or different for each channel. They can also be constant or varying along each channel. See the “Frame-Based Processing Examples” on page 2-391 section for more information.

### Sample-Based Processing

When you set the **Input processing** parameter to **Elements as channels (sample based)**, the block treats each element of the N-D input array as an independent channel. Thus, the total number of channels in the input is equal to the product of the input dimensions. The dimension of the output is the same as that of the input.

The **Delay** parameter can be a scalar integer by which to equally delay all channels or an N-D array of the same dimensions as the input array,

containing nonnegative integers that specify the number of sample intervals to delay each channel of the input.


There are four different choices for initial conditions. The initial conditions can be the same or different for each channel. They can also be the same or different within a channel. See the “Sample-Based Processing Examples” on page 2-395 section for more information.

## Resetting the Delay

The Delay block resets the delay whenever it detects a reset event at the optional **Rst** port. The reset sample time must be a positive integer multiple of the input sample time.

The reset event is specified by the **Reset port** parameter, and can be one of the following:


- None disables the **Rst** port.
- Rising edge triggers a reset operation when the **Rst** input does one of the following:
  - Rises from a negative value to a positive value or zero
  - Rises from zero to a positive value, where the rise is not a continuation of a rise from a negative value to zero (see the following figure)



# Delay

---

- Falling edge triggers a reset operation when the Rst input does one of the following:
  - Falls from a positive value to a negative value or zero
  - Falls from zero to a negative value, where the fall is not a continuation of a fall from a positive value to zero (see the following figure)



- Either edge triggers a reset operation when the Rst input is Rising edge or Falling edge (as described earlier).
- Non-zero sample triggers a reset operation at each sample time that the Rst input is not zero.

---

**Note** When running simulations in the Simulink MultiTasking mode, reset signals have a one-sample latency. Therefore, when the block detects a reset event, there is a one-sample delay at the reset port rate before the block applies the reset. For more information on latency and the Simulink tasking modes, see “Excess Algorithmic Delay (Tasking Latency)” and “Scheduling” in the *Simulink Coder User’s Guide*.

---

This block supports Simulink virtual buses.

## Examples

### Frame-Based Processing Examples

There are four different choices for initial conditions. The initial conditions can be the same or different for each channel. They can also be constant or varying along each channel. The next sections describe the behavior of the block for each of these four cases:

- “Case 1 — Use the Same Initial Conditions for Each Channel and Within a Channel” on page 2-391
- “Case 2 — Use Different Initial Conditions for Each Channel and the Same Initial Conditions Within a Channel” on page 2-392
- “Case 3 — Use the Same Initial Conditions for Each Channel and Different Initial Conditions Within a Channel” on page 2-393
- “Case 4 — Use Different Initial Conditions for Each Channel and Within a Channel” on page 2-394

#### Case 1 — Use the Same Initial Conditions for Each Channel and Within a Channel

Enter a scalar value for the initial conditions. This value is used as the constant initial condition value for each of the channels.

For example, suppose your input is a matrix and you set the **Input processing** parameter to **Columns** as channels (frame based).

$$\begin{bmatrix} 1 & 1 & 1 \\ 2 & 2 & 2 \\ 3 & 3 & 3 \end{bmatrix}, \begin{bmatrix} 4 & 4 & 4 \\ 5 & 5 & 5 \\ 6 & 6 & 6 \end{bmatrix}, \begin{bmatrix} 7 & 7 & 7 \\ 8 & 8 & 8 \\ 9 & 9 & 9 \end{bmatrix}, \dots$$

You want the initial conditions of your three-channel signal to be identical and zero for the first frame:

- 1 Set the **Delay (frames)** parameter to 1.
- 2 Clear the **Specify different initial conditions for each channel** and the **Specify different initial conditions within a channel** check boxes.

- 3 Set the **Initial conditions** parameter to a scalar value of 0.

The output of the delay block is

$$\begin{bmatrix} 0 & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & 0 \end{bmatrix}, \begin{bmatrix} 1 & 1 & 1 \\ 2 & 2 & 2 \\ 3 & 3 & 3 \end{bmatrix}, \begin{bmatrix} 4 & 4 & 4 \\ 5 & 5 & 5 \\ 6 & 6 & 6 \end{bmatrix}, \begin{bmatrix} 7 & 7 & 7 \\ 8 & 8 & 8 \\ 9 & 9 & 9 \end{bmatrix}, \dots$$

0, the scalar initial condition value, is used across the channels and within the channels for the first frame. This frame is the output at sample time zero.

## Case 2 – Use Different Initial Conditions for Each Channel and the Same Initial Conditions Within a Channel

The initial conditions must be a vector of length  $N$ , where  $N \geq 1$ .  $N$  is also equal to the number of channels in your signal. These initial condition values are used as the constant initial condition value for each of the channels.

For example, suppose your input is a matrix and you set the **Input processing** parameter to Columns as channels (frame based).

$$\begin{bmatrix} 1 & 1 & 1 \\ 2 & 2 & 2 \\ 3 & 3 & 3 \end{bmatrix}, \begin{bmatrix} 4 & 4 & 4 \\ 5 & 5 & 5 \\ 6 & 6 & 6 \end{bmatrix}, \begin{bmatrix} 7 & 7 & 7 \\ 8 & 8 & 8 \\ 9 & 9 & 9 \end{bmatrix}, \dots$$

You want the initial conditions of your three-channel signal to be [0 10 20] for the first frame:

- 1 Set the **Delay (frames)** parameter to 1.
- 2 Select the **Specify different initial conditions for each channel** check box.
- 3 Clear the **Specify different initial conditions within a channel** check box.

**4** Set the **Initial conditions** parameter to [0 10 20].

The output of the delay block is

$$\begin{bmatrix} 0 & 10 & 20 \\ 0 & 10 & 20 \\ 0 & 10 & 20 \end{bmatrix}, \begin{bmatrix} 1 & 1 & 1 \\ 2 & 2 & 2 \\ 3 & 3 & 3 \end{bmatrix}, \begin{bmatrix} 4 & 4 & 4 \\ 5 & 5 & 5 \\ 6 & 6 & 6 \end{bmatrix}, \begin{bmatrix} 7 & 7 & 7 \\ 8 & 8 & 8 \\ 9 & 9 & 9 \end{bmatrix}, \dots$$

The initial condition vector expands to create the frame that is output at sample time zero. Different initial conditions are used for each channel, but the same initial condition value is used with a channel.

### Case 3 – Use the Same Initial Conditions for Each Channel and Different Initial Conditions Within a Channel

In this case, the **Delay** parameter can be a scalar integer by which to equally delay all channels or a vector whose length is equal to the number of channels. All the values of this vector must be equal.

Enter the initial conditions as a vector. These values are used as the initial condition value along each of the channels to be delayed. The initial condition vector must have length equal to the value of the **Delay (frames)** parameter multiplied by the frame length. For example, if you want to delay your signal by two frames with frame length two and an initial condition value of 3, enter your initial condition vector as [3 3 3 3].

For example, suppose your input is a matrix and you set the **Input processing** parameter to **Columns** as channels (frame based).

$$\begin{bmatrix} 1 & 1 & 1 \\ 2 & 2 & 2 \\ 3 & 3 & 3 \end{bmatrix}, \begin{bmatrix} 4 & 4 & 4 \\ 5 & 5 & 5 \\ 6 & 6 & 6 \end{bmatrix}, \begin{bmatrix} 7 & 7 & 7 \\ 8 & 8 & 8 \\ 9 & 9 & 9 \end{bmatrix}, \dots$$

You want the initial conditions of your three-channel signal to be the same along each of the channels to be delayed:

**1** Set the **Delay (frame)** parameter to 1.

- 2 Clear the **Specify different initial conditions for each channel** check box.
- 3 Select the **Specify different initial conditions within a channel** check box.
- 4 Set the **Initial conditions** parameter to [10 20 30].

The output of the delay block is

$$\begin{bmatrix} 10 & 10 & 10 \\ 20 & 20 & 20 \\ 30 & 30 & 30 \end{bmatrix}, \begin{bmatrix} 1 & 1 & 1 \\ 2 & 2 & 2 \\ 3 & 3 & 3 \end{bmatrix}, \begin{bmatrix} 4 & 4 & 4 \\ 5 & 5 & 5 \\ 6 & 6 & 6 \end{bmatrix}, \begin{bmatrix} 7 & 7 & 7 \\ 8 & 8 & 8 \\ 9 & 9 & 9 \end{bmatrix}, \dots$$

The initial condition vector defines the initial condition values within each of the three channels. The same initial conditions are used for each channel, but different initial condition values are used with a channel.

## Case 4 – Use Different Initial Conditions for Each Channel and Within a Channel

Enter a cell array for your initial condition values. Or, when you have a scalar delay value, you can enter the initial conditions as a matrix.

For example, suppose your input is a matrix and you set the **Input processing** parameter to `Columns as channels` (frame based).

$$\begin{bmatrix} 1 & 1 & 1 \\ 2 & 2 & 2 \\ 3 & 3 & 3 \end{bmatrix}, \begin{bmatrix} 4 & 4 & 4 \\ 5 & 5 & 5 \\ 6 & 6 & 6 \end{bmatrix}, \begin{bmatrix} 7 & 7 & 7 \\ 8 & 8 & 8 \\ 9 & 9 & 9 \end{bmatrix}, \dots$$

You want the initial conditions of your three-channel signal to be different for each channel and along each channel.

- 1 Set the **Delay (frames)** parameter to 1.

- 2 Select the **Specify different initial conditions for each channel** and the **Specify different initial conditions within a channel** check boxes.
- 3 Set the **Initial conditions** parameter to either `[10 20 30; 40 50 60; 70 80 90]` or `{[10 40 70];[20 50 80];[30 60 90]}`. Each cell of the cell array represents the delay along one channel.

Regardless of whether you use a matrix or cell array, the output of the delay block is

$$\begin{bmatrix} 10 & 20 & 30 \\ 40 & 50 & 60 \\ 70 & 80 & 90 \end{bmatrix}, \begin{bmatrix} 1 & 1 & 1 \\ 2 & 2 & 2 \\ 3 & 3 & 3 \end{bmatrix}, \begin{bmatrix} 4 & 4 & 4 \\ 5 & 5 & 5 \\ 6 & 6 & 6 \end{bmatrix}, \begin{bmatrix} 7 & 7 & 7 \\ 8 & 8 & 8 \\ 9 & 9 & 9 \end{bmatrix} \dots$$

The initial condition matrix is the output at sample time zero. The elements of the initial condition cell array define the initial condition values within each channel. The first element, a vector, represents the initial conditions within channel 1. The second element, a vector, represents the initial conditions within channel 2, and so on. Different initial conditions are used for each channel and within the channels.

## Sample-Based Processing Examples

There are four different choices for initial conditions. The initial conditions can be the same or different for each channel. They can also be the same or different along each channel. The next sections describe the behavior of the block for each of these four cases:

- “Case 1 — Use the Same Initial Conditions for Each Channel and Within a Channel” on page 2-396
- “Case 2 — Use Different Initial Conditions for Each Channel and the Same Initial Conditions Within a Channel” on page 2-397
- “Case 3 — Use the Same Initial Conditions for Each Channel and Different Initial Conditions Within a Channel” on page 2-398

- “Case 4 — Use Different Initial Conditions for Each Channel and Within a Channel” on page 2-399

## Case 1 — Use the Same Initial Conditions for Each Channel and Within a Channel

Enter a scalar value for the initial conditions. This value is used as the constant initial condition value for each of the channels.

For example, suppose your input is a matrix and you set the **Input processing** parameter to `Elements as channels (sample based)`.

$$\begin{bmatrix} 1 & 1 \\ 1 & 1 \end{bmatrix}, \begin{bmatrix} 2 & 2 \\ 2 & 2 \end{bmatrix}, \begin{bmatrix} 3 & 3 \\ 3 & 3 \end{bmatrix}, \dots$$

You want the initial conditions of your four-channel signal to be identical and zero for the first two samples:

- 1 Set the **Delay (samples)** parameter to 2.
- 2 Clear the **Specify different initial conditions for each channel** and **Specify different initial conditions within a channel** check boxes.
- 3 Set the **Initial conditions** parameter to a scalar value of 0.

The output of the delay block is

$$\begin{bmatrix} 0 & 0 \\ 0 & 0 \end{bmatrix}, \begin{bmatrix} 0 & 0 \\ 0 & 0 \end{bmatrix}, \begin{bmatrix} 1 & 1 \\ 1 & 1 \end{bmatrix}, \begin{bmatrix} 2 & 2 \\ 2 & 2 \end{bmatrix}, \begin{bmatrix} 3 & 3 \\ 3 & 3 \end{bmatrix}, \dots$$

0, the scalar initial condition value, is used for each channel and within the channels. It is the output at sample time zero and sample time one.

## Case 2 – Use Different Initial Conditions for Each Channel and the Same Initial Conditions Within a Channel

The initial conditions must be an N-D array for N-D input. The initial conditions must have the same dimensions as the input data. These initial condition values are used as the constant initial condition value for each of the channels.

For example, suppose your input is a matrix and you set the **Input processing** parameter to `Elements as channels (sample based)`.

$$\begin{bmatrix} 1 & 1 \\ 1 & 1 \end{bmatrix}, \begin{bmatrix} 2 & 2 \\ 2 & 2 \end{bmatrix}, \begin{bmatrix} 3 & 3 \\ 3 & 3 \end{bmatrix}, \dots$$

You want the initial conditions of your four-channel signal to be

$$\begin{bmatrix} 7 & 9 \\ 11 & 13 \end{bmatrix}$$

for the first two samples:

- 1** Set the **Delay (samples)** parameter to 2.
- 2** Select the **Specify different initial conditions for each channel** check box.
- 3** Clear the **Specify different initial conditions within a channel** check box.
- 4** Set the **Initial conditions** parameter to `[7 9; 11 13]`.

The output of the delay block is

$$\begin{bmatrix} 7 & 9 \\ 11 & 13 \end{bmatrix}, \begin{bmatrix} 7 & 9 \\ 11 & 13 \end{bmatrix}, \begin{bmatrix} 1 & 1 \\ 1 & 1 \end{bmatrix}, \begin{bmatrix} 2 & 2 \\ 2 & 2 \end{bmatrix}, \begin{bmatrix} 3 & 3 \\ 3 & 3 \end{bmatrix}, \dots$$

The initial condition matrix is the output at sample time zero and sample time one. Different initial conditions are used for each channel; the same initial condition value is used within a channel.

### **Case 3 – Use the Same Initial Conditions for Each Channel and Different Initial Conditions Within a Channel**

In this case, for N-D sample-based inputs, the initial conditions parameter must be a vector whose length is equal to the delay value, specified by the **Delay** parameter. The values in this vector are used as the initial condition values along each of the channels to be delayed.

For example, suppose your input is a matrix and you set the **Input processing** parameter to `Elements as channels (sample based)`.

$$\begin{bmatrix} 1 & 1 \\ 1 & 1 \end{bmatrix}, \begin{bmatrix} 2 & 2 \\ 2 & 2 \end{bmatrix}, \begin{bmatrix} 3 & 3 \\ 3 & 3 \end{bmatrix}, \dots$$

You want the initial conditions of your four channel signal to be the same along each of the channels to be delayed:

- 1** Set the **Delay (samples)** parameter to 2.
- 2** Clear the **Specify different initial conditions for each channel** check box.
- 3** Select the **Specify different initial conditions within a channel** check box.
- 4** Set the **Initial conditions** parameter to [10 20].

The output of the delay block is

$$\begin{bmatrix} 10 & 10 \\ 10 & 10 \end{bmatrix}, \begin{bmatrix} 20 & 20 \\ 20 & 20 \end{bmatrix}, \begin{bmatrix} 1 & 1 \\ 1 & 1 \end{bmatrix}, \begin{bmatrix} 2 & 2 \\ 2 & 2 \end{bmatrix}, \begin{bmatrix} 3 & 3 \\ 3 & 3 \end{bmatrix}, \dots$$

The first element of the initial conditions vector is the output, for all channels, at sample time zero. The second element of the initial

conditions vector is the output, for all channels, at sample time one. The same initial conditions are used for each channel, but different initial condition values are used within a channel.

#### **Case 4 – Use Different Initial Conditions for Each Channel and Within a Channel**

Enter a cell array for your initial condition values. The cell array must be the same size as your input signal. Each cell of the cell array represents the delay values for one channel, and must be a vector of size equal to the delay value. If you have a vector or scalar input and a scalar delay value, you can enter the initial conditions as a matrix.

For example, suppose your input is a matrix and you set the **Input processing** parameter to **Elements as channels** (sample based).

[1 1], [2 2], [3 3],...

You want the initial conditions of your two channel signal to be different for each channel and along each channel:

- 1** Set the **Delay (samples)** parameter to 2.
- 2** Select the **Specify different initial conditions for each channel** and **Specify different initial conditions within a channel** check boxes.
- 3** Set the **Initial conditions** parameter to [10 20; 30 40].

The output of the delay block is

[10 20], [30 40], [1 1], [2 2]...

The first row of the initial conditions vector is the output at sample time zero. The second row of the initial conditions vector is the output at sample time one. Different initial conditions are used for each channel and within the channels.

In addition, suppose your input is a matrix and you set the **Input processing** parameter to `Elements as channels (sample based)`.

$$\begin{bmatrix} 1 & 1 \\ 1 & 1 \end{bmatrix}, \begin{bmatrix} 2 & 2 \\ 2 & 2 \end{bmatrix}, \begin{bmatrix} 3 & 3 \\ 3 & 3 \end{bmatrix}, \dots$$


You want the initial conditions of your two-channel signal to be different for each channel and along each channel:

- 1 Set the **Delay (samples)** parameter to 2.
- 2 Select the **Specify different initial conditions for each channel** and the **Specify different initial conditions within a channel** check boxes.
- 3 Set the **Initial conditions** parameter to `{[11 15] [12 16]; [13 17] [14 18]}`. The dimensions of the cell array match the dimensions of the input. Also, each element of the cell array represents the initial conditions within one channel.

The output of the delay block is

$$\begin{bmatrix} 11 & 12 \\ 13 & 14 \end{bmatrix}, \begin{bmatrix} 15 & 16 \\ 17 & 18 \end{bmatrix}, \begin{bmatrix} 1 & 1 \\ 1 & 1 \end{bmatrix}, \begin{bmatrix} 2 & 2 \\ 2 & 2 \end{bmatrix}, \dots$$

Each element of the cell array represents the initial conditions within a channel. The first element, a vector, represents the initial conditions within channel 1. The second element, a vector, represents the initial conditions within channel 2, and so on. Different initial conditions are used for each channel and within the channels.



## Dialog Box

### Input processing

Specify how the block should process the input. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The option Inherit from input (this choice will be removed - see release notes) will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Delay units

Select whether you want to delay your input by a specified number of **Samples** or **Frames**. This parameter appears only when you set the **Input processing** parameter to **Columns as channels** (frame based).

## Delay (samples) or Delay (frames)

See “Sample-Based Processing” on page 2-388 and “Frame-Based Processing” on page 2-388 for a description of what format to use for each configuration of the block dialog.

## Specify different initial conditions for each channel

Select this check box when you want the initial conditions to vary across the channels. When you do not select this check box, the initial conditions are the same across the channels.

## Specify different initial conditions within a channel

Select this check box when you want the initial conditions to vary within the channels. When you do not select this check box, the initial conditions are the same within the channels.

## Initial conditions

Enter a scalar, vector, matrix, or cell array of initial condition values, depending on your choice for the **Specify different initial conditions for each channel** and **Specify different initial conditions within a channel** check boxes. See “Sample-Based Processing” on page 2-388 and “Frame-Based Processing” on page 2-388 for a description of what format to use for each configuration of the block dialog.

## Reset port

Determines the reset event that causes the block to reset the delay. For more information, see “Resetting the Delay” on page 2-389.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point
- Fixed point (signed and unsigned)
- Boolean
- 8-, 16-, and 32-bit signed integers
- 8-, 16-, and 32-bit unsigned integers

## See Also

Unit Delay	Simulink
Variable Fractional Delay	DSP System Toolbox
Variable Integer Delay	DSP System Toolbox

# Delay Line

**Purpose** Rebuffer sequence of inputs

**Library** Signal Management / Buffers  
dspbuff3

## Description




The Delay Line block rebuffers a sequence of  $M_i$ -by- $N$  matrix inputs into a sequence of  $M_o$ -by- $N$  matrix outputs, where  $M_o$  is the output frame size you specify in the **Delay line size** parameter. Depending on whether  $M_o$  is greater than, less than, or equal to the input frame size,  $M_i$ , the output frames can be underlapped or overlapped. The block always performs frame-based processing and rebuffers each of the  $N$  input channels independently.

When  $M_o > M_i$ , the output frame overlap is the difference between the output and input frame size,  $M_o - M_i$ . When  $M_o < M_i$ , the output is underlapped; the Delay Line block discards the first  $M_i - M_o$  samples of each input frame so that only the last  $M_o$  samples are buffered into the corresponding output frame. When  $M_o = M_i$ , the output data is identical to the input data, but is delayed by the latency of the block. Due to the block's latency, the outputs are always delayed by one frame, the entries of which you specify in the **Initial conditions** parameter (see "Initial Conditions" on page 2-405).

The output frame period is equal to the input frame period ( $T_{fo} = T_{fi}$ ). The output sample period,  $T_{so}$ , is therefore equal to  $T_{fi}/M_o$ , or equivalently,  $T_{si}(M_i/M_o)$ .

In the most typical use, each output differs from the preceding output by only one sample, as illustrated below for scalar input.




Note that the first output of the block in the example above is all zeros; this is because the **Initial Conditions** parameter is set to zero.

## Initial Conditions

The Delay Line block's buffer is initialized to the value specified by the **Initial conditions** parameter. The block outputs this buffer at the first simulation step ( $t=0$ ). When the block's output is a vector, the **Initial conditions** can be a vector of the same size, or a scalar value to be repeated across all elements of the initial output. When the block's output is a matrix, the **Initial conditions** can be a matrix of the same size, a vector (of length equal to the number of matrix rows) to be repeated across all columns of the initial output, or a scalar to be repeated across all elements of the initial output.


## Examples

In the following ex\_delayline\_ref2 model, the block rebuffers a two-channel input with a **Delay line size** of 3.



The first output frame in this example is due to the latency of the Delay Line block; it is all zeros because the **Initial conditions** parameter is set to zero. Because the input frame size of 4 is larger than the output frame size of 3, only the last three samples in each input frame are propagated to the corresponding output frame. The frame periods of the input and output are the same, and the output sample period is  $T_{si} \cdot (M_i/M_o)$ , or  $4/3$  the input sample period.

# Delay Line



## Dialog Box

### Delay line size

Specify the number of rows in output matrix,  $M_o$ .

### Initial conditions

Specify the value of the block's initial output. When the block outputs a vector, the **Initial conditions** can be a vector of the same size, or a scalar value to be repeated across all elements of the initial output. When the block outputs a matrix, the **Initial conditions** can be a matrix of the same size, a vector (of length equal to the number of matrix rows) to be repeated across all columns of the initial output, or a scalar to be repeated across all elements of the initial output.

## **Allow direct feedthrough**

When you select this check box, the input data is not delayed by an extra frame before it is available at the output buffer. Instead, the input data is available immediately at the output port of the block.

## **Show En\_Out port for selectively enabling output**

When you select this check box, the En\_Out port appears on the block icon. This block uses a circular buffer internally even though the output is linear. This means that for valid output, data from the circular buffer has to be linearized. The En\_Out port determines whether or not a valid output needs to be computed based on the value of its Boolean input. If the input value to the En\_Out port is 1, the block output is linearized, and thus is valid. Otherwise, the output is not linearized, and is invalid. This allows the block to be more efficient when the tapped Delay Line's output is not required at each sample time.

Note that when the input value to the En\_Out port is 0, the block can give different results depending on the state of the model. The results can appear to match valid results or can be invalid, and they cannot be predicted. You should ignore the block output in all cases when the input to the En\_Out port is 0.

## **Hold previous value when the output is disabled**

This parameter only appears and applies when the **Show En\_Out port for selectively enabling output** parameter is selected. Use this parameter to specify the block output at those time steps when the internal state buffer is not being linearized to output valid data.

When you do not select this check box, the block memory is free to be used by other parts of the model, and the signal on the output port is invalid. When you select this check box, the most recent valid value is held on the output port, and slightly more memory is used by the block.

# Delay Line

---

## Treat $M \times 1$ and unoriented sample-based signals as

Specify how the block treats sample-based  $M$ -by-1 column vectors and unoriented sample-based vectors of length  $M$ . You can select one of the following options:

- **One channel** — When you select this option, the block treats  $M$ -by-1 and unoriented sample-based inputs as a column vector (one channel).
- **$M$  channels** (this choice will be removed see release notes) — When you select this option, the block treats  $M$ -by-1 and unoriented sample-based inputs as a 1-by- $M$  row vector. Because the block always does frame-based processing, the block interprets the 1-by- $M$  row vector as  $M$  individual channels.

---

**Note** This parameter will be removed in a future release. At that time, the Delay Line block will always perform frame-based processing.

---

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li></ul>

Port	Supported Data Types
------	----------------------

## See Also


Buffer	<ul style="list-style-type: none"><li>• Boolean DSP System Toolbox</li></ul>
Triggered Delay Line	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit signed integers DSP System Toolbox</li></ul>
(Obsolete)	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

# Detrend

**Purpose** Remove linear trend from vectors

**Library** Statistics  
dspstat3

## Description




The Detrend block removes a linear trend from the length- $M$  input vector,  $u$ , by subtracting the straight line that best fits the data in the least squares sense.

The least squares line,  $\hat{u} = ax + b$ , is the line with parameters  $a$  and  $b$  that minimizes the quantity

$$\sum_{i=1}^M (u_i - \hat{u}_i)^2$$

for  $M$  evenly-spaced values of  $x$ , where  $u_i$  is the  $i$ th element in the input vector. The output,  $y = u - \hat{u}$ , is always an  $M$ -by-1 column vector.



## Dialog Box

## Supported Data Types

- Double-precision floating point
- Single-precision floating point

## See Also

Cumulative Sum	DSP System Toolbox
Difference	DSP System Toolbox
Least Squares Polynomial Fit	DSP System Toolbox
Unwrap	DSP System Toolbox
detrend	MATLAB

# Difference

---

**Purpose** Compute element-to-element difference along specified dimension of input

**Library** Math Functions / Math Operations  
dspmathops

**Description** The Difference block computes the difference between adjacent elements in rows, columns, or a specified dimension of the input array  $u$ . You can configure the block to compute the difference only within the current input, or across consecutive inputs (running difference).



## Basic Operation

When you set the **Running difference** parameter to No, the block computes the difference between adjacent elements in the specified dimension of the current input. In this mode, the block can compute the difference along the columns, rows, or a specified dimension of the input.

### Columnwise Differencing

When you set the **Difference along** parameter to Columns, the block computes differences between adjacent elements in each column of the input.

```
y = diff(u) % Equivalent MATLAB code
```

For  $M$ -by- $N$  inputs, the output is an  $(M-1)$ -by- $N$  matrix whose  $j$ th column has the following elements:

$$y_{i,j} = u_{i+1,j} - u_{i,j} \quad 1 \leq i \leq (M-1)$$

### Rowwise Differencing

When you set the **Difference along** parameter to Rows, the block computes differences between adjacent elements in each row of the input.

```
y = diff(u,[],2) % Equivalent MATLAB code
```

The output is an  $M$ -by- $(N-1)$  matrix whose  $i$ th row has the following elements:

$$y_{i,j} = u_{i,j+1} - u_{i,j} \quad 1 \leq j \leq (N-1)$$

## Differencing Along Arbitrary Dimensions

When you set the **Difference along** parameter to **Specified dimension**, the behavior of the block is an extension of the rowwise differencing described earlier. The block computes differences between adjacent elements along the dimension you specify in the **Dimension** parameter.

`y = diff(u,[],d) % Equivalent MATLAB code where d is the dimension`

The output is an array whose length in the specified dimension is one less than that of the input, and whose lengths in other dimensions are unchanged. For example, consider an  $M$ -by- $N$ -by- $P$ -by- $R$  input array with elements  $u(i,j,k,l)$  and assume that **Dimension** is 3. The output of the block is an  $M$ -by- $N$ -by- $(P-1)$ -by- $R$  array with the following elements:

$$y_{i,j,k,l} = u_{i,j,k+1,l} - u_{i,j,k,l} \quad 1 \leq k \leq (P-1)$$

## Running Operation

When you set the **Running difference** parameter to **Yes**, the block computes the running difference along the columns of the input.

For an  $M$ -by- $N$  input matrix, the output is an  $M$ -by- $N$  matrix whose  $j$ th column has the following elements:

$$y_{i,j} = u_{i+1,j} - u_{i,j} \quad 2 \leq i \leq (M-1)$$


In running mode, the first element of the output for each column is the first input element minus the last input element of the previous frame. For the first frame, the block subtracts zero from the first input element.

$$y_{1,j}(t) = u_{1,j}(t) - u_{M,j}(t - T_f)$$

# Difference

## Fixed-Point Data Types

The following diagram shows the data types used within the Difference block for fixed-point signals.




You can set the accumulator and output data types in the block dialog as discussed in “Dialog Box” on page 2-415 .


## Examples

For an example showing the modes of the Difference block, open ex\_difference.


The following figure shows the output of the block when it is differencing along columns in nonrunning mode.



The following figure shows the output of the block when it is differencing along rows in nonrunning mode.




The following figure shows the second frame of block output when the block is computing the running difference.



## Dialog Box

The **Main** pane of the Difference block appears as follows.

# Difference



## Running difference

Specify whether or not the block computes a running difference. When you select **No**, the block computes the difference between adjacent elements in the current input. When you select **Yes**, the block computes the running difference across consecutive inputs. In running mode, the block always computes the difference along the columns of the input. See “Running Operation” on page 2-413 for more information.

---

**Note** The Inherit from input (this choice will be removed - see release notes) option will be removed in a future release. See “Difference Block Changes” in the *DSP System Toolbox Release Notes* for more information.

---

## **Difference along**

Specify whether the block computes the difference along the columns, rows, or specified dimension of the input.


## **Dimension**

Specify the one-based dimension along which to compute element-to-element differences.

This parameter is only visible when you select **Specified dimension** for the **Difference along** parameter.

The **Data Types** pane of the Difference block appears as follows.

# Difference



---

**Note** Floating-point inheritance takes precedence over the data type settings defined on this pane. When inputs are floating point, the block ignores these settings, and all internal data types are floating point.

---

## Rounding mode

Select the rounding mode for fixed-point operations.

### Overflow mode

Select the overflow mode for fixed-point operations.

### Accumulator data type

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-414 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`


Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

### Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-414 for illustrations depicting the use of the output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as accumulator`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

# Difference

---

## Minimum

Specify the minimum value that the block should output. The default value is [ ] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Maximum

Specify the maximum value that the block should output. The default value is [ ] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

## See Also

Cumulative Sum  
diff

DSP System Toolbox  
MATLAB

# Differentiator Filter

---

**Purpose** Design differentiator filter


**Library** Filtering / Filter Designs  
dspfdesign

**Description** This block brings the filter design capabilities of the `filterbuilder` function to the Simulink environment.



**Dialog Box** See “Differentiator Filter Design Dialog Box — Main Pane” on page 7-707 for more information about the parameters of this block. The **Data Types** and **Code Generation** panes are not available for blocks in the DSP System Toolbox Filter Designs library.

# Differentiator Filter



Function Block Parameters: Differentiator Filter

Differentiator Filter  
Design a differentiator.

[View Filter Response](#)

Filter specifications

Order mode:  Order:

Filter Type:

Frequency specifications

Frequency constraints:

Frequency units:  Input Fs:

Magnitude specifications

Magnitude constraints:

Algorithm

Design method:

► Design options

Filter Implementation

Structure:

Use basic elements to enable filter customization

Input processing:

Use symbolic names for coefficients

# Differentiator Filter

---

## View filter response

This button opens the Filter Visualization Tool (fvtool) from the Signal Processing Toolbox product. You can use the tool to display:

- Magnitude response, phase response, and group delay in the frequency domain.
- Impulse response and step response in the time domain.
- Pole-zero information.

The tool also helps you evaluate filter performance by providing information about filter order, stability, and phase linearity. For more information on FVTool, see the Signal Processing Toolbox documentation.

## Filter Specifications

### Order mode

Select either **Minimum** or **Specify** (the default). Selecting **Specify** enables the **Order** option so you can enter the filter order.

### Order

Enter the filter order. This option is enabled only if you set the **Order mode** to **Specify**. The default order is 31.

### Filter type

Select **Single-rate**, **Decimator**, **Interpolator**, or **Sample-rate converter**. Your choice determines the type of filter as well as the design methods and structures that are available to implement your filter. By default, the block specifies a single-rate filter.

- Selecting **Decimator** or **Interpolator** activates the **Decimation Factor** or the **Interpolation Factor** options respectively.
- Selecting **Sample-rate converter** activates both factors.

### Decimation Factor

Enter the decimation factor. This option is enabled only if the **Filter type** is set to **Decimator** or **Sample-rate converter**. The default value is 2.

## Interpolation Factor

Enter the interpolation factor. This option is enabled only if the **Filter type** is set to Interpolator or Sample-rate converter. The default value is 2.

## Frequency Specifications

The parameters in this group allow you to specify your filter response curve.

### Frequency constraints

This option is only available when you specify the order of the filter design. Supported options are Unconstrained and Passband edge and stopband edge.

### Frequency units

Use this parameter to specify whether your frequency settings are normalized or in absolute frequency. Select **Normalized (0 1)** to enter frequencies in normalized form. This behavior is the default. To enter frequencies in absolute values, select one of the frequency units from the drop-down list—Hz, kHz, MHz, or GHz. Selecting one of the unit options enables the **Input Fs** parameter.

### Input Fs

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter input. When you provide an input sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is available when you select one of the frequency options from the **Frequency units** list.

### Fpass

Enter the frequency at the end of the passband. Specify the value in either normalized frequency units or the absolute units you select in **Frequency units**.

### Fstop

Enter the frequency at the start of the stopband. Specify the value in either normalized frequency units or the absolute units you select in **Frequency units**.

# Differentiator Filter

---

## Magnitude Specifications

Parameters in this group specify the filter response in the passbands and stopbands. These parameters are only available for minimum-order designs.

### Magnitude constraints

This option is only available when you specify the order of your filter design. The available **Magnitude constraints** depend on the value of the **Frequency constraints** parameter. When you set the **Frequency constraints** parameter to Unconstrained, the **Magnitude constraints** parameter must also be Unconstrained. When you set the **Frequency constraints** parameter to Passband edge and stopband edge, the **Magnitude constraints** parameter can be Unconstrained, Passband ripple, or Stopband attenuation.

### Magnitude units

Specify the units for any parameter you provide in magnitude specifications. From the drop-down list, select one of the following options:

- Linear — Specify the magnitude in linear units.
- dB — Specify the magnitude in decibels (default).
- Squared — Specify the magnitude in squared units.

### A<sub>pass</sub>

Enter the filter ripple allowed in the passband in the units you choose for **Magnitude units**, either linear or decibels.

### A<sub>stop2</sub>

Enter the filter attenuation in the second stopband in the units you choose for **Magnitude units**, either linear or decibels.

## Algorithm

The parameters in this group allow you to specify the design method and structure of your filter.

## Design Method

Lists the design methods available for the frequency and magnitude specifications you entered. When you change the specifications for a filter, such as changing the impulse response, the methods available to design filters changes as well.

## Design Options

The options for each design are specific for each design method. This section does not present all of the available options for all designs and design methods. There are many more that you encounter as you select different design methods and filter specifications. The following options represent some of the most common ones available.

### Density factor

Density factor controls the density of the frequency grid over which the design method optimization evaluates your filter response function. The number of equally spaced points in the grid is the value you enter for **Density factor** times (filter order + 1).

Increasing the value creates a filter that more closely approximates an ideal equiripple filter but increases the time required to design the filter. The default value of 20 represents a reasonable trade between the accurate approximation to the ideal filter and the time to design the filter.

### Wpass

Passband weight. This option is only available for a specified-order design when **Frequency constraints** is equal to Passband edge and stopband edge and the **Design method** is Equiripple.

### Wstop

Stopband weight. This option is only available for a specified-order design when **Frequency constraints** is

# Differentiator Filter

---

equal to Passband edge and stopband edge and the **Design method** is Equiripple.

## Filter Implementation

### Structure

For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter. By default, FIR filters use direct-form structure.

### Use basic elements to enable filter customization

Select this check box to implement the filter as a subsystem of basic Simulink blocks. Clear the check box to implement the filter as a high-level subsystem. By default, this check box is cleared.

The high-level implementation provides better compatibility across various filter structures, especially filters that would contain algebraic loops when constructed using basic elements. On the other hand, using basic elements enables the following optimization parameters:

- **Optimize for zero gains** — Terminate chains that contain Gain blocks with a gain of zero.
- **Optimize for unit gains** — Remove Gain blocks that scale by a factor of one.
- **Optimize for delay chains** — Substitute delay chains made up of  $n$  unit delays with a single delay by  $n$ .
- **Optimize for negative gains** — Use subtraction in Sum blocks instead of negative gains in Gain blocks.

### Input processing

Specify how the block should process the input. The available options may vary depending on the settings of the **Filter Structure** and **Use basic elements for filter customization** parameters. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The **Inherited** (this choice will be removed see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

### Rate options

When the **Filter type** parameter specifies a multirate filter, select the rate processing rule for the block from following options:

- **Enforce single-rate processing** — When you select this option, the block maintains the sample rate of the input.
- **Allow multirate processing** — When you select this option, the block adjusts the rate at the output to accommodate an increased or reduced number of samples. To select this option, you must set the **Input processing** parameter to **Elements as channels (sample based)**.

### Use symbolic names for coefficients

Select this check box to enable the specification of coefficients using MATLAB variables. The available coefficient names differ depending on the filter structure. Using symbolic names allows tuning of filter coefficients in generated code. By default, this check box is cleared.

# Differentiator Filter

---

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

## Purpose


Filter each channel of input over time using static or time-varying digital filter implementations

## Library

Filtering / Filter Implementations

dsparch4

## Description



You can use the Digital Filter block to efficiently implement a floating-point or fixed-point filter for which you know the coefficients, or that is already defined in a `dfilt` object. The block independently filters each channel of the input signal with a specified digital IIR or FIR filter. The block can implement *static filters* with fixed coefficients, as well as *time-varying filters* with coefficients that change over time. You can tune the coefficients of a static filter during simulation.

This block filters each channel of the input signal independently over time. You must set the **Input processing** parameter to specify how the block interprets the input signal. You can select one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as an independent channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as an individual channel.

The output dimensions always match those of the input signal. The outputs of this block numerically match the outputs of the Digital Filter Design block and of the `dfilt` object.

---

**Note** The Digital Filter block has direct feedthrough, so if you connect the output of this block back to its input you get an algebraic loop. For more information on direct feedthrough and algebraic loops, see “Algebraic Loops” in the Simulink documentation.

---

## Sections of This Reference Page

- “Coefficient Source” on page 2-432
- “Supported Filter Structures” on page 2-432
- “Specifying Initial Conditions” on page 2-436
- “State Logging” on page 2-440
- “Fixed-Point Data Types” on page 2-441
- “Dialog Box” on page 2-441
- “Filter Structure Diagrams” on page 2-459
- “Supported Data Types” on page 2-495
- “See Also” on page 2-495

## Coefficient Source

The Digital Filter block can operate in three different modes. Select the mode in the **Coefficient source** group box.

- **Dialog parameters** Enter information about the filter such as structure and coefficients in the block mask.
- **Input port(s)** Enter the filter structure in the block mask, and the filter coefficients come in through one or more block ports. This mode is useful for specifying time-varying filters.
- **Discrete-time filter object (DFILT)** Specify the filter using a `dfilt` object.

## Supported Filter Structures

When you select **Discrete-time filter object (DFILT)**, the following `dfilt` structures are supported:

- `dfilt.df1`
- `dfilt.df1t`
- `dfilt.df2`

- `dfilt.df2t`
- `dfilt.df1sos`
- `dfilt.df1tsos`
- `dfilt.df2sos`
- `dfilt.df2tsos`
- `dfilt.dffir`
- `dfilt.dffirt`
- `dfilt.dfsymfir`
- `dfilt.dfasymfir`
- `dfilt.latticear`
- `dfilt.latticemamin`

When you select **Dialog parameters** or **Input port(s)**, the list of filter structures offered in the **Filter structure** parameter depends on whether you set the **Transfer function type** to IIR (poles & zeros), IIR (all poles), or FIR (all zeros), as summarized in the following table.

---

**Note** Each structure listed in the table below supports both fixed-point and floating-point signals.

---

The table also shows the vector or matrix of filter coefficients you must provide for each filter structure. For more information on how to specify filter coefficients for various filter structures, see “Specify Static Filters” and “Specify Time-Varying Filters”.

# Digital Filter

## Filter Structures and Filter Coefficients

Transfer Function Type	Supported Filter Structures	Filter Coefficient Specification
IIR (poles & zeros)	Direct form I Direct form I transposed Direct form II Direct form II transposed	<ul style="list-style-type: none"> <li>Numerator coefficients vector [b0, b1, b2, ..., bn]</li> <li>Denominator coefficients vector [a0, a1, a2, ..., am]</li> </ul> <p>See Special Consideration for the Leading Denominator Coefficient.</p>
	Biquadratic direct form I (SOS) Biquadratic direct form I transposed (SOS) Biquadratic direct form II (SOS) Biquadratic direct form II transposed (SOS)	<ul style="list-style-type: none"> <li><math>M</math>-by-6 second-order section (SOS) matrix.</li> <li>Scale values</li> </ul> <p>See “Specify the SOS Matrix (Biquadratic Filter Coefficients)”.</p>
IIR (all poles)	Direct form Direct form transposed	Denominator coefficients vector [a0, a1, a2, ..., am]  See Special Consideration for the Leading Denominator Coefficient.
	Lattice AR	Reflection coefficients vector [k1, k2, ..., kn]

## Filter Structures and Filter Coefficients (Continued)

Transfer Function Type	Supported Filter Structures	Filter Coefficient Specification
FIR (all zeros)	Direct form Direct form symmetric Direct form antisymmetric Direct form transposed	Numerator coefficients vector [b0, b1, b2, ..., bn]
	Lattice MA	Reflection coefficients vector [k1, k2, ..., kn]

### Special Considerations for the Leading Denominator Coefficient

In some cases, the Digital Filter block requires the leading denominator coefficient ( $a_0$ ) to be 1. This requirement applies under the following conditions:

- The Digital Filter block is operating in a fixed-point mode. The block operates in a fixed-point mode when at least one of the following statements is true:
  - The input to the Digital Filter block has a fixed-point or integer data type.
  - The **Fixed-point instrumentation mode** parameter under **Analysis > Fixed Point Tool** has a setting of Minimums, maximums and overflows.
- The **Coefficient source** has a setting of Dialog or Input port(s).

---

**Note** If you are working in one of the fixed-point situations described in the previous bullet, and the **Coefficient source** is set to Input port (s), you must select the **First denominator coefficient = 1, remove a0 term in the structure** check box.

---

- The **Transfer function type** and **Filter structure** parameters are set to one of the combinations described in the following table.

Transfer function type	Filter structure
IIR (poles & zeros)	Direct form I
	Direct form I transposed
	Direct form II
	Direct form II transposed
IIR (all poles)	Direct form
	Direct form transposed

The Digital Filter block produces an error if you use it in one of the these configurations and your leading denominator coefficient ( $a_0$ ) does not equal 1. To resolve the error, set your leading denominator coefficient to 1 by scaling all numerator and denominator coefficients by a factor of  $a_0$ .

## Specifying Initial Conditions

In **Dialog parameters** and **Input port(s)** modes, the block initializes the internal filter states to zero by default, which is equivalent to assuming past inputs and outputs are zero. You can optionally use the **Initial conditions** parameter to specify nonzero initial conditions for the filter delays.

To determine the number of initial condition values you must specify, and how to specify them, see the following table on Valid Initial Conditions and Number of Delay Elements (Filter States) on page

2-439. The **Initial conditions** parameter can take one of four forms as described in the following table.

## Valid Initial Conditions

Initial Condition	Examples	Description
Scalar	5 Each delay element for each channel is set to 5.	The block initializes all delay elements in the filter to the scalar value.
Vector (for applying the same delay elements to each channel)	For a filter with two delay elements: $[d_1 \ d_2]$ The delay elements for all channels are $d_1$ and $d_2$ .	Each vector element specifies a unique initial condition for a corresponding delay element. The block applies the same vector of initial conditions to each channel of the input signal. The vector length must equal the number of delay elements in the filter (specified in the table Number of Delay Elements (Filter States) on page 2-439).
Vector or matrix (for applying different delay elements to each channel)	For a 3-channel input signal and a filter with two delay elements: $[d_1 \ d_2 \ D_1 \ D_2 \ d_1 \ d_2]$ or $\begin{bmatrix} d_1 & D_1 & d_1 \\ d_2 & D_2 & d_2 \end{bmatrix}$ <ul style="list-style-type: none"> <li>The delay elements for channel 1 are <math>d_1</math> and <math>d_2</math>.</li> <li>The delay elements for channel 2 are <math>D_1</math> and <math>D_2</math>.</li> <li>The delay elements for channel 3 are <math>d_1</math> and <math>d_2</math>.</li> </ul>	Each vector or matrix element specifies a unique initial condition for a corresponding delay element in a corresponding channel: <ul style="list-style-type: none"> <li>The vector length must be equal to the product of the number of input channels and the number of delay elements in the filter (specified in the table Number of Delay Elements (Filter States) on page 2-439).</li> <li>The matrix must have the same number of rows as the number of delay elements in the filter (specified in the table Number of Delay</li> </ul>

# Digital Filter

---

## Valid Initial Conditions (Continued)

Initial Condition	Examples	Description
		Elements (Filter States) on page 2-439), and must have one column for each channel of the input signal.
Empty matrix	[ ] Each delay element for each channel is set to 0.	The empty matrix, [ ], is equivalent to setting the <b>Initial conditions</b> parameter to the scalar value 0.

The number of delay elements (filter states) per input channel depends on the filter structure, as indicated in the following table.

## Number of Delay Elements (Filter States)

Filter Structure	Number of Delay Elements per Channel
Direct form Direct form transposed Direct form symmetric Direct form antisymmetric	<code>#_of_filter_coeffs-1</code>
Direct form I Direct form I transposed	<ul style="list-style-type: none"> <li>• <code>#_of_zeros-1</code></li> <li>• <code>#_of_poles-1</code></li> </ul>
Direct form II Direct form II transposed	<code>max(#_of_zeros, #_of_poles)-1</code>
Biquadratic direct form I (SOS) Biquadratic direct form I transposed (SOS) Biquadratic direct form II (SOS) Biquadratic direct form II transposed (SOS)	<code>2 * #_of_filter_sections</code>
Lattice AR Lattice MA	<code>#_of_reflection_coeffs</code>

## State Logging

Simulink enables you to log the states in your model to the MATLAB workspace. The following table indicates which filter structures of the Digital Filter block support the Simulink state logging feature. See “States” in the Simulink User’s Guide documentation for more information.

<b>Transfer Function Type</b>	<b>Filter Structure</b>	<b>State Logging Supported</b>
<b>IIR (poles &amp; zeros)</b>	Direct form I	No
	Direct form I transposed	Yes
	Direct form II	No
	Direct form II transposed	Yes
	Biquadratic direct form I (SOS)	Yes
	Biquadratic direct form I transposed (SOS)	Yes
	Biquadratic direct form II (SOS)	Yes
	Biquadratic direct form II transposed (SOS)	Yes
<b>IIR (all poles)</b>	Direct form	No
	Direct form transposed	Yes
	Lattice AR	Yes
<b>FIR (all zeros)</b>	Direct form	No
	Direct form symmetric	No
	Direct form antisymmetric	No
	Direct form transposed	Yes
	Lattice MA	Yes

## Dialog Box

### Fixed-Point Data Types

All structures supported by the Digital Filter block support fixed-point data types. You can specify intermediate fixed-point data types for quantities such as the coefficients, accumulator, and product output for each filter structure. See “Filter Structure Diagrams” on page 2-459 for diagrams depicting the use of these intermediate fixed-point data types in each filter structure.

### Coefficient Source

The Digital Filter block can operate in three different modes. Select the mode in the **Coefficient source** group box.

- **Dialog parameters** Enter information about the filter such as structure and coefficients in the block mask.
- **Input port(s)** Enter the filter structure in the block mask, and the filter coefficients come in through one or more block ports. This mode is useful for specifying time-varying filters.
- **Discrete-time filter object (DFILT)** Specify the filter using a `dfilt` object.

Different items appear on the Digital Filter block dialog depending on whether you select **Dialog parameters**, **Input port(s)**, or **Discrete-time filter object (DFILT)** in the **Coefficient source** group box. See the following sections for details:

- “Specify Filter Characteristics in Dialog and/or Through Input Ports” on page 2-441
- “Specify Discrete-Time Filter Object” on page 2-454


### Specify Filter Characteristics in Dialog and/or Through Input Ports

The **Main** pane of the Digital Filter block dialog appears as follows when **Dialog parameters** is specified in the **Coefficient source** group

# Digital Filter

---

box. The parameters below can appear when **Dialog parameters** or **Input port(s)** is selected, as noted.



## **Transfer function type**

Select the type of transfer function of the filter; IIR (poles & zeros), IIR (all poles), or FIR (all zeros). See “Supported Filter Structures” on page 2-432 for more information.

## **Filter structure**

Select the filter structure. The selection of available structures varies depending the setting of the **Transfer function type** parameter. See “Supported Filter Structures” on page 2-432 for more information.

## **Numerator coefficients**

Specify the vector of numerator coefficients of the filter’s transfer function.

This parameter is only visible when **Dialog parameters** is selected *and* when the selected filter structure lends itself to specification with numerator coefficients. Tunable.

## **Denominator coefficients**

Specify the vector of denominator coefficients of the filter’s transfer function.

In some cases, the leading denominator coefficient ( $a_0$ ) must be 1. See Special Consideration for the Leading Denominator Coefficient for more information.

This parameter is only visible when **Dialog parameters** is selected *and* when the selected filter structure lends itself to specification with denominator coefficients. Tunable.

## **Reflection coefficients**

Specify the vector of reflection coefficients of the filter’s transfer function.

This parameter is only visible when **Dialog parameters** is selected *and* when the selected filter structure lends itself to specification with reflection coefficients. Tunable.

## SOS matrix (Mx6)

Specify an  $M$ -by-6 *SOS matrix* containing coefficients of a second-order section (SOS) filter, where  $M$  is the number of sections. You can use the `ss2sos` and `tf2sos` functions from Signal Processing Toolbox software to check whether your SOS matrix is valid. For more on the requirements of the SOS matrix, see “Specify the SOS Matrix (Biquadratic Filter Coefficients)”.

This parameter is only visible when **Dialog parameters** is selected *and* when the selected filter structure is biquadratic. Tunable.

## Scale values

Specify the scale values to be applied before and after each section of a biquadratic filter.

- If you specify a scalar, that value is applied before the first filter section. The rest of the scale values are set to 1.
- You can also specify a vector with  $M + 1$  elements, assigning a different value to each scale. See “Filter Structure Diagrams” on page 2-459 for diagrams depicting the use of scale values in biquadratic filter structures.

This parameter is only visible when **Dialog parameters** is selected *and* when the selected filter structure is biquadratic. Tunable.

## First denominator coefficient = 1, remove a0 term in the structure

Select this parameter to reduce the number of computations the block must make to produce the output by omitting the  $1 / a_0$  term in the filter structure. The block output is invalid if you select this parameter when the first denominator filter coefficient is *not* always 1 for your time-varying filter.

This parameter is only enabled when the **Input port(s)** is selected *and* when the selected filter structure lends itself to this

specification. See “Removing the  $a_0$  Term in the Filter Structure” for a diagram and details.

## **Coefficient update rate**

Specify how often the block updates time-varying filters; once per sample or once per frame.

This parameter appears only when the following conditions are met:

- You specify **Input port(s)** in the Coefficient source group box.
- You set the **Input processing** parameter to **Columns as channels (frame based)**.
- The filter structure you select lends itself to this specification. See “Specify Time-Varying Filters” for more information.

## **Initial conditions**

Specify the initial conditions of the filter states. To learn how to specify initial conditions, see “Specifying Initial Conditions” on page 2-436.

### **Initial conditions on zeros side**


(Not shown in dialog above.) Specify the initial conditions for the filter states on the side of the filter structure with the zeros ( $b_0, b_1, b_2, \dots$ ); see the diagram below.

This parameter is enabled only when the filter has both poles and zeros, *and* when you select a structure such as direct form I, which has separate filter states corresponding to the poles ( $a_k$ ) and zeros ( $b_k$ ). To learn how to specify initial conditions, see “Specifying Initial Conditions” on page 2-436.

### **Initial conditions on poles side**

(Not shown in dialog above.) Specify the initial conditions for the filter states on the side of the filter structure with the poles ( $a_0, a_1, a_2, \dots$ ); see the diagram below.

This parameter is enabled only when the filter has both poles and zeros, *and* when you select a structure such as direct form I, which has separate filter states corresponding to the poles ( $a_k$ ) and zeros ( $b_k$ ). To learn how to specify initial conditions, see “Specifying Initial Conditions” on page 2-436.



## Input processing

Specify how the block should process the input. You can set this parameter to one of the following options:

- Columns as channels (frame based) — When you select this option, the block treats each column of the input as a separate channel.
- Elements as channels (sample based) — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The Inherited (this choice will be removed - see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## View filter response


This button opens the Filter Visualization Tool (fvtool) from the Signal Processing Toolbox product and displays the filter response of the filter defined by the block. For more information on FVTool, see the Signal Processing Toolbox documentation.

---

**Note** If you specify a filter in the **Filter** parameter, you must click the **Apply** button to apply the filter before using the **View filter response** button.

---

The **Data Types** pane of the Digital Filter block dialog appears as follows when **Dialog parameters** is specified in the **Coefficient source** group box. The parameters below can appear when **Dialog parameters** or **Input port(s)** is selected, depending on the filter structure and whether the coefficients are being entered via ports or on the block mask.



## **Rounding mode**

Select the rounding mode for fixed-point operations. The filter coefficients do not obey this parameter; they always round to Nearest.

## **Overflow mode**

Select the overflow mode for fixed-point operations. The filter coefficients do not obey this parameter; they are always saturated.

## **Section I/O**

Choose how you specify the word length and the fraction length of the fixed-point data type going into and coming out of each section of a biquadratic filter. See “Filter Structure Diagrams” on page 2-459 for illustrations depicting the use of the section I/O data type in this block.

This parameter is only visible when the selected filter structure is biquadratic:

- When you select `Same as input`, these characteristics match those of the input to the block.
- When you select `Binary point scaling`, you can enter the word and fraction lengths of the section input and output, in bits.
- When you select `Slope and bias scaling`, you can enter the word lengths, in bits, and the slopes of the section input and output. This block requires power-of-two slope and a bias of zero.

## **Tap sum**

Choose how you specify the word length and the fraction length of the tap sum data type of a direct form symmetric or direct form antisymmetric filter. See “Filter Structure Diagrams” on page 2-459 for illustrations depicting the use of the tap sum data type in this block.

This parameter is only visible when the selected filter structure is either `Direct form symmetric` or `Direct form antisymmetric`:

- When you select **Same as input**, these characteristics match those of the input to the block.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the tap sum accumulator, in bits.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the tap sum accumulator. This block requires power-of-two slope and a bias of zero.

## **Multiplicand**

Choose how you specify the word length and the fraction length of the multiplicand data type of a direct form I transposed or biquadratic direct form I transposed filter. See “Filter Structure Diagrams” on page 2-459 for illustrations depicting the use of the multiplicand data type in this block.

This parameter is only visible when the selected filter structure is either **Direct form I transposed** or **Biquad direct form I transposed (SOS)**:

- When you select **Same as output**, these characteristics match those of the output to the block.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the multiplicand data type, in bits.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the multiplicand data type. This block requires power-of-two slope and a bias of zero.

## **Coefficients**

Choose how you specify the word length and the fraction length of the filter coefficients (numerator and/or denominator). See “Filter Structure Diagrams” on page 2-459 for illustrations depicting the use of the coefficient data types in this block:

- When you select **Same word length as input**, the word length of the filter coefficients match that of the input to the

block. In this mode, the fraction length of the coefficients is automatically set to the binary-point only scaling that provides you with the best precision possible given the value and word length of the coefficients.

- When you select **Specify word length**, you can enter the word length of the coefficients, in bits. In this mode, the fraction length of the coefficients is automatically set to the binary-point only scaling that provides you with the best precision possible given the value and word length of the coefficients.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the coefficients, in bits. If applicable, you can enter separate fraction lengths for the numerator and denominator coefficients.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the coefficients. If applicable, you can enter separate slopes for the numerator and denominator coefficients. This block requires power-of-two slope and a bias of zero.
- The filter coefficients do not obey the **Rounding mode** and the **Overflow mode** parameters; they are always saturated and rounded to Nearest.

## Product output

Use this parameter to specify how you would like to designate the product output word and fraction lengths. See “Filter Structure Diagrams” on page 2-459 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block:

- When you select **Same as input**, these characteristics match those of the input to the block.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the product output, in bits.

- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the product output. This block requires power-of-two slope and a bias of zero.

## Accumulator

Use this parameter to specify how you would like to designate the accumulator word and fraction lengths. See “Filter Structure Diagrams” on page 2-459 and “Multiplication Data Types” for illustrations depicting the use of the accumulator data type in this block:

- When you select **Same as input**, these characteristics match those of the input to the block.
- When you select **Same as product output**, these characteristics match those of the product output.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the accumulator, in bits.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the accumulator. This block requires power-of-two slope and a bias of zero.

## State

Use this parameter to specify how you would like to designate the state word and fraction lengths. See “Filter Structure Diagrams” on page 2-459 for illustrations depicting the use of the state data type in this block.

This parameter is not visible for direct form and direct form I filter structures.

- When you select **Same as input**, these characteristics match those of the input to the block.
- When you select **Same as accumulator**, these characteristics match those of the accumulator.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the accumulator, in bits.

- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the accumulator. This block requires power-of-two slope and a bias of zero.

## Output

Choose how you specify the output word length and fraction length:


- When you select **Same as input**, these characteristics match those of the input to the block.
- When you select **Same as accumulator**, these characteristics match those of the accumulator.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the output, in bits.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the output. This block requires power-of-two slope and a bias of zero.

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## Specify Discrete-Time Filter Object

The **Main** pane of the Digital Filter block dialog appears as follows when **Discrete-time filter object (DFILT)** is specified in the **Coefficient source** group box.



## Filter

Specify the discrete-time filter object (`dfilt`) that you would like the block to implement. You can do this in one of three ways:

- You can fully specify the `dfilt` object in the block mask, as shown in the default value.
- You can enter the variable name of a `dfilt` object that is defined in any workspace.
- You can enter a variable name for a `dfilt` object that is not yet defined.

## Input processing

Specify how the block should process the input. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The **Inherited** (this choice will be removed - see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## View filter response

This button opens the Filter Visualization Tool (`fvtool`) from the Signal Processing Toolbox product and displays the filter response of the `dfilt` object specified in the **Filter** parameter. For more information on FVTool, see the Signal Processing Toolbox documentation.


---

**Note** If you specify a filter in the **Filter** parameter, you must click the **Apply** button to apply the filter before using the **View filter response** button.

---

The **Data Types** pane of the Digital Filter block dialog appears as follows when **Discrete-time filter object (DFILT)** is specified in the **Coefficient source** group box.

# Digital Filter



The fixed-point settings of the filter object specified on the **Main** pane are displayed on the **Data Types** pane. You cannot change these settings directly on the block mask. To change the fixed-point settings you must edit the filter object directly.

For more information on discrete-time filter objects, see the `dfilt` reference page.


## Filter Structure Diagrams

The diagrams in the following sections show the filter structures supported by the Digital Filter block. They also show the data types used in the filter structures for fixed-point signals. You can set the coefficient, output, accumulator, product output, and state data types shown in these diagrams in the block dialog. This is discussed in “Dialog Box” on page 2-441.

- “IIR direct form I” on page 2-460
- “IIR direct form I transposed” on page 2-462
- “IIR direct form II” on page 2-465
- “IIR direct form II transposed” on page 2-467
- “IIR biquadratic direct form I” on page 2-470
- “IIR biquadratic direct form I transposed” on page 2-473
- “IIR biquadratic direct form II” on page 2-476
- “IIR biquadratic direct form II transposed” on page 2-478
- “IIR (all poles) direct form” on page 2-481
- “IIR (all poles) direct form transposed” on page 2-483
- “IIR (all poles) direct form lattice AR” on page 2-485
- “FIR (all zeros) direct form” on page 2-486
- “FIR (all zeros) direct form symmetric” on page 2-488
- “FIR (all zeros) direct form antisymmetric” on page 2-490
- “FIR (all zeros) direct form transposed” on page 2-492
- “FIR (all zeros) lattice MA” on page 2-494

# Digital Filter


## IIR direct form I



The following constraints are applicable when processing a fixed-point signal with this filter structure:


- Inputs can be real or complex.
- Numerator and denominator coefficients can be real or complex.
- Numerator and denominator coefficients must be the same complexity as each other.
  - When the numerator and denominator coefficients are specified via input ports and have different complexities from each other, you get an error.

- When the numerator and denominator coefficients are specified in the dialog and have different complexities from each other, the block does not error, but instead processes the filter as if two sets of complex coefficients are provided. The coefficient set that is real-valued is treated as if it is a complex vector with zero-valued imaginary parts.
- Numerator and denominator coefficients must have the same word length. They can have different fraction lengths.
- The State data type cannot be specified on the block mask for this structure, because the input and output states have the same data types as the input and output buffers.



# Digital Filter

## IIR direct form I transposed




The following constraints are applicable when processing a fixed-point signal with this filter structure:


- Inputs can be real or complex.
- Numerator and denominator coefficients can be real or complex.
- Numerator and denominator coefficients must be the same complexity as each other.

- When the numerator and denominator coefficients are specified via input ports and have different complexities from each other, you get an error.
- When the numerator and denominator coefficients are specified in the dialog and have different complexities from each other, the block does not error, but instead processes the filter as if two sets of complex coefficients are provided. The coefficient set that is real-valued is treated as if it is a complex vector with zero-valued imaginary parts.
- States are complex when either the input or the coefficients are complex.
- Numerator and denominator coefficients must have the same word length. They can have different fraction lengths.

# Digital Filter



## IIR direct form II




The following constraints are applicable when processing a fixed-point signal with this filter structure:


- Inputs can be real or complex.
- Numerator and denominator coefficients can be real or complex.
- Numerator and denominator coefficients must be the same complexity as each other.
  - When the numerator and denominator coefficients are specified via input ports and have different complexities from each other, you get an error.

# Digital Filter

- When the numerator and denominator coefficients are specified in the dialog and have different complexities from each other, the block does not error, but instead processes the filter as if two sets of complex coefficients are provided. The coefficient set that is real-valued is treated as if it is a complex vector with zero-valued imaginary parts.
- States are complex when either the inputs or the coefficients are complex.
- Numerator and denominator coefficients must have the same word length. They can have different fraction lengths.



## IIR direct form II transposed



The following constraints are applicable when processing a fixed-point signal with this filter structure:

- Inputs can be real or complex.
- Numerator and denominator coefficients can be real or complex.
- Numerator and denominator coefficients must be the same complexity as each other.
  - When the numerator and denominator coefficients are specified via input ports and have different complexities from each other, you get an error.


# Digital Filter

---

- When the numerator and denominator coefficients are specified in the dialog and have different complexities from each other, the block does not error, but instead processes the filter as if two sets of complex coefficients are provided. The coefficient set that is real-valued is treated as if it is a complex vector with zero-valued imaginary parts.
- States are complex when either the inputs or the coefficients are complex.
- Numerator and denominator coefficients must have the same word length. They can have different fraction lengths.



## IIR biquadratic direct form I




The following constraints are applicable when processing a fixed-point signal with this filter structure:

- Inputs and coefficients can be real or complex.
- Numerator and denominator coefficients can be real or complex.


- Specify the coefficients by a  $M$ -by-6 matrix in the block mask. You cannot specify coefficients by input ports for this filter structure.
- When the  $a_0$  element of any row is not equal to one, that row is normalized by  $a_0$  prior to filtering.
- States are complex when either the inputs or the coefficients are complex.
- You cannot specify the state data type on the block mask for this structure, because the input and output states have the same data types as the input.
- Scale values must have the same complexity as the coefficient SOS matrix.
- The scale value parameter must be a scalar or a vector of length  $M+1$ , where  $M$  is the number of sections.
- The **Section I/O** parameter determines the data type for the section input and output data types. The section input and stage output data type must have the same word length but can have different fraction lengths.

The following diagram shows the data types for one section of the filter.


# Digital Filter



The following diagram shows the data types between filter sections.



## IIR biquadratic direct form I transposed



The following constraints are applicable when processing a fixed-point signal with this filter structure:

- Inputs and coefficients can be real or complex.
- Numerator and denominator coefficients can be real or complex.

# Digital Filter


---

- Specify the coefficients by a  $M$ -by-6 matrix in the block mask. You cannot specify coefficients by input ports for this filter structure.
- When the  $a_0$  element of any row is not equal to one, that row is normalized by  $a_0$  prior to filtering.
- States are complex when either the inputs or the coefficients are complex.
- Scale values must have the same complexity as the coefficient SOS matrix.
- The scale value parameter must be a scalar or a vector of length  $M+1$ , where  $M$  is the number of sections.
- The **Section I/O** parameter determines the data type for the section input and output data types. The section input and section output data type must have the same word length but can have different fraction lengths.





# Digital Filter

The following diagram shows the data types between filter sections.



## IIR biquadratic direct form II




The following constraints are applicable when processing a fixed-point signal with this filter structure:

- Inputs and coefficients can be real or complex.
- Numerator and denominator coefficients can be real or complex.


- Specify the coefficients by a  $M$ -by-6 matrix in the block mask. You cannot specify coefficients by input ports for this filter structure.
- When the  $a_0$  element of any row is not equal to one, that row is normalized by  $a_0$  prior to filtering.
- States are complex when either the inputs or the coefficients are complex.
- Scale values must have the same complexity as the coefficient SOS matrix.
- The scale value parameter must be a scalar or a vector of length  $M+1$ , where  $M$  is the number of sections.
- The **Section I/O** parameter determines the data type for the section input and output data types. The section input and section output data type must have the same word length but can have different fraction lengths.

The following diagram shows the data types for one section of the filter.





The following diagram shows the data types between filter sections.

# Digital Filter



## IIR biquadratic direct form II transposed




The following constraints are applicable when processing a fixed-point signal with this filter structure:


- Inputs and coefficients can be real or complex.
- Numerator and denominator coefficients can be real or complex.
- Specify the coefficients by a  $M$ -by-6 matrix in the block mask. You cannot specify coefficients by input ports for this filter structure.
- When the  $a_0$  element of any row is not equal to one, that row is normalized by  $a_0$  prior to filtering.
- States are complex when either the inputs or the coefficients are complex.
- Scale values must have the same complexity as the coefficient SOS matrix.
- The scale value parameter must be a scalar or a vector of length  $M+1$ , where  $M$  is the number of sections.
- The **Section I/O** parameter determines the data type for the section input and output data types. The section input and section output data type must have the same word length but can have different fraction lengths.

The following diagram shows the data types for one section of the filter.


# Digital Filter



The following diagram shows the data types between filter sections.




## IIR (all poles) direct form




The following constraints are applicable when processing a fixed-point signal with this filter structure:

- Inputs and coefficients can be real or complex.
- Denominator coefficients can be real or complex.
- You cannot specify the state data type on the block mask for this structure, because the input and output states have the same data types as the input.

# Digital Filter




## IIR (all poles) direct form transposed



The following constraints are applicable when processing a fixed-point signal with this filter structure:

- Inputs and coefficients can be real or complex.
- Denominator coefficients can be real or complex.


# Digital Filter






# Digital Filter

## FIR (all zeros) direct form




The following constraints are applicable when processing a fixed-point signal with this filter structure:

- Inputs can be real or complex.
- Numerator coefficients can be real or complex.
- You cannot specify the state data type on the block mask for this structure, because the input and output states have the same data types as the input.



# Digital Filter

## FIR (all zeros) direct form symmetric




The following constraints are applicable when processing a fixed-point signal with this filter structure:

- Inputs can be real or complex.
- Numerator coefficients can be real or complex.
- You cannot specify the state data type on the block mask for this structure, because the input and output states have the same data types as the input.
- It is assumed that the filter coefficients are symmetric. Only the first half of the coefficients are used for filtering.
- The **Tap Sum** parameter determines the data type the filter uses when it sums the inputs prior to multiplication by the coefficients.



# Digital Filter

## FIR (all zeros) direct form antisymmetric




The following constraints are applicable when processing a fixed-point signal with this filter structure:

- Inputs can be real or complex.
- Numerator coefficients can be real or complex.
- You cannot specify the state data type on the block mask for this structure, because the input and output states have the same data types as the input.
- It is assumed that the filter coefficients are antisymmetric. Only the first half of the coefficients are used for filtering.
- The **Tap Sum** parameter determines the data type the filter uses when it sums the inputs prior to multiplication by the coefficients.









# Digital Filter

## FIR (all zeros) lattice MA



The following constraints are applicable when processing a fixed-point signal with this filter structure:

- Inputs and coefficients can be real or complex.
- Coefficients can be real or complex.



## Supported Data Types

- Double-precision floating point
- Single-precision floating point
- Fixed point (signed only)
- 8-, 16-, and 32-bit signed integers

## See Also

Allpole Filter	DSP System Toolbox
Digital Filter Design	DSP System Toolbox
Discrete Filter	Simulink
Discrete FIR Filter	Simulink
Filter Realization Wizard	DSP System Toolbox
dfilt	DSP System Toolbox
fdatool	DSP System Toolbox

# Digital Filter

---

fvtool

Signal Processing Toolbox

sptool

Signal Processing Toolbox

## Purpose

Design and implement digital FIR and IIR filters

## Library

Filtering / Filter Implementations

dsparch4

## Description



---

**Note** Use this block to design, analyze, and efficiently implement floating-point filters. The following blocks also implement digital filters, but serve slightly different purposes:

- **Digital Filter** — Use to efficiently implement floating-point or fixed-point filters that you have already designed. This block provides the same exact filter implementation as the Digital Filter Design block.
- **Filter Realization Wizard** — Use to implement floating-point or fixed-point filters built from Sum, Gain, and Unit Delay blocks. You can either design the filter within this block, or import the coefficients of a filter that you designed elsewhere.

---

The Digital Filter Design block implements a digital FIR or IIR filter that you design using the Filter Design and Analysis Tool (`fdatool`) GUI. This block provides the same filter implementation as the Digital Filter block.

You must specify whether the block performs frame-based or sample-based processing on the input by setting the **Input processing** parameter. The block applies the specified filter to each channel of a discrete-time input signal, and outputs the result. The outputs of the block numerically match the outputs of the Digital Filter block, the MATLAB `filter` function, and the DSP System Toolbox `filter` function.

The sampling frequency,  $F_s$ , that you specify in the FDATool GUI should be identical to the sampling frequency of the input to the Digital Filter Design block. When the sampling frequencies do not match, the

# Digital Filter Design

---

Digital Filter Design block returns a warning message and inherits the sampling frequency of the input block.

## Designing the Filter

Double-click the Digital Filter Design block to open FDATool. Use FDATool to design or import a digital FIR or IIR filter. To learn how to design filters with this block and FDATool, see the following topics:


- “Digital Filter Design Block”
- `fdatool` reference page

## Tuning the Filter During Simulation

You can tune the filter specifications in FDATool during simulations as long as your changes do not modify the filter length or filter order. The filter updates as soon as you apply any filter changes in FDATool.

## Examples

See the “Digital Filter Design Block” section in the DSP System Toolbox documentation.



## Dialog Box

For more information about the parameters on this dialog, see “FDATool”.

# Digital Filter Design

---

## Supported Data Types

- Double-precision floating point
- Single-precision floating point

## See Also

Analog Filter Design	DSP System Toolbox
Window Function	DSP System Toolbox
<code>fdatool</code>	DSP System Toolbox
<code>filter</code>	DSP System Toolbox
<code>fvtool</code>	Signal Processing Toolbox
<code>sptool</code>	Signal Processing Toolbox

To learn how to use this block and `FDATool`, see the following:

- “Filter Design”
- “Filter Analysis”
- “Digital Filter Design Block”

**Purpose** Design and implement a variety of FIR filters

**Library** dspobslib

## Description



---

**Note** The Digital FIR Filter Design block is still supported but is likely to be obsoleted in a future release. We strongly recommend replacing this block with the Digital Filter block.

---

The Digital FIR Filter Design block designs a discrete-time (digital) FIR filter in one of several different band configurations using a window method. Most of these filters are designed using the Signal Processing Toolbox `fir1` function, and are real with linear phase response. The block applies the filter to a discrete-time input using the Direct-Form II Transpose Filter (Obsolete) block.

An  $M$ -by- $N$  sample-based matrix input is treated as  $M*N$  independent channels, and an  $M$ -by- $N$  frame-based matrix input is treated as  $N$  independent channels. In both cases, the block filters each channel independently over time, and the output has the same size and frame status as the input.

For complete details on the classical FIR filter design algorithm, see the description of the `fir1` and `fir2` functions in the Signal Processing Toolbox documentation.


## Band Configurations

The band configuration for the filter is set from the **Filter type** pop-up menu. The band configuration parameters below this pop-up menu adapt appropriately to match the **Filter type** selection.

- **Lowpass and Highpass**


In lowpass and highpass configurations, the **Filter order** and **Cutoff frequency** parameters specify the filter design. Frequencies are normalized to half the sample frequency. The figure below shows the frequency response of the default order-22 filter with cutoff at 0.4.

# Digital FIR Filter Design (Obsolete)



- **Bandpass and Bandstop**


In bandpass and bandstop configurations, the **Filter order**, **Lower cutoff frequency**, and **Upper cutoff frequency** parameters specify the filter design. Frequencies are normalized to half the sample frequency, and the actual filter order is twice the **Filter order** parameter value. The figure below shows the frequency response of the default order-22 filter with lower cutoff at 0.4, and upper cutoff at 0.6.



- **Multiband**

In the multiband configuration, the **Filter order**, **Cutoff frequency vector**, and **Gain in the first band** parameters specify the filter design. The **Cutoff frequency vector** contains frequency points in the range 0 to 1, where 1 corresponds to half the sample frequency. Frequency points must appear in ascending order. The **Gain in the first band** parameter specifies the gain in the first band: 0 indicates a stopband, and 1 indicates a passband. Additional bands alternate between passband and stopband. The figure below shows the frequency response of the default order-22 filter with five bands, the first a passband.

**Cutoff frequency vector** = [0.2 0.4 0.6 0.8]



- **Arbitrary shape**

In the arbitrary shape configuration, the **Filter order**, **Frequency vector**, and **Gains at these frequencies** parameters specify the filter design. The **Frequency vector**,  $f_n$ , contains frequency points in the range 0 to 1 (inclusive) in ascending order, where 1 corresponds to half the sample frequency. The **Gains at these frequencies** parameter,  $m_n$ , is a vector containing the desired magnitude response at the corresponding points in the **Frequency vector**. (Note that the specifications for the **Arbitrary shape** configuration are similar to those for the Yule-Walker IIR Filter Design block. Arbitrary-shape

# Digital FIR Filter Design (Obsolete)


filters are designed using the Signal Processing Toolbox `fir2` function.)

The desired magnitude response of the design can be displayed by typing

```
plot(fn,mn)
```


Duplicate frequencies can be used to specify a step in the response (such as band 2 below). The figure shows an order-100 filter with five bands.

```
Frequency = [0.0 0.3 0.3 0.6 0.7 1.0]
Gains =     [0.0 1.0 0.0 0.0 0.5 0.5]
Band:      ~~~~~ ~~~~~ ~~~~~ ~~~~~ ~~~~~
           f1 f2 f3 f4 f5
```



The **Window type** parameter allows you to select from a variety of different windows. See the Window Function block reference for a complete description of the available options.

## Dialog Box



The parameters displayed in the dialog box vary for different design/band combinations. Only some of the parameters listed below are visible in the dialog box at any one time.

### Filter type

The type of filter to design: **Lowpass**, **Highpass**, **Bandpass**, **Bandstop**, **Multiband**, or **Arbitrary Shape**. Tunable.

### Filter order

The order of the filter. The filter length is one more than this value. For the **Bandpass** and **Bandstop** configurations, the order of the final filter is twice this value.

# Digital FIR Filter Design (Obsolete)

---

## **Cutoff frequency**

The normalized cutoff frequency for the **Highpass** and **Lowpass** filter configurations. A value of 1 specifies half the sample frequency. Tunable.

## **Lower cutoff frequency**

The lower passband or stopband frequency for the **Bandpass** and **Bandstop** filter configurations. A value of 1 specifies half the sample frequency. Tunable.

## **Upper cutoff frequency**

The upper passband or stopband frequency for the **Bandpass** and **Bandstop** filter configurations. A value of 1 specifies half the sample frequency. Tunable.

## **Cutoff frequency vector**

A vector of ascending frequency points defining the cutoff edges for the **Multiband** filter. A value of 1 specifies half the sample frequency. Tunable.

## **Gain in the first band**

The gain in the first band of the **Multiband** filter: 0 specifies a stopband, 1 specifies a passband. Additional bands alternate between passband and stopband. Tunable.

## **Frequency vector**

A vector of ascending frequency points defining the frequency bands of the **Arbitrary shape** filter. The frequency range is 0 to 1 including the endpoints, where 1 corresponds to half the sample frequency. Tunable.

## **Gains at these frequencies**

A vector containing the desired magnitude response for the **Arbitrary shape** filter at the corresponding points in the **Frequency vector**. Tunable.

## **Window type**

The type of window to apply. See the Window Function block reference. Tunable.

## Stopband ripple

The level (dB) of stopband ripple,  $R_s$ , for the **Chebyshev** window. Tunable.

## Beta

The **Kaiser** window  $\beta$  parameter. Increasing **Beta** widens the mainlobe and decreases the amplitude of the window sidelobes in the window's frequency magnitude response. Tunable.

## References

Antoniou, A. *Digital Filters: Analysis, Design, and Applications*. 2nd ed. New York, NY: McGraw-Hill, 1993.

Oppenheim, A. V. and R. W. Schaffer. *Discrete-Time Signal Processing*. Englewood Cliffs, NJ: Prentice Hall, 1989.


Proakis, J. and D. Manolakis. *Digital Signal Processing*. 3rd ed. Englewood Cliffs, NJ: Prentice-Hall, 1996.

# Digital FIR Raised Cosine Filter Design (Obsolete)

**Purpose** Design and implement raised cosine FIR filter

**Library** dspobslib

## Description



---

**Note** The Digital FIR Raised Cosine Filter Design block is still supported but is likely to be obsoleted in a future release. We strongly recommend replacing this block with the Digital Filter block.

---

The Digital FIR Raised Cosine Filter Design block uses the Signal Processing Toolbox `firrcos` function to design a lowpass, linear-phase, digital FIR filter with a raised cosine transition band. The block applies the filter to a discrete-time input using the Direct-Form II Transpose Filter (Obsolete) block.

An  $M$ -by- $N$  sample-based matrix input is treated as  $M*N$  independent channels, and an  $M$ -by- $N$  frame-based matrix input is treated as  $N$  independent channels. In both cases, the block filters each channel independently over time, and the output has the same size and frame status as the input.

The frequency response of the raised cosine filter is

$$H(f) = \begin{cases} \frac{1}{2f_{n0}} & 0 \leq |f| \leq (1-R)f_{n0} \\ \left[ \frac{1 + \cos \frac{\pi}{2Rf_{n0}} (|f| - (1-R)f_{n0})}{4f_{n0}} \right] & (1-R)f_{n0} \leq |f| \leq (1+R)f_{n0} \\ 0 & (1+R)f_{n0} \leq |f| \leq 1 \end{cases}$$

# Digital FIR Raised Cosine Filter Design (Obsolete)

where  $H(f)$  is the magnitude response at frequency  $f$ ,  $f_{n0}$  is the normalized cutoff frequency (-6 dB) specified by the **Upper cutoff frequency** parameter, and  $R$  is a rolloff factor in the range  $[0, 1]$  determining the passband-to-stopband transition width.

The **Square-root raised cosine filter** option designs a filter with magnitude response  $\sqrt{H(f)}$ . This is useful when the filter is part of a pair of matched filters.

When the **Design method** parameter is set to **Rolloff factor**, the secondary **Rolloff factor** parameter is enabled, and  $R$  can be directly specified. When **Design method** is set to **Transition bandwidth**, the secondary **Transition bandwidth** parameter is enabled, and the transition region bandwidth,  $\Delta f$ , can be specified in place of  $R$ . The transition region is centered on  $f_{n0}$  and must be sufficiently narrow to satisfy

$$0 < \left( f_{n0} \pm \frac{\Delta f}{2} \right) < 1$$

The **Upper cutoff frequency** and **Transition bandwidth** parameter values are normalized to half the sample frequency.

The **Window type** parameter allows you to apply a variety of different windows to the raised cosine filter. See the Window Function block reference for a complete description of the available options.

## Algorithm

The filter output is computed by convolving the input with a truncated, delayed, windowed version of the filter's impulse response. The impulse response for the raised cosine filter is

$$h(kT_s) = \frac{1}{F_s} \operatorname{sinc}(2\pi kT_s f_{n0}) \frac{\cos(2\pi RkT_s f_{n0})}{1 - (4RkT_s f_{n0})^2} \quad -\infty < k < \infty$$

which has limits

## Digital FIR Raised Cosine Filter Design (Obsolete)

---

$$h(0) = \frac{1}{F_s}$$

and

$$h\left(\pm \frac{1}{4Rf_{n0}}\right) = \frac{R}{2F_s} \sin\left(\frac{\pi}{2R}\right)$$

The impulse response for the square-root raised cosine filter is

$$h(kT_s) = \frac{4R \cos((1+R)2\pi kT_s f_{n0}) + \frac{\sin((1-R)2\pi kT_s f_{n0})}{8RkT_s f_{n0}}}{\pi F_s \sqrt{\frac{1}{2f_{n0}}((8RkT_s f_{n0})^2 - 1)}} \quad -\infty < k < \infty$$

which has limits

$$h(0) = (-4R - \pi + \pi R) \frac{\sqrt{2f_{n0}}}{\pi F_s}$$

and

$$\begin{aligned} \left(\pm \frac{1}{8Rf_{n0}}\right) = \frac{\sqrt{2f_{n0}}}{2\pi F_s} & \left[ \pi(1+R) \sin\left(\frac{\pi(1+R)}{4R}\right) - 4R \sin\left(\frac{\pi(R-1)}{4R}\right) \right. \\ & \left. + \pi(R-1) \cos\left(\frac{\pi(R-1)}{4R}\right) \right] \end{aligned}$$

# Digital FIR Raised Cosine Filter Design (Obsolete)

## Dialog Box

Function Block Parameters: Digital FIR Raised Cosine Filter Design

Digital FIR Raised Cosine Filter Design (mask) (link)  
Linear phase digital FIR lowpass raised cosine filter.

Parameters

Filter order:  
63

Upper cutoff frequency (0 to 1):  
0.5

Square-root raised cosine filter

Design method: Rolloff factor

Rolloff factor (0 to 1):  
0.6

Window type: Boxcar

Stopband attenuation in dB:  
5

Beta:  
10

Initial conditions:  
0

OK Cancel Help Apply

### Filter order

The order of the filter. The filter length is one more than this value.

### Upper cutoff frequency

The normalized cutoff frequency,  $f_{n0}$ . A value of 1 specifies half the sample frequency. Tunable.

# Digital FIR Raised Cosine Filter Design (Obsolete)

---

## Square-root raised cosine filter

Selects the square-root filter option, which designs a filter with magnitude response  $\sqrt{H(f)}$ . Tunable.

## Design method

The method used to design the transition region of the filter, **Rolloff factor** or **Transition bandwidth**. Tunable.

## Rolloff factor

The rolloff factor,  $R$ , enabled when **Rolloff factor** is selected in the **Design method** parameter. Tunable.

## Transition bandwidth

The transition bandwidth,  $\Delta f$ , enabled when **Transition bandwidth** is selected in the **Design method** parameter. Tunable.

## Window type

The type of window to apply. See the Window Function block reference. Tunable.

## Stopband attenuation in dB

The level (dB) of stopband attenuation,  $R_s$ , for the Chebyshev window. Tunable.

## Beta

The **Kaiser** window  $\beta$  parameter. Increasing  $\beta$  widens the mainlobe and decreases the amplitude of the window sidelobes in the window's frequency magnitude response. Tunable.

## Initial conditions

The filter's initial conditions, a scalar, vector, or matrix. See the Direct-Form II Transpose Filter (Obsolete) block reference for complete syntax information.

## References


Proakis, J. G. *Digital Communications*. Third ed. New York, NY: McGraw-Hill, 1995.

Proakis, J. G. and M. Salehi. *Contemporary Communication Systems Using MATLAB*. Boston, MA: PWS Publishing, 1998.

**Purpose** Design and implement IIR filter

**Library** dspobslib

## Description



---

**Note** The Digital IIR Filter Design block is still supported but is likely to be obsoleted in a future release. We strongly recommend replacing this block with the Digital Filter block.

---

The Digital IIR Filter Design block designs a discrete-time (digital) IIR filter in a lowpass, highpass, bandpass, or bandstop configuration, and applies it to the input using the Direct-Form II Transpose Filter (Obsolete) block.

An  $M$ -by- $N$  sample-based matrix input is treated as  $M*N$  independent channels, and an  $M$ -by- $N$  frame-based matrix input is treated as  $N$  independent channels. In both cases, the block filters each channel independently over time, and the output has the same size and frame status as the input.

The **Design method** parameter allows you to specify Butterworth, Chebyshev type I, Chebyshev type II, and elliptic filter designs. Note that for the bandpass and bandstop configurations, the actual filter length is twice the **Filter order** parameter value.

Filter Design	Description
Butterworth	The magnitude response of a Butterworth filter is maximally flat in the passband and monotonic overall.
Chebyshev type I	The magnitude response of a Chebyshev type I filter is equiripple in the passband and monotonic in the stopband.

# Digital IIR Filter Design (Obsolete)

Filter Design	Description
<b>Chebyshev type II</b>	The magnitude response of a Chebyshev type II filter is monotonic in the passband and equiripple in the stopband.
<b>Elliptic</b>	The magnitude response of an elliptic filter is equiripple in both the passband and the stopband.


The design and band configuration of the filter are selected from the **Design method** and **Filter type** pop-up menus in the dialog box. For each combination of design method and band configuration, an appropriate set of secondary parameters is displayed.

The table below lists the available parameters for each design/band combination. For lowpass and highpass band configurations, these parameters include the passband edge frequency  $f_{np}$ , the stopband edge frequency  $f_{ns}$ , the passband ripple  $R_p$ , and the stopband attenuation  $R_s$ . For bandpass and bandstop configurations, the parameters include the lower and upper passband edge frequencies,  $f_{np1}$  and  $f_{np2}$ , the lower and upper stopband edge frequencies,  $f_{ns1}$  and  $f_{ns2}$ , the passband ripple  $R_p$ , and the stopband attenuation  $R_s$ . Frequency values are normalized to half the sample frequency, and ripple and attenuation values are in dB.

	Lowpass	Highpass	Bandpass	Bandstop
<b>Butterworth</b>	Order, $f_{np}$	Order, $f_{np}$	Order, $f_{np1}$ , $f_{np2}$	Order, $f_{np1}$ , $f_{np2}$
<b>Chebyshev Type I</b>	Order, $f_{np}$ , $R_p$	Order, $f_{np}$ , $R_p$	Order, $f_{np1}$ , $f_{np2}$ , $R_p$	Order, $f_{np1}$ , $f_{np2}$ , $R_p$
<b>Chebyshev Type II</b>	Order, $f_{ns}$ , $R_s$	Order, $f_{ns}$ , $R_s$	Order, $f_{ns1}$ , $f_{ns2}$ , $R_s$	Order, $f_{ns1}$ , $f_{ns2}$ , $R_s$
<b>Elliptic</b>	Order, $f_{np}$ , $R_p$ , $R_s$	Order, $f_{np}$ , $R_p$ , $R_s$	Order, $f_{np1}$ , $f_{np2}$ , $R_p$ , $R_s$	Order, $f_{np1}$ , $f_{np2}$ , $R_p$ , $R_s$

The digital filters are designed using Signal Processing Toolbox software's filter design commands `butter`, `cheby1`, `cheby2`, and `ellip`.

## Dialog Box



The parameters displayed in the dialog box vary for different design/band combinations. Only some of the parameters listed below are visible in the dialog box at any one time.

### Design method

The filter design method: Butterworth, Chebyshev type I, Chebyshev type II, or Elliptic. Tunable.

### Filter type

The type of filter to design: Lowpass, Highpass, Bandpass, or Bandstop. Tunable.

### Filter order

The order of the filter for lowpass and highpass configurations. For bandpass and bandstop configurations, the length of the final filter is twice this value.

### Passband edge frequency

The normalized passband edge frequency for the highpass and lowpass configurations of the Butterworth, Chebyshev type I, and elliptic designs. Tunable.

# Digital IIR Filter Design (Obsolete)

---

## **Lower passband edge frequency**

The normalized lower passband frequency for the bandpass and bandstop configurations of the Butterworth, Chebyshev type I, and elliptic designs. Tunable.

## **Upper passband edge frequency**

The normalized upper passband frequency for the bandpass and bandstop configurations of the Butterworth, Chebyshev type I, or elliptic designs. Tunable.

## **Stopband edge frequency**

The normalized stopband edge frequency for the highpass and lowpass band configurations of the Chebyshev type II design. Tunable.

## **Lower stopband edge frequency**

The normalized lower stopband frequency for the bandpass and bandstop configurations of the Chebyshev type II design. Tunable.

## **Upper stopband edge frequency**

The normalized upper stopband frequency for the bandpass and bandstop filter configurations of the Chebyshev type II design. Tunable.

## **Passband ripple in dB**

The passband ripple, in dB, for the Chebyshev type I and elliptic designs. Tunable.

## **Stopband attenuation in dB**

The stopband attenuation, in dB, for the Chebyshev type II and elliptic designs. Tunable.

## **References**

Antoniou, A. *Digital Filters: Analysis, Design, and Applications*. 2nd ed. New York, NY: McGraw-Hill, 1993.

Oppenheim, A. V. and R. W. Schaffer. *Discrete-Time Signal Processing*. Englewood Cliffs, NJ: Prentice Hall, 1989.

Proakis, J. and D. Manolakis. *Digital Signal Processing*. 3rd ed. Englewood Cliffs, NJ: Prentice-Hall, 1996.

# Direct-Form II Transpose Filter (Obsolete)

---


## Purpose

Apply IIR filter to input

## Library

dspobslib

## Description



---

**Note** This block is now just an implementation of the Digital Filter block.

---

# Discrete Impulse

---

**Purpose** Generate discrete impulse

**Library** Sources  
dspsrcs4

**Description** The Discrete Impulse block generates an impulse (the value 1) at output sample  $D+1$ , where  $D$  is specified by the **Delay** parameter ( $D \geq 0$ ). All output samples preceding and following sample  $D+1$  are zero.

When  $D$  is a length- $N$  vector, the block generates an  $M$ -by- $N$  matrix output representing  $N$  distinct channels, where frame size  $M$  is specified by the **Samples per frame** parameter. The impulse for the  $i$ th channel appears at sample  $D(i)+1$ . For  $M=1$ , the output is sample based; otherwise, the output is frame based.

The **Sample time** parameter value,  $T_s$ , specifies the output signal sample period. The resulting frame period is  $M \cdot T_s$ .

**Examples** Construct the model below.



Configure the Discrete Impulse block to generate a frame-based three-channel output of type `double`, with impulses at samples 1, 4, and 6 of channels 1, 2, and 3, respectively. Use a sample period of 0.25 and a frame size of 4. The corresponding settings should be as follows:

- **Delay** = [0 3 5]
- **Sample time** = 0.25
- **Samples per frame** = 4
- **Output data type** = double

Run the model and look at the output, `dsp_examples_yout`. The first few samples of each channel are shown below.

```
dsp_examples_yout(1:10,:)
```


```
ans =  
    1    0    0  
    0    0    0  
    0    0    0  
    0    1    0  
    0    0    0  
    0    0    1  
    0    0    0  
    0    0    0  
    0    0    0  
    0    0    0  
    0    0    0
```

The block generates an impulse at sample 1 of channel 1 (first column), at sample 4 of channel 2 (second column), and at sample 6 of channel 3 (third column).

# Discrete Impulse

## Dialog Box

The **Main** pane of the Discrete Impulse block dialog appears as follows.



### Delay

The number of zero-valued output samples,  $D$ , preceding the impulse. A length- $N$  vector specifies an  $N$ -channel output.


### Sample time

The sample period,  $T_s$ , of the output signal. The output frame period is  $M \cdot T_s$ .

### Samples per frame

The number of samples,  $M$ , in each output frame. When the value of this parameter is 1, the block outputs a sample-based signal.

The **Data Types** pane of the Discrete Impulse block dialog appears as follows.



## Output data type

Specify the output data type for this block. You can select one of the following:

- A rule that inherits a data type, for example, `Inherit: Inherit via back propagation`. When you select this option, the output data type and scaling matches that of the next downstream block.
- A built in data type, such as `double`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

# Discrete Impulse

---

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point
- Fixed point
- Boolean
- 8-, 16-, and 32-bit signed integers
- 8-, 16-, and 32-bit unsigned integers

## See Also

Data Type Conversion	Simulink
Constant	Simulink
Multiphase Clock	DSP System Toolbox
N-Sample Enable	DSP System Toolbox
Signal From Workspace	DSP System Toolbox
impz	Signal Processing Toolbox

**Purpose** Show value of input

**Library** Sinks  
dspsnks4

**Description** The Display block is an implementation of the Simulink Display block. See Display for more information.

# Downsample

**Purpose** Resample input at lower rate by deleting samples

**Library** Signal Operations  
dsp\_sigops

## Description



The Downsample block decreases the sampling rate of the input by deleting samples. When the block performs frame-based processing, it resamples the data in each column of the  $M_i$ -by- $N$  input matrix independently. When the block performs sample-based processing, it treats each element of the input as a separate channel and resamples each channel of the input array across time. The resample rate is  $K$  times lower than the input sample rate, where  $K$  is the integer you specify for the **Downsample factor** parameter. The Downsample block resamples the input by discarding  $K-1$  consecutive samples following each sample that is passed through to the output.

The **Sample offset** parameter delays the output samples by an integer number of sample periods,  $D$ , where  $0 \leq D \leq (K-1)$ , so that any of the  $K$  possible output phases can be selected. For example, when you downsample the sequence 1, 2, 3, ... by a factor of 4, you can select from the following four phases.

Input Sequence	Sample Offset, $D$	Output Sequence ( $K=4$ )
1, 2, 3, ...	0	1, 5, 9, 13, 17, 21, 25, 29, ...
1, 2, 3, ...	1	0, 2, 6, 10, 14, 18, 22, 26, ...
1, 2, 3, ...	2	0, 3, 7, 11, 15, 19, 23, 27, ...
1, 2, 3, ...	3	0, 4, 8, 12, 16, 20, 24, 28, ...

The initial zero in each of the latter three output sequences in the table is a result of the default zero **Initial conditions** parameter setting for this example. See “Latency” on page 2-527 for more information on the **Initial conditions** parameter.

This block supports triggered subsystems when you set the **Rate options** parameter to `Enforce single-rate processing`.

## Sample-Based Processing

When you set the **Input processing** parameter to `Elements as channels (sample based)`, the input can be an N-D array. The Downsample block treats each element of the input as a separate channel, and resamples each channel of the input over time. The block downsamples the input array by discarding  $K-1$  samples following each sample that it passes through to the output. The input and output sizes of the Downsample block are identical.

The **Rate options** parameter specifies how the block adjusts the rate at the output to accommodate the reduced number of samples. There are two available options:

- `Allow multirate processing`

When you select `Allow multirate processing`, the sample period of the output is  $K$  times longer than the input sample period ( $T_{so} = KT_{si}$ ).

- `Enforce single-rate processing`

When you select `Enforce single-rate processing`, the block forces the output sample rate to match the input sample rate ( $T_{so} = T_{si}$ ) by repeating every  $K$ th input sample  $K$  times at the output. In this mode, the behavior of the block is similar to the operation of a Sample and Hold block with a repeating trigger event of period  $KT_{si}$ .

## Frame-Based Processing

When you set the **Input processing** parameter to `Columns as channels (frame based)`, the block treats each of the  $N$  input columns as an individual channel containing  $M_i$  sequential time samples. The block downsamples each channel independently by discarding  $K-1$  rows of the input matrix following each row that it passes through to the output.


# Downsample

The **Rate options** parameter specifies how the block adjusts the rate at the output to accommodate the reduced number of samples. There are two available options:

- Allow multirate processing

The block generates the output at the slower (downsampled) rate by using a proportionally longer frame *period* at the output port than at the input port. For downsampling by a factor of  $K$ , the output frame period is  $K$  times longer than the input frame period ( $T_{fo} = KT_{fi}$ ), but the input and output frame sizes are equal.


The `ex_downsample_ref1` model shows a single-channel input with a frame period of 1 second being downsampled by a factor of 4 to a frame period of 4 seconds. The input and output frame sizes are identical.



- Enforce single rate processing

The block generates the output at the slower (downsampled) rate using a proportionally smaller frame *size* than the input. For downsampling by a factor of  $K$ , the output frame size is  $K$  times smaller than the input frame size ( $M_o = M_i/K$ ), but the input and output frame rates are equal.

The `ex_downsample_ref2` model shows a single-channel input with a frame size of 64 being downsampled by a factor of 4 to a frame size of 16. The input and output frame rates are identical.



## Latency

The Downsample block has *zero-tasking latency* in the following cases:

- The **Downsample factor** parameter,  $K$ , is 1.
- The **Input processing** parameter is set to **Columns as channels** (frame based) and the **Rate options** parameter is set to **Enforce single-rate processing**.
- The **Input processing** parameter is set to **Columns as channels** (frame based) and the input frame size is equal to one.
- The **Input processing** parameter is set to **Elements as channels** (sample based), and **Sample offset** parameter,  $D$ , is 0.

Zero-tasking latency means that the block propagates input sample  $D+1$  (received at  $t=0$ ) as the first output sample, followed by input sample  $D+1+K$ , input sample  $D+1+2K$ , and so on. When there is zero-tasking latency, the block ignores the value of the **Initial conditions** parameter.

In all other cases, the latency is nonzero:

- When the **Input processing** parameter is set to **Elements as channels** (sample based), the latency is one sample.
- When the **Input processing** parameter is set to **Columns as channels** (frame based) and the input frame size is greater than one, the latency is one frame.

# Downsample

In all cases of *one-sample latency*, the initial condition for each channel appears as the first output sample. Input sample  $D+1$  appears as the second output sample for each channel, followed by input sample  $D+1+K$ , input sample  $D+1+2K$ , and so on. The **Initial conditions** parameter can be an array of the same size as the input, or a scalar to be applied to all signal channels.

In all cases of *one-frame latency*, the  $M_i$  rows of the initial condition matrix appear in sequence as the first  $M_i$  output rows. Input sample  $D+1$  (i.e. row  $D+1$  of the input matrix) appears in the output as sample  $M_i+1$ , followed by input sample  $D+1+K$ , input sample  $D+1+2K$ , and so on. The **Initial conditions** value can be an  $M_i$ -by- $N$  matrix containing one value for each channel, or a scalar to be repeated across all elements of the  $M_i$ -by- $N$  matrix. See the following example for an illustration of this case.


---

**Note** For more information on latency and the Simulink tasking modes, see “Excess Algorithmic Delay (Tasking Latency)” and “Scheduling” in the *Simulink Coder User’s Guide*.

---

## Examples

Open the `ex_downsample_ref3` model.




Run the model and look at the output, `yout`. The first few samples of each channel are as follows:

`yout =`

11	-11
12	-12
13	-13
14	-14
2	-2
4	-4
6	-6
8	-8
10	-10
12	-12
14	-14

You can see from the two Probe blocks that there are at least two distinct frame rates in this model. Because you ran this model in multirate, multitasking mode, the first row of the initial condition matrix appears as the first output sample, followed by the other three initial condition rows. The second row of the first input matrix (row  $D+1$ , where  $D$  is the **Sample offset**) appears in the output as sample 5 (sample  $M_i+1$ , where  $M_i$  is the input frame size).

# Downsample



## Dialog Box

### Downsample factor

The integer factor,  $K$ , by which to decrease the input sample rate.

### Sample offset

The sample offset,  $D$ , which must be an integer in the range  $[0, K-1]$ .

### Input processing

Specify how the block should process the input. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel. See “Frame-Based Processing” on page 2-525 for more information
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a

separate channel. See “Sample-Based Processing” on page 2-525 for more information.

---

**Note** The Inherited (this choice will be removed - see release notes) option will be removed in a future release.

---

### Rate options

Specify the method by which the block should downsample the input. You can select one of the following options:

- **Enforce single-rate processing** — When you select this option, the block maintains the input sample rate.
- **Allow multirate processing** — When you select this option, the block downsamples the signal such that the output sample rate is  $K$  times slower than the input sample rate.

### Initial conditions

The value with which the block is initialized for cases of nonzero latency. You can specify a scalar, or an array of the same size as the input. This parameter appears only when you set the **Rate options** parameter to **Allow multirate processing**.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>

# Downsample

---

Port	Supported Data Types
	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

## See Also

FIR Decimation	DSP System Toolbox
FIR Rate Conversion	DSP System Toolbox
Repeat	DSP System Toolbox
Sample and Hold	DSP System Toolbox
Upsample	DSP System Toolbox

**Purpose** Generate discrete- or continuous-time constant signal

**Library** Sources  
dspobslib

## Description



---

**Note** The DSP Constant block is still supported but is likely to be obsoleted in a future release. We strongly recommend replacing this block with the Constant block.

---

The DSP Constant block generates a signal whose value remains constant throughout the simulation. The **Constant value** parameter specifies the constant to output, and can be any valid MATLAB expression that evaluates to a scalar, vector, or matrix.


When **Sample mode** is set to Continuous, the output is a continuous-time signal. When **Sample mode** is set to Discrete, the **Sample time** parameter is visible, and the signal has the discrete output period specified by the **Sample time** parameter.

You can set the output signal to Frame-based, Sample-based, or Sample-based (interpret vectors as 1-D) with the **Output** parameter.

# DSP Constant (Obsolete)

## Dialog Box

The **Main** pane of the DSP Constant block dialog box appears as follows.



### Constant value

Specify the constant to generate. This parameter is Tunable; values entered here can be tuned, but their dimensions must remain fixed.

When you specify any data type information in this field, it is overridden by the value of the **Output data type** parameter in the **Data Types** pane, unless you select Inherit from 'Constant value'.

### Sample mode

Specify the sample mode of the output, Discrete for a discrete-time signal or Continuous for a continuous-time signal.

### Output


Specify whether the output is Sample-based (interpret vectors as 1-D), Sample-based, or Frame-based. When you select Sample-based and the output is a vector, its dimension

is constrained to match the **Constant value** dimension (row or column). When you select **Sample-based** (interpret vectors as 1-D), however, the output has no specified dimensionality.

## Sample time

Specify the discrete sample period for sample-based outputs. When you select **Frame-based** for the **Output** parameter, this parameter is named **Frame period**, and is the discrete frame period for the frame-based output. This parameter is only visible when you select **Discrete** for the **Sample mode** parameter.

The **Data Types** pane of the DSP Constant block dialog box appears as follows.



## Output data type

Specify the output data type in one of the following ways:

- Choose one of the built-in data types from the list.

## DSP Constant (Obsolete)

---

- Choose **Fixed-point** to specify the output data type and scaling in the **Signed**, **Word length**, **Set fraction length in output to**, and **Fraction length** parameters.
- Choose **User-defined** to specify the output data type and scaling in the **User-defined data type**, **Set fraction length in output to**, and **Fraction length** parameters.
- Choose **Inherit** from 'Constant value' to set the output data type and scaling to match the values of the **Constant value** parameter in the **Main** pane.
- Choose **Inherit via back propagation** to set the output data type and scaling to match the following block.

The value of this parameter overrides any data type information specified in the **Constant value** parameter in the **Main** pane, except when you select **Inherit** from 'Constant value'.

### **Signed**

Select to output a signed fixed-point signal. Otherwise, the signal is unsigned. This parameter is only visible when you select **Fixed-point** for the **Output data type** parameter.

### **Word length**

Specify the word length, in bits, of the fixed-point output data type. This parameter is only visible when you select **Fixed-point** for the **Output data type** parameter.

### **User-defined data type**

Specify any built-in or fixed-point data type. You can specify fixed-point data types using the following Simulink Fixed Point functions: `sfix`, `ufix`, `sint`, `uint`, `sfrac`, and `ufrac`. This parameter is only visible when you select **User-defined** for the **Output data type** parameter.

### **Set fraction length in output to**

Specify the scaling of the fixed-point output by either of the following two methods:

- Choose **Best precision** to have the output scaling automatically set such that the output signal has the best possible precision.
- Choose **User-defined** to specify the output scaling in the **Fraction length** parameter.

This parameter is only visible when you select **Fixed-point** for the **Output data type** parameter, or when you select **User-defined** and the specified output data type is a fixed-point data type.

### Fraction length

For fixed-point output data types, specify the number of fractional bits, or bits to the right of the binary point. This parameter is only visible when you select **Fixed-point** or **User-defined** for the **Output data type** parameter and **User-defined** for the **Set fraction length in output to** parameter.

### Supported Data Types

- Double-precision floating point
- Single-precision floating point
- Fixed point
- Boolean
- 8-, 16-, and 32-bit signed integers
- 8-, 16-, and 32-bit unsigned integers

### See Also

Constant	Simulink
Signal From Workspace	DSP System Toolbox

# DWT

---

## Purpose

Discrete wavelet transform (DWT) of input or decompose signals into subbands with smaller bandwidths and slower sample rates


## Library

Transforms

`dspxfm3`

## Description

The DWT block is the same as the Dyadic Analysis Filter Bank block in the Multirate Filters library, but with different default settings. See the Dyadic Analysis Filter Bank block reference page for more information.



**Purpose** Decompose signals into subbands with smaller bandwidths and slower sample rates or compute discrete wavelet transform (DWT)

**Library** Filtering / Multirate Filters  
dspmlti4

## Description

---

**Note** This block always interprets input signals as frames. The frame size of the input signal must be a multiple of  $2^n$ , where  $n$  is the value of the **Number of levels** parameter. The block decomposes the input signal into either  $n+1$  or  $2^n$  subbands. To decompose signals with a frame size that is not a multiple of  $2^n$ , use the Two-Channel Analysis Subband Filter block. (You can connect multiple copies of the Two-Channel Analysis Subband Filter block to create a multilevel dyadic analysis filter bank.)

---

You can configure this block to compute the Discrete Wavelet Transform (DWT) or decompose a broadband signal into a collection of subbands with smaller bandwidths and slower sample rates. The block uses a series of highpass and lowpass FIR filters to repeatedly divide the input frequency range, as illustrated in the figure “n-Level Asymmetric Dyadic Analysis Filter Bank”.

You can specify the filter bank’s highpass and lowpass filters by providing vectors of filter coefficients. You can do so directly on the block mask, or, if you have a Wavelet Toolbox™ license, you can specify wavelet-based filters by selecting a wavelet from the **Filter** parameter. You must set the filter bank structure to asymmetric or symmetric, and specify the number of levels in the filter bank.

For the same input, the DWT configuration of this block does not produce the same results as the Wavelet Toolbox `dwt` function. Because DSP System Toolbox is designed for real-time implementation and Wavelet Toolbox is designed for analysis, the products handle boundary conditions and filter states differently. To make the output of the `dwt`

# Dyadic Analysis Filter Bank

---

function match the DWT output of this block, complete the following steps:

- 1 Set the boundary condition of the `dwt` function to zero-padding. To do so, type `dwtmode('zpd')` at the MATLAB command line.
- 2 To match the latency of the block (implemented using FIR filters), add zeros to the input of the `dwt` function. The number of zeros you add must be equal to the half-length of the filter.

## Input Requirements

- Input must be a vector or matrix.
- The input frame size must be a multiple of  $2^n$ , where  $n$  is the number of filter bank levels. For example, a frame size of 16 would be appropriate for a three-level tree (16 is a multiple of  $2^3$ ).
- The block always treats input signals as frames and operates along the columns.

For an illustration of why the above input requirements exist, see the figure *Outputs of a 3-Level Asymmetric Dyadic Analysis Filter Bank* on page 2-541.

## Output Characteristics


The output characteristics vary depending on the block's parameter settings, as summarized in the following list and figure:

- **Number of levels** parameter set to  $n$
- **Tree structure** parameter setting:
  - **Asymmetric** — Block produces  $n+1$  output subbands
  - **Symmetric** — Block produces  $2^n$  output subbands
- **Output** parameter setting can be **Multiple ports** or **Single port**. When you set the **Output** parameter to **Single port**, the block outputs one vector or matrix of concatenated subbands. The following figure illustrates the difference between the two settings for a

# Dyadic Analysis Filter Bank

3-level asymmetric dyadic analysis filter bank. For an explanation of the illustrated output characteristics, see the table Output Characteristics for an n-Level Dyadic Analysis Filter Bank on page 2-542.

For more information about the filter bank levels and structures, see “Dyadic Analysis Filter Banks”.



**Outputs of a 3-Level Asymmetric Dyadic Analysis Filter Bank**

# Dyadic Analysis Filter Bank

The following table summarizes the different output characteristics of the block when it is set to output from single or multiple ports.

## Output Characteristics for an n-Level Dyadic Analysis Filter Bank

	Single Output Port	Multiple Output Ports
<b>Output Description</b>	Block concatenates all the subbands into one vector or matrix, and outputs the concatenated subbands from a single output port. Each output column contains subbands of the corresponding input channel.	Block outputs each subband from a separate output port. The topmost port outputs the subband with the highest frequencies. Each output column contains a subband for the corresponding input channel.
<b>Output Frame Rate</b>	<i>Not applicable</i>	Same as input frame rate (However, the output frame sizes can vary, so the output sample rates can vary.)
<b>Output Dimensions (Frame Size)</b>	Same number of rows and columns as the input.	<p>The output has the same number of columns as the input. The number of output rows is the output frame size. For an input with frame size <math>M_i</math> output <math>y_k</math> has frame size <math>M_{o,k}</math>:</p> <ul style="list-style-type: none"> <li>• <b>Symmetric</b> — All outputs have the frame size, <math>M_i / 2^n</math>.</li> <li>• <b>Asymmetric</b> — The frame size of each output (except the last) is half that of the output from the previous level. The outputs from the last two output ports have the same frame size since they originate from the same level in the filter bank.</li> </ul>

## Output Characteristics for an n-Level Dyadic Analysis Filter Bank (Continued)

	Single Output Port	Multiple Output Ports
		$M_{o,k} = \begin{cases} M_i / 2^k & (1 \leq k \leq n) \\ M_i / 2^n & (k = n + 1) \end{cases}$
<b>Output Sample Rate</b>	Same as input sample rate.	<p>Though the outputs have the same frame rate as the input, they have different frame sizes than the input. Thus, the output sample rates, <math>F_{so, k}</math>, are different from the input sample rate, <math>F_{si}</math>:</p> <ul style="list-style-type: none"> <li>• <b>Symmetric</b> — All outputs have the sample rate <math>F_{si} / 2^n</math>.</li> <li>• <b>Asymmetric</b> —</li> </ul> $F_{so,k} = \begin{cases} F_{si} / 2^k & (1 \leq k \leq n) \\ F_{si} / 2^n & (k = n + 1) \end{cases}$

### Filter Bank Filters

You must specify the highpass and lowpass filters in the filter bank by setting the **Filter** parameter to one of the following options:

- **User defined** — Allows you to explicitly specify the filters with two vectors of filter coefficients in the **Lowpass FIR filter coefficients** and **Highpass FIR filter coefficients** parameters. The block uses the same lowpass and highpass filters throughout the filter bank. The two filters should be halfband filters, where each filter passes the frequency band that the other filter stops.
- **Wavelet** such as **Biorthogonal** or **Daubechies** — The block uses the specified wavelet to construct the lowpass and highpass filters using the Wavelet Toolbox `wfilters` function. Depending on the wavelet,

# Dyadic Analysis Filter Bank

the block might enable either the **Wavelet order** or **Filter order [synthesis / analysis]** parameter. (The latter parameter allows you to specify different wavelet orders for the analysis and synthesis filter stages.) You must have a Wavelet Toolbox license to use wavelets.

## Specifying Filters with the Filter Parameter and Related Parameters


Filter	Sample Setting for Related Filter Specification Parameters	Corresponding Wavelet Function Syntax
User-defined	Filters based on Daubechies wavelets with wavelet order 3: <ul style="list-style-type: none"> <li>• <b>Lowpass FIR filter coefficients =</b> [0.0352 -0.0854 -0.1350 0.4599 0.8069 0.3327]</li> <li>• <b>Highpass FIR filter coefficients =</b> [-0.3327 0.8069 -0.4599 -0.1350 0.0854 0.0352]</li> </ul>	None
Haar	None	wfilters('haar')
Daubechies	<b>Wavelet order = 4</b>	wfilters('db4')
Symlets	<b>Wavelet order = 3</b>	wfilters('sym3')
Coiflets	<b>Wavelet order = 1</b>	wfilters('coif1')
Biorthogonal	<b>Filter order [synthesis / analysis] = [3/1]</b>	wfilters('bior3.1')
Reverse Biorthogonal	<b>Filter order [synthesis / analysis] = [3/1]</b>	wfilters('rbio3.1')
Discrete Meyer	None	wfilters('dmey')

## Examples

### Wavelets

The primary application for dyadic analysis filter banks and dyadic synthesis filter banks is coding for data compression using wavelets.

At the transmitting end, the output of the dyadic analysis filter bank is fed to a lossy compression scheme, which typically assigns the number of bits for each filter bank output in proportion to the relative energy in that frequency band. This represents the more powerful signal components by a greater number of bits than the less powerful signal components.



At the receiving end, the transmission is decoded and fed to a dyadic synthesis filter bank to reconstruct the original signal. The filter coefficients of the complementary analysis and synthesis stages are designed to cancel aliasing introduced by the filtering and resampling.

See “Calculate Channel Latencies Required for Wavelet Reconstruction” for an example using the Dyadic Analysis and Dyadic Synthesis Filter Bank blocks.


### Examples

See the floating-point frame-based version of the DSP System Toolbox Wavelet Reconstruction and Noise Reduction example, which uses the Dyadic Analysis Filter Bank and Dyadic Synthesis Filter Bank blocks.

## Dialog Box

The parameters displayed in the block dialog vary depending on the setting of the **Filter** parameter. Only some of the parameters described below are visible in the dialog box at any one time.

# Dyadic Analysis Filter Bank



## Filter

The type of filter used to determine the high- and low-pass FIR filters in the filter bank:

Select **User defined** to explicitly specify the filter coefficients in the **Lowpass FIR filter coefficients** and **Highpass FIR filter coefficients** parameters.

Select a wavelet such as **Biorthogonal** or **Daubechies** to specify a wavelet-based filter. The block uses the Wavelet Toolbox `wfilters` function to construct the filters. Extra parameters such as **Wavelet order** or **Filter order [synthesis / analysis]** might become enabled. For a list of the supported wavelets, see *Specifying Filters with the Filter Parameter and Related Parameters* on page 2-544.

## Lowpass FIR filter coefficients

A vector of filter coefficients (descending powers of  $z$ ) that specifies coefficients used by all the lowpass filters in the filter bank. This parameter is enabled when you set **Filter** to **User defined**. The lowpass filter should be a half-band filter that passes the frequency band stopped by the filter specified in the **Highpass FIR filter coefficients** parameter. The default values of this parameter specify a filter based on a Daubechies wavelet with wavelet order 3.

## Highpass FIR filter coefficients

A vector of filter coefficients (descending powers of  $z$ ) that specifies coefficients used by all the highpass filters in the filter bank. This parameter is enabled when you set **Filter** to **User defined**. The highpass filter should be a half-band filter that passes the frequency band stopped by the filter specified in the **Lowpass FIR filter coefficients** parameter. The default values of this parameter specify a filter based on a Daubechies wavelet with wavelet order 3.

# Dyadic Analysis Filter Bank

---

## Wavelet order

The order of the wavelet selected in the **Filter** parameter. This parameter is enabled only when you set **Filter** to certain types of wavelets, as shown in the Specifying Filters with the Filter Parameter and Related Parameters on page 2-544 table.

## Filter order [synthesis / analysis]

The order of the wavelet for the synthesis and analysis filter stages. For example, when you set the **Filter** parameter to **Biorthogonal** and set the **Filter order [synthesis / analysis]** parameter to [2 / 6], the block calls the `wfilters` function with input argument `'bior2.6'`. This parameter is enabled only when you set **Filter** to certain types of wavelets, as shown in Specifying Filters with the Filter Parameter and Related Parameters on page 2-544.

## Number of levels

The number of filter bank levels. An  $n$ -level asymmetric structure has  $n+1$  outputs, and an  $n$ -level symmetric structure has  $2^n$  outputs, as shown in the figures “ $n$ -Level Asymmetric Dyadic Analysis Filter Bank” and “ $n$ -Level Symmetric Dyadic Analysis Filter Bank”. The block’s icon changes depending on the value of this parameter.

The default setting of this parameter is 2.

## Tree structure

The structure of the filter bank: **Asymmetric**, or **Symmetric**. See the figures “ $n$ -Level Asymmetric Dyadic Analysis Filter Bank” and “ $n$ -Level Symmetric Dyadic Analysis Filter Bank”.

The default setting of this parameter is **Asymmetric** for the Dyadic Analysis Filter Bank block, and **Symmetric** for the DWT block.

## Output

Set to **Multiple ports** to output each output subband on a separate port (the topmost port outputs the subband with the highest frequency band). Set to **Single port** to concatenate the subbands into one vector or matrix and output the concatenated

subbands on a single port. For more information, see “Output Characteristics” on page 2-540.

The default setting of this parameter is `Multiple ports` for the Dyadic Analysis Filter Bank block, and `Single port` for the DWT block.

## References

Fliege, N. J. *Multirate Digital Signal Processing: Multirate Systems, Filter Banks, Wavelets*. West Sussex, England: John Wiley & Sons, 1994.

Strang, G. and T. Nguyen. *Wavelets and Filter Banks*. Wellesley, MA: Wellesley-Cambridge Press, 1996.

Vaidyanathan, P. P. *Multirate Systems and Filter Banks*. Englewood Cliffs, NJ: Prentice Hall, 1993.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

## See Also

DWT	DSP System Toolbox
Dyadic Synthesis Filter Bank	DSP System Toolbox
Two-Channel Analysis Subband Filter	DSP System Toolbox

# Dyadic Synthesis Filter Bank

## Purpose


Reconstruct signals from subbands with smaller bandwidths and slower sample rates or compute inverse discrete wavelet transform (IDWT)

## Library

Filtering / Multirate Filters

dspmlti4

## Description



---

**Note** This block always does frame-based processing, and its inputs must be of certain sizes. To use input subbands that do not fit the criteria of this block, use the Two-Channel Synthesis Subband Filter block. (You can connect multiple copies of the Two-Channel Synthesis Subband Filter block to create a multilevel dyadic synthesis filter bank.)

---

You can configure this block to compute the inverse discrete wavelet transform (IDWT) or reconstruct a signal from subbands with smaller bandwidths and slower sample rates. When the block computes the inverse discrete wavelet transform (IDWT) of the input, the output has the same dimensions as the input. Each column of the output is the IDWT of the corresponding input column. When reconstructing a signal, the block uses a series of highpass and lowpass FIR filters to reconstruct the signal from the input subbands, as illustrated in the figure “n-Level Asymmetric Dyadic Synthesis Filter Bank”. The reconstructed signal has a wider bandwidth and faster sample rate than the input subbands.

You can specify the filter bank’s highpass and lowpass filters by providing vectors of filter coefficients. You can do so directly on the block mask, or, if you have a Wavelet Toolbox license, you can specify wavelet-based filters by selecting a wavelet from the **Filter** parameter. You must set the filter bank structure to asymmetric or symmetric, and specify the number of levels in the filter bank.

When you set the **Input** parameter to **Multiple ports**, you must provide each subband to the block through a different input port as a vector or matrix. You should input the highest frequency band through the topmost port. When you set the **Input** parameter to **Single port**, the block input must be a vector or matrix of concatenated subbands.

---

**Note** To use a dyadic synthesis filter bank to perfectly reconstruct the output of a dyadic analysis filter bank, the number of levels and tree structures of both filter banks *must* be the same. In addition, the filters in the synthesis filter bank *must* be designed to perfectly reconstruct the outputs of the analysis filter bank. Otherwise, the reconstruction is not perfect.

This block automatically computes wavelet-based perfect reconstruction filters when the wavelet selection in the **Filter** parameter of this block is the *same* as the **Filter** parameter setting of the corresponding Dyadic Analysis Filter Bank block. The use of wavelets requires a Wavelet Toolbox license. To learn how to design your own perfect reconstruction filters, see “References” on page 2-560.

---

## Input Requirements

The inputs to this block are usually the outputs of a Dyadic Analysis Filter Bank block. Since the Dyadic Analysis Filter Bank block can output from either a single port or multiple ports, the Dyadic Synthesis Filter Bank block accepts inputs to either a single port or multiple ports.

The **Input** parameter sets whether the block accepts inputs from a single port or multiple ports, and thus determines the input requirements, as summarized in the following lists and figure.

---

**Note** Any output of a Dyadic Analysis Filter Bank block whose parameter settings match the corresponding settings of this block is a valid input to this block. For example, the setting of the Dyadic Analysis Filter Bank block parameter, **Output**, must be the same as this block’s **Input** parameter (Single port or Multiple ports).

---

## Valid Inputs for Input Set to Single Port

- Inputs must be vectors or matrices of concatenated subbands. The block always interprets the inputs as sample based.

# Dyadic Synthesis Filter Bank


---

- Each input column contains the subbands for an independent signal.
- Upper input rows contain the high-frequency subbands, and the lower rows contain the low-frequency subbands.

## **Valid Inputs for Input Set to Multiple Ports**

- Each subband must be provided as a vector or matrix to separate block input ports. The block always interprets the inputs as frame based.
- The columns of each input contains a subband for an independent signal.
- The input to the topmost input port is the subband containing the highest frequencies, and the input to the bottommost port is the subband containing the lowest frequencies.

# Dyadic Synthesis Filter Bank



**Valid Inputs to a 3-Level Asymmetric Dyadic Synthesis Filter Bank**

# Dyadic Synthesis Filter Bank

For general information about the filter banks, see “Dyadic Synthesis Filter Banks”.

## Output Characteristics

The following table summarizes the output characteristics for both types of inputs. For an illustration of why the output characteristics exist, see the figure Valid Inputs to a 3-Level Asymmetric Dyadic Synthesis Filter Bank on page 2-553.

	<b>Input = Multiple ports</b>	<b>Input = Single port (Concatenated Subband Inputs)</b>
<b>Output Frame Rate</b>	Same as the input frame rate.	Same as the input rate (the rate of the concatenated subband inputs).
<b>Output Frame Dimensions</b>	<ul style="list-style-type: none"><li>• The output has the same number of columns as the inputs.</li><li>• The number of output rows depends on the tree structure of the filter bank:<ul style="list-style-type: none"><li>▪ <b>Asymmetric</b> — The number of output rows is twice the number of rows in the input to the topmost input port.</li><li>▪ <b>Symmetric</b> — The number of output rows is the product of the number of input ports and the number of rows in an input to any input port.</li></ul></li></ul>	The output has the same number of rows and columns as the input.

For general information about the filter banks, see “Dyadic Synthesis Filter Banks”.

## Filter Bank Filters

You must specify the highpass and lowpass filters in the filter bank by setting the **Filter** parameter to one of the following options:

- **User defined** — Allows you to explicitly specify the filters with two vectors of filter coefficients in the **Lowpass FIR filter coefficients** and **Highpass FIR filter coefficients** parameters. The block uses the same lowpass and highpass filters throughout the filter bank. The two filters should be halfband filters, where each filter passes the frequency band that the other filter stops. To use this block to perfectly reconstruct a signal decomposed by a Dyadic Analysis Filter Bank block, the filters in this block *must* be designed to perfectly reconstruct the outputs of the analysis filter bank. To learn how to design your own perfect reconstruction filters, see “References” on page 2-560.
- **Wavelet such as Biorthogonal or Daubechies** — The block uses the specified wavelet to construct the lowpass and highpass filters using the Wavelet Toolbox function `wfilters`. Depending on the wavelet, the block might enable either the **Wavelet order** or **Filter order [synthesis / analysis]** parameter. (The latter parameter allows you to specify different wavelet orders for the analysis and synthesis filter stages.) To use this block to reconstruct a signal decomposed by a Dyadic Analysis Filter Bank block, you must set both blocks to use the same wavelets with the same order. You must have a Wavelet Toolbox license to use wavelets.

# Dyadic Synthesis Filter Bank

## Specifying Filters with the Filter Parameter and Related Parameters


Filter	Sample Setting for Related Filter Specification Parameters	Corresponding Wavelet Function Syntax
User-defined	Filters based on Daubechies wavelets with wavelet order 3: <ul style="list-style-type: none"><li>• <b>Lowpass FIR filter coefficients =</b> [0.0352 -0.0854 -0.1350 0.4599 0.8069 0.3327]</li><li>• <b>Highpass FIR filter coefficients =</b> [-0.3327 0.8069 -0.4599 -0.1350 0.0854 0.0352]</li></ul>	None
Haar	None	wfilters('haar')
Daubechies	Wavelet order = 4	wfilters('db4')
Symlets	Wavelet order = 3	wfilters('sym3')
Coiflets	Wavelet order = 1	wfilters('coif1')
Biorthogonal	Filter order [synthesis / analysis] = [3/1]	wfilters('bior3.1')
Reverse Biorthogonal	Filter order [synthesis / analysis] = [3/1]	wfilters('rbio3.1')
Discrete Meyer	None	wfilters('dmey')

### Examples

See “Examples” on page 2-545 on the Dyadic Analysis Filter Bank block reference page.

### Dialog Box

The parameters displayed in the block dialog vary depending on the setting of the **Filter** parameter. Only some of the parameters described below are visible in the dialog box at any one time.



# Dyadic Synthesis Filter Bank

---

---

**Note** To use this block to reconstruct a signal decomposed by a Dyadic Analysis Filter Bank block, all the parameters in this block must be the same as the corresponding parameters in the Dyadic Analysis Filter Bank block (except the **Lowpass FIR filter coefficients** and **Highpass FIR filter coefficients**; see the descriptions of these parameters).

---

## Filter

The type of filter used to determine the high- and low-pass FIR filters in the filter bank:

- Select **User defined** to explicitly specify the filter coefficients in the **Lowpass FIR filter coefficients** and **Highpass FIR filter coefficients** parameters.
- Select a wavelet such as **Biorthogonal** or **Daubechies** to specify a wavelet-based filter. The block uses the Wavelet Toolbox `wfilters` function to construct the filters. Extra parameters such as **Wavelet order** or **Filter order [synthesis / analysis]** might become enabled. For a list of the supported wavelets, see the table Specifying Filters with the Filter Parameter and Related Parameters on page 2-556.

## Lowpass FIR filter coefficients

A vector of filter coefficients (descending powers of  $z$ ) that specifies coefficients used by all the lowpass filters in the filter bank. This parameter is enabled when you set **Filter** to **User defined**. The lowpass filter should be a half-band filter that passes the frequency band stopped by the filter specified in the **Highpass FIR filter coefficients** parameter. To perfectly reconstruct a signal decomposed by the Dyadic Analysis Filter Bank, the filters in this block *must* be designed to perfectly reconstruct the outputs of the analysis filter bank. Otherwise, the reconstruction is not perfect. The default values of this parameter specify a perfect reconstruction filter for the default settings of the Dyadic Analysis Filter Bank (based on a Daubechies wavelet with wavelet order 3).

## Highpass FIR filter coefficients

A vector of filter coefficients (descending powers of  $z$ ) that specifies coefficients used by all the highpass filters in the filter bank. This parameter is enabled when you set **Filter** to **User defined**. The highpass filter should be a half-band filter that passes the frequency band stopped by the filter specified in the **Lowpass FIR filter coefficients** parameter. To perfectly reconstruct a signal decomposed by the Dyadic Analysis Filter Bank, the filters in this block *must* be designed to perfectly reconstruct the outputs of the analysis filter bank. Otherwise, the reconstruction is not perfect. The default values of this parameter specify a perfect reconstruction filter for the default settings of the Dyadic Analysis Filter Bank (based on a Daubechies wavelet with wavelet order 3).

## Wavelet order

The order of the wavelet selected in the **Filter** parameter. This parameter is enabled only when you set **Filter** to certain types of wavelets, as shown in the table Specifying Filters with the Filter Parameter and Related Parameters on page 2-556.

## Filter order [synthesis / analysis]

The order of the wavelet for the synthesis and analysis filter stages. For example, when you set the **Filter** parameter to **Biorthogonal** and set the **Filter order [synthesis / analysis]** parameter to [2 / 6], the block calls the `wfilters` function with input argument `'bior2.6'`. This parameter is enabled only when you set **Filter** to certain types of wavelets, as shown in Specifying Filters with the Filter Parameter and Related Parameters on page 2-556.

## Number of levels

The number of filter bank levels. An  $n$ -level asymmetric structure has  $n+1$  inputs, and an  $n$ -level symmetric structure has  $2^n$  inputs, as shown in “ $n$ -Level Asymmetric Dyadic Synthesis Filter Bank” and “ $n$ -Level Symmetric Dyadic Synthesis Filter Bank”.

The default setting of this parameter is 2.

# Dyadic Synthesis Filter Bank

---

## Tree structure

The structure of the filter bank: **Asymmetric**, or **Symmetric**. See the figures “n-Level Asymmetric Dyadic Synthesis Filter Bank” and “n-Level Symmetric Dyadic Synthesis Filter Bank”.

The default setting of this parameter is **Asymmetric** for the Dyadic Synthesis Filter Bank block, and **Symmetric** for the IDWT block.

## Input

Set to **Multiple ports** to accept each input subband at a separate port (the topmost port accepts the subband with the highest frequency band). Set to **Single port** to accept one vector or matrix of concatenated subbands at a single port. For more information, see “Input Requirements” on page 2-551.

The default setting of this parameter is **Multiple ports** for the Dyadic Synthesis Filter Bank block, and **Single port** for the IDWT block.

## References

Fliege, N. J. *Multirate Digital Signal Processing: Multirate Systems, Filter Banks, Wavelets*. West Sussex, England: John Wiley & Sons, 1994.

Strang, G. and T. Nguyen. *Wavelets and Filter Banks*. Wellesley, MA: Wellesley-Cambridge Press, 1996.

Vaidyanathan, P. P. *Multirate Systems and Filter Banks*. Englewood Cliffs, NJ: Prentice Hall, 1993.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

## See Also

Dyadic Analysis Filter Bank	DSP System Toolbox
IDWT	DSP System Toolbox
Two-Channel Synthesis Subband Filter	DSP System Toolbox


See “Multirate and Multistage Filters” for related information.

# Edge Detector

**Purpose** Detect transition from zero to nonzero value

**Library** Signal Management / Switches and Counters  
dspswit3

## Description




The Edge Detector block generates an impulse (the value 1) in a given output channel when the corresponding channel of the input transitions from zero to a nonzero value. When the input does not transition from zero to a nonzero value, the block generates a zero in the corresponding output channel.

The output has the same dimension and sample rate as the input. When you set the **Input processing** parameter to **Columns as channels (frame based)**, the block counts an edge that is split across two consecutive frames in the frame that contains the nonzero value. For example, if there is a zero at the bottom of the first frame and a nonzero value at the top of the second frame, the block counts the edge in the second frame.


## Examples

In the `ex_edgedetector_ref` model, the **Input processing** parameter of the Edge Detector block is set to **Columns as channels (frame based)**. Thus, the block interprets the 3-by-2 input as a multichannel signal with a frame size of 3. The Matrix Concatenate block concatenates the two input channels of the original signal with the two output channels of the Edge Detector block to create the four-channel workspace variable `sp_examples_yout`.




As shown in the following figure, the block finds edges at sample 7 in channel 1, and at samples 2, 5, and 9 in channel 2.

# Edge Detector



# Edge Detector

## Dialog Box



### Input processing

Specify how the block should process the input. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The Inherited (this choice will be removed - see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Supported Data Types

- Double-precision floating point
- Single-precision floating point
- Fixed point (signed and unsigned)

- Boolean — The block might output Boolean values depending on the input data type, and whether Boolean support is enabled or disabled.
- 8-, 16-, and 32-bit signed integers
- 8-, 16-, and 32-bit unsigned integers
- Enumerated

## See Also

Counter	DSP System Toolbox
Event-Count Comparator	DSP System Toolbox

# Event-Count Comparator

**Purpose** Detect threshold crossing of accumulated nonzero inputs

**Library** Signal Management / Switches and Counters  
dspswit3

## Description




The Event-Count Comparator block records the number of nonzero inputs to the Data port during the period that the block is enabled by a high signal (the value 1) at the Int port. Both inputs must be scalars.

When the number of accumulated nonzero inputs first equals the **Event threshold** setting, the block waits one additional sample interval, and then sets the output high (1). The block holds the output high until recording is restarted by a low-to-high (0-to-1) transition at the Int port.

The Event-Count Comparator block accepts real and complex floating-point and fixed-point inputs. However, because the block has discrete state, it does not support constant or continuous sample times. Therefore, at least one input or output port of the Event-Count Comparator block must be connected to a block whose **Sample time** parameter is discrete. The Event-Count Comparator block inherits this non-infinite discrete sample time.


## Examples

In the `ex_eventcountcomp_ref` model, the Event-Count Comparator block (**Event threshold** = 3) detects two threshold crossings in the input to the Data port, one at sample 4 and one at sample 12.




# Event-Count Comparator

All inputs and outputs are multiplexed into the workspace variable `yout`, whose contents are shown in the figure below. The two left columns in the illustration show the inputs to the Data and Int ports, the center column shows the state of the block's internal counter, and the right column shows the block's output.



# Event-Count Comparator



## Dialog Box

### Event threshold

Specify the value against which to compare the number of nonzero inputs. Tunable.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point
- Fixed point (signed and unsigned)
- Boolean
- 8-, 16-, and 32-bit signed integers
- 8-, 16-, and 32-bit unsigned integers
- Enumerated

## See Also

Counter

DSP System Toolbox

Edge Detector

DSP System Toolbox

# Extract Diagonal


## Purpose

Extract main diagonal of input matrix

## Library

Math Functions / Matrices and Linear Algebra / Matrix Operations  
dspmtrx3

## Description




The Extract Diagonal block populates the unoriented output vector with the elements on the main diagonal of the  $M$ -by- $N$  input matrix  $A$ .

$D = \text{diag}(A)$       Equivalent MATLAB code

The output vector has length  $\min(M, N)$ .

## Dialog Box



## Supported Data Types

- Double-precision floating point
- Single-precision floating point
- Fixed point (signed and unsigned)
- Boolean — Block outputs are always Boolean.
- 8-, 16-, and 32-bit signed integers
- 8-, 16-, and 32-bit unsigned integers

## See Also

Constant Diagonal Matrix	DSP System Toolbox
Create Diagonal Matrix	DSP System Toolbox

Extract Triangular Matrix

`diag`

DSP System Toolbox

MATLAB

# Extract Triangular Matrix

---

## Purpose


Extract lower or upper triangle from input matrices

## Library

Math Functions / Matrices and Linear Algebra / Matrix Operations


dspmtrx3

## Description



The Extract Triangular Matrix block creates a triangular matrix output from the upper or lower triangular elements of an  $M$ -by- $N$  input matrix. The block treats length- $M$  unoriented vector inputs as an  $M$ -by-1 matrix.

The **Extract** parameter selects between the two components of the input:





- **Upper** — Copies the elements on and above the main diagonal of the input matrix to an output matrix of the same size. The first *row* of the output matrix is therefore identical to the first *row* of the input matrix. The elements below the main diagonal of the output matrix are zero.
- **Lower** — Copies the elements on and below the main diagonal of the input matrix to an output matrix of the same size. The first *column* of the output matrix is therefore identical to the first *column* of the input matrix. The elements above the main diagonal of the output matrix are zero.

## Examples

The `ex_extracttriang_ref` model below shows the extraction of upper and lower triangles from a 5-by-3 input matrix.

# Extract Triangular Matrix



## Dialog Box

### Extract

The component of the matrix to copy to the output: upper triangle or lower triangle.

# Extract Triangular Matrix

---

## Supported Data Types

Port	Supported Data Types
A	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
U	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
L	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

## See Also

Autocorrelation LPC	DSP System Toolbox
Cholesky Factorization	DSP System Toolbox
Constant Diagonal Matrix	DSP System Toolbox
Extract Diagonal	DSP System Toolbox

Forward Substitution

DSP System Toolbox

LDL Factorization

DSP System Toolbox

LU Factorization

DSP System Toolbox

`tril`

MATLAB

`triu`


MATLAB

# Fast Block LMS Filter

**Purpose** Compute output, error, and weights using LMS adaptive algorithm

**Library** Filtering / Adaptive Filters  
dspadpt3

## Description



The Fast Block LMS Filter block implements an adaptive least mean-square (LMS) filter, where the adaptation of the filter weights occurs once for every block of data samples. The block estimates the filter weights, or coefficients, needed to convert the input signal into the desired signal. Connect the signal you want to filter to the Input port. The input signal can be a scalar or a column vector. Connect the signal you want to model to the Desired port. The desired signal must have the same data type, complexity, and dimensions as the input signal. The Output port outputs the filtered input signal. The Error port outputs the result of subtracting the output signal from the desired signal.

The block calculates the filter weights using the Block LMS Filter equations. For more information, see Block LMS Filter. The Fast Block LMS Filter block implements the convolution operation involved in the calculations of the filtered output,  $y$ , and the weight update function in the frequency domain using the FFT algorithm used in the Overlap-Save FFT Filter block. See Overlap-Save FFT Filter for more information.

Use the **Filter length** parameter to specify the length of the filter weights vector.

The **Block size** parameter determines how many samples of the input signal are acquired before the filter weights are updated. The input frame length must be a multiple of the **Block size** parameter.

The **Step-size ( $\mu$ )** parameter corresponds to  $\mu$  in the equations. You can either specify a step-size using the input port, Step-size, or enter a value in the Block Parameters: Block LMS Filter dialog box.

Use the **Leakage factor (0 to 1)** parameter to specify the leakage factor,  $0 < 1 - \mu\alpha \leq 1$ , in the leaky LMS algorithm shown below.

$$\mathbf{w}(k) = (1 - \mu\alpha)\mathbf{w}(k-1) - f(\mathbf{u}(n), e(n), \mu)$$

Enter the initial filter weights,  $\mathbf{w}(0)$ , as a vector or a scalar in the **Initial value of filter weights** text box. When you enter a scalar, the block uses the scalar value to create a vector of filter weights. This vector has length equal to the filter length and all of its values are equal to the scalar value.


When you select the **Adapt port** check box, an Adapt port appears on the block. When the input to this port is nonzero, the block continuously updates the filter weights. When the input to this port is zero, the filter weights remain at their current values.

When you want to reset the value of the filter weights to their initial values, use the **Reset input** parameter. The block resets the filter weights whenever a reset event is detected at the Reset port. The reset signal rate must be the same rate as the data signal input.


From the **Reset input** list, select None to disable the Reset port. To enable the Reset port, select one of the following from the **Reset input** list:

- **Rising edge** — Triggers a reset operation when the Reset input does one of the following:
  - Rises from a negative value to a positive value or zero
  - Rises from zero to a positive value, where the rise is not a continuation of a rise from a negative value to zero (see the following figure)

# Fast Block LMS Filter




- Falling edge — Triggers a reset operation when the Reset input does one of the following:
  - Falls from a positive value to a negative value or zero
  - Falls from zero to a negative value, where the fall is not a continuation of a fall from a positive value to zero (see the following figure)



- Either edge — Triggers a reset operation when the Reset input is a Rising edge or Falling edge (as described above)
- Non-zero sample — Triggers a reset operation at each sample time that the Reset input is not zero

Select the **Output filter weights** check box to create a Wts port on the block. For each iteration, the block outputs the current updated filter weights from this port.

# Fast Block LMS Filter



## Dialog Box

### Filter length

Enter the length of the FIR filter weights vector. The sum of the **Block size** and the **Filter length** must be a power of 2.

## Block size

Enter the number of samples to acquire before the filter weights are updated. The number of rows in the input must be an integer multiple of the **Block size**. The sum of the **Block size** and the **Filter length** must be a power of 2.

## Specify step-size via

Select Dialog to enter a value for mu, or select Input port to specify mu using the Step-size input port.

## Step-size (mu)

Enter the step-size. Tunable.

## Leakage factor (0 to 1)

Enter the leakage factor,  $0 < 1 - \mu\alpha \leq 1$ . Tunable.

## Initial value of filter weights

Specify the initial values of the FIR filter weights.

## Adapt port

Select this check box to enable the Adapt input port.

## Reset input

Select this check box to enable the Reset input port.

## Output filter weights

Select this check box to export the filter weights from the Wts port.

## References

Hayes, M.H. *Statistical Digital Signal Processing and Modeling*. New York: John Wiley & Sons, 1996.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Desired	<ul style="list-style-type: none"><li>• Must be the same as Input</li></ul>
Step-size	<ul style="list-style-type: none"><li>• Must be the same as Input</li></ul>

# Fast Block LMS Filter

---

Port	Supported Data Types
Adapt	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Reset	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Same as Input</li></ul>
Error	<ul style="list-style-type: none"><li>• Same as Input</li></ul>
Wts	<ul style="list-style-type: none"><li>• Same as Input</li></ul>

## See Also

Block LMS Filter	DSP System Toolbox
Kalman Adaptive Filter (Obsolete)	DSP System Toolbox
LMS Filter	DSP System Toolbox
RLS Filter	DSP System Toolbox

See “Adaptive Filters in Simulink” for related information.

**Purpose** Fast Fourier transform (FFT) of input

**Library** Transforms  
dspxfm3

**Description**



The FFT block computes the fast Fourier transform (FFT) of each row of a sample-based 1-by- $P$  input vector,  $u$ , or across the first dimension ( $P$ ) of an  $N$ -D input array,  $u$ . For user-specified FFT lengths, not equal to  $P$ , zero padding or modulo-length data wrapping occurs before the FFT operation, as per Orfanidis [1]:

```
y = fft(u,M) % P M
```

```
y(:,l) = fft(datawrap(u(:,l),M)) % P > M; l = 1, ..., N
```

When the input length,  $P$ , is greater than the FFT length,  $M$ , you may see magnitude increases in your FFT output. These magnitude increases occur because the FFT block uses modulo- $M$  data wrapping to preserve all available input samples.

To avoid such magnitude increases, you can truncate the length of your input sample,  $P$ , to the FFT length,  $M$ . To do so, place a Pad block before the FFT block in your model.

The  $k$ th entry of the  $l$ th output channel,  $y(k, l)$ , equals the  $k$ th point of the  $M$ -point discrete Fourier transform (DFT) of the  $l$ th input channel:

$$y(k, l) = \sum_{p=1}^P u(p, l) e^{-j2\pi(p-1)(k-1)/M} \quad k = 1, \dots, M$$

The block uses one of two possible FFT implementations. You can select an implementation based on the FFTW library [3], [4], or an implementation based on a collection of Radix-2 algorithms. You can select Auto to allow the block to choose the implementation.

## **FFTW Implementation**

The FFTW implementation provides an optimized FFT calculation including support for power-of-two and non-power-of-two transform lengths in both simulation and code generation. Generated code using the FFTW implementation will be restricted to those computers which are capable of running MATLAB. The input data type must be floating-point.

## **Radix-2 Implementation**

The Radix-2 implementation supports bit-reversed processing, fixed or floating-point data, and allows the block to provide portable C-code generation using the Simulink Coder. The dimension  $M$  of the  $M$ -by- $N$  input matrix, must be a power of two. To work with other input sizes, use the Pad block to pad or truncate these dimensions to powers of two, or if possible choose the FFTW implementation.

With Radix-2 selected, the block implements one or more of the following algorithms:

- Butterfly operation
- Double-signal algorithm
- Half-length algorithm
- Radix-2 decimation-in-time (DIT) algorithm
- Radix-2 decimation-in-frequency (DIF) algorithm

## **Radix-2 Algorithms for Real and Complex Signals**

Complexity of Input	Output Ordering	Algorithms Used for FFT Computation
Complex	Linear	Bit-reversed operation and radix-2 DIT
Complex	Bit-reversed	Radix-2 DIF
Real	Linear	Bit-reversed operation and radix-2 DIT in conjunction with the half-length and double-signal algorithms
Real	Bit-reversed	Radix-2 DIF in conjunction with the half-length and double-signal algorithms

The efficiency of the FFT algorithm can be enhanced for real input signals by forming complex-valued sequences from the real-valued sequences prior to the computation of the DFT. When there are  $2N+1$  real input channels, the FFT block forms these complex-valued sequences by applying the double-signal algorithm to the first  $2N$  input channels, and the half-length algorithm to the last odd-numbered channel.

For real input signals with fixed-point data types, it is possible to see different numerical results in the output of the last odd numbered channel, even when all input channels are identical. This numerical difference results from differences in the double-signal algorithm and the half-length algorithm.

You can eliminate this numerical difference in two ways:

- Using full precision arithmetic for fixed-point input signals
- Changing the input data type to floating point

For more information on the double-signal and half-length algorithms, see Proakis [2]. “Efficient Computation of the DFT of Two Real Sequences” on page 475 describes the double signal algorithm. “Efficient Computation of the DFT of a  $2N$ -Point Real Sequence” on page 476 describes the half-length algorithm.

## Radix-2 Optimization for the Table of Trigonometric Values

In certain situations, the block's Radix-2 algorithm computes all the possible trigonometric values of the twiddle factor

$$e^{j\frac{2\pi k}{K}}$$

where  $K$  is the greater value of either  $M$  or  $N$  and  $k = 0, \dots, K - 1$ . The block stores these values in a table and retrieves them during simulation. The number of table entries for fixed-point and floating-point is summarized in the following table:


Number of Table Entries for N-Point FFT	
floating-point	$3 N/4$
fixed-point	$N$

## Fixed-Point Data Types


The following diagrams show the data types used in the FFT block for fixed-point signals. You can set the sine table, accumulator, product output, and output data types displayed in the diagrams in the FFT dialog box as discussed in "Dialog Box" on page 2-589.

Inputs to the FFT block are first cast to the output data type and stored in the output buffer. Each butterfly stage then processes signals in the accumulator data type, with the final output of the butterfly being cast back into the output data type. The block multiplies in a twiddle factor before each butterfly stage in a decimation-in-time FFT and after each butterfly stage in a decimation-in-frequency FFT.


**Decimation-in-time IFFT**



**Decimation-in-frequency IFFT**



**Butterfly stage data types**



**Twiddle multiplication data types**



The output of the multiplier appears in the accumulator data type because both of the inputs to the multiplier are complex. For details on the complex multiplication performed, see “Multiplication Data Types”.


---

**Note** When the block input is fixed point, all internal data types are signed fixed point.

---

## Dialog Box

The **Main** pane of the FFT block dialog appears as follows.



## FFT implementation

Set this parameter to FFTW [3], [4] to support an arbitrary length input signal. The block restricts generated code with FFTW implementation to host computers capable of running MATLAB.

Set this parameter to Radix-2 for bit-reversed processing, fixed or floating-point data, or for portable C-code generation using the Simulink Coder. The dimension  $M$  of the  $M$ -by- $N$  input matrix, must be a power of two. To work with other input sizes, use the Pad block to pad or truncate these dimensions to powers of two, or if possible choose the FFTW implementation. See “Radix-2 Implementation” on page 2-584.

Set this parameter to Auto to let the block choose the FFT implementation. For non-power-of-two transform lengths, the block restricts generated code to MATLAB host computers.

## Output in bit-reversed order

Designate the order of the output channel elements relative to the ordering of the input elements. When you select this check box, the output channel elements appear in bit-reversed order relative to the input ordering. If you clear this check box, the output channel elements appear in linear order relative to the input ordering.

Linearly ordering the output requires extra data sorting manipulation, so in some situations it might be better to output in bit-reversed order.

---

**Note** The FFT block calculates its output in bit-reversed order. Linearly ordering the FFT block output requires an extra bit-reversal operation. Thus, in many situations, you can increase the speed of the FFT block by selecting the **Output in bit-reversed order** check box.

---

---

For more information ordering of the output, see “Linear and Bit-Reversed Output Order”.

**Scale result by FFT length**

When you select this parameter, the block divides the output of the FFT by the FFT length. This option is useful when you want the output of the FFT to stay in the same amplitude range as its input. This is particularly useful when working with fixed-point data types.

**Inherit FFT length from input dimensions**


Select to inherit the FFT length from the input dimensions. When you select this check box, the input length must be a power of two. When you do not select this check box, the **FFT length** parameter becomes available to specify the length.

**FFT length**

Specify FFT length. This parameter becomes available only when you do not select the **Inherit FFT length from input dimensions** parameter.

When you set the **FFT implementation** parameter to Radix-2, or when you check the **Output in bit-reversed order** check box, this value must be a power of two.

The **Data Types** pane of the FFT block dialog appears as follows.



**Rounding mode**

Select the rounding mode for fixed-point operations. The sine table values do not obey this parameter; instead, they always round to Nearest.

**Overflow mode**


Select the overflow mode for fixed-point operations. The sine table values do not obey this parameter; instead, they are always saturated.

**Sine table data type**

Choose how you specify the word length of the values of the sine table. The fraction length of the sine table values always equals the word length minus one. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Same word length as input`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16)`

The sine table values do not obey the **Rounding mode** and **Overflow mode** parameters; instead, they are always saturated and rounded to Nearest.


Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Sine table data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

**Product output data type**

Specify the product output data type. See Fixed-Point Data Types on page 586 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`


Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

### Accumulator data type

Specify the accumulator data type. See Fixed-Point Data Types on page 586 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

### Output data type

Specify the output data type. See Fixed-Point Data Types on page 586 for illustrations depicting the use of the output data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`.

When you select **Inherit: Inherit via internal rule**, the block calculates the output word length and fraction length automatically. The equations that the block uses to calculate the ideal output word length and fraction length depend on the setting of the **Divide butterfly outputs by two** check box.

- When you select the **Divide butterfly outputs by two** check box, the ideal output word and fraction lengths are the same as the input word and fraction lengths.
- When you clear the **Divide butterfly outputs by two** check box, the block computes the ideal output word and fraction lengths according to the following equations:

$$WL_{ideal\ output} = WL_{input} + \text{floor}(\log_2(\text{FFT length} - 1)) + 1$$

$$FL_{ideal\ output} = FL_{input}$$

Using these ideal results, the internal rule then selects word lengths and fraction lengths that are appropriate for your hardware. For more information, see “Inherit via Internal Rule”.

- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

### **Lock data type settings against changes by the fixed-point tools**

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## Examples

See the section on “Transform Time-Domain Data into Frequency Domain” in the *DSP System Toolbox User’s Guide*.

## References

[1] Orfanidis, S. J. *Introduction to Signal Processing*. Upper Saddle River, NJ: Prentice Hall, 1996, p. 497.

[2] Proakis, John G. and Dimitris G. Manolakis. *Digital Signal Processing*, 3rd ed. Upper Saddle River, NJ: Prentice Hall, 1996.

[3] FFTW (<http://www.fftw.org>)

[4] Frigo, M. and S. G. Johnson, “FFTW: An Adaptive Software Architecture for the FFT,” *Proceedings of the International Conference on Acoustics, Speech, and Signal Processing*, Vol. 3, 1998, pp. 1381-1384.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>

## See Also

DCT	DSP System Toolbox
IFFT	DSP System Toolbox
Pad	DSP System Toolbox

<code>fft</code>	MATLAB
<code>ifft</code>	MATLAB
<code>bitrevorder</code>	Signal Processing Toolbox
Simulink Coder	Simulink Coder

# Filter Realization Wizard

---


## Purpose

Construct filter realizations using Digital Filter block or Sum, Gain, and Delay blocks

## Library

Filtering / Filter Implementations  
dsparch4

## Description



---

**Note** Use this block to implement fixed-point or floating-point digital filters using Sum, Gain, and Delay blocks or the Digital Filter block. You can either design a filter by using the block parameters, or import the coefficients of a filter you have designed elsewhere.

The following blocks also implement digital filters, but serve slightly different purposes:



- Digital Filter — Use to implement floating-point or fixed-point filters that you have already designed
- Digital Filter Design — Use to design, analyze, and then implement floating-point filters.

---

The Filter Realization Wizard is a tool for automatically implementing a digital filter. You must specify a filter, its structure, and the data types for the inputs, outputs, and computations. The filter can support double-precision, single-precision, or fixed-point data types.

The Filter Realization Wizard can implement a digital filter in one of two ways. It can use a Digital Filter block, or it can create a subsystem block that implements the specified filter using Sum, Gain, and Delay blocks. If the Filter Realization Wizard creates a Digital Filter block, double-click the block to open the dialog box. If it creates a subsystem, double-click the subsystem block to see the filter implementation as shown in the figure below.

# Filter Realization Wizard



For more information about filter implementation, see “Specify the Filter Implementation” on page 2-601.

The parameters of the Filter Realization Wizard are a part of a larger GUI, the Filter Design and Analysis Tool (`fdatool`). You can use `FDATool` to design and analyze your filter, and then use the Filter Realization Wizard parameters to implement the filter in your models.

## Specify the Filter and Data Types

To specify a purely double-precision filter, you can either design a filter using the **Design Filter** panel, or import a filter using the **Import Filter** panel. (You can import `dfilt` filter objects as well as vectors of filter coefficients designed using Signal Processing Toolbox and DSP System Toolbox functions.)

You can also specify a fixed-point filter or a single-precision filter by using the **Set Quantization Parameters** panel.

# Filter Realization Wizard

---

---

**Note** *Running* a model containing implementations of fixed-point filters requires the Simulink Fixed Point product, but you can still edit models containing such filter implementations without it. See the Simulink Fixed Point documentation for more information.

---

See the following topics to learn how to use the panels to specify your filter:

- For more information on the **Design Filter** panel, see “FDATool” in the Signal Processing Toolbox documentation.
- For more information on the **Import Filter** panel, see in the Signal Processing Toolbox documentation.
- For more information on the **Set Quantization Parameters** panel, see “Access the Quantization Features of FDATool”.

To open a panel, click the appropriate button in the lower-left corner of FDATool.

## Supported Filter Structures

The Filter Realization Wizard supports the following structures:

- Direct form I
- Direct form I, second-order sections
- Direct form I transposed
- Direct form I transposed, second-order sections
- Direct form II
- Direct form II, second-order sections
- Direct form II transposed
- Direct form II transposed, second-order sections
- Direct form FIR

- Direct form FIR transposed
- Direct form symmetric FIR
- Direct form antisymmetric FIR
- Lattice all-pass
- Lattice AR
- Lattice ARMA
- Lattice MA for maximum phase
- Lattice MA for minimum phase
- Cascade
- Parallel


## Specify the Filter Implementation

You can determine how the Filter Realization Wizard models the specified filter using the **Build model using basic elements** check box. When you select this check box, the Filter Realization Wizard creates a subsystem block that implements your filter using Sum, Gain, and Delay blocks. When you clear this check box, the Filter Realization Wizard uses a Digital Filter block to implement your filter. The **Build model using basic elements** check box is available only when your filter can be implemented using a Digital Filter block.


The Filter Realization Wizard can generate a subsystem that represents either a double-precision or fixed-point filter. You must install the Simulink Fixed Point product to simulate a fixed-point filter. You can still edit the blocks used to implement the filter without installing the Simulink Fixed Point product.

# Filter Realization Wizard

Double-precision filter implemented with Sum, Gain, and Delay blocks



Fixed-point filter implemented with Sum, Gain, Delay, and Conversion blocks



## Implementations of Double-Precision and Fixed-Point Filters

### Command Line Alternative

The `dfilt` (digital filter) object has a method, `realizemd1`, that allows you to access the capabilities of the Filter Realization Wizard from the command line.

For more information about the `realizemd1` method, see the following sections:

- The topic on “Methods” in the `dfilt` reference page.
- The `realizemd1` reference page.

## Dialog Box

---

**Note** The following parameters for the Filter Realization Wizard are in the **Realize Model** pane of the Filter Design and Analysis Tool (FDATool) GUI. To open different panels of FDATool, click the different buttons at the lower-left corner. For more information about relevant panels, see “Specify the Filter and Data Types” on page 2-599.

---

# Filter Realization Wizard

The screenshot displays the 'Filter Design & Analysis Tool' window. The title bar reads 'Filter Design & Analysis Tool - [fwizdef.mat]'. The menu bar includes 'File', 'Edit', 'Analysis', 'Targets', 'View', 'Window', and 'Help'. A toolbar with various icons is located below the menu bar.

The main interface is divided into several sections:

- Current Filter Information:** A panel on the left containing the following details:
  - Structure: Direct-Form II, Second-Order Sections
  - Order: 8
  - Sections: 4
  - Stable: Yes
  - Source: DesignedButtons for 'Store Filter ...' and 'Filter Manager ...' are located at the bottom of this panel.
- Magnitude Response (dB):** A plot on the right showing the filter's magnitude response. The y-axis is labeled 'Magnitude (dB)' and ranges from 0 to -150. The x-axis is labeled 'Frequency (kHz)' and ranges from 0 to 10. The plot shows a flat line at 0 dB until approximately 10 kHz, after which it begins to roll off.
- Model:** A section at the bottom left with the following fields:
  - Block name: Filter
  - Destination: Current
  - User Defined: Untitled
  - Overwrite generated 'Filter' block:
  - Build model using basic elements:
  - Input processing: Columns as channels (frame based)
- Optimization:** A section on the bottom right with the following options:
  - Optimize for zero gain:
  - Optimize for unity gain:
  - Optimize for negative gain:
  - Optimize delay chain:
  - Optimize for unity gain:

A status bar at the bottom of the window displays the message: 'Loading session file ... done.'

**Block Name**

Enter the name of the new filter block.

**Destination**

Specify where the new filter block should be created. This can be in a new model or in the current (most recently selected) model.

**User Defined**

Specify the name of the target subsystem in which the Filter Realization Wizard should create the new filter block.

**Overwrite generated block “Filter” block**

When selected, the block overwrites any filter block in the current model with the name specified in the **Block Name** parameter. This parameter is enabled when the **Destination** parameter is set to Current.

**Build model using basic elements**

Select this check box to implement your filter using Sum, Gain, and Delay blocks. Clear this check box to implement your filter using the Digital Filter block. This parameter is available only when your filter can be modeled using the Digital Filter block.

**Optimize for zero gains**

Select this check box to remove zero-gain paths from the filter structure. For an example, see “Optimize the Filter Structure”.

**Optimize for unity gains**

Select this check box to substitute gains equal to 1 with a wire (short circuit). For an example, see “Optimize the Filter Structure”.

**Optimize for negative gains**

Select this check box to substitute gains equal to -1 with a wire (short circuit), and change the corresponding sums to subtractions. For an example, see “Optimize the Filter Structure”.

**Optimize delay chains**

Select this check box to substitute any delay chains made up of  $n$  unit delays with a single delay by  $n$ . For an example, see “Optimize the Filter Structure”.

# Filter Realization Wizard

---

## Optimize for unity scale values

Select this check box to remove all scale value multiplications by 1 from the filter structure.

## Input processing

Specify how the generated filter block or subsystem block processes the input. Depending on the type of filter you are designing, one or both of the following options may be available:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

For more information about sample- and frame-based processing, see “Sample- and Frame-Based Concepts”.

## Rate options

For multirate filters, specify how the block should process the input. You can set this parameter to one of the following options:

- **Enforce single-rate processing** — When you select this option, the block maintains the input sample rate.
- **Allow multirate processing** — When you select this option, the block adjusts the rate at the output to accommodate an increased or reduced number of samples.

## Realize Model

Click to create a filter block according to the settings you've specified. When the **Build model using basic elements** check box is selected, the filter is implemented as a subsystem block consisting of Sum, Gain, and Delay blocks. To see the filter implementation, double-click the subsystem block in your model.

---

**Note** For more information about relevant parameters in other panels of FDATool, see “Specify the Filter and Data Types” on page 2-599.

---

## References

- Oppenheim, A. V. and R. W. Schaffer. *Discrete-Time Signal Processing*. Englewood Cliffs, NJ: Prentice Hall, 1989.
- Proakis, J. and D. Manolakis. *Digital Signal Processing*. 3rd ed. Englewood Cliffs, NJ: Prentice-Hall, 1996.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point — Supported only when you install Simulink Fixed Point.
- Fixed point (signed and unsigned) — Supported only when you install Simulink Fixed Point and Fixed-Point Toolbox™.

## See Also

Digital Filter	DSP System Toolbox
Digital Filter Design	DSP System Toolbox
filter	DSP System Toolbox
realizemdl	DSP System Toolbox
dfilt	DSP System Toolbox

- “Filter Design”
- “Filter Analysis”
- “Select a Filter Design Block”


# FIR Decimation

---

**Purpose** Filter and downsample input signals

**Library** Filtering / Multirate Filters  
dspmlti4

## Description



The FIR Decimation block resamples the discrete-time input at a rate  $K$  times slower than the input sample rate, where  $K$  is the integer value you specify for the **Decimation factor** parameter. To do so, the block implements a polyphase filter structure and performs the following operations:

- 1 Filters the data in each channel of the input using a direct-form FIR filter.
- 2 Downsamples each channel of filtered data by discarding  $K-1$  consecutive samples following each sample that is retained.

The block uses a polyphase filter implementation because it is more efficient than straightforward filter-then-decimate algorithms. See Fliege [1] for more information.

You can use the FIR Decimation block inside triggered subsystems when you set the **Rate options** parameter to Enforce single-rate processing.

## Specifying the Filter Coefficients

The FIR Decimation block can operate in two different modes. Select the mode in the **Coefficient source** group box. If you select:

- **Dialog parameters**, you enter information about the filter such as structure and coefficients in the block dialog box.
- **Multirate filter object (MFILT)**, you specify the filter using an `mfilt` object.

When you select **Dialog parameters**, you use the **FIR filter coefficients** parameter to specify the numerator coefficients of the FIR filter transfer function  $H(z)$ .

$$H(z) = B(z) = b_1 + b_2z^{-1} + \dots + b_mz^{-(m-1)}$$

You can generate the FIR filter coefficient vector,  $[b(1) \ b(2) \ \dots \ b(m)]$ , using one of the Signal Processing Toolbox filter design functions (such as `intfilt`).

The filter you specify should be a lowpass filter with a normalized cutoff frequency no greater than  $1/K$ . The block internally initializes all filter states to zero.

---

**Note** You can use the block method to create your own filter blocks directly from your `mfilt` objects.

---

## Frame-Based Processing

When you set the **Input processing** parameter to `Columns as channels (frame based)`, the block resamples each column of the input over time. In this mode, the block can perform either single-rate or multirate processing. You can use the **Rate options** parameter to specify how the block resamples the input:

- When you set the **Rate options** parameter to `Enforce single-rate processing`, the input and output of the block have the same sample rate. To decimate the output while maintaining the input sample rate, the block resamples the data in each column of the input such that the frame size of the output ( $M_o$ ) is  $1/K$  times that of the input ( $M_o = M_i/K$ ),

In this mode, the input frame size,  $M_i$ , must be a multiple of the **Decimation factor**,  $K$ .

For an example of single-rate FIR Decimation, see “Example 1 — Single-Rate Processing” on page 2-612.

- When you set the **Rate options** parameter to Allow multirate processing, the input and output of the FIR Decimation block are the same size, but the sample rate of the output is  $K$  times slower than that of the input. In this mode, the block treats an  $M_i$ -by- $N$  matrix input as  $N$  independent channels. The block decimates each column of the input over time by keeping the frame size constant ( $M_i=M_o$ ), and making the output frame period ( $T_{fo}$ )  $K$  times longer than the input frame period ( $T_{fo} = K*T_{fi}$ ).

See “Example 2— Multirate Frame-Based Processing” on page 2-612 for an example that uses the FIR Decimation block in this mode.

## Sample-Based Processing

When you set the **Input processing** parameter to Elements as channels (sample based), the block treats an  $M$ -by- $N$  matrix input as  $M*N$  independent channels, and decimates each channel over time. The output sample period ( $T_{so}$ ) is  $K$  times longer than the input sample period ( $T_{so} = K*T_{si}$ ), and the input and output sizes are identical.

## Latency

When you use the FIR Decimation block in sample-based processing mode, the block always has zero-tasking latency. *Zero-tasking latency* means that the block propagates the first filtered input sample (received at time  $t=0$ ) as the first output sample. That first output sample is then followed by filtered input samples  $K+1$ ,  $2K+1$ , and so on.

When you use the FIR Decimation block in frame-based processing mode with a frame size greater than one, the block may exhibit *one-frame latency*. Cases of one-frame latency can occur when the input frame size is greater than one, and you set the **Input processing** and **Rate options** parameters of the FIR Decimation block as follows:

- **Input processing** = Columns as channels (frame based)
- **Rate options** = Allow multirate processing

In cases of one-frame latency, you can define the value of the first  $M_i$  output rows by setting the **Output buffer initial conditions**

parameter. The default value of the **Output buffer initial conditions** parameter is 0. However, you can enter a matrix containing one value for each channel of the input, or a scalar value to be applied to all channels. The first filtered input sample (first filtered row of the input matrix) appears in the output as sample  $M_i + 1$ . That sample is then followed by filtered input samples  $K + 1$ ,  $2K + 1$ , and so on.


---

**Note** For more information on latency and the Simulink tasking modes, see “Excess Algorithmic Delay (Tasking Latency)” in the *DSP System Toolbox User’s Guide* and “Scheduling” in the *Simulink Coder User’s Guide*.

---

## Fixed-Point Data Types

The following diagram shows the data types used within the FIR Decimation block for fixed-point signals.



You can set the coefficient, product output, accumulator, and output data types in the block dialog box as discussed in the “Dialog Box” on page 2-613 section. This diagram shows that data is stored in the input buffer with the same data type and scaling as the input. The block stores filtered data and any initial conditions in the output buffer using the output data type and scaling that you set in the block dialog box.

When at least one of the inputs to the multiplier is real, the output of the multiplier is in the product output data type. When both inputs

# FIR Decimation

to the multiplier are complex, the result of the multiplication is in the accumulator data type. For details on the complex multiplication performed by this block, see “Multiplication Data Types” in the *DSP System Toolbox User’s Guide*.

---


**Note** When the block input is fixed point, all internal data types are signed fixed-point values.

---

## Examples


### Example 1 – Single-Rate Processing

In the `ex_firdecimation_ref2` model, the FIR Decimation block decimates a single-channel input with a frame size of 64. Because the block is doing single-rate processing and the **Decimation factor** parameter is set to 4, the output of the FIR Decimation block has a frame size of 16. As shown in the following figure, the input and output of the FIR Decimation block have the same sample rate.



### Example 2— Multirate Frame-Based Processing

In the `ex_firdecimation_ref1` model, the FIR Decimation block decimates a single-channel input with a frame period of one second. Because the block is doing multirate frame-based processing and the **Decimation factor** parameter is set to 4, the frame period of the output is four seconds. As shown in the following figure, the input and output of the FIR Decimation block have the same frame size, but the sample rate of the output is four times that of the input.



### Example 3

The `ex_polyphasedec` model illustrates the underlying polyphase implementations of the FIR Decimation block. Run the model, and view the results on the scope. The output of the FIR Decimation block matches the output of the Polyphase Decimation Filter block.

### Example 4

The `ex_mrf_nlp` model illustrates the use of the FIR Decimation block in a number of multistage multirate filters.

## Dialog Box

### Coefficient Source

The FIR Decimation block can operate in two different modes. Select the mode in the **Coefficient source** group box. If you select

- **Dialog parameters**, you enter information about the filter such as structure and coefficients in the block mask.
- **Multirate filter object (MFILT)**, you specify the filter using an `mfilt` object.

Different items appear on the FIR Decimation block dialog depending on whether you select **Dialog parameters** or **Multirate filter object (MFILT)** in the **Coefficient source** group box. See the following sections for details:


- “Specify Filter Characteristics in Dialog” on page 2-614
- “Specify Multirate Filter Object” on page 2-622

# FIR Decimation

---

## **Specify Filter Characteristics in Dialog**

The **Main** pane of the FIR Decimation block dialog appears as follows when you select **Dialog parameters** in the **Coefficient source** group box.



# FIR Decimation

---

## **FIR filter coefficients**

Specify the lowpass FIR filter coefficients, in descending powers of  $z$ .

## **Decimation factor**

Specify the integer factor,  $K$ , by which to decrease the sample rate of the input sequence.

## **Filter Structure**

Choose whether to implement a `Direct form` or `Direct form transposed` filter.

## **Input processing**

Specify how the block should process the input. You can set this parameter to one of the following options:

- `Columns as channels (frame based)` — When you select this option, the block treats each column of the input as a separate channel.
- `Elements as channels (sample based)` — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The `Inherited` (this choice will be removed - see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## **Rate options**

Specify the method by which the block should decimate the input. You can select one of the following options:

- `Enforce single-rate processing` — When you select this option, the block maintains the input sample rate and decimates the signal by decreasing the output frame size by a factor of  $K$ . To select this option, you must set the **Input**

**processing** parameter to Columns as channels (frame based).

- Allow multirate processing — When you select this option, the block decimates the signal such that the output sample rate is  $K$  times slower than the input sample rate.

### Output buffer initial conditions

In the case of *one-frame latency*, this parameter specifies the output of the block until the first filtered input sample is available. The default value of this parameter is 0, but you can enter a matrix containing one value for each channel, or a scalar value to be applied to all signal channels. This parameter appears only when you configure the block to perform multirate processing.

See “Latency” on page 2-610 for more information about latency in the FIR Decimation block.

### View filter response

This button opens the Filter Visualization Tool (fvtool) from the Signal Processing Toolbox product and displays the filter response of the filter defined in the block. For more information on FVTool, see the Signal Processing Toolbox documentation.

---

**Note** If you specify a filter in the **Multirate filter variable** parameter, you must apply the filter by clicking the **Apply** button before using the **View filter response** button.

---

The **Data Types** pane of the FIR Decimation block dialog appears as follows when you select **Dialog parameters** in the **Coefficient source** group box.

# FIR Decimation

Function Block Parameters: FIR Decimation

FIR Decimation

Apply an FIR filter to the input signal, then downsample the signal by an integer-valued factor. The block implements the FIR filter using a polyphase filter structure.

Coefficient source

Dialog parameters

Multirate filter object (MFILT)

Main Data Types

Fixed-point operational parameters

Rounding mode:  Overflow mode:

Floating-point inheritance takes precedence over the settings in the 'Data Type' column below. When the block input is floating point, all block data types match the input. When the block input is fixed point, all internal data types are signed fixed point.

	Data Type	Assistant	Minimum	Maximum
Coefficients:	<input type="text" value="Inherit: Same word length as input"/>	<input type="button" value="&gt;&gt;"/>	<input type="text" value="[]"/>	<input type="text" value="[]"/>
Product output:	<input type="text" value="Inherit: Inherit via internal rule"/>	<input type="button" value="&gt;&gt;"/>		
Accumulator:	<input type="text" value="Inherit: Inherit via internal rule"/>	<input type="button" value="&gt;&gt;"/>		
Output:	<input type="text" value="Inherit: Same as accumulator"/>	<input type="button" value="&gt;&gt;"/>	<input type="text" value="[]"/>	<input type="text" value="[]"/>

Lock data type settings against changes by the fixed-point tools

OK Cancel Help

## Rounding mode

Select the rounding mode for fixed-point operations. The filter coefficients do not obey this parameter; they always round to Nearest.

---

**Note** The **Rounding mode** and **Overflow mode** settings have no effect on numerical results when all the following conditions exist:

- **Product output data type** is Inherit: Inherit via internal rule
- **Accumulator data type** is Inherit: Inherit via internal rule
- **Output data type** is Inherit: Same as accumulator

With these data type settings, the block is effectively operating in full precision mode.

---

## Overflow mode

Select the overflow mode for fixed-point operations. The filter coefficients do not obey this parameter; they are always saturated.

## Coefficients data type

Specify the coefficients data type. See “Fixed-Point Data Types” on page 2-611 and “Multiplication Data Types” for illustrations depicting the use of the coefficients data type in this block. You can set it to:

- A rule that inherits a data type, for example, Inherit: Same word length as input
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Coefficients data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Product output data type

Specify the product output data type. See “Fixed-Point Data Types” on page 2-611 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Accumulator data type

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-611 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-611 for illustrations depicting the use of the output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as accumulator`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

## Minimum

Specify the minimum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Maximum

Specify the maximum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)

# FIR Decimation

---


- Automatic scaling of fixed-point data types

## **Lock data type settings against changes by the fixed-point tools**

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## **Specify Multirate Filter Object**

The **Main** pane of the FIR Decimation block dialog appears as follows when you select **Multirate filter object (MFILT)** in the **Coefficient source** group box.



## Multirate filter variable

Specify the multirate filter object (`mfilt`) that you would like the block to implement. You can do this in one of three ways:

- You can fully specify the `mfilt` object in the block mask.
- You can enter the variable name of a `mfilt` object that is defined in any workspace.
- You can enter a variable name for a `mfilt` object that is not yet defined, as shown in the default value.

For more information on creating `mfilt` objects, see the `mfilt` function reference page.

## Input processing

Specify how the block should process the input. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The `Inherited` (this choice will be removed - see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Rate options

Specify the method by which the block should decimate the input. You can select one of the following options:

- **Enforce single-rate processing** — When you select this option, the block maintains the input sample rate, and

decimates the signal by decreasing the input frame size by a factor of  $K$ . To select this option, you must set the **Input processing** parameter to Columns as channels (frame based).

- Allow multirate processing — When you select this option, the block decimates the sample rate such that the output sample rate is  $K$  times slower than the input sample rate.

### View filter response

This button opens the Filter Visualization Tool (fvtool) from the Signal Processing Toolbox product and displays the filter response of the `mfilt` object specified in the **Multirate filter variable** parameter. For more information on FVTool, see the Signal Processing Toolbox documentation.

---

**Note** If you specify a filter in the **Multirate filter variable** parameter, you must apply the filter by clicking the **Apply** button before using the **View filter response** button.

---

The **Data Types** pane of the FIR Decimation block dialog appears as follows when you select **Multirate filter object (MFILT)** in the **Coefficient source** group box.

# FIR Decimation

Function Block Parameters: FIR Decimation

**FIR Decimation**

Apply an FIR filter to the input signal, then downsample the signal by an integer-valued factor. The block implements the FIR filter using a polyphase filter structure.

**Coefficient source**

Dialog parameters

Multirate filter object (MFILT)

**Main** | **Data Types**

Floating-point inheritance takes precedence over the settings in the 'Data Type' column below. When the block input is floating point, all block data types match the input. When the block input is fixed point, all internal data types are fixed point.

**Fixed-point operational parameters**

Rounding mode: Floor      Overflow mode: Wrap

**Fixed-point data types**

	Data Type
Coefficients	Same word length as input
Product output	Same as input
Accumulator	Same as product output
Output	Same as accumulator

?      OK      Cancel      Help

The fixed-point settings of the filter object specified on the **Main** pane are displayed on the **Data Types** pane. You cannot change these settings directly on the block mask. To change the fixed-point settings you must edit the filter object directly.

For more information on multirate filter objects, see the `mfilt` function reference page.

## References

[1] Fliege, N. J. *Multirate Digital Signal Processing: Multirate Systems, Filter Banks, Wavelets*. West Sussex, England: John Wiley & Sons, 1994.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>
Output	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>

## See Also

Downsample	DSP System Toolbox
FIR Interpolation	DSP System Toolbox
FIR Rate Conversion	DSP System Toolbox
<code>decimate</code>	Signal Processing Toolbox

# FIR Decimation

---

<code>fir1</code>	Signal Processing Toolbox
<code>fir2</code>	Signal Processing Toolbox
<code>fir1s</code>	Signal Processing Toolbox

**Purpose** Model FIR filters

**Library** Filtering / Filter Implementations  
dsparch4

**Description** This block is the same as the Simulink Discrete FIR Filter block. For more information, see the Discrete FIR Filter reference page in the Simulink documentation.


# FIR Interpolation

---

**Purpose** Upsample and filter input signals

**Library** Filtering / Multirate Filters  
dspmlti4

## Description



The FIR Interpolation block resamples the discrete-time input at a rate  $L$  times faster than the input sample rate, where  $L$  is the integer value you specify for the **Interpolation factor** parameter. To do so, the block implements a polyphase filter structure and performs the following operations:

- Upsamples each channel of the input to a higher rate by inserting  $L-1$  zeros between samples.
- Filters each channel of the upsampled data using a direct-form FIR filter.

The block uses a polyphase filter implementation because it is more efficient than straightforward upsample-then-filter algorithms. See Fliege [1] for more information.

You can use the FIR Interpolation block inside triggered subsystems when you set the **Rate options** parameter to `Enforce single-rate processing`.

## Specifying the Filter Coefficients

The FIR Interpolation block can operate in two different modes. Select the mode in the **Coefficient source** group box. If you select:

- **Dialog parameters**, you enter information about the filter such as structure and coefficients in the block dialog box.
- **Multirate filter object (MFILT)**, you specify the filter using an `mfilt` object.

When you select **Dialog parameters**, you use the **FIR filter coefficients** parameter to specify the numerator coefficients of the FIR filter transfer function  $H(z)$ .

$$H(z) = B(z) = b_1 + b_2z^{-1} + \dots + b_mz^{-(m-1)}$$

You can generate the FIR filter coefficient vector, [b(1) b(2) ... b(m)], using one of the Signal Processing Toolbox filter design functions (such as `intfilt`).

The filter you specify should be a lowpass filter with a length greater than the interpolation factor ( $m > L$ ) and a normalized cutoff frequency no greater than  $1/L$ . The block internally initializes all filter states to zero.

---

**Note** You can use the block method to create your own filter blocks directly from your `mfilt` objects.

---

## Frame-Based Processing

When you set the **Input processing** parameter to `Columns as channels (frame based)`, the block resamples each column of the input over time. In this mode, the block can perform either single-rate or multirate processing. You can use the **Rate options** parameter to specify how the block resamples the input:

- When you set the **Rate options** parameter to `Enforce single-rate processing`, the input and output of the block have the same sample rate. To interpolate the output while maintaining the input sample rate, the block resamples the data in each column of the input such that the frame size of the output ( $M_o$ ) is  $L$  times larger than that of the input ( $M_o = M_i * L$ ).

For an example of single-rate FIR Interpolation, see “Example 1 — Single-Rate Processing” on page 2-634.

- When you set the **Rate options** parameter to `Allow multirate processing`, the input and output of the FIR Interpolation block are the same size. However, the sample rate of the output is  $L$  times faster than that of the input. In this mode, the block treats an  $M_i$ -by- $N$  matrix input as  $N$  independent channels. The block

# FIR Interpolation

---

interpolates each column of the input over time by keeping the frame size constant ( $M_i=M_o$ ), while making the output frame period ( $T_{fo}$ )  $L$  times shorter than the input frame period ( $T_{fo} = T_{fi}/L$ ).

See “Example 2 — Multirate Frame-Based Processing” on page 2-635 for an example that uses the FIR Interpolation block in this mode.

## Sample-Based Processing

When you set the **Input processing** parameter to **Elements as channels (sample based)**, the block treats an  $M$ -by- $N$  matrix input as  $M*N$  independent channels, and interpolates each channel over time. The output sample period ( $T_{so}$ ) is  $L$  times shorter than the input sample period ( $T_{so} = T_{si}/L$ ), while the input and output sizes remain identical.

## Latency

When you run your models in Simulink **SingleTasking** mode or set the **Input processing** parameter to **Columns as channels (frame based)** and the **Rate options** parameter to **Enforce single-rate processing**, the FIR Interpolation block always has zero-tasking latency. *Zero-tasking latency* means that the block propagates the first filtered input sample (received at time  $t=0$ ) as the first output sample. That first output sample is then followed by  $L-1$  interpolated values, the second filtered input sample, and so on.

The only time the FIR Interpolation block exhibits latency is when you set the **Rate options** parameter set to **Allow multirate processing** and run your models in Simulink **MultiTasking** mode. The amount of latency for multirate, multitasking operation depends on the setting of the **Input processing** parameter, as shown in the following table.

<b>Input processing</b>	<b>Latency</b>
Elements as channels (sample based)	$L$ samples
Columns as channels (frame based)	$L$ frames ( $M_i$ samples per frame)

When the block exhibits latency, the default initial condition is zero. Alternatively, you can use the **Output buffer initial conditions** parameter to specify a matrix of initial conditions containing one value for each channel or a scalar initial condition to be applied to all channels. The block scales the **Output buffer initial conditions** by the **Interpolation factor** and outputs the scaled initial conditions until the first filtered input sample becomes available.

When the block is in sample-based processing mode, the block outputs the scaled initial conditions at the start of each channel, followed immediately by the first filtered input sample, then  $L-1$  interpolated values, and so on.

When the block is in frame-based processing mode and using the default initial condition of zero, the first  $M_i * L$  output rows contain zeros, where  $M_i$  is the input frame size. The first filtered input sample (first filtered row of the input matrix) appears in the output as sample  $M_i * L + 1$ . That value is then followed by  $L-1$  interpolated values, the second filtered input sample, and so on.

---


**Note** For more information on latency and the Simulink tasking modes, see “Excess Algorithmic Delay (Tasking Latency)” in the *DSP System Toolbox User’s Guide* and “Scheduling” in the *Simulink Coder User’s Guide*.

---

## Fixed-Point Data Types

The following diagram shows the data types used within the FIR Interpolation block for fixed-point signals.

# FIR Interpolation



You can set the coefficient, product output, accumulator, and output data types in the block dialog as discussed in “Dialog Box” on page 2-636 section. This diagram shows that input data is stored in the input buffer with the same data type and scaling as the input. The block stores filtered data and any initial conditions in the output buffer using the output data type and scaling that you set in the block dialog box.

When at least one of the inputs to the multiplier is real, the output of the multiplier is in the product output data type. When both inputs to the multiplier are complex, the result of the multiplication is in the accumulator data type. For details on the complex multiplication performed by this block, see “Multiplication Data Types” in the *DSP System Toolbox User’s Guide*.

---


**Note** When the block input is fixed point, all internal data types are signed fixed point.

---

## Examples


### Example 1 – Single-Rate Processing

In the `ex_firinterpolation_ref2`, the FIR Interpolation block interpolates a single-channel input with a frame size of 16. Because the block is doing single-rate processing and the **Interpolation factor** parameter is set to 4, the output of the FIR Interpolation block has a frame size of 64. As shown in the following figure, the input and output of the FIR Interpolation block have the same sample rate.



## Example 2 – Multirate Frame-Based Processing

In the `ex_firinterpolation_ref1`, the FIR Interpolation block interpolates a single-channel input with a frame period of 1 second (**Sample time** = 1/64 and **Samples per frame** = 64). Because the block is doing multirate frame-based processing and the **Interpolation factor** parameter is set to 4, the output of the FIR Interpolation block has a frame period of 0.25 seconds. As shown in the following figure, the input and output of the FIR Interpolation block have the same frame size, but the sample rate of the output is 1/4 times that of the input.



## Example 3

The `ex_polyphaseinterp` model illustrates the underlying polyphase implementations of the FIR Interpolation block. Run the model, and view the results on the scope. The output of the FIR Interpolation block matches the output of the Polyphase Interpolation Filter block.

## Example 4

The `ex_mrf_nlp` model illustrates the use of the FIR Interpolation block in a number of multistage multirate filters.

# FIR Interpolation

---

## Dialog Box

### Coefficient Source

The FIR Interpolation block can operate in two different modes. Select the mode in the **Coefficient source** group box. If you select


- **Dialog parameters**, you enter information about the filter such as structure and coefficients in the block mask.
- **Multirate filter object (MFILT)**, you specify the filter using an `mfilt` object.

Different items appear on the FIR Interpolation block dialog depending on whether you select **Dialog parameters** or **Multirate filter object (MFILT)** in the **Coefficient source** group box. See the following sections for details:

- “Specify Filter Characteristics in Dialog” on page 2-636
- “Specify Multirate Filter Object” on page 2-645

### Specify Filter Characteristics in Dialog

The **Main** pane of the FIR Interpolation block dialog appears as follows when you select **Dialog parameters** in the **Coefficient source** group box.



# FIR Interpolation

---

## **FIR filter coefficients**

Specify the FIR filter coefficients, in descending powers of  $z$ .

## **Interpolation factor**

Specify the integer factor,  $L$ , by which to increase the sample rate of the input sequence.

## **Input processing**

Specify how the block should process the input. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The Inherited (this choice will be removed - see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## **Rate options**

Specify the method by which the block should interpolate the input. You can select one of the following options:

- **Enforce single-rate processing** — When you select this option, the block maintains the input sample rate, and interpolates the signal by increasing the output frame size by a factor of  $L$ . To select this option, you must set the **Input processing** parameter to **Columns as channels (frame based)**.
- **Allow multirate processing** — When you select this option, the block interpolates the signal such that the output sample rate is  $L$  times faster than the input sample rate.

## Output buffer initial conditions

In cases of nonzero latency, the block divides this parameter by the **Interpolation factor** and outputs the results at the output port until the first filtered input sample is available. The default initial condition value is 0, but you can enter a matrix containing one value for each channel, or a scalar to be applied to all signal channels. This parameter appears only when you configure the block to perform multirate processing.

Output buffer initial conditions are stored in the output data type and scaling.

See “Latency” on page 2-632 for more information about latency in the FIR Interpolation block.

## View filter response

This button opens the Filter Visualization Tool (fvtool) from the Signal Processing Toolbox product and displays the filter response of the filter defined in the block. For more information on FVTool, see the Signal Processing Toolbox documentation.

---


**Note** If you specify a filter in the **Multirate filter variable** parameter, you must apply the filter by clicking the **Apply** button before using the **View filter response** button.

---

# FIR Interpolation

---

The **Data Types** pane of the FIR Interpolation block dialog appears as follows when you select **Dialog parameters** in the **Coefficient source** group box.



# FIR Interpolation

---

## **Rounding mode**

Select the rounding mode for fixed-point operations. The filter coefficients do not obey this parameter; they always round to Nearest.

---

**Note** The **Rounding mode** and **Overflow mode** settings have no effect on numerical results when all the following conditions exist:

- **Product output data type** is Inherit: Inherit via internal rule
- **Accumulator data type** is Inherit: Inherit via internal rule
- **Output data type** is Inherit: Same as accumulator

With these data type settings, the block is effectively operating in full precision mode.

---

## **Overflow mode**

Select the overflow mode for fixed-point operations. The filter coefficients do not obey this parameter; they are always saturated.

## **Coefficients data type**

Specify the coefficients data type. See “Fixed-Point Data Types” on page 2-633 and “Multiplication Data Types” for illustrations depicting the use of the coefficients data type in this block. You can set it to:

- A rule that inherits a data type, for example, Inherit: Same word length as input
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Coefficients data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## **Product output data type**

Specify the product output data type. See “Fixed-Point Data Types” on page 2-633 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## **Accumulator data type**

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-633 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

# FIR Interpolation

---

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-633 for illustrations depicting the use of the output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as accumulator`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

## Minimum

Specify the minimum value that the block should output. The default value is [ ] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Maximum

Specify the maximum value that the block should output. The default value is [ ] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)

- Automatic scaling of fixed-point data types


### **Lock data type settings against changes by the fixed-point tools**

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

### **Specify Multirate Filter Object**

The **Main** pane of the FIR Interpolation block dialog appears as follows when you select **Multirate filter object (MFILT)** in the **Coefficient source** group box.

# FIR Interpolation



## Multirate filter variable

Specify the multirate filter object (`mfilt`) that you would like the block to implement. You can do this in one of three ways:

- You can fully specify the `mfilt` object in the block mask.
- You can enter the variable name of a `mfilt` object that is defined in any workspace.
- You can enter a variable name for a `mfilt` object that is not yet defined, as shown in the default value.

For more information on creating `mfilt` objects, see the `mfilt` function reference page.

## Input processing

Specify how the block should process the input. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The Inherited (this choice will be removed - see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Rate options

Specify the method by which the block should interpolate the input. You can select one of the following options:

- **Enforce single-rate processing** — When you select this option, the block maintains the input sample rate, and interpolates the signal by increasing the output frame size by

# FIR Interpolation

---

a factor of  $L$ . To select this option, you must set the **Input processing** parameter to Columns as channels (frame based).

- **Allow multirate processing** — When you select this option, the block interpolates the signal such that the output sample rate is  $L$  times faster than the input sample rate.

## **View filter response**


This button opens the Filter Visualization Tool (fvtool) from the Signal Processing Toolbox product and displays the filter response of the `mfilt` object specified in the **Multirate filter variable** parameter. For more information on FVTool, see the Signal Processing Toolbox documentation.

---

**Note** If you specify a filter in the **Multirate filter variable** parameter, you must apply the filter by clicking the **Apply** button before using the **View filter response** button.

---

The **Data Types** pane of the FIR Interpolation block dialog appears as follows when you select **Multirate filter object (MFILT)** in the **Coefficient source** group box.



# FIR Interpolation

---

The fixed-point settings of the filter object specified on the **Main** pane are displayed on the **Data Types** pane. You cannot change these settings directly on the block mask. To change the fixed-point settings you must edit the filter object directly.

For more information on multirate filter objects, see the `mfilt` function reference page.

## References

[1] Fliege, N. J. *Multirate Digital Signal Processing: Multirate Systems, Filter Banks, Wavelets*. West Sussex, England: John Wiley & Sons, 1994.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

## See Also

FIR Decimation	DSP System Toolbox
FIR Rate Conversion	DSP System Toolbox
Upsample	DSP System Toolbox
<code>fir1</code>	Signal Processing Toolbox

<code>fir2</code>	Signal Processing Toolbox
<code>firls</code>	Signal Processing Toolbox
<code>interp</code>	Signal Processing Toolbox


# FIR Rate Conversion

---

**Purpose** Upsample, filter, and downsample input signals

**Library** Filtering / Multirate Filters  
dspmlti4

## Description



The FIR Rate Conversion block resamples the discrete-time input such that its sample period is  $K/L$  times the input sample period ( $T_{si}$ ).  $K$  is the integer value you specify for the **Decimation factor** parameter, and  $L$  is the integer value you specify for the **Interpolation factor** parameter.

The block treats each column of the input as a separate channel, and resamples the data in each channel independently over time. To do so, the block implements a polyphase filter structure and performs the following operations:

- 1 Upsamples the input to a higher rate by inserting  $L-1$  zeros between input samples.
- 2 Passes the upsampled data through a direct-form II transpose FIR filter.
- 3 Downsamples the filtered data to a lower rate by discarding  $K-1$  consecutive samples following each sample that the block retains.

The polyphase filter implementation is more efficient than a straightforward upsample-filter-decimate algorithm. See Orfanidis [1] for more information.

## Specifying the Resampling Rate

You specify the resampling rate of the FIR Rate Conversion block using the **Decimation factor** and **Interpolation factor** parameters. For an  $M_i$ -by- $N$  matrix input, the **Decimation factor**,  $K$ , and the **Interpolation factor**,  $L$ , must satisfy the following requirements:

- $K$  and  $L$  must be relatively prime integers; that is, the ratio  $K/L$  cannot be reduced to a ratio of smaller integers.

- $\frac{K}{L} = \frac{M_i}{M_o}$ , where  $M_i$  and  $M_o$  are the integer frame sizes of the input and output, respectively.

You can satisfy the second requirement by setting the **Decimation factor**,  $K$ , equal to the input frame size,  $M_i$ . When you do so, the output frame size,  $M_o$ , equals the **Interpolation factor**,  $L$ .

By changing the frame size in this way, the block is able to hold the frame period constant ( $T_{fi} = T_{fo}$ ) and achieve the desired conversion of the sample period, such that

$$T_{so} = \frac{K}{L} \times T_{si}$$

where  $T_{so}$  is the output sample period.

## Specifying the FIR Filter Coefficients

You can specify the FIR filter coefficients in one of two ways:

- To specify the coefficients on the dialog, select the **Dialog parameters** option in the **Coefficient source** group box.
- To specify the coefficients using an `mfilt` object, select the **Multirate filter object (MFILT)** option in the **Coefficient source** group box.

When you select the **Dialog parameters** option, you use the **FIR filter coefficients** parameter to specify the numerator coefficients of the FIR filter transfer function  $H(z)$ .

$$H(z) = B(z) = b_1 + b_2z^{-1} + \dots + b_mz^{-(m-1)}$$

You can generate the FIR filter coefficient vector, `[b(1) b(2) ... b(m)]`, using one of the Signal Processing Toolbox filter design functions (such as `intfilt`).


The coefficient vector you specify must have a length greater than the interpolation factor ( $m > L$ ). The FIR filter must be a lowpass filter with

# FIR Rate Conversion

a normalized cutoff frequency, no greater than  $\min(1/L, 1/K)$ . The block internally initializes all filter states to zero.

## Fixed-Point Data Types

The following diagram shows the data types used within the FIR Rate Conversion block for fixed-point signals.



You can set the coefficient, product output, accumulator, and output data types in the block dialog box as discussed in “Dialog Box” on page 2-655. The diagram shows that input data is stored in the input buffer in the same data type and scaling as the input. Filtered data resides in the output buffer in the output data type and scaling that you set in the block dialog. The block stores any initial conditions in the output buffer using the output data type and scaling that you set in the block dialog box.

The output of the multiplier is in the product output data type when at least one of the inputs to the multiplier is real. When both of the inputs to the multiplier are complex, the result of the multiplication is in the accumulator data type. For details on the complex multiplication performed, see “Multiplication Data Types”.

---


**Note** When the block input is fixed point, all internal data types are signed fixed point.

---

## Examples

### Example 1

The following figure shows how the FIR Rate Conversion block converts a 4-by-1 input with a sample period of  $3/4$ , to a 3-by-1 output with a sample period of 1. The frame period ( $T_f$ ) of 3 remains constant.



### Example 2

The `ex_audio_src` model provides a simple illustration of one way to convert a speech signal from one sample rate to another. In this model, the data is first sampled at 22,050 Hz and then resampled at 8000 Hz. If you listen to the output, you can hear that the high frequency content has been removed from the signal, although the speech sounds basically the same.

## Dialog Box

### Coefficient Source

The FIR Rate Conversion block can operate in two different modes. Select the mode in the **Coefficient source** group box. If you select

- **Dialog parameters**, you enter information about the filter such as structure and coefficients in the block mask.

# FIR Rate Conversion

---


- **Multirate filter object (MFILT)**, you specify the filter using an `mfilt` object.

Different items appear on the FIR Rate Conversion block dialog depending on whether you select **Dialog parameters** or **Multirate filter object (MFILT)** in the **Coefficient source** group box. See the following sections for details:

- “Specify Filter Characteristics in Dialog” on page 2-656
- “Specify Multirate Filter Object” on page 2-663

## **Specify Filter Characteristics in Dialog**

The **Main** pane of the FIR Rate Conversion block dialog appears as follows when **Dialog parameters** is selected in the **Coefficient source** group box.



## Interpolation factor

Specify the integer factor,  $L$ , by which to upsample the signal before filtering.

# FIR Rate Conversion

---

## **FIR filter coefficients**

Specify the FIR filter coefficients in descending powers of  $z$ .

## **Decimation factor**

Specify the integer factor,  $K$ , by which to downsample the signal after filtering.

## **View filter response**


This button opens the Filter Visualization Tool (fvtool) from the Signal Processing Toolbox product and displays the filter response of the filter defined in the block. For more information on FVTool, see the Signal Processing Toolbox documentation.

---

**Note** If you specify a filter in the **Multirate filter variable** parameter, you must apply the filter by clicking the **Apply** button before using the **View filter response** button.

---

The **Data Types** pane of the FIR Rate Conversion block dialog appears as follows when **Dialog parameters** is specified in the **Coefficient source** group box.



## Rounding mode

Select the rounding mode for fixed-point operations. The filter coefficients do not obey this parameter; they always round to Nearest.

# FIR Rate Conversion

---

---

**Note** The **Rounding mode** and **Overflow mode** settings have no effect on numerical results when all the following conditions exist:

- **Product output data type** is Inherit: Inherit via internal rule
- **Accumulator data type** is Inherit: Inherit via internal rule
- **Output data type** is Inherit: Same as accumulator

With these data type settings, the block is effectively operating in full precision mode.

---

## Overflow mode

Select the overflow mode for fixed-point operations. The filter coefficients do not obey this parameter; they are always saturated.

## Coefficients data type

Specify the coefficients data type. See “Fixed-Point Data Types” on page 2-654 and “Multiplication Data Types” for illustrations depicting the use of the coefficients data type in this block. You can set it to:

- A rule that inherits a data type, for example, Inherit: Same word length as input
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`


Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Coefficients data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Product output data type

Specify the product output data type. See “Fixed-Point Data Types” on page 2-654 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Accumulator data type

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-654 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-654 for illustrations depicting the use of the output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as accumulator`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

## Minimum

Specify the minimum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Maximum

Specify the maximum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types


## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## **Specify Multirate Filter Object**

The **Main** pane of the FIR Rate Conversion block dialog appears as follows when **Multirate filter object (MFILT)** is specified in the **Coefficient source** group box.

# FIR Rate Conversion



## Multirate filter variable

Specify the multirate filter object (`mfilt`) that you would like the block to implement. You can do this in one of three ways:

- You can fully specify the `mfilt` object in the block mask.
- You can enter the variable name of a `mfilt` object that is defined in any workspace.
- You can enter a variable name for a `mfilt` object that is not yet defined, as shown in the default value.

For more information on creating `mfilt` objects, see the `mfilt` function reference page.

### **View filter response**

This button opens the Filter Visualization Tool (`fvtool`) from the Signal Processing Toolbox product and displays the filter response of the `mfilt` object specified in the **Multirate filter variable** parameter. For more information on FVTool, see the Signal Processing Toolbox documentation.


---

**Note** If you specify a filter in the **Multirate filter variable** parameter, you must apply the filter by clicking the **Apply** button before using the **View filter response** button.

---

The **Data Types** pane of the FIR Rate Conversion block dialog appears similar to the following dialog when **Multirate filter object (MFILT)** is specified in the **Coefficient source** group box. The fixed-point data types you see depend on the `mfilt` object you use.

# FIR Rate Conversion



The fixed-point settings of the filter object specified on the **Main** pane are displayed on the **Data Types** pane. You cannot change these settings directly on the block mask. To change the fixed-point settings you must edit the filter object directly.

For more information on multirate filter objects, see the `mfilt` function reference page.

## References

[1] Orfanidis, S. J. *Introduction to Signal Processing*. Prentice Hall, 1996.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

## See Also

Downsample	DSP System Toolbox
FIR Decimation	DSP System Toolbox
FIR Interpolation	DSP System Toolbox
Upsample	DSP System Toolbox
<code>fir1</code>	Signal Processing Toolbox
<code>fir2</code>	Signal Processing Toolbox
<code>firls</code>	Signal Processing Toolbox
<code>upfirdn</code>	Signal Processing Toolbox

# FIR Rate Conversion

---

See the following sections for related information:

- “Convert Sample and Frame Rates in Simulink”
- “Multirate and Multistage Filters”

**Purpose**

Flip input vertically or horizontally

**Library**

Signal Management / Indexing

dspindex

**Description**

The Flip block vertically or horizontally reverses the  $M$ -by- $N$  input matrix,  $u$ . The output always has the same dimensionality as the input.

When you set the **Flip along** parameter to Columns, the block flips the input *vertically* so the first row of the input becomes the last row of the output.

```
y = flipud(u)           % Equivalent MATLAB code
```

When flipping the input vertically, the block treats length- $M$  unoriented vector inputs as  $M$ -by-1 column vectors.

When you set the **Flip along** parameter to Rows, the block flips the input *horizontally* so the first column of the input becomes the last column of the output.


```
y = fliplr(u)          % Equivalent MATLAB code
```

When flipping the input horizontally, the block treats length- $N$  unoriented vector inputs as 1-by- $N$  row vectors.

This block supports Simulink virtual buses.

# Flip

## Dialog Box



## Flip along

Specify the dimension along which to flip the input. When you set this parameter to **Columns**, the block flips the input vertically. When you set this parameter to **Rows**, the block flips the input horizontally.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li><li>• Enumerated</li></ul>

Port	Supported Data Types
Output	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed and unsigned)</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> <li>• Enumerated</li> </ul>

## See Also

Selector	Simulink
Transpose	DSP System Toolbox
Variable Selector	DSP System Toolbox
flipud	MATLAB
fliplr	MATLAB

# Forward Substitution

---


## Purpose

Solve  $LX=B$  for  $X$  when  $L$  is lower triangular matrix

## Library

Math Functions / Matrices and Linear Algebra / Linear System Solvers  
dspsolvers

## Description



The Forward Substitution block solves the linear system  $LX=B$  by simple forward substitution of variables, where:

- $L$  is the lower triangular  $M$ -by- $M$  matrix input to the L port.
- $B$  is the  $M$ -by- $N$  matrix input to the B port.

The  $M$ -by- $N$  matrix output  $X$  is the solution of the equations. The block does not check the rank of the inputs.

The block only uses the elements in the *lower triangle* of input  $L$  and ignores the upper elements. When you select **Input L is unit-lower triangular**, the block assumes the elements on the diagonal of  $L$  are 1s. This is useful when matrix  $L$  is the result of another operation, such as an LDL decomposition, that uses the diagonal elements to represent the  $D$  matrix.


The block treats a length- $M$  vector input at port B as an  $M$ -by-1 matrix.

## Fixed-Point Data Types

The following diagram shows the data types used within the Forward Substitution block for fixed-point signals.


# Forward Substitution

When input L is not unit-lower triangular:



# Forward Substitution

When input L is unit-lower triangular:




You can set the product output, accumulator, and output data types in the block dialog box, as discussed in the following section.

The output of the multiplier is in the product output data type when the input is real. When the input is complex, the result of the multiplication is in the accumulator data type. For details on the complex multiplication performed, see “Multiplication Data Types”.

## Dialog Box

The **Main** pane of the Forward Substitution block dialog box appears as follows.

# Forward Substitution



## Input L is unit-lower triangular

Select this check box only when all elements on the diagonal of  $L$  have a value of 1. When you do so, the block optimizes its behavior by skipping an unnecessary divide operation.

Do not select this check box if there are any elements on the diagonal of  $L$  that do not have a value of 1. When you clear the **Input L is unit-lower triangular** check box, the block always performs the necessary divide operation.

# Forward Substitution

---

## **Diagonal of complex input L is real**

Select to optimize simulation speed when the diagonal elements of complex input  $L$  are real. This parameter is only visible when **Input L is unit-upper triangular** is not selected.


---

**Note** When  $L$  is a complex fixed-point signal, you must select either **Input L is unit-lower triangular** or **Diagonal of complex input L is real**. In such a case, the block ignores any imaginary part of the diagonal of  $L$ .

---

# Forward Substitution

The **Data Types** pane of the Forward Substitution block dialog box appears as follows.



**Note** Floating-point inheritance takes precedence over the data type settings defined on this pane. When inputs are floating point, the block ignores these settings, and all internal data types are floating point.

# Forward Substitution

---

## **Rounding mode**

Select the rounding mode for fixed-point operations.

## **Overflow mode**

Select the overflow mode for fixed-point operations.

## **Product output data type**

Specify the product output data type. See “Fixed-Point Data Types” on page 2-672 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## **Accumulator data type**

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-672 for illustrations depicting the use of the accumulator data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-672 for illustrations depicting the use of the output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as first input`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

## Minimum

Specify the minimum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Maximum

Specify the maximum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

# Forward Substitution

---

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

### Supported Data Types

Port	Supported Data Types
L	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
B	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
X	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>

## See Also

Backward Substitution	DSP System Toolbox
Cholesky Solver	DSP System Toolbox
LDL Solver	DSP System Toolbox
Levinson-Durbin	DSP System Toolbox
LU Solver	DSP System Toolbox
QR Solver	DSP System Toolbox


See “Linear System Solvers” for related information.

# Frame Conversion

**Purpose** Specify sampling mode of output signal


**Library** Signal Management / Signal Attributes  
dspsigattribs

## Description



The Frame Conversion block passes the input through to the output and sets the output sampling mode to the value of the **Sampling mode of output signal** parameter, which can be either Frame-based or Sample-based. The output sampling mode can also be inherited from the signal at the Ref (reference) input port, which you make visible by selecting the **Inherit output sampling mode from <Ref> input port** check box.

The Frame Conversion block does not make any changes to the input signal other than the sampling mode. In particular, the block does not rebuffer or resize 2-D inputs. Because 1-D vectors cannot be frame based, when the input is a length- $M$  1-D vector and the block is in Frame-based mode, the output is a frame-based  $M$ -by-1 matrix — that is, a single channel.



## Dialog Box

### **Inherit output sampling mode from <Ref> input port**

Select to enable the Ref port from which the block inherits the output sampling mode.

## Sampling mode of output signal

Specify the sampling mode of the output signal, Frame-based or Sample-based.

## Supported Data Types

Port	Supported Data Types
In	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed only)</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> <li>• Enumerated</li> </ul>
Ref	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed only)</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> <li>• Enumerated</li> </ul>
Output	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed only)</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> <li>• Enumerated</li> </ul>

# Frame Conversion

---

## See Also


Buffer	DSP System Toolbox
Check Signal Attributes	DSP System Toolbox
Convert 1-D to 2-D	DSP System Toolbox
Convert 2-D to 1-D	DSP System Toolbox
Inherit Complexity	DSP System Toolbox
Unbuffer	DSP System Toolbox
Probe	Simulink
Reshape	Simulink
Signal Specification	Simulink

# Frame Status Conversion (Obsolete)

**Purpose** Specify frame status of output as sample based or frame based

**Library** dspobslib

## Description



---

**Note** The Frame Status Conversion block is still supported but is likely to be obsoleted in a future release. We strongly recommend replacing this block with the Frame Conversion block.

---


The Frame Status Conversion block passes the input through to the output, and sets the output frame status to the **Output signal** parameter, which can be either **Frame-based** or **Sample-based**. The output frame status can also be inherited from the signal at the **Ref** (reference) input port, which is made visible by selecting the **Inherit output frame status from Ref input port** check box.

When the **Output signal** parameter setting or the inherited signal's frame status differs from the input frame status, the block changes the input frame status accordingly, but does not otherwise alter the signal. In particular, the block does not rebuffer or resize 2-D inputs. Because 1-D vectors cannot be frame based, when the input is a length- $M$  1-D vector, and the **Output signal** parameter is set to **Frame-based**, the output is a frame-based  $M$ -by-1 matrix (that is, a single channel).

When the **Output signal** parameter or the inherited signal's frame status matches the input frame status, the block passes the input through to the output unaltered.

# Frame Status Conversion (Obsolete)

## Dialog Box



### Inherit output frame status from Ref input port

When selected, enables the Ref input port from which the block inherits the output frame status.

### Output signal

The output frame status, Frame-based or Sample-based.

## Supported Data Types

Port	Supported Data Types
In	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Ref	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• Boolean</li></ul>

# Frame Status Conversion (Obsolete)

Port	Supported Data Types
	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

## See Also

Check Signal Attributes	DSP System Toolbox
Convert 1-D to 2-D	DSP System Toolbox
Convert 2-D to 1-D	DSP System Toolbox
Inherit Complexity	DSP System Toolbox

# From Audio Device

---

**Purpose** Read audio data from computer's audio device

**Library** Sources  
dspsrcs4

## Description



The From Audio Device block reads audio data from an audio device in real time. This block is not supported for use with the Simulink Model block.

Use the **Device** parameter to specify the device from which to acquire audio. This parameter is automatically populated based on the audio devices installed on your system. If you plug or unplug an audio device from your system, type `clear mex` at the MATLAB command prompt to update this list.

Use the **Number of channels** parameter to specify the number of audio channels in the signal. For example:

- Enter 2 if the audio source is two channels (stereo).
- Enter 1 if the audio source is single channel (mono).
- Enter 6 if you are working with a 5.1 speaker system.

The block's output is an  $M$ -by- $N$  matrix, where  $M$  is the number of consecutive samples and  $N$  is the number of audio channels.

Use the **Sample rate (Hz)** parameter to specify the number of samples per second in the signal. If the audio data is processed in uncompressed pulse code modulation (PCM) format, it should typically be sampled at one of the standard audio device rates: 8000, 11025, 22050, 44100, or 48000 Hz.

The range of supported audio device sample rates and data type formats, depend on both the sound card and the API which is chosen for the sound card.

Use the **Device data type** parameter to specify the data type of the audio data that the device is placing in the buffer. You can choose:

- 8-bit integer
- 16-bit integer
- 24-bit integer
- 32-bit float
- Determine from output data type

If you choose `Determine from output data type`, the following table summarizes the block's behavior.

Output Data Type	Device Data Type
Double-precision floating point or single-precision floating point	32-bit floating point
32-bit integer	24-bit integer
16-bit integer	16-bit integer
8-bit integer	8-bit integer

If you choose `Determine from output data type` and the device does not support a data type, the block uses the next lowest precision data type supported by the device.

Use the **Frame size (samples)** parameter to specify the number of samples in the block's output. Use the **Output data type** parameter to specify the data type of audio data output by the block.


The generated code for this block relies on prebuilt .dll files. You can run this code outside the MATLAB environment, or redeploy it, but be sure to account for these extra .dll files when doing so. The `packNGo` function creates a single zip file containing all of the pieces required to run or rebuild this code. See `packNGo` for more information.

## Buffering

The `From Audio Device` block buffers the data from the audio device using the process illustrated by the following figure.

# From Audio Device

---



From Audio Device Block

- 1** At the start of the simulation, the audio device begins writing the input data to a buffer. This data has the data type specified by the **Device data type** parameter.
- 2** When the buffer is full, the From Audio Device block writes the contents of the buffer to the queue. Specify the size of this queue using the **Queue duration (seconds)** parameter.
- 3** As the audio device appends audio data to the bottom of the queue, the From Audio Device block pulls data from the top of the queue to fill the Simulink frame. This data has the data type specified by the **Output data type** parameter.

Select the **Automatically determine buffer size** check box to allow the block to calculate a conservative buffer size using the following equation:

$$size = 2^{\left\lceil \log_2 \frac{sr}{10} \right\rceil}$$

In this equation, *size* is the buffer size, and *sr* is the sample rate. If you clear this check box, the **Buffer size (samples)** parameter appears on the block. Use this parameter to specify the buffer size in samples.

When the simulation throughput rate is lower than the hardware throughput rate, the queue, which is initially empty, fills up. If the queue is full, the block drops the incoming data from the audio device. When the simulation throughput rate is higher than the hardware throughput rate, the From Audio Device block waits for new samples to become available.

## Troubleshooting

When Simulink cannot keep up with an audio device that is operating in real time, the queue fills up and the block begins to lose audio data. Here are several ways to deal with this situation:

- *Increase the queue duration.*

The **Queue duration (seconds)** parameter specifies the duration of the signal, in seconds, that can be buffered during the simulation. This is the maximum length of time that the block's data demand can lag behind the hardware's data supply.

- *Increase the buffer size.*

The size of the buffer processed in each interrupt from the audio device affects the performance of your model. If the buffer is too small, a large portion of hardware resources are used to write data to the queue. If the buffer is too big, Simulink must wait for the device to fill the buffer before it moves the data to the queue, which introduces latency.

- *Increase the simulation throughput rate.*

Two useful methods for improving simulation throughput rates are increasing the signal frame size and compiling the simulation into native code:

- Increase frame sizes and convert sample-based signals to frame-based signals throughout the model to reduce the amount of block-to-block communication overhead. This can increase throughput rates in many cases. However, larger frame sizes generally result in greater model latency due to initial buffering operations.

- Generate executable code with Simulink Coder code generation software. Native code runs much faster than Simulink and should provide rates adequate for real-time audio processing.


Other ways to improve throughput rates include simplifying the model and running the simulation on a faster PC processor. For other ideas on improving simulation performance, see “Delay and Latency” and “Performance” in the Simulink documentation.

### Audio Hardware API

The To Audio Device and From Audio Device blocks use the open-source PortAudio library in order to communicate with the audio hardware on a given computer. The PortAudio library supports a range of APIs designed to communicate with the audio hardware on a given platform. The following API choices were made when building the PortAudio library for the DSP System Toolbox product:

- Windows: DirectSound, WDM—KS, ASIO
- Linux: OSS, ALSA
- Mac: CoreAudio

To select or change the Audio Hardware API, select **Preferences** from the MATLAB Toolstrip. Then select DSP System Toolbox from the tree menu. In the **DSP System Toolbox Preferences** dialog box, the option is disabled if no device corresponds to that particular audio API.



## Dialog Box

### Device

Specify the device from which to acquire audio data.

### Number of channels

Specify the number of audio channels.

### Sample rate (Hz)

Specify the number of samples per second in the signal.

### Device data type

Specify the data type used by the device to acquire audio data.

# From Audio Device

---

## **Automatically determine buffer size**

Select this check box to enable the block to use a conservative buffer size.

## **Buffer size (samples)**

Specify the size of the buffer that the block uses to communicate with the audio device. This parameter is visible when the **Automatically determine buffer size** check box is cleared.

## **Queue duration (seconds)**

Specify the size of the queue in seconds.

## **Frame size (samples)**

Specify the number of samples in the block's output signal.

## **Output data type**

Select the data type of the block's output.

## **Supported Data Types**


<b>Port</b>	<b>Supported Data Types</b>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• 32-bit signed integers</li><li>• 16-bit signed integers</li><li>• 8-bit unsigned integers</li></ul>

## **See Also**

From Multimedia File	DSP System Toolbox
To Audio Device	DSP System Toolbox
audiorecorder	MATLAB
dsp.AudioRecorder	System Object

**Purpose** Read multimedia file

**Library** Sources  
dspsrcs4



**Description**

The From Multimedia File block reads audio samples, video frames, or both from a multimedia file. The block imports data from the file into a Simulink model.

---

**Note** This block supports code generation for the host computer that has file I/O available. You cannot use this block with Real-Time Windows Target™ software because that product does not support file I/O.

---

The generated code for this block relies on prebuilt library files. You can run this code outside the MATLAB environment, or redeploy it, but be sure to account for these extra library files when doing so. The packNGo function creates a single zip file containing all of the pieces required to run or rebuild this code. See packNGo for more information.

To run an executable file that was generated from a model containing this block, you may need to add precompiled shared library files to your system path. See “Understanding Code Generation” for details.

# From Multimedia File

---

## Supported Platforms and File Types

The supported file formats available to you depends on the codecs installed on your system.

### Windows® Platforms Supported File Formats

With the necessary Windows DirectShow codecs installed on your system, the From Multimedia File Block supports many video and audio file formats. This block performs best on platforms with Version 9.0 or later of DirectX® software.

The following table lists the most common file formats.

Multimedia Types	File Name Extensions
Image files	.jpg, .bmp
Video files	.qt, .mov, .avi, .asf, .asx, .wmv, .mpg, .mpeg, .mp2, .mp4, .m4v
Audio files	.wav, .wma, .aif, .aifc, .aiff, .mp3, .au, .snd, .mp4, .m4a, .flac, .ogg

Windows XP x64 platform ships with a limited set of 64-bit video and audio codecs. If the From Multimedia File block cannot work on a compressed multimedia file, try one of the two alternatives:

- Run the 32-bit version of MATLAB on your Windows XP x64 platform. Windows XP x64 ships with many 32-bit codecs.
- Save the multimedia file to a file format supported by the From Multimedia File block.

If you use Windows, use Windows Media player Version 11 or later with this block for best results.

### Non-Windows Platform Supported File Formats

The following table lists the most common file formats.

Multimedia Types	File Name Extensions
Video files	.avi, .mj2, .mov, .mp4, .m4v
Audio files	Uncompressed .avi, .mp3, .mp4, .m4a, .wav, .flac, .ogg

## Ports

The output ports of the From Multimedia File block change according to the content of the multimedia file. If the file contains only video frames, the **Image**, intensity **I**, or **R,G,B** ports appear on the block. If the file contains only audio samples, the **Audio** port appears on the block. If the file contains both audio and video, you can select the data to emit. The following table describes available ports.

Port	Description
<b>Image</b>	$M$ -by- $N$ -by- $P$ color video signal where $P$ is the number of color planes.
<b>I</b>	$M$ -by- $N$ matrix of intensity values.
<b>R, G, B</b>	Matrix that represents one plane of the RGB video stream. Outputs from the R, G, or B ports must have same dimensions.
<b>Audio</b>	Vector of audio data.
<b>Y, Cb, Cr</b>	Matrix that represents one frame of the YCbCr video stream. The Y, Cb, Cr ports produce the following outputs: $Y: M \times N$ $Cb: M \times \frac{N}{2}$ $Cr: M \times \frac{N}{2}$

## Sample Rates

The sample rate that the block uses depends on the audio and video sample rate. While the FMMF block operates at a single rate in Simulink, the underlying audio and video streams can produce different

# From Multimedia File

---

## Sample Time Calculations Used for Video and Audio Files

rates. In some cases, when the block outputs both audio and video, makes a small adjustment to the video rate.

$$\text{Sample time} = \frac{\text{ceil}(\text{AudioSampleRate} / \text{FPS})}{\text{AudioSampleRate}} .$$

When audio sample time,  $\frac{\text{AudioSampleRate}}{\text{FPS}}$  is noninteger, the equation cannot reduce to  $\frac{1}{\text{FPS}}$  .


In this case, to prevent synchronization problems, the block drops the corresponding video frame when the audio stream leads the video

stream by more than  $\frac{1}{\text{FPS}}$  .

In summary, the block outputs one video frame at each Simulink time step. To calculate the number of audio samples to output at each time step, the block divides the audio sample rate by the video frame rate (fps). If the audio sample rate does not divide evenly by the number of video frames per second, the block rounds the number of audio samples up to the nearest whole number. If necessary, the block periodically drops a video frame to maintain synchronization for large files.

## Dialog Box

The **Main** pane of the From Multimedia File block dialog appears as follows.



# From Multimedia File

---

## **File name**

Specify the name of the multimedia file from which to read. The block determines the type of file (audio and video, audio only, or video only) and provides the associated parameters.

If the location of the file does not appear on your MATLAB path, use the **Browse** button to specify the full path. Otherwise, if the location of this file appears on your MATLAB path, enter only the file name. On Windows platforms, this parameter supports URLs that point to MMS (Microsoft Media Server) streams.

## **Inherit sample time from file**

Select the **Inherit sample time from file** check box if you want the block sample time to be the same as the multimedia file. If you clear this check box, enter the block sample time in the **Desired sample time** parameter field. The file that the From Multimedia File block references, determines the block default sample time. You can also set the sample time for this block manually. If you do not know the intended sample rate of the video, let the block inherit the sample rate from the multimedia file.

## **Desired sample time**

Specify the block sample time. This parameter becomes available if you clear the **Inherit sample time from file** check box.

## **Number of times to play file**

Enter a positive integer or `inf` to represent the number of times to play the file.

## **Output end-of-file indicator**

Use this check box to determine whether the output is the last video frame or audio sample in the multimedia file. When you select this check box, a Boolean output port labeled EOF appears on the block. The output from the EOF port defaults to 1 when the last video frame or audio sample is output from the block. Otherwise, the output from the EOF port defaults to 0.

## **Multimedia outputs**

Specify Video and audio, Video only, or Audio only output file type. This parameter becomes available only when a video signal has both audio and video.

## **Samples per audio channel**

Specify number of samples per audio channel. This parameter becomes available for files containing audio.

## **Output color format**

Specify whether you want the block to output RGB, Intensity, or YCbCr 4:2:2 video frames. This parameter becomes available only for a signal that contains video. If you select RGB, use the **Image signal** parameter to specify how to output a color signal.

## **Image signal**

Specify how to output a color video signal. If you select One multidimensional signal, the block outputs an  $M$ -by- $N$ -by- $P$  color video signal, where  $P$  is the number of color planes, at one port. If you select Separate color signals, additional ports appear on the block. Each port outputs one  $M$ -by- $N$  plane of an RGB video stream. This parameter becomes available only if you set the **Image color space** parameter to RGB and the signal contains video.


## **Audio output sampling mode**

Select Sample based or Frame based output. If the input to the block has 3 or more dimensions, you must select Sample based output. This parameter appears when you specify a file containing audio for the **File name** parameter.

The **Data Types** pane of the To Multimedia File block dialog box appears as follows.

# From Multimedia File

---



## Audio output data type

Set the data type of the audio samples output at the Audio port. This parameter becomes available only if the multimedia file contains audio. You can choose double, single, int16, or uint8 types.

## Video output data type

Set the data type of the video frames output at the **R**, **G**, **B**, or **Image** ports. This parameter becomes available only if the multimedia file contains video. You can choose double, single, int8, uint8, int16, uint16, int32, uint32, or Inherit from file types.

## Supported Data Types

For source blocks to display video data properly, double- and single-precision floating-point pixel values must be between 0 and 1. For other data types, the pixel values must be between the minimum and maximum values supported by their data type.

Port	Supported Data Types	Supports Complex Values?
Image	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>	No
R, G, B	Same as the Image port	No
Audio	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• 16-bit signed integers</li> <li>• 8-bit unsigned integers</li> </ul>	No
Y, Cb,Cr	Same as the Image port	No

## From Multimedia File

---

### **See Also**

To Multimedia File  
“Sample Time”

DSP System Toolbox  
Simulink

## Purpose

Read audio data from standard audio device in real-time (32-bit Windows operating systems only)

## Library

dspwin32

## Description



---

**Note** The From Wave Device block is still supported but is likely to be obsoleted in a future release. We strongly recommend replacing this block with the From Audio Device block.

---

The From Wave Device block reads audio data from a standard Windows audio device in real-time. It is compatible with most popular Windows hardware, including Sound Blaster cards. (Models that contain both this block and the To Wave Device block require a *duplex-capable* sound card.)

The **Use default audio device** parameter allows the block to detect and use the system's default audio hardware. This option should be selected on systems that have a single sound device installed, or when the default sound device on a multiple-device system is the desired source. In cases when the default sound device is not the desired input source, clear **Use default audio device**, and select the desired device in the **Audio device menu** parameter.

When the audio source contains two channels (stereo), the **Stereo** check box should be selected. When the audio source contains a single channel (mono), the **Stereo** check box should be cleared. For stereo input, the block's output is an  $M$ -by-2 matrix containing one frame ( $M$  consecutive samples) of audio data from each of the two channels. For mono input, the block's output is an  $M$ -by-1 matrix containing one frame ( $M$  consecutive samples) of audio data from the mono input. The frame size,  $M$ , is specified by the **Samples per frame** parameter. For  $M=1$ , the output is sample based; otherwise, the output is frame based.

The audio data is processed in uncompressed pulse code modulation (PCM) format, and should typically be sampled at one of the standard Windows audio device rates: 8000, 11025, 22050, or 44100 Hz. You can

## From Wave Device (Obsolete)

---

select one of these rates from the **Sample rate** parameter. To specify a different rate, select the **User-defined** option and enter a value in the **User-defined sample rate** parameter.

The **Sample Width (bits)** parameter specifies the number of bits used to represent the signal samples read by the audio device. The following settings are available:

- 8 — allocates 8 bits to each sample, allowing a resolution of 256 levels
- 16 — allocates 16 bits to each sample, allowing a resolution of 65536 levels
- 24 — allocates 24 bits to each sample, allowing a resolution of 16777216 levels (only for use with 24-bit audio devices)

Higher sample width settings require more memory but yield better fidelity. The output from the block is independent of the **Sample width (bits)** setting. The output data type is determined by the **Data type** parameter setting.


### Buffering

Since the audio device accepts real-time audio input, Simulink software must read a continuous stream of data from the device throughout the simulation. Delays in reading data from the audio hardware can result in hardware errors or distortion of the signal. This means that the From Wave Device block must read data from the audio hardware as quickly as the hardware itself acquires the signal. However, the block often *cannot* match the throughput rate of the audio hardware, especially when the simulation is running from within Simulink rather than as generated code. (Simulink operations are generally slower than comparable hardware operations, and execution speed routinely varies during the simulation as the host operating system services other processes.) The block must therefore rely on a buffering strategy to ensure that signal data can be read on schedule without losing samples.

At the start of the simulation, the audio device begins writing the input data to a (hardware) buffer with a capacity of  $T_b$  seconds. The From Wave Device block immediately begins pulling the earliest samples off

the buffer (first in, first out) and collecting them in length- $M$  frames for output. As the audio device continues to append inputs to the bottom of the buffer, the From Wave Device block continues to pull inputs off the top of the buffer at the best possible rate.

The following figure shows an audio signal being acquired and output with a frame size of 8 samples. The buffer of the sound board is approaching its five-frame capacity at the instant shown, which means that the hardware is adding samples to the buffer more rapidly than the block is pulling them off. (If the signal sample rate was 8 kHz, this small buffer could hold approximately 0.005 second of data.)



When the simulation throughput rate is higher than the hardware throughput rate, the buffer remains empty throughout the simulation. If necessary, the From Wave Device block simply waits for new samples to become available on the buffer (the block does not interpolate between samples). More typically, the simulation throughput rate is lower than the hardware throughput rate, and the buffer tends to fill over the duration of the simulation.

## Troubleshooting

When the buffer size is too small in relation to the simulation throughput rate, the buffer might fill before the entire length of signal is processed. This usually results in a device error or undesired device output. When this problem occurs, you can choose to either increase the buffer size or the simulation throughput rate:

## From Wave Device (Obsolete)

---

- *Increase the buffer size*

The **Queue duration** parameter specifies the duration of signal,  $T_b$  (in real-time seconds), that can be buffered in hardware during the simulation. Equivalently, this is the maximum length of time that the block's data acquisition can lag the hardware's data acquisition. The number of frames buffered is approximately

$$\frac{T_b F_s}{M}$$

where  $F_s$  is the sample rate of the signal and  $M$  is the number of samples per frame. The required buffer size for a given signal depends on the signal length, the frame size, and the speed of the simulation. Note that increasing the buffer size might increase model latency.


- *Increase the simulation throughput rate*

Two useful methods for improving simulation throughput rates are increasing the signal frame size and compiling the simulation into native code:

- Increase frame sizes (and convert sample-based signals to frame-based signals) throughout the model to reduce the amount of block-to-block communication overhead. This can drastically increase throughput rates in many cases. However, larger frame sizes generally result in greater model latency due to initial buffering operations.
- Generate executable code with Simulink Coder. Native code runs much faster than Simulink, and should provide rates adequate for real-time audio processing.

More general ways to improve throughput rates include simplifying the model, and running the simulation on a faster PC processor. See “Delay and Latency” and “Performance” in the Simulink documentation for other ideas on improving simulation performance.

## Dialog Box



### Sample rate (Hz)

The sample rate of the audio data to be acquired. Select one of the standard Windows rates or the User-defined option.

### User-defined sample rate (Hz)

The (nonstandard) sample rate of the audio data to be acquired.

### Sample width (bits)

The number of bits used to represent each signal sample.

# From Wave Device (Obsolete)

---

## **Stereo**

Specifies stereo (two-channel) inputs when selected, mono (one-channel) inputs when cleared. Stereo output is  $M$ -by-2; mono output is  $M$ -by-1.

## **Samples per frame**

The number of audio samples in each successive output frame,  $M$ . When the value of this parameter is 1, the block outputs a sample-based signal.

## **Queue duration (seconds)**

The length of signal (in seconds) to buffer to the hardware at the start of the simulation.

## **Use default audio device**

Reads audio input from the system's default audio device when selected. Clear to enable the **Audio device ID** parameter and select a device.

## **Audio device**

The name of the audio device from which to read the audio output (lists the names of the installed audio device drivers). Select **Use default audio device** when the system has only a single audio card installed.

## **Data type**

The data type of the output: double-precision, single-precision, signed 16-bit integer, or unsigned 8-bit integer.

## **Supported Data Types**

- Double-precision floating point
- Single-precision floating point
- 16-bit signed integer
- 8-bit unsigned integer

### See Also

From Wave File  
(Obsolete)

DSP System Toolbox

To Wave Device  
(Obsolete)

DSP System Toolbox

audiorecorder


MATLAB

# From Wave File (Obsolete)

**Purpose** Read audio data from Microsoft Wave (.wav) file

**Library** dspwin32

## Description



**Note** The From Wave File block is still supported but is likely to be obsoleted in a future release. We strongly recommend replacing this block with the From Multimedia File block.

The From Wave File block streams audio data from a Microsoft® Wave (.wav) file and generates a signal with one of the data types and amplitude ranges in the following table.

**Note** AVI files are the only supported file type for non-Windows platforms.

Output Data Type	Output Amplitude Range
double	$\pm 1$
single	$\pm 1$
int16	-32768 to 32767 ( $-2^{15}$ to $2^{15} - 1$ )
uint8	0 to 255

The audio data must be in uncompressed pulse code modulation (PCM) format.

`y = wavread('filename')`      % Equivalent MATLAB code

The block supports 8-, 16-, 24-, and 32-bit Microsoft Wave (.wav) files.

The **File name** parameter can specify an absolute or relative path to the file. When the file is on the MATLAB path or in the current folder (the

folder returned by typing `pwd` at the MATLAB command line), you need only specify the file name. You do not need to specify the `.wav` extension.

---

**Note** The From Wave File block does not support `.wav` file names that contain a `+` character. To read `.wav` files that have a `+` character in the file name, use the From Multimedia File block.

---

For an audio file containing  $C$  channels, the block's output is an  $M$ -by- $C$  matrix containing one frame ( $M$  consecutive samples) of audio data from each channel. The frame size,  $M$ , is specified by the **Samples per output frame** parameter. For  $M=1$ , the output is sample based; otherwise, the output is frame based.

The output frame period,  $T_{fo}$ , is

$$T_{fo} = \frac{M}{F_s}$$

where  $F_s$  is the data sample rate in Hz.

To reduce the required number of file accesses, the block acquires  $L$  consecutive samples from the file during each access, where  $L$  is specified by the **Minimum number of samples for each read from file** parameter ( $L \geq M$ ). For  $L < M$ , the block instead acquires  $M$  consecutive samples during each access. Larger values of  $L$  result in fewer file accesses, which reduces run-time overhead.

Use the **Data type** parameter to specify the data type of the block's output. Your choices are `double`, `single`, `uint8`, or `int16`.

Select the **Loop** check box if you want to play the file more than once. Then, enter the number of times to play the file. The number you enter must be a positive integer or `inf`.

Use the **Number of times to play file** parameter to enter the number of times to play the file. The number you enter must be a positive integer or `inf`, to play the file until you stop the simulation.

## From Wave File (Obsolete)

---


The **Samples restart** parameter determines whether the samples from the audio file repeat immediately or repeat at the beginning of the next frame output from the output port. When you select **immediately after last sample**, the samples repeat immediately. When you select **at beginning of next frame**, the frame containing the last sample value from the audio file is zero padded until the frame is filled. The block then places the first sample of the audio file in the first position of the next output frame.

Use the **Output start-of-file indicator** parameter to determine when the first audio sample in the file is output from the block. When you select this check box, a Boolean output port labeled SOF appears on the block. The output from the SOF port is 1 when the first audio sample in the file is output from the block. Otherwise, the output from the SOF port is 0.

Use the **Output end-of-file indicator** parameter to determine when the last audio sample in the file is output from the block. When you select this check box, a Boolean output port labeled EOF appears on the block. The output from the EOF port is 1 when the last audio sample in the file is output from the block. Otherwise, the output from the EOF port is 0.

The block icon shows the name, sample rate (in Hz), number of channels (1 or 2), and sample width (in bits) of the data in the specified audio file. All sample rates are supported; the sample width must be either 8, 16, 24, or 32 bits.

## Dialog Box



### File name

Enter the path and name of the file to read. Paths can be relative or absolute.

# From Wave File (Obsolete)

---

---

**Note** The From Wave File block does not support .wav file names that contain a + character. To read .wav files that have a + character in the file name, use the From Multimedia File block.

---

## **Samples per output frame**

Enter the number of samples in each output frame,  $M$ . When the value of this parameter is 1, the block outputs a sample-based signal.

## **Minimum number of samples for each read from file**

Enter the number of consecutive samples to acquire from the file with each file access,  $L$ .

## **Data type**

Select the output data type: `double`, `single`, `uint8`, or `int16`. The data type setting determines the output's amplitude range, as shown in the preceding table.

## **Loop**

Select this check box if you want to play the file more than once.

## **Number of times to play file**

Enter the number of times you want to play the file.

## **Samples restart**

Select `immediately after last sample` to repeat the audio file immediately. Select `at beginning of next frame` to place the first sample of the audio file in the first position of the next output frame.

## **Output start-of-file indicator**

Use this check box to determine whether the output contains the first audio sample in the file.

## **Output end-of-file indicator**

Use this check box to determine whether the output contains the last audio sample in the file.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point
- 16-bit signed integer
- 8-bit unsigned integer

## See Also

From Audio Device

Signal From Workspace

To Multimedia File

wavread

DSP System Toolbox

DSP System Toolbox

DSP System Toolbox

MATLAB


# G711 Codec

---

**Purpose** Quantize narrowband speech input signals

**Library** Quantizers  
dspquant2

## Description



The G711 Codec block is a logarithmic scalar quantizer designed for narrowband speech. Narrowband speech is defined as a voice signal with an analog bandwidth of 4 kHz and a Nyquist sampling frequency of 8 kHz. The block quantizes a narrowband speech input signal so that it can be transmitted using only 8-bits. The G711 Codec block has three modes of operation: encoding, decoding, and conversion. You can choose the block's mode of operation by setting the **Mode** parameter.

If, for the **Mode** parameter, you choose Encode PCM to A-law, the block assumes that the linear PCM input signal has a dynamic range of 13 bits. Because the block always operates in saturation mode, it assigns any input value above  $2^{12} - 1$  to  $2^{12} - 1$  and any input value below  $-2^{12}$  to  $-2^{12}$ . The block implements an A-law quantizer on the input signal and outputs A-law index values. When you choose Encode PCM to mu-law, the block assumes that the linear PCM input signal has a dynamic range of 14 bits. Because the block always operates in saturation mode, it assigns any input value above  $2^{13} - 1$  to  $2^{13} - 1$  and any input value below  $-2^{13}$  to  $-2^{13}$ . The block implements a mu-law quantizer on the input signal and outputs mu-law index values.

If, for the **Mode** parameter, you choose Decode A-law to PCM, the block decodes the input A-law index values into quantized output values using an A-law lookup table. When you choose Decode mu-law to PCM, the block decodes the input mu-law index values into quantized output values using a mu-law lookup table.

If, for the **Mode** parameter, you choose Convert A-law to mu-law, the block converts the input A-law index values to mu-law index values. When you choose Convert mu-law to A-law, the block converts the input mu-law index values to A-law index values.

---

**Note** Set the **Mode** parameter to Convert A-law to mu-law or Convert mu-law to A-law only when the input to the block is A-law or mu-law index values.

---

If, for the **Mode** parameter, you choose Encode PCM to A-law or Encode PCM to mu-law, the **Overflow diagnostic** parameter appears on the block parameters dialog box. Use this parameter to determine the behavior of the block when overflow occurs. The following options are available:

- **Ignore** — Proceed with the computation and do not issue a warning message.
- **Warning** — Display a warning message in the MATLAB Command Window, and continue the simulation.
- **Error** — Display an error dialog box and terminate the simulation.


---

**Note** Like all diagnostic parameters on the Configuration Parameters dialog box, **Overflow diagnostic** parameter is set to **Ignore** in the code generated for this block by Simulink Coder code generation software.

---

# G711 Codec

## Dialog Box



### Mode

- When you choose **Encode PCM to A-law**, the block implements an A-law encoder.
- When you choose **Encode PCM to mu-law**, the block implements a mu-law encoder.
- When you choose **Decode A-law to PCM**, the block decodes the input index values into quantized output values using an A-law lookup table.
- When you choose **Decode mu-law to PCM**, the block decodes the input index values into quantized output values using a mu-law lookup table.
- When you choose **Convert A-law to mu-law**, the block converts the input A-law index values to mu-law index values.
- When you choose **Convert mu-law to A-law**, the block converts the input mu-law index values to A-law index values.

## Overflow diagnostic

Use this parameter to determine the behavior of the block when overflow occurs.

- Select **Ignore** to proceed with the computation without a warning message.
- Select **Warning** to display a warning message in the MATLAB Command Window and continue the simulation.
- Select **Error** to display an error dialog box and terminate the simulation.

This parameter is only visible if, for the **Mode** parameter, you select **Encode PCM to A-law** or **Encode PCM to mu-law**.

## References

ITU-T Recommendation G.711, "Pulse Code Modulation (PCM) of Voice Frequencies," *General Aspects of Digital Transmission Systems; Terminal Equipments*, International Telecommunication Union (ITU), 1993.

## Supported Data Types

Port	Supported Data Types
PCM	<ul style="list-style-type: none"> <li>• 16-bit signed integers</li> </ul>
A	<ul style="list-style-type: none"> <li>• 8-bit unsigned integers</li> </ul>
mu	<ul style="list-style-type: none"> <li>• 8-bit unsigned integers</li> </ul>

## See Also

Quantizer	Simulink
Scalar Quantizer Decoder	DSP System Toolbox
Scalar Quantizer Design	DSP System Toolbox
Uniform Decoder	DSP System Toolbox
Uniform Encoder	DSP System Toolbox
Vector Quantizer Decoder	DSP System Toolbox

# G711 Codec

---

Vector Quantizer Design

Vector Quantizer Encoder

DSP System Toolbox

DSP System Toolbox

**Purpose** Design halfband filter

**Library** Filtering / Filter Designs  
dspfdesign

**Description** This block brings the filter design capabilities of the `filterbuilder` function to the Simulink environment.



**Dialog Box** See “Halfband Filter Design Dialog Box — Main Pane” on page 7-715 for more information about the parameters of this block. The **Data Types** and **Code Generation** panes are not available for blocks in the DSP System Toolbox Filter Designs library.

# Halfband Filter

Function Block Parameters: Halfband Filter

Halfband Filter

Design a Halfband filter.

[View Filter Response](#)

Frequency specifications

Impulse response: FIR

Order mode: Minimum Order:

Response type: Lowpass

Filter Type: Single-rate

Frequency specifications

Frequency units: Normalized (0 to 1) Input Fs:

Transition width:

Magnitude specifications

Magnitude units: dB

Astop:

Algorithm

Design method: Equiripple

► Design options

Filter Implementation

Structure: Direct-form FIR

Use basic elements to enable filter customization

Input processing: Columns as channels (frame based)

Use symbolic names for coefficients

OK Cancel Help Apply

- Magnitude response, phase response, and group delay in the frequency domain.
- Impulse response and step response in the time domain.
- Pole-zero information.

The tool also helps you evaluate filter performance by providing information about filter order, stability, and phase linearity. For more information on FVTool, see the Signal Processing Toolbox documentation.

## Filter Specifications

In this group, you specify your filter type and order.

### Impulse response

Select either **FIR** or **IIR** from the drop-down list. **FIR** is the default. When you choose an impulse response, the design methods and structures you can use to implement your filter change accordingly.

---

**Note** The design methods and structures for **FIR** filters are not the same as the methods and structures for **IIR** filters.

---

### Order mode

Select either **Minimum** (the default) or **Specify** from the drop-down list. Selecting **Specify** enables the **Order** option (see the following sections) so you can enter the filter order.

### Response type

Specify the filter response as **Lowpass** (the default) or **Highpass**.

### Filter type

Select **Single-rate**, **Decimator**, or **Interpolator**. By default, the block specifies a single-rate filter.


# Halfband Filter

## Order

Enter the filter order. This option is enabled only when the **Filter order mode** is set to Specify.

## Frequency Specifications

The parameters in this group allow you to specify your filter response curve. Graphically, the filter specifications for a halfband lowpass filter look similar to those shown in the following figure.



In the figure, the transition region lies between the end of the passband and the start of the stopband. The width is defined explicitly by the value of **Transition width**.

## Frequency constraints

When **Order mode** is Specify, set this parameter to Unconstrained or Transition width.

## Frequency units

Use this parameter to specify whether your frequency settings are normalized or in absolute frequency. Select **Normalized (0 1)** to enter frequencies in normalized form. This behavior is the default. To enter frequencies in absolute values, select one of the

frequency units from the drop-down list—Hz, kHz, MHz, or GHz. Selecting one of the unit options enables the **Input Fs** parameter.

## **Input Fs**

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter input. When you provide an input sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is available when you select one of the frequency options from the **Frequency units** list.

## **Transition width**

Specify the width of the transition between the end of the passband and the edge of the stopband. Specify the value in normalized frequency units or the absolute units you select in **Frequency units**.

## **Magnitude Specifications**

Parameters in this group specify the filter response in the passbands and stopbands.

### **Magnitude constraints**

Specify **Unconstrained** (the default), or select **Stopband attenuation** to constrain the response in the stopband explicitly.

### **Magnitude units**

Specify the units for any parameter you provide in magnitude specifications. From the drop-down list, select one of the following options:

- **Linear** — Specify the magnitude in linear units.
- **dB** — Specify the magnitude in decibels (default).

### **Astop**

When **Magnitude units** is **Stopband attenuation**, enter the filter attenuation in the stopband in the units you choose for **Magnitude units**, either linear or decibels.

# Halfband Filter

---

## Algorithm

The parameters in this group allow you to specify the design method and structure of your filter.

## Design Method

Lists the design methods available for the frequency and magnitude specifications you entered. For FIR halfband filters, the available design options are equiripple, and Kaiser window. For IIR halfband filters, the available design options are Butterworth, elliptic, and IIR quasi-linear phase.

## Design Options

The following design options are available for FIR halfband filters when the user specifies an equiripple design:

### Minimum phase

Select the checkbox to specify a minimum-phase design.

### Stopband Shape

Stopband shape lets you specify how the stopband changes with increasing frequency. Choose one of the following options:

- Flat — Specifies that the stopband is flat. The attenuation does not change as the frequency increases.
- Linear — Specifies that the stopband attenuation changes linearly as the frequency increases. Change the slope of the stopband by setting **Stopband decay**.
- $1/f$  — Specifies that the stopband attenuation changes exponentially as the frequency increases, where  $f$  is the frequency. Set the power (exponent) for the decay in **Stopband decay**.

### Stopband Decay

When you set Stopband shape, Stopband decay specifies the amount of decay applied to the stopband. the following

conditions apply to Stopband decay based on the value of Stopband Shape:

- When you set **Stopband shape** to Flat, **Stopband decay** has no affect on the stopband.
- When you set **Stopband shape** to Linear, enter the slope of the stopband in units of dB/rad/s. The block applies that slope to the stopband.
- When you set **Stopband shape** to  $1/f$ , enter a value for the exponent  $n$  in the relation  $(1/f)^n$  to define the stopband decay. The block applies the  $(1/f)^n$  relation to the stopband to result in an exponentially decreasing stopband attenuation.

## Filter Implementation

### Structure

For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter.

### Use basic elements to enable filter customization

Select this check box to implement the filter as a subsystem of basic Simulink blocks. Clear the check box to implement the filter as a high-level subsystem. By default, this check box is cleared.

The high-level implementation provides better compatibility across various filter structures, especially filters that would contain algebraic loops when constructed using basic elements. On the other hand, using basic elements enables the following optimization parameters:

- **Optimize for zero gains** — Terminate chains that contain Gain blocks with a gain of zero.
- **Optimize for unit gains** — Remove Gain blocks that scale by a factor of one.

# Halfband Filter

---

- **Optimize for delay chains** — Substitute delay chains made up of  $n$  unit delays with a single delay by  $n$ .
- **Optimize for negative gains** — Use subtraction in Sum blocks instead of negative gains in Gain blocks.

## Optimize for unit-scale values

Select this check box to scale unit gains between sections in SOS filters. This parameter is available only for SOS filters.

## Input processing

Specify how the block should process the input. The available options may vary depending on the settings of the **Filter Structure** and **Use basic elements for filter customization** parameters. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The Inherited (this choice will be removed see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Rate options

When the **Filter type** parameter specifies a multirate filter, select the rate processing rule for the block from following options:

- **Enforce single-rate processing** — When you select this option, the block maintains the sample rate of the input.

- **Allow multirate processing** — When you select this option, the block adjusts the rate at the output to accommodate an increased or reduced number of samples. To select this option, you must set the **Input processing** parameter to **Elements** as **channels** (sample based).

### Use symbolic names for coefficients

Select this check box to enable the specification of coefficients using MATLAB variables. The available coefficient names differ depending on the filter structure. Using symbolic names allows tuning of filter coefficients in generated code. By default, this check box is cleared.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

# Highpass Filter

---

**Purpose** Design highpass filter

**Library** Filtering / Filter Designs  
dspfdesign

**Description** This block brings the filter design capabilities of the `filterbuilder` function to the Simulink environment.



**Dialog Box** See “Highpass Filter Design Dialog Box — Main Pane” on page 7-721 for more information about the parameters of this block. The **Data Types** and **Code Generation** panes are not available for blocks in the DSP System Toolbox Filter Designs library.

# Highpass Filter

Function Block Parameters: Highpass Filter

Highpass Filter  
Design a Highpass filter.

[View Filter Response](#)

Filter specifications

Impulse response:

Order mode:

Filter Type:

Frequency specifications

Frequency units:  Input Fs:

Fstop:  Fpass:

Magnitude specifications

Magnitude units:

Astop:  Apass:

Algorithm

Design method:

► Design options

Filter Implementation

Structure:

Use basic elements to enable filter customization

Input processing:

Use symbolic names for coefficients

# Highpass Filter

---

## View filter response

This button opens the Filter Visualization Tool (fvtool) from the Signal Processing Toolbox product. You can use the tool to display:

- Magnitude response, phase response, and group delay in the frequency domain.
- Impulse response and step response in the time domain.
- Pole-zero information.

The tool also helps you evaluate filter performance by providing information about filter order, stability, and phase linearity. For more information on FVTool, see the Signal Processing Toolbox documentation.

## Filter Specifications

In this group, you specify your filter format, such as the impulse response and the filter order.

### Impulse response

Select either **FIR** or **IIR** from the drop-down list. **FIR** is the default. When you choose an impulse response, the design methods and structures you can use to implement your filter change accordingly.

---

**Note** The design methods and structures for **FIR** filters are not the same as the methods and structures for **IIR** filters.

---

### Order mode

Select **Minimum** (the default) or **Specify**. Selecting **Specify** enables the **Order** option so you can enter the filter order. When you set the **Impulse response** to **IIR**, you can specify different numerator and denominator orders. To specify a different denominator order, you must select the **Denominator order** check box.

## Order

Enter the filter order. This option is enabled only if you set the **Order mode** to Specify.

## Denominator order

Select this check box to specify a different denominator order. This option is enabled only if you set the **Impulse response** to IIR and the **Order mode** to Specify.

## Filter type

Select Single-rate, Decimator, Interpolator, or Sample-rate converter. Your choice determines the type of filter as well as the design methods and structures that are available to implement your filter. By default, the block specifies a single-rate filter.

- Selecting Decimator or Interpolator activates the **Decimation Factor** or the **Interpolation Factor** options respectively.
- Selecting Sample-rate converter activates both factors.

## Decimation Factor

Enter the decimation factor. This option is enabled only if the **Filter type** is set to Decimator or Sample-rate converter. The default value is 2.


## Interpolation Factor

Enter the interpolation factor. This option is enabled only if the **Filter type** is set to Interpolator or Sample-rate converter. The default value is 2.

## Frequency Specifications

The parameters in this group allow you to specify your filter response curve. Graphically, the filter specifications look similar to those shown in the following figure.

# Highpass Filter



In the figure, the region between specification values  $F_{stop}$  and  $F_{pass}$  represents the transition region where the filter response is not constrained.

## Frequency constraints

When **Order mode** is **Specify**, select the filter features that the block uses to define the frequency response characteristics. The list contains the following options, when available for the filter specifications.

- **Stopband edge and passband edge** — Define the filter by specifying the frequencies for the edges for the stop- and passbands.
- **Passband edge** — Define the filter by specifying the edge of the passband.
- **Stopband edge** — Define the filter by specifying the edge of the stopband.
- **Stopband edge and 3 dB point** — For IIR filters, define the filter by specifying the frequency of the 3 dB point in the filter response and the edge of the stopband.
- **3 dB point** — Define the filter response by specifying the location of the 3 dB point. The 3 dB point is the frequency for the point three decibels below the passband value.

- **3 dB point and passband edge** — For IIR filters, define the filter by specifying the frequency of the 3 dB point in the filter response and the edge of the passband.
- **6 dB point** — For FIR filters, define the filter response by specifying the location of the 6 dB point. The 6 dB point is the frequency for the point six decibels below the passband value.

## Frequency units

Use this parameter to specify whether your frequency settings are normalized or in absolute frequency. Select **Normalized (0 1)** to enter frequencies in normalized form. This behavior is the default. To enter frequencies in absolute values, select one of the frequency units from the drop-down list—Hz, kHz, MHz, or GHz. Selecting one of the unit options enables the **Input Fs** parameter.

## Input Fs

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter input. When you provide an input sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is available when you select one of the frequency options from the **Frequency units** list.

## Fstop

Enter the frequency at the edge of the end of the stopband. Specify the value in either normalized frequency units or the absolute units you select in **Frequency units**.

## Fpass

Enter the frequency at the edge of the start of the passband. Specify the value in either normalized frequency units or the absolute units you select in **Frequency units**.

## F3dB

When **Frequency constraints** is **3 dB point, Stopband edge and 3 dB point**, or **3 dB point and passband edge**, specify the frequency of the 3 dB point. Specify the value in either normalized frequency units or the absolute units you select **Frequency units**.

# Highpass Filter

---

## F6dB

When **Frequency constraints** is 6 dB point, specify the frequency of the 6 dB point. Specify the value in either normalized frequency units or the absolute units you select **Frequency units**.

## Magnitude Specifications

Parameters in this group specify the filter response in the passbands and stopbands.

### Magnitude constraints

This option is only available when you specify the order of your filter design. Depending on the setting of the **Frequency constraints** parameter, some combination of the following options will be available for the **Magnitude constraints** parameter: Unconstrained, Passband ripple, Passband ripple and stopband attenuation or Stopband attenuation.

### Magnitude units

Specify the units for any parameter you provide in magnitude specifications. From the drop-down list, select one of the following options:

- Linear — Specify the magnitude in linear units.
- dB — Specify the magnitude in decibels (default).
- Squared — Specify the magnitude in squared units.

### Astop

Enter the filter attenuation in the stopband in the units you choose for **Magnitude units**, either linear or decibels.

### Apass

Enter the filter ripple allowed in the passband in the units you choose for **Magnitude units**, either linear or decibels.

## Algorithm

The parameters in this group allow you to specify the design method and structure of your filter.

## Design Method

Lists the design methods available for the frequency and magnitude specifications you entered. When you change the specifications for a filter, such as changing the impulse response, the methods available to design filters changes as well. The default IIR design method is usually Butterworth, and the default FIR method is Equiripple.

## Scale SOS filter coefficients to reduce chance of overflow

Selecting this parameter directs the design to scale the filter coefficients to reduce the chances that the inputs or calculations in the filter overflow and exceed the representable range of the filter. Clearing this option removes the scaling. This parameter applies only to IIR filters.

## Design Options

The options for each design are specific for each design method. This section does not present all of the available options for all designs and design methods. There are many more that you encounter as you select different design methods and filter specifications. The following options represent some of the most common ones available.

## Density factor

Density factor controls the density of the frequency grid over which the design method optimization evaluates your filter response function. The number of equally spaced points in the grid is the value you enter for **Density factor** times (filter order + 1).

Increasing the value creates a filter that more closely approximates an ideal equiripple filter but increases the time required to design the filter. The default value of 20 represents a reasonable trade between the accurate approximation to the ideal filter and the time to design the filter.

# Highpass Filter

---

## Phase constraint

Specify the phase constraint of the filter as **Linear**, **Maximum**, or **Minimum**.

## Minimum order

When you select this parameter, the design method determines and design the minimum order filter to meet your specifications. Some filters do not provide this parameter. Select **Any**, **Even**, or **Odd** from the drop-down list to direct the design to be any minimum order, or minimum even order, or minimum odd order.

## Match Exactly

Specifies that the resulting filter design matches either the passband or stopband or both bands when you select passband or stopband or both from the drop-down list.

## Stopband Shape

Stopband shape lets you specify how the stopband changes with increasing frequency. Choose one of the following options:

- **Flat** — Specifies that the stopband is flat. The attenuation does not change as the frequency increases.
- **Linear** — Specifies that the stopband attenuation changes linearly as the frequency increases. Change the slope of the stopband by setting **Stopband decay**.
- **1/f** — Specifies that the stopband attenuation changes exponentially as the frequency increases, where  $f$  is the frequency. Set the power (exponent) for the decay in **Stopband decay**.

## Stopband Decay

When you set Stopband shape, Stopband decay specifies the amount of decay applied to the stopband. the following conditions apply to Stopband decay based on the value of Stopband Shape:

- When you set **Stopband shape** to Flat, **Stopband decay** has no effect on the stopband.
- When you set **Stopband shape** to Linear, enter the slope of the stopband in units of dB/rad/s. `filterbuilder` applies that slope to the stopband.
- When you set **Stopband shape** to  $1/f$ , enter a value for the exponent  $n$  in the relation  $(1/f)^n$  to define the stopband decay. `filterbuilder` applies the  $(1/f)^n$  relation to the stopband to result in an exponentially decreasing stopband attenuation.

## Filter Implementation

### Structure

For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter. By default, FIR filters use direct-form structure, and IIR filters use direct-form II filters with SOS.

### Use basic elements to enable filter customization

Select this check box to implement the filter as a subsystem of basic Simulink blocks. Clear the check box to implement the filter as a high-level subsystem. By default, this check box is cleared.

The high-level implementation provides better compatibility across various filter structures, especially filters that would contain algebraic loops when constructed using basic elements. On the other hand, using basic elements enables the following optimization parameters:

- **Optimize for zero gains** — Terminate chains that contain Gain blocks with a gain of zero.
- **Optimize for unit gains** — Remove Gain blocks that scale by a factor of one.
- **Optimize for delay chains** — Substitute delay chains made up of  $n$  unit delays with a single delay by  $n$ .

# Highpass Filter

---

- **Optimize for negative gains** — Use subtraction in Sum blocks instead of negative gains in Gain blocks.

## Optimize for unit-scale values

Select this check box to scale unit gains between sections in SOS filters. This parameter is available only for SOS filters.

## Input processing

Specify how the block should process the input. The available options may vary depending on the settings of the **Filter Structure** and **Use basic elements for filter customization** parameters. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The Inherited (this choice will be removed see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Rate options

When the **Filter type** parameter specifies a multirate filter, select the rate processing rule for the block from following options:

- **Enforce single-rate processing** — When you select this option, the block maintains the sample rate of the input.
- **Allow multirate processing** — When you select this option, the block adjusts the rate at the output to accommodate an increased or reduced number of samples. To select this option,

you must set the **Input processing** parameter to Elements as channels (sample based).

### Use symbolic names for coefficients

Select this check box to enable the specification of coefficients using MATLAB variables. The available coefficient names differ depending on the filter structure. Using symbolic names allows tuning of filter coefficients in generated code. By default, this check box is cleared.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

# Hilbert Filter

---

**Purpose** Design Hilbert filter

**Library** Filtering / Filter Designs  
dspfdesign

**Description** This block brings the filter design capabilities of the `filterbuilder` function to the Simulink environment.



**Dialog Box** See “Hilbert Filter Design Dialog Box — Main Pane” on page 7-729 for more information about the parameters of this block. The **Data Types** and **Code** panes are not available for blocks in the DSP System Toolbox Filter Designs library.

Function Block Parameters: Hilbert Filter

Hilbert Filter

Design a Hilbert filter.

[View Filter Response](#)

Filter specifications

Impulse response: FIR

Order mode: Specify Order: 31

Filter Type: Single-rate

Frequency specifications

Frequency units: Normalized (0 to 1) Input Fs: 2

Transition width .1

Magnitude specifications

No magnitude constraints can be specified when specifying a filter order.

Algorithm

Design method: Equiripple

► Design options

Filter Implementation

Structure: Direct-form FIR

Use basic elements to enable filter customization

Input processing: Columns as channels (frame based)

Use symbolic names for coefficients

OK Cancel Help Apply

## View filter response

This button opens the Filter Visualization Tool (fvtool) from the Signal Processing Toolbox product. You can use the tool to display:

- Magnitude response, phase response, and group delay in the frequency domain.
- Impulse response and step response in the time domain.
- Pole-zero information.

The tool also helps you evaluate filter performance by providing information about filter order, stability, and phase linearity. For more information on FVTool, see the Signal Processing Toolbox documentation.

## Filter Specifications

In this group, you specify your filter format, such as the impulse response and the filter order.

### Impulse response

Select either **FIR** or **IIR** from the drop-down list. **FIR** is the default. When you choose an impulse response, the design methods and structures you can use to implement your filter change accordingly.

---

**Note** The design methods and structures for **FIR** filters are not the same as the methods and structures for **IIR** filters.

---

### Filter order mode

Select either **Minimum** (the default) or **Specify** from the drop-down list. Selecting **Specify** enables the **Order** option (see the following sections) so you can enter the filter order.

### Filter type

Select **Single-rate**, **Decimator**, **Interpolator**, or **Sample-rate converter**. Your choice determines the type of filter as well as the

design methods and structures that are available to implement your filter. By default, the block specifies a single-rate filter.

- Selecting **Decimator** or **Interpolator** activates the **Decimation Factor** or the **Interpolation Factor** options respectively.
- Selecting **Sample-rate converter** activates both factors.

## Order

Enter the filter order. This option is enabled only if **Specify** was selected for **Filter order mode**.

## Decimation Factor

Enter the decimation factor. This option is enabled only if the **Filter type** is set to **Decimator** or **Sample-rate converter**. The default value is 2.

## Interpolation Factor

Enter the interpolation factor. This option is enabled only if the **Filter type** is set to **Interpolator** or **Sample-rate converter**. The default value is 2.

## Frequency Specifications

The parameters in this group allow you to specify your filter response curve.

### Frequency units

Use this parameter to specify whether your frequency settings are normalized or in absolute frequency. Select **Normalized (0 1)** to enter frequencies in normalized form. This behavior is the default. To enter frequencies in absolute values, select one of the frequency units from the drop-down list—**Hz**, **KHz**, **MHz**, or **GHz**. Selecting one of the unit options enables the **Input Fs** parameter.

### Input Fs

**F<sub>s</sub>**, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter input. When you provide an input sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is

# Hilbert Filter

---

available when you select one of the frequency options from the **Frequency units** list.

## Transition width

Specify the width of the transitions at the ends of the passband. Specify the value in normalized frequency units or the absolute units you select in **Frequency units**.

## Magnitude Specifications

Parameters in this group specify the filter response in the passbands and stopbands.

### Magnitude units

Specify the units for any parameter you provide in magnitude specifications. From the drop-down list, select one of the following options:

- Linear — Specify the magnitude in linear units.
- dB — Specify the magnitude in decibels (default)
- Squared — Specify the magnitude in squared units.

### A<sub>pass</sub>

Enter the filter ripple allowed in the passband in the units you choose for **Magnitude units**, either linear or decibels.

## Algorithm

The parameters in this group allow you to specify the design method and structure of your filter.

### Design Method

Lists the design methods available for the frequency and magnitude specifications you entered. When you change the specifications for a filter, such as changing the impulse response, the methods available to design filters changes as well. The default FIR method is Equiripple.

## Design Options

The options for each design are specific for each design method. This section does not present all of the available options for all designs and design methods. There are many more that you encounter as you select different design methods and filter specifications. The following options represent some of the most common ones available.

### Density factor

Density factor controls the density of the frequency grid over which the design method optimization evaluates your filter response function. The number of equally spaced points in the grid is the value you enter for **Density factor** times (filter order + 1).

Increasing the value creates a filter that more closely approximates an ideal equiripple filter but increases the time required to design the filter. The default value of 20 represents a reasonable trade between the accurate approximation to the ideal filter and the time to design the filter.

### FIR Type

Specify whether to design a type 3 or a type 4 FIR filter. The filter type is defined as follows:

- Type 3 — FIR filter with even order antisymmetric coefficients
- Type 4 — FIR filter with odd order antisymmetric coefficients

Select either 3 or 4 from the drop-down list.

## Filter Implementation

### Structure

For the filter specifications and design method you select, this parameter lists the filter structures available to implement your

filter. By default, FIR filters use Direct-form FIR, and IIR filters use Cascade minimum-multiplier allpass.

## Use basic elements to enable filter customization

Select this check box to implement the filter as a subsystem of basic Simulink blocks. Clear the check box to implement the filter as a high-level subsystem. By default, this check box is cleared.

The high-level implementation provides better compatibility across various filter structures, especially filters that would contain algebraic loops when constructed using basic elements. On the other hand, using basic elements enables the following optimization parameters:

- **Optimize for zero gains** — Terminate chains that contain Gain blocks with a gain of zero.
- **Optimize for unit gains** — Remove Gain blocks that scale by a factor of one.
- **Optimize for delay chains** — Substitute delay chains made up of  $n$  unit delays with a single delay by  $n$ .
- **Optimize for negative gains** — Use subtraction in Sum blocks instead of negative gains in Gain blocks.

## Input processing

Specify how the block should process the input. The available options may vary depending on the settings of the **Filter Structure** and **Use basic elements for filter customization** parameters. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The Inherited (this choice will be removed see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Rate options

When the **Filter type** parameter specifies a multirate filter, select the rate processing rule for the block from following options:

- **Enforce single-rate processing** — When you select this option, the block maintains the sample rate of the input.
- **Allow multirate processing** — When you select this option, the block adjusts the rate at the output to accommodate an increased or reduced number of samples. To select this option, you must set the **Input processing** parameter to **Elements as channels** (sample based).

## Use symbolic names for coefficients

Select this check box to enable the specification of coefficients using MATLAB variables. The available coefficient names differ depending on the filter structure. Using symbolic names allows tuning of filter coefficients in generated code. By default, this check box is cleared.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

# Histogram

## Purpose



Generate histogram of input or sequence of inputs

## Library

Statistics

dspstat3

## Description



The Histogram block computes the frequency distribution of the elements in the input. You must use the **Find the histogram over** parameter to specify whether the block computes the histogram for Each column of the input or of the Entire input. The **Running histogram** check box allows you to select between basic operation and running operation, as described below.

The block distributes the elements of the input into the number of discrete bins specified by the **Number of bins** parameter,  $n$ .

```
y = hist(u,n)    % Equivalent MATLAB code
```

The Histogram block sorts all complex input values into bins according to their magnitude.

The histogram value for a given bin represents the frequency of occurrence of the input values bracketed by that bin. You specify the upper boundary of the highest-valued bin in the **Upper limit of histogram** parameter,  $B_M$ , and the lower boundary of the lowest-valued bin in the **Lower limit of histogram** parameter,  $B_m$ . The bins have equal width of

$$\Delta = \frac{B_M - B_m}{n}$$

and centers located at

$$B_m + \left(k + \frac{1}{2}\right)\Delta \quad k = 0, 1, 2, \dots, n - 1$$

Input values that fall on the border between two bins are placed into the lower valued bin; that is, each bin includes its upper boundary.

For example, a bin of width 4 centered on the value 5 contains the input value 7, but not the input value 3. Input values greater than the **Upper limit of histogram** parameter or less than **Lower limit of histogram** parameter are placed into the highest valued or lowest valued bin, respectively.

The values you enter for the **Upper limit of histogram** and **Lower limit of histogram** parameters must be real-valued scalars. NaN and inf are not valid values for the **Upper limit of histogram** and **Lower limit of histogram** parameters.

## Basic Operation

When the **Running histogram** check box is not selected, the Histogram block computes the frequency distribution of the current input.

When you set the **Find the histogram over** parameter to **Each column**, the Histogram block computes a histogram for each column of the  $M$ -by- $N$  matrix independently. The block outputs an  $n$ -by- $N$  matrix, where  $n$  is the **Number of bins** you specify. The  $j$ th column of the output matrix contains the histogram for the data in the  $j$ th column of the  $M$ -by- $N$  input matrix.

When you set the **Find the histogram over** parameter to **Entire input**, the Histogram block computes the frequency distribution for the entire input vector, matrix or N-D array. The block outputs an  $n$ -by-1 vector, where  $n$  is the **Number of bins** you specify.

## Running Operation

When you select the **Running histogram** check box, the Histogram block computes the frequency distribution of both the past and present data for successive inputs. The block resets the histogram (by emptying all of the bins) when it detects a reset event at the optional Rst port. See “Resetting the Running Histogram” on page 2-754 for more information on how to trigger a reset.

When you set the **Find the histogram over** parameter to **Each column**, the Histogram block computes a running histogram for each column of the  $M$ -by- $N$  matrix. The block outputs an  $n$ -by- $N$  matrix, where  $n$  is the **Number of bins** you specify. The  $j$ th column of the

# Histogram

---

output matrix contains the running histogram for the  $j$ th column of the  $M$ -by- $N$  input matrix.

When you set the **Find the histogram over** parameter to **Entire input**, the Histogram block computes a running histogram for the data in the first dimension of the input. The block outputs an  $n$ -by-1 vector, where  $n$  is the **Number of bins** you specify.

---

**Note** When the Histogram block is used in running mode and the input data type is non-floating point, the output of the histogram is stored as a `uint32` data type. The largest number that can be represented by this data type is  $2^{32} - 1$ . If the range of the `uint32` data type is exceeded, the output data will wrap back to 0.


---

## Resetting the Running Histogram


The block resets the running histogram whenever a reset event is detected at the optional Rst port. The reset signal and the input data signal must be the same rate.

You specify the reset event using the **Reset port** menu:

- **None** — Disables the Rst port
- **Rising edge** — Triggers a reset operation when the Rst input does one of the following:
  - Rises from a negative value to a positive value or zero
  - Rises from zero to a positive value, where the rise is not a continuation of a rise from a negative value to zero (see the following figure)



- **Falling edge** — Triggers a reset operation when the Rst input does one of the following:
  - Falls from a positive value to a negative value or zero
  - Falls from zero to a negative value, where the fall is not a continuation of a fall from a positive value to zero (see the following figure)



- **Either edge** — Triggers a reset operation when the Rst input is a Rising edge or Falling edge (as described earlier)
- **Non-zero sample** — Triggers a reset operation at each sample time that the Rst input is not zero

# Histogram

---

## Examples

### Real Input Data

The bin boundaries created by the Histogram block are determined by the data type of the input:

- Bin boundaries for real, double-precision input are cast into the data type `double`.
- Bin boundaries for real, fixed-point input are cast into the `int8` data type.

The following example shows the differences in the output of the Histogram block based on the data type of the input.

To create this model you need the following blocks.

Block	Library	Quantity
Constant	Simulink /Sources library	2
Display	Sinks	2
Histogram	Statistics	2

The parameter settings for the Double Precision Input Constant block are:

- **Constant value** = `double([1 2 3 4 5]')`
- **Interpret vector parameters as 1-D** = Clear this check box.
- **Sampling mode** = `Sample based`
- **Sample time** = `inf`

The parameter settings for the Fixed-Point Input Constant block are:


- **Constant value** = `int8([1 2 3 4 5]')`
- **Interpret vector parameters as 1-D** = Clear this check box.
- **Sampling mode** = `Sample based`

- **Sample time** = inf

The parameter settings for both Histogram blocks are:

- **Lower limit of histogram** = 1
- **Upper limit of histogram** = 3
- **Number of bins** = 5
- **Find the histogram over** = Entire input
- **Normalized** = Clear this check box.
- **Running histogram** = Clear this check box.

Connect the blocks as shown in the following figure, and run your model.



Running the fixed-point model generates the following warning:

Warning: The bin width resulting from the specified parameters is less than the precision of the input data type. This might cause unexpected results. Since bin width is calculated by  $((\text{upper limit} - \text{lower limit})/\text{number})$

# Histogram


---

of bins), you could increase upper limit or decrease lower limit or number of bins.

This warning alerts you that it is not a good use case to have a histogram where 2 or more bin boundaries are the same. As the warning suggests, increasing the range of the limits of the histogram, or decreasing the number of bins, can correct this problem.

## Dialog Box

The **Main** pane of the Histogram block dialog appears as follows.



### Lower limit of histogram

Enter a real-valued scalar for the lower boundary,  $B_m$ , of the lowest-valued bin. NaN and inf are not valid values for  $B_m$ . Tunable.

# Histogram

---

## Upper limit of histogram

Enter a real-valued scalar for the upper boundary,  $B_M$ , of the highest-valued bin. NaN and inf are not valid values for  $B_M$ . Tunable.

## Number of bins

The number of bins,  $n$ , in the histogram.

## Find the histogram over

Specify whether the block finds the histogram over the entire input or along each column of the input.

---

**Note** The Inherited (this choice will be removed - see release notes) option will be removed in a future release.

---

## Normalized

When selected, the output vector,  $v$ , is normalized such that  $\text{sum}(v) = 1$ .

Use of this parameter is not supported for fixed-point signals.


## Running histogram

Set to enable the running histogram operation, and clear to enable basic histogram operation. For more information, see “Basic Operation” on page 2-753 and “Running Operation” on page 2-753.

## Reset port

The type of event that resets the running histogram. For more information, see “Resetting the Running Histogram” on page 2-754. The reset signal and the input data signal must be the same rate. This parameter is enabled only when you select the **Running histogram** check box. For more information, see “Running Operation” on page 2-753.

The **Data Types** pane of the Histogram block dialog appears as follows.



---

**Note** The fixed-point parameters listed are only used for fixed-point complex inputs, which are distributed by squared magnitude.

---

## Rounding mode

Select the rounding mode for fixed-point operations.

## Overflow mode

Select the overflow mode for fixed-point operations.

## Product output data type

Specify the product output data type. See “Multiplication Data Types” for illustrations depicting the use of the product output data type. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`


Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Accumulator data type

Specify the accumulator data type. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

### Supported Data Types

Port	Supported Data Types
In	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed and unsigned)</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>
Output	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• 32-bit unsigned integers</li> </ul>
Rst	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>

### See Also

Sort	DSP System Toolbox
hist	MATLAB

**Purpose** Inverse discrete cosine transform (IDCT) of input

**Library** Transforms  
dspxfm3

## Description



The IDCT block computes the inverse discrete cosine transform (IDCT) of each channel in the  $M$ -by- $N$  input matrix,  $u$ .

`y = idct(u)`      % Equivalent MATLAB code

When the input is a sample-based row vector, the IDCT block computes the inverse discrete cosine transform across the vector dimension of the input. For all other N-D input arrays, the block computes the IDCT across the first dimension. The size of the first dimension (frame size), must be a power of two. To work with other frame sizes, use the Pad block to pad or truncate the frame size to a power-of-two length.

When the input is an  $M$ -by- $N$  matrix, the block treats each input column as an independent channel containing  $M$  consecutive samples. The block outputs an  $M$ -by- $N$  matrix whose  $l$ th column contains the length- $M$  IDCT of the corresponding input column.

$$y(m, l) = \sum_{k=1}^M w(k)u(k, l) \cos \frac{\pi(2m-1)(k-1)}{2M}, \quad m = 1, \dots, M$$

where

$$w(k) = \begin{cases} 1, & k = 1 \\ \sqrt{M}, & \\ \sqrt{\frac{2}{M}}, & 2 \leq k \leq M \end{cases}$$

The **Output sampling mode** parameter allows you to select the sampling mode of the output. If the input is an N-D array with 3 or

more dimensions, the **Output sampling mode** must be `Sample` based. The output sample rate and data type (real/complex) are the same as those of the input.

The **Sine and cosine computation** parameter determines how the block computes the necessary sine and cosine values. This parameter has two settings, each with its advantages and disadvantages, as described in the following table.




<b>Sine and Cosine Computation Parameter Setting</b>	<b>Sine and Cosine Computation Method</b>	<b>Effect on Block Performance</b>
Table lookup	The block computes and stores the trigonometric values before the simulation starts, and retrieves them during the simulation. When you generate code from the block, the processor running the generated code stores the trigonometric values computed by the block in a speed-optimized table, and retrieves the values during code execution.	The block usually runs much more quickly, but requires extra memory for storing the precomputed trigonometric values.
Trigonometric fcn	The block computes sine and cosine values during the simulation. When you generate code from the block, the processor running the generated code computes the sine and cosine values while the code runs.	The block usually runs more slowly, but does not need extra data memory. For code generation, the block requires a support library to emulate the trigonometric functions, increasing the size of the generated code.

### Fixed-Point Data Types


The following diagrams show the data types used within the IDCT block for fixed-point signals. You can set the sine table, accumulator, product

output, and output data types displayed in the diagrams in the IDCT block dialog as discussed in “Dialog Box” on page 2-769.


Inputs to the IDCT block are first cast to the output data type and stored in the output buffer. Each butterfly stage processes signals in the accumulator data type, with the final output of the butterfly being cast back into the output data type.



**Butterfly Stage Data Types**



**Twiddle Multiplication Data Types**



The output of the multiplier is in the product output data type when at least one of the inputs to the multiplier is real. When both of the

inputs to the multiplier are complex, the result of the multiplication is in the accumulator data type. For details on the complex multiplication performed, see “Multiplication Data Types”.


---

**Note** When the block input is fixed point, all internal data types are signed fixed point.

---

## Dialog Box

The **Main** pane of the IDCT block dialog appears as follows.



### Sine and cosine computation

Sets the block to compute sines and cosines by either looking up sine and cosine values in a speed-optimized table (**Table lookup**),

or by making sine and cosine function calls (Trigonometric fcn).

See the table in the “Description ” on page 2-764 section.

### **Output sampling mode**

Select **Sample based** or **Frame based** output. If the input to the IDCT block has 3 or more dimensions, you must select **Sample based** output.

The **Data Types** pane of the IDCT block dialog appears as follows.

**Function Block Parameters: IDCT**

IDCT

Compute the inverse discrete cosine transform (IDCT) across the first dimension of the input. The first dimension of the input must have a power-of-two length.

Main | Data Types

Fixed-point operational parameters

Rounding mode:  Overflow mode:

Floating-point inheritance takes precedence over the settings in the 'Data Type' column below. When the block input is floating point, all block data types match the input. When the block input is fixed point, all internal data types are signed fixed point.

	Data Type	Assistant	Minimum	Maximum
Sine table:	<input type="text" value="Inherit: Same word length as input"/>	<input type="text" value="&gt;&gt;"/>		
Product output:	<input type="text" value="Inherit: Inherit via internal rule"/>	<input type="text" value="&gt;&gt;"/>		
Accumulator:	<input type="text" value="Inherit: Inherit via internal rule"/>	<input type="text" value="&gt;&gt;"/>		
Output:	<input type="text" value="Inherit: Inherit via internal rule"/>	<input type="text" value="&gt;&gt;"/>	<input type="text" value="0"/>	<input type="text" value="0"/>

Lock data type settings against changes by the fixed-point tools

? OK Cancel Help Apply

### Rounding mode

Select the rounding mode for fixed-point operations. The sine table values do not obey this parameter; they always round to Nearest.

## Overflow mode

Select the overflow mode for fixed-point operations. The sine table values do not obey this parameter; instead, they are always saturated.

## Sine table data type

Choose how you specify the word length of the values of the sine table. The fraction length of the sine table values always equals the word length minus one. You can set this parameter to:


- A rule that inherits a data type, for example, `Inherit: Same word length as input`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16)`

The sine table values do not obey the **Rounding mode** and **Overflow mode** parameters; instead, they are always saturated and rounded to Nearest.

## Product output data type

Specify the product output data type. See “Fixed-Point Data Types” on page 2-765 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

### Accumulator data type

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-765 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

### Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-765 for illustrations depicting the use of the output data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`.

When you select `Inherit: Inherit via internal rule`, the block calculates the output word length and fraction length automatically. The internal rule first calculates an ideal output word length and fraction length using the following equations:


$$WL_{ideal\ output} = WL_{input} + \text{floor}(\log_2(DCT\ length - 1)) + 1$$

$$FL_{ideal\ output} = FL_{input}$$

Using these ideal results, the internal rule then selects word lengths and fraction lengths that are appropriate for your

hardware. For more information, see “Inherit via Internal Rule”.

- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

### Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed and unsigned)</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>
Output	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed only)</li> <li>• 8-, 16-, and 32-bit signed integers</li> </ul>

**See Also**

DCT

DSP System Toolbox

IFFT

DSP System Toolbox

idct

Signal Processing Toolbox

# Identity Matrix

---


## Purpose

Generate matrix with ones on main diagonal and zeros elsewhere

## Library

- Sources  
dspsrcs4
- Math Functions / Matrices and Linear Algebra / Matrix Operations  
dspmtx3

## Description



The Identity Matrix block generates a rectangular matrix with ones on the main diagonal and zeros elsewhere.

When you select the **Inherit output port attributes from input port** check box, the input port is enabled, and an  $M$ -by- $N$  matrix input generates an  $M$ -by- $N$  matrix output with the same sample period as the input. The values in the input matrix are ignored.

```
y = eye([M N]) % Equivalent MATLAB code
```

When you do not select the **Inherit output port attributes from input port** check box, the input port is disabled, and the dimensions of the output matrix are determined by the **Matrix size** parameter. A scalar value,  $M$ , specifies an  $M$ -by- $M$  identity matrix, while a two-element vector,  $[M N]$ , specifies an  $M$ -by- $N$  unit-diagonal matrix. You can specify the output sample period using the **Sample time** parameter.


## Examples

Set **Matrix size** to  $[3 \ 6]$  to generate the 3-by-6 unit-diagonal matrix below.

$$\begin{bmatrix} 1 & 0 & 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 & 0 \end{bmatrix}$$

## Dialog Box

The **Main** pane of the Identity Matrix block dialog appears as follows.



### **Inherit output port attributes from input port**

Enables the input port when selected. In this mode, the output inherits its dimensions, sample period, and data type from the input. The output is always real.

### **Matrix size**

The number of rows and columns in the output matrix: a scalar  $M$  for a square  $M$ -by- $M$  output, or a vector  $[M\ N]$  for an  $M$ -by- $N$  output. This parameter is disabled when you select **Inherit input port attributes from input port**.


# Identity Matrix

---

## Sample time

The discrete sample period of the output. This parameter is disabled when you select **Inherit input port attributes from input port**.

The **Data Types** pane of the Identity Matrix block dialog appears as follows.



## Output data type

Specify the output data type for this block. You can select one of the following:

- A rule that inherits a data type, for example, **Inherit**:  
Inherit via back propagation. When you select this option,

the output data type and scaling matches that of the next downstream block.

- A built in data type, such as `double`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>
Output	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>

# Identity Matrix

---

## See Also

Constant Diagonal Matrix

DSP System Toolbox

Constant

Simulink

eye

MATLAB



## Purpose

Inverse discrete wavelet transform (IDWT) of input or reconstruct signals from subbands with smaller bandwidths and slower sample rates

## Library

Transforms  
dspxfm3

## Description



The IDWT block is the same as the Dyadic Synthesis Filter Bank block in the Multirate Filters library, but with different default settings. See the Dyadic Synthesis Filter Bank block reference page for more information on how to use the block.

# IFFT

---

**Purpose** Inverse fast Fourier transform (IFFT) of input

**Library** Transforms  
dspxfm3

**Description** The IFFT block computes the inverse fast Fourier transform (IFFT) of each row of a sample-based 1-by- $P$  input vector, or across the first dimension ( $P$ ) of an  $N$ - $D$  input array.

When you specify an FFT length not equal to the length of the input vector, (or first dimension of the input array), the block implements zero padding or modulo- $M$ , (FFT length) data wrapping. This occurs before the IFFT operation, as per Orfanidis [1].

```
y = ifft(u,M) % P M
```

```
y(:,l) = ifft(datawrap(u(:,l),M)) % P > M; l = 1,...,N
```

When the input length,  $P$ , is greater than the FFT length,  $M$ , you may see magnitude increases in your IFFT output. These magnitude increases occur because the IFFT block uses modulo- $M$  data wrapping to preserve all available input samples.

To avoid such magnitude increases, you can truncate the length of your input sample,  $P$ , to the FFT length,  $M$ . To do so, place a Pad block before the IFFT block in your model.

The  $k$ th entry of the  $l$ th output channel,  $y(k, l)$ , is equal to the  $k$ th point of the  $M$ -point inverse discrete Fourier transform (IDFT) of the  $l$ th input channel:

$$y(k, l) = \frac{1}{M} \sum_{p=1}^P u(p, l) e^{j2\pi(p-1)(k-1)/M} \quad k = 1, \dots, M$$

The output of this block has the same dimensions as the input. If the input signal has a floating-point data type, the data type of the output signal uses the same floating-point data type. Otherwise, the

output can be any fixed-point data type. The block computes scaled and unscaled versions of the IFFT.

The input to this block can be floating-point or fixed-point, real or complex, and conjugate symmetric. The block uses one of two possible FFT implementations. You can select an implementation based on the FFTW library [1], [2], or an implementation based on a collection of Radix-2 algorithms. You can select Auto to allow the block to choose the implementation.

### **FFTW Implementation**

The FFTW implementation provides an optimized FFT calculation including support for power-of-two and non-power-of-two transform lengths in both simulation and code generation. Generated code using the FFTW implementation will be restricted to MATLAB host computers. The data type must be floating-point. Refer to Simulink Coder for more details on generating code.

### **Radix-2 Implementation**

The Radix-2 implementation supports bit-reversed processing, fixed or floating-point data, and allows the block to provide portable C-code generation using the Simulink Coder. The dimension  $M$  of the  $M$ -by- $N$  input matrix, must be a power of two. To work with other input sizes, use the Pad block to pad or truncate these dimensions to powers of two, or if possible choose the FFTW implementation.

With Radix-2 selected, the block implements one or more of the following algorithms:

- Butterfly operation
- Double-signal algorithm
- Half-length algorithm
- Radix-2 decimation-in-time (DIT) algorithm
- Radix-2 decimation-in-frequency (DIF) algorithm

## Radix-2 Algorithms for Real or Complex Input Complexity

Parameter Settings	Algorithms Used for IFFT Computation
<input type="checkbox"/> Input is in bit-reversed order <input type="checkbox"/> Input is conjugate symmetric	Bit-reversal operation and radix-2 DIT
<input checked="" type="checkbox"/> Input is in bit-reversed order <input type="checkbox"/> Input is conjugate symmetric	Radix-2 DIT
<input type="checkbox"/> Input is in bit-reversed order <input checked="" type="checkbox"/> Input is conjugate symmetric	Bit-reversal operation and radix-2 DIT in conjunction with the half-length and double-signal algorithms
<input checked="" type="checkbox"/> Input is in bit-reversed order <input checked="" type="checkbox"/> Input is conjugate symmetric	Radix-2 DIT in conjunction with the half-length and double-signal algorithms

## Radix-2 Optimization for the Table of Trigonometric Values

In certain situations, the block's Radix-2 algorithm computes all the possible trigonometric values of the twiddle factor

$$e^{j\frac{2\pi k}{K}}$$

where  $K$  is the greater value of either  $M$  or  $N$  and  $k = 0, \dots, K - 1$ . The block stores these values in a table and retrieves them during simulation. The number of table entries for fixed-point and floating-point is summarized in the following table:

<b>Number of Table Entries for N-Point FFT</b>	
floating-point	3 $N/4$
fixed-point	$N$


### **Fixed-Point Data Types**

The following diagrams show the data types used in the IFFT block for fixed-point signals. You can set the sine table, accumulator, product output, and output data types displayed in the diagrams in the IFFT dialog box as discussed in “Dialog Box” on page 2-790.


Inputs to the IFFT block are first cast to the output data type and stored in the output buffer. Each butterfly stage then processes signals in the accumulator data type, with the final output of the butterfly being cast back into the output data type. The block multiplies in a twiddle factor before each butterfly stage in a decimation-in-time IFFT and after each butterfly stage in a decimation-in-frequency IFFT.

# IFFT


## Decimation-in-time IFFT



## Decimation-in-frequency IFFT



## Butterfly stage data types



## Twiddle multiplication data types



The multiplier output appears in the accumulator data type because both of the inputs to the multiplier are complex. For details on the complex multiplication performed, refer to "Multiplication Data Types" in the DSP System Toolbox documentation.


### Fixed-Point Data Types

The following diagrams show the data types used within the IFFT block for fixed-point signals. You can set the sine table, accumulator, product output, and output data types displayed in the diagrams in the IFFT block dialog, as discussed in “Dialog Box” on page 2-790.


The IFFT block first casts input to the output data type and then stores it in the output buffer. Each butterfly stage then processes signals in the accumulator data type, with the final output of the butterfly being cast back into the output data type. The block multiplies in a twiddle factor before each butterfly stage in a decimation-in-time IFFT, and after each butterfly stage in a decimation-in-frequency IFFT.

# IFFT


## Decimation-in-time IFFT



## Decimation-in-frequency IFFT



## Butterfly stage data types



## Twiddle multiplication data types



The output of the multiplier is in the accumulator data type because both of the inputs to the multiplier are complex. For details on the complex multiplication performed, see "Multiplication Data Types".

---


**Note** When the block input is fixed point, all internal data types are signed fixed point.

---

# IFFT

## Dialog Box

The **Main** pane of the IFFT block dialog appears as follows.



### FFT implementation

Set this parameter to FFTW [1], [2] to support an arbitrary length input signal. The block restricts generated code with FFTW implementation to MATLAB host computers.

Set this parameter to Radix-2 for bit-reversed processing, fixed or floating-point data, or for portable C-code generation using the Simulink Coder. The dimension  $M$  of the  $M$ -by- $N$  input matrix, must be a power of two. To work with other input sizes, use the Pad block to pad or truncate these dimensions to powers of two, or if possible choose the FFTW implementation. See “Radix-2 Implementation” on page 2-783.

Set this parameter to Auto to let the block choose the FFT implementation. For non-power-of-two transform lengths, the block restricts generated code to MATLAB host computers.

### Input is in bit-reversed order

Select or clear this check box to designate the order of the input channel elements. Select this check box when the input should appear in reversed order, and clear it when the input should appear in linear order. The block yields invalid outputs when you do not set this parameter correctly. This check box only appears when you set the **FFT implementation** parameter to Radix-2 or Auto.

You cannot select this check box if you have cleared the **Inherit FFT length from input dimensions** check box, and you are specifying the FFT length using the **FFT length** parameter. Also, it cannot be selected when you set the **FFT implementation** parameter to FFTW.

For more information on ordering of the output, see “Linear and Bit-Reversed Output Order”.

## Input is conjugate symmetric

Select this option when the block inputs conjugate symmetric data and you want real-valued outputs. Selecting this check box optimizes the block's computation method.

The FFT block yields conjugate symmetric output when you input real-valued data. Taking the IFFT of a conjugate symmetric input matrix produces real-valued output. Therefore, if the input to the block is both floating point and conjugate symmetric, and you select the this check box, the block produces real-valued outputs.

You cannot select this check box if you have cleared the **Inherit FFT length from input dimensions** check box, and you are specifying the FFT length using the **FFT length** parameter.

If you input conjugate symmetric data to the IFFT block and do not select this check box, the IFFT block outputs a complex-valued signal with small imaginary parts. The block outputs invalid data if you select this option with non conjugate symmetric input data.

## Divide output by FFT length

When you select this check box, the block computes its output according to the IDFT equation, discussed in the Description section.

When you clear this check box, the block computes the output using a modified version of the IDFT:  $M \cdot y(k,l)$ , which is defined by the following equation:

$$M \cdot y(k,l) = \sum_{p=1}^P u(p,l) e^{j2\pi(p-1)(k-1)/M} \quad k = 1, \dots, M$$

Notice, the modified IDFT equation does not include the multiplication factor of  $1/M$ .

**Inherit FFT length from input dimensions**

Select to inherit the FFT length from the input dimensions. If you do not select this parameter, the **FFT length** parameter becomes available to specify the length. You cannot clear this parameter when you select either the **Input is in bit-reversed order** or the **Input is conjugate symmetric** parameter.

**FFT length**

Specify FFT length. This parameter only becomes available if you do not select the **Inherit FFT length from input dimensions** parameter.

When you set the **FFT implementation** parameter to Radix-2, or when you check the **Output in bit-reversed order** check box, this value must be a power of two.


o

**Output sampling mode**

Select **Sample based** or **Frame based** output. If the input to the IFFT block has 3 or more dimensions, you must select **Sample based** output.

The **Data Types** pane of the IFFT block dialog appears as follows.

# IFFT



**Rounding mode**

Select the rounding mode for fixed-point operations. The sine table values do not obey this parameter; instead, they always round to Nearest.

**Overflow mode**

Select the overflow mode for fixed-point operations. The sine table values do not obey this parameter; instead, they are always saturated.

**Sine table data type**

Choose how you specify the word length of the values of the sine table. The fraction length of the sine table values always equals the word length minus one. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Same word length as input`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16)`

The sine table values do not obey the **Rounding mode** and **Overflow mode** parameters; instead, they are always saturated and rounded to Nearest.

**Product output data type**

Specify the product output data type. See “Fixed-Point Data Types” on page 2-787 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Accumulator data type

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-787 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-787 for illustrations depicting the use of the output data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`.

When you select `Inherit: Inherit via internal rule`, the block calculates the output word length and fraction length automatically. The equations that the block uses to calculate the ideal output word length and fraction length depend on the setting of the **Divide output by FFT length** check box.

- When you select the **Divide output by FFT length** check box, the ideal output word and fraction lengths are the same as the input word and fraction lengths.

- When you clear the **Divide output by FFT length** check box, the block computes the ideal output word and fraction lengths according to the following equations:

$$WL_{ideal\ output} = WL_{input} + \text{floor}(\log_2(\text{FFT length} - 1)) + 1$$

$$FL_{ideal\ output} = FL_{input}$$

Using these ideal results, the internal rule then selects word lengths and fraction lengths that are appropriate for your hardware. For more information, see “Inherit via Internal Rule”.

- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

#### **Lock data type settings against changes by the fixed-point tools**

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## **Examples**

See “Transform Frequency-Domain Data into Time Domain” in the *DSP System Toolbox User’s Guide*.

## **References**

- [1] Orfanidis, S. J. *Introduction to Signal Processing*. Upper Saddle River, NJ: Prentice Hall, 1996, p. 497.
- [2] Proakis, John G. and Dimitris G. Manolakis. *Digital Signal Processing*, 3rd ed. Upper Saddle River, NJ: Prentice Hall, 1996.

[3] FFTW (<http://www.fftw.org>)

[4] Frigo, M. and S. G. Johnson, "FFTW: An Adaptive Software Architecture for the FFT," *Proceedings of the International Conference on Acoustics, Speech, and Signal Processing*, Vol. 3, 1998, pp. 1381-1384.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>

## References

[1] FFTW (<http://www.fftw.org>)

[2] Frigo, M. and S. G. Johnson, "FFTW: An Adaptive Software Architecture for the FFT," *Proceedings of the International Conference on Acoustics, Speech, and Signal Processing*, Vol. 3, 1998, pp. 1381-1384.

## See Also

FFT	DSP System Toolbox
IDCT	DSP System Toolbox
Pad	DSP System Toolbox
bitrevorder	Signal Processing Toolbox

`fft`

MATLAB

`ifft`

MATLAB

# Inherit Complexity

## Purpose

Change complexity of input to match reference signal

## Library


Signal Management / Signal Attributes

dspsigattribs


## Description



The Inherit Complexity block alters the input data at the Data port to match the complexity of the reference input at the Ref port. When the Data input is real, and the Ref input is complex, the block appends a zero-valued imaginary component,  $0i$ , to each element of the Data input.




When the Data input is complex, and the Ref input is real, the block outputs the real component of the Data input.



When both the Data input and Ref input are real, or when both the Data input and Ref input are complex, the block propagates the Data input with no change.

## Dialog Box



## Supported Data Types

Port	Supported Data Types
Data	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Ref	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

# Inherit Complexity

---

Port	Supported Data Types
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>


## See Also

Check Signal Attributes	DSP System Toolbox
Complex to Magnitude-Angle	Simulink
Complex to Real-Imag	Simulink
Magnitude-Angle to Complex	Simulink
Real-Imag to Complex	Simulink

**Purpose** Delay input by integer number of sample periods

**Library** dspobslib

## Description



---

**Note** The Integer Delay block will be removed from the product in a future release. We strongly recommend replacing this block with the Delay block.

---

The Integer Delay block delays a discrete-time input by the number of sample intervals specified in the **Delay** parameter. Noninteger delay values are rounded to the nearest integer, and negative delays are clipped at 0.

### Sample-Based Operation

When the input is a sample-based  $M$ -by- $N$  matrix, the block treats each of the  $M*N$  matrix elements as an independent channel. The **Delay** parameter,  $v$ , can be an  $M$ -by- $N$  matrix of positive integers that specifies the number of sample intervals to delay each channel of the input, or a scalar integer by which to equally delay all channels.

For example, when the input is  $M$ -by-1 and  $v$  is the matrix  $[v(1) \ v(2) \ \dots \ v(M)]'$ , the first channel is delayed by  $v(1)$  sample intervals, the second channel is delayed by  $v(2)$  sample intervals, and so on. Note that when a channel is delayed for  $\Delta$  sample-time units, the output sample at time  $t$  is the input sample at time  $t - \Delta$ . When  $t - \Delta$  is negative, then the output is the corresponding value specified by the **Initial conditions** parameter.

A 1-D vector of length  $M$  is treated as an  $M$ -by-1 matrix, and the output is 1-D.

The **Initial conditions** parameter specifies the output of the block during the initial delay in each channel. The initial delay for a particular channel is the time elapsed from the start of the simulation until the first input in that channel is propagated to the output. Both

# Integer Delay (Obsolete)


---

fixed and time-varying initial conditions can be specified in a variety of ways to suit the dimensions of the input.

## Fixed Initial Conditions

A fixed initial condition in sample-based mode can be specified as one of the following:

- Scalar value to be repeated at each sample time of the initial delay (for every channel). For a 2-by-2 input with the parameter settings below,



the block generates the following sequence of matrices at the start of the simulation,

$$\begin{bmatrix} -1 & -1 \\ -1 & -1 \end{bmatrix}, \begin{bmatrix} u_{11}^1 & -1 \\ -1 & -1 \end{bmatrix}, \begin{bmatrix} u_{11}^2 & u_{12}^1 \\ -1 & -1 \end{bmatrix}, \begin{bmatrix} u_{11}^3 & u_{12}^2 \\ u_{21}^1 & -1 \end{bmatrix}, \begin{bmatrix} u_{11}^4 & u_{12}^3 \\ u_{21}^2 & u_{22}^1 \end{bmatrix}, \dots$$

where  $u_{ij}^k$  is the  $i,j$ th element of the  $k$ th matrix in the input sequence.

- Array of size  $M$ -by- $N$ -by- $d$ . In this case, you can set different fixed initial conditions for each element of a sample-based input. This setting is explained further in the Array bullet in “Time-Varying Initial Conditions” on page 2-804.

Initial conditions cannot be specified by full matrices.

## Time-Varying Initial Conditions

A time-varying initial condition in sample-based mode can be specified in one of the following ways:

- Vector of length  $d$ , where  $d$  is the maximum value specified for any channel in the **Delay** parameter. The vector can be a  $L$ -by- $d$ , 1-by- $d$ , or 1-by-1-by- $d$ . The  $d$  elements of the vector are output in sequence, one at each sample time of the initial delay.

For a scalar input and the parameters shown below,

Delay (samples):  
5  
Initial conditions:  
[-1 -1 0 1]

the block outputs the sequence  $-1, -1, -1, 0, 1, \dots$  at the start of the simulation.

- Array of dimension  $M$ -by- $N$ -by- $d$ , where  $d$  is the value specified for the **Delay** parameter (the maximum value when the **Delay** is a vector) and  $M$  and  $N$  are the number of rows and columns, respectively, in the input matrix. The  $d$  pages of the array are output in sequence, one at each sample time of the initial delay. For a 2-by-3 input, and the parameters below,

Delay (samples):  
3  
Initial conditions:  
cat(3, [1 2 3; 4 5 6], [2 4 6; 1 3 5], [3 6 9; 0 4 8])

the block outputs the matrix sequence

$$\begin{bmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \end{bmatrix}, \begin{bmatrix} 2 & 4 & 6 \\ 1 & 3 & 5 \end{bmatrix}, \begin{bmatrix} 3 & 6 & 9 \\ 0 & 4 & 8 \end{bmatrix}$$

at the start of the simulation. Note that setting **Initial conditions** to an array with the same matrix for each entry implements constant initial conditions; a different constant initial condition for each input matrix element (channel).

Initial conditions cannot be specified by full matrices.

# Integer Delay (Obsolete)

---

## Frame-Based Operation

When the input is a frame-based  $M$ -by- $N$  matrix, the block treats each of the  $N$  columns as an independent channel, and delays each channel as specified by the **Delay** parameter.

For frame-based inputs, the **Delay** parameter can be a scalar integer by which to equally delay all channels. It can also be a 1-by- $N$  row vector, each element of which serves as the delay for the corresponding channel of the  $N$ -channel input. Likewise, it can also be an  $M$ -by-1 column vector, each element of which serves as the delay for one of the corresponding  $M$  samples for each channel. The **Delay** parameter can be an  $M$ -by- $N$  matrix of positive integers as well; in this case, each element of each channel is delayed by the corresponding element in the delay matrix. For instance, if the fifth element of the third column of the delay matrix was 3, then the fifth element of the third channel of the input matrix is always delayed by three sample-time units.


When a channel is delayed for  $\Delta$  sample-time units, the output sample at time  $t$  is the input sample at time  $t - \Delta$ . When  $t - \Delta$  is negative, then the output is the corresponding value specified in the **Initial conditions** parameter.

The **Initial conditions** parameter specifies the output during the initial delay. Both fixed and time-varying initial conditions can be specified. The initial delay for a particular channel is the time elapsed from the start of the simulation until the first input in that channel is propagated to the output.

## Fixed Initial Conditions

The settings shown below specify fixed initial conditions. The value entered in the **Initial conditions** parameter is repeated at the output for each sample time of the initial delay. A fixed initial condition in frame-based mode can be one of the following:

- Scalar value to be repeated for all channels of the output at each sample time of the initial delay. For a general  $M$ -by- $N$  input with the parameter settings below,



Delay (samples):  
5

Initial conditions:  
0

the first five samples in each of the  $N$  channels are zero. Notice that when the frame size is larger than the delay, all of these zeros are all included in the first output from the block.

- Array of size 1-by- $N$ -by- $D$ . In this case, you can also specify different fixed initial conditions for each channel. See “Time-Varying Initial Conditions” on page 2-807 for details.

Initial conditions cannot be specified by full matrices.


## Time-Varying Initial Conditions

The following settings specify time-varying initial conditions. For time-varying initial conditions, the values specified in the **Initial conditions** parameter are output in sequence during the initial delay. A time-varying initial condition in frame-based mode can be specified in the following ways:

- Vector of length  $D$ , where each of the  $N$  channels have the same initial conditions sequence specified in the vector.  $D$  is defined as follows:
  - When an element of the delay entry is less than the frame size,  
$$D = d + 1$$
where  $d$  is the maximum delay.
  - When the all elements of the delay entry are greater than the input frame size,  
$$D = d + \text{input frame size} - 1$$

Only the first  $d$  entries of the initial condition vector are used; the rest of the values are ignored, but you must include them nonetheless. For a two-channel ramp input `[1:100; 1:100]'` with a frame size of 4 and the parameter settings below,

# Integer Delay (Obsolete)




the block outputs the following sequence of frames at the start of the simulation.

$$\begin{bmatrix} -4 & -1 \\ -5 & -2 \\ 1 & -3 \\ 2 & -4 \end{bmatrix}, \begin{bmatrix} 3 & -5 \\ 4 & 1 \\ 5 & 2 \\ 6 & 3 \end{bmatrix}, \begin{bmatrix} 7 & 4 \\ 8 & 5 \\ 9 & 6 \\ 10 & 7 \end{bmatrix}, \dots$$

Note that since one of the delays, 2, is less than the frame size of the input, 4, the length of the **Initial conditions** vector is the sum of the maximum delay and 1 (5+1), which is 6. The first five entries of the initial conditions vector are used by the channel with the maximum delay, and the rest of the entries are ignored. Since the first channel is delayed for less than the maximum delay (2 sample time units), it only makes use of two of the initial condition entries.

- Array of size 1-by- $N$ -by- $D$ , where  $D$  is defined in “Time-Varying Initial Conditions” on page 2-807. In this case, the  $k$ th entry of each 1-by- $N$  entry in the array corresponds to an initial condition for the  $k$ th channel of the input matrix. Thus, a 1-by- $N$ -by- $D$  initial conditions input allows you to specify different initial conditions for each channel. For instance, for a two-channel ramp input `[1:100; 1:100]'` with a frame size of 4 and the parameter settings below,



the block outputs the following sequence of frames at the start of the simulation.

$$\begin{bmatrix} -1 & -2 \\ -3 & -4 \\ -5 & -6 \\ -7 & -8 \end{bmatrix}, \begin{bmatrix} -9 & -10 \\ 1 & 1 \\ 2 & 2 \\ 3 & 3 \end{bmatrix}, \begin{bmatrix} 4 & 4 \\ 5 & 5 \\ 6 & 6 \\ 7 & 7 \end{bmatrix}, \dots$$

Note that the channels have distinct time varying initial conditions; the initial conditions for channel 1 correspond to the first entry of each length-2 row vector in the initial conditions array, and the initial conditions for channel 2 correspond to the second entry of each row vector in the initial conditions array. Only the first five entries in the initial conditions array are used; the rest are ignored.

The 1-by- $N$ -by- $D$  array entry can also specify different fixed initial conditions for every channel; in this case, every 1-by- $N$  entry in the array would be identical, so that the initial conditions for each column are fixed over time.

Initial conditions cannot be specified by full matrices.



## Resetting the Delay

The block resets the delay whenever it detects a reset event at the optional Rst port. The reset sample time must be a positive integer multiple of the input sample time.



You specify the reset event in the **Reset port** parameter:

- None disables the Rst port.
- Rising edge — Triggers a reset operation when the Rst input does one of the following:
  - Rises from a negative value to a positive value or zero
  - Rises from zero to a positive value, where the rise is not a continuation of a rise from a negative value to zero (see the following figure)

# Integer Delay (Obsolete)



- Falling edge — Triggers a reset operation when the Rst input does one of the following:
  - Falls from a positive value to a negative value or zero
  - Falls from zero to a negative value, where the fall is not a continuation of a fall from a positive value to zero (see the following figure)



- Either edge — Triggers a reset operation when the Rst input is a Rising edge or Falling edge (as described above).
- Non-zero sample — Triggers a reset operation at each sample time that the Rst input is not zero.

---


**Note** When running simulations in the Simulink MultiTasking mode, sample-based reset signals have a one-sample latency, and frame-based reset signals have one frame of latency. Thus, there is a one-sample or one-frame delay between the time the block detects a reset event, and when it applies the reset. For more information on latency and the Simulink tasking modes, see “Excess Algorithmic Delay (Tasking Latency)” and “Scheduling” in the *Simulink Coder User’s Guide*.

---

## Examples

The dspafxr example illustrates an audio reverberation system built around the Integer Delay block.

## Dialog Box



### Delay

The number of sample periods to delay the input signal.

### Initial conditions

The value of the block’s output during the initial delay.

# Integer Delay (Obsolete)

---

## Reset port

Determines the reset event that causes the block to reset the delay. For more information, see “Resetting the Delay” on page 2-809.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point
- Fixed point (signed only)
- Boolean — The block accepts Boolean inputs to the Rst port, which is enabled by the **Reset port** parameter.
- 8-, 16-, and 32-bit signed integers
- 8-, 16-, and 32-bit unsigned integers

## See Also

Unit Delay

Variable Fractional Delay

Variable Integer Delay

Simulink

DSP System Toolbox

DSP System Toolbox

**Purpose** Interpolate values of real input samples

**Library** Signal Operations  
dspSigops

## Description



The Interpolation block interpolates discrete, real, inputs using linear or FIR interpolation. The block accepts both sample- and frame-based input data in the form of a vector, matrix, or sample-based N-D array. The block outputs a scalar, vector, matrix, or N-D array of the interpolated values, which has the same frame status as the input data.

You must specify the interpolation points (times at which to interpolate values) in a one-based interpolation array,  $I_{pts}$ . An entry of 1 in  $I_{pts}$  refers to the first sample of the input data, an entry of 2.5 refers to the sample half-way between the second and third input sample, and so on. Depending on the dimensions of the input data,  $I_{pts}$  can be a scalar, a length- $P$  row or column vector, a  $P$ -by- $N$  frame-based matrix, or a sample-based N-D array where  $P$  is the size of the first dimension of the N-D array. In most cases,  $P$  can be any positive integer. For more information about valid interpolation arrays, refer to the tables in “How the Block Applies Interpolation Arrays to Inputs” on page 2-814.

In most cases, the block applies  $I_{pts}$  across the first dimension of an N-D input array, or to each input vector. You can set the block to apply the same interpolation array for all input data (static interpolation points entered on the block mask) or to use a different interpolation array for each N-D array, matrix, or vector input (time-varying interpolation points received via the Pts input port).

## Sections of This Reference Page

- “Specifying Static Interpolation Points” on page 2-814
- “Specifying Time-Varying Interpolation Points” on page 2-814
- “How the Block Applies Interpolation Arrays to Inputs” on page 2-814
- “Handling Out-of-Range Interpolation Points” on page 2-820
- “Linear Interpolation Mode” on page 2-821

- “FIR Interpolation Mode” on page 2-822
- “Dialog Box” on page 2-823
- “Supported Data Types” on page 2-826

## Specifying Static Interpolation Points

To supply the block with a static interpolation array (an interpolation array applied to every vector or N-D array of input data), perform the following steps:

- Set the **Source of interpolation points** parameter to *Specify* via dialog.
- Enter the interpolation array in the **Interpolation points** parameter. To learn about interpolation arrays, see “How the Block Applies Interpolation Arrays to Inputs” on page 2-814.

## Specifying Time-Varying Interpolation Points

To supply the block with time-varying interpolation arrays (where the block uses a different interpolation array for each vector or N-D array input), perform the following steps:

- 1** Set the **Source of interpolation points** parameter to *Input port*, the **Pts** port appears on the block.
- 2** Generate a signal of interpolation arrays, and supply it to the **Pts** port. The block uses the input to this port as the interpolation points. To learn about interpolation arrays, see “How the Block Applies Interpolation Arrays to Inputs” on page 2-814.

## How the Block Applies Interpolation Arrays to Inputs

The interpolation array  $I_{\text{Pts}}$  represents the points in time at which to interpolate values of the input signal. An entry of 1 in  $I_{\text{Pts}}$  refers to the first sample of the input, an entry of 2.5 refers to the sample half-way between the second and third input sample, and so on. In most cases, when  $I_{\text{Pts}}$  is a vector, it can be of any length.

Valid values in the interpolation array,  $I_{pts}$ , range from 1 to the number of samples in each channel of the input. To learn how the block handles out of range interpolation values, see “Handling Out-of-Range Interpolation Points” on page 2-820.

Depending on the dimension and frame status of the input and the dimension of  $I_{pts}$ , the block usually applies  $I_{pts}$  to the input in one of the following ways:

- Applies the  $I_{pts}$  array across the first dimension of a sample-based N-D array or frame-based matrix input, resulting in a sample-based N-D array or frame-based matrix output.
- Applies the vector  $I_{pts}$  to each input vector (as if the input vector were a single channel), resulting in a vector output with the same orientation as the input (row or column).

The following tables summarize how the block applies the interpolation array  $I_{pts}$  to all the possible types of sample- and frame-based inputs, and show the resulting output dimensions.

The first table describes the block’s behavior when the **Source of interpolation points** is Specify via dialog and the input is sample based.

<b>Input Dimensions (Sample Based)</b>	<b>Valid Dimensions of Interpolation Array <math>I_{pts}</math></b>	<b>How Block Applies <math>I_{pts}</math> to Input</b>	<b>Output Dimensions (Sample Based)</b>
N-D Array  (ex. $M$ -by- $N$ -by- $Q$ )	1-by- $P$ row	Applies $I_{pts}$ to the first dimension of the input array	$P$ -by- $N$ -by- $Q$ array
	$P$ -by-1 column		
	$P$ -by- $N$ -by- $Q$ array	Applies the columns of $I_{pts}$ to the corresponding	

# Interpolation

Input Dimensions (Sample Based)	Valid Dimensions of Interpolation Array $I_{pts}$	How Block Applies $I_{pts}$ to Input	Output Dimensions (Sample Based)
		columns of the input array	
$M$ -by-1 column	1-by- $P$ row (block treats $I_n$ as a column)	Applies $I_{pts}$ to the input column	$P$ -by-1 column
	$P$ -by-1 column		
1-by- $N$ row	1-by- $P$ row	Applies $I_n$ to the input row	1-by- $P$ row
	$P$ -by-1 column (block treats $I_{pts}$ as a row)		

The next table describes the block's behavior when the **Source of interpolation points** is Specify via dialog and the input is frame based.

Input Dimensions (Frame Based)	Valid Dimensions of Interpolation Array $I_{pts}$	How Block Applies $I_{pts}$ to Input	Output Dimensions (Frame Based)
$M$ -by- $N$ matrix	1-by- $N$ row	Applies each column of $I_{pts}$ (each element of $I_{pts}$ ) to the corresponding column of the input matrix	1-by- $N$ row

Input Dimensions (Frame Based)	Valid Dimensions of Interpolation Array $I_{pts}$	How Block Applies $I_{pts}$ to Input	Output Dimensions (Frame Based)
	$P$ -by-1 column	Applies $I_{pts}$ to each input column	$P$ -by- $N$ matrix
	$P$ -by- $N$ matrix	Applies the columns of $I_{pts}$ to the corresponding columns of the input matrix	
$M$ -by-1 column	1-by- $P$ row (block treats $I_{pts}$ as a column)	Applies $I_{pts}$ to the input column	$P$ -by-1 column
	$P$ -by-1 column		
1-by- $N$ row (not recommended)	1-by- $N$ row	Not Applicable. Block copies input vector	1-by- $N$ row, a copy of the input vector
	$P$ -by-1 column		$P$ -by- $N$ matrix where each row is a copy of the input vector
	$P$ -by- $N$ matrix		

The next table describes the block's behavior when the **Source of interpolation points** is Input port and the input is sample based.

# Interpolation

Input Dimensions (Sample Based)	Valid Dimensions of Interpolation Array $I_{pts}$	How Block Applies $I_{pts}$ to Input	Output Dimensions (Sample Based)
N-D Array (ex. $M$ -by- $N$ -by- $Q$ )	Sample-based 1-by- $P$ row	Applies $I_{pts}$ to the first dimension of the input array	$P$ -by- $N$ -by- $Q$ array
	Sample- or frame-based $P$ -by-1 column		
	Sample-based $P$ -by- $N$ -by- $Q$ array	Applies the columns of $I_{pts}$ to the corresponding columns of the input array	
$M$ -by-1 column	Sample-based 1-by- $P$ row	Applies $I_{pts}$ to the input column	$P$ -by-1 column
	Sample- or frame-based $P$ -by-1 column		
1-by- $N$ row	Sample-based 1-by- $P$ row	Applies $I_{pts}$ to the input row	1-by- $P$ row
	Sample or frame-based $P$ -by-1 column		

The next table describes the block's behavior when the **Source of interpolation points** is Input port and the input is frame based.

<b>Input Dimensions (Frame Based)</b>	<b>Valid Dimensions of Interpolation Array <math>I_{pts}</math></b>	<b>How Block Applies <math>I_{pts}</math> to Input</b>	<b>Output Dimensions (Frame Based)</b>
$M$ -by- $N$ matrix	Frame-based 1-by- $N$ row	Applies each column of $I_{pts}$ (each element of $I_{pts}$ ) to the corresponding column of the input matrix	1-by- $N$ row
	Sample-based 1-by- $P$ row	Applies $I_{pts}$ to each input column	$P$ -by- $N$ matrix
	Frame- or sample-based $P$ -by-1 column		
Frame- or sample-based $P$ -by- $N$ matrix	Applies the columns of $I_{pts}$ to the corresponding columns of the input matrix		
$M$ -by-1 column	Sample-based 1-by- $P$ row	Applies $I_{pts}$ to the input column	$P$ -by-1 column
	Frame- or sample-based $P$ -by-1 column		

# Interpolation

Input Dimensions (Frame Based)	Valid Dimensions of Interpolation Array $I_{pts}$	How Block Applies $I_{pts}$ to Input	Output Dimensions (Frame Based)
1-by- $N$ row (not recommended)	Frame-based 1-by- $N$ row	Not Applicable. Block copies input vector	1-by- $N$ row, a copy of the input vector
	Sample-based 1-by- $P$ row		$P$ -by- $N$ matrix where each row is a copy of the input vector
	Frame- or sample-based $P$ -by-1 column		
	Frame- or sample-based $P$ -by- $N$ matrix		

## Handling Out-of-Range Interpolation Points

Valid values in the interpolation array  $I_{pts}$  range from 1 to the number of samples in each channel of the input. For instance, given a length-5 input vector  $D$ , all entries of  $I_{pts}$  must range from 1 to 5.  $I_{pts}$  cannot contain entries such as 7 or -9, since there is no 7th or -9th entry in  $D$ .

The **Out of range interpolation points** parameter sets how the block handles interpolation points that are fall outside the valid range, and has the following settings:

- **Clip** — The block replaces any out-of-range values in  $I_{pts}$  with the closest value in the valid range (from 1 to the number of input samples), and then proceeds with computations using the clipped version of  $I_{pts}$ .
- **Clip and warn** — In addition to **Clip**, the block issues a warning at the MATLAB command line every time clipping occurs.

- Error — When the block encounters an out-of-range value in  $I_{\text{Pts}}$ , the simulation stops, and the block issues an error at the MATLAB command line.

## Example of Clipping

Suppose the block is set to clip out-of-range interpolation points, and gets the following input vector and interpolation points:


- $D = [11 \ 22 \ 33 \ 44]'$
- $I_{\text{Pts}} = [10 \ 2.6 \ -3]'$

Because  $D$  has four samples, valid interpolation points range from 1 to 4. The block clips the interpolation point 10 to 4 and the point -3 to 1, resulting in the clipped interpolation vector  $I_{\text{PtsClipped}} = [4 \ 2.6 \ 1]'$ .

## Linear Interpolation Mode

When **Interpolation Mode** is set to **Linear**, the block interpolates data values by assuming that the data varies linearly between samples taken at adjacent sample times.

For instance, if the input signal  $D = [1 \ 2 \ 1.5 \ 3 \ 0.25]'$ , the following plot on the left shows the samples in  $D$ , and the plot on the right shows the linearly interpolated values between the samples in  $D$ .




# Interpolation

The following figure illustrates the case of a block in linear interpolation mode that is set to clip out-of-range interpolation points. The vector  $D$  supplies the input data and the vector  $I_{pts}$  supplies the interpolation points:

- $D = [1 \ 2 \ 1.5 \ 3 \ 0.25]'$
- $I_{pts} = [-4 \ 2.7 \ 4.3 \ 10]'$

The block clips the invalid interpolation points, and outputs the linearly interpolated values in a vector,  $[1 \ 1.65 \ 2.175 \ 0.25]'$ .

Interpolated Values of  $D$  at Clipped Interpolation Points



$$D = [1 \ 2 \ 1.5 \ 3 \ 0.25]'$$
$$I_{pts} = [-4 \ 2.7 \ 4.3 \ 10]'$$

Valid interpolation points range from 1 to 5, so -4 is clipped to 1 and 10 is clipped to 5.


$$\text{Clipped } I_{pts} = [1 \ 2.7 \ 4.3 \ 5]'$$

$$\text{Output} = [1 \ 1.65 \ 2.175 \ 0.25]'$$

## FIR Interpolation Mode

When **Interpolation Mode** is set to FIR, the block interpolates data values using an FIR interpolation filter, specified by various block

parameters. See FIR Interpolation Mode on page 1646 in the Variable Fractional Delay block reference for more information.



## Dialog Box

### Source of interpolation points

Choose how you want to specify the interpolation points. If you select **Specify via dialog**, the **Interpolation points** parameter become available. Use this option for static interpolation points. If you select **Input port**, the **Pts** port appears on the block. The block uses the input to this port as the interpolation points. Use this option for time-varying interpolation points. For more information, see “Specifying Static Interpolation Points” on page 2-814 and “Specifying Time-Varying Interpolation Points” on page 2-814.

## Interpolation points

The array of points in time at which to interpolate the input signal ( $I_{\text{Pts}}$ ). An entry of 1 in  $I_{\text{Pts}}$  refers to the first sample of the input, an entry of 2.5 refers to the sample half-way between the second and third input sample, and so on. See “How the Block Applies Interpolation Arrays to Inputs” on page 2-814. Tunable.

## Interpolation mode

Sets the block to interpolate by either linear or FIR interpolation. For more information, see “Linear Interpolation Mode” on page 2-821 and “FIR Interpolation Mode” on page 2-822.

## Interpolation filter half-length

Specify the half-length of the FIR interpolation filter (P). To perform the interpolation in FIR mode, the block uses the nearest  $2 \cdot P$  low-rate samples. In most cases, P low-rate samples must appear below and above each interpolation point. However, if you interpolate at a low-rate sample point, the block includes that low-rate sample in the required  $2 \cdot P$  samples and requires only  $2 \cdot P - 1$  neighboring low-rate samples. If an interpolation point does not have the required number of neighboring low-rate samples, the block interpolates that point using linear interpolation.

This parameter becomes available only when the **Interpolation mode** is set to FIR. For more information, see “FIR Interpolation Mode” on page 2-822.

## Interpolation points per input sample

Also known as the *upsampling factor*, this parameter defines the number of points per input sample (L) at which the block computes a unique FIR interpolation filter. To perform the FIR Interpolation, the block uses a polyphase structure with L filter arms of length  $2 \cdot P$ .

For example, if  $L=4$ , the block constructs a polyphase filter with four arms. The block then interpolates at points corresponding to  $1 + i/L$ ,  $2 + i/L$ ,  $3 + i/L$ ..., where the integers 1, 2, and 3 represent the low-rate samples, and  $i=0, 1, 2, 3$ . To interpolate at a point

that does not directly correspond to an arm of the polyphase filter requires an extra computation. The block first rounds that point down to the nearest value that does correspond to an arm of the polyphase filter. Thus, to interpolate at the point 2.2, the block rounds 2.2 down to 2, and computes the FIR interpolation using the first arm of the polyphase filter structure. Similarly, to interpolate the point 2.65, the block rounds the value down to 2.5 and uses the third arm of the polyphase filter structure.

This parameter becomes available only when the **Interpolation mode** is set to FIR. For more information, see “FIR Interpolation Mode” on page 2-822.

### **Normalized input bandwidth**

The bandwidth of the input divided by  $F_s/2$  (half the input sample frequency).

This parameter is only available when the **Interpolation mode** is set to FIR. For more information, see “FIR Interpolation Mode” on page 2-822.

### **Out of range interpolation points**

When an interpolation point is out of range, this parameter sets the block to either clip the interpolation point, clip the value and issue a warning at the MATLAB command line, or stop the simulation and issue an error at the MATLAB command line. For more information, see “Handling Out-of-Range Interpolation Points” on page 2-820.

# Interpolation

---


## Supported Data Types

Port	Supported Data Types
In	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Pts	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Out	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

**Purpose** Recover time-domain signals by performing inverse short-time, fast Fourier transform (FFT)

**Library** Transforms  
dspxfm3

## Description



The Inverse Short-Time FFT block reconstructs the time-domain signal from the frequency-domain output of the Short-Time FFT block using a two-step process. First, the block performs the overlap add algorithm shown below.

$$x[n] = \frac{L}{W(0)} \sum_{p=-\infty}^{\infty} \left[ \frac{1}{N} \sum_{k=0}^{N-1} X[pL, k] e^{j2\pi kn/N} \right]$$

Then, the block rebuffers the signal in order to reconstruct the time-domain signal. Depending on the analysis window used by the Short-Time FFT block, the Inverse Short-Time FFT block might or might not achieve perfect reconstruction of the time domain signal.


Connect your complex-valued, single-channel or multichannel input signal to the X(n,k) port. The block accepts unoriented vector, column vector and matrix input. The block outputs the real or complex-valued, single-channel or multichannel inverse short-time FFT at port x(n).

Connect your complex-valued, single-channel analysis window to the w(n) port. When you select the **Assert if analysis window does not support perfect signal reconstruction** check box, the block displays an error when the input signal cannot be perfectly reconstructed. The block uses the values you enter for the **Analysis window length (W)** and **Reconstruction error tolerance**, or maximum amount of allowable error in the reconstruction process, to determine if the signal can be perfectly reconstructed.

## Examples

The dspstsa example illustrates how to use the Short-Time FFT and Inverse Short-Time FFT blocks to remove the background noise from a speech signal.

# Inverse Short-Time FFT



## Dialog Box

### Analysis window length

Enter the length of the analysis window. This parameter is visible when you select the **Assert if analysis window does not support perfect signal reconstruction** check box.

### Overlap between consecutive STFFT frames (in samples)

Enter the number of samples of overlap for each frame of the Short-Time FFT block's input signal. This value should be the

same as the **Overlap between consecutive windows (in samples)** parameter in the Short-Time FFT block parameters dialog.

## **Samples per output frame**

Enter the desired frame size of the output signal.

## **Input is conjugate symmetric**

Select this check box when the input to the block is both floating point and conjugate symmetric, and you want real-valued outputs. When you select this check box when the input is not conjugate symmetric, the output of the block is invalid. This parameter cannot be used for fixed-point signals.

## **Assert if analysis window does not support perfect signal reconstruction**

Select this check box to display an error when the analysis window used by the Short-Time FFT block does not support perfect signal reconstruction.

## **Reconstruction error tolerance**

Enter the amount of acceptable error in the reconstruction of the original signal. This parameter is visible when you select the **Assert if analysis window does not support perfect signal reconstruction** check box.

## **References**

Quatieri, Thomas E. *Discrete-Time Speech Signal Processing*. Englewood Cliffs, NJ: Prentice-Hall, 2001.

# Inverse Short-Time FFT

---

## Supported Data Types

Port	Supported Data Types
X(n,k)	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
w(n)	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
x(n)	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

## See Also

Burg Method	DSP System Toolbox
Magnitude FFT	DSP System Toolbox
Periodogram	DSP System Toolbox
Short-Time FFT	DSP System Toolbox
Spectrum Scope	DSP System Toolbox
Window Function	DSP System Toolbox
Yule-Walker Method	DSP System Toolbox
pwelch	Signal Processing Toolbox

**Purpose** Design inverse sinc filter

**Library** Filtering / Filter Designs  
dspdesign

**Description** This block brings the filter design capabilities of the `filterbuilder` function to the Simulink environment.



**Dialog Box** See “Inverse Sinc Filter Design Dialog Box — Main Pane” on page 7-735 for more information about the parameters of this block. The **Data Types** and **Code Generation** panes are not available for blocks in the DSP System Toolbox Filter Designs library.

# Inverse Sinc Filter

Function Block Parameters: Inverse Sinc Filter

Inverse Sinc Filter  
Design an inverse-sinc filter.

[View Filter Response](#)

Filter specifications

Order mode:  Order:

Response type:

Filter Type:

Frequency specifications

Frequency units:  Input Fs:

Fpass:  Fstop:

Magnitude specifications

Magnitude units:

Apass:  Astop:

Algorithm

Design method:

► Design options

Filter Implementation

Structure:

Use basic elements to enable filter customization

Input processing:

Use symbolic names for coefficients

## View filter response

This button opens the Filter Visualization Tool (fvtool) from the Signal Processing Toolbox product. You can use the tool to display:

- Magnitude response, phase response, and group delay in the frequency domain.
- Impulse response and step response in the time domain.
- Pole-zero information.

The tool also helps you evaluate filter performance by providing information about filter order, stability, and phase linearity. For more information on FVTool, see the Signal Processing Toolbox documentation.

## Filter Specifications

In this group, you specify your filter format, such as the impulse response and the filter order.

### Order mode

Select either **Minimum** (the default) or **Specify** from the drop-down list. Selecting **Specify** enables the **Order** option (see the following sections) so you can enter the filter order.

### Response type

Select **Lowpass** or **Highpass** to design an inverse sinc lowpass or highpass filter.

### Filter type

Select **Single-rate**, **Decimator**, **Interpolator**, or **Sample-rate converter**. Your choice determines the type of filter as well as the design methods and structures that are available to implement your filter. By default, the block specifies a single-rate filter.

- Selecting **Decimator** or **Interpolator** activates the **Decimation Factor** or the **Interpolation Factor** options respectively.
- Selecting **Sample-rate converter** activates both factors.

# Inverse Sinc Filter

---

## Order

Enter the filter order. This option is enabled only if you set the **Order mode** to Specify.

## Decimation Factor

Enter the decimation factor. This option is enabled only if the **Filter type** is set to Decimator or Sample-rate converter. The default value is 2.

## Interpolation Factor

Enter the interpolation factor. This option is enabled only if the **Filter type** is set to Interpolator or Sample-rate converter. The default value is 2.

## Frequency Specifications

The parameters in this group allow you to specify your filter response curve.

Regions between specification values such as **Fpass** and **Fstop** represent transition regions where the filter response is not constrained.

## Frequency constraints

When **Order mode** is Specify, select the filter features that the block uses to define the frequency response characteristics. The list contains the following options, when available for the filter specifications.

- **Passband and stopband edges** — Define the filter by specifying the frequencies for the edges for the stop- and passbands.
- **Passband edges** — For IIR filters, define the filter by specifying frequencies for the edges of the passband.
- **Stopband edges** — For IIR filters, define the filter by specifying frequencies for the edges of the stopbands.
- **6 dB point** — For FIR filters, define the filter response by specifying the locations of the 6 dB point. The 6 dB point is the frequency for the point six decibels below the passband value.

## Frequency units

Use this parameter to specify whether your frequency settings are normalized or in absolute frequency. Select **Normalized (0 1)** to enter frequencies in normalized form. This behavior is the default. To enter frequencies in absolute values, select one of the frequency units from the drop-down list—Hz, kHz, MHz, or GHz. Selecting one of the unit options enables the **Input Fs** parameter.

## Input Fs

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter input. When you provide an input sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is available when you select one of the frequency options from the **Frequency units** list.

## Fpass

Enter the frequency at the end of the passband. Specify the value in either normalized frequency units or the absolute units you select in **Frequency units**.

## Fstop

Enter the frequency at the start of the stopband. Specify the value in either normalized frequency units or the absolute units you select in **Frequency units**.

## F6dB

When **Frequency constraints** is 6 dB point, specify the frequency of the 6 dB point. Specify the value in either normalized frequency units or the absolute units you select **Frequency units**.

## Magnitude Specifications

Parameters in this group specify the filter response in the passbands and stopbands.

## Magnitude units

Specify the units for any parameter you provide in magnitude specifications. From the drop-down list, select one of the following options:

# Inverse Sinc Filter

---

- Linear — Specify the magnitude in linear units.
- dB — Specify the magnitude in decibels (default)
- Squared — Specify the magnitude in squared units.

## **Apass**

Enter the filter ripple allowed in the passband in the units you choose for **Magnitude units**, either linear or decibels.

## **Astop**

Enter the filter attenuation in the stopband in the units you choose for **Magnitude units**, either linear or decibels.

## **Algorithm**

The parameters in this group allow you to specify the design method and structure of your filter.

## **Design Method**

Lists the design methods available for the frequency and magnitude specifications you entered. When you change the specifications for a filter, such as changing the impulse response, the methods available to design filters changes as well. The default FIR method is **Equiripple**.

## **Design Options**

The options for each design are specific for each design method. This section does not present all of the available options for all designs and design methods. There are many more that you encounter as you select different design methods and filter specifications. The following options represent some of the most common ones available.

## **Density factor**

Density factor controls the density of the frequency grid over which the design method optimization evaluates your filter response function. The number of equally spaced points in the grid is the value you enter for **Density factor** times (filter order + 1).

Increasing the value creates a filter that more closely approximates an ideal equiripple filter but increases the time required to design the filter. The default value of 20 represents a reasonable trade between the accurate approximation to the ideal filter and the time to design the filter.

## Phase constraint

Specify the phase constraint of the filter as **Linear**, **Maximum**, or **Minimum**.

## Minimum order

When you select this parameter, the design method determines and design the minimum order filter to meet your specifications. Some filters do not provide this parameter. Select **Any**, **Even**, or **Odd** from the drop-down list to direct the design to be any minimum order, or minimum even order, or minimum odd order.

## Stopband Shape

Stopband shape lets you specify how the stopband changes with increasing frequency. Choose one of the following options;

- **Flat** — Specifies that the stopband is flat. The attenuation does not change as the frequency increases.
- **Linear** — Specifies that the stopband attenuation changes linearly as the frequency increases. Change the slope of the stopband by setting **Stopband decay**.
- **1/f** — Specifies that the stopband attenuation changes exponentially as the frequency increases, where **f** is the frequency. Set the power (exponent) for the decay in **Stopband decay**.

## Stopband Decay

When you set **Stopband shape**, **Stopband decay** specifies the amount of decay applied to the stopband. the following

# Inverse Sinc Filter

---

conditions apply to **Stopband decay** based on the value of **Stopband Shape**:

- When you set **Stopband shape** to **Flat**, **Stopband decay** has no effect on the stopband.
- When you set **Stopband shape** to **Linear**, enter the slope of the stopband in units of dB/rad/s. The block applies that slope to the stopband.
- When you set **Stopband shape** to **1/f**, enter a value for the exponent  $n$  in the relation  $(1/f)^n$  to define the stopband decay. The block applies the  $(1/f)^n$  relation to the stopband to result in an exponentially decreasing stopband attenuation.

## Sinc frequency factor

A frequency dilation factor. The **Sinc frequency factor**,  $C$ , parameterizes the passband magnitude response for a lowpass design through  $H(\omega) = \text{sinc}(C\omega)^{-P}$  and through  $H(\omega) = \text{sinc}(C(1-\omega))^{-P}$  for a highpass design.

## Sinc power

Negative power of passband magnitude response. The **Sinc power**,  $P$ , parameterizes the passband magnitude response for a lowpass design through  $H(\omega) = \text{sinc}(C\omega)^{-P}$  and through  $H(\omega) = \text{sinc}(C(1-\omega))^{-P}$  for a highpass design.

## Filter Implementation

### Structure

For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter. By default, FIR filters use direct-form structure, and IIR filters use direct-form II filters with SOS.

### Use basic elements to enable filter customization

Select this check box to implement the filter as a subsystem of basic Simulink blocks. Clear the check box to implement the filter as a high-level subsystem. By default, this check box is cleared.

The high-level implementation provides better compatibility across various filter structures, especially filters that would contain algebraic loops when constructed using basic elements. On the other hand, using basic elements enables the following optimization parameters:

- **Optimize for zero gains** — Terminate chains that contain Gain blocks with a gain of zero.
- **Optimize for unit gains** — Remove Gain blocks that scale by a factor of one.
- **Optimize for delay chains** — Substitute delay chains made up of  $n$  unit delays with a single delay by  $n$ .
- **Optimize for negative gains** — Use subtraction in Sum blocks instead of negative gains in Gain blocks.

## Input processing

Specify how the block should process the input. The available options may vary depending on the settings of the **Filter Structure** and **Use basic elements for filter customization** parameters. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The Inherited (this choice will be removed see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

# Inverse Sinc Filter

---

## Rate options

When the **Filter type** parameter specifies a multirate filter, select the rate processing rule for the block from following options:

- **Enforce single-rate processing** — When you select this option, the block maintains the sample rate of the input.
- **Allow multirate processing** — When you select this option, the block adjusts the rate at the output to accommodate an increased or reduced number of samples. To select this option, you must set the **Input processing** parameter to **Elements as channels** (sample based).

## Use symbolic names for coefficients

Select this check box to enable the specification of coefficients using MATLAB variables. The available coefficient names differ depending on the filter structure. Using symbolic names allows tuning of filter coefficients in generated code. By default, this check box is cleared.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

# Kalman Adaptive Filter (Obsolete)

**Purpose** Compute filter estimates for inputs using Kalman adaptive filter algorithm


**Library** dspobslib

## Description



**Note** The Kalman Adaptive Filter block is still supported but is likely to be obsoleted in a future release. We strongly recommend replacing this block with the Kalman Filter block.

The Kalman Adaptive Filter block computes the optimal linear minimum mean-square estimate (MMSE) of the FIR filter coefficients using a one-step predictor algorithm. This Kalman filter algorithm is based on the following physical realization of a dynamic system.



The Kalman filter assumes that there are no deterministic changes to the filter taps over time (that is, the transition matrix is identity), and that the only observable output from the system is the filter output with additive noise. The corresponding Kalman filter is expressed in matrix form as

# Kalman Adaptive Filter (Obsolete)

$$g(n) = \frac{K(n-1)u(n)}{u^H(n)K(n-1)u(n) + Q_M}$$

$$y(n) = u^H(n)\hat{w}(n)$$

$$e(n) = d(n) - y(n)$$

$$\hat{w}(n+1) = \hat{w}(n) + e(n)g(n)$$

$$K(n) = K(n-1) - g(n)u^H(n)K(n-1) + Q_P$$

The variables are as follows

Variable	Description
$n$	The current algorithm iteration
$u(n)$	The buffered input samples at step $n$
$K(n)$	The correlation matrix of the state estimation error
$g(n)$	The vector of Kalman gains at step $n$
$\hat{w}(n)$	The vector of filter-tap estimates at step $n$
$y(n)$	The filtered output at step $n$
$e(n)$	The estimation error at step $n$
$d(n)$	The desired response at step $n$
$Q_M$	The correlation matrix of the measurement noise
$Q_P$	The correlation matrix of the process noise

The correlation matrices,  $Q_M$  and  $Q_P$ , are specified in the parameter dialog by scalar variance terms to be placed along the matrix diagonals, thus ensuring that these matrices are symmetric. The filter algorithm based on this constraint is also known as the random-walk Kalman filter.

# Kalman Adaptive Filter (Obsolete)

The implementation of the algorithm in the block is optimized by exploiting the symmetry of the input covariance matrix  $K(n)$ . This decreases the total number of computations by a factor of two.

The block icon has port labels corresponding to the inputs and outputs of the Kalman algorithm. Note that inputs to the In and Err ports must be sample-based scalars with the same complexity. The signal at the Out port is a scalar, while the signal at the Taps port is a sample-based vector.

Block Ports	Corresponding Variables
In	$u$ , the scalar input, which is internally buffered into the vector $u(n)$
Out	$y(n)$ , the filtered scalar output
Err	$e(n)$ , the scalar estimation error
Taps	$\hat{w}(n)$ , the vector of filter-tap estimates

An optional Adapt input port is added when you select the **Adapt port** check box in the dialog. When this port is enabled, the block continuously adapts the filter coefficients while the Adapt input is nonzero. A zero-valued input to the Adapt port causes the block to stop adapting, and to hold the filter coefficients at their current values until the next nonzero Adapt input.


The **FIR filter length** parameter specifies the length of the filter that the Kalman algorithm estimates. The **Measurement noise variance** and the **Process noise variance** parameters specify the correlation matrices of the measurement and process noise, respectively. The **Measurement noise variance** must be a scalar, while the **Process noise variance** can be a vector of values to be placed along the diagonal, or a scalar to be repeated for the diagonal elements.

The **Initial value of filter taps** specifies the initial value  $\hat{w}(0)$  as a vector, or as a scalar to be repeated for all vector elements. The **Initial**

# Kalman Adaptive Filter (Obsolete)

**error correlation matrix** specifies the initial value  $K(0)$ , and can be a diagonal matrix, a vector of values to be placed along the diagonal, or a scalar to be repeated for the diagonal elements.

## Dialog Box



The dialog box is titled "Block Parameters: Kalman Adaptive Filter" and contains the following information:

- Kalman Adaptive Filter (mask) (link)**
  - One-step Kalman predictor algorithm for adaptive FIR filtering of input signal.
  - Select the Adapt port check box to create an Adapt port on the block. When the input to this port is nonzero, the block enables filter adaptation. When the input to this port is zero, filter adaptation is disabled.
  - If the Reset port is enabled and a reset event occurs, the block resets the filter weights to their initial values.
- Parameters**
  - FIR filter length: 64
  - Measurement noise variance: 0.3
  - Process noise variance: 0.1
  - Initial value of filter taps: 0
  - Initial error correlation matrix: 0.5
  - Adapt port
  - Reset port: None

Buttons: OK, Cancel, Help, Apply

### FIR filter length

The length of the FIR filter.

# Kalman Adaptive Filter (Obsolete)

---

## Measurement noise variance

The value to appear along the diagonal of the measurement noise correlation matrix. Tunable.

## Process noise variance

The value to appear along the diagonal of the process noise correlation matrix. Tunable.

## Initial value of filter taps

The initial FIR filter coefficients.

## Initial error correlation matrix

The initial value of the error correlation matrix.

## Adapt port

Enables the Adapt port.

## References

Haykin, S. *Adaptive Filter Theory*. 3rd ed. Englewood Cliffs, NJ: Prentice Hall, 1996.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point

## See Also

LMS Adaptive Filter    DSP System Toolbox  
(Obsolete)

RLS Adaptive Filter    DSP System Toolbox  
(Obsolete)

See “Adaptive Filters in Simulink” for related information.

# Kalman Filter

## Purpose


Predict or estimate states of dynamic systems

## Library

Filtering/Adaptive Filters

dspadpt3

## Description



Use the Kalman Filter block to predict or estimate the state of a dynamic system from a series of incomplete and/or noisy measurements. Suppose you have a noisy linear system that is defined by the following equations:

$$x_k = Ax_{k-1} + w_{k-1}$$

$$z_k = Hx_k + v_k$$

This block can use the previously estimated state,  $\hat{x}_{k-1}$ , to predict the current state at time  $k$ ,  $x_k^-$ , as shown by the following equation:

$$x_k^- = A\hat{x}_{k-1}$$

$$P_k^- = AP_{k-1}A^T + Q$$

The block can also use the current measurement,  $z_k$ , and the predicted state,  $x_k^-$ , to estimate the current state value at time  $k$ ,  $\hat{x}_k$ , so that it is a more accurate approximation:

$$K_k = P_k^- H^T (HP_k^- H^T + R)^{-1}$$

$$\hat{x}_k = x_k^- + K_k (z_k - Hx_k^-)$$

$$\hat{P}_k = (I - K_k H) P_k^-$$

The variables in the previous equations are defined in the following table.

Variable	Definition	Default Value or Initial Condition
$x$	State	N/A
$\hat{x}$	Estimated state	<code>zeros([6, 1])</code>
$x^-$	Predicted state	N/A
$A$	State transition matrix	$\begin{bmatrix} 1 & 0 & 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 \end{bmatrix}$
$w$	Process noise	N/A
$z$	Measurement	N/A
$H$	Measurement matrix	$\begin{bmatrix} 1 & 0 & 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 \end{bmatrix}$
$v$	Measurement noise	N/A
$\hat{P}$	Estimated error covariance	<code>10*eye(6)</code>
$P^-$	Predicted error covariance	N/A
$Q$	Process noise covariance	<code>0.05*eye(6)</code>
$K$	Kalman gain	N/A

# Kalman Filter

---

Variable	Definition	Default Value or Initial Condition
$R$	Measurement noise covariance	eye(4)
$I$	Identity matrix	N/A

In the previous equations,  $z$  is a vector of measurement values. Most of the time, the block processes  $Z$ , an M-by-N matrix, where M is the number of measurement values and N is the number of filters.

Use the **Number of filters** parameter to specify the number of filters to use to predict or estimate the current value.

Use the **Enable filters** parameter to specify which filters are enabled or disabled at each time step. If you select **Always**, the filters are always enabled. If you choose **Specify via input port <Enable>**, the Enable port appears on the block. The input to this port must be a row vector of 1s and 0s whose length is equal to the number of filters. For example, if there are 3 filters and the input to the Enable port is [1 0 1], only the first and third filter are enabled at this time step. If you select the **Reset the estimated state and estimated error covariance when filters are disabled** check box, the estimated and predicted states as well as the estimated error covariance that correspond to the disabled filters are reset to their initial values.

---

**Note** All filters have the same state transition matrix, measurement matrix, initial conditions, and noise covariance, but their state, measurement, enable, and MSE signals are unique. Within the state, measurement, enable, and MSE signals, each column corresponds to a filter.

---

Use the **Measurement matrix source** parameter to specify how to enter the measurement matrix values. If you select **Specify via dialog**, the **Measurement matrix** parameter appears in the dialog

box. If you select `Input port <H>`, the H port appears on the block. Use this port to specify your measurement matrix.

See the Radar Tracking example for a demonstration of how to use this block. You can open this example by typing


```
aero_radmod_dsp
```

at the MATLAB command prompt.

# Kalman Filter

## Dialog Box

The Kalman Filter dialog box appears as shown in the following figure.



### Number of filters

Specify the number of filters to use to predict or estimate the current value.

**Enable filters**

Specify which filters are enabled or disabled at each time step. If you select Always, the filters are always enabled. If you choose Specify via input port <Enable>, the Enable port appears on the block.

**Reset the estimated state and estimated error covariance when filters are disabled**

If you select this check box, the estimated and predicted states as well as the estimated error covariance that correspond to the disabled filters are reset to their initial values. This parameter is visible if, for the **Enable filters** parameter, you select Specify via input port <Enable>.

**Initial condition for estimated state**

Enter the initial condition for the estimated state.

**Initial condition for estimated error covariance**

Enter the initial condition for the estimated error covariance.

**State transition matrix**

Enter the state transition matrix.

**Process noise covariance**

Enter the process noise covariance.

**Measurement matrix source**

Specify how to enter the measurement matrix values. If you select Specify via dialog, the **Measurement matrix** parameter appears in the dialog box. If you select Input port <H>, the H port appears on the block.

**Measurement matrix**

Enter the measurement matrix values. This parameter is visible if you select Specify via dialog for the **Measurement matrix source** parameter.

**Measurement noise covariance**

Enter the measurement noise covariance.

# Kalman Filter

---

**Output estimated measurement <Z\_est>**

Select this check box if you want the block to output the estimated measurement.

**Output estimated state <X\_est>**

Select this check box if you want the block to output the estimated state.

**Output MSE of estimated state <MSE\_est>**

Select this check box if you want the block to output the mean-squared error of the estimated state.

**Output predicted measurement <Z\_prd>**

Select this check box if you want the block to output the predicted measurement.

**Output predicted state <X\_prd>**

Select this check box if you want the block to output the predicted state.

**Output MSE of predicted state <MSE\_prb>**

Select this check box if you want the block to output the mean-squared error of the predicted state.

## References

[1] Haykin, Simon. *Adaptive Filter Theory*. Upper Saddle River, NJ: Prentice Hall, 1996.

[2] Welch, Greg and Gary Bishop, "An Introduction to the Kalman Filter," TR 95-041, Department of Computer Science, University of North Carolina.

## Supported Data Types

Port	Input/Output	Supported Data Types
Z	M-by-N measurement where M is the length of the measurement vector and N is the number of filters.	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> </ul>
Enable	1-by-N vector of 1s and 0s where N is the number of filters.	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Boolean</li> </ul>
H	M-by-P measurement matrix where M is the length of the measurement vector and P is the length of the filter state vectors.	Same as Z port
Z_est	M-by-N estimated measurement matrix where M is the length of the measurement vector and N is the number of filters.	Same as Z port
X_est	P-by-N estimated state matrix where P is the length of the filter state vectors and N is the number of filters.	Same as Z port

# Kalman Filter

---

Port	Input/Output	Supported Data Types
MSE_est	1-by-N vector that represents the mean-squared-error of the estimated state. N is the number of filters.	Same as Z port
Z_prd	M-by-N predicted measurement matrix where M is the length of the measurement vector and N is the number of filters.	Same as Z port
X_prd	P-by-N predicted state matrix where P is the length of the filter state vectors and N is the number of filters.	Same as Z port
MSE_prd	1-by-N vector that represents the mean-squared-error of the predicted state. N is the number of filters.	Same as Z port

## See Also

LDL Solver

DSP System Toolbox


## Purpose

Factor square Hermitian positive definite matrices into lower, upper, and diagonal components

## Library

Math Functions / Matrices and Linear Algebra / Matrix Factorizations  
dspfactors

## Description



The LDL Factorization block uniquely factors the square Hermitian positive definite input matrix  $S$  as

$$S = LDL^*$$

where  $L$  is a lower triangular square matrix with unity diagonal elements,  $D$  is a diagonal matrix, and  $L^*$  is the Hermitian (complex conjugate) transpose of  $L$ . Only the diagonal and lower triangle of the input matrix are used, and any imaginary component of the diagonal entries is disregarded.

The block's output is a composite matrix with lower triangle elements  $l_{ij}$  from  $L$ , diagonal elements  $d_{ij}$  from  $D$ , and upper triangle elements  $u_{ij}$  from  $L^*$ . The output format is shown below for a 5-by-5 matrix.

$d_{11}$	$u_{12}$	$u_{13}$	$u_{14}$	$u_{15}$
$l_{21}$	$d_{22}$	$u_{23}$	$u_{24}$	$u_{25}$
$l_{31}$	$l_{32}$	$d_{33}$	$u_{34}$	$u_{35}$
$l_{41}$	$l_{42}$	$l_{43}$	$d_{44}$	$u_{45}$
$l_{51}$	$l_{52}$	$l_{53}$	$l_{54}$	$d_{55}$

$$u_{ij} = l_{ji}^*$$


LDL factorization requires half the computation of Gaussian elimination (LU decomposition), and is always stable. It is more efficient than Cholesky factorization because it avoids computing the square roots of the diagonal elements.

The algorithm requires that the input be square and Hermitian positive definite. When the input is not positive definite, the block reacts with the behavior specified by the **Non-positive definite input** parameter.

# LDL Factorization

## Fixed-Point Data Types

The following diagram shows the data types used within the LDL Factorization block for fixed-point signals.



You can set the intermediate product, product output, accumulator, and output data types in the block dialog as discussed below.

The output of the second multiplier is in the product output data type when the input is real. When the input is complex, the result of the multiplication is in the accumulator data type. For details on the complex multiplication performed, see "Multiplication Data Types".

## Examples


LDL decomposition of a 3-by-3 Hermitian positive definite matrix:

$$\begin{bmatrix} 9 & -1 & 2 \\ -1 & 8 & -5 \\ 2 & -5 & 7 \end{bmatrix} \Rightarrow \begin{matrix} S = L D L' \\ \text{LDL Factorization} \end{matrix} \Rightarrow \begin{bmatrix} 9.00 & -0.11 & 0.22 \\ -0.11 & 7.89 & -0.61 \\ 0.22 & -0.61 & 3.66 \end{bmatrix}$$

$$L = \begin{bmatrix} 1 & 0 & 0 \\ -0.11 & 1 & 0 \\ 0.22 & -0.61 & 1 \end{bmatrix} \quad D = \begin{bmatrix} 9.00 & 0 & 0 \\ 0 & 7.89 & 0 \\ 0 & 0 & 3.66 \end{bmatrix} \quad L' = \begin{bmatrix} 1 & -0.11 & 0.22 \\ 0 & 1 & -0.61 \\ 0 & 0 & 1 \end{bmatrix}$$

## Dialog Box

The **Main** pane of the LDL Factorization block dialog appears as follows.



### Non-positive definite input


Specify the action when nonpositive definite matrix inputs occur:

# LDL Factorization

---

- **Ignore** — Proceed with the computation and do not issue an alert. The output is not a valid factorization. A partial factorization is present in the upper left corner of the output.
- **Warning** — Display a warning message in the MATLAB Command Window, and continue the simulation. The output is not a valid factorization. A partial factorization is present in the upper left corner of the output.
- **Error** — Display an error dialog and terminate the simulation.

The **Data Types** pane of the LDL Factorization block dialog appears as follows.



## Rounding mode

Select the rounding mode for fixed-point operations.

## Overflow mode

Select the overflow mode for fixed-point operations.

## Intermediate product

Specify the intermediate product data type. As shown in “Fixed-Point Data Types” on page 2-856, the output of the multiplier is cast to the intermediate product data type before the next element of the input is multiplied into it. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as input`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Product output data type

Specify the product output data type. See “Fixed-Point Data Types” on page 2-856 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Accumulator data type

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-856 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-856 for illustrations depicting the use of the output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as input`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

# LDL Factorization

---

## References

Golub, G. H., and C. F. Van Loan. *Matrix Computations*. 3rd ed. Baltimore, MD: Johns Hopkins University Press, 1996.

## Supported Data Types

Port	Supported Data Types
S	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
LDL'	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>

## See Also

Cholesky Factorization	DSP System Toolbox
LDL Inverse	DSP System Toolbox
LDL Solver	DSP System Toolbox
LU Factorization	DSP System Toolbox
QR Factorization	DSP System Toolbox

See “Matrix Factorizations” for related information.


## Purpose

Compute inverse of Hermitian positive definite matrix using LDL factorization

## Library

Math Functions / Matrices and Linear Algebra / Matrix Inverses  
dspinverses

## Description



The LDL Inverse block computes the inverse of the Hermitian positive definite input matrix  $S$  by performing an LDL factorization.

$$S^{-1} = (LDL^*)^{-1}$$

$L$  is a lower triangular square matrix with unity diagonal elements,  $D$  is a diagonal matrix, and  $L^*$  is the Hermitian (complex conjugate) transpose of  $L$ . Only the diagonal and lower triangle of the input matrix are used, and any imaginary component of the diagonal entries is disregarded.

LDL factorization requires half the computation of Gaussian elimination (LU decomposition), and is always stable. It is more efficient than Cholesky factorization because it avoids computing the square roots of the diagonal elements.

The algorithm requires that the input be Hermitian positive definite. When the input is not positive definite, the block reacts with the behavior specified by the **Non-positive definite input** parameter. The following options are available:


- **Ignore** — Proceed with the computation and do not issue an alert. The output is not a valid inverse.
- **Warning** — Display a warning message in the MATLAB command window, and continue the simulation. The output is not a valid inverse.
- **Error** — Display an error dialog and terminate the simulation.

# LDL Inverse

---

**Note** The **Non-positive definite input** parameter is a diagnostic parameter. Like all diagnostic parameters on the Configuration Parameters dialog, it is set to Ignore in the code generated for this block by Simulink Coder code generation software.

---



## Dialog Box

### Non-positive definite input

Response to nonpositive definite matrix inputs.

## References

Golub, G. H., and C. F. Van Loan. *Matrix Computations*. 3rd ed. Baltimore, MD: Johns Hopkins University Press, 1996.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point

## See Also

Cholesky Inverse	DSP System Toolbox
LDL Factorization	DSP System Toolbox
LDL Solver	DSP System Toolbox
LU Inverse	DSP System Toolbox

Pseudoinverse      DSP System Toolbox  
inv                    MATLAB

See “Matrix Inverses” for related information.

# LDL Solver

---


## Purpose

Solve  $SX=B$  for  $X$  when  $S$  is square Hermitian positive definite matrix

## Library

Math Functions / Matrices and Linear Algebra / Linear System Solvers  
dpsolvers

## Description



The LDL Solver block solves the linear system  $SX=B$  by applying LDL factorization to the matrix at the S port, which must be square ( $M$ -by- $M$ ) and Hermitian positive definite. Only the diagonal and lower triangle of the matrix are used, and any imaginary component of the diagonal entries is disregarded. The input to the B port is the right side  $M$ -by- $N$  matrix,  $B$ . The  $M$ -by- $N$  output matrix  $X$  is the unique solution of the equations.

A length- $M$  unoriented vector input for right side  $B$  is treated as an  $M$ -by-1 matrix.

When the input is not positive definite, the block reacts with the behavior specified by the **Non-positive definite input** parameter. The following options are available:

- **Ignore** — Proceed with the computation and do not issue an alert. The output is not a valid solution.
- **Warning** — Proceed with the computation and display a warning message in the MATLAB Command Window. The output is not a valid solution.
- **Error** — Display an error dialog and terminate the simulation.

---

**Note** The **Non-positive definite input** parameter is a diagnostic parameter. Like all diagnostic parameters on the Configuration Parameters dialog, it is set to Ignore in the code generated for this block by Simulink Coder code generation software.

---

## Algorithm

The LDL algorithm uniquely factors the Hermitian positive definite input matrix  $S$  as

$$S = LDL^*$$

where  $L$  is a lower triangular square matrix with unity diagonal elements,  $D$  is a diagonal matrix, and  $L^*$  is the Hermitian (complex conjugate) transpose of  $L$ .

The equation

$$LDL^*X = B$$

is solved for  $X$  by the following steps:

**1** Substitute

$$Y = DL^*X$$

**2** Substitute

$$Z = L^*X$$

**3** Solve one diagonal and two triangular systems.

$$LY = B$$


$$DZ = Y$$

$$L^*X = Z$$

# LDL Solver

---

## Dialog Box



## Supported Data Types

### Non-positive definite input

Response to nonpositive definite matrix inputs.

- Double-precision floating point
- Single-precision floating point

## See Also

Autocorrelation LPC	DSP System Toolbox
Cholesky Solver	DSP System Toolbox
LDL Factorization	DSP System Toolbox
LDL Inverse	DSP System Toolbox
Levinson-Durbin	DSP System Toolbox
LU Solver	DSP System Toolbox
QR Solver	DSP System Toolbox

See “Linear System Solvers” for related information.


# Least Squares FIR Filter Design (Obsolete)

---

**Purpose** Design and implement least-squares FIR filter

**Library** dspobslib

**Description**



---

**Note** The Least Squares FIR Filter Design block is still supported but is likely to be obsoleted in a future release. We strongly recommend replacing this block with the Digital Filter block.

---

The Least Squares FIR Filter Design block designs an FIR filter and applies it to a discrete-time input using the Direct Form II Transpose Filter block. The filter design uses the Signal Processing Toolbox `firls` function to minimize the integral of the squared error between the desired frequency response and the actual frequency response.

An  $M$ -by- $N$  sample-based matrix input is treated as  $M*N$  independent channels, and an  $M$ -by- $N$  frame-based matrix input is treated as  $N$  independent channels. In both cases, the block filters each channel independently over time, and the output has the same size and frame status as the input.

The **Filter type** parameter allows you to specify one of the following filters:

- **Multiband** — The Multiband filter designs a linear-phase filter with an arbitrary magnitude response.
- **Differentiator** — The Differentiator filter approximates the ideal differentiator. Differentiators are antisymmetric FIR filters with approximately linear magnitude responses. To obtain the correct derivative, scale the **Gains at these frequencies** vector by  $\pi F_s$  rad/s, where  $F_s$  is the sample frequency in Hertz.

# Least Squares FIR Filter Design (Obsolete)



- Hilbert Transformer — The Hilbert Transformer filter approximates the ideal Hilbert transformer. Hilbert transformers are antisymmetric FIR filters with approximately constant magnitude.

The **Band-edge frequency vector** parameter is a vector of frequency points in the range 0 to 1, where 1 corresponds to half the sample frequency. This vector must have even length, and intermediate points must appear in ascending order. The **Gains at these frequencies** parameter is a vector containing the desired magnitude response at the corresponding points in the **Band-edge frequency vector**.

Each odd-indexed frequency-amplitude pair defines the left endpoint of a line segment representing the desired magnitude response in that frequency band. The corresponding even-indexed frequency-amplitude pair defines the right endpoint. Between the frequency bands specified by these end-points, there may be undefined sections of the specified frequency response. These are called “don’t care” or “transition” regions, and the magnitude response in these areas is a result of the optimization in the other (specified) frequency ranges.

$$\begin{array}{l} \text{Band edge frequency} = [0 \quad 0.3 \quad 0.4 \quad 0.6 \quad 0.7 \quad 1] \\ \text{Gains} = [0 \quad 1 \quad 0 \quad 0 \quad 0.5 \quad 0.5] \end{array}$$

Band:      2            1            1



# Least Squares FIR Filter Design (Obsolete)

---

The **Weights** parameter is a vector that specifies the emphasis to be placed on minimizing the error in certain frequency bands relative to others. This vector specifies one weight per band, so it is half the length of the **Band-edge frequency vector** and **Gains at these frequencies** vectors.

In most cases, differentiators and Hilbert transformers have only a single band, so the weight is a scalar value that does not affect the final filter. However, the **Weights** parameter is useful when using the block to design an antisymmetric multiband filter, such as a Hilbert transformer with stopbands.

For more information on the **Band-edge frequency vector**, **Gains at these frequencies**, and **Weights** parameters, see “Filter Designs and Implementation” in the Signal Processing Toolbox documentation. For more on the FIR filter algorithm, see the description of the `firls` function in the Signal Processing Toolbox documentation.

## Examples

### Example 1: Multiband

Consider a lowpass filter with a transition band in the normalized frequency range 0.4 to 0.5, and 10 times more error minimization in the stopband than the passband. In this case,

- **Filter type** = Multiband
- **Band-edge frequency vector** = [0 0.4 0.5 1]
- **Gains at these frequencies** = [1 1 0 0]
- **Weights** = [1 10]

### Example 2: Differentiator

Assume the specifications for a differentiator filter require it to have order 21. The “ramp” response extends over the entire frequency range. In this case, specify:

- **Filter type** = Differentiator
- **Filter order** = 21

# Least Squares FIR Filter Design (Obsolete)

---

- **Band-edge frequency vector** = [0 1]
- **Gains at these frequencies** = [0  $\pi * F_s$ ]

For a type III (even order) filter, the differentiation band should stop short of half the sample frequency. For example, if the filter order is 20, you could specify the block parameters as follows:

- **Filter type** = Differentiator
- **Filter order** = 20
- **Band-edge frequency vector** = [0 0.9]
- **Gains at these frequencies** = [0  $0.9 * \pi * F_s$ ]


### **Example 3: Hilbert Transformer**

Assume the specifications for a Hilbert transformer filter require it to have order 21. The passband extends over approximately the entire frequency range. In this case, specify:

- **Filter type** = Hilbert Transform
- **Filter order** = 21
- **Band-edge frequency vector** = [0.1 1]
- **Gains at these frequencies** = [1 1]

# Least Squares FIR Filter Design (Obsolete)

## Dialog Box



### Filter type

The filter type. Tunable.

### Filter order

The filter order.

### Band-edge frequency vector

A vector of frequency points, in ascending order, in the range 0 to 1. The value 1 corresponds to half the sample frequency. This vector must have even length. Tunable.

### Gains at these frequencies

A vector of frequency-response amplitudes corresponding to the points in the **Band-edge frequency vector**. This vector must be the same length as the **Band-edge frequency vector**. Tunable.

# Least Squares FIR Filter Design (Obsolete)

---

## Weights

A vector containing one weight for each frequency band. This vector must be half the length of the **Band-edge frequency vector** and **Gains at these frequencies** vectors. Tunable.

## References

Oppenheim, A. V. and R. W. Schaffer. *Discrete-Time Signal Processing*. Englewood Cliffs, NJ: Prentice Hall, 1989.

Proakis, J. and D. Manolakis. *Digital Signal Processing*. 3rd ed. Englewood Cliffs, NJ: Prentice-Hall, 1996.


## Purpose

Compute polynomial coefficients that best fit input data in least-squares sense

## Library

Math Functions / Polynomial Functions  
dspolyfun

## Description



The Least Squares Polynomial Fit block computes the coefficients of the  $n$ th order polynomial that best fits the input data in the least-squares sense, where you specify  $n$  in the **Polynomial order** parameter. A distinct set of  $n+1$  coefficients is computed for each column of the  $M$ -by- $N$  input,  $u$ .

For a given input column, the block computes the set of coefficients,  $c_1, c_2, \dots, c_{n+1}$ , that minimizes the quantity

$$\sum_{i=1}^M (u_i - \hat{u}_i)^2$$

where  $u_i$  is the  $i$ th element in the input column, and

$$\hat{u}_i = f(x_i) = c_1 x_i^n + c_2 x_i^{n-1} + \dots + c_{n+1}$$

The values of the independent variable,  $x_1, x_2, \dots, x_M$ , are specified as a length- $M$  vector by the **Control points** parameter. The same  $M$  control points are used for all  $N$  polynomial fits, and can be equally or unequally spaced. The equivalent MATLAB code is shown below.

```
c = polyfit(x,u,n)           % Equivalent MATLAB code
```

For convenience, the block treats length- $M$  unoriented vector input as an  $M$ -by-1 matrix.

Each column of the  $(n+1)$ -by- $N$  output matrix,  $c$ , represents a set of  $n+1$  coefficients describing the best-fit polynomial for the corresponding column of the input. The coefficients in each column are arranged in order of descending exponents,  $c_1, c_2, \dots, c_{n+1}$ .


# Least Squares Polynomial Fit

## Examples


In the `ex_leastsqreopolyfit_ref` model below, the Polynomial Evaluation block uses the second-order polynomial

$$y = -2u^2 + 3$$

to generate four values of dependent variable  $y$  from four values of independent variable  $u$ , received at the top port. The polynomial coefficients are supplied in the vector `[-2 0 3]` at the bottom port. Note that the coefficient of the first-order term is zero.



The **Control points** parameter of the Least Squares Polynomial Fit block is configured with the same four values of independent variable  $u$  that are used as input to the Polynomial Evaluation block, `[1 2 3 4]`. The Least Squares Polynomial Fit block uses these values together with the input values of dependent variable  $y$  to reconstruct the original polynomial coefficients.



## Dialog Box

### Control points

The values of the independent variable to which the data in each input column correspond. For an  $M$ -by- $N$  input, this parameter must be a length- $M$  vector. Tunable.

### Polynomial order

The order,  $n$ , of the polynomial to be used in constructing the best fit. The number of coefficients is  $n+1$ .

## Supported Data Types

- Double-precision floating point
- Single-precision floating point

## See Also

Detrend	DSP System Toolbox
Polynomial Evaluation	DSP System Toolbox
Polynomial Stability Test	DSP System Toolbox
polyfit	MATLAB

# Levinson-Durbin


## Purpose

Solve linear system of equations using Levinson-Durbin recursion

## Library

Math Functions / Matrices and Linear Algebra / Linear System Solvers  
dpsolvers

## Description



The Levinson-Durbin block solves the  $n$ th-order system of linear equations

$$Ra = b$$

in the cases where:

- $R$  is a Hermitian, positive-definite, Toeplitz matrix.
- $b$  is identical to the first column of  $R$  shifted by one element and with the opposite sign.

$$\begin{bmatrix} r(1) & r^*(2) & \cdots & r^*(n) \\ r(2) & r(1) & \cdots & r^*(n-1) \\ \vdots & \vdots & \ddots & \vdots \\ r(n) & r(n-1) & \cdots & r(1) \end{bmatrix} \begin{bmatrix} a(2) \\ a(3) \\ \vdots \\ a(n+1) \end{bmatrix} = \begin{bmatrix} -r(2) \\ -r(3) \\ \vdots \\ -r(n+1) \end{bmatrix}$$

The input to the block,  $r = [r(1) \ r(2) \ \dots \ r(n+1)]$ , can be a vector or a matrix. If the input is a matrix, the block treats each column as an independent channel and solves it separately. Each channel of the input contains lags 0 through  $n$  of an autocorrelation sequence, which appear in the matrix  $R$ .

The block can output the polynomial coefficients,  $A$ , the reflection coefficients,  $K$ , and the prediction error power,  $P$ , in various combinations. The **Output(s)** parameter allows you to enable the  $A$  and  $K$  outputs by selecting one of the following settings:

- $A$  — For each channel, port A outputs  $A=[1 \ a(2) \ a(3) \ \dots \ a(n+1)]$ , the solution to the Levinson-Durbin equation.  $A$  has the same dimension as the input. You can also view the elements of each

output channel as the coefficients of an  $n$ th-order autoregressive (AR) process.

- **K** — For each channel, port **K** outputs  $K=[k(1) \ k(2) \ \dots \ k(n)]$ , which contains  $n$  reflection coefficients and has the same dimension as the input, less one element. A scalar input channel causes an error when you select **K**. You can use reflection coefficients to realize a lattice representation of the AR process described later in this page.
- **A** and **K** — The block outputs both representations at their respective ports. A scalar input channel causes an error when you select **A** and **K**.

Select the **Output prediction error power (P)** check box to output the prediction error power for each channel,  $P$ . For each channel,  $P$  represents the power of the output of an FIR filter with taps  $A$  and input autocorrelation described by  $r$ , where  $A$  represents a prediction error filter and  $r$  is the input to the block. In this case,  $A$  is a whitening filter.  $P$  has one element per input channel.

When you select the **If the value of lag 0 is zero, A=[1 zeros], K=[zeros], P=0** check box (default), an input channel whose  $r(1)$  element is zero generates a zero-valued output. When you clear this check box, an input with  $r(1) = 0$  generates NaNs in the output. In general, an input with  $r(1) = 0$  is invalid because it does not construct a positive-definite matrix  $R$ . Often, however, blocks receive zero-valued inputs at the start of a simulation. The check box allows you to avoid propagating NaNs during this period.

## Applications

One application of the Levinson-Durbin formulation implemented by this block is in the Yule-Walker AR problem, which concerns modeling an unknown system as an autoregressive process. You would model such a process as the output of an all-pole IIR filter with white Gaussian noise input. In the Yule-Walker problem, the use of the signal's autocorrelation sequence to obtain an optimal estimate leads to an  $Ra = b$  equation of the type shown above, which is most efficiently solved by Levinson-Durbin recursion. In this case, the input to the block

## Levinson-Durbin

---

represents the autocorrelation sequence, with  $r(1)$  being the zero-lag value. The output at the block's A port then contains the coefficients of the autoregressive process that optimally models the system. The coefficients are ordered in descending powers of  $z$ , and the AR process is minimum phase. The prediction error,  $G$ , defines the gain for the unknown system, where  $G = \sqrt{P}$ :

$$H(z) = \frac{G}{A(z)} = \frac{G}{1 + a(2)z^{-1} + \dots + a(n+1)z^{-n}}$$

The output at the block's K port contains the corresponding reflection coefficients,  $[k(1) \ k(2) \ \dots \ k(n)]$ , for the lattice realization of this IIR filter. The Yule-Walker AR Estimator block implements this autocorrelation-based method for AR model estimation, while the Yule-Walker Method block extends the method to spectral estimation.

Another common application of the Levinson-Durbin algorithm is in linear predictive coding, which is concerned with finding the coefficients of a moving average (MA) process (or FIR filter) that predicts the next value of a signal from the current signal sample and a finite number of past samples. In this case, the input to the block represents the signal's autocorrelation sequence, with  $r(1)$  being the zero-lag value, and the output at the block's A port contains the coefficients of the predictive MA process (in descending powers of  $z$ ).

$$H(z) = A(z) = 1 + a(2)z^{-1} + \dots + a(n+1)z^{-n}$$

These coefficients solve the following optimization problem:

$$\min_{\{a_i\}} E \left[ \left| x_n - \sum_{i=1}^N a_i x_{n-i} \right|^2 \right]$$

Again, the output at the block's K port contains the corresponding reflection coefficients,  $[k(1) \ k(2) \ \dots \ k(n)]$ , for the lattice realization of this FIR filter. The Autocorrelation LPC block in the Linear Prediction library implements this autocorrelation-based prediction method.


## Fixed-Point Data Types

The diagrams in this section show the data types used within the Levinson-Durbin block for fixed-point signals.

After initialization the block performs  $n$  updates. At the  $(j+1)$  update,

$$\text{value in accumulator} = r(j+1) + \sum a_j(i) \times r(j-i+1)$$

The following diagram displays the fixed-point data types used in this calculation:



The block then updates the reflection coefficients  $K$  according to


$$K_{j+1} = \text{value in accumulator} / P_j$$

The block then updates the prediction error power  $P$  according to

$$P_{j+1} = P_j - P_j \times K_{j+1} \times \text{conj}(K_{j+1})$$

# Levinson-Durbin


The next diagram displays the fixed-point data types used in this calculation:



The polynomial coefficients  $A$  are then updated according to

$$a_{j+1}(i) = a_j(i) + K_{j+1} \times \text{conj}(a_j(j-1+i))$$

This diagram displays the fixed-point data types used in this calculation:




## Algorithm

The algorithm requires  $O(n^2)$  operations for each input channel. This implementation is therefore much more efficient for large  $n$  than

standard Gaussian elimination, which requires  $O(n^3)$  operations per channel.

## Dialog Box

The **Main** pane of the Levinson-Durbin block dialog box appears as follows.



# Levinson-Durbin

---

## Output(s)

Specify the solution representation of  $Ra = b$  to output: model coefficients (A), reflection coefficients (K), or both (A and K). When the input is a scalar or row vector, you must set this parameter to A.

## Output prediction error power (P)

Select to output the prediction error at port P.


## If the value of lag 0 is zero, A=[1 zeros], K=[zeros], P=0

When you select this check box and the first element of the input,  $r(1)$ , is zero, the block outputs the following vectors, as appropriate:

- $A = [1 \text{ zeros}(1, n)]$
- $K = [\text{zeros}(1, n)]$
- $P = 0$

When you clear this check box, the block outputs a vector of NaNs for each channel whose  $r(1)$  element is zero.

The **Data Types** pane of the Levinson-Durbin block dialog box appears as follows.



**Note** Floating-point inheritance takes precedence over the data type settings defined on this pane. When inputs are floating point, the block ignores these settings, and all internal data types are floating point.

### Rounding mode

Select the rounding mode for fixed-point operations.

## Overflow mode

Select the overflow mode for fixed-point operations.

## Product output data type

Specify the product output data type. See “Fixed-Point Data Types” on page 2-881 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as input`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Accumulator data type

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-881 for illustrations depicting the use of the accumulator data type in this block. You can set it to:


- A rule that inherits a data type, for example, `Inherit: Same as input`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

**Polynomial coefficients (A)**

Specify the polynomial coefficients (*A*) data type. See “Fixed-Point Data Types” on page 2-881 for illustrations depicting the use of the *A* data type in this block. You can set it to an expression that evaluates to a valid data type, for example, `fixdt(1,16,15)`.

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **A** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

**Reflection coefficients (K)**

Specify the polynomial coefficients (*A*) data type. See “Fixed-Point Data Types” on page 2-881 for illustrations depicting the use of the *K* data type in this block. You can set it to an expression that evaluates to a valid data type, for example, `fixdt(1,16,15)`.

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **K** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

**Prediction error power (P)**

Specify the prediction error power (*P*) data type. See “Fixed-Point Data Types” on page 2-881 for illustrations depicting the use of the *P* data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as input`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **P** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Minimum

Specify the minimum values that the polynomial coefficients, reflection coefficients, or prediction error power should have. The default value is [ ] (unspecified). Simulink software uses this value to perform:

- Parameter range checking (see “Check Parameter Values”)
- Automatic scaling of fixed-point data types

## Maximum

Specify the maximum values that the polynomial coefficients, reflection coefficients, or prediction error power should have. The default value is [ ] (unspecified). Simulink software uses this value to perform:

- Parameter range checking (see “Check Parameter Values”)
- Automatic scaling of fixed-point data types

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## References

Golub, G. H. and C. F. Van Loan. Sect. 4.7 in *Matrix Computations*. 3rd ed. Baltimore, MD: Johns Hopkins University Press, 1996.

Ljung, L. *System Identification: Theory for the User*. Englewood Cliffs, NJ: Prentice Hall, 1987. Pgs. 278–280.

Kay, Steven M. *Modern Spectral Estimation: Theory and Application*. Englewood Cliffs, NJ: Prentice Hall, 1988.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point
- Fixed point (signed only)
- 8-, 16-, and 32-bit signed integers

## See Also

Cholesky Solver	DSP System Toolbox
LDL Solver	DSP System Toolbox
Autocorrelation LPC	DSP System Toolbox
LU Solver	DSP System Toolbox
QR Solver	DSP System Toolbox
Yule-Walker AR Estimator	DSP System Toolbox
Yule-Walker Method	DSP System Toolbox
levinson	Signal Processing Toolbox

See “Linear System Solvers” for related information.


# LMS Adaptive Filter (Obsolete)

---

**Purpose** Compute filter estimates for input using LMS adaptive filter algorithm

**Library** dspobslib

## Description



---

**Note** The LMS Adaptive Filter block is still supported but is likely to be obsoleted in a future release. We strongly recommend replacing this block with the LMS Filter block.

---

The LMS Adaptive Filter block implements an adaptive FIR filter using the stochastic gradient algorithm known as the normalized least mean-square (LMS) algorithm.

$$y(n) = \hat{w}^H(n-1)u(n)$$
$$e(n) = d(n) - y(n)$$
$$\hat{w}(n) = \hat{w}(n-1) + \frac{u(n)}{a + u^H(n)u(n)} \mu e^*(n)$$

The variables are as follows.

Variable	Description
$n$	The current algorithm iteration
$u(n)$	The buffered input samples at step $n$
$\hat{w}(n)$	The vector of filter-tap estimates at step $n$
$y(n)$	The filtered output at step $n$
$e(n)$	The estimation error at step $n$
$d(n)$	The desired response at step $n$
$\mu$	The adaptation step size

To overcome potential numerical instability in the tap-weight update, a small positive constant ( $\alpha = 1e-10$ ) has been added in the denominator.

To turn off normalization, clear the **Use normalization** check box in the parameter dialog. The block then computes the filter-tap estimate as

$$\hat{w}(n) = \hat{w}(n-1) + u(n)\mu e^*(n)$$

The block icon has port labels corresponding to the inputs and outputs of the LMS algorithm. Note that inputs to the In and Err ports must be sample-based scalars. The signal at the Out port is a scalar, while the signal at the Taps port is a sample-based vector.

Block Ports	Corresponding Variables
In	$u$ , the scalar input, which is internally buffered into the vector $u(n)$
Out	$y(n)$ , the filtered scalar output
Err	$e(n)$ , the scalar estimation error
Taps	$\hat{w}(n)$ , the vector of filter-tap estimates

# LMS Adaptive Filter (Obsolete)

---

An optional **Adapt** input port is added when you select the **Adapt input** check box in the dialog. When this port is enabled, the block continuously adapts the filter coefficients while the **Adapt** input is nonzero. A zero-valued input to the **Adapt** port causes the block to stop adapting, and to hold the filter coefficients at their current values until the next nonzero **Adapt** input.


The **FIR filter length** parameter specifies the length of the filter that the LMS algorithm estimates. The **Step size** parameter corresponds to  $\mu$  in the equations. Typically, for convergence in the mean square,  $\mu$  must be greater than 0 and less than 2. The **Initial value of filter taps** specifies the initial value  $\hat{w}(0)$  as a vector, or as a scalar to be repeated for all vector elements. The **Leakage factor** specifies the value of the leakage factor,  $1 - \mu\alpha$ , in the leaky LMS algorithm below. This parameter must be between 0 and 1.

$$\hat{w}(n+1) = (1 - \mu\alpha)\hat{w}(n) + \frac{u(n)}{u^H(n)u(n)} \mu e^*(n)$$

## Examples

See the `lmsadeq` and `lmsadtde` demos.

## Dialog Box



### **FIR filter length**

The length of the FIR filter.

### **Step-size**

The step-size, usually in the range (0, 2). Tunable.

### **Initial value of filter taps**

The initial FIR filter coefficients.

### **Leakage factor**

The leakage factor, in the range [0, 1]. Tunable.

### **Use normalization**

Select this check box to compute the filter-tap estimate using the normalized equations.

# LMS Adaptive Filter (Obsolete)

---

## Adapt input

Enables the Adapt port when selected.

## References

Haykin, S. *Adaptive Filter Theory*. 3rd ed. Englewood Cliffs, NJ: Prentice Hall, 1996.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point

## See Also

Kalman Adaptive Filter                      DSP System Toolbox  
(Obsolete)


RLS Adaptive Filter (Obsolete)        DSP System Toolbox

See “Adaptive Filters in Simulink” for related information.

**Purpose** Compute output, error, and weights using LMS adaptive algorithm

**Library** Filtering / Adaptive Filters  
dspadpt3

## Description



The LMS Filter block can implement an adaptive FIR filter using five different algorithms. The block estimates the filter weights, or coefficients, needed to minimize the error,  $e(n)$ , between the output signal  $y(n)$  and the desired signal,  $d(n)$ . Connect the signal you want to filter to the Input port. The input signal can be a scalar or a column vector. Connect the desired signal to the Desired port. The desired signal must have the same data type, complexity, and dimensions as the input signal. The Output port outputs the filtered input signal, which is the estimate of the desired signal. The Error port outputs the result of subtracting the output signal from the desired signal.

When you select **LMS** for the **Algorithm** parameter, the block calculates the filter weights using the least mean-square (LMS) algorithm. This algorithm is defined by the following equations.

$$y(n) = \mathbf{w}^T(n-1)\mathbf{u}(n)$$

$$e(n) = d(n) - y(n)$$

$$\mathbf{w}(n) = \mathbf{w}(n-1) + f(\mathbf{u}(n), e(n), \mu)$$

The weight update function for the LMS adaptive filter algorithm is defined as

$$f(\mathbf{u}(n), e(n), \mu) = \mu e(n) \mathbf{u}^*(n)$$

# LMS Filter

---

The variables are as follows.

Variable	Description
$n$	The current time index
$\mathbf{u}(n)$	The vector of buffered input samples at step $n$
$\mathbf{u}^*(n)$	The complex conjugate of the vector of buffered input samples at step $n$
$\mathbf{w}(n)$	The vector of filter weight estimates at step $n$
$y(n)$	The filtered output at step $n$
$e(n)$	The estimation error at step $n$
$d(n)$	The desired response at step $n$
$\mu$	The adaptation step size

When you select **Normalized LMS** for the **Algorithm** parameter, the block calculates the filter weights using the normalized LMS algorithm. The weight update function for the normalized LMS algorithm is defined as

$$f(\mathbf{u}(n), e(n), \mu) = \mu e(n) \frac{\mathbf{u}^*(n)}{\varepsilon + \mathbf{u}^H(n)\mathbf{u}(n)}$$

To overcome potential numerical instability in the update of the weights, a small positive constant, epsilon, has been added in the denominator. For double-precision floating-point input, epsilon is 2.2204460492503131e-016. For single-precision floating-point input, epsilon is 1.192092896e-07. For fixed-point input, epsilon is 0.

When you select **Sign-Error LMS** for the **Algorithm** parameter, the block calculates the filter weights using the LMS algorithm equations. However, each time the block updates the weights, it replaces the error

term  $e(n)$  with +1 when the error term is positive, -1 when it is negative, or 0 when it is zero.

When you select **Sign-Data LMS** for the **Algorithm** parameter, the block calculates the filter weights using the LMS algorithm equations. However, each time the block updates the weights, it replaces each sample of the input vector  $\mathbf{u}(n)$  with +1 when the input sample is positive, -1 when it is negative, or 0 when it is zero.

When you select **Sign-Sign LMS** for the **Algorithm** parameter, the block calculates the filter weights using the LMS algorithm equations. However, each time the block updates the weights, it replaces the error term  $e(n)$  with +1 when the error term is positive, -1 when it is negative, or 0 when it is zero. It also replaces each sample of the input vector  $\mathbf{u}(n)$  with +1 when the input sample is positive, -1 when it is negative, or 0 when it is zero.

Use the **Filter length** parameter to specify the length of the filter weights vector.

The **Step size (mu)** parameter corresponds to  $\mu$  in the equations. For convergence of the normalized LMS equations,  $0 < \mu < 2$ . You can either specify a step size using the input port, Step-size, or by entering a value in the Block Parameters: LMS Filter dialog.

Use the **Leakage factor (0 to 1)** parameter to specify the leakage factor  $1 - \mu\alpha$  where  $0 < 1 - \mu\alpha \leq 1$  in the leaky LMS algorithm shown below.

$$\mathbf{w}(n) = (1 - \mu\alpha)\mathbf{w}(n-1) + f(\mathbf{u}(n), e(n), \mu)$$

When you select **LMS** from the **Algorithm** list, the weight update function in the above equation is the LMS weight update function. When you select **Normalized LMS** from the **Algorithm** list, the weight update function in the above equation is the normalized LMS weight update function.

Enter the initial filter weights  $\mathbf{w}(0)$  as a vector or a scalar in the **Initial value of filter weights** text box. When you enter a scalar, the block uses the scalar value to create a vector of filter weights. This vector


has length equal to the filter length and all of its values are equal to the scalar value.

When you select the **Adapt port** check box, an Adapt port appears on the block. When the input to this port is greater than zero, the block continuously updates the filter weights. When the input to this port is less than or equal to zero, the filter weights remain at their current values.


When you want to reset the value of the filter weights to their initial values, use the **Reset port** parameter. The block resets the filter weights whenever a reset event is detected at the Reset port. The reset signal rate must be the same rate as the data signal input.

From the **Reset port** list, select **None** to disable the Reset port. To enable the Reset port, select one of the following from the **Reset port** list:

- **Rising edge** — Triggers a reset operation when the Reset input does one of the following:
  - Rises from a negative value to a positive value or zero
  - Rises from zero to a positive value, where the rise is not a continuation of a rise from a negative value to zero (see the following figure)



- **Falling edge** — Triggers a reset operation when the Reset input does one of the following:
  - Falls from a positive value to a negative value or zero
  - Falls from zero to a negative value, where the fall is not a continuation of a fall from a positive value to zero (see the following figure)



- **Either edge** — Triggers a reset operation when the Reset input is a Rising edge or Falling edge (as described above)
- **Non-zero sample** — Triggers a reset operation at each sample time that the Reset input is not zero

Select the **Output filter weights** check box to create a Wts port on the block. For each iteration, the block outputs the current updated filter weights from this port.

## Fixed-Point Data Types


The following diagrams show the data types used within the LMS Filter block for fixed-point signals; the table summarizes the definitions of variables used in the diagrams:

# LMS Filter


Variable	Definition
$\mathbf{u}$	Input vector
$\mathbf{W}$	Vector of filter weights
$\mu$	Step size
$e$	Error
$Q$	Quotient, $Q = \frac{\mu \cdot e}{\mathbf{u}'\mathbf{u}}$
Product $\mathbf{u}'\mathbf{u}$	Product data type in Energy calculation diagram
Accumulator $\mathbf{u}'\mathbf{u}$	Accumulator data type in Energy calculation diagram
Product $\mathbf{W}\mathbf{u}$	Product data type in Convolution diagram
Accumulator $\mathbf{W}\mathbf{u}$	Accumulator data type in Convolution diagram
Product $\mu \cdot e$	Product data type in Product of step size and error diagram
Product $Q \cdot \mathbf{u}$	Product and accumulator data type in Weight update diagram. <sup>1</sup>

<sup>1</sup>The accumulator data type for this quantity is automatically set to be the same as the product data type. The minimum, maximum, and overflow information for this accumulator is logged as part of the product information. Autoscaling treats this product and accumulator as one data type.


## Energy calculation (for normalized LMS algorithm only)



## Convolution




## Output error signal




# LMS Filter


## Product of step size and error (for LMS and Sign-Data LMS algorithms only)



## Quotient (for normalized LMS only)



## Weight update



You can set the data type of the parameters, weights, products, quotient, and accumulators in the block mask. Fixed-point inputs, outputs, and mask parameters of this block must have the following characteristics:

- The input signal and the desired signal must have the same word length, but their fraction lengths can differ.


- The step size and leakage factor must have the same word length, but their fraction lengths can differ.
- The output signal and the error signal have the same word length and the same fraction length as the desired signal.
- The quotient and the product output of the  $\mathbf{u}'\mathbf{u}$ ,  $\mathbf{W}\mathbf{u}$ ,  $\mu \cdot e$ , and  $Q \cdot \mathbf{u}$  operations must have the same word length, but their fraction lengths can differ.
- The accumulator data type of the  $\mathbf{u}'\mathbf{u}$  and  $\mathbf{W}\mathbf{u}$  operations must have the same word length, but their fraction lengths can differ.

The output of the multiplier is in the product output data type if at least one of the inputs to the multiplier is real. If both of the inputs to the multiplier are complex, the result of the multiplication is in the accumulator data type. For details on the complex multiplication performed, see “Multiplication Data Types”.

# LMS Filter

## Dialog Box

The **Main** pane of the LMS Filter block dialog appears as follows.



**Algorithm**

Choose the algorithm used to calculate the filter weights.

**Filter length**

Enter the length of the FIR filter weights vector.

**Specify step size via**

Select Dialog to enter a value for step size in the Block parameters: LMS Filter dialog. Select Input port to specify step size using the Step-size input port.

**Step size ( $\mu$ )**

Enter the step size  $\mu$ . Tunable.

**Leakage factor (0 to 1)**

Enter the leakage factor,  $0 < 1 - \mu\alpha \leq 1$ . Tunable.

**Initial value of filter weights**

Specify the initial values of the FIR filter weights.

**Adapt port**

Select this check box to enable the Adapt input port.


**Reset port**

Select this check box to enable the Reset input port.

**Output filter weights**

Select this check box to export the filter weights from the Wts port.

The **Data Types** pane of the LMS Filter block dialog appears as follows.



## Rounding mode

Select the rounding mode for fixed-point operations.

## Overflow mode

Select the overflow mode for fixed-point operations.

## Parameters

This parameter is visible if, for the **Specify step size via** parameter, you choose **Dialog**. Choose how you specify the word length and the fraction length of the leakage factor and step size:

- When you select **Same word length as first input**, the word length of the leakage factor and step size match that of the first input to the block. In this mode, the fraction length of the leakage factor and step size is automatically set to the binary-point only scaling that provides you with the best precision possible given the value and word length of the coefficients.
- When you select **Specify word length**, you can enter the word length of the leakage factor and step size, in bits. In this mode, the fraction length of the leakage factor and step size is automatically set to the binary-point only scaling that provides you with the best precision possible given the value and word length of the coefficients.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the leakage factor and step size, in bits. The leakage factor and the step size must have the same word length, but the fraction lengths can differ.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the leakage factor and step size. The leakage factor and the step size must have the same word length, but the slopes can differ. This block requires a power-of-two slope and a bias of zero.

If, for the **Specify step size via** parameter, you choose **Input port**, the word length of the leakage factor is the same as the word length of the step size input at the Step size port. The fraction length of the leakage factor is automatically set to the best precision possible based on the word length of the leakage factor.

## Weights

Choose how you specify the word length and fraction length of the filter weights of the block:

- When you select **Same as first input**, the word length and fraction length of the filter weights match those of the first input to the block.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the filter weights, in bits.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the filter weights. This block requires a power-of-two slope and a bias of zero.

## Products & quotient

Choose how you specify the word length and fraction length of  $\mathbf{u}'\mathbf{u}$ ,  $\mathbf{W}'\mathbf{u}$ ,  $\mu \cdot e$ ,  $Q \cdot \mathbf{u}$ , and the quotient,  $Q$ . Here,  $\mathbf{u}$  is the input vector,  $\mathbf{W}$  is the vector of filter weights,  $\mu$  is the step size,  $e$  is the

error, and  $Q$  is the quotient, which is defined as  $Q = \frac{\mu \cdot e}{\mathbf{u}'\mathbf{u}}$

- When you select **Same as first input**, the word length and fraction length of these quantities match those of the first input to the block.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of these quantities, in bits. The word length of the quantities must be the same, but the fraction lengths can differ.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of these quantities. The word length of the quantities must be the same, but the slopes can differ. This block requires a power-of-two slope and a bias of zero.

### Accumulators

Use this parameter to specify how you would like to designate the word and fraction lengths of the accumulators for the  $\mathbf{u}'\mathbf{u}$  and  $\mathbf{W}'\mathbf{u}$  operations.

---

**Note** This parameter is *not* used to designate the word and fraction lengths of the accumulator for the  $\mathbf{Q} \cdot \mathbf{u}$  operation. The accumulator data type for this quantity is automatically set to be the same as the product data type. The minimum, maximum, and overflow information for this accumulator is logged as part of the product information. Autoscaling treats this product and accumulator as one data type.

---

See “Fixed-Point Data Types” on page 2-899 and “Multiplication Data Types” for illustrations depicting the use of the accumulator data type in this block:

- When you select **Same as first input**, these characteristics match those of the input to the block.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the accumulators, in bits. The word length of both the accumulators must be the same, but the fraction lengths can differ.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the accumulators. The word length of both the accumulators must be the same, but the slopes can differ. This block requires a power-of-two slope and a bias of zero.

### Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

# LMS Filter

---

## References

Hayes, M.H. *Statistical Digital Signal Processing and Modeling*. New York: John Wiley & Sons, 1996.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Signed fixed point</li></ul>
Desired	<ul style="list-style-type: none"><li>• Must be the same as Input for floating-point signals</li><li>• Must be any signed fixed-point data type when Input is fixed point</li></ul>
Step-size	<ul style="list-style-type: none"><li>• Must be the same as Input for floating-point signals</li><li>• Must be any signed fixed-point data type when Input is fixed point</li></ul>
Adapt	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
Reset	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Must be the same as Input for floating-point signals</li><li>• Must be the same as Desired for fixed-point signals</li></ul>

Port	Supported Data Types
Error	<ul style="list-style-type: none"> <li>• Must be the same as Input for floating-point signals</li> <li>• Must be the same as Desired for fixed-point signals</li> </ul>
Wts	<ul style="list-style-type: none"> <li>• Must be the same as Input for floating-point signals</li> <li>• Obeys the <b>Weights</b> parameter for fixed-point signals</li> </ul>

## See Also

Kalman Adaptive Filter (Obsolete)	DSP System Toolbox
RLS Filter	DSP System Toolbox
Block LMS Filter	DSP System Toolbox
Fast Block LMS Filter	DSP System Toolbox

See “Adaptive Filters in Simulink” for related information.


# Lowpass Filter

---

**Purpose** Design lowpass filter

**Library** Filtering / Filter Designs  
dspfdesign

**Description** This block brings the filter design capabilities of the `filterbuilder` function to the Simulink environment.



# Lowpass Filter

Function Block Parameters: Lowpass Filter

Lowpass Filter  
Design a lowpass filter.

[View Filter Response](#)

Filter specifications

Impulse response: FIR

Order mode: Minimum

Filter Type: Single-rate

Frequency specifications

Frequency units: Normalized (0 to 1) Input Fs: 2

Fpass: .45 Fstop: .55

Magnitude specifications

Magnitude units: dB

Apass: 1 Astop: 60

Algorithm

Design method: Equiripple

► Design options

Filter Implementation

Structure: Direct-form FIR

Use basic elements to enable filter customization

Input processing: Columns as channels (frame based)

Use symbolic names for coefficients

OK Cancel Help Apply

# Lowpass Filter

---

- Impulse response and step response in the time domain.
- Pole-zero information.

The tool also helps you evaluate filter performance by providing information about filter order, stability, and phase linearity. For more information on FVTool, see the Signal Processing Toolbox documentation.

## Filter Specifications

In this group, you specify your filter format, such as the impulse response and the filter order.

### Impulse response

Select either **FIR** or **IIR** from the drop-down list. **FIR** is the default. When you choose an impulse response, the design methods and structures you can use to implement your filter change accordingly.

---

**Note** The design methods and structures for **FIR** filters are not the same as the methods and structures for **IIR** filters.

---

### Order mode

Select **Minimum** (the default) or **Specify**. Selecting **Specify** enables the **Order** option so you can enter the filter order. When you set the **Impulse response** to **IIR**, you can specify different numerator and denominator orders. To specify a different denominator order, you must select the **Denominator order** check box.

### Order

Enter the filter order. This option is enabled only if you set the **Order mode** to **Specify**.

## Denominator order

Select this check box to specify a different denominator order. This option is enabled only if you set the **Impulse response** to IIR and the **Order mode** to Specify.

## Filter type

Select Single-rate, Decimator, Interpolator, or Sample-rate converter. Your choice determines the type of filter as well as the design methods and structures that are available to implement your filter. By default, the block specifies a single-rate filter.

- Selecting Decimator or Interpolator activates the **Decimation Factor** or the **Interpolation Factor** options respectively.
- Selecting Sample-rate converter activates both factors.

## Decimation Factor

Enter the decimation factor. This option is enabled only if the **Filter type** is set to Decimator or Sample-rate converter. The default value is 2.


## Interpolation Factor

Enter the interpolation factor. This option is enabled only if the **Filter type** is set to Interpolator or Sample-rate converter. The default value is 2.

## Frequency Specifications

The parameters in this group allow you to specify your filter response curve. Graphically, the filter specifications look similar to the one shown in the following figure.

# Lowpass Filter



In the figure, regions between specification values such as  $F_{\text{pass}}$  and  $F_{\text{stop}}$  represent transition regions where the filter response is not constrained.

## Frequency constraints

When **Order mode** is **Specify**, select the filter features that the block uses to define the frequency response characteristics. The list contains the following options, when available for the filter specifications.

- **Stopband edge and passband edge** — Define the filter by specifying the frequencies for the edges for the stop- and passbands.
- **Passband edge** — Define the filter by specifying the edge of the passband.
- **Stopband edge** — Define the filter by specifying the edge of the stopband.
- **Stopband edge and 3 dB point** — For IIR filters, define the filter by specifying the frequency of the 3 dB point in the filter response and the edge of the stopband.
- **3 dB point** — Define the filter response by specifying the location of the 3 dB point. The 3 dB point is the frequency for the point three decibels below the passband value.

- **3 dB point and passband edge** — For IIR filters, define the filter by specifying the frequency of the 3 dB point in the filter response and the edge of the passband.
- **6 dB point** — For FIR filters, define the filter response by specifying the location of the 6 dB point. The 6 dB point is the frequency for the point six decibels below the passband value.

## Frequency units

Use this parameter to specify whether your frequency settings are normalized or in absolute frequency. Select **Normalized (0 1)** to enter frequencies in normalized form. This behavior is the default. To enter frequencies in absolute values, select one of the frequency units from the drop-down list—Hz, kHz, MHz, or GHz. Selecting one of the unit options enables the **Input Fs** parameter.

## Input Fs

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter input. When you provide an input sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is available when you select one of the frequency options from the **Frequency units** list.

## Fpass

Enter the frequency at the of the passband. Specify the value in either normalized frequency units or the absolute units you select in **Frequency units**.

## Fstop

Enter the frequency at the start of the stopband. Specify the value in either normalized frequency units or the absolute units you select in **Frequency units**.

## F3dB

When **Frequency constraints** is **3 dB point, Stopband edge and 3 dB point**, or **3 dB point and passband edge**, specify the frequency of the 3 dB point. Specify the value in either normalized frequency units or the absolute units you select in **Frequency units**.

# Lowpass Filter

---

## F6dB

When **Frequency constraints** is 6 dB point, specify the frequency of the 6 dB point. Specify the value in either normalized frequency units or the absolute units you select **Frequency units**.

## Magnitude Specifications

Parameters in this group specify the filter response in the passbands and stopbands.

### Magnitude constraints

This option is only available when you specify the order of your filter design. Depending on the setting of the **Frequency constraints** parameter, some combination of the following options will be available for the **Magnitude constraints** parameter: Unconstrained, Passband ripple, Passband ripple and stopband attenuation or Stopband attenuation.

### Magnitude units

Specify the units for any parameter you provide in magnitude specifications. From the drop-down list, select one of the following options:

- Linear — Specify the magnitude in linear units.
- dB — Specify the magnitude in decibels (default)
- Squared — Specify the magnitude in squared units.

### Apass

Enter the filter ripple allowed in the passband in the units you choose for **Magnitude units**, either linear or decibels.

### Astop

Enter the filter attenuation in the stopband in the units you choose for **Magnitude units**, either linear or decibels.

## Algorithm

The parameters in this group allow you to specify the design method and structure of your filter.

## Design Method

Lists the design methods available for the frequency and magnitude specifications you entered. When you change the specifications for a filter, such as changing the impulse response, the methods available to design filters changes as well. The default IIR design method is usually Butterworth, and the default FIR method is Equiripple.

## Scale SOS filter coefficients to reduce chance of overflow

Selecting this parameter directs the design to scale the filter coefficients to reduce the chances that the inputs or calculations in the filter overflow and exceed the representable range of the filter. Clearing this option removes the scaling. This parameter applies only to IIR filters.

## Design Options

The options for each design are specific for each design method. This section does not present all of the available options for all designs and design methods. There are many more that you encounter as you select different design methods and filter specifications. The following options represent some of the most common ones available.

### Density factor

Density factor controls the density of the frequency grid over which the design method optimization evaluates your filter response function. The number of equally spaced points in the grid is the value you enter for **Density factor** times (filter order + 1).

Increasing the value creates a filter that more closely approximates an ideal equiripple filter but increases the time required to design the filter. The default value of 20 represents a reasonable trade between the accurate approximation to the ideal filter and the time to design the filter.

# Lowpass Filter

---

## Phase constraint

Specify the phase constraint of the filter as **Linear**, **Maximum**, or **Minimum**.

## Minimum order

When you select this parameter, the design method determines and design the minimum order filter to meet your specifications. Some filters do not provide this parameter. Select **Any**, **Even**, or **Odd** from the drop-down list to direct the design to be any minimum order, or minimum even order, or minimum odd order.

## Match Exactly

Specifies that the resulting filter design matches either the passband or stopband or both bands when you select passband or stopband or both from the drop-down list.

## Stopband Shape

Stopband shape lets you specify how the stopband changes with increasing frequency. Choose one of the following options:

- **Flat** — Specifies that the stopband is flat. The attenuation does not change as the frequency increases.
- **Linear** — Specifies that the stopband attenuation changes linearly as the frequency increases. Change the slope of the stopband by setting **Stopband decay**.
- **1/f** — Specifies that the stopband attenuation changes exponentially as the frequency increases, where  $f$  is the frequency. Set the power (exponent) for the decay in **Stopband decay**.

## Stopband Decay

When you set Stopband shape, Stopband decay specifies the amount of decay applied to the stopband. the following conditions apply to Stopband decay based on the value of Stopband Shape:

- When you set **Stopband shape** to Flat, **Stopband decay** has no effect on the stopband.
- When you set **Stopband shape** to Linear, enter the slope of the stopband in units of dB/rad/s. The block applies that slope to the stopband.
- When you set **Stopband shape** to  $1/f$ , enter a value for the exponent  $n$  in the relation  $(1/f)^n$  to define the stopband decay. The block applies the  $(1/f)^n$  relation to the stopband to result in an exponentially decreasing stopband attenuation.

## Filter Implementation

### Structure

For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter. By default, FIR filters use direct-form structure, and IIR filters use direct-form II filters with SOS.

### Use basic elements to enable filter customization

Select this check box to implement the filter as a subsystem of basic Simulink blocks. Clear the check box to implement the filter as a high-level subsystem. By default, this check box is cleared.

The high-level implementation provides better compatibility across various filter structures, especially filters that would contain algebraic loops when constructed using basic elements. On the other hand, using basic elements enables the following optimization parameters:

- **Optimize for zero gains** — Terminate chains that contain Gain blocks with a gain of zero.
- **Optimize for unit gains** — Remove Gain blocks that scale by a factor of one.
- **Optimize for delay chains** — Substitute delay chains made up of  $n$  unit delays with a single delay by  $n$ .

# Lowpass Filter

---

- **Optimize for negative gains** — Use subtraction in Sum blocks instead of negative gains in Gain blocks.

## Optimize for unit-scale values

Select this check box to scale unit gains between sections in SOS filters. This parameter is available only for SOS filters.

## Input processing

Specify how the block should process the input. The available options may vary depending on the settings of the **Filter Structure** and **Use basic elements for filter customization** parameters. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The Inherited (this choice will be removed see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Rate options

When the **Filter type** parameter specifies a multirate filter, select the rate processing rule for the block from following options:

- **Enforce single-rate processing** — When you select this option, the block maintains the sample rate of the input.
- **Allow multirate processing** — When you select this option, the block adjusts the rate at the output to accommodate an increased or reduced number of samples. To select this option,

you must set the **Input processing** parameter to Elements as channels (sample based).

### Use symbolic names for coefficients

Select this check box to enable the specification of coefficients using MATLAB variables. The available coefficient names differ depending on the filter structure. Using symbolic names allows tuning of filter coefficients in generated code. By default, this check box is cleared.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>


# LPC to LSF/LSP Conversion

---

**Purpose** Convert linear prediction coefficients to line spectral pairs or line spectral frequencies

**Library** Estimation / Linear Prediction  
dsp1p

## Description



The LPC to LSF/LSP Conversion block takes a vector or matrix of linear prediction coefficients (LPCs) and converts it to a vector or matrix of line spectral pairs (LSPs) or line spectral frequencies (LSFs). When converting LPCs to LSFs, the block outputs match those of the `poly2lsf` function.

The block input must be a sample-based row vector, which is treated as a single channel, or a matrix, which is treated as a single channel per column.

The input LPCs for each channel,  $1, a_1, a_2, \dots, a_m$ , must be the denominator of the transfer function of a stable all-pole filter with the form given in the first equation of “Requirements for Valid Outputs” on page 2-924. A length- $M+1$  input channel yields a length- $M$  output channel. Inputs can be sample based or frame based, but outputs are always sample based.

See other sections of this reference page to learn about how to ensure that you get valid outputs, how to detect invalid outputs, how the block computes the LSF/LSP values, and more.

## Requirements for Valid Outputs

To get valid outputs, your inputs and the **Root finding coarse grid points** parameter value must meet these requirements:

- The input LPCs for each channel,  $1, a_1, a_2, \dots, a_m$ , must come from the denominator of the following transfer function,  $H(z)$ , of a stable all-pole filter (all roots of  $H(z)$  must be inside the unit circle). Note that the first term in  $H(z)$ 's denominator must be 1. When the input LPCs do not come from a transfer function of the following form, the block outputs are invalid.

$$H(z) = \frac{1}{1 + a_1 z^{-1} + a_2 z^{-2} + \dots + a_m z^{-m}}$$

- The **Root finding coarse grid points** parameter value must be large enough so that the block can find all the LSP or LSF values. (The output LSFs and LSPs are roots of polynomials related to the input LPC polynomial; the block looks for these roots to produce the output. For details, see “LSF and LSP Computation Method: Chebyshev Polynomial Method for Root Finding” on page 2-932.) When you do not set **Root finding coarse grid points** to a high enough value relative to the number of LPCs, the block might not find all the LSPs or LSFs and yield invalid outputs as described in “Root Finding Method Limitations: Failure to Find Roots” on page 2-936.

To learn about recognizing invalid inputs and outputs and parameters for dealing with them, see “Handling and Recognizing Invalid Inputs and Outputs” on page 2-927.

## Setting Outputs to LSFs or LSPs

Set the **Output** parameter to one of the following settings to determine whether the block outputs LSFs or LSPs:

- **LSF in radians (0 pi)** — Block outputs the LSF values between 0 and  $\pi$  radians in increasing order. The block does not output the guaranteed LSF values, 0 and  $\pi$ .
- **LSF normalized in range (0 0.5)** — Block outputs normalized LSF values in increasing order, computed by dividing the LSF values between 0 and  $\pi$  radians by  $2\pi$ . The block does not output the guaranteed normalized LSF values, 0 and 0.5.
- **LSP in range (-1 1)** — Block outputs LSP values in decreasing order, equal to the cosine of the LSF values between 0 and  $\pi$  radians. The block does not output the guaranteed LSP values, -1 and 1.

# LPC to LSF/LSP Conversion

---

## Adjusting Output Computation Time and Accuracy with Root Finding Parameters

The values  $n$  and  $k$  determine the block's output computation time and accuracy, where

- $n$  is the value of the **Root finding coarse grid points** parameter (choose this value with care; see the note below).
- $k$  is the value of the **Root finding bisection refinement** parameter.
- Decreasing the values of  $n$  and  $k$  decreases the output computation time, but also decreases output accuracy:
  - The upper bound of block's computation time is proportional to  $k \cdot (n - 1)$ .
  - Each LSP output is within  $1/(n \cdot 2^k)$  of the actual LSP value.
  - Each LSF output is within  $\Delta LSF$  of the actual LSF value,  $LSF_{act}$ , where

$$\Delta LSF = \left| a \cos(LSF_{act}) - a \cos\left(LSF_{act} + 1/(n \cdot 2^k)\right) \right|$$

---

**Note** When the value of the **Root finding coarse grid points** parameter is too small relative to the number of LPCs, the block might output invalid data as described in “Requirements for Valid Outputs” on page 2-924. Also see “Handling and Recognizing Invalid Inputs and Outputs” on page 2-927.

---

## Notable Input and Output Properties

- To get valid outputs, your input LPCs and the value of the **Root finding coarse grid points** parameter must meet the requirements described in “Requirements for Valid Outputs” on page 2-924.
- Length- $L+1$  input channel yields length- $L$  output channel

- Output is always sample based
- **Output** parameter determines the output type (see “Setting Outputs to LSFs or LSPs” on page 2-925):
  - LSFs — frequencies,  $w_k$ , where  $0 < w_k < \pi$  and  $w_k < w_{k+1}$
  - Normalized LSFs —  $w_k / 2\pi$
  - LSPs —  $\cos(w_k)$

## Handling and Recognizing Invalid Inputs and Outputs

The block outputs invalid data when your input LPCs and the value of the **Root finding coarse grid points** parameter do not meet the requirements described in “Requirements for Valid Outputs” on page 2-924. The following topics describe what invalid outputs look like, and how to set the block parameters provided for handling invalid inputs and outputs:

- “What Invalid Outputs Look Like” on page 2-927
- “Parameters for Handling Invalid Inputs and Outputs” on page 2-928

## What Invalid Outputs Look Like

The channels of an invalid output have the same dimensions, sizes, and frame statuses as the channels of a valid output. However, invalid output channels do not contain all the LSP or LSF values. Instead, they contain none or some of the LSP and LSF values and the rest of the output is filled with place holder values (-1, 0.5, or  $\pi$ ) depending on the **Output** parameter setting).

In short, all invalid outputs in a channel end in one of the place holder values (-1, 0.5, or  $\pi$ ) as illustrated in the following table. To learn how to use the block’s parameters for handling invalid inputs and outputs, see the next section.

# LPC to LSF/LSP Conversion

Output Parameter Setting	Place Holder	Sample Invalid Outputs
LSF in radians (0 pi)	$\pi$	$[w_1 \ w_2 \ w_3 \ \pi \ \pi \ \pi \ \pi \ \pi]$
LSF normalized in range (0 0.5)	0.5	$\begin{bmatrix} w_1 \\ w_2 \\ 0.5 \end{bmatrix}$
LSP in range (-1 1)	-1	$\begin{bmatrix} \cos(w_{13}) \\ \cos(w_{23}) \\ -1 \\ -1 \\ -1 \end{bmatrix}$

## Parameters for Handling Invalid Inputs and Outputs

You must set how the block handles invalid inputs and outputs by setting these parameters:

- Show output validity status (1=valid, 0=invalid)** — Set this parameter to activate a second output port that outputs a vector with one Boolean element per channel; 1 when the output of the corresponding channel is valid, and 0 when the output is invalid. The LSF and LSP outputs are invalid when the block fails to find all the LSF or LSP values or when the input LPCs are unstable (for details, see “Requirements for Valid Outputs” on page 2-924). See the previous section to learn how to recognize invalid outputs.
- If current output is invalid, overwrite with previous output** — Select this check box to cause the block to overwrite invalid outputs with the previous output. When you set this parameter you also need to consider these parameters:


- **When first output is invalid, overwrite with user-defined values** — When the first input is unstable, you can overwrite the invalid first output with either

- The default values, by clearing this check box
- Values you specify, by selecting this check box

The default initial overwrite values are the LSF or LSP representations of an all-pass filter. The vector that is used to overwrite invalid output is stored as an internal state.

- **User-defined LSP/LSF values for overwriting invalid first output** — Specify a vector of values for overwriting an invalid first output if you selected the **When first output is invalid, overwrite with user-defined values** parameter. For multichannel inputs, provide a matrix with the same number of channels as the input, or one vector that will be applied to every channel. The vector or matrix of LSP/LSF values you specify should have the same dimension, size, and frame status as the other outputs.
- **If first input value is not 1** — The block output in any channel is invalid when the first coefficient in an LPC vector is not 1; this parameter determines what the block does when given such inputs:
  - **Ignore** — Proceed with computations as if the first coefficient is 1.
  - **Normalize** — Divide the input LPCs by the value of the first coefficient before computing the output.
  - **Normalize and warn** — In addition to **Normalize**, display a warning message at the MATLAB command line.
  - **Error** — Stop the simulation and display an error message at the MATLAB command line.

# LPC to LSF/LSP Conversion



## Dialog Box

### Output

Specifies whether to convert the input linear prediction polynomial coefficients (LPCs) to LSP in range  $(-1, 1)$ , LSF in radians  $(0, \pi)$ , or LSF normalized in range  $(0, 0.5)$ . See “Setting Outputs to LSFs or LSPs” on page 2-925 for descriptions of the three settings.

### Root finding coarse grid points

The value  $n$ , where the block divides the interval  $(-1, 1)$  into  $n$  subintervals of equal length, and looks for roots (LSP values) in each subinterval. You must pick  $n$  large enough or the block

output might be invalid as described in “Requirements for Valid Outputs” on page 2-924. To learn how the block uses this parameter to compute the output, see “LSF and LSP Computation Method: Chebyshev Polynomial Method for Root Finding” on page 2-932. Also see “Adjusting Output Computation Time and Accuracy with Root Finding Parameters” on page 2-926. Tunable.

## **Root finding bisection refinement**

The value  $k$ , where each LSP output is within  $1/(n \cdot 2^k)$  of the actual LSP value, where  $n$  is the value of the **Root finding coarse grid points** parameter. To learn how the block uses this parameter to compute the output, see “LSF and LSP Computation Method: Chebyshev Polynomial Method for Root Finding” on page 2-932. Also see “Adjusting Output Computation Time and Accuracy with Root Finding Parameters” on page 2-926. Tunable.

## **Show output validity status**

Set this parameter to activate a second output port that outputs a vector with one Boolean element per channel; 1 when the output of the corresponding channel is valid, and 0 when the output is invalid. The LSF and LSP outputs are invalid when the block fails to find all the LSF or LSP values or when the input LPCs are unstable (for details, see “Requirements for Valid Outputs” on page 2-924).

## **If current output is invalid, overwrite with previous output**

Selecting this check box causes the block to overwrite invalid outputs with the previous output. Setting this parameter activates other parameters for taking care of initial overwrite values (when the very first output of the block is invalid). For more information, see “Parameters for Handling Invalid Inputs and Outputs” on page 2-928.

## **When first output is invalid, overwrite with user-defined values**

When the first input is unstable, you can overwrite the invalid first output with either

- The default values, by clearing this check box

- Values you specify, by selecting this check box  
The default initial overwrite values are the LSF or LSP representations of an all-pass filter. The vector that is used to overwrite invalid output is stored as an internal state. For more information, see “Parameters for Handling Invalid Inputs and Outputs” on page 2-928.

### **User-defined LSP/LSF values for overwriting invalid first output**

Specify a vector of values for overwriting an invalid first output if you selected the **When first output is invalid, overwrite with user-defined values** parameter. For multichannel inputs, provide a matrix with the same number of channels as the input, or one vector that will be applied to every channel. The vector or matrix of LSP/LSF values you specify should have the same dimension, size, and frame status as the other outputs.

### **If first input value is not 1**

Determines what the block does when the first coefficient of an input is not 1. The block can either proceed with computations as when the first coefficient is 1 (**Ignore**); divide the input LPCs by the value of the first coefficient before computing the output (**Normalize**); in addition to **Normalize**, display a warning message at the MATLAB command line (**Normalize and warn**); stop the simulation and display an error message at the MATLAB command line (**Error**). For more information, see “Parameters for Handling Invalid Inputs and Outputs” on page 2-928.

## **Theory**

### **LSF and LSP Computation Method: Chebyshev Polynomial Method for Root Finding**

---

**Note** To learn the principles on which the block’s LSP and LSF computation method is based, see the reference listed in “References” on page 2-938.

---

To compute LSP outputs for each channel, the block relies on the fact that LSP values are the roots of two particular polynomials related to the input LPC polynomial; the block finds these roots using the Chebyshev polynomial root finding method, described next. To compute LSF outputs, the block computes the arc cosine of the LSPs, outputting values ranging from 0 to  $\pi$  radians.

## Root Finding Method

LSPs, which are the roots of two particular polynomials, always lie in the range (-1, 1). (The guaranteed roots at 1 and -1 are factored out.) The block finds the LSPs by looking for a sign change of the two polynomials' values between points in the range (-1, 1). The block searches a maximum of  $k(n - 1)$  points, where

- $n$  is the value of the **Root finding coarse grid points** parameter.
- $k$  is the value of the **Root finding bisection refinement** parameter.

The block's method for choosing which points to check consists of the following two steps:


- 1 Coarse Root Finding** — The block divides the interval [-1, 1] into  $n$  intervals, each of length  $2/n$ , and checks the signs of both polynomials' values at the endpoints of the intervals. The block starts checking signs at 1, and continues checking signs at  $1 - 4/n$ ,  $1 - 6/n$ , and so on at steps of length  $2/n$ , outputting any point if it is a root. The block stops searching in these situations:
  - a** The block finds a sign change of a polynomial's values between two adjacent points. An interval containing a sign change is guaranteed to contain a root, so the block further searches the interval as described in Step 2, Root Finding Refinement.
  - b** The block finds and outputs all  $M$  roots (given a length- $M+1$  LPC input).
  - c** The block fails to find all  $M$  roots and yields invalid outputs as described in "Handling and Recognizing Invalid Inputs and Outputs" on page 2-927.

- 2 Root Finding Refinement** — When the block finds a sign change in an interval,  $[a, b]$ , it searches for the root guaranteed to lie in the interval by following these steps:
- a Check if Midpoint Is a Root** — The block checks the sign of the midpoint of the interval  $[a, b]$ . The block outputs the midpoint if it is a root, and continues Step 1, Coarse Root Finding, at the next point,  $a - 2/n$ . Otherwise, the block selects the half-interval with endpoints of opposite sign (either  $[a, (a + b)/2]$  or  $[(a + b)/2, b]$ ) and executes Step 2b, Stop or Continue Root Finding Refinement.
  - b Stop or Continue Root Finding Refinement** — When the block has repeated Step 2a  $k$  times ( $k$  is the value of the **Root finding bisection refinement** parameter), the block linearly interpolates the root by using the half-interval's endpoints, outputs the result as an LSP value, and returns to Step 1, Coarse Root Finding. Otherwise, the block repeats Step 2a using the half-interval.

**Coarse Root Finding:** LSPs are roots of two particular polynomials related to the input LPCs. Check signs of the two polynomials at evenly-spaced points to find all intervals containing a sign change. Output any roots (LSPs) found.

**Root finding coarse grid points = 5**

Divide  $[-1, 1]$  into five intervals of equal length and check signs of the polynomials' values at the endpoints of the intervals: 1, 0.6, 0.2, -0.2, -0.6, -1.




**Root Finding Refinement:** Whenever Coarse Root Finding identifies an interval containing a sign change, repeatedly bisect the interval to better approximate the root (LSP value).

**Bisection 1:** Check the sign of the polynomial at the midpoint of the interval and select the half-interval with endpoints of opposite sign:  $[0.2, 0.4]$

**Bisection 2:** Similar to Bisection 1

**Root finding bisection refinement = 3**  
Bisect all sign change intervals found in the Coarse Root Finding up to three times to find the root. When the root is not found in the last bisection, linearly interpolate the root.

**Bisection 3:** The last bisection. Since the midpoint of this interval is not the root, linearly interpolate the root and output the result as an LSP value.



## Coarse Root Finding and Root Finding Refinement


### **Root Finding Method Limitations: Failure to Find Roots**

The block root finding method described above can fail, causing the block to produce invalid outputs (for details on invalid outputs, see “Handling and Recognizing Invalid Inputs and Outputs” on page 2-927).


In particular, the block can fail to find some roots if the value of the **Root finding coarse grid points** parameter,  $n$ , is too small. If the polynomials oscillate quickly and have roots that are very close together, the root finding might be too coarse to identify roots that are very close to each other, as illustrated in Fixing a Failed Root Finding on page 2-937.

For higher-order input LPC polynomials, you should increase the **Root finding coarse grid points** value to ensure the block finds all the roots and produces valid outputs.

**Root Finding Fails:** The root search divides the interval  $[-1, 1]$  into four intervals, but all three roots are in a single interval. The block can only find one root per interval, so two of the roots are never found.



**Fix Root Finding so it Succeeds:** Increasing the value of the **Root finding coarse grid points** parameter to 15 ensures that each root is in its own interval, so all roots are found.



## Fixing a Failed Root Finding

# LPC to LSF/LSP Conversion

---

## Supported Data Types

- Double-precision floating point
- Single-precision floating point
- Boolean — Supported only by the optional output port that appears when you set the parameter, **Show output validity status (1=valid, 0=invalid)**

## References

Kabal, P. and Ramachandran, R. “The Computation of Line Spectral Frequencies Using Chebyshev Polynomials.” *IEEE Transactions on Acoustics, Speech, and Signal Processing*, Vol. ASSP-34 No. 6, December 1986. pp. 1419-1426.

## See Also

LSF/LSP to LPC Conversion	DSP System Toolbox
LPC to/from RC	DSP System Toolbox
LPC/RC to Autocorrelation	DSP System Toolbox
poly2lsf	Signal Processing Toolbox

## Purpose


Convert line spectral frequencies or line spectral pairs to linear prediction coefficients

## Library

Estimation / Linear Prediction

dsp1p

## Description




The LSF/LSP to LPC Conversion block takes a vector or matrix of line spectral pairs (LSPs) or line spectral frequencies (LSFs) and converts it to a vector or matrix of linear prediction polynomial coefficients (LPCs). When converting LSFs to LPCs, the block outputs match those of the `lsf2poly` function.

The block input must be a sample-based row vector, which is treated as a single channel, or a matrix, which is treated as a single channel per column. Each input channel must be in the same format, which you specify in the **Input** parameter:

- LSF in range  $(0 \pi)$  — Vector of LSF values between 0 and  $\pi$  radians in increasing order. Do not include the guaranteed LSF values, 0 and  $\pi$ .
- LSF normalized in range  $(0 0.5)$  — Vector of normalized LSF values in increasing order, (compute by dividing the LSF values between 0 and  $\pi$  radians by  $2\pi$ ). Do not include the guaranteed normalized LSF values, 0 and 0.5.
- LSP in range  $(-1 1)$  — Vector of LSP values in decreasing order, equal to the cosine of the LSF values between 0 and  $\pi$  radians. Do not include the guaranteed LSP values, -1 and 1.

# LSF/LSP to LPC Conversion



## Dialog Box

### Input

Specifies whether to convert LSP in range  $(-1 \ 1)$ , LSF in range  $(0 \ \pi)$ , or LSF normalized in range  $(0 \ 0.5)$  to linear prediction coefficients (LPCs).

## Supported Data Types

- Double-precision floating point
- Single-precision floating point

## References

Kabal, P. and Ramachandran, R. "The Computation of Line Spectral Frequencies Using Chebyshev Polynomials." *IEEE Transactions on Acoustics, Speech, and Signal Processing*, Vol. ASSP-34 No. 6, December 1986. pp. 1419-1426.

## See Also

LPC to LSF/LSP Conversion	DSP System Toolbox
LPC to/from RC	DSP System Toolbox
LPC/RC to Autocorrelation	DSP System Toolbox
lsf2poly	Signal Processing Toolbox

# LPC to/from Cepstral Coefficients

## Purpose


Convert linear prediction coefficients to cepstral coefficients or cepstral coefficients to linear prediction coefficients

## Library

Estimation / Linear Prediction

dsp1p

## Description



The LPC to/from Cepstral Coefficients block either converts linear prediction coefficients (LPCs) to cepstral coefficients (CCs) or cepstral coefficients to linear prediction coefficients. Set the **Type of conversion** parameter to LPCs to cepstral coefficients or Cepstral coefficients to LPCs to select the domain into which you want to convert your coefficients. The LPC port corresponds to LPCs, and the CC port corresponds to the CCs. For more information, see “Algorithm” on page 2-942.

The block input must be a sample-based row vector, which is treated as a single channel, or a matrix, which is treated as a single channel per column.

Consider a signal  $x(n)$  as the input to an FIR analysis filter represented by LPCs. The output of this analysis filter,  $e(n)$ , is known as the prediction error signal. The power of this error signal is denoted by  $P$ , the prediction error power.

When you select LPCs to cepstral coefficients from the **Type of conversion** list, you can specify the prediction error power in two ways. From the **Specify P** list, choose via `input port` to input the prediction error power using input port P. The input to the port must be a vector with length equal to the number of input channels. Select `assume P equals 1` to set the prediction error power equal to 1 for all channels.

When you select LPCs to cepstral coefficients from the **Type of conversion** list, the **Output size same as input size** check box appears. When you select this check box, the length of the input vector of LPCs is equal to the output vector of CCs. When you do not select this check box, enter a positive scalar for the **Length of output cepstral coefficients** parameter.

# LPC to/from Cepstral Coefficients

---

When you select LPCs to cepstral coefficients from the **Type of conversion** list, you can use the **If first input value is not 1** parameter to specify the behavior of the block when the first coefficient of the LPC vector is not 1. The following options are available:

- **Replace it with 1** — Changes the first value of the coefficient vector to 1. The other coefficient values are unchanged.
- **Normalize** — Divides the entire vector of coefficients by the first coefficient so that the first coefficient of the LPC vector is 1.
- **Normalize and Warn** — Divides the entire vector of coefficients by the first coefficient so that the first coefficient of the LPC vector is 1. The block displays a warning message telling you that your vector of coefficients has been normalized.
- **Error** — Displays an error telling you that the first coefficient of the LPC vector is not 1.

When you select Cepstral coefficients to LPCs from the **Type of conversion** list, the **Output P** check box appears on the block. Select this check box when you want to output the prediction error power from output port P.

## Algorithm

The cepstral coefficients are the coefficients of the Fourier transform representation of the logarithm magnitude spectrum. Consider a sequence,  $x(n)$ , having a Fourier transform  $X(\omega)$ . The cepstrum,  $c_x(n)$ , is defined by the inverse Fourier transform of  $C_x(\omega)$ , where  $C_x(\omega) = \log_e X(\omega)$ . See the Real Cepstrum block reference page for information on computing cepstrum coefficients from time-domain signals.

### LPC to CC

When in this mode, this block uses a recursion technique to convert

LPCs to CCs. The LPC vector is defined by  $[a_0 \ a_1 \ a_2 \ \dots \ a_p]$

and the CC vector is defined by  $[c_0 \ c_1 \ c_2 \ \dots \ c_p \ \dots \ c_{n-1}]$ . The recursion is defined by the following equations:

$$c_0 = \log_e P$$

$$c_m = -a_m + \frac{1}{m} \sum_{k=1}^{m-1} [-(m-k) \cdot a_k \cdot c_{(m-k)}], 1 \leq m \leq p$$

$$c_m = \sum_{k=1}^p \left[ \frac{-(m-k)}{m} \cdot a_k \cdot c_{(m-k)} \right], p < m < n$$

## CC to LPC


When in this mode, this block uses a recursion technique to convert CCs to LPCs. The CC vector is defined by  $[c_0 \ c_1 \ c_2 \ \dots \ c_p \ \dots \ c_n]$  and the LPC vector is defined by  $[a_0 \ a_1 \ a_2 \ \dots \ a_p]$ . The recursion is defined by the following equations

$$a_m = -c_m - \frac{1}{m} \sum_{k=1}^{m-1} [(m-k) \cdot c_{(m-k)} \cdot a_k]$$

$$P = \exp(C_0)$$

where  $m = 1, 2, \dots, p$ .

# LPC to/from Cepstral Coefficients



## Dialog Box

### Type of conversion

Choose `LPCs to cepstral coefficients` or `Cepstral coefficients to LPCs` to specify the domain into which you want to convert your coefficients.

### Specify P

Choose `via input port` to input the values of prediction error power using input port P. Select `assume P equals 1` to set the prediction error power equal to 1.

### Output size same as input size

When you select this check box, the length of the input vector of LPCs is equal to the output vector of CCs.

# LPC to/from Cepstral Coefficients

---

## Length of output cepstral coefficients

Enter a positive scalar that is the length of each output channel of CCs.

## If first input value is not 1

Select what you would like the block to do when the first coefficient of the LPC vector is not 1. You can choose `Replace it with 1`, `Normalize`, `Normalize and Warn`, and `Error`.

## Output P

Select this check box to output the prediction error power for each channel from output port P.

## References

Papamichalis, Panos E. *Practical Approaches to Speech Coding*. Englewood Cliffs, NJ: Prentice Hall, 1987.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point

## See Also

Levinson-Durbin	DSP System Toolbox
LPC to LSF/LSP Conversion	DSP System Toolbox
LSF/LSP to LPC Conversion	DSP System Toolbox
LPC to/from RC	DSP System Toolbox
LPC/RC to Autocorrelation	DSP System Toolbox
Real Cepstrum	DSP System Toolbox
Complex Cepstrum	DSP System Toolbox

# LPC to/from RC

---

## Purpose


Convert linear prediction coefficients to reflection coefficients or reflection coefficients to linear prediction coefficients

## Library

Estimation / Linear Prediction

dsp1p

## Description



The LPC to/from RC block either converts linear prediction coefficients (LPCs) to reflection coefficients (RCs) or reflection coefficients to linear prediction coefficients. Set the **Type of conversion** parameter to LPC to RC or RC to LPC to select the domain into which you want to convert your coefficients. The A port corresponds to LPC coefficients, and the K port corresponds to the RC coefficients. For more information, see “Algorithm” on page 2-947.

The block input must be a sample-based row vector, which is treated as a single channel, or a matrix, which is treated as a single channel per column.

Consider a signal  $x(n)$  as the input to an FIR analysis filter represented by LPC coefficients. The output of this analysis filter,  $e(n)$ , is known as the prediction error signal. The power of this error signal is denoted by  $P$ . When the zero lag autocorrelation coefficient of  $x(n)$  is one, the autocorrelation sequence and prediction error power are said to be normalized.

Select the **Output normalized prediction error power** check box to enable port P. The normalized prediction error power output at P is a vector with one element per input channel. Each element varies between zero and one.

Select the **Output LPC filter stability** check box to output the stability of the filter represented by the LPCs or RCs. The synthesis filter represented by the LPCs is stable when the absolute value of each of the roots of the LPC polynomial is less than one. The lattice filter represented by the RCs is stable when the absolute value of each reflection coefficient is less than 1. When the filter is stable, the block outputs a Boolean value of 1 for each input channel at the S port. When

the filter is unstable, the block outputs a Boolean value of 0 for each input channel at the S port.

**If first input value is not 1** parameter specifies the behavior of the block when the first coefficient of the LPC coefficient vector in any channel is not 1. The following options are available:

- **Replace it with 1** — Changes the first value of the coefficient channel to 1. The other coefficient values are unchanged.
- **Normalize** — Divides the entire channel of coefficients by the first coefficient so that the first coefficient of the LPC coefficient vector is 1.
- **Normalize and Warn** — Divides the entire channel of coefficients by the first coefficient so that the first coefficient of the LPC coefficient vector is 1. The block displays a warning message telling you that your vector of coefficients has been normalized.
- **Error** — Displays an error telling you that the first coefficient of the LPC coefficient channel is not 1.

## Algorithm

### LPC to RC

When in this mode, this block uses backward Levinson recursion to convert linear prediction coefficients (LPCs) to reflection coefficients (RCs). For a given Nth order LPC vector

$LPC_N = [1 \quad a_{N1} \quad a_{N2} \quad \dots \quad a_{NN}]$ , the block calculates the Nth reflection coefficient value using the formula  $\gamma_N = -a_{NN}$ . The block then finds the lower order LPC vectors,  $LPC_{N-1}$ ,  $LPC_{N-2}$ , ...,  $LPC_1$ , using the following recursion.

for  $p = N, N - 1, \dots, 2$ ,

$$\gamma_p = a_{pp}$$

$$F = 1 - \gamma_p^2$$

$$a_{p-1,m} = \frac{a_{p,m}}{F} - \frac{\gamma_p a_{p,p-m}}{F}, \quad 1 \leq m < p$$

end

Finally,  $\gamma_1 = -a_{11}$ . The reflection coefficient vector is  $[\gamma_1, \gamma_2, \dots, \gamma_N]$ .

## RC to LPC

When in this mode, this block uses Levinson recursion to convert reflection coefficients (RCs) to linear prediction coefficients (LPCs).

In this case, the input to the block is  $RC = [\gamma_1 \ \gamma_2 \ \dots \ \gamma_N]$ . The zeroth order LPC vector term is 1. Starting with this term, the block uses recursion to calculate the higher order LPC vectors,


$LPC_2, LPC_3, \dots, LPC_N$ , until it has calculated the entire LPC matrix.

$$LPC_{matrix} = \begin{bmatrix} LPC_0 \\ LPC_1 \\ LPC_2 \\ \dots \\ LPC_N \end{bmatrix} = \begin{bmatrix} 1 & 0 & 0 & 0 & \dots & 0 \\ 1 & a_{11} & 0 & 0 & \dots & 0 \\ 1 & a_{21} & a_{22} & 0 & \dots & 0 \\ 1 & a_{31} & a_{32} & a_{33} & \dots & 0 \\ \dots & \dots & \dots & \dots & \dots & \dots \\ 1 & a_{N1} & a_{N2} & a_{N3} & \dots & a_{NN} \end{bmatrix}$$

This LPC matrix consists of LPC vectors of order 0 through  $N$  found by using the Levinson recursion. The following are the formulas for the recursion steps, for  $p = 0, 1, \dots, N - 1$ .

$$a_{p+1,m} = a_{p,m} + \gamma_{p+1}a_{p,p+1-m}, \quad 1 \leq m \leq p$$

$$a_{p+1,p+1} = \gamma_{p+1}$$

**Dialog  
Box****Type of conversion**

Select LPC to RC or RC to LPC to select the domain into which you want to convert your coefficients.

**Output normalized prediction error power**

Select this check box to output the normalized prediction error power at port P.

**Output LPC filter stability**

Select this check box to output the stability of the filter. When the filter represented by the LPCs or RCs is stable, the block outputs a Boolean value of 1 for each input channel at the S port. When the filter represented by the LPCs or RCs is unstable, the block outputs a Boolean value of 0 for each input channel at the S port.

# LPC to/from RC

---

## If first input value is not 1

Select what you would like the block to do when the first coefficient of the LPC coefficient vector is not 1. You can choose `Replace it with 1`, `Normalize`, `Normalize and Warn`, and `Error`.

## References

Makhoul, J *Linear Prediction: A tutorial review*. Proc. IEEE. 63, 63, 56 (1975).

Markel, J.D. and A. H. Gray, Jr., *Linear Prediction of Speech*. New York, Springer-Verlag, 1976.

## Supported Data Types

- Double-precision floating-point
- Single-precision floating-point

## See Also

Levinson-Durbin	DSP System Toolbox
LPC to LSF/LSP Conversion	DSP System Toolbox
LSF/LSP to LPC Conversion	DSP System Toolbox
LPC/RC to Autocorrelation	DSP System Toolbox

## Purpose


Convert linear prediction coefficients or reflection coefficients to autocorrelation coefficients

## Library

Estimation / Linear Prediction

dsp1p

## Description



The LPC/RC to Autocorrelation block either converts linear prediction coefficients (LPCs) to autocorrelation coefficients (ACs) or reflection coefficients (RCs) to autocorrelation coefficients (ACs). Set the **Type of conversion** parameter to LPC to autocorrelation or RC to autocorrelation to select the domain from which you want to convert your coefficients. The A port corresponds to LPC coefficients, and the K port corresponds to the RC coefficients.

The block input must be a sample-based row vector, which is treated as a single channel, or a matrix, which is treated as a single channel per column.


Use the **Specify P** parameter to set the value of the prediction error power. You can set this parameter to 1 by selecting Assume P=1. When you select **Via input port**, a P port appears on the block. You can use this port to input the value of the actual, non-unity prediction error power for each channel. The length of this vector must equal the number of channels in the input.

The **If first input value is not 1** parameter specifies the behavior of the block when the first coefficient of the LPC coefficient vector is not 1. The following options are available:

- **Replace it with 1** — The block changes the first value of the coefficient vector to 1. The rest of the coefficient values are unchanged.
- **Normalize** — The block divides the entire vector of coefficients by the first coefficient so that the first coefficient of the LPC coefficient vector is 1.

# LPC/RC to Autocorrelation

- **Normalize and Warn** — The block divides the entire vector of coefficients by the first coefficient so that the first coefficient of the LPC coefficient vector is 1. The block displays a warning message telling you that your vector of coefficients has been normalized.
- **Error** — The block displays an error telling you that the first coefficient of the LPC coefficient vector is not 1.



## Dialog Box

### Type of conversion

From the list select LPC to autocorrelation or RC to autocorrelation to specify the domain from which you want to convert your coefficients.

### Specify P

From the list select Assume P=1 or Via input port to specify the value of prediction error power.

## If first input value is not 1

Select what you would like the block to do when the first coefficient of the LPC coefficient vector is not 1. You can choose `Replace it with 1`, `Normalize`, `Normalize and Warn`, and `Error`.

## References

Orfanidis, S.J. *Optimum Signal Processing*. New York, McGraw-Hill, 1988.

Makhoul, J. *Linear Prediction: A tutorial review*. Proc. IEEE. 63, 63, 56 (1975).

Markel, J.D. and A. H. Gray, Jr., *Linear Prediction of Speech*. New York, Springer-Verlag, 1976.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point

## See Also

Levinson-Durbin	DSP System Toolbox
LPC to LSF/LSP Conversion	DSP System Toolbox
LSF/LSP to LPC Conversion	DSP System Toolbox
LPC to/from RC	DSP System Toolbox

# LU Factorization


## Purpose

Factor square matrix into lower and upper triangular components

## Library

Math Functions / Matrices and Linear Algebra / Matrix Factorizations  
dspfactors

## Description



The LU Factorization block factors a row-permuted version of the square input matrix  $A$  as  $A_p = L*U$ , where  $L$  is a unit-lower triangular matrix,  $U$  is an upper triangular matrix, and  $A_p$  contains the rows of  $A$  permuted as indicated by the permutation index vector  $P$ . The block uses the pivot matrix  $A_p$  instead of the exact input matrix  $A$  because it improves the numerical accuracy of the factorization. You can determine the singularity of the input matrix  $A$  by enabling the optional output port  $S$ . When  $A$  is singular, the block outputs a 1 at port  $S$ ; when  $A$  is nonsingular, it outputs a 0.

To improve efficiency, the output of the LU Factorization block at port LU is a composite matrix containing both the lower triangle elements of  $L$  and the upper triangle elements of  $U$ . Thus, the output is in a different format than the output of the MATLAB `lu` function, which returns  $L$  and  $U$  as separate matrices. To convert the output from the block's LU port to separate  $L$  and  $U$  matrices, use the following code:


```
L = tril(LU, -1)+eye(size(LU));  
U = triu(LU);
```

If you compare the results produced by these equations to the actual output of the MATLAB `lu` function, you may see slightly different values. These differences are due to rounding error, and are expected.

See the `lu` function reference page in the MATLAB documentation for more information about LU factorizations.

## Fixed-Point Data Types

The following diagram shows the data types used within the LU Factorization block for fixed-point signals.



You can set the product output, accumulator, and output data types in the block dialog as discussed below.

The output of the multiplier is in the product output data type when the input is real. When the input is complex, the result of the multiplication is in the accumulator data type. For details on the complex multiplication performed, see “Multiplication Data Types”.


## Examples

The row-pivoted matrix  $A_p$  and permutation index vector  $P$  computed by the block are shown below for 3-by-3 input matrix  $A$ .

$$A = \begin{bmatrix} -1 & 8 & -5 \\ 9 & -1 & 2 \\ 2 & -5 & 7 \end{bmatrix} \quad P = (2 \ 1 \ 3) \quad A_p = \begin{bmatrix} 9 & -1 & 2 \\ -1 & 8 & -5 \\ 2 & -5 & 7 \end{bmatrix}$$

The LU output is a composite matrix whose lower subtriangle forms  $L$  and whose upper triangle forms  $U$ .


# LU Factorization



See “Factor a Matrix into Upper and Lower Submatrices Using the LU Factorization Block” in the *DSP System Toolbox User’s Guide* for another example using the LU Factorization block.

## Dialog Box

The **Main** pane of the LU Factorization block dialog appears as follows.




### Show singularity status

Select to output the singularity of the input at port S, which outputs Boolean data type values of 1 or 0. An output of 1

# LU Factorization

indicates that the current input is singular, and an output of 0 indicates the current input is nonsingular.

The **Data Types** pane of the LU Factorization block dialog appears as follows.



## Rounding mode

Select the rounding mode for fixed-point operations.

## Overflow mode

Select the overflow mode for fixed-point operations.

## Product output data type

Specify the product output data type. See “Fixed-Point Data Types” on page 2-954 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Accumulator data type

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-954 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

# LU Factorization

---

## Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-954 for illustrations depicting the use of the output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as input`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## References

Golub, G. H., and C. F. Van Loan. *Matrix Computations*. 3rd ed. Baltimore, MD: Johns Hopkins University Press, 1996.

## Supported Data Types

Port	Supported Data Types
A	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
LU	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li></ul>

Port	Supported Data Types
	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit signed integers</li></ul>
P	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• 32-bit unsigned integers</li></ul>
S	<ul style="list-style-type: none"><li>• Boolean</li></ul>

## See Also

Autocorrelation LPC	DSP System Toolbox
Cholesky Factorization	DSP System Toolbox
LDL Factorization	DSP System Toolbox
LU Inverse	DSP System Toolbox
LU Solver	DSP System Toolbox
Permute Matrix	DSP System Toolbox
QR Factorization	DSP System Toolbox
lu	MATLAB

See “Matrix Factorizations” for related information.

# LU Inverse


## Purpose

Compute inverse of square matrix using LU factorization

## Library

Math Functions / Matrices and Linear Algebra / Matrix Inverses  
dspinverses

## Description




The LU Inverse block computes the inverse of the square input matrix  $A$  by factoring and inverting row-pivoted variant  $A_p$ .

$$A_p^{-1} = (LU)^{-1}$$

$L$  is a lower triangular square matrix with unity diagonal elements, and  $U$  is an upper triangular square matrix. The block outputs the inverse matrix  $A^{-1}$ .

## Examples

See “Find the Inverse of a Matrix Using the LU Inverse Block” in the *DSP System Toolbox User’s Guide*.



## Dialog Box

## References

Golub, G. H., and C. F. Van Loan. *Matrix Computations*. 3rd ed. Baltimore, MD: Johns Hopkins University Press, 1996.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point

## See Also

Cholesky Inverse	DSP System Toolbox
LDL Inverse	DSP System Toolbox
LU Factorization	DSP System Toolbox
LU Solver	DSP System Toolbox
inv	MATLAB

See “Matrix Inverses” for related information.

# LU Solver


## Purpose

Solve  $AX=B$  for  $X$  when  $A$  is square matrix

## Library

Math Functions / Matrices and Linear Algebra / Linear System Solvers  
dspsolvers

## Description



The LU Solver block solves the linear system  $AX=B$  by applying LU factorization to the  $M$ -by- $M$  matrix at the A port. The input to the B port is the right side  $M$ -by- $N$  matrix,  $B$ . The  $M$ -by- $N$  matrix output  $X$  is the unique solution of the equations.

The block treats length- $M$  unoriented vector input to the input port  $B$  as an  $M$ -by-1 matrix.

## Algorithm

The LU algorithm factors a row-permuted variant ( $A_p$ ) of the square input matrix  $A$  as

$$A_p = LU$$

where  $L$  is a lower triangular square matrix with unity diagonal elements, and  $U$  is an upper triangular square matrix.

The matrix factors are substituted for  $A_p$  in

$$A_p X = B_p$$

where  $B_p$  is the row-permuted variant of  $B$ , and the resulting equation

$$LUX = B_p$$


is solved for  $X$  by making the substitution  $Y = UX$ , and solving two triangular systems.

$$\begin{aligned} LY &= B_p \\ UX &= Y \end{aligned}$$

## Examples

See “Solve  $AX=B$  Using the LU Solver Block” in the *DSP System Toolbox User’s Guide*.

## Dialog Box



## Supported Data Types

- Double-precision floating point
- Single-precision floating point

## See Also

Autocorrelation LPC	DSP System Toolbox
Cholesky Solver	DSP System Toolbox
LDL Solver	DSP System Toolbox
Levinson-Durbin	DSP System Toolbox
LU Factorization	DSP System Toolbox
LU Inverse	DSP System Toolbox
QR Solver	DSP System Toolbox

See “Linear System Solvers” for related information.

# Magnitude FFT


## Purpose

Compute nonparametric estimate of spectrum using periodogram method

## Library

- Estimation / Power Spectrum Estimation  
dspspect3
- Transforms  
dspxfm3

## Description



The Magnitude FFT block computes a nonparametric estimate of the spectrum using the periodogram method.

When the **Output** parameter is set to **Magnitude squared**, the block output for an  $M$ -by- $N$  input  $u$  is equivalent to

$$y = \text{abs}(\text{fft}(u, \text{nfft})) .^2 \quad \% M \quad \text{nfft}$$

When the **Output** parameter is set to **Magnitude**, the block output for an input  $u$  is equivalent to

$$y = \text{abs}(\text{fft}(u, \text{nfft})) \quad \% M \quad \text{nfft}$$

When  $M > N_{fft}$ , the block wraps the input to  $N_{fft}$  before computing the FFT using one of the above equations:

$$y(:, k) = \text{datawrap}(u(:, k), \text{nfft}) \quad \% 1 \quad k \quad N$$


The block treats an  $M$ -by- $N$  matrix input as  $M$  sequential time samples from  $N$  independent channels. The block computes a separate estimate for each of the  $N$  independent channels and generates an  $N_{fft}$ -by- $N$  matrix output. Each column of the output matrix contains the estimate of the corresponding input column's power spectral density at  $N_{fft}$  equally spaced frequency points in the range  $[0, F_s)$ , where  $F_s$  represents the signal's sample frequency. The block always outputs sample-based data.

The Magnitude FFT block supports real and complex floating-point inputs. The block also supports real fixed-point inputs in both

Magnitude and Magnitude squared modes, and complex fixed-point inputs in the Magnitude squared mode.

## Fixed-Point Data Types

The following diagram shows the data types used within the Magnitude FFT subsystem block for fixed-point signals.



The settings for the fixed-point parameters of the FFT block in the diagram above are as follows:

- Sine table — Same word length as input
- Integer rounding mode — Floor
- Saturate on integer overflow — unchecked
- Product output — Inherit via internal rule
- Accumulator — Inherit via internal rule
- Output — Inherit via internal rule


The settings for the fixed-point parameters of the Magnitude Squared block in the diagram above are as follows:

- Integer rounding mode — Floor
- Saturate on integer overflow — checked
- Output — Inherit via internal rule

## Examples

The `dspsacomp` example compares the periodogram method with several other spectral estimation methods.

# Magnitude FFT



## Dialog Box

### Output

Specify whether the block computes the magnitude FFT or magnitude-squared FFT of the input.

### FFT implementation

Set this parameter to FFTW [1], [2] to support an arbitrary length input signal. The block restricts generated code with FFTW implementation to MATLAB host computers.

Set this parameter to Radix-2 for bit-reversed processing, fixed or floating-point data, or for portable C-code generation using the Simulink Coder. The first dimension  $M$ , of the input matrix must be a power of two. To work with other input sizes, use the Pad block to pad or truncate these dimensions to powers of two, or if possible choose the FFTW algorithm.

Set this parameter to Auto to let the block choose the FFT implementation. For non-power-of-two transform lengths, the block restricts generated code to MATLAB host computers.

## **Inherit FFT length from input dimensions**

Select to use the input frame size as the number of data points, on which to perform the FFT. When you select this check box, this number must be a power of two. When you do not select this check box, the **FFT length** parameter specifies the number of data points.

## **FFT length**

Enter the number of data points on which to perform the FFT,  $N_{fft}$ . When  $N_{fft}$  is larger than the input frame size, each frame is zero-padded as needed. When  $N_{fft}$  is smaller than the input frame size, each frame is wrapped as needed. This parameter is enabled when you clear the **Inherit FFT length from input dimensions** check box.

When you set the **FFT implementation** parameter to Radix-2, this value must be a power of two.

## **References**

Oppenheim, A. V. and R. W. Schaffer. *Discrete-Time Signal Processing*. Englewood Cliffs, NJ: Prentice-Hall, 1989.

Orfanidis, S. J. *Introduction to Signal Processing*. Englewood Cliffs, NJ: Prentice-Hall, 1995.

Proakis, J. and D. Manolakis. *Digital Signal Processing*. 3rd ed. Englewood Cliffs, NJ: Prentice-Hall, 1996.

## **References**

[1] FFTW (<http://www.fftw.org>)

# Magnitude FFT

---

[2] Frigo, M. and S. G. Johnson, "FFTW: An Adaptive Software Architecture for the FFT," *Proceedings of the International Conference on Acoustics, Speech, and Signal Processing*, Vol. 3, 1998, pp. 1381-1384.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>

## See Also

Burg Method	DSP System Toolbox
Short-Time FFT	DSP System Toolbox
Spectrum Scope	DSP System Toolbox
Yule-Walker Method	DSP System Toolbox
pwelch	Signal Processing Toolbox

See "Spectral Analysis" for related information.

## Purpose

Compute 1-norm of matrix

## Library

Math Functions / Matrices and Linear Algebra / Matrix Operations  
dspmtx3

## Description




The Matrix 1-Norm block computes the 1-norm, or maximum column-sum, of an  $M$ -by- $N$  input matrix,  $A$ .

$$y = \|A\|_1 = \max_{1 \leq j \leq N} \sum_{i=1}^M |a_{ij}|$$

This is equivalent to

`y = max(sum(abs(A)))`      % Equivalent  
MATLAB code



The block treats length- $M$  unoriented vector input as an  $M$ -by-1 matrix. The output,  $y$ , is always a scalar.

The Matrix 1-Norm block supports real and complex floating-point inputs, and real fixed-point inputs.

## Fixed-Point Data Types

The following diagram shows the data types used within the Matrix 1-Norm block for fixed-point signals.

# Matrix 1-Norm

---




The block calculations are all done in the accumulator data type until the `max` is performed. The result is then cast to the output data type. You can set the accumulator and output data types in the block dialog as discussed in “Dialog Box” on page 2-972 below.

## Dialog Box

There are no parameters on the **Main** pane of this dialog.

The **Data types** pane of the Matrix 1-Norm block dialog appears as follows.



---

**Note** Floating-point inheritance takes precedence over the data type settings defined on this pane. When inputs are floating point, the block ignores these settings, and all internal data types are floating point.

---

### **Rounding mode**

Select the rounding mode for fixed-point operations.

### **Overflow mode**

Select the overflow mode for fixed-point operations.

## Accumulator data type

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-971 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-971 for illustrations depicting the use of the output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as accumulator`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

## Minimum

Specify the minimum value that the block should output. The default value is [ ] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Maximum

Specify the maximum value that the block should output. The default value is [ ] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## References

Golub, G. H., and C. F. Van Loan. *Matrix Computations*. 3rd ed. Baltimore, MD: Johns Hopkins University Press, 1996.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

# Matrix 1-Norm

---

Port	Supported Data Types
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

## See Also

Normalization	DSP System Toolbox
Reciprocal Condition	DSP System Toolbox
norm	MATLAB



<b>Purpose</b>	Concatenate input signals of same data type to create contiguous output signal
<b>Library</b>	Math Functions / Matrices and Linear Algebra / Matrix Operations dspmtx3
<b>Description</b>	The Matrix Concatenate block is an implementation of the Simulink Matrix Concatenate block. See Matrix Concatenate for more information.

# Matrix Exponential

**Purpose** Compute matrix exponential

**Library** Math Functions / Matrices and Linear Algebra / Matrix Operations  
dspmtx3

**Description** The Matrix Exponential block computes the matrix exponential using a scaling and squaring algorithm with a Pade approximation. The input matrix must be square.



## Dialog Box

**Supported Data Types**

- Double-precision floating point
- Single-precision floating point

**See Also**

Array-Vector Multiply	DSP System Toolbox
expm	MATLAB
Dot Product	Simulink

Matrix Product  
Product

DSP System Toolbox  
Simulink

# Matrix Multiply

---

<b>Purpose</b>	Multiply or divide inputs
<b>Library</b>	Math Functions / Matrices and Linear Algebra / Matrix Operations dspmtrx3
<b>Description</b>	The Matrix Multiply block is an implementation of the Simulink Product block. See Product for more information.


## Purpose

Multiply matrix elements along rows, columns, or entire input

## Library

Math Functions / Matrices and Linear Algebra / Matrix Operations  
dspmtx3

## Description



The Matrix Product block multiplies the elements of an  $M$ -by- $N$  input matrix  $u$  along its rows, its columns, or over all its elements.

When the **Multiply over** parameter is set to **Rows**, the block multiplies across the elements of each row and outputs the resulting  $M$ -by-1 matrix. The block treats length- $N$  unoriented vector input as a 1-by- $N$  matrix.

$$\begin{bmatrix} u_{11} & u_{12} & u_{13} \\ u_{21} & u_{22} & u_{23} \\ u_{31} & u_{32} & u_{33} \end{bmatrix} \Rightarrow \begin{bmatrix} y_1 \\ y_2 \\ y_3 \end{bmatrix} = \begin{bmatrix} \left( \prod_{j=1}^3 u_{1,j} \right) \\ \left( \prod_{j=1}^3 u_{2,j} \right) \\ \left( \prod_{j=1}^3 u_{3,j} \right) \end{bmatrix}$$

When the **Multiply over** parameter is set to **Columns**, the block multiplies down the elements of each column and outputs the resulting 1-by- $N$  matrix. The block treats length- $M$  unoriented vector input as an  $M$ -by-1 matrix.

$$\begin{bmatrix} u_{11} & u_{12} & u_{13} \\ u_{21} & u_{22} & u_{23} \\ u_{31} & u_{32} & u_{33} \end{bmatrix} \Downarrow \begin{bmatrix} y_1 & y_2 & y_3 \end{bmatrix} = \left[ \left( \prod_{i=1}^3 u_{i1} \right) \left( \prod_{i=1}^3 u_{i2} \right) \left( \prod_{i=1}^3 u_{i3} \right) \right]$$


# Matrix Product

When the **Multiply over** parameter is set to **Entire** input, the block multiplies all the elements of the input together and outputs the resulting scalar.

$$\begin{bmatrix} u_{11} & u_{12} & u_{13} \\ u_{21} & u_{22} & u_{23} \\ u_{31} & u_{32} & u_{33} \end{bmatrix} \Rightarrow y = \left( \prod_{i=1}^3 \prod_{j=1}^3 u_{ij} \right)$$

## Fixed-Point Data Types


The following diagram shows the data types used within the Matrix Product block for fixed-point signals.



The output of the multiplier is in the product output data type when at least one of the inputs to the multiplier is real. When both of the inputs to the multiplier are complex, the result of the multiplication is in the accumulator data type. For details on the complex multiplication performed, see “Multiplication Data Types”. You can set the accumulator, product output, intermediate product, and output data types in the block dialog as discussed in “Dialog Box” on page 2-982 below.

## Dialog Box

The **Main** pane of the Matrix Product block dialog appears as follows.




## **Multiply over**

Indicate whether to multiply together the elements of each row, each column, or the entire input.

The **Data Types** pane of the Matrix Product block dialog appears as follows.

# Matrix Product



---

**Note** Floating-point inheritance takes precedence over the data type settings defined on this pane. When inputs are floating point, the block ignores these settings, and all internal data types are floating point.

---

## **Rounding mode**

Select the rounding mode for fixed-point operations.

## **Overflow mode**

Select the overflow mode for fixed-point operations.

## Intermediate product

Specify the intermediate product data type. As shown in “Fixed-Point Data Types” on page 2-982, the output of the multiplier is cast to the intermediate product data type before the next element of the input is multiplied into it. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as input`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Product output data type

Specify the product output data type. See “Fixed-Point Data Types” on page 2-982 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Accumulator data type

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-982 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-982 for illustrations depicting the use of the output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as product output`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

## Minimum

Specify the minimum value that the block should output. The default value is [ ] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Maximum

Specify the maximum value that the block should output. The default value is [ ] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>
Output	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>

# Matrix Product

---

## See Also

Array-Vector  
Multiply

DSP System Toolbox

Matrix Square

DSP System Toolbox

Matrix Sum

DSP System Toolbox

prod

MATLAB


## Purpose

Compute square of input matrix

## Library

Math Functions / Matrices and Linear Algebra / Matrix Operations  
dspmtx3

## Description



The Matrix Square block computes the square of an  $M$ -by- $N$  input matrix,  $u$ , by premultiplying with the Hermitian transpose.

```
y = u' * u      % Equivalent MATLAB code
```

The block treats length- $M$  unoriented vector inputs as an  $M$ -by-1 matrix. When the input is an  $M$ -by- $N$  matrix, the output of the block is an  $N$ -by- $N$  matrix.

## Applications


The Matrix Square block is useful in a variety of applications:

- General matrix squares — The Matrix Square block computes the output matrix,  $y$ , without explicitly forming  $u'$ . It is therefore more efficient than other methods for computing the matrix square.
- Sum of squares — When the input is a column vector ( $N=1$ ), the block's operation is equivalent to a multiply-accumulate (MAC) process, or inner product. The output is the sum of the squares of the input, and is always a real scalar.
- Correlation matrix — When the input is a row vector ( $M=1$ ), the output,  $y$ , is the symmetric autocorrelation matrix, or outer product.

# Matrix Square

## Dialog Box

The **Signal Attributes** pane of the Matrix Square block dialog appears as follows.



### Output minimum

Specify the minimum value the block should output. The default value is [ ] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Output maximum

Specify the maximum value the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Output data type

Specify the output data type. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

## Lock output data type setting against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the **Output data type** you specify on the block mask.

## Integer rounding mode

Select the rounding mode for fixed-point operations.

## Overflow mode

Select this check box to have overflows saturate to the maximum or minimum value that the data type can represent. If you clear this check box, the block wraps all overflows. See overflow mode for more information.

# Matrix Square

---

When you select this check box, saturation applies to every internal operation on the block, not just the output or result. In general, the code generation process can detect when overflow is not possible. In this case, the code generator does not produce saturation code

## Supported Data Types

- Double-precision floating point
- Single-precision floating point

## See Also

Matrix Multiply	DSP System Toolbox
Matrix Product	DSP System Toolbox
Matrix Sum	DSP System Toolbox
Transpose	DSP System Toolbox

<b>Purpose</b>	Sum matrix elements along rows, columns, or entire input
<b>Library</b>	Math Functions / Matrices and Linear Algebra / Matrix Operations dspmtrx3
<b>Description</b>	The Matrix Sum block is an implementation of the Simulink Sum block. See Sum for more information.

# Matrix Sum (Obsolete)


## Purpose

Sum matrix elements along rows, columns, or entire input

## Library

Math Functions / Matrices and Linear Algebra / Matrix Operations  
dspobslib

## Description



The Matrix Sum block sums the elements of an  $M$ -by- $N$  input matrix  $u$  along its rows, its columns, or over all its elements.

When the **Sum over** parameter is set to **Rows**, the block sums across the elements of each row and outputs the resulting  $M$ -by-1 matrix. A length- $N$  1-D vector input is treated as a 1-by- $N$  matrix.

$$\begin{bmatrix} u_{11} & u_{12} & u_{13} \\ u_{21} & u_{22} & u_{23} \\ u_{31} & u_{32} & u_{33} \end{bmatrix} \Rightarrow \begin{bmatrix} y_1 \\ y_2 \\ y_3 \end{bmatrix} = \begin{bmatrix} \left( \sum_{j=1}^3 u_{1j} \right) \\ \left( \sum_{j=1}^3 u_{2j} \right) \\ \left( \sum_{j=1}^3 u_{3j} \right) \end{bmatrix}$$

When the **Sum over** parameter is set to **Columns**, the block sums down the elements of each column and outputs the resulting 1-by- $N$  matrix. A length- $M$  1-D vector input is treated as a  $M$ -by-1 matrix.

$$\begin{bmatrix} u_{11} & u_{12} & u_{13} \\ u_{21} & u_{22} & u_{23} \\ u_{31} & u_{32} & u_{33} \end{bmatrix} \downarrow$$
$$\begin{bmatrix} y_1 & y_2 & y_3 \end{bmatrix} = \left[ \left( \sum_{i=1}^3 u_{i1} \right) \left( \sum_{i=1}^3 u_{i2} \right) \left( \sum_{i=1}^3 u_{i3} \right) \right]$$


When the **Sum over** parameter is set to Entire input, the block sums all the elements of the input together and outputs the resulting scalar.

$$\begin{bmatrix} u_{11} & u_{12} & u_{13} \\ u_{21} & u_{22} & u_{23} \\ u_{31} & u_{32} & u_{33} \end{bmatrix} \Rightarrow y = \left( \sum_{i=1}^3 \sum_{j=1}^3 u_{ij} \right)$$

The output of the Matrix Sum block has the same frame status as the input. This block accepts real and complex fixed-point and floating-point inputs except for complex unsigned fixed-point inputs.

## Fixed-Point Data Types

The following diagram shows the data types used within the Matrix Sum block for fixed-point signals.




You can set the accumulator and output data types in the block dialog as discussed in “Dialog Box” on page 2-996 below.

# Matrix Sum (Obsolete)

---

## Dialog Box

The **Main** pane of the Matrix Sum block dialog appears as follows.




### Sum over

Indicate whether to sum the elements of each row, each column, or of the entire input.

The **Fixed-point** pane of the Matrix Sum block dialog appears as follows.

# Matrix Sum (Obsolete)



## Rounding mode


Select the rounding mode for fixed-point operations.

## Overflow mode

Select the overflow mode for fixed-point operations.

# Matrix Sum (Obsolete)

## Accumulator



As depicted above, the elements of the block input are cast to the accumulator data type before they are added together. The output of the adder remains in the accumulator data type as each element of the input is added to it. Use this parameter to specify how you would like to designate this accumulator word and fraction lengths:

- When you select **Inherit via internal rule**, the accumulator word length and fraction length are calculated automatically. For information about how the accumulator word and fraction lengths are calculated when an internal rule is used, see “Inherit via Internal Rule”.
- When you select **Same as input**, these characteristics match those of the input to the block.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the accumulator, in bits.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the accumulator. This block requires power-of-two slope and a bias of zero.

## Output

Choose how you specify the output word length and fraction length:

- When you select **Same as accumulator**, these characteristics match those of the accumulator.
- When you select **Same as input**, these characteristics match those of the input to the block.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the output, in bits.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the output. This block requires power-of-two slope and a bias of zero.

### Lock scaling against changes by the autoscaling tool

Select this parameter to prevent any fixed-point scaling you specify in this block mask from being overridden by the autoscaling feature of the Fixed-Point Tool. See the `fxptd1g` reference page for more information.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

# Matrix Sum (Obsolete)

---

## See Also

Matrix Product

DSP System Toolbox

Matrix Multiply

DSP System Toolbox

sum

MATLAB

**Purpose** Display matrices as color images

**Library** Sinks  
dpsnks4

## Description



The Matrix Viewer block displays an  $M$ -by- $N$  matrix input by mapping the matrix element values to a specified range of colors. The display is updated as each new input is received. This block treats an unoriented length  $M$  vector input as an  $M$ -by-1 matrix.

You can use the Matrix Viewer block in models running in Normal or Accelerator simulation modes. The software does not support this block in models running in Rapid Accelerator or External mode. For more information about these modes, see “How Acceleration Modes Work” in the *Simulink User’s Guide*.

### Image Properties

Select the **Image Properties** tab to show the image property parameters, which control the colormap and display.

You specify the mapping of matrix element values to colors in the **Colormap matrix**, **Minimum input value**, and **Maximum input value** parameters. For a colormap with  $L$  colors, the colormap matrix has dimension  $L$ -by-3, with one row for each color and one column for each element of the RGB triple that defines the color. Examples of RGB triples are

```
[ 1  0  0 ] (red)
[ 0  0  1 ] (blue)
[0.8 0.8 0.8] (light gray)
```

See the `ColorSpec` property in the MATLAB documentation for complete information about defining RGB triples.

MATLAB provides a number of functions for generating predefined colormaps, such as `hot`, `cool`, `bone`, and `autumn`. Each of these functions accepts the colormap size as an argument, and can be used in the **Colormap matrix** parameter. For example, when you

# Matrix Viewer

---

specify `gray(128)` for the **Colormap matrix** parameter, the matrix is displayed in 128 shades of gray. The color in the first row of the colormap matrix represents the value specified by the **Minimum input value** parameter, and the color in the last row represents the value specified by the **Maximum input value** parameter. Values between the minimum and maximum are quantized and mapped to the intermediate rows of the colormap matrix.

The documentation for the MATLAB `colormap` function provides complete information about specifying colormap matrices, and includes a complete list of the available colormap functions.

## Axis Properties

Select the **Axis Properties** tab to show the axis property parameters, which control labeling and positioning.

The **Axis origin** parameter determines where the first element of the input matrix,  $U(1,1)$ , is displayed. When you specify `Upper left corner`, the matrix is displayed in matrix orientation, with  $U(1,1)$  in the upper-left corner.

$$\begin{bmatrix} U_{11} & U_{12} & U_{13} & U_{14} \\ U_{21} & U_{22} & U_{23} & U_{24} \\ U_{31} & U_{32} & U_{33} & U_{34} \\ U_{41} & U_{42} & U_{43} & U_{44} \end{bmatrix}$$

When you specify `Lower left corner`, the matrix is flipped vertically to image orientation, with  $U(1,1)$  in the lower-left corner.

$$\begin{bmatrix} U_{41} & U_{42} & U_{43} & U_{44} \\ U_{31} & U_{32} & U_{33} & U_{34} \\ U_{21} & U_{22} & U_{23} & U_{24} \\ U_{11} & U_{12} & U_{13} & U_{14} \end{bmatrix}$$

**Axis zoom**, when selected, causes the image display to completely fill the figure window. Axis titles are not displayed. This option can also be

selected from the pop-up menu that is displayed when you right-click in the figure window. When **Axis zoom** is cleared, the axis labels and titles are displayed in a gray border surrounding the image axes.

## Figure Window

The image title in the figure title bar is the same as the block title. The axis tick marks reflect the size of the input matrix; the  $x$ -axis is numbered from 1 to  $N$  (number of columns), and the  $y$ -axis is numbered from 1 to  $M$  (number of rows).

Right-click the image in the figure window to access the following menu items:

- **Refresh** erases all data on the scope display except for the most recent image.
- **Autoscale** recomputes the minimum and maximum input values to fit the range of values observed in a series of 10 consecutive inputs. The numerical limits selected by the autoscale feature are shown in the **Minimum input value** and **Maximum input value** parameters, where you can make further adjustments to them manually.
- **Axis zoom**, when selected, causes the image to completely fill the figure window. Axis titles are not displayed. When **Axis zoom** is cleared, the axis labels and titles are displayed in a gray border surrounding the scope axes. This option can also be set in the Axis Properties pane of the parameter dialog.
- **Colorbar**, when selected, displays a bar with the specified colormap to the right of the image axes.
- **Save Position** automatically updates the **Figure position** parameter in the **Axis Properties** pane to reflect the figure window's current position and size on the screen. To make the scope window open at a particular location on the screen when the simulation runs, drag the window to the desired location, resize it, and select **Save Position**. The parameter dialog must be closed when you select **Save Position** for the **Figure position** parameter to be updated.

# Matrix Viewer


---

## Examples

See the Spectral Analysis Using the Periodogram Method example for a demonstration of using the Matrix Viewer block to create a moving spectrogram, or time-frequency plot, of a speech signal by updating just one column of the input matrix at each sample time.

## Dialog Box

The **Image Properties** pane of the Matrix Viewer block appears as follows.



### Colormap matrix

A 3-column matrix defining the colormap as a set of RGB triples, or a call to a colormap-generating function such as `hot` or `spring`. See the `ColorSpec` property for complete information about

defining RGB triples, and the MATLAB colormap function for a list of colormap-generating functions. Tunable.

### **Minimum input value**

The input value to be mapped to the color defined in the first row of the colormap matrix. Right-click in the figure window and select **Autoscale** from pop-up menu to set this parameter to the minimum value observed in a series of 10 consecutive matrix inputs. Tunable.

### **Maximum input value**


The input value to be mapped to the color defined in the last row of the colormap matrix. Right-click in the figure window and select **Autoscale** from the pop-up menu to set this parameter to the maximum value observed in a series of 10 consecutive matrix inputs. Tunable.

### **Display colorbar**

Select to display a bar with the selected colormap to the right of the image axes. Tunable.

The **Axis Properties** pane of the Matrix Viewer block appears as follows.

# Matrix Viewer



## Axis origin

The position within the axes where the first element of the input matrix,  $U(1,1)$ , is plotted; bottom left or top left. Tunable.

## X-axis title

The text to be displayed below the  $x$ -axis. Tunable.

## Y-axis title

The text to be displayed to the left of the  $y$ -axis. Tunable.

## Colorbar title

The text to be displayed to the right of the color bar, when **Display colorbar** is currently selected. Tunable.

**Figure position, [x y width height]**

A 4-element vector of the form [x y width height] specifying the position of the figure window, where (0,0) is the lower-left corner of the display. Tunable.

**Axis zoom**

Resizes the image to fill the figure window. Tunable.

**Supported Data Types**

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

**See Also**

Spectrum Scope	DSP System Toolbox
Vector Scope	DSP System Toolbox
colormap	MATLAB
ColorSpec	MATLAB
image	MATLAB

# Maximum

## Purpose


Find maximum values in input or sequence of inputs

## Library

Statistics

dspstat3

## Description



The Maximum block identifies the value and/or position of the largest element in each row or column of the input, along vectors of a specified dimension of the input, or of the entire input. The Maximum block can also track the maximum values in a sequence of inputs over a period of time. The **Mode** parameter specifies the block's mode of operation and can be set to Value, Index, Value and Index, or Running.

The Maximum block supports real and complex floating-point, fixed-point, and Boolean inputs. Real fixed-point inputs can be either signed or unsigned, while complex fixed-point inputs must be signed. The data type of the maximum values output by the block match the data type of the input. The index values output by the block are double when the input is double, and uint32 otherwise.

For the Value, Index, and Value and Index modes, the Maximum block produces identical results as the MATLAB `max` function when it is called as  $[y \ I] = \max(u, [], D)$ , where  $u$  and  $y$  are the input and output, respectively,  $D$  is the dimension, and  $I$  is the index.

## Value Mode

When the **Mode** parameter is set to Value, the block computes the maximum value in each row or column of the input, along vectors of a specified dimension of the input, or of the entire input at each sample time, and outputs the array  $y$ . Each element in  $y$  is the maximum value in the corresponding column, row, vector, or entire input. The output  $y$  depends on the setting of the **Find the maximum value over** parameter. For example, consider a 3-dimensional input signal of size  $M$ -by- $N$ -by- $P$ :

- Each row — The output at each sample time consists of an  $M$ -by-1-by- $P$  array, where each element contains the maximum value of each vector over the second dimension of the input. For an


input that is an  $M$ -by- $N$  matrix, the output at each sample time is an  $M$ -by-1 column vector.

- **Each column** — The output at each sample time consists of a 1-by- $N$ -by- $P$  array, where each element contains the maximum value of each vector over the first dimension of the input. For an input that is an  $M$ -by- $N$  matrix, the output at each sample time is a 1-by- $N$  row vector.

In this mode, the block treats length- $M$  unoriented vector inputs as  $M$ -by-1 column vectors.

- **Entire input** — The output at each sample time is a scalar that contains the maximum value in the  $M$ -by- $N$ -by- $P$  input matrix.
- **Specified dimension** — The output at each sample time depends on **Dimension**. If **Dimension** is set to 1, the output is the same as that when you select **Each column**. If **Dimension** is set to 2, the output is the same as when you select **Each row**. If **Dimension** is set to 3, the output at each sample time is an  $M$ -by- $N$  matrix containing the maximum value of each vector over the third dimension of the input.

For complex inputs, the block selects the value in each row or column of the input, along vectors of a specified dimension of the input, or of the entire input that has the maximum magnitude squared as shown below. For complex value  $u = a + bi$ , the magnitude squared is  $a^2 + b^2$ .



## Index Mode

When **Mode** is set to **Index**, the block computes the maximum value in each row or column of the input, along vectors of a specified dimension of the input, or of the entire input, and outputs the index array  $I$ .

# Maximum

---

Each element in  $I$  is an integer indexing the maximum value in the corresponding column, row, vector, or entire input. The output  $I$  depends on the setting of the **Find the maximum value over** parameter. For example, consider a 3-dimensional input signal of size  $M$ -by- $N$ -by- $P$ :

- **Each row** — The output at each sample time consists of an  $M$ -by-1-by- $P$  array, where each element contains the index of the maximum value of each vector over the second dimension of the input. For an input that is an  $M$ -by- $N$  matrix, the output at each sample time is an  $M$ -by-1 column vector.
- **Each column** — The output at each sample time consists of a 1-by- $N$ -by- $P$  array, where each element contains the index of the maximum value of each vector over the first dimension of the input. For an input that is an  $M$ -by- $N$  matrix, the output at each sample time is a 1-by- $N$  row vector.

In this mode, the block treats length- $M$  unoriented vector inputs as  $M$ -by-1 column vectors.

- **Entire input** — The output at each sample time is a 1-by-3 vector that contains the location of the maximum value in the  $M$ -by- $N$ -by- $P$  input matrix. For an input that is an  $M$ -by- $N$  matrix, the output will be a 1-by-2 vector.
- **Specified dimension** — The output at each sample time depends on **Dimension**. If **Dimension** is set to 1, the output is the same as when you select **Each column**. If **Dimension** is set to 2, the output is the same as when you select **Each row**. If **Dimension** is set to 3, the output at each sample time is an  $M$ -by- $N$  matrix containing the indices of the maximum values of each vector over the third dimension of the input.

When a maximum value occurs more than once, the computed index corresponds to the first occurrence. For example, when the input is the column vector  $[3 \ 2 \ 1 \ 2 \ 3]'$ , the computed one-based index of the maximum value is 1 rather than 5 when **Each column** is selected.

When inputs to the block are double-precision values, the index values are double-precision values. Otherwise, the index values are 32-bit unsigned integer values.

## Value and Index Mode

When **Mode** is set to **Value** and **Index**, the block outputs both the maxima and the indices.

## Running Mode

When **Mode** is set to **Running**, the block tracks the maximum value of each channel in a time sequence of  $M$ -by- $N$  inputs. In this mode, you must also specify a value for the **Input processing** parameter:

- When you select **Elements as channels (sample based)**, the block outputs an  $M$ -by- $N$  array. Each element  $y_{ij}$  of the output contains the maximum value observed in element  $u_{ij}$  for all inputs since the last reset.
- When you select **Columns as channels (frame based)**, the block outputs an  $M$ -by- $N$  matrix. Each element  $y_{ij}$  of the output contains the maximum value observed in the  $j$ th column of all inputs since the last reset, up to and including element  $u_{ij}$  of the current input.

## Running Mode for Variable-Size Inputs

When your inputs are of variable size, and you set the **Mode** to **Running**, there are two options:

- If you set the **Input processing** parameter to **Elements as channels (sample based)**, the state is reset.
- If you set the **Input processing** parameter to **Columns as channels (frame based)**, then there are two cases:
  - When the input size difference is in the number of channels (i.e., number of columns), the state is reset.
  - When the input size difference is in the length of channels (i.e., number of rows), there is no reset and the running operation is carried out as usual.


## Resetting the Running Maximum

The block resets the running maximum whenever a reset event is detected at the optional Rst port. The reset sample time must be a positive integer multiple of the input sample time.


When a reset event occurs while the **Input processing** parameter is set to **Elements as channels (sample based)**, the running maximum for each channel is initialized to the value in the corresponding channel of the current input. Similarly, when the **Input processing** parameter is set to **Columns as channels (frame based)**, the running maximum for each channel is initialized to the earliest value in each channel of the current input.

You specify the reset event in the **Reset port** menu:

- None — Disables the Rst port.
- Rising edge — Triggers a reset operation when the Rst input does one of the following:
  - Rises from a negative value to a positive value or zero
  - Rises from zero to a positive value, where the rise is not a continuation of a rise from a negative value to zero (see the following figure)



- **Falling edge** — Triggers a reset operation when the Rst input does one of the following:
  - Falls from a positive value to a negative value or zero
  - Falls from zero to a negative value, where the fall is not a continuation of a fall from a positive value to zero (see the following figure)



- **Either edge** — Triggers a reset operation when the Rst input is a Rising edge or Falling edge (as described above)
- **Non-zero sample** — Triggers a reset operation at each sample time that the Rst input is not zero

---

**Note** When running simulations in the Simulink MultiTasking mode, reset signals have a one-sample latency. Therefore, when the block detects a reset event, there is a one-sample delay at the reset port rate before the block applies the reset. For more information on latency and the Simulink tasking modes, see “Excess Algorithmic Delay (Tasking Latency)” and “Scheduling” in the *Simulink Coder User’s Guide*.

---

## ROI Processing

To calculate the statistical value within a particular region of interest (ROI) of the input, select the **Enable ROI processing** check box. This applies to any mode other than running mode and when you set the **Find the maximum value over** parameter to `Entire input` and you select the **Enable ROI processing** check box. ROI processing applies only for 2-D inputs.

---

**Note** Full ROI processing is available only if you have a Computer Vision System Toolbox™ license. If you do not have a Computer Vision System Toolbox license, you can still use ROI processing, but are limited to the **ROI type Rectangles**.

---

Use the **ROI type** parameter to specify whether the ROI is a rectangle, line, label matrix, or binary mask. A binary mask is a binary image that enables you to specify which pixels to highlight, or select. In a label matrix, pixels equal to 0 represent the background, pixels equal to 1 represent the first object, pixels equal to 2 represent the second object, and so on. When the **ROI type** parameter is set to `Label matrix`, the `Label` and `Label Numbers` ports appear on the block. Use the `Label Numbers` port to specify the objects in the label matrix for which the block calculates statistics. The input to this port must be a vector of scalar values that correspond to the labeled regions in the label matrix. For more information about the format of the input to the ROI port when the ROI is a rectangle or a line, see the `Draw Shapes` block reference page.

For rectangular ROIs, use the **ROI portion to process** parameter to specify whether to calculate the statistical value for the entire ROI or just the ROI perimeter.

Use the **Output** parameter to specify the block output. The block can output separate statistical values for each ROI or the statistical value for all specified ROIs. This parameter is not available if, for the **ROI type** parameter, you select `Binary mask`.

If, for the **ROI type** parameter, you select **Rectangles** or **Lines**, the **Output flag indicating if ROI is within image bounds** check box appears in the dialog box. If you select this check box, the Flag port appears on the block. The following tables describe the Flag port output based on the block parameters.

### Output = Individual statistics for each ROI

Flag Port Output	Description
0	ROI is completely outside the input image.
1	ROI is completely or partially inside the input image.

### Output = Single statistic for all ROIs

Flag Port Output	Description
0	All ROIs are completely outside the input image.
1	At least one ROI is completely or partially inside the input image.

If the ROI is partially outside the image, the block only computes the statistical values for the portion of the ROI that is within the image.

If, for the **ROI type** parameter, you select **Label matrix**, the **Output flag indicating if input label numbers are valid** check box appears in the dialog box. If you select this check box, the Flag port appears on the block. The following tables describe the Flag port output based on the block parameters.

# Maximum

---

## Output = Individual statistics for each ROI

Flag Port Output	Description
0	Label number is not in the label matrix.
1	Label number is in the label matrix.

## Output = Single statistic for all ROIs


Flag Port Output	Description
0	None of the label numbers are in the label matrix.
1	At least one of the label numbers is in the label matrix.

## Fixed-Point Data Types


The parameters on the **Data Types** pane of the block dialog are only used for complex fixed-point inputs. The sum of the squares of the real and imaginary parts of such an input are formed before a comparison is made, as described in “Value Mode” on page 2-1008. The results of the squares of the real and imaginary parts are placed into the product output data type. The result of the sum of the squares is placed into the accumulator data type. These parameters are ignored for other types of inputs.

## Examples

In the following `ex_maximum_ref` model, the Maximum block calculates the running maximum of a 3-by-2 matrix input, `dsp_examples_u`. The **Input processing** parameter is set to Columns as channels (frame based), so the block processes the input as a two channel signal with a frame size of three. The running maximum is reset at  $t=2$  by an impulse to the block's Rst port.




The operation of the block is shown in the following figure.



# Maximum

## Dialog Box

The **Main** pane of the Maximum block dialog appears as follows.



## Mode

Specify the block's mode of operation:

- Value — Output the maximum value of each input
- Index — Output the index of the maximum value
- Value and index — Output both the value and the index

- **Running** — Track the maximum value of the input sequence over time

For more information, see Description.

### **Input processing**

Specify how the block should process the input when computing the running maximum. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

This parameter appears only when you set the **Mode** to Running.

---

**Note** The option `Inherit from input` (this choice will be removed - see release notes) will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

### **Index base**

Specify whether the index of the maximum value is reported using one-based or zero-based numbering. This parameter is only visible when the **Mode** parameter is set to `Index` or `Value` and `index`.

### **Find the maximum value over**

Specify whether to find the maximum value along rows, columns, entire input, or the dimension specified in the **Dimension** parameter. For more information, see Description.

## Treat sample-based row input as a column

Select to treat sample-based length- $M$  row vector inputs as  $M$ -by-1 column vectors. This parameter is only visible when the **Find the maximum value of** parameter is set to Each column.

---

**Note** This check box will be removed in a future release. See “Sample-Based Row Vector Processing Changes” in the DSP System Toolbox Release Notes.

---

## Reset port

Specify the reset event that causes the block to reset the running maximum. The sample time of the input to the Rst port must be a positive integer multiple of the input sample time. This parameter appears only when you set the **Mode** parameter to Running. For information about the possible values of this parameter, see “Resetting the Running Maximum” on page 2-1012.

## Dimension

Specify the dimension (one-based value) of the input signal, over which the maximum is computed. The value of this parameter cannot exceed the number of dimensions in the input signal. This parameter is only visible when the **Find the maximum value over** parameter is set to Specified dimension.

## Enable ROI processing


Select this check box to calculate the statistical value within a particular region of each image. This parameter appears only when you set the **Find the maximum value over** parameter to Entire input, and the block is not in running mode.

---

**Note** Full ROI processing is available only if you have a Computer Vision System Toolbox license. If you do not have a Computer Vision System Toolbox license, you can still use ROI processing, but are limited to the **ROI type** Rectangles.

---

The ROI processing parameters appear on the dialog box as follows.



## ROI type

Specify the type of ROI you want to use. Your choices are Rectangles, Lines, Label matrix, or Binary mask.

## ROI portion to process

Specify whether you want to calculate the statistical value for the entire ROI or just the ROI perimeter. This parameter appears only if you specify an **ROI type** of Rectangles.

## Output

Specify the block output. The block can output a vector of separate statistical values for each ROI or a scalar value that represents the statistical value for all the specified ROIs. This parameter is not available if, for the **ROI type** parameter, you select Binary mask.

## Output flag

**Output flag indicating if ROI is within image bounds**


**Output flag indicating if label numbers are valid**

When you select either of these check boxes, the Flag port appears on the block. For a description of the Flag port output, see the tables in “ROI Processing” on page 2-1014.

The **Output flag indicating if ROI is within image bounds** check box is only visible when you select Rectangles or Lines as the **ROI type**.

The **Output flag indicating if label numbers are valid** check box is only visible when you select Label matrix for the **ROI type** parameter.

The **Data Types** pane of the Maximum block dialog appears as follows.



---

**Note** The parameters on the **Data Types** pane are only used for complex fixed-point inputs. The sum of the squares of the real and imaginary parts of such an input are formed before a comparison is made, as described in “Value Mode” on page 2-1008. The results of the squares of the real and imaginary parts are placed into the product output data type. The result of the sum of the squares is placed into the accumulator data type. These parameters are ignored for other types of inputs.

---

## **Rounding mode**

Select the rounding mode for fixed-point operations.

## **Overflow mode**

Select the overflow mode for fixed-point operations.

## **Product output data type**

Specify the product output data type. See “Fixed-Point Data Types” on page 2-1016 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as input`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## **Accumulator data type**

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-1016 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Same as product output`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

**Lock data type settings against changes by the fixed-point tools**

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

**Supported Data Types**

Port	Supported Data Types
Input	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed and unsigned)</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>
Reset	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>
Idx	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• 32-bit unsigned integers</li> </ul>
Val	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed and unsigned)</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>

# Maximum

---

## See Also

Mean

DSP System Toolbox

Minimum

DSP System Toolbox

MinMax

Simulink

max

MATLAB


**Purpose**

Find mean value of input or sequence of inputs

**Library**

Statistics

dspstat3

**Description**

The Mean block computes the mean of each row or column of the input, along vectors of a specified dimension of the input, or of the entire input. The Mean block can also track the mean value in a sequence of inputs over a period of time. To track the mean value in a sequence of inputs, select the **Running mean** check box.

**Basic Operation**

When you do not select the **Running mean** check box, the block computes the mean value in each row or column of the input, along vectors of a specified dimension of the input, or of the entire input at each individual sample time. Each element in the output array  $y$  is the mean value of the corresponding column, row, vector, or entire input. The output array  $y$  depends on the setting of the **Find the mean value over** parameter. For example, consider a 3-dimensional input signal of size  $M$ -by- $N$ -by- $P$ :

- **Entire input** — The output at each sample time is a scalar that contains the mean value of the  $M$ -by- $N$ -by- $P$  input matrix.

```
y = mean(u(:))      % Equivalent MATLAB code
```

- **Each row** — The output at each sample time consists of an  $M$ -by-1-by- $P$  array, where each element contains the mean value of each vector over the second dimension of the input. For an input that is an  $M$ -by- $N$  matrix, the output at each sample time is an  $M$ -by-1 column vector.

```
y = mean(u,2)      % Equivalent MATLAB code
```

- **Each column** — The output at each sample time consists of a 1-by- $N$ -by- $P$  array, where each element contains the mean value of each vector over the first dimension of the input. For an input that

# Mean

is an  $M$ -by- $N$  matrix, the output at each sample time is a 1-by- $N$  row vector.


```
y = mean(u) % Equivalent MATLAB code
```

In this mode, the block treats length- $M$  unoriented vector inputs as  $M$ -by-1 column vectors.

- **Specified dimension** — The output at each sample time depends on the value of the **Dimension** parameter. If you set the **Dimension** to 1, the output is the same as when you select **Each column**. If you set the **Dimension** to 2, the output is the same as when you select **Each row**. If you set the **Dimension** to 3, the output at each sample time is an  $M$ -by- $N$  matrix containing the mean value of each vector over the third dimension of the input.

```
y = mean(u,Dimension) % Equivalent MATLAB code
```

The mean of a complex input is computed independently for the real and imaginary components, as shown in the following figure.



## Running Operation

When you select the **Running mean** check box, the block tracks the mean value of each channel in a time sequence of inputs. In this mode, you must also specify a value for the **Input processing** parameter:

- When you select **Elements as channels (sample based)**, the block outputs an  $M$ -by- $N$  array. Each element  $y_{ij}$  of the output contains the mean value of the elements  $u_{ij}$  for all inputs since the last reset.

- When you select **Columns as channels** (frame based), the block outputs an  $M$ -by- $N$  matrix. Each element  $y_{ij}$  of the output contains the mean of the values in the  $j$ th column of all inputs since the last reset, up to and including element  $u_{ij}$  of the current input.

### Running Operation for Variable-Size Inputs

When your inputs are of variable size, and you select the **Running mean** check box, there are two options:

- If you set the **Input processing** parameter to **Elements as channels** (sample based), the state is reset.
- If you set the **Input processing** parameter to **Columns as channels** (frame based), then there are two cases:
  - When the input size difference is in the number of channels (i.e., number of columns), the state is reset.
  - When the input size difference is in the length of channels (i.e., number of rows), there is no reset and the running operation is carried out as usual.

### Resetting the Running Mean


The block resets the running mean whenever a reset event is detected at the optional Rst port. The reset sample time must be a positive integer multiple of the input sample time.

When a reset event occurs while the **Input processing** parameter is set to **Elements as channels** (sample based), the running mean for each channel is initialized to the value in the corresponding channel of the current input. Similarly, when the **Input processing** parameter is set to **Columns as channels** (frame based), the running mean for each channel is initialized to the earliest value in each channel of the current input.


You specify the reset event by the **Reset port** parameter:

- None disables the Rst port.

- **Rising edge** — Triggers a reset operation when the Rst input does one of the following:
  - Rises from a negative value to a positive value or zero
  - Rises from zero to a positive value, where the rise is not a continuation of a rise from a negative value to zero (see the following figure)



- **Falling edge** — Triggers a reset operation when the Rst input does one of the following:
  - Falls from a positive value to a negative value or zero
  - Falls from zero to a negative value, where the fall is not a continuation of a fall from a positive value to zero (see the following figure)



- **Either edge** — Triggers a reset operation when the Rst input is a Rising edge or Falling edge (as described earlier)
- **Non-zero sample** — Triggers a reset operation at each sample time that the Rst input is not zero

---

**Note** When running simulations in the Simulink MultiTasking mode, reset signals have a one-sample latency. Therefore, when the block detects a reset event, there is a one-sample delay at the reset port rate before the block applies the reset. For more information on latency and the Simulink tasking modes, see “Excess Algorithmic Delay (Tasking Latency)” and “Scheduling” in the *Simulink Coder User’s Guide*.

---

## ROI Processing

To calculate the statistical value within a particular region of interest (ROI) of the input, select the **Enable ROI processing** check box. This option is only available when the **Find the mean value over** parameter is set to **Entire input** and the **Running mean** check box is not selected. ROI processing is only supported for 2-D inputs.

---

**Note** Full ROI processing is only available to users who have a Computer Vision System Toolbox license. If you only have a DSP System Toolbox license, you can still use ROI processing, but are limited to the **ROI type** Rectangles.

---

Use the **ROI type** parameter to specify whether the ROI is a rectangle, line, label matrix, or binary mask. A binary mask is a binary image that enables you to specify which pixels to highlight, or select. In a label matrix, pixels equal to 0 represent the background, pixels equal to 1 represent the first object, pixels equal to 2 represent the second object, and so on. When the **ROI type** parameter is set to `Label matrix`, the Label and Label Numbers ports appear on the block. Use the Label Numbers port to specify the objects in the label matrix for which the block calculates statistics. The input to this port must be a vector of scalar values that correspond to the labeled regions in the label matrix. For more information about the format of the input to the ROI port when the ROI is a rectangle or a line, see the Draw Shapes block reference page.

For rectangular ROIs, use the **ROI portion to process** parameter to specify whether to calculate the statistical value for the entire ROI or just the ROI perimeter.

Use the **Output** parameter to specify the block output. The block can output separate statistical values for each ROI or the statistical value for all specified ROIs. This parameter is not available if, for the **ROI type** parameter, you select `Binary mask`.

If, for the **ROI type** parameter, you select `Rectangles` or `Lines`, the **Output flag indicating if ROI is within image bounds** check box appears in the dialog box. If you select this check box, the Flag port appears on the block. The following tables describe the Flag port output based on the block parameters.

**Output = Individual statistics for each ROI**

Flag Port Output	Description
0	ROI is completely outside the input image.
1	ROI is completely or partially inside the input image.

**Output = Single statistic for all ROIs**

Flag Port Output	Description
0	All ROIs are completely outside the input image.
1	At least one ROI is completely or partially inside the input image.

If the ROI is partially outside the image, the block only computes the statistical values for the portion of the ROI that is within the image.

If, for the **ROI type** parameter, you select `Label matrix`, the **Output flag indicating if input label numbers are valid** check box appears in the dialog box. If you select this check box, the Flag port appears on the block. The following tables describe the Flag port output based on the block parameters.

**Output = Individual statistics for each ROI**

Flag Port Output	Description
0	Label number is not in the label matrix.
1	Label number is in the label matrix.


# Mean

**Output = Single statistic for all ROIs**

Flag Port Output	Description
0	None of the label numbers are in the label matrix.
1	At least one of the label numbers is in the label matrix.

## Fixed-Point Data Types


The following diagram shows the data types used within the Mean block for fixed-point signals.




You can set the accumulator and output data types in the block dialog, as discussed in "Dialog Box" on page 2-1035.

## Examples

In the `ex_mean_ref` model, the Mean block calculates the running mean of a 3-by-2 matrix input,  $u$ . The **Input processing** parameter is set to `Columns as channels (frame based)`, so the block processes the input as a two channel signal with a frame size of three. The running mean is reset at  $t=2$  by an impulse to the block's `Rst` port.




The operation of the block is shown in the following figure.



## Dialog Box

The **Main** pane of the Mean block dialog appears as follows.

# Mean



## Running mean

Enables running operation when selected.

## Input processing

Specify how the block should process the input when computing the running mean. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.

- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

This parameter appears only when you select the **Running mean** check box.

---

**Note** The option **Inherit from input** (this choice will be removed - see release notes) will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

#### **Reset port**

Specify the reset event that causes the block to reset the running mean. The sample time of the input to the Rst port must be a positive integer multiple of the input sample time. This parameter appears only when you select the **Running mean** check box. For more information, see “Resetting the Running Mean” on page 2-1029.

#### **Find the mean value over**

Specify whether to find the mean value along rows, columns, entire input, or the dimension specified in the **Dimension** parameter. For more information, see “Basic Operation” on page 2-1027.

#### **Treat sample-based row input as a column**

Select to treat sample-based length- $M$  row vector inputs as  $M$ -by-1 column vectors. This parameter is only visible when the **Find the mean value over** parameter is set to **Each column**.

---

**Note** This check box will be removed in a future release. See “Sample-Based Row Vector Processing Changes” in the DSP System Toolbox Release Notes.

---

## Dimension

Specify the dimension (one-based value) of the input signal, over which the mean is computed. The value of this parameter cannot exceed the number of dimensions in the input signal. This parameter is only visible when the **Find the mean value over** parameter is set to Specified dimension.

## Enable ROI Processing

Select this check box to calculate the statistical value within a particular region of each image. This parameter is only available when the **Find the mean value over** parameter is set to Entire input, and the block is not in running mode.

---

**Note** Full ROI processing is available only if you have a Computer Vision System Toolbox license. If you do not have a Computer Vision System Toolbox license, you can still use ROI processing, but are limited to the **ROI type** Rectangles.

---

## ROI type

Specify the type of ROI you want to use. Your choices are Rectangles, Lines, Label matrix, or Binary mask.

## ROI portion to process

Specify whether you want to calculate the statistical value for the entire ROI or just the ROI perimeter. This parameter is only visible if, for the **ROI type** parameter, you specify Rectangles.

## Output

Specify the block output. The block can output a vector of separate statistical values for each ROI or a scalar value that represents the statistical value for all the specified ROIs. This parameter is not available if, for the **ROI type** parameter, you select Binary mask.

## Output flag

**Output flag indicating if ROI is within image bounds**

**Output flag indicating if label numbers are valid**


When you select either of these check boxes, the Flag port appears on the block. For a description of the Flag port output, see the tables in “ROI Processing” on page 2-1031.

The **Output flag indicating if ROI is within image bounds** check box is only visible when you select Rectangles or Lines as the **ROI type**.

The **Output flag indicating if label numbers are valid** check box is only visible when you select Label matrix for the **ROI type** parameter.

The **Data Types** pane of the Mean block dialog appears as follows.

# Mean



## **Rounding mode**

Select the rounding mode for fixed-point operations.

## **Overflow mode**

Select the overflow mode for fixed-point operations.

## **Accumulator data type**

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-1034 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Same as input`

- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

### Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-1034 for illustrations depicting the use of the output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as accumulator`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

### Minimum

Specify the minimum value that the block should output. The default value is `[]` (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Maximum

Specify the maximum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Reset	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

Port	Supported Data Types
ROI	Rectangles and lines: <ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul> Binary Mask: <ul style="list-style-type: none"> <li>• Boolean</li> </ul>
Label	<ul style="list-style-type: none"> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>
Label Numbers	<ul style="list-style-type: none"> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>
Output	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>
Flag	<ul style="list-style-type: none"> <li>• Boolean</li> </ul>

**See Also**

Maximum	DSP System Toolbox
Median	DSP System Toolbox
Minimum	DSP System Toolbox
Standard Deviation	DSP System Toolbox
mean	MATLAB


# Median

---

**Purpose** Find median value of input

**Library** Statistics  
dspstat3

## Description



The Median block computes the median value of each row or column of the input, along vectors of a specified dimension of the input, or of the entire input. The median of a set of input values is calculated as follows:

- 1 The values are sorted.
- 2 If the number of values is odd, the median is the middle value.
- 3 If the number of values is even, the median is the average of the two middle values.

For a given input  $u$ , the size of the output array  $y$  depends on the setting of the **Find the median value over** parameter. For example, consider a 3-dimensional input signal of size  $M$ -by- $N$ -by- $P$ :

- Entire input — The output at each sample time is a scalar that contains the median value of the  $M$ -by- $N$ -by- $P$  input matrix.

```
y = median(u(:))    % Equivalent MATLAB code
```

- Each row — The output at each sample time consists of an  $M$ -by-1-by- $P$  array, where each element contains the median value of each vector over the second dimension of the input. For an input that is an  $M$ -by- $N$  matrix, the output is an  $M$ -by-1 column vector.

```
y = median(u,2)    % Equivalent MATLAB code
```

- Each column — The output at each sample time consists of a 1-by- $N$ -by- $P$  array, where each element contains the median value of each vector over the first dimension of the input. For an input that is an  $M$ -by- $N$  matrix, the output at each sample time is a 1-by- $N$  row vector.

```
y = median(u)      % Equivalent MATLAB code
```

For convenience, length- $M$  1-D vector inputs are treated as  $M$ -by-1 column vectors when the block is in this mode. Sample-based length- $M$  row vector inputs are also treated as  $M$ -by-1 column vectors when the **Treat sample-based row input as a column** check box is selected.

- **Specified dimension** — The output at each sample time depends on **Dimension**. If **Dimension** is set to 1, the output is the same as when you select **Each column**. If **Dimension** is set to 2, the output is the same as when you select **Each row**. If **Dimension** is set to 3, the output at each sample time is an  $M$ -by- $N$  matrix containing the median value of each vector over the third dimension of the input.

```
y = median(u,Dimension)  % Equivalent MATLAB code
```

The block sorts complex inputs according to their magnitude.

## Fixed-Point Data Types

For fixed-point inputs, you can specify accumulator, product output, and output data types as discussed in “Dialog Box” on page 2-1046. Not all these fixed-point parameters are applicable for all types of fixed-point inputs. The following table shows when each kind of data type and scaling is used.

	<b>Output data type</b>	<b>Accumulator data type</b>	<b>Product output data type</b>
<b>Even <math>M</math></b>	X	X	
<b>Odd <math>M</math></b>	X		
<b>Odd <math>M</math> and complex</b>	X	X	X
<b>Even <math>M</math> and complex</b>	X	X	X

# Median

---


The accumulator and output data types and scalings are used for fixed-point signals when  $M$  is even. The result of the sum performed while calculating the average of the two central rows of the input matrix is stored in the accumulator data type and scaling. The total result of the average is then put into the output data type and scaling.

The accumulator and product output parameters are used for complex fixed-point inputs. The sum of the squares of the real and imaginary parts of such an input are formed before the input elements are sorted, as described in Description. The results of the squares of the real and imaginary parts are placed into the product output data type and scaling. The result of the sum of the squares is placed into the accumulator data type and scaling.

For fixed-point inputs that are both complex and have even  $M$ , the data types are used in all of the ways described. Therefore, in such cases, the accumulator type is used in two different ways.

## Dialog Box

The **Main** pane of the Median block dialog appears as follows.



### Sort algorithm

Specify whether to sort the elements of the input using a Quick sort or an Insertion sort algorithm.

### Find the median value over

Specify whether to find the median value along rows, columns, entire input, or the dimension specified in the **Dimension** parameter. For more information, see Description.

# Median

---

## **Treat sample-based row input as a column**

Select to treat sample-based length- $M$  row vector inputs as  $M$ -by-1 column vectors. This parameter is only visible when the **Find the median value over** parameter is set to Each column.

---


**Note** This check box will be removed in a future release. See “Sample-Based Row Vector Processing Changes” in the DSP System Toolbox Release Notes.

---

## **Dimension**

Specify the dimension (one-based value) of the input signal, over which the median is computed. The value of this parameter cannot exceed the number of dimensions in the input signal. This parameter is only visible when the **Find the median value over** parameter is set to Specified dimension.

The **Data Types** pane of the Median block dialog appears as follows.




---

**Note** Floating-point inheritance takes precedence over the data type settings defined on this pane. When inputs are floating point, the block ignores these settings, and all internal data types are floating point.

---

### Rounding mode

Select the rounding mode for fixed-point operations.

## Overflow mode

Select the overflow mode for fixed-point operations.

## Product output data type

Specify the product output data type. See “Fixed-Point Data Types” on page 2-1045 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as input`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Accumulator data type

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-1045 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Same as product output`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

### Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-1045 for illustrations depicting the use of the output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as accumulator`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

### Minimum

Specify the minimum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

### Maximum

Specify the maximum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

### Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

# Median

---

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• 8-, 16-, 32-, and 128-bit signed integers</li><li>• 8-, 16-, 32-, and 128-bit unsigned integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• 8-, 16-, 32-, and 128-bit signed integers</li><li>• 8-, 16-, 32-, and 128-bit unsigned integers</li></ul>

## See Also

Maximum	DSP System Toolbox
Mean	DSP System Toolbox
Minimum	DSP System Toolbox
Sort	DSP System Toolbox
Standard Deviation	DSP System Toolbox
Variance	DSP System Toolbox
median	MATLAB

**Purpose** Output values from controls on MIDI control surface

**Library** Sources  
dspsrcs4

## Description



The MIDI Controls block outputs values from controls on a MIDI control surface in real time.

Use the **MIDI device** parameter to specify the name of the MIDI control surface device from which to receive control values. You can choose:

- Default
- Specify other

If you choose **Default**, the block looks for a MATLAB preference with a group named `midi` and preference named `DefaultDevice`. You can set this preference using the MATLAB `setpref` function. For example, if the desired device is named `BCF2000`, you can type the following command at the MATLAB command line:

```
>> setpref('midi', 'DefaultDevice', 'BCF2000');
```

If the block does not find this preference, it then attempts to choose a device using an algorithm that is unspecified and platform dependent.

If you choose **Specify other**, then a **MIDI device name** edit box appears for you to enter a MATLAB expression for the device name. Enter any MATLAB expression that can evaluate to a string. Literal names must be enclosed in quotes, (for example, `'BCF2000'`).

You can determine the name of your MIDI device using the MATLAB function `midiid`, discussed in “Identifying MIDI Device Names and Control Numbers” on page 2-1055.

Use the **MIDI controls** parameter to specify the controls on the MIDI device to which the block should respond. This parameter also determines the size of the block output port. You can choose:

# MIDI Controls

---

- Respond to any control
- Respond to specified controls

If you choose **Respond to any control**, then the block output will be a scalar. This scalar outputs the value from any and all controls that are manipulated on the MIDI device. Use this option in simple cases when you need only a single control value and the control to which it responds is unimportant.

If you choose **Respond to specified controls**, then a **MIDI control numbers** edit box opens. In this box, enter a MATLAB expression for the device control numbers. Enter any MATLAB expression that can evaluate to a row vector of real double-precision values. The block outputs a 1-D vector with one element corresponding to the output of each specified control.

Use the **Initial values** parameter to specify the value of the block output when simulation starts. The MIDI protocol transmits control values only when a control changes. This protocol provides no means for the block to query the current value of a control. Thus, the block must have some initial value to output until it receives a control change from the device.

Use the **Send initial values to device at start** check box to synchronize the device controls with the block outputs when simulation starts. Some MIDI control surfaces are bidirectional, meaning that they not only send control values but can also receive them. For example, some devices have motorized controls that move to the appropriate position when they receive a control value. If you have such a bidirectional device, select this check box. The block attempts to send the initial values to the device when the simulation starts. No diagnostic message appears if the attempt fails.

The generated code for this block relies on prebuilt .dll files. You can run this code outside the MATLAB environment, or redeploy. However you must account for these extra .dll files when doing so. The packNGo function creates a single .zip file containing all of the pieces required to run or rebuild this code. See packNGo for more information.

## Output Port

The MIDI Controls block output is a vector whose width is determined by the **MIDI controls** and **MIDI control numbers** parameters previously described. The output data type is real double-precision floating point. The output values range from 0.0 to 1.0, inclusively. The output port back inherits its sample time.

## Identifying MIDI Device Names and Control Numbers

To specify a particular control on a particular MIDI device, you must know the name assigned to the device by the operating system. In addition, a number is always associated with the control. You can interactively discover this information using the MATLAB function, `midiid`. Follow these steps to identify device names and control numbers:

- 1 Verify that MIDI control surface device is correctly connected to the host computer running MATLAB.

---

**Note** For the most consistent behavior, MathWorks recommends that you connect your MIDI control surface device to your computer before starting MATLAB. In some circumstances MATLAB may not be able to find your device if you connect it after starting your MATLAB session. Also, it may not find your device if you disconnect it and reconnect it during your MATLAB session.

---

- 2 Type the following command at the MATLAB command line.

```
>> [ctlnum devname] = midiid
```

You are prompted to move the control in which you are interested.

```
>> [ctlnum devname] = midiid
```

Move the control you wish to identify; type ^C to abort.  
Waiting for control message ...

# MIDI Controls

---

- 3 Move the control. `midiid` detects the movement and returns the device name and control number.

```
>> [ctlnum devname] = midiid
Move the control you wish to identify; type ^C to abort.
Waiting for control message ... done
ctlnum =
    1081
devname =
    BCF2000
>>
```

- 4 Use the device name in the block dialog, or set it as the default device using `setpref`. Then, enter the control number in the block dialog. Concatenate the number with other control numbers as needed.

## Examples

### How to Output Values from Controls

Use this example to familiarize yourself with how to set controls in the MIDI Controls block as it interacts with the MIDI control surface.



Open the `ex_simplemidi` model, and follow these steps:

- 1  
Connect a MIDI device to the computer.
- 2  
Use `midiid` to determine the name of the device, and set it on the MIDI Controls block.
- 3  
Verify that any control changes the display value.

**4**

Use `midiid` to determine the number of a particular control, and set that on the MIDI Controls block.

**5**

Verify that a particular control changes the display value and that other controls do not.

**6**

Use `midiid` to determine the number of a few more controls, and set those on the MIDI Controls block.

**7**

Verify that the display block shows the correct number of values. Also verify that the controls you specified change the appropriate display values and that the other controls do not change the values.

**8**

Set each control to have a unique initial value.

**9**

Verify that the correct initial values appear on the display when the model starts.


**10**

If your MIDI device is bidirectional, on the MIDI Controls block, select the **Send initial values to device at start** check box.

**11**

Verify that the controls are set to the correct initial values when the model starts.

# MIDI Controls



## Dialog Box

### MIDI device

Specify whether to use a default MIDI device, or specify a particular device by name.

**MIDI device name**

Specify the name of a particular MIDI control surface device from which to receive control values.

**MIDI controls**

Specify whether to respond to any control on the MIDI device or respond to particular specified controls.

**MIDI control numbers**

Specify particular controls to which the block should respond.

**Initial values**

Specify initial values to output when simulation starts.

**Send initial values to device at start**

Select this check box to attempt to synchronize a bidirectional MIDI device with block initial values when simulation starts.

**Supported  
Data  
Types**

Port	Supported Data Types
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li></ul>

# Minimum

---

## Purpose


Find minimum values in input or sequence of inputs

## Library

Statistics

dspstat3

## Description



The Minimum block identifies the value and/or position of the smallest element in each row or column of the input, along vectors of a specified dimension of the input, or of the entire input. The Minimum block can also track the minimum values in a sequence of inputs over a period of time. The **Mode** parameter specifies the block's mode of operation, and can be set to Value, Index, Value and Index, or Running.

The Minimum block supports real and complex floating-point, fixed-point, and Boolean inputs. Real fixed-point inputs can be either signed or unsigned, while complex fixed-point inputs must be signed. The data type of the minimum values output by the block match the data type of the input. The index values output by the block are double when the input is double, and uint32 otherwise.

For the Value, Index, and Value and Index modes, the Minimum block produces identical results as the MATLAB `min` function when it is called as  $[y \ I] = \min(u, [], D)$ , where  $u$  and  $y$  are the input and output, respectively,  $D$  is the dimension, and  $I$  is the index.

## Value Mode

When the **Mode** parameter is set to Value, the block computes the minimum value in each row or column of the input, along vectors of a specified dimension of the input, or of the entire input at each sample time, and outputs the array  $y$ . Each element in  $y$  is the minimum value in the corresponding column, row, vector, or entire input. The output  $y$  depends on the setting of the **Find the minimum value over** parameter. For example, consider a 3-dimensional input signal of size  $M$ -by- $N$ -by- $P$ :

- Each row — The output at each sample time consists of an  $M$ -by-1-by- $P$  array, where each element contains the minimum value of each vector over the second dimension of the input. For an input

that is an  $M$ -by- $N$  matrix, the output at each sample time is an  $M$ -by-1 column vector.


- **Each column** — The output at each sample time consists of a 1-by- $N$ -by- $P$  array, where each element contains the minimum value of each vector over the first dimension of the input. For an input that is an  $M$ -by- $N$  matrix, the output at each sample time is a 1-by- $N$  row vector.

In this mode, the block treats length- $M$  unoriented vector inputs as  $M$ -by-1 column vectors.

- **Entire input** — The output at each sample time is a scalar that contains the minimum value in the  $M$ -by- $N$ -by- $P$  input matrix.
- **Specified dimension** — The output at each sample time depends on **Dimension**. If **Dimension** is set to 1, the output is the same as when you select **Each column**. If **Dimension** is set to 2, the output is the same as when you select **Each row**. If **Dimension** is set to 3, the output at each sample time is an  $M$ -by- $N$  matrix containing the minimum value of each vector over the third dimension of the input.

For complex inputs, the block selects the value in each row or column of the input, along vectors of a specified dimension of the input, or of the entire input that has the minimum magnitude squared as shown below.

For complex value  $u = a + bi$ , the magnitude squared is  $a^2 + b^2$ .



## Index Mode

When **Mode** is set to **Index**, the block computes the minimum value in each row or column of the input, along vectors of a specified dimension

# Minimum

---

of the input, or of the entire input, and outputs the index array  $I$ . Each element in  $I$  is an integer indexing the minimum value in the corresponding column, row, vector, or entire input. The output  $I$  depends on the setting of the **Find the minimum value over** parameter. For example, consider a 3-dimensional input signal of size  $M$ -by- $N$ -by- $P$ :

- **Each row** — The output at each sample time consists of an  $M$ -by-1-by- $P$  array, where each element contains the index of the minimum value of each vector over the second dimension of the input. For an input that is an  $M$ -by- $N$  matrix, the output at each sample time is an  $M$ -by-1 column vector.
- **Each column** — The output at each sample time consists of a 1-by- $N$ -by- $P$  array, where each element contains the index of the minimum value of each vector over the first dimension of the input. For an input that is an  $M$ -by- $N$  matrix, the output at each sample time is a 1-by- $N$  row vector.

In this mode, the block treats length- $M$  unoriented vector inputs as  $M$ -by-1 column vectors.

- **Entire input** — The output at each sample time is a 1-by-3 vector that contains the location of the minimum value in the  $M$ -by- $N$ -by- $P$  input matrix. For an input that is an  $M$ -by- $N$  matrix, the output will be a 1-by-2 vector.
- **Specified dimension** — The output at each sample time depends on **Dimension**. If **Dimension** is set to 1, the output is the same as when you select **Each column**. If **Dimension** is set to 2, the output is the same as when you select **Each row**. If **Dimension** is set to 3, the output at each sample time is an  $M$ -by- $N$  matrix containing the indices of the minimum values of each vector over the third dimension of the input.

When a minimum value occurs more than once, the computed index corresponds to the first occurrence. For example, when the input is the column vector  $[-1 \ 2 \ 3 \ 2 \ -1]'$ , the computed one-based index of the minimum value is 1 rather than 5 when **Each column** is selected.

## Value and Index Mode

When **Mode** is set to **Value** and **Index**, the block outputs both the minima and the indices.

## Running Mode

When **Mode** is set to **Running**, the block tracks the minimum value of each channel in a time sequence of  $M$ -by- $N$  inputs. In this mode, you must also specify a value for the **Input processing** parameter:

- When you select **Elements as channels (sample based)**, the block outputs an  $M$ -by- $N$  array. Each element  $y_{ij}$  of the output contains the minimum value observed in element  $u_{ij}$  for all inputs since the last reset.
- When you select **Columns as channels (frame based)**, the block outputs an  $M$ -by- $N$  matrix. Each element  $y_{ij}$  of the output contains the minimum value observed in the  $j$ th column of all inputs since the last reset, up to and including element  $u_{ij}$  of the current input.

## Running Mode for Variable-Size Inputs

When your inputs are of variable size, and you set the **Mode** to **Running**, there are two options:

- If you set the **Input processing** parameter to **Elements as channels (sample based)**, the state is reset.
- If you set the **Input processing** parameter to **Columns as channels (frame based)**, then there are two cases:
  - When the input size difference is in the number of channels (i.e., number of columns), the state is reset.
  - When the input size difference is in the length of channels (i.e., number of rows), there is no reset and the running operation is carried out as usual.


## Resetting the Running Minimum

The block resets the running minimum whenever a reset event is detected at the optional Rst port. The reset sample time must be a positive integer multiple of the input sample time.


When a reset event occurs while the **Input processing** parameter is set to **Elements as channels (sample based)**, the running minimum for each channel is initialized to the value in the corresponding channel of the current input. Similarly, when the **Input processing** parameter is set to **Columns as channels (frame based)**, the running minimum is initialized to the earliest value in each channel of the current input.

You specify the reset event by the **Reset port** parameter:

- None — Disables the Rst port
- Rising edge — Triggers a reset operation when the Rst input does one of the following:
  - Rises from a negative value to a positive value or zero
  - Rises from zero to a positive value, where the rise is not a continuation of a rise from a negative value to zero (see the following figure)



- **Falling edge** — Triggers a reset operation when the Rst input does one of the following:
  - Falls from a positive value to a negative value or zero
  - Falls from zero to a negative value, where the fall is not a continuation of a fall from a positive value to zero (see the following figure)



- **Either edge** — Triggers a reset operation when the Rst input is a Rising edge or Falling edge (as described above)
- **Non-zero sample** — Triggers a reset operation at each sample time that the Rst input is not zero

---

**Note** When running simulations in the Simulink MultiTasking mode, reset signals have a one-sample latency. Therefore, when the block detects a reset event, there is a one-sample delay at the reset port rate before the block applies the reset. For more information on latency and the Simulink tasking modes, see “Excess Algorithmic Delay (Tasking Latency)” and “Scheduling” in the *Simulink Coder User’s Guide*.

---

## ROI Processing

To calculate the statistical value within a particular region of interest (ROI) of the input, select the **Enable ROI processing** check box. This applies to any mode other than the running mode and when you set the **Find the minimum value over** parameter to `Entire input` and you select the **Enable ROI processing** check box. ROI processing applies only for 2-D inputs.

---

**Note** Full ROI processing is only available to users who have a Computer Vision System Toolbox license. If you only have a DSP System Toolbox license, you can still use ROI processing, but are limited to the **ROI type Rectangles**.

---

Use the **ROI type** parameter to specify whether the ROI is a rectangle, line, label matrix, or binary mask. A binary mask is a binary image that enables you to specify which pixels to highlight, or select. In a label matrix, pixels equal to 0 represent the background, pixels equal to 1 represent the first object, pixels equal to 2 represent the second object, and so on. When the **ROI type** parameter is set to `Label matrix`, the `Label` and `Label Numbers` ports appear on the block. Use the `Label Numbers` port to specify the objects in the label matrix for which the block calculates statistics. The input to this port must be a vector of scalar values that correspond to the labeled regions in the label matrix. For more information about the format of the input to the ROI port when the ROI is a rectangle or a line, see the `Draw Shapes` block reference page.

For rectangular ROIs, use the **ROI portion to process** parameter to specify whether to calculate the statistical value for the entire ROI or just the ROI perimeter.

Use the **Output** parameter to specify the block output. The block can output separate statistical values for each ROI or the statistical value for all specified ROIs. This parameter is not available if, for the **ROI type** parameter, you select `Binary mask`.

If, for the **ROI type** parameter, you select **Rectangles** or **Lines**, the **Output flag indicating if ROI is within image bounds** check box appears in the dialog box. If you select this check box, the Flag port appears on the block. The following tables describe the Flag port output based on the block parameters.

### Output = Individual statistics for each ROI

Flag Port Output	Description
0	ROI is completely outside the input image.
1	ROI is completely or partially inside the input image.

### Output = Single statistic for all ROIs

Flag Port Output	Description
0	All ROIs are completely outside the input image.
1	At least one ROI is completely or partially inside the input image.

If the ROI is partially outside the image, the block only computes the statistical values for the portion of the ROI that is within the image.

If, for the **ROI type** parameter, you select **Label matrix**, the **Output flag indicating if input label numbers are valid** check box appears in the dialog box. If you select this check box, the Flag port appears on the block. The following tables describe the Flag port output based on the block parameters.

# Minimum

---

## Output = Individual statistics for each ROI

Flag Port Output	Description
0	Label number is not in the label matrix.
1	Label number is in the label matrix.

## Output = Single statistic for all ROIs


Flag Port Output	Description
0	None of the label numbers are in the label matrix.
1	At least one of the label numbers is in the label matrix.

## Fixed-Point Data Types


The parameters on the **Data Types** pane of the block dialog are only used for complex fixed-point inputs. The sum of the squares of the real and imaginary parts of such an input are formed before a comparison is made, as described in “Value Mode” on page 2-1060. The results of the squares of the real and imaginary parts are placed into the product output data type. The result of the sum of the squares is placed into the accumulator data type. These parameters are ignored for other types of inputs.

## Examples

In the following `ex_minimum_ref` model, the Minimum block calculates the running minimum of a 3-by-2 matrix input. The **Input processing** parameter is set to `Columns as channels (frame based)`, so the block processes the input as a two channel signal with a frame size of three. The running minimum is reset at  $t=2$  by an impulse to the block's Rst port.




The operation of the block is shown in the following figure.



# Minimum

## Dialog Box

The **Main** pane of the Minimum block dialog appears as follows.



## Mode

Specify the block's mode of operation:

- Value — Output the minimum value of each input
- Index — Output the index of the minimum value
- Value and index — Output both the value and the index

- **Running** — Track the minimum value of the input sequence over time

For more information, see Description.

### **Index base**

Specify whether the index of the minimum value is reported using one-based or zero-based numbering. This parameter is only visible when the **Mode** parameter is set to **Index** or **Value** and **index**.

### **Find the minimum value over**

Specify whether to find the minimum value along rows, columns, entire input, or the dimension specified in the **Dimension** parameter. For more information, see Description.

### **Input processing**

Specify how the block should process the input when computing the running minimum. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

This parameter appears only when you set the **Mode** to **Running**.

---

**Note** The option **Inherit from input** (this choice will be removed - see release notes) will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Reset port

Specify the reset event that causes the block to reset the running minimum. The sample time of the input to the Rst port must be a positive integer multiple of the input sample time. This parameter appears only when you set the **Mode** parameter to **Running**. For information about the possible values of this parameter, see “Resetting the Running Minimum” on page 2-1064.

## Treat sample-based row input as a column

Select to treat sample-based length- $M$  row vector inputs as  $M$ -by-1 column vectors. This parameter is only visible when the **Find the minimum value of** parameter is set to **Each column**.

---

**Note** This check box will be removed in a future release. See “Sample-Based Row Vector Processing Changes” in the DSP System Toolbox Release Notes.

---

## Dimension

Specify the dimension (one-based value) of the input signal, over which the minimum is computed. The value of this parameter cannot exceed the number of dimensions in the input signal. This parameter is only visible when the **Find the minimum value over** parameter is set to **Specified dimension**.

## Enable ROI processing


Select this check box to calculate the statistical value within a particular region of each image. This parameter is only available when the **Find the minimum value over** parameter is set to **Entire input**, and the block is not in running mode.

---

**Note** Full ROI processing is only available to users who have a Computer Vision System Toolbox license. If you only have a DSP System Toolbox license, you can still use ROI processing, but are limited to the **ROI type Rectangles**.

---

The ROI processing parameters appear as follows.



## ROI type

Specify the type of ROI you want to use. Your choices are Rectangles, Lines, Label matrix, or Binary mask.

## **ROI portion to process**

Specify whether you want to calculate the statistical value for the entire ROI or just the ROI perimeter. This parameter is only visible if, for the **ROI type** parameter, you specify Rectangles.

## **Output**

Specify the block output. The block can output a vector of separate statistical values for each ROI or a scalar value that represents the statistical value for all the specified ROIs. This parameter is not available if, for the **ROI type** parameter, you select Binary mask.

## **Output flag**

**Output flag indicating if ROI is within image bounds**


**Output flag indicating if label numbers are valid**

When you select either of these check boxes, the Flag port appears on the block. For a description of the Flag port output, see the tables in “ROI Processing” on page 2-1066.

The **Output flag indicating if ROI is within image bounds** check box is only visible when you select Rectangles or Lines as the **ROI type**.

The **Output flag indicating if label numbers are valid** check box is only visible when you select Label matrix for the **ROI type** parameter.

The **Data Types** pane of the Minimum block dialog appears as follows.



---

**Note** The parameters on the **Data Types** pane are only used for complex fixed-point inputs. The sum of the squares of the real and imaginary parts of such an input are formed before a comparison is made, as described in “Value Mode” on page 2-1060. The results of the squares of the real and imaginary parts are placed into the product output data type. The result of the sum of the squares is placed into the accumulator data type. These parameters are ignored for other types of inputs.

---

## **Rounding mode**

Select the rounding mode for fixed-point operations.

## **Overflow mode**

Select the overflow mode for fixed-point operations.

## **Product output data type**

Specify the product output data type. See “Fixed-Point Data Types” on page 2-1068 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as input`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## **Accumulator data type**

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-1068 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Same as input`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

**Lock data type settings against changes by the fixed-point tools**

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

**Supported Data Types**

Port	Supported Data Types
Input	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed and unsigned)</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>
Reset	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>
Idx	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• 32-bit unsigned integers</li> </ul>
Val	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed and unsigned)</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>

# Minimum

---

## See Also

Maximum

DSP System Toolbox

Mean

DSP System Toolbox

MinMax

Simulink

Histogram

DSP System Toolbox

min

MATLAB

# Modified Covariance AR Estimator

## Purpose


Compute estimate of autoregressive (AR) model parameters using modified covariance method

## Library

Estimation / Parametric Estimation

dspparest3

## Description



The Modified Covariance AR Estimator block uses the modified covariance method to fit an autoregressive (AR) model to the input data. This method minimizes the forward and backward prediction errors in the least squares sense. The input is a frame of consecutive time samples, which is assumed to be the output of an AR system driven by white noise. The block computes the normalized estimate of the AR system parameters,  $A(z)$ , independently for each successive input.

$$H(z) = \frac{G}{A(z)} = \frac{G}{1 + a(2)z^{-1} + \dots + a(p+1)z^{-p}}$$

You specify the order,  $p$ , of the all-pole model in the **Estimation order** parameter. To guarantee a valid output, you must set the **Estimation order** parameter to be less than or equal to two thirds the input vector length.


The output port labeled A outputs the normalized estimate of the AR model coefficients in descending powers of  $z$ .

$$[1 \ a(2) \ \dots \ a(p+1)]$$

The scalar gain,  $G$ , is output from the output port labeled G.

See the Burg AR Estimator block reference page for a comparison of the Burg AR Estimator, Covariance AR Estimator, Modified Covariance AR Estimator, and Yule-Walker AR Estimator blocks.

# Modified Covariance AR Estimator



## Dialog Box

### Estimation order

Specify the order of the AR model,  $p$ .

## References

Kay, S. M. *Modern Spectral Estimation: Theory and Application*. Englewood Cliffs, NJ: Prentice-Hall, 1988.

Marple, S. L., Jr., *Digital Spectral Analysis with Applications*. Englewood Cliffs, NJ: Prentice-Hall, 1987.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
A	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
G	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

The output data type is the same as the input data type.

# Modified Covariance AR Estimator

---

## See Also

Burg AR Estimator

Covariance AR Estimator

Modified Covariance Method

Yule-Walker AR Estimator

`armcov`

DSP System Toolbox

DSP System Toolbox

DSP System Toolbox

DSP System Toolbox

Signal Processing Toolbox

# Modified Covariance Method

---

**Purpose** Power spectral density estimate using modified covariance method

**Library** Estimation / Power Spectrum Estimation  
dspsect3

## Description



The Modified Covariance Method block estimates the power spectral density (PSD) of the input using the modified covariance method. This method fits an autoregressive (AR) model to the signal. It does so by minimizing the forward and backward prediction errors in the least squares sense. The **Estimation order** parameter value specifies the order of the all-pole model. To guarantee a valid output, the **Estimation order** parameter must be less than or equal to two thirds of the input vector length. The block computes the spectrum from the FFT of the estimated AR model parameters.

The input must be a sample-based vector (row, column, or 1-D) or frame-based vector (column only). This input represents a frame of consecutive time samples from a single-channel signal. The block outputs a column vector containing the estimate of the power spectral density of the signal at  $N_{fft}$  equally spaced frequency points. The frequency points are in the range  $[0, F_s)$ , where  $F_s$  is the sampling frequency of the signal.

Selecting **Inherit FFT length from estimation order**, specifies that  $N_{fft}$  is one greater than the estimation order. Clearing the **Inherit FFT length from estimation order** check box allows you to use the **FFT length** parameter to specify  $N_{fft}$  as a power of 2. The block zero-pads or wraps the input to  $N_{fft}$  before computing the FFT. The output is always sample based.

When you select the **Inherit sample time from input** check box, the block computes the frequency data from the sample period of the input signal. For the block to produce valid output, the following conditions must hold:

- The input to the block is the original signal, with no samples added or deleted (by insertion of zeros, for example).

- The sample period of the time-domain signal in the simulation equals the sample period of the original time series.


If these conditions do not hold, clear the **Inherit sample time from input** check box. You can then specify a sample time using the **Sample time of original time series** parameter.

See the Burg Method block reference for a comparison of the Burg Method, Covariance Method, Modified Covariance Method, and Yule-Walker Method blocks.

## Examples

The `dspsacomp` example compares the modified covariance method with several other spectral estimation methods.

# Modified Covariance Method



## Dialog Box

### Estimation order

Specify the order of the AR model. To guarantee a valid output, the **Estimation order** parameter must be less than or equal to two thirds of the input vector length.

### Inherit FFT length from estimation order

When you select this check box, the option specifies that the FFT length is one greater than the estimation order. To specify the number of points on which to perform the FFT, clear this check box. You can then specify a power of two FFT length using the **FFT length** parameter.

### FFT length

Enter the number of data points,  $N_{fft}$ , on which to perform the FFT. When  $N_{fft}$  is larger than the input frame size, the block zero-pads each frame as needed. When  $N_{fft}$  is smaller than the input frame size, the block wraps each frame as needed. This

parameter becomes visible only when you clear the **Inherit FFT length from estimation order** check box.

## **Inherit sample time from input**

If you select the **Inherit sample time from input** check box, the block computes the frequency data from the sample period of the input signal. For the block to produce valid output, the following conditions must hold:

- The input to the block is the original signal, with no samples added or deleted (by insertion of zeros, for example).
- The sample period of the time-domain signal in the simulation equals the sample period of the original time series.

If these conditions do not hold, clear the **Inherit sample time from input** check box. You can then specify a sample time using the **Sample time of original time series** parameter.

## **Sample time of original time series**

Specify the sample time of the original time-domain signal. This parameter becomes visible only when you clear the **Inherit sample time from input** check box.

## **References**

Kay, S. M. *Modern Spectral Estimation: Theory and Application*. Englewood Cliffs, NJ: Prentice-Hall, 1988.

Marple, S. L. Jr., *Digital Spectral Analysis with Applications*. Englewood Cliffs, NJ: Prentice-Hall, 1987.

Orfanidis, S. J. *Introduction to Signal Processing*. Englewood Cliffs, NJ: Prentice-Hall, 1995.

# Modified Covariance Method

---

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

The output data type is the same as the input data type.

## See Also

Burg Method	DSP System Toolbox
Covariance Method	DSP System Toolbox
Modified Covariance AR Estimator	DSP System Toolbox
Short-Time FFT	DSP System Toolbox
Yule-Walker Method	DSP System Toolbox
spectrum.mcov	Signal Processing Toolbox

See “Spectral Analysis” for related information.


## Purpose

Generate multiple binary clock signals

## Library

- Sources  
dpsrcs4
- Signal Management / Switches and Counters  
dpswit3

## Description



The Multiphase Clock block generates a 1-by- $N$  vector of clock signals, where you specify the integer  $N$  in the **Number of phases** parameter. Each of the  $N$  phases has the same frequency,  $f$ , specified in hertz by the **Clock frequency** parameter.

The clock signal indexed by the **Starting phase** parameter is the first to become active, at  $t=0$ . The other signals in the output vector become active in turn, each one lagging the preceding signal's activation by  $1/(N*f)$  seconds, the phase interval. The period of the output is therefore  $1/(N*f)$  seconds.


The active level can be either high (1) or low (0), as specified by the **Active level (polarity)** parameter. The duration of the active level,  $D$ , is set by the **Number of phase intervals over which the clock is active**. This value, which can be an integer value between 1 and  $N-1$ , specifies the number of phase intervals that each signal should remain in the active state after becoming active. The active duty cycle of the signal is  $D/N$ .

## Examples

In the following `ex_multiphaseclock_ref` model, the Multiphase Clock block generates a 100 Hz five-phase output in which the third signal is first to become active. The block uses a high active level with a duration of one interval.


# Multiphase Clock

---



The Scope window below shows the Multiphase Clock block's output. Note that the first active level appears at  $t=0$  on  $y(3)$ , the second active level appears at  $t=0.002$  on  $y(4)$ , the third active level appears at  $t=0.004$  on  $y(5)$ , the fourth active level appears at  $t=0.006$  on  $y(1)$ , and the fifth active level appears at  $t=0.008$  on  $y(2)$ . Each signal becomes active  $1/(5*100)$  seconds after the previous signal.


# Multiphase Clock



To experiment further, try changing the **Number of phase intervals over which clock is active** setting to 3 so that the active-level duration is three phase intervals (60% duty cycle).

# Multiphase Clock

---



## Dialog Box

### Clock frequency

The frequency of all output clock signals.

### Number of phases

The number of different phases,  $N$ , in the output vector.

### Starting phase

The vector index of the output signal to first become active.

### Number of phase intervals over which clock is active

The duration of the active level for every output signal.

### Active level

The active level, High (1) or Low (0).

### Output data type

The output data type.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point
- Boolean

## See Also

Clock	Simulink
Counter	DSP System Toolbox
Pulse Generator	Simulink
Event-Count Comparator	DSP System Toolbox

# Multiport Selector

---


## Purpose

Distribute arbitrary subsets of input rows or columns to multiple output ports

## Library

Signal Management / Indexing  
dspindex

## Description



The Multiport Selector block extracts multiple subsets of rows or columns from  $M$ -by- $N$  input matrix  $u$ , and propagates each new submatrix to a distinct output port. The block treats an unoriented length- $M$  vector input as an  $M$ -by-1 matrix.

The **Indices to output** parameter is a cell array whose  $k$ th cell contains a one-dimensional indexing expression specifying the subset of input rows or columns to be propagated to the  $k$ th output port. The total number of cells in the array determines the number of output ports on the block.

When you set the **Select** parameter to **Rows**, the block uses the one-dimensional indices you specify to select matrix rows, and all elements on the chosen rows are included. When you set the **Select** parameter to **Columns**, the block uses the one-dimensional indices you specify to select matrix columns, and all elements on the chosen columns are included. A given input row or column can appear any number of times in any of the outputs, or not at all.

When an index references a nonexistent row or column of the input, the block reacts with the action you specify using the **Invalid index** parameter.

## Examples

### Example 1

Consider the following **Indices to output** cell array:


```
{4, [1:2 5], [7;8], 10:-1:6}
```

This is a four-cell array, which requires the block to generate four independent outputs (each at a distinct port). The table below shows

the dimensions of these outputs when **Select** = Rows and the input dimension is  $M$ -by- $N$ .

<b>Cell</b>	<b>Expression</b>	<b>Description</b>	<b>Output Size</b>
1	4	Row 4 of input	1-by- $N$
2	[1:2 5]	Rows 1, 2, and 5 of input	3-by- $N$
3	[7;8]	Rows 7 and 8 of input	2-by- $N$
4	10:-1:6	Rows 10, 9, 8, 7, and 6 of input	5-by- $N$

# Multiport Selector



## Dialog Box

### Select

Specify the dimension of the input to select, Rows or Columns.

### Indices to output

A cell array specifying the row- or column-subsets to propagate to each of the output ports. The number of cells in the array determines the number of output ports on the block.

### Invalid index

Specify how the block handles an invalid index value. You can select one of the following options:

- **Clip index** — Clip the index to the nearest valid value, and do not issue an alert.

For example, if the block receives a 64-by-4 input and the **Select** parameter is set to **Rows**, the block clips an index of 72 to 64. For the same input, if the **Select** parameter is set to **Columns**, the block clips an index of 72 to 4. In both cases, the block clips an index of -2 to 1.

- **Clip and warn** — Clip the index to the nearest valid value and display a warning message at the MATLAB command line.
- **Generate error** — Display an error dialog box and terminate the simulation.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed and unsigned)</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> <li>• Enumerated</li> </ul>
Outputs	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed and unsigned)</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> <li>• Enumerated</li> </ul>

# Multiport Selector

---

## See Also

Permute Matrix  
Selector  
Submatrix  
Variable Selector

DSP System Toolbox  
Simulink  
DSP System Toolbox  
DSP System Toolbox


## Purpose

Output ones or zeros for specified number of sample times

## Library

- Sources  
dpsrcs4
- Signal Management / Switches and Counters  
dpswit3

## Description



The N-Sample Enable block outputs the inactive value (0 or 1, whichever is not selected in the **Active level** parameter) during the first  $N$  sample times, where  $N$  is the **Trigger count** value. Beginning with output sample  $N+1$ , the block outputs the active value (1 or 0, whichever you select in the **Active level** parameter) until a reset event occurs or the simulation terminates.



The output of the block is always a scalar.

The **Reset input** check box enables the Rst input port. At any time during the count, a trigger event at the input port resets the counter to its initial state. This block supports triggered subsystems when you select the **Reset input** check box.



You specify the triggering event in the **Trigger type** pop-up menu:

- **Rising edge** — Triggers a reset operation when the Rst input does one of the following:
  - Rises from a negative value to a positive value or zero
  - Rises from zero to a positive value, where the rise is not a continuation of a rise from a negative value to zero (see the following figure)


# N-Sample Enable



- Falling edge — Triggers a reset operation when the Rst input does one of the following:
  - Falls from a positive value to a negative value or zero
  - Falls from zero to a negative value, where the fall is not a continuation of a fall from a positive value to zero (see the following figure)



- Either edge — Triggers a reset operation when the Rst input is a Rising edge or Falling edge (as described above).
- Non-zero sample — Triggers a reset operation at each sample time that the Rst input is not zero.



## Dialog Box

### Trigger count

Specify the number of samples for which the block outputs the active value. Tunable.

### Active level

Specify the value to output after the first  $N$  sample times, 0 or 1. Tunable.

### Reset input

Select to enable the Rst input port.

# N-Sample Enable

---

## Trigger type

Select type of event that triggers a reset when the Rst port is enabled.

## Sample time

Specify the sample period,  $T_s$ , for the block's counter. The block switches from the active value to the inactive value at  $t=T_s*(N+1)$ .

## Output data type

Select the output data type.

## Supported Data Types

- Double-precision floating point
- Boolean — The block accepts Boolean inputs to the Rst port, which is enabled when you select the **Reset input** parameter.


## See Also

Counter	DSP System Toolbox
N-Sample Switch	DSP System Toolbox

**Purpose** Switch between two inputs after specified number of sample periods

**Library** Signal Management / Switches and Counters  
dspswit3

## Description



The N-Sample Switch block outputs the signal connected to the top input port during the first  $N$  sample times after the simulation begins or the block is reset, where you specify  $N$  in the **Switch count** parameter. Beginning with output sample  $N+1$ , the block outputs the signal connected to the bottom input until the next reset event or the end of the simulation.

You specify the sample period of the output in the **Sample time** parameter (that is, the output sample period is not inherited from the sample period of either input). The block applies a zero-order hold at the input ports, so the value the block reads from a given port between input sample times is the value of the most recent input to that port.

Both inputs must have the same dimension, except in the following two cases:

- When one input is a scalar, the block expands the scalar input to match the size of the other input.
- When one input is an unoriented vector and the other input is a row or column vector with the same number of elements, the block reshapes the unoriented vector to match the dimension of the other input.


The **Reset input** check box enables the Rst input port. At any time during the count, a trigger event at the Rst port resets the counter to zero. The reset sample time must be a positive integer multiple of the input sample time. This block supports triggered subsystems when you select the **Reset input** check box.

You specify the triggering event in the **Trigger type** pop-up menu, and can be one of the following:


# N-Sample Switch

---

- **Rising edge** — Triggers a reset operation when the Rst input does one of the following:
  - Rises from a negative value to a positive value or zero
  - Rises from zero to a positive value, where the rise is not a continuation of a rise from a negative value to zero (see the following figure)




- **Falling edge** — Triggers a reset operation when the Rst input does one of the following:
  - Falls from a positive value to a negative value or zero
  - Falls from zero to a negative value, where the fall is not a continuation of a fall from a positive value to zero (see the following figure)



- **Either edge** — Triggers a reset operation when the Rst input is a Rising edge or Falling edge (as described above).
- **Non-zero sample** — Triggers a reset operation at each sample time that the Rst input is not zero.

# N-Sample Switch



## Dialog Box

### Switch count

The number of sample periods,  $N$ , for which the output is connected to the top input before switching to the bottom input. Tunable.

### Reset input

Enables the Rst input port when selected. The rate of the reset signal must be a positive integer multiple of the rate of the data signal input.

### Trigger type

The type of event at the Rst port that resets the block's counter. This parameter is enabled when you select **Reset input**. Tunable.

## Sample time

The sample period,  $T_s$ , for the block's counter. The block switches inputs at  $t=T_s*(N+1)$ .

## Supported Data Types

- Double-precision floating point
- Single-precision floating point
- Fixed point (signed and unsigned)
- Boolean — The block accepts Boolean inputs to the Rst port, which is enabled when you set the **Reset input** parameter.
- 8-, 16-, and 32-bit signed integers
- 8-, 16-, and 32-bit unsigned integers

## See Also


Counter	DSP System Toolbox
N-Sample Enable	DSP System Toolbox

# NCO


**Purpose** Generate real or complex sinusoidal signals

**Library** Signal Operations  
dsp\_sigops

## Description



The NCO block generates a multichannel real or complex sinusoidal signal, with independent frequency and phase in each output channel. The amplitude of the created signal is always 1. The block implements the algorithm as shown in the following diagram:



The implementation of a numerically controlled oscillator (NCO) has two distinct parts. First, a phase accumulator accumulates the phase increment and adds in the phase offset. In this stage, an optional internal dither signal can also be added. The NCO output is then calculated by quantizing the results of the phase accumulator section and using them to select values from a lookup table.

Given a desired output frequency  $F_0$ , calculate the value of the **Phase increment** block parameter with

$$\text{phase increment} = \left( \frac{F_0 \cdot 2^N}{F_s} \right)$$

where  $N$  is the accumulator word length and

$$F_s = \frac{1}{T_s} = \frac{1}{\text{sample time}}$$

The frequency resolution of an NCO is defined by

$$\Delta f = \frac{1}{T_s \cdot 2^N} \text{ Hz}$$

Given a desired phase offset (in radians), calculate the **Phase offset** block parameter with

$$\text{phase offset} = \frac{2^N \cdot \text{desired phase offset}}{2\pi}$$

The spurious free dynamic range (SFDR) is estimated as follows for a lookup table with  $2^P$  entries, where  $P$  is the number of quantized accumulator bits:

$$SFDR = (6P) \text{ dB} \quad \text{without dither}$$

$$SFDR = (6P + 12) \text{ dB} \quad \text{with dither}$$

This block uses a quarter-wave lookup table technique that stores table values from 0 to  $\pi/2$ . The block calculates other values on demand using the accumulator data type, then casts them into the output data type. This can lead to quantization effects at the range limits of a given data type. For example, consider a case where you would expect the value of the sine wave to be  $-1$  at  $\pi$ . Because the lookup table value at that point must be calculated, the block might not yield exactly  $-1$ , depending on the precision of the accumulator and output data types.


The NCO block supports real inputs only. All outputs are real except for the output signal in Complex exponential mode.

To produce a multichannel output, specify a vector quantity for the **Phase increment** and **Phase offset** parameters. Both parameters must have the same length, which defines the number of output channels. Each element of each vector is applied to a different output channel.

## Fixed-Point Data Types

The following diagram shows the data types used within the NCO block.

I = Integer  
 A = Accumulator data type  
 D = Dither bits  
 Q = Quantized accumulator bits  
 P = Phase quantization data type  
 O = Output data type



- You can set the accumulator and output data types in the block dialog as discussed in “Dialog Box” on page 2-1113 below.

---

**Note** The lookup table for this block is constructed from double-precision floating-point values. Thus, the maximum amount of precision you can achieve in your output is 53 bits. Setting the word length of the **Output** data type to values greater than 53 bits does not improve the precision of your output.

---

- The phase increment and phase offset inputs must be integers or fixed-point data types with zero fraction length.
- You specify the number of quantized accumulator bits in the **Number of quantized accumulator bits** parameter.
- The phase quantization error word length is equal to the accumulator word length minus the number of quantized accumulator bits, and the fraction length is zero.

## Examples

The NCO block is used in the GSM Digital Down Converter product example. Open this example by typing `dspddc` at the MATLAB command line.

You can also try the following example. Design an NCO source with the following specifications:

- Desired output frequency  $F_0 = 510$  Hz
- Frequency resolution  $\Delta f = 0.05$  Hz
- Spurious free dynamic range  $SFDR \geq 90$  dB
- Sample period  $T_s = 1/8000$  s
- Desired phase offset  $\pi/2$

1

Calculate the number of required accumulator bits from the equation for frequency resolution:

$$\Delta f = \frac{1}{T_s \cdot 2^N} \text{ Hz}$$

$$0.05 = \frac{1}{\frac{1}{8000} \cdot 2^N} \text{ Hz}$$

$$N = 18$$

Note that  $N$  must be an integer value. The value of  $N$  is rounded up to the nearest integer; 18 accumulator bits are needed to accommodate the value of the frequency resolution.

**2**

Using this best value of  $N$ , calculate the frequency resolution that will be achieved by the NCO block:

$$\Delta f = \frac{1}{T_s \cdot 2^N} \text{ Hz}$$

$$\Delta f = \frac{1}{\frac{1}{8000} \cdot 2^{18}} \text{ Hz}$$

$$\Delta f = 0.0305$$

**3**

Calculate the number of quantized accumulator bits from the equation for spurious free dynamic range and the fact that for a lookup table with  $2^P$  entries,  $P$  is the number of quantized accumulator bits:

$$SFDR = (6P + 12) \text{ dB}$$

$$96 \text{ dB} = (6P + 12) \text{ dB}$$

$$P = 14$$

**4**

Select the number of dither bits. In general, a good choice for the number of dither bits is the accumulator word length minus the number of quantized accumulator bits; in this case 4.

**5**

Calculate the phase increment:

$$\text{phase increment} = \text{round}\left(\frac{F_0 \cdot 2^N}{F_s}\right)$$

$$\text{phase increment} = \text{round}\left(\frac{510 \cdot 2^{18}}{8000}\right)$$

$$\text{phase increment} = 16712$$

**6**

Calculate the phase offset:


$$\text{phase offset} = \frac{2^{\text{accumulator word length}} \cdot \text{desired phase offset}}{2\pi}$$

$$\text{phase offset} = \frac{2^{18} \cdot \frac{\pi}{2}}{2\pi}$$


$$\text{phase offset} = 65536$$

**7**

Type `ex_nco_example` at the MATLAB command line to open the following model:




The NCO block in the model is populated with the specifications and quantities you just calculated. The output word length and fraction length depend on the constraints of your hardware; this example uses a word length of 16 and a fraction length of 14. You can verify that the specifications of this problem have been met by looking at the **NCO Characterization** pane of the NCO block.



Experiment with the model to observe the effects on the output shown on the Spectrum Scope. For example, try turning dithering on and off, and try changing the number of dither bits.

## Dialog Box

The **Main** pane of the NCO dialog appears as follows.



### Phase increment source

Choose how you specify the phase increment. The phase increment can come from an input port or from the dialog.

- If you select **Input port**, the inc port appears on the block icon.

- If you select **Specify via dialog**, the **Phase increment** parameter appears.

## **Phase increment**

Specify the phase increment. Only integer data types, including fixed-point data types with zero fraction length, are allowed. The dimensions of the phase increment are dictated by those of the phase offset:

- When you specify the phase offset on the block dialog box, the phase increment must be a scalar or a vector with the same length as the phase offset. The block applies each element of the vector to a different channel, and therefore the vector length defines the number of output channels.
- When you specify the phase offset via an input port, the offset port treats each column of the input as an independent channel. The phase increment length must equal the number of columns in the input to the offset port.

This parameter is visible only if you set the **Phase increment source** parameter to **Specify via dialog**.

## **Phase offset source**

Choose how you specify the phase offset. The phase offset can come from an input port or from the dialog.

- If you select **Input port**, the offset port appears on the block icon.
- If you select **Specify via dialog**, the **Phase offset** parameter appears.

When you specify the phase offset via an input port, it can be a scalar, vector, or a full matrix. The block treats each column of the input to the offset port as an independent channel. The number of channels in the phase offset must match the number of channels in the data input. For each frame of the input, the block can apply different phase offsets to each sample and channel.

Only integer data types, including fixed-point data types with zero fraction length, are allowed.

**Phase offset**

Specify the phase offset. When you specify the phase offset using this parameter rather than via an input port, it must be a scalar or vector with the same length as the phase increment. Scalars are expanded to a vector with the same length as the phase increment. Each element of the phase offset vector is applied to a different channel of the input, and therefore the vector length defines the number of output channels. Only integer data types, including fixed-point data types with zero fraction length, are allowed.

This parameter is visible only if **Specify via dialog** is selected for the **Phase offset source** parameter.

**Add internal dither**

Select to add internal dithering to the NCO algorithm. Dithering is added using the PN Sequence Generator from the Communications System Toolbox™ product.

**Number of dither bits**

Specify the number of dither bits.

This parameter is visible only if **Add internal dither** is selected.

**Quantize phase**

Select to enable quantization of the accumulated phase.

**Number of quantized accumulator bits**

Specify the number of quantized accumulator bits. This determines the number of entries in the lookup table. The number of quantized accumulator bits must be less than the accumulator word length.

This parameter is visible only if **Quantize phase** is selected.

**Show phase quantization error port**

Select to output the phase quantization error. When you select this, the Qerr port appears on the block icon.

This parameter is visible only if **Quantize phase** is selected.

### **Output signal**

Choose whether the block should output a **Sine**, **Cosine**, **Complex exponential**, or **Sine and cosine** signals. If you select **Sine** and **cosine**, the two signals output on different ports.

### **Sample time**

Specify the sample time in seconds when the block is acting as a source. When either the phase increment or phase offset come in via block input ports, the sample time is inherited and this parameter is not visible.


### **Samples per frame**

Specify the number of samples per frame. When the value of this parameter is 1, the block outputs a sample-based signal. When the value is greater than 1, the block outputs a frame-based signal of the specified size. In frame-based mode, the phase increment and phase offset can vary from channel to channel and from frame to frame, but they are constant along each channel in a given frame.

When the phase offset input port exists, it has the same frame status as any output port present. When the phase increment input port exists, it does not support frames.

This parameter is only visible if either **Phase increment source** or **Phase offset source** is set to **Specify via dialog**.

The **Data Types** pane of the NCO dialog appears as follows.



### Rounding mode

The rounding mode used for this block when inputs are fixed point is always Floor.

### Overflow mode

The overflow mode used for this block when inputs are fixed point is always Wrap.

### Accumulator

Specify the word length of the accumulator data type. The fraction length is always zero; this is an integer data type.

## Output

Specify the output data type.


- Choose `double` or `single` for a floating-point implementation.
- When you select `Binary point scaling`, you can enter the word length and the fraction length of the output, in bits.

---

**Note** The lookup table for this block is constructed from double-precision floating-point values. Thus, the maximum amount of precision you can achieve in your output is 53 bits. Setting the word length of the **Output** data type to values greater than 53 bits does not improve the precision of your output.

---

The **NCO Characterization** pane of the NCO dialog appears as follows.



The **NCO Characterization** pane does not have any parameters. Instead, it provides you with details on the NCO signal currently being implemented by the block:

- **Number of data points for lookup table** — The lookup table is implemented as a quarter-wave sine table. The number of lookup table data points is defined by

$$2^{\text{number of quantized accumulator bits}-2} + 1$$

- Quarter wave sine lookup table size — The quarter wave sine lookup table size is defined by

$$\frac{(\text{number of data points for lookup table}) \cdot (\text{output word length})}{8} \text{ bytes}$$

- Theoretical spurious free dynamic range — The spurious free dynamic range (SFDR) is calculated as follows for a lookup table with  $2^P$  entries:

$$SFDR = (6P) \text{ dB} \quad \text{without dither}$$

$$SFDR = (6P + 12) \text{ dB} \quad \text{with dither}$$

## Supported Data Types

Port	Supported Data Types
inc	<ul style="list-style-type: none"> <li>• Fixed point with zero fraction length</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>
offset	<ul style="list-style-type: none"> <li>• Fixed point with zero fraction length</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>
sin	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point</li> </ul>
Qerr	<ul style="list-style-type: none"> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>

**See Also**

PN Sequence  
Generator

Communications System Toolbox

Sine Wave

DSP System Toolbox


# Normalization

---

**Purpose** Perform vector normalization along rows, columns, or specified dimension

**Library** Math Functions / Math Operations  
dspmathops

## Description



The Normalization block independently normalizes each row, column, or vector of the specified dimension of the input. The block accepts both fixed- and floating-point signals in the squared 2-norm mode, but only floating-point signals in the 2-norm mode. The output always has the same dimensions as the input.

This block treats an arbitrarily dimensioned input  $U$  as a collection of vectors oriented along the specified dimension. The block normalizes these vectors by either their norm or the square of their norm.

For example, consider a 3-dimensional input  $U(i,j,k)$  and assume that you want to normalize along the second dimension. First, define the 2-dimensional intermediate quantity  $V(i,k)$  such that each element of  $V$  is the norm of one of the vectors in  $U$ :

$$V(i,k) = \left( \sum_{j=1}^J U^2(i,j,k) \right)^{1/2}$$

Given  $V$ , the output of the block  $Y(i,j,k)$  in 2-norm mode is

$$Y(i,j,k) = \frac{U(i,j,k)}{V(i,k) + b}$$


In squared 2-norm mode, the block output is

$$Y(i,j,k) = \frac{U(i,j,k)}{V(i,k)^2 + b}$$

The normalization bias,  $b$ , is typically chosen to be a small positive constant (for example, 1e-10) that prevents potential division by zero.

## Fixed-Point Data Types

The following diagram shows the data types used within the Normalization block for fixed-point signals (squared 2-norm mode only).



The output of the multiplier is in the product output data type when the input is real. When the input is complex, the result of the multiplication is in the accumulator data type. For details on the complex multiplication performed, see “Multiplication Data Types”. You can set the accumulator, product output, and output data types in the block dialog as discussed in “Dialog Box” on page 2-1123.


## Examples

See “Zero Algorithmic Delay” in the *DSP System Toolbox User’s Guide* for an example.

## Dialog Box

The **Main** pane of the Normalization dialog appears as follows.

# Normalization



## Norm

Specify the type of normalization to perform, 2-norm or Squared 2-norm. 2-norm mode supports floating-point signals only. Squared 2-norm supports both fixed-point and floating-point signals.

## Normalization bias

Specify the real value  $b$  to be added in the denominator to avoid division by zero. Tunable.

**Normalize over**

Specify whether to normalize along rows, columns, or the dimension specified in the **Dimension** parameter.

**Dimension**

Specify the one-based value of the dimension over which to normalize. The value of this parameter cannot exceed the number of dimensions in the input signal. This parameter is only visible if **Specified dimension** is selected for the **Normalize over** parameter.

**Treat sample-based row input as a column**

Select to treat a sample-based row input as a column.


---

**Note** This check box will be removed in a future release. See “Sample-Based Row Vector Processing Changes” in the DSP System Toolbox Release Notes.

---

The **Data Types** pane of the Normalization dialog appears as follows.

# Normalization



---

**Note** The parameters on this pane are only applicable to fixed-point signals when the block is in squared 2-norm mode. See “Fixed-Point Data Types” on page 2-1123 for a diagram of how the product output, accumulator, and output data types are used in this case.

---

## **Rounding mode**

Select the rounding mode for fixed-point operations.


## **Overflow mode**

Select the overflow mode for fixed-point operations.

## **Product output data type**

Specify the product output data type. See “Fixed-Point Data Types” on page 2-1123 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as input`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## **Accumulator data type**

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-1123 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Same as product output`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

# Normalization


---

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-1123 for illustrations depicting the use of the output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as product output`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

## Minimum

Specify the minimum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Maximum

Specify the maximum value that the block should output. The default value is [] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

### Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

### See Also

Array-Vector Multiply	DSP System Toolbox
Reciprocal Condition	DSP System Toolbox
norm	MATLAB

# Nyquist Filter

---

**Purpose** Design Nyquist filter

**Library** Filtering / Filter Designs  
dspfdesign

**Description** This block brings the filter design capabilities of the `filterbuilder` function to the Simulink environment.



**Dialog Box** See “Nyquist Filter Design Dialog Box — Main Pane” on page 7-750 for more information about the parameters of this block. The **Data Types** and **Code Generation** panes are not available for blocks in the DSP System Toolbox Filter Designs library.

Parameters of this block that do not change filter order or structure are tunable.

# Nyquist Filter

Function Block Parameters: Nyquist Filter

Nyquist Filter  
Design a Nyquist filter.

[View Filter Response](#)

Filter specifications

Band:

Impulse response:

Filter order mode:

Filter Type:

Frequency specifications

Frequency units:  Input Fs:

Transition width:

Magnitude specifications

Magnitude units:

Astop:

Algorithm

Design method:

Filter Implementation

Structure:

Use basic elements to enable filter customization

Input processing:

Use symbolic names for coefficients

# Nyquist Filter

---

## View filter response

This button opens the Filter Visualization Tool (fvtool) from the Signal Processing Toolbox product. You can use the tool to display:

- Magnitude response, phase response, and group delay in the frequency domain.
- Impulse response and step response in the time domain.
- Pole-zero information.

The tool also helps you evaluate filter performance by providing information about filter order, stability, and phase linearity. For more information on FVTool, see the Signal Processing Toolbox documentation.

## Filter Specifications

In this group, you specify your filter format, such as the impulse response and the filter order.

### Band

Specifies the location of the center of the transition region between the passband and the stopband. The center of the transition region,  $F_c$ , is calculated using the value for **Band**:

$$F_c = F_s / (2 \cdot \mathbf{Band}).$$

The default value, 2, corresponds to a halfband filter.

### Impulse response

Select either FIR or IIR from the drop-down list. FIR is the default. When you choose an impulse response, the design methods and structures you can use to implement your filter change accordingly. These options are both available only when **Band** is 2. For values of **Band** greater than 2, only FIR designs are supported.

---

**Note** The design methods and structures for FIR filters are not the same as the methods and structures for IIR filters.

---

## Filter order mode

Select either **Minimum** (the default) or **Specify** from the drop-down list. Selecting **Specify** enables the **Order** option (see the following sections) so you can enter the filter order.

## Filter type

Select **Single-rate**, **Decimator**, **Interpolator**, or **Sample-rate converter**. Your choice determines the type of filter as well as the design methods and structures that are available to implement your filter. By default, the block specifies a single-rate filter.

- Selecting **Decimator** or **Interpolator** activates the **Decimation Factor** or the **Interpolation Factor** options respectively.
- Selecting **Sample-rate converter** activates both factors.

## Order

Enter the filter order. This option is enabled only if **Specify** was selected for **Filter order mode**.

## Decimation Factor

Enter the decimation factor. This option is enabled only if the **Filter type** is set to **Decimator** or **Sample-rate converter**. The default value is 2.

## Interpolation Factor

Enter the interpolation factor. This option is enabled only if the **Filter type** is set to **Interpolator** or **Sample-rate converter**. The default value is 2.

## Frequency Specifications

The parameters in this group allow you to specify your filter response curve.

# Nyquist Filter

---

## Frequency constraints

Select the filter features that the block uses to define the frequency response characteristics.

## Frequency units

Use this parameter to specify whether your frequency settings are normalized or in absolute frequency. Select **Normalized (0 1)** to enter frequencies in normalized form. This behavior is the default. To enter frequencies in absolute values, select one of the frequency units from the drop-down list—Hz, kHz, MHz, or GHz. Selecting one of the unit options enables the **Input Fs** parameter.

## Input Fs

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter input. When you provide an input sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is available when you select one of the frequency options from the **Frequency units** list.

## Transition width

Specify the width of the transition between the end of the passband and the edge of the stopband. Specify the value in normalized frequency units or the absolute units you select in **Frequency units**.

## Magnitude Specifications

Parameters in this group specify the filter response in the passbands and stopbands.

## Magnitude units

Specify the units for any parameter you provide in magnitude specifications. From the drop-down list, select one of the following options:

- **Linear** — Specify the magnitude in linear units.
- **dB** — Specify the magnitude in decibels (default)
- **Squared** — Specify the magnitude in squared units.

**Astop**

Enter the filter attenuation in the stopband in the units you choose for **Magnitude units**, either linear or decibels.

# Nyquist Filter

---

## Algorithm

The parameters in this group allow you to specify the design method and structure of your filter.

## Design Method

Lists the design methods available for the frequency and magnitude specifications you entered. When you change the specifications for a filter, such as changing the impulse response, the methods available to design filters changes as well. The default IIR design method is Butterworth, and the default FIR method is Kaiser window.

## Scale SOS filter coefficients to reduce chance of overflow

Selecting this parameter directs the design to scale the filter coefficients to reduce the chances that the inputs or calculations in the filter overflow and exceed the representable range of the filter. Clearing this option removes the scaling. This parameter applies only to IIR filters.

## Design Options

The options for each design are specific for each design method. This section does not present all of the available options for all designs and design methods. There are many more that you encounter as you select different design methods and filter specifications. The following options represent some of the most common ones available.

## Density factor

Density factor controls the density of the frequency grid over which the design method optimization evaluates your filter response function. The number of equally spaced points in the grid is the value you enter for **Density factor** times (filter order + 1).

Increasing the value creates a filter that more closely approximates an ideal equiripple filter but increases the time required to design the filter. The default value of

20 represents a reasonable trade between the accurate approximation to the ideal filter and the time to design the filter.

## Minimum order

When you select this parameter, the design method determines and design the minimum order filter to meet your specifications. Some filters do not provide this parameter. Select Any, Even, or Odd from the drop-down list to direct the design to be any minimum order, or minimum even order, or minimum odd order.

## Stopband Shape

Stopband shape lets you specify how the stopband changes with increasing frequency. Choose one of the following options:

- **Flat** — Specifies that the stopband is flat. The attenuation does not change as the frequency increases.
- **Linear** — Specifies that the stopband attenuation changes linearly as the frequency increases. Change the slope of the stopband by setting **Stopband decay**.

## Stopband Decay

When you set Stopband shape, Stopband decay specifies the amount of decay applied to the stopband. the following conditions apply to Stopband decay based on the value of Stopband Shape:

- When you set **Stopband shape** to **Flat**, **Stopband decay** has no affect on the stopband.
- When you set **Stopband shape** to **Linear**, enter the slope of the stopband in units of dB/rad/s. The block applies that slope to the stopband.
- When you set **Stopband shape** to  $1/f$ , enter a value for the exponent  $n$  in the relation  $(1/f)^n$  to define the stopband decay. The block applies the  $(1/f)^n$  relation to

# Nyquist Filter

---

the stopband to result in an exponentially decreasing stopband attenuation.

## Filter Implementation

### Structure

For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter.

### Use basic elements to enable filter customization

Select this check box to implement the filter as a subsystem of basic Simulink blocks. Clear the check box to implement the filter as a high-level subsystem. By default, this check box is cleared.

The high-level implementation provides better compatibility across various filter structures, especially filters that would contain algebraic loops when constructed using basic elements. On the other hand, using basic elements enables the following optimization parameters:

- **Optimize for zero gains** — Terminate chains that contain Gain blocks with a gain of zero.
- **Optimize for unit gains** — Remove Gain blocks that scale by a factor of one.
- **Optimize for delay chains** — Substitute delay chains made up of  $n$  unit delays with a single delay by  $n$ .
- **Optimize for negative gains** — Use subtraction in Sum blocks instead of negative gains in Gain blocks.

### Input processing

Specify how the block should process the input. The available options may vary depending on the settings of the **Filter Structure** and **Use basic elements for filter customization** parameters. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The **Inherited** (this choice will be removed see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

### Rate options

When the **Filter type** parameter specifies a multirate filter, select the rate processing rule for the block from following options:

- **Enforce single-rate processing** — When you select this option, the block maintains the sample rate of the input.
- **Allow multirate processing** — When you select this option, the block adjusts the rate at the output to accommodate an increased or reduced number of samples. To select this option, you must set the **Input processing** parameter to **Elements as channels (sample based)**.

### Use symbolic names for coefficients

Select this check box to enable the specification of coefficients using MATLAB variables. The available coefficient names differ depending on the filter structure. Using symbolic names allows tuning of filter coefficients in generated code. By default, this check box is cleared.

# Nyquist Filter

---


## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

**Purpose** Design octave filter

**Library** Filtering / Filter Designs  
dspfdesign


**Description** This block brings the filter design capabilities of the `filterbuilder` function to the Simulink environment.



**Dialog Box** See “Octave Filter Design Dialog Box — Main Pane” on page 7-758 for more information about the parameters of this block. The **Data Types** and **Code Generation** panes are not available for blocks in the DSP System Toolbox Filter Designs library.

Parameters of this block that do not change filter order or structure are tunable.

# Octave Filter



## View filter response

This button opens the Filter Visualization Tool (`fvtool`) from the Signal Processing Toolbox product. You can use the tool to display:

- Magnitude response, phase response, and group delay in the frequency domain.
- Impulse response and step response in the time domain.
- Pole-zero information.

The tool also helps you evaluate filter performance by providing information about filter order, stability, and phase linearity. For more information on FVTool, see the Signal Processing Toolbox documentation.

## Filter Specifications

### Order

Specify filter order. Possible values are: 4, 6, 8, 10.

### Bands per octave

Specify the number of bands per octave. Possible values are: 1, 3, 6, 12, 24.

### Frequency units

Specify frequency units as Hz or kHz.

### Input Fs

Specify the input sampling frequency in the frequency units specified previously.

### Center Frequency

Select from the drop-down list of available center frequency values.

## Algorithm

### Design Method

Butterworth is the design method used for this type of filter.

### Scale SOS filter coefficients to reduce chance of overflow

Select the check box to scale the filter coefficients.

## Filter Implementation

### Structure

Specify filter structure. Choose from:

- Direct-form I SOS
- Direct-form II SOS
- Direct-form I transposed SOS
- Direct-form II transposed SOS

### Use basic elements to enable filter customization

Select this check box to implement the filter as a subsystem of basic Simulink blocks. Clear the check box to implement the filter as a high-level subsystem. By default, this check box is cleared.

The high-level implementation provides better compatibility across various filter structures, especially filters that would contain algebraic loops when constructed using basic elements. On the other hand, using basic elements enables the following optimization parameters:

- **Optimize for zero gains** — Terminate chains that contain Gain blocks with a gain of zero.
- **Optimize for unit gains** — Remove Gain blocks that scale by a factor of one.
- **Optimize for delay chains** — Substitute delay chains made up of  $n$  unit delays with a single delay by  $n$ .
- **Optimize for negative gains** — Use subtraction in Sum blocks instead of negative gains in Gain blocks.

### Optimize for unit-scale values

Select this check box to scale unit gains between sections in SOS filters. This parameter is available only for SOS filters.

## Input processing

Specify how the block should process the input. The available options may vary depending on the settings of the **Filter Structure** and **Use basic elements for filter customization** parameters. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The Inherited (this choice will be removed see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Rate options

When the **Filter type** parameter specifies a multirate filter, select the rate processing rule for the block from following options:

- **Enforce single-rate processing** — When you select this option, the block maintains the sample rate of the input.
- **Allow multirate processing** — When you select this option, the block adjusts the rate at the output to accommodate an increased or reduced number of samples. To select this option, you must set the **Input processing** parameter to **Elements as channels (sample based)**.

## Use symbolic names for coefficients

Select this check box to enable the specification of coefficients using MATLAB variables. The available coefficient names differ depending on the filter structure. Using symbolic names allows

# Octave Filter

---

tuning of filter coefficients in generated code. By default, this check box is cleared.


## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

**Purpose** Truncate vectors by removing or keeping beginning or ending values

**Library** Signal Operations  
dsp\_sigops

### Description



The Offset block removes or keeps values from the beginning or end of the input vectors. You specify the length of the output vectors using the **Output port length** parameter. The inputs to the In ports (In1, In2, ...) can be scalars or vectors, but they must be the same size and data type. The offset values are the inputs to the O ports (O1, O2, ...); they must be scalar values with the same data type. These offset values should be integer values because they determine the number of values the block discards or retains from each input vector. The block rounds any offset value that is a noninteger value to the nearest integer value. There is one output port for each pair of In and O ports.


Use the **Mode** parameter to determine which values the block discards or retains from the input vector. To discard the initial values of the vector, select **Remove beginning samples**. To discard the final values of the vector, select **Remove ending samples**. To retain the initial values of the vector, select **Keep beginning samples**. To retain the final values of a vector, select **Keep ending samples**.

Use the **Number of input data-offset pairs** parameter to specify the number of inputs to the block. The number of input ports is twice the scalar value you enter. For example, if you enter 3, ports In1, O1, In2, O2, In3, and O3 appear on the block.

The block uses the **Output port length** parameter to determine the length of the output vectors. If you select **Same as input**, the block outputs vectors that are the same length as the input to the In ports. If you select **User-defined**, the **Output length** parameter appears. Enter a scalar that represents the desired length of the output vectors. If your desired output length is greater than the number of values you extracted from your input vector, the block zero-pads the end of the vector to reach the length you specified.

# Offset

Use the **Action for out of range offset value** parameter to determine how the block behaves when an offset value is not in the range  $0 \leq \text{offset value} \leq N$ , where  $N$  is the input vector length. Select **Clip** if you want any offset values less than 0 to be set to 0 and any offset values greater than  $N$  to be set to  $N$ . Select **Clip and warn** if you want to be warned when any offset values less than 0 are set to 0 and any offset values greater than  $N$  are set to  $N$ . Select **Error** if you want the simulation to stop and display an error when the offset values are out of range.



## Dialog Box

### Mode

Use this parameter to determine which values the block discards or retains from the input vector. Your choices are **Remove beginning samples**, **Remove ending samples**, **Keep beginning samples**, and **Keep ending samples**.

### Number of input data-offset pairs

Specify the number of inputs to the block. The number of input ports is twice the scalar value you enter.

## **Output port length**

Use this parameter to specify the length of the output vectors. If you select **Same as input**, the output vectors are the same length as the input vectors. If you select **User-defined**, you can enter the desired length of the output vectors.

## **Output length**

Enter a scalar that represents the desired length of the output vectors. This parameter is visible if, for the **Output port length** parameter, you select **User-defined**.

## **Action for out of range offset value**

Use this parameter to determine how the block behaves when an offset value is not in the range such that  $0 \leq \text{offset value} \leq N$ , where  $N$  is the input vector length. When you want any offset values less than 0 to be set to 0 and any offset values greater than  $N$  to be set to  $N$ , select **Clip**. When you want to be warned when any offset values less than 0 are set to 0 and any offset values greater than  $N$  are set to  $N$ , select **Clip and warn**. When you want the simulation to stop and display an error when the offset values are out of range, select **Error**.

# Offset

---

## Supported Data Types

Port	Supported Data Types
In	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
O	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Out	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>

**Purpose** Implement overlap-add method of frequency-domain filtering

**Library** Filtering / Filter Implementations  
dsparch4


## Description



The Overlap-Add FFT Filter block uses an FFT to implement the *overlap-add method*, a technique that combines successive frequency-domain filtered sections of an input sequence.

The block accepts vector or matrix inputs, and treats each column of the input as an individual channel. The block unbuffers the input data into row vectors such that the length of the output vector is equal to the number of channels in the input. The data output rate of the block is  $M$  times faster than its data input rate, where  $M$  is the length of the columns in the input (frame-size).

The block breaks the scalar input sequence  $u$ , of length  $nu$ , into length- $L$  nonoverlapping data sections,



which it linearly convolves with the filter's FIR coefficients,

$$H(z) = B(z) = b_1 + b_2z^{-1} + \dots + b_{n+1}z^{-n}$$

The numerator coefficients for  $H(z)$  are specified as a vector by the **FIR coefficients** parameter. The coefficient vector,  $\mathbf{b} = [b(1) \ b(2) \ \dots \ b(n+1)]$ , can be generated by one of the filter design functions in the Signal Processing Toolbox product, such as `fir1`. All filter states are internally initialized to zero.

When either the filter coefficients or the inputs to the block are complex, the **Output** parameter should be set to `Complex`. Otherwise, the default **Output** setting, `Real`, instructs the block to take only the real part of the solution.

The block's overlap-add operation is equivalent to


# Overlap-Add FFT Filter

---

```
y = ifft(fft(u(i:i+L-1),nfft) .* fft(b,nfft))
```

where you specify **nfft** in the **FFT size** parameter as a power-of-two value greater (typically *much* greater) than  $n+1$ . Values for **FFT size** that are not powers of two are rounded upwards to the nearest power-of-two value to obtain **nfft**.

The block overlaps successive output sections by  $n$  points and sums them.



The first  $L$  samples of each summation are output in sequence. The block chooses the parameter  $L$  based on the filter order and the FFT size.

$$L = \text{nfft} - n$$

## Latency

In *single-tasking* operation, the Overlap-Add FFT Filter block has a latency of  $\text{nfft} - n + 1$  samples. The first  $\text{nfft} - n + 1$  consecutive outputs from the block are zero; the first filtered input value appears at the output as sample  $\text{nfft} - n + 2$ .


In *multitasking* operation, the Overlap-Add FFT Filter block has a latency of  $2 * (\text{nfft} - n + 1)$  samples. The first  $2 * (\text{nfft} - n + 1)$  consecutive outputs from the block are zero; the first filtered input value appears at the output as sample  $2 * (\text{nfft} - n) + 3$ .

---

**Note** For more information on latency and the Simulink software tasking modes, see “Excess Algorithmic Delay (Tasking Latency)” and “Scheduling” in the Simulink Coder documentation.

---

# Overlap-Add FFT Filter



## Dialog Box

### FFT size

The size of the FFT, which should be a power-of-two value greater than the length of the specified FIR filter.

### FIR coefficients

The filter numerator coefficients.

# Overlap-Add FFT Filter

---

## Output

The complexity of the output; Real or Complex. When the input signal or the filter coefficients are complex, this should be set to Complex.

## Treat Mx1 and unoriented sample-based signals as

Specify how the block treats sample-based  $M$ -by-1 column vectors and unoriented sample-based vectors of length  $M$ . You can select one of the following options:

- One channel — When you select this option, the block treats  $M$ -by-1 and unoriented sample-based inputs as a column vector (one channel).
- M channels (this choice will be removed see release notes) — When you select this option, the block treats  $M$ -by-1 and unoriented sample-based inputs as a 1-by- $M$  row vector.

---

**Note** This parameter will be removed in a future release. At that time, the block will always treat  $M$ -by-1 and unoriented vectors as a single channel.

---

## References

Oppenheim, A. V. and R. W. Schaffer. *Discrete-Time Signal Processing*. Englewood Cliffs, NJ: Prentice Hall, 1989.

Proakis, J. and D. Manolakis. *Digital Signal Processing*. 3rd ed. Englewood Cliffs, NJ: Prentice-Hall, 1996.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point

## See Also

Overlap-Save FFT Filter

DSP System Toolbox product

**Purpose** Implement overlap-save method of frequency-domain filtering

**Library** Filtering / Filter Implementations  
dsparch4

## Description



The Overlap-Save FFT Filter block uses an FFT to implement the *overlap-save method*, a technique that combines successive frequency-domain filtered sections of an input sequence.

The block accepts vector or matrix inputs, and treats each column of the input as an individual channel. The block unbuffers the input data into row vectors such that the length of the output vector is equal to the number of channels in the input. The data output rate of the block is  $M$  times faster than its data input rate, where  $M$  is the length of the columns in the input (frame-size).

Overlapping sections of input  $u$  are circularly convolved with the FIR filter coefficients

$$H(z) = B(z) = b_1 + b_2z^{-1} + \dots + b_{n+1}z^{-n}$$

The numerator coefficients for  $H(z)$  are specified as a vector by the **FIR coefficients** parameter. The coefficient vector,  $\mathbf{b} = [b(1) \ b(2) \ \dots \ b(n+1)]$ , can be generated by one of the filter design functions in the Signal Processing Toolbox product, such as `fir1`. All filter states are internally initialized to zero.

When either the filter coefficients or the inputs to the block are complex, the **Output** parameter should be set to `Complex`. Otherwise, the default **Output** setting, `Real`, instructs the block to take only the real part of the solution.

The circular convolution of each section is computed by multiplying the FFTs of the input section and filter coefficients, and computing the inverse FFT of the product.

```
y = ifft(fft(u(i:i+(L-1))),nfft) .* fft(b,nfft)
```

# Overlap-Save FFT Filter

---

where you specify  $nfft$  in the **FFT size** parameter as a power of two value greater (typically *much* greater) than  $n+1$ . Values for **FFT size** that are not powers of two are rounded upwards to the nearest power-of-two value to obtain  $nfft$ .

The first  $n$  points of the circular convolution are invalid and are discarded. The Overlap-Save FFT Filter block outputs the remaining  $nfft - n$  points, which are equivalent to the linear convolution.

## Latency

In *single-tasking* operation, the Overlap-Save FFT Filter block has a latency of  $nfft - n + 1$  samples. The first  $nfft - n + 1$  consecutive outputs from the block are zero; the first filtered input value appears at the output as sample  $nfft - n + 2$ .


In *multitasking* operation, the Overlap-Save FFT Filter block has a latency of  $2 * (nfft - n + 1)$  samples. The first  $2 * (nfft - n + 1)$  consecutive outputs from the block are zero; the first filtered input value appears at the output as sample  $2 * (nfft - n) + 3$ .

---

**Note** For more information on latency and the Simulink environment tasking modes, see “Excess Algorithmic Delay (Tasking Latency)” and “Scheduling” in the Simulink Coder documentation.

---

# Overlap-Save FFT Filter



## Dialog Box

### FFT size

The size of the FFT, which should be a power of two value greater than the length of the specified FIR filter.

### FIR coefficients

The filter numerator coefficients.

# Overlap-Save FFT Filter

---

## Output

The complexity of the output; Real or Complex. When the input signal or the filter coefficients are complex, this should be set to Complex.

## Treat Mx1 and unoriented sample-based signals as

Specify how the block treats sample-based  $M$ -by-1 column vectors and unoriented sample-based vectors of length  $M$ . You can select one of the following options:

- One channel — When you select this option, the block treats  $M$ -by-1 and unoriented sample-based inputs as a column vector (one channel).
- M channels (this choice will be removed see release notes) — When you select this option, the block treats  $M$ -by-1 and unoriented sample-based inputs as a 1-by- $M$  row vector.

---

**Note** This parameter will be removed in a future release. At that time, the block will always treat  $M$ -by-1 and unoriented vectors as a single channel.

---

## References

Oppenheim, A. V. and R. W. Schaffer. *Discrete-Time Signal Processing*. Englewood Cliffs, NJ: Prentice Hall, 1989.

Proakis, J. and D. Manolakis. *Digital Signal Processing*. 3rd ed. Englewood Cliffs, NJ: Prentice-Hall, 1996.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point

## See Also

Overlap-Add FFT Filter      DSP System Toolbox



## Purpose

Overwrite submatrix or subdiagonal of input


## Library

- Math Functions / Matrices and Linear Algebra / Matrix Operations  
dspmtx3
- Signal Management / Indexing  
dspindex

## Description



The Overwrite Values block overwrites a contiguous submatrix or subdiagonal of an input matrix. You can provide the overwriting values by typing them in a block parameter, or through an additional input port, which is useful for providing overwriting values that change at each time step.



The block accepts scalars, vectors and matrices. The output always has the same size as the original input signal, not necessarily the same size as the signal containing the overwriting values. The input(s) and output of this block must have the same data type.

## Specifying the Overwriting Values

The **Source of overwriting value(s)** parameter determines how you must provide the overwriting values, and has the following settings.

- **Specify via dialog** — You must provide the overwriting value(s) in the **Overwrite with** parameter. The block uses the same overwriting values to overwrite the specified portion of the input at each time step. To learn how to specify valid overwriting values, see “Valid Overwriting Values” on page 2-1160.
- **Second input port** — You must provide overwriting values through a second block input port, *V*. Use this setting to provide different

# Overwrite Values




overwriting values at each time step. The output inherits its size and rate from the input signal, *not* the overwriting values.

The rate at which you provide the overwriting values through input port V must match the rate at which the block receives each input matrix at input port A. In other words, the input signals must have the same Simulink sample time.






## Valid Overwriting Values

The overwriting values can be a single constant, vector, or matrix, depending on the portion of the input you are overwriting, regardless of whether you provide the overwriting values through an input port or by providing them in the **Overwrite with** parameter.

### Valid Overwriting Values

Portion of Input to Overwrite	Valid Overwriting Values	Example
A single element in the input 	Any constant value, $v$	$v = 9$ 
A length- $k$ portion of the diagonal 	Any length- $k$ column or row vector, $v$	$k = 3 \quad v = [2 \ 4 \ 6]$ or $\begin{bmatrix} 2 \\ 4 \\ 6 \end{bmatrix}$ 


## Valid Overwriting Values (Continued)

Portion of Input to Overwrite	Valid Overwriting Values	Example
<p>A length-<math>k</math> portion of a row</p> 	Any length- $k$ row vector, $v$	$k = 3 \quad v = [2 \ 4 \ 6]$ 
<p>A length-<math>k</math> portion of a column</p> 	Any length- $k$ column vector, $v$	$k = 2 \quad v = \begin{bmatrix} 4 \\ 6 \end{bmatrix}$ 
<p>An <math>m</math>-by-<math>n</math> submatrix</p> 	Any $m$ -by- $n$ matrix, $v$	$m = 2 \quad n = 3 \quad v = \begin{bmatrix} 4 & 5 & 6 \\ 7 & 8 & 9 \end{bmatrix}$ 

This block supports Simulink virtual buses.

# Overwrite Values

---



## Dialog Box

---

**Note** Only some of the following parameters are visible in the dialog box at any one time.

---

**Overwrite**

Determines whether to overwrite a specified submatrix or a specified portion of the diagonal.

**Source of overwriting value(s)**

Determines where you must provide the overwriting values: either through an input port, or by providing them in the **Overwrite with** parameter. For more information, see “Specifying the Overwriting Values” on page 2-1159.

**Overwrite with**

The value(s) with which to overwrite the specified portion of the input matrix. Enabled only when **Source of overwriting value(s)** is set to `Specify via dialog`. To learn how to specify valid overwriting values, see “Valid Overwriting Values” on page 2-1160.

**Row span**

The range of input rows to be overwritten. Options are `All rows`, `One row`, or `Range of rows`. For descriptions of these options, see “Dialog Box” on page 2-1162.

**Row/Starting row**

The input row that is the first row of the submatrix that the block overwrites. For a description of the options for the **Row** and **Starting row** parameters, see `Settings for Row, Column, Starting Row, and Starting Column Parameters` on page 2-1168. **Row** is enabled when **Row span** is set to `One row`, and **Starting row** when **Row span** is set to `Range of rows`.

**Row index/Starting row index**

Index of the input row that is the first row of the submatrix that the block overwrites. See how to use these parameters in `Settings for Row, Column, Starting Row, and Starting Column Parameters` on page 2-1168. **Row index** is enabled when **Row** is set to `Index`, and **Starting row index** when **Starting row** is set to `Index`.

**Row offset/Starting row offset**

The offset of the input row that is the first row of the submatrix that the block overwrites. See how to use these parameters in

# Overwrite Values

---

Settings for Row, Column, Starting Row, and Starting Column Parameters on page 2-1168. **Row offset** is enabled when **Row** is set to `Offset from middle` or `Offset from last`, and **Starting row offset** is enabled when **Starting row** is set to `Offset from middle` or `Offset from last`.

## Ending row

The input row that is the last row of the submatrix that the block overwrites. For a description of this parameter's options, see Settings for Ending Row and Ending Column Parameters on page 2-1169. This parameter is enabled when **Row span** is set to `Range of rows`, and **Starting row** is set to any option but `Last`.

## Ending row index

Index of the input row that is the last row of the submatrix that the block overwrites. See how to use this parameter in Settings for Ending Row and Ending Column Parameters on page 2-1169. Enabled when **Ending row** is set to `Index`.

## Ending row offset

The offset of the input row that is the last row of the submatrix that the block overwrites. See how to use this parameter in Settings for Ending Row and Ending Column Parameters on page 2-1169. Enabled when **Ending row** is set to `Offset from middle` or `Offset from last`.

## Column span

The range of input columns to be overwritten. Options are `All columns`, `One column`, or `Range of columns`. For descriptions of the analogous row options, see "Dialog Box" on page 2-1162.

## Column/Starting column

The input column that is the first column of the submatrix that the block overwrites. For a description of the options for the **Column** and **Starting column** parameters, see Settings for Row, Column, Starting Row, and Starting Column Parameters on page 2-1168. **Column** is enabled when **Column span** is set to `One column`, and **Starting column** when **Column span** is set to `Range of columns`.

## **Column index/Starting column index**

Index of the input column that is the first column of the submatrix that the block overwrites. See how to use these parameters in Settings for Row, Column, Starting Row, and Starting Column Parameters on page 2-1168. **Column index** is enabled when **Column** is set to Index, and **Starting column index** when **Starting column** is set to Index.

## **Column offset/Starting column offset**

The offset of the input column that is the first column of the submatrix that the block overwrites. See how to use these parameters in Settings for Row, Column, Starting Row, and Starting Column Parameters on page 2-1168. **Column offset** is enabled when **Column** is set to Offset from middle or Offset from last, and **Starting column offset** is enabled when **Starting column** is set to Offset from middle or Offset from last.

## **Ending column**

The input column that is the last column of the submatrix that the block overwrites. For a description of this parameter's options, see Settings for Ending Row and Ending Column Parameters on page 2-1169. This parameter is enabled when **Column span** is set to Range of columns, and **Starting column** is set to any option but Last.

## **Ending column index**

Index of the input column that is the last column of the submatrix that the block overwrites. See how to use this parameter in Settings for Ending Row and Ending Column Parameters on page 2-1169. This parameter is enabled when **Ending column** is set to Index.

## **Ending column offset**

The offset of the input column that is the last column of the submatrix that the block overwrites. See how to use this parameter in Settings for Ending Row and Ending Column Parameters on page 2-1169. This parameter is enabled when

# Overwrite Values

---

**Ending column** is set to `Offset from middle` or `Offset from last`.

## Diagonal span

The range of diagonal elements to be overwritten. Options are `All elements`, `One element`, or `Range of elements`. For descriptions of these options, see “Overwriting a Subdiagonal” on page 2-1172.

## Element/Starting element

The input diagonal element that is the first element in the subdiagonal that the block overwrites. For a description of the options for the **Element** and **Starting element** parameters, see `Element and Starting Element Parameters` on page 2-1172.

**Element** is enabled when **Element span** is set to `One element`, and **Starting element** when **Element span** is set to `Range of elements`.

## Element index/Starting element index

Index of the input diagonal element that is the first element of the subdiagonal that the block overwrites. See how to use these parameters in `Element and Starting Element Parameters` on page 2-1172. **Element index** is enabled when **Element** is set to `Index`, and **Starting element index** when **Starting element** is set to `Index`.

## Element offset/Starting element offset

The offset of the input diagonal element that is the first element of the subdiagonal that the block overwrites. See how to use these parameters in `Element and Starting Element Parameters` on page 2-1172. **Element offset** is enabled when **Element** is set to `Offset from middle` or `Offset from last`, and **Starting element offset** is enabled when **Starting element** is set to `Offset from middle` or `Offset from last`.

## Ending element

The input diagonal element that is the last element of the subdiagonal that the block overwrites. For a description of this parameter’s options, see `Ending Element Parameters` on page 2-1173. This parameter is enabled when **Element span** is set to

Range of elements, and **Starting element** is set to any option but Last.

### Ending element index

Index of the input diagonal element that is the last element of the subdiagonal that the block overwrites. See how to use this parameter in Ending Element Parameters on page 2-1173. This parameter is enabled when **Ending element** is set to Index.

### Ending element offset

The offset of the input diagonal element that is the last element of the subdiagonal that the block overwrites. See how to use this parameter in Ending Element Parameters on page 2-1173. This parameter is enabled when **Ending element** is set to Offset from middle or Offset from last.

## Examples

### Overwriting a Submatrix

To overwrite a submatrix, follow these steps:

- 1 Set the **Overwrite** parameter to Submatrix.
- 2 Specify the overwriting values as described in “Specifying the Overwriting Values” on page 2-1159.
- 3 Specify which rows and columns of the input matrix are contained in the submatrix that you want to overwrite by setting the **Row span** parameter to one of the following options and the **Column span** to the analogous column-related options:
  - All rows — The submatrix contains all rows of the input matrix.
  - One row — The submatrix contains only one row of the input matrix, which you must specify in the **Row** parameter, as described in the following table.
  - Range of rows — The submatrix contains one or more rows of the input, which you must specify in the **Starting Row** and **Ending row** parameters, as described in the following tables.

# Overwrite Values

- 4 When you set **Row span** to One row or Range of rows, you need to further specify the row(s) contained in the submatrix by setting the **Row** or **Starting row** and **Ending row** parameters. Likewise, when you set **Column span** to One column or Range of columns, you must further specify the column(s) contained in the submatrix by setting the **Column** or **Starting column** and **Ending column** parameters. For descriptions of the settings for these parameters, see the following tables.

## Settings for Row, Column, Starting Row, and Starting Column Parameters

Settings for Specifying the Submatrix's First Row or Column	First Row of Submatrix (Only row for Row span = One row)	First Column of Submatrix (Only row for Row span = One row)
First	First row of the input	First column of the input
Index	Input row specified in the <b>Row index</b> parameter	Input column specified in the <b>Column index</b> parameter
Offset from last	Input row with the index $M - \text{rowOffset}$ where M is the number of input rows, and $\text{rowOffset}$ is the value of the <b>Row offset</b> or <b>Starting row offset</b> parameter	Input column with the index $N - \text{colOffset}$ where N is the number of input columns, and $\text{colOffset}$ is the value of the <b>Column offset</b> or <b>Starting column offset</b> parameter
Last	Last row of the input	Last column of the input

## Settings for Row, Column, Starting Row, and Starting Column Parameters (Continued)

<b>Settings for Specifying the Submatrix's First Row or Column</b>	<b>First Row of Submatrix (Only row for Row span = One row)</b>	<b>First Column of Submatrix (Only row for Row span = One row)</b>
Offset from middle	Input row with the index $\text{floor}(M/2 + 1 - \text{rowOffset})$ where M is the number of input rows, and rowOffset is the value of the <b>Row offset</b> or <b>Starting row offset</b> parameter	Input column with the index $\text{floor}(N/2 + 1 - \text{colOffset})$ where N is the number of input columns, and colOffset is the value of the <b>Column offset</b> or <b>Starting column offset</b> parameter
Middle	Input row with the index $\text{floor}(M/2 + 1)$ where M is the number of input rows	Input columns with the index $\text{floor}(N/2 + 1)$ where N is the number of input columns

## Settings for Ending Row and Ending Column Parameters

<b>Settings for Specifying the Submatrix's Last Row or Column</b>	<b>Last Row of Submatrix</b>	<b>Last Column of Submatrix</b>
Index	Input row specified in the <b>Ending row index</b> parameter	Input column specified in the <b>Ending column index</b> parameter
Offset from last	Input row with the index $M - \text{rowOffset}$ where M is the number of input	Input column with the index $N - \text{colOffset}$ where N is the number of input

# Overwrite Values

## Settings for Ending Row and Ending Column Parameters (Continued)


Settings for Specifying the Submatrix's Last Row or Column	Last Row of Submatrix	Last Column of Submatrix
	rows, and rowOffset is the value of the <b>Ending row offset</b> parameter	columns, and colOffset is the value of the <b>Ending column offset</b> parameter
Last	Last row of the input	Last column of the input
Offset from middle	Input row with the index $\text{floor}(M/2 + 1 - \text{rowOffset})$ where M is the number of input rows, and rowOffset is the value of the <b>Ending row offset</b> parameter	Input column with the index $\text{floor}(N/2 + 1 - \text{colOffset})$ where N is the number of input columns, and colOffset is the value of the <b>Ending column offset</b> parameter
Middle	Input row with the index $\text{floor}(M/2 + 1)$ where M is the number of input rows	Input columns with the index $\text{floor}(N/2 + 1)$ where N is the number of input columns

For example, to overwrite the lower-right 2-by-3 submatrix of a 3-by-5 input matrix with all zeros, enter the following set of parameters:

- **Overwrite** = Submatrix
- **Source of overwriting value(s)** = Specify via dialog
- **Overwrite with** = 0
- **Row span** = Range of rows
- **Starting row** = Index
- **Starting row index** = 2
- **Ending row** = Last

- **Column span** = Range of columns
- **Starting column** = Offset from last
- **Starting column offset** = 2
- **Ending column** = Last

The following figure shows the block with the above settings overwriting a portion of a 3-by-5 input matrix.



There are often several possible parameter combinations that select the *same* submatrix from the input. For example, instead of specifying Last for **Ending column**, you could select the same submatrix by specifying

- **Ending column** = Index
- **Ending column index** = 5

# Overwrite Values

---

## Overwriting a Subdiagonal

To overwrite a subdiagonal, follow these steps:

- 1 Set the **Overwrite** parameter to **Diagonal**.
- 2 Specify the overwriting values as described in “Specifying the Overwriting Values” on page 2-1159.
- 3 Specify the subdiagonal that you want to overwrite by setting the **Diagonal span** parameter to one of the following options:
  - **All elements** — Overwrite the entire input diagonal.
  - **One element** — Overwrite one element in the diagonal, which you must specify in the **Element** parameter (described below).
  - **Range of elements** — Overwrite a portion of the input diagonal, which you must specify in the **Starting element** and **Ending element** parameters, as described in the following table.
- 4 When you set **Diagonal span** to **One element** or **Range of elements**, you need to further specify which diagonal element(s) to overwrite by setting the **Element** or **Starting element** and **Ending element** parameters. See the following tables.

### Element and Starting Element Parameters

Settings for Element and Starting Element Parameters	First Element in Subdiagonal (Only element when Diagonal span = One element)
First	Diagonal element in first row of the input
Index	$k$ th diagonal element, where $k$ is the value of the <b>Element index</b> or <b>Starting element index</b> parameter

## Element and Starting Element Parameters (Continued)

Settings for Element and Starting Element Parameters	First Element in Subdiagonal (Only element when Diagonal span = One element)
Offset from last	Diagonal element in the row with the index $M - \text{offset}$ where $M$ is the number of input rows, and $\text{offset}$ is the value of the <b>Element offset</b> or <b>Starting element offset</b> parameter
Last	Diagonal element in the last row of the input
Offset from middle	Diagonal element in the input row with the index $\text{floor}(M/2 + 1 - \text{offset})$ where $M$ is the number of input rows, and $\text{offset}$ is the value of the <b>Element offset</b> or <b>Starting element offset</b> parameter
Middle	Diagonal element in the input row with the index $\text{floor}(M/2 + 1)$ where $M$ is the number of input rows

## Ending Element Parameters

Settings for Ending Element Parameter	Last Element in Subdiagonal
Index	$k$ th diagonal element, where $k$ is the value of the <b>Ending element index</b> parameter
Offset from last	Diagonal element in the row with the index $M - \text{offset}$ where $M$ is the number of input rows, and $\text{offset}$ is the value of the <b>Ending element offset</b> parameter
Last	Diagonal element in the last row of the input

# Overwrite Values

## Ending Element Parameters (Continued)

Settings for Ending Element Parameter	Last Element in Subdiagonal
Offset from middle	Diagonal element in the input row with the index $\text{floor}(M/2 + 1 - \text{offset})$ where M is the number of input rows, and <b>offset</b> is the value of the <b>Ending element offset</b> parameter
Middle	Diagonal element in the input row with the index $\text{floor}(M/2 + 1)$ where M is the number of input rows

## Supported Data Types

The input(s) and output of this block must have the same data type.

Port	Supported Data Types
A	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
V	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>

Port	Supported Data Types
	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
B	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

## See Also

Reshape	Simulink
Selector	Simulink
Submatrix	DSP System Toolbox
Variable Selector	DSP System Toolbox
reshape	MATLAB

# Pad

---

## Purpose

Pad or truncate specified dimension(s)

## Library

Signal Operations

dspsigops


## Description



The Pad block extends or crops the dimensions of the input by padding or truncating along its columns, rows, columns and rows, or any dimension(s) you specify. Truncation occurs when you specify output dimensions that are shorter than the corresponding input dimensions. If the input and output lengths are the same, the block is a pass-through.

You can enter the pad value in the block mask or via an input port. You can enter output sizes in the block mask, or have the block pad the specified dimensions until their length is the next highest power of two. The **Pad signal at** parameter controls whether the specified input dimensions are padded or truncated at their beginning, end, or both. For odd pad or truncation lengths, the extra pad value or truncation is applied to the end of the signal. When the block is in Specified dimensions mode, you can specify either the output size or the pad size.

You can have the block warn or error when an input signal is truncated using the **Action when truncation occurs** parameter.

**Dialog  
Box****Pad over**

Specify the dimensions over which to pad or truncate: Columns, Rows, Columns and rows, None, or Specified dimensions.

**Dimensions to pad**

Specify the one-based dimension(s) over which to pad or truncate. The value for this parameter can be a scalar or a vector. For example, specify 1 to pad columns. Specify [1 2] to pad columns and rows. Specify [1 3 5] to pad the first, third, and fifth dimensions.

This parameter is only visible when Specified dimensions is selected for the **Pad over** parameter.

## **Pad value source**

Choose how you specify the pad value. The pad value can come from an input port or from the dialog:

- If you select `Input port`, the `PVal` port appears on the block icon.
- If you select `Specify via dialog`, the **Pad value** parameter appears.

## **Pad value**

Specify the constant scalar value with which to pad the input. Tunable.

This parameter is only visible when `Specify via dialog` is selected for the **Pad value source** parameter.

## **Output column mode**

Choose how you specify the column length of the output:

- If you select `User-specified`, the **Column size** parameter appears.
- If you select `Next power of two`, the block pads the output columns until their length is the next highest power of two. If the column length is already a power of two, the columns are not padded.

This parameter is only visible when `Columns` or `Columns and rows` is selected for the **Pad over** parameter.

## **Column size**

Specify the column length of the output. If the specified column length is longer than the input column length, the columns are padded. If the specified column length is shorter than the input column length, the columns are truncated. This parameter is only visible when `User-specified` is selected for the **Output column mode** parameter.

## **Output row mode**

Choose how you specify the output row length of the output:

- If you select **User-specified**, the **Row size** parameter appears.
- If you select **Next power of two**, the block pads the output rows until their length is the next highest power of two. If the row length is already a power of two, the rows are not padded.

This parameter is only visible when **Rows** or **Columns** and **rows** is selected for the **Pad over** parameter.

#### **Row size**

Specify the row length of the output. If the specified row length is longer than the input row length, the rows are padded. If the specified row length is shorter than the input row length, the rows are truncated. This parameter is only visible when **User-specified** is selected for the **Output row mode** parameter.

#### **Specify**

Choose whether you want to control the output length of the specified dimensions by specifying the pad size or the output size.

This parameter is only visible when **Specified dimensions** is selected for the **Pad over** parameter.

#### **Pad size at beginning**

Specify how many values to add to the beginning of the input signal along the specified dimension(s). This parameter must be a scalar or a vector with the same number of elements as the **Dimensions to pad** parameter. Each element in the **Pad size at beginning** parameter gives the pad length for the beginning of the corresponding dimension in the **Dimensions to pad** parameter. Values of this parameter must be zero or a positive integer.

This parameter is only visible if **Pad size** is selected for the **Specify** parameter.

## **Pad size at end**

Specify how many values to add to the end of the input signal along the specified dimension(s). This parameter must be a scalar or a vector with the same number of elements as the **Dimensions to pad** parameter. Each element in the **Pad size at end** parameter gives the pad length for the end of the corresponding dimension in the **Dimensions to pad** parameter. Values of this parameter must be zero or a positive integer.

This parameter is only visible if `Pad size` is selected for the **Specify** parameter.

## **Output size mode**

Choose how you specify the output length of the specified dimensions:

- If you select `User-specified`, the **Output size** parameter appears.
- If you select `Next power of two`, the block pads the specified dimensions until their length is the next highest power of two. If the dimension length is already a power of two, no padding occurs in that dimension.

This parameter is only visible if `Output size` is selected for the **Specify** parameter.

## **Output size**

Specify the output length of the specified dimension(s). This parameter must be a scalar or a vector with the same number of elements as the **Dimensions to pad** parameter. Each element in the **Output size** vector gives the output length for the corresponding dimension in the **Dimensions to pad** vector. If the specified length is longer than the input length for a given dimension, that dimension is padded. If the specified length is shorter than the input length for a given dimension, that dimension is truncated.

This parameter is only visible if `Output size` is selected for the `Specify` parameter.

**Pad signal at**

Specify whether to pad or truncate the signal at the `Beginning`, `End`, or `Beginning and end` of the specified dimension(s). When you select `Beginning and end`, half the pad length is added to the beginning of the signal, and half is added to the end of the signal. For an odd pad length, the extra value is added to the end of the signal. This also applies to truncation. In this mode, an equal number of values are truncated from the beginning and the end of the signal. In the case of an odd truncation length, the extra value is removed from the end of the signal.

**Action when truncation occurs**

Choose `None` when you do not want to be notified that the input is truncated. Select `Warning` to display a warning when the input is truncated. Choose `Error` when to display an error and terminate the simulation when the input is truncated.

**Supported Data Types**

Port	Supported Data Types
Input	<ul style="list-style-type: none"> <li>• Double-precision floating-point</li> <li>• Single-precision floating-point</li> <li>• Fixed point (signed and unsigned)</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>
Output	<ul style="list-style-type: none"> <li>• Double-precision floating-point</li> <li>• Single-precision floating-point</li> <li>• Fixed point (signed and unsigned)</li> <li>• Boolean</li> </ul>


## See Also

Port	Supported Data Types
Concatenate	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit signed integers</li></ul> Simulink
Repeat	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit unsigned integers</li></ul> DSP System Toolbox
Submatrix	DSP System Toolbox
Upsample	DSP System Toolbox
Variable Selector	DSP System Toolbox

**Purpose** Design parametric equalizer

**Library** Filtering / Filter Designs  
dspfdesign

**Description** This block brings the filter design capabilities of the `filterbuilder` function to the Simulink environment.



**Dialog Box** See “Parametric Equalizer Filter Design Dialog Box — Main Pane” on page 7-761 for more information about the parameters of this block. The **Data Types** and **Code Generation** panes are not available for blocks in the DSP System Toolbox Filter Designs library.

Parameters of this block that do not change filter order or structure are tunable.

# Parametric Equalizer

Function Block Parameters: Parametric Equalizer

Parametric Equalizer

Design a parametric equalizer.

[View Filter Response](#)

Filter specifications

Order mode:  Order:

Frequency specifications

Frequency constraints:

Frequency units:  Input Fs:

Center frequency:  Bandwidth

Passband width:

Gain specifications

Gain constraints:

Gain units:

Reference gain:  Center frequency gain:

Bandwidth gain:  Passband gain:

Algorithm

Design method:

Scale SOS filter coefficients to reduce chance of overflow

Filter Implementation

Structure:

Use basic elements to enable filter customization

Optimize for unit scale values

Input processing:

Use symbolic names for coefficients

## View filter response

This button opens the Filter Visualization Tool (fvtool) from the Signal Processing Toolbox product. You can use the tool to display:

- Magnitude response, phase response, and group delay in the frequency domain.
- Impulse response and step response in the time domain.
- Pole-zero information.

The tool also helps you evaluate filter performance by providing information about filter order, stability, and phase linearity. For more information on FVTool, see the Signal Processing Toolbox documentation.

## Filter Specifications

### Order mode

Select **Minimum** to design a minimum order filter that meets the design specifications, or **Specify** to enter a specific filter order. The order mode also affects the possible frequency constraints, which in turn limit the gain specifications. For example, if you specify a **Minimum** order filter, the available frequency constraints are:

- Center frequency, bandwidth, passband width
- Center frequency, bandwidth, stopband width

If you select **Specify**, the available frequency constraints are:

- Center frequency, bandwidth
- Center frequency, quality factor
- Shelf type, cutoff frequency, quality factor
- Shelf type, cutoff frequency, shelf slope parameter
- Low frequency, high frequency

# Parametric Equalizer

---

## Order

Specify the filter order. This parameter is enabled only if the **Order mode** is set to **Specify**.

## Frequency specifications

Depending on the filter order, the possible frequency constraints change. Once you choose the frequency constraints, the input boxes in this area change to reflect the selection.

## Frequency constraints

Select the specification to represent the frequency constraints. The following options are available:

- Center frequency, bandwidth, passband width (available for minimum order only)
- Center frequency, bandwidth, stopband width (available for minimum order only)
- Center frequency, bandwidth (available for a specified order only)
- Center frequency, quality factor (available for a specified order only)
- Shelf type, cutoff frequency, quality factor (available for a specified order only)
- Shelf type, cutoff frequency, shelf slope parameter (available for a specified order only)
- Low frequency, high frequency (available for a specified order only)

## Frequency units

Select the frequency units from the available drop down list (Normalized, Hz, kHz, MHz, GHz). If **Normalized** is selected, then the **Input Fs** box is disabled for input.

## Input Fs

Enter the input sampling frequency. This input box is disabled for input if Normalized is selected in the **Frequency units** input box.

## Center frequency

Enter the center frequency in the units specified by the value in **Frequency units**.

## Bandwidth

The bandwidth determines the frequency points at which the filter magnitude is attenuated by the value specified as the **Bandwidth gain** in the **Gain specifications** section. By default, the **Bandwidth gain** defaults to  $\text{db}(\text{sqrt}(.5))$ , or  $-3$  dB relative to the center frequency. The **Bandwidth** property only applies when the **Frequency constraints** are: Center frequency, bandwidth, passband width, Center frequency, bandwidth, stopband width, or Center frequency, bandwidth.

## Passband width

The passband width determines the frequency points at which the filter magnitude is attenuated by the value specified as the **Passband gain** in the **Gain specifications** section. This option is enabled only if the filter is of minimum order, and the frequency constraint selected is Center frequency, bandwidth, passband width.

## Stopband width

The stopband width determines the frequency points at which the filter magnitude is attenuated by the value specified as the **Stopband gain** in the **Gain specifications** section. This option is enabled only if the filter is of minimum order, and the frequency constraint selected is Center frequency, bandwidth, stopband width.

## Low frequency

Enter the low frequency cutoff. This option is enabled only if the filter order is user specified and the frequency constraint selected

# Parametric Equalizer

---

is Low frequency, high frequency. The filter magnitude is attenuated by the amount specified in **Bandwidth gain**.

## High frequency

Enter the high frequency cutoff. This option is enabled only if the filter order is user specified and the frequency constraint selected is Low frequency, high frequency. The filter magnitude is attenuated by the amount specified in **Bandwidth gain**.

## Gain Specifications

Depending on the filter order and frequency constraints, the possible gain constraints change. Also, once you choose the gain constraints the input boxes in this area change to reflect the selection.

### Gain constraints

Select the specification array to represent gain constraints, and remember that not all of these options are available for all configurations. The following is a list of all available options:

- Reference, center frequency, bandwidth, passband
- Reference, center frequency, bandwidth, stopband
- Reference, center frequency, bandwidth, passband, stopband
- Reference, center frequency, bandwidth

### Gain units

Specify the gain units either dB or squared. These units are used for all gain specifications in the dialog box.

### Reference gain

The reference gain determines the level to which the filter magnitude attenuates in **Gain units**. The reference gain is a *floor* gain for the filter magnitude response. For example, you may use the reference gain together with the **Center frequency gain** to leave certain frequencies unattenuated (reference gain of 0 dB) while boosting other frequencies.

## **Bandwidth gain**

Specifies the gain in **Gain units** at which the bandwidth is defined. This property applies only when the **Frequency constraints** specification contains a bandwidth parameter, or is Low frequency, high frequency.

## **Center frequency gain**

Specify the center frequency in **Gain units**

## **Passband gain**

The passband gain determines the level in **Gain units** at which the passband is defined. The passband is determined either by the **Passband width** value, or the **Low frequency** and **High frequency** values in the **Frequency specifications** section.

## **Stopband gain**

The stopband gain is the level in **Gain units** at which the stopband is defined. This property applies only when the **Order mode** is minimum and the **Frequency constraints** are Center frequency, bandwidth, stopband width.

## **Boost/cut gain**

The boost/cut gain applies only when the designing a shelving filter. Shelving filters include the **Shelf** type parameter in the **Frequency constraints** specification. The gain in the passband of the shelving filter is increased by **Boost/cut gain** dB from a *floor* gain of 0 dB.

## **Algorithm**

### **Design method**

Select the design method from the drop-down list. Different methods are available depending on the chosen filter constraints.

### **Scale SOS filter coefficients to reduce chance of overflow**

Select the check box to scale the filter coefficients.

# Parametric Equalizer

---

## Filter Implementation

### Structure

Specify filter structure. Choose from:

- Direct-form I SOS
- Direct-form II SOS
- Direct-form I transposed SOS
- Direct-form II transposed SOS

### Use basic elements to enable filter customization

Select this check box to implement the filter as a subsystem of basic Simulink blocks. Clear the check box to implement the filter as a high-level subsystem. By default, this check box is cleared.

The high-level implementation provides better compatibility across various filter structures, especially filters that would contain algebraic loops when constructed using basic elements. On the other hand, using basic elements enables the following optimization parameters:

- **Optimize for zero gains** — Terminate chains that contain Gain blocks with a gain of zero.
- **Optimize for unit gains** — Remove Gain blocks that scale by a factor of one.
- **Optimize for delay chains** — Substitute delay chains made up of  $n$  unit delays with a single delay by  $n$ .
- **Optimize for negative gains** — Use subtraction in Sum blocks instead of negative gains in Gain blocks.

### Optimize for unit-scale values

Select this check box to scale unit gains between sections in SOS filters. This parameter is available only for SOS filters.

## Input processing

Specify how the block should process the input. The available options may vary depending on the settings of the **Filter Structure** and **Use basic elements for filter customization** parameters. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The Inherited (this choice will be removed see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Rate options

When the **Filter type** parameter specifies a multirate filter, select the rate processing rule for the block from following options:

- **Enforce single-rate processing** — When you select this option, the block maintains the sample rate of the input.
- **Allow multirate processing** — When you select this option, the block adjusts the rate at the output to accommodate an increased or reduced number of samples. To select this option, you must set the **Input processing** parameter to **Elements as channels (sample based)**.

## Use symbolic names for coefficients

Select this check box to enable the specification of coefficients using MATLAB variables. The available coefficient names differ depending on the filter structure. Using symbolic names allows

# Parametric Equalizer

---

tuning of filter coefficients in generated code. By default, this check box is cleared.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>


## Purpose

Determine whether each value of input signal is local minimum or maximum

## Library

Signal Operations  
dspops

## Description



The Peak Finder block counts the number of local extrema in each column of the real-valued input signal. The block outputs the number of local extrema at the Cnt port. You can also configure the block to output the extrema indices, the extrema values, and a binary indicator of whether or not the extrema are maxima or minima.

To qualify as an extrema, a point has to be larger (or smaller) than both of its neighboring points. Thus, end points are never considered extrema.

If you select the **Output peak indices** check box, the Idx port appears on the block. The block outputs the zero-based extrema indices at the Idx port. If you select the **Output peak values** check box, the Val port appears on the block. The block outputs the extrema values at the Val port. If you select either of these check boxes and set the **Peak type(s)** to **Maxima** and **Minima**, the Pol port also appears on the block. If the signal value is a maximum, the block outputs a 1 at the Pol ("Polarity") port. If the signal value is a minimum, the block outputs a 0 at the Pol port.

Use the **Maximum number of peaks to find** parameter to specify how many extrema to look for in each input signal. The block stops searching the input signal once this maximum number of extrema has been found.

If you select the **Ignore peaks within threshold of neighboring values** check box, the block no longer detects low-amplitude peaks. This feature allows the block to ignore noise within a threshold value that you define. Enter a threshold value for the **Threshold** parameter. Now, the current value is a maximum if  $(\text{current} - \text{previous}) > \text{threshold}$  and  $(\text{current} - \text{next}) > \text{threshold}$ . The current value is a minimum if  $(\text{current} - \text{previous}) < -\text{threshold}$  and  $(\text{current} - \text{next}) < -\text{threshold}$ .

# Peak Finder

## Examples

### Example 1

Consider the input vector

[9 6 10 3 4 5 0 12]

The table below shows the analysis made by the Peak Finder block. Note that the first and last input signal values are not considered:

Previous, current, and next values	9 6 10	6 10 3	10 3 4	3 4 5	4 5 0	5 0 12
Current value if it is an extremum	6	10	3	—	5	0
Index of current value if it is an extremum	1	2	3	—	5	6
Polarity of current value if it is an extremum	0	1	0	—	1	0

Therefore, for this example the outputs at the block ports are

Cnt: 5


Idx: [1 2 3 5 6]

Val: [6 10 3 5 0]

Pol: [0 1 0 1 0]

### Example 2

Note that the **Overflow mode** parameter can affect the output of the block when the input is fixed point. Consider the following model:



In this model, the settings in the Constant block are

- **Constant value** —  $[-1 \ 0.5 \ -1]$
- **Interpret vector parameters as 1-D** — not selected
- **Sampling mode** — Sample based
- **Sample time** — 1
- **Output data type** — `<data type expression>`
- **Mode** — Fixed point
- **Sign** — Signed

# Peak Finder

---

- **Scaling** — Binary point
- **Word length** — 16
- **Fraction length** — 15


The settings in the Peak Finder blocks are

- **Peak type(s)** — Maxima
- **Output peak indices** — not selected
- **Output peak values** — selected
- **Maximum number of peaks to find** — 2
- **Ignore peaks within threshold of neighboring values** — selected
- **Threshold** — 0.25
- **Overflow mode** — Wrap for Peak Finder Wrap, Saturate for Peak Finder Saturate

Setting the **Overflow mode** parameter of the Peak Finder Wrap block to Wrap causes the calculations  $(\text{current} - \text{previous}) > \text{threshold}$  and  $(\text{current} - \text{next}) > \text{threshold}$  to wrap on overflow, thereby causing the maximum to be missed.

## Dialog Box

The **Main** pane of the Peak Finder block dialog appears as follows.



### Peak type(s)

Specify whether you are looking for maxima, minima, or both.

### Output peak indices

Select this check box if you want the block to output the extrema indices at the Idx port.

### Output peak values

Select this check box if you want the block to output the extrema values at the Val port.

# Peak Finder

---

## **Maximum number of peaks to find**

Enter the number of extrema to look for in each input signal. The block stops searching the input signal for extrema once the maximum number of extrema has been found. The value of this parameter must be an integer greater than or equal to one.


## **Ignore peaks within threshold of neighboring values**

Select this check box if you want to eliminate the detection of peaks whose amplitudes are within a specified threshold of neighboring values.

## **Threshold**

Enter your threshold value. This parameter appears if you select the **Ignore peaks within threshold of neighboring values** check box.

When you select the **Ignore peaks within threshold of neighboring values** check box, the **Data Types** pane of the Peak Finder block appears as follows.



## Overflow mode

Select the overflow mode to be used when block inputs are fixed point.

# Peak Finder

---

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Cnt	<ul style="list-style-type: none"><li>• 32-bit unsigned integers</li></ul>
Idx	<ul style="list-style-type: none"><li>• 32-bit unsigned integers</li></ul>
Val	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Pol	<ul style="list-style-type: none"><li>• Boolean</li></ul>


## See Also

Maximum	DSP System Toolbox
Minimum	DSP System Toolbox

**Purpose** Design peak or notch filter

**Library** Filtering / Filter Designs  
dspfdesign

**Description** This block brings the filter design capabilities of the `filterbuilder` function to the Simulink environment.



**Dialog Box** See “Peak/Notch Filter Design Dialog Box — Main Pane” on page 7-767 for more information about the parameters of this block. The **Data Types** and **Code Generation** panes are not available for blocks in the DSP System Toolbox Filter Designs library.

Parameters of this block that do not change filter order or structure are tunable.

# Peak-Notch Filter

Function Block Parameters: Peak-Notch Filter

Peak/Notch Filter

Design a peak or notch filter.

[View Filter Response](#)

Filter specifications

Response:  Order:

Frequency specifications

Frequency constraints:

Frequency units:  Input Fs:

Center frequency:  Quality factor:

Magnitude specifications

Magnitude constraints:

Algorithm

Design method:

Scale SOS filter coefficients to reduce chance of overflow

Filter Implementation

Structure:

Use basic elements to enable filter customization

Optimize for unit scale values

Input processing:

Use symbolic names for coefficients

- Impulse response and step response in the time domain.
- Pole-zero information.

The tool also helps you evaluate filter performance by providing information about filter order, stability, and phase linearity. For more information on FVTool, see the Signal Processing Toolbox documentation.

## Filter Specifications

In this area you can specify whether you want to design a peaking filter or a notching filter, as well as the order of the filter.

### Response

Select **Peak** or **Notch** from the drop-down list. The rest of the parameters that specify are equivalent for either filter type.

### Order

Enter the filter order. The order must be even.

## Frequency Specifications

This group of parameters allows you to specify frequency constraints and units.

### Frequency Constraints

Select the frequency constraints for filter specification. There are two choices as follows:

- Center frequency and quality factor
- Center frequency and bandwidth

### Frequency units

The frequency units are normalized by default. If you specify units other than normalized, the block assumes that you wish to specify an input sampling frequency, and enables this input box. The choice of frequency units are: Normalized (0 to 1), Hz, kHz, MHz, GHz.

# Peak-Notch Filter

---

## Input Fs

This input box is enabled if **Frequency units** other than Normalized (0 to 1) are specified. Enter the input sampling frequency.

## Center frequency

Enter the center frequency in the units specified previously.

## Quality Factor

This input box is enabled only when Center frequency and quality factor is chosen for the **Frequency Constraints**. Enter the quality factor.

## Bandwidth

This input box is enabled only when Center frequency and bandwidth is chosen for the **Frequency Constraints**. Enter the bandwidth.

## Magnitude Specifications

This group of parameters allows you to specify the magnitude constraints, as well as their values and units.

### Magnitude Constraints

Depending on the choice of constraints, the other input boxes are enabled or disabled. Select from four magnitude constraints available:

- Unconstrained
- Passband ripple
- Stopband attenuation
- Passband ripple and stopband attenuation

### Magnitude units

Select the magnitude units: either dB or squared.

## **Apass**

This input box is enabled if the magnitude constraints selected are Passband ripple or Passband ripple and stopband attenuation. Enter the passband ripple.

## **Astop**

This input box is enabled if the magnitude constraints selected are Stopband attenuation or Passband ripple and stopband attenuation. Enter the stopband attenuation.

## **Algorithm**

The parameters in this group allow you to specify the design method and structure of your filter.

### **Design Method**

Lists all design methods available for the frequency and magnitude specifications you entered. When you change the specifications for a filter the methods available to design filters changes as well.

### **Scale SOS filter coefficients to reduce chance of overflow**

Selecting this parameter directs the design to scale the filter coefficients to reduce the chances that the inputs or calculations in the filter overflow and exceed the representable range of the filter. Clearing this option removes the scaling. This parameter applies only to IIR filters.

## **Filter Implementation**

### **Structure**

Specify filter structure. Choose from:

- Direct-form I SOS
- Direct-form II SOS
- Direct-form I transposed SOS
- Direct-form II transposed SOS

# Peak-Notch Filter

---

## Use basic elements to enable filter customization

Select this check box to implement the filter as a subsystem of basic Simulink blocks. Clear the check box to implement the filter as a high-level subsystem. By default, this check box is cleared.

The high-level implementation provides better compatibility across various filter structures, especially filters that would contain algebraic loops when constructed using basic elements. On the other hand, using basic elements enables the following optimization parameters:

- **Optimize for zero gains** — Terminate chains that contain Gain blocks with a gain of zero.
- **Optimize for unit gains** — Remove Gain blocks that scale by a factor of one.
- **Optimize for delay chains** — Substitute delay chains made up of  $n$  unit delays with a single delay by  $n$ .
- **Optimize for negative gains** — Use subtraction in Sum blocks instead of negative gains in Gain blocks.

## Optimize for unit-scale values

Select this check box to scale unit gains between sections in SOS filters. This parameter is available only for SOS filters.

## Input processing

Specify how the block should process the input. The available options may vary depending on the settings of the **Filter Structure** and **Use basic elements for filter customization** parameters. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The Inherited (this choice will be removed see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Rate options

When the **Filter type** parameter specifies a multirate filter, select the rate processing rule for the block from following options:

- **Enforce single-rate processing** — When you select this option, the block maintains the sample rate of the input.
- **Allow multirate processing** — When you select this option, the block adjusts the rate at the output to accommodate an increased or reduced number of samples. To select this option, you must set the **Input processing** parameter to **Elements as channels** (sample based).

## Use symbolic names for coefficients

Select this check box to enable the specification of coefficients using MATLAB variables. The available coefficient names differ depending on the filter structure. Using symbolic names allows tuning of filter coefficients in generated code. By default, this check box is cleared.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

# Periodogram

---



## Purpose

Power spectral density or mean-square spectrum estimate using periodogram method

## Library

Estimation / Power Spectrum Estimation  
dspsect3


## Description



The Periodogram block estimates the power spectral density (PSD) or mean-square spectrum (MSS) of the input. It does so by using the periodogram method and Welch's averaged, modified periodogram method. The block averages the squared magnitude of the FFT computed over windowed sections of the input. It then normalizes the spectral average by the square of the sum of the window samples. See "Periodogram" and "Welch's Method" in the Signal Processing Toolbox documentation for more information.

The block treats  $M$ -by- $N$  frame-based matrix input and  $M$ -by- $N$  sample-based matrix input as  $M$  sequential time samples from  $N$  independent channels. The block computes a separate estimate for each of the  $N$  independent channels and generates an  $N_{fft}$ -by- $N$  matrix output.

Each column of the output matrix contains the estimate of the power spectral density of the corresponding input column at  $N_{fft}$  equally spaced frequency points. The frequency points are in the range  $[0, F_s)$ , where  $F_s$  is the sampling frequency of the signal. The block always outputs sample-based data.



## Dialog Box

### Measurement

Specify the type of measurement for the block to perform: Power spectral density or Mean-square spectrum. Tunable.

# Periodogram

---

## Window

Select the type of window to apply. See the Window Function block reference page for more details. Tunable.

## Stopband attenuation in dB

Enter the level, in decibels (dB), of stopband attenuation,  $R_s$ , for the Chebyshev window. This parameter becomes visible if, for the **Window** parameter, you choose Chebyshev. Tunable.

## Beta

Enter the  $\beta$  parameter for the Kaiser window. This parameter becomes visible if, for the **Window** parameter, you chose Kaiser. Increasing **Beta** widens the mainlobe and decreases the amplitude of the sidelobes in the displayed frequency magnitude response. Tunable. See the Window Function block reference page for more details.

## Window sampling

From the list, choose **Symmetric** or **Periodic**. See the Window Function block reference page for more details. Tunable.

## FFT implementation

Set this parameter to FFTW [1], [2] to support an arbitrary length input signal. The block restricts generated code with FFTW implementation to MATLAB host computers.

Set this parameter to Radix-2 for bit-reversed processing, fixed or floating-point data, or for portable C-code generation using the Simulink Coder. The first dimension  $M$ , of the input matrix must be a power of two. To work with other input sizes, use the Pad block to pad or truncate these dimensions to powers of two, or if possible choose the FFTW implementation.

Set this parameter to Auto to let the block choose the FFT implementation. For non-power-of-two transform lengths, the block restricts generated code to MATLAB host computers.

## **Inherit FFT length from input dimensions**

When you select this check box, the block uses the input frame size as the number of data points,  $N_{fft}$ , on which to perform the FFT. To specify the number of points on which to perform the FFT, clear the **Inherit FFT length from estimation order** check box. You can then specify a power of two FFT length using the **FFT length** parameter.

## **FFT length**

Enter the number of data points on which to perform the FFT,  $N_{fft}$ . When  $N_{fft}$  is larger than the input frame size, the block zero-pads each frame as needed. When  $N_{fft}$  is smaller than the input frame size, the block wraps each frame as needed. This parameter becomes visible only when you clear the **Inherit FFT length from input dimensions** check box.

When you set the **FFT implementation** parameter to Radix-2, this value must be a power of two.

## **Number of spectral averages**

Specify the number of spectra to average. When you set this value to 1, the block computes the periodogram of the input. When you set this value greater 1, the block implements “Welch’s Method” to compute a modified periodogram of the input.

## **Inherit sample time from input**

If you select the **Inherit sample time from input** check box, the block computes the frequency data from the sample period of the input signal. For the block to produce valid output, the following conditions must hold:

- The input to the block is the original signal, with no samples added or deleted (by insertion of zeros, for example).
- The sample period of the time-domain signal in the simulation equals the sample period of the original time series.

# Periodogram

---

If these conditions do not hold, clear the **Inherit sample time from input** check box. You can then specify a sample time using the **Sample time of original time series** parameter.

## **Sample time of original time series**

Specify the sample time of the original time-domain signal. This parameter becomes visible only when you clear the **Inherit sample time from input** check box.

## **Example**

The `dspstfft` example provides an illustration of using the Periodogram and Matrix Viewer blocks to create a spectrogram. The `dpsacomp` example compares the Periodogram block with several other spectral estimation methods.

## **References**

Oppenheim, A. V. and R. W. Schaffer. *Discrete-Time Signal Processing*. Englewood Cliffs, NJ: Prentice Hall, 1989.

Orfanidis, S. J. *Introduction to Signal Processing*. Englewood Cliffs, NJ: Prentice-Hall, 1995.

Proakis, J. and D. Manolakis. *Digital Signal Processing*. 3rd ed. Englewood Cliffs, NJ: Prentice-Hall, 1996.

## **References**

[1] FFTW (<http://www.fftw.org>)

[2] Frigo, M. and S. G. Johnson, "FFTW: An Adaptive Software Architecture for the FFT," *Proceedings of the International Conference on Acoustics, Speech, and Signal Processing*, Vol. 3, 1998, pp. 1381-1384.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

## See Also

Burg Method	DSP System Toolbox
Inverse Short-Time FFT	DSP System Toolbox
Magnitude FFT	DSP System Toolbox
Short-Time FFT	DSP System Toolbox
Spectrum Scope	DSP System Toolbox
Window Function	DSP System Toolbox
Yule-Walker Method	DSP System Toolbox
<code>spectrum.periodogram</code>	Signal Processing Toolbox
<code>spectrum.welch</code>	Signal Processing Toolbox

See “Spectral Analysis” for related information.

# Permute Matrix

---

## Purpose


Reorder matrix rows or columns

## Library

Math Functions / Matrices and Linear Algebra / Matrix Operations

dspmtrx3

## Description



The Permute Matrix block reorders the rows or columns of M-by-N input matrix A as specified by indexing input P.

When the **Permute** parameter is set to **Rows**, the block uses the rows of A to create a new matrix with the same column dimension. Input P is a length-L vector whose elements determine where each row from A should be placed in the L-by-N output matrix.

`% Equivalent MATLAB code`

```
y = [A(P(1),:) ; A(P(2),:) ; A(P(3),:) ; ... ; A(P(end),:)]
```

For row permutation, the block treats length-M unoriented vector input at the A port as an M-by-1 matrix.

When the **Permute** parameter is set to **Columns**, the block uses the columns of A to create a new matrix with the same row dimension. Input P is a length-L vector whose elements determine where each column from A should be placed in the M-by-L output matrix.

`% Equivalent MATLAB code`

```
y = [A(:,P(1)) A(:,P(2)) A(:,P(3)) ... A(:,P(end))]
```

For column permutation, the block treats length-N unoriented vector input at the A port as a 1-by-N matrix.

When an index value in input P references a nonexistent row or column of matrix A, the block reacts with the behavior specified by the **Invalid permutation index** parameter. The following options are available:


- **Clip index** — Clip the index to the nearest valid value (1 or M for row permutation, and 1 or N for column permutation), and *do not* issue an alert. Example: For a 3-by-7 input matrix, a column index of 9 is clipped to 7, and a row index of -2 is clipped to 1.

- **Clip and warn** — Display a warning message in the MATLAB command window, and clip the index as described above.
- **Generate error** — Display an error dialog box and terminate the simulation.

When length of the permutation vector P is not equal to the number of rows or columns of the input matrix A, you can choose to get an error dialog box and terminate the simulation by selecting **Error when length of P is not equal to Permute dimension size**.


## Examples

In the model below, the top Permute Matrix block places the second row of the input matrix in both the first and fifth rows of the output matrix, and places the third row of the input matrix in the three middle rows of the output matrix. The bottom Permute Matrix block places the second column of the input matrix in both the first and fifth columns of the output matrix, and places the third column of the input matrix in the three middle columns of the output matrix.



As shown in the example above, rows and columns of A can appear any number of times in the output, or not at all.

# Permute Matrix



## Dialog Box

### Permute

Method of constructing the output matrix; by permuting rows or columns of the input.

### Index mode

When set to One-based, a value of 1 in the permutation vector P refers to the first row or column of the input matrix A. When set to Zero-based, a value of 0 in P refers to the first row or column of A.

### Invalid permutation index

Response to an invalid index value. Tunable.

### Error when length of P is not equal to Permute dimension size

Option to display an error dialog box and terminate the simulation when the length of the permutation vector P is not equal to the number of rows or columns of the input matrix A.

## Supported Data Types

Port	Supported Data Types
A	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed and unsigned)</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> <li>• Enumerated</li> </ul>
P	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> <li>• Enumerated</li> </ul>
Output	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed and unsigned)</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> <li>• Enumerated</li> </ul>

## See Also

Submatrix	DSP System Toolbox
Transpose	DSP System Toolbox

# Permute Matrix

---


Variable Selector	DSP System Toolbox
<code>permute</code>	MATLAB

See “Reorder Channels in Multichannel Frame-Based Signals” for related information.

**Purpose** Evaluate polynomial expression

**Library** Math Functions / Polynomial Functions  
dspolyfun

**Description** The Polynomial Evaluation block applies a polynomial function to the real or complex input at the In port.



```
y = polyval(u) % Equivalent MATLAB code
```

The Polynomial Evaluation block performs these types of operation more efficiently than the equivalent construction using Simulink Sum and Math Function blocks.


When you select the **Use constant coefficients** check box, you specify the polynomial expression in the **Constant coefficients** parameter. When you do not select **Use constant coefficients**, a variable polynomial expression is specified by the input to the **Coefs** port. In both cases, the polynomial is specified as a vector of real or complex coefficients in order of descending exponents.

The table below shows some examples of the block's operation for various coefficient vectors.

Coefficient Vector	Equivalent Polynomial Expression
[1 2 3 4 5]	$y = u^4 + 2u^3 + 3u^2 + 4u + 5$
[1 0 3 0 5]	$y = u^4 + 3u^2 + 5$
[1 2+i 3 4-3i 5i]	$y = u^4 + (2+i)u^3 + 3u^2 + (4-3i)u + 5i$

Each element of a vector or matrix input to the In port is processed independently, and the output size is the same as the input.

# Polynomial Evaluation



## Dialog Box

### Use constant coefficients

Select to enable the **Constant coefficients** parameter and disable the **Coeffs** input port.

### Constant coefficients

Specify the vector of polynomial coefficients to apply to the input, in order of descending exponents. This parameter is enabled when you select the **Use constant coefficients** check box.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point

## See Also

Least Squares Polynomial Fit	DSP System Toolbox
Math Function	Simulink
Sum	Simulink
polyval	MATLAB

## Purpose


Use Schur-Cohn algorithm to determine whether all roots of input polynomial are inside unit circle

## Library

Math Functions / Polynomial Functions

dsppolyfun

## Description



The Polynomial Stability Test block uses the Schur-Cohn algorithm to determine whether all roots of a polynomial are within the unit circle.

```
y = all(abs(roots(u)) < 1) % Equivalent MATLAB code
```

Each column of the M-by-N input matrix  $u$  contains M coefficients from a distinct polynomial,

$$f(x) = u_1 x^{M-1} + u_2 x^{M-2} + \dots + u_M$$

arranged in order of descending exponents,  $u_1, u_2, \dots, u_M$ . The polynomial has order M-1 and positive integer exponents.

Inputs to the block represent the polynomial coefficients as shown in the previous equation. The block always treats length-M unoriented vector input as an M-by-1 matrix.

The output is a 1-by-N matrix with each column containing the value 1 or 0. The value 1 indicates that the polynomial in the corresponding column of the input is stable; that is, the magnitudes of all solutions to  $f(x) = 0$  are less than 1. The value 0 indicates that the polynomial in the corresponding column of the input might be unstable; that is, the magnitude of at least one solution to  $f(x) = 0$  is greater than or equal to 1.

## Applications


This block is most commonly used to check the pole locations of the denominator polynomial,  $A(z)$ , of a transfer function,  $H(z)$ .

$$H(z) = \frac{B(z)}{A(z)} = \frac{b_1 + b_2 z^{-1} + \dots + b_m z^{-(m-1)}}{a_1 + a_2 z^{-1} + \dots + a_n z^{-(n-1)}}$$

# Polynomial Stability Test

---

The poles are the  $n-1$  roots of the denominator polynomial,  $A(z)$ . When any poles are located outside the unit circle, the transfer function  $H(z)$  is unstable. As is typical in DSP applications, the transfer function above is specified in descending powers of  $z^{-1}$  rather than  $z$ .



## Dialog Box

## Supported Data Types

- Double-precision floating point
- Single-precision floating point
- Boolean — Block outputs are always Boolean.

## See Also

Least Squares Polynomial Fit  
Polynomial Evaluation  
polyfit

DSP System Toolbox  
DSP System Toolbox  
MATLAB

## Purpose

Compute Moore-Penrose pseudoinverse of matrix

## Library

Math Functions / Matrices and Linear Algebra / Matrix Inverses  
dspinverses

## Description



The Pseudoinverse block computes the Moore-Penrose pseudoinverse of input matrix  $A$ .

```
[U,S,V] = svd(A,0)           % Equivalent MATLAB code
```


The pseudoinverse of  $A$  is the matrix  $A^\dagger$  such that

$$A^\dagger = VS^\dagger U^*$$

where  $U$  and  $V$  are orthogonal matrices, and  $S$  is a diagonal matrix. The pseudoinverse has the following properties:

- $AA^\dagger = (AA^\dagger)^*$
- $A^\dagger A = (A^\dagger A)^*$
- $AA^\dagger A = A$
-

# Pseudoinverse



## Dialog Box

### Show error status port

Select to enable the E output port, which reports a failure to converge. The possible values you can receive on the port are:

- 0 — The pseudoinverse calculation converges.
- 1 — The pseudoinverse calculation does not converge.

If the pseudoinverse calculation fails to converge, the output at port X is an undefined matrix of the correct size.

## References

Golub, G. H., and C. F. Van Loan. *Matrix Computations*. 3rd ed. Baltimore, MD: Johns Hopkins University Press, 1996.

## Supported Data Types

Port	Supported Data Types
A	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
X	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
E	<ul style="list-style-type: none"><li>• Boolean</li></ul>

## See Also

Cholesky Inverse	DSP System Toolbox
LDL Inverse	DSP System Toolbox
LU Inverse	DSP System Toolbox
Singular Value Decomposition	DSP System Toolbox
inv	MATLAB

See “Matrix Inverses” for related information.

# Pulse Shaping Filter

---

**Purpose** Design pulse shaping filter

**Library** Filtering / Filter Designs  
dspfdesign

**Description** This block brings the filter design capabilities of the `filterbuilder` function to the Simulink environment.



**Dialog Box** See “Pulse-shaping Filter Design Dialog Box—Main Pane” on page 7-771 for more information about the parameters of this block. The **Data Types** and **Code** panes are not available for blocks in the DSP System Toolbox Filter Designs library.

Parameters of this block that do not change filter order or structure are tunable.

# Pulse Shaping Filter

Function Block Parameters: Pulse Shaping Filter

Pulse-shaping Filter

Design a pulse-shaping filter.

[View Filter Response](#)

Filter specifications

Pulse shape: Raised Cosine

Order mode: Minimum Order:

Samples per symbol: 8

Filter Type: Single-rate

Frequency specifications

Rolloff factor: .5

Frequency units: Normalized (0 to 1) Input Fs: 2

Magnitude specifications

Magnitude units: dB

Astop: 50

Algorithm

Design method: Window

Filter Implementation

Structure: Direct-form FIR

Use basic elements to enable filter customization

Input processing: Columns as channels (frame based)

Use symbolic names for coefficients

OK Cancel Help **2-1227** Apply

# Pulse Shaping Filter

---

## View filter response

This button opens the Filter Visualization Tool (fvtool) from the Signal Processing Toolbox product. You can use the tool to display:

- Magnitude response, phase response, and group delay in the frequency domain.
- Impulse response and step response in the time domain.
- Pole-zero information.

The tool also helps you evaluate filter performance by providing information about filter order, stability, and phase linearity. For more information on FVTool, see the Signal Processing Toolbox documentation.

## Filter Specifications

In this group, you specify the shape and length of the filter.

### Pulse shape

Select the shape of the impulse response from the following options:

- Raised Cosine
- Square Root Raised Cosine
- Gaussian

### Order mode

This specification is only available for raised cosine and square root raised cosine filters. For these filters, select one of the following options:

- **Minimum**— This option will result in the minimum-length filter satisfying the user-specified **Frequency specifications**.
- **Specify order**—This option allows the user to construct a raised cosine or square root cosine filter of a specified order by entering an even number in the **Order** input box. The length of the impulse response will be  $\text{Order}+1$ .

- **Specify symbols**—This option enables the user to specify the length of the impulse response in an alternative manner. If **Specify symbols** is chosen, the **Order** input box changes to the **Number of symbols** input box.

## **Samples per symbol**

Specify the oversampling factor. Increasing the oversampling factor guards against aliasing and improves the FIR filter approximation to the ideal frequency response. If **Order** is specified in **Number of symbols**, the filter length will be **Number of symbols\*Samples per symbol+1**. The product **Number of symbols\*Samples per symbol** must be an even number.

If a Gaussian filter is specified, the filter length must be specified in **Number of symbols** and **Samples per symbol**. The product **Number of symbols\*Samples per symbol** must be an even number. The filter length will be **Number of symbols\*Samples per symbol+1**.

## **Frequency specifications**

In this group, you specify the frequency response of the filter. For raised cosine and square root raised cosine filters, the frequency specifications include:

### **Rolloff factor**

The rolloff factor takes values in the range [0,1]. The smaller the rolloff factor, the steeper the transition in the stopband.

### **Frequency units**

The frequency units are normalized by default. If you specify units other than normalized, the block assumes that you wish to specify an input sampling frequency, and enables this input box. The choice of frequency units are: **Normalized (0 to 1)**, **Hz**, **KHz**, **MHz**, **GHz**

For a Gaussian pulse shape, the available frequency specifications are:

# Pulse Shaping Filter

---

## Bandwidth-time product

This option allows the user to specify the width of the Gaussian filter. Note that this is independent of the length of the filter. The bandwidth-time product (BT) must be a positive real number. Smaller values of the bandwidth-time product result in larger pulse widths in time and steeper stopband transitions in the frequency response.

## Frequency units

The frequency units are normalized by default. If you specify units other than normalized, the block assumes that you wish to specify an input sampling frequency, and enables this input box. The choice of frequency units are: Normalized (0 to 1), Hz, kHz, MHz, GHz

## Magnitude specifications

If the **Order mode** is specified as minimum, the magnitude units may be selected from:

- dB — Specify the magnitude in decibels (default).
- Linear — Specify the magnitude in linear units.

## Algorithm

The only design method available for FIR pulse-shaping filters is the window method.

## Filter Implementation

### Structure

For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter. FIR filters use direct-form structure.

### Use basic elements to enable filter customization

Select this check box to implement the filter as a subsystem of basic Simulink blocks. Clear the check box to implement the filter as a high-level subsystem. By default, this check box is cleared.

The high-level implementation provides better compatibility across various filter structures, especially filters that would contain algebraic loops when constructed using basic elements. On the other hand, using basic elements enables the following optimization parameters:

- **Optimize for zero gains** — Terminate chains that contain Gain blocks with a gain of zero.
- **Optimize for unit gains** — Remove Gain blocks that scale by a factor of one.
- **Optimize for delay chains** — Substitute delay chains made up of  $n$  unit delays with a single delay by  $n$ .
- **Optimize for negative gains** — Use subtraction in Sum blocks instead of negative gains in Gain blocks.

### Optimize for unit-scale values

Select this check box to scale unit gains between sections in SOS filters. This parameter is available only for SOS filters.

### Input processing

Specify how the block should process the input. The available options may vary depending on the settings of the **Filter Structure** and **Use basic elements for filter customization** parameters. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

# Pulse Shaping Filter

---

---

**Note** The Inherited (this choice will be removed see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Rate options

When the **Filter type** parameter specifies a multirate filter, select the rate processing rule for the block from following options:

- **Enforce single-rate processing** — When you select this option, the block maintains the sample rate of the input.
- **Allow multirate processing** — When you select this option, the block adjusts the rate at the output to accommodate an increased or reduced number of samples. To select this option, you must set the **Input processing** parameter to **Elements as channels** (sample based).

## Use symbolic names for coefficients

Select this check box to enable the specification of coefficients using MATLAB variables. The available coefficient names differ depending on the filter structure. Using symbolic names allows tuning of filter coefficients in generated code. By default, this check box is cleared.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>


## Purpose

Factor arbitrary matrix into unitary and upper triangular components

## Library

Math Functions / Matrices and Linear Algebra / Matrix Factorizations  
 dspfactors

## Description



The QR Factorization block uses a sequence of Householder transformations to triangularize the input matrix  $A$ . The block factors a column permutation of the  $M$ -by- $N$  input matrix  $A$  as

$$A_e = QR$$

The column-pivoted matrix  $A_e$  contains the columns of  $A$  permuted as indicated by the contents of length- $N$  permutation vector  $E$ .

`Ae = A(:,E)`      % Equivalent MATLAB code

The block selects a column permutation vector  $E$ , which ensures that the diagonal elements of matrix  $R$  are arranged in order of decreasing magnitude.

$$|r_{i+1,j+1}| < |r_{i,j}| \quad i = j$$

The size of matrices  $Q$  and  $R$  depends on the setting of the **Output size** parameter:

- When you select **Economy** for the output size,  $Q$  is an  $M$ -by- $\min(M,N)$  unitary matrix, and  $R$  is a  $\min(M,N)$ -by- $N$  upper-triangular matrix.

`[Q R E] = qr(A,0)`      % Equivalent MATLAB code

- When you select **Full** for the output size,  $Q$  is an  $M$ -by- $M$  unitary matrix, and  $R$  is a  $M$ -by- $N$  upper-triangular matrix.

`[Q R E] = qr(A)`      % Equivalent MATLAB code

The block treats length- $M$  unoriented vector input as an  $M$ -by-1 matrix.

# QR Factorization

---

QR factorization is an important tool for solving linear systems of equations because of good error propagation properties and the invertability of unitary matrices:

$$Q^{-1} = Q'$$

where  $Q'$  is the complex conjugate transpose of  $Q$ .


Unlike LU and Cholesky factorizations, the matrix  $A$  does not need to be square for QR factorization. However, QR factorization requires twice as many operations as LU Factorization (Gaussian elimination).

## Examples

The **Output size** parameter of the QR factorization block has two settings: **Economy** and **Full**. When the  $M$ -by- $N$  input matrix  $A$  has dimensions such that  $M > N$ , the dimensions of output matrices  $Q$  and  $R$  differ depending on the setting of the **Output size** parameter. If, however, the size of the input matrix  $A$  is such that  $M \leq N$ , output matrices  $Q$  and  $R$  have the same dimensions, regardless of whether the **Output size** is set to **Economy** or **Full**.

The input to the QR Factorization block in the following model is a 5-by-2 matrix  $A$ . When you change the setting of the **Output size** parameter from **Economy** to **Full**, the dimensions of the output given by the QR Factorization block also change.


- 1 Open the model by typing `ex_qrfactorization_ref` at the MATLAB command line.
- 2 Double-click the QR Factorization block, set the **Output size** parameter to **Economy**, and run the model.



The QR Factorization block outputs a 5-by-2 matrix  $Q$  and a 2-by-2 matrix  $R$ .


- 3 Change the **Output size** parameter of the QR Factorization block to Full and rerun the model.

# QR Factorization



The QR Factorization block outputs a 5-by-5 matrix  $Q$  and a 5-by-2 matrix  $R$ .

## Dialog Box



### Output size

Specify the size of output matrices  $Q$  and  $R$ :

- **Economy** — When this output size is selected, the block outputs an  $M$ -by- $\min(M,N)$  unitary matrix  $Q$  and a  $\min(M,N)$ -by- $N$  upper-triangular matrix  $R$ .
- **Full** — When this output size is selected, the block outputs an  $M$ -by- $M$  unitary matrix  $Q$  and a  $M$ -by- $N$  upper-triangular matrix  $R$ .

## References

Golub, G. H., and C. F. Van Loan. *Matrix Computations*. 3rd ed. Baltimore, MD: Johns Hopkins University Press, 1996.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> </ul>
Output	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> </ul>

# QR Factorization

---

## See Also

Cholesky Factorization	DSP System Toolbox
LU Factorization	DSP System Toolbox
QR Solver	DSP System Toolbox
Singular Value Decomposition	DSP System Toolbox
qr	MATLAB

See “Matrix Factorizations” for related information.


## Purpose

Find minimum-norm-residual solution to  $AX=B$

## Library

Math Functions / Matrices and Linear Algebra / Linear System Solvers  
dpsolvers

## Description



The QR Solver block solves the linear system  $AX=B$ , which can be overdetermined, underdetermined, or exactly determined. The system is solved by applying QR factorization to the M-by-N matrix, A, at the A port. The input to the B port is the right side M-by-L matrix, B. The block treats length-M unoriented vector input as an M-by-1 matrix.

The output at the x port is the N-by-L matrix, X. X is chosen to minimize the sum of the squares of the elements of  $B-AX$ . When B is a vector, this solution minimizes the vector 2-norm of the residual ( $B-AX$  is the residual). When B is a matrix, this solution minimizes the matrix Frobenius norm of the residual. In this case, the columns of X are the solutions to the L corresponding systems  $AX_k=B_k$ , where  $B_k$  is the kth column of B, and  $X_k$  is the kth column of X.

X is known as the minimum-norm-residual solution to  $AX=B$ . The minimum-norm-residual solution is unique for overdetermined and exactly determined linear systems, but it is not unique for underdetermined linear systems. Thus when the QR Solver is applied to an underdetermined system, the output X is chosen such that the number of nonzero entries in X is minimized.

## Algorithm

QR factorization factors a column-permuted variant ( $A_e$ ) of the M-by-N input matrix A as

$$A_e = QR$$

where Q is a M-by- $\min(M,N)$  unitary matrix, and R is a  $\min(M,N)$ -by-N upper-triangular matrix.

The factored matrix is substituted for  $A_e$  in

$$A_e X = B_e$$

# QR Solver


---

and

$$QRX = B_e$$

is solved for X by noting that  $Q^{-1} = Q^*$  and substituting  $Y = Q^*B_e$ . This requires computing a matrix multiplication for Y and solving a triangular system for X.

$$RX = Y$$



## Dialog Box

## Supported Data Types

- Double-precision floating point
- Single-precision floating point

## See Also

Levinson-Durbin	DSP System Toolbox
LDL Solver	DSP System Toolbox
LU Solver	DSP System Toolbox
QR Factorization	DSP System Toolbox
SVD Solver	DSP System Toolbox

See “Linear System Solvers” for related information.


<b>Purpose</b>	Discretize input at specified interval
<b>Library</b>	Quantizers dspquant2
<b>Description</b>	The Quantizer block is an implementation of the Simulink Quantizer block. See Quantizer for more information.

# Queue

**Purpose** Store inputs in FIFO register


**Library** Signal Management / Buffers  
dsbuff3

## Description



The Queue block stores a sequence of input samples in a first in, first out (FIFO) register. The register capacity is set by the **Register size** parameter, and inputs can be scalars, vectors, or matrices.

The block *pushes* the input at the In port onto the end of the queue when a trigger event is received at the Push port. When a trigger event is received at the Pop port, the block *pops* the first element off the queue and holds the Out port at that value. The first input to be pushed onto the queue is always the first to be popped off.



A trigger event at the optional **Rst** port empties the queue contents. When you select **Clear output port on reset**, then a trigger event at the **Rst** port empties the queue *and* sets the value at the **Out** port to zero. This setting also applies when a disabled subsystem containing the Queue block is reenabled; the **Out** port value is only reset to zero in this case when you select **Clear output port on reset**.

When you select the **Allow direct feedthrough** check box and two or more of the control input ports are triggered at the same time step, the operations are executed in the following order:

- 1 Rst
- 2 Push
- 3 Pop



When you clear the **Allow direct feedthrough** check box and two or more of the control input ports are triggered at the same time step, the operations are executed in the following order:

- 1 Rst
- 2 Pop
- 3 Push



The rate of the trigger signal must be the same as the rate of the data signal input. You specify the triggering event for the Push, Pop, and Rst ports by the **Trigger type** pop-up menu:

- **Rising edge** — Triggers execution of the block when the trigger input does one of the following:
  - Rises from a negative value to a positive value or zero
  - Rises from zero to a positive value, where the rise is not a continuation of a rise from a negative value to zero; see the following figure

# Queue



- Falling edge — Triggers execution of the block when the trigger input does one of the following:
  - Falls from a positive value to a negative value or zero
  - Falls from zero to a negative value, where the fall is not a continuation of a fall from a positive value to zero; see the following figure



- Either edge — Triggers execution of the block when the trigger input is a Rising edge or Falling edge (as described above).
- Non-zero sample — Triggers execution of the block at each sample time that the trigger input is not zero.

---

**Note** If your model contains any referenced models that use a Queue block with the **Push onto full register** parameter set to **Dynamic reallocation**, you cannot simulate your top-level model in Simulink Accelerator mode.

---

The **Push onto full register** parameter specifies the block's behavior when a trigger is received at the Push port but the register is full. The **Pop empty register** parameter specifies the block's behavior when a trigger is received at the Pop port but the register is empty. The following options are available for both cases:

- **Ignore** — Ignore the trigger event, and continue the simulation.
- **Warning** — Ignore the trigger event, but display a warning message in the MATLAB Command Window.
- **Error** — Display an error dialog box and terminate the simulation.

---

**Note** The **Push onto full register** and **Pop empty register** parameters are diagnostic parameters. Like all diagnostic parameters on the Configuration Parameters dialog box, they are set to **Ignore** in the code generated for this block by Simulink Coder code generation software.

---

The **Push onto full register** parameter additionally offers the **Dynamic reallocation** option, which dynamically resizes the register to accept as many additional inputs as memory permits. To find out how many elements are on the queue at a given time, enable the Num output port by selecting the **Show number of register entries port** parameter.

# Queue

---






**Note** When Dynamic reallocation is selected, the **System target file** parameter on the **Code Generation** pane of the Model Configuration Parameters dialog box must be set to `grt_malloc.tlc` Generic Real-Time Target with dynamic memory allocation.

---

## Examples

### Example 1

The table below illustrates the Queue block's operation for a **Register size** of 4, **Trigger type** of **Either edge**, and **Clear output port on reset** enabled. Because the block triggers on both rising and falling edges in this example, each transition from 1 to 0 or 0 to 1 in the Push, Pop, and Rst columns below represents a distinct trigger event. A 1 in the Empty column indicates an empty queue, while a 1 in the Full column indicates a full queue.

In	Push	Pop	Rst	Queue	Out	Empty	Full	Num
1	0	0	0	top  bottom	0	1	0	0
2	1	0	0	top  bottom	0	0	0	1
3	0	0	0	top  bottom	0	0	0	2
4	1	0	0	top  bottom	0	0	0	3
5	0	0	0	top  bottom	0	0	1	4
6	0	1	0	top  bottom	2	0	0	3
7	0	0	0	top  bottom	3	0	0	2
8	0	1	0	top  bottom	4	0	0	1


In	Push	Pop	Rst	Queue	Out	Empty	Full	Num
9	0	0	0		5	1	0	0
10	1	0	0		5	0	0	1
11	0	0	0		5	0	0	2
12	1	0	1		0	0	0	1

Note that at the last step shown, the Push and Rst ports are triggered simultaneously. The Rst trigger takes precedence, and the queue is first cleared and then pushed.

## Example 2

The dspqdemo example provides another example of the operation of the Queue block.

# Queue



## Dialog Box

### Register size

The number of entries that the FIFO register can hold.

### Trigger type

The type of event that triggers the block's execution. The rate of the trigger signal must be the same as the rate of the data signal input.

**Push onto full register**

Response to a trigger received at the Push port when the register is full. Inputs to this port must have the same built-in data type as inputs to the Pop and Rst input ports.

When Dynamic reallocation is selected, the **System target file** parameter on the **Code Generation** pane of the Model Configuration Parameters dialog box must be set to `grt_malloc.tlc` Generic Real-Time Target with dynamic memory allocation.

**Pop empty register**

Response to a trigger received at the Pop port when the register is empty. Inputs to this port must have the same built-in data type as inputs to the Push and Rst input ports.

**Show empty register indicator port**

Enable the Empty output port, which is high (1) when the queue is empty, and low (0) otherwise.

**Show full register indicator port**

Enable the Full output port, which is high (1) when the queue is full, and low (0) otherwise. The Full port remains low when you select Dynamic reallocation from the **Push onto full register** parameter.

**Show number of register entries port**

Enable the Num output port, which tracks the number of entries currently on the queue. When inputs to the In port are double-precision values, the outputs from the Num port are double-precision values. Otherwise, the outputs from the Num port are 32-bit unsigned integer values.

**Show reset port to clear internal stack buffer**

Enable the Rst input port, which empties the queue when the trigger specified by the **Trigger type** is received. Inputs to this port must have the same built-in data type as inputs to the Push and Pop input ports.

## Clear output port on reset

Reset the Out port to zero, in addition to clearing the queue, when a trigger is received at the Rst input port.

## Allow direct feedthrough

When you select this check box, the input data is available immediately at the output port of the block. You can turn off direct feedthrough and delay the input data by an extra frame by clearing the **Allow direct feedthrough** check box.

## Supported Data Types

Port	Supported Data Types
In	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Push	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul> <p>Inputs to this port must have the same built-in data type as inputs to the Pop and Rst input ports</p>

Port	Supported Data Types
Pop	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul> <p>Inputs to this port must have the same built-in data type as inputs to the Push and Rst input ports.</p>
Rst	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul> <p>Inputs to this port must have the same built-in data type as inputs to the Push and Pop input ports.</p>
Out	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Empty	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Boolean</li></ul>

# Queue

---

Port	Supported Data Types
Full	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Boolean</li></ul>
Num	<ul style="list-style-type: none"><li>• Double-precision floating point The block outputs a double-precision floating-point value at this port when the data type of the In port is double-precision floating-point.</li><li>• 32-bit unsigned integers The block outputs a 32-bit unsigned integer value at this port when the data type of the In port is anything other than double-precision floating-point.</li></ul>

## See Also

Buffer	DSP System Toolbox
Delay Line	DSP System Toolbox
Stack	DSP System Toolbox

**Purpose** Generate randomly distributed values

**Library** Sources  
dspsrcs4

## Description



The Random Source block generates a frame of  $M$  values drawn from a uniform or Gaussian pseudorandom distribution, where you specify  $M$  in the **Samples per frame** parameter.

This reference page contains a detailed discussion of the following Random Source block topics:

- “Distribution Type” on page 2-1253
- “Output Complexity” on page 2-1254
- “Output Repeatability” on page 2-1256
- “Specifying the Initial Seed” on page 2-1256
- “Sample Period” on page 2-1257
- “Dialog Box” on page 2-1258
- “Supported Data Types” on page 2-1261
- “See Also” on page 2-1261

### Distribution Type

When the **Source type** parameter is set to **Uniform**, the output samples are drawn from a uniform distribution whose minimum and maximum values are specified by the **Minimum** and **Maximum** parameters, respectively. All values in this range are equally likely to be selected. A length- $N$  vector specified for one or both of these parameters generates an  $N$ -channel output ( $M$ -by- $N$  matrix) containing a unique random distribution in each channel.

For example, specify

- **Minimum** = [ 0 0 -3 -3]

# Random Source

---

- **Maximum** = [10 10 20 20]

to generate a four-channel output whose first and second columns contain random values in the range [0, 10], and whose third and fourth columns contain random values in the range [-3, 20]. When you specify only one of the **Minimum** and **Maximum** parameters as a vector, the block scalar expands the other parameter so it is the same length as the vector.

When the **Source type** parameter is set to **Gaussian**, you must also set the **Method** parameter, which determines the method by which the block computes the output, and has the following settings:

- **Ziggurat** — Produces Gaussian random values by using the Ziggurat method.
- **Sum of uniform values** — Produces Gaussian random values by adding and scaling uniformly distributed random signals based on the central limit theorem. This theorem states that the probability distribution of the sum of a sufficiently high number of random variables approaches the Gaussian distribution. You must set the **Number of uniform values to sum** parameter, which determines the number of uniformly distributed random numbers to sum to produce a single Gaussian random value.

For both settings of the **Method** parameter, the output samples are drawn from the normal distribution defined by the **Mean** and **Variance** parameters. A length-N vector specified for one or both of the **Mean** and **Variance** parameters generates an N-channel output (M-by-N frame matrix) containing a distinct random distribution in each column. When you specify only one of these parameters as a vector, the block scalar expands the other parameter so it is the same length as the vector.

## Output Complexity

The block's output can be either real or complex, as determined by the **Real** and **Complex** options in the **Complexity** parameter. These settings control all channels of the output, so real and complex data cannot be combined in the same output. For complex output with a

Uniform distribution, the real and imaginary components in each channel are both drawn from the same uniform random distribution, defined by the **Minimum** and **Maximum** parameters for that channel.

For complex output with a **Gaussian** distribution, the real and imaginary components in each channel are drawn from normal distributions with different means. In this case, the **Mean** parameter for each channel should specify a complex value; the real component of the **Mean** parameter specifies the mean of the real components in the channel, while the imaginary component specifies the mean of the imaginary components in the channel. When either the real or imaginary component is omitted from the **Mean** parameter, a default value of 0 is used for the mean of that component.

For example, a **Mean** parameter setting of [5+2i 0.5 3i] generates a three-channel output with the following means.

Channel 1 mean	<i>real</i> = 5	<i>imaginary</i> = 2
Channel 2 mean	<i>real</i> = 0.5	<i>imaginary</i> = 0
Channel 3 mean	<i>real</i> = 0	<i>imaginary</i> = 3

For complex output, the **Variance** parameter,  $\sigma^2$ , specifies the *total variance* for each output channel. This is the sum of the variances of the real and imaginary components in that channel.

$$\sigma^2 = \sigma_{\text{Re}}^2 + \sigma_{\text{Im}}^2$$

The specified variance is equally divided between the real and imaginary components, so that

$$\sigma_{\text{Re}}^2 = \frac{\sigma^2}{2}$$
$$\sigma_{\text{Im}}^2 = \frac{\sigma^2}{2}$$

## Output Repeatability

The **Repeatability** parameter determines whether or not the block outputs the same signal each time you run the simulation. You can set the parameter to one of the following options:

- **Repeatable** — Outputs the same signal each time you run the simulation. The first time you run the simulation, the block randomly selects an initial seed. The block reuses these same initial seeds every time you rerun the simulation.
- **Specify seed** — Outputs the same signal each time you run the simulation. Every time you run the simulation, the block uses the initial seed(s) specified in the **Initial seed** parameter. Also see “Specifying the Initial Seed” on page 2-1256.
- **Not repeatable** — Does not output the same signal each time you run the simulation. Every time you run the simulation, the block randomly selects an initial seed.

## Specifying the Initial Seed

When you set the **Repeatability** parameter to **Specify seed**, you must set the **Initial seed** parameter. The **Initial seed** parameter specifies the initial seed for the pseudorandom number generator. The generator produces an identical sequence of pseudorandom numbers each time it is executed with a particular initial seed.

## Specifying Initial Seeds for Real Outputs

To specify the N initial seeds for an N-channel real-valued output, **Complexity** parameter set to **Real**, provide one of the following in the **Initial seed** parameter:


- **Length-N vector of initial seeds** — Uses each vector element as an initial seed for the corresponding channel in the N-channel output.
- **Single scalar** — Uses the scalar to generate N random values, which it uses as the seeds for the N-channel output.

## Specifying Initial Seeds for Complex Outputs

To specify the initial seeds for an N-channel complex-valued output, **Complexity** parameter set to **Complex**, provide one of the following in the **Initial seed** parameter:

- Length-N vector of initial seeds — Uses each vector element as an initial seed for generating N channels of *real* random values. The block uses pairs of adjacent values in each of these channels as the real and imaginary components of the final output, as illustrated in the following figure.
- Single scalar — Uses the scalar to generate N random values, which it uses as the seeds for generating N channels of *real* random values. The block uses pairs of adjacent values in each of these channels as the real and imaginary components of the final output, as illustrated in the following figure.

Use N channels of real random values to create the N-channel complex random output.



## Sample Period

The **Sample time** parameter value,  $T_s$ , specifies the random sequence sample period when the **Sample mode** parameter is set to **Discrete**. In this mode, the block generates the number of samples specified by the **Samples per frame** parameter value,  $M$ , and outputs this frame



# Random Source

with a period of  $M \cdot T_s$ . For  $M=1$ , the output is sample based; otherwise, the output is frame based.

When **Sample mode** is set to Continuous, the block is configured for continuous-time operation, and the **Sample time** and **Samples per frame** parameters are disabled. Note that many DSP System Toolbox blocks do not accept continuous-time inputs.

## Dialog Box

Only some of the parameters described below are visible in the dialog box at any one time.



**Source type**

The distribution from which to draw the random values, **Uniform** or **Gaussian**. For more information, see “Distribution Type” on page 2-1253.

**Method**

The method by which the block computes the Gaussian random values, **Ziggurat** or **Sum of uniform values**. This parameter is enabled when **Source type** is set to **Gaussian**. For more information, see “Distribution Type” on page 2-1253.

**Minimum**

The minimum value in the uniform distribution. This parameter is enabled when you select **Uniform** from the **Source type** parameter. Tunable.

**Maximum**

The maximum value in the uniform distribution. This parameter is enabled when you select you select **Uniform** from the **Source type** parameter. Tunable.

**Number of uniform values to sum**

The number of uniformly distributed random values to sum to compute a single number in a Gaussian random distribution. This parameter is enabled when the **Source type** parameter is set to **Gaussian**, and the **Method** parameter is set to **Sum of uniform values**. For more information, see “Distribution Type” on page 2-1253.

**Mean**

The mean of the Gaussian (normal) distribution. This parameter is enabled when you select **Gaussian** from the **Source type** parameter. Tunable.

**Variance**

The variance of the Gaussian (normal) distribution. This parameter is enabled when you select **Gaussian** from the **Source type** parameter. Tunable.

## Repeatability

The repeatability of the block output: **Not repeatable**, **Repeatable**, or **Specify seed**. In the **Repeatable** and **Specify seed** settings, the block outputs the same signal every time you run the simulation. For details, see “Output Repeatability” on page 2-1256.

## Initial seed

The initial seed(s) to use for the random number generator when you set the **Repeatability** parameter to **Specify seed**. For details, see “Specifying the Initial Seed” on page 2-1256. Tunable.

## Inherit output port attributes

When you select this check box, block inherits the sample mode, sample time, output data type, complexity, and signal dimensions of a sample-based signal from a downstream block. When you select this check box, the **Sample mode**, **Sample time**, **Samples per frame**, **Output data type**, and **Complexity** parameters are disabled.

Suppose you want to back propagate a 1-D vector. The output of the Random Source block is a length  $M$  sample-based 1-D vector, where length  $M$  is inherited from the downstream block. When the **Minimum**, **Maximum**, **Mean**, or **Variance** parameter specifies  $N$  channels, the 1-D vector output contains  $M/N$  samples from each channel. An error occurs in this case when  $M$  is not an integer multiple of  $N$ .

Suppose you want to back propagate a  $M$ -by- $N$  signal. When  $N > 1$ , your signal has  $N$  channels. When  $N = 1$ , your signal has  $M$  channels. The value of the **Minimum**, **Maximum**, **Mean**, or **Variance** parameter can be a scalar or a vector of length equal to the number of channels. You can specify these parameters as either row or column vectors, except when the signal is a row vector. In this case, the **Minimum**, **Maximum**, **Mean**, or **Variance** parameter must also be specified as a row vector.

## Sample mode

The sample mode, Continuous or Discrete. This parameter is enabled when the **Inherit output port attributes** check box is cleared.

## Sample time

The sample period,  $T_s$ , of the random output sequence. The output frame period is  $M \cdot T_s$ . This parameter is enabled when the **Inherit output port attributes** check box is cleared.

## Samples per frame

The number of samples,  $M$ , in each output frame. When the value of this parameter is 1, the block outputs a sample-based signal.

This parameter is enabled when the **Inherit output port attributes** check box is cleared.

## Output data type

The data type of the output, single-precision or double-precision. This parameter is enabled when the **Inherit output port attributes** check box is cleared.

## Complexity

The complexity of the output, Real or Complex. This parameter is enabled when the **Inherit output port attributes** check box is cleared.

## Supported Data Types

- Double-precision floating-point
- Single-precision floating-point

## See Also

Discrete Impulse	DSP System Toolbox
Maximum	DSP System Toolbox
Minimum	DSP System Toolbox

## Random Source


---

Signal From Workspace	DSP System Toolbox
Standard Deviation	DSP System Toolbox
Variance	DSP System Toolbox
Constant	Simulink
Random Number	Simulink
Signal Generator	Simulink
rand	MATLAB
randn	MATLAB
RandStream	MATLAB

**Purpose** Compute real cepstrum of input

**Library** Transforms  
dspxfm3

## Description



The Real Cepstrum block computes the real cepstrum of each column in the real-valued  $M$ -by- $N$  input matrix,  $u$ . The block treats each column of the input as an independent channel containing  $M$  consecutive samples. The block does not accept complex-valued inputs.

The output is a real  $M_o$ -by- $N$  matrix, where you specify  $M_o$  in the **FFT length** parameter. Each output column contains the length- $M_o$  real cepstrum of the corresponding input column.

```
y = real(ifft(log(abs(fft(u,M0)))))
```


or, more compactly,

```
y = rceps(u,M0)
```

When you select the **Inherit FFT length from input port dimensions** check box, the output frame size matches the input frame size ( $M_o=M$ ). In this case, the block processes *sample-based* length- $M$  row vector inputs as a single channel (that is, as an  $M$ -by-1 column vector), and returns the result as a length- $M$  column vector. The block *always* processes unoriented vector inputs as a single channel, and returns the result as a length- $M$  column vector.

The output port rate is the same as the input port rate.

# Real Cepstrum



## Dialog Box

### Inherit FFT length from input port dimensions

When you select this check box, the output frame size matches the input frame size.

### FFT length

The number of frequency points at which to compute the FFT, which is also the output frame size,  $M_o$ . This parameter is visible only when you clear the **Inherit FFT length from input port dimensions** check box.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point

## See Also

Complex Cepstrum	DSP System Toolbox
DCT	DSP System Toolbox
FFT	DSP System Toolbox
rceps	Signal Processing Toolbox

## Purpose

Compute reciprocal condition of square matrix in 1-norm

## Library

Math Functions / Matrices and Linear Algebra / Matrix Operations  
dspmtx3

## Description



The Reciprocal Condition block computes the reciprocal of the condition number for a square input matrix A.

```
y = rcond(A) % Equivalent MATLAB code
```

or

$$y = \frac{1}{\kappa} = \frac{1}{\|A^{-1}\|_1 \|A\|_1}$$



where  $\kappa$  is the condition number ( $\kappa \geq 1$ ), and  $y$  is the scalar output ( $0 \leq y < 1$ ).

The matrix 1-norm,  $\|A\|_1$ , is the maximum column-sum in the M-by-M matrix A.

$$\|A\|_1 = \max_{1 \leq j \leq M} \sum_{i=1}^M |a_{ij}|$$

For a 3-by-3 matrix:

# Reciprocal Condition



## Dialog Box

## References

Golub, G. H., and C. F. Van Loan. *Matrix Computations*. 3rd ed. Baltimore, MD: Johns Hopkins University Press, 1996.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point

## See Also

Matrix 1-Norm	DSP System Toolbox
Normalization	DSP System Toolbox
rcond	MATLAB

# Remez FIR Filter Design (Obsolete)

**Purpose** Design and apply equiripple FIR filter

**Library** dspobslib

## Description



---

**Note** The Remez FIR Filter Design block is still supported but is likely to be obsoleted in a future release. We strongly recommend replacing this block with the Digital Filter block.

---

The Remez FIR Filter Design block implements the Parks-McClellan algorithm to design and apply a linear-phase filter with an arbitrary multiband magnitude response. The filter design, which uses the Signal Processing Toolbox `firpm` function, minimizes the maximum error between the desired frequency response and the actual frequency response. Such filters are called *equiripple* due to the equiripple behavior of their approximation error. The block applies the filter to a discrete-time input using the Direct-Form II Transpose Filter block.

An  $M$ -by- $N$  sample-based matrix input is treated as  $M \times N$  independent channels, and an  $M$ -by- $N$  frame-based matrix input is treated as  $N$  independent channels. In both cases, the block filters each channel independently over time, and the output has the same size and frame status as the input.

The **Filter type** parameter allows you to specify one of the following filters:

- Multiband

The multiband filter has an arbitrary magnitude response and linear phase.

- Differentiator

The differentiator filter approximates the ideal differentiator. Differentiators are antisymmetric FIR filters with approximately linear magnitude responses. To obtain the correct derivative, scale

# Remez FIR Filter Design (Obsolete)

---

the **Gains at these frequencies** vector by  $\pi F_s$  rad/s, where  $F_s$  is the sample frequency in Hertz.

- Hilbert Transformer



The Hilbert transformer filter approximates the ideal Hilbert transformer. Hilbert transformers are antisymmetric FIR filters with approximately constant magnitude.

The **Band-edge frequency vector** parameter is a vector of frequency points in the range 0 to 1, where 1 corresponds to half the sample frequency. Each band is defined by the two bounding frequencies, so this vector must have even length. Frequency points must appear in ascending order. The **Gains at these frequencies** parameter is a vector of the same size containing the desired magnitude response at the corresponding points in the **Band-edge frequency vector**.

Each odd-indexed frequency-amplitude pair defines the left endpoint of a line segment representing the desired magnitude response in that frequency band. The corresponding even-indexed frequency-amplitude pair defines the right endpoint. Between the frequency bands specified by these end-points, there may be undefined sections of the specified frequency response. These are called “don’t care” or “transition” regions, and the magnitude response in these areas is a by-product of the optimization in the other specified frequency ranges.

# Remez FIR Filter Design (Obsolete)

$$\begin{aligned} \text{Band edge frequency} &= [0 \quad 0.3 \quad 0.4 \quad 0.6 \quad 0.7 \quad 1] \\ \text{Gains} &= [0 \quad 1 \quad 0 \quad 0 \quad 0.5 \quad 0.5] \\ \text{Band:} & \quad \underbrace{\quad}_2 \quad \underbrace{\quad}_1 \quad \underbrace{\quad}_1 \end{aligned}$$



The **Weights** parameter is a vector that specifies the emphasis to be placed on minimizing the error in certain frequency bands relative to others. This vector specifies one weight per band, so it is half the length of the **Band-edge frequency vector** and **Gains at these frequencies** vectors.

In most cases, differentiators and Hilbert transformers have only a single band, so the weight is a scalar value that does not affect the final filter. However, the **Weights** parameter is useful when using the block to design an antisymmetric multiband filter, such as a Hilbert transformer with stopbands.

## Examples

### Example 1: Multiband

Consider a lowpass filter with a transition band in the normalized frequency range 0.4 to 0.5, and 10 times greater error minimization in the stopband than in the passband.

In this case:

- **Filter type** = Multiband

# Remez FIR Filter Design (Obsolete)

---

- **Band-edge frequency vector** = [0 0.4 0.5 1]
- **Gains at these frequencies** = [1 1 0 0]
- **Weights** = [1 10]

## Example 2: Differentiator

Assume the specifications for a differentiator filter require it to have order 21. The “ramp” response extends over the entire frequency range. In this case, specify:


- **Filter type** = Differentiator
- **Band-edge frequency vector** = [0 1]
- **Gains at these frequencies** = [0 pi\*Fs]
- **Filter order** = 21

For a type III even order filter, the differentiation band should stop short of half the sample frequency. For example, if the filter order is 20, you could specify the block parameters as follows:

- **Filter type** = Differentiator
- **Band-edge frequency vector** = [0 0.9]
- **Gains at these frequencies** = [0 0.9\*pi\*Fs]
- **Filter order** = 20

# Remez FIR Filter Design (Obsolete)

## Dialog Box



### Filter type

The filter type. Tunable.

### Band-edge frequency vector

A vector of frequency points, in ascending order, in the range 0 to 1. The value 1 corresponds to half the sample frequency. This vector must have even length. Tunable.

### Gains at these frequencies

A vector of frequency-response magnitudes corresponding to the points in the **Band-edge frequency** vector. This vector must be the same length as the **Band-edge frequency** vector. Tunable.

### Weights

A vector containing one weight for each frequency band. This vector must be half the length of the **Band-edge frequency** and **Gains at these frequencies** vectors. Tunable.

# Remez FIR Filter Design (Obsolete)

---

## Filter order

The filter order.

## References


Oppenheim, A. V. and R. W. Schaffer. *Discrete-Time Signal Processing*. Englewood Cliffs, NJ: Prentice Hall, 1989.

Proakis, J. and D. Manolakis. *Digital Signal Processing*. 3rd ed. Englewood Cliffs, NJ: Prentice-Hall, 1996.

**Purpose** Resample input at higher rate by repeating values

**Library** Signal Operations  
dspops

## Description



The Repeat block upsamples each channel of the  $M_i$ -by- $N$  input to a rate  $L$  times higher than the input sample rate. To do so, the block repeats each consecutive input sample  $L$  times at the output. You specify the integer  $L$  in the **Repetition count** parameter.

You can use the Repeat block inside of triggered subsystems when you set the **Rate options** parameter to Enforce single-rate processing.

### Frame-Based Processing

When you set the **Input processing** parameter to Columns as channels (frame based), the block upsamples each column of the input over time. In this mode, the block can perform either single-rate or multirate processing. You can use the **Rate options** parameter to specify how the block upsamples the input:

- When you set the **Rate options** parameter to Enforce single-rate processing, the input and output of the block have the same sample rate. In this mode, the block outputs a signal with a proportionally larger frame *size* than the input. The block upsamples each channel independently by repeating each row of the input matrix  $L$  times at the output. For upsampling by a factor of  $L$ , the output frame size is  $L$  times larger than the input frame size ( $M_o = M_i * L$ ), but the input and output frame rates are equal.

For an example of single-rate upsampling, see Example: Single-Rate Processing on page 2-1275.

- When you set the **Rate options** parameter to Allow multirate processing, the block treats an  $M_i$ -by- $N$  matrix input as  $N$  independent channels. The block generates the output at the faster (upsampled) rate by using a proportionally shorter frame *period* at the output port than at the input port. For  $L$  repetitions of the input, the output frame period is  $L$  times shorter than the input frame

period ( $T_{fo} = T_{fi}/L$ ). In this mode, the output always has the same frame size as the input.

See Example: Multirate, Frame-Based Processing on page 2-1275 for an example that uses the Repeat block in this mode.

## Sample-Based Processing

When you set the **Input processing** parameter to `Elements as channels (sample based)`, the block treats an  $M$ -by- $N$  matrix input as  $M \times N$  independent channels, and upsamples each channel over time. The block upsamples each channel over time such that the output sample rate is  $L$  times higher than the input sample rate ( $T_{so} = T_{si}/L$ ). In this mode, the output is always the same size as the input.

## Zero Latency

The Repeat block has *zero-tasking latency* for all single-rate operations. The block is in a single-rate mode if you set the **Repetition count** parameter to 1 or if you set the **Input processing** parameter to `Columns as channels (frame based)` and the **Rate options** parameter to `Enforce single-rate processing`.

The Repeat block also has zero-tasking latency for multirate operations if you run your model in Simulink single-tasking mode.

Zero-tasking latency means that the block repeats the first input (received at  $t=0$ ) for the first  $L$  output samples, the second input for the next  $L$  output samples, and so on.

## Nonzero Latency

The Repeat block has tasking latency for multirate, multitasking operation:

- In multirate, sample-based processing mode, the initial condition for each channel is repeated for the first  $L$  output samples. The channel's first input appears as output sample  $L+1$ . The **Initial conditions** parameter can be an  $M_i$ -by- $N$  matrix containing one value for each channel, or a scalar to be applied to all signal channels.

- In multirate, frame-based processing mode, the first row of the initial condition matrix is repeated for the first  $L$  output samples, the second row of the initial condition matrix is repeated for the next  $L$  output samples, and so on. The first row of the first input matrix appears in the output as sample  $M_1L+1$ . The **Initial conditions** parameter can be an  $M_1$ -by- $N$  matrix, or a scalar to be repeated across all elements of the  $M_1$ -by- $N$  matrix.

---


**Note** For more information on latency and the Simulink tasking modes, see “Excess Algorithmic Delay (Tasking Latency)” and “Scheduling” in the *Simulink Coder User’s Guide*.

---

## Examples

### Example: Single-Rate Processing



In the `ex_repeat_ref2` model, the Repeat block resamples a single-channel input with a frame size of 16. The block repeats input values to upsample the input by a factor of 4. Thus, the output of the block has a frame size of 64. The input and output frame rates are identical.



### Example: Multirate, Frame-Based Processing

In the `ex_repeat_ref1` model, the Repeat block resamples a single-channel input with a frame period of 1 second. The block repeats input values to upsample the input by a factor of 4. Thus, the output of the block has a frame period of 0.25 seconds. The input and output frame sizes are identical.

# Repeat



## Dialog Box

### Repetition count

The integer number of times,  $L$ , that the input value is repeated at the output. This is the factor by which the block increases the output frame size or sample rate.

### Input processing

Specify how the block should process the input. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate

---

channel. In this mode, the block can perform single-rate or multirate processing.

- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel. In this mode, the block always performs multirate processing.

---

**Note** The option **Inherit from input** (this choice will be removed - see release notes) will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

### Rate options

Specify the method by which the block upsamples the input. You can select one of the following options:

- **Enforce single-rate processing** — When you select this option, the block maintains the input sample rate by increasing the output frame size by a factor of  $L$ . To select this option, you must set the **Input processing** parameter to **Columns as channels (frame based)**.
- **Allow multirate processing** — When you select this option, the block resamples the signal such that the output sample rate is  $L$  times faster than the input sample rate.

### Initial conditions

The value with which the block is initialized for cases of nonzero latency; a scalar or matrix. This parameter appears only when you configure the block to perform multirate processing.

# Repeat

---

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

## See Also

FIR Interpolation

DSP System Toolbox

Upsample


DSP System Toolbox

# RLS Adaptive Filter (Obsolete)

**Purpose** Compute filter estimates for input using RLS adaptive filter algorithm

**Library** dspobslib

## Description



**Note** The RLS Adaptive Filter block is still supported but is likely to be obsoleted in a future release. We strongly recommend replacing this block with the RLS Filter block.

The RLS Adaptive Filter block recursively computes the recursive least squares (RLS) estimate of the FIR filter coefficients.

The corresponding RLS filter is expressed in matrix form as

$$k(n) = \frac{\lambda^{-1}P(n-1)u(n)}{1 + \lambda^{-1}u^H(n)P(n-1)u(n)}$$

$$y(n) = \bar{w}^H(n-1)u(n)$$

$$e(n) = d(n) - y(n)$$

$$\bar{w}(n) = \bar{w}(n-1) + k(n)e^*(n)$$

$$P(n) = \lambda^{-1}P(n-1) - \lambda^{-1}k(n)u^H(n)P(n-1)$$

where  $\lambda^{-1}$  denotes the reciprocal of the exponential weighting factor. The variables are as follows

Variable	Description
$n$	The current algorithm iteration
$u(n)$	The buffered input samples at step $n$
$P(n)$	The inverse correlation matrix at step $n$
$k(n)$	The gain vector at step $n$
$\bar{w}(n)$	The vector of filter-tap estimates at step $n$

# RLS Adaptive Filter (Obsolete)

Variable	Description
$y(n)$	The filtered output at step $n$
$e(n)$	The estimation error at step $n$
$d(n)$	The desired response at step $n$
$\lambda$	The exponential memory weighting factor

The block icon has port labels corresponding to the inputs and outputs of the RLS algorithm. Note that inputs to the In and Err ports must be sample-based scalars. The signal at the Out port is a scalar, while the signal at the Taps port is a sample-based vector.

Block Ports	Corresponding Variables
In	$u$ , the scalar input, which is internally buffered into the vector $u(n)$
Out	$y(n)$ , the filtered scalar output
Err	$e(n)$ , the scalar estimation error
Taps	$\hat{w}(0)$ , the vector of filter-tap estimates

An optional Adapt input port is added when you select the **Adapt input** check box in the dialog box. When this port is enabled, the block continuously adapts the filter coefficients while the Adapt input is nonzero. A zero-valued input to the Adapt port causes the block to stop adapting, and to hold the filter coefficients at their current values until the next nonzero Adapt input.

The implementation of the algorithm in the block is optimized by exploiting the symmetry of the inverse correlation matrix  $P(n)$ . This decreases the total number of computations by a factor of two.

The **FIR filter length** parameter specifies the length of the filter that the RLS algorithm estimates. The **Memory weighting factor** corresponds to  $\lambda$  in the equations, and specifies how quickly the filter

“forgets” past sample information. Setting  $\lambda=1$  specifies an infinite memory; typically,  $0.95 \leq \lambda \leq 1$ .

The **Initial value of filter taps** specifies the initial value  $\hat{w}(0)$  as a vector, or as a scalar to be repeated for all vector elements. The initial value of  $P(n)$  is

$$I \frac{1}{\sigma^2}$$


where you specify  $\sigma^2$  in the **Initial input variance estimate** parameter.

## Examples

The `r1sdemo` example illustrates a noise cancellation system built around the RLS Adaptive Filter block.

# RLS Adaptive Filter (Obsolete)

## Dialog Box



### **FIR filter length**

The length of the FIR filter.

### **Memory weighting factor**

The exponential weighting factor, in the range  $[0, 1]$ . A value of 1 specifies an infinite memory. Tunable.

### **Initial value of filter taps**

The initial FIR filter coefficients.

### **Initial input variance estimate**

The initial value of  $1/P(n)$ .

### **Adapt input**

Enables the Adapt port.

## References

Haykin, S. *Adaptive Filter Theory*. 3rd ed. Englewood Cliffs, NJ: Prentice Hall, 1996.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point

## See Also

Kalman Adaptive Filter (Obsolete)      DSP System Toolbox

LMS Adaptive Filter (Obsolete)      DSP System Toolbox

See “Adaptive Filters in Simulink” for related information.

# RLS Filter

## Purpose


Compute filtered output, filter error, and filter weights for given input and desired signal using RLS adaptive filter algorithm

## Library

Filtering / Adaptive Filters

dspadpt3

## Description



The RLS Filter block recursively computes the least squares estimate (RLS) of the FIR filter weights. The block estimates the filter weights, or coefficients, needed to convert the input signal into the desired signal. Connect the signal you want to filter to the Input port. The input signal can be a scalar or a column vector. Connect the signal you want to model to the Desired port. The desired signal must have the same data type, complexity, and dimensions as the input signal. The Output port outputs the filtered input signal. The Error port outputs the result of subtracting the output signal from the desired signal.

The corresponding RLS filter is expressed in matrix form as

$$\mathbf{k}(n) = \frac{\lambda^{-1} \mathbf{P}(n-1) \mathbf{u}(n)}{1 + \lambda^{-1} \mathbf{u}^H(n) \mathbf{P}(n-1) \mathbf{u}(n)}$$

$$y(n) = \mathbf{w}(n-1) \mathbf{u}(n)$$

$$e(n) = d(n) - y(n)$$

$$\mathbf{w}(n) = \mathbf{w}(n-1) + \mathbf{k}^H(n) e(n)$$

$$\mathbf{P}(n) = \lambda^{-1} \mathbf{P}(n-1) - \lambda^{-1} \mathbf{k}(n) \mathbf{u}^H(n) \mathbf{P}(n-1)$$

where  $\lambda^{-1}$  denotes the reciprocal of the exponential weighting factor. The variables are as follows

Variable	Description
$n$	The current time index
$\mathbf{u}(n)$	The vector of buffered input samples at step $n$
$\mathbf{P}(n)$	The inverse correlation matrix at step $n$

Variable	Description
$\mathbf{k}(n)$	The gain vector at step $n$
$\mathbf{w}(n)$	The vector of filter-tap estimates at step $n$
$y(n)$	The filtered output at step $n$
$e(n)$	The estimation error at step $n$
$d(n)$	The desired response at step $n$
$\lambda$	The forgetting factor

The implementation of the algorithm in the block is optimized by exploiting the symmetry of the inverse correlation matrix  $P(n)$ . This decreases the total number of computations by a factor of two.

Use the **Filter length** parameter to specify the length of the filter weights vector.

The **Forgetting factor (0 to 1)** parameter corresponds to  $\lambda$  in the equations. It specifies how quickly the filter “forgets” past sample information. Setting  $\lambda=1$  specifies an infinite memory. Typically,

$1 - \frac{1}{2L} < \lambda < 1$ , where  $L$  is the filter length. You can specify a forgetting factor using the input port, Lambda, or enter a value in the **Forgetting factor (0 to 1)** parameter in the Block Parameters: RLS Filter dialog box.

Enter the initial filter weights,  $\hat{w}(0)$ , as a vector or a scalar for the **Initial value of filter weights** parameter. When you enter a scalar, the block uses the scalar value to create a vector of filter weights. This vector has length equal to the filter length and all of its values are equal to the scalar value.

The initial value of  $P(n)$  is

$$\frac{1}{\sigma^2} I$$

# RLS Filter

---


where you specify  $\sigma^2$  in the **Initial input variance estimate** parameter.

When you select the **Adapt port** check box, an Adapt port appears on the block. When the input to this port is nonzero, the block continuously updates the filter weights. When the input to this port is zero, the filter weights remain at their current values.


When you want to reset the value of the filter weights to their initial values, use the **Reset input** parameter. The block resets the filter weights whenever a reset event is detected at the Reset port. The reset signal rate must be the same rate as the data signal input.

From the **Reset input** list, select None to disable the Reset port. To enable the Reset port, select one of the following from the **Reset input** list:

- **Rising edge** — Triggers a reset operation when the Reset input does one of the following:
  - Rises from a negative value to a positive value or zero
  - Rises from zero to a positive value, where the rise is not a continuation of a rise from a negative value to zero; see the following figure



- **Falling edge** — Triggers a reset operation when the Reset input does one of the following:
  - Falls from a positive value to a negative value or zero
  - Falls from zero to a negative value, where the fall is not a continuation of a fall from a positive value to zero; see the following figure




- **Either edge** — Triggers a reset operation when the Reset input is a Rising edge or Falling edge, as described above
- **Non-zero sample** — Triggers a reset operation at each sample time that the Reset input is not zero

Select the **Output filter weights** check box to create a Wts port on the block. For each iteration, the block outputs the current updated filter weights from this port.

## Examples

The `r1sdemo` example illustrates a noise cancellation system built around the RLS Filter block.

# RLS Filter



## Dialog Box

### Filter length

Enter the length of the FIR filter weights vector.

### Specify forgetting factor via

Select **Dialog** to enter a value for the forgetting factor in the Block parameters: RLS Filter dialog box. Select **Input port** to specify the forgetting factor using the Lambda input port.

**Forgetting factor (0 to 1)**

Enter the exponential weighting factor in the range  $0 \leq \lambda \leq 1$ . A value of 1 specifies an infinite memory. Tunable.

**Initial value of filter weights**

Specify the initial values of the FIR filter weights.

**Initial input variance estimate**

The initial value of  $1/P(n)$ .

**Adapt port**

Select this check box to enable the Adapt input port.

**Reset input**

Select this check box to enable the Reset input port.

**Output filter weights**

Select this check box to export the filter weights from the Wts port.

**References**

Hayes, M.H. *Statistical Digital Signal Processing and Modeling*. New York: John Wiley & Sons, 1996.

**Supported Data Types**

- Double-precision floating point
- Single-precision floating point

**See Also**

Kalman Adaptive Filter (Obsolete)	DSP System Toolbox
LMS Filter	DSP System Toolbox
Block LMS Filter	DSP System Toolbox
Fast Block LMS Filter	DSP System Toolbox

See “Adaptive Filters in Simulink” for related information.

## Purpose

Compute root-mean-square value of input or sequence of inputs

## Library

Statistics

dspstat3

## Description



The RMS block computes the RMS value of each row or column of the input, along vectors of a specified dimension of the input, or of the entire input. The RMS block can also track the RMS value in a sequence of inputs over a period of time. The **Running RMS** parameter selects between basic operation and running operation.

## Basic Operation

When you do not select the **Running RMS** check box, the block computes the RMS value of each row or column of the input, along vectors of a specified dimension of the input, or of the entire input at each individual sample time, and outputs the array  $y$ . Each element in  $y$  is the RMS value of the corresponding column, row, vector, or entire input. The output  $y$  depends on the setting of the **Find the RMS value over** parameter. For example, consider a 3-dimensional input signal of size  $M$ -by- $N$ -by- $P$ :

- **Entire input** — The output at each sample time is a scalar that contains the RMS value of the entire input.
- **Each row** — The output at each sample time consists of an  $M$ -by-1-by- $P$  array, where each element contains the RMS value of each vector over the second dimension of the input. For an input that is an  $M$ -by- $N$  matrix, the output at each sample time is an  $M$ -by-1 column vector.
- **Each column** — The output at each sample time consists of a 1-by- $N$ -by- $P$  array, where each element contains the RMS value of each vector over the first dimension of the input. For an input that is an  $M$ -by- $N$  matrix, the output at each sample time is a 1-by- $N$  row vector.

In this mode, the block treats length- $M$  unoriented vector inputs as  $M$ -by-1 column vectors.

- **Specified dimension** — The output at each sample time depends on **Dimension**. If **Dimension** is set to 1, the output is the same as that when you select **Each column**. If **Dimension** is set to 2, the output is the same as when you select **Each row**. If **Dimension** is set to 3, the output at each sample time is an  $M$ -by- $N$  matrix containing the RMS value of each vector over the third dimension of the input.

The RMS value of the  $j$ th column of an  $M$ -by- $N$  input matrix  $u$  is given by

$$y_j = \sqrt{\frac{\sum_{i=1}^M |u_{ij}|^2}{M}} \quad 1 \leq j \leq N$$

`y = sqrt(sum(u.*conj(u))/size(u,1))`      % Equivalent MATLAB code

## Running Operation

When you select the **Running RMS** check box, the block tracks the RMS value of successive inputs to the block. In this mode, you must also specify a value for the **Input processing** parameter:

- When you select **Elements as channels (sample based)**, the block outputs an  $M$ -by- $N$  array. Each element  $y_{ij}$  of the output contains the RMS value of the element  $u_{ij}$  over all inputs since the last reset.
- When you select **Columns as channels (frame based)**, the block outputs an  $M$ -by- $N$  matrix. Each element  $y_{ij}$  of the output contains the RMS value of the  $j$ th column over all inputs since the last reset, up to and including element  $u_{ij}$  of the current input.

## Running Operation for Variable-Size Inputs

When your inputs are of variable size, and you select the **Running RMS** check box, there are two options:

- If you set the **Input processing** parameter to `Elements as channels (sample based)`, the state is reset.
- If you set the **Input processing** parameter to `Columns as channels (frame based)`, then there are two cases:
  - When the input size difference is in the number of channels (i.e., number of columns), the state is reset.
  - When the input size difference is in the length of channels (i.e., number of rows), there is no reset and the running operation is carried out as usual.


## Resetting the Running RMS

The block resets the running RMS whenever a reset event is detected at the optional `Rst` port. The reset sample time must be a positive integer multiple of the input sample time.


When a reset event occurs while the **Input processing** parameter is set to `Elements as channels (sample based)`, the running RMS for each channel is initialized to the value in the corresponding channel of the current input. Similarly, when the **Input processing** parameter is set to `Columns as channels (frame based)`, the running RMS for each channel is initialized to the earliest value in each channel of the current input.

You specify the reset event in the **Reset port** parameter:

- `None` disables the `Rst` port.
- `Rising edge` — Triggers a reset operation when the `Rst` input does one of the following:
  - Rises from a negative value to a positive value or zero
  - Rises from zero to a positive value, where the rise is not a continuation of a rise from a negative value to zero (see the following figure)



- Falling edge — Triggers a reset operation when the Rst input does one of the following:
  - Falls from a positive value to a negative value or zero
  - Falls from zero to a negative value, where the fall is not a continuation of a fall from a positive value to zero (see the following figure)



- Either edge — Triggers a reset operation when the Rst input is a Rising edge or Falling edge, as described earlier
- Non-zero sample — Triggers a reset operation at each sample time that the Rst input is not zero


---

**Note** When running simulations in the Simulink MultiTasking mode, reset signals have a one-sample latency. Therefore, when the block detects a reset event, there is a one-sample delay at the reset port rate before the block applies the reset. For more information on latency and the Simulink tasking modes, see “Excess Algorithmic Delay (Tasking Latency)” and “Scheduling” in the *Simulink Coder User’s Guide*.


---

## Examples


In the following `ex_rms_ref` model, the RMS block calculates the running RMS of a 3-by-2 matrix input, `u`. The **Input processing** parameter is set to `Columns as channels (frame based)`, so the block processes the input as a two channel signal with a frame size of three. The running RMS is reset at  $t=2$  by an impulse to the block’s `Rst` port.



The operation of the block is shown in the following figure.



## Dialog Box



### Running RMS

Enables running operation when selected.

### Input processing

Specify how the block should process the input when computing the running RMS. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

This parameter appears only when you select the **Running RMS** check box.

---

**Note** The option *Inherit from input* (this choice will be removed - see release notes) will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

**Reset port**

Specify the reset event that causes the block to reset the running RMS. The sample time of the input to the Rst port must be a positive integer multiple of the input sample time. This parameter appears only when you select the **Running RMS** check box. For more information, see “Resetting the Running RMS” on page 2-1292.

**Find the RMS value over**

Specify whether to find the RMS value along rows, columns, entire input, or the dimension specified in the **Dimension** parameter. For more information, see “Basic Operation” on page 2-1290.

**Treat sample-based row input as a column**

Select to treat sample-based length- $M$  row vector inputs as  $M$ -by-1 column vectors. This parameter is only visible when the **Find the RMS value over** parameter is set to *Each column*.

---

**Note** This check box will be removed in a future release. See “Sample-Based Row Vector Processing Changes” in the *DSP System Toolbox Release Notes*.

---

**Dimension**

Specify the dimension (one-based value) of the input signal, over which the RMS value is computed. The value of this parameter cannot exceed the number of dimensions in the input signal. This parameter is only visible when the **Find the RMS value over** parameter is set to *Specified dimension*.

# RMS

---

## Supported Data Types

- Double-precision floating point
- Single-precision floating point
- Boolean — The block accepts Boolean inputs to the Rst port.


## See Also

Mean	DSP System Toolbox
Variance	DSP System Toolbox

**Purpose** Sample and hold input signal

**Library** Signal Operations  
dspSigOps

## Description



The Sample and Hold block acquires the input at the signal port whenever it receives a trigger event at the trigger port (marked by  $\nabla$ ). The block then holds the output at the acquired input value until the next triggering event occurs.

The trigger input must be a sample-based scalar with sample rate equal to the input frame rate at the signal port. You specify the trigger event using the **Trigger type** parameter:

- **Rising edge** triggers the block to acquire the signal input when the trigger input rises from a negative value or zero to a positive value.
- **Falling edge** triggers the block to acquire the signal input when the trigger input falls from a positive value or zero to a negative value.
- **Either edge** triggers the block to acquire the signal input when the trigger input either rises from a negative value or zero to a positive value or falls from a positive value or zero to a negative value.


You specify the block's output prior to the first trigger event using the **Initial condition** parameter. When the acquired input is an M-by-N matrix, the **Initial condition** can be an M-by-N matrix, or a scalar to be repeated across all elements of the matrix. When the input is a length-M unoriented vector, the **Initial condition** can be a length-M row or column vector, or a scalar to be repeated across all elements of the vector.

If you select the **Latch (buffer) input** check box, the block outputs the value of the input from the previous time step until the next triggering event occurs. To use this block in a loop, select this check box.

# Sample and Hold

---

## Dialog Box



### Trigger type

The type of event that triggers the block to acquire the input signal.

### Initial condition

The block's output prior to the first trigger event.

### Latch (buffer) input

If you select this check box, the block outputs the value of the input from the previous time step until the next triggering event occurs.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Trigger	<ul style="list-style-type: none"><li>• Any data type supported by the Trigger block</li></ul>
Outputs	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

## See Also

Downsample	DSP System Toolbox
N-Sample Switch	DSP System Toolbox

# Scalar Quantizer (Obsolete)

---


## Purpose

Convert input signal into set of quantized output values or index values, or convert set of index values into quantized output signal

## Library

dspobslib

## Description



---

**Note** The Scalar Quantizer block is still supported but is likely to be obsoleted in a future release. We strongly recommend replacing this block with the Scalar Quantizer Encoder block or the Scalar Quantizer Decoder block.

---

The Scalar Quantizer block has three modes of operation. In Encoder mode, the block maps each input value to a quantization region by comparing the input value to the quantizer boundary points defined in the **Boundary points** parameter. The block outputs the index of the associated region. In Decoder mode, the block transforms the input index values into quantized output values, defined in the **Codebook** parameter. In the Encoder and Decoder mode, the block performs both the encoding and decoding operations. The block outputs the index values and the quantized output values.

You can select how you want to enter the **Boundary points** and/or **Codebook** values using the **Source of quantizer** parameters. When you select **Specify via dialog**, type the parameters into the block parameters dialog box. Select **Input ports**, and port B and/or C appears on the block. In Encoder and Encoder and decoder mode, the input to port B is used as the **Boundary points**. In Decoder and Encoder and decoder mode, the input to port C is used as the **Codebook**.

In Encoder and Encoder and decoder mode, the **Boundary points** are the values used to break up the input signal into regions. Each region is specified by an index number. When your first boundary point is  $-\infty$  and your last boundary point is  $\infty$ , your quantizer is unbounded. When your first and last boundary point is finite, your

quantizer is bounded. When only your first or last boundary point is `-inf` or `inf`, your quantizer is semi-bounded.

For instance, when your input signal ranges from 0 to 11, you can create a bounded quantizer using the following boundary points:

```
[0 0.5 3.7 5.8 6.0 11]
```

The boundary points can have equal or varied spacing. Any input values between 0 and 0.5 would correspond to index 0. Input values between 0.5 and 3.7 would correspond to index 1, and so on.

Suppose you wanted to create an unbounded quantizer with the following boundary points:

```
[-inf 0 2 5.5 7.1 10 inf]
```

When your input signal has values less than 0, these values would be assigned to index 0. When your input signal has values greater than 10, these values would be assigned to index 6.

When an input value is the same as a boundary point, the **Tie-breaking rule** parameter defines the index to which the value is assigned. When you want the input value to be assigned to the lower index value, select **Choose the lower index**. To assign the input value with the higher index, select **Choose the higher index**.

In `Decoder` and `Encoder` and `decoder` mode, the **Codebook** is a vector of quantized output values that correspond to each index value.

In `Encoder` and `Encoder` and `decoder` mode, the **Searching method** determines how the appropriate quantizer index is found. Select **Linear** and the `Scalar Quantizer` block compares the input value to the first region defined by the first two boundary points. When the input value does not fall within this region, the block then compares the input value to the next region. This process continues until the input value is determined to be within a region and is associated with the appropriate index value. The computational cost of this process is of the order  $P$ , where  $P$  is the number of boundary points.

# Scalar Quantizer (Obsolete)

---

Select **Binary** for the **Searching method** and the block compares the input value to the middle value of the boundary points vector. When the input value is larger than this boundary point, the block discards the boundary points that are lower than this middle value. The block then compares the input value to the middle boundary point of the new range, defined by the remaining boundary points. This process continues until the input value is associated with the appropriate index value. The computational cost of this process is of the order  $\log_2 P$ , where  $P$  is the number of boundary points. In most cases, the **Binary** option is faster than the **Linear** option.

In **Decoder** mode, the input to this block is a vector of index values, where  $0 \leq \text{index} < N$  and  $N$  is the length of the codebook vector. Use the **Action for out of range input** parameter to determine what happens when an input index value is out of this range. When you want any index values less than 0 to be set to 0 and any index values greater than or equal to  $N$  to be set to  $N - 1$ , select **Clip**. When you want to be warned when any index values less than 0 are set to 0 and any index values greater than or equal to  $N$  are set to  $N - 1$ , select **Clip and warn**. When you want the simulation to stop and display an error when the index values are out of range, select **Error**.

In **Encoder** and **decoder** mode, you can select the **Output the quantization error** check box. The quantization error is the difference between the input value and the quantized output value. Select this check box to output the quantization error for each input value from the **Err** port on this block.

## Data Type Support

In **Encoder** mode, the input data values and the boundary points can be the input to the block at ports **U** and **B**. Similarly, in **Encoder** and **decoder** mode, the codebook values can also be the input to the block at port **C**. The data type of the input data values, boundary points, and codebook values can be **double**, **single**, **uint8**, **uint16**, **uint32**, **int8**, **int16**, or **int32**. In **Decoder** mode, the input to the block can be the index values and the codebook values. The data type of the index input to the block at port **Idx** can be **uint8**, **uint16**, **uint32**, **int8**, **int16**, or

int32. The data type of the codebook values can be double, single, uint8, uint16, uint32, int8, int16, or int32.

In Encoder mode, the output of the block is the index values. In Encoder and decoder mode, the output can also include the quantized output values and the quantization error. In Encoder and Encoder and decoder mode, use the **Output index data type** parameter to specify the data type of the index output from the block at port Idx. The data type of the index output can be uint8, uint16, uint32, int8, int16, or int32. The data type of the quantized output and the quantization error can be double, single, uint8, uint16, uint32, int8, int16, or int32. In Decoder mode, the output of the block is the quantized output values. Use the **Output data type** parameter to specify the data type of the quantized output values. The data type can be double, single, uint8, uint16, uint32, int8, int16, int32.

---

**Note** The input data, codebook values, boundary points, quantization error, and the quantized output values must have the same data type whenever they are present in any of the quantizer modes.

---

# Scalar Quantizer (Obsolete)

## Dialog Box

**Block Parameters: Scalar Quantizer**

Scalar Quantizer (mask) (link)

The Scalar Quantizer block has three modes of operation. In Encoder mode, the block maps each input value to a quantization region by comparing the input value to the user-specified quantizer boundary points. The block outputs the index of the associated region. In Decoder mode, the block transforms the input index values into quantized output values, defined by the quantizer codebook. In the Encoder & Decoder mode, the block performs both the encoding and decoding operations. The block outputs the index values and the quantized output values.

The Boundary points parameter is a vector of dimension  $N$  whose values are arranged in ascending order ( $[p_1 \ p_2 \ \dots \ p_N]$ ). The quantizer codebook is a vector of length  $(N-1)$ . The quantizer is unbounded if  $p_1$  is  $-\text{inf}$  and  $p_N$  is  $\text{inf}$ . When the quantizer is bounded,  $p_1$  is the lower bound for the input values. Any input less than  $p_1$  is clipped to  $p_1$  and then quantized. Similarly,  $p_N$  is the upper bound for the input values. Any input greater than  $p_N$  is clipped to  $p_N$  and is then quantized.

Parameters

Quantizer mode: Encoder

Source of quantizer parameters: Specify via dialog

Boundary points:  
[ 0 1 2 3 4 5 6 7 8 9]

Searching method: Binary


Tie-breaking rule: Choose the lower index

..... Show additional parameters .....


Output index data type: int32

OK Cancel Help Apply

## Scalar Quantizer (Obsolete)



# Scalar Quantizer (Obsolete)



## Quantizer mode

Specify Encoder, Decoder, or Encoder and decoder as a mode of operation.

## Source of quantizer parameters

Choose Specify via dialog to type the parameters into the block parameters dialog box. Select Input ports to specify the parameters using the block's input ports. In Encoder and Encoder and decoder mode, input the **Boundary points** using port B. In Decoder and Encoder and decoder mode, input the **Codebook** values using port C.

## Boundary points

Enter a vector of values that represent the boundary points of the quantizer regions. Tunable.

## Codebook

Enter a vector of quantized output values that correspond to each index value. Tunable.

## Searching method

Select Linear and the block finds the region in which the input value is located using a linear search. Select Binary and the block finds the region in which the input value is located using a binary search.

## Tie-breaking rule

Set this parameter to determine the behavior of the block when the input value is the same as the boundary point. When you select Choose the lower index, the input value is assigned to lower index value. When you select Choose the higher index, the value is assigned to the higher index.

## Action for out of range input

Choose the block's behavior when an input index value is out of range, where  $0 \leq \text{index} < N$  and  $N$  is the length of the codebook vector. Select Clip, when you want any index values less than 0 to be set to 0 and any index values greater than or equal to  $N$  to be set to  $N - 1$ . Select Clip and warn, when you want to be warned when any index values less than 0 are set to 0 and any

# Scalar Quantizer (Obsolete)

---

index values greater than or equal to  $N$  are set to  $N - 1$ . Select **Error**, when you want the simulation to stop and display an error when the index values are out of range.

## Output the quantization error

In **Encoder** and **decoder** mode, select this check box to output the quantization error from the **Err** port on this block.

## Output index data type

In **Encoder** and **Encoder and decoder** mode, specify the data type of the index output from the block at port **Idx**. The data type can be **uint8**, **uint16**, **uint32**, **int8**, **int16**, or **int32**. This parameter becomes visible when you select the **Show additional parameters** check box.

## Output data type

In **Decoder** mode, specify the data type of the quantized output. The data type can be **uint8**, **uint16**, **uint32**, **int8**, **int16**, **int32**, **single**, or **double**. This parameter becomes visible when you select **Specify via dialog** for the **Source of quantizer parameters** and you select the **Show additional parameters** check box.

## References

Gersho, A. and R. Gray. *Vector Quantization and Signal Compression*. Boston: Kluwer Academic Publishers, 1992.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point
- Fixed point
- 8-, 16-, and 32-bit signed integers
- 8-, 16-, and 32-bit unsigned integers

For more information on what data types are supported for each quantizer mode, see “Data Type Support” on page 2-1304.

## See Also

Quantizer

Scalar Quantizer Decoder

Scalar Quantizer Design

Scalar Quantizer Encoder

Uniform Encoder

Uniform Decoder

Simulink


DSP System Toolbox

# Scalar Quantizer Decoder

**Purpose** Convert each index value into quantized output value

**Library** Quantizers  
dspquant2

## Description



The Scalar Quantizer Decoder block transforms the zero-based input index values into quantized output values. The set of all possible quantized output values is defined by the **Codebook values** parameter.

Use the **Codebook values** parameter to specify a matrix containing all possible quantized output values. You can select how you want to enter the codebook values using the **Source of codebook** parameter. When you select **Specify via dialog**, type the codebook values into the block parameters dialog box. When you select **Input port**, port C appears on the block. The block uses the input to port C as the **Codebook values** parameter.

The input to this block is a vector of integer index values, where  $0 \leq \text{index} < N$  and  $N$  is the number of distinct codeword vectors in the codebook matrix. Use the **Action for out of range index value** parameter to determine what happens when an input index value is outside this range. When you want any index value less than 0 to be set to 0 and any index value greater than or equal to  $N$  to be set to  $N-1$ , select **Clip**. When you want to be warned when clipping occurs, select **Clip and warn**. When you want the simulation to stop and the block to display an error when the index values are out of range, select **Error**.

## Data Type Support


The data type of the index values input at port I can be `uint8`, `uint16`, `uint32`, `int8`, `int16`, or `int32`. The data type of the codebook values input at port C can be `double`, `single`, or `Fixed-point`.

The output of the block is the quantized output values. If, for the **Source of codebook** parameter, you select **Specify via dialog**, the **Codebook and output data type** parameter appears. You can use this parameter to specify the data type of the codebook and quantized output values. In this case, the data type of the output values can be **Same as input**, `double`, `single`, `Fixed-point`, or **User-defined**.

If, for the **Source of codebook** parameter you select **Input port**, the quantized output values have the same data type as the codebook values input at port C.

## Dialog Box

The **Main** pane of the Scalar Quantizer Decoder block dialog appears as follows.



### Action for out of range index value

Use this parameter to determine the block's behavior when an input index value is out of range, where  $0 \leq \text{index} < N$  and  $N$  is the length of the codebook vector. Select **Clip**, when you want any index values less than 0 to be set to 0 and any index values greater than or equal to  $N$  to be set to  $N - 1$ . Select **Clip and warn**, when you want to be warned when clipping occurs. Select **Error**, when you want the simulation to stop and the block to display an error when the index values are outside the range.

# Scalar Quantizer Decoder


## Source of codebook

Choose **Specify** via dialog to type the codebook values into the block parameters dialog box. Select **Input** port to specify the codebook using input port C.

## Codebook values

Enter a vector of quantized output values that correspond to each index value. Tunable.

The **Data Types** pane of the Scalar Quantizer Decoder block dialog appears as follows.



## Codebook and output data type

Specify the data type of the codebook and quantized output values. You can select one of the following:

- A rule that inherits a data type, for example, **Inherit: Same as input**.

- A built in data type, such as double
- An expression that evaluates to a valid data type, for example, `fixdt(1,16)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

This parameter is available only when you set the **Source of codebook** parameter to `Specify via dialog`. If you set the **Source of codebook** parameter to `Input port`, the output values have the same data type as the input codebook values.

## References

Gersho, A. and R. Gray. *Vector Quantization and Signal Compression*. Boston: Kluwer Academic Publishers, 1992.

## Supported Data Types

Port	Supported Data Types
I	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
C	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
Q(U)	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point</li></ul>

# Scalar Quantizer Decoder

---

Port	Supported Data Types
	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

For more information on what data types are supported for each quantizer mode, see “Data Type Support” on page 2-1312.

## See Also

Quantizer	Simulink
Scalar Quantizer Design	DSP System Toolbox
Scalar Quantizer Encoder	DSP System Toolbox
Uniform Encoder	DSP System Toolbox
Uniform Decoder	DSP System Toolbox


## Purpose

Start Scalar Quantizer Design Tool (SQDTool) to design scalar quantizer using Lloyd algorithm

## Library

Quantizers  
dspquant2

## Description



Double-click on the Scalar Quantizer Design block to start SQDTool, a GUI that allows you to design and implement a scalar quantizer. Based on your input values, SQDTool iteratively calculates the codebook values that minimize the mean squared error until the stopping criteria for the design process is satisfied. The block uses the resulting quantizer codebook values and boundary points to implement your scalar quantizer encoder and/or decoder.

For the **Training Set** parameter, enter a set of observations, or samples, of the signal you want to quantize. This data can be any variable defined in the MATLAB workspace including a variable created using a MATLAB function, such as the default value `randn(10000,1)`.

You have two choices for the **Source of initial codebook** parameter. Select **Auto-generate** to have the block choose the values of the initial codebook vector. In this case, the minimum training set value becomes the first codeword, and the maximum training set value becomes the last codeword. Then, the remaining initial codewords are equally spaced between these two values to form a codebook vector of length  $N$ , where  $N$  is the **Number of levels** parameter. When you select **User defined**, enter the initial codebook values in the **Initial codebook** field. Then, set the **Source of initial boundary points** parameter. You can select **Mid-points** to locate the boundary points at the midpoint between the codewords. To calculate the mid-points, the block internally arranges the initial codebook values in ascending order. You can also choose **User defined** and enter your own boundary points in the **Initial boundary points (unbounded)** field. Only one boundary point can be located between two codewords. When you select **User defined** for the **Source of initial boundary points** parameter, the values you enter in the **Initial codebook** and **Initial boundary points (unbounded)** fields must be arranged in ascending order.

# Scalar Quantizer Design

---

---

**Note** This block assumes that you are designing an unbounded quantizer. Therefore, the first and last boundary points are always `-inf` and `inf` regardless of any other boundary point values you might enter.

---

After you have specified the quantization parameters, the block performs an iterative process to design the optimal scalar quantizer. Each step of the design process involves using the Lloyd algorithm to calculate codebook values and quantizer boundary points. Then, the block calculates the squared quantization error and checks whether the stopping criteria has been satisfied.

The two possible options for the **Stopping criteria** parameter are `Relative threshold` and `Maximum iteration`. When you want the design process to stop when the fractional drop in the squared quantization error is below a certain value, select `Relative threshold`. Then, for **Relative threshold**, type the maximum acceptable fractional drop. When you want the design process to stop after a certain number of iterations, choose `Maximum iteration`. Then, enter the maximum number of iterations you want the block to perform in the **Maximum iteration** field. For **Stopping criteria**, you can also choose `Whichever comes first` and enter a **Relative threshold** and **Maximum iteration** value. The block stops iterating as soon as one of these conditions is satisfied.

With each iteration, the block quantizes the training set values based on the newly calculated codebook values and boundary points. When the training point lies on a boundary point, the algorithm uses the **Tie-breaking rules** parameter to determine which region the value is associated with. When you want the training point to be assigned to the lower indexed region, select `Lower indexed codeword`. To assign the training point with the higher indexed region, select `Higher indexed codeword`.

The **Searching methods** parameter determines how the block compares the training points to the boundary points. Select `Linear search` and `SQDTool` compares each training point to each quantization

region sequentially. This process continues until all the training points are associated with the appropriate regions.

Select **Binary search** for the **Searching methods** parameter and the block compares the training point to the middle value of the boundary points vector. When the training point is larger than this boundary point, the block discards the lower boundary points. The block then compares the training point to the middle boundary point of the new range, defined by the remaining boundary points. This process continues until the training point is associated with the appropriate region.

Click **Design and Plot** to design the quantizer with the parameter values specified on the left side of the GUI. The performance curve and the staircase character of the quantizer are updated and displayed in the figures on the right side of the GUI.

---

**Note** You must click **Design and Plot** to apply any changes you make to the parameter values in the SQDTool dialog box.

---

SQDTool can export parameter values that correspond to the figures displayed in the GUI. Click the **Export Outputs** button, or press **Ctrl+E**, to export the **Final Codebook**, **Final Boundary Points**, and **Error** values to the workspace, a text file, or a MAT-file. The **Error** values represent the mean squared error for each iteration.

In the **Model** section of the GUI, specify the destination of the block that will contain the parameters of your quantizer. For **Destination**, select **Current model** to create a block with your parameters in the model you most recently selected. Type `gcs` in the MATLAB Command Window to display the name of your current model. Select **New model** to create a block in a new model file.

From the **Block type** list, select **Encoder** to design a Scalar Quantizer Encoder block. Select **Decoder** to design a Scalar Quantizer Decoder block. Select **Both** to design a Scalar Quantizer Encoder block and a Scalar Quantizer Decoder block.

# Scalar Quantizer Design

---

In the **Encoder block name** field, enter a name for the Scalar Quantizer Encoder block. In the **Decoder block name** field, enter a name for the Scalar Quantizer Decoder block. When you have a Scalar Quantizer Encoder and/or Decoder block in your destination model with the same name, select the **Overwrite target block(s)** check box to replace the block's parameters with the current parameters. When you do not select this check box, a new Scalar Quantizer Encoder and/or Decoder block is created in your destination model.

Click **Generate Model**. SQDTool uses the parameters that correspond to the current plots to set the parameters of the Scalar Quantizer Encoder and/or Decoder blocks.

## Dialog Box

The screenshot displays the SQ Design Tool dialog box with the following configuration:

- Training Set: `randn(10000,1)`
- Scalar quantizer:
  - Source of initial codebook: Auto-generate
  - Number of levels: 15
  - Initial codebook: [-1.0 : 0.15 : 1.1]
  - Source of initial boundary points: Mid-points
  - Initial boundary points (unbounded): [-0.9 : 0.15 : 1.1]
- Stopping criteria:
  - Stopping criteria: Relative threshold
  - Relative threshold:  $1e-7$
  - Maximum iteration: 1000
- Algorithmic details:
  - Searching methods: Binary search
  - Tie-breaking rules: Lower indexed codeword
- Model:
  - Destination: Current model
  - Block type: Encoder
  - Encoder block name: SQ Encoder
  - Decoder block name: SQ Decoder
  - Overwrite target block(s)

Buttons: Design and Plot, Export Outputs, Generate Model

Performance plots:

- Performance curve (mean square error at each iteration):** Shows Mean Square Error vs. Number of iterations. The error starts at approximately 0.65 and drops to near zero by iteration 10. Total number of iterations = 75.
- Staircase character of the quantizer:** Shows Final Codewords vs. Final Boundary Points. The plot shows a staircase function with 15 levels, indicating the quantizer's output for different input ranges.

# Scalar Quantizer Design

---

## Training Set

Enter the samples of the signal you would like to quantize. This data set can be a MATLAB function or a variable defined in the MATLAB workspace. The typical length of this data vector is  $1e6$ .

## Source of initial codebook

Select `Auto-generate` to have the block choose the initial codebook values. Select `User defined` to enter your own initial codebook values.

## Number of levels

Enter the length of the codebook vector. For a b-bit quantizer, the length should be  $N = 2^b$ .

## Initial codebook

Enter your initial codebook values. From the **Source of initial codebook** list, select `User defined` in order to activate this parameter.

## Source of initial boundary points

Select `Mid-points` to locate the boundary points at the midpoint between the codebook values. Choose `User defined` to enter your own boundary points. From the **Source of initial codebook** list, select `User defined` in order to activate this parameter.

## Initial boundary points (unbounded)

Enter your initial boundary points. This block assumes that you are designing an unbounded quantizer. Therefore, the first and last boundary point are `-inf` and `inf`, regardless of any other boundary point values you might enter. From the **Source of initial boundary points** list, select `User defined` in order to activate this parameter.

## Stopping criteria

Choose `Relative threshold` to enter the maximum acceptable fractional drop in the squared quantization error. Choose `Maximum iteration` to specify the number of iterations at which to stop. Choose `Whichever comes first` and the block stops the iteration process as soon as the relative threshold or maximum iteration value is attained.

## Relative threshold

Type the value that is the maximum acceptable fractional drop in the squared quantization error.

## Maximum iteration

Enter the maximum number of iterations you want the block to perform. From the **Stopping criteria** list, select **Maximum iteration** in order to activate this parameter.

## Searching methods

Choose **Linear search** to use a linear search method when comparing the training points to the boundary points. Choose **Binary search** to use a binary search method when comparing the training points to the boundary points.

## Tie-breaking rules

When a training point lies on a boundary point, choose **Lower indexed codeword** to assign the training point to the lower indexed quantization region. Choose **Higher indexed codeword** to assign the training point to the higher indexed region.

## Design and Plot

Click this button to display the performance curve and the staircase character of the quantizer in the figures on the right side of the GUI. These plots are based on the current parameter settings.

You must click **Design and Plot** to apply any changes you make to the parameter values in the SQDTool GUI.

## Export Outputs

Click this button, or press **Ctrl+E**, to export the **Final Codebook**, **Final Boundary Points**, and **Error** values to the workspace, a text file, or a MAT-file.

## Destination

Choose **Current model** to create a Scalar Quantizer block in the model you most recently selected. Type `gcs` in the MATLAB Command Window to display the name of your current model. Choose **New model** to create a block in a new model file.

# Scalar Quantizer Design

---

## Block type

Select Encoder to design a Scalar Quantizer Encoder block. Select Decoder to design a Scalar Quantizer Decoder block. Select Both to design a Scalar Quantizer Encoder block and a Scalar Quantizer Decoder block.

## Encoder block name

Enter a name for the Scalar Quantizer Encoder block.

## Decoder block name

Enter a name for the Scalar Quantizer Decoder block.

## Overwrite target block(s)

When you do not select this check box and a Scalar Quantizer Encoder and/or Decoder block with the same block name exists in the destination model, a new Scalar Quantizer Encoder and/or Decoder block is created in the destination model. When you select this check box and a Scalar Quantizer Encoder and/or Decoder block with the same block name exists in the destination model, the parameters of these blocks are overwritten by new parameters.

## Generate Model

Click this button and SQDTool uses the parameters that correspond to the current plots to set the parameters of the Scalar Quantizer Encoder and/or Decoder blocks.

## References

Gersho, A. and R. Gray. *Vector Quantization and Signal Compression*. Boston: Kluwer Academic Publishers, 1992.

## Supported Data Types

- Double-precision floating point

## See Also

Quantizer	Simulink
Scalar Quantizer Decoder	DSP System Toolbox

Scalar Quantizer Encoder

DSP System Toolbox

Uniform Encoder

DSP System Toolbox

Uniform Decoder

DSP System Toolbox

# Scalar Quantizer Encoder


## Purpose

Encode each input value by associating it with index value of quantization region

## Library

Quantizers  
dspquant2

## Description



The Scalar Quantizer Encoder block maps each input value to a quantization region by comparing the input value to the quantizer boundary points defined in the **Boundary points** parameter. The block outputs the zero-based index of the associated region.

You can select how you want to enter the **Boundary points** using the **Source of quantizer parameters**. When you select Specify via dialog, type the boundary points into the block parameters dialog box. When you select Input port, port B appears on the block. The block uses the input to port B as the **Boundary points** parameter.

Use the **Boundary points** parameter to specify the boundary points for your quantizer. These values are used to break up the set of input numbers into regions. Each region is specified by an index number.

Let  $N$  be the number of quantization regions. When the codebook is defined as  $[c_1 \ c_2 \ c_3 \ \dots \ c_N]$ , and the **Boundary points** parameter is defined as  $[p_0 \ p_1 \ p_2 \ p_3 \ \dots \ p_N]$ , then  $p_0 < c_1 < p_1 < c_2 < \dots < p_{(N-1)} < c_N < p_N$  for a regular quantizer. When your quantizer is bounded, from the **Partitioning** list, select Bounded. You need to specify  $N+1$  boundary points, or  $[p_0 \ p_1 \ p_2 \ p_3 \ \dots \ p_N]$ . When your quantizer is unbounded, from the **Partitioning** list, select Unbounded. You need to specify  $N-1$  boundary points, or  $[p_1 \ p_2 \ p_3 \ \dots \ p_{(N-1)}]$ ; the block sets  $p_0$  equal to  $-\text{inf}$  and  $p_N$  equal to  $\text{inf}$ .

The block uses the **Partitioning** parameter to interpret the boundary points you enter. For instance, to create a bounded quantizer, from the **Partitioning** list, select Bounded and enter the following boundary points:

```
[0 0.5 3.7 5.8 6.0 11]
```

The block assigns any input values between 0 and 0.5 to index 0, input values between 0.5 and 3.7 to index 1, and so on. The block assigns any values that are less than 0 to index 0, the lowest index value. The block assigns any values that are greater than 11 to index 4, the highest index value.

To create an unbounded quantizer, from the **Partitioning** list, select **Unbounded** and enter the following boundary points:

```
[0 0.5 3.7 5.8 6.0 11]
```

The block assigns any input values between 0 and 0.5 to index 1, input values between 0.5 and 3.7 to index 2, and so on. The block assigns any input values less than 0 to index 0 and any values greater than 11 to index 6.

The **Searching method** parameter determines how the appropriate quantizer index is found. When you select **Linear**, the Scalar Quantizer Encoder block compares the input value to the first region defined by the first two boundary points. When the input value does not fall within this region, the block then compares the input value to the next region. This process continues until the input value is determined to be within a region and is associated with the appropriate index value. The computational cost of this process is of the order  $P$ , where  $P$  is the number of boundary points.

When you select **Binary** for the **Searching method**, the block compares the input value to the middle value of the boundary points vector. When the input value is larger than this boundary point, the block discards the boundary points that are lower than this middle value. The block then compares the input value to the middle boundary point of the new range, defined by the remaining boundary points. This process continues until the input value is associated with the appropriate index value. The computational cost of this process is of the order  $\log_2 P$ , where  $P$  is the number of boundary points. In most cases, the **Binary** option is faster than the **Linear** option.

When an input value is the same as a boundary point, the **Tie-breaking rule** parameter determines the region to which the value is assigned.

# Scalar Quantizer Encoder

---

When you want the input value to be assigned to the lower indexed region, select **Choose the lower index**. To assign the input value with the higher indexed region, select **Choose the higher index**.

Select the **Output codeword** check box to output the codeword values that correspond to each index value at port Q(U).

Select the **Output the quantization error** check box to output the quantization error for each input value from the Err port on this block. The quantization error is the difference between the input value and the quantized output value.

When you select either the **Output codeword** check box or the **Output quantization error** check box, you must also enter your codebook values. If, from the **Source of quantizer parameters** list, you choose **Specify via dialog**, use the **Codebook** parameter to enter a vector of quantized output values that correspond to each region. If, from the **Source of quantizer parameters** list, you choose **Input port**, use input port C to specify your codebook values.

If, for the **Partitioning** parameter, you select **Bounded**, the **Output clipping status** check box and the **Action for out of range input** parameter appear. When you select the **Output clipping status** check box, port S appears on the block. Any time an input value is outside the range defined by the **Boundary points** parameter, the block outputs a 1 at the S port. When the value is inside the range, the blocks outputs a 0.

You can use the **Action for out of range input** parameter to determine the block's behavior when an input value is outside the range defined by the **Boundary points** parameter. Suppose the boundary points for a bounded quantizer are defined as  $[p_0 \ p_1 \ p_2 \ p_3 \ \dots \ p_N]$  and the possible index values are defined as  $[i_0 \ i_1 \ i_2 \ \dots \ i_{(N-1)}]$ , where  $i_0=0$  and  $i_0 < i_1 < i_2 < \dots < i_{(N-1)}$ . When you want any input value less than  $p_0$  to be assigned to index value  $i_0$  and any input values greater than  $p_N$  to be assigned to index value  $i_{(N-1)}$ , select **Clip**. When you want to be warned when clipping occurs, select **Clip and warn**. When you want the simulation to stop and the block to display an error when the index values are out of range, select **Error**.

The Scalar Quantizer Encoder block accepts real floating-point and fixed-point inputs. For more information on the data types accepted by each port, see “Data Type Support” on page 2-1329 or “Supported Data Types” on page 2-1335.

## Data Type Support

The input data values, boundary points, and codebook values can be input to the block at ports U, B, and C, respectively. The data type of the inputs can be `double`, `single`, or `Fixed-point`.

The outputs of the block can be the index values, the quantized output values, the quantization error, and the clipping status. Use the **Index output data type** parameter to specify the data type of the index output from the block at port I. You can choose `int8`, `uint8`, `int16`, `uint16`, `int32`, or `uint32`. The data type of the quantized output and the quantization error can be `double`, `single`, or `Fixed-point`. The clipping status values output at port S are Boolean values.

---


**Note** The input data, boundary points, codebook values, quantized output values, and the quantization error must have the same data type whenever they are present.

---

## Dialog Box

The **Main** pane of the Scalar Quantizer Encoder block dialog appears as follows.

# Scalar Quantizer Encoder



## Source of quantizer parameters

Choose **Specify via dialog** to enter the boundary points and codebook values using the block parameters dialog box. Select **Input port** to specify the parameters using the block's input ports. Input the boundary points and codebook values using ports B and C, respectively.

## Partitioning

When your quantizer is bounded, select **Bounded**. When your quantizer is unbounded, select **Unbounded**.

## Boundary points

Enter a vector of values that represent the boundary points of the quantizer regions. This parameter is visible when you select **Specify via dialog** from the **Source of quantizer parameters** list. Tunable.

## Searching method

When you select **Linear**, the block finds the region in which the input value is located using a linear search. When you select **Binary**, the block finds the region in which the input value is located using a binary search.

## Tie-breaking rule

Set this parameter to determine the behavior of the block when the input value is the same as the boundary point. When you select **Choose the lower index**, the input value is assigned to lower indexed region. When you select **Choose the higher index**, the value is assigned to the higher indexed region.

## Output codeword

Select this check box to output the codeword values that correspond to each index value at port Q(U).

## Output quantization error

Select this check box to output the quantization error for each input value at port Err.

# Scalar Quantizer Encoder

---

## Codebook

Enter a vector of quantized output values that correspond to each index value. If, for the **Partitioning** parameter, you select **Bounded** and your boundary points vector has length  $N$ , then you must specify a codebook of length  $N-1$ . If, for the **Partitioning** parameter, you select **Unbounded** and your boundary points vector has length  $N$ , then you must specify a codebook of length  $N+1$ .

This parameter is visible when you select **Specify** via dialog from the **Source of quantizer parameters** list and you select either the **Output codeword** or **Output quantization error** check box. Tunable.

## Output clipping status

When you select this check box, port **S** appears on the block. Any time an input value is outside the range defined by the **Boundary points** parameter, the block outputs a 1 at this port. When the value is inside the range, the block outputs a 0. This parameter is visible when you select **Bounded** from the **Partitioning** list.

## Action for out of range input


Use this parameter to determine the behavior of the block when an input value is outside the range defined by the **Boundary points** parameter. Suppose the boundary points are defined as  $[p_0 \ p_1 \ p_2 \ p_3 \ \dots \ p_N]$  and the index values are defined as  $[i_0 \ i_1 \ i_2 \ \dots \ i_{(N-1)}]$ . When you want any input value less than  $p_0$  to be assigned to index value  $i_0$  and any input values greater than  $p_N$  to be assigned to index value  $i_{(N-1)}$ , select **Clip**. When you want to be warned when clipping occurs, select **Clip and warn**. When you want the simulation to stop and the block to display an error when the index values are out of range, select **Error**. This parameter is visible when you select **Bounded** from the **Partitioning** list.

## Index output data type

Specify the data type of the index output from the block at port **I**. You can choose **int8**, **uint8**, **int16**, **uint16**, **int32**, or **uint32**.

The **Data Types** pane of the Scalar Quantizer Encoder block dialog appears as follows.

# Scalar Quantizer Encoder



## Rounding mode

Select the rounding mode for fixed-point operations.

## Overflow mode

Select the overflow mode to be used when block inputs are fixed point.

## References

Gersho, A. and R. Gray. *Vector Quantization and Signal Compression*. Boston: Kluwer Academic Publishers, 1992.

## Supported Data Types

Port	Supported Data Types
U	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
B	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
C	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
I	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

# Scalar Quantizer Encoder

---

Port	Supported Data Types
Q(U)	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
Err	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
S	<ul style="list-style-type: none"><li>• Boolean</li></ul>

For more information on what data types are supported for each quantizer mode, see “Data Type Support” on page 2-1329.

## See Also

Quantizer	Simulink
Scalar Quantizer Decoder	DSP System Toolbox
Scalar Quantizer Design	DSP System Toolbox
Uniform Encoder	DSP System Toolbox
Uniform Decoder	DSP System Toolbox

<b>Purpose</b>	Select input elements from vector, matrix, or multidimensional signal
<b>Library</b>	Signal Management / Indexing dspindex
<b>Description</b>	The Selector block is an implementation of the Simulink Selector block. See Selector for more information.

# Short-Time FFT

## Purpose


Nonparametric estimate of spectrum using short-time, fast Fourier transform (FFT) method

## Library

Transforms

dspxfm3

## Description



Short-Time FFT

The Short-Time FFT block computes a nonparametric estimate of the spectrum. The block buffers, applies a window, and zero pads the input signal. The block then takes the FFT of the signal, transforming it into the frequency domain.


Connect your single-channel analysis window to the  $w(n)$  port. For the **Analysis window length** parameter, enter the length of the analysis window,  $W$ . The block buffers the input signal such that it has a frame length of  $W$

Connect your single-channel or multichannel input signal to the  $x(n)$  port. After the block buffers and windows this signal, it zero-pads the signal before computing the FFT. For the **FFT length** parameter, enter the length to which the block pads the input signal. For the **Overlap between consecutive windows (in samples)** parameter, enter the number of samples to overlap each frame of the input signal.

The block outputs the complex-valued, single-channel or multichannel short-time FFT at port  $X(n,k)$ .

## Fixed-Point Data Types

The following diagram shows the data types used within the Short-Time FFT subsystem block for fixed-point signals.



The settings for the fixed-point parameters of the Array-Vector Multiply block in the diagram above are as follows:

- **Rounding Mode** — Floor
- **Overflow Mode** — Wrap
- **Product output** — Inherit via internal rule
- **Accumulator** — Inherit via internal rule
- **Output** — Same as first input

The settings for the fixed-point parameters of the FFT block in the diagram above are as follows:


- **Rounding Mode** — Floor
- **Overflow Mode** — Wrap
- **Sine table** — Same word length as input
- **Product output** — Inherit via internal rule
- **Accumulator** — Inherit via internal rule
- **Output** — Inherit via internal rule

See the FFT and Array-Vector Multiply block reference pages for more information.

## Examples

The `dspstsa_win32` example illustrates how to use the Short-Time FFT and Inverse Short-Time FFT blocks to remove the background noise from a speech signal.

# Short-Time FFT



## Dialog Box

### Analysis window length

Specify the frame length of the analysis window. The **Analysis window length** must be a positive integer value greater than one.

### Overlap between consecutive windows (in samples)

Enter the number of samples of overlap for each frame of the input signal.

### FFT length

Enter the length to which the block pads the input signal.

## Treat $M \times 1$ and unoriented sample-based signals as

Specify how the block treats sample-based  $M$ -by-1 column vectors and unoriented sample-based vectors of length  $M$ . You can select one of the following options:

- **One channel** — When you select this option, the block treats  $M$ -by-1 and unoriented sample-based inputs as a column vector (one channel).
- **$M$  channels (this choice will be removed see release notes)** — When you select this option, the block treats  $M$ -by-1 and unoriented sample-based inputs as a 1-by- $M$  row vector.

---

**Note** This parameter will be removed in a future release. See the *DSP System Toolbox Release Notes* for more information.

---

## References

Quatieri, Thomas E. *Discrete-Time Speech Signal Processing*. Englewood Cliffs, NJ: Prentice-Hall, 2001.

## Supported Data Types

Port	Supported Data Types
x(n)	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed only)</li> <li>• 8-, 16-, and 32-bit signed integers</li> </ul>
w(n)	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed only)</li> </ul>

## Short-Time FFT

---

Port	Supported Data Types
	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit signed integers</li></ul>
X(n,k)	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>

## See Also

Burg Method	DSP System Toolbox
Inverse Short-Time FFT	DSP System Toolbox
Magnitude FFT	DSP System Toolbox
Periodogram	DSP System Toolbox
Spectrum Scope	DSP System Toolbox
Window Function	DSP System Toolbox
Yule-Walker Method	DSP System Toolbox
<code>pwelch</code>	Signal Processing Toolbox

See “Spectral Analysis” for related information.

# Signal From Workspace

---

**Purpose** Import signal from MATLAB workspace

**Library** Sources  
dspsrcs4

## Description



The Signal From Workspace block imports a signal from the MATLAB workspace into the Simulink model. The **Signal** parameter specifies the name of a MATLAB workspace variable containing the signal to import, or any valid MATLAB expression defining a matrix or 3-D array.

When the **Signal** parameter specifies an M-by-N matrix ( $M \neq 1$ ), each of the N columns is treated as a distinct channel. You specify the frame size in the **Samples per frame** parameter,  $M_0$ , and the output is an  $M_0$ -by-N matrix containing  $M_0$  consecutive samples from each signal channel. You specify the output sample period in the **Sample time** parameter,  $T_s$ , and the output frame period is  $M_0 * T_s$ . For  $M_0 = 1$ , the output is sample based; otherwise the output is frame based. For convenience, an imported row vector ( $M = 1$ ) is treated as a single channel, so the output dimension is  $M_0$ -by-1.

When the **Signal** parameter specifies an M-by-N-by-P array, each of the P pages (an M-by-N matrix) is output in sequence with period  $T_s$ . The **Samples per frame** parameter must be set to 1, and the output is always sample based.

## Initial and Final Conditions

Unlike the Simulink From Workspace block, the Signal From Workspace block holds the output value constant between successive output frames (that is, no linear interpolation takes place). Additionally, the initial signal values are always produced immediately at  $t=0$ .

When the block has output all of the available signal samples, it can start again at the beginning of the signal, or simply repeat the final value or generate zeros until the end of the simulation. (The block does not extrapolate the imported signal beyond the last sample.) The **Form output after final data value by** parameter controls this behavior:

- When you specify **Setting To Zero**, the block generates zero-valued outputs for the duration of the simulation after generating the last frame of the signal.
- When you specify **Holding Final Value**, the block repeats the final sample for the duration of the simulation after generating the last frame of the signal.
- When you specify **Cyclic Repetition**, the block repeats the signal from the beginning after it reaches the last sample in the signal. If the frame size you specify in the **Samples per frame** parameter does not evenly divide the input length, a buffer block is inserted into the Signal From Workspace subsystem, and the model becomes multirate. If you do not want your model to become multirate, make sure the frame size evenly divides the input signal length.

Select the **Warn when frame size does not evenly divide input length** parameter to be alerted when the input length is not an integer multiple of the frame size and your model will become multirate. Use the Model Explorer to turn these warnings on or off model-wide:

- 1** Select **Model Explorer** from the **View** menu in your model.
- 2** In the **Search** bar of the Model Explorer, search by **Property Name** for the `ignoreOrWarnInputAndFrameLengths` property. Each block with the **Warn when frame size does not evenly divide input length** check box appears in the list in the **Contents** pane.
- 3** Select each of the blocks for which you wish to toggle the warning parameter, and select or deselect the check box in the `ignoreOrWarnInputAndFrameLengths` column.


## Examples

### Example 1

In the first model, `ex_signal_from_workspace_fb`, the Signal From Workspace imports a two-channel signal from the workspace matrix, `A`. The **Sample time** is set to 1 and the **Samples per frame** is set to 4, so the output is frame based with a frame size of 4 and a frame period of 4 seconds. The **Form output after final data value by** parameter


# Signal From Workspace

specifies Setting To Zero, so all outputs after the third frame (at  $t=8$ ) are zero.




## Example 2

In the second model, ex\_signal\_from\_workspace\_sb, the Signal From Workspace block imports a sample-based matrix signal from the 3-D workspace array, A. Again, the **Form output after final data value** by parameter specifies Setting To Zero, so all outputs after the third (at  $t=2$ ) are zero.



The **Samples per frame** parameter is set to 1 for 3-D input.

## Dialog Box



### Signal

The name of the MATLAB workspace variable from which to import the signal, or a valid MATLAB expression specifying the signal.

### Sample time

The sample period,  $T_s$ , of the output. The output frame period is  $M_o * T_s$ .

### Samples per frame

The number of samples,  $M_o$ , to buffer into each output frame. This value must be 1 when you specify a 3-D array in the **Signal** parameter.

# Signal From Workspace

---

## **Form output after final data value by**

Specifies the output after all of the specified signal samples have been generated. The block can output zeros for the duration of the simulation (**Setting to zero**), repeat the final data sample (**Holding Final Value**) or repeat the entire signal from the beginning (**Cyclic Repetition**).

## **Warn when frame size does not evenly divide input length**

Select this parameter to be alerted when the input length is not an integer multiple of the frame size and your model will become multirate. For more information, see “Initial and Final Conditions” on page 2-1344.

This parameter is only visible when **Cyclic Repetition** is selected for the **Form output after final data value by** parameter.

## **Supported Data Types**

- Double-precision floating point
- Single-precision floating point
- Fixed point (signed and unsigned)
- 8-, 16-, and 32-bit signed integers
- 8-, 16-, and 32-bit unsigned integers

## **See Also**

From Audio Device	DSP System Toolbox
From Wave File (Obsolete)	DSP System Toolbox
Signal From Workspace	DSP System Toolbox
From Workspace	Simulink
To Workspace	Simulink
Triggered Signal From Workspace	DSP System Toolbox

See the sections below for related information:

- “Create Sample-Based Signals”
- “Create Frame-Based Signals”
- “Import and Export Sample-Based Signals”
- “Import and Export Frame-Based Signals”

# Signal To Workspace

**Purpose** Write data to MATLAB workspace

**Library** Sinks  
dspsnks4

## Description



The Signal To Workspace block writes data from your simulation into an array or structure in the main MATLAB workspace. You can specify a name for the workspace variable as well as whether the data is saved as an array, structure, or structure with time.

When the **Save format** is set to Array or Structure, the dimensions of the output depend on the input dimensions and the setting of the **Save 2-D signals as** parameter. The following table summarizes the output dimensions under various conditions. In the table,  $K$  represents the value of the **Limit data points to last** parameter.

Input Signal Dimensions	Save 2-D Signals as ...	Signal To Workspace Output Dimension
$M$ -by- $N$ matrix	2-D array (concatenate along first dimension)	$K$ -by- $N$ matrix. If you set the <b>Limit data points to last</b> parameter to <code>inf</code> , $K$ represents the total number of samples acquired in each column by the end of simulation. This is equivalent to multiplying the input frame size ( $M$ ) by the total number

Input Signal Dimensions	Save 2-D Signals as ...	Signal To Workspace Output Dimension
		of $M$ -by- $N$ inputs acquired by the block.
$M$ -by- $N$ matrix	3-D array (concatenate along third dimension)	$M$ -by- $N$ -by- $K$ array. If you set the <b>Limit data points to last</b> parameter to <code>inf</code> , $K$ represents the total number of $M$ -by- $N$ inputs acquired by the end of the simulation.
Length- $N$ unoriented vector	Any setting	$K$ -by- $N$ matrix
$N$ -dimensional array where $N > 2$	Any setting	Array with $N+1$ dimensions, where the size of the last dimension is equal to $K$ . If you set the <b>Limit data points to last</b> parameter to <code>inf</code> , $K$ represents the total number of $M$ -by- $N$ inputs acquired by the end of simulation

## Examples


### Example 1: Save 2-D Signals as a 2-D Array

In the `ex_sigtoworkspace_ref2` model, the Signal To Workspace block receives a 2-by-4 matrix input and logs 11 frames (two samples per frame) by the end of the simulation. Because the **Save 2-D signals as** parameter is set to 2-D array (concatenate along first

# Signal To Workspace

dimension), the block concatenates the input along the first dimension to create a 22-by-4 matrix,  $A$ , in the MATLAB workspace.

The following figure illustrates the behavior of the Signal to Workspace block in this example.




In the 2-D output mode, there is no indication of where one frame ends and another begins. To log input frames separately, set the **Save 2-D signals as** parameter to 3-D array (concatenate along third dimension), as shown in Example 2.

## Example 2: Save 2-D Signals as a 3-D Array


In the `ex_signtoworkspace_ref1` model, the input to the Signal To Workspace block is a 2-by-4 matrix. The **Save 2-D signals as** parameter is set to 3-D array (concatenate along third dimension), so by the end of the simulation the Signal To Workspace block logs 11 frames of data as a 2-by-4-by-11 array,  $A$ , in the MATLAB workspace.

The following figure illustrates the behavior of the Signal to Workspace block in this example.

# Signal To Workspace



# Signal To Workspace



## Dialog Box

### Variable name

Specify the name of the array or structure into which the block logs the simulation data. The block creates this variable in the MATLAB workspace only after the simulation stops running.

When you enter the name of an existing workspace variable, the block overwrites that variable with the simulation data.

## Limit data points to last

Specify the maximum number of samples or frames the block will save. When the simulation generates more than the specified maximum number of samples or frames, the simulation saves only the most recently generated data. To capture all data, set this parameter to `inf`. See the table in the Description section for more information on how this parameter affects the dimensions of the logged data.

## Decimation

Specify a positive integer  $d$  to determine how often the block writes data to the workspace array or structure. The block writes data to the array or structure every  $d$ th sample. With the default decimation value of 1, the block writes data at every time step.

## Save format

Specify the format in which to save simulation output to the workspace. You can select one of the following options:

- **Array** — Select this option to save the data as an N-dimensional array. If the input signal is an unoriented vector, the resulting workspace array is 2-D. Each input vector is saved in a row of the output matrix, vertically concatenated onto the previous vector. If the input signal is 2-dimensional, the dimensions of the resulting workspace array depend on the setting of the **Save 2-D signals as** parameter.
- **Structure** — Select this option to save the data as a structure consisting of three fields: `time`, `signals` and `blockName`. In this mode, the `time` field is empty, and the `blockName` field contains the name of the Signal To Workspace block. The `signals` field contains a structure with three additional fields: `values`, `dimensions`, and `label`. The `values` field contains the array of signal values, the `dimensions` field specifies the dimensions of the values array, and the `label` field contains the label of the input line.

# Signal To Workspace

---

- **Structure with time** — This option is the same as **Structure**, except that the **time** field contains a vector of simulation time steps. This is the only output format that can be read directly by a **From Workspace** block. When you select this option, the **Save 2-D signals as** parameter is not available. In this mode, the block always saves 2-D input arrays as a 3-D array.

The default setting of this parameter is **Array**.

## **Save 2-D signals as**

Specify whether the block outputs 2-D signals as a 2-D or 3-D array in the MATLAB workspace:

- **2-D array (concatenate along first dimension)** — When you select this option, the block saves an  $M$ -by- $N$  input signal as a  $(K*M)$ -by- $N$  matrix, where  $K*M$  is the total number of samples acquired by the end of the simulation. The block vertically concatenates each  $M$ -by- $N$  matrix input with the previous input to produce the 2-D output array. See “Example 1: Save 2-D Signals as a 2-D Array” on page 2-1351 for more information about this mode.
- **3-D array (concatenate along third dimension)** — When you select this option, the block saves an  $M$ -by- $N$  input signal as an  $M$ -by- $N$ -by- $K$  array, where  $K$  is the number of  $M$ -by- $N$  inputs logged by the end of the simulation.  $K$  has an upper bound equal to the value of the **Limit data points to last** parameter. See “Example 2: Save 2-D Signals as a 3-D Array” on page 2-1352 for more information about this mode.

This parameter is visible only when you set the **Save format** parameter to **Array** or **Structure**. When you set the **Save format** parameter to **Structure with time**, the block outputs the 2-D input signal as a 3-D array.

---

**Note** The Inherit from input (this choice will be removed - see release notes) option will be removed in a future release. See “Signal To Workspace Block Changes” in the *DSP System Toolbox Release Notes* for more information.

---

## Log fixed-point data as a fi object

Select this check box to log fixed-point data to the MATLAB workspace as a Fixed-Point Toolbox `fi` object. Otherwise, fixed-point data is logged to the workspace as `double`.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point
- Fixed point (signed and unsigned)
- 8-, 16-, and 32-bit signed integers
- 8-, 16-, and 32-bit unsigned integers

## See Also

Triggered To Workspace  
To Workspace

DSP System Toolbox  
Simulink

# Sine Wave

---

**Purpose** Generate continuous or discrete sine wave

**Library** Sources  
dspsrcs4

## Description



The Sine Wave block generates a multichannel real or complex sinusoidal signal, with independent amplitude, frequency, and phase in each output channel. A real sinusoidal signal is generated when the **Output complexity** parameter is set to `Real`, and is defined by an expression of the type

$$y = A \sin(2\pi ft + \phi)$$

where you specify  $A$  in the **Amplitude** parameter,  $f$  in hertz in the **Frequency** parameter, and  $\phi$  in radians in the **Phase offset** parameter. A complex exponential signal is generated when the **Output complexity** parameter is set to `Complex`, and is defined by an expression of the type

$$y = Ae^{j(2\pi ft + \phi)} = A\{\cos(2\pi ft + \phi) + j \sin(2\pi ft + \phi)\}$$

## Sections of This Reference Page

- “Generating Multichannel Outputs” on page 2-1359
- “Output Sample Time and Samples Per Frame” on page 2-1359
- “Sample Mode” on page 2-1359
- “Discrete Computational Methods” on page 2-1360
- “Examples” on page 2-1363
- “Dialog Box” on page 2-1364
- “Supported Data Types” on page 2-1369
- “See Also” on page 2-1369

## Generating Multichannel Outputs

For both real and complex sinusoids, the **Amplitude**, **Frequency**, and **Phase offset** parameter values ( $A$ ,  $f$ , and  $\varphi$ ) can be scalars or length- $N$  vectors, where  $N$  is the desired number of channels in the output. When you specify at least one of these parameters as a length- $N$  vector, scalar values specified for the other parameters are applied to every channel.

For example, to generate the three-channel output containing the real sinusoids below, set **Output complexity** to Real and the other parameters as follows:

- **Amplitude** = [1 2 3]
- **Frequency** = [1000 500 250]
- **Phase offset** = [0 0  $\pi/2$ ]

$$y = \begin{cases} \sin(2000\pi t) & \text{(channel 1)} \\ 2\sin(1000\pi t) & \text{(channel 2)} \\ 3\sin\left(500\pi t + \frac{\pi}{2}\right) & \text{(channel 3)} \end{cases}$$

## Output Sample Time and Samples Per Frame

In all discrete modes, the block buffers the sampled sinusoids into frames of size  $M$ , where you specify  $M$  in the **Samples per frame** parameter. The output is a frame-based  $M$ -by- $N$  matrix with frame period  $M \cdot T_s$ , where you specify  $T_s$  in the **Sample time** parameter. For  $M=1$ , the output is sample based.

## Sample Mode

The **Sample mode** parameter specifies the block's sampling property, which can be Continuous or Discrete:

- Continuous

# Sine Wave

---

In continuous mode, the sinusoid in the  $i$ th channel,  $y_i$ , is computed as a continuous function,

$$y_i = A_i \sin(2\pi f_i t + \phi_i) \quad (\text{real})$$

or

$$y_i = A_i e^{j(2\pi f_i t + \phi_i)} \quad (\text{complex})$$

and the block's output is continuous. In this mode, the block's operation is the same as that of a Simulink Sine Wave block with **Sample time** set to 0. This mode offers high accuracy, but requires trigonometric function evaluations at each simulation step, which is computationally expensive. Additionally, because this method tracks absolute simulation time, a discontinuity will eventually occur when the time value reaches its maximum limit.

Note also that many DSP System Toolbox blocks do not accept continuous-time inputs.

- **Discrete**

In discrete mode, the block's discrete-time output can be generated by directly evaluating the trigonometric function, by table lookup, or by a differential method. The three options are explained below.

## **Discrete Computational Methods**

When you select **Discrete** from the **Sample mode** parameter, the secondary **Computation method** parameter provides three options for generating the discrete sinusoid:

- **Trigonometric Fcn**

- Table Lookup
- Differential

---

**Note** To generate fixed-point sinusoids, you must select Table Lookup.

---

## Trigonometric Fcn

The trigonometric function method computes the sinusoid in the  $i$ th channel,  $y_i$ , by sampling the continuous function

$$y_i = A_i \sin(2\pi f_i t + \phi_i) \quad (\text{real})$$

or

$$y_i = A_i e^{j(2\pi f_i t + \phi_i)} \quad (\text{complex})$$

with a period of  $T_s$ , where you specify  $T_s$  in the **Sample time** parameter. This mode of operation shares the same benefits and liabilities as the Continuous sample mode described above.

At each sample time, the block evaluates the sine function at the appropriate time value *within the first cycle* of the sinusoid. By constraining trigonometric evaluations to the first cycle of each sinusoid, the block avoids the imprecision of computing the sine of very large numbers, and eliminates the possibility of discontinuity during extended operations (when an absolute time variable might overflow). This method therefore avoids the memory demands of the table lookup method at the expense of many more floating-point operations.

## Table Lookup

The table lookup method precomputes the *unique* samples of every output sinusoid at the start of the simulation, and recalls the samples from memory as needed. Because a table of finite length can only be constructed when all output sequences repeat, the method requires that the period of every sinusoid in the output be evenly divisible by the sample period. That is,  $1/(f_i T_s) = k_i$  must be an integer value for every channel  $i = 1, 2, \dots, N$ .

When the **Optimize table for** parameter is set to **Speed**, the table constructed for each channel contains  $k_i$  elements. When the **Optimize table for** parameter is set to **Memory**, the table constructed for each channel contains  $k_i/4$  elements.

For long output sequences, the table lookup method requires far fewer floating-point operations than any of the other methods, but can demand considerably more memory, especially for high sample rates (long tables). This is the recommended method for models that are intended to emulate or generate code for DSP hardware, and that therefore need to be optimized for execution speed.

---

**Note** The lookup table for this block is constructed from double-precision floating-point values. Thus, when you use the **Table lookup** computation mode, the maximum amount of precision you can achieve in your output is 53 bits. Setting the word length of the **Output** or **User-defined** data type to values greater than 53 bits does not improve the precision of your output.

---

## Differential

The differential method uses an incremental algorithm. This algorithm computes the output samples based on the output values computed at the previous sample time (and precomputed update terms) by making use of the following identities.

$$\begin{aligned}\sin(t + T_s) &= \sin(t)\cos(T_s) + \cos(t)\sin(T_s) \\ \cos(t + T_s) &= \cos(t)\cos(T_s) - \sin(t)\sin(T_s)\end{aligned}$$

The update equations for the sinusoid in the  $i$ th channel,  $y_i$ , can therefore be written in matrix form as

$$\begin{bmatrix} \sin\{2\pi f_i(t + T_s) + \phi_i\} \\ \cos\{2\pi f_i(t + T_s) + \phi_i\} \end{bmatrix} = \begin{bmatrix} \cos(2\pi f_i T_s) & \sin(2\pi f_i T_s) \\ -\sin(2\pi f_i T_s) & \cos(2\pi f_i T_s) \end{bmatrix} \begin{bmatrix} \sin(2\pi f_i t + \phi_i) \\ \cos(2\pi f_i t + \phi_i) \end{bmatrix}$$

where you specify  $T_s$  in the **Sample time** parameter. Since  $T_s$  is constant, the right-hand matrix is a constant and can be computed once at the start of the simulation. The value of  $A_i \sin[2\pi f_i(t + T_s) + \phi_i]$  is then computed from the values of  $\sin(2\pi f_i t + \phi_i)$  and  $\cos(2\pi f_i t + \phi_i)$  by a simple matrix multiplication at each time step.

This mode offers reduced computational load, but is subject to drift over time due to cumulative quantization error. Because the method is not contingent on an absolute time value, there is no danger of discontinuity during extended operations (when an absolute time variable might overflow).


## Examples

The `dspsinecomp` example provides a comparison of all the available sine generation methods.

# Sine Wave

## Dialog Box

The **Main** pane of the Sine Wave block dialog appears as follows.



**Amplitude**

A length- $N$  vector containing the amplitudes of the sine waves in each of  $N$  output channels, or a scalar to be applied to all  $N$  channels. The vector length must be the same as that specified for the **Frequency** and **Phase offset** parameters. Tunable when **Computation method** is to Trigonometric fcn or Differential.

**Frequency**

A length- $N$  vector containing frequencies, in Hertz, of the sine waves in each of  $N$  output channels, or a scalar to be applied to all  $N$  channels. The vector length must be the same as that specified for the **Amplitude** and **Phase offset** parameters. You can specify positive, zero, or negative frequencies. Tunable when **Sample mode** is Continuous or **Computation method** is Trigonometric fcn.

**Phase offset**

A length- $N$  vector containing the phase offsets, in radians, of the sine waves in each of  $N$  output channels, or a scalar to be applied to all  $N$  channels. The vector length must be the same as that specified for the **Amplitude** and **Frequency** parameters. Tunable when **Sample mode** is Continuous or **Computation method** is Trigonometric fcn.

**Sample mode**

The block's sampling behavior, Continuous or Discrete. This parameter is not tunable.

**Output complexity**

The type of waveform to generate: Real specifies a real sine wave, Complex specifies a complex exponential. This parameter is not tunable.

**Computation method**

The method by which discrete-time sinusoids are generated: Trigonometric fcn, Table lookup, or Differential. This parameter is not tunable. For more information on each of the

# Sine Wave

---

available options, see “Discrete Computational Methods” on page 2-1360 in the Description section.

This parameter is only visible when you set the **Sample mode** to Discrete.

---

**Note** To generate fixed-point sinusoids, you must set the **Computation method** to Table lookup.

---

## Optimize table for

Optimizes the table of sine values for Speed or Memory (this parameter is only visible when the **Computation method** parameter is set to Table lookup). When optimized for speed, the table contains  $k$  elements, and when optimized for memory, the table contains  $k/4$  elements, where  $k$  is the number of input samples in one full period of the sine wave.

## Sample time

The period with which the sine wave is sampled,  $T_s$ . The block’s output frame period is  $M * T_s$ , where you specify  $M$  in the **Samples per frame** parameter. This parameter is disabled when you select Continuous from the **Sample mode** parameter. This parameter is not tunable.

## Samples per frame

The number of consecutive samples from each sinusoid to buffer into the output frame,  $M$ . When the value of this parameter is 1, the block outputs a sample-based signal.

This parameter is disabled when you select Continuous from the **Sample mode** parameter.

## Resetting states when re-enabled


This parameter only applies when the Sine Wave block is located inside an enabled subsystem and the **States when enabling** parameter of the Enable block is set to reset. This parameter

determines the behavior of the Sine Wave block when the subsystem is re-enabled. The block can either reset itself to its starting state (**Restart at time zero**), or resume generating the sinusoid based on the current simulation time (**Catch up to simulation time**). This parameter is disabled when you select **Continuous** from the **Sample mode** parameter.

The **Data Types** pane of the Sine Wave block dialog appears as follows.

# Sine Wave

---



## Output data type

Specify the output data type for this block. You can select one of the following:

- A rule that inherits a data type, for example, `Inherit: Inherit via back propagation`. When you select this option, the output data type and scaling matches that of the next downstream block.
- A built in data type, such as `double`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

---

**Note** The lookup table for this block is constructed from double-precision floating-point values. Thus, when you use the **Table lookup** computation mode, the maximum amount of precision you can achieve in your output is 53 bits. Setting the word length of the **Output** or **User-defined** data type to values greater than 53 bits does not improve the precision of your output.

---

## Supported Data Types

- Double-precision floating point
- Single-precision floating point
- Fixed point (signed only)
- 8-, 16-, and 32-bit signed integers

## See Also

Chirp	DSP System Toolbox
Complex Exponential	DSP System Toolbox

# Sine Wave

---

Signal From Workspace

Signal Generator

Sine Wave

sin

DSP System Toolbox

Simulink

Simulink

MATLAB

# Singular Value Decomposition


## Purpose

Factor matrix using singular value decomposition

## Library

Math Functions / Matrices and Linear Algebra / Matrix Factorizations  
dspfactors

## Description



The Singular Value Decomposition block factors the  $M$ -by- $N$  input matrix  $A$  such that

$$A = U \cdot \text{diag}(S) \cdot V^*$$

where

- $U$  is an  $M$ -by- $P$  matrix
- $V$  is an  $N$ -by- $P$  matrix
- $S$  is a length- $P$  vector
- $P$  is defined as  $\min(M, N)$

When

- $M = N$ ,  $U$  and  $V$  are both  $M$ -by- $M$  unitary matrices
- $M > N$ ,  $V$  is an  $N$ -by- $N$  unitary matrix, and  $U$  is an  $M$ -by- $N$  matrix whose columns are the first  $N$  columns of a unitary matrix
- $N > M$ ,  $U$  is an  $M$ -by- $M$  unitary matrix, and  $V$  is an  $N$ -by- $M$  matrix whose columns are the first  $M$  columns of a unitary matrix


In all cases,  $S$  is an unoriented vector of positive singular values having length  $P$ .

Length- $N$  row inputs are treated as length- $N$  columns.

Note that the first (maximum) element of output  $S$  is equal to the 2-norm of the matrix  $A$ .

# Singular Value Decomposition

## Dialog Box



### Show singular vector ports

Select to enable the U and V output ports.

### Show error status port

Select to enable the E output port, which reports a failure to converge. The possible values you can receive on the port are:

- 0 — The singular value decomposition calculation converges.
- 1 — The singular value decomposition calculation does not converge.

If the singular value decomposition calculation fails to converge, the output at ports U, S, and V are undefined matrices of the correct size.

## References

Golub, G. H., and C. F. Van Loan. *Matrix Computations*. 3rd ed. Baltimore, MD: Johns Hopkins University Press, 1996.

# Singular Value Decomposition

## Supported Data Types

Port	Supported Data Types
A	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
U	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
S	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
V	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
E	<ul style="list-style-type: none"><li>• Boolean</li></ul>

## See Also

Autocorrelation LPC	DSP System Toolbox
Cholesky Factorization	DSP System Toolbox
LDL Factorization	DSP System Toolbox
LU Inverse	DSP System Toolbox
Pseudoinverse	DSP System Toolbox
QR Factorization	DSP System Toolbox
SVD Solver	DSP System Toolbox
svd	MATLAB

See “Matrix Factorizations” for related information.

# Sort

---

**Purpose** Sort input elements by value

**Library** Statistics  
dspstat3

## Description



The Sort block ranks the values of the input elements using either a quick sort or an insertion sort algorithm. The quick sort algorithm uses a recursive sort method and is faster at sorting more than 32 elements. The insertion sort algorithm uses a non-recursive method and is faster at sorting less than 32 elements. You should also always use the insertion sort algorithm when you are generating code from the Sort block if you do not want recursive function calls in your code. To specify the sort method, use the **Sort algorithm** parameter.

The **Mode** parameter specifies the block's mode of operation, and can be set to Value, Index, or Value and index.

### Value Mode

When **Mode** is set to Value, the block sorts the elements in each column of the  $M$ -by- $N$  input matrix  $u$  in order of ascending or descending value, as specified by the **Sort order** parameter.

```
val = sort(u)
val = flipud(sort(u))
```

The output at each sample time,  $val$ , is an  $M$ -by- $N$  matrix containing the sorted columns of  $u$ .

The block sorts complex inputs according to their magnitude.

### Index Mode

When **Mode** is set to Index, the block sorts the elements in each column of the  $M$ -by- $N$  input matrix  $u$ ,

```
[val,idx] = sort(u)
[val,idx] = flipud(sort(u))
```

and outputs the  $M$ -by- $N$  index matrix, `idx`. The  $j$ th column of `idx` is an index vector that permutes the  $j$ th column of `u` to the desired sorting order.

```
val(:,j) = u(idx(:,j),j)
```

The index value outputs are always 32-bit unsigned integer values.

### **Value and Index Mode**

When **Mode** is set to **Value** and **index**, the block outputs both the sorted matrix, `val`, and the index matrix, `idx`.


### **Fixed-Point Data Types**

The parameters on the **Data Types** pane are only used for complex fixed-point inputs. Complex fixed-point inputs are sorted by magnitude squared. The sum of the squares of the real and imaginary parts of such an input are formed before a comparison is made, as described in “Value Mode” on page 2-1374. The results of the squares of the real and imaginary parts are placed into the product output data type. The result of the sum of the squares is placed into the accumulator data type. These parameters are ignored for other types of inputs.

# Sort

## Dialog Box

The **Main** pane of the Sort block dialog appears as follows.



### Mode

Specify the block's mode of operation: Output the sorted matrix (Value), the index matrix (Index), or both (Value and index).

**Sort order**


Specify the order in which to sort the training points, Descending or Ascending.

**Sort algorithm**

Specify whether the elements of the input are sorted using a Quick sort or an Insertion sort algorithm.

The **Data Types** pane of the Sort block dialog appears as follows.

# Sort



---

**Note** The parameters on the **Data Types** pane are only used for complex fixed-point inputs. The sum of the squares of the real and imaginary parts of such an input are formed before a comparison is made, as described in “Value Mode” on page 2-1374. The results of the squares of the real and imaginary parts are placed into the product output data type. The result of the sum of the squares is placed into the accumulator data type. These parameters are ignored for other types of inputs.

---

### **Rounding mode**

Select the rounding mode for fixed-point operations.

### **Overflow mode**

Select the overflow mode for fixed-point operations.

### **Product output data type**

Specify the product output data type. See “Fixed-Point Data Types” on page 2-1375 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as input`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Accumulator data type

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-1375 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Same as product output`
- An expression that evaluates to a valid data type, for example, `fixdt([],16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• 8-, 16-, 32-, and 128-bit unsigned integers</li><li>• 8-, 16-, 32-, and 128-bit signed integers</li></ul>
Val	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• 8-, 16-, 32-, and 128-bit unsigned integers</li></ul>

**See Also**

Port	Supported Data Types
	<ul style="list-style-type: none"><li>• 8-, 16-, 32-, and 128-bit signed integers</li></ul>
Histogram Idx	DSP System Toolbox
Median	DSP System Toolbox
sort	MATLAB

# Spectrum Scope

---

**Purpose** Display mean-square spectrum or power spectral density of each input signal

**Library** Sinks  
dsp.snks4

## Description



The Spectrum Scope block computes and displays the mean-square spectrum or power spectral density of each input signal. The input can be a vector or a matrix.

---

**Note** When the **Buffer input** and **Specify FFT length** parameters are both cleared, the block input length must be a power of two.

---

For an example that uses the Spectrum Scope block, see “Display Frequency-Domain Data” section in the DSP System Toolbox documentation.

---

**Note** For information about the Spectrum Analyzer system object, see `dsp.SpectrumAnalyzer`.

---

## Scope Properties Pane

The **Spectrum units** parameter allows you to specify the following information:

- The type of measurement for the block to compute (Power Spectral Density or Mean-Square Spectrum)
- The type of scaling for the block to use (linear or log)

You can set the **Spectrum units** parameter to one of the options shown in the following table.

Spectrum Units	Measurement Type	Scaling
Watts	Mean-Square Spectrum (MSS)	Linear
dBW dBm	Mean-Square Spectrum (MSS)	Logarithmic
Watts/Hertz	Power Spectral Density (PSD)	Linear
dBW/Hertz dBm/Hertz	Power Spectral Density (PSD)	Logarithmic

The  $X$ -axis units are always expressed in Hertz. The spacing between frequency points is  $1/(N_{fft}T_s)$ .

The **Spectrum type** parameter specifies the range of frequencies over which the block computes the spectrum. The available options are **One-sided** ( $[0 \dots Fs/2]$ ) and **Two-sided** ( $(-Fs/2 \dots Fs/2]$ ), where  $F_s$  is the sampling frequency of the original time-domain signal. Both the one-sided and two-sided options compute the full power spectrum. The Spectrum Scope block only supports **One-sided** ( $[0 \dots Fs/2]$ ) spectrums for real input signals.

Other DSP System Toolbox FFT-based blocks, including the blocks in the Power Spectrum Estimation library, always compute the FFT at frequencies in the range  $[0, F_s)$ .

Select the **Buffer input** check box to buffer the input signal. When the block buffers the input, the **Buffer size** parameter specifies the number of input samples to buffer before computing and displaying the magnitude FFT. You also use the **Buffer overlap** parameter to specify the number of samples from the previous buffer to include in the current buffer. To compute the number of new input samples the block acquires before computing and displaying the magnitude FFT, subtract the buffer overlap from the buffer size.

The display update period is

# Spectrum Scope

---

$$(M_o - L) * T_s$$

where

- $M_o$  = buffer size
- $L$  = buffer overlap
- $T_s$  = input sample period

For negative buffer overlap values, the block discards the appropriate number of input samples after the buffer fills. The block also updates the scope display at a slower rate than in the zero-overlap case.

---

**Note** If you are using the Spectrum Scope block inside an enabled subsystem and you select the **Buffer input** check box, you may get unexpected results. See “Behavior in Enabled Subsystems” on page 2-1394 for more information.

---

The **Window** and **Window sampling** parameters apply to the specification of the window function. See the Window Function block reference page for more details on these parameters.

The block determines the FFT length,  $N_{fft}$ , in the following ways:

- If you clear the **Specify FFT length** check box and select **Buffer input**, the block uses the buffer size as the FFT size.
- If you clear both the **Specify FFT length** and **Buffer input** check boxes, the block uses the input size as the FFT size.
- If you select the **Specify FFT length** check box, the **FFT length** parameter appears in the dialog box. Enter the number of samples on which you want the block to perform the FFT. This value must be a power of two.

The block zero pads or wraps the buffer of each channel to the FFT length before computing the FFT.

The value of the **Number of spectral averages** parameter determines the number of spectra to average. Setting this parameter to 1 effectively disables averaging. See the Periodogram block reference page for more information.

## Display Properties Pane

The **Display Properties** pane enables you to control how the block displays your data.

The **Show grid** parameter toggles the background grid on and off.

If you select the **Persistence** check box, the window maintains successive displays. That is, the scope does not erase the display after each frame (or collection of frames), but overlays successive input frames in the scope display.

If you select the **Frame number** check box, the block displays the number of the current frame in the input sequence on the scope window, and the block increments the count as each new input is received. Counting starts at 1 with the first input frame, and continues until the simulation stops.

If you select the **Channel legend** check box, a legend indicating the line color, style, and marker of each channel's data is added. When the input signal is labeled, that label appears in the channel legend. When the input signal is not labeled, but comes from a Concatenate block or a Mux block with labeled inputs, those labels appear in the channel legend. Otherwise, each channel in the legend is labeled with the channel number (CH 1, CH 2, etc.). Click and drag the legend to reposition it in the scope window; double-click the line label to edit the text. If you rerun the simulation, the labels revert to the defaults.

If you select the **Compact display** check box, the scope completely fills the figure window. The scope does not display menus and axis titles, but it does show the numerical axis labels within the axes. If you clear the **Compact display** check box, the scope displays the axis labels and

# Spectrum Scope

---

titles in a gray border surrounding the scope axes, and the window's menus and toolbar become visible.

If you select the **Open scope at start of simulation** check box, the scope opens at the start of the simulation. If you clear this parameter, the scope does not open automatically during the simulation. You can use this feature when you have several scope blocks in a model, and you do not want to view all the associated scopes during the simulation.

To view a scope window that is not open during simulation, click **Open scope immediately** on the **Display Properties** pane of the desired Scope block.

---

**Note** Before running a model that contains a Spectrum Scope block in Accelerator, Rapid Accelerator, or External mode, you must select the **Open scope at start of simulation** check box. If you do not select this check box before running your model for the first time, the scope will not display your simulation data.

---

The **Scope position** parameter specifies a four-element vector of the form

[left bottom width height]

specifying the position of the scope window on the screen, where (0,0) is the lower-left corner of the display. See the MATLAB `figure` function for more information.

## Axis Properties Pane

If you select the **Inherit sample time from input** check box, the block computes the frequency data from the sample period of the input to the block. For the block to produce valid output, the following conditions must hold:

- The input to the block is the original signal, with no samples added or deleted (by insertion of zeros, for example).

- The sample period of the time-domain signal in the simulation equals the sample period of the original time series.

In cases where not all these conditions hold, specify the appropriate value for the **Sample time of original time series** parameter.

When you set the **Frequency display limits** to Auto, the block displays the full spectrum over the frequency range specified by the **Spectrum type** parameter.

The **Frequency display offset** parameter allows you to offset the range of values displayed on the frequency axis of the Spectrum Scope.

- When the **Frequency display offset** is 0, the block displays the DC frequency (0 Hz) at 0 Hz.
- When **Frequency display offset** is a nonzero value, the block displays the DC frequency (0 Hz) at the value specified in the **Frequency display offset** parameter. If you set the **Frequency display limits** parameter to User-defined, the block does not automatically relabel the frequency axis. However, if you set the **Frequency display limits** to Auto, the values displayed on the frequency axis shift according to the **Frequency display offset** parameter.

For example, if the block has the following settings:

- **Spectrum Units** = Watts/Hertz
- **Spectrum Type** = Two-sided ( $(-F_s/2 \dots F_s/2]$ )
- **Frequency display offset (Hz)** = 0
- **Frequency display limits** = Auto
- Sampling frequency ( $F_s$ ) = 1000 Hz

Then, based on these settings:

- The values on the frequency axis of the spectrum scope range from -500 Hz to 500 Hz.
- The block centers the DC frequency (0 Hz) at 0 Hz.

# Spectrum Scope

---

If you change the **Frequency display offset (Hz)** parameter to 100, the block:

- Relabels the frequency axis such that the values range from -400 Hz to 600 Hz.
- Centers the DC frequency (0 Hz) at 100 Hz.

When you set the **Frequency display limits** to **User-defined**, the **Minimum frequency (Hz)** and **Maximum frequency (Hz)** parameters set the range of the horizontal axis.

**Minimum Y-limit** and **Maximum Y-limit** parameters allow you to set the range of the vertical axis. Setting these parameters equates to setting the `ymin` and `ymax` values of the MATLAB `axis` function.

The **Y-axis label** is the text displayed to the left of the y-axis.

## Line Properties Pane

Use the parameters on the **Line Properties** pane to help you distinguish between two or more independent channels of data on the scope.

The **Line visibilities** parameter specifies which channel's data is displayed on the scope, and which is hidden. The syntax specifies the visibilities in list form, where the term `on` or `off` as a list entry specifies the visibility of the corresponding channel's data. The list entries are separated by the pipe symbol, `|`.

For example, a five-channel signal would ordinarily generate five distinct plots on the scope. To disable plotting of the third and fifth lines, enter the following visibility specification in the **Line visibilities** parameter.

```
on | on | off | on | off  
ch 1 ch 2 ch 3 ch 4 ch 5
```


Note that the first (leftmost) list item corresponds to the first signal channel (leftmost column of the input matrix).

The **Line styles** parameter specifies the line style with which each channel's data is displayed on the scope. The syntax specifies the channel line styles in list form, with each list entry specifying a style for the corresponding channel's data. The list entries are separated by the pipe symbol, |.

For example, a five-channel signal would ordinarily generate all five plots with a solid line style. To plot each line with a different style, enter

```
- | -- | : | -. | -  
ch 1 ch 2 ch 3 ch 4 ch 5
```

These settings plot the signal channels with the following styles.

Line Style	Command to Type in Line Style Parameter	Appearance
Solid	-	
Dashed	--	
Dotted	:	
Dash-dot	-.	
No line	none	No line appears

Note that the first (leftmost) list item, '-', corresponds to the first signal channel (leftmost column of the input matrix). See the LineSpec property of the MATLAB line function for more information about the available markers.

The **Line markers** parameter specifies the marker style with which each channel's samples are represented on the scope. The syntax specifies the channels' marker styles in list form, with each list entry

# Spectrum Scope

specifying a marker for the corresponding channel's data. The list entries are separated by the pipe symbol, |.

For example, a five-channel signal would ordinarily generate all five plots with no marker symbol (that is, the individual sample points are not marked on the scope). To instead plot each line with a different marker style, you could enter

```
* | . | x | s | d
ch 1 ch 2 ch 3 ch 4 ch 5
```

These settings plot the signal channels with the following styles.

Marker Style	Command to Type in Marker Style Parameter	Appearance
Asterisk	*	
Point	.	
Cross	x	
Square	s	
Diamond	d	

Note that the leftmost list item, '\*', corresponds to the first signal channel or leftmost column of the input matrix. See the LineSpec property of the MATLAB line function for more information about the available markers.

To produce a stem plot for the data in a particular channel, type the word stem instead of one of the basic marker shapes.

The **Line colors** parameter specifies the color in which each channel's data is displayed on the scope. The syntax specifies the channel colors in list form, with each list entry specifying a color (in one of the MATLAB ColorSpec formats) for the corresponding channel's data. The list entries are separated by the pipe symbol, |.

For example, a five-channel signal would ordinarily generate all five plots in the color black. To instead plot the lines with the color order below, enter

```
[0 0 0] | [0 0 1] | [1 0 0] | [0 1 0] | [.7529 0 .7529]
  ch 1      ch 2      ch 3      ch 4      ch 5
```

or

```
'k' | 'b' | 'r' | 'g' | [.7529 0 .7529]
ch 1 ch 2 ch 3 ch 4      ch 5
```

These settings plot the signal channels in the following colors (8-bit RGB equivalents shown in the center column).

Color	RGB Equivalent	Appearance
Black	(0,0,0)	
Blue	(0,0,255)	
Red	(255,0,0)	
Green	(0,255,0)	
Dark purple	(192,0,192)	

# Spectrum Scope

---

Note that the leftmost list item, 'k', corresponds to the first signal channel or leftmost column of the input matrix. See the MATLAB function `ColorSpec` for more information about the color syntax.

## Spectrum Scope Window

The title that appears in the title bar of the scope window is the same as the block title. In addition to the standard MATLAB figure window menus such as **File**, **Window**, and **Help**, the Spectrum Scope window contains **View**, **Axes**, and **Channels** menus.

The options in the **View** menu allow you to zoom in and out of the scope window:

- To zoom in on the scope window, you must first select **View > Zoom In** or click the corresponding Zoom In toolbar button (). You can then zoom in by clicking in the center of your area of interest, or by clicking and dragging your cursor to draw a rectangular area of interest inside of the scope window.
- To zoom in on the x-axis of the scope window, you must first select **View > Zoom X** or click the corresponding Zoom X-Axis toolbar button () on the scope window. You can then zoom in on the x-axis with a single click inside the scope window, or by clicking and dragging the cursor along the x-axis over your area of interest.
- To zoom in on the y-axis of the scope window, you must first select **View > Zoom Y** or click the corresponding Zoom Y-Axis toolbar button (). You can then zoom in on the y-axis with a single click inside the scope window, or by clicking and dragging the cursor along the y-axis over your area of interest.
- To return to the original view of the scope window, you have the following options:
  - Select **Full View** from the **View** menu.
  - Click the Restore default view toolbar button () on the Spectrum Scope window.

- Right-click inside the scope window and select **Reset to Original View**.

---

**Note** To zoom out in smaller increments, you can right-click inside of the scope window and select **Zoom Out**. You can also zoom out by holding down the **Shift** key and clicking the left mouse button inside the scope window.

---

The parameters that you set using the **Axes** menu apply to all channels. Many of the parameters in this menu are also accessible through the block parameters dialog box. For descriptions of these parameters, see “Display Properties Pane” on page 2-1399. Below are descriptions of other parameters in the **Axes** menu:

- **Refresh** erases all data on the scope display, except for the most recent trace. This command is useful in conjunction with the **Persistence** setting.
- **Autoscale** resizes the *y*-axis to best fit the vertical range of the data.

---

**Note** The **Minimum Y-limit** and **Maximum Y-limit** parameters on the **Axis properties** pane of the block dialog are not updated to display the numerical limits selected by the autoscale feature.

---

- **Save Axes Settings** allows you to save the current axes settings. When you select this option, the **Minimum Y-limit** and **Maximum Y-limit** parameters of the **Axes Properties** pane update with the current *y*-axes limits. The **Frequency display limits** parameter is set to **User-defined**, and the current *x*-axes limits are saved in the **Minimum Frequency (Hz)** and **Maximum Frequency (Hz)** parameters. To save these axes settings for your next MATLAB session, you need to resave your model.

- **Save Scope Position** automatically updates the **Scope position** parameter in the **Axis Properties** pane of the block dialog. When you select **Save Scope Position**, the block saves the current position and size of the scope window. To make the scope window open at a particular location on the screen when the simulation runs, drag the window to the desired location, resize it, and select **Save Scope Position** from the **Axes** menu.

The properties listed in the **Channels** menu apply to a particular channel. All of the parameters in this menu are also accessible through the block parameters dialog box. For descriptions of these parameters, see “Line Properties Pane” on page 2-1388.

Many of these options are also accessible by right-clicking the mouse anywhere on the scope display. The menu that is displayed contains a combination of the options available in the **View**, **Axes** and **Channels** menus.

---

**Note** When you select **Compact Display** from the **Axes** menu, the scope window menus are no longer visible. Right-click in the Spectrum Scope window and click **Compact Display** to make the menus reappear.

---

## Behavior in Enabled Subsystems


When you clear the **Buffer input** check box, the Spectrum Scope block is fully supported inside of “Enabled Subsystems”. However, when you choose to buffer the input to the Spectrum Scope block, you may get unexpected results inside of enabled subsystems. For more information about the limitations of buffering signals inside of enabled subsystems, see the “Behavior in Enabled Subsystems” on page 2-172 section of the Buffer block reference page.

## Examples

See “Display Frequency-Domain Data” in the *DSP System Toolbox User’s Guide*.

## Dialog Box

### Scope Properties Pane



### Spectrum units

Specify the spectrum units as described in the following table. The specified units determine the type of measurement to compute (Mean-Square Spectrum or Power Spectral Density). They also determine the type of Y-axis scaling (linear or logarithmic).

# Spectrum Scope

Spectrum Units	Measurement Type	Scaling
Watts	Mean-Square Spectrum (MSS)	Linear
dBW dBm	Mean-Square Spectrum (MSS)	Logarithmic
Watts/Hertz	Power Spectral Density (PSD)	Linear
dBW/Hertz dBm/Hertz	Power Spectral Density (PSD)	Logarithmic

You can only tune this parameter within the same **Measurement type**. The block cannot switch between computing the mean-square spectrum and the power spectral density while the simulation is running.

## Spectrum type

Specify the range of frequencies over which to compute the magnitudes in the input. The available options are **One-sided** ( $[0 \dots F_s/2]$ ) and **Two-sided** ( $(-F_s/2 \dots F_s/2]$ ), where  $F_s$  is the sampling frequency of the original frequency-domain signal. If you select **One-sided** ( $[0 \dots F_s/2]$ ), the input signal must be real-valued. Tunable.

## Buffer input

Select this check box to rebuffer the input data.

If you are using the Spectrum Scope block inside of an enabled subsystem, you may get unexpected results. See “Behavior in Enabled Subsystems” on page 2-1394 for more information.

The Spectrum Scope block does not support buffering in models running in external mode. To buffer the input when running your

model in external mode, clear this check box and place a Buffer block before the Spectrum Scope block in your model.

## **Buffer size**

Specify the number of input samples that the block buffers before computing and displaying the magnitude FFT. You must specify a real integer value greater than or equal to two. If you do not select the **Specify FFT length** check box, the **Buffer size** must be a power of two.

This parameter becomes visible only when you select the **Buffer input** check box.

## **Buffer overlap**

Specify the number of samples from the previous buffer to include in the current buffer. To compute the number of new input samples the block acquires before computing and displaying the magnitude FFT, subtract the buffer overlap from the buffer size.

This parameter becomes visible only when you select the **Buffer input** check box.

## **Treat Mx1 and unoriented sample-based signals as**

Specify how the block treats sample-based  $M$ -by-1 column vectors and unoriented sample-based vectors of length  $M$ . You can select one of the following options:

- **One channel** — When you select this option, the block treats  $M$ -by-1 and unoriented sample-based inputs as a column vector (one channel).
- **M channels** — When you select this option, the block treats  $M$ -by-1 and unoriented sample-based inputs as a 1-by- $M$  row vector.

## **Window**

Specify the type of window to apply. See the Window Function block reference page for more details. Tunable.

## **Stopband attenuation in dB**

Enter the level, in decibels (dB), of stopband attenuation,  $R_s$ , for the Chebyshev window. Tunable.

This parameter becomes visible only when you select Chebyshev for the **Window** parameter.

## **Beta**

Enter the  $\beta$  parameter for the Kaiser window. Increasing **Beta** widens the mainlobe and decreases the amplitude of the sidelobes in the displayed frequency magnitude response. Tunable.

This parameter becomes visible only if you select Kaiser for the **Window** parameter.

## **Window sampling**

Choose Symmetric or Periodic. Tunable.

This parameter becomes visible only if Blackman, Hamming, Hann, or Hanning is selected for the **Window** parameter.

## **Specify FFT length**

Select this check box to specify the FFT length yourself in the **FFT length** parameter.

## **FFT length**


Enter the number of samples on which you want the block to perform the FFT. The value you specify must be a power of two.

This parameter becomes visible only when you select the **Specify FFT length** check box.

## **Number of spectral averages**

The number of spectra to average. Setting this parameter to 1 effectively disables averaging. See the Periodogram block reference page for more information.

## Display Properties Pane



### Show grid

Toggle the scope grid on and off. Tunable.

### Persistence

Select this check box to maintain successive displays. That is, the scope does not erase the display after each frame (or collection

# Spectrum Scope

---

of frames), but overlays successive input frames in the scope display. Tunable.

## **Frame number**

If you select this check box, the number of the current frame in the input sequence appears in the Vector Scope window. Tunable.

## **Channel legend**

Toggles the legend on and off. Tunable.

## **Compact display**

Resizes the scope to fill the window. Tunable.

## **Open scope at start of simulation**

Select this check box to open the scope at the start of the simulation. When you clear this parameter, the scope does not automatically open during the simulation. Tunable.

---

**Note** Before running a model that contains a Spectrum Scope block in Accelerator, Rapid Accelerator, or External mode, you must select the **Open scope at start of simulation** check box. If you do not select this check box before running your model for the first time, the scope will not display your simulation data.

---


## **Open scope immediately**

If the scope is not open during simulation, select this check box to open it. This parameter is visible only while the simulation is running.

## **Scope position**

A four-element vector of the form [left bottom width height] specifying the position of the scope window. (0,0) is the lower-left corner of the display. Tunable.

## Axis Properties Pane



### Inherit sample time from input

If you select this check box, the block computes the time-domain sample period from the frame period and frame size of the frequency-domain input. Use this parameter only when the length of each frame of frequency-domain data equals the frame length of the time-domain data that generated it.

---

**Note** The block cannot inherit sample time when you specify a non-zero value for the **Buffer overlap** parameter and set the **Spectrum units** parameter to dBW/Hertz, Watts/Hertz or dBm/Hertz. You must specify the sample time by clearing this check box and using the **Sample time of original time series** parameter.

---

### **Sample time of original time series**

Enter the sample period of the original time-domain signal.

### **Frequency display offset**

The **Frequency display offset** parameter allows you to offset the range of values displayed on the frequency axis of the Spectrum Scope. The value specified in this field becomes the new label for the DC frequency (0 Hz). See the example in the “Axis Properties Pane” on page 2-1386 section for more information.

### **Frequency display limits**

Select Auto to have the limits of the  $x$ -axis set for you automatically. Select User-defined to set the limits yourself in the **Minimum frequency** and **Maximum frequency** parameters.

### **Minimum frequency (Hz)**

Specify the minimum frequency value of the  $x$ -axis in Hertz. This parameter is only visible if the **Frequency display limits** parameter is set to User-defined. Tunable.

### **Maximum frequency (Hz)**

Specify the maximum frequency value of the  $x$ -axis in Hertz. This parameter is only visible if the **Frequency display limits** parameter is set to User-defined. Tunable.

### **Minimum Y-limit**

Specify the minimum value of the  $y$ -axis. Setting this parameter is analogous to setting the  $y_{min}$  value of the MATLAB axis function. Tunable.

**Maximum Y-limit**


Specify the maximum value of the  $y$ -axis. Setting this parameter is analogous to setting the `ymax` value of the MATLAB `axis` function. Tunable.

**Y-axis label**

Specify text for the block to display to the left of the  $y$ -axis. Tunable.

# Spectrum Scope

## Line Properties Pane



### Line visibilities

Enter on or off to specify the visibility of the scope traces for various channels. Separate your choices for each channel with a pipe (|) symbol. Tunable.

## Line styles

Enter the line styles of the scope traces for various channels using the MATLAB line function `LineStyle` formats. Separate your choices for each channel with by a pipe (|) symbol. Tunable.

## Line markers

Enter the line markers of the scope traces for various channels using the MATLAB line function `Marker` formats. Separate your choices for each channel with by a pipe (|) symbol. Tunable.

## Line colors

Enter the colors of the scope traces for various channels using the MATLAB `ColorSpec` formats. Separate your choices for each channel with by a pipe (|) symbol. Tunable.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

## See Also


FFT	DSP System Toolbox
Periodogram	DSP System Toolbox
Short-Time FFT	DSP System Toolbox
Vector Scope	DSP System Toolbox
Window Function	DSP System Toolbox

# Stack

**Purpose** Store inputs into LIFO register


**Library** Signal Management / Buffers  
dspbuff3

## Description



The Stack block stores a sequence of input samples in a last in, first out (LIFO) register. The register capacity is set by the **Stack depth** parameter, and inputs can be scalars, vectors, or matrices.

The block *pushes* the input at the In port onto the top of the stack when a trigger event is received at the Push port. When a trigger event is received at the Pop port, the block *pops* the top element off the stack and holds the Out port at that value. The last input to be pushed onto the stack is always the first to be popped off.



A trigger event at the optional Rst port empties the stack contents. When you select **Clear output port on reset**, then a trigger event at the Rst port empties the stack *and* sets the value at the Out port to zero. This setting also applies when a disabled subsystem containing


the Stack block is reenabled; the Out port value is only reset to zero in this case when you select **Clear output port on reset**.

When two or more of the control input ports are triggered at the same time step, the operations are executed in the following order:

- 1 Rst
- 2 Push
- 3 Pop


The rate of the trigger signal must be the same as the rate of the data signal input. You specify the triggering event for the Push, Pop, and Rst ports in the **Trigger type** pop-up menu:

- **Rising edge** — Triggers execution of the block when the trigger input does one of the following:
  - Rises from a negative value to a positive value or zero
  - Rises from zero to a positive value, where the rise is not a continuation of a rise from a negative value to zero (see the following figure)



- **Falling edge** — Triggers execution of the block when the trigger input does one of the following:

- Falls from a positive value to a negative value or zero
- Falls from zero to a negative value, where the fall is not a continuation of a fall from a positive value to zero (see the following figure)



- Either edge — Triggers execution of the block when the trigger input is a Rising edge or Falling edge (as described above).
- Non-zero sample — Triggers execution of the block at each sample time that the trigger input is not zero.

---

**Note** If your model contains any referenced models that use a Stack block with the **Push full stack** parameter set to Dynamic reallocation, you cannot simulate your top-level model in Simulink Accelerator mode.

---

The **Push full stack** parameter specifies the block's behavior when a trigger is received at the Push port but the register is full. The **Pop empty stack** parameter specifies the block's behavior when a trigger is received at the Pop port but the register is empty. The following options are available for both cases:

- Ignore — Ignore the trigger event, and continue the simulation.

- **Warning** — Ignore the trigger event, but display a warning message in the MATLAB command window.
- **Error** — Display an error dialog box and terminate the simulation.

---

**Note** The **Push full stack** and **Pop empty stack** parameters are diagnostic parameters. Like all diagnostic parameters on the Configuration Parameters dialog box, they are set to **Ignore** in the code generated for this block by Simulink Coder code generation software.

---

The **Push full stack** parameter additionally offers the **Dynamic reallocation** option, which dynamically resizes the register to accept as many additional inputs as memory permits. To find out how many elements are on the stack at a given time, enable the Num output port by selecting the **Show number of stack entries port** parameter.

---

**Note** When **Dynamic reallocation** is selected, the **System target file** parameter on the **Code Generation** pane of the Model Configuration Parameters dialog box must be set to `grt_malloc.tlc` Generic Real-Time Target with dynamic memory allocation.


---

## Examples

### Example 1

The table below illustrates the Stack block's operation for a **Stack depth** of 4, **Trigger type** of `Either edge`, and **Clear output port on reset** enabled. Because the block triggers on both rising and falling edges in this example, each transition from 1 to 0 or 0 to 1 in the **Push**, **Pop**, and **Rst** columns below represents a distinct trigger event. A 1 in the **Empty** column indicates an empty buffer, while a 1 in the **Full** column indicates a full buffer.


# Stack

In	Push	Pop	Rst	Stack	Out	Empty	Full	Num
1	0	0	0	top  bottom	0	1	0	0
2	1	0	0	top  bottom	0	0	0	1
3	0	0	0	top  bottom	0	0	0	2
4	1	0	0	top  bottom	0	0	0	3
5	0	0	0	top  bottom	0	0	1	4
6	0	1	0	top  bottom	5	0	0	3
7	0	0	0	top  bottom	4	0	0	2
8	0	1	0	top  bottom	3	0	0	1
9	0	0	0	top  bottom	2	1	0	0
10	1	0	0	top  bottom	2	0	0	1
11	0	0	0	top  bottom	2	0	0	2
12	1	0	1	top  bottom	0	0	0	1

Note that at the last step shown, the Push and Rst ports are triggered simultaneously. The Rst trigger takes precedence, and the stack is first cleared and then pushed.

## Example 2

The dspqdemo example provides an example of the related Queue block.

**Dialog  
Box****Stack depth**

The number of entries that the LIFO register can hold.

**Trigger type**

The type of event that triggers the block's execution. The rate of the trigger signal must be the same as the rate of the data signal input.

**Push full stack**

Response to a trigger received at the Push port when the register is full. Inputs to this port must have the same built-in data type as inputs to the Pop and Rst input ports.

When **Dynamic** reallocation is selected, the **System target file** parameter on the **Code Generation** pane of the Model Configuration Parameters dialog box must be set to `grt_malloc.tlc` Generic Real-Time Target with dynamic memory allocation.

### **Pop empty stack**

Response to a trigger received at the Pop port when the register is empty. Inputs to this port must have the same built-in data type as inputs to the Push and Rst input ports.

### **Show empty stack indicator port**

Enable the Empty output port, which is high (1) when the stack is empty, and low (0) otherwise.

### **Show full stack indicator port**

Enable the Full output port, which is high (1) when the stack is full, and low (0) otherwise. The Full port remains low when you select **Dynamic reallocation** from the **Push full stack** parameter.

### **Show number of stack entries port**

Enable the Num output port, which tracks the number of entries currently on the stack. When inputs to the In port are double-precision values, the outputs from the Num port are double-precision values. Otherwise, the outputs from the Num port are 32-bit unsigned integer values.

### **Show reset port to clear internal stack buffer**

Enable the Rst input port, which empties the stack when the trigger specified by the **Trigger type** is received. Inputs to this port must have the same built-in data type as inputs to the Push and Pop input ports.

### **Clear output port on reset**

Reset the Out port to zero (in addition to clearing the stack) when a trigger is received at the Rst input port.

**Supported  
Data  
Types**

<b>Port</b>	<b>Supported Data Types</b>
In	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Push	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul> <p>Inputs to this port must have the same built-in data type as inputs to the Pop and Rst input ports</p>
Pop	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul> <p>Inputs to this port must have the same built-in data type as inputs to the Push and Rst input ports.</p>

# Stack

Port	Supported Data Types
Rst	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul> <p>Inputs to this port must have the same built-in data type as inputs to the Push and Pop input ports.</p>
Out	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Empty	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Boolean</li></ul>
Full	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Boolean</li></ul>
Num	<ul style="list-style-type: none"><li>• Double-precision floating point</li></ul> <p>The block outputs a double-precision floating-point value at this port when the data type of the In port is double-precision floating-point.</p> <ul style="list-style-type: none"><li>• 32-bit unsigned integers</li></ul> <p>The block outputs a 32-bit unsigned integer value at this port when the data type of the In port is anything other than double-precision floating-point.</p>

**See Also**


- Buffer                      DSP System Toolbox
- Delay Line                 DSP System Toolbox
- Queue                        DSP System Toolbox

# Standard Deviation

**Purpose** Find standard deviation of input or sequence of inputs

**Library** Statistics  
dspstat3

## Description



The Standard Deviation block computes the standard deviation of each row or column of the input, along vectors of a specified dimension of the input, or of the entire input. The Standard Deviation block can also track the standard deviation of a sequence of inputs over a period of time. The **Running standard deviation** parameter selects between basic operation and running operation.

## Basic Operation

When you do not select the **Running standard deviation** check box, the block computes the standard deviation of each row or column of the input, along vectors of a specified dimension of the input, or of the entire input at each individual sample time, and outputs the array  $y$ . Each element in  $y$  contains the standard deviation of the corresponding column, row, vector, or entire input. The output  $y$  depends on the setting of the **Find the standard deviation value over** parameter. For example, consider a 3-dimensional input signal of size  $M$ -by- $N$ -by- $P$ :

- **Entire input** — The output at each sample time is a scalar that contains the standard deviation of the entire input.

```
y = std(u(:))      % Equivalent MATLAB code
```

- **Each Row** — The output at each sample time consists of an  $M$ -by-1-by- $P$  array, where each element contains the standard deviation of each vector over the second dimension of the input. For an input that is an  $M$ -by- $N$  matrix, the output at each sample time is an  $M$ -by-1 column vector.

```
y = std(u,0,2)    % Equivalent MATLAB code
```

- **Each Column** — The output at each sample time consists of a 1-by- $N$ -by- $P$  array, where each element contains the standard deviation of each vector over the first dimension of the input. For an input that is an  $M$ -by- $N$  matrix, the output at each sample time is a 1-by- $N$  row vector.

```
y = std(u,0,1)      % Equivalent MATLAB code
```

In this mode, the block treats length- $M$  unoriented vector inputs as  $M$ -by-1 column vectors.

- **Specified Dimension** — The output at each sample time depends on **Dimension**. If **Dimension** is set to 1, the output is the same as when you select **Each column**. If **Dimension** is set to 2, the output is the same as when you select **Each row**. If **Dimension** is set to 3, the output at each sample time is an  $M$ -by- $N$  matrix containing the standard deviation of each vector over the third dimension of the input.

```
y = std(u,0,Dimension)  % Equivalent MATLAB code
```

For purely real or purely imaginary inputs, the standard deviation of the  $j$ th column of an  $M$ -by- $N$  input matrix is the square root of its variance:

$$y_j = \sigma_j = \sqrt{\frac{\sum_{i=1}^M |u_{ij} - \mu_j|^2}{M-1}} \quad 1 \leq j \leq N$$

For complex inputs, the output is the *total standard deviation*, which equals the square root of the *total variance*, or the square root of the sum of the variances of the real and imaginary parts. The standard deviation of each column in an  $M$ -by- $N$  input matrix is given by:

$$\sigma_j = \sqrt{\sigma_{j,\text{Re}}^2 + \sigma_{j,\text{Im}}^2}$$

# Standard Deviation

---

---

**Note** The total standard deviation does *not* equal the sum of the real and imaginary standard deviations.

---

## Running Operation

When you select the **Running standard deviation** check box, the block tracks the standard deviation of successive inputs to the block. In this mode, you must also specify a value for the **Input processing** parameter:

- When you select **Elements as channels (sample based)**, the block outputs an  $M$ -by- $N$  array. Each element  $y_{ij}$  of the output contains the standard deviation of the element  $u_{ij}$  over all inputs since the last reset.
- When you select **Columns as channels (frame based)**, the block outputs an  $M$ -by- $N$  matrix. Each element  $y_{ij}$  of the output contains the standard deviation of the  $j$ th column over all inputs since the last reset, up to and including element  $u_{ij}$  of the current input.

## Running Operation for Variable-Size Inputs

When your inputs are of variable size, and you select the **Running standard deviation** check box, there are two options:


- If you set the **Input processing** parameter to **Elements as channels (sample based)**, the state is reset.
- If you set the **Input processing** parameter to **Columns as channels (frame based)**, then there are two cases:
  - When the input size difference is in the number of channels (i.e., number of columns), the state is reset.
  - When the input size difference is in the length of channels (i.e., number of rows), there is no reset and the running operation is carried out as usual.

## Resetting the Running Standard Deviation

The block resets the running standard deviation whenever a reset event is detected at the optional Rst port. The reset sample time must be a positive integer multiple of the input sample time.

You specify the reset event in the **Reset port** parameter:


- None disables the Rst port.
- Rising edge — Triggers a reset operation when the Rst input does one of the following:
  - Rises from a negative value to a positive value or zero
  - Rises from zero to a positive value, where the rise is not a continuation of a rise from a negative value to zero (see the following figure)



- Falling edge — Triggers a reset operation when the Rst input does one of the following:
  - Falls from a positive value to a negative value or zero
  - Falls from zero to a negative value, where the fall is not a continuation of a fall from a positive value to zero (see the following figure)

# Standard Deviation

---



- Either edge — Triggers a reset operation when the Rst input is a Rising edge or Falling edge (as described earlier)
- Non-zero sample — Triggers a reset operation at each sample time that the Rst input is not zero

---

**Note** When running simulations in the Simulink MultiTasking mode, reset signals have a one-sample latency. Therefore, when the block detects a reset event, there is a one-sample delay at the reset port rate before the block applies the reset. For more information on latency and the Simulink tasking modes, see “Excess Algorithmic Delay (Tasking Latency)” and “Scheduling” in the *Simulink Coder User’s Guide*.

---

## ROI Processing

To calculate the statistical value within a particular region of interest (ROI) of the input, select the **Enable ROI processing** check box. This option is only available when the **Find the standard deviation value over** parameter is set to Entire input and the **Running standard deviation** check box is not selected. ROI processing is only supported for 2-D inputs.

---

**Note** Full ROI processing is available only if you have a Computer Vision System Toolbox license. If you do not have a Computer Vision System Toolbox license, you can still use ROI processing, but are limited to the **ROI type** Rectangles.

---

Use the **ROI type** parameter to specify whether the ROI is a rectangle, line, label matrix, or binary mask. A binary mask is a binary image that enables you to specify which pixels to highlight, or select. In a label matrix, pixels equal to 0 represent the background, pixels equal to 1 represent the first object, pixels equal to 2 represent the second object, and so on. When the **ROI type** parameter is set to `Label matrix`, the Label and Label Numbers ports appear on the block. Use the Label Numbers port to specify the objects in the label matrix for which the block calculates statistics. The input to this port must be a vector of scalar values that correspond to the labeled regions in the label matrix. For more information about the format of the input to the ROI port when the ROI is a rectangle or a line, see the Draw Shapes block reference page.

For rectangular ROIs, use the **ROI portion to process** parameter to specify whether to calculate the statistical value for the entire ROI or just the ROI perimeter.

Use the **Output** parameter to specify the block output. The block can output separate statistical values for each ROI or the statistical value for all specified ROIs. This parameter is not available if, for the **ROI type** parameter, you select `Binary mask`.

If, for the **ROI type** parameter, you select `Rectangles` or `Lines`, the **Output flag indicating if ROI is within image bounds** check box appears in the dialog box. If you select this check box, the Flag port appears on the block. The following tables describe the Flag port output based on the block parameters.

# Standard Deviation

---

## Output = Individual statistics for each ROI

Flag Port Output	Description
0	ROI is completely outside the input image.
1	ROI is completely or partially inside the input image.

## Output = Single statistic for all ROIs

Flag Port Output	Description
0	All ROIs are completely outside the input image.
1	At least one ROI is completely or partially inside the input image.

If the ROI is partially outside the image, the block only computes the statistical values for the portion of the ROI that is within the image.

If, for the **ROI type** parameter, you select **Label matrix**, the **Output flag indicating if input label numbers are valid** check box appears in the dialog box. If you select this check box, the Flag port appears on the block. The following tables describe the Flag port output based on the block parameters.

## Output = Individual statistics for each ROI


Flag Port Output	Description
0	Label number is not in the label matrix.
1	Label number is in the label matrix.

**Output = Single statistic for all ROIs**

Flag Port Output	Description
0	None of the label numbers are in the label matrix.
1	At least one of the label numbers is in the label matrix.


## Examples

In the following `ex_standarddeviation_ref` model, the Standard Deviation block calculates the running standard deviation of a 3-by-2 matrix input,  $u$ . The **Input processing** parameter is set to **Columns as channels (frame based)**, so the block processes the input as a two channel signal with a frame size of three. The running standard deviation is reset at  $t=2$  by an impulse to the block's Rst port.




The operation of the block is shown in the following figure.

# Standard Deviation



## Dialog Box



### Running standard deviation

Enables running operation when selected.

### Input processing

Specify how the block should process the input when computing the running standard deviation. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

This parameter appears only when you select the **Running standard deviation** check box.

# Standard Deviation

---

---

**Note** The option Inherit from input (this choice will be removed - see release notes) will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Reset port

Specify the reset event that causes the block to reset the running standard deviation. The sample time of the input to the Rst port must be a positive integer multiple of the input sample time. This parameter appears only when you select the **Running standard deviation** check box. For more information, see “Resetting the Running Standard Deviation” on page 2-1419.

## Find the standard deviation value over

Specify whether to find the standard deviation value along rows, columns, entire input, or the dimension specified in the **Dimension** parameter. For more information, see “Basic Operation” on page 2-1416.

## Treat sample-based row input as a column

Select to treat sample-based length- $M$  row vector inputs as  $M$ -by-1 column vectors. This parameter is only visible when the **Find the standard deviation value over** parameter is set to Each column.

---

**Note** This check box will be removed in a future release. See “Sample-Based Row Vector Processing Changes” in the DSP System Toolbox Release Notes.

---

## Dimension

Specify the dimension (one-based value) of the input signal, over which the standard deviation is computed. The value of this parameter cannot exceed the number of dimensions in the input signal. This parameter is only visible when the **Find the**

**standard deviation value over** parameter is set to Specified dimension.

## Enable ROI Processing

Select this check box to calculate the statistical value within a particular region of each image. This parameter is only available when the **Find the standard deviation value over** parameter is set to Entire input, and the block is not in running mode.

---

**Note** Full ROI processing is available only when you have a Computer Vision System Toolbox license. If you do not have a Computer Vision System Toolbox license, you can still use ROI processing, but are limited to the **ROI type** Rectangles.

---

## ROI type

Specify the type of ROI you want to use. Your choices are Rectangles, Lines, Label matrix, or Binary mask.

## ROI portion to process

Specify whether you want to calculate the statistical value for the entire ROI or just the ROI perimeter. This parameter is only visible if, for the **ROI type** parameter, you specify Rectangles.

## Output

Specify the block output. The block can output a vector of separate statistical values for each ROI or a scalar value that represents the statistical value for all the specified ROIs. This parameter is not available if, for the **ROI type** parameter, you select Binary mask.

## Output flag

**Output flag indicating if ROI is within image bounds**

**Output flag indicating if label numbers are valid**

# Standard Deviation

---

When you select either of these check boxes, the Flag port appears on the block. For a description of the Flag port output, see the tables in “ROI Processing” on page 2-1420.

The **Output flag indicating if ROI is within image bounds** check box is only visible when you select Rectangles or Lines as the **ROI type**.

The **Output flag indicating if label numbers are valid** check box is only visible when you select Label matrix for the **ROI type** parameter.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Reset	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
ROI	Rectangles and lines: <ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul> Binary Mask:

Port	Supported Data Types
	<ul style="list-style-type: none"><li>• Boolean</li></ul>
Label	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Label Numbers	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Flag	<ul style="list-style-type: none"><li>• Boolean</li></ul>

## See Also

Mean	DSP System Toolbox
RMS	DSP System Toolbox
Variance	DSP System Toolbox
std	MATLAB

# Submatrix

---


## Purpose

Select subset of elements (submatrix) from matrix input

## Library

- Math Functions / Matrices and Linear Algebra / Matrix Operations  
dspmtx3
- Signal Management / Indexing  
dspindex

## Description



The Submatrix block extracts a contiguous submatrix from the  $M$ -by- $N$  input matrix  $u$ . The block treats length- $M$  unoriented vector input as an  $M$ -by-1 matrix. The **Row span** parameter provides three options for specifying the range of rows in  $u$  to be retained in submatrix output  $y$ :

- All rows  
Specifies that  $y$  contains all  $M$  rows of  $u$ .
- One row  
Specifies that  $y$  contains only one row from  $u$ . The **Row** parameter (described below) is enabled to allow selection of the desired row.
- Range of rows  
Specifies that  $y$  contains one or more rows from  $u$ . The **Starting row** and **Ending row** parameters (described below) are enabled to allow selection of the desired range of rows.

The **Column span** parameter contains a corresponding set of three options for specifying the range of columns in  $u$  to be retained in submatrix  $y$ : All columns, One column, or Range of columns. The One column option enables the **Column** parameter, and Range of columns options enable the **Starting column** and **Ending column** parameters.

### Range Specification Options

When you select One row or Range of rows from the **Row span** parameter, you specify the desired row or range of rows in the **Row** parameter, or the **Starting row** and **Ending row** parameters. Similarly, when you select One column or Range of columns from the

**Column span** parameter, you specify the desired column or range of columns in the **Column** parameter, or the **Starting column** and **Ending column** parameters.

The **Row**, **Column**, **Starting row** or **Starting column** can be specified in six ways:

- **First**

For rows, this specifies that the first row of  $u$  should be used as the first row of  $y$ . When all columns are to be included, this is equivalent to  $y(1,:) = u(1,:)$ .

For columns, this specifies that the first column of  $u$  should be used as the first column of  $y$ . When all rows are to be included, this is equivalent to  $y(:,1) = u(:,1)$ .

- **Index**

For rows, this specifies that the row of  $u$ , `firstrow`, forward-indexed by the **Row index** parameter or the **Starting row index** parameter, should be used as the first row of  $y$ . When all columns are to be included, this is equivalent to  $y(1,:) = u(\text{firstrow},:)$ .

For columns, this specifies that the column of  $u$ , forward-indexed by the **Column index** parameter or the **Starting column index** parameter, `firstcol`, should be used as the first column of  $y$ . When all rows are to be included, this is equivalent to  $y(:,1) = u(:,\text{firstcol})$ .

- **Offset from last**

For rows, this specifies that the row of  $u$  offset from row  $M$  by the **Row offset** or **Starting row offset** parameter, `firstrow`, should be used as the first row of  $y$ . When all columns are to be included, this is equivalent to  $y(1,:) = u(M-\text{firstrow},:)$ .

For columns, this specifies that the column of  $u$  offset from column  $N$  by the **Column offset** or **Starting column offset** parameter, `firstcol`, should be used as the first column of  $y$ . When all rows are to be included, this is equivalent to  $y(:,1) = u(:,N-\text{firstcol})$ .

# Submatrix

---

- Last

For rows, this specifies that the last row of  $u$  should be used as the only row of  $y$ . When all columns are to be included, this is equivalent to  $y = u(M, :)$ .

For columns, this specifies that the last column of  $u$  should be used as the only column of  $y$ . When all rows are to be included, this is equivalent to  $y = u(:, N)$ .

- Offset from middle

When you select this option, the block selects the first row or column of the output  $y$  by adding the specified offset to the middle row or column of the input  $u$ . When the number,  $X$ , of input rows or columns is even, the block defines the middle one as  $X/2 + 1$ . When the number of input rows or columns is odd, the block defines the middle one as  $\text{ceil}(X/2)$ .

When all columns are to be included, the following code defines the starting row:  $y(1, :) = u(\text{MiddleRow} + \text{Offset}, :)$ , where **Offset** is the value of the **Row offset** or **Starting row offset** parameter. When all rows are to be included, the following code defines the starting column:  $y(:, 1) = u(:, \text{MiddleColumn} + \text{Offset})$ , where **Offset** is the value of the **Column offset** or **Starting column offset** parameter.

- Middle

When you select this option, the block uses the middle row or column of the input  $u$  as the first row or column of the output  $y$ . When the number,  $X$ , of input rows or columns is even, the block defines the middle one as  $X/2 + 1$ . When the number of input rows or columns is odd, the block defines the middle one as  $\text{ceil}(X/2)$ .

When all columns are to be included, the following code defines the starting row:  $y = u(\text{MiddleRow}, :)$ . When all rows are to be included, the following code defines the starting column:  $y = u(:, \text{MiddleColumn})$ .

The **Ending row** or **Ending column** can similarly be specified in five ways:

- Index

For rows, this specifies that the row of  $u$  forward-indexed by the **Ending row index** parameter, `lastrow`, should be used as the last row of  $y$ . When all columns are to be included, this is equivalent to  $y(\text{end}, :) = u(\text{lastrow}, :)$ .

For columns, this specifies that the column of  $u$  forward-indexed by the **Ending column index** parameter, `lastcol`, should be used as the last column of  $y$ . When all rows are to be included, this is equivalent to  $y(:, \text{end}) = u(:, \text{lastcol})$ .

- Offset from last

For rows, this specifies that the row of  $u$  offset from row  $M$  by the **Ending row offset** parameter, `lastrow`, should be used as the last row of  $y$ . When all columns are to be included, this is equivalent to  $y(\text{end}, :) = u(M - \text{lastrow}, :)$ .

For columns, this specifies that the column of  $u$  offset from column  $N$  by the **Ending column offset** parameter, `lastcol`, should be used as the last column of  $y$ . When all rows are to be included, this is equivalent to  $y(:, \text{end}) = u(:, N - \text{lastcol})$ .

- Last

For rows, this specifies that the last row of  $u$  should be used as the last row of  $y$ . When all columns are to be included, this is equivalent to  $y(\text{end}, :) = u(M, :)$ .

For columns, this specifies that the last column of  $u$  should be used as the last column of  $y$ . When all rows are to be included, this is equivalent to  $y(:, \text{end}) = u(:, N)$ .

- Offset from middle

When you select this option, the block selects the last row or column of the output  $y$  by adding the specified offset to the middle row or column of the input  $u$ . When the number,  $X$ , of input rows or columns

# Submatrix

is even, the block defines the middle one as  $X/2 + 1$ . When the number of input rows or columns is odd, the block defines the middle one as  $\text{ceil}(X/2)$ .

When all columns are to be included, the following code defines the ending row:  $y(\text{end}, :) = u(\text{MiddleRow} + \text{Offset}, :)$ , where **Offset** is the value of the **Ending row offset** parameter. When all rows are to be included, the following code defines the ending column:  $y(:, \text{end}) = u(:, \text{MiddleColumn} + \text{Offset})$ , where **Offset** is the value of the **Ending column offset** parameter.

- Middle

When you select this option, the block uses the middle row or column of the input  $u$  as the last row or column of the output  $y$ . When the number,  $X$ , of input rows or columns is even, the block defines the middle one as  $X/2 + 1$ . When the number of input rows or columns is odd, the block defines the middle one as  $\text{ceil}(X/2)$ .


When all columns are to be included, the following code defines the ending row:  $y(\text{end}, :) = u(\text{MiddleRow}, :)$ . When all rows are to be included, the following code defines the ending column:  $y(:, \text{end}) = u(:, \text{MiddleColumn})$ .

This block supports Simulink virtual buses.

## Examples


The `ex_submatrix_ref` model uses a Submatrix block to extract a 3-by-2 submatrix from the lower-right corner of a 5-by-7 input matrix.

The following figure shows the operation of the Submatrix block with a 5-by-7 input matrix of random integer elements, `randi([0 9], 5, 7)`.



There are often several possible parameter combinations that you can use to select the *same* submatrix from the input. For example, in the case of a 5-by-7 input matrix, instead of specifying Last for **Ending column**, you could select the same submatrix by specifying

- **Ending column** = Index
- **Ending column index** = 7



## Dialog Box

The parameters displayed in the dialog box vary for different menu combinations. Only some of the parameters listed below are visible in the dialog box at any one time.

# Submatrix

---

## **Row span**

The range of input rows to be retained in the output. Options are All rows, One row, or Range of rows.

## **Row/Starting row**

The input row to be used as the first row of the output. **Row** is enabled when you select One row from **Row span**, and **Starting row** when you select Range of rows from **Row span**.

## **Row index/Starting row index**

The index of the input row to be used as the first row of the output. **Row index** is enabled when you select Index from Row, and **Starting row index** when you select Index from **Starting row**.

## **Row offset/Starting row offset**

The offset of the input row to be used as the first row of the output. **Row offset** is enabled when you select Offset from middle or Offset from last from **Row**, and Starting row offset is enabled when you select Offset from middle or Offset from last from **Starting row**.

## **Ending row**

The input row to be used as the last row of the output. This parameter is enabled when you select Range of rows from **Row span** and you select any option but Last from **Starting row**.

## **Ending row index**

The index of the input row to be used as the last row of the output. This parameter is enabled when you select Index from **Ending row**.

## **Ending row offset**

The offset of the input row to be used as the last row of the output. This parameter is enabled when you select Offset from middle or Offset from last from **Ending row**.

## **Column span**

The range of input columns to be retained in the output. Options are All columns, One column, or Range of columns.

## **Column/Starting column**

The input column to be used as the first column of the output.

**Column** is enabled when you select **One column** from **Column span**, and **Starting column** is enabled when you select **Range of columns** from **Column span**.

## **Column index/Starting column index**

The index of the input column to be used as the first column of the output. **Column index** is enabled when you select **Index** from **Column**, and **Starting column index** is enabled when you select **Index** from **Starting column**.

## **Column offset/Starting column offset**

The offset of the input column to be used as the first column of the output. **Column offset** is enabled when you select **Offset from middle** or **Offset from last** from **Column**. **Starting column offset** is enabled when you select **Offset from middle** or **Offset from last** from **Starting column**.

## **Ending column**

The input column to be used as the last column of the output. This parameter is enabled when you select **Range of columns** from **Column span** and you select any option but **Last** from **Starting column**.

## **Ending column index**

The index of the input column to be used as the last column of the output. This parameter is enabled when you select **Index** from **Ending column**.

## **Ending column offset**

The offset of the input column to be used as the last column of the output. This parameter is enabled when you select **Offset from middle** or **Offset from last** from **Ending column**.

# Submatrix

---

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li><li>• Enumerated</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li><li>• Enumerated</li></ul>

## See Also

Reshape	Simulink
Selector	Simulink
Variable Selector	DSP System Toolbox
reshape	MATLAB

See “Split Multichannel Signals into Several Multichannel Signals” for related information.


## Purpose

Solve  $AX=B$  using singular value decomposition

## Library

Math Functions / Matrices and Linear Algebra / Linear System Solvers  
dpsolvers

## Description




The SVD Solver block solves the linear system  $AX=B$ , which can be overdetermined, underdetermined, or exactly determined. The system is solved by applying singular value decomposition (SVD) factorization to the  $M$ -by- $N$  matrix  $A$ , at the A port. The input to the B port is the right side  $M$ -by- $L$  matrix,  $B$ . The block treats length- $M$  unoriented vector input as an  $M$ -by-1 matrix.

The output at the X port is the  $N$ -by- $L$  matrix,  $X$ .  $X$  is chosen to minimize the sum of the squares of the elements of  $B-AX$  (the residual). When  $B$  is a vector, this solution minimizes the vector 2-norm of the residual. When  $B$  is a matrix, this solution minimizes the matrix Frobenius norm of the residual. In this case, the columns of  $X$  are the solutions to the  $L$  corresponding systems  $AX_k=B_k$ , where  $B_k$  is the  $k$ th column of  $B$ , and  $X_k$  is the  $k$ th column of  $X$ .

$X$  is known as the minimum-norm-residual solution to  $AX=B$ . The minimum-norm-residual solution is unique for overdetermined and exactly determined linear systems, but it is not unique for underdetermined linear systems. Thus when the SVD Solver block is applied to an underdetermined system, the output  $X$  is chosen such that the number of nonzero entries in  $X$  is minimized.

# SVD Solver

## Dialog Box



### Show error status port

Select to enable the E output port, which reports a failure to converge. The possible values you can receive on the port are:

- 0 — The singular value decomposition calculation converges.
- 1 — The singular value decomposition calculation does not converge.

If the singular value decomposition calculation fails to converge, the output at port X is an undefined matrix of the correct size.

## Supported Data Types

Port	Supported Data Types
A	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
B	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
X	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
E	<ul style="list-style-type: none"><li>• Boolean</li></ul>

## See Also

Autocorrelation LPC	DSP System Toolbox
Cholesky Solver	DSP System Toolbox
LDL Solver	DSP System Toolbox
Levinson-Durbin	DSP System Toolbox
LU Inverse	DSP System Toolbox
Pseudoinverse	DSP System Toolbox
QR Solver	DSP System Toolbox
Singular Value Decomposition	DSP System Toolbox

See “Linear System Solvers” for related information.


# Time Scope

---

**Purpose** Display time-domain signals


**Library** Sinks  
dspsnks4

## Description



The Time Scope block displays signals in the time domain. The Time Scope block accepts input signals with the following characteristics:

- Continuous or discrete sample time
- Real- or complex-valued
- Fixed or variable size dimensions
- Floating- or fixed-point data type
- N-dimensional
- Simulink enumerations



You can use the Time Scope block in models running in Normal or Accelerator simulation modes. You can also use the Time Scope block in models running in Rapid Accelerator or External simulation modes, with some limitations. See the “Supported Simulation Modes” on page 2-1525 section for more information.

You can use the Time Scope block inside of all subsystems and conditional subsystems. *Conditional subsystems* include enabled subsystems, triggered subsystems, enabled and triggered subsystems, and function-call subsystems. See “About Conditional Subsystems” in the Simulink documentation for more information.

For an example that uses the Time Scope block, see the Display Time-Domain Data section in the DSP System Toolbox documentation.

See the following sections for more information on the Time Scope:

- “Displaying Multiple Signals” on page 2-1444
- “Signal Display” on page 2-1447
- “Toolbar” on page 2-1451
- “Simulation Toolbar” on page 2-1454
- “Measurements Panels” on page 2-1456
- “Properties Dialog Box” on page 2-1479
- “Style Dialog Box” on page 5-1135
- “Simulation Stepping Options” on page 2-1493
- “Core — General UI Options” on page 2-1495
- “Visuals — Time Domain Options” on page 2-1498
- “Tools — Plot Navigation Options” on page 2-1507
- “Sources — Simulink Options” on page 2-1511
- “Examples” on page 2-1511
- “Supported Data Types” on page 2-1525
- “Supported Simulation Modes” on page 2-1525

---

**Note** For information about the Time Scope System object, see `dsp.TimeScope`.

---

## Displaying Multiple Signals

### Multiple Signal Input

You can configure the Time Scope block to show multiple signals within the same display or on separate displays. By default, the signals appear as different-colored lines on the same display. The signals can have

different dimensions, sample rates, and data types. Each signal can be either real or complex valued. You can set the number of input ports on the Time Scope block in the following ways:

- Right-click the Time Scope block in your model to bring up the context menu. Point your cursor to the **Signals & Ports > Number of Input Ports** item on the context menu. You can then select the number of input ports for the Time Scope block. If the desired number of input signals is 1, 2, or 3, then click on the appropriate value. To configure a Time Scope block to have more than three input ports, select **More**, and enter a number for the **Number of input ports** parameter.
- Open the Time Scope window by double-clicking the Time Scope block in your model. To specify how many input ports the Time Scope block should have, in the Time Scope menu, select **File > Number of Input Ports** from the scope menu.

An input signal may contain multiple channels, depending on its dimensions. Multiple channels of data are always shown as different-colored lines on the same display.

## Multiple Time Offsets

You can offset all channels of an input signal by the same number of seconds or offset each channel independently. To offset all channels equally, select **View > Properties**, and specify a scalar value for the **Time display offset** parameter on the **Main** pane. To offset each channel independently, specify a vector of offset values. When you specify a **Time display offset** vector of length  $N$ , the scope offsets the input channels as follows:


- When  $N$  is equal to the number of input channels, the scope offsets each channel according to its corresponding value in the offset vector.
- When  $N$  is less than the number of input channels, the scope applies the values you specify in the offset vector to the first  $N$  input channels. The scope does not offset the remaining channels.

# Time Scope


- When  $N$  is greater than the number of input channels, the scope offsets each input channel according to the corresponding value in the offset vector. The scope ignores all values in the offset vector that do not correspond to a channel of the input.

## Multiple Displays

You can display multiple channels of data on different displays in the Scope window. In the Scope toolbar, select **View > Layout**, or select the Layout button (  ). This feature allows you to tile the window into a number of separate displays, up to a grid of 4 rows and 4 columns. For example, if there are three inputs to the Scope, you can display the signals in separate displays by selecting row 3, column 1, as shown in the following figure.



After you select row 3, column 1, the Scope window has three separate displays, as shown in the following figure.




## Signal Display

Time Scope uses the simulation start time and stop time in order to determine the default time range. However, you can define the length of simulation time for which the Time Scope displays data. To change the signal display settings, select **View > Properties** to bring up the Properties dialog box. Then, modify the values for the **Time span** and **Time display offset** parameters on the **Time** tab. For example, if you set the **Time span** to 20 seconds and the **Time display offset** to 0, the scope displays 20 seconds' worth of simulation data at a time. The values on the *time*-axis of the Time Scope display remain the same throughout simulation.

To communicate the simulation time that corresponds to the current display, the scope uses the **Time units**, **Time offset**, and **Simulation time** indicators on the scope window. The following figure highlights these and other important aspects of the Time Scope window.

# Time Scope



- **Minimum time-axis limit** — The Time Scope sets the minimum *time*-axis limit using the value of the **Time display offset** parameter on the **Time** tab of the Properties dialog box. If you specify a vector of values for the **Time display offset** parameter, the scope uses the smallest of those values to set the minimum *time*-axis limit.
- **Maximum time-axis limit** — The Time Scope sets the maximum *time*-axis limit by summing the value of **Time display offset** parameter with the value of the **Time span** parameter. If you specify a vector of values for the **Time display offset** parameter, the scope sets the maximum *time*-axis limit by summing the largest of those values with the value of the **Time span** parameter.
- **Simulation status** — Provides the current status of the model simulation. The status can be one of the following conditions:
  - Initializing
  - Ready
  - Running
  - Paused

The **Simulation status** is part of the **Status Bar** in the Time Scope window. You can choose to hide or display the entire **Status Bar**. From the Time Scope menu, select **View > Status Bar**.

- **Time units** — The units used to describe the *time*-axis. The Time Scope sets the time units using the value of the **Time Units** parameter on the **Time** tab of the Properties dialog box. By default, this parameter is set to **Metric** (based on Time Span) and displays in metric units such as milliseconds, microseconds, minutes, days, etc. You can change it to **Seconds** to always display the *time*-axis values in units of seconds. You can change it to **None** to not display any units on the *time*-axis. When you set this parameter to **None**, then Time Scope shows only the word **Time** on the *time*-axis.

To hide both the word **Time** and the values on the *time*-axis, set the **Show time-axis labels** parameter to **None**. To hide both the word **Time** and the values on the *time*-axis in all displays except the bottom ones in each column of displays, set this parameter to **Bottom Displays Only**. This behavior differs from the Simulink Scope block, which always shows the values but never shows a label on the *x*-axis.

- **Time offset** — The **Time offset** value helps you determine the simulation times for which the scope is displaying data. The value is always in the range  $0 \leq \text{Time offset} \leq \text{Simulation time}$ .


For example, if you set the **Time span** to 20 seconds, and you see a **Time offset** of 0 (secs) on the scope window, the scope is displaying data for the first 0 to 20 seconds of simulation time. When you see the **Time offset** change to 20 (secs), the scope is displaying data for simulation times is greater than 20 seconds and less than or equal to 40 seconds. The scope continues to update the **Time offset** value until the simulation is complete.

- **Simulation time** — When the model is running or simulation has been paused, the scope displays the current simulation time. If the model simulation completes or is stopped, the scope displays the time at which the simulation stopped. The **Simulation time** is part of the **Status Bar** in the Time Scope window. You can choose to hide or display the entire **Status Bar**. From the Time Scope menu, select **View > Status Bar** .

# Time Scope

## Axes Maximization

You can specify whether to display the Time Scope in maximized axes mode. In this mode, the axes are expanded to fill the entire display. To conserve space, no labels appear in each display. Instead, tick-mark values appear on top of the plotted data. The following figure highlights the important indicators in this mode of the Time Scope window.



To toggle this mode, in the Time Scope menu, select **View > Properties** to bring up the Properties dialog box. In the **Main** pane, set the **Maximize axes** parameter. You can select one of the following options:

- Auto — In this mode, the axes appear maximized in all displays only if the **Title** and **Y-Axis label** parameters are empty for every display. If you enter any value in any display for either of these parameters, the axes are not maximized.
- On — In this mode, the axes appear maximized in all displays. Any values entered into the **Title** and **Y-Axis label** parameters are hidden.
- Off — In this mode, none of the axes appear maximized.

The default setting is Auto.

## Reduce Updates to Improve Performance

By default, the Time Scope updates the displays periodically at a rate not exceeding 20 hertz. If you would like the Time Scope to update on every simulation time step, you can disable the **Reduce Updates to Improve Performance** option. In the Time Scope menu, select

**Simulation > Reduce Updates to Improve Performance** to clear the check box. However, as a recommended practice, you can leave this option enabled because doing so can significantly improve the speed of the simulation.

## Toolbar

The Time Scope toolbar contains the following buttons.

### Print and Properties Buttons

Button	Menu Location	Shortcut Keys	Description
	<b>File &gt; Print</b>	<b>Ctrl+P</b>	Print the current scope window. Printing is available only when the scope display is not changing. You can enable printing by placing the scope in snapshot mode, pausing or stopping model simulation, or simulating the model in step-forward mode.  To print the current scope window to a figure rather than sending it to your printer, select <b>File &gt; Print to figure</b> .
	<b>View &gt; Properties</b>	N/A	Open the <b>Properties</b> dialog box. See the “Properties Dialog Box” on page 2-1479 section for more information.

# Time Scope

## Axes Control Buttons

	<b>Tools &gt; Zoom In</b>	N/A	When this tool is active, you can zoom in on the scope window. To do so, click in the center of your area of interest, or click and drag your cursor to draw a rectangular area of interest inside the scope window.
	<b>Tools &gt; Zoom X</b>	N/A	When this tool is active, you can zoom in on the x-axis. To do so, click inside the scope window, or click and drag your cursor along the x-axis over your area of interest.
	<b>Tools &gt; Zoom Y</b>	N/A	When this tool is active, you can zoom in on the y-axis. To do so, click inside the scope window, or click and drag your cursor along the y-axis over your area of interest.
	<b>Tools &gt; Scale Axes Limits</b>	<b>Ctrl+A</b>	<p>Click this button to scale the axes in the active scope window.</p> <p>Alternatively, you can enable automatic axes scaling by selecting one of the following options from the <b>Tools</b> menu:</p> <ul style="list-style-type: none"><li>• <b>Automatically Scale Axes Limits</b> — When you select this option, the scope scales the axes as needed during simulation.</li><li>• <b>Scale Axes Limits at Stop</b> — When you select this option, the scope scales the axes each time the simulation is stopped.</li></ul>

## Measurements Buttons

	<b>Tools &gt; Measurements &gt; Cursor Measurements</b>	N/A	<p>Open or close the <b>Cursor Measurements</b> panel. This panel puts screen cursors on all the displays.</p> <p>See the “Cursor Measurements Panel” on page 5-1114 section for more information.</p>
	<b>Tools &gt; Measurements &gt; Signal Statistics</b>	N/A	<p>Open or close the <b>Signal Statistics</b> panel. This panel displays the maximum, minimum, peak-to-peak difference, mean, median, RMS values of a selected signal, and the times at which the maximum and minimum occur.</p> <p>See the “Signal Statistics Panel” on page 5-1116 section for more information.</p>
	<b>Tools &gt; Measurements &gt; Bilevel Measurements</b>	N/A	<p>Open or close the <b>Bilevel Measurements</b> panel. This panel displays information about a selected signal’s transitions, overshoots or undershoots, and cycles.</p> <p>See the “Bilevel Measurements Panel” on page 5-1118 section for more information.</p>
	<b>Tools &gt; Measurements &gt; Peak Finder</b>	N/A	<p>Open or close the <b>Peak Finder</b> panel. This panel displays maxima and the times at which they occur, allowing the settings for peak threshold, maximum number of peaks, and peak excursion to be modified.</p>

# Time Scope

			See the “Peak Finder Panel” on page 5-1132 section for more information.
--	--	--	--

## Other Buttons

	<b>View &gt; Layout</b>	N/A	Arrange the layout of displays in the Time Scope. This feature allows you to tile your screen into a number of separate displays, up to a grid of 4 rows and 4 columns. You may find multiple displays useful when the Time Scope takes multiple input signals. The default display is 1 row and 1 column. See the “Multiple Displays” on page 5-1104 section for more information.
---	-------------------------	-----	---

You can control whether this toolbar appears in the Time Scope window. From the Time Scope menu, select **View > Toolbar**.

## Simulation Toolbar

The Simulation Toolbar contains the following buttons.

<b>Button</b>	<b>Menu Location</b>	<b>Shortcut Keys</b>	<b>Description</b>
	<b>Simulation &gt; Simulation Stepping Options</b>	N/A	Open the <b>Simulation Stepping Options</b> dialog box. This button appears only when you have previous stepping disabled. See the “Simulation Stepping Options”

Button	Menu Location	Shortcut Keys	Description
			on page 2-1493 section for more information.
	<b>Simulation &gt; Previous Step</b>	N/A	Advance the model simulation backward by one time step. This button appears only when you have previous stepping enabled and the model simulation is paused.
	<b>Simulation &gt; Run</b>	<b>Ctrl+T, p, Space</b>	Start the model simulation. This button appears only when the model simulation is stopped.
	<b>Simulation &gt; Continue</b>	<b>p, Space</b>	Continue the model simulation. This button appears only when the model simulation is paused.
	<b>Simulation &gt; Pause</b>	<b>p, Space</b>	Pause the model simulation. This button appears only when the model simulation is running.
	<b>Simulation &gt; Step Forward</b>	<b>Right arrow, Page Down</b>	Advance the model simulation forward by one time step. This button starts the model simulation, allows it to run for one time step, and then pauses it again. The scope window then updates with the latest data.
	<b>Simulation &gt; Stop</b>	<b>Ctrl+T, s</b>	Stop the model simulation. This button appears only when the model simulation is running or paused.

# Time Scope

Button	Menu Location	Shortcut Keys	Description
	<b>Simulation &gt; Simulink Snapshot</b>	N/A	Take a snapshot of the current scope display. This button temporarily freezes the scope display, while allowing simulation to continue running. To unfreeze the scope display and view the current simulation data, toggle this button to turn off snapshot mode.
	<b>View &gt; Highlight Simulink Block</b>	<b>Ctrl+L</b>	Bring the model window forward, and highlight the Time Scope block whose display you are currently viewing. The Time Scope block that corresponds to the active Time Scope window flashes three times in the model.

You can control whether this toolbar appears in the Time Scope window. From the Time Scope menu, select **View > Simulation Toolbar**.

To see a full listing of the shortcut keys for these simulation controls, from the Time Scope menu, select **Help > Keyboard Command Help**.

## Measurements Panels

The Measurements panels are the five panels that appear to the right side of the Time Scope GUI. These panels are labeled **Trace selection**, **Signal statistics**, **Bilevel measurements**, and **Peak finder**.

The Time Domain Measurements panels only appear if the **Measurements** tool is enabled in the Time Scope — Tools:Plot Navigation Options dialog box. To open this dialog box, in the Time Scope menu, select **File > Configuration** and click the **Tools** pane. If you disable the tool by clearing the **Enabled** check box, the Time Domain Measurements tools no longer display in the Time Scope GUI. You can reenable the tool at any time by selecting the **Enabled** check

box. See the “Tools — Plot Navigation Options” on page 2-1507 section for more information.

## Measurements Panel Buttons

Each of the Measurements panels contains the following buttons that enable you to modify the appearance of the current panel.

Button	Description
	Move the current panel to the top. When you are displaying more than one panel, this action moves the current panel above all the other panels.
	Collapse the current panel. When you first enable a panel, by default, it displays one or more of its panes. Click this button to hide all of its panes to conserve space. After you click this button, it becomes the expand button  .
	Expand the current panel. This button appears after you click the collapse button to hide the panes in the current panel. Click this button to display the panes in the current panel and show measurements again. After you click this button, it becomes the collapse button  again.
	Undock the current panel. This button lets you move the current panel into a separate window that can be relocated anywhere on your screen. After you click this button, it becomes the dock button  in the new window.
	Dock the current panel. This button appears only after you click the undock button. Click this button to put the current panel back into the right side of the Scope window. After you click this button, it becomes the undock button  again.
	Close the current panel. This button lets you remove the current panel from the right side of the Scope window.

Some panels have their measurements separated by category into a number of panes. Click the pane expand button  to show each pane


# Time Scope

---

that is hidden in the current panel. Click the pane collapse button  to hide each pane that is shown in the current panel.

## Trace Selection Panel


When you use the Scope to view multiple signals, the Trace Selection panel appears if you have more than one signal displayed and you click on any of the other Measurements panels. Choose the signal name for which you would like to display time domain measurements. See the following figure.



You can choose to hide or display the **Trace Selection** panel. In the Scope menu, select **Tools > Measurements > Trace Selection**.

## Cursor Measurements Panel

The **Cursor Measurements** panel displays screen cursors. You can choose to hide or display the **Cursor Measurements** panel. In the Scope menu, select **Tools > Measurements > Cursor Measurements**. Alternatively, in the Scope toolbar, click the Cursor Measurements  button.



## Settings Pane

The **Settings** pane enables you to modify the type of screen cursors used to calculate time and value measurements.

- **Screen Cursors**— Shows screen cursors.
- **Horizontal**— Shows horizontal screen cursors.
- **Vertical**— Shows vertical screen cursors.
- **Waveform Cursors**— Shows cursors that attach to the input signals.
- **Lock Cursor Spacing**— Locks the time difference between the two cursors.

## Measurements Pane

The **Measurements** pane shows the time and value measurements.

# Time Scope

- **1** |— Shows or enables you to modify the time or value at cursor number one, or both.
- **2** :— Shows or enables you to modify the time or value at cursor number two, or both.
- **$\Delta t$** — Shows the absolute value of the difference in the times between cursor number one and cursor number two.
- **$\Delta V$** — Shows the absolute value of the difference in signal amplitudes between cursor number one and cursor number two.
- **$1/\Delta t$** — Shows the rate, the reciprocal of the absolute value of the difference in the times between cursor number one and cursor number two.
- **$\Delta V/\Delta t$** — Shows the slope, the ratio of the absolute value of the difference in signal amplitudes between cursors to the absolute value of the difference in the times between cursors.

## Signal Statistics Panel

The **Signal Statistics** panel displays the maximum, minimum, peak-to-peak difference, mean, median, and RMS values of a selected signal. It also shows the times at which the maximum and minimum values occur. You can choose to hide or display the **Signal Statistics** panel. In the Scope menu, select **Tools > Measurements > Signal Statistics**. Alternatively, in the Scope toolbar, click the Signal Statistics  button.

	Value	Time (us)
Max	2.343	22.500
Min	-57.337 m	5.000
Peak to Peak	2.400	
Mean	1.150	
Median	1.152	
RMS	1.628	

## Signal Statistics Measurements

The **Signal Statistics** panel shows statistics about the portion of the input signal within the  $x$ -axis and  $y$ -axis limits of the active display. The statistics shown are:

- **Max** — Shows the maximum or largest value within the displayed portion of the input signal. For more information on the algorithm this measurement uses, see the MATLAB `max` function reference.
- **Min** — Shows the minimum or smallest value within the displayed portion of the input signal. For more information on the algorithm this measurement uses, see the MATLAB `min` function reference.
- **Peak to Peak** — Shows the difference between the maximum and minimum values within the displayed portion of the input signal. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `peak2peak` function reference.
- **Mean** — Shows the average or mean of all the values within the displayed portion of the input signal. For more information on the algorithm this measurement uses, see the MATLAB `mean` function reference.
- **Median** — Shows the median value within the displayed portion of the input signal. For more information on the algorithm this measurement uses, see the MATLAB `median` function reference.
- **RMS** — Shows the difference between the maximum and minimum values within the displayed portion of the input signal. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `rms` function reference.


When you use the zoom options in the Scope, the Signal Statistics measurements automatically adjust to the time range shown in the display. In the Scope toolbar, click the **Zoom In** or **Zoom X** button to constrict the  $x$ -axis range of the display, and the statistics shown reflect this time range. For example, you can zoom in on one pulse to make the **Signal Statistics** panel display information about only that particular pulse.

# Time Scope

The Signal Statistics measurements are valid for any units of the input signal. The letter after the value associated with each measurement represents the appropriate International System of Units (SI) prefix, such as *m* for *milli*-. For example, if the input signal is measured in volts, an *m* next to a measurement value indicates that this value is in units of millivolts.

## Bilevel Measurements Panel


The **Bilevel Measurements** panel shows information about a selected signal's transitions, overshoots or undershoots, and cycles. You can choose to hide or display the **Bilevel Measurements** panel. In the Scope menu, select **Tools > Measurements > Bilevel Measurements**. Alternatively, in the Scope toolbar, you can select the Bilevel Measurements  button.



The **Bilevel Measurements** panel is separated into four panes, labeled **Settings**, **Transitions**, **Overshoots / Undershoots**, and **Cycles**. You can expand each pane to see the available options.

## Settings Pane

The **Settings** pane enables you to modify the properties used to calculate various measurements involving transitions, overshoots, undershoots, and cycles. You can modify the high-state level, low-state level, state-level tolerance, upper-reference level, mid-reference level, and lower-reference level, as shown in the following figure.




- **Auto State Level** — When this check box is selected, the Bilevel measurements panel autodetects the high- and low- state levels of a bilevel waveform. For more information on the algorithm this option uses, see the Signal Processing Toolbox `statelevels` function

# Time Scope


---

reference. When this check box is cleared, you may enter in values for the high- and low- state levels manually.

- **High** — Used to manually specify the value that denotes a positive polarity, or high-state level, as shown in the following figure.




- **Low** — Used to manually specify the value that denotes a negative polarity, or low-state level, as shown in the following figure.



- **State Level Tolerance** — Tolerance within which the initial and final levels of each transition must be within their respective state levels. This value is expressed as a percentage of the difference between the high- and low-state levels.
- **Upper Ref Level** — Used to compute the end of the rise-time measurement or the start of the fall time measurement. This value is expressed as a percentage of the difference between the high- and low-state levels.
- **Mid Ref Level** — Used to determine when a transition occurs. This value is expressed as a percentage of the difference between the high- and low- state levels. In the following figure, the mid-reference level is shown as the horizontal line, and its corresponding mid-reference level instant is shown as the vertical line.

# Time Scope

---




- **Lower Ref Level** — Used to compute the end of the fall-time measurement or the start of the rise-time measurement. This value is expressed as a percentage of the difference between the high- and low-state levels.
- **Settle Seek** — The duration after the mid-reference level instant when each transition occurs used for computing a valid settling time. This value is equivalent to the input parameter, `D`, which you can set when you run the `settlingtime` function. The settling time is displayed in the **Overshoots/Undershoots** pane.

## Transitions Pane

The **Transitions** pane displays calculated measurements associated with the input signal changing between its two possible state level values, high and low.

A positive-going transition, or *rising edge*, in a bilevel waveform is a transition from the low-state level to the high-state level. A positive-going transition has a slope value greater than zero. The following figure shows a positive-going transition.




Whenever there is a plus sign (+) next to a text label, this symbol refers to measurement associated with a rising edge, a transition from a low-state level to a high-state level.

A negative-going transition, or *falling edge*, in a bilevel waveform is a transition from the high-state level to the low-state level. A negative-going transition has a slope value less than zero. The following figure shows a negative-going transition.

# Time Scope

---



Whenever there is a minus sign (–) next to a text label, this symbol refers to measurement associated with a falling edge, a transition from a high-state level to a low-state level.


The Transition measurements assume that the amplitude of the input signal is in units of volts. You must convert all input signals to volts for the Transition measurements to be valid.

- **High** — The high-amplitude state level of the input signal over the duration of the **Time Span** parameter. You can set **Time Span** in the **Main** pane of the Visuals:Time Domain Options dialog box. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `statelevels` function reference.
- **Low** — The low-amplitude state level of the input signal over the duration of the **Time Span** parameter. You can set **Time Span** in the **Main** pane of the Visuals:Time Domain Options dialog box. For

more information on the algorithm this measurement uses, see the Signal Processing Toolbox `statelevels` function reference.

- **Amplitude** — Difference in amplitude between the high-state level and the low-state level.
- **+ Edges** — Total number of positive-polarity, or rising, edges counted within the displayed portion of the input signal.
- **+ Rise Time** — Average amount of time required for each rising edge to cross from the lower-reference level to the upper-reference level. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `risetime` function reference.
- **+ Slew Rate** — Average slope of each rising-edge transition line within the upper- and lower-percent reference levels in the displayed portion of the input signal. The region in which the slew rate is calculated appears in gray in the following figure.

# Time Scope




For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `slewrates` function reference.

- – **Edges** — Total number of negative-polarity or falling edges counted within the displayed portion of the input signal.
- – **Fall Time** — Average amount of time required for each falling edge to cross from the upper-reference level to the lower-reference level. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `falltime` function reference.
- – **Slew Rate** — Average slope of each falling edge transition line within the upper- and lower-percent reference levels in the displayed portion of the input signal. For more information on the algorithm

this measurement uses, see the Signal Processing Toolbox `slewrates` function reference.

## Overshoots/Undershoots


The **Overshoots/Undershoots** pane displays calculated measurements involving the distortion and damping of the input signal. *Overshoot* and *undershoot* refer to the amount that a signal respectively exceeds and falls below its final steady-state value. *Preshoot* refers to the amount prior to a transition that a signal varies from its initial steady-state value. This figure shows preshoot, overshoot, and undershoot for a rising-edge transition.




The next figure shows preshoot, overshoot, and undershoot for a falling-edge transition.

# Time Scope

---



- + **Preshoot** — Average lowest aberration in the region immediately preceding each rising transition.
- + **Overshoot** — Average highest aberration in the region immediately following each rising transition. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox overshoot function reference.
- + **Undershoot** — Average lowest aberration in the region immediately following each rising transition. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox undershoot function reference.
- + **Settling Time** — Average time required for each rising edge to enter and remain within the tolerance of the high-state level for the remainder of the settle seek duration. The settling time is the time after the mid-reference level instant when the signal crosses into and remains in the tolerance region around the high-state level. This crossing is illustrated in the following figure.



You can modify the settle seek duration parameter in the **Settings** pane. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `settlingtime` function reference.

- – **Preshoot** — Average highest aberration in the region immediately preceding each falling transition.
- – **Overshoot** — Average highest aberration in the region immediately following each falling transition. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `overshoot` function reference.
- – **Undershoot** — Average lowest aberration in the region immediately following each falling transition. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `undershoot` function reference.
- – **Settling Time** — Average time required for each falling edge to enter and remain within the tolerance of the low-state level for the remainder of the settle seek duration. The settling time is the time after the mid-reference level instant when the signal crosses into and remains in the tolerance region around the low-state level. You can

# Time Scope


---

modify the settle seek duration parameter in the **Settings** pane. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `settlingtime` function reference.

## Cycles

The **Cycles** pane displays calculated measurements pertaining to repetitions or trends in the displayed portion of the input signal.

- **Period** — Average duration between adjacent edges of identical polarity within the displayed portion of the input signal. The Bilevel measurements panel calculates period as follows. It takes the difference between the mid-reference level instants of the initial transition of each positive-polarity pulse and the next positive-going transition. These mid-reference level instants appear as red dots in the following figure.



For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `pulseperiod` function reference.

- **Frequency** — Reciprocal of the average period. Whereas period is typically measured in some metric form of seconds, or seconds per cycle, frequency is typically measured in hertz or cycles per second.
- **+ Pulses** — Number of positive-polarity pulses counted.
- **+ Width** — Average duration between rising and falling edges of each positive-polarity pulse within the displayed portion of the input signal. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `pulsewidth` function reference.
- **+ Duty Cycle** — Average ratio of pulse width to pulse period for each positive-polarity pulse within the displayed portion of the input signal. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `dutycycle` function reference.
- **- Pulses** — Number of negative-polarity pulses counted.
- **- Width** — Average duration between rising and falling edges of each negative-polarity pulse within the displayed portion of the input signal. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `pulsewidth` function reference.
- **- Duty Cycle** — Average ratio of pulse width to pulse period for each negative-polarity pulse within the displayed portion of the input signal. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `dutycycle` function reference.

When you use the zoom options in the Scope, the bilevel measurements automatically adjust to the time range shown in the display. In the Scope toolbar, click the **Zoom In** or **Zoom X** button to constrict the *x*-axis range of the display, and the statistics shown reflect this time range. For example, you can zoom in on one rising edge to make the **Bilevel Measurements** panel display information about only that


# Time Scope

---

particular rising edge. However, this feature does not apply to the **High** and **Low** measurements.

## Peak Finder Panel

The **Peak Finder** panel displays maxima and the times at which they occur, allowing the settings for peak threshold, maximum number of peaks, and peak excursion to be modified. You can choose to hide or display the **Peak Finder** panel. In the Scope menu, select **Tools > Measurements > Peak Finder**. Alternatively, in the Scope toolbar, select the Peak Finder  button.




The **Peak finder** panel is separated into two panes, labeled **Settings** and **Peaks**. You can expand each pane to see the available options.

## Settings Pane

The **Settings** pane enables you to modify the parameters used to calculate the peak values within the displayed portion of the input

signal. For more information on the algorithms this pane uses, see the Signal Processing Toolbox `findpeaks` function reference.

- **Peak Threshold** — The level above which peaks are detected. This setting is equivalent to the `MINPEAKHEIGHT` parameter, which you can set when you run the `findpeaks` function.
- **Max Num of Peaks** — The maximum number of peaks to show. This setting is equivalent to the `NPEAKS` parameter, which you can set when you run the `findpeaks` function.
- **Min Peaks Distance** — The minimum number of samples between adjacent peaks. This setting is equivalent to the `MINPEAKDISTANCE` parameter, which you can set when you run the `findpeaks` function.
- **Peak Excursion** — The minimum height difference between a peak and its neighboring samples. Peak excursion is illustrated alongside peak threshold in the following figure.



Whereas the peak threshold is a minimum value necessary for a sample value to be a peak, the peak excursion is the minimum difference between a peak sample and the samples to its left and right

in the time domain. In the figure, the green vertical line illustrates the lesser of the two height differences between the labeled peak and its neighboring samples. This height difference must be greater than the **Peak Excursion** value for the labeled peak to be classified as a peak. Compare this setting to peak threshold, which is illustrated by the red horizontal line. The amplitude must be above this horizontal line for the labeled peak to be classified as a peak.

The peak excursion setting is equivalent to the **THRESHOLD** parameter, which you can set when you run the `findpeaks` function.

- **Label peaks** — When this check box is selected, the Peak Finder displays the calculated peak values directly on the plot. By default, this check box is cleared and no values are displayed on the plot.
- **Sort by time** — When this check box is selected, the Peak Finder puts the largest calculated peak values in the time range shown in the display in time-sorted order. The Peak Finder displays the peak values in the **Peaks** pane. The **Max Num of Peaks** parameter still controls the number of peaks listed. By default, this check box is cleared and the **Peak Finder** panel displays the largest calculated peak values in the **Peaks** pane in decreasing order of peak height.

## Peaks Pane

The **Peaks** pane displays all of the largest calculated peak values and the times at which the peaks occur, using the parameters you define in the **Settings** pane. You set the **Max Num of Peaks** parameter to specify the number of peaks shown in the list. Using the **Sort by time** check box, you set the order in which the peaks are listed.

The numerical values displayed in the **Value** column are equivalent to the `pks` output argument returned when you run the `findpeaks` function. The numerical values displayed in the **Time** column are similar to the `locs` output argument returned when you run the `findpeaks` function.

When you use the zoom options in the Scope, the peak locations automatically adjust to the time range shown in the display. In the Scope toolbar, click the **Zoom In** or **Zoom X** button to constrict the


x-axis range of the display, and the statistics shown reflect this time range. For example, you can zoom in on one peak to make the **Peak Finder** panel display information about only that particular peak.

## Properties Dialog Box

The Properties dialog box controls various properties about the Time Scope displays. From the Time Scope menu, select **View > Properties** to open this dialog box. Alternatively, in the Time Scope toolbar, click the Properties  button.

### Main Pane

The **Main** pane of the Properties dialog box appears as follows.



# Time Scope

---

## **Open at simulation start**

Select this check box to ensure that the Time Scope opens when the simulation starts.

## **Number of input ports**

Specify the number of input ports that should appear on the left side of the Time Scope block.

## **Input processing**

Specify whether the Time Scope should treat the input signal as Columns as channels (frame based) or Elements as channels (sample based). Tunable.

Frame-based processing is only available for discrete input signals. For more information about frame-based input channels, see the “What Is Frame-Based Processing?” section in the DSP System Toolbox documentation. For an example that uses the Time Scope block and frame-based input signals, see the Display Time-Domain Data in the Time Scope section in the DSP System Toolbox documentation.

## **Maximize axes**

Specify whether to display the Time Scope in maximized axes mode. In this mode, each of the axes are expanded to fit into the entire display. To conserve space, no labels appear in each display. Instead, tick-mark values appear on top of the plotted data. You can select one of the following options:

- **Auto** — In this mode, the axes appear maximized in all displays only if the **Title** and **Y-Axis label** parameters are empty for every display. If you enter any value in any display for either of these parameters, the axes are not maximized.
- **On** — In this mode, the axes appear maximized in all displays. Any values entered into the **Title** and **Y-Axis label** parameters are hidden.
- **Off** — In this mode, none of the axes appear maximized.

The default setting is Auto.

## Axes scaling

Specify when the Time Scope should automatically scale the axes. You can select one of the following options:

- **Manual** — When you select this option, the Time Scope does not automatically scale the axes. You can manually scale the axes in any of the following ways:
  - Select **Tools > Scale axes limits**.
  - Press the **Scale Axes Limits** toolbar button.
  - When the scope GUI is the active window, press **Ctrl** and **A** simultaneously.
- **Auto** — When you select this option, the Time Scope scales the axes as needed, both during and after simulation. Selecting this option enables the **Do not allow Y-axis limits to shrink** check box. By default, this parameter is selected, and the Time Scope does not shrink the *y*-axis limits when scaling the axes.
- **Once at stop** — Selecting this option causes the Time Scope to scale the axes each time simulation is stopped. The Time Scope does not scale the axes during simulation.

This parameter is Tunable.

---

**Note** Click the link labeled **Configure** to the right of the **Axes scaling** parameter to see additional axes scaling parameters. After you click this button, its label changes to **Hide**. To hide these additional parameters, click the **Hide** link.

---

## Do not allow Y-axis limits to shrink

When you select this parameter, the *y*-axis limits are only allowed to grow during axes scaling operations. If you clear this check box, the *y*-axis limits may shrink during axes scaling operations.

# Time Scope

---

This parameter appears only when you select **Auto** for the **Axis Scaling** parameter. When you set the **Axis Scaling** parameter to **Manual** or **Once at stop**, the *y*-axis limits are allowed to shrink. Tunable.

## **Y-axis Data range (%)**

Set the percentage of the *y*-axis the Scope should use to display the data when scaling the axes. Valid values are between 1 and 100. For example, if you set this parameter to 100, the Scope scales the *y*-axis limits such that your data uses the entire *y*-axis range. If you then set this parameter to 30, the Scope increases the *y*-axis range such that your data uses only 30% of the *y*-axis range. Tunable.

## **Y-axis Align**

Specify where the Scope should align your data with respect to the *y*-axis when it scales the axes. You can select **Top**, **Center**, or **Bottom**. Tunable.

## **Scale X-axis limits**

Check this box to allow the Scope to scale the *x*-axis limits when it scales the axes. Tunable.

## **X-axis Data range (%)**

Set the percentage of the *x*-axis the Scope should use to display the data when scaling the axes. Valid values are between 1 and 100. For example, if you set this parameter to 100, the Scope scales the *x*-axis limits such that your data uses the entire *x*-axis range. If you then set this parameter to 30, the Scope increases the *x*-axis range such that your data uses only 30% of the *x*-axis range. Use the *x*-axis **Align** parameter to specify data placement with respect to the *x*-axis.


This parameter appears only when you select the **Scale X-axis limits** check box. Tunable.

## **X-axis Align**

Specify how the Scope should align your data with respect to the *x*-axis: **Left**, **Center**, or **Right**. This parameter appears only when you select the **Scale X-axis limits** check box. Tunable.

## **Time Pane**

The **Time** pane of the Properties dialog box appears as follows.



## Time span


Specify the time span, either by selecting a predefined option or by entering a numeric value in seconds. You can select one of the following options:

- **Auto calculate** — In this mode, the Time Scope automatically calculates the appropriate value for time span from the difference between the simulation “Start time” and “Stop time” parameters.
- **One frame period** — In this mode, the Time Scope uses the frame period of the input signal to the Time Scope block. This option is only available when the **Input processing** parameter is set to **Columns as channels (frame based)**. This option is not available when you set the **Input processing** parameter to **Elements as channels (sample based)**.

# Time Scope

- `<user defined>` — In this mode, you specify the time span by replacing the text `<user defined>` with a numeric value in seconds.

The scope sets the *time*-axis limits using the value of this parameter and the value of the **Time display offset** parameter. For example, if you set the **Time display offset** to  $5e-6$  and the **Time span** to  $25e-6$ , the scope sets the *time*-axis limits as shown in the following figure.



Tunable. For more information, see “Signal Display” on page 2-1447.

## Time span overrun

Specify how the scope displays new data beyond the visible time span. The default setting is Wrap. You can select one of the following options:

- **Wrap** — In this mode, the scope displays new data until the data reaches the maximum *time*-axis limit. When the data reaches the maximum *time*-axis limit of the scope window, the Time Scope clears the display. The Time Scope then updates the time offset value and begins displaying subsequent data points starting from the minimum *time*-axis limit.
- **Scroll** — In this mode, the scope scrolls old data to the left to make room for new data on the right side of the scope display. This mode is graphically intensive and can affect run-time performance, but it is beneficial for debugging and monitoring time-varying signals.

This parameter is Tunable.

## Time units

Specify the units used to describe the *time*-axis. The default setting is Metric. You can select one of the following options:

- **Metric** — In this mode, Time Scope converts the times on the *time*-axis to some metric units such as milliseconds, microseconds, nanoseconds, etc. Time Scope chooses the appropriate metric units, based on the minimum *time*-axis limit and the maximum *time*-axis limit of the scope window.
- **Seconds** — In this mode, Time Scope always displays the units on the *time*-axis as seconds.
- **None** — In this mode, Time Scope displays no units on the *time*-axis. Time Scope shows only the word Time on the *time*-axis.

Tunable.

## Time display offset


This parameter allows you to offset the values displayed on the *time*-axis by a specified number of seconds. When you specify a scalar value, the scope offsets all channels equally. When you specify a vector of offset values, the scope offsets each channel independently. Tunable.

When you specify a **Time display offset** vector of length  $N$ , the scope offsets the input channels as follows:

- When  $N$  is equal to the number of input channels, the scope offsets each channel according to its corresponding value in the offset vector.
- When  $N$  is less than the number of input channels, the scope applies the values you specify in the offset vector to the first  $N$  input channels. The scope does not offset the remaining channels.
- When  $N$  is greater than the number of input channels, the scope offsets each input channel according to the corresponding value in the offset vector. The scope ignores all values in the offset vector that do not correspond to a channel of the input.

# Time Scope

The scope computes the *time*-axis range using the values of the **Time display offset** and **Time span** parameters. For example, if you set the **Time display offset** to  $5\text{e-}6$  and the **Time span** to  $25\text{e-}6$ , the scope sets the *time*-axis limits as shown in the following figure.



Similarly, when you specify a vector of values, the scope sets the minimum *time*-axis limit using the smallest value in the vector. To set the maximum *time*-axis limit, the scope sums the largest value in the vector with the value of the **Time span** parameter. For more information, see “Signal Display” on page 2-1447.

## Show time-axis labels


Specify how to display the time units used to describe the *time*-axis. The default setting is All. You can select one of the following options:

- All — In this mode, the *time*-axis labels appear in all displays.
- None — In this mode, the *time*-axis labels do not appear in the displays.
- Bottom Displays Only — In this mode, the *time*-axis labels appear in only the bottom row of the displays.

Tunable.

## Display Pane

The **Display** pane of the Properties dialog box appears as follows.



### Select Display

Specify the active display as a number, where a display number corresponds to the index of the input signal. The index of a display is its column-wise placement index. The default setting is 1. Set this parameter to control the display for which you intend to modify the title, legend, grid, *y*-axis limits, *y*-axis label, and magnitude/phase display parameters. Tunable.

### Title

Specify the active display title as a string. By default, the active display has no title. Tunable.

## **Show legend**

Select this check box to show the legend in the active display. The channel legend displays a name for each channel of each input signal. When the legend appears, you can place it anywhere inside of the scope window. To turn the legend off, clear the **Show legend** check box. Tunable.

You can edit the name of any channel in the legend. To do so, double-click the current name, and enter a new channel name. By default, the scope names each channel according to either its signal name or the name of the block from which it comes. If the signal has multiple channels, the scope uses an index number to identify each channel of that signal. For example, a 2-channel signal named `MySignal` would have the following default names in the channel legend: `MySignal:1`, `MySignal:2`.

The Time Scope does not display signal names that were labeled within an unmasked subsystem. You must label all input signals to the Time Scope block that originate from an unmasked subsystem.


To change the appearance of any channel of any input signal in the Time Scope window, from the Time Scope menu, select **View > Style**.

## **Show grid**


When you select this check box, a grid appears in the active display of the Time Scope GUI. To hide the grid, clear this check box. Tunable.

## **Plot signal(s) as magnitude and phase**

When you select this check box, the Time Scope splits the magnitude and phase of the input signal on two separate axes within the same active display. By default, this box is cleared. If the input is a complex-valued signal, then the Time Scope plots the real and imaginary portions on the same display. These real and imaginary portions appear as different-colored lines on the same axes within the same active display, as shown in the following figure.



After you select this check box and click **OK**, the active display changes to show the magnitude of the input signal on the top axes and its phase, in degrees, on the bottom axes, as shown in the following figure.



This feature is particularly useful for complex-valued input signals. If the input is a real-valued signal, after you select this check box,

# Time Scope

---

the phase will be 0 degrees when the amplitude of the input signal is nonnegative and 180 degrees when the input signal is negative. Tunable.

## **Minimum Y-limit**

Specify the minimum value of the  $y$ -axis. Tunable.

When you select the **Plot signal(s) as magnitude and phase** check box, the value of this parameter always applies to the magnitude plot on the top axes. The phase plot on the bottom axes is always limited to a minimum value of  $-180$  degrees.

## **Maximum Y-limit**

Specify the maximum value of the  $y$ -axis. Tunable.

When you select the **Plot signal(s) as magnitude and phase** check box, the value of this parameter always applies to the magnitude plot on the top axes. The phase plot on the bottom axes is always limited to a maximum value of 180 degrees.


## **Y-axis label**

Specify the text for the scope to display to the left of the  $y$ -axis. Tunable.

This parameter becomes invisible when you select the **Plot signal(s) as magnitude and phase** check box. When you enable that parameter, the  $y$ -axis label always appears as **Magnitude** on the top axes and **Phase** on the bottom axes.

## **Style Dialog Box**

In the **Style** dialog box, you can customize the style of displays. You are able to change the color of the figure containing the displays, the background and foreground colors of display axes, and properties of lines in a display. From the Scope menu, select **View > Style** to open this dialog box.



## Properties

The **Style** dialog box allows you to modify the following properties of the Scope GUI:

### Figure color

Specify the color that you want to apply to the background of the Scope GUI. By default, the figure color is gray.

### Plot type

Specify the type of plot to use. The default setting is **Line**. Valid values for **Plot type** are:

- **Line** — Displays input signal as lines connecting each of the sampled values. This approach is similar to the functionality of the MATLAB `line` or `plot` function.
- **Stairs** — Displays input signal as a *stairstep* graph. A stairstep graph is made up of only horizontal lines and vertical lines. Each

horizontal line represents the signal value for a discrete sample period and is connected to two vertical lines. Each vertical line represents a change in values occurring at a sample. This approach is equivalent to the MATLAB `stairs` function. Stairstep graphs are useful for drawing time history graphs of digitally sampled data.

- **Auto** — Displays input signal as a line graph if it is a continuous signal and displays input signal as a stairstep graph if it is a discrete signal.

This parameter is Tunable.

### **Select display**

Specify the active display as a number, where a display number corresponds to the index of the input signal. The number of a display corresponds to its column-wise placement index. The default setting is 1. Set this parameter to control which display should have its axes colors, line properties, marker properties, and visibility changed. Tunable.

### **Axes colors**

Specify the color that you want to apply to the background of the axes for the active display.

### **Properties for line**

Specify the signal for which you want to modify the visibility, line properties, and marker properties.

### **Visible**

Specify whether the selected signal on the active display should be visible. If you clear this check box, the line disappears.

### **Line**

Specify the line style, line width, and line color for the selected signal on the active display.

### **Marker**

Specify marks for the selected signal on the active display to show at data points. This parameter is similar to the **Marker** property for the MATLAB Handle Graphics® plot objects. You can choose any of the marker symbols from the following table.


Specifier	Marker Type
none	No marker (default)
○	Circle
□	Square
×	Cross
•	Point
+	Plus sign
*	Asterisk
◇	Diamond
▽	Downward-pointing triangle
△	Upward-pointing triangle
◁	Left-pointing triangle
▷	Right-pointing triangle
☆	Five-pointed star (pentagram)
☆☆	Six-pointed star (hexagram)

## Simulation Stepping Options

The Simulation Stepping Options dialog box lets you control the simulation behavior. You can pause the simulation at a specified time, enable stepping back, or specify options for stepping back. You can also modify the number of steps by which to step forward or backward. To open this dialog box, in the Time Scope menu, select **Simulation > Stepping Options** to open this dialog box.

# Time Scope

Alternatively, if stepping back is disabled, in the Time Scope toolbar, click the previous step  button.



The Simulation Stepping Options dialog box is not unique to Time Scope; it can also be launched from any Simulink model. To open this dialog box from any Simulink model, select **Simulation > Stepping Options**. For more information, see “Simulation Stepping” in the Simulink documentation.

## Enable stepping back

Select this check box to enable the Time Scope to take steps back in time. When selected, Time Scope enables the previous step button () on the simulation toolbar.

## Maximum number of saved back steps

Specify the maximum number of back steps that the Time Scope saves in memory. To maximize simulation speed, the value for this parameter should be kept small. The default setting is 10.

## Interval between stored back steps

Specify the number of steps between back steps that the Time Scope saves in memory for previous stepping. Set this parameter to a larger number to increase the time span of a back step without increasing the amount of memory used. The default setting is 1.

## Move back/forward by

Specify the number of steps forward or backward that the Time Scope progresses when you click the next step () and previous step () buttons. The default setting is 1.

## Pause simulation when time reaches

Select this check box to enable the Time Scope to pause the simulation when it reaches a specified time.


## Pause simulation when time reaches

Specify the time at which you want Time Scope to pause when the check box is selected.

## Core — General UI Options


The Core:General UI Options dialog box controls the general settings for the Time Scope GUI. From the Time Scope menu bar, select **File > Configuration** to open the Time Scope — Configuration dialog box. Click on the **Core** pane, and the following dialog box appears.

# Time Scope



To open the Core:General UI Options dialog box, select **General UI** and click **Options**. The following dialog box appears.

## General UI Options



## Display the full source path in the title bar

If you select this check box, the Time Scope GUI displays the model name and full Simulink path to the data source in the title bar. Otherwise, a shortened name appears.

## Open message log

Use this parameter to control when the Message Log window opens. The Message Log window helps you debug any issues with the Time Scope. Using the drop-down list, you can choose to open the Message Log window under any of the following conditions:

- for any new messages
- for warn/fail messages
- only for fail messages
- manually


You can open the Message Log at any time by selecting **Help > Message Log**. The Message Log dialog box provides a system-level record of loaded configuration settings and registered extensions. The Message Log displays summaries and details of each message, and you can filter the display of messages by **Type** and **Category**.

- The **Type** parameter allows you to select which types of messages to display in the Message Log. You can select **All**, **Info**, **Warn**, or **Fail**.
- The **Category** parameter allows you to select the category of messages to display in the Message Log. You can select **All**, **Configuration**, or **Extension**.
  - The scope uses **Configuration** messages to indicate when new configuration files are loaded.
  - The scope uses **Extension** messages to indicate when components are registered. For example, you may see a **Simulink registered** message, indicating that a component has been successfully registered with Simulink and is available for configuration.

# Time Scope

## Visuals – Time Domain Options


The Time Scope — Visuals:Time Domain Options dialog box controls the visual configuration settings of the Time Scope displays. You can open this dialog box from the Time Scope — Configuration dialog box. From the Time Scope menu bar, select **File > Configuration** to open the Time Scope — Configuration dialog box. Click the **Visuals** pane, and the following dialog box appears.



The Time Scope GUI has only one available visual, so you must ensure that the **Enabled** check box is selected. To open the Time Scope — Visuals:Time Domain Options dialog box, select **Time Domain** and click **Options**.

### Main Pane

The **Main** pane of the Time Scope — Visuals:Time Domain Options dialog box appears as follows.



## Input processing

Specify whether the Time Scope should treat the input signal as Columns as channels (frame based) or Elements as channels (sample based). Tunable.

Frame-based processing is only available for discrete input signals. For more information about frame-based input channels, see the “What Is Frame-Based Processing?” section in the *DSP System Toolbox User’s Guide*. For an example that uses the Time Scope block and frame-based input signals, see the Display Time-Domain Data in the Time Scope section in the *DSP System Toolbox User’s Guide*.


## Time span

Specify the time span, either by selecting a predefined option or by entering a numeric value in seconds. You can select one of the following options:

# Time Scope

- **Auto calculate** — In this mode, the Time Scope automatically calculates the appropriate value for time span from the difference between the simulation “Start time” and “Stop time” parameters. This option is available only for the Time Scope block but not for the `dsp.TimeScope` System object.
- **One frame period** — In this mode, the Time Scope uses the frame period of the input signal to the Time Scope block. This option is only available when the **Input processing** parameter is set to **Columns as channels (frame based)**. This option is not available when you set the **Input processing** parameter to **Elements as channels (sample based)**.
- **<user defined>** — In this mode, you specify the time span by replacing the text `<user defined>` with a numeric value in seconds.

The scope sets the *time*-axis limits using the value of this parameter and the value of the **Time display offset** parameter. For example, if you set the **Time display offset** to  $5e-6$  and the **Time span** to  $25e-6$ , the scope sets the *time*-axis limits as shown in the following figure.



This parameter is Tunable.

## **Time span overrun**

Specify how the scope displays new data beyond the visible time span. The default setting is **Wrap**. You can select one of the following options:

- **Wrap** — In this mode, the scope displays new data until the data reaches the maximum *time*-axis limit. When the data reaches the maximum *time*-axis limit of the scope window, the Time Scope clears the display. The Time Scope then updates the time offset value, and begins displaying subsequent data points starting from the minimum *time*-axis limit.
- **Scroll** — In this mode, the scope scrolls old data to the left to make room for new data on the right side of the scope display. This mode is graphically intensive and can affect run-time performance, but it is beneficial for debugging and monitoring time-varying signals.

This parameter is Tunable.

### **Time units**

Specify the units used to describe the *time*-axis. The default setting is **Metric**. You can select one of the following options:

- **Metric** — In this mode, Time Scope converts the times on the *time*-axis to some metric units such as milliseconds, microseconds, days, etc. Time Scope chooses the appropriate metric units, based on the minimum *time*-axis limit and the maximum *time*-axis limit of the scope window.
- **Seconds** — In this mode, Time Scope always displays the units on the *time*-axis as seconds.
- **None** — In this mode, Time Scope displays no units on the *time*-axis. Time Scope shows only the word **Time** on the *time*-axis.

This parameter is Tunable.

### **Time display offset**


This parameter allows you to offset the values displayed on the *time*-axis by a specified number of seconds. When you specify a scalar value, the scope offsets all channels equally. When you specify a vector of offset values, the scope offsets each channel independently. Tunable.

When you specify a **Time display offset** vector of length  $N$ , the scope offsets the input channels as follows:

# Time Scope

- When  $N$  is equal to the number of input channels, the scope offsets each channel according to its corresponding value in the offset vector.
- When  $N$  is less than the number of input channels, the scope applies the values you specify in the offset vector to the first  $N$  input channels. The scope does not offset the remaining channels.
- When  $N$  is greater than the number of input channels, the scope offsets each input channel according to the corresponding value in the offset vector. The scope ignores all values in the offset vector that do not correspond to a channel of the input.

The scope computes the *time*-axis range using the values of the **Time display offset** and **Time span** parameters. For example, if you set the **Time display offset** to  $5\text{e-}6$  and the **Time span** to  $25\text{e-}6$ , the scope sets the *time*-axis limits as shown in the following figure.



Similarly, when you specify a vector of values, the scope sets the minimum *time*-axis limit using the smallest value in the vector. To set the maximum *time*-axis limit, the scope sums the largest value in the vector with the value of the **Time span** parameter. For more information, see “Signal Display” on page 2-1447.

## Show time-axis labels

Specify how to display the time units used to describe the *time*-axis. The default setting is All. You can select one of the following options:

- All — In this mode, the *time*-axis labels appear in all displays.
- None — In this mode, the *time*-axis labels do not appear in the displays.
- Bottom Displays Only — In this mode, the *time*-axis labels appear in only the bottom row of the displays.

Tunable.

### **Maximize axes**


Specify whether to display the Time Scope in maximized axes mode. In this mode, each of the axes are expanded to fit into the entire display. In each display, there is no space to show labels. Tick mark values are shown on top of the plotted data. The default setting is Auto. You can select one of the following options:

- Auto — In this mode, the axes appear maximized in all displays only if the **Title** and **Y-Axis label** parameters are empty for every display. If you enter any value in any display for either of these parameters, the axes are not maximized.
- On — In this mode, the axes appear maximized in all displays. Any values entered into the **Title** and **Y-Axis label** parameters are hidden.
- Off — In this mode, none of the axes appear maximized.

### **Display Pane**

The **Display** pane of the Visuals:Time Domain Options dialog box appears as follows.

# Time Scope



## Select display

Specify the active display as a number, where a display number corresponds to the index of the input signal. The index of a display is its column-wise placement index. The default setting is 1. Set this parameter to control the display for which you intend to modify the title, legend, grid,  $y$ -axis limits,  $y$ -axis label, and magnitude/phase display parameters. Tunable.

## Title

Specify the active display title as a string. By default, the active display has no title. Tunable.

## Show legend

Select this check box to show the legend in the active display. The channel legend displays a name for each channel of each input signal. When the legend appears, you can place it anywhere inside of the scope window. To turn the legend off, clear the **Show legend** check box. Tunable.

You can edit the name of any channel in the legend. To do so, double-click the current name, and enter a new channel name. By default, the scope names each channel according to either its signal name or the name of the block from which it comes. If the signal has multiple channels, the scope uses an index number to identify each channel of that signal. For example, a 2-channel signal named **MySignal** would have the following default names in the channel legend: **MySignal:1**, **MySignal:2**.

The Time Scope does not display signal names that were labeled within an unmasked subsystem. You must label all input signals to the Scope block that originate from an unmasked subsystem.

To change the appearance of any channel of any input signal in the Scope window, from the menu, select **View > Style**.


### **Show grid**

When you select this check box, a grid appears in the active display of the Scope. To hide the grid, clear this check box. Tunable.


### **Plot signal(s) as magnitude and phase**

When you select this check box, the Scope splits the active display into a magnitude plot and a phase plot. By default, this check box is cleared. If the input signal is complex valued, the Scope plots the real and imaginary portions on the same axes. These real and imaginary portions appear as different-colored lines on the same axes within the same active display, as shown in the following figure.

# Time Scope



Selecting this check box and clicking the **Apply** or **OK** button changes the active display. The magnitude of the input signal appears on the top axes and its phase, in degrees, appears on the bottom axes. See the following figure.



This feature is particularly useful for complex-valued input signals. If the input is a real-valued signal, selecting this check box always produces the same behavior. The phase is 0 for nonnegative input and 180 degrees for negative input. Tunable.

### **Minimum Y-limit**

Specify the minimum value of the  $y$ -axis. Tunable.

When you select the **Plot signal(s) as magnitude and phase** check box, the value of this parameter always applies to the magnitude plot on the top axes. The phase plot on the bottom axes is always limited to a minimum value of  $-180$  degrees.

### **Maximum Y-limit**

Specify the maximum value of the  $y$ -axis. Tunable.

When you select the **Plot signal(s) as magnitude and phase** check box, the value of this parameter always applies to the magnitude plot on the top axes. The phase plot on the bottom axes is always limited to a maximum value of 180 degrees.

### **Y-axis label**

Specify the text for the scope to display to the left of the  $y$ -axis. Tunable.


This parameter becomes invisible when you select the **Plot signal(s) as magnitude and phase** check box. When you enable that parameter, the  $y$ -axis label always appears as **Magnitude** on the top axes and **Phase** on the bottom axes.

## **Tools — Plot Navigation Options**

The Tools:Plot Navigation Options dialog box provides you with the ability to automatically zoom in on and zoom out of your data, and to scale the axes of the Time Scope. In the Time Scope menu, select **Tools > Axes Scaling Options** to open this dialog box.

Alternatively, you can open this dialog box from the Time Scope — Configuration dialog box. In the Time Scope menu, select **File > Configuration** to open the Time Scope — Configuration dialog box. Click the **Tools** pane, and the following dialog box appears.

# Time Scope



The **Tools** pane in the Time Scope – Configuration dialog box contains the tools that appear on the Time Scope GUI. By default, the **Plot Navigation** tool is enabled. If you disable the tool by clearing the **Enabled** check box, the axes scaling and zoom tools no longer display in the Time Scope GUI. You can reenble the tool at any time by selecting the **Enabled** check box.

By default, the **Measurements** tool is also enabled. If you disable the tool by clearing the **Enabled** check box, the Time Domain Measurements tools no longer display in the Time Scope GUI. See the “Measurements Panels” on page 2-1456 section for more information. You can reenble the tool at any time by selecting the **Enabled** check box.

To open the Time Scope — Tools:Plot Navigation Options dialog box, select the **Plot Navigation** tool, and then click the **Options** button.

## Parameters

The Tools:Plot Navigation Options dialog box appears as follows.

Parameters

Axes scaling:

Do not allow Y-axis limits to shrink

Y-axis

Data range (%):  Align:

Scale X-axis limits

Data range (%):  Align:

? OK Cancel Apply

## Axis Scaling

Specify when the Scope should automatically scale the axes. You can select one of the following options:

- **Manual** — When you select this option, the Scope does not automatically scale the axes. You can manually scale the axes in any of the following ways:
  - Select **Tools > Scale axes limits**.
  - Press the **Scale Axes Limits** toolbar button.
  - When the scope GUI is the active window, press **Ctrl+A**.
- **Auto** — When you select this option, the Scope scales the axes as needed, both during and after simulation. Selecting this option enables the **Do not allow Y-axis limits to shrink** check box. By default, this parameter is selected, and the Scope does not shrink the y-axis limits when scaling the axes.
- **Once at stop** — Selecting this option causes the Scope to scale the axes each time simulation is stopped. The Scope does not scale the axes during simulation.

# Time Scope

---

This parameter is Tunable.

## **Do not allow Y-axis limits to shrink**

When you select this parameter, the *y*-axis limits are only allowed to grow during axes scaling operations. If you clear this check box, the *y*-axis limits may shrink during axes scaling operations.

This parameter appears only when you select **Auto** for the **Axis Scaling** parameter. When you set the **Axis Scaling** parameter to **Manual** or **Once at stop**, the *y*-axis limits are allowed to shrink. Tunable.

## **Y-axis Data range (%)**

Set the percentage of the *y*-axis that the Scope should use to display the data when scaling the axes. Valid values are between 1 and 100. For example, if you set this parameter to 100, the Scope scales the *y*-axis limits such that your data uses the entire *y*-axis range. If you then set this parameter to 30, the Scope increases the *y*-axis range such that your data uses only 30% of the *y*-axis range. Tunable.

## **Y-axis Align**

Specify where the Scope should align your data with respect to the *y*-axis when it scales the axes. You can select **Top**, **Center**, or **Bottom**. Tunable.

## **Scale X-axis limits**

Check this box to allow the Scope to scale the *x*-axis limits when it scales the axes. Tunable.

## **X-axis Data range (%)**

Set the percentage of the *x*-axis that the Scope should use to display the data when scaling the axes. Valid values are between 1 and 100. For example, if you set this parameter to 100, the Scope scales the *x*-axis limits such that your data uses the entire *x*-axis range. If you then set this parameter to 30, the Scope increases the *x*-axis range such that your data uses only 30% of the *x*-axis range. Use the *x*-axis **Align** parameter to specify data placement with respect to the *x*-axis.

This parameter appears only when you select the **Scale X-axis limits** check box. Tunable.


## Sources — Simulink Options

### X-axis Align

Specify how the Scope should align your data with respect to the *x*-axis: Left, Center, or Right. This parameter appears only when you select the **Scale X-axis limits** check box. Tunable.

The Sources:Simulink Options dialog box lets you control the number of samples for each input signal that Time Scope holds in its memory cache. In the Time Scope menu, select **View > Data History Options** to open this dialog box.

### Data History Options



### Limit data points to last

Specify the number of data points for each input signal that Time Scope holds in its memory cache. The number of data points is equal to the product of the number of channels in the signal and the number of time samples. The default setting is 50000.

## Examples

The first few examples illustrate how to use the Time Scope block to view a variety of input signals in the time domain.

- “Example: Display Complex-valued Input Signal” on page 2-1512
- “Example: Display Variable-size Input Signal” on page 2-1514
- “Example: Display Simulink Enumeration Input Signal” on page 2-1516


The remaining examples demonstrate how to use the Measurements Panels in the Time Scope GUI to glean information about the input signals.

# Time Scope


- “Example: Use Bilevel Measurements Panel with Clock Input Signal” on page 2-1519
- “Example: Find Heart Rate Using Peak Finder Panel with ECG Input Signal” on page 2-1522

## Example: Display Complex-valued Input Signal

At the MATLAB command prompt, type `ex_timescope_complexinp` to open the example model. The following Simulink model appears.




By default, when the input is a complex-valued signal, Time Scope plots the real and imaginary portions on the same axes. These real and imaginary portions appear as different-colored lines on the same axes within the same active display. Run your model to see the time domain output, as shown in the following figure.




The Properties dialog box controls the visual configuration settings of the Time Scope displays. From the Time Scope menu, select **View > Properties** to open this dialog box. Selecting the **Plot signal(s) as magnitude and phase** check box specifies for Time Scope to plot the magnitude and phase of the input signal. The magnitude and phase appear on two separate axes within the same active display. After you select this check box, click **OK**. The active display shows the magnitude of the input signal on the top axes. The signal phase, in degrees, appears on the bottom axes. See the following figure.

# Time Scope



## Example: Display Variable-size Input Signal


At the MATLAB command prompt, type `ex_timescope_varsize` to open the example model. The following Simulink model appears.



In this example, the size of the input signal to the Time Scope block changes as the simulation progresses. When the simulation time is less than 5 seconds, Time Scope plots the signal connected to the third input port of the Switch block, which has signal dimensions 1 by 2. After 5 seconds, Time Scope plots the signal connected to the first input port of the Switch block, which has signal dimensions 1 by 3. Run your model to see the time domain output, as shown in the following figure.

# Time Scope


---



As you can see in the figure, the third line on the display, colored cyan, appears only after 5 seconds.

## **Example: Display Simulink Enumeration Input Signal**

At the MATLAB command prompt, type `ex_timescope_slenum` to open the example model. The following Simulink model appears.




In this example, Simulink imports the variable  $x$ , which is a Simulink enumeration data type, from the MATLAB workspace. This variable is created when the model loads because the commands that construct it reside in the Preload function. To view these commands, in the Simulink menu, select **File > Model Properties > Model Properties**. The following lines of MATLAB code appear.

```
if ~exist('BasicColors','class')
    Simulink.defineIntEnumType('BasicColors', ...
        {'Red', 'Yellow', 'Blue'}, ...
        [0;1;2], ...
        'Description', 'Basic colors', ...
        'DefaultValue', 'Blue', ...
```

# Time Scope

```
'AddClassNameToEnumNames', true);  
end  
x = [BasicColors(0), BasicColors(2), BasicColors(1)];
```


The Signal from Workspace block has a Sample time of 3 seconds. Thus, the input signal changes to the next value in the vector  $x$  every 3 seconds. Run your model to see the time domain output, as shown in the following figure.



As you can see in the figure, the y-axis shows the units of amplitude as one of Red, Yellow, or Blue. The input signal value changes from Red to Blue at 3 seconds and from Blue to Yellow at 6 seconds.

## Example: Use Bilevel Measurements Panel with Clock Input Signal

At the MATLAB command prompt, type `ex_timescope_clockex` to open the example model. The following Simulink model appears.




In this example, Simulink imports the variable  $x$  from the MATLAB workspace. This variable is created when the model loads because the commands that construct it reside in the Preload function. To

# Time Scope

view these commands, in the Simulink menu, select **File > Model Properties > Model Properties**. The Model Properties dialog box appears. Click the **Callbacks** tab. The following lines of MATLAB code appear.

```
load clockex;  
ts = t(2)-t(1);
```


Run your model to see the time domain output. To show the **Bilevel Measurements** panel, in the Time Scope menu, select **Tools > Measurements > Bilevel Measurements**. To collapse the **Transitions** pane, click the pane collapse button (▼) next to that label. To expand the **Settings** pane and the **Overshoots / Undershoots** pane, click the pane expand button (▶) next to each label. The Time Scope figure appears as shown in the following figure.



As you can see in the figure, the value for the rising edge **Settling Time** parameter is initially not displayed. The reason for this is that the default value for the **Settle Seek** parameter is too large for this example. In this case, the settle seek time is longer than the entire simulation duration. Enter a value for settle seek of  $2e-6$ , and press the **Enter** key. Time Scope now displays a rising edge settling time value of **118.392 ns**.


The settling time value displayed is actually the statistical average of the settling times for all five rising edges. To show the settling time for only one rising edge, you can zoom in on that transition. In the Time Scope toolbar, click the Zoom X button (). Click on the display near a value of 2 microseconds on the *time*-axis. Drag to the right and release near a value of 4 microseconds on the *time*-axis. Time Scope updates the rising edge **Settling Time** value to reflect the new time window, as shown in the following figure.

# Time Scope



## Example: Find Heart Rate Using Peak Finder Panel with ECG Input Signal

At the MATLAB command prompt, type `ex_timescope_heartbeat` to open the example model. The following Simulink model appears.




In this example, Simulink imports the variable *mhb* from the MATLAB workspace. The variable *mhb* is created when the model loads because the commands that construct *mhb* are in the Preload function. To view these commands, in the Simulink menu, select **File > Model Properties > Model Properties**. The Model Properties dialog box appears. Click the **Callbacks** tab. The following lines of MATLAB code appear.

```
x1 = 3.5*ecg(2700).';  
y1 = sgolayfilt(kron(ones(1,13),x1),0,21);  
n = (1:30000)';  
del = round(2700*rand(1));  
mhb = y1(n + del);  
ts = 0.00025;
```

# Time Scope

This example uses the Savitzky-Golay filter in Signal Processing Toolbox. For more information, see the `sgolayfilt` function reference page or run the `sgolaydemo` example.

Run your model to see the time domain output. To show the **Peak Finder** panel, in the Time Scope menu, select **Tools > Measurements > Peak Finder**. To expand the **Settings** pane, click the pane expand button (▶) next to that label. Enter a value for **Max Num of Peaks** of 10 and press the **Enter** key. Time Scope now displays in the **Peaks** pane a list of 10 peak amplitude values, and the times at which they occur, as shown in the following figure.



As you can see from the list of peak values, there is a constant time difference of 0.675 seconds between each heartbeat. Therefore, the heart rate of the ECG signal is given by the following equation.

$$\frac{60 \frac{\text{sec}}{\text{min}}}{0.675 \frac{\text{sec}}{\text{beat}}} = 88.89 \frac{\text{beats}}{\text{min}} (\text{bpm})$$

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed and unsigned)</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> <li>• Simulink enumerations</li> </ul>

## Supported Simulation Modes

You can use the Time Scope block in models running the following supported simulation modes.

Mode	Supported	Notes and Limitations
Normal	Yes	
Accelerator	Yes	

# Time Scope

Mode	Supported	Notes and Limitations
Rapid Accelerator	Yes	You can use Rapid Accelerator mode as a method to increase the execution speed of your Simulink model. Rapid Accelerator mode creates an executable that includes the solver and model methods. This executable resides outside MATLAB and Simulink. Rapid Accelerator mode uses External mode to communicate with Simulink. For more information about Rapid Accelerator mode, see “Acceleration” in the Simulink documentation.
PIL	No	
SIL	No	
External	Yes	<p>You can use External mode to tune block parameters in real time and view block outputs in many types of blocks and subsystems. External mode establishes communication between a host system, where the Simulink environment resides, and a target system, where the executable runs after it is generated by the code generation and build process. For more information about External mode, see “Host/Target Communication” in the Simulink Coder documentation.</p> <p>Time Scope does not support data archiving. See “Set External Mode Data Archiving Parameters” in the Real-Time Windows Target documentation.</p> <p>Do not interactively open or close the Time Scope between the Connect and Start of the target. Attempting to do causes a checksum mismatch between the built model and the</p>

Mode	Supported	Notes and Limitations
		model in session. Open the Time Scope either before building or after starting the simulation.

For more information about these modes, see “How Acceleration Modes Work” in the Simulink documentation.

## See Also

Scope | `dsp.TimeScope` | Spectrum Scope | Vector Scope | `sptool`

## How To

- Display Time-Domain Data in the Time Scope

# Time-Varying Direct-Form II Transpose Filter (Obsolete)

---

**Purpose** Apply variable IIR filter to input

**Library** dspobslib

**Description**



---

**Note** This block is now just an implementation of the Digital Filter block.

---

# Time-Varying Lattice Filter (Obsolete)

---

**Purpose** Apply variable lattice filter to input

**Library** dspobslib

**Description**

---

**Note** This block is now just an implementation of the Digital Filter block.

---

# Toeplitz

---

**Purpose** Generate matrix with Toeplitz symmetry

**Library** Math Functions / Matrices and Linear Algebra / Matrix Operations  
dspmtx3

**Description** The Toeplitz block generates a Toeplitz matrix from inputs defining the first column and first row. The top input (Col) is a vector containing the values to be placed in the first *column* of the matrix, and the bottom input (Row) is a vector containing the values to be placed in the first *row* of the matrix.

```
y = toeplitz(Col,Row) % Equivalent MATLAB code
```

The other elements of the matrix obey the relationship

$$y(i,j) = y(i-1,j-1)$$

and the output has dimension [length(Col) length(Row)]. The y(1,1) element is inherited from the Col input. For example, the following inputs

```
Col = [1 2 3 4 5]  
Row = [7 7 3 3 2 1 3]
```

produce the Toeplitz matrix

$$\begin{bmatrix} 1 & 7 & 3 & 3 & 2 & 1 & 3 \\ 2 & 1 & 7 & 3 & 3 & 2 & 1 \\ 3 & 2 & 1 & 7 & 3 & 3 & 2 \\ 4 & 3 & 2 & 1 & 7 & 3 & 3 \\ 5 & 4 & 3 & 2 & 1 & 7 & 3 \end{bmatrix}$$


When you select the **Symmetric** check box, the block generates a symmetric (Hermitian) Toeplitz matrix from a single input, u, defining both the first row and first column of the matrix.

```
y = toeplitz(u) % Equivalent MATLAB code
```

The output has dimension  $[\text{length}(u) \text{ length}(u)]$ . For example, the Toeplitz matrix generated from the input vector  $[1 \ 2 \ 3 \ 4]$  is

$$\begin{bmatrix} 1 & 2 & 3 & 4 \\ 2 & 1 & 2 & 3 \\ 3 & 2 & 1 & 2 \\ 4 & 3 & 2 & 1 \end{bmatrix}$$

The Toeplitz block supports real and complex floating-point and fixed-point inputs.



## Dialog Box

### Symmetric

When selected, enables the single-input configuration for symmetric Toeplitz matrix output.

### Saturate on integer overflow

When you generate a symmetric Toeplitz matrix with this block, if the input vector is complex, the output is a symmetric Hermitian matrix whose elements satisfy the relationship

# Toeplitz

$$y(i, j) = \text{conj}(y(j, i))$$

For fixed-point signals the conjugate operation could result in an overflow. When you select this parameter, overflows saturate. This parameter is only visible with the **Symmetric** parameter is selected. This parameter is ignored for floating-point signals.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers (real signals only)</li></ul>
Toep Col	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

Port	Supported Data Types
Toep Row	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed and unsigned)</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>
Output	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Fixed point (signed and unsigned)</li> <li>• Boolean</li> <li>• 8-, 16-, and 32-bit signed integers</li> <li>• 8-, 16-, and 32-bit unsigned integers</li> </ul>

## See Also

Constant Diagonal Matrix  
toeplitz

DSP System Toolbox  
MATLAB


# To Audio Device

---

**Purpose** Write audio data to computer's audio device

**Library** Sinks  
dspnks4

## Description



The To Audio Device block sends audio data to your computer's audio device. This block is not supported for use with the Simulink Model block.

Use the **Device** parameter to specify the device to which you want to send the audio data. This parameter is automatically populated based on the audio devices installed on your system. If you plug or unplug an audio device from your system, type `clear mex` at the MATLAB command prompt to update the list.

Select the **Inherit sample rate from input** check box if you want the block to inherit the sample rate of the audio signal from the input to the block. If you clear this check box, the **Sample rate (Hz)** parameter appears on the block. Use this parameter to specify the number of samples per second in the signal.

The range of supported audio device sample rates and data type formats, depend on both the sound card and the API which is chosen for the sound card.

Use the **Device data type** to specify the data type of the audio data that is sent to the device. You can choose:

- 8-bit integer
- 16-bit integer
- 24-bit integer
- 32-bit float
- Determine from input data type

If you choose **Determine from input data type**, the following table summarizes the block's behavior.


Input Data Type	Device Data Type
Double-precision floating point or single-precision floating point	32-bit floating point
32-bit integer	24-bit integer
16-bit integer	16-bit integer
8-bit integer	8-bit integer

If you choose `Determine` from `input data type` and the device does not support the input data type, the block uses the next lowest-precision data type supported by the device.

The generated code for this block relies on prebuilt `.dll` files. You can run this code outside the MATLAB environment, or redeploy it, but be sure to account for these extra `.dll` files when doing so. The `packNGo` function creates a single zip file containing all of the pieces required to run or rebuild this code. See `packNGo` for more information.

## Buffering

The To Audio Device block buffers the data from a Simulink signal using the process illustrated by the following figure.



To Audio Device Block

# To Audio Device

---

- 1** At the start of the simulation, the queue is filled with silence. Specify the size of this queue using the **Queue duration (seconds)** parameter. As Simulink runs, the block appends Simulink frames to the bottom of the queue.
- 2** At each time step, the blocks sends a buffer of samples from the top of the queue to the audio device. Select the **Automatically determine buffer size** check box to allow the block to use a conservative buffer size. See the From Audio Device block reference page for the equation the block uses to calculate this buffer size. If you clear this check box, the **Buffer size (samples)** parameter appears on the block. Use this parameter to specify the size of the buffer in samples.
- 3** The block writes the buffer of audio data to the device. If the queue did not contain enough data to completely fill the buffer, the block fills the remaining portion of the buffer with zeros. This data has a the data type specified by the **Device data type** parameter.

When the simulation throughput rate is lower than the hardware throughput rate, the queue, which is initially full, becomes empty. If the queue is empty, the block sends zeros (silence) to the audio device. When the simulation throughput rate is higher than the hardware throughput rate, the To Audio Device block waits to write data to the queue.

To minimize the chance of dropouts, the block checks to make sure the queue duration is at least as large as the maximum of the buffer size and the frame size. If it is not, the queue duration is automatically set to this maximum value.

## Troubleshooting

When Simulink cannot keep up with an audio device that is operating in real time, the queue becomes empty and gaps occur in the audio data that the block sends to the device. Here are several ways to deal with this situation:

- *Increase the queue duration.*

The **Queue duration (seconds)** parameter specifies the duration of the signal, in seconds, that can be buffered during the simulation. This is the maximum length of time that the block's data supply can lag the hardware's data demand.

- *Increase the buffer size.*

The size of the buffer processed in each interrupt from the audio device affects the performance of your model. If the buffer is too small, a large portion of hardware resources are used to write data to the device. If the buffer is too big, Simulink must wait for the device to empty the buffer before it can write the data to the queue, which introduces latency.

- *Increase the simulation throughput rate.*

Two useful methods for improving simulation throughput rates are increasing the signal frame size and compiling the simulation into native code:

- Increase frame sizes and use frame-based processing throughout the model to reduce the amount of block-to-block communication overhead. This can increase throughput rates in many cases. However, larger frame sizes generally result in greater model latency due to initial buffering operations.
- Generate executable code with Simulink Coder code generation software. Native code runs much faster than Simulink and should provide rates adequate for real-time audio processing.

Other ways to improve throughput rates include simplifying the model and running the simulation on a faster PC processor. For other ideas on improving simulation performance, see “Delay and Latency” and “Performance” in the Simulink documentation.

## **Channel-to-Speaker Mapping on Windows Operating Systems**

The To Audio Device and From Audio Device blocks can support multiple channels. On Windows operating systems, the channel-to-speaker mapping is defined as listed below. This mapping only applies when

## To Audio Device

---

your sound card is properly configured and capable of receiving the audio data you send. If the number of channels on the card does not match the number of channels on the block, or if you specify a data type for the **Device data type** parameter that is not supported by your device, the Windows mixer intervenes to translate from one format to another. If the Windows mixer does intervene, the channel-to-speaker mapping might differ from what is specified here.

- Single channel input — Front center speaker  
On systems with two speakers, the front center channel is split between the right and left speakers.
- Multichannel input — Channels are assigned to speakers as follows:
  - One channel — Front center
  - Two channels — Front left, front right
  - Four channels — Front left, front right, rear left, rear right
  - Six channels — Front left, front right, front center, low frequency, rear left, rear right
  - Eight channels — Front left, front right, front center, low frequency, rear left, rear right, front left center, front right center
  - For all other channel combinations, the channel assignment is dictated by the audio card.

### Audio Hardware API

The To Audio Device and From Audio Device blocks use the open-source PortAudio library in order to communicate with the audio hardware on a given computer. The PortAudio library supports a range of APIs designed to communicate with the audio hardware on a given platform. The following API choices were made when building the PortAudio library for the DSP System Toolbox product:


- Windows: DirectSound, WDM-KS, ASIO
- Linux: OSS, ALSA

- Mac: CoreAudio

To select or change the Audio Hardware API, select **Preferences** from the MATLAB Toolstrip. Then select DSP System Toolbox from the tree menu. In the **DSP System Toolbox Preferences** dialog box, the option is disabled if no device corresponds to that particular audio API.

## Example

See the Positional Audio example for a demonstration of how to use this block. You can open this example by typing `dspAudioPos` at the MATLAB command line.



## Dialog Box

### Device

Specify which device to send the audio data to.

### Inherit sample rate from input

Select this check box if you want the block to inherit the sample rate of the audio signal from the input to the block.

# To Audio Device

---

## Sample rate (Hz)

Specify the number of samples per second in the signal. This parameter is visible when the **Inherit sample rate from input** check box is cleared.

## Device data type

Specify the data type of the audio data sent to the device.

## Automatically determine buffer size

Select this check box to allow the block to calculate a conservative buffer size.

## Buffer size (samples)

Specify the size of the buffer. This parameter is visible when the **Automatically determine buffer size** check box is cleared.

## Queue duration (seconds)

Specify the size of the queue in seconds.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• 32-bit signed integers</li><li>• 16-bit signed integers</li><li>• 8-bit unsigned integers</li></ul>


## See Also

From Audio Device	DSP System Toolbox
To Multimedia File	DSP System Toolbox
audioplayer	MATLAB
sound	MATLAB
dsp.AudioPlayer	System Object

**Purpose** Write video frames and audio samples to multimedia file

**Library** Sinks  
dspnks4

## Description



The To Multimedia File block writes video frames, audio samples, or both to a multimedia (.avi, .wav, .wma, or .wmv) file.

You can compress the video frames or audio samples by selecting a compression algorithm. You can connect as many of the input ports as you want. Therefore, you can control the type of video and/or audio the multimedia file receives.

---

**Note** This block supports code generation for platforms that have file I/O available. You cannot use this block with Real-Time Windows Target software, because that product does not support file I/O.

This block performs best on platforms with Version 11 or later of Windows Media® Player software. This block supports only uncompressed RGB24 AVI files on Linux® and Mac platforms.

Windows 7 UAC (User Account Control), may require administrative privileges to encode WMV and WMA files.

---

The generated code for this block relies on prebuilt library files. You can run this code outside the MATLAB environment, or redeploy it, but be sure to account for these extra library files when doing so. The

# To Multimedia File

---

packNGo function creates a single zip file containing all of the pieces required to run or rebuild this code. See packNGo for more information.

To run an executable file that was generated from a model containing this block, you may need to add precompiled shared library files to your system path. See “Understanding Code Generation” for details.

## Cross-Platform Supported File Formats for Audio Files

Audio files can be of the following formats on all platforms:


- WAV
- FLAC
- OGG

## Ports

Port	Description
Image	$M$ -by- $N$ -by-3 matrix RGB, Intensity, or YCbCr 4:2:2 signal.
R, G, B	Matrix that represents one plane of the RGB video stream. Inputs to the R, G, or B port must have the same dimensions and data type.
Audio	Vector of audio data
Y, Cb, Cr	Matrix that represents one frame of the YCbCr video stream. The Y, Cb, and Cr ports use the following dimensions: $Y: M \times N$ $Cb: M \times \frac{N}{2}$ $Cr: M \times \frac{N}{2}$

## Dialog Box

The **Main** pane of the To Multimedia File block dialog appears as follows.



### File name

Specify the name of the multimedia file. The block saves the file in your current folder. To specify a different file or location, click the **Save As...** button.

### File type

Specify the file type of the multimedia file. You can select avi, wav, wma, or wmv.

# To Multimedia File

---

## **Write**

Specify whether the block writes video frames, audio samples, or both to the multimedia file. You can select **Video and audio**, **Video only**, or **Audio only**.

## **Audio compressor**

Select the type of compression algorithm to use to compress the audio data. This compression reduces the size of the multimedia file. Choose **None (uncompressed)** to save uncompressed audio data to the multimedia file.

---

**Note** The other items available in this parameter list are the audio compression algorithms installed on your system. For information about a specific audio compressor, see the documentation for that compressor.

---

## **Audio data type**

Select the audio data type. You can use the **Audio data type** parameter only for uncompressed wave files.

## **Video compressor**

Select the type of compression algorithm to use to compress the video data. This compression reduces the size of the multimedia file. Choose **None (uncompressed)** to save uncompressed video data to the multimedia file.

---

**Note** The other items available in this parameter list are the video compression algorithms installed on your system. For information about a specific video compressor, see the documentation for that compressor.

---

## **File color format**

Select the color format of the data stored in the file. You can select either **RGB** or **YCbCr 4:2:2**.

## Image signal

Specify how the block accepts a color video signal. If you select **One multidimensional signal**, the block accepts an  $M$ -by- $N$ -by- $P$  color video signal, where  $P$  is the number of color planes, at one port. If you select **Separate color signals**, additional ports appear on the block. Each port accepts one  $M$ -by- $N$  plane of an RGB video stream.

## Supported Data Types

For the block to display video data properly, double- and single-precision floating-point pixel values must be between 0 and 1. Any other data type requires the pixel values between the minimum and maximum values supported by their data type.

Check the specific codecs you are using for supported audio rates.

Port	Supported Data Types	Supports Complex Values?
Image	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• Boolean</li> <li>• 8-, 16- 32-bit signed integers</li> <li>• 8-, 16- 32-bit unsigned integers</li> </ul>	No
R, G, B	Same as Image port	No
Audio	<ul style="list-style-type: none"> <li>• Double-precision floating point</li> <li>• Single-precision floating point</li> <li>• 16-bit signed integers</li> <li>• 32-bit signed integers</li> <li>• 8-bit unsigned integers</li> </ul>	No
Y, Cb, Cr	Same as Image port	No

## To Multimedia File

---

### **See Also**

From Multimedia File DSP System Toolbox


# To Wave Device (Obsolete)

---

**Purpose** Send audio data to standard Windows audio device in real time

**Library** dspwin32

## Description



---

**Note** The To Wave Device block is still supported but is likely to be obsoleted in a future release. We strongly recommend replacing this block with the To Audio Device block.

---

The To Wave Device block sends audio data to a standard Windows audio device in real time. It is compatible with most popular Windows hardware, including Sound Blaster cards. The data is sent to the hardware in uncompressed pulse code modulation (PCM) format, and should typically be sampled at one of the standard Windows audio device rates: 8000, 11025, 22050, or 44100 Hz. Some hardware might support other rates in addition to these.

---

**Note** Models that contain both the To Wave Device block and the From Wave Device block require a duplex-capable sound card.

---

The **Use default audio device** check box allows the To Wave Device block to detect and use the system's default audio hardware. You should select this option for systems that have a single sound device installed, or when the default sound device on a multiple-device system is your desired target. When the default sound device is *not* your desired output device, clear **Use default audio device**, and set the desired hardware in the **Audio device** parameter. This parameter lists the names of the installed audio devices.

The block input can contain audio data from a mono or stereo signal. A mono signal is represented as either a sample-based scalar or a frame-based length- $M$  vector, where  $M$  is frame size. A stereo signal is represented as a sample-based length-2 vector or a frame-based  $M$ -by-2 matrix.

## To Wave Device (Obsolete)

---

When the input data type is `uint8`, the block conveys the signal samples to the audio device using 8 bits. When the input data type is `double`, `single`, `int16`, or fixed point with a word length of 16 and a fraction length of 15, the block conveys the signal samples to the audio device using 16 bits by default. For inputs of data type `double` and `single`, you can also set the block to convey the signal samples using 24 bits by selecting the **Enable 24-bit output for double- and single-precision input signals** check box. The 24-bit sample width requires more memory but in general yields better fidelity.

The amplitude of the input must be in a valid range that depends on the input data type, as shown in the following table. Amplitudes outside the valid range are clipped to the nearest allowable value.

Input Data Type	Valid Input Amplitude Range
<code>double</code>	$-1 \leq \textit{amplitude} < 1$
<code>single</code>	$-1 \leq \textit{amplitude} < 1$
<code>int16</code>	$-32768 \leq \textit{amplitude} \leq 32767$
<code>uint8</code>	$0 \leq \textit{amplitude} \leq 255$
Fixed point with a word length of 16 and a fraction length of 15	$-1 \leq \textit{amplitude} \leq 1 - 2^{-15}$

### Buffering

Because audio devices generate real-time audio output, the Simulink environment must maintain a continuous flow of data to a device throughout simulation. Delays in passing data to the audio hardware can result in hardware errors or distortion of the output. This means that the To Wave Device block must in principle supply data to the

## To Wave Device (Obsolete)

audio hardware as quickly as the hardware reads the data. However, the To Wave Device block often *cannot* match the throughput rate of the audio hardware, especially when the simulation is running within Simulink rather than as generated code. Simulink execution speed can vary during the simulation as the host operating system services other processes. The block must therefore rely on a buffering strategy to ensure that signal data is available to the hardware on demand.


---

**Note** This block requires real-time execution of the parent model for best performance.

---

The following block parameters control the memory management for this block:

- **Queue duration**
- **Automatically determine internal buffer size** or **User-defined internal buffer size**
- **Initial output delay**



The **Queue duration** parameter defines the overall size of the block's buffer. The block reads in chunks of data in the size of the input dimensions and stores them in the buffer. The internal buffer size defines the dimensions of the block output to the hardware. You can define the internal buffer size yourself in the **User-defined internal buffer size** parameter. If you select **Automatically determine internal buffer size** instead, the internal buffer size is calculated for you according to the following rules:

## To Wave Device (Obsolete)

---

- If the input to the block has a frame size of 32 samples or larger, the internal buffer size be the same as the input frame size.
- If the input to the block has a frame size smaller than 32 samples, the internal buffer size is based on the input sample rate according to the following table, where

$$F_s = \textit{sampling frequency} = \frac{1}{\textit{sample time}}$$

$F_s$ (Hz)	Internal Buffer Size (samples)
$F_s < 8000$	$\min(64, 2 * F_s)$
$8000 \leq F_s < 22,050$	128
$22,050 \leq F_s < 44,100$	256
$44,100 \leq F_s < 96,000$	512
$F_s \geq 96,000$	1024

To minimize the chance of dropouts, the block checks to make sure that the queue duration is at least as big as twice the internal buffer size. If it is not, the queue duration is automatically set to twice the internal buffer size.

The **Initial output delay** parameter enables you to preload the buffer before the block starts to output data to the audio device, which can be helpful for models that do not run in real time. However, for real-time applications, it is best to set the initial output delay to zero (one frame of delay), or as close to zero as possible.

## Troubleshooting

If you are getting undesirable audio output using the To Wave Device block, first determine whether your model can run in real time. Replace the To Wave Device block with a To Wave File block, run the model, and compare the model's simulation stop time to the elapsed time on your watch. If the model simulation stop time is less than the elapsed time on your watch, your model can probably run in real time. Then,

- If your model can run in real time,
  - 1 Select **Automatically determine internal buffer size**. This alone might solve the problem. If not,
  - 2 Try increasing the **Queue duration** parameter to a relatively large value, such as 0.5 s.

## To Wave Device (Obsolete)


---

If one or both of these options restores desirable audio output, you can try reducing the internal buffer size and/or queue duration until the quality of the audio output again degrades.

- If your model is not running in real time, try to make it run in real time by
  - 1 Optimizing the model (using a more efficient implementation), or
  - 2 Using a Simulink “Acceleration” mode, or
  - 3 Generating stand-alone code

If none of these are possible, but the model only runs for a short period of time, set the **Queue duration** parameter to a size equal to a significant fraction of the model stop time and use a similarly large initial delay. This is not an optimal solution, but might work in some cases.

## Dialog Box



### Queue duration (seconds)

Specify the overall buffer size. To minimize the chance of dropouts, the block checks to make sure that the queue duration is as least as large as twice the internal buffer size. If it is not, the queue duration is automatically set to twice the internal buffer size.

### Automatically determine internal buffer size

Select to have the block automatically select the internal buffer size for you. For details, see “Buffering” on page 2-1548.

# To Wave Device (Obsolete)

---

## **User-defined internal buffer size (samples)**

Define the internal buffer size, or the size of the chunks of data sent by the block to the audio hardware device.

This parameter is only visible when **Automatically determine internal buffer size** is not selected.

## **Initial output delay (seconds)**

Specify the amount of time by which to delay the initial output to the audio device. During this time data accumulates in the block's buffer. Any value less than or equal to the queue duration specifies the smallest possible initial delay, which is a single frame.

## **Use default audio device**

Select to direct audio output to the system's default audio device.

## **Audio device**

This parameter lists the names of the installed audio devices. Specify the name of the audio device to receive the audio output. Select **Use default audio device** when the system has only a single audio card installed.

This parameter is only enabled when the **Use default audio device** check box is not selected.

## **Enable 24-bit output for double and single precision input signals**

Select to output 24-bit data when inputs are double- or single-precision. Otherwise, the block outputs 16-bit data for double- and single-precision inputs.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Signed fixed point with a word length of 16 and a fraction length of 15</li><li>• 16-bit signed integers</li><li>• 8-bit unsigned integers</li></ul>

## See Also

From Wave Device (Obsolete)	DSP System Toolbox
To Wave File (Obsolete)	DSP System Toolbox
audioplayer	MATLAB
sound	MATLAB

# To Wave File (Obsolete)

---

**Purpose** Write audio data to file in Microsoft Wave (.wav) format

**Library** dspwin32

## Description



---

**Note** The To Wave File block is still supported but is likely to be obsoleted in a future release. We strongly recommend replacing this block with the To Multimedia File block.

---

The To Wave File block streams audio data to a Microsoft Wave (.wav) file in the uncompressed pulse code modulation (PCM) format. For compatibility reasons, the sample rate of the discrete-time input signal should typically be one of the standard Windows audio device rates (8000, 11025, 22050, or 44100 Hz), although the block supports arbitrary rates.

The input to the block,  $u$ , can contain audio data with one or more channels. A signal with  $C$  channels is represented as a sample-based length- $C$  vector or a frame-based  $M$ -by- $C$  matrix. The amplitude of the input should be in the range  $\pm 1$ . Values outside this range are clipped to the nearest allowable value.


```
wavwrite(u,Fs,bits,'filename')    % Equivalent MATLAB code
```

---

**Note** AVI files are the only supported file type for non-Windows platforms.

---

## Dialog Box



### File name

Specify the path and name of the file to write. Paths can be relative or absolute. You do not need to specify the .wav extension.

### Sample width (bits)

Specify the number of bits used to represent the signal samples in the file. The higher sample width settings require more memory but yield better fidelity for double- and single-precision inputs:

- 8 — Allocates 8 bits to each sample, allowing a resolution of 256 levels
- 16 — Allocates 16 bits to each sample, allowing a resolution of 65536 levels
- 24 — Allocates 24 bits to each sample, allowing a resolution of 16777216 levels
- 32 — Allocates 32 bits to each sample, allowing a resolution of  $2^{32}$  levels ranging from -1 to 1

# To Wave File (Obsolete)

---

The 8-, 16-, and 24-bit modes output integer data, while the 32-bit mode outputs single-precision floating-point data.

## Minimum number of samples for each write to file

Specify the number of consecutive samples,  $L$ , to write with each file access. To reduce the required number of file accesses, the block writes  $L$  consecutive samples to the file during each access for  $L \geq M$ . For  $L < M$ , the block instead writes  $M$  consecutive samples during each access. Larger values of  $L$  result in fewer file accesses, which reduces run-time overhead.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Signed fixed point with a word length of 16 and a fraction length of 15</li><li>• 16-bit signed integers</li><li>• 8-bit unsigned integers</li></ul>

## See Also

From Multimedia File	DSP System Toolbox
To Audio Device	DSP System Toolbox
Signal To Workspace	DSP System Toolbox
To Workspace	Simulink
wavwrite	MATLAB


## Purpose

Transpose matrix

## Library

Math Functions / Matrices and Linear Algebra / Matrix Operations  
dspmtx3

## Description



The Transpose block transposes the M-by-N input matrix to size N-by-M. When you select the **Hermitian** check box, the block performs the Hermitian (complex conjugate) transpose.

`y = u'`     % Equivalent MATLAB code

$$\begin{bmatrix} u_{11} & u_{12} & u_{13} \\ u_{21} & u_{22} & u_{23} \end{bmatrix} \xrightarrow{u'} \begin{bmatrix} u_{11}^* & u_{21}^* \\ u_{12}^* & u_{22}^* \\ u_{13}^* & u_{23}^* \end{bmatrix}$$

When you do not select the **Hermitian** check box, the block performs the nonconjugate transpose.

`y = u.'`     % Equivalent MATLAB code


$$\begin{bmatrix} u_{11} & u_{12} & u_{13} \\ u_{21} & u_{22} & u_{23} \end{bmatrix} \xrightarrow{u.'} \begin{bmatrix} u_{11} & u_{21} \\ u_{12} & u_{22} \\ u_{13} & u_{23} \end{bmatrix}$$

The block treats length-M vector input as an M-by-1 matrix.

The Transpose block supports real and complex floating-point and fixed-point data types. When **Hermitian** is selected, the block input must be a signed data type.

# Transpose

## Dialog Box



### Hermitian

When selected, specifies the complex conjugate transpose.

### Saturate on integer overflow

This parameter is only visible when the **Hermitian** parameter is selected because overflows can occur when computing the complex conjugate of complex fixed-point signals. When you select this parameter, such overflows saturate. This parameter is ignored for floating-point signals and for real-valued fixed-point signals.

## Supported Data Types

When **Hermitian** is selected, the block input must be a signed data type.

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>

Port	Supported Data Types
	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

## See Also

Math Function	Simulink
Permute Matrix	DSP System Toolbox
Reshape	Simulink
Submatrix	DSP System Toolbox


# Triggered Delay Line (Obsolete)

---

**Purpose** Buffer sequence of inputs into frame-based output

**Library** dspobslib

## Description



---

**Note** The Triggered Delay Line block is still supported but is likely to be obsoleted in a future release. We strongly recommend replacing this block with the Delay Line block.

---

The Triggered Delay Line block acquires a collection of  $M_0$  input samples into a frame, where you specify  $M_0$  in the **Delay line size** parameter. The block buffers a single sample from input 1 whenever it is triggered by the control signal at input 2 (f). When the next triggering event occurs, the newly acquired input sample is appended to the output frame so that the new output overlaps the previous output by  $M_0-1$  samples. Between triggering events the block ignores input 1 and holds the output at its last value.

You specify the triggering event at input 2 in the **Trigger type** pop-up menu:

- **Rising edge** triggers execution of the block when the trigger input rises from a negative value to zero or a positive value, or from zero to a positive value.
- **Falling edge** triggers execution of the block when the trigger input falls from a positive value to zero or a negative value, or from zero to a negative value.
- **Either edge** triggers execution of the block when either a rising or falling edge (as described above) occurs.

The Triggered Delay Line block has zero latency, so the new input appears at the output in the same simulation time step. The output frame period is the same as the input sample period,  $T_{fo}=T_{si}$ .

## Sample-Based Operation

In sample-based operation, the Triggered Delay Line block buffers a sequence of sample-based length- $N$  vector inputs (1-D, row, or column) into a sequence of overlapping sample-based  $M_o$ -by- $N$  matrix outputs, where you specify  $M_o$  in the **Delay line size** parameter ( $M_o > 1$ ). That is, each input vector becomes a *row* in the sample-based output matrix. When  $M_o = 1$ , the input is simply passed through to the output, and retains the same dimension. Sample-based full-dimension matrix inputs are not accepted.

## Frame-Based Operation


In frame-based operation, the Triggered Delay Line block rebuffers a sequence of frame-based  $M_i$ -by- $N$  matrix inputs into an sequence of overlapping frame-based  $M_o$ -by- $N$  matrix outputs, where  $M_o$  is the output frame size specified by the **Delay line size** parameter (that is, the number of consecutive samples from the input frame to rebuffer into the output frame).  $M_o$  can be greater or less than the input frame size,  $M_i$ . Each of the  $N$  input channels is rebuffered independently.

## Initial Conditions

The Triggered Delay Line block's buffer is initialized to the value specified by the **Initial condition** parameter. The block always outputs this buffer at the first simulation step ( $t=0$ ). When the block's output is a vector, the **Initial condition** can be a vector of the same size or a scalar value to be repeated across all elements of the initial output. When the block's output is a matrix, the **Initial condition** can be a matrix of the same size or a scalar to be repeated across all elements of the initial output.

# Triggered Delay Line (Obsolete)

## Dialog Box



### Trigger type

The type of event that triggers the block's execution.

### Delay line size

The length of the output frame (number of rows in output matrix),  $M_o$ .

### Initial condition

The value of the block's initial output, a scalar, vector, or matrix.

# Triggered Delay Line (Obsolete)

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Trigger	<ul style="list-style-type: none"><li>• Any data type supported by the Trigger block</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

## See Also

Buffer	DSP System Toolbox
Delay Line	DSP System Toolbox
Unbuffer	DSP System Toolbox


# Triggered Signal From Workspace

---

**Purpose** Import signal samples from MATLAB workspace when triggered

**Library** Signal Operations  
dspSigOps

## Description



The Triggered Signal From Workspace block imports signal samples from the MATLAB workspace into the Simulink model when triggered by the control signal at the input port (⚡). The **Signal** parameter specifies the name of a MATLAB workspace variable containing the signal to import, or any valid MATLAB expression defining a matrix or 3-D array.

When the **Signal** parameter specifies an M-by-N matrix ( $M \neq 1$ ), each of the N columns is treated as a distinct channel. You specify the frame size in the **Samples per frame** parameter,  $M_o$ , and the output when triggered is an  $M_o$ -by-N matrix containing  $M_o$  consecutive samples from each signal channel. For  $M_o=1$ , the output is sample based; otherwise the output is frame based. For convenience, an imported row vector ( $M=1$ ) is treated as a single channel, so the output dimension is  $M_o$ -by-1.

When the **Signal** parameter specifies an M-by-N-by-P array, the block generates a single page of the array (an M-by-N matrix) at each trigger time. The **Samples per frame** parameter must be set to 1, and the output is always sample based.

## Trigger Event

You specify the triggering event at the input port in the **Trigger type** pop-up menu:

- **Rising edge** triggers execution of the block when the trigger input rises from a negative value to zero or a positive value, or from zero to a positive value.
- **Falling edge** triggers execution of the block when the trigger input falls from a positive value to zero or a negative value, or from zero to a negative value.

- Either edge triggers execution of the block when either a rising or falling edge (as described above) occurs.


## Initial and Final Conditions

The **Initial output** parameter specifies the output of the block from the start of the simulation until the first trigger event arrives. Between trigger events, the block holds the output value constant at its most recent value (that is, no linear interpolation takes place). For single-channel signals, the **Initial output** parameter value can be a vector of length  $M_0$  or a scalar to repeat across the  $M_0$  elements of the initial output frames. For matrix outputs ( $M_0$ -by- $N$  or  $M$ -by- $N$ ), the **Initial output** parameter value can be a matrix of the same size or a scalar to be repeated across all elements of the initial output.

When the block has output all of the available signal samples, it can start again at the beginning of the signal, or simply repeat the final value or generate zeros until the end of the simulation. (The block does not extrapolate the imported signal beyond the last sample.) The **Form output after final data value by** parameter controls this behavior:

- When you specify **Setting To Zero**, the block generates zero-valued outputs for the duration of the simulation after generating the last frame of the signal.
- When you specify **Holding Final Value**, the block repeats the final sample for the duration of the simulation after generating the last frame of the signal.
- When you specify **Cyclic Repetition**, the block repeats the signal from the beginning after generating the last frame. When there are not enough samples at the end of the signal to fill the final frame, the block zero-pads the final frame as necessary to ensure that the output for each cycle is identical (for example, the  $i$ th frame of one cycle contains the same samples as the  $i$ th frame of any other cycle).

# Triggered Signal From Workspace



## Dialog Box

### Signal

The name of the MATLAB workspace variable from which to import the signal, or a valid MATLAB expression specifying the signal.

### Trigger type

The type of event that triggers the block's execution.

### Initial output

The value to output until the first trigger event is received.

### Samples per frame

The number of samples,  $M_o$ , to buffer into each output frame. This value must be 1 when you specify a 3-D array in the **Signal** parameter.

## Form output after final data value by

Specifies the output after all of the specified signal samples have been generated. The block can output zeros for the duration of the simulation (**Setting to zero**), repeat the final data sample (**Holding Final Value**) or repeat the entire signal from the beginning (**Cyclic Repetition**).

## Supported Data Types

- Double-precision floating point
- Single-precision floating point
- Fixed point (signed and unsigned)
- 8-, 16-, and 32-bit signed integers
- 8-, 16-, and 32-bit unsigned integers

## See Also

Signal From Workspace	DSP System Toolbox
Signal To Workspace	DSP System Toolbox
Triggered To Workspace	DSP System Toolbox


# Triggered To Workspace

---

**Purpose** Write input sample to MATLAB workspace when triggered

**Library** Sinks  
dspnsks4

## Description



The Triggered To Workspace block creates a matrix or array variable in the MATLAB workspace, where it stores the acquired inputs at the end of a simulation. The block overwrites an existing variable with the same name.

When you set the **Save 2-D signals as** parameter to 2-D array (concatenate along first dimension, the block saves an  $M$ -by- $N$  input as a  $P$ -by- $N$  matrix, where  $P$  is the **Maximum number of rows** parameter. When the simulation progresses long enough for the block to acquire more than  $P$  samples, the block stores only the most recent  $P$  samples. The **Decimation factor**,  $D$ , allows you to store only every  $D$ th input matrix.

When you set the **Save 2-D signals as** parameter to 3-D array (concatenate along third dimension, the block saves an  $M$ -by- $N$  input as a three-dimensional array in which each  $M$ -by- $N$  page represents a single sample from each of the  $M*N$  channels (the most recent input matrix occupies the last page). The maximum size of this variable is limited to  $M$ -by- $N$ -by- $P$ , where  $P$  is the **Maximum number of rows** parameter. When the simulation progresses long enough for the block to acquire more than  $P$  inputs, it stores only the last  $P$  inputs. The **Decimation factor**,  $D$ , allows you to store only every  $D$ th input matrix.

The block acquires and buffers a single frame from input 1 whenever it is triggered by the control signal at input 2 (⚡). At all other times, the block ignores input 1. You specify the triggering event at input 2 in the **Trigger type** pop-up menu:

- **Rising edge** triggers execution of the block when the trigger input rises from a negative value to zero or a positive value, or from zero to a positive value.


- **Falling edge** triggers execution of the block when the trigger input falls from a positive value to zero or a negative value, or from zero to a negative value.
- **Either edge** triggers execution of the block when either a rising or falling edge (as described above) occurs.

To save a record of the sample time corresponding to each sample value, open the Configuration Parameters dialog box. In the **Select** pane, click **Data Import/Export**. In the **Save to workspace** section, select the **Time** check box.

The nontriggered version of this block is the Signal To Workspace block.

# Triggered To Workspace

## Dialog Box



### Trigger type

The type of event that triggers the block's execution.

### Variable name

The name of the workspace variable in which to store the data.

## Maximum number of rows

The maximum number of rows (one row per time step) to be saved,  $P$ .

## Decimation

The decimation factor,  $D$ .

## Save 2-D signals as

Specify whether the block saves 2-D signals as a 2-D or 3-D array in the MATLAB workspace:

- 2-D array (concatenate along first dimension) — When you select this option, the block vertically concatenates each  $M$ -by- $N$  matrix input with the previous input to produce a 2-D output array.
- 3-D array (concatenate along third dimension) — When you select this option, the block saves an  $M$ -by- $N$  input signal as a 3-D array. The maximum size of this 3-D array is limited to  $M$ -by- $N$ -by- $P$ , where  $P$  is the **Maximum number of rows** parameter. When the simulation progresses long enough for the block to acquire more than  $P$  inputs, the block stores only the last  $P$  inputs. The **Decimation factor**,  $D$ , allows you to store only every  $D$ th input matrix.

---

**Note** The Inherit from input (this choice will be removed - see release notes) option will be removed in a future release. See the *DSP System Toolbox Release Notes* for more information.

---

## Log fixed-point data as a fi object

Select to log fixed-point data to the MATLAB workspace as a Fixed-Point Toolbox `fi` object. Otherwise, fixed-point data is logged to the workspace as `double`.

# Triggered To Workspace

---

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>Any data type supported by the To Workspace block</li></ul>
Trigger	<ul style="list-style-type: none"><li>Any data type supported by the Trigger block</li></ul>

## See Also

Signal From Workspace	DSP System Toolbox
Signal To Workspace	DSP System Toolbox
To Workspace	Simulink
Triggered Signal From Workspace	DSP System Toolbox

# Two-Channel Analysis Subband Filter

## Purpose


Decompose signal into high-frequency and low-frequency subbands

## Library

Filtering / Multirate Filters


`dspmlti4`

## Description



The Two-Channel Analysis Subband Filter block decomposes the input into high-frequency and low-frequency subbands, each with half the bandwidth and half the sample rate of the input.

The block filters the input with a pair of highpass and lowpass FIR filters, and then downsamples the results by 2, as illustrated in the following figure.



The block implements the FIR filtering and downsampling steps together using a polyphase filter structure, which is more efficient than the straightforward filter-then-decimate algorithm shown in the preceding figure. Each subband is the first phase of the respective polyphase filter. You can implement a multilevel dyadic analysis filter bank by connecting multiple copies of this block or by using the Dyadic Analysis Filter Bank block. See “Creating Multilevel Dyadic Analysis Filter Banks” on page 2-1578 for more information.

You must provide a vector of filter coefficients for the lowpass and highpass FIR filters. Each filter should be a half-band filter that passes the frequency band that the other filter stops.

See the following topics for more information about this block:

- “Specifying the FIR Filters” on page 2-1576
- “Frame-Based Processing” on page 2-1576
- “Sample-Based Processing” on page 2-1577
- “Latency” on page 2-1577

# Two-Channel Analysis Subband Filter

---

- “Creating Multilevel Dyadic Analysis Filter Banks” on page 2-1578

## Specifying the FIR Filters

You must provide the vector of numerator coefficients for the lowpass and highpass filters in the **Lowpass FIR filter coefficients** and **Highpass FIR filter coefficients** parameters.

For example, to specify a filter with the following transfer function, enter the vector [b(1) b(2) . . . b(m)].

$$H(z) = B(z) = b_1 + b_2z^{-1} + \dots + b_mz^{-(m-1)}$$

Each filter should be a half-band filter that passes the frequency band that the other filter stops. You can use the Two-Channel Synthesis Subband Filter block to reconstruct the input to this block. To do so, you must design perfect reconstruction filters to use in the synthesis subband filter.

The best way to design perfect reconstruction filters is to use the Wavelet Toolbox `wfilters` function in to design both the filters both in this block and in the Two-Channel Synthesis Subband Filter block. You can also use other DSP System Toolbox and Signal Processing Toolbox functions. To learn how to design your own perfect reconstruction filters, see “References” on page 2-1589.

The Two-Channel Analysis Subband Filter block initializes all filter states to zero.

## Frame-Based Processing

When you set the **Input processing** parameter to **Columns as channels (frame based)**, the block accepts any two  $M$ -by- $N$  matrices with the same frame rates. The block treats each column of the input as the high- or low-frequency subbands of the corresponding output channel. You can use the **Rate options** parameter to specify how the block resamples the input:

- When you set the **Rate options** parameter to **Enforce single-rate processing**, the input to the block can be an  $M$ -by- $N$  matrix, where

# Two-Channel Analysis Subband Filter

---

$M$  is a multiple of two. The block treats each column of the input as an independent channel and decomposes each channel over time. The block outputs two matrices, where each column of the output is the high- or low-frequency subband of the corresponding input column. To maintain the input sample rate, the block decreases the output frame size by a factor of two.

- When you set the **Rate options** parameter to **Allow multirate processing**, the block treats an  $M_i$ -by- $N$  matrix input as  $N$  independent channels and decomposes each channel over time. The block outputs two  $M$ -by- $N$  matrices, where each column of the output is the high- or low-frequency subband of the corresponding input column. The input and output frame *sizes* are the same, but the frame *rate* of the output is half that of the input. Thus, the overall sample rate of the output is half that of the input.

In this mode, the block has one frame of latency, as described in the “Latency” on page 2-1577 section.

## Sample-Based Processing

When you set the **Input processing** parameter to **Elements as channels** (sample based), the block treats an  $M$ -by- $N$  matrix input as  $M \cdot N$  independent channels. The block decomposes each channel over time and outputs two  $M$ -by- $N$  matrices whose sample rates are half the input sample rate. Each element in the output matrix is the high- or low-frequency subband output of the corresponding element of the input matrix.

Depending on the setting of your Simulink configuration parameters, the output may have one sample of latency, as described in the “Latency” on page 2-1577 section.

## Latency

When you set the **Input processing** parameter to **Columns as channels** (frame based) and the **Rate options** parameter to **Enforce single-rate processing**, the Two-Channel Analysis Subband Filter block always has zero-tasking latency. *Zero-tasking latency* means that

# Two-Channel Analysis Subband Filter

---

the block propagates the first input sample (received at time  $t=0$ ) as the first output sample.

When you set the **Rate options** parameter to Allow multirate processing, the Two-Channel Analysis Subband Filter block may exhibit latency. The amount of latency depends on the setting of the **Input processing** parameter of this block, and the setting of the Simulink **Tasking mode for periodic sample times** configuration parameter. The following table summarizes the conditions that produce latency when the block is performing multirate processing.

<b>Input processing</b>	<b>Tasking mode for periodic sample times</b>	<b>Latency</b>
Elements as channels (sample based)	SingleTasking	None.
	MultiTasking or Auto	One sample. The first output sample in each channel always has a value of 0.
Columns as channels (frame based)	SingleTasking, MultiTasking or Auto	One frame. All samples in the first output frame have a value of 0.

---

**Note** For more information on latency and the Simulink tasking modes, see “Excess Algorithmic Delay (Tasking Latency)” in the *DSP System Toolbox User’s Guide* and “Scheduling” in the *Simulink Coder User’s Guide*.

---

## Creating Multilevel Dyadic Analysis Filter Banks

The Two-Channel Analysis Subband Filter block is the basic unit of a dyadic analysis filter bank. You can connect several of these blocks to implement an  $n$ -level filter bank, as illustrated in the following figure. For a review of dyadic analysis filter banks, see the Dyadic Analysis Filter Bank block reference page.

# Two-Channel Analysis Subband Filter

---

When you create a filter bank by connecting multiple copies of this block, the output values of the filter bank differ depending on whether there is latency. Though the output values differ, both sets of values are valid; the difference arises from changes in latency. See the “Latency” on page 2-1577 section for more information about when latency can occur in the Two-Channel Analysis Subband Filter block.

In some cases, rather than connecting several Two-Channel Analysis Subband Filter blocks, you can use the Dyadic Analysis Filter Bank block, which is faster and requires less memory. In particular, the Dyadic Analysis Filter Bank block is more efficient under the following conditions:


- The frame size of the signal you are decomposing is a multiple of  $2^n$ .
- You are decomposing the signal into  $n+1$  or  $2^n$  subbands.

In all other cases, use Two-Channel Analysis Subband Filter blocks to implement your filter banks.

# Two-Channel Analysis Subband Filter

## 3-Level Dyadic Analysis Filter Banks

### Conceptual illustration




Both implementations of the dyadic analysis filter bank decompose a frame-based signal with frame size a multiple of  $2^n$  into  $n+1$  subbands, where  $n = 3$ .


In this case, the Dyadic Analysis Filter Bank block's implementation is more efficient.

Use the Two-Channel Analysis Subband Filter block implementation for other cases, such as to handle sample-based inputs, or to handle frame-based inputs whose frame size is not a multiple of  $2^n$ .

### Two-Channel Analysis Subband Filter block implementation



### Dyadic Analysis Filter Bank block implementation




The Dyadic Analysis Filter Bank block allows you to specify the filter bank filters by providing vectors of filter coefficients, just as this block does. The Dyadic Analysis Filter Bank block provides an additional option of using wavelet-based filters that the block designs by using a wavelet you specify.

## Fixed-Point Data Types

The Two-Channel Analysis Subband Filter Bank block is composed of two FIR Decimation blocks as shown in the following diagram.

# Two-Channel Analysis Subband Filter




For fixed-point signals, you can set the coefficient, product output, accumulator, and output data types of the FIR Decimation blocks as discussed in “Dialog Box” on page 2-1581. For a diagram showing the usage of these data types, see the FIR Decimation block reference page.

## Dialog Box

The **Main** pane of the Two-Channel Analysis Subband Filter block dialog appears as follows.

# Two-Channel Analysis Subband Filter



## Lowpass FIR filter coefficients

Specify a vector of lowpass FIR filter coefficients, in descending powers of  $z$ . The lowpass filter should be a half-band filter that passes the frequency band stopped by the filter specified in the **Highpass FIR filter coefficients** parameter. The default values of this parameter specify a filter based on a third-order

# Two-Channel Analysis Subband Filter

---

Daubechies wavelet. When you use the Two-Channel Synthesis Subband Filter block to reconstruct the input to this block, you need to design perfect reconstruction filters to use in the synthesis subband filter. For more information, see “Specifying the FIR Filters” on page 2-1576.

## Highpass FIR filter coefficients

Specify a vector of highpass FIR filter coefficients, in descending powers of  $z$ . The highpass filter should be a half-band filter that passes the frequency band stopped by the filter specified in the **Lowpass FIR filter coefficients** parameter. The default values of this parameter specify a filter based on a third-order Daubechies wavelet. When you use the Two-Channel Synthesis Subband Filter block to reconstruct the input to this block, you need to design perfect reconstruction filters to use in the synthesis subband filter. For more information, see “Specifying the FIR Filters” on page 2-1576.

## Input processing

Specify how the block should process the input. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The Inherited (this choice will be removed - see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

# Two-Channel Analysis Subband Filter

---

## Rate options

Specify the rate processing rule for the block. You can set this parameter to one of the following options:

- **Enforce single-rate processing** — When you select this option, the block treats each column of the input as an independent channel and decomposes each channel over time. The output has the same sample rate as the input, but the output frame size is half that of the input frame size. To select this option, you must set the **Input processing** parameter to **Columns as channels (frame based)**.
- **Allow multirate processing** — When you select this option, the input and output of the block are the same size, but the sample rate of the output is half that of the input.

Some settings of this parameter cause the block to have nonzero latency. See “Latency” on page 2-1577 for more information.

The **Data Types** pane of the Two-Channel Analysis Subband Filter block dialog appears as follows.

# Two-Channel Analysis Subband Filter

Function Block Parameters: Two-Channel Analysis Subband Filter

Two-Channel Analysis Subband Filter

Decompose a signal into a high-frequency subband (Hi band) and a low-frequency subband (Lo band) using the specified highpass and lowpass FIR filters. Each subband has half the bandwidth and half the sample rate of the original signal. Usually, the highpass and lowpass filters should be half-band filters designed to complement each other.

Main Data Types

Fixed-point operational parameters

Rounding mode: Floor Overflow mode: Wrap

Floating-point inheritance takes precedence over the settings in the 'Data Type' column below. When the block input is floating point, all block data types match the input.

	Data Type	Assistant	Minimum	Maximum
Coefficients:	Inherit: Same word length as input	>>	[]	[]
Product output:	Inherit: Inherit via internal rule	>>		
Accumulator:	Inherit: Inherit via internal rule	>>		
Output:	Inherit: Same as accumulator	>>	[]	[]

Lock data type settings against changes by the fixed-point tools

OK Cancel Help Apply

## Rounding mode

Select the rounding mode for fixed-point operations. The filter coefficients do not obey this parameter; they are always rounded to Nearest.

# Two-Channel Analysis Subband Filter

---

---

**Note** The **Rounding mode** and **Overflow mode** settings have no effect on numerical results when all the following conditions exist:

- **Product output data type** is Inherit: Inherit via internal rule
- **Accumulator data type** is Inherit: Inherit via internal rule
- **Output data type** is Inherit: Same as accumulator

With these data type settings, the block is effectively operating in full precision mode.

---

## Overflow mode

Select the overflow mode for fixed-point operations. The filter coefficients do not obey this parameter; they are always saturated.

## Coefficients data type

Specify the coefficients data type. See “Fixed-Point Data Types” on page 2-1580 and “Multiplication Data Types” for illustrations depicting the use of the coefficients data type in this block. You can set it to:

- A rule that inherits a data type, for example, Inherit: Same word length as input
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Coefficients data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Product output data type

Specify the product output data type. See “Fixed-Point Data Types” on page 2-1580 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set it to:


- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`

---

**Note** The actual product output word length may be equal to or greater than the calculated ideal product output word length, depending on the settings on the **Hardware Implementation** pane of the Configuration Parameters dialog box.

---

- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Accumulator data type

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-1580 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

# Two-Channel Analysis Subband Filter

---

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-1580 for illustrations depicting the use of the output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as accumulator`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

## Minimum

Specify the minimum value that the block should output. The default value is [ ] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Maximum

Specify the maximum value that the block should output. The default value is [ ] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)

# Two-Channel Analysis Subband Filter

---

- Automatic scaling of fixed-point data types

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## References

Fliege, N. J. *Multirate Digital Signal Processing: Multirate Systems, Filter Banks, Wavelets*. West Sussex, England: John Wiley & Sons, 1994.

Strang, G. and T. Nguyen. *Wavelets and Filter Banks*. Wellesley, MA: Wellesley-Cambridge Press, 1996.

Vaidyanathan, P. P. *Multirate Systems and Filter Banks*. Englewood Cliffs, NJ: Prentice Hall, 1993.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point
- Fixed point (signed only)
- 8-, 16-, and 32-bit signed integers

## See Also

DWT	DSP System Toolbox
Dyadic Analysis Filter Bank	DSP System Toolbox
FIR Decimation	DSP System Toolbox
IDWT	DSP System Toolbox
Two-Channel Synthesis Subband Filter	DSP System Toolbox
<code>fir1</code>	Signal Processing Toolbox
<code>fir2</code>	Signal Processing Toolbox
<code>firls</code>	Signal Processing Toolbox
<code>wfilters</code>	Wavelet Toolbox

# Two-Channel Analysis Subband Filter

---

For related information, see “Multirate and Multistage Filters”.


# Two-Channel Synthesis Subband Filter

**Purpose** Reconstruct signal from high-frequency and low-frequency subbands

**Library** Filtering / Multirate Filters


dspmlti4

## Description



The Two-Channel Synthesis Subband Filter block reconstructs a signal from its high-frequency and low-frequency subbands, each with half the bandwidth and half the sample rate of the original signal. Use this block to reconstruct signals decomposed by the Two-Channel Analysis Subband Filter block.

The block upsamples the high- and low-frequency subbands by 2, and then filters the results with a pair of highpass and lowpass FIR filters, as illustrated in the following figure.



The block implements the FIR filtering and downsampling steps together using a polyphase filter structure, which is more efficient than the straightforward interpolate-then-filter algorithm shown in the preceding figure. You can implement a multilevel dyadic synthesis filter bank by connecting multiple copies of this block or by using the Dyadic Synthesis Filter Bank block. For more information, see “Creating Multilevel Dyadic Synthesis Filter Banks” on page 2-1595.

You must provide a vector of filter coefficients for the lowpass and highpass FIR filters. Each filter should be a half-band filter that passes the frequency band that the other filter stops. You can use this block to reconstruct the output of a Two-Channel Analysis Subband Filter block. To do so, you must design the filters in this block such that they perfectly reconstruct the outputs of the analysis filters.

See the following topics for more information about this block:

- “Specifying the FIR Filters” on page 2-1592

# Two-Channel Synthesis Subband Filter

---

- “Frame-Based Processing” on page 2-1592
- “Sample-Based Processing” on page 2-1593
- “Latency” on page 2-1594
- “Creating Multilevel Dyadic Synthesis Filter Banks” on page 2-1595

## Specifying the FIR Filters

You must provide the vector of numerator coefficients for the lowpass and highpass filters in the **Lowpass FIR filter coefficients** and **Highpass FIR filter coefficients** parameters.

For example, to specify a filter with the following transfer function, enter the vector [b(1) b(2) . . . b(m)].

$$H(z) = B(z) = b_1 + b_2z^{-1} + \dots + b_mz^{-(m-1)}$$

Each filter should be a half-band filter that passes the frequency band that the other filter stops. You can use this block to reconstruct the output of a Two-Channel Analysis Subband Filter block. To do so, you must design the filters in this block such that they perfectly reconstruct the outputs of the analysis filters.

The best way to design perfect reconstruction filters is to use the Wavelet Toolbox `wfilters` function for the filters in both this block *and* in the corresponding Two-Channel Analysis Subband Filter block. You can also use DSP System Toolbox and Signal Processing Toolbox functions. To learn how to design your own perfect reconstruction filters, see “References” on page 2-1605.

The Two-Channel Synthesis Subband Filter block initializes all filter states to zero.

## Frame-Based Processing

When you set the **Input processing** parameter to **Columns as channels (frame based)**, the block accepts any two  $M$ -by- $N$  matrices with the same frame rates. The block treats each column of the input as the high- or low-frequency subbands of the corresponding output

channel. You can use the **Rate options** parameter to specify how the block resamples the input:

- When you set the **Rate options** parameter to **Enforce single-rate processing**, the input to the block can be any two  $M$ -by- $N$  matrices with the same frame rate. The block treats each input column as the high- or low-frequency subbands of the corresponding output channel. The input to the topmost input port should contain the high-frequency subbands. The block outputs one matrix, where each column is reconstructed from the corresponding columns of each input matrix. The input and output frame *rates* are the same, but the frame *size* of the output is twice that of the input.
- When you set the **Rate options** parameter to **Allow multirate processing**, the block treats each column of the input as the high- or low-frequency subbands of the corresponding output channel. The input to the topmost input port should contain the high-frequency subbands. The block outputs one matrix, where each column is reconstructed from the corresponding columns of the input matrices. The input and output frame *sizes* are the same, but the frame *rate* of the output is twice that of the input. Thus, the overall sample rate of the output is twice that of the input sample rate.

In this mode, the block has one frame of latency, as described in the “Latency” on page 2-1594 section.

## Sample-Based Processing

When you set the **Input processing** parameter to **Elements as channels (sample based)**, the block accepts any two  $M$ -by- $N$  matrices with the same sample rates. The block treats each  $M$ -by- $N$  matrix as  $M \cdot N$  independent subbands. Each element of the input matrices is the high- or low-frequency subband of the corresponding channel in the output matrix. The input to the topmost input port should contain the high-frequency subbands. The block outputs one matrix with the same dimensions as the input matrices, but a sample rate that is twice that of the input. The block reconstructs each element of the output from the corresponding elements in the input matrices.

# Two-Channel Synthesis Subband Filter

---

Depending on the setting of your Simulink configuration parameters, the output may have one sample of latency, as described in the “Latency” on page 2-1594 section.

## Latency

When you set the **Input processing** parameter to Columns as channels (frame based) and the **Rate options** parameter to Enforce single-rate processing, the Two-Channel Synthesis Subband Filter block always has zero-tasking latency. *Zero-tasking latency* means that the block propagates the first input sample (received at time  $t=0$ ) as the first output sample.

When you set the **Rate options** parameter to Allow multirate processing, the Two-Channel Synthesis Subband Filter block may exhibit latency. The amount of latency depends on the setting of the **Input processing** parameter of this block and the setting of the Simulink **Tasking mode for periodic sample times** configuration parameter. The following table summarizes the conditions that produce latency when the block is performing multirate processing.

<b>Input processing</b>	<b>Tasking mode for periodic sample times</b>	<b>Latency</b>
Elements as channels (sample based)	SingleTasking	None.
	MultiTasking or Auto	One sample. The first output sample in each channel always has a value of 0.
Columns as channels (frame based)	SingleTasking, MultiTasking or Auto	One frame. All samples in the first output frame have a value of 0.

---

**Note** For more information on latency and the Simulink tasking modes, see “Excess Algorithmic Delay (Tasking Latency)” in the *DSP System Toolbox User’s Guide* and “Scheduling” in the *Simulink Coder User’s Guide*.

---

## Creating Multilevel Dyadic Synthesis Filter Banks

The Two-Channel Synthesis Subband Filter block is the basic unit of a dyadic synthesis filter bank. You can connect several of these blocks to implement an  $n$ -level filter bank, as illustrated in the following figure. For a review of dyadic synthesis filter banks, see the Dyadic Synthesis Filter Bank block reference page.

When you create a filter bank by connecting multiple copies of this block, the output values of the filter bank differ depending on whether there is latency. Though the output values differ, both sets of values are valid; the difference arises from changes in latency. See the “Latency” on page 2-1594 section for more information about when latency can occur in the Two-Channel Analysis Subband Filter block.


In some cases, rather than connecting several Two-Channel Analysis Subband Filter blocks, you can use the Dyadic Analysis Filter Bank block, which is faster and requires less memory. In particular, the Dyadic Analysis Filter Bank block is more efficient under the following conditions:

- You are reconstructing a signal from  $2^n$  or  $n+1$  subbands.
- The frame size of the signal you are reconstructing is a multiple of  $2^n$ .
- The properties of the subbands you are working with match those of the outputs of the Dyadic Analysis Filter Bank block. These properties are described in the Dyadic Analysis Filter Bank reference page.

# Two-Channel Synthesis Subband Filter

## 3-Level Dyadic Synthesis Filter Banks

### Conceptual illustration




Both implementations of the dyadic analysis filter bank reconstruct a frame-based signal from  $n+1$  subbands, where  $n = 3$ .

In this case, the Dyadic Synthesis Filter Bank block's implementation is more efficient, since the input subbands have the properties of the outputs of a Dyadic Analysis Filter Bank block.


Use the Two-Channel Synthesis Subband Filter block implementation for other cases, such as to handle separate sample-based vectors or matrices of subbands (rather than a single sample-based vector or matrix of concatenated subbands), or to output sample-based signals.

### Two-Channel Synthesis Subband Filter block implementation



Two-Channel Synthesis Subband Filter

### Dyadic Synthesis Filter Bank block implementation




Dyadic Synthesis Filter Bank

The Dyadic Synthesis Filter Bank block allows you to specify the filter bank filters by providing vectors of filter coefficients, just as this block does. The Dyadic Synthesis Filter Bank block provides an additional option of using wavelet-based filters that the block designs by using a wavelet you specify.

## Fixed-Point Data Types

The Two-Channel Synthesis Subband Filter block is composed of two FIR Interpolation blocks as shown in the following diagram.

# Two-Channel Synthesis Subband Filter




For fixed-point signals, you can set the coefficient, product output, accumulator, and output data types used in the FIR Interpolation blocks as discussed in “Dialog Box” on page 2-1597. For a diagram showing the usage of these data types within the FIR blocks, see the FIR Interpolation block reference page.

In addition, the inputs to the Sum block shown in the previous diagram are accumulated using the accumulator data type. The output of the Sum block is then cast from the accumulator data type to the output data type. Therefore the output of the Two-Channel Synthesis Subband Filter block is in the output data type. You also set these data types in the block dialog box as discussed in the “Dialog Box” on page 2-1597 section.

## Dialog Box

The **Main** pane of the Two-Channel Synthesis Subband Filter block dialog appears as follows.

# Two-Channel Synthesis Subband Filter



## Lowpass FIR filter coefficients

A vector of lowpass FIR filter coefficients, in descending powers of  $z$ . The lowpass filter should be a half-band filter that passes the frequency band stopped by the filter specified in the **Highpass FIR filter coefficients** parameter. To use this block to reconstruct the output of a Two-Channel Analysis

# Two-Channel Synthesis Subband Filter

---

Subband Filter block, you must design the filters in this block to perfectly reconstruct the outputs of the analysis filters. For more information, see “Specifying the FIR Filters” on page 2-1592.

## Highpass FIR filter coefficients

A vector of highpass FIR filter coefficients, in descending powers of  $z$ . The highpass filter should be a half-band filter that passes the frequency band stopped by the filter specified in the **Lowpass FIR filter coefficients** parameter. To use this block to reconstruct the output of a Two-Channel Analysis Subband Filter block, you must design the filters in this block to perfectly reconstruct the outputs of the analysis filters. For more information, see “Specifying the FIR Filters” on page 2-1592.

## Input processing

Specify how the block should process the input. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The Inherited (this choice will be removed - see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Rate options

Specify the rate processing rule for the block. You can set this parameter to one of the following options:

- **Enforce single-rate processing** — When you select this option, the block treats each column of the input as an

# Two-Channel Synthesis Subband Filter

---


independent channel and reconstructs each channel over time. The output has the same sample rate as the input, but the output frame size is twice that of the input frame size. To select this option, you must set the **Input processing** parameter to Columns as channels (frame based).

- **Allow multirate processing** — When you select this option, the input and output of the block are the same size, but the sample rate of the output is twice that of the input.

Some settings of this parameter cause the block to have nonzero latency. See “Latency” on page 2-1594 for more information.

The **Data Types** pane of the Two-Channel Synthesis Subband Filter block dialog appears as follows.

# Two-Channel Synthesis Subband Filter



## Round mode

Select the rounding mode for fixed-point operations. The filter coefficients do not obey this parameter; they always round to Nearest.

# Two-Channel Synthesis Subband Filter

---

---

**Note** The **Rounding mode** and **Overflow mode** settings have no effect on numerical results when all the following conditions exist:

- **Product output data type** is Inherit: Inherit via internal rule
- **Accumulator data type** is Inherit: Inherit via internal rule
- **Output data type** is Inherit: Same as accumulator

With these data type settings, the block is effectively operating in full precision mode.

---

## Overflow mode

Select the overflow mode for fixed-point operations. The filter coefficients do not obey this parameter; they are always saturated.

## Coefficients data type

Specify the coefficients data type. See “Fixed-Point Data Types” on page 2-1596 and “Multiplication Data Types” for illustrations depicting the use of the coefficients data type in this block. You can set it to:

- A rule that inherits a data type, for example, Inherit: Same word length as input
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Coefficients data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Product output data type

Specify the product output data type. See “Fixed-Point Data Types” on page 2-1596 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block. You can set it to:


- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`

---

**Note** The actual product output word length may be equal to or greater than the calculated ideal product output word length, depending on the settings on the **Hardware Implementation** pane of the Configuration Parameters dialog box.

---

- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Product output data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Accumulator data type

Specify the accumulator data type. See “Fixed-Point Data Types” on page 2-1596 for illustrations depicting the use of the accumulator data type in this block. You can set this parameter to:

- A rule that inherits a data type, for example, `Inherit: Inherit via internal rule`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

# Two-Channel Synthesis Subband Filter

---

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Accumulator data type** parameter.

See “Specify Data Types Using Data Type Assistant” in *Simulink User’s Guide* for more information.

## Output data type

Specify the output data type. See “Fixed-Point Data Types” on page 2-1596 for illustrations depicting the use of the output data type in this block. You can set it to:

- A rule that inherits a data type, for example, `Inherit: Same as accumulator`
- An expression that evaluates to a valid data type, for example, `fixdt(1,16,0)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

## Minimum

Specify the minimum value that the block should output. The default value is [ ] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)
- Automatic scaling of fixed-point data types

## Maximum

Specify the maximum value that the block should output. The default value is [ ] (unspecified). Simulink software uses this value to perform:

- Simulation range checking (see “Signal Ranges”)

# Two-Channel Synthesis Subband Filter

---

- Automatic scaling of fixed-point data types

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## References

Fliege, N. J. *Multirate Digital Signal Processing: Multirate Systems, Filter Banks, Wavelets*. West Sussex, England: John Wiley & Sons, 1994.

Strang, G. and T. Nguyen. *Wavelets and Filter Banks*. Wellesley, MA: Wellesley-Cambridge Press, 1996.

Vaidyanathan, P. P. *Multirate Systems and Filter Banks*. Englewood Cliffs, NJ: Prentice Hall, 1993.

## Supported Data Types

- Double-precision floating point
- Single-precision floating point
- Fixed point (signed only)
- 8-, 16-, and 32-bit signed integers

## See Also

DWT	DSP System Toolbox
Dyadic Synthesis Filter Bank	DSP System Toolbox
FIR Interpolation	DSP System Toolbox
IDWT	DSP System Toolbox
Two-Channel Analysis Subband Filter	DSP System Toolbox
<code>fir1</code>	Signal Processing Toolbox
<code>fir2</code>	Signal Processing Toolbox
<code>firls</code>	Signal Processing Toolbox
<code>wfilters</code>	Wavelet Toolbox

# Two-Channel Synthesis Subband Filter


---

For related information, see “Multirate and Multistage Filters”.

**Purpose** Receive uint8 vector as UDP message

**Library** Sources  
dspsrcs4


## Description



The UDP Receive block receives UDP packets from an IP network port and saves them to its buffer. With each sample, the block output, emits the contents of a single UDP packet as a data vector.

The generated code for this block relies on prebuilt .dll files. You can run this code outside the MATLAB environment, or redeploy it, but be sure to account for these extra .dll files when doing so. The packNGo function creates a single zip file containing all of the pieces required to run or rebuild this code. See packNGo for more information.

# UDP Receive



## Dialog

### Local IP port

Specify the IP port number upon to receive UDP packets. This value defaults to 25000. The value can range 1–65535.

---

**Note** On Linux, to set the IP port number below 1024, run MATLAB with root privileges. For example, at the Linux command line, enter:

```
sudo matlab
```

---

### **Remote IP address ('0.0.0.0' to accept all)**

Specify the IP address from which to accept packets. Entering a specific IP address blocks UDP packets from other addresses. To accept packets from any IP address, enter '0.0.0.0'. This value defaults to '0.0.0.0'.

### **Receive buffer size (bytes)**

Make the receive buffer large enough to avoid data loss caused by buffer overflows. This value defaults to 8192.

### **Maximum length for Message**

Specify the maximum length, in vector elements, of the data output vector. Set this parameter to a value equal or greater than the data size of a UDP packet. The system truncates data that exceeds this length. This value defaults to 255.

If you disable **Output variable-size signal**, the block outputs a fixed-length output the same length as the **Maximum length for Message**.

### **Data type for Message**

Set the data type of the vector elements in the Message output. Match the data type with the data input used to create the UDP packets. This option defaults to `uint8`.

### **Output variable-size signal**

If your model supports signals of varying length, enable the **Output variable-size signal** parameter. This checkbox defaults to selected (enabled). In that case:

# UDP Receive

---

- The output vector varies in length, depending on the amount of data in the UDP packet.
- The block emits the data vector from a single unlabeled output.

If your model does not support signals of varying length, disable the **Output variable-size signal** parameter. In that case:

- The block emits a fixed-length output the same length as the **Maximum length for Message**.
- If the UDP packet contains less data than the fixed-length output, the difference contains invalid data.
- The block emits the data vector from the **Message** output.
- The block emits the length of the valid data from the **Length** output.
- The block dialog box displays the **Data type for Length** parameter.

In both cases, the block truncates data that exceeds the **Maximum length for Message**.

## Data type for Length

Set the data type of the Length output. This option defaults to double.

## Blocking time (seconds)

For each sample, wait this length of time for a UDP packet before returning control to the scheduler. This value defaults to `inf`, which indicates to wait indefinitely.

---

**Note** This parameter appears only in the Embedded Coder<sup>®</sup> UDP Receive block.

---

## Sample time (seconds)

Specify how often the scheduler runs this block. Enter a value greater than zero. In real-time operation, setting this option to a

large value reduces the likelihood of dropped UDP messages. This value defaults to a sample time of 0.01 s.

**See Also**


Byte Pack, Byte Reversal, Byte Unpack, UDP Send

# UDP Send

---

**Purpose** Send UDP message

**Library** Sinks  
dspsnks4




## Description

The UDP Send block transmits an input vector as a UDP message over an IP network port.

The generated code for this block relies on prebuilt .dll files. You can run this code outside the MATLAB environment, or redeploy it, but be sure to account for these extra .dll files when doing so. The packNGo function creates a single zip file containing all of the pieces required to run or rebuild this code. See packNGo for more information.

## Dialog Box



### IP address ('255.255.255.255' for broadcast)

Specify the IP address or hostname to which the block sends the message. To broadcast the UDP message, retain the default value, '255.255.255.255'.

### Remote IP port

Specify the port to which the block sends the message. The value defaults to 25000, but the values range from 1–65535.

---

**Note** On Linux, to set the IP port number below 1024, run MATLAB with root privileges. For example, at the Linux command line, enter:

```
sudo matlab
```

---

# UDP Send

---

## **Local IP port source**

To let the system automatically assign the port number, select **Assign automatically**. To specify the IP port number using the **Local IP port** parameter, select **Specify**.

## **Local IP port**

Specify the IP port number from which the block sends the message.

If the receiving address expects messages from a particular port number, enter that number here.


## **See Also**

Byte PackByte Reversal, Byte Unpack, UDP Receive


**Purpose** Unbuffer input frame into sequence of scalar outputs

**Library** Signal Management / Buffers  
dspbuff3

## Description




The Unbuffer block unbuffers an  $M_1$ -by- $N$  input into a 1-by- $N$  output. That is, inputs are unbuffered *row-wise* so that each matrix row becomes an independent time-sample in the output. The rate at which the block receives inputs is generally less than the rate at which the block produces outputs.



The block adjusts the output rate so that the *sample period* is the same at both the input and output,  $T_{so} = T_{si}$ . Therefore, the output sample period for an input of frame size  $M_1$  and frame period  $T_{fi}$  is  $T_{fi}/M_1$ , which represents a *rate*  $M_1$  times higher than the input frame rate. In the example above, the block receives inputs only once every three sample periods, but produces an output once every sample period. To rebuffer inputs to a larger or smaller frame size, use the Buffer block.

In the model below, the block unbuffers a four-channel input with a frame size of three. The **Initial conditions** parameter is set to zero and the tasking mode is set to multitasking, so the first three outputs are zero vectors.

# Unbuffer



## Zero Latency

The Unbuffer block has *zero-tasking latency* in Simulink single-tasking mode. Zero-tasking latency means that the first input sample (received at  $t=0$ ) appears as the first output sample.

## Nonzero Latency

For *multitasking* operation, the Unbuffer block's buffer is initialized with the value specified by the **Initial conditions** parameter, and the block begins unbuffering this frame at the start of the simulation. Inputs to the block are therefore delayed by one buffer length, or  $M_i$  samples.


The **Initial conditions** parameter can be one of the following:

- A scalar to be repeated for the first  $M_i$  output samples of every channel
- A length- $M_i$  vector containing the values of the first  $M_i$  output samples for every channel
- An  $M_i$ -by- $N$  matrix containing the values of the first  $M_i$  output samples in each of  $N$  channels

---

**Note** For more information on latency and the Simulink tasking modes, see “Excess Algorithmic Delay (Tasking Latency)” and “Scheduling” in the *Simulink Coder User’s Guide*.

---



## Dialog Box

### Initial conditions

The value of the block’s initial output for cases of nonzero latency. You can specify a scalar, vector, or matrix.

# Unbuffer

## Sample-based processing

Specify how the block processes sample-based inputs. You can select one of the following options:

- Same as frame based — When you select this option, the block performs frame-based processing on sample-based inputs. The block unbuffers  $M_i$ -by- $N$  matrix inputs into a 1-by- $N$  output. Each row of the input matrix becomes an independent time-sample in the output.
- Pass through (this choice will be removed see release notes) — When you select this option and the input to the block is sample based, the block does not unbuffer the input. The output of the block is the same as the input.

---

**Note** This parameter will be removed in a future release.

---

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

## See Also

Buffer

DSP System Toolbox

See “Unbuffer Frame-Based Signals into Sample-Based Signals” for related information.


# Uniform Decoder

---

**Purpose** Decode integer input into floating-point output

**Library** Quantizers  
dspquant2

## Description



The Uniform Decoder block performs the inverse operation of the Uniform Encoder block, and reconstructs quantized floating-point values from encoded integer input. The block adheres to the definition for uniform decoding specified in ITU-T Recommendation G.701.

Inputs can be real or complex values of the following six integer data types: `uint8`, `uint16`, `uint32`, `int8`, `int16`, or `int32`.

The block first casts the integer input values to floating-point values, and then uniquely maps (decodes) them to one of  $2^B$  uniformly spaced floating-point values in the range  $[-V, (1-2^{1-B})V]$ , where you specify  $B$  in the **Bits** parameter (as an integer between 2 and 32) and  $V$  is a floating-point value specified by the **Peak** parameter. The smallest input value representable by  $B$  bits (0 for an unsigned input data type;  $-2^{B-1}$  for a signed input data type) is mapped to the value  $-V$ . The largest input value representable by  $B$  bits ( $2^{B-1}$  for an unsigned input data type;  $2^{B-1}-1$  for a signed input data type) is mapped to the value  $(1-2^{1-B})V$ . Intermediate input values are linearly mapped to the intermediate values in the range  $[-V, (1-2^{1-B})V]$ .

To correctly decode values encoded by the Uniform Encoder block, the **Bits** and **Peak** parameters of the Uniform Decoder block should be set to the same values as the **Bits** and **Peak** parameters of the Uniform Encoder block. The **Overflow mode** parameter specifies the Uniform Decoder block's behavior when the integer input is outside the range representable by  $B$  bits. When you select **Saturate**, *unsigned* input values greater than  $2^{B-1}$  saturate at  $2^{B-1}$ ; *signed* input values greater than  $2^{B-1}-1$  or less than  $-2^{B-1}$  saturate at those limits. The real and imaginary components of complex inputs saturate independently.

When you select **Wrap**, *unsigned* input values,  $u$ , greater than  $2^{B-1}$  are wrapped back into the range  $[0, 2^{B-1}]$  using  $\text{mod-}2^B$  arithmetic.

$$u = \text{mod}(u, 2^B)$$

*Signed* input values,  $u$ , greater than  $2^{B-1}-1$  or less than  $-2^{B-1}$  are wrapped back into that range using mod- $2^B$  arithmetic.

$$u = (\text{mod}(u+2^B/2, 2^B) - (2^B/2))$$

The real and imaginary components of complex inputs wrap independently.

The **Output type** parameter specifies whether the decoded floating-point output is single or double precision. Either level of output precision can be used with any of the six integer input data types.

## Examples

See example model `ex_uniform_decoder`.

In this example, the input to the block is the `uint8` output of a Uniform Encoder block. This block has comparable settings: **Peak** = 2, **Bits** = 3, and **Output type** = `Unsigned`. (Comparable settings ensure that inputs to the Uniform Decoder block do not saturate or wrap. See the example on the Uniform Encoder block reference page for more about these settings.)


The real and complex components of each input are independently mapped to one of  $2^3$  distinct levels in the range  $[-2.0, 1.5]$ .

0	is mapped to	-2.0
1	is mapped to	-1.5
2	is mapped to	-1.0
3	is mapped to	-0.5
4	is mapped to	0.0
5	is mapped to	0.5
6	is mapped to	1.0
7	is mapped to	1.5

# Uniform Decoder

---

## Dialog Box



### Peak

Specify the largest amplitude represented in the encoded input. To correctly decode values encoded with the Uniform Encoder block, set the **Peak** parameters in both blocks to the same value.

### Bits

Specify the number of input bits,  $B$ , used to encode the data. (This can be less than the total number of bits supplied by the input data type.) To correctly decode values encoded with the Uniform Encoder block, set the **Bits** parameters in both blocks to the same value.

### Overflow mode

Specify the block's behavior when the integer input is outside the range representable by  $B$  bits. Out-of-range inputs can either saturate at the extreme value, or wrap back into range.

### Output type

Specify the precision of the floating-point output, **single** or **double**.

## References

*General Aspects of Digital Transmission Systems: Vocabulary of Digital Transmission and Multiplexing, and Pulse Code Modulation (PCM) Terms*, International Telecommunication Union, ITU-T Recommendation G.701, March, 1993

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

## See Also

Data Type Conversion	Simulink
Quantizer	Simulink
Scalar Quantizer Decoder	DSP System Toolbox
Uniform Encoder	DSP System Toolbox
udecode	Signal Processing Toolbox
uencode	Signal Processing Toolbox


# Uniform Encoder

---

**Purpose** Quantize and encode floating-point input into integer output

**Library** Quantizers  
dspquant2

## Description



The Uniform Encoder block performs the following two operations on each floating-point sample in the input vector or matrix:

- 1 Quantizes the value using the same precision
- 2 Encodes the quantized floating-point value to an integer value

In the first step, the block quantizes an input value to one of  $2^B$  uniformly spaced levels in the range  $[-V, (1-2^{1-B})V]$ , where you specify  $B$  in the **Bits** parameter and you specify  $V$  in the **Peak** parameter. The quantization process rounds both positive and negative inputs *downward* to the nearest quantization level, with the exception of those that fall exactly on a quantization boundary. The real and imaginary components of complex inputs are quantized independently.

The number of bits,  $B$ , can be any integer value between 2 and 32, inclusive. Inputs greater than  $(1-2^{1-B})V$  or less than  $-V$  saturate at those respective values. The real and imaginary components of complex inputs saturate independently.

In the second step, the quantized floating-point value is uniquely mapped (encoded) to one of  $2^B$  integer values. When the **Output type** is set to **Unsigned integer**, the smallest quantized floating-point value,  $-V$ , is mapped to the integer 0, and the largest quantized floating-point value,  $(1-2^{1-B})V$ , is mapped to the integer  $2^B-1$ . Intermediate quantized floating-point values are linearly (uniformly) mapped to the intermediate integers in the range  $[0, 2^B-1]$ . For efficiency, the block automatically selects an *unsigned* output data type (uint8, uint16, or uint32) with the minimum number of bits equal to or greater than  $B$ .

When the **Output type** is set to **Signed integer**, the smallest quantized floating-point value,  $-V$ , is mapped to the integer  $-2^{B-1}$ , and the largest quantized floating-point value,  $(1-2^{1-B})V$ , is mapped to the

integer  $2^{B-1}-1$ . Intermediate quantized floating-point values are linearly mapped to the intermediate integers in the range  $[-2^{B-1}, 2^{B-1}-1]$ . The block automatically selects a *signed* output data type (`int8`, `int16`, or `int32`) with the minimum number of bits equal to or greater than  $B$ .

Inputs can be real or complex, double or single precision. The output data types that the block uses are shown in the table below. Note that most of the DSP System Toolbox blocks accept only double-precision inputs. Use the Simulink Data Type Conversion block to convert integer data types to double precision. See “Data Types” in the Simulink documentation for a complete discussion of data types, as well as a list of Simulink blocks capable of reduced-precision operations.

Bits	Unsigned Integer	Signed Integer
2 to 8	<code>uint8</code>	<code>int8</code>
9 to 16	<code>uint16</code>	<code>int16</code>
17 to 32	<code>uint32</code>	<code>int32</code>

The Uniform Encoder block operations adhere to the definition for uniform encoding specified in ITU-T Recommendation G.701.

## Examples


See example model `ex_uniform_encoder`.

In this example, the following parameters are set:

- **Peak** = 2
- **Bits** = 3
- **Output type** = Unsigned

The following figure illustrates uniform encoding.

# Uniform Encoder



The real and complex components of each input (horizontal axis) are independently quantized to one of  $2^3$  distinct levels in the range  $[-2, 1.5]$ . These components are then mapped to one of  $2^3$  integer values in the range  $[0, 7]$ .


-2.0 is mapped to 0  
 -1.5 is mapped to 1  
 -1.0 is mapped to 2  
 -0.5 is mapped to 3  
 0.0 is mapped to 4  
 0.5 is mapped to 5  
 1.0 is mapped to 6  
 1.5 is mapped to 7

This table shows the results for a few particular inputs.

Input	Quantized Input	Output	Notes
1.6	1.5+0.0i	7+4i	
-0.4	-0.5+0.0i	3+4i	
-3.2	-2.0+0.0i	4i	Saturation (real)

Input	Quantized Input	Output	Notes
0.4-1.2i	0.0-1.5i	4+i	
0.4-6.0i	0.0-2.0i	4	Saturation (imaginary)
-4.2+3.5i	-2.0+2.0i	7i	Saturation (real and imaginary)

The output data type is automatically set to `uint8`, the most efficient format for this input range.



## Dialog Box

### Peak

The largest input amplitude to be encoded,  $V$ . Real or imaginary input values greater than  $(1-2^{1-B})V$  or less than  $-V$  saturate (independently for complex inputs) at those limits.

# Uniform Encoder

---

## Bits

Specify the number of bits,  $B$ , needed to represent the integer output. The number of levels at which the block quantizes the floating-point input is  $2^B$ .

## Output type

The data type of the block's output, `Unsigned integer` or `Signed integer`. Unsigned outputs are `uint8`, `uint16`, or `uint32`, while signed outputs are `int8`, `int16`, or `int32`.

## References

*General Aspects of Digital Transmission Systems: Vocabulary of Digital Transmission and Multiplexing, and Pulse Code Modulation (PCM) Terms*, International Telecommunication Union, ITU-T Recommendation G.701, March, 1993

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Output	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit integers</li></ul>


## See Also

Data Type Conversion	Simulink
Quantizer	Simulink
Scalar Quantizer Decoder	DSP System Toolbox
Uniform Decoder	DSP System Toolbox
<code>udecode</code>	Signal Processing Toolbox
<code>uencode</code>	Signal Processing Toolbox

**Purpose** Unwrap signal phase

**Library** Signal Operations  
dspops

## Description



The Unwrap block unwraps each channel of the input by adding or subtracting appropriate multiples of  $2\pi$  to each channel element. The input can be a vector or matrix, and must have radian phase entries. The block recognizes phase discontinuities larger than the **Tolerance** parameter setting. For more information about phase unwrapping, see the “Definition of Phase Unwrap” on page 2-1633.

The block preserves the input size and dimension, and the output port rate equals the input port rate.

## Unwrap Method

The Unwrap block unwraps each channel of its input matrix or input vector by adding  $2\pi k$  to each successive channel element, and updating  $k$  at each *phase jump*. A phase jump occurs when the difference between two adjacent phase value entries exceeds the value of the **Tolerance** parameter.

The following code illustrates how the block unwraps the data in a given input channel  $u$ .

```
k=0;    % initialize k to 0
i=1;    % initialize the counter to 1
alpha=pi; % set alpha to the desired Tolerance. In this case, pi

for i = 1:(size(u)-1)
    yout(i,:)=u(i)+(2*pi*k); % add 2*pi*k to ui
    if((abs(u(i+1)-u(i)))>(abs(alpha))) %if diff is greater than alpha
        if u(i+1)<u(i) % if the phase jump is negative, increment k
            k=k+1;
        else % if the phase jump is positive, decrement k
            k=k-1;
        end
    end
end
```

# Unwrap

---

```
        end
    end
end
yout((i+1),:)=u(i+1)+(2*pi*k); % add 2*pi*k to the last element of the in
```

## Frame-Based Processing


When you configure the block to perform frame-based processing, the block supports two different unwrap modes. In both modes, the block adds  $2\pi k$  to each input channel's elements, and updates  $k$  at each phase discontinuity. The difference between the two modes is how often the block resets the initial phase value ( $k$ ) to zero. You can choose to unwrap data across frame boundaries (default), or to unwrap only within input frames, by resetting the initial phase value each time a new input frame is received.

### Unwrapping Across Frame Boundaries

In the default mode, the block ignores boundaries between input frames, and continues to unwrap the data in each channel without resetting the initial phase value to zero. To specify this mode, clear the **Do not unwrap phase discontinuities between successive frames** check box. The following figure illustrates how the block unwraps data in this mode.

### Default Frame-Based Unwrap Mode

Do not unwrap phase discontinuities between successive frames




### Unwrapping Within Frames

When you select the **Do not unwrap phase discontinuities between successive frames** check box, the block treats each frame of input data independently. In this mode, the block resets the initial phase value to zero each time a new input frame is received. The following figure illustrates how the block unwraps data in this mode.

# Unwrap

## Nondefault Frame-Based Unwrap Mode


Do not unwrap phase discontinuities between successive frames



## Sample-Based Processing

When you configure the block to perform sample-based processing, the block treats each element of the input as an individual channel. The block unwraps the data in each channel of the input, and does not reset the initial phase to zero each time a new input is received. The following figure illustrates how the block unwraps data when performing sample-based processing.

### Sample-Based Unwrap Mode




### Definition of Phase Unwrap

Algorithms that compute the phase of a signal often only output phases between  $-\pi$  and  $\pi$ . For instance, such algorithms compute the phase of  $\sin(2\pi + 3)$  to be 3, since  $\sin(3) = \sin(2\pi + 3)$ , and since the actual phase,  $2\pi + 3$ , is not between  $-\pi$  and  $\pi$ . Such algorithms compute the phases of  $\sin(-4\pi + 3)$  and  $\sin(16\pi + 3)$  to be 3 as well.


Phase unwrap or unwrap is a process often used to reconstruct a signal's original phase. Unwrap algorithms add appropriate multiples of  $2\pi$  to each phase input to restore original phase values, as illustrated in the following diagram. See "Unwrap Method" on page 2-1629 for more information on the unwrap algorithm used by this block.

The following figure illustrates the concept of phase unwrapping.

# Unwrap



## Dialog Box



### Tolerance

The jump size that the block recognizes as a true phase discontinuity. The default is set to  $\pi$  (rather than a smaller value) to avoid altering legitimate signal features. To increase the block's sensitivity, set the **Tolerance** to a value slightly less than  $\pi$ .

### Input processing

Specify how the block should process the input. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The Inherited (this choice will be removed - see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## **Do not unwrap phase discontinuities between successive frames**

When you clear this check box, the block ignores boundaries between input frames and does not reset the initial phase value to zero each time a new input is received. In this mode, the block continuously unwraps the data in each column of the input. When you select this check box, the block treats each frame of input data independently, and resets the initial phase value for each new input frame. See the “Frame-Based Processing” on page 2-1630 section for more information.

This parameter is available only when you configure the block to perform frame-based processing. In sample-based processing mode, the block does not reset the initial phase value to zero for each new input. See “Sample-Based Processing” on page 2-1632 for more information.

## **Supported Data Types**

- Double-precision floating point
- Single-precision floating point

## **See Also**

unwrap                      MATLAB

**Purpose** Resample input at higher rate by inserting zeros

**Library** Signal Operations  
dspops

## Description



The Upsample block resamples each channel of the  $M_i$ -by- $N$  input at a rate  $L$  times higher than the input sample rate by inserting  $L-1$  zeros between consecutive samples. You specify the integer  $L$  in the **Upsample factor** parameter. The **Sample offset** parameter,  $D$ , allows you to delay the output samples by an integer number of sample periods. Doing so enables you to select any of the  $L$  possible output phases. The value you specify for the **Sample offset** parameter must be in the range  $0 \leq D < (L-1)$ .

You can use this block inside of triggered subsystems when you set the **Rate options** parameter to Enforce single-rate processing.

### Frame-Based Processing

When you set the **Input processing** parameter to Columns as channels (frame based), the block upsamples each column of the input over time. In this mode, the block can perform either single-rate or multirate processing. You can use the **Rate options** parameter to specify how the block upsamples the input:

- When you set the **Rate options** parameter to Enforce single-rate processing, the input and output of the block have the same sample rate. In this mode, the block outputs a signal with a proportionally larger frame *size* than the input. For upsampling by a factor of  $L$ , the output frame size is  $L$  times larger than the input frame size ( $M_o = M_i * L$ ), but the input and output frame rates are equal.

For an example of single-rate upsampling, see Example: Single-Rate Processing on page 2-1639.

- When you set the **Rate options** parameter to Allow multirate processing, the block treats an  $M_i$ -by- $N$  matrix input as  $N$  independent channels. The block upsamples each column of the input

over time by keeping the frame size constant ( $M_i=M_o$ ), and making the output frame period ( $T_{fo}$ )  $L$  times shorter than the input frame period ( $T_{fo} = T_{fi}/L$ ).

See Example: Multirate, Frame-Based Processing on page 2-1639 for an example that uses the Upsample block in this mode.

## Sample-Based Processing

When you set the **Input processing** parameter to `Elements as channels` (sample based), the block treats an  $M$ -by- $N$  matrix input as  $M*N$  independent channels, and upsamples each channel over time. In this mode, the block always performs multirate processing. The output sample rate is  $L$  times higher than the input sample rate ( $T_{so} = T_{si}/L$ ), and the input and output sizes are identical.

## Zero Latency

The Upsample block has *zero-tasking latency* for all single-rate operations. The block is in a single-rate mode if you set the **Upsample factor** parameter to 1 or if you set the **Input processing** parameter to `Columns as channels` (frame based) and the **Rate options** parameter to `Enforce single-rate processing`.

The Upsample block also has zero-tasking latency for multirate operations if you run your model in Simulink single-tasking mode.

Zero-tasking latency means that the block propagates the first input (received at  $t=0$ ) immediately following the  $D$  consecutive zeros specified by the **Sample offset** parameter. This output ( $D+1$ ) is followed in turn by the  $L-1$  inserted zeros and the next input sample.

## Nonzero Latency

The Upsample block has tasking latency for multirate, multitasking operation:

- In multirate, sample-based processing mode, the initial condition for each channel appears as output sample  $D+1$ , and is followed by  $L-1$  inserted zeros. The channel's first input appears as output sample  $D+L+1$ . The **Initial conditions** parameter can be an  $M_i$ -by- $N$  matrix

containing one value for each channel, or a scalar to be applied to all signal channels.

- In multirate, frame-based processing mode, the first row of the initial condition matrix appears as output sample  $D+1$ , and is followed by  $L-1$  inserted rows of zeros, the second row of the initial condition matrix, and so on. The first row of the first input matrix appears in the output as sample  $M_1L+D+1$ . The **Initial conditions** parameter can be an  $M_1$ -by- $N$  matrix, or a scalar to be repeated across all elements of the input matrix.

---


**Note** For more information on latency and the Simulink tasking modes, see “Excess Algorithmic Delay (Tasking Latency)” and “Scheduling” in the *Simulink Coder User’s Guide*.

---

## Examples

### Example: Single-Rate Processing

In the `ex_upsample_ref2` model, the Upsample block resamples a single-channel input with a frame size of 16. The block upsamples the input by a factor of 4. Thus, the output of the block has a frame size of 64. Because the block is in single-rate processing mode, the input and output frame rates are identical.





### Example: Multirate, Frame-Based Processing

In the `ex_upsample_ref1` model, the Upsample block resamples a single-channel input with a frame period of 1 second. The block

# Upsample

upsamples the input by a factor of 4. Thus, the output of the block has a frame period of 0.25 seconds. Because the block is in multirate processing mode, the input and output frame sizes are identical.



## Dialog Box

### Upsample factor

The integer factor,  $L$ , by which to increase the input sample rate.

## Sample offset

The sample offset,  $D$ , which must be an integer in the range  $[0, L-1]$ .

## Input processing

Specify how the block should process the input. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel. In this mode, the block can perform single-rate or multirate processing.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel. In this mode, the block always performs multirate processing.

---

**Note** The option **Inherit from input** (this choice will be removed - see release notes) will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Rate options

Specify the method by which the block upsamples the input. You can select one of the following options:

- **Enforce single-rate processing** — When you select this option, the block maintains the input sample rate by increasing the output frame size by a factor of  $L$ . To select this option, you must set the **Input processing** parameter to **Columns as channels (frame based)**.
- **Allow multirate processing** — When you select this option, the block resamples the signal such that the output sample rate is  $L$  times faster than the input sample rate.

# Upsample

---

## Initial conditions

The value with which the block is initialized for cases of nonzero latency, a scalar or matrix. This value appears in the output as sample  $D+1$ . This parameter appears only when you configure the block to perform multirate processing.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

## See Also

Downsample	DSP System Toolbox
FIR Interpolation	DSP System Toolbox
FIR Rate Conversion	DSP System Toolbox
Repeat	DSP System Toolbox

## Purpose


Delay input by time-varying fractional number of sample periods

## Library

Signal Operations

dspsigops

## Description



The Variable Fractional Delay block delays each element of the discrete-time N-D input array,  $u$ , by a variable number of sample intervals. The input delay values can be integer or noninteger values. The block provides three different interpolation modes: Linear, FIR, and Farrow.

The block computes the value for each channel of the output based on the stored samples in memory most closely indexed by the Delay input,  $v$ , and the interpolation method specified by the **Interpolation mode** parameter.

- In **Linear** interpolation mode, the block stores the  $D_{max}+1$  most recent samples received at the In port for each channel, where  $D_{max}$  is the value you specify for the **Maximum delay (Dmax) in samples** parameter.
- In **FIR** interpolation mode, the block stores the  $D_{max}+P+1$  most recent samples received at the In port for each channel, where  $P$  is the value you specify for the **Interpolation filter half-length (P)** parameter.
- In **Farrow** interpolation mode, the block stores the  $D_{max} + \frac{N}{2} + 1$  most recent samples received at the In port for each channel, where  $N$  is the value you specify for the **Farrow filter length (N)** parameter.

The Variable Fractional Delay block assumes that the input values at the Delay port are between  $D_{min}$  and  $D_{max}$ , where  $D_{min}$  appears in the **Valid delay range** section on the **Main** pane of the block mask, and  $D_{max}$  is the value of the **Maximum delay (Dmax) in samples** parameter. The block clips delay values less than  $D_{min}$  to  $D_{min}$  and delay values greater than  $D_{max}$  to  $D_{max}$ .

# Variable Fractional Delay

---

You must consider additional factors when selecting valid Delay values for the FIR and Farrow interpolation modes. For more information about these considerations, refer to FIR Interpolation Mode on page 1646 or Farrow Interpolation Mode on page 1648, respectively.

The Variable Fractional Delay block is similar to the Variable Integer Delay block, in that they both store a minimum of  $D_{max}+1$  past samples in memory. The Variable Fractional Delay block differs only in the way that these stored samples are accessed; a fractional delay requires the computation of a value by interpolation from the nearby samples in memory.

## Sample-Based Processing

When you set the **Input processing** parameter to `Elements as channels (sample based)`, the block treats each element of the N-D input array,  $u$ , as an independent channel. The input to the Delay port,  $v$ , must either be an N-D array of the same size and dimension as the input  $u$ , or be a scalar value, such that  $D_{min} \leq v \leq D_{max}$ .

For example, consider an  $M$ -by- $N$  input matrix. The block treats each of the  $M*N$  matrix elements as independent channels. The input to the Delay port can be an  $M$ -by- $N$  matrix of floating-point values in the range  $D_{min} \leq v \leq D_{max}$  that specifies the number of sample intervals to delay each channel of the input, or it can be a scalar floating-point value,  $D_{min} \leq v \leq D_{max}$ , by which to equally delay all channels.

In sample-based processing mode, the block treats an unoriented vector input as an  $M$ -by-1 matrix. In this mode, the output is also an unoriented vector.

The **Initial conditions** parameter specifies the values in the block's memory at the start of the simulation in the same manner as the Variable Integer Delay block. See the Variable Integer Delay block reference page for more information.

## Frame-Based Processing

When you set the **Input processing** parameter to `Columns as channels (frame based)`, the block treats each of the  $N$  input columns as an independent channel containing  $M_i$  sequential time samples.

The input to the Delay port,  $v$ , contains floating-point values that specify the number of sample intervals to delay the current input.

The input to the Delay port can be a scalar value to uniformly delay every sample in every channel. It can also be a length- $M$  column vector, containing one delay for each sample in the input frame. The block applies the set of delays contained in the vector identically to every channel of a multichannel input. The Delay port entry can also be a length- $N$  row vector, containing one delay for each channel. Finally, the Delay port entry can be an  $M$ -by- $N$  matrix, containing a different delay for each corresponding element of the input.

For example, if  $v$  is the  $M_i$ -by-1 matrix  $[v(1) \ v(2) \ \dots \ v(M_i)]'$ , the earliest sample in the current frame is delayed by  $v(1)$  fractional sample intervals, the following sample in the frame is delayed by  $v(2)$  fractional sample intervals, and so on. The block applies the set of fractional delays contained in  $v$  identically to every channel of a multichannel input.

The **Initial conditions** parameter specifies the values in the block's memory at the start of the simulation in the same manner as the Variable Integer Delay block. See the Variable Integer Delay block reference page for more information.

## Interpolation Modes

The delay value specified at the Delay port serves as an index into the block's memory,  $U$ , which stores, at a minimum, the  $D_{max}+1$  most recent samples received at the In port for each channel. For example, an integer delay of 5 on a scalar input sequence retrieves and outputs the fifth most recent input sample from the block's memory,  $U(5)$ . The block computes fractional delays by interpolating between stored samples; the three available interpolation modes are Linear, FIR and Farrow.

### Linear Interpolation Mode

For noninteger delays, at each sample time, the Linear Interpolation mode uses the two samples in memory nearest to the specified delay to compute a value for the sample at that time. If  $v$  is the specified fractional delay for a scalar input, the output sample,  $y$ , is computed as follows.

# Variable Fractional Delay

---

```
vi = floor(v)      % vi = integer delay
vf = v-vi         % vf = fractional delay
y = (1-vf)*U(vi+1) + vf*U(vi)
```

## FIR Interpolation Mode

In FIR Interpolation mode, the block provides a discrete set of fractional delays described by:

$$v + \frac{i}{L}, \quad v \geq P-1, \quad i = 0, 1, \dots, L-1$$

If  $v$  is less than  $P-1$ , the block's behavior depends on the setting of the **For small input delay values** parameter. You can specify the block's behavior when the input delay value is too small to center the kernel (less than  $P-1$ ), by setting the **For small input delay values** parameter:

- If you select **Clip to the minimum value necessary for centered kernel**, the block remains in FIR interpolation mode by clipping small input delay values to the smallest value necessary to center the kernel.

To determine the minimum delay value, select **Clip to the minimum value necessary for centered kernel**, and click **Apply** on the block mask. All input delay values less than the value displayed for  $D_{min}$  will be clipped to  $D_{min}$ .

- If you select **Switch to linear interpolation if kernel cannot be centered**, the block computes fractional delays using linear interpolation when the input delay value is less than  $P-1$ .

To add an extra delay to the minimum possible delay value, select the **Disable direct feedthrough by increasing minimum possible delay by one** check box. Checking this box prevents algebraic loops from occurring when you use the block inside a feedback loop.

In FIR Interpolation mode, the block implements a polyphase structure to compute a value for each sample at the desired delay. Each arm of the structure corresponds to a different delay value and the

output computed for each sample corresponds to the output of the arm with a delay value nearest to the desired input delay. Thus, only a discrete set of delays is actually possible. The number of coefficients in each of the  $L$  filter arms of the polyphase structure is  $2P$ . In most cases, using values of  $P$  between 4 and 6 will provide you with reasonably accurate interpolation values.

In this mode, the Signal Processing Toolbox `intfilt` function computes an FIR filter for interpolation.

For example, when you set the parameters on the block mask to the following values:

- Interpolation filter half-length (P): 4
- Interpolation points per input sample: 10
- Normalized input bandwidth: 1

The filter coefficients are given by:

```
b = intfilt(10,4,1);
```

The block then implements this filter as a polyphase structure, as described previously.

Increasing the **Interpolation filter half length (P)** increases the accuracy of the interpolation, but also increases the number of computations performed per input sample, as well as the amount of memory needed to store the filter coefficients. Increasing the **Interpolation points per input sample (L)** increases the number of representable discrete delay points, but also increases the simulation's memory requirements and does not affect the computational load per sample.

The **Normalized input bandwidth (0 to 1)** parameter allows you to take advantage of the bandlimited frequency content of the input. For example, if you know that the input signal does not have frequency content above  $F_s/4$ , you can specify a value of 0.5 for the **Normalized**

# Variable Fractional Delay

---

**input bandwidth (0 to 1)** to constrain the frequency content of the output to that range.

---

**Note** You can consider each of the  $L$  interpolation filters to correspond to one output phase of an “upsample-by- $L$ ” FIR filter. Thus, the **Normalized input bandwidth (0 to 1)** value improves the stopband in critical regions, and relaxes the stopband requirements in frequency regions where there is no signal energy.

---

## Farrow Interpolation Mode

In Farrow interpolation mode, the block uses the LaGrange method to interpolate values.

To increase the minimum possible delay value, select the **Disable direct feedthrough by increasing minimum possible delay by one** check box. Checking this box prevents algebraic loops from occurring when you use the block inside a feedback loop.

To specify the block’s behavior when the input delay value is too small

to center the kernel (less than  $\frac{N}{2} - 1$ ), set the **For small input delay values** parameter:

- If you select **Clip to the minimum value necessary for centered kernel**, the block clips small input delay values to the smallest value necessary to keep the kernel centered. This increases  $D_{min}$  but yields more accurate interpolation values.

To determine the minimum delay value, select **Clip to the minimum value necessary for centered kernel**, and click **Apply** on the block mask. All input delay values less than the value displayed for  $D_{min}$  will be clipped to  $D_{min}$ .

- If you select **Use off-centered kernel**, the block computes fractional delays using a Farrow filter with an off-centered kernel. This mode does not increase  $D_{min}$ , but if there are input delay values

less than  $\frac{N}{2} - 1$ , the results are less accurate than the results achieved by keeping the kernel centered.

## Fixed-Point Data Types

The diagrams in the following sections show the data types used within the Variable Fractional Delay block for fixed-point signals.

Although you can specify most of these data types on the **Data Types** pane of the block mask, the following data types are computed internally by the block and cannot be directly specified on the block mask.

Data Type	Word Length	Fraction Length
vf data type	Same word length as the <b>Coefficients</b>	Same as the word length
HoldInteger data type	Same word length as the input delay value	0 bits
Integer data type	32 bits	0 bits

---

**Note** When the block input is fixed point, all internal data types are signed fixed point.

---

To compute the integer ( $v_i$ ) and fractional ( $v_f$ ) parts of the input delay value ( $v$ ), the Variable Fractional Delay block uses the following equations:

# Variable Fractional Delay


$$D_{min} < v < D_{max} \Rightarrow \begin{cases} v_i = \text{floor}(v) \\ v_f = v - v_i \end{cases}$$

$$v \leq D_{min} \Rightarrow \begin{cases} v_i = D_{min} \\ v_f = 0 \end{cases}$$

$$v \geq D_{max} \Rightarrow \begin{cases} v_i = D_{max} \\ v_f = 0 \end{cases}$$


## Linear Interpolation Mode

The following diagram shows the fixed-point data types used by the Linear interpolation mode of the Variable Fractional Delay block.



## FIR Interpolation Mode

The following diagram illustrates how the Variable Fractional Delay block selects the arm of the polyphase filter structure that most closely matches the fractional delay value ( $v_f$ ).




See the “Fixed-Point Data Types” on page 2-633 section of the FIR Interpolation reference page for a diagram showing the fixed-point data types used by the Variable Fractional Delay block in FIR interpolation mode.

## Farrow Interpolation Mode

The following diagram shows the fixed-point data types used by the Farrow interpolation mode of the Variable Fractional Delay block where:


- **Farrow filter length (N) = 4**
- **For small input delay values = Clip** to the minimum value necessary to for centered kernel



# Variable Fractional Delay

The following diagram shows the fixed-point data types used by the Farrow interpolation mode of the Variable Fractional Delay block where:

- **Farrow filter length (N) = 4**
- **For small input delay values = Use off-centered kernel**




Diff is computed from the integer part of the delay value ( $v_i$ ) and the **Farrow filter length (N)** according to the following equation:

$$Diff = v_i - \left( \frac{N-1}{2} \right)$$

$$Diff \geq 0 \Rightarrow Diff = 0$$

$$Diff < 0 \Rightarrow Diff = -Diff$$

The following diagram shows the fixed-point data types used by the Digital Filter block's FIR direct form filter.



## Examples

The `dspaudioeffects` example illustrates three audio effects applied to a short segment of music. When you set the **Audio effect** of the Effect block to **Flanging**, the model uses the Variable Fractional Delay block to mix the original signal with a delayed version of itself.

To see the Flanging subsystem, right-click the Effect block, and select **Diagram > Mask > Look Under Mask**. Next, double-click the Flanging block in the Effect block subsystem that just opened. The

# Variable Fractional Delay


---

Flanging subsystem opens, and you can see the parameters of the Variable Fractional Delay block.

# Variable Fractional Delay

## Dialog Box

The **Main** pane of the Variable Fractional Delay block dialog appears as follows.



# Variable Fractional Delay

---

## **Interpolation mode**

The method by which to interpolate between adjacent stored samples to obtain a value for the sample indexed by the input at the Delay port.

## **Interpolation filter half-length (P)**

Half the number of input samples to use in the FIR interpolation filter. This parameter is only visible when the **Interpolation mode** is set to FIR.

## **Farrow filter length (N)**

The number of input samples to use in the Farrow interpolation filter. This parameter is only visible when the **Interpolation mode** is set to Farrow.

## **Interpolation points per input sample**

The number of points per input sample,  $L$ , at which a unique FIR interpolation filter is computed. This parameter is only visible when the **Interpolation mode** is set to FIR.

## **Normalized input bandwidth (0 to 1)**

The bandwidth to which the interpolated output samples should be constrained. The value must be a real scalar between 0 and 1. A value of 1 specifies half the sample frequency. This parameter is only visible when the **Interpolation mode** is set to FIR.

## **Maximum delay (Dmax) in samples**

The maximum delay that the block can produce,  $D_{max}$ . Input delay values exceeding this maximum are clipped to  $D_{max}$ .

## **Input processing**

Specify how the block should process the input. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The Inherited (this choice will be removed - see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Initial conditions

The values with which the block’s memory is initialized. See the Variable Integer Delay block for more information.

## Disable direct feedthrough by increasing minimum possible delay by one

Select this box to disable direct feedthrough by increasing the minimum possible delay value. When you set the **Input processing** parameter to Columns as channels (frame based), the block increases the minimum possible delay value by  $frame\ size - 1$ . Similarly, when you set the **Input processing** parameter to Elements as channels (sample based), the block increases the minimum possible delay value by one sample.

Checking this box allows you to use the Variable Fractional Delay block in feedback loops.

## For small input delay values

Specify the block’s behavior when the input delay values are too small to center the kernel. This parameter is only visible when the **Interpolation mode** is set to FIR or Farrow.

You can specify how the block handles input delay values that are too small for the kernel to be centered using one of the following choices:

- In both FIR and Farrow interpolation modes, you can select Clip to the minimum value necessary for centered kernel. This option forces the block to increase  $D_{min}$  to the smallest value necessary to keep the kernel centered.

# Variable Fractional Delay

---

- In FIR interpolation mode, you can select `Switch to linear interpolation` if `kernel` cannot be centered. This option forces the block to preserve the value of  $D_{min}$  and compute all interpolated values using `Linear interpolation`.
- In Farrow interpolation mode, you can select `Use off-centered kernel`. This option forces the block to preserve the value of  $D_{min}$  and compute the interpolated values using a farrow filter with an off-centered kernel.


## Valid delay range

The values displayed in this section of the **Main** pane are calculated (in samples) by the block based on the current parameter settings.

- `Dmin` is the smallest possible valid delay value (in samples) based on the current settings of the block parameters. The block clips all input delay values less than `Dmin` to `Dmin`.
- `Dmax` is the maximum valid delay value (in samples) based on the current settings of the block parameters. The block clips all input delay values greater than `Dmax` to `Dmax`.

The **Data Types** pane of the Variable Fractional Delay block dialog appears as follows.

# Variable Fractional Delay



# Variable Fractional Delay

---

## **Rounding mode**

Select the rounding mode for fixed-point operations.

## **Overflow mode**

Select the overflow mode for fixed-point operations.

## **Coefficients**

Choose how you specify the word length and fraction length of the filter coefficients.

- When you select **Same word length as input**, the word length of the filter coefficients match that of the input to the block. In this mode, the fraction length of the coefficients is automatically set to the binary-point only scaling that provides you with the best precision possible given the value and word length of the coefficients.
- When you select **Specify word length**, you can enter the word length of the coefficients, in bits. In this mode, the fraction length of the coefficients is automatically set to the binary-point only scaling that provides you with the best precision possible given the value and word length of the coefficients.

## **Product output**

Use this parameter to specify how you would like to designate the product output word and fraction lengths. See “Fixed-Point Data Types” on page 2-1649 and “Multiplication Data Types” for illustrations depicting the use of the product output data type in this block.

- When you select **Same as first input**, these characteristics match those of the first input to the block.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the product output, in bits.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the product output. This block requires power-of-two slope and a bias of zero.

## Accumulator

Use this parameter to specify how you would like to designate the accumulator word and fraction lengths. See “Fixed-Point Data Types” on page 2-1649 and “Multiplication Data Types” for illustrations depicting the use of the accumulator data type in this block:

- When you select **Same as product output**, these characteristics match those of the product output.
- When you select **Same as first input**, these characteristics match those of the first input to the block.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the accumulator, in bits.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the accumulator. This block requires power-of-two slope and a bias of zero.

## Product output polyval

Choose how you specify the word length and fraction length of the product output polyval data type. This parameter is only visible when the **Interpolation mode** is set to **Farrow**.

- When you select **Same as first input**, these characteristics match those of the first input to the block.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the product output polyval in bits.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the product output polyval. This block requires power-of-two slope and a bias of zero.

## Accumulator polyval

Choose how you specify the word length and fraction length of the accumulator polyval data type. This parameter is only visible when the **Interpolation mode** is set to **Farrow**.

# Variable Fractional Delay

---

- When you select `Same as first input`, these characteristics match those of the first input to the block.
- When you select `Binary point scaling`, you can enter the word length and the fraction length of the accumulator polyval in bits.
- When you select `Slope and bias scaling`, you can enter the word length, in bits, and the slope of the accumulator polyval. This block requires power-of-two slope and a bias of zero.

## Multiplicand polyval

Choose how you specify the word length and fraction length of the multiplicand polyval data type. This parameter is only visible when the **Interpolation mode** is set to `Farrow`.

- When you select `Same as first input`, these characteristics match those of the first input to the block.
- When you select `Binary point scaling`, you can enter the word length and the fraction length of the multiplicand polyval, in bits.
- When you select `Slope and bias scaling`, you can enter the word length, in bits, and the slope of the multiplicand polyval. This block requires power-of-two slope and a bias of zero.

## Output

Choose how you specify the output word length and fraction length:

- When you select `Same as accumulator`, these characteristics match those of the accumulator.
- When you select `Same as first input`, these characteristics match those of the first input to the block.
- When you select `Binary point scaling`, you can enter the word length and the fraction length of the output, in bits.

- When you select **Slope** and **bias scaling**, you can enter the word length, in bits, and the slope of the output. This block requires power-of-two slope and a bias of zero.

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Delay	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

# Variable Fractional Delay

---

## See Also

Delay

Unit Delay

Variable Integer Delay

DSP System Toolbox

Simulink

DSP System Toolbox

## Purpose


Delay input by time-varying integer number of sample periods

## Library

Signal Operations

dspsigops

## Description



The Variable Integer Delay block delays the discrete-time input at the In port by the integer number of sample intervals specified by the input to the Delay port. The sample rate of the input signal at the In port must be the same as the sample rate of the input signal at the Delay port. When these sample rates are not the same, you need to insert a Zero-Order Hold or Rate Transition block in order to make the sample rates identical. When you set the **Input processing** parameter to **Elements as channels (sample based)**, the delay for an N-D input can be a scalar value to uniformly delay every sample in every channel, or a matrix containing one delay value for each channel of the input. When you set the **Input processing** parameter to **Columns as channels (frame based)**, the delay can be a scalar value to uniformly delay every sample in every channel, a vector containing one delay value for each sample in the input frame, or a vector containing one delay value for each channel in the input frame.

The delay values should be in the range of 0 to  $D$ , where  $D$  is the **Maximum delay**. Delay values greater than  $D$  or less than 0 are clipped to those respective values and noninteger delays are rounded to the nearest integer value.

The Variable Integer Delay block differs from the Delay block in the following ways.

# Variable Integer Delay

<b>Variable Integer Delay Block</b>	<b>Delay Block</b>
The delay is provided as an input to the Delay port.	You specify the delay as a parameter setting in the dialog box.
Delay can vary with time; for example, when the block performs frame-based processing, the $n$ th element's delay in the first input frame can differ from the $n$ th element's delay in the second input frame.	Delay cannot vary with time; for example, when the block performs frame-based processing, the $n$ th element's delay is the same for every input frame.
When you use the Variable Integer Delay block in a feedback loop, you must check the <b>Disable direct feedthrough by increasing minimum possible delay by one</b> check box. This prevents the occurrence of an algebraic loop when the delay of the Variable Integer Delay block is driven to zero.	You can use the Delay block to break an algebraic loop.

## Sample-Based Processing

When you set the **Input processing** parameter to **Elements as channels (sample based)**, the Variable Integer Delay block supports N-D input arrays. When the input is an  $M$ -by- $N$ -by- $P$  array, the block treats each of the  $M*N*P$  elements as independent channels, and applies the delay at the Delay port to each channel.

The Variable Integer Delay block stores the  $D+1$  most recent samples received at the In port for each channel. At each sample time the block outputs the stored sample(s) indexed by the input to the Delay port.


# Variable Integer Delay

For example, when the input to the In port,  $u$ , is a scalar signal, the block stores a vector,  $U$ , of the  $D+1$  most recent signal samples. When the current input sample is  $U(1)$ , the previous input sample is  $U(2)$ , and so on, then the block's output is

```
y = U(v+1);    % Equivalent MATLAB code
```

where  $v$  is the input to the Delay port. A delay value of 0 ( $v=0$ ) causes the block to pass through the sample at the In port in the same simulation step that it is received. The block's memory is initialized to the **Initial conditions** value at the start of the simulation (see below).

The next figure shows the block output for a scalar ramp sequence at the In port, a **Maximum delay** of 5, an **Initial conditions** of 0, and a variety of different delays at the Delay port.



The current input at each time step is immediately stored in memory as  $U(1)$ . This allows the current input to be available at the output for a delay of 0 ( $v=0$ ).

# Variable Integer Delay


---

The **Initial conditions** parameter specifies the values in the block's memory at the start of the simulation. Unlike the Delay block, the Variable Integer Delay block does not have a fixed initial delay period during which the initial conditions appear at the output. Instead, the initial conditions are propagated to the output only when they are indexed in memory by the value at the Delay port. Both fixed and time-varying initial conditions can be specified in a variety of ways to suit the dimensions of the input sequence.

## Fixed Initial Conditions

The settings in this section specify fixed initial conditions. For a fixed initial condition, the block initializes each of  $D$  samples in memory to the value entered in the **Initial conditions** parameter. A fixed initial condition in sample-based mode can be specified in one of the following ways:

- Scalar value with which to initialize every sample of every channel in memory. For a general  $M$ -by- $N$  input and the parameter settings in this figure,



the block initializes 100  $M$ -by- $N$  matrices in memory with zeros.

- Array of size  $M$ -by- $N$ -by- $D$ . In this case, you can specify different fixed initial conditions for each channel. See the Array bullet in “Time-Varying Initial Conditions” on page 2-1668 below for details.

## Time-Varying Initial Conditions

The following settings specify time-varying initial conditions. For a time-varying initial condition, the block initializes each of  $D$  samples in memory to one of the values entered in the **Initial conditions** parameter. This allows you to specify a unique output value for each sample in memory. A time-varying initial condition in sample-based mode can be specified in one of the following ways:

- Vector containing  $D$  elements with which to initialize memory samples  $U(2:D+1)$ , where  $D$  is the **Maximum delay**. For a scalar input and the parameters in the next figure, the block initializes  $U(2:6)$  with values  $[-1, -1, -1, 0, 1]$ .

Maximum delay (samples):  
5

Initial conditions:  
[-1 -1 0 1]

- Array of dimension  $M$ -by- $N$ -by- $D$  with which to initialize memory samples  $U(2:D+1)$ , where  $D$  is the **Maximum delay** and  $M$  and  $N$  are the number of rows and columns, respectively, in the input matrix. For a 2-by-3 input and the following parameters, the block initializes memory locations  $U(2:5)$  with values

$$U(2) = \begin{bmatrix} 1 & 1 & 1 \\ 1 & 1 & 1 \end{bmatrix}, U(3) = \begin{bmatrix} 2 & 2 & 2 \\ 2 & 2 & 2 \end{bmatrix}, U(4) = \begin{bmatrix} 3 & 3 & 3 \\ 3 & 3 & 3 \end{bmatrix}, U(5) = \begin{bmatrix} 4 & 4 & 4 \\ 4 & 4 & 4 \end{bmatrix}$$

Maximum delay (samples):  
4

Initial conditions:  
cat(3, [1 1 1 1 1], [2 2 2 2 2], [3 3 3 3 3], [4 4 4 4 4])

An  $M$ -by- $N$ -by- $P$ -by- $D$  array can be entered for the **Initial Conditions** parameter when the input is an  $M$ -by- $N$ -by- $P$  array. The  $(M,N,P,T)$ th sample of the **Initial Conditions** matrix provides the initial condition value for the  $(M,N,P)$ th channel of the input matrix at delay =  $D-t+1$  samples.

## Frame-Based Processing

When you set the **Input processing** parameter to **Columns as channels (frame based)**, the input can be an  $M$ -by- $N$  matrix. The block treats each of the  $N$  input columns as independent channels containing  $M$  sequential time samples.

# Variable Integer Delay

---

In this mode, the input at the Delay port can be a scalar value to uniformly delay every sample in every channel. It can also be a length- $M$  column vector containing one delay value for each sample in the input frame(s). The set of delays contained in the vector is applied identically to every channel of a multichannel input. The Delay port entry can also be a length- $N$  row vector, containing one delay for each channel. Finally, the Delay port entry can be an  $M$ -by- $N$  matrix, containing a different delay for each corresponding element of the input.

Vector  $v$  does not specify when the samples in the current input frame will appear in the output. Rather,  $v$  indicates which previous input samples (stored in memory) should be included in the current output frame. The first sample in the current output frame is the input sample  $v(1)$  intervals earlier in the sequence, the second sample in the current output frame is the input sample  $v(2)$  intervals earlier in the sequence, and so on.


The illustration below shows how this works for an input with a sample period of 1 and frame size of 4. The **Maximum delay** ( $D_{max}$ ) is 5, and the **Initial conditions** parameter is set to -1. The delay input changes from [1 3 0 5] to [2 0 0 2] after the second input frame. The samples in each output frame are the values in memory indexed by the elements of  $v$ :

$$y(1) = U(v(1)+1)$$

$$y(2) = U(v(2)+1)$$

$$y(3) = U(v(3)+1)$$

$$y(4) = U(v(4)+1)$$



The **Initial conditions** parameter specifies the values in the block's memory at the start of the simulation. Both fixed and time-varying initial conditions can be specified.

## Fixed Initial Conditions

The settings shown in this section specify fixed initial conditions. For a fixed initial condition, the block initializes each of  $D$  samples in memory to the value entered in the **Initial conditions** parameter. A fixed initial condition in frame-based mode can be one of the following:

- Scalar value with which to initialize every sample of every channel in memory. For a general  $M$ -by- $N$  input with the parameter settings below, the block initializes five samples in memory with zeros.

# Variable Integer Delay

Maximum delay (samples):  
5  
Initial conditions:  
0

- Array of size 1-by- $N$ -by- $D$ . In this case, you can specify different fixed initial conditions for each channel. See the Array bullet in “Time-Varying Initial Conditions” on page 2-1672 below for details.

## Time-Varying Initial Conditions

The following setting specifies a time-varying initial condition. For a time-varying initial condition, the block initializes each of  $D$  samples in memory to one of the values entered in the **Initial conditions** parameter. This allows you to specify a unique output value for each sample in memory. When the block is performing frame-based processing, you can specify a time-varying initial condition in the following ways:

- Vector containing  $D$  elements. In this case, all channels have the same set of time-varying initial conditions specified by the entries of the vector. For the ramp input `[1:100; 1:100]'` with a frame size of 4, delay of 5, and the following parameter settings, the block outputs the following sequence of frames at the start of the simulation:


$$\begin{bmatrix} -1 & -1 \\ -2 & -2 \\ -3 & -3 \\ -4 & -4 \end{bmatrix}, \begin{bmatrix} -5 & -5 \\ 1 & 1 \\ 2 & 2 \\ 3 & 3 \end{bmatrix}, \begin{bmatrix} 4 & 4 \\ 5 & 5 \\ 6 & 6 \\ 7 & 7 \end{bmatrix}, \dots$$

Maximum delay (samples):  
5  
Initial conditions:  
[-1 -2 -3 -4 -5]

- Array of size 1-by- $N$ -by- $D$ . In this case, you can specify different time-varying initial conditions for each channel. For the ramp input

`[1:100; 1:100]'` with a frame size of 4, delay of 5, and the following parameter settings, the block outputs the following sequence of frames at the start of the simulation:

$$\begin{bmatrix} -1 & -11 \\ -2 & -22 \\ -3 & -33 \\ -4 & -44 \end{bmatrix}, \begin{bmatrix} -5 & -55 \\ 1 & 1 \\ 2 & 2 \\ 3 & 3 \end{bmatrix}, \begin{bmatrix} 4 & 4 \\ 5 & 5 \\ 6 & 6 \\ 7 & 7 \end{bmatrix}, \dots$$




By specifying a 1-by- $N$ -by- $D$  initial condition array such that each 1-by- $N$  vector entry is identical, you can implement different fixed initial conditions for each channel.

## Examples

See “Basic Algorithmic Delay” in the *DSP System Toolbox User’s Guide*.

# Variable Integer Delay



## Dialog Box

### Maximum delay

The maximum delay that the block can produce for any sample. Delay input values exceeding this maximum are clipped at the maximum.

### Initial conditions

The values with which the block's memory is initialized.

### Input processing

Specify how the block should process the input. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.

- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The **Inherited** (this choice will be removed - see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

### Disable direct feedthrough by increasing minimum possible delay by one

Select this box to disable direct feedthrough by adding one to the minimum possible delay value. When you set the **Input processing** parameter to **Columns as channels (frame based)**, the block increases the minimum possible delay value by  $frame\ size - 1$ . Similarly, when you set the **Input processing** parameter to **Elements as channels (sample based)**, the block increases the minimum possible delay value by one sample.

Checking this box allows you to use the Variable Integer Delay block in feedback loops.

## Supported Data Types

Port	Supported Data Types
In	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>

# Variable Integer Delay

---

Port	Supported Data Types
	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Delay	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Out	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>


## See Also

Delay	DSP System Toolbox
Variable Fractional Delay	DSP System Toolbox

**Purpose** Select subset of rows or columns from input

**Library** Signal Management / Indexing  
dspindex

## Description



The Variable Selector block extracts a subset of rows or columns from the  $M$ -by- $N$  input matrix  $u$  at each input port. You specify the number of input and output ports in the **Number of input signals** parameter.

When the **Select** parameter is set to Rows, the Variable Selector block extracts rows from each input matrix, while if the **Select** parameter is set to Columns, the block extracts columns.

When the **Selector mode** parameter is set to Variable, the length- $L$  vector input to the Idx port selects  $L$  rows or columns of each input to pass through to the output. The elements of the indexing vector can be updated at each sample time, but the vector length must remain the same throughout the simulation.

When the **Selector mode** parameter is set to Fixed, the Idx port is disabled, and the length- $L$  vector specified in the **Elements** parameter selects  $L$  rows or columns of each input to pass through to the output. The **Elements** parameter is tunable, so you can change the values of the indexing vector elements at any time during the simulation; however, the vector length must remain the same.

For both variable and fixed indexing modes, the row selection operation is equivalent to

```
y = u(idx,:)      % Equivalent MATLAB code
```

and the column selection operation is equivalent to

```
y = u(:,idx)     % Equivalent MATLAB code
```

where  $idx$  is the length- $L$  indexing vector. The row selection output size is  $L$ -by- $N$  and the column selection output size is  $M$ -by- $L$ . Input rows or columns can appear any number of times in the output, or not at all.

# Variable Selector

---

When the input is an unoriented vector, the **Select** parameter is ignored; the output is a unoriented vector of length  $L$  containing those elements specified by the length- $L$  indexing vector.


When an element of the indexing vector references a nonexistent row or column of the input, the block reacts with the action you specify using the **Invalid index** parameter.

When the indexing vector elements are of Boolean data type, the block performs logical indexing. Select **Fill empty spaces in outputs (for logical indexing)** to access the **Fill values** parameter. These values are appended to the output to make it as long as the input elements.

---

**Note** The Variable Selector block always copies the selected input rows to a contiguous block of memory (unlike the Simulink Selector block).

---



**Dialog**

# Variable Selector

---

## Box

### Number of input signals

Specify the number of input signals. An input port is created on the block for each input signal.

### Select

Specify the dimension of the input to select, **Rows** or **Columns**.

### Selector mode

Specify the type of indexing operation to perform, **Variable** or **Fixed**. Variable indexing uses the input at the **Idx** port to select rows or columns from the input at the **In** port. Fixed indexing uses the **Elements** parameter value to select rows from the input at the **In** port, and disables the **Idx** port.

### Elements

Specify a vector containing the indices of the input rows or columns that will appear in the output matrix. This parameter appears only when you set the **Selector mode** to **Fixed**.

### Index mode

When set to **One-based**, an index value of 1 refers to the first row or column of the input. When set to **Zero-based**, an index value of 0 refers to the first row or column of the input.

### Invalid index

Specify how the block handles an invalid index value. You can select one of the following options:

- **Clip index** — Clip the index to the nearest valid value, and do not issue an alert.

For example, if the block receives a 64-by-4 input and the **Select** parameter is set to **Rows**, the block clips an index of 72 to 64. For the same input, if the **Select** parameter is set to **Columns**, the block clips an index of 72 to 4. In both cases, the block clips an index of -2 to 1.

- **Clip and warn** — Clip the index to the nearest valid value and display a warning message at the MATLAB command line.

- **Generate error** — Display an error dialog box and terminate the simulation.

This parameter is tunable.

### **Fill empty spaces in outputs (for logical indexing)**

When the indexing vector elements are of Boolean data type, the block performs logical indexing. This can cause empty spaces in the output. Select this parameter to designate values to be appended to the output in the **Fill values** parameter.

### **Fill values**

Specify the fill values when the block performs logical indexing. This parameter appears only when you select the **Fill empty spaces in outputs (for logical indexing)** check box.

## **Supported Data Types**

<b>Port</b>	<b>Supported Data Types</b>
In	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li><li>• Enumerated</li></ul>
Idx	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

# Variable Selector

---

Port	Supported Data Types
	<ul style="list-style-type: none"><li>• Enumerated</li></ul>
Out	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li><li>• Enumerated</li></ul>

## See Also

Multipoint Selector	DSP System Toolbox
Permute Matrix	DSP System Toolbox
Selector	Simulink
Submatrix	DSP System Toolbox

**Purpose** Compute variance of input or sequence of inputs

**Library** Statistics  
dspstat3

## Description



The Variance block computes the unbiased variance of each row or column of the input, along vectors of a specified dimension of the input, or of the entire input. The Variance block can also track the variance of a sequence of inputs over a period of time. The **Running variance** parameter selects between basic operation and running operation.

## Basic Operation

When you do not select the **Running variance** check box, the block computes the variance of each row or column of the input, along vectors of a specified dimension of the input, or of the entire input at each individual sample time, and outputs the array  $y$ . Each element in  $y$  is the variance of the corresponding column, row, vector, or entire input. The output  $y$  depends on the setting of the **Find the variance value over** parameter. For example, consider a 3-dimensional input signal of size  $M$ -by- $N$ -by- $P$ :

- **Entire input** — The output at each sample time is a scalar that contains the variance of the entire input.

```
y = var(u(:))      % Equivalent MATLAB code
```

- **Each row** — The output at each sample time consists of an  $M$ -by-1-by- $P$  array, where each element contains the variance of each vector over the second dimension of the input. For an input that is an  $M$ -by- $N$  matrix, the output at each sample time is an  $M$ -by-1 column vector.

```
y = var(u,0,2)    % Equivalent MATLAB code
```

- **Each column** — The output at each sample time consists of a 1-by- $N$ -by- $P$  array, where each element contains the variance of each

# Variance

---

vector over the first dimension of the input. For an input that is an  $M$ -by- $N$  matrix, the output at each sample time is a 1-by- $N$  row vector.

```
y = var(u,0,1)      % Equivalent MATLAB code
```

In this mode, the block treats length- $M$  unoriented vector inputs as  $M$ -by-1 column vectors.

- **Specified dimension** — The output at each sample time depends on **Dimension**. If **Dimension** is set to 1, the output is the same as that when you select **Each column**. If **Dimension** is set to 2, the output is the same as when you select **Each row**. If **Dimension** is set to 3, the output at each sample time is an  $M$ -by- $N$  matrix containing the variance of each vector over the third dimension of the input.

```
y = var(u,0,Dimension)  % Equivalent MATLAB code
```

For purely real or purely imaginary inputs, the variance of an  $M$ -by- $N$  matrix is the square of the standard deviation:

$$y = \sigma^2 = \frac{\sum_{i=1}^M \sum_{j=1}^N |u_{ij}|^2 - \frac{\left| \sum_{i=1}^M \sum_{j=1}^N u_{ij} \right|^2}{M * N}}{M * N - 1}$$

For complex inputs, the variance is given by the following equation:

$$\sigma^2 = \sigma_{\text{Re}}^2 + \sigma_{\text{Im}}^2$$

## Running Operation

When you select the **Running variance** check box, the block tracks the variance of successive inputs to the block. In this mode, you must also specify a value for the **Input processing** parameter:

- When you select **Elements as channels (sample based)**, the block outputs an  $M$ -by- $N$  array. Each element  $y_{ij}$  of the output contains the variance of the element  $u_{ij}$  over all inputs since the last reset.
- When you select **Columns as channels (frame based)**, the block outputs an  $M$ -by- $N$  matrix. Each element  $y_{ij}$  of the output contains the variance of the  $j$ th column over all inputs since the last reset, up to and including element  $u_{ij}$  of the current input.

## Running Operation for Variable-Size Inputs

When your inputs are of variable size, and you select the **Running variance** check box, there are two options:


- If you set the **Input processing** parameter to **Elements as channels (sample based)**, the state is reset.
- If you set the **Input processing** parameter to **Columns as channels (frame based)**, then there are two cases:
  - When the input size difference is in the number of channels (i.e., number of columns), the state is reset.
  - When the input size difference is in the length of channels (i.e., number of rows), there is no reset and the running operation is carried out as usual.

## Resetting the Running Variance


The block resets the running variance whenever a reset event is detected at the optional Rst port. The reset sample time must be a positive integer multiple of the input sample time.

You specify the reset event in the **Reset port** parameter:

- None disables the Rst port.
- Rising edge — Triggers a reset operation when the Rst input does one of the following:
  - Rises from a negative value to a positive value or zero
  - Rises from zero to a positive value, where the rise is not a continuation of a rise from a negative value to zero (see the following figure)



- Falling edge — Triggers a reset operation when the Rst input does one of the following:
  - Falls from a positive value to a negative value or zero
  - Falls from zero to a negative value, where the fall is not a continuation of a fall from a positive value to zero (see the following figure)



- Either edge — Triggers a reset operation when the Rst input is a Rising edge or Falling edge (as described earlier)
- Non-zero sample — Triggers a reset operation at each sample time that the Rst input is not zero

---

**Note** When running simulations in the Simulink MultiTasking mode, reset signals have a one-sample latency. Therefore, when the block detects a reset event, there is a one-sample delay at the reset port rate before the block applies the reset. For more information on latency and the Simulink tasking modes, see “Excess Algorithmic Delay (Tasking Latency)” and the topic on models with multiple sample rates in the Simulink Coder documentation.

---

## ROI Processing

To calculate the statistical value within a particular region of interest (ROI) of the input, select the **Enable ROI processing** check box. This option is only available when the **Find the variance value over** parameter is set to Entire input and the **Running variance** check box is not selected. ROI processing is only supported for 2-D inputs.

---

**Note** Full ROI processing is available only if you have a Computer Vision System Toolbox license. If you do not have a Computer Vision System Toolbox license, you can still use ROI processing, but are limited to the **ROI type** Rectangles.

---

Use the **ROI type** parameter to specify whether the ROI is a binary mask, label matrix, rectangle, or line. ROI processing is only supported for 2-D inputs.

- A binary mask is a binary image that enables you to specify which pixels to highlight, or select.
- In a label matrix, pixels equal to 0 represent the background, pixels equal to 1 represent the first object, pixels equal to 2 represent the second object, and so on. When the **ROI type** parameter is set to **Label matrix**, the Label and Label Numbers ports appear on the block. Use the Label Numbers port to specify the objects in the label matrix for which the block calculates statistics. The input to this port must be a vector of scalar values that correspond to the labeled regions in the label matrix.
- For more information about the format of the input to the ROI port when the ROI is a rectangle or a line, see the Draw Shapes reference page.

---

**Note** For rectangular ROIs, use the **ROI portion to process** parameter to specify whether to calculate the statistical value for the entire ROI or just the ROI perimeter.

---

Use the **Output** parameter to specify the block output. The block can output separate statistical values for each ROI or the statistical value for all specified ROIs. This parameter is not available if, for the **ROI type** parameter, you select **Binary mask**.

If, for the **ROI type** parameter, you select **Rectangles** or **Lines**, the **Output flag indicating if ROI is within image bounds** check box appears in the dialog box. If you select this check box, the Flag port appears on the block. The following tables describe the Flag port output based on the block parameters.

### Output = Individual Statistics for Each ROI

Flag Port Output	Description
0	ROI is completely outside the input image.
1	ROI is completely or partially inside the input image.

### Output = Single Statistic for All ROIs

Flag Port Output	Description
0	All ROIs are completely outside the input image.
1	At least one ROI is completely or partially inside the input image.

If the ROI is partially outside the image, the block only computes the statistical values for the portion of the ROI that is within the image.

If, for the **ROI type** parameter, you select **Label matrix**, the **Output flag indicating if input label numbers are valid** check box appears in the dialog box. If you select this check box, the Flag port appears on the block. The following tables describe the Flag port output based on the block parameters.

# Variance

---

## Output = Individual Statistics for Each ROI

Flag Port Output	Description
0	Label number is not in the label matrix.
1	Label number is in the label matrix.


## Output = Single Statistic for All ROIs

Flag Port Output	Description
0	None of the label numbers are in the label matrix.
1	At least one of the label numbers is in the label matrix.

## Fixed-Point Data Types

The parameters on the **Data Types** pane of the block dialog are only used for fixed-point inputs. For purely real or purely imaginary inputs, the variance of the input is the square of its standard deviation. For complex inputs, the output is the sum of the variance of the real and imaginary parts of the input.

The following diagram shows the data types used within the Variance block for fixed-point signals.




The results of the magnitude-squared calculations in the figure are in the product output data type. You can set the accumulator, product output, and output data types in the block dialog as discussed in “Dialog Box” on page 2-1693.


## Examples

In the following `ex_variance_ref` model, the Variance block calculates the running variance of a 3-by-2 matrix input,  $u$ . The **Input processing** parameter is set to **Columns as channels (frame based)**, so the block processes the input as a two channel signal with a frame size of three. The running variance is reset at  $t=2$  by an impulse to the block’s `Rst` port.

# Variance




The operation of the block is shown in the following figure.



## Dialog Box

The **Main** pane of the Variance block dialog appears as follows.



### Running variance

Enables running operation when selected.

## Input processing

Specify how the block should process the input when computing the running variance. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

This parameter appears only when you select the **Running variance** check box.

---

**Note** The option *Inherit from input* (this choice will be removed - see release notes) will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

## Reset port

Specify the reset event that causes the block to reset the running variance. The sample time of the input to the Rst port must be a positive integer multiple of the input sample time. This parameter appears only when you select the **Running variance** check box. For more information, see “Resetting the Running Variance” on page 2-1686

## Find the variance value over

Specify whether to find the variance along rows, columns, entire input, or the dimension specified in the **Dimension** parameter. For more information, see “Basic Operation” on page 2-1683.

## Treat sample-based row input as a column

Select to treat sample-based length- $M$  row vector inputs as  $M$ -by-1 column vectors. This parameter is only visible when the **Find the variance value over** parameter is set to Each column.

---

**Note** This check box will be removed in a future release. See “Sample-Based Row Vector Processing Changes” in the DSP System Toolbox Release Notes.

---

## Dimension

Specify the dimension (one-based value) of the input signal, over which the variance is computed. The value of this parameter cannot exceed the number of dimensions in the input signal. This parameter is only visible when the **Find the variance value over** parameter is set to Specified dimension.

## Enable ROI Processing

Select this check box to calculate the statistical value within a particular region of each image. This parameter is only available when the **Find the variance value over** parameter is set to Entire input, and the block is not in running mode.

---

**Note** Full ROI processing is available only if you have a Computer Vision System Toolbox license. If you do not have a Computer Vision System Toolbox license, you can still use ROI processing, but are limited to the **ROI type** Rectangles.

---

## ROI type

Specify the type of ROI you want to use. Your choices are Rectangles, Lines, Label matrix, or Binary mask.

# Variance

---

## **ROI portion to process**

Specify whether you want to calculate the statistical value for the entire ROI or just the ROI perimeter. This parameter is only visible if, for the **ROI type** parameter, you specify Rectangles.

## **Output**

Specify the block output. The block can output a vector of separate statistical values for each ROI or a scalar value that represents the statistical value for all the specified ROIs. This parameter is not available if, for the **ROI type** parameter, you select Binary mask.

## **Output flag**

**Output flag indicating if ROI is within image bounds**


**Output flag indicating if label numbers are valid**

When you select either of these check boxes, the Flag port appears on the block. For a description of the Flag port output, see the tables in “ROI Processing” on page 2-1687.

The **Output flag indicating if ROI is within image bounds** check box is only visible when you select Rectangles or Lines as the **ROI type**.

The **Output flag indicating if label numbers are valid** check box is only visible when you select Label matrix for the **ROI type** parameter.

The **Data Types** pane of the Variance block dialog appears as follows.



## **Rounding mode**

Select the rounding mode for fixed-point operations.

## **Overflow mode**

Select the overflow mode for fixed-point operations.

---

**Note** See “Fixed-Point Data Types” on page 2-1690 for more information on how the product output, accumulator, and output data types are used in this block.

---

## **Input-squared product**

Use this parameter to specify how to designate the input-squared product word and fraction lengths:

- When you select `Same as input`, these characteristics match those of the input to the block.
- When you select `Binary point scaling`, you can enter the word length and the fraction length of the input-squared product, in bits.
- When you select `Slope and bias scaling`, you can enter the word length, in bits, and the slope of the input-squared product. This block requires power-of-two slope and a bias of zero.

## **Input-sum-squared product**

Use this parameter to specify how to designate the input-sum-squared product word and fraction lengths:

- When you select `Same as input-squared product`, these characteristics match those of the input-squared product.
- When you select `Binary point scaling`, you can enter the word length and the fraction length of the input-sum-squared product, in bits.
- When you select `Slope and bias scaling`, you can enter the word length, in bits, and the slope of the input-sum-squared product. This block requires power-of-two slope and a bias of zero.

## **Accumulator**

Use this parameter to specify the accumulator word and fraction lengths resulting from a complex-complex multiplication in the block:

- When you select **Same as input-squared product**, these characteristics match those of the input-squared product.
- When you select **Same as input**, these characteristics match those of the input to the block.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the accumulator, in bits.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the accumulator. This block requires power-of-two slope and a bias of zero.

## **Output**

Choose how you specify the output word length and fraction length:

- When you select **Same as accumulator**, these characteristics match those of the accumulator.
- When you select **Same as input-squared product**, these characteristics match those of the input-squared product.
- When you select **Same as input**, these characteristics match those of the input to the block.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the output, in bits.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the output. This block requires power-of-two slope and a bias of zero.

## **Lock data type settings against changes by the fixed-point tools**

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

# Variance

---

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Reset	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
ROI	Rectangles and lines: <ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul> Binary Mask: <ul style="list-style-type: none"><li>• Boolean</li></ul>
Label	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Label Numbers	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

Port	Supported Data Types
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Flag	<ul style="list-style-type: none"><li>• Boolean</li></ul>

## See Also


Mean	DSP System Toolbox
RMS	DSP System Toolbox
Standard Deviation	DSP System Toolbox
var	MATLAB

# Vector Quantizer Decoder

**Purpose** Find vector quantizer codeword that corresponds to given, zero-based index value

**Library** Quantizers  
dspquant2

## Description



The Vector Quantizer Decoder block associates each input index value with a codeword, a column vector of quantized output values defined in the **Codebook values** parameter. When you input multiple index values into this block, the block outputs a matrix of quantized output vectors. This matrix is created by horizontally concatenating the codeword vectors that correspond to each index value.

You can select how you want to enter the codebook values using the **Source of codebook** parameter. When you select **Specify via dialog**, you can type the codebook values into the block parameters dialog box. Select **Input port** and port C appears on the block. The block uses the input to port C as the **Codebook values** parameter.

The **Codebook values** parameter is a  $k$ -by- $N$  matrix of values, where  $k \geq 1$  and  $N \geq 1$ . Each column of this matrix is a codeword vector, and each codeword vector corresponds to an index value. The index values are zero based; therefore, the first codeword vector corresponds to an index value of 0, the second codeword vector corresponds to an index value of 1, and so on.

The input to this block is a vector of index values, where  $0 \leq \text{index} < N$  and  $N$  is the number of columns of the codebook matrix. Use the **Action for out of range index value** parameter to determine how the block behaves when an input index value is out of this range. When you want any index values less than 0 to be set to 0 and any index values greater than or equal to  $N$  to be set to  $N-1$ , select **Clip**. When you want to be warned when any index values less than 0 are set to 0 and any index values greater than or equal to  $N$  are set to  $N-1$ , select **Clip and warn**. When you want the simulation to stop and display an error when the index values are out of range, select **Error**.

## Data Type Support


The input to the block can be the index values and the codebook values. The data type of the index input to the block at port I can be `uint8`, `uint16`, `uint32`, `int8`, `int16`, or `int32`. The data type of the codebook values can be `double`, `single`, or `Fixed-point`.

The output of the block is the quantized output values. These quantized output values always have the same data type as the codebook values. When the codebook values are specified via an input port, the block assigns the same data type to the Q(U) output port. When the codebook values are specified via the dialog, use the **Codebook and output data type** parameter to specify the data type of the Q(U) output port. The data type of the codebook and quantized output can be `Same as input`, `double`, `single`, `Fixed-point`, `User-defined`, or `Inherit` via back propagation.

# Vector Quantizer Decoder

## Dialog Box

The **Main** pane of the Vector Quantizer Decoder block dialog appears as follows.



### Action for out of range index value

Choose the behavior of the block when an input index value is out of range, where  $0 \leq index < N$  and  $N$  is the length of the codebook vector. Select **Clip** when you want any index values less than 0 to be set to 0 and any index values greater than or equal to  $N$  to be set to  $N-1$ . Select **Clip and warn** when you want to be warned when any index values less than 0 are set to 0 and any index values greater than or equal to  $N$  are set to  $N-1$ . Select **Error** when you want the simulation to stop and display an error when the index values are out of range.


### Source of codebook

Choose **Specify via dialog** to type the codebook values into the block parameters dialog box. Select **Input port** to specify the codebook values using the block's input port, **C**.

## Codebook values

Enter a  $k$ -by- $N$  matrix of quantized output values, where  $1 \leq k$  and  $1 \leq N$ . Each column of your matrix corresponds to an index value. This parameter is visible if, from the **Source of codebook** list, you select **Specify via dialog**.

The **Data Types** pane of the Vector Quantizer Decoder block dialog appears as follows.



## Codebook and output data type

Specify the data type of the codebook and quantized output values. You can select one of the following:

- A rule that inherits a data type, for example, **Inherit: Same as input**.
- A built in data type, such as **double**

# Vector Quantizer Decoder

- An expression that evaluates to a valid data type, for example, `fixdt(1,16)`

Click the **Show data type assistant** button  to display the **Data Type Assistant**, which helps you set the **Output data type** parameter.

See “Specify Block Output Data Types” in *Simulink User’s Guide* for more information.

This parameter is available only when you set the **Source of codebook** parameter to **Specify via dialog**. If you set the **Source of codebook** parameter to **Input port**, the output values have the same data type as the input codebook values.

## References

Gersho, A. and R. Gray. *Vector Quantization and Signal Compression*. Boston: Kluwer Academic Publishers, 1992.

## Supported Data Types

Port	Supported Data Types
I	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
C	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
Q(U)	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

## See Also

Quantizer	Simulink
Scalar Quantizer Decoder	DSP System Toolbox
Scalar Quantizer Design	DSP System Toolbox
Uniform Encoder	DSP System Toolbox
Uniform Decoder	DSP System Toolbox
Vector Quantizer Encoder	DSP System Toolbox

# Vector Quantizer Design

---

## Purpose


Design vector quantizer using Vector Quantizer Design Tool (VQDTool)

## Library

Quantizers

dspquant2

## Description



Vector Quantizer  
Design

Double-click on the Vector Quantizer Design block to start VQDTool, a GUI that allows you to design and implement a vector quantizer. You can also start VQDTool by typing `vqdttool` at the MATLAB command prompt. Based on your specifications, VQDTool iteratively calculates the codebook values that minimize the mean squared error between the training set and the codebook until the stopping criteria for the design process is satisfied. The block uses the resulting codebook values to implement your vector quantizer.

For the **Training Set** parameter, enter a  $k$ -by- $M$  matrix of values you want to use to train the quantizer codebook. The variable  $k$ , where  $k \geq 1$ , is the length of each training vector. It also represents the dimension of your quantizer. The variable  $M$ , where  $M \geq 2$ , is the number of training vectors. This data can be created using a MATLAB function, such as the default value `randn(10,1000)`, or it can be any variable defined in the MATLAB workspace.

You have two choices for the **Source of initial codebook** parameter. Select **Auto-generate** to have the block choose the values of the initial codebook. In this case, the block picks  $N$  random training vectors as the initial codebook, where  $N$  is the **Number of levels** parameter and  $N \geq 2$ . When you select **User defined**, enter the initial codebook values in the **Initial codebook** field. The initial codebook matrix must have the same number of rows as the training set. Each column of the codebook is a codeword, and your codebook must have at least two codewords.

For the given training set and initial codebook, the block performs an iterative process, using the Generalized Lloyd Algorithm (GLA), to design a final codebook. For each iteration of the GLA, the block first associates each training vector with its nearest codeword by calculating

the distortion. You can specify one of the two possible methods for calculating distortion using the **Distortion measure** parameter.

When you select Squared error for the **Distortion measure** parameter, the block finds the nearest codeword by calculating the squared error (unweighted). Consider the codebook

$CB = [CW_1 \ CW_2 \ \dots \ CW_N]$ . This codebook has  $N$  codewords; each codeword has  $k$  elements. The  $i$ -th codeword is defined as

$CW_i = [a_{1i} \ a_{2i} \ \dots \ a_{ki}]$ . The training set has  $M$  columns and is defined as  $U = [U_1 \ U_2 \ \dots \ U_M]$ , where the  $p$ -th training vector

is  $U_p = [u_{1p} \ u_{2p} \ \dots \ u_{kp}]'$ . The squared error (unweighted) is calculated using the equation

$$D = \sum_{j=1}^k (a_{ji} - u_{jp})^2$$

When you select Weighted squared error for the **Distortion measure** parameter, enter a vector or matrix for the **Weighting factor** parameter. When the weighting factor is a vector, its length must be equal to the number of rows in the training set. This weighting factor is used for each training vector. When the weighting factor is a matrix, it must be the same size as the training set matrix. The block finds the nearest codeword by calculating the weighted squared error. If the weighting factor for the  $p$ -th column of the training vector,  $U_p$ ,

is defined as  $Wp = [w_{1p} \ w_{2p} \ \dots \ w_{kp}]'$ , then the weighted squared error is defined by the equation

$$D = \sum_{j=1}^k w_{jp} (a_{ji} - u_{jp})^2$$

Once the block has associated all the training vectors with their nearest codeword vectors, the block calculates the mean squared error for the

# Vector Quantizer Design

---

codebook and checks to see if the stopping criteria for the process has been satisfied.

The two possible options for the **Stopping criteria** parameter are **Relative threshold** and **Maximum iteration**. When you want the design process to stop when the fractional drop in the squared error is below a certain value, select **Relative threshold**. Then, type the maximum acceptable fractional drop in the **Relative threshold** field. The fraction drop in the squared error is defined as

$$\frac{\text{error at previous iteration} - \text{error at current iteration}}{\text{error at previous iteration}}$$

When you want the design process to stop after a certain number of iterations, choose **Maximum iteration**. Then, enter the maximum number of iterations you want the block to perform in the **Maximum iteration** field. For **Stopping criteria**, you can also choose **Whichever comes first** and enter **Relative threshold** and **Maximum iteration** values. The block stops iterating as soon as one of these conditions is satisfied.

When a training vector has the same distortion for two different codeword vectors, the algorithm uses the **Tie-breaking rule** parameter to determine which codeword vector the training vector is associated with. When you want the training vector to be associated with the lower indexed codeword, select **Lower indexed codeword**. To associate the training vector with the higher indexed codeword, select **Higher indexed codeword**.

With each iteration, the block updates the codeword values in order to minimize the distortion. The **Codebook update method** parameter defines the way the block calculates these new codebook values.

---

**Note** If, for the **Distortion measure** parameter, you choose **Squared error**, the **Codebook update method** parameter is set to **Mean**.

---

If, for the **Distortion measure** parameter, you choose Weighted squared error and you choose Mean for the **Codebook update method** parameter, the new codeword vector is found as follows. Suppose there are three training vectors associated with one codeword vector. The training vectors are

$$TS_1 = \begin{bmatrix} 1 \\ 2 \end{bmatrix}, TS_3 = \begin{bmatrix} 10 \\ 12 \end{bmatrix}, \text{ and } TS_7 = \begin{bmatrix} 11 \\ 12 \end{bmatrix}.$$

$$CW_{new} = \begin{bmatrix} \frac{1+10+11}{3} \\ \frac{2+12+12}{3} \end{bmatrix}$$

The new codeword vector is calculated as

where the denominator is the number of training vectors associated with this codeword. If, for the **Codebook update method** parameter,

you choose Centroid and you specify the weighting factors  $W_1 = \begin{bmatrix} 0.1 \\ 0.2 \end{bmatrix}$ ,

$W_3 = \begin{bmatrix} 1 \\ 0.6 \end{bmatrix}$ , and  $W_7 = \begin{bmatrix} 0.3 \\ 0.4 \end{bmatrix}$ , the new codeword vector is calculated as

$$CW_{new} = \begin{bmatrix} \frac{(0.1)(1) + (1)(10) + (0.3)(11)}{0.1 + 1 + 0.3} \\ \frac{(0.2)(2) + (0.6)(12) + (0.4)(12)}{0.2 + 0.6 + 0.4} \end{bmatrix}$$

Click **Design and Plot** to design the quantizer with the parameter values specified on the left side of the GUI. The performance curve and the entropy of the quantizer are updated and displayed in the figures on the right side of the GUI.

# Vector Quantizer Design

---

---

**Note** You must click **Design and Plot** to apply any changes you make to the parameter values in the VQDTool dialog box.

---

The following is an example of how the block calculates the entropy of the quantizer at each iteration. Suppose you have a codebook with four codewords and a training set with 200 training vectors. Also suppose that, at the  $i$ -th iteration, 40 training vectors are associated with the first codeword, 60 training vectors are associated with the second codeword, 20 training vectors are associated with the third codeword, and 80 training vectors are associated with the fourth codeword. The probability that a training vector is associated with the first codeword

is  $\frac{40}{200}$ . The probabilities that training vectors are associated with

the second, third, and fourth codewords are  $\frac{60}{200}$ ,  $\frac{20}{200}$ , and  $\frac{80}{200}$ , respectively. The GUI uses these probabilities to calculate the entropy according to the equation

$$H = \sum_{i=1}^N -p_i \log_2 p_i$$

where  $N$  is the number of codewords. Based on these probabilities, the GUI calculates the entropy of the quantizer at the  $i$ -th iteration as

$$H = -\left( \frac{40}{200} \log_2 \frac{40}{200} + \frac{60}{200} \log_2 \frac{60}{200} + \frac{20}{200} \log_2 \frac{20}{200} + \frac{80}{200} \log_2 \frac{80}{200} \right)$$
$$H = 1.8464$$

VQDTool can export parameter values that correspond to the figures displayed in the GUI. Click the **Export Outputs** button, or press **Ctrl+E**, to export the **Final Codebook**, **Mean Square Error**, and **Entropy** values to the workspace, a text file, or a MAT-file.

In the **Model** section of the GUI, specify the destination of the block that will contain the parameters of your quantizer. For **Destination**, select `Current model` to create a block with your parameters in the model you most recently selected. Type `gcs` in the MATLAB Command Window to display the name of your current model. Select `New model` to create a block in a new model file.

From the **Block type** list, select `Encoder` to design a Vector Quantizer Encoder block. Select `Decoder` to design a Vector Quantizer Decoder block. Select `Both` to design a Vector Quantizer Encoder block and a Vector Quantizer Decoder block.

In the **Encoder block name** field, enter a name for the Vector Quantizer Encoder block. In the **Decoder block name** field, enter a name for the Vector Quantizer Decoder block. When you have a Vector Quantizer Encoder and/or Decoder block in your destination model with the same name, select the **Overwrite target block** check box to replace the block's parameters with the current parameters. When you do not select this check box, a new Vector Quantizer Encoder and/or Decoder block is created in your destination model.

Click **Generate Model**. VQDTool uses the parameters that correspond to the current plots to set the parameters of the Vector Quantizer Encoder and/or Decoder blocks.

# Vector Quantizer Design

## Dialog Box

The screenshot shows the VQ Design Tool interface with the following configuration:

- Training Set: `randn(10,1000)`
- Vector quantizer:
  - Source of initial codebook: Auto-generate
  - Number of levels: 16
  - Initial codebook: `randn(10,16)`
  - Distortion measure: Squared error
  - Weighting factor: `ones(10,1000)`
- Stopping criteria:
  - Stopping criteria: Relative threshold
  - Relative threshold:  $1e-7$
  - Maximum iteration: 1000
- Algorithmic details:
  - Tie-breaking rule: Lower indexed codeword
  - Codebook update method: Mean
- Model:
  - Destination: Current model
  - Block type: Encoder
  - Encoder block name: VQ Encoder
  - Decoder block name: VQ Decoder
  - Overwrite target block(s)

Buttons: Design and Plot, Export Outputs, Generate Model

Status: Ready

Total number of iterations = 36

### Performance curve (mean square error at each iteration)

Number of Iterations	Mean Square Error
0	9.2
1	8.5
2	7.5
3	7.0
4	6.8
5	6.6
10	6.5
15	6.45
20	6.4
25	6.4
30	6.4
35	6.4
36	6.4

### Entropy

Number of Iterations	Entropy
0	3.55
1	3.7
2	3.85
3	3.95
4	3.98
5	3.99
10	3.99
15	3.99
20	3.99
25	3.99
30	3.99
35	3.99
36	3.99

## Training Set

Enter the samples of the signal you would like to quantize. This data set can be a MATLAB function or a variable defined in the MATLAB workspace. The typical length of this data vector is  $1e5$ .

## Source of initial codebook

Select `Auto-generate` to have the block choose the initial codebook values. Choose `User defined` to enter your own initial codebook values.

## Number of levels

Enter the number of codeword vectors,  $N$ , in your codebook matrix, where  $N \geq 2$ .

## Initial codebook

Enter your initial codebook values. From the **Source of initial codebook** list, select `User defined` in order to activate this parameter. The codebook must have the same number of rows as the training set. You must provide at least two codeword vectors.

## Distortion measure

When you select `Squared error`, the block finds the nearest codeword by calculating the squared error (unweighted). When you select `Weighted squared error`, the block finds the nearest codeword by calculating the weighted squared error.

## Weighting factor

Enter a vector or matrix. The block uses these values to compute the weighted squared error. When the weighting factor is a vector, its length must be equal to the number of rows in the training set. This weighting factor is used for each training vector. When the weighting factor is a matrix, it must be the same size as the training set matrix. The individual weighting factors cannot be negative. The weighting factor vector or matrix cannot contain all zeros.

## Stopping criteria

Choose `Relative threshold` to enter the maximum acceptable fractional drop in the squared quantization error. Choose `Maximum iteration` to specify the number of iterations at which to stop.

# Vector Quantizer Design

---

Choose `Whichever comes first` and the block stops the iteration process as soon as the relative threshold or maximum iteration value is attained.

## Relative threshold

This parameter is available when you choose `Relative threshold` or `Whichever comes first` for the **Stopping criteria** parameter. Enter the value that is the maximum acceptable fractional drop in the squared quantization error.

## Maximum iteration

This parameter is available when you choose `Maximum iteration` or `Whichever comes first` for the **Stopping criteria** parameter. Enter the maximum number of iterations you want the block to perform.

## Tie-breaking rules

When a training vector has the same distortion for two different codeword vectors, select `Lower indexed codeword` to associate the training vector with the lower indexed codeword. Select `Higher indexed codeword` to associate the training vector with the lower indexed codeword.

## Codebook update method

When you choose `Mean`, the new codeword vector is calculated by taking the average of all the training vector values that were associated with the original codeword vector. When you choose `Centroid`, the block calculates the new codeword vector by taking the weighted average of all the training vector values that were associated with the original codeword vector. Note that if, for the **Distortion measure** parameter, you choose `Squared error`, the **Codebook update method** parameter is set to `Mean`.

## Destination

Choose `Current model` to create a Vector Quantizer block in the model you most recently selected. Type `gcs` in the MATLAB Command Window to display the name of your current model. Choose `New model` to create a block in a new model file.

## Block type

Select **Encoder** to design a Vector Quantizer Encoder block.  
Select **Decoder** to design a Vector Quantizer Decoder block. Select **Both** to design a Vector Quantizer Encoder block and a Vector Quantizer Decoder block.

## Encoder block name

Enter a name for the Vector Quantizer Encoder block.

## Decoder block name

Enter a name for the Vector Quantizer Decoder block.

## Overwrite target block

When you do not select this check box and a Vector Quantizer Encoder and/or Decoder block with the same block name exists in the destination model, a new Vector Quantizer Encoder and/or Decoder block is created in the destination model. When you select this check box and a Vector Quantizer Encoder and/or Decoder block with the same block name exists in the destination model, the parameters of these blocks are overwritten by new parameters.

## Generate Model

Click this button and VQDTool uses the parameters that correspond to the current plots to set the parameters of the Vector Quantizer Encoder and/or Decoder blocks.

## Design and Plot

Click this button to design a quantizer using the parameters on the left side of the GUI and to update the performance curve and entropy plots on the right side of the GUI.

You must click **Design and Plot** to apply any changes you make to the parameter values in the VQDTool GUI.

## Export Outputs

Click this button, or press **Ctrl+E**, to export the **Final Codebook**, **Mean Squared Error**, and **Entropy** values to the workspace, a text file, or a MAT-file.

# Vector Quantizer Design

---

## References

Gersho, A. and R. Gray. *Vector Quantization and Signal Compression*. Boston: Kluwer Academic Publishers, 1992.

## Supported Data Types

- Double-precision floating point

## See Also

Quantizer	Simulink
Scalar Quantizer Decoder	DSP System Toolbox
Scalar Quantizer Design	DSP System Toolbox
Uniform Encoder	DSP System Toolbox
Uniform Decoder	DSP System Toolbox
Vector Quantizer Decoder	DSP System Toolbox
Vector Quantizer Encoder	DSP System Toolbox


## Purpose

For given input, find index of nearest codeword based on Euclidean or weighted Euclidean distance measure

## Library

Quantizers  
dspquant2

## Description



The Vector Quantizer Encoder block compares each input column vector to the codeword vectors in the codebook matrix. Each column of this codebook matrix is a codeword. The block finds the codeword vector nearest to the input column vector and returns its zero-based index. This block supports real floating-point and fixed-point signals on all input ports.

The block finds the nearest codeword by calculating the distortion. The block uses two methods for calculating distortion: Euclidean squared error (unweighted) and weighted Euclidean squared error. Consider

the codebook,  $CB = [CW_1 \ CW_2 \ \dots \ CW_N]$ . This codebook has  $N$  codewords; each codeword has  $k$  elements. The  $i$ -th codeword is defined

as a column vector,  $CW_i = [a_{1i} \ a_{2i} \ \dots \ a_{ki}]$ . The multichannel input has  $M$  columns and is defined as  $U = [U_1 \ U_2 \ \dots \ U_M]$ , where the

$p$ -th input column vector is  $U_p = [u_{1p} \ u_{2p} \ \dots \ u_{kp}]'$ . The squared error (unweighted) is calculated using the equation

$$D = \sum_{j=1}^k (a_{ji} - u_{jp})^2$$

The weighted squared error is calculated using the equation

$$D = \sum_{j=1}^k w_j (a_{ji} - u_{jp})^2$$

# Vector Quantizer Encoder

---

where the weighting factor is defined as  $W = [w_1 \ w_2 \ \dots \ w_k]$ . The index of the codeword that is associated with the minimum distortion is assigned to the input column vector.

You can select how you want to enter the codebook values using the **Source of codebook** parameter. When you select **Specify via dialog**, you can type the codebook values into the block parameters dialog box. Select **Input port** and port C appears on the block. The block uses the input to port C as the **Codebook** parameter.

The **Codebook** parameter is an  $k$ -by- $N$  matrix of values, where  $k \geq 1$  and  $N \geq 1$ . Each input column vector is compared to this codebook. Each column of the codebook matrix is a codeword, and each codeword has an index value. The first codeword vector corresponds to an index value of 0, the second codeword vector corresponds to an index value of 1, and so on. The codeword vectors must have the same number of rows as the input,  $U$ .

For the **Distortion measure** parameter, select **Squared error** when you want the block to calculate the distortion by evaluating the Euclidean distance between the input column vector and each codeword in the codebook. Select **Weighted squared error** when you want to use a weighting factor to emphasize or deemphasize certain input values.

For the **Source of weighting factor** parameter, select **Specify via dialog** to enter a weighting factor vector in the dialog box. Choose **Input port** to specify the weighting factor using port W.

Use the **Weighting factor** parameter to emphasize or deemphasize certain input values when calculating the distortion measure. For example, consider the  $p$ -th input column vector,  $U_p$ , as previously defined. When you want to neglect the effect of the first element of this vector, enter  $[0 \ 1 \ 1 \ \dots \ 1]$  as the **Weighting factor** parameter. This weighting factor is used to calculate the weighted squared error using the equation

$$D = \sum_{j=1}^k w_j (a_{ji} - u_{jp})^2$$

Because of the weighting factor used in this example, the weighted squared error is not affected by the first element of the input matrix. Therefore, the first element of the input column vector no longer impacts the choice of index value output by the Vector Quantizer Encoder block.

Use the **Index output data type** parameter to specify the data type of the index values output at port I. The data type of the index values can be `int8`, `uint8`, `int16`, `uint16`, `int32`, or `uint32`.

When an input vector is equidistant from two codewords, the block uses the **Tie-breaking rule** parameter to determine which index value the block chooses. When you want the input vector to be represented by the lower index valued codeword, select `Choose the lower index`. To represent the input column vector by the higher index valued codeword, select `Choose the higher index`.

Select the **Output codeword** check box to output at port Q(U) the codeword vectors that correspond to each index value. When the input is a matrix, the corresponding codeword vectors are horizontally concatenated into a matrix.

Select the **Output quantization error** check box to output at port D the quantization error that results when the block represents the input column vector by its nearest codeword. When the input is a matrix, the quantization error values are horizontally concatenated.

The Vector Quantizer Encoder block accepts real floating-point and fixed-point inputs. For more information on the data types accepted by each port, see “Data Type Support” on page 2-1721 or “Supported Data Types” on page 2-1728.

## Data Type Support

The input data values, codebook values, and weighting factor values are input to the block at ports U, C, and W, respectively. The data type of the input data values, codebook values, and weighting factor values can


# Vector Quantizer Encoder

be double, single, or Fixed-point. The input data, codebook values, and weighting factor must be the same data type.

The outputs of the block are the index values, output codewords, and quantization error. Use the **Index output data type** parameter to specify the data type of the index output from the block at port I. The data type of the index can be int8, uint8, int16, uint16, int32, or uint32. The data type of the output codewords and the quantization error can be double, single, or Fixed-point. The block assigns the data type of the output codewords and the quantization error based on the data type of the input data.

## Fixed-Point Data Types


The following diagram shows the data types used within the Vector Quantizer Encoder block for fixed-point signals.



You can set the product output, accumulator, and index output data types in the block dialog as discussed below.

## Dialog Box

The **Main** pane of the Vector Quantizer Encoder block dialog appears as follows.



# Vector Quantizer Encoder

---

## Source of codebook

Choose `Specify via dialog` to type the codebook values into the block parameters dialog box. Select `Input port` to specify the codebook values using the block's input port, `C`.

## Codebook

Enter a  $k$ -by- $N$  matrix of values, where  $1 \leq k$  and  $1 \leq N$ , to which your input column vector or matrix is compared. This parameter is visible if, from the **Source of codebook** list, you select `Specify via dialog`.

## Distortion measure

Select `Squared error` when you want the block to calculate the distortion by evaluating the Euclidean distance between the input column vector and each codeword in the codebook. Select `Weighted squared error` when you want the block to calculate the distortion by evaluating a weighted Euclidean distance using a weighting factor to emphasize or deemphasize certain input values.

## Source of weighting factor

Select `Specify via dialog` to enter a value for the weighting factor in the dialog box. Choose `Input port` and specify the weighting factor using port `W` on the block. This parameter is visible if, for the **Distortion measure** parameter, you select `Weighted squared error`.

## Weighting factor

Enter a vector of values. This vector must have length equal to the number of rows of the input, `U`. This parameter is visible if, for the **Source of weighting factor** parameter, you select `Specify via dialog`.

## Tie-breaking rule

Set this parameter to determine the behavior of the block when an input column vector is equidistant from two codewords. When you want the input column vector to be represented by the lower index valued codeword, select `Choose the lower index`. To represent

the input column vector by the higher index valued codeword, select `Choose the higher index`.

## **Output codeword**

Select this check box to output the codeword vectors nearest to the input column vectors.

## **Output quantization error**


Select this check box to output the quantization error value that results when the block represents the input column vector by the nearest codeword.

## **Index output data type**

Select `int8`, `uint8`, `int16`, `uint16`, `int32`, or `uint32` as the data type of the index output at port I.

The **Data Types** pane of the Vector Quantizer Encoder block dialog appears as follows.

# Vector Quantizer Encoder



## Rounding mode

Select the rounding mode for fixed-point operations.

## Overflow mode

Select the overflow mode to be used when block inputs are fixed point.


## Product output



As depicted above, the output of the multiplier is placed into the product output data type and scaling. Use this parameter to specify how you would like to designate this product output word and fraction lengths.

- When you select **Same as input**, these characteristics match those of the input to the block.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the product output, in bits.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the product output. This block requires power-of-two slope and zero bias.

## Accumulator



As depicted above, inputs to the accumulator are cast to the accumulator data type. The output of the adder remains in the

# Vector Quantizer Encoder

---

accumulator data type as each element of the input is added to it. Use this parameter to specify how you would like to designate the accumulator word and fraction lengths.

- When you select **Same as product output**, these characteristics match those of the product output.
- When you select **Same as input**, these characteristics match those of the input to the block.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the accumulator, in bits.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the accumulator. This block requires power-of-two slope and zero bias.

## References

Gersho, A. and R. Gray. *Vector Quantization and Signal Compression*. Boston: Kluwer Academic Publishers, 1992.

## Supported Data Types

Port	Supported Data Types
U	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
C	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>

Port	Supported Data Types
W	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
I	<ul style="list-style-type: none"><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Q(U)	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
D	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>

## See Also

Quantizer	Simulink
Scalar Quantizer Decoder	DSP System Toolbox
Scalar Quantizer Design	DSP System Toolbox
Uniform Encoder	DSP System Toolbox
Uniform Decoder	DSP System Toolbox
Vector Quantizer Decoder	DSP System Toolbox

# Vector Scope

---

**Purpose** Display vector or matrix of time-domain, frequency-domain, or user-defined data

**Library** Sinks  
dspsnks4

## Description



The Vector Scope block is a comprehensive display tool similar to a digital oscilloscope. The block can display time-domain, frequency-domain, or user-defined signals. You can use the Vector Scope block to plot consecutive time samples from a vector, or to plot vectors containing data such as filter coefficients or spectral magnitudes. To compute and plot the periodogram of a signal with a single block, use the Spectrum Scope block.

The input to the Vector Scope block can be any real-valued matrix or vector. The block treats each column of an  $M$ -by- $N$  matrix input as an independent channel of data with  $M$  consecutive samples.

The block plots each sample of each input channel sequentially across the horizontal axis of the plot.


## Scope Properties Pane

The **Scope Properties** pane enables you to plot time-domain, frequency-domain, or user-defined data, and adjust the horizontal display span of the plot. The scope displays frames of data, and updates the display for each new input frame.

The **Input domain** parameter specifies the domain of the input data. If you select **Time**, for  $M$ -by- $N$  inputs containing time-domain data, the block treats each of the  $N$  input frames (columns) as a succession of  $M$  consecutive samples taken from a time series. That is, each data point in the input frame is assumed to correspond to a unique time value. Also, the **Time display span (number of frames)** parameter appears on the pane. Enter a scalar value greater than or equal to one that corresponds to the number of frames to be displayed across the width of the scope window.

If you select **Frequency** for the **Input domain** parameter, for  $M$ -by- $N$  inputs containing frequency-domain data, the block treats each of the  $N$  input frames (columns) as a vector of spectral magnitude data corresponding to  $M$  consecutive ascending frequency indices. That is, when the input is a single column vector,  $u$ , each value in the input frame,  $u(i)$ , is assumed to correspond to a unique frequency value,  $f(i)$ , where  $f(i+1) > f(i)$ .

If you select **User-defined** for the **Input domain** parameter, the block does not assume that the input frame data is time-domain or frequency-domain data. You can plot the data in the appropriate manner. Also, the **Horizontal display span (number of frames)** parameter appears on the pane. Enter a scalar value greater than or equal to one that corresponds to the number of frames to be displayed across the width of the scope window.



## Display Properties Pane

The **Display Properties** pane enables you to control how the block displays your data.

## Vector Scope

---

The **Show grid** parameter toggles the background grid on and off.

If you select the **Persistence** check box, the window maintains successive displays. That is, the scope does not erase the display after each frame (or collection of frames), but overlays successive input frames in the scope display.

If you select the **Frame number** check box, the block displays the number of the current frame in the input sequence on the scope window, and the block increments the count as each new input is received. Counting starts at 1 with the first input frame, and continues until the simulation stops.

If you select the **Channel legend** check box, a legend indicating the line color, style, and marker of each channel's data is added. When the input signal is labeled, that label appears in the channel legend. When the input signal is not labeled, but comes from a Concatenate block or a Mux block with labeled inputs, those labels appear in the channel legend. Otherwise, each channel in the legend is labeled with the channel number (CH 1, CH 2, etc.). Click and drag the legend to reposition it in the scope window; double-click on the line label to edit the text. If you rerun the simulation, the labels revert to the defaults.

If you select the **Compact display** check box, the scope completely fills the figure window. The scope does not display menus and axis titles, but it does show the numerical axis labels within the axes. If you clear the **Compact display** check box, the scope displays the axis labels and titles in a gray border surrounding the scope axes, and the window's menus and toolbar become visible.

If you select the **Open scope at start of simulation** check box, the scope opens at the start of the simulation. If you clear this parameter, the scope does not open automatically during the simulation. You can use this feature when you have several scope blocks in a model, and you do not want to view all the associated scopes during the simulation.

---

**Note** Before running a model that contains a Vector Scope block in Accelerator, Rapid Accelerator, or External mode, you must select the **Open scope at start of simulation** check box. If you do not select this check box before running your model for the first time, the scope will not display your simulation data.

---

If you want to view a scope window that is not open during simulation, click **Open scope immediately** on the **Display Properties** pane of the desired Scope block.

The **Scope position** parameter specifies a four-element vector of the form

[left bottom width height]

specifying the position of the scope window on the screen, where (0,0) is the lower-left corner of the display. See the MATLAB figure function for more information.

## Axis Properties Pane

The parameters that are available on the **Axis Properties** pane depend on the setting of the **Input domain** parameter on the **Scope Properties** pane.

### Time Domain Inputs

When **Time display limits** is set to Auto, the block scales the horizontal axis of time-domain signals automatically. The range of the time axis is  $[0, S * T_{fi}]$ , where  $T_{fi}$  is the input frame period, and  $S$  is the **Time display span (number of frames)** parameter on the **Scope**

**Properties** pane. The spacing between time points is  $T_{fi}/(M - 1)$ , where  $M$  is the number of samples in each consecutive input frame.

When **Time display limits** is set to User-defined, the **Minimum X-limit (s)** and **Maximum X-limit (s)** parameters set the range of the horizontal axis.

# Vector Scope

---

**Minimum Y-limit** and **Maximum Y-limit** parameters set the range of the vertical axis. Setting these parameters is analogous to setting the `ymin` and `ymax` values of the MATLAB `axis` function.

The **Y-axis label** is the text displayed to the left of the  $y$ -axis.

## Frequency Domain Inputs

The **Frequency units** parameter specifies whether the frequency axis values should be in units of Hertz or rad/sec. When the **Frequency units** parameter is set to Hertz, the spacing between frequency points is  $1/(M * T_s)$ , where  $T_s$  is the sample time of the original time-domain signal. When the **Frequency units** parameter is set to rad/sec, the spacing between frequency points is  $2\pi/(M * T_s)$ .

The **Frequency range** parameter specifies the range of frequencies over which the magnitudes in the input should be plotted. The available options are  $[0 \dots Fs/2]$ ,  $[-Fs/2 \dots Fs/2]$ , and  $[0 \dots Fs]$ , where  $F_s$  is the original time-domain signal's sample frequency. The Vector Scope block assumes that the input data spans the range  $[0, F_s)$ , which is the same as the output from an FFT. To plot over the range  $[0 \dots Fs/2]$  the scope truncates the input vector, leaving only the first half of the data, then plots these remaining samples over half the frequency range. To plot over the range  $[-Fs/2 \dots Fs/2]$ , the scope reorders the input vector elements such that the last half of the data becomes the first half, and vice versa; then it relabels the  $x$ -axis accordingly.

If you select the **Inherit sample time from input** check box for frequency domain inputs, the block scales the frequency axis by reconstructing the frequency data from the frame-period of the frequency-domain input. This is valid when the following conditions hold:

- Each frame of frequency-domain data shares the same length as the frame of time-domain data from which it was generated; for example, when the FFT is computed on the same number of points as are contained in the time-domain input.
- The sample period of the time-domain signal in the simulation is equal to the period with which the physical signal was originally sampled.

# Vector Scope

---

- Consecutive frames containing the time-domain signal do not overlap each other; that is, a particular signal sample does not appear in more than one sequential frame.

In cases where not all of these conditions hold, specify the appropriate value for the **Sample time of original time series** parameter.

When **Frequency display limits** is set to Auto, the block scales the horizontal axis of frequency-domain signals automatically. To do this, the Vector Scope block needs to know the sample period of the original time-domain sequence represented by the frequency-domain data. Specify this period by entering a value for the **Sample time of original time series** parameter.

When **Frequency display limits** is set to User-defined, the **Minimum frequency** and **Maximum frequency** parameters set the range of the horizontal axis.

The **Y-axis scaling** parameter allows you to select Magnitude or dB scaling along the  $y$ -axis.

**Minimum Y-limit** and **Maximum Y-limit** parameters set the range of the vertical axis. Setting these parameters is analogous to setting the  $y_{min}$  and  $y_{max}$  values of the MATLAB axis function.

The **Y-axis label** is the text displayed to the left of the  $y$ -axis.

## User-Defined Inputs

If you select the **Inherit sample increment from input** check box for user-defined input domains, the block scales the horizontal axis by computing the horizontal interval between samples in the input frame from the frame period of the input. For example, when the input frame period is 1, and there are 64 samples per input frame, the interval between samples is computed to be  $1/64$ . Computing the interval this way is usually only valid when the following conditions hold:

- The input is a nonoverlapping time series; the  $x$ -axis on the scope represents time.

- The input sample period (1/64 in the above example) is equal to the period with which the physical signal was originally sampled.

In cases where not all of these conditions hold, use the **X display offset (samples)** and **Increment per sample in input** parameters.

The **X-axis title** is the text displayed below the  $x$ -axis.

When **X display limits** is set to Auto, the block scales the horizontal axis of user-defined domain signals automatically. To do this, the Vector Scope block needs to know the spacing of the input data. Specify this spacing using the **Increment per sample in input** parameter,  $I_s$ . This parameter represents the numerical interval between adjacent  $x$ -axis points corresponding to the input data. The range of the horizontal axis is  $[0, M * I_s * S]$ , where  $M$  is the number of samples in each consecutive input frame, and  $S$  is the **Horizontal display span (number of frames)** parameter that you specify in the **Scope Properties** pane.

When **X display limits** is set to User-defined, the **Minimum X-limit (samples)** and **Maximum X-limit (samples)** parameters set the range of the horizontal axis.

**Minimum Y-limit** and **Maximum Y-limit** parameters set the range of the vertical axis. Setting these parameters is analogous to setting the  $y_{\min}$  and  $y_{\max}$  values of the MATLAB `axis` function.

The **Y-axis label** is the text displayed to the left of the  $y$ -axis.

## Line Properties Pane

Use the parameters on the **Line Properties** pane to help you distinguish between two or more independent channels of data on the scope.

The **Line visibilities** parameter specifies which channel's data is displayed on the scope, and which is hidden. The syntax specifies the visibilities in list form, where the term `on` or `off` as a list entry specifies the visibility of the corresponding channel's data. The list entries are separated by the pipe symbol, `|`.

# Vector Scope

For example, a five-channel signal would ordinarily generate five distinct plots on the scope. To disable plotting of the third and fifth lines, enter the following visibility specification in the **Line visibilities** parameter.

```
on | on | off | on | off  
ch 1 ch 2 ch 3 ch 4 ch 5
```

Note that the first (leftmost) list item corresponds to the first signal channel (leftmost column of the input matrix).

The **Line styles** parameter specifies the line style with which each channel's data is displayed on the scope. The syntax specifies the channel line styles in list form, with each list entry specifying a style for the corresponding channel's data. The list entries are separated by the pipe symbol, |.

For example, a five-channel signal would ordinarily generate all five plots with a solid line style. To plot each line with a different style, enter

```
- | -- | : | -. | -  
ch 1 ch 2 ch 3 ch 4 ch 5
```

These settings plot the signal channels with the following styles.

Line Style	Command to Type in Line Style Parameter	Appearance
Solid	-	
Dashed	--	
Dotted	:	
Dash-dot	-.	
No line	none	No line appears

Note that the first (leftmost) list item, ' - ', corresponds to the first signal channel (leftmost column of the input matrix). See the `LineStyle` property of the MATLAB `line` function for more information about the style syntax.

The **Line markers** parameter specifies the marker style with which each channel's samples are represented on the scope. The syntax specifies the channels' marker styles in list form, with each list entry specifying a marker for the corresponding channel's data. The list entries are separated by the pipe symbol, `|`.

For example, a five-channel signal would ordinarily generate all five plots with no marker symbol (that is, the individual sample points are not marked on the scope). To instead plot each line with a different marker style, you could enter

```
* | . | x | s | d
ch 1 ch 2 ch 3 ch 4 ch 5
```

These settings plot the signal channels with the following styles.

Marker Style	Command to Type in Marker Style Parameter	Appearance
Asterisk	*	
Point	.	
Cross	x	

# Vector Scope

Marker Style	Command to Type in Marker Style Parameter	Appearance
Square	s	
Diamond	d	

Note that the leftmost list item, '\*', corresponds to the first signal channel or leftmost column of the input matrix. See the LineSpec property of the MATLAB line function for more information about the available markers.

To produce a stem plot for the data in a particular channel, type the word `stem` instead of one of the basic marker shapes.

The **Line colors** parameter specifies the color in which each channel's data is displayed on the scope. The syntax specifies the channel colors in list form, with each list entry specifying a color (in one of the MATLAB ColorSpec formats) for the corresponding channel's data. The list entries are separated by the pipe symbol, |.

For example, a five-channel signal would ordinarily generate all five plots in the color black. To instead plot the lines with the color order below, enter

```
[0 0 0] | [0 0 1] | [1 0 0] | [0 1 0] | [.7529 0 .7529]  
ch 1     ch 2     ch 3     ch 4     ch 5
```

or

```
'k' | 'b' | 'r' | 'g' | [.7529 0 .7529]  
ch 1 ch 2 ch 3 ch 4     ch 5
```

These settings plot the signal channels in the following colors (8-bit RGB equivalents shown in the center column).

Color	RGB Equivalent	Appearance
Black	(0,0,0)	
Blue	(0,0,255)	
Red	(255,0,0)	
Green	(0,255,0)	
Dark purple	(192,0,192)	

Note that the leftmost list item, 'k', corresponds to the first signal channel or leftmost column of the input matrix. See the MATLAB function `ColorSpec` for more information about the color syntax.

## Vector Scope Window

The title that appears in the title bar of the scope window is the same as the block title. In addition to the standard MATLAB figure window menus such as **File**, **Window**, and **Help**, the Vector Scope window contains **View**, **Axes**, and **Channels** menus.

The options in the **View** menu allow you to zoom in and out of the scope window:

- To zoom in on the scope window, you must first select **View > Zoom In** or click the corresponding Zoom In toolbar button (). You can then zoom in by clicking in the center of your area of interest, or by clicking and dragging your cursor to draw a rectangular area of interest inside of the scope window.
- To zoom in on the x-axis of the scope window, you must first select **View > Zoom X**, or click the corresponding Zoom X-Axis toolbar

# Vector Scope

---

button (⊗) on the scope window. You can then zoom in on the *x*-axis with a single click inside the scope window or by clicking and dragging the cursor along the *x*-axis over your area of interest.

- To zoom in on the *y*-axis of the scope window, you must first select **View > Zoom Y** or click the corresponding **Zoom Y-Axis** toolbar button (⊗). You can then zoom in on the *y*-axis with a single click inside the scope window or by clicking and dragging the cursor along the *y*-axis over your area of interest.
- To return to the original view of the scope window, you have the following options:
  - Select **Full View** from the **View** menu .
  - Click the **Restore default view** toolbar button (⊗) on the Vector Scope window.
  - Right-click inside the scope window, and select **Reset to Original View**.

---

**Note** To zoom out in smaller increments, you can right-click inside of the scope window and select **Zoom Out**. You can also zoom out by holding down the **Shift** key and clicking the left mouse button inside the scope window.

---

The parameters that you set using the **Axes** menu apply to all channels. Many of the parameters in this menu are also accessible through the block parameters dialog box. For descriptions of these parameters, see “Display Properties Pane” on page 2-1731. Below are descriptions of other parameters in the **Axes** menu:

- **Refresh** erases all data on the scope display, except for the most recent trace. This command is useful in conjunction with the **Persistence** setting.
- **Autoscale** resizes the *y*-axis to best fit the vertical range of the data.

---

**Note** The **Minimum Y-limit** and **Maximum Y-limit** parameters on the **Axis properties** pane of the block dialog are not updated to display the numerical limits selected by the autoscale feature.

---

- **Save Axes Settings** allows you to save the current axes settings. When you select this option, the **Minimum Y-limit** and **Maximum Y-limit** parameters of the **Axes Properties** pane update with the current *y*-axes limits. The **Time display limits** (or **Frequency display limits**) parameter is set to User-defined, and the current *x*-axes limits are saved in the **Minimum X-limit** and **Maximum X-limit** (or **Minimum Frequency** and **Maximum Frequency**) parameters. To save these axes settings for your next MATLAB session, you need to resave your model.
- **Save Scope Position** updates the **Scope position** parameter on the **Display Properties** pane of the block dialog to reflect the scope window's current position and size. To make the scope window open at a particular location on the screen when the simulation runs, drag the window to the desired location, resize it, and select **Save Scope Position** from the **Axes** menu.

The properties listed in the **Channels** menu apply to a particular channel. All of the parameters in this menu are also accessible through the block parameters dialog box. For descriptions of these parameters, see “Line Properties Pane” on page 2-1737.

Many of these options can also be accessed by right-clicking with the mouse anywhere on the scope display. The menu that is displayed contains a combination of the options available in the **View**, **Axes** and **Channels** menus.

# Vector Scope

---


---

**Note** When you select **Compact Display** from the **Axes** menu, the scope window menus are no longer visible. Right-click in the Vector Scope window and click **Compact Display** in order to make the menus reappear.

---

## Dialog Box

### Scope Properties Pane



### Input domain

Select the domain of the input. Your choices are Time, Frequency, or User-defined. Tunable.


## Time display span (number of frames)

The number of consecutive frames to display (horizontally) on the scope at any one time. This parameter is visible when the **Input domain** parameter is set to Time.

## Horizontal display span (number of frames)

The number of consecutive frames to display (horizontally) on the scope at any one time. This parameter is visible when the **Input domain** parameter is set to User-defined.

## Display Properties Pane



## Show grid

Toggle the scope grid on and off. Tunable.

## Persistence

Select this check box to maintain successive displays. That is, the scope does not erase the display after each frame (or collection

# Vector Scope

---

of frames), but overlays successive input frames in the scope display. Tunable.

## **Frame number**

If you select this check box, the number of the current frame in the input sequence appears in the Vector Scope window. Tunable.

## **Channel legend**

Toggles the legend on and off. Tunable.

## **Compact display**

Resizes the scope to fill the window. Tunable.

## **Open scope at start of simulation**

Select this check box to open the scope at the start of the simulation. When this parameter is cleared, the scope does not open automatically during the simulation. Tunable.

---

**Note** Before running a model that contains a Vector Scope block in Accelerator, Rapid Accelerator, or External mode, you must select the **Open scope at start of simulation** check box. If you do not select this check box before running your model for the first time, the scope will not display your simulation data.

---

## **Open scope immediately**

If the scope is not open during simulation, select this check box to open it. This parameter is visible only while the simulation is running.


## **Scope position**

A four-element vector of the form [left bottom width height] specifying the position of the scope window. (0,0) is the lower-left corner of the display. Tunable.

## **Axis Properties Pane**

The parameters that are available on the **Axis Properties** pane depend on the setting of the **Input domain** parameter on the **Scope**

**Properties** pane. When **Time** is selected for the **Input domain** parameter, the following parameters are available on the **Axis Properties** pane:



## Time display limits

Select **Auto** to have the limits of the *x*-axis set for you automatically, or **User-defined** to set the limits yourself in the **Minimum X-limit (s)** and **Maximum X-limit (s)** parameters.

# Vector Scope

---

## **Minimum X-limit (s)**

Specify the minimum value of the  $x$ -axis in seconds. This parameter is only visible if the **Time display limits** parameter is set to User-defined. Tunable.

## **Maximum X-limit (s)**

Specify the maximum value of the  $x$ -axis in seconds. This parameter is only visible if the **Time display limits** parameter is set to User-defined. Tunable.

## **Minimum Y-limit**

Specify the minimum value of the  $y$ -axis. Setting this parameter is analogous to setting the `ymin` value of the MATLAB axis function. Tunable.


## **Maximum Y-limit**

Specify the maximum value of the  $y$ -axis. Setting this parameter is analogous to setting the `ymax` value of the MATLAB axis function. Tunable.

## **Y-axis label**

Specify text to be displayed to the left of the  $y$ -axis. Tunable.

When Frequency is selected for the **Input domain** parameter, the following parameters are available on the **Axis Properties** pane:



## Frequency units

Choose the frequency units for the *x*-axis, Hertz or rad/sec. Tunable.

**Frequency range**

Specify the frequency range over which to plot the data. Tunable.

**Inherit sample time from input**

If you select this check box, the block computes the time-domain sample period from the frame period and frame size of the frequency-domain input. Use this parameter only when the length of the each frame of frequency-domain data is the same as the length of the frame of time-domain data from which it was generated. Tunable.

**Sample time of original time series**

Enter the sample period,  $T_s$ , of the original time-domain signal. This parameter is only visible when the **Inherit sample time from input** check box is not selected. Tunable.

**Frequency display limits**

Select Auto to have the limits of the  $x$ -axis set for you automatically, or User-defined to set the limits yourself in the **Minimum frequency** and **Maximum frequency** parameters.

**Minimum frequency**

Specify the minimum frequency value of the  $x$ -axis in Hertz or rad/sec. This parameter is only visible if the **Frequency display limits** parameter is set to User-defined. Tunable.

**Maximum frequency**

Specify the maximum frequency value of the  $x$ -axis in Hertz or rad/sec. This parameter is only visible if the **Frequency display limits** parameter is set to User-defined. Tunable.

**Y-axis scaling**

Choose either dB (decibel) or Magnitude scaling for the  $y$ -axis. Tunable.

**Minimum Y-limit**

Specify the minimum value of the  $y$ -axis. Setting this parameter is analogous to setting the  $y_{min}$  value of the MATLAB axis function. Tunable.

**Maximum Y-limit**


Specify the maximum value of the  $y$ -axis. Setting this parameter is analogous to setting the `ymin` value of the MATLAB `axis` function. Tunable.

**Y-axis label**

Specify text to be displayed to the left of the  $y$ -axis. Tunable.

When `User-defined` is selected for the **Input domain** parameter, the following parameters are available on the **Axis Properties** pane:

# Vector Scope



## Inherit sample increment from input

When you select this check box, the block scales the horizontal axis by computing the horizontal interval between samples in the input frame from the frame period of the input. Use this parameter only when the input's sample period is equal to the period with which the physical signal was originally sampled. Tunable.

**X display offset (samples)**

Specify an offset for the  $x$ -axis display in samples. This parameter is only visible when the **Inherit sample increment from input** check box is not selected. Tunable.

**Increment per sample in input**

Enter the numerical interval between adjacent  $x$ -axis points corresponding to the user-defined input data. This parameter is only visible when the **Inherit sample increment from input** check box is not selected. Tunable.

**X-axis title**

Enter the text to be displayed below the  $x$ -axis. Tunable.

**X display limits**

Select Auto to have the limits of the  $x$ -axis set for you automatically, or User-defined to set the limits yourself in the **Minimum X-limit (samples)** and **Maximum X-limit (samples)** parameters.

**Minimum X-limit (samples)**

Specify the minimum value of the  $x$ -axis in samples. This parameter is only visible if the **X display limits** parameter is set to User-defined. Tunable.

**Maximum X-limit (samples)**

Specify the maximum value of the  $x$ -axis in samples. This parameter is only visible if the **X display limits** parameter is set to User-defined. Tunable.

**Minimum Y-limit**

Specify the minimum value of the  $y$ -axis. Setting this parameter is analogous to setting the  $y_{min}$  value of the MATLAB axis function. Tunable.

**Maximum Y-limit**

Specify the maximum value of the  $y$ -axis. Setting this parameter is analogous to setting the  $y_{max}$  value of the MATLAB axis function. Tunable.


# Vector Scope

---

## Y-axis label

Specify text to be displayed to the left of the  $y$ -axis. Tunable.

## Line Properties Pane



## Line visibilities

Enter on or off to specify the visibility of the various channels' scope traces. Separate your choices for each channel with by a pipe (|) symbol. Tunable.

## Line styles

Enter the line styles of the various channels' scope traces. Separate your choices for each channel with by a pipe (|) symbol. Tunable.

## Line markers

Enter the line markers of the various channels' scope traces. Separate your choices for each channel with by a pipe (|) symbol.Tunable.

## Line colors

Enter the colors of the various channels' scope traces using the ColorSpec formats. Separate your choices for each channel with by a pipe (|) symbol.Tunable.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed and unsigned)</li><li>• Boolean</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>

## See Also

Matrix Viewer	DSP System Toolbox
Spectrum Scope	DSP System Toolbox

# Waterfall

---

**Purpose** View vectors of data over time


**Library** Sinks  
dspsnks4

## Description



The Waterfall block displays multiple vectors of data at one time. These vectors represent the input data at consecutive sample times. The input to the block can be real or complex-valued data vectors of any data type including fixed-point data types. However, the input is converted to double-precision before the block processes the data. The Waterfall block displays only real-valued, double-precision vectors of data.

The data is displayed in a three-dimensional axis in the Waterfall window. By default, the  $x$ -axis represents amplitude, the  $y$ -axis represents samples, and the  $z$ -axis represents time. You can adjust the number of sample vectors that the block displays, move and resize the Waterfall window, and modify block parameter values during the simulation. The Waterfall window has toolbar buttons that enable you to zoom in on displayed data, suspend data capture, freeze the scope's display, save the scope position, and export data to the workspace. The toolbar buttons are labeled in the following figure, which shows the Waterfall window as it appears when you double-click a Waterfall block.



## Sections of This Reference Page

- “Waterfall Parameters” on page 2-1758
- “Display Parameters” on page 2-1760
- “Axes Parameters” on page 2-1761

# Waterfall

---

- “Data History Parameters” on page 2-1763
- “Triggering Parameters” on page 2-1764
- “Scope Trigger Function” on page 2-1768
- “Transform Parameters” on page 2-1770
- “Scope Transform Function” on page 2-1772
- “Examples” on page 2-1773

## **Waterfall Parameters**


You can control the display and behavior of the Waterfall window using the Parameters dialog box.

---

**Note** You can alter the Waterfall parameters while the simulation is running. However, when you make changes to values in text boxes, you must click **Enter** or click outside the text box before the block accepts your changes.

---


- 1** To open the Parameters dialog box, click the **Scope parameters** button.



The Parameters dialog box appears.

# Waterfall


---



**2** Click on the different panes to enter parameter settings.

## **Display Parameters**

The following parameters control the Waterfall window's display.



### **Display traces**

Enter the number of vectors of data to be displayed in the Waterfall window.

### **Update interval**

Enter the number of vectors the block should store before it displays them to the window.

### **Colormap**

Choose a colormap for the displayed data.

### **Transparency**


Specify the transparency of the newest and oldest data vectors. Placing the slider in the left-most position tells the block to make the data vector transparent. Placing the slider in the right-most position tells the block to make the data vector opaque. The intermediate data vectors transition between the two chosen transparency values.

### **Axes Parameters**

The following parameters control the axes in the Waterfall window.

# Waterfall

---



## **Y Min**

Enter the minimum value of the  $y$ -axis.

## **Y Max**

Enter the maximum value of the  $y$ -axis.

## **Axis color**

Enter a background color for the axes. Specify the color using a character string. For example, to specify black, enter 'k'.

## **X Axis**

Enter the  $x$ -axis label.

## **Y Axis**


Enter the  $y$ -axis label.

## **Z Axis**

Enter the  $z$ -axis label.

## Data History Parameters

The following parameters control how many input data vectors the Waterfall block stores. They also control how the data is exported to the MATLAB workspace or SPTool.



### History traces

Enter the number of vectors (traces) that you want the block to store.

### When the buffer is full

Use this parameter to control the behavior of the block when the buffer is filled:

- **Overwrite** — The old data is replaced with the new data.
- **Suspend** — The block stops storing data in the buffer; however, the simulation continues to run.
- **Extend** — The block extends the buffer so that it can continue to store all the input data.

# Waterfall

---

## Data logging

Use this parameter to control which data is exported from the block:

- **Selected** — The selected data vector is exported.
- **All visible** — All of the data vectors displayed in the Waterfall window are exported.
- **All history** — All of the data vectors stored in the block's history buffer are exported.

## Export variable

Enter the name of the variable that represents your data in the MATLAB workspace or SPTool. The default variable name is `ExportData`.

## Export at end of simulation

Select this check box to automatically export the data to the MATLAB workspace when the simulation stops.

## Triggering Parameters

The following parameters control when the Waterfall block starts and stops capturing data.



## Begin recording

This parameter controls when the Waterfall block starts capturing data:

- **Immediately** — The Waterfall window captures the input data as soon as the simulation starts.
- **After T seconds** — The **Time, T** parameter appears in the dialog box. Enter the number of seconds the block should wait before it begins capturing data.
- **After N inputs** — The **Count, N** parameter appears in the dialog box. Enter the number of inputs the block should receive before it begins capturing data.
- **User-defined** — The **Function name** parameter appears in the dialog box. Enter the name of a MATLAB function that defines when the block should begin capturing data. For more information about how you define this function, see “Scope Trigger Function” on page 2-1768.

## Stop recording

This parameter controls when the Waterfall block stops capturing data:

- **Never** — The block captures the input data as long as the simulation is running.
- **After T seconds** — The **Time, T** parameter appears in the dialog box. Enter the number of seconds the block should wait before it stops capturing data.
- **After N inputs** — The **Count, N** parameter appears in the dialog box. Enter the number of inputs the block should receive before it stops capturing data.
- **User-defined** — The **Function name** parameter appears in the dialog box. Enter the name of a MATLAB function that defines when the block should stop capturing data. For more information about how you define this function, see “Scope Trigger Function” on page 2-1768.


## Re-arm trigger

This parameter controls when the Waterfall block begins waiting to capture data. It is available only when you select **After T seconds**, **After N inputs**, or **User-defined** for the **Stop recording** parameter:

- **Never** — The Waterfall Scope block starts and stops capturing data as defined by the **Begin recording** and **Stop recording** parameters.
- **After T seconds** — The **Time, T** parameter appears in the dialog box. Enter the number of seconds the block should wait before it begins waiting to capture data.
- **After N inputs** — The **Count, N** parameter appears in the dialog box. Enter the number of inputs the block should receive before it begins waiting to capture data.
- **User-defined** — The **Function name** parameter appears in the dialog box. Enter the name of a MATLAB function that


defines when the block should begin waiting to capture data. For more information about how you define this function, see “Scope Trigger Function” on page 2-1768.

The triggering process is illustrated in the state diagram below.



## Scope Trigger Function

You can create custom scope trigger functions to control when the scope starts, stops, or begins waiting to capture data.



These functions must be valid MATLAB functions and be located either in the current folder or on the MATLAB path.

Each scope trigger function must have the following form

```
y = functionname(blk,t,u),
```

where `functionname` refers to the name you give your scope trigger function. The variable `blk` is the Simulink block handle. When the scope trigger function is called by the block, Simulink automatically populates this variable with the handle of the Waterfall block. The variable `t` is the current simulation time, represented by a real, double-precision, scalar value. The variable `u` is the vector input to the block. The output of the scope trigger function, `y`, is interpreted as a logical signal. It is either true or false:

- Begin recording scope trigger function
  - When the output of this scope trigger function is true, the Waterfall block starts capturing data.
  - When the output is false, the block remains in its current state.
- Stop recording scope trigger function
  - When the output of this scope trigger function is true, the block stops capturing data.
  - When the output is false, the block remains in its current state.
- Re-arm trigger scope trigger function
  - When the output of this scope trigger function is true, the block waits for a begin recording event.
  - When the output is false, the block remains in its current state.

---

**Note** The Waterfall block passes its input data directly to the scope trigger functions. These functions do not use the transformed data defined by the Transform parameters.

---

The following is an example of a scope trigger function. This function, called `trigPower` detects when the energy in `u` exceeds a certain threshold.

```
function y = trigPower(blk, t, u)
```

```
y = (u'*u > 2300);
```

The following is another example of a scope trigger function. This function, called `count3`, triggers the scope once three vectors with positive means are input to the block. Then, the function resets itself and begins searching for the next three input vectors with positive means. This scope trigger function is valid only when one Waterfall block is present in your model.

# Waterfall

---

```
function y = count3(blk, t, u)

persistent state;
if isempty(state); state = 0; end
if mean(u)>0; state = state+1; end
y = (state>=3);
if y; state = 0; end
```

## Transform Parameters

The following parameters transform the input data to the Waterfall block. The result of the transform is displayed in the Waterfall window.



---

**Note** The block assumes that the input to the block corresponds to the **Transform** parameter you select. For example, when you choose **Complex-> Angle**, the block assumes that the input is complex. The block does not produce an error when the input is not complex. Therefore, you must verify the format of your input data to guarantee that a meaningful result is displayed in the Waterfall window.

---

## Transform

Choose a transform that you would like to apply to the input of the Waterfall block:


- **None** — The input is displayed as it is received by the block.
- **Amplitude-> dB** — The block converts the input amplitude into decibels.
- **Complex-> Mag Lin** — The block converts the complex input into linear magnitude.
- **Complex-> Mag dB** — The block converts the complex input into magnitude in decibels.
- **Complex-> Angle** — The block converts the complex input into phase.
- **FFT-> Mag Lin Fs/2** — The block takes the linear magnitude of the FFT input and plots it from 0 to the Nyquist frequency.
- **FFT-> Mag dB Fs/2** — The block takes the magnitude of the FFT input, converts it to decibels, and plots it from 0 to the Nyquist frequency.
- **FFT-> Angle Fs/2** — The block converts the FFT input into phase and plots it from 0 to the Nyquist frequency.
- **Power-> dB** — The block converts the input power into decibels.

## Function

This parameter is only available when you select **User-defined fcn** for the **Transform** parameter. Enter a function that you would like to apply to the input of the Waterfall block. For more information about how you define this function, see “Scope Transform Function” on page 2-1772.

## Expression

This parameter is only available when you select **User-defined expr** for the **Transform** parameter. Enter an expression that you would like to apply to the input of the Waterfall block. The result of this expression must be real-valued. When you write the expression, be sure to include only one unknown variable. The block assumes this unknown variable represents the input to the block. When the block believes your expression is invalid, the following window appears.



When you click **No**, your expression is not applied to the input. When you click **Yes** and your expression is invalid, your simulation stops and Simulink displays an error.

## Scope Transform Function

You can create a scope transform function to control how the Waterfall block transforms your input data. This function must have a valid

MATLAB function name and be located either in the current folder or on the MATLAB path.

Your scope transform function must have the following form

```
y = functionname(u),
```

where `functionname` refers to the name you give your function. The variable `u` is the real or complex vector input to the block. The output of the scope transform function, `y`, must be a double-precision, real-valued vector. When it is not, the simulation stops and Simulink displays an error. Note that the output vector does not need to be the same size as the input vector.

## Examples

The following examples illustrate some capabilities of the Waterfall block.

- “Exporting Data” on page 2-1773
- “Capturing Data” on page 2-1774
- “Linking Scopes” on page 2-1775
- “Selecting Data” on page 2-1776
- “Zooming” on page 2-1779
- “Rotating the Display” on page 2-1779
- “Scaling the Axes” on page 2-1779
- “Saving Scope Settings” on page 2-1780

### Exporting Data

You can use the Waterfall block to export data to the MATLAB workspace or to SPTool:

- 1 Open and run the `dspanc` example.
- 2 While the simulation is running, click the **Export to Workspace** button.

- 3 Type `whos` at the MATLAB command line.

The variable `ExportData` appears in your MATLAB workspace. `ExportData` is a 40-by-6 matrix. This matrix represents the six data vectors that were present in the Waterfall window at the time you clicked the **Export to Workspace** button. Each column of this matrix contains 40 filter coefficients. The columns of data were captured at six consecutive instants in time.

You can control what data is exported using the **Data logging** parameter in **Data history** pane of the Parameters dialog box. For more information, see “Data History Parameters” on page 2-1763.

- 4 While the simulation is running, click the **Export to SPTool** button.

The SPTool GUI opens and the variable `ExportData` is displayed in the **Signals** list.

For more information about SPTool, see the Signal Processing Toolbox documentation.

## Capturing Data

You can use the Waterfall block to interact with your data while it is being captured:

- 1 Open and run the `dspanc` example.
- 2 While the simulation is running, click the **Suspend data capture** button.

The Waterfall block no longer captures or displays the data coming from the Downsample block.
- 3 To continue capturing data, click the **Resume data capture** button.
- 4 To freeze the data display while continuing to capture data, click the **Snapshot display** button.


- To view the Waterfall block that the data is coming from, click the **Go to scope block** button.

In the Simulink model window, the Waterfall block that corresponds to the active Waterfall window flashes. This feature is helpful when you have more than one Waterfall block in a model and you want to clarify which data is being displayed.

## Linking Scopes

You can link several Waterfall blocks together in order to capture the effect of a model event in all of the Waterfall windows in the model:

- Open the dspanc example.
- Drag a second Waterfall block into the example model.
- Connect this block to the Output port of the LMS Filter block as shown in the figure below.



# Waterfall

---

**4** Run the model and view the model behavior in both Waterfall windows.

**5** In the dspnc/Waterfall window, click the **Link scopes** button.

**6** In the same window, click the **Suspend data capture** button.

The data capture is suspended in both scope windows.

**7** Click the **Resume data capture** button.

The data capture resumes in both scope windows.


**8** In the dspnc/Waterfall window, click the **Snapshot display** button.

In both scope windows, the data display freezes while the block continues to capture data.

**9** To continue displaying the captured data, click the **Resume display** button.

## Selecting Data


The following figure shows the Waterfall window displaying the output of the dspnc example:



- 1 To select a particular set of data, click the **Select** button.
- 2 Click on the Time Bar at the bottom right of the axes to select a vector of data.

The Waterfall block highlights the selected trace.

# Waterfall



While the simulation is running, in the bottom right corner, the Waterfall window displays the relative index of the selected trace. For example, in the previous figure, the selected vector is two sample times away from the most current data vector. When the simulation is stopped, the Waterfall window displays both the relative index and the simulation time associated with the selected trace.

**3** To deselect the data vector, click it again.

**4** Click-and-drag along the Time Bar.

Your selection follows the movement of the pointer.

You can use this feature to choose a particular vector to export to the MATLAB workspace or SPTool. For more information, see “Data History Parameters” on page 2-1763.

## Zooming

You can use the Waterfall window to zoom in on data:

- 1 Click the **Zoom camera** button.
- 2 In the Waterfall window, click and hold down the left mouse button.
- 3 Move the mouse up and down and side-to-side to move closer and farther away from the axes.
- 4 To resize the axes to fit the Waterfall window, click the **Fit to view** button.

## Rotating the Display

You can rotate the data displayed in the Waterfall window:

- 1 Click on the **Orbit camera** button.
- 2 In the Waterfall window, click and hold down the left mouse button.
- 3 Move the mouse in a circular motion to rotate the axes.
- 4 To return to the position of the original axes, click the **Restore scope position and view** button.

## Scaling the Axes

You can use the Waterfall window to rescale the y-axis values:

- 1 Open and run the `dspanc` example.
- 2 Click the **Rescale amplitude** button.

The y-axis changes so that its minimum value is zero. The maximum value is scaled to fit the data displayed.



Vector Scope	DSP System Toolbox
Spectrum Scope	DSP System Toolbox
Matrix Viewer	DSP System Toolbox
Signal To Workspace	DSP System Toolbox
Triggered To Workspace	DSP System Toolbox

# Wavelet Analysis (Obsolete)


## Purpose

Decompose signal into components of logarithmically decreasing frequency intervals and sample rates (requires the Wavelet Toolbox product)

## Library

dspobslib


## Description



**Note** The Wavelet Analysis block will be removed from the product in a future release. We strongly recommend replacing this block with the DWT block.

The Wavelet Analysis block uses the Wavelet Toolbox `wfilters` function to construct a dyadic analysis filter bank that decomposes a broadband signal into a collection of successively more bandlimited components. An  $n$ -level filter bank structure is shown below, where  $n$  is specified by the **Number of levels** parameter.

Wavelet Analysis Filter Bank,  $n$  Levels



At each level, the low-frequency output of the previous level is decomposed into adjacent high- and low-frequency subbands by a highpass (HP) and lowpass (LP) filter pair. Each of the two output subbands is half the bandwidth of the input to that level. The

bandlimited output of each filter is maximally decimated by a factor of 2 to preserve the bit rate of the original signal.

## Filter Coefficients

The filter coefficients for the highpass and lowpass filters are computed by the Wavelet Toolbox function `wfilters`, based on the wavelet specified in the **Wavelet name** parameter. The table below lists the available options.

Wavelet Name	Sample Wavelet Function Syntax
Haar	<code>wfilters('haar')</code>
Daubechies	<code>wfilters('db4')</code>
Symlets	<code>wfilters('sym3')</code>
Coiflets	<code>wfilters('coif1')</code>
Biorthogonal	<code>wfilters('bior3.1')</code>
Reverse Biorthogonal	<code>wfilters('rbio3.1')</code>
Discrete Meyer	<code>wfilters('dmey')</code>

The **Daubechies**, **Symlets**, and **Coiflets** options enable a secondary **Wavelet order** parameter that allows you to specify the wavelet order. For example, if you specify a **Daubechies** wavelet with **Wavelet order** equal to 6, the Wavelet Analysis block calls the `wfilters` function with input argument `'db6'`.

The **Biorthogonal** and **Reverse Biorthogonal** options enable a secondary **Filter order [synthesis / analysis]** parameter that allows you to independently specify the wavelet order for the analysis and synthesis filter stages. For example, if you specify a **Biorthogonal** wavelet with **Filter order [synthesis / analysis]** equal to `[2 / 6]`, the Wavelet Analysis block calls the `wfilters` function with input argument `'bior2.6'`.

# Wavelet Analysis (Obsolete)

---

See the Wavelet Toolbox documentation for more information about the `wfilters` function. If you want to explicitly specify the FIR coefficients for the analysis filter bank, use the Dyadic Analysis Filter Bank block.

## Tree Structure

The wavelet tree structure has  $n+1$  outputs, where  $n$  is the number of levels. The sample rate and bandwidth of the top output are half the input sample rate and bandwidth. The sample rate and bandwidth of each additional output (except the last) are half that of the output from the previous level. In general, for an input with sample period  $T_{si} = T_s$ , and bandwidth  $BW$ , output  $y_k$  has sample period  $T_{so,k}$  and bandwidth  $BW_k$ .

$$T_{so,k} = \begin{cases} (2^k)T_s & (1 \leq k \leq n) \\ (2^n)T_s & (k = n + 1) \end{cases}$$

$$BW_k = \begin{cases} \frac{BW}{2^k} & (1 \leq k \leq n) \\ \frac{BW}{2^n} & (k = n + 1) \end{cases}$$

Note that in frame-based mode, the change in the sample period of output  $y_k$  is reflected by its frame size  $M_{o,k}$ , rather than by its frame rate.


$$M_{o,k} = \begin{cases} \frac{M_i}{2^k} & (1 \leq k \leq n) \\ \frac{M_i}{2^n} & (k = n + 1) \end{cases}$$

The bottom two outputs ( $y_n$  and  $y_{n+1}$ ) share the same sample period, bandwidth, and frame size because they originate at the same tree level.

## Sample-Based Operation

An  $M$ -by- $N$  sample-based matrix input is treated as  $M \cdot N$  independent channels, and the block filters each channel independently over time. The output at each port is the same size as the input, one output channel for each input channel. As described earlier, each output port has a different sample period.

The figure below shows the input and output sample periods for a 64-channel sample-based input to a three-level filter bank. The input has a period of 1, so the fastest output has a period of 2.




## Frame-Based Operation

An  $M_i$ -by- $N$  frame-based matrix input is treated as  $N$  independent channels, and the block filters each channel independently over time. The input frame size  $M_i$  must be a multiple of  $2^n$ , and  $n$  is the number of filter bank levels. For example, a frame size of 8 would be appropriate for a three-level tree ( $2^3=8$ ). The number of columns in each output is the same as the number of columns in the input.

Each output port has the same frame period as the input. The reduction in the output sample rates results from the smaller output frame sizes, as shown in the example below for a four-channel input to a three-level filter bank.

# Wavelet Analysis (Obsolete)

---



## Zero Latency

The Wavelet Analysis block has no tasking latency for frame-based operation, which is always single-rate. The block therefore analyzes the first input sample (received at  $t=0$ ) to produce the first output sample at each port.

## Nonzero Latency


For sample-based operation, the Wavelet Analysis block is multirate and has  $2^{n-1}$  samples of latency in both Simulink tasking modes. As a result, the block repeats a zero initial condition in each channel for the first  $2^{n-1}$  output samples, before propagating the first analyzed input sample (computed from the input received at  $t=0$ ).

---

**Note** For more information on latency and the Simulink tasking modes, see “Excess Algorithmic Delay (Tasking Latency)” and the topic on models with multiple sample rates in the Simulink Coder documentation.

---

## Dialog Box



The parameters displayed in the dialog box vary for different wavelet types. Only some of the parameters listed below are visible in the dialog box at any one time.

### Wavelet name

The wavelet used in the analysis.

### Wavelet order

The order for the **Daubechies**, **Symlets**, and **Coiflets** wavelets. This parameter is available only when one of these wavelets is selected in the **Wavelet name** menu.

### Filter order [synthesis / analysis]

The filter orders for the synthesis and analysis stages of the **Biorthogonal** and **Reverse Biorthogonal** wavelets. For example, [2 / 6] selects a second-order synthesis stage and a sixth-order analysis stage. The **Filter order** parameter is available only when one of the above wavelets is selected in the **Wavelet name** menu.

### Number of levels

The number of filter bank levels. An  $n$ -level structure has  $n+1$  outputs.

# Wavelet Analysis (Obsolete)

---

## References

Fliege, N. J. *Multirate Digital Signal Processing: Multirate Systems, Filter Banks, Wavelets*. West Sussex, England: John Wiley & Sons, 1994.

Strang, G. and T. Nguyen. *Wavelets and Filter Banks*. Wellesley, MA: Wellesley-Cambridge Press, 1996.

Vaidyanathan, P. P. *Multirate Systems and Filter Banks*. Englewood Cliffs, NJ: Prentice Hall, 1993.

## Supported Data Types

- Double-precision floating point

## See Also

Dyadic Analysis Filter Bank	DSP System Toolbox
Wavelet Synthesis (Obsolete)	DSP System Toolbox
wfilters	Wavelet Toolbox

# Wavelet Synthesis (Obsolete)


## Purpose

Reconstruct signal from its multirate bandlimited components (requires the Wavelet Toolbox product)

## Library

dspobslib


## Description



**Note** The Wavelet Synthesis block will be removed from the product in a future release. We strongly recommend replacing this block with the IDWT block.

The Wavelet Synthesis block uses the Wavelet Toolbox `wfilters` function to reconstruct a signal that was decomposed by the Wavelet Analysis (Obsolete) block. The reconstruction or synthesis process is the inverse of the analysis process, and restores the original signal by upsampling, filtering, and summing the bandlimited inputs in stages corresponding to the analysis process. An  $n$ -level synthesis filter bank structure is shown below, where  $n$  is specified by the **Number of levels** parameter.

### Wavelet Synthesis Filter Bank, $n$ Levels



At each level, the two bandlimited inputs (one low-frequency, one high-frequency, both with the same sample rate) are upsampled by

# Wavelet Synthesis (Obsolete)

---

a factor of 2 to match the sample rate of the input to the next stage. They are then filtered by a highpass (HP) and lowpass (LP) filter pair with coefficients calculated to cancel (in the subsequent summation) the aliasing introduced in the corresponding analysis filter stage. The output from each (upsample-filter-sum) level has twice the bandwidth and twice the sample rate of the input to that level.

For perfect reconstruction, the Wavelet Synthesis and Wavelet Analysis blocks must have the same parameter settings.

## Filter Coefficients

The filter coefficients for the highpass and lowpass filters are computed by the Wavelet Toolbox function `wfilters`, based on the wavelet specified in the **Wavelet name** parameter. The table below lists the available options.

Wavelet Name	Sample Wavelet Function Syntax
Haar	<code>wfilters('haar')</code>
Daubechies	<code>wfilters('db4')</code>
Symlets	<code>wfilters('sym3')</code>
Coiflets	<code>wfilters('coif1')</code>
Biorthogonal	<code>wfilters('bior3.1')</code>
Reverse Biorthogonal	<code>wfilters('rbio3.1')</code>
Discrete Meyer	<code>wfilters('dmey')</code>

The **Daubechies**, **Symlets**, and **Coiflets** options enable a secondary **Wavelet order** parameter that allows you to specify the wavelet order. For example, if you specify a **Daubechies** wavelet with **Wavelet order** equal to 6, the Wavelet Synthesis block calls the `wfilters` function with input argument `'db6'`.

The **Biorthogonal** and **Reverse Biorthogonal** options enable a secondary **Filter order [synthesis / analysis]** parameter that allows

you to independently specify the wavelet order for the analysis and synthesis filter stages. For example, if you specify a **Biorthogonal** wavelet with **Filter order [synthesis / analysis]** equal to [2 / 6], the Wavelet Synthesis block calls the `wfilters` function with input argument `'bior2.6'`.

See the Wavelet Toolbox documentation for more information about the `wfilters` function. If you want to explicitly specify the FIR coefficients for the synthesis filter bank, use the Dyadic Synthesis Filter Bank block.

## Tree Structure

The wavelet tree structure has  $n+1$  inputs, where  $n$  is the number of levels. The sample rate and bandwidth of the output are twice the sample rate and bandwidth of the top input. The sample rate and bandwidth of each additional input (except the last) are half that of the input to the previous level.

$$T_{si,k+1} = 2T_{si,k} \quad 1 \leq k < n$$

$$BW_{k+1} = \frac{BW_k}{2} \quad 1 \leq k < n$$

The bottom two inputs ( $u_n$  and  $u_{n+1}$ ) should have the same sample rate and bandwidth since they are processed by the same level.

$$T_{si,n+1} = T_{si,n}$$

$$BW_{n+1} = BW_n$$

Note that in frame-based mode, the sample period of input  $u_k$  is reflected by its frame size  $M_{i,k}$ , rather than by its frame rate.

# Wavelet Synthesis (Obsolete)


$$M_{i,k+1} = \frac{M_{i,k}}{2} \quad 1 \leq k < n$$

$$M_{i,n+1} = M_{i,n}$$

## Sample-Based Operation

An  $M$ -by- $N$  sample-based matrix input is treated as  $M \cdot N$  independent channels, and the block filters each channel independently over time. The output is the same size as the input at each port, one output channel for each input channel. As described earlier, each input port has a different sample period.

The figure below shows the input and output sample periods for the four 64-channel sample-based inputs to a three-level filter bank. The fastest input has a period of 2, so the output period is 1.




## Frame-Based Operation

An  $M_f$ -by- $N$  frame-based matrix input is treated as  $N$  independent channels, and the block filters each channel independently over time. The number of columns in the output is the same as the number of columns in the input.

All inputs must have the same frame period, which is also the output frame period. The different input sample rates should be represented by the input frame sizes: If the input to the top port has frame size  $M_f$ , the input to the second-from-top port should have frame size  $M_f/2$ , the input to the third-from-top port should have frame size  $M_f/4$ , and so on. The input to the bottom port should have the same frame size

as the second-from-bottom port. The increase in the sample rate of the output is also represented by its frame size, which is twice the largest input frame size.

The relationship between sample periods, frame periods, and frame sizes is shown below for a four-channel frame-based input to a 3-level filter bank.



## Zero Latency

The Wavelet Synthesis block has no tasking latency for frame-based operation, which is always single-rate. The block therefore uses the first input samples (received at  $t=0$ ) to synthesize the first output sample.

## Nonzero Latency

For sample-based operation, the Wavelet Synthesis block is multirate and has the following tasking latencies:

- $2^n - 2$  samples in Simulink's single-tasking mode
- $2^n$  samples in Simulink's multitasking mode

In the above cases, the block repeats a zero initial condition in each channel for the first  $D$  output samples, where  $D$  is the latency shown above. For example, in single-tasking mode the block generates  $2^n - 2$  zero-valued output samples in each channel before propagating the first synthesized output sample (computed from the inputs received at  $t=0$ ).

# Wavelet Synthesis (Obsolete)


---

---

**Note** For more information on latency and the Simulink tasking modes, see “Excess Algorithmic Delay (Tasking Latency)” and the topic on models with multiple sample rates in the Simulink Coder documentation.

---

## Dialog Box



The parameters displayed in the dialog box vary for different wavelet types. Only some of the parameters listed below are visible in the dialog box at any one time.

### Wavelet name

The wavelet used in the synthesis.

### Wavelet order

The order for the **Daubechies**, **Symlets**, and **Coiflets** wavelets. This parameter is available only when one of these wavelets is selected in the **Wavelet name** menu.

### Filter order [synthesis / analysis]

The filter orders for the synthesis and analysis stages of the **Biorthogonal** and **Reverse Biorthogonal** wavelets. For example, [2 / 6] selects a second-order synthesis stage and a sixth-order analysis stage. The **Filter order** parameter is available only when one of the above wavelets is selected in the **Wavelet name** menu.

## Number of levels

The number of filter bank levels. An  $n$ -level structure has  $n+1$  outputs.

## References

Fliege, N. J. *Multirate Digital Signal Processing: Multirate Systems, Filter Banks, Wavelets*. West Sussex, England: John Wiley & Sons, 1994.

Strang, G. and T. Nguyen. *Wavelets and Filter Banks*. Wellesley, MA: Wellesley-Cambridge Press, 1996.

Vaidyanathan, P. P. *Multirate Systems and Filter Banks*. Englewood Cliffs, NJ: Prentice Hall, 1993.

## Supported Data Types

- Double-precision floating point

## See Also

Dyadic Synthesis Filter Bank	DSP System Toolbox
Wavelet Analysis (Obsolete)	DSP System Toolbox
wfilters	Wavelet Toolbox

# Window Function

## Purpose


Compute and/or apply window to input signal

## Library

Signal Operations

dspsigops

## Description



The Window Function block computes a window and/or applies a window to an input signal. The input signal can be a matrix or an N-D array.

## Operation Modes

The Window Function block has three modes of operation that you can select via the **Operation** parameter. In each mode, the block first creates a window vector  $w$  by sampling the window specified in the **Window type** parameter at  $M$  discrete points. The operation modes are:

- Apply window to input

In this mode, the block computes an  $M$ -by-1 window vector  $w$  and applies it to the input. The output  $y$  always has the same dimension as the input.

When the input is an  $M$ -by- $N$  matrix  $u$ , the window is multiplied element-wise with each of the  $N$  channels in the input matrix  $u$ . This is equivalent to the following MATLAB code:

```
y = repmat(w,1,N) .* u           % Equivalent MATLAB code
```

The window is always applied to the first dimension:

$$y(i, j, \dots, k) = w(i) * u(i, j, \dots, k) \quad i = 1, \dots, M, \quad j = 1, \dots, N, \quad \dots, \quad k = 1, \dots, P$$

A length- $M$  unoriented vector input is treated as an  $M$ -by-1 matrix.

- Generate window

In this mode, the block generates an unoriented window vector  $w$  with length  $M$  specified by the **Window length** parameter. The In port is disabled for this mode.

- **Generate and apply window**

In this mode, the block generates an  $M$ -by-1 window vector  $w$  and applies it to the input. The block produces two outputs:

- At the Out port, the block produces the result of the multiplication  $y$ , which has the same dimension as the input.
- At the Win port, the block produces the  $M$ -by-1 window vector  $w$ .

When the input is an  $M$ -by- $N$  matrix  $u$ , the window is multiplied element-wise with each of the  $N$  channels in the input matrix  $u$ . This is equivalent to the following MATLAB code:

```
y = repmat(w,1,N) .* u      % Equivalent MATLAB code
```

The window is always applied to the first dimension:

$$y(i,j,\dots,k) = w(i) * u(i,j,\dots,k) \quad i = 1,\dots,M, \quad j = 1,\dots,N, \quad \dots, \quad k = 1,\dots,P$$

A length- $M$  1-D vector input is treated as an  $M$ -by-1 matrix.

## Window Type

The following table lists the available window types. For complete information about the window functions, consult the Signal Processing Toolbox documentation.

# Window Function

---

Window Type	Description
Bartlett	Computes a Bartlett window. $w = \text{bartlett}(M)$
Blackman	Computes a Blackman window. $w = \text{blackman}(M)$
Boxcar	Computes a rectangular window. $w = \text{rectwin}(M)$
Chebyshev	Computes a Chebyshev window with stopband ripple $R$ . $w = \text{chebwin}(M, R)$
Hamming	Computes a Hamming window. $w = \text{hamming}(M)$
Hann	Computes a Hann window (also known as a Hanning window). $w = \text{hann}(M)$
Hanning	Obsolete. This window type is included only for compatibility with older models. Use the Hann <b>Window type</b> instead of Hanning whenever possible.
Kaiser	Computes a Kaiser window with the Kaiser parameter $\beta$ . $w = \text{kaiser}(M, \beta)$

Window Type	Description
Taylor	Computes a Taylor window.  <code>w = taylorwin(M)</code>
Triang	Computes a triangular window.  <code>w = triang(M)</code>
User Defined	Computes the user-defined window function specified by the entry in the <b>Window function name</b> parameter, <code>usrwin</code> .  <code>w = usrwin(M)</code> % Window takes no extra parameters <code>w = usrwin(M,x<sub>1</sub>,...,x<sub>n</sub>)</code> % Window takes extra parameters {x <sub>1</sub> ... x <sub>n</sub> }

## Window Sampling

For the generalized-cosine windows (Blackman, Hamming, Hann, and Hanning), the **Sampling** parameter determines whether the window samples are computed in a periodic or a symmetric manner. For example, when **Sampling** is set to `Symmetric`, a Hamming window of length  $M$  is computed as

```
w = hamming(M) % Symmetric (aperiodic) window
```

When **Sampling** is set to `Periodic`, the same window is computed as

```
w = hamming(M+1) % Periodic (asymmetric) window  
w = w(1:M)
```


# Window Function

---

## **Fixed-Point Data Types**

The following diagram shows the data types used within the Window Function block for fixed-point signals for each of the three operating modes.

## Apply window to input




The input data type comes from the driving block. You can set the window, product output, and output data types in the block dialog. In this mode, the window vector is not output from the block.

## Generate window



In this mode, the block acts as a source. The window vector is output in the window data type you specify in the block dialog.

## Generate and apply window



The input data type comes from the driving block. You can set the window, product output, and output data types in the block dialog. In this mode, the window vector is output from the block.

You can set the window, product output, and output data types in the block dialog box. For more information see the “Dialog Box” on page 2-1803 section.


# Window Function

## Examples

The following model uses the Window Function block to generate and apply a Hamming window to a 3-dimensional input array.

In this example, set the **Operation** mode of the Window Function block to **Generate and apply window**, so the block provides two outputs: the window vector  $w$  at the Win port, and the result of the multiplication  $y$  at the Out port.


Open the model by typing `ex_windowfunction_ref` at the MATLAB command line, and run it.



- The length of the first dimension of the input array is 10, so the Window Function block generates and outputs a Hamming window vector of length 10. To see the window vector generated by the Window Function block, type `w` at the MATLAB command line.
- To see the result of the multiplication, type `y` at the MATLAB command line.

## Dialog Box

The **Main** pane of the Window Function block dialog appears as follows.



# Window Function

---

## Operation

Specify the block's operation, as discussed in "Operation Modes" on page 2-1796. The port configuration of the block is updated to match the setting of this parameter.

## Window type

Specify the window type to apply, as listed in "Window Type" on page 2-1797. Tunable in simulation only.

## Sampling

Specify the window sampling for generalized-cosine windows. This parameter is only visible when you select **Blackman**, **Hamming**, **Hann**, or **Hanning** for the **Window type** parameter. Tunable in simulation only.

## Sample Mode

Specify the sample mode for the block, **Continuous** or **Discrete**, when it is in **Generate Window** mode. In the **Apply window to output** and **Generate and apply window** modes, the block inherits the sample time from its driving block. Therefore, this parameter is only visible when you select **Generate window** for the **Operation** parameter.

## Sample time

Specify the sample time for the block when it is in **Generate window** and **Discrete** modes. In **Apply window to output** and **Generate and apply window** modes, the block inherits the sample time from its driving block. This parameter is only visible when you select **Discrete** for the **Sample Mode** parameter.

## Window length

Specify the length of the window to apply. This parameter is only visible when you select **Generate window** for the **Operation** parameter. Otherwise, the window vector length is computed to match the length of the first dimension of the input.

## Stopband attenuation in dB

Specify the level of stopband attenuation,  $R_s$ , in decibels. This parameter is only visible when you select **Chebyshev** for the **Window type** parameter. Tunable in simulation only.

## **Beta**

Specify the Kaiser window  $\beta$  parameter. Increasing  $\beta$  widens the mainlobe and decreases the amplitude of the window sidelobes in the window's frequency magnitude response. This parameter is only visible when you select Kaiser for the **Window type** parameter. Tunable in simulation only.

## **Number of sidelobes**

Specify the number of sidelobes as a scalar integer value greater than zero. This parameter is only visible when you select Taylor for the **Window type** parameter.

## **Maximum sidelobe level relative to mainlobe (dB)**

Specify, in decibels, the maximum sidelobe level relative to the mainlobe. This parameter must be a scalar less than or equal to zero. The default value of  $-30$  produces sidelobes with peaks 30 dB down from the mainlobe peak. This parameter is only visible when you select Taylor for the **Window type** parameter.

## **Window function name**

Specify the name of the user-defined window function to be calculated by the block. This parameter is only visible when you select User defined for the **Window type** parameter.

## **Specify additional arguments to the hamming function**

Select to enable the **Cell array of additional arguments** parameter, when the user-defined window requires parameters other than the window length. This parameter is only visible when you select User defined for the **Window type** parameter.

## **Cell array of additional arguments**

Specify the extra parameters required by the user-defined window function, besides the window length. This parameter is only available when you select the **Specify additional arguments to the hamming function** parameter. The entry must be a cell array.

The **Data Types** pane of the Window Function block dialog is discussed in the following sections:

# Window Function


---

“Parameters for Generate Window Only Mode” on page 2-1806

“Parameters for Apply Window Modes” on page 2-1808

## Parameters for Generate Window Only Mode

The **Data Types** pane of the Window Function block dialog appears as follows when the **Operation** parameter is set to Generate window.



### Window data type

Specify the window data type in one of the following ways:

- Choose **double** or **single** from the list.

- Choose **Fixed-point** to specify the window data type and scaling in the **Signed**, **Word length**, **Set fraction length in output to**, and **Fraction length** parameters.
- Choose **User-defined** to specify the window data type and scaling in the **User-defined data type**, **Set fraction length in output to**, and **Fraction length** parameters.
- Choose **Inherit via back propagation** to set the window data type and scaling to match the following block.

## **Signed**

Select to output a signed fixed-point signal. Otherwise, the signal is unsigned.

## **Word length**

Specify the word length, in bits, of the fixed-point window data type. This parameter is only visible when you select **Fixed-point** for the **Window data type** parameter.

## **User-defined data type**

Specify any built-in or fixed-point data type. You can specify fixed-point data types using the Simulink Fixed Point functions `sfix`, `ufix`, `sint`, `uint`, `sfrac`, and `ufrac`. This parameter is only visible when you select **User-defined** for the **Window data type** parameter.

## **Set fraction length in output to**

Specify the scaling of the fixed-point window data type by either of the following two methods:

- Choose **Best precision** to have the window data type scaling automatically set such that the output signal has the best possible precision.
- Choose **User-defined** to specify the window data type scaling in the **Fraction length** parameter.

This parameter is only visible when you select **Fixed-point** or **User-defined** for the **Window data type** parameter, and when the specified window data type is a fixed-point data type.

# Window Function


---

## **Fraction length**

Specify the fraction length, in bits, of the fixed-point window data type. This parameter is only visible when you select **Fixed-point** or **User-defined** for the **Window data type** parameter and **User-defined** for the **Set fraction length in output to** parameter.

## **Parameters for Apply Window Modes**

The **Data Types** pane of the Window Function block dialog appears as follows when the **Operation** parameter is set to either **Apply window to input** or **Generate and apply window**.



## Rounding mode

Select the rounding mode for fixed-point operations.

# Window Function

---

The window vector  $w$  does not obey this parameter; it always rounds to Nearest.

---

**Note** The **Rounding mode** and **Overflow mode** settings have no effect on numerical results when both of the following conditions exist:

- **Product output data type** is `Inherit` via internal rule
  - **Output data type** is `Same` as product output
- With these data type settings, the block is effectively operating in full precision mode.
- 

## Overflow mode

Select the overflow mode for fixed-point operations.

The window vector  $w$  does not obey this parameter; it is always saturated.

## Window

Choose how you specify the word length and fraction length of the window vector  $w$ .

When you select `Same word length as input`, the word length of the window vector elements is the same as the word length of the input. The fraction length is automatically set to the best precision possible.

When you select `Specify word length`, you can enter the word length of the window vector elements in bits. The fraction length is automatically set to the best precision possible.

When you select `Binary point scaling`, you can enter the word length and the fraction length of the window vector elements in bits.

When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the window vector elements. This block requires power-of-two slope and a bias of zero.

The window vector does not obey the **Rounding mode** and **Overflow mode** parameters; it is always saturated and rounded to Nearest.

## Product output

Use this parameter to specify how you want to designate the product output word and fraction lengths. See “Fixed-Point Data Types” on page 2-1690 for illustrations depicting the use of the product output data type in this block:

- When you select **Inherit via internal rule**, the product output word length and fraction length are calculated automatically. For information about how the product output word and fraction lengths are calculated when an internal rule is used, see “Inherit via Internal Rule”.
- When you select **Same as input**, these characteristics match those of the input to the block.
- When you select **Binary point scaling**, you can enter the word length and the fraction length of the product output, in bits.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the product output. This block requires power-of-two slope and a bias of zero.

## Output

Choose how you specify the word length and fraction length of the output of the block:

- When you select **Same as product output**, these characteristics match those of the product output.
- When you select **Same as input**, these characteristics match those of the input to the block.

# Window Function

---

- When you select **Binary point scaling**, you can enter the word length and the fraction length of the output, in bits.
- When you select **Slope and bias scaling**, you can enter the word length, in bits, and the slope of the output. This block requires power-of-two slope and a bias of zero.

## Lock data type settings against changes by the fixed-point tools

Select this parameter to prevent the fixed-point tools from overriding the data types you specify on the block mask.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point (signed only)</li><li>• 8-, 16-, and 32-bit signed integers</li></ul>
Win	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li><li>• Fixed point</li><li>• 8-, 16-, and 32-bit integers</li></ul>

## See Also

FFT	DSP System Toolbox
bartlett	Signal Processing Toolbox
blackman	Signal Processing Toolbox
rectwin	Signal Processing Toolbox


<code>chebwin</code>	Signal Processing Toolbox
<code>hamming</code>	Signal Processing Toolbox
<code>hann</code>	Signal Processing Toolbox
<code>kaiser</code>	Signal Processing Toolbox
<code>taylorwin</code>	Signal Processing Toolbox
<code>triang</code>	Signal Processing Toolbox

# Yule-Walker AR Estimator

**Purpose** Compute estimate of autoregressive (AR) model parameters using Yule-Walker method

**Library** Estimation / Parametric Estimation  
dsparest3

## Description



The Yule-Walker AR Estimator block uses the Yule-Walker AR method, also called the autocorrelation method, to fit an autoregressive (AR) model to the windowed input data by minimizing the forward prediction error in the least squares sense. This formulation leads to the Yule-Walker equations, which are solved by the Levinson-Durbin recursion. Block outputs are always nonsingular.

The Yule-Walker AR Estimator block can output the AR model coefficients as polynomial coefficients, reflection coefficients, or both. Each channel of the input is a sample-based vector (row, column, or 1-D) or frame-based vector (column only) representing a frame of consecutive time samples from a signal that is assumed to be the output of an AR system driven by white noise. The block computes the normalized estimate of the AR system parameters,  $A(z)$ , independently for each successive input frame.

$$H(z) = \frac{\sqrt{G}}{A(z)} = \frac{\sqrt{G}}{1 + a(2)z^{-1} + \dots + a(p+1)z^{-p}}$$

When you select **Inherit estimation order from input dimensions**, the order  $p$  of the all-pole model is one less than the length of each input channel. Otherwise, the order is the value specified by the **Estimation order** parameter. To guarantee a valid output, you must set the **Estimation order** parameter to be a scalar less than or equal to half the input channel length. The Yule-Walker AR Estimator and Burg AR Estimator blocks return similar results for large frame sizes.


When **Output(s)** is set to A, port A is enabled. For each channel, port A outputs a column of length  $p+1$  that contains the normalized estimate of the AR model coefficients in descending powers of  $z$

[1 a(2) ... a(p+1)]

When **Output(s)** is set to K, port K is enabled. For each channel, port K outputs a length- $p$  column whose elements are the AR model reflection coefficients. When **Output(s)** is set to A and K, both port A and K are enabled, and each port outputs the respective AR model coefficients for each channel.

The square of the model gain,  $G$ , is provided at port G.  $G$  is a scalar for each channel.

See the Burg AR Estimator block reference page for a comparison of the Burg AR Estimator, Covariance AR Estimator, Modified Covariance AR Estimator, and Yule-Walker AR Estimator blocks.



## Dialog Box

### Output(s)

The type of AR model coefficients output by the block. The block can output polynomial coefficients (A), reflection coefficients (K), or both (A and K).

### Inherit estimation order from input dimensions

When selected, sets the estimation order  $p$  to one less than the length of each input channel.

# Yule-Walker AR Estimator

---

## Estimation order

The order of the AR model,  $p$ . This parameter is enabled when you do not select **Inherit estimation order from input dimensions**.

## References

Kay, S. M. *Modern Spectral Estimation: Theory and Application*. Englewood Cliffs, NJ: Prentice-Hall, 1988.

Marple, S. L., Jr., *Digital Spectral Analysis with Applications*. Englewood Cliffs, NJ: Prentice-Hall, 1987.

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
A	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
K	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
G	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

## See Also


Burg AR Estimator	DSP System Toolbox
Covariance AR Estimator	DSP System Toolbox
Modified Covariance AR Estimator	DSP System Toolbox
Yule-Walker Method	DSP System Toolbox
aryule	Signal Processing Toolbox

# Yule-Walker IIR Filter Design (Obsolete)

**Purpose** Design and apply IIR filter

**Library** dspobslib

## Description



---

**Note** The Yule-Walker IIR Filter Design block is still supported but is likely to be obsoleted in a future release. We strongly recommend replacing this block with the Digital Filter block.

---

The Yule-Walker IIR Filter Design block designs a recursive (ARMA) digital filter with arbitrary multiband magnitude response, and applies it to a discrete-time input using the Direct-Form II Transpose Filter block. The filter design, which uses the Signal Processing Toolbox `yulewalk` function, performs a least-squares fit to the specified frequency response.




An  $M$ -by- $N$  sample-based matrix input is treated as  $M*N$  independent channels, and an  $M$ -by- $N$  frame-based matrix input is treated as  $N$  independent channels. In both cases, the block filters each channel independently over time, and the output has the same size and frame status as the input.

The **Band-edge frequency vector** parameter is a vector of frequency points in the range 0 to 1, where 1 corresponds to half the sample frequency. The first element of this vector must be 0 and the last element 1, and intermediate points must appear in ascending order. The **Magnitudes at these frequencies** parameter is a vector containing the desired magnitude response at the points specified in the **Band-edge frequency vector**.

Note that, unlike the Remez FIR Filter Design block, each frequency-magnitude pair specifies the junction of two adjacent frequency bands, so there are no “don’t care” regions.

# Yule-Walker IIR Filter Design (Obsolete)

Band edge frequency = [0.0 0.3 0.4 0.6 0.7 1.0]  
 Magnitudes [0.0 1.0 0.0 0.0 0.5 0.5]  
 Band:  $\underbrace{\quad}_L \underbrace{\quad}_I \underbrace{\quad}_T \underbrace{\quad}_F$




When specifying the **Band-edge frequency vector** and **Magnitudes at these frequencies** vectors, avoid excessively sharp transitions from passband to stopband. You may need to experiment with the slope of the transition region to get the best filter design.

For more details on the Yule-Walker filter design algorithm, see the description of the `yulewalk` function in the Signal Processing Toolbox documentation.

# Yule-Walker IIR Filter Design (Obsolete)

## Dialog Box



### Filter order

The order of the filter.

### Band-edge frequency vector

A vector of frequency points. The value 1 corresponds to half the sample frequency. The first element of this vector must be 0 and the last element 1. Tunable.

### Magnitudes at these frequencies

A vector of frequency response magnitudes corresponding to the points in the **Band-edge frequency vector**. This vector must be the same length as the **Band-edge frequency vector**. Tunable.

## References

Oppenheim, A. V. and R. W. Schaffer. *Discrete-Time Signal Processing*. Englewood Cliffs, NJ: Prentice Hall, 1989.

Proakis, J. and D. Manolakis. *Digital Signal Processing*. 3rd ed. Englewood Cliffs, NJ: Prentice-Hall, 1996.


# Yule-Walker Method

---

**Purpose** Power spectral density estimate using Yule-Walker method

**Library** Estimation / Power Spectrum Estimation  
dspspect3

## Description



The Yule-Walker Method block estimates the power spectral density (PSD) of the input using the Yule-Walker AR method. This method, also called the *autocorrelation method*, fits an autoregressive (AR) model to the windowed input data. It does so by minimizing the forward prediction error in the least squares sense. This formulation leads to the Yule-Walker equations, which the Levinson-Durbin recursion solves. Block outputs are always nonsingular.

The input is a sample-based vector (row, column, or 1-D) or frame-based vector (column only). This input represents a frame of consecutive time samples from a single-channel signal. The block outputs a column vector containing the estimate of the power spectral density of the signal at  $N_{fft}$  equally spaced frequency points. The frequency points are in the range  $[0, F_s)$ , where  $F_s$  is the sampling frequency of the signal.

When you select **Inherit estimation order from input dimensions**, the order of the all-pole model is one less than the input frame size. Otherwise, the **Estimation order** parameter value specifies the order. To guarantee a valid output, the **Estimation order** parameter must be less than or equal to half the input vector length. The block computes the spectrum from the FFT of the estimated AR model parameters.

Selecting the **Inherit FFT length from estimation order** parameter specifies that  $N_{fft}$  is one greater than the estimation order. Clearing the **Inherit FFT length from estimation order** check box allows you to use the **FFT length** parameter to specify  $N_{fft}$  as a power of 2. The block zero-pads or wraps the input to  $N_{fft}$  before computing the FFT. The output is always sample based.


When you select the **Inherit sample time from input** check box, the block computes the frequency data from the sample period of the input signal. For the block to produce valid output, the following conditions must hold:

- The input to the block is the original signal, with no samples added or deleted (by insertion of zeros, for example).
- The sample period of the time-domain signal in the simulation equals the sample period of the original time series.

If these conditions do not hold, clear the **Inherit sample time from input** check box. You can then specify a sample time using the **Sample time of original time series** parameter.

See the Burg Method block reference for a comparison of the Burg Method, Covariance Method, Modified Covariance Method, and Yule-Walker AR Estimator blocks. The Yule-Walker AR Estimator and Burg Method blocks return similar results for large buffer lengths.

# Yule-Walker Method



## Dialog Box

### **Inherit estimation order from input dimensions**

When you select this option, it sets the estimation order to one less than the length of the input vector.

### **Estimation order**

Specify the order of the AR model. This parameter is only visible when you clear the **Inherit estimation order from input dimensions** check box.

### **Inherit FFT length from estimation order**

When you select the **Inherit FFT length from estimation order** check box, the FFT length is one greater than the estimation order. To specify the number of points on which to perform the FFT, clear the **Inherit FFT length from estimation order** check box. You can then specify a power-of-two FFT length using the **FFT length** parameter.

## FFT length

Enter the number of data points on which to perform the FFT,  $N_{fft}$ . When  $N_{fft}$  is larger than the input frame size, the block zero-pads each frame as needed. When  $N_{fft}$  is smaller than the input frame size, the block wraps each frame as needed. This parameter becomes visible only when you clear the **Inherit FFT length from input dimensions** check box.

## Inherit sample time from input

When you select the **Inherit sample time from input** check box, the block computes the frequency data from the sample period of the input signal. For the block to produce valid output, the following conditions must hold:

- The input to the block is the original signal, with no samples added or deleted (by insertion of zeros, for example).
- The sample period of the time-domain signal in the simulation equals the sample period of the original time series.

If these conditions do not hold, clear the **Inherit sample time from input** check box. You can then specify a sample time using the **Sample time of original time series** parameter.

## Sample time of original time series

Specify the sample time of the original time-domain signal. This parameter becomes visible only when you clear the **Inherit sample time from input** check box.

## References

Kay, S. M. *Modern Spectral Estimation: Theory and Application*. Englewood Cliffs, NJ: Prentice-Hall, 1988.

Marple, S. L. Jr., *Digital Spectral Analysis with Applications*. Englewood Cliffs, NJ: Prentice-Hall, 1987.

Orfanidis, S. J. *Introduction to Signal Processing*. Englewood Cliffs, NJ: Prentice-Hall, 1995.

# Yule-Walker Method

---

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>
Output	<ul style="list-style-type: none"><li>• Double-precision floating point</li><li>• Single-precision floating point</li></ul>

The output data type is the same as the input data type.

## See Also

Burg Method	DSP System Toolbox
Covariance Method	DSP System Toolbox
Levinson-Durbin	DSP System Toolbox
Autocorrelation LPC	DSP System Toolbox
Short-Time FFT	DSP System Toolbox
Yule-Walker AR Estimator	DSP System Toolbox
<code>spectrum.yulear</code>	Signal Processing Toolbox

See “Spectral Analysis” for related information.

## Purpose


Count number of times signal crosses zero in single time step

## Library

Signal Operations

dspsigops

## Description



The Zero Crossing block concludes that a signal in a given channel has passed through zero if it meets any of the following criteria, where  $x_i$  is the current signal value,  $x_{i-1}$  is the previous signal value, and so on:

- $x_i < 0$  and  $x_{i-1} > 0$
- $x_i > 0$  and  $x_{i-1} < 0$
- For some positive integer  $L$ ,  $x_i < 0$ ,  $x_{i-l} = 0$ , and  $x_{i-L-1} > 0$ , where  $0 \leq l \leq L$ .
- For some positive integer  $L$ ,  $x_i > 0$ ,  $x_{i-l} = 0$ , and  $x_{i-L-1} < 0$ , where  $0 \leq l \leq L$ .

For the first input value,  $x_{i-1}$  and  $x_{i-2}$  are zero. The block outputs the number of times the signal crosses zero in a single time step at the Cnt port.

The input to this block must be a real-valued fixed-point or floating-point signal. If you set the **Input processing** parameter to **Elements as channels (sample based)**, the block treats each element of the input as a time-varying channel. If you set the **Input processing** parameter to **Columns as channels (frame based)**, the block treats each column of the input as an independent channel.

## Examples

The following example, `ex_zero_crossing` illustrates the behavior of the Zero Crossing block.


To run the model for one time step, the **Stop time** is set to 0.

1

Run the model.

# Zero Crossing

Because the signal passes through zero once during the first time step, the Zero Crossing block finds one zero crossing. The number of detected zero crossings in the first time step is shown in the Display block in the following figure.




## 2

To run the model for two time steps, change the simulation **Stop time** to 1. To do so, open the Configuration Parameters dialog box by selecting **Model Configuration Parameters** from the **Simulation** menu. In the **Solver** pane, set **Stop time** to 1.


## 3

Run the model.

The Zero Crossing block remembers that the last value of the last frame was 3. Therefore, the signal passes through zero twice during the second time step. It passes through zero while going from 3 to -3, and it passes through zero again while going from -3 to 3. The Zero Crossing block finds two zero crossings in the second time step as shown in the Display block in the following figure.



## Dialog Box



### Input processing

Specify how the block should process the input. You can set this parameter to one of the following options:

- **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
- **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.

---

**Note** The Inherited (this choice will be removed - see release notes) option will be removed in a future release. See “Frame-Based Processing” in the *DSP System Toolbox Release Notes* for more information.

---

# Zero Crossing

---

## Supported Data Types

Port	Supported Data Types
Input	<ul style="list-style-type: none"><li>• Double-precision floating-point</li><li>• Single-precision floating-point</li><li>• Fixed point (signed and unsigned)</li><li>• 8-, 16-, and 32-bit signed integers</li><li>• 8-, 16-, and 32-bit unsigned integers</li></ul>
Cnt	<ul style="list-style-type: none"><li>• 32-bit unsigned integers</li></ul>

## See Also

Hit Crossing

Simulink

# System object Reference

---

Define New System Objects (p. 3-2)	Define new kinds of System objects
Estimation (p. 3-3)	Perform spectrum estimates and autoregressive modeling
Filtering (p. 3-4)	Design, create, and work with filters
Math Functions (p. 3-5)	Perform linear algebra and basic math calculations
Quantizers (p. 3-6)	Design and implement quantization schemes
Signal Management (p. 3-7)	Perform basic signal processing operations
Signal Operations (p. 3-8)	Control signal attributes, buffer signals, and index signals
Sinks (p. 3-9)	View or log signals
Sources (p. 3-10)	Generate discrete-time signals
Measurements and Statistics (p. 3-11)	Perform statistical computations on signals
Transforms (p. 3-12)	Compute transforms

## Define New System Objects

<code>getDiscreteStateImpl</code>	Discrete state property values
<code>getNumInputsImpl</code>	Number of input arguments passed to step and setup methods
<code>getNumOutputsImpl</code>	Number of outputs returned by method
<code>isDoneImpl</code>	End-of-data flag
<code>isInactivePropertyImpl</code>	Active or inactive flag for properties
<code>loadObjectImpl</code>	Load saved System object from MAT file
<code>matlab.System</code>	Base class for System objects
<code>matlab.system.mixin.FiniteSource</code>	Finite source mixin class
<code>matlab.system.StringSet</code>	Set of valid string values
<code>processTunedPropertiesImpl</code>	Action when tunable properties change
<code>releaseImpl</code>	Release resources
<code>resetImpl</code>	Reset System object™ states
<code>saveObjectImpl</code>	Save System object in MAT file
<code>setProperties</code>	Set property values from name-value pair inputs
<code>setupImpl</code>	Initialize System object
<code>stepImpl</code>	System output and state update equations
<code>validateInputsImpl</code>	Validate inputs to step method
<code>validatePropertiesImpl</code>	Validate property values

## Estimation

<code>dsp.BurgAREstimator</code>	Estimate of autoregressive (AR) model parameters using Burg method
<code>dsp.BurgSpectrumEstimator</code>	Parametric spectral estimate using Burg method
<code>dsp.CepstralToLPC</code>	Convert cepstral coefficients to linear prediction coefficients
<code>dsp.LevinsonSolver</code>	Solve linear system of equations using Levinson-Durbin recursion
<code>dsp.LPCToAutocorrelation</code>	Convert linear prediction coefficients to autocorrelation coefficients
<code>dsp.LPCToCepstral</code>	Convert linear prediction coefficients to cepstral coefficients
<code>dsp.LPCToLSF</code>	Convert linear prediction coefficients to line spectral frequencies
<code>dsp.LPCToLSP</code>	Convert linear prediction coefficients to line spectral pairs
<code>dsp.LPCToRC</code>	Convert linear prediction coefficients to reflection coefficients
<code>dsp.LSFToLPC</code>	Convert line spectral frequencies to linear prediction coefficients
<code>dsp.LSPToLPC</code>	Convert line spectral pairs to linear prediction coefficients
<code>dsp.RCToAutocorrelation</code>	Convert reflection coefficients to autocorrelation coefficients
<code>dsp.RCToLPC</code>	Convert reflection coefficients to linear prediction coefficients

## Filtering

<code>dsp.AllpoleFilter</code>	IIR Filter with no zeros
<code>dsp.BiquadFilter</code>	IIR filter using biquadratic structures
<code>dsp.BlockLMSFilter</code>	Output, error, and weights using Block LMS adaptive algorithm
<code>dsp.CICDecimator</code>	Decimate input using Cascaded Integrator-Comb filter
<code>dsp.CICInterpolator</code>	Interpolate signal using Cascaded Integrator-Comb filter
<code>dsp.DigitalFilter</code>	Static or time-varying digital filter
<code>dsp.DyadicAnalysisFilterBank</code>	Dyadic analysis filter bank
<code>dsp.DyadicSynthesisFilterBank</code>	Reconstruct signals from subbands
<code>dsp.FIRDecimator</code>	FIR polyphase decimator
<code>dsp.FIRFilter</code>	Static or time-varying FIR filter
<code>dsp.FIRInterpolator</code>	Polyphase FIR interpolator
<code>dsp.FIRRateConverter</code>	Sample rate converter
<code>dsp.IIRFilter</code>	Infinite Impulse Response (IIR) filter
<code>dsp.LMSFilter</code>	LMS adaptive filter
<code>dsp.SubbandAnalysisFilter</code>	Decompose signal into high-frequency and low-frequency subbands
<code>dsp.SubbandSynthesisFilter</code>	Reconstruct signal from high-frequency and low-frequency subbands

## Math Functions

<code>dsp.ArrayVectorAdder</code>	Add array to vector along specified dimension
<code>dsp.ArrayVectorDivider</code>	Divide array by vector along specified dimension
<code>dsp.ArrayVectorMultiplier</code>	Multiply array by vector along specified dimension
<code>dsp.ArrayVectorSubtractor</code>	Subtract vector from array along specified dimension
<code>dsp.CumulativeProduct</code>	Cumulative product of channel, column, or row elements
<code>dsp.CumulativeSum</code>	Cumulative sum of channel, column, or row elements
<code>dsp.LDLFactor</code>	Factor square Hermitian positive definite matrices into components
<code>dsp.LevinsonSolver</code>	Solve linear system of equations using Levinson-Durbin recursion
<code>dsp.LowerTriangularSolver</code>	Solve lower-triangular matrix equation
<code>dsp.LUFactor</code>	Factor square matrix into lower and upper triangular matrices
<code>dsp.Normalizer</code>	Vector normalization along specified dimension
<code>dsp.UpperTriangularSolver</code>	Solve upper-triangular matrix equation

## Quantizers

<code>dsp.ScalarQuantizerDecoder</code>	Convert each index value into quantized output value
<code>dsp.ScalarQuantizerEncoder</code>	Associate input value with index value of quantization region
<code>dsp.UniformDecoder</code>	Decode integer input into floating-point output
<code>dsp.UniformEncoder</code>	Quantize and encode floating-point input into integer output
<code>dsp.VectorQuantizerDecoder</code>	Vector quantizer codeword for given index value
<code>dsp.VectorQuantizerEncoder</code>	Vector quantization encoding

## Signal Management

dsp.Buffer

Buffer input signal

dsp.Counter

Count up or down through specified range of numbers

dsp.DelayLine

Rebuffer sequence of inputs with one-sample shift

## Signal Operations

<code>dsp.Convolver</code>	Convolution of two inputs
<code>dsp.Delay</code>	Delay input by specified number of samples or frames
<code>dsp.DigitalDownConverter</code>	Digitally downconvert input signal
<code>dsp.DigitalUpConverter</code>	Digitally upconvert input signal
<code>dsp.Interpolator</code>	Linear or FIR interpolation
<code>dsp.NCO</code>	Generate real or complex sinusoidal signals
<code>dsp.PeakFinder</code>	Determine extrema (maxima or minima) in input signal
<code>dsp.PhaseUnwrapper</code>	Unwrap signal phase
<code>dsp.VariableFractionalDelay</code>	Delay input by time-varying fractional number of sample periods
<code>dsp.VariableIntegerDelay</code>	Delay input by time-varying integer number of sample periods
<code>dsp.Window</code>	Window object
<code>dsp.ZeroCrossingDetector</code>	Zero crossing detector

## Sinks

<code>dsp.AudioFileWriter</code>	Write audio samples to audio file
<code>dsp.AudioPlayer</code>	Play audio data using computer's audio device
<code>dsp.MatFileWriter</code>	Write MAT file
<code>dsp.SignalSink</code>	Log simulation data in buffer
<code>dsp.SpectrumAnalyzer</code>	Display frequency spectrum of time-domain signals
<code>dsp.TimeScope</code>	Time domain signal display
<code>dsp.UDPSender</code>	Send UDP packets to network
<code>signalblks.MultimediaFileWriter</code>	Write video frames, audio samples, or both to multimedia file

## Sources

<code>dsp.AudioFileReader</code>	Read audio samples from audio file
<code>dsp.AudioRecorder</code>	Record audio data using computer's audio device
<code>dsp.Chirp</code>	Generate swept-frequency cosine (chirp) signal
<code>dsp.MatFileReader</code>	Read MAT file
<code>dsp.SignalSource</code>	Import variable from workspace
<code>dsp.SineWave</code>	Discrete-time sinusoid
<code>dsp.UDPReceiver</code>	Receive UDP packets from network
<code>signalblks.MultimediaFileReader</code>	Read video frames, audio samples, or both from multimedia file

## Measurements and Statistics

dsp.Autocorrelator	Autocorrelation sequence
dsp.Crosscorrelator	Cross-correlation of two inputs
dsp.Histogram	Histogram of input or sequence of inputs
dsp.Maximum	Find maximum value of input or sequence of inputs
dsp.Mean	Find mean value of input or sequence of inputs
dsp.Median	Median value of input
dsp.Minimum	Find minimum values of input or sequence of inputs
dsp.PeakToPeak	Peak-to-peak value
dsp.PeakToRMS	Peak-to-root-mean-square value of vector
dsp.PulseMetrics	Pulse metrics of bilevel waveforms
dsp.RMS	Root mean square of vector elements
dsp.StandardDeviation	Standard deviation of input or sequence of inputs
dsp.StateLevels	State-level estimation for bilevel rectangular waveform
dsp.TransitionMetrics	Transition metrics of bilevel waveforms
dsp.Variance	Variance of input or sequence of inputs

## Transforms

<code>dsp.AnalyticSignal</code>	Analytic signals of discrete-time inputs
<code>dsp.DCT</code>	Discrete cosine transform (DCT)
<code>dsp.FFT</code>	Discrete Fourier transform
<code>dsp.IDCT</code>	Inverse discrete cosine transform (IDCT)
<code>dsp.IFFT</code>	Inverse discrete Fourier transform (IDFFT)

# Analysis Methods for Filter System Objects

---

## Analysis Methods for Filter System Objects

Method	Description
Single-rate and Multirate Analysis	
fvtool	Filter visualization tool
info	Filter information
freqz	Frequency response of a discrete-time filter
phasez	Phase response of a discrete-time filter
zerophase	Zero-phase response of a discrete-time filter
grpdelay	Group delay of a discrete-time filter
phasedelay	Phase delay of a discrete-time filter
impz	Impulse response of a discrete-time filter
stepz	Step response of a discrete-time filter
zplane	Pole/Zero plot
cost	Cost estimate
measure	measure filter response
order	Filter order
firtype	Determine the type (1–4) of a linear phase FIR filter
coeffs	Return filter coefficients
Multirate Analysis	
polyphase	Polyphase decomposition of multirate filters
gain	Gain of a Cascaded Integrator-Comb (CIC) filter

<b>Method</b>	<b>Description</b>
Second-order Sections	
scale	Scale second-order sections
scalecheck	Check scale of second-order sections
scaleopts	Create options object for sos scaling
cumsec	Vector of cumulative second-order section filters
reorder	Reorder second-order sections
sos	Convert IIR filter to Biquad filter
Code Generation	
realizemdl	Filter realization diagram
Fixed-point (supported by FIRFilter, IIRFilter, AllpoleFilter, and BiquadFilter only)	
noisepsd	Power spectral density of filter output due to roundoff noise
noisepsdopts	Create options object for noisepsd computation
freqrespest	Frequency response estimate via filtering
freqrespopts	Create options object for frequency response estimate
Other	
isallpass	True for allpass discrete-time filter
islinphase	True for linear discrete-time filter
ismaxphase	True if maximum phase
isminphase	True if minimum phase
isreal	True for discrete-time filter with real coefficients
isstable	True if the filter is stable

<b>Method</b>	<b>Description</b>
isfir	True if the filter is FIR
issos	True if filter is in second order sections form
specifyall	Specify all fixed-point properties

# Alphabetical List

---

# dsp.AllpoleFilter

---

**Purpose** IIR Filter with no zeros

**Description** The `AllpoleFilter` object filters each channel of the input using Allpole filter implementations.

To filter each channel of the input:

- 1 Define and set up your Allpole filter. See “Construction” on page 5-2.
- 2 Call `step` to filter each channel of the input according to the properties of `dsp.AllpoleFilter`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `HAllpole = dsp.AllpoleFilter` returns an Allpole filter System object, `HAllpole`, which independently filters each channel of the input over successive calls to the `step` method. This System object uses a specified Allpole filter implementation.

`HAllpole = dsp.AllpoleFilter('PropertyName',PropertyValue, ...)` returns an Allpole filter System object, `HAllpole`, with each property set to the specified value.

## Properties

### Structure

Filter structure

Specify the filter structure.

You can specify the filter structure as one of | `Direct form` | `Direct form transposed` | `Lattice AR`. The default is `Direct form`. Analysis methods are not supported for fixed-point processing if the structure is `Direct form` or `Direct form transposed`. This property is nontunable.

### Denominator

Filter denominator coefficients

Specify the denominator coefficients as a real or complex numeric row vector. This property is applicable when the Structure

property is set to one of `Direct form` | `Direct form transposed`. The default value of this property is `[1 0.1]`. This property is tunable.

## ReflectionCoefficients

Lattice filter coefficients

Specify the lattice filter coefficients as a real or complex numeric row vector. This property is applicable when the `Structure` property is set to `Lattice AR`. The default value of this property is `[0.2 0.4]`. This property is tunable.

## InitialConditions

Initial conditions for the filter states

Specify the initial conditions of the filter states. The default value is `0`.

You can specify the initial conditions as a scalar, vector, or matrix. If you specify a scalar value, this System object initializes all delay elements in the filter to that value. You can also specify a vector whose length equals the number of delay elements in the filter. When you do so, each vector element specifies a unique initial condition for the corresponding delay element. The object applies the same vector of initial conditions to each channel of the input signal.

You can also specify a matrix with the same number of rows as the number of delay elements in the filter and one column for each channel of the input signal. In this case, each element specifies a unique initial condition for the corresponding delay element in the corresponding channel. This property is tunable.

## FrameBasedProcessing

Process input as frames or as samples

Set this property to `true` to enable frame-based processing. When this property is `true`, the Allpole filter treats each column as an independent channel. Set this property to `false` to enable

sample-based processing. When this property is `false`, the Allpole filter treats each element of the input as an individual channel. The default is `true`. This property is nontunable.

## **CoefficientsDataType**

Denominator coefficients word- and fraction-length designations

Specify the denominator coefficients fixed-point data type as one of `Same word length as input` | `Custom`. The default is `Same word length as input`. This property is nontunable.

## **ReflectionCoefficientsDataType**

Reflection coefficients word- and fraction-length designations

Specify the reflection coefficients fixed-point data type as one of `Same word length as input` | `Custom`. The default is `Same word length as input`. This property is nontunable.

## **Fixed-Point Properties**

### **ProductDataType**

Product word- and fraction-length designations

Specify the product fixed-point data type as one of `Full precision` | `Same as input` | `Custom` |. The default is `Full precision`. This property is nontunable.

### **AccumulatorDataType**

Accumulator word- and fraction-length designations

Specify the accumulator fixed-point data type to one of `Full precision` | `Same as input` | `Same as product` | `Custom` |. The default is `Full precision`. This property is nontunable.

### **OutputDataType**

Output word- and fraction-length designations

Specify the output fixed-point data type as one of | Same as accumulator | Same as input | Custom |. The default is Same as input. This property is nontunable.

## **StateDataType**

State word- and fraction-length designations

Specify the state fixed-point data type as one of | Same as input | Same as accumulator | Custom. The default is Same as accumulator. This property is nontunable.

## **CustomCoefficientsDataType**

Custom denominator word- and fraction-lengths

Specify the denominator coefficients fixed-point type as an autosigned numeric type object. This property is applicable when the `CoefficientsDataType` property is `Custom`. The default value of this property is `numericType([],16,15)`. This property is nontunable.

## **CustomReflectionCoefficientsDataType**

Custom reflection coefficients word- and fraction-lengths

Specify the denominator coefficients fixed-point type as an autosigned numeric type object. This property is applicable when the `ReflectionCoefficientsDataType` property is `Custom`. The default value of this property is `numericType([],16,15)`. This property is nontunable.

## **CustomProductDataType**

Custom Product word- and fraction-lengths

Specify the product fixed-point type as an autosigned scaled numeric type object. This property applies when you set the `ProductDataType` property to `Custom`. The default is `numericType([],32,30)`. This property is nontunable.

## **CustomAccumulatorDataType**

Custom accumulator word- and fraction-lengths

# dsp.AllpoleFilter

---

Specify the accumulator fixed-point type as an autosigned scaled `numericType` object. This property applies when you set the `AccumulatorDataType` property to `Custom`. The default is `numericType([],32,30)`. This property is nontunable.

## CustomStateDataType

Custom state word- and fraction-lengths

Specify the state fixed-point type as an autosigned scaled `numericType` object. This property applies when you set the `StateDataType` property to `Custom`. The default is `numericType([],16,15)`. This property is nontunable.

## CustomOutputDataType

Custom output word- and fraction-lengths

Specify the output fixed-point type as an autosigned scaled `numericType` object. This property applies when you set the `OutputDataType` property to `Custom`. The default is `numericType([],16,15)`. This property is nontunable.

## Methods

<code>clone</code>	Create Allpole filter with same property values
<code>freqz</code>	Frequency response
<code>fvtool</code>	Open filter visualization tool
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>impz</code>	Impulse response
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>phasez</code>	Unwrapped phase response

release	Allow property value and input characteristics changes
reset	Reset internal states of Allpole filter
step	Filter input with Allpole filter object

More “Analysis Methods for Filter System Objects” on page 4-2.

---

**Note** In AllpoleFilter, analysis methods are not supported for fixed-point processing if the structure is `Direct form` or `Direct form transposed`.

---

## Examples

Use an IIR filter to apply a lowpass filter to a waveform with two sinusoidal frequencies.

```
t = [0:63]./32e3;  
xin = (sin(2*pi*4e3*t)+sin(2*pi*12e3*t)) / 2;  
  
hSR = dsp.SignalSource(xin', 4);  
hLog = dsp.SignalSink;  
hallpole = dsp.AllpoleFilter;  
a = lpc(xin,6);  
hallpole.Denominator = a;  
  
while ~isDone(hSR)  
    input = step(hSR);  
    filteredOutput = step(hallpole,input);  
    step(hLog,filteredOutput);  
end  
  
filteredResult = hLog.Buffer;  
sper = spectrum.periodogram;  
psd(sper,filteredResult,'Fs',32e3)
```

# dsp.AllpoleFilter

---

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Allpole Filter block reference page. The object properties correspond to the block parameters.

Both this object and its corresponding block let you specify whether to process inputs as individual samples or as frames of data. The object uses the `FrameBasedProcessing` property. The block uses the **Input processing** parameter. See “Set the FrameBasedProcessing Property of a System object” for more information.

## See Also

`dsp.BiquadFilter` | `dsp.FIRFilter` | `dsp.IIRFilter`

**Purpose** Create Allpole filter with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a Allpole filter object, `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with uninitialized states.

# dsp.AllpoleFilter.freqz

---

**Purpose** Frequency response

**Syntax**

```
[h,w] = freqz(H)
[h,w] = freqz(H,n)
[h,w] = freqz(H,Name,Value)
freqz(H)
```

**Description**

`[h,w] = freqz(H)` returns the complex, 8192–element frequency response vector `h`, and the corresponding frequencies `w` in radians/sample.

`[h,w] = freqz(H,n)` returns the complex, `n`-element frequency response vector `h`, and the corresponding frequencies `w` in radians/sample, using `n` samples.

`[h,w] = freqz(H,Name,Value)` returns the frequency response and the corresponding frequencies, with additional options specified by one or more `Name, Value` pair arguments.

`freqz(H)` uses `FVTool` to plot the magnitude and unwrapped phase of the frequency response of the filter System object `H`.

**Purpose** Open filter visualization tool

**Syntax** `fvtool(H)`  
`fvtool(H, 'Arithmetic', ARITH, ...)`

**Description** `fvtool(H)` performs an analysis and computes the magnitude response of the filter System object H.

`fvtool(H, 'Arithmetic', ARITH, ...)` analyzes the filter System object H, based on the arithmetic specified in the ARITH input. ARITH can be set to one of 'double', 'single', or 'fixed'. The analysis tool assumes a double precision filter when the arithmetic input is not specified and the filter System object is in an unlocked state. The 'Arithmetic' input is only relevant for the analysis of filter System objects.

# dsp.AllpoleFilter.getNumInputs

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose**

Number of outputs of step method

**Syntax**

`N = getNumOutputs(H)`

**Description**

`N = getNumOutputs(H)` returns the number of outputs, `N`, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# dsp.AllpoleFilter.impz

---

**Purpose** Impulse response

**Syntax** `[h,t] = impz(H)`  
`[h,t] = impz(H,Name,Value)`  
`impz(H)`

**Description** `[h,t] = impz(H)` returns the impulse response `h`, and the corresponding time points `t` at which the impulse response of `H` is computed.

`[h,t] = impz(H,Name,Value)` returns the impulse response `h`, and the corresponding time points `t`, with additional options specified by one or more `Name, Value` pair arguments.

`impz(H)` uses FVTool to plot the impulse response of the filter System object `H`.

---

**Note** You can use `impz` for both real and complex filters. When you omit the output arguments, `impz` plots only the real part of the impulse response.

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the Allpole filter.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.AllpoleFilter.phasez

---

**Purpose** Unwrapped phase response

**Syntax**  
`[phi,w] = phasez(H)`  
`[phi,w] = phasez(H,n)`  
`[phi,w] = phasez(H,Name,Value)`  
`phasez(H)`

**Description**

`[phi,w] = phasez(H)` returns the 8192–element phase response vector `phi`, and the corresponding frequencies `w` in radians/sample.

`[phi,w] = phasez(H,n)` returns the `n`-element phase response vector `phi`, and the corresponding frequencies `w` in radians/sample, using `n` samples.

`[phi,w] = phasez(H,Name,Value)` returns the phase response and the corresponding frequencies, with additional options specified by one or more `Name, Value` pair arguments.

`phasez(H)` uses FVTool to plot the phase response of the filter System object `H`.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

# dsp.AllpoleFilter.reset

---

**Purpose** Reset internal states of Allpole filter

**Syntax** reset(H)

**Description** reset(H) resets the filter states of the Allpole filter object, H, to their initial values of 0. The initial filter state values correspond to the initial conditions for the difference equation defining the filter. After the step method applies the Allpole filter object to nonzero input data, the states may be nonzero. Invoking the step method again without first invoking the reset method may produce different outputs for an identical input.

For example:

```
n = 0:100;
x = cos(0.2*pi*n)+sin(0.8*pi*n);
H = dsp.AllpoleFilter;
a = lpc(x,20);
H.Denominator = a;
y = step(H,x);
% Filter states are nonzero
% Invoke step method again without resetting states
y1 = step(H,x);
isequal(y,y1) % returns 0
% Now reset filter states to 0
reset(H)
% Invoke step method
y2 = step(H,x);
isequal(y,y2) % returns a 1
```

**Purpose** Filter input with Allpole filter object

**Syntax**  $Y = \text{step}(H,X)$

**Description**  $Y = \text{step}(H,X)$  filters the real or complex input signal  $X$  using the Allpole filter,  $H$ , to produce the output  $Y$ . When the input data is of a fixed-point type, it must be signed. The Allpole filter object operates on each channel of the input signal independently over successive calls to step method.

---

**Note** The object performs an initialization the first time the step method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the release method to unlock the object.

---

# dsp.AnalyticSignal

---

**Purpose** Analytic signals of discrete-time inputs

**Description** The `AnalyticSignal` object computes analytic signals of discrete-time inputs. The real part of the analytic signal in each channel is a replica of the real input in that channel, and the imaginary part is the Hilbert transform of the input. In the frequency domain, the analytic signal doubles the positive frequency content of the original signal while zeroing-out negative frequencies and retaining the DC component. The object computes the Hilbert transform using an equiripple FIR filter.

To compute the analytic signal of a discrete-time input:

- 1 Define and set up your analytic signal calculation. See “Construction” on page 5-20.
- 2 Call `step` to compute the analytic signal according to the properties of `dsp.AnalyticSignal`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.AnalyticSignal` returns an analytic signal object, `H`, that computes the complex analytic signal corresponding to each channel of a real  $M$ -by- $N$  input matrix.

`H = dsp.AnalyticSignal('PropertyName',PropertyValue,...)` returns an analytic signal object, `H`, with each specified property set to the specified value.

`H = dsp.AnalyticSignal(order,'PropertyName',PropertyValue,...)` returns an analytic signal object, `H`, with the `FilterOrder` property set to `order` and other specified properties set to the specified values.

**Properties** **FilterOrder**

Filter order used to compute Hilbert transform

Specify the order of the equiripple FIR filter used in computing the Hilbert transform as an even integer scalar. The default is 100.

## FrameBasedProcessing

Process input as frames or samples

Set this property to `true` to enable frame-based processing. Set this property to `false` to enable sample-based processing. The default is `true`.

## Methods

<code>clone</code>	Create analytic signal object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>reset</code>	Reset internal states of analytic signal object
<code>step</code>	Analytic signal

## Examples

Compute the analytic signal of a sinusoidal input.

```
t = (-1:0.01:1)';  
x = sin(4*pi*t);  
hanlytc = dsp.AnalyticSignal(200);  
y = step(hanlytc,x);  
  
subplot(2,1,1), plot(t, x);  
title('Original Signal');  
subplot(2,1,2), plot(t, [real(y) imag(y)]);  
title('Analytic signal of the input')  
legend('Real signal','Imaginary signal',...  
       'Location','best');
```

# dsp.AnalyticSignal

---

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Analytic Signal block reference page. The object properties correspond to the block parameters.

Both this object and its corresponding block let you specify whether to process inputs as individual samples or as frames of data. The object uses the `FrameBasedProcessing` property. The block uses the **Input processing** parameter. See “Set the FrameBasedProcessing Property of a System object” for more information.

## See Also

`dsp.FFT` | `dsp.IFFT`

**Purpose**

Create analytic signal object with same property values

**Syntax**

`C = clone(H)`

**Description**

`C = clone(H)` creates an `AnalyticSignal` object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with uninitialized states.

# dsp.AnalyticSignal.getNumInputs

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**      `N = getNumInputs(H)` returns the number of expected inputs to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.AnalyticSignal.getNumOutputs

---

**Purpose**

Number of outputs of step method

**Syntax**

`N = getNumOutputs(H)`

**Description**

`N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# dsp.AnalyticSignal.isLocked

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `AnalyticSignal` object `H`.  
The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

# **dsp.AnalyticSignal.reset**

---

**Purpose**            Reset internal states of analytic signal object

**Syntax**            `reset(H)`

**Description**       `reset(H)` sets the internal states of the `AnalyticSignal` object `H` to their initial values.

**Purpose** Analytic signal

**Syntax**  $Y = \text{step}(H, X)$

**Description**  $Y = \text{step}(H, X)$  computes the analytic signal,  $Y$ , of the  $M$ -by- $N$  input matrix  $X$ , according to the equation

$$\mathbf{Y} = \mathbf{X} + jH\{\mathbf{X}\}$$

where  $j$  is the imaginary unit and  $H\{\mathbf{X}\}$  denotes the Hilbert transform.

When you set the `FrameBasedProcessing` property to `false`, each of the  $M$ -by- $N$  matrix elements is an independent channel. Thus, the method computes the analytic signal for each element of  $X$ . When you set the `FrameBasedProcessing` property to `true`, each of the  $N$  columns in  $X$  contains  $M$  sequential time samples from an independent channel. The method computes the analytic signal for each channel.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.ArrayVectorAdder

---

**Purpose** Add array to vector along specified dimension

**Description** The ArrayVectorAdder object adds an N-D array to a vector along a specified dimension. The length of the vector must equal the size of the N-D array along the specified dimension.

To add an N-D array to a vector along a specified dimension:

- 1 Define and set up your array-vector addition object. See “Construction” on page 5-30.
- 2 Call `step` to add the N-D array according to the properties of `dsp.ArrayVectorAdder`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.ArrayVectorAdder` returns an array-vector addition object, `H`, that adds a vector to an N-D array along the first dimension.

`H = dsp.ArrayVectorAdder('PropertyName',PropertyValue, ...)` returns an array-vector addition object, `H`, with each property set to the specified value.

## Properties

### Dimension

Dimension along which to add vector elements to input

Specify the dimension along which to add the input array to the elements of the vector as a positive integer. The length of the vector must match the size of the N-D array along the specified dimension. The default is 1.

### VectorSource

Source of vector

Specify the source of the vector values as `|Input port | Property |`. The default is `Input port`.

### Vector

Vector values

Specify the vector values. This property applies only when you set the `VectorSource` property to `Property`. The default is `[0.5 0.25]`. This property is tunable.

## Fixed-Point Properties

### FullPrecisionOverride

Full precision override for fixed-point arithmetic

Specify whether to use full precision rules. If you set `FullPrecisionOverride` to `true`, which is the default, the object computes all internal arithmetic and output data types using full precision rules. These rules provide the most accurate fixed-point numerics. It also turns off the display of other fixed-point properties because they do not apply individually. These rules guarantee that no quantization occurs within the object. Bits are added, as needed, to ensure that no roundoff or overflow occurs. If you set `FullPrecisionOverride` to `false`, fixed-point data types are controlled through individual fixed-point property settings. For more information, see “Full Precision for Fixed-Point System Objects”.

### RoundingMethod

Rounding method for fixed-point operations

Specify the rounding method as `| Ceiling | Convergent | Floor | Nearest | Round | Simplest | Zero |`. The default is `Floor`. This property applies only if the object is not in full precision mode.

### OverflowAction

Overflow action for fixed-point operations

Specify the overflow action as `| Wrap | Saturate |`. The default is `Wrap`. This property applies only if the object is not in full precision mode.

### VectorDataType

# dsp.ArrayVectorAdder

---

Vector word and fraction lengths

Specify the vector fixed-point data type as | Same word length as input | Custom |. This property applies when you set the VectorSource property to Property. The default is Same word length as input.

## **CustomVectorDataType**

Vector word and fraction lengths

Specify the vector fixed-point type as a numeric type object with a Signedness of Auto. This property applies when you set the VectorSource property to Property and the VectorDataType property to Custom. The default is numeric type ([ ], 16, 15).

## **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point data type as | Full precision | Same as first input | Custom |. The default is Full precision.

## **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled numeric type object with a Signedness of Auto. This property applies only when the AccumulatorDataType property is Custom. The default is numeric type ([ ], 32, 30).

## **OutputDataType**

Output word and fraction lengths

Specify the output fixed-point data type as | Same as accumulator | Same as first input | Custom |.

## **CustomOutputDataType**

Output word and fraction lengths

Specify the output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when the `OutputDataType` property is `Custom`. The default is `numericType([],16,15)`.

## Methods

<code>clone</code>	Create array-vector adder object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>step</code>	Add vector to N-D array

## Examples

Add 2-by-1 vector to 2-by-2 matrix along the first dimension of the array.

```
hava = dsp.ArrayVectorAdder;  
a = ones(2);  
x = [1 2]';  
y = step(hava, a, x);
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Array-Vector Add block reference page. The object properties correspond to the block parameters, except:

The array-vector addition object does not have **Minimum** or **Maximum** options for data output.

## See Also

`dsp.ArrayVectorMultiplier` | `dsp.ArrayVectorDivider` | `dsp.ArrayVectorSubtractor`

## **dsp.ArrayVectorAdder.clone**

---

<b>Purpose</b>	Create array-vector adder object with same property values
<b>Syntax</b>	<code>C = clone(H)</code>
<b>Description</b>	<code>C = clone(H)</code> creates an array-vector adder object, <code>C</code> , with the same property values as <code>H</code> . The clone method creates a new unlocked object.

# dsp.ArrayVectorAdder.getNumInputs

---

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.ArrayVectorAdder.getNumOutputs**

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the array-vector adder.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.ArrayVectorAdder.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

**Purpose** Add vector to N-D array

**Syntax**  
 $Y = \text{step}(H,A)$   
 $Y = \text{step}(H,A,V)$

**Description**  $Y = \text{step}(H,A)$  returns  $Y$ , the result of adding the input array  $A$  to the elements of the vector specified in the `Vector` property along the specified dimension when the `VectorSource` property is `Property`. The length of the vector specified in the `Vector` property must equal the length of the specified dimension of  $A$ .

$Y = \text{step}(H,A,V)$  returns  $Y$ , the result of adding the input array  $A$  to the elements of the input vector  $V$  along the specified dimension when the `VectorSource` property is `Input port`. The length of the input  $V$  must equal the length of the specified dimension of  $A$ .

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the `System` object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.ArrayVectorDivider

---

**Purpose** Divide array by vector along specified dimension

**Description** The `ArrayVectorDivider` object divides an array by a vector along a specified dimension.

To divide an array by a vector along a specified dimension:

- 1 Define and set up your array-vector division object. See “Construction” on page 5-40.
- 2 Call `step` to divide the array according to the properties of `dsp.ArrayVectorDivider`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.ArrayVectorDivider` returns an array-vector division object, `H`, that divides an input array by the elements of a vector along the first dimension of the array.

`H = dsp.ArrayVectorDivider('PropertyName',PropertyValue,...)` returns an array-vector division object, `H`, with each property set to the specified value.

## Properties

### Dimension

Dimension along which to divide input by vector elements

Specify the dimension along which to divide the input array by the elements of a vector as a positive integer. The default is 1.

### VectorSource

Source of vector

Specify the source of the vector values as `| Input port | Property |`. The default is `Input port`.

### Vector

Vector values

Specify the vector values. This property applies when you set the `VectorSource` property to `Property`. The default is `[0.5 0.25]`. This property is tunable.

## Fixed-Point Properties

### RoundingMethod

Rounding method for fixed-point operations

Specify the rounding method as `| Ceiling | Convergent | Floor | Nearest | Round | Simplest | Zero |`. The default is `Floor`.

### OverflowAction

Overflow action for fixed-point operations

Specify the overflow action as `| Wrap | Saturate |`. The default is `Wrap`.

### VectorDataType

Vector word and fraction lengths

Specify the vector fixed-point mode as `| Same word length as input | Custom |`. This property applies when you set the `VectorSource` property to `Property`. The default is `Same word length as input`.

### CustomVectorDataType

Vector word and fraction lengths

Specify the vector fixed-point data type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `VectorSource` property to `Property` and the `VectorDataType` property to `Custom`. The default is `numericType([],16,15)`.

### OutputDataType

Output word and fraction lengths

# dsp.ArrayVectorDivider

---

Specify the output fixed-point data type as | Same as first input | Custom |. The default is Same as first input.

## CustomOutputDataType

Output word and fraction lengths

Specify the output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `OutputDataType` property to `Custom`. The default is `numericType([], 16, 15)`.

## Methods

<code>clone</code>	Create array-vector division object with same property values
<code>getNumInputs</code>	Number of expected inputs to <code>step</code> method
<code>getNumOutputs</code>	Number of outputs of <code>step</code> method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>step</code>	Divide array by vector

## Examples

Divide a matrix by a vector.

```
havd = dsp.ArrayVectorDivider;  
a = ones(2);  
x = [2 3]';  
y = step(havd, a, x);
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Array-Vector Divide block reference page. The object properties correspond to the block parameters, except:

The array-vector division object does not have **Minimum** or **Maximum** options for data output.

## See Also

[dsp.ArrayVectorMultiplier](#) | [dsp.ArrayVectorAdder](#) |  
[dsp.ArrayVectorSubtractor](#)

## **dsp.ArrayVectorDivider.clone**

---

**Purpose** Create array-vector division object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates an array-vector division object, `C`, with the same property values as `H`. The clone method creates a new unlocked object.

# **dsp.ArrayVectorDivider.getNumInputs**

---

**Purpose**                      Number of expected inputs to step method

**Syntax**                      `N = getNumInputs(H)`

**Description**                `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.ArrayVectorDivider.getNumOutputs**

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the array-vector divider.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# **dsp.ArrayVectorDivider.release**

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

**Purpose** Divide array by vector

**Syntax**  
 $Y = \text{step}(H,A,V)$   
 $Y = \text{step}(H,A)$

**Description**  $Y = \text{step}(H,A,V)$  returns  $Y$ , the result of dividing the input array  $A$  by the elements of input vector  $V$  along the specified dimension when the `VectorSource` property is `Input port`. The length of the input  $V$  must equal the length of the specified dimension of  $A$ .

$Y = \text{step}(H,A)$  returns  $Y$ , the result of dividing the input array  $A$  by the elements of the vector specified in the `Vector` property along the specified dimension when the `VectorSource` property is `Property`. The length of the vector specified in the `Vector` property must equal the length of the specified dimension of  $A$ .

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.ArrayVectorMultiplier

---

**Purpose** Multiply array by vector along specified dimension

**Description** The `ArrayVectorMultiplier` object multiplies an array by a vector along a specified dimension.

To multiply an array by a vector along a specified:

- 1 Define and set up your array-vector multiplication object. See “Construction” on page 5-50.
- 2 Call `step` to multiply the array according to the properties of `dsp.ArrayVectorMultiplier`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.ArrayVectorMultiplier` returns an array-vector multiplication object, `H`, that multiplies an input N-D array by the elements of a vector along the second dimension.

`H = dsp.ArrayVectorMultiplier('PropertyName',PropertyValue,...)` returns an array-vector multiplication object, `H`, with each property set to the specified value.

**Properties**

**Dimension**

Dimension along which to multiply input by vector elements

Specify the dimension along which to multiply the input array by the elements of vector as a positive integer. The default is 2.

**VectorSource**

Source of vector

Specify the source of the vector values as one of `Input port` or `Property`. The default is `Input port`.

**Vector**

Vector to multiply array

Specify the vector by which to multiply the array. This property applies when you set the `VectorSource` property to `Property`. The default is `[0.5 0.25]`. This property is tunable.

## Fixed-Point Properties

### RoundingMethod

Rounding method for fixed-point operations

Specify the rounding method as `Ceiling`, `Convergent`, `Floor`, `Nearest`, `Round`, `Simplest`, `Zero`. The default is `floor`.

### OverflowAction

Overflow action for fixed-point operations

Specify the overflow action as `Wrap` or `Saturate`. The default is `Wrap`.

### VectorDataType

Vector word and fraction lengths

Specify the vector fixed-point data type as `Same word length as input`, `Custom`. This property applies when you set the `VectorSource` property to `Property`. The default is `Same word length as input`.

### CustomVectorDataType

Vector word and fraction lengths

Specify the vector fixed-point type as a `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `VectorSource` property to `Property` and the `VectorDataType` property to `Custom`. The default is `numericType([],16,15)`.

### ProductDataType

Product word and fraction lengths

# dsp.ArrayVectorMultiplier

---

Specify the product fixed-point data type as Full precision, Same as first input, or Custom. The default is Full precision.

## **CustomProductDataType**

Product word and fraction lengths

Specify the product fixed-point type as a scaled numeric type object with a Signedness of Auto. This property applies when you set the ProductDataType property to Custom. The default is numeric type ([ ], 32, 30).

## **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point data type as Full precision, Same as product, Same as first input, or Custom. The default is Full precision.

## **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled numeric type object with a Signedness of Auto. This property applies when you set the AccumulatorDataType property to Custom. The default is numeric type ([ ], 32, 30).

## **OutputDataType**

Output word and fraction lengths

Specify the output fixed-point data type as Same as product, Same as first input, or Custom. The default is Same as product.

## **CustomOutputDataType**

Output word and fraction lengths

Specify the output fixed-point type as a scaled numeric type object with a Signedness of Auto. This property applies when

you set the `OutputDataType` property to `Custom`. The default is `numerictype([],16,15)`.

## Methods

<code>clone</code>	Create array-vector multiplication object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>step</code>	Multiply array by vector

## Examples

Multiply a matrix by a vector:

```
havm = dsp.ArrayVectorMultiplier;  
a = ones(2);  
x = [2 3]';  
y = step(havm, a, x);
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the [Array-Vector Multiply](#) block reference page. The object properties correspond to the block parameters, except:

- The array-vector multiplication object does not have **Minimum** or **Maximum** options for data output.

## See Also

[dsp.ArrayVectorAdder](#) | [dsp.ArrayVectorDivider](#) | [dsp.ArrayVectorSubtractor](#)

## **dsp.ArrayVectorMultiplier.clone**

---

**Purpose** Create array-vector multiplication object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates an array-vector multiplication object, `C`, with the same property values as `H`. The clone method creates a new unlocked object.

# dsp.ArrayVectorMultiplier.getNumInputs

---

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.ArrayVectorMultiplier.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of output arguments from the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the array-vector multiplication object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.ArrayVectorMultiplier.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

**Purpose** Multiply array by vector

**Syntax**  $Y = \text{step}(H,A,V)$   
 $Y = \text{step}(H,A)$

**Description**  $Y = \text{step}(H,A,V)$  returns  $Y$ , the result of multiplying the input array  $A$  by the elements of input vector  $V$  along the specified dimension when the `VectorSource` property is `Input port`. The length of the input  $V$  must equal the length of the specified dimension of  $A$ .

$Y = \text{step}(H,A)$  returns  $Y$ , the result of multiplying the input array  $A$  by the elements of vector specified in `Vector` property along the specified dimension when the `VectorSource` property is set to `Property`. The length of the vector specified in `Vector` property must equal the length of the specified dimension of  $A$ .

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.ArrayVectorSubtractor

---

**Purpose** Subtract vector from array along specified dimension

**Description** The ArrayVectorSubtractor object subtracts a vector from an N-D array along a specified dimension.

To subtract a vector from an N-D array along a specified dimension:

- 1** Define and set up your array-vector subtraction object. See “Construction” on page 5-60.
- 2** Call `step` to subtract the vector according to the properties of `dsp.ArrayVectorSubtractor`. The behavior of `step` is specified to each object in the toolbox.

**Construction** `H = dsp.ArrayVectorSubtractor` returns an array-vector subtraction object, `H`, that subtracts the elements of a vector from an N-D input array along the first dimension.

`H = dsp.ArrayVectorSubtractor('PropertyName',PropertyValue,...)` returns an array-vector subtraction object, `H`, with each property set to the specified value.

## Properties

### Dimension

Dimension along which to subtract vector elements from input

Specify the dimension along which to subtract the elements of the vector from the input array as an integer-valued scalar greater than 0. The default is 1.

### VectorSource

Source of vector

Specify the source of the vector values as one of `Input port` or `Property`. The default is `Input port`.

### Vector

Vector values

Specify the vector values. This property applies when you set the `VectorSource` property to `Property`. The default is `[0.5 0.25]`. This property is tunable.

## Fixed-Point Properties

### FullPrecisionOverride

Full precision override for fixed-point arithmetic

Specify whether to use full precision rules. If you set `FullPrecisionOverride` to `true`, which is the default, the object computes all internal arithmetic and output data types using full precision rules. These rules provide the most accurate fixed-point numerics. It also turns off the display of other fixed-point properties because they do not apply individually. These rules guarantee that no quantization occurs within the object. Bits are added, as needed, to ensure that no roundoff or overflow occurs. If you set `FullPrecisionOverride` to `false`, fixed-point data types are controlled through individual fixed-point property settings. For more information, see “Full Precision for Fixed-Point System Objects”.

### RoundingMethod

Rounding method for fixed-point operations

Specify the rounding method as `Ceiling`, `Convergent`, `Floor`, `Nearest`, `Round`, `Simplest`, or `Zero`. This property applies only if the object is not in full precision mode.

### OverflowAction

Overflow action for fixed-point operations

Specify the overflow action as one of `Wrap` or `Saturate`. The default is `Wrap`. This property applies only if the object is not in full precision mode.

### VectorDataType

Vector word and fraction lengths

# dsp.ArrayVectorSubtractor

---

Specify the vector fixed-point data type as `Same word length as input` or `Custom`. This property applies when you set the `VectorSource` property to `Property`. The default is `Same word length as input`.

## **CustomVectorDataType**

Vector word and fraction lengths

Specify the vector fixed-point type as a `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `VectorSource` property to `Property` and the `VectorDataType` property to `Custom`. The default is `numericType([],16,15)`.

## **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point data type as one of `Full precision`, `Same as first input`, or `Custom`. The default is `Full precision`.

## **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `AccumulatorDataType` property to `Custom`. The default is `numericType([],32,30)`.

## **OutputDataType**

Output word and fraction lengths

Specify the output fixed-point data type as `Same as accumulator`, `Same as first input`, or `Custom`. The default is `Same as accumulator`.

## **CustomOutputDataType**

Output word and fraction lengths

Specify the output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `OutputDataType` property to `Custom`. The default is `numericType([], 16, 15)`.

## Methods

<code>clone</code>	Create array-vector subtractor with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>step</code>	Subtract vector from array along specified dimension

## Examples

Subtract a vector from a matrix:

```
havs = dsp.ArrayVectorSubtractor;  
a = ones(2);  
x = [1 2]';  
y = step(havs, a, x);
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the [Array-Vector Subtract](#) block reference page. The object properties correspond to the block parameters, except:

The array-vector subtraction object does not have **Minimum** or **Maximum** options for data output.

## See Also

[dsp.ArrayVectorMultiplier](#) | [dsp.ArrayVectorDivider](#) | [dsp.ArrayVectorAdder](#)

## **dsp.ArrayVectorSubtractor.clone**

---

**Purpose** Create array-vector subtractor with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates an array-vector subtractor object, `C`, with the same property values as `H`. The clone method creates a new unlocked object.

# dsp.ArrayVectorSubtractor.getNumInputs

---

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.ArrayVectorSubtractor.getNumOutputs**

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the array-vector subtractor object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.ArrayVectorSubtractor.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Subtract vector from array along specified dimension

**Syntax**  
 $Y = \text{step}(H,A,V)$   
 $Y = \text{step}(H,A)$

**Description**  $Y = \text{step}(H,A,V)$  returns  $Y$ . The value of  $Y$  results from subtracting the elements of input vector  $V$  from the input array  $A$  along the specified dimension when the `VectorSource` property is `Input port`. The length of the input  $V$  must equal the length of the specified dimension of  $A$ .

$Y = \text{step}(H,A)$  returns  $Y$ . The value of  $Y$  results from subtracting the elements of the vector specified in the `Vector` property from the input array  $A$  along the specified dimension when the `VectorSource` property is `Property`. The length of the vector specified in the `Vector` property must equal the length of the specified dimension of  $A$ .

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.AudioFileReader

---

**Purpose** Read audio samples from audio file

**Description** The `AudioFileReader` object reads audio samples from an audio file.  
To read audio samples from an audio file:

- 1 Define and set up your audio file reader object. See “Construction” on page 5-70.
- 2 Call `step` to read audio samples according to the properties of `dsp.AudioFileReader`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.AudioFileReader` returns an audio file reader System object, `H` that reads audio from an audio file. This audio file can be of the following formats on all platforms:

- MP3
- M4a
- MP4
- WAV
- FLAC
- OGG

`H = dsp.AudioFileReader('PropertyName',PropertyValue,...)` returns an audio file reader System object, `H`, with each specified property set to the specified value.

`H = dsp.AudioFileReader(FileName,'PropertyName',PropertyValue,...)` returns an audio file reader object, `H`, with `FileName` property set to `FILENAME` and other specified properties set to the specified values.

**Properties** **Filename**

Name of audio file from which to read

Specify the name of an audio file as a string. Specify the full path for the file only if the file is not on the MATLAB path. On UNIX platforms, the audio file reader only supports uncompressed AVI files. The default is `speech_dft.avi`.

## **PlayCount**

Number of times to play file

Specify a positive integer or `inf` as the number of times to play the file. If you enter `inf`, the file plays repeatedly. The default is `inf`.

## **SampleRate**

Sampling rate of the audio file

This read-only property displays the sampling rate, in hertz, of the audio file.

## **SamplesPerFrame**

Number of samples in audio frame

Specify the number of samples in an audio frame as a positive, scalar integer value. The default value is 1024.

## **OutputDataType**

Data type of output

Set the data type of the audio data output from the audio file reader object. Specify the data type as `|double| single | int16 | uint8|`. The default is `int16`.

## **Methods**

<code>clone</code>	Create audio file reader object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method

# dsp.AudioFileReader

---

info	Information about specific audio file
isDone	End-of-file status (logical)
isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
reset	Reset internal states of audio file reader to read from beginning of file
step	Read audio samples from audio file

## Examples

Read and play back an audio file using the standard audio output device.

```
hmfr = dsp.AudioFileReader('speech_dft.avi');
hap = dsp.AudioPlayer('SampleRate', 22050);

while ~isDone(hmfr)
    audio = step(hmfr);
    step(hap, audio);
end

release(hmfr); % release the input file
release(hap); % release the audio output device
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the From Multimedia File block reference page. The object properties correspond to the block parameters, except:

- The object has no corresponding property for the **Inherit sample time from file** block parameter. The object always inherits the sample time from the file.

- The object has no corresponding property for the **Output end-of-file indicator** parameter. The object always outputs EOF as the last output.
- The object has no corresponding property for the **Multimedia Outputs** parameter because audio is the only supported output.
- The object has no corresponding property for the **Image signal** block parameter.
- The object has no corresponding property for the **Output color format** parameter.
- The object has no corresponding property for the **Video output data type** parameter.

## See Also

`dsp.AudioFileWriter`

# **dsp.AudioFileReader.clone**

---

**Purpose** Create audio file reader object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates an `AudioFileReader` System object, `C`, with the same property values as `H`.

The clone method creates a new unlocked object with uninitialized states.

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of inputs, `N`, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.AudioFileReader.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Information about specific audio file

**Syntax** `S = info(H)`

**Description** `S = info(H)` returns a MATLAB structure, `S`, with information about the audio file specified in the `Filename` property. The number of fields in `S` varies depending on the audio content of the file. For possible fields and values for the structure `S`, see the following table.

Field	Value
SampleRate	Audio sampling rate of the audio file in Hz.
NumBits	Number of bits used to encode the audio stream.
NumChannels	Number of audio channels.

# **dsp.AudioFileReader.isDone**

---

**Purpose**            End-of-file status (logical)

**Syntax**            STATUS = isDone(H)

**Description**        STATUS = isDone(H) returns a logical value, STATUS , when the AudioFileReader object, H , reaches the end of the audio file. If you set the PlayCount property to a value greater than 1 , STATUS is true each time the object reaches the end of the file. STATUS is the same as the EOF output value in the step method syntax.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `y = isLocked(H)`

**Description** `y = isLocked(H)` returns the locked state, Y, of the `AudioFileReader` object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# **dsp.AudioFileReader.reset**

---

<b>Purpose</b>	Reset internal states of audio file reader to read from beginning of file
<b>Syntax</b>	<code>reset(H)</code>
<b>Description</b>	<code>reset(H)</code> resets the <code>AudioFileReader</code> object to read from the beginning of the file.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections. This method lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

# dsp.AudioFileReader.step

---

**Purpose** Read audio samples from audio file

**Syntax** AUDIO = step(H)  
[AUDIO,EOF] = step(H)

**Description** AUDIO = step(H) outputs one frame of audio samples, AUDIO. You can specify the number of times to play the file using the PlayCount property. After playing the file for the number of times you specify, AUDIO contains silence.

[AUDIO,EOF] = step(H) returns an end-of-file indicator, EOF. EOF is true each time the output AUDIO contains the last audio sample in the file.

---

**Note** The object performs an initialization the first time the step method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the release method to unlock the object.

---

<b>Purpose</b>	Write audio samples to audio file
<b>Description</b>	<p>The AudioFileWriter object writes audio samples to an audio file.</p> <p>To write audio samples to an audio file:</p> <ol style="list-style-type: none"><li>1 Define and set up your audio file writer object. See “Construction” on page 5-83.</li><li>2 Call <code>step</code> to write audio samples according to the properties of <code>dsp.AudioFileWriter</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.AudioFileWriter</code> returns an audio file writer System object, H. This object writes audio samples to an audio file. This audio file can be of the following formats on all platforms:</p> <ul style="list-style-type: none"><li>• WAV</li><li>• FLAC</li><li>• OGG</li></ul> <p><code>H = dsp.AudioFileWriter('PropertyName',PropertyValue,...)</code> returns an audio file writer System object, H, with each specified property set to the specified value.</p> <p><code>H = dsp.AudioFileWriter(FILENAME,'PropertyName',PropertyValue,...)</code> returns an audio file writer System object, H. This object has the <code>Filename</code> property set to <code>FILENAME</code> and other specified properties set to the specified values.</p>
<b>Properties</b>	<p><b>Filename</b></p> <p>Name of audio file to which to write</p> <p>Specify the name of the audio file as a string. The default is <code>output.avi</code>.</p>

## **FileFormat**

Audio file format

Specify which audio file format the object writes. On Microsoft platforms, select AVI, WAV, or WMA. On all other platforms, the only selection available is AVI. These abbreviations correspond to the following file formats:

- AVI: Audio-Video Interleave
- WAV: Microsoft WAVE Files
- WMA: Windows Media Audio

The default is AVI.

## **SampleRate**

Sampling rate of audio data stream

Specify the sampling rate of the input audio data as a positive, numeric scalar value. The default is 44100 .

## **Compressor**

Algorithm that compresses audio data

Specify the type of compression algorithm the audio file writer uses to compress the audio data. Compression reduces the size of the audio file. Select `None` (uncompressed) to save uncompressed audio data to the file. The other options available reflect the audio compression algorithms installed on your system. You can use tab completion to query valid `Compressor` options for your computer by typing `H.Compressor = '` and then pressing the tab key. This property applies when writing WAV or AVI files on Windows platforms.

## **DataType**

Data type of the uncompressed audio

Specify the type of uncompressed audio data written to the file as one of `inherit`, `int16`, `int24`, `single`, or `uint8`. This property only applies when writing uncompressed WAV files. The default value of this property is `int16`.

## Methods

<code>clone</code>	Create audio file writer object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>step</code>	Write one frame of audio output samples

## Examples

Decimate an audio signal, and write it to disk as an AVI file.

```
hmfr = dsp.AudioFileReader('OutputDataType',...  
    'double');  
hfirdec = dsp.FIRDecimator; % decimate by 2  
hmfw = dsp.AudioFileWriter...  
    ('speech_dft_11025.avi', ...  
    'SampleRate', 22050/2);  
  
while ~isDone(hmfr)  
    audio = step(hmfr);  
    audiod = step(hfirdec, audio);  
    step(hmfw, audiod);  
end  
  
release(hmfr);
```

```
release(hmfw);
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the To Multimedia File block reference page. The object properties correspond to the block parameters, except:

- The object `FileFormat` property does not support video-only file formats.
- The object has no corresponding property for the **Write** parameter. The object writes only audio content to files.
- The object has no corresponding property for the **Video compressor** parameter.
- The object has no corresponding property for the **File color format** parameter.
- The object has no corresponding property for the **Image signal** parameter.

## See Also

`dsp.AudioFileReader`

<b>Purpose</b>	Create audio file writer object with same property values
<b>Syntax</b>	<code>C = clone(H)</code>
<b>Description</b>	<code>C = clone(H)</code> creates an <code>AudioFileWriter System</code> object <code>C</code> , with the same property values as <code>H</code> . The clone method creates a new unlocked object.

# dsp.AudioFileWriter.getNumInputs

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, of the step method

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose**

Number of outputs of step method

**Syntax**

`N = getNumOutputs(H)`

**Description**

`N = getNumOutputs(H)` returns the number of outputs, of step method `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# **dsp.AudioFileWriter.isLocked**

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `AudioFileWriter` System object `H`.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections. This method lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

# dsp.AudioFileWriter.step

---

**Purpose** Write one frame of audio output samples

**Syntax** `step(H,AUDIO)`

**Description** `step(H,AUDIO)` writes one frame of audio samples, `AUDIO`, to the output file. `AUDIO` is either a vector or an M-by-N matrix for mono or N-channel audio inputs respectively.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

<b>Purpose</b>	Play audio data using computer's audio device
<b>Description</b>	<p>The <code>AudioPlayer</code> object plays audio data using the computer's audio device.</p> <p>To play audio data using the computer's audio device:</p> <ol style="list-style-type: none"><li>1 Define and set up your audio player object. See "Construction" on page 5-93.</li><li>2 Call <code>step</code> to play audio data according to the properties of <code>dsp.AudioPlayer</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.AudioPlayer</code> returns an audio player object, <code>H</code>, that plays audio samples using an audio output device in real-time.</p> <p><code>H = dsp.AudioPlayer('PropertyName',PropertyValUe, ...)</code> returns an audio player object, <code>H</code>, with each property set to the specified value.</p> <p><code>H = dsp.AudioPlayer(SAMPLERATE, 'PropertyName',PropertyValUe, ...)</code> returns an audio player object, <code>H</code>, with the <code>SampleRate</code> property set to <code>SAMPLERATE</code> and other specified properties set to the specified values.</p>
<b>Properties</b>	<p><b>DeviceName</b></p> <p>Device to which to send audio data</p> <p>Specify the device to which to send the audio data. The default is <code>Default</code>, which is the computer's standard output device. You can use tab completion to query valid <code>DeviceName</code> assignments for your computer by typing <code>H.DeviceName = '</code> and then pressing the tab key.</p> <p><b>SampleRate</b></p> <p>Number of samples per second sent to audio device</p>

# dsp.AudioPlayer

---

Specify the number of samples per second in the signal as an integer. The default is 44100.

## **DeviceDataType**

Data type used by device

Specify the data type used by the audio device to acquire audio data as Determine from input data type, 8-bit integer, 16-bit integer, 24-bit integer, or 32-bit float. The default is Determine from input data type.

## **BufferSizeSource**

Source of Buffer Size

Specify how to determine the buffer size as Auto or Property. The default is Auto.

## **BufferSize**

Buffer size

Specify the size of the buffer that the audio player object uses to communicate with the audio device as an integer. This property applies when you set the BufferSizeSource property to Property. The default is 4096.

## **QueueDuration**

Size of queue in seconds

Specify the length of the audio queue, in seconds. The default is 1.0.

## **Methods**

clone	Create audio player object with same property values
getNumInputs	Number of expected inputs to step method
getNumOutputs	Number of outputs of step method

isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
step	Write audio to audio output device

## Examples

Read in an AVI audio file, and play the file back using the standard audio output device:

```
hafr = dsp.AudioFileReader;
hap = dsp.AudioPlayer('SampleRate',22050);

while ~isDone(hafr)
    audio = step(hafr);
    step(hap,audio);
end

pause(hap.QueueDuration); % Wait until audio plays to the end

release(hafr); % close input file, release resources
release(hap); % close audio output device, release resources
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the To Audio Device block reference page. The object properties correspond to the block parameters.

## See Also

[dsp.AudioFileReader](#) | [dsp.AudioRecorder](#)

## How To

- Set the Audio Hardware API

# **dsp.AudioPlayer.clone**

---

**Purpose** Create audio player object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates an audio player object, `C`, with the same property values as `H`. The clone method creates a new unlocked object.

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.AudioPlayer.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the audio player object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.AudioPlayer.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose**

Write audio to audio output device

**Syntax**

`Y = step(H,AUDIO)`

**Description**

`Y = step(H,AUDIO)` writes one frame of AUDIO samples to the selected audio output device, Y.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.AudioRecorder

---

**Purpose** Record audio data using computer's audio device

**Description** The AudioRecorder object records audio data using the computer's audio device.

To record audio data using the computer's audio device:

- 1** Define and set up your audio recorder object. See “Construction” on page 5-102.
- 2** Call `step` to record audio data according to the properties of `dsp.AudioRecorder`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.AudioRecorder` returns an audio recorder object, `H`, that records audio samples using an audio input device in real-time.

`H = dsp.AudioRecorder('PropertyName',PropertyValue, ...)` returns an audio recorder object, `H`, with each property set to the specified value.

**Properties** **DeviceName**

Device from which to acquire audio data

Specify the device from which to acquire audio data. The default is `Default`, which is the computer's standard input device. You can use tab completion to query valid `DeviceName` assignments for your computer. by typing `H.DeviceName = '` and then pressing the tab key. The tab completion functionality shows all valid audio device names for your computer.

**SampleRate**

Number of samples per second read from audio device

Specify the number of samples per second in the signal as an integer. The default is 44100.

**NumChannels**

Number of audio channels

Specify the number of audio channels as an integer. The default is 2.

## **DeviceDataType**

Data type used by device

Specify the data type used by the device to acquire audio data as Determine from output data type, 8-bit integer, 16-bit integer, 24-bit integer, or 32-bit float. The default is Determine from output data type.

## **BufferSizeSource**

Source of Buffer Size

Specify how to determine the buffer size as Auto or Property. The default is Auto.

## **BufferSize**

Buffer size

Specify as an integer the size of the buffer that the audio recorder object uses to communicate with the audio device. This property applies when you set the BufferSizeSource property to Property. The default is 4096.

## **QueueDuration**

Size of queue in seconds

Specify the length of the audio queue, in seconds. The default is 1.0.

## **SamplesPerFrame**

Number of samples in the output signal

Specify the number of samples in the audio recorder's output as an integer. The default is 1024.

## **OutputDataType**

# dsp.AudioRecorder

---

Data type of the output

Select the output data type as `uint8`, `int16`, `int32`, `single`, or `double`. The default is `single`.

## Methods

<code>clone</code>	Create audio recorder object with same property values
<code>getNumInputs</code>	Number of expected inputs to <code>step</code> method
<code>getNumOutputs</code>	Number of outputs of <code>step</code> method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>step</code>	Record audio from computer's recording device

## Examples

Record ten seconds of speech from a microphone, and send the output to a `.wav` file:

```
har = dsp.AudioRecorder;
hmfw = dsp.AudioFileWriter('myspeech.avi','FileFormat','AVI');

disp('Speak into microphone now');

tic;
while toc < 10,
    step(hmfw, step(har));
end

release(har);
release(hmfw);
disp('Recording complete');
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the From Audio Device block reference page. The object properties correspond to the block parameters.

## See Also

`dsp.AudioFileReader` | `dsp.AudioPlayer`

## How To

- Set the Audio Hardware API

# **dsp.AudioRecorder.clone**

---

**Purpose** Create audio recorder object with same property values

**Syntax** clone(H)

**Description** clone(H) creates an audio recorder object, C, with the same property values as H. The clone method creates a new unlocked object.

# dsp.AudioRecorder.getNumInputs

---

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the `step` method

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.AudioRecorder.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the audio recorder.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.AudioRecorder.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

**Purpose** Record audio from computer's recording device

**Syntax** AUDIO = step(H)

**Description** AUDIO = step(H) reads one frame of audio samples from the selected audio input device.

# dsp.Autocorrelator

---

**Purpose** Autocorrelation sequence

**Description** The `Autocorrelator` object returns the autocorrelation sequence for a discrete-time, deterministic input, or the autocorrelation sequence estimate for a discrete-time, wide-sense stationary (WSS) random process at positive lags.

To obtain the autocorrelation sequence:

- 1 Define and set up your autocorrelator. See “Construction” on page 5-112.
- 2 Call `step` to compute the autocorrelation sequence according to the properties of `dsp.Autocorrelator`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.Autocorrelator` returns an autocorrelator, `H`, that computes the autocorrelation along the first dimension of an N-D array. By default, the autocorrelator computes the autocorrelation at lags from zero to  $N - 1$ , where  $N$  is the length of the input vector or the row dimension of the input matrix. Inputting a row vector results in a row of zero-lag autocorrelation sequence values, one for each column of the row vector. The default autocorrelator returns the unscaled autocorrelation and performs the computation in the time domain.

`H = dsp.Autocorrelator('PropertyName',PropertyValue, ...)` returns an autocorrelator, `H`, with each property set to the specified value.

**Properties** **MaximumLagSource**

Source of maximum lag

Specify how to determine the range of lags for the autocorrelation as `Auto` or `Property`. If the value of `MaximumLagSource` is `Auto`, the autocorrelator computes the autocorrelation over all nonnegative lags in the interval  $[0, N - 1]$ , where  $N$  is the length of the first dimension of the input. Otherwise, the object computes

the autocorrelation using lags in the range  $[0, \text{MaximumLag}]$ . The default is `Auto`.

## MaximumLag

Maximum positive lag

Specify the maximum lag as a positive integer. This property applies only when the `MaximumLagSource` property is `Property`. The `MaximumLag` must be less than the length of the input data. The default is 1.

## Scaling

Autocorrelation function scaling

Specify the scaling to apply to the output as `None`, `Biased`, `Unbiased`, or `Unity at zero-lag`. Set this property to `None` to generate the autocorrelation function without scaling. This option is appropriate if you are computing the autocorrelation of a nonrandom (deterministic) input.

The `Biased` option scales the autocorrelation by  $1/N$ , where  $N$  is the length of the input data. Scaling by  $1/N$  yields a biased, finite-sample approximation to the theoretical autocorrelation of a WSS random process. In spite of the bias, scaling by  $1/N$  has the desirable property that the sample autocorrelation matrix is nonnegative definite, a property possessed by the theoretical autocorrelation matrices of all wide-sense stationary random processes. The Fourier transform of the biased autocorrelation estimate is the *periodogram*, a widely used estimate of the power spectral density of a WSS process.

The `Unbiased` option scales the estimate of the autocorrelation by  $1/(N-1)$ . Scaling by  $N-1$  produces an unbiased estimate of the theoretical autocorrelation. However, using the unbiased option, you can obtain an estimate of the autocorrelation function that fails to have the nonnegative definite property.

Use the `Unity at zero-lag` option to normalize the autocorrelation estimate as identically one at lag zero. See

“Definitions” on page 5-116 for more detail on scaling. The default is `None`.

## **Method**

Domain for computing autocorrelations

Specify the domain for computing autocorrelations as `Time Domain` or `Frequency Domain`. You must set this property to `Time Domain` for fixed-point signals. The default is `Time Domain`.

## **Fixed-Point Properties**

### **FullPrecisionOverride**

Full precision override for fixed-point arithmetic

Specify whether to use full precision rules. If you set `FullPrecisionOverride` to `true`, which is the default, the object computes all internal arithmetic and output data types using full precision rules. These rules provide the most accurate fixed-point numerics. It also turns off the display of other fixed-point properties because they do not apply individually. These rules guarantee that no quantization occurs within the object. Bits are added, as needed, to ensure that no roundoff or overflow occurs. If you set `FullPrecisionOverride` to `false`, fixed-point data types are controlled through individual fixed-point property settings. For more information, see “Full Precision for Fixed-Point System Objects”.

### **RoundingMethod**

Rounding method for fixed-point operations

Specify the rounding method as `Ceiling`, `Convergent`, `Floor`, `Nearest`, `Round`, `Simplest`, or `Zero`. This property applies only when you set the `Method` property to `Time Domain`. The default is `Floor`. This property applies only if the object is not in full precision mode.

### **OverflowAction**

Overflow action for fixed-point operations

Specify the overflow action as `Wrap` or `Saturate`. This property applies only when you set the `Method` property to `Time Domain`. The default is `Wrap`. This property applies only if the object is not in full precision mode.

## **ProductDataType**

Product word and fraction lengths

Specify the product fixed-point data type as one of `Full precision`, `Same as input`, or `Custom`. This property applies only when you set the `Method` property to `Time Domain`. The default is `Full precision`

## **CustomProductDataType**

Product word and fraction lengths

Specify the product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `Method` property to `Time Domain` and the `ProductDataType` property to `Custom`. The default is `numericType([],32,30)`.

## **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point data type as one of `Full precision`, `Same as product`, `Same as input`, or `Custom`. This property applies only when the `Method` property is `Time Domain`. The default is `Full precision`.

## **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `Method` property to `Time Domain` and

# dsp.Autocorrelator

---

the `AccumulatorDataType` property to `Custom`. The default is `isnumericitype([],32,30)`.

## **OutputDataType**

Output word and fraction lengths

Specify the output fixed-point data type as `Same as accumulator`, `Same as product`, `Same as input`, or `Custom`. This property applies only when the `Method` property is `Time Domain`. The default is `Same as accumulator`.

## **CustomOutputDataType**

Output word and fraction lengths

Specify the output fixed-point type as a scaled `numericitype` object with a `Signedness` of `Auto`. This property applies only when you set the `Method` property to `Time Domain` and the `OutputDataType` property to `Custom`. The default is `numericitype([],16,15)`.

## **Methods**

<code>clone</code>	Create autocorrelator object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>step</code>	Autocorrelation sequence

## **Definitions**

The autocorrelation of a deterministic discrete-time sequence,  $x(n)$  is:

$$r_x(h) = \sum_{n=0}^{N-h-1} x^*(n)x(n+h) \quad h = 0, 1, \dots, N-1$$

where  $h$  is the lag and  $*$  denotes the complex conjugate. If the input is a length  $N$  realization of a WSS stationary random process,  $r_x(h)$  is an estimate of the theoretical autocorrelation:

$$\rho_x(h) = E\{x^*(n)x(n+h)\}$$

where  $E\{\}$  is the expectation operator. The Unity at zero-lag normalization divides each sequence value by the autocorrelation or autocorrelation estimate at zero lag.

$$\frac{\rho_x(h)}{\rho_x(0)} = \frac{E\{x^*(n)x(n+h)\}}{E\{|x(0)|^2\}}$$

The most commonly used estimate of the theoretical autocorrelation of a WSS random process is the biased estimate:

$$\hat{\rho}_x(h) = \frac{1}{N} \sum_{k=0}^{N-h-1} x^*(k)x(k+h)$$

## Examples

Compute autocorrelation for all positive lags:

```

hac1 = dsp.Autocorrelator;
% x is a column vector
x = [1:100]';
y = step(hac1, x);

```

---

Compute the autocorrelation of a sine wave in white Gaussian noise with approximate 95% upper and lower confidence limits:

```


S = rng('default');
% Sine wave with period N=4
x = 1.4*cos(pi/2*(1:100))'+randn(100,1);

```

## dsp.Autocorrelator

---

```
MaxLag = 20;
H = dsp.Autocorrelator('MaximumLagSource',...
    'Property','MaximumLag',MaxLag,'Scaling','Unity at zero-lag');
SigAutocorr = step(H,x);
stem(SigAutocorr,'b','markerfacecolor',[0 0 1]);
line(1:MaxLag+1,1.96/sqrt(100)*ones(MaxLag+1,1),...
    'linestyle','-.','linewidth',2);
line(1:MaxLag+1,-1.96/sqrt(100)*ones(MaxLag+1,1),...
    'linestyle','-.','linewidth',2);
axis([1 20 -1 1]);
title('Sine Wave + Noise Autocorrelation'); xlabel('Lag');
```



As this figure shows, the autocorrelation estimate demonstrates the four sample periodic sine wave with excursions outside the 95% white Gaussian noise confidence limits every two samples.

# **dsp.Autocorrelator**

---

## **Algorithms**

This object implements the algorithm, inputs, and outputs described on the Autocorrelation block reference page. The object properties correspond to the block parameters.

## **See Also**

`dsp.Crosscorrelator`

**Purpose** Create autocorrelator object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates an autocorrelator object, `C`, with the same property values as `H`. The `clone` method creates a new unlocked object.

# **dsp.Autocorrelator.getNumInputs**

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose** Number of outputs of step method

**Syntax** N = getNumOutputs(H)

**Description** N = getNumOutputs(H) returns the number of outputs, N, of the step method

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# dsp.Autocorrelator.isLocked

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the autocorrelator.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

# dsp.Autocorrelator.step

---

**Purpose** Autocorrelation sequence

**Syntax**  $Y = \text{step}(H,X)$

**Description**  $Y = \text{step}(H,X)$  computes the autocorrelation sequence  $Y$  for the columns of the input  $X$ .

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

<b>Purpose</b>	IIR filter using biquadratic structures
<b>Description</b>	<p>The <code>BiquadFilter</code> object implements an IIR filter structure using biquadratic or second-order sections (SOS).</p> <p>To implement an IIR filter structure using biquadratic or SOS:</p> <ol style="list-style-type: none"><li>1 Define and set up your biquadratic IIR filter. See “Construction” on page 5-127.</li><li>2 Call <code>step</code> to implement the IIR filter according to the properties of <code>dsp.BiquadFilter</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.BiquadFilter</code> returns a default biquadratic IIR filter, <code>H</code>, which independently filters each channel of the input over successive calls to the <code>step</code> method using the SOS section <code>[1 0.3 0.4 1 0.1 0.2]</code> with a direct-form II transposed structure.</p> <p><code>H = dsp.BiquadFilter('PropertyName',PropertyValue, ...)</code> returns a biquadratic filter object, <code>H</code>, with each property set to the specified value.</p>
<b>Properties</b>	<p><b>Structure</b></p> <p>Filter structure</p> <p>Specify the filter structure as one of   Direct form I   Direct form I transposed   Direct form II   Direct form II transposed  . The default is Direct form II transposed.</p> <p><b>SOSMatrixSource</b></p> <p>SOS matrix source</p> <p>Specify the source of the SOS matrix as one of   Property   Input port  . The default is Property.</p> <p><b>SOSMatrix</b></p> <p>SOS matrix</p>

Specify the second-order section (SOS) matrix as an N-by-6 matrix, where N is the number of sections in the filter. The default is [1 0.3 0.4 1 0.1 0.2]. Each row of the SOS matrix contains the numerator and denominator coefficients of the corresponding section of the filter. The system function,  $H(z)$ , of a biquad filter is:

$$H(z) = \frac{\sum_{k=0}^2 b_k z^{-k}}{1 - \sum_{l=1}^2 a_l z^{-l}}$$

The coefficients are ordered in the rows of the SOS matrix as  $(b_0, b_1, b_2, 1, -a_1, -a_2)$ . You can use coefficients of real or complex values. This property applies only when you set the `SOSMatrixSource` property to `Property`. The leading denominator coefficient of the biquad filter,  $a_0$ , equals 1 for each filter section, regardless of the specified value. This property is tunable when the `OptimizeUnityScaleValues` property is `false`.

## ScaleValues

Scale values for each biquad section

Specify the scale values to apply before and after each section of a biquad filter. `ScaleValues` must be either a scalar or a vector of length N+1, where N is the number of sections. If you set this property to a scalar, the scalar value is used as the gain value only before the first filter section. The remaining gain values are set to 1. If you set this property to a vector of N+1 values, each value is used for a separate section of the filter.

This property applies only when you set the `SOSMatrixSource` property to `Property`. The default is 1. This property is tunable when the `OptimizeUnityScaleValues` property is `false`.

## InitialConditions

Initial conditions for direct form II structures

Specify the initial conditions of the filter states when the `Structure` property is one of `| Direct form II | Direct form II transposed |`. The number of states or delay elements (zeros and poles) in a direct-form II biquad filter equals twice the number of filter sections. You can specify the initial conditions as a scalar, vector, or matrix.

When you specify a scalar value, the biquad filter initializes all delay elements in the filter to that value. When you specify a vector of length equal to the number of delay elements in the filter, each vector element specifies a unique initial condition for the corresponding delay element.

The biquad filter applies the same vector of initial conditions to each channel of the input signal. When you specify a vector of length equal to the product of the number of input channels and the number of delay elements in the filter, each element specifies a unique initial condition for the corresponding delay element in the corresponding channel. When you specify a matrix with the same number of rows as the number of delay elements in the filter, and one column for each channel of the input signal, each element specifies a unique initial condition for the corresponding delay element in the corresponding channel. The default is the scalar 0.

## **NumeratorInitialConditions**

Initial conditions on zeros side

Specify the initial conditions of the filter states on the side of the filter structure with the zeros. This property applies only when you set the `Structure` property to one of `| Direct form I | Direct form I transposed |`. The number of states or delay elements in the numerator of a direct-form I biquad filter equals twice the number of filter sections. You can specify the initial conditions as a scalar, vector, or matrix. When you specify a scalar, the biquad filter initializes all delay elements on the zeros side in the filter to that value. When you specify a vector of length equal to the number of delay elements on the zeros side in the

filter, each vector element specifies a unique initial condition for the corresponding delay element on the zeros side.

The biquad filter applies the same vector of initial conditions to each channel of the input signal. When you specify a vector of length equal to the product of the number of input channels and the number of delay elements on the zeros side in the filter, each element specifies a unique initial condition for the corresponding delay element on the zeros side in the corresponding channel. When you specify a matrix with the same number of rows as the number of delay elements on the zeros side in the filter, and one column for each channel of the input signal, each element specifies a unique initial condition for the corresponding delay element on the zeros side in the corresponding channel. The default is the scalar 0.

## **DenominatorInitialConditions**

Initial conditions on poles side

Specify the initial conditions of the filter states on the side of the filter structure with the poles. This property only applies when you set the `Structure` property to one of `| Direct form I` `| Direct form I transposed |`. The number of denominator states, or delay elements, in a direct-form I (noncanonic) biquad filter equals twice the number of filter sections. You can specify the initial conditions as a scalar, vector, or matrix. When you specify a scalar, the biquad filter initializes all delay elements on the poles side of the filter to that value. When you specify a vector of length equal to the number of delay elements on the poles side in the filter, each vector element specifies a unique initial condition for the corresponding delay element on the poles side.

The object applies the same vector of initial conditions to each channel of the input signal. When you specify a vector of length equal to the product of the number of input channels and the number of delay elements on the poles side in the filter, each element specifies a unique initial condition for the corresponding delay element on the poles side in the corresponding channel.

When you specify a matrix with the same number of rows as the number of delay elements on the poles side in the filter, and one column for each channel of the input signal, each element specifies a unique initial condition for the corresponding delay element on the poles side in the corresponding channel. The default is the scalar 0.

## **OptimizeUnityScaleValues**

Optimize unity scale values

When this Boolean property is set to `true`, the biquad filter removes all unity scale gain computations. This reduces the number of computations and increases the fixed-point accuracy. This property applies only when you set the `SOSMatrixSource` property to `Property`. The default is `true`.

## **ScaleValuesInputPort**

How to specify scale values

Select how to specify scale values. This property applies only when the `SOSMatrixSource` property is `Input port`. By default, this property is `true`, and the scale values are specified via the input port. When this property is `false`, all scale values are 1.

## **FrameBasedProcessing**

Enable frame-based processing

Set this property to `true` to enable frame-based processing. When this property is `true`, the biquad filter treats each column as an independent channel. Set this property to `false` to enable sample-based processing. When this property is `false`, the biquad filter treats each element of the input as an individual channel. The default is `true`.

## **Fixed-Point Properties**

### **RoundingMethod**

Rounding method for fixed-point operations

# dsp.BiquadFilter

---

Specify the rounding method as one of | Ceiling | Convergent | Floor | Nearest | Round | Simplest | Zero |. The default is Floor.

## **OverflowAction**

Overflow action for fixed-point operations

Specify the overflow action as one of | Wrap | Saturate |. The default is Wrap.

## **MultiplicandDataType**

Multiplicand word and fraction lengths

Specify the multiplicand fixed-point data type as one of | Same as output | Custom |. This property applies only when you set the Structure property to Direct form I transposed. The default is Same as output.

## **CustomMultiplicandDataType**

Custom multiplicand word and fraction lengths

Specify the multiplicand fixed-point type as a scaled numeric type object with a Signedness of Auto. This property applies only when you set the MultiplicandDataType property to Custom. The default is numeric type([],32,30).

## **SectionInputDataType**

Section input word and fraction lengths

Specify the section input fixed-point data type as one of | Same as input | Custom |. The default is Same as input.

## **CustomSectionInputDataType**

Custom section input word and fraction lengths

Specify the section input fixed-point type as a scaled numeric type object with a Signedness of Auto. This property applies only when you set the SectionInputDataType property to Custom. The default is numeric type([],16,15).

## **SectionOutputDataType**

Section output word and fraction lengths

Specify the section output fixed-point data type as one of | Same as section input | Custom |. The default is Same as section input.

## **CustomSectionOutputDataType**

Custom section output word and fraction lengths

Specify the section output fixed-point type as a signed, scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `SectionOutputDataType` property to `Custom`. The default is `numericType([],16,15)`.

## **NumeratorCoefficientsDataType**

Numerator coefficients word and fraction lengths

Specify the numerator coefficients fixed-point data type as one of | Same word length as input | Custom |. This property applies only when you set the `SOSMatrixSource` property to `Property`. Setting this property also sets the `DenominatorCoefficientsDataType` and `ScaleValuesDataType` properties to the same value. The default is Same word length as input.

## **CustomNumeratorCoefficientsDataType**

Custom numerator coefficients word and fraction lengths

Specify the numerator coefficients fixed-point type as a `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `SOSMatrixSource` property to `Property` and the `NumeratorCoefficientsDataType` property to `Custom`. The word length of the `CustomNumeratorCoefficientsDataType`, `CustomDenominatorCoefficientsDataType`, and `CustomScaleValuesDataType` properties must be the same. The default is `numericType([],16,15)`.

## **DenominatorCoefficientsDataType**

Denominator coefficients word and fraction lengths

Specify the denominator coefficients fixed-point data type as one of | Same word length as input | Custom |. This property applies only when you set the `SOSMatrixSource` property to `Property`. Setting this property also sets the `NumeratorCoefficientsDataType` and `ScaleValuesDataType` properties to the same value. The default is Same word length as input.

## **CustomDenominatorCoefficientsDataType**

Custom denominator coefficients word and fraction lengths

Specify the denominator coefficients fixed-point type as a `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `SOSMatrixSource` property to `Property` and the `DenominatorCoefficientsDataType` property to `Custom`. The `CustomNumeratorCoefficientsDataType`, `CustomDenominatorCoefficientsDataType`, and `CustomScaleValuesDataType` properties must have the same word lengths. The default is `numericType([],16,15)`.

## **ScaleValuesDataType**

Scale values word and fraction lengths

Specify the scale values fixed-point data type as one of | Same word length as input | Custom |. This property applies only when you set the `SOSMatrixSource` property to `Property`. Setting this property also sets the `NumeratorCoefficientsDataType` and `DenominatorCoefficientsDataType` properties to the same value. The default is Same word length as input.

## **CustomScaleValuesDataType**

Custom scale values word and fraction lengths

Specify the scale values fixed-point type as a `numericType` object with a `Signedness` of `Auto`. This property applies

only when you set the `SOSMatrixSource` property to `Property` and the `ScaleValuesDataType` property to `Custom`. The `CustomNumeratorCoefficientsDataType`, `CustomDenominatorCoefficientsDataType`, and `CustomScaleValuesDataType` properties must have the same word lengths. The default is `numerictype([],16,15)`.

## **NumeratorProductDataType**

Numerator product word and fraction lengths

Specify the product fixed-point data type as one of `| Same as input | Custom |`. Setting this property also sets the `DenominatorProductDataType` property to the same value. The default is `Same as input`.

## **CustomNumeratorProductDataType**

Custom numerator product word and fraction lengths

Specify the product fixed-point type as a scaled `numerictype` object with a `Signedness` of `Auto`. This property applies only when you set the `NumeratorProductDataType` property to `Custom`. The `CustomNumeratorProductDataType` and `CustomDenominatorProductDataType` properties must have the same word lengths. The default is `numerictype([],32,30)`.

## **DenominatorProductDataType**

Denominator product word and fraction lengths

Specify the product fixed-point data type as one of `| Same as input | Custom |`. Setting this property also sets the `NumeratorProductDataType` property to the same value. The default is `Same as input`.

## **CustomDenominatorProductDataType**

Custom denominator product word and fraction lengths

Specify the product fixed-point type as a scaled `numerictype` object with a `Signedness` of `Auto`. This property applies only when you set the `DenominatorProductDataType`

to Custom. The `CustomNumeratorProductDataType` and `CustomDenominatorProductDataType` properties must have the same word lengths. The default is `numerictype([],32,30)`.

## **NumeratorAccumulatorDataType**

Numerator accumulator word and fraction lengths

Specify the numerator accumulator fixed-point data type as one of `| Same as input | Same as product | Custom |`. Setting this property also sets the `DenominatorAccumulatorDataType` property to the same value. The default is `Same as product`.

## **CustomNumeratorAccumulatorDataType**

Custom numerator accumulator word and fraction lengths

Specify the numerator accumulator fixed-point type as a scaled `numerictype` object with a `Signedness` of `Auto`. This property applies only when you set the `NumeratorAccumulatorDataType` property to `Custom`. The `CustomNumeratorAccumulatorDataType` and `CustomDenominatorAccumulatorDataType` properties must have the same word lengths. The default is `numerictype([],32,30)`.

## **DenominatorAccumulatorDataType**

Denominator accumulator word and fraction lengths

Specify the denominator accumulator fixed-point data type as one of `| Same as input | Same as product | Custom |`. Setting this property also sets the `NumeratorAccumulatorDataType` property to the same value. The default is `Same as product`.

## **CustomDenominatorAccumulatorDataType**

Custom denominator accumulator word and fraction lengths

Specify the denominator accumulator fixed-point type as a scaled `numerictype` object with a `Signedness` of `Auto`. This property applies only when you set the `DenominatorAccumulatorDataType` property to `Custom`. The `CustomNumeratorAccumulatorDataType` and `CustomDenominatorAccumulatorDataType` properties

must have the same word lengths. The default is `numericType([],32,30)`.

## **StateDataType**

State word and fraction lengths

Specify the state fixed-point data type as one of | Same as input | Same as accumulator | Custom|. This property applies when you set the Structure property to Direct form II or Direct form II transposed. The default is Same as accumulator.

## **CustomStateDataType**

Custom state word and fraction lengths

Specify the state fixed-point type as a scaled `numericType` object with a Signedness of Auto. This property applies only when you set the `StateDataType` property to Custom. The default is `numericType([],16,15)`.

## **NumeratorStateDataType**

Numerator state word and fraction lengths

Specify the numerator state fixed-point data type as one of | Same as input | Same as accumulator | Custom|. Setting this property also sets the `DenominatorStateDataType` property to the same value. This property applies only when you set the Structure property to Direct form I transposed. The default is Same as accumulator.

## **CustomNumeratorStateDataType**

Custom numerator state word and fraction lengths

Specify the numerator state fixed-point type as a scaled `numericType` object with a Signedness of Auto. This property applies only when you set the `StateDataType` property to Custom. The `CustomNumeratorProductDataType` and `CustomDenominatorProductDataType` properties must have the same word lengths. The default is `numericType([],16,15)`.

## **DenominatorStateDataType**

Denominator state word and fraction lengths

Specify the denominator state fixed-point data type as one of | Same as input | Same as accumulator | Custom |. Setting this property also sets the NumeratorStateDataType property to the same value. This property applies only when you set the Structure property to Direct form I transposed. The default is Same as accumulator.

## **CustomDenominatorStateDataType**

Custom denominator state word and fraction lengths

Specify the denominator state fixed-point type as a scaled numeric type object with a Signedness of Auto. This property applies only when you set the StateDataType property to Custom. The CustomNumeratorStateDataType and CustomDenominatorStateDataType properties must have the same word lengths. The default is numeric type ([ ], 16, 15).

## **OutputDataType**

Output word and fraction lengths

Specify the output fixed-point data type as one of | Same as input | Same as accumulator | Custom |. The default is Same as accumulator.

## **CustomOutputDataType**

Custom output word and fraction lengths

Specify the output fixed-point type as a scaled numeric type object with a Signedness of Auto. This property applies only when you set the OutputDataType property to Custom. The default is numeric type ([ ], 16, 15).

## Methods

clone	Create biquad filter object with same property values
freqz	Frequency response
fvtool	Open filter visualization tool
getNumInputs	Number of expected inputs to step method
getNumOutputs	Number of outputs of step method
impz	Impulse response
isLocked	Locked status for input attributes and nontunable properties
phasez	Unwrapped phase response
release	Allow property value and input characteristics changes
reset	Reset states of biquad filter object
step	Filter input with biquad filter object

More “Analysis Methods for Filter System Objects” on page 4-2.

## Examples

Use a fourth order, lowpass biquadratic filter object with a normalized cutoff frequency of 0.4 to filter high frequencies from an input signal. Display the result as a PSD using the Welch method:

```
t = (0:1000)'/8e3;  
xin = sin(2*pi*1e3*t)+sin(2*pi*3e3*t); % Input is 1 &  
                                     % 3kHz sinusoids  
hFromWS = dsp.SignalSource(xin, 100);  
hLog = dsp.SignalSink;  
  
[z,p,k] = ellip(4,1,60,.4); % Set up the filter  
[s,g] = zp2sos(z,p,k);
```

# dsp.BiquadFilter

---

```
hBqF=dsp.BiquadFilter('Structure','Direct form I', ...  
    'SOSMatrix',s,'ScaleValues',g);
```

```
while ~isDone(hFromWS)  
    input = step(hFromWS);  
    filteredOutput = step(hBqF,input);  
    step(hLog,filteredOutput);  
end
```

```
filteredResult = hLog.Buffer;  
swelch = spectrum.welch;  
psd(swelch,filteredResult,'Fs',8e3);
```


Design and apply a lowpass Butterworth filter using a biquad filter object. Create another object for Welch spectral analysis.

```
Fs = 10000; % Sampling frequency 10 kHz  
t = 0:(1/Fs):1;  
x = cos(2*pi*250*t)+0.5*sin(2*pi*1000*t)+0.25*cos(2*pi*2000*t);
```

```
% Design SOS Butterworth filter with fdesign.lowpass  
Hd = fdesign.lowpass('Fp,Fst,Ap,Ast',500,550,0.5,60,10000);  
D = design(Hd,'butter');  
H = dsp.BiquadFilter('SOSMatrix',D.sosMatrix,...  
    'ScaleValues',D.ScaleValues);  
y = step(H,x');
```

```
SpecWelch = spectrum.welch('Hamming',256,70);  
InputPsd = psd(SpecWelch,x,'Fs',1e4);  
OutputPsd = psd(SpecWelch,y,'Fs',1e4);
```

```
plot(InputPsd.Frequencies,10*log10(InputPsd.Data),'b');  
hold on;  
plot(OutputPsd.Frequencies,10*log10(OutputPsd.Data),'k',...  
    'linewidth',2);  
xlabel('Hz'); ylabel('dB');  
legend('Input Data','Output Data','Location','best');
```



## Algorithms

This object implements the algorithm, inputs, and outputs described on the Biquad Filter block reference page. The object properties correspond to the block parameters, except:

- **Coefficient source** – the biquad filter object does not accept `dfilt` objects as an `SOSMatrixSource`.
- **Action when the `a0` values of the SOS matrix are not one** – the biquad filter object assumes the zero-th-order denominator coefficient equals 1 regardless of the specified value. The biquad filter object does not support the `Error` or `Warn` options found in the corresponding block.

Both this object and its corresponding block let you specify whether to process inputs as individual samples or as frames of data. The object uses the `FrameBasedProcessing` property. The block uses the **Input processing** parameter. See “Set the `FrameBasedProcessing` Property of a System object” for more information.

## See Also

`dsp.DigitalFilter`

## **dsp.BiquadFilter.clone**

---

**Purpose** Create biquad filter object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a biquad filter object, `C`, with the same property values as `H`. The clone method creates a new unlocked object with uninitialized states.

**Purpose**

Frequency response

**Syntax**

```
[h,w] = freqz(H)
[h,w] = freqz(H,n)
[h,w] = freqz(H,Name,Value)
freqz(H)
```

**Description**

`[h,w] = freqz(H)` returns the complex, 8192–element frequency response vector `h`, and the corresponding frequencies `w` in radians/sample.

`[h,w] = freqz(H,n)` returns the complex, `n`-element frequency response vector `h`, and the corresponding frequencies `w` in radians/sample, using `n` samples.

`[h,w] = freqz(H,Name,Value)` returns the frequency response and the corresponding frequencies, with additional options specified by one or more `Name, Value` pair arguments.

`freqz(H)` uses `FVTool` to plot the magnitude and unwrapped phase of the frequency response of the filter `System` object `H`.

# dsp.BiquadFilter.fvtool

---

**Purpose** Open filter visualization tool

**Syntax** `fvtool(H)`  
`fvtool(H, 'Arithmetic', ARITH, ...)`

**Description** `fvtool(H)` performs an analysis and computes the magnitude response of the filter System object H.

`fvtool(H, 'Arithmetic', ARITH, ...)` analyzes the filter System object H, based on the arithmetic specified in the ARITH input. ARITH can be set to one of 'double', 'single', or 'fixed'. The analysis tool assumes a double precision filter when the arithmetic input is not specified and the filter System object is in an unlocked state. The 'Arithmetic' input is only relevant for the analysis of filter System objects.

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.BiquadFilter.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**      `N = getNumOutputs(H)` returns the number of outputs, N, of the step method

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Impulse response

**Syntax**  
`[h,t] = impz(H)`  
`[h,t] = impz(H,Name,Value)`  
`impz(H)`

**Description** `[h,t] = impz(H)` returns the impulse response `h`, and the corresponding time points `t` at which the impulse response of `H` is computed.

`[h,t] = impz(H,Name,Value)` returns the impulse response `h`, and the corresponding time points `t`, with additional options specified by one or more `Name, Value` pair arguments.

`impz(H)` uses `FVTool` to plot the impulse response of the filter System object `H`.

---

**Note** You can use `impz` for both real and complex filters. When you omit the output arguments, `impz` plots only the real part of the impulse response.

---

# dsp.BiquadFilter.isLocked

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the biquad filter object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Unwrapped phase response

**Syntax**

```
[phi,w] = phasez(H)  
[phi,w] = phasez(H,n)  
[phi,w] = phasez(H,Name,Value)  
phasez(H)
```

**Description**

`[phi,w] = phasez(H)` returns the 8192–element phase response vector `phi`, and the corresponding frequencies `w` in radians/sample.

`[phi,w] = phasez(H,n)` returns the `n`-element phase response vector `phi`, and the corresponding frequencies `w` in radians/sample, using `n` samples.

`[phi,w] = phasez(H,Name,Value)` returns the phase response and the corresponding frequencies, with additional options specified by one or more `Name, Value` pair arguments.

`phasez(H)` uses FVTool to plot the phase response of the filter System object `H`.

# dsp.BiquadFilter.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

**Purpose** Reset states of biquad filter object

**Syntax** reset(H)

**Description** reset(H) resets the filter states of the biquad filter object,H, to the specified initial conditions. After the step method applies the biquad filter object to nonzero input data, the states may change. Invoking the step method again without first invoking the reset method may produce different outputs for an identical input.

Example of resetting filter states:

```
n =0:20;
x = cos(pi/4*n)+sin(pi/2*n);
H = dsp.BiquadFilter;
y = step(H,x');
% Apply step method without invoking reset
y1 = step(H,x');
isequal(y,y1) % Returns a 0
% Reset filter states to zero
reset(H)
% Now invoke step method
y2 = step(H,x');
isequal(y,y2) % Returns a 1
```

# dsp.BiquadFilter.step

---

**Purpose** Filter input with biquad filter object

**Syntax**  
 $Y = \text{step}(H, X)$   
 $Y = \text{step}(H, X, \text{NUM}, \text{DEN})$   
 $Y = \text{step}(H, X, \text{NUM}, \text{DEN}, G)$

**Description**  $Y = \text{step}(H, X)$  filters the real or complex input signal  $X$ , and outputs the filtered values,  $Y$ . The biquad filter object filters each channel of the input signal over successive calls to the `step` method.

$Y = \text{step}(H, X, \text{NUM}, \text{DEN})$  filters the input using  $\text{NUM}$  as the numerator coefficients, and  $\text{DEN}$  as the denominator coefficients of the biquad filter.  $\text{NUM}$  must be a 3-by- $N$  numeric matrix and  $\text{DEN}$  must be a 2-by- $N$  numeric matrix, where  $N$  is the number of biquad filter sections. The object assumes that the first denominator coefficient of each section is 1. This configuration applies when the `SOSMatrixSource` property is `Input Port` and the `ScaleValuesInputPort` property is `false`.

$Y = \text{step}(H, X, \text{NUM}, \text{DEN}, G)$  specifies the scale values,  $G$ , of the biquad filter.  $G$  must be a 1-by- $(N + 1)$  numeric vector, where  $N$  is the number of biquad filter sections. This configuration applies when the `SOSMatrixSource` property is `Input Port` and the `ScaleValuesInputPort` property is `true`.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

<b>Purpose</b>	Output, error, and weights using Block LMS adaptive algorithm
<b>Description</b>	<p>The <code>BlockLMSFilter</code> object computes output, error, and weights using the Block LMS adaptive algorithm.</p> <p>To compute the output, error, and weights:</p> <ol style="list-style-type: none"><li>1 Define and set up your adaptive FIR filter. See “Construction” on page 5-153.</li><li>2 Call <code>step</code> to compute the output, error, and weights according to the properties of <code>dsp.BlockLMSFilter</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H=dsp.BlockLMSFilter</code> returns an adaptive FIR filter, <code>H</code>, that filters the input signal and computes filter weights based on the Block Least Mean Squares (LMS) algorithm.</p> <p><code>H=dsp.BlockLMSFilter('PropertyName',PropertyValue,...)</code> returns an adaptive FIR filter, <code>H</code>, with each specified property set to the specified value.</p> <p><code>H=dsp.BlockLMSFilter(length,blocksize,'PropertyName',...PropertyValue,...)</code> returns an adaptive FIR filter, <code>H</code>, with the <code>Length</code> property set to <code>length</code>, the <code>BlockSize</code> property set to <code>blocksize</code>, and other specified properties set to the specified values.</p>
<b>Properties</b>	<p><b>Length</b></p> <p>Length of FIR filter weights vector</p> <p>Specify the length of the FIR filter weights vector as a positive integer scalar. The default is 32.</p> <p><b>BlockSize</b></p> <p>Number of samples acquired before weight adaptation</p> <p>Specify the number of samples of the input signal to acquire before the object updates the filter weights. The input frame length must be an integer multiple of the block size. The default is 32.</p>

## **StepSizeSource**

Source of adaptation step size

Choose to specify the adaptation step size factor as `Property` or `Input port`. The default is `Property`.

## **StepSize**

Adaptation step size

Specify the adaptation step size factor as a scalar, nonnegative numeric value. The default is `0.1`. This property applies only when you set the `StepSizeSource` property to `'Property'`. This property is tunable.

## **LeakageFactor**

Leakage factor used in Leaky LMS algorithm

Specify the leakage factor used in Leaky LMS algorithm as a scalar numeric value between 0 and 1, both inclusive. When the value is less than 1, the System object implements a leaky LMS algorithm. The default is 1, providing no leakage in the adapting algorithm. This property is tunable.

## **InitialWeights**

Initial values of filter weights

Specify the initial values of the filter weights as a scalar or a vector of length equal to the `Length` property value. The default is 0.

## **AdaptInputPort**

Additional input to enable adaptation of filter weights.

Specify when the object should adapt the filter weights. By default, the value of this property is `false`, and the filter continuously updates the filter weights. When this property is set to `true`, an adaptation control input is provided to the `step` method. If the value of this input is nonzero, the filter continuously updates the filter weights. If the input is zero, the filter weights remain at their current value.

## WeightsResetInputPort

Additional input to enable weights reset

Specify whether the FIR filter can reset the filter weights. By default, the value of this property is `false`, and the object does not reset the weights. When this property is set to `true`, a reset control input is provided to the `step` method, and the `WeightsResetCondition` property applies. The object resets the filter weights based on the values of the `WeightsResetCondition` property and the reset input to the `step` method.

## WeightsResetCondition

Condition that triggers the resetting of filter weights

Specify the event to reset the filter weights as one of `Rising edge`, `Falling edge`, `Either edge`, or `Non-zero`. The object resets the filter weights based on the values of this property and the reset input to the `step` method. This property applies only when you set the `WeightsResetInputPort` property to `true`. The default is `Non-zero`.

## WeightsOutputPort

Output filter weights

Set this property to `true` to output the adapted filter weights. The default is `true`.

## Methods

<code>clone</code>	Create adaptive block LMS filter object with same property values
<code>getNumInputs</code>	Number of expected inputs to <code>step</code> method
<code>getNumOutputs</code>	Number of outputs of <code>step</code> method
<code>isLocked</code>	Locked status for input attributes and nontunable properties

# dsp.BlockLMSFilter

---

release	Allow property value and input characteristics changes
reset	Reset internal states of adaptive FIR filter object
step	Filter inputs using Block LMS algorithm

## Examples

Remove noise using the Block LMS adaptive algorithm:

```
hblms = dsp.BlockLMSFilter(10, 5);
hblms.StepSize = 0.01;
hblms.WeightsOutputPort = false;
hfilt = dsp.DigitalFilter;
hfilt.TransferFunction = 'FIR (all zeros)';
hfilt.Numerator = fir1(10, [.5, .75]);
x = randn(1000,1); % Noise
d = step(hfilt, x) + sin(0:.05:49.95)'; % Noise + Signal
[y, err] = step(hblms, x, d);
subplot(2,1,1), plot(d), title('Noise + Signal');
subplot(2,1,2), plot(err), title('Signal');
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Block LMS Filter block reference page. The object properties correspond to the block parameters.

## See Also

[dsp.LMSFilter](#) | [dsp.DigitalFilter](#)

**Purpose** Create adaptive block LMS filter object with same property values

**Syntax**

**Description** `C = clone(H)` creates a `BlockLMSFilter` object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with uninitialized states.

# dsp.BlockLMSFilter.getNumInputs

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**      `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose**

Number of outputs of step method

**Syntax**

`N = getNumOutputs(H)`

**Description**

`N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# **dsp.BlockLMSFilter.isLocked**

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `BlockLMSFilter` object `H`.  
The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

# **dsp.BlockLMSFilter.reset**

---

**Purpose**            Reset internal states of adaptive FIR filter object

**Syntax**            `reset(H)`

**Description**        `reset(H)` sets the internal states of the `BlockLMSFilter` object `H` to their initial values.

## Purpose

Filter inputs using Block LMS algorithm

## Syntax

```
[Y,ERR,WTS] = step(H,X,D)
[Y,ERR] = step(H,X,D)
[...] = step(H,X,D,MU)
[...] = step(H,X,D,A)
[...] = step(H,X,D,R)
[Y,ERR,WTS] = step(H,X,D,MU,A,R)
```

## Description

`[Y,ERR,WTS] = step(H,X,D)` filters the input `X`, using `D` as the desired signal, and returns the filtered output in `Y`. The filter error is in `ERR`, and the estimated filter weights is in `WTS`. The filter weights update once for every block of data that the object processes.

`[Y,ERR] = step(H,X,D)` returns only the filtered output in `Y` and the filter error in `ERR`, when the `WeightsOutputPort` property is `false`.

`[...] = step(H,X,D,MU)` uses `MU` as the step size, when you set the `StepSizeSource` property to `Input port`.

`[...] = step(H,X,D,A)` uses `A` as the adaptation control, when you set the `AdaptInputPort` property to `true`. When `A` is nonzero, the filter continuously updates the filter weights. When `A` is zero, the filter weights remain constant.

`[...] = step(H,X,D,R)` uses `R` as a reset signal, when you set the `WeightsResetInputPort` property to `true`. Use the `WeightsResetCondition` property to set the reset trigger condition. If a reset event occurs, the filter resets the filter weights to their initial values.

`[Y,ERR,WTS] = step(H,X,D,MU,A,R)` filters input `X`, using `D` as the desired signal, `MU` as the step size, `A` as the adaptation control, and `R` as the reset signal. The objects returns the filtered output in `Y`, the filter error in `ERR`, and the adapted filter weights in `WTS`. Set the properties appropriately to provide all possible inputs.

## **dsp.BlockLMSFilter.step**

---

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

<b>Purpose</b>	Buffer input signal
<b>Description</b>	<p>The Buffer object buffers an input signal. The number of samples per channel in the input must equal the difference between the output buffer size and buffer overlap (i.e., <code>Length - OverlapLength</code>). When you set <code>FrameBasedProcessing</code> to <code>true</code>, the number of samples per channel equals the number of rows in the input. If you set <code>FrameBasedProcessing</code> to <code>false</code>, the number of samples per channel equals 1.</p> <p>To buffer an input signal:</p> <ol style="list-style-type: none"><li>1 Define and set up your buffer System object. See “Construction” on page 5-165.</li><li>2 Call <code>step</code> to buffer the input according to the properties of <code>dsp.Buffer</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H=dsp.Buffer</code> returns a buffer System object, <code>HBUFF</code>, used to buffer input signals with overlap.</p> <p><code>H=dsp.Buffer('PropertyName',PropertyValuel,...)</code> returns a buffer object, <code>H</code>, with each specified property set to the specified value.</p> <p><code>H=dsp.Buffer(LEN,OVRLAP,ICS,'PropertyName',...PropertyValuel,...)</code> returns a buffer object, <code>H</code>, with <code>Length</code> property set to <code>LEN</code>, <code>OverlapLength</code> property set to <code>OVRLAP</code>, <code>InitialConditions</code> property set to <code>ICS</code> and other specified properties set to the specified values.</p>
<b>Properties</b>	<p><b>Length</b></p> <p>Number of samples to buffer</p> <p>Specify the number of consecutive samples from each input channel to buffer. You can set this property to any scalar integer greater than 0 of MATLAB built-in numeric data type. The default is 64.</p>

## OverlapLength

Amount of overlap between outputs

Specify the number of samples by which consecutive output frames overlap. You can set this property to any scalar integer greater than or equal to 0 of MATLAB built-in numeric data type. The default is 0.

## InitialConditions

Initial output

Specify the value of the object's initial output for cases of nonzero latency as a scalar, vector, or matrix. The default is 0.

## FrameBasedProcessing

Enable frame-based processing

If this property is set to `true`, each column of the input is treated as a separate channel for buffering. If the value of this property is `false`, each element of the input is treated as a separate channel. The default is `true`.

## Methods

<code>clone</code>	Create instance of an object with the same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes

reset	Reset the internal states of a System object
step	Buffer input signal based on past values

## Examples

Create a buffer of 256 samples with 128 sample overlap:

```
hreader=dsp.SignalSource(randn(1024,1),128);
hbuff=dsp.Buffer(256,128);

for i=1:8
    y=step(hbuff,step(hreader));
    % y is of length 256 with 128 samples
    % from previous input
end
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Buffer block reference page. The object properties correspond to the block properties, except as noted.

This object processes inputs as frames or as samples by setting the `FrameBasedProcessing` property. The corresponding block has a temporary **Treat Mx1 and unoriented sample-based signals as** parameter with `One channel` option for frame behavior and `M channels` option for sample behavior. See the Buffer block reference page and “Set the `FrameBasedProcessing` Property of a System object” for more information.

## See Also

`dsp.DelayLine` | `dsp.Delay`

## **dsp.Buffer.clone**

---

**Purpose** Create instance of an object with the same property values

**Syntax** `C=clone(H)`

**Description** `C=clone(H)` creates a Buffer System object C, with the same property values as H.

The `clone` method creates a new unlocked object.

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.Buffer.getNumOutputs**

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** isLocked(H)

**Description** isLocked(H) returns the locked state of the Buffer System object.

The isLocked method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the step method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the isLocked method returns a true value.

# dsp.Buffer.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Reset the internal states of a System object

**Syntax** reset(H)

**Description** reset(H) resets the internal states of buffer to their initial values.

For many System objects, this method is a no-op. Objects that have internal states will describe in their help what the reset method does for that object.

The reset method is always a no-op for unlocked System objects, as the states may not be allocated when the object is not locked.

# dsp.Buffer.step

---

**Purpose** Buffer input signal based on past values

**Syntax**  $Y = \text{step}(H,X)$

**Description**  $Y = \text{step}(H,X)$  creates output  $Y$  based on current input and stored past values of  $X$  . Output length equals the `Length` property.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

<b>Purpose</b>	Estimate of autoregressive (AR) model parameters using Burg method
<b>Description</b>	<p>The BurgAREstimator object computes the estimate of the autoregressive (AR) model parameters using the Burg method.</p> <p>To compute the estimate of the AR model parameters:</p> <ol style="list-style-type: none"><li>1 Define and set up your System object. See “Construction” on page 5-175.</li><li>2 Call step to compute the estimate according to the properties of dsp.BurgAREstimator. The behavior of step is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><math>H = \text{dsp.BurgAREstimator}</math> returns a Burg BurgAREstimator System object, H, that performs parametric AR estimation using the Burg maximum entropy method.</p> <p><math>H = \text{dsp.BurgAREstimator}('PropertyName', PropertyValue, \dots)</math> returns a Burg AR estimator object, H, with each specified property set to the specified value.</p>
<b>Properties</b>	<p><b>AOutputPort</b></p> <p>Enable output of polynomial coefficients</p> <p>Set this property to true to output the polynomial coefficients, A, of the AR model the object computes. The default is true. Either the AOutputPort property, the KOutputPort property, or both must be true.</p> <p><b>KOutputPort</b></p> <p>Enable output of reflection coefficients</p> <p>Set this property to true to output the reflection coefficients, K, for the AR model that the object computes. The default is false. Either the AOutputPort property, the KOutputPort property, or both must be true.</p> <p><b>EstimationOrderSource</b></p>

# dsp.BurgAREstimator

---

Source of estimation order

Specify how to determine estimator order as Auto or Property. When you set this property to Auto, the object assumes the estimation order is one less than the length of the input vector. When you set this property to Property, the value in EstimationOrder is used. The default is Auto.

## EstimationOrder

Order of AR model

Set the AR model estimation order to a real positive integer. This property applies when you set the EstimationOrderSource to Property. The default is 4.

## Methods


clone	Create Burg AR Estimator object with same property values
getNumInputs	Number of expected inputs to step method
getNumOutputs	Number of outputs of step method
isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
step	Normalized estimate of AR model parameter

## Examples

Use the Burg AR Estimator System object to estimate the parameters of an AR model:

```
rng default; % Use default random number generator and seed
noise = randn(100,1); % Normalized white Gaussian noise
x = filter(1,[1 1/2 1/3 1/4 1/5],noise);
hburgarest = dsp.BurgAREstimator(...
```

```
'EstimationOrderSource', 'Property', ...  
'EstimationOrder', 4);  
[a, g] = step(hburgarest, x);  
x_est = filter(g, a, x);  
plot(1:100,[x x_est]);  
title('Original and estimated signals');  
legend('Original', 'Estimated');
```



# dsp.BurgAREstimator

---

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Burg AR Estimator block reference page. The object properties correspond to the block parameters, except:

**Output(s)** block parameter corresponds to the AOutputPort and the KOutputPort object properties.

## See Also

`dsp.LevinsonSolver`

**Purpose** Create Burg AR Estimator object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a BurgAREstimator System object `C`, with the same property values as `H`. The clone method creates a new unlocked object.

# **dsp.BurgAREstimator.getNumInputs**

---

**Purpose**                Number of expected inputs to step method

**Syntax**                `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.BurgAREstimator.getNumOutputs

---

**Purpose** Number of outputs of step method

**Syntax** N = getNumOutputs(H)

**Description** N = getNumOutputs(H) returns the number of outputs, N, of the step method

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# **dsp.BurgAREstimator.isLocked**

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the BurgAREstimator System object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

# dsp.BurgAREstimator.step

---

**Purpose** Normalized estimate of AR model parameter

**Syntax**  
[A,G] = step(H,X)  
[K,G] = step(H,X)  
[A,K,G] = step(H,X)

**Description** [A,G] = step(H,X) computes the normalized estimate of the AR model parameters to fit the input, X, in the least square sense. The input X must be a column vector. Output A is a column vector that contains the normalized estimate of the AR model polynomial coefficients in descending powers of z. The scalar G is the AR model gain.

[K,G] = step(H,X) returns K, a column vector containing the AR model reflection coefficients when you set the KOutputPort property to true and the AOutputPort property to false.

[A,K,G] = step(H,X) returns the AR model polynomial coefficients A, reflection coefficients K, and the scalar gain G when the AOutputPort and KOutputPort properties are both true.

---

**Note** The object performs an initialization the first time the step method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the release method to unlock the object.

---

## Purpose

Parametric spectral estimate using Burg method

## Description

The `BurgSpectrumEstimator` object computes a parametric spectral estimate of the input using the Burg method. The object fits an autoregressive (AR) model to the signal by minimizing the forward and backward prediction errors (via least-squares). The AR parameters are constrained to satisfy the Levinson-Durbin recursion.

To compute the parametric spectral estimate of the input:

- 1 Define and set up your System object. See “Construction” on page 5-185.
- 2 Call `step` to compute the estimate according to the properties of `dsp.BurgSpectrumEstimator`. The behavior of `step` is specific to each object in the toolbox.

## Construction

`H = dsp.BurgSpectrumEstimator` returns an object, `H`, that estimates the power spectral density (PSD) of the input frame using the Burg method.

`H =`

`dsp.BurgSpectrumEstimator('PropertyName',PropertyValue,...)` returns a spectrum estimator, `H`, with each specified property set to the specified value.

## Properties

### EstimationOrderSource

Source of estimation order

Specify the source of the estimation order as `Auto` or `Property`. If you set this property to `Auto`, the object assumes the estimation order is one less than the length of the input vector. The default value is `Property`.

### EstimationOrder

Order of AR model

# dsp.BurgSpectrumEstimator

---

Specify the order of AR model as a real positive integer. This property applies only when you set the `EstimationOrderSource` property to `Property`. The default value is 6.

## **FFTLengthSource**

Source of FFT length

Specify the source of the FFT length as `Auto` or `Property`. When you set this property to `Auto`, the object assumes the FFT length is one more than the estimation order. When you set this property to `Property`, the `FFTLength` property value must be an integer power of two.

## **FFTLength**

FFT length as power-of-two integer value

Specify the FFT length as a power-of-two numeric scalar. This property applies when you set the `FFTLengthSource` property to `Property`. The default value is 256.

## **SampleRate**

Sample rate of input time series

Specify the sampling rate of the original input time series as a positive numeric scalar in hertz. The default value is 1.

## **Methods**

<code>clone</code>	Create estimator object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties

release	Allow property value and input characteristics changes
step	Estimate of power spectral density

## Examples

Estimate PSD using the Burg method:

```
x = randn(100,1);
h = dsp.BurgSpectrumEstimator('EstimationOrder', 4);
y = filter(1,[1 1/2 1/3 1/4 1/5],x); % Fourth order AR filter
p = step(h,y); % Uses default FFT length of 256

plot([0:255]/256, p);
title('Burg Method Spectral Density Estimate');
xlabel('Normalized frequency'); ylabel('Power/frequency');
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Burg Method block reference page. The object properties correspond to the block properties.

## See Also

[dsp.BurgAREstimator](#) | [dsp.LevinsonSolver](#)

# **dsp.BurgSpectrumEstimator.clone**

---

**Purpose** Create estimator object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a `BurgSpectrumEstimator` object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object.

# **dsp.BurgSpectrumEstimator.getNumInputs**

---

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.BurgSpectrumEstimator.getNumOutputs**

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `BurgSpectrumEstimator` object `H`.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.BurgSpectrumEstimator.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Estimate of power spectral density

**Syntax**  $Y = \text{step}(H,X)$

**Description**  $Y = \text{step}(H,X)$  outputs  $Y$ , a spectral estimate of input  $X$ , using the Burg method.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.CepstralToLPC

---

<b>Purpose</b>	Convert cepstral coefficients to linear prediction coefficients	
<b>Description</b>	The <code>CepstralToLPC</code> object converts cepstral coefficients to linear prediction coefficients (LPC). To convert cepstral coefficients to LPC:  <ol style="list-style-type: none"><li>1 Define and set up your System object. See “Construction” on page 5-194.</li><li>2 Call <code>step</code> to convert the coefficients according to the properties of <code>dsp.CepstralToLPC</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>	
<b>Construction</b>	<code>H=dsp.CepstralToLPC</code> returns a System object, <code>H</code> , that converts the cepstral coefficients (CCs) to linear prediction coefficients (LPCs).  <code>H=dsp.CepstralToLPC('PropertyName',PropertyValue,...)</code> returns a Cepstral to LPC object, <code>H</code> , with each specified property set to the specified value.	
<b>Properties</b>	<b>PredictionErrorOutputPort</b>	Enable prediction error power output  Set this property to <code>true</code> to output the prediction error power. The prediction error power is the power of the error output of an FIR analysis filter represented by the LPCs for a given input signal. The default is <code>false</code> .
<b>Methods</b>	<code>clone</code>	Create cepstral to LPC object with same property values
	<code>getNumInputs</code>	Number of expected inputs to the method
	<code>getNumOutputs</code>	Number of outputs of the method

isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
step	LPC coefficients from column of cepstral coefficients

## Examples

Convert cepstral coefficients to linear prediction coefficients (LPC):

```
cc=[0 0.9920 0.4919 0.3252 0.2418 , ...  
0.1917 0.1583 0.1344 0.1165 0.0956]';  
hcc2lpc=dsp.CepstralToLPC;  
a=step(hcc2lpc,cc);
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the [LPC to/from Cepstral Coefficients](#) block reference page. The object properties correspond to the block parameters.

## See Also

[dsp.LPCToCepstral](#) | [dsp.LSFToLPC](#) | [dsp.RCToLPC](#)

# **dsp.CepstralToLPC.clone**

---

**Purpose** Create cepstral to LPC object with same property values

**Syntax** `C=clone(H)`

**Description** `C=clone(H)` creates a `CepstralToLPC` System object `C`, with the same property values as `H`.

The `clone` method creates a new unlocked object.

**Purpose**                      Number of expected inputs to the `step` method

**Syntax**                      `N = getNumInputs(H)`

**Description**                `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

## **dsp.CepstralToLPC.getNumOutputs**

---

**Purpose**            Number of outputs of the `step` method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `CepstralToLPC` System object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.CepstralToLPC.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** LPC coefficients from column of cepstral coefficients

**Syntax** `A=step(H,CC)`  
`[A,P]=step(H,CC)`

**Description** `A=step(H,CC)` computes the linear prediction coefficients (LPC) coefficients, `A`, from the columns of cepstral coefficients, `CC`.  
`[A,P]=step(H,CC)` converts the columns of the cepstral coefficients `CC` to the LPCs and returns the prediction error power `P` when the `PredictionErrorOutputPort` property is true.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.Chirp

---

**Purpose** Generate swept-frequency cosine (chirp) signal

**Description** The Chirp object generates a swept-frequency cosine (chirp) signal.  
To generate the chirp signal:

- 1 Define and set up your chirp signal. See “Construction” on page 5-202.
- 2 Call `step` to generate the signal according to the properties of `dsp.Chirp`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.Chirp` returns a chirp signal, `H`, with unity amplitude.  
`H = dsp.Chirp('PropertyName',PropertyValue,...)` returns a chirp signal, `H`, with each specified property set to the specified value.

**Properties** **Type**

Frequency sweep type

Specify the frequency sweep type as `Swept cosine`, `Linear`, `Logarithmic`, or `Quadratic`. This property specifies how the output instantaneous frequency sweep varies over time. The default value is `Linear`.

**SweepDirection**

Sweep direction

Specify the sweep direction as either `Unidirectional` or `Bidirectional`. The default value is `Unidirectional`.

**InitialFrequency**

Initial frequency (hertz)

When you set the `Type` property to `Linear`, `Quadratic`, or `Logarithmic`, this property specifies the initial instantaneous frequency in hertz of the output chirp signal. When you set the `Type` property to `Logarithmic`, the value of this property is one

less than the actual initial frequency of the sweep. Also, when the sweep is logarithmic, the initial frequency must be less than the target frequency, specified by the TargetFrequency property. This property is tunable. The default value is 1000.

### TargetFrequency

Target frequency (hertz)

When you set the Type property to Linear, Quadratic, or Logarithmic, this property specifies the instantaneous frequency of the output signal in hertz at the target time. When you set the Type property to Swept Cosine, the target frequency is the instantaneous frequency of the output at half the target time. Also, when the sweep is logarithmic, the target frequency must be greater than the initial frequency, specified by the InitialFrequency property. This property is tunable. The default value is 4000.

### TargetTime

Target time

When you set the Type property to Linear, Quadratic, or Logarithmic, this property specifies the target time in seconds at which the target frequency is reached. When you set the Type property to Swept cosine, this property specifies the time at which the sweep reaches  $2f_{tgt} - f_{init}$  Hz, where  $f_{tgt}$  is the TargetFrequency and  $f_{init}$  is the InitialFrequency. The target time should not be greater than the sweep time, specified by the SweepTime property. This property is tunable. The default value is 1.

### SweepTime

Sweep time

When you set the SweepDirection property to Unidirectional, the sweep time in seconds is the period of the output frequency sweep. When you set the SweepDirection property to Bidirectional, the sweep time is half the period of the output

frequency sweep. The sweep time should be no less than the target time, specified by the `TargetTime`. This property must be a positive numeric scalar and is tunable. The default value is 1.

## **InitialPhase**

Initial phase

Specify initial phase of the output in radians at time  $t = 0$ . This property is tunable. The default value is 0.

## **SampleRate**

Sample rate

Specify the sampling rate of the output in hertz as a positive numeric scalar. The default value is 8000.

## **SamplesPerFrame**

Samples per output frame

Specify the number of samples to buffer into each output as a positive integer. The default value is 1.

## **OutputDataType**

Output data type

Specify the output data type as `double` or `single`. The default value is `double`.

## **Methods**

<code>clone</code>	Create chirp object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties

release	Allow property value and input characteristics changes
reset	Reset internal states of chirp object
step	Generate chirp signal

**Examples**

Generate a bidirectional swept chirp signal:

```
hchirp = dsp.Chirp(...  
    'SweepDirection', 'Bidirectional', ...  
    'TargetFrequency', 25, ...  
    'InitialFrequency', 0,...  
    'TargetTime', 1, ...  
    'SweepTime', 1, ...  
    'SamplesPerFrame', 400, ...  
    'SampleRate', 400);  
plot(step(hchirp));
```

**Algorithms**

This object implements the algorithm, inputs, and outputs described on the Chirp block reference page. The object properties correspond to the block parameters.

**See Also**

dsp.SineWave

# **dsp.Chirp.clone**

---

**Purpose** Create chirp object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a Chirp object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with uninitialized states.

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.Chirp.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the Chirp object H.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.Chirp.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Reset internal states of chirp object

**Syntax** reset(H)

**Description** reset(H) sets the internal states of the Chirp object H to their initial values. After you reset H, the frequency sweep restarts from the beginning.

# dsp.Chirp.step

---

**Purpose** Generate chirp signal

**Syntax**  $Y = \text{step}(H)$

**Description**  $Y = \text{step}(H)$  returns a swept-frequency cosine output,  $Y$ .

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

<b>Purpose</b>	Decimate input using Cascaded Integrator-Comb filter
<b>Description</b>	<p>The <code>CICDecimator</code> object decimates inputs using a Cascaded Integrator-Comb filter. Inputs and outputs to the object have signed fixed-point data types. You must have a Fixed-Point Toolbox license to use the <code>CICDecimator System</code> object.</p> <p>To decimate inputs using a CIC filter:</p> <ol style="list-style-type: none"><li>1 Define and set up your System object. See “Construction” on page 5-213.</li><li>2 Call <code>step</code> to decimate the input according to the properties of <code>dsp.CICDecimator</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.CICDecimator</code> returns a <code>CICDecimator System</code> object, <code>H</code>, that you can use to decimate the input with a cascaded integrator-comb (CIC) decimation filter.</p> <p><code>H = dsp.CICDecimator('PropertyName',PropertyValue,...)</code> returns a <code>CICDecimator</code> object, <code>H</code>, with each specified property set to the value you specify.</p> <p><code>H = dsp.CICDecimator(R,M,N,'PropertyName', PropertyValue, ...)</code> returns a <code>CICDecimator</code> object, <code>H</code>, with the <code>DecimationFactor</code> property set to <code>R</code>, the <code>DifferentialDelay</code> property set to <code>M</code>, the <code>NumSections</code> property set to <code>N</code>, and any other specified properties set to the values you specify.</p>
<b>Properties</b>	<p><b>DecimationFactor</b></p> <p>Decimation factor of filter</p> <p>Specify a positive integer amount by which the object decimates the input. The default is 2.</p> <p><b>DifferentialDelay</b></p> <p>Differential delay of filter comb sections</p>

Specify a positive integer delay value for the object to use in each comb section of the filter. The default is 1.

## **NumSections**

Number of integrator and comb sections

Specify the number of integrator and comb sections in the CIC filter as a positive integer value. The default is 2.

## **FixedPointDataType**

Fixed-point property setting

Specify the fixed-point data type as one of | Full precision | Minimum section word lengths | Specify word lengths | Specify word and fraction lengths |. The default is Full precision. When you set this property to:

- Full precision – the CICDecimator object automatically determines the word and fraction lengths of the filter sections and output.
- Minimum section word length – the object automatically determines the word and fraction lengths of the filter sections and the fraction length of the output. You must specify the OutputWordLength.
- Specify word lengths – the object automatically determines the fraction lengths of the filter sections and the output. You must specify values for the OutputWordLength and the SectionWordLengths properties.
- Specify word and fraction lengths, – the object does not automatically determine word and fraction lengths for the filter sections or the output. You must specify them using the OutputFractionLength, OutputWordLength, SectionFractionLengths, and SectionWordLengths properties.

## **SectionWordLengths**

Word length of each filter section

Specify the fixed-point word length for each section of the CIC filter as a scalar or a vector of length  $2 \times \text{NumSections}$ . This property applies only when you set the `FixedPointDataType` property to either `Specify word lengths` or `Specify word and fraction lengths`. The default is [16 16 16 16].

### **SectionFractionLengths**

Fraction length of each filter section

Specify the fixed-point fraction length for each section of the CIC filter as a scalar or a vector of length  $2 \times \text{NumSections}$ . This property applies only when you set the `FixedPointDataType` property to `Specify word and fraction lengths`. The default is 0.

### **OutputWordLength**

Word length of filter output

Specify the fixed-point word length for the filter output. This property applies only when you set the `FixedPointDataType` property to `Minimum section word lengths`, `Specify word lengths`, or `Specify word and fraction lengths`. The default is 32.

### **OutputFractionLength**

Fraction length of filter output

Specify the fixed-point fraction length for the output of the CIC filter. This property applies only when you set the `FixedPointDataType` property to `Specify word and fraction lengths`. The default is 0.

## **Methods**

<code>clone</code>	Create CIC Decimator object with same property values
<code>freqz</code>	Frequency response

# dsp.CICDecimator

---

fvtool	Open filter visualization tool
getNumInputs	Number of expected inputs to step method
getNumOutputs	Number of outputs of step method
impz	Impulse response
isLocked	Locked status for input attributes and nontunable properties
phasez	Unwrapped phase response
release	Allow property value and input characteristics changes
reset	Reset filter states of CIC decimator object
step	Decimate input using Cascaded Integrator-Comb filter

More “Analysis Methods for Filter System Objects” on page 4-2.

## Examples

Decimate signal by a factor of 4 (i.e., downsample the signal from 44.1 kHz to 11.025 kHz):

```
hciddec = dsp.CICDecimator(4);  
%   DecimationFactor = 4  
%   default NumSections = 2 and DifferentialDelay = 1  
hciddec.FixedPointDataType = 'Minimum section word lengths';  
hciddec.OutputWordLength = 16;  
  
% Create fixed-point sinusoidal input signal  
Fs = 44.1e3;           % Original sampling frequency  
n = (0:1023)';        % 1024 samples, 0.0232 sec signal  
x = fi(sin(2*pi*1e3/Fs*n),true,16,15);  
  
% Create SignalSource System object
```

```
hsr = dsp.SignalSource(x, 64);

% Decimate output with 16 samples per frame
y = zeros(16,16);
for ii=1:16
    y(ii,:) = step(hcicdec, step( hsr ));
end

% Plot first frame of original and decimated signals.
% Output latency is 2 samples.
gainCIC = ...
    (hcicdec.DecimationFactor*hcicdec.DifferentialDelay)^hcicdec.NumSec;
stem(n(1:56)/Fs, double(x(4:59))); hold on;
stem(n(1:14)/(Fs/hcicdec.DecimationFactor),double(y(1,3:end))/gainCIC);
xlabel('Time (sec)');ylabel('Signal Amplitude');
legend('Original signal', 'Decimated signal', 'location', 'north');
hold off;
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the CIC Decimation block reference page. The object properties correspond to the block properties, except:

- The **Rate options** block parameter is not supported by the dsp.CICDecimator object.

## See Also

dsp.CICInterpolator | dsp.FIRDecimator

## **dsp.CICDecimator.clone**

---

**Purpose** Create CIC Decimator object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a `CICDecimator System` object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with un-initialized states.

**Purpose** Frequency response

**Syntax**

```
[h,w] = freqz(H)
[h,w] = freqz(H,n)
[h,w] = freqz(H,Name,Value)
freqz(H)
```

**Description** `[h,w] = freqz(H)` returns the complex, 8192–element frequency response vector `h`, and the corresponding frequencies `w` in radians/sample.

`[h,w] = freqz(H,n)` returns the complex, `n`-element frequency response vector `h`, and the corresponding frequencies `w` in radians/sample, using `n` samples.

`[h,w] = freqz(H,Name,Value)` returns the frequency response and the corresponding frequencies, with additional options specified by one or more `Name, Value` pair arguments.

`freqz(H)` uses FVTool to plot the magnitude and unwrapped phase of the frequency response of the filter System object `H`.

# **dsp.CICDecimator.fvtool**

---

**Purpose** Open filter visualization tool

**Syntax** `fvtool(H)`  
`fvtool(H, 'Arithmetic', ARITH, ...)`

**Description** `fvtool(H)` performs an analysis and computes the magnitude response of the filter System object H.

`fvtool(H, 'Arithmetic', ARITH, ...)` analyzes the filter System object H, based on the arithmetic specified in the ARITH input. ARITH can be set to one of 'double', 'single', or 'fixed'. The analysis tool assumes a double precision filter when the arithmetic input is not specified and the filter System object is in an unlocked state. The 'Arithmetic' input is only relevant for the analysis of filter System objects.

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.CICDecimator.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**      `N = getNumOutputs(H)` returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Impulse response

**Syntax**  
`[h,t] = impz(H)`  
`[h,t] = impz(H,Name,Value)`  
`impz(H)`

**Description** `[h,t] = impz(H)` returns the impulse response `h`, and the corresponding time points `t` at which the impulse response of `H` is computed.

`[h,t] = impz(H,Name,Value)` returns the impulse response `h`, and the corresponding time points `t`, with additional options specified by one or more `Name, Value` pair arguments.

`impz(H)` uses `FVTool` to plot the impulse response of the filter System object `H`.

---

**Note** You can use `impz` for both real and complex filters. When you omit the output arguments, `impz` plots only the real part of the impulse response.

---

# **dsp.CICDecimator.isLocked**

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the CICDecimator System object H.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Unwrapped phase response

**Syntax**

```
[phi,w] = phasez(H)  
[phi,w] = phasez(H,n)  
[phi,w] = phasez(H,Name,Value)  
phasez(H)
```

**Description**

`[phi,w] = phasez(H)` returns the 8192–element phase response vector `phi`, and the corresponding frequencies `w` in radians/sample.

`[phi,w] = phasez(H,n)` returns the `n`-element phase response vector `phi`, and the corresponding frequencies `w` in radians/sample, using `n` samples.

`[phi,w] = phasez(H,Name,Value)` returns the phase response and the corresponding frequencies, with additional options specified by one or more `Name, Value` pair arguments.

`phasez(H)` uses FVTool to plot the phase response of the filter System object `H`.

# dsp.CICDecimator.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Reset filter states of CIC decimator object

**Syntax** reset(H)

**Description** reset(H) resets the filter states of the CICDecimator System object H to zero.

# dsp.CICDecimator.step

---

**Purpose** Decimate input using Cascaded Integrator-Comb filter

**Syntax**  $Y = \text{step}(H, X)$

**Description**  $Y = \text{step}(H, X)$  decimates the fixed-point input  $X$  to produce a fixed-point output  $Y$  using the `CICDecimator System` object  $H$ .

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

## Purpose

Interpolate signal using Cascaded Integrator-Comb filter

## Description

The `CICInterpolator` object interpolates inputs using a Cascaded Integrator-Comb (CIC) filter. Inputs and outputs to the object have signed fixed-point data types. You must have a Fixed-Point Toolbox license to use the `CICInterpolator` System object.

To interpolate inputs using a CIC filter:

- 1 Define and set up your System object. See “Construction” on page 5-229.
- 2 Call `step` to interpolate the input according to the properties of `dsp.CICInterpolator`. The behavior of `step` is specific to each object in the toolbox.

## Construction

`H = dsp.CICInterpolator` returns a System object, `H`, that you can use to interpolate the input with a cascaded integrator-comb (CIC) interpolation filter.

`H = dsp.CICInterpolator('PropertyName',PropertyValue,...)` returns a CIC interpolation object, `H`, with each specified property set to the value you specify.

`H = dsp.CICInterpolator(R,M,N,'PropertyName',PropertyValue,...)` returns a `CICInterpolator` object, `H`, with the `InterpolationFactor` property set to `R`, the `DifferentialDelay` property set to `M`, the `NumSections` property set to `N`, and other specified properties set to the values you specify.

## Properties

### InterpolationFactor

Interpolation factor of filter

Specify a positive integer amount by which the object interpolates the input signal. The default is 2.

### DifferentialDelay

# dsp.CICInterpolator

---

Differential delay of filter comb sections

Specify a positive integer delay value for the object to use in each comb section of the filter. The default is 1.

## **NumSections**

Number of integrator and comb sections

Specify the number of integrator and comb sections in the CIC filter as a positive integer value. The default is 2.

## **FixedPointDataType**

Fixed-point property setting

Specify the fixed-point data type as one of | Full precision | Minimum section word lengths | Specify word lengths | Specify word and fraction lengths |. The default is Full precision. When you set this property to:

- **Full precision** – the CICInterpolator object automatically determines the word and fraction lengths of the filter sections and output.
- **Minimum section word length** – the object automatically determines the word and fraction lengths of the filter sections and the fraction length of the output. You must specify the OutputWordLength.
- **Specify word lengths** – the object automatically determines the fraction lengths of the filter sections and the output. You must specify values for the OutputWordLength and the SectionWordLengths properties.
- **Specify word and fraction lengths** – the object does not automatically determine word and fraction lengths for the filter sections or the output. You must specify them using the OutputFractionLength, OutputWordLength, SectionFractionLengths, and SectionWordLengths properties.

## **SectionWordLengths**

Word length of each filter section

Specify the fixed-point word length for each section of the CIC filter as a scalar or a vector of length  $2 \times \text{NumSections}$ . This property applies only when you set the `FixedPointDataType` property to `Specify word lengths` or `Specify word and fraction lengths`. The default is [16 16 16 16].

## **SectionFractionLengths**

Fraction length of each filter section

Specify the fixed-point fraction length for each section of the CIC filter as a scalar or a vector of length  $2 \times \text{NumSections}$ . This property applies only when you set the `FixedPointDataType` property to `Specify word and fraction lengths`. The default is 0.

## **OutputWordLength**

Word length of filter output

Specify the fixed-point word length for the filter output. This property applies only when you set the `FixedPointDataType` property to `Minimum section word lengths`, `Specify word lengths`, or `Specify word and fraction lengths`. The default is 32.

## **OutputFractionLength**

Fraction length of filter output

Specify the fixed-point fraction length for the output of the CIC filter. This property applies only when you set the `FixedPointDataType` property to `Specify word and fraction lengths`. The default is 0.

# dsp.CICInterpolator

---

## Methods

clone	Create CIC Interpolator object with same property values
freqz	Frequency response
fvtool	Open filter visualization tool
getNumInputs	Number of expected inputs to step method
getNumOutputs	Number of outputs of step method
impz	Impulse response
isLocked	Locked status for input attributes and nontunable properties
phasez	Unwrapped phase response
release	Allow property value and input characteristics changes
reset	Reset internal states of CIC Interpolator object
step	Interpolate signal using Cascaded Integrator-Comb filter

More “Analysis Methods for Filter System Objects” on page 4-2.

## Examples

Interpolate signal by a factor of 2 (upsample the signal from 22.05 kHz to 44.1 kHz):

```
hcicint = dsp.CICInterpolator(2);  
% default NumSections = 2, DifferentialDelay = 1  
  
% Create fixed-point sinusoidal input signal  
Fs = 22.05e3; % Original sampling frequency  
n = (0:511)'; % 512 samples, 0.0113 sec signal  
x = fi(sin(2*pi*1e3/Fs*n),true,16,15);
```

```
% Create SignalSource System object
hsr = dsp.SignalSource(x, 32);

% Interpolate output with 64 samples per frame
y = zeros(16,64);
for ii=1:16
    y(ii,:) = step(hcicint,step( hsr ));
end

% Plot first frame of original and interpolated signals.
% Output latency is 2 samples.
gainCIC = ...
    (hcicint.InterpolationFactor*hcicint.DifferentialDelay)...
    ^hcicint.NumSections/hcicint.InterpolationFactor;
stem(n(1:31)/Fs, double(x(1:31)), 'r', 'filled'); hold on;
stem(n(1:61)/(Fs*hcicint.InterpolationFactor), ...
    double(y(1,4:end))/gainCIC, 'b');
xlabel('Time (sec)');ylabel('Signal Amplitude');
legend('Original signal', 'Interpolated signal',...
    'location', 'north');
hold off;
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the CIC Interpolation block reference page. The object properties correspond to the block properties, except:

- The **Framing** block parameter is not supported by the dsp.CICInterpolator object. The object always maintains the input frame rate.
- The **Rate options** block parameter is not supported by the dsp.CICInterpolator object.
- The **Input processing** block parameter is not supported by the dsp.CICInterpolator object.

# **dsp.CICInterpolator**

---

- The object does not have a property that allows you to specify the source of the coefficients. The object cannot import coefficients from an `mfilt` object.

## **See Also**

`dsp.CICDecimator` | `dsp.FIRInterpolator`

**Purpose**

Create CIC Interpolator object with same property values

**Syntax**

`C = clone(H)`

**Description**

`C = clone(H)` creates a `CICInterpolator System` object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with un-initialized states.

# dsp.CICInterpolator.freqz

---

**Purpose** Frequency response

**Syntax** `[h,w] = freqz(H)`  
`[h,w] = freqz(H,n)`  
`[h,w] = freqz(H,Name,Value)`  
`freqz(H)`

**Description** `[h,w] = freqz(H)` returns the complex, 8192–element frequency response vector `h`, and the corresponding frequencies `w` in radians/sample.

`[h,w] = freqz(H,n)` returns the complex, `n`-element frequency response vector `h`, and the corresponding frequencies `w` in radians/sample, using `n` samples.

`[h,w] = freqz(H,Name,Value)` returns the frequency response and the corresponding frequencies, with additional options specified by one or more `Name, Value` pair arguments.

`freqz(H)` uses FVTool to plot the magnitude and unwrapped phase of the frequency response of the filter System object `H`.

**Purpose** Open filter visualization tool

**Syntax** fvtool(H)  
fvtool(H, 'Arithmetic', ARITH, ...)

**Description** fvtool(H) performs an analysis and computes the magnitude response of the filter System object H.

fvtool(H, 'Arithmetic', ARITH, ...) analyzes the filter System object H, based on the arithmetic specified in the ARITH input. ARITH can be set to one of 'double', 'single', or 'fixed'. The analysis tool assumes a double precision filter when the arithmetic input is not specified and the filter System object is in an unlocked state. The 'Arithmetic' input is only relevant for the analysis of filter System objects.

# dsp.CICInterpolator.getNumInputs

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose**

Number of outputs of step method

**Syntax**

`N = getNumOutputs(H)`

**Description**

`N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# dsp.CICInterpolator.impz

---

**Purpose** Impulse response

**Syntax** `[h,t] = impz(H)`  
`[h,t] = impz(H,Name,Value)`  
`impz(H)`

**Description** `[h,t] = impz(H)` returns the impulse response `h`, and the corresponding time points `t` at which the impulse response of `H` is computed.

`[h,t] = impz(H,Name,Value)` returns the impulse response `h`, and the corresponding time points `t`, with additional options specified by one or more `Name, Value` pair arguments.

`impz(H)` uses `FVTool` to plot the impulse response of the filter System object `H`.

---

**Note** You can use `impz` for both real and complex filters. When you omit the output arguments, `impz` plots only the real part of the impulse response.

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `CICInterpolator` System object `H`.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.CICInterpolator.phasez

---

**Purpose** Unwrapped phase response

**Syntax**  
`[phi,w] = phasez(H)`  
`[phi,w] = phasez(H,n)`  
`[phi,w] = phasez(H,Name,Value)`  
`phasez(H)`

**Description** `[phi,w] = phasez(H)` returns the 8192–element phase response vector `phi`, and the corresponding frequencies `w` in radians/sample.

`[phi,w] = phasez(H,n)` returns the `n`-element phase response vector `phi`, and the corresponding frequencies `w` in radians/sample, using `n` samples.

`[phi,w] = phasez(H,Name,Value)` returns the phase response and the corresponding frequencies, with additional options specified by one or more `Name, Value` pair arguments.

`phasez(H)` uses FVTool to plot the phase response of the filter System object `H`.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

## **dsp.CICInterpolator.reset**

---

**Purpose**            Reset internal states of CIC Interpolator object

**Syntax**            reset(H)

**Description**        reset(H) resets the internal states of the CICInterpolator System object H to zero.

**Purpose** Interpolate signal using Cascaded Integrator-Comb filter

**Syntax**  $Y = \text{step}(H,X)$

**Description**  $Y = \text{step}(H,X)$  interpolates the fixed-point input  $X$  to produce a fixed-point output  $Y$  using the `CICInterpolator` System object  $H$ .

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.Convolver

---

**Purpose** Convolution of two inputs

**Description** The `Convolver` computes the convolution of two inputs.

To compute the convolution of two inputs:

- 1 Define and set up your convolver. See “Construction” on page 5-246.
- 2 Call `step` to compute the convolution according to the properties of `dsp.Convolver`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.Convolver` returns a convolver object, `H`, that convolves two inputs. For N-D arrays, the convolver computes the convolution column-wise. For arrays, the inputs must have an equal number of columns. If one input is a vector and the other is an N-D array, the convolver computes the convolution of the vector with each column of the N-D array. Convolver inputs of length  $N$  and  $M$  results in a sequence of length  $N+M-1$ . Convolver matrices of size  $M$ -by- $N$  and  $P$ -by- $N$  results in a matrix of size  $(M+P-1)$ -by- $N$ .

`H = dsp.Convolver('PropertyName',PropertyValue, ...)` returns a convolver object, `H`, with each property set to the specified value.

## Properties

### Method

Domain for computing convolutions

Specify the domain in which the convolver performs the convolutions as `Time Domain`, `Frequency Domain`, or `Fastest`. Computing convolutions in the time domain minimizes memory use. Computing convolutions in the frequency domain may require fewer computations depending on the input length. If the value of this property is `Fastest`, the object computes convolutions in the domain which minimizes the number of computations. The default is `Time Domain`.

## Fixed-Point Properties

### FullPrecisionOverride

Full precision override for fixed-point arithmetic

Specify whether to use full precision rules. If you set `FullPrecisionOverride` to `true`, which is the default, the object computes all internal arithmetic and output data types using full precision rules. These rules provide the most accurate fixed-point numerics. It also turns off the display of other fixed-point properties because they do not apply individually. These rules guarantee that no quantization occurs within the object. Bits are added, as needed, to ensure that no roundoff or overflow occurs. If you set `FullPrecisionOverride` to `false`, fixed-point data types are controlled through individual fixed-point property settings. For more information, see “Full Precision for Fixed-Point System Objects”.

### RoundingMethod

Rounding method for fixed-point operations

Specify the rounding method as `Ceiling`, `Convergent`, `Floor`, `Nearest`, `Round`, `Simplest`, or `Zero`. The default is `Floor`. This property applies only if the object is not in full precision mode.

### OverflowAction

Overflow action for fixed-point operations

Specify the overflow action as `Wrap` or `Saturate`. The default is `Wrap`. This property applies only if the object is not in full precision mode.

### ProductDataType

Product word and fraction lengths

Specify the product fixed-point data type as `Full precision`, `Same as first input`, or `Custom`. The default is `Full precision`.

### CustomProductDataType

Product word and fraction lengths

Specify the product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when the `ProductDataType` property is `Custom`. The default is `numericType([],32,30)`.

## **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point data type as `Full precision`, `Same as product`, `Same as first input`, or `Custom`. The default is `Full precision`.

## **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when the `AccumulatorDataType` property is `Custom`. The default is `numericType([],32,30)`.

## **OutputDataType**

Output word and fraction lengths

Specify the output fixed-point data type as `Same as accumulator`, `Same as product`, `Same as first input`, or `Custom`. The default is `Same as accumulator`.

## **CustomOutputDataType**

Output word and fraction lengths

Specify the output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when the `OutputDataType` property is `Custom`. The default is `numericType([],16,15)`.

## Methods

<code>clone</code>	Create convolver object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>step</code>	Convolution of inputs

## Examples

Convolution of two rectangular sequences:

```
hconv = dsp.Convolver;  
x = ones(10,1);  
y = step(hconv, x, x);  
% Result is a triangular sequence  
plot(y);
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Convolution block reference page. The object properties correspond to the block parameters.

## See Also

`dsp.Autocorrelator` | `dsp.Crosscorrelator`

## **dsp.Convolver.clone**

---

**Purpose** Create convolver object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a convolver object, `C`, with the same property values as `H`. The clone method creates a new unlocked object.

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.Convolver.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the convolver object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.Convolver.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Convolution of inputs

**Syntax**  $Y = \text{step}(H,A,B)$

**Description**  $Y = \text{step}(H,A,B)$  convolves the inputs A and B.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.Counter

---

**Purpose** Count up or down through specified range of numbers

**Description** The Counter object counts up or down through a specified range of numbers.

To count up or down through a specified range of numbers:

- 1 Define and set up your counter. See “Construction” on page 5-256.
- 2 Call `step` to count up or down according to the properties of `dsp.Counter`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.Counter` returns a counter System object, `H`, that counts up when the input is nonzero.

`H = dsp.Counter('PropertyName',PropertyValue,...)` returns a counter System object, `H`, with each specified property set to the specified value.

## Properties

### Direction

Count up or down

Specify the counter direction as `Up` or `Down`. The default is `Up`. This property is tunable.

### CountEventInputPort

Add input to specify a count event

Set this property to `true` to enable a count event input for the internal counter. The internal counter increments or decrements whenever the count event input satisfies the condition you specify in the `CountEventCondition` property. When you set this property to `false`, the internal counter is free running, that is, the counter increments or decrements on every call to the `step` method. The default is `true`.

### CountEventCondition

Condition that increments, decrements, or resets internal counter

Specify the event at the count event input that increments or decrements the counter as `Rising edge`, `Falling edge`, `Either edge` or `Non-zero`.

If you set the `ResetInputPort` and `CountEventInputPort` properties to `true`, the counter is reset when the event you specify for the `CountEventCondition` occurs. This property applies only when you set the `CountEventInputPort` property to `true`.

### **CounterSizeSource**

Source of counter size data type

Specify the source of the counter size data type as `Property` or `Input port`. The default is `Property`.

### **CounterSize**

Range of integer values to count through

Specify the range of integer values to count through before recycling to zero as `8 bits`, `16 bits`, `32 bits` or `Maximum`. The default is `Maximum`.

### **MaximumCount**

Counter's maximum value

Specify the counter's maximum value as a numeric scalar value. This property applies only when you set the `CounterSizeSource` property to `Property` and the `CounterSize` property to `Maximum`. The default is `255`. This property is tunable.

### **InitialCount**

Counter initial value

Specify the initial value for the counter. The default is `0`. This property is tunable.

### **CountOutputPort**

Output count

Set this property to `true` to enable output of the internal count. The default is `true`. You cannot set both `CountOutputPort` and `HitOutputPort` to `false` at the same time.

## **HitOutputPort**

Output hit events

Set this property to `true` to enable output of the hit events. You cannot set both `CountOutputPort` and `HitOutputPort` to `false` at the same time. The default is `true`.

## **HitValues**

Values whose occurrence in count produce a true hit output

Specify an integer scalar or a vector of integers, whose occurrences in the count you want flagged as a hit. This property applies only when you set the `HitOutputPort` property to `true`.

## **ResetInputPort**

Add input to enable internal counter reset

When you set this property to `true`, specify a reset input to the `step` method. When the reset input receives the event you specify for the `CountEventCondition` property, the counter resets. If you set the `CountEventInputPort` property to `false`, the counter resets whenever the reset input is not zero.

## **SamplesPerFrame**

Number of samples in each output frame

Specify the number of samples in each output frame. This property applies only when you set the `CountEventInputPort` property to `false`, indicating a free-running counter. The default is 1.

## **CountOutputDataType**

Data type of count output

Specify the data type of the count output, CNT, as `double`, `single`, `int8`, `uint8`, `int16`, `uint16`, `int32` or `uint32`. This property applies when you set the `CountOutputPort` property to `true`. The default is `double`.

## Methods

<code>clone</code>	Create counter object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>reset</code>	Reset internal states of Counter object
<code>step</code>	Increment or decrement the internal counter

## Examples

Use Counter System object for counting from 0 to 5:

```
hcounter = dsp.Counter('MaximumCount', 5, ...  
'CountOutputPort', true, ...  
'HitOutputPort', false, ...  
'ResetInputPort', false);  
sgnl = [0 1 0 1 0 1 0 1 0 1 0 1];  
for ii = 1:length(sgnl)  
    %count at every rising edge of the input signal.  
    cnt(ii) = step(hcounter, sgnl(ii));  
end  
cnt
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Counter block reference page. The object properties correspond to the block parameters.

- The `CountEventCondition` object property does not have a free-running option. Set the `CountEventInputPort` property to `false` to obtain the free-running option.
- The `CounterSizeSource` and `CounterSize` object properties correspond to the **Counter size** block parameter.
- The `CountOutputPort` and `HitOutputPort` correspond to the **Output** block parameter.
- There is no object property that corresponds to the **Hit data type** block parameter. The output type is logical in MATLAB. (This logical is different from the popup logical in the block. For the object, logical corresponds to Boolean in the block.)

**Purpose** Create counter object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a `Counter` object `C`, with the same property values as `H`. The clone method creates a new unlocked object with uninitialized states.

# **dsp.Counter.getNumInputs**

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**      `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose**

Number of outputs of step method

**Syntax**

`N = getNumOutputs(H)`

**Description**

`N = getNumOutputs(H)` returns the number of outputs, `N`, from the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# **dsp.Counter.isLocked**

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the Counter System object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

## **dsp.Counter.reset**

---

<b>Purpose</b>	Reset internal states of Counter object
<b>Syntax</b>	<code>reset(H)</code>
<b>Description</b>	<code>reset(H)</code> resets the internal states of the counter object H to their initial values.

**Purpose** Increment or decrement the internal counter

**Syntax**

```
[CNT,HIT] = step(H,EVENT,RESET)
CNT = step(H,EVENT,RESET)
HIT = step(H,EVENT,RESET)
[...] = step(H)
[...] = step(H,EVENT)
```

**Description** [CNT,HIT] = step(H,EVENT,RESET) increments, decrements, or resets the internal counter as specified by the values of the EVENT and RESET inputs. The output argument CNT denotes the present value of the counter. A trigger event at the EVENT input causes the counter to increment or decrement. A trigger event at the RESET input resets the counter to its initial state.

CNT = step(H,EVENT,RESET) returns the current value of the count when you set the CountOutputPort property to true, and the HitOutputPort property to false.

HIT = step(H,EVENT,RESET) returns a Boolean value indicating whether the count has reached any of the values specified by the HitValues property. This condition applies when you set the HitOutputPort property to true and the CountOutputPort property to false.

[...] = step(H) increments or decrements the free-running internal counter when you set the CountEventInputPort property to false and the ResetInputPort property to false.

[...] = step(H,EVENT) increments or decrements the internal counter when the EVENT input matches the event you specify for the CountEventCondition property and you set the ResetInputPort property to false.

## **dsp.Counter.step**

---

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

## Purpose

Cross-correlation of two inputs

## Description

The `Crosscorrelator` returns the cross-correlation sequence for two discrete-time deterministic inputs. This object can also return the cross-correlation sequence estimate for two discrete-time, jointly wide-sense stationary (WSS), random processes.

To obtain the cross-correlation for two discrete-time deterministic inputs:

- 1 Define and set up your cross-correlator. See “Construction” on page 5-269.
- 2 Call `step` to compute the cross-correlation according to the properties of `dsp.Crosscorrelator`. The behavior of `step` is specific to each object in the toolbox.

## Construction

`H = dsp.Crosscorrelator` returns a cross-correlator object, `H`, that computes the cross-correlation of two inputs. For N-D arrays, the cross-correlator computes the correlation column-wise. The inputs must have an equal number of columns. If one input is a vector and the other is an N-D array, the cross-correlator computes the cross-correlation of the vector with each column of the N-D array. Cross correlating inputs of length  $N$  and  $M$  results in a cross-correlation sequence of length  $N+M-1$ . Cross correlating matrices of size  $M$ -by- $N$  and  $P$ -by- $N$  results in a matrix of cross-correlation sequences of size  $M+P-1$ -by- $N$ .

`H = dsp.Crosscorrelator('PropertyName',PropertyValue, ...)` returns a cross-correlator, `H`, with each property set to the specified value.

## Properties

### Method

Domain for computing correlations

Specify the domain for computing correlation as `Time Domain`, `Frequency Domain`, or `Fastest`. Computing correlations in the time domain minimizes memory use. Computing correlations

in the frequency domain may require fewer computations than computing in the time domain depending on the input length. If the value of this property is `Fastest`, the cross-correlator operates in the domain which minimizes the number of computations. The default is `Time Domain`.

## **Fixed-Point Properties**

### **FullPrecisionOverride**

Full precision override for fixed-point arithmetic

Specify whether to use full precision rules. If you set `FullPrecisionOverride` to `true`, which is the default, the object computes all internal arithmetic and output data types using full precision rules. These rules provide the most accurate fixed-point numerics. It also turns off the display of other fixed-point properties because they do not apply individually. These rules guarantee that no quantization occurs within the object. Bits are added, as needed, to ensure that no roundoff or overflow occurs. If you set `FullPrecisionOverride` to `false`, fixed-point data types are controlled through individual fixed-point property settings. For more information, see “Full Precision for Fixed-Point System Objects”.

### **RoundingMethod**

Rounding method for fixed-point operations

Specify the rounding method as one of `Ceiling`, `Convergent`, `Floor`, `Nearest`, `Round`, `Simplest`, or `Zero`. The default is `Floor`. This property applies only if the object is not in full precision mode.

### **OverflowAction**

Overflow action for fixed-point operations

Specify the overflow action as one of `Wrap` or `Saturate`. The default is `Wrap`. This property applies only if the object is not in full precision mode.

## **ProductDataType**

Product word and fraction lengths

Specify the product fixed-point data type as one of Full Precision, Same as first input, or Custom. The default is Full Precision.

## **CustomProductDataType**

Product word and fraction lengths

Specify the product fixed-point type as a scaled numeric type object with a Signedness of Auto. This property applies only when the ProductDataType property is Custom. The default is numeric type([],32,30).

## **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point data type as Full Precision, Same as product, Same as first input, or Custom. The default is Full Precision.

## **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled numeric type object with a Signedness of Auto. This property applies only when the AccumulatorDataType property is Custom. The default is numeric type([],32,30).

## **OutputDataType**

Output word and fraction lengths

Specify the output fixed-point data type as one of Same as accumulator, Same as product, Same as first input, or Custom. The default is Same as accumulator.

## **CustomOutputDataType**

Output word and fraction lengths

# dsp.Crosscorrelator

---

Specify the output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when the `OutputDataType` property is `Custom`. The default is `numericType([], 16, 15)`.

## Methods

<code>clone</code>	Create cross-correlator object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>step</code>	Cross-correlation sequence

## Definitions

The cross-correlation of two length  $N$  deterministic inputs, or realizations of jointly WSS random processes,  $x$  and  $y$ , is:

$$r_{xy}(h) = \begin{cases} \sum_{n=0}^{N-h-1} x(n+h)y^*(n) & 0 \leq h \leq N-1 \\ r_{yx}^*(h) & -(N-1) \leq h \leq 0 \end{cases}$$

where  $h$  is the lag and  $*$  denotes the complex conjugate. If the inputs are realizations of jointly WSS stationary random processes,  $r_{xy}(h)$  is an unnormalized estimate of the theoretical cross-correlation:

$$\rho_{xy}(h) = E\{x(n+h)y^*(n)\}$$

where  $E\{\}$  is the expectation operator.

## Examples

Compute correlation between two signals:


```
hcorr = dsp.Crosscorrelator;
t=[0:0.001:1];
x1=sin(2*pi*2*t)+0.05*sin(2*pi*50*t);
x2=sin(2*pi*2*t);
y=step(hcorr,x1,x2); %computes cross-correlation of x1 and x2
figure,plot(t,x1,'b',t, x2, 'g');
legend('Input signal 1',' Input signal 2')
figure, plot(y); title('Correlated output')
```

---

Use cross-correlation to detect delay in jointly stationary white Gaussian noise inputs:

```
S = rng('default');
% white Gaussian noise input
x = randn(100,1);
% Create copy delayed by 10 samples
% x1[n]=x[n-10]
Hdelay = dsp.Delay(10);
x1= step(Hdelay,x);
Hxcorr = dsp.Crosscorrelator;
y = step(Hxcorr,x1,x);
lags = 0:99; %Positive lags
stem(lags,y(100:end),'markerfacecolor',[0 0 1]);
axis([0 99 -125 125]);
xlabel('Lags');
title('Cross-Correlation of Input Noise and Delayed Version');
```

# dsp.Crosscorrelator



The theoretical cross-correlation sequence is identically zero except at lag 10. Note this is not true in the sample cross-correlation sequence, but the estimate demonstrates a peak at the correct lag.

## Algorithms

This object implements the algorithm, inputs, and outputs described on the [Correlation block reference page](#). The object properties correspond to the block parameters.

## See Also

[dsp.Autocorrelator](#) | [dsp.Convolver](#)

# **dsp.Crosscorrelator.clone**

---

**Purpose** Create cross-correlator object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a cross-correlator object, `C`, with the same property values as `H`. The clone method creates a new unlocked object.

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.Crosscorrelator.getNumOutputs**

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the cross-correlator.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.Crosscorrelator.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Cross-correlation sequence

**Syntax**  $Y = \text{step}(H,A,B)$

**Description**  $Y = \text{step}(H,A,B)$  computes the cross-correlation of A and B and returns the result in Y.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.CumulativeProduct

---

## Purpose

Cumulative product of channel, column, or row elements

## Description

The `CumulativeProduct` object computes the cumulative product of channel, column, or row elements.

To compute the cumulative product of channel, column, or row elements:

- 1 Define and set up your cumulative product object. See “Construction” on page 5-282.
- 2 Call `step` to compute the cumulative product according to the properties of `dsp.CumulativeProduct`. The behavior of `step` is specific to each object in the toolbox.

## Construction

`H = dsp.CumulativeProduct` returns a cumulative product object, `H`, that computes the cumulative product of input matrix or input vector elements along the default `Dimension`.

`H = dsp.CumulativeProduct('PropertyName',PropertyValue,...)` returns a cumulative product object, `H`, with each specified property set to the specified value.

## Properties

### Dimension

Computation dimension for cumulative product

Specify the computation dimension as one of `| Channels (running product) | Rows | Columns |`. The default is `Channels (running product)`.

### ResetInputPort

Enable resetting cumulative product via input port

Set this property to `true` to enable resetting the cumulative product. When you set this property to `true`, specify a reset signal to the `step` method to reset the cumulative product. You can access this property when the `Dimension` property is set to `Channels (running product)`. The default is `false`.

## **ResetCondition**

Reset condition for cumulative product

Specify the event on the reset input port that causes resetting the cumulative product to one of | Rising edge | Falling edge | Either edge | Non-zero |. This property applies when you set the ResetInputPort property to true and the Dimension property to Channels (running product). The default is Rising edge.

## **FrameBasedProcessing**

Enable frame-based processing

Set this property to true to enable frame-based processing. Set this property to false to enable sample-based processing. You can access this property when the Dimension property is set to Channels (running product). The default is false.

## **Fixed-Point Properties**

### **RoundingMethod**

Rounding method for fixed-point operations

Specify the rounding method as one of | Ceiling | Convergent | Floor | Nearest, | Round | Simplest | Zero |. The default is Floor.

### **OverflowAction**

Overflow action for fixed-point operations

Specify the overflow action as one of | Wrap | Saturate |. The default is Wrap.

### **IntermediateProductDataType**

Intermediate product word and fraction lengths

Specify the intermediate product fixed-point data type as one of | Same as input | Custom |. The default is Same as input.

### **CustomIntermediateProductDataType**

# dsp.CumulativeProduct

---

Intermediate product word and fraction lengths

Specify the intermediate product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `IntermediateProductDataType` property to `Custom`. The default is `numericType([], 16, 15)`.

## **ProductDataType**

Product output word and fraction lengths

Specify the product output fixed-point data type as one of `| Same as input | Custom |`. The default is `Same as input`.

## **CustomProductDataType**

Custom product output word and fraction lengths

Specify the product output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `ProductDataType` property to `Custom`. The default is `numericType([], 32, 30)`.

## **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point data type as one of `| Same as product output | Same as input | Custom |`. The default is `Same as input`.

## **CustomAccumulatorDataType**

Custom accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `AccumulatorDataType` property to `Custom`. The default is `numericType([], 32, 30)`.

## **OutputDataType**

Output word and fraction lengths

Specify the output fixed-point data type as one of | Same as product output | Same as input | Custom |. The default is Same as input.

## CustomOutputDataType

Custom output word and fraction lengths

Specify the output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `OutputDataType` property to `Custom`. The default is `numericType([], 16, 15)`.

## Methods

<code>clone</code>	Create cumulative product object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>reset</code>	Reset running cumulative product
<code>step</code>	Cumulative product of input along specified dimension for input

## Examples

Compute the cumulative product of a matrix:

```
hcprod = dsp.CumulativeProduct;  
x = magic(2);  
y = step(hcprod,x);  
y = step(hcprod,x)
```

# dsp.CumulativeProduct

---

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Cumulative Product block reference page. The object properties correspond to the block parameters, except:

The **Reset port** block parameter corresponds to both the `ResetCondition` and `ResetInputPort` object properties.

Both this object and its corresponding block let you specify whether to process inputs as individual samples or as frames of data. The object uses the `FrameBasedProcessing` property. The block uses the **Input processing** parameter. See “Set the `FrameBasedProcessing` Property of a System object” for more information.

## See Also

`dsp.CumulativeSum`

**Purpose** Create cumulative product object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a `CumulativeProduct System` object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with uninitialized states.

# **dsp.CumulativeProduct.getNumInputs**

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.CumulativeProduct.getNumOutputs

---

**Purpose**

Number of outputs of step method

**Syntax**

`N = getNumOutputs(H)`

**Description**

`N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# dsp.CumulativeProduct.isLocked

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `CumulativeProduct` object `H`.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

## **dsp.CumulativeProduct.reset**

---

**Purpose**            Reset running cumulative product

**Syntax**            `reset(H)`

**Description**       `reset(H)` resets the running cumulative product for object H to zero.

**Purpose** Cumulative product of input along specified dimension for input

**Syntax**  
 $Y = \text{step}(H, X)$   
 $Y = \text{step}(H, X, R)$

**Description**  $Y = \text{step}(H, X)$  computes the cumulative product along the specified dimension for the input  $X$ .  
 $Y = \text{step}(H, X, R)$  resets the cumulative product object's state based on the `ResetCondition` property value and the value of the reset signal,  $R$  when the `ResetInputPort` property is true.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.CumulativeSum

---

## Purpose

Cumulative sum of channel, column, or row elements

## Description

The `CumulativeSum` object computes the cumulative sum of channel, column, or row elements.

To compute the cumulative sum of channel, column, or row elements:

- 1 Define and set up your cumulative sum object. See “Construction” on page 5-294.
- 2 Call `step` to compute the cumulative sum according to the properties of `dsp.CumulativeSum`. The behavior of `step` is specific to each object in the toolbox.

## Construction

`H = dsp.CumulativeSum` returns a cumulative sum System object, `H`, which computes the running cumulative sum for each channel in the input.

`H = dsp.CumulativeSum('PropertyName',PropertyValue,...)` returns a cumulative sum object, `H`, with each specified property set to the specified value.

## Properties

### Dimension

Computation dimension for cumulative sum

Specify the computation dimension as one of `| Channels (running sum) | Rows | Columns |`. The default is `Channels (running sum)`.

### ResetInputPort

Enable resetting cumulative sum via input port.

Set this property to `true` to enable resetting the cumulative sum. When you set this property to `true`, you also specify a reset input to the `step` method to reset the cumulative sum. The default is `false`.

### ResetCondition

Reset condition for cumulative sum

Specify the event on the reset input port that resets the cumulative sum as one of | Rising edge | Falling edge | Either edge | Non-zero |. This property applies when you set the ResetInputPort property to true. The default is Rising edge.

## **FrameBasedProcessing**

Enable frame-based processing

Set this property to true to enable frame-based processing. Set this property to false to enable sample-based processing. You can access this property when the Dimension property is Channels (running sum). The default is false.

## **Fixed-Point Properties**

### **RoundingMethod**

Rounding method for fixed-point operations

Specify the rounding method as one of | Ceiling | Convergent | Floor, Nearest, Round, Simplest | Zero |. The default is Floor.

### **OverflowAction**

Overflow action for fixed-point operations

Specify the overflow action as one of | Wrap | Saturate |. The default is Wrap.

### **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point data type as one of | Same as input | Custom |. The default is Same as input.

### **CustomAccumulatorDataType**

Custom accumulator word and fraction lengths

# dsp.CumulativeSum

---

Specify the accumulator fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `AccumulatorDataType` property to `Custom`. The default is `numericType([], 32, 30)`.

## **OutputDataType**

Output word and fraction lengths

Specify the output fixed-point data type as one of one of `| Same as accumulator | Same as input | Custom |`. The default is `Same as accumulator`.

## **CustomOutputDataType**

Custom output word and fraction lengths

Specify the output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `OutputDataType` property to `Custom`. The default is `numericType([], 16, 15)`.

## **Methods**

<code>clone</code>	Create cumulative sum object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>reset</code>	Reset internal states of cumulative sum object to zero
<code>step</code>	Cumulative sum along specified dimension for input

## Examples

Use a cumulative sum object to compute the cumulative sum of a matrix:

```
hcsun = dsp.CumulativeSum;  
x = magic(2);  
y = step(hcsun,x);  
y = step(hcsun,x)
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Cumulative Sum block reference page. The object properties correspond to the block properties, except:

The **Reset port** block parameter corresponds to both the `ResetCondition` and the `ResetInputPort` object properties

Both this object and its corresponding block let you specify whether to process inputs as individual samples or as frames of data. The object uses the `FrameBasedProcessing` property. The block uses the **Input processing** parameter. See “Set the `FrameBasedProcessing` Property of a System object” for more information.

## See Also

`dsp.CumulativeProduct`

## **dsp.CumulativeSum.clone**

---

**Purpose** Create cumulative sum object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a `CumulativeSum` object `C`, with same property values as `H`. The `clone` method creates a new unlocked object with uninitialized states.

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.CumulativeSum.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `CumulativeSum` object `H`.  
The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.CumulativeSum.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose**

Reset internal states of cumulative sum object to zero

**Syntax**

reset(H)

**Description**

reset(H) sets the states for the running cumulative sum object, H, to zero when the Dimension property is set to Channels (running sum).

# dsp.CumulativeSum.step

---

**Purpose** Cumulative sum along specified dimension for input

**Syntax**  
 $Y = \text{step}(H,X)$   
 $Y = \text{step}(H,X,R)$

**Description**  $Y = \text{step}(H,X)$  computes the cumulative sum along the specified dimension for the input  $X$ .  
 $Y = \text{step}(H,X,R)$  resets the System object's state based on the `ResetCondition` property value and the value of the reset signal,  $R$ . You can only reset the state if the `ResetInputPort` property is `true`.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

<b>Purpose</b>	Discrete cosine transform (DCT)
<b>Description</b>	<p>The DCT object computes the discrete cosine transform (DCT) of input.</p> <p>To compute the DCT of input:</p> <ol style="list-style-type: none"><li>1 Define and set up your DCT object. See “Construction” on page 5-305.</li><li>2 Call <code>step</code> to compute the DCT according to the properties of <code>dsp.DCT</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.DCT</code> returns a discrete cosine transform (DCT) object, <code>H</code>, used to compute the DCT of a real or complex input signal.</p> <p><code>H = dsp.DCT('PropertyName',PropertyVaLue, ...)</code> returns a DCT object, <code>H</code>, with each property set to the specified value.</p>
<b>Properties</b>	<p><b>SineComputation</b></p> <p>Method to compute sines and cosines</p> <p>Specify how the DCT object computes the trigonometric values as <code>Trigonometric function</code> or <code>Table lookup</code>. This property must be set to <code>Table lookup</code> for fixed-point inputs. The default is <code>Table lookup</code>.</p> <p><b>Fixed-Point Properties</b></p> <p><b>RoundingMethod</b></p> <p>Rounding method for fixed-point operations</p> <p>Specify the rounding method as one of <code>Ceiling</code>, <code>Convergent</code>, <code>Floor</code>, <code>Nearest</code>, <code>Round</code>, <code>Simplest</code>, or <code>Zero</code>. This property applies when you set the <code>SineComputation</code> property to <code>Table lookup</code>.</p> <p><b>OverflowAction</b></p> <p>Overflow action for fixed-point operations</p>

Specify the overflow action as one of `Wrap` or `Saturate`. This property applies when you set the `SineComputation` property to `Table lookup`.

## **SineTableDataType**

Sine table word-length designation

Specify the sine table fixed-point data type as one of `Same word length as input` or `Custom`. This property applies when you set the `SineComputation` property to `Table lookup`.

## **CustomSineTableDataType**

Sine table word length

Specify the sine table fixed-point type as an unscaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `SineComputation` property to `Table lookup` and the `SineTableDataType` property to `Custom`. The default is `numericType([],16)`.

## **ProductDataType**

Product word and fraction lengths

Specify the product fixed-point data type as one of `Full precision`, `Same as input`, `Custom`. This property applies when you set the `SineComputation` property to `Table lookup`.

## **CustomProductDataType**

Product word and fraction lengths

Specify the product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `SineComputation` property to `Table lookup` and the `ProductDataType` property to `Custom`. The default is `numericType([],32,30)`.

## **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point data type as one of `Full precision`, `Same as input`, `Same as product`, or `Custom`. This property applies when you set the `SineComputation` property to `Table lookup`.

### **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `SineComputation` property to `Table lookup` and the `AccumulatorDataType` property to `Custom`. The default is `numericType([],32,30)`.

### **OutputDataType**

Output word and fraction lengths

Specify the output fixed-point data type as one of `Full precision`, `Same as input`, `Custom`. This property applies when you set the `SineComputation` property to `Table lookup`. The default is `Full precision`.

### **CustomOutputDataType**

Output word and fraction lengths

Specify the output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `SineComputation` property to `Table lookup` and the `OutputDataType` property to `Custom`. The default is `numericType([],16,15)`.

## **Methods**

<code>clone</code>	Create discrete cosine transform object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method

isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
step	Discrete cosine transform (DCT) of input

## Examples

Use DCT to analyze the energy content in a sequence:

```
x = (1:128).' + 50*cos((1:128).'*2*pi/40);
hdct = dsp.DCT;
X = step(hdct, x);
% Set the DCT coefficients which represent less
% than 0.1% of the total energy to 0 and
% reconstruct the sequence using IDCT.
[XX, ind] = sort(abs(X),1,'descend');
ii = 1;
while (norm([XX(1:ii);zeros(128-ii,1)]) <= 0.999*norm(XX))
    ii = ii+1;
end
disp(['Number of DCT coefficients that represent 99.9%',...
    'of the total energy in the sequence: ',num2str(ii)]);
XXt = zeros(128,1);
XXt(ind(1:ii)) = X(ind(1:ii));
hidct = dsp.IDCT;
xt = step(hidct, XXt);
plot(1:128,[x xt]);
legend('Original signal','Reconstructed signal',...
    'location','best');
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the DCT block reference page. The object properties correspond to the block parameters.

## See Also

[dsp.IDCT](#) | [dsp.FFT](#) | [dsp.IFFT](#)

**Purpose** Create discrete cosine transform object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates an instance of the current discrete cosine transform object, `C`, with the same property values as `H`. The clone method creates a new unlocked object.

# dsp.DCT.getNumInputs

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**      `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# dsp.DCT.isLocked

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the DCT object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

# dsp.DCT.step

---

**Purpose** Discrete cosine transform (DCT) of input

**Syntax**  $Y = \text{step}(H,X)$

**Description**  $Y = \text{step}(H,X)$  computes the DCT of the input  $X$ .

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

<b>Purpose</b>	Delay input by specified number of samples or frames
<b>Description</b>	<p>The Delay object delays an input by a specified number of samples or frames.</p> <p>To delay an input by a specified number of samples or frames:</p> <ol style="list-style-type: none"><li>1 Define and set up your delay object. See “Construction” on page 5-315.</li><li>2 Call <code>step</code> to delay the input according to the properties of <code>dsp.Delay</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.Delay</code> returns a delay object, <code>H</code>, to delay the input by one sample.</p> <p><code>H = dsp.Delay('PropertyName', PropertyValue, ...)</code> returns a delay object, <code>H</code>, with each property set to the specified value.</p> <p><code>H = dsp.Delay(LEN, 'PropertyName', PropertyValue, ...)</code> returns a delay object, <code>H</code>, with the <code>Length</code> property set to <code>LEN</code> and other specified properties set to the specified values.</p>
<b>Properties</b>	<p><b>Units</b></p> <p>Delay units as samples or frames</p> <p>Specify the delay units as one of <code>  Samples   Frames  </code>. This property applies when you set the <code>FrameBasedProcessing</code> property to <code>true</code>. The default is <code>Samples</code>.</p> <p><b>Length</b></p> <p>Amount of delay</p> <p>Specify amount of delay to apply to the input signal. You can set this property to a scalar, a vector, or an array containing nonnegative integers depending on the value of the <code>FrameBasedProcessing</code> property.</p>

If the `FrameBasedProcessing` property is `false`, the value can be a scalar by which to delay all input channels equally, or an N-D array of the same dimensions as the input whose values specify the number of sample intervals to delay each channel of the input.

If the `FrameBasedProcessing` property is `true`, the value can be an integer by which to equally delay all channels or a vector whose length equals the number of input columns (channels).

The default is 1.

## **InitialConditionsPerChannel**

Enable different initial conditions per channel

Set this property to `true` to specify different initial conditions per channel. The default value is `false`.

## **InitialConditionsPerSample**

Enable different initial conditions per sample

Set this property to `true` to specify different initial conditions per sample. The default value is `false`.

## **InitialConditions**

Initial output of delay object

Specify the initial output(s) of the delay object. You can set this property to a scalar, vector, matrix, or a cell array depending on the values of the `FrameBasedProcessing`, `InitialConditionsPerChannel`, `InitialConditionsPerSample`, and `Units` properties. The default is 0.

If the `FrameBasedProcessing` property is `false`, and the input is an N-D array, the dimensions of this property value have the following requirements:

- If the `InitialConditionsPerChannel` and `InitialConditionsPerSample` properties are both `false`, the property value must be a scalar. If the `InitialConditionsPerChannel` property is `true` and the

If the `InitialConditionsPerSample` property is `false`, the value must have the same dimensions as the input. If the `InitialConditionsPerChannel` property is `false` and the `InitialConditionsPerSample` property is `true`, the value must be a vector of length equal to the `Length` property value.

- If the `InitialConditionsPerChannel` and `InitialConditionsPerSample` properties are both `true`, the property value must be a cell array of the same size as the input signal. Each cell of the cell array contains the delay values for one channel, and must be a vector of length equal to the `Length` property value.

If the `FrameBasedProcessing` property is `true`, and the input is an  $M$ -by- $N$  matrix, the dimensions of this property value must be as follows:

- If the `InitialConditionsPerChannel` and `InitialConditionsPerSample` properties are both `false`, the property value must be a scalar.
- If the `InitialConditionsPerChannel` property is `true` and the `InitialConditionsPerSample` property is `false`, the value must be a vector of length  $N$ .
- If the `InitialConditionsPerChannel` property is `false`, the `InitialConditionsPerSample` property is `true`, and the `Units` property is `Frames`, the value must be a vector of length equal to the product of  $M$  and the `Length` property value.
- If the `InitialConditionsPerChannel` property is `false`, the `InitialConditionsPerSample` property is `true`, and the `Units` property is `Samples`, the value must be a vector of length equal to the `Length` property value.
- If the `InitialConditionsPerChannel` and `InitialConditionsPerChannel` properties are both `true`, the property value must be a cell array of size  $N$ . Each cell of the cell array contains the delay values for one channel.

- If the `Units` property is `Frames`, each cell must be a vector of length equal to the product of  $M$  and the `Length` property value.
- If the `Units` property is `Samples`, each cell must be a vector of length equal to the `Length` property value.

## **ResetInputPort**

Enable resetting delay states

Specify when the delay object should reset the delay states. By default, the value of this property is `false`, and the object does not reset the delay states. When this property is set to `true`, a reset control input is provided to the `step` method, and the `ResetCondition` property applies. The object resets the delay states based on the values of the `ResetCondition` property and the reset input to the `step` method.

## **ResetCondition**

Reset trigger setting for delay

Specify the event to reset the delay as one of `| Rising edge | Falling edge | Either edge | Non-zero |`. The delay object resets the delay based on the values of this property and the reset input to the `step` method. This property applies when you set the `ResetInputPort` property to `true`. The default is `Non-zero`.

## **FrameBasedProcessing**

Enable frame-based processing

Set this property to `true` to enable frame-based processing. Set this property to `false` to enable sample-based processing. The default is `true`.

## Methods

<code>clone</code>	Create delay object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>reset</code>	Reset delay states
<code>step</code>	Apply delay to input

## Examples

Delay input by five samples:

```
hdelay1 = dsp.Delay(5);  
% Output is [0 0 0 0 0 1 2 3 4 5]'  
y = step(hdelay1, (1:10)');
```

---

Delay input by one frame:

```
hdelay2 = dsp.Delay;  
hdelay2.Units = 'Frames';  
hdelay2.Length = 1;  
  
% Output is zeros(10,1)  
y1 = step(hdelay2, (1:10)');  
  
% Output is (1:10)'  
y2 = step(hdelay2, (11:20)');
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Delay block reference page. The object properties correspond to the block parameters.

Both this object and its corresponding block let you specify whether to process inputs as individual samples or as frames of data. The object uses the `FrameBasedProcessing` property. The block uses the **Input processing** parameter. See “Set the FrameBasedProcessing Property of a System object” for more information.

## See Also

`dsp.VariableIntegerDelay` | `dsp.VariableFractionalDelay`.

**Purpose**

Create delay object with same property values

**Syntax**

`C = clone(H)`

**Description**

`C = clone(H)` creates a delay object, `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with uninitialized states.

# dsp.Delay.getNumInputs

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# dsp.Delay.isLocked

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the delay object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

# dsp.Delay.reset

---

**Purpose**            Reset delay states

**Syntax**            reset(H)

**Description**        reset(H) resets the states of the delay object H to the values specified in the InitialConditions property.

After you invoke the step method for a nonzero input, the delay object states may change and invoking the step method again without invoking the reset method may produce different outputs for identical inputs.

For example:

```
H = dsp.Delay(5);
% Delay input by 5 samples
y = step(H, (1:10)');
% Output is [0 0 0 0 0 1 2 3 4 5]'
% Invoke step without reset
y1 = step(H, (1:10)');
% Output is [6 7 8 9 10 1 2 3 4 5]'
% Reset states
reset(H);
y2 = step(H, (1:10)');
% Output is [0 0 0 0 0 1 2 3 4 5]'
```

**Purpose** Apply delay to input

**Syntax**  
 $Y = \text{step}(H, X)$   
 $Y = \text{step}(H, X, R)$

**Description**  $Y = \text{step}(H, X)$  adds delay to input  $X$  to return output  $Y$ .  
 $Y = \text{step}(H, X, R)$  adds delay to  $X$ , and selectively resets the delay object's state based on the value of reset input  $R$  and the value of the `ResetCondition` property. You can use this option only when you set the `ResetInputPort` property to `true`.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.DelayLine

---

**Purpose** Rebuffer sequence of inputs with one-sample shift

**Description** The `DelayLine` object rebuffers a sequence of inputs with one-sample shift.

To rebuffer a sequence of inputs with one-sample shift:

- 1 Define and set up your delay line object. See “Construction” on page 5-328.
- 2 Call `step` to rebuffer the sequence of inputs according to the properties of `dsp.DelayLine`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.DelayLine` returns a delay line System object, `H`, that buffers the input samples into a sequence of overlapping or underlapping matrix outputs.

`H = dsp.DelayLine('PropertyName',PropertyValue,...)` returns a delay line System object, `H`, with each specified property set to the specified value.

`H = dsp.DelayLine(DELAYSIZE,INITIAL,'PropertyName',PropertyValue,...)` returns a delay line System object, `H`, with the `Length` property set to `DELAYSIZE`, `InitialConditions` property set to `INITIAL` and other specified properties set to the specified values.

## Properties

### Length

Number of rows in output matrix

Specify the number of rows in the output matrix as a scalar positive integer. The default is 64.

### InitialConditions

Initial delay line output

Set the value of the object's initial output as one of | scalar | vector | matrix |.

For vector outputs, the following selections apply for the `InitialConditions` property:

- A vector of the same size
- A scalar value that you want repeated across all elements of the initial output

For matrix outputs, the following selections apply for the `InitialConditions` property:

- A matrix of the same size
- A vector (equal to the length of the number of matrix rows) that repeats across all columns of the initial output
- A scalar that repeats across all elements of the initial output

The default is 0.

## **DirectFeedthrough**

Enable passing input data to output without extra frame delay

When you set this property to `true`, there is no input data delay by an extra frame before it is available at the output buffer.

Instead, the input data is available immediately at the output.

When you set this property to `false`, there is one frame delay on the output. The default is `false`.

## **EnableOutputInputPort**

Enable selective output linearization

The object internally uses a circular buffer, even though the output is linear. To obtain a valid output, the object must linearize the circular buffer. When this property is `true`, the object uses an additional Boolean input to determine if a valid output calculation is needed. If Boolean the input value is 1, the object's output is linearized and thus valid. If Boolean the input value is 0, the output is not linearized and is invalid. This allows the object to be

# dsp.DelayLine

---

more efficient when each step does not require the tapped delay line output. When you set this property to `false`, the output is always linearized and valid. The default is `false`.

## HoldPreviousValue

Hold previous valid value for invalid output

If you set this property to `true`, the most recent, valid value is held on the output. If you set this property to `false`, the signal on the output is invalid data. This property applies only when you set the `EnableOutputInputPort` property to `true`. The default is `false`.

## Methods

<code>clone</code>	Create delay line object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>reset</code>	Reset internal states of delay line object
<code>step</code>	Delayed version of input

## Examples

Use a delay line object with a delay line size of 4 samples:

```
hdelayline = dsp.DelayLine( ...  
    'Length', 4, ...  
    'DirectFeedthrough', true, ...  
    'InitialConditions', -2, ...  
    'EnableOutputInputPort', true, ...  
    'HoldPreviousValue', true);
```

```
en = logical([1 1 0 1 0]);  
y = zeros(4,5);  
for ii = 1:5  
    y(:,ii) = step(hdelayline, ii, en(ii));  
end
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Delay Line block reference page. The object properties correspond to the block properties, except as noted.

This object processes inputs as separate channels (frames). The corresponding block has a temporary **Treat Mx1 and unoriented sample-based signals as** parameter with a `One channel` option for frame-based behavior and an `M channels` option for sample-based behavior. See the Delay Line block reference page and “Set the FrameBasedProcessing Property of a System object” for more information.

## See Also

`dsp.Delay`

# **dsp.DelayLine.clone**

---

**Purpose** Create delay line object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a `DelayLine` object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with uninitialized states.

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.DelayLine.getNumOutputs**

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, from the step method

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** isLocked(H)

**Description** isLocked(H) returns the locked state of the DelayLine object H.

The isLocked method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the step method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the isLocked method returns a true value.

# dsp.DelayLine.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Reset internal states of delay line object

**Syntax** reset(H)

**Description** reset(H) sets the internal delay buffers of the DelayLine object H to their initial conditions.

# dsp.DelayLine.step

---

**Purpose** Delayed version of input

**Syntax**  
 $Y = \text{step}(H, X)$   
 $Y = \text{step}(H, X, EN)$

**Description**  $Y = \text{step}(H, X)$  returns the delayed version of input  $X$ .  $Y$  is an output matrix with the same number of rows as the delay line size. Each column of  $X$  is treated as a separate channel.

The System object rebuffers a sequence of  $M_i$ -by- $N$  matrix inputs into a sequence of  $M_o$ -by- $N$  matrix outputs, where  $M_o$  is the output frame size specified by the Length property. Depending on whether  $M_o$  is greater than, less than, or equal to the input frame size,  $M_i$ , the output frames can be underlapped or overlapped. Each of the  $N$  input channels is rebuffered independently:

- When  $M_o > M_i$ , the output frame overlap is the difference between the output and input frame size,  $M_o - M_i$ .
- When  $M_o < M_i$ , the output is underlapped; the object discards the first  $M_i - M_o$  samples of each input frame so that only the last  $M_o$  samples are buffered into the corresponding output frame.
- When  $M_o = M_i$ , the output data is identical to the input data, but is delayed by the latency of the object.

$Y = \text{step}(H, X, EN)$  selectively outputs the delayed version of input  $X$  depending on the Boolean input  $EN$ . This occurs only when you set the EnableOutputInputPort property to true. If  $EN$  is false, use the HoldPreviousValue property to specify if the object should hold the previous output value(s).

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.DigitalDownConverter

---


**Purpose** Digitally downconvert input signal

**Description** The `DigitalDownConverter` object digitally downconverts the input signal.

To digitally downconvert the input signal:

- 1** Define and set up your digital down converter. See “Construction” on page 5-340.
- 2** Call `step` to downconvert the input according to the properties of `dsp.DigitalDownConverter`. The behavior of `step` is specific to each object in the toolbox.


**Construction** `h = dsp.DigitalDownConverter` returns a digital down-converter (DDC) System object, `h`. The object frequency downconverts the input signal by multiplying it with a complex exponential with center frequency equal to the value in the `CenterFrequency` property. The object downsamples the frequency down-converted signal using a cascade of three decimation filters. When you set the `FilterSpecification` property to `Design` parameters, the DDC object designs the decimation filters according to the filter parameters that you set in the filter-related object properties. In this case the filter cascade consists of a CIC decimator, a CIC compensator and a third FIR decimation stage. The following block diagram shows the architecture of the digital down converter.




The scaling section normalizes the CIC gain and the oscillator power. It may also contain a correction factor to achieve the desired ripple specification. When you set the **Oscillator** property to `InputPort`, the normalization factor does not include the oscillator power factor. Depending on the setting of the **DecimationFactor** property, you may be able to bypass the third filter stage. When the arithmetic is double or single precision, the CIC interpolator is implemented as a simple FIR interpolator with a boxcar response. A true CIC interpolator can only operate with fixed-point signals. The CIC filter is emulated with an FIR filter so that you can run simulations with floating-point data.

The following block diagram represents the DDC arithmetic with single or double-precision, floating-point inputs.

# dsp.DigitalDownConverter




The following block diagram represents the DDC arithmetic with signed fixed-point inputs.



- WL is the word length of the input, and FL is the fraction length of the input.
- The input of each filter is cast to the data type specified in the **FiltersInputDataType** and **CustomFiltersInputDataType** properties.
- The oscillator output is cast to a word length equal to the input word length plus one. The fraction length is equal to the input word length minus one.
- The scaling at the output of the CIC decimator consists of coarse- and fine-gain adjustments. The coarse gain is achieved using the `reinterpretcast` function on the CIC decimator output. The fine gain is achieved using full-precision multiplication.

The following figure depicts the coarse- and fine-gain operations.



If the normalization gain is  $G$ , (where  $0 < G \leq 1$ ), then:

- $WLCic$  is the word length of the CIC decimator output and  $FLCic$  is the fraction length of the CIC decimator output
- $F1 = \text{abs}(\text{nextpow2}(G))$ , indicating the part of  $G$  achieved using bit shifts (coarse gain)

# dsp.DigitalDownConverter

---

- $F2$  = fraction length specified by the **FiltersInputDataType** and **CustomFiltersInputDataType** properties
- $fg = fi((2^{F1}) * G, true, 16)$ , indicating that the remaining gain cannot be achieved with a bit shift (fine gain)

`h = dsp.DigitalDownConverter(Name, Value)` returns a DDC object, `h`, with the specified property `Name` set to the specified `Value`. You can specify additional name-value pair arguments in any order as `(Name1, Value1, ..., NameN, ValueN)`.

## Properties

### SampleRate

Sample rate of input signal

Set this property to a positive scalar value, greater than or equal to twice the value of the `CenterFrequency` property. The default is 30 Megahertz.

### DecimationFactor

Decimation factor

Set this property to a positive, integer scalar, or to a 1-by-2 or 1-by-3 vector of positive integers.

When you set this property to a scalar the object automatically chooses the decimation factors for each of the three filtering stages. The scalar value you specify cannot be a prime number.

When you set this property to a 1-by-2 vector, the object bypasses the third filter stage and sets the decimation factor of the first and second filtering stages to the values in the first and second vector elements respectively. When you set the `FilterSpecification` property to `Design` parameters, both elements of the `DecimationFactor` vector must be greater than one. When you set the `FilterSpecification` property to `Coefficients`, the first element of the `DecimationFactor` vector must be greater than 1.

When you set this property to a 1-by-3 vector, the  $i$ th element of the vector specifies the decimation factor for the  $i$ th filtering stage. When you set the `FilterSpecification` property to `Design parameters`, the first and second elements of the `DecimationFactor` vector must be greater than one and the third element must be 1 or 2. When you set the `FilterSpecification` property to `Coefficients`, the first element of the `DecimationFactor` vector must be greater than 1. When you set the `FilterSpecification` property to `Coefficients`, you must set the `DecimationFactor` property to a 1-by-3 or 1-by-2 vector. The default is 100.

## FilterSpecification

Filter specification

Set the filter specification as one of `Design parameters` | `Coefficients`. The default is `Design parameters`. The DDC object performs decimation using a cascade of three decimation filters. The first filter stage is always a CIC decimator. When you set the `FilterSpecification` property to `Design parameters`, the object designs the cascade of decimation filters internally, according to a set of parameters that you specify using the filter-related object properties. In this case, the second and third stages of the cascade consist of a CIC compensator, and a halfband or lowpass FIR decimator respectively. When you set the `FilterSpecification` property to `Coefficients`, you specify an arbitrary set of filter coefficients for the second and third filter stages using the `SecondFilterCoefficients`, and `ThirdFilterCoefficients` properties respectively. You specify the number of CIC sections using the `NumCICSections` property. In all cases, the third filter stage can be bypassed by setting the `DecimationFactor` property appropriately.

When the input data type is double or single the object implements an  $N$ -section CIC decimation filter as an FIR filter with a response that corresponds to a cascade of  $N$  boxcar filters. A true CIC filter with actual comb and integrator sections is implemented when the input data is of a fixed point type.

## **MinimumOrderDesign**

Minimum order filter design

When you set this property to true the object designs filters with the minimum order that meets the passband ripple, stopband attenuation, passband frequency, and stopband frequency specifications that you set using the `PassbandRipple`, `StopbandAttenuation`, `Bandwidth`, `StopbandFrequencySource`, and `StopbandFrequency` properties. When you set this property to false, the object designs filters with orders that you specify in the `NumCICSections`, `SecondFilterOrder`, and `ThirdFilterOrder` properties. The filter designs meet the passband and stopband frequency specifications that you set using the `Bandwidth`, `StopbandFrequencySource`, and `StopbandFrequency` properties. This property applies when you set the `FilterSpecification` property to `Design` parameters. The default is true.

## **NumCICSections**

Number of sections of CIC decimator

Set this property to a positive, integer scalar. This property applies when you set the `FilterSpecification` property to `Design` parameters and the `MinimumOrderDesign` property to false, or when you set the `FilterSpecification` property to `Coefficients`. The default is 3.

## **SecondFilterCoefficients**

Coefficients of second filter stage

Set this property to a double precision row vector of real coefficients that correspond to an FIR filter. Usually, the response of this filter should be that of a CIC compensator since a CIC decimation filter precedes the second filter stage. This property applies when you set the `FilterSpecification` property to `Coefficients`. The default is 1.

## **ThirdFilterCoefficients**

Coefficients of third filter stage

Set this property to a double precision row vector of real coefficients that correspond to an FIR filter. When you set the `DecimationFactor` property to a 1-by-2 vector, the object ignores the value of the `ThirdFilterCoefficients` property because the third filter stage is bypassed. This property applies when you set the `FilterSpecification` property to `Coefficients`. The default is 1.

## **SecondFilterOrder**

Order of CIC compensation filter stage

Set this property to a positive, integer scalar. This property applies when you set the `FilterSpecification` property to `Design` parameters and the `MinimumOrderDesign` property to `false`. The default is 12.

## **ThirdFilterOrder**

Order of third filter stage

Set this property to a positive, integer, even scalar. When you set the `DecimationFactor` property to a 1-by-2 vector, the object ignores the `ThirdFilterOrder` property because the third filter stage is bypassed. This property applies when you set the `FilterSpecification` property to `Design` parameters and the `MinimumOrderDesign` property to `false`. The default is 10.

## **Bandwidth**

Two sided bandwidth of input signal in Hertz

Set this property to a positive, integer scalar. The object sets the passband frequency of the cascade of filters to one-half of the value that you specify in the `Bandwidth` property. This property applies when you set the `FilterSpecification` property to `Design` parameters. The default is 200 kilohertz.

## **StopbandFrequencySource**

Source of stopband frequency

Specify the source of the stopband frequency as one of Auto | Property. The default is Auto. When you set this property to Auto, the object places the cutoff frequency of the cascade filter response at approximately  $F_c = \text{SampleRate}/M/2$  Hertz, where  $M$  is the total decimation factor that you specify in the DecimationFactor property. The object computes the stopband frequency as  $F_{stop} = F_c + TW/2$ .  $TW$  is the transition bandwidth of the cascade response computed as  $2*(F_c - F_p)$ , and the passband frequency,  $F_p$ , equals Bandwidth/2. This property applies when you set the FilterSpecification property to Design parameters.

## StopbandFrequency

Stopband frequency in Hertz

Set this property to a double precision positive scalar. This property applies when you set the FilterSpecification property to Design parameters and the StopbandFrequencySource property to Property. The default is 150 kilohertz.

## PassbandRipple

Passband ripple of cascade response in decibels.

Set this property to a double precision, positive scalar. When you set the MinimumOrderDesign property to true, the object designs the filters so that the cascade response meets the passband ripple that you specify in the PassbandRipple property. This property applies when you set the FilterSpecification property to Design parameters and the MinimumOrderDesign property to true. The default is 0.1 decibels.

## StopbandAttenuation

Stopband attenuation of cascade response in decibels

Set this property to a double precision, positive scalar. When you set the MinimumOrderDesign property to true, the object designs the filters so that the cascade response meets the stopband attenuation that you specify in the

StopbandAttenuation property. This property applies when you set the FilterSpecification property to Design parameters and the MinimumOrderDesign property to true. The default is 60 decibels.

## **Oscillator**

Type of oscillator

Specify the oscillator as one of Sine wave | NCO | Input port. The default is Sine wave. When you set this property to Sine wave, the object frequency down converts the input signal using a complex exponential obtained from samples of a sinusoidal trigonometric function. When you set this property to NCO the object performs frequency down conversion with a complex exponential obtained using a numerically controlled oscillator (NCO). When you set this property to Input port, the object performs frequency down conversion using the complex signal that you set as an input to the step method.

## **CenterFrequency**

Center frequency of input signal in Hertz

Specify this property as a double precision positive scalar that is less than or equal to half the value of the SampleRate property. The object down converts the input signal from the passband center frequency you specify in the CenterFrequency property, to 0 Hertz. This property applies when you set the Oscillator property to Sine wave or NCO. The default is 14 Megahertz.

## **NumAccumulatorBits**

Number of NCO accumulator bits

Specify this property as an integer scalar in the range [1 128]. This property applies when you set the Oscillator property to NCO. The default is 16.

## **NumQuantizedAccumulatorBits**

Number of NCO quantized accumulator bits

Specify this property as an integer scalar in the range [1 128]. The value you specify in this property must be less than the value you specify in the NumAccumulatorBits property. This property applies when you set the Oscillator property to NCO. The default is 12.

## **Dither**

Dither control for NCO

When you set this property to true, a number of dither bits specified in the NumDitherBits property will be used to apply dither to the NCO signal. This property applies when you set the Oscillator property to NCO. The default is true.

## **NumDitherBits**

Number of NCO dither bits

Specify this property as an integer scalar smaller than the number of accumulator bits that you specify in the NumAccumulatorBits property. This property applies when you set the Oscillator property to NCO and the Dither property to true. The default is 4.

## **Fixed-Point Properties**

### **SecondFilterCoefficientsDataType**

Data type of second filter coefficients

Specify the second filter coefficients data type as Same as input | Custom. The default is Same as input. This property applies when you set the FilterSpecification property to Coefficients.

### **CustomSecondFilterCoefficientsDataType**

Fixed-point data type of second filter coefficients

Specify the second filter coefficients fixed-point type as a scaled numerictype object with a Signedness of Auto. This property

applies when you set the `SecondFilterCoefficientsDataType` property to `Custom`. The default is `numerictype([],16,15)`.

## **ThirdFilterCoefficientsDataType**

Data type of third filter coefficients

Specify the third filter coefficients data type as `Same as input` | `Custom`. The default is `Same as input`. This property applies when you set the `FilterSpecification` property to `Coefficients`.

## **CustomThirdFilterCoefficientsDataType**

Fixed-point data type of third filter coefficients

Specify the third filter coefficients fixed-point type as a scaled `numerictype` object with a `Signedness` of `Auto`. This property applies when you set the `ThirdFilterCoefficientsDataType` property to `Custom`. The default is `numerictype([],16,15)`.

## **FiltersInputDataType**

Data type of input of each filter stage

Specify the data type at the input of the first, second, and third (if it has not been bypassed) filter stages as one of `Same as input` | `Custom`. The default is `Same as input`. The object casts the data at the input of each filter stage according to the value you set in this property.

## **CustomFiltersInputDataType**

Fixed-point data type of input of each filter stage

Specify the filters input fixed-point type as a scaled `numerictype` object with a `Signedness` of `Auto`. This property applies when you set the `FiltersInputDataType` property to `Custom`. The default is `numerictype([],16,15)`.

## **OutputDataType**

Data type of output

# dsp.DigitalDownConverter

---

Specify the data type of output as `Same as input` | `Custom`. The default is `Same as input`.

## CustomOutputDataType

Fixed-point data type of output

Specify the output fixed-point type as a scaled numeric type object with a Signedness of `Auto`. This property applies when you set the `OutputDataType` property to `Custom`. The default is `numericType([], 16, 15)`.

## Methods

<code>clone</code>	Create digital down converter object with same property values
<code>fvtool</code>	Visualize response of filter cascade
<code>getDecimationFactors</code>	Get decimation factors of each filter stage
<code>getFilterOrders</code>	Get orders of decimation filters
<code>getFilters</code>	Get handles to decimation filter objects
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>groupDelay</code>	Group delay of filter cascade
<code>isLocked</code>	Locked status for input attributes and non-tunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>step</code>	Digitally down convert input signal
<code>visualizeFilterStages</code>	Display response of filter stages

## Copy Semantics

Handle. To learn how handle classes affect copy operations, see Copying Objects in the MATLAB Programming Fundamentals documentation.

## Examples

Create a digital up converter object that up samples a 1 KHz sinusoidal signal by a factor of 20 and up converts it to 50 KHz. Create a digital down converter object that down converts the signal to 0 Hz and down samples it by a factor of 20.

```
% Create a sine wave generator to obtain the 1 KHz
% sinusoidal signal with a sample rate of 6 KHz.
Fs = 6e3; % Sample rate
hSig = dsp.SineWave('Frequency',1000,'SampleRate',...
Fs,'SamplesPerFrame',1024);
x = step(hSig); % generate signal

% Create a DUC object. Use minimum order filter designs and set
% passband ripple to 0.2 dB and the stopband attenuation to 55 dB.
% Set the double sided signal bandwidth to 2 KHz.
hDUC = dsp.DigitalUpConverter(...
'InterpolationFactor', 20,...
'SampleRate', Fs,...
'Bandwidth', 2e3,...
'StopbandAttenuation', 55,...
'PassbandRipple',0.2,...
'CenterFrequency',50e3);

% Create a DDC object. Use minimum order filter designs and set the
% passband ripple to 0.2 dB and the stopband attenuation to 55 dB.
hDDC = dsp.DigitalDownConverter(...
'DecimationFactor',20,...
'SampleRate', Fs*20,...
'Bandwidth', 3e3,...
'StopbandAttenuation', 55,...
'PassbandRipple',0.2,...
'CenterFrequency',50e3);

% Create a spectrum estimator to visualize the signal spectrum before
```

# dsp.DigitalDownConverter

---

```
% up converting, after up converting, and after down converting.
hSEst = spectrum.welch; hSEst.SegmentLength = length(x)/10;
hOpts=psdopts(hSEst);
set(hOpts, 'Fs', Fs, 'SpectrumType','twosided','CenterDC',true);
figure; psd(hSEst,x,hOpts)
title('Spectrum of baseband signal x')

% Up convert the signal and visualize the spectrum
xUp = step(hDUC,x); % up convert
hOpts.Fs = Fs*20; hSEst.SegmentLength = length(xUp)/10;
figure; psd(hSEst,xUp,hOpts)
title('Spectrum of up converted signal xUp')

% Down convert the signal and visualize the spectrum
xDown = step(hDDC,xUp); % down convert
hOpts.Fs = Fs; hSEst.SegmentLength = length(xDown)/10;
figure; psd(hSEst,xDown,hOpts)
title('Spectrum of down converted signal xDown')

% Visualize the response of the decimation filters
visualizeFilterStages(hDDC)
```

For additional examples using this System object, see the following demos:

- Digital Up and Down Conversion for Family Radio Service
- Design and Analysis of a Digital Down Converter

## See Also

`dsp.DigitalUpConverter`

**Purpose**

Create digital down converter object with same property values

**Syntax**

`C = clone(H)`

**Description**

`C = clone(H)` creates a `DigitalDownConverter System` object, `C`, with the same property values as `H`.

The `clone` method creates a new unlocked object with uninitialized states.

# dsp.DigitalDownConverter.fvtool

---

**Purpose** Visualize response of filter cascade

**Syntax**  
`fvtool(H)`  
`fvtool(H,...,'Arithmetic',ARITH,...)`  
`fvtool(H,..., PROP1, VALUE1,PROP2,VALUE2,...)`

**Description** `fvtool(H)` plots the magnitude response of the cascade of filters. By default, the object plots the cascade response up to the second CIC null frequency (or to the first when only one CIC null exists). When you set the `FilterSpecification` property to `Design` parameters the method plots a mask based on the filter specifications.

`fvtool(H,...,'Arithmetic',ARITH,...)` specifies the arithmetic of the filter cascade. You set input `ARITH` to `double`, `single`, or `fixed-point`. When object `H` is in an unlocked state you must specify the arithmetic. When object `H` is in a locked state the arithmetic input is ignored.

`fvtool(H,..., PROP1, VALUE1,PROP2,VALUE2,...)` launches `FVTool` and sets the specified `FVTool` properties to the specified values.

# **dsp.DigitalDownConverter.getDecimationFactors**

---

**Purpose** Get decimation factors of each filter stage

**Syntax** `M = getDecimationFactors(H)`

**Description** `M = getDecimationFactors(H)` returns a vector, `M`, with the decimation factors of each filter stage. If the third filter stage is bypassed, then `M` is a 1-by-2 vector containing the decimation factors of the first and second filter stages in the first and second elements respectively. If the third filter stage is not bypassed then `M` is a 1-by-3 vector containing the decimation factors of the first, second and third filter stages.

# **dsp.DigitalDownConverter.getFilters**

---

**Purpose** Get handles to decimation filter objects

**Syntax** `S = getFilters(H)`  
`getFilters(H, 'Arithmetic', ARITH)`

**Description** `S = getFilters(H)` returns a structure, `S`, with copies of the filter System objects and the CIC normalization factor that form the decimation filter cascade. The `ThirdFilterStage` structure field is empty if the third filter stage has been bypassed. The CIC normalization factor equals the inverse of the CIC filter gain. In some cases, this gain includes a correction factor to ensure that the cascade response meets the ripple specifications.

`getFilters(H, 'Arithmetic', ARITH)` specifies the arithmetic of the filter stages. You can set `ARITH` to `double`, `single`, or `fixed-point`. When object `H` is in an unlocked state, you must specify the arithmetic input. When object `H` is in a locked state, the arithmetic input is ignored.

When `H` is in an unlocked state, and you specify the arithmetic as `fixed-point`, the `getFilters` method returns filter System objects. The custom coefficient data type properties of these System objects are set to the values that the `dsp.DigitalDownConverter` System object uses to process data when you call the `step` method. All other fixed-point properties are set to their default values.

When `H` is in a locked state, and the input to the `step` method is of a fixed-point data type, the `getFilters` method returns filter System objects. All fixed-point properties of these System objects are set to the exact values that the `dsp.DigitalDownConverter` System object uses to process the data.

# **dsp.DigitalDownConverter.getFilterOrders**

---

**Purpose** Get orders of decimation filters

**Syntax** `S = getFilterOrders(H)`

**Description** `S = getFilterOrders(H)` returns a structure, `S`, that contains the orders of the interpolation filter stages. The `ThirdFilterOrder` structure field will be empty if the third filter stage has been bypassed.

# dsp.DigitalDownConverter.getNumInputs

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.DigitalDownConverter.getNumOutputs

---

**Purpose**

Number of outputs of step method

**Syntax**

`N = getNumOutputs(H)`

**Description**

`N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# **dsp.DigitalDownConverter.groupDelay**

---

**Purpose**            Group delay of filter cascade

**Syntax**             $D = \text{groupDelay}(H,N)$   
                       $[D,F] = \text{groupDelay}(H,N)$

**Description**         $D = \text{groupDelay}(H,N)$  returns a vector of group delays,  $D$ , evaluated at  $N$  frequency points equally spaced around the upper half of the unit circle. If you don't specify  $N$ , it defaults to 8192.

$[D,F] = \text{groupDelay}(H,N)$  returns a vector of frequencies,  $F$ , at which the group delay has been computed.

**Purpose** Locked status for input attributes and non-tunable properties

**Syntax** `Y = isLocked(H)`

**Description** `Y = isLocked(H)` returns the locked state, `Y`, of the `DigitalUpConverter` object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# **dsp.DigitalDownConverter.release**

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections. This method lets you change any properties or input characteristics.

**Purpose** Digitally down convert input signal

**Syntax**  
 $Y = \text{step}(H,X)$   
 $Y = \text{step}(H,X,Z)$

**Description**  $Y = \text{step}(H,X)$  takes a real or complex input column vector  $X$  and outputs a frequency down converted and down sampled signal  $Y$ . The length of input  $X$  must be a multiple of the decimation factor.  $X$  can be of data type double, single, signed integer, or signed fixed point (fi objects). The length of  $Y$  is equal to the length of  $X$  divided by the `DecimationFactor`. When the data type of  $X$  is double or single precision, the data type of  $Y$  is the same as that of  $X$ . When the data type of  $X$  is of a fixed point type, the data type of  $Y$  is defined by the `OutputDataType` property.

$Y = \text{step}(H,X,Z)$  uses the complex input,  $Z$ , as the oscillator signal used to frequency down convert input  $X$ , when you set the `Oscillator` property to `Input` port. The length of  $Z$  must be equal to the length of  $X$ .  $Z$  can be of data type double, single, signed integer, or signed fixed point (fi objects).

# dsp.DigitalDownConverter.visualizeFilterStages

---

**Purpose** Display response of filter stages

**Syntax**  
`visualizeFilterStages(H)`  
`visualizeFilterStages(H, 'Arithmetic', ARITH)`  
`hfvt = visualizeFilterStages(H)`

**Description** `visualizeFilterStages(H)` plots the magnitude response of the filter stages and of the cascade response. When you set the `FilterSpecification` property to `Design` parameters the method plots a mask based on the filter specifications. By default, the object plots the response of the filters up to the second CIC null frequency (or to the first when only one CIC null exists).

`visualizeFilterStages(H, 'Arithmetic', ARITH)` specifies the arithmetic of the filter stages. You set input `ARITH` to `double`, `single`, or `fixed-point`. When object `H` is in an unlocked state you must specify the arithmetic. When object `H` is in a locked state the arithmetic input is ignored.

`hfvt = visualizeFilterStages(H)` returns the handle to the `FVTool` object.

<b>Purpose</b>	Static or time-varying digital filter
<b>Description</b>	<p>The <code>DigitalFilter</code> object filters each channel of the input using static or time-varying digital filter implementations.</p> <p>To filter each channel of the input using digital filter implementation:</p> <ol style="list-style-type: none"><li>1 Define and set up your IIR digital filter. See “Construction” on page 5-367.</li><li>2 Call <code>step</code> to filter each channel according to the properties of <code>dsp.DigitalFilter</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.DigitalFilter</code> returns a default IIR digital filter object, <code>H</code>, which independently filters each channel of the input over successive calls to the <code>step</code> method, using a specified digital filter implementation. The default numerator coefficients are <code>[1 2]</code> and denominator coefficients are <code>[1 0.1]</code>.</p> <p><code>H = dsp.DigitalFilter('PropertyName',PropertyValue, ...)</code> returns a digital filter object, <code>H</code>, with each property set to the specified value.</p>
<b>Properties</b>	<p><b>TransferFunction</b></p> <p>Type of filter transfer function</p> <p>Specify the type of digital filter transfer function as one of <code>  IIR (poles &amp; zeros)   IIR (all poles)   FIR (all zeros)  </code>. The default is <code>IIR (poles &amp; zeros)</code>.</p> <p><b>Structure</b></p> <p>Filter structure</p> <p>Specify the filter structure.</p> <p>When you set the <code>TransferFunction</code> property to <code>FIR (all zeros)</code>, you can specify the filter structure as one of <code> </code></p>

Direct form | Direct form symmetric | Direct form antisymmetric | Direct form transposed | Lattice MA | .  
The default is Direct form.

When you set the TransferFunction property to IIR (all poles), you can specify the filter structure as Direct form, Direct form transposed, or Lattice AR. The default is Direct form.

When you set the TransferFunction to IIR (poles & zeros), you can specify the filter structure as Direct form I, Direct form I transposed, Direct form II, Direct form II transposed, Biquad direct form I (SOS), Biquad direct form I transposed (SOS), Biquad direct form II (SOS), or Biquad direct form II transposed (SOS). The biquad filter structure does not apply when you set the CoefficientsSource property to Input port. The default is Direct form II transposed.

## **CoefficientsSource**

Source of filter coefficients

Specify the source of the filter coefficients as one of | Property | Input port | . The default is Property. When you specify Input port, the digital filter object updates the time-varying filter once every frame, when the FrameBasedProcessing property is true. When the FrameBasedProcessing property is false, it updates once every sample.

## **Numerator**

Numerator coefficients

Specify the filter numerator coefficients as a real or complex numeric vector. This property applies when you set the TransferFunction property to FIR (all zeros), the CoefficientsSource property to Property, and the Structure property is not set to Lattice MA. This property also applies when you set the TransferFunction property to IIR (poles & zeros), the CoefficientsSource to Property, and the

TransferFunction property to Direct form, Direct form symmetric, Direct form antisymmetric, or Direct form transposed. The default is [1 2]. This property is tunable.

## **Denominator**

Denominator coefficients

Specify the filter denominator coefficients as a real or complex numeric vector. This property applies when you set the TransferFunction property to IIR (all poles), the CoefficientsSource property to Property and the Structure property is not set to Lattice AR. This property also applies when you set the TransferFunction property to IIR (poles & zeros), the CoefficientsSource to Property, and the TransferFunction property to Direct form, Direct form symmetric, Direct form antisymmetric, or Direct form transposed. When the TransferFunction property is IIR (poles & zeros), the numerator and denominator must have the same complexity. The default is [1 0.1]. This property is tunable.

## **ReflectionCoefficients**

Reflection coefficients of lattice filter structure

Specify the reflection coefficients of a lattice filter as a real or complex numeric vector. This property applies when you set the TransferFunction property to FIR (all zeros), the Structure property to Lattice MA, and the CoefficientsSource property to Property. This property also applies when you set the TransferFunction property to IIR (all poles), the Structure property to Lattice AR, and the CoefficientsSource property to Property. The default is [0.2 0.4]. This property is tunable.

## **SOSMatrix**

SOS matrix of biquad filter structure

Specify the second-order section (SOS) matrix of a biquad filter as an  $M$ -by-6 matrix, where  $M$  is the number of sections in the

filter. Each row of the SOS matrix contains the numerator and denominator coefficients of the corresponding filter section. The first three elements of each row are the numerator coefficients and the last three elements are the denominator coefficients. You can use real or complex coefficients. This property applies when you set the `TransferFunction` property to IIR (poles and zeros), the `CoefficientsSource` property to `Property`, and the `Structure` property to Biquad direct form I (SOS), Biquad direct form I transposed (SOS), Biquad direct form II (SOS), or Biquad direct form II transposed (SOS). The default is [1 0.3 0.4 1 0.1 0.2]. This property is tunable.

## ScaleValues

Scale values of biquad filter structure

Specify the scale values to apply before and after each section of a biquad filter. `ScaleValues` must be a scalar or a vector of length  $M+1$ , where  $M$  is the number of sections. If you specify a scalar value, that value is used as the gain value before the first section of the second-order filter and the rest of the gain values are set to 1. If you specify a vector of  $M+1$  values, each value is used for a separate section of the filter. This property applies when you set the `TransferFunction` property to IIR (poles & zeros), the `CoefficientsSource` property to `Property`, and the `Structure` property to Biquad direct form I (SOS), Biquad direct form I transposed (SOS), Biquad direct form II (SOS), or Biquad direct form II transposed (SOS). The default is 1. This property is tunable.

## IgnoreFirstDenominatorCoefficient

Assume first denominator coefficient is 1

Setting this Boolean property to `true` reduces the number of computations to produce the digital filter output by omitting the first denominator term,  $a_0$ , (poles side) in the filter structure. The object output is invalid when you set this property to `true` when the first denominator coefficient is not always 1 for your time-varying filter. The object ignores this property for

fixed-point inputs, because this object does not support nonunity  $a_0$  coefficients for fixed-point inputs.

This property applies when you set the `CoefficientsSource` property to `Input port`, the `TransferFunction` property to `IIR (all poles)`, and the `Structure` property is not set to `Lattice AR`. This property also applies when you set the `CoefficientsSource` property to `Input port`, the `TransferFunction` property to `IIR (poles & zeros)`, and the `Structure` property to `Direct form`, `Direct form symmetric`, `Direct form antisymmetric`, or `Direct form transposed`. The default is `true`.

## InitialConditions

Initial conditions for all poles or all zeros filter

Specify the initial conditions of the filter states. When the `TransferFunction` property is `FIR (all zeros)` or `IIR (all poles)`, the number of states or delay elements equals the number of reflection coefficients for the lattice structure, or the number of filter coefficients–1 for the other direct form structures. When the `TransferFunction` property is `IIR (poles & zeros)`, the number of states for direct form II and direct form II transposed structures equals the  $\max(N, M) - 1$ , where  $N$  and  $M$  are the number of poles and zeros, respectively.

You can specify the initial conditions as a scalar, vector, or matrix. If you specify a scalar value, the digital filter object initializes all delay elements in the filter to that value. If you specify a vector whose length equals the number of delay elements in the filter, each vector element specifies a unique initial condition for the corresponding delay element. The object applies the same vector of initial conditions to each channel of the input signal.

If you specify a vector whose length equals the product of the number of input channels and the number of delay elements in the filter, each element specifies a unique initial condition for the corresponding delay element in the corresponding channel.

If you specify a matrix with the same number of rows as the number of delay elements in the filter, and one column for each channel of the input signal, each element specifies a unique initial condition for the corresponding delay element in the corresponding channel. This property applies when you do not set the Structure property to Direct Form I, Direct Form I transposed, Biquad direct form I (SOS), or Biquad direct form I transposed (SOS). The default is 0.

## **NumeratorInitialConditions**

Initial conditions on zeros side

Specify the initial conditions of the filter states on the side of the filter structure with the zeros. This property applies when you set the TransferFunction property to IIR (poles & zeros) and the Structure property is Direct form I, Direct form I transposed, Biquad direct form I (SOS), or Biquad direct form I transposed (SOS). The default is 0. See the InitialConditions property for information on setting initial conditions.

## **DenominatorInitialConditions**

Initial conditions on poles side

Specify the initial conditions of the filter states on the side of the direct form I (noncanonic) filter structure with the poles. This property applies when you set the TransferFunction property to IIR (poles & zeros) and the Structure property to Direct form I, Direct form I transposed, Biquad direct form I (SOS), or Biquad direct form I transposed (SOS). The default is 0. See the InitialConditions property for information on setting initial conditions.

## **FrameBasedProcessing**

Enable frame-based processing

Set this property to `true` to enable frame-based processing. Set this property to `false` to enable sample-based processing. The default is `true`.

## Fixed-Point Properties

### RoundingMethod

Rounding method for fixed-point operations

Specify the rounding method as one of | `Ceiling` | `Convergent` | `Floor` | `Nearest` | `Round` | `Simplest` | `Zero` |. The default is `Floor`.

### OverflowAction

Overflow action for fixed-point operations

Specify the overflow action as one of | `Wrap` | `Saturate` |. The default is `Wrap`.

### TapSumDataType

Tap sum word and fraction lengths

Specify the tap sum fixed-point data type as one of | `Same as input` | `Custom` |. This property applies when you set the `TransferFunction` property to `FIR (all zeros)` and the `Structure` property to either `Direct form symmetric` or `Direct form antisymmetric`. The default is `Same as input`.

### CustomTapSumDataType

Custom tap sum word and fraction lengths

Specify the tap sum fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `TapSumDataType` property to `Custom`. The default is `numericType([],32,30)`.

### MultiplicandDataType

Multiplicand word and fraction lengths

Specify the multiplicand fixed-point data type as one of | Same as output | Custom |. This property applies when you set the Structure property to either Direct form I transposed or Biquad direct form I transposed (SOS). The default is Same as output.

## **CustomMultiplicandDataType**

Custom multiplicand word and fraction lengths

Specify the multiplicand fixed-point type as a scaled numeric type object with a Signedness of Auto. This property applies when you set the MultiplicandDataType property to Custom. The default is numeric type ([ ], 32, 30).

## **SectionInputDataType**

Section input word and fraction lengths

Specify the section input fixed-point data type as one of | Same as input | Custom |. Setting this property also sets the SectionOutputDataType property to the same value. This property applies when you set the TransferFunction property to IIR (poles & zeros) and the Structure property to one of the biquad filter structures. The default is Same as input.

## **CustomSectionInputDataType**

Custom section input word and fraction lengths

Specify the section input fixed-point type as a scaled numeric type object with a Signedness of Auto. This property applies when you set the SectionInputDataType property to Custom. The CustomSectionInputDataType and CustomSectionOutputDataType property values must have equal word lengths. The default is numeric type ([ ], 16, 15).

## **SectionOutputDataType**

Section output word and fraction lengths

Specify the section output fixed-point data type as one of | Same as input | Custom |. Setting this property also sets

the `SectionInputDataType` property to the same value. This property applies when you set the `TransferFunction` property to IIR (poles & zeros) and the `Structure` property to one of the biquad filter structures. The default is `Same as input`.

## **CustomSectionOutputDataType**

Custom section output word and fraction lengths

Specify the section output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `SectionOutputDataType` property to `Custom`. The `CustomSectionInputDataType` and `CustomSectionOutputDataType` property values must have equal word lengths. The default is `numericType([],16,15)`.

## **NumeratorCoefficientsDataType**

Numerator coefficients word and fraction lengths

Specify the numerator coefficients fixed-point data type as one of `| Same word length as input | Custom |`. Setting this property also sets the `DenominatorCoefficientsDataType` and the `ScaleValuesDataType` properties, if applicable, to the same value. This property applies when you set the `CoefficientsSource` property to `Property` and the `TransferFunction` property is not set to IIR (all poles). The default is `Same word length as input`.

## **CustomNumeratorCoefficientsDataType**

Custom numerator coefficients word and fraction lengths

Specify the numerator coefficients fixed-point type as a `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `NumeratorCoefficientsDataType` property to `Custom`. The `CustomNumeratorCoefficientsDataType`, `CustomDenominatorCoefficientsDataType` and `ScaleValuesDataType` properties, if applicable, must have equal word lengths. The default is `numericType([],16,15)`.

## **DenominatorCoefficientsDataType**

Denominator coefficients word and fraction lengths

Specify the denominator coefficients fixed-point data type as one of | Same word length as input | Custom |. Setting this property also sets the NumeratorCoefficientsDataType and ScaleValuesDataType properties, if applicable, to the same value. This property applies when you set the CoefficientsSource property to Property and the TransferFunction property is not set to FIR (all zeros). The default is Same word length as input.

## **CustomDenominatorCoefficientsDataType**

Custom denominator coefficients word and fraction lengths

Specify the denominator coefficients fixed-point type as a numeric type object with a Signedness of Auto. This property applies when you set the DenominatorCoefficientsDataType property to Custom. The CustomNumeratorCoefficientsDataType, CustomDenominatorCoefficientsDataType and CustomScaleValuesDataType properties, if they apply, must have equal word lengths. The default is numeric type([], 16, 15).

## **ScaleValuesDataType**

Scale values word and fraction lengths

Specify the scale values fixed-point data type as one of | Same word length as input | Custom |. Setting this property also sets the NumeratorCoefficientsDataType and the DenominatorCoefficientsDataType properties, if they apply, to the same value. This property applies when you set the CoefficientsSource property to Property, the TransferFunction property to IIR (poles & zeros), and the Structure property to one of the biquad filter structures. The default is Same word length as input.

## **CustomScaleValuesDataType**

Custom scale values word and fraction lengths

Specify the scale values fixed-point type as a `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `CoefficientsSource` property to `Property` and the `ScaleValuesDataType` property to `Custom`. The `CustomNumeratorCoefficientsDataType`, `CustomDenominatorCoefficientsDataType`, and the `CustomScaleValuesDataType` properties, if applicable, must have equal word lengths. The default is `numericType([],16,15)`.

### **ProductDataType**

Product word and fraction lengths

Specify the product fixed-point data type as one of `| Same as input | Custom |`. The default is `Same as input`.

### **CustomProductDataType**

Custom product word and fraction lengths

Specify the product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `ProductDataType` property to `Custom`. The default is `numericType([],32,30)`.

### **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point data type to one of `| Same as input | Same as product | Custom |`. The default is `Same as product`.

### **CustomAccumulatorDataType**

Custom accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `AccumulatorDataType` property to `Custom`. The default is `numericType([],32,30)`.

## StateDataType

State word and fraction lengths

Specify the state fixed-point data type as one of | Same as input | Same as accumulator | Custom |. This property does not apply to any of the direct form or direct form I filter structures. The default is Same as accumulator.

## CustomStateDataType

Custom state word and fraction lengths

Specify the state fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `StateDataType` property to `Custom`. The default is `numericType([],16,15)`.

## OutputDataType

Output word and fraction lengths

Specify the output fixed-point data type as one of | Same as input | Same as accumulator | Custom |. The default is Same as accumulator.

## CustomOutputDataType

Custom output word and fraction lengths

Specify the output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `OutputDataType` property to `Custom`. The default is `numericType([],16,15)`.

## Methods

<code>clone</code>	Create static or time-varying digital filter with same property values
<code>getNumInputs</code>	Number of expected inputs to step method

getNumOutputs	Number of outputs of step method
isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
reset	Reset internal states of digital filter
step	Filter input with digital filter object

## Examples

Use an FIR filter to apply a low pass filter to a waveform with two sinusoidal components:

```
t = [0:63]./32e3;  
xin = (sin(2*pi*4e3*t)+sin(2*pi*12e3*t)) / 2;
```

```
hSR = dsp.SignalSource(xin', 4);  
hLog = dsp.SignalSink;  
hFilt = dsp.DigitalFilter;  
hFilt.TransferFunction = 'FIR (all zeros)';  
hFilt.Numerator = fir1(10,0.5);
```

```
while ~isDone(hSR)  
    input = step(hSR);  
    filteredOutput = step(hFilt,input);  
    step(hLog,filteredOutput);  
end
```

```
filteredResult = hLog.Buffer;  
sper = spectrum.periodogram;  
psd(sper,filteredResult,'Fs',32e3)
```

# dsp.DigitalFilter

---

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Digital Filter block reference page. The object properties correspond to the block parameters.

Both this object and its corresponding block let you specify whether to process inputs as individual samples or as frames of data. The object uses the `FrameBasedProcessing` property. The block uses the **Input processing** parameter. See “Set the FrameBasedProcessing Property of a System object” for more information.

## See Also

`dsp.BiquadFilter`

**Purpose** Create static or time-varying digital filter with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a digital filter object, `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with uninitialized states.

# dsp.DigitalFilter.getNumInputs

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose**

Number of outputs of step method

**Syntax**

`N = getNumOutputs(H)`

**Description**

`N = getNumOutputs(H)` returns the number of outputs, `N`, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# **dsp.DigitalFilter.isLocked**

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the digital filter.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

# dsp.DigitalFilter.reset

---

**Purpose** Reset internal states of digital filter

**Syntax** reset(H)

**Description** reset(H) resets the filter states of the digital filter object,H, to their initial values of 0. The initial filter state values correspond to the initial conditions for the difference equation defining the filter. After the step method applies the digital filter object to nonzero input data, the states may be nonzero. Invoking the step method again without first invoking the reset method may produce different outputs for an identical input.

For example:

```
H = dsp.DigitalFilter;
H.TransferFunction = 'FIR (all zeros)';
H.Numerator = fir1(20,0.25);
n = 0:100;
x = cos(0.2*pi*n)+sin(0.8*pi*n);
y = step(H,x);
% Filter states are nonzero
% Invoke step method again without resetting states
y1 = step(H,x);
isequal(y,y1) % returns 0
% Now reset filter states to 0
reset(H)
% Invoke step method
y2 = step(H,x);
isequal(y,y2) % returns a 1
```

**Purpose** Filter input with digital filter object

**Syntax**

```
Y = step(HFILT,X)
Y = step(HFILT,X,COEFF)
Y = step(HFILT,X,NUM,DEN)
```

**Description** `Y = step(HFILT,X)` filters the real or complex input signal `X` using the digital filter, `H`, to produce the output `Y`. The digital filter object operates on each channel of the input signal independently over successive calls to `step` method.

`Y = step(HFILT,X,COEFF)` uses the time-varying numerator or denominator coefficients, `COEFF`, to filter the input signal `X` and produce the output `Y`. You can use this option when you set the `TransferFunction` property to either `FIR` (all zeros) or `IIR` (all poles) and the `CoefficientsSource` property to `Input` port.

`Y = step(HFILT,X,NUM,DEN)` uses the time-varying numerator coefficients `NUM` and the time-varying denominator coefficients `DEN` to filter the input signal `X` and produce the output `Y`. You can use this option when you set the `TransferFunction` property to `IIR` (poles and zeros) and the `CoefficientsSource` property to `Input` port.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---


# dsp.DigitalUpConverter

**Purpose** Digitally upconvert input signal

**Description** The DigitalUpConverter object digitally upconverts the input signal. To digitally up convert the input signal:


- 1 Define and set up your digital up converter. See “Construction” on page 5-388.
- 2 Call `step` to upconvert the input according to the properties of `dsp.DigitalUpConverter`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `h = dsp.DigitalUpConverter` returns a digital up-converter (DDC) System object, `h`. The object up samples the input signal using a cascade of three interpolation filters. This object frequency upconverts the up sampled signal by multiplying it with a complex exponential with center frequency equal to the value in the `CenterFrequency` property. When you set the `FilterSpecification` property to 'Design parameters', the DUC object designs the interpolation filters according to the filter specifications that you set in the filter-related object properties. In this case the filter cascade consists of a first FIR interpolation stage, a CIC compensator, and a CIC interpolator. The following block diagram shows the architecture of the digital up converter.



The scaling section normalizes the CIC gain and the oscillator power. It may also contain a correction factor to achieve the desired ripple specification. Depending on the setting of the **InterpolationFactor** property, you may be able to bypass the first filter stage. When the arithmetic is double or single precision, the CIC interpolator is implemented as a simple FIR interpolator with a boxcar response. A true CIC interpolator can only operate with fixed-point signals. The CIC filter is emulated with an FIR filter so that you can run simulations with floating-point data.


The following diagram represents the DUC arithmetic with single or double-precision, floating-point inputs.



The following block diagram represents the DUC arithmetic with signed fixed-point inputs.


# dsp.DigitalUpConverter

---



- WL is the word length of the input, and FL is the fraction length of the input.
- The output of each filter is cast to the data type specified in the **FiltersOutputDataType** and **CustomFiltersOutputDataType** properties. The casting of the CIC output occurs after the scaling factor is applied.
- The oscillator output is cast to a word length equal to the **FiltersOutputDataType** word length plus one. The fraction length is equal to the **FiltersOutputDataType** word length minus one.
- The scaling at the output of the CIC interpolator consists of coarse- and fine-gain adjustments. The coarse gain is achieved using the `reinterprecast` function on the CIC interpolator output. The fine gain is achieved using full-precision multiplication.

The following figure depicts the coarse- and fine-gain operations.



If the normalization gain is  $G$ , (where  $0 < G \leq 1$ ), then:

- $WLCic$  is the word length of the CIC interpolator output and  $FLCic$  is the fraction length of the CIC interpolator output
- $F1 = \text{abs}(\text{nextpow2}(G))$ , indicating the part of  $G$  achieved using bit shifts (coarse gain)
- $F2 =$  fraction length specified by the **FiltersOutputDataType** and **CustomFiltersOutputDataType** properties
- $fg = \text{fi}((2^{F1}) * G, \text{true}, 16)$ , indicating that the remaining gain cannot be achieved with a bit shift (fine gain)

`h = dsp.DigitalUpConverter('PropertyName', 'PropertyValue')` returns a DUC object, `h`, with each specified property set to the specified value. You can specify additional name-value pair arguments in any order as `(Name1, Value1, ..., NameN, ValueN)`.

## Properties

### SampleRate

Sample rate of input signal

Set this property to a positive scalar. The value of this property multiplied by the total interpolation factor must be greater than

or equal to twice the value of the `CenterFrequency` property. The default is `30e6`.

## **InterpolationFactor**

Set this property to a positive, integer scalar, or to a 1-by-2 or 1-by-3 vector of positive integers. When you set this property to a scalar the object automatically chooses the interpolation factors for each of the three filtering stages. The scalar value you specify cannot be a prime number. When you set this property to a 1-by-2 vector, the object bypasses the first filter stage and sets the interpolation factor of the second and third filtering stages to the values in the first and second vector elements respectively. When you set the `FilterSpecification` property to `Design parameters`, both elements of the `InterpolationFactor` vector must be greater than one. When you set the `FilterSpecification` property to `Coefficients`, the second element of the `InterpolationFactor` vector must be greater than 1. When you set this property to a 1-by-3 vector, the  $i^{\text{th}}$  element of the vector specifies the interpolation factor for the  $i^{\text{th}}$  filtering stage. When you set the `FilterSpecification` property to `Design parameters`, the second and third elements of the `InterpolationFactor` vector must be greater than one and the first element must be 1 or 2. When you set the `FilterSpecification` property to `Coefficients`, the third element of the `InterpolationFactor` vector must be greater than 1. When you set the `InterpolationFactor` property to `Coefficients`, you must set the `InterpolationFactor` property to a 1-by-3 or 1-by-2 vector . The default is 100.

## **FilterSpecification**

Set the filter specification as one of `Design parameters` | `Coefficients`. The default is `Design parameters`. The DUC object performs interpolation using a cascade of three interpolation filters. The third filter stage is always a CIC interpolator. When you set this property to `Design parameters`, the object designs the cascade of interpolation filters internally, according to a set of parameters that you specify using the

filter-related object properties. In this case, the first and second stages of the cascade consist of a halfband or lowpass FIR interpolator, and a CIC compensator respectively. When you set this property to `Coefficients`, you specify an arbitrary set of filter coefficients for the first and second stages using the `FirstFilterCoefficients`, and `SecondFilterCoefficients` properties respectively. You specify the number of CIC sections using the `NumCICSections` property. In all cases, the first filter stage can be bypassed by setting the `InterpolationFactor` property appropriately.

When the input data type is double or single the object implements an  $N$ -section CIC interpolation filter as an FIR filter with a response that corresponds to a cascade of  $N$  boxcar filters. A true CIC filter with actual comb and integrator sections is implemented when the input data is of a fixed point type.

### **MinimumOrderDesign**

Minimum order filter design.

When you set this property to true the object designs filters with the minimum order that meets the passband ripple, stopband attenuation, passband frequency, and stopband frequency specifications that you set using the `PassbandRipple`, `StopbandAttenuation`, `Bandwidth`, `StopbandFrequencySource`, and `StopbandFrequency` properties. When you set this property to false, the object designs filters with orders that you specify in the `FirstFilterOrder`, `SecondFilterOrder`, and `NumCICSections` properties. The filter designs meet the passband and stopband frequency specifications that you set using the `Bandwidth`, `StopbandFrequencySource`, and `StopbandFrequency` properties. This property applies when you set the `FilterSpecification` property to `Design` parameters. The default is true.

### **FirstFilterCoefficients**

Coefficients of first filter stage.

Set this property to a double precision row vector of real coefficients that correspond to an FIR filter. When you set the `InterpolationFactor` property to a 1-by-2 vector, the object ignores the value of the `FirstFilterCoefficients` property because the first filter stage is bypassed. This property applies when you set the `FilterSpecification` property to `Coefficients`. The default is 1.

## **SecondFilterOrder**

Order of CIC compensation filter stage

Set this property to a positive, integer scalar. This property applies when you set the `FilterSpecification` property to `Design` parameters and the `MinimumOrderDesign` property to `false`. The default is 12.

## **SecondFilterCoefficients**

Coefficients of second filter stage.

Set this property to a double precision row vector of real coefficients that correspond to an FIR filter. Usually, the response of this filter should be that of a CIC compensator since a CIC interpolation filter follows the second filter stage. This property applies when you set the `FilterSpecification` property to `Coefficients`. The default is 1.

## **FirstFilterOrder**

Order of first filter stage

Set this property to a positive, integer, even scalar. When you set the `InterpolationFactor` property to a 1-by-2 vector, the object ignores the `FirstFilterOrder` property because the first filter stage is bypassed. This property applies when you set the `FilterSpecification` property to `Design` parameters and the `MinimumOrderDesign` property to `false`. The default is 10.

## **NumCICSections**

Number of sections of CIC interpolator

Set this property to a positive, integer scalar. This property applies when you set the `FilterSpecification` property to `Design` parameters and the `MinimumOrderDesign` property to `false`, or when you set the `FilterSpecification` property to `Coefficients`. The default is 3.

## **Bandwidth**

Two sided bandwidth of input signal in Hertz .

Set this property to a positive, integer scalar. The object sets the passband frequency of the cascade of filters to one-half of the value that you specify in the `Bandwidth` property. This property applies when you set the `FilterSpecification` property to `Design` parameters. The default is 200e3 Hertz.

## **StopbandFrequencySource**

Source of stopband frequency.

Specify the source of the stopband frequency as one of `Auto` | `Property`. The default is `Auto`. When you set this property to `Auto`, the object places the cutoff frequency of the cascade filter response at approximately  $F_c = \text{SampleRate}/2$  Hertz, and computes the stopband frequency as  $F_{stop} = F_c + TW/2$ .  $TW$  is the transition bandwidth of the cascade response, computed as  $2*(F_c - F_p)$ , and the passband frequency,  $F_p$ , equals `Bandwidth/2`. This property applies when you set the `FilterSpecification` property to `Design` parameters.

## **StopbandFrequency**

Stopband frequency in Hertz

Set this property to a double precision positive scalar. This property applies when you set the `FilterSpecification` property to `Design` parameters and the `StopbandFrequencySource` property to `Property`. The default is 150e3 Hertz.

## **PassbandRipple**

Passband ripple of cascade response in dB.

Set this property to a double precision, positive scalar. When you set the `MinimumOrderDesign` property to true, the object designs the filters so that the cascade response meets the passband ripple that you specify in the `PassbandRipple` property. This property applies when you set the `FilterSpecification` property to `Design` parameters and the `MinimumOrderDesign` property to true. The default is 0.1 dB.

## **StopbandAttenuation**

Stopband attenuation of cascade response in dB.

Set this property to a double precision, positive scalar. When you set the `MinimumOrderDesign` property to true, the object designs the filters so that the cascade response meets the stopband attenuation that you specify in the `StopbandAttenuation` property. This property applies when you set the `FilterSpecification` property to `Design` parameters and the `MinimumOrderDesign` property to true. The default is 60 dB.

## **Oscillator**

Type of oscillator.

Specify the oscillator as one of `Sine wave` | `NCO`. The default is `Sine wave`. When you set this property to `Sine wave`, the object frequency up converts the output of the interpolation filter cascade using a complex exponential signal obtained from samples of a sinusoidal trigonometric function. When you set this property to `NCO` the object performs frequency up conversion with a complex exponential obtained using a numerically controlled oscillator (NCO).

## **CenterFrequency**

Center frequency of output signal in Hertz .

Specify this property as a double precision, positive scalar. The value of this property must be less than or equal to half the product of the `SampleRate` property times the total interpolation

factor. The object up converts the input signal so that the output spectrum centers at the frequency you specify in the `CenterFrequency` property. The default is 14e6 Hertz.

## **NumAccumulatorBits**

Number of NCO accumulator bits

Specify this property as an integer scalar in the range [1 128]. This property applies when you set the `Oscillator` property to `NCO`. The default is 16.

See also `dsp.NCO`.

## **NumQuantizedAccumulatorBits**

Number of NCO quantized accumulator bits.

Specify this property as an integer scalar in the range [1 128]. The value you specify for this property must be less than the value you specify in the `NumAccumulatorBits` property. This property applies when you set the `Oscillator` property to `NCO`. The default is 12.

See also `dsp.NCO`.

## **Dither**

Dither control for NCO .

When you set this property to true, the object uses the number of dither bits specified in the `NumDitherBits` property when applying dither to the NCO signal. This property applies when you set the `Oscillator` property to `NCO`. The default is true.

See also `dsp.NCO`.

## **NumDitherBits**

Number of NCO dither bits.

Specify this property as an integer scalar smaller than the number of accumulator bits that you specify in the `NumAccumulatorBits`

property. This property applies when you set the `Oscillator` property to `NCO` and the `Dither` property to `true`. The default is `4`.

See also `dsp.NCO`.

## Fixed-Point Properties

### FirstFilterCoefficientsDataType

Data type of first filter coefficients

Specify first filter coefficients data type as `Same as input|Custom`. The default is `Same as input`. This property applies when you set the `FilterSpecification` property to `Coefficients`.

### CustomFirstFilterCoefficientsDataType

Fixed-point data type of first filter coefficients

Specify the first filter coefficients fixed-point type as a scaled `numerictype` object with a `Signedness` of `Auto`. This property applies when you set the `FirstFilterCoefficientsDataType` property to `Custom`. The default is `numerictype([],16,15)`.

### SecondFilterCoefficientsDataType

Data type of second filter coefficients

Specify the second filter coefficients data type as `Same as input|Custom`. The default is `Same as input`. This property applies when you set the `FilterSpecification` property to `Coefficients`.

### CustomSecondFilterCoefficientsDataType

Fixed-point data type of second filter coefficients

Specify the second filter coefficients fixed-point type as a scaled `numerictype` object with a `Signedness` of `Auto`. This property applies when you set the `SecondFilterCoefficientsDataType` property to `Custom`. The default is `numerictype([],16,15)`.

## FiltersOutputDataType

Data type of output of each filter stage

Specify the data type at the output of the first (if it has not been bypassed), second, and third filter stages as one of `Same as input` | `Custom`. The default is `Same as input`. The object casts the data at the output of each filter stage according to the value you set in this property. For the CIC stage, the casting is done after the signal has been scaled by the normalization factor.

## CustomFiltersOutputDataType

Fixed-point data type of output of each filter stage

Specify the filters output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `FiltersOutputDataType` property to `Custom`. The default is `numericType([], 16, 15)`.

## OutputDataType

Data type of output

Specify the data type of output as `Same as input` | `Custom`. The default is `Same as input`.

## CustomOutputDataType

Fixed-point data type of output

Specify the output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `OutputDataType` property to `Custom`. The default is `numericType([], 16, 15)`.

## Methods

<code>clone</code>	Create digital up converter object with same property values
<code>fvtool</code>	Visualize response of filter cascade

# dsp.DigitalUpConverter

---

<code>getFilterOrders</code>	Get orders of interpolation filters
<code>getFilters</code>	Get handles to interpolation filter objects
<code>getInterpolationFactors</code>	Get interpolation factors of each filter stage
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>groupDelay</code>	Group delay of filter cascade
<code>isLocked</code>	Locked status for input attributes and non-tunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>step</code>	Process inputs using the object algorithm
<code>visualizeFilterStages</code>	Display response of filter stages

## Examples

Create a digital up converter object that up samples a 1 KHz sinusoidal signal by a factor of 20 and up converts it to 50 KHz.

```
% Create a sine wave generator to obtain the 1 KHz sinusoidal signal
% with a sample rate of 6 KHz.
Fs = 6e3; % Sample rate
hSig = dsp.SineWave('Frequency',1000,'SampleRate', Fs,'SamplesPerFrame',100);
x = step(hSig); % generate signal

% Create a DUC object. Use minimum order filter designs and set the
% passband ripple to 0.2 dB and the stopband attenuation to 55 dB. Set
% the double sided signal bandwidth to 2 KHz.
hDUC = dsp.DigitalUpConverter(...
    'InterpolationFactor', 20,...
    'SampleRate', Fs,...
    'Bandwidth', 2e3,...
```

```
'StopbandAttenuation', 55,...
'PassbandRipple', 0.2,...
'CenterFrequency', 50e3);

% Create a spectrum estimator to visualize the signal spectrum before
% and after up converting.
hSEst = spectrum.welch; hSEst.SegmentLength = length(x)/10;
hOpts=psdopts(hSEst);
set(hOpts, 'Fs', Fs, 'SpectrumType', 'twosided', 'CenterDC', true);
figure; psd(hSEst,x,hOpts)
title('Spectrum of baseband signal x')

% Up convert the signal and visualize the spectrum
xUp = step(hDUC,x); % up convert
hOpts.Fs = Fs*20; hSEst.SegmentLength = length(xUp)/10;
figure; psd(hSEst,xUp,hOpts)
title('Spectrum of up converted signal xUp')

% Visualize the response of the interpolation filters
visualizeFilterStages(hDUC)
```

For additional examples using this System object, see the following demos:

- Digital Up and Down Conversion for Family Radio Service
- Design and Analysis of a Digital Down Converter

## See Also

`dsp.DigitalDownConverter`

# dsp.DigitalUpConverter.clone

---

**Purpose** Create digital up converter object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a `DigitalUpConverter System` object, `C`, with the same property values as `H`.

The clone method creates a new unlocked object with uninitialized states.

**Purpose**

Visualize response of filter cascade

**Syntax**

```
fvtool(H)
fvtool(H,...,'Arithmetic',ARITH,...)
fvtool(H,..., PROP1, VALUE1,PROP2,VALUE2)
```

**Description**

fvtool(H) plots the magnitude response of the cascade of filters. By default, the object plots the cascade response up to the second CIC null frequency (or to the first when only one CIC null exists). When you set the FilterSpecification property to Design parameters the method plots a mask based on the filter specifications.

fvtool(H,...,'Arithmetic',ARITH,...) specifies the arithmetic of the filter cascade. You set input ARITH to double, single, or fixed-point. When object H is in an unlocked state you must specify the arithmetic. When object H is in a locked state the arithmetic input is ignored.

fvtool(H,..., PROP1, VALUE1,PROP2,VALUE2) launches FVTool and sets the specified FVTool properties to the specified values.

# dsp.DigitalUpConverter.getFilters

---

**Purpose** Get handles to interpolation filter objects

**Syntax** `S = getFilters(H)`  
`getFilters(H, 'Arithmetic', ARITH)`

**Description** `S = getFilters(H)` returns a structure, `S`, with copies of the filter System objects and the CIC normalization factor that form the interpolation filter cascade. The `FirstFilterStage` structure field is empty if the first filter stage has been bypassed. The CIC normalization factor equals the inverse of the CIC filter gain. In some cases, this gain includes a correction factor to ensure that the cascade response meets the ripple specifications.

`getFilters(H, 'Arithmetic', ARITH)` specifies the arithmetic of the filter stages. You set `ARITH` to `double`, `single`, or `fixed-point`. When object `H` is in an unlocked state, you must specify the arithmetic input. When object `H` is in a locked state, the arithmetic input is ignored.

When `H` is in an unlocked state, and you specify the arithmetic as `fixed-point`, the `getFilters` method returns filter System objects. The custom coefficient data type properties of these System objects are set to the values that the `dsp.DigitalUpConverter` System object uses to process data when you call the `step` method. All other fixed-point properties are set to their default values.

When `H` is in a locked state, and the input to the `step` method is of a fixed-point data type, the `getFilters` method returns filter System objects. All fixed-point properties of these System objects are set to the exact values that the `dsp.DigitalUpConverter` System object uses to process the data.

**Purpose** Get orders of interpolation filters

**Syntax** `S = getFilterOrders(H)`

**Description** `S = getFilterOrders(H)` returns a structure, `S`, that contains the orders of the interpolation filter stages. The `FirstFilterOrder` structure field will be empty if the first filter stage has been bypassed.

# **dsp.DigitalUpConverter.getInterpolationFactors**

---

**Purpose**                    Get interpolation factors of each filter stage

**Syntax**                    `M = getInterpolationFactors(H)`

**Description**              `M = getInterpolationFactors(H)` returns a vector, `M`, with the interpolation factors of each filter stage. If the first filter stage is bypassed, then `M` is a 1-by-2 vector containing the interpolation factors of the second and third stages in the first and second elements respectively. If the first filter stage is not bypassed then `M` is a 1-by-3 vector containing the interpolation factors of the first, second and third filter stages.

**Purpose** Number of expected inputs to step method

**Syntax** N = getNumInputs(H)

**Description** N = getNumInputs(H) returns the number of expected inputs, N, to the step method

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.DigitalUpConverter.getNumOutputs**

---

**Purpose**                Number of outputs of step method

**Syntax**                `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Group delay of filter cascade

**Syntax**  
`D = groupDelay(H,N)`  
`[D,F] = groupDelay(H,N)`

**Description**  
`D = groupDelay(H,N)` returns a vector of group delays, `D`, evaluated at `N` frequency points equally spaced around the upper half of the unit circle. If you don't specify `N`, it defaults to 8192.  
`[D,F] = groupDelay(H,N)` returns a vector, `F`, of frequencies at which the group delay has been computed.

# **dsp.DigitalUpConverter.isLocked**

---

**Purpose** Locked status for input attributes and non-tunable properties

**Syntax** `Y = isLocked(H)`

**Description** `Y = isLocked(H)` returns the locked state, `Y`, of the `DigitalUpConverter` object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections. This method lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

# dsp.DigitalUpConverter.step

---

**Purpose** Process inputs using the object algorithm

**Syntax**  $Y = \text{step}(H,X)$

**Description**  $Y = \text{step}(H,X)$  takes a real or complex input column vector  $X$  and outputs an up sampled and frequency up converted signal  $Y$ .  $X$  can be of data type double, single, signed integer, or signed fixed point (fi objects). The length of  $Y$  is equal to the length of  $X$  multiplied by the `InterpolationFactor`. When the data type of  $X$  is double or single precision, the data type of  $Y$  is the same as that of  $X$ . When the data type of  $X$  is of a fixed point type, the data type of  $Y$  is defined by the `OutputDataType` property.

**Purpose**

Display response of filter stages

**Syntax**

```
visualizeFilterStages(H)  
visualizeFilterStages(H,'Arithmetic',ARITH)  
hfvt = visualizeFilterStages(H)
```

**Description**

`visualizeFilterStages(H)` plots the magnitude response of the filter stages and of the cascade response. When the `FilterSpecification` property is set to `Design` parameters the method plots a mask based on the filter specifications. By default, the object plots the response of the filters up to the second CIC null frequency (or to the first when only one CIC null exists).

`visualizeFilterStages(H,'Arithmetic',ARITH)` specifies the arithmetic of the filter stages. You set input `ARITH` to `'double'`, `'single'`, or `'fixed-point'`. When object `H` is in an unlocked state you must specify the arithmetic. When object `H` is in a locked state the arithmetic input is ignored.

`hfvt = visualizeFilterStages(H)` returns the handle to the `FVTool` object.

# dsp.DyadicAnalysisFilterBank

---

**Purpose** Dyadic analysis filter bank

**Description** The `DyadicAnalysisFilterBank` object uses a series of highpass and lowpass FIR filters to provide approximate octave band frequency decompositions of the input. Each filter output is downsampled by a factor of two. With the appropriate analysis filters and tree structure, the dyadic analysis filter bank is a discrete wavelet transform (DWT) or discrete wavelet packet transform (DWPT).

To obtain approximate octave band frequency decompositions of the input:

- 1 Define and set up your dyadic analysis filter bank. See “Construction” on page 5-414.
- 2 Call `step` to get the octave half band frequency decompositions of the input according to the properties of `dsp.DyadicAnalysisFilterBank`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.DyadicAnalysisFilterBank` constructs a dyadic analysis filter bank object, `H`, that computes the level-two discrete wavelet transform (DWT) of a column vector input. For a 2-D matrix input, the object transforms the columns using the Daubechies third-order extremal phase wavelet. The length of the input along the first dimension must be a multiple of 4.

`H = dsp.DyadicAnalysisFilterBank('PropertyName',PropertyValue, ...)` returns a dyadic analysis filter bank object, `H`, with each property set to the specified value.

**Properties** **Filter**

Type of filter used in subband decomposition

Specify the type of filter used to determine the high and lowpass FIR filters in the dyadic analysis filter bank as `Custom`, `Haar`, `Daubechies`, `Symlets`, `Coiflets`, `Biorthogonal`, `Reverse`

Biorthogonal, or Discrete Meyer. All property values except Custom require Wavelet Toolbox software. If the value of this property is Custom, the filter coefficients are specified by the values of the CustomLowpassFilter and CustomHighpassFilter properties. Otherwise, the dyadic analysis filter bank object uses the Wavelet Toolbox function `wfilters` to construct the filters. The following table lists supported wavelet filters and example syntax to construct the filters:

Filter	Example Setting	Syntax for Analysis Filters
Haar	N/A	<code>[Lo_D,Hi_D]=wfilters('haar');</code>
Daubechies extremal phase	<code>WaveletOrder=3;</code>	<code>[Lo_D,Hi_D]=wfilters('db3');</code>
Symlets (Daubechies least-asymmetric)	<code>WaveletOrder=4;</code>	<code>[Lo_D,Hi_D]=wfilters('sym4');</code>
Coiflets	<code>WaveletOrder=1;</code>	<code>[Lo_D,Hi_D]=wfilters('coif1');</code>
Biorthogonal	<code>FilterOrder='[3/1]';</code>	<code>[Lo_D,Hi_D,Lo_R,Hi_R]=... wfilters('bior3.1');</code>
Reverse biorthogonal	<code>FilterOrder='[3/1]';</code>	<code>[Lo_D,Hi_D,Lo_R,Hi_R]=... wfilters('rbior3.1');</code>
Discrete Meyer	N/A	<code>[Lo_D,Hi_D]=wfilters('dmey');</code>

### CustomLowpassFilter

Lowpass FIR filter coefficients

Specify a vector of lowpass FIR filter coefficients, in powers of  $z^{-1}$ . Use a half-band filter that passes the frequency band stopped by the filter specified in the CustomHighpassFilter property. This property applies when you set the Filter property to Custom. The default specifies a Daubechies third-order extremal phase scaling (lowpass) filter.

### CustomHighpassFilter

# dsp.DyadicAnalysisFilterBank

---

Highpass FIR filter coefficients

Specify a vector of highpass FIR filter coefficients, in powers of  $z^{-1}$ . Use a half-band filter that passes the frequency band stopped by the filter specified in the `CustomLowpassFilter` property. This property applies when you set the `Filter` property to `Custom`. The default specifies a Daubechies 3rd-order extremal phase wavelet (highpass) filter.

## WaveletOrder

Order for orthogonal wavelets

Specify the order of the wavelet selected in the `Filter` property. This property applies when you set the `Filter` property to an orthogonal wavelet: `Daubechies` (Daubechies extremal phase), `Symlets` (Daubechies least-asymmetric), or `Coiflets`. The default is 2.

## FilterOrder

Analysis and synthesis filter orders for biorthogonal filters

Specify the order of the analysis and synthesis filter orders for biorthogonal filter banks as 1 / 1, 1 / 3, 1 / 5, 2 / 2, 2 / 4, 2 / 6, 2 / 8, 3 / 1, 3 / 3, 3 / 5, 3 / 7, 3 / 9, 4 / 4, or 5 / 5, 6 / 8. Unlike orthogonal wavelets, biorthogonal wavelets require different filters for the analysis (decomposition) and synthesis (reconstruction) of an input. The first number indicates the order of the synthesis (reconstruction) filter. The second number indicates the order of the analysis (decomposition) filter. This property applies when you set the `Filter` property to `Biorthogonal` or `Reverse Biorthogonal`. The default is 1 / 1.

## NumLevels

Number of filter bank levels used in analysis (decomposition)

Specify the number of filter bank analysis levels a positive integer. A level- $N$  asymmetric structure produces  $N+1$  output subbands. A level- $N$  symmetric structure produces  $2^N$  output subbands. The

default is 2. The size of the input along the first dimension must be a multiple of  $2^N$ , where  $N$  is the number of levels.

## TreeStructure

Structure of filter bank

Specify the structure of the filter bank as `Asymmetric` or `Symmetric`. The asymmetric structure decomposes only the lowpass filter output from each level. The symmetric structure decomposes the highpass and lowpass filter outputs from each level. If the analysis filters are scaling (lowpass) and wavelet (highpass) filters, the asymmetric structure is the discrete wavelet transform, while the symmetric structure is the discrete wavelet packet transform.

When this property is `Symmetric`, the output has  $2^N$  subbands each of size  $M/2^N$ . In this case,  $M$  is the length of the input along the first dimension and  $N$  is the value of the `NumLevels` property. When this property is `Asymmetric`, the output has  $N+1$  subbands. The following equation gives the length of the output in the  $k$ th subband in the asymmetric case:

$$M_k = \begin{cases} \frac{M}{2^k} & 1 \leq k \leq N \\ \frac{M}{2^N} & k = N + 1 \end{cases}$$

The default is `Asymmetric`.

## Methods

<code>clone</code>	Create dyadic analysis filter bank object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method

# dsp.DyadicAnalysisFilterBank

---

isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
reset	Reset filter states
step	Decompose input with dyadic filter bank

## Examples

Denoise square wave input using dyadic analysis and synthesis filter banks:

```
t = 0:.0001:.0511;
x= square(2*pi*30*t);
xn = x' + 0.08*randn(length(x),1);
hdydan1 = dsp.DyadicAnalysisFilterBank;

% The filter coefficients correspond to a 'haar' wavelet.
hdydan1.CustomLowpassFilter = [1/sqrt(2) 1/sqrt(2)];
hdydan1.CustomHighpassFilter = [-1/sqrt(2) 1/sqrt(2)];
hdydsyn = dsp.DyadicSynthesisFilterBank;
hdydsyn.CustomLowpassFilter = [1/sqrt(2) 1/sqrt(2)];
hdydsyn.CustomHighpassFilter = [1/sqrt(2) -1/sqrt(2)];

C = step(hdydan1, xn);

% Subband outputs
C1 = C(1:256); C2 = C(257:384); C3 = C(385:512);

% Set higher frequency coefficients to zero
% to remove the noise.
x_den = step(hdydsyn, [zeros(length(C1),1);...
zeros(length(C2),1);C3]);

subplot(2,1,1), plot(xn); title('Original noisy Signal');
subplot(2,1,2), plot(x_den); title('Denoised Signal');
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Dyadic Analysis Filter Bank block reference page. The object properties correspond to the block parameters, except:

The dyadic analysis filter bank object always concatenates the subbands into a single column vector for a column vector input, or into the columns of a matrix for a matrix input. This behavior corresponds to the block's behavior when you set the **Output** parameter to `Single` port.

## See Also

`dsp.DyadicSynthesisFilterBank` | `dsp.SubbandAnalysisFilter`

# **dsp.DyadicAnalysisFilterBank.clone**

---

**Purpose** Create dyadic analysis filter bank object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a dyadic analysis filter bank object, `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with uninitialized states.

# **dsp.DyadicAnalysisFilterBank.getNumInputs**

---

**Purpose**                      Number of expected inputs to step method

**Syntax**                      `N = getNumInputs(H)`

**Description**                `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.DyadicAnalysisFilterBank.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# dsp.DyadicAnalysisFilterBank.isLocked

---

<b>Purpose</b>	Locked status for input attributes and nontunable properties
<b>Syntax</b>	<code>isLocked(H)</code>
<b>Description</b>	<p><code>isLocked(H)</code> returns the locked state of the dyadic analysis filter bank object.</p> <p>The <code>isLocked</code> method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the <code>step</code> method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the <code>isLocked</code> method returns a true value.</p>

# dsp.DyadicAnalysisFilterBank.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

**Purpose** Reset filter states

**Syntax** reset(H)

**Description** reset(H) resets the filter states of the dyadic analysis filter bank object, H, to their initial values of zero. After the step method applies the dyadic analysis filter bank to nonzero input data, the filter states may change. Invoking the step method again without first invoking the reset method may produce different outputs for an identical input.

Example of resetting filter states:

```
X = [1 1 7 9 2 8 8 6]';  
H = dsp.DyadicAnalysisFilterBank('NumLevels',1);  
% Filter states are zero  
y = step(H,X);  
% Invoke step method again without resetting states  
y1 = step(H,X);  
isequal(y,y1) % Returns 0  
reset(H); % Reset filter states to zero  
y2 = step(H,X);  
isequal(y,y2) % Returns 1
```

# dsp.DyadicAnalysisFilterBank.step

---

**Purpose** Decompose input with dyadic filter bank

**Syntax**  $Y = \text{step}(H,X)$

**Description**  $Y = \text{step}(H,X)$  computes the subband decomposition of the input  $X$  and outputs the dyadic subband decomposition in  $Y$  as a single concatenated column vector or matrix of coefficients. Each column of  $X$  is treated as an independent input, and the number of rows of  $X$  must be a multiple of  $2^N$ , where  $N$  is the value of the NumLevels property. The elements of  $Y$  are ordered with the highest frequency subband first followed by subbands in decreasing frequency

**Examples** Subband ordering for level-two asymmetric tree structure:

```
t = 0:.001:1.023;
% Sampling frequency 1 kHz input length 1024
x = square(2*pi*30*t);
xn = x' + 0.08*randn(length(x),1);
% Default asymmetric structure with
% Daubechies order 3 extremal phase wavelet
H = dsp.DyadicAnalysisFilterBank;
Y = step(H,xn);
% Level 2 yields 3 subbands (two detail-one approximation)
% Nyquist frequency is 500 Hz
D1 = Y(1:512); % subband approx. [250, 500] Hz
D2 = Y(513:768); % subband approx. [125, 250] Hz
Approx = Y(769:1024); % subband approx. [0,125] Hz
```

---

Subband ordering for symmetric tree structure:

```
t = 0:.001:1.023;
% Sampling frequency 1 kHz input length 1024
x = square(2*pi*30*t);
xn = x' + 0.08*randn(length(x),1); % symmetric structure with
% Daubechies order 3 extremal phase wavelet
```

```
H = dsp.DyadicAnalysisFilterBank('TreeStructure',...  
    'Symmetric');  
Y = step(H,xn);  
D1 = Y(1:256); % subband approx. [375,500] Hz  
D2 = Y(257:512); % subband approx. [250,375] Hz  
D3 = Y(513:768); % subband approx. [125,250] Hz  
Approx = Y(769:1024); % subband approx. [0, 125] Hz
```

# dsp.DyadicSynthesisFilterBank

---

**Purpose** Reconstruct signals from subbands

**Description** The `DyadicSynthesisFilterBank` object reconstructs signals from subbands with smaller bandwidths and lower sample rates. The filter bank uses a series of highpass and lowpass FIR filters to repeatedly reconstruct the signal.

To reconstruct signals from subbands with smaller bandwidths and lower sample rates:

- 1 Define and set up your synthesis filter bank. See “Construction” on page 5-428.
- 2 Call `step` to reconstruct the signal according to the properties of `dsp.DyadicSynthesisFilterBank`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.DyadicSynthesisFilterBank` returns a synthesis filter bank, `H`, that reconstructs a signal from its subbands with smaller bandwidths and smaller sample rates.

`H = dsp.DyadicSynthesisFilterBank('PropertyName',PropertyValue,...)` returns a synthesis filter bank, `H`, with each specified property set to the specified value.

**Properties** **Filter**

Type of filter used in filter bank

Specify the type of filter used to determine the highpass and lowpass FIR filters in the filter bank as one of `Custom`, `Haar`, `Daubechies`, `Symlets`, `Coiflets`, `Biorthogonal`, `Reverse Biorthogonal`, or `Discrete Meyer`. If you set this property to `Custom`, the `CustomLowpassFilter` and `CustomHighpassFilter` properties specify the filter coefficients. Otherwise, the object uses the Wavelet Toolbox `wfilters` function to construct the filters. Depending on the filter, the `WaveletOrder` or `FilterOrder`

property might apply. For a list of the supported wavelets, see the following table.

<b>Filter</b>	<b>Sample Setting for Related Filter Specification Properties</b>	<b>Corresponding Wavelet Toolbox Function Syntax</b>
Haar	None	wfilters('haar')
Daubechies	H.WaveletOrder = 4	wfilters('db4')
Symlets	H.WaveletOrder = 3	wfilters('sym3')
Coiflets	H.WaveletOrder = 1	wfilters('coif1')
Biorthogonal	H.FilterOrder = '[3/1]'	wfilters('bior3.1')
Reverse Biorthogonal	H.FilterOrder = '[3/1]'	wfilters('rbior3.1')
Discrete Meyer	None	wfilters('dmey')

In order to automatically design wavelet-based filters, install the Wavelet Toolbox product. Otherwise, use the CustomLowpassFilter and CustomHighpassFilter properties to specify lowpass and highpass FIR filters.

## CustomLowpassFilter

Lowpass FIR filter coefficients

Specify a vector of lowpass FIR filter coefficients, in descending powers of  $z$ . Use a half-band filter that passes the frequency band stopped by the filter specified in the CustomHighpassFilter property. This property applies only when you set the Filter property to Custom. To perfectly reconstruct a signal decomposed by the DyadicAnalysisFilterBank, design the filters in the

synthesis filter bank to perfectly reconstruct the outputs of the analysis filter bank. Otherwise, the reconstruction is imperfect. The default values of this property specify a perfect reconstruction filter for the default settings of the analysis filter bank (based on a third-order Daubechies wavelet).

## CustomHighpassFilter

Highpass FIR filter coefficients

Specify a vector of highpass FIR filter coefficients, in descending powers of  $z$ . Use a half-band filter that passes the frequency band stopped by the filter specified in the `CustomLowpassFilter` property. This property applies only when you set the `Filter` property to `Custom`. To perfectly reconstruct a signal decomposed by the `DyadicAnalysisFilterBank`, design the filters in the synthesis filter bank to perfectly reconstruct the outputs of the analysis filter bank. Otherwise, the reconstruction is imperfect. The default values of this property specify a perfect reconstruction filter for the default settings of the analysis filter bank (based on a third-order Daubechies wavelet).

## WaveletOrder

Wavelet order

Specify the order of the wavelet selected in the `Filter` property. This property applies only when you set the `Filter` property to `Daubechies`, `Symlets` or `Coiflets`. The default is 2.

## FilterOrder

Wavelet order for synthesis filter stage

Specify the order of the wavelet for the synthesis filter stage as:

- First order: `'[1/1]'`, `'[1/3]'`, or `'[1/5]'`.
- Second order: `'[2/2]'`, `'[2/4]'`, `'[2/6]'`, or `'[2/8]'`.
- Third order: `'[3/1]'`, `'[3/3]'`, `'[3/5]'`, `'[3/7]'`, or `'[3/9]'`.
- Fourth order: `'[4/4]'`.

- Fifth order: '[5/5]'.
- Sixth order: '[6/8]'.

This property applies only when you set the `Filter` property to `Biorthogonal` or `Reverse Biorthogonal`. The default is '[1/1]'.

## NumLevels

Number of filter bank levels

Specify the number of filter bank levels as a scalar integer. An  $N$ -level asymmetric structure has  $N + 1$  input subbands, and an  $N$ -level symmetric structure has  $2^N$  input subbands. The default is 2.

rg

## TreeStructure

Structure of filter bank

Specify the structure of the filter bank as `Asymmetric` or `Symmetric`. In the asymmetric structure, the low-frequency subband input to each level is the output of the previous level, while the high-frequency subband input to each level is an input to the filter bank. In the symmetric structure, both the low- and high-frequency subband inputs to each level are outputs from the previous level. The default is `Asymmetric`.

## Methods

<code>clone</code>	Create synthesis filter bank object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of the step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties

# dsp.DyadicSynthesisFilterBank

---

release	Allow property value and input characteristics changes
reset	Reset internal states of dyadic synthesis filter bank object
step	Reconstruct signal from high- and low-frequency subbands

## Examples

Remove noise from a signal using filter banks:

```
t = 0:.0001:.0511;
x = square(2*pi*30*t);
xn = x' + 0.08*randn(length(x),1);
hdydanl = dsp.DyadicAnalysisFilterBank;

% The filter coefficients correspond to a 'haar' wavelet.
hdydanl.CustomLowpassFilter = [1/sqrt(2) 1/sqrt(2)];
hdydanl.CustomHighpassFilter = [-1/sqrt(2) 1/sqrt(2)];
hdydsyn = dsp.DyadicSynthesisFilterBank;
hdydsyn.CustomLowpassFilter = [1/sqrt(2) 1/sqrt(2)];
hdydsyn.CustomHighpassFilter = [1/sqrt(2) -1/sqrt(2)];

C = step(hdydanl, xn);

% Subband outputs
C1 = C(1:256); C2 = C(257:384); C3 = C(385:512);

% Set high-frequency coefficients to zero to remove noise.
x_den = step(hdydsyn, ...
    [zeros(length(C1),1); ...
    zeros(length(C2),1); ...
    C3]);

subplot(2,1,1), plot(xn); title('Original Noisy Signal');
subplot(2,1,2), plot(x_den); title('Denoised Signal');
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Dyadic Synthesis Filter Bank block reference page. The object properties correspond to the block parameters, except:

The object only receives data as a vector or matrix of concatenated subbands, as specified using the `step` method.

## See Also

`dsp.DyadicAnalysisFilterBank` | `dsp.SubbandSynthesisFilter`

# **dsp.DyadicSynthesisFilterBank.clone**

---

**Purpose** Create synthesis filter bank object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a `DyadicSynthesisFilterBank` object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with uninitialized states.

# **dsp.DyadicSynthesisFilterBank.getNumInputs**

---

**Purpose**                      Number of expected inputs to step method

**Syntax**                      `N = getNumInputs(H)`

**Description**                `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.DyadicSynthesisFilterBank.getNumOutputs**

---

**Purpose**            Number of outputs of the step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# dsp.DyadicSynthesisFilterBank.isLocked

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `DyadicSynthesisFilterBank` object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.DyadicSynthesisFilterBank.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

<b>Purpose</b>	Reset internal states of dyadic synthesis filter bank object
<b>Syntax</b>	<code>reset(H)</code>
<b>Description</b>	<code>reset(H)</code> sets the internal states of the dyadic synthesis filter bank object H to their initial values.

# dsp.DyadicSynthesisFilterBank.step

---

**Purpose** Reconstruct signal from high- and low-frequency subbands

**Syntax**  $X = \text{step}(H,S)$

**Description**  $X = \text{step}(H,S)$  reconstructs the concatenated subband input  $S$  to output  $X$ . Each column of input  $S$  contains the subbands for an independent signal. Upper rows contain the high-frequency subbands, and lower rows contain the low-frequency subbands. The number of rows of  $S$  must be a multiple of  $2^N$ , where  $N$  is the value of the NumLevels property.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

<b>Purpose</b>	Discrete Fourier transform
<b>Description</b>	<p>The FFT object computes the discrete Fourier transform (DFT) of an input. The object uses one or more of the following fast Fourier transform (FFT) algorithms depending on the complexity of the input and whether the output is in linear or bit-reversed order:</p> <ul style="list-style-type: none"><li>• Double-signal algorithm</li><li>• Half-length algorithm</li><li>• Radix-2 decimation-in-time (DIT) algorithm</li><li>• Radix-2 decimation-in-frequency (DIF) algorithm</li><li>• An algorithm chosen by FFTW [1], [2]</li></ul> <p>To compute the DFT of an input:</p> <ol style="list-style-type: none"><li><b>1</b> Define and set up your FFT object. See “Construction” on page 5-441.</li><li><b>2</b> Call <code>step</code> to compute the DFT of the input according to the properties of <code>dsp.FFT</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.FFT</code> returns a FFT object, <code>H</code>, that computes the DFT of an <math>N</math>-D array. For column vectors or multidimensional arrays, the FFT object computes the DFT along the first dimension. If the input is a row vector, the FFT object computes a row of single-sample DFTs and issues a warning.</p> <p><code>H = dsp.FFT('PropertyName',PropertyValue, ...)</code> returns a FFT object, <code>H</code>, with each property set to the specified value.</p>
<b>Properties</b>	<p><b>FFTImplementation</b></p> <p>FFT implementation</p>

Specify the implementation used for the FFT as one of `Auto` | `Radix-2` | `FFTW`. When you set this property to `Radix-2`, the FFT length must be a power of two.

## **BitReversedOutput**

Order of output elements relative to input elements

Designate order of output channel elements relative to order of input elements. Set this property to `true` to output the frequency indices in bit-reversed order. The default is `false`, which corresponds to a linear ordering of frequency indices.

## **Normalize**

Divide butterfly outputs by two

Set this property to `true` if the output of the FFT should be divided by the FFT length. This option is useful when you want the output of the FFT to stay in the same amplitude range as its input. This is particularly useful when working with fixed-point data types.

The default value of this property is `false` with no scaling.

## **FFTLengthSource**

Source of FFT length

Specify how to determine the FFT length as `Auto` or `Property`. When you set this property to `Auto`, the FFT length equals the number of rows of the input signal. The default is `Auto`.

## **FFTLength**

FFT length

Specify the FFT length. This property applies when you set the `FFTLengthSource` property to `Property`. The default is `64`.

This property must be a power of two when the input is a fixed-point data type, or when you set the `BitReversedOutput` property to `true`, or when you set the `FFTImplementation` property to `Radix-2`.

## Fixed-Point Properties

### RoundingMethod

Rounding method for fixed-point operations

Specify the rounding method as one of `Ceiling`, `Convergent`, `Floor`, `Nearest`, `Round`, `Simplest`, `Zero`. The default is `Floor`.

### OverflowAction

Overflow action for fixed-point operations

Specify the overflow action as `Wrap` or `Saturate`. The default is `Wrap`.

### SineTableDataType

Sine table word and fraction lengths

Specify the sine table data type as `Same word length as input` or `Custom`. The default is `Same word length as input`.

### CustomSineTableDataType

Sine table word and fraction lengths

Specify the sine table fixed-point type as an unscaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `SineTableDataType` property to `Custom`. The default is `numericType([],16)`.

### ProductDataType

Product word and fraction lengths

Specify the product data type as `Full precision`, `Same as input`, or `Custom`. The default is `Full precision`.

### CustomProductDataType

Product word and fraction lengths

Specify the product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when

you set the `ProductDataType` property to `Custom`. The default is `numerictype([],32,30)`.

## **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator data type as `Full` precision, `Same as input`, `Same as product`, or `Custom`. The default is `Full` precision.

## **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled `numerictype` object with a `Signedness` of `Auto`. This property applies when you set the `AccumulatorDataType` property to `Custom`. The default is `numerictype([],32,30)`.

## **OutputDataType**

Output word and fraction lengths

Specify the output data type as one of `Full` precision, `Same as input`, `Custom`. The default is `Full` precision.

## **CustomOutputDataType**

Output word and fraction lengths

Specify the output fixed-point type as a scaled `numerictype` object with a `Signedness` of `Auto`. This property applies when you set the `OutputDataType` property to `Custom`. The default is `numerictype([],16,15)`.

## **Methods**

<code>clone</code>	Create FFT object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method

getNumOutputs	Number of outputs of step method
isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
step	Discrete Fourier transform of input

## Examples

Find frequency components of a signal in additive noise:

```

Fs = 800; L = 1000;
t = (0:L-1)'/Fs;
x = sin(2*pi*250*t) + 0.75*cos(2*pi*340*t);
y = x + .5*randn(size(x)); % noisy signal

hfft = dsp.FFT('FFTLengthSource', 'Property', ...
'FFTLength', 1024);

Y = step(hfft, y);

% Plot the single-sided amplitude spectrum
plot(Fs/2*linspace(0,1,512), 2*abs(Y(1:512)/1024));
title('Single-sided amplitude spectrum of noisy signal y(t)');
xlabel('Frequency (Hz)'); ylabel('|Y(f)|');

```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the FFT block reference page. The object properties correspond to the block parameters.

## References

- [1] FFTW (<http://www.fftw.org>)
- [2] Frigo, M. and S. G. Johnson, "FFTW: An Adaptive Software Architecture for the FFT," *Proceedings of the International Conference on Acoustics, Speech, and Signal Processing*, Vol. 3, 1998, pp. 1381-1384.

# **dsp.FFT**

---

## **See Also**

[dsp.IFFT](#) | [dsp.DCT](#) | [dsp.IDCT](#)

**Purpose** Create FFT object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates an FFT object with the same property values as H. The clone method creates a new unlocked object.

# dsp.FFT.getNumInputs

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# dsp.FFT.isLocked

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the FFT object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

# dsp.FFT.step

---

**Purpose** Discrete Fourier transform of input

**Syntax**  $Y = \text{step}(H,X)$

**Description**  $Y = \text{step}(H,X)$  computes the FFT,  $Y$ , of the input  $X$  along the first dimension of  $X$ . When the `FFTLengthSource` property is `Auto`, the length of  $X$  along the first dimension must be a positive integer power of two. This length is also the FFT length. When the `FFTLengthSource` property is `Property`, the `FFTLength` property must be a positive integer power of two.

<b>Purpose</b>	FIR polyphase decimator
<b>Description</b>	<p>The <code>FIRDecimator</code> object resamples vector or matrix inputs along the first dimension. The object resamples at a rate <math>M</math> times slower than the input sampling rate, where <math>M</math> is the integer-valued downsampling factor. The decimation combines an FIR anti-aliasing filter with downsampling. The FIR decimator object uses a polyphase implementation of the FIR filter.</p> <p>To resample vector or matrix inputs along the first dimension:</p> <ol style="list-style-type: none"><li>1 Define and set up your FIR decimator. See “Construction” on page 5-453.</li><li>2 Call <code>step</code> to resample the vector or matrix inputs according to the properties of <code>dsp.FIRDecimator</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.FIRDecimator</code> returns an FIR decimator, <code>H</code>, which applies an FIR filter with a cutoff frequency of <math>0.4\pi</math> radians/sample to the input and downsamples the filter output by factor of 2.</p> <p><code>H = dsp.FIRDecimator('PropertyName',PropertyValue, ...)</code> returns an FIR decimator, <code>H</code>, with each property set to the specified value.</p> <p><code>H = dsp.FIRDecimator(DECIM, NUM, 'PropertyName',PropertyValue, ...)</code> returns an FIR decimator, <code>H</code>, with the integer-valued <code>DecimationFactor</code> property set to <code>DECIM</code>, the <code>Numerator</code> property set to <code>NUM</code>, and other specified properties set to the specified values.</p>
<b>Properties</b>	<p><b>DecimationFactor</b></p> <p>Decimation factor</p> <p>Specify the downsampling factor as a positive integer. The FIR decimator reduces the sampling rate of the input by this factor.</p>

The size of the input along the first dimension must be a multiple of the decimation factor. The default is 2.

## Numerator

FIR filter coefficients

Specify the numerator coefficients of the FIR filter in powers of  $z^{-l}$ . The following equation defines the system function for a filter of length  $L$ :

$$H(z) = \sum_{l=0}^{L-1} b_l z^{-l}$$

To prevent aliasing as a result of downsampling, the filter transfer function should have a normalized cutoff frequency no greater than  $1/\text{DecimationFactor}$ . You can specify the filter coefficients as a vector in the supported data types. The FIR decimator does not support `dfilt` or `mfilt` objects as sources of the filter coefficients. The default is `fir1(35,0.4)`.

## Structure

Filter structure

Specify the implementation of the FIR filter as either `Direct form` or `Direct form transposed`. The default is `Direct form`.

## Fixed-Point Properties

### FullPrecisionOverride

Full precision override for fixed-point arithmetic

Specify whether to use full precision rules. If you set `FullPrecisionOverride` to `true`, which is the default, the object computes all internal arithmetic and output data types using full precision rules. These rules provide the most accurate fixed-point numerics. It also turns off the display of other fixed-point properties because they do not apply individually. These rules guarantee that no quantization occurs within the object. Bits are

added, as needed, to ensure that no roundoff or overflow occurs. If you set `FullPrecisionOverride` to `false`, fixed-point data types are controlled through individual fixed-point property settings. For more information, see “Full Precision for Fixed-Point System Objects”.

## **RoundingMethod**

Rounding method for fixed-point operations

Specify the rounding method as one of `Ceiling` | `Convergent` | `Floor` | `Nearest` | `Round` | `Simplest` | `Zero` |. The default is `Floor`. This property applies only if the object is not in full precision mode.

## **OverflowAction**

Overflow action for fixed-point operations

Specify the overflow action as one of `Wrap` or `Saturate`. This property applies only if the object is not in full precision mode.

## **CoefficientsDataType**

Coefficients word and fraction lengths

Specify the coefficients fixed-point data type as `Same word length as input` or `Custom`. The default is `Same word length as input`.

## **CustomCoefficientsDataType**

Coefficients word and fraction lengths

Specify the coefficients fixed-point type as a `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `CoefficientsDataType` property to `Custom`. The default is `numericType([], 16, 15)`.

## **ProductDataType**

Product word and fraction lengths

Specify the product fixed-point data type as one of | Full precision | Same as input | Custom |. The default is Full precision.

## **CustomProductDataType**

Product word and fraction lengths

Specify the product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `ProductDataType` property to `Custom`. The default is `numericType([],32,30)`.

## **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point data type as one of | Full precision | Same as product | Same as input | Custom |. The default is Full precision.

## **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `AccumulatorDataType` property to `Custom`. The default is `numericType([],32,30)`.

## **OutputDataType**

Output word and fraction lengths

Specify the output fixed-point data type as one of | Same as accumulator | Same as product | Same as input | Custom |. The default is Same as accumulator.

## **CustomOutputDataType**

Output word and fraction lengths

Specify the output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when

you set the `OutputDataType` property to `Custom`. The default is `numerictype([ ]1,16,15)`.

## Methods

<code>clone</code>	Create FIR decimator object with same property values
<code>freqz</code>	Frequency response
<code>fvtool</code>	Open filter visualization tool
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>impz</code>	Impulse response
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>phasez</code>	Unwrapped phase response
<code>release</code>	Allow property value and input characteristics changes
<code>reset</code>	Reset filter states of FIR decimator
<code>step</code>	Decimate input by integer factor

More “Analysis Methods for Filter System Objects” on page 4-2.

## Definitions

### Polyphase Subfilters

A polyphase implementation of an FIR decimator *splits* the lowpass FIR filter impulse response into  $M$  different subfilters, where  $M$  is the downsampling, or decimation factor. Let  $h(n)$  denote the FIR filter impulse response of length  $L$  and  $u(n)$  the input signal. Decimating the filter output by a factor of  $M$  is equivalent to the downsampled convolution:

# dsp.FIRDecimator

---

$$y(n) = \sum_{l=0}^{L-1} h(l)u(nM - l)$$

The key to the efficiency of polyphase filtering is that specific input values are only multiplied by select values of the impulse response in the downsampled convolution. For example, letting  $M=2$ , the input values  $u(0), u(2), u(4), \dots$  are only combined with the filter coefficients  $h(0), h(2), h(4), \dots$ , and the input values  $u(1), u(3), u(5), \dots$  are only combined with the filter coefficients  $h(1), h(3), h(5), \dots$ . By splitting the filter coefficients into two polyphase subfilters, no unnecessary computations are performed in the convolution. The outputs of the convolutions with the polyphase subfilters are interleaved and summed to yield the filter output. The following MATLAB code demonstrates how to construct the two polyphase subfilters for the default order 35 filter in the `Numerator` property and the default `DecimationFactor` property value of two:

```
M = 2;
Num = fir1(35,0.4);
FiltLength = length(Num);
Num = flipud(Num(:));

if (rem(FiltLength, M) ~= 0)
    nzeros = M - rem(FiltLength, M);
    Num = [zeros(nzeros,1); Num]; % Appending zeros
end

len = length(Num);
nrows = len / M;
PolyphaseFilt = flipud(reshape(Num, M, nrows).');
```

The columns of `PolyphaseFilt` are subfilters containing the two *phases* of the filter in `Num`. For a general downsampling factor of  $M$ , there are  $M$  phases and therefore  $M$  subfilters.

## Examples

Decimate a sum of sine waves with angular frequencies of  $\pi/4$  and  $2\pi/3$  radians/sample by a factor of two. To prevent aliasing, the

FIR decimator filters out the  $2\pi/3$  radians/sample component before downsampling:


```
x = cos(pi/4*[0:95]')+sin(2*pi/3*[0:95]');
H = dsp.FIRDecimator;
y = step(H,x);

% View group delay of default FIR filter
fvtool(fir1(35,0.4),1,'analysis','grpdelay');
% Group delay of the default linear-phase FIR filter
% is 17.5 samples. Downsampling by a factor of
% two expect an approx. 8.75 sample delay in the output
% y with the initial filter states of zero

subplot(211);
stem(x(1:length(x)/2),'b','markerfacecolor',[0 0 1]);
title('Input Signal');
subplot(212);
stem(y,'b','markerfacecolor',[0 0 1]);
title('Output--Lowpass filtered and downsampled by 2');
```

The figure shows that the delay in the decimated output is consistent with the group delay of the filter when the initial filter states are zero.

# dsp.FIRDecimator



Reduce the sampling rate of an audio signal by 1/2 and play it:

```
hmfr = dsp.AudioFileReader('OutputDataType',...  
    'single');  
hap = dsp.AudioPlayer(22050/2);  
hfirdec = dsp.FIRDecimator;  
  
while ~isDone(hmfr)  
    frame = step(hmfr);  
    y = step(hfirdec, frame);  
    step(hap, y);  
end  
  
release(hmfr);  
pause(0.5);  
release(hap);
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the FIR Decimation block reference page. The object properties correspond to the block parameters, except:

- **Coefficient source** – The FIR decimator object does not support `mfilt` objects.
- **Framing** – The FIR decimator object only supports `Maintain input frame rate`
- **Output buffer initial conditions** – The FIR decimator object does not support this parameter.
- **Rate options** – The FIR decimator object does not support this parameter.
- **Input processing** The FIR decimator object does not support this parameter.

### See Also

`dsp.FIRInterpolator` | `dsp.FIRRateConverter`

# **dsp.FIRDecimator.clone**

---

**Purpose** Create FIR decimator object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates an FIR decimator object, `C`, with the same property values as `H`. The clone method creates a new unlocked object with uninitialized states.

**Purpose** Frequency response

**Syntax**

```
[h,w] = freqz(H)
[h,w] = freqz(H,n)
[h,w] = freqz(H,Name,Value)
freqz(H)
```

**Description** `[h,w] = freqz(H)` returns the complex, 8192–element frequency response vector `h`, and the corresponding frequencies `w` in radians/sample.

`[h,w] = freqz(H,n)` returns the complex, `n`-element frequency response vector `h`, and the corresponding frequencies `w` in radians/sample, using `n` samples.

`[h,w] = freqz(H,Name,Value)` returns the frequency response and the corresponding frequencies, with additional options specified by one or more `Name, Value` pair arguments.

`freqz(H)` uses `FVTool` to plot the magnitude and unwrapped phase of the frequency response of the filter System object `H`.

# **dsp.FIRDecimator.fvtool**

---

**Purpose** Open filter visualization tool

**Syntax** `fvtool(H)`  
`fvtool(H, 'Arithmetic', ARITH, ...)`

**Description** `fvtool(H)` performs an analysis and computes the magnitude response of the filter System object H.

`fvtool(H, 'Arithmetic', ARITH, ...)` analyzes the filter System object H, based on the arithmetic specified in the ARITH input. ARITH can be set to one of 'double', 'single', or 'fixed'. The analysis tool assumes a double precision filter when the arithmetic input is not specified and the filter System object is in an unlocked state. The 'Arithmetic' input is only relevant for the analysis of filter System objects.

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.FIRDecimator.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Impulse response

**Syntax**  
`[h,t] = impz(H)`  
`[h,t] = impz(H,Name,Value)`  
`impz(H)`

**Description** `[h,t] = impz(H)` returns the impulse response `h`, and the corresponding time points `t` at which the impulse response of `H` is computed.

`[h,t] = impz(H,Name,Value)` returns the impulse response `h`, and the corresponding time points `t`, with additional options specified by one or more `Name, Value` pair arguments.

`impz(H)` uses `FVTool` to plot the impulse response of the filter System object `H`.

---

**Note** You can use `impz` for both real and complex filters. When you omit the output arguments, `impz` plots only the real part of the impulse response.

---

# **dsp.FIRDecimator.isLocked**

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the FIR decimator.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Unwrapped phase response

**Syntax**

```
[phi,w] = phasez(H)  
[phi,w] = phasez(H,n)  
[phi,w] = phasez(H,Name,Value)  
phasez(H)
```

**Description**

`[phi,w] = phasez(H)` returns the 8192–element phase response vector `phi`, and the corresponding frequencies `w` in radians/sample.

`[phi,w] = phasez(H,n)` returns the `n`-element phase response vector `phi`, and the corresponding frequencies `w` in radians/sample, using `n` samples.

`[phi,w] = phasez(H,Name,Value)` returns the phase response and the corresponding frequencies, with additional options specified by one or more `Name, Value` pair arguments.

`phasez(H)` uses FVTool to plot the phase response of the filter System object `H`.

# dsp.FIRDecimator.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Reset filter states of FIR decimator

**Syntax** reset(H)

**Description** reset(H) resets the filter states of the FIR decimator object,H, to the initial values of zero. After the step method applies the FIR decimator to nonzero input data, the filter states may change. Invoking the step method again without first invoking the reset method may produce different outputs for an identical input.

Example of resetting filter states:

```
H = dsp.FIRDecimator;
x = cos(pi/8*[0:1023]')+sin(pi/4*[0:1023]');
y = step(H,x);
% Invoke step method again without reset
y1 = step(H,x);
isequal(y,y1) % Returns 0
% Reset filter states
reset(H);
y2 = step(H,x);
isequal(y,y2) % Returns 1
```

# dsp.FIRDecimator.step

---

**Purpose** Decimate input by integer factor

**Syntax**  $Y = \text{step}(H,X)$

**Description**  $Y = \text{step}(H,X)$  outputs the filtered and downsampled values,  $Y$ , of the input signal,  $X$ . A  $K_i$ -by- $N$  input matrix is treated as  $N$  independent channels. The length of each column must be a multiple of the `DecimationFactor` property value. The FIR decimator operates on each channel separately and generates a  $K_o$ -by- $N$  output matrix where  $K_o = K_i/M$  with  $M$  the decimation factor. The object supports real and complex floating-point and fixed-point inputs, except for complex unsigned fixed-point inputs.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

<b>Purpose</b>	Static or time-varying FIR filter
<b>Description</b>	<p>The <code>FIRFilter</code> object filters each channel of the input using static or time-varying FIR filter implementations.</p> <p>To filter each channel of the input:</p> <ol style="list-style-type: none"><li>1 Define and set up your FIR filter. See “Construction” on page 5-473.</li><li>2 Call <code>step</code> to filter each channel of the input according to the properties of <code>dsp.FIRFilter</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.FIRFilter</code> returns a default FIR filter object, <code>H</code>, which independently filters each channel of the input over successive calls to the <code>step</code> method, using a specified FIR filter implementation. The default numerator coefficients are <code>[0.5 0.5]</code>.</p> <p><code>H = dsp.FIRFilter('PropertyName',PropertyValue, ...)</code> returns an FIR filter system object, <code>H</code>, with each property set to the specified value.</p>
<b>Properties</b>	<p><b>Structure</b></p> <p>Filter structure</p> <p>Specify the filter structure.</p> <p>You can specify the filter structure as one of   <code>Direct form</code>   <code>Direct form symmetric</code>   <code>Direct form antisymmetric</code>   <code>Direct form transposed</code>   <code>Lattice MA</code>  . The default is <code>Direct form</code>.</p> <p><b>NumeratorSource</b></p> <p>Source of filter coefficients</p> <p>Specify the source of the filter coefficients as one of   <code>Property</code>   <code>Input port</code>  . The default is <code>Property</code>. When you specify <code>Input port</code>, the filter object updates the time-varying filter once</p>

every frame, when the `FrameBasedProcessing` property is true. When the `FrameBasedProcessing` property is false, it updates once every sample.

This applies when you set the `Structure` to `Direct form` | `Direct form symmetric` | `Direct form antisymmetric` | `Direct form transposed`.

## **ReflectionCoefficientsSource**

Source of filter coefficients

Specify the source of the Lattice filter coefficients as one of `Property` | `Input port` |. The default is `Property`. When you specify `Input port`, the filter object updates the time-varying filter once every frame, when the `FrameBasedProcessing` property is true. When the `FrameBasedProcessing` property is false, it updates once every sample.

This applies when you set the `Structure` to `Lattice MA`.

## **Numerator**

Numerator coefficients

Specify the filter coefficients as a real or complex numeric row vector. This property applies when you set the `NumeratorSource` property to `Property`, and the `Structure` property is not set to `Direct form`, `Direct form symmetric`, `Direct form antisymmetric`, or `Direct form transposed`. The default is `[0.5 0.5]`. This property is tunable.

## **ReflectionCoefficients**

Reflection coefficients of lattice filter structure

Specify the reflection coefficients of a lattice filter as a real or complex numeric row vector. This property applies when you set the `Structure` property to `Lattice MA`, and the `ReflectionCoefficientsSource` property to `Property`. The default is `[0.5 0.5]`. This property is tunable.

## **InitialConditions**

## Initial conditions for the FIR filter

Specify the initial conditions of the filter states. The number of states or delay elements equals the number of reflection coefficients for the lattice structure, or the number of filter coefficients–1 for the other direct form structures.

You can specify the initial conditions as a scalar, vector, or matrix. If you specify a scalar value, the FIR filter object initializes all delay elements in the filter to that value. If you specify a vector whose length equals the number of delay elements in the filter, each vector element specifies a unique initial condition for the corresponding delay element. The object applies the same vector of initial conditions to each channel of the input signal.

If you specify a vector whose length equals the product of the number of input channels and the number of delay elements in the filter, each element specifies a unique initial condition for the corresponding delay element in the corresponding channel.

If you specify a matrix with the same number of rows as the number of delay elements in the filter, and one column for each channel of the input signal, each element specifies a unique initial condition for the corresponding delay element in the corresponding channel. The default is 0.

## **FrameBasedProcessing**

Enable frame-based processing

Set this property to `true` to enable frame-based processing. Set this property to `false` to enable sample-based processing. The default is `true`.

## **Fixed-Point Properties**

### **FullPrecisionOverride**

Full precision override for fixed-point arithmetic

Specify whether to use full precision rules. If you set `FullPrecisionOverride` to `true`, which is the default, the object computes all internal arithmetic and output data types using full precision rules. These rules provide the most accurate fixed-point numerics. It also turns off the display of other fixed-point properties because they do not apply individually. These rules guarantee that no quantization occurs within the object. Bits are added, as needed, to ensure that no roundoff or overflow occurs. If you set `FullPrecisionOverride` to `false`, fixed-point data types are controlled through individual fixed-point property settings. For more information, see “Full Precision for Fixed-Point System Objects”.

## **RoundingMethod**

Rounding method for fixed-point operations

Specify the rounding method as one of | `Ceiling` | `Convergent` | `Floor` | `Nearest` | `Round` | `Simplest` | `Zero` |. The default is `Floor`. This property applies only if the object is not in full precision mode.

## **OverflowAction**

Overflow action for fixed-point operations

Specify the overflow action as one of | `Wrap` | `Saturate` |. The default is `Wrap`. This property applies only if the object is not in full precision mode.

## **CoefficientsDataType**

Coefficients word and fraction lengths

Specify the coefficients fixed-point data type as one of | `Same word length as input` | `Custom` |. This property applies when you set the `NumeratorSource` property to `Property`. The default is `Same word length as input`.

## **CustomCoefficientsDataType**

Custom coefficients word and fraction lengths

Specify the coefficients fixed-point type as a `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `CoefficientsDataType` property to `Custom`. The default is `numericType(true,16,15)`.

## **ReflectionCoefficientsDataType**

Reflection coefficients word and fraction lengths

Specify the reflection coefficients fixed-point data type as one of `Same word length as input` | `Custom` |. This property applies when you set the `ReflectionCoefficientsSource` property to `Property`. The default is `Same word length as input`.

## **CustomReflectionCoefficientsDataType**

Custom reflection coefficients word and fraction lengths

Specify the numerator fixed-point type as a signed or unsigned `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `ReflectionCoefficientsDataType` property to `Custom`. The default is `numericType(true,16,15)`.

## **ProductDataType**

Product word and fraction lengths

Specify the product fixed-point data type as one of `Full precision` | `Same as input` | `Custom` |. The default is `Full precision`.

## **CustomProductDataType**

Custom product word and fraction lengths

Specify the product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `ProductDataType` property to `Custom`. The default is `numericType(true,32,30)`.

## **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point data type to one of | Full precision | Same as input | Same as product | Custom |. The default is Full precision.

## **CustomAccumulatorDataType**

Custom accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `AccumulatorDataType` property to `Custom`. The default is `numericType(true,32,30)`.

## **StateDataType**

State word and fraction lengths

Specify the state fixed-point data type as one of | Same as input | Same as accumulator | Custom |. This property does not apply to any of the direct form or direct form I filter structures. The default is Same as accumulator.

## **CustomStateDataType**

Custom state word and fraction lengths

Specify the state fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `StateDataType` property to `Custom`. The default is `numericType(true,16,15)`.

## **OutputDataType**

Output word and fraction lengths

Specify the output fixed-point data type as one of | Same as input | Same as accumulator | Custom |. The default is Same as accumulator.

## **CustomOutputDataType**

Custom output word and fraction lengths

Specify the output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `OutputDataType` property to `Custom`. The default is `numericType(true,16,15)`.

## Methods

<code>clone</code>	Create static or time-varying FIR filter with same property values
<code>freqz</code>	Frequency response
<code>fvtool</code>	Open filter visualization tool
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>impz</code>	Impulse response
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>phasez</code>	Unwrapped phase response
<code>release</code>	Allow property value and input characteristics changes
<code>reset</code>	Reset internal states of FIR filter
<code>step</code>	Filter input with FIR filter object

More “Analysis Methods for Filter System Objects” on page 4-2.

## Examples

Use an FIR filter to apply a low pass filter to a waveform with two sinusoidal components:

```
t = [0:63]./32e3;
xin = (sin(2*pi*4e3*t)+sin(2*pi*12e3*t)) / 2;

hSR = dsp.SignalSource(xin', 4);
hLog = dsp.SignalSink;
```

```
hFIR = dsp.FIRFilter;
hFIR.Numerator = fir1(10,0.5);

while ~isDone(hSR)
    input = step(hSR);
    filteredOutput = step(hFIR,input);
    step(hLog,filteredOutput);
end

filteredResult = hLog.Buffer;
sper = spectrum.periodogram;
psd(sper,filteredResult,'Fs',32e3)
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Discrete FIR Filter block reference page. The object properties correspond to the block parameters.

Both this object and its corresponding block let you specify whether to process inputs as individual samples or as frames of data. The object uses the `FrameBasedProcessing` property. The block uses the **Input processing** parameter. See “Set the FrameBasedProcessing Property of a System object” for more information.

## See Also

`dsp.BiquadFilter`

**Purpose** Create static or time-varying FIR filter with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a FIR filter object, `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with uninitialized states.

# dsp.FIRFilter.freqz

---

**Purpose** Frequency response

**Syntax**  
`[h,w] = freqz(H)`  
`[h,w] = freqz(H,n)`  
`[h,w] = freqz(H,Name,Value)`  
`freqz(H)`

**Description**

`[h,w] = freqz(H)` returns the complex, 8192–element frequency response vector `h`, and the corresponding frequencies `w` in radians/sample.

`[h,w] = freqz(H,n)` returns the complex, `n`-element frequency response vector `h`, and the corresponding frequencies `w` in radians/sample, using `n` samples.

`[h,w] = freqz(H,Name,Value)` returns the frequency response and the corresponding frequencies, with additional options specified by one or more `Name, Value` pair arguments.

`freqz(H)` uses `FVTool` to plot the magnitude and unwrapped phase of the frequency response of the filter System object `H`.

**Purpose** Open filter visualization tool

**Syntax** `fvtool(H)`  
`fvtool(H, 'Arithmetic', ARITH, ...)`

**Description** `fvtool(H)` performs an analysis and computes the magnitude response of the filter System object H.

`fvtool(H, 'Arithmetic', ARITH, ...)` analyzes the filter System object H, based on the arithmetic specified in the ARITH input. ARITH can be set to one of 'double', 'single', or 'fixed'. The analysis tool assumes a double precision filter when the arithmetic input is not specified and the filter System object is in an unlocked state. The 'Arithmetic' input is only relevant for the analysis of filter System objects.

## **dsp.FIRFilter.getNumInputs**

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose**

Number of outputs of step method

**Syntax**

`N = getNumOutputs(H)`

**Description**

`N = getNumOutputs(H)` returns the number of outputs, `N`, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# dsp.FIRFilter.impz

---

**Purpose** Impulse response

**Syntax** `[h,t] = impz(H)`  
`[h,t] = impz(H,Name,Value)`  
`impz(H)`

**Description** `[h,t] = impz(H)` returns the impulse response `h`, and the corresponding time points `t` at which the impulse response of `H` is computed.

`[h,t] = impz(H,Name,Value)` returns the impulse response `h`, and the corresponding time points `t`, with additional options specified by one or more `Name, Value` pair arguments.

`impz(H)` uses `FVTool` to plot the impulse response of the filter System object `H`.

---

**Note** You can use `impz` for both real and complex filters. When you omit the output arguments, `impz` plots only the real part of the impulse response.

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the FIR filter.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.FIRFilter.phasez

---

**Purpose** Unwrapped phase response

**Syntax**  
`[phi,w] = phasez(H)`  
`[phi,w] = phasez(H,n)`  
`[phi,w] = phasez(H,Name,Value)`  
`phasez(H)`

**Description**

`[phi,w] = phasez(H)` returns the 8192–element phase response vector `phi`, and the corresponding frequencies `w` in radians/sample.

`[phi,w] = phasez(H,n)` returns the `n`-element phase response vector `phi`, and the corresponding frequencies `w` in radians/sample, using `n` samples.

`[phi,w] = phasez(H,Name,Value)` returns the phase response and the corresponding frequencies, with additional options specified by one or more `Name, Value` pair arguments.

`phasez(H)` uses `FVTool` to plot the phase response of the filter System object `H`.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

# dsp.FIRFilter.reset

---

**Purpose** Reset internal states of FIR filter

**Syntax** reset(H)

**Description** reset(H) resets the filter states of the FIR filter object,H, to their initial values of 0. The initial filter state values correspond to the initial conditions for the difference equation defining the filter. After the step method applies the FIR filter object to nonzero input data, the states may be nonzero. Invoking the step method again without first invoking the reset method may produce different outputs for an identical input.

For example:

```
H = dsp.FIRFilter;  
H.Numerator = fir1(20,0.25);  
n = 0:100;  
x = cos(0.2*pi*n)+sin(0.8*pi*n);  
y = step(H,x);  
% Filter states are nonzero  
% Invoke step method again without resetting states  
y1 = step(H,x);  
isequal(y,y1) % returns 0  
% Now reset filter states to 0  
reset(H)  
% Invoke step method  
y2 = step(H,x);  
isequal(y,y2) % returns a 1
```

**Purpose** Filter input with FIR filter object

**Syntax**  
`Y = step(HFIR,X)`  
`Y = step(HFIR,X,COEFF)`

**Description** `Y = step(HFIR,X)` filters the real or complex input signal `X` using the FIR filter, `H`, to produce the output `Y`. When the input data is of a fixed-point type, it must be signed when the structure is set to `Direct form symmetric` or `Direct form antisymmetric`. The FIR filter object operates on each channel of the input signal independently over successive calls to `step` method.

`Y = step(HFIR,X,COEFF)` uses the time-varying coefficients, `COEFF`, to filter the input signal `X` and produce the output `Y`. You can use this option when you set the `NumeratorSource` or `ReflectionCoefficientsSource` property to `Input port`.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.FIRInterpolator

---

**Purpose** Polyphase FIR interpolator

**Description** The `FIRInterpolator` object upsamples an input by the integer upsampling factor,  $L$ , followed by an FIR anti-imaging filter. The filter coefficients are scaled by the interpolation factor. A polyphase interpolation structure implements the filter. The resulting discrete-time signal has a sampling rate  $L$  times the original sampling rate.

To upsample an input:

- 1 Define and set up your FIR interpolator. See “Construction” on page 5-492.
- 2 Call `step` to upsample the input according to the properties of `dsp.FIRInterpolator`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.FIRInterpolator` returns an FIR interpolator, `H`, which upsamples an input signal by a factor of 3 and applies an FIR filter to interpolate the output.

`H = dsp.FIRInterpolator('PropertyName',PropertyValue, ...)` returns an FIR interpolator, `H`, with each property set to the specified value.

`H = dsp.FIRInterpolator(INTERP, NUM, 'PropertyName',PropertyValue, ...)` returns an FIR interpolation object, `H`, with the `InterpolationFactor` property set to `INTERP`, the `Numerator` property set to `NUM`, and other properties set to the specified values.

**Properties** **InterpolationFactor**

Interpolation factor

Specify the integer factor,  $L$ , by which to increase the sampling rate of the input signal. The polyphase implementation uses  $L$  polyphase subfilters to compute convolutions at the lower sample

rate. The FIR interpolator delays and interleaves these lower-rate convolutions to obtain the higher-rate output. The property value defaults to 3.

## Numerator

FIR filter coefficients

Specify the numerator coefficients of the FIR anti-imaging filter as the coefficients of a polynomial in  $z^{-1}$ . Indexing from zero, the filter coefficients are:

$$H(z) = \sum_{n=0}^{N-1} b(n)z^{-n}$$

To act as an effective anti-imaging filter, the coefficients must correspond to a lowpass filter with a normalized cutoff frequency no greater than the reciprocal of the `InterpolationFactor`. The filter coefficients are scaled by the value of the `InterpolationFactor` property before filtering the signal. To form the  $L$  polyphase subfilters, `Numerator` is appended with zeros if necessary. The default is the output of `fir1(15,0.25)`.

## Fixed-Point Properties

### FullPrecisionOverride

Full precision override for fixed-point arithmetic

Specify whether to use full precision rules. If you set `FullPrecisionOverride` to `true`, which is the default, the object computes all internal arithmetic and output data types using full precision rules. These rules provide the most accurate fixed-point numerics. It also turns off the display of other fixed-point properties because they do not apply individually. These rules guarantee that no quantization occurs within the object. Bits are added, as needed, to ensure that no roundoff or overflow occurs. If you set `FullPrecisionOverride` to `false`, fixed-point data types are controlled through individual fixed-point property settings.

For more information, see “Full Precision for Fixed-Point System Objects”.

## **RoundingMethod**

Rounding method for fixed-point operations

Specify the rounding method as one of | `Ceiling` | `Convergent` | `Floor` | `Nearest` | `Round` | `Simplest` | `Zero` |. The default is `Floor`. This property applies only if the object is not in full precision mode.

## **OverflowAction**

Overflow action for fixed-point operations

Specify the overflow action as one of | `Wrap` | `Saturate` |. The default is `Wrap`. This property applies only if the object is not in full precision mode.

## **CoefficientsDataType**

Coefficient word and fraction lengths

Specify the coefficients fixed-point data type as one of | `Same word length as input` | `Custom` |. The default is `Same word length as input`.

## **CustomCoefficientsDataType**

Coefficient word and fraction lengths

Specify the coefficients fixed-point type as a `numericType` object with a `Signedness` of `Auto`. This property applies only when the `CoefficientsDataType` property is `Custom`. The default is `numericType([],16,15)`.

## **ProductDataType**

Product word and fraction lengths

Specify the product fixed-point data type as one of | `Full precision` | `Same as input` | `Custom` |. The default is `Full precision`.

## **CustomProductDataType**

Product word and fraction lengths

Specify the product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when the `ProductDataType` property is `Custom`. The default is `numericType([],32,30)`.

## **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point data type as one of `| Full precision | Same as product | Same as input | Custom |`. The default is `Full precision`.

## **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when the `AccumulatorDataType` property is `Custom`. The default is `numericType([],32,30)`.

## **OutputDataType**

Output word and fraction lengths

Specify the output fixed-point data type as one of `| Same as accumulator | Same as product | Same as input | Custom |`. The default is `Same as accumulator`.

## **CustomOutputDataType**

Output word and fraction lengths

Specify the output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when the `OutputDataType` property is `Custom`. The default is `numericType([],16,15)`.

# dsp.FIRInterpolator

---

## Methods

clone	Create FIR interpolator object with same property values
freqz	Frequency response
fvtool	Open filter visualization tool
getNumInputs	Number of expected inputs to step method
getNumOutputs	Number of outputs of step method
impz	Impulse response
isLocked	Locked status for input attributes and nontunable properties
phasez	Unwrapped phase response
release	Allow property value and input characteristics changes
reset	Reset FIR interpolator filter states
step	Upsample and interpolate input

More “Analysis Methods for Filter System Objects” on page 4-2.

## Examples

Double the sampling rate of an audio signal from 22.05 kHz to 44.1 kHz, and play the audio:

```
hmfr = dsp.AudioFileReader('OutputDataType',...  
    'single');  
hap = dsp.AudioPlayer(44100);  
hfirint = dsp.FIRInterpolator(2, ...  
    firpm(30, [0 0.45 0.55 1], [1 1 0 0]));  
  
while ~isDone(hmfr)  
    frame = step(hmfr);  
    y = step(hfirint, frame);  
end
```

```
        step(hap, y);  
end  
  
pause(1);  
release(hmfr);  
release(hap);
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the FIR Interpolation block reference page. The object properties correspond to the block parameters, except:

- The `FIRInterpolator` object does not have a property that corresponds to the **Input processing** parameter of the FIR Interpolation block.
- The **Rate options** block parameter is not supported by the `FIRInterpolator` object.

## See Also

`dsp.FIRDecimator` | `dsp.FIRRateConverter`

# **dsp.FIRInterpolator.clone**

---

**Purpose** Create FIR interpolator object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates an FIR interpolator, `C`, with the same property values as `H`. The clone method creates a new unlocked object with uninitialized states.

**Purpose** Frequency response

**Syntax**  
`[h,w] = freqz(H)`  
`[h,w] = freqz(H,n)`  
`[h,w] = freqz(H,Name,Value)`  
`freqz(H)`

**Description** `[h,w] = freqz(H)` returns the complex, 8192–element frequency response vector `h`, and the corresponding frequencies `w` in radians/sample.

`[h,w] = freqz(H,n)` returns the complex, `n`-element frequency response vector `h`, and the corresponding frequencies `w` in radians/sample, using `n` samples.

`[h,w] = freqz(H,Name,Value)` returns the frequency response and the corresponding frequencies, with additional options specified by one or more `Name, Value` pair arguments.

`freqz(H)` uses FVTool to plot the magnitude and unwrapped phase of the frequency response of the filter System object `H`.

# **dsp.FIRInterpolator.fvtool**

---

**Purpose** Open filter visualization tool

**Syntax** `fvtool(H)`  
`fvtool(H, 'Arithmetic', ARITH, ...)`

**Description** `fvtool(H)` performs an analysis and computes the magnitude response of the filter System object H.

`fvtool(H, 'Arithmetic', ARITH, ...)` analyzes the filter System object H, based on the arithmetic specified in the ARITH input. ARITH can be set to one of 'double', 'single', or 'fixed'. The analysis tool assumes a double precision filter when the arithmetic input is not specified and the filter System object is in an unlocked state. The 'Arithmetic' input is only relevant for the analysis of filter System objects.

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.FIRInterpolator.getNumOutputs**

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of output from the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Impulse response

**Syntax**  
`[h,t] = impz(H)`  
`[h,t] = impz(H,Name,Value)`  
`impz(H)`

**Description** `[h,t] = impz(H)` returns the impulse response `h`, and the corresponding time points `t` at which the impulse response of `H` is computed.

`[h,t] = impz(H,Name,Value)` returns the impulse response `h`, and the corresponding time points `t`, with additional options specified by one or more `Name, Value` pair arguments.

`impz(H)` uses `FVTool` to plot the impulse response of the filter System object `H`.

---

**Note** You can use `impz` for both real and complex filters. When you omit the output arguments, `impz` plots only the real part of the impulse response.

---

# **dsp.FIRInterpolator.isLocked**

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the FIR interpolator.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Unwrapped phase response

**Syntax**

```
[phi,w] = phasez(H)  
[phi,w] = phasez(H,n)  
[phi,w] = phasez(H,Name,Value)  
phasez(H)
```

**Description**

`[phi,w] = phasez(H)` returns the 8192–element phase response vector `phi`, and the corresponding frequencies `w` in radians/sample.

`[phi,w] = phasez(H,n)` returns the `n`-element phase response vector `phi`, and the corresponding frequencies `w` in radians/sample, using `n` samples.

`[phi,w] = phasez(H,Name,Value)` returns the phase response and the corresponding frequencies, with additional options specified by one or more `Name, Value` pair arguments.

`phasez(H)` uses FVTool to plot the phase response of the filter System object `H`.

# dsp.FIRInterpolator.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Reset FIR interpolator filter states

**Syntax** reset(H)

**Description** reset(H) resets the filter states of the FIR filter in the interpolator object, H, to their initial values of 0. The initial filter state values correspond to the initial conditions for the constant coefficient linear difference equation defining the FIR filter. After the step method applies the interpolator to nonzero input data, the states may be nonzero. Invoking the step method again without first invoking the reset method may produce different outputs for an identical input.

Reset filter states to 0 to produce consistent output:

```
H = dsp.FIRInterpolator(2);
x =[1 -1]'; x = repmat(x,8,1);
y = step(H,x); % Filter states are nonzero
% Use reset method to set states to zero
reset(H);
% Apply FIR interpolator to input x
y1 = step(H,x);
isequal(y,y1)
% Returns a 1
```

## dsp.FIRInterpolator.step

---

**Purpose** Upsample and interpolate input

**Syntax**  $Y = \text{step}(H, X)$

**Description**  $Y = \text{step}(H, X)$  outputs the upsampled and interpolated values,  $Y$ , of the input signal  $X$ . A  $K$ -by- $N$  input matrix is treated as  $N$  independent channels. The FIR interpolator object interpolates each channel over the first dimension and generates a  $M$ -by- $N$  output matrix, where  $M$  is the product of  $K$  and the upsampling factor,  $L$ .

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

<b>Purpose</b>	Sample rate converter
<b>Description</b>	<p>The FIRRateConverter performs sampling rate conversion by a rational factor on a vector or matrix input. The FIR rate convertor cascades an interpolator with a decimator. The interpolator upsamples the input by the upsampling factor, <math>L</math>, followed by a lowpass FIR filter. The FIR filter acts both as an anti-imaging filter and an anti-aliasing filter prior to decimation. The decimator downsamples the output of upsampling and FIR filtering by the downsampling factor <math>M</math>. You must use upsampling and downsampling factors that are relatively prime, or coprime. The resulting discrete-time signal has a sampling rate <math>L/M</math> times the original sampling rate.</p> <p>To perform sampling rate conversion:</p> <ol style="list-style-type: none"><li>1 Define and set up your FIR sample rate converter. See “Construction” on page 5-509.</li><li>2 Call <code>step</code> to perform sampling rate conversion according to the properties of <code>dsp.FIRRateConverter</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.FIRRateConverter</code> returns a FIR sample rate converter, <code>H</code>, that resamples an input signal at a rate <math>3/2</math> times the original sampling rate.</p> <p><code>H = dsp.FIRRateConverter('PropertyName',PropertyValue, ...)</code> returns an FIR sample rate converter, <code>H</code>, with each property set to the specified value.</p> <p><code>H = dsp.FIRRateConverter(L,M,NUM,'PropertyName',PropertyValue, ...)</code> returns an FIR sample rate converter, <code>H</code>, with the <code>InterpolationFactor</code> property set to <math>L</math>, the <code>DecimationFactor</code> property set to <math>M</math>, the <code>Numerator</code> property set to <math>NUM</math>, and other specified properties set to the specified values.</p>
<b>Properties</b>	<p><b>InterpolationFactor</b></p> <p>Interpolation factor</p>

Specify the integer upsampling factor. The default is 3.

## **DecimationFactor**

Decimation factor

Specify the integer downsampling factor. The default is 2.

## **Numerator**

FIR filter coefficients

Specify the FIR filter coefficients in powers of  $z^{-1}$ . The length of filter coefficients must exceed the interpolation factor. Use a lowpass with normalized cutoff frequency no greater than  $\min(1/\text{InterpolationFactor}, 1/\text{DecimationFactor})$ . All initial filter states are zero. The default is `firpm(70,[0 0.28 0.32 1],[1 1 0 0])`.

## **Fixed-Point Properties**

### **FullPrecisionOverride**

Full precision override for fixed-point arithmetic

Specify whether to use full precision rules. If you set `FullPrecisionOverride` to `true`, which is the default, the object computes all internal arithmetic and output data types using full precision rules. These rules provide the most accurate fixed-point numerics. It also turns off the display of other fixed-point properties because they do not apply individually. These rules guarantee that no quantization occurs within the object. Bits are added, as needed, to ensure that no roundoff or overflow occurs. If you set `FullPrecisionOverride` to `false`, fixed-point data types are controlled through individual fixed-point property settings. For more information, see “Full Precision for Fixed-Point System Objects”.

### **RoundingMethod**

Rounding method for fixed-point operations

Specify the rounding method as one of | `Ceiling` | `Convergent` | `Floor` | `Nearest` | `Round` | `Simplest` | `Zero` |. The default is `Floor`. This property applies only if the object is not in full precision mode.

## **OverflowAction**

Overflow action for fixed-point operations

Specify the overflow action as one of | `Wrap` | `Saturate` |. The default is `Wrap`. This property applies only if the object is not in full precision mode.

## **CoefficientsDataType**

Word and fraction lengths of filter coefficients

Specify the filter coefficient fixed-point data type as one of | `Same word length as input` | `Custom` |. The default is `Same word length as input`.

## **CustomCoefficientsDataType**

Word and fraction lengths of filter coefficients

Specify the filter coefficient fixed-point type as a `numericType` object with a `Signedness` of `Auto`. This property applies only when the `CoefficientsDataType` property is `Custom`. The default is `numericType([],16,15)`.

## **ProductDataType**

Product word and fraction lengths

Specify the product fixed-point data type as one of | `Full precision` | `Same as input` | `Custom` |. The default is `Full precision`.

## **CustomProductDataType**

Product word and fraction lengths

Specify the product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only

# dsp.FIRRateConverter

---

when the `ProductDataType` property is `Custom`. The default is `numericType([],32,30)`.

## **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point data type as one of | `Full precision` | `Same as product` | `Same as input` | `Custom` |. The default is `Full precision`.

## **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when the `AccumulatorDataType` property is `Custom`. The default is `numericType([],32,30)`.

## **OutputDataType**

Output word and fraction lengths

Specify the output fixed-point data type as one of | `Same as accumulator` | `Same as product` | `Same as input` | `Custom` |. The default is `Same as accumulator`.

## **CustomOutputDataType**

Output word and fraction lengths

Specify the output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when the `OutputDataType` property is `Custom`. The default is `numericType([],16,15)`.

## **Methods**

<code>clone</code>	Create FIR sample rate convertor object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method

<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>reset</code>	Reset states of FIR sample rate converter
<code>step</code>	Resample input with FIR rate converter

## Examples

Resample a 100 Hz sine wave signal by a factor of 3:2:

```
hsin = dsp.SineWave(1, 100, 'SampleRate', 5000, 'SamplesPerFrame', 50);

% Create a FIR rate converter filter. The default interpolation
% factor is 3 and decimation factor is 2.
hfirrc = dsp.FIRRateConverter;
input = step(hsin);
output = step(hfirrc, input);

% Plot the original and resampled signals.
ndelay = round(length(hfirrc.Numerator)/2/hfirrc.DecimationFactor);
indx = ndelay+1:length(output);
x = (0:length(indx)-1)/hsin.SampleRate*hfirrc.DecimationFactor/hfirrc.
stem((0:38)/hsin.SampleRate, input(1:39)); hold on;
stem(x, hfirrc.InterpolationFactor*output(indx), 'r');
legend('Original', 'Resampled');
```

---

Resample and play an audio signal from 48 kHz to 32 kHz (Windows only):

```
if ispc %This example runs only on Windows
    hmfr = dsp.AudioFileReader('audio48kHz.wav', ...
```

# dsp.FIRRateConverter

---

```
'OutputDataType', 'single', ...
'SamplesPerFrame', 300);
hap = dsp.AudioPlayer(32000);

% Create an FIRRateConverter System object with interpolation
% factor = 2, decimation factor = 3. Default FIR filter
% coefficients define a lowpass filter with normalized
% cutoff frequency of 1/3.
hfirrc = dsp.FIRRateConverter(2,3);

while ~isDone(hmfr)
    audio1 = step(hmfr);
    audio2 = step(hfirrc, audio1);
    step(hap, audio2);
end

release(hmfr);
release(hap);

else
    disp('This example runs only on Windows platforms.');
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the FIR Rate Conversion block reference page. The object properties correspond to the block parameters.

## See Also

[dsp.FIRInterpolator](#) | [dsp.FIRDecimator](#)

**Purpose** Create FIR sample rate convertor object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates an FIR sample rate converter object, `C`, with the same property values as `H`. The clone method creates a new unlocked object with uninitialized states.

# dsp.FIRRateConverter.getNumInputs

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.FIRRateConverter.getNumOutputs

---

**Purpose**

Number of outputs of step method

**Syntax**

`N = getNumOutputs(H)`

**Description**

`N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# **dsp.FIRRateConverter.isLocked**

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the FIR sample rate converter. The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

# dsp.FIRRateConverter.reset

---

**Purpose** Reset states of FIR sample rate converter

**Syntax** reset(H)

**Description** reset(H) resets the filter states of the FIR filter in the sample rate converter, H, to their initial values of 0. The initial filter state values correspond to the initial conditions for the constant coefficient linear difference equation defining the FIR filter. After the step method applies the FIR rate converter to nonzero input data, the states may be nonzero. Invoking the step method again without first invoking the reset method may produce different outputs for an identical input.

Reset filter states to 0 to produce consistent output:

```
H = dsp.FIRRateConverter(2,4);
x =[1 -1]'; x = repmat(x,8,1);
y = step(H,x); % Filter states are nonzero
% Use reset method to set states to zero
reset(H);
% Apply sampling rate converter to input x
y1 = step(H,x);
isequal(y,y1)
% Returns a 1
```

**Purpose** Resample input with FIR rate converter

**Syntax**  $Y = \text{step}(H, X)$

**Description**  $Y = \text{step}(H, X)$  resamples the input  $X$  and returns the resampled signal  $Y$ . An  $M$ -by- $N$  matrix input is treated as  $N$  independent channels.

# dsp.Histogram

---

**Purpose** Histogram of input or sequence of inputs

**Description** The Histogram object generates a histogram for an input or a sequence of inputs.

To generate a histogram for an input or a sequence of inputs:

- 1 Define and set up your histogram object. See “Construction” on page 5-522.
- 2 Call `step` to generate the histogram for an input according to the properties of `dsp.Histogram`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.Histogram` returns a histogram object, `H`, that computes the frequency distribution of the elements in each input matrix.

`H = dsp.Histogram('PropertyName',PropertyValue, ...)` returns a histogram object, `H`, with each specified property set to the specified value.

`H = dsp.Histogram(MIN,MAX,NUMBINS,'PropertyName',PropertyValue,...)` returns a histogram object, `H`, with the `LowerLimit` property set to `MIN`, `UpperLimit` property set to `MAX`, `NumBins` property set to `NUMBINS` and other specified properties set to the specified values.

## Properties

### LowerLimit

Lower boundary

Specify the lower boundary of the lowest-valued bin as a real-valued scalar. NaN and Inf are not valid values for this property. The default is 0. This property is tunable.

### UpperLimit

Upper boundary

Specify the upper boundary of the highest-valued bin as a real-valued scalar. NaN and Inf are not valid values for this property. The default is 10. This property is tunable.

## **NumBins**

Number of bins in histogram

Specify the number of bins in the histogram. The default is 11.

## **Dimension**

Specify how the histogram calculation is performed over the data as one of | All | Column |. The default is Column.

## **Normalize**

Enable output vector normalization

Specify whether the histogram object normalizes the output vector,  $v$ , so that  $sum(v) = 1$ . When you set this property to true, the output vector is normalized. When you set it to false, the object supports fixed-point operations and does not use this property for normalization. The default is false.

## **RunningHistogram**

Enable calculation over successive step method calls

Set this property to true to enable running histogram calculations for the input elements over successive calls to the step method. Set this property to false to compute a histogram for the current input. The default is false.

## **ResetInputPort**

Enable resetting in running histogram mode

Set this property to true to enable resetting the running histogram. When you set the property to true, specify a reset input to the step method that resets the running histogram. This property applies when you set the RunningHistogram property to true. When this property is false, the histogram object does not reset. The default is false.

## **ResetCondition**

Reset condition for running histogram mode

Specify the event that resets the running histogram as one of | Rising edge | Falling edge | Either edge | Non-zero |. This property applies when you set the ResetInputPort property to true. The default is Non-zero

## **Fixed-Point Properties**

### **RoundingMethod**

Rounding method for fixed-point operations

Specify the rounding method as one of | Ceiling | Convergent | Floor | Nearest | Round | Simplest | Zero |. The default is Floor.

### **OverflowAction**

Overflow action for fixed-point operations

Specify the overflow action as one of | Wrap | Saturate |. The default is Wrap.

### **ProductDataType**

Product word and fraction lengths

Specify the product fixed-point data type as one of | Same as input | Custom |. The default is Same as input.

### **CustomProductDataType**

Custom product word and fraction lengths

Specify the product fixed-point type as a scaled numeric type object with a Signedness of Auto. This property applies when you set the ProductDataType property to Custom. The default is numeric type ([ ], 32, 30).

### **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point data type as one of | Same as product | Same as input | Custom |. The default is Same as input.

## CustomAccumulatorDataType

Custom accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `AccumulatorDataType` property to `Custom`. The default is `numericType([],32,30)`.

## Methods

<code>clone</code>	Create histogram object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>reset</code>	Reset histogram bin values to zero
<code>step</code>	Histogram for input data

## Examples

Compute a histogram with four bins, for possible input values 1 through 4:

```
hhist = dsp.Histogram(1,4,4);
y = step(hhist, [1 2 2 3 3 3 4 4 4 4]');
% y equals [1; 2; 3; 4] - one one, two twos, etc.
```

# dsp.Histogram

---

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Histogram block reference page. The object properties correspond to the block parameters, except:

- The **Reset port** block parameter corresponds to both the `ResetCondition` and the `ResetInputPort` object properties.
- The **Find histogram over** block parameter corresponds to the `Dimension` property of the object.

## See Also

`dsp.Maximum` | `dsp.Minimum` | `dsp.Mean`

**Purpose** Create histogram object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a Histogram System object `C`, with the same property values as `H`. The clone method creates a new unlocked object with uninitialized states.

# dsp.Histogram.getNumInputs

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose** Number of outputs of step method

**Syntax** `N = getNumOutputs(H)`

**Description** `N = getNumOutputs(H)` returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# dsp.Histogram.isLocked

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the Histogram System object. The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

## **dsp.Histogram.reset**

---

**Purpose**            Reset histogram bin values to zero

**Syntax**            reset(H)

**Description**        reset(H) sets the Histogram object bin values to zero when you set the RunningHistogram property to true.

**Purpose** Histogram for input data

**Syntax**  
 $Y = \text{step}(H,X)$   
 $Y = \text{step}(H,X,R)$

**Description**  $Y = \text{step}(H,X)$  returns a histogram  $Y$  for the input data  $X$ . When the `RunningHistogram` property is `true`,  $Y$  corresponds to the histogram of the input elements over successive calls to the `step` method.

$Y = \text{step}(H,X,R)$  resets the histogram state based on the value of  $R$  and the object's `ResetCondition` property. You can reset the histogram state only when the `RunningHistogram` and the `ResetInputPort` properties are `true`.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

## Purpose

Inverse discrete cosine transform (IDCT)

## Description

The IDCT object computes the inverse discrete cosine transform (IDCT) of an input.

To compute the IDCT of an input:

- 1 Define and set up your IDCT object. See “Construction” on page 5-534.
- 2 Call `step` to compute the IDCT of an input according to the properties of `dsp.IDCT`. The behavior of `step` is specific to each object in the toolbox.

## Construction

`H = dsp.IDCT` returns an inverse discrete cosine transform (IDCT) object, `H`. This object computes the IDCT of a real or complex input signal using the `Table lookup` method.

`H = dsp.IDCT('PropertyName',PropertyValue,...)` returns an inverse discrete cosine transform (IDCT) object, `H`, with each property set to the specified value.

## Properties

### SineComputation

Method to compute sines and cosines

Specify how the IDCT object computes the trigonometric function values as `Trigonometric function` or `Table lookup`. You must set this property to `Table lookup` for fixed-point inputs. The default is `Table lookup`.

### Fixed-Point Properties

#### RoundingMethod

Rounding method for fixed-point operations

Specify the rounding method as one of `Ceiling`, `Convergent`, `Floor`, `Nearest`, `Round`, `Simplest`, or `Zero`. This property applies when you set the `SineComputation` property to `Table lookup`.

**OverflowAction**

Overflow action for fixed-point operations

Specify the overflow action as one of `Wrap` or `Saturate`. This property applies when you set the `SineComputation` property to `Table lookup`.

**SineTableDataType**

Sine table word-length designation

Specify the sine table fixed-point data type as one of `Same word length as input` or `Custom`. This property applies when you set the `SineComputation` property to `Table lookup`.

**CustomSineTableDataType**

Sine table word length

Specify the sine table fixed-point type as a signed, unscaled `numericType` object. This property applies when you set the `SineComputation` property to `Table lookup` and the `SineTableDataType` property to `Custom`. The default is `numericType(true,16)`.

**ProductDataType**

Product word and fraction lengths

Specify the product fixed-point data type as one of `Full precision`, `Same as input`, `Custom`. This property applies when you set the `SineComputation` property to `Table lookup`.

**CustomProductDataType**

Product word and fraction lengths

Specify the product fixed-point type as a signed, scaled `numericType` object. This property applies when you set the `SineComputation` property to `Table lookup` and the `ProductDataType` property to `Custom`. The default is `numericType(true,32,30)`.

## **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point data type as one of `Full precision`, `Same as input`, `Same as product`, or `Custom`. This property applies when you set the `SineComputation` property to `Table lookup`.

## **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a signed, scaled `numericType` object. This property applies when you set the `SineComputation` property to `Table lookup` and the `AccumulatorDataType` property to `Custom`. The default is `numericType(true,32,30)`.

## **OutputDataType**

Output word and fraction lengths

Specify the output fixed-point data type as one of `Full precision`, `Same as input`, `Custom`. This property applies when you set the `SineComputation` property to `Table lookup`. The default is `Full precision`.

## **CustomOutputDataType**

Output word and fraction lengths

Specify the output fixed-point type as a signed, scaled `numericType` object. This property applies when you set the `SineComputation` property to `Table lookup` and the `OutputDataType` property to `Custom`. The default is `numericType(true,16,15)`.

**Methods**

clone	Create inverse discrete cosine transform object with same property values
getNumInputs	Number of expected inputs to step method
getNumOutputs	Number of outputs of step method
isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
step	Inverse discrete cosine transform (IDCT) of input

**Examples**

Use DCT to analyze the energy content in a sequence:

```
x = (1:128).' + 50*cos((1:128).'*2*pi/40);
hdct = dsp.DCT;

X = step(hdct, x);
% Set the DCT coefficients which represent less
% than 0.1% of the total energy to 0 and
% reconstruct the sequence using IDCT.
[XX, ind] = sort(abs(X),1,'descend');
ii = 1;

while (norm([XX(1:ii);zeros(128-ii,1)]) <= 0.999*norm(XX))
    ii = ii+1;
end

disp(['Number of DCT coefficients that represent 99.9%',...
'of the total energy in the sequence: ',num2str(ii)]);
XXt = zeros(128,1);
XXt(ind(1:ii)) = X(ind(1:ii));
```

```
hidct = dsp.IDCT;  
xt = step(hidct, XXt);  
  
plot(1:128,[x xt]);  
legend('Original signal','Reconstructed signal',...  
      'location','best');
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the IDCT block reference page. The object properties correspond to the block parameters.

## See Also

dsp.DCT | dsp.FFT | dsp.IFFT.

**Purpose** Create inverse discrete cosine transform object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a copy of the current IDCT object, `C`, with the same property values as `H`. The clone method creates a new unlocked object.

# dsp.IDCT.getNumInputs

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# dsp.IDCT.isLocked

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the IDCT object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

## dsp.IDCT.step

---

**Purpose** Inverse discrete cosine transform (IDCT) of input

**Syntax**  $Y = \text{step}(H,X)$

**Description**  $Y = \text{step}(H,X)$  computes the inverse discrete cosine transform,  $Y$ , of input  $X$ .

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

---

<b>Purpose</b>	Inverse discrete Fourier transform (IDFFT)
<b>Description</b>	<p>The IFFT object computes the inverse discrete Fourier transform (IDFFT) of the input. The object uses one or more of the following fast Fourier transform (FFT) algorithms depending on the complexity of the input and whether the output is in linear or bit-reversed order:</p> <ul style="list-style-type: none"><li>• Double-signal algorithm</li><li>• Half-length algorithm</li><li>• Radix-2 decimation-in-time (DIT) algorithm</li><li>• Radix-2 decimation-in-frequency (DIF) algorithm</li><li>• An algorithm chosen by FFTW [1], [2]</li></ul> <p>To compute the IFFT of the input:</p> <ol style="list-style-type: none"><li>1 Define and set up your IFFT object. See “Construction” on page 5-545.</li><li>2 Call <code>step</code> to compute the IFFT of the input according to the properties of <code>dsp.IFFT</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.IFFT</code> returns an IFFT object, <code>H</code>, that computes the IDFT of a column vector or <math>N</math>-D array. For column vectors or <math>N</math>-D arrays, the IFFT object computes the IDFT along the first dimension of the array. If the input is a row vector, the IFFT object computes a row of single-sample IDFTs and issues a warning.</p> <p><code>H = dsp.IFFT('PropertyName',PropertyValue, ...)</code> returns an IFFT object, <code>H</code>, with each property set to the specified value.</p>
<b>Properties</b>	<p><b>FFTImplementation</b></p> <p>FFT implementation</p>

Specify the implementation used for the FFT as one of `Auto` | `Radix-2` | `FFTW`. When you set this property to `Radix-2`, the FFT length must be a power of two.

## **BitReversedInput**

Enable bit-reversed order interpretation of input elements

Set this property to `true` if the order of Fourier transformed input elements to the IFFT object are in bit-reversed order. This property applies only when the `FFTLengthSource` property is `Auto`. The default is `false`, which denotes linear ordering.

## **ConjugateSymmetricInput**

Enable conjugate symmetric interpretation of input

Set this property to `true` if the input is conjugate symmetric to yield real-valued outputs. The discrete Fourier transform of a real valued sequence is conjugate symmetric, and setting this property to `true` optimizes the IDFT computation method. Setting this property to `false` for conjugate symmetric inputs may result in complex output values with nonzero imaginary parts. This occurs due to rounding errors. Setting this property to `true` for nonconjugate symmetric inputs results in invalid outputs. This property applies only when the `FFTLengthSource` property is `Auto`. The default is `false`.

## **Normalize**

Enable dividing output by FFT length

Specify whether to divide the IFFT output by the FFT length. The default is `true` and each element of the output is divided by the FFT length.

## **FFTLengthSource**

Source of FFT length

Specify how to determine the FFT length as `Auto` or `Property`. When you set this property to `Auto`, the FFT length equals the number of rows of the input signal. This property applies only

when both the `BitReversedInput` and `ConjugateSymmetricInput` properties are false. The default is `Auto`.

### **FFTLength**

FFT length

Specify the FFT length as a numeric scalar. This property applies when you set the `BitReversedInput` and `ConjugateSymmetricInput` properties to false, and the `FFTLengthSource` property to `Property`. The default is 64.

This property must be a power of two when the input is a fixed-point data type, or when you set the `FFTImplementation` property to `Radix-2`.

When you set the FFT implementation property to `Radix-2`, or when you set the `BitReversedOutput` property to true, this value must be a power of two.

### **Fixed-Point Properties**

#### **RoundingMethod**

Rounding method for fixed-point operations

Specify the rounding method as `Ceiling`, `Convergent`, `Floor`, `Nearest`, `Round`, `Simplest`, or `Zero`. The default is `Floor`.

#### **OverflowAction**

Overflow action for fixed-point operations

Specify the overflow action as `Wrap` or `Saturate`. The default is `Wrap`.

#### **SineTableDataType**

Sine table word and fraction lengths

Specify the sine table data type as `Same word length as input` or `Custom`. The default is `Same word length as input`.

#### **CustomSineTableDataType**

Sine table word and fraction lengths

Specify the sine table fixed-point type as an unscaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `SineTableDataType` property to `Custom`. The default is `numericType([],16)`.

## **ProductDataType**

Product word and fraction lengths

Specify the product data type as `Full precision`, `Same as input`, or `Custom`. The default is `Full precision`.

## **CustomProductDataType**

Product word and fraction lengths

Specify the product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `ProductDataType` property to `Custom`. The default is `numericType([],32,30)`.

## **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator data type as `Full precision`, `Same as input`, `Same as product`, or `Custom`. The default is `Full precision`.

## **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `AccumulatorDataType` property to `Custom`. The default is `numericType([],32,30)`.

## **OutputDataType**

Output word and fraction lengths

Specify the output data type as `Full` precision, `Same as input`, or `Custom`. The default is `Full` precision.

### CustomOutputDataType

Output word and fraction lengths

Specify the output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `OutputDataType` property to `Custom`. The default is `numericType([],16,15)`.

## Methods

<code>clone</code>	Create IFFT object with same property values
<code>getNumInputs</code>	Number of expected inputs to <code>step</code> method
<code>getNumOutputs</code>	Number of outputs of <code>step</code> method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>step</code>	Inverse discrete Fourier transform of input

## Examples

Use DFT and IDFT to analyze the energy content in a sequence:

```
Fs = 40; L = 128;
t = (0:L-1)'/Fs;
x = sin(2*pi*10*t) + 0.75*cos(2*pi*15*t);
y = x + .5*randn(size(x)); % noisy signal
hfft = dsp.FFT;
hifft = dsp.IFFT('ConjugateSymmetricInput', true);
X = step(hifft, x);
[XX, ind] = sort(abs(X),1,'descend');
XXn = sqrt(cumsum(XX.^2))/norm(XX);
```

# dsp.IFFT

---

```
ii = find(XXn > 0.999, 1);
disp('Number of FFT coefficients that represent 99.9% ')
disp(['of the total energy in the sequence: ', num2str(ii)]);
XXt = zeros(128,1);
XXt(ind(1:ii)) = X(ind(1:ii));
xt = step(hifft, XXt);
% Verify the reconstructed signal matches the original
norm(x-xt)
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the IFFT block reference page. The object properties correspond to the block parameters, except:

**Output sampling mode** parameter is not supported by dsp.IFFT.

## References

- [1] FFTW (<http://www.fftw.org>)
- [2] Frigo, M. and S. G. Johnson, "FFTW: An Adaptive Software Architecture for the FFT," *Proceedings of the International Conference on Acoustics, Speech, and Signal Processing*, Vol. 3, 1998, pp. 1381-1384.

## See Also

dsp.FFT | dsp.DCT | dsp.IDCT

**Purpose** Create IFFT object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates an IFFT object, `C`, with the same property values as `H`. The clone method creates a new unlocked object.

# dsp.IFFT.getNumInputs

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# dsp.IFFT.isLocked

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the IFFT object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

# dsp.IFFT.step

---

**Purpose** Inverse discrete Fourier transform of input

**Syntax**  $Y = \text{step}(H,X)$

**Description**  $Y = \text{step}(H,X)$  computes the inverse discrete Fourier transform (IDFT),  $Y$ , of the input  $X$  along the first dimension of  $X$ . When the `FFTLengthSource` property is `Auto`, the length of  $X$  along the first dimension must be a positive integer power of two. When the `FFTLengthSource` property is `'Property'`, the length of  $X$  along the first dimension can be any positive integer and the `FFTLength` property must be a positive integer power of two.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

<b>Purpose</b>	Infinite Impulse Response (IIR) filter
<b>Description</b>	<p>The <code>IIRFilter</code> object filters each channel of the input using IIR filter implementations.</p> <p>To filter each channel of the input:</p> <ol style="list-style-type: none"><li>1 Define and set up your IIR filter. See “Construction” on page 5-557.</li><li>2 Call <code>step</code> to filter each channel of the input according to the properties of <code>dsp.IIRFilter</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>HIIR = dsp.IIRFilter</code> returns an IIR filter System object, <code>HIIR</code>, which independently filters each channel of the input over successive calls to the <code>step</code> method. This System object uses a specified IIR filter implementation.</p> <p><code>HIIR = dsp.IIRFilter('PropertyName',PropertyValue, ...)</code> returns an IIR filter System object, <code>HIIR</code>, with each property set to the specified value.</p>
<b>Properties</b>	<p><b>Structure</b></p> <p>Filter structure</p> <p>Specify the filter structure.</p> <p>You can specify the filter structure as one of   Direct form I   Direct form I transposed   Direct form II   Direct form II transposed. The default is Direct form II transposed. This property is nontunable.</p> <p><b>Numerator</b></p> <p>Filter numerator coefficients</p> <p>Specify the numerator coefficients as a real or complex numeric row vector. The default is [1 1]. This property is tunable.</p>

## Denominator

Filter denominator coefficients

Specify the denominator coefficients as a real or complex numeric row vector. The default value of this property is `[1 0.1]`. This property is tunable.

## InitialConditions

Initial conditions for the IIR filter

Specify the initial conditions of the filter states. This property is applicable when the structure is one of `Direct form II` | `Direct form II transposed`. The default value is 0. The number of states equals the  $\max(N,M) - 1$ , where N and M are the number of poles and zeros respectively.

You can specify the initial conditions as a scalar, vector, or matrix. If you specify a scalar value, this System object initializes all delay elements in the filter to that value. You can also specify a vector whose length equals the number of delay elements in the filter. When you do so, each vector element specifies a unique initial condition for the corresponding delay element. The object applies the same vector of initial conditions to each channel of the input signal.

You can also specify a matrix with the same number of rows as the number of delay elements in the filter and one column for each channel of the input signal. In this case, each element specifies a unique initial condition for the corresponding delay element in the corresponding channel. This property is tunable.

## NumeratorInitialConditions

Initial conditions on zeros side

Specify the initial conditions of the filter states on the side of the filter structure with the zeros. This property is applicable when the Structure property is one of `Direct form I` | `Direct form I transposed`. The default value of this property is 0. The number

of states equals the  $\max(N, M) - 1$ , where  $N$  and  $M$  are the number of poles and zeros respectively.

You can specify the initial conditions as a scalar, vector, or matrix. When you specify a scalar, the IIR filter initializes all delay elements on the zeros side in the filter to that value. You can specify a vector of length equal to the number of delay elements on the zeros side in the filter. When you do so, each vector element specifies a unique initial condition for the corresponding delay element on the zeros side.

You can also specify a matrix with the same number of rows as the number of delay elements on the zeros side in the filter, and one column for each channel of the input signal. In this case, each element specifies a unique initial condition for the corresponding delay element on the zeros side in the corresponding channel. This property is tunable.

### **DenominatorInitialConditions**

Initial conditions on poles side

Specify the initial conditions of the filter states on the side of the filter structure with the poles. This property is applicable when the Structure property is one of `Direct form I` | `Direct form I transposed`. The default value of this property is 0. The number of states equals the  $\max(N, M) - 1$ , where  $N$  and  $M$  are the number of poles and zeros respectively.

You can specify the initial conditions as a scalar, vector, or matrix. When you specify a scalar, the IIR filter initializes all delay elements on the poles side of the filter to that value. You can specify a vector of length equal to the number of delay elements on the poles side in the filter. When you do so, each vector element specifies a unique initial condition for the corresponding delay element on the poles side.

You can also specify a matrix with the same number of rows as the number of delay elements on the poles side in the filter, and one column for each channel of the input signal. In this case, each

element specifies a unique initial condition for the corresponding delay element on the poles side in the corresponding channel. This property is tunable.

## **FrameBasedProcessing**

Process input as frames or as samples

Set this property to `true` to enable frame-based processing. When this property is `true`, the IIR filter treats each column as an independent channel. Set this property to `false` to enable sample-based processing. When this property is `false`, the IIR filter treats each element of the input as an individual channel. The default is `true`. This property is nontunable.

## **NumeratorCoefficientsDataType**

Numerator coefficients word- and fraction-length designations

Specify the numerator coefficients fixed-point data type as one of `Same word length as input` | `Custom`. The default is `Same word length as input`. This property is nontunable.

## **DenominatorCoefficientsDataType**

Denominator coefficients word- and fraction-length designations

Specify the denominator coefficients fixed-point data type as one of `Same word length as input` | `Custom`. The default is `Same word length as input`. This property is nontunable.

## **Fixed-Point Properties**

### **NumeratorProductDataType**

Product word- and fraction-length designations on zeros side

Specify the numerator product fixed-point data type as one of | `Full precision` | `Same as input` | `Custom` |. The default is `Full precision`. This property is nontunable.

### **DenominatorProductDataType**

Product word- and fraction-length designations on poles side

Specify the denominator product fixed-point data type as one of | Full precision | Same as input | Custom |. The default is Full precision. This property is nontunable.

### **NumeratorAccumulatorDataType**

Accumulator word- and fraction-length designations on zeros side

Specify the numerator accumulator fixed-point data type to one of | Full precision | Same as input | Same as product | Custom |. The default is Full precision. This property is nontunable.

### **DenominatorAccumulatorDataType**

Accumulator word- and fraction-length designations on poles side

Specify the denominator accumulator fixed-point data type to one of | Full precision | Same as input | Same as product | Custom |. The default is Full precision. This property is nontunable.

### **OutputDataType**

Output word- and fraction-length designations

Specify the output fixed-point data type as one of | Full precision | Same as input | Custom |. The default is Same as input. This property is nontunable.

### **StateDataType**

State word- and fraction-length designations

Specify the state fixed-point data type as one of | Same as input | Custom |. This property does not apply to Direct form I filter structure. The default is Same as input. This property is nontunable.

### **MultiplicandDataType**

Multiplicand word- and fraction-length designations

Specify the multiplicand fixed-point data type as one of | Same as input | Custom |. This property is applicable only when the Structure property is Direct form I transposed. The default is Same as input. This property is nontunable.

## **CustomNumeratorCoefficientsDataType**

Numerator coefficients word- and fraction-lengths

Specify the numerator coefficients fixed-point type as an autosigned numeric type object. This property is applicable when the NumeratorCoefficientsDataType property is Custom. The default value of this property is numeric type ([,16,15]). This property is nontunable.

## **CustomDenominatorCoefficientsDataType**

Denominator coefficients word- and fraction-lengths

Specify the denominator coefficients fixed-point type as an autosigned numeric type object. This property is applicable when the DenominatorCoefficientsDataType property is Custom. The default value of this property is numeric type ([, 16, 15) . This property is nontunable.

## **CustomNumeratorProductDataType**

Custom product word- and fraction-lengths on zeros side

Specify the numerator product fixed-point type as an autosigned scaled numeric type object. This property applies when you set the NumeratorProductDataType property to Custom. The default is numeric type ([,32,30). This property is nontunable.

## **CustomDenominatorProductDataType**

Custom product word- and fraction-lengths on poles side

Specify the denominator product fixed-point type as an autosigned scaled numeric type object. This property applies when you set the DenominatorProductDataType property to Custom. The default is numeric type ([,32,30). This property is nontunable.

## **CustomNumeratorAccumulatorDataType**

Custom accumulator word- and fraction-lengths on zeros side

Specify the numerator accumulator fixed-point type as an autosigned scaled `numericType` object. This property applies when you set the `NumeratorAccumulatorDataType` property to `Custom`. The default is `numericType([],32,30)`. This property is nontunable.

## **CustomDenominatorAccumulatorDataType**

Custom accumulator word- and fraction-lengths on poles side

Specify the denominator accumulator fixed-point type as an autosigned scaled `numericType` object. This property applies when you set the `DenominatorAccumulatorDataType` property to `Custom`. The default is `numericType([],32,30)`. This property is nontunable.

## **CustomStateDataType**

Custom state word- and fraction-lengths

Specify the state fixed-point type as an autosigned scaled `numericType` object. This property applies when you set the `StateDataType` property to `Custom`. The default is `numericType([],16,15)`. This property is nontunable.

## **CustomOutputDataType**

Custom output word- and fraction-lengths

Specify the output fixed-point type as an autosigned scaled `numericType` object. This property applies when you set the `OutputDataType` property to `Custom`. The default is `numericType([],16,15)`. This property is nontunable.

## **CustomMultiplicandDataType**

Custom multiplicand word- and fraction-lengths

Specify the multiplicand fixed-point type as an autosigned scaled `numericType` object. This property applies when you set

the `MultiplicandDataType` property to `Custom`. The default is `numericType([],16,15)`. This property is nontunable.

## Methods

<code>clone</code>	Create IIR filter with same property values
<code>freqz</code>	Frequency response
<code>fvtool</code>	Open filter visualization tool
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>impz</code>	Impulse response
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>phasez</code>	Unwrapped phase response
<code>release</code>	Allow property value and input characteristics changes
<code>reset</code>	Reset internal states of IIR filter
<code>step</code>	Filter input with IIR filter object

More “Analysis Methods for Filter System Objects” on page 4-2.

## Examples

Use an IIR filter to apply a lowpass filter to a waveform with two sinusoidal frequencies.

```
t = [0:63] ./ 32e3;  
xin = (sin(2*pi*4e3*t) + sin(2*pi*12e3*t)) / 2;  
  
hSR = dsp.SignalSource(xin', 4);  
hLog = dsp.SignalSink;  
hIIR = dsp.IIRFilter;  
[b,a] = butter(6,0.5);
```

```
hIIR.Numerator = b;  
hIIR.Denominator = a;  
  
while ~isDone(hSR)  
    input = step(hSR);  
    filteredOutput = step(hIIR,input);  
    step(hLog,filteredOutput);  
end  
  
filteredResult = hLog.Buffer;  
sper = spectrum.periodogram;  
psd(sper,filteredResult,'Fs',32e3)
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Discrete Filter block reference page. The object properties correspond to the block parameters.

Both this object and its corresponding block let you specify whether to process inputs as individual samples or as frames of data. The object uses the `FrameBasedProcessing` property. The block uses the **Input processing** parameter. See “Set the FrameBasedProcessing Property of a System object” for more information.

## See Also

`dsp.BiquadFilter` | `dsp.FIRFilter` | `dsp.AllpoleFilter`

## **dsp.IIRFilter.clone**

---

**Purpose** Create IIR filter with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a IIR filter object, `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with uninitialized states.

**Purpose** Frequency response

**Syntax**  
`[h,w] = freqz(H)`  
`[h,w] = freqz(H,n)`  
`[h,w] = freqz(H,Name,Value)`  
`freqz(H)`

**Description** `[h,w] = freqz(H)` returns the complex, 8192–element frequency response vector `h`, and the corresponding frequencies `w` in radians/sample.

`[h,w] = freqz(H,n)` returns the complex, `n`-element frequency response vector `h`, and the corresponding frequencies `w` in radians/sample, using `n` samples.

`[h,w] = freqz(H,Name,Value)` returns the frequency response and the corresponding frequencies, with additional options specified by one or more `Name, Value` pair arguments.

`freqz(H)` uses FVTool to plot the magnitude and unwrapped phase of the frequency response of the filter System object `H`.

# dsp.IIRFilter.fvtool

---

**Purpose** Open filter visualization tool

**Syntax** fvtool(H)  
fvtool(H, 'Arithmetic', ARITH, ...)

**Description** fvtool(H) performs an analysis and computes the magnitude response of the filter System object H.

fvtool(H, 'Arithmetic', ARITH, ...) analyzes the filter System object H, based on the arithmetic specified in the ARITH input. ARITH can be set to one of 'double', 'single', or 'fixed'. The analysis tool assumes a double precision filter when the arithmetic input is not specified and the filter System object is in an unlocked state. The 'Arithmetic' input is only relevant for the analysis of filter System objects.

**Purpose**                      Number of expected inputs to step method

**Syntax**                      `N = getNumInputs(H)`

**Description**                `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.IIRFilter.getNumOutputs**

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Impulse response

**Syntax**  
`[h,t] = impz(H)`  
`[h,t] = impz(H,Name,Value)`  
`impz(H)`

**Description** `[h,t] = impz(H)` returns the impulse response `h`, and the corresponding time points `t` at which the impulse response of `H` is computed.

`[h,t] = impz(H,Name,Value)` returns the impulse response `h`, and the corresponding time points `t`, with additional options specified by one or more `Name, Value` pair arguments.

`impz(H)` uses `FVTool` to plot the impulse response of the filter System object `H`.

---

**Note** You can use `impz` for both real and complex filters. When you omit the output arguments, `impz` plots only the real part of the impulse response.

---

# **dsp.IIRFilter.isLocked**

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the IIR filter.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Unwrapped phase response

**Syntax**

```
[phi,w] = phasez(H)  
[phi,w] = phasez(H,n)  
[phi,w] = phasez(H,Name,Value)  
phasez(H)
```

**Description**

`[phi,w] = phasez(H)` returns the 8192–element phase response vector `phi`, and the corresponding frequencies `w` in radians/sample.

`[phi,w] = phasez(H,n)` returns the `n`-element phase response vector `phi`, and the corresponding frequencies `w` in radians/sample, using `n` samples.

`[phi,w] = phasez(H,Name,Value)` returns the phase response and the corresponding frequencies, with additional options specified by one or more `Name, Value` pair arguments.

`phasez(H)` uses FVTool to plot the phase response of the filter System object `H`.

# dsp.IIRFilter.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Reset internal states of IIR filter

**Syntax** reset(H)

**Description** reset(H) resets the filter states of the IIR filter object, H, to their initial values of 0. The initial filter state values correspond to the initial conditions for the difference equation defining the filter. After the step method applies the IIR filter object to nonzero input data, the states may be nonzero. Invoking the step method again without first invoking the reset method may produce different outputs for an identical input.

For example:

```
H = dsp.IIRFilter;
[b,a] = ellip(20, 0.5, 80, 0.25);
H.Numerator = b;
H.Denominator = a;
n = 0:100;
x = cos(0.2*pi*n)+sin(0.8*pi*n);
y = step(H,x);
% Filter states are nonzero
% Invoke step method again without resetting states
y1 = step(H,x);
isequal(y,y1) % returns 0
% Now reset filter states to 0
reset(H)
% Invoke step method
y2 = step(H,x);
isequal(y,y2) % returns a 1
```

# dsp.IIRFilter.step

---

**Purpose** Filter input with IIR filter object

**Syntax**  $Y = \text{step}(H, X)$

**Description**  $Y = \text{step}(H, X)$  filters the real or complex input signal  $X$  using the IIR filter,  $H$ , to produce the output  $Y$ . When the input data is of a fixed-point type, it must be signed. The IIR filter object operates on each channel of the input signal independently over successive calls to step method.

---

**Note** The object performs an initialization the first time the step method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the release method to unlock the object.

---

<b>Purpose</b>	Linear or FIR interpolation
<b>Description</b>	<p>The <code>Interpolator</code> object interpolates real-valued inputs using linear or polyphase FIR interpolation.</p> <p>To interpolate real-valued inputs:</p> <ol style="list-style-type: none"><li>1 Define and set up your interpolation object. See “Construction” on page 5-577.</li><li>2 Call <code>step</code> to interpolate the input according to the properties of <code>dsp.Interpolator</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.Interpolator</code> returns a handle to an interpolation object, <code>H</code>. The interpolation method defaults to <code>Linear</code> and the interpolation points default to a <math>5 \times 1</math> vector.</p> <p><code>H = dsp.Interpolator('PropertyName',PropertyValue,...)</code> returns an interpolation object, <code>H</code>, with the specified property name and value pairs.</p>
<b>Properties</b>	<p><b>InterpolationPointsSource</b></p> <p>Source of interpolation points</p> <p>You can select a value of <code>Property</code> or <code>Input port</code>. If you set this property to <code>Input port</code>, you must provide the interpolation points as an input to the <code>step</code> method when you interpolate the input. The default is <code>Property</code>.</p> <p><b>InterpolationPoints</b></p> <p>Interpolation points</p> <p>This property only applies when you set the <code>InterpolationPointsSource</code> property to <code>Property</code>. Specify the interpolation points as a column vector or a matrix with the same number of channels as the input.</p>

The valid range of the values in the interpolation vector is from 1 to the number of samples in each channel of the input. If you specify interpolation points outside the valid range, the object *clips* the point to the nearest point in the valid range. For example, if the input is [2 3.1 -2.1], the valid range of interpolation points is from 1 to 3. If you specify the following vector of interpolation points [-1 1.5 2 2.5 3 3.5], the interpolator object clips -1 to 1 and 3.5 to 3. This clipping results in the interpolation points [1 1.5 2 2.5 3 3]. The default is [1.1;4.8;2.67;1.6;3.2]. This property is tunable.

## Method

Interpolation method

Specify the interpolation method as `Linear` or `FIR`. When this property is `Linear`, the interpolator object interpolates data values by assuming that the data varies linearly between adjacent samples. When this property is `FIR`, the interpolator object uses polyphase interpolation to replace filtering (convolution) at the upsampled rate with a series of convolutions at the lower rate. The interpolator object always performs linear interpolation if there are insufficient low-rate samples to perform FIR interpolation as explained in the description of the `FilterHalfLength` property. The default is `Linear`.

## FilterHalfLength

Interpolation filter half length

This property applies only when you set the `Method` property to `FIR`. For a filter half length of  $P$ , the polyphase FIR subfilters have length  $2P$ . FIR interpolation always requires  $2P$  low-rate samples for every interpolation point.

- If the interpolation point does not correspond to a low-rate sample, FIR interpolation requires  $P$  low-rate samples below and  $P$  low-rate samples above the interpolation point.

- If the interpolation point corresponds to a low-rate sample, the  $2P$ -sample requirement includes the low-rate sample.
- If there are less than  $2P$  neighboring low-rate samples, the interpolator object uses linear interpolation.

For example, for an input [1 4 1 4 1 4 1 4], upsampling by a factor of four results in the equally spaced interpolation points `InterP = 1:0.25:8;`. The points `InterP(9:12)` are [3.0 3.25 3.5 3.75]. Assuming a `FilterHalfLength` property equal to 2, interpolating at these points uses the four low-rate samples from the input with indices (2,3,4,5). If you set the `FilterHalfLength` property to 4 in this case, the interpolator object uses linear interpolation because there are not enough low-rate samples to perform FIR interpolation.

The longer the `FilterHalfLength` property, the better the quality of the interpolation. However, the costs are increased computation and requiring more low-rate samples below and above the interpolation point. In general, setting the `FilterHalfLength` property between 4 and 6 provides reasonably accurate interpolation.

## **InterpolationPointsPerSample**

Interpolation points per input sample

This property only applies when you set the `Method` property to `FIR` and indicates the upsampling factor,  $L$ . An upsampling factor of  $L$  inserts  $L-1$  zeros between low-rate samples. Interpolation results from filtering the upsampled sequence with a lowpass anti-imaging filter. The interpolator object uses a polyphase FIR implementation with `InterpolationPointsPerSample` subfilters of length  $2P$ , where  $P$  is the `FilterHalfLength` property. Denoting the low-rate samples in the upsampled input by  $nL$ ,  $n=1,2,\dots$ , the interpolator object uses exactly one of the `InterpolationPointsPerSample` subfilters, or filter arms, to interpolate at the points  $nL+i/L$ , where  $i=0,1,2,\dots,L-1$ .

# dsp.Interpolator

---

If you specify interpolation points which do not correspond to a polyphase subfilter, the object rounds the point down to the nearest interpolation point associated with a polyphase subfilter. For example, you set the `InterpolationPointsPerSample` property to 4 and interpolate at the points [3 3.2 3.4 3.6 3.8]. The interpolator object uses the first polyphase subfilter for the points [3.0 3.2], the second subfilter for the point 3.4, the third subfilter for the point 3.6, and the fourth subfilter for the point 3.8.

## Bandwidth

Normalized input bandwidth

This property applies only when you set the `Method` property to FIR. The normalized bandwidth is a real-valued scalar between 0 and 1, where 1 equals the Nyquist frequency, or 1/2 the sampling frequency ( $F_s$ ). You may know that your input does not have frequency content above some cutoff frequency less than the Nyquist frequency. You can use this information to improve the FIR interpolation filters by relaxing the stopband requirements in frequency regions where the signal has no energy. For example, if the input signal does not have frequency content above  $F_s/8$ , you can specify a value of 0.25 for the `Bandwidth` property. The default value is 0.5.

## Methods

<code>clone</code>	Create interpolator object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties

release	Allow property value and input characteristics changes
step	Linear or FIR interpolation

## Definitions

A polyphase implementation of an FIR interpolation filter *splits* the lowpass FIR filter impulse response into a number of different subfilters. Let  $L$  represent the number of interpolation points per sample, or the upsampling factor, and  $P$  the half length of the polyphase subfilters. Indexing from zero, if  $h(n)$  is the impulse response of the FIR filter, the  $k$ -th subfilter is:

$$h_k(n) = h(k + nL) \quad k = 0, 1, \dots, L-1 \quad n = 0, 1, \dots, 2P-1$$

The following table describes the decomposition of an 18-coefficient FIR filter into 3 polyphase subfilters of length 6, the defaults for the FIR interpolator object:

Coefficients	Polyphase Subfilter
$h(0), h(3), h(6), \dots, h(15)$	$h_0(n)$
$h(1), h(4), h(7), \dots, h(16)$	$h_1(n)$
$h(2), h(5), h(8), \dots, h(17)$	$h_2(n)$

The following code shows how to find the polyphase subfilters for the default FIR interpolator object:

```
H = dsp.Interpolator('Method','FIR');
L = H.InterpolationPointsPerSample;
P = H.FilterHalfLength;
FiltCoeffs = intfilt(L,P,H.Bandwidth);
% Returns filter of length 2*P*L-1
FiltLen=length(FiltCoeffs);
FiltCols = ceil(FiltLen/2/L);
```

# dsp.Interpolator

---


```
% We need 2*P*L coefficients
% Prepending a zero does not affect the filter magnitude
FiltCoeffs = [zeros(FiltCols*2*L-FiltLen,1); FiltCoeffs(:)];

% Each column of PolyPhaseCoeffs is a polyphase subfilter
PolyPhaseCoeffs = reshape(FiltCoeffs,FiltCols,2*L)';
```

## Examples

Compare linear interpolation with FIR interpolation:

```
x =[1 4];
x = repmat(x,1,4);
x1 = 1:0.25:8;
hFIR =dsp.Interpolator('Method','FIR','FilterHalfLength',2,...
'InterpolationPoints',x1,'InterpolationPointsPerSample',4);
hLin =dsp.Interpolator('InterpolationPoints',x1');
OutFIR = step(hFIR,x');
OutLin = step(hLin,x');
stem(OutFIR,'b-.','linewidth',2); hold on;
stem(OutLin,'r','markerfacecolor',[1 0 0]);
axis([0 30 0 5]); legend('FIR','Linear','Location','Northeast');
```




For the indices 1 to 5 and 25 to 29, the interpolator object uses linear interpolation in both cases. The reason for this is that there are not enough low-rate samples surrounding the interpolation points at those indices to use FIR interpolation with the specified filter length.

Interpolate a sinusoid with linear interpolation:


```
t = 0:.0001:.0511;
x = sin(2*pi*20*t);
x1 = x(1:50:end);
I = 1:0.1:length(x1);
H = dsp.Interpolator('InterpolationPointsSource',...
    'Input port');
y = H.step(x1',I');
stem(I',y, 'r');
title('Original and Interpolated Signal');
hold on; stem(x1, 'Linewidth', 2);
legend('Interpolated','Original');
```

# dsp.Interpolator



Interpolate a sum of sinusoids with FIR interpolation and Input Port as the source of interpolation points:

```
Fs = 1000;
t = 0:(1/Fs):0.1-(1/Fs);
x = cos(2*pi*50*t)+0.5*sin(2*pi*100*t);
x1 = x(1:4:end);
I = 1:(1/4):length(x1);
% Decimate without aliasing
H = dsp.Interpolator('Method','FIR',...
'FilterHalfLength',3,'InterpolationPointsSource','Input Port');
y = H.step(x1,I);
stem(I,y,'r'); hold on;
axis([0 25 -2 2]);
stem(x1,'b','linewidth',2);
legend('Interpolated Signal','Original',...
'Location','Northeast');
```



## Algorithms

This object implements the algorithm, inputs, and outputs described on the Interpolation block reference page. The object properties correspond to the Simulink block parameters, except:

**Out of range interpolation points** — The interpolator object only has the `Clip` option. The Simulink block has the additional `Clip` and `warn` and `Error` options.

## See Also

`intfilt` | `dsp.FIRInterpolator` | `dsp.VariableFractionalDelay`

## **dsp.Interpolator.clone**

---

**Purpose** Create interpolator object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates an interpolator object, `C`, with the same property values as `H`. The clone method creates a new unlocked object with uninitialized states.

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.Interpolator.getNumOutputs**

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**      `N = getNumOutputs(H)` returns the number of outputs, N, of step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the interpolator.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.Interpolator.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Linear or FIR interpolation

**Syntax**  
`Y = step(H,X)`  
`Y = step(H,X,IPTS)`

**Description** `Y = step(H,X)` outputs the interpolated sequence, `Y`, of the input vector or matrix `X` as specified in the `InterpolationPoints` property.

`Y = step(H,X,IPTS)` outputs the interpolated sequence as specified by the input argument `IPTS` when the `InterpolationPointsSource` property is set to 'Input port'. `IPTS` a column vector or a matrix of interpolation points. If `IPTS` is a matrix, it must have the same number of channels as the input.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.LDLFactor

---

**Purpose** Factor square Hermitian positive definite matrices into components

**Description** The `LDLFactor` object factors square Hermitian positive definite matrices into lower, upper, and diagonal components. The object uses only the lower triangle of  $S$ .

To factor these matrices into lower, upper, and diagonal components:

- 1 Define and set up your LDL factor object. See “Construction” on page 5-592.
- 2 Call `step` to factor the matrices according to the properties of `dsp.LDLFactor`. The behavior of `step` is specific to each object in the toolbox.

**Construction**  $H = \text{dsp.LDLFactor}$  returns an LDL factor System object,  $H$ , that computes unit lower triangular  $L$  and diagonal  $D$  such that  $S = LDL'$  for square, symmetric/Hermitian, positive definite input matrix  $S$ .

$H = \text{dsp.LDLFactor}('PropertyName', PropertyValue, \dots)$  returns an LDL factor System object,  $H$ , with each specified property set to the specified value.

**Properties** **Fixed-Point Properties**

**AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point data type as `Full precision`, `Same as input`, `Same as product` or `Custom`. The default is `Full precision`

**CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled numeric type object with a `Signedness` of `Auto`. This property applies when you

set the `AccumulatorDataType` property to `Custom`. The default is `numericType([],32,30)`.

## **CustomIntermediateProductDataType**

Intermediate product word and fraction lengths

Specify the intermediate product fixed-point type as a signed, scaled `numericType` object. This property applies when you set the `IntermediateProductDataType` property to `Custom`. The default is `numericType(true,16,15)`.

## **CustomOutputDataType**

Output word and fraction lengths

Specify the output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `OutputDataType` property to `Custom`. The default is `numericType([],16,15)`.

## **CustomProductDataType**

Product word and fraction lengths

Specify the product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `ProductDataType` property to `Custom`. The default is `numericType([],32,30)`.

## **IntermediateProductDataType**

Intermediate product word and fraction lengths

Specify the intermediate product fixed-point data type as `Same as input` or `Custom`. The default is `Same as input`.

## **OutputDataType**

Output word and fraction lengths

Specify the output fixed-point data type as `Same as input` or `Custom`. The default is `Same as input`.

## **OverflowAction**

# dsp.LDLFactor

---

Overflow action for fixed-point operations

Specify the overflow action as one of `Wrap` or `Saturate`. The default is `Wrap`.

## ProductDataType

Product word and fraction lengths

Specify the product fixed-point data type as `Full precision`, `Same as input` or `Custom`. The default is `Full precision`.

## RoundingMethod

Rounding method for fixed-point operations

Specify the rounding method as: `Ceiling`, `Convergent`, `Floor`, `Nearest`, `Round`, `Simplest` or `Zero`. The default is `Floor`.

## Methods

<code>clone</code>	Create an LDL Factor object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs for step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>step</code>	Decompose matrix into components

## Examples

Decompose a square Hermitian positive definite matrix using LDL factor:

```
A = gallery('randcorr',5);  
hldl = dsp.LDLFactor;
```

```
y = step(hld1, A);
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the LDL Factorization block reference page. The object properties correspond to the block parameters, except:

No object property that corresponds to the **Non-positive definite input** block parameter. The object does not issue any alerts for nonpositive definite inputs. The output is not a valid factorization. A partial factorization is in the upper left corner of the output.

## See Also

dsp.LUFactor

## **dsp.LDLFactor.clone**

---

**Purpose** Create an LDL Factor object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates an LDLFactor System object `C`, with the same property values as `H`. The clone method creates a new unlocked object.

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the `step` method

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.LDLFactor.getNumOutputs

---

**Purpose**            Number of outputs for step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `LDLFactor` object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.LDLFactor.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Decompose matrix into components

**Syntax**  $Y = \text{step}(H,S)$

**Description**  $Y = \text{step}(H,S)$  decomposes the matrix  $S$  into lower, upper, and diagonal components. The output  $Y$  is a composite matrix with the  $L$  as its lower triangular part and  $D$  as the diagonal and  $L'$  as its upper triangular part. If  $S$  is not positive definite the output  $Y$  is not a valid factorization.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.LevinsonSolver

---

**Purpose** Solve linear system of equations using Levinson-Durbin recursion

**Description** The LevinsonSolver object solves linear systems of equations using Levinson-Durbin recursion.

To solve linear systems of equations using Levinson-Durbin recursion:

- 1 Define and set up your System object. See “Construction” on page 5-602.
- 2 Call `step` to solve the system of equations according to the properties of `dsp.LevinsonSolver`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.LevinsonSolver` returns a System object, `H`, that solves a Hermitian Toeplitz system of equations using the Levinson-Durbin recursion.

`H = dsp.LevinsonSolver('PropertyName',PropertyValue,...)` returns a Levinson-Durbin object, `H`, with each specified property set to the specified value.

**Properties** **AOutputPort**

Enable polynomial coefficients output

Set this property to `true` to output the polynomial coefficients  $A$ . Both `AOutputPort` and `KOutputPort` properties cannot be `false` at the same time. For scalar inputs, set the `AOutputPort` property to `true`. The default is `false`.

**KOutputPort**

Enable reflection coefficients output

Set this property to `true` to output the reflection coefficients  $K$ . You cannot set both the `AOutputPort` and `KOutputPort` properties to `false` at the same time. For scalar inputs, you must set the `KOutputPort` property to `false`. The default is `true`.

**PredictionErrorOutputPort**

Enable prediction error output

Set this property to `true` to output the prediction error. The default is `false`.

## **ZerothLagZeroAction**

Action when value of lag zero is zero

Specify the output for an input with the first coefficient as zero. Select `Ignore` or `Use zeros`. The default is `Use zeros`.

## **Fixed-Point Properties**

### **RoundingMethod**

Rounding method for fixed-point operations

Specify the rounding method as `Ceiling`, `Convergent`, `Floor`, `Nearest`, `Round`, `Simplest`, or `Zero`. The default is `Floor`.

### **OverflowAction**

Overflow action for fixed-point operations

Specify the overflow action as `Wrap`, `Saturate`. The default is `Wrap`.

### **ACoefficientDataType**

$A$  coefficient word and fraction lengths

This constant property has a value of `Custom`.

### **CustomACoefficientDataType**

$A$  coefficient word and fraction lengths

Specify the  $A$  coefficient fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. The default is `numericType([], 16, 15)`.

### **KCoefficientDataType**

$K$  coefficient word and fraction lengths

This constant property has a value of `Custom`.

## **CustomKCoefficientDataType**

$K$  coefficient word and fraction lengths

Specify the  $K$  coefficient fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. The default is `numericType([],16,15)`.

## **PredictionErrorDataType**

Prediction error power word and fraction lengths

Specify the prediction error power fixed-point data type as `Same as input` or `Custom`. The default is `Same as input`.

## **CustomPredictionErrorDataType**

Prediction error power word and fraction lengths

Specify the prediction error power fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when the `PredictionErrorDataType` property is `Custom`. The default is `numericType([],16,15)`.

## **ProductDataType**

Product word and fraction lengths

Specify the product fixed-point data type as `Same as input` or `Custom`. The default is `Custom`

## **CustomProductDataType**

Product word and fraction lengths

Specify the product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when the `ProductDataType` property is `Custom`. The default is `numericType([],32,30)`.

## **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the Accumulator fixed-point data type as Same as input, Same as product, or Custom. The default is Custom.

## CustomAccumulatorDataType

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled numeric type object with a Signedness of Auto. This property applies only when the AccumulatorDataType property is Custom. The default is numeric type([ ],32,30).

## Methods

clone	Create Levinson solver object with same property values
getNumInputs	Number of expected inputs to step method
getNumOutputs	Number of outputs of step method
isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
step	Reflection coefficients corresponding to columns of input

## Examples

Use the Levinson solver to compute polynomial coefficients from autocorrelation coefficients:

```
hlevinson = dsp.LevinsonSolver;  
hlevinson.AOutputPort = true;  
hlevinson.KOutputPort = false;  
x = (1:100)';  
hac = dsp.Autocorrelator(...  
    'MaximumLagSource', 'Property', ...  
    'MaximumLag', 10);
```

# dsp.LevinsonSolver

---

```
a = step(hac, x);  
c = step(hlevinson, a); % Compute polynomial coefficients
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Levinson-Durbin block reference page. The object properties correspond to the block parameters, except:

**Output(s)** block parameter corresponds to the AOutputPort and the KOutputPort object properties.

## See Also

dsp.Autocorrelator

<b>Purpose</b>	Create Levinson solver object with same property values
<b>Syntax</b>	<code>C = clone(H)</code>
<b>Description</b>	<code>C = clone(H)</code> creates a LevinsonSolver object System object C, with the same property values as H. The clone method creates a new unlocked object.

# dsp.LevinsonSolver.getNumInputs

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# **dsp.LevinsonSolver.isLocked**

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the LevinsonSolver System object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

# dsp.LevinsonSolver.step

---

**Purpose** Reflection coefficients corresponding to columns of input

**Syntax**

```
K = step(H,X)
A = step(H,X)
[A, K] = step(H,X)
[... , P] = step(H,X)
```

**Description** `K = step(H,X)` returns reflection coefficients `K` corresponding to the columns of input `X`. `X` is typically a column or matrix of autocorrelation coefficients with lag 0 as the first element.

`A = step(H,X)` returns polynomial coefficients `A` when the `AOutputPort` property is true and the `KOutputPort` property is false.

`[A, K] = step(H,X)` returns polynomial coefficients `A` and reflection coefficients `K` when both the `AOutputPort` and `KOutputPort` properties are true.

`[... , P] = step(H,X)` also returns the error power `P` when the `PredictionErrorOutputPort` property is true.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

## Purpose

LMS adaptive filter

## Description

The `LMSFilter` implements an adaptive FIR filter object that returns the filtered output, the error vector, and filter weights. The LMS filter uses one of five different LMS algorithms.

To implement the adaptive FIR filter object:

- 1 Define and set up your adaptive FIR filter object. See “Construction” on page 5-613.
- 2 Call `step` to implement the filter according to the properties of `dsp.LMSFilter`. The behavior of `step` is specific to each object in the toolbox.

## Construction

`H = dsp.LMSFilter` returns an adaptive FIR filter object, `H`, that computes the filtered output, filter error and the filter weights for a given input and desired signal using the Least Mean Squares (LMS) algorithm.

`H = dsp.LMSFilter('PropertyName', PropertyValue, ...)` returns an LMS filter object, `H`, with each property set to the specified value.

`H = dsp.LMSFilter(LEN, 'PropertyName', PropertyValue, ...)` returns an LMS filter object, `H`, with the `Length` property set to `LEN`, and other specified properties set to the specified values.

## Properties

### Method

Method to calculate filter weights

Specify the method used to calculate filter weights as `LMS`, `Normalized LMS`, `Sign-Error LMS`, `Sign-Data LMS`, or `Sign-Sign LMS`. The default is `LMS`.

### Length

Length of FIR filter weights vector

Specify the length of the FIR filter weights vector as a positive integer. The default is 32.

## **StepSizeSource**

How to specify adaptation step size

Choose how to specify the adaptation step size factor as `Property` or `Input port`. The default is `Property`.

## **StepSize**

Adaptation step size

Specify the adaptation step size factor as a nonnegative real number. For convergence of the normalized LMS method, set the step size greater than 0 and less than 2. This property only applies when the `StepSizeSource` property is `Property`. The default is 0.1. This property is tunable.

## **LeakageFactor**

Leakage factor used in LMS filter

Specify the leakage factor as a real number between 0 and 1 inclusive. A leakage factor of 1 corresponds to no leakage in the adapting method. The default is 1. This property is tunable.

## **InitialConditions**

Initial conditions of filter weights

Specify the initial values of the FIR filter weights as a scalar or vector of length equal to the `Length` property value. The default is 0.

## **AdaptInputPort**

Enable weight adaptation

Specify when the LMS filter should adapt the filter weights. By default, the value of this property is `false`, and the object continuously updates the filter weights. When this property is set to `true`, an adaptation control input is provided to the

step method. If the value of this input is nonzero, the object continuously updates the filter weights. If the input is zero, the filter weights remain at their current value.

## **WeightsResetInputPort**

Enable weight reset

Specify when the LMS filter should reset the filter weights. By default, the value of this property is `false`, and the object does not reset the weights. When this property is set to `true`, a reset control input is provided to the `step` method, and the `WeightsResetCondition` property applies. The object resets the filter weights based on the values of the `WeightsResetCondition` property and the reset input to the `step` method.

## **WeightsResetCondition**

Reset trigger setting for filter weights

Specify the event to reset the filter weights as `Rising edge`, `Falling edge`, `Either edge`, or `Non-zero`. The LMS filter resets the filter weights based on the values of this property and the reset input to the `step` method. This property only applies when the `WeightsResetInputPort` property is `true`. The default is `Non-zero`.

## **WeightsOutputPort**

Enable returning filter weights

Set this property to `true` to output the adapted filter weights. The default is `true`.

## **Fixed-Point Properties**

### **RoundingMethod**

Rounding method for fixed-point operations

Specify the rounding method as `Ceiling`, `Convergent`, `Floor`, `Nearest`, `Round`, `Simplest`, or `Zero`. The default is `Floor`.

## **OverflowAction**

Overflow action for fixed-point operations

Specify the overflow action as `Wrap` or `Saturate`. The default is `Wrap`.

## **StepSizeDataType**

Step size word and fraction lengths

Specify the step size fixed-point data type as `Same word length as first input` or `Custom`. Setting this property also sets the `LeakageFactorDataType` property to the same value. This property only applies when the `StepSizeSource` property is `Property`. The default is `Same word length as first input`.

## **CustomStepSizeDataType**

Step size word and fraction lengths

Specify the step size fixed-point type as a `numericType` object with a `Signedness` of `Auto`. This property only applies when the `StepSizeSource` property is `Property` and the `StepSizeDataType` property is `Custom`. This property and the `CustomLeakageFactorDataType` property must have the same word lengths. The default is `numericType([],16,15)`.

## **LeakageFactorDataType**

Leakage factor word and fraction lengths

Specify the leakage factor fixed-point data type as `Same word length as first input` or `Custom`. Setting this property also sets the `StepSizeDataType` property to the same value. This property only applies when the `StepSizeSource` property is `Property`. The default is `Same word length as first input`.

## **CustomLeakageFactorDataType**

Leakage factor word and fraction lengths

Specify the leakage factor fixed-point type as a `numericType` object with a `Signedness` of `Auto`. This property only applies

when the `StepSizeSource` property is `Property` and the `LeakageFactorDataType` property is `Custom`. This property and the `CustomStepSizeDataType` property must have the same word lengths. The default is `numerictype([],16,15)`.

## **WeightsDataType**

Weights word and fraction lengths

Specify the filter weights fixed-point data type as `Same as first input` or `Custom`. The default is `Same as first input`.

## **CustomWeightsDataType**

Weights word and fraction lengths

Specify the filter weights fixed-point type as a scaled `numerictype` object with a `Signedness` of `Auto`. This property only applies when the `WeightsDataType` property is `Custom`. The default is `numerictype([],16,15)`.

## **EnergyProductDataType**

Energy product word and fraction lengths

Specify the energy product fixed-point data type as `Same as first input` or `Custom`. This property only applies when the `Method` property is `Normalized LMS`. Setting this property also sets the `ConvolutionProductDataType`, `StepSizeErrorProductDataType`, `WeightsUpdateProductDataType`, and `QuotientDataType` properties to the same value. The default is `Same as first input`.

## **CustomEnergyProductDataType**

Energy product word and fraction lengths

Specify the energy product fixed-point type as a scaled `numerictype` object with a `Signedness` of `Auto`. This property only applies when the `Method` property is `Normalized LMS` and the `EnergyProductDataType` property is `Custom`. The `CustomEnergyProductDataType`,

CustomConvolutionProductDataType, CustomStepSizeErrorProductDataType, CustomWeightsUpdateProductDataType, and CustomQuotientDataType properties must have the same word lengths. The default is `numerictype([],32,20)`.

## **EnergyAccumulatorDataType**

Energy accumulator word and fraction lengths

Specify the energy accumulator fixed-point data type as `Same as first input` or `Custom`. This property only applies when the `Method` property is `Normalized LMS`. Setting this property also sets the `ConvolutionAccumulatorDataType` property to the same value. The default is `Same as first input`.

## **CustomEnergyAccumulatorDataType**

Energy accumulator word and fraction lengths

Specify the energy accumulator fixed-point type as a scaled `numerictype` object with a `Signedness` of `Auto`. This property only applies when the `Method` property is `Normalized LMS` and the `EnergyAccumulatorDataType` property is `Custom`. The `CustomEnergyProductDataType`, `CustomConvolutionProductDataType`, `CustomStepSizeErrorProductDataType`, `CustomWeightsUpdateProductDataType`, and `CustomQuotientDataType` properties must have the same word lengths. The default is `numerictype([],32,20)`.

## **ConvolutionProductDataType**

Convolution product word and fraction lengths

Specify the convolution product fixed-point data type as `Same as first input` or `Custom`. Setting this property also sets the `EnergyProductDataType`, `StepSizeErrorProductDataType`, `WeightsUpdateProductDataType` and `QuotientDataType` properties to the same value. The default is `Same as first input`.

## **CustomConvolutionProductDataType**

Convolution product word and fraction lengths

Specify the convolution product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property only applies when the `ConvolutionProductDataType` property is `Custom`. The `CustomEnergyProductDataType`, `CustomConvolutionProductDataType`, `CustomStepSizeErrorProductDataType`, `CustomWeightsUpdateProductDataType`, and `CustomQuotientDataType` properties must have the same word lengths. The default is `numericType([],32,20)`.

## **ConvolutionAccumulatorDataType**

Convolution accumulator word and fraction lengths

Specify the convolution accumulator fixed-point data type as `Same as first input` or `Custom`. Setting this property also sets the `EnergyAccumulatorDataType` property to the same value. The default is `Same as first input`.

## **CustomConvolutionAccumulatorDataType**

Convolution accumulator word and fraction lengths

Specify the convolution accumulator fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property only applies when the `ConvolutionAccumulatorDataType` property is `Custom`. The `CustomEnergyAccumulatorDataType` and `CustomConvolutionAccumulatorDataType` properties must have the same word lengths. The default is `numericType([],32,20)`.

## **StepSizeErrorProductDataType**

Step size error product word and fraction lengths

Specify the step size error product fixed-point data type as `Same as first input` or `Custom`. Setting this property also sets the `ConvolutionProductDataType`, `EnergyProductDataType`, `WeightsUpdateProductDataType`, and `QuotientDataType`

properties to the same value. The default is Same as first input.

## **CustomStepSizeErrorProductDataType**

Step size error product word and fraction lengths

Specify the step size error product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property only applies when the `StepSizeErrorProductDataType` property is `Custom`. The `CustomEnergyProductDataType`, `CustomConvolutionProductDataType`, `CustomStepSizeErrorProductDataType`, `CustomWeightsUpdateProductDataType`, and `CustomQuotientDataType` properties must have the same word lengths. The default is `numericType([],32,20)`.

## **WeightsUpdateProductDataType**

Weight update product word and fraction lengths

Specify the weight update product fixed-point data type as `Same as first input` or `Custom`. Setting this property also sets the `ConvolutionProductDataType`, `EnergyProductDataType`, `StepSizeErrorProductDataType`, and `QuotientDataType` properties to the same value. The default is `Same as first input`.

## **CustomWeightsUpdateProductDataType**

Weight update product word and fraction lengths

Specify the weight update product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property only applies when the `WeightsUpdateProductDataType` property is `Custom`. The `CustomEnergyProductDataType`, `CustomConvolutionProductDataType`, `CustomStepSizeErrorProductDataType`, `CustomWeightsUpdateProductDataType`, and `CustomQuotientDataType` properties must have the same word lengths. The default is `numericType([],32,20)`.

**QuotientDataType**

Quotient word and fraction lengths

Specify the quotient fixed-point data type as Same as first input, Custom. This property only applies when the Method property is Normalized LMS. Setting this property also sets the ConvolutionProductDataType, EnergyProductDataType, StepSizeErrorProductDataType, and WeightsUpdateProductDataType properties to the same value. The default is Same as first input.

**CustomQuotientDataType**

Quotient word and fraction lengths

Specify the quotient fixed-point type as a scaled numerictype object with a Signedness of Auto. This property only applies when the Method property is Normalized LMS and the QuotientDataType property is Custom. The CustomEnergyProductDataType, CustomConvolutionProductDataType, CustomStepSizeErrorProductDataType, CustomWeightsUpdateProductDataType, and CustomQuotientDataType properties must have the same word lengths. The default is numerictype([],32,20).

**Methods**

clone	Create LMS filter object with same property values
getNumInputs	Number of expected inputs to step method
getNumOutputs	Number of outputs of step method
isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes

reset	Reset filter states for LMS filter
step	Apply LMS adaptive filter to input

## Examples

Determine system identification of an FIR filter:

```
hlms1 = dsp.LMSFilter(11, 'StepSize', 0.01);
hfilt = dsp.DigitalFilter; % System to be identified
hfilt.TransferFunction = 'FIR (all zeros)';
hfilt.Numerator = fir1(10, .25);
x = randn(1000,1); % input signal

d = step(hfilt, x) + 0.01*randn(1000,1); % desired signal
[y,e,w] = step(hlms1, x, d);

subplot(2,1,1), plot(1:1000, [d,y,e]);
title('System Identification of an FIR filter');
legend('Desired', 'Output', 'Error');
xlabel('time index'); ylabel('signal value');
subplot(2,1,2); stem([hfilt.Numerator.', w]);
legend('Actual', 'Estimated');
xlabel('coefficient #'); ylabel('coefficient value');
```

---

Cancel noise in a signal:

```
hlms2 = dsp.LMSFilter('Length', 11, ...
    'Method', 'Normalized LMS',...
    'AdaptInputPort', true, ...
    'StepSizeSource', 'Input port', ...
    'WeightsOutputPort', false);
hfilt2 = dsp.DigitalFilter(...
    'TransferFunction', 'FIR (all zeros)', ...
    'Numerator', fir1(10, [.5, .75]));
x = randn(1000,1); % Noise
d = step(hfilt2, x) + sin(0:.05:49.95)'; % Noise + Signal
```

```
a = 1; % adaptation control
mu = 0.05; % step size
[y, err] = step(hlms2, x, d, mu, a);

subplot(2,1,1), plot(d), title('Noise + Signal');
subplot(2,1,2), plot(err), title('Signal');
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the LMS Filter block reference page. The object properties correspond to the block parameters.

## See Also

[dsp.BlockLMSFilter](#) | [dsp.DigitalFilter](#)

## **dsp.LMSFilter.clone**

---

**Purpose** Create LMS filter object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates an LMS filter object, `C`, with the same property values as `H`. The clone method creates a new unlocked object with uninitialized states.

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.LMSFilter.getNumOutputs**

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the LMS filter.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.LMSFilter.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Reset filter states for LMS filter

**Syntax** reset(H)

**Description** reset(H) resets the filter states of the LMS FIR filter,H, to their initial values specified in the InitialConditions property. The initial filter state values correspond to the initial conditions for difference equation defining the adaptive filter. After the step method applies the LMS filter to nonzero input data, the states may be different. Invoking the step method again without first invoking the reset method may produce different outputs for an identical input.

Example of resetting filter states:

```
hlms1 = dsp.LMSFilter(11, 'StepSize', 0.01);
hfilt = dsp.DigitalFilter; % System to be identified
hfilt.TransferFunction = 'FIR (all zeros)';
hfilt.Numerator = fir1(10, .25);
x = randn(1000,1); % input signal
d = step(hfilt, x) + 0.01*randn(1000,1); % desired signal
[y,e,w] = step(hlms1, x, d);
% Call step method again without resetting filter states
[y1,e1,w1] = step(hlms1,x,d);
isequal(y,y1) % Returns 0
% Now reset the filter states to zero
reset(hlms1)
% invoke step method
[y2,e2,w2] = step(hlms1,x,d);
isequal(y,y2) % Returns 1
```

# dsp.LMSFilter.step

---

**Purpose** Apply LMS adaptive filter to input

**Syntax**

```
[Y,ERR,WTS] = step(H,X,D)
[Y, ERR] = step(H,X,D)
[...] = step(H,X,D,MU)
[...] = step(H,X,D,A)
[...] = step(H,X,D,R)
[Y,ERR,WTS] = step(H,X,D,MU,A,R)
```

**Description** `[Y,ERR,WTS] = step(H,X,D)` applies the LMS filter object, `H` to the input `X`, using `D` as the desired signal. This approach returns the filtered output in `Y`, the filter error in `ERR`, and the estimated filter weights in `WTS`. The LMS filter estimates the filter weights needed to minimize the mean square error between the output and the desired signal.

`[Y, ERR] = step(H,X,D)` filters the input `X`, using `D` as the desired signal. This approach returns the filtered output in `Y` and the filter error in `ERR` when the `WeightsOutputPort` property is `false`.

`[...] = step(H,X,D,MU)` uses `MU` as the step size, when the `StepSizeSource` property is `'Input port'`.

`[...] = step(H,X,D,A)` uses `A` as the adaptation control, when the `AdaptInputPort` property is `true`. When `A` is nonzero, the LMS filter continuously updates the filter weights. When `A` is zero, the filter weights remain constant.

`[...] = step(H,X,D,R)` uses `R` as a reset signal when the `WeightsResetInputPort` property is `true`. The `WeightsResetCondition` property can be used to set the reset trigger condition. If a reset event occurs, the LMS filter resets the filter weights to their initial values.

`[Y,ERR,WTS] = step(H,X,D,MU,A,R)` filters the input `X` using `D` as the desired signal, `MU` as the step size, `A` as the adaptation control, and `R` as the reset signal. This approach returns the filtered output in `Y`, the filter error in `ERR`, and the adapted filter weights in `WTS`.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.LowerTriangularSolver

---

**Purpose** Solve lower-triangular matrix equation

**Description** The `LowerTriangularSolver` object solves  $LX = B$  for  $X$  when  $L$  is a square, lower-triangular matrix with the same number of rows as  $B$ .

To solve  $LX = B$  for  $X$ :

- 1 Define and set up your linear system solver. See “Construction” on page 5-632.
- 2 Call `step` to solve the equation according to the properties of `dsp.LowerTriangularSolver`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.LowerTriangularSolver` returns a linear system solver, `H`, used to solve the linear system  $LX = B$ , where  $L$  is a lower (or unit-lower) triangular matrix.

`H = dsp.LowerTriangularSolver('PropertyName',PropertyValue,...)` returns a linear system solver, `H`, with each specified property set to the specified value.

## Properties

### OverwriteDiagonal

Replace diagonal elements of input with ones

When you set this property to `true`, the linear system solver replaces the elements on the diagonal of the input,  $L$ , with ones. Set this property to either `true` or `false`. The default is `false`.

### RealDiagonalElements

Indicate that diagonal of complex input is real

When you set this property to `true`, the linear system solver optimizes computation speed if the diagonal elements of complex input,  $L$ , are real. This property applies only when you set the `OverwriteDiagonal` property to `false`. Set this property to either `true` or `false`. The default is `false`.

## **Fixed-Point Properties**

### **RoundingMethod**

Rounding method for fixed-point operations

Specify the rounding method as `Ceiling`, `Convergent`, `Floor`, `Nearest`, `Round`, `Simplest`, or `Zero`. The default is `Floor`.

### **OverflowAction**

Overflow action for fixed-point operations

Specify the overflow action as `Wrap` or `Saturate`. The default is `Wrap`.

### **ProductDataType**

Data type of product

Specify the product data type as `Full precision`, `Same as input`, or `Custom`. The default is `Full precision`.

### **CustomProductDataType**

Product word and fraction lengths

Specify the product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `ProductDataType` property to `Custom`. The default is `numericType([],32,30)`.

### **AccumulatorDataType**

Data type of accumulator

Specify the accumulator data type as `Full precision`, `Same as first input`, `Same as product`, or `Custom`. The default is `Full precision`.

### **CustomAccumulatorDataType**

Accumulator word and fraction lengths

# dsp.LowerTriangularSolver

---

Specify the accumulator fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `AccumulatorDataType` property to `Custom`. The default is `numericType([],32,30)`.

## OutputDataType

Data type of output

Specify the output data type as `Same as first input` or `Custom`. The default is `Same as first input`.

## CustomOutputDataType

Output word and fraction lengths

Specify the output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `OutputDataType` property to `Custom`. The default is `numericType([],16,15)`.

## Methods

<code>clone</code>	Create lower triangular solver object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>step</code>	Solve matrix equation for specified inputs

## Examples

Solve a lower-triangular matrix equation:

```
hlowtriang = dsp.LowerTriangularSolver;
```

```
u = tril(rand(4, 4));  
b = rand(4, 1);  
% Check that result is the solution to the linear  
% equations.  
x1 = inv(u)*b  
x = step(hlowtriang, u, b)
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Forward Substitution block reference page. The object properties correspond to the block parameters.

## See Also

`dsp.UpperTriangularSolver`

# **dsp.LowerTriangularSolver.clone**

---

**Purpose** Create lower triangular solver object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a `LowerTriangularSolver` object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object.

# **dsp.LowerTriangularSolver.getNumInputs**

---

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.LowerTriangularSolver.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `LowerTriangularSolver` object `H`.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.LowerTriangularSolver.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

**Purpose** Solve matrix equation for specified inputs

**Syntax**  $X = \text{step}(H,L,B)$

**Description**  $X = \text{step}(H,L,B)$  computes the solution,  $X$ , of the matrix equation  $LX = B$ , where  $L$  is a square, lower-triangular matrix with the same number of rows as the matrix  $B$ .

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.LPCToAutocorrelation

---

**Purpose** Convert linear prediction coefficients to autocorrelation coefficients

**Description** The LPCToAutocorrelation System object converts linear prediction coefficients to autocorrelation coefficients.

To convert LPC to autocorrelation coefficients:

- 1 Define and set up your LPC to autocorrelation object. See “Construction” on page 5-642.
- 2 Call `step` to convert LPC according to the properties of `dsp.LPCToAutocorrelation`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.LPCToAutocorrelation` returns an LPC to autocorrelation System object, `H`, that converts linear prediction coefficients (LPC) to autocorrelation coefficients.

`H = dsp.LPCToAutocorrelation('PropertyName',PropertyValue,...)` returns an LPC to autocorrelation conversion object, `H`, with each specified property set to the specified value.

**Properties** **PredictionErrorInputPort**

Enable prediction error power input

Choose how to select the prediction error power. When you set this property to `true`, you must specify the prediction error power as a second input to the `step` method. When you set this property to `false`, the object assumes that the prediction error power is 1. The default is `false`.

**NonUnityFirstCoefficientAction**

Action to take when first LPC coefficient is not 1

Specify the action that the object takes when the first coefficient of each channel of the LPC input is not 1. Select `Replace with 1` or `Normalize`. The default is `Replace with 1`.

## Methods

clone	Create LPC to autocorrelation object with same property values
getNumInputs	Number of expected inputs to step method
getNumOutputs	Number of outputs of step method
isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
step	Autocorrelation coefficients from LPC coefficients

## Examples

Convert the linear prediction coefficients to autocorrelation coefficients:

```
a = [1.0 -1.4978 1.4282 -1.3930 0.9076 -0.3855 0.0711].';  
hlpc2ac = dsp.LPCToAutocorrelation;  
ac = step(hlpc2ac, a);
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the LPC/RC to Autocorrelation block reference page. The object properties correspond to the block parameters, except:

The object does not have a property that corresponds to the **Type of Conversion** block parameter. The object's behavior corresponds to the block's behavior when you set the **Type of Conversion** parameter to LPC to autocorrelation.

## See Also

dsp.LPCToLSF | dsp.LPCToRC | dsp.LPCToCepstral |  
dsp.RCToAutocorrelation

# **dsp.LPCToAutocorrelation.clone**

---

**Purpose** Create LPC to autocorrelation object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates an `LPCToAutocorrelation System` object `C`, with the same property values as `H`. The clone method creates a new unlocked object.

# dsp.LPCToAutocorrelation.getNumInputs

---

**Purpose** Number of expected inputs to step method

**Syntax** N = getNumInputs(H)

**Description** N = getNumInputs(H) returns the number of expected inputs, N, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.LPCToAutocorrelation.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the LPCToAutocorrelation System object H.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.LPCToAutocorrelation.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose**

Autocorrelation coefficients from LPC coefficients

**Syntax**

AC = step(H,A)  
AC = step(H,A,P)

**Description**

AC = step(H,A) converts the columns of the linear prediction coefficients, A, to autocorrelation coefficients, AC. The object assumes a prediction error power of 1.

AC = step(H,A,P) when you set the PredictionErrorInputPort property to true, converts the columns of the linear prediction coefficients, A, to autocorrelation coefficients, AC. This conversion uses P as the prediction error power. P must be a row vector with same number of columns as A.

---

**Note** The object performs an initialization the first time the step method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the release method to unlock the object.

---

# dsp.LPCToCepstral

---

**Purpose** Convert linear prediction coefficients to cepstral coefficients

**Description** The `LPCToCepstral` object converts linear prediction coefficients to cepstral coefficients.

To convert LPC to cepstral coefficients:

- 1 Define and set up your LPC to cepstral converter. See “Construction” on page 5-650.
- 2 Call `step` to convert LPC according to the properties of `dsp.LPCToCepstral`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.LPCToCepstral` returns an LPC to cepstral converter object, `H`, that converts linear prediction coefficients (LPCs) to cepstral coefficients (CCs).

`H = dsp.LPCToCepstral('PropertyName',PropertyValue,...)` returns an LPC to cepstral converter object, `H`, with each specified property set to the specified value.

## Properties

### **PredictionErrorInputPort**

Enable prediction error power input

Choose how to set the prediction error power. When you set this property to `true`, you must specify the prediction error as a second input to the `step` method. When you set this property to `false`, the object assumes the prediction error power is 1. The default is `false`.

### **CepstrumLengthSource**

Source of cepstrum length

Select how to specify the length of cepstral coefficients: `Auto` or `Property`. The default is `Auto`. When this property is set to `Auto`, the length of each channel of the cepstral coefficients output is the

same as the length of each channel of the input LPC coefficients. The default is Property.

### **CepstrumLength**

Number of output cepstral coefficients

Set the length of the output cepstral coefficients vector as a scalar numeric integer. This property applies when you set the CepstrumLengthSource property to Property. The default is 10.

### **NonUnityFirstCoefficientAction**

LPC coefficient nonunity action

Specify the action that the object takes when the first coefficient of each channel of the LPC input is not 1. Select **Replace with 1** or **Normalize**. The default is **Replace with 1**.

## **Methods**

clone	Create LPC to cepstral object with same property values
getNumInputs	Number of expected inputs to step method
getNumOutputs	Number of outputs of step method
isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
step	Cepstral coefficients from columns of input LPC coefficients

## **Examples**

Convert the linear prediction coefficients (LPC) to cepstral coefficients:

```
hlevinson = dsp.LevinsonSolver;
hlevinson.AOutputPort = true; % Output polynomial coefficients
hac = dsp.Autocorrelator;
```

# dsp.LPCToCepstral

---

```
hac.MaximumLagSource = 'Property';
hac.MaximumLag = 9; % Compute autocorrelation lags between [0:9]
hlpc2cc = dsp.LPCToCepstral;
x = [1:100]';
a = step(hac, x);
A = step(hlevinson, a); % Compute LPC coefficients
CC = step(hlpc2cc, A); % Convert LPC to CC.
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the LPC to/from Cepstral Coefficients block reference page. The object properties correspond to the block parameters, except:

The object does not have a property that corresponds to the **Type of Conversion** block parameter. The object's behavior corresponds to the block's behavior when you set the **Type of Conversion** parameter to LPCs to cepstral coefficients.

## See Also

[dsp.CepstralToLPC](#) | [dsp.LPCToLSF](#) | [dsp.LPCToRC](#)

**Purpose**

Create LPC to cepstral object with same property values

**Syntax**

`C = clone(H)`

**Description**

`C = clone(H)` creates an LPCToCepstral System object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object.

# dsp.LPCToCepstral.getNumInputs

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose**

Number of outputs of step method

**Syntax**

`N = getNumOutputs(H)`

**Description**

`N = getNumOutputs(H)` returns the number of outputs, `N`, from the `step` method

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# dsp.LPCToCepstral.isLocked

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `LPCToCepstral System` object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

# dsp.LPCToCepstral.step

---

**Purpose** Cepstral coefficients from columns of input LPC coefficients

**Syntax**  
CC = step(H,A)  
CC = step(H,A,P)

**Description** CC = step(H,A) computes the cepstral coefficients, CC, from the columns of input linear prediction coefficients, A. The object assumes the prediction error power is 1.

CC = step(H,A,P) when you set the PredictionErrorInputPort property to true, computes the cepstral coefficients, CC, from the columns of input linear prediction coefficients, A. This conversion uses P as the prediction error power.

---

**Note** The object performs an initialization the first time the step method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the release method to unlock the object.

---

<b>Purpose</b>	Convert linear prediction coefficients to line spectral frequencies
<b>Description</b>	<p>The LPCToLSF object converts linear prediction coefficients to line spectral frequencies.</p> <p>To convert LPC to LSF:</p> <ol style="list-style-type: none"><li>1 Define and set up your LPC to LSF converter. See “Construction” on page 5-659.</li><li>2 Call <code>step</code> to convert LPC according to the properties of <code>dsp.LPCToLSF</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.LPCToLSF</code> returns a System object, <code>H</code>, that converts linear prediction coefficients (LPCs) to line spectral frequencies (LSFs).</p> <p><code>H = dsp.LPCToLSF('PropertyName',PropertyValue,...)</code> returns an LPC to LSF System object, <code>H</code>, with each specified property set to the specified value.</p>
<b>Properties</b>	<p><b>NumCoarseGridPoints</b></p> <p>Number of coarse subintervals used for finding roots (LSP values)</p> <p>Specify the number of coarse subintervals, <math>n</math>, used for finding line spectral pairs (LSP) values as a positive scalar integer. LSPs, which are the roots of two particular polynomials related to the input LPC polynomial, always lie in the range <math>(-1, 1)</math>. The System object finds these roots using the Chebyshev polynomial root finding method. To compute LSF outputs, the object computes the arc cosine of the LSPs, outputting values ranging from 0 to <math>\pi</math> radians. The object divides the interval <math>(-1, 1)</math> into <math>n</math> subintervals and looks for roots in each subinterval. If you set <math>n</math> too small in relation to the LPC polynomial order, the object can fail to find some of the roots. The default is 64. This property is tunable.</p> <p><b>NumBisects</b></p> <p>Value of bisection refinement used for finding roots</p>

Specify the root bisection refinement value,  $k$ , used in the Chebyshev polynomial root finding method, where each line spectral pair (LSP) output is within

$\frac{1}{(n \cdot 2^k)}$  of the actual LSP value. Here  $n$  is the value of the NumCoarseGridPoints property, and the object searches a maximum of  $k \cdot (n - 1)$  points for finding the roots. You must set the NumBisects property value  $k$ , to a positive scalar integer. The default is 4. This property is tunable.

### **ExceptionOutputPort**

Produces output with validity status of LSF output

Set this property to `true` to return a second output that indicates whether the computed LSF values are valid. The output is a vector with a length equal to the number of channels. A logical value of 1 indicates valid output. A logical value of 0 indicates invalid output. The LSF outputs are invalid when the object fails to find all the LSF values or when the input LPCs are unstable. The default is `false`.

### **OverwriteInvalidOutput**

Enable overwriting invalid output with previous output

Specify the action that the System object should take for invalid LSF outputs. When you set this property to `true`, the object overwrites the invalid output with the previous output. When you set this property to `false`, the object does not take any action on invalid outputs and ignores the outputs.

### **FirstOutputValuesSource**

Source of values for first output when output is invalid

Specify the source of values for the first output when the output is invalid as `Auto` or `Property`. This property applies when you

set the `OverwriteInvalidOutput` property to `true`. The default is `Auto`. When you set this property to `Auto`, the object uses a default value for the first output. The default value corresponds to the LSF representation of an allpass filter.

### **FirstOutputValues**

Value of the first output

Specify a numeric vector of LSF values for overwriting an invalid first output. The length of this vector must be one less than the length of the input LPC vector. For multichannel inputs, you can set this property to a matrix with the same number of channels as the input, or one vector that is applied to every channel. The default is an empty vector. This property applies when you set the `OverwriteInvalidOutput` property to `true` and the `FirstOutputValuesSource` property to `Property`.

### **NonUnityFirstCoefficientAction**

Action to take when first LPC coefficient is not 1

Specify the action the object takes when the first coefficient of each channel of the LPC input is not 1 as `Replace with 1` or `Normalize`. The default is `Replace with 1`.

## **Methods**

<code>clone</code>	Create LPC To LSF object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes

reset	Reset values for overwriting invalid outputs to their initial values
step	Convert LPC coefficients to line spectral frequencies

## Examples

Convert to linear prediction coefficients to line spectral frequencies:

```
a = [1.0000 0.6149 0.9899 0.0000 0.0031 -0.0082]';  
hlpc2lsf = dsp.LPCToLSF;  
y = step(hlpc2lsf, a); % Convert to LSF coefficients
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the LPC to LSF/LSP Conversion block reference page. The object properties correspond to the block parameters, except:

There is no object property that corresponds to the **Output** block parameter. The object only supports LSF outputs in the range  $(0, \Pi)$

## See Also

dsp.LSFToLPC | dsp.LPCToLSP

**Purpose** Create LPC To LSF object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates an LPCToLSF System object `C`, with the same property values as `H`. The clone method creates a new unlocked object.

## dsp.LPCToLSF.getNumInputs

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose** Number of outputs of step method

**Syntax** N = getNumOutputs(H)

**Description** N = getNumOutputs(H) returns the number of outputs, N, of the step method

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# dsp.LPCToLSF.isLocked

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** isLocked(H)

**Description** isLocked(H) returns the locked state of the LPCToLSF System object.  
The isLocked method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the step method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the isLocked method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

## **dsp.LPCToLSF.reset**

---

<b>Purpose</b>	Reset values for overwriting invalid outputs to their initial values
<b>Syntax</b>	reset(H)
<b>Description</b>	reset(H) resets the values for overwriting the invalid outputs to their initial values.

**Purpose**

Convert LPC coefficients to line spectral frequencies

**Syntax**

```
LSF = step(H,A)  
[..., STATUS] = step(H,A)
```

**Description**

LSF = step(H,A) converts the LPC coefficients, A , to line spectral frequencies, LSF, in the range (0 pi). The System object operates along the columns of the input A.

[..., STATUS] = step(H,A) also returns the status flag, STATUS, indicating if the current output is valid when the ExceptionOutputPort property is true.

---

**Note** The object performs an initialization the first time the step method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the release method to unlock the object.

---

# dsp.LPCToLSP

---

<b>Purpose</b>	Convert linear prediction coefficients to line spectral pairs
<b>Description</b>	<p>The LPCToLSP object converts linear prediction coefficients to line spectral pairs.</p> <p>To convert LPC to LSP:</p> <ol style="list-style-type: none"><li>1 Define and set up your LPC to LSP converter. See “Construction” on page 5-670.</li><li>2 Call <code>step</code> to convert LPC according to the properties of <code>dsp.LPCToLSP</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.LPCToLSP</code> returns a System object, <code>H</code>, that converts linear prediction coefficients (LPCs) to line spectral pairs (LSPs).</p> <p><code>H = dsp.LPCToLSP('PropertyName',PropertyValue,...)</code> returns an LPC to LSF System object, <code>H</code>, with each specified property set to the specified value.</p>
<b>Properties</b>	<p><b>NumCoarseGridPoints</b></p> <p>Number of coarse subintervals used for finding roots (LSP values)</p> <p>Specify the number of coarse subintervals, <math>n</math>, used for finding line spectral pairs (LSP) values, as a positive scalar integer. LSPs, which are the roots of two particular polynomials related to the input LPC polynomial, always lie in the range <math>(-1, 1)</math>. The System object finds these roots using the Chebyshev polynomial root finding method. The object divides the interval <math>(-1, 1)</math> into <math>n</math> subintervals and looks for roots in each subinterval. If <math>n</math> is set to too small a number in relation to the LPC polynomial order, the object can fail to find some of the roots. The default is 64. This property is tunable.</p> <p><b>NumBisects</b></p> <p>Value of bisection refinement used for finding roots</p>

Specify the root bisection refinement value,  $k$ , that the Chebyshev polynomial uses in the root finding method. For each line spectral pair (LSP) the output is within

$$\frac{1}{n \cdot 2^k}$$

of the actual LSP value. Here  $n$  is the value of the NumCoarseGridPoints property and the object searches a maximum of

$$k \cdot (n-1)$$

points for finding the roots. The NumBisects property value  $k$ , must be a positive scalar integer. The default is 4. This property is tunable.

#### **ExceptionOutputPort**

Produces output with validity status of LSP output

Set this property to `true` to return a second output that indicates whether the computed LSP values are valid. The object outputs a vector length equal to the number of channels. A logical value of 1 indicates the output is valid. A logical value of 0 indicates the output is invalid. The LSP outputs are invalid when the object fails to find all the LSP values or when the input LPCs are unstable. The default is `false`.

#### **OverwriteInvalidOutput**

Enable overwriting invalid output with previous output

Specify the action that the object takes for invalid LSP outputs. When you set this property to `true`, the object overwrites the invalid output with the previous output. When you set this property to `false`, the object takes no action on invalid outputs and ignores the outputs.

#### **FirstOutputValuesSource**

Source of values for first output when output is invalid

Specify the source of values for the first output when the output is invalid as `Auto` or `Property`. This property applies only when you set the `OverwriteInvalidOutput` property to `true`. The default is `Auto`. When this property is `Auto`, the object uses a default value for the first output. The default value corresponds to the LSP representation of an allpass filter.

## **FirstOutputValues**

Value of first output

Specify a numeric vector of LSP values for overwriting an invalid first output. The length of this vector must be one less than the length of the input LPC vector. For multichannel inputs, set this property can to a matrix with the same number of channels as the input or one vector that you apply to every channel. The default is an empty vector. This property applies only when you set the `OverwriteInvalidOutput` property to `true` and the `FirstOutputValuesSource` property to `Property`.

## **NonUnityFirstCoefficientAction**

First coefficient nonunity action

Specify the action that the object takes when the first coefficient of each channel of the LPC input is not equal to 1. Specify as one of `Replace with 1` or `Normalize`. The default is `Replace with 1`.

## **Methods**

<code>clone</code>	Create LPC To LSP object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties

release	Allow property value and input characteristics changes
reset	Reset values for overwriting invalid outputs to their initial values
step	Convert linear prediction coefficients to line spectral pairs

**Examples**

Convert the LPC coefficients to LSP coefficients:

```
a = [1.0000 0.6149 0.9899 0.0000 0.0031 -0.0082]';
hlpc2lsp = dsp.LPCToLSP;
y = step(hlpc2lsp, a); % Convert to LSP coefficients
```

**Algorithms**

This object implements the algorithm, inputs, and outputs described on the LPC to LSF/LSP Conversion block reference page. The object properties correspond to the block parameters, except:

No object property corresponds to the **Output** block parameter. The object only supports LSP outputs.

**See Also**

dsp.LSPToLPC | dsp.LPCToLSF

## **dsp.LPCToLSP.clone**

---

**Purpose** Create LPC To LSP object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a LPCToLSP System object `C`, with the same property values as `H`. The clone method creates a new unlocked object.

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the `step` method

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.LPCToLSP.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**      `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the LPCToLSP System object. The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.LPCToLSP.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

<b>Purpose</b>	Reset values for overwriting invalid outputs to their initial values
<b>Syntax</b>	reset(H)
<b>Description</b>	reset(H) resets the values for overwriting the invalid outputs to their initial values.

# dsp.LPCToLSP.step

---

**Purpose** Convert linear prediction coefficients to line spectral pairs

**Syntax** LSF = step(H,A)  
[ ..., STATUS] = step(H,A)

**Description** LSF = step(H,A) converts the LPC coefficients, A , to line spectral pairs normalized in the range (-1 1), LSP. The object operates along the columns of the input A.

[ ..., STATUS] = step(H,A) also returns the status flag, STATUS, indicating if the current output is valid when the ExceptionOutputPort property is true.

---

**Note** The object performs an initialization the first time the step method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the release method to unlock the object.

---

<b>Purpose</b>	Convert linear prediction coefficients to reflection coefficients
<b>Description</b>	<p>The LPCToRC object converts linear prediction coefficients to reflection coefficients.</p> <p>To convert LPC to reflection coefficients:</p> <ol style="list-style-type: none"> <li><b>1</b> Define and set up your LPC to RC converter. See “Construction” on page 5-681.</li> <li><b>2</b> Call <code>step</code> to convert LPC according to the properties of <code>dsp.LPCToRC</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li> </ol>
<b>Construction</b>	<p><code>H = dsp.LPCToRC</code> returns an LPC to RC System object, <code>H</code>, that converts linear prediction coefficients (LPC) to reflection coefficients (RC).</p> <p><code>H = dsp.LPCToRC('PropertyName',PropertyValue,...)</code> returns an LPC to RC conversion object, <code>H</code>, with each specified property set to the specified value.</p>
<b>Properties</b>	<p><b>PredictionErrorOutputPort</b></p> <p>Enable normalized prediction error power output</p> <p>Set this property to <code>true</code> to return the normalized error power as a vector with one element per input channel. Each element varies between zero and one. The default is <code>true</code>.</p> <p><b>ExceptionOutputPort</b></p> <p>Produces output with stability status of filter represented by LPC coefficients</p> <p>Set this property to <code>true</code> to return the stability status of the filter. A logical value of 1 indicate a stable filter. A logical value of 0 indicate an unstable filter. The default is <code>false</code>.</p> <p><b>NonUnityFirstCoefficientAction</b></p> <p>Action to take when first LPC coefficient is not 1</p>

Specify the action that the object takes when the first coefficient of each channel of the LPC input is not 1. Select `Replace` with 1 or `Normalize`. The default is `Replace` with 1.

## Methods

<code>clone</code>	Create LPC to RC object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>step</code>	Convert columns of linear prediction coefficients to reflection coefficients

## Examples

Convert the linear prediction coefficients to reflection coefficients:

```
load mtlb

hlevinson = dsp.LevinsonSolver;
hlevinson.AOutputPort = true;
hlevinson.KOutputPort = false;

hac = dsp.Autocorrelator;
hlpc2rc = dsp.LPCToRC;
hac.MaximumLagSource = 'Property';

% Compute autocorrelation for lags between [0:10]
hac.MaximumLag = 10;
a = step(hac, mtlb);
A = step(hlevinson, a); % Compute LPC coefficients
```

```
[K, P] = step(hlpc2rc, A); % Convert to RC
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the LPC to/from RC block reference page. The object properties correspond to the block parameters, except:

- There is no object property that corresponds to the **Type of conversion** block parameter. The object always converts LPC to RC.
- The `NonUnityFirstCoefficientAction` object property corresponds to the **If first input value is not 1** block parameter. There is neither a `Normalize` and `warn` nor an `Error` option for the object.

## See Also

`dsp.RCToLPC` | `dsp.LPCToAutocorrelation`

## **dsp.LPCToRC.clone**

---

**Purpose** Create LPC to RC object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a LPCToRC System object `C`, with the same property values as `H`. The clone method creates a new unlocked object.

**Purpose** Number of expected inputs to step method

**Syntax** N = getNumInputs(H)

**Description** N = getNumInputs(H) returns the number of expected inputs, N, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.LPCToRC.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the LPCToRC System object H. The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.LPCToRC.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Convert columns of linear prediction coefficients to reflection coefficients

**Syntax**

```
[K,P] = step(H,A)
K = step(H,A)
[... , S] = step(H,A)
```

**Description** [K,P] = step(H,A) converts the columns of linear prediction coefficients, A, to reflection coefficients K and outputs the normalized prediction error power, P.

K = step(H,A) when you set the PredictionErrorOutputPort property to false, converts the columns of linear prediction coefficients, A, to reflection coefficients K.

[... , S] = step(H,A) also outputs the LPC filter stability, S, when you set the ExceptionOutputPort property to true.

---

**Note** The object performs an initialization the first time the step method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the release method to unlock the object.

---

# dsp.LSFToLPC

---

**Purpose** Convert line spectral frequencies to linear prediction coefficients

**Description** The LSFToLPC object converts line spectral frequencies to linear prediction coefficients.

To convert LSF to LPC:

- 1 Define and set up your LSF to LPC converter. See “Construction” on page 5-690.
- 2 Call `step` to convert LSF according to the properties of `dsp.LSFToLPC`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.LSFToLPC` returns an LSF to LPC System object, `H`, which converts line spectral frequencies (LSFs) to linear prediction coefficients (LPCs).

Methods		
	<code>clone</code>	Create LSF to LPC object with same property values
	<code>getNumInputs</code>	Number of expected inputs to <code>step</code> method
	<code>getNumOutputs</code>	Number of outputs of <code>step</code> method
	<code>isLocked</code>	Locked status for input attributes and nontunable properties
	<code>release</code>	Allow property value and input characteristics changes
	<code>step</code>	Convert input line spectral frequencies to linear prediction coefficients

**Examples** Convert line spectral frequencies to linear prediction coefficients:

```
a = [1.0000 0.6149 0.9899 0.0000 0.0031 -0.0082]'
```

```
hlpc2lsf = dsp.LPCToLSF;  
ylsf = step(hlpc2lsf, a);  
hlsf2lpc = dsp.LSFToLPC;  
ylpc = step(hlsf2lpc, ylsf) % Check values are same as a.
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the LSF/LSP to LPC Conversion block reference page. The object properties correspond to the block parameters, except:

The object does not have a property that corresponds to the **Input** block parameter. The object's behavior corresponds to the block's behavior when you set the **Input** parameter to LSF in range  $(0, \pi)$ .

## See Also

[dsp.LPCToLSF](#) | [dsp.LSPToLPC](#)

## **dsp.LSFToLPC.clone**

---

**Purpose** Create LSF to LPC object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates an LSFToLPC System object `C`, with the same property values as `H`. The clone method creates a new unlocked object.

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the `step` method

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.LSFToLPC.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the LSFToLPC System object. The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.LSFToLPC.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

<b>Purpose</b>	Convert input line spectral frequencies to linear prediction coefficients
<b>Syntax</b>	$A = \text{step}(H, \text{LSF})$
<b>Description</b>	$A = \text{step}(H, \text{LSF})$ converts the input line spectral frequencies, (LSF), in the range $(0, \pi)$ , LSF , to linear prediction coefficients, A. The input can be a vector or a matrix, where each column of the matrix is treated as a separate channel.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.LSPToLPC

---

**Purpose** Convert line spectral pairs to linear prediction coefficients

**Description** The LSPToLPC object converts line spectral pairs to linear prediction coefficients.

To convert LSP to LPC:

- 1 Define and set up your LSP to LPC converter. See “Construction” on page 5-698.
- 2 Call `step` to convert LSP according to the properties of `dsp.LSPToLPC`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.LSPToLPC` returns an LSP to LPC System object, `H`, which converts line spectral pairs (LSPs) to linear prediction coefficients (LPCs).

## Methods

<code>clone</code>	Create LSP to LPC object with same property values
<code>getNumInputs</code>	Number of expected inputs to <code>step</code> method
<code>getNumOutputs</code>	Number of outputs of <code>step</code> method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>step</code>	Convert input line spectral pairs to linear prediction coefficients

## Examples

Convert line spectral pairs to linear prediction coefficients:

```
y1sp = [0.7080 0.0103 -0.3021 -0.3218 -0.7093]';  
hlsp2lpc = dsp.LSPToLPC;
```

```
y1pc = step(hlsp2lpc, y1sp)
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the LSF/LSP to LPC Conversion block reference page. The object properties correspond to the block parameters, except:

No object property corresponds to the **Input** block parameter. The object converts LSP in the range  $(-1, 1)$  to LPC.

## See Also

[dsp.LPCToLSP](#) | [dsp.LSFToLPC](#)

# **dsp.LSPToLPC.clone**

---

**Purpose** Create LSP to LPC object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates an LSPToLPC System object `C`, with the same property values as `H`. The clone method creates a new unlocked object.

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.LSPToLPC.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the LSPToLPC System object. The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.LSPToLPC.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Convert input line spectral pairs to linear prediction coefficients

**Syntax**  $A = \text{step}(H, \text{LSP})$

**Description**  $A = \text{step}(H, \text{LSP})$  converts the input line spectral pairs in the range  $(-1, 1)$ , LSP, to linear prediction coefficients, A. The input can be a vector or a matrix, where each column of the matrix is treated as a separate channel.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.LUFactor

---

## Purpose

Factor square matrix into lower and upper triangular matrices

## Description

The LUFactor object factors a square matrix into lower and upper triangular matrices.

To factor a square matrix into lower and upper triangular matrices:

- 1 Define and set up your System object. See “Construction” on page 5-706.
- 2 Call `step` to factor the square matrix according to the properties of `dsp.LUFactor`. The behavior of `step` is specific to each object in the toolbox.

## Construction

`H = dsp.LUFactor` returns an LUFactor System object, `H`, which factors a row permutation of a square input matrix  $A$  as  $A_p = L \cdot U$ , where  $L$  is the unit-lower triangular matrix, and  $U$  is the upper triangular matrix. The row-pivoted matrix  $A_p$  contains the rows of  $A$  permuted as indicated by the permutation index vector  $P$ . The equivalent MATLAB code is `Ap = A(P, :)`.

`H = dsp.LUFactor('PropertyName', PropertyValue, ...)` returns an LUFactor object, `H`, with each specified property set to the specified value.

## Properties

### ExceptionOutputPort

Set to `true` to output singularity of input

Set this property to `true` to output the singularity of the input as logical data type values of `true` or `false`. An output of `true` indicates that the current input is singular, and an output of `false` indicates the current input is nonsingular.

### Fixed-Point Properties

### RoundingMethod

Rounding method for fixed-point operations

Specify the rounding method as

|Ceiling|Convergent|Floor|Nearest|Round|Simplest|Zero|. The default is Floor.

## **OverflowAction**

Overflow action for fixed-point operations

Specify the overflow action as Wrap or Saturate. The default is Wrap.

## **ProductDataType**

Product word and fraction lengths

Specify the product fixed-point data type as Full precision, Same as input or Custom. The default is Full precision.

## **CustomProductDataType**

Product word and fraction lengths

Specify the product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `ProductDataType` property to `Custom`. The default is `numericType([],32,30)`.

## **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point data type as Full precision, Same as input, Same as product or Custom. The default is Full precision.

## **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `AccumulatorDataType` property to `Custom`. The default is `numericType([],32,30)`.

## OutputDataType

Output word and fraction lengths

Specify the output fixed-point data type as `Same as input` or `Custom`. The default is `Same as input`.

## CustomOutputDataType

Output word and fraction lengths

Specify the output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `OutputDataType` property to `Custom`. The default is `numericType([],16,15)`.

## Methods

<code>clone</code>	Create LU Factor object with same property values
<code>getNumInputs</code>	Number of expected inputs to <code>step</code> method
<code>getNumOutputs</code>	Number of outputs of <code>step</code> method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>step</code>	Decompose matrix into lower and upper triangular matrices

## Examples

Decompose a square matrix into the lower and upper components:

```
hlu = dsp.LUFactor;  
x = rand(4)  
[LU, P] = step(hlu, x);  
L = tril(LU,-1)+diag(ones(size(LU,1),1));  
U = triu(LU);  
y = L*U
```

```
% Check back whether this equals the permuted x  
xp = x(P,:)
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the LU Factorization block reference page. The object properties correspond to the block parameters.

## See Also

dsp.LDLFactor

# dsp.LUFactor.clone

---

**Purpose** Create LU Factor object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates an LUFactor object `C`, with the same property values as `H`. The clone method creates a new unlocked object.

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, *N*, of the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.LUFactor.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the LUFactor object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.LUFactor.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Decompose matrix into lower and upper triangular matrices

**Syntax**  
[LU,P] = step(H,A)  
[LU,P,S] = step(H,A)

**Description** [LU,P] = step(H,A) decomposes the matrix A into lower and upper triangular matrices. The output LU is a composite matrix with lower triangle elements from L and upper triangle elements from U . The permutation vector P is the second output.

[LU,P,S] = step(H,A) returns an additional output S indicating if the input is singular when the ExceptionOutputPort property is set to true.

---

**Note** The object performs an initialization the first time the step method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the release method to unlock the object.

---

# dsp.MatFileReader

---

**Purpose** Read MAT file

**Description** The `MatFileReader` object reads V7.3 MAT files.

To read V7.3 MAT files:

- 1 Define and set up your System object. See “Construction” on page 5-716.
- 2 Call `step` to read the MAT file according to the properties of `dsp.MatFileReader`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.MatFileReader` returns a System object, `H`, to read data from a V7.3 MAT file.

`H = dsp.MatFileReader('PropertyName',PropertyValue,...)` returns a MAT file reader System object, `H`, with each specified property set to the specified value.

`H = dsp.MatFileReader(FILENAME,VARIABLENAME'PropertyName',PropertyValue,...)` returns a MAT file reader System object, `H`, with the `Filename` property set to `FILENAME`, the `VariableName` property set to `VARIABLENAME`, and other specified properties set to the specified values.

## Properties

### Filename

Name of MAT file from which to read

Specify the name of a MAT file as a string. Specify the full path for the file only if the file is not on the MATLAB path. The default file name is `Untitled.mat`.

### VariableName

Name of the variable to read

Name of the variable stored in and read from the MAT file. The default variable name is `x`.

## FrameBasedProcessing

Enable frame-based processing

Set this property to `true` to enable frame-based processing. Set this property to `false` to enable sample-based processing. The default is `true`.

## SamplesPerFrame

Number of samples per output frame

Specify the number of elements to read from the MAT file each time the `step` method is called. This property applies when `FrameBaseProcessing` is `true`. The default number of samples per frame is 1.

## Methods

<code>clone</code>	Create MAT file reader object with same property values
<code>isDone</code>	End-of-file status
<code>isLocked</code>	Locked status (logical) for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>reset</code>	Reset internal states of multimedia file reader to read from beginning of file
<code>step</code>	Read data from a variable in the MAT file

## Examples

Use `dsp.MatFileReader` and `dsp.MatFileWriter` to stream data.

```
filename = [tempname '.mat']; % Create variable name
```

```
originalData = rand(40,2);
```

# dsp.MatFileReader

---

```
save(filename,'originalData','-v7.3'); % Write to MAT file

H = dsp.MatFileReader(filename,'VariableName',...
    'originalData','SamplesPerFrame', 4);
while ~isDone(H) % Stream data into MATLAB
    finalData = step(H);
end
```

## See Also

dsp.MatFileWriter

**Purpose** Create MAT file reader object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a `MatFileReader` System object `C`, with the same property values as `H`.

The `clone` method creates a new unlocked object with uninitialized states.

# dsp.MatFileReader.isLocked

---

**Purpose** Locked status (logical) for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `MatFileReader` object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** End-of-file status

**Syntax** STATUS = isDone(H)

**Description** STATUS = isDone(H) returns a logical value, STATUS. When the MatFileReader object, H , reaches the end of the MAT file, STATUS is true.

# dsp.MatFileReader.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections. This method lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

<b>Purpose</b>	Reset internal states of multimedia file reader to read from beginning of file
<b>Syntax</b>	<code>reset(H)</code>
<b>Description</b>	<code>reset(H)</code> resets the <code>MatFileReader</code> object to read from the beginning of the file.

# dsp.MatFileReader.step

---

**Purpose** Read data from a variable in the MAT file

**Syntax** `X = step(H)`

**Description** `X = step(H)` reads data,  $X$ , from a variable stored in a MAT-file. The variable is assumed to be  $N$ -dimensional and a MATLAB built-in datatype. If the `FrameBasedProcessing` property is true, the data is read into MATLAB by reading along the first dimension. If `FrameBasedProcessing` is false, the data is read into MATLAB along the last dimension.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

**Purpose** Write MAT file

**Description** The MatFileWriter object writes data to a V7.3 MAT file.

To write data to a V7.3 MAT file:

- 1** Define and set up your System object. See “Construction” on page 5-725.
- 2** Call step to write data according to the properties of dsp.MatFileWriter. The behavior of step is specific to each object in the toolbox.

**Construction** H = dsp.MatFileWriter returns a MAT file writer System object, H, that writes data to a V7.3 MAT file.

H = dsp.MatFileWriter('PropertyName',PropertyValue,...) returns a MAT file writer System object, H, with each specified property set to the specified value.

H = dsp.MatFileWriter(FILENAME,'PropertyName',PropertyValue,...) returns a MAT file writer System object, H, with Filename property set to FILENAME and other specified properties set to the specified values.

**Properties** **Filename**

Name of MAT file to write

Specify the name of a MAT file as a string. Specify the full path for the file only if the file is not on the MATLAB path. The default file name is Untitled.mat.

**VariableName**

Name of the variable to write

Name of the variable to which to write. This variable is stored in the MAT file. The default variable name is x.

**FrameBasedProcessing**

# dsp.MatFileWriter

---

Enable frame-based processing

Set this property to `true` to enable frame-based processing. Set this property to `false` to enable sample-based processing. In frame-based mode, this System object streams the data to the first dimension. In sample-based mode, a new dimension is appended to the end of the data set. The default is `true`.

## Methods

<code>clone</code>	Create MAT file writer object with the same property values
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>step</code>	Write one frame of MAT file data

## Examples

Use `dsp.MatFileWriter` and `dsp.MatFileReader` to stream data.

```
% First, create a variable name
filename = [tempname '.mat'];

% Next, write that variable to a MAT-file.
hmfw = dsp.MatFileWriter(filename, 'VariableName', 'originalData')
for i=1:10
    originalData = rand(4,2);
    step(hmfw, originalData);
end
release(hmfw); % This will close the MAT file

% Finally, load the variable back into MATLAB.
data = load(filename, 'originalData');
```

## See Also

`dsp.MatFileReader`

**Purpose** Create MAT file writer object with the same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a `MatFileWriter` System object `C`, with the same property values as `H`. The clone method creates a new unlocked object.

# dsp.MatFileWriter.isLocked

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `MatFileWriter` System object `H`.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections. `release` also closes the file. This method lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

# dsp.MatFileWriter.step

---

**Purpose** Write one frame of MAT file data

**Syntax** `step(H,X)`

**Description** `step(H,X)` writes one frame of data,  $X$ , to the variable stored in the MAT file. The variable is assumed to be N-dimensional and a MATLAB built-in data type. If the `FrameBasedProcessing` property is `true`, the data is written to the file by concatenating along the first dimension. If `FrameBasedProcessing` is `false`, the data is written by appending an additional dimension to the end of the data set.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

<b>Purpose</b>	Find maximum value of input or sequence of inputs
<b>Description</b>	<p>The Maximum object finds the maximum values of an input or sequence of inputs.</p> <p>To compute the maximum value of an input or sequence of inputs:</p> <ol style="list-style-type: none"><li>1 Define and set up your System object. See “Construction” on page 5-731.</li><li>2 Call <code>step</code> to find the maximum according to the properties of <code>dsp.Maximum</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.Maximum</code> returns an object, <code>H</code>, that computes the value and index of the maximum elements in an input or a sequence of inputs along the specified <code>Dimension</code>.</p> <p><code>H = dsp.Maximum('PropertyName',PropertyValue,...)</code> returns a maximum-finding object, <code>H</code>, with each specified property set to the specified value.</p>
<b>Properties</b>	<p><b>ValueOutputPort</b></p> <p>Output maximum value</p> <p>Set this property to <code>true</code> in order to output the maximum of the input. This property applies only when you set the <code>RunningMaximum</code> property to <code>false</code>. The default is <code>true</code>.</p> <p><b>RunningMaximum</b></p> <p>Calculate over single input or multiple inputs</p> <p>When you set this property to <code>true</code>, the object computes the maximum value over successive calls to the <code>step</code> method. When you set this property to <code>false</code>, the object computes the maximum value over the current input. The default is <code>false</code>.</p> <p><b>IndexOutputPort</b></p>

Output index of maximum value

Set this property to `true` to output the index of the maximum value of the input. This property applies only when you set the `RunningMaximum` property to `false`. The default is `true`.

## **ResetInputPort**

Additional input to enable resetting of running maximum

Set this property to `true` to enable resetting the running maximum. When you set this property to `true`, you must specify a reset input to the `step` method to reset the running maximum. This property applies only when you set the `RunningMaximum` property to `true`. The default is `false`.

This property applies only when you set the `RunningMaximum` property to `true`. The default is `false`.

## **ResetCondition**

Condition that triggers resetting of running maximum

Specify the event that resets the running maximum as one of `| Rising edge | Falling edge | Either edge | Non-zero |`. This property applies only when you set the `ResetInputPort` property to `true`. The default is `Non-zero`.

## **IndexBase**

Numbering base for index of maximum value

Specify whether to start the index numbering from `One` or `Zero` when computing the index of the maximum value. This property applies only when you set the `IndexOutputPort` property to `true`. The default is `One`.

## **Dimension**

Dimension to operate along

Specify how the maximum calculation is performed over the data as one of `| All | Row | Column | Custom |`. This property applies when you set the `RunningMaximum` property to `false`. The default is `Column`.

## **CustomDimension**

Numerical dimension to calculate over

Specify the integer dimension of the input signal over which the object finds the maximum. The cannot exceed the number of dimensions in the input signal. This property only applies when you set the Dimension property to Custom. The default is 1.

## **ROIProcessing**

Enable region-of-interest processing

Set this property to true to enable calculation of the maximum value within a particular region of an image. This property applies when you set the Dimension property to All and the RunningMaximum property to false. The default is false.

For full ROI processing support, install the Computer Vision System Toolbox product. If you only have the DSP System Toolbox product installed, you can only specify the value of the ROIForm property as Rectangles.

## **ROIForm**

Type of region of interest

Specify the type of region of interest as one of | Rectangles | Lines | Label matrix | Binary mask |. This property applies only when you set the ROIProcessing property to true. The default is Rectangles.

For full ROI processing support, install the Computer Vision System Toolbox product. If you have only the DSP System Toolbox product installed, you can only specify the as Rectangles.

## **ROIPortion**

Calculate over entire ROI or just perimeter

Specify whether to calculate the maximum over the Entire ROI or the ROI perimeter. This property applies only when you set the ROIForm property to Rectangles. The default is Entire ROI.

## **ROIStatistics**

Calculate statistics for each ROI or one for all ROIs

Specify whether to calculate Individual statistics for each ROI or a Single statistic for all ROIs. This property applies only when you set the ROIForm property to Rectangles, Lines, or Label matrix.

## **ValidityOutputPort**

Output flag indicating if any part of ROI is outside input image

When you set the ROIForm property to one of | Lines | Rectangles |, set this property to true to return the validity of the specified ROI being completely inside of the image. When you set the ROIForm property to Label Matrix, set this property to true to return the validity of the specified label numbers. The default is false.

## **FrameBasedProcessing**

Process input as frames or samples

Set this property to true to enable frame-based processing for 2-D inputs. Set this property to false to enable sample-based processing. The object always performs sample-based processing for N-D inputs where N is greater than 2. This property applies when you set the RunningMaximum to true. The default is true.

## **Fixed-Point Properties**

### **RoundingMethod**

Rounding method for fixed-point operations

Specify the rounding method as one of | Ceiling | Convergent | Floor | Nearest | Round | Simplest | Zero |. The default is Floor.

### **OverflowAction**

Action to take when integer input is out-of-range

Specify the overflow action as one of | Wrap | Saturate |. The default is Wrap.

## **ProductDataType**

Data type of product

Specify the product fixed-point data type as one of | Same as input | Custom |. The default is Same as input.

## **CustomProductDataType**

Product word and fraction lengths

Specify the product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `AccumulatorDataType` property to `Custom`. The default is `numericType([],32,30)`.

## **AccumulatorDataType**

Data type of accumulator

Specify the accumulator fixed-point data type as one of | Same as product | Same as input | Custom |. The default is Same as product.

## **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `AccumulatorDataType` property to `Custom`. The default is `numericType([],32,30)`.

## **Methods**

<code>clone</code>	Create maximum-finding object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method

# dsp.Maximum

---

getNumOutputs	Number of outputs of step method
isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
reset	Reset computation of running maximum
step	Maximum value

## Examples

Find a maximum value and its index:

```
hmax1 = dsp.Maximum;  
x = randn(100,1);  
[y, I] = step(hmax1, x);
```

---

Compute a running maximum:

```
hmax2 = dsp.Maximum;  
hmax2.RunningMaximum = true;  
x = randn(100,1);  
y = step(hmax2, x);  
% y(i) is the maximum of all values in the vector x(1:i)
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Maximum block reference page. The object properties correspond to the block parameters, except:

**Treat sample-based row input as a column** block parameter is not supported by the dsp.Maximum object.

Both this object and its corresponding block let you specify whether to process inputs as individual samples or as frames of data. The object uses the FrameBasedProcessing property. The block uses the **Input**

**processing** parameter. See “Set the FrameBasedProcessing Property of a System object” for more information.

## See Also

dsp.Minimum | dsp.Mean

# **dsp.Maximum.clone**

---

**Purpose** Create maximum-finding object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a Maximum object C, with the same property values as H. The `clone` method creates a new unlocked object with uninitialized states.

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.Maximum.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `Maximum` object `H`.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.Maximum.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose**            Reset computation of running maximum

**Syntax**            `reset(H)`

**Description**        `reset(H)` resets the computation of the running maximum for the `Maximum` object `H`.

# dsp.Maximum.step

---

## Purpose

Maximum value

## Syntax

```
[VAL,IND] = step(H,X)
VAL = step(H,X)
IND = step(H,X)
VAL = step(H,X,R)
[...] = step(H,I,ROI)
[...] = step(H,I,LABEL,LABELNUMBERS)
[... ,FLAG] = step(H,I,ROI)
[... ,FLAG] = step(H,I,LABEL,LABELNUMBERS)
```

## Description

`[VAL,IND] = step(H,X)` returns the maximum value, `VAL`, and the index or position of the maximum value, `IND`, along the specified Dimension of `X`.

`VAL = step(H,X)` returns the maximum value, `VAL`, of the input `X`. When the `RunningMaximum` property is true, `VAL` corresponds to the maximum value over successive calls to the `step` method.

`IND = step(H,X)` returns the zero- or one-based index `IND` of the maximum value. To enable this type of processing, set the `IndexOutputPort` property to true and the `ValueOutputPort` and `RunningMaximum` properties to false.

`VAL = step(H,X,R)` resets the state of `H` based on the value of reset signal, `R`, and the `ResetCondition` property. To enable this type of processing, set the `RunningMaximum` property to true and the `ResetInputPort` property to true.

`[...] = step(H,I,ROI)` computes the maximum of an input image, `I`, within the given region of interest, `ROI`. To enable this type of processing, set the `ROIProcessing` property to true and the `ROIForm` property to `Lines`, `Rectangles` or `Binary mask`.

`[...] = step(H,I,LABEL,LABELNUMBERS)` computes the maximum of an input image, `I`, for a region whose labels are specified in the vector `LABELNUMBERS`. To enable this type of processing, set the `ROIProcessing` property to true and the `ROIForm` property to `Label matrix`.

[...,FLAG] = step(H,I,ROI) returns FLAG, indicating whether the given region of interest is within the image bounds. To enable this type of processing, set the ROIProcessing and ValidityOutputPort properties to true and the ROIForm property to Lines, Rectangles or Binary mask.

[...,FLAG] = step(H,I,LABEL,LABELNUMBERS) returns FLAG, indicating whether the input label numbers are valid. To enable this type of processing, set the ROIProcessing and ValidityOutputPort properties to true and the ROIForm property to Label matrix.

For full ROI processing support, install the Computer Vision System Toolbox product. If you only have the DSP System Toolbox product installed, you can only specify the value of the ROIForm property as Rectangles.

---

**Note** The object performs an initialization the first time the step method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the release method to unlock the object.

---

# dsp.Mean

---

**Purpose** Find mean value of input or sequence of inputs

**Description** The Mean object finds the mean of an input or sequence of inputs.  
To compute the mean of an input or sequence of inputs:

- 1 Define and set up your System object. See “Construction” on page 5-746.
- 2 Call `step` to compute the mean according to the properties of `dsp.Mean`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.Mean` returns an object, `H`, that computes the mean of an input or a sequence of inputs.

`H = dsp.Mean('PropertyName',PropertyValue,...)` returns a mean-finding object, `H`, with each specified property set to the specified value.

## Properties

### RunningMean

Calculate over single input or multiple inputs

When you set this property to `true`, the object calculates the mean over successive calls to the `step` method. When you set this property to `false`, the object computes the mean over the current input. The default is `false`.

### ResetInputPort

Additional input to enable resetting of running mean

Set this property to `true` to enable resetting of the running mean. When you set this property to `true`, you must specify a reset input to the `step` method to reset the running mean. This property applies only when you set the `RunningMean` property to `true`. The default is `false`.

### ResetCondition

Condition that triggers resetting of running mean

Specify the event that resets the running maximum as one of | Rising edge | Falling edge | Either edge | Non-zero |. This property applies only when you set the ResetInputPort property to true. The default is Non-zero.

### **Dimension**

Dimension to operate along

Specify how the mean calculation is performed over the data as one of | All | Row | Column | Custom |. This property applies when you set the RunningMean property to false. The default is Column.

### **CustomDimension**

Numerical dimension to calculate over

Specify the integer dimension, indexed from one, of the input signal over which the object calculates the mean. The value cannot exceed the number of dimensions in the input signal. This property only applies when you set the Dimension property to Custom. The default is 1.

### **ROIProcessing**

Enable region-of-interest processing

Set this property to true to enable calculation of the mean within a particular region of an image. This property applies when you set the Dimension property to All and the RunningMean property to false. The default is false.

For full ROI processing support, install the Computer Vision System Toolbox product. If you only have the DSP System Toolbox product installed, you can only specify the value of the ROIForm property as Rectangles.

### **ROIForm**

Type of region of interest

Specify the type of region of interest as one of | Rectangles | Lines | Label matrix |. This property applies only when you set the ROIProcessing property to true. The default is Rectangles.

For full ROI processing support, install the Computer Vision System Toolbox product. If you have only the DSP System Toolbox product installed, you can only specify the as Rectangles.

## **ROIPortion**

Calculate over entire ROI or just perimeter

Specify whether to calculate the mean over the Entire ROI or the ROI perimeter. This property applies only when you set the ROIForm property to Rectangles. The default is Entire ROI.

## **ROIStatistics**

Calculate statistics for each ROI or one for all ROIs

Specify whether to calculate Individual statistics for each ROI or a Single statistic for all ROIs. This property applies only when you set the ROIForm property to Rectangles, Lines, or Label matrix. The default is Individual statistics for each ROI.

## **ValidityOutputPort**

Output flag indicating if any part of ROI is outside input image

When you set the ROIForm property to one of | Lines | Rectangles | Binary mask |, set this property to true to return the validity of the specified ROI being completely inside of the image. When you set the ROIForm property to Label Matrix, set this property to true to return the validity of the specified label numbers. The default is false.

## **FrameBasedProcessing**

Process input as frames or samples

Set this property to true to enable frame-based processing for 2-D inputs. Set this property to false to enable sample-based

processing. The object always performs sample-based processing for N-D inputs where N is greater than 2. This property applies when you set the `RunningMean` to true. The default is true.

### **Fixed-Point Properties**

#### **RoundingMethod**

Rounding method for fixed-point operations

Specify the rounding method as one of | `Ceiling` | `Convergent` | `Floor` | `Nearest` | `Round` | `Simplest` | `Zero` |. The default is `Floor`.

#### **OverflowAction**

Action to take when integer input is out-of-range

Specify the overflow action as one of | `Wrap` | `Saturate` |. The default is `Wrap`.

#### **AccumulatorDataType**

Data type of accumulator

Specify the accumulator fixed-point data type as one of | `Same as input` | `Custom` |. The default is `Same as input`.

#### **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `AccumulatorDataType` property to `Custom`. The default is `numericType([],32,30)`.

#### **OutputDataType**

Data type of output

Specify the output fixed-point data type as one of | `Same as accumulator` | `Same as input` | `Custom` |. The default is `Same as accumulator`.

## CustomOutputDataType

Output word and fraction lengths

Specify the output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `OutputDataType` property to `Custom`. The default is `numericType([],32,30)`.

## Methods

<code>clone</code>	Create mean object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>reset</code>	Reset internal states of mean-finding object
<code>step</code>	Mean value

## Examples

Compute the mean of a signal:

```
hmean1 = dsp.Mean;  
x = randn(100,1);  
y = step(hmean1, x);
```

---

Compute the running mean of a signal:

```
hmean2 = dsp.Mean;  
hmean2.RunningMean = true;  
x = randn(100,1);
```

```
y = step(hmean2, x);  
% y(i) is the mean of all values in the vector x(1:i)
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Mean block reference page. The object properties correspond to the block parameters, except:

**Treat sample-based row input as a column** block parameter is not supported by the `dsp.Mean` object.

Both this object and its corresponding block let you specify whether to process inputs as individual samples or as frames of data. The object uses the `FrameBasedProcessing` property. The block uses the **Input processing** parameter. See “Set the `FrameBasedProcessing` Property of a System object” for more information.

## See Also

`dsp.Maximum` | `dsp.Minimum`

# dsp.Mean.clone

---

**Purpose** Create mean object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a Mean object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with uninitialized states.

**Purpose** Number of expected inputs to step method

**Syntax** N = getNumInputs(H)

**Description** N = getNumInputs(H) returns the number of expected inputs, N, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.Mean.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the Mean object H.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.Mean.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Reset internal states of mean-finding object

**Syntax** reset(H)

**Description** reset(H) sets the internal states of the Mean object H to their initial values.

# dsp.Mean.step

---

**Purpose** Mean value

**Syntax**

```
Y = step(H,X)
Y = step(H,X,R)
Y = step(H,X,ROI)
Y = step(H,X,LABEL,LABELNUMBERS)
[Y,FLAG] = step(H,X,ROI)
[Y,FLAG] = step(H,X,LABEL,LABELNUMBERS)
```

**Description** `Y = step(H,X)` computes the mean of `X`. When you set the `RunningMean` property to `true`, `Y` corresponds to the mean successive calls to the `step` method.

`Y = step(H,X,R)` resets the computation of the running mean based on the value of the reset signal, `R`, and the `ResetCondition` property. To enable this type of processing, set the `RunningMean` property to `true` and the `ResetInputPort` property to `true`.

`Y = step(H,X,ROI)` computes the mean of input image `X` within the given region of interest `ROI`. To enable this type of processing, set the `ROIProcessing` property to `true` and the `ROIForm` property to `Lines`, `Rectangles` or `Binary mask`.

`Y = step(H,X,LABEL,LABELNUMBERS)` computes the mean of the input image, `X`, for the region whose labels are specified in the vector `LABELNUMBERS`. The regions are defined and labeled in the matrix `LABEL`. To enable this type of processing, set the `ROIProcessing` property to `true` and the `ROIForm` property to `Label matrix`.

`[Y,FLAG] = step(H,X,ROI)` returns `FLAG`, indicating whether the given region of interest `ROI`, is within the image bounds. To enable this type of processing, set the `ROIProcessing` and `ValidityOutputPort` properties to `true` and the `ROIForm` property to `Lines`, `Rectangles` or `Binary mask`.

`[Y,FLAG] = step(H,X,LABEL,LABELNUMBERS)` returns `FLAG` which indicates whether the input label numbers are valid. To enable this type of processing, set the `ROIProcessing` and `ValidityOutputPort` properties to `true` and the `ROIForm` property to `Label matrix`.

For full ROI processing support, install the Computer Vision System Toolbox product. If you have only the DSP System Toolbox product installed, you can only specify the value of this property as `Rectangles`.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.Median

---

**Purpose** Median value of input

**Description** The Median object computes the median value of the input. The object can compute the median along each dimension (row or column) of the input or of the entire input.

To compute the median of the input:

- 1 Define and set up your median System object. See “Construction” on page 5-760.
- 2 Call `step` to compute the median according to the properties of `dsp.Median`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.Median` returns a median System object, `H`, that computes the median along the columns of the input using the `Quick sort` sorting method.

`H = dsp.Median('PropertyName',PropertyValue,...)` returns a median System object, `H`, with each property set to the value you specify.

**Properties** **SortMethod**

Sort method

Specify the method the object should use to sort the data before computing the median. You can specify `Quick sort` or `Insertion sort`. The quick sort algorithm uses a recursive sort method and is faster at sorting more than 32 elements. The insertion sort algorithm uses a nonrecursive method and is faster at sorting less than 32 elements. If you are using the Median object to generate code, you should use the insertion sort algorithm to prevent recursive function calls in your generated code. The default is `Quick sort`.

**Dimension**

Dimension to operate along

Specify the dimension along which the object computes the median values. You can specify one of | All | Row | Column | Custom |. The default is Column.

## **CustomDimension**

Numerical dimension to operate along

Specify the dimension of the input signal (as a one-based value), over which the object computes the median. The cannot exceed the number of dimensions in the input signal. This property applies only when you set the Dimension property to Custom. The default is 1.

## **Fixed-Point Properties**

### **RoundingMethod**

Rounding method for fixed-point operations

Specify the rounding method as one of | Ceiling | Convergent | Floor | Nearest | Round | Simplest | Zero |. The default is Floor.

### **OverflowAction**

Overflow action for fixed-point operations

Specify the overflow action as one of | Wrap | Saturate |. The default is Wrap.

### **ProductDataType**

Product word and fraction lengths

Specify the product data type as one of | Same as input | Custom |. The default is Same as input.

### **CustomProductDataType**

Product word and fraction lengths

Specify the product data type as a scaled `numericType` object with a Signedness of Auto. This property applies only when

you set the `ProductDataType` property to `Custom`. The default is `numerictype([],32,30)`.

## **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator data type as one of `| Same as product | Same as input | Custom |`. The default is `Same as product`.

## **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the fixed-point accumulator data type as a scaled `numerictype` object with a `Signedness` of `Auto`. This property applies only when you set the `AccumulatorDataType` property to `Custom`. The default is `numerictype([],32,30)`.

## **OutputDataType**

Output word and fraction lengths

Specify the output data type as one of `| Same as accumulator | Same as product | Same as input | Custom |`. The default is `Same as accumulator`.

## **CustomOutputDataType**

Output word and fraction lengths

Specify the data type of the output as a scaled `numerictype` object with a `Signedness` of `Auto`. This property applies only when you set the `OutputDataType` property to `Custom`. The default is `numerictype([],16,15)`.

## **Methods**

<code>clone</code>	Create median object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method

getNumOutputs	Number of outputs of step method
isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
step	Median value

## Examples

Compute the median value of the input column:

```
h = dsp.Median;  
x = [7 -9 0 -1 2 0 3 5 -9]';  
y = step(h, x)
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Median block reference page. The object properties correspond to the block properties, except:

**Treat sample-based row input as a column** block parameter is not supported by the dsp.Median System object.

## See Also

dsp.Mean | dsp.Minimum | dsp.Maximum | dsp.Variance

## **dsp.Median.clone**

---

**Purpose** Create median object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a median object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object.

**Purpose** Number of expected inputs to step method

**Syntax** N = getNumInputs(H)

**Description** N = getNumInputs(H) returns the number of expected inputs, N, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.Median.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the Median System object H. The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.Median.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Median value

**Syntax**  $Y = \text{step}(H,X)$

**Description**  $Y = \text{step}(H,X)$  computes the median value of the input  $X$  and returns the result in  $Y$ .

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.Minimum

---

**Purpose** Find minimum values of input or sequence of inputs

**Description** The Minimum object finds the minimum value of an input or sequence of inputs.

To compute the minimum value of an input or sequence of inputs:

- 1** Define and set up your System object. See “Construction” on page 5-770.
- 2** Call `step` to compute the minimum according to the properties of `dsp.Minimum`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.Minimum` returns an object, `H`, that computes the value and/or index of the minimum elements in an input or a sequence of inputs over the specified `Dimension`.

`H = dsp.Minimum('PropertyName',PropertyValue,...)` returns a minimum-finding object, `H`, with each specified property set to the specified value.

**Properties** **ValueOutputPort**

Output minimum value

Set this property to `true` in order to output the minimum value of the input. This property applies only when you set the `theRunningMinimum` property to `false`. The default is `true`.

**RunningMinimum**

Calculate over single input or multiple inputs

When you set this property to `true`, the object computes the minimum value over successive calls to the `step` method. When you set this property to `false`, the object computes the minimum value over the current input. The default is `false`.

**IndexOutputPort**

Output index of minimum value

Set this property to `true` to output the index of the minimum value of the input. This property applies only when you set the `RunningMinimum` property to `false`. The default is `true`.

## **ResetInputPort**

Additional input to enable resetting of running minimum

Set this property to `true` to enable resetting of the running minimum. When you set this property to `true`, you must specify a reset input to the `step` method to reset the running minimum. This property applies only when you set the `RunningMinimum` property to `true`. The default is `false`.

## **ResetCondition**

Condition that triggers resetting of running minimum

Specify the event that resets the running minimum as one of | `Rising edge` | `Falling edge` | `Either edge` | `Non-zero` |. This property applies only when you set the `ResetInputPort` property to `true`. The default is `Non-zero`.

## **IndexBase**

Numbering base for index of minimum value

Specify the numbering used when computing the index of the minimum value as starting from either `One` or `Zero`. This property applies only when you set the `IndexOutputPort` property to `true`. The default is `One`.

## **Dimension**

Dimension to operate along

Specify how the minimum calculation is performed over the data as one of | `All` | `Row` | `Column` | `Custom` |. This property applies when you set the `RunningMinimum` property to `false`. The default is `Column`.

## **CustomDimension**

Numerical dimension to calculate over

Specify the integer dimension of the input signal over which the object finds the minimum. The cannot exceed the number of dimensions in the input signal. This property only applies when you set the `Dimension` property to `Custom`. The default is 1.

## **ROIProcessing**

Enable region-of-interest processing

Set this property to `true` to enable calculation of the minimum value within a particular region of an image. This property applies when you set the `Dimension` property to `All` and the `RunningMinimum` property to `false`. The default is `false`.

For full ROI processing support, install the Computer Vision System Toolbox product. If you only have the DSP System Toolbox product installed, you can only specify the value of the `ROIForm` property as `Rectangles`.

## **ROIForm**

Type of region of interest

Specify the type of region of interest as one of `Rectangles` | `Lines` | `Label matrix` | `Binary mask` |. This property applies only when you set the `ROIProcessing` property to `true`. The default is `Rectangles`.

For full ROI processing support, install the Computer Vision System Toolbox product. If you have only the DSP System Toolbox product installed, you can only specify the as `Rectangles`.

## **ROIPortion**

Calculate over entire ROI or just perimeter

Specify whether to calculate the minimum over the `Entire ROI` or the `ROI perimeter`. This property applies only when you set the `ROIForm` property to `Rectangles`. The default is `Entire ROI`.

## **ROIStatistics**

Calculate statistics for each ROI or one for all ROIs

Specify whether to calculate Individual statistics for each ROI or a Single statistic for all ROIs. This property applies only when you set the ROIForm property to Rectangles, Lines, or Label matrix.

## **ValidityOutputPort**

Output flag indicating if any part of ROI is outside input image

When you set the ROIForm property to Lines or Rectangles, set this property to true to return the validity of the specified ROI being completely inside of the image. When you set the ROIForm property to Label Matrix, set this property to true to return the validity of the specified label numbers. The default is false.

## **FrameBasedProcessing**

Process input as frames or samples

Set this property to true to enable frame-based processing for 2-D inputs. Set this property to false to enable sample-based processing. The object always performs sample-based processing for N-D inputs where N is greater than 2. This property applies when you set the RunningMinimum to true. The default is true.

## **Fixed-Point Properties**

### **RoundingMethod**

Rounding method for fixed-point operations

Specify the rounding method as one of | Ceiling | Convergent | Floor | Nearest | Round | Simplest | Zero |. The default is Floor.

### **OverflowAction**

Action to take when integer input is out-of-range

Specify the overflow action as one of | Wrap | Saturate |. The default is Wrap.

## **ProductDataType**

Data type of product

Specify the product fixed-point data type as one of | Same as input | Custom |. The default is Same as input.

## **CustomProductDataType**

Product word and fraction lengths

Specify the product fixed-point type as a scaled numeric type object with a Signedness of Auto. This property applies only when you set the AccumulatorDataType property to Custom. The default is numeric type([],32,30).

## **AccumulatorDataType**

Data type of accumulator

Specify the accumulator fixed-point data type as one of | Same as product | Same as input | Custom |. The default is Same as product.

## **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled numeric type object with a Signedness of Auto. This property applies only when you set the AccumulatorDataType property to Custom. The default is numeric type([],32,30).

## **Methods**

clone	Create minimum-finding object with same property values
getNumInputs	Number of expected inputs to step method
getNumOutputs	Number of outputs of step method

isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
reset	Reset internal states of minimum-finding object
step	Operate on inputs to calculate outputs

## Examples

Find a minimum value and its index:

```
hmin1 = dsp.Minimum;  
x = randn(100,1);  
[y, I] = step(hmin1, x);
```

---

Compute a running minimum:

```
hmin2 = dsp.Minimum;  
hmin2.RunningMinimum = true;  
x = randn(100,1);  
y = step(hmin2, x);  
% y(i) is the minimum of all values in the vector x(1:i)
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Minimum block reference page. The object properties correspond to the block parameters, except:

**Treat sample-based row input as a column** block parameter is not supported by the dsp.Minimum object.

Both this object and its corresponding block let you specify whether to process inputs as individual samples or as frames of data. The object uses the FrameBasedProcessing property. The block uses the **Input**

# dsp.Minimum

---

**processing** parameter. See “Set the FrameBasedProcessing Property of a System object” for more information.

## See Also

dsp.Maximum | dsp.Mean

<b>Purpose</b>	Create minimum-finding object with same property values
<b>Syntax</b>	<code>C = clone(H)</code>
<b>Description</b>	<code>C = clone(H)</code> creates a Minimum object C, with the same property values as H. The <code>clone</code> method creates a new unlocked object with uninitialized states.

# **dsp.Minimum.getNumInputs**

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**      `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose** Number of outputs of step method

**Syntax** N = getNumOutputs(H)

**Description** N = getNumOutputs(H) returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# dsp.Minimum.isLocked

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** isLocked(H)

**Description** isLocked(H) returns the locked state of the Minimum object H.

The isLocked method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the step method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the isLocked method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

## **dsp.Minimum.reset**

---

**Purpose**            Reset internal states of minimum-finding object

**Syntax**            reset(H)

**Description**        reset(H) sets the internal states of the Minimum object H to their initial values.

## Purpose

Operate on inputs to calculate outputs

## Syntax

```
[VAL,IND] = step(H,X)
VAL = step(H,X)
IND = step(H,X)
VAL = step(H,X,R)
[...] = step(H,I,ROI)
[...] = step(H,I,LABEL,LABELNUMBERS)
[... ,FLAG] = step(H,I,ROI)
[... ,FLAG] = step(H,I,LABEL,LABELNUMBERS)
```

## Description

`[VAL,IND] = step(H,X)` returns the minimum value, `VAL`, and the index or position of the minimum value, `IND`, along the specified Dimension of `X`.

`VAL = step(H,X)` returns the minimum value, `VAL`, of the input `X`. When the `RunningMinimum` property is true, `VAL` corresponds to the minimum value over successive calls to the `step` method.

`IND = step(H,X)` returns the zero- or one-based index `IND` of the minimum value when the `IndexOutputPort` property is true and the `ValueOutputPort` property is false. You must set the `RunningMinimum` property to false to use this syntax.

`VAL = step(H,X,R)` resets the state of `H` based on the value of reset signal, `R`, and the `ResetCondition` property. To enable this type of processing, set the `RunningMinimum` property to true and the `ResetInputPort` property to true.

`[...] = step(H,I,ROI)` computes the minimum of an input image, `I`, within the given region of interest, `ROI`. To enable this type of processing, set the `ROIProcessing` property to true and the `ROIForm` property to `Lines`, `Rectangles` or `Binary mask`.

`[...] = step(H,I,LABEL,LABELNUMBERS)` computes the minimum of an input image, `I`, for a region whose labels are specified in the vector `LABELNUMBERS`. This property applies only when you set the `ROIProcessing` property to true and the `ROIForm` property to `Label matrix`.

## dsp.Minimum.step

---

[...,FLAG] = step(H,I,ROI) returns FLAG, indicating whether the given region of interest is within the image bounds. To enable this type of processing, set the ROIProcessing and ValidityOutputPort properties to true and the ROIForm property to Lines, Rectangles or Binary mask.

[...,FLAG] = step(H,I,LABEL,LABELNUMBERS) returns FLAG, indicating whether the input label numbers are valid. To enable this type of processing, set the ROIProcessing and ValidityOutputPort properties to true and the ROIForm property to Label matrix.

For full ROI processing support, install the Computer Vision System Toolbox product. If you have only the DSP System Toolbox product installed, you can only specify the value of the ROIForm property as Rectangles.

---

**Note** The object performs an initialization the first time the step method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the release method to unlock the object.

---

**Purpose** Read video frames, audio samples, or both from multimedia file

---

**Note** MultimediaFileReader will be removed in a future release. Use AudioFileReader instead. See dsp.AudioFileReader.

---

**Description** The MultimediaFileReader object reads video frames, audio samples, or both from a multimedia file.

To read video frames, audio samples, or both from a multimedia file:

- 1** Define and set up your multimedia file reader. See “Construction” on page 5-785.
- 2** Call step to read from a multimedia file according to the properties of signalblks.MultimediaFileReader. The behavior of step is specific to each object in the toolbox.

**Construction** H = signalblks.MultimediaFileReader returns a multimedia file reader System object, H, to read video and/or audio from a multimedia file.

H =  
signalblks.MultimediaFileReader('PropertyName',PropertyValue,...)  
returns a multimedia file reader System object, H, with each specified property set to the specified value.

H =  
signalblks.MultimediaFileReader(FILENAME,'PropertyName',PropertyValue,...)  
returns a multimedia file reader System object, H, with Filename property set to FILENAME and other specified properties set to the specified values.

**Properties** **Filename**

Name of multimedia file from which to read

# signalblks.MultimediaFileReader

---

Specify the name of a multimedia file as a string. Specify the full path for the file only if the file is not on the MATLAB path. On UNIX platforms, the multimedia file reader only supports uncompressed AVI files. The default is `speech_dft.avi`.

## **PlayCount**

Number of times to play file

Specify a positive integer or `inf` to represent the number of times to play the file. The default is `inf`.

## **AudioOutputPort**

Choose to output audio data

Use this property to control the audio output from the multimedia file reader. This property applies only when a multimedia file contains both audio and video streams. The default is `true`.

## **VideoOutputPort**

Choose to output video data

Use this property to control the video output from the multimedia file reader. This property only applies when a multimedia file contains both audio and video streams. The default is `false`.

## **SamplesPerAudioFrame**

Number of samples per audio frame

Specify the number of samples per audio frame as a positive scalar integer value. This property applies when the multimedia file contains only audio data. The default is `1024`.

## **ImageColorSpace**

Choose whether output is RGB, intensity, or YCbCr

Specify whether you want the multimedia file reader to output RGB, Intensity, or YCbCr 4:2:2 video frames. This property applies only when the multimedia file contains video. The default is RGB.

## VideoOutputDataType

Data type of video data output

Set the data type of the video data output from the multimedia file reader. The multimedia file reader supports the following output data types: `double`, `single`, `int8`, `uint8`, `int16`, `uint16`, `int32`, `uint32` or `Inherit`. This property applies if the multimedia file contains video. The default is `single`.

## AudioOutputDataType

Data type of audio samples output

Set the data type of the audio data output from the multimedia file reader. The multimedia file reader supports the following output data types: `double`, `single`, `int16`, `uint8`. This property applies only if the multimedia file contains audio. The default is `int16`.

## Methods

<code>clone</code>	Create multimedia file reader object with same property values
<code>close</code>	Release resources
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>info</code>	Information about specific multimedia file
<code>isDone</code>	End-of-file status (logical)
<code>isLocked</code>	Locked status for input attributes and nontunable properties

# signalblks.MultimediaFileReader

---

reset	Reset internal states of multimedia file reader to read from beginning of file
step	Output one frame of video frames, audio samples, or both to multimedia signal

## Examples

Read an audio file and play the file back using the standard audio output device:

```
hmfr = signalblks.MultimediaFileReader('speech_dft.avi');
hap = dsp.AudioPlayer('SampleRate', 22050);
while ~isDone(hmfr)
    audio = step(hmfr);
    step(hap, audio);
end
close(hmfr); % close the input file
close(hap); % close the audio output device
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the From Multimedia File block reference page. The object properties correspond to the block parameters, except:

- The object has no corresponding property for the **Inherit sample time from file** block parameter. The object always inherits the sample time from the file.
- The object has no corresponding property for the **Output end-of-file indicator** parameter. The object always outputs EOF as the last output.
- The **Multimedia outputs** block parameter corresponds to both the AudioOutputPort and the VideoOutputPort object properties.
- The object has no corresponding property for the **Image signal** block parameter. The object always outputs an  $M$ -by- $N$ -by- $P$  color video signal.

**See Also** `signalblks.MultimediaFileWriter`

# signalblks.MultimediaFileReader.clone

---

**Purpose** Create multimedia file reader object with same property values

---

**Note** MultimediaFileReader will be removed in a future release. Use AudioFileReader instead. See dsp.AudioFileReader.clone.

---

**Syntax** C = clone(H)

**Description** C = clone(H) creates a MultimediaFileReader System object C, with the same property values as H.

The clone method creates a new unlocked object with uninitialized states.

**Purpose** Release resources

---

**Note** MultimediaFileReader will be removed in a future release. Use AudioFileReader instead. See dsp.AudioFileWriter.release .

---

**Syntax** close(H)

**Description** close(H) releases system resources (such as memory, file handles or hardware connections).

# signalblks.MultimediaFileReader.getNumInputs

---

**Purpose** Number of expected inputs to step method

---

**Note** MultimediaFileReader will be removed in a future release. Use AudioFileReader instead. See dsp.AudioFileReader.getNumInputs.

---

**Syntax** N = getNumInputs(H)

**Description** N = getNumInputs(H) returns the number of outputs, N, to the step method

The getNumInputs method returns a positive integer that is the number of expected inputs (not counting the object itself) to the step method. This value will change if you alter any properties that turn inputs on or off. You must call the step method with the number of input arguments equal to the result of getNumInputs(H).

# signalblks.MultimediaFileReader.getNumOutputs

---

**Purpose** Number of outputs of step method

---

**Note** MultimediaFileReader will be removed in a future release. Use AudioFileReader instead. See dsp.AudioFileReader.getNumOutputs.

---

**Syntax** N = getNumOutputs(H)

**Description** N = getNumOutputs(H) returns the number of outputs, N, of the step method

The getNumOutputs method returns a positive integer that is the number of outputs from the step method. This value will change if you alter any properties that turn outputs on or off.

# signalblks.MultimediaFileReader.info

**Purpose** Information about specific multimedia file

---

**Note** `MultimediaFileReader` will be removed in a future release. Use `AudioFileReader` instead. See `dsp.AudioFileReader.info`.

---

**Syntax** `S = info(H)`

**Description** `S = info(H)` returns a MATLAB structure, `S`, with information about the multimedia file specified in the `Filename` property. The number of fields for `S` varies depending on the audio or video content of the file. The possible fields and values for the structure `S` are shown in the following table.

Field	Value
Audio	Logical value indicating if the file has audio content.
Video	Logical value indicating if the file has video content.
AudioSampleRate	Audio sampling rate of the multimedia file in hertz. This field is available when the file has audio content.
AudioNumBits	Number of bits used to encode the audio stream. This field is available when the file has audio content.
AudioNumChannels	Number of audio channels. This field is available when the file has audio content.
FrameRate	Frame rate of the video stream in frames per second. The value may vary from the actual frame rate of the recorded video, and considers any synchronization issues between audio and video streams when the file contains both audio and video content. This variation indicates that video frames may be dropped if the audio stream leads the video stream by more than $1/(\text{actual video frames per second})$ . This field is available when the file has video content.

<b>Field</b>	<b>Value</b>
VideoSize	Video size as a two-element numeric vector of the form [VideoWidthInPixels, VideoHeightInPixels]. This field is available when the file has video content.
VideoFormat	Video signal format. This field is available when the file has video content.

# signalblks.MultimediaFileReader.isDone

---

**Purpose** End-of-file status (logical)

---

**Note** `MultimediaFileReader` will be removed in a future release. Use `AudioFileReader` instead. See `dsp.AudioFileReader.isDone`.

---

**Syntax** `STATUS = isDone(H)`

**Description** `STATUS = isDone(H)` returns a logical value, `STATUS`, when the `MultimediaFileReader` object, `H`, reaches the end of the multimedia file. If you set the `PlayCount` property to a value greater than 1, `STATUS` is true each time the object reaches the end of the file. `STATUS` is the same as the EOF output value in the process method syntax.

# signalblks.MultimediaFileReader.isLocked

---

**Purpose** Locked status for input attributes and nontunable properties

---

**Note** MultimediaFileReader will be removed in a future release. Use AudioFileReader instead. See dsp.AudioFileReader.isLocked.

---

**Syntax** isLocked(H)

**Description** isLocked(H) returns the locked state of the MultimediaFileReader object.

The isLocked method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the step method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the isLocked method returns a true value.

# signalblks.MultimediaFileReader.reset

---

**Purpose** Reset internal states of multimedia file reader to read from beginning of file

---

**Note** `MultimediaFileReader` will be removed in a future release. Use `AudioFileReader` instead. See `dsp.AudioFileReader.reset`.

---

**Syntax** `reset(H)`

**Description** `reset(H)` resets the `MultimediaFileReader` object to read from the beginning of the file.

## Purpose

Output one frame of video frames, audio samples, or both to multimedia signal

---

**Note** `MultimediaFileReader` will be removed in a future release. Use `AudioFileReader` instead. See `dsp.AudioFileReader.step`.

---

## Syntax

```
AUDIO = step(H)
I = step(H)
[I,AUDIO] = step(H)
[... ,EOF] = step(H)
[Y,CB,CR] = step(H)
[Y,CB,CR,AUDIO] = step(H)
```

## Description

`AUDIO = step(H)` outputs one frame of audio samples, `AUDIO`. This behavior requires the `AudioOutputPort` property to be true and an input file that contains audio data. After the object plays the file the number of times `PlayCount` specifies, `AUDIO` contains silence.

`I = step(H)` outputs one frame of multidimensional video signal, `I`. To obtain this behavior, set the `VideoOutputPort` property to true and use an input file that contains video data.

`[I,AUDIO] = step(H)` outputs one frame of multidimensional video signal, `I`, and one frame of audio samples, `AUDIO`. This behavior requires the `AudioOutputPort` and `VideoOutputPort` properties to be true and an input file that contains audio and video data.

`[... ,EOF] = step(H)` gives the end-of-file indicator in `EOF`. `EOF` is true each time the output contains the last audio sample and/or video frame in the file.

`[Y,CB,CR] = step(H)` outputs one frame of YCbCr 4:2:2 video data in the color components `Y`, `CB`, and `CR`. This behavior applies when you set the `VideoOutputPort` property to true, the `ImageColorSpace` property to YCbCr 4:2:2, and an input file which contains video data.

## signalblks.MultimediaFileReader.step

---

[Y,CB,CR,AUDIO] = step(H) outputs one frame of YCbCr 4:2:2 video data in the color components Y, CB, and CR, and one frame of audio samples in AUDIO. This applies when you set the AudioOutputPort and VideoOutputPort properties to true, the ImageColorSpace property to YCbCr 4:2:2, and an input file which contains audio and video data.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

**Purpose** Write video frames, audio samples, or both to multimedia file

---

**Note** MultimediaFileWriter will be removed in a future release. Use AudioFileWriter instead. See dsp.AudioFileWriter.

---

**Description** The MultimediaFileWriter object writes video frames, audio samples, or both to a multimedia file.

To write video frames, audio samples, or both to a multimedia file:

- 1** Define and set up your multimedia file writer. See “Construction” on page 5-801.
- 2** Call step to write to a multimedia file according to the properties of signalblks.MultimediaFileWriter. The behavior of step is specific to each object in the toolbox.

**Construction** H = signalblks.MultimediaFileWriter returns a multimedia file writer System object, H, that writes video frames, audio samples, or both to a multimedia file (such as an AVI file).

H =  
signalblks.MultimediaFileWriter('PropertyName',PropertyValue,...)  
returns a multimedia file writer System object, H, with each specified property set to the specified value.

H =  
signalblks.MultimediaFileWriter(FILENAME,'PropertyName',PropertyValue...)  
returns a multimedia file writer System object, H, with Filename property set to FILENAME and other specified properties set to the specified values.

**Properties** **Filename**

Name of multimedia file to which to write

Specify the name of the multimedia file as a string. The default is `output.avi`.

## **FileFormat**

Multimedia file format

Specify which multimedia file format the object writes. On Microsoft platforms, select AVI, WAV, WMV, or WMA. These abbreviations correspond to the following file formats:

- WAV: Microsoft WAVE Files
- WMV: Windows Media Video
- WMA: Windows Media Audio
- AVI: Audio-Video Interleave

The default setting for this property is AVI.

On all other platforms, the only selection is AVI.

## **AudioInputPort**

Choose to write audio data

Use this property to specify whether the multimedia file writer object writes audio samples to a multimedia file. When you enable both this property and `VideoInputPort`, ensure that the video and audio input signals have the same frame period. Adjust the frame size (or number of rows) of the audio signal so that the frame period of the video signal is the same as the frame period of the audio signal. Calculate frame size by dividing the audio signal frequency by the frame rate of the video signal. The audio signal frequency is in samples per second (specified by `SampleRate`). The video signal frame rate is in frames per second (specified by `FrameRate`). The default selection for this property is `true`.

The multimedia file object takes a column vector as an input. Every column is a separate channel and each row corresponds to a single audio sample.

## **VideoInputPort**

Choose to write video data

Use this property to specify whether the multimedia file writer object writes video frames to a multimedia file. When you enable both this property and the `AudioInputPort` property, ensure that the video and audio input signals have the same frame period. Adjust frame size (or number of rows) for the audio signal so the frame period is equal of both the video signal and the audio signal. Calculate frame size by dividing the audio signal frequency by the frame rate of the video signal. The audio signal frequency is in samples per second (specified by `SampleRate`). The video signal frame rate is in frames per second (specified by `FrameRate`). The default selection for this property is `false`

## **AudioCompressor**

Algorithm that compresses audio data

Specify the type of compression algorithm the multimedia file writer uses to compress the audio data. Compression reduces the size of the multimedia file. Select `None` (uncompressed) to save uncompressed audio data to a multimedia file. The other options available reflect the audio compression algorithms installed on your system. This property is only available when writing WAV or AVI files on Windows platforms.

## **VideoCompressor**

Algorithm that compresses video data

Specify the type of compression algorithm to multimedia file writer uses to compress the video data. This compression reduces the size of the multimedia file. Choose `None` (uncompressed) to save uncompressed video data to a multimedia file. The other options reflect the available video compression algorithms installed on your system. This property is only available when writing AVI files on Windows platforms.

## **SampleRate**

# signalblks.MultimediaFileWriter

---

Sampling rate of audio data stream

Specify the sampling rate of the input audio data as a positive numeric scalar. The default is 44100. This property only applies when you set the `AudioInputPort` property to `true`.

## **FrameRate**

Frame rate of video data stream

Specify the frame rate of the video data in frames per second as a positive numeric scalar. The default is 30. This property only applies when you set the `VideoInputPort` property to `true`.

## **AudioDataType**

Data type of the uncompressed audio

Specify the type of uncompressed audio data written to the file. This property only applies when writing uncompressed WAV files.

## **FileColorSpace**

Color space to use when creating a file

Specify the color space of AVI files as `RGB` or `YCbCr 4:2:2`. This property only applies on Windows platforms when you set the `FileFormat` property to `AVI`. The default is `RGB`.

## **Methods**

<code>clone</code>	Create multimedia file writer object with the same property values
<code>close</code>	Release resources
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method

isLocked	Locked status for input attributes and nontunable properties
step	Write one frame of audio output samples

## Examples

Decimate an audio signal, and write signal to disk as an AVI file:

```
hmfr = signalblks.MultimediaFileReader...
    ('AudioOutputDataType','double');
hfirdec = dsp.FIRDecimator; % decimate by 2
hmfw = signalblks.MultimediaFileWriter...
    ('speech_dft_11025.avi', ...
    'SampleRate', 22050/2);

while ~isDone(hmfr)
    audio = step(hmfr);
    audiod = step(hfirdec, audio);
    step(hmfw, audiod);
end

close(hmfr);
close(hmfw);
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the To Multimedia File block reference page. The object properties correspond to the block parameters, except:

- The **Write** block parameter corresponds to both the AudioOutputPort and the VideoOutputPort object properties.
- The FrameRate and SampleRate properties are not available on the block. The block inherits these signals from the input line connected to the ports.

# signalblks.MultimediaFileWriter

---

## See Also

`signalblks.MultimediaFileReader`

**Purpose** Create multimedia file writer object with the same property values

---

**Note** MultimediaFileWriter will be removed in a future release. Use AudioFileWriter instead. See dsp.AudioFileWriter.clone.

---

**Syntax** C = clone(H)

**Description** C = clone(H) creates a MultimediaFileWriter System object C, with the same property values as H. The clone method creates a new unlocked object.

# signalblks.MultimediaFileWriter.close

---

**Purpose** Release resources

---

**Note** MultimediaFileWriter will be removed in a future release. Use AudioFileWriter instead. See dsp.AudioFileWriter.release.

---

**Syntax** close(H)

**Description** close(H) releases system resources (such as memory, file handles or hardware connections).

# signalblks.MultimediaFileWriter.getNumInputs

---

**Purpose** Number of expected inputs to step method

---

**Note** MultimediaFileWriter will be removed in a future release. Use AudioFileWriter instead. See dsp.AudioFileWriter.getNumInputs.

---

**Syntax** N = getNumInputs(H)

**Description** N = getNumInputs(H) returns the number of expected inputs, N, of the step method

The getNumInputs method returns a positive integer that is the number of expected inputs (not counting the object itself) to the step method. This value will change if you alter any properties that turn inputs on or off. You must call the step method with the number of input arguments equal to the result of getNumInputs(H).

# signalblks.MultimediaFileWriter.getNumOutputs

---

**Purpose** Number of outputs of step method

---

**Note** MultimediaFileWriter will be removed in a future release. Use AudioFileWriter instead. See dsp.AudioFileWriter.getNumOutputs.

---

**Syntax** N = getNumOutputs(H)

**Description** N = getNumOutputs(H) returns the number of outputs, N, of the step method.

The getNumOutputs method returns a positive integer that is the number of outputs from the step method. This value will change if you alter any properties that turn outputs on or off.

# signalblks.MultimediaFileWriter.isLocked

---

**Purpose** Locked status for input attributes and nontunable properties

---

**Note** MultimediaFileWriter will be removed in a future release. Use AudioFileWriter instead. See dsp.AudioFileWriter.isLocked.

---

**Syntax** isLocked(H)

**Description** isLocked(H) returns the locked state of the MultimediaFileWriter System object H.

The isLocked method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the step method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the isLocked method returns a true value.

# signalblks.MultimediaFileWriter.step

---

## Purpose

Write one frame of audio output samples

---

**Note** `MultimediaFileWriter` will be removed in a future release. Use `AudioFileWriter` instead. See `dsp.AudioFileWriter.step`.

---

## Syntax

```
step(H,AUDIO)
step(H,I)
step(H,I,AUDIO)
step(H,Y,Cb,Cr)
step(H,Y,CB,CR)
step(H,Y,CB,CR,AUDIO)
```

## Description

`step(H,AUDIO)` writes one frame of audio samples, `AUDIO`, to the output file when you enable the `AudioInputPort` property. `AUDIO` is either a vector or an  $M$ -by-2 matrix for mono or stereo inputs, respectively.

`step(H,I)` writes one frame of video, `I`, to the output file when you enable the `VideoInputPort` property. `I` is an  $M$ -by- $N$ -by-3 color video signal.

`step(H,I,AUDIO)` writes one frame of video, `I`, and one frame of audio samples, `AUDIO`, to the output file when you enable both the `AudioInputPort` and `VideoInputPort` properties.

`step(H,Y,Cb,Cr)` writes one frame of video with `Y`, `Cb`, `Cr` components to the file. This applies only when you set the `FileColorSpace` property to `YCbCr 4:2:2`

`step(H,Y,CB,CR)` writes one frame of `YCbCr 4:2:2` data in the color components `Y`, `CB`, and `CR`, to the output file when you set the `VideoInputPort` property to `true`. The width of `CB` and `CR` must be half of the width of `Y`, and the value of the `FileColorSpace` property must be set to `YCbCr 4:2:2`.

`step(H,Y,CB,CR,AUDIO)` writes one frame of `YCbCr 4:2:2` data in the color components `Y`, `CB`, and `CR`, and one frame of audio samples, `AUDIO`, to the output file when you set both the `AudioInputPort` and

VideoInputPort properties to true. The width of CB and CR must be half of the width of Y, and the value of the FileColorSpace property must be set to YCbCr 4:2:2.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

**Purpose** Generate real or complex sinusoidal signals

**Description** The numerically controlled oscillator, or NCO, object generates real or complex sinusoidal signals. The amplitude of the generated signal is always 1.

To generate real or complex sinusoidal signals:

- 1 Define and set up your NCO System object. See “Construction” on page 5-814.
- 2 Call `step` to generate the signals according to the properties of `dsp.NCO`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.NCO` returns an NCO System object, `H`, that generates a multichannel real or complex sinusoidal signal, with independent frequency and phase in each output channel.

`H = dsp.NCO('PropertyName',PropertyVaLue,...)` returns an NCO System object, `H`, with each specified property set to the specified value.

## Properties

### PhaseIncrementSource

Source of phase increment

Indicate how to specify the phase increment: `Property` or `Input port`. The default is `Input port`.

### PhaseIncrement

Phase increment

Specify the phase increment as an integer scalar. This property applies only when you set the `PhaseIncrementSource` property to `Property`. The default is 100.

### PhaseOffsetSource

Source of phase offset

Specify the phase offset as Property or Input port. The default is Property.

**PhaseOffset**

Phase offset

Specify the phase offset as an integer scalar. This property applies only when you set the PhaseOffsetSource property to Property. The default is 0.

**Dither**

Enable adding internal dithering to NCO algorithm

Set this property to true to add internal dithering to the NCO algorithm. Dithering is added using the PN Sequence Generator from the Communications System Toolbox product. The default is true.

**NumDitherBits**

Number of dither bits

Specify the number of dither bits as a positive integer. This property applies only when you set the Dither property to true. The default is 4.

**PhaseQuantization**

Enable quantization of accumulated phase

Set this property to true to enable quantization of the accumulated phase. The default is true.

**NumQuantizerAccumulatorBits**

Number of quantizer accumulator bits

Specify the number of quantizer accumulator bits as an integer scalar greater than 1 and less than the accumulator word length. This property determines the number of entries in the lookup table of sine values. This property applies only when you set the PhaseQuantization property to true. The default is 12.

## **PhaseQuantizationErrorOutputPort**

Enable output of phase quantization error

Set this property to `true` to output the phase quantization error. This property applies only when you set the `PhaseQuantization` property to `true`. The default is `false`.

## **Waveform**

Type of output signal

Specify the type of the output signal: `Sine`, `Cosine`, `Complex exponential` or `Sine and cosine`. The default is `Sine`.

## **SamplesPerFrame**

Number of output samples per frame

Specify the number of samples per frame of the output signal. This property applies only when you set the `PhaseOffsetSource` property to `Property`. The default is `1`. When the `PhaseOffsetSource` property is `Input port`, and the `PhaseIncrementSource` property is `Property`, the number of rows or frame size of the phase offset input determines the number of samples per frame of the output signal. When you set both the `PhaseOffsetSource` and `PhaseIncrementSource` properties to `Input port`, the number of rows in the inputs must be `1`, and the samples per frame of the output signal is `1`.

## **OutputDataType**

Output data type

Specify the output data type as one of `double`, `single` or `Custom`. The default is `Custom`.

## **Fixed-Point Properties**

### **RoundingMethod**

Rounding method for fixed-point operations

This constant property has a value `Floor`.

### **OverflowAction**

Overflow action for fixed-point operations

This constant property has a value `Wrap`.

### **AccumulatorDataType**

Accumulator word and fraction lengths

This constant property has a value `Custom`.

### **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as an unscaled `numericType` object with a `Signedness` of `Auto`. The default is `numericType([],16)`.

### **CustomOutputDataType**

Output word and fraction lengths

Specify the output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `OutputDataType` property to `Custom`. The default is `numericType([],16,14)`.

## **Methods**

<code>clone</code>	Create NCO object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>info</code>	Characteristic information about generated signal

isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
reset	Reset accumulator of NCO object
step	Sinusoidal signal with specified phase increment

## Examples

Design an NCO source according to given specifications:

```
F0 = 510; % Output frequency = 510 Hz
df = 0.05; % Frequency resolution = 0.05 Hz
minSFDR = 96; % Spurious free dynamic range >= 96 dB
Ts = 1/8000; % Sample period = 1/8000 sec
dphi = pi/2; % Desired phase offset = pi/2;
```

Calculate number of accumulator bits required for the given frequency resolution

```
Nacc = ceil(log2(1/(df*Ts)));
% Actual frequency resolution achieved
actdf = 1/(Ts*2^Nacc);
% Calculate number of quantized accumulator bits
% required from the SFDR requirement
Nqacc = ceil((minSFDR-12)/6);
% Calculate the phase increment
phIncr = round(F0*Ts*2^Nacc);
% Calculate the phase offset
phOffset = 2^Nacc*dphi/(2*pi);

hnco = dsp.NCO('PhaseIncrementSource', 'Property', ...
'PhaseIncrement', phIncr,...
'PhaseOffset', phOffset,...
'NumDitherBits', 4, ...
'NumQuantizerAccumulatorBits', Nqacc,...
```

```
'SamplesPerFrame', 1/Ts, ...  
'CustomAccumulatorDataType', numerictype([],Nacc));  
  
y = step(hnco);  
% Plot the mean-square spectrum of the 510 Hz sinewave  
% generated by the NCO  
sperd = spectrum.periodogram('hann'); ...  
sperd.SamplingFlag = 'periodic';  
msspectrum(sperd,double(y),'Fs',1/Ts);
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the NCO block reference page. The object properties correspond to the block properties, except:

There is no object property that corresponds to the **Sample time** block parameter. The objects assumes a sample time of one second.

## See Also

dsp.SineWave

# dsp.NCO.clone

---

**Purpose** Create NCO object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates an NCO system object `C`, with the same property values as `H`. The clone method creates a new unlocked object with uninitialized states

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.NCO.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Characteristic information about generated signal

**Syntax** `S = info(H)`

**Description** `S = info(H)` returns a structure containing characteristic information, `S`, about the signal being generated by the NCO System object, `H`. The number of fields of `S`, and their values vary depending on the property value settings of `H`. For description of the possible fields and their values, see the following table.

Field	Value
NumPointsLUT	Number of data points for lookup table. The lookup table is implemented as a quarter-wave sine table.
SineLUTSize	Quarter-wave sine lookup table size in bytes.
TheoreticalSFDR	Theoretical spurious free dynamic range (SFDR) in dBc. This field applies when you set the <code>PhaseQuantization</code> property to <code>true</code> .
FrequencyResolution	Frequency resolution of the NCO in Hz. The sample time of the output signal is assumed to be 1 sec.

# dsp.NCO.isLocked

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** isLocked(H)

**Description** isLocked(H) returns the locked state of the NCO System object.

The isLocked method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the step method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the isLocked method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

## **dsp.NCO.reset**

---

**Purpose**            Reset accumulator of NCO object

**Syntax**            reset(H)

**Description**        reset(H) resets the accumulator of the NCO System object, H, to zero.

<b>Purpose</b>	Sinusoidal signal with specified phase increment
<b>Syntax</b>	<pre>Y = step(H, INC) Y = step(H) Y = step(H, OFFSET) Y = step(H, INC, OFFSET) [Y, QERR] = step(H, ...)</pre>
<b>Description</b>	<p><code>Y = step(H, INC)</code> returns a sinusoidal signal, <code>Y</code>, generated by the NCO with the specified phase increment, <code>INC</code>. <code>INC</code> must be a built-in integer or a <code>fi</code> object comprising either a scalar or a row vector, where each row element corresponds to a separate channel.</p> <p><code>Y = step(H)</code> when the <code>PhaseIncrementSource</code> and <code>PhaseOffsetSource</code> properties are both <code>Property</code>, returns a sinusoidal signal, <code>Y</code>.</p> <p><code>Y = step(H, OFFSET)</code> returns a sinusoidal signal, <code>Y</code>, with phase offset, <code>OFFSET</code>, when the <code>PhaseOffsetSource</code> property is <code>Input port</code>. <code>OFFSET</code> must be a built-in integer or a <code>fi</code> object. The number of rows of <code>OFFSET</code> determines the number of samples per frame of the output signal. The number of columns of the <code>OFFSET</code> determines the number of channels of the output signal.</p> <p><code>Y = step(H, INC, OFFSET)</code> returns a sinusoidal signal, <code>Y</code>, with phase increment, <code>INC</code>, and phase offset, <code>OFFSET</code>, when the <code>PhaseIncrementSource</code> and the <code>PhaseOffsetSource</code> properties are both <code>Input port</code>. <code>INC</code> and <code>OFFSET</code> must both be row vectors of the same length, where the length determines the number of channels in the output signal.</p> <p><code>[Y, QERR] = step(H, ...)</code> when the <code>PhaseQuantization</code> and the <code>PhaseQuantizationErrorOutputPort</code> properties are both <code>true</code>, returns a sinusoidal signal, <code>Y</code>, and output quantization error, <code>QERR</code>.</p>

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

<b>Purpose</b>	Vector normalization along specified dimension
<b>Description</b>	<p>The Normalizer object performs vector normalization along rows, columns, or specified dimension.</p> <p>To perform vector normalization:</p> <ol style="list-style-type: none"><li>1 Define and set up your normalization object. See “Construction” on page 5-829.</li><li>2 Call <code>step</code> to perform vector normalization according to the properties of <code>dsp.Normalizer</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.Normalizer</code> returns a normalization object, <code>H</code>, that normalizes the input over each column by the squared 2-norm of the column plus a bias term of <math>1e-10</math> used to protect against divide-by-zero.</p> <p><code>H = dsp.Normalizer('PropertyName',PropertyValue, ...)</code> returns a normalization object, <code>H</code>, with each property set to the specified value.</p>
<b>Properties</b>	<p><b>Method</b></p> <p>Type of normalization to perform</p> <p>Specify the type of normalization to perform as 2-norm or Squared 2-norm. The 2-norm mode supports floating-point signals only. The Squared 2-norm supports both fixed-point and floating-point signals. The default is Squared 2-norm.</p> <p><b>Bias</b></p> <p>Real number added in denominator to avoid division by zero</p> <p>Specify the real number to add in the denominator to avoid division by zero. The default is <math>1e-10</math>. This property is tunable.</p> <p><b>Dimension</b></p> <p>Dimension to operate along</p>

Specify whether to normalize along `Column`, `Row`, or `Custom`. The default is `Column`.

## **CustomDimension**

Numerical dimension to operate along

Specify the one-based value of the dimension over which to normalize. The value of this parameter cannot exceed the number of dimensions in the input signal. This property applies when `Dimension` property is `Custom`. The default is 1.

## **Fixed-Point Properties**

### **RoundingMethod**

Rounding method for fixed-point operations

Specify the rounding method as one of `Ceiling`, `Convergent`, `Floor`, `Nearest`, `Round`, `Simplest`, or `Zero`. The default is `Floor`.

### **OverflowAction**

Overflow action for fixed-point operations

Specify the overflow action as one of `Wrap` or `Saturate`. The default is `Wrap`.

### **ProductDataType**

Product word and fraction lengths

Specify the product fixed-point data type as one of `Same as input` or `Custom`.

### **CustomProductDataType**

Product word and fraction lengths

Specify the product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `ProductDataType` property to `Custom`. The default to `numericType([],32,32)`.

## **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point data type as one of Same as product, Same as input, Custom. The default is Same as product.

## **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `AccumulatorDataType` property to `Custom`. The default is `numericType([],32,30)`.

## **OutputDataType**

Output word and fraction lengths

Specify the output fixed-point data type as one of Same as accumulator, Same as product, Same as input, Custom. The default is Same as product.

## **CustomOutputDataType**

Output word and fraction lengths

Specify the output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `OutputDataType` property to `Custom`. The default is `numericType([],32,32)`.

## **Methods**

<code>clone</code>	Create normalization object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method

# dsp.Normalizer

---

isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
step	Normalize input along specified dimension

## Examples

Normalize a matrix:

```
hnorm = dsp.Normalizer;  
x = magic(3);  
y = step(hnorm, x);
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Normalization block reference page. The object properties correspond to the block parameters, except:

- **Treat sample-based row input as column** — The block allows you to input a row vector and normalize the row vector as a column vector. The normalization object always normalizes along the value of the `Dimension` property.
- The normalization object does not support the **Minimum** and **Maximum** options for data output.

## See Also

`dsp.ArrayVectorMultiplier`

**Purpose** Create normalization object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a normalizer object, `C`, with the same property values. The clone method creates a new unlocked object.

# dsp.Normalizer.getNumInputs

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose**

Number of outputs of step method

**Syntax**

`N = getNumOutputs(H)`

**Description**

`N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# dsp.Normalizer.isLocked

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the normalization object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

# dsp.Normalizer.step

---

**Purpose** Normalize input along specified dimension

**Syntax**  $Y = \text{step}(H,X)$

**Description**  $Y = \text{step}(H,X)$  returns a normalized output  $Y$ . The input  $X$  must be floating-point for the 2-norm mode, and either fixed-point and floating-point for the Squared 2-norm mode.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

<b>Purpose</b>	Determine extrema (maxima or minima) in input signal
<b>Description</b>	<p>The PeakFinder object determines the extrema (maxima or minima) in the input signal.</p> <p>To compute the extrema in the input signal:</p> <ol style="list-style-type: none"><li>1 Define and set up your peak finder. See “Construction” on page 5-839.</li><li>2 Call <code>step</code> to compute the extrema according to the properties of <code>dsp.PeakFinder</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.PeakFinder</code> returns a peak finder System object, <code>H</code>, that compares the current signal value to the previous and next values to determine if the current value is an extremum.</p> <p><code>H = dsp.PeakFinder('PropertyName',PropertyValue,...)</code> returns a peak finder System object, <code>H</code>, with each specified property set to the specified value.</p>
<b>Properties</b>	<p><b>PeakType</b></p> <p>Looking for maxima, minima, or both</p> <p>Specify whether the object is looking for maxima, minima, or both. You can set this property to <code>oMaxima</code>, <code>Minima</code>, <code>Maxima</code> and <code>Minima</code>. The default is <code>Maxima</code> and <code>Minima</code>.</p> <p><b>PeakIndicesOutputPort</b></p> <p>Enable output of extrema indices</p> <p>Set this property to <code>true</code> to output the extrema indices. The default is <code>false</code>.</p> <p><b>PeakValuesOutputPort</b></p> <p>Enable output of extrema values</p> <p>Set this property to <code>true</code> to output the extrema values. The default is <code>false</code>.</p>

## **MaximumPeakCount**

Number of extrema to look for in each input signal

The object stops searching the input signal for extrema after the maximum number of extrema has been found. The value of this property must be an integer greater than or equal to one. The default is 10.

## **IgnoreSmallPeaks**

Enable ignoring peaks below threshold

Set this property to `true` if you want to eliminate the detection of peaks whose amplitudes are within a specified threshold of neighboring values. The default is `false`.

## **PeakThreshold**

Threshold below which peaks are ignored

Specify the noise threshold value. This property defines the current input value as a maximum if:

- The current input value minus the previous input value is greater than the threshold, and
- The current input value minus next input value is greater than the threshold.

This property applies when you set the `IgnoreSmallPeaks` property to `true`. The default is 0.

## **Fixed-Point Properties**

### **RoundingMethod**

Rounding method for fixed-point operations

The rounding method is a constant property set to `Floor`.

### **OverflowAction**

Overflow action for fixed-point operations

Specify the overflow action as Wrap or Saturate. The default is Wrap.

## Methods

clone	Create peak finder object with same property values
getNumInputs	Number of expected inputs to the step method
getNumOutputs	Number of outputs of step method
isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
step	Number of extrema in input signal

## Examples

Determine whether each value of an input signal is local maximum or minimum:

```
hpeaks1 = dsp.PeakFinder;
hpeaks1.PeakIndicesOutputPort = true;
hpeaks1.PeakValuesOutputPort = true;

x1 = [9 6 10 3 4 5 0 12]';
% Find the peaks of each input
% [prev;cur;next]: {[9;6;10],[6;10;3],...}
[cnt1, idx1, val1, pol1] = step(hpeaks1, x1);
```

---

Determine peak values for a fixed-point input signal:

```
hpeaks2 = dsp.PeakFinder('PeakType', 'Maxima', ...
```

# dsp.PeakFinder

---

```
'PeakValuesOutputPort', true, ...  
'MaximumPeakCount', 2, ...  
'IgnoreSmallPeaks', true, ...  
'PeakThreshold', 0.25, ...  
'OverflowAction', 'Saturate');  
x2 = fi([-1;0.5;0],true,16,15);  
[cnt2, val2] = step(hpeaks2, x2);
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Peak Finder block reference page. The object properties correspond to the block parameters.

## See Also

[dsp.Maximum](#) | [dsp.Minimum](#)

**Purpose** Create peak finder object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a PeakFinder System object `C`, with the same property values as `H`. The clone method creates a new unlocked object with uninitialized states.

# **dsp.PeakFinder.getNumInputs**

---

**Purpose**            Number of expected inputs to the step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# **dsp.PeakFinder.isLocked**

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `PeakFinder System` object. The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

# dsp.PeakFinder.step

---

**Purpose** Number of extrema in input signal

**Syntax**

```
YCNT = step(H,X)
[ YCNT,IDX ] = step(H,X)
[ ... , VAL ] = step(H,X)
[ ... , POL ] = step(H,X)
```

**Description** YCNT = step(H,X) returns the number of extrema (minima, maxima, or both) YCNT in input signal X.

[ YCNT,IDX ] = step(H,X) when the `PeakIndicesOutputPort` property is true, returns the number of extrema YCNT and peak indices IDX in input signal X.

[ ... , VAL ] = step(H,X) also returns the peak values VAL in input signal X when the `PeakValuesOutputPort` property is true.

[ ... , POL ] = step(H,X) also returns the extrema polarity POL in input signal X when the `PeakType` property is `Maxima` and `Minima` and the `PeakIndicesOutputPort` property is true. The polarity is 1 for maxima and 0 for minima.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

<b>Purpose</b>	Peak-to-peak value
<b>Description</b>	<p>The PeakToPeak object computes the peak-to-peak value of an input. To obtain the peak-to-peak value:</p> <ol style="list-style-type: none"><li>1 Define and set up your peak-to-peak calculation. See “Construction” on page 5-849.</li><li>2 Call <code>step</code> to compute the peak-to-peak value for an input vector according to the properties of <code>dsp.PeakToPeak</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.PeakToPeak</code> creates a peak-to-peak System object, <code>H</code>, that computes the difference between the maximum and minimum value in an input or a sequence of inputs.</p> <p><code>H = dsp.PeakToPeak('PropertyName',PropertyValue,...)</code> returns an <code>PeakToPeak</code> System object, <code>H</code>, with each specified property set to the specified value.</p>
<b>Properties</b>	<p><b>CustomDimension</b></p> <p>Dimension to operate along. Specify the dimension as a positive integer along which the peak-to-peak difference is computed. The value of this property cannot exceed the number of dimensions in the input signal. This property applies when the <code>Dimension</code> property is <code>'Custom'</code>.</p> <p><b>Default:</b> 1</p> <p><b>Dimension</b></p> <p>Dimension to operate along. Specify the dimension along which to calculate the peak-to-peak ratio as one of <code>'All'</code>, <code>'Row'</code>, <code>'Column'</code>, or <code>'Custom'</code>. This property applies when the <code>RunningPeakToPeak</code> property is <code>false</code>. If you set this property to <code>'Custom'</code>, specify the dimension using the <code>CustomDimension</code> property.</p>

**Default:** 'Column'

## **FrameBasedProcessing**

Process input in frames or as samples. Set this property to `true` to enable frame-based processing. Set this property to `false` to enable sample-based processing. This property applies when the `RunningPeakToPeak` property is `true`.

**Default:** `true`

## **ResetCondition**

Reset condition for running peak-to-peak mode. Specify the event to reset the running peak-to-peak as one of 'Rising edge', 'Falling edge', 'Either edge', or 'Non-zero'. This property applies when the `ResetInputPort` property is `true`.

## **ResetInputPort**

Enables resetting in running peak-to-peak mode. Set this property to `true` to enable resetting the running peak-to-peak. When the property is set to `true`, a reset input must be specified to the call of `step` to reset the running peak-to-peak difference. This property applies when the `RunningPeakToPeak` property is `true`.

**Default:** `false`

## **RunningPeakToPeak**

Calculation over successive calls to `step`. Set this property to `true` to enable the calculation of the peak-to-peak difference over successive calls to the `step`.

**Default:** `false`

## Methods

clone	Clones the current instance of the peak-to-peak object
getNumInputs	Number of expected inputs to the method
getNumOutputs	Number of outputs of the method
isLocked	Locked status (logical) for input attributes and nontunable properties
release	Allow property value and input characteristics changes
reset	Reset the running peak-to-peak object
step	Compute peak-to-peak value

## Examples

### Peak-to-Peak Value of Vector

Determine the peak-to-peak value for a vector input.

```
in1 = (1:10)';  
h1 = dsp.PeakToPeak;  
y1 = step(h1, in1);
```

### Peak-to-Peak Value of Matrix Input

Determine the peak-to-peak value of a matrix input.

```
in2 = magic(4);  
h2 = dsp.PeakToPeak;  
h2.Dimension = 'All';  
y2 = step(h2, in2)
```

## References

[1] *IEEE® Standard on Transitions, Pulses, and Related Waveforms*, IEEE Standard 181, 2003.

# dsp.PeakToPeak

---

## See Also

[dsp.Maximum](#) | [dsp.PeakToRMS](#) |

<b>Purpose</b>	Clones the current instance of the peak-to-peak object
<b>Syntax</b>	<code>clone(H)</code>
<b>Description</b>	<code>clone(H)</code> clones the current instance of the peak-to-peak object, H.

# dsp.PeakToPeak.getNumInputs

---

**Purpose**            Number of expected inputs to the `step` method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the `step` method for the peak-to-peak object `H`.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose**            Number of outputs of the `step` method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method for the peak-to-peak object, `H`.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# **dsp.PeakToPeak.isLocked**

---

**Purpose** Locked status (logical) for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the peak-to-peak object H.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

# **dsp.PeakToPeak.reset**

---

**Purpose**            Reset the running peak-to-peak object

**Syntax**            reset(H)

**Description**        reset(H) resets the running peak-to-peak value for the object H.

**Purpose** Compute peak-to-peak value

**Syntax**  
`Y = step(H,X)`  
`Y = step(H,X,R)`

**Description** `Y = step(H,X)` computes the peak-to-peak value, `Y`, of the floating-point input vector `X`. When the `RunningPeakToPeak` property is `true`, `Y` corresponds to the peak-to-peak value of the input elements over successive calls to the `step` method.

`Y = step(H,X,R)` computes the peak-to-peak value of the input elements over successive calls to the `step` method. The object optionally resets its state based on the reset input signal, `R`, and the value of the `ResetCondition` property. This is possible when you set both the `RunningPeakToPeak` and the `ResetInputPort` properties to `true`.

# dsp.PeakToRMS

---

**Purpose** Peak-to-root-mean-square value of vector

**Description** The PeakToRMS object calculates the peak-to-root-mean-square ratio of a vector.

To compute the peak-to-root-mean-square ratio:

- 1 Define and set up your peak-to-root-mean-square calculation. See “Construction” on page 5-860.
- 2 Call `step` to calculate the peak-to-root-mean-square value for an input vector according to the properties of `dsp.PeakToRMS`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.PeakToRMS` creates a peak-to-root-mean-square System object, `H`, that returns the ratio of the maximum magnitude (peak) to the root-mean-square (RMS) value in an input or a sequence of inputs.

`H = dsp.PeakToRMS('PropertyName',PropertyValue,...)` returns an `PeakToRMS` System object, `H`, with each specified property set to the specified value.

## Properties

### CustomDimension

Numerical dimension to operate along. Specify the dimension as a positive integer along which the peak-to-RMS ratio is computed. The value of this property cannot exceed the number of dimensions in the input signal. This property applies when `Dimension` property is 'Custom'.

**Default:** 1

### DecibelScaledOutput

Report output in decibels (dB). Set this property to `true` to enable output in dB. Set this property to `false` to report output as a ratio.

**Default:** `true`

## **Dimension**

Dimension to operate along. Specify the dimension along which to calculate the peak-to-RMS ratio as one of 'All', 'Row', 'Column', or 'Custom'. This property applies when the `RunningPeakToRMS` property is false. If you set this property to 'Custom', specify the dimension using the `CustomDimension` property.

**Default:** 'Column'

## **FrameBasedProcessing**

Process input in frames or as samples. Set this property to true to enable frame-based processing. Set this property to false to enable sample-based processing. This property applies when the `RunningPeakToRMS` property is true.

**Default:** true

## **ResetCondition**

Reset condition for running peak-to-RMS mode. Specify the event to reset the running peak-to-RMS as one of 'Rising edge', 'Falling edge', 'Either edge', or 'Non-zero'. This property applies when the `ResetInputPort` property is true.

## **ResetInputPort**

Enables resetting in running peak-to-RMS mode. Set this property to true to enable resetting. When the property is set to true, a reset input must be specified in the call to `step` to reset the running peak-to-RMS ratio. This property applies when the `RunningPeakToRMS` property is true.

**Default:** false

## **RunningPeakToRMS**

# dsp.PeakToRMS

---

Calculation over successive calls to `step`. Set this property to `true` to enable the calculation of the peak-to-RMS ratio over successive calls to the `step`.

**Default:** `false`

## Methods

<code>clone</code>	Clones the current instance of the peak-to-root-mean-square object
<code>getNumInputs</code>	Number of expected inputs to the method
<code>getNumOutputs</code>	Number of outputs of the method
<code>isLocked</code>	Locked status (logical) for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>reset</code>	Reset the running peak-to-root-mean-square object
<code>step</code>	Compute peak-to-RMS ratio

## Definitions

### Peak-magnitude-to-RMS Level

The peak-magnitude-to-RMS level is

$$\frac{\|X\|_{\infty}}{\sqrt{\frac{1}{N} \sum_{n=1}^N |X_n|^2}}$$

where the  $l$ -infinity norm and RMS values are computed along the specified dimension.

## Examples

### Peak-to-RMS Ratio of Vector Input

Determine the peak-to-RMS ratio of a vector input.

```
in1 = (1:10)';  
h1 = dsp.PeakToRMS;  
y1 = step(h1,in1);
```

### Peak-to-RMS Ratio of Matrix Input

Determine the peak-to-RMS ratio of a matrix input.

```
in2 = magic(4);  
h2 = dsp.PeakToRMS;  
h2.Dimension = 'All';  
y2 = step(h2, in2)
```

## References

[1] *IEEE Standard on Transitions, Pulses, and Related Waveforms*, IEEE Standard 181, 2003.

## See Also

[dsp.Maximum](#) | [dsp.PeakToPeak](#) |

# **dsp.PeakToRMS.clone**

---

**Purpose** Clones the current instance of the peak-to-root-mean-square object

**Syntax** `clone(H)`

**Description** `clone(H)` clones the current instance of the peak-to-root-mean-square (RMS) object H.

**Purpose** Number of expected inputs to the step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the step method for the peak-to-root-mean-square object `H`.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.PeakToRMS.getNumOutputs**

---

**Purpose**            Number of outputs of the `step` method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

<b>Purpose</b>	Locked status (logical) for input attributes and nontunable properties
<b>Syntax</b>	isLocked(H)
<b>Description</b>	isLocked(H) returns the locked state of the peak-to-root-mean-square object H.

# dsp.PeakToRMS.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose**            Reset the running peak-to-root-mean-square object

**Syntax**            `reset(H)`

**Description**        `reset(H)` resets the running peak-to-root-mean-square value for the object H.

# dsp.PeakToRMS.step

---

**Purpose** Compute peak-to-RMS ratio

**Syntax**  $Y = \text{step}(H,X)$   
 $Y = \text{step}(H,X,R)$

**Description**  $Y = \text{step}(H,X)$  computes the peak-to-RMS ratio,  $Y$ , of the floating-point input vector  $X$ . When the `RunningPeakToRMS` property is `true`,  $Y$  corresponds to the peak-to-RMS ratio of the input elements over successive calls to the `step` method.

$Y = \text{step}(H,X,R)$  computes the peak-to-RMS ratio of the input elements over successive calls to the `step` method. The object optionally resets its state based on the reset input signal,  $R$ , and the value of the `ResetCondition` property. This is possible when you set both the `RunningPeakToRMS` and the `ResetInputPort` properties to `true`.

<b>Purpose</b>	Unwrap signal phase
<b>Description</b>	<p>The PhaseUnwrapper object unwraps the signal phase input specified in radians.</p> <p>To unwrap the signal phase input:</p> <ol style="list-style-type: none"><li>1 Define and set up your System object. See “Construction” on page 5-871.</li><li>2 Call <code>step</code> to unwrap the signal phase according to the properties of <code>dsp.PhaseUnwrapper</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.PhaseUnwrapper</code> returns a System object, <code>H</code>. This System object adds or subtracts appropriate multiples of <math>2\pi</math> to each input element to remove phase discontinuities (unwrap).</p> <p><code>H = dsp.PhaseUnwrapper('PropertyName',PropertyValue,...)</code> returns an unwrapped System object, <code>H</code>, with each specified property set to the specified value.</p>
<b>Properties</b>	<p><b>InterFrameUnwrap</b></p> <p>Enable unwrapping of phase discontinuities between successive frames</p> <p>Set this property to <code>false</code> to unwrap phase discontinuities only within the frame. Set this property to <code>true</code> to also unwrap phase discontinuities between successive frames. This property applies when you set the <code>FrameBasedProcessing</code> to <code>true</code>. The default is <code>true</code>.</p> <p><b>Tolerance</b></p> <p>Jump size as true phase discontinuity</p> <p>Specify the jump size that the phase unwrapper recognizes as a true phase discontinuity. The default is set to <math>\pi</math> (rather than a smaller value) to avoid altering legitimate signal features.</p>

# dsp.PhaseUnwrapper

---

To increase the phase wrapper sensitivity, set the `Tolerance` property to a value slightly less than  $\pi$ .

## FrameBasedProcessing

Enable frame-based processing

Set this property to `true` to enable frame-based processing. Set this property to `false` to enable sample-based processing. The default is `true`.

## Methods

<code>clone</code>	Create phase unwrapper object with same property values
<code>getNumInputs</code>	Number of expected inputs to the method
<code>getNumOutputs</code>	Number of outputs of the method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>reset</code>	Reset internal states of Phase Unwrapper System object
<code>step</code>	Unwrap input phase signal input

## Examples

Unwrap input phase data:

```
hunwrap = dsp.PhaseUnwrapper;
p = [0 2/5 4/5 -4/5 -2/5 0 2/5 4/5 -4/5 -2/5 0 2/5 ...
     4/5 -4/5, -2/5]*pi;
y = step(hunwrap, p');
figure,stem(p); hold
stem(y, 'r');
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Unwrap block reference page. The object properties correspond to the Simulink block parameters.

Objects and blocks interpret frames differently. Objects process inputs as frames or as samples by setting the `FrameBasedProcessing` property. Blocks process inputs as frames or as samples by inheriting the frame information from the input ports. See “Set the `FrameBasedProcessing` Property of a System object” for more information.

## See Also

`unwrap`

# **dsp.PhaseUnwrapper.clone**

---

<b>Purpose</b>	Create phase unwrapper object with same property values
<b>Syntax</b>	<code>clone(H)</code>
<b>Description</b>	<code>clone(H)</code> clones the current instance of the phase unwrapper object H.

# dsp.PhaseUnwrapper.getNumInputs

---

**Purpose** Number of expected inputs to the step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs to the step method

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.PhaseUnwrapper.getNumOutputs**

---

**Purpose**            Number of outputs of the `step` method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of the `step` method  
The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

<b>Purpose</b>	Locked status for input attributes and nontunable properties
<b>Syntax</b>	isLocked(H)
<b>Description</b>	isLocked(H) returns the locked state of the phase unwrapper object H.

# dsp.PhaseUnwrapper.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Reset internal states of Phase Unwrapper System object

**Syntax** reset(H)

**Description** reset(H) resets the  $2\pi$  multiplier k to 0 for the phase unwrapper object H. See “Frame-Based Processing” on page 2-1630 for details.

# dsp.PhaseUnwrapper.step

---

**Purpose** Unwrap input phase signal input

**Syntax**  $Y = \text{step}(H,X)$

**Description**  $Y = \text{step}(H,X)$  unwraps the input signal  $X$  in radians for the root mean square (RMS) object  $H$ .

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

## Purpose

Pulse metrics of bilevel waveforms

## Description

The `PulseMetrics` object computes rise times, fall times, pulse widths, and cycle metrics including pulse period, pulse separation, and duty cycle for bilevel waveforms.

To obtain pulse metrics for a bilevel waveform:

- 1 Define and set up your pulse metrics. See “Construction” on page 5-881.
- 2 Call `step` to compute the pulse metrics according to the properties of `dsp.PulseMetrics`. The behavior of `step` is specific to each object in the toolbox.

## Construction

`H = dsp.PulseMetrics` creates a pulse metrics System object, `H`. The object computes the rise time, fall time, and width of a pulse. `dsp.PulseMetrics` also computes cycle metrics such as pulse separations, periods, and duty cycles. Because a pulse contains two transitions, the object contains a superset of the capability defined in `dsp.TransitionMetrics`.

`H = dsp.PulseMetrics('PropertyName',PropertyValue,...)` returns a `PulseMetrics` System object, `H`, with each specified property set to the specified value.

## Properties

### CycleOutputPort

Enable cycle metrics. If `CycleOutputPort` is `true`, cycle metrics are reported for each pulse period.

**Default:** `false`

### MaximumRecordLength

Maximum samples to preserve between calls to `step`. This property requires a positive integer that specifies the maximum number of samples to save between calls to the `step` method. When the number of samples to be saved exceeds this length, the

oldest excess samples are discarded. This property applies when the `RunningMetrics` property is true and is tunable.

**Default:** 1000

## **PercentReferenceLevels**

Lower-, middle-, and upper-percent reference levels. This property contains a three-element numeric row vector that contains the lower-, middle-, and upper-percent reference levels. These reference levels are used as an offset between the lower and upper states of the waveform when computing the duration of each transition.

**Default:** [10 50 90]

## **PercentStateLevelTolerance**

Tolerance of the state level (in percent). This property requires a scalar that specifies the maximum deviation from either the low or high state before it is considered to be outside that state. The tolerance is expressed as a percentage of the waveform amplitude.

**Default:** 2

## **Polarity**

Polarity of pulse to extract. This property specifies the type of pulse to extract by the polarity of the leading transition. Valid values for this property are 'positive' or 'negative'.

**Default:** 'positive'

## **PostshootOutputPort**

Enable posttransition aberration metrics. If this property is set to true, overshoot and undershoot metrics are reported for a region defined immediately after each transition. The posttransition aberration region is defined as the waveform interval that begins

at the end of each transition and whose duration is the value of `PostshootSeekFactor` times the computed transition duration. If a complete subsequent transition is detected before the interval is over, the region is truncated at the start of the subsequent transition. The metrics are computed for each transition that has a complete posttransition aberration region.

**Default:** false

### **PostshootSeekFactor**

Corresponds to the duration of time to search for the overshoot and undershoot metrics immediately following each transition. The duration is expressed as a factor of the duration of the transition. This property is enabled only when the `PostshootOutputPort` property is set to true and is tunable.

**Default:** 3

### **PreshootOutputPort**

Enable pretransition aberration metrics. If `PreshootOutputPort` is set to true, overshoot and undershoot metrics are reported for a region defined immediately before each transition. The pretransition aberration region is defined as the waveform interval that ends at the start of each transition and whose duration is `PreshootSeekFactor` times the computed transition duration.

**Default:** 'false'

### **PreshootSeekFactor**

Corresponds to the duration of time to search for the overshoot and undershoot metrics immediately preceding each transition. The duration is expressed as a factor of the duration of the transition. This property is enabled only when the `PreshootOutputPort` property is set to true and is tunable.

**Default:** 3

## **RunningMetrics**

Enable metrics over all calls to `step`. If `RunningMetrics` is set to `false`, metrics are computed for each call to `step` independently. If `RunningMetrics` is set to `true`, metrics are computed across subsequent calls to `step`. If there are not enough samples to compute metrics associated with the last transition, posttransition aberration region, or settling seek duration in the current record, the object will defer reporting all transition, aberration, and settling metrics associated with the last transition until a subsequent call to `step` is made with enough data to compute all enabled metrics for that transition.

**Default:** `false`

## **SampleRate**

Sampling rate of uniformly-sampled signal. Specify the sample rate in hertz as a positive scalar. This property is used to construct the internal time values that correspond to the input sample values. Time values start with zero. This property applies when the `TimeInputPort` property is set to `false`.

**Default:** 1

## **SettlingOutputPort**

Enable settling metrics. If the `SettlingOutputPort` property is set to `true`, settling metrics are reported for each transition. The region used to compute the settling metrics starts at the midcrossing and lasts until the `SettlingSeekDuration` has elapsed. If an intervening transition occurs, or the signal has not settled within the `PercentStateLevelTolerance` of the final level, `NaN` is returned for each metric. If there are not enough samples after the last transition to complete the `SettlingSeekDuration`, no metrics are reported for the last

transition. The metrics are reported for the transition the next time step is called if the `RunningMetrics` property is set to `true`.

**Default:** `false`

## **SettlingSeekDuration**

Duration of time over which to search for settling. This property value is a scalar that specifies the amount of time to inspect from the mid-reference level crossing (in seconds). If the transition has not yet settled, or a subsequent complete transition is detected within this duration, the `PulseMetrics` object will report `NaN` for all settling metrics. This property is tunable and applies only when you set the `SettlingOutputPort` property to `true`.

**Default:** `0.02`

## **StateLevels**

Low- and high-state levels. This property is a 2–element numeric row vector that contains the low- and high-state levels respectively. These state levels correspond to the nominal logic low and high levels of the pulse waveform. This property is tunable.

**Default:** `[0 2.3]`

## **StateLevelsSource**

Auto or manual state-level computation. If `StateLevelsSource` is set to `'Auto'`, the first record sent to `step` is sent to `dsp.StateLevels` with the default settings to determine the state levels of the incoming waveform. If this property is set to `'Property'`, the object uses the values the user specifies in the `StateLevels` property.

**Default:** `'Property'`

## TimeInputPort

Add input to specify sample instants. Set `TimeInputPort` to `true` to enable an additional real input column vector to `step` to specify the sample instants that correspond to the sample values. If this property is `false`, the sample instants are built internally. The sample instants start at zero and increment by the reciprocal of the `SampleRate` property for subsequent samples. The sample instants continue to increment if the `RunningMetrics` property is set to `true` and no intervening calls to the `reset` or `release` methods are encountered.

**Default:** `false`

## TransitionOutputPort

Enable transition metrics. If the `TransitionOutputPort` property is set to `true`, transition metrics are reported for the initial and final transitions of each pulse.

**Default:** `false`

## Methods

<code>clone</code>	Clones the current instance of the pulse metrics object
<code>getNumInputs</code>	Number of expected inputs to the method
<code>getNumOutputs</code>	Number of outputs of the method
<code>isLocked</code>	Locked status (logical) for input attributes and nontunable properties
<code>plot</code>	Plots signal and metrics computed in last call to

reset	Reset the running pulse metrics object
step	Pulse metrics of bilevel waveforms

## Examples

### Width, Period, and Duty Cycle

Determine the width, period, and duty cycle of a 5 V pulse sampled at 4 MHz.

Load the data and sampling instants.

```
load('pulseex.mat', 'x', 't');
```

Construct your pulse metrics System object. Set the `TimeInputPort` property to `true` to specify the sampling instants as an input to `step`. Set the `CycleOutputPort` property to `true` to obtain metrics for each pulse. Because the input is a 5V pulse, set the `StateLevels` property to `[0 5]`.

```
hpm1 = dsp.PulseMetrics('TimeInputPort',true, ...  
                        'CycleOutputPort', true, ...  
                        'StateLevels',[0 5])
```

Call `step` to compute the cycle metrics and plot the result.

```
[pulse, cycle] = step(hpm1,x,t);  
plot(hpm1)  
text(t(2),-0.5,['Duty Cycle: ',num2str(cycle.DutyCycle)]);
```

### Slew Rates for 2.3 V Digital Clock

Find the slew rates of the leading and trailing edges of a 2.3 V digital clock sampled at 4 MHz.

Construct your pulse metrics System object. Set the `TransitionOutputPort` property to `true` to report transition metrics for the initial and final transitions. Set the `StateLevelsSource` property to `'Auto'` to estimate the state levels from the data.

# dsp.PulseMetrics

---

```
hpm2 = dsp.PulseMetrics('SampleRate',4e6, ...  
                        'TransitionOutputPort', true, ...  
                        'StateLevelsSource','Auto');
```

Compute the pulse and transition metrics and plot the result.

```
[pulse, transition] = step(hpm2,x);  
plot(hpm2)
```

## References

[1] *IEEE Standard on Transitions, Pulses, and Related Waveforms*, IEEE Standard 181, 2003.

## See Also

[dsp.StateLevels](#) | [dsp.TransitionMetrics](#) |

**Purpose** Clones the current instance of the pulse metrics object

**Syntax** `clone(H)`

**Description** `clone(H)` clones the current instance of the pulse metrics object H.

# **dsp.PulseMetrics.getNumInputs**

---

**Purpose**                Number of expected inputs to the `step` method

**Syntax**                `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the `step` method for the pulse metrics object `H`.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose**            Number of outputs of the `step` method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# **dsp.PulseMetrics.isLocked**

---

**Purpose** Locked status (logical) for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the pulse metrics object H.

**Purpose** Plots signal and metrics computed in last call to step

**Syntax** plot(H)

**Description** plot(H) plots the signal and metrics resulting from the last call of the step method.

By default plot displays

- the low and high state levels and the state-level boundaries defined by the PercentStateLevelTolerance property.
- the lower-, middle-, and upper-reference levels.
- the locations of the mid-reference level crossings of the positive (+) and negative (-) transitions of each detected pulse.

When the TransitionOutputPort property is set to true, the locations of the upper and lower crossings are also plotted. When the PreshootOutputPort or PostShootOutputPort properties are set to true, the corresponding overshoots and undershoots are plotted as inverted or noninverted triangles. When the SettlingOutputPort property is set to true, the locations where the signal enters and remains within the lower and upper state boundaries over the specified seek duration are plotted.

# **dsp.PulseMetrics.reset**

---

**Purpose**            Reset the running pulse metrics object

**Syntax**            `reset(H)`

**Description**

`reset(H)` clears information from previous calls to `step`.

## Purpose

Pulse metrics of bilevel waveforms

## Syntax

```
PULSE = step(H,X)
[PULSE,CYCLE] = step(H,X)
[PULSE, TRANSITION] = step(H,X)
[PULSE,PRESHOOT] = step(H,X)
[PULSE,POSTSHOOT] = step(H,X)
[PULSE,SETTLING] = step(H,X)
[...] = step(H,X,T)
```

## Description

`PULSE = step(H,X)` returns a structure array, `PULSE`, whose fields contain real-valued column vectors. The number of rows of each field corresponds to the number of complete pulses found in the real-valued column vector input, `X`. Each pulse starts with a transition of the polarity specified by the `Polarity` property and ends with a transition of the opposite polarity.

`PULSE` fields:

- `PositiveCross` — Instants where the positive-going transitions cross the mid-reference level of each pulse
- `NegativeCross` — Instants where the negative-going transitions cross the mid-reference level of each pulse
- `Width` — Absolute difference between `PositiveCross` and `NegativeCross` of each pulse
- `RiseTime` — Duration between the linearly-interpolated instants when the positive-going (rising) transition of each pulse crosses the lower- and upper-reference levels
- `FallTime` — Duration between the linearly-interpolated instants when the negative-going (falling) transition of each pulse crosses the upper- and lower-reference levels

`[PULSE,CYCLE] = step(H,X)` returns a structure array, `CYCLE`, whose fields contain real-valued column vectors when you set the `CycleOutputPort` property to `true`. The number of rows of each field

corresponds to the number of complete pulse periods found in the real-valued column vector input, `X`. You need at least three consecutive alternating polarity transitions that start and end with the same polarity as the value of the `Polarity` property if you want to compute cycle metrics. If the last transition found in the input `X` does not match the polarity of the `Polarity` property, the pulse separation, period, frequency, and duty cycle are not reported for the last pulse. If the `RunningMetrics` property is set to `true` when this occurs, all pulse, cycle, transition, preshoot, postshoot, and settling metrics associated with the last pulse are deferred until a subsequent call to `step` detects the next transition.

CYCLE fields:

- `Period` — Duration between the first transition of the current pulse and the first transition of the next pulse
- `Frequency` — Reciprocal of the period
- `Separation` — Durations between the mid-reference level crossings of the second transition of each pulse and the first transition of the next pulse
- `Width` — Durations between the mid-reference level crossings of the first and second transitions of each pulse. This is equivalent to the `width` parameter of the `PULSE` structure.
- `DutyCycle` — Ratio of the width to the period for each pulse

`[PULSE, TRANSITION] = step(H,X)` returns a structure array, `TRANSITION`, when you set the `TransitionOutputPort` property to `true`. The fields of `TRANSITION` contain real-valued matrices with two columns which correspond to the metrics of the first and second transitions. The number of rows corresponds to the number of pulses found in the input waveform.

TRANSITION fields:

- `Duration` — Amount of time between the interpolated instants where the transition crosses the lower- and upper-reference levels

- **SlewRate** — Ratio of absolute difference between the upper and lower reference levels to the transition duration
- **MiddleCross** — Linearly-interpolated instant in time where the transition first crosses the mid-reference level
- **LowerCross** — Linearly-interpolated instant where the signal crosses the lower-reference level
- **UpperCross** — Linearly-interpolated instant where the signal crosses the upper-reference level

[PULSE, PRESHOOT] = step(H,X) returns a structure array, PRESHOOT, when you set the PreshootOutputPort property to true. The fields of PRESHOOT contain real-valued 2-column matrices whose row length corresponds to the number of transitions found in the input waveform. The field names are identical to those of the POSTSHOOT structure array.

[PULSE, POSTSHOOT] = step(H,X) returns a structure, POSTSHOOT, when you set the PostshootOutputPort property to true. The fields of POSTSHOOT contain real-valued 2-column matrices whose row length corresponds to the number of transitions found in the input waveform.

PRESHOOT and POSTSHOOT fields:

- **Overshoot** — Overshoot of the region of interest expressed as a percentage of the waveform amplitude
- **Undershoot** — Undershoot of the region of interest expressed as a percentage of the waveform amplitude
- **OvershootLevel** — Level of the overshoot
- **UndershootLevel** — Level of the undershoot
- **OvershootInstant** — Instant that corresponds to the overshoot
- **UndershootInstant** — Instant that corresponds to the undershoot

[PULSE, SETTLING] = step(H,X) returns a structure array, SETTLING, when you set the SettlingOutputPort property to true. The fields of SETTLING correspond to the settling metrics for each transition. Each

## dsp.PulseMetrics.step

---

field is a column vector whose elements correspond to the individual settling durations, levels, and instants.

SETTLING fields:

- **Duration** — Amount of time from when the signal crosses the mid-reference level to the time where the signal enters and remains within the specified `PercentStateLevelTolerance` of the waveform amplitude over the specified settling seek duration
- **Instant** — Instant in time where the signal enters and remains within the specified tolerance
- **Level** — Level of the waveform where it enters and remains within the specified tolerance

The above operations can be used simultaneously, provided the System object properties are set appropriately. One example of providing all possible inputs and returning all possible outputs is :

```
[ PULSE, CYCLE, TRANSITION, PRESHOOT, POSTSHOOT, SETTLING ] =  
step(H,X) which returns the PULSE, CYCLE, TRANSITION, PRESHOOT,  
POSTSHOOT, and SETTLING structures when the CycleOutputPort,  
PreshootOutputPort, PostshootPort, and SettlingOutputPort  
properties are true. You may enable or disable any combination of  
output ports. However, the output arguments are defined in the order  
shown here.
```

```
[ ... ] = step(H,X,T) performs the above metrics with respect to a  
sampled signal, whose sample values, X, and sample instants, T, are  
real-valued column vectors of the same length. The additional input T  
applies only when you set the TimeInputPort property to true.
```

<b>Purpose</b>	Convert reflection coefficients to autocorrelation coefficients
<b>Description</b>	<p>The RCToAutocorrelation object converts reflection coefficients to autocorrelation coefficients.</p> <p>To convert reflection coefficients to autocorrelation coefficients:</p> <ol style="list-style-type: none"><li>1 Define and set up your System object. See “Construction” on page 5-899.</li><li>2 Call <code>step</code> to convert reflection coefficients according to the properties of <code>dsp.RCToAutocorrelation</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.RCToAutocorrelation</code> returns an RCToAutocorrelation System object, H. This object converts reflection coefficients to autocorrelation coefficients, assuming an error power of 1.</p> <p>H = <code>dsp.RCToAutocorrelation('PropertyName',PropertyValue,...)</code> returns an object, H, that converts reflection coefficients into autocorrelation coefficients, with each specified property set to the specified value.</p>
<b>Properties</b>	<p><b>PredictionErrorInputPort</b></p> <p>Enable prediction error power input</p> <p>Choose how to select the prediction error power. When you set this property to <code>true</code>, you must specify the prediction error power as a second input to the <code>step</code> method. When you set this property to <code>false</code>, the object assumes a prediction error power of 1. The default is <code>false</code>.</p>

# dsp.RCToAutocorrelation

---

## Methods

clone	Create RC to autocorrelation object with same property values
getNumInputs	Number of expected inputs to step method
getNumOutputs	Number of outputs of step method
isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
step	Convert columns of reflection coefficients to autocorrelation coefficients

## Examples

Convert reflection coefficients to autocorrelation coefficients:

```
k = [-0.8091 0.2525 -0.5044 0.4295 -0.2804 0.0711].';  
hrc2ac = dsp.RCToAutocorrelation;  
ac = step(hrc2ac, k);
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the LPC/RC to Autocorrelation block reference page. The object properties correspond to the block parameters, except:

- There is no object property that corresponds to the **Type of conversion** block parameter.
- **PredictionErrorInputPort** is a pop-up menu choice on the block. Setting the PredictionErrorInputPort object property to false corresponds to selecting Assume P = 1 in the pop-up menu. Setting PredictionErrorInputPort to true corresponds to selecting Via input port from the pop-up menu.

**See Also**

[dsp.LPCToLSF](#) | [dsp.LPCToRC](#) | [dsp.LPCToCepstral](#) |  
[dsp.LPCToAutocorrelation](#)

# **dsp.RCToAutocorrelation.clone**

---

**Purpose** Create RC to autocorrelation object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a `RCToAutocorrelation System` object `C`, with the same property values as `H`. The clone method creates a new unlocked object.

# dsp.RCToAutocorrelation.getNumInputs

---

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.RCToAutocorrelation.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**      `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `RCToAutocorrelation System` object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.RCToAutocorrelation.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Convert columns of reflection coefficients to autocorrelation coefficients

**Syntax** AC = step(H,K)  
AC = step(H,K,P)

**Description** AC = step(H,K) converts the columns of the reflection coefficients, K, to autocorrelation coefficients, AC.

AC = step(H,K,P) when you set the PredictionErrorInputPort property to true, converts the columns of the reflection coefficients, K, to autocorrelation coefficients, AC, using P as the prediction error power. P must be a row vector with same number of columns as in K.

---

**Note** The object performs an initialization the first time the step method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the release method to unlock the object.

---

# dsp.RCToLPC

---

<b>Purpose</b>	Convert reflection coefficients to linear prediction coefficients
<b>Description</b>	<p>The RCToLPC object converts reflection coefficients to linear prediction coefficients.</p> <p>To convert reflection coefficients to LPC:</p> <ol style="list-style-type: none"><li>1 Define and set up your RC to LPC System object. See “Construction” on page 5-908.</li><li>2 Call <code>step</code> to convert RC to LPC according to the properties of <code>dsp.RCToLPC</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.RCToLPC</code> returns an RC to LPC System object, <code>H</code>, that converts reflection coefficients (RC) to linear prediction coefficients (LPC).</p> <p><code>H = dsp.RCToLPC('PropertyName',PropertyValue,...)</code> returns an RC to LPC conversion object, <code>H</code>, with each specified property set to the specified value.</p>
<b>Properties</b>	<p><b>PredictionErrorOutputPort</b></p> <p>Enable normalized prediction error power output</p> <p>Set this property to <code>true</code> to return the normalized error power as a vector with one element per input channel. Each element varies between 0 and 1. The default is <code>true</code>.</p> <p><b>ExceptionOutputPort</b></p> <p>Produce output with stability status of filter represented by LPC coefficients</p> <p>Set this property to <code>true</code> to return the stability of the filter. The output is a vector of a length equal to the number of channels. A logical value of 1 indicates a stable filter. A logical value of 0 indicates an unstable filter. The default is <code>false</code>.</p>

**Methods**

clone	Creates instance of object with same property values
getNumInputs	Number of expected inputs to step method
getNumOutputs	Number of outputs of step method
isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
step	Convert columns of reflection coefficients to linear prediction coefficients

**Examples**

Convert reflection coefficients to linear prediction coefficients:

```

hlevinson = dsp.LevinsonSolver;
hac = dsp.Autocorrelator;
hac.MaximumLagSource = 'Property';
hac.MaximumLag = 10; % Compute autocorrelation
                    % lags between [0:10]
hrc2lpc = dsp.RCToLPC;

x = (1:100)';
a = step(hac, x);
k = step(hlevinson, a); % Compute reflection coefficients
[A, P] = step(hrc2lpc, k);

```

**Algorithms**

This object implements the algorithm, inputs, and outputs described on the LPC to/from RC block reference page. The object properties correspond to the block parameters, except:

There is no object property that corresponds to the **Type of conversion** block parameter. The object always converts LPC to RC.

# **dsp.RCToLPC**

---

## **See Also**

[dsp.LPCToRC](#) | [dsp.LPCToAutocorrelation](#)

**Purpose** Creates instance of object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates an RCToLPC System object `C`, with the same property values as `H`. The clone method creates a new unlocked object.

# **dsp.RCToLPC.getNumInputs**

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs to the step method

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# **dsp.RCToLPC.isLocked**

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the RCToLPC System object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

## dsp.RCToLPC.step

---

**Purpose** Convert columns of reflection coefficients to linear prediction coefficients

**Syntax**

```
[A,P] = step(H,K)
A = step(H,K)
[... , S] = step(H,K)
```

**Description** [A,P] = step(H,K) converts the columns of the reflection coefficients, K, to linear prediction coefficients, A, and outputs the normalized prediction error power, P.

A = step(H,K) when the PredictionErrorOutputPort property is false, converts the columns of the reflection coefficients, K, to linear prediction coefficients, A.

[... , S] = step(H,K) also outputs the LPC filter stability, S, when the ExceptionOutputPort property is true.

---

**Note** The object performs an initialization the first time the step method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the release method to unlock the object.

---

---

<b>Purpose</b>	Root mean square of vector elements
<b>Description</b>	<p>The RMS object computes the root mean square (RMS) value.</p> <p>To compute the RMS value of your input:</p> <ol style="list-style-type: none"><li>1 Define and set up your RMS calculation. See “Construction” on page 5-917.</li><li>2 Call <code>step</code> to compute the RMS value for an input according to the properties of <code>dsp.RMS</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.RMS</code> returns a System object, <code>H</code>, that computes the root mean square (RMS) of an input or a sequence of inputs over the specified Dimension.</p> <p><code>H = dsp.RMS('PropertyName',PropertyValue,...)</code> returns an RMS System object, <code>H</code>, with each specified property set to the specified value.</p>
<b>Properties</b>	<p><b>RunningRMS</b></p> <p>Enable calculating RMS over time</p> <p>Set this property to <code>true</code> to enable calculating the RMS over successive calls to the <code>step</code> method.</p> <p><b>Default:</b> <code>false</code></p> <p><b>ResetInputPort</b></p> <p>Enable resetting in running RMS mode</p> <p>Set this property to <code>true</code> to enable resetting the running RMS. When the property is set to <code>true</code>, you must specify a reset input to the <code>step</code> method to reset the running RMS. This property applies when you set the <code>RunningRMS</code> property to <code>true</code>.</p> <p><b>Default:</b> <code>false</code></p>

## **ResetCondition**

Reset condition for running RMS mode

Specify the event to reset the running RMS as one of **Rising edge**, **Falling edge**, **Either edge**, or **Non-zero**. **Non-zero** resets the running RMS each time a nonzero sample is acquired. See “Rising and Falling Edges” on page 5-919 for definitions of rising and falling edges. This property applies when you set the **ResetInputPort** property to **true**.

**Default:** Non-zero

## **Dimension**

Dimension to compute RMS value along

Specify the dimension along which to calculate the RMS as one of **All**, **Row**, **Column**, or **Custom**. This property applies only when you set the **RunningRMS** property to **false**. Specifying the **Dimension** property as **All** computes the RMS value over the entire input.

**Default:** Column

## **CustomDimension**

Numerical dimension to operate along

Specify the dimension (one-based scalar integer value) of the input signal, along which the RMS is computed. The cannot exceed the number of dimensions in the input signal. This property applies when you set the **Dimension** property to **Custom**.

**Default:** 1

## **FrameBasedProcessing**

Enable frame-based processing

Set this property to **true** to enable frame-based processing for 2-dimensional inputs. Set this property to **false** to

enable sample-based processing. The object always performs sample-based processing for N-D inputs where N is greater than 2. This property applies when you set the RunningRMS property to true.

**Default:** true

## Methods

clone	Clones the current instance of the root mean square object
getNumInputs	Number of expected inputs to the method
getNumOutputs	Number of outputs of the method
isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
reset	Reset the running root mean square object
step	Root mean square of input

## Definitions

### Root-Mean-Square Level

The root-mean-square level of a vector,  $X$ , is



$$X_{\text{RMS}} = \sqrt{\frac{1}{N} \sum_{n=1}^N |X_n|^2}$$

with the summation performed along the specified dimension.

### Rising and Falling Edges



A rising edge:

- Rises from a negative value to a positive value or zero.
- Rises from zero to a positive value, where the rise is not a continuation of a rise from a negative value to zero.



A falling edge:

- Falls from a positive value to a negative value or zero.
- Falls from zero to a negative value, where the fall is not a continuation of a fall from a positive value to zero.



## Examples

### RMS Value of Vector Input

Compute the RMS value of a vector consisting of the integers 1 to 10.

Create a row vector of the integers 1 to 10. Construct the RMS System object with the Dimension property set to 'literal'. Compute the RMS value.

```
x = 1:10;  
hrms = dsp.RMS('Dimension','row');  
rmsval = step(hrms,x);
```

### RMS Value of Matrix Input

Compute the RMS value of a matrix with the Dimension property set to 'All'.

```
in2 = magic(4);  
hrms2d = dsp.RMS;  
hrms2d.Dimension = 'All';  
y_rms2 = step(hrms2d, in2);
```

The output is equivalent to reshaping the 4-by-4 matrix into a 16-by-1, or 1-by-16 vector and computing the RMS value for the vector.

## Algorithms

This object implements the algorithm, inputs, and outputs described on the RMS block reference page. The object properties correspond to the Simulink block parameters, except:

- **Treat sample-based row input as a column** block parameter is not supported by the dsp.RMS object.
- **Reset Port** block parameter corresponds to both the ResetCondition and the ResetInputPort object properties.

Both this object and its corresponding block let you specify whether to process inputs as individual samples or as frames of data. The object uses the FrameBasedProcessing property. The block uses the **Input processing** parameter. See “Set the FrameBasedProcessing Property of a System object” for more information.

# dsp.RMS

---

## **See Also**

`dsp.Mean` | `dsp.StandardDeviation` | `dsp.Variance`.

**Purpose** Clones the current instance of the root mean square object

**Syntax** `clone(H)`

**Description** `clone(H)` clones the current instance of the root mean square (RMS) object H

# **dsp.RMS.getNumInputs**

---

**Purpose**            Number of expected inputs to the `step` method

**Syntax**            `N = getNumInputs(H)`

**Description**      `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the `step` method for the root mean square (RMS) object `H`.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose**            Number of outputs of the `step` method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# dsp.RMS.isLocked

---

<b>Purpose</b>	Locked status for input attributes and nontunable properties
<b>Syntax</b>	<code>isLocked(H)</code>
<b>Description</b>	<code>isLocked(H)</code> returns the locked state of the root mean square (RMS) object H.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

## **dsp.RMS.reset**

---

**Purpose**            Reset the running root mean square object

**Syntax**            `reset(H)`

**Description**        `reset(H)` resets the running root mean square (RMS) for the object H.

**Purpose** Root mean square of input

**Syntax**  
 $Y = \text{step}(H,X)$   
 $Y = \text{step}(H,X,R)$

**Description**  $Y = \text{step}(H,X)$  computes the root mean square (RMS) output,  $Y$ , of input vector  $X$ . When the `RunningRMS` property is true,  $Y$  corresponds to the RMS of the input elements over successive calls to the `step` method.

$Y = \text{step}(H,X,R)$  resets the running RMS state based on the value of  $R$ , the reset signal, and the `ResetCondition` property. This computation is possible when you set both the `RunningRMS` and the `ResetInputPort` properties to true.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.ScalarQuantizerDecoder

---

**Purpose** Convert each index value into quantized output value

**Description** The `ScalarQuantizerDecoder` object converts each index value into a quantized output value. The specified codebook defines the set of all possible quantized output values or codewords. Input index values less than 0 are set to 0 and index values greater  $N - 1$  are set to  $N - 1$ .  $N$  is the length of the codebook vector.

To convert an index value into a quantized output value:

- 1 Define and set up your scalar quantizer decoder. See “Construction” on page 5-930.
- 2 Call `step` to convert the index value according to the properties of `dsp.ScalarQuantizerDecoder`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.ScalarQuantizerDecoder` returns a scalar quantizer decoder System object, `H`, that transforms zero-based input index values into quantized output values.

`H = dsp.ScalarQuantizerDecoder('PropertyName',PropertyValue,...)` returns a scalar quantizer decoder object, `H`, with each specified property set to the specified value.

**Properties** **CodebookSource**  
How to specify codebook values  
Specify how to determine the codebook values as `Property` or `Input port`. The default is `Property`.

**Codebook**  
Codebook  
Specify the codebook as a vector of quantized output values that correspond to each index value. The default is `1:10`. This property is tunable.

## OutputDataType

Data type of codebook and quantized output

Specify the data type of the codebook and quantized output values as `Same` as `input`, `double`, `single` or `Custom`. The default is `double`.

## Fixed-Point Properties

### CustomOutputDataType

Output word and fraction lengths

Specify the output fixed-point type as a signed or unsigned `numericType` object. This property applies only when you set the `OutputDataType` property to `Custom`. The default is `numericType(true,16)`.

## Methods

<code>clone</code>	Create scalar quantizer decoder object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>step</code>	Operate on inputs to calculate outputs

## Examples

Given a codebook and index values as inputs, determine the corresponding output quantized values:

```
codebook = single([-2.1655 -1.3238 -0.7365 -0.2249 0.2726, ...
```

# dsp.ScalarQuantizerDecoder

---

```
0.7844 1.3610 2.1599]);  
indices = uint8([1 3 5 7 6 4 2 0]);  
hsqdec = dsp.ScalarQuantizerDecoder;  
hsqdec.CodebookSource = 'Input port';  
qout = step(hsqdec, indices, codebook);
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Scalar Quantizer Decoder block reference page. The object properties correspond to the block parameters, except:

There is no object property that directly corresponds to the **Action for out of range index value** block parameter. The object sets any index values less than 0 to 0 and any index values greater than or equal to  $N$  to  $N - 1$ .

## See Also

[dsp.ScalarQuantizerEncoder](#) | [dsp.VectorQuantizerDecoder](#)

**Purpose** Create scalar quantizer decoder object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a `ScalarQuantizerDecoder System` object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with uninitialized states.

# dsp.ScalarQuantizerDecoder.getNumInputs

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**      `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.ScalarQuantizerDecoder.getNumOutputs**

---

**Purpose**

Number of outputs of step method

**Syntax**

`N = getNumOutputs(H)`

**Description**

`N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# **dsp.ScalarQuantizerDecoder.isLocked**

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `ScalarQuantizerDecoder` System object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

# dsp.ScalarQuantizerDecoder.step

---

**Purpose** Operate on inputs to calculate outputs

**Syntax**  $Q = \text{step}(H, I)$   
 $Q = \text{step}(H, I, C)$

**Description**  $Q = \text{step}(H, I)$  returns the quantized output values  $Q$  corresponding to the input indices  $I$ . The data type of  $I$  can be `uint8`, `uint16`, `uint32`, `int8`, `int16`, or `int32`. The `OutputDataType` property determines the data type for  $Q$ .

$Q = \text{step}(H, I, C)$  uses input  $C$  as the codebook values when you set the `CodebookSource` property to `Input` port. The data type of  $C$  can be `double`, `single`, or `fixed-point`. The output  $Q$  has the same data type as the codebook input  $C$ .

<b>Purpose</b>	Associate input value with index value of quantization region
<b>Description</b>	<p>The <code>ScalarQuantizerEncoder</code> object encodes each input value by associating that value with the index value of the quantization region. Then, the object outputs the index of the associated region.</p> <p>To encode an input value by associating it with an index value of the quantization region:</p> <ol style="list-style-type: none"><li>1 Define and set up your scalar quantizer encoder. See “Construction” on page 5-939.</li><li>2 Call <code>step</code> to encode the input value according to the properties of <code>dsp.ScalarQuantizerEncoder</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.ScalarQuantizerEncoder</code> returns a scalar quantizer encoder System object, <code>H</code>. This object maps each input value to a quantization region by comparing the input value to the user-specified boundary points.</p> <p><code>H = dsp.ScalarQuantizerEncoder('PropertyName',PropertyValue,...)</code> returns a scalar quantizer encoder object, <code>H</code>, with each specified property set to the specified value.</p>
<b>Properties</b>	<p><b>BoundaryPointsSource</b></p> <p>Source of boundary points</p> <p>Specify how to determine the boundary points and codebook values as <code>Property</code> or <code>Input port</code>. The default is <code>Property</code>.</p> <p><b>Partitioning</b></p> <p>Quantizer is bounded or unbounded</p> <p>Specify the quantizer as <code>Bounded</code> or <code>Unbounded</code>. The default is <code>Bounded</code>.</p> <p><b>BoundaryPoints</b></p>

Boundary points of quantizer regions

Specify the boundary points of quantizer regions as a vector. The vector values must be in ascending order. Let [p0 p1 p2 p3 ... pN] denote the boundary points property in the quantizer. If the quantizer is bounded, the object uses this property to specify [p0 p1 p2 p3 ... pN]. If the quantizer is unbounded, the object uses this property to specify [p1 p2 p3 ... p(N-1)] and sets p0 = -Inf and pN = +Inf. This property applies when you set the BoundaryPointsSource property to Property. The default is 1:10. This property is tunable.

## SearchMethod

Find quantizer index by linear or binary search

Specify whether to find the appropriate quantizer index using a linear search or a binary search as one of Linear or Binary. The computational cost of the linear search method is of the order  $P$  and the computational cost of the binary search method is of the order

$$\log_2(P)$$

where  $P$  is the number of boundary points. The default is Linear.

## TiebreakerRule

Behavior when input equals boundary point

Specify whether the input value is assigned to the lower indexed region or higher indexed region when the input value equals boundary point by selecting Choose the lower index or Choose the higher index. The default is Choose the lower index.

## CodewordOutputPort

Enable output of codeword value

Set this property to true to output the codeword values that correspond to each index value. The default is false.

## QuantizationErrorOutputPort

Enable output of quantization error

Set this property to `true` to output the quantization error for each input value. The quantization error is the difference between the input value and the quantized output value. The default is `false`.

## **Codebook**

Codebook

Specify the codebook as a vector of quantized output values that correspond to each region. If the `Partitioning` property is `Bounded` and the boundary points vector has length `N`, you must set this property to a vector of length `N-1`. If the `Partitioning` property is `Unbounded` and the boundary points vector has length `N`, you must set this property to a vector of length `N+1`. This property applies when you set the `BoundaryPointsSource` property to `Property` and either the `CodewordOutputPort` property or the `QuantizationErrorOutputPort` property is `true`. The default is `1.5:9.5`. This property is tunable.

## **ClippingStatusOutputPort**

Enable output of clipping status

Set this property to `true` to output the clipping status. The output is a 1 when an input value is outside the range defined by the `BoundaryPoints` property. When the value is inside the range, the exception output is a 0. This property applies when you set the `Partitioning` property to `Bounded`. The default is `false`.

## **OutputIndexDataType**

Data type of the index output

Specify the data type of the index output from the object as: `int8`, `uint8`, `int16`, `uint16`, `int32`, `uint32`. The default is `int32`.

## **Fixed-Point Properties**

### **RoundingMethod**

# dsp.ScalarQuantizerEncoder

---

Rounding method for fixed-point operations

Specify the rounding method as `Ceiling`, `Convergent`, `Floor`, `Nearest`, `Round`, `Simplest` or `Zero`. The default is `Floor`.

## OverflowAction

Overflow action for fixed-point operations

Specify the overflow action as `Wrap` or `Saturate`. The default is `Wrap`.

## Methods

<code>clone</code>	Create an instance of an object with the same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>step</code>	Operate on inputs to calculate outputs

## Examples

Quantize the varying fractional inputs between zero and five to the closest integers, and then plot the results:

```
hsqe = dsp.ScalarQuantizerEncoder;  
hsqe.BoundaryPoints = [-.001 .499 1.499 ...  
    2.499 3.499 4.499 5.001];  
hsqe.CodewordOutputPort = true;  
hsqe.Codebook = [0 1 2 3 4 5];  
input = (0:0.02:5)';  
[index, quantizedValue] = step(hsqe, input);  
plot(1:length(input), [input quantizedValue]);
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the [Scalar Quantizer Encoder](#) block reference page. The object properties correspond to the block parameters.

## See Also

[dsp.ScalarQuantizerDecoder](#) | [dsp.VectorQuantizerEncoder](#)

# **dsp.ScalarQuantizerEncoder.clone**

---

**Purpose** Create an instance of an object with the same property values

**Syntax**

**Description** `C = clone(H)` creates a `ScalarQuantizerEncoder` object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object.

# **dsp.ScalarQuantizerEncoder.getNumInputs**

---

**Purpose**                    Number of expected inputs to step method

**Syntax**                    `N = getNumInputs(H)`

**Description**              `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.ScalarQuantizerEncoder.getNumOutputs**

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `ScalarQuantizerEncoder` object `H`.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.ScalarQuantizerEncoder.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

## Purpose

Operate on inputs to calculate outputs

## Syntax

```
INDEX= step(HSQE,INPUT)
[...] = step(HSQE,INPUT,BPOINTS)
[...] = step(HSQE,INPUT,BPOINTS,CODEBOOK)
[... ,CODEWORD] = step(HSQE, ...)
[... , QERR] = step(HSQE, ...)
[... ,CLIPSTATUS] = step(HSQE, ...)
```

## Description

INDEX= step(HSQE,INPUT) returns the INDEX of the quantization region to which the INPUT belongs. The input data, boundary points, codebook values, quantized output values, and the quantization error must have the same data type whenever they are present.

[...] = step(HSQE,INPUT,BPOINTS) when the BoundaryPointsSource property is Input port, uses input BPOINTS as the boundary points .

[...] = step(HSQE,INPUT,BPOINTS,CODEBOOK) uses input BPOINTS as the boundary points and input CODEBOOK as the codebook when the BoundaryPointsSource property is Input port and either the CodewordOutputPort property or the QuantizationErrorOutputPort property is true.

[... ,CODEWORD] = step(HSQE, ...) outputs the CODEWORD values that corresponds to each index value when the CodewordOutputPort property is true.

[... , QERR] = step(HSQE, ...) outputs the quantization error QERR for each input value when the QuantizationErrorOutputPort property is true.

[... ,CLIPSTATUS] = step(HSQE, ...) also returns output CLIPSTATUS as the clipping status output port for each input value when the Partitioning property is Bounded and the ClippingStatusOutputPort property is true. If an input value is outside the range defined by the BoundaryPoints property, CLIPSTATUS is true. If an input value is inside the range, CLIPSTATUS is false.

## **dsp.ScalarQuantizerEncoder.step**

---

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

<b>Purpose</b>	Log simulation data in buffer
<b>Description</b>	<p>The <code>SignalSink</code> object logs MATLAB simulation data. This object accepts any numeric data type.</p> <p>To log MATLAB simulation data :</p> <ol style="list-style-type: none"><li>1 Define and set up your signal sink. See “Construction” on page 5-951.</li><li>2 Call <code>step</code> to log the simulation data according to the properties of <code>dsp.SignalSink</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.SignalSink</code> returns a signal sink, <code>H</code>, that logs 2-D input data in the object.</p> <p><code>H = dsp.SignalSink('PropertyName',PropertyValue,...)</code> returns a signal sink, <code>H</code>, with each specified property set to the specified value.</p>
<b>Properties</b>	<p><b>FrameBasedProcessing</b></p> <p>Process input as frames or samples</p> <p>To enable frame-based processing for 2-D inputs, set this property to <code>true</code>. When you set this property to <code>false</code>, the object performs sample-based processing on 2-D inputs. The signal sink object always performs sample-based processing for N-D inputs when <code>N</code> is greater than 2. The default is <code>true</code>.</p> <p><b>BufferLength</b></p> <p>Maximum number of input frames or samples to log</p> <p>Specify the maximum number of frames to log when the object is performing frame-based processing, or the maximum number of samples to log when the object is performing sample-based processing. The object always preserves the most recent data in the buffer. When you specify a buffer length that is greater than the input length, the object pads the end of the logged data with</p>

# dsp.SignalSink

---

zeros. To capture all input data without extra padding, set the `BufferLength` property to `inf`. The default is `inf`.

## Decimation

Decimation factor

Setting this property to any positive integer  $d$  causes the signal sink to write data at every  $d$ th sample. The default is 1.

## FrameHandlingMode

Output dimensionality for frame-based inputs

Set the dimension of the output array for frame-based inputs as 2-D array (`concatenate`) or 3-D array (`separate`). Concatenation occurs along the first dimension for 2-D array (`concatenate`). This property applies only when you set the `FrameBasedProcessing` property to `true`. The default is 2-D array (`concatenate`).

## Buffer

Logged Data (read only)

The signal sink writes simulation data into a buffer. Specify the maximum length of the buffer with the `BufferLength` property.

## Methods

<code>clone</code>	Create signal logger object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes

reset	Reset internal states of signal logger object
step	Store signal in buffer

## Examples

Log input data.

```
hlog = dsp.SignalSink;
for i=1:10
    y = sin(i);
    step(hlog,y);
end
log = hlog.Buffer; % log = sin([1;2;3;4;5;6;7;8;9;10])
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Signal To Workspace block reference page. The object properties correspond to the block properties, except:

The object always generates fixed-point output for fixed-point input.

Objects and blocks interpret frames differently. Objects process inputs as frames or as samples by setting the `FrameBasedProcessing` property. Blocks process inputs as frames or as samples by inheriting the frame information from the input ports. See “Set the `FrameBasedProcessing` Property of a System object” for more information.

## See Also

`dsp.SignalSource`

# **dsp.SignalSink.clone**

---

**Purpose** Create signal logger object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a `SignalSink` object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with uninitialized states.

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.SignalSink.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**      `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `SignalSink` object `H`.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# **dsp.SignalSink.reset**

---

**Purpose**            Reset internal states of signal logger object

**Syntax**            reset(H)

**Description**        reset(H) sets the internal states of the SignalSink object H to their initial values.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

# dsp.SignalSink.step

---

**Purpose** Store signal in buffer

**Syntax** `step(H,Y)`

**Description** `step(H,Y)` buffers the signal `Y`. The buffer may be accessed at any time from the `Buffer` property of `H`.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

## Purpose

Import variable from workspace

## Description

The `SignalSource` object imports a variable from the MATLAB workspace.

To import a variable from the MATLAB workspace:

- 1 Define and set up your signal source. See “Construction” on page 5-961.
- 2 Call `step` to import the variable according to the properties of `dsp.SignalSource`. The behavior of `step` is specific to each object in the toolbox.

## Construction

`H = dsp.SignalSource` returns a signal source System object, `H`, that outputs the variable one sample or frame at a time.

`H = dsp.SignalSource('PropertyName',PropertyValue,...)` returns a signal source object, `H`, with each specified property set to the specified value.

`H = dsp.SignalSource(signal,spf,'PropertyName',PropertyValue,...)` returns a signal source object, `H`, with the `Signal` property set to `signal`, the `SamplesPerFrame` property set to `spf`, and other specified properties set to the specified values.

## Properties

### Signal

Variable or expression containing the signal

Specify the name of the workspace variable from which to import the signal, or a valid expression specifying the signal. The default is `[1:10]`.

### SamplesPerFrame

Number of samples per output frame

# dsp.SignalSource

---

Specify the number of samples to buffer into each output frame. This property must be 1 when you specify a 3-D array in the Signal property. The default is 1.

## SignalEndAction

Action after final signal values are generated

Specify the output after all of the specified signal samples have been generated as one of Set to zero, Hold final value, or Cyclic repetition. The default is Set to zero.

## Methods

clone	Create signal reader object with same property values
getNumInputs	Number of expected inputs to step method
getNumOutputs	Number of outputs of step method
isDone	End-of-file status for signal reader object
isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
reset	Reset internal states of signal reader object
step	Read one sample or frame of signal

## Examples

Create a signal source to output one sample at a time:

```
hsr1 = dsp.SignalSource;  
hsr1.Signal = randn(1024, 1);  
y1 = zeros(1024,1);  
idx = 1;
```

```
while(~isDone(hsr1))
    y1(idx) = step(hsr1);
    idx = idx+1;
end
```

---

Create a signal source to output vectors:

```
hsr2 = dsp.SignalSource(randn(1024, 1), 128);
y2 = step(hsr2); % y2 is a 128-by-1 frame of samples
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Signal From Workspace block reference page. The object properties correspond to the block parameters, except:

The object does not have properties that correspond to the **Sample time** or **Warn when frame size does not evenly divide input length** block parameters.

## See Also

`dsp.SignalSink`

# **dsp.SignalSource.clone**

---

**Purpose** Create signal reader object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a `SignalSource` object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with un-initialized states.

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.SignalSource.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** End-of-file status for signal reader object

**Syntax** isDone(H)

**Description** isDone(H) returns a logical value indicating whether or not the SignalSource object, H, has reached the end of the imported signal. If the SignalEndAction property is set to `Cyclic` repetition, this method will return `true` every time the reader reaches the end.

# dsp.SignalSource.isLocked

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `SignalSource` object `H`.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Reset internal states of signal reader object

**Syntax** reset(H)

**Description** reset(H) resets the signal reader object H, to start reading from the beginning of the imported signal.

# dsp.SignalSource.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Read one sample or frame of signal

**Syntax**  $Y = \text{step}(H)$

**Description**  $Y = \text{step}(H)$  outputs one sample or frame of data,  $Y$ , from each column of the imported signal. The imported signal is the variable or expression you specify for the **Signal** property of the **SignalSource** System object  $H$ .

---

**Note** The object performs an initialization the first time the **step** method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the **release** method to unlock the object.

---

# dsp.SineWave

---

**Purpose** Discrete-time sinusoid

**Description** The SineWave object generates a discrete-time sinusoid. The sine wave object generates a real-valued sinusoid or a complex exponential. A real-valued, discrete-time sinusoid is defined as:

$$y(n) = A \sin(2\pi fn + \phi)$$

where  $A$  is the amplitude,  $f$  is the frequency in hertz, and  $\phi$  is the initial phase, or phase offset, in radians. A complex exponential is defined as:

$$y(n) = Ae^{j(2\pi fn + \phi)}$$

For both real and complex sinusoids, the amplitude, frequency, and phase offsets can be scalars or length- $N$  vectors, where  $N$  is the desired number of channels in the output. When you specify at least one of these properties as a length- $N$  vector, scalar values specified for the other properties are applied to each of the  $N$  channels.

To generate a discrete-time sinusoid:

- 1 Define and set up your sine wave. See “Construction” on page 5-972.
- 2 Call `step` to generate the sinusoid according to the properties of `dsp.SineWave`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.SineWave` returns a sine wave object, `H`, that generates a real-valued sinusoid with an amplitude of 1, a frequency of 100 Hz, and a phase offset of 0. By default, the sine wave object only generates one sample.

`H = dsp.SineWave('PropertyName',PropertyValue, ...)` returns a sine wave object, `H`, with each property set to the specified value.

`H = dsp.SineWave(AMP,FREQ,PHASE, 'PropertyName',PropertyValue, ...)` returns a sine wave object, `H`, with the `Amplitude` property set to `AMP`, the `Frequency` property set to

FREQ, the PhaseOffset property set to PHASE, and the other specified properties set to the specified values.

## Properties

### Amplitude

Amplitude of the sine wave

Specify the amplitude as a length- $N$  vector containing the amplitudes of the sine waves in each of  $N$  output channels, or a scalar to apply to all  $N$  channels. The vector length must equal that specified for the Frequency and PhaseOffset properties. The default value is 1. This property is tunable when the Method property is Trigonometric function or Differential.

### Frequency

Frequency of the sine wave

Specify a length- $N$  vector containing frequencies, in hertz, of the sine waves in each of  $N$  output channels, or a scalar to apply to all  $N$  channels. The vector length must equal that specified for the Amplitude and PhaseOffset properties. You can specify positive, zero, or negative frequencies. The default is 100. This property is tunable when the Method property is Trigonometric function.

### PhaseOffset

Phase offset of the sine wave in radians

A length- $N$  vector containing the phase offsets, in radians, of the sine waves in each of  $N$  output channels, or a scalar to apply to all  $N$  channels. The vector length must equal that specified for the Amplitude and Frequency properties. The default value is 0. This property is tunable when the Method property is Trigonometric function.

### ComplexOutput

Indicates whether the sine wave is complex or real

Set to true to output a complex exponential. The default value is false.

## **Method**

Method used to generate sinusoids

The sinusoids are generated by either the `Trigonometric` function, `Table lookup`, or `Differential` methods. The `trigonometric` function method computes the sinusoid by sampling the continuous-time sinusoid. The `table lookup` method precomputes the unique samples of every output sinusoid at the start of the simulation, and recalls the samples from memory as needed. The `differential` method uses an incremental algorithm. This algorithm computes the output samples based on the output values computed at the previous sample time and precomputed update terms. The default value is `Trigonometric` function.

## **TableOptimization**

Optimizes the table of sine values for speed or memory

Optimizes the table of sine values for `Speed` or `Memory`. When optimized for speed, the table contains  $k$  elements, and when optimized for memory, the table contains  $k/4$  elements, where  $k$  is the number of input samples in one full period of the sine wave. This property applies only when the `Method` property is `Table lookup`. The default value is `Speed`.

## **SampleRate**

Sampling rate for the sine wave

Specify the sampling rate of the output, in hertz, as a positive numeric scalar. The default is 1000.

## **SamplesPerFrame**

Number of samples per frame

Specify the number of consecutive samples from each sinusoid to buffer into the output frame. The default is 1.

## **OutputDataType**

Output data type

Specify the output data type as `double`, `single`, or `Custom`. The default value is `double`.

## Fixed-Point Properties

### CustomOutputDataType

Output word and fraction lengths

Specify the output fixed-point type as a `numericType` object with a `Signedness` of `Auto`. This property applies only when the `OutputDataType` property is `Custom`. The default value is `numericType([1,16])`.

## Methods

<code>clone</code>	Create sine wave object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>reset</code>	Reset sine wave to the beginning
<code>step</code>	Discrete-time sine wave

## Examples

Generate a sine wave with an amplitude of 2, frequency of 10 Hz, and initial phase of 0:

```
hsin1 = dsp.SineWave(2, 10);  
hsin1.SamplesPerFrame = 1000;  
y = step(hsin1);
```

# dsp.SineWave

---

```
plot(y);
```

---

Generate two sine waves offset by a phase of  $\pi/2$  radians:

```
hsin2 = dsp.SineWave;  
hsin2.Frequency = 10;  
hsin2.PhaseOffset = [0 pi/2];  
hsin2.SamplesPerFrame = 1000;  
y = step(hsin2);  
plot(y);
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Sine Wave block reference page. The object properties correspond to the block parameters.

## See Also

[dsp.Chirp](#) | [dsp.NCO](#)

**Purpose** Create sine wave object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a sine wave object, `C`, with the same property values as `H`. The clone method creates a new unlocked object with uninitialized states.

# dsp.SineWave.getNumInputs

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose** Number of outputs of step method

**Syntax** `N = getNumOutputs(H)`

**Description** `N = getNumOutputs(H)` returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# **dsp.SineWave.isLocked**

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the sine wave object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

# dsp.SineWave.reset

---

**Purpose**                Reset sine wave to the beginning

**Syntax**                reset(H)

**Description**        reset(H) resets the sine wave object to the beginning ( $n=0$ ). If you invoke the `step` method without first invoking the `reset` method, the sine wave object generates additional samples of the original sinusoid. As an example:

```
H = dsp.SineWave('Amplitude',1,'Frequency',1/4,'SamplesPerFrame',7);
% 7 samples of a sine wave with frequency of 1/4 Hz
y = step(H);
% Call step method without reset
y1 = step(H);
stem([y; y1])
% y1 is a continuation of y
% Now reset
reset(H);
y2 = step(H);
% y2 starts at n=0 and equals y
isequal(y,y2)
```

**Purpose** Discrete-time sine wave

**Syntax**  $Y = \text{step}(H)$

**Description**  $Y = \text{step}(H)$  produces the sine wave  $Y$  using the specifications in the object  $H$ .

# dsp.SpectrumAnalyzer

---


**Purpose** Display frequency spectrum of time-domain signals

**Description** The SpectrumAnalyzer object displays the frequency spectrum of time-domain signals.

To display the spectra of signals in the Spectrum Analyzer:

- 1** Define and set up your Spectrum Analyzer. See “Construction” on page 5-986.
- 2** Call `step` to display the frequency spectrum of the signals in the Spectrum Analyzer figure. The behavior of `step` is specific to each object in the toolbox.

Use the MATLAB `clear` function to close the Spectrum Analyzer figure window and clear its associated data. Use the `hide` method to hide the Spectrum Analyzer window and the `show` method to make it visible.



See the following sections for more information on the Spectrum Analyzer Graphical User Interface:

- “Signal Display” on page 5-1000
- “Toolbar” on page 5-1006
- “Spectrum Settings” on page 5-1009
- “Measurements Panels” on page 5-1016
- “Visuals — Spectrum Options” on page 5-1022
- “Style Dialog Box” on page 5-1023
- “Tools — Plot Navigation Options” on page 5-1026

# dsp.SpectrumAnalyzer

---

## Construction

`H = dsp.SpectrumAnalyzer` creates a Spectrum Analyzer System object, `H`. This object displays the frequency spectrum of real- and complex-valued floating- and fixed-point signals.

`H = dsp.SpectrumAnalyzer('Name', Value, ...)` creates a Spectrum Analyzer System object, `H`, with each specified property *Name* set to the specified value. You can specify *Name–Value* arguments in any order.

## Properties

### CenterFrequency

Frequency over which span is centered

Specify as a real scalar the center frequency, in hertz, of the span over which the Spectrum Analyzer computes and plots the spectrum. This property applies when you set the `FrequencySpan` property to 'Span and center frequency'. The overall span, defined by the `Span` and `CenterFrequency` properties, must fall within the Nyquist frequency interval. When the `TwoSidedSpectrum` property is set to `true`, the interval is

$\left[ -\frac{SampleRate}{2}, \frac{SampleRate}{2} \right] + FrequencyOffset$  hertz. When the `TwoSidedSpectrum` property is set to `false`, the interval

is  $\left[ 0, \frac{SampleRate}{2} \right] + FrequencyOffset$  hertz.

This property is Tunable.

**Default:** 0

### FFTLength

FFT length

Specify as a positive, scalar integer the length of the FFT that Spectrum Analyzer uses to compute spectral estimates. This property applies only when you set the `FFTLengthSource` property to 'Property'.

This property is Tunable.

**Default:** 128

## FFTLengthSource

Source of the FFT length value

Specify the source of the FFT length value as one of 'Auto' or 'Property'.

- When you set this property to 'Auto', the Spectrum Analyzer sets the FFT length to the data segment length required to achieve the specified resolution bandwidth.
- When you set this property to 'Property', specify the number of FFT points using the FFTLength property.

This property is Tunable.

**Default:** 'Auto'

## FrequencyOffset

Frequency offset

Specify as a real, scalar value a frequency offset, in hertz. The *frequency*-axis values, which you also specify, are offset by the value specified in this property. The overall span must fall within the *Nyquist* frequency interval. When the TwoSidedSpectrum property is true, the Nyquist interval is

$\left[ -\frac{SampleRate}{2}, \frac{SampleRate}{2} \right] + FrequencyOffset$  hertz. When you set the TwoSidedSpectrum property to false, the Nyquist

interval is  $\left[ 0, \frac{SampleRate}{2} \right] + FrequencyOffset$  hertz. You can control the overall span in different ways based on how you set the FrequencySpan property.

**Default:** 0

## FrequencyScale

Frequency scale

Specify the frequency scale as either 'Linear' or 'Log'. When you set this property to 'Log', the Spectrum Analyzer displays the frequencies on the x-axis on a logarithmic scale. To use the 'Log' setting, you must also set the TwoSidedSpectrum property to false. When the TwoSidedSpectrum property is true, you must set this property to 'Linear'.

This property is Tunable.

**Default:** 'Linear'

## FrequencySpan

Frequency span mode

Specify the frequency span mode as one of 'Full', 'Span and center frequency', or 'Start and stop frequencies'.

- When you set this property to 'Full', the Spectrum Analyzer computes and plots the spectrum over the entire *Nyquist* frequency interval. When the TwoSidedSpectrum property is true, the Nyquist interval is

$\left[ -\frac{SampleRate}{2}, \frac{SampleRate}{2} \right] + FrequencyOffset$  hertz. If you set the TwoSidedSpectrum property to false, the Nyquist

interval is  $\left[ 0, \frac{SampleRate}{2} \right] + FrequencyOffset$  hertz.

- When you set this property to 'Span and center frequency', the Spectrum Analyzer computes and plots the spectrum over the interval specified by the Span and CenterFrequency properties.
- When you set this property to 'Start and stop frequencies', the Spectrum Analyzer computes and plots the

spectrum over the interval specified by the StartFrequency and StopFrequency properties.

This property is Tunable.

**Default:** 'Full'

## **Grid**

Option to enable or disable grid display

When you set this property to true, the grid appears. When you set this property to false, the grid does not appear.

This property is Tunable.

**Default:** false

## **LegendSource**

Source of legend

Specify the source of the legend as either None or Auto. When you set this property to 'None', the Spectrum Analyzer does not display a legend. When you set this property to 'Auto', the Spectrum Analyzer displays a legend with automatic string labels for each input channel.

This property is Tunable.

**Default:** 'None'

## **MaxHoldTrace**

Max-hold trace flag

Set this property to true to compute and plot the maximum-hold spectrum of each input channel. The maximum-hold spectrum at each frequency bin is computed by keeping the maximum value of all the power spectrum estimates. When you toggle this property, the Spectrum Analyzer resets its maximum-hold computations.

# dsp.SpectrumAnalyzer

---

This property is Tunable.

See also: `MinHoldTrace`, `NormalTrace`.

**Default:** `false`

## **MinHoldTrace**

Min-hold trace flag

Set this property to `true` to compute and plot the minimum-hold spectrum of each input channel. The minimum-hold spectrum at each frequency bin is computed by keeping the minimum value of all the power spectrum estimates. When you toggle this property, the Spectrum Analyzer resets its minimum-hold computations.

This property is Tunable.

See also: `MaxHoldTrace`, `NormalTrace`.

**Default:** `false`

## **Name**

Caption to display on Spectrum Analyzer window

Specify the caption to display on the Spectrum Analyzer window as any string.

This property is Tunable.

**Default:** `'Spectrum Analyzer'`

## **NormalTrace**

Normal trace flag

Set this property to `false` to remove the display of the normal traces. These traces display the free-running spectral estimates. Note that even when the traces are removed from the display, the Spectrum Analyzer continues its spectral computations.

This property is Tunable.

See also: MaxHoldTrace, MinHoldTrace.

**Default:** true

## Position

Spectrum Analyzer window position in pixels

Specify, in pixels, the size and location of the Spectrum Analyzer window as a 4-element double vector of the form, [left bottom width height]. You can place the Spectrum Analyzer window in a specific position on your screen by modifying the values for this property.

This property is Tunable.

**Default:** The default depends on your screen resolution. By default, the Spectrum Analyzer window appears in the center of your screen with a width of 410 pixels and height of 300 pixels.

## PowerUnits

Power units

Specify the units in which the Spectrum Analyzer displays power values as either 'dBm', 'dBW', or 'Watts'.

This property is Tunable.

**Default:** 'dBm'

## RBW

Resolution bandwidth

Specify as a real, positive scalar the resolution bandwidth (RBW), in hertz. RBW controls the spectral resolution of Spectrum Analyzer. This property applies only when you set the RBWSource property to 'Property'. You must specify a value to ensure that

there are at least two RBW intervals over the specified frequency span. Thus, the ratio of the overall span to RBW must be greater

than two:  $\frac{span}{RBW} > 2$ . You can specify the overall span in different ways based on how you set the FrequencySpan property.

This property is Tunable.

See also: RBWSource.

**Default:** 9.76

## **RBWSource**

Source of resolution bandwidth value

Specify the source of the resolution bandwidth (RBW) as either 'Auto' or 'Property'.

- When you set this property to 'Auto', the Spectrum Analyzer adjusts the spectral estimation resolution. This adjustment ensures that there are 1024 RBW intervals over the defined frequency span.
- When you set this property to 'Property', specify the resolution bandwidth directly when you set the RBW property.

This property is Tunable.

See also: RBW.

**Default:** 'Auto'

## **ReferenceLoad**

Reference load

Specify as a real, positive scalar the load, in ohms, that the Spectrum Analyzer uses as a reference to compute power values.

This property is Tunable.

**Default:** 1

## SampleRate

Sample rate of input

Specify the sampling rate, in hertz, of the input signals, as a finite numeric scalar.

**Default:** 10e3

## SidelobeAttenuation

Sidelobe attenuation of window

Specify as a real, positive scalar the window sidelobe attenuation, in decibels (dB). This property applies only when you set the Window property to 'Chebyshev' or 'Kaiser'.

This property is Tunable.

**Default:** 60

## Span

Frequency span over which spectrum is computed and plotted

Specify as a real, positive scalar the frequency span, in hertz, over which the Spectrum Analyzer computes and plots the spectrum. This property applies only when you set the FrequencySpan property to 'Span and center frequency'. The overall span, defined by this property and the CenterFrequency property, must fall within the *Nyquist* frequency interval. When the TwoSidedSpectrum property is true, the Nyquist interval is

$\left[ -\frac{SampleRate}{2}, \frac{SampleRate}{2} \right] + FrequencyOffset$  hertz. When you set the TwoSidedSpectrum property to false, the Nyquist

interval is  $\left[ 0, \frac{SampleRate}{2} \right] + FrequencyOffset$  hertz.

This property is Tunable.

See also: CenterFrequency, TwoSidedSpectrum.

**Default:** 10e3

## **SpectralAverages**

Number of spectral averages

Specify as a positive, scalar integer the number of spectral averages. The Spectrum Analyzer computes the current power spectrum estimate by averaging the last  $N$  power spectrum estimates. This property defines the number of spectral averages,  $N$ .

This property is Tunable.

**Default:** 10

## **SpectrumType**

Spectrum type

Specify the spectrum type as one of 'Power' or 'Power density'.

- When you set this property to 'Power', the Spectrum Analyzer shows the power spectrum.
- When you set this property to 'Power density', the Spectrum Analyzer shows the power spectral density. The power spectral density is the magnitude squared of the spectrum normalized to a bandwidth of 1 hertz.

This property is Tunable.

**Default:** 'Power'

## **StartFrequency**

Start frequency over which spectrum is computed

Specify as a real scalar the start frequency, in hertz, over which the Spectrum Analyzer computes and plots the spectrum. This property applies only when you set the `FrequencySpan` property to 'Start and stop frequencies'. The overall span, which is defined by `StopFrequency` and this property, must fall within the *Nyquist* frequency interval. When the `TwoSidedSpectrum` property is true, the Nyquist interval is

$\left[-\frac{SampleRate}{2}, \frac{SampleRate}{2}\right] + FrequencyOffset$  hertz. If you set the `TwoSidedSpectrum` property to false, the Nyquist interval

is  $\left[0, \frac{SampleRate}{2}\right] + FrequencyOffset$  hertz.

This property is Tunable.

See also: `StopFrequency`, `TwoSidedSpectrum`.

**Default:** -5e3

## StopFrequency

Stop frequency over which spectrum is computed

Specify as a real scalar the stop frequency, in hertz, over which the Spectrum Analyzer computes and plots the spectrum. This property applies only when you set the `FrequencySpan` property to 'Start and stop frequencies'. The overall span, defined by this property and the `StartFrequency` property, must fall within the *Nyquist* frequency interval. When the `TwoSidedSpectrum` property is set to true, the interval is

$\left[-\frac{SampleRate}{2}, \frac{SampleRate}{2}\right] + FrequencyOffset$  hertz. When the `TwoSidedSpectrum` property is set to false, the interval

is  $\left[0, \frac{SampleRate}{2}\right] + FrequencyOffset$  hertz.

This property is Tunable.

See also: StartFrequency, TwoSidedSpectrum.

**Default:** 5e3

## Title

Display title

Specify the display title as a string.

This property is Tunable.

**Default:** ''

## TwoSidedSpectrum

Two sided spectrum flag

Set this property to `true` to compute and plot two-sided spectral estimates. Set this property to `false` to compute and plot one-sided spectral estimates. If you set this property to `false`, then the input signal must be real valued. When the input signal is complex valued, you must set this property to `true`.

When this property is `false`, Spectrum Analyzer uses *power folding*. The *y*-axis values are twice the amplitude that they would be if this property were set to `true`, except at 0 and the Nyquist frequency. A one-sided PSD contains the total power of the signal in the frequency interval from DC to half of the Nyquist rate. For more information, see the `pwelch` function reference page.

**Default:** true

## Window

Window function

Specify a window function for the spectral estimator as one of the options in the following table. For information on any window

function, follow the link to the corresponding function reference in the Signal Processing Toolbox documentation.

Window Option	Corresponding Function in Signal Processing Toolbox
'Rectangular'	rectwin
'Chebyshev'	chebwin
'Flat Top'	flattopwin
'Hamming'	hamming
'Hann'	hann
'Kaiser'	kaiser

This property is Tunable.

**Default:** 'Hann'

## YLabel

The label for the *y*-axis

Specify as a string the *y*-axis label. Regardless of this property, Spectrum Analyzer always displays power units as one of 'dBm', 'dBW', 'Watts', 'dBm/Hz', 'dBW/Hz', 'Watts/Hz'.

This property is Tunable.

See also: PowerUnits.

**Default:** ''

## YLimits

The limits for the *y*-axis

Specify as a 2-element numeric vector the *y*-axis limits, [ymin, ymax]. The units directly depend upon the PowerUnits property.

This property is Tunable.

# dsp.SpectrumAnalyzer

---

**Default:** [-80, 20]

## Methods

clone	Create spectrum scope object with same property values
getNumInputs	Number of expected inputs to step method
getNumOutputs	Number of outputs of step method
hide	Hide Spectrum Analyzer window
isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
reset	Reset internal states of Spectrum Analyzer object
show	Make Spectrum Analyzer window visible
step	Display signal in Spectrum Analyzer figure

## Examples

View a two-sided power spectrum of a sine wave with noise on the Spectrum Analyzer.

```
hsin = dsp.SineWave('Frequency',100,'SampleRate',1000);
hsin.SamplesPerFrame = 1000;
hsa = dsp.SpectrumAnalyzer('SampleRate',hsin.SampleRate);
for ii = 1:250
    x = step(hsin) + 0.05*randn(1000,1);
    step(hsa, x);
end
```

Run the release method to automatically scale the axes.

```
release(hsa);
```

Run the MATLAB `clear` function to close the Spectrum Analyzer window.

```
clear('hsa');
```

View a one-sided power spectrum made from the sum of five real sine waves with different amplitudes and frequencies.

```
Fs = 100e6; % Sampling frequency  
fSz = 5000; % Frame size
```

```
hsin1 = dsp.SineWave(1e0, 5e6, 0, 'SamplesPerFrame', fSz, 'SampleRate', Fs);  
hsin2 = dsp.SineWave(1e-1, 15e6, 0, 'SamplesPerFrame', fSz, 'SampleRate', Fs);  
hsin3 = dsp.SineWave(1e-2, 25e6, 0, 'SamplesPerFrame', fSz, 'SampleRate', Fs);  
hsin4 = dsp.SineWave(1e-3, 35e6, 0, 'SamplesPerFrame', fSz, 'SampleRate', Fs);  
hsin5 = dsp.SineWave(1e-4, 45e6, 0, 'SamplesPerFrame', fSz, 'SampleRate', Fs);
```

```
hsb = dsp.SpectrumAnalyzer;  
hsb.SampleRate = Fs;  
hsb.SpectralAverages = 1;  
hsb.TwoSidedSpectrum = false;  
hsb.RBWSource = 'Auto';  
hsb.PowerUnits = 'dBW';  
hsb.Position = [749 227 976 721];  
for idx = 1:1e2  
    y1 = step(hsin1);  
    y2 = step(hsin2);  
    y3 = step(hsin3);  
    y4 = step(hsin4);  
    y5 = step(hsin5);  
    step(hsb, y1+y2+y3+y4+y5+0.0001*randn(fSz, 1));  
end
```

Run the `release` method to automatically scale the axes.

```
release(hsb);
```


# dsp.SpectrumAnalyzer

Run the MATLAB `clear` function to close the Spectrum Analyzer window.

```
clear('hsb');
```

## Signal Display

The Spectrum Analyzer indicates the spectrum computation settings that are represented in the current display. Check the **Resolution Bandwidth**, **Number of FFT Points**, **Frequency Span**, and **Center Frequency** indicators on the axes in the scope window for this information. These indicators relate to the **Minimum Frequency-Axis limit** and **Maximum Frequency-Axis limit** values on the *frequency*-axis of the scope window. The values specified by these indicators may be changed by modifying parameters in the **Spectrum Settings** panel. You can also view the object state and the amount of time data that correspond to the current display. Check the **Simulation Status** and **Simulation time** indicators on the status bar in the scope window for this information. The following figure highlights these aspects of the Spectrum Analyzer window.



- **Frequency Span** — The range of values shown on the *frequency*-axis on the Spectrum Analyzer window.

## Details

Spectrum Analyzer sets the frequency span using the values of parameters on the **Main options** pane of the **Spectrum Settings** panel.

- **Span (Hz) and CF (Hz) visible** — The **Frequency Span** value equals the **Span** parameter in the **Main options** pane. You can also get or set this value from the **Span** property when the **FrequencySpan** property is set to 'Span and Center Frequency'.
- **FStart (Hz) and FStop (Hz)** — The **Frequency Span** value equals the difference of the **FStop** and **FStart** parameters in the **Main options** pane, as given by the formula:  $f_{span} = f_{stop} - f_{start}$ . You can also get or set these values from the **StartFrequency** and **StopFrequency** properties when the **FrequencySpan** property is set to 'Start and stop frequencies'.

By default, the **Full Span** check box in the **Main options** pane is enabled, and its equivalent **FrequencySpan** property is set to 'Full'. In this case, the Spectrum Analyzer computes and plots the spectrum over the entire *Nyquist* frequency interval. When the **Two-sided spectrum** check box in the **Trace options** pane is enabled, and its equivalent **TwoSidedSpectrum** property is true, the Nyquist interval

is  $\left[ -\frac{SampleRate}{2}, \frac{SampleRate}{2} \right] + FrequencyOffset$  hertz. If you set the **TwoSidedSpectrum** property to false, the Nyquist interval

is  $\left[ 0, \frac{SampleRate}{2} \right] + FrequencyOffset$  hertz.


- **Resolution Bandwidth** — The smallest positive frequency that can be resolved.

## Details

Spectrum Analyzer sets the resolution bandwidth using the value of the **RBW** parameter on the **Main options** pane of the **Spectrum Settings** panel. You can also get or set this value from the RBW property when RBWSource is set to 'Property'. By default, the **RBW** parameter on the **Main options** pane and the related RBWSource property are set to 'Auto'. In this case, the Spectrum Analyzer determines the appropriate value to ensure that there are 1024 RBW intervals over the specified **Frequency Span**.

You can set the resolution bandwidth to whatever value you choose. For this reason, there is a minimum boundary on the number of input samples required to compute a spectral update. This number of input samples required to compute one spectral update is shown as **Samples/update** in the **Main options** pane. This value is directly

related to *RBW* by the following equation: 
$$N = \frac{0.2 \times NENBW \times F_s}{RBW}$$
. *NENBW* is the normalized effective noise bandwidth, a factor of the windowing method used, which is shown in the **Frequency Options** pane.  $F_s$  is the sample rate. In some cases, the number of samples provided in the input are not sufficient to achieve the resolution bandwidth that you specify. When this situation occurs, Spectrum Analyzer produces a message on the display, as shown in the following figure.



Spectrum Analyzer removes this message and displays a spectral estimate as soon as enough data has been input.

- **Number of FFT Points** — The Fast Fourier Transform (FFT) length.

## Details

Spectrum Analyzer sets the number of FFT points using the value of the **NFFT** parameter on the **Trace options** pane of the **Spectrum Settings** panel. You can also get or set this value from the **FFTLength** property when the **FFTLengthSource** property is set to 'Property'. By default, the **NFFT** parameter on the **Trace options** pane and the related **FFTLengthSource** property are set to 'Auto'. In this case, the Spectrum Analyzer sets the number of FFT points to the data segment length needed to achieve the specified **Resolution Bandwidth**.

- **Center Frequency** — The value shown at the middle point of the *frequency*-axis on the Spectrum Analyzer display.

## Details

Spectrum Analyzer sets the center frequency using the values of parameters on the **Main options** pane of the **Spectrum Settings** panel.

- **Span (Hz) and CF (Hz) visible** — The **Center Frequency** value equals the **CF** parameter in the **Main options** pane. You can also get or set this value from the `CenterFrequency` property when the `FrequencySpan` property is set to 'Span and Center Frequency'.
- **FStart (Hz) and FStop (Hz) visible** — The **Center Frequency** value equals half the sum of the **FStop** and **FStart** parameters in the **Main options** pane, as given by the

formula:  $f_{center} = \frac{f_{start} + f_{stop}}{2}$ . You can also get or set these values from the `StartFrequency` and `StopFrequency` properties when the `FrequencySpan` property is set to 'Start and stop frequencies'.

- **Minimum Frequency-Axis limit** — The value shown at the far-left side of the *frequency*-axis on the Spectrum Analyzer window. Spectrum Analyzer sets the minimum *frequency*-axis limit using the values of the parameters on the **Main options** pane of the **Spectrum Settings** panel.

## Details

- **Span (Hz) and CF (Hz) visible** — The **Minimum Frequency-Axis limit** value equals the difference between the center frequency and half the frequency span, as given by the

following formula:  $f_{min} = f_{center} - \frac{f_{span}}{2}$ . In this case, you can modify the minimum *frequency*-axis limit by changing the **Span** and **CF** parameters in the **Main options** pane. You can also get

or set these values from the `Span` and `CenterFrequency` properties when the `FrequencySpan` property is set to 'Span and Center Frequency'.

- `FStart` (Hz) and `FStop` (Hz) visible — The **Minimum Frequency-Axis limit** value equals the **FStart** parameter in the **Main options** pane. You can also get or set this value from the `StartFrequency` property when the `FrequencySpan` property is set to 'Start and stop frequencies'.
- **Maximum Frequency-Axis limit** — The value shown at the far-right side of the *frequency*-axis on the Spectrum Analyzer window. Spectrum Analyzer sets the maximum *frequency*-axis limit using the values of the parameters on the **Main options** pane of the **Spectrum Settings** panel.

## Details

- `Span` (Hz) and `CF` (Hz) visible — The **Maximum Frequency-Axis limit** value equals the sum of the center frequency and half the frequency span, as given by the following

formula:  $f_{max} = f_{center} + \frac{f_{span}}{2}$ . In this case, you can modify the maximum *frequency*-axis limit by changing the **Span** and **CF** parameters in the **Main options** pane. You can also get or set these values from the `Span` and `CenterFrequency` properties when the `FrequencySpan` property is set to 'Span and Center Frequency'.

- `FStart` (Hz) and `FStop` (Hz) visible — The **Maximum Frequency-Axis limit** value equals the **FStop** parameter in the **Main options** pane. You can also get or set this value from the `StopFrequency` property when the `FrequencySpan` property is set to 'Start and stop frequencies'.
- **Simulation Status** — Provides the current status of the model simulation.

## Details

The status can be one of the following conditions:

- **Processing** — Occurs after you construct the SpectrumAnalyzer object and before you run the `release` method.
- **Stopped** — Occurs after you run the `release` method.

The **Simulation Status** is part of the **Status Bar** in the Spectrum Analyzer window. You can choose to hide or display the entire **Status Bar**. From the Spectrum Analyzer menu, select **View > Status Bar**.

- **Simulation time** — The amount of time that has progressed since the Spectrum Analyzer System object was first constructed or reset.

## Details

Every time you call the `step` method, the simulation time increases by the number of rows in the input signal divided by the sample

rate, as given by the following formula:  $t_{sim} = t_{sim} + \frac{\text{length}(x)}{\text{SampleRate}}$ . At the beginning of a simulation, you can modify the **SampleRate** parameter on the **Main options** pane of the **Spectrum Settings** panel. You can also set the sample rate using the `SampleRate` property.

The **Simulation time** indicator is a component of the **Status Bar** in the Spectrum Analyzer window. You can choose to hide or display the entire **Status Bar**. From the Spectrum Analyzer menu, select **View > Status Bar**.

For more information, see “Spectrum Settings” on page 5-1009.

## Toolbar

The Spectrum Analyzer toolbar contains the following buttons.

## Print, Settings, and Properties Buttons

Button	Menu Location	Shortcut Keys	Description
	File > Print	Ctrl+P	<p>Print the current Spectrum Analyzer window. To enable printing, run the release method.</p> <p>To print the current scope window to a figure rather than sending it to your printer, select <b>File &gt; Print to figure</b>.</p>
	View > Spectrum Settings	N/A	<p>Open or close the <b>Spectrum Settings</b> panel. You can modify the settings in this panel to control the manner in which the spectrum is calculated.</p> <p>See the “Spectrum Settings” on page 5-1009 section for more information.</p>
	View > Properties	N/A	<p>Open the <b>Visuals — Spectrum Options</b> dialog box.</p> <p>See the “Visuals — Spectrum Options” on page 5-1022 section for more information.</p>

## Axes Control Buttons

	Tools > Zoom In	N/A	<p>When this tool is active, you can zoom in on the scope window. To do so, click in the center of your area of interest, or click and drag your cursor to draw</p>
---	-----------------	-----	---

# dsp.SpectrumAnalyzer

			a rectangular area of interest inside the scope window.
	<b>Tools &gt; Zoom X</b>	N/A	When this tool is active, you can zoom in on the <i>x</i> -axis. To do so, click inside the scope window, or click and drag your cursor along the <i>x</i> -axis over your area of interest.
	<b>Tools &gt; Zoom Y</b>	N/A	When this tool is active, you can zoom in on the <i>y</i> -axis. To do so, click inside the scope window, or click and drag your cursor along the <i>y</i> -axis over your area of interest.
	<b>Tools &gt; Scale Axes Limits</b>	<b>Ctrl+A</b>	<p>Click this button to scale the axes in the active scope window.</p> <p>Alternatively, you can enable automatic axes scaling by selecting one of the following options from the <b>Tools</b> menu:</p> <ul style="list-style-type: none"><li>• <b>Automatically Scale Axes Limits</b> — When you select this option, the scope scales the axes as needed during simulation.</li><li>• <b>Scale Axes Limits at Stop</b> — When you select this option, the scope scales the axes each time the simulation is stopped.</li></ul>

## Measurements Buttons

	<b>Tools &gt; Measurements &gt; Peak Finder</b>	N/A	<p>Open or close the <b>Peak Finder</b> panel. This panel displays maxima and the frequencies at which they occur, allowing the settings for peak threshold, maximum number of peaks, and peak excursion to be modified.</p> <p>See the “Peak Finder Panel” on page 5-1018 section for more information.</p>
---	---	-----	--

---

**Note** The zoom buttons do not change the settings related to span for Spectrum Analyzer. These buttons are purely graphical. Spectrum computations are not affected when you zoom.


---

You can control whether this toolbar appears in the Spectrum Analyzer window. From the Spectrum Analyzer menu, select **View > Toolbar**.

## Spectrum Settings

The **Spectrum Settings** panel appears at the right side of the Spectrum Analyzer figure. This panel enables you to modify settings to control the manner in which the spectrum is calculated. You can choose to hide or display the **Spectrum Settings** panel. In the Spectrum Analyzer menu, select **View > Spectrum Settings**. Alternatively, in the Spectrum Analyzer toolbar, select the Spectrum Settings  button.

# dsp.SpectrumAnalyzer



The **Spectrum Settings** panel is separated into three panes, labeled **Main Options**, **Trace Options**, and **Frequency Options**. You can expand each pane to see the available options.

## Main Options Pane

The **Main Options** pane enables you to modify the main options.

- **Sample rate (Hz)** — The sample rate, in hertz, of the input signals. This parameter is also known as sampling frequency.
- **Full span** — Enable this check box to have Spectrum Analyzer compute and plot the spectrum over the entire *Nyquist* frequency interval. By default, when the **Two-sided spectrum** check box is also enabled, the Nyquist interval is

$\left[ -\frac{SampleRate}{2}, \frac{SampleRate}{2} \right] + FrequencyOffset$  hertz. If you clear the **Two-sided spectrum** check box, the Nyquist interval

is  $\left[ 0, \frac{SampleRate}{2} \right] + FrequencyOffset$  hertz. Enabling this check box is equivalent to setting the `FrequencySpan` property to 'Full'.

- **Span (Hz)** and **CF (Hz)**, or **FStart (Hz)** and **FStop (Hz)** — When **Span (Hz)** is showing in the **Main Options** pane, you define the range of values shown on the *frequency*-axis on the Spectrum Analyzer window using frequency span and center frequency. From the drop-down list, select **FStart (Hz)** to define the range of *frequency*-axis values using start frequency and stop frequency instead.
  - **Span (Hz)** — The frequency span, in hertz. This parameter defines the range of values shown on the *frequency*-axis on the Spectrum Analyzer window. When this parameter is set to a numeric value, then it is equivalent to the Span property when the FrequencySpan property is set to 'Span and Center Frequency'.  
When this parameter is set to
  - **CF (Hz)** — The center frequency, in hertz. This parameter defines the value shown at the middle point of the *frequency*-axis on the Spectrum Analyzer window. This parameter is equivalent to the CenterFrequency property when the FrequencySpan property is set to 'Span and Center Frequency'.
  - **FStart (Hz)** — The start frequency, in hertz. This parameter defines the value shown at the leftmost side of the *frequency*-axis on the Spectrum Analyzer window. This parameter is equivalent to the StartFrequency property when the FrequencySpan property is set to 'Start and stop frequencies'.
  - **FStop (Hz)** — The stop frequency, in hertz. The parameter defines the value shown at the rightmost side of the *frequency*-axis on the Spectrum Analyzer window. This parameter is equivalent to the StopFrequency property when the FrequencySpan property is set to 'Start and stop frequencies'.
- **RBW (Hz)** — The resolution bandwidth, in hertz. This parameter defines the smallest positive frequency that can be resolved. By default, this parameter is set to Auto. In this case, the Spectrum Analyzer determines the appropriate value to ensure that there are 1024 *RBW* intervals over the specified **Frequency Span**. This case is equivalent to when you set the RBWSource property to 'Auto'.

# dsp.SpectrumAnalyzer


---

If you set this parameter to a numeric value, then you must specify a value that ensures there are at least two *RBW* intervals over the specified frequency span. In other words, the ratio of the overall

span to *RBW* must be at least two:  $\frac{\text{span}}{\text{RBW}} > 2$ . In this case, this parameter is equivalent to the `RBW` property, when `RBWSource` is set to 'Property'.

- **Samples/update** — The number of input samples required to compute one spectral update. This parameter is directly related to

*RBW* by the following equation:  $N = \frac{0.2 \times \text{NENBW} \times F_s}{\text{RBW}}$ . *NENBW* is the normalized effective noise bandwidth, a factor of the windowing method used, which is shown in the **Frequency Options** pane.  $F_s$  is the sample rate. If the number of samples provided in the input are not sufficient to achieve the resolution bandwidth that you specify, Spectrum Analyzer produces a message on the display as shown in the following figure.



## Trace Options Pane

The **Trace Options** pane enables you to modify the trace options.

- **Type** — The type of spectrum to display. Acceptable options are **Power** and **Power density**. When you set this parameter to **Power**, the Spectrum Analyzer shows the power spectrum. When you set this parameter to **Power density**, the Spectrum Analyzer shows the power spectral density. The power spectral density is the magnitude of the spectrum normalized to a bandwidth of 1 hertz. This parameter is equivalent to the `SpectrumType` property.
- **Units** — The units of the spectrum. Acceptable options are **dBm**, **dBW**, and **Watts**. This parameter is equivalent to the `PowerUnits` property.
- **Averages** — Specify as a positive, scalar integer the number of spectral averages. Spectrum Analyzer computes the current power spectrum estimate by averaging the last  $N$  power spectrum

estimates. This property defines the number of spectral averages,  $N$ . This parameter is equivalent to the `SpectralAverages` property.

- **NFFT** — The number of Fast Fourier Transform (FFT) points. This parameter defines the length of the FFT that Spectrum Analyzer uses to compute spectral estimates. Acceptable options are `Auto` or a positive, scalar integer. By default, when this parameter is set to `Auto`, Spectrum Analyzer sets the number of FFT points to the data segment length needed to achieve the resolution bandwidth you specified. This case is equivalent to when you set the `FFTLengthSource` property to `'Auto'`.

When this parameter is set to a positive integer, this parameter is equivalent to the `n` parameter that you can set when you run the MATLAB `fft` function. In this case, this parameter is also equivalent to `FFTLength` when you set `FFTLengthSource` to `'Property'`.

- **Ref. load** — The reference load, in ohms, used to scale the spectrum. Specify as a real, positive scalar the load, in ohms, that the Spectrum Analyzer uses as a reference to compute power values. This parameter is equivalent to the `ReferenceLoad` property.
- **Normal trace** — Normal trace view. By default, when this check box is enabled, Spectrum Analyzer calculates and plots the power spectrum or power spectrum density computed by the *Welch* estimator. The Welch estimator performs a smoothing operation by averaging a number of spectral estimates. To clear this check box, you must first select either the **Max hold trace** or the **Min hold trace** check box. This parameter is equivalent to the `NormalTrace` property.
- **Max hold trace** — Maximum hold trace view. Select this check box to enable Spectrum Analyzer to plot the maximum spectral values of all the estimates obtained. This parameter is equivalent to the `MaxHoldTrace` property.
- **Min hold trace** — Minimum hold trace view. Select this check box to enable Spectrum Analyzer to plot the minimum spectral values of all the estimates obtained. This parameter is equivalent to the `MinHoldTrace` property.

- **Two-sided spectrum** — Select this check box to enable two-sided spectrum view. In this view, both negative and positive frequencies are shown. If you clear this check box, Spectrum Analyzer shows a one-sided spectrum with only positive frequencies. Spectrum Analyzer requires that this parameter is selected when the input signal is complex-valued. This parameter is equivalent to the `TwoSidedSpectrum` property.

## Frequency Options Pane

The **Frequency Options** pane enables you to modify the frequency options.

- **Scale** — Linear or logarithmic scale. When the frequency span contains negative frequency values, Spectrum Analyzer disables the logarithmic option. This parameter is equivalent to the `FrequencyScale` property.
- **Offset** — The constant frequency offset to apply to the entire spectrum. This constant offset parameter is simply added to the values on the *frequency*-axis in the Spectrum Analyzer window. It is not used in any spectral computations. It does not affect any settings related to frequency span or resolution. This parameter is equivalent to the `FrequencyOffset` property.
- **Window** — The windowing method to apply to the spectrum. This parameter is equivalent to the `Window` property.

Windowing is used to control the effect of sidelobes in spectral estimation. For more information about windowing, see “Windows” in the Signal Processing Toolbox documentation.
- **Attenuation (dB)** — The sidelobe attenuation, in decibels (dB). This property applies only when you set the **Window** parameter to `Chebyshev` or `Kaiser`. This parameter is equivalent to the `SidelobeAttenuation` property.
- **NENBW** — Normalized Effective Noise Bandwidth of the window. This parameter is a measure of the noise performance of the window. It is the width of a rectangular filter that accumulates the same

# dsp.SpectrumAnalyzer

noise power with the same peak power gain. NENBW can be calculated from the windowing function using the following equation:

$$NENBW = \frac{\sum w^2(nT)}{n}.$$

The rectangular window has the smallest NENBW, with a value of 1. All other windows have a larger NENBW value. For example, the Hann window has an NENBW value of 1.5.

**Measurements Panels** The Measurements panels are the other two panels that appear to the right side of the Spectrum Analyzer figure. These panels are labeled **Trace selection** and **Peak finder**.

## Measurements Panel Buttons

Each of the Measurements panels contains the following buttons that enable you to modify the appearance of the current panel.


Button	Description
	Move the current panel to the top. When you are displaying more than one panel, this action moves the current panel above all the other panels.
	Collapse the current panel. When you first enable a panel, by default, it displays one or more of its panes. Click this button to hide all of its panes to conserve space. After you click this button, it becomes the expand button  .
	Expand the current panel. This button appears after you click the collapse button to hide the panes in the current panel. Click this button to display the panes in the current panel and show measurements again. After you click this button, it becomes the collapse button  again.

Button	Description
	Undock the current panel. This button lets you move the current panel into a separate window that can be relocated anywhere on your screen. After you click this button, it becomes the dock button  in the new window.
	Dock the current panel. This button appears only after you click the undock button. Click this button to put the current panel back into the right side of the Scope window. After you click this button, it becomes the undock button  again.
	Close the current panel. This button lets you remove the current panel from the right side of the Scope window.

Some panels have their measurements separated by category into a number of panes. Click the pane expand button  to show each pane that is hidden in the current panel. Click the pane collapse button  to hide each pane that is shown in the current panel.

## Trace Selection Panel


When you use the Scope to view multiple signals, the Trace Selection panel appears if you have more than one signal displayed and you click on any of the other Measurements panels. Choose the signal name for which you would like to display time domain measurements. See the following figure.



You can choose to hide or display the **Trace Selection** panel. In the Scope menu, select **Tools > Measurements > Trace Selection**.

## Peak Finder Panel

The **Peak Finder** panel displays maxima and the times at which they occur, allowing the settings for peak threshold, maximum number of peaks, and peak excursion to be modified. You can choose to hide or display the **Peak Finder** panel. In the Spectrum Analyzer menu, select **Tools > Measurements > Peak Finder**. Alternatively, in the Spectrum Analyzer toolbar, select the Peak Finder  button.




The **Peak finder** panel is separated into two panes, labeled **Settings** and **Peaks**. You can expand each pane to see the available options.

## Settings Pane

The **Settings** pane enables you to modify the parameters used to calculate the peak values within the displayed portion of the input signal. For more information on the algorithms this pane uses, see the Signal Processing Toolbox `findpeaks` function reference.

- **Peak Threshold** — The level above which peaks are detected. This setting is equivalent to the `MINPEAKHEIGHT` parameter, which you can set when you run the `findpeaks` function.
- **Max Num of Peaks** — The maximum number of peaks to show. This setting is equivalent to the `NPEAKS` parameter, which you can set when you run the `findpeaks` function.
- **Min Peaks Distance** — The minimum number of samples between adjacent peaks. This setting is equivalent to the `MINPEAKDISTANCE` parameter, which you can set when you run the `findpeaks` function.
- **Peak Excursion** — The minimum height difference between a peak and its neighboring samples. Peak excursion is illustrated alongside peak threshold in the following figure.



Whereas the peak threshold is a minimum value necessary for a sample value to be a peak, the peak excursion is the minimum difference between a peak sample and the samples to its left and right in the time domain. In the figure, the green vertical line illustrates the lesser of the two height differences between the labeled peak and its neighboring samples. This height difference must be greater than the **Peak Excursion** value for the labeled peak to be classified as a peak. Compare this setting to peak threshold, which is illustrated by the red horizontal line. The amplitude must be above this horizontal line for the labeled peak to be classified as a peak.

The peak excursion setting is equivalent to the `THRESHOLD` parameter, which you can set when you run the `findpeaks` function.

- **Label peaks** — When this check box is selected, the Peak Finder displays the calculated peak values directly on the plot. By default, this check box is cleared and no values are displayed on the plot.
- **Sort by order** — When this check box is selected, the Peak Finder puts the largest calculated peak values in frequency-sorted order. The Peak Finder displays the peak values in the **Peaks** pane. The number of peaks listed is still controlled by the **Max Num of Peaks** parameter. By default, this check box is cleared and the **Peak Finder** panel displays the largest calculated peak values in the **Peaks** pane in decreasing order of peak height.

## Peaks Pane

The **Peaks** pane displays all of the largest calculated peak values and the frequencies at which the peaks occur, using the parameters you define in the **Settings** pane. You set the **Max Num of Peaks** parameter to specify the number of peaks shown in the list. You set the order in which the peaks are listed using the **Sort by time** check box.

The numerical values displayed in the **Value** column are equivalent to the `pk`s output argument returned when you run the `findpeaks` function. The numerical values displayed in the **Frequency** column are similar to the `locs` output argument returned when you run the `findpeaks` function.


When you use the zoom options in the Spectrum Analyzer GUI, the peak locations automatically adjust to the frequency range shown in the display. In the Spectrum Analyzer toolbar, click the **Zoom In** or **Zoom X** button to make adjustments. If you constrict the *x*-axis range of the display, then the statistics shown reflect this frequency range. For example, if you zoom in on one peak, the **Peak Finder** panel displays information about only that particular peak.

## Visuals – Spectrum Options

The Visuals:Spectrum Options dialog box controls the visual configuration settings of the Spectrum Analyzer displays. From the Spectrum Analyzer menu, select **View > Properties** to open this dialog box. Alternatively, in the Spectrum Analyzer toolbar, click the properties  button.

### Display Pane

The **Display** pane of the Spectrum Analyzer — Visuals:Spectrum Options dialog box appears as follows.



#### Title

Specify the display title as a string. By default, the display has no title. Tunable.

#### Show legend

Select this check box to show the legend in the active display. The channel legend displays a name for each channel of each input signal. When the legend appears, you can place it anywhere inside of the scope window. To turn the legend off, clear the **Show legend** check box. Tunable.

You can edit the name of any channel in the legend. To do so, double-click the current name, and enter a new channel name. By default, the scope names each channel according to either its signal name or the name of the block from which it comes. If the signal has multiple channels, the scope uses an index number to identify each channel of that signal. For example, a 2-channel signal would have the following default names in the channel legend: Channel 1, Channel 2.

To change the appearance of any channel of any input signal in the Spectrum Analyzer window, from the Spectrum Analyzer menu, select **View > Style**.

### **Show grid**

When you select this check box, a grid appears in the active display of the Spectrum Analyzer GUI. To hide the grid, clear this check box. Tunable.

### **Minimum Y-limit**

Specify the minimum value of the  $y$ -axis. Tunable.

### **Maximum Y-limit**


Specify the maximum value of the  $y$ -axis. Tunable.

### **Y-axis label**

Specify the text for the scope to display to the left of the  $y$ -axis. Regardless of this property, Spectrum Analyzer always displays power units after this text as one of 'dBm', 'dBW', 'Watts', 'dBm/Hz', 'dBW/Hz', or 'Watts/Hz'. Tunable.

## **Style Dialog Box**

In the **Style** dialog box, you can customize the style of displays. You are able to change the color of the figure, the background and foreground colors of the axes, and properties of the lines. From the Spectrum Analyzer menu, select **View > Style** to open this dialog box.



## Properties

The **Style** dialog box allows you to modify the following properties of the Spectrum Analyzer GUI:

### Figure color

Specify the color that you want to apply to the background of the Spectrum Analyzer GUI. By default, the figure color is gray.

### Axes colors

Specify the color that you want to apply to the background of the axes for the display.

### Properties for line

Specify the channel for which you want to modify the visibility, line properties, and marker properties.

### Visible

Specify whether the selected signal on the display should be visible. If you clear this check box, the line disappears.

## Line

Specify the line style, line width, and line color for the selected signal on the display.

## Marker

Specify marks for the selected signal on the display to show at data points. This parameter is similar to the Marker property for the MATLAB Handle Graphics plot objects. You can choose any of the marker symbols from the following table.

Specifier	Marker Type
none	No marker (default)
○	Circle
□	Square
×	Cross
•	Point
+	Plus sign
*	Asterisk
◇	Diamond
▽	Downward-pointing triangle
△	Upward-pointing triangle
◁	Left-pointing triangle
▷	Right-pointing triangle

# dsp.SpectrumAnalyzer

Specifier	Marker Type
☆	Five-pointed star (pentagram)
✧	Six-pointed star (hexagram)

## Tools – Plot Navigation Options

The Tools:Plot Navigation Options dialog box allows you to automatically zoom in on and zoom out of your data. You can also scale the axes of the Spectrum Analyzer. In the Spectrum Analyzer menu, select **Tools > Axes Scaling Options** to open this dialog box.

### Parameters

The Tools:Plot Navigation Options dialog box appears as follows.

Parameters

Axes scaling:

Do not allow Y-axis limits to shrink

Y-axis

Data range (%):  Align:

Scale X-axis limits

Data range (%):  Align:

### Axis Scaling

Specify when the Scope should automatically scale the axes. You can select one of the following options:

- **Manual** — When you select this option, the Scope does not automatically scale the axes. You can manually scale the axes in any of the following ways:

- Select **Tools > Scale axes limits**.
- Press the **Scale Axes Limits** toolbar button.
- When the scope GUI is the active window, press **Ctrl+A**.
- **Auto** — When you select this option, the Scope scales the axes as needed, both during and after simulation. Selecting this option enables the **Do not allow Y-axis limits to shrink** check box. By default, this parameter is selected, and the Scope does not shrink the y-axis limits when scaling the axes.
- **Once at stop** — Selecting this option causes the Scope to scale the axes each time simulation is stopped. The Scope does not scale the axes during simulation.

This parameter is Tunable.

### **Do not allow Y-axis limits to shrink**

When you select this parameter, the y-axis limits are only allowed to grow during axes scaling operations. If you clear this check box, the y-axis limits may shrink during axes scaling operations.

This parameter appears only when you select **Auto** for the **Axis Scaling** parameter. When you set the **Axis Scaling** parameter to **Manual** or **Once at stop**, the y-axis limits are allowed to shrink. Tunable.

### **Y-axis Data range (%)**

Set the percentage of the y-axis that the Scope should use to display the data when scaling the axes. Valid values are between 1 and 100. For example, if you set this parameter to 100, the Scope scales the y-axis limits such that your data uses the entire y-axis range. If you then set this parameter to 30, the Scope increases the y-axis range such that your data uses only 30% of the y-axis range. Tunable.

### **Y-axis Align**

Specify where the Scope should align your data with respect to the y-axis when it scales the axes. You can select **Top**, **Center**, or **Bottom**. Tunable.

### **Scale X-axis limits**

Check this box to allow the Scope to scale the x-axis limits when it scales the axes. Tunable.

# dsp.SpectrumAnalyzer

---

## **X-axis Data range (%)**

Set the percentage of the  $x$ -axis that the Scope should use to display the data when scaling the axes. Valid values are between 1 and 100. For example, if you set this parameter to 100, the Scope scales the  $x$ -axis limits such that your data uses the entire  $x$ -axis range. If you then set this parameter to 30, the Scope increases the  $x$ -axis range such that your data uses only 30% of the  $x$ -axis range. Use the  $x$ -axis **Align** parameter to specify data placement with respect to the  $x$ -axis.

This parameter appears only when you select the **Scale X-axis limits** check box. Tunable.

## **X-axis Align**

Specify how the Scope should align your data with respect to the  $x$ -axis: Left, Center, or Right. This parameter appears only when you select the **Scale X-axis limits** check box. Tunable.

## **See Also**

`dsp.TimeScope`

**Purpose**

Create spectrum scope object with same property values

**Syntax**

```
C = clone(H)
```

**Description**

`C = clone(H)` creates a `SpectrumAnalyzer` object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with uninitialized states.

# **dsp.SpectrumAnalyzer.getNumInputs**

---

**Purpose**                    Number of expected inputs to step method

**Syntax**                    `N = getNumInputs(H)`

**Description**            `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method. *N* equals the value of the `NumInputPorts` property.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.SpectrumAnalyzer.getNumOutputs**

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method. The Spectrum Analyzer is a sink object, so `N` equals 0.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# **dsp.SpectrumAnalyzer.hide**

---

**Purpose** Hide Spectrum Analyzer window

**Syntax** `hide(H)`

**Description** `hide(H)` hides the Spectrum Analyzer window, associated with System object, H.

**See Also** `dsp.SpectrumAnalyzer` | `dsp.SpectrumAnalyzer.show`

<b>Purpose</b>	Locked status for input attributes and nontunable properties
<b>Syntax</b>	<code>isLocked(H)</code>
<b>Description</b>	<p><code>isLocked(H)</code> returns the locked state of the <code>SpectrumAnalyzer</code> object <code>H</code>.</p> <p>The <code>isLocked</code> method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the <code>step</code> method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the <code>isLocked</code> method returns a true value.</p>

# dsp.SpectrumAnalyzer.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections. This method lets you change any properties or input characteristics.

You should call the `release` method after calling the `step` method when there is no new data for the simulation. When you call the `release` method, the axes will automatically scale in the Spectrum Analyzer figure window. After calling the `release` method, any non-tunable properties can be set once again.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

**Algorithms** In operation, the `release` method is similar to the `mdlTerminate` function.

**See Also** `dsp.SpectrumAnalyzer` | `dsp.SpectrumAnalyzer.reset`

<b>Purpose</b>	Reset internal states of Spectrum Analyzer object
<b>Syntax</b>	<code>reset(H)</code>
<b>Description</b>	<p><code>reset(H)</code> sets the internal states of the <code>SpectrumAnalyzer</code> object <code>H</code> to their initial values.</p> <p>You should call the <code>reset</code> method after calling the <code>step</code> method when you want to clear the Spectrum Analyzer figure displays, prior to releasing system resources. This action enables you to start a simulation from the beginning. When you call the <code>reset</code> method, the displays will become blank again. In this sense, its functionality is similar to that of the MATLAB <code>clf</code> function. Do not call the <code>reset</code> method after calling the <code>release</code> method.</p>
<b>Algorithms</b>	In operation, the <code>reset</code> method is similar to a consecutive execution of the <code>mdlTerminate</code> function and the <code>mdlInitializeConditions</code> function.
<b>See Also</b>	<code>dsp.SpectrumAnalyzer</code>   <code>dsp.SpectrumAnalyzer.release</code>

# dsp.SpectrumAnalyzer.show

---

**Purpose**            Make Spectrum Analyzer window visible

**Syntax**            `show(H)`

**Description**        `show(H)` makes the Spectrum Analyzer window, associated with System object, H, visible.

**See Also**            `dsp.SpectrumAnalyzer` | `dsp.SpectrumAnalyzer.hide`

**Purpose** Display signal in Spectrum Analyzer figure

**Syntax** `step(H,X)`  
`step(H,X1,X2,...,XN)`

**Description** `step(H,X)` displays the signal, X, in the Spectrum Analyzer figure.  
`step(H,X1,X2,...,XN)` displays the signals X1, X2,...,XN in the Spectrum Analyzer figure when you set the `NumInputPorts` property to N. In this case, X1, X2,...,XN can have different data types and dimensions.

# dsp.StandardDeviation

---

**Purpose** Standard deviation of input or sequence of inputs

**Description** The StandardDeviation object computes the standard deviation for an input or sequence of inputs.

To compute the standard deviation for an input or sequence of inputs:

- 1** Define and set up your standard deviation object. See “Construction” on page 5-1038.
- 2** Call `step` to compute the standard deviation according to the properties of `dsp.StandardDeviation`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.StandardDeviation` returns a standard deviation System object, `H`, that computes the standard deviation for the columns of input.

`H = dsp.StandardDeviation('PropertyName',PropertyValue,...)` returns a standard deviation System object, `H`, with each specified property set to the specified value.

## Properties

### RunningStandardDeviation

Enable calculation over successive calls to the `step` method

Set this property to `true` to enable the calculation of standard deviation over successive calls to the `step` method. The default is `false`.

### ResetInputPort

Enable resetting in running standard deviation mode

Set this property to `true` to enable resetting for the running standard deviation. When the property is set to `true`, you must specify a reset input to the `step` method to reset the running standard deviation. This property applies only when you set the `RunningStandardDeviation` property to `true`. The default is `false`.

### ResetCondition

Reset condition for running standard deviation mode

Specify event to reset the running standard deviation as one of | Rising edge | Falling edge | Either edge | Non-zero |. This property applies only when you set the ResetInputPort property to true. The default is Non-zero.

## **Dimension**

Dimension to operate along

Specify how the standard deviation calculation is performed over the data as one of | All | Row | Column | Custom |. This property applies only when you set the RunningStandardDeviation property to false. The default is Column.

## **CustomDimension**

Numerical dimension to operate along

Specify the dimension (one-based value) of the input signal, over which the object computes the standard deviation. The cannot exceed the number of dimensions for the input signal. This property applies when you set the Dimension property to Custom. The default is 1.

## **ROIProcessing**

ROIProcessing

Enable region of interest processing

Set this property to true to enable calculating the standard deviation within a particular region for each image. This property applies only when you set the RunningStandardDeviation property to false and the Dimension property is All. The default is false.

Full ROI processing support requires a Computer Vision System Toolbox license. With only the DSP System Toolbox license, Rectangles is the only selection that applies for the ROIForm property.

# dsp.StandardDeviation

---

## **ROIForm**

Type of region of interest

Specify the type of region of interest as one of | `Rectangles` | `Lines` | `Label matrix` | `Binary mask` |. This property applies only when you set the `ROIProcessing` property to `true`. The default is `Rectangles`.

Full ROI processing support requires a Computer Vision System Toolbox license. With only the DSP System Toolbox license, `Rectangles` is the only selection that applies for the `ROIForm` property.

## **ROIPortion**

Calculate over entire ROI or just perimeter

Specify the region over which to calculate the standard deviation as one of | `Entire ROI` | `ROI perimeter` |. This property applies if the `ROIForm` property is `Rectangles`. The default is `Entire ROI`.

## **ROIStatistics**

Statistics for each ROI, or one for all ROIs

Specify what statistics to calculate as one of | `Individual statistics for each ROI` | `Single statistic for all ROIs` |. This property applies when you set the `ROIForm` property to `Rectangles`, `Lines`, or `Label matrix`. The default is `Individual statistics for each ROI`.

## **ValidityOutputPort**

Enable output of validity check of ROI or label numbers

Indicate whether to return the validity of the specified ROI being completely inside image when the `ROIForm` property is `Lines`, `Rectangles` or `Binary mask`. Indicate whether to return the validity of the specified label numbers when the `ROIForm` property is `Label Matrix`. This property applies when you set the `ROIForm` property to anything except `Binary Mask`. The default is `false`.

## FrameBasedProcessing

Enable frame-based processing

Set this property to `true` to enable frame-based processing. Set this property to `false` to enable sample-based processing. This property applies only when you set the `RunningStandardDeviation` property to `true`. The default is `true`.

## Methods

<code>clone</code>	Create standard deviation object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>reset</code>	Reset states for running standard deviation computation
<code>step</code>	Calculate standard deviation of input

## Examples

Compute running standard deviation of a signal:

```
hstd2 = dsp.StandardDeviation;  
hstd2.RunningStandardDeviation = true;  
x = randn(100,1);  
y = step(hstd2,x);  
% y(i) is the standard deviation of all values  
% in the vector x(1:i)
```

# dsp.StandardDeviation

---

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Standard Deviation block reference page. The object properties correspond to the block parameters, except:

- The **Reset port** block parameter corresponds to the `ResetInputPort` and `ResetCondition` object properties.
- **Treat sample-based row input as a column** block parameter is not supported by the `dsp.StandardDeviation` object.

Both this object and its corresponding block let you specify whether to process inputs as individual samples or as frames of data. The object uses the `FrameBasedProcessing` property. The block uses the **Input processing** parameter. See “Set the `FrameBasedProcessing` Property of a System object” for more information.

## See Also

`dsp.Variance` | `dsp.Maximum` | `dsp.Minimum` | `dsp.Mean`

**Purpose** Create standard deviation object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a `StandardDeviation` object `C`, with the same property values as `H`. The clone method creates a new unlocked object with uninitialized states.

# **dsp.StandardDeviation.getNumInputs**

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**      `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.StandardDeviation.getNumOutputs**

---

**Purpose**

Number of outputs of step method

**Syntax**

`N = getNumOutputs(H)`

**Description**

`N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# **dsp.StandardDeviation.isLocked**

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `StandardDeviation` object `H`.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

# **dsp.StandardDeviation.reset**

---

**Purpose**            Reset states for running standard deviation computation

**Syntax**            `reset(H)`

**Description**        `reset(H)` sets the internal states of the `StandardDeviation` object `H` to their initial values when computing the running standard deviation.

**Purpose** Calculate standard deviation of input

**Syntax**

```
Y = step(H,X)
Y = step(H,X,R)
Y = step(H,X,ROI)
Y = step(H,X,LABEL,LABELNUMBERS)
[Y, FLAG] = step(H,X,ROI)
[Y, FLAG] = step(H,X,LABEL,LABELNUMBERS)
```

**Description**

`Y = step(H,X)` computes the standard deviation, `Y`, of input `X`. The object computes the standard deviation over successive calls to the `step` method when the `RunningStandardDeviation` property is true.

`Y = step(H,X,R)` resets its state based on the value of reset signal `R` and the `ResetCondition` property. You can use this option only when the `RunningStandardDeviation` property is true.

`Y = step(H,X,ROI)` uses additional input `ROI` as the region of interest when the `ROIProcessing` property is set to true and the `ROIForm` property is set to `Lines`, `Rectangles` or `Binary mask`.

`Y = step(H,X,LABEL,LABELNUMBERS)` computes the standard deviation of input image `X` for region labels contained in vector `LABELNUMBERS`, with matrix `LABEL` marking pixels of different regions. This option is available when the `ROIProcessing` property is set to true and the `ROIForm` property is set to `Label matrix`.

`[Y, FLAG] = step(H,X,ROI)` returns `FLAG` which indicates whether the given region of interest is within the image bounds when the `ValidityOutputPort` property is true.

`[Y, FLAG] = step(H,X,LABEL,LABELNUMBERS)` returns `FLAG` which indicates whether the input label numbers are valid when the `ValidityOutputPort` property is true.

## **dsp.StandardDeviation.step**

---

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

<b>Purpose</b>	State-level estimation for bilevel rectangular waveform
<b>Description</b>	<p>The StateLevels object estimates the state levels of a bilevel rectangular waveform.</p> <p>To estimate the state levels of a bilevel waveform:</p> <ol style="list-style-type: none"><li>1 Define and set up your state-level estimation. See “Construction” on page 5-1051.</li><li>2 Call <code>step</code> to estimate the state levels for an input vector according to the properties of <code>dsp.StateLevels</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.StateLevels</code> creates a state-level estimation System object, <code>H</code>, that estimates state levels in a bilevel rectangular waveform using the histogram method with 100 bins.</p> <p><code>H = dsp.StateLevels('PropertyName',PropertyVaLue,...)</code> returns an StateLevels System object, <code>H</code>, with each specified property set to the specified value.</p>
<b>Properties</b>	<p><b>HistogramBounds</b></p> <p>Minimum and maximum levels of the histogram. Specify the range of the histogram as a 2-element real-valued row vector. Signal values outside the range defined by this property are ignored. This property applies when you set the Method property to 'Histogram mode' or 'Histogram mean', and either RunningStateLevels is true, or the HistogramBoundsSource property is set to 'Property'.</p> <p><b>Default:</b> [0 5]</p> <p><b>HistogramBoundsSource</b></p> <p>Source of histogram bounds. Specify how to determine the histogram bounds as one of 'Auto' or 'Property'. When you set this property to 'Auto', the histogram bounds are determined by</p>

# dsp.StateLevels

---

the minimum and maximum input values. When you set this property to 'Property', the histogram bounds are determined by the value of the HistogramBounds property. This property applies when you set the Method property to 'Histogram mode' or 'Histogram mean', and the RunningStateLevels property is false.

**Default:** 'Auto'

## **HistogramNumBins**

Number of bins in the histogram. Specify the number of bins in the histogram. This property applies when you set the Method property to 'Histogram mode' or 'Histogram mean'.

**Default:** 100

## **HistogramOutputPort**

Enable histogram output. Set this property to true to output the histogram used in the computation of the state levels. This property applies when you set the Method property to 'Histogram mode' or 'Histogram mean'.

**Default:** false

## **Method**

Algorithm used to compute state levels. Specify the method used to compute state levels as one of 'Histogram mean', 'Histogram mode', or 'Peak to peak'.

**Default:** 'Histogram mode'

## **RunningStateLevels**

Calculation over successive calls to step. Set this property to true to enable computation of the state levels over successive calls to the step. Otherwise, compute the state levels of the current

input. When you set the `RunningStateLevels` property to `false` and you are using a histogram to compute your state levels, you must set the `HistogramBoundsSource` property to `'Property'`.

## Methods

<code>clone</code>	Clones the current instance of the state levels object
<code>getNumInputs</code>	Number of expected inputs to the method
<code>getNumOutputs</code>	Number of outputs of the method
<code>isLocked</code>	Locked status (logical) for input attributes and nontunable properties
<code>plot</code>	Plot signal, state levels, and histogram
<code>release</code>	Allow property value and input characteristics changes
<code>reset</code>	Reset internal states of state levels object
<code>step</code>	Estimate state levels for bilevel rectangular waveform

## Definitions

### State

A particular level, which can be associated with an upper and lower state boundary. States are ordered from the most negative to the most positive. In a bilevel waveform, the most negative state is the low state. The most positive state is the high state.

### State-Level Tolerances

Each state level can have associated lower- and upper-state boundaries. These state boundaries are defined as the state level plus or minus a scalar multiple of the difference between the high state and low state.

## dsp.StateLevels


---

To provide a useful tolerance region, the scalar is typically a small number such as 2/100 or 3/100. In general, the  $\alpha\%$  tolerance region for the low state is defined as

$$S_1 \pm \frac{\alpha}{100}(S_2 - S_1)$$

where  $S_1$  is the low-state level and  $S_2$  is the high-state level. Replace the first term in the equation with  $S_2$  to obtain the  $\alpha\%$  tolerance region for the high state.

The following figure illustrates lower and upper 2% state boundaries (tolerance regions) for a positive-polarity bilevel waveform. The estimated state levels are indicated by a dashed red line.



**Examples**

**State Levels of 2.3 V Underdamped Noisy Clock**

Compute and plot the state levels of a 2.3 V underdamped noisy clock.

# dsp.StateLevels

---

Load the clock data in the variable, *x*, and the sampling instants in the variable, *t*.

```
load('clockex.mat', 'x', 't');
```

Estimate the state levels.

```
h = dsp.StateLevels;  
levels = step(h, x);
```

Plot the clock data along with the estimated state levels and histograms.

```
plot(h)
```

## Algorithms

The StateLevels System object uses the histogram method to estimate the states of a bilevel waveform. The histogram method is described in [1]. To summarize the method:

- 1 Determine the maximum and minimum amplitudes and amplitude range of the data.
- 2 For the specified number of histogram bins, determine the bin width as the ratio of the amplitude range to the number of bins.
- 3 Sort the data values into the histogram bins.
- 4 Identify the lowest-indexed histogram bin,  $i_{low}$ , and highest-indexed histogram bin,  $i_{high}$ , with nonzero counts.
- 5 Divide the histogram into two subhistograms. The lower-histogram bins are  $i_{low} \leq i \leq 1/2(i_{high} - i_{low})$ .

The upper-histogram bins are  $i_{low} + 1/2(i_{high} - i_{low}) \leq i \leq i_{high}$ .

- 6 Compute the state levels by determining the mode or mean of the lower and upper histograms.

## References

- [1] *IEEE Standard on Transitions, Pulses, and Related Waveforms*, IEEE Standard 181, 2003, pp. 15–17.

**See Also**      [dsp.TransitionMetrics](#) | [dsp.PulseMetrics](#) |

# **dsp.StateLevels.clone**

---

**Purpose** Clones the current instance of the state levels object

**Syntax** `clone(H)`

**Description** `clone(H)` clones the current instance of the state levels object H.

**Purpose** Number of expected inputs to the step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the step method for the state levels object `H`.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.StateLevels.getNumOutputs**

---

**Purpose**            Number of outputs of the `step` method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status (logical) for input attributes and nontunable properties

**Syntax** isLocked(H)

**Description** isLocked(H) returns the locked state of the state levels object.

The isLocked method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the step method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the isLocked method returns a true value.

# **dsp.StateLevels.plot**

---

**Purpose** Plot signal, state levels, and histogram

**Syntax** `plot(H)`

**Description** `plot(H)` plots the signal and state levels computed in the last call to the `step` method. If the `Method` property of the state levels object is set to `'Histogram mode'` or `'Histogram Mean'`, the histogram is plotted in a subplot below the signal.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

## **dsp.StateLevels.reset**

---

<b>Purpose</b>	Reset internal states of state levels object
<b>Syntax</b>	<code>reset(H)</code>
<b>Description</b>	<code>reset(H)</code> resets the state levels object, H, to clear information accumulated from previous calls to <code>step</code> .

**Purpose** Estimate state levels for bilevel rectangular waveform

**Syntax** LEVELS = step(H,X)  
[LEVELS,HISTOGRAM] = step(H,X)

**Description** LEVELS = step(H,X) returns a 2-element row vector, LEVELS, containing the estimated state levels for X. X is a real-valued column vector.

[LEVELS,HISTOGRAM] = step(H,X) returns a double-precision column vector, HISTOGRAM, containing the histogram of the sample values in X. You can obtain this output only when you set the Method property to either 'Histogram mean' or 'Histogram mode', and you set the HistogramOutputPort property to true.

# dsp.SubbandAnalysisFilter

---

**Purpose** Decompose signal into high-frequency and low-frequency subbands

**Description** The SubbandAnalysisFilter object decomposes a signal into high-frequency and low-frequency subbands.

To decompose a signal into high-frequency and low-frequency subbands:

- 1 Define and set up your two-channel subband analysis filter. See “Construction” on page 5-1066.
- 2 Call `step` to decompose the signal according to the properties of `dsp.SubbandAnalysisFilter`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.SubbandAnalysisFilter` returns a two-channel subband analysis filter, `H`, that decomposes the input signal into a high-frequency subband and a low-frequency subband, each with half the bandwidth of the input.

`H = dsp.SubbandAnalysisFilter('PropertyName',PropertyValue,...)` returns a two-channel subband analysis filter, `H`, with each specified property set to the specified value.

`H = dsp.SubbandAnalysisFilter(lpc,hpc,'PropertyName',PropertyValue,...)` returns a two-channel subband analysis filter, `H`, with the `LowpassCoefficients` property set to `lpc`, the `HighpassCoefficients` property set to `hpc`, and other specified properties set to the specified values.

**Properties** **LowpassCoefficients**

Lowpass FIR filter coefficients

Specify a vector of lowpass FIR filter coefficients, in descending powers of  $z$ . For the lowpass filter, use a half-band filter that passes the frequency band stopped by the filter specified in the `HighpassCoefficients` property. The default values of

this property specify a filter based on a third-order Daubechies wavelet.

## **HighpassCoefficients**

Highpass FIR filter coefficient

Specify a vector of highpass FIR filter coefficients, in descending powers of  $z$ . For the highpass filter, use a half-band filter that passes the frequency band stopped by the filter specified in the `LowpassCoefficients` property. The default values of this property specify a filter based on a third-order Daubechies wavelet.

## **Fixed-Point Properties**

### **FullPrecisionOverride**

Full precision override for fixed-point arithmetic

Specify whether to use full precision rules. If you set `FullPrecisionOverride` to `true`, which is the default, the object computes all internal arithmetic and output data types using full precision rules. These rules provide the most accurate fixed-point numerics. It also turns off the display of other fixed-point properties because they do not apply individually. These rules guarantee that no quantization occurs within the object. Bits are added, as needed, to ensure that no roundoff or overflow occurs. If you set `FullPrecisionOverride` to `false`, fixed-point data types are controlled through individual fixed-point property settings. For more information, see “Full Precision for Fixed-Point System Objects”.

### **RoundingMethod**

Rounding method for fixed-point operations

Specify the rounding method as one of | `Ceiling` | `Convergent` | `Floor` | `Nearest` | `Round` | `Simplest` | `Zero` |. The default is `Floor`. This property applies only if the object is not in full precision mode.

# dsp.SubbandAnalysisFilter

---

## **OverflowAction**

Action to take when integer input is out of range

Specify the overflow action as one of | Wrap | Saturate |. The default is Wrap. This property applies only if the object is not in full precision mode.

## **CoefficientsDataType**

Data type of the coefficients

Specify the FIR filter coefficients fixed-point data type as one of | Same word length as input | Custom |. The default is Same word length as input.

## **CustomCoefficientsDataType**

Coefficients word and fraction lengths

Specify the FIR filter coefficients fixed-point type as a `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `CoefficientsDataType` property to `Custom`. The default is `numericType([],16,15)`.

## **ProductDataType**

Data type of product

Specify the product data type as one of | Full precision | Same as input | Custom |. The default is Full precision.

## **CustomProductDataType**

Product word and fraction lengths

Specify the product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `ProductDataType` property to `Custom`. The default is `numericType([],32,30)`.

## **AccumulatorDataType**

Data type of accumulator

Specify the accumulator data type as one of `Full precision` | `Same as input` | `Same as product` | `Custom` |. The default is `Full precision`.

## **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `AccumulatorDataType` property to `Custom`. The default is `numericType([],32,30)`.

## **OutputDataType**

Data type of output

Specify the output data type as one of `Same as accumulator` | `Same as product` | `Same as input` | `Custom` |. The default is `Same as accumulator`.

## **CustomOutputDataType**

Output word and fraction lengths

Specify the output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `OutputDataType` property to `Custom`. The default is `numericType([],16,14)`.

## **Methods**

<code>clone</code>	Create subband analysis filter object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties

# dsp.SubbandAnalysisFilter

---

release	Allow property value and input characteristics changes
reset	Reset filter states of subband analysis filter object
step	Decompose signal into high- and low-frequency subbands

## Examples

Perfectly reconstruct a signal using subband analysis and synthesis filters:

```
load dspwlets; % load the filter coefficients lod, hid, lor and hir
ha = dsp.SubbandAnalysisFilter(lod, hid);
hs = dsp.SubbandSynthesisFilter(lor, hir);
u = randn(128,1);

[hi, lo] = step(ha, u); % Two channel analysis
y = step(hs, hi, lo); % Two channel synthesis

% Plot difference between original and reconstructed signals
% with filter latency compensated
plot(u(1:end-7)-y(8:end));
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Two-Channel Analysis Subband Filter block reference page. The object properties correspond to the block parameters, except:

- The `SubbandAnalysisFilter` object does not have a property that corresponds to the **Input processing** parameter of the Two-Channel Analysis Subband Filter block. The object assumes the input is frame based and always maintains the input frame rate.
- The **Rate options** block parameter is not supported by the `dsp.SubbandAnalysisFilter` object.

## See Also

`dsp.SubbandSynthesisFilter` | `dsp.DyadicAnalysisFilterBank`

**Purpose** Create subband analysis filter object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` create a `SubbandAnalysisFilter` object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with uninitialized states.

# dsp.SubbandAnalysisFilter.getNumInputs

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.SubbandAnalysisFilter.getNumOutputs**

---

## **Purpose**

Number of outputs of step method

## **Syntax**

`N = getNumOutputs(H)`

## **Description**

`N = getNumOutputs(H)` returns the number of output from the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# **dsp.SubbandAnalysisFilter.isLocked**

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `SubbandAnalysisFilter` object `H`.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

# **dsp.SubbandAnalysisFilter.reset**

---

<b>Purpose</b>	Reset filter states of subband analysis filter object
<b>Syntax</b>	<code>reset(H)</code>
<b>Description</b>	<code>reset(H)</code> sets the filter states of the <code>SubbandAnalysisFilter</code> object <code>H</code> to 0.

**Purpose** Decompose signal into high- and low-frequency subbands

**Syntax** [HI,L0] = step(H,SIG)

**Description** [HI,L0] = step(H,SIG) decomposes the input signal, SIG, into a high-frequency subband, HI, and a low-frequency subband, L0.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.SubbandSynthesisFilter

---

**Purpose** Reconstruct signal from high-frequency and low-frequency subbands

**Description** The `SubbandSynthesisFilter` object reconstructs a signal from high-frequency and low-frequency subbands.

To reconstruct a signal from high-frequency and low-frequency subbands:

- 1 Define and set up your two-channel subband synthesis filter. See “Construction” on page 5-1078.
- 2 Call `step` to reconstruct the signal according to the properties of `dsp.SubbandSynthesisFilter`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.SubbandSynthesisFilter` returns a two-channel subband synthesis filter, `H`, that reconstructs a signal from its high-frequency subband and low-frequency subband. Each subband contains half the bandwidth of the original signal.

`H = dsp.SubbandSynthesisFilter('PropertyName',PropertyValue,...)` returns a two-channel subband synthesis filter, `H`, with each specified property set to the specified value.

`H = dsp.SubbandSynthesisFilter(lpc,hpc,'PropertyName',PropertyValue,...)` returns a two-channel subband synthesis filter, `H`. The object has the `LowpassCoefficients` property set to `lpc`, the `HighpassCoefficients` property set to `hpc`, and other specified properties set to the specified values.

**Properties** **LowpassCoefficients**

Lowpass FIR filter coefficients

Specify a vector of lowpass FIR filter coefficients, in descending powers of  $z$ . For the lowpass filter, use a half-band filter that passes the frequency band stopped by the filter specified in the `HighpassCoefficients` property. The default values of

this property specify a filter based on a third-order Daubechies wavelet.

## **HighpassCoefficients**

Highpass FIR filter coefficients

Specify a vector of highpass FIR filter coefficients, in descending powers of  $z$ . For the highpass filter, use a half-band filter that passes the frequency band stopped by the filter specified in the `LowpassCoefficients` property. The default values of this property specify a filter based on a third-order Daubechies wavelet.

## **Fixed-Point Properties**

### **FullPrecisionOverride**

Full precision override for fixed-point arithmetic

Specify whether to use full precision rules. If you set `FullPrecisionOverride` to `true`, which is the default, the object computes all internal arithmetic and output data types using full precision rules. These rules provide the most accurate fixed-point numerics. It also turns off the display of other fixed-point properties because they do not apply individually. These rules guarantee that no quantization occurs within the object. Bits are added, as needed, to ensure that no roundoff or overflow occurs. If you set `FullPrecisionOverride` to `false`, fixed-point data types are controlled through individual fixed-point property settings. For more information, see “Full Precision for Fixed-Point System Objects”.

### **RoundingMethod**

Rounding method for fixed-point operations

Specify the rounding method as one of | `Ceiling` | `Convergent` | `Floor` | `Nearest` | `Round` | `Simplest` | `Zero` |. The default is `Floor`. This property applies only if the object is not in full precision mode.

# dsp.SubbandSynthesisFilter

---

## **OverflowAction**

Action to take when integer input is out of range

Specify the overflow action as one of | Wrap | Saturate |. The default is Wrap. This property applies only if the object is not in full precision mode.

## **CoefficientsDataType**

Data type of the coefficients

Specify the FIR filter coefficients fixed-point data type as one of | Same word length as input | Custom |. The default is Same word length as input.

## **CustomCoefficientsDataType**

Coefficient word and fraction lengths

Specify the FIR filter coefficients fixed-point type as a `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `CoefficientsDataType` property to `Custom`. The default is `numericType([],16,15)`.

## **ProductDataType**

Data type of product

Specify the product data type as one of | Full precision | Same as input | Custom |. The default is Full precision.

## **CustomProductDataType**

Product word and fraction lengths

Specify the product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `ProductDataType` property to `Custom`. The default is `numericType([],32,30)`.

## **AccumulatorDataType**

Data type of accumulator

Specify the accumulator data type as one of | Full precision | Same as input | Same as product | Custom |. The default is Full precision.

## **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `AccumulatorDataType` property to `Custom`. The default is `numericType([],32,30)`.

## **OutputDataType**

Data type of output

Specify the output data type as one of | Same as accumulator | Same as product | Same as input | Custom |. The default is Same as accumulator.

## **CustomOutputDataType**

Output word and fraction lengths

Specify the output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `OutputDataType` property to `Custom`. The default is `numericType([],16,14)`.

## **Methods**

<code>clone</code>	Create subband synthesis filter object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties

# dsp.SubbandSynthesisFilter

---

release	Allow property value and input characteristics changes
reset	Reset internal states of subband synthesis filter object
step	Reconstruct signal from high- and low-frequency subbands

## Examples

Perfectly reconstruct a signal using subband analysis and synthesis filters:

```
load dspwlets; % Load filter coefficients lod,
               % hid, lor and hir
ha = dsp.SubbandAnalysisFilter(lod, hid);
hs = dsp.SubbandSynthesisFilter(lor, hir);
u = randn(128,1);

[hi, lo] = step(ha, u); % Two channel analysis
y = step(hs, hi, lo); % Two channel synthesis

% Plot difference between original and reconstructed
% signals with filter latency compensated
plot(u(1:end-7)-y(8:end));
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Two-Channel Synthesis Subband Filter block reference page. The object properties correspond to the block parameters, except:

- The `SubbandSynthesisFilter` object does not have a property that corresponds to the **Input processing** parameter of the Two-Channel Synthesis Subband Filter block. The object only performs sample-based processing and always maintains the input frame rate.
- The **Rate options** block parameter is not supported by the `SubbandSynthesisFilter` object.

## **See Also**

`dsp.SubbandAnalysisFilter` | `dsp.DyadicSynthesisFilterBank`

# **dsp.SubbandSynthesisFilter.clone**

---

**Purpose** Create subband synthesis filter object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a `SubbandSynthesisFilter` object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with uninitialized states.

# dsp.SubbandSynthesisFilter.getNumInputs

---

**Purpose** Number of expected inputs to step method

**Syntax** N = getNumInputs(H)

**Description** N = getNumInputs(H) returns the number of expected inputs, N, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.SubbandSynthesisFilter.getNumOutputs**

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# **dsp.SubbandSynthesisFilter.isLocked**

---

**Purpose**

Locked status for input attributes and nontunable properties

**Syntax**

`isLocked(H)`

**Description**

`isLocked(H)` returns the locked state of the `SubbandSynthesisFilter` object `H`.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# **dsp.SubbandSynthesisFilter.release**

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Reset internal states of subband synthesis filter object

**Syntax** reset(H)

**Description** reset(H) sets the internal states of the SubbandSynthesisFilter object H to their initial values.

# dsp.SubbandSynthesisFilter.step

---

**Purpose** Reconstruct signal from high- and low-frequency subbands

**Syntax**  $Y = \text{step}(H, HI, LO)$

**Description**  $Y = \text{step}(H, HI, LO)$  reconstructs a signal from a high-frequency subband, HI, and a low-frequency subband, LO.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

**Purpose** Time domain signal display


**Description** The TimeScope object displays time-domain signals.

To display time-domain signals in the Time Scope:

- 1** Define and set up your Time Scope. See “Construction” on page 5-1093.
- 2** Call `step` to display the signal in the Time Scope figure. The behavior of `step` is specific to each object in the toolbox.

Use the MATLAB `clear` function to close the Time Scope figure window.

# dsp.TimeScope



See the following sections for information on the Time Scope System object:

- “Construction” on page 5-1093

- “Properties” on page 5-1094
- “Methods” on page 5-1103

See the following sections for information on the Time Scope Graphical User Interface:

- “Displaying Multiple Signals” on page 5-1103
- “Signal Display” on page 5-1105
- “Toolbar” on page 5-1109
- “Measurements Panels” on page 5-1112
- “Style Dialog Box” on page 5-1135
- “Core — General UI Options” on page 5-1138
- “Visuals — Time Domain Options” on page 5-1140
- “Tools — Plot Navigation Options” on page 5-1149
- “Sources — Streaming Options” on page 5-1153

For examples on how to use the Time Scope System object, see “Examples” on page 5-1153.

---

**Note** For information about the Time Scope block, see Time Scope.

---

## Construction

`H = dsp.TimeScope` returns a Time Scope System object, `H`. This object displays real- and complex-valued floating and fixed-point signals in the time domain.

`H = dsp.TimeScope('PropertyName',PropertyValue,...)` creates a Time Scope System object, `H`, with each specified property `PropertyName` set to the specified value.

`H =`

`dsp.TimeScope(NUMINPUTS,SAMPLERATE,'PropertyName',PropertyValue,...)`

creates a Time Scope System object, H. This object has the NumInputPorts property set to *NUMINPUTS*, the SampleRate property set to *SAMPLERATE*, and other specified properties set to the specified values. *NUMINPUTS* and *SAMPLERATE* are value-only arguments. You can specify *PropertyName–PropertyValue* arguments in any order.

## Properties

### ActiveDisplay

Active display for display-specific properties

Specify as an integer the active display number for getting and setting relevant properties. The number of a display corresponds to its column-wise placement index. Setting this property controls which display is used for YLimits, YLabel, LegendSource, Grid, Title, and MagnitudePhase. This property is Tunable.

**Default:** 1

### FrameBasedProcessing

Process input in frames or as samples

When you set this property to true, you enable frame-based processing. When you set this property to false, you enable sample-based processing. This property is Tunable.

**Default:** true

### Grid

Option to enable or disable grid display

When you set this property to true, the grid appears. When you set this property to false, the grid does not appear. When set, ActiveDisplay controls which display is updated. This property is Tunable.

**Default:** false

### LayoutDimensions

Layout grid dimensions

Specify the layout grid dimensions as a 2-element vector: [numberOfRows, numberOfColumns]. You may use no more than four rows or four columns. This property is Tunable.

**Default:** [1,1]

## **LegendSource**

Source of legend

Specify the source of the legend as either None or Auto. When you set this property to 'None', the Time Scope does not display a legend. When you set this property to 'Auto', the Time Scope displays a legend with automatic string labels for each input channel. See FrameBasedProcessing for information on input channels. This property is Tunable.

**Default:** 'None'

## **MagnitudePhase**

Plot signal as Magnitude-and-Phase

Set this property to true to plot the magnitude and phase of the input signal on two separate axes within the same active display. When set, ActiveDisplay controls which displays are updated. The active display shows the magnitude of the input signal on the top axes and its phase, in degrees, on the bottom axes.

This property is particularly useful for complex-valued input signals. When the input signal is real-valued and you select this check box, the phase will be 0 degrees when the amplitude of the input signal is nonnegative and 180 degrees when the input signal is negative. This property is Tunable.

**Default:** false

## **MaximizeAxes**

## Maximize axes control

Specify whether to display the Time Scope in maximized axes mode. In this mode, each of the axes is expanded to fit into the entire display. To conserve space, labels do not appear in each display. Instead, tick-mark values appear on top of the plotted data. You can select one of the following options:

- **Auto** — In this mode, the axes appear maximized in all displays only if the `Title` and `YLabel` properties are empty for every display. If you enter any value in any display for either of these properties, the axes are not maximized.
- **On** — In this mode, the axes appear maximized in all displays. Any values entered into the `Title` and `YLabel` properties are hidden.
- **Off** — In this mode, none of the axes appear maximized.

This property is Tunable.

**Default:** 'Auto'

## Name

Caption to display on Time Scope window

Specify the caption to display on the scope window as any string. This property is Tunable.

**Default:** 'Time Scope'

## NumInputPorts

Number of input signals

Specify the number of input signals to display on the Time Scope as a positive integer. You must invoke the `step` method with the same number of inputs as the value of this property.

**Default:** 1

## **PlotType**

Option to control the type of plot

Specify the type of plot to use for all the input signals displayed in the Time Scope GUI.

- When you set this property to 'Line' , Time Scope displays the input signal as lines connecting each of the sampled values. This approach is similar to the functionality of the MATLAB `line` or `plot` function.
- When you set this property to 'Stairs' , Time Scope displays the input signal as a *stairstep* graph. A stairstep graph is made up of only horizontal lines and vertical lines. Each horizontal line represents the signal value for a discrete sample period and is connected to two vertical lines. Each vertical line represents a change in values occurring at a sample. This approach is equivalent to the MATLAB `stairs` function. Stairstep graphs are useful for drawing time history graphs of digitally sampled data.

This property is Tunable.

**Default:** 'Line'

## **Position**

Time Scope window position in pixels

Specify, in pixels, the size and location of the Time Scope window as a 4-element double vector of the form, [`left bottom width height`]. You can place the Time Scope window in a specific position on your screen by modifying the values to this property. This property is Tunable.

**Default:** The default depends on your screen resolution. By default, the Time Scope window is placed in the center of your screen with a width of 410 pixels and height of 300 pixels.

## **ReduceUpdates**

Reduce updates to improve performance

When you set this property to `true`, the Time Scope logs data for later use and updates the window periodically. When you set this property to `false`, the Time Scope updates every time the `step` method is called. The simulation speed is faster when this property is set to `true`. This property is Tunable.

You can also modify this property from the Time Scope GUI. Opening the **Simulation** menu and clearing the **Reduce Updates to Improve Performance** check box is the same as setting this property to `false`.

**Default:** `true`

## **SampleRate**

Sample rate of inputs

Specify the sampling rate, in hertz, of any input signal, as a scalar or as a numeric vector with length equal to the value of `NumInputPorts`. The inverse of the sample rate determines the spacing between points on the *x*-axis (time axis) in the displayed signal. When you set `SampleRate` to a scalar value and `NumInputPorts` is greater than 1, the object uses the same sample rate for all inputs.

**Default:** `1`

## **TimeAxisLabels**

Time-axis labels

Specify how time-axis labels should appear in the Time Scope displays as one of 'All', 'Bottom', or 'None'.

- When you set this property to 'All', time-axis labels appear in all displays.
- When you set this property to 'Bottom', time-axis labels appear in the bottom display of each column.
- When you set this property to 'None', there are no labels in any displays.

This property is Tunable.

**Default:** 'All'

## **TimeDisplayOffset**

Time display offset

Specify the offset, in seconds, to apply to the *x*-axis (time axis). This property can be either a numeric scalar or a vector of length equal to the number of input channels. If you specify this property as a scalar, then that value is the time display offset for all channels. If you specify a vector, each vector element is the time offset for the corresponding channel. For vectors with length less than the number of input channels, the time display offsets for the remaining channels are set to 0. If a vector has a length greater than the number of input channels, the extra vector elements are ignored. This property is Tunable.

See `FrameBasedProcessing` for information on input channels. See `TimeSpan` and `TimeSpanSource` for information on the *x*-axis limits and time span settings.

**Default:** 0

## **TimeSpan**

Specify the time span, in seconds, as a positive, numeric scalar value. This property applies when `FrameBasedProcessing` is `false`. This property also applies when `FrameBasedProcessing` is `true` and `TimeSpanSource` is `Property`. The  $x$ -axis limits are calculated as follows.

Minimum  $x$ -axis limit = `min(TimeDisplayOffset)`

Maximum  $x$ -axis limit = `max(TimeDisplayOffset) + TimeSpan`

where `TimeDisplayOffset` and `TimeSpan` are the values of their respective properties. This property is Tunable.

**Default:** 10

## **TimeSpanOverrunMode**

Wrap or scroll when the `TimeSpan` value is overrun

Specify how the Time Scope displays new data beyond the visible time span as one of 'Wrap' or 'Scroll'.

- When you set this property to `Wrap`, the Time Scope displays new data up until it reaches the maximum  $x$ -axis limit. When the data reaches the maximum  $x$ -axis limit of the Time Scope window, the Time Scope clears the display. The Time Scope then updates the time offset value and begins displaying subsequent data points starting from the minimum  $x$ -axis limit.
- When you set this property to `Scroll`, the Time Scope scrolls old data to the left to make room for new data on the right side of the Time Scope display. This mode is graphically intensive and can affect run-time performance, but it is beneficial for debugging and for monitoring time-varying signals.

This property is Tunable.

**Default:** 'Wrap'

## **TimeSpanSource**

## Source of time span

Specify the source of the time span for frame-based input signals as one of 'Auto' or 'Property'. This property applies when `FrameBasedProcessing` is set to true. When you set this property to 'Property', the object derives the *x*-axis limits from the `TimeDisplayOffset` and `TimeSpan` properties. When you set this property to Auto, the *x*-axis limits are the following:

$$\begin{aligned}\text{Minimum } x\text{-axis limit} &= \min(\text{TimeDisplayOffset}) \\ \text{Maximum } x\text{-axis limit} &= \max(\text{TimeDisplayOffset}) + \\ &\quad \max(1/\text{SampleRate}.*\text{FrameSize})\end{aligned}$$

where `TimeDisplayOffset` and `SampleRate` are the values of their respective properties. *FrameSize* is a vector equal to the number of rows in each input signal.

This property is Tunable.

**Default:** 'Property'

## TimeUnits

Units of the time axis

Specify the units used to describe the time axis.

- When you set this property to 'Metric', the Time Scope converts the time axis values to the most appropriate metric units, such as microseconds, milliseconds, minutes, days, etc.
- When you set this property to 'Seconds', the Time Scope will always leave the time units as seconds.
- When you set this property to 'None', the Time Scope will not display any units on the time axis.

This property is Tunable.

**Default:** 'Metric'

## Title

Display title

Specify the display title as a string. When set, `ActiveDisplay` controls which display is updated. This property is Tunable.

**Default:** ''

## YLabel

The label for the  $y$ -axis

Specify the  $y$ -axis label as a string. This property applies only when `MagnitudePhase` is `false`. When `MagnitudePhase` is `true`, the two  $y$ -axis labels are read-only values that are set to 'Magnitude' and 'Phase' for the magnitude plot and the phase plot, respectively. When set, `ActiveDisplay` controls which display is updated. This property is Tunable.

**Default:** 'Amplitude' if `MagnitudePhase` is `false`

## YLimits

The limits for the  $y$ -axis

Specify the  $y$ -axis limits as a 2-element numeric vector, [`ymin` `ymax`]. When set, `ActiveDisplay` controls which display is updated.

When `MagnitudePhase` is `true`, this property specifies the  $y$ -axis limits of only the magnitude plot. The  $y$ -axis limits of the phase plot are always `[-180, 180]`. This property is Tunable.

**Default:** `[-10, 10]` if `MagnitudePhase` is `false`, `[0, 10]` if `MagnitudePhase` is `true`.

## Methods

clone	Create time scope object with same property values
getNumInputs	Number of expected inputs to step method
getNumOutputs	Number of outputs of step method
hide	Hide time scope window
isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
reset	Reset internal states of time scope object
show	Make time scope window visible
step	Display signal in time scope figure

## Displaying Multiple Signals

### Multiple Signal Input

You can configure the Time Scope to show multiple signals within the same display or on separate displays. By default, the signals appear as different-colored lines on the same display. The signals can have different dimensions, sample rates, and data types. Each signal can be either real or complex valued. You can set the number of input ports on the Time Scope in the following ways:


- Set the NumInputPorts property. This property is nontunable, so you should set it before you run the step method.
- Run the show method to open the Scope window. In the Scope menu, select **File > Number of Input Ports**.

# dsp.TimeScope


An input signal may contain multiple channels, depending on its dimensions. Multiple channels of data always appear as different-colored lines on the same display.

## Multiple Displays

You can display multiple channels of data on different displays in the Scope window. In the Scope toolbar, select **View > Layout**, or select the Layout button (). This feature allows you to tile the window into a number of separate displays, up to a grid of 4 rows and 4 columns. For example, if there are three inputs to the Scope, you can display the signals in separate displays by selecting row 3, column 1, as shown in the following figure.



After you select row 3, column 1, the Scope window has three separate displays, as shown in the following figure.




## Signal Display

Time Scope uses the **Time span** and **Time display offset** parameters in order to determine the time range. To change the signal display settings, select **View > Properties** to bring up the Visuals:Time Domain Options dialog box. Then, modify the values for the **Time span** and **Time display offset** parameters on the **Main** tab. For example, if you set the **Time span** to 25 seconds, the scope displays 25 seconds' worth of simulation data at a time. If you also set the **Time display offset** to 5 seconds, the scope displays values on the time axis from 5 to 30 seconds. The values on the *time*-axis of the Time Scope display remain the same throughout simulation.

To communicate the simulation time that corresponds to the current display, the scope uses the **Time units**, **Time offset**, and **Simulation time** indicators on the scope window. The following figure highlights these and other important aspects of the Time Scope window.

# dsp.TimeScope



## Time Indicators

- **Minimum time-axis limit** — The Time Scope sets the minimum *time*-axis limit using the value of the **Time display offset** parameter on the **Main** tab of the Visuals:Time Domain Options dialog box. If you specify a vector of values for the **Time display offset** parameter, the scope uses the smallest of those values to set the minimum *time*-axis limit.
- **Maximum time-axis limit** — The Time Scope sets the maximum *time*-axis limit by summing the value of **Time display offset** parameter with the value of the **Time span** parameter. If you specify a vector of values for the **Time display offset** parameter, the scope sets the maximum *time*-axis limit by summing the largest of those values with the value of the **Time span** parameter.
- **Time units** — The units used to describe the *time*-axis. The Time Scope sets the time units using the value of the **Time units** parameter on the **Main** tab of the Visuals:Time Domain Options dialog box. By default, this parameter is set to **Metric** (based on **Time Span**) and displays in metric units such as milliseconds, microseconds, minutes, days, etc. You can change it to **Seconds** to always display the *time*-axis values in units of seconds. You can change it to **None** to not display any units on the *time*-axis. When you set this parameter to **None**, then Time Scope shows only the word **Time** on the *time*-axis.

To hide both the word `Time` and the values on the *time*-axis, set the **Show time-axis labels** parameter to `None`. To hide both the word `Time` and the values on the *time*-axis in all displays except the bottom ones in each column of displays, set this parameter to `Bottom Displays Only`. This behavior differs from the Simulink Scope block, which always shows the values but never shows a label on the *x*-axis.

For more information, see “Visuals — Time Domain Options” on page 5-1140.

## Simulation Indicators

- **Simulation status** — Provides the current status of the model simulation. The status can be one of the following conditions:
  - **Processing** — Occurs after you run the `step` method and before you run the `release` method.
  - **Stopped** — Occurs after you construct the `TimeScope` object and before you first run the `step` method. This status also occurs after you run the `release` method.

The **Simulation status** is part of the **Status Bar** in the Time Scope window. You can choose to hide or display the entire **Status Bar**. From the Time Scope menu, select **View > Status Bar**.

- **Time offset** — The **Time offset** value helps you determine the simulation times for which the scope is displaying data. The value is always in the range  $0 \leq \text{Time offset} \leq \text{Simulation time}$ .

Suppose you set the **Time span** to 20 seconds, and you see a **Time offset** of 0 (`secs`) on the scope window. This value indicates that the scope is displaying data for the first 0 to 20 seconds of simulation time. If the **Time offset** changes to 20 (`secs`), the scope displays data for simulation times from 20 seconds to 40 seconds. The scope continues to update the **Time offset** value until the simulation is complete.

- **Simulation time** — The amount of time that has progressed since the Time Scope object was first constructed or reset. Every time you

# dsp.TimeScope


call the `step` method, the simulation time increases by the number of rows in the input signal divided by the sample rate, as given by

the following formula:  $t_{sim} = t_{sim} + \frac{\text{length}(x)}{\text{SampleRate}}$ . You can modify the **SampleRate** parameter on the **Main options** pane of the **Spectrum Settings** panel. You can also set the sample rate using the `SampleRate` property.

The **Simulation time** is part of the **Status Bar** in the Time Scope window. You can choose to hide or display the entire **Status Bar**. From the Time Scope menu, select **View > Status Bar**.

## Axes Maximization

You can specify whether to display the Time Scope in maximized axes mode. In this mode, the axes are expanded to fill the entire display. In each display, there is no space to show titles or axis labels. The minimum and maximum *time*-axis limits are located at the far-left and far-right edges of the display. The values at the axis tick marks appear as grid lines on top of the axes. The following figure highlights the important indicators in this mode of the Time Scope window.



To enable this mode, in the Time Scope menu, select **View > Properties** to bring up the Visuals:Time Domain Options dialog box. In the **Main** pane, you can set the **Maximize axes** parameter to one of the following options:

- **Auto** — In this mode, the axes appear maximized in all displays only if the **Title** and **Y-Axis label** parameters are empty for every display. If you enter any value in any display for either of these parameters, the axes are not maximized.
- **On** — In this mode, the axes appear maximized in all displays. Any values entered into the **Title** and **Y-Axis label** parameters are hidden.
- **Off** — In this mode, none of the axes appear maximized.

You can also set the `MaximizeAxes` property to one of the aforementioned options.

## Reduce Updates to Improve Performance

By default, the Time Scope updates the displays periodically at a rate not exceeding 20 Hz. If you would like the Time Scope to update on every simulation time step, you can disable the **Reduce Updates to Improve Performance** option. In the Time Scope menu, select **Playback > Reduce Updates to Improve Performance** to clear the check box. You can also set the `ReduceUpdates` property to `false` to disable this option. However, as a recommended practice, you can leave this option enabled because doing so can significantly improve the speed of the simulation.

## Toolbar

The Time Scope toolbar contains the following buttons.

## Axes Control Buttons

	<b>Tools &gt; Zoom In</b>	N/A	When this tool is active, you can zoom in on the scope window. To do so, click in the center of your area of interest, or click and drag your cursor to draw a rectangular area of interest inside the scope window.
	<b>Tools &gt; Zoom X</b>	N/A	When this tool is active, you can zoom in on the x-axis. To do so, click inside the scope window, or click and drag your cursor along the x-axis over your area of interest.
	<b>Tools &gt; Zoom Y</b>	N/A	When this tool is active, you can zoom in on the y-axis. To do so, click inside the scope window, or click and drag your cursor along the y-axis over your area of interest.
	<b>Tools &gt; Scale Axes Limits</b>	<b>Ctrl+A</b>	<p>Click this button to scale the axes in the active scope window.</p> <p>Alternatively, you can enable automatic axes scaling by selecting one of the following options from the <b>Tools</b> menu:</p> <ul style="list-style-type: none"><li>• <b>Automatically Scale Axes Limits</b> — When you select this option, the scope scales the axes as needed during simulation.</li><li>• <b>Scale Axes Limits at Stop</b> — When you select this option, the scope scales the axes each time the simulation is stopped.</li></ul>

**Measurements Buttons**

	<p><b>Tools &gt; Measurements &gt; Cursor Measurements</b></p>	<p>N/A</p>	<p>Open or close the <b>Cursor Measurements</b> panel. This panel puts screen cursors on all the displays.</p> <p>See the “Cursor Measurements Panel” on page 5-1114 section for more information.</p>
	<p><b>Tools &gt; Measurements &gt; Signal Statistics</b></p>	<p>N/A</p>	<p>Open or close the <b>Signal Statistics</b> panel. This panel displays the maximum, minimum, peak-to-peak difference, mean, median, RMS values of a selected signal, and the times at which the maximum and minimum occur.</p> <p>See the “Signal Statistics Panel” on page 5-1116 section for more information.</p>
	<p><b>Tools &gt; Measurements &gt; Bilevel Measurements</b></p>	<p>N/A</p>	<p>Open or close the <b>Bilevel Measurements</b> panel. This panel displays information about a selected signal’s transitions, overshoots or undershoots, and cycles.</p> <p>See the “Bilevel Measurements Panel” on page 5-1118 section for more information.</p>
	<p><b>Tools &gt; Measurements &gt; Peak Finder</b></p>	<p>N/A</p>	<p>Open or close the <b>Peak Finder</b> panel. This panel displays maxima and the times at which they occur, allowing the settings for peak threshold, maximum number of peaks, and peak excursion to be modified.</p>

			See the “Peak Finder Panel” on page 5-1132 section for more information.
--	--	--	--

## Other Buttons

	<b>View &gt; Layout</b>	N/A	Arrange the layout of displays in the Time Scope. This feature allows you to tile your screen into a number of separate displays, up to a grid of 4 rows and 4 columns. You may find multiple displays useful when the Time Scope takes multiple input signals. The default display is 1 row and 1 column. See the “Multiple Displays” on page 5-1104 section for more information.
---	-------------------------	-----	---

You can control whether this toolbar appears in the Time Scope window. From the Time Scope menu, select **View > Toolbar**.

## Measurements Panels

The Measurements panels are the five panels that appear to the right side of the Time Scope GUI. These panels are labeled **Trace selection**, **Cursor measurements**, **Signal statistics**, **Bilevel measurements**, and **Peak finder**.

The Time Domain Measurements panels only appear if the **Measurements** tool is enabled in the Time Scope — Tools:Plot Navigation Options dialog box. To open this dialog box, in the Time Scope menu, select **File > Configuration** and click the **Tools** pane. If you disable the tool by clearing the **Enabled** check box, the Time Domain Measurements tools no longer display in the Time Scope GUI. You can reenable the tool at any time by selecting the **Enabled** check box. See the “Tools — Plot Navigation Options” on page 5-1149 section for more information.

## Measurements Panel Buttons


Each of the Measurements panels contains the following buttons that enable you to modify the appearance of the current panel.

Button	Description
	Move the current panel to the top. When you are displaying more than one panel, this action moves the current panel above all the other panels.
	Collapse the current panel. When you first enable a panel, by default, it displays one or more of its panes. Click this button to hide all of its panes to conserve space. After you click this button, it becomes the expand button  .
	Expand the current panel. This button appears after you click the collapse button to hide the panes in the current panel. Click this button to display the panes in the current panel and show measurements again. After you click this button, it becomes the collapse button  again.
	Undock the current panel. This button lets you move the current panel into a separate window that can be relocated anywhere on your screen. After you click this button, it becomes the dock button  in the new window.
	Dock the current panel. This button appears only after you click the undock button. Click this button to put the current panel back into the right side of the Scope window. After you click this button, it becomes the undock button  again.
	Close the current panel. This button lets you remove the current panel from the right side of the Scope window.

Some panels have their measurements separated by category into a number of panes. Click the pane expand button  to show each pane that is hidden in the current panel. Click the pane collapse button  to hide each pane that is shown in the current panel.

## Trace Selection Panel


When you use the Scope to view multiple signals, the Trace Selection panel appears if you have more than one signal displayed and you click on any of the other Measurements panels. Choose the signal name for which you would like to display time domain measurements. See the following figure.



You can choose to hide or display the **Trace Selection** panel. In the Scope menu, select **Tools > Measurements > Trace Selection**.

## Cursor Measurements Panel

The **Cursor Measurements** panel displays screen cursors. You can choose to hide or display the **Cursor Measurements** panel. In the Scope menu, select **Tools > Measurements > Cursor Measurements**. Alternatively, in the Scope toolbar, click the Cursor Measurements  button.



### Settings Pane

The **Settings** pane enables you to modify the type of screen cursors used to calculate time and value measurements.

- **Screen Cursors**— Shows screen cursors.
- **Horizontal**— Shows horizontal screen cursors.
- **Vertical**— Shows vertical screen cursors.
- **Waveform Cursors**— Shows cursors that attach to the input signals.
- **Lock Cursor Spacing**— Locks the time difference between the two cursors.

### Measurements Pane

The **Measurements** pane shows the time and value measurements.

- **1** |— Shows or enables you to modify the time or value at cursor number one, or both.
- **2** :— Shows or enables you to modify the time or value at cursor number two, or both.
- **$\Delta t$** — Shows the absolute value of the difference in the times between cursor number one and cursor number two.
- **$\Delta V$** — Shows the absolute value of the difference in signal amplitudes between cursor number one and cursor number two.
- **$1/\Delta t$** — Shows the rate, the reciprocal of the absolute value of the difference in the times between cursor number one and cursor number two.
- **$\Delta V/\Delta t$** — Shows the slope, the ratio of the absolute value of the difference in signal amplitudes between cursors to the absolute value of the difference in the times between cursors.

## Signal Statistics Panel

The **Signal Statistics** panel displays the maximum, minimum, peak-to-peak difference, mean, median, and RMS values of a selected signal. It also shows the times at which the maximum and minimum values occur. You can choose to hide or display the **Signal Statistics** panel. In the Scope menu, select **Tools > Measurements > Signal Statistics**. Alternatively, in the Scope toolbar, click the Signal Statistics  button.

	Value	Time (us)
Max	2.343	22.500
Min	-57.337 m	5.000
Peak to Peak	2.400	
Mean	1.150	
Median	1.152	
RMS	1.628	

## Signal Statistics Measurements

The **Signal Statistics** panel shows statistics about the portion of the input signal within the  $x$ -axis and  $y$ -axis limits of the active display. The statistics shown are:


- **Max** — Shows the maximum or largest value within the displayed portion of the input signal. For more information on the algorithm this measurement uses, see the MATLAB `max` function reference.
- **Min** — Shows the minimum or smallest value within the displayed portion of the input signal. For more information on the algorithm this measurement uses, see the MATLAB `min` function reference.
- **Peak to Peak** — Shows the difference between the maximum and minimum values within the displayed portion of the input signal. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `peak2peak` function reference.
- **Mean** — Shows the average or mean of all the values within the displayed portion of the input signal. For more information on the algorithm this measurement uses, see the MATLAB `mean` function reference.
- **Median** — Shows the median value within the displayed portion of the input signal. For more information on the algorithm this measurement uses, see the MATLAB `median` function reference.
- **RMS** — Shows the difference between the maximum and minimum values within the displayed portion of the input signal. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `rms` function reference.

When you use the zoom options in the Scope, the Signal Statistics measurements automatically adjust to the time range shown in the display. In the Scope toolbar, click the **Zoom In** or **Zoom X** button to constrict the  $x$ -axis range of the display, and the statistics shown reflect this time range. For example, you can zoom in on one pulse to make the **Signal Statistics** panel display information about only that particular pulse.

The Signal Statistics measurements are valid for any units of the input signal. The letter after the value associated with each measurement represents the appropriate International System of Units (SI) prefix, such as *m* for *milli*-. For example, if the input signal is measured in volts, an *m* next to a measurement value indicates that this value is in units of millivolts.

## Bilevel Measurements Panel


The **Bilevel Measurements** panel shows information about a selected signal's transitions, overshoots or undershoots, and cycles. You can choose to hide or display the **Bilevel Measurements** panel. In the Scope menu, select **Tools > Measurements > Bilevel Measurements**. Alternatively, in the Scope toolbar, you can select the Bilevel Measurements  button.



The **Bilevel Measurements** panel is separated into four panes, labeled **Settings**, **Transitions**, **Overshoots / Undershoots**, and **Cycles**. You can expand each pane to see the available options.

## Settings Pane


The **Settings** pane enables you to modify the properties used to calculate various measurements involving transitions, overshoots, undershoots, and cycles. You can modify the high-state level, low-state level, state-level tolerance, upper-reference level, mid-reference level, and lower-reference level, as shown in the following figure.




- **Auto State Level** — When this check box is selected, the Bilevel measurements panel autodetects the high- and low- state levels of a bilevel waveform. For more information on the algorithm this option uses, see the Signal Processing Toolbox `statelevels` function

reference. When this check box is cleared, you may enter in values for the high- and low- state levels manually.


- **High** — Used to manually specify the value that denotes a positive polarity, or high-state level, as shown in the following figure.



- **Low** — Used to manually specify the value that denotes a negative polarity, or low-state level, as shown in the following figure.



- **State Level Tolerance** — Tolerance within which the initial and final levels of each transition must be within their respective state levels. This value is expressed as a percentage of the difference between the high- and low-state levels.
- **Upper Ref Level** — Used to compute the end of the rise-time measurement or the start of the fall time measurement. This value is expressed as a percentage of the difference between the high- and low-state levels.
- **Mid Ref Level** — Used to determine when a transition occurs. This value is expressed as a percentage of the difference between the high- and low- state levels. In the following figure, the mid-reference level is shown as the horizontal line, and its corresponding mid-reference level instant is shown as the vertical line.




- **Lower Ref Level** — Used to compute the end of the fall-time measurement or the start of the rise-time measurement. This value is expressed as a percentage of the difference between the high- and low-state levels.
- **Settle Seek** — The duration after the mid-reference level instant when each transition occurs used for computing a valid settling time. This value is equivalent to the input parameter, `D`, which you can set when you run the `settlingtime` function. The settling time is displayed in the **Overshoots/Undershoots** pane.

## Transitions Pane


The **Transitions** pane displays calculated measurements associated with the input signal changing between its two possible state level values, high and low.

A positive-going transition, or *rising edge*, in a bilevel waveform is a transition from the low-state level to the high-state level. A positive-going transition has a slope value greater than zero. The following figure shows a positive-going transition.



Whenever there is a plus sign (+) next to a text label, this symbol refers to measurement associated with a rising edge, a transition from a low-state level to a high-state level.

A negative-going transition, or *falling edge*, in a bilevel waveform is a transition from the high-state level to the low-state level. A negative-going transition has a slope value less than zero. The following figure shows a negative-going transition.




Whenever there is a minus sign (–) next to a text label, this symbol refers to measurement associated with a falling edge, a transition from a high-state level to a low-state level.

The Transition measurements assume that the amplitude of the input signal is in units of volts. You must convert all input signals to volts for the Transition measurements to be valid.

- **High** — The high-amplitude state level of the input signal over the duration of the **Time Span** parameter. You can set **Time Span** in the **Main** pane of the Visuals:Time Domain Options dialog box. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `statelevels` function reference.
- **Low** — The low-amplitude state level of the input signal over the duration of the **Time Span** parameter. You can set **Time Span** in the **Main** pane of the Visuals:Time Domain Options dialog box. For

more information on the algorithm this measurement uses, see the Signal Processing Toolbox `statelevels` function reference.

- **Amplitude** — Difference in amplitude between the high-state level and the low-state level.
- **+ Edges** — Total number of positive-polarity, or rising, edges counted within the displayed portion of the input signal.
- **+ Rise Time** — Average amount of time required for each rising edge to cross from the lower-reference level to the upper-reference level. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `risetime` function reference.
- **+ Slew Rate** — Average slope of each rising-edge transition line within the upper- and lower-percent reference levels in the displayed portion of the input signal. The region in which the slew rate is calculated appears in gray in the following figure.




For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `slewrates` function reference.

- – **Edges** — Total number of negative-polarity or falling edges counted within the displayed portion of the input signal.
- – **Fall Time** — Average amount of time required for each falling edge to cross from the upper-reference level to the lower-reference level. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `falltime` function reference.
- – **Slew Rate** — Average slope of each falling edge transition line within the upper- and lower-percent reference levels in the displayed portion of the input signal. For more information on the algorithm


this measurement uses, see the Signal Processing Toolbox `slewrates` function reference.

### Overshoots/Undershoots


The **Overshoots/Undershoots** pane displays calculated measurements involving the distortion and damping of the input signal. *Overshoot* and *undershoot* refer to the amount that a signal respectively exceeds and falls below its final steady-state value. *Preshoot* refers to the amount prior to a transition that a signal varies from its initial steady-state value. This figure shows preshoot, overshoot, and undershoot for a rising-edge transition.



The next figure shows preshoot, overshoot, and undershoot for a falling-edge transition.



- + **Preshoot** — Average lowest aberration in the region immediately preceding each rising transition.
- + **Overshoot** — Average highest aberration in the region immediately following each rising transition. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox overshoot function reference.
- + **Undershoot** — Average lowest aberration in the region immediately following each rising transition. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox undershoot function reference.
- + **Settling Time** — Average time required for each rising edge to enter and remain within the tolerance of the high-state level for the remainder of the settle seek duration. The settling time is the time after the mid-reference level instant when the signal crosses into and remains in the tolerance region around the high-state level. This crossing is illustrated in the following figure.



You can modify the settle seek duration parameter in the **Settings** pane. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `settlingtime` function reference.


- – **Preshoot** — Average highest aberration in the region immediately preceding each falling transition.
- – **Overshoot** — Average highest aberration in the region immediately following each falling transition. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `overshoot` function reference.
- – **Undershoot** — Average lowest aberration in the region immediately following each falling transition. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `undershoot` function reference.
- – **Settling Time** — Average time required for each falling edge to enter and remain within the tolerance of the low-state level for the remainder of the settle seek duration. The settling time is the time after the mid-reference level instant when the signal crosses into and remains in the tolerance region around the low-state level. You can

modify the settle seek duration parameter in the **Settings** pane. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `settlingtime` function reference.

## Cycles

The **Cycles** pane displays calculated measurements pertaining to repetitions or trends in the displayed portion of the input signal.

- **Period** — Average duration between adjacent edges of identical polarity within the displayed portion of the input signal. The Bilevel measurements panel calculates period as follows. It takes the difference between the mid-reference level instants of the initial transition of each positive-polarity pulse and the next positive-going transition. These mid-reference level instants appear as red dots in the following figure.



For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `pulseperiod` function reference.


- **Frequency** — Reciprocal of the average period. Whereas period is typically measured in some metric form of seconds, or seconds per cycle, frequency is typically measured in hertz or cycles per second.
- **+ Pulses** — Number of positive-polarity pulses counted.
- **+ Width** — Average duration between rising and falling edges of each positive-polarity pulse within the displayed portion of the input signal. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `pulsewidth` function reference.
- **+ Duty Cycle** — Average ratio of pulse width to pulse period for each positive-polarity pulse within the displayed portion of the input signal. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `dutycycle` function reference.
- **- Pulses** — Number of negative-polarity pulses counted.
- **- Width** — Average duration between rising and falling edges of each negative-polarity pulse within the displayed portion of the input signal. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `pulsewidth` function reference.
- **- Duty Cycle** — Average ratio of pulse width to pulse period for each negative-polarity pulse within the displayed portion of the input signal. For more information on the algorithm this measurement uses, see the Signal Processing Toolbox `dutycycle` function reference.

When you use the zoom options in the Scope, the bilevel measurements automatically adjust to the time range shown in the display. In the Scope toolbar, click the **Zoom In** or **Zoom X** button to constrict the *x*-axis range of the display, and the statistics shown reflect this time range. For example, you can zoom in on one rising edge to make the **Bilevel Measurements** panel display information about only that

particular rising edge. However, this feature does not apply to the **High** and **Low** measurements.

## Peak Finder Panel

The **Peak Finder** panel displays maxima and the times at which they occur, allowing the settings for peak threshold, maximum number of peaks, and peak excursion to be modified. You can choose to hide or display the **Peak Finder** panel. In the Scope menu, select **Tools > Measurements > Peak Finder**. Alternatively, in the Scope toolbar, select the Peak Finder  button.




The **Peak finder** panel is separated into two panes, labeled **Settings** and **Peaks**. You can expand each pane to see the available options.

## Settings Pane

The **Settings** pane enables you to modify the parameters used to calculate the peak values within the displayed portion of the input

signal. For more information on the algorithms this pane uses, see the Signal Processing Toolbox `findpeaks` function reference.

- **Peak Threshold** — The level above which peaks are detected. This setting is equivalent to the `MINPEAKHEIGHT` parameter, which you can set when you run the `findpeaks` function.
- **Max Num of Peaks** — The maximum number of peaks to show. This setting is equivalent to the `NPEAKS` parameter, which you can set when you run the `findpeaks` function.
- **Min Peaks Distance** — The minimum number of samples between adjacent peaks. This setting is equivalent to the `MINPEAKDISTANCE` parameter, which you can set when you run the `findpeaks` function.
- **Peak Excursion** — The minimum height difference between a peak and its neighboring samples. Peak excursion is illustrated alongside peak threshold in the following figure.



Whereas the peak threshold is a minimum value necessary for a sample value to be a peak, the peak excursion is the minimum difference between a peak sample and the samples to its left and right

in the time domain. In the figure, the green vertical line illustrates the lesser of the two height differences between the labeled peak and its neighboring samples. This height difference must be greater than the **Peak Excursion** value for the labeled peak to be classified as a peak. Compare this setting to peak threshold, which is illustrated by the red horizontal line. The amplitude must be above this horizontal line for the labeled peak to be classified as a peak.

The peak excursion setting is equivalent to the **THRESHOLD** parameter, which you can set when you run the `findpeaks` function.

- **Label peaks** — When this check box is selected, the Peak Finder displays the calculated peak values directly on the plot. By default, this check box is cleared and no values are displayed on the plot.
- **Sort by time** — When this check box is selected, the Peak Finder puts the largest calculated peak values in the time range shown in the display in time-sorted order. The Peak Finder displays the peak values in the **Peaks** pane. The **Max Num of Peaks** parameter still controls the number of peaks listed. By default, this check box is cleared and the **Peak Finder** panel displays the largest calculated peak values in the **Peaks** pane in decreasing order of peak height.

## Peaks Pane

The **Peaks** pane displays all of the largest calculated peak values and the times at which the peaks occur, using the parameters you define in the **Settings** pane. You set the **Max Num of Peaks** parameter to specify the number of peaks shown in the list. Using the **Sort by time** check box, you set the order in which the peaks are listed.


The numerical values displayed in the **Value** column are equivalent to the `pks` output argument returned when you run the `findpeaks` function. The numerical values displayed in the **Time** column are similar to the `locs` output argument returned when you run the `findpeaks` function.

When you use the zoom options in the Scope, the peak locations automatically adjust to the time range shown in the display. In the Scope toolbar, click the **Zoom In** or **Zoom X** button to constrict the

x-axis range of the display, and the statistics shown reflect this time range. For example, you can zoom in on one peak to make the **Peak Finder** panel display information about only that particular peak.

## Style Dialog Box

In the **Style** dialog box, you can customize the style of displays. You are able to change the color of the figure containing the displays, the background and foreground colors of display axes, and properties of lines in a display. From the Scope menu, select **View > Style** to open this dialog box.



### Properties

The **Style** dialog box allows you to modify the following properties of the Scope GUI:

#### Figure color

Specify the color that you want to apply to the background of the Scope GUI. By default, the figure color is gray.

## Plot type

Specify the type of plot to use. The default setting is `Line`. Valid values for **Plot type** are:

- `Line` — Displays input signal as lines connecting each of the sampled values. This approach is similar to the functionality of the MATLAB `line` or `plot` function.
- `Stairs` — Displays input signal as a *stairstep* graph. A stairstep graph is made up of only horizontal lines and vertical lines. Each horizontal line represents the signal value for a discrete sample period and is connected to two vertical lines. Each vertical line represents a change in values occurring at a sample. This approach is equivalent to the MATLAB `stairs` function. Stairstep graphs are useful for drawing time history graphs of digitally sampled data.
- `Auto` — Displays input signal as a line graph if it is a continuous signal and displays input signal as a stairstep graph if it is a discrete signal.

This parameter is Tunable.

## Select display

Specify the active display as a number, where a display number corresponds to the index of the input signal. The number of a display corresponds to its column-wise placement index. The default setting is 1. Set this parameter to control which display should have its axes colors, line properties, marker properties, and visibility changed. Tunable.

## Axes colors

Specify the color that you want to apply to the background of the axes for the active display.

## Properties for line

Specify the signal for which you want to modify the visibility, line properties, and marker properties.

## Visible

Specify whether the selected signal on the active display should be visible. If you clear this check box, the line disappears.

## Line

Specify the line style, line width, and line color for the selected signal on the active display.

## Marker

Specify marks for the selected signal on the active display to show at data points. This parameter is similar to the Marker property for the MATLAB Handle Graphics plot objects. You can choose any of the marker symbols from the following table.


Specifier	Marker Type
none	No marker (default)
○	Circle
□	Square
×	Cross
•	Point
+	Plus sign
*	Asterisk
◇	Diamond
▽	Downward-pointing triangle
△	Upward-pointing triangle
◁	Left-pointing triangle
▷	Right-pointing triangle

# dsp.TimeScope

Specifier	Marker Type
☆	Five-pointed star (pentagram)
✧	Six-pointed star (hexagram)


## Core — General UI Options

The Core:General UI Options dialog box controls the general settings for the Time Scope GUI. From the Time Scope menu bar, select **File > Configuration** to open the Time Scope — Configuration dialog box. Click on the **Core** pane, and the following dialog box appears.



To open the Core:General UI Options dialog box, select **General UI** and click **Options**. The following dialog box appears.

## General UI Options



### Open message log

Use this parameter to control when the Message Log window opens. The Message Log window helps you debug any issues with the Time Scope. Using the drop-down list, you can choose to open the Message Log window under any of the following conditions:

- for any new messages
- for warn/fail messages
- only for fail messages
- manually

You can open the Message Log at any time by selecting **Help > Message Log**. The Message Log dialog box provides a system-level record of loaded configuration settings and registered extensions. The Message Log displays summaries and details of each message, and you can filter the display of messages by **Type** and **Category**.

- The **Type** parameter allows you to select which types of messages to display in the Message Log. You can select **All**, **Info**, **Warn**, or **Fail**.
- The **Category** parameter allows you to select the category of messages to display in the Message Log. You can select **All**, **Configuration**, or **Extension**.


- The scope uses `Configuration` messages to indicate when new configuration files are loaded.
- The scope uses `Extension` messages to indicate when components are registered. For example, you may see a `Simulink registered` message, indicating that a component has been successfully registered with Simulink and is available for configuration.

## Visuals – Time Domain Options

The Time Scope — Visuals:Time Domain Options dialog box controls the visual configuration settings of the Time Scope displays. From the Time Scope menu, select **View > Properties** to open this dialog box.

### Main Pane

The **Main** pane of the Time Scope — Visuals:Time Domain Options dialog box appears as follows.



### Input processing

Specify whether the Time Scope should treat the input signal as Columns as channels (frame based) or Elements as channels (sample based). Tunable.

Frame-based processing is only available for discrete input signals. For more information about frame-based input channels, see the “What Is Frame-Based Processing?” section in the *DSP System Toolbox User’s Guide*. For an example that uses the Time Scope block and frame-based input signals, see the Display Time-Domain Data in the Time Scope section in the *DSP System Toolbox User’s Guide*.


### Time span

Specify the time span, either by selecting a predefined option or by entering a numeric value in seconds. You can select one of the following options:

# dsp.TimeScope

- **Auto calculate** — In this mode, the Time Scope automatically calculates the appropriate value for time span from the difference between the simulation “Start time” and “Stop time” parameters. This option is available only for the Time Scope block but not for the dsp.TimeScope System object.
- **One frame period** — In this mode, the Time Scope uses the frame period of the input signal to the Time Scope block. This option is only available when the **Input processing** parameter is set to **Columns as channels (frame based)**. This option is not available when you set the **Input processing** parameter to **Elements as channels (sample based)**.
- **<user defined>** — In this mode, you specify the time span by replacing the text <user defined> with a numeric value in seconds.

The scope sets the *time*-axis limits using the value of this parameter and the value of the **Time display offset** parameter. For example, if you set the **Time display offset** to  $5e-6$  and the **Time span** to  $25e-6$ , the scope sets the *time*-axis limits as shown in the following figure.



This parameter is Tunable.

### **Time span overrun**

Specify how the scope displays new data beyond the visible time span. The default setting is **Wrap**. You can select one of the following options:

- **Wrap** — In this mode, the scope displays new data until the data reaches the maximum *time*-axis limit. When the data reaches the maximum *time*-axis limit of the scope window, the Time Scope clears the display. The Time Scope then updates the time offset value, and begins displaying subsequent data points starting from the minimum *time*-axis limit.
- **Scroll** — In this mode, the scope scrolls old data to the left to make room for new data on the right side of the scope display. This mode is graphically intensive and can affect run-time performance, but it is beneficial for debugging and monitoring time-varying signals.

This parameter is Tunable.

### **Time units**

Specify the units used to describe the *time*-axis. The default setting is **Metric**. You can select one of the following options:

- **Metric** — In this mode, Time Scope converts the times on the *time*-axis to some metric units such as milliseconds, microseconds, days, etc. Time Scope chooses the appropriate metric units, based on the minimum *time*-axis limit and the maximum *time*-axis limit of the scope window.
- **Seconds** — In this mode, Time Scope always displays the units on the *time*-axis as seconds.
- **None** — In this mode, Time Scope displays no units on the *time*-axis. Time Scope shows only the word **Time** on the *time*-axis.

This parameter is Tunable.

### **Time display offset**


This parameter allows you to offset the values displayed on the *time*-axis by a specified number of seconds. When you specify a scalar value, the scope offsets all channels equally. When you specify a vector of offset values, the scope offsets each channel independently. Tunable.

When you specify a **Time display offset** vector of length  $N$ , the scope offsets the input channels as follows:

# dsp.TimeScope

- When  $N$  is equal to the number of input channels, the scope offsets each channel according to its corresponding value in the offset vector.
- When  $N$  is less than the number of input channels, the scope applies the values you specify in the offset vector to the first  $N$  input channels. The scope does not offset the remaining channels.
- When  $N$  is greater than the number of input channels, the scope offsets each input channel according to the corresponding value in the offset vector. The scope ignores all values in the offset vector that do not correspond to a channel of the input.

The scope computes the *time*-axis range using the values of the **Time display offset** and **Time span** parameters. For example, if you set the **Time display offset** to  $5\text{e-}6$  and the **Time span** to  $25\text{e-}6$ , the scope sets the *time*-axis limits as shown in the following figure.



Similarly, when you specify a vector of values, the scope sets the minimum *time*-axis limit using the smallest value in the vector. To set the maximum *time*-axis limit, the scope sums the largest value in the vector with the value of the **Time span** parameter. For more information, see “Signal Display” on page 2-1447.

## Show time-axis labels

Specify how to display the time units used to describe the *time*-axis. The default setting is All. You can select one of the following options:

- All — In this mode, the *time*-axis labels appear in all displays.
- None — In this mode, the *time*-axis labels do not appear in the displays.
- Bottom Displays Only — In this mode, the *time*-axis labels appear in only the bottom row of the displays.

Tunable.


### **Maximize axes**

Specify whether to display the Time Scope in maximized axes mode. In this mode, each of the axes are expanded to fit into the entire display. In each display, there is no space to show labels. Tick mark values are shown on top of the plotted data. The default setting is Auto. You can select one of the following options:

- Auto — In this mode, the axes appear maximized in all displays only if the **Title** and **Y-Axis label** parameters are empty for every display. If you enter any value in any display for either of these parameters, the axes are not maximized.
- On — In this mode, the axes appear maximized in all displays. Any values entered into the **Title** and **Y-Axis label** parameters are hidden.
- Off — In this mode, none of the axes appear maximized.

### **Display Pane**

The **Display** pane of the Visuals:Time Domain Options dialog box appears as follows.



### Select display

Specify the active display as a number, where a display number corresponds to the index of the input signal. The index of a display is its column-wise placement index. The default setting is 1. Set this parameter to control the display for which you intend to modify the title, legend, grid, *y*-axis limits, *y*-axis label, and magnitude/phase display parameters. Tunable.

### Title

Specify the active display title as a string. By default, the active display has no title. Tunable.

### Show legend

Select this check box to show the legend in the active display. The channel legend displays a name for each channel of each input signal. When the legend appears, you can place it anywhere inside of the scope window. To turn the legend off, clear the **Show legend** check box. Tunable.

You can edit the name of any channel in the legend. To do so, double-click the current name, and enter a new channel name. By default, the scope names each channel according to either its signal name or the name of the block from which it comes. If the signal has multiple channels, the scope uses an index number to identify each channel of that signal. For example, a 2-channel signal named `MySignal` would have the following default names in the channel legend: `MySignal:1`, `MySignal:2`.

The Time Scope does not display signal names that were labeled within an unmasked subsystem. You must label all input signals to the Scope block that originate from an unmasked subsystem.

To change the appearance of any channel of any input signal in the Scope window, from the menu, select **View > Style**.


### **Show grid**

When you select this check box, a grid appears in the active display of the Scope. To hide the grid, clear this check box. Tunable.


### **Plot signal(s) as magnitude and phase**

When you select this check box, the Scope splits the active display into a magnitude plot and a phase plot. By default, this check box is cleared. If the input signal is complex valued, the Scope plots the real and imaginary portions on the same axes. These real and imaginary portions appear as different-colored lines on the same axes within the same active display, as shown in the following figure.

# dsp.TimeScope



Selecting this check box and clicking the **Apply** or **OK** button changes the active display. The magnitude of the input signal appears on the top axes and its phase, in degrees, appears on the bottom axes. See the following figure.



This feature is particularly useful for complex-valued input signals. If the input is a real-valued signal, selecting this check box always produces the same behavior. The phase is 0 for nonnegative input and 180 degrees for negative input. Tunable.

**Minimum Y-limit**

Specify the minimum value of the  $y$ -axis. Tunable.

When you select the **Plot signal(s) as magnitude and phase** check box, the value of this parameter always applies to the magnitude plot on the top axes. The phase plot on the bottom axes is always limited to a minimum value of  $-180$  degrees.

**Maximum Y-limit**

Specify the maximum value of the  $y$ -axis. Tunable.

When you select the **Plot signal(s) as magnitude and phase** check box, the value of this parameter always applies to the magnitude plot on the top axes. The phase plot on the bottom axes is always limited to a maximum value of 180 degrees.

**Y-axis label**


Specify the text for the scope to display to the left of the  $y$ -axis. Tunable.

This parameter becomes invisible when you select the **Plot signal(s) as magnitude and phase** check box. When you enable that parameter, the  $y$ -axis label always appears as **Magnitude** on the top axes and **Phase** on the bottom axes.

**Tools —  
Plot  
Navigation  
Options**

The Time Scope — Tools:Plot Navigation Options dialog box provides you with the ability to automatically zoom in on and zoom out of your data, and to scale the axes of the Time Scope. In the Time Scope menu, select **Tools > Axes Scaling Options** to open this dialog box.

Alternatively, you can open this dialog box from the Time Scope — Configuration dialog box. In the Time Scope menu, select **File > Configuration** to open the Time Scope — Configuration dialog box. Click the **Tools** pane, and the following dialog box appears.



The **Tools** pane in the Time Scope – Configuration dialog box contains the tools that appear on the Time Scope GUI. By default, the **Plot Navigation** tool is enabled. If you disable the tool by clearing the **Enabled** check box, the axes scaling and zoom tools no longer display in the Time Scope GUI. You can reenble the tool at any time by selecting the **Enabled** check box.

By default, the **Measurements** tool is also enabled. If you disable the tool by clearing the **Enabled** check box, the Time Domain Measurements tools no longer display in the Time Scope GUI. See the “Measurements Panels” on page 5-1112 section for more information. You can reenble the tool at any time by selecting the **Enabled** check box.

To open the Time Scope — Tools:Plot Navigation Options dialog box, select the **Plot Navigation** tool, and then click the **Options** button.

## Parameters

The Tools:Plot Navigation Options dialog box appears as follows.

Parameters

Axes scaling:

Do not allow Y-axis limits to shrink

Y-axis

Data range (%):  Align:

Scale X-axis limits

Data range (%):  Align:



### Axis Scaling

Specify when the Scope should automatically scale the axes. You can select one of the following options:

- **Manual** — When you select this option, the Scope does not automatically scale the axes. You can manually scale the axes in any of the following ways:
  - Select **Tools > Scale axes limits**.
  - Press the **Scale Axes Limits** toolbar button.
  - When the scope GUI is the active window, press **Ctrl+A**.
- **Auto** — When you select this option, the Scope scales the axes as needed, both during and after simulation. Selecting this option enables the **Do not allow Y-axis limits to shrink** check box. By default, this parameter is selected, and the Scope does not shrink the y-axis limits when scaling the axes.
- **Once at stop** — Selecting this option causes the Scope to scale the axes each time simulation is stopped. The Scope does not scale the axes during simulation.

This parameter is Tunable.

### **Do not allow Y-axis limits to shrink**

When you select this parameter, the  $y$ -axis limits are only allowed to grow during axes scaling operations. If you clear this check box, the  $y$ -axis limits may shrink during axes scaling operations.

This parameter appears only when you select **Auto** for the **Axis Scaling** parameter. When you set the **Axis Scaling** parameter to **Manual** or **Once at stop**, the  $y$ -axis limits are allowed to shrink. Tunable.

### **Y-axis Data range (%)**

Set the percentage of the  $y$ -axis that the Scope should use to display the data when scaling the axes. Valid values are between 1 and 100. For example, if you set this parameter to 100, the Scope scales the  $y$ -axis limits such that your data uses the entire  $y$ -axis range. If you then set this parameter to 30, the Scope increases the  $y$ -axis range such that your data uses only 30% of the  $y$ -axis range. Tunable.

### **Y-axis Align**

Specify where the Scope should align your data with respect to the  $y$ -axis when it scales the axes. You can select **Top**, **Center**, or **Bottom**. Tunable.

### **Scale X-axis limits**

Check this box to allow the Scope to scale the  $x$ -axis limits when it scales the axes. Tunable.

### **X-axis Data range (%)**

Set the percentage of the  $x$ -axis that the Scope should use to display the data when scaling the axes. Valid values are between 1 and 100. For example, if you set this parameter to 100, the Scope scales the  $x$ -axis limits such that your data uses the entire  $x$ -axis range. If you then set this parameter to 30, the Scope increases the  $x$ -axis range such that your data uses only 30% of the  $x$ -axis range. Use the  **$x$ -axis Align** parameter to specify data placement with respect to the  $x$ -axis.

This parameter appears only when you select the **Scale X-axis limits** check box. Tunable.


## Sources — Streaming Options

### X-axis Align

Specify how the Scope should align your data with respect to the *x*-axis: Left, Center, or Right. This parameter appears only when you select the **Scale X-axis limits** check box. Tunable.

The Sources:Streaming Options dialog box lets you control the number of input signal samples that Time Scope holds in memory. In the Time Scope menu, select **View > Data History Options** to open this dialog box.

### Data History Options



### Limit data points to last

Specify the number of input signal samples that Time Scope holds in memory. The default is 50000.

## Examples

The first few examples illustrate how to use the Time Scope block to view a variety of input signals in the time domain.

- “Example: Display Simple Sine Wave Input Signal” on page 5-1154
- “Example: View Sine Wave Input Signals at Different Sample Rates and Offsets” on page 5-1154
- “Example: Display Complex-valued Input Signal” on page 5-1155
- “Example: Display Variable-size Input Signal” on page 5-1157

The remaining examples demonstrate how to use the Measurements Panels in the Time Scope GUI to glean information about the input signals.

- “Example: Use Bilevel Measurements Panel with Clock Input Signal” on page 5-1158
- “Example: Find Heart Rate Using Peak Finder Panel with ECG Input Signal” on page 5-1161

## **Example: Display Simple Sine Wave Input Signal**

Construct `dsp.SineWave` and `dsp.TimeScope` objects. Run the `step` method to display the signal.

```
hsin = dsp.SineWave('Frequency',100, 'SampleRate', 1000);
hsin.SamplesPerFrame = 10;
hts1 = dsp.TimeScope('SampleRate', hsin.SampleRate,'TimeSpan', 0.1);
for ii = 1:10
    x = step(hsin);
    step(hts1, x);
end
```

Run the `release` method to automatically scale the axes.

```
release(hts1)
```

Run the MATLAB `clear` function to close the Time Scope window.

```
clear hts1 hsin x;
```

## **Example: View Sine Wave Input Signals at Different Sample Rates and Offsets**

Construct `dsp.SineWave` and `dsp.FirDecimator` objects. Use the `dsp.FirDecimator` object to create a new signal that equals the original signal, but decimated by a factor of 2. Construct a `dsp.TimeScope` object with 2 input ports. Run the `step` method to display the signal.

```
Fs = 1000; % Sampling frequency
hsin1 = dsp.SineWave('Frequency',50,...
    'SampleRate',Fs, ...
    'SamplesPerFrame', 100);
% Create FIRDecimator System object to decimate by 2
```

```
hfilt = dsp.FIRDecimator;
% Create TimeScope System object with 2 input ports (channels)
hts2 = dsp.TimeScope(2, [Fs Fs/2], ...
    'TimeDisplayOffset', [0 38/Fs], ...
    'TimeSpan', 0.25, ...
    'YLimits',[-1 1], ...
    'LegendSource', 'Auto');
for ii = 1:2
    xsine = step(hsin1);
    xdec = step(hfilt,xsine);
    step(hts2, xsine, xdec);
end
```

Run the release method to automatically scale the axes.

```
release(hts2)
```

Run the MATLAB clear function to close the Time Scope window.

```
clear hts2 Fs hsin1 hfilt ii xsine xdec;
```


## Example: Display Complex-valued Input Signal

Create a vector representing a complex-valued sinusoidal signal and construct a dsp.TimeScope object. Run the step method to display the signal.

```
fs = 1000; t = (0:1/fs:10)';
CxSine = cos(2*pi*0.2*t) + 1i*sin(2*pi*0.2*t);
CxSineSum = cumsum(CxSine);
figure(101); subplot(2,1,1); stairs(t,abs(CxSineSum)); % Plot magnitude
subplot(2,1,2); stairs(t,(180/pi)*angle(CxSineSum)); % Plot phase
h1 = dsp.TimeScope(1, fs, 'TimeSpanSource', 'Auto');
step(h1,CxSineSum);
```

By default, when the input is a complex-valued signal, Time Scope plots the real and imaginary portions on the same axes. These real and imaginary portions appear as different-colored lines on the same axes within the same active display, as shown in the following figure.


# dsp.TimeScope



Change the MagnitudePhase property to true.

```
set(h1, 'MagnitudePhase', true);
```

Time Scope now plots the magnitude and phase of the input signal on two separate axes within the same active display. The active display changes to show the magnitude of the input signal on the top axes and its phase, in degrees, on the bottom axes, as shown in the following figure.



Run the `release` method to automatically scale the axes.

```
release(h1);
```

Run the MATLAB `clear` function to close the Time Scope window, and remove the variables you created from the workspace.

```
close(101);
clear h1 fs t CxSine CxSineSum
```

### Example: Display Variable-size Input Signal

Create a vector that represents a two-channel constant signal. Create another vector that represents a three-channel constant signal. Construct a `dsp.TimeScope` object with 2 input ports. Run the `step` method to display the signal.

```
fs = 10;
```

## dsp.TimeScope

---

```
sigdim2 = [ones(5*fs,1), 1+ones(5*fs,1)]; % 2-dim 0-5s
sigdim3 = [2+ones(5*fs,1), 3+ones(5*fs,1), 4+ones(5*fs,1)]; % 3-dim 5-10s
h2 = dsp.TimeScope(2, fs, 'TimeSpanSource', 'Property');
set(h2, 'PlotType', 'Stairs');
set(h2, 'TimeSpanOverrunMode', 'Scroll');
set(h2, 'TimeDisplayOffset', [0,0,5]);
step(h2,[sigdim2; sigdim3(:,1:2)], sigdim3(:,3));
```

In this example, the size of the input signal to the Time Scope block changes as the simulation progresses. When the simulation time is less than 5 seconds, Time Scope plots only the signal *sigdim2*, which has two channels. After 5 seconds, Time Scope also plots the signal *sigdim3*, which has three channels.

Run the release method to automatically scale the axes.

```
release(h2);
```

Run the MATLAB `clear` function to close the Time Scope window, and remove the variables you created from the workspace.

```
clear h2 fs sigdim2 sigdim3
```

### **Example: Use Bilevel Measurements Panel with Clock Input Signal**

Load the clock data into the variable, *x*. Find the sample time, *ts*.

```
load clockex;
ts = t(2)-t(1);
```


Construct a `dsp.TimeScope` object. Run the step method to display the signal.

```
h4 = dsp.TimeScope(1, 1/ts, 'TimeSpanSource', 'Auto');
step(h4,x);
```

Run the release method to automatically scale the axes.

```
release(h4);
```


To show the **Bilevel Measurements** panel, in the Time Scope menu, select **Tools > Measurements > Bilevel Measurements**. To collapse the **Transitions** pane, click the pane collapse button (▼) next to that label. To expand the **Settings** pane and the **Overshoots / Undershoots** pane, click the pane expand button (▶) next to each label. The Time Scope figure appears as shown in the following figure.



As you can see in the figure, the value for the rising edge **Settling Time** parameter is initially not displayed. The reason for this is that the default value for the **Settle Seek** parameter is too large for this example. In this case, the settle seek time is longer than the entire simulation duration. Enter a value for settle seek of  $2e-6$ , and press the **Enter** key. Time Scope now displays a rising edge settling time value of 118.392 ns.

# dsp.TimeScope

This settling time value displayed is actually the statistical average of the settling times for all five rising edges. To show the settling time for only one rising edge, you can zoom in on that transition. In the Time Scope toolbar, click the Zoom X button (). Then, click the display near a value of 2 microseconds on the *time*-axis. Drag to the right and release near a value of 4 microseconds on the *time*-axis. Time Scope updates the rising edge **Settling Time** value to reflect the new time window, as shown in the following figure.



Run the MATLAB `clear` function to close the Time Scope window, and remove the variables you created from the workspace.

```
clear h4 x t ts
```

### Example: Find Heart Rate Using Peak Finder Panel with ECG Input Signal

First, create the electrocardiogram (ECG) signal.

```
x1 = 3.5*ecg(2700).';  
y1 = sgolayfilt(kron(ones(1,13),x1),0,21);  
n = (1:30000)';  
del = round(2700*rand(1));  
mhb = y1(n + del);  
ts = 0.00025;
```

This example uses the Savitzky-Golay filter in Signal Processing Toolbox. For more information, see the `sgolayfilt` function reference page or run the `sgolaydemo` example.

Construct a `dsp.TimeScope` object. Run the `step` method to display the signal.


```
h5 = dsp.TimeScope(1, 1/ts, 'TimeSpanSource', 'Auto');  
step(h5,mhb);
```

Run the `release` method to automatically scale the axes.

```
release(h5);
```

To show the **Peak Finder** panel, in the Time Scope menu, select **Tools > Measurements > Peak Finder**. To expand the **Settings** pane, click the pane expand button (▶) next to that label. Enter a value for **Max Num of Peaks** of 10, and press the **Enter** key. Time Scope now displays in the **Peaks** pane a list of 10 peak amplitude values, and the times at which they occur, as shown in the following figure.

# dsp.TimeScope



As you can see from the list of peak values, there is a constant time difference of 0.675 seconds between each heartbeat. Therefore, the heart rate of the ECG signal is given by the following equation:

$$\frac{60 \frac{\text{sec}}{\text{min}}}{0.675 \frac{\text{sec}}{\text{beat}}} = 88.89 \frac{\text{beats}}{\text{min}} (\text{bpm})$$

Run the MATLAB `clear` function to close the Time Scope window, and remove the variables you created from the workspace.

```
clear h5 x1 y1 n del mhb ts
```

## See Also

Time Scope | `dsp.SpectrumAnalyzer` | `sptool`

**Purpose** Create time scope object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a `TimeScope` object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with uninitialized states.

# dsp.TimeScope.getNumInputs

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method. *N* equals the value of the `NumInputPorts` property.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose** Number of outputs of step method

**Syntax** `N = getNumOutputs(H)`

**Description** `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method. The time scope is a sink object, so `N` equals 0.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# **dsp.TimeScope.hide**

---

**Purpose** Hide time scope window

**Syntax** `hide(H)`

**Description** `hide(H)` hides the time scope window, associated with System object, H.

**See Also** `dsp.TimeScope.show`

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the TimeScope object H.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.TimeScope.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** release(H)

**Description** release(H) releases system resources, such as memory, file handles, and hardware connections. This method lets you change any properties or input characteristics.

You should call the `release` method after calling the `step` method when there is no new data for the simulation. When you call the `release` method, the axes will automatically scale in the Time Scope figure window. After calling the `release` method, any non-tunable properties can be set once again.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

**Examples** View a sine wave on the time scope. When you finish the simulation, release system resources. Note that when you run the release method, the axes automatically scale.

```
hsin = dsp.SineWave('Frequency',100, 'SampleRate', 1000);
hsin.SamplesPerFrame = 10;

hts1 = dsp.TimeScope('SampleRate', hsin.SampleRate,'TimeSpan', 0.1);
for ii = 1:10
    x = step(hsin);
    step(hts1, x);
end

release(hts1);
```

View two sine waves with different sample rates and time offsets. When you finish the simulation, release system resources. Note that when you run the release method, the axes automatically scale.

```
Fs = 1000; % Sampling frequency

hsin1 = dsp.SineWave('Frequency',50,...
    'SampleRate',Fs, ...
    'SamplesPerFrame', 100);

% Create FIRDecimator System object to decimate by 2
hfilt = dsp.FIRDecimator;

% Create TimeScope System object with 2 input
% ports (channels)
hts2 = dsp.TimeScope(2, [Fs Fs/2], ...
    'TimeDisplayOffset', [0 38/Fs], ...
    'TimeSpan', 0.25, ...
    'YLimits',[-1 1], ...
    'LegendSource', 'Auto');

for ii = 1:2
    xsine = step(hsin1);
    xdec = step(hfilt,xsine);
    step(hts2, xsine, xdec);
end

release(hts2);
```

## Algorithms

In operation, the release method is similar to the mdlTerminate function.

## See Also

dsp.TimeScope.reset

# dsp.TimeScope.reset

---

**Purpose** Reset internal states of time scope object

**Syntax** reset(H)

**Description** reset(H) sets the internal states of the TimeScope object H to their initial values.

You should call the reset method after calling the step method when you want to clear the Time Scope figure displays, prior to releasing system resources. This action enables you to start a simulation from the beginning. When you call the reset method, the displays will become blank again. In this sense, its functionality is similar to that of the MATLAB clf function. Do not call the reset method after calling the release method.

## Examples

View a sine wave on the time scope. When you finish the simulation, pause for 5 seconds and then reset the screen. Then, view a different sine wave on the same time scope.

```
hsin = dsp.SineWave('Frequency', 100, 'SampleRate', 1000, 'SamplesPerFrame', 100);
hsin1 = dsp.SineWave('Frequency', 50, 'SampleRate', 1000, 'SamplesPerFrame', 100);

hts1 = dsp.TimeScope('SampleRate', hsin.SampleRate, 'TimeSpan', 0.1);
for ii = 1:10
    x = step(hsin);
    step(hts1, x);
end

% Pause and then reset internal states
pause(5);
reset(hts1);

for ii = 1:10
    x = step(hsin1);
    step(hts1, x);
end
```

```
release(hts1);
```

## Algorithms

In operation, the reset method is similar to a consecutive execution of the `mdlTerminate` function and the `mdlInitializeConditions` function.

## See Also

`dsp.TimeScope` | `dsp.TimeScope.release`

# dsp.TimeScope.show

---

**Purpose**            Make time scope window visible

**Syntax**            show(H)

**Description**        show(H) makes the time scope window, associated with System object, H, visible.

**See Also**            dsp.TimeScope.hide

**Purpose** Display signal in time scope figure

**Syntax** `step(H,X)`  
`step(H,X1,X2,...,XN)`

**Description** `step(H,X)` displays the signal, X, in the time scope figure.  
`step(H,X1,X2,...,XN)` displays the signals X1, X2,...,XN in the time scope figure when you set the NumInputPorts property to N. In this case, X1, X2,...,XN can have different data types and dimensions.

# dsp.TransitionMetrics

---

**Purpose** Transition metrics of bilevel waveforms

**Description** The TransitionMetrics object extracts information such as duration, slew rate, and reference-level crossings for each transition found in the bilevel waveform. The TransitionMetrics object can additionally return preshoot, postshoot and settling metrics for the regions immediately before and after each transition.

To obtain transition metrics for a bilevel waveform:

- 1 Define and set up your transition metrics. See “Construction” on page 5-1174.
- 2 Call `step` to calculate the transition metrics according to the properties of `dsp.TransitionMetrics`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.TransitionMetrics` creates a transition metrics System object, `H`. The object computes the rise time, fall time and width of a pulse. TransitionMetrics additionally computes cycle metrics such as pulse separations, periods, and duty cycles.

`H = dsp.TransitionMetrics('PropertyName',PropertyValue,...)` returns a TransitionMetrics System object, `H`, with each specified property set to the specified value.

**Properties** **MaximumRecordLength**

Maximum samples to preserve between calls to `step`. This property requires a positive integer that specifies the maximum number of samples to save between calls to the `step` method. When the number of samples to be saved exceeds this length, the oldest excess samples are discarded. This property applies when `RunningMetrics` is true and is tunable.

**Default:** 1000

**PercentReferenceLevels**

Lower-, middle-, and upper-percent reference levels. This property contains a 3-element numeric row vector that contains the lower-, middle-, and upper-percent reference levels. These reference levels are used as an offset between the low and high states of the waveform when computing the duration of each transition.

**Default:** [10 50 90]

### **PercentStateLevelTolerance**

Tolerance of the state level (in percent). This property requires a scalar that specifies the maximum deviation from either the low or high state before it is considered to be outside that state. The tolerance is expressed as a percentage of the waveform amplitude.

**Default:** 2

### **PostshootOutputPort**

Enable posttransition aberration metrics. If this property is set to true, overshoot and undershoot metrics are reported for a region defined immediately after each transition. The posttransition aberration region is defined as the waveform interval that begins at the end of each transition and whose duration is the value of PostshootSeekFactor times the computed transition duration. If a complete subsequent transition is detected before the interval is over, the region is truncated at the start of the subsequent transition. The metrics are computed for each transition that has a complete posttransition aberration region.

**Default:** false

### **PostshootSeekFactor**

Corresponds to the duration of time to search for the overshoot and undershoot metrics immediately following each transition. The duration is expressed as a factor of the duration of the transition.

# dsp.TransitionMetrics

---

This property is enabled only when the `PostshootOutputPort` property is set to `true` and is tunable.

**Default:** 3

## **PreshootOutputPort**

Enable pretransition aberration metrics. If the `PreshootOutputPort` property is set to `true`, overshoot and undershoot metrics are reported for a region defined immediately before each transition. The pretransition aberration region is defined as the waveform interval that ends at the start of each transition and whose duration is `PreshootSeekFactor` times the computed transition duration.

**Default:** false

## **PreshootSeekFactor**

Corresponds to the duration of time to search for the overshoot and undershoot metrics immediately preceding each transition. The duration is expressed as a factor of the duration of the transition. This property is enabled only when the `PreshootOutputPort` property is set to `true` and is tunable.

**Default:** 3

## **RunningMetrics**

Enable metrics over all calls to `step`. If `RunningMetrics` is set to `false`, metrics are computed for each call to `step` independently. If `RunningMetrics` is set to `true`, metrics are computed across subsequent calls to `step`. If there are not enough samples to compute metrics associated with the last transition, posttransition aberration region, or settling seek duration in the current record, the object defers reporting all transition, aberration, and settling metrics associated with the last transition until a subsequent call

to step is made with enough data to compute all enabled metrics for that transition.

**Default:** false

## **SampleRate**

Sampling rate of uniformly-sampled signal. Specify the sample rate in hertz as a positive scalar. This property is used to construct the internal time values that correspond to the input sample values. Time values start with zero. This property applies when the `TimeInputPort` property is set to false.

**Default:** 1

## **SettlingOutputPort**

Enable settling metrics. If `SettlingOutputPort` is set to true, settling metrics are reported for each transition. The region used to compute the settling metrics starts at the midcrossing and lasts until the `SettlingSeekDuration` has elapsed. If an intervening transition occurs, or the signal has not settled within the `PercentStateLevelTolerance` of the final level, NaN is returned for each metric. If there are not enough samples after the last transition to complete the `SettlingSeekDuration`, no metrics are reported for the last transition. The metrics are reported for the transition the next time step is called if the `RunningMetrics` property is set to true.

**Default:** false

## **SettlingSeekDuration**

Duration of time over which to search for settling. This property is a scalar that specifies the amount of time to inspect from the mid-reference level crossing (in seconds). If the transition has not yet settled, or a subsequent complete transition is detected within this duration, the `TransitionMetrics` object reports NaN for all

# dsp.TransitionMetrics

---

settling metrics. This property is tunable and applies only when you set the `SettlingOutputPort` property to `true`.

**Default:** 0.02

## StateLevels

Low- and high-state levels. This property is a 2-element numeric row vector that contains the low and high state levels respectively. These state levels correspond to the nominal logic low and high levels of the pulse waveform. This property is tunable.

**Default:** [0 2.3]

## StateLevelsSource

Auto or manual state level computation. If the `StateLevelsSource` property is set to 'Auto', the first record sent to `step` is sent to `dsp.StateLevels` with the default settings to determine the state levels of the incoming waveform. If this property is set to 'Property', the object uses the values the user specifies in the `StateLevels` property.

**Default:** 'Property'

## TimeInputPort

Add input to specify sample instants. Set `TimeInputPort` to `true` to enable an additional real input column vector to `step` to specify the sample instants that correspond to the sample values. If this property is `false`, the sample instants are built internally. The sample instants start at zero and increment by the reciprocal of the `SampleRate` property for subsequent samples. The sample instants continue to increment if the `RunningMetrics` property is set to `true` and no intervening calls to the `reset` or `release` methods are encountered.

**Default:** false

## Methods

<code>clone</code>	Clones the current instance of the transition metrics object
<code>getNumInputs</code>	Number of expected inputs to the method
<code>getNumOutputs</code>	Number of outputs of the method
<code>isLocked</code>	Locked status (logical) for input attributes and nontunable properties
<code>plot</code>	Plots signal and metrics computed in last call to
<code>reset</code>	Reset the running transition metrics object
<code>step</code>	Transition metrics of bilevel waveform

## Examples

### Transition and Preshoot Information of a 2.3 V Step Waveform

Compute transition and preshoot information of a 2.3 V step waveform sampled at 4 MHz

Load the data.

```
load('transitionex.mat', 'x');
```

Construct your transition metrics System object. Set the `SampleRate` property to 4 MHz, set the `StateLevelsSource` property to 'Auto' to estimate the state levels from the data, set the `PreshootOutputPort` property to `true` to output pretransition aberration metrics when you call `step`.

```
htm1 = dsp.TransitionMetrics('SampleRate',4e6, ...  
                             'StateLevelsSource','Auto', ...  
                             'PreshootOutputPort',true)
```

# dsp.TransitionMetrics

---

Call `step` to compute the transition and preshoot information. Plot the result.

```
[transition, preshoot] = step(htm1, x)
plot(htm1)
```

## Transition, Postshoot, and Settling Information of a 2.3 V Step Waveform

Compute transition, postshoot, and settling information of a 2.3 V step waveform sampled at 4 MHz.

Load the data along with the sampling instants.

```
load('transitionex.mat', 'x', 't');
```

Construct your transition metrics object setting the `TimeInputPort` property to `true` and the `StateLevels` property to match waveform state levels. To output the postshoot information and settling information when you call `step`, set the `PostShootOutputPort` and `SettlingOutputPort` properties to `true`. Set the settling seek duration to 2 microseconds.

```
htm2 = dsp.TransitionMetrics('TimeInputPort',true, ...
                             'StateLevels',[0 2.3], ...
                             'PostshootOutputPort',true, ...
                             'SettlingOutputPort',true, ...
                             'SettlingSeekDuration',2e-6)
```

Compute the transition, postshoot, and settling information with `step` and plot the result.

```
[transition, postshoot, settling] = step(htm2,x,t)
plot(htm2)
```

## References

[1] *IEEE Standard on Transitions, Pulses, and Related Waveforms*, IEEE Standard 181, 2003.

## See Also

`dsp.StateLevels` | `dsp.PulseMetrics` |

<b>Purpose</b>	Clones the current instance of the transition metrics object
<b>Syntax</b>	<code>clone(H)</code>
<b>Description</b>	<code>clone(H)</code> clones the current instance of the transition metrics object H.

# **dsp.TransitionMetrics.getNumInputs**

---

**Purpose**                Number of expected inputs to the step method

**Syntax**                `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method for the transition metrics object *H*.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.TransitionMetrics.getNumOutputs

---

**Purpose** Number of outputs of the `step` method

**Syntax** `N = getNumOutputs(H)`

**Description** `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# **dsp.TransitionMetrics.isLocked**

---

<b>Purpose</b>	Locked status (logical) for input attributes and nontunable properties
<b>Syntax</b>	<code>isLocked(H)</code>
<b>Description</b>	<code>isLocked(H)</code> returns the locked state of the transition metrics object H.

**Purpose**

Plots signal and metrics computed in last call to step

**Syntax**

plot(H)

**Description**

plot(H) plots the signal and metrics resulting from the last call of the step method.

By default plot displays

- the low and high state levels and the state-level boundaries defined by the PercentStateLevelTolerance property.
- the lower-, middle-, and upper-reference levels.
- the locations of the mid-reference level crossings of the positive (+) and negative (-) transitions of each detected pulse.

When you set the TransitionOutputPort property to true, the locations of the upper and lower crossings are also plotted. When the PreshootOutputPort or PostShootOutputPort properties are set to true, the corresponding overshoots and undershoots are plotted as inverted or non-inverted triangles. When the SettlingOutputPort property is set to true, the locations where the signal enters and remains within the upper- and lower-state boundaries over the specified seek duration are plotted.

# **dsp.TransitionMetrics.reset**

---

**Purpose**            Reset the running transition metrics object

**Syntax**            reset(H)

**Description**

reset(H) clears information from previous calls to step.

**Purpose** Transition metrics of bilevel waveform

**Syntax**

```
PULSE = step(H,X)
[PULSE,CYCLE] = step(H,X)
[PULSE,TRANSITION] = step(H,X)
[PULSE,PRESHOOT] = step(H,X)
[PULSE,POSTSHOOT] = step(H,X)
[PULSE,SETTLING] = step(H,X)
[...] = step(H,X,T)
```

**Description** PULSE = step(H,X) returns a structure array, PULSE, whose fields contain real-valued column vectors. The number of rows of each field corresponds to the number of complete pulses found in the real-valued column vector input, X. Each pulse starts with a transition of the polarity specified by the Polarity property and ends with a transition of the opposite polarity.

PULSE fields:

- **PositiveCross** — Instants where the positive-going transitions cross the mid-reference level of each pulse
- **NegativeCross** — Instants where the negative-going transitions cross the mid-reference level of each pulse
- **Width** — Absolute difference between **PositiveCross** and **NegativeCross** of each pulse
- **RiseTime** — Duration between the linearly-interpolated instants when the positive-going (rising) transition of each pulse crosses the lower- and upper-reference levels
- **FallTime** — Duration between the linearly-interpolated instants when the negative-going (falling) transition of each pulse crosses the upper- and lower-reference levels

[PULSE,CYCLE] = step(H,X) returns a structure array, CYCLE, whose fields contain real-valued column vectors when you set the `CycleOutputPort` property to true. The number of rows of each field

## dsp.TransitionMetrics.step

---

corresponds to the number of complete pulse periods found in the real-valued column vector input, `X`. You need at least three consecutive alternating polarity transitions that start and end with the same polarity as the value of the `Polarity` property if you want to compute cycle metrics. If the last transition found the input, `X`, does not match the polarity of the `Polarity` property, the pulse separation, period, frequency, and duty cycle are not reported for the last pulse. If the `RunningMetrics` property is set to `true` when this occurs, all pulse, cycle, transition, preshoot, postshoot, and settling metrics associated with the last pulse are deferred until a subsequent call to `step` detects the next transition.

CYCLE fields:

- `Period` — Duration between the first transition of the current pulse and the first transition of the next pulse
- `Frequency` — Reciprocal of the period
- `Separation` — Durations between the mid-reference level crossings of the second transition of each pulse and the first transition of the next pulse
- `Width` — Durations between the mid-reference level crossings of the first and second transitions of each pulse. This is equivalent to the width parameter of the `PULSE` structure.
- `DutyCycle` — Ratio of the width to the period for each pulse

`[PULSE, TRANSITION] = step(H,X)` returns a structure array, `TRANSITION`, when you set the `TransitionOutputPort` property to `true`. The fields of `TRANSITION` contain real-valued matrices with two columns which correspond to the metrics of the first and second transitions. The number of rows corresponds to the number of pulses found in the input waveform.

TRANSITION fields:

- `Duration` — Amount of time between the interpolated instants where the transition crosses the lower- and upper-reference levels

- **SlewRate** — Ratio of absolute difference between the upper- and lower-reference levels to the transition duration
- **MiddleCross** — Linearly-interpolated instant where the transition first crosses the mid-reference level
- **LowerCross** — Linearly-interpolated instant where the signal crosses the lower-reference level
- **UpperCross** — Linearly-interpolated instant where the signal crosses the upper-reference level

[PULSE, PRESHOOT] = step(H,X) returns a structure array, PRESHOOT, when you set the PreshootOutputPort property to true. The fields of PRESHOOT contain real-valued 2-column matrices whose row length corresponds to the number of transitions found in the input waveform. The field names are identical to those of the POSTSHOOT structure.

[PULSE, POSTSHOOT] = step(H,X) returns a structure array, POSTSHOOT, when you set the PostshootOutputPort property to true. The fields of POSTSHOOT contain real-valued 2-column matrices whose row length corresponds to the number of transitions found in the input waveform.

PRESHOOT and POSTSHOOT fields:

- **Overshoot** — Overshoot of the region of interest expressed as a percentage of the waveform amplitude
- **Undershoot** — Undershoot of the region of interest expressed as a percentage of the waveform amplitude
- **OvershootLevel** — Level of the overshoot
- **UndershootLevel** — Level of the undershoot
- **OvershootInstant** — Instant that corresponds to the overshoot
- **UndershootInstant** — Instant that corresponds to the undershoot

[PULSE, SETTLING] = step(H,X) returns a structure, SETTLING, when you set the SettlingOutputPort property to true. The fields of

## dsp.TransitionMetrics.step

---

SETTLING correspond to the settling metrics for each transition. Each field is a column vector whose elements correspond to the individual settling durations, levels, and instants.

SETTLING fields:

- **Duration** — Amount of time from when the signal crosses the mid-reference level to the time where the signal enters and remains within the specified `PercentStateLevelTolerance` of the waveform amplitude over the specified settling seek duration
- **Instant** — Instant in time where the signal enters and remains within the specified tolerance
- **Level** — Level of the waveform where it enters and remains within the specified tolerance

The above operations can be used simultaneously, provided the System object properties are set appropriately. One example of providing all possible inputs and returning all possible outputs is :

```
[ PULSE, CYCLE, TRANSITION, PRESHOOT, POSTSHOOT, SETTLING ] =  
step(H,X) which returns the PULSE, CYCLE, TRANSITION, PRESHOOT,  
POSTSHOOT, and SETTLING structure arrays when the CycleOutputPort,  
PreshootOutputPort, PostshootPort, and SettlingOutputPort  
properties are true. You may enable or disable any combination of  
output ports. However, the output arguments are defined in the order  
shown here.
```

```
[ ... ] = step(H,X,T) performs the above metrics with respect to a  
sampled signal, whose sample values, X, and sample instants, T, are  
real-valued column vectors of the same length. The additional input T  
applies only when you set the TimeInputPort property to true.
```

<b>Purpose</b>	Receive UDP packets from network
<b>Description</b>	<p>The <code>UDPReceiver</code> object receives UDP packets from the network.</p> <p>To receive UDP packets from the network:</p> <ol style="list-style-type: none"><li>1 Define and set up your UDP receiver. See “Construction” on page 5-1191.</li><li>2 Call <code>step</code> to receive the UDP packets according to the properties of <code>dsp.UDPReceiver</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.UDPReceiver</code> returns a UDP receiver System object, <code>H</code>, that receives UDP packets from a specified port.</p> <p><code>H = dsp.UDPReceiver('PropertyName',PropertyVaLue, ...)</code> returns a window object, <code>H</code>, with each property set to the specified value.</p>
<b>Properties</b>	<p><b>LocalIPPort</b></p> <p>Local port on which to receive data</p> <p>Specify the port on which to receive data. The default is 25000.</p> <p><b>RemoteIPAddress</b></p> <p>Address from which data was sent</p> <p>Specify the remote IP address from which to receive data. The default is '0.0.0.0', which indicates that data is accepted from any remote IP address.</p> <p><b>ReceiveBufferSize</b></p> <p>Maximum size of internal buffer</p> <p>Specify the size of the buffer that receives UDP packets, in bytes. The default is 8192.</p> <p><b>MaximumMessageLength</b></p>

# dsp.UDPReceiver

---

Maximum size of output message

Specify the size of the output message. If received packets exceed the specified value, their contents are truncated. The default is 255.

## MessageDataType

Data type of the message

Specify the data type of the message as | double | single | int8 | uint8 | int16 | uint16 | int32 | uint32 | logical |. The default is uint8.

## Methods

clone	Create UDP receiver object with same property values
getNumInputs	Number of expected inputs to step method
getNumOutputs	Number of outputs of step method
isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
step	Multiply input by window

## Examples

Send some UDP packets, and calculate the number of successfully transmitted bytes:

```
hudpr = dsp.UDPReceiver;  
hudps = dsp.UDPSender;  
  
bytesSent = 0;  
bytesReceived = 0;  
dataLength = 128;
```

```
for k = 1:20
    dataSent = uint8(255*rand(1,dataLength));
    bytesSent = bytesSent + dataLength;
    step(hudps, dataSent);
    dataReceived = step(hudpr);
    bytesReceived = bytesReceived + length(dataReceived);
end

release(hudps);
release(hudpr);

fprintf('Bytes sent:      %d\n', bytesSent);
fprintf('Bytes received: %d\n', bytesReceived);
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the UDP Receive block reference page. The object properties correspond to the block parameters, except:

- The **Output variable-size signal** parameter is not included in the System object.
- The **Sample time** parameter is not included in the System object.

## See Also

dsp.UDPSender

# **dsp.UDPReceiver.clone**

---

**Purpose** Create UDP receiver object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a UDP receiver object, `C`, with the same property values as `H`. The clone method creates a new unlocked object.

**Purpose** Number of expected inputs to step method

**Syntax** N = getNumInputs(H)

**Description** N = getNumInputs(H) returns the number of expected inputs, N, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.UDPReceiver.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `Y = isLocked(H)`

**Description** `Y = isLocked(H)` returns the locked state, `Y`, of the UDP receiver object. The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.UDPReceiver.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections. This method lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Multiply input by window

**Syntax** P = step (H)

**Description**

P = step (H) receives one UDP packet, P, from the network.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

The first time you call the `step` method on a `UDPReceiver` object, the object also allocates resources and begins listening for data. As a result, the first `step` call may not receive data.

# dsp.UDPSender

---

**Purpose** Send UDP packets to network

**Description** The UDPSender object sends UDP packets to the network.  
To send UDP packets to the network:

- 1 Define and set up your UDP sender. See “Construction” on page 5-1200.
- 2 Call `step` to send the packets according to the properties of `dsp.UDPSender`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.UDPSender` returns a UDP sender object, `H`, that sends UDP packets to a specified port.

`H = dsp.UDPSender('PropertyName',PropertyValue, ...)` returns a UDP sender object, `H`, with each property set to the specified value.

## Properties

### RemoteIPAddress

Remote address to which to send data

Specify the remote (i.e., host) IP address to which the data is sent. The default is '127.0.0.1', which is the local host.

### RemoteIPPort

Remote port to which to send data

Specify the port at the remote IP address to which the data is sent. The default is 25000.

### LocalIPPortSource

Source of the LocalIPPort property

Specify how to determine the port on the host as | Auto | Property |. If you specify Auto, the object selects the port dynamically from the available ports. If you specify Property, the object uses the source specified in the LocalIPPort property. The default is Auto.

## LocalIPPort

Local port from which to send data

Specify the port from which to send data. This property applies when you set the LocalIPPortSource property to Auto. The default is 25000.

## Methods

clone	Create UDP sender object with same property values
getNumInputs	Number of expected inputs to step method
getNumOutputs	Number of outputs of step method
isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
step	Send a UDP packet to network

## Examples

Send a number of UDP packets, and calculate the number of successfully transmitted bytes:

```
hudpr = dsp.UDPReceiver;  
hudps = dsp.UDPSEnder;  
  
bytesSent = 0;  
bytesReceived = 0;  
dataLength = 128;  
  
for k = 1:20  
    dataSent = uint8(255*rand(1,dataLength));  
    bytesSent = bytesSent + dataLength;  
    step(hudps, dataSent);  
    dataReceived = step(hudpr);  
end
```

# dsp.UDPsender

---

```
        bytesReceived = bytesReceived + length(dataReceived);  
    end  
  
    release(hudps);  
    release(hudpr);  
  
    fprintf('Bytes sent:      %d\n', bytesSent);  
    fprintf('Bytes received: %d\n', bytesReceived);
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the UDP Send block reference page. The object properties correspond to the block parameters.

## See Also

dsp.UDPReceiver

**Purpose** Create UDP sender object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a UDP sender object, `C`, with the same property values as `H`. The clone method creates a new unlocked object.

# dsp.UDPSEnder.getNumInputs

---

**Purpose**                Number of expected inputs to step method

**Syntax**                `getNumInputs(H)`

**Description**        `getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose**

Number of outputs of step method

**Syntax**

`N = getNumOutputs(H)`

**Description**

`N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# dsp.UDPsender.isLocked

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** isLocked(H)

**Description** isLocked(H) returns the locked state of the UDP sender object.

The isLocked method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the step method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the isLocked method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `Y = release(H)`

**Description** `Y = release(H)` releases system resources, such as memory, file handles, and hardware connections. This method lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

## dsp.UDPsender.step

---

**Purpose** Send a UDP packet to network

**Syntax** `Y = step(H,PACKET)`

**Description** `Y = step(H,PACKET)` sends one UDP packet, `PACKET`, to the network.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

## Purpose

Decode integer input into floating-point output

## Description

The `UniformDecoder` object decodes integer input into floating-point output. The decoder adheres to the definition for uniform decoding specified in ITU-T Recommendation G.701.

To decode an integer input into a floating-point output:

- 1 Define and set up your uniform decoder. See “Construction” on page 5-1209.
- 2 Call `step` to decode the input according to the properties of `dsp.UniformDecoder`. The behavior of `step` is specific to each object in the toolbox.

## Construction

`H = dsp.UniformDecoder` returns a uniform decoder, `H`, that performs the inverse operation of the `UniformEncoder` object, reconstructing quantized floating-point values from encoded integer input.

`H = dsp.UniformDecoder('PropertyName',PropertyValue,...)` returns a uniform decoder, `H`, with each specified property set to the specified value.

`H = dsp.UniformDecoder(peakvalue,numbits,'PropertyName',PropertyValue,...)` returns a uniform decoder, `H`, with the `PeakValue` property set to `peakvalue`, the `NumBits` property set to `numbits`, and other specified properties set to the specified values.

## Properties

### PeakValue

Largest amplitude represented in encoded input

Specify the largest amplitude represented in the encoded input as a nonnegative numeric scalar. To correctly decode values encoded with the `UniformEncoder` object, set the `PeakValue` property in both objects to the same value. For more information on setting this property, see the `PeakValue` property description on the `dsp.UniformEncoder` reference page. The default is 1.

# dsp.UniformDecoder

---

## NumBits

Number of input bits used to encode data

Specify the number of bits used to encode the input data as an integer value between 2 and 32. The value of this property can be less than the total number of bits supplied by the input data type. To correctly decode values encoded with the `UniformEncoder` object, set the `NumBits` property in both objects to the same value. For more information on setting this property, see the `NumBits` property description on the `dsp.UniformEncoder` reference page. The default is 3.

## OverflowAction

Action to take when integer input is out of range

Specify the behavior of the uniform decoder when the integer input is out of range as `Saturate` or `Wrap`. The value of the `NumBits` property specifies the representable range of the input. The default is `Saturate`.

## OutputDataType

Output data type as single or double

Specify the data type of the output as `single` or `double`. The default is `double`.

## Methods

<code>clone</code>	Create uniform decoder object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties

release	Allow property value and input characteristics changes
step	Decode integer input into quantized floating-point output

## Examples

Decode an encoded sequence:

```
hue = dsp.UniformEncoder;
hue.PeakValue = 2;
hue.NumBits = 4;
hue.OutputDataType = 'Signed integer';
x = (0:0.25:2)'; % Create an input sequence
hud = dsp.UniformDecoder;
hud.PeakValue = 2;
hud.NumBits = 4;
x_encoded = step(hue, x);
% Check that the last element has been saturated.
x_decoded = step(hud, x_encoded);
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Uniform Decoder block reference page. The object properties correspond to the block parameters.

## See Also

`dsp.UniformEncoder`

# dsp.UniformDecoder.clone

---

**Purpose** Create uniform decoder object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a `UniformDecoder` object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object. The clone method creates an instance of an object. The property values, but not internal states, are copied into the new instance of the object.

# dsp.UniformDecoder.getNumInputs

---

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.UniformDecoder.getNumOutputs**

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**      `N = getNumOutputs(H)` returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `UniformDecoder` object `H`.  
The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.UniformDecoder.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Decode integer input into quantized floating-point output

**Syntax**  $Y = \text{step}(H, X)$

**Description**  $Y = \text{step}(H, X)$  reconstructs quantized floating-point output  $Y$  from the encoded integer input  $X$ . Input  $X$  can be real or complex values of the following six integer data types: `uint8`, `uint16`, `uint32`, `int8`, `int16`, or `int32`.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.UniformEncoder

---

<b>Purpose</b>	Quantize and encode floating-point input into integer output
<b>Description</b>	<p>The <code>UniformEncoder</code> object quantizes floating-point input, using the precision you specify in the <code>NumBits</code> property, and encodes the quantized input into integer output. The operations of the uniform encoder adhere to the definition for uniform encoding specified in ITU-T Recommendation G.701.</p> <p>To quantize and encode a floating-point input into an integer output:</p> <ol style="list-style-type: none"><li>1 Define and set up your uniform encoder. See “Construction” on page 5-1218.</li><li>2 Call <code>step</code> to encode the input according to the properties of <code>dsp.UniformEncoder</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.UniformEncoder</code> returns a uniform encoder, <code>H</code>, that quantizes floating-point input samples and encodes them as integers using <math>2N</math>-level quantization, where <math>N</math> is an integer.</p> <p><code>H = dsp.UniformEncoder('PropertyName',PropertyValue,...)</code> returns an uniform encoder, <code>H</code>, with each specified property set to the specified value.</p> <p><code>H = dsp.UniformEncoder(peakvalue,numbits,'PropertyName',PropertyValue,...)</code> returns a uniform encoder, <code>H</code>, with the <code>PeakValue</code> property set to <code>peakvalue</code>, the <code>NumBits</code> property set to <code>numbits</code>, and other specified properties set to the specified values.</p>
<b>Properties</b>	<p><b>PeakValue</b></p> <p>Largest input amplitude to be encoded</p> <p>Specify the largest input amplitude to be encoded, as a nonnegative numeric scalar. If the real or imaginary input are outside of the interval <math>[-P,(1 - 2^{(1-B)})P]</math>, where <math>P</math> is the peak value and <math>B</math> is the value of the <code>NumBits</code> property, the uniform encoder</p>

saturates (independently for complex inputs) at those limits. The default is 1.

## NumBits

Number of bits needed to represent output

Specify the number of bits needed to represent the integer output as an integer value between 2 and 32. The number of levels at which the uniform encoder quantizes the floating-point input is  $2^B$ , where  $B$  is the number of bits. The default is 8.

## OutputDataType

Data type of output

Specify the data type of the output as `Unsigned integer` or `Signed integer`. Unsigned outputs are `uint8`, `uint16`, or `uint32`, and signed outputs are `int8`, `int16`, or `int32`. The quantized inputs are linearly (uniformly) mapped to the intermediate integers in the interval  $[0, 2^{(B-1)}]$  when you set this property to `Unsigned integer`, and in the interval  $[-2^{(B-1)}, 2^{(B-1)} - 1]$  when you set this property to `Signed integer`. The variable  $B$  in both expressions corresponds to the value of the `NumBits` property.

## Methods

<code>clone</code>	Create uniform encoder object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>step</code>	Quantize and encode input

# dsp.UniformEncoder

---

## Examples

Encode a sequence:

```
hue = dsp.UniformEncoder;
hue.PeakValue = 2;
hue.NumBits = 4;
hue.OutputDataType = 'Signed integer';
x = [-1:0.01:1]'; % Create an input sequence
x_encoded = step(hue, x);
plot(x, x_encoded, '.');
xlabel('Input'); ylabel('Encoded Output'); grid
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Uniform Encoder block reference page. The object properties correspond to the block parameters.

## See Also

dsp.UniformDecoder

**Purpose**

Create uniform encoder object with same property values

**Syntax**

`C = clone(H)`

**Description**

`C = clone(H)` creates a `UniformEncoder` object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object.

# dsp.UniformEncoder.getNumInputs

---

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.UniformEncoder.getNumOutputs

---

**Purpose**

Number of outputs of step method

**Syntax**

`N = getNumOutputs(H)`

**Description**

`N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# dsp.UniformEncoder.isLocked

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `UniformEncoder` object `H`.  
The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

# dsp.UniformEncoder.step

---

**Purpose** Quantize and encode input

**Syntax**  $Y = \text{step}(H, X)$

**Description**  $Y = \text{step}(H, X)$  quantizes and encodes the input  $X$  to  $Y$ . Input  $X$  can be real or complex, double-, or single-precision values. The uniform encoder chooses the output data type according to the following table.

Number of Bits	Unsigned Integer	Signed Integer
2 to 8	uint8	int8
9 to 16	uint16	int16
17 to 32	uint32	int32

The row corresponds to the value of the NumBits property, and the column corresponds to the value of the OutputDataType property.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

## Purpose

Solve upper-triangular matrix equation

## Description

The UpperTriangularSolver object solves  $UX = B$  for  $X$  when  $U$  is a square, upper-triangular matrix with the same number of rows as  $B$ .

To solve  $UX = B$ :

- 1 Define and set up your linear system solver. See “Construction” on page 5-1227.
- 2 Call `step` to solve the equation according to the properties of `dsp.UpperTriangularSolver`. The behavior of `step` is specific to each object in the toolbox.

## Construction

`H = dsp.UpperTriangularSolver` returns a linear system solver, `H`, used to solve  $UX = B$  where  $U$  is an upper (or unit-upper) triangular matrix.

`H =`

`dsp.UpperTriangularSolver('PropertyName',PropertyValue,...)` returns a linear system solver, `H`, with each specified property set to the specified value.

## Properties

### OverwriteDiagonal

Replace diagonal elements of input with ones

When you set this property to `true`, the linear system solver replaces the elements on the diagonal of the input,  $U$ , with ones. Set this property to either `true` or `false`. The default is `false`.

### RealDiagonalElements

Indicate that diagonal of complex input is real

When you set this property to `true`, the linear system solver optimizes computation speed if the diagonal elements of complex input,  $U$ , are real. This property applies only when you set the `OverwriteDiagonal` property to `false`. Set this property to either `true` or `false`. The default is `false`.

# dsp.UpperTriangularSolver

---

## **Fixed-Point Properties**

### **RoundingMethod**

Rounding method for fixed-point operations

Specify the rounding method as `Ceiling`, `Convergent`, `Floor`, `Nearest`, `Round`, `Simplest`, or `Zero`. The default is `Floor`.

### **OverflowAction**

Overflow action for fixed-point operations

Specify the overflow action as `Wrap` or `Saturate`. The default is `Wrap`.

### **ProductDataType**

Data type of product

Specify the product data type as `Full precision`, `Same as input`, or `Custom`. The default is `Full precision`.

### **CustomProductDataType**

Product word and fraction lengths

Specify the product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `ProductDataType` property to `Custom`. The default is `numericType([],32,30)`.

### **AccumulatorDataType**

Data type of accumulator

Specify the accumulator data type as `Full precision`, `Same as first input`, `Same as product`, or `Custom`. The default is `Full precision`.

### **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `AccumulatorDataType` property to `Custom`. The default is `numericType([],32,30)`.

## OutputDataType

Data type of output

Specify the output data type as `Same as first input` or `Custom`. The default is `Same as first input`.

## CustomOutputDataType

Output word and fraction lengths

Specify the output fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `OutputDataType` property to `Custom`. The default is `numericType([],16,15)`.

## Methods

<code>clone</code>	Create upper triangular solver object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>step</code>	Solve matrix equation for specified inputs

## Examples

Solve an upper-triangular matrix equation:

```
huptriang = dsp.UpperTriangularSolver;
```

# dsp.UpperTriangularSolver

---

```
u = triu(rand(4, 4));  
b = rand(4, 1);  
% Check that result is the solution to the linear  
% equations.  
x1 = inv(u)*b  
x = step(huptriang, u, b)
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Backward Substitution block reference page. The object properties correspond to the block parameters.

## See Also

[dsp.LowerTriangularSolver](#)

**Purpose** Create upper triangular solver object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates an UpperTriangularSolver object C, with the same property values as H. The `clone` method creates a new unlocked object.

# **dsp.UpperTriangularSolver.getNumInputs**

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.UpperTriangularSolver.getNumOutputs

---

**Purpose**

Number of outputs of step method

**Syntax**

`N = getNumOutputs(H)`

**Description**

`N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# dsp.UpperTriangularSolver.isLocked

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `UpperTriangularSolver` object `H`.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

# dsp.UpperTriangularSolver.step

---

**Purpose** Solve matrix equation for specified inputs

**Syntax**  $X = \text{step}(H,U,B)$

**Description**  $X = \text{step}(H,U,B)$  computes the solution,  $X$ , of the matrix equation  $UX = B$ , where  $U$  is a square, upper-triangular matrix with the same number of rows as the matrix  $B$ .

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

<b>Purpose</b>	Delay input by time-varying fractional number of sample periods
<b>Description</b>	<p>The <code>VariableFractionalDelay</code> object delays the input by a time-varying fractional number of sample periods.</p> <p>To delay the input by a time-varying fractional number of sample periods:</p> <ol style="list-style-type: none"><li>1 Define and set up your variable fractional delay object. See “Construction” on page 5-1237.</li><li>2 Call <code>step</code> to delay the input according to the properties of <code>dsp.VariableFractionalDelay</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.VariableFractionalDelay</code> returns a variable fractional delay System object, <code>H</code>, that delays a discrete-time input by a time-varying fractional number of sample periods.</p> <p><code>H = dsp.VariableFractionalDelay('PropertyName',PropertyValue,...)</code> returns a variable fractional delay System object, <code>H</code>, with each property set to the specified value.</p>
<b>Properties</b>	<p><b>InterpolationMethod</b></p> <p>Interpolation method</p> <p>Specify the method by which the block interpolates between adjacent stored samples to obtain a value for the sample indexed by the input. You can set this property to one of   <code>Linear</code>   <code>FIR</code>   <code>Farrow</code>  . When you set this property to <code>FIR</code>, the object uses the Signal Processing Toolbox <code>intfilt</code> function to compute an FIR filter for interpolation. The default is <code>Linear</code>.</p> <p><b>FilterHalfLength</b></p> <p>FIR interpolation filter half-length</p>

# dsp.VariableFractionalDelay

---

Specify the half-length of the FIR interpolation filter as a positive scalar integer. This property applies only when you set the `InterpolationMethod` property to `FIR`. For periodic signals, a larger value of this property (that is, a higher order filter) yields a better estimate of the delayed output sample. Setting this property to a value between 4 and 6 (that is, a 7th to 11th order filter) is usually adequate. The default is 4.

## **FilterLength**

Length of Farrow filter

Specify the length of the FIR filter implemented using the Farrow structure, as a positive scalar integer. This property applies only when you set the `InterpolationMethod` property to `Farrow`. The default is 4.

## **InterpolationPointsPerSample**

Number of interpolation points per input sample

Specify the number of interpolation points per input sample at which a unique FIR interpolation filter is computed. You must specify the number of interpolation points per input sample as a positive scalar integer. This property applies only when you set the `InterpolationMethod` property to `FIR`. The default is 10.

## **Bandwidth**

Normalized input bandwidth

Specify the bandwidth to which you want to constrain the interpolated output samples. You must enter the bandwidth as a scalar value between 0 and 1. You can use this property to take advantage of the bandlimited frequency content of the input. For example, if the input signal does not have frequency content above  $F_s/4$  (where  $F_s$  is the sampling frequency), you can specify a value of 0.5 for the `Bandwidth` property. A value of 1 for the `Bandwidth` property corresponds to half the sampling frequency ( $F_s$ ). This property applies only when you set the `InterpolationMethod` property to `FIR`. The default is 1.

## InitialConditions

Initial values in memory

Specify the values with which the object's memory is initialized. The dimensions of this property can vary depending on the setting of the `FrameBasedProcessing` property, and whether you want fixed or time-varying initial conditions. The default is 0.

When you set the `FrameBasedProcessing` property to `false`, the object supports N-D input arrays. For an M-by-N-by-P sample-based input array `U`, you can set the `InitialConditions` property as follows:

- To specify fixed initial conditions, set the `InitialConditions` property to a scalar value. The object initializes every sample of every channel in memory using the value you specify.
- The dimensions you specify for time-varying initial conditions depend on the value of the `InterpolationMethod` property:
  - If you set the `InterpolationMethod` property to `Linear`, set the `InitialConditions` property to an array of dimension Mx-by-N-by-P-by-D. The object uses the values in this array to initialize memory samples `U(2:D+1)`, where D is the value of the `MaximumDelay` property.
  - If you set the `InterpolationMethod` property to either `FIR` or `Farrow`, set the `InitialConditions` property to an array of dimension M-by-N-by-P-by-(D+L). The object uses the values in this array to initialize memory samples `U(2:D+1)`, where D is the value of the `MaximumDelay` property. For FIR interpolation, L is the value of the `FilterHalfLength` property. For Farrow interpolation, L equals `floor` of half the value of the `FilterLength` property (`floor(FilterLength/2)`).

When you set the `FrameBasedProcessing` property to `true`, the object treats each of the N input columns as a frame containing M sequential time samples from an independent channel.

# dsp.VariableFractionalDelay

---

For an M-by-N frame-based input matrix U, you can set the `InitialConditions` property as follows:

- To specify fixed initial conditions, set the `InitialConditions` property to a scalar value. The object initializes every sample of every channel in memory using the value you specify.
- The dimensions you specify for time-varying initial conditions depend on the value of the `InterpolationMethod` property. To specify different time-varying initial conditions for each channel, set the `InitialConditions` property as follows:
  - If you set the `InterpolationMethod` property to `Linear`, set the `InitialConditions` property to an array of size 1-by-N-by-D, where D is the value of the `MaximumDelay` property.
  - If you set the `InterpolationMethod` property to `FIR` or `Farrow`, set the `InitialConditions` property to an array of size 1-by-N-by-(D+L), where D is the value of the `MaximumDelay` property. For FIR interpolation, L is the value of the `FilterHalfLength` property. For Farrow interpolation, L equals floor of half the value of the `FilterLength` property (`floor(FilterLength/2)`).

## **MaximumDelay**

Maximum delay

Specify the maximum delay the object can produce for any sample. The maximum delay must be a positive scalar integer value. The object clips input delay values greater than the `MaximumDelay` to the `MaximumDelay`. The default is 100.

## **DirectFeedthrough**

Allow direct feedthrough

When you set this property to `true`, the object allows direct feedthrough. When you set this property to `false`, the object increases the minimum possible delay by one. The default is `true`.

## **FIRSmallDelayAction**

Action for small input delay values in FIR interpolation mode

Specify the action the object should take for small input delay values when using the FIR interpolation method. You can set this property to `Clip` to the minimum value necessary for centered kernel, or `Switch` to linear interpolation if kernel cannot be centered. This property applies only when you set the `InterpolationMethod` property to `FIR`. The default is `Clip` to the minimum value necessary for centered kernel.

## **FarrowSmallDelayAction**

Action for small input delay values in Farrow interpolation mode

Specify the action the object should take for small input delay values when using the Farrow interpolation method. You can set this property to `Clip` to the minimum value necessary for centered kernel, or `Use off-centered kernel`. This property applies only when you set the `InterpolationMethod` property to `Farrow`. The default is `Clip` to the minimum value necessary for centered kernel.

## **FrameBasedProcessing**

Treat input as frame based or sample based

Set this property to `true` to enable frame-based processing. When you do so, the object accepts `M-by-N` input matrices and treats each of the `N` input columns as a frame containing `M` sequential time samples from an independent channel. Set this property to `false` to enable sample-based processing. When you do so, the object supports `N-D` inputs and treats each element of the input as a separate channel. The default is `true`.

## **Fixed-Point Properties**

### **RoundingMethod**

# dsp.VariableFractionalDelay

---

Rounding method for fixed-point operations

Specify the rounding method as one of | Ceiling | Convergent, | Floor | Nearest | Round | Simplest | Zero |. The default is Zero.

## **OverflowAction**

Overflow action for fixed-point operations

Specify the overflow action as one of | Wrap | Saturate |. The default is Wrap.

## **CoefficientsDataType**

Coefficient word and fraction lengths

Specify the coefficients data type as one of | Same word length as input | Custom |. The default is Same word length as input.

## **CustomCoefficientsDataType**

Coefficients word length

Specify the coefficients word length as an `numericType` object with a `Signedness` of `Auto`. If the `InterpolationMethod` is `Linear`, specify that the `numericType` object is unsigned; otherwise the object should be signed. This property applies only when you set the `CoefficientsDataType` property to `Custom`. The default is `numericType([],32)`.

## **ProductPolynomialValueDataType**

Product polynomial values word and fraction lengths

Specify the product polynomial value data type as one of | Same as first input | Custom |. This property applies only when you set the `InterpolationMethod` property to `Farrow`. The default is Same as first input.

## **CustomProductPolynomialValueDataType**

Product polynomial values word and

**fraction lengths** Specify the product polynomial values fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `InterpolationMethod` property to `Farrow` and the `ProductPolynomialValueDataType` property to `Custom`. The default is `numericType([],32,10)`.

## **AccumulatorPolynomialValueDataType**

Accumulator polynomial value word and fraction lengths

Specify the accumulator polynomial value data type as one of `| Same as first input | Custom |`. This property applies only when you set the `InterpolationMethod` property to `Farrow`. The default is `Same as first input`.

## **CustomAccumulatorPolynomialValueDataType**

Accumulator polynomial value word and fraction lengths

Specify the data type of the accumulator polynomial values as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `InterpolationMethod` property to `Farrow` and the `AccumulatorPolynomialValueDataType` property to `Custom`. The default is `numericType([],32,10)`.

## **MultiplicandPolynomialValueDataType**

Multiplicand polynomial value word and fraction lengths

Specify the multiplicand polynomial values data type as one of `| Same as first input | Custom |`. This property applies only when you set the `InterpolationMethod` property to `Farrow`. The default is `Same as first input`.

## **CustomMultiplicandPolynomialValueDataType**

Multiplicand polynomial value word and fraction lengths

Specify the fixed-point data type of the multiplicand polynomial values as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `InterpolationMethod` property to `Farrow` and the

# **dsp.VariableFractionalDelay**

---

MultiplicandPolynomialValueDataType property to Custom. The default is `numericType([],32,10)`.

## **ProductDataType**

Product word and fraction lengths

Specify the product data type as one of | Same as first input | Custom |. The default is Same as first input.

## **CustomProductDataType**

Product word and fraction lengths

Specify the product data type as a scaled `numericType` object with a Signedness of Auto. This property applies only when you set the ProductDataType property to Custom. The default is `numericType([],32,10)`.

## **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator data type as one of | Same as product | Same as first input | Custom |. The default is Same as product.

## **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the fixed-point accumulator data type as a scaled `numericType` object with a Signedness of Auto. This property applies only when you set the AccumulatorDataType property to Custom. The default is `numericType([],32,10)`.

## **OutputDataType**

Output word and fraction lengths

Specify the output data type as one of | Same as accumulator | Same as first input | Custom |. The default is Same as accumulator.

## **CustomOutputDataType**

Output word and fraction lengths

Specify the data type of the output as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies only when you set the `OutputDataType` property to `Custom`. The default is `numericType([],32,10)`.

## Methods

<code>clone</code>	Create variable fractional delay object with same property values
<code>getNumInputs</code>	Number of expected inputs to <code>step</code> method
<code>getNumOutputs</code>	Number of outputs of <code>step</code> method
<code>info</code>	Characteristic information about valid delay range
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>reset</code>	Reset internal states of variable fractional delay object
<code>step</code>	Delay input by time-varying fractional number of sample periods

## Examples

Delay a signal by a varying fractional number of sample periods:

```
hsr = dsp.SignalSource;  
hvfd = dsp.VariableFractionalDelay;  
hLog = dsp.SignalSink;  
  
for ii = 1:10  
    delayedSig = step(hvfd, step(hsr), ii/10);  
    step(hLog, delayedSig);  
end
```

# dsp.VariableFractionalDelay

---

```
end

sigd = hLog.Buffer;

% The output sigd corresponds to the values of the delayed signal
% that are sampled at fixed-time intervals. For visualization
% purposes, we can instead plot the time instants at which the
% amplitudes of signal samples are constant by treating the
% signals as the sampling instants.

stem(hsr.Signal, 1:10, 'b')
hold on;
stem(sigd.', 1:10, 'r');
legend('Original signal',...
      'Variable fractional delayed signal', ...
      'Location','best')
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Variable Fractional Delay block reference page. The object properties correspond to the block properties, except:

When you set the `DirectFeedthrough` property of the `System` object to `true`, the object allows direct feedthrough. This behavior is different from the way the block behaves when you select the corresponding **Disable direct feedthrough by increasing minimum possible delay by one** check box on the block dialog. When you enable this block parameter, the block does not allow direct feedthrough.

Both this object and its corresponding block let you specify whether to process inputs as individual samples or as frames of data. The object uses the `FrameBasedProcessing` property. The block uses the **Input processing** parameter. See “Set the `FrameBasedProcessing` Property of a `System` object” for more information.

## See Also

`dsp.VariableIntegerDelay` | `dsp.Delay` | `dsp.DelayLine`

**Purpose** Create variable fractional delay object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a `VariableFractionalDelay` System object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with uninitialized states.

# **dsp.VariableFractionalDelay.getNumInputs**

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.VariableFractionalDelay.getNumOutputs**

---

**Purpose**

Number of outputs of step method

**Syntax**

`N = getNumOutputs(H)`

**Description**

`N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# **dsp.VariableFractionalDelay.info**

---

**Purpose** Characteristic information about valid delay range

**Syntax** `S = info(H)`

**Description** `S = info(H)` returns a structure, `S`, containing characteristic information about the `VariableFractionalDelay` System object, `H`. `S` has one field, `ValidDelayRange` which is a string containing the possible range of delay values based on the current property values of the `VariableFractionalDelay` object. The `ValidDelayRange` is in the format `[MinValidDelay, MaxValidDelay]`. The object clips all input delay values to be within this `ValidDelayRange`.

# dsp.VariableFractionalDelay.isLocked

---

<b>Purpose</b>	Locked status for input attributes and nontunable properties
<b>Syntax</b>	<code>isLocked(H)</code>
<b>Description</b>	<p><code>isLocked(H)</code> returns the locked state of the <code>VariableFractionalDelay</code> System object.</p> <p>The <code>isLocked</code> method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the <code>step</code> method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the <code>isLocked</code> method returns a true value.</p>

# dsp.VariableFractionalDelay.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

**Purpose**

Reset internal states of variable fractional delay object

**Syntax**

`reset(H)`

**Description**

`reset(H)` resets the internal states of the `VariableFractionalDelay` System object `H` to their initial values.

# dsp.VariableFractionalDelay.step

---

**Purpose** Delay input by time-varying fractional number of sample periods

**Syntax**  $Y = \text{step}(H,X,D)$

**Description**  $Y = \text{step}(H,X,D)$  delays the input  $X$  by  $D$  samples, where  $D$  should be less than or equal to the value specified in the `MaximumDelay` property.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

<b>Purpose</b>	Delay input by time-varying integer number of sample periods
<b>Description</b>	<p>The <code>VariableIntegerDelay</code> object delays input by time-varying integer number of sample periods.</p> <p>To delay the input by a time-varying integer number of sample periods:</p> <ol style="list-style-type: none"><li>1 Define and set up your variable integer delay object. See “Construction” on page 5-1255.</li><li>2 Call <code>step</code> to delay the input according to the properties of <code>dsp.VariableIntegerDelay</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.VariableIntegerDelay</code> returns a variable integer delay System object, <code>H</code>, that delays discrete-time input by a time-varying integer number of sample periods.</p> <p><code>H = dsp.VariableIntegerDelay('PropertyName',PropertyValue,...)</code> returns a variable integer delay System object, <code>H</code>, with each property set to the specified value.</p>
<b>Properties</b>	<p><b>MaximumDelay</b></p> <p>Maximum delay</p> <p>Specify the maximum delay the object can produce for any sample. The maximum delay must be a positive scalar integer value. The object clips input delay values greater than the <code>MaximumDelay</code> to the <code>MaximumDelay</code>. The default is 100.</p> <p><b>InitialConditions</b></p> <p>Initial values in memory</p> <p>Specify the values with which the object’s memory is initialized. The dimensions of this property can vary depending on the setting of the <code>FrameBasedProcessing</code> property, and whether you want fixed or time-varying initial conditions. The default is 0.</p>

# dsp.VariableIntegerDelay

---

When you set the `FrameBasedProcessing` property to `false`, the object supports N-D input arrays. For an M-by-N-by-P sample-based input array `U`, you can set the `InitialConditions` property as follows:

- To specify fixed initial conditions, set the `InitialConditions` property to a scalar value. The object initializes every sample of every channel in memory using the value you specify.
- To specify time-varying initial conditions, set the `InitialConditions` property to an array of dimension M-by-N-by-P-by-D. The object uses the values in this array to initialize memory samples `U(2:D+1)`, where D is the value of the `MaximumDelay` property.

When you set the `FrameBasedProcessing` property to `true`, the object treats each of the N input columns as a frame containing M sequential time samples from an independent channel. For an M-by-N frame-based input matrix `U`, you can set the `InitialConditions` property as follows:

- To specify fixed initial conditions, set the `InitialConditions` property to a scalar value. The object initializes every sample of every channel in memory using the value you specify.
- To specify different time-varying initial conditions for each channel, set the `InitialConditions` property to an array of size 1-by-N-by-D, where D is the value of the `MaximumDelay` property.

## **DirectFeedthrough**

Allow direct feedthrough

When you set this property to `true`, the object allows direct feedthrough. When you set this property to `false`, the object increases the minimum possible delay by one. The default is `true`.

## **FrameBasedProcessing**

Treat input as frame based or sample based

Set this property to `true` to enable frame-based processing. When you do so, the object accepts M-by-N input matrices and treats each of the N input columns as a frame containing M sequential time samples from an independent channel. Set this property to `false` to enable sample-based processing. When you do so, the object supports N-D inputs and treats each element of the input as a separate channel. The default is `true`.

## Methods

<code>clone</code>	Create variable integer delay object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>reset</code>	Reset internal states of variable integer delay object
<code>step</code>	Delay input by time-varying integer number of sample periods

## Examples

Delay a signal by a varying integer number of sample periods:

```
h = dsp.VariableIntegerDelay;  
x = 1:100;  
ii = 0;  
k = 0;  
yout = [];  
  
while(ii+10 <= 100)
```

# dsp.VariableIntegerDelay

---

```
        y = step(h, x(ii+1:ii+10)', k*ones(10,1));
        yout = [yout;y];
        ii = ii+10;
        k = k+1;
    end

    stem(x, 'b');
    hold on; stem(yout, 'r');
    legend('Original Signal', 'Variable Integer Delayed Signal')
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Variable Integer Delay block reference page. The object properties correspond to the block properties, except:

When you set the `DirectFeedthrough` property of the System object to `true`, the object allows direct feedthrough. This behavior is different from the way the block behaves when you select the corresponding **Disable direct feedthrough by increasing minimum possible delay by one** check box on the block dialog. When you enable this block parameter, the block does not allow direct feedthrough.

Both this object and its corresponding block let you specify whether to process inputs as individual samples or as frames of data. The object uses the `FrameBasedProcessing` property. The block uses the **Input processing** parameter. See “Set the FrameBasedProcessing Property of a System object” for more information.

## See Also

[dsp.VariableFractionalDelay](#) | [dsp.Delay](#) | [dsp.DelayLine](#)

**Purpose** Create variable integer delay object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a `VariableIntegerDelay` System object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with uninitialized states.

# **dsp.VariableIntegerDelay.getNumInputs**

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.VariableIntegerDelay.getNumOutputs**

---

**Purpose**

Number of outputs of step method

**Syntax**

`N = getNumOutputs(H)`

**Description**

`N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# **dsp.VariableIntegerDelay.isLocked**

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `VariableIntegerDelay` System object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

# **dsp.VariableIntegerDelay.reset**

---

**Purpose**            Reset internal states of variable integer delay object

**Syntax**            reset(H)

**Description**       reset(H) resets the internal states of the VariableIntegerDelay System object H to their initial values.

**Purpose** Delay input by time-varying integer number of sample periods

**Syntax**  $Y = \text{step}(H, X, D)$

**Description**  $Y = \text{step}(H, X, D)$  delays the input  $X$  by  $D$  samples, where  $D$  should be less than or equal to the value specified in the `MaximumDelay` property and greater than or equal to 0. The object clips delay values greater than the `MaximumDelay` to the `MaximumDelay`, and clips values less than zero to zero. If you enter a noninteger delay value, the object rounds that value to the nearest integer value.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.Variance

---

## Purpose

Variance of input or sequence of inputs

## Description

The Variance object computes variance for an input or sequence of inputs.

To compute the variance of an input or sequence of inputs:

- 1 Define and set up your variance System object. See “Construction” on page 5-1266.
- 2 Call `step` to compute the variance according to the properties of `dsp.Variance`. The behavior of `step` is specific to each object in the toolbox.

## Construction

`H = dsp.Variance` returns a variance System object, `H`, that computes the variance of an input or a sequence of inputs over the specified Dimension.

`H = dsp.Variance('PropertyName',PropertyValue,...)` returns a variance System object, `H`, with each specified property set to the specified value.

## Properties

### RunningVariance

Enable calculation over time

Set this property to `true` to enable variance calculation over successive calls to the `step` method. The default is `false`.

### ResetInputPort

Enable reset input port

Set this property to `true` to enable reset input port. When you set the property to `true`, specify a reset input for the `step` method. The running variance resets anytime the variance object achieves the condition you specify for the `ResetCondition` property. This property applies when you set the `RunningVariance` property to `true`. The default is `false`.

### ResetCondition

Reset condition for running variance mode

Specify which event resets the running variance as one of | Rising edge | Falling edge | Either edge | Non-zero |. This property applies when you set the ResetInputPort property to true.

## **Dimension**

Dimension to operate along

Specify how the object performs the variance calculation over the data as one of | All | Row | Column | Custom |. This property applies when you set the RunningVariance property to false. The default is Column.

## **CustomDimension**

Numerical dimension to operate along

Specify the input signal dimension (one-based value) the object uses to compute variance. The cannot exceed the number of dimensions in the input signal. This property applies when you set the Dimension property to Custom. The default is 1.

## **ROIProcessing**

Enable region-of-interest processing

Set this property to true to enable calculating the variance within a particular region of each image. This property applies when you set the RunningVariance property to false and the Dimension property to All. The default is false. Full ROI processing support requires a Computer Vision System Toolbox license. With only the DSP System Toolbox license, Rectangles is the only selection for the ROIForm property.

## **ROIForm**

Define the type of region of interest.

Specify the type of region of interest as one of | Rectangles | Lines | Label matrix | Binary mask |. This property applies

when you set the `ROIProcessing` property to `true`. The default is `Rectangle`.

## **ROIPortion**

Calculate over entire ROI or just perimeter

Specify the region over which to calculate variance as one of `| Entire ROI | ROI perimeter |`. This property applies when you set the `ROIForm` property to `Rectangles`. The default is `Entire ROI`.

## **ROIStatistics**

Statistics for each ROI or one for all ROIs

Specify if statistics calculations are one of `| Individual statistics for each ROI | Single statistic for all ROIs |`. This property applies when `ROIForm` property is not `Binary mask`. The default is `Individual statistics for each ROI`.

## **ValidityOutputPort**

Enable output of validity check of ROI or label numbers

Indicate whether to return the validity of the specified ROI being completely inside image when the `ROIForm` property is `Lines` or `Rectangles`. Indicate whether to return the validity of the specified label numbers when the `ROIForm` property is `Label Matrix`. This property applies when you set the `ROIForm` property to anything except `Binary Mask`. The default is `false`.

## **FrameBasedProcessing**

Enable frame-based processing

Set this property to `true` to enable frame-based processing. Set this property to `false` to enable sample-based processing. This property applies when you set the `RunningVariance` property to `true`. The default is `true`.

## Fixed-Point Properties

### RoundingMethod

Rounding method for fixed-point operations

Specify the rounding method as one of | Ceiling | Convergent | Floor | Nearest | Round | Simplest | Zero |. The default is Floor

### OverflowAction

Overflow action for fixed-point operations

Specify the overflow action as one of | Wrap | Saturate |. The default is Wrap.

### InputSquaredProductDataType

Input-squared product word and fraction lengths

Specify the input-squared product fixed-point data type as one of | Same as input | Custom |. The default is Same as input.

### CustomInputSquaredProductDataType

Input-squared product word and fraction lengths

Specify the input-squared product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `InputSquaredProductDataType` property to `Custom`. The default is `numericType([],32,15)`.

### InputSumSquaredProductDataType

Input-sum-squared product word and fraction lengths

Specify the input-sum-squared product fixed-point data type as one of | Same as input-squared product | Custom |. The default is Same as input-squared product.

### CustomInputSumSquaredProductDataType

Input-sum-squared product word and fraction lengths

Specify the input-sum-squared product fixed-point type as a scaled `numerictype` object with a `Signedness` of `Auto`. This property applies when you set the `InputSumSquaredProductDataType` property to `Custom`. The default is `numerictype([],32,23)`.

## **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point data type as one of | `Same as input-squared product` | `Same as input` | `Custom` |. The default is `Same as input-squared product`.

## **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled `numerictype` object with a `Signedness` of `Auto`. This property applies when you set the `AccumulatorDataType` property to `Custom`. The default is `numerictype([],32,0)`.

## **OutputDataType**

Output word and fraction lengths

Specify the output fixed-point data type as one of | `Same as input-squared product` | `Same as input` | `Custom` |. The default is `Same as input-squared product`.

## **CustomOutputDataType**

Output word and fraction lengths

Specify the output fixed-point type as a scaled `numerictype` object with a `Signedness` of `Auto`. This property only applies when the `OutputDataType` property to `Custom`. The default is `numerictype([],16,0)`.

## Methods

<code>clone</code>	Create variance object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>reset</code>	Reset variance to zero
<code>step</code>	Variance of input

## Examples

Compute the running variance for a signal:

```
hvar = dsp.Variance;  
hvar.RunningVariance = true;  
x = randn(100,1);  
y = step(hvar, x);  
% y(i) is the running variance of all values in the vector x(1:i)
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Variance block reference page. The object properties correspond to the block parameters, except:

- **Treat sample-based row input as a column** block parameter is not supported by the `dsp.Variance` object.
- **Reset port** block parameter corresponds to both the `ResetCondition` and the `ResetInputPort` object properties.

Both this object and its corresponding block let you specify whether to process inputs as individual samples or as frames of data. The object

## dsp.Variance

---

uses the `FrameBasedProcessing` property. The block uses the **Input processing** parameter. See “Set the `FrameBasedProcessing` Property of a System object” for more information.

### See Also

[dsp.Mean](#) | [dsp.RMS](#) | [dsp.StandardDeviation](#)

**Purpose** Create variance object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a Variance System object `C`, with the same property values as `H`. The clone method creates a new unlocked object with uninitialized states.

# dsp.Variance.getNumInputs

---

**Purpose**            Number of expected inputs to step method

**Syntax**            `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the step method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

**Purpose**

Number of outputs of step method

**Syntax**

`N = getNumOutputs(H)`

**Description**

`N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# dsp.Variance.isLocked

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** isLocked(H)

**Description** isLocked(H) returns the locked state of the Variance System object.  
The isLocked method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the step method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the isLocked method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

## **dsp.Variance.reset**

---

**Purpose**            Reset variance to zero

**Syntax**            reset(H)

**Description**       reset(H) sets the variance to zero when the RunningVariance property is true.

## Purpose

Variance of input

## Syntax

```
Y = step(H,X)
Y = step(H,X,R)
VAR2D = step(H,X,ROI)
VAR2D = step(H,X,LABEL,LABELNUMBERS)
[VAR2D,FLAG] = step(H,X,ROI)
[VAR2D,FLAG] = step(H,X,LABEL,LABELNUMBERS)
```

## Description

`Y = step(H,X)` computes the variance, `Y`, of input `X` over successive calls to the `step` method, when the `RunningVariance` property is true.

`Y = step(H,X,R)` resets its state based on the value of reset signal `R`, the `ResetInputPort` property and the `ResetCondition` property. This option applies when the `RunningVariance` property is true and the `ResetInputPort` property is set to true.

`VAR2D = step(H,X,ROI)` computes the variance of input image, `X`, within the given region of interest, `ROI`, when the `ROIProcessing` property is true and the `ROIForm` property is `Lines`, `Rectangles` or `Binary mask`. Full ROI processing support requires a Computer Vision System Toolbox license. With only the DSP System Toolbox license, the `ROIForm` property only supports `Rectangles`.

`VAR2D = step(H,X,LABEL,LABELNUMBERS)` computes the variance of input image, `X`, for region labels contained in vector `LABELNUMBERS`, with matrix `LABEL` marking pixels of different regions. This option is available when the `ROIProcessing` property is true and the `ROIForm` property is `Label matrix`.

`[VAR2D,FLAG] = step(H,X,ROI)` returns `FLAG` which indicates whether the given region of interest is within the image bounds when both the `ROIProcessing` and `ValidityOutputPort` properties are true and the `ROIForm` property is set to `Lines`, `Rectangles` or `Binary mask`.

`[VAR2D,FLAG] = step(H,X,LABEL,LABELNUMBERS)` returns `FLAG` which indicates whether the input label numbers are valid when both the `ROIProcessing` and `ValidityOutputPort` properties are true and the `ROIForm` property is set to `Label matrix`.

## dsp.Variance.step

---

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

<b>Purpose</b>	Vector quantizer codeword for given index value
<b>Description</b>	<p>The <code>VectorQuantizerDecoder</code> object returns the vector quantizer codeword for a given index value. Each column of the <code>Codebook</code> property is a codeword.</p> <p>To obtain the vector quantizer codeword for a given index value:</p> <ol style="list-style-type: none"><li>1 Define and set up your vector quantizer decoder. See “Construction” on page 5-1281.</li><li>2 Call <code>step</code> to get the vector quantizer codeword according to the properties of <code>dsp.VectorQuantizerDecoder</code>. The behavior of <code>step</code> is specific to each object in the toolbox.</li></ol>
<b>Construction</b>	<p><code>H = dsp.VectorQuantizerDecoder</code> creates a vector quantizer decoder System object, <code>H</code>, that returns a vector quantizer codeword corresponding to a given, zero-based index value.</p> <p><code>H = dsp.VectorQuantizerDecoder('PropertyName',PropertyValue,...)</code> returns a vector quantizer decoder, <code>H</code>, with each specified property set to the specified value.</p>
<b>Properties</b>	<p><b>CodebookSource</b></p> <p>Source of codebook values</p> <p>Specify the codebook source as <code>Property</code> or <code>Input port</code>. When you select <code>Property</code>, the object reads the codebook from the <code>codebook</code> property. When you select <code>Input port</code>, the object reads the codebook from the input of the <code>step</code> method.</p> <p>The default is <code>Property</code>.</p> <p><b>Codebook</b></p> <p><code>codebook</code></p>

# dsp.VectorQuantizerDecoder

---

Specify quantized output values as a  $k$ -by- $N$  matrix, where  $k \geq 1$  and  $N \geq 1$ . Each column of the codebook matrix is a codeword, and each codeword corresponds to an index value. This property applies when you set the CodebookSource property to Property. The default is:

$$\begin{bmatrix} 1.5 & 13.3 & 136.4 & 6.8 \\ 2.5 & 14.3 & 137.4 & 7.8 \\ 3.5 & 15.3 & 138.4 & 8.8 \end{bmatrix}$$

This property is tunable.

## OutputDataType

Data type of codebook and quantized output

Specify the data type of the codebook and quantized output values as: Same as input, double, single or Custom. This property applies only when you set CodebookSource to Property. The default is double.

## Fixed-Point Properties

### CustomOutputDataType

Output word and fraction lengths

Specify the output fixed-point type as a signed or unsigned numeric type object. This property applies only when you set the OutputDataType property to Custom. The default is numeric type (true, 16).

## Methods

clone	Create vector quantizer decoder object with same property values
getNumInputs	Number of expected inputs to step method
getNumOutputs	Number of outputs of step method

isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
step	Quantized output values corresponding to input indices

## Examples

Given index values as an input, determine the corresponding vector quantized codewords for a specified codebook:

```
hvfdec = dsp.VectorQuantizerDecoder;  
hvfdec.Codebook = [1 10 100;2 20 200;3 30 300];  
indices = uint8([1 0 2 0]);  
qout = step(hvfdec, indices)
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the [Vector Quantizer Decoder](#) block reference page. The object properties correspond to the block parameters, except:

There is no object property that directly corresponds to the **Action for out of range index value** block parameter. The object sets any index values less than 0 to 0 and any index values greater than or equal to  $N$  to  $N-1$ .

## See Also

[dsp.VectorQuantizerEncoder](#) | [dsp.ScalarQuantizerDecoder](#)

# **dsp.VectorQuantizerDecoder.clone**

---

**Purpose** Create vector quantizer decoder object with same property values

**Syntax**

**Description** `C = clone(H)` creates a `VectorQuantizerDecoder` object `C`, with the same property values as `H`. The `clone` method creates a new unlocked object with uninitialized states.

# **dsp.VectorQuantizerDecoder.getNumInputs**

---

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.VectorQuantizerDecoder.getNumOutputs**

---

**Purpose**                Number of outputs of step method

**Syntax**                `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `VectorQuantizerDecoder` object `H`.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.VectorQuantizerDecoder.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

**Purpose**

Quantized output values corresponding to input indices

**Syntax**

$Q = \text{step}(H, I)$   
 $Q = \text{step}(H, I, C)$

**Description**

$Q = \text{step}(H, I)$  returns the quantized output values  $Q$  corresponding to the input indices  $I$ . The data type of  $I$  can be `uint8`, `uint16`, `uint32`, `int8`, `int16`, or `int32`. The `OutputDataType` property determines the data type of  $Q$ .

$Q = \text{step}(H, I, C)$  uses input  $C$  as the codebook values when the `CodebookSource` property is `Input port`. The data type of  $C$  can be `double`, `single`, or `fixed-point`. The output  $Q$  has the same data type as the codebook input  $C$ .

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.VectorQuantizerEncoder

---

**Purpose** Vector quantization encoding

**Description** The `VectorQuantizerEncoder` object performs vector quantization encoding. The object finds the nearest codeword by computing a distortion based on Euclidean or weighted Euclidean distance.

To perform vector quantization encoding:

- 1 Define and set up your vector quantizer encoder. See “Construction” on page 5-1290.
- 2 Call `step` to perform the quantization encoding according to the properties of `dsp.VectorQuantizerEncoder`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.VectorQuantizerEncoder` returns a vector quantizer encoder System object, `H`. This object finds a zero-based index of the nearest codeword for each given input column vector.

`H = dsp.VectorQuantizerEncoder('PropertyName',PropertyValue,...)` returns a vector quantizer encoder System object, `H`, with each specified property set to the specified value.

## Properties

### CodebookSource

Source of codebook values

Specify how to determine the codebook values as `Property` or `Input port`. The default is `Property`.

### Codebook

Codebook

Specify the codebook to which the input column vector or matrix is compared, as a  $k$ -by- $N$  matrix. Each column of the codebook matrix is a codeword, and each codeword corresponds to an index value. The codeword vectors must have the same number of rows as the input. The first codeword vector corresponds to an index

value of 0, the second codeword vector corresponds to an index value of 1, and so on. This property applies when you set the CodebookSource property to Property. The default is:

$$\begin{bmatrix} 1.5 & 13.3 & 136.4 & 6.8 \\ 2.5 & 14.3 & 137.4 & 7.8 \\ 3.5 & 15.3 & 138.4 & 8.8 \end{bmatrix}$$

This property is tunable.

## **DistortionMeasure**

Distortion calculation method

Specify how to calculate the distortion as Squared error or Weighted squared error. If you set this property to Squared error, the object calculates the distortion by evaluating the Euclidean distance between the input column vector and each codeword in the codebook. If you set this property to Weighted squared error, the object calculates the distortion by evaluating a weighted Euclidean distance using a weighting factor to emphasize or deemphasize certain input values. The default is Squared error.

## **WeightsSource**

Source of weighting factor

Specify how to determine weighting factor as Property or Input port. This property applies when you set the DistortionMeasure property to Weighted squared error. The default is Property.

## **Weights**

Weighting factor

Specify the weighting factor as a vector of length equal to the number of rows of the input. This property applies when you set the DistortionMeasure property to Weighted squared error and WeightsSource property is Property. The default is [1 1 1]. This property is tunable.

# dsp.VectorQuantizerEncoder

---

## **TiebreakerRule**

Behavior when input column vector is equidistant from two codewords.

Specify whether to represent the input column vector by the lower index valued codeword or higher indexed valued codeword when an input column vector is equidistant from two codewords. You can set this property to `Choose the lower index` or `Choose the higher index`. The default is `Choose the lower index`.

## **CodewordOutputPort**

Enable output of codeword value

Set this property to `true` to output the codeword vectors nearest to the input column vectors. The default is `false`.

## **QuantizationErrorOutputPort**

Enable output of quantization error

Set this property to `true` to output the quantization error value that results when the object represents the input column vector by the nearest codeword. The default is `false`.

## **OutputIndexDataType**

Data type of index output

Specify the data type of the index output as: `int8`, `uint8`, `int16`, `uint16`, `int32`, `uint32`. The default is `int32`.

## **Fixed-Point Properties**

### **RoundingMethod**

Rounding method for fixed-point operations

Specify the rounding method as `Ceiling`, `Convergent`, `Floor`, `Nearest`, `Round`, `Simplest` or `Zero`. The default is `Floor`.

### **OverflowAction**

Overflow action for fixed-point operations

Specify the overflow action as `Wrap` or `Saturate`. The default is `Wrap`.

## **ProductDataType**

Product word and fraction lengths

Specify the product fixed-point data type as `Same as input` or `Custom`. The default is `Same as input`.

## **CustomProductDataType**

Product word and fraction lengths

Specify the product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `ProductDataType` property to `Custom`.

## **AccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point data type as `Same as input`, or `Custom`. The default is `Same as product`.

## **CustomAccumulatorDataType**

Accumulator word and fraction lengths

Specify the accumulator fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `AccumulatorDataType` property to `Custom`.

## **Methods**

<code>clone</code>	Create vector quantizer encoder object with same property values
<code>getNumInputs</code>	Number of expected inputs to <code>step</code> method
<code>getNumOutputs</code>	Number of outputs of <code>step</code> method

# dsp.VectorQuantizerEncoder

---

isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
step	Quantization region to which input belongs

## Examples

Find the indices of nearest codewords based on Euclidean distances:

```
hvfqenc = dsp.VectorQuantizerEncoder(...
'Codebook', [-1 -1 1 1;1 -1 -1 1], ...
'CodewordOutputPort', true, ...
'QuantizationErrorOutputPort', true, ...
'OutputIndexDataType', 'uint8');
% Generate an input signal with some additive noise
x = sign(rand(2,40)-0.5) + 0.1*randn(2,40);
[ind, cw, err] = step(hvfqenc, x);
plot(cw(1,:), cw(2,:), 'r0', x(1,:), x(2,:), 'g. ');
legend('Quantized', 'Inputs', 'location', 'best');
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Vector Quantizer Encoder block reference page. The object properties correspond to the block parameters.

## See Also

[dsp.VectorQuantizerDecoder](#) | [dsp.ScalarQuantizerEncoder](#)

**Purpose**

Create vector quantizer encoder object with same property values

**Syntax****Description**

`C = clone(H)` creates a `VectorQuantizerEncoder` object `C`, with the same property values as `H`. The clone method creates a new unlocked object.

# **dsp.VectorQuantizerEncoder.getNumInputs**

---

**Purpose**                Number of expected inputs to `step` method

**Syntax**                `N = getNumInputs(H)`

**Description**        `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the `step` method

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.VectorQuantizerEncoder.getNumOutputs**

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, N, of the step method

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

# **dsp.VectorQuantizerEncoder.isLocked**

---

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the `VectorQuantizerEncoder` System object `H`.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a System object in code generated from MATLAB, but once you release its resources, you cannot use that System object again.

---

# dsp.VectorQuantizerEncoder.step

---

**Purpose** Quantization region to which input belongs

**Syntax**

```
INDEX = step(H,INPUT)
INDEX = step(H,...,CODEBOOK)
INDEX = step(H,...,WEIGHTS)
[... , CODEWORD] = step(H, ...)
[... , QERR] = step(H, ...)
```

**Description** `INDEX = step(H,INPUT)` returns `INDEX`, a scalar or column vector representing the quantization region(s) to which `INPUT` belongs. `INPUT` can be a column vector of size  $k$ -by-1 or an  $M$  multichannel matrix of dimensions  $k$ -by- $M$ , where  $k$  is the length of each codeword in the codebook. All inputs to the object can be real floating-point or fixed-point values and must be of the same data type. The output index values can be signed or unsigned integers.

`INDEX = step(H,...,CODEBOOK)` uses the codebook given in input `CODEBOOK`, a  $k$ -by- $N$  matrix with  $N$  codewords each of length  $k$ . This option is available when the `CodebookSource` property is `Input port`.

`INDEX = step(H,...,WEIGHTS)` uses the input vector `WEIGHTS` to emphasize or de-emphasize certain input values when calculating the distortion measure. `WEIGHTS` must be a vector of length equal to the number of rows of `INPUT`. This option is available when the `DistortionMeasure` property is `Weighted squared error` and the `WeightsSource` property is `Input port`.

`[... , CODEWORD] = step(H, ...)` outputs the `CODEWORD` values that correspond to each index value when the `CodewordOutputPort` property is `true`.

`[... , QERR] = step(H, ...)` outputs the quantization error `QERR` for each input value when the `QuantizationErrorOutputPort` property is `true`.

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# dsp.Window

---

**Purpose** Window object

**Description** The Window object applies a window to an input signal.

To apply a window to an input signal:

- 1 Define and set up your window. See “Construction” on page 5-1302.
- 2 Call `step` to apply the window according to the properties of `dsp.Window`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.Window` returns a window object, `H`, that applies a Hamming window with symmetric sampling.

`H = dsp.Window('PropertyName',PropertyValue, ...)` returns a window object, `H`, with each property set to the specified value.

`H = dsp.Window(WINDOW,'PropertyName',PropertyValue, ...)` returns a window object, `H`, with the `WindowFunction` property set to `WINDOW` and other properties set to the specified values.

## Properties

### WindowFunction

Type of window

Specify the type of window to apply as Bartlett, Blackman, Boxcar, Chebyshev, Hamming, Hann, Hanning, Kaiser, Taylor, Triang. This property is tunable. The default is Hamming.

### WeightsOutputPort

Enable the output of window weights

Set this property to `true` to output the window weights. The weights are an  $M$ -by-1 vector with  $M$  equal to the first dimension of the input. The default is `false`.

### StopbandAttenuation

Level of stopband attenuation in decibels

Specify the level of stopband attenuation in decibels. This property only applies when the `WindowFunction` property is `Chebyshev`. The default is 50. This property is tunable.

## **Beta**

Kaiser window parameter

Specify the Kaiser window parameter as a real number. Increasing the absolute value of `Beta` widens the mainlobe and decreases the amplitude of the window sidelobes in the window's frequency magnitude response. This property only applies when `WindowFunction` property is `Kaiser`. The default is 10. This property is tunable.

## **NumConstantSidelobes**

Number of constant sidelobes

Specify the number of constant sidelobes as an integer greater than zero. This property only applies when `WindowFunction` property is `Taylor`. The default is 4. This property is tunable.

## **MaximumSidelobeLevel**

Maximum sidelobe level relative to mainlobe

Specify, in decibels, the maximum sidelobe level relative to the mainlobe as a real number less than or equal to zero. The default is -30, which produces sidelobes with peaks 30 dB down from the mainlobe peak. This property only applies when `WindowFunction` property is `Taylor`. This property is tunable.

## **Sampling**

Window sampling for generalized-cosine windows

Specify the window sampling for generalized-cosine windows as `Symmetric` or `Periodic`. This property only applies when `WindowFunction` property is `Blackman`, `Hamming`, `Hann`, or `Hanning`. This property is tunable.

## **Fixed-Point Properties**

### **FullPrecisionOverride**

Full precision override for fixed-point arithmetic

Specify whether to use full precision rules. If you set `FullPrecisionOverride` to `true`, which is the default, the object computes all internal arithmetic and output data types using full precision rules. These rules provide the most accurate fixed-point numerics. It also turns off the display of other fixed-point properties because they do not apply individually. These rules guarantee that no quantization occurs within the object. Bits are added, as needed, to ensure that no roundoff or overflow occurs. If you set `FullPrecisionOverride` to `false`, fixed-point data types are controlled through individual fixed-point property settings. For more information, see “Full Precision for Fixed-Point System Objects”.

### **RoundingMethod**

Rounding method for fixed-point operations

Specify the rounding method as one of `Ceiling`, `Convergent`, `Floor`, `Nearest`, `Round`, `Simplest`, or `Zero`. The default is `Floor`. This property applies only if the object is not in full precision mode.

### **OverflowAction**

Overflow action for fixed-point operations

Specify the overflow action as one of `Wrap` or `Saturate`. The default is `Wrap`. This property applies only if the object is not in full precision mode.

### **WindowDataType**

Window word and fraction lengths

Specify the window fixed-point data type as one of `Same word length as input` or `Custom`. The default is `Same word length as input`.

## **CustomWindowDataType**

Window word and fraction lengths

Specify the window fixed-point type as a `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `WindowDataType` property to `Custom`. The default is `numericType([],16,15)`.

## **ProductDataType**

Product word and fraction lengths

Specify the product fixed-point data type as one of `Full precision`, `Same as input`, or `Custom`. The default is `Full precision`.

## **CustomProductDataType**

Product word and fraction lengths

Specify the product fixed-point type as a scaled `numericType` object with a `Signedness` of `Auto`. This property applies when you set the `ProductDataType` property to `Custom`. The default is `numericType([],16,15)`.

## **OutputDataType**

Output data type

Specify the output fixed-point data type as one of `Same as product`, `Same as input`, `Custom`. The default is `Same as product`.

## **CustomOutputDataType**

Output word and fraction lengths

Specify the output fixed-point type as a `numericType` object with a `Signedness` of `Auto`. This property applies when you

# dsp.Window

---

set the `OutputDataType` property to `Custom`. The default is `numericType([],16,15)`.

## Methods

<code>clone</code>	Create window object with same property values
<code>getNumInputs</code>	Number of expected inputs to step method
<code>getNumOutputs</code>	Number of outputs of step method
<code>isLocked</code>	Locked status for input attributes and nontunable properties
<code>release</code>	Allow property value and input characteristics changes
<code>step</code>	Multiply input by window

## Examples

Apply Hamming window to input signal:

```
hwin = dsp.Window( ...  
'WindowFunction', 'Hamming', ...  
'WeightsOutputPort',true);  
x = rand(64,1);  
[y, w] = step(hwin, x);  
% View the window's time and frequency domain responses  
wvtool(w);
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the [Window Function block reference page](#). The object properties correspond to the block parameters, except:

- **Operation** — The window object does not support the `Generate window` option.
- **Operation** — The `Generate and apply window` option on the block corresponds to the `WeightsOutputPort` property set to `true` on the window object.

- The window object only supports frame-based processing.

## See Also

`dsp.FFT` | `sigwin.bartlett` | `sigwin.blackman` | `sigwin.chebwin` |  
`sigwin.hamming` | `sigwin.hann` | `sigwin.kaiser` | `sigwin.taylorwin`  
| `sigwin.triang` | `wvtool`

# **dsp.Window.clone**

---

**Purpose** Create window object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a window object, `C`, with the same property values as `H`. The clone method creates a new unlocked object.

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, `N`, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# dsp.Window.getNumOutputs

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**        `N = getNumOutputs(H)` returns the number of outputs, `N`, of the `step` method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the window object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.Window.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Multiply input by window

**Syntax**  $Y = \text{step}(H,X)$   
 $[Y, W] = \text{step}(H,X)$

**Description**  $Y = \text{step}(H,X)$  generates the windowed output,  $Y$ , of the input,  $X$ , using the specified window.

$[Y, W] = \text{step}(H,X)$  returns the window values  $W$  when the `WeightsOutputPort` property is true.

# dsp.ZeroCrossingDetector

---

**Purpose** Zero crossing detector

**Description** The ZeroCrossingDetector object counts the number of times the signal crosses zero, or changes sign. The zero crossing detector supports both floating-point and fixed-point data types.

To count the number of times a signal crosses zero or changes sign:

- 1 Define and set up your zero crossing detector. See “Construction” on page 5-1314.
- 2 Call `step` to count the number of times according to the properties of `dsp.ZeroCrossingDetector`. The behavior of `step` is specific to each object in the toolbox.

**Construction** `H = dsp.ZeroCrossingDetector` returns a zero crossing detector object, `H`, that counts the number of zero crossings in the real-valued, floating-point, or fixed-point frame-based vector or matrix.

`H = dsp.ZeroCrossingDetector('PropertyName',PropertyValue, ...)` returns a zero crossing detector object, `H`, with each property set to the specified value.

**Properties** **FrameBasedProcessing**

Enable frame-based processing

Set this property to `true` to enable frame-based processing. Set this property to `false` to enable sample-based processing. The default is `true`.

If the `FrameBasedProcessing` property is `true`:

- The zero crossing detector treats a column vector or the columns of a matrix as single, independent channels.
- The zero crossing detector treats a length  $N$  row vector as  $N$  independent channels.

If the `FrameBasedProcessing` property is `false`:

- The zero crossing detector treats each entry of a vector or matrix as an independent channel.

## Methods

clone	Create zero crossing detection object with same property values
getNumInputs	Number of expected inputs to step method
getNumOutputs	Number of outputs of step method
isLocked	Locked status for input attributes and nontunable properties
release	Allow property value and input characteristics changes
step	Count zero crossings in input

## Examples

Find number of zero crossings in electrocardiogram data:

```
EcgData = ecg(500)';  
Hzerocross = dsp.ZeroCrossingDetector;  
NumZeroCross = step(Hzerocross, EcgData); % Equal to 4  
plot(1:500, EcgData, 'b', [0 500], [0 0], 'r', 'linewidth', 2);
```

## Algorithms

This object implements the algorithm, inputs, and outputs described on the Zero Crossing block reference page. The object properties correspond to the block parameters.

Both this object and its corresponding block let you specify whether to process inputs as individual samples or as frames of data. The object uses the `FrameBasedProcessing` property. The block uses the **Input processing** parameter. See “Set the `FrameBasedProcessing` Property of a System object” for more information.

# **dsp.ZeroCrossingDetector.clone**

---

**Purpose** Create zero crossing detection object with same property values

**Syntax** `C = clone(H)`

**Description** `C = clone(H)` creates a zero crossing detector object, `C`, with the same property values as `H`. The clone method creates a new unlocked object.

# dsp.ZeroCrossingDetector.getNumInputs

---

**Purpose** Number of expected inputs to step method

**Syntax** `N = getNumInputs(H)`

**Description** `N = getNumInputs(H)` returns the number of expected inputs, *N*, to the `step` method.

The `getNumInputs` method returns a positive integer that is the number of expected inputs (not counting the object itself) to the `step` method. This value will change if you alter any properties that turn inputs on or off. You must call the `step` method with the number of input arguments equal to the result of `getNumInputs(H)`.

# **dsp.ZeroCrossingDetector.getNumOutputs**

---

**Purpose**            Number of outputs of step method

**Syntax**            `N = getNumOutputs(H)`

**Description**      `N = getNumOutputs(H)` returns the number of outputs, N, of step method.

The `getNumOutputs` method returns a positive integer that is the number of outputs from the `step` method. This value will change if you alter any properties that turn outputs on or off.

**Purpose** Locked status for input attributes and nontunable properties

**Syntax** `isLocked(H)`

**Description** `isLocked(H)` returns the locked state of the zero crossing detector object.

The `isLocked` method returns a logical value that indicates whether input attributes and nontunable properties for the object are locked. The object performs an internal initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. After locking, the `isLocked` method returns a true value.

# dsp.ZeroCrossingDetector.release

---

**Purpose** Allow property value and input characteristics changes

**Syntax** `release(H)`

**Description** `release(H)` releases system resources, such as memory, file handles, and hardware connections, and lets you change any properties or input characteristics.

---

**Note** You can use the `release` method on a `System` object in code generated from MATLAB, but once you release its resources, you cannot use that `System` object again.

---

**Purpose** Count zero crossings in input

**Syntax**  $Y = \text{step}(H, X)$

**Description**  $Y = \text{step}(H, X)$  counts the number of zero crossings,  $Y$ , in the vector or matrix input  $X$ .

---

**Note** The object performs an initialization the first time the `step` method is executed. This initialization locks nontunable properties and input specifications, such as dimensions, complexity, and data type of the input data. If you change a nontunable property or an input specification, the System object issues an error. To change nontunable properties or inputs, you must first call the `release` method to unlock the object.

---

# matlab.System

---

**Purpose** Base class for System objects

**Description** `matlab.System` is the base class for System objects. In your class definition file, you must subclass your object from this base class (or from another class that derives from this base class). Subclassing allows you to use the implementation and service methods provided by this base class to build your object. You use this syntax as the first line of your class definition file to directly inherit from the `matlab.System` base class, where `ObjectName` is the name of your object:

```
classdef ObjectName < matlab.System
```

---

**Note** You must set `Access=protected` for each `matlab.System` method you use in your code.

---

Methods		
	<code>getDiscreteStateImpl</code>	Discrete state property values
	<code>getNumInputsImpl</code>	Number of input arguments passed to step and setup methods
	<code>getNumOutputsImpl</code>	Number of outputs returned by method
	<code>isInactivePropertyImpl</code>	Active or inactive flag for properties
	<code>loadObjectImpl</code>	Load saved System object from MAT file
	<code>processTunedPropertiesImpl</code>	Action when tunable properties change
	<code>releaseImpl</code>	Release resources
	<code>resetImpl</code>	Reset System object states
	<code>saveObjectImpl</code>	Save System object in MAT file

<code>setProperty</code>	Set property values from name-value pair inputs
<code>setupImpl</code>	Initialize System object
<code>stepImpl</code>	System output and state update equations
<code>validateInputsImpl</code>	Validate inputs to step method
<code>validatePropertiesImpl</code>	Validate property values

## Attributes

In addition to the attributes available for MATLAB objects, you can apply the following attributes to any property of a custom System object.

<code>Nontunable</code>	After an object is locked (after <code>step</code> or <code>setup</code> has been called), use <code>Nontunable</code> to prevent a user from changing that property value. By default, all properties are tunable. The <code>Nontunable</code> attribute is useful to lock a property that has side effects when changed. This attribute is also useful for locking a property value assumed to be constant during processing. You should always specify properties that affect the number of input or output ports as <code>Nontunable</code> .
<code>Logical</code>	Use <code>Logical</code> to limit the property value to a logical, scalar value. Any scalar value that can be converted to a logical is also valid, such as 0 or 1.
<code>PositiveInteger</code>	Use <code>PositiveInteger</code> to limit the property value to a positive integer value.
<code>DiscreteState</code>	Use <code>DiscreteState</code> to mark a property so it will display its state value when you use the <code>getDiscreteState</code> method.

To learn more about attributes, see “Property Attributes” in the MATLAB Object-Oriented Programming documentation.

## Examples

Create a simple System object, `AddOne`, which subclasses from `matlab.System`. You place this code into a MATLAB file, `AddOne.m`.

```
classdef AddOne < matlab.System
%ADDONE Compute an output value that increments the input by one

    methods (Access=protected)
        % stepImpl method is called by the step method.
        function y = stepImpl(~,x)
            y = x + 1;
        end
    end
end
```

To use this object, create an instance of `AddOne`, provide an input, and use the `step` method:

```
hAdder = AddOne;
x = 1;
y = step(hAdder,x)
```

---

Assign the `Nontunable` attribute to the `InitialValue` property, which you define in your class definition file.

```
properties (Nontunable)
    InitialValue
end
```

## See Also

`matlab.system.StringSet` | | | |  
`matlab.system.mixin.FiniteSource` | | |

## How To

- “Object-Oriented Programming”

- Class Attributes
- Property Attributes
- “Method Attributes”
- “Define Basic System Objects”
- 
- 
- 
- “Define Property Attributes”
- 
- 
-

# matlab.System.getDiscreteStateImpl

---

**Purpose** Discrete state property values

**Syntax** `s = getDiscreteStateImpl(obj)`

**Description** `s = getDiscreteStateImpl(obj)` returns a struct `s` of state values. The field names of the struct are the object's `DiscreteState` property names. To restrict or change the values returned by `getDiscreteState` method, you can override this `getDiscreteStateImpl` method. End users cannot specify scaled double fi objects as inputs to discrete state properties.

`getDiscreteStatesImpl` is called by the `getDiscreteState` method, which is called by the `setup` method.

---

**Note** You must set `Access=protected` for this method.

---

**Input Arguments** **obj**  
System object handle

**Output Arguments** **s**  
Struct of state values.

**Examples**

```
methods (Access=protected)
    function s = getDiscreteState(obj)
    end
end
```

**See Also** `setupImpl` | | |

**How To**

- “Define Property Attributes”
- 
-

.

# matlab.System.getNumInputsImpl

---

**Purpose** Number of input arguments passed to step and setup methods

**Syntax** `num = getNumInputsImpl(obj)`

**Description** `num = getNumInputsImpl(obj)` returns the number of inputs `num` (excluding the System object handle) expected by the `step` method. The default implementation returns 1, which requires one input from the user, in addition to the System object handle. To specify a value other than 1, you must use include the `getNumInputsImpl` method in your class definition file.

`getNumInputsImpl` is called by the `getNumInputs` method and by the `setup` method if the number of inputs has not been determined already.

---

**Note** You must set `Access=protected` for this method.

---

**Input Arguments**

**obj** System object handle

**Output Arguments**

**num** Number of inputs expected by the `step` method for the specified object.

**Default:** 1

**Examples** Specify the number of inputs (2, in this case) expected by the `step` method.

```
methods (Access=protected)
    function num = getNumInputsImpl(obj)
        num = 2;
    end
end
```

Specify that the step method will not accept any inputs.

```
methods (Access=protected)
    function num = getNumInputsImpl(~)
        num = 0;
    end
end
```

## See Also

[setupImpl](#) | | | [stepImpl](#) | | | [getNumOutputsImpl](#) | | |

## How To

- “Change Number of Step Inputs or Outputs”
- 
- 
-

# matlab.System.getNumOutputsImpl

---

**Purpose** Number of outputs returned by step method

**Syntax** num = getNumOutputsImpl (obj)

**Description** num = getNumOutputsImpl (obj) returns the number of outputs from the step method. The default implementation returns 1 output. To specify a value other than 1, you must use include the getNumOutputsImpl method in your class definition file.

getNumOutputsImpl is called by the getNumOutputs method, if the number of outputs has not been determined already.

---

**Note** You must set Access=protected for this method.

---

**Input Arguments**

**obj**  
System object handle

**Output Arguments**

**num**  
Number of outputs to be returned by the step method for the specified object.

**Examples** Specify the number of outputs (2, in this case) returned from the step method.

```
methods (Access=protected)
    function num = getNumOutputsImpl(obj)
        num = 2;
    end
end
```

---

Specify that the step method does not return any outputs.

```
methods (Access=protected)
```

```
function num = getNumOutputsImpl(-)
    num = 0;
end
end
```

## See Also

[stepImpl](#) | | | [getNumInputsImpl](#) | | | [setupImpl](#) | | |

## How To

- “Change Number of Step Inputs or Outputs”
- 
- 
-

# matlab.System.isInactivePropertyImpl

---

**Purpose** Active or inactive flag for properties

**Syntax** `flag = isInactivePropertyImpl(obj,prop)`

**Description** `flag = isInactivePropertyImpl(obj,prop)` specifies whether a property is inactive for the current object configuration. An *inactive property* is a property that is not relevant to the object, given the values of other properties. Inactive properties are not shown if you use the `disp` method to display object properties. If you attempt to use public access to directly access or use `get` or `set` on an inactive property, a warning occurs.

`isInactiveProperty` is called by the `disp` method and by the `get` and `set` methods.

---

**Note** You must set `Access=protected` for this method.

---

**Input Arguments**

**obj**  
System object handle

**prop**  
Property name

**Output Arguments**

**flag**  
Logical scalar value indicating whether the input property `prop` is inactive for the current object configuration.

**Examples**

Display the `InitialValue` property only when the `UseRandomInitialValue` property value is `false`.

```
methods (Access=protected)
function flag = isInactivePropertyImpl(obj,propertyName)
    if strcmp(propertyName,'InitialValue')
        flag = obj.UseRandomInitialValue;
```

```
        else
            flag = false;
        end
    end
end
```

## See Also

[setProperty](#) | [get](#) | [set](#)

## How To

- “Hide Inactive Properties”
- 
- 
-

# matlab.System.loadObjectImpl

---

<b>Purpose</b>	Load saved System object from MAT file
<b>Syntax</b>	<code>loadObjectImpl(obj)</code>
<b>Description</b>	<code>loadObjectImpl(obj)</code> loads a saved System object, <code>obj</code> , from a MAT file. Your <code>loadObjectImpl</code> method should correspond to your <code>saveObjectImpl</code> method to ensure that all saved properties and data are loaded.
<b>Input Arguments</b>	<b>obj</b> System object handle
<b>Examples</b>	Load a saved System object. In this case, the object contains a child object, protected and private properties, and a discrete state. <pre>methods(Access=protected) function loadObjectImpl(obj, s, wasLocked)     % Load child System objects     obj.child = matlab.System.loadObject(s.child);      % Save protected &amp; private properties     obj.protected = s.protected;     obj.pdependentprop = s.pdependentprop;      % Save state only if locked when saved     if wasLocked         obj.state = s.state;     end      % Call base class method     loadObjectImpl@matlab.System(obj,s,wasLocked); end end</pre>
<b>See Also</b>	<code>saveObjectImpl</code>

## How To

- “Load System Object”
- “Save System Object”

# matlab.System.processTunedPropertiesImpl

---

**Purpose** Action when tunable properties change

**Syntax** `processTunedPropertiesImpl(obj)`

**Description** `processTunedPropertiesImpl(obj)` specifies the actions to perform when one or more tunable property values change. This method is called as part of the next call to the `step` method after a tunable property value changes. A property is tunable only if its `Nontunable` attribute is `false`, which is the default.

`processTunedPropertiesImpl` is called by the `step` method.

---

**Note** You must set `Access=protected` for this method.

---

**Tips** Use this method when a tunable property affects a different property value. For example, two property values determine when to calculate a lookup table. You want to perform that calculation when either property changes. You also want the calculation to be done only once if both properties change before the next call to the `step` method.

**Input Arguments**

**obj**  
System object handle

**Examples** Use `processTunedPropertiesImpl` to recalculate the lookup table if the value of either the `NumNotes` or `MiddleC` property changes.

```
methods (Access=protected)
function processTunedPropertiesImpl(obj)
    % Generate a lookup table of note frequencies
    obj.pLookupTable = obj.MiddleC * (1+log(1:obj.NumNotes)/log(12));
end
end
```

**See Also** `validatePropertiesImpl` | | | `setProperties` | | |

## How To

- “Validate Property and Input Values”
- 
- 
- 
- “Define Property Attributes”
- 
- 
-

# matlab.System.releaseImpl

---

**Purpose** Release resources

**Syntax** `releaseImpl(obj)`

**Description** `releaseImpl(obj)` releases any resources used by the System object, such as file handles. This method also performs any necessary cleanup tasks. To release resources for a System object, you must use `releaseImpl` instead of a destructor.

`releaseImpl` is called by the `release` method. `releaseImpl` is also called when the object is deleted or cleared from memory, or when all references to the object have gone out of scope.

---

**Note** You must set `Access=protected` for this method.

---

**Input Arguments** **obj**  
System object handle

**Examples** Use the `releaseImpl` method to close a file.

```
methods (Access=protected)
function releaseImpl(obj)
    fclose(obj.pFileID);
end
end
```

**See Also** `resetImpl` | | |

**How To**

- “Release System Object Resources”
- 
- 
-

<b>Purpose</b>	Reset System object states
<b>Syntax</b>	<code>resetImpl(obj)</code>
<b>Description</b>	<p><code>resetImpl(obj)</code> defines the state reset equations for the System object. Typically you reset the states to a set of initial values.</p> <p><code>resetImpl</code> is called by the <code>reset</code> method. It is also called by the <code>setup</code> method, after the <code>setupImpl</code> method.</p>

---

**Note** You must set `Access=protected` for this method.

---

<b>Input Arguments</b>	<p><b>obj</b> System object handle</p>
------------------------	--

**Examples** Use the `reset` method to reset the counter `pCount` property to zero.

```
methods (Access=protected)
    function resetImpl(obj)
        obj.pCount = 0;
    end
end
```

**See Also** `releaseImpl` | | |

**How To**

- “Reset Algorithm State”
- 
- 
-

# matlab.System.saveObjectImpl

---

**Purpose** Save System object in MAT file

**Syntax** `saveObjectImpl(obj)`

**Description** `saveObjectImpl(obj)` defines what System object `obj` property and state values are saved in a MAT file when a user calls `save` on that object. `save` calls `saveObject`, which then calls `saveObjectImpl`. If you do not define a `saveObjectImpl` method for your System object class, only public properties are saved. To save any private or protected properties or state information, you must define a `saveObjectImpl` in your class definition file.

You should save the state of an object only if the object is locked. When the user loads that saved object, it loads in that locked state.

To save child object information, you use the associated `saveObject` method within the `saveObjectImpl` method.

End users can use `load`, which calls `loadObjectImpl` to load a System object into their workspace.

**Input Arguments**

**obj**  
System object handle

**Examples** Define what is saved for the System object. Call the base class version of `saveObjectImpl` to save public properties. Then, save any child System objects and any protected and private properties. Finally, save the state, if the object is locked.

```
methods(Access=protected)
function s = saveObjectImpl(obj)
    s = saveObjectImpl@matlab.System(obj);
    s.child = matlab.System.saveObject(obj.child);
    s.protected = obj.protected;
    s.pdependentprop = obj.pdependentprop;
    if isLocked(obj)
        s.state = obj.state;
```

```
        end  
    end  
end
```

## See Also

loadObjectImpl

## How To

- “Save System Object”
- “Load System Object”

# matlab.System.setProperties

---

**Purpose** Set property values from name-value pair inputs

**Syntax** `setProperties(obj,numargs,name1,value1,name2,value2,...)`  
`setProperties(obj,numargs,arg1,...,argm,name1,value1,name2,value2,...)`

**Description** `setProperties(obj,numargs,name1,value1,name2,value2,...)` provides the name-value pair inputs to the System object constructor. Use this syntax if every input must specify both name and value.

---

**Note** To allow standard name-value pair handling at construction, define `setProperties` for your System object.

---

`setProperties(obj,numargs,arg1,...,argm,name1,value1,name2,value2,...)` provides the value-only inputs, followed by the name-value pair inputs to the System object during object construction. Use this syntax if you want to allow users to specify one or more inputs by their values only.

## Input Arguments

### **obj**

System object handle

### **numargs**

Number of inputs passed in by the object constructor

### **name\***

Name of property

### **value\***

Value of the property

### **arg\***

Value of property (for value-only input to the object constructor)

## Examples

Set up the object so users can specify property values via name-value pairs when constructing the object.

```
methods
    function obj = MyFile(varargin)
        setProperties(obj,nargin,varargin{:});
    end
end
```

## How To

- “Set Property Values at Construction Time”
- 
- 
-

# matlab.System.setupImpl

---

**Purpose** Initialize System object

**Syntax** `setupImpl(obj,input1, input2,...)`

**Description** `setupImpl(obj,input1, input2,...)` sets up a System object. To acquire resources for a System object, you must use `setupImpl` instead of a constructor. `setupImpl` executes the first time the `step` method is called on an object after that object has been created. It also executes the next time `step` is called after an object has been released. . The number of inputs must match the number of inputs defined in the `getNumInputsImpl` method. You pass the inputs into `setupImpl` to use the input sizes, datatypes, etc. in the one-time calculations.

`setupImpl` is called by the `setup` method, which is done automatically as the first subtask of the `step` method on an unlocked System object.

---

**Note** You must set `Access=protected` for this method.

---

**Tips** To validate properties or inputs use the `validatePropertiesImpl`, `validateInputsImpl`, or `setProperties` methods. Do not include validation in `setupImpl`.

**Input Arguments** **obj**  
System object handle

**input\***  
Inputs to the `setup` method

**Examples** Open a file for writing using the `setupImpl` method.

```
methods (Access=protected)
function setupImpl(obj,data)
    obj.pFileID = fopen(obj.FileName, 'wb');
    if obj.pFileID < 0
```

```
        error('Opening the file failed');
    end
end
end
```

## See Also

[validatePropertiesImpl](#) | | | [validateInputsImpl](#) | | |  
[setPropertyies](#) | | |

## How To

- “Initialize Properties and Setup One-Time Calculations”
- 
- 
- 
- “Set Property Values at Construction Time”
- 
- 
-

# matlab.System.stepImpl

---

**Purpose** System output and state update equations

**Syntax** [output1,output2,...] = stepImpl(obj,input1,input2,...)

**Description** [output1,output2,...] = stepImpl(obj,input1,input2,...) defines the algorithm to execute when you call the step method on the specified object obj. The step method calculates the outputs and updates the object's state values using the inputs, properties, and state update equations.

stepImpl is called by the step method.

---

**Note** You must set Access=protected for this method.

---

**Tips** The number of input arguments and output arguments must match the values returned by the getNumInputsImpl and getNumOutputsImpl methods, respectively

**Input Arguments** **obj**  
System object handle

**input\***  
Inputs to the step method

**Output Arguments** **output**  
Output returned from the step method.

**Examples** Use the stepImpl method to increment two numbers.

```
methods (Access=protected)
function [y1,y2] = stepImpl(obj,x1,x2)
    y1 = x1 + 1;
    y2 = x2 + 1;
end
```

## See Also

[getNumInputsImpl | | |](#) [getNumOutputsImpl | | |](#)  
[validateInputsImpl | | |](#)

## How To

- “Define Basic System Objects”
- 
- 
- 
- “Change Number of Step Inputs or Outputs”
- 
- 
-

# matlab.System.validateInputsImpl

---

**Purpose** Validate inputs to step method

**Syntax** `validateInputsImpl(obj,input1,input2,...)`

**Description** `validateInputsImpl(obj,input1,input2,...)` validates inputs to the step method at the beginning of initialization. Validation includes checking data types, complexity, cross-input validation, and validity of inputs controlled by a property value.

`validateInputsImpl` is called by the `setup` method before `setupImpl`. `validateInputsImpl` executes only once.

---

**Note** You must set `Access=protected` for this method.

---

**Input Arguments**

**obj**  
System object handle

**input\***  
Inputs to the setup method

**Examples** Validate that the input is numeric.

```
methods (Access=protected)
function validateInputsImpl(~,x)
    if ~isnumeric(x)
        error('Input must be numeric');
    end
end
end
```

**See Also** [validatePropertiesImpl](#) | [setupImpl](#) |  |  |

**How To**

- “Validate Property and Input Values”
-

- 
-

# matlab.System.validatePropertiesImpl

---

**Purpose** Validate property values

**Syntax** `validatePropertiesImpl(obj)`

**Description** `validatePropertiesImpl(obj)` validates interdependent or interrelated property values at the beginning of object initialization, such as checking that the dependent or related inputs are the same size.

`validatePropertiesImpl` is the first method called by the `setup` method. `validatePropertiesImpl` also is called before the `processTunablePropertiesImpl` method.

---

**Note** You must set `Access=protected` for this method.

---

**Input Arguments**

**obj**  
System object handle

**Examples** Validate that the `useIncrement` property is true and that the value of the `increment` property is greater than zero.

```
methods (Access=protected)
    function validatePropertiesImpl(obj)
        if obj.useIncrement && obj.increment < 0
            error('The increment value must be positive');
        end
    end
end
```

**See Also** [processTunedPropertiesImpl](#) | [setupImpl](#) | [validateInputsImpl](#)

**How To**

- “Validate Property and Input Values”
-

·  
·

# matlab.system.mixin.FiniteSource

---

**Purpose** Finite source mixin class

**Description** `matlab.system.mixin.FiniteSource` is a class that defines the `isDone` method, which reports the state of a finite data source, such as an audio file.

To use this method, you must subclass from this class in addition to the `matlab.System` base class. You use the following syntax as the first line of your class definition file, where `ObjectName` is the name of your object:

```
classdef ObjectName < matlab.System &...  
    matlab.system.mixin.FiniteSource
```

**Methods** `isDoneImpl` End-of-data flag

**See Also** `matlab.System` | | |

**Tutorials**

- “Define Finite Source Objects”
- 
- 
- 

**How To**

- “Object-Oriented Programming”
- Class Attributes
- Property Attributes

<b>Purpose</b>	End-of-data flag
<b>Syntax</b>	<code>status = isDoneImpl(obj)</code>
<b>Description</b>	<p><code>status = isDoneImpl(obj)</code> indicates if an end-of-data condition has occurred. The <code>isDone</code> method should return <code>false</code> when data from a finite source has been exhausted, typically by having read and output all data from the source. You should also define the result of future reads from an exhausted source in the <code>isDoneImpl</code> method.</p> <p><code>isDoneImpl</code> is called by the <code>isDone</code> method.</p>
<b>Input Arguments</b>	<p><b>obj</b></p> <p>System object handle</p>
<b>Output Arguments</b>	<p><b>status</b></p> <p>Logical value, <code>true</code> or <code>false</code>, that indicates if an end-of-data condition has occurred or not, respectively.</p>
<b>Examples</b>	<p>Set up <code>isDoneImpl</code> so the <code>isDone</code> method checks whether the object has completed eight iterations.</p> <pre>methods (Access=private)     function bdone = isDoneImpl(obj)         bdone = obj.NumIters==8;     end end</pre>
<b>See Also</b>	<a href="#">matlab.system.mixin.FiniteSource</a>
<b>How To</b>	<ul style="list-style-type: none"><li>• “Define Finite Source Objects”</li><li>•</li><li>•</li><li>•</li></ul>

# matlab.system.StringSet

---

**Purpose** Set of valid string values

**Description** `matlab.system.StringSet` defines a list of valid string values for a property. This class validates the string in the property and enables tab completion for the property value. A *StringSet* allows only predefined or customized strings as values for the property.

A `StringSet` uses two linked properties, which you must define in the same class. One is a public property that contains the current string value. This public property is displayed to the user. The other property is a hidden property that contains the list of all possible string values. This hidden property should also have the transient attribute so its value is not saved to disk when you save the System object.

The following considerations apply when using `StringSets`:

- The string property that holds the current string can have any name.
- The property that holds the `StringSet` must use the same name as the string property with the suffix “Set” appended to it. The string set property is an instance of the `matlab.system.StringSet` class.
- Valid strings, defined in the `StringSet`, must be declared using a cell array. The cell array cannot be empty nor can it have any empty strings. Valid strings must be unique and are case-insensitive.
- The string property must be set to a valid `StringSet` value.

**Examples** Set the string property, `Flavor`, and the `StringSet` property, `FlavorSet`, in this example.

```
properties
    Flavor='Chocolate';
end

properties (Hidden,Transient)
    FlavorSet = ...
        matlab.system.StringSet({'Vanilla','Chocolate'});
end
```

## See Also

[matlab.System](#) | | |

## How To

- “Object-Oriented Programming”
- Class Attributes
- Property Attributes
- “Limit Property Values to Finite String Set”
- 
- 
-

# matlab.system.StringSet

---

# Function Reference

---

Adaptive Filters (p. 6-2)	Design adaptive filters
Discrete-Time Filters (p. 6-5)	Design FIR and IIR discrete-time filter objects
Filter Specifications — Response Types (p. 6-7)	Create objects that specify filter responses
Filter Specifications — Design Methods (p. 6-9)	Design filter objects from specification objects
Multirate Filters (p. 6-10)	Design multirate filter objects
GUIs (p. 6-11)	Use graphical user interface tools to design filters
Filter Analysis (p. 6-12)	Analyze filters and filter objects
Fixed-Point Filters (p. 6-15)	Create fixed-point filters
Quantized Filter Analysis (p. 6-16)	Analyze fixed-point filters
SOS Conversion (p. 6-17)	Work with second-order section filters
Filter Design (p. 6-18)	Design filters (not object-based)
Filter Conversion (p. 6-19)	Transform filters to other forms, or use features in filter to develop another filter
Signal Logging (p. 6-20)	Access data from logged signals
Simulink Signal Processing Functions (p. 6-21)	DSP System Toolbox functions for signal processing in Simulink

## Adaptive Filters

Least Mean Squares (p. 6-2)	Filter with LMS techniques
Recursive Least Squares (p. 6-3)	Filter with RLS techniques
Affine Projection (p. 6-3)	Filter with affine projection
Frequency Domain (p. 6-3)	Filter in the frequency domain
Lattice (p. 6-4)	Filter with lattice filters

## Least Mean Squares

<code>adaptfilt.adjLMS</code>	FIR adaptive filter that uses adjoint LMS algorithm
<code>adaptfilt.blms</code>	FIR adaptive filter that uses BLMS
<code>adaptfilt.blmsfft</code>	FIR adaptive filter that uses FFT-based BLMS
<code>adaptfilt.dlms</code>	FIR adaptive filter that uses delayed LMS
<code>adaptfilt.filtxLMS</code>	FIR adaptive filter that uses filtered-x LMS
<code>adaptfilt.lms</code>	FIR adaptive filter that uses LMS
<code>adaptfilt.nlms</code>	Normalized least mean squares adaptive filter
<code>adaptfilt.sd</code>	Sign-data FIR adaptive filter
<code>adaptfilt.se</code>	FIR adaptive filter that uses sign-error algorithm
<code>adaptfilt.ss</code>	FIR adaptive filter that uses sign-sign algorithm

## Recursive Least Squares

<code>adaptfilt.ftf</code>	Fast transversal LMS adaptive filter
<code>adaptfilt.hrls</code>	FIR adaptive filter that uses householder (RLS)
<code>adaptfilt.hswrls</code>	FIR adaptive filter that uses householder sliding window RLS
<code>adaptfilt.qrdrls</code>	FIR adaptive filter that uses QR-decomposition-based RLS
<code>adaptfilt.rls</code>	Recursive least-squares FIR adaptive filter
<code>adaptfilt.swftf</code>	FIR adaptive filter that uses sliding window fast transversal least squares
<code>adaptfilt.swrls</code>	FIR adaptive filter that uses window recursive least squares (RLS)

## Affine Projection

<code>adaptfilt.ap</code>	FIR adaptive filter that uses direct matrix inversion
<code>adaptfilt.apru</code>	FIR adaptive filter that uses recursive matrix updating
<code>adaptfilt.bap</code>	FIR adaptive filter that uses block affine projection

## Frequency Domain

<code>adaptfilt.fdaf</code>	FIR adaptive filter that uses frequency-domain with bin step size normalization
<code>adaptfilt.pbfdaf</code>	Partitioned block frequency-domain FIR adaptive filter

<code>adaptfilt.pbufdaf</code>	Partitioned block unconstrained frequency-domain adaptive filter
<code>adaptfilt.tdafdct</code>	Adaptive filter that uses discrete cosine transform
<code>adaptfilt.tdafdft</code>	Adaptive filter that uses discrete Fourier transform
<code>adaptfilt.ufdaf</code>	FIR adaptive filter that uses unconstrained frequency-domain with quantized step size normalization

### **Lattice**

<code>adaptfilt.gal</code>	FIR adaptive filter that uses gradient lattice
<code>adaptfilt.lsl</code>	Least squares lattice adaptive filter
<code>adaptfilt.qrdls1</code>	QR-decomposition-based least-squares lattice adaptive filter

## Discrete-Time Filters

<code>dfilt</code>	Discrete-time filter
<code>dfilt.allpass</code>	Allpass filter
<code>dfilt.calattice</code>	Coupled-allpass, lattice filter
<code>dfilt.calatticepc</code>	Coupled-allpass, power-complementary lattice filter
<code>dfilt.cascade</code>	Cascade of discrete-time filters
<code>dfilt.cascadeallpass</code>	Cascade of allpass discrete-time filters
<code>dfilt.cascadewdfallpass</code>	Cascade allpass WDF filters to construct allpass WDF
<code>dfilt.delay</code>	Delay filter
<code>dfilt.df1</code>	Discrete-time, direct-form I filter
<code>dfilt.df1sos</code>	Discrete-time, SOS direct-form I filter
<code>dfilt.df1t</code>	Discrete-time, direct-form I transposed filter
<code>dfilt.df1tsos</code>	Discrete-time, SOS direct-form I transposed filter
<code>dfilt.df2</code>	Discrete-time, direct-form II filter
<code>dfilt.df2sos</code>	Discrete-time, SOS, direct-form II filter
<code>dfilt.df2t</code>	Discrete-time, direct-form II transposed filter
<code>dfilt.df2tsos</code>	Discrete-time, SOS direct-form II transposed filter
<code>dfilt.dfasymfir</code>	Discrete-time, direct-form antisymmetric FIR filter
<code>dfilt.dffir</code>	Discrete-time, direct-form FIR filter

<code>dfilt.dffirt</code>	Discrete-time, direct-form FIR transposed filter
<code>dfilt.dfsymfir</code>	Discrete-time, direct-form symmetric FIR filter
<code>dfilt.farrowfd</code>	Fractional Delay Farrow filter
<code>dfilt.farrowlinearfd</code>	Farrow Linear Fractional Delay filter
<code>dfilt.fftfir</code>	Discrete-time, overlap-add, FIR filter
<code>dfilt.latticeallpass</code>	Discrete-time, lattice allpass filter
<code>dfilt.latticear</code>	Discrete-time, lattice, autoregressive filter
<code>dfilt.latticearma</code>	Discrete-time, lattice, autoregressive, moving-average filter
<code>dfilt.latticemamax</code>	Discrete-time, lattice, moving-average filter with maximum phase
<code>dfilt.latticemamin</code>	Discrete-time, lattice, moving-average filter with minimum phase
<code>dfilt.parallel</code>	Discrete-time, parallel structure filter
<code>dfilt.scalar</code>	Discrete-time, scalar filter
<code>dfilt.wdfallpass</code>	Wave digital allpass filter

## Filter Specifications — Response Types

<code>fdesign</code>	Filter specification object
<code>fdesign.arbgrpdelay</code>	Arbitrary group delay filter specification object
<code>fdesign.arbmag</code>	Arbitrary response magnitude filter specification object
<code>fdesign.arbmagnphase</code>	Arbitrary response magnitude and phase filter specification object
<code>fdesign.audioweighting</code>	Audio weighting filter specification object
<code>fdesign.bandpass</code>	Bandpass filter specification object
<code>fdesign.bandstop</code>	Bandstop filter specification object
<code>fdesign.ciccomp</code>	CIC compensator filter specification object
<code>fdesign.comb</code>	IIR comb filter specification object
<code>fdesign.decimator</code>	Decimator filter specification object
<code>fdesign.differentiator</code>	Differentiator filter specification object
<code>fdesign.fracdelay</code>	Fractional delay filter specification object
<code>fdesign.halfband</code>	Halfband filter specification object
<code>fdesign.highpass</code>	Highpass filter specification object
<code>fdesign.hilbert</code>	Hilbert filter specification object
<code>fdesign.interpolator</code>	Interpolator filter specification
<code>fdesign.isinchnp</code>	Inverse sinc highpass filter specification
<code>fdesign.isinclp</code>	Inverse sinc lowpass filter specification
<code>fdesign.lowpass</code>	Lowpass filter specification
<code>fdesign.notch</code>	Notch filter specification

<code>fdesign.nyquist</code>	Nyquist filter specification
<code>fdesign.octave</code>	Octave filter specification
<code>fdesign.parameq</code>	Parametric equalizer filter specification
<code>fdesign.peak</code>	Peak filter specification
<code>fdesign.polysrc</code>	Construct polynomial sample-rate converter (POLYSRC) filter designer
<code>fdesign.pulseshaping</code>	Pulse-shaping filter specification object
<code>fdesign.rsrc</code>	Rational-factor sample-rate converter specification

## Filter Specifications — Design Methods

<code>butter</code>	Butterworth IIR filter design using specification object
<code>cheby1</code>	Chebyshev Type I filter using specification object
<code>cheby2</code>	Chebyshev Type II filter using specification object
<code>design</code>	Apply design method to filter specification object
<code>designmethods</code>	Methods available for designing filter from specification object
<code>designopts</code>	Valid input arguments and values for specification object and method
<code>ellip</code>	Elliptic filter using specification object
<code>equiripple</code>	Equiripple single-rate or multirate FIR filter from specification object
<code>fircls</code>	FIR Constrained Least Squares filter
<code>ifir</code>	Interpolated FIR filter from filter specification
<code>iirlinphase</code>	Quasi-linear phase IIR filter from halfband filter specification
<code>kaiserwin</code>	Kaiser window filter from specification object
<code>maxflat</code>	Maxflat FIR filter
<code>multistage</code>	Multistage filter from specification object
<code>validstructures</code>	Structures for specification object with design method
<code>window</code>	FIR filter using windowed impulse response

## Multirate Filters

<code>mfilt.cascade</code>	Cascade filter objects
<code>mfilt.cicdecim</code>	Fixed-point CIC decimator
<code>mfilt.cicinterp</code>	Fixed-point CIC interpolator
<code>mfilt.farrowsrc</code>	Sample rate converter with arbitrary conversion factor
<code>mfilt.ffsetfirinterp</code>	Overlap-add FIR polyphase interpolator
<code>mfilt.firdecim</code>	Direct-form FIR polyphase decimator
<code>mfilt.firfracdecim (Obsolete)</code>	Direct-form FIR polyphase fractional decimator
<code>mfilt.firfracinterp (Obsolete)</code>	Direct-form FIR polyphase fractional interpolator
<code>mfilt.firinterp</code>	FIR filter-based interpolator
<code>mfilt.firsrc</code>	Direct-form FIR polyphase sample rate converter
<code>mfilt.firtdecim</code>	Direct-form transposed FIR filter
<code>mfilt.holdinterp</code>	FIR hold interpolator
<code>mfilt.iirdecim</code>	IIR decimator
<code>mfilt.iirinterp</code>	IIR interpolator
<code>mfilt.iirwdfdecim</code>	IIR wave digital filter decimator
<code>mfilt.iirwdfinterp</code>	IIR wave digital filter interpolator
<code>mfilt.linearinterp</code>	Linear interpolator

## GUIs

`fdatool`

Open Filter Design and Analysis  
Tool

`filterbuilder`

GUI-based filter design

## Filter Analysis

<code>autoscale</code>	Automatic dynamic range scaling
<code>block</code>	Generate block from multirate or multistage filter
<code>coeffs</code>	Coefficients for filters
<code>cost</code>	Estimate cost of discrete-time or multirate filter
<code>cumsec</code>	Vector of SOS filters for cumulative sections
<code>denormalize</code>	Undo filter coefficient and gain changes caused by normalize
<code>disp</code>	Filter properties and values
<code>double</code>	Cast fixed-point filter to use double-precision arithmetic
<code>euclidfactors</code>	Euclid factors for multirate filter
<code>fftcoeffs</code>	Frequency-domain coefficients
<code>filter</code>	Filter data with filter object
<code>filtstates.cic</code>	Store CIC filter states
<code>firtype</code>	Type of linear phase FIR filter
<code>freqrespest</code>	Frequency response estimate via filtering
<code>freqrespopts</code>	Options for filter frequency response analysis
<code>freqsamp</code>	Real or complex frequency-sampled FIR filter from specification object
<code>freqz</code>	Frequency response of filter
<code>grpdelay</code>	Filter group delay
<code>help</code>	Help for design method with filter specification
<code>impz</code>	Filter impulse response

<code>isfir</code>	Determine whether filter is FIR
<code>islinphase</code>	Determine whether filter is linear phase
<code>ismaxphase</code>	Determine whether filter is maximum phase
<code>isminphase</code>	Determine whether filter is minimum phase
<code>isreal</code>	Determine whether filter uses real coefficients
<code>isstable</code>	Determine whether filter is stable
<code>limitcycle</code>	Response of single-rate, fixed-point IIR filter
<code>maxstep</code>	Maximum step size for adaptive filter convergence
<code>measure</code>	Measure filter magnitude response
<code>msepred</code>	Predicted mean-squared error for adaptive filter
<code>msesim</code>	Measured mean-squared error for adaptive filter
<code>noisepsd</code>	Power spectral density of filter output due to roundoff noise
<code>noisepsdopts</code>	Options for running filter output noise PSD
<code>norm</code>	P-norm of filter
<code>normalize</code>	Normalize filter numerator or feed-forward coefficients
<code>normalizefreq</code>	Switch filter specification between normalized frequency and absolute frequency
<code>nstates</code>	Number of filter states
<code>order</code>	Order of fixed-point filter

<code>phasedelay</code>	Phase delay of filter
<code>phasez</code>	Unwrapped phase response for filter
<code>polyphase</code>	Polyphase decomposition of multirate filter
<code>qreport</code>	Most recent fixed-point filtering operation report
<code>realizemdl</code>	Simulink subsystem block for filter
<code>reffilter</code>	Reference filter for fixed-point or single-precision filter
<code>reorder</code>	Rearrange sections in SOS filter
<code>reset</code>	Reset filter properties to initial conditions
<code>scale</code>	Scale sections of SOS filter
<code>scalecheck</code>	Check scaling of SOS filter
<code>set2int</code>	Configure filter for integer filtering
<code>setspecs</code>	Specifications for filter specification object
<code>specifyall</code>	Fixed-point scaling modes in direct-form FIR filter
<code>stepz</code>	Step response for filter
<code>sysobj</code>	Create filter System object from discrete-time filter or multirate filter
<code>zerophase</code>	Zero-phase response for filter
<code>zplane</code>	Zero-pole plot for filter

To see the full listing of analysis methods that apply to the `adaptfilt`, `dfilt`, or `mfilt` objects, enter `help adaptfilt`, `help dfilt`, or `help mfilt` at the MATLAB prompt.

## Fixed-Point Filters

<code>cell2sos</code>	Convert cell array to SOS matrix
<code>get</code>	Properties of quantized filter
<code>isreal</code>	Test if filter coefficients are real
<code>reset</code>	Reset properties of quantized filter to initial values
<code>scale</code>	Scale sections of SOS filters
<code>scalecheck</code>	Check scaling of SOS filter
<code>scaleopts</code>	Scaling options for second-order section scaling
<code>set</code>	Properties of quantized filter
<code>sos</code>	Convert quantized filter to SOS form, order, and scale
<code>sos2cell</code>	Convert SOS matrix to cell array

## Quantized Filter Analysis

<code>freqz</code>	Frequency response of filter
<code>impz</code>	Filter impulse response
<code>isallpass</code>	Determine whether filter is allpass
<code>isfir</code>	Determine whether filter is FIR
<code>islinphase</code>	Determine whether filter is linear phase
<code>ismaxphase</code>	Determine whether filter is maximum phase
<code>isminphase</code>	Determine whether filter is minimum phase
<code>isreal</code>	Determine whether filter uses real coefficients
<code>issos</code>	Determine whether filter is SOS form
<code>isstable</code>	Determine whether filter is stable
<code>noisepsd</code>	Power spectral density of filter output due to roundoff noise
<code>noisepsopts</code>	Options for running filter output noise PSD
<code>zplane</code>	Zero-pole plot for filter

## SOS Conversion

<code>cell2sos</code>	Convert a cell array to a second-order sections matrix
<code>sos</code>	Convert a quantized filter to second-order sections form, order, and scale
<code>sos2cell</code>	Convert a second-order sections matrix to a cell array

## Filter Design

<code>fdatool</code>	Open Filter Design and Analysis Tool
<code>filterbuilder</code>	GUI-based filter design
<code>firband</code>	Constrained-band equiripple FIR filter
<code>firceqrip</code>	Constrained equiripple FIR filter
<code>fireqint</code>	Equiripple FIR interpolators
<code>fingr</code>	Parks-McClellan FIR filter
<code>firhalfband</code>	Halfband FIR filter
<code>firlpnorm</code>	Least P-norm optimal FIR filter
<code>firls</code>	Least-square linear-phase FIR filter design
<code>firminphase</code>	Minimum-phase FIR spectral factor
<code>firnyquist</code>	Lowpass Nyquist (Lth-band) FIR filter
<code>ifir</code>	Interpolated FIR filter from filter specification
<code>iircomb</code>	IIR comb notch or peak filter
<code>iirgrpdelay</code>	Optimal IIR filter with prescribed group-delay
<code>iirlpnorm</code>	Least P-norm optimal IIR filter
<code>iirlpnormc</code>	Constrained least Pth-norm optimal IIR filter
<code>iirnotch</code>	Second-order IIR notch filter
<code>iirpeak</code>	Second-order IIR peak or resonator filter

## Filter Conversion

ca2tf	Convert coupled allpass filter to transfer function form
cl2tf	Convert coupled allpass lattice to transfer function form
convert	Convert filter structure of discrete-time or multirate filter
firlp2hp	Convert FIR lowpass filter to Type I FIR highpass filter
firlp2lp	Convert FIR Type I lowpass to FIR Type 1 lowpass with inverse bandwidth
iirlp2bp	Transform IIR lowpass filter to IIR bandpass filter
iirlp2bs	Transform IIR lowpass filter to IIR bandstop filter
iirlp2hp	Transform lowpass IIR filter to highpass filter
iirlp2lp	Transform lowpass IIR filter to different lowpass filter
iirpowcomp	Power complementary IIR filter
set2int	Configure filter for integer filtering
tf2ca	Transfer function to coupled allpass
tf2cl	Transfer function to coupled allpass lattice

## Signal Logging

<code>dsp.util.getLogsArray</code>	Return logged signal as MATLAB array
<code>dsp.util.getSignalPath</code>	Paths to logged signals
<code>dsp.util.SignalPath</code>	Properties of paths to signals

## Simulink Signal Processing Functions

<code>dsplib</code>	Open top-level DSP System Toolbox library
<code>dspstartup</code>	Configure Simulink environment for signal processing systems
<code>dsp_links</code>	Identify whether blocks in model are current, deprecated, or obsolete
<code>liblinks</code>	Check model for blocks from specific DSP System Toolbox libraries
<code>rebuffer_delay</code>	Number of samples of delay introduced by buffering and unbuffering operations



# Functions — Alphabetical List

---

**Purpose** Adaptive filter

**Syntax** `ha = adaptfilt.algorithm('input1',input2,...)`

**Description** `ha = adaptfilt.algorithm('input1',input2,...)` returns the adaptive filter object `ha` that uses the adaptive filtering technique specified by *algorithm*. When you construct an adaptive filter object, include an *algorithm* specifier to implement a specific adaptive filter. Note that you do not enclose the algorithm option in single quotation marks as you do for most strings. To construct an adaptive filter object you must supply an *algorithm* string — there is no default algorithm, although every constructor creates a default adaptive filter when you do not provide input arguments such as `input1` or `input2` in the calling syntax.

## Algorithms

For adaptive filter (`adaptfilt`) objects, the *algorithm* string determines which adaptive filter algorithm your `adaptfilt` object implements. Each available algorithm entry appears in one of the tables along with a brief description of the algorithm. Click on the algorithm in the first column to get more information about the associated adaptive filter technique.

- “Least Mean Squares (LMS) Based FIR Adaptive Filters” on page 7-3
- “Recursive Least Squares (RLS) Based FIR Adaptive Filters” on page 7-4
- “Affine Projection (AP) FIR Adaptive Filters” on page 7-4
- “FIR Adaptive Filters in the Frequency Domain (FD)” on page 7-5
- “Lattice Based (L) FIR Adaptive Filters” on page 7-5

**Least Mean Squares (LMS) Based FIR Adaptive Filters**

<b>adaptfilt.algorithm String</b>	<b>Algorithm Used to Generate Filter Coefficients</b>
adaptfilt.adjlms	Use the Adjoint LMS FIR adaptive filter algorithm
adaptfilt.blms	Use the Block LMS FIR adaptive filter algorithm
adaptfilt.blmsfft	Use the FFT-based Block LMS FIR adaptive filter algorithm
adaptfilt.dlms	Use the delayed LMS FIR adaptive filter algorithm
adaptfilt.filtxlms	Use the filtered-x LMS FIR adaptive filter algorithm
adaptfilt.lms	Use the LMS FIR adaptive filter algorithm
adaptfilt.nlms	Use the normalized LMS FIR adaptive filter algorithm
adaptfilt.sd	Use the sign-data LMS FIR adaptive filter algorithm
adaptfilt.se	Use the sign-error LMS FIR adaptive filter algorithm
adaptfilt.ss	Use the sign-sign LMS FIR adaptive filter algorithm

For further information about an adapting algorithm, refer to the reference page for the algorithm.

## Recursive Least Squares (RLS) Based FIR Adaptive Filters

<b>adaptfilt.algorithm String</b>	<b>Algorithm Used to Generate Filter Coefficients</b>
adaptfilt.ftf	Use the fast transversal least squares adaptation algorithm
adaptfilt.qrdrls	Use the QR-decomposition RLS adaptation algorithm
adaptfilt.hrls	Use the householder RLS adaptation algorithm
adaptfilt.hswrls	Use the householder SWRLS adaptation algorithm
adaptfilt.rls	Use the recursive-least squares (RLS) adaptation algorithm
adaptfilt.swrls	Use the sliding window (SW) RLS adaptation algorithm
adaptfilt.swftf	Use the sliding window FTF adaptation algorithm

For more complete information about an adapting algorithm, refer to the reference page for the algorithm.

## Affine Projection (AP) FIR Adaptive Filters

<b>adaptfilt.algorithm String</b>	<b>Algorithm Used to Generate Filter Coefficients</b>
adaptfilt.ap	Use the affine projection algorithm that uses direct matrix inversion
adaptfilt.apru	Use the affine projection algorithm that uses recursive matrix updating
adaptfilt.bap	Use the block affine projection adaptation algorithm

To find more information about an adapting algorithm, refer to the reference page for the algorithm.

**FIR Adaptive Filters in the Frequency Domain (FD)**

<b>adaptfilt.algorithm String</b>	<b>Algorithm Used to Generate Filter Coefficients</b>
adaptfilt.fdaf	Use the frequency domain adaptation algorithm
adaptfilt.pbfdaf	Use the partition block version of the FDAF algorithm
adaptfilt.pbufdaf	Use the partition block unconstrained version of the FDAF algorithm
adaptfilt.tdafdct	Use the transform domain adaptation algorithm using DCT
adaptfilt.tdafdft	Use the transform domain adaptation algorithm using DFT
adaptfilt.ufdaf	Use the unconstrained FDAF algorithm for adaptation

For more information about an adapting algorithm, refer to the reference page for the algorithm.

**Lattice Based (L) FIR Adaptive Filters**

<b>adaptfilt.algorithm String</b>	<b>Algorithm Used to Generate Filter Coefficients</b>
adaptfilt.gal	Use the gradient adaptive lattice filter adaptation algorithm
adaptfilt.lsl	Use the least squares lattice adaptation algorithm
adaptfilt.qrdsl	Use the QR decomposition least squares lattice adaptation algorithm

For more information about an adapting algorithm, refer to the reference page for the algorithm.

## Properties for All Adaptive Filter Objects

Each reference page for an algorithm and `adaptfilt.algorithm` object specifies which properties apply to the adapting algorithm and how to use them.

## Methods for Adaptive Filter Objects

As is true with all objects, methods enable you to perform various operations on `adaptfilt` objects. To use the methods, you apply them to the object handle that you assigned when you constructed the `adaptfilt` object.

Most of the analysis methods that apply to `dfilt` objects also work with `adaptfilt` objects. Methods like `freqz` rely on the filter coefficients in the `adaptfilt` object. Since the coefficients change each time the filter adapts to data, you should view the results of using a method as an analysis of the filter at a moment in time for the object. Use caution when you apply an analysis method to your adaptive filter objects — always check that your result approached your expectation.

In particular, the Filter Visualization Tool (FVTool) supports all of the `adaptfilt` objects. Analyzing and viewing your `adaptfilt` objects is straightforward — use the `fvtool` method with the name of your object

```
fvtool(objectname)
```

to launch FVTool and work with your object.

Some methods share their names with functions in Signal Processing Toolbox software, or even functions in this toolbox. Functions that share names with methods behave in a similar way. Using the same name for more than one function or method is called *overloading* and is common in many toolboxes.

Method	Description
<code>adaptfilt/coefficients</code>	Return the instantaneous adaptive filter coefficients
<code>adaptfilt/filter</code>	Apply an <code>adaptfilt</code> object to your signal
<code>adaptfilt/freqz</code>	Plot the instantaneous adaptive filter frequency response
<code>adaptfilt/grpdelay</code>	Plot the instantaneous adaptive filter group delay
<code>adaptfilt/impz</code>	Plot the instantaneous adaptive filter impulse response.
<code>adaptfilt/info</code>	Return the adaptive filter information.
<code>adaptfilt/isfir</code>	Test whether an adaptive filter is a finite impulse response (FIR) filter.
<code>adaptfilt/islinphase</code>	Test whether an adaptive filter is linear phase
<code>adaptfilt/ismaxphase</code>	Test whether an adaptive filter is maximum phase
<code>adaptfilt/isminphase</code>	Test whether an adaptive filter is minimum phase
<code>adaptfilt/isreal</code>	True whether an adaptive filter has real coefficients
<code>adaptfilt/isstable</code>	Test whether an adaptive filter is stable
<code>adaptfilt/maxstep</code>	Return the maximum step size for an adaptive filter
<code>adaptfilt/msepred</code>	Return the predicted mean square error
<code>adaptfilt/msesim</code>	Return the measured mean square error via simulation.

Method	Description
<code>adaptfilt/phasez</code>	Plot the instantaneous adaptive filter phase response
<code>adaptfilt/reset</code>	Reset an adaptive filter to initial conditions
<code>adaptfilt/stepz</code>	Plot the instantaneous adaptive filter step response
<code>adaptfilt/tf</code>	Return the instantaneous adaptive filter transfer function
<code>adaptfilt/zerophase</code>	Plot the instantaneous adaptive filter zerophase response
<code>adaptfilt/zpk</code>	Return a matrix containing the instantaneous adaptive filter zero, pole, and gain values
<code>adaptfilt/zplane</code>	Plot the instantaneous adaptive filter in the Z-plane

## Working with Adaptive Filter Objects

The next sections cover viewing and changing the properties of `adaptfilt` objects. Generally, modifying the properties is the same for `adaptfilt`, `dfilt`, and `mfilt` objects and most of the same methods apply to all.

### Viewing Object Properties

As with any object, you can use `get` to view a `adaptfilt` object's properties. To see a specific property, use

```
get(ha, 'property')
```

To see all properties for an object, use

```
get(ha)
```

## Changing Object Properties

To set specific properties, use

```
set(ha, 'property1', value1, 'property2', value2, ...)
```

You must use single quotation marks around the property name so MATLAB treats them as strings.

## Copying an Object

To create a copy of an object, use `copy`.

```
ha2 = copy(ha)
```

---

**Note** Using the syntax `ha2 = ha` copies only the object handle and does not create a new object — `ha` and `ha2` are not independent. When you change the characteristics of `ha2`, those of `ha` change as well.

---

## Using Filter States

Two properties control your adaptive filter states.


- `States` — stores the current states of the filter. Before the filter is applied, the states correspond to the initial conditions and after the filter is applied, the states correspond to the final conditions.
- `PersistentMemory` — resets the filter before filtering. The default value is `false` which causes the properties that are modified by the filter, such as `coefficients` and `states`, to be reset to the value you specified when you constructed the object, before you use the object to filter data. Setting `PersistentMemory` to `true` allows the object to retain its current properties between filtering operations, rather than resetting the filter to its property values at construction.

## Examples

Construct an LMS adaptive filter object and use it to identify an unknown system. For this example, use 500 iteration of the adapting process to determine the unknown filter coefficients. Using the LMS

algorithm represents one of the most straightforward technique for adaptive filters.

```
x = randn(1,500); % Input to the filter
b = fir1(31,0.5); % FIR system to be identified
n = 0.1*randn(1,500); % Observation noise signal
d = filter(b,1,x)+n; % Desired signal
mu = 0.008; % LMS step size.
ha = adaptfilt.lms(32,mu);
[y,e] = filter(ha,x,d);
subplot(2,1,1); plot(1:500,[d;y;e]);
title('System Identification of an FIR Filter');
legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,1,2); stem([b.',ha.coefficients.']);
legend('Actual','Estimated');
xlabel('Coefficient #'); ylabel('Coefficient Value'); grid on;
```



**See Also**

`dfilt` | `filter` | `mfilt`

<b>Purpose</b>	FIR adaptive filter that uses adjoint LMS algorithm
<b>Syntax</b>	<code>ha = adaptfilt.adjlims(l,step,leakage,pathcoeffs,pathest,... errstates,pstates,coeffs,states)</code>
<b>Description</b>	<p><code>ha = adaptfilt.adjlims(l,step,leakage,pathcoeffs,pathest,... errstates,pstates,coeffs,states)</code> constructs object <code>ha</code>, an FIR adjoint LMS adaptive filter. <code>l</code> is the adaptive filter length (the number of coefficients or taps) and must be a positive integer. <code>l</code> defaults to 10 when you omit the argument. <code>step</code> is the adjoint LMS step size. It must be a nonnegative scalar. When you omit the <code>step</code> argument, <code>step</code> defaults to 0.1.</p> <p><code>leakage</code> is the adjoint LMS leakage factor. It must be a scalar between 0 and 1. When <code>leakage</code> is less than one, you implement a leaky version of the <code>adjlims</code> algorithm to determine the filter coefficients. <code>leakage</code> defaults to 1 specifying no leakage in the algorithm.</p> <p><code>pathcoeffs</code> is the secondary path filter model. This vector should contain the coefficient values of the secondary path from the output actuator to the error sensor.</p> <p><code>pathest</code> is the estimate of the secondary path filter model. <code>pathest</code> defaults to the values in <code>pathcoeffs</code>.</p> <p><code>errstates</code> is a vector of error states of the adaptive filter. It must have a length equal to the filter order of the secondary path model estimate. <code>errstates</code> defaults to a vector of zeros of appropriate length. <code>pstates</code> contains the secondary path FIR filter states. It must be a vector of length equal to the filter order of the secondary path model. <code>pstates</code> defaults to a vector of zeros of appropriate length. The initial filter coefficients for the secondary path filter compose vector <code>coeffs</code>. It must be a length <code>l</code> vector. <code>coeffs</code> defaults to a length <code>l</code> vector of zeros. <code>states</code> is a vector containing the initial filter states. It must be a vector of length <code>l+ne-1</code>, where <code>ne</code> is the length of <code>errstates</code>. When you omit <code>states</code>, it defaults to an appropriate length vector of zeros.</p>

## Properties

In the syntax for creating the `adaptfilt` object, the input options are properties of the object created. This table lists the properties for the adjoint LMS object, their default values, and a brief description of the property.

Property	Default Value	Description
Algorithm	None	Specifies the adaptive filter algorithm the object uses during adaptation
Coefficients	Length <code>l</code> vector with zeros for all elements	Adjoint LMS FIR filter coefficients. Should be initialized with the initial coefficients for the FIR filter prior to adapting. You need <code>l</code> entries in <code>coefficients</code> . Updated filter coefficients are returned in <code>coefficients</code> when you use <code>s</code> as an output argument.
ErrorStates	[0,...,0]	A vector of the error states for your adaptive filter, with length equal to the order of your secondary path filter.
FilterLength	10	The number of coefficients in your adaptive filter.
Leakage	1	Specifies the leakage parameter. Allows you to implement a leaky algorithm. Including a leakage factor can improve the results of the algorithm by forcing the algorithm to continue to adapt even after it reaches a minimum value. Ranges between 0 and 1.
SecondaryPathCoeffs	No default	A vector that contains the coefficient values of your secondary path from the output actuator to the error sensor.
SecondaryPathEstimate	<code>pathcoeffs</code> values	An estimate of the secondary path filter model.

Property	Default Value	Description
SecondaryPathStates	Length of the secondary path filter. All elements are zeros.	The states of the secondary path filter, the unknown system
States	$l+ne+1$ , where $ne$ is <code>length(errstates)</code>	Contains the initial conditions for your adaptive filter and returns the states of the FIR filter after adaptation. If omitted, it defaults to a zero vector of length equal to $l+ne+1$ . When you use <code>adaptfilt.adjlims</code> in a loop structure, use this element to specify the initial filter states for the adapting FIR filter.
Stepsize	0.1	Sets the adjoint LMS algorithm step size used for each iteration of the adapting algorithm. Determines both how quickly and how closely the adaptive filter converges to the filter solution.
PersistentMemory	false or true	Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter. <code>PersistentMemory</code> returns to zero any state that the filter changes during processing. States that the filter does not change are not affected. Defaults to <code>false</code> .

### Examples


Demonstrate active noise control of a random noise signal that runs for 1000 samples.

```
x = randn(1,1000);    % Noise source
g = fir1(47,0.4);    % FIR primary path system model
```

# adaptfilt.adjlims

```
n = 0.1*randn(1,1000); % Observation noise signal
d = filter(g,1,x)+n; % Signal to be canceled (desired)
b = fir1(31,0.5); % FIR secondary path system model
mu = 0.008; % Adjoint LMS step size
ha = adaptfilt.adjlims(32,mu,1,b);
[y,e] = filter(ha,x,d);
plot(1:1000,d,'b',1:1000,e,'r');
title('Active Noise Control of a Random Noise Signal');
legend('Original','Attenuated');
xlabel('Time Index'); ylabel('Signal Value'); grid on;
```

Reviewing the figure shows that the adaptive filter attenuates the original noise signal as you expect.



## References

Wan, Eric., “Adjoint LMS: An Alternative to Filtered-X LMS and Multiple Error LMS,” Proceedings of the International Conference on Acoustics, Speech, and Signal Processing (ICASSP), pp. 1841-1845, 1997

## See Also

[adaptfilt.dlms](#) | [adaptfilt.filtxlms](#)

**Purpose** FIR adaptive filter that uses direct matrix inversion

**Syntax** `ha = adaptfilt.ap(1,step,projectord,offset,coeffs,states,...  
errstates,epsstates)`

**Description** `ha = adaptfilt.ap(1,step,projectord,offset,coeffs,states,...  
errstates,epsstates)` constructs an affine projection FIR adaptive filter `ha` using direct matrix inversion.

**Input Arguments**

Entries in the following table describe the input arguments for `adaptfilt.ap`.

<b>Input Argument</b>	<b>Description</b>
<code>1</code>	Adaptive filter length (the number of coefficients or taps) and it must be a positive integer. <code>1</code> defaults to 10.
<code>step</code>	Affine projection step size. This is a scalar that should be a value between zero and one. Setting <code>step</code> equal to one provides the fastest convergence during adaptation. <code>step</code> defaults to 1.
<code>projectord</code>	Projection order of the affine projection algorithm. <code>projectord</code> defines the size of the input signal covariance matrix and defaults to two.
<code>offset</code>	Offset for the input signal covariance matrix. You should initialize the covariance matrix to a diagonal matrix whose diagonal entries are equal to the <code>offset</code> you specify. <code>offset</code> should be positive. <code>offset</code> defaults to one.

<b>Input Argument</b>	<b>Description</b>
coeffs	Vector containing the initial filter coefficients. It must be a length 1 vector, the number of filter coefficients. coeffs defaults to length 1 vector of zeros when you do not provide the argument for input.
states	Vector of the adaptive filter states. states defaults to a vector of zeros which has length equal to $(1 + \text{projectord} - 2)$ .
errstates	Vector of the adaptive filter error states. errstates defaults to a zero vector with length equal to $(\text{projectord} - 1)$ .
epsstates	Vector of the epsilon values of the adaptive filter. epsstates defaults to a vector of zeros with $(\text{projectord} - 1)$ elements.

## Properties

Since your `adaptfilt.ap` filter is an object, it has properties that define its behavior in operation. Note that many of the properties are also input arguments for creating `adaptfilt.ap` objects. To show you the properties that apply, this table lists and describes each property for the affine projection filter object.

<b>Name</b>	<b>Range</b>	<b>Description</b>
Algorithm	None	Defines the adaptive filter algorithm the object uses during adaptation
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps

<b>Name</b>	<b>Range</b>	<b>Description</b>
ProjectionOrder	1 to as large as needed.	Projection order of the affine projection algorithm. ProjectionOrder defines the size of the input signal covariance matrix and defaults to two.
OffsetCov	Matrix of values	Contains the offset covariance matrix
Coefficients	Vector of elements	Vector containing the initial filter coefficients. It must be a length 1 vector, the number of filter coefficients. coeffs defaults to length 1 vector of zeros when you do not provide the argument for input.
States	Vector of elements, data type double	Vector of the adaptive filter states. states defaults to a vector of zeros which has length equal to $(1 + \text{projectord} - 2)$ .
ErrorStates	Vector of elements	Vector of the adaptive filter error states. errstates defaults to a zero vector with length equal to $(\text{projectord} - 1)$ .
EpsilonStates	Vector of elements	Vector of the epsilon values of the adaptive filter. epsstates defaults to a vector of zeros with $(\text{projectord} - 1)$ elements.

Name	Range	Description
StepSize	Any scalar from zero to one, inclusive	Specifies the step size taken between filter coefficient updates
PersistentMemory	false or true	Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter. PersistentMemory returns to zero any state that the filter changes during processing. States that the filter does not change are not affected. Defaults to true.

## Examples

Quadrature phase shift keying (QPSK) adaptive equalization using a 32-coefficient FIR filter. Run the adaptation for 1000 iterations.


```
D = 16; % Number of samples of delay
b = exp(j*pi/4)*[-0.7 1]; % Numerator coefficients of channel
a = [1 -0.7]; % Denominator coefficients of channel
ntr= 1000; % Number of iterations
s = sign(randn(1,ntr+D)) + j*sign(randn(1,ntr+D)); % Baseband Signal
n = 0.1*(randn(1,ntr+D) + j*randn(1,ntr+D)); % Noise signal
r = filter(b,a,s)+n; % Received signal
x = r(1+D:ntr+D); % Input signal (received signal)
d = s(1:ntr); % Desired signal (delayed QPSK signal)
mu = 0.1; % Step size
po = 4; % Projection order
offset = 0.05; % Offset for covariance matrix
ha = adaptfilt.ap(32,mu,po,offset);
[y,e] = filter(ha,x,d);
subplot(2,2,1); plot(1:ntr,real([d;y;e])); title('In-Phase Components');
```

```

legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,2,2); plot(1:ntr,imag([d;y;e]));
title('Quadrature Components');
legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,2,3); plot(x(ntr-100:ntr),'.');
axis([-3 3 -3 3]); title('Received Signal Scatter Plot');
axis('square'); xlabel('Real[x]'); ylabel('Imag[x]'); grid on;
subplot(2,2,4); plot(y(ntr-100:ntr),'.'); axis([-3 3 -3 3]);
title('Equalized Signal Scatter Plot');
axis('square'); xlabel('Real[y]'); ylabel('Imag[y]'); grid on;

```

The four plots shown reveal the QPSK process at work.



## References

- [1] Ozeki, K. and Umeda, T., "An Adaptive Filtering Algorithm Using an Orthogonal Projection to an Affine Subspace and Its Properties," Electronics and Communications in Japan, vol.67-A, no. 5, pp. 19-27, May 1984

[2] Maruyama, Y., "A Fast Method of Projection Algorithm," Proc. 1990 IEICE Spring Conf., B-744

## **See Also**

`msesim`

**Purpose** FIR adaptive filter that uses recursive matrix updating

**Syntax** `ha = adaptfilt.apru(l,step,projectord,offset,coeffs,states, ...errstates,epsstates)`

**Description** `ha = adaptfilt.apru(l,step,projectord,offset,coeffs,states, ...errstates,epsstates)` constructs an affine projection FIR adaptive filter `ha` using recursive matrix updating.

### Input Arguments

Entries in the following table describe the input arguments for `adaptfilt.apru`.

Input Argument	Description
<code>l</code>	Adaptive filter length (the number of coefficients or taps). It must be a positive integer. <code>l</code> defaults to 10.
<code>step</code>	Affine projection step size. This is a scalar that should be a value between zero and one. Setting <code>step</code> equal to one provides the fastest convergence during adaptation. <code>step</code> defaults to 1.
<code>projectord</code>	Projection order of the affine projection algorithm. <code>projectord</code> defines the size of the input signal covariance matrix and defaults to two.
<code>offset</code>	Offset for the input signal covariance matrix. You should initialize the covariance matrix to a diagonal matrix whose diagonal entries are equal to the offset you specify. <code>offset</code> should be positive. <code>offset</code> defaults to one.
<code>coeffs</code>	Vector containing the initial filter coefficients. It must be a length <code>l</code> vector, the number of filter coefficients. <code>coeffs</code> defaults to length <code>l</code> vector of zeros when you do not provide the argument for input.

<b>Input Argument</b>	<b>Description</b>
states	Vector of the adaptive filter states. states defaults to a vector of zeros which has length equal to $(1 + \text{projectord} - 2)$ .
errstates	Vector of the adaptive filter error states. errstates defaults to a zero vector with length equal to $(\text{projectord} - 1)$ .
epsstates	Vector of the epsilon values of the adaptive filter. epsstates defaults to a vector of zeros with $(\text{projectord} - 1)$ elements.

## Properties

Since your `adaptfilt.apru` filter is an object, it has properties that define its behavior in operation. Note that many of the properties are also input arguments for creating `adaptfilt.apru` objects. To show you the properties that apply, this table lists and describes each property for the affine projection filter object.

<b>Name</b>	<b>Range</b>	<b>Description</b>
Algorithm	None	Defines the adaptive filter algorithm the object uses during adaptation
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps
ProjectionOrder	1 to as large as needed.	Projection order of the affine projection algorithm. <code>ProjectionOrder</code> defines the size of the input signal covariance matrix and defaults to two.

Name	Range	Description
OffsetCov	Matrix of values	Contains the offset covariance matrix
Coefficients	Vector of elements	Vector containing the initial filter coefficients. It must be a length 1 vector, the number of filter coefficients. <code>coeffs</code> defaults to length 1 vector of zeros when you do not provide the argument for input.
States	Vector of elements, data type double	Vector of the adaptive filter states. <code>states</code> defaults to a vector of zeros which has length equal to $(1 + \text{projectord} - 2)$ .
ErrorStates	Vector of elements	Vector of the adaptive filter error states. <code>errstates</code> defaults to a zero vector with length equal to $(\text{projectord} - 1)$ .
EpsilonStates	Vector of elements	Vector of the epsilon values of the adaptive filter. <code>epsstates</code> defaults to a vector of zeros with $(\text{projectord} - 1)$ elements.

Name	Range	Description
StepSize	Any scalar from zero to one, inclusive	Specifies the step size taken between filter coefficient updates
PersistentMemory	false or true	Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter. PersistentMemory returns to zero any state that the filter changes during processing. States that the filter does not change are not affected. Defaults to true.

## Examples

Demonstrate quadrature phase shift keying (QPSK) adaptive equalization using a 32-coefficient FIR filter. This example runs the adaptation process for 1000 iterations.

```

D = 16; % Number of samples of delay
b = exp(1j*pi/4)*[-0.7 1]; % Numerator coefficients of channel
a = [1 -0.7]; % Denominator coefficients of channel
ntr= 1000; % Number of iterations
s = sign(randn(1,ntr+D)) + 1j*sign(randn(1,ntr+D)); % Baseband
n = 0.1*(randn(1,ntr+D) + 1j*randn(1,ntr+D)); % Noise signal
r = filter(b,a,s)+n; % Received signal
x = r(1+D:ntr+D); % Input signal (received signal)
d = s(1:ntr); % Desired signal (delayed QPSK signal)
mu = 0.1; % Step size
po = 4; % Projection order
offset = 0.05; % Offset
ha = adaptfilt.apru(32,mu,po,offset); [y,e] = filter(ha,x,d);
subplot(2,2,1); plot(1:ntr,real([d;y;e])); title('In-Phase Components');


```

```

legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,2,2); plot(1:ntr,imag([d;y;e])); title('Quadrature Components');
legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,2,3); plot(x(ntr-100:ntr),'.'); axis([-3 3 -3 3]);
title('Received Signal Scatter Plot');
axis('square'); xlabel('Real[x]'); ylabel('Imag[x]'); grid on;
subplot(2,2,4); plot(y(ntr-100:ntr),'.'); axis([-3 3 -3 3]);
title('Equalized Signal Scatter Plot');
axis('square'); xlabel('Real[y]'); ylabel('Imag[y]'); grid on;

```

In the following component and scatter plots, you see the results of QPSK equalization.



## References

- [1] Ozeki. K., T. Omeda, "An Adaptive Filtering Algorithm Using an Orthogonal Projection to an Affine Subspace and Its Properties," Electronics and Communications in Japan, vol. 67-A, no. 5, pp. 19-27, May 1984

[2] Maruyama, Y, "A Fast Method of Projection Algorithm," Proceedings 1990 IEICE Spring Conference, B-744

**See Also**

adaptfilt | adaptfilt.ap | adaptfilt.bap

**Purpose** FIR adaptive filter that uses block affine projection

**Syntax** `ha = adaptfilt.bap(1,step,projectord,offset,coeffs,states)`

**Description** `ha = adaptfilt.bap(1,step,projectord,offset,coeffs,states)` constructs a block affine projection FIR adaptive filter `ha`.

### Input Arguments

Entries in the following table describe the input arguments for `adaptfilt.bap`.

Input Argument	Description
<code>1</code>	Adaptive filter length (the number of coefficients or taps) and it must be a positive integer. <code>1</code> defaults to 10.
<code>step</code>	Affine projection step size. This is a scalar that should be a value between zero and one. Setting <code>step</code> equal to one provides the fastest convergence during adaptation. <code>step</code> defaults to 1.
<code>projectord</code>	Projection order of the affine projection algorithm. <code>projectord</code> defines the size of the input signal covariance matrix and defaults to two.
<code>offset</code>	Offset for the input signal covariance matrix. You should initialize the covariance matrix to a diagonal matrix whose diagonal entries are equal to the <code>offset</code> you specify. <code>offset</code> should be positive. <code>offset</code> defaults to one.

Input Argument	Description
coeffs	Vector containing the initial filter coefficients. It must be a length 1 vector, the number of filter coefficients. <code>coeffs</code> defaults to length 1 vector of zeros when you do not provide the argument for input.
states	Vector of the adaptive filter states. <code>states</code> defaults to a vector of zeros which has length equal to $(1 + \text{projectord} - 2)$ .

## Properties

Since your `adaptfilt.bap` filter is an object, it has properties that define its behavior in operation. Note that many of the properties are also input arguments for creating `adaptfilt.bap` objects. To show you the properties that apply, this table lists and describes each property for the affine projection filter object.

Name	Range	Description
Algorithm	None	Defines the adaptive filter algorithm the object uses during adaptation
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps
ProjectionOrder	1 to as large as needed.	Projection order of the affine projection algorithm. <code>ProjectionOrder</code> defines the size of the input signal covariance matrix and defaults to two.
OffsetCov	Matrix of values	Contains the offset covariance matrix

Name	Range	Description
Coefficients	Vector of elements	Vector containing the initial filter coefficients. It must be a length 1 vector, the number of filter coefficients. <code>coeffs</code> defaults to length 1 vector of zeros when you do not provide the argument for input.
States	Vector of elements, data type double	Vector of the adaptive filter states. <code>states</code> defaults to a vector of zeros which has length equal to $(1 + \text{projectord} - 2)$ .
StepSize	Any scalar from zero to one, inclusive	Specifies the step size taken between filter coefficient updates
PersistentMemory	false or true	Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter. <code>PersistentMemory</code> returns to zero any state that the filter changes during processing. States that the filter does not change are not affected. Defaults to true.


### Examples

Show an example of quadrature phase shift keying (QPSK) adaptive equalization using a 32-coefficient FIR filter.

```
D = 16; % delay
```

```
b = exp(1j*pi/4)*[-0.7 1];           % Numerator coefficients
a = [1 -0.7];                       % Denominator coefficients
ntr= 1000;                           % Number of iterations
s = sign(randn(1,ntr+D))+1j*sign(randn(1,ntr+D)); % Baseband signal
n = 0.1*(randn(1,ntr+D) + 1j*randn(1,ntr+D)); % Noise signal
r = filter(b,a,s)+n;                 % Received signal
x = r(1+D:ntr+D);                   % Input signal (received signal)
d = s(1:ntr);                       % Desired signal (delayed QPSK signal)
mu = 0.5;                           % Step size
po = 4;                             % Projection order
offset = 1.0;                       % Offset for covariance matrix
ha = adaptfilt.bap(32,mu,po,offset);
[y,e] = filter(ha,x,d); subplot(2,2,1);
plot(1:ntr,real([d;y;e]));
title('In-Phase Components'); legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,2,2); plot(1:ntr,imag([d;y;e]));
title('Quadrature Components');
legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,2,3); plot(x(ntr-100:ntr),'.'); axis([-3 3 -3 3]);
title('Received Signal Scatter Plot'); axis('square');
xlabel('Real[x]'); ylabel('Imag[x]'); grid on;
subplot(2,2,4); plot(y(ntr-100:ntr),'.'); axis([-3 3 -3 3]);
title('Equalized Signal Scatter Plot'); axis('square');
xlabel('Real[y]'); ylabel('Imag[y]'); grid on;
```

Using the block affine projection object in QPSK results in the plots shown here.



## References

- [1] Ozeki, K. and T. Omeda, "An Adaptive Filtering Algorithm Using an Orthogonal Projection to an Affine Subspace and Its Properties," *Electronics and Communications in Japan*, vol. 67-A, no. 5, pp. 19-27, May 1984
- [2] Montazeri, M. and Duhamel, P, "A Set of Algorithms Linking NLMS and Block RLS Algorithms," *IEEE Transactions Signal Processing*, vol. 43, no. 2, pp, 444-453, February 1995

## See Also

`adaptfilt` | `adaptfilt.ap` | `adaptfilt.apru`

# adaptfilt.blms

---

<b>Purpose</b>	FIR adaptive filter that uses BLMS
<b>Syntax</b>	<code>ha = adaptfilt.blms(l,step,leakage,blocklen,coeffs,states)</code>
<b>Description</b>	<p><code>ha = adaptfilt.blms(l,step,leakage,blocklen,coeffs,states)</code> constructs an FIR block LMS adaptive filter <code>ha</code>, where <code>l</code> is the adaptive filter length (the number of coefficients or taps) and must be a positive integer. <code>l</code> defaults to 10.</p> <p><code>step</code> is the block LMS step size. You must set <code>step</code> to a nonnegative scalar. You can use function <code>maxstep</code> to determine a reasonable range of step size values for the signals being processed. When unspecified, <code>step</code> defaults to 0.</p> <p><code>leakage</code> is the block LMS leakage factor. It must be a scalar between 0 and 1. If you set <code>leakage</code> to be less than one, you implement the leaky block LMS algorithm. <code>leakage</code> defaults to 1 specifying no leakage in the adapting algorithm.</p> <p><code>blocklen</code> is the block length used. It must be a positive integer and the signal vectors <code>d</code> and <code>x</code> should be divisible by <code>blocklen</code>. Larger block lengths result in faster per-sample execution times but with poor adaptation characteristics. When you choose <code>blocklen</code> such that <code>blocklen + length(coeffs)</code> is a power of 2, use <code>adaptfilt.blmsfft</code>. <code>blocklen</code> defaults to 1.</p> <p><code>coeffs</code> is a vector of initial filter coefficients. it must be a length <code>l</code> vector. <code>coeffs</code> defaults to length <code>l</code> vector of zeros.</p> <p><code>states</code> contains a vector of your initial filter states. It must be a length <code>l</code> vector and defaults to a length <code>l</code> vector of zeros when you do not include it in your calling function.</p>
<b>Properties</b>	In the syntax for creating the <code>adaptfilt</code> object, the input options are properties of the object created. This table lists the properties for the adjoint LMS object, their default values, and a brief description of the property.

<b>Property</b>	<b>Default Value</b>	<b>Description</b>
Algorithm	None	Defines the adaptive filter algorithm the object uses during adaptation
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps
Coefficients	Vector of elements	Vector containing the initial filter coefficients. It must be a length 1 vector where 1 is the number of filter coefficients. <code>coeffs</code> defaults to length 1 vector of zeros when you do not provide the argument for input.
States	Vector of elements	Vector of the adaptive filter states. <code>states</code> defaults to a vector of zeros which has length equal to 1
Leakage		Specifies the leakage parameter. Allows you to implement a leaky algorithm. Including a leakage factor can improve the results of the algorithm by forcing the algorithm to continue to adapt even after it reaches a minimum value. Ranges between 0 and 1.
BlockLength	Vector of length 1	Size of the blocks of data processed in each iteration

Property	Default Value	Description
StepSize	0.1	Sets the block LMS algorithm step size used for each iteration of the adapting algorithm. Determines both how quickly and how closely the adaptive filter converges to the filter solution. Use <code>maxstep</code> to determine the maximum usable step size.
PersistentMemory	false or true	Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter. <code>PersistentMemory</code> returns to zero any state that the filter changes during processing. States that the filter does not change are not affected. Defaults to <code>false</code> .

## Examples

Use an adaptive filter to identify an unknown 32nd-order FIR filter. In this example 500 input samples result in 500 iterations of the adaptation process. You see in the plot that follows the example code that the adaptive filter has determined the coefficients of the unknown system under test.


```
x = randn(1,500);           % Input to the filter
b = fir1(31,0.5);          % FIR system to be identified
no = 0.1*randn(1,500);     % Observation noise signal
d = filter(b,1,x)+no;      % Desired signal
mu = 0.008;                % Block LMS step size
n = 5;                     % Block length
ha = adaptfilt.blms(32,mu,1,n);
[y,e] = filter(ha,x,d);
subplot(2,1,1); plot(1:500,[d;y;e]);
```

```

title('System Identification of an FIR Filter');
legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,1,2); stem([b.','ha.coefficients.']);
legend('Actual','Estimated');
xlabel('Coefficient #'); ylabel('Coefficient Value');
grid on;

```

Based on looking at the figures here, the adaptive filter correctly identified the unknown system after 500 iterations, or fewer. In the lower plot, you see the comparison between the actual filter coefficients and those determined by the adaptation process.



**References**

Shynk, J.J., “Frequency-Domain and Multirate Adaptive Filtering,” IEEE Signal Processing Magazine, vol. 9, no. 1, pp. 14-37, Jan. 1992.

**See Also**

adaptfilt.blmsfft | adaptfilt.fdaf | adaptfilt.lms

# adaptfilt.blmsfft

---

**Purpose** FIR adaptive filter that uses FFT-based BLMS

**Syntax** `ha = adaptfilt.blmsfft(l,step,leakage,blocklen,coeffs,states)`

**Description** `ha = adaptfilt.blmsfft(l,step,leakage,blocklen,coeffs,states)` constructs an FIR block LMS adaptive filter object `ha` where `l` is the adaptive filter length (the number of coefficients or taps) and must be a positive integer. `l` defaults to 10. `step` is the block LMS step size. It must be a nonnegative scalar. The function `maxstep` may be helpful to determine a reasonable range of step size values for the signals you are processing. `step` defaults to 0.

`leakage` is the block LMS leakage factor. It must also be a scalar between 0 and 1. When `leakage` is less than one, the `adaptfilt.blmsfft` implements a leaky block LMS algorithm. `leakage` defaults to 1 (no leakage). `blocklen` is the block length used. It must be a positive integer such that

$$\text{blocklen} + \text{length}(\text{coeffs})$$

is a power of two; otherwise, an `adaptfilt.blms` algorithm is used for adapting. Larger block lengths result in faster execution times, with poor adaptation characteristics as the cost of the speed gained. `blocklen` defaults to 1. Enter your initial filter coefficients in `coeffs`, a vector of length `l`. When omitted, `coeffs` defaults to a length `l` vector of all zeros. `states` contains a vector of initial filter states; it must be a length `l` vector. `states` defaults to a length `l` vector of all zeros when you omit the `states` argument in the calling syntax.

**Properties** In the syntax for creating the `adaptfilt` object, the input options are properties of the object you create. This table lists the properties for the block LMS object, their default values, and a brief description of the property.

<b>Property</b>	<b>Default Value</b>	<b>Description</b>
Algorithm	None	Defines the adaptive filter algorithm the object uses during adaptation
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps
Coefficients	Vector of elements	Vector containing the initial filter coefficients. It must be a length 1 vector where 1 is the number of filter coefficients. <code>coefficients</code> defaults to length 1 vector of zeros when you do not provide the argument for input.
States	Vector of elements of length 1	Vector of the adaptive filter states. <code>states</code> defaults to a vector of zeros which has length equal to 1
Leakage	1	Specifies the leakage parameter. Allows you to implement a leaky algorithm. Including a leakage factor can improve the results of the algorithm by forcing the algorithm to continue to adapt even after it reaches a minimum value. Ranges between 0 and 1.
BlockLength	Vector of length 1	Size of the blocks of data processed in each iteration

Property	Default Value	Description
StepSize	0.1	Sets the block LMS algorithm step size used for each iteration of the adapting algorithm. Determines both how quickly and how closely the adaptive filter converges to the filter solution. Use <code>maxstep</code> to determine the maximum usable step size.
PersistentMemory	false or true	Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter. <code>PersistentMemory</code> returns to zero any state that the filter changes during processing. States that the filter does not change are not affected. Defaults to false.


## Examples

Identify an unknown FIR filter with 32 coefficients using 512 iterations of the adapting algorithm.

```
x = randn(1,512);           % Input to the filter
b = fir1(31,0.5);          % FIR system to be identified
no = 0.1*randn(1,512);     % Observation noise signal
d = filter(b,1,x)+no;      % Desired signal
mu = 0.008;                % Step size
n = 16;                    % Block length
ha = adaptfilt.blmsfft(32,mu,1,n);
[y,e] = filter(ha,x,d);
subplot(2,1,1); plot(1:500,[d(1:500);y(1:500);e(1:500)]);
title('System Identification of an FIR Filter');
legend('Desired','Output','Error'); xlabel('Time Index');
```

```
ylabel('Signal Value');
subplot(2,1,2); stem([b.',ha.coefficients.']);
legend('actual','estimated'); grid on;
xlabel('Coefficient #'); ylabel('Coefficient Value');
```

As a result of running the adaptation process, filter object ha now matches the unknown system FIR filter b, based on comparing the filter coefficients derived during adaptation.



**References**

Shynk, J.J., “Frequency-Domain and Multirate Adaptive Filtering,” IEEE Signal Processing Magazine, vol. 9, no. 1, pp. 14-37, Jan. 1992.

**See Also**

[adaptfilt.blms](#) | [adaptfilt.fdaf](#) | [adaptfilt.lms](#) | [filter](#)

# adaptfilt.dlms

---

**Purpose** FIR adaptive filter that uses delayed LMS

**Syntax** `ha = adaptfilt.dlms(1,step,leakage,delay,errstates,coeffs, ...states)`

**Description** `ha = adaptfilt.dlms(1,step,leakage,delay,errstates,coeffs, ...states)` constructs an FIR delayed LMS adaptive filter `ha`.

## Input Arguments

Entries in the following table describe the input arguments for `adaptfilt.dlms`.

Input Argument	Description
<code>1</code>	Adaptive filter length (the number of coefficients or taps) and it must be a positive integer. <code>1</code> defaults to 10.
<code>step</code>	LMS step size. It must be a nonnegative scalar. You can use <code>maxstep</code> to determine a reasonable range of step size values for the signals being processed. <code>step</code> defaults to 0.
<code>leakage</code>	Your LMS leakage factor. It must be a scalar between 0 and 1. When <code>leakage</code> is less than one, <code>adaptfilt.lms</code> implements a leaky LMS algorithm. When you omit the <code>leakage</code> property in the calling syntax, it defaults to 1 providing no leakage in the adapting algorithm.
<code>delay</code>	Update delay given in time samples. This scalar should be a positive integer — negative delays do not work. <code>delay</code> defaults to 1.
<code>errstates</code>	Vector of the error states of your adaptive filter. It must have a length equal to the update delay ( <code>delay</code> ) in samples. <code>errstates</code> defaults to an appropriate length vector of zeros.

Input Argument	Description
coeffs	Vector of initial filter coefficients. it must be a length 1 vector. coeffs defaults to length 1 vector with elements equal to zero.
states	Vector of initial filter states for the adaptive filter. It must be a length 1-1 vector. states defaults to a length 1-1 vector of zeros.

## Properties

In the syntax for creating the `adaptfilt` object, the input options are properties of the object you create. This table lists the properties for the block LMS object, their default values, and a brief description of the property.

Property	Default Value	Description
Algorithm	None	Defines the adaptive filter algorithm the object uses during adaptation
Coefficients	Vector of elements	Vector containing the initial filter coefficients. It must be a length 1 vector where 1 is the number of filter coefficients. coeffs defaults to length 1 vector of zeros when you do not provide the argument for input. LMS FIR filter coefficients. Should be initialized with the initial coefficients for the FIR filter prior to adapting. You need 1 entries in coeffs.
Delay	1	Specifies the update delay for the adaptive algorithm.

Property	Default Value	Description
ErrorStates	Vector of zeros with the number of elements equal to delay	A vector comprising the error states for the adaptive filter.
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps.
Leakage	1	Specifies the leakage parameter. Allows you to implement a leaky algorithm. Including a leakage factor can improve the results of the algorithm by forcing the algorithm to continue to adapt even after it reaches a minimum value. Ranges between 0 and 1.
PersistentMemory	false or true	Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter if you have not changed the filter since you constructed it. PersistentMemory returns to zero any state that the filter changes during processing. States that the filter does not change are not affected. Defaults to false.


Property	Default Value	Description
StepSize	0.1	Sets the LMS algorithm step size used for each iteration of the adapting algorithm. Determines both how quickly and how closely the adaptive filter converges to the filter solution.
States	Vector of elements, data type double	Vector of the adaptive filter states. <code>states</code> defaults to a vector of zeros which has length equal to $(1 + \text{projectord} - 2)$ .

## Examples

System identification of a 32-coefficient FIR filter. Refer to the figure that follows to see the results of the adapting filter process.

```
x = randn(1,500);      % Input to the filter
b = fir1(31,0.5);     % FIR system to be identified
n = 0.1*randn(1,500); % Observation noise signal
d = filter(b,1,x)+n;  % Desired signal
mu = 0.008;          % LMS step size.
delay = 1;           % Update delay
ha = adaptfilt.dlms(32,mu,1,delay);
[y,e] = filter(ha,x,d);
subplot(2,1,1); plot(1:500,[d;y;e]);
title('System Identification of an FIR Filter');
legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,1,2); stem([b.',ha.coefficients.']);
legend('Actual','Estimated'); grid on;
xlabel('Coefficient #'); ylabel('Coefficient Value');
```

Using a delayed LMS adaptive filter in the process to identify an unknown filter appears to work as planned, as shown in this figure.



## References

Shynk, J.J., "Frequency-Domain and Multirate Adaptive Filtering,"  
IEEE Signal Processing Magazine, vol. 9, no. 1, pp. 14-37, Jan. 1992.

## See Also

`adaptfilt.adj1ms` | `adaptfilt.filtx1ms` | `adaptfilt.1ms`

**Purpose** FIR adaptive filter that uses frequency-domain with bin step size normalization

**Syntax** `ha = adaptfilt.fdaf(l,step,leakage,delta,lambda,blocklen,offset,...coeffs,states)`

**Description** `ha = adaptfilt.fdaf(l,step,leakage,delta,lambda,blocklen,offset,...coeffs,states)` constructs a frequency-domain FIR adaptive filter `ha` with bin step size normalization. If you omit all the input arguments you create a default object with `l = 10` and `step = 1`.

### Input Arguments

Entries in the following table describe the input arguments for `adaptfilt.fdaf`.

Input Argument	Description
<code>l</code>	Adaptive filter length (the number of coefficients or taps). <code>l</code> must be a positive integer; it defaults to 10 when you omit the argument.
<code>step</code>	Step size of the adaptive filter. This is a scalar and should lie in the range (0,1]. <code>step</code> defaults to 1.
<code>leakage</code>	Leakage parameter of the adaptive filter. If this parameter is set to a value between zero and one, you implement a leaky FDAF algorithm. <code>leakage</code> defaults to 1 — no leakage provided in the algorithm.
<code>delta</code>	Initial common value of all of the FFT input signal powers. Its initial value should be positive. <code>delta</code> defaults to 1.
<code>lambda</code>	Specifies the averaging factor used to compute the exponentially-windowed FFT input signal powers for the coefficient updates. <code>lambda</code> should lie in the range (0,1]. <code>lambda</code> defaults to 0.9.

<b>Input Argument</b>	<b>Description</b>
<code>blocklen</code>	Block length for the coefficient updates. This must be a positive integer. For faster execution, $(\text{blocklen} + 1)$ should be a power of two. <code>blocklen</code> defaults to 1.
<code>offset</code>	Offset for the normalization terms in the coefficient updates. Use this to avoid divide by zeros or by very small numbers when any of the FFT input signal powers become very small. <code>offset</code> defaults to zero.
<code>coeffs</code>	Initial time-domain coefficients of the adaptive filter. <code>coeff</code> should be a length <code>l</code> vector. The adaptive filter object uses these coefficients to compute the initial frequency-domain filter coefficients via an FFT computed after zero-padding the time-domain vector by the <code>blocklen</code> .
<code>states</code>	The adaptive filter states. <code>states</code> defaults to a zero vector that has length equal to <code>l</code> .

## Properties

Since your `adaptfilt.fdaf` filter is an object, it has properties that define its behavior in operation. Note that many of the properties are also input arguments for creating `adaptfilt.fdaf` objects. To show you the properties that apply, this table lists and describes each property for the `adaptfilt.fdaf` filter object.

<b>Name</b>	<b>Range</b>	<b>Description</b>
Algorithm	None	Defines the adaptive filter algorithm the object uses during adaptation.
AvgFactor	(0, 1]	Specifies the averaging factor used to compute the exponentially-windowed FFT input signal powers for the coefficient updates. Same as the input argument <code>lambda</code> .
BlockLength	Any integer	Block length for the coefficient updates. This must be a positive integer. For faster execution, $(\text{blocklen} + 1)$ should be a power of two. <code>blocklen</code> defaults to 1.
FFTCoefficients		Stores the discrete Fourier transform of the filter coefficients in <code>coeffs</code> .
FFTStates		States for the FFT operation.
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps.
Leakage		Leakage parameter of the adaptive filter. if this parameter is set to a value between zero and one, you implement a leaky FDAF algorithm. <code>leakage</code> defaults to 1 — no leakage provided in the algorithm.

Name	Range	Description
Offset	Any positive real value	Offset for the normalization terms in the coefficient updates. Use this to avoid dividing by zero or by very small numbers when any of the FFT input signal powers become very small. <code>offset</code> defaults to zero.
PersistentMemory	false or true	Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter. <code>PersistentMemory</code> returns to zero any state that the filter changes during processing. States that the filter does not change are not affected. Defaults to <code>false</code> .
Power		A vector of 2*1 elements, each initialized with the value <code>delta</code> from the input arguments. As you filter data, <code>Power</code> gets updated by the filter process.
StepSize	Any scalar from zero to one, inclusive	Specifies the step size taken between filter coefficient updates


## Examples

Quadrature Phase Shift Keying (QPSK) adaptive equalization using 1024 iterations of a 32-coefficient FIR filter. After this example code, a figure demonstrates the equalization results.

```

D = 16; % Number of samples of delay
b = exp(1j*pi/4)*[-0.7 1]; % Numerator coefficients of channel
a = [1 -0.7]; % Denominator coefficients of channel
ntr= 1024; % Number of iterations
s = sign(randn(1,ntr+D))+1j*sign(randn(1,ntr+D)); %QPSK signal
n = 0.1*(randn(1,ntr+D) + 1j*randn(1,ntr+D)); % Noise signal
r = filter(b,a,s)+n; % Received signal
x = r(1+D:ntr+D); % Input signal (received signal)
d = s(1:ntr); % Desired signal (delayed QPSK signal)
del = 1; % Initial FFT input powers
mu = 0.1; % Step size
lam = 0.9; % Averaging factor
ha = adaptfilt.fdaf(32,mu,1,del,lam);
[y,e] = filter(ha,x,d);
subplot(2,2,1); plot(1:ntr,real([d;y;e])); title('In-Phase Components');
legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('signal value');
subplot(2,2,2); plot(1:ntr,imag([d;y;e])); title('Quadrature Components');
legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('signal value');
subplot(2,2,3); plot(x(ntr-100:ntr),'.'); axis([-3 3 -3 3]);
title('Received Signal Scatter Plot'); axis('square');
xlabel('Real[x]'); ylabel('Imag[x]'); grid on;
subplot(2,2,4); plot(y(ntr-100:ntr),'.'); axis([-3 3 -3 3]);
title('Equalized Signal Scatter Plot'); axis('square');
xlabel('Real[y]'); ylabel('Imag[y]'); grid on;

```



## References

Shynk, J.J., "Frequency-Domain and Multirate Adaptive Filtering,"  
IEEE Signal Processing Magazine, vol. 9, no. 1, pp. 14-37, Jan. 1992

## See Also

adaptfilt.ufdaf | adaptfilt.pbfdaf | adaptfilt.blms |  
adaptfilt.blmsfft

**Purpose** FIR adaptive filter that uses filtered-x LMS

**Syntax** `ha = adaptfilt.filtxLms(1,step,leakage,pathcoeffs,pathest,...errstates,pstates,coeffs,states)`

**Description** `ha = adaptfilt.filtxLms(1,step,leakage,pathcoeffs,pathest,...errstates,pstates,coeffs,states)` constructs an filtered-x LMS adaptive filter `ha`.

### Input Arguments

Entries in the following table describe the input arguments for `adaptfilt.filtxLms`.

Input Argument	Description
1	Adaptive filter length (the number of coefficients or taps) and it must be a positive integer. 1 defaults to 10.
step	Filtered LMS step size. it must be a nonnegative scalar. step defaults to 0.1.
leakage	is the filtered-x LMS leakage factor. it must be a scalar between 0 and 1. If it is less than one, a leaky version of <code>adaptfilt.filtxLms</code> is implemented. leakage defaults to 1 (no leakage).
pathcoeffs	is the secondary path filter model. this vector should contain the coefficient values of the secondary path from the output actuator to the error sensor.
pathest	is the estimate of the secondary path filter model. pathest defaults to the values in pathcoeffs.
fstates	is a vector of filtered input states of the adaptive filter. fstates defaults to a zero vector of length equal to $(1 - 1)$ .

Input Argument	Description
pstates	are the secondary path FIR filter states. it must be a vector of length equal to the $(\text{length}(\text{pathcoeffs}) - 1)$ . pstates defaults to a vector of zeros of appropriate length.
coeffs	is a vector of initial filter coefficients. it must be a length 1 vector. coeffs defaults to length 1 vector of zeros.
states	Vector of initial filter states. states defaults to a zero vector of length equal to the larger of $(\text{length}(\text{pathcoeffs}) - 1)$ and $(\text{length}(\text{pathest}) - 1)$ .

## Properties

In the syntax for creating the `adaptfilt` object, the input options are properties of the object created. This table lists the properties for the adjoint LMS object, their default values, and a brief description of the property.

Property	Default Value	Description
Algorithm	None	Defines the adaptive filter algorithm the object uses during adaptation
Coefficients	Vector of elements	Vector containing the initial filter coefficients. It must be a length 1 vector where 1 is the number of filter coefficients. coeffs defaults to length 1 vector of zeros when you do not provide the argument for input.

Property	Default Value	Description
FilteredInputStates	1-1	Vector of filtered input states with length equal to 1 - 1.
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps
States	Vector of elements	Vector of the adaptive filter states. <code>states</code> defaults to a vector of zeros which has length equal to $(1 + \text{projectord} - 2)$
SecondaryPathCoeffs	No default	A vector that contains the coefficient values of your secondary path from the output actuator to the error sensor
SecondaryPathEstimate	pathcoeffs values	An estimate of the secondary path filter model
SecondaryPathStates	Vector of size (length (pathcoeffs) - 1) with all elements equal to zero.	The states of the secondary path FIR filter — the unknown system
StepSize	0.1	Sets the filtered-x algorithm step size used for each iteration of the adapting algorithm. Determines both how quickly and how closely the


Property	Default Value	Description
		adaptive filter converges to the filter solution.

## Examples

Demonstrate active noise control of a random noise signal over 1000 iterations.

As the figure that follows this code demonstrates, the filtered-x LMS filter successfully controls random noise in this context.

```
x = randn(1,1000); % Noise source
g = fir1(47,0.4); % FIR primary path system model
n = 0.1*randn(1,1000); % Observation noise signal
d = filter(g,1,x)+n; % Signal to be cancelled
b = fir1(31,0.5); % FIR secondary path system model
mu = 0.008; % Filtered-X LMS step size
ha = adaptfilt.filtxllms(32,mu,1,b);
[y,e] = filter(ha,x,d); plot(1:1000,d,'b',1:1000,e,'r');
title('Active Noise Control of a Random Noise Signal');
legend('Original','Attenuated');
xlabel('Time Index'); ylabel('Signal Value'); grid on;
```



## See also

`adaptfilt.d1ms`, `adaptfilt.lms`

## References

Kuo, S.M., and Morgan, D.R. *Active Noise Control Systems: Algorithms and DSP Implementations*, New York, N.Y: John Wiley & Sons, 1996.

Widrow, B., and Stearns, S.D. *Adaptive Signal Processing*, Upper Saddle River, N.J: Prentice Hall, 1985.

# adaptfilt.ftf

---

**Purpose** Fast transversal LMS adaptive filter

**Syntax** `ha = adaptfilt.ftf(1,lambda,delta,gamma,gstates,coeffs,states)`

**Description** `ha = adaptfilt.ftf(1,lambda,delta,gamma,gstates,coeffs,states)` constructs a fast transversal least squares adaptive filter object `ha`.

## Input Arguments

Entries in the following table describe the input arguments for `adaptfilt.ftf`.

Input Argument	Description
<code>l</code>	Adaptive filter length (the number of coefficients or taps) and it must be a positive integer. <code>l</code> defaults to 10.
<code>lambda</code>	RLS forgetting factor. This is a scalar that should lie in the range $(1-0.5/l, 1]$ . <code>lambda</code> defaults to 1.
<code>delta</code>	Soft-constrained initialization factor. This scalar should be positive and sufficiently large to prevent an excessive number of Kalman gain rescues. <code>delta</code> defaults to one.
<code>gamma</code>	Conversion factor. <code>gamma</code> defaults to one specifying soft-constrained initialization.
<code>gstates</code>	States of the Kalman gain updates. <code>gstates</code> defaults to a zero vector of length <code>l</code> .
<code>coeffs</code>	Length <code>l</code> vector of initial filter coefficients. <code>coeffs</code> defaults to a length <code>l</code> vector of zeros.
<code>states</code>	Vector of initial filter States. <code>states</code> defaults to a zero vector of length $(l-1)$ .

## Properties

Since your `adaptfilt.ftf` filter is an object, it has properties that define its operating behavior. Note that many of the properties are also input arguments for creating `adaptfilt.ftf` objects. To show you the properties that apply, this table lists and describes each property for the fast transversal least squares filter object.

Name	Range	Description
Algorithm	None	Defines the adaptive filter algorithm the object uses during adaptation
BkwdPrediction		Returns the predicted samples generated during adaptation. Refer to [2] in the bibliography for details about linear prediction.
Coefficients	Vector of elements	Vector containing the initial filter coefficients. It must be a length 1 vector where 1 is the number of filter coefficients. <code>coeffs</code> defaults to length 1 vector of zeros when you do not provide the argument for input.
ConversionFactor		Conversion factor. Called <code>gamma</code> when it is an input argument, it defaults to the matrix [1 -1] that specifies soft-constrained initialization.
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps
ForgettingFactor		RLS forgetting factor. This is a scalar that should lie in the range (1-0.5/1, 1]. <code>lambda</code> defaults to 1.


Name	Range	Description
FwdPrediction		Contains the predicted values for samples during adaptation. Compare these to the actual samples to get the error and power.
InitFactor		Soft-constrained initialization factor. This scalar should be positive and sufficiently large to prevent an excessive number of Kalman gain rescues. <code>delta</code> defaults to one.
KalmanGain		Empty when you construct the object, this gets populated after you run the filter.
PersistentMemory	false or true	Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter if you have not changed the filter since you constructed it. <code>PersistentMemory</code> returns to zero any state that the filter changes during processing. States that the filter does not change are not affected. Defaults to <code>false</code> .
States	Vector of elements, data type double	Vector of the adaptive filter states. <code>states</code> defaults to a vector of zeros which has length equal to $(1 + \text{projectord} - 2)$ .

## Examples

System Identification of a 32-coefficient FIR filter by running the identification process for 500 iterations.

```
x = randn(1,500); % Input to the filter
b = fir1(31,0.5); % FIR system to be identified
n = 0.1*randn(1,500); % Observation noise signal
d = filter(b,1,x)+n; % Desired signal
N = 31; % Adaptive filter order
lam = 0.99; % RLS forgetting factor
del = 0.1; % Soft-constrained initialization factor
ha = adaptfilt.ftf(32,lam,del);
[y,e] = filter(ha,x,d);
subplot(2,1,1); plot(1:500,[d;y;e]);
title('System Identification of an FIR Filter');
legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('signal value');
subplot(2,1,2); stem([b.',ha.Coefficients.']);
legend('Actual','Estimated'); grid on;
xlabel('coefficient #'); ylabel('Coefficient Value');
```

For this example of identifying an unknown system, the figure shows that the adaptation process identifies the filter coefficients for the unknown FIR filter within the first 150 iterations.



## References

D.T.M. Slock and Kailath, T., "Numerically Stable Fast Transversal Filters for Recursive Least Squares Adaptive Filtering," IEEE Trans. Signal Processing, vol. 38, no. 1, pp. 92-114.

## See Also

`adaptfilt.swftf` | `adaptfilt.rls` | `adaptfilt.lsl`

**Purpose** FIR adaptive filter that uses gradient lattice

**Syntax** `ha = adaptfilt.gal(1,step,leakage,offset,rstep,delta,lambda,...rcoeffs,coeffs,states)`

**Description** `ha = adaptfilt.gal(1,step,leakage,offset,rstep,delta,lambda,...rcoeffs,coeffs,states)` constructs a gradient adaptive lattice FIR filter `ha`.

### Input Arguments

Entries in the following table describe the input arguments for `adaptfilt.gal`.

Input Argument	Description
<code>1</code>	Length of the joint process filter coefficients. It must be a positive integer and must be equal to the length of the reflection coefficients plus one. <code>1</code> defaults to 10.
<code>step</code>	Joint process step size of the adaptive filter. This scalar should be a value between zero and one. <code>step</code> defaults to 0.
<code>leakage</code>	Leakage factor of the adaptive filter. It must be a scalar between 0 and 1. Setting leakage less than one implements a leaky algorithm to estimate both the reflection and the joint process coefficients. <code>leakage</code> defaults to 1 (no leakage).
<code>offset</code>	Specifies an optional offset for the denominator of the step size normalization term. It must be a scalar greater or equal to zero. A non-zero <code>offset</code> is useful to avoid divide-by-near-zero conditions when the input signal amplitude becomes very small. <code>offset</code> defaults to 1.

<b>Input Argument</b>	<b>Description</b>
<code>rstep</code>	Reflection process step size of the adaptive filter. This scalar should be a value between zero and one. <code>rstep</code> defaults to <code>step</code> .
<code>delta</code>	Initial common value of the forward and backward prediction error powers. It should be a positive value. 0.1 is the default value for <code>delta</code> .
<code>lambda</code>	Specifies the averaging factor used to compute the exponentially windowed forward and backward prediction error powers for the coefficient updates. <code>lambda</code> should lie in the range (0, 1]. <code>lambda</code> defaults to the value (1 - <code>step</code> ).
<code>rcoeffs</code>	Vector of initial reflection coefficients. It should be a length (l-1) vector. <code>rcoeffs</code> defaults to a zero vector of length (l-1).
<code>coeffs</code>	Vector of initial joint process filter coefficients. It must be a length l vector. <code>coeffs</code> defaults to a length l vector of zeros.
<code>states</code>	Vector of the backward prediction error states of the adaptive filter. <code>states</code> defaults to a zero vector of length (l-1).

## Properties

Since your `adaptfilt.gal` filter is an object, it has properties that define its behavior in operation. Note that many of the properties are also input arguments for creating `adaptfilt.gal` objects. To show you the properties that apply, this table lists and describes each property for the affine projection filter object.

Name	Range	Description
Algorithm	None	Defines the adaptive filter algorithm the object uses during adaptation
AvgFactor		Specifies the averaging factor used to compute the exponentially-windowed forward and backward prediction error powers for the coefficient updates. Same as the input argument <code>lambda</code> .
BkwdPredErrorPower		Returns the minimum mean-squared prediction error. Refer to [2] in the bibliography for details about linear prediction
Coefficients	Vector of elements	Vector containing the initial filter coefficients. It must be a length <code>1</code> vector where <code>1</code> is the number of filter coefficients. <code>coeffs</code> defaults to length <code>1</code> vector of zeros when you do not provide the argument for input.
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps
FwdPredErrorPower		Returns the minimum mean-squared prediction error in the forward direction. Refer to [2] in the bibliography for details about linear prediction.

Name	Range	Description
Leakage	0 to 1	Leakage parameter of the adaptive filter. If this parameter is set to a value between zero and one, you implement a leaky GAL algorithm. <code>leakage</code> defaults to 1 — no leakage provided in the algorithm.
Offset		Offset for the normalization terms in the coefficient updates. Use this to avoid dividing by zero or by very small numbers when input signal amplitude becomes very small. <code>offset</code> defaults to one.
PersistentMemory	false or true	Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter if you have not changed the filter since you constructed it. <code>PersistentMemory</code> returns to zero any state that the filter changes during processing. States that the filter does not change are not affected. Defaults to <code>false</code> .
ReflectionCoeffs		Coefficients determined for the reflection portion of the filter during adaptation.

Name	Range	Description
ReflectionCoeffsStep		Size of the steps used to determine the reflection coefficients.
States	Vector of elements	Vector of the adaptive filter states. <code>states</code> defaults to a vector of zeros which has length equal to $(1 + \text{projectord} - 2)$ .
StepSize	0 to 1	Specifies the step size taken between filter coefficient updates


## Examples

Perform a Quadrature Phase Shift Keying (QPSK) adaptive equalization using a 32-coefficient adaptive filter over 1000 iterations.

```
D = 16; % Number of delay samples
b = exp(1j*pi/4)*[-0.7 1]; % Numerator coefficients
a = [1 -0.7]; % Denominator coefficients
ntr= 1000; % Number of iterations
s = sign(randn(1,ntr+D)) + 1j*sign(randn(1,ntr+D)); % QPSK signal
n = 0.1*(randn(1,ntr+D) + 1j*randn(1,ntr+D)); % Noise signal
r = filter(b,a,s)+n; % Received signal
x = r(1+D:ntr+D); % Input signal (received signal)
d = s(1:ntr); % Desired signal (delayed QPSK signal)
L = 32; % filter length
mu = 0.007; % Step size
ha = adaptfilt.gal(L,mu);
[y,e] = filter(ha,x,d);
subplot(2,2,1); plot(1:ntr,real([d;y;e]));
title('In-Phase Components');
legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('signal value');
subplot(2,2,2); plot(1:ntr,imag([d;y;e]));
title('Quadrature Components');
legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
```

```
subplot(2,2,3); plot(x(ntr-100:ntr),'.'); axis([-3 3 -3 3]);  
title('Received Signal Scatter Plot'); axis('square');  
xlabel('Real[x]'); ylabel('Imag[x]'); grid on;  
subplot(2,2,4); plot(y(ntr-100:ntr),'.');  
axis([-3 3 -3 3]); title('Equalized Signal Scatter Plot');  
axis('square'); xlabel('Real[y]'); ylabel('Imag[y]'); grid on;
```

To see the results, look at this figure.



## References

Griffiths, L.J. "A Continuously Adaptive Filter Implemented as a Lattice Structure," Proc. IEEE Int. Conf. on Acoustics, Speech, and Signal Processing, Hartford, CT, pp. 683-686, 1977

Haykin, S., *Adaptive Filter Theory*, 3rd Ed., Upper Saddle River, NJ, Prentice Hall, 1996

## See Also

`adaptfilt.qrdls1` | `adaptfilt.ls1` | `adaptfilt.tdafdft`

**Purpose** FIR adaptive filter that uses householder (RLS)

**Syntax** `ha = adaptfilt.hrls(1,lambda,sqrtinvcov,coeffs,states)`

**Description** `ha = adaptfilt.hrls(1,lambda,sqrtinvcov,coeffs,states)` constructs an FIR householder RLS adaptive filter `ha`.

### Input Arguments

Entries in the following table describe the input arguments for `adaptfilt.hrls`.

Input Argument	Description
<code>l</code>	Adaptive filter length (the number of coefficients or taps) and it must be a positive integer. <code>l</code> defaults to 10.
<code>lambda</code>	RLS forgetting factor. This is a scalar and should lie in the range (0, 1]. <code>lambda</code> defaults to 1 meaning the adaptation process retains infinite memory.
<code>sqrtinvcov</code>	Square-root of the inverse of the sliding window input signal covariance matrix. This square matrix should be full-ranked.
<code>coeffs</code>	Vector of initial filter coefficients. It must be a length <code>l</code> vector. <code>coeffs</code> defaults to being a length <code>l</code> vector of zeros.
<code>states</code>	Vector of initial filter states. It must be a length <code>l-1</code> vector. <code>states</code> defaults to a length <code>l-1</code> vector of zeros.

### Properties

Since your `adaptfilt.hrls` filter is an object, it has properties that define its behavior in operation. Note that many of the properties are also input arguments for creating `adaptfilt.hrls` objects. To show you the properties that apply, this table lists and describes each property for the affine projection filter object.

Name	Range	Description
Algorithm	None	Defines the adaptive filter algorithm the object uses during adaptation
Coefficients	Vector of elements	Vector containing the initial filter coefficients. It must be a length 1 vector where 1 is the number of filter coefficients. <code>coeffs</code> defaults to length 1 vector of zeros when you do not provide the argument for input.
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps
ForgettingFactor	Scalar	RLS forgetting factor. This is a scalar and should lie in the range (0, 1]. Same as input argument <code>lambda</code> . It defaults to 1 meaning the adaptation process retains infinite memory.
KalmanGain	Vector of size (1,1)	Empty when you construct the object, this gets populated after you run the filter.


Name	Range	Description
PersistentMemory	false or true	Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter if you have not changed the filter since you constructed it. PersistentMemory returns to zero any state that the filter changes during processing. Defaults to false.
SqrtInvCov	Matrix of doubles	Square root of the inverse of the sliding window input signal covariance matrix. This square matrix should be full-ranked.
States	Vector of elements, data type double	Vector of the adaptive filter states. states defaults to a vector of zeros which has length equal to (1 - 1).

## Examples

Use 500 iterations of an adaptive filter object to identify a 32-coefficient FIR filter system. Both the example code and the resulting figure show the successful filter identification through adaptive filter processing.

```
x = randn(1,500); % Input to the filter
b = fir1(31,0.5); % FIR system to be identified
n = 0.1*randn(1,500); % Observation noise signal
d = filter(b,1,x)+n; % Desired signal
G0 = sqrt(10)*eye(32); % Initial sqrt correlation matrix inverse
lam = 0.99; % RLS forgetting factor
ha = adaptfilt.hrls(32,lam,G0);
[y,e] = filter(ha,x,d);
subplot(2,1,1); plot(1:500,[d;y;e]);
```

```
title('System Identification of an FIR Filter');  
legend('Desired','Output','Error');  
xlabel('Time Index'); ylabel('Signal Value');  
subplot(2,1,2); stem([b.','ha.Coefficients.']);  
legend('Actual','Estimated'); grid on;  
xlabel('Coefficient #'); ylabel('Coefficient Value');
```



## See Also

[adaptfilt.hswrls](#) | [adaptfilt.qrdrls](#) | [adaptfilt.rls](#)

**Purpose** FIR adaptive filter that uses householder sliding window RLS

**Syntax** `ha = adaptfilt.hswrls(1,lambda,sqrtinvcov,swblocklen,dstates,coeffs,states)`

**Description** `ha = adaptfilt.hswrls(1,lambda,sqrtinvcov,swblocklen,dstates,coeffs,states)` constructs an FIR householder sliding window recursive-least-square adaptive filter `ha`.

### Input Arguments

Entries in the following table describe the input arguments for `adaptfilt.hswrls`.

Input Argument	Description
<code>1</code>	Adaptive filter length (the number of coefficients or taps) and it must be a positive integer. <code>1</code> defaults to 10.
<code>lambda</code>	Recursive least square (RLS) forgetting factor. This is a scalar and should lie in the range (0, 1]. <code>lambda</code> defaults to 1 meaning the adaptation process retains infinite memory.
<code>sqrtinvcov</code>	Square-root of the inverse of the sliding window input signal covariance matrix. This square matrix should be full-ranked.
<code>swblocklen</code>	Block length of the sliding window. This integer must be at least as large as the filter length. <code>swblocklen</code> defaults to 16.
<code>dstates</code>	Desired signal states of the adaptive filter. <code>dstates</code> defaults to a zero vector with length equal to $(swblocklen - 1)$ .

# adaptfilt.hswrls

---

Input Argument	Description
coeffs	Vector of initial filter coefficients. It must be a length 1 vector. coeffs defaults to being a length 1 vector of zeros.
states	Vector of initial filter states. It must be a length $(1 + \text{swblocklen} - 2)$ vector. states defaults to a length $(1 + \text{swblocklen} - 2)$ vector of zeros.

## Properties

Since your `adaptfilt.hswrls` filter is an object, it has properties that define its behavior in operation. Note that many of the properties are also input arguments for creating `adaptfilt.hswrls` objects. To show you the properties that apply, this table lists and describes each property for the affine projection filter object.

Name	Range	Description
Algorithm	None	Defines the adaptive filter algorithm the object uses during adaptation
Coefficients	Vector of elements	Vector containing the initial filter coefficients. It must be a length 1 vector where 1 is the number of filter coefficients. coeffs defaults to length 1 vector of zeros when you do not provide the argument for input.
DesiredSignalStates	Vector	Desired signal states of the adaptive filter. dstates defaults to a zero vector with length equal to $(\text{swblocklen} - 1)$ .

Name	Range	Description
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps
ForgettingFactor	Scalar	Root-least-square (RLS) forgetting factor. This is a scalar and should lie in the range (0, 1]. Same as input argument lambda. It defaults to 1 meaning the adaptation process retains infinite memory.
KalmanGain	(1,1) vector	Empty when you construct the object, this gets populated after you run the filter.
PersistentMemory	false or true	Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter if you have not changed the filter since you constructed it. PersistentMemory returns to zero any state that the filter changes during processing. Defaults to false.
SqrtInvCov	1-by-1 Matrix	Square-root of the inverse of the sliding window input signal covariance matrix. This square matrix should be full-ranked.


Name	Range	Description
States	Vector of elements, data type double	Vector of the adaptive filter states. <code>states</code> defaults to a vector of zeros which has length equal to $(1 + \text{projectord} - 2)$ .
SwBlockLength	Integer	Block length of the sliding window. This integer must be at least as large as the filter length. <code>swblocklen</code> defaults to 16.

## Examples

System Identification of a 32-coefficient FIR filter.

```
x = randn(1,500); % Input to the filter
b = fir1(31,0.5); % FIR system to be identified
n = 0.1*randn(1,500); % Observation noise signal
d = filter(b,1,x)+n; % Desired signal
G0 = sqrt(10)*eye(32); % Initial sqrt correlation matrix inverse
lam = 0.99; % RLS forgetting factor
N = 64; % block length
ha = adaptfilt.hswrls(32,lam,G0,N);
[y,e] = filter(ha,x,d);
subplot(2,1,1); plot(1:500,[d;y;e]);
title('System Identification of an FIR Filter');
legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,1,2); stem([b.',ha.Coefficients.']);
legend('Actual','Estimated'); grid on;
xlabel('Coefficient #'); ylabel('Coefficient Value');
```

In the pair of plots shown in the figure you see the comparison of the desired and actual output for the adapting filter and the coefficients of both filters, the unknown and the adapted.



## See Also

[adaptfilt.hrls](#) | [adaptfilt.qrdrls](#) | [adaptfilt.rls](#)

# adaptfilt.lms

---

**Purpose** FIR adaptive filter that uses LMS

**Syntax** `ha = adaptfilt.lms(l,step,leakage,coeffs,states)`

**Description** `ha = adaptfilt.lms(l,step,leakage,coeffs,states)` constructs an FIR LMS adaptive filter object `ha`.

## Input Arguments

Entries in the following table describe the input arguments for `adaptfilt.lms`.

Input Argument	Description
<code>l</code>	Adaptive filter length (the number of coefficients or taps) and it must be a positive integer. <code>l</code> defaults to 10.
<code>step</code>	LMS step size. It must be a nonnegative scalar. You can use <code>maxstep</code> to determine a reasonable range of step size values for the signals being processed. <code>step</code> defaults to 0.1.
<code>leakage</code>	Your LMS leakage factor. It must be a scalar between 0 and 1. When <code>leakage</code> is less than one, <code>adaptfilt.lms</code> implements a leaky LMS algorithm. When you omit the <code>leakage</code> property in the calling syntax, it defaults to 1 providing no leakage in the adapting algorithm.
<code>coeffs</code>	Vector of initial filter coefficients. it must be a length <code>l</code> vector. <code>coeffs</code> defaults to length <code>l</code> vector with elements equal to zero.
<code>states</code>	Vector of initial filter states for the adaptive filter. It must be a length <code>l-1</code> vector. <code>states</code> defaults to a length <code>l-1</code> vector of zeros.

## Properties

In the syntax for creating the `adaptfilt` object, the input options are properties of the object created. This table lists the properties for the `adaptfilt.lms` object, their default values, and a brief description of the property.

Property	Range	Property Description
Algorithm	None	Reports the adaptive filter algorithm the object uses during adaptation
Coefficients	Vector of elements	Vector containing the initial filter coefficients. It must be a length <code>l</code> vector where <code>l</code> is the number of filter coefficients. <code>coeffs</code> defaults to a length <code>l</code> vector of zeros when you do not provide the vector as an input argument.
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps
Leakage	0 to 1	LMS leakage factor. It must be a scalar between zero and one. When it is less than one, a leaky NLMS algorithm results. <code>leakage</code> defaults to 1 (no leakage).

Property	Range	Property Description
PersistentMemory	false or true	Determine whether the filter states and coefficients get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter. PersistentMemory returns to zero any property value that the filter changes during processing. Property values that the filter does not change are not affected. Defaults to false.
States	Vector of elements, data type double	Vector of the adaptive filter states. states defaults to a vector of zeros which has length equal to (1 - 1).
StepSize	0 to 1	LMS step size. It must be a scalar between zero and one. Setting this step size value to one provides the fastest convergence. step defaults to 0.1.

## Examples

Use 500 iterations of an adapting filter system to identify and unknown 32nd-order FIR filter.


```
x = randn(1,500); % Input to the filter
b = fir1(31,0.5); % FIR system to be identified
n = 0.1*randn(1,500); % Observation noise signal
d = filter(b,1,x)+n; % Desired signal
mu = 0.008; % LMS step size.
ha = adaptfilt.lms(32,mu);
[y,e] = filter(ha,x,d);
subplot(2,1,1); plot(1:500,[d;y;e]);
```

```

title('System Identification of an FIR Filter');
legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,1,2); stem([b.','ha.coefficients.']);
legend('Actual','Estimated');
xlabel('Coefficient #'); ylabel('Coefficient Value'); grid on;

```

Using LMS filters in an adaptive filter architecture is a time honored means for identifying an unknown filter. By running the example code provided you can demonstrate one process to identify an unknown FIR filter.



## References

Shynk J.J., “Frequency-Domain and Multirate Adaptive Filtering,”  
 IEEE Signal Processing Magazine, vol. 9, no. 1, pp. 14-37, Jan. 1992.

## See Also

adaptfilt.blms | adaptfilt.blmsfft | adaptfilt.dlms  
 | adaptfilt.nlms | adaptfilt.tdafdft | adaptfilt.sd |  
 adaptfilt.se | adaptfilt.ss

# adaptfilt.lsl

---

**Purpose** Least squares lattice adaptive filter

**Syntax** `ha = adaptfilt.lsl(1,lambda,delta,coeffs,states)`

**Description** `ha = adaptfilt.lsl(1,lambda,delta,coeffs,states)` constructs a least squares lattice adaptive filter `ha`.

## Input Arguments

Entries in the following table describe the input arguments for `adaptfilt.lsl`.

Input Argument	Description
<code>l</code>	Length of the joint process filter coefficients. It must be a positive integer and must be equal to the length of the prediction coefficients plus one. <code>L</code> defaults to 10.
<code>lambda</code>	Forgetting factor of the adaptive filter. This is a scalar and should lie in the range (0, 1]. <code>lambda</code> defaults to 1. <code>lambda = 1</code> denotes infinite memory while adapting to find the new filter.
<code>delta</code>	Soft-constrained initialization factor in the least squares lattice algorithm. It should be positive. <code>delta</code> defaults to 1.
<code>coeffs</code>	Vector of initial joint process filter coefficients. It must be a length <code>l</code> vector. <code>coeffs</code> defaults to a length <code>l</code> vector of all zeros.
<code>states</code>	Vector of the backward prediction error states of the adaptive filter. <code>states</code> defaults to a length <code>l</code> vector of all zeros, specifying soft-constrained initialization for the algorithm.

## Properties

Since your `adaptfilt.lsl` filter is an object, it has properties that define its behavior in operation. Note that many of the properties are

also input arguments for creating `adaptfilt.lsl` objects. To show you the properties that apply, this table lists and describes each property for the filter object.

Name	Range	Description
Algorithm	None	Defines the adaptive filter algorithm the object uses during adaptation.
BkwdPrediction		Returns the predicted samples generated during adaptation. Refer to [2] in the bibliography for details about linear prediction.
Coefficients	Vector of elements	Vector containing the initial filter coefficients. It must be a length <code>l</code> vector where <code>l</code> is the number of filter coefficients. <code>coeffs</code> defaults to length <code>l</code> vector of zeros when you do not provide the argument for input.
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps.
ForgettingFactor		Forgetting factor of the adaptive filter. This is a scalar and should lie in the range (0, 1]. It defaults to 1. Setting forgetting factor = 1 denotes infinite memory while adapting to find the new filter. Note that this is the <code>lambda</code> input argument.

Name	Range	Description
FwdPrediction		Contains the predicted values for samples during adaptation. Compare these to the actual samples to get the error and power.
InitFactor		Soft-constrained initialization factor. This scalar should be positive and sufficiently large to prevent an excessive number of Kalman gain rescues. <code>delta</code> defaults to one.
PersistentMemory	false or true	Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter if you have not changed the filter since you constructed it. <code>PersistentMemory</code> returns to zero any state that the filter changes during processing. States that the filter does not change are not affected. Defaults to false.
States	Vector of elements, data type double	Vector of the adaptive filter states. <code>states</code> defaults to a vector of zeros which has length equal to 1.


## Examples

Demonstrate Quadrature Phase Shift Keying (QPSK) adaptive equalization using a 32-coefficient adaptive filter running for 1000 iterations. After you review the example code, the figure shows the results of running the example to use QPSK adaptive equalization with a 32nd-order FIR filter. The error between the in-phase and quadrature components, as shown by the errors plotted in the upper plots, falls to near zero. Also, the equalized signal shows the clear quadrature nature.

```

D = 16; % Number of samples of delay
b = exp(1j*pi/4)*[-0.7 1]; % Numerator coefficients of channel
a = [1 -0.7]; % Denominator coefficients of channel
ntr= 1000; % Number of iterations
s = sign(randn(1,ntr+D))+1j*sign(randn(1,ntr+D)); % QPSK signal
n = 0.1*(randn(1,ntr+D) + 1j*randn(1,ntr+D)); % Noise signal
r = filter(b,a,s)+n; % Received signal
x = r(1+D:ntr+D); % Input signal (received signal)
d = s(1:ntr); % Desired signal (delayed QPSK signal)
lam = 0.995; % Forgetting factor
del = 1; % initialization factor
ha = adaptfilt.lsl(32,lam,del);
[y,e] = filter(ha,x,d);
subplot(2,2,1); plot(1:ntr,real([d;y;e]));
title('In-Phase Components');
legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,2,2); plot(1:ntr,imag([d;y;e]));
title('Quadrature Components');
legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,2,3); plot(x(ntr-100:ntr),'.'); axis([-3 3 -3 3]);
title('Received Signal Scatter Plot'); axis('square');
xlabel('Real[x]'); ylabel('Imag[x]'); grid on;
subplot(2,2,4); plot(y(ntr-100:ntr),'.'); axis([-3 3 -3 3]);
title('Equalized Signal Scatter Plot'); grid on;
axis('square'); xlabel('Real[y]'); ylabel('Imag[y]');

```



## References

Haykin, S., *Adaptive Filter Theory*, 2nd Edition, Prentice Hall, N.J., 1991

## See Also

`adaptfilt.qrdls1` | `adaptfilt.gal` | `adaptfilt.ftf` | `adaptfilt.rls`

## Purpose

Normalized least mean squares adaptive filter

## Syntax

`ha = adaptfilt.nlms(1,step,leakage,offset,coeffs,states)`

## Description

`ha = adaptfilt.nlms(1,step,leakage,offset,coeffs,states)` constructs a normalized least-mean squares (NLMS) FIR adaptive filter object named `ha`.

## Input Arguments

Entries in the following table describe the input arguments for `adaptfilt.nlms`.

Input Argument	Description
<code>1</code>	Adaptive filter length (the number of coefficients or taps) and it must be a positive integer. <code>1</code> defaults to 10.
<code>step</code>	NLMS step size. It must be a scalar between 0 and 2. Setting this step size value to one provides the fastest convergence. <code>step</code> defaults to 1.
<code>leakage</code>	NLMS leakage factor. It must be a scalar between zero and one. When it is less than one, a leaky NLMS algorithm results. <code>leakage</code> defaults to 1 (no leakage).
<code>offset</code>	Specifies an optional offset for the denominator of the step size normalization term. You must specify <code>offset</code> to be a scalar greater than or equal to zero. Nonzero offsets can help avoid a divide-by-near-zero condition that causes errors. Use this to avoid dividing by zero (or by very small numbers) when the square of the input data norm becomes very small (when the input signal amplitude becomes very small). When you omit it, <code>offset</code> defaults to zero.

Input Argument	Description
coeffs	Vector composed of your initial filter coefficients. Enter a length 1 vector. coeffs defaults to a vector of zeros with length equal to the filter order.
states	Your initial adaptive filter states appear in the states vector. It must be a vector of length 1-1. states defaults to a length 1-1 vector with zeros for all of the elements.

## Properties

In the syntax for creating the `adaptfilt` object, the input options are properties of the object you create. This table lists the properties for normalized LMS objects, their default values, and a brief description of the property.

Property	Range	Property Description
Algorithm	None	Reports the adaptive filter algorithm the object uses during adaptation
Coefficients	Vector of elements	Vector containing the initial filter coefficients. It must be a length 1 vector where 1 is the number of filter coefficients. coeffs defaults to length 1 vector of zeros when you do not provide the argument for input.
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps

<b>Property</b>	<b>Range</b>	<b>Property Description</b>
Leakage	0 to 1	NLMS leakage factor. It must be a scalar between zero and one. When it is less than one, a leaky NLMS algorithm results. <code>leakage</code> defaults to 1 (no leakage).
Offset	0 or greater	Specifies an optional offset for the denominator of the step size normalization term. You must specify <code>offset</code> to be a scalar greater than or equal to zero. Nonzero offsets can help avoid a divide-by-near-zero condition that causes errors. Use this to avoid dividing by zero (or by very small numbers) when the square of the input data norm becomes very small (when the input signal amplitude becomes very small). When you omit it, <code>offset</code> defaults to zero.
PersistentMemory	false or true	Determine whether the filter states and coefficients get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter. <code>PersistentMemory</code> returns to zero any property value that the filter changes during processing. Property values that the filter does not change are not affected. Defaults to <code>false</code> .


Property	Range	Property Description
States	Vector of elements, data type double	Vector of the adaptive filter states. <code>states</code> defaults to a vector of zeros which has length equal to $(1 - 1)$ .
StepSize	0 to 1	NLMS step size. It must be a scalar between zero and one. Setting this step size value to one provides the fastest convergence. <code>step</code> defaults to one.

## Examples

To help you compare this algorithm's performance to other LMS-based algorithms, such as BLMS or LMS, this example demonstrates the NLMS adaptive filter in use to identify the coefficients of an unknown FIR filter of order equal to 32 — an example used in other adaptive filter examples.

```
x = randn(1,500); % Input to the filter
b = fir1(31,0.5); % FIR system to be identified
n = 0.1*randn(1,500); % Observation noise signal
d = filter(b,1,x)+n; % Desired signal
mu = 1; % NLMS step size
offset = 50; % NLMS offset
ha = adaptfilt.nlms(32,mu,1,offset);
[y,e] = filter(ha,x,d);
subplot(2,1,1);
plot(1:500,[d;y;e]);
legend('Desired','Output','Error');
title('System Identification of FIR Filter');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,1,2);
stem([b', ha.coefficients']);
legend('Actual','Estimated'); grid on;
xlabel('Coefficient #'); ylabel('Coefficient Value');
```

As you see from the figure, the nlms variant again closely matches the actual filter coefficients in the unknown FIR filter.



**See Also**

[adaptfilt.ap](#) | [adaptfilt.apru](#) | [adaptfilt.lms](#) | [adaptfilt.rls](#)  
| [adaptfilt.swrls](#)

# adaptfilt.pbfdaf

---

**Purpose** Partitioned block frequency-domain FIR adaptive filter

**Syntax** `ha = adaptfilt.pbfdaf(1,step,leakage,delta,lambda,blocklen,offset,coeffs,states)`

**Description** `ha = adaptfilt.pbfdaf(1,step,leakage,delta,lambda,blocklen,offset,coeffs,states)` constructs a partitioned block frequency-domain FIR adaptive filter `ha` that uses bin step size normalization during adaptation.

## Input Arguments

Entries in the following table describe the input arguments for `adaptfilt.pbfdaf`.

Input Argument	Description
<code>1</code>	Adaptive filter length (the number of coefficients or taps) and it must be a positive integer. <code>L</code> defaults to 10.
<code>step</code>	Step size of the adaptive filter. This is a scalar and should lie in the range (0,1]. <code>step</code> defaults to 1.
<code>leakage</code>	Leakage parameter of the adaptive filter. When you set this argument to a value between zero and one, a leaky version of the PBFDAF algorithm is implemented. <code>leakage</code> defaults to 1— no leakage.
<code>delta</code>	Initial common value of all of the FFT input signal powers. Its initial value should be positive. <code>delta</code> defaults to 1.
<code>lambda</code>	Averaging factor used to compute the exponentially windowed FFT input signal powers for the coefficient updates. <code>lambda</code> should lie in the range (0,1]. <code>lambda</code> defaults to 0.9.

Input Argument	Description
blocklen	Block length for the coefficient updates. This must be a positive integer such that $(1/\text{blocklen})$ is also an integer. For faster execution, <code>blocklen</code> should be a power of two. <code>blocklen</code> defaults to two.
offset	Offset for the normalization terms in the coefficient updates. This can be useful to avoid divide by zeros conditions, or dividing by very small numbers, if any of the FFT input signal powers become very small. <code>offset</code> defaults to zero.
coeffs	Initial time-domain coefficients of the adaptive filter. It should be a vector of length 1. The PBFDAF algorithm uses these coefficients to compute the initial frequency-domain filter coefficient matrix via FFTs.
states	Specifies the filter initial conditions. <code>states</code> defaults to a zero vector of length 1.

## Properties

Since your `adaptfilt.pbfdaf` filter is an object, it has properties that define its behavior in operation. Note that many of the properties are also input arguments for creating `adaptfilt.pbfdaf` objects. To show you the properties that apply, this table lists and describes each property for the filter object.

Name	Range	Description
Algorithm	None	Defines the adaptive filter algorithm the object uses during adaptation.
AvgFactor		Averaging factor used to compute the exponentially windowed FFT input signal powers for the coefficient updates. AvgFactor should lie in the range (0,1]. AvgFactor defaults to 0.9. Called lambda as an input argument.
BlockLength		Block length for the coefficient updates. This must be a positive integer such that (1/blocklen) is also an integer. For faster execution, blocklen should be a power of two. blocklen defaults to two.
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps.
FFTCoefficients		Stores the discrete Fourier transform of the filter coefficients in coeffs.
FFTStates		States for the FFT operation.

<b>Name</b>	<b>Range</b>	<b>Description</b>
Leakage	0 to 1	Leakage parameter of the adaptive filter. When you set this argument to a value between zero and one, a leaky version of the PBFDAF algorithm is implemented. Leakage defaults to 1 — no leakage.
Offset		Offset for the normalization terms in the coefficient updates. This can be useful to avoid divide by zeros conditions, or dividing by very small numbers, if any of the FFT input signal powers become very small. offset defaults to zero.
PersistentMemory	false or true	Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter. PersistentMemory returns to zero any state that the filter changes during processing. States that the filter does not change are not affected. Defaults to false.

Name	Range	Description
Power		A vector of 2*1 elements, each initialized with the value delta from the input arguments. As you filter data, Power gets updated by the filter process.
StepSize	0 to 1	Step size of the adaptive filter. This is a scalar and should lie in the range (0,1]. step defaults to 1.

## Examples

An example of Quadrature Phase Shift Keying (QPSK) adaptive equalization using a 32-coefficient FIR filter.

```

D = 16; % Number of samples of delay
b = exp(1j*pi/4)*[-0.7 1]; % Numerator coefficients of channel
a = [1 -0.7]; % Denominator coefficients of channel
ntr = 1000; % Number of iterations
s = sign(randn(1,ntr+D))+1j*sign(randn(1,ntr+D)); % Baseband QPSK signal
n = 0.1*(randn(1,ntr+D) + 1j*randn(1,ntr+D)); % Noise signal
r = filter(b,a,s)+n; % Received signal
x = r(1+D:ntr+D); % Input signal (received signal)
d = s(1:ntr); % Desired signal (delayed QPSK signal)
del = 1; % Initial FFT input powers
mu = 0.1; % Step size
lam = 0.9; % Averaging factor
N = 8; % Block size
ha = adaptfilt.pbfdaf(32,mu,1,del,lam,N);
[y,e] = filter(ha,x,d);
subplot(2,2,1); plot(1:ntr,real([d;y;e])); title('In-Phase Components');
legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,2,2); plot(1:ntr,imag([d;y;e]));
title('Quadrature Components');
legend('Desired','Output','Error');


```

```

xlabel('Time Index'); ylabel('Signal Value');
subplot(2,2,3); plot(x(ntr-100:ntr),'.'); axis([-3 3 -3 3]);
title('Received Signal Scatter Plot');
axis('square'); xlabel('Real[x]'); ylabel('Imag[x]'); grid on;
subplot(2,2,4); plot(y(ntr-100:ntr),'.'); axis([-3 3 -3 3]);
title('Equalized Signal Scatter Plot');
axis('square'); xlabel('Real[y]'); ylabel('Imag[y]'); grid on;subplot(2,2,4); plot(y(ntr-100:ntr),'.');
title('Equalized Signal Scatter Plot');
axis('square'); xlabel('Real[y]'); ylabel('Imag[y]'); grid on;

```

In the figure shown, the four subplots provide the details of the results of the QPSK process used in the equalization for this example.



## References

So, J.S. and K.K. Pang, “Multidelay Block Frequency Domain Adaptive Filter,” IEEE Trans. Acoustics, Speech, and Signal Processing, vol. 38, no. 2, pp. 373-376, February 1990

Paez Borrillo, J.M. and M.G. Otero, “On The Implementation of a Partitioned Block Frequency Domain Adaptive Filter (PBFDAF) For Long Acoustic Echo Cancellation,” Signal Processing, vol. 27, no. 3, pp. 301-315, June 1992

# adaptfilt.pbfdaf

---

## See Also

`adaptfilt.fdaf` | `adaptfilt.pbufdaf` | `adaptfilt.blmsfft`

**Purpose** Partitioned block unconstrained frequency-domain adaptive filter

**Syntax** `ha = adaptfilt.pbufdaf(1,step,leakage,delta,lambda,blocklen,...offset,coeffs,states)`

**Description** `ha = adaptfilt.pbufdaf(1,step,leakage,delta,lambda,blocklen,...offset,coeffs,states)` constructs a partitioned block unconstrained frequency-domain FIR adaptive filter `ha` with bin step size normalization.

### Input Arguments

Entries in the following table describe the input arguments for `adaptfilt.pbufdaf`.

Input Argument	Description
<code>1</code>	Adaptive filter length (the number of coefficients or taps) and it must be a positive integer. <code>L</code> defaults to 10.
<code>step</code>	Step size of the adaptive filter. This is a scalar and should lie in the range (0,1]. <code>step</code> defaults to 1.
<code>leakage</code>	Leakage parameter of the adaptive filter. When you set this argument to a value between zero and one, a leaky version of the PBFDAF algorithm is implemented. <code>leakage</code> defaults to 1 — no leakage.
<code>delta</code>	Initial common value of all of the FFT input signal powers. Its initial value should be positive. <code>delta</code> defaults to 1.
<code>lambda</code>	Averaging factor used to compute the exponentially windowed FFT input signal powers for the coefficient updates. <code>lambda</code> should lie in the range (0,1]. <code>lambda</code> defaults to 0.9.

<b>Input Argument</b>	<b>Description</b>
<code>blocklen</code>	Block length for the coefficient updates. This must be a positive integer such that $(1/\text{blocklen})$ is also an integer. For faster execution, <code>blocklen</code> should be a power of two. <code>blocklen</code> defaults to two.
<code>offset</code>	Offset for the normalization terms in the coefficient updates. This can be useful to avoid divide by zeros conditions, or dividing by very small numbers, if any of the FFT input signal powers become very small. <code>offset</code> defaults to zero.
<code>coeffs</code>	Initial time-domain coefficients of the adaptive filter. It should be a vector of length 1. The PBFDAF algorithm uses these coefficients to compute the initial frequency-domain filter coefficient matrix via FFTs.
<code>states</code>	Specifies the filter initial conditions. <code>states</code> defaults to a zero vector of length 1.

## Properties

Since your `adaptfilt.pbufdaf` filter is an object, it has properties that define its behavior in operation. Note that many of the properties are also input arguments for creating `adaptfilt.pbufdaf` objects. To show you the properties that apply, this table lists and describes each property for the filter object.

<b>Name</b>	<b>Range</b>	<b>Description</b>
Algorithm	None	Defines the adaptive filter algorithm the object uses during adaptation
AvgFactor		Averaging factor used to compute the exponentially windowed FFT input signal powers for the coefficient updates. AvgFactor should lie in the range (0,1]. AvgFactor defaults to 0.9. Called lambda as an input argument.
BlockLength		Block length for the coefficient updates. This must be a positive integer such that (1/blocklen) is also an integer. For faster execution, blocklen should be a power of two. blocklen defaults to two.
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps
FFTCoefficients		Stores the discrete Fourier transform of the filter coefficients in coeffs.
FFTStates		States for the FFT operation.

## adaptfilt.pbufdaf

---

Name	Range	Description
Leakage	0 to 1	Leakage parameter of the adaptive filter. When you set this argument to a value between zero and one, a leaky version of the PBFDAF algorithm is implemented. <code>Leakage</code> defaults to 1 — no leakage.
Offset		Offset for the normalization terms in the coefficient updates. This can be useful to avoid divide by zeros conditions, or dividing by very small numbers, if any of the FFT input signal powers become very small. <code>voffset</code> defaults to zero.
PersistentMemory	false or true	Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter. <code>PersistentMemory</code> returns to zero any state that the filter changes during processing. States that the filter does not change are not affected. Defaults to false.

Name	Range	Description
Power	2*1 element vector	A vector of 2*1 elements, each initialized with the value <code>delta</code> from the input arguments. As you filter data, <code>Power</code> gets updated by the filter process.
StepSize	0 to 1	Step size of the adaptive filter. This is a scalar and should lie in the range (0,1]. <code>step</code> defaults to 1.


## Examples

Demonstrating Quadrature Phase Shift Keying (QPSK) adaptive equalization using a 32-coefficient FIR filter. To perform the equalization, this example runs for 1000 iterations.

```
D = 16;          % Number of samples of delay
b = exp(1j*pi/4)*[-0.7 1]; % Numerator coefficients of channel
a = [1 -0.7];    % Denominator coefficients of channel
ntr= 1000;       % Number of iterations
s = sign(randn(1,ntr+D))+1j*sign(randn(1,ntr+D)); % Baseband QPSK signal
n = 0.1*(randn(1,ntr+D) + 1j*randn(1,ntr+D)); % Noise signal
r = filter(b,a,s)+n; % Received signal
x = r(1+D:ntr+D); % Input signal (received signal)
d = s(1:ntr); % Desired signal (delayed QPSK signal)
del = 1; % Initial FFT input powers
mu = 0.1; % Step size
lam = 0.9; % Averaging factor
N = 8; % Block size
ha = adaptfilt.pbufdaf(32,mu,1,del,lam,N);
[y,e] = filter(ha,x,d);
subplot(2,2,1); plot(1:ntr,real([d;y;e]));
title('In-Phase Components'); legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,2,2); plot(1:ntr,imag([d;y;e]));
title('Quadrature Components');
```

```
legend('Desired','Output','Error');  
xlabel('Time Index'); ylabel('Signal Value');  
subplot(2,2,3); plot(x(ntr-100:ntr),'.'); axis([-3 3 -3 3]);  
title('Received Signal Scatter Plot'); axis('square');  
xlabel('Real[x]'); ylabel('Imag[x]'); grid on;  
subplot(2,2,4); plot(y(ntr-100:ntr),'.'); axis([-3 3 -3 3]);  
title('Equalized Signal Scatter Plot'); axis('square');  
xlabel('Real[y]'); ylabel('Imag[y]'); grid on;
```

You can compare this algorithm to another, such as the `pbfdaf` version. Use the same example of QPSK adaptation. The following figure shows the results.



## References

So, J.S. and K.K. Pang, "Multidelay Block Frequency Domain Adaptive Filter," *IEEE Trans. Acoustics, Speech, and Signal Processing*, vol. 38, no. 2, pp. 373-376, February 1990

Paez Borrillo, J.M. and M.G. Otero, "On The Implementation of a Partitioned Block Frequency Domain Adaptive Filter (PBFDAF) for Long Acoustic Echo Cancellation," *Signal Processing*, vol. 27, no. 3, pp. 301-315, June 1992

**See Also**

[adaptfilt.ufdaf](#) | [adaptfilt.pbfdaf](#) | [adaptfilt.blmsfft](#)

# adaptfilt.qrdls1

---

**Purpose** QR-decomposition-based least-squares lattice adaptive filter

**Syntax** `ha = adaptfilt.qrdls1(1,lambda,delta,coeffs,states)`

**Description** `ha = adaptfilt.qrdls1(1,lambda,delta,coeffs,states)` returns a QR-decomposition-based least squares lattice adaptive filter `ha`.

## Input Arguments

Entries in the following table describe the input arguments for `adaptfilt.qrdls1`.

Input Argument	Description
<code>l</code>	Length of the joint process filter coefficients. It must be a positive integer and must be equal to the length of the prediction coefficients plus one. <code>l</code> defaults to 10.
<code>lambda</code>	Forgetting factor of the adaptive filter. This is a scalar and should lie in the range (0, 1]. <code>lambda</code> defaults to 1. <code>lambda = 1</code> denotes infinite memory while adapting to find the new filter.
<code>delta</code>	Soft-constrained initialization factor in the least squares lattice algorithm. It should be positive. <code>delta</code> defaults to 1.
<code>coeffs</code>	Vector of initial joint process filter coefficients. It must be a length <code>l</code> vector. <code>coeffs</code> defaults to a length <code>l</code> vector of all zeros.
<code>states</code>	Vector of the angle normalized backward prediction error states of the adaptive filter

## Properties

Since your `adaptfilt.qrdls1` filter is an object, it has properties that define its behavior in operation. Note that many of the properties are also input arguments for creating `adaptfilt.qrdls1` objects. To

show you the properties that apply, this table lists and describes each property for the filter object.

Name	Range	Description
Algorithm	None	Defines the adaptive filter algorithm the object uses during adaptation
BkwdPrediction		Returns the predicted samples generated during adaptation. Refer to [2] in the bibliography for details about linear prediction.
Coefficients	Vector of elements	Vector containing the initial filter coefficients. It must be a length 1 vector where 1 is the number of filter coefficients. coeffs defaults to length 1 vector of zeros when you do not provide the argument for input.
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps
ForgettingFactor		Forgetting factor of the adaptive filter. This is a scalar and should lie in the range (0, 1]. It defaults to 1. Setting forgetting factor = 1 denotes infinite memory while adapting to find the new filter. Note that this is the lambda input argument.

Name	Range	Description
FwdPrediction		Returns the predicted samples generated during adaptation in the forward direction. Refer to [2] in the bibliography for details about linear prediction.
InitFactor		Soft-constrained initialization factor. This scalar should be positive and sufficiently large to prevent an excessive number of Kalman gain rescues. <code>delta</code> defaults to one.
PersistentMemory	false or true	Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter if you have not changed the filter since you constructed it. <code>PersistentMemory</code> returns to zero any state that the filter changes during processing. States that the filter does not change are not affected. Defaults to <code>false</code> .
States	Vector of elements, data type double	Vector of the adaptive filter states. <code>states</code> defaults to a vector of zeros which has length equal to <code>1 - 1</code>

## Examples


Implement Quadrature Phase Shift Keying (QPSK) adaptive equalization using a 32-coefficient adaptive filter. To see the results of

the equalization process in this example, look at the figure that follows the example code.

```

D = 16; % Number of samples of delay
b = exp(1j*pi/4)*[-0.7 1]; % Numerator coefficients of channel
a = [1 -0.7]; % Denominator coefficients of channel
ntr= 1000; % Number of iterations
s = sign(randn(1,ntr+D))+1j*sign(randn(1,ntr+D)); % Baseband QPSK signal
n = 0.1*(randn(1,ntr+D) + 1j*randn(1,ntr+D)); % Noise signal
r = filter(b,a,s)+n; % Received signal
x = r(1+D:ntr+D); % Input signal (received signal)
d = s(1:ntr); % Desired signal (delayed QPSK signal)
lam = 0.995; % Forgetting factor
del = 1; % Soft-constrained initialization factor
ha = adaptfilt.qrdsls(32,lam,del);
[y,e] = filter(ha,x,d);
subplot(2,2,1); plot(1:ntr,real([d;y;e]));
title('In-Phase Components'); legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,2,2); plot(1:ntr,imag([d;y;e]));
title('Quadrature Components'); legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,2,3); plot(x(ntr-100:ntr),'.'); axis([-3 3 -3 3]);
title('Received Signal Scatter Plot'); axis('square');
xlabel('Real[x]'); ylabel('Imag[x]'); grid on;
subplot(2,2,4); plot(y(ntr-100:ntr),'.'); axis([-3 3 -3 3]);
title('Equalized Signal Scatter Plot'); axis('square');
xlabel('Real[y]'); ylabel('Imag[y]'); grid on;

```



## References

Haykin, S., *Adaptive Filter Theory*, 2nd Edition, Prentice Hall, N.J., 1991

## See Also

`adaptfilt.qrdls` | `adaptfilt.gal` | `adaptfilt.ftf` | `adaptfilt.lsl`

**Purpose** FIR adaptive filter that uses QR-decomposition-based RLS

**Syntax** `ha = adaptfilt.qdrpls(1,lambda,sqrtcov,coeffs,states)`

**Description** `ha = adaptfilt.qdrpls(1,lambda,sqrtcov,coeffs,states)` constructs an FIR QR-decomposition-based recursive-least squares (RLS) adaptive filter object `ha`.

### Input Arguments

Entries in the following table describe the input arguments for `adaptfilt.qdrpls`.

Input Argument	Description
<code>l</code>	Adaptive filter length (the number of coefficients or taps) and it must be a positive integer. <code>l</code> defaults to 10.
<code>lambda</code>	RLS forgetting factor. This is a scalar and should lie within the range (0, 1]. <code>lambda</code> defaults to 1.
<code>sqrtcov</code>	Upper-triangular Cholesky (square root) factor of the input covariance matrix. Initialize this matrix with a positive definite upper triangular matrix.
<code>coeffs</code>	Vector of initial filter coefficients. It must be a length <code>l</code> vector. <code>coeffs</code> defaults to length <code>l</code> vector whose elements are zeros.
<code>states</code>	Vector of initial filter states. It must be a length <code>l-1</code> vector. <code>states</code> defaults to a length <code>l-1</code> vector of zeros.

### Properties

Since your `adaptfilt.qdrpls` filter is an object, it has properties that define its behavior in operation. Note that many of the properties are also input arguments for creating `adaptfilt.qdrpls` objects. To show you the properties that apply, this table lists and describes each property for the filter object.

## adaptfilt.qdrfs

---

Name	Range	Description
Algorithm	None	Defines the adaptive filter algorithm the object uses during adaptation
Coefficients	Vector of length 1	Vector containing the initial filter coefficients. It must be a length 1 vector where 1 is the number of filter coefficients. <code>coeffs</code> defaults to length 1 vector of zeros when you do not provide the argument for input.
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps
ForgettingFactor	Scalar	Forgetting factor of the adaptive filter. This is a scalar and should lie in the range (0, 1]. It defaults to 1. Setting <code>forgetting factor = 1</code> denotes infinite memory while adapting to find the new filter. Note that this is the <code>lambda</code> input argument.

Name	Range	Description
PersistentMemory	false or true	Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter if you have not changed the filter since you constructed it. PersistentMemory returns to zero any state that the filter changes during processing. States that the filter does not change are not affected. Defaults to false.
SqrtCov	Square matrix with each dimension equal to the filter length 1	Upper-triangular Cholesky (square root) factor of the input covariance matrix. Initialize this matrix with a positive definite upper triangular matrix.
States	Vector of elements	Vector of the adaptive filter states. states defaults to a vector of zeros which has length equal to (1 + projectord - 2).

## Examples

System Identification of a 32-coefficient FIR filter (500 iterations).

```


x = randn(1,500);      % Input to the filter
b = fir1(31,0.5);     % FIR system to be identified
n = 0.1*randn(1,500); % Observation noise signal
d = filter(b,1,x)+n;  % Desired signal
G0 = sqrt(.1)*eye(32); % Initial sqrt correlation matrix

```

# adaptfilt.qrdrls

```
lam = 0.99; % RLS forgetting factor
ha = adaptfilt.qrdrls(32, lam, G0);
[y, e] = filter(ha, x, d);
subplot(2,1,1); plot(1:500, [d; y; e]);
title('System Identification of an FIR Filter');
legend('Desired', 'Output', 'Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,1,2); stem([b.', ha.Coefficients.']);
legend('Actual', 'Estimated'); grid on;
xlabel('Coefficient #'); ylabel('Coefficient Value');
```

Using this variant of the RLS algorithm successfully identifies the unknown FIR filter, as shown here.



## See Also

[adaptfilt.rls](#) | [adaptfilt.hrls](#) | [adaptfilt.hswrls](#) | [adaptfilt.swrls](#)

**Purpose** Recursive least-squares FIR adaptive filter

**Syntax** `ha = adaptfilt.rls(l,lambda,invcov,coeffs,states)`

**Description** `ha = adaptfilt.rls(l,lambda,invcov,coeffs,states)` constructs an FIR direct form RLS adaptive filter `ha`.

**Input Arguments**

Entries in the following table describe the input arguments for `adaptfilt.rls`.

Input Argument	Description
<code>l</code>	Adaptive filter length (the number of coefficients or taps) and it must be a positive integer. <code>l</code> defaults to 10.
<code>lambda</code>	RLS forgetting factor. This is a scalar and should lie in the range (0, 1]. <code>lambda</code> defaults to 1.
<code>invcov</code>	Inverse of the input signal covariance matrix. For best performance, you should initialize this matrix to be a positive definite matrix.
<code>coeffs</code>	Vector of initial filter coefficients. it must be a length <code>l</code> vector. <code>coeffs</code> defaults to length <code>l</code> vector with elements equal to zero.
<code>states</code>	Vector of initial filter states for the adaptive filter. It must be a length <code>l-1</code> vector. <code>states</code> defaults to a length <code>l-1</code> vector of zeros.

**Properties**

Since your `adaptfilt.rls` filter is an object, it has properties that define its behavior in operation. Note that many of the properties are also input arguments for creating `adaptfilt.rls` objects. To show you the properties that apply, this table lists and describes each property for the filter object.

Name	Range	Description
Algorithm	None	Defines the adaptive filter algorithm the object uses during adaptation.
Coefficients	Vector containing 1 elements	Vector containing the initial filter coefficients. It must be a length 1 vector where 1 is the number of filter coefficients. <code>coeffs</code> defaults to length 1 vector of zeros when you do not provide the argument for input.
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps. Remember that filter length is filter order + 1.
ForgettingFactor	Scalar	Forgetting factor of the adaptive filter. This is a scalar and should lie in the range (0, 1]. It defaults to 1. Setting <code>forgetting factor = 1</code> denotes infinite memory while adapting to find the new filter. Note that this is the <code>lambda</code> input argument.
InvCov	Matrix of size 1-by-1	Upper-triangular Cholesky (square root) factor of the input covariance matrix. Initialize this matrix with a positive definite upper triangular matrix.
KalmanGain	Vector of size (1,1)	Empty when you construct the object, this gets populated after you run the filter.


Name	Range	Description
PersistentMemory	false or true	Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter if you have not changed the filter since you constructed it. PersistentMemory returns to zero any state that the filter changes during processing. Defaults to false.
States	Double array	Vector of the adaptive filter states. states defaults to a vector of zeros which has length equal to $(1 + \text{projectord} - 2)$ .

## Examples

System Identification of a 32-coefficient FIR filter over 500 adaptation iterations.

```
x = randn(1,500); % Input to the filter
b = fir1(31,0.5); % FIR system to be identified
n = 0.1*randn(1,500); % Observation noise signal
d = filter(b,1,x)+n; % Desired signal
P0 = 10*eye(32); % Initial sqrt correlation matrix inverse
lam = 0.99; % RLS forgetting factor
ha = adaptfilt.rls(32,lam,P0);
[y,e] = filter(ha,x,d);
subplot(2,1,1); plot(1:500,[d;y;e]);
title('System Identification of an FIR Filter');
legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,1,2); stem([b.',ha.Coefficients.']);
legend('Actual','Estimated');
xlabel('Coefficient #'); ylabel('Coefficient value'); grid on;
```

In this example of adaptive filtering using the RLS algorithm to update the filter coefficients for each iteration, the figure shown reveals the fidelity of the derived filter after adaptation.



## See Also

[adaptfilt.hrls](#) | [adaptfilt.hswrls](#) | [adaptfilt.qdr1s](#)

**Purpose** Sign-data FIR adaptive filter

**Syntax** `ha = adaptfilt.sd(l,step,leakage,coeffs,states)`

**Description** `ha = adaptfilt.sd(l,step,leakage,coeffs,states)` constructs an FIR sign-data adaptive filter object `ha`.

**Input Arguments**

Entries in the following table describe the input arguments for `adaptfilt.sd`.

Input Argument	Description
<code>l</code>	Adaptive filter length (the number of coefficients or taps) and it must be a positive integer. <code>l</code> defaults to 10.
<code>step</code>	SD step size. It must be a nonnegative scalar. <code>step</code> defaults to 0.1
<code>leakage</code>	Your SD leakage factor. It must be a scalar between 0 and 1. When <code>leakage</code> is less than one, <code>adaptfilt.sd</code> implements a leaky SD algorithm. When you omit the <code>leakage</code> property in the calling syntax, it defaults to 1 providing no leakage in the adapting algorithm.
<code>coeffs</code>	Vector of initial filter coefficients. it must be a length <code>l</code> vector. <code>coeffs</code> defaults to length <code>l</code> vector with elements equal to zero.
<code>states</code>	Vector of initial filter states for the adaptive filter. It must be a length <code>l-1</code> vector. <code>states</code> defaults to a length <code>l-1</code> vector of zeros.

**Properties** In the syntax for creating the `adaptfilt` object, the input options are properties of the object you create. This table lists the properties for

sign-data objects, their default values, and a brief description of the property.

<b>Property</b>	<b>Default Value</b>	<b>Description</b>
Al gorithm	Sign-data	Defines the adaptive filter algorithm the object uses during adaptation.
Coefficients	zeros(1,1)	Vector containing the initial filter coefficients. It must be a length <code>l</code> vector where <code>l</code> is the number of filter coefficients. <code>coeffs</code> defaults to length <code>l</code> vector of zeros when you do not provide the argument for input. Should be initialized with the initial coefficients for the FIR filter prior to adapting. You need <code>l</code> entries in <code>coefficients</code> .
FilterLength	10	Reports the length of the filter, the number of coefficients or taps.
Leakage	0	Specifies the leakage parameter. Allows you to implement a leaky algorithm. Including a leakage factor can improve the results of the algorithm by forcing the algorithm to continue to adapt even after it reaches a minimum value. Ranges between 0 and 1. Defaults to 0.

Property	Default Value	Description
PersistentMemory	false or true	Determine whether the filter states and coefficients get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter. PersistentMemory returns to zero any property value that the filter changes during processing. Property values that the filter does not change are not affected. Defaults to false.
States	zeros(1-1,1)	Vector of the adaptive filter states. states defaults to a vector of zeros which has length equal to (1 - 1).
StepSize	0.1	Sets the SD algorithm step size used for each iteration of the adapting algorithm. Determines both how quickly and how closely the adaptive filter converges to the filter solution.


## Examples

Adaptive line enhancement using a 32-coefficient FIR filter to perform the enhancement. This example runs for 5000 iterations, as you see in property iter.

```
d = 1; % Number of samples of delay
ntr= 5000; % Number of iterations
v = sin(2*pi*0.05*[1:ntr+d]); % Sinusoidal signal
n = randn(1,ntr+d); % Noise signal
```

```
x = v(1:ntr)+n(1:ntr);           % Input signal
d = v(1+d:ntr+d)+n(1+d:ntr+d); % Desired signal
mu = 0.0001;                     % Sign-data step size.
ha = adaptfilt.sd(32,mu);
[y,e] = filter(ha,x,d);
subplot(2,1,1); plot(1:ntr,[d;y;v(1:end-1)]);
axis([ntr-100 ntr -3 3]);
title('Adaptive Line Enhancement of a Noisy Sinusoidal Signal');
legend('Observed','Enhanced','Original');
xlabel('Time Index'); ylabel('Signal Value');
[pxx,om] = pwelch(x(ntr-1000:ntr));
pyy = pwelch(y(ntr-1000:ntr));
subplot(2,1,2);
plot(om/pi,10*log10([pxx/max(pxx),pyy/max(pyy)]));
axis([0 1 -60 20]); legend('Observed','Enhanced');
xlabel('Normalized Frequency (\times \pi rad/sample)');
ylabel('Power Spectral Density'); grid on;
```

Each of the variants — sign-data, sign-error, and sign-sign — uses the same example. You can compare the results by viewing the figure shown for each adaptive filter method — `adaptfilt.sd`, `adaptfilt.se`, and `adaptfilt.ss`.



## References

Moschner, J.L., "Adaptive Filter with Clipped Input Data," Ph.D. thesis, Stanford Univ., Stanford, CA, June 1970.

Hayes, M., *Statistical Digital Signal Processing and Modeling*, New York Wiley, 1996.

## See Also

[adaptfilt.lms](#) | [adaptfilt.se](#) | [adaptfilt.ss](#)

**Purpose** FIR adaptive filter that uses sign-error algorithm

**Syntax** `ha = adaptfilt.se(1,step,leakage,coeffs,states)`

**Description** `ha = adaptfilt.se(1,step,leakage,coeffs,states)` constructs an FIR sign-error adaptive filter `ha`.

### Input Arguments

Entries in the following table describe the input arguments for `adaptfilt.se`.

Input Argument	Description
<code>l</code>	Adaptive filter length (the number of coefficients or taps) and it must be a positive integer. <code>l</code> defaults to 10.
<code>step</code>	SE step size. It must be a nonnegative scalar. You can use <code>maxstep</code> to determine a reasonable range of step size values for the signals being processed. <code>step</code> defaults to 0.1
<code>leakage</code>	Your SE leakage factor. It must be a scalar between 0 and 1. When <code>leakage</code> is less than one, <code>adaptfilt.se</code> implements a leaky SE algorithm. When you omit the <code>leakage</code> property in the calling syntax, it defaults to 1 providing no leakage in the adapting algorithm.
<code>coeffs</code>	Vector of initial filter coefficients. it must be a length <code>l</code> vector. <code>coeffs</code> defaults to length <code>l</code> vector with elements equal to zero.
<code>states</code>	Vector of initial filter states for the adaptive filter. It must be a length <code>l-1</code> vector. <code>states</code> defaults to a length <code>l-1</code> vector of zeros.

## Properties

In the syntax for creating the `adaptfilt` object, the input options are properties of the object you create. This table lists the properties for the sign-error SD object, their default values, and a brief description of the property.

Property	Default Value	Description
Algorithm	Sign-error	Defines the adaptive filter algorithm the object uses during adaptation
Coefficients	<code>zeros(1,1)</code>	Vector containing the initial filter coefficients. It must be a length 1 vector where 1 is the number of filter coefficients. <code>coeffs</code> defaults to length 1 vector of zeros when you do not provide the argument for input. Should be initialized with the initial coefficients for the FIR filter prior to adapting.
FilterLength	10	Reports the length of the filter, the number of coefficients or taps
Leakage	1	Specifies the leakage parameter. Allows you to implement a leaky algorithm. Including a leakage factor can improve the results of the algorithm by forcing the algorithm to continue to adapt even after it reaches a minimum value. Ranges between 0 and 1. Defaults to one if omitted.

Property	Default Value	Description
PersistentMemory	false or true	Determine whether the filter states and coefficients get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter. PersistentMemory returns to zero any property value that the filter changes during processing. Property values that the filter does not change are not affected. Defaults to false.
States	zeros(1-1,1)	Vector of the adaptive filter states. states defaults to a vector of zeros which has length equal to (1 -1).
StepSize	0.1	Sets the SE algorithm step size used for each iteration of the adapting algorithm. Determines both how quickly and how closely the adaptive filter converges to the filter solution.

Use inspect(ha) to view or change the object properties graphically using the MATLAB Property Inspector.

## Examples

Adaptive line enhancement using a 32-coefficient FIR filter running over 5000 iterations.


```
d = 1; % Number of samples of delay
ntr= 5000; % Number of iterations
v = sin(2*pi*0.05*(1:ntr+d)); % Sinusoidal signal
n = randn(1,ntr+d); % Noise signal
```

```

x = v(1:ntr)+n(1:ntr);          % Input signal --(delayed desired signal)
d = v(1+d:ntr+d)+n(1+d:ntr+d); % Desired signal
mu = 0.0001;                    % Sign-error step size
ha = adaptfilt.se(32,mu);
[y,e] = filter(ha,x,d);
subplot(2,1,1);
plot(1:ntr,[d;y;v(1:end-1)]);
axis([ntr-100 ntr -3 3]);
title('Adaptive Line Enhancement of Noisy Sinusoid');
legend('Observed','Enhanced','Original');
xlabel('Time Index'); ylabel('Signal Value');
HWelch = spectrum.welch;
InputPsd = psd(HWelch,x(ntr-1000:ntr));
OutputPsd = psd(HWelch,y(ntr-1000:ntr));
CompPsdEst = [InputPsd.Data/max(InputPsd.Data), OutputPsd.Data/max(OutputPsd.Data)];
subplot(2,1,2); plot(InputPsd.Frequencies/pi,10*log10(CompPsdEst));
axis([0 1 -60 20]); legend('Observed','Enhanced');
xlabel('Normalized Frequency (\times \pi rad/sample)');
ylabel('Power Spectral Density'); grid on;

```

Compare the figure shown here to the ones for `adaptfilt.sd` and `adaptfilt.ss` to see how the variants perform on the same example.



## References

Gersho, A, "Adaptive Filtering With Binary Reinforcement," IEEE Trans. Information Theory, vol. IT-30, pp. 191-199, March 1984.

Hayes, M, *Statistical Digital Signal Processing and Modeling*, New York, Wiley, 1996.

## See Also

[adaptfilt.sd](#) | [adaptfilt.ss](#) | [adaptfilt.lms](#)

**Purpose** FIR adaptive filter that uses sign-sign algorithm

**Syntax** `ha = adaptfilt.ss(1,step,leakage,coeffs,states)`

**Description** `ha = adaptfilt.ss(1,step,leakage,coeffs,states)` constructs an FIR sign-error adaptive filter `ha`.

**Input Arguments**

Entries in the following table describe the input arguments for `adaptfilt.ss`.

Input Argument	Description
<code>1</code>	Adaptive filter length (the number of coefficients or taps) and it must be a positive integer. <code>1</code> defaults to 10.
<code>step</code>	SS step size. It must be a nonnegative scalar. <code>step</code> defaults to 0.1.
<code>leakage</code>	Your SS leakage factor. It must be a scalar between 0 and 1. When <code>leakage</code> is less than one, <code>adaptfilt.lms</code> implements a leaky SS algorithm. When you omit the <code>leakage</code> property in the calling syntax, it defaults to 1 providing no leakage in the adapting algorithm.
<code>coeffs</code>	Vector of initial filter coefficients. it must be a length <code>1</code> vector. <code>coeffs</code> defaults to length <code>1</code> vector with elements equal to zero.
<code>states</code>	Vector of initial filter states for the adaptive filter. It must be a length <code>1 - 1</code> vector. <code>states</code> defaults to a length <code>1-1</code> vector of zeros.

`adaptfilt.ss` can be called for a block of data, when `x` and `d` are vectors, or in “sample by sample mode” using a For-loop with the method `filter`:

```
for n = 1:length(x)
```

# adaptfilt.ss

---

```
ha = adaptfilt.ss(25,0.9);  
[y(n),e(n)] = filter(ha,(x(n),d(n),s));  
end
```

## Properties

In the syntax for creating the `adaptfilt` object, most of the input options are properties of the object you create. This table lists the properties for sign-sign objects, their default values, and a brief description of the property.

Property	Default Value	Description
Algorithm	Sign-sign	Defines the adaptive filter algorithm the object uses during adaptation
Coefficients	<code>zeros(1,1)</code>	Vector containing the initial filter coefficients. It must be a length 1 vector where 1 is the number of filter coefficients. <code>coeffs</code> defaults to length 1 vector of zeros when you do not provide the argument for input. Should be initialized with the initial coefficients for the FIR filter prior to adapting.
FilterLength	10	Reports the length of the filter, the number of coefficients or taps


Property	Default Value	Description
Leakage	1	Specifies the leakage parameter. Allows you to implement a leaky algorithm. Including a leakage factor can improve the results of the algorithm by forcing the algorithm to continue to adapt even after it reaches a minimum value. Ranges between 0 and 1. 1 is the default value.
PersistentMemory	false or true	Determine whether the filter states and coefficients get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter. PersistentMemory returns to zero any property value that the filter changes during processing. Property values that the filter does not change are not affected. Defaults to false.
States	zeros(1-1,1)	Vector of the adaptive filter states. states defaults to a vector of zeros which has length equal to (1-1).
StepSize	0.1	Sets the SE algorithm step size used for each iteration of the adapting algorithm. Determines both how quickly and how closely the adaptive filter converges to the filter solution.

## Examples

Demonstrating adaptive line enhancement using a 32-coefficient FIR filter provides a good introduction to the sign-sign algorithm.

```
d = 1; % Number of samples of delay
ntr= 5000; % Number of iterations
v = sin(2*pi*0.05*(1:ntr+d)); % Sinusoidal signal
n = randn(1,ntr+d); % Noise signal
x = v(1:ntr)+n(1:ntr); % Input signal --(delayed desired signal)
d = v(1+d:ntr+d)+n(1+d:ntr+d); % Desired signal
mu = 0.0001; % Sign-error step size
ha = adaptfilt.ss(32,mu);
[y,e] = filter(ha,x,d);
subplot(2,1,1);
plot(1:ntr,[d;y;v(1:end-1)]);
axis([ntr-100 ntr -3 3]);
title('Adaptive Line Enhancement of Noisy Sinusoid');
legend('Observed','Enhanced','Original');
xlabel('Time Index'); ylabel('Signal Value');
HWelch = spectrum.welch;
InputPsd = psd(HWelch,x(ntr-1000:ntr));
OutputPsd = psd(HWelch,y(ntr-1000:ntr));
CompPsdEst = [InputPsd.Data/max(InputPsd.Data), OutputPsd.Data/max(OutputPsd.Data)];
subplot(2,1,2); plot(InputPsd.Frequencies/pi,10*log10(CompPsdEst));
axis([0 1 -60 20]); legend('Observed','Enhanced');
xlabel('Normalized Frequency (\times \pi rad/sample)');
ylabel('Power Spectral Density'); grid on;
```

This example is the same as the ones used for the sign-data and sign-error examples. Comparing the figures shown for each of the others lets you assess the performance of each for the same task.



## References

Lucky, R.W, "Techniques For Adaptive Equalization of Digital Communication Systems," Bell Systems Technical Journal, vol. 45, pp. 255-286, Feb. 1966

Hayes, M., *Statistical Digital Signal Processing and Modeling*, New York, Wiley, 1996.

## See Also

[adaptfilt.se](#) | [adaptfilt.sd](#) | [adaptfilt.lms](#)

# adaptfilt.swftf

---

**Purpose** FIR adaptive filter that uses sliding window fast transversal least squares

**Syntax** `ha = adaptfilt.swftf(1,delta,blocklen,gamma,gstates, dstates,...coeffs,states)`

**Description** `ha = adaptfilt.swftf(1,delta,blocklen,gamma,gstates, dstates,...coeffs,states)` constructs a sliding window fast transversal least squares adaptive filter `ha`.

## Input Arguments

Entries in the following table describe the input arguments for `adaptfilt.swftf`.

Input Argument	Description
<code>1</code>	Adaptive filter length (the number of coefficients or taps) and it must be a positive integer. <code>1</code> defaults to 10.
<code>delta</code>	Soft-constrained initialization factor. This scalar should be positive and sufficiently large to maintain stability. <code>delta</code> defaults to 1.
<code>blocklen</code>	Block length of the sliding window. This must be an integer at least as large as the filter length <code>1</code> , which is the default value.
<code>gamma</code>	Conversion factor. <code>gamma</code> defaults to the matrix $[1 \ -1]$ that specifies soft-constrained initialization.
<code>gstates</code>	States of the Kalman gain updates. <code>gstates</code> defaults to a zero vector of length $(1 + \text{blocklen} - 1)$ .
<code>dstates</code>	Desired signal states of the adaptive filter. <code>dstates</code> defaults to a zero vector of length equal to $(\text{blocklen} - 1)$ . For a default object, <code>dstates</code> is $(1-1)$ .

Input Argument	Description
coeffs	Vector of initial filter coefficients. It must be a length 1 vector. coeffs defaults to length 1 vector of all zeros.
states	Vector of initial filter states. states defaults to a zero vector of length equal to $(l + \text{blocklen} - 2)$ .

## Properties

Since your `adaptfilt.swftf` filter is an object, it has properties that define its behavior in operation. Note that many of the properties are also input arguments for creating `adaptfilt.swftf` objects. To show you the properties that apply, this table lists and describes each property for the filter object.

Name	Range	Description
Algorithm	None	Defines the adaptive filter algorithm the object uses during adaptation
BkwdPredictions		Returns the predicted samples generated during adaptation. Refer to [2] in the bibliography for details about linear prediction.
BlockLength		Block length of the sliding window. This must be an integer at least as large as the filter length 1, which is the default value.
Coefficients	Vector of elements	Vector containing the initial filter coefficients. It must be a length 1 vector where 1 is the number of filter coefficients. coeffs defaults to length 1 vector of zeros when you do not provide the argument for input.

Name	Range	Description
ConversionFactor		Conversion factor. Called <code>gamma</code> when it is an input argument, it defaults to the matrix <code>[1 -1]</code> that specifies soft-constrained initialization.
DesiredSignalStates		Desired signal states of the adaptive filter. <code>dstates</code> defaults to a zero vector with length equal to <code>(blocklen - 1)</code> .
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps
FwdPrediction		Contains the predicted values for samples during adaptation. Compare these to the actual samples to get the error and power.
InitFactor		Soft-constrained initialization factor. This scalar should be positive and sufficiently large to prevent an excessive number of Kalman gain rescues. <code>delta</code> defaults to one.
KalmanGain		Empty when you construct the object, this gets populated after you run the filter.
KalmanGainStates		Contains the states of the Kalman gains for the adaptive algorithm. Initialized to a vector of double data type entries.

Name	Range	Description
PersistentMemory	false or true	Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter if you have not changed the filter since you constructed it. PersistentMemory returns to zero any state that the filter changes during processing. States that the filter does not change are not affected. Defaults to false.
States	Vector of elements, data type double	Vector of the adaptive filter states. states defaults to a vector of zeros which has length equal to $(1 + \text{projectord} - 2)$ .


## Examples

Over 500 iterations, perform a system identification of a 32-coefficient FIR filter.

```
x = randn(1,500); % Input to the filter
b = fir1(31,0.5); % FIR system to be identified
n = 0.1*randn(1,500); % Observation noise signal
d = filter(b,1,x)+n; % Desired signal
L = 32; % Adaptive filter length
del = 0.1; % Soft-constrained initialization factor
N = 64; % block length
ha = adaptfilt.swftf(L,del,N);
[y,e] = filter(ha,x,d);
subplot(2,1,1); plot(1:500,[d;y;e]);
title('System Identification of an FIR Filter');
legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
```

```
subplot(2,1,2); stem([b.',ha.Coefficients.']);  
legend('Actual','Estimated');  
xlabel('Coefficient #'); ylabel('Coefficient Value'); grid on;
```

Review the figure for the results of the example. When you evaluate the example you should get the same results, within the differences in the random noise signal you use.



## References

Slock, D.T.M., and T. Kailath, "A Modular Prewindowing Framework for Covariance FTF RLS Algorithms," *Signal Processing*, vol. 28, pp. 47-61, 1992

Slock, D.T.M., and T. Kailath, "A Modular Multichannel Multi-Experiment Fast Transversal Filter RLS Algorithm," *Signal Processing*, vol. 28, pp. 25-45, 1992

## See Also

[adaptfilt.ftf](#) | [adaptfilt.swrls](#) | [adaptfilt.ap](#) | [adaptfilt.apru](#)

**Purpose** FIR adaptive filter that uses window recursive least squares (RLS)

**Syntax** `ha = adaptfilt.swrls(1,lambda,invcov,swblocklen,  
dstates,...coeffs,states)`

**Description** `ha = adaptfilt.swrls(1,lambda,invcov,swblocklen,  
dstates,...coeffs,states)` constructs an FIR sliding window RLS  
adaptive filter `ha`.

### Input Arguments

Entries in the following table describe the input arguments for `adaptfilt.swrls`.

Input Argument	Description
<code>1</code>	Adaptive filter length (the number of coefficients or taps). It must be a positive integer. <code>1</code> defaults to 10.
<code>lambda</code>	RLS forgetting factor. This is a scalar and should lie within the range (0, 1]. <code>lambda</code> defaults to 1.
<code>invcov</code>	Inverse of the input signal covariance matrix. You should initialize <code>invcov</code> to a positive definite matrix.
<code>swblocklen</code>	Block length of the sliding window. This integer must be at least as large as the filter length. <code>swblocklen</code> defaults to 16.
<code>dstates</code>	Desired signal states of the adaptive filter. <code>dstates</code> defaults to a zero vector with length equal to $(swblocklen - 1)$ .
<code>coeffs</code>	Vector of initial filter coefficients. It must be a length <code>1</code> vector. <code>coeffs</code> defaults to length <code>1</code> vector of all zeros.
<code>states</code>	Vector of initial filter states. <code>states</code> defaults to a zero vector of length equal to $(1 + swblocklen - 2)$ .

## Properties

Since your `adaptfilt.swrls` filter is an object, it has properties that define its behavior in operation. Note that many of the properties are also input arguments for creating `adaptfilt.swrls` objects. To show you the properties that apply, this table lists and describes each property for the filter object.

Name	Range	Description
Algorithm	None	Defines the adaptive filter algorithm the object uses during adaptation
Coefficients	Any vector of 1 elements	Vector containing the initial filter coefficients. It must be a length 1 vector where 1 is the number of filter coefficients. <code>coeffs</code> defaults to length 1 vector of zeros when you do not provide the argument for input.
DesiredSignalStates	Vector	Desired signal states of the adaptive filter. <code>dstates</code> defaults to a zero vector with length equal to $(\text{swblocklen} - 1)$ .
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps

<b>Name</b>	<b>Range</b>	<b>Description</b>
ForgettingFactor	Scalar	Forgetting factor of the adaptive filter. This is a scalar and should lie in the range (0, 1]. It defaults to 1. Setting forgetting factor = 1 denotes infinite memory while adapting to find the new filter. Note that this is the lambda input argument.
InvCov	Matrix	Square matrix with each dimension equal to the filter length $l$ .
KalmanGain	Vector with dimensions (1,1)	Empty when you construct the object, this gets populated after you run the filter.
PersistentMemory	false or true	Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter if you have not changed the filter since you constructed it. PersistentMemory returns to zero any state that the filter changes during processing. Defaults to false.

Name	Range	Description
States	Vector of elements, data type double	Vector of the adaptive filter states. <code>states</code> defaults to a vector of zeros which has length equal to $(1 + \text{swblocklen} - 2)$
SwBlockLength	Integer	Block length of the sliding window. This integer must be at least as large as the filter length. <code>swblocklen</code> defaults to 16.


## Examples

System Identification of a 32-coefficient FIR filter. Use 500 iterations to adapt to the unknown filter. After the example code, you see a figure that plots the results of the running the code.

```
x = randn(1,500); % Input to the filter
b = fir1(31,0.5); % FIR system to be identified
n = 0.1*randn(1,500); % Observation noise signal
d = filter(b,1,x)+n; % Desired signal
P0 = 10*eye(32); % Initial correlation matrix inverse
lam = 0.99; % RLS forgetting factor
N = 64; % Block length
ha = adaptfilt.swrls(32,lam,P0,N);
[y,e] = filter(ha,x,d);
subplot(2,1,1); plot(1:500,[d;y;e]);
title('System Identification of an FIR Filter');
legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,1,2); stem([b.',ha.Coefficients.']);
legend('Actual','Estimated');
xlabel('Coefficient #'); ylabel('Coefficient Value'); grid on;
```

In the figure you see clearly that the adaptive filter process successfully identified the coefficients of the unknown FIR filter. You knew it

had to or many things that you take for granted, such as modems on computers, would not work.



**See Also**

[adaptfilt.rl](#) | [adaptfilt.qdr](#) | [adaptfilt.hswrl](#)

# adaptfilt.tdafdct

---

**Purpose** Adaptive filter that uses discrete cosine transform

**Syntax** `ha = adaptfilt.tdafdct(1, step, leakage, offset, delta, lambda, coeffs, states)`

**Description** `ha = adaptfilt.tdafdct(1, step, leakage, offset, delta, lambda, coeffs, states)` constructs a transform-domain adaptive filter `ha` object that uses the discrete cosine transform to perform filter adaptation.

## Input Arguments

Entries in the following table describe the input arguments for `adaptfilt.tdafdct`.

Input Argument	Description
<code>1</code>	Adaptive filter length (the number of coefficients or taps) and it must be a positive integer. <code>1</code> defaults to 10.
<code>step</code>	Adaptive filter step size. It must be a nonnegative scalar. You can use <code>maxstep</code> to determine a reasonable range of step size values for the signals being processed. <code>step</code> defaults to 0.
<code>leakage</code>	Leakage parameter of the adaptive filter. When you set this argument to a value between zero and one, you are implementing a leaky version of the TDAFDCT algorithm. <code>leakage</code> defaults to 1 — no leakage.
<code>offset</code>	Offset for the normalization terms in the coefficient updates. You can use this argument to avoid dividing by zero or by very small numbers when any of the FFT input signal powers become very small. <code>offset</code> defaults to zero.

Input Argument	Description
delta	Initial common value of all of the transform domain powers. Its initial value should be positive. delta defaults to 5.
lambda	Averaging factor used to compute the exponentially-windowed estimates of the powers in the transformed signal bins for the coefficient updates. lambda should lie between zero and one. For default filter objects, lambda equals (1 - step).
coeffs	Initial time domain coefficients of the adaptive filter. Set it to be a length 1 vector. coeffs defaults to a zero vector of length 1.
states	Initial conditions of the adaptive filter. states defaults to a zero vector with length equal to (1 - 1).

## Properties

Since your `adaptfilt.tdafdct` filter is an object, it has properties that define its behavior in operation. Note that many of the properties are also input arguments for creating `adaptfilt.tdafdct` objects. To show you the properties that apply, this table lists and describes each property for the transform domain filter object.

Name	Range	Description
Algorithm	None	Defines the adaptive filter algorithm the object uses during adaptation.
AvgFactor		Averaging factor used to compute the exponentially-windowed estimates of the powers in the transformed signal bins for the coefficient updates. AvgFactor

Name	Range	Description
		should lie between zero and one. For default filter objects, AvgFactor equals (1 - step). lambda is the input argument that represent AvgFactor.
Coefficients	Vector of elements	Vector containing the initial filter coefficients. It must be a length 1 vector where 1 is the number of filter coefficients. coeffs defaults to length 1 vector of zeros when you do not provide the argument for input.
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps.
Leakage	0 to 1	Leakage parameter of the adaptive filter. When you set this argument to a value between zero and one, you are implementing a leaky version of the TDAFDFT algorithm. leakage defaults to 1 — no leakage.
Offset		Offset for the normalization terms in the coefficient updates. You can use this argument to avoid dividing by zeros or by very small numbers when any of the FFT input signal powers become very small. offset defaults to zero.

Name	Range	Description
PersistentMemory	false or true	Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter. PersistentMemory returns to zero any state that the filter changes during processing. States that the filter does not change are not affected. Defaults to false.
Power	2*1 element vector	A vector of 2*1 elements, each initialized with the value delta from the input arguments. As you filter data, Power gets updated by the filter process.
States	Vector of elements, data type double	Vector of the adaptive filter states. states defaults to a vector of zeros which has length equal to (1 + projectord - 2).
StepSize	0 to 1	Step size. It must be a nonnegative scalar, greater than zero and less than or equal to 1. You can use maxstep to determine a reasonable range of step size values for the signals being processed. step defaults to 0.


For checking the values of properties for an adaptive filter object, use `get(ha)` or enter the object name, without a trailing semicolon, at the MATLAB prompt.

## Examples

Using 1000 iterations, perform a Quadrature Phase Shift Keying (QPSK) adaptive equalization using a 32-coefficient FIR filter.

```
D = 16; % Number of samples of delay
b = exp(1j*pi/4)*[-0.7 1]; % Numerator coefficients of channel
a = [1 -0.7]; % Denominator coefficients of channel
ntr= 1000; % Number of iterations
s = sign(randn(1,ntr+D)) + 1j*sign(randn(1,ntr+D)); %QPSK signal
n = 0.1*(randn(1,ntr+D) + 1j*randn(1,ntr+D)); % Noise signal
r = filter(b,a,s)+n; % Received signal
x = r(1+D:ntr+D); % Input signal (received signal)
d = s(1:ntr); % Desired signal (delayed QPSK signal)
L = 32; % filter length
mu = 0.01; % Step size
ha = adaptfilt.tdafdct(L,mu);
[y,e] = filter(ha,x,d);
subplot(2,2,1);
plot(1:ntr,real([d;y;e])); title('In-Phase Components');
legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,2,2); plot(1:ntr,imag([d;y;e]));
title('Quadrature Components');
legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,2,3); plot(x(ntr-100:ntr),'.');
axis([-3 3 -3 3]); title('Received Signal Scatter Plot');
axis('square'); xlabel('Real[x]'); ylabel('Imag[x]'); grid on;
subplot(2,2,4); plot(y(ntr-100:ntr),'.'); axis([-3 3 -3 3]);
title('Equalized Signal Scatter Plot'); grid on;
axis('square'); xlabel('Real[y]'); ylabel('Imag[y]');
```

Compare the plots shown in this figure to those in the other time domain filter variations. The comparison should help you select and understand how the variants differ.



**References**

Haykin, S., *Adaptive Filter Theory*, 3rd Edition, Prentice Hall, N.J., 1996.

**See Also**

[adaptfilt.tdafdft](#) | [adaptfilt.fdaf](#) | [adaptfilt.blms](#)

# adaptfilt.tdafdft

---

**Purpose** Adaptive filter that uses discrete Fourier transform

**Syntax** `ha = adaptfilt.tdafdft(1,step,leakage,offset,  
delta,lambda,...coeffs,states)`

**Description** `ha = adaptfilt.tdafdft(1,step,leakage,offset,  
delta,lambda,...coeffs,states)` constructs a transform-domain adaptive filter object `ha` using a discrete Fourier transform.

## Input Arguments

Entries in the following table describe the input arguments for `adaptfilt.tdafdft`.

Input Argument	Description
<code>1</code>	Adaptive filter length (the number of coefficients or taps) and it must be a positive integer. <code>1</code> defaults to 10.
<code>step</code>	Adaptive filter step size. It must be a nonnegative scalar. You can use <code>maxstep</code> to determine a reasonable range of step size values for the signals being processed. <code>step</code> defaults to 0.
<code>leakage</code>	Leakage parameter of the adaptive filter. When you set this argument to a value between zero and one, you are implementing a leaky version of the TDAFDFT algorithm. <code>leakage</code> defaults to 1 — no leakage.
<code>offset</code>	Offset for the normalization terms in the coefficient updates. You can use this argument to avoid dividing by zeros or by very small numbers when any of the FFT input signal powers become very small. <code>offset</code> defaults to zero.

Input Argument	Description
delta	Initial common value of all of the transform domain powers. Its initial value should be positive. delta defaults to 5.
lambda	Averaging factor used to compute the exponentially-windowed estimates of the powers in the transformed signal bins for the coefficient updates. lambda should lie between zero and one. For default filter objects, LAMBDA equals (1 - step).
coeffs	Initial time domain coefficients of the adaptive filter. Set it to be a length 1 vector. coeffs defaults to a zero vector of length 1.
states	Initial conditions of the adaptive filter. states defaults to a zero vector with length equal to (1 - 1).

## Properties

Since your `adaptfilt.tdafdft` filter is an object, it has properties that define its behavior in operation. Note that many of the properties are also input arguments for creating `adaptfilt.tdafdft` objects. To show you the properties that apply, this table lists and describes each property for the transform domain filter object.

Name	Range	Description
Algorithm	None	Defines the adaptive filter algorithm the object uses during adaptation
AvgFactor		Averaging factor used to compute the exponentially-windowed estimates of the powers in the transformed signal bins for the coefficient updates. AvgFactor

Name	Range	Description
		should lie between zero and one. For default filter objects, AvgFactor equals (1 - step). lambda is the input argument that represent AvgFactor.
Coefficients	Vector of elements	Vector containing the initial filter coefficients. It must be a length 1 vector where 1 is the number of filter coefficients. coeffs defaults to length 1 vector of zeros when you do not provide the argument for input.
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps
Leakage	0 to 1	Leakage parameter of the adaptive filter. When you set this argument to a value between zero and one, you are implementing a leaky version of the TDAFDFT algorithm. leakage defaults to 1 — no leakage.
Offset		Offset for the normalization terms in the coefficient updates. You can use this argument to avoid dividing by zeros or by very small numbers when any of the FFT input signal powers become very small. offset defaults to zero.

Name	Range	Description
PersistentMemory	false or true	Determines whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter. PersistentMemory returns to zero any state that the filter changes during processing. States that the filter does not change are not affected. Defaults to false.
Power	2*1 element vector	A vector of 2*1 elements, each initialized with the value delta from the input arguments. As you filter data, Power gets updated by the filter process.
States	Vector of elements, data type double	Vector of the adaptive filter states. states defaults to a vector of zeros which has length equal to (1 + projectord - 2).
StepSize	0 to 1	Step size. It must be a nonnegative scalar, greater than zero and less than or equal to 1. step defaults to 0.

### Examples


Quadrature Phase Shift Keying (QPSK) adaptive equalization using a 32-coefficient FIR filter (1000 iterations).

```
D = 16; % Number of samples of delay
b = exp(1j*pi/4)*[-0.7 1]; % Numerator coefficients of channel
a = [1 -0.7]; % Denominator coefficients of channel
ntr= 1000; % Number of iterations
```

```
s = sign(randn(1,ntr+D)) + 1j*sign(randn(1,ntr+D));% Baseband QPSK signal
n = 0.1*(randn(1,ntr+D) + 1j*randn(1,ntr+D));      % Noise signal
r = filter(b,a,s)+n;                               % Received signal
x = r(1+D:ntr+D);                                  % Input signal (received signal)
d = s(1:ntr);                                       % Desired signal (delayed QPSK signal)
L = 32;                                             % filter length
mu = 0.01;                                         % Step size
ha = adaptfilt.tdafdft(L,mu);
[y,e] = filter(ha,x,d);
subplot(2,2,1); plot(1:ntr,real([d;y;e]));
title('In-Phase Components');
legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,2,2); plot(1:ntr,imag([d;y;e]));
title('Quadrature Components');
legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,2,3); plot(x(ntr-100:ntr),'.');
axis([-3 3 -3 3]); title('Received Signal Scatter Plot');
axis('square'); xlabel('Real[x]'); ylabel('Imag[x]'); grid on;
subplot(2,2,4); plot(y(ntr-100:ntr),'.');
axis([-3 3 -3 3]); title('Equalized Signal Scatter Plot');
axis('square'); xlabel('Real[y]'); ylabel('Imag[y]'); grid on;
```

All of the time domain adaptive filter reference pages use this QPSK example. By comparing the results for each variation you get an idea of the differences in the way each one performs.

This figure demonstrates the results of running the example code shown.



**References**

Haykin, S., *Adaptive Filter Theory*, 3rd Edition, Prentice Hall, N.J., 1996

**See Also**

adaptfilt.tdafdfct | adaptfilt.fdaf | adaptfilt.blms

# adaptfilt.ufdaf

---

**Purpose** FIR adaptive filter that uses unconstrained frequency-domain with quantized step size normalization

**Syntax** `ha = adaptfilt.ufdaf(1,step,leakage,delta,lambda,blocklen,offset,coeffs,states)`

**Description** `ha = adaptfilt.ufdaf(1,step,leakage,delta,lambda,blocklen,offset,coeffs,states)`

constructs an unconstrained frequency-domain FIR adaptive filter `ha` with quantized step size normalization.

## Input Arguments

Entries in the following table describe the input arguments for `adaptfilt.ufdaf`.

Input Argument	Description
1	Adaptive filter length (the number of coefficients or taps) and it must be a positive integer. 1 defaults to 10.
step	Adaptive filter step size. It must be a nonnegative scalar. <code>step</code> defaults to 0.
leakage	Leakage parameter of the adaptive filter. When you set this argument to a value between zero and one, you are implementing a leaky version of the UFDAF algorithm. <code>leakage</code> defaults to 1 — no leakage.
delta	Initial common value of all of the FFT input signal powers. the initial value of <code>delta</code> should be positive, and it defaults to 1.

<b>Input Argument</b>	<b>Description</b>
<code>lambda</code>	Specifies the averaging factor used to compute the exponentially-windowed FFT input signal powers for the coefficient updates. <code>lambda</code> should lie in the range (0,1]. For default UFDaf filter objects, <code>lambda</code> defaults to 0.9.
<code>blocklen</code>	Block length for the coefficient updates. This must be a positive integer. For faster execution, ( <code>blocklen - 1</code> ) should be a power of two. <code>blocklen</code> defaults to 1.
<code>offset</code>	Offset for the normalization terms in the coefficient updates. This can help you avoid divide by zero conditions, or divide by very small numbers conditions, when any of the FFT input signal powers become very small. Default value is zero.
<code>coeffs</code>	Initial time-domain coefficients of the adaptive filter. It should be a length 1 vector. The filter object uses these coefficients to compute the initial frequency-domain filter coefficients via an FFT computed after zero-padding the time-domain vector by <code>blocklen</code> .
<code>states</code>	Adaptive filter states. <code>states</code> defaults to a zero vector with length equal to 1.

## Properties

Since your `adaptfilt.ufdaf` filter is an object, it has properties that define its behavior in operation. Note that many of the properties are also input arguments for creating `adaptfilt.ufdaf` objects. To show you the properties that apply, this table lists and describes each property for the filter object.

Name	Range	Description
Algorithm	None	Defines the adaptive filter algorithm the object uses during adaptation
AvgFactor		Specifies the averaging factor used to compute the exponentially-windowed FFT input signal powers for the coefficient updates. AvgFactor should lie in the range (0,1]. For default UFDAF filter objects, AvgFactor defaults to 0.9. Note that AvgFactor and lambda are the same thing — lambda is an input argument and AvgFactor a property of the object.
BlockLength		Block length for the coefficient updates. This must be a positive integer. For faster execution, (blocklen + 1) should be a power of two. blocklen defaults to 1.
FFTCoefficients		Stores the discrete Fourier transform of the filter coefficients in coeffs.
FFTStates		States for the FFT operation.
FilterLength	Any positive integer	Reports the length of the filter, the number of coefficients or taps

<b>Name</b>	<b>Range</b>	<b>Description</b>
Leakage	0 to 1	Leakage parameter of the adaptive filter. When you set this argument to a value between zero and one, you are implementing a leaky version of the UFDAF algorithm. Leakage defaults to 1 — no leakage.
Offset		Offset for the normalization terms in the coefficient updates. This can help you avoid divide by zero conditions, or divide by very small numbers conditions, when any of the FFT input signal powers become very small. Default value is zero.
PersistentMemory	false or true	Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter. PersistentMemory returns to zero any state that the filter changes during processing. States that the filter does not change are not affected. Defaults to false.

Name	Range	Description
Power	2*1 element vector	A vector of 2*1 elements, each initialized with the value <code>delta</code> from the input arguments. As you filter data, Power gets updated by the filter process.
StepSize	0 to 1	Adaptive filter step size. It must be a nonnegative scalar. You can use <code>maxstep</code> to determine a reasonable range of step size values for the signals being processed. <code>step</code> defaults to 0.

## Examples

Show an example of Quadrature Phase Shift Keying (QPSK) adaptive equalization using a 32-coefficient adaptive filter. For fidelity, use 1024 iterations. The figure that follows the code provides the information you need to assess the performance of the equalization process.

```


D = 16; % Number of samples of delay
b = exp(1j*pi/4)*[-0.7 1]; % Numerator coefficients of channel
a = [1 -0.7]; % Denominator coefficients of channel
ntr= 1024; % Number of iterations
s = sign(randn(1,ntr+D))+1j*sign(randn(1,ntr+D));% Baseband QPSK signal
n = 0.1*(randn(1,ntr+D) + 1j*randn(1,ntr+D));
r = filter(b,a,s)+n;% Received signal
x = r(1+D:ntr+D); % Input signal (received signal)
d = s(1:ntr); % Desired signal (delayed QPSK signal)
del = 1; %Initial FFT input powers
mu = 0.1; % Step size
lam = 0.9; % Averaging factor
ha = adaptfilt.ufdaf(32,mu,1,del,lam);
[y,e] = filter(ha,x,d);
subplot(2,2,1); plot(1:1000,real([d(1:1000);y(1:1000);e(1:1000)]));

```

```

title('In-Phase Components'); legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,2,2); plot(1:ntr,imag([d;y;e]));
title('Quadrature Components'); legend('Desired','Output','Error');
xlabel('Time Index'); ylabel('Signal Value');
subplot(2,2,3); plot(x(ntr-100:ntr),'.'); axis([-3 3 -3 3]);
title('Received Signal Scatter Plot'); axis('square');
xlabel('Real[x]'); ylabel('Imag[x]'); grid on;
subplot(2,2,4); plot(y(ntr-100:ntr),'.'); axis([-3 3 -3 3]);
title('Equalized Signal Scatter Plot'); axis('square');
xlabel('Real[y]'); ylabel('Imag[y]'); grid on;

```



**References**

Shynk, J.J., “Frequency-domain and Multirate Adaptive Filtering,” IEEE Signal Processing Magazine, vol. 9, no. 1, pp. 14-37, Jan. 1992

**See Also**

adaptfilt.fdaf | adaptfilt.pbufdaf | adaptfilt.blms | adaptfilt.blmsfft

# allpassbpc2bpc

---

**Purpose** Allpass filter for complex bandpass transformation

**Syntax** [AllpassNum,AllpassDen] = allpassbpc2bpc(Wo,Wt)

**Description** [AllpassNum,AllpassDen] = allpassbpc2bpc(Wo,Wt) returns the numerator, AllpassNum, and the denominator, AllpassDen, of the first-order allpass mapping filter for performing a complex bandpass to complex bandpass frequency transformation. This transformation effectively places two features of an original filter, located at frequencies  $W_{o1}$  and  $W_{o2}$ , at the required target frequency locations  $W_{t1}$  and  $W_{t2}$ . It is assumed that  $W_{t2}$  is greater than  $W_{t1}$ . In most of the cases the features selected for the transformation are the band edges of the filter passbands. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones.

Relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter,  $F_1$  and  $F_2$ , with  $F_1$  preceding  $F_2$ . Feature  $F_1$  will still precede  $F_2$  after the transformation. However, the distance between  $F_1$  and  $F_2$  will not be the same before and after the transformation.

This transformation can also be used for transforming other types of filters; e.g., complex notch filters or resonators can be repositioned at two distinct desired frequencies at any place around the unit circle. This is very attractive for adaptive systems.

## Examples

Design the allpass mapping filter changing the complex bandpass filter with the band edges at  $W_{o1}=0.2$  and  $W_{o2}=0.4$  to the new band edges of  $W_{t1}=0.3$  and  $W_{t2}=0.6$ . Find the frequency response of the allpass mapping filter:

```
Wo = [0.2, 0.4]; Wt = [0.3, 0.6];
[AllpassNum, AllpassDen] = allpassbpc2bpc(Wo, Wt);
[ha, f] = freqz(AllpassNum, AllpassDen, 'whole');
plot(f/pi, angle(ha)/pi, Wt, Wo, 'ro'); title('Mapping Function Wo(Wt)');
xlabel('New Frequency, Wt'); ylabel('Old Frequency, Wo');
```

## Arguments

Variable	Description
<i>Wo</i>	Frequency values to be transformed from the prototype filter
<i>Wt</i>	Desired frequency locations in the transformed target filter
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

Frequencies must be normalized to be between -1 and 1, with 1 corresponding to half the sample rate.

## See Also

`iirbpc2bpc` | `zpkbpc2bpc`

# allpasslp2bp

---

**Purpose** Allpass filter for lowpass to bandpass transformation

**Syntax** [AllpassNum, AllpassDen] = allpasslp2bp(Wo, Wt)

**Description** [AllpassNum, AllpassDen] = allpasslp2bp(Wo, Wt) returns the numerator, AllpassNum, and the denominator, AllpassDen, of the second-order allpass mapping filter for performing a real lowpass to real bandpass frequency transformation. This transformation effectively places one feature of an original filter, located at frequency  $-W_o$ , at the required target frequency location,  $W_{t1}$ , and the second feature, originally at  $+W_o$ , at the new location,  $W_{t2}$ . It is assumed that  $W_{t2}$  is greater than  $W_{t1}$ . This transformation implements the “DC mobility,” which means that the Nyquist feature stays at Nyquist, but the DC feature moves to a location dependent on the selection of  $W_t$ .

Relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter,  $F_1$  and  $F_2$ , with  $F_1$  preceding  $F_2$ . Feature  $F_1$  will still precede  $F_2$  after the transformation. However, the distance between  $F_1$  and  $F_2$  will not be the same before and after the transformation.

Choice of the feature subject to the lowpass to bandpass transformation is not restricted only to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones.

Lowpass to bandpass transformation can also be used for transforming other types of filters; e.g., real notch filters or resonators can be doubled and repositioned at two distinct desired frequencies.


**Examples** Design the allpass mapping filter changing the lowpass filter with cutoff frequency at  $W_o=0.5$  to the real-valued bandpass filter with cutoff frequencies at  $W_{t1}=0.25$  and  $W_{t2}=0.375$ .

Compute the frequency response and plot the phase response normalized to  $\pi$ , which is in effect the mapping function  $W_o(W_t)$ . Please note that the transformation works in the same way for both positive and negative frequencies:

```

Wo = 0.5; Wt = [0.25, 0.375];
[AllpassNum, AllpassDen] = allpasslp2bp(Wo, Wt);
[h, f] = freqz(AllpassNum, AllpassDen, 'whole');
plot(f/pi, abs(angle(h))/pi, Wt, Wo, 'ro');
title('Mapping Function Wo(Wt)');
xlabel('New Frequency, Wt'); ylabel('Old Frequency, Wo');

```



## Arguments

Variable	Description
<i>Wo</i>	Frequency value to be transformed from the prototype filter
<i>Wt</i>	Desired frequency locations in the transformed target filter

Variable	Description
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

Frequencies must be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.

## References

Constantinides, A.G., "Spectral transformations for digital filters," *IEEE Proceedings*, vol. 117, no. 8, pp. 1585-1590, August 1970.

Nowrouzian, B. and A.G. Constantinides, "Prototype reference transfer function parameters in the discrete-time frequency transformations," *Proceedings 33rd Midwest Symposium on Circuits and Systems*, Calgary, Canada, vol. 2, pp. 1078-1082, August 1990.

Nowrouzian, B. and L.T. Bruton, "Closed-form solutions for discrete-time elliptic transfer functions," *Proceedings of the 35th Midwest Symposium on Circuits and Systems*, vol. 2, pp. 784-787, 1992.

Constantinides, A.G., "Design of bandpass digital filters," *IEEE Proceedings*, vol. 1, pp. 1129-1231, June 1969.

## See Also

iir1p2bp | zpk1p2bp

**Purpose**

Allpass filter for lowpass to complex bandpass transformation

**Syntax**

[AllpassNum,AllpassDen] = allpasslp2bpc(Wo,Wt)

**Description**

[AllpassNum,AllpassDen] = allpasslp2bpc(Wo,Wt) returns the numerator, AllpassNum, and the denominator, AllpassDen, of the first-order allpass mapping filter for performing a real lowpass to complex bandpass frequency transformation. This transformation effectively places one feature of an original filter, located at frequency  $-W_o$ , at the required target frequency location,  $W_{t1}$ , and the second feature, originally at  $+W_o$ , at the new location,  $W_{t2}$ . It is assumed that  $W_{t2}$  is greater than  $W_{t1}$ .

Relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter,  $F_1$  and  $F_2$ , with  $F_1$  preceding  $F_2$ . Feature  $F_1$  will still precede  $F_2$  after the transformation. However, the distance between  $F_1$  and  $F_2$  will not be the same before and after the transformation.

Choice of the feature subject to the lowpass to bandpass transformation is not restricted only to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones.

Lowpass to bandpass transformation can also be used for transforming other types of filters; e.g., real notch filters or resonators can be doubled and positioned at two distinct desired frequencies at any place around the unit circle forming a pair of complex notches/resonators. This transformation can be used for designing bandpass filters for radio receivers from the high-quality prototype lowpass filter.

**Examples**

Design the allpass mapping filter changing the real lowpass filter with the cutoff frequency of  $W_o=0.5$  into a complex bandpass filter with band edges of  $W_{t1}=0.2$  and  $W_{t2}=0.4$  precisely defined. Calculate the frequency response of the mapping filter in the full range:

```
Wo = 0.5; Wt = [0.2,0.4];
[AllpassNum, AllpassDen] = allpasslp2bpc(Wo, Wt);
```

# allpasslp2bpc

---

```
[h, f] = freqz(AllpassNum, AllpassDen, 'whole');
```

## Arguments

Variable	Description
<i>Wo</i>	Frequency value to be transformed from the prototype filter. It should be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.
<i>Wt</i>	Desired frequency locations in the transformed target filter. They should be normalized to be between -1 and 1, with 1 corresponding to half the sample rate.
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

## See Also

iir1p2bpc | zpk1p2bpc

**Purpose**

Allpass filter for lowpass to bandstop transformation

**Syntax**

[AllpassNum,AllpassDen] = allpasslp2bs(Wo,Wt)

**Description**

[AllpassNum,AllpassDen] = allpasslp2bs(Wo,Wt) returns the numerator, AllpassNum, and the denominator, AllpassDen, of the second-order allpass mapping filter for performing a real lowpass to real bandstop frequency transformation. This transformation effectively places one feature of an original filter, located at frequency  $-W_o$ , at the required target frequency location,  $W_{t1}$ , and the second feature, originally at  $+W_o$ , at the new location,  $W_{t2}$ . It is assumed that  $W_{t2}$  is greater than  $W_{t1}$ . This transformation implements the "Nyquist Mobility," which means that the DC feature stays at DC, but the Nyquist feature moves to a location dependent on the selection of  $W_o$  and  $W_t$ .

Relative positions of other features of an original filter change in the target filter. This means that it is possible to select two features of an original filter,  $F_1$  and  $F_2$ , with  $F_1$  preceding  $F_2$ . After the transformation feature  $F_2$  will precede  $F_1$  in the target filter. However, the distance between  $F_1$  and  $F_2$  will not be the same before and after the transformation.


Choice of the feature subject to the lowpass to bandstop transformation is not restricted only to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones.

**Examples**

Design the allpass filter changing the lowpass filter with cutoff frequency at  $W_o=0.5$  to the real bandstop filter with cutoff frequencies at  $W_{t1}=0.25$  and  $W_{t2}=0.375$ :

```
Wo = 0.5; Wt = [0.25, 0.375];
[AllpassNum, AllpassDen] = allpasslp2bs(Wo, Wt);
[h, f] = freqz(AllpassNum, AllpassDen, 'whole');
plot(f/pi, abs(angle(h))/pi, Wt, Wo, 'ro');
title('Mapping Function Wo(Wt)');
xlabel('New Frequency, Wt'); ylabel('Old Frequency, Wo');
```

In the figure, you find the mapping filter function as determined by the example. Note the response is normalized to  $\pi$ :



## Arguments

Variable	Description
$W_o$	Frequency value to be transformed from the prototype filter
$W_t$	Desired frequency locations in the transformed target filter
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

Frequencies must be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.

## References

Constantinides, A.G., "Spectral transformations for digital filters," *IEEE Proceedings*, vol. 117, no. 8, pp. 1585-1590, August 1970.

Nowrouzian, B. and A.G. Constantinides, "Prototype reference transfer function parameters in the discrete-time frequency transformations," *Proceedings 33rd Midwest Symposium on Circuits and Systems*, Calgary, Canada, vol. 2, pp. 1078-1082, August 1990.

Nowrouzian, B. and L.T. Bruton, "Closed-form solutions for discrete-time elliptic transfer functions," *Proceedings of the 35th Midwest Symposium on Circuits and Systems*, vol. 2, pp. 784-787, 1992.

Constantinides, A.G., "Design of bandpass digital filters," *IEEE Proceedings*, vol. 1, pp. 1129-1231, June 1969.

## See Also

iir1p2bs | zpk1p2bs

# allpasslp2bsc

---

**Purpose** Allpass filter for lowpass to complex bandstop transformation

**Syntax** [AllpassNum,AllpassDen] = allpasslp2bsc(Wo,Wt)

**Description** [AllpassNum,AllpassDen] = allpasslp2bsc(Wo,Wt) returns the numerator, AllpassNum, and the denominator, AllpassDen, of the first-order allpass mapping filter for performing a real lowpass to complex bandstop frequency transformation. This transformation effectively places one feature of an original filter, located at frequency  $-W_o$ , at the required target frequency location,  $W_{t1}$ , and the second feature, originally at  $+W_o$ , at the new location,  $W_{t2}$ . It is assumed that  $W_{t2}$  is greater than  $W_{t1}$ . Additionally the transformation swaps passbands with stopbands in the target filter.

Relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter,  $F_1$  and  $F_2$ , with  $F_1$  preceding  $F_2$ . Feature  $F_1$  will still precede  $F_2$  after the transformation. However, the distance between  $F_1$  and  $F_2$  will not be the same before and after the transformation.

Choice of the feature subject to the lowpass to bandstop transformation is not restricted only to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones.

Lowpass to bandpass transformation can also be used for transforming other types of filters; e.g., real notch filters or resonators can be doubled and positioned at two distinct desired frequencies at any place around the unit circle forming a pair of complex notches/resonators. This transformation can be used for designing bandstop filters for band attenuation or frequency equalizers, from the high-quality prototype lowpass filter.

**Examples** Design the allpass filter changing the real lowpass filter with the cutoff frequency of  $W_o=0.5$  into a complex bandstop filter with band edges of  $W_{t1}=0.2$  and  $W_{t2}=0.4$  precisely defined:

```
Wo = 0.5; Wt = [0.2,0.4];
```

```
[AllpassNum, AllpassDen] = allpasslp2bsc(Wo, Wt);  
[h, f] = freqz(AllpassNum, AllpassDen, 'whole');
```

## Arguments

Variable	Description
<i>Wo</i>	Frequency value to be transformed from the prototype filter. It should be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.
<i>Wt</i>	Desired frequency locations in the transformed target filter. They should be normalized to be between -1 and 1, with 1 corresponding to half the sample rate.
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

## See Also

iir1p2bsc | zpk1p2bsc

# allpasslp2hp

---

**Purpose** Allpass filter for lowpass to highpass transformation

**Syntax** [AllpassNum, AllpassDen] = allpasslp2hp(Wo, Wt)

**Description** [AllpassNum, AllpassDen] = allpasslp2hp(Wo, Wt) returns the numerator, AllpassNum, and the denominator, AllpassDen, of the first-order allpass mapping filter for performing a real lowpass to real highpass frequency transformation. This transformation effectively places one feature of an original filter, located originally at frequency,  $W_o$ , at the required target frequency location,  $W_t$ , at the same time rotating the whole frequency response by half of the sampling frequency. Result is that the DC and Nyquist features swap places.

Relative positions of other features of an original filter change in the target filter. This means that it is possible to select two features of an original filter,  $F_1$  and  $F_2$ , with  $F_1$  preceding  $F_2$ . After the transformation feature  $F_2$  will precede  $F_1$  in the target filter. However, the distance between  $F_1$  and  $F_2$  will not be the same before and after the transformation.

Choice of the feature subject to the lowpass to highpass transformation is not restricted to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband.

Lowpass to highpass transformation can also be used for transforming other types of filters; e.g., notch filters or resonators can change their position in a simple way by using the lowpass to highpass transformation.

**Examples** Design the allpass filter changing the lowpass filter to the highpass filter with its cutoff frequency moved from  $W_o=0.5$  to  $W_t=0.25$ .

Plot the phase response normalized to  $\pi$ , which is in effect the mapping function  $W_o(W_t)$ . Please note that the transformation works in the same way for both positive and negative frequencies:

```
Wo = 0.5; Wt = 0.25;  
[AllpassNum, AllpassDen] = allpasslp2hp(Wo, Wt);
```

```
[h, f] = freqz(AllpassNum, AllpassDen, 'whole');
plot(f/pi, abs(angle(h))/pi, Wt, Wo, 'ro');
title('Mapping Function Wo(Wt)');
xlabel('New Frequency, Wt');
ylabel('Old Frequency, Wo');
```

## Arguments

Variable	Description
<i>Wo</i>	Frequency value to be transformed from the prototype filter
<i>Wt</i>	Desired frequency location in the transformed target filter
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

Frequencies must be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.

## References

- Constantinides, A.G., "Spectral transformations for digital filters," *IEE Proceedings*, vol. 117, no. 8, pp. 1585-1590, August 1970.
- Nowrouzian, B. and A.G. Constantinides, "Prototype reference transfer function parameters in the discrete-time frequency transformations," *Proceedings 33rd Midwest Symposium on Circuits and Systems*, Calgary, Canada, vol. 2, pp. 1078-1082, August 1990.
- Nowrouzian, B. and L.T. Bruton, "Closed-form solutions for discrete-time elliptic transfer functions," *Proceedings of the 35th Midwest Symposium on Circuits and Systems*, vol. 2, pp. 784-787, 1992.
- Constantinides, A.G., "Frequency transformations for digital filters," *Electronics Letters*, vol. 3, no. 11, pp. 487-489, November 1967.

## See Also

iir1p2hp | zpk1p2hp

# allpasslp2lp

---

**Purpose** Allpass filter for lowpass to lowpass transformation

**Syntax** [AllpassNum, AllpassDen] = allpasslp2lp(Wo, Wt)

**Description** [AllpassNum, AllpassDen] = allpasslp2lp(Wo, Wt) returns the numerator, AllpassNum, and the denominator, AllpassDen, of the first-order allpass mapping filter for performing a real lowpass to real lowpass frequency transformation. This transformation effectively places one feature of an original filter, located originally at frequency  $W_o$ , at the required target frequency location,  $W_t$ .

Relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter,  $F_1$  and  $F_2$ , with  $F_1$  preceding  $F_2$ . Feature  $F_1$  will still precede  $F_2$  after the transformation. However, the distance between  $F_1$  and  $F_2$  will not be the same before and after the transformation.

Choice of the feature subject to the lowpass to lowpass transformation is not restricted to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband and so on.


Lowpass to lowpass transformation can also be used for transforming other types of filters; e.g., notch filters or resonators can change their position in a simple way by applying the lowpass to lowpass transformation.

## Examples

Design the allpass filter changing the lowpass filter cutoff frequency originally at  $W_o=0.5$  to  $W_t=0.25$ . Plot the phase response normalized to  $\pi$ , which is in effect the mapping function  $W_o(W_t)$ . Please note that the transformation works in the same way for both positive and negative frequencies:

```
Wo = 0.5; Wt = 0.25;
[AllpassNum, AllpassDen] = allpasslp2lp(Wo, Wt);
[h, f] = freqz(AllpassNum, AllpassDen, 'whole');
plot(f/pi, abs(angle(h))/pi, Wt, Wo, 'ro');
title('Mapping Function Wo(Wt)');
```

```
xlabel('New Frequency, Wt'); ylabel('Old Frequency, Wo');
```



As shown in the figure, `allpass2lp` generates a mapping function that converts your prototype lowpass filter to a target lowpass filter with different passband specifications.

## Arguments

Variable	Description
$W_o$	Frequency value to be transformed from the prototype filter
$W_t$	Desired frequency location in the transformed target filter

Variable	Description
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

Frequencies must be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.

## References

Constantinides, A.G., "Spectral transformations for digital filters," *IEEE Proceedings*, vol. 117, no. 8, pp. 1585-1590, August 1970.

Nowrouzian, B. and A.G. Constantinides, "Prototype reference transfer function parameters in the discrete-time frequency transformations," *Proceedings 33rd Midwest Symposium on Circuits and Systems*, Calgary, Canada, vol. 2, pp. 1078-1082, August 1990.

Nowrouzian, B. and L.T. Bruton, "Closed-form solutions for discrete-time elliptic transfer functions," *Proceedings of the 35th Midwest Symposium on Circuits and Systems*, vol. 2, pp. 784-787, 1992.

Constantinides, A.G., "Frequency transformations for digital filters," *Electronics Letters*, vol. 3, no. 11, pp. 487-489, November 1967.

## See Also

iir1p2lp | zpk1p2lp

**Purpose**

Allpass filter for lowpass to M-band transformation

**Syntax**

```
[AllpassNum,AllpassDen] = allpasslp2mb(Wo,Wt)
[AllpassNum,AllpassDen] = allpasslp2mb(Wo,Wt,Pass)
```

**Description**

[AllpassNum,AllpassDen] = allpasslp2mb(Wo,Wt) returns the numerator, AllpassNum, and the denominator, AllpassDen, of the Mth-order allpass mapping filter for performing a real lowpass to real multipassband frequency transformation. Parameter M is the number of times an original feature is replicated in the target filter. This transformation effectively places one feature of an original filter, located at frequency  $W_o$ , at the required target frequency locations,  $W_{t1}, \dots, W_{tM}$ . By default the DC feature is kept at its original location.

[AllpassNum,AllpassDen] = allpasslp2mb(Wo,Wt,Pass) allows you to specify an additional parameter, Pass, which chooses between using the "DC Mobility" and the "Nyquist Mobility." In the first case the Nyquist feature stays at its original location and the DC feature is free to move. In the second case the DC feature is kept at an original frequency and the Nyquist feature is movable.

Relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter,  $F_1$  and  $F_2$ , with  $F_1$  preceding  $F_2$ . Feature  $F_1$  will still precede  $F_2$  after the transformation. However, the distance between  $F_1$  and  $F_2$  will not be the same before and after the transformation.


Choice of the feature subject to this transformation is not restricted to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones.

This transformation can also be used for transforming other types of filters; e.g., notch filters or resonators can be easily replicated at a number of required frequency locations without redesigning them. A good application would be an adaptive tone cancellation circuit reacting to the changing number and location of tones.

## Examples

Design the allpass filter changing the real lowpass filter with the cutoff frequency of  $W_0=0.5$  into a real multiband filter with band edges of  $W_t=[1:2:9]/10$  precisely defined. Plot the phase response normalized to  $\pi$ , which is in effect the mapping function  $W_0(W_t)$ . Please note that the transformation works in the same way for both positive and negative frequencies:

```
Wo = 0.5; Wt = [1:2:9]/10;  
[AllpassNum, AllpassDen] = allpasslp2mb(Wo, Wt);  
[h, f] = freqz(AllpassNum, AllpassDen, 'whole');  
plot(f/pi, abs(angle(h))/pi, Wt, Wo, 'ro');  
title('Mapping Function Wo(Wt)');  
xlabel('New Frequency, Wt'); ylabel('Old Frequency, Wo');
```



**Arguments**

Variable	Description
<i>Wo</i>	Frequency value to be transformed from the prototype filter
<i>Wt</i>	Desired frequency locations in the transformed target filter
<i>Pass</i>	Choice ('pass' / 'stop') of passband/stopband at DC, 'pass' being the default
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

Frequencies must be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.

**References**

Franchitti, J.C., "All-pass filter interpolation and frequency transformation problems," *MSc Thesis*, Dept. of Electrical and Computer Engineering, University of Colorado, 1985.

Feyh, G., J.C. Franchitti and C.T. Mullis, "All-pass filter interpolation and frequency transformation problem," *Proceedings 20th Asilomar Conference on Signals, Systems and Computers*, Pacific Grove, California, pp. 164-168, November 1986.

Mullis, C.T. and R.A. Roberts, *Digital Signal Processing*, section 6.7, Reading, Massachusetts, Addison-Wesley, 1987.

Feyh, G., W.B. Jones and C.T. Mullis, *An extension of the Schur Algorithm for frequency transformations*, *Linear Circuits, Systems and Signal Processing: Theory and Application*, C. J. Byrnes et al Eds, Amsterdam: Elsevier, 1988.

**See Also**

iir1p2mb | zpk1p2mb

# allpasslp2mbc

---

**Purpose** Allpass filter for lowpass to complex M-band transformation

**Syntax** [AllpassNum, AllpassDen] = allpasslp2mbc(Wo, Wt)

**Description** [AllpassNum, AllpassDen] = allpasslp2mbc(Wo, Wt) returns the numerator, AllpassNum, and the denominator, AllpassDen, of the Mth-order allpass mapping filter for performing a real lowpass to complex multipassband frequency transformation. Parameter M is the number of times an original feature is replicated in the target filter. This transformation effectively places one feature of an original filter, located at frequency  $W_o$ , at the required target frequency locations,  $W_{t1}, \dots, W_{tM}$ .

Relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter,  $F_1$  and  $F_2$ , with  $F_1$  preceding  $F_2$ . Feature  $F_1$  will still precede  $F_2$  after the transformation. However, the distance between  $F_1$  and  $F_2$  will not be the same before and after the transformation.

Choice of the feature subject to this transformation is not restricted to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones.

This transformation can also be used for transforming other types of filters; e.g., notch filters or resonators can be easily replicated at a number of required frequency locations without the need to design them again. A good application would be an adaptive tone cancellation circuit reacting to the changing number and location of tones.

**Examples** Design the allpass filter changing the real lowpass filter with the cutoff frequency of  $W_o=0.5$  into a complex multiband filter with band edges of  $W_t=[-3+1:2:9]/10$  precisely defined:

```
Wo = 0.5; Wt = [-3+1:2:9]/10;  
[AllpassNum, AllpassDen] = allpasslp2mbc(Wo, Wt);
```


Calculate the frequency response of the mapping filter in the full range:

```
[h, f] = freqz(AllpassNum, AllpassDen, 'whole');
```

Plot the phase response normalized to  $\pi$ , which is in effect the mapping function  $W_o(W_t)$ . Please note that the transformation works in the same way for both positive and negative frequencies:

```
plot(f/pi, angle(h)/pi, Wt, Wo, 'ro');
title('Mapping Function Wo(Wt)');
xlabel('New Frequency, Wt'); ylabel('Old Frequency, Wo');
```

In this example, the resulting mapping function converts real filters to multiband complex filters.



# allpasslp2mbc

---

## Arguments

Variable	Description
<i>Wo</i>	Frequency value to be transformed from the prototype filter. It should be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.
<i>Wt</i>	Desired frequency locations in the transformed target filter. They should be normalized to be between -1 and 1, with 1 corresponding to half the sample rate.
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

## See Also

iir1p2mbc | zpk1p2mbc

<b>Purpose</b>	Allpass filter for lowpass to complex N-point transformation
<b>Syntax</b>	[AllpassNum,AllpassDen] = allpasslp2xc(Wo,Wt)
<b>Description</b>	<p>[AllpassNum,AllpassDen] = allpasslp2xc(Wo,Wt) returns the numerator, AllpassNum, and the denominator, AllpassDen, of the Nth-order allpass mapping filter, where N is the allpass filter order, for performing a real lowpass to complex multipoint frequency transformation. Parameter N also specifies the number of replicas of the prototype filter created around the unit circle after the transformation. This transformation effectively places N features of the, original filter located at frequencies <math>W_{o1}, \dots, W_{oN}</math>, at the required target frequency locations, <math>W_{t1}, \dots, W_{tM}</math>.</p> <p>Relative positions of other features of an original filter are the same in the target filter for the Nyquist mobility and are reversed for the DC mobility. For the Nyquist mobility this means that it is possible to select two features of an original filter, <math>F_1</math> and <math>F_2</math>, with <math>F_1</math> preceding <math>F_2</math>. Feature <math>F_1</math> will still precede <math>F_2</math> after the transformation. However, the distance between <math>F_1</math> and <math>F_2</math> will not be the same before and after the transformation. For DC mobility feature <math>F_2</math> will precede <math>F_1</math> after the transformation.</p> <p>Choice of the feature subject to this transformation is not restricted to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones. The only condition is that the features must be selected in such a way that when creating N bands around the unit circle, there will be no band overlap.</p> <p>This transformation can also be used for transforming other types of filters; e.g., notch filters or resonators can be easily replicated at a number of required frequency locations. A good application would be an adaptive tone cancellation circuit reacting to the changing number and location of tones.</p>
<b>Examples</b>	Design the allpass filter moving four features of an original complex filter given in $W_o$ to the new independent frequency locations $W_t$ . Please

# allpasslp2xc

---

note that the transformation creates N replicas of an original filter around the unit circle, where N is the order of the allpass mapping filter:

```
Wo = [-0.2, 0.3, -0.7, 0.4]; Wt = [0.3, 0.5, 0.7, 0.9];  
[AllpassNum, AllpassDen] = allpasslp2xc(Wo, Wt);  
[h, f] = freqz(AllpassNum, AllpassDen, 'whole');
```

## Arguments

Variable	Description
<i>Wo</i>	Frequency values to be transformed from the prototype filter
<i>Wt</i>	Desired frequency locations in the transformed target filter
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

Frequencies must be normalized to be between -1 and 1, with 1 corresponding to half the sample rate.

## See Also

[iir1p2xc](#) | [zpk1p2xc](#)

**Purpose**

Allpass filter for lowpass to N-point transformation

**Syntax**

[AllpassNum,AllpassDen] = allpasslp2xn(Wo,Wt)  
 [AllpassNum,AllpassDen] = allpasslp2xn(Wo,Wt,Pass)

**Description**

[AllpassNum,AllpassDen] = allpasslp2xn(Wo,Wt) returns the numerator, AllpassNum, and the denominator, AllpassDen, of the Nth-order allpass mapping filter, where N is the allpass filter order, for performing a real lowpass to real multipoint frequency transformation. Parameter N also specifies the number of replicas of the prototype filter created around the unit circle after the transformation. This transformation effectively places N features of an original filter, located at frequencies  $W_{o1}, \dots, W_{oN}$ , at the required target frequency locations,  $W_{t1}, \dots, W_{tM}$ . By default the DC feature is kept at its original location.

[AllpassNum,AllpassDen] = allpasslp2xn(Wo,Wt,Pass) allows you to specify an additional parameter, Pass, which chooses between using the “DC Mobility” and the “Nyquist Mobility.” In the first case the Nyquist feature stays at its original location and the DC feature is free to move. In the second case the DC feature is kept at an original frequency and the Nyquist feature is movable.

Relative positions of other features of an original filter are the same in the target filter for the Nyquist mobility and are reversed for the DC mobility. For the Nyquist mobility this means that it is possible to select two features of an original filter,  $F_1$  and  $F_2$ , with  $F_1$  preceding  $F_2$ . Feature  $F_1$  will still precede  $F_2$  after the transformation. However, the distance between  $F_1$  and  $F_2$  will not be the same before and after the transformation. For DC mobility feature  $F_2$  will precede  $F_1$  after the transformation.

Choice of the feature subject to this transformation is not restricted to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones. The only condition is that the features must be selected in such a way that when creating N bands around the unit circle, there will be no band overlap.

This transformation can also be used for transforming other types of filters; e.g., notch filters or resonators can be easily replicated at a number of required frequency locations without the need of designing them again. A good application would be an adaptive tone cancellation circuit reacting to the changing number and location of tones.

## Arguments

Variable	Description
<i>Wo</i>	Frequency values to be transformed from the prototype filter
<i>Wt</i>	Desired frequency locations in the transformed target filter
<i>Pass</i>	Choice ('pass' / 'stop') of passband/stopband at DC, 'pass' being the default
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

Frequencies must be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.

## References

Cain, G.D., A. Krukowski and I. Kale, "High Order Transformations for Flexible IIR Filter Design," *VII European Signal Processing Conference (EUSIPCO'94)*, vol. 3, pp. 1582-1585, Edinburgh, United Kingdom, September 1994.

Krukowski, A., G.D. Cain and I. Kale, "Custom designed high-order frequency transformations for IIR filters," *38th Midwest Symposium on Circuits and Systems (MWSCAS'95)*, Rio de Janeiro, Brazil, August 1995.

## See Also

`iir1p2xn` | `zpk1p2xn`

**Purpose** Allpass filter for integer upsample transformation

**Syntax** [AllpassNum,AllpassDen] = allpassrateup(N)

**Description** [AllpassNum,AllpassDen] = allpassrateup(N) returns the numerator, AllpassNum, and the denominator, AllpassDen, of the Nth-order allpass mapping filter for performing the rateup frequency transformation, which creates N equal replicas of the prototype filter frequency response.

Relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter,  $F_1$  and  $F_2$ , with  $F_1$  preceding  $F_2$ . Feature  $F_1$  will still precede  $F_2$  after the transformation. However, the distance between  $F_1$  and  $F_2$  will not be the same before and after the transformation.

**Examples** Design the allpass filter creating the effect of upsampling the digital filter four times:

Choose any feature from an original filter, say at  $W_o=0.2$ :

```
N = 4;
Wo = 0.2; Wt = Wo/N + 2*[0:N-1]/N;
[AllpassNum, AllpassDen] = allpassrateup(N);
```

Calculate the frequency response of the mapping filter in the full range:

```
[h, f] = freqz(AllpassNum, AllpassDen, 'whole');
```

## Arguments

Variable	Description
<i>N</i>	Frequency replication ratio (upsampling ratio)
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

**See Also** iirrrateup | zpkrateup

# allpassshift

---

**Purpose** Allpass filter for real shift transformation

**Syntax** [AllpassNum,AllpassDen] = allpassshift(Wo,Wt)

**Description** [AllpassNum,AllpassDen] = allpassshift(Wo,Wt) returns the numerator, AllpassNum, and the denominator, AllpassDen, of the second-order allpass mapping filter for performing a real frequency shift transformation. This transformation places one selected feature of an original filter, located at frequency  $W_o$ , at the required target frequency location,  $W_t$ . This transformation implements the “DC mobility,” which means that the Nyquist feature stays at Nyquist, but the DC feature moves to a location dependent on the selection of  $W_o$  and  $W_t$ .

Relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter,  $F_1$  and  $F_2$ , with  $F_1$  preceding  $F_2$ . Feature  $F_1$  will still precede  $F_2$  after the transformation. However, the distance between  $F_1$  and  $F_2$  will not be the same before and after the transformation.

Choice of the feature subject to the real shift transformation is not restricted to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones.

This transformation can also be used for transforming other types of filters; e.g., notch filters or resonators can be moved to a different frequency by applying a shift transformation. In such a way you can avoid designing the filter from the beginning.

**Examples** Design the allpass filter precisely shifting one feature of the lowpass filter originally at  $W_o=0.5$  to the new frequencies of  $W_t=0.25$ :


```
Wo = 0.5; Wt = 0.25;  
[AllpassNum, AllpassDen] = allpassshift(Wo, Wt);
```

Calculate the frequency response of the mapping filter in the full range:

```
[h, f] = freqz(AllpassNum, AllpassDen, 'whole');
```

Plot the phase response normalized to  $\pi$ , which is in effect the mapping function  $W_o(W_t)$ . Please note that the transformation works in the same way for both positive and negative frequencies:

```
plot(f/pi, abs(angle(h))/pi, Wt, Wo, 'ro');  
title('Mapping Function Wo(Wt)');  
xlabel('New Frequency, Wt'); ylabel('Old Frequency, Wo');
```



# allpassshift

---

## Arguments

Variable	Description
<i>Wo</i>	Frequency value to be transformed from the prototype filter
<i>Wt</i>	Desired frequency location in the transformed target filter
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

Frequencies must be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.

## See Also

`iirshift` | `zpkshift`

**Purpose**

Allpass filter for complex shift transformation

**Syntax**

```
[AllpassNum,AllpassDen] = allpassshiftc(Wo,Wt)
[AllpassNum,AllpassDen] = allpassshiftc(0,0.5)
[AllpassNum,AllpassDen] = allpassshiftc(0,-0.5)
```

**Description**

[AllpassNum,AllpassDen] = allpassshiftc(Wo,Wt) returns the numerator, AllpassNum, and denominator, AllpassDen, vectors of the allpass mapping filter for performing a complex frequency shift of the frequency response of the digital filter by an arbitrary amount.

[AllpassNum,AllpassDen] = allpassshiftc(0,0.5) calculates the allpass filter for doing the Hilbert transformation, a 90 degree counterclockwise rotation of an original filter in the frequency domain.

[AllpassNum,AllpassDen] = allpassshiftc(0,-0.5) calculates the allpass filter for doing an inverse Hilbert transformation, i.e. a 90 degree clockwise rotation of an original filter in the frequency domain.

**Examples**

Design the allpass filter precisely rotating the whole filter by the amount defined by the location of the selected feature from an original filter,  $W_o=0.5$ , and its required position in the target filter,  $W_t=0.25$ :

```
Wo = 0.5; Wt = 0.25;
[AllpassNum, AllpassDen] = allpassshiftc(Wo, Wt);
```

Calculate the frequency response of the mapping filter in the full range:

```
[h, f] = freqz(AllpassNum, AllpassDen, 'whole');
```

**Arguments**

Variable	Description
<i>Wo</i>	Frequency value to be transformed from the prototype filter
<i>Wt</i>	Desired frequency location in the transformed target filter

# allpassshiftc

---

Variable	Description
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

Frequencies must be normalized to be between -1 and 1, with 1 corresponding to half the sample rate.

## References

Oppenheim, A.V., R.W. Schaffer and J.R. Buck, *Discrete-Time Signal Processing*, Prentice-Hall International Inc., 1989.

Dutta-Roy, S.C. and B. Kumar, "On Digital Differentiators, Hilbert Transformers, and Half-band Low-pass Filters," *IEEE Transactions on Education*, vol. 32, pp. 314-318, August 1989.

## See Also

iirshiftc | zpkshiftc

**Purpose** Automatic dynamic range scaling

**Syntax** `autoscale(hd,x)`  
`hnew = autoscale(hd,x)`

**Description** `autoscale(hd,x)` provides dynamic range scaling for each node of the filter `hd`. This method runs signal `x` through `hd` in floating-point to simulate filtering. `autoscale` uses the maximum and minimum data obtained from that simulation at each filter node to set fraction lengths to cover the simulation full range and maximize the precision. Word lengths are not changed during autoscaling.

`hnew = autoscale(hd,x)` If you request an output, `autoscale` returns a new filter with the scaled fraction lengths. The original filter is not changed.


For introductory demonstrations of the automatic scale process, refer to the following demos in the toolbox:

- Fixed-Point Scaling of an Elliptic IIR Filter
- Floating-Point to Fixed-Point Conversion of IIR Filters
- Floating-Point to Fixed-Point Conversion of FIR Filters

**Examples** Demonstrate dynamic range scaling in a lattice ARMA filter:

```
hd = design(fdesign.bandpass,'ellip');  
hd = convert(hd,'latticearma');  
hd.arithmetic = 'fixed';  
rng(4); x = rand(100,10); % Training input data.  
hd(2) = autoscale(hd,x);  
hfvf = fvtool(hd,'Analysis','mestimate','Showreference','off');  
legend(hfvf, 'Before Autoscaling', 'After Autoscaling')
```

# autoscale



**See Also** [qreport](#)

**Purpose** Generate block from multirate or multistage filter

**Syntax** `block(hm)`  
`block(hm, 'propertyname1', propertyvalue1, 'propertyname2', propertyvalue2, ...)`

**Description** `block(hm)` generates a DSP System Toolbox block equivalent to `hm`.  
`block(hm, 'propertyname1', propertyvalue1, 'propertyname2', propertyvalue2, ...)` generates a DSP System Toolbox block using the options specified in the property name/property value pairs. The valid properties and their values are

Property Name	Property Values	Description and Values
Destination	'current' (default), 'new', or <i>Subsystemname</i> .	Determine which Simulink model gets the block. Enter 'current', 'new', or specify the name of an existing subsystem with <i>Subsystemname</i> . 'current' adds the block to your current Simulink model. Specifying 'new' opens a new model and adds the block. Specifying <i>Subsystemname</i> opens a new model and adds the block. If you provide the name of a subsystem in <i>Subsystemname</i> , <code>block</code> adds the new block to your specified subsystem.
Blockname	'filter' (default)	Specify the name of the generated block. The name appears below the block in the model. When you do not specify a block name, the default is <code>filter</code> .

# block

Property Name	Property Values	Description and Values
OverwriteBlock	'off' (default), or 'on'.	Tell block whether to overwrite an existing block of the same name, or create a new block. 'off' is the default setting—block does not overwrite existing blocks with matching names. Switching from 'off' to 'on' directs block to overwrite existing blocks.
MapStates	'off' (default), or 'on'.	Specify whether to apply the current filter states to the new block. This lets you save states from a filter object you may have used or configured in a specific way. The default setting of 'off' means the states are not transferred to the block. Choosing 'on' preserves the current filter states in the block.
Link20bj	'off' (default), or 'on'.	Specify how to set the <b>Coefficient source</b> in the block mask. The default setting is 'off' and the <b>Coefficient source</b> is set to <b>Dialog parameters</b> . Setting Link20bj to 'on' sets the <b>Coefficient source</b> to <b>Discrete-time filter object (DFILT)</b> . The Link20bj and MapCoeffstoPorts cannot be simultaneously 'on'.

Property Name	Property Values	Description and Values
MapCoeffsToPorts	'off' (default) or 'on'	Specify whether to map the coefficients of the filter to the ports of the block. The Link2Obj and MapCoeffsToPorts cannot be simultaneously 'on'. See mfilt for a list of supported filter objects.
CoeffNames	{ 'Num' } (default FIR) { 'Num', 'Den' } (default direct form IIR) { 'Num', 'Den', 'g' } (default IIR SOS), { 'K' } (default form lattice)	Specify the coefficient variable names as string variables in a cell array. MapCoeffsToPorts must be set to 'on' for this property to apply.
InputProcessing	'columns as channels' (default), 'elements as channels', or 'inherited'	Specify sample-based (elements as channels) or frame-based (columns as channels) processing. The Inherited (this choice will be removed - see release notes) option will be removed in a future release.
RateOption	'enforce single rate' (default) or 'allow multirate'	Specify how the block adjusts the rate at the output to accommodate the reduced number of samples. This parameter applies only when InputProcessing is 'columns as channels'.

## Using block to Realize Fixed-Point Multirate Filters

When the source filter `hm` is fixed-point, the input word and fraction lengths for the block are derived from the block input signal. The realization process issues a warning and ignores the input word and input fraction lengths that are part of the source filter object, choosing to inherit the settings from the input data. Other fixed-point properties map directly to settings for word and fraction length in the realized block.

### Examples

Two examples of using `block` demonstrate the syntax capabilities. Both examples start from an `mfilt` object with interpolation factor of three. In the first example, use `block` with the default syntax, letting the function determine the block name and configuration.

```
hm = mfilt.firdecim(3);
```



Now use the default syntax to create a block.

```
block(hm);
```

In this second example, define the block name to meet your needs by using the property name/property value pair input arguments.

```
block(hm, 'blockname', 'firdecim');
```

The figure below shows the blocks in a Simulink model. When you try these examples, you see that the second block writes over the first block location. You can avoid this by moving the first block before you generate the second, always naming your block with the `blockname` property, or setting the `Destination` property to `new` which puts the filter block in a new Simulink model.



**See Also**

realizemd1

**How To**

- “Realize Filters as Simulink Subsystem Blocks”

# butter

---

**Purpose** Butterworth IIR filter design using specification object

**Syntax**  
`hd = design(d, 'butter')`  
`hd = design(d, 'butter', designoption, value...)`

**Description** `hd = design(d, 'butter')` designs a Butterworth IIR digital filter using the specifications supplied in the object `d`.

`hd = design(d, 'butter', designoption, value...)` returns a Butterworth IIR filter where you specify a design option and value.

To determine the available design options, use `designopts` with the specification object and the design method as input arguments as shown.

```
designopts(d, 'method')
```

For complete help about using `butter`, refer to the command line help system. For example, to get specific information about using `butter` with `d`, the specification object, enter the following at the MATLAB prompt.


```
help(d, 'butter')
```

**Examples** Construct a default lowpass filter specification object and design a Butterworth filter:

```
d = fdesign.lowpass;  
hd = design(d, 'butter', 'matchexactly', 'stopband');
```

Construct a highpass filter specification object and design a Butterworth filter:

```
%Order 8 and 3 dB frequency 0.6*pi radians/sample  
d = fdesign.highpass('N,F3dB',8,.6);  
hd = design(d, 'butter');  
fvtool(hd)
```



**See Also** [cheby1](#) | [cheby2](#) | [ellip](#)

**Purpose** Convert coupled allpass filter to transfer function form

**Syntax**  
[b,a]=ca2tf(d1,d2)  
[b,a]=ca2tf(d1,d2,beta)  
[b,a,bp]=ca2tf(d1,d2)  
[b,a,bp]=ca2tf(d1,d2,beta)

**Description** [b,a]=ca2tf(d1,d2) returns the vector of coefficients b and the vector of coefficients a corresponding to the numerator and the denominator of the transfer function

$$H(z) = B(z) / A(z) = \frac{1}{2} [H1(z) + H2(z)]$$

d1 and d2 are real vectors corresponding to the denominators of the allpass filters H1(z) and H2(z).

[b,a]=ca2tf(d1,d2,beta) where d1, d2 and beta are complex, returns the vector of coefficients b and the vector of coefficients a corresponding to the numerator and the denominator of the transfer function

$$H(z) = B(z) / A(z) = \frac{1}{2} [ -(\bar{\beta}) \cdot H1(z) + \beta \cdot H2(z) ]$$

[b,a,bp]=ca2tf(d1,d2), where d1 and d2 are real, returns the vector bp of real coefficients corresponding to the numerator of the power complementary filter G(z)

$$G(z) = Bp(z) / A(z) = \frac{1}{2} [H1(z) - H2(z)]$$

[b,a,bp]=ca2tf(d1,d2,beta), where d1, d2 and beta are complex, returns the vector of coefficients bp of real or complex coefficients that correspond to the numerator of the power complementary filter G(z)

$$G(z) = Bp(z) / A(z) = \frac{1}{2_j} [ -(\bar{\beta}) \cdot H1(z) + \beta \cdot H2(z) ]$$

## Examples

Create a filter, convert the filter to coupled allpass form, and convert the result back to the original structure (create the power complementary filter as well).

```
[b,a]=cheby1(10,.5,.4);
[d1,d2,beta]=tf2ca(b,a);           % tf2ca returns the %
                                   % denominators of the %
                                   % allpasses.

[num,den,numpc]=ca2tf(d1,         % Reconstruct the original
d2,beta);                          % filter plus the power %
                                   % complementary one.

[h,w,s]=freqz(num,den);
hpc = freqz(numpc,den);
s.plot = 'mag';
s.yunits = 'sq';
freqzplot([h hpc],w,s);           % Plot the mag response of
                                   % the % original filter and
                                   % the % power complementary
                                   % one.
```

## See Also

cl2tf | iirpowcomp | tf2ca | tf2cl

# cheby1

---

**Purpose** Chebyshev Type I filter using specification object

**Syntax**

```
hd = design(d, 'cheby1')  
hd = design(d, 'cheby1', designoption, value, designoption,  
value, ...)
```

**Description** `hd = design(d, 'cheby1')` designs a type I Chebyshev IIR digital filter using the specifications supplied in the object `d`. Depending on the filter specification object, `cheby1` may or may not be a valid design. Use `designmethods` with the filter specification object to determine if a Chebyshev type I filter design is possible.

`hd = design(d, 'cheby1', designoption, value, designoption, value, ...)` returns a type I Chebyshev IIR filter where you specify design options as input arguments.

To determine the available design options, use `designopts` with the specification object and the design method as input arguments as shown.

```
designopts(d, 'method')
```

For complete help about using `cheby1`, refer to the command line help system. For example, to get specific information about using `cheby1` with `d`, the specification object, enter the following at the MATLAB prompt.

```
help(d, 'cheby1')
```

**Examples** These examples use filter specification objects to construct Chebyshev type I filters. In the first example, you use the `matchexactly` option to ensure the performance of the filter in the passband.


```
d = fdesign.lowpass; designopts(d, 'cheby1');  
hd = design(d, 'cheby1', 'matchexactly', 'passband');
```

Specify the filter order, passband edge frequency, and the passband ripple to get the filter exactly as required.

```
d = fdesign.highpass('n,fp,ap',7,20,.4,50);  
hd = design(d,'cheby1');
```

Use `fvtool` to view the resulting filter.

```
fvtool(hd)
```



By design, `cheby1` returns filters that use second-order sections (SOS). For many applications, and for most fixed-point applications, SOS filters are particularly well-suited.

## See Also

[design](#) | [designmethods](#) | [fdesign](#)

# cheby2

---

## Purpose

Chebyshev Type II filter using specification object

## Syntax

```
hd = design(d, 'cheby2')  
hd = design(d, 'cheby2', designoption, value, designoption,  
value, ...)
```

## Description

`hd = design(d, 'cheby2')` designs a Chebyshev II IIR digital filter using the specifications supplied in the object `d`.

`hd = design(d, 'cheby2', designoption, value, designoption, value, ...)` returns a Chebyshev II IIR filter where you specify design options as input arguments.

To determine the available design options, use `designopts` with the specification object and the design method as input arguments as shown.

```
designopts(d, 'method')
```

For complete help about using `cheby1`, refer to the command line help system. For example, to get specific information about using `cheby2` with `d`, the specification object, enter the following at the MATLAB prompt.

```
help(d, 'cheby2')
```

## Examples

These examples use filter specification objects to construct Chebyshev type I filters. In the first example, you use the `matchexactly` option to ensure the performance of the filter in the passband.

```
d = fdesign.lowpass;  
hd = design(d, 'cheby2', 'matchexactly', 'passband');
```


`cheby2` also designs highpass, bandpass, and bandstop filters. Here is a highpass filter where you specify the filter order, the stopband edge frequency, and the stopband attenuation to get the filter exactly as required.

```
d = fdesign.highpass('n,fst,ast', 5, 20, 55, 50);
```

```
hd=design(d, 'cheby2');
```

The Filter Visualization Tool shows the highpass filter meets the specifications.

```
fvtool(hd)
```



By design, `cheby2` returns filters that use second-order sections. For many applications, and for most fixed-point applications, SOS filters are particularly well-suited for use.

## See Also

`butter` | `cheby1` | `ellip`

**Purpose** Convert coupled allpass lattice to transfer function form

**Syntax**  
[b,a] = cl2tf(k1,k2)  
[b,a] = cl2tf(k1,k2,beta)  
[b,a,bp] = cl2tf(k1,k2)  
[b,a,bp] = cl2tf(k1,k2,beta)

**Description** [b,a] = cl2tf(k1,k2) returns the numerator and denominator vectors of coefficients b and a corresponding to the transfer function

$$H(z) = B(z) / A(z) = \frac{1}{2} [H1(z) + H2(z)]$$

where  $H1(z)$  and  $H2(z)$  are the transfer functions of the allpass filters determined by  $k1$  and  $k2$ , and  $k1$  and  $k2$  are real vectors of reflection coefficients corresponding to allpass lattice structures.

[b,a] = cl2tf(k1,k2,beta) where  $k1$ ,  $k2$  and  $\beta$  are complex, returns the numerator and denominator vectors of coefficients b and a corresponding to the transfer function

$$H(z) = B(z) / A(z) = \frac{1}{2} [ -(\bar{\beta}) \cdot H1(z) + \beta \cdot H2(z) ]$$

[b,a,bp] = cl2tf(k1,k2) where  $k1$  and  $k2$  are real, returns the vector bp of real coefficients corresponding to the numerator of the power complementary filter  $G(z)$


$$G(z) = Bp(z) / A(z) = \frac{1}{2} [H1(z) - H2(z)]$$

[b,a,bp] = cl2tf(k1,k2,beta) where  $k1$ ,  $k2$  and  $\beta$  are complex, returns the vector of coefficients bp of possibly complex coefficients corresponding to the numerator of the power complementary filter  $G(z)$

$$G(z) = Bp(z) / A(z) = \frac{1}{2^j} [ -(\bar{\beta}) \cdot H1(z) + \beta \cdot H2(z) ]$$

## Examples

```
[b,a]=cheby1(10,.5,.4); %TF2CL returns the reflection coeffs
[k1,k2,beta]=tf2cl(b,a); % Reconstruct the original filter
% plus the power complementary one.
[num,den,numpc]=cl2tf(k1,k2,beta);
[h,w]=freqz(num,den); hpc = freqz(numpc,den);
% and the power complementary one.
subplot(211);
plot(w./pi,20*log10(abs(h)), 'k'); hold on; grid on;
plot(w./pi,20*log10(abs(hpc)), 'b');
xlabel('Normalized Frequency (x \pi radians/sample)');
ylabel('dB');
legend('Original Filter', 'Power Complementary Filter', ...
      'Location', 'best');
subplot(212);
plot(w./pi,unwrap(angle(h)), 'k'); hold on; grid on;
xlabel('Normalized Frequency (x \pi radians/sample)');
ylabel('Phase (radians)');
plot(w./pi,unwrap(angle(hpc)), 'b');
```



## See Also

[tf2c1](#) | [tf2ca](#) | [ca2tf](#) | [tf2latc](#) | [latc2tf](#) | [iirpowcomp](#)

<b>Purpose</b>	Coefficients for filters
<b>Syntax</b>	<pre>s = coeffs(ha) s = coeffs(hd) s = coeffs(hm) s = coeffs(hs) s = coeffs(hs,Name,Value)</pre>
<b>Description</b>	<p><code>s = coeffs(ha)</code> returns a structure containing the coefficients of the adaptive filter <code>ha</code>.</p> <p><code>s = coeffs(hd)</code> returns a structure containing the coefficients of the discrete-time filter <code>hd</code>.</p> <p><code>s = coeffs(hm)</code> returns a structure containing the coefficients of the multirate filter <code>hm</code>.</p> <p><code>s = coeffs(hs)</code> returns filter coefficients for the filter System object <code>hs</code>.</p> <p><code>s = coeffs(hs,Name,Value)</code> returns filter coefficients for the filter System object <code>hs</code> with additional options specified by one or more <code>Name,Value</code> pair arguments.</p>
<b>Input Arguments</b>	<p><b>ha</b> Adaptive <code>adaptfilt</code> filter object.</p> <p><b>hd</b> Discrete-time <code>dfilt</code> filter object.</p> <p><b>hm</b> Multirate <code>mfilt</code> filter object. CIC-based filters do not have coefficients, so the function does not support CIC filter structures such as <code>mfilt.cicdecim</code>.</p> <p><b>hs</b></p>

Filter System object. The function supports the following filter structures.

- `dsp.FIRFilter`
- `dsp.BiquadFilter`
- `dsp.FIRInterpolator`
- `dsp.FIRDecimator`
- `dsp.FIRRateConverter`

### **Name-Value Pair Arguments**

Specify optional comma-separated pairs of `Name`, `Value` arguments, where `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes ( `' '`). You can specify several name and value pair arguments in any order as `Name1,Value1,...,NameN,ValueN`.

### **Arithmetic**

`'double' | 'single' | 'fixed'`

For filter System object inputs only, specify the arithmetic used during analysis. When you specify `'double'` or `'single'`, the function performs double- or single-precision analysis. When you specify `'fixed'`, the arithmetic changes depending on the setting of the `CoefficientDataType` property and whether the System object is locked or unlocked.

**Details for Fixed-Point Arithmetic**

<b>System Object State</b>	<b>Coefficient Data Type</b>	<b>Rule</b>
Unlocked	'Same as input'	The function assumes that the coefficient data type is signed, 16 bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Unlocked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.
Locked	'Same as input'	When the input data type is 'double' or 'fixed', the function assumes that the coefficient data type is signed, 16-bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Locked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.

When you do not specify the arithmetic, the function uses double-precision arithmetic if the filter System object is in an unlocked state. If the System object is locked, the function performs analysis based on the locked input data type.

## Output Arguments


**s**

Structure with a single field, `Numerator`, containing filter coefficients. For adaptive filters, `s` contains the instantaneous frequency response available at the time you use the function.

## Examples

`coeffs` works the same way for all filters. This example uses a multirate filter `hm` to demonstrate the function.

```
hm=mfilt.firdecim(3);  
s=coeffs(hm);  
stem(s.Numerator)
```



The filter coefficients may be extracted by typing `s.Numerator` at the command prompt.

**See Also**

`adaptfilt` | `freqz` | `grpdelay` | `impz` | `info` | `phasez` | `stepz` |  
`zerophase` | `zplane`

# coeread

---

**Purpose** Read Xilinx COE file

**Syntax** `hd = coeread(filename)`

**Description** `hd = coeread(filename)` extracts the Distributed Arithmetic FIR filter coefficients defined in the XILINX CORE Generator .COE file specified by `filename`. It returns a `dfilt` object, the fixed-point filter `hd`. If you do not provide the file type extension `.coe` with the `filename`, the function assumes the `.coe` extension.

**See Also** `coewrite` | `dfilt` | `dfilt.dffir`

**Purpose**

Write Xilinx COE file

**Syntax**

```
coewrite(hd)
coewrite(hd,radix)
coewrite(...,filename)
```

**Description**

`coewrite(hd)` writes a XILINX Distributed Arithmetic FIR filter coefficient .COE file which can be loaded into the XILINX CORE Generator. The coefficients are extracted from the fixed-point `dfilt` object `hd`. Your fixed-point filter must be a direct form FIR structure `dfilt` object with one section and whose `Arithmetic` property is set to `fixed`. You cannot export single-precision, double-precision, or floating-point filters as .coe files, nor multiple-section filters. To enable you to provide a name for the file, `coewrite` displays a dialog box where you fill in the file name. If you do not specify the name of the output file, the default file name is `untitled.coe`.

`coewrite(hd,radix)` indicates the radix (number base) used to specify the FIR filter coefficients. Valid `radix` values are 2 for binary, 10 for decimal, and 16 for hexadecimal (default).

`coewrite(...,filename)` writes a XILINX.COE file to `filename`. If you omit the file extension, `coewrite` adds the .coe extension to the name of the file.

The `coewrite` function always generates the XILINX.COE file in your current folder. To use this function, you must have write permission in your current folder.

**Examples**

`coewrite` generates an ASCII text file that contains the filter coefficients in a format the XILINX CORE Generator can read and load. In this example, you create a 30th-order fixed-point filter and generate the .coe file that includes the filter coefficients as well as associated information about the filter.

```
b = firceqip(30,0.4,[0.05 0.03]); hq = dfilt.dffir(b);
set(hq,'arithmetic','fixed'); coewrite(hq,10,'mycoefile');
```

## coewrite

---

The `coewrite` function generates the output file, `mycoefile.coe`, in your current folder. The `.coe` file contains the radix, coefficient width, and filter coefficients. The file reports the filter coefficients in column-major order. The radix, coefficient width, and filter coefficients are the minimum set of data needed in a `.coe` file.

### See Also

`coeread` | `dfilt` | `dfilt.dffir`

## Purpose

Constrain coefficient wordlength

## Syntax

```
Hq = constraincoeffwl(Hd,wordlength)
Hq = constraincoeffwl(Hd,wordlength,'Ntrials',N)
Hq = constraincoeffwl(Hd,wordlength,...,'NoiseShaping',
    NSFlag)
Hq = constraincoeffwl(Hd,wordlength,...,'Apasstol',Apasstol)
Hq = constraincoeffwl(Hd,wordlength,...,'Astoptol',Astoptol)
```

## Description

`Hq = constraincoeffwl(Hd,wordlength)` returns a fixed-point filter `Hq` meeting the design specifications of the single-stage or multistage FIR filter object `Hd` with a wordlength of at most `wordlength` bits. For multistage filters, `wordlength` can either be a scalar or vector. If `wordlength` is a scalar, the same `wordlength` is used for all stages. If `wordlength` is a vector, each stage uses the corresponding element in the vector. The vector length must equal the number of stages. `Hd` must be generated using `fdesign` and `design`. `constraincoeffwl` uses a stochastic noise-shaping procedure by default to minimize the wordlength. To obtain repeatable results on successive function calls, initialize the uniform random number generator `rand`

`Hq = constraincoeffwl(Hd,wordlength,'Ntrials',N)` specifies the number of Monte Carlo trials to use. `Hq` is first filter among the trials to meet the specifications in `Hd` with a wordlength of at most `wordlength`.

`Hq = constraincoeffwl(Hd,wordlength,...,'NoiseShaping',NSFlag)` enables or disables the stochastic noise-shaping procedure in the constraint of the wordlength. By default `NSFlag` is true. Setting `NSFlag` to false constrains the wordlength without using noise-shaping.

`Hq = constraincoeffwl(Hd,wordlength,...,'Apasstol',Apasstol)` specifies the passband ripple tolerance in dB. `'Apasstol'` defaults to `1e-4`.

`Hq = constraincoeffwl(Hd,wordlength,...,'Astoptol',Astoptol)` specifies the stopband tolerance in dB. `'Astoptol'` defaults to `1e-2`


# constraincoeffwl

You must have the Fixed-Point Toolbox software installed to use this function.

## Examples

Design fixed-point filter with a wordlength of at most 11 bits:

```
Hf = fdesign.lowpass('Fp,Fst,Ap,Ast',.4,.5,1,60);  
Hd = design(Hf,'equiripple'); % 43 coefficients  
Hq = constraincoeffwl(Hd,11); % 45 11-bit coefficients  
hfvt = fvtool(Hd,Hq,'showreference','off');  
legend(hfvt,'Floating-point Filter','Fixed-point Filter');
```



## See Also

[design](#) | [fdesign](#) | [maximizestopband](#) | [minimizecoeffwl](#) | [measure](#)  
| [rand](#)

## Tutorials

- “Fixed-Point Data Types”

**Purpose** Convert filter structure of discrete-time or multirate filter

**Syntax** `hq = convert(hq,newstruct)`  
`hm = convert(hm,newstruct)`

**Description** **Discrete-Time Filters**

`hq = convert(hq,newstruct)` returns a quantized filter whose structure has been transformed to the filter structure specified by string `newstruct`. You can enter any one of the following quantized filter structures:

- 'antisymmetricfir': Antisymmetric finite impulse response (FIR)
- 'df1': Direct form I
- 'df1t': Direct form I transposed
- 'df1sos': Direct-Form I, Second-Order Sections
- 'df1tsos': Direct-Form I Transposed, Second-Order Sections
- 'df2': Direct form II
- 'df2t': Direct form II transposed. Default filter structure
- 'df2sos': Direct-Form II, Second-Order Sections
- 'df2tsos': Direct-Form II Transposed, Second-Order Sections
- 'dffir': FIR
- 'dffirt': Direct form FIR transposed
- 'latcallpass': Lattice allpass
- 'latticeca': Lattice coupled-allpass
- 'latticecapc': Lattice coupled-allpass power-complementary
- 'latticear': Lattice autoregressive (AR)
- 'latticemamax': Lattice moving average (MA) maximum phase
- 'latticemamin': Lattice moving average (MA) minimum phase

# convert

---

- 'latticearma': Lattice ARMA
- 'statespace': Single-input/single-output state-space
- 'symmetricfir': Symmetric FIR. Even and odd forms

All filters can be converted to the following structures:

- 'df1': Direct form I
- 'df1t': Direct form I transposed
- 'df1sos': Direct-Form I, Second-Order Sections
- 'df1tsos': Direct-Form I Transposed, Second-Order Sections
- 'df2': Direct form II
- 'df2t': Direct form II transposed. Default filter structure
- 'df2sos': Direct-Form II, Second-Order Sections
- 'df2tsos': Direct-Form II Transposed, Second-Order Sections
- 'statespace': Single-input/single-output state-space
- 'symmetricfir': Symmetric FIR. Even and odd forms

For the following filter classes, you can specify other conversions as well:

- Minimum phase FIR filters can be converted to `latticeamin`
- Maximum phase FIR filters can be converted to `latticeamax`
- Allpass filters can be converted to `latcallpass`

`convert` generates an error when you specify a conversion that is not possible.

## Multirate Filters

`hm = convert(hm,newstruct)` returns a multirate filter whose structure has been transformed to the filter structure specified by string `newstruct`. You can enter any one of the following multirate filter structures, defined by the strings shown, for `newstruct`:

## Cascaded Integrator-Comb Structure

- `cicdecim` — CIC-based decimator
- `cicinterp` — CIC-based interpolator

### FIR Structures

- `firdecim` — FIR decimator
- `firtdecim` — transposed FIR decimator
- `firfracdecim` — FIR fractional decimator
- `firinterp` — FIR interpolator
- `firfracinterp` — FIR fractional interpolator
- `firsrc` — FIR sample rate change filter
- `firholdinterp` — FIR interpolator that uses hold interpolation between input samples
- `firlinearinterp` — FIR interpolator that uses linear interpolation between input samples
- `fftfirinterp` — FFT-based FIR interpolator

You cannot convert between the FIR and CIC structures.

## Examples

```
[b,a]=ellip(5,3,40,.7); hq = dfilt.df2t(b,a);  
hq2 = convert(hq,'df1');
```

For an example of changing the structure of a multirate filter, try the following conversion from a CIC interpolator to a CIC interpolator with zero latency.

```
hm = mfilt.cicinterp(2,2,3,8,8);
```

# convert

---

---

**Note** The above example will generate a warning:

Warning: Using reference filter for structure conversion.  
Fixed-point attributes will not be converted.

Since CIC interpolators only use fixed-point arithmetic, the user may disregard this warning. The fixed-point structure will not be lost on conversion.

---

## See Also

`mfilt` | `dfilt`

**Purpose**

Estimate cost of discrete-time or multirate filter

**Syntax**

```
c = cost(hd)
c = cost(hm)
c = cost(hs)
c = cost(hs,Name,Value)
```

**Description**

`c = cost(hd)` returns a cost estimate `c` for the discrete-time filter `hd`.  
`c = cost(hm)` return a cost estimate `c` for the multirate filter `hm`.  
`c = cost(hs)` returns a cost estimate `c` for the filter System object `hs`.  
`c = cost(hs,Name,Value)` returns a cost estimate `c` for the filter System object `hs` with additional options specified by one or more `Name,Value` pair arguments.

**Input Arguments****hd**

Discrete-time `dfilt` filter object.

**hm**

Multirate `mfilt` filter object.

**hs**

Filter System object. The function supports the following filter structures.

- `dsp.FIRFilter`
- `dsp.BiquadFilter`
- `dsp.FIRInterpolator`
- `dsp.CICInterpolator`
- `dsp.FIRDecimator`
- `dsp.CICDecimator`
- `dsp.FIRRateConverter`

### **Name-Value Pair Arguments**

Specify optional comma-separated pairs of **Name**, **Value** arguments, where **Name** is the argument name and **Value** is the corresponding value. **Name** must appear inside single quotes ( ' '). You can specify several name and value pair arguments in any order as **Name1,Value1,...,NameN,ValueN**.

### **Arithmetic**

`'double' | 'single' | 'fixed'`

For filter System object inputs only, specify the arithmetic used during analysis. When you specify 'double' or 'single', the function performs double- or single-precision analysis. When you specify 'fixed', the arithmetic changes depending on the setting of the **CoefficientDataType** property and whether the System object is locked or unlocked.

### **Details for Fixed-Point Arithmetic**

<b>System Object State</b>	<b>Coefficient Data Type</b>	<b>Rule</b>
Unlocked	'Same as input'	The function assumes that the coefficient data type is signed, 16 bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Unlocked	'Custom'	The function performs fixed-point analysis based on the setting of the <b>CustomCoefficientsDataType</b> property.

System Object State	Coefficient Data Type	Rule
Locked	'Same as input'	When the input data type is 'double' or 'fixed', the function assumes that the coefficient data type is signed, 16-bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Locked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.

When you do not specify the arithmetic for non-CIC structures, the function uses double-precision arithmetic if the filter System object is in an unlocked state. If the System object is locked, the function performs analysis based on the locked input data type. CIC structures only support fixed-point arithmetic.

## Output Arguments

**c**

Cost estimate. **c** has the following fields.

## cost

---

Estimated Value	Field Name	Description
Number of Multiplications	nmult	Number of multiplications during the filter run. nmult ignores multiplications by -1, 0, and 1 in the total multiple.
Number of Additions	nadd	Number of additions during the filter run.
Number of States	nstates	Number of states the filter uses.
Multiplications per Input Sample	multperinputsample	Number of multiplication operations performed for each input sample
Additions per Input Sample	addperinputsample	Number of addition operations performed for each input sample

### Examples

These examples show you the cost method applied to `dfilt` and `mfilt` objects.

```
hd = design(fdesign.lowpass);  
c = cost(hd);
```

When you are using a multirate filter object, cost works the same way.

```
d = fdesign.decimator(4,'cic');  
hm = design(d,'multisection');
```

### See Also

`qreport`

**Purpose**

Vector of SOS filters for cumulative sections

**Syntax**

```
h = cumsec(hd)
h = cumsec(hd,indices)
h = cumsec(hd,indices,secondary)
cumsec(hd,...)
h = cumsec(hs)
h = cumsec(hs,Name,Value)
```

**Description**

`h = cumsec(hd)` returns a vector `h` of SOS filter objects with the cumulative sections. Each element in `h` is a filter with the structure of the original filter. The first element is the first filter section of `hd`. The second element of `h` is a filter that represents the combination of the first and second sections of `hd`. The third element of `h` is a filter which combines sections 1, 2, and 3 of `hd`. This pattern continues until the final element of `h` contains all the sections of `hd` and should be identical to `hd`.

`h = cumsec(hd,indices)` returns a vector `h` of SOS filter objects whose indices into the original filter are in the vector `indices`.

`h = cumsec(hd,indices,secondary)` uses the secondary scaling points `secondary` in the sections to determine where the sections should be split.

`cumsec(hd,...)` uses `FVTool` to plot the magnitude response of the cumulative sections.

`h = cumsec(hs)` returns the cumulative sections of the `dsp.BiquadFilter` filter System object `hs`. You can also use the optional input arguments `indices` and `secondary` with this syntax. You can also omit the output argument `h` to use `FVTool` to plot the magnitude response of the cumulative sections.

`h = cumsec(hs,Name,Value)` returns the cumulative sections of the filter System object `hs` with additional options specified by one or more `Name,Value` pair arguments.

## Input Arguments

### **hd**

Discrete-time `dfilt.df1sos`, `dfilt.df2tsos`, `dfilt.df2sos`, or `dfilt.df1tsosfilter` object.

### **hs**

`dsp.BiquadFilter` filter System object.

### **indices**

Filter indices. Use `indices` to specify the filter sections `cumsec` uses to compute the cumulative responses.

### **secondary**

This option applies only when `hd` is a `df2sos` and `df1tsos` filter. For these second-order section structures, the `secondary` scaling points refer to the scaling locations between the recursive and the nonrecursive parts of the section (the "middle" of the section). Argument `secondary` accepts either `true` or `false`. By default, `secondary` is `false`.

## **Name-Value Pair Arguments**

Specify optional comma-separated pairs of `Name`, `Value` arguments, where `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes ( ' '). You can specify several name and value pair arguments in any order as `Name1,Value1,...,NameN,ValueN`.

### **Arithmetic**

`'double'` | `'single'` | `'fixed'`

For filter System object inputs only, specify the arithmetic used during analysis. When you specify `'double'` or `'single'`, the function performs double- or single-precision analysis. When you specify `'fixed'`, the arithmetic changes depending on the setting of the `CoefficientDataType` property and whether the System object is locked or unlocked.

**Details for Fixed-Point Arithmetic**


<b>System Object State</b>	<b>Coefficient Data Type</b>	<b>Rule</b>
Unlocked	'Same as input'	The function assumes that the coefficient data type is signed, 16 bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Unlocked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.
Locked	'Same as input'	When the input data type is 'double' or 'fixed', the function assumes that the coefficient data type is signed, 16-bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Locked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.

When you do not specify the arithmetic, the function uses double-precision arithmetic if the filter System object is in an unlocked state. If the System object is locked, the function performs analysis based on the locked input data type.

## Examples

To demonstrate how cumsec works, this example plots the relative responses of the sections of a sixth-order filter SOS filter with three sections. Each curve adds one more section to form the filter response.

```
hs = fdesign.lowpass('n,fc',6,.4); hd = butter(hs);
h = cumsec(hd); hfvt = fvtool(h);
legend(hfvt,'First Section','First Two Sections','Overall Filter');
```



## See Also

scale | scalecheck

**Purpose** Undo filter coefficient and gain changes caused by `normalize`

**Syntax** `denormalize(hq)`

**Description** `denormalize(hq)` reverses the coefficient changes you make when you use `normalize` with `hq`. The filter coefficients do not change if you call `denormalize(hq)` before you use `normalize(hq)`. Calling `denormalize` more than once on a filter does not change the coefficients after the first `denormalize` call.

**Examples** Make a quantized filter `hq` and normalize the filter coefficients. After normalizing the coefficients, restore them to their original values by reversing the effects of the `normalize` function.

```
d=fdesign.highpass('n,F3dB',14,0.45);
hd =design(d,'butter');
hd.arithmetic='fixed';
normalize(hd)
NormSOSMatrix = hd.sosMatrix;
denormalize(hd)
eqSOSMatrices = isequal(NormSOSMatrix,hd.sosMatrix);
% returns a 0
```

**See Also** `normalize`

# design

---

**Purpose** Apply design method to filter specification object

**Syntax**

```
H = design(D)
H = design(D,METHOD)
H = design(D,METHOD,PARAM1,VALUE1,PARAM2,VALUE2,...)
H = design(D,METHOD,OPTS)
Hs = design(D,...,'SystemObject',sysobjflag)
```

**Description** H = design(D) uses the filter specifications object D to generate a filter H. When you do not provide a design method as an input argument, design uses a default design method. Use designmethods(D,'default') to see the default design method for your filter specifications object.

H = design(D,METHOD) forces the design method specified by the string METHOD. METHOD must be one of the strings returned by designmethods. Use designmethods(D,'default') to determine which algorithm is used by default.

The design method you provide as the designmethod input argument must be one of the methods returned by

designmethods(d)

To help you design filters more quickly, the input argument METHOD accepts a variety of special keywords that force design to behave in different ways. The following table presents the keywords you can use for METHOD and how design responds to the keyword.

Designmethod Keyword	Description of the design Response
'FIR'	Forces design to produce an FIR filter. When no FIR design method exists for object D, design returns an error.
'IIR'	Forces design to produce an IIR filter. When no IIR design method exists for object D, design returns an error.

Designmethod Keyword	Description of the design Response
'ALLFIR'	Produces filters from every applicable FIR design method for the specifications in D, one filter for each design method. As a result, <code>design</code> returns multiple filters in the output object.
'ALLIIR'	Produces filters from every applicable IIR design method for the specifications in D, one filter for each design method. As a result, <code>design</code> returns multiple filters in the output object.
'ALL'	Designs filters using all applicable design methods for the specifications object D. As a result, <code>design</code> returns multiple filters, one for each design method. <code>design</code> uses the design methods in the order that <code>designmethods(D)</code> returns them.

Keywords are not case sensitive

When `design` returns multiple filters in the output object, use indexing to see the individual filters. For example, to see the third filter in H, enter

```
H(3)
```

`H = design(D,METHOD,PARAM1,VALUE1,PARAM2,VALUE2,...)` specifies design-method options. Use `help(D,METHOD)` for complete information on which design-method-specific options are available. You can also use `designopts(D,METHOD)` for a less-detailed listing of the design-method-specific options.

`H = design(D,METHOD,OPTS)` specifies design-method options using the structure `OPTS`. `OPTS` is usually obtained from `designopts` and then specified as an input to `design`. Use `help(D,METHOD)` for more information on optional inputs.

`Hs = design(D,...,'SystemObject',sysobjflag)` uses the filter specifications object D to generate a filter System object `Hs` when

`sysobjflag` is true. To generate System objects, you must have the DSP System Toolbox product installed. When `sysobjflag` is false, the function generates a `dfilt` or `mfilt` object `H`, as described previously. Design methods and design options for filter System objects are not necessarily the same as those for `dfilt` and `mfilt` objects. To check design methods for System objects, use `designmethods` with the `'SystemObject'`, `sysobjflag` syntax.

If you are specifying design-method-specific options using `OPTS`, you can also set `OPTS.SystemObject` to true instead of calling `design` with the `'SystemObject'`, `sysobjflag` syntax.

## Examples

Design an FIR equiripple lowpass filter. The passband edge frequency is  $0.2\pi$  radians/sample, and the stopband edge frequency is  $0.25\pi$  radians/sample. The passband ripple is 0.5 dB, and the stopband attenuation is 40 dB.

```
D = fdesign.lowpass('Fp,Fst,Ap,Ast',0.2,0.25,0.5,40);
H = design(D); % Uses the default equiripple method.
```

If you have the DSP System Toolbox software installed, you can design a minimum-phase FIR equiripple filter. Design a minimum-phase filter and compare the pole-zero plots of the original and minimum-phase designs.

```
Hmin = design(D,'equiripple','MinPhase',true);
hfvt = fvtool([H Hmin],'analysis','polezero');
legend(hfvt,'Original Design','Minimum Phase Design');
```

Design a Butterworth lowpass filter. The passband edge frequency is  $0.2\pi$  radians/sample, and the stopband edge frequency is  $0.25\pi$  radians/sample. The passband ripple is 0.5 dB, and the stopband attenuation is 40 dB. Obtain help on the design options specific to the Butterworth design method. Design the filter with the `"MatchExactly"` option set to `'Passband'`.

```
D = fdesign.lowpass('Fp,Fst,Ap,Ast',0.2,0.25,0.5,40);
% Query design-method-specific options
```

```
help(D,'butter')
% Match passband exactly
H = design(D,'butter','MatchExactly','passband');
```

If you have the DSP System Toolbox software, you can specify the  $P$ -th norm scaling on the second-order sections. Use L-infinity norm scaling in the time domain.

```
H = design(D,'butter','MatchExactly','passband','SOSScaleNorm','linf');
```

If you have the DSP System Toolbox software, you can create a filter System object.

```
Hs = design(D,'SystemObject',true);
```

## See Also

[designmethods](#) | [designopts](#)

# designmethods

---

<b>Purpose</b>	Methods available for designing filter from specification object
<b>Syntax</b>	<pre>M = designmethods(D) M = designmethods(D,'default') M = designmethods(D,TYPE) M = designmethods(D,'full') Ms = designmethods(D,...,'SystemObject',<i>sysobjflag</i>)</pre>
<b>Description</b>	<p><code>M = designmethods(D)</code> returns the available design methods for the filter specification object, <code>D</code>, and the current value of the <code>Specification</code> property.</p> <p><code>M = designmethods(D,'default')</code> returns the default design method for the filter specification object <code>D</code> and the current value of the <code>Specification</code> property.</p> <p><code>M = designmethods(D,TYPE)</code> returns either the <code>TYPE</code> design methods that apply to <code>D</code>. <code>TYPE</code> can be either <code>'FIR'</code> or <code>'IIR'</code>.</p> <p><code>M = designmethods(D,'full')</code> returns the full name for each of the available design methods. For example, <code>designmethods</code> with the <code>'full'</code> argument returns <code>Butterworth</code> for the <code>butter</code> method.</p> <p><code>Ms = designmethods(D,...,'SystemObject',<i>sysobjflag</i>)</code> returns the available design methods for designing filter System objects when <i>sysobjflag</i> is true. To use System objects, you must have the DSP System Toolbox product installed. When <i>sysobjflag</i> is false, the function checks methods for creating <code>dfilt</code> and <code>mfilt</code> objects, as described previously. Design methods and design options for filter System objects are not necessarily the same as those for <code>dfilt</code> and <code>mfilt</code> objects.</p>
<b>Examples</b>	<p>Construct a lowpass filter specification object and determine the valid design methods. Obtain detailed command line help on the Chebyshev type I design method.</p> <pre>D =fdesign.lowpass('Fp,Fst,Ap,Ast',500,600,0.5,60,1e4); M = designmethods(D) help(D,M{2})</pre>

The last line of the example is equivalent to `help(D, 'cheby1')`.

If you have DSP System Toolbox software installed, use the `'SystemObject'`, *sysobjflag* syntax to return design methods for a filter System object:

```
Ms = designmethods(D, 'SystemObject', true);
```

### See Also

[design](#) | [designopts](#) | [fdesign](#)

# designopts

---

**Purpose** Valid input arguments and values for specification object and method

**Syntax** `OPTS = designopts(D,METHOD)`

**Description** `OPTS = designopts(D,METHOD)` returns a structure array with the default design parameters used by the design method `METHOD`. `METHOD` must be one of the strings returned by `designmethods`.

Use `help(D,METHOD)` to get a description of the design parameters.

If you have DSP System Toolbox software installed, `OPTS` has the `SystemObject` property if at least one of the structures available for that design method is supported by System objects. However, not all structures for that design method are supported by System objects.

**Examples** Create a lowpass filter with a numerator and denominator order of 10 and a 3-dB frequency of  $0.2\pi$  radians/sample. Obtain the default design parameters for a Butterworth design, and test whether the filter structure is a direct-form II biquad.

```
D = fdesign.lowpass('Nb,Na,F3dB',10,10,0.2);
OPTS = designopts(D,'butter');
if (OPTS.FilterStructure == 'df2sos')
    fprintf('The default filter structure is Direct-Form II\n');
    fprintf('with second-order sections.\n');
end
```

If you have DSP System Toolbox software installed, `OPTS` has the `SystemObject` property.

**See Also** `design` | `designmethods` | `fdesign` | `validstructures`

**Purpose** Discrete-time filter

**Syntax**

```
hd = dfilt.structure(input1,...)
hd = [dfilt.structure(input1,...), dfilt.structure(input1,
...),...]
hd = design(d,'designmethod')
```

**Description** `hd = dfilt.structure(input1,...)` returns a discrete-time filter, `hd`, of type *structure*. Each *structure* takes one or more inputs. When you specify a *dfilt.structure* with no inputs, a default filter is created.

---

**Note** You must use a *structure* with `dfilt`.

---

`hd = [dfilt.structure(input1,...), dfilt.structure(input1,...),...]` returns a vector containing `dfilt` filters.

### Structures

Structures for `dfilt.structure` specify the type of filter structure. Available types of structures for `dfilt` are shown below.

<b>dfilt.structure</b>	<b>Description</b>	<b>Coefficient Mapping Support in <code>realizemdl</code></b>
<code>dfilt.allpass</code>	Allpass filter	Supported
<code>dfilt.cascadeallpass</code>	Cascade of allpass filter sections	Supported
<code>dfilt.cascadewdfallpass</code>	Cascade of allpass wave digital filters	Supported
<code>dfilt.delay</code>	Delay	Not supported
<code>dfilt.df1</code>	Direct-form I	Supported
<code>dfilt.df1sos</code>	Direct-form I, second-order sections	Supported

<b>dfilt.structure</b>	<b>Description</b>	<b>Coefficient Mapping Support in realizedmdl</b>
dfilt.df1t	Direct-form I transposed	Supported
dfilt.df1tsos	Direct-form I transposed, second-order sections	Supported
dfilt.df2	Direct-form II	Supported
dfilt.df2sos	Direct-form II, second-order sections	Supported
dfilt.df2t	Direct-form II transposed	Supported
dfilt.df2tsos	Direct-form II transposed, second-order sections	Supported
dfilt.dffir	Direct-form FIR	Supported
dfilt.dffirt	Direct-form FIR transposed	Supported
dfilt.dfsymfir	Direct-form symmetric FIR	Supported
dfilt.dfasymfir	Direct-form antisymmetric FIR	Supported
dfilt.farrowfd	Generic fractional delay Farrow filter	Supported
dfilt.farrowlinearfd	Linear fractional delay Farrow filter	Not supported
dfilt.ffsetfir	Overlap-add FIR	Not supported
dfilt.latticeallpass	Lattice allpass	Supported
dfilt.latticear	Lattice autoregressive (AR)	Supported
dfilt.latticearma	Lattice autoregressive moving-average (ARMA)	Supported
dfilt.latticemamax	Lattice moving-average (MA) for maximum phase	Supported
dfilt.latticemamin	Lattice moving-average (MA) for minimum phase	Supported

<b>dfilt.structure</b>	<b>Description</b>	<b>Coefficient Mapping Support in realizemdl</b>
<code>dfilt.calattice</code>	Coupled, allpass lattice	Supported
<code>dfilt.calatticepc</code>	Coupled, allpass lattice with power complementary output	Supported
<code>dfilt.statespace</code>	State-space	Supported
<code>dfilt.scalar</code>	Scalar gain object	Supported
<code>dfilt.wdfallpass</code>	Allpass wave digital filter object	Supported
<code>dfilt.cascade</code>	Filters arranged in series	Supported
<code>dfilt.parallel</code>	Filters arranged in parallel	Supported

For more information on each structure, refer to its reference page.

`hd = design(d, 'designmethod')` returns the `dfilt` object `hd` resulting from the filter specification object `d` and the design method you specify in *designmethod*. When you omit the *designmethod* argument, `design` uses the default design method to construct a filter from the object `d`.

With this syntax, you design filters by:

- 1** Specifying the filter specifications, such as the response shape (perhaps `highpass`) and details (passband edges and attenuation).
- 2** Selecting a method (such as `equiripple`) to design the filter.
- 3** Applying the method to the specifications object with `design(d, 'designmethod')`.

Using the specification-based technique can be more effective than the coefficient-based filter design techniques.

### **Design Methods for Design Syntax**

When you use the `hd = design(d, 'designmethod')` syntax, you have a range of design methods available depending on `d`, the filter

specification object. The next table lists all of the design methods in the toolbox.

<b>Design Method String</b>	<b>Filter Design Result</b>
butter	Butterworth IIR
cheby1	Chebyshev Type I IIR
cheby2	Chebyshev Type II IIR
ellip	Elliptic IIR
equiripple	Equiripple with the same ripple in the pass and stopbands
firls	Least-squares FIR
fregsamp	Frequency-Sampled FIR
ifir	Interpolated FIR
iirlpnorm	Least Pth norm IIR
iirls	Least-Squares IIR
kaiserwin	Kaiser-windowed FIR
lagrange	Fractional delay filter
multistage	Multistage FIR
window	Windowed FIR

As the specifications object `d` changes, the available methods for designing filters from `d` also change. For instance, if `d` is a lowpass filter with the default specification `'Fp,Fst,Ap,Ast'`, the applicable methods are:

```
% Create an object to design a lowpass filter.
d=fdesign.lowpass;
designmethods(d) % What design methods apply to object d?
```

---

If you change the specification string to 'N,F3dB', the available design methods change:

```
d=fdesign.lowpass('N,F3dB');  
designmethods(d)
```

## Analysis Methods

Methods provide ways of performing functions directly on your `dfilt` object without having to specify the filter parameters again. You can apply these methods directly on the variable you assigned to your `dfilt` object.

For example, if you create a `dfilt` object, `hd`, you can check whether it has linear phase with `islinphase(hd)`, view its frequency response plot with `fvtool(hd)`, or obtain its frequency response values with `h = freqz(hd)`. You can use all of the methods described here in this way.

---

**Note** If your variable `hd` is a 1-D array of `dfilt` filters, the method is applied to each object in the array. Only `freqz`, `grpdelay`, `impz`, `is*`, `order`, and `stepz` methods can be applied to arrays. The `zplane` method can be applied to an array only if `zplane` is used without outputs.

---

Some of the methods listed here have the same name as functions in Signal Processing Toolbox software. They behave similarly.

<b>Method</b>	<b>Description</b>
<code>addstage</code>	Adds a stage to a <code>cascade</code> or <code>parallel</code> object, where a stage is a separate, modular filter. Refer to <code>dfilt.cascade</code> and <code>dfilt.parallel</code> .
<code>block</code>	<p><code>block(hd)</code> creates a block of the <code>dfilt</code> object. The <code>block</code> method can specify these properties and values:</p> <p>'Destination' indicates where to place the block. 'Current' places the block in the current Simulink model. 'New' creates a new model. Default value is 'Current'.</p> <p>'Blockname' assigns the entered string to the block name. Default name is 'Filter'.</p> <p>'OverwriteBlock' indicates whether to overwrite the block generated by the <code>block</code> method ('on') and defined by <code>Blockname</code>. Default is 'off'.</p> <p>'MapStates' specifies initial conditions in the block ('on'). Default is 'off'. Refer to "Using Filter States" in Signal Processing Toolbox documentation.</p>
<code>cascade</code>	Returns the series combination of two <code>dfilt</code> objects. Refer to <code>dfilt.cascade</code> .
<code>coeffs</code>	Returns the filter coefficients in a structure containing fields that use the same property names as those in the original <code>dfilt</code> .
<code>convert</code>	Converts a <code>dfilt</code> object from one filter structure, to another filter structure.

Method	Description
<code>fcfwrite</code>	<p>Writes a filter coefficient ASCII file. The file can contain a single filter or a vector of objects. The file can contain multirate filters (<code>mfilt</code>) or adaptive filters (<code>adaptfilt</code>). The default file name is <code>untitled.fcf</code>.</p> <p><code>fcfwrite(hd,filename)</code> writes to a disk file named <code>filename</code> in the current working folder. The <code>.fcf</code> extension is added automatically.</p> <p><code>fcfwrite(...,fmt)</code> writes the coefficients in the format <code>fmt</code>, where valid <code>fmt</code> strings are:</p> <ul style="list-style-type: none"> <li>'hex' for hexadecimal</li> <li>'dec' for decimal</li> <li>'bin' for binary representation</li> </ul>
<code>fftcoeffs</code>	Returns the frequency-domain coefficients used when filtering with a <code>dfilt.fftfir</code>
<code>filter</code>	Performs filtering using the <code>dfilt</code> object.
<code>firtype</code>	Returns the type (1-4) of a linear phase FIR filter.
<code>freqz</code>	Plots the frequency response in <code>fvtool</code> . Unlike the <code>freqz</code> function, this <code>dfilt</code> <code>freqz</code> method has a default length of 8192.
<code>grpdelay</code>	Plots the group delay in <code>fvtool</code> .
<code>impz</code>	Plots the impulse response in <code>fvtool</code> .
<code>impzlength</code>	Returns the length of the impulse response.
<code>info</code>	Displays <code>dfilt</code> information, such as filter structure, length, stability, linear phase, and, when appropriate, lattice and ladder length.

<b>Method</b>	<b>Description</b>
<code>isallpass</code>	Returns a logical 1 (i.e., true) if the <code>dfilt</code> object in an allpass filter or a logical 0 (i.e., false) if it is not.
<code>iscascade</code>	Returns a logical 1 if the <code>dfilt</code> object is cascaded or a logical 0 if it is not.
<code>isfir</code>	Returns a logical 1 if the <code>dfilt</code> object has finite impulse response (FIR) or a logical 0 if it does not.
<code>islinphase</code>	Returns a logical 1 if the <code>dfilt</code> object is linear phase or a logical 0 if it is not.
<code>ismaxphase</code>	Returns a logical 1 if the <code>dfilt</code> object is maximum-phase or a logical 0 if it is not.
<code>isminphase</code>	Returns a logical 1 if the <code>dfilt</code> object is minimum-phase or a logical 0 if it is not.
<code>isparallel</code>	Returns a logical 1 if the <code>dfilt</code> object has parallel stages or a logical 0 if it does not.
<code>isreal</code>	Returns a logical 1 if the <code>dfilt</code> object has real-valued coefficients or a logical 0 if it does not.
<code>isscalar</code>	Returns a logical 1 if the <code>dfilt</code> object is a scalar or a logical 0 if it is not scalar.
<code>issos</code>	Returns a logical 1 if the <code>dfilt</code> object has second-order sections or a logical 0 if it does not.
<code>isstable</code>	Returns a logical 1 if the <code>dfilt</code> object is stable or a logical 0 if it are not.

Method	Description
nsections	Returns the number of sections in a second-order sections filter. If a multistage filter contains stages with multiple sections, using nsections returns the total number of sections in all the stages (a stage with a single section returns 1).
nstages	Returns the number of stages of the filter, where a stage is a separate, modular filter.
nstates	Returns the number of states for an object.
order	Returns the filter order. If <code>hd</code> is a single-stage filter, the order is given by the number of delays needed for a minimum realization of the filter. If <code>hd</code> has multiple stages, the order is given by the number of delays needed for a minimum realization of the overall filter.
parallel	Returns the parallel combination of two <code>dfilt</code> filters. Refer to <code>dfilt.parallel</code> .
phasez	Plots the phase response in <code>fvtool</code> .
realizemdl	<p>(Available only with Simulink.)</p> <p><code>realizemdl(hd)</code> creates a Simulink model containing a subsystem block realization of your <code>dfilt</code>.</p> <p><code>realizemdl(hd,p1,v1,p2,v2,...)</code> creates the block using the properties <code>p1</code>, <code>p2</code>,... and values <code>v1</code>, <code>v2</code>,... specified.</p> <p>The following properties are available:</p> <p>'Blockname' specifies the name of the block. The default value is 'Filter'.</p> <p>'Destination' specifies whether to add the block to a current Simulink model or create a</p>

<b>Method</b>	<b>Description</b>
	<p>new model. Valid values are 'Current' and 'New'.</p> <p>'OverwriteBlock' specifies whether to overwrite an existing block that was created by <code>realizemdl</code> or create a new block. Valid values are 'on' and 'off'. Only blocks created by <code>realizemdl</code> are overwritten.</p> <p>The following properties optimize the block structure. Specifying 'on' turns the optimization on and 'off' creates the block without optimization. The default for each block is 'off'.</p> <p>'OptimizeZeros' removes zero-gain blocks.</p> <p>'OptimizeOnes' replaces unity-gain blocks with a direct connection.</p> <p>'OptimizeNegOnes' replaces negative unity-gain blocks with a sign change at the nearest summation block.</p> <p>'OptimizeDelayChains' replaces delay chains made up of <math>n</math> unit delays with a single delay by <math>n</math>.</p>
<code>removestage</code>	Removes a stage from a cascade or parallel <code>dfilt</code> . Refer to <code>dfilt.cascade</code> and <code>dfilt.parallel</code> .
<code>setstage</code>	Overwrites a stage of a cascade or parallel <code>dfilt</code> . Refer to <code>dfilt.cascade</code> and <code>dfilt.parallel</code> .

Method	Description
sos	<p>Converts the <code>dfilt</code> to a second-order sections <code>dfilt</code>. If <code>hd</code> has a single section, the returned filter has the same class.</p> <p><code>sos(hd, flag)</code> specifies the ordering of the second-order sections. If <code>flag='UP'</code>, the first row contains the poles closest to the origin, and the last row contains the poles closest to the unit circle. If <code>flag='down'</code>, the sections are ordered in the opposite direction. The zeros are always paired with the poles closest to them.</p> <p><code>sos(hd, flag, scale)</code> specifies the scaling of the gain and the numerator coefficients of all second-order sections. <code>scale</code> can be <code>'none'</code>, <code>'inf'</code> (infinity-norm), or <code>'two'</code> (2-norm). Using infinity-norm scaling with up ordering minimizes the probability of overflow in the realization. Using 2-norm scaling with down ordering minimizes the peak roundoff noise.</p>
ss	<p>Converts the <code>dfilt</code> to state-space. To see the separate <code>A, B, C, D</code> matrices for the state-space model, use <code>[A, B, C, D]=ss(hd)</code>.</p>
stepz	<p>Plots the step response in <code>fvtool</code></p> <p><code>stepz(hd, n)</code> computes the first <code>n</code> samples of the step response.</p> <p><code>stepz(hd, n, Fs)</code> separates the time samples by <math>T = 1/Fs</math>, where <code>Fs</code> is assumed to be in hertz.</p>
sysobj	<p>Converts the <code>dfilt</code> to a filter System object. See the reference page for a list of supported objects.</p>

Method	Description
tf	Converts the <code>dfilt</code> to a transfer function.
zerophase	Plots the zero-phase response in <code>fvtool</code> .
zpk	Converts the <code>dfilt</code> to zeros-pole-gain form.
zplane	Plots a pole-zero plot in <code>fvtool</code> .

## Viewing Properties

As with any object, use `get` to view a `dfilt` properties. To see a specific property, use

```
get(hd, 'property')
```

To see all properties for an object, use

```
get(hd)
```

---

**Note** `dfilt` objects include an arithmetic property. You can change the internal arithmetic of the filter from double-precision to single-precision using: `hd.arithmetic = 'single'`.

If you have Fixed-Point Toolbox software, you can change the arithmetic property to fixed-point using: `hd.arithmetic = 'fixed'`

---

## Changing Properties

To set specific properties, use

```
set(hd, 'property1', value, 'property2', value, ...)
```

You must use single quotation marks around the property name. Use single quotation marks around the value argument when the value is a string, such as `specifyall` or `fixed`.

## Copying an Object

To create a copy of an object, use the `copy` method.

```
h2 = copy(hd)
```

---

**Note** Using the syntax `H2 = hd` copies only the object handle and does not create a new, independent object.

---

## Converting Between Filter Structures

To change the filter structure of a `dfilt` object `hd`, use

```
hd2 = convert(hd, 'structure_string');
```

where `structure_string` is any valid structure name in single quotation marks. If `hd` is a cascade or parallel structure, each stage is converted to the new structure.

## Using Filter States

Two properties control the filter states:

- `states` — Stores the current states of the filter. Before the filter is applied, the states correspond to the initial conditions and after the filter is applied, the states correspond to the final conditions. For `df1`, `df1t`, `df1sos` and `df1tsos` structures, `states` returns a `filtstates` object.
- `PersistentMemory` — Controls whether filter states are saved. The default value is `'false'`, which causes the initial conditions to be reset to zero before filtering and turns off the display of states information. Setting `PersistentMemory` to `'true'` allows the filter to use your initial conditions or to reuse the final conditions from a previous filtering operation as the initial conditions of the next filtering operation. The `true` setting also displays information about the filter states.

---

**Note** If you set the `states` and want to use them for filtering, you must set `PersistentMemory` to `'true'` before you use the filter.

---

## Examples

Create a direct-form I filter, and use a method to see if it is stable.

```
[b,a] = butter(8,0.25);  
hd = dfilt.df1(b,a);  
isstable(hd)
```

If a `dfilt`'s numerator values do not fit on a single line, a description of the vector is displayed. To see the specific numerator values for this example, use

```
B = get(hd,'numerator');  
% or  
B1 = hd.numerator;
```

Create an array containing two `dfilt` objects, apply a method and verify that the method acts on both objects. Use a method to test whether the objects are FIR objects.

```
b = fir1(5,.5);  
hd = dfilt.dfir(b);           % Create an FIR filter object  
[b,a] = butter(5,.5);       % Create IIR filter  
hd(2) = dfilt.df2t(b,a);    % Create DF2T object and place  
                             % in the second column of hd.  
  
[h,w] = freqz(hd);  
test_fir = isfir(hd)  
% hd(1) is FIR and hd(2) is not.
```

Refer to the reference pages for each structure for more examples.

## See Also

```
dfilt | design | fdesign | realizemd1 | sos | stepz |  
dfilt.cascade | dfilt.df1 | dfilt.df1t | dfilt.df2 | dfilt.df2t  
| dfilt.dfasymfir | dfilt.dffir | dfilt.dffirt | dfilt.dfsymfir  
| dfilt.latticeallpass | dfilt.latticear | dfilt.latticearma  
| dfilt.latticemamax | dfilt.latticemamin | dfilt.parallel |  
dfilt.statespace | filter | freqz | grpdelay | impz | zplane
```

**Purpose** Allpass filter

**Syntax** `hd = dfilt.allpass(c)`

**Description** `hd = dfilt.allpass(c)` constructs an allpass filter with the minimum number of multipliers from the elements in vector `c`. To be valid, `c` must contain one, two, three, or four real elements. The number of elements in `c` determines the order of the filter. For example, `c` with two elements creates a second-order filter and `c` with four elements creates a fourth-order filter.

The transfer function for the allpass filter is defined by

$$H(z) = \frac{c(n) + c(n-1)z^{-1} + \dots + z^{-n}}{1 + c(1)z^{-1} + \dots + c(n)z^{-n}}$$

given the coefficients in `c`.

To construct a cascade of allpass filter objects, use `dfilt.cascadeallpass`. For more information about creating cascades of allpass filters, refer to `dfilt.cascadeallpass`.

## Properties

The following table provides a list of all the properties associated with an allpass `dfilt` object.

Property Name	Brief Description
AllpassCoefficients	Contains the coefficients for the allpass filter object
FilterStructure	Describes the signal flow for the filter object, including all of the active elements that perform operations during filtering — gains, delays, sums, products, and input/output.

# dfilt.allpass

---

Property Name	Brief Description
PersistentMemory	Specifies whether to reset the filter states and memory before each filtering operation. Lets you decide whether your filter retains states from previous filtering runs. <code>False</code> is the default setting.
States	This property contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions. They also provide linkage between the sections of a multisection filter, such as a cascade filter. For details, refer to <code>filtstates</code> in Signal Processing Toolbox documentation or in the Help system.

## Examples

This example constructs and displays the information about a second-order allpass filter that uses the minimum number of multipliers.

```
c = [1.5, 0.7];  
% Create a second-order dfilt object.  
hd = dfilt.allpass(c);
```

## See Also


`dfilt` | `dfilt.cascadeallpass` | `dfilt.cascadewdfallpass` | `dfilt.latticeallpass` | `mfilt.iirdecim` | `mfilt.iirinterp`

**Purpose** Coupled-allpass, lattice filter

**Syntax** `hd = dfilt.calattice(k1,k2,beta)`  
`hd = dfilt.calattice`

**Description** `hd = dfilt.calattice(k1,k2,beta)` returns a discrete-time, coupled-allpass, lattice filter object `hd`, which is two allpass, lattice filter structures coupled together. The lattice coefficients for each structure are vectors `k1` and `k2`. Input argument `beta` is shown in the diagram below.

`hd = dfilt.calattice` returns a default, discrete-time coupled-allpass, lattice filter object, `hd`. The default values are `k1 = k2 = []`, which is the default value for `dfilt.latticeallpass`, and `beta = 1`. This filter passes the input through to the output unchanged.



## Examples

Specify a third-order lattice coupled-allpass filter structure for a `dfilt` filter, `hd` with the following code.

```
k1 = [0.9511 + 1j*0.3088; 0.7511 + 1j*0.1158];  
k2 = 0.7502 - 1j*0.1218;  
beta = 0.1385 + 1j*0.9904;  
hd = dfilt.calattice(k1,k2,beta);
```

The `Allpass1` and `Allpass2` properties store vectors of coefficients.

## See Also


`dfilt.calatticepc` | `dfilt` | `dfilt.latticeallpass` |  
`dfilt.latticear` | `dfilt.latticearma` | `dfilt.latticemax` |  
`dfilt.latticemin`

**Purpose** Coupled-allpass, power-complementary lattice filter

**Syntax** `hd = dfilt.calatticepc(k1,k2)`  
`hd = dfilt.calatticepc`

**Description** `hd = dfilt.calatticepc(k1,k2)` returns a discrete-time, coupled-allpass, lattice filter object `hd`, with power-complementary output. This object is two allpass lattice filter structures coupled together to produce complementary output. The lattice coefficients for each structure are vectors, `k1` and `k2`, respectively. `beta` is shown in the following diagram.

`hd = dfilt.calatticepc` returns a default, discrete-time, coupled-allpass, lattice filter object `hd`, with power-complementary output. The default values are `k1 = k2 = []`, which is the default value for the `dfilt.latticeallpass`. The default for `beta = 1`. This filter passes the input through to the output unchanged.



## Examples

Specify a third-order lattice coupled-allpass power complementary filter structure for a filter  $h_d$  with the following code. You see from the returned properties that `Allpass1` and `Allpass2` contain vectors of coefficients for the constituent filters.

```
k1 = [0.9511 + 0.3088i; 0.7511 + 0.1158i];
k2 = 0.7502 - 0.1218i;
beta = 0.1385 + 0.9904i;
hd = dfilt.calatticepc(k1,k2,beta);
```

To see the coefficients for `Allpass1`, check the property values.

```
get(hd, 'Allpass1')
```

## See Also

```
dfilt.calattice | dfilt | dfilt.latticeallpass |  
dfilt.latticear | dfilt.latticearma | dfilt.latticemamax |  
dfilt.latticemamin
```

# dfilt.cascade

**Purpose** Cascade of discrete-time filters


**Syntax** Refer to `dfilt.cascade` in Signal Processing Toolbox documentation for more information.

**Description** `hd = dfilt.cascade(filterobject1,filterobject2,...)` returns a discrete-time filter object `hd` of type `cascade`, which is a serial interconnection of two or more filter objects `filterobject1`, `filterobject2`, and so on. `dfilt.cascade` accepts any combination of `dfilt` objects (discrete time filters) to cascade, as well as Farrow filter objects.

You can use the standard notation to cascade one or more filters:

```
cascade(hd1,hd2,...)
```

where `hd1`, `hd2`, and so on can be mixed types, such as `dfilt` objects and `mfilt` objects.



`hd1`, `hd2`, and so on can be fixed-point filters. All filters in the cascade must be the same arithmetic format — `double`, `single`, or `fixed`. `hd`, the filter object returned, inherits the format of the cascaded filters.

**Examples** Cascade a lowpass filter and a highpass filter to produce a bandpass filter.

```
[b1,a1]=butter(8,0.6); % Lowpass
[b2,a2]=butter(8,0.4,'high'); % Highpass
h1=dfilt.df2t(b1,a1);
h2=dfilt.df2t(b2,a2);
hcas=dfilt.cascade(h1,h2); % Bandpass with passband 0.4-0.6
% View stage 1 with hcas.Stage(1)
```

**See Also** `dfilt` | `dfilt.parallel` | `dfilt.scalar`

**Purpose**

Cascade of allpass discrete-time filters

**Syntax**

```
hd = dfilt.cascadeallpass(c1,c2,...)
```

**Description**

`hd = dfilt.cascadeallpass(c1,c2,...)` constructs a cascade of allpass filters, each of which uses the minimum number of multipliers, given the filter coefficients provided in `c1`, `c2`, and so on.

Each vector `c` represents one section in the cascade filter. `c` vectors must contain one, two, three, or four elements as the filter coefficients for each section. As a result of the design algorithm, each section is a `dfilt.allpass` structure whose coefficients are given in the matching `c` vector, such as the `c1` vector contains the coefficients for the first stage.

States for each section are shared between sections.

Vectors `c` do not have to be the same length. You can combine various length vectors in the input arguments. For example, you can cascade fourth-order sections with second-order sections, or first-order sections.

For more information about the vectors `ci` and about the transfer function of each section, refer to `dfilt.allpass`.

Generally, you do not construct these allpass cascade filters directly. Instead, they result from the design process for an IIR filter. Refer to the first example in Examples for more about using `dfilt.cascadeallpass` to design an IIR filter.

**Properties**

In the next table, the row entries are the filter properties and a brief description of each property.

# dfilt.cascadeallpass

Property Name	Brief Description
AllpassCoefficients	Contains the coefficients for the allpass filter object
FilterStructure	Describes the signal flow for the filter object, including all of the active elements that perform operations during filtering — gains, delays, sums, products, and input/output.
PersistentMemory	Specifies whether to reset the filter states and memory before each filtering operation. Lets you decide whether your filter retains states from previous filtering runs. <code>False</code> is the default setting.
States	This property contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions. They also provide linkage between the sections of a multisection filter, such as a cascade filter. For details, refer to <code>filtstates</code> in Signal Processing Toolbox documentation or in the Help system.

## Examples

Two examples show how `dfilt.cascadeallpass` works in very different applications — designing a halfband IIR filter and constructing an allpass cascade of `dfilt` objects.

First, design the IIR halfband filter using cascaded allpass filters. Each branch of the parallel cascade construction is a `cascadeallpass` filter object.

```
tw = 100; % Transition width of filter to be designed, 100 Hz.
ast = 80; % Stopband attenuation of filter to be designed, 80dB.
fs = 2000; % Sampling frequency of signal to be filtered.
% Store halfband design specs in the specifications object d.
d = fdesign.halfband('tw,ast',tw,ast,fs);
```

Now perform the actual filter design. `hd` contains two `dfilt.cascadeallpass` objects.

```
hd = design(d,'ellip','filterstructure','cascadeallpass');  
% Get summary information about one dfilt.cascadeallpass stage.  
StageInfo = hd.Stage(1).Stage(1);
```

This second example constructs a `dfilt.cascadeallpass` filter object directly given allpass coefficients for the input vectors.

```
section1 = 0.8;  
section2 = [1.2,0.7];  
section3 = [1.3,0.9];  
hd = dfilt.cascadeallpass(section1,section2,section3);  
% Get information about the filter  
% return informatio in character array  
S = info(hd);
```

### See Also

[dfilt](#) | [dfilt.allpass](#) | [dfilt.cascadewdfallpass](#) |  
[mfilt.iirdecim](#) | [mfilt.iirinterp](#)

# dfilt.cascadewdfallpass

---

**Purpose** Cascade allpass WDF filters to construct allpass WDF

**Syntax** `hd = dfilt.cascadewdfallpass(c1,c2,...)`

**Description** `hd = dfilt.cascadewdfallpass(c1,c2,...)` constructs a cascade of allpass wave digital filters given the allpass coefficients in the vectors `c1`, `c2`, and so on.

Each `c` vector contains the coefficients for one section of the cascaded filter. `C` vectors must have one, two, or four elements (coefficients). Three element vectors are not supported.

When the `c` vector has four elements, the first and third elements of the vector must be 0. Each section of the cascade is an allpass wave digital filter, from `dfilt.wdfallpass`, with the coefficients given by the corresponding `c` vector. That is, the first section has coefficients from vector `c1`, the second section coefficients come from `c2`, and on until all of the `c` vectors are used.

You can mix the lengths of the `c` vectors. They do not need to be the same length. For example, you can cascade several fourth-order sections (`length(c) = 4`) with first or second-order sections.

Wave digital filters are usually used to create other filters. This toolbox uses them to implement halfband filters, which the first example in Examples demonstrates. They are most often building blocks for filters.

Generally, you do not construct these WDF allpass cascade filters directly. Instead, they result from the design process for an IIR filter. Refer to the first example in Examples for more about using `dfilt.cascadewdfallpass` to design an IIR filter.

For more information about the `c` vectors and the transfer function for the allpass filters, refer to `dfilt.wdfallpass`.

**Properties** In the next table, the row entries are the filter properties and a brief description of each property.

Property Name	Brief Description
AllpassCoefficients	Contains the coefficients for the allpass wave digital filter object
FilterStructure	Describes the signal flow for the filter object, including all of the active elements that perform operations during filtering — gains, delays, sums, products, and input/output.
PersistentMemory	Specifies whether to reset the filter states and memory before each filtering operation. Lets you decide whether your filter retains states from previous filtering runs. <code>False</code> is the default setting.
States	This property contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions. They also provide linkage between the sections of a multisection filter, such as a cascade filter. For details, refer to <code>filtstates</code> in Signal Processing Toolbox documentation or in the Help system.

## Examples

To demonstrate two approaches to using `dfilt.cascadewdfallpass` to design a filter, these examples show both direct construction and construction as part of another filter.

The first design shown creates an IIR halfband filter that uses lattice wave digital filters. Each branch of the parallel connection in the lattice is an allpass cascade wave digital filter.

```
tw = 100; % Transition width of filter, 100 Hz.
ast = 80; % Stopband attenuation of filter, 80 dB.
fs = 2000; % Sampling frequency of signal to filter.
% Store halfband specs.
d = fdesign.halfband('tw,ast',tw,ast,fs);
```


# dfilt.cascadewdfallpass

Now perform the actual halfband design process. `hd` contains two `dfilt.cascadewdfallpass` filters.

```
hd = design(d,'ellip','filterstructure','cascadewdfallpass');  
% Summary info on dfilt.cascadewdfallpass.  
StageSummary = hd.stage(1).stage(2);
```

This example demonstrates direct construction of a `dfilt.cascadewdfallpass` filter with allpass coefficients.

```
section1 = 0.8;  
section2 = [1.5,0.7];  
section3 = [1.8,0.9];  
hd = dfilt.cascadewdfallpass(section1,section2,section3);
```



**See Also**      `dfilt` | `dfilt.wdfallpass`

# dfilt.delay

---

**Purpose** Delay filter


**Syntax**  
`Hd = dfilt.delay`  
`Hd = dfilt.delay(latency)`

**Description** `Hd = dfilt.delay` returns a discrete-time filter, `Hd`, of type `delay`, which adds a single delay to any signal filtered with `Hd`. The filtered signal has its values shifted by one sample.

`Hd = dfilt.delay(latency)` returns a discrete-time filter, `Hd`, of type `delay`, which adds the number of delay units specified in `latency` to any signal filtered with `Hd`. The filtered signal has its values shifted by the `latency` number of samples. The values that appear before the shifted signal are the filter states.

**Examples** Create a delay filter with a latency of 4 and filter a simple signal to view the impact of applying a delay.

```
h = dfilt.delay(4);  
Fs = 1000;  
t = 0:1/Fs:1;  
sig = cos(2*pi*100*t);  
y = filter(h,sig);  
subplot(211);  
stem(sig,'markerfacecolor',[0 0 1]);  
axis([0 20 -2 2]);  
title('Input Signal');  
subplot(212);  
stem(y,'markerfacecolor',[0 0 1]);  
axis([0 20 -2 2]);  
title('Delayed Signal');
```



**See Also** [dfilt](#)

# dfilt.df1

---

## Purpose

Discrete-time, direct-form I filter

## Syntax

Refer to `dfilt.df1` in Signal Processing Toolbox documentation.

## Description

`hd = dfilt.df1` returns a default discrete-time, direct-form I filter object that uses double-precision arithmetic. By default, the numerator and denominator coefficients `b` and `a` are set to 1. With these coefficients the filter passes the input to the output without changes.

Make this filter a fixed-point or single-precision filter by changing the value of the `Arithmetic` property for the filter `hd` as follows:

- To change to single-precision filtering, enter

```
set(hd,'arithmetic','single');
```

- To change to fixed-point filtering, enter

```
set(hd,'arithmetic','fixed');
```

For more information about the property `Arithmetic`, refer to “`Arithmetic`” on page 8-19.


---

**Note** `a(1)`, the leading denominator coefficient, cannot be 0. To allow you to change the arithmetic setting to `fixed` or `single`, `a(1)` must be equal to 1.

---

## Fixed-Point Filter Structure

The following figure shows the signal flow for the direct-form I filter implemented by `dfilt.df1`. To help you see how the filter processes the coefficients, input, output, and states of the filter, as well as numerical operations, the figure includes the locations of the arithmetic and data type format elements within the signal flow.



## Notes About the Signal Flow Diagram

To help you understand where and how the filter performs fixed-point arithmetic during filtering, the figure shows various labels associated with data and functional elements in the filter. The following table describes each label in the signal flow and relates the label to the filter properties that are associated with it.

The labels use a common format — a prefix followed by the word “format.” In this use, “format” means the word length and fraction length associated with the filter part referred to by the prefix.

For example, the InputFormat label refers to the word length and fraction length used to interpret the data input to the filter. The format properties InputWordLength and InputFracLength (as shown in the table) store the word length and the fraction length in bits. Or consider NumFormat, which refers to the word and fraction lengths (CoeffWordLength, NumFracLength) associated with representing filter numerator coefficients.

<b>Signal Flow Label</b>	<b>Corresponding Word Length Property</b>	<b>Corresponding Fraction Length Property</b>	<b>Related Properties</b>
DenAccumFormat	AccumWordLength	DenAccumFracLength	AccumMode, CastBeforeSum
DenFormat	CoeffWordLength	DenFracLength	CoeffAutoScale , SignedDenominator
DenProdFormat	CoeffWordLength	DenProdFracLength	ProductMode, ProductWordLength
InputFormat	InputWordLength	InputFracLength	None
NumAccumFormat	AccumWordLength	NumAccumFracLength	AccumMode, CastBeforeSum
NumFormat	CoeffWordLength	NumFracLength	CoeffAutoScale, Signed, Numerator
NumProdFormat	CoeffWordLength	NumProdFracLength	ProductWordLength, ProductMode
OutputFormat	OutputWordLength	OutputFracLength	OutputMode

Most important is the label position in the diagram, which identifies where the format applies.

As one example, look at the label DenProdFormat, which always follows a denominator coefficient multiplication element in the signal flow. The label indicates that denominator coefficients leave the multiplication element with the word length and fraction length associated with product operations that include denominator coefficients. From reviewing the table, you see that the DenProdFormat refers to the properties ProdWordLength, ProductMode and DenProdFracLength that fully define the denominator format after multiply (or product) operations.

## Properties

In this table you see the properties associated with df1 implementations of dfilt objects.

---

**Note** The table lists all the properties that a filter can have. Many of the properties are dynamic, meaning they exist only in response to the settings of other properties. You might not see all of the listed properties all the time. To view all the properties for a filter at any time, use `get(hd)` where `hd` is a filter.

---

For further information about the properties of this filter or any `dfilt` object, refer to “Fixed-Point Filter Properties” on page 8-2.

Property Name	Brief Description
<code>AccumMode</code>	Determines how the accumulator outputs stored values. Choose from full precision ( <code>FullPrecision</code> ), or whether to keep the most significant bits ( <code>KeepMSB</code> ) or least significant bits ( <code>KeepLSB</code> ) when output results need shorter word length than the accumulator supports. To let you set the word length and the precision (the fraction length) used by the output from the accumulator, set <code>AccumMode</code> to <code>SpecifyPrecision</code> .
<code>AccumWordLength</code>	Sets the word length used to store data in the accumulator/buffer.
<code>Arithmetic</code>	Defines the arithmetic the filter uses. Gives you the options <code>double</code> , <code>single</code> , and <code>fixed</code> . In short, this property defines the operating mode for your filter.
<code>CastBeforeSum</code>	Specifies whether to cast numeric data to the appropriate accumulator format (as shown in the signal flow diagrams) before performing sum operations.

<b>Property Name</b>	<b>Brief Description</b>
CoeffAutoScale	Specifies whether the filter automatically chooses the proper fraction length to represent filter coefficients without overflowing. Turning this off by setting the value to <code>false</code> enables you to change the NumFracLength and DenFracLength properties to specify the precision used.
CoeffWordLength	Specifies the word length to apply to filter coefficients.
DenAccumFracLength	Specifies the fraction length the filter algorithm uses to interpret the results of product operations involving denominator coefficients. You can change the value for this property when you set AccumMode to SpecifyPrecision.
DenFracLength	Set the fraction length the filter uses to interpret denominator coefficients. DenFracLength is always available, but it is read-only until you set CoeffAutoScale to <code>false</code> .
Denominator	Stores the denominator coefficients for the IIR filter.
DenProdFracLength	Specifies how the filter algorithm interprets the results of product operations involving denominator coefficients. You can change this property value when you set ProductMode to SpecifyPrecision.
FilterStructure	Describes the signal flow for the filter object, including all of the active elements that perform operations during filtering — gains, delays, sums, products, and input/output.

<b>Property Name</b>	<b>Brief Description</b>
InputFracLength	Specifies the fraction length the filter uses to interpret input data.
InputWordLength	Specifies the word length applied to interpret input data.
NumAccumFracLength	Specifies how the filter algorithm interprets the results of addition operations involving numerator coefficients. You can change the value of this property after you set AccumMode to SpecifyPrecision.
Numerator	Holds the numerator coefficient values for the filter.
NumFracLength	Sets the fraction length used to interpret the value of numerator coefficients.
NumProdFracLength	Specifies how the filter algorithm interprets the results of product operations involving numerator coefficients. Available to be changed when you set ProductMode to SpecifyPrecision.
OutputFracLength	Determines how the filter interprets the filter output data. You can change the value of OutputFracLength when you set OutputMode to SpecifyPrecision.
OutputWordLength	Determines the word length used for the output data.

<b>Property Name</b>	<b>Brief Description</b>
OverflowMode	Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either <code>saturate</code> (limit the output to the largest positive or negative representable value) or <code>wrap</code> (set overflowing values to the nearest representable value using modular arithmetic). The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow — they maintain full precision.
ProductMode	Determines how the filter handles the output of product operations. Choose from full precision ( <code>FullPrecision</code> ), or whether to keep the most significant bit ( <code>KeepMSB</code> ) or least significant bit ( <code>KeepLSB</code> ) in the result when you need to shorten the data words. For you to be able to set the precision (the fraction length) used by the output from the multiplies, you set <code>ProductMode</code> to <code>SpecifyPrecision</code> .
ProductWordLength	Specifies the word length to use for multiplication operation results. This property becomes writable (you can change the value) when you set <code>ProductMode</code> to <code>SpecifyPrecision</code> .
PersistentMemory	Specifies whether to reset the filter states and memory before each filtering operation. Lets you decide whether your filter retains states from previous filtering runs. <code>False</code> is the default setting.

Property Name	Brief Description
RoundMode	<p data-bbox="765 319 1314 440">Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths).</p> <ul data-bbox="765 479 1322 1003" style="list-style-type: none"><li data-bbox="765 479 1262 505">• <code>ceil</code> - Round toward positive infinity.</li><li data-bbox="765 527 1292 678">• <code>convergent</code> - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.</li><li data-bbox="765 701 1107 727">• <code>fix</code> - Round toward zero.</li><li data-bbox="765 749 1285 775">• <code>floor</code> - Round toward negative infinity.</li><li data-bbox="765 798 1277 857">• <code>nearest</code> - Round toward nearest. Ties round toward positive infinity.</li><li data-bbox="765 880 1322 1003">• <code>round</code> - Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.</li></ul> <p data-bbox="765 1041 1297 1201">The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always round. Finally, products never overflow — they maintain full precision.</p>

# dfilt.df1

---

Property Name	Brief Description
Signed	Specifies whether the filter uses signed or unsigned fixed-point coefficients. Only coefficients reflect this property setting.
States	This property contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions. The states use <code>fi</code> objects, with the associated properties from those objects. For details, refer to <code>filtstates</code> in Signal Processing Toolbox documentation or in the Help system.

## Examples

Specify a second-order direct-form I structure for a `dfilt` object, `hd`, with the following code:

```
b = [0.3 0.6 0.3];  
a = [1 0 0.2];  
hd = dfilt.df1(b,a);  
% Convert hd to fixed-point filter  
set(hd,'arithmetic','fixed')
```

## See Also

`dfilt` | `dfilt.df1t` | `dfilt.df2` | `dfilt.df2t`

**Purpose**

Discrete-time, SOS direct-form I filter

**Syntax**

Refer to `dfilt.df1sos` in Signal Processing Toolbox documentation.

**Description**

`hd = dfilt.df1sos(s)` returns a discrete-time, second-order section, direct-form I filter object `hd`, with coefficients given in the `s` matrix.

Make this filter a fixed-point or single-precision filter by changing the value of the `Arithmetic` property for the filter `hd` as follows:

- To change to single-precision filtering, enter

```
set(hd,'arithmetic','single');
```

- To change to fixed-point filtering, enter

```
set(hd,'arithmetic','fixed');
```

For more information about the property `Arithmetic`, refer to “Arithmetic” on page 8-19.

`hd = dfilt.df1sos(b1,a1,b2,a2,...)` returns a discrete-time, second-order section, direct-form I filter object `hd`, with coefficients for the first section given in the `b1` and `a1` vectors, for the second section given in the `b2` and `a2` vectors, and so on.

`hd = dfilt.df1sos(...,g)` includes a gain vector `g`. The elements of `g` are the gains for each section. The maximum length of `g` is the number of sections plus one. When you do not specify `g`, all gains default to one.

`hd = dfilt.df1sos` returns a default, discrete-time, second-order section, direct-form I filter object, `hd`. This filter passes the input through to the output unchanged.


---

**Note** The leading coefficient of the denominator `a(1)` cannot be 0. To allow you to change the arithmetic setting to `fixed` or `single`, `a(1)` must be equal to 1.

---

## Fixed-Point Filter Structure

The following figure shows the signal flow for the direct-form I filter implemented in second-order sections by `dfilt.df1sos`. To help you see how the filter processes the coefficients, input, and states of the filter, as well as numerical operations, the figure includes the locations of the formatting objects within the signal flow.



## Notes About the Signal Flow Diagram

To help you understand where and how the filter performs fixed-point arithmetic during filtering, the figure shows various labels associated with data and functional elements in the filter. The following table describes each label in the signal flow and relates the label to the filter properties that are associated with it.

The labels use a common format — a prefix followed by the letters “frmt” (format). In this use, “frmt” means the word length and fraction length associated with the filter part referred to by the prefix.

For example, the `InputFrmt` label refers to the word length and fraction length used to interpret the data input to the filter. The format properties `InputWordLength` and `InputFracLength` (as shown in the table) store the word length and the fraction length in bits. Similarly consider `NumFrmt`, which refers to the word and fraction lengths

(CoeffWordLength, NumFracLength) associated with representing filter numerator coefficients.

<b>Signal Flow Label</b>	<b>Corresponding Word Length Property</b>	<b>Corresponding Fraction Length Property</b>	<b>Related Properties</b>
DenAccumFrmt	AccumWordLength	DenAccumFracLength	AccumMode, CastBeforeSum
DenFrmt	CoeffWordLength	DenFracLength	CoeffAutoScale, Signed, Denominator
DenProdFrmt	CoeffWordLength	DenProdFracLength	ProductMode, ProductWordLength
DenStateFrmt	DenStateWordLength	DenStateFracLength	CastBeforeSum, States
InputFrmt	InputWordLength	InputFracLength	None
NumAccumFrmt	AccumWordLength	NumAccumFracLength	AccumMode, CastBeforeSum
NumFrmt	CoeffWordLength	NumFracLength	CoeffAutoScale, Signed, Numerator
NumProdFrmt	CoeffWordLength	NumProdFracLength	ProductWordLength, ProductMode
NumStateFrmt	NumStateWordLength	NumStateFracLength	States
OutputFrmt	OutputWordLength	OutputFracLength	OutputMode
ScaleValueFrmt	CoeffWordLength	ScaleValueFracLength	CoeffAutoScale, ScaleValues

Most important is the label position in the diagram, which identifies where the format applies.

As one example, look at the label DenProdFrmt, which always follows a denominator coefficient multiplication element in the signal flow. The label indicates that denominator coefficients leave the multiplication element with the word length and fraction length associated with

product operations that include denominator coefficients. From reviewing the table, you see that the DenProdFrmt refers to the properties ProdWordLength, ProductMode and DenProdFracLength that fully define the denominator format after multiply (or product) operations.

## Properties

In this table you see the properties associated with SOS implementation of direct-form I `dfilt` objects.

---

**Note** The table lists all the properties that a filter can have. Many of the properties are dynamic, meaning they exist only in response to the settings of other properties. You might not see all of the listed properties all the time. To view all the properties for a filter at any time, use

`get(hd)`

where `hd` is a filter.

---

For further information about the properties of this filter or any `dfilt` object, refer to “Fixed-Point Filter Properties” on page 8-2.

Property Name	Brief Description
AccumMode	Determines how the accumulator outputs stored values. Choose from full precision (FullPrecision), or whether to keep the most significant bits (KeepMSB) or least significant bits (KeepLSB) when output results need shorter word length than the accumulator supports. To let you set the word length and the precision (the fraction length) used by the output

Property Name	Brief Description
	from the accumulator, set <code>AccumMode</code> to <code>SpecifyPrecision</code> .
<code>AccumWordLength</code>	Sets the word length used to store data in the accumulator/buffer.
<code>Arithmetic</code>	Defines the arithmetic the filter uses. Gives you the options <code>double</code> , <code>single</code> , and <code>fixed</code> . In short, this property defines the operating mode for your filter.
<code>CastBeforeSum</code>	Specifies whether to cast numeric data to the appropriate accumulator format (as shown in the signal flow diagrams) before performing sum operations.
<code>CoeffAutoScale</code>	Specifies whether the filter automatically chooses the proper fraction length to represent filter coefficients without overflowing. Turning this off by setting the value to <code>false</code> enables you to change the <code>NumFracLength</code> and <code>DenFracLength</code> properties to specify the precision used.
<code>CoeffWordLength</code>	Specifies the word length to apply to filter coefficients.
<code>DenAccumFracLength</code>	Specifies the fraction length used to interpret data in the accumulator used to hold the results of sum operations. You can change the value for this property when you set <code>AccumMode</code> to <code>SpecifyPrecision</code> .
<code>DenFracLength</code>	Set the fraction length the filter uses to interpret denominator coefficients. <code>DenFracLength</code> is always available, but it is read-only until you set <code>CoeffAutoScale</code> to <code>false</code> .

Property Name	Brief Description
DenProdFracLength	Specifies how the filter algorithm interprets the results of product operations involving denominator coefficients. You can change this property value when you set <code>ProductMode</code> to <code>SpecifyPrecision</code> .
DenStateFracLength	Specifies the fraction length used to interpret the states associated with denominator coefficients in the filter.
DenStateWordLength	Specifies the word length used to represent the states associated with denominator coefficients in the filter.
FilterStructure	Describes the signal flow for the filter object, including all of the active elements that perform operations during filtering—gains, delays, sums, products, and input/output.
InputFracLength	Specifies the fraction length the filter uses to interpret input data.
InputWordLength	Specifies the word length applied to interpret input data.
NumAccumFracLength	Specifies how the filter algorithm interprets the results of addition operations involving numerator coefficients. You can change the value of this property after you set <code>AccumMode</code> to <code>SpecifyPrecision</code> .
NumFracLength	Sets the fraction length used to interpret the value of numerator coefficients.
NumStateFracLength	Specifies the fraction length used to interpret the states associated with numerator coefficient operations in the filter.

Property Name	Brief Description
NumWordFracLength	Specifies the word length used to interpret the states associated with numerator coefficient operations in the filter.
OptimizeScaleValues	When true, the filter skips multiplication-by-one scaling. When false, the filter performs multiplication-by-one scaling.
OutputFracLength	Determines how the filter interprets the filter output data. You can change the value of OutputFracLength when you set OutputMode to SpecifyPrecision.
OutputMode	<p>Sets the mode the filter uses to scale the filtered data for output. You have the following choices:</p> <ul style="list-style-type: none"> <li>• <b>AvoidOverflow</b> — directs the filter to set the output data word length and fraction length to avoid causing the data to overflow.</li> <li>• <b>BestPrecision</b> — directs the filter to set the output data word length and fraction length to maximize the precision in the output data.</li> <li>• <b>SpecifyPrecision</b> — lets you set the word and fraction lengths used by the output data from filtering.</li> </ul>
OutputWordLength	Determines the word length applied for the output data.

Property Name	Brief Description
OverflowMode	Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either <code>saturate</code> (limit the output to the largest positive or negative representable value) or <code>wrap</code> (set overflowing values to the nearest representable value using modular arithmetic). The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow—they maintain full precision.
ProductMode	Determines how the filter handles the output of product operations. Choose from full precision ( <code>FullPrecision</code> ), or whether to keep the most significant bit ( <code>KeepMSB</code> ) or least significant bit ( <code>KeepLSB</code> ) in the result when you need to shorten the data words. For you to be able to set the precision (the fraction length) used by the output from the multiplies, you set <code>ProductMode</code> to <code>SpecifyPrecision</code> .
ProductWordLength	Specifies the word length to use for multiplication operation results. This property becomes writable (you can change the value) when you set <code>ProductMode</code> to <code>SpecifyPrecision</code> .
PersistentMemory	Specifies whether to reset the filter states and memory before each filtering operation. Lets you decide whether your filter retains states from previous filtering runs. <code>False</code> is the default setting.

Property Name	Brief Description
RoundMode	<p>Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths).</p> <ul style="list-style-type: none"> <li>• <code>ceil</code> - Round toward positive infinity.</li> <li>• <code>convergent</code> - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.</li> <li>• <code>fix</code> - Round toward zero.</li> <li>• <code>floor</code> - Round toward negative infinity.</li> <li>• <code>nearest</code> - Round toward nearest. Ties round toward positive infinity.</li> <li>• <code>round</code> - Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.</li> </ul> <p>The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always round. Finally, products never overflow — they maintain full precision.</p>
ScaleValueFracLength	<p>Scale values work with SOS filters. Setting this property controls how your filter interprets the scale values by setting the fraction length. Only available when you disable <code>AutoScaleMode</code> by setting it to <code>false</code>.</p>

Property Name	Brief Description
ScaleValues	Scaling for the filter objects in SOS filters.
Signed	Specifies whether the filter uses signed or unsigned fixed-point coefficients. Only coefficients reflect this property setting.
SosMatrix	Holds the filter coefficients as property values. Displays the matrix in the format [sections x coefficients/section datatype]. A [15x6 double] SOS matrix represents a filter with 6 coefficients per section and 15 sections, using data type <code>double</code> to represent the coefficients.
States	This property contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions. The states use <code>fi</code> objects, with the associated properties from those objects. For details, refer to <code>filtstates</code> in Signal Processing Toolbox documentation or in the Help system.
StateWordLength	Sets the word length used to represent the filter states.

## Examples

Specify a fixed-point, second-order section, direct-form I `dfilt` object with the following code:


```
b = [0.3 0.6 0.3];  
a = [1 0 0.2];  
hd = dfilt.df1sos(b,a);  
% Convert to fixed-point filter  
hd.arithmetic = 'fixed';
```

## See Also

`dfilt` | `dfilt.df2tsos`

---

<b>Purpose</b>	Discrete-time, direct-form I transposed filter
<b>Syntax</b>	Refer to <code>dfilt.df1t</code> in Signal Processing Toolbox documentation.
<b>Description</b>	<p><code>hd = dfilt.df1t(b,a)</code> returns a discrete-time, direct-form I transposed filter object <code>hd</code>, with numerator coefficients <code>b</code> and denominator coefficients <code>a</code>.</p> <p>Make this filter a fixed-point or single-precision filter by changing the value of the <code>Arithmetic</code> property for the filter <code>hd</code> as follows:</p> <ul style="list-style-type: none"><li>• To change to single-precision filtering, enter <pre>set(hd,'arithmetic','single');</pre></li><li>• To change to fixed-point filtering, enter <pre>set(hd,'arithmetic','fixed');</pre></li></ul> <p>For more information about the property <code>Arithmetic</code>, refer to “Arithmetic” on page 8-19.</p> <p><code>hd = dfilt.df1t</code> returns a default, discrete-time, direct-form I transposed filter object <code>hd</code>, with <code>b=1</code> and <code>a=1</code>. This filter passes the input through to the output unchanged.</p> <hr/> <p><b>Note</b> The leading coefficient of the denominator <code>a(1)</code> cannot be 0. To allow you to change the arithmetic setting to <code>fixed</code> or <code>single</code>, <code>a(1)</code> must be equal to 1.</p> <hr/>
<b>Fixed-Point Filter Structure</b>	The following figure shows the signal flow for the transposed direct-form I filter implemented by <code>dfilt.df1t</code> . To help you see how the filter processes the coefficients, input, and states of the filter, as well as numerical operations, the figure includes the locations of the formatting objects within the signal flow.



## Notes About the Signal Flow Diagram

To help you understand where and how the filter performs fixed-point arithmetic during filtering, the figure shows various labels associated with data and functional elements in the filter. The following table describes each label in the signal flow and relates the label to the filter properties that are associated with it.

The labels use a common format — a prefix followed by the letters “frmt” (format). In this use, “frmt” means the word length and fraction length associated with the filter part referred to by the prefix.

For example, the InputFrmt label refers to the word length and fraction length used to interpret the data input to the filter. The format properties InputWordLength and InputFracLength (as shown in the table) store the word length and the fraction length in bits. Or consider NumFrmt, which refers to the word and fraction lengths (CoeffWordLength, NumFracLength) associated with representing filter numerator coefficients.

<b>Signal Flow Label</b>	<b>Corresponding Word Length Property</b>	<b>Corresponding Fraction Length Property</b>	<b>Related Properties</b>
DenAccumFrmt	AccumWordLength	DenAccumFracLength	AccumMode, CastBeforeSum
DenFrmt	CoeffWordLength	DenFracLength	CoeffAutoScale, , Signed, Denominator
DenProdFrmt	CoeffWordLength	DenProdFracLength	ProductMode, ProductWordLength
DenStateFrmt	DenStateWordLength	DenStateFracLength	CastBeforeSum, States
InputFrmt	InputWordLength	InputFracLength	None
Multiplicandfrmt	Multiplicand-WordLength	Multiplicand-FracLength	CastBeforeSum
NumAccumFrmt	AccumWordLength	NumAccumFracLength	AccumMode, CastBeforeSum
NumFrmt	CoeffWordLength	NumFracLength	CoeffAutoScale, Signed, Numerator
NumProdFrmt	CoeffWordLength	NumProdFracLength	ProductWordLength, ProductMode
NumStateFrmt	NumStateWord- Length	NumStateFrac- Length	States
OutputFrmt	OutputWordLength	OutputFracLength	OutputMode

Most important is the label position in the diagram, which identifies where the format applies.

As one example, look at the label DenProdFrmt, which always follows a denominator coefficient multiplication element in the signal flow. The label indicates that denominator coefficients leave the multiplication element with the word length and fraction length associated with product operations that include denominator coefficients. From

reviewing the table, you see that the DenProdFrmt refers to the properties ProdWordLength, ProductMode and DenProdFracLength that fully define the denominator format after multiply (or product) operations.

## Properties

In this table you see the properties associated with df1t implementation of dfilt objects.

---

**Note** The table lists all the properties that a filter can have. Many of the properties are dynamic, meaning they exist only in response to the settings of other properties. You might not see all of the listed properties all the time. To view all the properties for a filter at any time, use

`get(hd)`

where `hd` is a filter.

---

For further information about the properties of this filter or any dfilt object, refer to “Fixed-Point Filter Properties” on page 8-2.

Property Name	Brief Description
AccumMode	Determines how the accumulator outputs stored values. Choose from full precision (FullPrecision), or whether to keep the most significant bits (KeepMSB) or least significant bits (KeepLSB) when output results need shorter word length than the accumulator supports. To let you set the word length and the precision (the fraction length) used by the output from the accumulator, set AccumMode to SpecifyPrecision.
AccumWordLength	Sets the word length used to store data in the accumulator/buffer.

Property Name	Brief Description
Arithmetic	Defines the arithmetic the filter uses. Gives you the options <code>double</code> , <code>single</code> , and <code>fixed</code> . In short, this property defines the operating mode for your filter.
CastBeforeSum	Specifies whether to cast numeric data to the appropriate accumulator format (as shown in the signal flow diagrams) before performing sum operations.
CoeffAutoScale	Specifies whether the filter automatically chooses the proper fraction length to represent filter coefficients without overflowing. Turning this off by setting the value to <code>false</code> enables you to change the <code>NumFracLength</code> and <code>DenFracLength</code> properties to specify the precision used.
CoeffWordLength	Specifies the word length to apply to filter coefficients.
DenAccumFracLength	Specifies the fraction length used to interpret data in the accumulator used to hold the results of sum operations. You can change the value for this property when you set <code>AccumMode</code> to <code>SpecifyPrecision</code> .
DenFracLength	Set the fraction length the filter uses to interpret denominator coefficients. <code>DenFracLength</code> is always available, but it is read-only until you set <code>CoeffAutoScale</code> to <code>false</code> .
Denominator	Holds the denominator coefficients for the filter.

Property Name	Brief Description
DenProdFracLength	Specifies how the filter algorithm interprets the results of product operations involving denominator coefficients. You can change this property value when you set ProductMode to SpecifyPrecision.
DenStateFracLength	Specifies the fraction length used to interpret the states associated with denominator coefficients in the filter.
FilterStructure	Describes the signal flow for the filter object, including all of the active elements that perform operations during filtering — gains, delays, sums, products, and input/output.
InputFracLength	Specifies the fraction length the filter uses to interpret input data.
InputWordLength	Specifies the word length applied to interpret input data.
MultiplicandFracLength	Sets the fraction length for values (multiplicands) used in multiply operations in the filter.
MultiplicandWordLength	Sets the word length applied to the values input to a multiply operation (the multiplicands).
NumAccumFracLength	Specifies how the filter algorithm interprets the results of addition operations involving numerator coefficients. You can change the value of this property after you set AccumMode to SpecifyPrecision.

Property Name	Brief Description
Numerator	Holds the numerator coefficient values for the filter.
NumFracLength	Sets the fraction length used to interpret the value of numerator coefficients.
NumProdFracLength	Specifies how the filter algorithm interprets the results of product operations involving numerator coefficients. Available to be changed when you set <code>ProductMode</code> to <code>SpecifyPrecision</code> .
NumStateFracLength	For IIR filters, this defines the binary point location applied to the numerator states of the filter. Specifies the fraction length used to interpret the states associated with numerator coefficient operations in the filter.
OutputFracLength	Determines how the filter interprets the filter output data. You can change the value of <code>OutputFracLength</code> when you set <code>OutputMode</code> to <code>SpecifyPrecision</code> .
OutputMode	Sets the mode the filter uses to scale the filtered data for output. You have the following choices: <ul style="list-style-type: none"><li>• <code>AvoidOverflow</code> — directs the filter to set the output data word length and fraction length to avoid causing the data to overflow.</li><li>• <code>BestPrecision</code> — directs the filter to set the output data word length and fraction length to maximize the precision in the output data.</li></ul>

<b>Property Name</b>	<b>Brief Description</b>
	<ul style="list-style-type: none"><li>• <b>SpecifyPrecision</b> — lets you set the word and fraction lengths used by the output data from filtering.</li></ul>
<b>OutputWordLength</b>	Determines the word length used for the output data.
<b>OverflowMode</b>	Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either <b>saturate</b> (limit the output to the largest positive or negative representable value) or <b>wrap</b> (set overflowing values to the nearest representable value using modular arithmetic). The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow—they maintain full precision.
<b>ProductMode</b>	Determines how the filter handles the output of product operations. Choose from full precision ( <b>FullPrecision</b> ), or whether to keep the most significant bit ( <b>KeepMSB</b> ) or least significant bit ( <b>KeepLSB</b> ) in the result when you need to shorten the data words. For you to be able to set the precision (the fraction length) used by the output from the multiplies, you set <b>ProductMode</b> to <b>SpecifyPrecision</b> .

Property Name	Brief Description
ProductWordLength	Specifies the word length to use for multiplication operation results. This property becomes writable (you can change the value) when you set ProductMode to SpecifyPrecision.
PersistentMemory	Specifies whether to reset the filter states and memory before each filtering operation. Lets you decide whether your filter retains states from previous filtering runs. False is the default setting.
RoundMode	Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths). <ul style="list-style-type: none"><li>• <code>ceil</code> - Round toward positive infinity.</li><li>• <code>convergent</code> - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.</li><li>• <code>fix</code> - Round toward zero.</li><li>• <code>floor</code> - Round toward negative infinity.</li><li>• <code>nearest</code> - Round toward nearest. Ties round toward positive infinity.</li><li>• <code>round</code> - Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.</li></ul>

Property Name	Brief Description
	The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always round. Finally, products never overflow — they maintain full precision.
Signed	Specifies whether the filter uses signed or unsigned fixed-point coefficients. Only coefficients reflect this property setting.
StateAutoScale	Setting autoscaling for filter states to <code>true</code> reduces the possibility of overflows occurring during fixed-point operations. Set to <code>false</code> , <code>StateAutoScale</code> lets the filter select the fraction length to limit the overflow potential.
States	This property contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions.
StateWordLength	Sets the word length used to represent the filter states.

## Examples

Specify a second-order direct-form I transposed filter structure for a `dfilt` object, `hd`, with the following code:

```
b = [0.3 0.6 0.3];  
a = [1 0 0.2];  
hd = dfilt.df1t(b,a);  
% Convert filter to single-precision arithmetic  
set(hd,'arithmetic','single')
```

## See Also

[dfilt](#) | [dfilt.df1](#) | [dfilt.df2](#) | [dfilt.df2t](#)

---

<b>Purpose</b>	Discrete-time, SOS direct-form I transposed filter
<b>Syntax</b>	Refer to <code>dfilt.df1tsos</code> in Signal Processing Toolbox documentation.
<b>Description</b>	<p><code>hd = dfilt.df1tsos(s)</code> returns a discrete-time, second-order section, direct-form I, transposed filter object <code>hd</code>, with coefficients given in the <code>s</code> matrix.</p> <p>Make this filter a fixed-point or single-precision filter by changing the value of the <code>Arithmetic</code> property for the filter <code>hd</code> as follows:</p> <ul style="list-style-type: none"><li>• To change to single-precision filtering, enter <pre>set(hd,'arithmetic','single');</pre></li><li>• To change to fixed-point filtering, enter <pre>set(hd,'arithmetic','fixed');</pre></li></ul> <p>For more information about the property <code>Arithmetic</code>, refer to .</p> <p><code>hd = dfilt.df1tsos(b1,a1,b2,a2,...)</code> returns a discrete-time, second-order section, direct-form I, transposed filter object <code>hd</code>, with coefficients for the first section given in the <code>b1</code> and <code>a1</code> vectors, for the second section given in the <code>b2</code> and <code>a2</code> vectors, etc.</p> <p><code>hd = dfilt.df1tsos(...,g)</code> includes a gain vector <code>g</code>. The elements of <code>g</code> are the gains for each section. The maximum length of <code>g</code> is the number of sections plus one. If <code>g</code> is not specified, all gains default to one.</p> <p><code>hd = dfilt.df1tsos</code> returns a default, discrete-time, second-order section, direct-form I, transposed filter object, <code>hd</code>. This filter passes the input through to the output unchanged.</p>


---

**Note** The leading coefficient of the denominator `a(1)` cannot be 0. To allow you to change the arithmetic setting to `fixed` or `single`, `a(1)` must be equal to 1.

---

## Fixed-Point Filter Structure

The following figure shows the signal flow for the direct-form I transposed filter implemented using second-order sections by `dfilt.df1tsos`. To help you see how the filter processes the coefficients, input, and states of the filter, as well as numerical operations, the figure includes the locations of the formatting objects within the signal flow.



## Notes About the Signal Flow Diagram

To help you understand where and how the filter performs fixed-point arithmetic during filtering, the figure shows various labels associated with data and functional elements in the filter. The following table describes each label in the signal flow and relates the label to the filter properties that are associated with it.

The labels use a common format — a prefix followed by the letters “frmt” (format). In this use, “frmt” means the word length and fraction length associated with the filter part referred to by the prefix.

For example, the InputFrmt label refers to the word length and fraction length used to interpret the data input to the filter. The format properties InputWordLength and InputFracLength (as shown in the table) store the word length and the fraction length in bits. Or consider NumFrmt, which refers to the word and fraction lengths (CoeffWordLength, NumFracLength) associated with representing filter numerator coefficients.

<b>Signal Flow Label</b>	<b>Corresponding Word Length Property</b>	<b>Corresponding Fraction Length Property</b>	<b>Related Properties</b>
DenAccumFrmt	AccumWordLength	DenAccumFracLength	AccumMode, CastBeforeSum
DenFrmt	CoeffWordLength	DenFracLength	CoeffAutoScale, Signed, Denominator
DenProdFrmt	CoeffWordLength	DenProdFracLength	ProductMode, ProductWordLength
DenStateFrmt	DenStateWordLength	DenStateFracLength	CastBeforeSum, States
InputFrmt	InputWordLength	InputFracLength	None
MultiplicandFrmt	Multiplicand-WordLength	Multiplicand-FracLength	CastBeforeSum
NumAccumFrmt	AccumWordLength	NumAccumFracLength	AccumMode, CastBeforeSum
NumFrmt	CoeffWordLength	NumFracLength	CoeffAutoScale, Signed, Numerator
NumProdFrmt	CoeffWordLength	NumProdFracLength	ProductWordLength, ProductMode
NumStateFrmt	NumStateWordLength	NumStateFracLength	States
OutputFrmt	OutputWordLength	OutputFracLength	OutputMode
ScaleValueFrmt	CoeffWordLength	ScaleValue-FracLength	CoeffAutoScale, ScaleValues

Most important is the label position in the diagram, which identifies where the format applies.

As one example, look at the label DenProdFrmt, which always follows a denominator coefficient multiplication element in the signal flow. The label indicates that denominator coefficients leave the multiplication element with the word length and fraction length associated with product operations that include denominator coefficients. From reviewing the table, you see that the DenProdFrmt refers to the properties ProdWordLength, ProductMode and DenProdFracLength that fully define the denominator format after multiply (or product) operations.

## Properties

In this table you see the properties associated with SOS implementation of transposed direct-form I `dfilt` objects.

---

**Note** The table lists all the properties that a filter can have. Many of the properties are dynamic, meaning they exist only in response to the settings of other properties. You might not see all of the listed properties all the time. To view all the properties for a filter at any time, use

```
get(hd)
```

where `hd` is a filter.

---

For further information about the properties of this filter or any `dfilt` object, refer to “Fixed-Point Filter Properties” on page 8-2.

Property Name	Brief Description
AccumMode	Determines how the accumulator outputs stored values. Choose from full precision ( <code>FullPrecision</code> ), or whether to keep the most significant bits ( <code>KeepMSB</code> ) or least significant bits ( <code>KeepLSB</code> ) when output results need shorter word length than the accumulator supports. To let you set the word length and the precision (the fraction length) used by the output from the accumulator, set <code>AccumMode</code> to <code>SpecifyPrecision</code> .
AccumWordLength	Sets the word length used to store data in the accumulator/buffer.
Arithmetic	Defines the arithmetic the filter uses. Gives you the options <code>double</code> , <code>single</code> , and <code>fixed</code> . In short, this property defines the operating mode for your filter.
CastBeforeSum	Specifies whether to cast numeric data to the appropriate accumulator format (as shown in the signal flow diagrams) before performing sum operations.
CoeffAutoScale	Specifies whether the filter automatically chooses the proper fraction length to represent filter coefficients without overflowing. Turning this off by setting the value to <code>false</code> enables you to change the <code>NumFracLength</code> and <code>DenFracLength</code> properties to specify the precision used.

<b>Property Name</b>	<b>Brief Description</b>
CoeffWordLength	Specifies the word length to apply to filter coefficients.
DenAccumFracLength	Specifies the fraction length used to interpret data in the accumulator used to hold the results of sum operations. You can change the value for this property when you set AccumMode to SpecifyPrecision.
DenFracLength	Set the fraction length the filter uses to interpret denominator coefficients. DenFracLength is always available, but it is read-only until you set CoeffAutoScale to false.
DenProdFracLength	Specifies how the filter algorithm interprets the results of product operations involving denominator coefficients. You can change this property value when you set ProductMode to SpecifyPrecision.
DenStateFracLength	Specifies the fraction length used to interpret the states associated with denominator coefficients in the filter.
FilterStructure	Describes the signal flow for the filter object, including all of the active elements that perform operations during filtering—gains, delays, sums, products, and input/output.
InputFracLength	Specifies the fraction length the filter uses to interpret input data.

<b>Property Name</b>	<b>Brief Description</b>
InputWordLength	Specifies the word length applied to interpret input data.
MultiplicandFracLength	Sets the fraction length for values (multiplicands) used in multiply operations in the filter.
MultiplicandWordLength	Sets the word length applied to the values input to a multiply operation (the multiplicands)
NumAccumFracLength	Specifies how the filter algorithm interprets the results of addition operations involving numerator coefficients. You can change the value of this property after you set AccumMode to SpecifyPrecision.
Numerator	Holds the numerator coefficient values for the filter.
NumProdFracLength	Specifies how the filter algorithm interprets the results of product operations involving numerator coefficients. Available to be changed when you set ProductMode to SpecifyPrecision.
NumStateFracLength	For IIR filters, this defines the binary point location applied to the numerator states of the filter. Specifies the fraction length used to interpret the states associated with numerator coefficient operations in the filter.

Property Name	Brief Description
NumStateWordLength	For IIR filters, this defines the word length applied to the numerator states of the filter. Specifies the word length used to interpret the states associated with numerator coefficient operations in the filter.
OptimizeScaleValues	When true, the filter skips multiplication-by-one scaling. When false, the filter performs multiplication-by-one scaling.
OutputFracLength	Determines how the filter interprets the filter output data. You can change the value of OutputFracLength when you set OutputMode to SpecifyPrecision.
OutputMode	Sets the mode the filter uses to scale the filtered data for output. You have the following choices: <ul style="list-style-type: none"><li>• <b>AvoidOverflow</b> — directs the filter to set the output data word length and fraction length to avoid causing the data to overflow.</li><li>• <b>BestPrecision</b> — directs the filter to set the output data word length and fraction length to maximize the precision in the output data.</li><li>• <b>SpecifyPrecision</b> — lets you set the word and fraction lengths used by the output data from filtering.</li></ul>

Property Name	Brief Description
OutputWordLength	Determines the word length used for the output data.
OverflowMode	Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either <b>saturate</b> (limit the output to the largest positive or negative representable value) or <b>wrap</b> (set overflowing values to the nearest representable value using modular arithmetic). The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow—they maintain full precision.
ProductMode	Determines how the filter handles the output of product operations. Choose from full precision ( <b>FullPrecision</b> ), or whether to keep the most significant bit ( <b>KeepMSB</b> ) or least significant bit ( <b>KeepLSB</b> ) in the result when you need to shorten the data words. For you to be able to set the precision (the fraction length) used by the output from the multiplies, you set <b>ProductMode</b> to <b>SpecifyPrecision</b> .

Property Name	Brief Description
ProductWordLength	Specifies the word length to use for multiplication operation results. This property becomes writable (you can change the value) when you set ProductMode to SpecifyPrecision.
PersistentMemory	Specifies whether to reset the filter states and memory before each filtering operation. Lets you decide whether your filter retains states from previous filtering runs. False is the default setting.
RoundMode	Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths). <ul style="list-style-type: none"><li>• <code>ceil</code> - Round toward positive infinity.</li><li>• <code>convergent</code> - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.</li><li>• <code>fix</code> - Round toward zero.</li><li>• <code>floor</code> - Round toward negative infinity.</li><li>• <code>nearest</code> - Round toward nearest. Ties round toward positive infinity.</li></ul>

Property Name	Brief Description
	<ul style="list-style-type: none"><li>• round - Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.</li></ul> <p>The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always round. Finally, products never overflow — they maintain full precision.</p>
ScaleValueFracLength	Scale values work with SOS filters. Setting this property controls how your filter interprets the scale values by setting the fraction length. Only available when you disable AutoScaleMode by setting it to false.
ScaleValues	Scaling for the filter objects in SOS filters.
Signed	Specifies whether the filter uses signed or unsigned fixed-point coefficients. Only coefficients reflect this property setting.

Property Name	Brief Description
SosMatrix	Holds the filter coefficients as property values. Displays the matrix in the format [sections x coefficients/sectiondatatype]. A [15x6 double] SOS matrix represents a filter with 6 coefficients per section and 15 sections, using data type double to represent the coefficients.
StateAutoScale	Setting autoscaling for filter states to true reduces the possibility of overflows occurring during fixed-point operations. Set to false, StateAutoScale lets the filter select the fraction length to limit the overflow potential.
States	This property contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions.
StateWordLength	Sets the word length used to represent the filter states.

## Examples

With the following code, this example specifies a second-order section, direct-form I transposed `dfilt` object for a filter. Then convert the filter to fixed-point operation.

```
b = [0.3 0.6 0.3];  
a = [1 0 0.2];  
hd = dfilt.df1tsos(b,a);  
set(hd,'arithmetic','fixed')
```

**See Also**

[dfilt](#) | [dfilt.df1sos](#) | [dfilt.df2sos](#) | [dfilt.df2tsos](#)

# dfilt.df2

---

**Purpose** Discrete-time, direct-form II filter

**Syntax** Refer to `dfilt.df2` in Signal Processing Toolbox documentation.

**Description** `hd = dfilt.df2(b,a)` returns a discrete-time, direct-form II filter object `hd`, with numerator coefficients `b` and denominator coefficients `a`.

Make this filter a fixed-point or single-precision filter by changing the value of the `Arithmetic` property for the filter `hd` as follows:

- To change to single-precision filtering, enter

```
set(hd,'arithmetic','single');
```

- To change to fixed-point filtering, enter

```
set(hd,'arithmetic','fixed');
```

For more information about the property `Arithmetic`, refer to “`Arithmetic`” on page 8-19.

`hd = dfilt.df2` returns a default, discrete-time, direct-form II filter object `hd`, with `b = 1` and `a = 1`. This filter passes the input through to the output unchanged.


---

**Note** The leading coefficient of the denominator `a(1)` cannot be 0. To allow you to change the arithmetic setting to `fixed` or `single`, `a(1)` must be equal to 1.

---

## Fixed-Point Filter Structure

The following figure shows the signal flow for the direct-form II filter implemented by `dfilt.df2`. To help you see how the filter processes the coefficients, input, and states of the filter, as well as numerical operations, the figure includes the locations of the formatting objects within the signal flow.



### Notes About the Signal Flow Diagram

To help you understand where and how the filter performs fixed-point arithmetic during filtering, the figure shows various labels associated with data and functional elements in the filter. The following table describes each label in the signal flow and relates the label to the filter properties that are associated with it.

The labels use a common format — a prefix followed by the letters “frmt” (format). In this use, “frmt” means the word length and fraction length associated with the filter part referred to by the prefix.

For example, the InputFrmt label refers to the word length and fraction length used to interpret the data input to the filter. The format properties InputWordLength and InputFracLength (as shown in the table) store the word length and the fraction length in bits. Or consider NumFrmt, which refers to the word and fraction lengths (CoeffWordLength, NumFracLength) associated with representing filter numerator coefficients.

<b>Signal Flow Label</b>	<b>Corresponding Word Length Property</b>	<b>Corresponding Fraction Length Property</b>	<b>Related Properties</b>
DenAccumFrmt	AccumWordLength	DenAccumFracLength	AccumMode, CastBeforeSum
DenFrmt	CoeffWordLength	DenFracLength	CoeffAutoScale, Signed, Denominator
DenProdFrmt	CoeffWordLength	DenProdFracLength	ProductMode, ProductWordLength
InputFrmt	InputWordLength	InputFracLength	None
NumAccumFrmt	AccumWordLength	NumAccumFracLength	AccumMode, CastBeforeSum
NumFrmt	CoeffWordLength	NumFracLength	CoeffAutoScale, Signed, Numerator
NumProdFrmt	CoeffWordLength	NumProdFracLength	ProductWordLength, ProductMode
OutputFrmt	OutputWordLength	OutputFracLength	OutputMode
StateFrmt	StateWordLength	StateFracLength	States

Most important is the label position in the diagram, which identifies where the format applies.

As one example, look at the label DenProdFrmt, which always follows a denominator coefficient multiplication element in the signal flow. The label indicates that denominator coefficients leave the multiplication element with the word length and fraction length associated with product operations that include denominator coefficients. From reviewing the table, you see that the DenProdFrmt refers to the properties ProdWordLength, ProductMode and DenProdFracLength that fully define the denominator format after multiply (or product) operations.

## Properties

In this table you see the properties associated with the df2 implementation of dfilt objects.

---

**Note** The table lists all the properties that a filter can have. Many of the properties are dynamic, meaning they exist only in response to the settings of other properties. You might not see all of the listed properties all the time. To view all the properties for a filter at any time, use

```
get(hd)
```

where `hd` is a filter.

---

For further information about the properties of this filter or any dfilt object, refer to “Fixed-Point Filter Properties” on page 8-2.

Property Name	Brief Description
AccumMode	Determines how the accumulator outputs stored values. Choose from full precision ( <code>FullPrecision</code> ), or whether to keep the most significant bits ( <code>KeepMSB</code> ) or least significant bits ( <code>KeepLSB</code> ) when output results need shorter word length than the accumulator supports. To let you set the word length and the precision (the fraction length) used by the output from the accumulator, set <code>AccumMode</code> to <code>SpecifyPrecision</code> .
AccumWordLength	Sets the word length used to store data in the accumulator/buffer.
Arithmetic	Defines the arithmetic the filter uses. Gives you the options <code>double</code> , <code>single</code> , and <code>fixed</code> . In short, this property defines the operating mode for your filter.

<b>Property Name</b>	<b>Brief Description</b>
CastBeforeSum	Specifies whether to cast numeric data to the appropriate accumulator format (as shown in the signal flow diagrams) before performing sum operations.
CoeffAutoScale	Specifies whether the filter automatically chooses the proper fraction length to represent filter coefficients without overflowing. Turning this off by setting the value to <code>false</code> enables you to change the <code>NumFracLength</code> and <code>DenFracLength</code> properties to specify the precision used.
CoeffWordLength	Specifies the word length to apply to filter coefficients.
DenAccumFracLength	Specifies the fraction length used to interpret data in the accumulator used to hold the results of sum operations. You can change the value for this property when you set <code>AccumMode</code> to <code>SpecifyPrecision</code> .
DenFracLength	Set the fraction length the filter uses to interpret denominator coefficients. <code>DenFracLength</code> is always available, but it is read-only until you set <code>CoeffAutoScale</code> to <code>false</code> .
Denominator	Holds the denominator coefficients for IIR filters.
DenProdFracLength	Specifies how the filter algorithm interprets the results of product operations involving denominator coefficients. You can change this property value when you set <code>ProductMode</code> to <code>SpecifyPrecision</code> .

<b>Property Name</b>	<b>Brief Description</b>
FilterStructure	Describes the signal flow for the filter object, including all of the active elements that perform operations during filtering — gains, delays, sums, products, and input/output.
InputFracLength	Specifies the fraction length the filter uses to interpret input data.
InputWordLength	Specifies the word length applied to interpret input data.
NumAccumFracLength	Specifies how the filter algorithm interprets the results of addition operations involving numerator coefficients. You can change the value of this property after you set AccumMode to SpecifyPrecision.
Numerator	Holds the numerator coefficient values for the filter.
NumFracLength	Sets the fraction length used to interpret the value of numerator coefficients.
NumProdFracLength	Specifies how the filter algorithm interprets the results of product operations involving numerator coefficients. Available to be changed when you set ProductMode to SpecifyPrecision.
OutputFracLength	Determines how the filter interprets the filter output data. You can change the value of OutputFracLength when you set OutputMode to SpecifyPrecision.

Property Name	Brief Description
OutputMode	<p>Sets the mode the filter uses to scale the filtered data for output. You have the following choices:</p> <ul style="list-style-type: none"><li>• <b>AvoidOverflow</b> — directs the filter to set the output data word length and fraction length to avoid causing the data to overflow.</li><li>• <b>BestPrecision</b> — directs the filter to set the output data word length and fraction length to maximize the precision in the output data.</li><li>• <b>SpecifyPrecision</b> — lets you set the word and fraction lengths used by the output data from filtering.</li></ul>
OutputWordLength	<p>Determines the word length used for the output data.</p>
OverflowMode	<p>Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either <b>saturate</b> (limit the output to the largest positive or negative representable value) or <b>wrap</b> (set overflowing values to the nearest representable value using modular arithmetic). The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow—they maintain full precision.</p>

Property Name	Brief Description
ProductMode	<p>Determines how the filter handles the output of product operations. Choose from full precision (<code>FullPrecision</code>), or whether to keep the most significant bit (<code>KeepMSB</code>) or least significant bit (<code>KeepLSB</code>) in the result when you need to shorten the data words. For you to be able to set the precision (the fraction length) used by the output from the multiplies, you set <code>ProductMode</code> to <code>SpecifyPrecision</code>.</p>
PersistentMemory	<p>Specifies whether to reset the filter states and memory before each filtering operation. Lets you decide whether your filter retains states from previous filtering runs. <code>False</code> is the default setting.</p>
RoundMode	<p>Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths).</p> <ul style="list-style-type: none"><li>• <code>ceil</code> - Round toward positive infinity.</li><li>• <code>convergent</code> - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.</li><li>• <code>fix</code> - Round toward zero.</li><li>• <code>floor</code> - Round toward negative infinity.</li><li>• <code>nearest</code> - Round toward nearest. Ties round toward positive infinity.</li><li>• <code>round</code> - Round toward nearest. Ties round toward negative infinity for negative</li></ul>

## dfilt.df2

Property Name	Brief Description
	numbers, and toward positive infinity for positive numbers.  The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always round. Finally, products never overflow — they maintain full precision.
Signed	Specifies whether the filter uses signed or unsigned fixed-point coefficients. Only coefficients reflect this property setting.
StateFracLength	When you set <code>StateAutoScale</code> to <code>false</code> , you enable the <code>StateFracLength</code> property that lets you set the fraction length applied to interpret the filter states.
States	This property contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions.
StateWordLength	Sets the word length used to represent the filter states.

### Examples

Specify a second-order direct-form II filter structure for a `dfilt` object, `hd`, with the following code:

```
b = [0.3 0.6 0.3];  
a = [1 0 0.2];  
hd = dfilt.df2(b,a);  
% Change filter to fixed-point  
set(hd,'arithmetic','fixed')
```

### See Also

`dfilt` | `dfilt.df1` | `dfilt.df1t` | `dfilt.df2t`

**Purpose**

Discrete-time, SOS, direct-form II filter

**Syntax**

Refer to `dfilt.df2sos` in Signal Processing Toolbox documentation.

**Description**

`hd = dfilt.df2sos(s)` returns a discrete-time, second-order section, direct-form II filter object `hd`, with coefficients given in the `s` matrix.

Make this filter a fixed-point or single-precision filter by changing the value of the `Arithmetic` property for the filter `hd` as follows:

- To change to single-precision filtering, enter

```
set(hd,'arithmetic','single');
```

- To change to fixed-point filtering, enter

```
set(hd,'arithmetic','fixed');
```

For more information about the property `Arithmetic`, refer to “Arithmetic” on page 8-19.

`hd = dfilt.df2sos(b1,a1,b2,a2,...)` returns a discrete-time, second-order section, direct-form II object, `hd`, with coefficients for the first section given in the `b1` and `a1` vectors, for the second section given in the `b2` and `a2` vectors, etc.

`hd = dfilt.df2sos(...,g)` includes a gain vector `g`. The elements of `g` are the gains for each section. The maximum length of `g` is the number of sections plus one. If `g` is not specified, all gains default to one.

`hd = dfilt.df2sos` returns a default, discrete-time, second-order section, direct-form II filter object, `hd`. This filter passes the input through to the output unchanged.


---

**Note** The leading coefficient of the denominator `a(1)` cannot be 0. To allow you to change the arithmetic setting to `fixed` or `single`, `a(1)` must be equal to 1.

---

## Fixed-Point Filter Structure

The figure below shows the signal flow for the direct-form II filter implemented with second-order sections by `dfilt.df2sos`. To help you see how the filter processes the coefficients, input, and states of the filter, as well as numerical operations, the figure includes the locations of the formatting objects within the signal flow.



## Notes About the Signal Flow Diagram

To help you understand where and how the filter performs fixed-point arithmetic during filtering, the figure shows various labels associated with data and functional elements in the filter. The following table describes each label in the signal flow and relates the label to the filter properties that are associated with it.

The labels use a common format — a prefix followed by the letters “frmt” (format). In this use, “frmt” means the word length and fraction length associated with the filter part referred to by the prefix.

For example, the `InputFrmt` label refers to the word length and fraction length used to interpret the data input to the filter. The `frmt` properties `InputWordLength` and `InputFracLength` (as shown in the table) store the word length and the fraction length in bits. Or consider `NumFrmt`, which refers to the word and fraction lengths

(CoeffWordLength, NumFracLength) associated with representing filter numerator coefficients.

<b>Signal Flow Label</b>	<b>Corresponding Word Length Property</b>	<b>Corresponding Fraction Length Property</b>	<b>Related Properties</b>
DenAccumFrmt	AccumWordLength	DenAccumFracLength	AccumMode, CastBeforeSum
DenFrmt	CoeffWordLength	DenFracLength	CoeffAutoScale, Signed, sosMatrix
DenProdFrmt	CoeffWordLength	DenProdFracLength	ProductMode, ProductWordLength, sosMatrix
InputFrmt	InputWordLength	InputFracLength	None
NumAccumFrmt	AccumWordLength	NumAccumFracLength	AccumMode, CastBeforeSum
NumFrmt	CoeffWordLength	NumFracLength	CoeffAutoScale, Signed, sosMatrix
NumProdFrmt	CoeffWordLength	NumProdFracLength	ProductWordLength, ProductMode
OutputFrmt	OutputWordLength	OutputFracLength	OutputMode
ScaleValueFrmat	CoeffWordLength	ScaleValue-FracLength	CoeffAutoScale, ScaleValues
SectionInputFormt	SectionInput-WordLength	SectionInput-FracLength	SectionInput-AutoScale
SectionOutputFrmt	SectionOutput-WordLength	SectionOutput-FracLength	SectionOutput-AutoScale
StateFrmt	StateWordLength	StateFracLength	CastBeforeSum, States

Most important is the label position in the diagram, which identifies where the format applies.

As one example, look at the label DenProdFrmt, which always follows a denominator coefficient multiplication element in the signal flow. The label indicates that denominator coefficients leave the multiplication element with the word length and fraction length associated with product operations that include denominator coefficients. From reviewing the table, you see that the DenProdFrmt refers to the properties ProdWordLength, ProductMode and DenProdFracLength that fully define the denominator format after multiply (or product) operations.

## Properties

In this table you see the properties associated with second-order section implementation of direct-form II `dfilt` objects.

---

**Note** The table lists all the properties that a filter can have. Many of the properties are dynamic, meaning they exist only in response to the settings of other properties. You might not see all of the listed properties all the time. To view all the properties for a filter at any time, use

```
get(hd)
```

where `hd` is a filter.

---

For further information about the properties of this filter or any `dfilt` object, refer to “Fixed-Point Filter Properties” on page 8-2.

Property Name	Brief Description
AccumMode	Determines how the accumulator outputs stored values. Choose from full precision (FullPrecision), or whether to keep the most significant bits (KeepMSB) or least significant bits (KeepLSB) when output results need shorter word length than the accumulator supports. To let you set the word length and the precision (the fraction length) used by the output from the accumulator, set AccumMode to SpecifyPrecision.
AccumWordLength	Sets the word length used to store data in the accumulator/buffer.
Arithmetic	Defines the arithmetic the filter uses. Gives you the options double, single, and fixed. In short, this property defines the operating mode for your filter.
CastBeforeSum	Specifies whether to cast numeric data to the appropriate accumulator format (as shown in the signal flow diagrams) before performing sum operations.
CoeffAutoScale	Specifies whether the filter automatically chooses the proper fraction length to represent filter coefficients without overflowing. Turning this off by setting the value to false enables you to change the NumFracLength and DenFracLength properties to specify the precision used.
CoeffWordLength	Specifies the word length to apply to filter coefficients.

<b>Property Name</b>	<b>Brief Description</b>
DenAccumFracLength	Specifies the fraction length used to interpret data in the accumulator used to hold the results of sum operations. You can change the value for this property when you set AccumMode to SpecifyPrecision.
DenFracLength	Set the fraction length the filter uses to interpret denominator coefficients. DenFracLength is always available, but it is read-only until you set CoeffAutoScale to false.
DenProdFracLength	Specifies how the filter algorithm interprets the results of product operations involving denominator coefficients. You can change this property value when you set ProductMode to SpecifyPrecision.
FilterStructure	Describes the signal flow for the filter object, including all of the active elements that perform operations during filtering—gains, delays, sums, products, and input/output.
InputFracLength	Specifies the fraction length the filter uses to interpret input data.
InputWordLength	Specifies the word length applied to interpret input data.
NumAccumFracLength	Specifies how the filter algorithm interprets the results of addition operations involving numerator coefficients. You can change the value of this property after you set AccumMode to SpecifyPrecision.
NumFracLength	Sets the fraction length used to interpret the value of numerator coefficients.

Property Name	Brief Description
NumProdFracLength	Specifies how the filter algorithm interprets the results of product operations involving numerator coefficients. Available to be changed when you set ProductMode to SpecifyPrecision.
OptimizeScaleValues	When true, the filter skips multiplication-by-one scaling. When false, the filter performs multiplication-by-one scaling.
OutputFracLength	Determines how the filter interprets the filter output data. You can change the value of OutputFracLength when you set OutputMode to SpecifyPrecision.
OutputMode	<p>Sets the mode the filter uses to scale the filtered data for output. You have the following choices:</p> <ul style="list-style-type: none"> <li>• <b>AvoidOverflow</b> — directs the filter to set the output data word length and fraction length to avoid causing the data to overflow.</li> <li>• <b>BestPrecision</b> — directs the filter to set the output data word length and fraction length to maximize the precision in the output data.</li> <li>• <b>SpecifyPrecision</b> — lets you set the word and fraction lengths used by the output data from filtering.</li> </ul>
OutputWordLength	Determines the word length used for the output data.

Property Name	Brief Description
OverflowMode	Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either <code>saturate</code> (limit the output to the largest positive or negative representable value) or <code>wrap</code> (set overflowing values to the nearest representable value using modular arithmetic). The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow — they maintain full precision.
ProductMode	Determines how the filter handles the output of product operations. Choose from full precision ( <code>FullPrecision</code> ), or whether to keep the most significant bit ( <code>KeepMSB</code> ) or least significant bit ( <code>KeepLSB</code> ) in the result when you need to shorten the data words. For you to be able to set the precision (the fraction length) used by the output from the multiplies, you set <code>ProductMode</code> to <code>SpecifyPrecision</code> .
ProductWordLength	Specifies the word length to use for multiplication operation results. This property becomes writable (you can change the value) when you set <code>ProductMode</code> to <code>SpecifyPrecision</code> .
PersistentMemory	Specifies whether to reset the filter states and memory before each filtering operation. Lets you decide whether your filter retains states from previous filtering runs. <code>False</code> is the default setting.

Property Name	Brief Description
RoundMode	<p>Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths).</p> <ul style="list-style-type: none"> <li>• <code>ceil</code> - Round toward positive infinity.</li> <li>• <code>convergent</code> - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.</li> <li>• <code>fix</code> - Round toward zero.</li> <li>• <code>floor</code> - Round toward negative infinity.</li> <li>• <code>nearest</code> - Round toward nearest. Ties round toward positive infinity.</li> <li>• <code>round</code> - Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.</li> </ul> <p>The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always round. Finally, products never overflow — they maintain full precision.</p>
ScaleValueFracLength	<p>Scale values work with SOS filters. Setting this property controls how your filter interprets the scale values by setting the fraction length. Only available when you disable <code>AutoScaleMode</code> by setting it to <code>false</code>.</p>

Property Name	Brief Description
ScaleValues	Scaling for the filter objects in SOS filters.
SectionInputAutoScale	Tells the filter whether to set the stage input data format to minimize the occurrence of overflow conditions.
SectionInputFracLength	Lets you set the fraction length for section inputs in SOS filters, if you set SectionInputAutoScale to false.
SectionInputWordLength	Lets you set the word length for section inputs in SOS filters, if you set SectionInputAutoScale to false.
SectionOutputAutoScale	Tells the filter whether to set the section output data format to minimize the occurrence of overflow conditions.
SectionOutputFracLength	Lets you set the fraction length for section outputs in SOS filters, if you set SectionOutputAutoScale to off.
SectionOutputWordLength	Lets you set the word length for section outputs in SOS filters, if you set SectionOutputAutoScale to false.
Signed	Specifies whether the filter uses signed or unsigned fixed-point coefficients. Only coefficients reflect this property setting.
SosMatrix	Holds the filter coefficients as property values. Displays the matrix in the format [sections x coefficients/section datatype]. A [15x6 double] SOS matrix represents a filter with 6 coefficients per section and 15 sections, using data type double to represent the coefficients.

Property Name	Brief Description
StateFracLength	When you set StateAutoScale to false, you enable the StateFracLength property that lets you set the fraction length applied to interpret the filter states.
States	This property contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions.
StateWordLength	Sets the word length used to represent the filter states.

## Examples

Specify a second-order section, direct-form II `dfilt` object for a Butterworth filter converted to second-order sections, with the following code:

```
[z,p,k] = butter(30,0.5);
[s,g] = zp2sos(z,p,k);
hd = dfilt.df2sos(s,g);
% Convert filter to fixed-point
hd.arithmetic='fixed';
```

## See Also

`dfilt` | `dfilt.df1sos` | `dfilt.df1tsos` | `dfilt.df2tsos`

<b>Purpose</b>	Discrete-time, direct-form II transposed filter
<b>Syntax</b>	Refer to <code>dfilt.df2t</code> in Signal Processing Toolbox documentation.
<b>Description</b>	<p><code>hd = dfilt.df2t(b,a)</code> returns a discrete-time, direct-form II transposed filter object <code>hd</code>, with numerator coefficients <code>b</code> and denominator coefficients <code>a</code>.</p> <p>Make this filter a fixed-point or single-precision filter by changing the value of the <code>Arithmetic</code> property for the filter <code>hd</code> as follows:</p> <ul style="list-style-type: none"><li>• To change to single-precision filtering, enter <pre>set(hd,'arithmetic','single');</pre></li><li>• To change to fixed-point filtering, enter <pre>set(hd,'arithmetic','fixed');</pre></li></ul> <p>For more information about the property <code>Arithmetic</code>, refer to “Arithmetic” on page 8-19.</p> <p><code>hd = dfilt.df2t</code> returns a default, discrete-time, direct-form II transposed filter object <code>hd</code>, with <code>b = 1</code> and <code>a = 1</code>. This filter passes the input through to the output unchanged.</p>


---

**Note** The leading coefficient of the denominator `a(1)` cannot be 0. To allow you to change the arithmetic setting to `fixed` or `single`, `a(1)` must be equal to 1.

---

## Fixed-Point Filter Structure

The following figure shows the signal flow for the direct-form II transposed filter implemented by `dfilt.df2t`. To help you see how the filter processes the coefficients, input, and states of the filter, as well as numerical operations, the figure includes the locations of the formatting objects within the signal flow.



### Notes About the Signal Flow Diagram

To help you understand where and how the filter performs fixed-point arithmetic during filtering, the figure shows various labels associated with data and functional elements in the filter. The following table describes each label in the signal flow and relates the label to the filter properties that are associated with it.

The labels use a common format — a prefix followed by the letters “frmt.” In this use, “frmt” means the word length and fraction length associated with the filter part referred to by the prefix.

For example, the InputFrm label refers to the word length and fraction length used to interpret the data input to the filter. The

format properties `InputWordLength` and `InputFracLength` (as shown in the table) store the word length and the fraction length in bits. Or consider `NumFrmt`, which refers to the word and fraction lengths (`CoeffWordLength`, `NumFracLength`) associated with representing filter numerator coefficients.

<b>Signal Flow Label</b>	<b>Corresponding Word Length Property</b>	<b>Corresponding Fraction Length Property</b>	<b>Related Properties</b>
DenAccumFrmt	AccumWordLength	DenAccumFracLength	AccumMode, CastBeforeSum
DenFrmt	CoeffWordLength	DenFracLength	CoeffAutoScale, Signed, Denominator
DenProdFrmt	CoeffWordLength	DenProdFracLength	ProductMode, ProductWordLength
InputFrmt	InputWordLength	InputFracLength	None
NumAccumFrmt	AccumWordLength	NumAccumFracLength	AccumMode, CastBeforeSum
NumFrmt	CoeffWordLength	NumFracLength	CoeffAutoScale, Signed, Numerator
NumProdFrmt	CoeffWordLength	NumProdFracLength	ProductWordLength, ProductMode
OutputFrmt	OutputWordLength	OutputFracLength	None
StateFrmt	StateWordLength	StateFracLength	States

Most important is the label position in the diagram, which identifies where the format applies.

As one example, look at the label `DenProdFrmt`, which always follows a denominator coefficient multiplication element in the signal flow. The label indicates that denominator coefficients leave the multiplication element with the word length and fraction length associated with product operations that include denominator coefficients. From reviewing the table, you see that the `DenProdFrmt` refers to the

properties `ProdWordLength`, `ProductMode` and `DenProdFracLength` that fully define the denominator format after multiply (or product) operations.

## Properties

In this table you see the properties associated with `df2t` implementation of `dfilt` objects.

---

**Note** The table lists all the properties that a filter can have. Many of the properties are dynamic, meaning they exist only in response to the settings of other properties. You might not see all of the listed properties all the time. To view all the properties for a filter at any time, use

`get(hd)`

where `hd` is a filter.

---

For further information about the properties of this filter or any `dfilt` object, refer to “Fixed-Point Filter Properties” on page 8-2.

Property Name	Brief Description
<code>AccumMode</code>	Determines how the accumulator outputs stored values. Choose from full precision ( <code>FullPrecision</code> ), or whether to keep the most significant bits ( <code>KeepMSB</code> ) or least significant bits ( <code>KeepLSB</code> ) when output results need shorter word length than the accumulator supports. To let you set the word length and the precision (the fraction length) used by the output from the accumulator, set <code>AccumMode</code> to <code>SpecifyPrecision</code> .
<code>AccumWordLength</code>	Sets the word length used to store data in the accumulator/buffer.

<b>Property Name</b>	<b>Brief Description</b>
Arithmetic	Defines the arithmetic the filter uses. Gives you the options <code>double</code> , <code>single</code> , and <code>fixed</code> . In short, this property defines the operating mode for your filter.
CastBeforeSum	Specifies whether to cast numeric data to the appropriate accumulator format (as shown in the signal flow diagrams) before performing sum operations.
CoeffAutoScale	Specifies whether the filter automatically chooses the proper fraction length to represent filter coefficients without overflowing. Turning this off by setting the value to <code>false</code> enables you to change the <code>NumFracLength</code> and <code>DenFracLength</code> properties to specify the precision used.
CoeffWordLength	Specifies the word length to apply to filter coefficients.
DenAccumFracLength	Specifies the fraction length used to interpret data in the accumulator used to hold the results of sum operations. You can change the value for this property when you set <code>AccumMode</code> to <code>SpecifyPrecision</code> .
DenFracLength	Set the fraction length the filter uses to interpret denominator coefficients. <code>DenFracLength</code> is always available, but it is read-only until you set <code>CoeffAutoScale</code> to <code>false</code> .
Denominator	Holds the denominator coefficients for IIR filters.

<b>Property Name</b>	<b>Brief Description</b>
DenProdFracLength	Specifies how the filter algorithm interprets the results of product operations involving denominator coefficients. You can change this property value when you set <code>ProductMode</code> to <code>SpecifyPrecision</code> .
FilterStructure	Describes the signal flow for the filter object, including all of the active elements that perform operations during filtering—gains, delays, sums, products, and input/output.
InputFracLength	Specifies the fraction length the filter uses to interpret input data.
InputWordLength	Specifies the word length applied to interpret input data.
NumAccumFracLength	Specifies how the filter algorithm interprets the results of addition operations involving numerator coefficients. You can change the value of this property after you set <code>AccumMode</code> to <code>SpecifyPrecision</code> .
Numerator	Holds the numerator coefficient values for the filter.
NumFracLength	Sets the fraction length used to interpret the value of numerator coefficients.
NumProdFracLength	Specifies how the filter algorithm interprets the results of product operations involving numerator coefficients. Available to be changed when you set <code>ProductMode</code> to <code>SpecifyPrecision</code> .
OutputFracLength	Determines how the filter interprets the filter output data.
OutputWordLength	Determines the word length used for the output data.

<b>Property Name</b>	<b>Brief Description</b>
OverflowMode	Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either <code>saturate</code> (limit the output to the largest positive or negative representable value) or <code>wrap</code> (set overflowing values to the nearest representable value using modular arithmetic). The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow — they maintain full precision.
ProductMode	Determines how the filter handles the output of product operations. Choose from full precision ( <code>FullPrecision</code> ), or whether to keep the most significant bit ( <code>KeepMSB</code> ) or least significant bit ( <code>KeepLSB</code> ) in the result when you need to shorten the data words. For you to be able to set the precision (the fraction length) used by the output from the multiplies, you set <code>ProductMode</code> to <code>SpecifyPrecision</code> .
ProductWordLength	Specifies the word length to use for multiplication operation results. This property becomes writable (you can change the value) when you set <code>ProductMode</code> to <code>SpecifyPrecision</code> .
PersistentMemory	Specifies whether to reset the filter states and memory before each filtering operation. Lets you decide whether your filter retains states from previous filtering runs. <code>False</code> is the default setting.

Property Name	Brief Description
RoundMode	<p>Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths).</p> <ul style="list-style-type: none"><li>• <code>ceil</code> - Round toward positive infinity.</li><li>• <code>convergent</code> - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.</li><li>• <code>fix</code> - Round toward zero.</li><li>• <code>floor</code> - Round toward negative infinity.</li><li>• <code>nearest</code> - Round toward nearest. Ties round toward positive infinity.</li><li>• <code>round</code> - Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.</li></ul> <p>The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always round. Finally, products never overflow — they maintain full precision.</p>
Signed	<p>Specifies whether the filter uses signed or unsigned fixed-point coefficients. Only coefficients reflect this property setting.</p>

Property Name	Brief Description
StateAutoScale	Setting autoscaling for filter states to <code>true</code> reduces the possibility of overflows occurring during fixed-point operations. Set to <code>false</code> , <code>StateAutoScale</code> lets the filter select the fraction length to limit the overflow potential.
StateFracLength	When you set <code>StateAutoScale</code> to <code>false</code> , you enable the <code>StateFracLength</code> property that lets you set the fraction length applied to interpret the filter states.
States	This property contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions.
StateWordLength	Sets the word length used to represent the filter states.

## Examples

Create a fixed-point filter by specifying a second-order direct-form II transposed filter structure for a `dfilt` object, and then converting the double-precision arithmetic setting to fixed-point.

```
b = [0.3 0.6 0.3];  
a = [1 0 0.2];  
hd = dfilt.df2t(b,a);  
% Convert filter to fixed-point  
set(hd,'arithmetic','fixed')
```

## See Also

`dfilt` | `dfilt.df1` | `dfilt.df1t` | `dfilt.df2`

<b>Purpose</b>	Discrete-time, SOS direct-form II transposed filter
<b>Syntax</b>	Refer to <code>dfilt.df2tsos</code> in Signal Processing Toolbox documentation.
<b>Description</b>	<p><code>hd = dfilt.df2tsos(s)</code> returns a discrete-time, second-order section, direct-form II, transposed filter object <code>hd</code>, with coefficients given in the matrix <code>s</code>.</p> <p>Make this filter a fixed-point or single-precision filter by changing the value of the <code>Arithmetic</code> property for the filter <code>hd</code> as follows:</p> <ul style="list-style-type: none"><li>• To change to single-precision filtering, enter <pre>set(hd,'arithmetic','single');</pre></li><li>• To change to fixed-point filtering, enter <pre>set(hd,'arithmetic','fixed');</pre></li></ul> <p>For more information about the property <code>Arithmetic</code>, refer to “Arithmetic” on page 8-19.</p> <p><code>hd = dfilt.df2tsos(b1,a1,b2,a2,...)</code> returns a discrete-time, second-order section, direct-form II, transposed filter object <code>hd</code>, with coefficients for the first section given in the <code>b1</code> and <code>a1</code> vectors, for the second section given in the <code>b2</code> and <code>a2</code> vectors, etc.</p> <p><code>hd = dfilt.df2tsos(...,g)</code> includes a gain vector <code>g</code>. The elements of <code>g</code> are the gains for each section. The maximum length of <code>g</code> is the number of sections plus one. If <code>g</code> is not specified, all gains default to one.</p> <p><code>hd = dfilt.df2tsos</code> returns a default, discrete-time, second-order section, direct-form II, transposed filter object, <code>hd</code>. This filter passes the input through to the output unchanged.</p>


---

**Note** The leading coefficient of the denominator `a(1)` cannot be 0. To allow you to change the arithmetic setting to `fixed` or `single`, `a(1)` must be equal to 1.

---

## Fixed-Point Filter Structure

The figure below shows the signal flow for the second-order section transposed direct-form II filter implemented by `dfilt.df2tsos`. To help you see how the filter processes the coefficients, input, and states of the filter, as well as numerical operations, the figure includes the locations of the formatting objects within the signal flow.



## Notes About the Signal Flow Diagram

To help you understand where and how the filter performs fixed-point arithmetic during filtering, the figure shows various labels associated with data and functional elements in the filter. The following table describes each label in the signal flow and relates the label to the filter properties that are associated with it.

The labels use a common format — a prefix followed by the letters “frmt” (format). In this use, “frmt” indicates the word length and fraction length associated with the filter part referred to by the prefix.

For example, the InputFrmt label refers to the word length and fraction length used to interpret the data input to the filter. The format properties InputWordLength and InputFracLength (as shown in the table) store the word length and the fraction length in bits. Or consider NumFrmt, which refers to the word and fraction lengths (CoeffWordLength, NumFracLength) associated with representing filter numerator coefficients.

Signal Flow Label	Corresponding Word Length Property	Corresponding Fraction Length Property	Related Properties
DenAccumFrmt	AccumWordLength	DenAccumFracLength	AccumMode, CastBeforeSum
DenFrmt	CoeffWordLength	DenFracLength	CoeffAutoScale, Signed, Denominator
DenProdFrmt	CoeffWordLength	DenProdFracLength	ProductMode, ProductWordLength
InputFrmt	InputWordLength	InputFracLength	None
NumAccumFrmt	AccumWordLength	NumAccumFracLength	AccumMode, CastBeforeSum
NumFrmt	CoeffWordLength	NumFracLength	CoeffAutoScale, SignedNumerator

<b>Signal Flow Label</b>	<b>Corresponding Word Length Property</b>	<b>Corresponding Fraction Length Property</b>	<b>Related Properties</b>
NumProdFrmt	CoeffWordLength	NumProdFracLength	ProductWordLength, ProductMode
OutputFrmt	OutputWordLength	OutputFracLength	OutputMode
ScaleValueFrmt	CoeffWordLength	ScaleValueFracLength	CoeffAutoScale, ScaleValues
SectionInputFrmt	SectionInput-WordLength	SectionInput-FracLength	
SectionOutputFrmt	SectionOutput-WordLength	SectionOutput-FracLength	
StateFrmt	StateWordLength	StateFracLength	States

Most important is the label position in the diagram, which identifies where the format applies.

As one example, look at the label DenProdFrmt, which always follows a denominator coefficient multiplication element in the signal flow. The label indicates that denominator coefficients leave the multiplication element with the word length and fraction length associated with product operations that include denominator coefficients. From reviewing the table, you see that the DenProdFrmt refers to the properties ProdWordLength, ProductMode and DenProdFracLength that fully define the denominator format after multiply (or product) operations.

## Properties

In this table you see the properties associated with second-order section implementation of transposed direct-form II dfilt objects.

---

**Note** The table lists all the properties that a filter can have. Many of the properties are dynamic, meaning they exist only in response to the settings of other properties. You might not see all of the listed properties all the time. To view all the properties for a filter at any time, use

```
get(hd)
```

where `hd` is a filter.

---

For further information about the properties of this filter or any `dfilt` object, refer to “Fixed-Point Filter Properties” on page 8-2.

Property Name	Brief Description
AccumMode	Determines how the accumulator outputs stored values. Choose from full precision ( <code>FullPrecision</code> ), or whether to keep the most significant bits ( <code>KeepMSB</code> ) or least significant bits ( <code>KeepLSB</code> ) when output results need shorter word length than the accumulator supports. To let you set the word length and the precision (the fraction length) used by the output from the accumulator, set <code>AccumMode</code> to <code>SpecifyPrecision</code> .
AccumWordLength	Sets the word length used to store data in the accumulator/buffer.
Arithmetic	Defines the arithmetic the filter uses. Gives you the options <code>double</code> , <code>single</code> , and <code>fixed</code> . In short, this property defines the operating mode for your filter.
CastBeforeSum	Specifies whether to cast numeric data to the appropriate accumulator format (as shown in the signal flow diagrams) before performing sum operations.

## dfilt.df2tsos

---

<b>Property Name</b>	<b>Brief Description</b>
CoeffAutoScale	Specifies whether the filter automatically chooses the proper fraction length to represent filter coefficients without overflowing. Turning this off by setting the value to <code>false</code> enables you to change the <code>NumFracLength</code> and <code>DenFracLength</code> properties to specify the precision used.
CoeffWordLength	Specifies the word length to apply to filter coefficients.
DenAccumFracLength	Specifies the fraction length used to interpret data in the accumulator used to hold the results of sum operations. You can change the value for this property when you set <code>AccumMode</code> to <code>SpecifyPrecision</code> .
DenFracLength	Set the fraction length the filter uses to interpret denominator coefficients. <code>DenFracLength</code> is always available, but it is read-only until you set <code>CoeffAutoScale</code> to <code>false</code> .
DenProdFracLength	Specifies how the filter algorithm interprets the results of product operations involving denominator coefficients. You can change this property value when you set <code>ProductMode</code> to <code>SpecifyPrecision</code> .
FilterStructure	Describes the signal flow for the filter object, including all of the active elements that perform operations during filtering — gains, delays, sums, products, and input/output.
InputFracLength	Specifies the fraction length the filter uses to interpret input data.
InputWordLength	Specifies the word length applied to interpret input data.
NumAccumFracLength	Specifies how the filter algorithm interprets the results of addition operations involving numerator coefficients. You can change the value of this property after you set <code>AccumMode</code> to <code>SpecifyPrecision</code> .

Property Name	Brief Description
NumFracLength	Sets the fraction length used to interpret the value of numerator coefficients.
NumProdFracLength	Specifies how the filter algorithm interprets the results of product operations involving numerator coefficients. Available to be changed when you set ProductMode to SpecifyPrecision.
OptimizeScaleValues	When true, the filter skips multiplication-by-one scaling. When false, the filter performs multiplication-by-one scaling.
OutputFracLength	Determines how the filter interprets the filter output data. You can change the value of OutputFracLength when you set OutputMode to SpecifyPrecision.
OutputMode	<p>Sets the mode the filter uses to scale the filtered data for output. You have the following choices:</p> <ul style="list-style-type: none"> <li>• <b>AvoidOverflow</b> — directs the filter to set the output data word length and fraction length to avoid causing the data to overflow.</li> <li>• <b>BestPrecision</b> — directs the filter to set the output data word length and fraction length to maximize the precision in the output data.</li> <li>• <b>SpecifyPrecision</b> — lets you set the word and fraction lengths used by the output data from filtering.</li> </ul>
OutputWordLength	Determines the word length used for the output data.

Property Name	Brief Description
OverflowMode	Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either <code>saturate</code> (limit the output to the largest positive or negative representable value) or <code>wrap</code> (set overflowing values to the nearest representable value using modular arithmetic). The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow — they maintain full precision.
ProductMode	Determines how the filter handles the output of product operations. Choose from full precision ( <code>FullPrecision</code> ), or whether to keep the most significant bit ( <code>KeepMSB</code> ) or least significant bit ( <code>KeepLSB</code> ) in the result when you need to shorten the data words. For you to be able to set the precision (the fraction length) used by the output from the multiplies, you set <code>ProductMode</code> to <code>SpecifyPrecision</code> .
ProductWordLength	Specifies the word length to use for multiplication operation results. This property becomes writable (you can change the value) when you set <code>ProductMode</code> to <code>SpecifyPrecision</code> .
PersistentMemory	Specifies whether to reset the filter states and memory before each filtering operation. Lets you decide whether your filter retains states from previous filtering runs. <code>False</code> is the default setting.

Property Name	Brief Description
RoundMode	<p>Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths).</p> <ul style="list-style-type: none"> <li>• <code>ceil</code> - Round toward positive infinity.</li> <li>• <code>convergent</code> - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.</li> <li>• <code>fix</code> - Round toward zero.</li> <li>• <code>floor</code> - Round toward negative infinity.</li> <li>• <code>nearest</code> - Round toward nearest. Ties round toward positive infinity.</li> <li>• <code>round</code> - Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.</li> </ul> <p>The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always round. Finally, products never overflow — they maintain full precision.</p>
ScaleValueFracLength	<p>Scale values work with SOS filters. Setting this property controls how your filter interprets the scale values by setting the fraction length. Only available when you disable <code>AutoScaleMode</code> by setting it to <code>false</code>.</p>
ScaleValues	<p>Scaling for the filter objects in SOS filters.</p>
Signed	<p>Specifies whether the filter uses signed or unsigned fixed-point coefficients. Only coefficients reflect this property setting.</p>

Property Name	Brief Description
SosMatrix	Holds the filter coefficients as property values — you use <code>set</code> and <code>get</code> to modify them. Displays the matrix in the format [sections x coefficients/section data type].
SectionInputFracLength	Lets you set the fraction length for section inputs in SOS filters, if you set <code>SectionInputAutoScale</code> to <code>false</code> .
SectionInputWordLength	Lets you set the word length for section inputs in SOS filters, if you set <code>SectionInputAutoScale</code> to <code>false</code> .
SectionOutputFracLength	Lets you set the fraction length for section outputs in SOS filters, if you set <code>SectionOutputAutoScale</code> to <code>off</code> .
SectionOutputWordLength	Lets you set the word length for section outputs in SOS filters, if you set <code>SectionOutputAutoScale</code> to <code>false</code> .
StateAutoScale	Setting autoscaling for filter states to <code>true</code> reduces the possibility of overflows occurring during fixed-point operations. Set to <code>false</code> , <code>StateAutoScale</code> lets the filter select the fraction length to limit the overflow potential.
StateFracLength	When you set <code>StateAutoScale</code> to <code>false</code> , you enable the <code>StateFracLength</code> property that lets you set the fraction length applied to interpret the filter states.
States	This property contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions.
StateWordLength	Sets the word length used to represent the filter states.

## Examples

Construct a second-order section Butterworth filter for fixed-point filtering. Start by specifying a Butterworth filter, and then convert the filter to second-order sections, with the following code:

```
[z,p,k] = butter(30,0.5);
```

```
[s,g] = zp2sos(z,p,k);  
hd = dfilt.df2tsos(s,g);  
% convert filter to fixed-point  
hd.arithmetic='fixed';
```

### See Also

[dfilt](#) | [dfilt.df1sos](#) | [dfilt.df1tsos](#) | [dfilt.df2sos](#)

# dfilt.dfasymfir

---

<b>Purpose</b>	Discrete-time, direct-form antisymmetric FIR filter
<b>Syntax</b>	Refer to <code>dfilt.dfasymfir</code> in Signal Processing Toolbox documentation.
<b>Description</b>	<p><code>hd = dfilt.dfasymfir(b)</code> returns a discrete-time, direct-form, antisymmetric FIR filter object <code>hd</code>, with numerator coefficients <code>b</code>.</p> <p>Make this filter a fixed-point or single-precision filter by changing the value of the <code>Arithmetic</code> property for the filter <code>hd</code> as follows:</p> <ul style="list-style-type: none"><li>• To change to single-precision filtering, enter <pre>set(hd,'arithmetic','single');</pre></li><li>• To change to fixed-point filtering, enter <pre>set(hd,'arithmetic','fixed');</pre></li></ul> <p>For more information about the property <code>Arithmetic</code>, refer to “Arithmetic” on page 8-19.</p> <p><code>hd = dfilt.dfasymfir</code> returns a default, discrete-time, direct-form, antisymmetric FIR filter object <code>hd</code>, with <code>b=1</code>. This filter passes the input through to the output unchanged.</p>


---

**Note** Only the coefficients in the first half of vector `b` are used because `dfilt.dfasymfir` assumes the coefficients in the second half are antisymmetric to those in the first half. For example, in the figure coefficients,  $b(4) = -b(3)$ ,  $b(5) = -b(2)$ , and  $b(6) = -b(1)$ .

---

## Fixed-Point Filter Structure

The following figure shows the signal flow for the odd-order antisymmetric FIR filter implemented by `dfilt.dfasymfir`. The even-order filter uses similar flow. To help you see how the filter processes the coefficients, input, and states of the filter, as well as numerical operations, the figure includes the locations of the formatting objects within the signal flow.



### Notes About the Signal Flow Diagram

To help you understand where and how the filter performs fixed-point arithmetic during filtering, the figure shows various labels associated with data and functional elements in the filter. The following table describes each label in the signal flow and relates the label to the filter properties that are associated with it.

The labels use a common format — a prefix followed by the word “format.” In this use, “format” means the word length and fraction length associated with the filter part referred to by the prefix.

For example, the `InputFormat` label refers to the word length and fraction length used to interpret the data input to the filter. The format properties `InputWordLength` and `InputFracLength` (as shown in the table) store the word length and the fraction length in bits. Or consider `NumFormat`, which refers to the word and fraction lengths (`CoeffWordLength`, `NumFracLength`) associated with representing filter numerator coefficients.

<b>Signal Flow Label</b>	<b>Corresponding Word Length Property</b>	<b>Corresponding Fraction Length Property</b>	<b>Related Properties</b>
AccumFormat	AccumWordLength	AccumFracLength	None
InputFormat	InputWordLength	InputFracLength	None
NumFormat	CoeffWordLength	NumFracLength	CoeffAutoScale, , Signed, Numerator
OutputFormat	OutputWordLength	OutputFracLength	None
ProductFormat	ProductWordLength	ProductFracLength	None
TapSumFormat	InputWordLength	InputFracLength	InputFormat

Most important is the label position in the diagram, which identifies where the format applies.

As one example, look at the label ProductFormat, which always follows a coefficient multiplication element in the signal flow. The label indicates that coefficients leave the multiplication element with the word length and fraction length associated with product operations that include coefficients. From reviewing the table, you see that the ProductFormat refers to the properties ProductFracLength and ProductWordLength that fully define the coefficient format after multiply (or product) operations.

## Properties

In this table you see the properties associated with an antisymmetric FIR implementation of dfilt objects.

---

**Note** The table lists all the properties that a filter can have. Many of the properties are dynamic, meaning they exist only in response to the settings of other properties. You might not see all of the listed properties all the time. To view all the properties for a filter at any time, use

```
get(hd)
```

where `hd` is a filter.

---

For further information about the properties of this filter or any `dfilt` object, refer to “Fixed-Point Filter Properties” on page 8-2.

Name	Values	Description
AccumFracLength	Any positive or negative integer number of bits [27]	Specifies the fraction length used to interpret data output by the accumulator.
AccumWordLength	Any integer number of bits[33]	Sets the word length used to store data in the accumulator.
Arithmetic	fixed for fixed-point filters	Setting this to <code>fixed</code> allows you to modify other filter properties to customize your fixed-point filter.
CoeffAutoScale	[true], false	Specifies whether the filter automatically chooses the proper fraction length to represent filter coefficients without overflowing. Turning this off by setting the value to <code>false</code> enables you to change the <code>NumFracLength</code> property value to specify the precision used.
CoeffWordLength	Any integer number of bits [16]	Specifies the word length to apply to filter coefficients.

## dfilt.dfasymfir

Name	Values	Description
FilterInternals	[FullPrecision], SpecifyPrecision	Controls whether the filter automatically sets the output word and fraction lengths, product word and fraction lengths, and the accumulator word and fraction lengths to maintain the best precision results during filtering. The default value, FullPrecision, sets automatic word and fraction length determination by the filter. SpecifyPrecision makes the output and accumulator-related properties available so you can set your own word and fraction lengths for them.
InputFracLength	Any positive or negative integer number of bits [15]	Specifies the fraction length the filter uses to interpret input data. Also controls TapSumFracLength.
InputWordLength	Any integer number of bits [16]	Specifies the word length applied to interpret input data. Also determines TapSumWordLength.
NumFracLength	Any positive or negative integer number of bits [14]	Sets the fraction length used to interpret the numerator coefficients.
OutputFracLength	Any positive or negative integer number of bits [29]	Determines how the filter interprets the filter output data. You can change the value of OutputFracLength when you set FilterInternals to SpecifyPrecision.
OutputWordLength	Any integer number of bits [33]	Determines the word length used for the output data. You make this property editable by setting FilterInternals to SpecifyPrecision.

Name	Values	Description
OverflowMode	saturate, [wrap]	Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either <b>saturate</b> (limit the output to the largest positive or negative representable value) or <b>wrap</b> (set overflowing values to the nearest representable value using modular arithmetic). The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow — they maintain full precision.
ProductFracLength	Any positive or negative integer number of bits [27]	Specifies the fraction length to use for multiplication operation results. This property becomes writable (you can change the value) when you set ProductMode to <b>SpecifyPrecision</b> .
ProductWordLength	Any integer number of bits [33]	Specifies the word length to use for multiplication operation results. This property becomes writable (you can change the value) when you set ProductMode to <b>SpecifyPrecision</b> .
RoundMode	[convergent], ceil, fix, floor, nearest, round	Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths). <ul style="list-style-type: none"> <li>• <b>ceil</b> - Round toward positive infinity.</li> <li>• <b>convergent</b> - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.</li> <li>• <b>fix</b> - Round toward zero.</li> </ul>

Name	Values	Description
		<ul style="list-style-type: none"> <li>• <code>floor</code> - Round toward negative infinity.</li> <li>• <code>nearest</code> - Round toward nearest. Ties round toward positive infinity.</li> <li>• <code>round</code> - Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.</li> </ul> <p>The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always round. Finally, products never overflow — they maintain full precision.</p>
Signed	[true], false	Specifies whether the filter uses signed or unsigned fixed-point coefficients. Only coefficients reflect this property setting.
States	fi object to match the filter arithmetic setting	Contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions. The states use fi objects, with the associated properties from those objects. For details, refer to fixed-point objects in Fixed-Point Toolbox documentation.

## Examples

### Odd Order

Specify a fifth-order direct-form antisymmetric FIR filter structure for a `dfilt` object, `hd`, with the following code:

```
b = [-0.008 0.06 -0.44 0.44 -0.06 0.008];
hd = dfilt.dfasymfir(b);
```

## Even Order

Specify a fourth-order direct-form antisymmetric FIR filter structure for `dfilt` object `hd`, with the following code:

```
b = [-0.01 0.1 0.0 -0.1 0.01];  
hd = dfilt.dfasymfir(b);  
hd.arithmetic='fixed';  
FilterCoefs = get(hd,'numerator');  
% or equivalently  
FilterCoefs = hd.numerator;
```

## See Also

[dfilt](#) | [dfilt.dffir](#) | [dfilt.dffirt](#) | [dfilt.dfsymfir](#)

**Purpose** Discrete-time, direct-form FIR filter

**Syntax** Refer to `dfilt.dffir` in Signal Processing Toolbox documentation.

**Description** `hd = dfilt.dffir(b)` returns a discrete-time, direct-form finite impulse response (FIR) filter object `hd`, with numerator coefficients `b`.  
Make this filter a fixed-point or single-precision filter by changing the value of the `Arithmetic` property for the filter `hd` as follows:

- To change to single-precision filtering, enter

```
set(hd,'arithmetic','single');
```

- To change to fixed-point filtering, enter


```
set(hd,'arithmetic','fixed');
```

For more information about the property `Arithmetic`, refer to “`Arithmetic`” on page 8-19.

`hd = dfilt.dffir` returns a default, discrete-time, direct-form FIR filter object `hd`, with `b=1`. This filter passes the input through to the output unchanged.

## Fixed-Point Filter Structure

The following figure shows the signal flow for the direct-form FIR filter implemented by `dfilt.dffir`. To help you see how the filter processes the coefficients, input, and states of the filter, as well as numerical operations, the figure includes the locations of the formatting objects within the signal flow.



### Notes About the Signal Flow Diagram

To help you understand where and how the filter performs fixed-point arithmetic during filtering, the figure shows various labels associated with data and functional elements in the filter. The following table describes each label in the signal flow and relates the label to the filter properties that are associated with it.

The labels use a common format — a prefix followed by the letters “frmt” (format). In this use, “frmt” indicates the word length and fraction length associated with the filter part referred to by the prefix.

For example, the `InputFrmt` label refers to the word length and fraction length used to interpret the data input to the filter. The format properties `InputWordLength` and `InputFracLength` (as shown in the table) store the word length and the fraction length in bits. Or consider `NumFrmt`, which refers to the word and fraction lengths (`CoeffWordLength`, `NumFracLength`) associated with representing filter numerator coefficients.

Signal Flow Label	Corresponding Word Length Property	Corresponding Fraction Length Property	Related Properties
AccumFrmt	AccumWordLength	AccumFracLength	None
InputFrmt	InputWordLength	InputFracLength	None
NumFrmt	CoeffWordLength	NumFracLength	CoeffAutoScale, Signed, Numerator
OutputFrmt	OutputWordLength	OutputFracLength	None
ProductFrmt	ProductWordLength	ProductFracLength	None

Most important is the label position in the diagram, which identifies where the format applies.

As one example, look at the label `ProductFrmt`, which always follows a coefficient multiplication element in the signal flow. The label indicates that coefficients leave the multiplication element with the word length and fraction length associated with product operations that include coefficients. From reviewing the table, you see that the `ProductFrmt` refers to the properties `ProductFracLength` and `ProductWordLength` that fully define the coefficient format after multiply (or product) operations.

## Properties

In this table you see the properties associated with direct-form FIR implementation of `dfilt` objects.

---

**Note** The table lists all the properties that a filter can have. Many of the properties are dynamic, meaning they exist only in response to the settings of other properties. You might not see all of the listed properties all the time. To view all the properties for a filter at any time, use

```
get(hd)
```

where `hd` is a filter.

---

For further information about the properties of this filter or any `dfilt` object, refer to “Fixed-Point Filter Properties” on page 8-2.

Name	Values	Description
AccumFracLength	Any positive or negative integer number of bits [30]	Specifies the fraction length used to interpret data output by the accumulator.
AccumWordLength	Any integer number of bits [34]	Sets the word length used to store data in the accumulator.
Arithmetic	fixed for fixed-point filters	Setting this to <code>fixed</code> allows you to modify other filter properties to customize your fixed-point filter.
CoeffAutoScale	[true], false	Specifies whether the filter automatically chooses the proper fraction length to represent filter coefficients without overflowing. Turning this off by setting the value to <code>false</code> enables you to change the <code>NumFracLength</code> property value to specify the precision used.
CoeffWordLength	Any integer number of bits [16]	Specifies the word length to apply to filter coefficients.
FilterInternals	[FullPrecision], SpecifyPrecision	Controls whether the filter automatically sets the output word and fraction lengths, product word and fraction lengths, and the accumulator word and fraction lengths to maintain the best precision results during filtering. The default value, <code>FullPrecision</code> , sets automatic word and fraction length determination by the filter. <code>SpecifyPrecision</code> makes the output and accumulator-related properties available so you can set your own word and fraction lengths for them.

Name	Values	Description
InputFracLength	Any positive or negative integer number of bits [15]	Specifies the fraction length the filter uses to interpret input data.
InputWordLength	Any integer number of bits [16]	Specifies the word length applied to interpret input data.
NumFracLength	Any positive or negative integer number of bits [14]	Sets the fraction length used to interpret the numerator coefficients.
OutputFracLength	Any positive or negative integer number of bits [32]	Determines how the filter interprets the filter output data. You can change the value of <code>OutputFracLength</code> when you set <code>FilterInternals</code> to <code>SpecifyPrecision</code> .
OutputWordLength	Any integer number of bits [39]	Determines the word length used for the output data. You make this property editable by setting <code>FilterInternals</code> to <code>SpecifyPrecision</code> .
OverflowMode	saturate, [wrap]	Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either <code>saturate</code> (limit the output to the largest positive or negative representable value) or <code>wrap</code> (set overflowing values to the nearest representable value using modular arithmetic). The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow — they maintain full precision.

Name	Values	Description
ProductFracLength	Any positive or negative integer number of bits [30]	Specifies the fraction length to use for multiplication operation results. This property becomes writable (you can change the value) when you set ProductMode to SpecifyPrecision.
ProductWordLength	Any integer number of bits [32]	Specifies the word length to use for multiplication operation results. This property becomes writable (you can change the value) when you set ProductMode to SpecifyPrecision.
RoundMode	[convergent], ceil, fix, floor, nearest, round	<p>Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths).</p> <ul style="list-style-type: none"> <li>• <b>ceil</b> - Round toward positive infinity.</li> <li>• <b>convergent</b> - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.</li> <li>• <b>fix</b> - Round toward zero.</li> <li>• <b>floor</b> - Round toward negative infinity.</li> <li>• <b>nearest</b> - Round toward nearest. Ties round toward positive infinity.</li> <li>• <b>round</b> - Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.</li> </ul> <p>The choice you make affects only the accumulator and output arithmetic. Coefficient</p>

# dfilt.dffir

Name	Values	Description
		and input arithmetic always round. Finally, products never overflow — they maintain full precision.
Signed	[true], false	Specifies whether the filter uses signed or unsigned fixed-point coefficients. Only coefficients reflect this property setting.
States	fi object to match the filter arithmetic setting	Contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions. The states use fi objects, with the associated properties from those objects. For details, refer to fixed-point objects in Fixed-Point Toolbox documentation.

## Examples

Specify a second-order direct-form FIR filter structure for a `dfilt` object `hd`, with the following code that constructs the filter in double-precision format and then converts the filter to fixed-point operation:

```
b = [0.05 0.9 0.05];  
hd = dfilt.dffir(b);  
% Create fixed-point filter  
hd.arithmetic='fixed';  
% Change FilterInternals property to  
% SpecifyPrecision enabling other properties  
hd.FilterInternals='SpecifyPrecision';
```


## See Also

`dfilt` | `dfilt.dfasymfir` | `dfilt.dffirt` | `dfilt.dfsymfir`

---

<b>Purpose</b>	Discrete-time, direct-form FIR transposed filter
<b>Syntax</b>	Refer to <code>dfilt.dffirt</code> in Signal Processing Toolbox documentation.
<b>Description</b>	<p><code>hd = dfilt.dffirt(b)</code> returns a discrete-time, direct-form FIR transposed filter object <code>hd</code>, with numerator coefficients <code>b</code>.</p> <p>Make this filter a fixed-point or single-precision filter by changing the value of the <code>Arithmetic</code> property for the filter <code>hd</code> as follows:</p> <ul style="list-style-type: none"><li>• To change to single-precision filtering, enter <pre>set(hd,'arithmetic','single');</pre></li><li>• To change to fixed-point filtering, enter <pre>set(hd,'arithmetic','fixed');</pre></li></ul> <p>For more information about the property <code>Arithmetic</code>, refer to “Arithmetic” on page 8-19.</p> <p><code>hd = dfilt.dffirt</code> returns a default, discrete-time, direct-form FIR transposed filter object <code>hd</code>, with <code>b = 1</code>. This filter passes the input through to the output unchanged.</p>
<b>Fixed-Point Filter Structure</b>	<p>The following figure shows the signal flow for the transposed direct-form FIR filter implemented by <code>dfilt.dffirt</code>. To help you see how the filter processes the coefficients, input, and states of the filter, as well as numerical operations, the figure includes the locations of the formatting objects within the signal flow.</p>

# dfilt.dffirt



## Notes About the Signal Flow Diagram

To help you understand where and how the filter performs fixed-point arithmetic during filtering, the figure shows various labels associated with data and functional elements in the filter. The following table describes each label in the signal flow and relates the label to the filter properties that are associated with it.

The labels use a common format — a prefix followed by the word “format.” In this use, “format” means the word length and fraction length associated with the filter part referred to by the prefix.

For example, the InputFormat label refers to the word length and fraction length used to interpret the data input to the filter. The format properties InputWordLength and InputFracLength (as shown in the table) store the word length and the fraction length in bits. Or consider NumFormat, which refers to the word and fraction lengths (CoeffWordLength, NumFracLength) associated with representing filter numerator coefficients.

<b>Signal Flow Label</b>	<b>Corresponding Word Length Property</b>	<b>Corresponding Fraction Length Property</b>	<b>Related Properties</b>
AccumFormat	AccumWordLength	AccumFracLength	None
InputFormat	InputWordLength	InputFracLength	None
NumFormat	CoeffWordLength	NumFracLength	CoeffAutoScale, Signed, Numerator
OutputFormat	OutputWordLength	OutputFracLength	None
ProductFormat	ProductWordLength	ProductFracLength	None

Most important is the label position in the diagram, which identifies where the format applies.

As one example, look at the label ProductFormat, which always follows a coefficient multiplication element in the signal flow. The label indicates that coefficients leave the multiplication element with the word length and fraction length associated with product operations that include coefficients. From reviewing the table, you see that the ProductFormat refers to the properties ProductFracLength and ProductWordLength that fully define the coefficient format after multiply (or product) operations.

## Properties

In this table you see the properties associated with the transposed direct-form FIR implementation of dfilt objects.

---

**Note** The table lists all the properties that a filter can have. Many of the properties are dynamic, meaning they exist only in response to the settings of other properties. You might not see all of the listed properties all the time. To view all the properties for a filter at any time, use

`get(hd)`

where `hd` is a filter.

---

For further information about the properties of this filter or any `dfilt` object, refer to “Fixed-Point Filter Properties” on page 8-2.

Name	Values	Description
AccumFracLength	Any positive or negative integer number of bits [30]	Specifies the fraction length used to interpret data output by the accumulator.
AccumWordLength	Any integer number of bits[34]	Sets the word length used to store data in the accumulator.
Arithmetic	fixed for fixed-point filters	Setting this to <code>fixed</code> allows you to modify other filter properties to customize your fixed-point filter.
CoeffAutoScale	[true], false	Specifies whether the filter automatically chooses the proper fraction length to represent filter coefficients without overflowing. Turning this off by setting the value to <code>false</code> enables you to change the <code>NumFracLength</code> property value to specify the precision used.
CoeffWordLength	Any integer number of bits [16]	Specifies the word length to apply to filter coefficients.

Name	Values	Description
FilterInternals	[FullPrecision], SpecifyPrecision	Controls whether the filter automatically sets the output word and fraction lengths, product word and fraction lengths, and the accumulator word and fraction lengths to maintain the best precision results during filtering. The default value, FullPrecision, sets automatic word and fraction length determination by the filter. SpecifyPrecision makes the output and accumulator-related properties available so you can set your own word and fraction lengths for them.
InputFracLength	Any positive or negative integer number of bits [15]	Specifies the fraction length the filter uses to interpret input data.
InputWordLength	Any integer number of bits [16]	Specifies the word length applied to interpret input data.
NumFracLength	Any positive or negative integer number of bits [14]	Sets the fraction length used to interpret the numerator coefficients.
OutputFracLength	Any positive or negative integer number of bits [30]	Determines how the filter interprets the filter output data. You can change the value of OutputFracLength when you set FilterInternals to SpecifyPrecision.
OutputWordLength	Any integer number of bits [34]	Determines the word length used for the output data. You make this property editable by setting FilterInternals to SpecifyPrecision.

Name	Values	Description
OverflowMode	saturate, [wrap]	<p>Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either <b>saturate</b> (limit the output to the largest positive or negative representable value) or <b>wrap</b> (set overflowing values to the nearest representable value using modular arithmetic). The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow—they maintain full precision.</p>
RoundMode	[convergent], ceil, fix, floor, nearest, round	<p>Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths).</p> <ul style="list-style-type: none"><li>• <b>ceil</b> - Round toward positive infinity.</li><li>• <b>convergent</b> - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.</li><li>• <b>fix</b> - Round toward zero.</li><li>• <b>floor</b> - Round toward negative infinity.</li><li>• <b>nearest</b> - Round toward nearest. Ties round toward positive infinity.</li><li>• <b>round</b> - Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.</li></ul>

Name	Values	Description
		The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always round. Finally, products never overflow — they maintain full precision.
Signed	[true], false	Specifies whether the filter uses signed or unsigned fixed-point coefficients. Only coefficients reflect this property setting.
States	fi object to match the filter arithmetic setting	Contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions. The states use fi objects, with the associated properties from those objects. For details, refer to fixed-point objects in Fixed-Point Toolbox documentation.

### Examples

Specify a second-order direct-form FIR transposed filter structure for a `dfilt` object, `hd`, with the following code:

```
b = [0.05 0.9 0.05];
hd = dfilt.dffirt(b);
set(hd,'arithmetic','fixed')
```

### See Also

`dfilt` | `dfilt.dffir` | `dfilt.dfasymfir` | `dfilt.dfsymfir`

# dfilt.dfsymfir

---


<b>Purpose</b>	Discrete-time, direct-form symmetric FIR filter
<b>Syntax</b>	Refer to <code>dfilt.dfsymfir</code> in Signal Processing Toolbox documentation.
<b>Description</b>	<p><code>hd = dfilt.dfsymfir(b)</code> returns a discrete-time, direct-form symmetric FIR filter object <code>hd</code>, with numerator coefficients <code>b</code>.</p> <p>Make this filter a fixed-point or single-precision filter by changing the value of the <code>Arithmetic</code> property for the filter <code>hd</code> as follows:</p> <ul style="list-style-type: none"><li>• To change to single-precision filtering, enter <pre>set(hd,'arithmetic','single');</pre></li><li>• To change to fixed-point filtering, enter <pre>set(hd,'arithmetic','fixed');</pre></li></ul> <p>For more information about the property <code>Arithmetic</code>, refer to “<code>Arithmetic</code>” on page 8-19.</p> <p><code>hd = dfilt.dfsymfir</code> returns a default, discrete-time, direct-form symmetric FIR filter object <code>hd</code>, with <code>b=1</code>. This filter passes the input through to the output unchanged.</p>

---

**Note** Only the coefficients in the first half of vector `b` are used because `dfilt.dfsymfir` assumes the coefficients in the second half are symmetric to those in the first half. In the following figure, for example,  $b(3) = 0$ ,  $b(4) = b(2)$  and  $b(5) = b(1)$ .

---

<b>Fixed-Point Filter Structure</b>	In the following figure you see the signal flow diagram for the symmetric FIR filter that <code>dfilt.dfsymfir</code> implements.
-------------------------------------	---



### Notes About the Signal Flow Diagram

To help you understand where and how the filter performs fixed-point arithmetic during filtering, the figure shows various labels associated with data and functional elements in the filter. The following table describes each label in the signal flow and relates the label to the filter properties that are associated with it.

The labels use a common format — a prefix followed by the letters “frmt” (format). In this use, “frmt” indicates the word length and fraction length associated with the filter part referred to by the prefix.

For example, the InputFrmt label refers to the word length and fraction length used to interpret the data input to the filter. The format properties InputWordLength and InputFracLength (as shown in the table) store the word length and the fraction length in bits. Or consider NumFrmt, which refers to the word and fraction lengths (CoeffWordLength, NumFracLength) associated with representing filter numerator coefficients.

<b>Signal Flow Label</b>	<b>Corresponding Word Length Property</b>	<b>Corresponding Fraction Length Property</b>	<b>Related Properties</b>
AccumFrmt	AccumWordLength	AccumFracLength	None
InputFrmt	InputWordLength	InputFracLength	None
NumFrmt	CoeffWordLength	NumFracLength	CoeffAutoScale, Signed, Numerator
OutputFrmt	OutputWordLength	OutputFracLength	None
ProductFrmt	ProductWordLength	ProductFracLength	None
TapSumFrmt	InputWordLength	InputFracLength	None

Most important is the label position in the diagram, which identifies where the format applies.

As one example, look at the label ProductFrmt, which always follows a coefficient multiplication element in the signal flow. The label indicates that coefficients leave the multiplication element with the word length and fraction length associated with product operations that include coefficients. From reviewing the table, you see that the ProductFrmt refers to the properties ProductFracLength and ProductWordLength that fully define the coefficient format after multiply (or product) operations.

## Properties

In this table you see the properties associated with the symmetric FIR implementation of dfilt objects.

---

**Note** The table lists all the properties that a filter can have. Many of the properties are dynamic, meaning they exist only in response to the settings of other properties. You might not see all of the listed properties all the time. To view all the properties for a filter at any time, use

```
get(hd)
```

where `hd` is a filter.

---

For further information about the properties of this filter or any `dfilt` object, refer to “Fixed-Point Filter Properties” on page 8-2.

Name	Values	Description
AccumFracLength	Any positive or negative integer number of bits [27]	Specifies the fraction length used to interpret data output by the accumulator.
AccumWordLength	Any integer number of bits[33]	Sets the word length used to store data in the accumulator.
Arithmetic	fixed for fixed-point filters	Setting this to <code>fixed</code> allows you to modify other filter properties to customize your fixed-point filter.
CoeffAutoScale	[true], false	Specifies whether the filter automatically chooses the proper fraction length to represent filter coefficients without overflowing. Turning this off by setting the value to <code>false</code> enables you to change the <code>NumFracLength</code> property value to specify the precision used.
CoeffWordLength	Any integer number of bits [16]	Specifies the word length to apply to filter coefficients.

## dfilt.dfsymfir

Name	Values	Description
FilterInternals	[FullPrecision], SpecifyPrecision	Controls whether the filter automatically sets the output word and fraction lengths, product word and fraction lengths, and the accumulator word and fraction lengths to maintain the best precision results during filtering. The default value, FullPrecision, sets automatic word and fraction length determination by the filter. SpecifyPrecision makes the output and accumulator-related properties available so you can set your own word and fraction lengths for them.
InputFracLength	Any positive or negative integer number of bits [15]	Specifies the fraction length the filter uses to interpret input data.
InputWordLength	Any integer number of bits [16]	Specifies the word length applied to interpret input data.
NumFracLength	Any positive or negative integer number of bits [14]	Sets the fraction length used to interpret the numerator coefficients.
OutputFracLength	Any positive or negative integer number of bits [29]	Determines how the filter interprets the filter output data. You can change the value of OutputFracLength when you set FilterInternals to SpecifyPrecision.
OutputWordLength	Any integer number of bits [33]	Determines the word length used for the output data. You make this property editable by setting FilterInternals to SpecifyPrecision.

Name	Values	Description
OverflowMode	saturate, [wrap]	Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either <code>saturate</code> (limit the output to the largest positive or negative representable value) or <code>wrap</code> (set overflowing values to the nearest representable value using modular arithmetic). The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow—they maintain full precision.
ProductFracLength	Any positive or negative integer number of bits [29]	Specifies the fraction length to use for multiplication operation results. This property becomes writable (you can change the value) when you set <code>ProductMode</code> to <code>SpecifyPrecision</code> .
ProductWordLength	Any integer number of bits [33]	Specifies the word length to use for multiplication operation results. This property becomes writable (you can change the value) when you set <code>ProductMode</code> to <code>SpecifyPrecision</code> .

Name	Values	Description
RoundMode	[convergent], ceil, fix, floor, nearest, round	<p>Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths).</p> <ul style="list-style-type: none"><li>• <code>ceil</code> - Round toward positive infinity.</li><li>• <code>convergent</code> - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.</li><li>• <code>fix</code> - Round toward zero.</li><li>• <code>floor</code> - Round toward negative infinity.</li><li>• <code>nearest</code> - Round toward nearest. Ties round toward positive infinity.</li><li>• <code>round</code> - Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.</li></ul> <p>The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always round. Finally, products never overflow — they maintain full precision.</p>

Name	Values	Description
Signed	[true], false	Specifies whether the filter uses signed or unsigned fixed-point coefficients. Only coefficients reflect this property setting.
States	fi object to match the filter arithmetic setting	Contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions. The states use fi objects, with the associated properties from those objects. For details, refer to fixed-point objects in Fixed-Point Toolbox documentation.

## Examples

### Odd Order

Specify a fifth-order direct-form symmetric FIR filter structure for a `dfilt` object `hd`, with the following code:

```
b = [-0.008 0.06 0.44 0.44 0.06 -0.008];
hd = dfilt.dfsymfir(b);
% Create fixed-point filter
set(hd,'arithmetic','fixed')
% Change FilterInternals property to
% SpecifyPrecision
hd.Filterinternals='SpecifyPrecision';
```

### Even Order

Specify a fourth-order, fixed-point, direct-form symmetric FIR filter structure for a `dfilt` object `hd`, with the following code:

```
b = [-0.01 0.1 0.8 0.1 -0.01];
hd = dfilt.dfsymfir(b);
set(hd,'arithmetic','fixed');
```

## See Also

`dfilt` | `dfilt.dfasymfir` | `dfilt.dffir` | `dfilt.dffirt`

# dfilt.farrowfd

---

**Purpose** Fractional Delay Farrow filter

**Syntax** Hd = dfilt.farrowd(D, COEFFS)

**Description** Hd = dfilt.farrowd(D, COEFFS)


Constructs a discrete-time fractional delay Farrow filter with COEFFS coefficients and D delay.

**Examples** Farrow filters can be designed with the dfilt.farrowfd filter designer.

```
coeffs = [-1/6 1/2 -1/3 0;1/2 -1 -1/2 1;  
-1/2 1/2 1 0;1/6 0 -1/6 0];  
Hd = dfilt.farrowfd(0.5, coeffs);
```

Design a cubic fractional delay filter with the Lagrange method.

```
fdelay = .2; % Fractional delay  
d = fdesign.fracdelay(fdelay,'N',3);  
Hd = design(d, 'lagrange', 'FilterStructure', 'farrowfd');  
fvtool(Hd, 'Analysis', 'grpdelay');
```



For more information about fractional delay filter implementations, see the “Fractional Delay Filters Using Farrow Structures” example, `farrowdemo`.

## How To

- `dfilt`

# dfilt.farrowlinearfd

---

**Purpose** Farrow Linear Fractional Delay filter

**Syntax** Hd = DFILT.FARROWLINEARFD(D)

**Description** Hd = DFILT.FARROWLINEARFD(D)  
Constructs a discrete-time linear fractional delay Farrow filter with the delay D.

**Examples** Farrow linear fractional delay filter with 1/2 sample delay:

```
Hd = dfilt.farrowlinearfd(0.5);  
n = cos(pi/10*(0:159));  
y = filter(Hd,x);  
stem(x(1:40));  
axis([0 40 -2 2]);  
hold on;  
stem(y(1:40),'color',[1 0 0],'markerfacecolor',[1 0 0]);  
legend('Original Signal','Filtered Signal','Location','best');
```

For more information about fractional delay filter implementations, see the “Fractional Delay Filters Using Farrow Structures” example, `farrowdemo`.

**How To** • `dfilt`

---

<b>Purpose</b>	Discrete-time, overlap-add, FIR filter
<b>Syntax</b>	<pre>Hd = dfilt.fftfir(b,len) Hd = dfilt.fftfir(b) Hd = dfilt.fftfir</pre>
<b>Description</b>	<p>This object uses the overlap-add method of block FIR filtering, which is very efficient for streaming data.</p> <p><code>Hd = dfilt.fftfir(b,len)</code> returns a discrete-time, FFT, FIR filter, <code>Hd</code>, with numerator coefficients, <code>b</code> and block length, <code>len</code>. The block length is the number of input points to use for each overlap-add computation.</p> <p><code>Hd = dfilt.fftfir(b)</code> returns a discrete-time, FFT, FIR filter, <code>Hd</code>, with numerator coefficients, <code>b</code> and block length, <code>len=100</code>.</p> <p><code>Hd = dfilt.fftfir</code> returns a default, discrete-time, FFT, FIR filter, <code>Hd</code>, with the numerator <code>b=1</code> and block length, <code>len=100</code>. This filter passes the input through to the output unchanged.</p>


---

**Note** When you use a `dfilt.fftfir` object to filter, the input signal length must be an integer multiple of the object's block length, `len`. The resulting number of FFT points = (filter length + the block length - 1). The filter is most efficient if the number of FFT points is a power of 2.

---

The `fftfir` uses an overlap-add block processing algorithm, which is represented as follows,

# dfilt.fftfir



where  $len$  is the block length and  $M$  is the length of the numerator-1,  $(length(b) - 1)$ , which is also the number of states. The output of each convolution is a block that is longer than the input block by a tail of  $(length(b) - 1)$  samples. These tails overlap the next block and are added to it. The states reported by `dfilt.fftfir` are the tails of the final convolution.

## Examples

Create an FFT FIR discrete-time filter with coefficients from a 30<sup>th</sup> order lowpass equiripple design:


```
b = firpm(30,[0 .1 .2 .5]*2,[1 1 0 0]);  
Hd = dfilt.fftfir(b);  
% To obtain frequency domain coefficients  
% used in filtering  
Coeffs = fftcoeffs(Hd);
```

## See Also

`dfilt` | `dfilt.dffir` | `dfilt.dfasymfir` | `dfilt.dffirt` | `dfilt.dfsymfir`

<b>Purpose</b>	Discrete-time, lattice allpass filter
<b>Syntax</b>	Refer to <code>dfilt.latticeallpass</code> in Signal Processing Toolbox documentation.
<b>Description</b>	<p><code>hd = dfilt.latticeallpass(k)</code> returns a discrete-time, lattice allpass filter object <code>hd</code>, with lattice coefficients, <code>k</code>.</p> <p>Make this filter a fixed-point or single-precision filter by changing the value of the <code>Arithmetic</code> property for the filter <code>hd</code> as follows:</p> <ul style="list-style-type: none"><li>• To change to single-precision filtering, enter <pre>set(hd, 'arithmetic', 'single');</pre></li><li>• To change to fixed-point filtering, enter <pre>set(hd, 'arithmetic', 'fixed');</pre></li></ul> <p>For more information about the property <code>Arithmetic</code>, refer to “Arithmetic” on page 8-19.</p> <p><code>hd = dfilt.latticeallpass</code> returns a default, discrete-time, lattice allpass filter object <code>hd</code>, with <code>k=[ ]</code>. This filter passes the input through to the output unchanged.</p>
<b>Fixed-Point Filter Structure</b>	<p>The following figure shows the signal flow for the allpass lattice filter implemented by <code>dfilt.latticeallpass</code>. To help you see how the filter processes the coefficients, input, and states of the filter, as well as numerical operations, the figure includes the locations of the formatting objects within the signal flow.</p>

# dfilt.latticeallpass



## Notes About the Signal Flow Diagram

To help you understand where and how the filter performs fixed-point arithmetic during filtering, the figure shows various labels associated with data and functional elements in the filter. The following table describes each label in the signal flow and relates the label to the filter properties that are associated with it.

The labels use a common format — a prefix followed by the word “format.” In this use, “format” means the word length and fraction length associated with the filter part referred to by the prefix.

For example, the InputFormat label refers to the word length and fraction length used to interpret the data input to the filter. The format properties InputWordLength and InputFracLength (as shown in the table) store the word length and the fraction length in bits. Or consider NumFormat, which refers to the word and fraction lengths (CoeffWordLength, NumFracLength) associated with representing filter numerator coefficients.

Signal Flow Label	Corresponding Word Length Property	Corresponding Fraction Length Property	Related Properties
AccumFormat	AccumWordLength	AccumFracLength	AccumMode
InputFormat	InputWordLength	InputFracLength	None
LatticeFormat	CoeffWordLength	LatticeFracLength	CoeffAutoScale
OutputFormat	OutputWordLength	OutputFracLength	OutputMode
ProductFormat	ProductWordLength	ProductFracLength	ProductMode
StateFormat	StateWordLength	StateFracLength	States

Most important is the label position in the diagram, which identifies where the format applies.

As one example, look at the label ProductFormat, which always follows a coefficient multiplication element in the signal flow. The label indicates that coefficients leave the multiplication element with the word length and fraction length associated with product operations that include coefficients. From reviewing the table, you see that the ProductFormat refers to the properties ProductFracLength, ProductWordLength, and ProductMode that fully define the coefficient format after multiply (or product) operations.

## Properties

In this table you see the properties associated with the allpass lattice implementation of dfilt objects.

---

**Note** The table lists all the properties that a filter can have. Many of the properties are dynamic, meaning they exist only in response to the settings of other properties. You might not see all of the listed properties all the time. To view all the properties for a filter at any time, use

```
get(hd)
```

where `hd` is a filter.

---

## dfilt.latticeallpass

---

For further information about the properties of this filter or any `dfilt` object, refer to “Fixed-Point Filter Properties” on page 8-2.

Property Name	Brief Description
<code>AccumFracLength</code>	Specifies the fraction length used to interpret data output by the accumulator. This is a property of FIR filters and lattice filters. IIR filters have two similar properties — <code>DenAccumFracLength</code> and <code>NumAccumFracLength</code> — that let you set the precision for numerator and denominator operations separately.
<code>AccumMode</code>	Determines how the accumulator outputs stored values. Choose from full precision ( <code>FullPrecision</code> ), or whether to keep the most significant bits ( <code>KeepMSB</code> ) or least significant bits ( <code>KeepLSB</code> ) when output results need shorter word length than the accumulator supports. To let you set the word length and the precision (the fraction length) used by the output from the accumulator, set <code>AccumMode</code> to <code>SpecifyPrecision</code> .
<code>AccumWordLength</code>	Sets the word length used to store data in the accumulator/buffer.
<code>Arithmetic</code>	Defines the arithmetic the filter uses. Gives you the options <code>double</code> , <code>single</code> , and <code>fixed</code> . In short, this property defines the operating mode for your filter.
<code>CastBeforeSum</code>	Specifies whether to cast numeric data to the appropriate accumulator format (as shown in the signal flow diagrams) before performing sum operations.

<b>Property Name</b>	<b>Brief Description</b>
<code>CoeffAutoScale</code>	Specifies whether the filter automatically chooses the proper fraction length to represent filter coefficients without overflowing. Turning this off by setting the value to <code>false</code> enables you to change the <code>LatticeFracLength</code> property value to specify the precision used.
<code>CoeffWordLength</code>	Specifies the word length to apply to filter coefficients.
<code>FilterStructure</code>	Describes the signal flow for the filter object, including all of the active elements that perform operations during filtering — gains, delays, sums, products, and input/output.
<code>InputFracLength</code>	Specifies the fraction length the filter uses to interpret input data.
<code>InputWordLength</code>	Specifies the word length applied to interpret input data.
<code>Lattice</code>	Any lattice structure coefficients. No default value.
<code>LatticeFracLength</code>	Sets the fraction length applied to the lattice coefficients.
<code>OutputFracLength</code>	Determines how the filter interprets the filter output data. You can change the value of <code>OutputFracLength</code> when you set <code>OutputMode</code> to <code>SpecifyPrecision</code> .

## dfilt.latticeallpass

---

Property Name	Brief Description
OutputMode	<p>Sets the mode the filter uses to scale the filtered data for output. You have the following choices:</p> <ul style="list-style-type: none"><li>• <b>AvoidOverflow</b> — directs the filter to set the output data word length and fraction length to avoid causing the data to overflow.</li><li>• <b>BestPrecision</b> — directs the filter to set the output data word length and fraction length to maximize the precision in the output data.</li><li>• <b>SpecifyPrecision</b> — lets you set the word and fraction lengths used by the output data from filtering.</li></ul>
OutputWordLength	<p>Determines the word length used for the output data.</p>
OverflowMode	<p>Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either <b>saturate</b> (limit the output to the largest positive or negative representable value) or <b>wrap</b> (set overflowing values to the nearest representable value using modular arithmetic). The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow—they maintain full precision.</p>
ProductFracLength	<p>For the output from a product operation, this sets the fraction length used to interpret the data. This property becomes writable (you can change the value) when you set <b>ProductMode</b> to <b>SpecifyPrecision</b>.</p>

Property Name	Brief Description
ProductMode	Determines how the filter handles the output of product operations. Choose from full precision (FullPrecision), or whether to keep the most significant bit (KeepMSB) or least significant bit (KeepLSB) in the result when you need to shorten the data words. For you to be able to set the precision (the fraction length) used by the output from the multiplies, you set ProductMode to SpecifyPrecision.
ProductWordLength	Specifies the word length to use for multiplication operation results. This property becomes writable (you can change the value) when you set ProductMode to SpecifyPrecision.
PersistentMemory	Specifies whether to reset the filter states and memory before each filtering operation. Lets you decide whether your filter retains states from previous filtering runs. False is the default setting.
RoundMode	Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths). <ul style="list-style-type: none"> <li>• <code>ceil</code> - Round toward positive infinity.</li> <li>• <code>convergent</code> - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.</li> <li>• <code>fix</code> - Round toward zero.</li> <li>• <code>floor</code> - Round toward negative infinity.</li> </ul>

Property Name	Brief Description
	<ul style="list-style-type: none"><li>• nearest - Round toward nearest. Ties round toward positive infinity.</li><li>• round - Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.</li></ul> <p>The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always round. Finally, products never overflow — they maintain full precision.</p>
Signed	Specifies whether the filter uses signed or unsigned fixed-point coefficients. Only coefficients reflect this property setting.
StateFracLength	When you set <code>StateAutoScale</code> to <code>false</code> , you enable the <code>StateFracLength</code> property that lets you set the fraction length applied to interpret the filter states.
States	This property contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions. The states use <code>fi</code> objects, with the associated properties from those objects. For details, refer to <code>filtstates</code> in Signal Processing Toolbox documentation or in the Help system.
StateWordLength	Sets the word length used to represent the filter states.

## Examples

Specify a third-order lattice allpass filter structure for a `dfilt` object `hd`, with the following code:

```
k = [.66 .7 .44];  
hd=dfilt.latticeallpass(k);  
% convert to fixed-point arithmetic  
hd.arithmetic = 'fixed';
```

### See Also

```
dfilt | dfilt.latticear | dfilt.latticearma |  
dfilt.latticemamax | dfilt.latticemamin
```

**Purpose** Discrete-time, lattice, autoregressive filter

**Syntax** Refer to `dfilt.latticear` in Signal Processing Toolbox documentation.

**Description** `hd = dfilt.latticear(k)` returns a discrete-time, lattice autoregressive filter object `hd`, with lattice coefficients, `k`.

Make this filter a fixed-point or single-precision filter by changing the value of the `Arithmetic` property for the filter `hd` as follows:

- To change to single-precision filtering, enter

```
set(hd,'arithmetic','single');
```

- To change to fixed-point filtering, enter

```
set(hd,'arithmetic','fixed');
```

For more information about the property `Arithmetic`, refer to “`Arithmetic`” on page 8-19.

`hd = dfilt.latticear` returns a default, discrete-time, lattice autoregressive filter object `hd`, with `k=[]`. This filter passes the input through to the output unchanged.

## Fixed-Point Filter Structure

The following figure shows the signal flow for the autoregressive lattice filter implemented by `dfilt.latticear`. To help you see how the filter processes the coefficients, input, and states of the filter, as well as numerical operations, the figure includes the locations of the formatting objects within the signal flow.



Signal Flow Label	Corresponding Word Length Property	Corresponding Fraction Length Property	Related Properties
LatticeFormat	CoeffWordLength	LatticeFracLength	CoeffAutoScale
OutputFormat	OutputWordLength	OutputFracLength	OutputMode
ProductFormat	ProductWordLength	ProductFracLength	ProductMode
StateFormat	StateWordLength	StateFracLength	States

Most important is the label position in the diagram, which identifies where the format applies.

As one example, look at the label ProductFormat, which always follows a coefficient multiplication element in the signal flow. The label indicates that coefficients leave the multiplication element with the word length and fraction length associated with product operations that include coefficients. From reviewing the table, you see that the ProductFormat refers to the properties ProductFracLength, ProductWordLength, and ProductMode that fully define the coefficient format after multiply (or product) operations.

## Properties

In this table you see the properties associated with the autoregressive lattice implementation of dfilt objects.

---

**Note** The table lists all the properties that a filter can have. Many of the properties are dynamic, meaning they exist only in response to the settings of other properties. You might not see all of the listed properties all the time. To view all the properties for a filter at any time, use

```
get(hd)
```

where hd is a filter.

---

For further information about the properties of this filter or any dfilt object, refer to “Fixed-Point Filter Properties” on page 8-2.

Property Name	Brief Description
AccumFracLength	Specifies the fraction length used to interpret data output by the accumulator. This is a property of FIR filters and lattice filters. IIR filters have two similar properties — DenAccumFracLength and NumAccumFracLength — that let you set the precision for numerator and denominator operations separately.
AccumMode	Determines how the accumulator outputs stored values. Choose from full precision (FullPrecision), or whether to keep the most significant bits (KeepMSB) or least significant bits (KeepLSB) when output results need shorter word length than the accumulator supports. To let you set the word length and the precision (the fraction length) used by the output from the accumulator, set AccumMode to SpecifyPrecision.
AccumWordLength	Sets the word length used to store data in the accumulator/buffer.
Arithmetic	Defines the arithmetic the filter uses. Gives you the options double, single, and fixed. In short, this property defines the operating mode for your filter.
CastBeforeSum	Specifies whether to cast numeric data to the appropriate accumulator format (as shown in the signal flow diagrams) before performing sum operations.

<b>Property Name</b>	<b>Brief Description</b>
CoeffAutoScale	Specifies whether the filter automatically chooses the proper fraction length to represent filter coefficients without overflowing. Turning this off by setting the value to <code>false</code> enables you to change the <code>LatticeFracLength</code> to specify the precision used.
CoeffWordLength	Specifies the word length to apply to filter coefficients.
FilterStructure	Describes the signal flow for the filter object, including all of the active elements that perform operations during filtering—gains, delays, sums, products, and input/output.
InputFracLength	Specifies the fraction length the filter uses to interpret input data.
InputWordLength	Specifies the word length applied to interpret input data.
Lattice	Any lattice structure coefficients.
LatticeFracLength	Sets the fraction length applied to the lattice coefficients.
OutputFracLength	Determines how the filter interprets the filter output data. You can change the value of <code>OutputFracLength</code> when you set <code>OutputMode</code> to <code>SpecifyPrecision</code> .

Property Name	Brief Description
OutputMode	<p>Sets the mode the filter uses to scale the filtered data for output. You have the following choices:</p> <ul style="list-style-type: none"> <li>• <b>AvoidOverflow</b> — directs the filter to set the output data word length and fraction length to avoid causing the data to overflow.</li> <li>• <b>BestPrecision</b> — directs the filter to set the output data word length and fraction length to maximize the precision in the output data.</li> <li>• <b>SpecifyPrecision</b> — lets you set the word and fraction lengths used by the output data from filtering.</li> </ul>
OutputWordLength	<p>Determines the word length used for the output data.</p>
OverflowMode	<p>Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either <b>saturate</b> (limit the output to the largest positive or negative representable value) or <b>wrap</b> (set overflowing values to the nearest representable value using modular arithmetic). The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow — they maintain full precision.</p>
ProductFracLength	<p>For the output from a product operation, this sets the fraction length used to interpret the data. This property becomes writable (you can change the value) when you set <b>ProductMode</b> to <b>SpecifyPrecision</b>.</p>

Property Name	Brief Description
ProductMode	Determines how the filter handles the output of product operations. Choose from full precision ( <b>FullPrecision</b> ), or whether to keep the most significant bit ( <b>KeepMSB</b> ) or least significant bit ( <b>KeepLSB</b> ) in the result when you need to shorten the data words. For you to be able to set the precision (the fraction length) used by the output from the multiplies, you set <b>ProductMode</b> to <b>SpecifyPrecision</b> .
ProductWordLength	Specifies the word length to use for multiplication operation results. This property becomes writable (you can change the value) when you set <b>ProductMode</b> to <b>SpecifyPrecision</b> .
PersistentMemory	Specifies whether to reset the filter states and memory before each filtering operation. Lets you decide whether your filter retains states from previous filtering runs. <b>False</b> is the default setting.
RoundMode	Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths). <ul style="list-style-type: none"><li>• <b>ceil</b> - Round toward positive infinity.</li><li>• <b>convergent</b> - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.</li><li>• <b>fix</b> - Round toward zero.</li><li>• <b>floor</b> - Round toward negative infinity.</li></ul>

Property Name	Brief Description
	<ul style="list-style-type: none"> <li>• <code>nearest</code> - Round toward nearest. Ties round toward positive infinity.</li> <li>• <code>round</code> - Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.</li> </ul> <p>The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always round. Finally, products never overflow — they maintain full precision.</p>
<code>Signed</code>	Specifies whether the filter uses signed or unsigned fixed-point coefficients. Only coefficients reflect this property setting.
<code>StateFracLength</code>	When you set <code>StateAutoScale</code> to <code>false</code> , you enable the <code>StateFracLength</code> property that lets you set the fraction length applied to interpret the filter states.
<code>States</code>	This property contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions. The states use <code>fi</code> objects, with the associated properties from those objects. For details, refer to <code>filtstates</code> in Signal Processing Toolbox documentation or in the Help system.
<code>StateWordLength</code>	Sets the word length used to represent the filter states.

## Examples

Specify a third-order lattice autoregressive filter structure for a `dfilt` object, `hd`, with the following code that creates a fixed-point filter.

## dfilt.latticear


---

```
k = [.66 .7 .44];  
hd1=dfilt.latticear(k);  
hd1.arithmetic='fixed';  
specifyall(hd1);
```

### See Also

```
dfilt | dfilt.latticeallpass | dfilt.latticearma |  
dfilt.latticemamax | dfilt.latticemamin
```

<b>Purpose</b>	Discrete-time, lattice, autoregressive, moving-average filter
<b>Syntax</b>	Refer to <code>dfilt.latticearma</code> in Signal Processing Toolbox documentation.
<b>Description</b>	<p><code>hd = dfilt.latticearma(k)</code> returns a discrete-time, lattice moving-average autoregressive filter object <code>hd</code>, with lattice coefficients, <code>k</code>.</p> <p>Make this filter a fixed-point or single-precision filter by changing the value of the <code>Arithmetic</code> property for the filter <code>hd</code> as follows:</p> <ul style="list-style-type: none"><li>• To change to single-precision filtering, enter <pre>set(hd,'arithmetic','single');</pre></li><li>• To change to fixed-point filtering, enter <pre>set(hd,'arithmetic','fixed');</pre></li></ul> <p>For more information about the property <code>Arithmetic</code>, refer to “Arithmetic” on page 8-19.</p> <p><code>hd</code> <code>dfilt.latticearma</code> returns a default, discrete-time, lattice moving-average, autoregressive filter object <code>hd</code>, with <code>k = []</code>. This filter passes the input through to the output unchanged.</p>
<b>Fixed-Point Filter Structure</b>	<p>The following figure shows the signal flow for the autoregressive lattice filter implemented by <code>dfilt.latticearma</code>. To help you see how the filter processes the coefficients, input, and states of the filter, as well as numerical operations, the figure includes the locations of the formatting objects within the signal flow.</p>



## Notes About the Signal Flow Diagram

To help you understand where and how the filter performs fixed-point arithmetic during filtering, the figure shows various labels associated with data and functional elements in the filter. The following table describes each label in the signal flow and relates the label to the filter properties that are associated with it.

The labels use a common format — a prefix followed by the word “format.” In this use, “format” means the word length and fraction length associated with the filter part referred to by the prefix.

For example, the `InputFormat` label refers to the word length and fraction length used to interpret the data input to the filter. The format properties `InputWordLength` and `InputFracLength` (as shown in the table) store the word length and the fraction length in bits. Or consider `NumFormat`, which refers to the word and fraction lengths (`CoeffWordLength`, `NumFracLength`) associated with representing filter numerator coefficients.

<b>Signal Flow Label</b>	<b>Corresponding Word Length Property</b>	<b>Corresponding Fraction Length Property</b>	<b>Related Properties</b>
InputFormat	InputWordLength	InputFracLength	None
LadderAccumFormat	AccumWordLength	LadderAccumFracLength	AccumMode
LadderFormat	CoeffWordLength	LadderFracLength	CoeffAutoScale
LadderProdFormat	ProductWordLength	LadderProdFracLength	ProductMode
LatticeAccumFormat	AccumWordLength	LatticeAccum-FracLength	AccumMode
LatticeFormat	CoeffWordLength	LatticeFracLength	CoeffAutoScale
LatticeProdFormat	ProductWordLength	LatticeProdFracLength	ProductMode
OutputFormat	OutputWordLength	OutputFracLength	OutputMode
StateFormat	StateWordLength	StateFracLength	States

Most important is the label position in the diagram, which identifies where the format applies.

As one example, look at the label `LatticeProdFormat`, which always follows a coefficient multiplication element in the signal flow. The label indicates that lattice coefficients leave the multiplication element with the word length and fraction length associated with product operations that include coefficients. From reviewing the table, you see that the `LatticeProdFormat` refers to the properties `ProductWordLength`, `LatticeProdFracLength`, and `ProductMode` that fully define the coefficient format after multiply (or product) operations.

## Properties

In this table you see the properties associated with the autoregressive moving-average lattice implementation of `dfilt` objects.

---

**Note** The table lists all the properties that a filter can have. Many of the properties are dynamic, meaning they exist only in response to the settings of other properties. You might not see all of the listed properties all the time. To view all the properties for a filter at any time, use

`get(hd)`

where `hd` is a filter.

---

For further information about the properties of this filter or any `dfilt` object, refer to “Fixed-Point Filter Properties” on page 8-2.

Property Name	Brief Description
AccumFracLength	Specifies the fraction length used to interpret data output by the accumulator. This is a property of FIR filters and lattice filters. IIR filters have two similar properties — <code>DenAccumFracLength</code> and <code>NumAccumFracLength</code> — that let you set the precision for numerator and denominator operations separately.
AccumMode	Determines how the accumulator outputs stored values. Choose from full precision ( <code>FullPrecision</code> ), or whether to keep the most significant bits ( <code>KeepMSB</code> ) or least significant bits ( <code>KeepLSB</code> ) when output results need shorter word length than the accumulator supports. To let you set the word length and the precision (the fraction length) used by the output from the accumulator, set <code>AccumMode</code> to <code>SpecifyPrecision</code> .

Property Name	Brief Description
AccumWordLength	Sets the word length used to store data in the accumulator/buffer.
Arithmetic	Defines the arithmetic the filter uses. Gives you the options <code>double</code> , <code>single</code> , and <code>fixed</code> . In short, this property defines the operating mode for your filter.
CastBeforeSum	Specifies whether to cast numeric data to the appropriate accumulator format (as shown in the signal flow diagrams) before performing sum operations.
CoeffAutoScale	Specifies whether the filter automatically chooses the proper fraction length to represent filter coefficients without overflowing. Turning this off by setting the value to <code>false</code> enables you to change the <code>LatticeFracLength</code> property to specify the precision used.
CoeffWordLength	Specifies the word length to apply to filter coefficients.
FilterStructure	Describes the signal flow for the filter object, including all of the active elements that perform operations during filtering—gains, delays, sums, products, and input/output.
InputFracLength	Specifies the fraction length the filter uses to interpret input data.
InputWordLength	Specifies the word length applied to interpret input data.
Ladder	Stores the ladder coefficients for lattice ARMA ( <code>dfilt.latticearma</code> ) filters.

Property Name	Brief Description
LadderAccumFracLength	Sets the fraction length used to interpret the output from sum operations that include the ladder coefficients. You can change this property value after you set AccumMode to SpecifyPrecision.
LadderFracLength	Determines the precision used to represent the ladder coefficients in ARMA lattice filters.
Lattice	Stores the lattice structure coefficients.
LatticeFracLength	Sets the fraction length applied to the lattice coefficients.
OutputFracLength	Determines how the filter interprets the filter output data. You can change the value of OutputFracLength when you set OutputMode to SpecifyPrecision.
OutputMode	Sets the mode the filter uses to scale the filtered data for output. You have the following choices: <ul style="list-style-type: none"><li>• <b>AvoidOverflow</b> — directs the filter to set the output data word length and fraction length to avoid causing the data to overflow.</li><li>• <b>BestPrecision</b> — directs the filter to set the output data word length and fraction length to maximize the precision in the output data.</li><li>• <b>SpecifyPrecision</b> — lets you set the word and fraction lengths used by the output data from filtering.</li></ul>

<b>Property Name</b>	<b>Brief Description</b>
OutputWordLength	Determines the word length used for the output data.
OverflowMode	Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either saturate (limit the output to the largest positive or negative representable value) or wrap (set overflowing values to the nearest representable value using modular arithmetic). The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow—they maintain full precision.
ProductFracLength	For the output from a product operation, this sets the fraction length used to interpret the data. This property becomes writable (you can change the value) when you set <code>ProductMode</code> to <code>SpecifyPrecision</code> .
ProductMode	Determines how the filter handles the output of product operations. Choose from full precision ( <code>FullPrecision</code> ), or whether to keep the most significant bit ( <code>KeepMSB</code> ) or least significant bit ( <code>KeepLSB</code> ) in the result when you need to shorten the data words. For you to be able to set the precision (the fraction length) used by the output from the multiplies, you set <code>ProductMode</code> to <code>SpecifyPrecision</code> .

Property Name	Brief Description
ProductWordLength	Specifies the word length to use for multiplication operation results. This property becomes writable (you can change the value) when you set ProductMode to SpecifyPrecision.
PersistentMemory	Specifies whether to reset the filter states and memory before each filtering operation. Lets you decide whether your filter retains states from previous filtering runs. False is the default setting.
RoundMode	<p>Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths).</p> <ul style="list-style-type: none"><li>• <code>ceil</code> - Round toward positive infinity.</li><li>• <code>convergent</code> - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.</li><li>• <code>fix</code> - Round toward zero.</li><li>• <code>floor</code> - Round toward negative infinity.</li><li>• <code>nearest</code> - Round toward nearest. Ties round toward positive infinity.</li><li>• <code>round</code> - Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.</li></ul> <p>The choice you make affects only the accumulator and output arithmetic.</p>

Property Name	Brief Description
	Coefficient and input arithmetic always round. Finally, products never overflow — they maintain full precision.
Signed	Specifies whether the filter uses signed or unsigned fixed-point coefficients. Only coefficients reflect this property setting.
StateFracLength	When you set <code>StateAutoScale</code> to <code>false</code> , you enable the <code>StateFracLength</code> property that lets you set the fraction length applied to interpret the filter states.
States	This property contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions. The states use <code>fi</code> objects, with the associated properties from those objects. For details, refer to <code>filtstates</code> in Signal Processing Toolbox documentation or in the Help system.
StateWordLength	Sets the word length used to represent the filter states.

**See Also**

dfilt | dfilt.latticeallpass | dfilt.latticear |  
dfilt.latticemamin | dfilt.latticemamin

# dfilt.latticemamax

---

**Purpose** Discrete-time, lattice, moving-average filter with maximum phase

**Syntax** Refer to `dfilt.latticemamax` in Signal Processing Toolbox documentation.

**Description** `hd = dfilt.latticemamax(k)` returns a discrete-time, lattice, moving-average filter object `hd`, with lattice coefficients `k`.  
Make this filter a fixed-point or single-precision filter by changing the value of the `Arithmetic` property for the filter `hd` as follows:

- To change to single-precision filtering, enter

```
set(hd,'arithmetic','single');
```

- To change to fixed-point filtering, enter

```
set(hd,'arithmetic','fixed');
```

For more information about the property `Arithmetic`, refer to “Arithmetic” on page 8-19.

---

**Note** When the `k` coefficients define a maximum phase filter, the resulting filter in this structure is maximum phase. When your coefficients do not define a maximum phase filter, placing them in this structure does not produce a maximum phase filter.


---

`hd = dfilt.latticemamax` returns a default discrete-time, lattice, moving-average filter object `hd`, with `k = []`. This filter passes the input through to the output unchanged.

## Fixed-Point Filter Structure

The following figure shows the signal flow for the maximum phase implementation of a moving-average lattice filter implemented by `dfilt.latticemamax`. To help you see how the filter processes the coefficients, input, and states of the filter, as well as numerical

operations, the figure includes the locations of the formatting objects within the signal flow.



### Notes About the Signal Flow Diagram

To help you understand where and how the filter performs fixed-point arithmetic during filtering, the figure shows various labels associated with data and functional elements in the filter. The following table describes each label in the signal flow and relates the label to the filter properties that are associated with it.

The labels use a common format — a prefix followed by the word “format.” In this use, “format” means the word length and fraction length associated with the filter part referred to by the prefix.

For example, the InputFormat label refers to the word length and fraction length used to interpret the data input to the filter. The format properties InputWordLength and InputFracLength (as shown in the table) store the word length and the fraction length in bits. Or consider NumFormat, which refers to the word and fraction lengths (CoeffWordLength, NumFracLength) associated with representing filter numerator coefficients.

Signal Flow Label	Corresponding Word Length Property	Corresponding Fraction Length Property	Related Properties
AccumFormat	AccumWordLength	AccumFracLength	AccumMode
InputFormat	InputWordLength	InputFracLength	None
LatticeFormat	CoeffWordLength	LatticeFracLength	CoeffAutoScale
OutputFormat	OutputWordLength	OutputFracLength	OutputMode
ProductFormat	ProductWordLength	ProductFracLength	ProductMode
StateFormat	StateWordLength	StateFracLength	States

Most important is the label position in the diagram, which identifies where the format applies.

As one example, look at the label ProductFormat, which always follows a coefficient multiplication element in the signal flow. The label indicates that coefficients leave the multiplication element with the word length and fraction length associated with product operations that include coefficients. From reviewing the table, you see that the ProductFormat refers to the properties ProductFracLength, ProductWordLength, and ProductMode that fully define the coefficient format after multiply (or product) operations.

## Properties

In this table you see the properties associated with the maximum phase, moving average lattice implementation of dfilt objects.

---

**Note** The table lists all the properties that a filter can have. Many of the properties are dynamic, meaning they exist only in response to the settings of other properties. You might not see all of the listed properties all the time. To view all the properties for a filter at any time, use

```
get(hd)
```

where `hd` is a filter.

---

For further information about the properties of this filter or any `dfilt` object, refer to “Fixed-Point Filter Properties” on page 8-2.

Property Name	Brief Description
<code>AccumFracLength</code>	Specifies the fraction length used to interpret data output by the accumulator. This is a property of FIR filters and lattice filters. IIR filters have two similar properties — <code>DenAccumFracLength</code> and <code>NumAccumFracLength</code> — that let you set the precision for numerator and denominator operations separately.
<code>AccumMode</code>	Determines how the accumulator outputs stored values. Choose from full precision ( <code>FullPrecision</code> ), or whether to keep the most significant bits ( <code>KeepMSB</code> ) or least significant bits ( <code>KeepLSB</code> ) when output results need shorter word length than the accumulator supports. To let you set the word length and the precision (the fraction length) used by the output from the accumulator, set <code>AccumMode</code> to <code>SpecifyPrecision</code> .
<code>AccumWordLength</code>	Sets the word length used to store data in the accumulator/buffer.
<code>Arithmetic</code>	Defines the arithmetic the filter uses. Gives you the options <code>double</code> , <code>single</code> , and <code>fixed</code> . In short, this property defines the operating mode for your filter.
<code>CastBeforeSum</code>	Specifies whether to cast numeric data to the appropriate accumulator format (as shown in the signal flow diagrams) before performing sum operations.

<b>Property Name</b>	<b>Brief Description</b>
CoeffAutoScale	Specifies whether the filter automatically chooses the proper fraction length to represent filter coefficients without overflowing. Turning this off by setting the value to <code>false</code> enables you to change the <code>LatticeFracLength</code> property to specify the precision used.
CoeffWordLength	Specifies the word length to apply to filter coefficients.
FilterStructure	Describes the signal flow for the filter object, including all of the active elements that perform operations during filtering—gains, delays, sums, products, and input/output.
InputFracLength	Specifies the fraction length the filter uses to interpret input data.
InputWordLength	Specifies the word length applied to interpret input data.
Lattice	Any lattice structure coefficients.
LatticeFracLength	Sets the fraction length applied to the lattice coefficients.
OutputFracLength	Determines how the filter interprets the filter output data. You can change the value of <code>OutputFracLength</code> when you set <code>OutputMode</code> to <code>SpecifyPrecision</code> .

Property Name	Brief Description
OutputMode	<p>Sets the mode the filter uses to scale the filtered data for output. You have the following choices:</p> <ul style="list-style-type: none"> <li>• <b>AvoidOverflow</b> — directs the filter to set the output data word length and fraction length to avoid causing the data to overflow.</li> <li>• <b>BestPrecision</b> — directs the filter to set the output data word length and fraction length to maximize the precision in the output data.</li> <li>• <b>SpecifyPrecision</b> — lets you set the word and fraction lengths used by the output data from filtering.</li> </ul>
OutputWordLength	<p>Determines the word length used for the output data.</p>
OverflowMode	<p>Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either <b>saturate</b> (limit the output to the largest positive or negative representable value) or <b>wrap</b> (set overflowing values to the nearest representable value using modular arithmetic). The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow—they maintain full precision.</p>
ProductFracLength	<p>For the output from a product operation, this sets the fraction length used to interpret the data. This property becomes writable (you can change the value) when you set <b>ProductMode</b> to <b>SpecifyPrecision</b>.</p>

Property Name	Brief Description
ProductMode	Determines how the filter handles the output of product operations. Choose from full precision ( <b>FullPrecision</b> ), or whether to keep the most significant bit ( <b>KeepMSB</b> ) or least significant bit ( <b>KeepLSB</b> ) in the result when you need to shorten the data words. For you to be able to set the precision (the fraction length) used by the output from the multiplies, you set <b>ProductMode</b> to <b>SpecifyPrecision</b> .
ProductWordLength	Specifies the word length to use for multiplication operation results. This property becomes writable (you can change the value) when you set <b>ProductMode</b> to <b>SpecifyPrecision</b> .
PersistentMemory	Specifies whether to reset the filter states and memory before each filtering operation. Lets you decide whether your filter retains states from previous filtering runs. <b>False</b> is the default setting.
RoundMode	Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths). <ul style="list-style-type: none"><li>• <b>ceil</b> - Round toward positive infinity.</li><li>• <b>convergent</b> - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.</li><li>• <b>fix</b> - Round toward zero.</li><li>• <b>floor</b> - Round toward negative infinity.</li></ul>

Property Name	Brief Description
	<ul style="list-style-type: none"> <li>• nearest - Round toward nearest. Ties round toward positive infinity.</li> <li>• round - Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.</li> </ul> <p>The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always round. Finally, products never overflow — they maintain full precision.</p>
Signed	Specifies whether the filter uses signed or unsigned fixed-point coefficients. Only coefficients reflect this property setting.
StateFracLength	When you set <code>StateAutoScale</code> to <code>false</code> , you enable the <code>StateFracLength</code> property that lets you set the fraction length applied to interpret the filter states.
States	This property contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions. The states use <code>fi</code> objects, with the associated properties from those objects. For details, refer to <code>filtstates</code> in Signal Processing Toolbox documentation or in the Help system.
StateWordLength	Sets the word length used to represent the filter states.

## Examples

Specify a fourth-order lattice, moving-average, maximum phase filter structure for a `dfilt` object, `hd`, with the following code:

## dfilt.latticemamax

---

```
k = [.66 .7 .44 .33];  
hd = dfilt.latticemamax(k);
```

### See Also

[dfilt](#) | [dfilt.latticeallpass](#) | [dfilt.latticear](#) |  
[dfilt.latticearma](#) | [dfilt.latticemamin](#)

**Purpose** Discrete-time, lattice, moving-average filter with minimum phase

**Syntax** Refer to `dfilt.latticemamin` in Signal Processing Toolbox documentation.

**Description** `hd = dfilt.latticemamin(k)` returns a discrete-time, lattice, moving-average, minimum phase, filter object `hd`, with lattice coefficients `k`.

Make this filter a fixed-point or single-precision filter by changing the value of the `Arithmetic` property for the filter `hd` as follows:

- To change to single-precision filtering, enter

```
set(hd,'arithmetic','single');
```

- To change to fixed-point filtering, enter

```
set(hd,'arithmetic','fixed');
```

For more information about the property `Arithmetic`, refer to “Arithmetic” on page 8-19.

---

**Note** When the `k` coefficients define a minimum phase filter, the resulting filter in this structure is minimum phase. When your coefficients do not define a minimum phase filter, placing them in this structure does not produce a minimum phase filter.


---

`hd = dfilt.latticemamin` returns a default discrete-time, lattice, moving-average, minimum phase, filter object `hd`, with `k=[ ]`. This filter passes the input through to the output unchanged.

## Fixed-Point Filter Structure

The following figure shows the signal flow for the minimum phase implementation of a moving-average lattice filter implemented by `dfilt.latticemamin`. To help you see how the filter processes the coefficients, input, and states of the filter, as well as numerical

operations, the figure includes the locations of the formatting objects within the signal flow.



## Notes About the Signal Flow Diagram

To help you understand where and how the filter performs fixed-point arithmetic during filtering, the figure shows various labels associated with data and functional elements in the filter. The following table describes each label in the signal flow and relates the label to the filter properties that are associated with it.

The labels use a common format — a prefix followed by the word “format.” In this use, “format” means the word length and fraction length associated with the filter part referred to by the prefix.

For example, the InputFormat label refers to the word length and fraction length used to interpret the data input to the filter. The format properties InputWordLength and InputFracLength (as shown in the table) store the word length and the fraction length in bits. Or consider NumFormat, which refers to the word and fraction lengths (CoeffWordLength, NumFracLength) associated with representing filter numerator coefficients.

Signal Flow Label	Corresponding Word Length Property	Corresponding Fraction Length Property	Related Properties
AccumFormat	AccumWordLength	AccumFracLength	AccumMode
InputFormat	InputWordLength	InputFracLength	None
LatticeFormat	CoeffWordLength	LatticeFracLength	CoeffAutoScale
OutputFormat	OutputWordLength	OutputFracLength	OutputMode
ProductFormat	ProductWordLength	ProductFracLength	ProductMode
StateFormat	StateWordLength	StateFracLength	States

Most important is the label position in the diagram, which identifies where the format applies.

As one example, look at the label ProductFormat, which always follows a coefficient multiplication element in the signal flow. The label indicates that coefficients leave the multiplication element with the word length and fraction length associated with product operations that include coefficients. From reviewing the table, you see that the ProductFormat refers to the properties ProductFracLength, ProductWordLength, and ProductMode that fully define the coefficient format after multiply (or product) operations.

## Properties

In this table you see the properties associated with the minimum phase, moving average lattice implementation of dfilt objects.

---

**Note** The table lists all the properties that a filter can have. Many of the properties are dynamic, meaning they exist only in response to the settings of other properties. You might not see all of the listed properties all the time. To view all the properties for a filter at any time, use

```
get(hd)
```

where `hd` is a filter.

---

## dfilt.latticemamin

---

For further information about the properties of this filter or any `dfilt` object, refer to “Fixed-Point Filter Properties” on page 8-2.

Property Name	Brief Description
<code>AccumFracLength</code>	Specifies the fraction length used to interpret data output by the accumulator. This is a property of FIR filters and lattice filters. IIR filters have two similar properties — <code>DenAccumFracLength</code> and <code>NumAccumFracLength</code> — that let you set the precision for numerator and denominator operations separately.
<code>AccumMode</code>	Determines how the accumulator outputs stored values. Choose from full precision ( <code>FullPrecision</code> ), or whether to keep the most significant bits ( <code>KeepMSB</code> ) or least significant bits ( <code>KeepLSB</code> ) when output results need shorter word length than the accumulator supports. To let you set the word length and the precision (the fraction length) used by the output from the accumulator, set <code>AccumMode</code> to <code>SpecifyPrecision</code> .
<code>AccumWordLength</code>	Sets the word length used to store data in the accumulator/buffer.
<code>Arithmetic</code>	Defines the arithmetic the filter uses. Gives you the options <code>double</code> , <code>single</code> , and <code>fixed</code> . In short, this property defines the operating mode for your filter.
<code>CastBeforeSum</code>	Specifies whether to cast numeric data to the appropriate accumulator format (as shown in the signal flow diagrams) before performing sum operations.

Property Name	Brief Description
CoeffAutoScale	Specifies whether the filter automatically chooses the proper fraction length to represent filter coefficients without overflowing. Turning this off by setting the value to <code>false</code> enables you to change the <code>LatticeFracLength</code> property to specify the precision used.
CoeffWordLength	Specifies the word length to apply to filter coefficients.
FilterStructure	Describes the signal flow for the filter object, including all of the active elements that perform operations during filtering — gains, delays, sums, products, and input/output.
InputFracLength	Specifies the fraction length the filter uses to interpret input data.
InputWordLength	Specifies the word length applied to interpret input data.
Lattice	Any lattice structure coefficients.
LatticeFracLength	Sets the fraction length applied to the lattice coefficients.
OutputFracLength	Determines how the filter interprets the filter output data. You can change the value of <code>OutputFracLength</code> when you set <code>OutputMode</code> to <code>SpecifyPrecision</code> .

Property Name	Brief Description
OutputMode	<p>Sets the mode the filter uses to scale the filtered data for output. You have the following choices:</p> <ul style="list-style-type: none"><li>• <b>AvoidOverflow</b> — directs the filter to set the output data word length and fraction length to avoid causing the data to overflow.</li><li>• <b>BestPrecision</b> — directs the filter to set the output data word length and fraction length to maximize the precision in the output data.</li><li>• <b>SpecifyPrecision</b> — lets you set the word and fraction lengths used by the output data from filtering.</li></ul>
OutputWordLength	<p>Determines the word length used for the output data.</p>
OverflowMode	<p>Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either <b>saturate</b> (limit the output to the largest positive or negative representable value) or <b>wrap</b> (set overflowing values to the nearest representable value using modular arithmetic). The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow — they maintain full precision.</p>
ProductFracLength	<p>For the output from a product operation, this sets the fraction length used to interpret the data. This property becomes writable (you can change the value) when you set <b>ProductMode</b> to <b>SpecifyPrecision</b>.</p>

Property Name	Brief Description
ProductMode	Determines how the filter handles the output of product operations. Choose from full precision ( <code>FullPrecision</code> ), or whether to keep the most significant bit ( <code>KeepMSB</code> ) or least significant bit ( <code>KeepLSB</code> ) in the result when you need to shorten the data words. For you to be able to set the precision (the fraction length) used by the output from the multiplies, you set <code>ProductMode</code> to <code>SpecifyPrecision</code> .
ProductWordLength	Specifies the word length to use for multiplication operation results. This property becomes writable (you can change the value) when you set <code>ProductMode</code> to <code>SpecifyPrecision</code> .
PersistentMemory	Specifies whether to reset the filter states and memory before each filtering operation. Lets you decide whether your filter retains states from previous filtering runs. <code>False</code> is the default setting.
RoundMode	Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths). <ul style="list-style-type: none"> <li>• <code>ceil</code> - Round toward positive infinity.</li> <li>• <code>convergent</code> - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.</li> <li>• <code>fix</code> - Round toward zero.</li> <li>• <code>floor</code> - Round toward negative infinity.</li> </ul>

Property Name	Brief Description
	<ul style="list-style-type: none"><li>• nearest - Round toward nearest. Ties round toward positive infinity.</li><li>• round - Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.</li></ul> <p>The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always round. Finally, products never overflow — they maintain full precision.</p>
Signed	Specifies whether the filter uses signed or unsigned fixed-point coefficients. Only coefficients reflect this property setting.
StateFracLength	When you set <code>StateAutoScale</code> to <code>false</code> , you enable the <code>StateFracLength</code> property that lets you set the fraction length applied to interpret the filter states.
States	This property contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions. The states use <code>fi</code> objects, with the associated properties from those objects. For details, refer to <code>filtstates</code> in Signal Processing Toolbox documentation or in the Help system.
StateWordLength	Sets the word length used to represent the filter states.

## Examples

Specify a third-order lattice, moving-average, minimum phase, filter structure for a `dfilt` object, `hd`, with the following code:

```
k = [.66 .7 .44];  
hd = dfilt.latticemamin(k);
```

### See Also

```
dfilt | dfilt.latticeallpass | dfilt.latticear |  
dfilt.latticearma | dfilt.latticemamax
```

# dfilt.parallel

**Purpose** Discrete-time, parallel structure filter


**Syntax** Refer to `dfilt.parallel` in Signal Processing Toolbox documentation.

**Description** `hd = dfilt.parallel(hd1,hd2,...)` returns a discrete-time filter object `hd`, which is a structure of two or more `dfilt` filter objects, `hd1`, `hd2`, and so on arranged in parallel.

You can also use the standard notation to combine filters into a parallel structure.

`parallel(hd1,hd2,...)`

In this syntax, `hd1`, `hd2`, and so on can be a mix of `dfilt` objects, `mfilt` objects, and `adaptfilt` objects.



`hd1`, `hd2`, and so on can be fixed-point filters. All filters in the parallel structure must be the same arithmetic format — double, single, or fixed. `hd`, the filter returned, inherits the format of the individual filters.

**See Also** `dfilt` | `dfilt.cascade` | `parallel` | `dfilt.cascade` | `dfilt.parallel`

**Purpose** Discrete-time, scalar filter

**Syntax** Refer to `dfilt.scalar` in Signal Processing Toolbox documentation.

**Description** `dfilt.scalar(g)` returns a discrete-time, scalar filter object with gain `g`, where `g` is a scalar.

Make this filter a fixed-point or single-precision filter by changing the value of the `Arithmetic` property for the filter `hd` as follows:

- To change to single-precision filtering, enter

```
set(hd,'arithmetic','single');
```

- To change to fixed-point filtering, enter

```
set(hd,'arithmetic','fixed');
```

For more information about the property `Arithmetic`, refer to “`Arithmetic`” on page 8-19.

`dfilt.scalar` returns a default, discrete-time scalar gain filter object `hd`, with gain 1.

**Properties** In this table you see the properties associated with the scalar implementation of `dfilt` objects.

---

**Note** The table lists all the properties that a filter can have. Many of the properties are dynamic, meaning they exist only in response to the settings of other properties. You might not see all of the listed properties all the time. To view all the properties for a filter at any time, use

```
get(hd)
```

where `hd` is a filter.

---

For further information about the properties of this filter or any `dfilt` object, refer to “Fixed-Point Filter Properties” on page 8-2.

Property Name	Brief Description
Arithmetic	Defines the arithmetic the filter uses. Gives you the options <code>double</code> , <code>single</code> , and <code>fixed</code> . In short, this property defines the operating mode for your filter.
CastBeforeSum	Specifies whether to cast numeric data to the appropriate accumulator format (as shown in the signal flow diagrams) before performing sum operations.
CoeffAutoScale	Specifies whether the filter automatically chooses the proper fraction length to represent filter coefficients without overflowing. Turning this off by setting the value to <code>false</code> enables you to change the <code>CoeffFracLength</code> property to specify the precision used.
CoeffFracLength	Set the fraction length the filter uses to interpret coefficients. <code>CoeffFracLength</code> is always available, but it is read-only until you set <code>CoeffAutoScale</code> to <code>false</code> .
CoeffWordLength	Specifies the word length to apply to filter coefficients.
FilterStructure	Describes the signal flow for the filter object, including all of the active elements that perform operations during filtering — gains, delays, sums, products, and input/output.
Gain	Returns the gain for the scalar filter. Scalar filters do not alter the input data except by adding gain.
InputFracLength	Specifies the fraction length the filter uses to interpret input data.

Property Name	Brief Description
InputWordLength	Specifies the word length applied to interpret input data.
OutputFracLength	Determines how the filter interprets the filter output data. You can change the value of OutputFracLength when you set OutputMode to SpecifyPrecision.
OutputMode	<p>Sets the mode the filter uses to scale the filtered data for output. You have the following choices:</p> <ul style="list-style-type: none"> <li>• <b>AvoidOverflow</b> — directs the filter to set the output data word length and fraction length to avoid causing the data to overflow.</li> <li>• <b>BestPrecision</b> — directs the filter to set the output data word length and fraction length to maximize the precision in the output data.</li> <li>• <b>SpecifyPrecision</b> — lets you set the word and fraction lengths used by the output data from filtering.</li> </ul>
OutputWordLength	Determines the word length used for the output data.
OverflowMode	Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either <b>saturate</b> (limit the output to the largest positive or negative representable value) or <b>wrap</b> (set overflowing values to the nearest representable value using modular arithmetic). The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow — they maintain full precision.


Property Name	Brief Description
PersistentMemory	Specifies whether to reset the filter states and memory before each filtering operation. Lets you decide whether your filter retains states from previous filtering runs. <code>False</code> is the default setting.
RoundMode	<p>Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths).</p> <ul style="list-style-type: none"><li>• <code>ceil</code> - Round toward positive infinity.</li><li>• <code>convergent</code> - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.</li><li>• <code>fix</code> - Round toward zero.</li><li>• <code>floor</code> - Round toward negative infinity.</li><li>• <code>nearest</code> - Round toward nearest. Ties round toward positive infinity.</li><li>• <code>round</code> - Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.</li></ul> <p>The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always round. Finally, products never overflow — they maintain full precision.</p>

Property Name	Brief Description
Signed	Specifies whether the filter uses signed or unsigned fixed-point coefficients. Only coefficients reflect this property setting.
States	This property contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions. The states use <code>fi</code> objects, with the associated properties from those objects. For details, refer to <code>filtstates</code> in Signal Processing Toolbox documentation or in the Help system.

## Examples

Create a direct-form I filter object `hd_filt` and a scalar object with a gain of 3 `hd_gain` and cascade them together.

```
b = [0.3 0.6 0.3];
a = [1 0 0.2];
hd_filt = dfilt.df1(b,a);
hd_gain = dfilt.scalar(3);
hd_cascade=cascade(hd_gain,hd_filt);
fvtool_handle = fvtool(hd_filt,hd_gain,hd_cascade);
legend(fvtool_handle,'IIR Filter (direct form I)',...
'Gain','Cascaded Filter');
```



To view the stages of the cascaded filter, use

```
hd.Stage(1)
```

and

```
hd.Stage(2)
```

## See Also

```
dfilt | dfilt.cascade
```

**Purpose** Wave digital allpass filter

**Syntax** `hd = dfilt.wdfallpass(c)`

**Description** `hd = dfilt.wdfallpass(c)` constructs an allpass wave digital filter structure given the allpass coefficients in vector `c`.

Vector `c` must have, one, two, or four elements (filter coefficients). Filters with three coefficients are not supported. When you use `c` with four coefficients, the first and third coefficients must be 0.

Given the coefficients in `c`, the transfer function for the wave digital allpass filter is defined by

$$H(z) = \frac{c(n) + c(n-1)z^{-1} + \dots + z^{-n}}{1 + c(1)z^{-1} + \dots + c(n)z^{-n}}$$

Internally, the allpass coefficients are converted to wave digital filters for filtering. Note that `dfilt.wdfallpass` allows only stable filters. Also note that the leading coefficient in the denominator, a 1, does not need to be included in vector `c`.

Use the constructor `dfilt.cascadewdfallpass` to cascade `wdfallpass` filters.

To compare these filters to other similar filters, `dfilt.wdfallpass` and `dfilt.cascadewdfallpass` filters have the same number of multipliers as the non-wave digital filters `dfilt.allpass` and `dfilt.cascadeallpass`. However, the wave digital filters use fewer states and they may require more adders in the filter structure.

Wave digital filters are usually used to create other filters. This toolbox uses them to implement halfband filters, which the first example in Examples demonstrates. They are most often building blocks for filters.

**Properties** In the next table, the row entries are the filter properties and a brief description of each property.

Property Name	Brief Description
AllpassCoefficients	Contains the coefficients for the allpass wave digital filter object
FilterStructure	Describes the signal flow for the filter object, including all of the active elements that perform operations during filtering — gains, delays, sums, products, and input/output.
PersistentMemory	Specifies whether to reset the filter states and memory before each filtering operation. Lets you decide whether your filter retains states from previous filtering runs. <code>False</code> is the default setting.
States	This property contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions. They also provide linkage between the sections of a multisection filter, such as a cascade filter. For details, refer to <code>filtstates</code> in Signal Processing Toolbox documentation or in the Help system.

## Filter Structure

When you change the order of the wave digital filters in the cascade, the filter structure changes as well.

As shown in this example, `realizemd1` lets you see the filter structure used for your filter, if you have Simulink installed.


```
section11=0.8;  
section12=[1.5,0.7];  
section13=[1.8,0.9];  
hd1=dfilt.cascadewdfallpass(section11,section12,section13);
```

```
section21=[0.8,0.4];  
section22=[0,1.5,0,0.7];
```

```
section23=[0,1.8,0,0.9];  
hd2=dfilt.cascadewdfallpass(section21,section22,section23);  
% If you have Simulink  
realizemdl(hd2)
```


hd1 has this filter structure with three sections.

# dfilt.wdfallpass



The filter structure for `hd2` is somewhat different, with the different orders and interconnections between the three sections.

# dfilt.wdfallpass




## Examples

Construct a second-order wave digital allpass filter with two coefficients. Note that to use `realizemdl`, you must have Simulink.

```
c = [1.5,0.7];
hd = dfilt.wdfallpass(c);
```

With Simulink installed, `realizemdl` returns this structure for `hd`.



## See Also

`dfilt` | `dfilt.allpass` | `dfilt.latticeallpass` |  
`dfilt.cascadewdfallpass` | `dfilt.cascadeallpass` |  
`mfilt.iirdecim` | `mfilt.iirinterp`

# disp

---

## Purpose

Filter properties and values

## Syntax

```
disp(hd)
disp(ha)
disp(hm)
```

## Description

Similar to omitting the closing semicolon from an expression on the command line, except that `disp` does not display the variable name. `disp` lists the property names and property values for any filter object, such as a `dfilt` object or `adaptfilt` object.

The following examples illustrate the default display for an adaptive filter `ha` and a multirate filter `hm`.

```
ha=adaptfilt.rls;
fprintf('Displaying properties for default RLS adaptive filter:\n');
fprintf('\n');
disp(ha)
pause(2);
hm=mfilt.cicdecim(6);
fprintf('Displaying properties for cascaded integrator-comb decimator\n');
fprintf('with a decimation factor of 6:\n');
fprintf('\n');
disp(hm)
```

## See Also

`set`

**Purpose**

Cast fixed-point filter to use double-precision arithmetic

**Syntax**

```
hd = double(h)
```

**Description**

`hd = double(h)` returns a new filter `hd` that has the same structure and coefficients as `h`, but whose arithmetic property is set to `double` to use double-precision arithmetic for filtering. `double(h)` is not the same as the `reffilter(h)` function:

- `hd`, the filter returned by `double` has the quantized coefficients of `h` represented in double-precision floating-point format
- The reference filter returned by `reffilter` has double-precision, floating-point coefficients that have not been quantized.

You might find `double(h)` useful to isolate the effects of quantizing the coefficients of a filter by using `double` to create a filter `hd` that operates in double-precision but uses the quantized filter coefficients.

**Examples**

Use the same filter, once with fixed-point arithmetic and once with floating-point, to compare fixed-point filtering with double-precision floating-point filtering.

```
h = dfilt.dffir(firgr(27,[0 .4 .6 1],...  
[1 1 0 0])); % Lowpass filter.  
% Set h to use fixed-point arithmetic to filter.  
% Quantize the coeffs.  
h.arithmetic = 'fixed';  
% Cast h to double-precision  
hd = double(h);  
% Set up an input signal.  
n = 0:99; x = sin(0.7*pi*n(:));  
y = filter(h,x); % Fixed-point output.  
yd = filter(hd,x); % Floating-point output.  
FixedFloatNormDiff=norm(yd-double(y),inf);
```

**See Also**

`reffilter`

# dsp.util.getLogLogsArray

---

**Purpose** Return logged signal as MATLAB array

**Syntax**

```
Array = dsp.util.getLogLogsArray(LogObject,Format2D,  
    'SignalPath',PATH)  
Array = dsp.util.getLogLogsArray(LogObject,Format2D,  
    'SignalName',NAME)
```

**Description**

Array =  
dsp.util.getLogLogsArray(LogObject,Format2D,'SignalPath',PATH)  
returns a MATLAB array that contains a signal in LogObject. You  
must specify the PATH to the signal in LogObject using the  
Name, Value pair argument.

Array =  
dsp.util.getLogLogsArray(LogObject,Format2D,'SignalName',NAME)  
returns a MATLAB array that contains a signal in LogObject. You  
must specify the NAME of the signal in LogObject using the  
Name, Value pair argument.

## Input Arguments

### LogObject

Specify the name of the object that contains your logged signals. Valid classes for LogObject depend on the syntax you use:

- When you specify PATH as a dsp.util.SignalPath object, LogObject can be either a Simulink.SimulationData.Dataset or Simulink.SimulationData.Signal object.
- When you specify PATH as the full path to a block in a Simulink model, LogObject must be a Simulink.SimulationData.Dataset object.
- When you specify the NAME of a signal in LogObject, LogObject can be an object of class timeseries, Simulink.SimulationData.Dataset, or Simulink.SimulationData.Signal.

### Format2D

Specify a logical value to determine whether the function formats 3-D logged signals as a 2-D or 3-D MATLAB array. When you set this property to `true`, the function uses the following formula to format the 3-D logged signal into a 2-D MATLAB array:

```
dim = size(signal);  
ntimes = dim(1)*dim(3);  
Array = reshape(permute(signal,[1 3 2]),[ntimes dim(2)]);
```

When you set this property to `false`, the function returns the logged signal without any reformatting.

## PATH

Specify the path to the logged signal in `LogObject`. You can specify the path using a `dsp.util.SignalPath` object, or you can provide the full path to a block in your Simulink model. To get the full path to a block in your Simulink model, use the `gcb` command.

## NAME

Specify the name of the signal in `LogObject`.

## Output Arguments

### Array

The output `Array` is a MATLAB array that contains the specified logged signal. When the input is a 3-D logged signal, the dimensions of `Array` depend on the value you specify for `Format2D`:

- When `Format2D` is `true`, `Array` is a 2-D MATLAB array.
- When `Format2D` is `false`, `Array` is a 3-D MATLAB array.

When the input is not a 3-D signal, the dimensions of the output `Array` match those of the input.

# dsp.util.getLogArrays

---

## Examples

---

**Note** To run the following examples, you must first load `ex_logouts.mat` which contains a `Simulink.SimulationData.Dataset` object. Alternatively, you can open and simulate the `ex_log_utils` Simulink model. Doing so will log signals and generate the necessary `ex_logouts` object.

---

### Extract a unique signal named **Signal3x4** from `ex_logouts`.

```
dsp.util.getLogArrays(ex_logouts, true, 'SignalName', 'Signal3x4')
```

### Extract a unique signal named **Signal3x4** from `ex_logouts` as a **3-D** array.

```
dsp.util.getLogArrays(ex_logouts, false, 'SignalName', 'Signal3x4')
```

### Find and extract a specific signal from multiple signals that have the same name.

Because `ex_logouts` contains multiple signals named `Signal2x4`, you must use the `dsp.util.getSignalPath` function to find the paths to each of those signals.

```
paths = dsp.util.getSignalPath(ex_logouts, 'Signal2x4')
% paths is a 2x1 array of dsp.util.SignalPath objects. Next, examine
% the BlockPath property of each paths object.
paths.BlockPath
% Find the signal path that corresponds to the logged signal you are
% interested in. For example paths(2). You can then use the
% dsp.util.getLogArrays function and provide the 'SignalPath' name-value
% pair argument.
dsp.util.getLogArrays(ex_logouts, true, 'SignalPath', paths(2))
```

### Find and extract a signal from a bus.

Use the `dsp.util.getSignalPath` function to get paths to all the signals in the bus named `Bus1`.

```
buspaths = dsp.util.getSignalPath(ex_logout, 'Bus1')
% buspaths is a 2x1 array of dsp.util.SignalPath objects. Examine the
% BusElement property of each buspaths object.
buspaths.BusElement
% Select a signal path. For example buspaths(1). This is the path to the
% signal named 'Signal3x4' in bus 'Bus' that is contained in bus 'Bus1'.
% Now that you have the path to the signal, call dsp.util.getLogsArray
% using the 'SignalPath' name-value pair argument.
dsp.util.getLogsArray(ex_logout, true, 'SignalPath', buspaths(1))
```

## See Also

```
dsp.util.getSignalPath | dsp.util.SignalPath
| Simulink.SimulationData.BlockPath
| Simulink.SimulationData.Dataset
| Simulink.SimulationData.Signal | timeseries
```

## How To

- “Export Signal Data Using Signal Logging”
- “Configure a Signal for Signal Logging”
- “Specify the Signal Logging Data Format”

# dsp.util.getSignalPath

---

**Purpose** Paths to logged signals

**Syntax** Path = dsp.util.getSignalPath(LogObject, SignalName)

**Description** Path = dsp.util.getSignalPath(LogObject, SignalName) returns all paths to signals in LogObject with name SignalName. The output Path is a dsp.util.SignalPath object or an array of dsp.util.SignalPath objects.

**Tips**

- To return the path to an unnamed signal in LogObject, set SignalName to the empty string (' ').

**Input Arguments**

**LogObject**  
Specify the name of the object that contains your logged signals. LogObject must be a Simulink.SimulationData.Dataset or Simulink.SimulationData.Signal object.

**SignalName**  
Specify the name of a logged signal in LogObject.

**Output Arguments**

**Path**  
The output Path contains the path to all signals named SignalName in LogObject.

- If LogObject contains a unique signal with name SignalName, the function returns a single dsp.util.SignalPath object.
- If LogObject contains more than one signal with the specified name, the function returns an array of dsp.util.SignalPath objects.

## Examples

---

**Note** To run the following examples, you must first load `ex_logstdout.mat` which contains a `Simulink.SimulationData.Dataset` object. Alternatively, you can open and simulate the `ex_log_utils` Simulink model. Doing so will log signals and generate the necessary `ex_logstdout` object.

---

### Find and extract a specific signal from multiple signals that have the same name.

Because `ex_logstdout` contains multiple signals named `Signal2x4`, you must use the `dsp.util.getSignalPath` function to find the paths to each of those signals.

```
paths = dsp.util.getSignalPath(ex_logstdout, 'Signal2x4')
% paths is a 2x1 array of dsp.util.SignalPath objects. Next, examine
% the BlockPath property of each paths object.
paths.BlockPath
% Find the signal path that corresponds to the logged signal you are
% interested in. For example paths(2). You can then use the
% dsp.util.getLogArray function and provide the 'SignalPath' name-value
% pair argument.
dsp.util.getLogArray(ex_logstdout, true, 'SignalPath', paths(2))
```

### Find and extract a signal from a bus.

Use the `dsp.util.getSignalPath` function to get paths to all the signals in the bus named `Bus1`.

```
buspaths = dsp.util.getSignalPath(ex_logstdout, 'Bus1')
% buspaths is a 2x1 array of dsp.util.SignalPath objects. Examine the
% BusElement property of each buspaths object.
buspaths.BusElement
% Select a signal path. For example buspaths(1). This is the path to t
% signal named 'Signal3x4' in bus 'Bus' that is contained in bus 'Bus'
% Now that you have the path to the signal, call dsp.util.getLogArray
% using the 'SignalPath' name-value pair argument.
dsp.util.getLogArray(ex_logstdout, true, 'SignalPath', buspaths(1))
```

# dsp.util.getSignalPath

---

## See Also

`dsp.util.getLogsArray` | `dsp.util.SignalPath`  
| `Simulink.SimulationData.Dataset`  
| `Simulink.SimulationData.Signal` |  
`Simulink.SimulationData.updateDatasetFormatLogging`

## How To

- “Export Signal Data Using Signal Logging”
- “Configure a Signal for Signal Logging”
- “Specify the Signal Logging Data Format”

## Purpose

Properties of paths to signals

## Description

`dsp.util.SignalPath` objects contain path information for signals in `Simulink.SimulationData.Dataset` objects. You get `Simulink.SimulationData.Dataset` objects when you use `Dataset` logging to log signals from a Simulink model.

## Construction

`dsp.util.SignalPath` objects are returned by the `dsp.util.getSignalPath` function and can be used as input to the `dsp.util.getLogArrays` function.

## Properties

### SignalName

Contains the name of the signal output by the block at the specified `BlockPath`.

### BlockPath

Provides the `Simulink.SimulationData.BlockPath` to the block in the Simulink model from which the signal originates.

### PortIndex

Provides the output port index of the block from which the logged signal `SignalName` originates.

### BusElement

Provides a string description of a signal in a logged bus. When `SignalPath` is not a logged bus, this property will be an empty string.

If the `SignalPath` object is a logged bus signal, the `BusElement` string will be formatted as follows:

- When the bus contains a nonbus signal, `BusElement` is the name of that signal.
- When the bus contains a nested bus that contains a nonbus signal, `BusElement` will be a dot-separated string consisting of

## dsp.util.SignalPath

---

the name of the nested bus followed by the name of the non-bus signal. For example: `nestbus.signal1`

- When the bus contains nested busses within nested busses to any depth, `BUSElement` will be a dot-separated string. This string contains each of the nested bus names, and ends with the nonbus signal name. For example: `outernestedbus.innernestedbus.signal1`

### See Also

`dsp.util.getLogsArray` | `dsp.util.getSignalPath`  
| `Simulink.SimulationData.BlockPath` |  
`Simulink.SimulationData.Dataset`

<b>Purpose</b>	Identify whether blocks in model are current, deprecated, or obsolete
<b>Syntax</b>	<pre>dsp_links dsp_links('modelname')</pre>
<b>Description</b>	<p>dsp_links returns a structure with three elements that identify whether the DSP System Toolbox blocks in the current model are current, deprecated, or obsolete. Each element is one of the three block categories and contains a cell array of strings. Each string is the name of a library block in the current model.</p> <p>dsp_links('modelname') returns the three-element structure for the specified model.</p>
<b>Definitions</b>	<p><b>Obsolete Blocks</b></p> <p><i>Obsolete blocks</i> are blocks that the toolbox no longer supports. In some cases, these blocks no longer function properly.</p> <p><b>Deprecated Blocks</b></p> <p><i>Deprecated blocks</i> are blocks that the toolbox still supports but are likely to become obsolete in a future release. Refer to the block reference page for suggested replacements.</p> <p><b>Current Blocks</b></p> <p><i>Current blocks</i> are blocks that the toolbox supports and that represent the latest block functionality.</p>
<b>Examples</b>	<p>Display block support information for the specified model, and then find the name of the first current block:</p> <pre>sys = 'dspcochlear'; load_system(sys)      % Load the dspcochlear model links = dsp_links(sys) % Run dsp_links on the model links.current{1}      % Find the name of the first current block</pre>
<b>See Also</b>	liblinks

# dsplib

---

**Purpose** Open top-level DSP System Toolbox library

**Syntax** `dsplib`


**Description** `dsplib` opens the top-level DSP System Toolbox block library model.

**Examples** View and gain access to the DSP System Toolbox blocks:

```
dsplib
```

**Alternatives** To view and gain access to the DSP System Toolbox blocks using the Simulink library browser:

- Type `simulink` at the MATLAB command line, and then expand the DSP System Toolbox node in the library browser.



- Click the Simulink icon from the MATLAB Toolstrip.

**Purpose** Configure Simulink environment for signal processing systems

**Syntax** dspstartup

**Description** dspstartup configures Simulink environment parameters with settings appropriate for a typical signal processing project. You can use the dspstartup function in the following ways:

- At the MATLAB command line. Doing so configures the Simulink environment in your current session for signal processing projects.
- By adding a call to the dspstartup function from your startup.m file. When you do so, MATLAB configures your Simulink environment for typical signal processing projects each time you launch MATLAB.

When the function successfully configures your Simulink environment, MATLAB displays the following message in the command window.

```
Changed default Simulink settings for signal processing systems (dspstartup.m).
```

The dspstartup.m file executes the following commands. See set\_param in the Simulink documentation.

```
set_param(0, ...  
    'SingleTaskRateTransMsg', 'error', ...  
    'multiTaskRateTransMsg', 'error', ...  
    'Solver',                  'fixedstepdiscrete', ...  
    'SolverMode',              'SingleTasking', ...  
    'StartTime',                '0.0', ...  
    'StopTime',                 'inf', ...  
    'FixedStep',                'auto', ...  
    'SaveTime',                 'off', ...  
    'SaveOutput',               'off', ...  
    'AlgebraicLoopMsg',        'error', ...  
    'SignalLogging',           'off');
```

## Examples

Add a call to the `dspstartup` function from your `startup.m` file:

- 1 To find out if there is a `startup.m` file on your MATLAB path, run the following code at the MATLAB command line:

```
which startup.m
```

- 2 If MATLAB returns '`startup.m`' not found., see “Startup Options” in the MATLAB documentation to learn more about the `startup.m` file.

If MATLAB returns a path to your `startup.m` file, open that file for editing.

```
edit startup.m
```

- 3 Add a call to the `dspstartup` function. Your `startup.m` file now resembles the following code sample:

```
%STARTUP  Startup file
%  This file is executed when MATLAB starts up, if it exists
%  anywhere on the path.  In this case, the startup.m file
%  runs the dspstartup.m file to configure the Simulink
%  environment with settings appropriate for typical
%  signal processing projects.

dspstartup;
```

## See Also

`startup`

## How To

- “Configure the Simulink Environment for Signal Processing Models”

**Purpose**

Elliptic filter using specification object

**Syntax**

```
hd = design(d,'ellip')
hd = design(d,'ellip',designoption,value,designoption,...
value,...)
```

**Description**

hd = design(d,'ellip') designs an elliptical IIR digital filter using the specifications supplied in the object h.

hd = design(d,'ellip',designoption,value,designoption,... value,...) returns an elliptical or Cauer FIR filter where you specify design options as input arguments.

To determine the available design options, use designopts with the specification object and the design method as input arguments as shown.

```
designopts(d,'method')
```

For complete help about using ellip, refer to the command line help system. For example, to get specific information about using ellip with d, the specification object, enter the following at the MATLAB prompt.

```
help(d,'ellip')
```

**Examples**

These examples demonstrate how to use ellip to design filters based on filter specification objects.

**Example 1**


Construct the default bandpass filter specification object and design an elliptic filter.

```
d = fdesign.bandpass;
hd = design(d,'ellip','matchexactly','both');
```

## Example 2

Construct a lowpass object with order, passband-edge frequency, stopband-edge frequency, and passband ripple specifications, and then design an elliptic filter.


```
d = fdesign.lowpass('n,fp,fst,ap',6,20,25,.8,80);
design(d,'ellip'); % Starts FVtool to display the filter.
```



## Example 3

Construct a lowpass object with filter order, passband edge frequency, passband ripple, and stopband attenuation specifications, and then design an elliptic filter.

```
d = fdesign.lowpass('n,fp,ap,ast',6,20,.8,60,80);
design(d,'ellip'); % Starts FVTool to display the filter.
```



**See Also**

[butter](#) | [cheby1](#) | [cheby2](#)

# euclidfactors

---

**Purpose** Euclid factors for multirate filter

**Syntax** `[lo,mo] = euclidfactors(hm)`

**Description** `[lo,mo] = euclidfactors(hm)` returns integer factors `lo` and `mo` such that  $(lo*L)-(mo*M) = -1$ . `L` and `M` are relatively prime and represent the interpolation and decimation factors of the multirate filter `hm`.

`euclidfactors` works with the multirate filters `mfilt.firfracdecim` and `mfilt.firfracinterp`. You cannot return `lo` and `mo` for decimators or interpolators.

**Examples** Use an FIR fractional decimator, with `L = 5` and `M = 7`, to show what `euclidfactors` does.

Indeed,  $(lo*L)-(mo*M) = (4*5)-(3*7) = -1$ .

**See Also** `polyphase` | `nstates`


<b>Purpose</b>	Equiripple single-rate or multirate FIR filter from specification object
<b>Syntax</b>	<pre>hd = design(d,'equiripple') hd = design(d,'equiripple',designoption,value,designoption, ...value,...)</pre>
<b>Description</b>	<p><code>hd = design(d,'equiripple')</code> designs an equiripple FIR digital filter or multirate filter using the specifications supplied in the object <code>d</code>. Equiripple filter designs minimize the maximum ripple in the passbands and stopbands.</p> <p><code>hd</code> is either a <code>dfilt</code> object (a single-rate digital filter) or an <code>mfilt</code> object (a multirate digital filter) depending on the <code>Specification</code> property of the filter specification object <code>d</code> and the specifications object type — halfband or interpolator.</p> <p>When you use <code>equiripple</code> with Nyquist filter specification objects, you might encounter design cases where the filter design does not converge. Convergence errors occur mostly at large filter orders, or small transition widths, or large stopband attenuations. These specifications, alone or combined, can cause design failures. For more information, refer to <code>fdesign.nyquist</code> in the online Help system.</p> <p><code>hd = design(d,'equiripple',designoption,value,designoption,...value,...)</code> returns an equiripple FIR filter where you specify design options as input arguments.</p> <p>To determine the available design options, use <code>designopts</code> with the specification object and the design method as input arguments as shown.</p> <pre>designopts(d,'method')</pre> <p>For complete help about using <code>equiripple</code>, refer to the command line help system. For example, to get specific information about using <code>equiripple</code> with <code>d</code>, the specification object, enter the following at the MATLAB prompt.</p> <pre>help(d,'equiripple')</pre>

## Examples

Here is an example of designing a single-rate equiripple filter from a halfband filter specification object. Notice the `help` command used to learn about the options for the specification object and method.

```
d = fdesign.halfband('tw,ast',0.1,80);  
designmethods(d)  
help(d,'equiripple')  
designopts(d,'equiripple')  
hd = design(d,'equiripple','stopbandshape','flat');  
fvtool(hd);
```

Displaying the filter in FVTool shows the equiripple nature of the filter.



`equiripple` also designs multirate filters. This example generates a halfband interpolator filter.

```
d = fdesign.interpolator(2); % Interpolation factor = 2.  
hd = design(d,'equiripple');
```

This final example designs an equiripple filter with a direct-form structure by specifying the **filterstructure** argument. To set the design options for the filter, use the `designopts` method and options object `opts`.

```
d = fdesign.lowpass('fp,fst,ap,ast');  
opts=designopts(d,'equiripple')  
opts.FilterStructure='dffirt'  
opts.MinPhase=1;  
opts.DensityFactor=20;  
opts  
hd=design(d,'equiripple',opts)
```

---

**Note** The `MaxPhase` design option for equiripple FIR filters is currently only available for lowpass, highpass, bandpass, and bandstop filters.

---

## See Also

`fdesign.nyquist` | `firls` | `kaiserwin`

# fcfwrite

---

**Purpose** Write file containing filter coefficients

**Syntax**

```
fcfwrite(h)
fcfwrite(h,filename)
fcfwrite(...,'fmt')
```

**Description** `fcfwrite(h)` writes a filter coefficient ASCII file in a folder you choose, or your current MATLAB working folder. `h` can be a single filter object or a vector of filter objects. On execution, `fcfwrite` opens the **Export Filter Coefficients to .FCF File** dialog box to let you assign a file name for the output file. You can choose the destination folder within this dialog as well.

The default file name is `untitled.fcf`. When you have DSP System Toolbox software, you can use `fcfwrite(h)` to write filter coefficient files for multirate filters, adaptive filters, and discrete-time filters.

`fcfwrite(h,filename)` writes the filter coefficients and general information to a text file called `filename` in your present MATLAB working folder and opens the file in the MATLAB editor for you to review or modify.

If you do not include a file extension in `filename`, `fcfwrite` adds the extension `fcf` to `filename`.

`fcfwrite(...,'fmt')` writes the filter coefficients in the format specified by the input argument `fmt`. Valid `fmt` values are `hex` for hexadecimal, `dec` for decimal, or `bin` for binary representation of the filter coefficients.

**Examples** To demonstrate `fcfwrite`, create a fixed-point IIR filter at the command line, and then write the filter coefficients to a file named `iirfilter.fcf`.

```
d=fdesign.lowpass;
hd=design(d,'butter');
set(hd,'arithmetic','fixed');
fcfwrite(hd,'iirfilter.fcf');
```

Here is the output from fcfwrite as it appears in the MATLAB editor. Not shown here is the filename — `iirfilter.fcf` as specified and some comments at the top of the file.

```
%
%
% Coefficient Format: Decimal
%
% Discrete-Time IIR Filter (real)
% -----
% Filter Structure      : Direct-Form II, Second-Order
%                       Sections
% Number of Sections   : 13
% Stable                : Yes
% Linear Phase         : No
% Arithmetic           : fixed
% Numerator             : s16,13 -> [-4 4)
% Denominator          : s16,14 -> [-2 2)
% Scale Values         : s16,14 -> [-2 2)
% Input                : s16,15 -> [-1 1)
% Section Input        : s16,8 -> [-128 128)
% Section Output       : s16,10 -> [-32 32)
% Output               : s16,10 -> [-32 32)
% State                : s16,15 -> [-1 1)
% Numerator Prod       : s32,28 -> [-8 8)
% Denominator Prod    : s32,29 -> [-4 4)
% Numerator Accum      : s40,28 -> [-2048 2048)
% Denominator Accum   : s40,29 -> [-1024 1024)
% Round Mode          : convergent
% Overflow Mode       : wrap
% Cast Before Sum     : true
```

SOS matrix:

```
1  2  1  1  -0.22222900390625  0.88262939453125
1  2  1  1  -0.19903564453125  0.68621826171875
1  2  1  1  -0.18060302734375  0.5303955078125
```

```
1 2 1 1 -0.1658935546875 0.40570068359375
1 2 1 1 -0.154052734375 0.305419921875
1 2 1 1 -0.14453125 0.22479248046875
1 2 1 1 -0.136962890625 0.16015625
1 2 1 1 -0.13092041015625 0.10906982421875
1 2 1 1 -0.126220703125 0.06939697265625
1 2 1 1 -0.12274169921875 0.0399169921875
1 2 1 1 -0.12030029296875 0.01947021484375
1 2 1 1 -0.118896484375 0.0074462890625
1 1 0 1 -0.0592041015625 0
```

Scale Values:

```
0.41510009765625
0.371826171875
0.33746337890625
0.3099365234375
0.287841796875
0.27008056640625
0.25579833984375
0.2445068359375
0.23577880859375
0.22930908203125
0.22479248046875
0.22216796875
0.47039794921875
1
```

To write two or more filters out to one file, provide the filters as a vector to `fcfwrite`:


```
fcfwrite([hd hd1 hd2])
```

## See Also

```
adaptfilt | mfilt | dfilt
```

---

<b>Purpose</b>	Open Filter Design and Analysis Tool
<b>Syntax</b>	fdatool
<b>Description</b>	<p>fdatool opens the Filter Design and Analysis Tool (FDATool). Use this tool to:</p> <ul style="list-style-type: none"><li>• Design filters</li><li>• Quantize filters (with DSP System Toolbox software installed)</li><li>• Analyze filters</li><li>• Modify existing filter designs</li><li>• Create multirate filters (with DSP System Toolbox software installed)</li><li>• Realize Simulink models of quantized, direct-form, FIR filters (with DSP System Toolbox software installed)</li><li>• Perform digital frequency transformations of filters (with DSP System Toolbox software installed)</li></ul> <p>Refer to “Use FDATool with DSP System Toolbox Software” for more information about using the analysis, design, and quantization features of FDATool. For general information about using FDATool, refer to “FDATool” in Signal Processing Toolbox documentation.</p> <p>When you open FDATool and you have DSP System Toolbox software installed, FDATool incorporates features that are added by DSP System Toolbox software. With DSP System Toolbox software installed, FDATool lets you design and analyze quantized filters, as well as convert quantized filters to various filter structures, transform filters, design multirate filters, and realize models of filters.</p>



Use the buttons on the sidebar to configure the design area to use various tools in FDATool.


**Set Quantization Parameters** — provides access to the properties of the quantizers that compose a quantized filter. When you click **Set Quantization Parameters**, you see FDATool displaying the

quantization options at the bottom of the dialog box (the design area), as shown in the figure.

**Transform Filter** — clicking this button opens the *Frequency Transformations* pane so you can use digital frequency transformations to change the magnitude response of your filter.

**Create a multirate filter** — clicking this button switches FDATool to multirate filter design mode so you can design interpolators, decimators, and fractional rate change filters.

**Realize Model** — starting from your quantized, direct-form, FIR filter, clicking this button creates a Simulink model of your filter structure in new model window.



Other options in the menu bar let you convert the filter structure to a new structure, change the order of second-order sections in a filter, or change the scaling applied to the filter, among many possibilities.

## **Tips**

By incorporating many advanced filter design methods from DSP System Toolbox software, FDATool provides more design methods than the SPTool Filter Designer.

## **See Also**

`fdatool` | `fvtool` | `sptool`

**Purpose** Filter specification object

**Syntax**

```
d = fdesign.response  
d = fdesign.response(spec)  
d = fdesign.response(...,Fs)  
d = fdesign.response(...,magunits)
```

**Description** **Filter Specification Objects**

`d = fdesign.response` returns a filter specification object `d`, of filter response `response`. To create filters from `d`, use one of the design methods listed in “Using Filter Design Methods with Specification Objects” on page 7-484

---

**Note** Several of the filter response types described below are only available if your installation includes the DSP System Toolbox. The DSP System Toolbox significantly expands the functionality available for the specification, design, and analysis of filters.

---

Here is how you design filters using `fdesign`.

- 1** Use `fdesign.response` to construct a filter specification object.
- 2** Use `designmethods` to determine which filter design methods work for your new filter specification object.
- 3** Use `design` to apply your filter design method from step 2 to your filter specification object to construct a filter object.
- 4** Use `FVTool` to inspect and analyze your filter object.

---

**Note** `fdesign` does not create filters. `fdesign` returns a filter specification object that contains the specifications for a filter, such as the passband cutoff or attenuation in the stopband. To design a filter `hd` from a filter specification object `d`, use `d` with a filter design method such as `butter` —`hd = design(d, 'butter')`.

---

For more guidance about using `fdesign`, refer to the examples in “Getting Started”. Alternatively, type the following at the MATLAB prompt for more information:

```
help fdesign
```

*response* can be one of the entries in the following table that specify the filter response desired, such as a bandstop filter or an interpolator.

<b>fdesign Response String</b>	<b>Description</b>
<code>arbgrpdelay</code>	<code>fdesign.arbgrpdelay</code> creates an object to specify allpass arbitrary group delay filters. Requires the DSP System Toolbox
<code>arbmag</code>	<code>fdesign.arbmag</code> creates an object to specify IIR filters that have arbitrary magnitude responses defined by the input arguments.
<code>arbmagnphase</code>	<code>fdesign.arbmagnphase</code> creates an object to specify IIR filters that have arbitrary magnitude and phase responses defined by the input arguments. Requires the DSP System Toolbox.
<code>audioweighting</code>	<code>fdesign.audioweighting</code> creates a filter specification object for audio weighting filters. The supported audio weighting types are: A, C, C-message, ITU-T 0.41, and ITU-R 468-4 weighting. Requires the DSP System Toolbox

<b>fdesign Response String</b>	<b>Description</b>
bandpass	<code>fdesign.bandpass</code> creates an object to specify bandpass filters.
bandstop	<code>fdesign.bandstop</code> creates an object to specify bandstop filters.
ciccomp	<code>fdesign.ciccomp</code> creates an object to specify filters that compensate for the CIC decimator or interpolator response curves. Requires the DSP System Toolbox.
comb	<code>fdesign.comb</code> creates an object to specify a notching or peaking comb filter. Requires the DSP System Toolbox.
decimator	<code>fdesign.decimator</code> creates an object to specify decimators. Requires the DSP System Toolbox.
differentiator	<code>fdesign.differentiator</code> creates an object to specify an FIR differentiator filter.
fracdelay	<code>fdesign.fracdelay</code> creates an object to specify fractional delay filters. Requires the DSP System Toolbox.
halfband	<code>fdesign.halfband</code> creates an object to specify halfband filters. Requires the DSP System Toolbox.
highpass	<code>fdesign.highpass</code> creates an object to specify highpass filters.
hilbert	<code>fdesign.hilbert</code> creates an object to specify an FIR Hilbert transformer.
interpolator	<code>fdesign.interpolator</code> creates an object to specify interpolators. Requires the DSP System Toolbox.

<b>fdesign Response String</b>	<b>Description</b>
isinchp	<code>fdesign.isinchp</code> creates an object to specify an inverse sinc highpass filter. Requires the DSP System Toolbox.
isinclp	<code>fdesign.isinclp</code> creates an object to specify an inverse sinc lowpass filters. Requires the DSP System Toolbox.
lowpass	<code>fdesign.lowpass</code> creates an object to specify lowpass filters.
notch	<code>fdesign.notch</code> creates an object to specify notch filters. Requires the DSP System Toolbox.
nyquist	<code>fdesign.nyquist</code> creates an object to specify nyquist filters. Requires the DSP System Toolbox.
octave	<code>fdesign.octave</code> creates an object to specify octave and fractional octave filters. Requires the DSP System Toolbox.
parameq	<code>fdesign.parameq</code> creates an object to specify parametric equalizer filters. Requires the DSP System Toolbox.
peak	<code>fdesign.peak</code> creates an object to specify peak filters. Requires the DSP System Toolbox.
polysrc	<code>fdesign.polysrc</code> creates an object to specify polynomial sample-rate converter filters. Requires the DSP System Toolbox.
pulseshaping	<code>fdesign.pulseshaping</code> creates an object to specify pulse-shaping filters.
rsrc	<code>fdesign.rsrc</code> creates an object to specify rational-factor sample-rate converters. Requires the DSP System Toolbox.

Use the doc `fdesign.response` syntax at the MATLAB prompt to get help on a specific structure. Using doc in a syntax like

```
doc fdesign.lowpass
doc fdesign.bandstop
```

gets more information about the lowpass or bandstop structure objects.

Each response has a property `Specification` that defines the specifications to use to design your filter. You can use defaults or specify the `Specification` property when you construct the specifications object.

With the strings for the `Specification` property, you provide filter constraints such as the filter order or the passband attenuation to use when you construct your filter from the specification object.

## Properties

`fdesign` returns a filter specification object. Every filter specification object has the following properties.

Property Name	Default Value	Description
Response	Depends on the chosen type	Defines the type of filter to design, such as an interpolator or bandpass filter. This is a read-only value.
Specification	Depends on the chosen type	Defines the filter characteristics used to define the desired filter performance, such as the cutoff frequency $F_c$ or the filter order $N$ .

Property Name	Default Value	Description
Description	Depends on the filter type you choose	Contains descriptions of the filter specifications used to define the object, and the filter specifications you use when you create a filter from the object. This is a read-only value.
NormalizedFrequency	Logical true	Determines whether the filter calculation uses normalized frequency from 0 to 1, or the frequency band from 0 to $F_s/2$ , the sampling frequency. Accepts either true or false without single quotation marks. Audio weighting filters do not support normalized frequency.

In addition to these properties, filter specification objects may have other properties as well, depending on whether they design `dfilt` objects or `mfilt` objects.

Added Properties for <code>mfilt</code> Objects	Description
DecimationFactor	Specifies the amount to decrease the sampling rate. Always a positive integer.
InterpolationFactor	Specifies the amount to increase the sampling rate. Always a positive integer.
PolyphaseLength	Polyphase length is the length of each polyphase subfilter that composes the decimator or interpolator or rate-change

Added Properties for mfilt Objects	Description
	factor filters. Total filter length is the product of p1 and the rate change factors. p1 must be an even integer.

`d = fdesign.response(spec)`. In `spec`, you specify the variables to use that define your filter design, such as the passband frequency or the stopband attenuation. The specifications are applied to the filter design method you choose to design your filter.

For example, when you create a default lowpass filter specification object, `fdesign.lowpass` sets the passband frequency `Fp`, the stopband frequency `Fst`, the stopband attenuation `Ast`, and the passband ripple `Ap` :

```
H = fdesign.lowpass
% Without a terminating semicolon
% the filter specifications are displayed
```

The default specification '`Fp,Fst,Ap,Ast`' is only one of the possible specifications for `fdesign.lowpass`. To see all available specifications:

```
H = fdesign.lowpass;
set(H, 'specification')
```

The DSP System Toolbox software supports all available specification strings. The Signal Processing Toolbox supports a subset of the specification strings. See the reference pages for the filter specification object to determine which specification strings your installation supports.

One important note is that the specification string you choose determines which design methods apply to the filter specifications object.

Specifications that do not contain the filter order result in minimum order designs when you invoke the `design` method:

```
d = fdesign.lowpass;
% Specification is Fp,Fst,Ap,Ast
Hd = design(d,'equiripple');
length(Hd.Numerator) % returns 43
% Filter order is 42
fvtool(Hd) %view magnitude
```

`d = fdesign.response(...,Fs)` specifies the sampling frequency in Hz to use in the filter specifications. The sampling frequency is a scalar trailing all other input arguments. If you specify a sampling frequency, all frequency specifications are in Hz.

`d = fdesign.response(...,magunits)` specifies the units for any magnitude specification you provide in the input arguments. `magunits` can be one of the following strings:

- 'linear' — specify the magnitude in linear units
- 'dB' — specify the magnitude in decibels
- 'squared' — specify the magnitude in power units

When you omit the `magunits` argument, `fdesign` assumes that all magnitudes are in decibels. Note that `fdesign` stores all magnitude specifications in decibels (converting to decibels when necessary) regardless of how you specify the magnitudes.

## Using Filter Design Methods with Specification Objects

After you create a filter specification object, you use a filter design method to implement your filter with a selected algorithm. Use `designmethods` to determine valid design methods for your filter specification object.

```
d = fdesign.lowpass('N,Fc,Ap,Ast',10,0.2,0.5,40);
designmethods(d)
% Design FIR equiripple filter
hd = design(d,'equiripple');
```

When you use any of the design methods without providing an output argument, the resulting filter design appears in FVTool by default.

Along with filter design methods, `fdesign` works with supporting methods that help you create filter specification objects or determine which design methods work for a given specifications object.

<b>Supporting Function</b>	<b>Description</b>
<code>setspecs</code>	Set all of the specifications simultaneously.
<code>designmethods</code>	Return the design methods.
<code>designopts</code>	Return the input arguments and default values that apply to a specifications object and method

You can set filter specification values by passing them after the `Specification` argument, or by passing the values without the `Specification` string.

Filter object constructors take the input arguments in the same order as `setspecs` and the order in the strings for `Specification`. Enter `doc setspecs` at the prompt for more information about using `setspecs`.

When the first input to `fdesign` is not a valid `Specification` string like `'n,fc'`, `fdesign` assumes that the input argument is a filter specification and applies it using the default `Specification` string —`fp,fst,ap,ast` for a lowpass object, for example.

## Examples

The following examples require only the Signal Processing Toolbox.

### Example 1—Bandstop Filter

A bandstop filter specification object for data sampled at 8 kHz. The stopband between 2 and 2.4 kHz is attenuated at least 80 dB:

```
H = fdesign.bandstop('Fp1,Fst1,Fst2,Fp2,Ap1,Ast,Ap2',...
    1600,2000,2400,2800,1,80,1,8000);
```

### Example 2—Lowpass Filter

A lowpass filter specification object for data sampled at 10 kHz. The passband frequency is 500 Hz and the stopband frequency is 750 Hz.

The passband ripple is set to 1 dB and the required attenuation in the stopband is 80 dB.

```
H = fdesign.lowpass('Fp,Fst,Ap,Ast',500,750,1,80,10000);
```

### Example 3—Highpass Filter

A default highpass filter specification object.

```
H = fdesign.highpass % Creates specifications object.  
H.Description
```

Notice the correspondence between the property values in **Specification** and **Description** — in **Description** you see in words the definitions of the variables shown in **Specification**.

### Example 4—Filter Specification and Design

Lowpass Butterworth filter specification object

Use a filter specification object to construct a lowpass Butterworth filter with default **Specification** 'Fp,Fst,Ap,Ast'. Set the passband edge frequency to  $0.4\pi$  radians/sample, a stopband frequency of  $0.5\pi$  radians/sample, a passband ripple of 1 dB, and 80 dB of stopband attenuation.

```
d = fdesign.lowpass(0.4,0.5,1,80);
```


Determine which design methods apply to d.

```
designmethods(d)
```

You can use d and the butter design method to design a Butterworth filter.

```
hd = design(d,'butter','matchexactly','passband');  
fvtool(hd);
```

The resulting filter magnitude response shown by FVTool appears in the following figure.



If you have the DSP System Toolbox software installed, the preceding figure appears with the filter specification mask.

## See Also

`designmethods` | `designopts` | `fdatool` | `filterbuilder` | `fvtool`

# fdesign.arbgrpdelay

---

**Purpose** Arbitrary group delay filter specification object

**Syntax**

```
D = fdesign.arbgrpdelay(SPEC)
D = fdesign.arbgrpdelay(SPEC,SPEC1,SPEC2,...)
D = fdesign.arbgrpdelay(N,F,Gd)
D = fdesign.arbgrpdelay(...,Fs)
```

**Description** Arbitrary group delay filters are allpass filters you can use for correcting phase distortion introduced by other filters. `fdesign.arbgrpdelay` uses an iterative least  $p$ -th norm optimization procedure to minimize the phase response error [1].

`D = fdesign.arbgrpdelay(SPEC)` specifies an allpass arbitrary group delay filter with the `Specification` property set to `SPEC`. See “Input Arguments” on page 7-489 for a description of supported specifications.

`D = fdesign.arbgrpdelay(SPEC,SPEC1,SPEC2,...)` initializes the allpass arbitrary group delay filter specification object with specifications `SPEC1,SPEC2,...`. See `SPEC` for a description of supported specifications.

`D = fdesign.arbgrpdelay(N,F,Gd)` specifies an allpass arbitrary group delay filter. The filter order is equal to `N`, frequency vector equal to `F`, and group delay vector equal to `Gd`. See `SPEC` for a description of the filter order, frequency vector, and group delay vector inputs. See the example Allpass Filter with Arbitrary Group Delay for an example using this syntax.

`D = fdesign.arbgrpdelay(...,Fs)` specifies the sampling frequency in hertz as a trailing scalar. If you do not specify a sampling frequency, all frequencies are normalized frequencies and group delay values are in samples. If you specify a sampling frequency, group delay values are in seconds.

**Tips** If your arbitrary group delay design produces the error `Poorly conditioned Hessian matrix`, attempt one or more of the following:

- Set the `MaxPoleRadius` IIR lp norm design option to some number less than 1. Set this option when you design your filter with the syntax:

```
design(d, 'iirlpnorm', 'MaxPoleRadius', 0.95)
```

See the Frequency Dispersion and Multiband Delay Equalization examples for the use of the `MaxPoleRadius` design option.

- Reduce the order of your filter design.

## Input Arguments

### SPEC

Specification string. `SPEC` is one of the following two strings. The entries are not case sensitive.

- 'N,F,Gd'
- 'N,B,F,Gd'

The string entries are defined as follows:

- **N** — Filter order. This value must be an even positive integer. The numerator and denominator orders are both equal to `N`. “Allpass Systems” on page 7-491 explains why the numerator and denominator filter orders are equal and the order must be even in `fdesign.arbgrpdelay`.
- **F** — Frequency vector for the group delay specifications. The elements of the frequency vector must increase monotonically. If you do not specify a sampling frequency, `Fs`, in hertz, the frequencies are normalized frequencies. For a single-band design, the first element of the normalized frequency vector must be zero and the last element must be 1. These correspond to 0 and  $\pi$  radians/sample respectively. For multiband designs, the union of the frequency vectors must range from [0,1].

If you specify a sampling frequency, `Fs`, the first element of the frequency vector in a single-band design must be 0. The last element must be the Nyquist frequency, `Fs/2`. For multiband designs, the union of the frequency vectors must range from [0,`Fs/2`].

# fdesign.arbgrpdelay

---

- **Gd** — Group delay vector. A vector with nonnegative elements equal in length to the frequency vector, **F**. The elements of **Gd** specify the nonnegative group delay at the corresponding element of the frequency vector, **F**.

If you do not specify a sampling frequency, **F<sub>s</sub>**, in Hertz, the group delays are in samples. If you specify a sampling frequency, the group delays are in seconds.

- **B** — Number of frequency bands. If you use this specification, you must specify a frequency and group delay vector for each band. The union of the frequency vectors must range from [0,1] in normalized frequency, or [0,**F<sub>s</sub>**/2] when a sampling frequency is specified. The elements in the union of the frequency bands must be monotonically increasing.

For example:

```
filterorder = 14;
freqband1 = [0 0.1 0.4]; grpdelay1 = [1 2 3];
freqband2 = [0.5 0.8 1]; grpdelay2 = [3 2 1];
D = fdesign.arbgrpdelay('N,B,F,Gd',filterorder,2,freqband1,grpdelay1,freqband2,grpdelay2)
```

**Default:** 'N,F,Gd'

## **F<sub>s</sub>**

Sampling frequency. Specify the sampling frequency as a trailing positive scalar after all other input arguments. Specifying a sampling frequency forces the group delay units to be in seconds. If you specify a sampling frequency, the first element of the frequency vector must be 0. The last element must be the Nyquist frequency, **F<sub>s</sub>**/2.

## **Output Arguments**

### **D**

Filter specification object. An allpass arbitrary group delay filter specification object containing the following modifiable properties: **Specification**, **NormalizedFrequency**, **FilterOrder**, **Frequencies**, and **GroupDelay**.

Use the `normalizefreq` method to change the `NormalizedFrequency` property after construction.

## Definitions **Group Delay in Discrete-Time Filter Design**

The frequency response of a rational discrete-time filter is:

$$H(e^{j\omega}) = \frac{B(e^{j\omega})}{A(e^{j\omega})}$$

The argument of the frequency response as a function of the angle,  $\omega$ , is referred to as the *phase response*.

The negative of the first derivative of the argument with respect to  $\omega$  is the group delay.

$$\tau(\omega) = -\frac{d}{d\omega} \text{Arg}(H(e^{j\omega}))$$

Systems with nonlinear phase responses have nonconstant group delay, which causes dispersion of the frequency components of the signal. You may not want this phase distortion even if the magnitude distortion introduced by the filter produces the desired effect. See [Frequency Dispersion](#) for an illustration of frequency dispersion resulting from nonconstant group delay.

In these cases, you can cascade the frequency-selective filter with an allpass filter that compensates for the group delay. This process is often referred to as *delay equalization*.

### Allpass Systems

The general form of an allpass system function with a real-valued impulse response is:

$$H_{ap}(z) = \prod_{k=1}^M \frac{z^{-1} - d_k}{1 - d_k z^{-1}} \prod_{k=1}^N \frac{(z^{-1} - c_k)(z^{-1} - c_k^*)}{(1 - c_k z^{-1})(1 - c_k^* z^{-1})}$$

where the  $d_k$  denote the real-valued poles and the  $c_k$  denote the complex-valued poles, which occur in conjugate pairs.

The preceding equation demonstrates that allpass systems with real-valued impulse responses have  $2N+M$  zeros and poles. The poles and zeros occur in pairs with reciprocal magnitudes. The filter order is always the same for the numerator and denominator.

Because `fdesign.arbgrpdelay` uses robust second-order section (biquad) filter structures to implement the allpass arbitrary group delay filter, the filter order must be even.

## Examples


Construct a signal consisting of two discrete-time windowed sinusoids (wave packets) with disjoint time support to illustrate frequency dispersion. One discrete-time sinusoid has a frequency of  $\pi/2$  radians/sample and the other has a frequency of  $\pi/4$  radians/sample. There are 9 periods of the higher-frequency sinusoid that precede 5 periods of the lower-frequency signal.

Create the signal.

```
x = zeros(300,1);  
x(1:36) = cos(pi/2*(0:35)).*hamming(36)';  
x(40:40+39) = cos(pi/4*(0:39)).*hamming(40)';
```

Create an arbitrary group delay filter that delays the higher-frequency wave packet by approximately 100 samples.

```
N = 18;  
f = 0:.1:1;  
gd = ones(size(f));  
% Delay pi/2 radians/sample by 100 samples  
gd(6) = 100;  
d = fdesign.arbgrpdelay(N,f,gd);  
Hd = design(d,'iirlpnorm','MaxPoleRadius',0.9);  
% Visualize the group delay  
fvtool(Hd,'analysis','grpdelay');
```




Filter the input signal with the arbitrary group delay filter and illustrate the frequency dispersion. The high-frequency wave packet, which initially preceded the low-frequency wave packet, now occurs later because of the nonconstant group delay.

```
y = filter(Hd,x);
subplot(211)
plot(x); title('Input Signal');
grid on; ylabel('Amplitude');
subplot(212);
plot(y); title('Output Signal'); grid on;
```

# fdesign.arbgrpdelay

---

```
xlabel('Samples'); ylabel('Amplitude');
```




---

Design an allpass filter with an arbitrary group delay.

```
N = 10;  
f = [0 0.02 0.04 0.06 0.08 0.1 0.25 0.5 0.75 1];  
g = [5 5 5 5 5 5 4 3 2 1];  
w = [2 2 2 2 2 2 1 1 1 1];  
hgd = fdesign.arbgrpdelay(N,f,g);  
Hgd = design(hgd,'iirlpnorm','Weights',w,'MaxPoleRadius',0.95);
```

```
fvtool(Hgd,'Analysis','grpdelay') ;
```




Perform multiband delay equalization outside the stopband.

```
Fs = 1e3;  
Hcheby2 = design(fdesign.bandstop('N,Fst1,Fst2,Ast',10,150,400,60,Fs));  
f1 = 0.0:0.5:150; % Hz  
g1 = grpdelay(Hcheby2,f1,Fs) ./ Fs; % seconds  
f2 = 400:0.5:500; % Hz  
g2 = grpdelay(Hcheby2,f2,Fs) ./ Fs; % seconds
```

# fdesign.arbgrpdelay

```
maxg = max([g1 g2]);  
% Design an arbitrary group delay allpass filter to equalize the group  
% delay of the bandstop filter. Use an order 18 multiband design and spec  
% two bands.  
hgd = fdesign.arbgrpdelay('N,B,F,Gd',18,2,f1,maxg-g1,f2,maxg-g2,Fs);  
Hgd = design(hgd,'iirlpnorm','MaxPoleRadius',0.95);  
Hcascade = cascade(Hcheby2,Hgd);  
hft = fvtool(Hcheby2,Hgd,Hcascade,'Analysis','grpdelay','Fs',Fs);  
legend(hft,'Original Bandstop Filter','Allpass Arbitrary Group Delay  
'Delay Equalization','Location','North');
```



## Algorithms

fdesign.arbgrpdelay uses a least  $p$ -th norm iterative optimization described in [1].

## References

[1] Antoniou, A. *Digital Signal Processing: Signals, Systems, and Filters.*, New York:McGraw-Hill, 2006, pp. 719–771.

## Alternatives

iirgrpdelay — Returns an allpass arbitrary group delay filter. The iirgrpdelay function returns the numerator and denominator coefficients. This behavior differs from that of fdesign.arbgrpdelay, which returns the filter in second-order sections. iirgrpdelay accepts only normalized frequencies.

## See Also

fdesign | design | iirgrpdelay

## How To

- “Design a Filter in Fdesign — Process Overview”

# fdesign.arbmag

---

**Purpose** Arbitrary response magnitude filter specification object

**Syntax**

```
D = fdesign.arbmag
D = fdesign.arbmag(SPEC)
D = fdesign.arbmag(SPEC,specvalue1,specvalue2,...)
D = fdesign.arbmag(specvalue1,specvalue2,specvalue3)
D = fdesign.arbmag(...,Fs)
```

**Description** D = fdesign.arbmag constructs an arbitrary magnitude filter specification object D.

D = fdesign.arbmag(SPEC) initializes the Specification property to SPEC. The input argument SPEC must be one of the strings shown in the following table. Specification strings are not case sensitive.

---

**Note** Specifications strings marked with an asterisk require the DSP System Toolbox software.

---

- 'N,F,A' — Single band design (default)
- 'F,A,R' — Single band minimum order design \*
- 'N,B,F,A' — Multiband design
- 'N,B,F,A,C' — Constrained multiband design \*
- 'B,F,A,R' — Multiband minimum order design \*
- 'Nb,Na,F,A' — Single band design \*
- 'Nb,Na,B,F,A' — Multiband design \*

The string entries are defined as follows:

- A — Amplitude vector. Values in A define the filter amplitude at frequency points you specify in f, the frequency vector. If you use A, you must use F as well. Amplitude values must be real. For complex values designs, use fdesign.arbmagnphase.
- B — Number of bands in the multiband filter

- **C** — Constrained band flag. This enables you to constrain the passband ripple in your multiband design. You cannot constrain the passband ripple in all bands simultaneously.
- **F** — Frequency vector. Frequency values in specified in **F** indicate locations where you provide specific filter response amplitudes. When you provide **F**, you must also provide **A**.
- **N** — Filter order for FIR filters and the numerator and denominator orders for IIR filters.
- **Nb** — Numerator order for IIR filters
- **Na** — Denominator order for IIR filter designs
- **R** — Ripple

By default, this method assumes that all frequency specifications are supplied in normalized frequency.

### Specifying Frequency and Amplitude Vectors

**F** and **A** are the input arguments you use to define the filter response desired. Each frequency value you specify in **F** must have a corresponding response value in **A**. The following table shows how **F** and **A** are related.

Define the frequency vector **F** as [0 0.25 0.3 0.4 0.5 0.6 0.7 0.75 1.0]

Define the response vector **A** as [1 1 0 0 0 0 1 1]

These specifications connect **F** and **A** as shown here:

<b>F (Normalized Frequency)</b>	<b>A (Response Desired at F)</b>
0	1
0.25	1
0.3	0
0.4	0

<b>F (Normalized Frequency)</b>	<b>A (Response Desired at F)</b>
0.5	0
0.6	0
0.7	0
0.75	1
1.0	1

Different specifications can have different design methods available. Use `designmethods` to get a list of design methods available for a given specification string and filter specification object.

Use `designopts` to get a list of design options available for a filter specification object and a given design method. Enter `help(D,METHOD)` to get detailed help on the available design options for a given design method.

`D = fdesign.arbmag(SPEC,specvalue1,specvalue2,...)` initializes the specifications with `specvalue1`, `specvalue2`. Use `get(D,'Description')` for descriptions of the various specifications `specvalue1`, `specvalue2`, ... `specvalueN`.

`D = fdesign.arbmag(specvalue1,specvalue2,specvalue3)` uses the default specification string 'N,F,A', setting the filter order, filter frequency vector, and the amplitude vector to the values `specvalue1`, `specvalue2`, and `specvalue3`.

`D = fdesign.arbmag(...,Fs)` specifies the sampling frequency in Hz. All other frequency specifications are also assumed to be in Hz when you specify `Fs`.

## Examples


### Design of a multiband arbitrary-magnitude filter

Use `fdesign.arbmag` to design a 3-band filter.

Use the given frequency and amplitude vectors in “Specifying Frequency and Amplitude Vectors” on page 7-499.

```
N = 150;
B = 3;
F = [0 .25 .3 .4 .5 .6 .7 .75 1];
A = [1 1 0 0 0 0 0 1 1];
A1 = A(1:2);
A2 = A(3:7);
A3 = A(8:end);
F1 = F(1:2);
F2 = F(3:7);
F3 = F(8:end);
d = fdesign.arbmag('N,B,F,A',N,B,F1,A1,F2,A2,F3,A3);
Hd = design(d);
fvtool(Hd)
```

A response with two passbands — one roughly between 0 and 0.25 and the second between 0.75 and 1 — results from the mapping between F and A.



## Design of a single band arbitrary-magnitude filter

Use `fdesign.arbmag` to design a single band equiripple filter.

```
n = 120;  
f = linspace(0,1,100); % 100 frequency points.  
as = ones(1,100)-f*0.2;  
absorb = [ones(1,30), (1-0.6*bohmanwin(10))', ...  
ones(1,5), (1-0.5*bohmanwin(8))', ones(1,47)];  
a = as.*absorb;  
d = fdesign.arbmag('N,F,A',n,f,a);  
hd1 = design(d,'equiripple');
```

If you have the DSP System Toolbox, you can design a minimum-phase equiripple filter.

```
hd2 = design(d,'equiripple','MinPhase',true);  
hfvt = fvtool([hd1 hd2],'analysis','polezero');  
legend(hfvt,'Equiripple Filter','Minimum-phase Equiripple Filter');
```


## Design of a multiband minimum order arbitrary-magnitude filter

Use `fdesign.arbmag` to design a multiband minimum order filter.

This example requires the DSP System Toolbox.

Place the notches at  $0.25\pi$  and  $0.55\pi$  radians/sample

```
d = fdesign.arbmag('B,F,A,R');  
d.NBands = 5;  
d.B1Frequencies = [0 0.2];  
d.B1Amplitudes = [1 1];  
d.B1Ripple = 0.25;  
d.B2Frequencies = 0.25;  
d.B2Amplitudes = 0;  
d.B3Frequencies = [0.3 0.5];  
d.B3Amplitudes = [1 1];  
d.B3Ripple = 0.25;  
d.B4Frequencies = 0.55;  
d.B4Amplitudes = 0;  
d.B5Frequencies = [0.6 1];  
d.B5Amplitudes = [1 1];  
d.B5Ripple = 0.25;  
Hd = design(d,'equiripple');  
fvtool(Hd)
```



## Design of a multiband constrained arbitrary-magnitude filter


Use `fdesign.arbmag` to design a multiband constrained FIR filter.

This example requires the DSP System Toolbox.

Force the frequency response at  $0.15\pi$  radians/sample to 0 dB.

```
d = fdesign.arbmag('N,B,F,A,C',82,2);  
d.B1Frequencies = [0 0.06 .1];  
d.B1Amplitudes = [0 0 0];  
d.B2Frequencies = [.15 1];  
d.B2Amplitudes = [1 1];
```

```
% Design a filter with no constraints
Hd1 = design(d,'equiripple','B2ForcedFrequencyPoints',0.15);
% Add a constraint to the first band to increase attenuation
d.B1Constrained = true;
d.B1Ripple = .001;
Hd2 = design(d,'equiripple','B2ForcedFrequencyPoints',0.15);
hfvtool(Hd1,Hd2);
legend(hfvtool,'Original Design','Design with Constrained Stopband Ripple');
```

**See Also**

[design](#) | [designmethods](#) | [fdesign](#)

# fdesign.arbmagnphase

---

**Purpose** Arbitrary response magnitude and phase filter specification object

**Syntax**

```
d = fdesign.arbmagnphase
d = fdesign.arbmagnphase(specification)
d = fdesign.arbmagnphase(specification,specvalue1,specvalue2,
    ...)
d = fdesign.arbmagnphase(specvalue1,specvalue2,specvalue3)
d = fdesign.arbmagnphase(...,fs)
```

**Description** `d = fdesign.arbmagnphase` constructs an arbitrary magnitude filter specification object `d`.

`d = fdesign.arbmagnphase(specification)` initializes the `Specification` property for specifications object `d` to the string in `specification`. The input argument `specification` must be one of the strings shown in the following table. Specification strings are not case sensitive.

Specification String	Description of Resulting Filter
<code>n, f, h</code>	Single band design (default). FIR and IIR ( <code>n</code> is the order for both numerator and denominator).
<code>n, b, f, h</code>	FIR multiband design where <code>b</code> defines the number of bands.
<code>nb, na, f, h</code>	IIR single band design.

The following table describes the arguments in the strings.

Argument	Description
<code>b</code>	Number of bands in the multiband filter.
<code>f</code>	Frequency vector. Frequency values specified in <code>f</code> indicate locations where you provide specific filter response amplitudes. When you provide <code>f</code> you must also provide <code>h</code> which contains the response values.

Argument	Description
h	Complex frequency response values.
n	Filter order for FIR filters and the numerator and denominator orders for IIR filters (when not specified by nb and na).
nb	Numerator order for IIR filters.
na	Denominator order for IIR filter designs.

By default, this method assumes that all frequency specifications are supplied in normalized frequency.

## Specifying f and h

f and h are the input arguments you use to define the filter response desired. Each frequency value you specify in f must have a corresponding response value in h. This example creates a filter with two passbands (b = 4) and shows how f and h are related. This example is for illustration only. It is not an actual filter.

Define the frequency vector f as [0 0.1 0.2 0.4 0.5 0.6 0.9 1.0]

Define the response vector h as [0 0.5 0.5 0.1 0.1 0.8 0.8 0]


These specifications connect f and h as shown in the following table.

f (Normalized Frequency)	h (Response Desired at f)
0	0
0.1	0.5
0.2	0.5
0.4	0.1
0.5	0.1
0.6	0.8

# fdesign.arbmagnphase

<b>f (Normalized Frequency)</b>	<b>h (Response Desired at f)</b>
0.9	0.8
1.0	0.0

A response with two passbands—one roughly between 0.1 and 0.2 and the second between 0.6 and 0.9—results from the mapping between  $f$  and  $h$ . Plotting  $f$  and  $h$  yields the following figure that resembles a filter with two passbands.



The second example in Examples shows this plot in more detail with a complex filter response for  $h$ . In the example,  $h$  uses complex values for the response.

Different specification types often have different design methods available. Use `designmethods(d)` to get a list of design methods available for a given specification string and specifications object.

```
d =  
fdesign.arbmagnphase(specification,specvalue1,specvalue2,...)  
initializes the filter specification object with specvalue1, specvalue2,  
and so on. Use get(d, 'description') for descriptions of the various  
specifications specvalue1, specvalue2, ...specn.
```

```
d = fdesign.arbmagnphase(specvalue1,specvalue2,specvalue3)  
uses the default specification string n,f,h, setting the filter order, filter  
frequency vector, and the complex frequency response vector to the  
values specvalue1, specvalue2, and specvalue3.
```

```
d = fdesign.arbmagnphase(...,fs) specifies the sampling frequency  
in Hz. All other frequency specifications are also assumed to be in Hz  
when you specify fs.
```

## Examples


Use `fdesign.arbmagnphase` to model a complex analog filter:

```
d=fdesign.arbmagnphase('n,f,h',100); % N=100, f and h set to defaults.  
design(d,'freqsamp');
```

For a more complex example, design a bandpass filter with low group delay by specifying the desired delay and using `f` and `h` to define the filter bands.

```
n = 50;      % Group delay of a linear phase filter would be 25.  
gd = 12;    % Set the desired group delay for the filter.  
f1=linspace(0,.25,30); % Define the first stopband frequencies.  
f2=linspace(.3,.56,40);% Define the passband frequencies.  
f3=linspace(.62,1,30); % Define the second stopband frequencies.  
h1 = zeros(size(f1)); % Specify the filter response at the freqs in f1.  
h2 = exp(-1j*pi*gd*f2); % Specify the filter response at the freqs in f2.  
h3 = zeros(size(f3)); % Specify the response at the freqs in f3.  
d=fdesign.arbmagnphase('n,b,f,h',50,3,f1,h1,f2,h2,f3,h3);  
D = design(d,'equiripple');  
fvtool(D,'Analysis','freq');
```

# fdesign.arbmagnphase



## See Also

`fdesign` | `design` | `designmethods` | `setspecs`

## Purpose

Audio weighting filter specification object

## Syntax

```
HAWf = fdesign.audioweighting  
HAWf = fdesign.audioweighting(spec)  
HAWf = fdesign.audioweighting(spec,specvalue1,specvalue2)  
HAWf = fdesign.audioweighting(specvalue1,specvalue2)  
HAWf = fdesign.audioweighting(...,Fs)
```

## Description

Supported audio weighting filter types are: A weighting, C weighting, C-message, ITU-T 0.41, and ITU-R 468–4 weighting.

*HAWf* = fdesign.audioweighting constructs an audio weighting filter specification object *HAWf* with a weighting type of A and a filter class of 1. Use the `design` method to instantiate a `dfilt` object based on the specifications in *HAWf*. Use `designmethods` to find valid filter design methods. Because the standards for audio weighting filters are in Hz, normalized frequency specifications are not supported for `fdesign.audioweighting` objects. The default sampling frequency for A weighting, C weighting, C-message, and ITU-T 0.41 filters is 48 kHz. The default sampling frequency for the ITU-R 468–4 filter is 80 kHz. If you invoke the `normalizefreq` method, a warning is issued when you instantiate the `dfilt` object and the default sampling frequencies in Hz are used.

*HAWf* = fdesign.audioweighting(*spec*) returns an audio weighting filter specification object using default values for the specification string in *spec*. The following are valid entries for *spec*. The entries are not case sensitive.

- 'WT,Class' (default *spec*)

The 'WT,Class' specification is valid for A weighting and C weighting filters of class 1 or 2.

The weighting type is specified by the string: 'A' or 'C'. The class is the scalar 1 or 2.

The default values for 'WT,Class' are 'A',1.

- 'WT'

The 'WT' specification is valid for C-message (default), ITU-T 0.41, and ITU-R 468–4 weighting filters.

The weighting type is specified by the string: 'Cmessage', 'ITUT041', or 'ITUR4684'.

*HAwf* = fdesign.audioweighting(*spec*,*specvalue1*,*specvalue2*) constructs an audio weighting filter specification object *HAwf* and sets its specifications at construction time.

*HAwf* = fdesign.audioweighting(*specvalue1*,*specvalue2*) constructs an audio weighting filter specification object *HAwf* with the specification 'WT,Class' using the values you provide. The valid weighting types are 'A' or 'C'.

*HAwf* = fdesign.audioweighting(...,*Fs*) specifies the sampling frequency in Hz. The sampling frequency is a scalar trailing all other input arguments.

## Input Arguments

### Parameter Name/Value Pairs

#### WT

Weighting type

The weighting type defines the frequency response of the filter. The valid weighting types are: A weighting, C weighting, C-message, ITU-T 0.41, and ITU-R 468–4 weighting. The weighting types are described in “Definitions” on page 7-513.

#### Class

Filter Class

Filter class is only applicable for A weighting and C weighting filters. The filter class describes the frequency-dependent tolerances specified in the relevant standards [1], [2]. There are two possible class values: 1 and 2. Class 1 weighting filters have stricter tolerances than class 2 filters. The filter class value does not affect the design. The class value is only used to provide a specification mask in *fvtool* for the analysis of the filter design.

Default: 1

## Definitions

### A weighting

The specifications for the A weighting filter are found in ANSI standard S1.42-2001. The A weighting filter is based on the 40-phon Fletcher-Munson equal loudness contour [3]. One phon is equal to one dB sound pressure level (SPL) at one kHz. The Fletcher-Munson equal loudness contours are designed to account for frequency and level dependent differences in the perceived loudness of tonal stimuli. The 40-phon contour reflects the fact that the human auditory system is more sensitive to frequencies around 1–2 kHz than lower and higher frequencies. The filter roll off is more pronounced at lower frequencies and more modest at higher frequencies. While A weighting is based on the equal loudness contour for low-level (40-phon) tonal stimuli, it is commonly used in the United States for assessing potential health risks associated with noise exposure to narrowband and broadband stimuli at high levels.

### C weighting

The specifications for the C weighting filter are found in ANSI standard S1.42-2001. The C weighting filter approximates the 100-phon Fletcher-Munson equal loudness contour for tonal stimuli. The C weighting magnitude response is essentially flat with 3-dB frequencies at 31.5 Hz and 8000 Hz. While C weighting is not as common as A weighting, sound level meters frequently have a C weighting filter option.

### C-message

The specifications for the C-message weighting filter are found in Bell System Technical Reference, PUB 41009. C-message weighting filters are designed for measuring the impact of noise on telecommunications circuits used in speech transmission [6]. C-message weighting filters are commonly used in North America, while the ITU-T 0.41 filter is more commonly used outside of North America.

## ITU-R 468-4

The specifications for the ITU-R 468-4 weighting filter are found in the International Telecommunication Union Recommendation ITU-R BS.468-4. ITU-R 468-4 is an equal loudness contour weighting filter. Unlike the A weighting filter, the ITU-R 468-4 filter describes subjective loudness judgements for broadband stimuli [4]. A common criticism of the A weighting filter is that it underestimates the loudness judgement of real-world stimuli particularly in the frequency band from about 1–9 kHz. A comparison of A weighting and ITU-R 468-4 weighting curves shows that the ITU-R 468-4 curve applies more gain between 1 and 10 kHz with a peak difference of approximately 12 dB around 6–7 kHz.


## ITU-T 0.41

The specifications for the ITU-T 0.41 filter are found in the ITU-T Recommendation 0.41. ITU-T 0.41 weighting filters are designed for measuring the impact of noise on telecommunications circuits used in speech transmission [5]. ITU-T 0.41 weighting filters are commonly used outside of North America, while the C-message weighting filter is more common in North America.

## Examples

Compare class 1 A weighting and ITU-R 468-4 filters between 0.1 and 12 kHz:


```
HawfA = fdesign.audioweighting('WT,Class','A',1,44.1e3);  
% Sampling frequency is 44.1 kHz  
HawfITUR = fdesign.audioweighting('WT','ITUR4684',44.1e3);  
Afilter = design(HawfA);  
ITURfilter = design(HawfITUR);  
hfvT = fvtool([Afilter ITURfilter]);  
axis([0.1 12 -80 20]);  
legend(hfvT,'A-weighting','ITU-R 468-4');
```



Compare C-message and ITU-T 0.41 filters:


```
hCmessage = fdesign.audioweighting('WT','Cmessage',24e3);
hITUT = fdesign.audioweighting('WT','ITUT041',24e3);
dCmessage = design(hCmessage);
dITUT = design(hITUT);
hfvt = fvtool([dCmessage dITUT]);
legend(hfvt,'C-Message Weighting','ITU-T 0.41 Weighting');
axis([0.1 10 -50 5]);
```

# fdesign.audioweighting



Construct an ITU-R 468–4 filter using all available design methods:

```
HAwf = fdesign.audioweighting('WT','ITUR4684');  
ValidDesigns = designmethods(HAwf);  
% returns iirlpnorm,equiripple,freqsamp in cell array  
D = design(HAwf,'all'); % returns all designs  
hfvf = fvtool(D);  
legend(hfvf,'Least P-norm IIR','FIR Equiripple',...  
'FIR Frequency Sampling')
```



## References

- [1] *American National Standard Design Response of Weighting Networks for Acoustical Measurements*, ANSI S1.42-2001, Acoustical Society of America, New York, NY, 2001.
- [2] *Electroacoustics Sound Level Meters Part 1: Specifications*, IEC 61672-1, First Edition 2002-05.
- [3] Fletcher, H. and W.A. Munson. "Loudness, its definition, measurement and calculation." *Journal of the Acoustical Society of America*, Vol. 5, 1933, pp. 82–108.
- [4] *Measurement of Audio-Frequency Noise Voltage Level in Sound Broadcasting*, International Telecommunication Union Recommendation ITU-R BS.468-4, 1986.
- [5] *Psophometer for Use on Telephone-Type Circuits*, ITU-T Recommendation 0.41.

# fdesign.audioweighting

---

[6] *Transmission Parameters Affecting Voiceband Data*  
*Transmission-Measuring Techniques*, Bell System Technical Reference,  
PUB 41009, 1972.

## See Also

`design` | `designmethods` | `fdesign` | `fvtool`

## How To

- Audio Weighting Filters Example
- “Design a Filter in Fdesign — Process Overview”

## Purpose

Bandpass filter specification object

## Syntax

```
D = fdesign.bandpass
D = fdesign.bandpass(SPEC)
D = fdesign.bandpass(spec,specvalue1,specvalue2,...)
D = fdesign.bandpass(specvalue1,specvalue2,specvalue3,
specvalue4,...specvalue4,specvalue5,specvalue6)
D = fdesign.bandpass(...,Fs)
D = fdesign.bandpass(...,MAGUNITS)
```

## Description

`D = fdesign.bandpass` constructs a bandpass filter specification object `D`, applying default values for the properties `Fstop1`, `Fpass1`, `Fpass2`, `Fstop2`, `Astop1`, `Apass`, and `Astop2` — one possible set of values you use to specify a bandpass filter.

`D = fdesign.bandpass(SPEC)` constructs object `D` and sets its `Specification` property to `SPEC`. Entries in the `SPEC` string represent various filter response features, such as the filter order, that govern the filter design. Valid entries for `SPEC` are shown below and used to define the bandpass filter. The strings are not case sensitive.

---

**Note** Specifications strings marked with an asterisk require the DSP System Toolbox software.

---

- 'Fst1,Fp1,Fp2,Fst2,Ast1,Ap,Ast2' (default spec)
- 'N,F3dB1,F3dB2'
- "N,F3dB1,F3dB2,Ap" \*
- 'N,F3dB1,F3dB2,Ast' \*
- 'N,F3dB1,F3dB2,Ast1,Ap,Ast2' \*
- 'N,F3dB1,F3dB2,BWp' \*
- 'N,F3dB1,F3dB2,BWst' \*
- 'N,Fc1,Fc2'

- 'N,Fc1,Fc2,Ast1,Ap,Ast2'
- 'N,Fp1,Fp2,Ap'
- 'N,Fp1,Fp2,Ast1,Ap,Ast2'
- 'N,Fst1,Fp1,Fp2,Fst2'
- 'N,Fst1,Fp1,Fp2,Fst2,C' \*
- 'N,Fst1,Fp1,Fp2,Fst2,Ap' \*
- 'N,Fst1,Fst2,Ast'
- 'Nb,Na,Fst1,Fp1,Fp2,Fst2' \*

The string entries are defined as follows:

- **Ap** — amount of ripple allowed in the pass band. Also called **Apass**.
- **Ast1** — attenuation in the first stop band in decibels (the default units). Also called **Astop1**.
- **Ast2** — attenuation in the second stop band in decibels (the default units). Also called **Astop2**.
- **BWp** — bandwidth of the filter passband. Specified in normalized frequency units.
- **BWst** — bandwidth of the filter stopband. Specified in normalized frequency units.
- **C** — Constrained band flag. This enables you to specify passband ripple or stopband attenuation for fixed-order designs in one or two of the three bands.


In the specification string 'N,Fst1,Fp1,Fp2,Fst2,C', you cannot specify constraints in both stopbands and the passband simultaneously. You can specify constraints in any one or two bands.

- **F3dB1** — cutoff frequency for the point 3 dB point below the passband value for the first cutoff. Specified in normalized frequency units. (IIR filters)

- **F3dB2** — cutoff frequency for the point 3 dB point below the passband value for the second cutoff. Specified in normalized frequency units. (IIR filters)
- **Fc1** — cutoff frequency for the point 6 dB point below the passband value for the first cutoff. Specified in normalized frequency units. (FIR filters)
- **Fc2** — cutoff frequency for the point 6 dB point below the passband value for the second cutoff. Specified in normalized frequency units. (FIR filters)
- **Fp1** — frequency at the edge of the start of the pass band. Specified in normalized frequency units. Also called **Fpass1**.
- **Fp2** — frequency at the edge of the end of the pass band. Specified in normalized frequency units. Also called **Fpass2**.
- **Fst1** — frequency at the edge of the start of the first stop band. Specified in normalized frequency units. Also called **Fstop1**.
- **Fst2** — frequency at the edge of the start of the second stop band. Specified in normalized frequency units. Also called **Fstop2**.
- **N** — filter order for FIR filters. Or both the numerator and denominator orders for IIR filters when **na** and **nb** are not provided.
- **Na** — denominator order for IIR filters
- **Nb** — numerator order for IIR filters

Graphically, the filter specifications look similar to those shown in the following figure.

# fdesign.bandpass



Regions between specification values like  $F_{st1}$  and  $F_{p1}$  are transition regions where the filter response is not explicitly defined.

The filter design methods that apply to a bandpass filter specification object change depending on the Specification string. Use `designmethods` to determine which design methods apply to an object and the Specification property value.

Use `designopts` to determine the design options for a given design method. Enter `help(D,METHOD)` at the MATLAB command line to obtain detailed help on the design options for a given design method, METHOD.

`D = fdesign.bandpass(spec,specvalue1,specvalue2,...)`  
constructs an object D and sets its specifications at construction time.

`D = fdesign.bandpass(specvalue1,specvalue2,specvalue3,specvalue4,...specvalue4,specvalue5,specvalue6)`  
constructs D with the default Specification property string, using the values you provide as input arguments for `specvalue1,specvalue2,specvalue3,specvalue4,specvalue4,specvalue5,specvalue6` and `specvalue7`.

`D = fdesign.bandpass(...,Fs)` adds the argument `Fs`, specified in Hz to define the sampling frequency to use. In this case, all frequencies in the specifications are in Hz as well.

`D = fdesign.bandpass(...,MAGUNITS)` specifies the units for any magnitude specification you provide in the input arguments. `MAGUNITS` can be one of

- 'linear' — specify the magnitude in linear units
- 'dB' — specify the magnitude in dB (decibels)
- 'squared' — specify the magnitude in power units

When you omit the `MAGUNITS` argument, `fdesign` assumes that all magnitudes are in decibels. Note that `fdesign` stores all magnitude specifications in decibels (converting to decibels when necessary) regardless of how you specify the magnitudes.

## Examples

Filter a discrete-time signal with a bandpass filter. The signal is a sum of three discrete-time sinusoids,  $\pi/8$ ,  $\pi/2$ , and  $3\pi/4$  radians/sample.

```
n = 0:159;  
x = cos(pi/8*n)+cos(pi/2*n)+sin(3*pi/4*n);
```

Design an FIR equiripple bandpass filter to remove the lowest and highest discrete-time sinusoids.

```
d = fdesign.bandpass('Fst1,Fp1,Fp2,Fst2,Ast1,Ap,Ast2',1/4,3/8,5/8,6/8,  
Hd = design(d,'equiripple');
```

Apply the filter to the discrete-time signal.

```
y = filter(Hd,x);  
freq = 0:(2*pi)/length(x):pi;  
xdft = fft(x);  
ydft = fft(y);  
plot(freq,abs(xdft(1:length(x)/2+1)));  
hold on;  
plot(freq,abs(ydft(1:length(x)/2+1)),'r','linewidth',2);  
legend('Original Signal','Bandpass Signal');
```

## fdesign.bandpass

---

Design an IIR Butterworth filter of order 10 with 3-dB frequencies of 1 and 1.2 kHz. The sampling frequency is 10 kHz

```
d = fdesign.bandpass('N,F3dB1,F3dB2',10,1e3,1.2e3,1e4);  
Hd = design(d,'butter');  
fvtool(Hd)
```

---

This example requires the DSP System Toolbox software.

Design a constrained-band FIR equiripple filter of order 100 with a passband of [1, 1.4] kHz. Both stopband attenuation values are constrained to 60 dB. The sampling frequency is 10 kHz.

```
d = fdesign.bandpass('N,Fst1,Fp1,Fp2,Fst2,C',100,800,1e3,1.4e3,1.6e3,1e4);  
d.Stopband1Constrained = true; d.Astop1 = 60;  
d.Stopband2Constrained = true; d.Astop2 = 60;  
Hd = design(d,'equiripple');  
fvtool(Hd);  
measure(Hd)
```

The passband ripple is slightly over 2 dB. Because the design constrains both stopbands, you cannot constrain the passband ripple.

### See Also

fdesign, fdesign.bandstop, fdesign.highpass, fdesign.lowpass

## Purpose

Bandstop filter specification object

## Syntax

```
D = fdesign.bandstop
D = fdesign.bandstop(SPEC)
D = fdesign.bandstop(SPEC,specvalue1,specvalue2,...)
D = fdesign.bandstop(specvalue1,specvalue2,specvalue3,specvalue4,...
specvalue5,specvalue6,specvalue7)
D = fdesign.bandstop(...,Fs)
D = fdesign.bandstop(...,MAGUNITS)
```

## Description

D = fdesign.bandstop constructs a bandstop filter specification object D, applying default values for the properties Fpass1, Fstop1, Fstop2, Fpass2, Apass1, Astop1 and Apass2.

D = fdesign.bandstop(SPEC) constructs object D and sets the Specification property to SPEC. Entries in the SPEC string represent various filter response features, such as the filter order, that govern the filter design. Valid entries for SPEC are shown below. The strings are not case sensitive.

---

**Note** Specifications strings marked with an asterisk require the DSP System Toolbox software.

---

- 'Fp1,Fst1,Fst2,Fp2,Ap1,Ast,Ap2' (default spec)
- 'N,F3dB1,F3dB2'
- 'N,F3dB1,F3dB2,Ap' \*
- 'N,F3dB1,F3dB2,Ap,Ast' \*
- 'N,F3dB1,F3dB2,Ast' \*
- 'N,F3dB1,F3dB2,BWp' \*
- 'N,F3dB1,F3dB2,BWst' \*
- 'N,Fc1,Fc2'

- 'N,Fc1,Fc2,Ap1,Ast,Ap2'
- 'N,Fp1,Fp2,Ap'
- 'N,Fp1,Fp2,Ap,Ast'
- 'N,Fp1,Fst1,Fst2,Fp2'
- 'N,Fp1,Fst1,Fst2,Fp2,C' \*
- 'N,Fp1,Fst1,Fst2,Fp2,Ap' \*
- 'N,Fst1,Fst2,Ast'
- 'Nb,Na,Fp1,Fst1,Fst2,Fp2' \*


The string entries are defined as follows:

- **Ap** — amount of ripple allowed in the passband in decibels (the default units). Also called **Apass**.
- **Ap1** — amount of ripple allowed in the pass band in decibels (the default units). Also called **Apass1**.
- **Ap2** — amount of ripple allowed in the pass band in decibels (the default units). Also called **Apass2**.
- **Ast** — attenuation in the first stopband in decibels (the default units). Also called **Astop1**.
- **BWp** — bandwidth of the filter passband. Specified in normalized frequency units.
- **BWst** — bandwidth of the filter stopband. Specified in normalized frequency units.
- **C** — Constrained band flag. This enables you to specify passband ripple or stopband attenuation for fixed-order designs in one or two of the three bands.

In the specification string 'N,Fp1,Fst1,Fst2,Fp2,C', you cannot specify constraints simultaneously in both passbands and the stopband. You can specify constraints in any one or two bands.

- $F_{3dB1}$  — cutoff frequency for the point 3 dB point below the passband value for the first cutoff.
- $F_{3dB2}$  — cutoff frequency for the point 3 dB point below the passband value for the second cutoff.
- $F_{c1}$  — cutoff frequency for the point 6 dB point below the passband value for the first cutoff. (FIR filters)
- $F_{c2}$  — cutoff frequency for the point 6 dB point below the passband value for the second cutoff. (FIR filters)
- $F_{p1}$  — frequency at the start of the pass band. Also called  $F_{pass1}$ .
- $F_{p2}$  — frequency at the end of the pass band. Also called  $F_{pass2}$ .
- $F_{st1}$  — frequency at the end of the first stop band. Also called  $F_{stop1}$ .
- $F_{st2}$  — frequency at the start of the second stop band. Also called  $F_{stop2}$ .
- $N$  — filter order.
- $N_a$  — denominator order for IIR filters.
- $N_b$  — numerator order for IIR filters.

Graphically, the filter specifications look similar to those shown in the following figure.



Regions between specification values like `Fp1` and `Fst1` are transition regions where the filter response is not explicitly defined.

The filter design methods that apply to a bandstop filter specification object change depending on the `Specification` string. Use `designmethods` to determine which design methods apply to an object and the `Specification` property value.

Use `designopts` to determine the design options for a given design method. Enter `help(D,METHOD)` at the MATLAB command line to obtain detailed help on the design options for a given design method, `METHOD`.

`D = fdesign.bandstop(SPEC,specvalue1,specvalue2,...)`  
constructs an object `D` and sets its specifications at construction time.

`D = fdesign.bandstop(specvalue1,specvalue2,specvalue3,specvalue4,...,specvalue5,specvalue6,specvalue7)` constructs an object `D` with the default `Specification` property string, using the values you provide in `specvalue1`, `specvalue2`, `specvalue3`, `specvalue4`, `specvalue5`, `specvalue6` and `specvalue7`.

`D = fdesign.bandstop(...,Fs)` adds the argument `Fs`, specified in Hz to define the sampling frequency. If you specify the sampling frequency as a trailing scalar, all frequencies in the specifications are in Hz as well.

`D = fdesign.bandstop(...,MAGUNITS)` specifies the units for any magnitude specification you provide in the input arguments. `MAGUNITS` can be one of

- 'linear' — specify the magnitude in linear units
- 'dB' — specify the magnitude in dB (decibels)
- 'squared' — specify the magnitude in power units

When you omit the `MAGUNITS` argument, `fdesign` assumes that all magnitudes are in decibels. Note that `fdesign` stores all magnitude specifications in decibels (converting to decibels when necessary) regardless of how you specify the magnitudes.

## Examples

Construct a bandstop filter to reject the discrete frequency band between  $3\pi/8$  and  $5\pi/8$  radians/sample. Apply the filter to a discrete-time signal consisting of the superposition of three discrete-time sinusoids.

Design an FIR equiripple filter and view the magnitude response.

```
d = fdesign.bandstop('Fp1,Fst1,Fst2,Fp2,Ap1,Ast,Ap2',2/8,3/8,5/8,6/8,1,1,1);
Hd = design(d,'equiripple');
fvtool(Hd)
```

Construct the discrete-time signal to filter.

```
n = 0:99;
x = cos(pi/5*n)+sin(pi/2*n)+cos(4*pi/5*n);
y = filter(Hd,x);
xdft = fft(x);
ydft = fft(y);
freq = 0:(2*pi)/length(x):pi;
plot(freq,abs(xdft(1:length(x)/2+1)));
hold on;
plot(freq,abs(ydft(1:length(y)/2+1)),'r','linewidth',2);
xlabel('Radians/Sample'); ylabel('Magnitude');
legend('Original Signal','Bandstop Signal');
```

---

Create a Butterworth bandstop filter for data sampled at 10 kHz. The stopband is [1,1.5] kHz. The order of the filter is 20.

```
d = fdesign.bandstop('N,F3dB1,F3dB2',20,1e3,1.5e3,1e4);
Hd = design(d,'butter');
fvtool(Hd);
```

Zoom in on the magnitude response plot to verify that the 3-dB down points are located at 1 and 1.5 kHz.

---

The following example requires the DSP System Toolbox license.

## fdesign.bandstop

---

Design a constrained-band FIR equiripple filter of order 100 for data sampled at 10 kHz. You can specify constraints on at most two of the three bands: two passbands and one stopband. In this example, you choose to constrain the passband ripple to be 0.5 dB in each passband. Design the filter, visualize the magnitude response and measure the filter's design.

```
d = fdesign.bandstop('N,Fp1,Fst1,Fst2,Fp2,C',100,800,1e3,1.5e3,1.7e3,1e4)
d.Passband1Constrained = true; d.Apass1 = 0.5;
d.Passband2Constrained = true; d.Apass2 = 0.5;
Hd = design(d,'equiripple');
fvtool(Hd);
measure(Hd)
```

With this order filter and passband ripple constraints, you achieve approximately 50 dB of stopband attenuation.

### See Also

fdesign, fdesign.bandpass, fdesign.highpass, fdesign.lowpass

**Purpose**

CIC compensator filter specification object

**Syntax**

```
d= fdesign.ciccomp
d= fdesign.ciccomp(d,nsections,rcic)
d= fdesign.ciccomp(...,spec)
h = fdesign.ciccomp(...,spec,specvalue1,specvalue2,...)
```

**Description**

`d= fdesign.ciccomp` constructs a CIC compensator specifications object `d`, applying default values for the properties `Fpass`, `Fstop`, `Apass`, and `Astop`. In this syntax, the filter has two sections and the differential delay is 1.

Using `fdesign.ciccomp` with a design method creates a `dfilt` object, a single-rate discrete-time filter.

`d= fdesign.ciccomp(d,nsections,rcic)` constructs a CIC compensator specifications object with the filter differential delay set to `d`, the number of sections in the filter set to `nsections`, and the CIC rate change factor set to `rcic`. The default values of these parameters are: the differential delay equal to 1, the number of sections equal to 2, and the CIC rate change factor equal to 1.

If the CIC rate change factor is equal to 1, the filter passband response is an inverse sinc that is an approximation to the true inverse passband response of the CIC filter.

If you specify a CIC rate change factor not equal to 1, the filter passband response is an inverse Dirichlet sinc that matches exactly the true inverse passband response of the CIC filter.

`d= fdesign.ciccomp(...,spec)` constructs a CIC Compensator specifications object and sets its `Specification` property to `spec`. Entries in the `spec` string represent various filter response features, such as the filter order, that govern the filter design. Valid entries for `spec` are shown in the list below. The strings are not case sensitive.


- 'fp,fst,ap,ast' (default spec)
- 'n,fc,ap,ast'
- 'n,fp,ap,ast'

- 'n,fp,fst'
- 'n,fst,ap,ast'

The string entries are defined as follows:

- ap — amount of ripple allowed in the pass band in decibels (the default units). Also called  $A_{pass}$ .
- ast — attenuation in the stop band in decibels (the default units). Also called  $A_{stop}$ .
- fc — cutoff frequency for the point 6 dB point below the passband value. Specified in normalized frequency units.
- fp — frequency at the end of the pass band. Specified in normalized frequency units. Also called  $F_{pass}$ .
- fst — frequency at the start of the stop band. Specified in normalized frequency units. Also called  $F_{stop}$ .
- n — filter order.

In graphic form, the filter specifications look like this:



Regions between specification values like  $f_p$  and  $f_{st}$  are transition regions where the filter response is not explicitly defined.

The filter design methods that apply to a CIC compensator specifications object change depending on the Specification string.

Use `designmethods` to determine which design method applies to an object and its specification string.

```
h = fdesign.ciccomp(...,spec,specvalue1,specvalue2,...)
```


constructs an object and sets the specifications in the order they are specified in the `spec` input when you construct the object.

## Designing CIC Compensators

Typically, when they develop filters, designers want flat passbands and transition regions that are as narrow as possible. CIC filters present a  $(\sin x/x)$  profile in the passband and relatively wide transitions.

To compensate for this fall off in the passband, and to try to reduce the width of the transition region, you can use a CIC compensator filter that demonstrates an  $(x/\sin x)$  profile in the passband. `fdesign.ciccomp` is specifically tailored to designing CIC compensators.

Here is a plot of a CIC filter and a compensator for that filter. The example that produces these filters follows the plot.



Given a CIC filter, how do you design a compensator for that filter? CIC compensators share three defining properties with the CIC filter — differential delay,  $d$ ; number of sections,  $\text{numberofsections}$ ; and the usable passband frequency,  $F_{\text{pass}}$ .

By taking the number of sections, passband, and differential delay from your CIC filter and using them in the definition of the CIC compensator, the resulting compensator filter effectively corrects for the passband droop of the CIC filter, and narrows the transition region.

As a demonstration of this concept, this example creates a CIC decimator and its compensator.

```
fs = 96e3; % Input sampling frequency.
fpass = 4e3; % Frequency band of interest.
m = 6; % Decimation factor.
hcic = design(fdesign.decimator(m,'cic',1,fpass,60,fs));
```


```
hd = cascade(dfilt.scalar(1/gain(hcic)),hcic);
hd(2) = design(fdesign.ciccomp(hcic.differentialdelay, ...
    hcic.numberofsections,fpass,4.5e3,.1,60,fs/m));
fvtool(hd(1),hd(2),...
cascade(hd(1),hd(2)), 'Fs', [96e3 96e3/m 96e3])
```

You see the results in the preceding plot.

## Examples

Designed to compensate for the rolloff inherent in CIC filters, CIC compensators can improve the performance of your CIC design. This example designs a compensator *d* with five sections and a differential delay equal to one. The plot displayed after the code shows the increasing gain in the passband that is characteristic of CIC compensators, to overcome the droop in the CIC filter passband. Ideally, cascading the CIC compensator with the CIC filter results in a lowpass filter with flat passband response and narrow transition region.

```
h = fdesign.ciccomp;
set(h, 'NumberOfSections', 5, 'DifferentialDelay', 1);
hd = equiripple(h);
fvtool(hd);
```



This compensator would work for a decimator or interpolator that had differential delay of 1 and 5 sections.

**See Also**

`fdesign.decimator` | `fdesign.interpolator`

**Purpose** IIR comb filter specification object

**Syntax**

```
d=fdesign.comb
d=fdesign.comb(combtype)
d=fdesign(combtype,specstring)
d=fdesign(combtype,specstring,specvalue1,specvalue2,...)
d=fdesign.comb(...,Fs)
```

**Description** `fdesign.comb` specifies a peaking or notching comb filter. Comb filters amplify or attenuate a set of harmonically related frequencies.

`d=fdesign.comb` creates a notching comb filter specification object and applies default values for the filter order ( $N=10$ ) and quality factor ( $Q=16$ ).

`d=fdesign.comb(combtype)` creates a comb filter specification object of the specified type and applies default values for the filter order and quality factor. The valid entries for `combtype` are shown in the following table. The entries are not case-sensitive.

Argument	Description
notch	creates a comb filter that attenuates a set of harmonically related frequencies.
peak	creates a comb filter that amplifies a set of harmonically related frequencies.

`d=fdesign(combtype,specstring)` creates a comb filter specification object of type `combtype` and sets its `Specification` property to `specstring` with default values. The entries in `specstring` determine the number of peaks or notches in the comb filter as well as their bandwidth and slope. Valid entries for `specstring` are shown below. The entries are not case-sensitive.

- 'N,Q' (default)
- 'N,BW'

- 'L,BW,GWB,Nsh'

The following table describes the arguments in *specstring*.

Argument	Description
BW	Bandwidth of the notch or peak. By default the bandwidth is calculated at the point $-3$ dB down from the center frequency of the peak or notch. For example, setting $BW=0.01$ specifies that the $-3$ dB point will be $\pm 0.005$ (in normalized frequency) from the center of the notch or peak.
GWB	Gain at which the bandwidth is measured. This allows the user to specify the bandwidth of the notch or peak at a gain different from the $-3$ dB default.
L	Upsampling factor for a shelving filter of order $Nsh$ . $L$ determines the number of peaks or notches, which are equally spaced over the normalized frequency interval $[-1,1]$ .
N	Filter order. Specifies a filter with $N+1$ numerator and denominator coefficients. The filter will have $N$ peaks or notches equally spaced over the interval $[-1,1]$ .

Argument	Description
Nsh	Shelving filter order. Nsh represents a positive integer that determines the sharpness of the peaks or notches. The greater the value of the shelving filter order, the steeper the slope of the peak or notch. This results in a filter of order $L \cdot Nsh$ .
Q	Peak or notch quality factor. Q represents the ratio of the lowest center frequency peak or notch (not including DC) to the bandwidth calculated at the $-3$ dB point.

`d=fdesign(combtype,specstring,specvalue1,specvalue2,...)` creates an IIR comb filter specification object of type `combtype` and sets its `Specification` property to the values in `specvalue1,specvalue2,...`

`d=fdesign.comb(...,Fs)` creates an IIR comb filter specification object using the sampling frequency, `Fs`, of the signal to be filtered. The function assumes that `Fs` is in Hertz and must be specified as a scalar trailing all other provided values.


## Examples

These examples demonstrate how to create IIR comb filter specification objects. First, create a default specification object.

```
d=fdesign.comb;
```


In the next example, create a notching filter of order 8 with a bandwidth of 0.02 (normalized frequency) referenced to the  $-3$  dB point.

```
d = fdesign.comb('notch','N,BW',8,0.02);
Hd = design(d);
fvtool(Hd)
```




Next, create a peaking comb filter with 5 peaks and a quality factor of 25.

```
d = fdesign.comb('peak','N,Q',5,25);  
Hd = design(d);  
fvtool(Hd)
```



In the next example, create a notching filter to remove interference at 60 Hz and its harmonics. The following code creates a filter with 10 notches and a notch bandwidth of 5 Hz referenced to the -4dB level. The filter has a shelving filter order of 4 and a sampling frequency of 600 Hz. Because the notches are equidistantly spaced in the interval [-300, 300] Hz, they occur at multiples of 60 Hz.

```
d = fdesign.comb('notch','L,BW,GBW,Nsh',10,5,-4,4,600);
Hd=design(d);
fvtool(Hd)
```



## Purpose

Decimator filter specification object

## Syntax

```
D = fdesign.decimator(M)
D = fdesign.decimator(M,RESPONSE)
D = fdesign.decimator(M,PULSESHAPINGRESPONSE,SPS)
D = fdesign.decimator(M,CICRESPONSE,D)
D = fdesign.decimator(M,RESPONSE,SPEC)
D = fdesign.decimator(...,SPEC,specvalue1,specvalue2,...)
D = fdesign.decimator(...,Fs)
D = fdesign.decimator(...,MAGUNITS)
```

## Description

`D = fdesign.decimator(M)` constructs a decimator filter specification object `D` with the `DecimationFactor` property equal to the positive integer `M` and the `Response` property set to `'Nyquist'`. The default values for the transition width and stopband attenuation in the Nyquist design are  $0.1\pi$  radians/sample and 80 dB. If `M` is unspecified, `M` defaults to 2.

`D = fdesign.decimator(M,RESPONSE)` constructs a decimator specification object with the decimation factor `M` and the `'Response'` property.

`D = fdesign.decimator(M,PULSESHAPINGRESPONSE,SPS)` constructs a pulse-shaping decimator specification object with the decimation factor `M` and `'Response'` property equal to one of the supported pulse-shaping filters: `'Gaussian'`, `'Raised Cosine'`, or `'Square Root Raised Cosine'`. `SPS` is the samples per symbol. The samples per symbol, `SPS`, must precede any specification string.

`D = fdesign.decimator(M,CICRESPONSE,D)` constructs a CIC or CIC compensator decimator specification object with the decimation factor, `M`, `'Response'` property equal to `'CIC'` or `'CICCOMP'`, and `D` equal to the differential delay. The differential delay, `D`, must precede any specification string.

Because you are designing multirate filters, the specification strings available are not the same as the specifications for designing single-rate filters. The decimation factor `M` is not included in the specification strings. Different filter responses support different specifications. The

# fdesign.decimator

following table lists the supported response types and specification strings. The strings are not case sensitive.

Design String	Valid Specification Strings
'Arbitrary Magnitude'	See <code>fdesign.arbmag</code> for a description of the specification string entries. <ul style="list-style-type: none"> <li>• 'N,F,A' (default string)</li> <li>• 'N,B,F,A'</li> </ul>
'Arbitrary Magnitude and Phase'	See <code>fdesign.arbmagnphase</code> for a description of the specification string entries. <ul style="list-style-type: none"> <li>• 'N,F,H' (default string)</li> <li>• 'N,B,F,H'</li> </ul>
'Bandpass'	See <code>fdesign.bandpass</code> for a description of the specification string entries. <ul style="list-style-type: none"> <li>• 'Fst1,Fp1,Fp2,Fst2,Ast1,Ap,Ast2' (default string)</li> <li>• 'N,Fc1,Fc2'</li> <li>• 'N,Fst1,Fp1,Fp2,Fst2'</li> </ul>
'Bandstop'	See <code>fdesign.bandstop</code> for a description of the specification string entries.
'CIC'	'Fp,Ast' — Only valid specification. Fp is the passband frequency and Ast is the stopband attenuation in decibels.  To specify a CIC decimator, include the differential delay after 'CIC' and before the filter specification string: 'Fp,Ast'. For example: d = <code>fdesign.decimator(2,'cic',4,'Fp,Ast',0.4,40);</code>

Design String	Valid Specification Strings
'CIC Compensator'	<p>See <code>fdesign.ciccomp</code> for a description of the specification string entries.</p> <ul style="list-style-type: none"> <li>'Fp,Fst,Ap,Ast' (default string)</li> <li>'N,Fc,Ap,Ast'</li> <li>'N,Fp,Ap,Ast'</li> <li>'N,Fp,Fst'</li> <li>'N,Fst,Ap,Ast'</li> </ul> <p>To specify a CIC compensator decimator, include the differential delay after 'CICCOMP' and before the filter specification string.. For example:  <code>d = fdesign.decimator(2,'ciccomp',4);</code></p>
'Differentiator'	'N' — filter order
'Gaussian'	<p>'Nsym,BT' — Nsym is the filter order in symbols and BT is the bandwidth-symbol time product.</p> <p>The specification string must be preceded by an integer-valued <code>SamplesPerSymbol</code>.</p>
'Halfband'	<p>See <code>fdesign.halfband</code> for a description of the specification string entries.</p> <ul style="list-style-type: none"> <li>'TW,Ast' (default string)</li> <li>'N,TW'</li> <li>'N'</li> <li>'N,Ast'</li> </ul> <p>If you use the quasi-linear IIR design method, <code>iirlinphase</code>, with a halfband specification, the interpolation factor must be 2.</p>

<b>Design String</b>	<b>Valid Specification Strings</b>
'Highpass'	<p>See <code>fdesign.highpass</code> for a description of the specification string entries.</p> <ul style="list-style-type: none"><li>• 'Fst,Fp,Ast,Ap' (default string)</li><li>• 'N,F3db'</li><li>• 'N,Fc'</li><li>• 'N,Fc,Ast,Ap'</li><li>• 'N,Fp,Ast,Ap'</li><li>• 'N,Fst,Ast,Ap'</li><li>• 'N,Fst,Fp'</li><li>• 'N,Fst,Ast,Ap'</li><li>• 'N,Fst,Fp,Ast'</li></ul>
'Hilbert'	<p>See <code>fdesign.hilbert</code> for a description of the specification string entries.</p> <ul style="list-style-type: none"><li>• 'N,TW' (default string)</li><li>• 'TW,Ap'</li></ul>
'Inverse-sinc Lowpass'	<p>See <code>fdesign.isinclp</code> for a description of the specification string entries.</p> <ul style="list-style-type: none"><li>• 'Fp,Fst,Ap,Ast' (default string))</li><li>• 'N,Fc,Ap,Ast'</li><li>• 'N,Fp,Fst'</li><li>• 'N,Fst,Ap,Ast'</li></ul>

Design String	Valid Specification Strings
'Inverse-sinc Highpass'	<p>See <code>fdesign.isinchnp</code> for a description of the specification string entries.</p> <ul style="list-style-type: none"> <li>• 'Fst,Fp,Ast,Ap' (default string)</li> <li>• 'N,Fc,Ast,Ap'</li> <li>• 'N,Fst,Fp'</li> <li>• 'N,Fst,Ast,Ap'</li> </ul>
'Lowpass'	<p>See <code>fdesign.lowpass</code> for a description of the specification string entries.</p> <ul style="list-style-type: none"> <li>• 'Fp,Fst,Ap,Ast' (default string)</li> <li>• 'N,F3dB'</li> <li>• 'N,Fc'</li> <li>• 'N,Fc,Ap,Ast'</li> <li>• 'N,Fp,Ap,Ast'</li> <li>• 'N,Fp,Fst'</li> <li>• 'N,Fp,Fst,Ap'</li> <li>• 'N,Fp,Fst,Ast'</li> <li>• 'N,Fst,Ap,Ast'</li> </ul>

# fdesign.decimator

Design String	Valid Specification Strings
'Nyquist'	<p>See <code>fdesign.nyquist</code> for a description of the specification string entries. For all Nyquist specifications, you must specify the <i>L</i>th band. This typically corresponds to the <code>DecimationFactor</code>.</p> <ul style="list-style-type: none"><li>• 'TW,Ast' (default string)</li><li>• 'N'</li><li>• 'N,Ast'</li><li>• 'N,Ast'</li></ul>
'Raised Cosine'	<p>See <code>fdesign.pulseshaping</code> for a description of the specification string entries.</p> <ul style="list-style-type: none"><li>• 'Ast,Beta' (default string)</li><li>• 'Nsym,Beta'</li><li>• 'N,Beta'</li></ul> <p>The specification string must be preceded by an integer-valued <code>SamplesPerSymbol</code>.</p>
'Square Root Raised Cosine'	<p>See <code>fdesign.pulseshaping</code> for a description of the specification string entries.</p> <ul style="list-style-type: none"><li>• 'Ast,Beta' (default string)</li><li>• 'Nsym,Beta'</li><li>• 'N,Beta'</li></ul> <p>The specification string must be preceded by an integer-valued <code>SamplesPerSymbol</code>.</p>

`D = fdesign.decimator(M,RESPONSE,SPEC)` constructs object `D` and sets the `Specification` property to `SPEC` for the response type, `RESPONSE`. Entries in the `SPEC` string represent various filter response features,

such as the filter order, that govern the filter design. Valid entries for SPEC depend on the RESPONSE type.

Because you are designing multirate filters, the specification strings available are not the same as the specifications for designing single-rate filters with such response types as `fdesign.lowpass`. The strings are not case sensitive.

The decimation factor *M* is not in the specification strings.

`D = fdesign.decimator(...,SPEC,specvalue1,specvalue2,...)` constructs an object *D* and sets its specifications at construction time.

`D = fdesign.decimator(...,Fs)` provides the sampling frequency of the signal to be filtered. *F<sub>s</sub>* must be specified as a scalar trailing the other numerical values provided. *F<sub>s</sub>* is assumed to be in Hz as are all other frequency values provided.

`D = fdesign.decimator(...,MAGUNITS)` specifies the units for any magnitude specification you provide in the input arguments. *MAGUNITS* can be one of

- 'linear' — specify the magnitude in linear units.
- 'dB' — specify the magnitude in dB (decibels).
- 'squared' — specify the magnitude in power units.

When you omit the *MAGUNITS* argument, `fdesign` assumes that all magnitudes are in decibels. Note that `fdesign` stores all magnitude specifications in decibels (converting to decibels when necessary) regardless of how you specify the magnitudes.

## Examples

These examples show how to construct decimating filter specification objects. First, create a default specifications object without using input arguments except for the decimation factor *m*.

```
d = fdesign.decimator(2,'Nyquist',2,0.1,80) % Set tw=0.1, and ast=80.
```

Now create an object by passing a specification type string 'fst1,fp1,fp2,fst2,ast1,ap,ast2' and a design — the resulting object uses default values for the filter specifications. You must provide

# fdesign.decimator

---

the design input argument, `bandpass` in this example, when you include a specification.

```
d=fdesign.decimator(8,'bandpass',...  
'fst1,fp1,fp2,fst2,ast1,ap,ast2');
```

Create another decimating filter specification object, passing the specification values to the object rather than accepting the default values for `fp`, `fst`, `ap`, `ast`.

```
d=fdesign.decimator(3,'lowpass',.45,0.55,.1,60);
```

Now pass the filter specifications that correspond to the specifications — `n`, `fc`, `ap`, `ast`.

```
d=fdesign.decimator(3,'ciccomp',1,2,'n,fc,ap,ast',...  
20,0.45,.05,50);
```

Now design a decimator using the `equiripple` design method.


```
hm = equiripple(d);
```

Pass a new specification type for the filter, specifying the filter order. Note that the inputs must include the differential delay `dd` with the CIC input argument to design a CIC specification object.

```
m = 5;  
dd = 2;  
d = fdesign.decimator(m,'cic',dd,'fp,ast',0.55,55);
```

In this example, you specify a sampling frequency as the last input argument. Here is it 1000 Hz. Design an `equiripple` filter and plot the magnitude response:

```
d=fdesign.decimator(8,'bandpass','fst1,fp1,fp2,fst2,ast1,ap,ast2',...  
100,150,250,300,50,.05,50,1000);  
fvtool(design(d,'equiripple'))
```



## See Also

[fdesign](#) | [fdesign.arbmag](#) | [fdesign.arbmagnphase](#) | [fdesign.interpolator](#) | [fdesign.rsrc](#)

# fdesign.differentiator

---

**Purpose** Differentiator filter specification object

**Syntax**

```
D = fdesign.differentiator
D = fdesign.differentiator(SPEC)
D = fdesign.differentiator(SPEC,specvalue1,specvalue2, ...)
D = fdesign.differentiator(specvalue1)
D = fdesign.differentiator(...,Fs)
D = fdesign.differentiator(...,MAGUNITS)
```

**Description** `D = fdesign.differentiator` constructs a default differentiator filter designer `D` with the filter order set to 31.

`D = fdesign.differentiator(SPEC)` initializes the filter designer `Specification` property to `SPEC`. You provide one of the following strings as input to replace `SPEC`. The string you provide is not case sensitive.

---

**Note** Specifications strings marked with an asterisk require the DSP System Toolbox software.

---

- 'N' — Full band differentiator (default)
- 'N,Fp,Fst' — Partial band differentiator
- 'N,Fp,Fst,Ap' — Partial band differentiator \*
- 'N,Fp,Fst,Ast' — Partial band differentiator \*
- 'Ap' — Minimum order full band differentiator \*
- 'Fp,Fst,Ap,Ast' — Minimum order partial band differentiator \*

The string entries are defined as follows:

- `Ap` — amount of ripple allowed in the pass band in decibels (the default units). Also called `Apass`.
- `Ast` — attenuation in the stop band in decibels (the default units). Also called `Astop`.

- `Fp` — frequency at the start of the pass band. Specified in normalized frequency units. Also called `Fpass`.
- `Fst` — frequency at the end of the stop band. Specified in normalized frequency units. Also called `Fstop`.
- `N` — filter order.

By default, `fdesign.differentiator` assumes that all frequency specifications are provided in normalized frequency units. Also, decibels is the default for all magnitude specifications.

Use `designopts` to determine the design options for a given design method. Enter `help(D,METHOD)` at the MATLAB command line to obtain detailed help on the design options for a given design method, `METHOD`.

`D = fdesign.differentiator(SPEC,specvalue1,specvalue2, ...)` initializes the filter designer specifications in `SPEC` with `specvalue1`, `specvalue2`, and so on. To get a description of the specifications `specvalue1`, `specvalue2`, and more, enter

```
get(d,'description')
```

at the Command prompt.

`D = fdesign.differentiator(specvalue1)` assumes the default specification string `N`, setting the filter order to the value you provide.

`D = fdesign.differentiator(...,Fs)` adds the argument `Fs`, specified in Hz to define the sampling frequency to use. In this case, all frequencies in the specifications are in Hz as well.

`D = fdesign.differentiator(...,MAGUNITS)` specifies the units for any magnitude specification you provide in the input arguments. `MAGUNITS` can be one of

- `'linear'` — specify the magnitude in linear units
- `'dB'` — specify the magnitude in dB (decibels)
- `'squared'` — specify the magnitude in power units

# fdesign.differentiator

---

When you omit the `MAGUNITS` argument, `fdesign` assumes that all magnitudes are in decibels. Note that `fdesign` stores all magnitude specifications in decibels (converting to decibels when necessary) regardless of how you specify the magnitudes.

## Examples

Use an FIR equiripple differentiator to transform frequency modulation into amplitude modulation, which can be detected using an envelope detector.

Modulate a message signal consisting of a 20-Hz sine wave with a 1 kHz carrier frequency. The sampling frequency is 10 kHz .


```
t = linspace(0,1,1e4);
x = cos(2*pi*20*t);
Fc = 1e3;
Fs = 1e4;
y = modulate(x,Fc,Fs,'fm');
```

Design the equiripple FIR differentiator of order 31.

```
d = fdesign.differentiator(31,1e4);
Hd = design(d,'equiripple');
```

Filter the modulated signal and take the Hilbert transform to obtain the envelope.

```
y1 = filter(Hd,y);
y1 = hilbert(y1);
% Plot the envelope
plot(t.*1000,abs(y1));
xlabel('Milliseconds'); ylabel('Magnitude');
grid on;
title('Envelope of the Demodulated Signal');
```




From the preceding figure, you see that the envelope completes two cycles every 100 milliseconds. The envelope is oscillating at 20 Hz, which corresponds to the frequency of the message signal.

Design an FIR differentiator using least squares and plot the zero phase response.


```
d = fdesign.differentiator(33); % Filter order is 33.
hd = design(d,'firls');
fvtool(hd,'magnitudedisplay','zero-phase',...
'frequencyrange','[-pi, pi]')
```

# fdesign.differentiator



Design a narrow band differentiator. Differentiate the first 25 percent of the frequencies in the Nyquist range and filter the higher frequencies.

```
Fs=20000; %sampling frequency
d = fdesign.differentiator('N,Fp,Fst',54,2500,3000,Fs);
Hd= design(d,'equiripple');
% Weight the stopband to increase attenuation
Hd1 = design(d,'equiripple','Wstop',4);
hfvt = fvtool(Hd,Hd1,'magnitudedisplay','zero-phase',...
'frequencyrange',[0, Fs/2]);
legend(hfvt,'Without stopband weighting',...
'With stopband weighting');
```



**See Also** [design](#) | [fdesign](#)

# fdesign.fracdelay

---

**Purpose** Fractional delay filter specification object

**Syntax**

```
d = fdesign.fracdelay(delta)
d = fdesign.fracdelay(delta, 'N')
d = fdesign.fracdelay(delta, 'N', n)
d = fdesign.fracdelay(delta, n)
d = fdesign.fracdelay(..., fs)
```

**Description**

`d = fdesign.fracdelay(delta)` constructs a default fractional delay filter designer `d` with the filter order set to 3 and the delay value set to `delta`. The fractional delay `delta` must be between 0 and 1 samples.

`d = fdesign.fracdelay(delta, 'N')` initializes the filter designer specification string to `N`, where `N` specifies the fractional delay filter order and defaults to filter order of 3.

Use `designmethods(d)` to get a list of the design methods available for a specification string.

`d = fdesign.fracdelay(delta, 'N', n)` initializes the filter designer to specification string `N` and sets the filter order to `n`.

`d = fdesign.fracdelay(delta, n)` assumes the default specification `N`, filter order, and sets the filter order to the value you provide in input `n`.

`d = fdesign.fracdelay(..., fs)` adds the argument `fs`, specified in units of Hertz (Hz) to define the sampling frequency. In this case, specify the fractional delay `delta` to be between 0 and  $1/fs$ .

**Examples**

Design a second-order fractional delay filter of 0.2 samples using the Lagrange method. Implement the filter using a Farrow fractional delay (`fd`) structure.

```
d = fdesign.fracdelay(0.2, 'N', 2);
hd = design(d, 'lagrange', 'filterstructure', 'farrowfd');
fvtool(hd, 'analysis', 'grpdelay')
```

Design a cubic fractional delay filter with a sampling frequency of 8 kHz and fractional delay of 50 microseconds using the Lagrange method.

```
d = fdesign.fracdelay(50e-6,'N',3,8000);  
Hd = design(d, 'lagrange', 'FilterStructure', 'farrowfd');
```

### See Also

[design](#) | [designopts](#) | [fdesign](#) | [setspecs](#)

# fdesign.halfband

---

**Purpose** Halfband filter specification object

**Syntax**

```
d = fdesign.halfband
d = fdesign.halfband('type',type)
d = fdesign.halfband(spec)
d = fdesign.halfband(spec,specvalue1,specvalue2,...)
d = fdesign.halfband(specvalue1,specvalue2)
d = fdesign.halfband(...,fs)
d = fdesign.halfband(...,magunits)
```

**Description** `d = fdesign.halfband` constructs a halfband filter specification object `d`, applying default values for the properties `tw` and `ast`.

Using `fdesign.halfband` with a design method generates a `dfilt` object.

`d = fdesign.halfband('type',type)` initializes the filter designer 'Type' property with `type`. "type" must be either `lowpass` or `highpass` and is not case sensitive.

`d = fdesign.halfband(spec)` constructs object `d` and sets its 'Specification' to `spec`. Entries in the `spec` string represent various filter response features, such as the filter order, that govern the filter design. Valid entries for `spec` are shown below. The strings are not case sensitive.

- `tw,ast` (default `spec`)
- `n,tw`
- `n`
- `n,ast`

The string entries are defined as follows:

- `ast` — attenuation in the stop band in decibels (the default units).
- `n` — filter order.
- `tw` — width of the transition region between the pass and stop bands. Specified in normalized frequency units.

By default, all frequency specifications are assumed to be in normalized frequency units. Moreover, all magnitude specifications are assumed to be in dB. Different specification types may have different design methods available.

The filter design methods that apply to a halfband filter specification object change depending on the `Specification` string. Use `designmethods` to determine which design method applies to an object and its specification string. Different filter design methods also have options that you can specify. Use `designopts` with the design method string to see the available options. For example:

```
f=fdesign.halfband('N,TW');  
designmethods(f)
```

```
d = fdesign.halfband(spec,specvalue1,specvalue2,...)  
constructs an object d and sets its specifications at construction time.
```

```
d = fdesign.halfband(specvalue1,specvalue2) constructs an  
object d assuming the default Specification property string tw,ast,  
using the values you provide for the input arguments specvalue1 and  
specvalue2 for tw and ast.
```

```
d = fdesign.halfband(...,fs) adds the argument fs, specified in Hz  
to define the sampling frequency to use. In this case, all frequencies in  
the specifications are in Hz as well.
```

```
d = fdesign.halfband(...,magunits) specifies the units for any  
magnitude specification you provide in the input arguments. magunits  
can be one of
```

- `linear` — specify the magnitude in linear units
- `dB` — specify the magnitude in dB (decibels)
- `squared` — specify the magnitude in power units

When you omit the `magunits` argument, `fdesign` assumes that all magnitudes are in decibels. Note that `fdesign` stores all magnitude specifications in decibels (converting to decibels when necessary) regardless of how you specify the magnitudes.

## Examples

Create a default halfband filter specifications object:

```
d=fdesign.halfband;
```

Create another halfband filter object, passing the specification values to the object rather than accepting the default values for `n` and `ast`.

```
d = fdesign.halfband('n,ast', 42, 80);
```

For another example, pass the filter values that correspond to the default Specification — `n,ast`.

```
d = fdesign.halfband(.01, 80);
```

This example designs an equiripple FIR filter, starting by passing a new specification type and specification values to `fdesign.halfband`.

```
hs = fdesign.halfband('n,ast',80,70);  
hd =design(hs,'equiripple'); % Opens FVTool automatically.
```

In this example, pass the specifications for the filter, and then design a least-squares FIR filter from the object, using `firls` as the design method.


```
hs = fdesign.halfband('n,tw', 42, .04);  
% designmethods(hs)  
hd=design(hs,'firls');
```

Create two equiripple halfband filters with and without a nonnegative zero phase response:

```
f=fdesign.halfband('N,TW',12,0.2);  
% Equiripple halfband filter with nonnegative zero phase response  
Hd1=design(f,'equiripple','ZeroPhase',true);  
% Equiripple halfband filter with zero phase false  
% 'zerophase',false is the default  
Hd2=design(f,'equiripple','ZeroPhase',false);  
%Obtain real-valued amplitudes (not magnitudes)  
[Hr_zerophase,W]=zerophase(Hd1);
```

```
[Hr,W]=zerophase(Hd2);
% Plot and compare response
plot(W,Hr_zerophase,'k','linewidth',2);
xlabel('Radians/sample'); ylabel('Amplitude');
hold on;
plot(W,Hr,'r');
axis tight; grid on;
legend('with ''ZeroPhase'', true','with ''ZeroPhase'' false');
```

Note that the amplitude of the zero phase response (black line) is nonnegative for all frequencies.



The 'ZeroPhase' option is valid only for equiripple halfband designs with the 'N,TW' specification. You cannot specify 'MinPhase' and 'ZeroPhase' to be simultaneously 'true'.

## See Also

fdesign | fdesign.decimator | design | fdesign.interpolator | fdesign.nyquist | setspecs | zerophase

# fdesign.highpass

---

**Purpose** Highpass filter specification object

**Syntax**

```
D = fdesign.highpass
D = fdesign.highpass(SPEC)
D = fdesign.highpass(SPEC,specvalue1,specvalue2,...)
D = fdesign.highpass(specvalue1,specvalue2,specvalue3,
specvalue4)
D = fdesign.highpass(...,Fs)
D = fdesign.highpass(...,MAGUNITS)
```

**Description** D = fdesign.highpass constructs a highpass filter specification object D, applying default values for the specification string, 'Fst,Fp,Ast,Ap'.  
D = fdesign.highpass(SPEC) constructs object D and sets the Specification property to SPEC. Entries in the SPEC string represent various filter response features, such as the filter order, that govern the filter design. Valid entries for SPEC are shown below. The strings are not case sensitive.

---

**Note** Specifications strings marked with an asterisk require the DSP System Toolbox software.

---

- 'Fst,Fp,Ast,Ap' (default spec)
- 'N,F3db'
- 'N,F3db,Ap' \*
- 'N,F3db,Ast' \*
- 'N,F3db,Ast,Ap' \*
- 'N,F3db,Fp' \*
- 'N,Fc'
- 'N,Fc,Ast,Ap'
- 'N,Fp,Ap'


- 'N,Fp,Ast,Ap'
- 'N,Fst,Ast'
- 'N,Fst,Ast,Ap'
- 'N,Fst,F3db' \*
- 'N,Fst,Fp'
- 'N,Fst,Fp,Ap' \*
- 'N,Fst,Fp,Ast' \*
- 'Nb,Na,Fst,Fp' \*

The string entries are defined as follows:

- Ap — amount of ripple allowed in the pass band in decibels (the default units). Also called Apass.
- Ast — attenuation in the stop band in decibels (the default units). Also called Astop.
- F3db — cutoff frequency for the point 3 dB point below the passband value. Specified in normalized frequency units.
- Fc — cutoff frequency for the point 6 dB point below the passband value. Specified in normalized frequency units.
- Fp — frequency at the start of the pass band. Specified in normalized frequency units. Also called Fpass.
- Fst — frequency at the end of the stop band. Specified in normalized frequency units. Also called Fstop.
- N — filter order.
- Na and Nb are the order of the denominator and numerator.

Graphically, the filter specifications look similar to those shown in the following figure.

# fdesign.highpass



Regions between specification values like  $F_{st}$  and  $F_p$  are transition regions where the filter response is not explicitly defined.

The filter design methods that apply to a highpass filter specification object change depending on the `Specification` string. Use `designmethods` to determine which design method applies to an object and its specification string.

Use `designopts` to determine which design options are valid for a given design method. For detailed information on design options for a given design method, `METHOD`, enter `help(D,METHOD)` at the MATLAB command line.

`D = fdesign.highpass(SPEC,specvalue1,specvalue2,...)` constructs an object `d` and sets its specification values at construction time.

`D = fdesign.highpass(specvalue1,specvalue2,specvalue3,specvalue4)` constructs an object `D` with the default `Specification` property and the values you enter for `specvalue1,specvalue2,...`

`D = fdesign.highpass(...,Fs)` provides the sampling frequency for the filter specification object. `Fs` is in Hz and must be specified as a scalar trailing the other numerical values provided. If you specify a sampling frequency, all other frequency specifications are in Hz.

`D = fdesign.highpass(...,MAGUNITS)` specifies the units for any magnitude specification you provide in the input arguments. `MAGUNITS` can be one of

- 'linear' — specify the magnitude in linear units
- 'dB' — specify the magnitude in dB (decibels)
- 'squared' — specify the magnitude in power units

When you omit the MAGUNITS argument, `fdesign` assumes that all magnitudes are in decibels. Note that `fdesign` stores all magnitude specifications in decibels (converting to decibels when necessary) regardless of how you specify the magnitudes.

## Examples

Highpass filter a discrete-time signal consisting of two sine waves.

Create a highpass filter specification object. Specify the passband frequency to be  $0.25\pi$  radians/sample and the stopband frequency to be  $0.15\pi$  radians/sample. Specify 1 dB of allowable passband ripple and a stopband attenuation of 60 dB.

```
d = fdesign.highpass('Fst,Fp,Ast,Ap',0.15,0.25,60,1);
```

Query the valid design methods for your filter specification object, `d`.

```
designmethods(d)
```

Create an FIR equiripple filter and view the filter magnitude response with `fvtool`.

```
Hd = design(d,'equiripple');  
fvtool(Hd);
```

Create a signal consisting of the sum of two discrete-time sinusoids with frequencies of  $\pi/8$  and  $\pi/4$  radians/sample and amplitudes of 1 and 0.25 respectively. Filter the discrete-time signal with the FIR equiripple filter object, `Hd`

```
n = 0:159;  
x = cos((pi/8)*n)+0.25*sin((pi/4)*n);  
y = filter(Hd,x);  
Omega = (2*pi)/160;  
freq = 0:(2*pi)/160:pi;
```

## fdesign.highpass

---

```
xdft = fft(x);
ydft = fft(y);
plot(freq,abs(xdft(1:length(x)/2+1)));
hold on;
plot(freq,abs(ydft(1:length(y)/2+1)),'r','linewidth',2);
legend('Original Signal','Lowpass Signal', ...
'Location','NorthEast');
ylabel('Magnitude'); xlabel('Radians/Sample');
```

---

Create a filter of order 10 with a 6-dB frequency of 9.6 kHz and a sampling frequency of 48 kHz.

```
d=fdesign.highpass('N,Fc',10,9600,48000);
designmethods(d)
% only valid design method is FIR window method
Hd = design(d);
% Display filter magnitude response
fvtool(Hd);
```

---

If you have the DSP System Toolbox software, you can specify the shape of the stopband and the rate at which the stopband decays.

Create two FIR equiripple filters with different linear stopband slopes. Specify the passband frequency to be  $0.3\pi$  radians/sample and the stopband frequency to be  $0.35\pi$  radians/sample. Specify 1 dB of allowable passband ripple and a stopband attenuation of 60 dB. Design one filter with a 20 dB/rad/sample stopband slope and another filter with 40 dB/rad/sample.

```
D = fdesign.highpass('Fst,Fp,Ast,Ap',0.3,0.35,60,1);
Hd1 = design(D,'equiripple','StopBandShape','linear','StopBandDecay',20);
Hd2 = design(D,'equiripple','StopBandShape','linear','StopBandDecay',40);
hfvtool([Hd1 Hd2]);
legend(hfvtool,'20 dB/rad/sample','40 dB/rad/sample');
```

## See Also

[design](#) | [designmethods](#) | [fdesign](#)

# fdesign.hilbert

---

**Purpose** Hilbert filter specification object

**Syntax**

```
d = fdesign.hilbert
d = fdesign.hilbert(specvalue1,specvalue2)
d = fdesign.hilbert(spec)
d = fdesign.hilbert(spec,specvalue1,specvalue2)
d = fdesign.hilbert(...,Fs)
d = fdesign.hilbert(...,MAGUNITS)
```

**Description**

`d = fdesign.hilbert` constructs a default Hilbert filter designer `d` with `N`, the filter order, set to 30 and `TW`, the transition width set to  $0.1\pi$  radians/sample.

`d = fdesign.hilbert(specvalue1,specvalue2)` constructs a Hilbert filter designer `d` assuming the default specification string `'N, TW'`. You input `specvalue1` and `specvalue2` for `N` and `TW`.

`d = fdesign.hilbert(spec)` initializes the filter designer `Specification` property to `spec`. You provide one of the following strings as input to replace `spec`. The specification strings are not case sensitive.

---

**Note** Specifications strings marked with an asterisk require the DSP System Toolbox software.

---

- `'N, TW'` default spec string.
- `'TW, Ap' *`

The string entries are defined as follows:

- `Ap` — amount of ripple allowed in the pass band in decibels (the default units). Also called `Apass`.
- `N` — filter order.
- `TW` — width of the transition region between the pass and stop bands.

By default, `fdesign.hilbert` assumes that all frequency specifications are provided in normalized frequency units. Also, decibels is the default for all magnitude specifications.

Different specification strings may have different design methods available. Use `designmethods(d)` to get a list of the design methods available for a given specification string.

`d = fdesign.hilbert(spec,specvalue1,specvalue2)` initializes the filter designer specifications in `spec` with `specvalue1`, `specvalue2`, and so on. To get a description of the specifications `specvalue1` and `specvalue2`, enter

```
get(d, 'description')
```

at the Command prompt.

`d = fdesign.hilbert(...,Fs)` adds the argument `Fs`, specified in Hz to define the sampling frequency. In this case, all frequencies in the specifications are in Hz as well.

`d = fdesign.hilbert(...,MAGUNITS)` specifies the units for any magnitude specification you provide in the input arguments. `MAGUNITS` can be one of

- 'linear' — specify the magnitude in linear units
- 'dB' — specify the magnitude in dB (decibels)
- 'squared' — specify the magnitude in power units

When you omit the `MAGUNITS` argument, `fdesign` assumes that all magnitudes are in decibels. Note that `fdesign` stores all magnitude specifications in decibels (converting to decibels when necessary) regardless of how you specify the magnitudes.


## Examples

Design a Hilbert transformer of order 30 with a transition width of  $0.2\pi$  radians/sample. Plot the zero phase response from  $[-\pi,\pi]$  radians/sample and the impulse response.

```
d = fdesign.hilbert('N,TW',30,0.2);
```


# fdesign.hilbert

```
% Show available design methods
designmethods(d)
% Use least square minimization to obtain linear-phase FIR filter
Hd = design(d,'equiripple');
% Display zero phase response from [-pi,pi)
fvtool(Hd,'magnitudedisplay','zero-phase',...
'frequencyrange','[-pi, pi)')
```



The impulse response of this even order filter is antisymmetric (type III).

```
fvtool(Hd,'analysis','impulse')
```




Apply the filter to a discrete-time sinusoid with a frequency of  $\pi/2$  radians/sample.

```
n = 0:99;
x = cos(pi/2*n);
y = filter(Hd,x);
% Correct for the filter delay
Delay = floor(length(Hd.Numerator)/2);
y = y(Delay+1:end);
```

# fdesign.hilbert

Plot the filter input and output and validate the approximate  $\pi/2$  phase shift obtained with the Hilbert transformer.


```
stem(x(1:end-Delay), 'markerfacecolor', [0 0 1]);  
hold on;  
stem(y, 'Color', [1 0 0], 'markerfacecolor', [1 0 0]);  
axis([10 20 -1.5 1.5]); grid on;  
xlabel('Samples'); ylabel('Amplitude');  
legend('Input', 'Output', 'Location', 'NorthWest')
```



Because the frequency of the discrete-time sinusoid is  $\pi/2$  radians/sample, a one sample shift corresponds to a phase shift of  $\pi/2$ .


Form the analytic signal and demonstrate that the frequency content of the analytic signal is zero for negative frequencies and approximately twice the spectrum of the input for positive frequencies.

```
x1 = x(1:end-Delay);  
% Form the analytic signal  
xa = x1+1j*y;  
freq = -pi:(2*pi)/length(x1):pi-(2*pi)/length(x);  
plot(freq,abs(fftshift(fft(x1))));  
hold on;  
plot(freq,abs(fftshift(fft(xa))), 'r'); grid on;  
xlabel('Radians/Sample'); ylabel('Magnitude');  
legend('Input DFT', 'Analytic Signal DFT', 'Location', 'NorthWest');
```



Design a minimum-order Hilbert transformer that has a sampling frequency of 1 kHz. Specify the passband ripple to be 1 dB.

```
d = fdesign.hilbert('TW,Ap',1,0.1,1e3);  
hd = design(d,'equiripple');  
fvtool(hd,'magnitudedisplay','zero-phase', ...  
    'frequencyrange','[-Fs/2, Fs/2)');
```



**See Also**    design | fdesign | setspecs

# fdesign.interpolator

---

**Purpose** Interpolator filter specification

**Syntax**

```
D = fdesign.interpolator(L)
D = fdesign.interpolator(L,RESPONSE)
D = fdesign.interpolator(L,PULSESHPINGRESPONSE,SPS)
D = fdesign.interpolator(L,CICRESPONSE,D)
D = fdesign.interpolator(L,RESPONSE,spec)
D = fdesign.interpolator(...,spec,specvalue1,specvalue2,...)
D = fdesign.interpolator(...,Fs)
d = fdesign.interpolator(...,MAGUNITS)
```

**Description** `D = fdesign.interpolator(L)` constructs an interpolator filter specification object `D` with the `InterpolationFactor` property equal to the positive integer `L` and the `Response` property set to 'Nyquist'. The default values for the transition width and stopband attenuation in the Nyquist design are  $0.1\pi$  radians/sample and 80 dB. If `L` is unspecified, `L` defaults to 2.

`D = fdesign.interpolator(L,RESPONSE)` constructs a interpolator specification object with the interpolation factor `L` and the 'Response' property set to one of the supported types.

`D = fdesign.interpolator(L,PULSESHPINGRESPONSE,SPS)` constructs a pulse-shaping interpolator specification object with the interpolation factor `L` and 'Response' property equal to one of the supported pulse-shaping filters: 'Gaussian', 'Raised Cosine', or 'Square Root Raised Cosine'. `SPS` is the samples per symbol. The samples per symbol, `SPS`, must precede any specification string.

`D = fdesign.interpolator(L,CICRESPONSE,D)` constructs a CIC or CIC compensator interpolator specification object with the interpolation factor, `L`, and 'Response' property equal to 'CIC' or 'CICCOMP'. `D` is the differential delay. The differential delay, `D`, must precede any specification string.

`D = fdesign.interpolator(L,RESPONSE,spec)` constructs object `D` and sets its `Specification` property to `spec`. Entries in the `spec` string represent various filter response features, such as the filter order, that

govern the filter design. Valid entries for `spec` depend on the design type of the specifications object.

When you add the `spec` input argument, you must also add the `RESPONSE` input argument.

Because you are designing multirate filters, the specification strings available are not the same as the specifications for designing single-rate filters with design methods such as `fdesign.lowpass`. The strings are not case sensitive.

The interpolation factor `L` is not in the specification strings. The different filter responses support different specifications. The following table lists the supported response types and specification strings.

Design String	Valid Specification Strings
'Arbitrary Magnitude'	See <code>fdesign.arbmag</code> for a description of the specification string entries. <ul style="list-style-type: none"> <li>'N,F,A' (default string)</li> <li>'N,B,F,A'</li> </ul>
'Arbitrary Magnitude and Phase'	See <code>fdesign.arbmagnphase</code> for a description of the specification string entries. <ul style="list-style-type: none"> <li>'N,F,H' (default string)</li> <li>'N,B,F,H'</li> </ul>
'Bandpass'	See <code>fdesign.bandpass</code> for a description of the specification string entries. <ul style="list-style-type: none"> <li>'Fst1,Fp1,Fp2,Fst2,Ast1,Ap,Ast2' (default string)</li> <li>'N,Fc1,Fc2'</li> <li>'N,Fst1,Fp1,Fp2,Fst2'</li> </ul>
'Bandstop'	See <code>fdesign.bandstop</code> for a description of the specification string entries.

- 'N,Fc1,Fc2'
- 'N,Fp1,Fst1,Fst2,Fp2'
- 'Fp1,Fst1,Fst2,Fp2,Ap1,Ast,Ap2' (default string)

# fdesign.interpolator

Design String	Valid Specification Strings
'CIC'	<p>'Fp,Ast' — Only valid specification. Fp is the passband frequency and Ast is the stopband attenuation in decibels.</p> <p>To specify a CIC interpolator, include the differential delay after 'CIC' and before the filter specification string: 'Fp,Ast'. For example:</p> <pre>d = fdesign.interpolator(2,'cic',4,'Fp,Ast',0.4,40);</pre>
'CIC Compensator'	<p>See <code>fdesign.ciccomp</code> for a description of the specification string entries.</p> <ul style="list-style-type: none"> <li>• 'Fp,Fst,Ap,Ast' (default string)</li> <li>• 'N,Fc,Ap,Ast'</li> <li>• 'N,Fp,Ap,Ast'</li> <li>• 'N,Fp,Fst'</li> <li>• 'N,Fst,Ap,Ast'</li> </ul> <p>To specify a CIC compensator interpolator, include the differential delay after 'CICCOMP' and before the filter specification string.. For example:</p> <pre>d = fdesign.interpolator(2,'ciccomp',4);</pre>
'Differentiator'	'N' — filter order
'Gaussian'	<p>'Nsym,BT — Nsym is the filter order in symbols and BT is the bandwidth-symbol time product.</p> <p>The specification string must be preceded by an integer-valued <code>SamplesPerSymbol</code>.</p>

Design String	Valid Specification Strings
'Halfband'	<p>See <code>fdesign.halfband</code> for a description of the specification string entries.</p> <ul style="list-style-type: none"> <li>• 'TW,Ast' (default string)</li> <li>• 'N,TW'</li> <li>• `N'</li> <li>• 'N,Ast'</li> </ul> <p>If you use the quasi-linear IIR design method, <code>iirlinphase</code>, with a halfband specification, the interpolation factor must be 2.</p>
'Highpass'	<p>See <code>fdesign.highpass</code> for a description of the specification string entries.</p> <ul style="list-style-type: none"> <li>• 'Fst,Fp,Ast,Ap' (default string)</li> <li>• 'N,F3db'</li> <li>• 'N,Fc'</li> <li>• 'N,Fc,Ast,Ap'</li> <li>• 'N,Fp,Ast,Ap'</li> <li>• 'N,Fst,Ast,Ap'</li> <li>• 'N,Fst,Fp'</li> <li>• 'N,Fst,Ast,Ap'</li> <li>• 'N,Fst,Fp,Ast'</li> </ul>
'Hilbert'	<p>See <code>fdesign.hilbert</code> for a description of the specification string entries.</p> <ul style="list-style-type: none"> <li>• 'N,TW' (default string)</li> <li>• 'TW,Ap'</li> </ul>

# fdesign.interpolator

---

<b>Design String</b>	<b>Valid Specification Strings</b>
'Inverse-sinc Lowpass'	See <code>fdesign.isinc1p</code> for a description of the specification string entries. <ul style="list-style-type: none"><li>• 'Fp,Fst,Ap,Ast' (default string)</li><li>• 'N,Fc,Ap,Ast'</li><li>• 'N,Fp,Fst'</li><li>• 'N,Fst,Ap,Ast'</li></ul>
'Inverse-sinc Highpass'	See <code>fdesign.isinchp</code> for a description of the specification string entries. <ul style="list-style-type: none"><li>• 'Fst,Fp,Ast,Ap' (default string)</li><li>• 'N,Fc,Ast,Ap'</li><li>• 'N,Fst,Fp'</li><li>• 'N,Fst,Ast,Ap'</li></ul>
'Lowpass'	See <code>fdesign.lowpass</code> for a description of the specification string entries. <ul style="list-style-type: none"><li>• 'Fp,Fst,Ap,Ast' (default string)</li><li>• 'N,F3dB'</li><li>• 'N,Fc'</li><li>• 'N,Fc,Ap,Ast'</li><li>• 'N,Fp,Ap,Ast'</li><li>• 'N,Fp,Fst'</li><li>• 'N,Fp,Fst,Ap'</li><li>• 'N,Fp,Fst,Ast'</li><li>• 'N,Fst,Ap,Ast'</li></ul>

Design String	Valid Specification Strings
'Nyquist'	<p>See <code>fdesign.nyquist</code> for a description of the specification string entries. For all Nyquist specifications, you must specify the <math>L</math>th band. This typically corresponds to the interpolation factor so that the nonzero samples of the upsampler output are preserved.</p> <ul style="list-style-type: none"> <li>• 'TW,Ast' (default string)</li> <li>• 'N'</li> <li>• 'N,Ast'</li> <li>• 'N,Ast'</li> </ul>
'Raised Cosine'	<p>See <code>fdesign.pulseshaping</code> for a description of the specification string entries.</p> <ul style="list-style-type: none"> <li>• 'Ast,Beta' (default string)</li> <li>• 'Nsym,Beta'</li> <li>• 'N,Beta'</li> </ul> <p>The specification string must be preceded by an integer-valued <code>SamplesPerSymbol</code>.</p>
'Square Root Raised Cosine'	<p>See <code>fdesign.pulseshaping</code> for a description of the specification string entries.</p> <ul style="list-style-type: none"> <li>• 'Ast,Beta' (default string)</li> <li>• 'Nsym,Beta'</li> <li>• 'N,Beta'</li> </ul> <p>The specification string must be preceded by an integer-valued <code>SamplesPerSymbol</code>.</p>

`D = fdesign.interpolator(...,spec,specvalue1,specvalue2,...)`  
constructs an object `D` and sets its specifications at construction time.

# fdesign.interpolator

---

`D = fdesign.interpolator(...,Fs)` adds the argument `Fs`, specified in Hz, to define the sampling frequency to use. In this case, all frequencies in the specifications are in Hz as well.

`d = fdesign.interpolator(...,MAGUNITS)` specifies the units for any magnitude specification you provide in the input arguments. `MAGUNITS` can be one of

- 'linear' — specify the magnitude in linear units.
- 'dB' — specify the magnitude in dB (decibels).
- 'squared' — specify the magnitude in power units.

When you omit the `MAGUNITS` argument, `fdesign` assumes that all magnitudes are in decibels. Note that `fdesign` stores all magnitude specifications in decibels (converting to decibels when necessary) regardless of how you specify the magnitudes.

## Examples

These examples show how to construct interpolating filter specification objects. First, create a default specifications object without using input arguments except for the interpolation factor `l`.

```
l = 2;  
d = fdesign.interpolator(2);
```

Now create an object by passing a specification string `'fst1,fp1,fp2,fst2,ast1,ap,ast2'` and a design — the resulting object uses default values for all of the filter specifications. You must provide the design input argument when you include a specification.

```
d=fdesign.interpolator(8,'bandpass','fst1,fp1,fp2,fst2,ast1,ap,ast2');
```

Create another interpolating filter object, passing the specification values to the object rather than accepting the default values for, in this case, `fp,fst,ap,ast`.

```
d=fdesign.interpolator(3,'lowpass',.45,0.55,.1,60);
```

Now pass the filter specifications that correspond to the specifications — `n,fc,ap,ast`.

```
d=fdesign.interpolator(3,'ciccomp',1,2,'n,fc,ap,ast',...  
20,0.45,.05,50);
```

With the specifications object in your workspace, design an interpolator using the `equiripple` design method.

```
hm = design(d,'equiripple');
```

Pass a new specification type for the filter, specifying the filter order.

```
d = fdesign.interpolator(5,'CIC',1,'fp,ast',0.55,55);
```

With the specifications object in your workspace, design an interpolator using the `multisection` design method.

```
hm = design(d,'multisection');
```

In this example, you specify a sampling frequency as the right most input argument. Here, it is set to 1000 Hz.

```
d=fdesign.interpolator(8,'bandpass','fst1,fp1,fp2,fst2,ast1,ap,ast2',...  
0.25,0.35,.55,.65,50,.05,1e3);
```

In this, the last example, use the `linear` option for the filter specification object and specify the stopband ripple attenuation in linear form.

```
d = fdesign.interpolator(4,'lowpass','n,fst,ap,ast',15,0.55,.05,...  
1e3,'linear'); % 1e3 = 60dB.
```

Now design a CIC interpolator for a signal sampled at 19200 Hz. Specify the differential delay of 2 and set the attenuation of information beyond 50 Hz to be at least 80 dB.

The filter object sampling frequency is  $(1 \times f_s)$  where `fs` is the sampling frequency of the input signal.

## fdesign.interpolator

---

```
dd = 2;      % Differential delay.
fp = 50;    % Passband of interest.
ast = 80;   % Minimum attenuation of alias components in passband.
fs = 600;   % Sampling frequency for input signal.
l = 32;     % Interpolation factor.
d = fdesign.interpolator(l,'cic',dd,'fp,ast',fp,ast,l*fs);
hm = design(d); %Use the default design method.
```


This next example results in a minimum-order CIC compensator that interpolates by 4 and compensates for the droop in the passband for the CIC filter `hm` from the previous example.

```
nsecs = hm.numberofsections;
d = fdesign.interpolator(4,'ciccomp',dd,nsecs,...
50,100,0.1,80,fs);
hmc = design(d,'equiripple');
hmc.arithmetic = 'fixed';
```

`hmc` is designed to compensate for `hm`. To see the effect of the compensating CIC filter, use FVTool to analyze both filters individually and include the compound filter response by cascading `hm` and `hmc`.

```
hfvtool = fvtool(hmc,hm,cascade(hmc,hm),'fs',[fs,l*fs,l*fs],...
'showreference','off');
legend(hfvtool,'CIC Compensator','CIC Interpolator',...
'Overall Response');
```

FVTool returns with this plot.




For the third example, use `fdesign.interpolator` to design a minimum-order Nyquist interpolator that uses a Kaiser window. For comparison, design a multistage interpolator as well and compare the responses.

```


l = 15; % Set the interpolation factor and the Nyquist band.
tw = 0.05; % Specify the normalized transition width.
ast = 40; % Set the minimum stopband attenuation in dB.
d = fdesign.interpolator(l,'nyquist',l,tw,ast);
hm = design(d,'kaiserwin');
hm2 = design(d,'multistage'); % Design the multistage interpolator.
hfv = fvtool(hm,hm2);
legend(hfv,'Kaiser Window','Multistage')
    
```

FVTool shows both responses.



Design a lowpass interpolator for an interpolation factor of 8. Compare the single-stage equiripple design to a multistage design with the same interpolation factor.

```
l = 8; % Interpolation factor.
d = fdesign.interpolator(l,'lowpass');
hm(1) = design(d,'equiripple');
% Use halfband filters whenever possible.
hm(2) = design(d,'multistage','usehalfbands',true);
hfvt = fvtool(hm);
legend(hfvt,'Single-Stage Equiripple','Multistage')
```



## See Also

[fdesign](#) | [fdesign.arbmag](#) | [fdesign.arbmagnphase](#) |  
[fdesign.interpolator](#) | [fdesign.rsrc](#) | [setspecs](#)

# fdesign.isinchnp

---

**Purpose** Inverse sinc highpass filter specification

**Syntax**

```
D = fdesign.isinchnp
D = fdesign.isinchnp(SPEC)
D = fdesign.isinchnp(SPEC,specvalue1,specvalue2,...)
D = fdesign.isinchnp(specvalue1,specvalue2,specvalue3,
    specvalue4)
D = fdesign.isinchnp(...,Fs)
D = fdesign.isinchnp(...,MAGUNITS)
```

**Description** `D = fdesign.isinchnp` constructs an inverse sinc highpass filter specification object `D`, applying default values for the default specification string `'Fst,Fp,Ast,Ap'`.

`D = fdesign.isinchnp(SPEC)` constructs object `D` and sets the `Specification` property to `SPEC`. Entries in the `SPEC` string represent various filter response features, such as the filter order, that govern the filter design. Valid entries for `SPEC` are shown below. The strings are not case sensitive.

- `'Fst,Fp,Ast,Ap'` (default spec)
- `'N,Fc,Ast,Ap'`
- `'N,Fst,Fp'`
- `'N,Fp,Ast,Ap'`
- `'N,Fst,Ast,Ap'`

The string entries are defined as follows:

- `Ast` — attenuation in the stopband in decibels (the default units). Also called `Astop`.
- `Ap` — amount of ripple allowed in the passband in decibels (the default units). Also called `Apass`.
- `Fp` — frequency at the start of the passband. Specified in normalized frequency units. Also called `Fpass`.

- `Fst` — frequency at the end of the stopband. Specified in normalized frequency units. Also called `Fstop`.
- `N` — filter order.

The filter design methods that apply to an inverse sinc highpass filter specification object change depending on the value of the `Specification` property. Use `designmethods` to determine which design method applies to a specific `Specification`.

Use `designopts` to see the available design options for a specific design method. Enter `help(D,METHOD)` at the MATLAB command line to obtain detailed information on the design options for a given design method, `METHOD`.

`D = fdesign.isinchnp(SPEC,specvalue1,specvalue2,...)`  
 constructs an object `D` and sets the specifications at construction time.

`D = fdesign.isinchnp(specvalue1,specvalue2,specvalue3,specvalue4)`  
 constructs an object `D` assuming the default `Specification` property string `'Fst,Fp,Ast,Ap'`, using the values you provide in `specvalue1,specvalue2, specvalue3, and specvalue4`.

`D = fdesign.isinchnp(...,Fs)` adds the argument `Fs`, specified in Hz to define the sampling frequency to use. In this case, all frequencies in the specifications are in Hz as well.

`D = fdesign.isinchnp(...,MAGUNITS)` specifies the units for any magnitude specification you provide in the input arguments. `MAGUNITS` can be one of

- `'linear'` — specify the magnitude in linear units
- `'dB'` — specify the magnitude in dB (decibels)
- `'squared'` — specify the magnitude in power units

When you omit the `MAGUNITS` argument, `fdesign` assumes that all magnitudes are in decibels. Note that `fdesign` stores all magnitude specifications in decibels (converting to decibels when necessary) regardless of how you specify the magnitudes.

# fdesign.isinchnp

---

The design method of `fdesign.isinchnp` implements a filter with a passband magnitude response equal to:


$$H(\omega) = \text{sinc}(C(1 - \omega))^{-P}$$

You can control the values of the sinc frequency factor,  $C$ , and the sinc power,  $P$ , using the `'SincFrequencyFactor'` and `'SincPower'` options in the design method. `'SincFrequencyFactor'` and `'SincPower'` default to 0.5 and 1 respectively.

## Examples


Design a minimum order inverse sinc highpass filter and shape the stopband to have a slope of 20 dB/radian/sample.

```
d = fdesign.isinchnp('Fst,Fp,Ast,Ap',.4,.5,40,0.01);  
Hd = design(d);  
% Shape the stopband to have a linear slope of 20 dB/rad/sample  
Hd1 = design(d,'StopbandShape','linear','StopbandDecay',20);  
fvtool(Hd,Hd1);
```



Design a 50th order inverse sinc highpass filter. Set the sinc frequency factor to 0.25, and the sinc power to 16 to achieve a magnitude response in the passband of the form  $H(\omega) = \text{sinc}(0.25*(1-\omega))^{(-16)}$ .

```
d = fdesign.isinchnp('N,Fst,Fp',50,.4,.5);
Hd = design(d,'SincFrequencyFactor',0.25,'SincPower',16);
fvtool(Hd);
```



## See Also

`design` | `designmethods` | `fdesign` | `fdesign.ciccomp` |  
`fdesign.highpass` | `fdesign.isinchnp` | `fdesign.nyquist`

**Purpose**

Inverse sinc lowpass filter specification

**Syntax**

```
d = fdesign.isinclp
d = fdesign.isinclp(spec)
d = fdesign.isinclp(spec,specvalue1,specvalue2,...)
d = fdesign.isinclp(specvalue1,specvalue2,specvalue3,
    specvalue4)
d = fdesign.isinclp(...,Fs)
d = fdesign.isinclp(...,MAGUNITS)
```

**Description**

`d = fdesign.isinclp` constructs an inverse sinc lowpass filter specification object `d`, applying default values for the default specification string, `'Fp,Fst,Ap,Ast'`.

`d = fdesign.isinclp(spec)` constructs object `d` and sets its 'Specification' to `spec`. Entries in the `spec` string represent various filter response features, such as the filter order, that govern the filter design. Valid entries for `spec` are shown below. The strings are not case sensitive.

- `'Fp,Fst,Ap,Ast'` (default `spec`)
- `'N,Fc,Ap,Ast'`
- `'N,Fp,Ap,Ast'`
- `'N,Fp,Fst'`
- `'N,Fst,Ap,Ast'`

The string entries are defined as follows:

- `Ast` — attenuation in the stopband in decibels (the default units). Also called `Astop`.
- `Ap` — amount of ripple allowed in the passband in decibels (the default units). Also called `Apass`.
- `Fp` — frequency at the start of the passband. Specified in normalized frequency units. Also called `Fpass`.

# fdesign.isinclp

---

- *Fst* — frequency at the end of the stopband. Specified in normalized frequency units. Also called *Fstop*.
- *N* — filter order.

The filter design methods that apply to an inverse sinc lowpass filter specification object change depending on the `Specification` string. Use `designmethods` to determine which design method applies to an object and its specification string.

`d = fdesign.isinclp(spec,specvalue1,specvalue2,...)`  
constructs an object `d` and sets its specifications at construction time.

`d = fdesign.isinclp(specvalue1,specvalue2,specvalue3,specvalue4)`  
constructs an object `d` assuming the default `Specification` property string `'Fp,Fst,Ap,Ast'`, using the values you provide in `specvalue1,specvalue2,specvalue3,` and `specvalue4`.

`d = fdesign.isinclp(...,Fs)` adds the argument `Fs`, specified in Hz to define the sampling frequency to use. In this case, all frequencies in the specifications are in Hz as well.

`d = fdesign.isinclp(...,MAGUNITS)` specifies the units for any magnitude specification you provide in the input arguments. `MAGUNITS` can be one of

- `'linear'` — specify the magnitude in linear units
- `'dB'` — specify the magnitude in dB (decibels)
- `'squared'` — specify the magnitude in power units

When you omit the `MAGUNITS` argument, `fdesign` assumes that all magnitudes are in decibels. Note that `fdesign` stores all magnitude specifications in decibels (converting to decibels when necessary) regardless of how you specify the magnitudes.

The design method of `fdesign.isinclp` implements a filter with a passband magnitude response equal to:

$$H(\omega) = \text{sinc}(C\omega)^{-P}$$

You can control the values of the sinc frequency factor,  $C$ , and the sinc power,  $P$ , using the 'SincFrequencyFactor' and 'SincPower' options in the design method. 'SincFrequencyFactor' and 'SincPower' default to 0.5 and 1 respectively.

## Examples


Pass the specifications for the default specification — 'Fp,Fst,Ap,Ast' — as input arguments to the specifications object.

```
d = fdesign.isinclp(.4,.5,.01,40);  
hd = design(d,'equiripple');  
fvtool(hd);
```

---

Design a 50th order inverse sinc lowpass filter. Set the sinc frequency factor to 0.25 and the sinc power to 16 to achieve a magnitude response in the passband of the form  $H(w) = \text{sinc}(0.25*w)^{-16}$ .

```
d = fdesign.isinclp('N,Fp,Fst',50,.4,.5);  
Hd = design(d,'SincFrequencyFactor',0.25,'SincPower',16);  
fvtool(Hd, 'MagnitudeDisplay', 'Magnitude');
```



## See Also

`fdesign` | `fdesign.bandpass` | `fdesign.bandstop` |  
`fdesign.halfband` | `fdesign.highpass` | `fdesign.lowpass` |  
`fdesign.nyquist`

**Purpose** Lowpass filter specification

**Syntax**

```
D = fdesign.lowpass
D = fdesign.lowpass(SPEC)
D = fdesign.lowpass(SPEC,specvalue1,specvalue2,...)
D = fdesign.lowpass(specvalue1,specvalue2,specvalue3,
    specvalue4)
D = fdesign.lowpass(...,Fs)
D = fdesign.lowpass(...,MAGUNITS)
```

**Description**

D = fdesign.lowpass constructs a lowpass filter specification object D, applying default values for the default specification string 'Fp,Fst,Ap,Ast'.

D = fdesign.lowpass(SPEC) constructs object D and sets the Specification property to the string in SPEC. Entries in the SPEC string represent various filter response features, such as the filter order, that govern the filter design. Valid entries for SPEC are shown below. The strings are not case sensitive.

---

**Note** Specifications strings marked with an asterisk require the DSP System Toolbox software.

---


- 'Fp,Fst,Ap,Ast' (default spec)
- 'N,F3db'
- 'N,F3db,Ap' \*
- 'N,F3db,Ap,Ast' \*
- 'N,F3db,Ast' \*
- 'N,F3db,Fst' \*
- 'N,Fc'
- "N,Fc,Ap,Ast"

- 'N,Fp,Ap'
- 'N,Fp,Ap,Ast'
- 'N,Fp,Fst,Ap' \*
- 'N,Fp,F3db' \*
- 'N,Fp,Fst'
- 'N,Fp,Fst,Ast' \*
- 'N,Fst,Ap,Ast' \*
- 'N,Fst,Ast'
- 'Nb,Na,Fp,Fst' \*

The string entries are defined as follows:

- Ap — amount of ripple allowed in the pass band in decibels (the default units). Also called Apass.
- Ast — attenuation in the stop band in decibels (the default units). Also called Astop.
- F3db — cutoff frequency for the point 3 dB point below the passband value. Specified in normalized frequency units.
- Fc — cutoff frequency for the point 6 dB point below the passband value. Specified in normalized frequency units.
- Fp — frequency at the start of the pass band. Specified in normalized frequency units. Also called Fpass.
- Fst — frequency at the end of the stop band. Specified in normalized frequency units. Also called Fstop.
- N — filter order.
- Na and Nb are the order of the denominator and numerator.

Graphically, the filter specifications look similar to those shown in the following figure.



Regions between specification values like  $F_p$  and  $F_{st}$  are transition regions where the filter response is not explicitly defined.

`D = fdesign.lowpass(SPEC,specvalue1,specvalue2,...)` constructs an object `D` and sets the specification values at construction time using `specvalue1`, `specvalue2`, and so on for all of the specification variables in `SPEC`.

`D = fdesign.lowpass(specvalue1,specvalue2,specvalue3,specvalue4)` constructs an object `D` with values for the default Specification property string `'Fp,Fst,Ap,Ast'` using the specifications you provide as input arguments `specvalue1,specvalue2,specvalue3,specvalue4`.

`D = fdesign.lowpass(...,Fs)` adds the argument `Fs`, specified in Hz to define the sampling frequency to use. In this case, all frequencies in the specifications are in Hz as well.

`D = fdesign.lowpass(...,MAGUNITS)` specifies the units for any magnitude specification you provide in the input arguments. `MAGUNITS` can be one of

- `'linear'` — specify the magnitude in linear units
- `'dB'` — specify the magnitude in dB (decibels)
- `'squared'` — specify the magnitude in power units

When you omit the `MAGNUNITS` argument, `fdesign` assumes that all magnitudes are in decibels. Note that `fdesign` stores all magnitude specifications in decibels (converting to decibels when necessary) regardless of how you specify the magnitudes.

## Examples

Lowpass filter a discrete-time signal consisting of two sine waves.

Create a lowpass filter specification object. Specify the passband frequency to be  $0.15\pi$  radians/sample and the stopband frequency to be  $0.25\pi$  radians/sample. Specify 1 dB of allowable passband ripple and a stopband attenuation of 60 dB.

```
d=fdesign.lowpass('Fp,Fst,Ap,Ast',0.15,0.25,1,60);
```

Query the valid design methods for your filter specification object, `d`.

```
designmethods(d)
```

Create an FIR equiripple filter and view the filter magnitude response with `fvtool`.

```
Hd = design(d,'equiripple');  
fvtool(Hd);
```

Create a signal consisting of the sum of two discrete-time sinusoids with frequencies of  $\pi/8$  and  $\pi/4$  radians/sample and amplitudes of 1 and 0.25 respectively. Filter the discrete-time signal with the FIR equiripple filter object, `Hd`.

```
n = 0:159;  
x = 0.25*cos((pi/8)*n)+sin((pi/4)*n);  
y = filter(Hd,x);  
Domega = (2*pi)/160;  
freq = 0:(2*pi)/160:pi;  
xdft = fft(x);  
ydft = fft(y);  
plot(freq,abs(xdft(1:length(x)/2+1)));  
hold on;  
plot(freq,abs(ydft(1:length(y)/2+1)),'r','linewidth',2);
```

```
legend('Original Signal','Highpass Signal', ...  
      'Location','NorthEast');  
ylabel('Magnitude'); xlabel('Radians/Sample');
```

---

Create a filter of order 10 with a 6-dB frequency of 9.6 kHz and a sampling frequency of 48 kHz.

```
d=fdesign.lowpass('N,Fc',10,9600,48000);  
designmethods(d)  
% only valid design method is FIR window method  
Hd = design(d);  
% Display filter magnitude response  
fvtool(Hd);
```

Zoom in on the magnitude response to verify that the -6 dB point is at 9.6 kHz.

---

If you have the DSP System Toolbox software, you can specify the shape of the stopband and the rate at which the stopband decays. The following example requires the DSP System Toolbox.

Create an FIR equiripple filter with a passband frequency of  $0.2\pi$  radians/sample, a stopband frequency of  $0.25\pi$  radians/sample, a passband ripple of 1 dB, and a stopband attenuation of 60 dB. Design the filter with a 20 dB/rad/sample linear stopband.

```
D = fdesign.lowpass('Fp,Fst,Ap,Ast',0.2,0.25,1,60);  
Hd = design(D,'equiripple','StopBandShape','linear','StopBandDecay',20);  
fvtool(Hd);
```

## See Also

[design](#) | [designmethods](#) | [fdesign](#)

# fdesign.notch

---

**Purpose** Notch filter specification

**Syntax**

```
d = fdesign.notch(specstring, value1, value2, ...)  
d = fdesign.notch(n,f0,q)  
d = fdesign.notch(...,Fs)  
d = fdesign.notch(...,MAGUNITS)
```

**Description** `d = fdesign.notch(specstring, value1, value2, ...)` constructs a notch filter specification object `d`, with a specification string set to `specstring` and values provided for all members of the `specstring`. The possible specification strings, which are not case sensitive, are listed as follows:

- 'N,F0,Q' (default)
- 'N,F0,Q,Ap'
- 'N,F0,Q,Ast'
- 'N,F0,Q,Ap,Ast'
- 'N,F0,BW'
- 'N,F0,BW,Ap'
- 'N,F0,BW,Ast'
- 'N,F0,BW,Ap,Ast'

where the variables are defined as follows:

- N - Filter Order (must be even)
- F0 - Center Frequency
- Q - Quality Factor
- BW - 3-dB Bandwidth
- Ap - Passband Ripple (decibels)
- Ast - Stopband Attenuation (decibels)

Different specification strings, resulting in different specification objects, may have different design methods available. Use the function

`designmethods` to get a list of design methods available for a given specification. For example:

```
d = fdesign.notch('N,F0,Q,Ap',6,0.5,10,1);
% designmethods(d) returns
% Design Methods for class fdesign.notch (N,F0,Q,Ap):
% cheby1
```

`d = fdesign.notch(n,f0,q)` constructs a notch filter specification object using the default specstring ('N,F0,Q') and setting the corresponding values to `n`, `f0`, and `q`.

By default, all frequency specifications are assumed to be in normalized frequency units. All magnitude specifications are assumed to be in decibels.

`d = fdesign.notch(...,Fs)` constructs a notch filter specification object while providing the sampling frequency of the signal to be filtered. `Fs` must be specified as a scalar trailing the other values provided. If you specify an `Fs`, it is assumed to be in Hz, as are all the other frequency values provided.


`d = fdesign.notch(...,MAGUNITS)` constructs a notch filter specification while providing the units for any magnitude specification given. `MAGUNITS` can be one of the following: 'linear', 'dB', or 'squared'. If this argument is omitted, 'dB' is assumed. The magnitude specifications are always converted and stored in decibels regardless of how they were specified. If `Fs` is provided, `MAGUNITS` must follow `Fs` in the input argument list.

## Examples

Design a notching filter with a passband ripple of 1 dB.

```
d = fdesign.notch('N,F0,Q,Ap',6,0.5,10,1);
Hd = design(d);
fvtool(Hd)
```

# fdesign.notch



**See Also** [fdesign](#) | [fdesign.peak](#)

**Purpose**

Nyquist filter specification

**Syntax**

```
d = fdesign.nyquist
d = fdesign.nyquist(1,spec)
d = fdesign.nyquist(1,spec,specvalue1,specvalue2,...)
d = fdesign.nyquist(1,specvalue1,specvalue2)
d = fdesign.nyquist(...,fs)
d = fdesign.nyquist(...,magunits)
```

**Description**

`d = fdesign.nyquist` constructs a Nyquist or L-band filter specification object `d`, applying default values for the properties `tw` and `ast`. By default, the filter object designs a minimum-order half-band ( $L=2$ ) Nyquist filter.

Using `fdesign.nyquist` with a design method generates a `dfilt` object.

`d = fdesign.nyquist(1,spec)` constructs object `d` and sets its Specification property to `spec`. Use `1` to specify the desired value for `L`.  $L = 2$  designs a half-band FIR filter,  $L = 3$  a third-band FIR filter, and so on. When you use a Nyquist filter as an interpolator, `l` or `L` is the interpolation factor. The first input argument must be `l` when you are not using the default syntax `d = fdesign.nyquist`.

Entries in the `spec` string represent various filter response features, such as the filter order, that govern the filter design. Valid entries for `spec` are shown below. The strings are not case sensitive.

- `tw,ast` (default `spec`)
- `n,tw`
- `n`
- `n,ast`

The string entries are defined as follows:

- `ast` — attenuation in the stop band in decibels (the default units).
- `n` — filter order.

- `tw` — width of the transition region between the pass and stop bands. Specified in normalized frequency units.

The filter design methods that apply to a Nyquist filter specification object change depending on the `Specification` string. Use `designmethods` to determine which design method applies to an object and its specification string. Different filter design methods also have options that you can specify. Use `designopts` with the design method string to see the available options. For example:

```
f=fdesign.nyquist(4,'N,TW');  
designmethods(f)
```

```
d = fdesign.nyquist(1,spec,specvalue1,specvalue2,...)
```

constructs an object `d` and sets its specification to `spec`, and the specification values to `specvalue1`, `specvalue2`, and so on at construction time.

```
d = fdesign.nyquist(1,specvalue1,specvalue2)
```

constructs an object `d` with the values you provide in `1`, `specvalue1`, `specvalue2` as the values for `l`, `tw` and `ast`.

```
d = fdesign.nyquist(...,fs)
```

adds the argument `fs`, specified in Hz to define the sampling frequency to use. In this case, all frequencies in the specifications are in Hz as well.

```
d = fdesign.nyquist(...,magunits)
```

specifies the units for any magnitude specification you provide in the input arguments. `magunits` can be one of

- `linear` — specify the magnitude in linear units
- `dB` — specify the magnitude in dB (decibels)
- `squared` — specify the magnitude in power units

When you omit the `magunits` argument, `fdesign` assumes that all magnitudes are in decibels. Note that `fdesign` stores all magnitude specifications in decibels (converting to decibels when necessary) regardless of how you specify the magnitudes.

## Limitations of the Nyquist fdesign Object

Using Nyquist filter specification objects with the `equiripple` design method imposes a few limitations on the resulting filter, caused by the `equiripple` design algorithm.

- When you request a minimum-order design from `equiripple` with your Nyquist object, the design algorithm might not converge and can fail with a filter convergence error.
- When you specify the order of your desired filter, and use the `equiripple` design method, the design might not converge.
- Generally, the following specifications, alone or in combination with one another, can cause filter convergence problems with Nyquist objects and the `equiripple` design method.
  - very high order
  - small transition width
  - very large stopband attenuation

Note that halfband filters (filters where  $\text{band} = 2$ ) do not exhibit convergence problems.

When convergence issues arise, either in the cases mentioned or in others, you might be able to design your filter with the `kaiserwin` method.

In addition, if you use Nyquist objects to design decimators or interpolators (where the interpolation or decimation factor is not a prime number), using multistage filter designs might be your best approach.

## Examples

These examples show how to construct a Nyquist filter specification object. First, create a default specifications object without using input arguments.

```
d=fdesign.nyquist
```

Now create an object by passing a specification type string 'n,ast' — the resulting object uses default values for n and ast.

```
d=fdesign.nyquist(2,'n,ast')
```

Create another Nyquist filter object, passing the specification values to the object rather than accepting the default values for n and ast.

```
d=fdesign.nyquist(3,'n,ast',42,80)
```

Finally, pass the filter specifications that correspond to the default Specification — tw,ast. When you pass only the values, fdesign.nyquist assumes the default Specification string.

```
d = fdesign.nyquist(4,.01,80)
```

Now design a Nyquist filter using the kaiserwin design method.


```
hd = design(d,'kaiserwin')
```

Create two equiripple Nyquist 4th-band filters with and without a nonnegative zero phase response:

```
f=fdesign.nyquist(4,'N,TW',12,0.2);  
% Equiripple Nyquist 4th-band filter with  
% nonnegative zero phase response  
Hd1=design(f,'equiripple','zerophase',true);  
% Equiripple Nyquist 4th-band filter with 'ZeroPhase' set to false  
% 'zerophase',false is the default  
Hd2=design(f,'equiripple','zerophase',false);  
%Obtain real-valued amplitudes (not magnitudes)  
[Hr_zerophase,W]=zerophase(Hd1);  
[Hr,W]=zerophase(Hd2);  
% Plot and compare response  
plot(W,Hr_zerophase,'k','linewidth',2);  
xlabel('Radians/sample'); ylabel('Amplitude');  
hold on;  
plot(W,Hr,'r');  
axis tight; grid on;
```

```
legend('with 'ZeroPhase', true','with 'ZeroPhase' false');
```

Note that the amplitude of the zero phase response (black line) is nonnegative for all frequencies.



The 'ZeroPhase' option is valid only for equiripple Nyquist designs with the 'N,TW' specification. You cannot specify 'MinPhase' and 'ZeroPhase' to be simultaneously 'true'.

## See Also

fdesign | fdesign.interpolator | fdesign.halfband |  
fdesign.interpolator | fdesign.rsrc | zerophase

# fdesign.octave

---

**Purpose** Octave filter specification

**Syntax**

```
d = fdesign.octave(1)
d = fdesign.octave(1, MASK)
d = fdesign.octave(1, MASK, spec)
d = fdesign.octave(..., Fs)
```

**Description** `d = fdesign.octave(1)` constructs an octave filter specification object `d`, with 1 bands per octave. The default value for 1 is 1.

`d = fdesign.octave(1, MASK)` constructs an octave filter specification object `d` with 1 bands per octave and `MASK` specification for the FVTool. The available values for `mask` are:

- 'class 0'
- 'class 1'
- 'class 2'

`d = fdesign.octave(1, MASK, spec)` constructs an octave filter specification object `d` with 1 bands per octave, `MASK` specification for the FVTool, and the `spec` specification string. The specification strings available are:

- 'N, F0'

(not case sensitive), where:


- N is the filter order
- F0 is the center frequency.

The center frequency is typically specified in normalized frequency units, unless a sampling frequency in Hz is included in the specification: `d = fdesign.octave(..., Fs)`. In this case, all frequencies must be specified in Hz, with the center frequency falling between 20 Hz and 20 kHz (the audio range).

**Examples** Design an sixth order, octave-band class 0 filter with a center frequency of 1000 Hz and, a sampling frequency of 44.1 kHz.

```
d = fdesign.octave(1, 'Class 0', 'N,F0', 6, 1000, 44100);  
Hd = design(d);  
fvtool(Hd)
```

The following figure shows the magnitude response plot of the filter. The logarithmic scale for frequency is automatically set by FVTool for the octave filters.

**See Also**

fdesign

# fdesign.parmeq

---

**Purpose** Parametric equalizer filter specification

**Syntax** `d = fdesign.parmeq(spec, specvalue1, specvalue2, ...)`  
`d = fdesign.parmeq(... fs)`

**Description** `d = fdesign.parmeq(spec, specvalue1, specvalue2, ...)` constructs a parametric equalizer filter design object, where `spec` is a non-case sensitive specification string. The choices for `spec` are as follows:

- 'FO, BW, BWp, Gref, GO, GBW, Gp' (minimum order default)
- 'FO, BW, BWst, Gref, GO, GBW, Gst'
- 'FO, BW, BWp, Gref, GO, GBW, Gp, Gst'
- 'N, FO, BW, Gref, GO, GBW'
- 'N, FO, BW, Gref, GO, GBW, Gp'
- 'N, FO, Fc, Qa, GO'
- 'N, FO, Fc, S, GO'
- 'N, FO, BW, Gref, GO, GBW, Gst'
- 'N, FO, BW, Gref, GO, GBW, Gp, Gst'
- 'N, Flow, Fhigh, Gref, GO, GBW'
- 'N, Flow, Fhigh, Gref, GO, GBW, Gp'
- 'N, Flow, Fhigh, Gref, GO, GBW, Gst'
- 'N, Flow, Fhigh, Gref, GO, GBW, Gp, Gst'

where the parameters are defined as follows:

- BW — Bandwidth
- BWp — Passband Bandwidth
- BWst — Stopband Bandwidth
- Gref — Reference Gain (decibels)

- $G_0$  — Center Frequency Gain (decibels)
- $GBW$  — Gain at which Bandwidth (BW) is measured (decibels)
- $G_p$  — Passband Gain (decibels)
- $G_{st}$  — Stopband Gain (decibels)
- $N$  — Filter Order
- $F_0$  — Center Frequency
- $F_c$  — Cutoff frequency
- $F_{high}$  - Higher Frequency at Gain  $GBW$
- $F_{low}$  - Lower Frequency at Gain  $GBW$
- $Q_a$ -Quality Factor
- $S$ -Slope Parameter for Shelving Filters

Regardless of the specification string chosen, there are some conditions that apply to the specification parameters. These are as follows:


- Specifications for parametric equalizers must be given in decibels
- To boost the input signal, set  $G_0 > G_{ref}$ ; to cut, set  $G_{ref} > G_0$
- For boost:  $G_0 > G_p > GBW > G_{st} > G_{ref}$ ; For cut:  $G_0 < G_p < GBW < G_{st} < G_{ref}$
- Bandwidth must satisfy:  $BW_{st} > BW > BW_p$

`d = fdesign.parmeq(... fs)` adds the input sampling frequency.  $F_s$  must be specified as a scalar trailing the other numerical values provided, and is assumed to be in Hz.

## Examples


Design a Chebyshev Type II parametric equalizer filter that cuts by 12 dB:

```
d = fdesign.parmeq('N,Flow,Fhigh,Gref,G0,GBW,Gst',...
    4,.3,.5,0,-12,-10,-1);
Hd = design(d,'cheby2');
fvtool(Hd)
```



Design a 4th order audio lowpass ( $F0 = 0$ ) shelving filter with cutoff frequency of  $Fc = 0.25$ , quality factor  $Qa = 10$ , and boost gain of  $G0 = 8$  dB:


```
d = fdesign.parameq('N,F0,Fc,Qa,G0',4,0,0.25,10,8);  
Hd = design(d);  
fvtool(Hd)
```



Design 4th-order highpass shelving filters with  $S=1.5$  and  $S=3$ :

```

N=4;
FO = 1;
Fc = .4; % Cutoff Frequency
GO = 10;
S = 1.5;
S2=3;
f = fdesign.parmeq('N,FO,Fc,S,GO',N,FO,Fc,S,GO);
h1 = design(f);
f.S=3;
h2=design(f);
hfvt=fvtool([h1 h2]);
set(hfvt,'Filters',[h1 h2]);
legend(hfvt,'S=1.5','S=3');
    
```



## See Also

fdesign

## How To

- Parametric Equalizer Design

**Purpose**

Peak filter specification

**Syntax**

```
d = fdesign.peak(specstring, value1, value2, ...)  
d = fdesign.peak(n,f0,q)  
d = fdesign.peak(...,Fs)  
d = fdesign.peak(...,MAGUNITS)
```

**Description**

`d = fdesign.peak(specstring, value1, value2, ...)` constructs a peaking filter specification object `d`, with a specification string set to `specstring` and values provided for all members of the `specstring`. The possible specification strings, which are not case sensitive, are listed as follows:

- 'N,F0,Q' (default)
- 'N,F0,Q,Ap'
- 'N,F0,Q,Ast'
- 'N,F0,Q,Ap,Ast'
- 'N,F0,BW'
- 'N,F0,BW,Ap'
- 'N,F0,BW,Ast'
- 'N,F0,BW,Ap,Ast'

where the variables are defined as follows:

- N - Filter Order (must be even)
- F0 - Center Frequency
- Q - Quality Factor
- BW - 3-dB Bandwidth
- Ap - Passband Ripple (decibels)
- Ast - Stopband Attenuation (decibels)

Different specification strings, resulting in different specification objects, may have different design methods available. Use the function

`designmethods` to get a list of design methods available for a given specification. For example:

```
>> d = fdesign.peak('N,F0,Q,Ap',6,0.5,10,1);  
>> designmethods(d)
```

Design Methods for class `fdesign.peak (N,F0,Q,Ap)`:

`cheby1`

`d = fdesign.peak(n,f0,q)` constructs a peaking filter specification object using the default `specstring ('N,F0,Q')` and setting the corresponding values to `n`, `f0`, and `q`.

By default, all frequency specifications are assumed to be in normalized frequency units. All magnitude specifications are assumed to be in decibels.

`d = fdesign.peak(...,Fs)` constructs a peak filter specification object while providing the sampling frequency of the signal to be filtered. `Fs` must be specified as a scalar trailing the other values provided. If you specify an `Fs`, it is assumed to be in Hz, as all the other frequency values provided.

`d = fdesign.peak(...,MAGUNITS)` constructs a notch filter specification while providing the units for any magnitude specification given. `MAGUNITS` can be one of the following: `'linear'`, `'dB'`, or `'squared'`. If this argument is omitted, `'dB'` is assumed. The magnitude specifications are always converted and stored in decibels regardless of how they were specified. If `Fs` is provided, `MAGUNITS` must follow `Fs` in the input argument list.


## Examples

Design a Chebyshev Type II peaking filter with a stopband attenuation of 80 dB:

```
d = fdesign.peak('N,F0,BW,Ast',8,.65,.02,80);  
Hd = design(d,'cheby2');
```

```
fvtool(Hd)
```

This design produces a filter with the magnitude response shown in the following figure.

**See Also**

`fdesign` | `fdesign.notch` | `fdesign.parmreq`

# fdesign.polysrc

---

**Purpose** Construct polynomial sample-rate converter (POLYSRC) filter designer

**Syntax**

```
d = fdesign.polysrc(L,m)
d = fdesign.polysrc(L,m,'Fractional Delay','Np',Np)
d = fdesign.polysrc(...,Fs)
```

**Description**

`d = fdesign.polysrc(L,m)` constructs a polynomial sample-rate converter filter designer `D` with an interpolation factor `L` and a decimation factor `M`. `L` defaults to 3. `M` defaults to 2. `L` and `M` can be arbitrary positive numbers.


`d = fdesign.polysrc(L,m,'Fractional Delay','Np',Np)` initializes the filter designer specification with `Np` and sets the polynomial order to the value `Np`. If omitted `Np` defaults to 3.

`d = fdesign.polysrc(...,Fs)` specifies the sampling frequency (in Hz).

**Examples** This example shows how to design sample-rate converter that uses a 3rd order Lagrange interpolation filter to convert from 44.1kHz to 48kHz:

```
[L,M] = rat(48/44.1);
f = fdesign.polysrc(L,M,'Fractional Delay','Np',3);
Hm = design(f,'lagrange');
% Original sampling frequency
Fs = 44.1e3;
% 9408 samples, 0.213 seconds long
n = 0:9407;
% Original signal, sinusoid at 1kHz
x = sin(2*pi*1e3/Fs*n);
% 10241 samples, still 0.213 seconds
y = filter(Hm,x);
% Plot original sampled at 44.1kHz
stem(n(1:45)/Fs,x(1:45))
hold on
% Plot fractionally interpolated signal (48kHz) in red
stem((n(3:51)-2)/(Fs*L/M),y(3:51),'r','filled')
xlabel('Time (sec)');ylabel('Signal value')
legend('44.1 kHz sample rate','48 kHz sample rate')
```

This code generates the following figure.



For more information about Farrow SRCs, see the “Efficient Sample Rate Conversion between Arbitrary Factors” example, `efficientsrcdemo`.

## See Also

`fdesign`

# fdesign.pulseshaping

---

**Purpose** Pulse-shaping filter specification object

**Syntax**

```
D = fdesign.pulseshaping
D = fdesign.pulseshaping(sps)
D = fdesign.pulseshaping(sps,shape)
d = fdesign.pulseshaping(sps,shape,spec,value1,value2,...)
d = fdesign.pulseshaping(...,fs)
d = fdesign.pulseshaping(...,magunits)
```

**Description** `D = fdesign.pulseshaping` constructs a specification object `D`, which can be used to design a minimum-order raised cosine filter object with a default stop band attenuation of 60dB and a rolloff factor of 0.25.

`D = fdesign.pulseshaping(sps)` constructs a minimum-order raised cosine filter specification object `d` with a positive integer-valued oversampling factor, `SamplesPerSymbol`.

`D = fdesign.pulseshaping(sps,shape)` constructs `d` where `shape` specifies the `PulseShape` property. Valid entries for `shape` are:

- 'Raised Cosine'
- 'Square Root Raised Cosine'
- 'Gaussian'

`d = fdesign.pulseshaping(sps,shape,spec,value1,value2,...)` constructs `d` where `spec` defines the `Specification` properties. The string entries for `spec` specify various properties of the filter, including the order and frequency response. Valid entries for `spec` depend upon the `shape` property. For 'Raised Cosine' and 'Square Root Raised Cosine' filters, the valid entries for `spec` are:

- 'Ast,Beta' (minimum order; default)
- 'Nsym,Beta'
- 'N,Beta'

The string entries are defined as follows:

- **Ast** —stopband attenuation (in dB). The default stopband attenuation for a raised cosine filter is 60 dB. The default stopband attenuation for a square root raised cosine filter is 30 dB. If **Ast** is specified, the minimum-order filter is returned.
- **Beta** —rolloff factor expressed as a real-valued scalar ranging from 0 to 1. Smaller rolloff factors result in steeper transitions between the passband and stopband of the filter.
- **Nsym** —filter order in symbols. The length of the impulse response is given by  $Nsym * SamplesPerSymbol + 1$ . The product  $Nsym * SamplesPerSymbol$  must be even.
- **N** —filter order (must be even). The length of the impulse response is  $N + 1$ .

If the **shape** property is specified as 'Gaussian', the valid entries for **spec** are:

- 'Nsym,BT' (default)

The string entries are defined as follows:

- **Nsym**—filter order in symbols. **Nsym** defaults to 6. The length of the filter impulse response is  $Nsym * SamplesPerSymbol + 1$ . The product  $Nsym * SamplesPerSymbol$  must be even.
- **BT** —the 3-dB bandwidth-symbol time product. **BT** is a positive real-valued scalar, which defaults to 0.3. Larger values of **BT** produce a narrower pulse width in time with poorer concentration of energy in the frequency domain.

`d = fdesign.pulseshaping(...,fs)` specifies the sampling frequency of the signal to be filtered. **fs** must be specified as a scalar trailing the other numerical values provided. For this case, **fs** is assumed to be in Hz and is used for analysis and visualization.

`d = fdesign.pulseshaping(...,magunits)` specifies the units for any magnitude specification you provide in the input arguments. Valid entries for **magunits** are:

- **linear** — specify the magnitude in linear units

- dB — specify the magnitude in dB (decibels)
- squared — specify the magnitude in power units

When you omit the `magunits` argument, `fdesign` assumes that all magnitudes are in decibels. Note that `fdesign` stores all magnitude specifications in decibels (converting to decibels when necessary) regardless of how you specify the magnitudes.

After creating the specification object `d`, you can use the `design` function to create a filter object such as `h` in the following example:

```
d = fdesign.pulseshaping(8,'Raised Cosine','Nsym,Beta',6,0.25);  
h = design(d);
```

Normally, the `Specification` property of the specification object also determines which design methods you can use when you create the filter object. Currently, regardless of the `Specification` property, the `design` function uses the window design method with all `fdesign.pulseshaping` specification objects. The window method creates an FIR filter with a windowed impulse response.


## Examples

Pulse-shaping can be used to change the waveform of transmitted pulses so the signal bandwidth matches that of the communication channel. This helps to reduce distortion and intersymbol interference (ISI).

This example shows how to design a minimum-order raised cosine filter that provides a stop band attenuation of 60 dB, rolloff factor of 0.50, and 8 samples per symbol.


```
h = fdesign.pulseshaping(8,'Raised Cosine','Ast,Beta',60,0.50);  
Hd = design(h);  
fvtool(Hd)
```

This code generates the following figure.



This example shows how to design a raised cosine filter that spans 8 symbol durations (i.e., of order 8 symbols), has a rolloff factor of 0.50, and oversampling factor of 10.

```
h = fdesign.pulseshaping(10,'Raised Cosine','Nsym,Beta',8,0.50);  
Hd = design(h);  
fvtool(Hd, 'impulse')
```




# fdesign.pulseshaping


---

This example shows how to design a square root raised cosine filter of order 42, rolloff factor of 0.25, and 10 samples per symbol.

```
h = fdesign.pulseshaping(10,'Square Root Raised Cosine','N,Beta',42);  
Hd = design(h);  
fvtool(Hd, 'impulse')
```



The following example demonstrates how to create a Gaussian pulse-shaping filter with an oversampling factor (sps) of 10, a bandwidth-time symbol product of 0.2, and 8 symbol periods. The sampling frequency is specified as 10 kHz.



**Purpose** Rational-factor sample-rate converter specification

**Syntax**

```
D = fdesign.rsrc(L,M)
D = fdesign.rsrc(L,M,RESPONSE)
D = fdesign.rsrc(L,M,PULSESHAPINGRESPONSE,SPS)
D = fdesign.rsrc(L,M,CICRESPONSE,D)
D = fdesign.rsrc(L,M,RESPONSE,SPEC)
D = fdesign.rsrc(L,M,SPEC,specvalue1,specvalue2,...)
D = fdesign.rsrc(...,Fs)
D = fdesign.rsrc(...,MAGUNITS)
```

**Description** `D = fdesign.rsrc(L,M)` constructs a rational-factor sample-rate filter specification object `D` with the `InterpolationFactor` property equal to the positive integer `L`, the `DecimationFactor` property equal to the positive integer `M` and the `Response` property set to 'Nyquist'. The default values for the transition width and stopband attenuation in the Nyquist design are  $0.1\pi$  radians/sample and 80 dB. If `L` is unspecified, `L` defaults to 3. If `M` is unspecified, `M` defaults to 2.

`D = fdesign.rsrc(L,M,RESPONSE)` constructs an rational-factor sample-rate converter with the interpolation factor `L`, decimation factor `M`, and the response you specify in `RESPONSE`.

`D = fdesign.rsrc(L,M,PULSESHAPINGRESPONSE,SPS)` constructs a pulse-shaping rational-factor sample-rate convertor filter specification object with the 'RESPONSE' property equal to one of the supported pulseshaping filters: 'Gaussian', 'Raised Cosine', or 'Square Root Raised Cosine'. `SPS` is the samples per symbol. The samples per symbol, `SPS`, must precede any specification string.

`D = fdesign.rsrc(L,M,CICRESPONSE,D)` constructs a CIC or CIC compensator rational-factor sample-rate convertor filter specification object with the 'RESPONSE' property equal to 'CIC' or 'CICCOMP'. `D` is the differential delay. The differential delay, `D`, must precede any specification string.

Because you are designing multirate filters, the specification strings available are not the same as the specifications for designing single-rate filters. The interpolation and decimation factors are not included in

the specification strings. Different filter responses support different specifications. The following table lists the supported response types and specification strings. The strings are not case sensitive.

<b>Design String</b>	<b>Valid Specification Strings</b>
'Arbitrary Magnitude'	See <code>fdesign.arbmag</code> for a description of the specification string entries. <ul style="list-style-type: none"> <li>'N,F,A' (default string)</li> <li>'N,B,F,A'</li> </ul>
'Arbitrary Magnitude and Phase'	See <code>fdesign.arbmagnphase</code> for a description of the specification string entries. <ul style="list-style-type: none"> <li>'N,F,H' (default string)</li> <li>'N,B,F,H'</li> </ul>
'Bandpass'	See <code>fdesign.bandpass</code> for a description of the specification string entries. <ul style="list-style-type: none"> <li>'Fst1,Fp1,Fp2,Fst2,Ast1,Ap,Ast2' (default string)</li> <li>'N,Fc1,Fc2'</li> <li>'N,Fst1,Fp1,Fp2,Fst2'</li> </ul>
'Bandstop'	See <code>fdesign.bandstop</code> for a description of the specification string entries.
'CIC'	'Fp,Fst,Ap,Ast' — Only valid specification. Fp is the passband frequency, Fst is the stopband frequency, Ap is the passband ripple, and Ast is the stopband attenuation in decibels.  To specify a CIC rational-factor sample-rate convertor, include the differential delay after 'CIC' and before the filter specification string: 'Fp,Ast'. For example: <code>d = fdesign.rsrc(2,2,'cic',4);</code>

Design String	Valid Specification Strings
'CIC Compensator'	<p>See <code>fdesign.ciccomp</code> for a description of the specification string entries.</p> <ul style="list-style-type: none"> <li>'Fp,Fst,Ap,Ast' (default string)</li> <li>'N,Fc,Ap,Ast'</li> <li>'N,Fp,Ap,Ast'</li> <li>'N,Fp,Fst'</li> <li>'N,Fst,Ap,Ast'</li> </ul> <p>To specify a CIC compensator rational-factor sample-rate convertor, include the differential delay after 'CICCOMP' and before the filter specification string. For example:  <code>d = fdesign.rsrc(2,2,'ciccomp',4);</code></p>
'Differentiator'	'N' — filter order
'Gaussian'	<p>'Nsym,BT — Nsym is the filter order in symbols and BT is the bandwidth-symbol time product.</p> <p>The specification string must be preceded by an integer-valued <code>SamplesPerSymbol</code>.</p>
'Halfband'	<p>See <code>fdesign.halfband</code> for a description of the specification string entries.</p> <ul style="list-style-type: none"> <li>'TW,Ast' (default string)</li> <li>'N,TW'</li> <li>'N'</li> <li>'N,Ast'</li> </ul> <p>If you use the quasi-linear IIR design method, <code>iirlinphase</code>, with a halfband specification, the interpolation factor must be 2.</p>

<b>Design String</b>	<b>Valid Specification Strings</b>
'Highpass'	<p>See <code>fdesign.highpass</code> for a description of the specification string entries.</p> <ul style="list-style-type: none"> <li>• 'Fst,Fp,Ast,Ap' (default string)</li> <li>• 'N,F3db'</li> <li>• 'N,Fc'</li> <li>• 'N,Fc,Ast,Ap'</li> <li>• 'N,Fp,Ast,Ap'</li> <li>• 'N,Fst,Ast,Ap'</li> <li>• 'N,Fst,Fp'</li> <li>• 'N,Fst,Ast,Ap'</li> <li>• 'N,Fst,Fp,Ast'</li> </ul>
'Hilbert'	<p>See <code>fdesign.hilbert</code> for a description of the specification string entries.</p> <ul style="list-style-type: none"> <li>• 'N,TW' (default string)</li> <li>• 'TW,Ap'</li> </ul>
'Inverse-sinc Lowpass'	<p>See <code>fdesign.isinclp</code> for a description of the specification string entries.</p> <ul style="list-style-type: none"> <li>• 'Fp,Fst,Ap,Ast' (default string))</li> <li>• 'N,Fc,Ap,Ast'</li> <li>• 'N,Fp,Fst'</li> <li>• 'N,Fst,Ap,Ast'</li> </ul>

<b>Design String</b>	<b>Valid Specification Strings</b>
'Inverse-sinc Highpass'	See <code>fdesign.isinchnp</code> for a description of the specification string entries. <ul style="list-style-type: none"><li>• 'Fst,Fp,Ast,Ap' (default string)</li><li>• 'N,Fc,Ast,Ap'</li><li>• 'N,Fst,Fp'</li><li>• 'N,Fst,Ast,Ap'</li></ul>
'Lowpass'	See <code>fdesign.lowpass</code> for a description of the specification string entries. <ul style="list-style-type: none"><li>• 'Fp,Fst,Ap,Ast' (default string)</li><li>• 'N,F3dB'</li><li>• 'N,Fc'</li><li>• 'N,Fc,Ap,Ast'</li><li>• 'N,Fp,Ap,Ast'</li><li>• 'N,Fp,Fst'</li><li>• 'N,Fp,Fst,Ap'</li><li>• 'N,Fp,Fst,Ast'</li><li>• 'N,Fst,Ap,Ast'</li></ul>

Design String	Valid Specification Strings
'Nyquist'	<p>See <code>fdesign.nyquist</code> for a description of the specification string entries. For all Nyquist specifications, you must specify the <i>L</i>th band. This typically corresponds to the interpolation factor so that the nonzero samples of the upsampler output are preserved.</p> <ul style="list-style-type: none"> <li>• 'TW,Ast' (default string)</li> <li>• 'N'</li> <li>• 'N,Ast'</li> <li>• 'N,Ast'</li> </ul>
'Raised Cosine'	<p>See <code>fdesign.pulseshaping</code> for a description of the specification string entries.</p> <ul style="list-style-type: none"> <li>• 'Ast,Beta' (default string)</li> <li>• 'Nsym,Beta'</li> <li>• 'N,Beta'</li> </ul> <p>The specification string must be preceded by an integer-valued <code>SamplesPerSymbol</code>.</p>
'Square Root Raised Cosine'	<p>See <code>fdesign.pulseshaping</code> for a description of the specification string entries.</p> <ul style="list-style-type: none"> <li>• 'Ast,Beta' (default string)</li> <li>• 'Nsym,Beta'</li> <li>• 'N,Beta'</li> </ul> <p>The specification string must be preceded by an integer-valued <code>SamplesPerSymbol</code>.</p>

`D = fdesign.rsrc(L,M,RESPONSE,SPEC)` constructs object `D` and sets its `Specification` property to `SPEC`. Entries in the `SPEC` string represent various filter response features, such as the filter order, that govern

the filter design. Valid entries for SPEC depend on the design type of the specifications object.

When you add the SPEC input argument, you must also add the RESPONSE input argument.

`D = fdesign.rsrc(L,M,SPEC,specvalue1,specvalue2,...)`  
constructs an object D and sets its specifications at construction time.

`D = fdesign.rsrc(...,Fs)` provides the sampling frequency of the signal to be filtered. Fs must be specified as a scalar trailing the other numerical values provided. Fs is assumed to be in Hz as are all other frequency values provided.

`D = fdesign.rsrc(...,MAGUNITS)` specifies the units for any magnitude specification you provide in the input arguments. MAGUNITS can be one of

- 'linear' — specify the magnitude in linear units.
- 'dB' — specify the magnitude in dB (decibels).
- 'squared' — specify the magnitude in power units.

When you omit the MAGUNITS argument, fdesign assumes that all magnitudes are in decibels. Note that fdesign stores all magnitude specifications in decibels (converting to decibels when necessary) regardless of how you specify the magnitudes.

## Examples

Design a rational-factor sample-rate converter. Set the rational sample-rate change to 5/3. Use the default Nyquist design with a transition width of  $0.05\pi$  radians/sample and stopband attenuation of 40 dB. The *L*th band factor in the Nyquist design is equal to the interpolation factor.

```
d = fdesign.rsrc(5,3,'nyquist',5,.05,40);  
hm = design(d,'kaiserwin'); %design with Kaiser window
```

---

Design a rational-factor sample-rate converter. Set the rational sample-rate change to 5/3. Use a Nyquist design with the 'N,TW'

specification string. Set the order equal to 12 and the transition width to  $0.1\pi$  radians/sample. The  $L$ th band factor in the Nyquist design is equal to the interpolation factor.

```
d = fdesign.rsrc(5,3,'nyquist',5,'N,TW',12,0.1);
```

---

Design a rational-factor sample-rate converter. Assume the data are sampled at 10 kHz. Set the rational sample-rate change to  $3/2$ . Use a Nyquist design with the 'N,TW' specification string. Set the order equal to 12 and the transition width to 100 Hz. The  $L$ th band factor in the Nyquist design is equal to the interpolation factor.

```
d = fdesign.rsrc(3,2,'nyquist',3,'N,TW',12,100,1e4);  
hd = design(d,'equiripple');
```

**See Also**

[design](#) | [designmethods](#) | [fdesign.rsrc](#) | [fdesign.interpolator](#) | [setspecs](#) | [fdesign.arbmag](#) | [fdesign.arbmagnphase](#)

# fftcoeffs

---

**Purpose** Frequency-domain coefficients

**Syntax**  
`c = fftcoeffs(hd)`  
`c = fftcoeffs(ha)`

**Description** `c = fftcoeffs(hd)` return the frequency-domain coefficients used when filtering with the `dfilt.fftfilter` object. `c` contains the coefficients

`c = fftcoeffs(ha)` return the frequency-domain coefficients used when filtering with `adaptfilt` objects.

`fftcoeffs` applies to the following adaptive filter algorithms:

- `adaptfilt.fdaf`
- `adaptfilt.pbfdaf`
- `adaptfilt.pbudaf`
- `adaptfilt.ufdaf`

**Examples** This example demonstrates returning the FFT coefficients from the discrete-time filter `hd`.

```
b = [0.05 0.9 0.05];  
len = 50;  
hd = dfilt.fftfilter(b,len);  
c=fftcoeffs(hd);
```

Similarly, you can use `fftcoeffs` with the adaptive filters algorithms listed above. Start by constructing an adaptive filter `ha`.

```
d = 16; % Number of samples of delay.  
b = exp(1j*pi/4)*[-0.7 1]; % Numerator coefficients of channel.  
a = [1 -0.7]; % Denominator coefficients of channel.  
ntr= 1000; % Number of iterations.  
s = sign(randn(1,ntr+d)) +...  
1j*sign(randn(1,ntr+d)); % Baseband QPSK signal.  
n = 0.1*(randn(1,ntr+d) + 1j*randn(1,ntr+d)); % Noise signal.  
r = filter(b,a,s)+n; % Received signal.
```

```
x = r(1+d:ntr+d);           % Input signal (received signal).
s = s(1:ntr);               % Desired signal (delayed QPSK signal).
del = 1;                    % Initial FFT input powers.
mu = 0.1;                   % Step size.
lam = 0.9;                  % Averaging factor.
blocksize = 8;              % Block size.
ha = adaptfilt.pbufdaf(32,mu,1,del,lam,blocksize);
```

Here are the coefficients before you filter a signal.

```
c=fftcoeffs(ha);
% all coefficients are zero
NumNonzero =nnz(c);
```

Filtering a signal *y* produces complex nonzero coefficients that you use `fftcoeffs` to see.

```
[y,e] = filter(ha,x,s);
c=fftcoeffs(ha);
```

## See Also

```
adaptfilt.fdaf | adaptfilt.pbfdaf | adaptfilt.pbufdaf |
adaptfilt.ufdaf
```

**Purpose** Filter data with filter object

**Syntax** **Fixed-Point Filter Syntaxes**

```
y = filter(hd,x)
y = filter(hd,x,dim)
```

**Adaptive Filter Syntax**

```
y = filter(ha,x,d)
[y,e] = filter(ha,x,d)
```

**Multirate Filter Syntax**

```
y = filter(hm,x)
y = filter(hm,x,dim)
```

**Description** This reference page contains three sections that describe the syntaxes for the filter objects:

- “Fixed-Point Filter Syntaxes” on page 7-640
- “Adaptive Filter Syntaxes” on page 7-641
- “Multirate Filter Syntaxes” on page 7-642

**Fixed-Point Filter Syntaxes**

`y = filter(hd,x)` filters a vector of real or complex input data `x` through a fixed-point filter `hd`, producing filtered output data `y`. The vectors `x` and `y` have the same length. `filter` stores the final conditions for the filter in the `States` property of `hd` — `hd.States`.

When you set the property `PersistentMemory` to `false` (the default setting), the initial conditions for the filter are set to zero before filtering starts. To use nonzero initial conditions for `hd`, set `PersistentMemory` to `true`. Then set `hd.States` to a vector of `nstates(hd)` elements, one element for each state to set. If you specify a scalar for `hd.States`, `filter` expands the scalar to a vector of the proper length for the states. All elements of the expanded vector have the value of the scalar.

If `x` is a matrix, `y = filter(hd,x)` filters along each column of `x` to produce a matrix `y` of independent channels. If `x` is a multidimensional

array, `y = filter(hd,x)` filters `x` along the first nonsingleton dimension of `x`.

To use nonzero initial conditions when you are filtering a matrix `x`, set the filter states to a matrix of initial condition values. Set the initial conditions by setting the `States` property for the filter (`hd.states`) to a matrix of `nstates(hd)` rows and `size(x,2)` columns.

`y = filter(hd,x,dim)` applies the filter `hd` to the input data located along the specific dimension of `x` specified by `dim`.

When you are filtering multichannel data, `dim` lets you specify which dimension of the input matrix to filter along — whether a row represents a channel or a column represents a channel. When you provide the `dim` input argument, the filter operates along the dimension specified by `dim`. When your input data `x` is a vector or matrix and `dim` is 1, each column of `x` is treated as a one input channel. When `dim` is 2, the filter treats each row of the input `x` as a channel.

To filter multichannel data in a loop environment, you must use the `dim` input argument to set the proper processing dimension.

You specify the initial conditions for each channel individually, when needed, by setting `hm.states` to a matrix of `nstates(hd)` rows (one row containing the states for one channel of input data) and `size(x,2)` columns (one column containing the filter states for each channel).

### Adaptive Filter Syntaxes

`y = filter(ha,x,d)` filters a vector of real or complex input data `x` through an adaptive filter object `ha`, producing the estimated desired response data `y` from the process of adapting the filter. The vectors `x` and `y` have the same length. Use `d` for the desired signal. Note that `d` and `x` must be the same length signal chains.

`[y,e] = filter(ha,x,d)` produces the estimated desired response data `y` and the prediction error `e` (refer to previous syntax for more information).

## Multirate Filter Syntaxes

`y = filter(hd,x)` filters a vector of real or complex input data `x` through a fixed-point filter `hd`, producing filtered output data `y`. The vectors `x` and `y` have the same length. `filter` stores the final conditions for the filter in the `States` property of `hd` — `hd.states`.


`y = filter(hm,x,dim)` applies the filter `hd` to the input data located along the specific dimension of `x` specified by `dim`.

When you are filtering multichannel data, `dim` lets you specify which dimension of the input matrix to filter along — whether a row represents a channel or a column represents a channel. When you provide the `dim` input argument, the filter operates along the dimension specified by `dim`. When your input data `x` is a vector or matrix and `dim` is 1, each column of `x` is treated as a one input channel. When `dim` is 2, the filter treats each row of the input `x` as a channel.

To filter multichannel data in a loop environment, you must use the `dim` input argument to set the processing dimension.

You specify the initial conditions for each channel individually, when needed, by setting `hm.states` to a matrix of `nstates(hm)` rows (one row containing the states for one channel of input data) and `size(x,2)` columns (one column containing the filter states for each channel).

The number of data samples in your input data set `x` does not need to be a multiple of the rate change factor `r` for the object. When the rate change factor is not an even divisor of the number of input samples `x`, `filter` processes the samples as shown in the following figure, where the rate change factor is 3 and the number of input samples is 23. Decimators always take the first input sample to generate the first output sample. After that, the next output sample comes after each `r` number of input samples.



## Examples

Filter a signal using a filter with various initial conditions (IC) or no initial conditions.

```
x = randn(100,1); % Original signal.
b = fir1(50,.4); % 50th-order linear-phase FIR filter.
hd = dfilt.dffir(b); % Direct-form FIR implementation.
```

```
% Do not set specific initial conditions.
```


```
y1 = filter(hd,x); % 'PersistentMemory'='false' (default).
zf = hd.states; % Final conditions.
```

Now use nonzero initial conditions by setting ICs after before you filter.

```
hd.persistentmemory = true;
hd.states = 1; % Uses scalar expansion.
y2 = filter(hd,x);
stem([y1 y2]) % Different sequences at beginning.
```

Looking at the stem plot shows that the sequences are different at the beginning of the filter process.

# filter



Here is one way to use `filter` with streaming data.


```
reset(hd);           % Clear filter history.  
y3 = filter(hd,x);  % Filter entire signal in one block.
```

As an experiment, repeat the process, filtering the data as sections, rather than in streaming form.

```
reset(hd);           % Clear filter history.  
yloop = zeros(20,5); % Preallocate output array.  
xblock = reshape(x,[20 5]);  
for i=1:5,  
    yloop(:,i) = filter(hd,xblock(:,i));  
end
```

Use a stem plot to see the comparison between streaming and block-by-block filtering.

```
stem([y3 yloop(:)]);
```



Filtering the signal section-by-section is equivalent to filtering the entire signal at once.

To show the similarity between filtering with discrete-time and with multirate filters, this example demonstrates multirate filtering.

```
Fs = 44.1e3; % Original sampling frequency: 44.1kHz.
n = [0:10239].'; % 10240 samples, 0.232 second long signal.
x = sin(2*pi*1e3/Fs*n); % Original signal, sinusoid at 1kHz.
m = 2; % Decimation factor.
hm = mfilter.firdecim(m); % Use the default filter.
```

First, filter without setting initial conditions.

```
y1 = filter(hm,x);      % PersistentMemory is false (default).  
zf = hm.states;        % Final conditions.
```

This time, set nonzero initial conditions before filtering the data.

```
hm.persistentmemory = true;  
hm.states = 1;         % Uses scalar expansion to set ICs.  
y2 = filter(hm,x);  
stem([y1(1:60) y2(1:60)]) % Show the filtering results.
```

Note the different sequences at the start of filtering.

Finally, try filtering streaming data.

```
reset(hm);             % Clear the filter history.  
y3 = filter(hm,x);     % Filter entire signal in one block.
```

As with the discrete-time filter, filtering the signal section by section is equivalent to filtering the entire signal at once.

```
reset(hm);             % Clear filter history again.  
yloop = zeros(1024,5); % Preallocate output array.  
xblock = reshape(x,[2048 5]);  
for i=1:5,  
    yloop(:,i) = filter(hm,xblock(:,i));  
end  
stem([y3 yloop(:)]);
```

## Algorithms

### Quantized Filters

The `filter` command implements fixed- or floating-point arithmetic on the quantized filter structure you specify.

The algorithm applied by `filter` when you use a discrete-time filter object on an input signal depends on the response you chose for the filter, such as lowpass or Nyquist or bandstop. To learn more about each filter algorithm, refer to the literature reference provided on the appropriate discrete-time filter reference page.

---

**Note** `dfilt/filter` does not normalize the filter coefficients automatically. Function `filter` supplied by MATLAB does normalize the coefficients.

---

### Adaptive Filters

The algorithm used by `filter` when you apply an adaptive filter object to a signal depends on the algorithm you chose for your adaptive filter. To learn more about each adaptive filter algorithm, refer to the literature reference provided on the appropriate `adaptfilt.algorithm` reference page.

### Multirate Filters

The algorithm applied by `filter` when you apply a multirate filter objects to signals depends on the algorithm you chose for the filter — the form of the multirate filter, such as decimator or interpolator. To learn more about each filter algorithm, refer to the literature reference provided on the appropriate multirate filter reference page.

### References

[1] Oppenheim, A.V., and R.W. Schaffer, *Discrete-Time Signal Processing*, Prentice-Hall, 1989.

### See Also

`adaptfilt` | `impz` | `mfilt` | `nstates` | `dfilt`

# filterbuilder

---

**Purpose** GUI-based filter design

**Syntax** `filterbuilder(h)`  
`filterbuilder('response')`

**Description** `filterbuilder` starts a GUI-based tool for building filters. It relies on the `fdesign` object-object oriented filter design paradigm, and is intended to reduce development time during the filter design process. `filterbuilder` uses a specification-centered approach to find the best algorithm for the desired response.

---

**Note** You must have the Signal Processing Toolbox installed to use `fdesign` and `filterbuilder`. Some of the features described below may be unavailable if your installation does not additionally include the DSP System Toolbox. You can verify the presence of both toolboxes by typing `ver` at the command prompt.

---

The `filterbuilder` GUI contains many features not available in `FDATool`. For more information on how to use `filterbuilder`, see “Filterbuilder Design Process”.

To use `filterbuilder`, enter `filterbuilder` at the MATLAB command line using one of three approaches:

- Simply enter `filterbuilder`. MATLAB opens a dialog for you to select a filter response type. After you select a filter response type, `filterbuilder` launches the appropriate filter design dialog box.
- Enter `filterbuilder(h)`, where `h` is an existing filter object. For example, if `h` is a bandpass filter, `filterbuilder(h)` opens the bandpass filter design dialog box. (The `h` object must have been created using `filterbuilder` or must be a `dfilt`, `mfilt`, or filter System object created using `fdesign`.)

**Note** You must have the DSP System Toolbox software to create and import filter System objects.

- Enter `filterbuilder('response')`, replacing *response* with a response string from the following table. MATLAB opens a filter design dialog that corresponds to the response string.

**Note** You must have the DSP System Toolbox software to implement a number of the filter designs listed in the following table. If you only have the Signal Processing Toolbox software, you can design a limited set of the following filter-response types.

Response String	Description of Resulting Filter Design	Filter Object
arbgrpdelay	Arbitrary group delay filter design	<code>fdesign.arbgrpdelay</code>
arbmag	Arbitrary magnitude filter design	<code>fdesign.arbmag</code>
arbmagnphase	Arbitrary response filter (magnitude and phase)	<code>fdesign.arbmagnphase</code>
audioweighting	Audio weighting filter	<code>fdesign.audioweighting</code>
bandpass or bp	Bandpass filter	<code>fdesign.bandpass</code>
bandstop or bs	Bandstop filter	<code>fdesign.bandstop</code>
cic	CIC filter	<code>fdesign.decimator(M,'cic',... or</code>
ciccomp	CIC compensator	<code>fdesign.ciccomp r(L,'cic',</code>
comb	Comb filter	<code>fdesign.comb</code>

and  
`fdesign.interpolator`

# filterbuilder

---

Response String	Description of Resulting Filter Design	Filter Object
diff	Differentiator filter	fdesign.differentiator
fracdelay	Fractional delay filter	fdesign.fracdelay
halfband or hb	Halfband filter	fdesign.halfband
highpass or hp	Highpass filter	fdesign.highpass
hilb	Hilbert filter	fdesign.hilbert
isinc, isinclp, or isinchp	Inverse sinc lowpass or highpass filter	fdesign.isinclp and fdesign.isinchp
lowpass or lp	Lowpass filter (default)	fdesign.lowpass
notch	Notch filter	fdesign.notch
nyquist	Nyquist filter	fdesign.nyquist
octave	Octave filter	fdesign.octave
parameq	Parametric equalizer filter	fdesign.parameq
peak	Peak filter	fdesign.peak
pulseshaping	Pulse-shaping filter	fdesign.pulseshaping

---


**Note** Because they do not change the filter structure, the magnitude specifications and design method are tunable when using `filterbuilder`.

---

## Filterbuilder Design Panes

### Main Design Pane

The main pane of filterbuilder varies depending on the filter response type, but the basic structure is the same. The following figure shows the basic layout of the dialog box.



As you choose the response for the filter, the available options and design parameters displayed in the dialog box change. This display allows you to focus only on parameters that make sense in the context of your filter design.

Every filter design dialog box includes the options displayed at the top of the dialog box, shown in the following figure.



- **Save variable as** — When you click **Apply** to apply your changes or **OK** to close this dialog box, `filterbuilder` saves the current filter to your MATLAB workspace as a filter object with the name you enter.
- **View Filter Response** — Displays the magnitude response for the current filter specifications and design method by opening the Filter Visualization Tool (`fvttool`).

---


**Note** The `filterbuilder` dialog box includes an **Apply** option. Each time you click **Apply**, `filterbuilder` writes the modified filter to your MATLAB workspace. This modified filter has the variable name you assign in **Save variable as**. To apply changes without overwriting the variable in your workspace, change the variable name in **Save variable as** before you click **Apply**.

---

There are three tabs in the Filterbuilder dialog box, containing three panes: **Main**, **Data Types**, and **Code Generation**. The first pane changes according to the filter being designed. The last two panes are the same for all filters. These panes are discussed in the following sections.

## Data Types Pane

The second tab in the Filterbuilder dialog box is shown in the following figure.



The **Arithmetic** drop down box allows the choice of **Double precision**, **Single precision**, or **Fixed point**. Some of these options may be unavailable depending on the filter parameters. The following table describes these options.

<b>Arithmetic List Entry</b>	<b>Effect on the Filter</b>
Double precision	All filtering operations and coefficients use double-precision, floating-point representations and math. When you use filterbuilder to

Arithmetic List Entry	Effect on the Filter
	create a filter, double precision is the default value for the Arithmetic property.
Single precision	All filtering operations and coefficients use single-precision floating-point representations and math.
Fixed point	This string applies selected default values, typically used on many digital processors, for the properties in the fixed-point filter. These properties include coefficient word lengths, fraction lengths, and various operating modes. This setting allows signed fixed data types only. Fixed-point filter design with <code>filterbuilder</code> is available only when you install Fixed-Point Toolbox software along with DSP System Toolbox software.

The following figure shows the **Data Types** pane after you select **Fixed point** for **Arithmetic** and set **Filter internals** to **Specify precision**. This figure shows the **Data Types** pane for the case where the **Use a System object to implement filter** check box is not selected in the **Main** pane.

 Bandpass Design

Bandpass Design

Design a bandpass filter.

Save variable as:

Main | Data Types | Code Generation

Arithmetic:

Fixed-point data types

	Mode	Signed	Word length	Fr
Input signal	Binary point scaling	yes	<input type="text" value="16"/>	<input type="text" value="15"/>
Coefficients	<input type="text" value="Specify word length"/>	<input checked="" type="checkbox"/>	<input type="text" value="16"/>	
Filter internals	<input type="text" value="Specify precision"/>			
Product	Binary point scaling	yes	<input type="text" value="32"/>	<input type="text" value="29"/>
Accum	Binary point scaling	yes	<input type="text" value="40"/>	<input type="text" value="29"/>
Output	Binary point scaling	yes	<input type="text" value="16"/>	<input type="text" value="15"/>

Fixed-point operational parameters

Rounding mode:  Overflow mode:

## Input signal

Specify the format the filter applies to data to be filtered. For all cases, `filterbuilder` implements filters that use binary point scaling and signed input. You set the word length and fraction length as needed.

## Coefficients

Choose how you specify the word length and the fraction length of the filter numerator and denominator coefficients:

- `Specify word length` enables you to enter the word length of the coefficients in bits. In this mode, `filterbuilder` automatically sets the fraction length of the coefficients to the binary-point only scaling that provides the best possible precision for the value and word length of the coefficients.
- `Binary point scaling` enables you to enter the word length and the fraction length of the coefficients in bits. If applicable, enter separate fraction lengths for the numerator and denominator coefficients.
- The filter coefficients do not obey the **Rounding mode** and **Overflow mode** parameters that are available when you select `Specify precision` from the Filter internals list. Coefficients are always saturated and rounded to `Nearest`.

## Section Input

Choose how you specify the word length and the fraction length of the fixed-point data type going into each section of an SOS filter. This parameter is visible only when the selected filter structure is IIR and SOS.

- `Binary point scaling` enables you to enter the word and fraction lengths of the section input in bits.
- `Specify word length` enables you to enter the word lengths in bits.

## Section Output

Choose how you specify the word length and the fraction length of the fixed-point data type coming out of each section of an SOS

filter. This parameter is visible only when the selected filter structure is IIR and SOS.

- **Binary point scaling** enables you to enter the word and fraction lengths of the section output in bits.
- **Specify word length** enables you to enter the output word lengths in bits.

## State

Contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions. Use this parameter to specify how to designate the state word and fraction lengths. This parameter is not visible for direct form and direct form I filter structures because `filterbuilder` deduces the state directly from the input format. States always use signed representation:

- **Binary point scaling** enables you to enter the word length and the fraction length of the accumulator in bits.
- **Specify precision** enables you to enter the word length and fraction length in bits (if available).

## Product

Determines how the filter handles the output of product operations. Choose from the following options:

- **Full precision** — Maintain full precision in the result.
- **Keep LSB** — Keep the least significant bit in the result when you need to shorten the data words.
- **Specify Precision** — Enables you to set the precision (the fraction length) used by the output from the multiplies.

## Filter internals

Specify how the fixed-point filter performs arithmetic operations within the filter. The affected filter portions are filter products, sums, states, and output. Select one of these options:

- **Full precision** — Specifies that the filter maintains full precision in all calculations for products, output, and in the accumulator.
- **Specify precision** — Set the word and fraction lengths applied to the results of product operations, the filter output, and the accumulator. Selecting this option enables the word and fraction length controls.

## **Signed**

Selecting this option directs the filter to use signed representations for the filter coefficients.

## **Word length**

Sets the word length for the associated filter parameter in bits.

## **Fraction length**

Sets the fraction length for the associate filter parameter in bits.

## **Accum**

Use this parameter to specify how you would like to designate the accumulator word and fraction lengths.

Determines how the accumulator outputs stored values. Choose from the following options:

- **Full precision** — Maintain full precision in the accumulator.
- **Keep MSB** — Keep the most significant bit in the accumulator.
- **Keep LSB** — Keep the least significant bit in the accumulator when you need to shorten the data words.
- **Specify Precision** — Enables you to set the precision (the fraction length) used by the accumulator.

## **Output**

Sets the mode the filter uses to scale the output data after filtering. You have the following choices:

- **Avoid Overflow** — Set the output data fraction length to avoid causing the data to overflow. **Avoid overflow** is considered

the conservative setting because it is independent of the input data values and range.

- **Best Precision** — Set the output data fraction length to maximize the precision in the output data.
- **Specify Precision** — Set the fraction length used by the filtered data.

## **Fixed-point operational parameters**

Parameters in this group control how the filter rounds fixed-point values and how it treats values that overflow.

### **Rounding mode**

Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths).

- **ceil** - Round toward positive infinity.
- **convergent** - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.
- **zero/fix** - Round toward zero.
- **floor** - Round toward negative infinity.
- **nearest** - Round toward nearest. Ties round toward positive infinity.
- **round** - Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.

The choice you make affects everything except coefficient values and input data which always round. In most cases, products do not overflow—they maintain full precision.

### **Overflow mode**

Sets the mode the filter uses to respond to overflow conditions in fixed-point arithmetic. Choose from the following options:

- **Saturate** — Limit the output to the largest positive or negative representable value.
- **Wrap** — Set overflowing values to the nearest representable value using modular arithmetic.

The choice you make affects everything except coefficient values and input data which always round. In most cases, products do not overflow—they maintain full precision.

### **Cast before sum**

Specifies whether to cast numeric data to the appropriate accumulator format before performing sum operations. Selecting **Cast before sum** ensures that the results of the affected sum operations match most closely the results found on most digital signal processors. Performing the cast operation before the summation adds one or two additional quantization operations that can add error sources to your filter results.


If you clear **Cast before sum**, the filter prevents the addends from being cast to the sum format before the addition operation. Choose this setting to get the most accurate results from summations without considering the hardware your filter might use. The input format referenced by **Cast before sum** depends on the filter structure you are using.

The effect of clearing or selecting **Cast before sum** is as follows:

- **Cleared** — Configures filter summation operations to retain the addends in the format carried from the previous operation.
- **Selected** — Configures filter summation operations to convert the input format of the addends to match the summation output format before performing the summation operation. Usually, selecting **Cast before sum** generates results from the summation that more closely match those found from digital signal processors.

## Code Generation Pane

The code generation pane contains options for various implementations of the completed filter design. Depending on your installation, you can generate MATLAB, VHDL, and Verilog code from the designed filter. You can also choose to create or update a Simulink model from the designed filter. The following section explains these options.



## HDL

For more information on this option, see “Opening the Filter Design HDL Coder™ GUI From the filterbuilder GUI”.

## MATLAB

### Generate MATLAB code based on filter specifications

- **Generate function that returns your filter as an output**

Selecting this option generates a function that designs either a DFILT/MFILT object or a system object (depending on whether you have selected the **Use a System object to implement the filter** check box) using `fdesign`. The function call returns a filter object.

- **Generate function that filters your data**

Selecting this option generates a function that takes data as input, and outputs data filtered with the designed filter.


Clicking on the **Generate MATLAB code** button, brings up a Save File dialog. Specify the file name and location, and save. The filter is now contained in an editable file.

## Simulink Model

### Generate Simulink blocks and subsystems from your designed filters

When the **Use a System object to implement filter** check box is selected in the **Main** pane, you are able to generate Simulink models as long as the **Arithmetic** is not set to **Fixed point** in the **Data Types** pane. If the **Arithmetic** is set to **Fixed point**, the **Generate Model** button in the **Simulink model** panel will be disabled.

Clicking on the **Generate Model** button brings up the **Export to Simulink** dialog box, as shown in the following figure.



You can set the following parameters in this dialog box:


- **Block Name** — The name for the new subsystem block, set to **Filter** by default.
- **Destination** — **Current** saves the generated model to the current Simulink model; **New** creates a new model to contain the generated block; **User Defined** creates a new model or subsystem to the user-specified location enumerated in the **User Defined** text box.
- **Overwrite generated 'Filter' block** — When this check box is selected, DSP System Toolbox software overwrites an existing block with the name specified in **Block Name**; when cleared, creates a new block with the same name.
- **Build model using basic elements** — When this check box is selected, DSP System Toolbox software builds the model using only basic blocks.
- **Optimize for zero gains** — When this check box is selected, DSP System Toolbox software removes all zero gain blocks from the model.

- **Optimize for unity gains** — When this check box is selected, DSP System Toolbox software replaces all unity gains with direct connections.
  - **Optimize for negative gains** — When this check box is selected, DSP System Toolbox software removes all negative unity gain blocks, and changes sign at the nearest summation block.
  - **Optimize delay chains** — When this check box is selected, DSP System Toolbox software replaces delay chains made up of  $n$  unit delays with a single delay by  $n$ .
  - **Optimize for unity scale values** — When this check box is selected, DSP System Toolbox software removes all scale value multiplications by 1 from the filter structure.
  - **Input processing** — Specify how the generated filter block or subsystem block processes the input. Depending on the type of filter you are designing, one or both of the following options may be available:
    - **Columns as channels (frame based)** — When you select this option, the block treats each column of the input as a separate channel.
    - **Elements as channels (sample based)** — When you select this option, the block treats each element of the input as a separate channel.
- For more information about sample- and frame-based processing, see “Sample- and Frame-Based Concepts”.
- **Realize Model** — DSP System Toolbox software builds the model with the set parameters.

## Filter Responses

Select your filter response from the **filterbuilder Response Selection** main menu.

If you have the DSP System Toolbox software, the following **Response Selection** menu appears.



Select your desired filter response from the menu and design your filter. The following sections describe the options available for each response type.

## Arbitrary Response Filter Design Dialog Box – Main Pane

Arbitrary Response Design

Arbitrary Response Design

Design an arbitrary response filter. The constraint can be on the magnitude only, or on the magnitude and the phase.

Save variable as:

Main | Data Types | Code Generation

Filter specifications

Impulse response:

Order mode:

Order:

Filter type:

Response specifications

Number of bands:

Specify response as:

Frequency units:

Band properties

	Frequencies	Amplitudes
1	<code>linspace(0, 1, 30)</code>	<code>[ones(1, 7) zeros(1,8) ones(1,8) ze</code>

Algorithm

Design method:

▸ Design options

## Filter specifications

Parameters in this group enable you to specify your filter format, such as the impulse response and the filter order.

### Impulse response

This dialog only applies if you have the DSP System Toolbox software. Select either **FIR** or **IIR** from the drop down list, where **FIR** is the default impulse response. When you choose an impulse response, the design methods and structures you can use to implement your filter change accordingly. Arbitrary group delay designs are only available if **Impulse response** is **IIR**. Without the DSP System Toolbox, the only available arbitrary response filter design is **FIR**.

### Order mode

This dialog only applies if you have the DSP System Toolbox software. Choose **Minimum** or **Specify**. Choosing **Specify** enables the **Order** dialog.

### Order

This dialog only applies when **Order mode** is **Specify**. For an **FIR** design, specify the filter order. For an **IIR** design, you can specify an equal order for the numerator and denominator, or you can specify different numerator and denominator orders. The default is equal orders. To specify a different denominator order, check the **Denominator order** box. Because the Signal Processing Toolbox only supports **FIR** arbitrary-magnitude filters, you do not have the option to specify a denominator order.

### Denominator order

Select the check box and enter the denominator order. This option is enabled only if **IIR** is selected for **Impulse response**.

### Filter type

This dialog only applies if you have the DSP System Toolbox software and is only available for **FIR** filters. Select **Single-rate**, **Decimator**, **Interpolator**, or **Sample-rate converter**. Your choice determines the type of filter as well as the design methods

and structures that are available to implement your filter. By default, filterbuilder specifies single-rate filters.

- Selecting Decimator or Interpolator activates the **Decimation Factor** or the **Interpolation Factor** options respectively.
- Selecting Sample-rate converter activates both factors.

When you design either a decimator or interpolator, the resulting filter is a bandpass filter that either decimates or interpolates your input signal.

### **Decimation Factor**

Enter the decimation factor. This option is enabled only if the **Filter type** is set to Decimator or Sample-rate converter. The default factor value is 2 for Decimator and 3 for Sample-rate converter.

### **Interpolation Factor**

Enter the decimation factor. This option is enabled only if the **Filter type** is set to Interpolator or Sample-rate converter. The default factor value is 2.

## **Response Specification**

### **Number of Bands**

Select the number of bands in the filter. Multiband design is available for both FIR and IIR filters.

### **Specify response as:**

Specify the response as Amplitudes, Magnitudes and phase, Frequency response, or Group delay. Amplitudes is the only option if you do not have the DSP System Toolbox software. Group delay is only available for IIR designs.

### **Frequency units**

Specify frequency units as either Normalized, Hz, kHz, MHz, or GHz.

### Input Fs

Enter the input sampling frequency in the units specified in the **Frequency units** drop-down box. This option is enabled when **Frequency units** is set to an option in hertz.

### Band Properties

These properties are modified automatically depending on the response chosen in the **Specify response as** drop-down box. Two or three columns are presented for input. The first column is always Frequencies. The other columns are either Amplitudes, Magnitudes, Phases, or Frequency Response. Enter the corresponding vectors of values for each column.

- **Frequencies and Amplitudes** — These columns are presented for input if you select Amplitudes in the **Specify response as** drop-down box.
- **Frequencies, Magnitudes, and Phases** — These columns are presented for input if the response chosen in the **Specify response as** drop-down box is Magnitudes and phases.
- **Frequencies and Frequency response** — These columns are presented for input if the response chosen in the **Specify response as** drop-down box is Frequency response.

### Algorithm

The options for each design are specific for each design method. In the arbitrary response design, the available options also depend on the **Response specifications**. This section does not present all of the available options for all designs and design methods.

### Design Method

Select the design method for the filter. Different methods are enabled depending on the defining parameters entered in the previous sections.

## Design Options

- **Window** — Valid when the **Design method** is Frequency Sampling. Replace the square brackets with the name of a window function or function handle. For example, 'hamming' or @hamming. If the window function takes parameters other than the length, use a cell array. For example, {'kaiser',3.5} or {@chebwin,60}.
- **Density factor** — Valid when the **Design method** is equiripple. Density factor controls the density of the frequency grid over which the design method optimization evaluates your filter response function. The number of equally spaced points in the grid is the value you enter for **Density factor** times (filter order + 1).

Increasing the value creates a filter that more closely approximates an ideal equiripple filter but increases the time required to design the filter. The default value of 16 represents a reasonable trade between the accurate approximation to the ideal filter and the time to design the filter.

The default changes to 20 for an IIR arbitrary group delay design.

- **Phase constraint** — Valid when the **Design method** is equiripple, you have the DSP System Toolbox installed, and **Specify response as** is set to Amplitudes. Choose one of Linear, Minimum, or Maximum.
- **Weights** — Uses the weights in **Weights** to weight the error for a single-band design. If you have multiple frequency bands, the **Weights** design option changes to **B1 Weights**, **B2 Weights** to designate the separate bands. Use **Bi Weights** to specify weights for the i-th band. The **Bi Weights** design option is only available when you specify the i-th band as an unconstrained.
- **Bi forced frequency point** — This option is only available in a multi-band constrained equiripple design when **Specify response as** is Amplitudes. **Bi forced frequency point** is

the frequency point in the  $i$ -th band at which the response is forced to be zero. The index  $i$  corresponds to the frequency bands in **Band properties**. For example, if you specify two bands in **Band properties**, you have **B1 forced frequency point** and **B2 forced frequency point**.

- **Norm** — Valid only for IIR arbitrary group delay designs. **Norm** is the norm used in the optimization. The default value is 128, which essentially equals the L-infinity norm. The norm must be even.
- **Max pole radius** — Valid only for IIR arbitrary group delay designs. Constrains the maximum pole radius. The default is 0.999999. Reducing the **Max pole radius** can produce a transfer function more resistant to quantization.
- **Init norm** — Valid only for IIR arbitrary group delay designs. The initial norm used in the optimization. The default initial norm is 2.
- **Init numerator** — Specifies an initial estimate of the filter numerator coefficients.
- **Init denominator** — Specifies an initial estimate of the filter denominator coefficients. This may be useful in difficult optimization problems. In allpass filters, you only have to specify either the denominator or numerator coefficients. If you specify the denominator coefficients, you can obtain the numerator coefficients.

## Filter implementation

### Structure

Select the structure for the filter. The available filter structures depend on the parameters you select for your filter.

### Use a System object to implement filter

Selecting this check box gives you the choice of using a system object to implement the filter. By default the check box is turned

off. When the current design method or structure is not supported by a system object filter, then this check box is disabled.

## Audio Weighting Filter Design Dialog Box – Main Pane

The screenshot shows the 'Audio Weighting Design' dialog box with the 'Main' tab selected. The dialog has a title bar with a close button (X) and a standard Windows-style icon. The main content area is titled 'Audio Weighting Design' and contains the instruction 'Design an audio weighting filter.' Below this, there is a 'Save variable as:' field containing the text 'Haw' and a 'View Filter Response' button. The dialog is divided into three tabs: 'Main', 'Data Types', and 'Code Generation'. The 'Main' tab is active and contains three sections: 'Filter specifications', 'Algorithm', and 'Filter implementation'. In the 'Filter specifications' section, 'Weighting type' is set to 'A', 'Class' is '1', 'Impulse response' is 'IIR', 'Frequency units' is 'Hz', and 'Input Fs' is '48000'. The 'Algorithm' section has 'Design method' set to 'ANSI S1.42' and a checked checkbox for 'Scale SOS filter coefficients to reduce chance of overflow'. The 'Filter implementation' section has 'Structure' set to 'Direct-form II SOS' and an unchecked checkbox for 'Use a System object to implement filter'. At the bottom of the dialog are four buttons: 'OK', 'Cancel', 'Help', and 'Apply'.

Audio Weighting Design

Audio Weighting Design

Design an audio weighting filter.

Save variable as: Haw View Filter Response

Main Data Types Code Generation

Filter specifications

Weighting type: A Class: 1

Impulse response: IIR

Frequency units: Hz Input Fs: 48000

Algorithm

Design method: ANSI S1.42

Scale SOS filter coefficients to reduce chance of overflow

Filter implementation

Structure: Direct-form II SOS

Use a System object to implement filter

OK Cancel Help Apply

## Filter specifications

- **Weighting type** — The weighting type defines the frequency response of the filter. The valid weighting types are: A, C, C-message, ITU-T 0.41, and ITU-R 468–4 weighting. See `fdesign.audioweighting` for definitions of the weighting types.
- **Class** — Filter class is only applicable for A weighting and C weighting filters. The filter class describes the frequency-dependent tolerances specified in the relevant standards. There are two possible class values: 1 and 2. Class 1 weighting filters have stricter tolerances than class 2 filters. The filter class value does not affect the design. The class value is only used to provide a specification mask in `fvtool` for the analysis of the filter design.
- **Impulse response** — Impulse response type as one of IIR or FIR. For A, C, C-message, and ITU-R 468–4 filter, IIR is the only option. For a ITU-T 0.41 weighting filter, FIR is the only option.
- **Frequency units** — Choose Hz, kHz, MHz, or GHz. Normalized frequency designs are not supported for audio weighting filters.
- **Input Fs** — The sampling frequency in **Frequency units**. For example, if **Frequency units** is set to kHz, setting **Input Fs** to 40 is equivalent to a 40 kHz sampling frequency.

## Algorithm

- **Design method** — Valid design methods depend on the weighting type. For type A and C weighting filters, the only valid design type is ANSI S1.42. This is an IIR design method that follows ANSI standard S1.42–2001. For a C message filter, the only valid design method is Bell 41009, which is an IIR design method following the Bell System Technical Reference PUB 41009. For a ITU-R 468–4 weighting filter, you can design an IIR or FIR filter. If you choose an IIR design, the design method is IIR least p-norm. If you choose an FIR design, the design method choices are: Equirriple or Frequency Sampling. For an ITU-T 0.41 weighting filter, the available FIR design methods are equirriple or Frequency Sampling

- **Scale SOS filter coefficients to reduce chance of overflow** — Selecting this parameter directs the design to scale the filter coefficients to reduce the chances that the inputs or calculations in the filter overflow and exceed the representable range of the filter. Clearing this option removes the scaling. This parameter applies only to IIR filters.

## **Filter implementation**

- **Structure** — For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter. For audio weighting IIR filter designs, you can choose direct form I or II biquad (SOS). You can also choose to implement these structures in transposed form.

For FIR designs, you can choose direct form, direct-form transposed, direct-form symmetric, direct-form asymmetric structures, or an overlap and add structure.

- **Use a System object to implement filter** — Selecting this check box gives you the choice of using a system object to implement the filter. By default the check box is turned off. When the current design method or structure is not supported by a system object filter, then this check box is disabled.

## Bandpass Filter Design Dialog Box – Main Pane

Bandpass Design

Bandpass Design

Design a bandpass filter.

Save variable as:  View Filter Respo...

Main Data Types Code Generation

Filter specifications

Impulse response:

Order mode:

Filter type:

Frequency specifications

Frequency units:

Fstop1:  Fpass1:

Fpass2:  Fstop2:

Magnitude specifications

Magnitude units:

Astop1:  Apass:

Astop2:

Algorithm

Design method:

▼ Design options

Density factor:

Phase constraint:

Minimum order:

Uniform grid

Filter implementation

## Filter specifications

Parameters in this group enable you to specify your filter format, such as the impulse response and the filter order.

### Impulse response

Select FIR or IIR from the drop-down list, where FIR is the default impulse response. When you choose an impulse response, the design methods and structures you can use to implement your filter change accordingly.

---

**Note** The design methods and structures for FIR filters are not the same as the methods and structures for IIR filters.

---

### Order mode

Select Minimum (the default) or Specify from the drop-down box. Selecting Specify enables the **Order** option so you can enter the filter order.

If you have the DSP System Toolbox software installed, you can specify IIR filters with different numerator and denominator orders. The default is equal orders. To specify a different denominator order, check the **Denominator order** box.

**Filter type** — This dialog only applies if you have the DSP System Toolbox software.

Select Single-rate, Decimator, Interpolator, or Sample-rate converter. Your choice determines the type of filter as well as the design methods and structures that are available to implement your filter. By default, filterbuilder specifies single-rate filters.

- Selecting Decimator or Interpolator activates the **Decimation Factor** or the **Interpolation Factor** options respectively.
- Selecting Sample-rate converter activates both factors.

## Order

Enter the filter order. This option is enabled only if you select Specify for **Order mode**.

## Decimation Factor


Enter the decimation factor. This option is enabled only if the **Filter type** is set to Decimator or Sample-rate converter. The default factor value is 2.

## Interpolation Factor

Enter the decimation factor. This option is enabled only if the **Filter type** is set to Interpolator or Sample-rate converter. The default factor value is 2.

## Frequency specifications

The parameters in this group allow you to specify your filter response curve. Graphically, the filter specifications look similar to those shown in the following figure.



In the figure, regions between specification values such as  $F_{stop1}$  and  $F_{pass1}$  represent transition regions where the filter response is not explicitly defined.

## Frequency constraints

Select the filter features to use to define the frequency response characteristics. This dialog applies only when **Order mode** is **Specify**.

- **Passband and stopband edges** — Define the filter by specifying the frequencies for the edges for the stop- and passbands.
- **Passband edges** — Define the filter by specifying frequencies for the edges of the passband.
- **Stopband edges** — Define the filter by specifying frequencies for the edges of the stopbands.
- **3dB points** — Define the filter response by specifying the locations of the 3 dB points (IIR filters). The 3-dB point is the frequency for the point 3 dB below the passband value.
- **3dB points and passband width** — Define the filter by specifying frequencies for the 3-dB points in the filter response and the width of the passband. (IIR filters)
- **3dB points and stopband widths** — Define the filter by specifying frequencies for the 3-dB points in the filter response and the width of the stopband. (IIR filters)
- **6dB points** — Define the filter response by specifying the locations of the 6-dB points. The 6-dB point is the frequency for the point 6dB below the passband value. (FIR filters)

## Frequency units

Use this parameter to specify whether your frequency settings are normalized or in absolute frequency. Select **Normalized (0 1)** to enter frequencies in normalized form. This behavior is the default. To enter frequencies in hertz, select one of the frequency units from the drop-down list—Hz, kHz, MHz, or GHz. Selecting one of the unit options enables the **Input Fs** parameter.

**Input Fs**

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter input. When you provide an input sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is available when you select one of the frequency options from the **Frequency units** list.

**Fstop1**

Enter the frequency at the edge of the end of the first stopband. Specify the value in either normalized frequency units or the absolute units you select in **Frequency units**.

**Fpass1**

Enter the frequency at the edge of the start of the passband. Specify the value in either normalized frequency units or the absolute units you select **Frequency units**.

**Fpass2**

Enter the frequency at the edge of the end of the passband. Specify the value in either normalized frequency units or the absolute units you select **Frequency units**.

**Fstop2**

Enter the frequency at the edge of the start of the second stopband. Specify the value in either normalized frequency units or the absolute units you select **Frequency units**.

**Magnitude specifications**

The parameters in this group let you specify the filter response in the passbands and stopbands.

**Magnitude constraints**

Specify as **Unconstrained** or **Constrained** bands. You must have the DSP System Toolbox software to select **Constrained** bands. Selecting **Constrained** bands enables dialogs for both stopbands and the passband: **Astop1**, **Astop2**, and **Apass**. You cannot specify constraints for all three bands simultaneously.

Setting **Magnitude constraints** to **Constrained bands** enables the **Wstop** and **Wpass** options under **Design options**.

## Magnitude units

Specify the units for any parameter you provide in magnitude specifications. Select one of the following options from the drop-down list.

- **Linear** — Specify the magnitude in linear units.
- **dB** — Specify the magnitude in dB (decibels). This is the default setting.
- **Squared** — Specify the magnitude in squared units.

## Astop1

Enter the filter attenuation in the first stopband in the units you choose for **Magnitude units**, either linear or decibels.

## Apass

Enter the filter ripple allowed in the passband in the units you choose for **Magnitude units**, either linear or decibels.

## Astop2

Enter the filter attenuation in the second stopband in the units you choose for **Magnitude units**, either linear or decibels.

## Algorithm

The parameters in this group allow you to specify the design method and structure that `filterbuilder` uses to implement your filter.

## Design Method

Lists the design methods available for the frequency and magnitude specifications you entered. When you change the specifications for a filter, such as changing the impulse response, the methods available to design filters changes as well. The default IIR design method is usually Butterworth, and the default FIR method is equiripple.

## Scale SOS filter coefficients to reduce chance of overflow

Selecting this parameter directs the design to scale the filter coefficients to reduce the chances that the inputs or calculations in the filter overflow and exceed the representable range of the filter. Clearing this option removes the scaling. This parameter applies only to IIR filters.

## Design Options

The options for each design are specific for each design method. This section does not present all of the available options for all designs and design methods. There are many more that you encounter as you select different design methods and filter specifications. The following options represent some of the most common ones available.

### Density factor

Density factor controls the density of the frequency grid over which the design method optimization evaluates your filter response function. The number of equally spaced points in the grid is the value you enter for **Density factor** times (filter order + 1).

Increasing the value creates a filter that more closely approximates an ideal equiripple filter but increases the time required to design the filter. The default value of 16 represents a reasonable trade between the accurate approximation to the ideal filter and the time to design the filter.

### Phase constraint

Valid when the **Design method** is `equiripple` and you have the DSP System Toolbox installed. Choose one of `Linear`, `Minimum`, or `Maximum`.

### Minimum order

This option only applies when you have the DSP System Toolbox software and **Order mode** is `Minimum`.

Select `Any` (default), `Even`, or `Odd`. Selecting `Even` or `Odd` forces the minimum-order design to be an even or odd order.

**Wstop1**

Weight for the first stopband.

**Wpass**

Passband weight.

**Wstop2**

Weight for the second stopband.

**Max pole radius**

Valid only for IIR designs. Constrains the maximum pole radius. The default is 1. Reducing the max pole radius can produce a transfer function more resistant to quantization.

**Init norm**

Valid only for IIR designs. The initial norm used in the optimization. The default initial norm is 2.

**Init numerator**

Specifies an initial estimate of the filter numerator coefficients. This may be useful in difficult optimization problems.

**Init denominator**

Specifies an initial estimate of the filter denominator coefficients. This may be useful in difficult optimization problems.

**Filter implementation****Structure**

For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter. By default, FIR filters use direct-form structure, and IIR filters use direct-form II filters with SOS.

**Use a System object to implement filter**

Selecting this check box gives you the choice of using a system object to implement the filter. By default the check box is turned off. When the current design method or structure is not supported by a system object filter, then this check box is disabled.

**Bandstop Filter Design Dialog Box – Main Pane**

 Bandstop Design

Bandstop Design  
Design a bandstop filter.

Save variable as:  View Filter Re...

Main Data Types Code Generation

Filter specifications

Impulse response:

Order mode:

Filter type:

Frequency specifications

Frequency units:

Fpass1:  Fstop1:

Fstop2:  Fpass2:

Magnitude specifications

Magnitude units:

Apass1:  Astop:

Apass2:

Algorithm

Design method:

▼ Design options

Density factor:

Phase constraint:

Uniform grid

Filter implementation

Structure:

## Filter specifications

Parameters in this group enable you to specify your filter format, such as the impulse response and the filter order.

### Impulse response

Select FIR or IIR from the drop-down list, where FIR is the default impulse response. When you choose an impulse response, the design methods and structures you can use to implement your filter change accordingly.

---

**Note** The design methods and structures for FIR filters are not the same as the methods and structures for IIR filters.

---

### Order mode

Select Minimum (the default) or Specify from the drop-down list. Selecting Specify enables the **Order** option so you can enter the filter order.

If you have the DSP System Toolbox software installed, you can specify IIR filters with different numerator and denominator orders. The default is equal orders. To specify a different denominator order, check the **Denominator order** box.

### Filter type

Select Single-rate, Decimator, Interpolator, or Sample-rate converter. Your choice determines the type of filter as well as the design methods and structures that are available to implement your filter. By default, filterbuilder specifies single-rate filters.

- Selecting Decimator or Interpolator activates the **Decimation Factor** or the **Interpolation Factor** options respectively.
- Selecting Sample-rate converter activates both factors.

When you design either a decimator or an interpolator, the resulting filter is a bandpass filter that either decimates or interpolates your input signal.

## Order

Enter the filter order. This option is enabled only if Specify was selected for **Order mode**.

## Decimation Factor


Enter the decimation factor. This option is enabled only if the **Filter type** is set to Decimator or Sample-rate converter. The default factor value is 2.

## Interpolation Factor

Enter the decimation factor. This option is enabled only if the **Filter type** is set to Interpolator or Sample-rate converter. The default factor value is 2.

## Frequency specifications

The parameters in this group allow you to specify your filter response curve. Graphically, the filter specifications look similar to those shown in the following figure.



## Frequency constraints

Select the filter features to use to define the frequency response characteristics. This dialog applies only when **Order mode** is **Specify**.

- **Passband and stopband edges** — Define the filter by specifying the frequencies for the edges for the stop- and passbands.
- **Passband edges** — Define the filter by specifying frequencies for the edges of the passband.
- **Stopband edges** — Define the filter by specifying frequencies for the edges of the stopbands.
- **3dB points** — Define the filter response by specifying the locations of the 3 dB points (IIR filters). The 3 dB point is the frequency for the point 3 dB point below the passband value.
- **3dB points and passband width** — Define the filter by specifying frequencies for the 3 dB points in the filter response and the width of the passband (IIR filters).
- **3dB points and stopband widths** — Define the filter by specifying frequencies for the 3 dB points in the filter response and the width of the stopband (IIR filters).
- **6dB points** — Define the filter response by specifying the locations of the 6-dB points (FIR filters). The 6-dB point is the frequency for the point 6 dB point below the passband value.

## Frequency units

Use this parameter to specify whether your frequency settings are normalized or in absolute frequency. Select **Normalized (0 1)** to enter frequencies in normalized form. This behavior is the default. To enter frequencies in absolute values, select one of the frequency units from the drop-down list—Hz, kHz, MHz, or GHz. Selecting one of the unit options enables the **Input Fs** parameter.

**Input Fs**

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter input. When you provide an input sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is available when you select one of the frequency options from the **Frequency units** list.

**Output Fs**

When you design an interpolator, Fs represents the sampling frequency at the filter output rather than the filter input. This option is available only when you set **Filter type** is interpolator.

**Fpass1**

Enter the frequency at the edge of the end of the first passband. Specify the value in either normalized frequency units or the absolute units you select in **Frequency units**.

**Fstop1**

Enter the frequency at the edge of the start of the stopband. Specify the value in either normalized frequency units or the absolute units you select **Frequency units**.

**Fstop2**

Enter the frequency at the edge of the end of the stopband. Specify the value in either normalized frequency units or the absolute units you select **Frequency units**.

**Fpass2**

Enter the frequency at the edge of the start of the second passband. Specify the value in either normalized frequency units or the absolute units you select **Frequency units**.

**Magnitude specifications**

The parameters in this group let you specify the filter response in the passbands and stopbands.

## Magnitude constraints

Specify as **Unconstrained** or **Constrained** bands. You must have the DSP System Toolbox software to select **Constrained** bands. Selecting **Constrained** bands enables dialogs for both passbands and the stopband: **Apass1**, **Apass2**, and **Astop**. You cannot specify constraints for all three bands simultaneously.

Setting **Magnitude constraints** to **Constrained** bands enables the **Wstop** and **Wpass** options under **Design options**.

## Magnitude units

Specify the units for any parameter you provide in magnitude specifications. Select one of the following options from the drop-down list.

- **Linear** — Specify the magnitude in linear units.
- **dB** — Specify the magnitude in decibels (default).
- **Squared** — Specify the magnitude in squared units.

## Apass1

Enter the filter ripple allowed in the first passband in the units you choose for **Magnitude units**, either linear or decibels.

## Astop

Enter the filter attenuation in the stopband in the units you choose for **Magnitude units**, either linear or decibels

## Apass2

Enter the filter ripple allowed in the second passband in the units you choose for **Magnitude units**, either linear or decibels

## Algorithm

The parameters in this group allow you to specify the design method and structure that **filterbuilder** uses to implement your filter.

## Design Method

Lists the design methods available for the frequency and magnitude specifications you entered. When you change the

specifications for a filter, such as changing the impulse response, the methods available to design filters changes as well. The default IIR design method is usually Butterworth, and the default FIR method is equiripple.

### **Scale SOS filter coefficients to reduce chance of overflow**

Selecting this parameter directs the design to scale the filter coefficients to reduce the chances that the inputs or calculations in the filter overflow and exceed the representable range of the filter. Clearing this option removes the scaling. This parameter applies only to IIR filters.

### **Design Options**

The options for each design are specific for each design method. This section does not present all of the available options for all designs and design methods. There are many more that you encounter as you select different design methods and filter specifications. The following options represent some of the most common ones available.

### **Density factor**

Density factor controls the density of the frequency grid over which the design method optimization evaluates your filter response function. The number of equally spaced points in the grid is the value you enter for **Density factor** times (filter order + 1).

Increasing the value creates a filter that more closely approximates an ideal equiripple filter but increases the time required to design the filter. The default value of 16 represents a reasonable trade between the accurate approximation to the ideal filter and the time to design the filter.

### **Phase constraint**

Valid when the **Design method** is equiripple and you have the DSP System Toolbox installed. Choose one of Linear, Minimum, or Maximum.

**Minimum order**

This option only applies when you have the DSP System Toolbox software and **Order mode** is Minimum.

Select Any (default), Even, or Odd. Selecting Even or Odd forces the minimum-order design to be an even or odd order.

**Wpass1**

Weight for the first passband.

**Wstop**

Stopband weight.

**Wpass2**

Weight for the second passband.

**Match exactly**

Specifies that the resulting filter design matches either the passband or stopband or both bands when you select passband or stopband .

**Max pole radius**

Valid only for IIR designs. Constrains the maximum pole radius. The default is 1. Reducing the max pole radius can produce a transfer function more resistant to quantization.

**Init norm**

Valid only for IIR designs. The initial norm used in the optimization. The default initial norm is 2.

**Init numerator**

Specifies an initial estimate of the filter numerator coefficients. This may be useful in difficult optimization problems.

**Init denominator**

Specifies an initial estimate of the filter denominator coefficients. This may be useful in difficult optimization problems.

## **Filter implementation**

### **Structure**

For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter. By default, FIR filters use direct-form structure, and IIR filters use direct-form II filters with SOS.

### **Use a System object to implement filter**

Selecting this check box gives you the choice of using a system object to implement the filter. By default the check box is turned off. When the current design method or structure is not supported by a system object filter, then this check box is disabled.

## CIC Filter Design Dialog Box – Main Pane

CIC Design

CIC Design

Design a Cascaded Integrator-Comb filter.

Save variable as: Hcic View F

Main Data Types Code Generation

Filter specifications

Filter type: Decimator Factor: 2

Differential delay: 1

Frequency specifications

Frequency units: Normalized (0 to 1)

Fpass: .01

Magnitude specifications

Magnitude units: dB

Astop: 60

Filter implementation

Use a System object to implement filter

OK Cancel Help

## Filter specifications

Parameters in this group enable you to specify your CIC filter format, such as the filter type and the differential delay.

### Filter type

Select whether your filter will be a decimator or an interpolator. Your choice determines the type of filter and the design methods and structures that are available to implement your filter. Selecting decimator or interpolator activates the **Factor** option. When you design an interpolator, you enable the **Output Fs** parameter.

When you design either a decimator or interpolator, the resulting filter is a CIC filter that decimates or interpolates your input signal.

### Differential Delay

Specify the differential delay of your CIC filter as an integer value greater than or equal to 1. The default value is 1. The differential delay changes the shape, number, and location of nulls in the filter response. Increasing the differential delay increases the sharpness of the nulls and the response between the nulls. In practice, differential delay values of 1 or 2 are the most common.

### Factor

Specify the decimation or interpolation factor for your filter as an integer value greater than or equal to 1. The default value is 2.

## Frequency specifications

### Frequency units

Use this parameter to specify whether your frequency settings are normalized or in absolute frequency. Select **Normalized (0 1)** to enter frequencies in normalized form. This behavior is the default. To enter frequencies in absolute values, select one of the frequency units from the drop-down list—Hz, kHz, MHz, or GHz. Selecting one of the unit options enables the **Input Fs** parameter.

## **Input Fs**

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter input. When you provide an input sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is available when you select one of the frequency options from the **Frequency units** list.

## **Output Fs**

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter output. When you provide an output sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is available only when you design interpolators.

## **Fpass**

Enter the frequency at the end of the passband. Specify the value in either normalized frequency units or the absolute units you select **Frequency units**.

## **Magnitude specifications**

### **Magnitude units**

Specify the units for any parameter you provide in magnitude specifications. Select one of the following options from the drop-down list.

- Linear — Specify the magnitude in linear units.
- dB — Specify the magnitude in decibels (default).
- Squared — Specify the magnitude in squared units.

### **Astop**

Enter the filter attenuation in the stopband in the units you choose for **Magnitude units**, either linear or decibels.

## **Filter implementation**

### **Use a System object to implement filter**

Selecting this check box gives you the choice of using a system object to implement the filter. By default the check box is turned off. When the current design method or structure is not supported by a system object filter, then this check box is disabled.

## CIC Compensator Filter Design Dialog Box – Main Pane

The image shows a software dialog box titled "CIC Compensator Design". The main pane contains several sections for configuring the filter design:

- Save variable as:** Hciccomp
- View Filter Response** button
- Filter specifications:**
  - Order mode: Minimum
  - Filter type: Single-rate
  - Number of CIC sections: 2
  - Differential delay: 1
  - CIC rate change factor
- Frequency specifications:**
  - Frequency units: Normalized (0 to 1)
  - Fpass: .45
  - Fstop: .55
- Magnitude specifications:**
  - Magnitude units: dB
  - Apass: 1
  - Astop: 60
- Algorithm:**
  - Design method: Equiripple
  - Design options:
    - Density factor: 16
    - Phase constraint: Linear
    - Minimum order: Any
    - Stopband shape: Flat
    - Stopband decay: 0

## Filter specifications

Parameters in this group enable you to specify your filter format, such as the filter order mode and the filter type.

### Order mode

Select **Minimum** (the default) or **Specify** from the drop-down list. Selecting **Specify** enables the **Order** option (see the following sections) so you can enter the filter order.

### Filter type

Select **Single-rate**, **Decimator**, **Interpolator**, or **Sample-rate converter**. Your choice determines the type of filter as well as the design methods and structures that are available to implement your filter. By default, `filterbuilder` specifies single-rate filters.

- Selecting **Decimator** or **Interpolator** activates the **Decimation Factor** or the **Interpolation Factor** options respectively.
- Selecting **Sample-rate converter** activates both factors.

When you design either a decimator or an interpolator, the resulting filter is a bandpass filter that either decimates or interpolates your input signal.

### Order

Enter the filter order. This option is enabled only if **Specify** was selected for **Order mode**.

### Decimation Factor

Enter the decimation factor. This option is enabled only if the **Filter type** is set to **Decimator** or **Sample-rate converter**. The default factor value is 2.

### Interpolation Factor

Enter the decimation factor. This option is enabled only if the **Filter type** is set to **Interpolator** or **Sample-rate converter**. The default factor value is 2.

## **Number of CIC sections**

Specify the number of sections in the CIC filter for which you are designing this compensator. Select the number of sections from the drop-down list or enter the number.

## **Differential Delay**

Specify the differential delay of your target CIC filter. The default value is 1. Most CIC filters use 1 or 2.

## **Frequency specifications**

The parameters in this group allow you to specify your filter response curve.

## **Frequency specifications**

### **Frequency units**

Use this parameter to specify whether your frequency settings are normalized or in absolute frequency. Select **Normalized (0 1)** to enter frequencies in normalized form. This behavior is the default. To enter frequencies in absolute values, select one of the frequency units from the drop-down list—Hz, kHz, MHz, or GHz. Selecting one of the unit options enables the **Input Fs** parameter.

### **Input Fs**

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter input. When you provide an input sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is available when you select one of the frequency options from the **Frequency units** list.

### **Output Fs**

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter output. When you provide an output sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is available only when you design interpolators.

## **F<sub>pass</sub>**

Enter the frequency at the end of the passband. Specify the value in either normalized frequency units or the absolute units you select **Frequency units**.

## **F<sub>stop</sub>**

Enter the frequency at the start of the stopband. Specify the value in either normalized frequency units or the absolute units you select **Frequency units**.

## **Magnitude specifications**

The parameters in this group let you specify the filter response in the passbands and stopbands.

### **Magnitude units**

Specify the units for any parameter you provide in magnitude specifications. Select one of the following options from the drop-down list.

- Linear — Specify the magnitude in linear units.
- dB — Specify the magnitude in decibels (default).
- Squared — Specify the magnitude in squared units.

## **A<sub>pass</sub>**

Enter the filter ripple allowed in the passband in the units you choose for **Magnitude units**, either linear or decibels

## **Algorithm**

The parameters in this group allow you to specify the design method and structure that `filterbuilder` uses to implement your filter.

### **Design Method**

Lists the design methods available for the frequency and magnitude specifications you entered. When you change the specifications for a filter, such as changing the impulse response, the methods available to design filters changes as well. The

default IIR design method is usually Butterworth, and the default FIR method is equiripple.

## Design Options

The options for each design are specific for each design method. This section does not present all of the available options for all designs and design methods. There are many more that you encounter as you select different design methods and filter specifications. The following options represent some of the most common ones available.

### Density factor

Density factor controls the density of the frequency grid over which the design method optimization evaluates your filter response function. The number of equally spaced points in the grid is the value you enter for **Density factor** times (filter order + 1).

Increasing the value creates a filter that more closely approximates an ideal equiripple filter but increases the time required to design the filter. The default value of 16 represents a reasonable trade between the accurate approximation to the ideal filter and the time to design the filter.

### Minimum phase

To design a filter that is minimum phase, select **Minimum phase**. Clearing the **Minimum phase** option removes the phase constraint—the resulting design is not minimum phase.

### Minimum order

When you select this parameter, the design method determines and design the minimum order filter to meet your specifications. Some filters do not provide this parameter. Select Any, Even, or Odd from the drop-down list to direct the design to be any minimum order, or minimum even order, or minimum odd order.

---

**Note** Generally, **Minimum order** designs are not available for IIR filters.

---

### **Match exactly**

Specifies that the resulting filter design matches either the passband or stopband or both bands when you select **passband** or **stopband** or both from the drop-down list.

### **Stopband Shape**

Stopband shape lets you specify how the stopband changes with increasing frequency. Choose one of the following options:

- **Flat** — Specifies that the stopband is flat. The attenuation does not change as the frequency increases.
- **Linear** — Specifies that the stopband attenuation changes linearly as the frequency increases. Change the slope of the stopband by setting **Stopband decay**.
- **1/f** — Specifies that the stopband attenuation changes exponentially as the frequency increases, where **f** is the frequency. Set the power (exponent) for the decay in **Stopband decay**.

### **Stopband Decay**

When you set Stopband shape, Stopband decay specifies the amount of decay applied to the stopband. the following conditions apply to Stopband decay based on the value of Stopband Shape:

- When you set **Stopband shape** to **Flat**, **Stopband decay** has no affect on the stopband.
- When you set **Stopband shape** to **Linear**, enter the slope of the stopband in units of dB/rad/s. **filterbuilder** applies that slope to the stopband.
- When you set **Stopband shape** to **1/f**, enter a value for the exponent  $n$  in the relation  $(1/f)^n$  to define the stopband decay.

`filterbuilder` applies the  $(1/f)^n$  relation to the stopband to result in an exponentially decreasing stopband attenuation.

## **Filter implementation**

### **Structure**

For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter. By default, FIR filters use direct-form structure, and IIR filters use direct-form II filters with SOS.

### **Use a System object to implement filter**

Selecting this check box gives you the choice of using a system object to implement the filter. By default the check box is turned off. When the current design method or structure is not supported by a system object filter, then this check box is disabled.

**Comb Filter Design Dialog Box—Main Pane**

Comb Design

Design a comb filter.

Save variable as:

Main | Data Types | Code Generation

Filter specifications

Comb Type:

Order mode:  Order:

Frequency specifications

Frequency constraints:

Quality factor:

Frequency units:

Notch Frequencies:

Magnitude specifications

No magnitude constraints can be specified when specifying a filter order.

Algorithm

Design method:

Filter implementation

Structure:

Use a System object to implement filter

## Filter specifications

Parameters in this group enable you to specify the type of comb filter and the number of peaks or notches.


### Comb Type

Select Notch or Peak from the drop-down list. Notch creates a comb filter that attenuates a set of harmonically related frequencies. Peak creates a comb filter that amplifies a set of harmonically related frequencies.

### Order mode

Select Order or Number of Peaks/Notches from the drop-down menu.


Select Order to enter the desired filter order in the



Order:

dialog box. The comb filter has notches or peaks at increments of  $2/Order$  in normalized frequency units.

Select Number of Peaks or Number of Notches to specify the number of peaks or notches and the Shelving filter order



Main | Data Types | Code Generation

Filter specifications

Comb Type:

Order mode:  Number of Peaks

Shelving filter order

## Shelving filter order

The Shelving filter order is a positive integer that determines the sharpness of the peaks or notches. Larger values result in sharper peaks or notches.

## Frequency specifications

Parameters in this group enable you to specify the frequency constraints and frequency units.

### Frequency specifications

Select Quality factor or Bandwidth.

Quality factor is the ratio of the center frequency of the peak or notch to the bandwidth calculated at the  $-3$  dB point.

Bandwidth specifies the bandwidth of the peak or notch. By default the bandwidth is measured at the  $-3$  dB point. For example, setting the bandwidth equal to 0.1 results in 3 dB frequencies at normalized frequencies 0.05 above and below the center frequency of the peak or notch.

### Frequency Units

Specify the frequency units. The default is normalized frequency. Choosing an option in Hz enables the **Input Fs** dialog box.

## Magnitude specifications

Specify the units for the magnitude specification and the gain at which the bandwidth is measured. This menu is disabled if you specify a filter order. Select one of the following magnitude units from the drop down list:

- dB — Specify the magnitude in decibels (default).
- Squared — Specify the magnitude in squared units.

**Bandwidth gain** — Specify the gain at which the bandwidth is measured. The default is  $-3$  dB.

## **Algorithm**

The parameters in this group allow you to specify the design method and structure that `filterbuilder` uses to implement your filter.

## **Design Method**

The IIR Butterworth design is the only option for peaking or notching comb filters.

## **Filter implementation**

### **Structure**

For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter.

### **Use a System object to implement filter**

Selecting this check box gives you the choice of using a system object to implement the filter. By default the check box is turned off.

## Differentiator Filter Design Dialog Box – Main Pane


The image shows a software dialog box titled "Differentiator Design". It contains several sections for configuring a differentiator filter. At the top, there is a "Save variable as:" field with the value "Hdf" and a "View Filter Response" button. Below this are three tabs: "Main", "Data Types", and "Code Generation". The "Main" tab is active and contains the following sections:

- Filter specifications:** "Order mode:" is set to "Minimum" and "Filter type:" is set to "Single-rate".
- Frequency specifications:** "Frequency units:" is set to "Normalized (0 to 1)", "Fpass:" is 0.45, and "Fstop:" is 0.55.
- Magnitude specifications:** "Magnitude units:" is set to "dB", "Apass:" is 1, and "Astop:" is 60.
- Algorithm:** "Design method:" is set to "Equiripple".
- Design options:** "Density factor:" is 16.
- Filter implementation:** "Structure:" is set to "Direct-form FIR". There is an unchecked checkbox for "Use a System object to implement filter".

At the bottom of the dialog are buttons for "OK", "Cancel", "Help", and "Apply".

## Filter specifications

Parameters in this group enable you to specify your filter format, such as the impulse response and the filter order. Graphically, the filter specifications look similar to those shown in the following figure.



In the figure, regions between specification values such as **Fpass** ( $f_1$ ) and **Fstop** ( $f_3$ ) represent transition regions where the filter response is not explicitly defined.

### Order mode

Select **Minimum** (the default) or **Specify** from the drop-down list. Selecting **Specify** enables the **Order** option (see the following sections) so you can enter the filter order.

### Filter type

Select **Single-rate**, **Decimator**, **Interpolator**, or **Sample-rate converter**. Your choice determines the type of filter as well as the design methods and structures that are available to implement your filter. By default, **filterbuilder** specifies single-rate filters.

- Selecting **Decimator** or **Interpolator** activates the **Decimation Factor** or the **Interpolation Factor** options respectively.
- Selecting **Sample-rate converter** activates both factors.

When you design either a decimator or an interpolator, the resulting filter is a bandpass filter that either decimates or interpolates your input signal.

### **Order**

Enter the filter order. This option is enabled only if **Specify** was selected for **Order mode**.

### **Decimation Factor**

Enter the decimation factor. This option is enabled only if the **Filter type** is set to **Decimator** or **Sample-rate converter**. The default factor value is 2.

### **Interpolation Factor**

Enter the decimation factor. This option is enabled only if the **Filter type** is set to **Interpolator** or **Sample-rate converter**. The default factor value is 2.

## **Frequency specifications**

The parameters in this group allow you to specify your filter response curve.

### **Frequency constraints**

This option is only available when you specify the order of the filter design. Supported options are **Unconstrained** and **Passband edge and stopband edge**.

### **Frequency units**

Use this parameter to specify whether your frequency settings are normalized or in absolute frequency. Select **Normalized (0 1)** to enter frequencies in normalized form. This behavior is the default. To enter frequencies in absolute values, select one of the

frequency units from the drop-down list—Hz, kHz, MHz, or GHz. Selecting one of the unit options enables the **Input Fs** parameter.

## **Input Fs**

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter input. When you provide an input sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is available when you select one of the frequency options from the **Frequency units** list.

## **Fpass**

Enter the frequency at the end of the passband. Specify the value in either normalized frequency units or the absolute units you select **Frequency units**.

## **Fstop**

Enter the frequency at the start of the stopband. Specify the value in either normalized frequency units or the absolute units you select **Frequency units**.

## **Magnitude specifications**

The parameters in this group let you specify the filter response in the passbands and stopbands.

## **Magnitude constraints**

This option is only available when you specify the order of your filter design. The options for **Magnitude constraints** depend on the value of the **Frequency constraints**. If the value of **Frequency constraints** is Unconstrained, **Magnitude constraints** must be Unconstrained. If the value of **Frequency constraints** is Passband edge and stopband edge, **Magnitude constraints** can be Unconstrained, Passband ripple, or Stopband attenuation.

## Magnitude units

Specify the units for any parameter you provide in magnitude specifications. Select one of the following options from the drop-down list.

- Linear — Specify the magnitude in linear units.
- dB — Specify the magnitude in decibels (default).
- Squared — Specify the magnitude in squared units.

## Apass

Enter the filter ripple allowed in the passband in the units you choose for **Magnitude units**, either linear or decibels.

## Astop2

Enter the filter attenuation in the second stopband in the units you choose for **Magnitude units**, either linear or decibels.

## Algorithm

The parameters in this group allow you to specify the design method and structure that `filterbuilder` uses to implement your filter.

## Design Method

Lists the design methods available for the frequency and magnitude specifications you entered. When you change the specifications for a filter, such as changing the impulse response, the methods available to design filters changes as well. The default IIR design method is usually Butterworth, and the default FIR method is equiripple.

## Scale SOS filter coefficients to reduce chance of overflow

Selecting this parameter directs the design to scale the filter coefficients to reduce the chances that the inputs or calculations in the filter overflow and exceed the representable range of the filter. Clearing this option removes the scaling. This parameter applies only to IIR filters.

## Design Options

The options for each design are specific for each design method. This section does not present all of the available options for all designs and design methods. There are many more that you encounter as you select different design methods and filter specifications.

## Density factor

Density factor controls the density of the frequency grid over which the design method optimization evaluates your filter response function. The number of equally spaced points in the grid is the value you enter for **Density factor** times (filter order + 1).

Increasing the value creates a filter that more closely approximates an ideal equiripple filter but increases the time required to design the filter. The default value of 16 represents a reasonable trade between the accurate approximation to the ideal filter and the time to design the filter.

## Wpass

Passband weight. This option is only available for a specified-order design when **Frequency constraints** is equal to Passband edge and stopband edge and the **Design method** is Equiripple.

## Wstop

Stopband weight. This option is only available for a specified-order design when **Frequency constraints** is equal to Passband edge and stopband edge and the **Design method** is Equiripple.

## Filter implementation

### Structure


For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter. By default, FIR filters use direct-form structure, and IIR filters use direct-form II filters with SOS.

### Use a System object to implement filter

Selecting this check box gives you the choice of using a system object to implement the filter. By default the check box is turned

off. When the current design method or structure is not supported by a system object filter, then this check box is disabled.

### Fractional Delay Filter Design Dialog Box – Main Pane



#### Frequency specifications

Parameters in this group enable you to specify your filter format, such as the fractional delay and the filter order.

## **Order**

If you choose **Specify** for **Order mode**, enter your filter order in this field, or select the order from the drop-down list. `list.filterbuilder` designs a filter with the order you specify.

## **Fractional delay**

Specify a value between 0 and 1 samples for the filter fractional delay. The default value is 0.5 samples.

## **Frequency units**

Use this parameter to specify whether your frequency settings are normalized or in absolute frequency. Select **Normalized (0 1)** to enter frequencies in normalized form. This behavior is the default. To enter frequencies in absolute values, select one of the frequency units from the drop-down list—Hz, kHz, MHz, or GHz. Selecting one of the unit options enables the **Input Fs** parameter.

## **Input Fs**

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter input. When you provide an input sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is available when you select one of the frequency options from the **Frequency units** list.

## Halfband Filter Design Dialog Box – Main Pane

Halfband Design

Halfband Design

Design a Halfband filter.

Save variable as:  View Filter Response

Main Data Types Code Generation

Frequency specifications

Impulse response:

Order mode:

Response type:

Filter type:

Frequency specifications

Frequency units:

Transition width:

Magnitude specifications

Magnitude units:

Astop:

Algorithm

Design method:

Design options

Minimum phase

Stopband shape:

Stopband decay:

Filter implementation 7-715

Structure:

Use a System object to implement filter

## Filter specifications

Parameters in this group enable you to specify your filter type and order.

### Impulse response

Select FIR or IIR from the drop-down list, where FIR is the default impulse response. When you choose an impulse response, the design methods and structures you can use to implement your filter change accordingly.

---

**Note** The design methods and structures for FIR filters are not the same as the methods and structures for IIR filters.

---

### Order mode

Select Minimum (the default) or Specify from the drop-down list. Selecting Specify enables the **Order** option (see the following sections) so you can enter the filter order.

### Filter type

Select Single-rate, Decimator, or Interpolator. By default, filterbuilder specifies single-rate filters.


When you design either a decimator or an interpolator, the resulting filter is a bandpass filter that decimates or interpolates your input by a factor of two.

### Order

Enter the filter order. This option is enabled only if Specify was selected for **Order mode**.

## Frequency specifications

The parameters in this group allow you to specify your filter response curve. Graphically, the filter specifications for a halfband lowpass filter look similar to those shown in the following figure.



In the figure, the transition region lies between the end of the passband and the start of the stopband. The width is defined explicitly by the value of **Transition width**.

### Frequency units

Use this parameter to specify whether your frequency settings are normalized or in absolute frequency. Select **Normalized (0 1)** to enter frequencies in normalized form. This behavior is the default. To enter frequencies in absolute values, select one of the frequency units from the drop-down list—Hz, kHz, MHz, or GHz. Selecting one of the unit options enables the **Input Fs** parameter.

### Input Fs

$F_s$ , specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter input. When you provide an input sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is available when you select one of the frequency options from the **Frequency units** list.

## Transition width

Specify the width of the transition between the end of the passband and the edge of the stopband. Specify the value in normalized frequency units or the absolute units you select in **Frequency units**.

## Magnitude specifications

The parameters in this group let you specify the filter response in the passbands and stopbands.

## Magnitude units

Specify the units for any parameter you provide in magnitude specifications. Select one of the following options from the drop-down list.

- Linear — Specify the magnitude in linear units.
- dB — Specify the magnitude in decibels (default).

## Astop

Enter the filter attenuation in the stopband in the units you choose for **Magnitude units**, either linear or decibels.

## Algorithm

The parameters in this group allow you to specify the design method and structure that `filterbuilder` uses to implement your filter.

## Design Method

Lists the design methods available for the frequency and magnitude specifications you entered. For FIR halfband filters, the available design options are Equiripple and Kaiser window. For IIR halfband filters, the available design options are Butterworth, Elliptic, and IIR quasi-linear phase.

## Design Options

The following design options are available for FIR halfband filters when the user specifies an equiripple design:

**Minimum phase**

To design a filter that is minimum phase, select **Minimum phase**. Clearing the **Minimum phase** option removes the phase constraint—the resulting design is not minimum phase.

**Stopband Shape**

Stopband shape lets you specify how the stopband changes with increasing frequency. Choose one of the following options:

- **Flat** — Specifies that the stopband is flat. The attenuation does not change as the frequency increases.
- **Linear** — Specifies that the stopband attenuation changes linearly as the frequency increases. Change the slope of the stopband by setting **Stopband decay**.
- **1/f** — Specifies that the stopband attenuation changes exponentially as the frequency increases, where  $f$  is the frequency. Set the power (exponent) for the decay in **Stopband decay**.

**Stopband Decay**

When you set Stopband shape, Stopband decay specifies the amount of decay applied to the stopband. the following conditions apply to Stopband decay based on the value of Stopband Shape:

- When you set **Stopband shape** to **Flat**, **Stopband decay** has no affect on the stopband.
- When you set **Stopband shape** to **Linear**, enter the slope of the stopband in units of dB/rad/s. **filterbuilder** applies that slope to the stopband.
- When you set **Stopband shape** to **1/f**, enter a value for the exponent  $n$  in the relation  $(1/f)^n$  to define the stopband decay. **filterbuilder** applies the  $(1/f)^n$  relation to the stopband to result in an exponentially decreasing stopband attenuation.

## **Filter implementation**

### **Structure**

For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter.

### **Use a System object to implement filter**

Selecting this check box gives you the choice of using a system object to implement the filter. By default the check box is turned off. When the current design method or structure is not supported by a system object filter, then this check box is disabled.

## Highpass Filter Design Dialog Box – Main Pane

Highpass Design
✕

Highpass Design

Design a Highpass filter.

Save variable as:  View Filter Response

Main
Data Types
Code Generation

Filter specifications

Impulse response:

Order mode:

Filter type:

Frequency specifications

Frequency units:

Fstop:  Fpass:

Magnitude specifications

Magnitude units:

Astop:  Apass:

Algorithm

Design method:

▼ Design options

Density factor:

Phase constraint:

Minimum order:

Stopband shape:

Stopband decay:

Uniform grid

## Filter specifications

Parameters in this group enable you to specify your filter format, such as the impulse response and the filter order.

### Impulse response

Select FIR or IIR from the drop-down list, where FIR is the default impulse response. When you choose an impulse response, the design methods and structures you can use to implement your filter change accordingly.

---

**Note** The design methods and structures for FIR filters are not the same as the methods and structures for IIR filters.

---

### Order mode

Select Minimum (the default) or Specify from the drop-down list. Selecting Specify enables the **Order** option so you can enter the filter order.

If your **Impulse response** is IIR, you can specify an equal order for the numerator and denominator, or different numerator and denominator orders. The default is equal orders. To specify a different denominator order, check the **Denominator order** box.

### Filter type

This option is only available if you have the DSP System Toolbox software. Select Single-rate, Decimator, Interpolator, or Sample-rate converter. Your choice determines the type of filter as well as the design methods and structures that are available to implement your filter. By default, filterbuilder specifies single-rate filters.

- Selecting Decimator or Interpolator activates the **Decimation Factor** or the **Interpolation Factor** options respectively.
- Selecting Sample-rate converter activates both factors.

When you design either a decimator or an interpolator, the resulting filter is a highpass filter that either decimates or interpolates your input signal.

### Order

Enter the filter order. This option is enabled only if Specify was selected for **Order mode**.

### Decimation Factor


Enter the decimation factor. This option is enabled only if the **Filter type** is set to Decimator or Sample-rate converter. The default factor value is 2.

### Interpolation Factor

Enter the interpolation factor. This option is enabled only if the **Filter type** is set to Interpolator or Sample-rate converter. The default factor value is 2.

### Frequency specifications

The parameters in this group allow you to specify your filter response curve. Graphically, the filter specifications look similar to those shown in the following figure.



In the figure, the region between specification values F<sub>stop</sub> and F<sub>pass</sub> represents the transition region where the filter response is not explicitly defined.

## Frequency constraints

Select the filter features to use to define the frequency response characteristics. The list contains the following options, when available for the filter specifications.

- **Stopband edge and passband edge** — Define the filter by specifying the frequencies for the edges for the stopband and passband.
- **Passband edge** — Define the filter by specifying the frequency for the edge of the passband.
- **Stopband edge** — Define the filter by specifying the frequency for the edges of the stopband.
- **Stopband edge and 3dB point** — Define the filter by specifying the stopband edge frequency and the 3-dB down point (IIR designs).
- **3dB point and passband edge** — Define the filter by specifying the 3-dB down point and passband edge frequency (IIR designs).
- **3dB point** — Define the filter by specifying the frequency for the 3-dB point (IIR designs or maxflat FIR).
- **6dB point** — Define the filter by specifying the frequency for the 6-dB point in the filter response (FIR designs).

## Frequency units

Use this parameter to specify whether your frequency settings are normalized or in absolute frequency. Select **Normalized (0 1)** to enter frequencies in normalized form. This behavior is the default. To enter frequencies in absolute values, select one of the frequency units from the drop-down list—Hz, kHz, MHz, or GHz. Selecting one of the unit options enables the **Input Fs** parameter.

## Input Fs

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter input. When you provide an input sampling frequency, all frequencies in the

specifications are in the selected units as well. This parameter is available when you select one of the frequency options from the **Frequency units** list.

**Fpass**

Enter the frequency at the of the passband. Specify the value in either normalized frequency units or the absolute units you select **Frequency units**.

**Fstop**

Enter the frequency at the start of the stopband. Specify the value in either normalized frequency units or the absolute units you select **Frequency units**.

**Magnitude specifications**

The parameters in this group let you specify the filter response in the passbands and stopbands.

**Magnitude units**

Specify the units for any parameter you provide in magnitude specifications. Select one of the following options from the drop-down list.

- Linear — Specify the magnitude in linear units.
- dB — Specify the magnitude in decibels (default).
- Squared — Specify the magnitude in squared units.

**Astop**

Enter the filter attenuation in the stopband in the units you choose for **Magnitude units**, either linear or decibels.

**Apass**

Enter the filter ripple allowed in the passband in the units you choose for **Magnitude units**, either linear or decibels.

## Algorithm

The parameters in this group allow you to specify the design method and structure that `filterbuilder` uses to implement your filter.

## Design Method

Lists the design methods available for the frequency and magnitude specifications you entered. When you change the specifications for a filter, such as changing the impulse response, the methods available to design filters changes as well. The default IIR design method is usually Butterworth, and the default FIR method is equiripple.

## Scale SOS filter coefficients to reduce chance of overflow

Selecting this parameter directs the design to scale the filter coefficients to reduce the chances that the inputs or calculations in the filter overflow and exceed the representable range of the filter. Clearing this option removes the scaling. This parameter applies only to IIR filters.

## Design Options

The options for each design are specific for each design method. This section does not present all of the available options for all designs and design methods. There are many more that you encounter as you select different design methods and filter specifications. The following options represent some of the most common ones available.

## Density factor

Density factor controls the density of the frequency grid over which the design method optimization evaluates your filter response function. The number of equally spaced points in the grid is the value you enter for **Density factor** times (filter order + 1).

Increasing the value creates a filter that more closely approximates an ideal equiripple filter but increases the time required to design the filter. The default value of 16 represents a

reasonable trade between the accurate approximation to the ideal filter and the time to design the filter.

**Phase constraint**

This option only applies when you have the DSP System Toolbox software and when the **Design method** is `equiripple`. Select one of `Linear`, `Minimum`, or `Maximum`.

**Minimum order** — This option only applies when you have the DSP System Toolbox software and the **Order mode** is `Minimum`.

Select `Any` (default), `Even`, or `Odd`. Selecting `Even` or `Odd` forces the minimum-order design to be an even or odd order.

**Match Exactly**

Specifies that the resulting filter design matches either the passband or stopband when you select `Passband` or `Stopband`.

**Stopband Shape**

Stopband shape lets you specify how the stopband changes with increasing frequency. Choose one of the following options:

- **Flat** — Specifies that the stopband is flat. The attenuation does not change as the frequency increases.
- **Linear** — Specifies that the stopband attenuation changes linearly as the frequency increases. Change the slope of the stopband by setting **Stopband decay**.
- **1/f** — Specifies that the stopband attenuation changes exponentially as the frequency increases, where  $f$  is the frequency. Set the power (exponent) for the decay in **Stopband decay**.

**Stopband Decay**

When you set Stopband shape, Stopband decay specifies the amount of decay applied to the stopband. the following conditions apply to Stopband decay based on the value of Stopband Shape:

- When you set **Stopband shape** to `Flat`, **Stopband decay** has no affect on the stopband.

- When you set **Stopband shape** to Linear, enter the slope of the stopband in units of dB/rad/s. `filterbuilder` applies that slope to the stopband.
- When you set **Stopband shape** to  $1/f$ , enter a value for the exponent  $n$  in the relation  $(1/f)^n$  to define the stopband decay. `filterbuilder` applies the  $(1/f)^n$  relation to the stopband to result in an exponentially decreasing stopband attenuation.

## **Wpass**

Passband weight. This option only applies when **Impulse response** is FIR and **Order mode** is Specify.

## **Wstop**

Stopband weight. This option only applies when **Impulse response** is FIR and **Order mode** is Specify.

## **Filter implementation**

### **Structure**

For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter. By default, FIR filters use direct-form structure, and IIR filters use direct-form II filters with SOS.

### **Use a System object to implement filter**

Selecting this check box gives you the choice of using a system object to implement the filter. By default the check box is turned off. When the current design method or structure is not supported by a system object filter, then this check box is disabled.

## Hilbert Filter Design Dialog Box – Main Pane

Hilbert Design

Hilbert Design

Design a Hilbert filter.

Save variable as:

Main Data Types Code Generation

Filter specifications

Impulse response:

Order mode:

Filter type:

Frequency specifications

Frequency units:

Transition width

Magnitude specifications

Magnitude units:

Apass:

Algorithm

Design method:

▼ Design options

Density factor:

FIR Type:

Filter implementation

Structure:

Use a System object to implement filter

7-729

OK Cancel Help Apply

## Impulse response

Select FIR or IIR from the drop-down list, where FIR is the default impulse response. When you choose an impulse response, the design methods and structures you can use to implement your filter change accordingly.

---

**Note** The design methods and structures for FIR filters are not the same as the methods and structures for IIR filters.

---

## Order mode

This option is only available if you have the DSP System Toolbox software. Select either **Minimum** (the default) or **Specify** from the drop-down list. Selecting **Specify** enables the **Order** option (see the following sections) so you can enter the filter order.

## Filter type

This option is only available if you have the DSP System Toolbox software. Select **Single-rate**, **Decimator**, **Interpolator**, or **Sample-rate converter**. Your choice determines the type of filter as well as the design methods and structures that are available to implement your filter. By default, **filterbuilder** specifies single-rate filters.

- Selecting **Decimator** or **Interpolator** activates the **Decimation Factor** or the **Interpolation Factor** options respectively.
- Selecting **Sample-rate converter** activates both factors.

When you design either a decimator or an interpolator, the resulting filter is a bandpass filter that either decimates or interpolates your input signal.

## Order

Enter the filter order. This option is enabled only if **Specify** was selected for **Order mode**.

**Decimation Factor**


Enter the decimation factor. This option is enabled only if the **Filter type** is set to Decimator or Sample-rate converter. The default factor value is 2.

**Interpolation Factor**

Enter the decimation factor. This option is enabled only if the **Filter type** is set to Interpolator or Sample-rate converter. The default factor value is 2.

**Frequency specifications**

The parameters in this group allow you to specify your filter response curve. Graphically, the filter specifications look similar to those shown in the following figure.



In the figure, the regions between 0 and  $f_1$  and between  $f_2$  and 1 represent the transition regions where the filter response is explicitly defined by the transition width.

## Frequency units

Use this parameter to specify whether your frequency settings are normalized or in absolute frequency. Select **Normalized (0 1)** to enter frequencies in normalized form. This behavior is the default. To enter frequencies in absolute values, select one of the frequency units from the drop-down list—Hz, kHz, MHz, or GHz. Selecting one of the unit options enables the **Input Fs** parameter.

## Input Fs

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter input. When you provide an input sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is available when you select one of the frequency options from the **Frequency units** list.

## Transition width

Specify the width of the transitions at the ends of the passband. Specify the value in normalized frequency units or the absolute units you select in **Frequency units**.

## Magnitude specifications

The parameters in this group let you specify the filter response in the passbands and stopbands.

## Magnitude units

Specify the units for any parameter you provide in magnitude specifications. Select one of the following options from the drop-down list.

- **Linear** — Specify the magnitude in linear units.
- **dB** — Specify the magnitude in decibels (default)
- **Squared** — Specify the magnitude in squared units.

## Apass

Enter the filter ripple allowed in the passband in the units you choose for **Magnitude units**, either linear or decibels.

## Algorithm

The parameters in this group allow you to specify the design method and structure that `filterbuilder` uses to implement your filter.

## Design Method

Lists the design methods available for the frequency and magnitude specifications you entered. When you change the specifications for a filter, such as changing the impulse response, the methods available to design filters changes as well. The default IIR design method is usually Butterworth, and the default FIR method is equiripple.

## Scale SOS filter coefficients to reduce chance of overflow

Selecting this parameter directs the design to scale the filter coefficients to reduce the chances that the inputs or calculations in the filter overflow and exceed the representable range of the filter. Clearing this option removes the scaling. This parameter applies only to IIR filters.

## Design Options

The options for each design are specific for each design method. This section does not present all of the available options for all designs and design methods. There are many more that you encounter as you select different design methods and filter specifications. The following options represent some of the most common ones available.

## Density factor

Density factor controls the density of the frequency grid over which the design method optimization evaluates your filter response function. The number of equally spaced points in the grid is the value you enter for **Density factor** times (filter order + 1).

Increasing the value creates a filter that more closely approximates an ideal equiripple filter but increases the time required to design the filter. The default value of 16 represents a

reasonable trade between the accurate approximation to the ideal filter and the time to design the filter.

## **FIR Type**

This option is only available in a minimum-order design. Specify whether to design a type 3 or a type 4 FIR filter. The filter type is defined as follows:

- Type 3 — FIR filter with even order antisymmetric coefficients
  - Type 4 — FIR filter with odd order antisymmetric coefficients
- Select 3 or 4 from the drop-down list.

## **Filter implementation**

### **Structure**

For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter. By default, FIR filters use direct-form structure, and IIR filters use direct-form II filters with SOS.

### **Use a System object to implement filter**

Selecting this check box gives you the choice of using a system object to implement the filter. By default the check box is turned off. When the current design method or structure is not supported by a system object filter, then this check box is disabled.

## Inverse Sinc Filter Design Dialog Box – Main Pane

The dialog box is titled "Inverse Sinc Design" and contains the following sections and controls:

- Title Bar:** Inverse Sinc Design
- Description:** Inverse Sinc Design. Design an inverse-sinc filter.
- Save variable as:** Hisinc
- Buttons:** View Filter Response
- Tabs:** Main (selected), Data Types, Code Generation
- Filter specifications:**
  - Order mode: Minimum
  - Response type: Lowpass
  - Filter type: Single-rate
- Frequency specifications:**
  - Frequency units: Normalized (0 to 1)
  - Fpass: .45
  - Fstop: .55
- Magnitude specifications:**
  - Magnitude units: dB
  - Apass: 1
  - Astop: 60
- Algorithm:**
  - Design method: Equiripple
  - Design options:
    - Density factor: 16
    - Phase constraint: Linear
    - Minimum order: Any
    - Stopband shape: Flat
    - Stopband decay: 0
    - Sinc frequency factor: 0.5
    - Sinc power: 1
- Filter implementation:**
  - Structure: Direct-form FIR
  - Use a System object to implement filter
- Buttons:** OK, Cancel, Help, Apply

### Filter specifications

Parameters in this group enable you to specify your filter format, such as the impulse response and the filter order.

## **Order mode**

Select **Minimum** (the default) or **Specify** from the drop-down list. Selecting **Specify** enables the **Order** option (see the following sections) so you can enter the filter order.

## **Response type**

Select **Lowpass** or **Highpass** to design an inverse sinc lowpass or highpass filter.

## **Filter type**

Select **Single-rate**, **Decimator**, **Interpolator**, or **Sample-rate converter**. Your choice determines the type of filter as well as the design methods and structures that are available to implement your filter. By default, **filterbuilder** specifies single-rate filters.

- Selecting **Decimator** or **Interpolator** activates the **Decimation Factor** or the **Interpolation Factor** options respectively.
- Selecting **Sample-rate converter** activates both factors.

When you design either a decimator or an interpolator, the resulting filter is a bandpass filter that either decimates or interpolates your input signal.

## **Order**

Enter the filter order. This option is enabled only if **Specify** was selected for **Order mode**.

## **Decimation Factor**


Enter the decimation factor. This option is enabled only if the **Filter type** is set to **Decimator** or **Sample-rate converter**. The default factor value is 2.

## **Interpolation Factor**

Enter the decimation factor. This option is enabled only if the **Filter type** is set to **Interpolator** or **Sample-rate converter**. The default factor value is 2.

## Frequency specifications

The parameters in this group allow you to specify your filter response curve. Graphically, the filter specifications look similar to those shown in the following figure.



Regions between specification values such as  $F_{pass}$  and  $F_{stop}$  represent transition regions where the filter response is not explicitly defined.

## Frequency constraints

This option is only available when you specify the filter order. The following options are available:

- Passband and stopband edges — Define the filter by specifying the frequencies for the edges for the stop- and passbands.
- Passband edge — Define the filter by specifying frequencies for the edges of the passband.
- Stopband edge — Define the filter by specifying frequencies for the edges of the stopbands.

- **6dB point** — The 6-dB point is the frequency for the point 6 dB point below the passband value.

## **Frequency units**

Use this parameter to specify whether your frequency settings are normalized or in absolute frequency. Select **Normalized (0 1)** to enter frequencies in normalized form. This behavior is the default. To enter frequencies in absolute values, select one of the frequency units from the drop-down list—Hz, kHz, MHz, or GHz. Selecting one of the unit options enables the **Input Fs** parameter.

## **Input Fs**

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter input. When you provide an input sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is available when you select one of the frequency options from the **Frequency units** list.

## **Fpass**

Enter the frequency at the end of the passband. Specify the value in either normalized frequency units or the absolute units you select **Frequency units**.

## **Fstop**

Enter the frequency at the start of the stopband. Specify the value in either normalized frequency units or the absolute units you select **Frequency units**.

## **Magnitude specifications**

The parameters in this group let you specify the filter response in the passbands and stopbands.

## **Magnitude units**

Specify the units for any parameter you provide in magnitude specifications. Select one of the following options from the drop-down list.

- **Linear** — Specify the magnitude in linear units.

- dB — Specify the magnitude in decibels (default)
- Squared — Specify the magnitude in squared units.

**Apass**

Enter the filter ripple allowed in the passband in the units you choose for **Magnitude units**, either linear or decibels.

**Astop**

Enter the filter attenuation in the stopband in the units you choose for **Magnitude units**, either linear or decibels.

**Algorithm**

The parameters in this group allow you to specify the design method and structure that `filterbuilder` uses to implement your filter.

**Design Method**

Lists the design methods available for the frequency and magnitude specifications you entered. When you change the specifications for a filter, such as changing the impulse response, the methods available to design filters changes as well. The default IIR design method is usually Butterworth, and the default FIR method is equiripple.

**Design Options**

The options for each design are specific for each design method. This section does not present all of the available options for all designs and design methods. There are many more that you encounter as you select different design methods and filter specifications. The following options represent some of the most common ones available.

**Density factor**

Density factor controls the density of the frequency grid over which the design method optimization evaluates your filter response function. The number of equally spaced points in the grid is the value you enter for **Density factor** times (filter order + 1).

Increasing the value creates a filter that more closely approximates an ideal equiripple filter but increases the time required to design the filter. The default value of 16 represents a reasonable trade between the accurate approximation to the ideal filter and the time to design the filter.

## Phase constraint

Available options are Linear, Minimum, and Maximum.

## Stopband Shape

Stopband shape lets you specify how the stopband changes with increasing frequency. Choose one of the following options;

- **Flat** — Specifies that the stopband is flat. The attenuation does not change as the frequency increases.
- **Linear** — Specifies that the stopband attenuation changes linearly as the frequency increases. Change the slope of the stopband by setting **Stopband decay**.
- **1/f** — Specifies that the stopband attenuation changes exponentially as the frequency increases, where  $f$  is the frequency. Set the power (exponent) for the decay in **Stopband decay**.

## Stopband Decay

When you set Stopband shape, Stopband decay specifies the amount of decay applied to the stopband. the following conditions apply to Stopband decay based on the value of Stopband Shape:

- When you set **Stopband shape** to Flat, **Stopband decay** has no affect on the stopband.
- When you set **Stopband shape** to Linear, enter the slope of the stopband in units of dB/rad/s. `filterbuilder` applies that slope to the stopband.
- When you set **Stopband shape** to 1/f, enter a value for the exponent  $n$  in the relation  $(1/f)^n$  to define the stopband decay. `filterbuilder` applies the  $(1/f)^n$  relation to the stopband to result in an exponentially decreasing stopband attenuation.

**Sinc frequency factor**

A frequency dilation factor. The sinc frequency factor,  $C$ , parameterizes the passband magnitude response for a lowpass design through  $H(\omega) = \text{sinc}(C\omega)^{-P}$  and for a highpass design through  $H(\omega) = \text{sinc}(C(1-\omega))^{-P}$ .

**Sinc power**

Negative power of passband magnitude response. The sinc power,  $P$ , parameterizes the passband magnitude response for a lowpass design through  $H(\omega) = \text{sinc}(C\omega)^{-P}$  and for a highpass design through  $H(\omega) = \text{sinc}(C(1-\omega))^{-P}$ .

**Filter implementation****Structure**

For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter. By default, FIR filters use direct-form structure.

**Use a System object to implement filter**

Selecting this check box gives you the choice of using a system object to implement the filter. By default the check box is turned off. When the current design method or structure is not supported by a system object filter, then this check box is disabled.

## Lowpass Filter Design Dialog Box – Main Pane

Lowpass Design

Lowpass Design  
Design a lowpass filter.

Save variable as:

Main | Data Types | Code Generation

Filter specifications

Impulse response:

Order mode:

Filter type:

Frequency specifications

Frequency units:

Fpass:  Fstop:

Magnitude specifications

Magnitude units:

Apass:  Astop:

Algorithm

Design method:

▼ Design options

Density factor:

Phase constraint:

Minimum order:

Stopband shape:

Stopband decay:

Uniform grid

Filter implementation

## Filter specifications

Parameters in this group enable you to specify your filter format, such as the impulse response and the filter order.

### Impulse response

Select FIR or IIR from the drop-down list, where FIR is the default impulse response. When you choose an impulse response, the design methods and structures you can use to implement your filter change accordingly.

---

**Note** The design methods and structures for FIR filters are not the same as the methods and structures for IIR filters.

---

### Order mode

Select Minimum (the default) or Specify from the drop-down list. Selecting Specify enables the **Order** option (see the following sections) so you can enter the filter order.

If your **Impulse response** is IIR, you can specify an equal order for the numerator and denominator, or different numerator and denominator orders. The default is equal orders. To specify a different denominator order, check the **Denominator order** box.

### Filter type

This option is only available if you have the DSP System Toolbox. Select Single-rate, Decimator, Interpolator, or Sample-rate converter. Your choice determines the type of filter as well as the design methods and structures that are available to implement your filter. By default, filterbuilder specifies single-rate filters.

- Selecting Decimator or Interpolator activates the **Decimation Factor** or the **Interpolation Factor** options respectively.
- Selecting Sample-rate converter activates both factors.

When you design either a decimator or an interpolator, the resulting filter is a bandpass filter that either decimates or interpolates your input signal.

## Order

Enter the filter order. This option is enabled only if Specify was selected for **Order mode**.

## Decimation Factor


Enter the decimation factor. This option is enabled only if the **Filter type** is set to Decimator or Sample-rate converter. The default factor value is 2.

## Interpolation Factor

Enter the decimation factor. This option is enabled only if the **Filter type** is set to Interpolator or Sample-rate converter. The default factor value is 2.

## Frequency specifications

The parameters in this group allow you to specify your filter response curve. Graphically, the filter specifications look similar to the one shown in the following figure.



In the figure, regions between specification values such as  $F_{\text{pass}}$  and  $F_{\text{stop}}$  represent transition regions where the filter response is not explicitly defined.

### Frequency constraints

Select the filter features to use to define the frequency response characteristics. The list contains the following options, when available for the filter specifications.

- **Passband and stopband edge** — Define the filter by specifying the frequencies for the edge of the stopband and passband.
- **Passband edge** — Define the filter by specifying the frequency for the edge of the passband.
- **Stopband edge** — Define the filter by specifying the frequency for the edges of the stopband.
- **Passband edge and 3dB point** — Define the filter by specifying the passband edge frequency and the 3-dB down point (IIR designs).
- **3dB point and stopband edge** — Define the filter by specifying the 3-dB down point and stopband edge frequency (IIR designs).
- **3dB point** — Define the filter by specifying the frequency for the 3-dB point (IIR designs or maxflat FIR).
- **6dB point** — Define the filter by specifying the frequency for the 6-dB point in the filter response (FIR designs).

### Frequency units

Use this parameter to specify whether your frequency settings are normalized or in absolute frequency. Select **Normalized (0 1)** to enter frequencies in normalized form. This behavior is the default. To enter frequencies in absolute values, select one of the frequency units from the drop-down list—Hz, kHz, MHz, or GHz. Selecting one of the unit options enables the **Input Fs** parameter.

### Input Fs

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter input. When you provide an input sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is

available when you select one of the frequency options from the **Frequency units** list.

## **Fpass**

Enter the frequency at the of the passband. Specify the value in either normalized frequency units or the absolute units you select **Frequency units**.

## **Fstop**

Enter the frequency at the start of the stopband. Specify the value in either normalized frequency units or the absolute units you select **Frequency units**.

## **Magnitude specifications**

The parameters in this group let you specify the filter response in the passbands and stopbands.

### **Magnitude units**

Specify the units for any parameter you provide in magnitude specifications. Select one of the following options from the drop-down list.

- Linear — Specify the magnitude in linear units.
- dB — Specify the magnitude in decibels (default)
- Squared — Specify the magnitude in squared units.

### **Apass**

Enter the filter ripple allowed in the passband in the units you choose for **Magnitude units**, either linear or decibels.

### **Astop**

Enter the filter attenuation in the stopband in the units you choose for **Magnitude units**, either linear or decibels.

## **Algorithm**

The parameters in this group allow you to specify the design method and structure that `filterbuilder` uses to implement your filter.

## Design Method

Lists the design methods available for the frequency and magnitude specifications you entered. When you change the specifications for a filter, such as changing the impulse response, the methods available to design filters changes as well. The default IIR design method is usually Butterworth, and the default FIR method is equiripple.

## Scale SOS filter coefficients to reduce chance of overflow

Selecting this parameter directs the design to scale the filter coefficients to reduce the chances that the inputs or calculations in the filter overflow and exceed the representable range of the filter. Clearing this option removes the scaling. This parameter applies only to IIR filters.

## Design Options

The options for each design are specific for each design method. This section does not present all of the available options for all designs and design methods. There are many more that you encounter as you select different design methods and filter specifications. The following options represent some of the most common ones available.

## Density factor

Density factor controls the density of the frequency grid over which the design method optimization evaluates your filter response function. The number of equally spaced points in the grid is the value you enter for **Density factor** times (filter order + 1).

Increasing the value creates a filter that more closely approximates an ideal equiripple filter but increases the time required to design the filter. The default value of 16 represents a reasonable trade between the accurate approximation to the ideal filter and the time to design the filter.

## Phase constraint

This option only applies when you have the DSP System Toolbox software and when the **Design method** is equiripple. Select one of Linear, Minimum, or Maximum.

**Minimum order** — This option only applies when you have the DSP System Toolbox software and the **Order mode** is Minimum.

Select Any (default), Even, or Odd. Selecting Even or Odd forces the minimum-order design to be an even or odd order.

## Match Exactly

Specifies that the resulting filter design matches either the passband or stopband when you select Passband or Stopband.

## Stopband Shape

Stopband shape lets you specify how the stopband changes with increasing frequency. Choose one of the following options:

- **Flat** — Specifies that the stopband is flat. The attenuation does not change as the frequency increases.
- **Linear** — Specifies that the stopband attenuation changes linearly as the frequency increases. Change the slope of the stopband by setting **Stopband decay**.
- **1/f** — Specifies that the stopband attenuation changes exponentially as the frequency increases, where  $f$  is the frequency. Set the power (exponent) for the decay in **Stopband decay**.

## Stopband Decay

When you set Stopband shape, Stopband decay specifies the amount of decay applied to the stopband. the following conditions apply to Stopband decay based on the value of Stopband Shape:

- When you set **Stopband shape** to Flat, **Stopband decay** has no affect on the stopband.
- When you set **Stopband shape** to Linear, enter the slope of the stopband in units of dB/rad/s. `filterbuilder` applies that slope to the stopband.

- When you set **Stopband shape** to  $1/f$ , enter a value for the exponent  $n$  in the relation  $(1/f)^n$  to define the stopband decay. **filterbuilder** applies the  $(1/f)^n$  relation to the stopband to result in an exponentially decreasing stopband attenuation.

### **Wpass**

Passband weight. This option only applies when **Impulse response** is FIR and **Order mode** is Specify.

### **Wstop**

Stopband weight. This option only applies when **Impulse response** is FIR and **Order mode** is Specify.

## **Filter implementation**

### **Structure**

For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter. By default, FIR filters use direct-form structure, and IIR filters use direct-form II filters with SOS.

### **Use a System object to implement filter**

Selecting this check box gives you the choice of using a system object to implement the filter. By default the check box is turned off. When the current design method or structure is not supported by a system object filter, then this check box is disabled.

### **Notch**

See “Peak/Notch Filter Design Dialog Box — Main Pane” on page 7-767.

## Nyquist Filter Design Dialog Box – Main Pane

Nyquist Design

Nyquist Design  
Design a Nyquist filter.

Save variable as: Hnyq View Filter Response

Main Data Types Code Generation

Filter specifications

Band: 2

Impulse response: FIR

Filter order mode: Minimum

Filter type: Single-rate

Frequency specifications

Frequency units: Normalized (0 to 1)

Transition width: .1

Magnitude specifications

Magnitude units: dB

Astop: 80

Algorithm

Design method: Kaiser window

Filter implementation

Structure: Direct-form FIR

Use a System object to implement filter

OK Cancel Help Apply

## Filter specifications

Parameters in this group enable you to specify your filter format, such as the impulse response and the filter order.

### Band

Specifies the location of the center of the transition region between the passband and the stopband. The center of the transition region,  $bw$ , is calculated using the value for Band:

$$bw = F_s/(2*Band).$$

### Impulse response

Select FIR or IIR from the drop-down list, where FIR is the default impulse response. When you choose an impulse response, the design methods and structures you can use to implement your filter change accordingly.

---

**Note** The design methods and structures for FIR filters are not the same as the methods and structures for IIR filters.

---

### Order mode

Select Minimum (the default) or Specify from the drop-down list. Selecting Specify enables the **Order** option (see the following sections) so you can enter the filter order.

### Filter type

Select Single-rate, Decimator, Interpolator, or Sample-rate converter. Your choice determines the type of filter as well as the design methods and structures that are available to implement your filter. By default, filterbuilder specifies single-rate filters.

- Selecting Decimator or Interpolator activates the **Decimation Factor** or the **Interpolation Factor** options respectively.
- Selecting Sample-rate converter activates both factors.

# filterbuilder

---

When you design either a decimator or an interpolator, the resulting filter is a bandpass filter that either decimates or interpolates your input signal.

## Order

Enter the filter order. This option is enabled only if Specify was selected for **Order mode**.

## Decimation Factor


Enter the decimation factor. This option is enabled only if the **Filter type** is set to Decimator or Sample-rate converter. The default factor value is 2.

## Interpolation Factor

Enter the decimation factor. This option is enabled only if the **Filter type** is set to Interpolator or Sample-rate converter. The default factor value is 2.

## Frequency specifications

The parameters in this group allow you to specify your filter response curve. Graphically, the filter specifications look similar to those shown in the following figure.



In the figure, BW is the width of the transition region and **Band** determines the location of the center of the region.

### Frequency constraints

Select the filter features to use to define the frequency response characteristics. The list contains the following options, when available for the filter specifications.

- **Passband and stopband edges** — Define the filter by specifying the frequencies for the edges for the stopbands and passbands.
- **Passband edges** — Define the filter by specifying frequencies for the edges of the passband.
- **Stopband edges** — Define the filter by specifying frequencies for the edges of the stopbands.
- **3 dB points** — Define the filter response by specifying the locations of the 3 dB points. The 3 dB point is the frequency for the point 3 dB point below the passband value.
- **3 dB points and passband width** — Define the filter by specifying frequencies for the 3 dB points in the filter response and the width of the passband.
- **3 dB points and stopband widths** — Define the filter by specifying frequencies for the 3 dB points in the filter response and the width of the stopband.

### Frequency units

Use this parameter to specify whether your frequency settings are normalized or in absolute frequency. Select **Normalized (0 1)** to enter frequencies in normalized form. This behavior is the default. To enter frequencies in absolute values, select one of the frequency units from the drop-down list—Hz, kHz, MHz, or GHz. Selecting one of the unit options enables the **Input Fs** parameter.

## Input Fs

Fs, specified in the units you selected for **Frequency units**, defines the sampling frequency at the filter input. When you provide an input sampling frequency, all frequencies in the specifications are in the selected units as well. This parameter is available when you select one of the frequency options from the **Frequency units** list.

## Transition width

Specify the width of the transition between the end of the passband and the edge of the stopband. Specify the value in normalized frequency units or the absolute units you select in **Frequency units**.

## Magnitude specifications

The parameters in this group let you specify the filter response in the passbands and stopbands.

### Magnitude units

Specify the units for any parameter you provide in magnitude specifications. Select one of the following options from the drop-down list.

- Linear — Specify the magnitude in linear units.
- dB — Specify the magnitude in decibels (default)
- Squared — Specify the magnitude in squared units.

### Astop

Enter the filter attenuation in the stopband in the units you choose for **Magnitude units**, either linear or decibels.

## Algorithm

The parameters in this group allow you to specify the design method and structure that `filterbuilder` uses to implement your filter.

### Design Method

Lists the design methods available for the frequency and magnitude specifications you entered. When you change the specifications for a filter, such as changing the impulse response, the methods available to design filters changes as well. The default IIR design method is usually Butterworth, and the default FIR method is equiripple.

### Scale SOS filter coefficients to reduce chance of overflow

Selecting this parameter directs the design to scale the filter coefficients to reduce the chances that the inputs or calculations in the filter overflow and exceed the representable range of the filter. Clearing this option removes the scaling. This parameter applies only to IIR filters.

### Design Options

The options for each design are specific for each design method. This section does not present all of the available options for all designs and design methods. There are many more that you encounter as you select different design methods and filter specifications. The following options represent some of the most common ones available.

### Density factor

Density factor controls the density of the frequency grid over which the design method optimization evaluates your filter response function. The number of equally spaced points in the grid is the value you enter for **Density factor** times (filter order + 1).

Increasing the value creates a filter that more closely approximates an ideal equiripple filter but increases the time required to design the filter. The default value of 16 represents a reasonable trade between the accurate approximation to the ideal filter and the time to design the filter.

## Minimum phase

To design a filter that is minimum phase, select **Minimum phase**. Clearing the **Minimum phase** option removes the phase constraint—the resulting design is not minimum phase.

## Minimum order

When you select this parameter, the design method determines and designs the minimum order filter to meet your specifications. Some filters do not provide this parameter. Select Any, Even, or Odd from the drop-down list to direct the design to be any minimum order, or minimum even order, or minimum odd order.

---

**Note** Generally, **Minimum order** designs are not available for IIR filters.

---

## Match Exactly

Specifies that the resulting filter design matches either the passband or stopband or both bands when you select passband or stopband or both from the drop-down list.

## Stopband Shape

Stopband shape lets you specify how the stopband changes with increasing frequency. Choose one of the following options:

- **Flat** — Specifies that the stopband is flat. The attenuation does not change as the frequency increases.
- **Linear** — Specifies that the stopband attenuation changes linearly as the frequency increases. Change the slope of the stopband by setting **Stopband decay**.
- **1/f** — Specifies that the stopband attenuation changes exponentially as the frequency increases, where  $f$  is the frequency. Set the power (exponent) for the decay in **Stopband decay**.

### Stopband Decay

When you set Stopband shape, Stopband decay specifies the amount of decay applied to the stopband. the following conditions apply to Stopband decay based on the value of Stopband Shape:

- When you set **Stopband shape** to Flat, **Stopband decay** has no affect on the stopband.
- When you set **Stopband shape** to Linear, enter the slope of the stopband in units of dB/rad/s. filterbuilder applies that slope to the stopband.
- When you set **Stopband shape** to  $1/f$ , enter a value for the exponent  $n$  in the relation  $(1/f)^n$  to define the stopband decay. filterbuilder applies the  $(1/f)^n$  relation to the stopband to result in an exponentially decreasing stopband attenuation.

### Filter implementation

#### Structure

For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter. By default, FIR filters use direct-form structure, and IIR filters use direct-form II filters with SOS.

#### Use a System object to implement filter

Selecting this check box gives you the choice of using a system object to implement the filter. By default the check box is turned off. When the current design method or structure is not supported by a system object filter, then this check box is disabled.

## Octave Filter Design Dialog Box – Main Pane

Octave Design

Octave Design

Design an octave filter.

Save variable as:

Main | Data Types | Code Generation

Filter specifications

Order:

Bands per octave:

Frequency units:  Input Fs:

Center frequency:

Algorithm

Design method:

Scale SOS filter coefficients to reduce chance of overflow

Filter implementation

Structure:

Use a System object to implement filter

## **Filter specifications**

### **Order**

Specify filter order. Possible values are: 4, 6, 8, 10.

### **Bands per octave**

Specify the number of bands per octave. Possible values are: 1, 3, 6, 12, 24.

### **Frequency units**

Specify frequency units as Hz or kHz.

### **Input Fs**

Specify the input sampling frequency in the frequency units specified previously.

### **Center Frequency**

Select from the drop-down list of available center frequency values.

## **Algorithm**

### **Design Method**

Butterworth is the design method used for this type of filter.

### **Scale SOS filter coefficients to reduce chance of overflow**

Select the check box to scale the filter coefficients.

## **Filter implementation**

### **Structure**

Specify filter structure. Choose from:

- Direct-form I SOS
- Direct-form II SOS
- Direct-form I transposed SOS
- Direct-form II transposed SOS

## **Use a System object to implement filter**

Selecting this check box gives you the choice of using a system object to implement the filter. By default, the check box is turned off. When the current design method or structure is not supported by a system object filter, then this check box is disabled.

**Parametric Equalizer Filter Design Dialog Box – Main Pane**

Parametric Equalizer

Design a parametric equalizer.

Save variable as: Hpe View Filter Response

Main Data Types Code Generation

Filter specifications

Order mode: Minimum

Frequency specifications

Frequency constraints: Center frequency, bandwidth, passband width

Frequency units: Normalized (0 to 1)

Center frequency: 0.5 Bandwidth: 0.3

Passband width: 0.2

Gain specifications

Gain constraints: Reference, center frequency, bandwidth, passband

Gain units: dB

Reference gain: -10 Center frequency gain: 0

Bandwidth gain:  $\text{db}(\sqrt{.5})$  Passband gain: -1

Algorithm

Design method: Butterworth

Scale SOS filter coefficients to reduce chance of overflow

Filter implementation

Structure: Direct-form II SOS

Use a System object to implement filter

OK Cancel Help Apply

## Filter specifications

### Order mode

Select **Minimum** to design a minimum order filter that meets the design specifications, or **Specify** to enter a specific filter order. The order mode also affects the possible frequency constraints, which in turn limit the gain specifications. For example, if you specify a **Minimum** order filter, the available frequency constraints are:

- Center frequency, bandwidth, passband width
- Center frequency, bandwidth, stopband width

If you select **Specify**, the available frequency constraints are:

- Center frequency, bandwidth
- Center frequency, quality factor
- Shelf type, cutoff frequency, quality factor
- Shelf type, cutoff frequency, shelf slope parameter
- Low frequency, high frequency

### Order

This parameter is enabled only if the **Order mode** is set to **Specify**. Enter the filter order in this text box.

## Frequency specifications

Depending on the filter order, the possible frequency constraints change. Once you choose the frequency constraints, the input boxes in this area change to reflect the selection.

### Frequency constraints

Select the specification to represent the frequency constraints. The following options are available:

- Center frequency, bandwidth, passband width (available for minimum order only)

- Center frequency, bandwidth, stopband width (available for minimum order only)
- Center frequency, bandwidth (available for a specified order only)
- Center frequency, quality factor (available for a specified order only)
- Shelf type, cutoff frequency, quality factor (available for a specified order only)
- Shelf type, cutoff frequency, shelf slope parameter (available for a specified order only)
- Low frequency, high frequency (available for a specified order only)

### Frequency units

Select the frequency units from the available drop down list (Normalized, Hz, kHz, MHz, GHz). If Normalized is selected, then the **Input Fs** box is disabled for input.

### Input Fs

Enter the input sampling frequency. This input box is disabled for input if Normalized is selected in the **Frequency units** input box.

### Center frequency

Enter the center frequency in the units specified by the value in **Frequency units**.

### Bandwidth

The bandwidth determines the frequency points at which the filter magnitude is attenuated by the value specified as the **Bandwidth gain** in the **Gain specifications** section. By default, the **Bandwidth gain** defaults to  $\text{db}(\text{sqrt}(.5))$ , or  $-3$  dB relative to the center frequency. The **Bandwidth** property only applies when the **Frequency constraints** are: Center frequency, bandwidth, passband width, Center frequency, bandwidth, stopband width, or Center frequency, bandwidth.

## Passband width

The passband width determines the frequency points at which the filter magnitude is attenuated by the value specified as the **Passband gain** in the **Gain specifications** section. This option is enabled only if the filter is of minimum order, and the frequency constraint selected is Center frequency, bandwidth, passband width.

## Stopband width

The stopband width determines the frequency points at which the filter magnitude is attenuated by the value specified as the **Stopband gain** in the **Gain specifications** section. This option is enabled only if the filter is of minimum order, and the frequency constraint selected is Center frequency, bandwidth, stopband width.

## Low frequency

Enter the low frequency cutoff. This option is enabled only if the filter order is user specified and the frequency constraint selected is Low frequency, high frequency. The filter magnitude is attenuated by the amount specified in **Bandwidth gain**.

## High frequency

Enter the high frequency cutoff. This option is enabled only if the filter order is user specified and the frequency constraint selected is Low frequency, high frequency. The filter magnitude is attenuated by the amount specified in **Bandwidth gain**.

## Gain specifications

Depending on the filter order and frequency constraints, the possible gain constraints change. Also, once you choose the gain constraints the input boxes in this area change to reflect the selection.

## Gain constraints

Select the specification array to represent gain constraints, and remember that not all of these options are available for all configurations. The following is a list of all available options:

- Reference, center frequency, bandwidth, passband
- Reference, center frequency, bandwidth, stopband
- Reference, center frequency, bandwidth, passband, stopband
- Reference, center frequency, bandwidth

## Gain units

Specify the gain units either dB or squared. These units are used for all gain specifications in the dialog box.

## Reference gain

The reference gain determines the level to which the filter magnitude attenuates in **Gain units**. The reference gain is a *floor* gain for the filter magnitude response. For example, you may use the reference gain together with the **Center frequency gain** to leave certain frequencies unattenuated (reference gain of 0 dB) while boosting other frequencies.

## Bandwidth gain

Specifies the gain in **Gain units** at which the bandwidth is defined. This property applies only when the **Frequency constraints** specification contains a bandwidth parameter, or is Low frequency, high frequency.

## Center frequency gain

Specify the center frequency in **Gain units**

## Passband gain

The passband gain determines the level in **Gain units** at which the passband is defined. The passband is determined either by the **Passband width** value, or the **Low frequency** and **High frequency** values in the **Frequency specifications** section.

## Stopband gain

The stopband gain is the level in **Gain units** at which the stopband is defined. This property applies only when the **Order mode** is minimum and the **Frequency constraints** are Center frequency, bandwidth, stopband width.

## **Boost/cut gain**

The boost/cut gain applies only when the designing a shelving filter. Shelving filters include the `Shelf` type parameter in the **Frequency constraints** specification. The gain in the passband of the shelving filter is increased by **Boost/cut gain** dB from a *floor* gain of 0 dB.

## **Algorithm**

### **Design method**

Select the design method from the drop-down list. Different IIR design methods are available depending on the filter constraints you specify.

### **Scale SOS filter coefficients to reduce chance of overflow**

Select the check box to scale the filter coefficients.

## **Filter implementation**

### **Structure**

Select filter structure. The possible choices are:

- Direct-form I SOS
- Direct-form II SOS
- Direct-form I transposed SOS
- Direct-form II transposed SOS

### **Use a System object to implement filter**

Selecting this check box gives you the choice of using a system object to implement the filter. By default the check box is turned off. When the current design method or structure is not supported by a system object filter, then this check box is disabled.

## Peak/Notch Filter Design Dialog Box – Main Pane

Peak/Notch Design

Peak/Notch Design  
Design a peak or notch filter.

Save variable as:

Main

Filter specifications

Response:  Order:

Frequency specifications

Frequency constraints:

Frequency units:

Center frequency:  Quality factor

Magnitude specifications

Magnitude constraints:

Algorithm

Design method:

Scale SOS filter coefficients to reduce chance of overflow

Filter implementation

Structure:

Use a System object to implement filter

## **Filter specifications**

In this area you can specify whether you want to design a peaking filter or a notching filter, as well as the order of the filter.

### **Response**

Select Peak or Notch from the drop-down box.

### **Order**

Enter the filter order. The order must be even.

## **Frequency specifications**

This group of parameters allows you to specify frequency constraints and units.

### **Frequency Constraints**

Select the frequency constraints for filter specification. There are two choices as follows:

- Center frequency and quality factor
- Center frequency and bandwidth

### **Frequency units**

The frequency units are normalized by default. If you specify units other than normalized, `filterbuilder` assumes that you wish to specify an input sampling frequency, and enables this input box. The choice of frequency units are: Normalized (0 to 1), Hz, kHz, MHz, GHz.

### **Input Fs**

This input box is enabled if **Frequency units** other than Normalized (0 to 1) are specified. Enter the input sampling frequency.

### **Center frequency**

Enter the center frequency in the units you specified in **Frequency units**.

## **Quality Factor**

This input box is enabled only when Center frequency and quality factor is chosen for the **Frequency Constraints**. Enter the quality factor.

## **Bandwidth**

This input box is enabled only when Center frequency and bandwidth is chosen for the **Frequency Constraints**. Enter the bandwidth.

## **Magnitude specifications**

This group of parameters allows you to specify the magnitude constraints, as well as their values and units.

### **Magnitude Constraints**

Depending on the choice of constraints, the other input boxes are enabled or disabled. Select from four magnitude constraints available:

- Unconstrained
- Passband ripple
- Stopband attenuation
- Passband ripple and stopband attenuation

### **Magnitude units**

Select the magnitude units: either dB or squared.

### **A<sub>pass</sub>**

This input box is enabled if the magnitude constraints selected are Passband ripple or Passband ripple and stopband attenuation. Enter the passband ripple.

### **A<sub>stop</sub>**

This input box is enabled if the magnitude constraints selected are Stopband attenuation or Passband ripple and stopband attenuation. Enter the stopband attenuation.

## Algorithm

The parameters in this group allow you to specify the design method and structure that `filterbuilder` uses to implement your filter.

## Design Method

Lists all design methods available for the frequency and magnitude specifications you entered. When you change the specifications for a filter the methods available to design filters changes as well.

## Scale SOS filter coefficients to reduce chance of overflow

Selecting this parameter directs the design to scale the filter coefficients to reduce the chances that the inputs or calculations in the filter overflow and exceed the representable range of the filter. Clearing this option removes the scaling. This parameter applies only to IIR filters.

## Filter implementation

### Structure

Lists all available filter structures for the filter specifications and design method you select. The typical options are:

- Direct-form I SOS
- Direct-form II SOS
- Direct-form I transposed SOS
- Direct-form II transposed SOS

### Use a System object to implement filter

Selecting this check box gives you the choice of using a system object to implement the filter. By default the check box is turned off. When the current design method or structure is not supported by a system object filter, then this check box is disabled.

**Pulse-shaping Filter Design Dialog Box—Main Pane**

**Pulse-shaping Design**

Pulse-shaping Design  
Design a pulse-shaping filter.

Save variable as:

Main | Data Types | Code Generation

Filter specifications

Pulse shape:

Order mode:

Samples per symbol:

Filter type:

Frequency specifications

Rolloff factor:

Frequency units:

Magnitude specifications

Magnitude units:

Astop:

Algorithm

Design method:

Filter implementation

Structure:

Use a System object to implement filter

## Filter specifications

Parameters in this group enable you to specify the shape and length of the filter.

### Pulse shape

Select the shape of the impulse response from the following options:

- Raised Cosine
- Square Root Raised Cosine
- Gaussian

### Order mode

This specification is only available for raised cosine and square root raised cosine filters. For these filters, select one of the following options:

- **Minimum**— This option will result in the minimum-length filter satisfying the user-specified **Frequency specifications**.
- **Specify order**—This option allows the user to construct a raised cosine or square root cosine filter of a specified order by entering an even number in the **Order** input box. The length of the impulse response will be  $\text{Order}+1$ .
- **Specify symbols**—This option enables the user to specify the length of the impulse response in an alternative manner. If **Specify symbols** is chosen, the **Order** input box changes to the **Number of symbols** input box.

### Samples per symbol

Specify the oversampling factor. Increasing the oversampling factor guards against aliasing and improves the FIR filter approximation to the ideal frequency response. If **Order** is specified in **Number of symbols**, the filter length will be  $\text{Number of symbols} * \text{Samples per symbol} + 1$ . The product  $\text{Number of symbols} * \text{Samples per symbol}$  must be an even number.

If a Gaussian filter is specified, the filter length must be specified in **Number of symbols** and **Samples per symbol**. The product **Number of symbols\*Samples per symbol** must be an even number. The filter length will be **Number of symbols\*Samples per symbol+1**.

### **Filter Type**

This option is only available if you have the DSP System Toolbox software. Choose **Single rate**, **Decimator**, **Interpolator**, or **Sample-rate converter**. If you select **Decimator** or **Interpolator**, the decimation and interpolation factors default to the value of the **Samples per symbol**. If you select **Sample-rate converter**, the interpolation factor defaults to **Samples per symbol** and the decimation factor defaults to 3.

### **Frequency specifications**

Parameters in this group enable you to specify the frequency response of the filter. For raised cosine and square root raised cosine filters, the frequency specifications include:

#### **Rolloff factor**

The rolloff factor takes values in the range [0,1]. The smaller the rolloff factor, the steeper the transition in the stopband.

#### **Frequency units**

The frequency units are normalized by default. If you specify units other than normalized, **filterbuilder** assumes that you wish to specify an input sampling frequency, and enables this input box. The choice of frequency units are: **Normalized** (0 to 1), **Hz**, **kHz**, **MHz**, **GHz**

For a Gaussian pulse shape, the available frequency specifications are:

#### **Bandwidth-time product**

This option allows the user to specify the width of the Gaussian filter. Note that this is independent of the length of the filter. The bandwidth-time product (BT) must be a positive real number.

Smaller values of the bandwidth-time product result in larger pulse widths in time and steeper stopband transitions in the frequency response.

## Frequency units

The frequency units are normalized by default. If you specify units other than normalized, `filterbuilder` assumes that you wish to specify an input sampling frequency, and enables this input box. The choice of frequency units are: Normalized (0 to 1), Hz, kHz, MHz, GHz

## Magnitude specifications

If the **Order mode** is specified as Minimum, the **Magnitude units** may be selected from:

- dB—Specify the magnitude in decibels (default).
- Linear—Specify the magnitude in linear units.

## Algorithm

The only **Design method** available for FIR pulse-shaping filters is the Window method.

## Filter implementation

### Structure

For the filter specifications and design method you select, this parameter lists the filter structures available to implement your filter. By default, FIR filters use direct-form structure.

### Use a System object to implement filter

Selecting this check box gives you the choice of using a system object to implement the filter. By default the check box is turned off. When the current design method or structure is not supported by a system object filter, then this check box is disabled.

**Purpose**

Store CIC filter states

**Description**

`filtstates.cic` objects hold the states information for CIC filters. Once you create a CIC filter, the states for the filter are stored in `filtstates.cic` objects, and you can access them and change them as you would any property of the filter. This arrangement parallels that of the `filtstates` object that IIR direct-form I filters use (refer to `filtstates` for more information).

Each `States` property in the CIC filter comprises two properties — `Numerator` and `Comb` — that hold `filtstates.cic` objects. Within the `filtstates.cic` objects are the numerator-related and comb-related filter states. The states are column vectors, where each column represents the states for one section of the filter. For example, a CIC filter with four decimator sections and four interpolator sections has `filtstates.cic` objects that contain four columns of states each.

**Examples**

To show you the `filtstates.cic` object, create a CIC decimator and filter a signal:

```
fs = 44.1e3;           % Original sampling frequency: 44.1kHz.  
n = 0:10239;         % 10240 samples, 0.232 second long signal.  
x = sin(2*pi*1e3/fs*n); % Original signal, sinusoid at 1kHz.  
hm=mfilt.cicdecim(5,2,4);  
y=filter(hm,x);
```

`hm` has nonzero states now.

You can use `int` to see the states as 32-bit integers.

```
s=hm.states;  
int(s.Integrator)
```

**See Also**

`mfilt` | `mfilt.cicdecim` | `mfilt.cicinterp` | `filtstates`

# firband

---

**Purpose** Constrained-band equiripple FIR filter

**Syntax**

```
b = firband(n,f,a,w,c)
b = firband(n,f,a,s)
b = firband(...,'1')
b = firband(...,'minphase')
b = firband(...,'check')
b = firband(...,{lgrid})
[b,err] = firband(...)
[b,err,res] = firband(...)
```

**Description** `firband` is a minimax filter design algorithm that you use to design the following types of real FIR filters:

- Types 1-4 linear phase
  - Type 1 is even order, symmetric
  - Type 2 is odd order, symmetric
  - Type 3 is even order, antisymmetric
  - Type 4 is odd order, antisymmetric
- Minimum phase
- Maximum phase
- Minimum order (even or odd), extra ripple
- Maximal ripple
- Constrained ripple
- Single-point band (notching and peaking)
- Forced gain
- Arbitrary shape frequency response curve filters

`b = firband(n,f,a,w,c)` designs filters having constrained error magnitudes (ripples). `c` is a cell array of strings of the same length as `w`. The entries of `c` must be either 'c' to indicate that the corresponding element in `w` is a constraint (the ripple for that band cannot exceed that

value) or `'w'` indicating that the corresponding entry in `w` is a weight. There must be at least one unconstrained band — `c` must contain at least one `w` entry. For instance, Example 1 below uses a weight of one in the passband, and constrains the stopband ripple not to exceed 0.2 (about 14 dB).

A hint about using constrained values: if your constrained filter does not touch the constraints, increase the error weighting you apply to the unconstrained bands.

Notice that, when you work with constrained stopbands, you enter the stopband constraint according to the standard conversion formula for power — the resulting filter attenuation or constraint equals  $20 \cdot \log(\text{constraint})$  where *constraint* is the value you enter in the function. For example, to set 20 dB of attenuation, use a value for the constraint equal to 0.1. This applies to constrained stopbands only.

`b = fircband(n, f, a, s)` is used to design filters with special properties at certain frequency points. `s` is a cell array of strings and must be the same length as `f` and `a`. Entries of `s` must be one of:

- `'n'` — normal frequency point.
- `'s'` — single-point band. The frequency band is given by a single point. You must specify the corresponding gain at this frequency point in `a`.
- `'f'` — forced frequency point. Forces the gain at the specified frequency band to be the value specified.
- `'i'` — indeterminate frequency point. Use this argument when bands abut one another (no transition region).

`b = fircband(..., '1')` designs a type 1 filter (even-order symmetric). You could also specify type 2 (odd-order symmetric), type 3 (even-order antisymmetric), or type 4 (odd-order antisymmetric) filters. Note there are restrictions on `a` at `f = 0` or `f = 1` for types 2, 3, and 4.

`b = fircband(..., 'minphase')` designs a minimum-phase FIR filter. There is also `'maxphase'`.

# fircband

---

`b = fircband(..., 'check')` produces a warning when there are potential transition-region anomalies in the filter response.

`b = fircband(..., {lgrid})`, where `{lgrid}` is a scalar cell array containing an integer, controls the density of the frequency grid.

`[b,err] = fircband(...)` returns the unweighted approximation error magnitudes. `err` has one element for each independent approximation error.

`[b,err,res] = fircband(...)` returns a structure `res` of optional results computed by `fircband`, and contains the following fields:

Structure Field	Contents
<code>res.fgrid</code>	Vector containing the frequency grid used in the filter design optimization
<code>res.des</code>	Desired response on <code>fgrid</code>
<code>res.wt</code>	Weights on <code>fgrid</code>
<code>res.h</code>	Actual frequency response on the frequency grid
<code>res.error</code>	Error at each point (desired response - actual response) on the frequency grid
<code>res.iextr</code>	Vector of indices into <code>fgrid</code> of external frequencies
<code>res.fextr</code>	Vector of extremely frequencies
<code>res.order</code>	Filter order
<code>res.edgecheck</code>	Transition-region anomaly check. One element per band edge. Element values have the following meanings: 1 = OK , 0 = probable transition-region anomaly , -1 = edge not checked. Computed when you specify the 'check' input option in the function syntax.

Structure Field	Contents
res.iterations	Number of Remez iterations for the optimization
res.evals	Number of function evaluations for the optimization

## Examples


Two examples of designing filters with constrained bands.

### Example 1

design a 12th-order lowpass filter with a constraint on the filter response.

```
b = fircband(12,[0 0.4 0.5 1], [1 1 0 0], ...  
[1 0.2], {'w' 'c'});
```

Using `fvtool` to display the result `b` shows you the response of the filter you designed.




## Example 2

design two filters of different order with the stopband constrained to 60 dB. Use excess order (80) in the second filter to improve the passband ripple.

```
b1=firband(60,[0 .2 .25 1],[1 1 0 0],...  
[1 .001],{'w','c'});  
b2=firband(80,[0 .2 .25 1],[1 1 0 0],...  
[1 .001],{'w','c'});  
hfvt = fvtool(b1,1,b2,1);  
legend(hfvt,'Filter Order 60','Filter Order 80');
```

To set the stopband constraint to 60 dB, enter 0.001, since  $20 \cdot \log(0.001) = -60$ , or 60 dB of signal attenuation.

**See Also**

[firceqrip](#) | [firgr](#) | [firls](#) | [firpm](#)

# fireqint

---

**Purpose** Equiripple FIR interpolators

**Syntax**

```
b = fireqint(n,1,alpha)
b = fireqint(n,1,alpha,w)
b = fireqint('minorder',1,alpha,r)
b = fireqint({'minorder',initord},1,alpha,r)
```

**Description** `b = fireqint(n,1,alpha)` designs an FIR equiripple filter useful for interpolating input signals. `n` is the filter order and it must be an integer. `1`, also an integer, is the interpolation factor. `alpha` is the bandlimitedness factor, identical to the same feature in `intfilt`.

`alpha` is inversely proportional to the transition bandwidth of the filter. It also affects the bandwidth of the don't-care regions in the stopband. Specifying `alpha` allows you to control how much of the Nyquist interval your input signal occupies. This can be beneficial for signals to be interpolated because it allows you to increase the transition bandwidth without affecting the interpolation, resulting in better stopband attenuation for a given `1`. If you set `alpha` to `1`, `fireqint` assumes that your signal occupies the entire Nyquist interval. Setting `alpha` to a value less than one allows for don't-care regions in the stopband. For example, if your input occupies half the Nyquist interval, you could set `alpha` to `0.5`.

The signal to be interpolated is assumed to have zero (or negligible) power in the frequency band between  $(\alpha \cdot \pi)$  and  $\pi$ . `alpha` must therefore be a positive scalar between `0` and `1`. `fireqint` treat such bands as don't-care regions for assessing filter design.

`b = fireqint(n,1,alpha,w)` allows you to specify a vector of weights in `w`. The number of weights required in `w` is given by `1 + floor(1/2)`. The weights in `w` are applied to the passband ripple and stopband attenuations. Using weights (values between `0` and `1`) enables you to specify different attenuations in different parts of the stopband, as well as providing the ability to adjust the compromise between passband ripple and stopband attenuation.

`b = fireqint('minorder',1,alpha,r)` allows you to design a minimum-order filter that meets the design specifications. `r` is a vector

of maximum deviations or ripples from the ideal filter magnitude response. When you use the input argument **minorder**, you must provide the vector **r**. The number of elements required in **r** is given by  $1 + \text{floor}(1/2)$ .


`b = fireqint({'minorder',initord},l,alpha,r)` adds the argument **initord** so you can provide an initial estimate of the filter order. Any positive integer is valid here. Again, you must provide **r**, the vector of maximum deviations or ripples, from the ideal filter magnitude response.

## Examples

Design a minimum order interpolation filter for  $l = 6$  and  $\alpha = 0.8$ . A vector of ripples must be supplied with the input argument **minorder**.

```
b = fireqint('minorder',6,.8,[0.01 .1 .05 .02]);  
hm = mfilt.firinterp(6,b); % Create a polyphase interpolator filter  
zerophase(hm);
```

Here is the resulting plot of the zerophase response for **hm**.



For `hm`, the minimum order filter with the requested design specifications, here is the filter information.

`hm =`

```
FilterStructure: 'Direct-Form FIR Polyphase Interpolator'  
Arithmetic: 'double'  
Numerator: [1x70 double]  
InterpolationFactor: 6  
PersistentMemory: false
```

## See Also

`firgr` | `firhalfband` | `firls` | `firnyquist` | `mfilt` | `intfilt`

**Purpose** Constrained equiripple FIR filter

**Syntax**

```
B = firceqrip(n,Fo,DEV)
B = firceqrip(...,'slope',r)
B = firceqrip(...,'passedge')
B = firceqrip(...,'stopedge')
B = firceqrip(...,'high')
B = firceqrip(...,'min')
B = firceqrip(...,'invsinc',C)
B = firceqrip(...,'invdiric',C)
```

**Description** `B = firceqrip(n,Fo,DEV)` designs an order  $n$  filter (filter length equal  $n + 1$ ) lowpass FIR filter with linear phase.

`firceqrip` produces the same equiripple lowpass filters that `firpm` produces using the Parks-McClellan algorithm. The difference is how you specify the filter characteristics for the function.

The input argument `Fo` specifies the frequency at the upper edge of the passband in normalized frequency ( $0 < Fo < 1$ ). The two-element vector `dev` specifies the peak or maximum error allowed in the passband and stopbands. Enter `[d1 d2]` for `dev` where `d1` sets the passband error and `d2` sets the stopband error.

`B = firceqrip(...,'slope',r)` uses the input keyword 'slope' and input argument `r` to design a filter with a nonequiripple stopband. `r` is specified as a positive constant and determines the slope of the stopband attenuation in dB/normalized frequency. Greater values of `r` result in increased stopband attenuation in dB/normalized frequency.

`B = firceqrip(...,'passedge')` designs a filter where `Fo` specifies the frequency at which the passband starts to rolloff.

`B = firceqrip(...,'stopedge')` designs a filter where `Fo` specifies the frequency at which the stopband begins.

`B = firceqrip(...,'high')` designs a high pass FIR filter instead of a lowpass filter.

`B = firceqrip(...,'min')` designs a minimum-phase filter.

`B = firceqrip(..., 'invsinc', C)` designs a lowpass filter whose magnitude response has the shape of an inverse sinc function. This may be used to compensate for sinc-like responses in the frequency domain such as the effect of the zero-order hold in a D/A converter. The amount of compensation in the passband is controlled by `C`, which is specified as a scalar or two-element vector. The elements of `C` are specified as follows:

- If `C` is supplied as a real-valued scalar or the first element of a two-element vector, `firceqrip` constructs a filter with a magnitude response of  $1/\text{sinc}(C \cdot \pi \cdot F)$  where `F` is the normalized frequency.
- If `C` is supplied as a two-element vector, the inverse-sinc shaped magnitude response is raised to the positive power `C(2)`. If we set `P=C(2)`, `firceqrip` constructs a filter with a magnitude response  $1/\text{sinc}(C \cdot \pi \cdot F)^P$ .

If this FIR filter is used with a cascaded integrator-comb (CIC) filter, setting `C(2)` equal to the number of stages compensates for the multiplicative effect of the successive sinc-like responses of the CIC filters.

---

**Note** Since the value of the inverse sinc function becomes unbounded at  $C=1/F$ , the value of `C` should be greater the reciprocal of the passband edge frequency. This can be expressed as  $F_0 < 1/C$ . For users familiar with CIC decimators, `C` is equal to 1/2 the product of the differential delay and decimation factor.

---

`B = firceqrip(..., 'invdiric', C)` designs a lowpass filter with a passband that has the shape of an inverse Dirichlet sinc function. The frequency response of the inverse Dirichlet sinc function is given by

$$\left\{ rC \left( \frac{\sin(f/2r)}{\sin(Cf/2)} \right) \right\}^p$$

where  $C$ ,  $r$ , and  $p$  are scalars. The input  $C$  can be a scalar or vector containing 2 or 3 elements. If  $C$  is a scalar,  $p$  and  $r$  equal 1. If  $C$  is a two-element vector, the first element is  $C$  and the second element is  $p$ ,  $[C \ p]$ . If  $C$  is a three-element vector, the third element is  $r$ ,  $[C \ p \ r]$ .

## Examples


To introduce a few of the variations on FIR filters that you design with `firceqrip`, these five examples cover both the default syntax `b = firceqrip(n,wo,del)` and some of the optional input arguments. For each example, the input arguments  $n$ ,  $wo$ , and  $del$  remain the same.

### Example 1

Design an order = 30 FIR filter.

```
b = firceqrip(30,0.4,[0.05 0.03]); fvtool(h)
```

When the plot appears in the Filter Visualization Tool window, select **Analysis > Overlay Analysis > Phase Response**. Then select **View > Full View**. This displays the following plot.



## Example 2

Design an order = 30 FIR filter with the `stopedge` keyword to define the response at the edge of the filter stopband.

```
b = firceqrip(30,0.4,[0.05 0.03],'stopedge'); fvtool(h)
```

## Example 3

Design an order = 30 FIR filter with the `slope` keyword and `r = 20`.

```
b = firceqrip(30,0.4,[0.05 0.03],'slope',20,'stopedge'); fvtool(h)
```


## Example 4

Design an order = 30 FIR filter defining the stopband and specifying that the resulting filter is minimum phase with the `min` keyword.

```
b = firceqrip(30,0.4,[0.05 0.03],'stopedge','min'); fvtool(h)
```

Comparing this filter to the filter in Example 1, the cutoff frequency  $\omega_0 = 0.4$  now applies to the edge of the stopband rather than the point at which the frequency response magnitude is 0.5.

Viewing the zero-pole plot shown here reveals this is a minimum phase FIR filter — the zeros lie on or inside the unit circle,  $z = 1$ .




### Example 5

Design an order = 30 FIR filter with the `invsinc` keyword to shape the filter passband with an inverse sinc function.

```
b = firceqrip(30,0.4,[0.05 0.03],'invsinc',[2 1.5]); fvtool(h)
```

With the inverse sinc function being applied defined as  $1/\text{sinc}(2*w)^{1.5}$ , the figure shows the reshaping of the passband that results from using the **`invsinc`** keyword option, and entering `c` as the two-element vector `[2 1.5]`.



## Inverse-Dirichlet-Sinc-Shaped Passband

Design two order 30 constrained equiripple FIR filters with inverse-Dirichlet-sinc-shaped passbands. The cutoff frequency in both designs is  $\pi/4$  radians/sample. Set  $C=1$  in one design  $C=2$  in the second design. The maximum passband and stopband ripple is 0.05. Set  $p=1$  in one design and  $p=2$  in the second design.

Design the filters.

```
b1 = firceqrip(30,0.25,[0.05 0.05],'invdiric',[1 1]);  
b2 = firceqrip(30,0.25,[0.05 0.05],'invdiric',[2 2]);
```

Obtain the filter frequency responses using `freqz`. Plot the magnitude responses.

```
[h1,~] = freqz(b1,1);  
[h2,w] = freqz(b2,1);  
plot(w,abs(h1)); hold on;  
plot(w,abs(h2),'r');  
axis([0 pi 0 1.5]);  
xlabel('Radians/sample');
```

```
ylabel('Magnitude');  
legend('C=1 p=1', 'C=2 p=2');
```

Inspect the stopband ripple in the design with  $C=1$  and  $p=1$ . The constrained design sets the maximum ripple to be 0.05. Zoom in on the stopband from the cutoff frequency of  $\pi/4$  radians/sample to  $3\pi/4$  radians/sample.

```
figure;  
plot(w,abs(h1));  
set(gca,'xlim',[pi/4 3*pi/4]);  
grid on;
```

## See Also

```
diric | fdesign.decimator | firhalfband | firnyquist | firgr  
| ifir | iirgrpdelay | iirlpnorm | iirlpnormc | fircls | firls  
| firpm | sinc
```

# fircls

---

**Purpose** FIR Constrained Least Squares filter

**Syntax**

```
hd = design(d, 'fircls')
hd = design(d, 'fircls', 'FilterStructure', value)
hd = design(d, 'fircls', 'PassbandOffset', value)
hd = design(d, 'fircls', 'zerophase', value)
```

**Description** `hd = design(d, 'fircls')` designs a FIR Constrained Least Squares (CLS) filter, `hd`, from a filter specifications object, `d`.

`hd = design(d, 'fircls', 'FilterStructure', value)` where `value` is one of the following filter structures:

- 'dffir', a discrete-time, direct-form FIR filter (the default value)
- 'dffirt', a discrete-time, direct-form FIR transposed filter
- 'dfsymfir', a discrete-time, direct-form symmetric FIR filter
- 'fftfir', a discrete-time, overlap-add, FIR filter

`hd = design(d, 'fircls', 'PassbandOffset', value)` where `value` sets the passband band gain in dB. The `PassbandOffset` and `Ap` values affect the upper and lower approximation bound in the passband as follows:

- Lower bound =  $(\text{PassbandOffset} - A_p/2)$
- Upper bound =  $(\text{PassbandOffset} + A/2)$

For bandstop filters, the `PassbandOffset` is a vector of length two that specifies the first and second passband gains. The `PassbandOffset` value defaults to 0 for lowpass, highpass and bandpass filters. The `PassbandOffset` value defaults to [0 0] for bandstop filters.

`hd = design(d, 'fircls', 'zerophase', value)` where `value` is either 'true' ('1') or 'false' ('0'). If `zerophase` is true, the lower approximation bound in the stopband is forced to zero (i.e., the filter has a zero phase response). `Zerophase` is false (0) by default.

To determine the available design options, use `designopts` with the specification object and the design method as input arguments as shown.

```
designopts(d,'fircls')
```


For complete help about using `fircls`, refer to the command line help system. For example, to get specific information about using `fircls` with `d`, the specification object, enter the following at the MATLAB prompt.

```
help(d,'fircls')
```

## Examples

The following example designs a constrained least-squares FIR lowpass filter.

```
h = fdesign.lowpass('n,fc,ap,ast', 50, 0.3, 2, 30);
Hd = design(h, 'fircls');
fvtool(Hd)
```




The following example constructs a constrained least-squares FIR bandpass filter.

```
d = fdesign.bandpass('N,Fc1,Fc2,Ast1,Ap,Ast2', ...
```

# fircls

```
30,0.4,0.6,60,1,60);  
Hd = design(d, 'fircls');  
fvtool(Hd)
```



**See Also**

[cheby1](#) | [cheby2](#) | [ellip](#)

**Purpose**

Parks-McClellan FIR filter

**Syntax**

```
b = firgr(n,f,a,w)
b = firgr(n,f,a,'hilbert')
b = firgr(m,f,a,r),
b = firgr({m,ni},f,a,r)
b = firgr(n,f,a,w,e)
b = firgr(n,f,a,s)
b = firgr(n,f,a,s,w,e)
b = firgr(...,'1')
b = firgr(...,'minphase')
b = firgr(...,'check')
b = firgr(...,{lgrid}),
[b,err] = firgr(...)
[b,err,res] = firgr(...)
b = firgr(n,f,fresp,w)
b = firgr(n,f,{fresp,p1,p2,...},w)
b = firgr(n,f,a,w)
```

**Description**

`firgr` is a minimax filter design algorithm you use to design the following types of real FIR filters:

- Types 1-4 linear phase:
  - Type 1 is even order, symmetric
  - Type 2 is odd order, symmetric
  - Type 3 is even order, antisymmetric
  - Type 4 is odd order, antisymmetric
- Minimum phase
- Maximum phase
- Minimum order (even or odd)
- Extra ripple
- Maximal ripple

- Constrained ripple
- Single-point band (notching and peaking)
- Forced gain
- Arbitrary shape frequency response curve filters

`b = firgr(n,f,a,w)` returns a length  $n+1$  linear phase FIR filter which has the best approximation to the desired frequency response described by `f` and `a` in the minimax sense. `w` is a vector of weights, one per band. When you omit `w`, all bands are weighted equally. For more information on the input arguments, refer to `firpm` in *Signal Processing Toolbox User's Guide*.

`b = firgr(n,f,a,'hilbert')` and `b = firgr(n,f,a,'differentiator')` design FIR Hilbert transformers and differentiators. For more information on designing these filters, refer to `firpm` in *Signal Processing Toolbox User's Guide*.

`b = firgr(m,f,a,r)`, where `m` is one of 'minorder', 'mineven' or 'minodd', designs filters repeatedly until the minimum order filter, as specified in `m`, that meets the specifications is found. `r` is a vector containing the peak ripple per frequency band. You must specify `r`. When you specify 'mineven' or 'minodd', the minimum even or odd order filter is found.

`b = firgr({m,ni},f,a,r)` where `m` is one of 'minorder', 'mineven' or 'minodd', uses `ni` as the initial estimate of the filter order. `ni` is optional for common filter designs, but it must be specified for designs in which `firpmord` cannot be used, such as while designing differentiators or Hilbert transformers.

`b = firgr(n,f,a,w,e)` specifies independent approximation errors for different bands. Use this syntax to design extra ripple or maximal ripple filters. These filters have interesting properties such as having the minimum transition width. `e` is a cell array of strings specifying the approximation errors to use. Its length must equal the number of bands. Entries of `e` must be in the form 'e#' where # indicates which approximation error to use for the corresponding band. For example, when `e = {'e1', 'e2', 'e1'}`, the first and third bands use the same

approximation error 'e1' and the second band uses a different one 'e2'. Note that when all bands use the same approximation error, such as {'e1', 'e1', 'e1', ...}, it is equivalent to omitting e, as in `b = firgr(n,f,a,w)`.

`b = firgr(n,f,a,s)` is used to design filters with special properties at certain frequency points. `s` is a cell array of strings and must be the same length as `f` and `a`. Entries of `s` must be one of:

- 'n' — normal frequency point.
- 's' — single-point band. The frequency “band” is given by a single point. The corresponding gain at this frequency point must be specified in `a`.
- 'f' — forced frequency point. Forces the gain at the specified frequency band to be the value specified.
- 'i' — indeterminate frequency point. Use this argument when adjacent bands abut one another (no transition region).

For example, the following command designs a bandstop filter with zero-valued single-point stop bands (notches) at 0.25 and 0.55.

```
b = firgr(42,[0 0.2 0.25 0.3 0.5 0.55 0.6 1],...
[1 1 0 1 1 0 1 1],{'n' 'n' 's' 'n' 'n' 's' 'n' 'n'})
```

`b = firgr(82,[0 0.055 0.06 0.1 0.15 1],[0 0 0 0 1 1],...{'n' 'i' 'f' 'n' 'n' 'n'})` designs a highpass filter with the gain at 0.06 forced to be zero. The band edge at 0.055 is indeterminate since the first two bands actually touch. The other band edges are normal.

`b = firgr(n,f,a,s,w,e)` specifies weights and independent approximation errors for filters with special properties. The weights and properties are included in vectors `w` and `e`. Sometimes, you may need to use independent approximation errors to get designs with forced values to converge. For example,

```
b = firgr(82,[0 0.055 0.06 0.1 0.15 1], [0 0 0 0 1 1],...
{'n' 'i' 'f' 'n' 'n' 'n'}, [10 1 1] ,{'e1' 'e2' 'e3'});
```

`b = firgr(..., '1')` designs a type 1 filter (even-order symmetric). You can specify type 2 (odd-order symmetric), type 3 (even-order antisymmetric), and type 4 (odd-order antisymmetric) filters as well. Note that restrictions apply to `a` at `f = 0` or `f = 1` for FIR filter types 2, 3, and 4.

`b = firgr(..., 'minphase')` designs a minimum-phase FIR filter. You can use the argument `'maxphase'` to design a maximum phase FIR filter.

`b = firgr(..., 'check')` returns a warning when there are potential transition-region anomalies.

`b = firgr(..., {lgrid})`, where `{lgrid}` is a scalar cell array. The value of the scalar controls the density of the frequency grid by setting the number of samples used along the frequency axis.

`[b,err] = firgr(...)` returns the unweighted approximation error magnitudes. `err` contains one element for each independent approximation error returned by the function.

`[b,err,res] = firgr(...)` returns the structure `res` comprising optional results computed by `firgr`. `res` contains the following fields.

Structure Field	Contents
<code>res.fgrid</code>	Vector containing the frequency grid used in the filter design optimization
<code>res.des</code>	Desired response on <code>fgrid</code>
<code>res.wt</code>	Weights on <code>fgrid</code>
<code>res.h</code>	Actual frequency response on the frequency grid
<code>res.error</code>	Error at each point (desired response - actual response) on the frequency grid
<code>res.iextr</code>	Vector of indices into <code>fgrid</code> of external frequencies
<code>res.fextr</code>	Vector of external frequencies

Structure Field	Contents
res.order	Filter order
res.edgecheck	Transition-region anomaly check. One element per band edge. Element values have the following meanings: 1 = OK, 0 = probable transition-region anomaly, -1 = edge not checked. Computed when you specify the 'check' input option in the function syntax.
res.iterations	Number of s iterations for the optimization
res.evals	Number of function evaluations for the optimization

`firgr` is also a “function function,” allowing you to write a function that defines the desired frequency response.

`b = firgr(n,f,fresp,w)` returns a length  $N + 1$  FIR filter which has the best approximation to the desired frequency response as returned by the user-defined function `fresp`. Use the following `firgr` syntax to call `fresp`:

```
[dh,dw] = fresp(n,f,gf,w)
```

where:

- `fresp` is the string variable that identifies the function that you use to define your desired filter frequency response.
- `n` is the filter order.
- `f` is the vector of frequency band edges which must appear monotonically between 0 and 1, where 1 is one-half of the sampling frequency. The frequency bands span  $f(k)$  to  $f(k+1)$  for  $k$  odd. The intervals  $f(k+1)$  to  $f(k+2)$  for  $k$  odd are “transition bands” or “don’t care” regions during optimization.

- `gf` is a vector of grid points that have been chosen over each specified frequency band by `firgr`, and determines the frequencies at which `firgr` evaluates the response function.
- `w` is a vector of real, positive weights, one per band, for use during optimization. `w` is optional in the call to `firgr`. If you do not specify `w`, it is set to unity weighting before being passed to `fresp`.
- `dh` and `dw` are the desired frequency response and optimization weight vectors, evaluated at each frequency in grid `gf`.

`firgr` includes a predefined frequency response function named `'firpmfrf2'`. You can write your own based on the simpler `'firpmfrf'`. See the help for `private/firpmfrf` for more information.

`b = firgr(n,f,{fresp,p1,p2,...},w)` specifies optional arguments `p1`, `p2`,..., `pn` to be passed to the response function `fresp`.

`b = firgr(n,f,a,w)` is a synonym for `b = firgr(n,f{'firpmfrf2',a},w)`, where `a` is a vector containing your specified response amplitudes at each band edge in `f`. By default, `firgr` designs symmetric (even) FIR filters. `'firpmfrf2'` is the predefined frequency response function. If you do not specify your own frequency response function (the `fresp` string variable), `firgr` uses `'firpmfrf2'`.

`b = firgr(...,'h')` and `b = firgr(...,'d')` design antisymmetric (odd) filters. When you omit the `'h'` or `'d'` arguments from the `firgr` command syntax, each frequency response function `fresp` can tell `firgr` to design either an even or odd filter. Use the command syntax `sym = fresp('defaults',{n,f,[],w,p1,p2,...})`.

`firgr` expects `fresp` to return `sym = 'even'` or `sym = 'odd'`. If `fresp` does not support this call, `firgr` assumes even symmetry.

For more information about the input arguments to `firgr`, refer to `firpm`.

## Examples

These examples demonstrate some filters you might design using `firgr`.

### Example 1

design an FIR filter with two single-band notches at 0.25 and 0.55

```
b1 = firgr(42,[0 0.2 0.25 0.3 0.5 0.55 0.6 1],[1 1 0 1 1 0 1 1],...  
{'n' 'n' 's' 'n' 'n' 's' 'n' 'n'});
```

### Example 2

design a highpass filter whose gain at 0.06 is forced to be zero. The gain at 0.055 is indeterminate since it should about the band.

```
b2 = firgr(82,[0 0.055 0.06 0.1 0.15 1],[0 0 0 0 1 1],...  
{'n' 'i' 'f' 'n' 'n' 'n'});
```

### Example 3


design a second highpass filter with forced values and independent approximation errors.

```
b3 = firgr(82,[0 0.055 0.06 0.1 0.15 1], [0 0 0 0 1 1], ...  
{'n' 'i' 'f' 'n' 'n' 'n'}, [10 1 1] ,{'e1' 'e2' 'e3'});
```

Use the filter visualization tool to view the results of the filters created in these examples.

```
fvtool(b1,1,b2,1,b3,1)
```

Here is the figure from FVTool.



## References

Shpak, D.J. and A. Antoniou, "A generalized Remez method for the design of FIR digital filters," *IEEE Trans. Circuits and Systems*, pp. 161-174, Feb. 1990.

## See Also

`butter` | `cheby1` | `cheby2` | `ellip` | `freqz` | `filter` | `firls` | `fircls` | `firpm`

**Purpose**

Halfband FIR filter

**Syntax**

```
b = firhalfband(n,fp)
b = firhalfband(n,win)
b = firhalfband(n,dev,'dev')
b = firhalfband('minorder',fp,dev)
b = firhalfband('minorder',fp,dev,'kaiser')
b = firhalfband(...,'high')
b = firhalfband(...,'minphase')
```

**Description**

`b = firhalfband(n,fp)` designs a lowpass halfband FIR filter of order `n` with an equiripple characteristic. `n` must be an even integer. `fp` determines the passband edge frequency, and it must satisfy  $0 < fp < 1/2$ , where  $1/2$  corresponds to  $\pi/2$  rad/sample.

`b = firhalfband(n,win)` designs a lowpass Nth-order filter using the truncated, windowed-impulse response method instead of the equiripple method. `win` is an `n+1` length vector. The ideal impulse response is truncated to length `n + 1`, and then multiplied point-by-point with the window specified in `win`.

`b = firhalfband(n,dev,'dev')` designs an Nth-order lowpass halfband filter with an equiripple characteristic. Input argument `dev` sets the value for the maximum passband and stopband ripple allowed.

`b = firhalfband('minorder',fp,dev)` designs a lowpass minimum-order filter, with passband edge `fp`. The peak ripple is constrained by the scalar `dev`. This design uses the equiripple method.

`b = firhalfband('minorder',fp,dev,'kaiser')` designs a lowpass minimum-order filter, with passband edge `fp`. The peak ripple is constrained by the scalar `dev`. This design uses the Kaiser window method.

`b = firhalfband(...,'high')` returns a highpass halfband FIR filter.

`b = firhalfband(...,'minphase')` designs a minimum-phase FIR filter such that the filter is a spectral factor of a halfband filter (recall that `h = conv(b,flip1r(b))` is a halfband filter). This can be useful for designing perfect reconstruction, two-channel FIR filter

# firhalfband


banks. The **minphase** option for `firhalfband` is not available for the window-based halfband filter designs — `b = firhalfband(n,win)` and `b = firhalfband('minorder',fp,dev,'kaiser')`.

In the minimum phase cases, the filter order must be odd.

## Examples


This example designs a minimum order halfband filter with specified maximum ripple:

```
b = firhalfband('minorder',.45,0.0001);  
h = dfilt.dfsymfir(b);  
impz(b) % Impulse response is zero for every other sample
```



The next example designs a halfband filter with specified maximum ripple of 0.0001 dB in the pass and stop bands.

```
b = firhalfband(98,0.0001,'dev');  
h = mfilter.firdecim(2,b); % Create a polyphase decimator  
freqz(h); % 80 dB attenuation in the stopband
```



## References

Saramaki, T, "Finite Impulse Response Filter Design," *Handbook for Digital Signal Processing*. S.K. Mitra and J.F. Kaiser Eds. Wiley-Interscience, N.Y., 1993, Chapter 4.

## See Also

`firnyquist` | `firgr` | `fir1` | `firls` | `firpm`

# firlp2lp

---

<b>Purpose</b>	Convert FIR Type I lowpass to FIR Type 1 lowpass with inverse bandwidth
<b>Syntax</b>	<code>g = firlp2lp(b)</code>
<b>Description</b>	<p><code>g = firlp2lp(b)</code> transforms the Type I lowpass FIR filter <code>b</code> with zero-phase response <math>H_r(w)</math> to a Type I lowpass FIR filter <code>g</code> with zero-phase response <math>[1 - H_r(\pi-w)]</math>.</p> <p>When <code>b</code> is a narrowband filter, <code>g</code> will be a wideband filter and vice versa. The passband and stopband ripples of <code>g</code> will be equal to the stopband and passband ripples of <code>b</code>.</p>
<b>Examples</b>	<p>Overlay the original narrowband lowpass and the resulting wideband lowpass</p> <pre>b = firgr(36,[0 .2 .25 1],[1 1 0 0],[1 5]); zerophase(b); hold on h = firlp2lp(b); zerophase(h);</pre>
<b>References</b>	Saramaki, T, Finite Impulse Response Filter Design, <i>Handbook for Digital Signal Processing</i> . S.K. Mitra and J.F. Kaiser Eds. Wiley-Interscience, N.Y., 1993, Chapter 4.
<b>See Also</b>	<code>firlp2hp</code>   <code>zerophase</code>

**Purpose**

Convert FIR lowpass filter to Type I FIR highpass filter

**Syntax**

```
g = firlp2hp(b)
g = firlp2hp(b, 'narrow')
g = firlp2hp(b, 'wide')
```

**Description**

`g = firlp2hp(b)` transforms the lowpass FIR filter `b` into a Type I highpass FIR filter `g` with zero-phase response  $H_r(\pi-w)$ . Filter `b` can be any FIR filter, including a nonlinear-phase filter.

The passband and stopband ripples of `g` will be equal to the passband and stopband ripples of `b`.

`g = firlp2hp(b, 'narrow')` transforms the lowpass FIR filter `b` into a Type I narrow band highpass FIR filter `g` with zero-phase response  $H_r(\pi-w)$ . `b` can be any FIR filter, including a nonlinear-phase filter.


`g = firlp2hp(b, 'wide')` transforms the Type I lowpass FIR filter `b` with zero-phase response  $H_r(w)$  into a Type I wide band highpass FIR filter `g` with zero-phase response  $1 - H_r(w)$ . Note the restriction that `b` must be a Type I linear-phase filter.

For this case, the passband and stopband ripples of `g` will be equal to the stopband and passband ripples of `b`.

**Examples**

Overlay the original narrowband lowpass (the prototype filter) and the post-conversion narrowband highpass and wideband highpass filters to compare and assess the conversion. The following plot shows the results.

```
b = firgr(36,[0 .2 .25 1],[1 1 0 0],[1 3]);
h = firlp2hp(b);
hfvtool(b,1,h,1);
legend(hfvtool,'Prototype Lowpass','Narrowband Highpass');
```



## References

Saramaki, T, Finite Impulse Response Filter Design, *Handbook for Digital Signal Processing* Mitra, S.K. and J.F. Kaiser Eds. Wiley-Interscience, N.Y., 1993, Chapter 4.

## See Also

firlp2lp | zerophase

**Purpose** Least P-norm optimal FIR filter

**Syntax**

```
b = firlpnorm(n,f,edges,a)
b = firlpnorm(n,f,edges,a,w)
b = firlpnorm(n,f,edges,a,w,p)
b = firlpnorm(n,f,edges,a,w,p,dens)
b = firlpnorm(n,f,edges,a,w,p,dens,initnum)
b = firlpnorm(...,'minphase')
[b,err] = firlpnorm(...)
```

**Description** `b = firlpnorm(n,f,edges,a)` returns a filter of numerator order `n` which represents the best approximation to the frequency response described by `f` and `a` in the least-Pth norm sense. `P` is set to 128 by default, which is essentially equivalent to the infinity norm. Vector `edges` specifies the band-edge frequencies for multiband designs. `firlpnorm` uses an unconstrained quasi-Newton algorithm to design the specified filter.

`f` and `a` must have the same number of elements, which can exceed the number of elements in `edges`. This lets you specify filters with any gain contour within each band. However, the frequencies in `edges` must also be in vector `f`. Always use `freqz` to check the resulting filter.

---

**Note** `firlpnorm` uses a nonlinear optimization routine that may not converge in some filter design cases. Furthermore the algorithm is not well-suited for certain large-order (order > 100) filter designs.

---

`b = firlpnorm(n,f,edges,a,w)` uses the weights in `w` to weight the error. `w` has one entry per frequency point (the same length as `f` and `a`) which tells `firlpnorm` how much emphasis to put on minimizing the error in the vicinity of each frequency point relative to the other points. For example,

```
b = firlpnorm(20,[0 .15 .4 .5 1],[0 .4 .5 1],...
[1 1.6 1 0 0],[1 1 1 10 10])
```

designs a lowpass filter with a peak of 1.6 within the passband, and with emphasis placed on minimizing the error in the stopband.

`b = firlpnorm(n,f,edges,a,w,p)` where `p` is a two-element vector [`pmin pmax`] lets you specify the minimum and maximum values of `p` used in the least- $p$ th algorithm. Default is [2 128] which essentially yields the L-infinity, or Chebyshev, norm. `pmin` and `pmax` should be even numbers. The design algorithm starts optimizing the filter with `pmin` and moves toward an optimal filter in the `pmax` sense. When `p` is the string `'inspect'`, `firlpnorm` does not optimize the resulting filter. You might use this feature to inspect the initial zero placement.

`b = firlpnorm(n,f,edges,a,w,p,dens)` specifies the grid density `dens` used in the optimization. The number of grid points is [`dens*(n+1)`]. The default is 20. You can specify `dens` as a single-element cell array. The grid is equally spaced.

`b = firlpnorm(n,f,edges,a,w,p,dens,initnum)` lets you determine the initial estimate of the filter numerator coefficients in vector `initnum`. This can prove helpful for difficult optimization problems. The pole-zero editor in Signal Processing Toolbox software can be used for generating `initnum`.

`b = firlpnorm(...,'minphase')` where string `'minphase'` is the last argument in the argument list generates a minimum-phase FIR filter. By default, `firlpnorm` design mixed-phase filters. Specifying input option `'minphase'` causes `firlpnorm` to use a different optimization method to design the minimum-phase filter. As a result of the different optimization used, the minimum-phase filter can yield slightly different results.

`[b,err] = firlpnorm(...)` returns the least- $p$ th approximation error `err`.

## Examples

To demonstrate `firlpnorm`, here are two examples — the first designs a lowpass filter and the second a highpass, minimum-phase filter.

```
% Lowpass filter with a peak of 1.4 in the passband.  
b = firlpnorm(22,[0 .15 .4 .5 1],[0 .4 .5 1],[1 1.4 1 0 0],...
```


```
[1 1 1 2 2]);
fvtool(b)
```

From the figure you see the resulting filter is lowpass, with the desired 1.4 peak in the passband (notice the 1.4 specified in vector a).


Now for the minimum-phase filter.

```
% Highpass minimum-phase filter optimized for the 4-norm.
b = firlpnorm(44,[0 .4 .45 1],[0 .4 .45 1],[0 0 1 1],[5 1 1 1],...
[2 4], 'minphase');
fvtool(b)
```

As shown in the next figure, this is a minimum-phase, highpass filter.



The next zero-pole plot shows the minimum phase nature more clearly.



## References

Saramaki, T, Finite Impulse Response Filter Design, *Handbook for Digital Signal Processing* Mitra, S.K. and J.F. Kaiser Eds. Wiley-Interscience, N.Y., 1993, Chapter 4.

## See Also

firgr | iirgrpdelay | iirlpnorm | iirlpnormc | filter | fvtool | freqz | zplane

---

<b>Purpose</b>	Least-square linear-phase FIR filter design
<b>Syntax</b>	<pre>b = firls(n,f,a) b = firls(n,f,a,w) b = firls(n,f,a,ftype) b = firls(n,f,a,w,ftype)</pre>
<b>Description</b>	<p><code>b = firls(n,f,a)</code> returns row vector <code>b</code> containing the <code>n+1</code> coefficients of the order <code>n</code> FIR filter. This filter has frequency-amplitude characteristics approximately matching those given by vectors, <code>f</code> and <code>a</code>.</p> <p><code>b = firls(n,f,a,w)</code> uses the weights in vector <code>w</code>, to weigh the error.</p> <p><code>b = firls(n,f,a,ftype)</code> specifies a filter type where <code>ftype</code> is:</p> <ul style="list-style-type: none"><li>• 'hilbert'</li><li>• 'differentiator'</li></ul> <p><code>b = firls(n,f,a,w,ftype)</code> uses the weights in vector <code>w</code> to weigh the error. It also specifies a filter type where <code>ftype</code> is:</p> <ul style="list-style-type: none"><li>• 'hilbert'</li><li>• 'differentiator'</li></ul>
<b>Input Arguments</b>	<p><b>n - Filter order</b> (default)   integer scalar</p> <p>Order of the filter, specified as an integer scalar. For odd orders, the frequency response at the Nyquist frequency is necessarily 0. For this reason, <code>firls</code> always uses an even filter order for configurations with a passband at the Nyquist frequency. If you specify an odd-valued <code>n</code>, <code>firls</code> increments it by 1.</p> <p><b>Example:</b> 8</p>

## Data Types

int8 | int16 | int32 | int64

**Complex Number Support:** No

## **f** - Pairs of frequency points

vector of numeric values

Pairs of frequency points, specified as a vector of values ranging between 0 and 1, where 1 corresponds to the Nyquist frequency. The frequencies must be in increasing order, and duplicate frequency points are allowed. You can use duplicate frequency points to design filters exactly like those returned by the `fir1` and `fir2` functions with a rectangular (`rectwin`) window.

`f` and `a` are the same length. This length must be an even number.

**Example:** [0 0.3 0.4 1]

## Data Types

double | single

**Complex Number Support:** No

## **a** - Amplitude values

vector of numeric values

Amplitude values of the function at each frequency point, specified as a vector of the same length as `f`. This length must be an even number.

The desired amplitude at frequencies between pairs of points  $(f(k), f(k+1))$  for  $k$  odd, is the line segment connecting the points  $(f(k), a(k))$  and  $(f(k+1), a(k+1))$ .

The desired amplitude at frequencies between pairs of points  $(f(k), f(k+1))$  for  $k$  even is unspecified. These are transition or “don’t care” regions.

**Example:** [1 1 0 0]

## Data Types

double | single

**Complex Number Support:** No

**w - Weights**

vector of numeric values

Weights to weigh the fit for each frequency band, specified as a vector of length half the length of `f` and `a`, so there is exactly one weight per band. `w` indicates how much emphasis to put on minimizing the integral squared error in each band, relative to the other bands.

**Example:** `[0.5 1]`**Data Types**

double | single

**Complex Number Support:** No**ftype - Filter type**

'hilbert' and 'differentiator'

Filter type, specified as either 'hilbert' or 'differentiator'.

**Example:** 'hilbert'**Data Types**

char

**Output Arguments****b - Filter coefficients**

vector of numeric values

Filter coefficients, returned as a numeric vector of  $n+1$  values, where  $n$  is the filter order.

`b = firls(n, f, a)` designs a linear-phase filter of type I ( $n$  odd) and type II ( $n$ ). The output coefficients, or “taps,” in `b` obey the relation:

$$b(k) = b(n+2-k), k = 1, \dots, n + 1$$

`b = firls(n, f, a, 'hilbert')` designs a linear-phase filter with odd symmetry (type III and type IV). The output coefficients, or “taps,” in `b` obey the relation:

$$b(k) = -b(n+2-k), k = 1, \dots, n + 1$$

`b = firls(n,f,a,'differentiator')` designs type III and type IV filters, using a special weighting technique. For nonzero amplitude bands, the integrated squared error has a weight of  $(1/f)^2$ . This weighting causes the error at low frequencies to be much smaller than at high frequencies. For FIR differentiators, which have an amplitude characteristic proportional to frequency, the filters minimize the relative integrated squared error. This value is the integral of the square of the ratio of the error to the desired amplitude.

## Examples

### Design a Lowpass Filter with Transition Band

The following illustrates how to design a lowpass filter of order 225 with transition band.

Create the frequency and amplitude vectors, `f` and `a`.

```
f = [0 0.25 0.3 1]
a = [1 1 0 0]
```

Use `firls` to obtain the  $n+1$  coefficients of the order  $n$  lowpass FIR filter.

```
b = firls(255,f,a);
```

### Design an Antisymmetric Filter with Piecewise Linear Passbands

The following shows how to design a 24<sup>th</sup>-order anti-symmetric filter with piecewise linear passbands, and plot the desired and actual amplitude responses.

Create the frequency and amplitude vectors, `f` and `a`.

```
f = [0 0.3 0.4 0.6 0.7 0.9];
a = [0 1 0 0 0.5 0.5];
```

Use `firls` to obtain the 25 coefficients of the filter.

```
b = firls(24,f,a,'hilbert');
```


Plot the ideal amplitude response along with the transition regions.

```
plot(f.*pi,a,'o','markerfacecolor',[1 0 0]);  
hold on;  
plot(f.*pi,a,'r--','linewidth',2);
```

Use `freqz` to obtain the frequency response of the designed filter and plot the magnitude response of the filter.

```
[H,F] = freqz(b,1);  
plot(F,abs(H));  
set(gca,'xlim',[0 pi])  
legend('Filter Specification','Transition Regions','Magnitude Response')
```

# firls



## Algorithms

`firls` designs a linear-phase FIR filter. This filter minimizes the weighted, integrated squared error between an ideal piecewise linear function and the magnitude response of the filter over a set of desired frequency bands.

Reference [1] describes the theoretical approach behind `firls`. The function solves a system of linear equations involving an inner product matrix of size roughly  $n/2$  using the `MATLAB \` operator.

This function designs type I, II, III, and IV linear-phase filters. Type I and II are the defaults for  $n$  even and odd respectively. The 'hilbert' and 'differentiator' flags produce type III ( $n$  even) and IV ( $n$  odd) filters. The various filter types have different symmetries and constraints on their frequency responses (see [2] for details).

Linear Phase Filter Type	Filter Order	Symmetry of Coefficients	Response $H(f)$ , $f = 0$	Response $H(f)$ , $f = 1$ (Nyquist)
Type I	Even	$b(k) = b(n+2-k)$ , $k=1, \dots, n+1$	No restriction	No restriction
Type II	Even	$b(k) = b(n+2-k)$ , $k=1, \dots, n+1$	No restriction	$H(1) = 0$
Type III	Odd	$b(k) = -b(n+2-k)$ , $k=1, \dots, n+1$	$H(0) = 0$	$H(1) = 0$
Type IV	Odd	$b(k) = -b(n+2-k)$ , $k=1, \dots, n+1$	$H(0) = 0$	No restriction

## Definitions

## Diagnostics

Error and warning messages

One of the following diagnostic messages is displayed when an incorrect argument is used:

`F` must be even length.

`F` and `A` must be equal lengths.

Requires symmetry to be 'hilbert' or 'differentiator'.

Requires one weight per band.

Frequencies in `F` must be nondecreasing.

Frequencies in `F` must be in range `[0,1]`.

A more serious warning message is

Warning: Matrix is close to singular or badly scaled.

This tends to happen when the product of the filter length and transition width grows large. In this case, the filter coefficients `b` might not represent the desired filter. You can check the filter by looking at its frequency response.

## References

- [1] Parks, T.W., and C.S. Burrus, *Digital Filter Design*, John Wiley & Sons, 1987, pp. 54-83.
- [2] Oppenheim, A.V., and R.W. Schaffer, *Discrete-Time Signal Processing*, Prentice-Hall, 1989, pp. 256-266.

## See Also

`fir1` | `fir2` | `firrcos` | `firpm`

**Purpose** Minimum-phase FIR spectral factor

**Syntax**  
`h = firminphase(b)`  
`h = firminphase(b,nz)`

**Description** `h = firminphase(b)` computes the minimum-phase FIR spectral factor `h` of a linear-phase FIR filter `b`. Filter `b` must be real, have even order, and have nonnegative zero-phase response.

`h = firminphase(b,nz)` specifies the number of zeros, `nz`, of `b` that lie on the unit circle. You must specify `nz` as an even number to compute the minimum-phase spectral factor because every root on the unit circle must have even multiplicity. Including `nz` can help `firminphase` calculate the required FIR spectral factor. Zeros with multiplicity greater than two on the unit circle cause problems in the spectral factor determination.

---

**Note** You can find the maximum-phase spectral factor, `g`, by reversing `h`, such that `g = fliplr(h)`, and `b = conv(h, g)`.

---

**Examples** This example designs a constrained least squares filter with a nonnegative zero-phase response, and then uses `firminphase` to compute the minimum-phase spectral factor.

```
f = [0 0.4 0.8 1];  
a = [0 1 0];  
up = [0.02 1.02 0.01];  
lo = [0 0.98 0]; % The zeros insure nonnegative zero-phase resp.  
n = 32;  
b = fircls(n,f,a,up,lo);  
h = firminphase(b);
```

**References** Saramaki, T, Finite Impulse Response Filter Design, *Handbook for Digital Signal Processing* Mitra, S.K. and J.F. Kaiser Eds. Wiley-Interscience, N.Y., 1993, Chapter 4.

# firminphase

---

## **See Also**

fingr | fircls | zerophase

<b>Purpose</b>	Lowpass Nyquist (Lth-band) FIR filter
<b>Syntax</b>	<pre> b = firnyquist(n,l,r) b = firnyquist('minorder',l,r,dev) b = firnyquist(n,l,r,decay) b = firnyquist(n,l,r,'nonnegative') b = firnyquist(n,l,r,'minphase') </pre>
<b>Description</b>	<p><code>b = firnyquist(n,l,r)</code> designs an Nth order, Lth band, Nyquist FIR filter with a rolloff factor <math>r</math> and an equiripple characteristic.</p> <p>The rolloff factor <math>r</math> is related to the normalized transition width <math>tw</math> by <math>tw = 2\pi(r/l)</math> (rad/sample). The order, <math>n</math>, must be even. <math>l</math> must be an integer greater than one. If <math>l</math> is not specified, it defaults to 4. <math>r</math> must satisfy <math>0 &lt; r &lt; 1</math>. If <math>r</math> is not specified, it defaults to 0.5.</p> <p><code>b = firnyquist('minorder',l,r,dev)</code> designs a minimum-order, Lth band Nyquist FIR filter with a rolloff factor <math>r</math> using the Kaiser window. The peak ripple is constrained by the scalar <code>dev</code>.</p> <p><code>b = firnyquist(n,l,r,decay)</code> designs an Nth order (<math>n</math>), Lth band (<math>l</math>), Nyquist FIR filter where the scalar <code>decay</code>, specifies the rate of decay in the stopband. <code>decay</code> must be nonnegative. If you omit or leave it empty, <code>decay</code> defaults to 0 which yields an equiripple stopband. A nonequiripple stopband (<code>decay</code> <math>\neq</math> 0) may be desirable for decimation purposes.</p> <p><code>b = firnyquist(n,l,r,'nonnegative')</code> returns an FIR filter with nonnegative zero-phase response. This filter can be spectrally factored into minimum-phase and maximum-phase “square-root” filters. This allows you to use the spectral factors in applications such as matched-filtering.</p> <p><code>b = firnyquist(n,l,r,'minphase')</code> returns the minimum-phase spectral factor <code>bmin</code> of order <math>n</math>. <code>bmin</code> meets the condition <code>b=conv(bmin,bmax)</code> so that <code>b</code> is an Lth band FIR Nyquist filter of order <math>2n</math> with filter rolloff factor <math>r</math>. Obtain <code>bmax</code>, the maximum phase spectral factor by reversing the coefficients of <code>bmin</code>. For example, <code>bmax = bmin(end:-1:1)</code>.</p>

# firnyquist

---

## Examples

### Example 1

This example designs a minimum phase factor of a Nyquist filter.

```
bmin = firnyquist(47,10,.45,'minphase');  
b = firnyquist(2*47,10,.45,'nonnegative');  
[h,w,s] = freqz(b); hmin = freqz(bmin);  
fvtool(b,1,bmin,1);
```

### Example 2

This example compares filters with different decay rates.

```
b1 = firnyquist(72,8,.3,0); % Equiripple  
b2 = firnyquist(72,8,.3,15);  
b3 = firnyquist(72,8,.3,25);  
fvtool(b1,1,b2,1,b3,1);
```

## References

T. Saramaki, Finite Impulse Response Filter Design, *Handbook for Digital Signal Processing*, Mitra, S.K. and J.F. Kaiser Eds. Wiley-Interscience, N.Y., 1993, Chapter 4.

## See Also

[firhalfband](#) | [firngr](#) | [firls](#) | [firminphase](#) | [firrcos](#) | [firls](#)

**Purpose**

Two-channel FIR filter bank for perfect reconstruction

**Syntax**

```
[h0,h1,g0,g1] = firpr2chfb(n,fp)
[h0,h1,g0,g1] = firpr2chfb(n,dev,'dev')
[h0,h1,g0,g1] = firpr2chfb('minorder',fp,dev)
```

**Description**

`[h0,h1,g0,g1] = firpr2chfb(n,fp)` designs four FIR filters for the analysis sections (`h0` and `h1`) and synthesis section is (`g0` and `g1`) of a two-channel perfect reconstruction filter bank. The design corresponds to the orthogonal filter banks also known as power-symmetric filter banks.

`n` is the order of all four filters. It must be an odd integer. `fp` is the passband-edge for the lowpass filters `h0` and `g0`. The passband-edge argument `fp` must be less than 0.5. `h1` and `g1` are highpass filters with the passband-edge given by  $(1-fp)$ .

`[h0,h1,g0,g1] = firpr2chfb(n,dev,'dev')` designs the four filters such that the maximum stopband ripple of `h0` is given by the scalar `dev`. Specify `dev` in linear units, not decibels. The stopband-ripple of `h1` is also be given by `dev`, while the maximum stopband-ripple for both `g0` and `g1` is  $(2*dev)$ .


`[h0,h1,g0,g1] = firpr2chfb('minorder',fp,dev)` designs the four filters such that `h0` meets the passband-edge specification `fp` and the stopband-ripple `dev` using minimum order filters to meet the specification.

**Examples**

Design a filter bank with filters of order `n` equal to 99 and passband edges of 0.45 and 0.55.

```
n = 99;
[h0,h1,g0,g1] = firpr2chfb(n,.45);
fvtool(h0,1,h1,1,g0,1,g1,1);
```

Here are the filters, showing clearly the passband edges.



Use the following stem plots to verify perfect reconstruction using the filter bank created by `firpr2chfb`.

```
stem(1/2*conv(g0,h0)+1/2*conv(g1,h1))
n=0:n;
stem(1/2*conv((-1).^n.*h0,g0)+1/2*conv((-1).^n.*h1,g1))
stem(1/2*conv((-1).^n.*g0,h0)+1/2*conv((-1).^n.*g1,h1))
stem(1/2*conv((-1).^n.*g0,(-1).^n.*h0)+...
1/2*conv((-1).^n.*g1,(-1).^n.*h1))
stem(conv((-1).^n.*h1,h0)-conv((-1).^n.*h0,h1))
```

## See Also

`firceqrip` | `firgr` | `firhalfband` | `firnyquist`

**Purpose** Type of linear phase FIR filter

**Syntax**

```
t = firtype(hd)
t = firtype(hm)
t = firtype(hs)
```

**Description** `t = firtype(hd)` determines the type (1 through 4) of a discrete-time FIR filter object `hd`, returning the type number in `t`. Filter `hd` must be real and have linear phase.

`t = firtype(hm)` determines the type (1 through 4) of the multirate filter object `hm`. The filter must be real and have linear phase. When `hm` has multiple sections, all sections must be real FIR filters with linear phase. In this case, `t` is a cell array containing the filter type of each section.

`t = firtype(hs)` determines the type (1 through 4) of the filter System object `hs`. The filter must be real and have linear phase.

## Input Arguments

**hd**  
Discrete-time `dfilt` filter object.

**hm**  
Multirate `mfilt` filter object.

**hs**  
Filter System object. The function supports the following filter structures.

- `dsp.FIRFilter`
- `dsp.BiquadFilter`
- `dsp.FIRInterpolator`
- `dsp.CICInterpolator`
- `dsp.FIRDecimator`

# firtype

---

- `dsp.CICDecimator`
- `dsp.FIRRateConverter`

## Output Arguments

**t**

Filter type. **t** is either 1, 2, 3, or 4. These types are defined as follows:

- Type 1 — Even-order symmetric coefficients
- Type 2 — Odd-order symmetric coefficients
- Type 3 — Even-order antisymmetric coefficients
- Type 4 — Odd-order antisymmetric coefficients

## Examples

Determine the type of the default interpolator for  $L=4$ .

```
l = 4;  
hm = mfilt.firinterp(l);  
firtype(hm)  
ans =
```

```
1
```

## See Also

`islinphase`

## Purpose

Frequency response estimate via filtering

## Syntax

```
[h,w] = freqrespest(H,L)
[h,w] = freqrespest(H,L,param1,value1,param2,value2,...)
[h,w] = freqrespest(H,L,opts)
freqrespest(H,...)
```

## Description

`[h,w] = freqrespest(H,L)` estimates the frequency response of a `dfilt` object or a filter System object. A set of input data is filtered and then forming the ratio between output data and input data. The test input data comprises sinusoids with uniformly distributed random frequencies.

Use this technique for comparing the performance of fixed-point filters to that of another filter type. You can, for example, compare fixed—point frequency response estimate to that of a similar filter that uses quantized coefficients, but applies floating-point arithmetic internally. Such comparison determines whether the fixed-point filter performance closely matches the floating-point, quantized coefficients version of the filter.

`L` is the number of trials to use to compute the estimate. If you do not specify this value, `L` defaults to 10. More trials generates a more accurate estimate of the response, but require more time to compute the estimate.

`h` is the estimate of the complex frequency response. `w` contains the vector of frequencies at which `h` is estimated.

`[h,w] = freqrespest(H,L,param1,value1,param2,value2,...)` accepts `H` as either a `dfilt` object or a filter System object. This approach uses parameter value (PV) pairs as input arguments to specify optional parameters for the test. These parameters are the valid PV pairs. Enter the parameter names as string input arguments in single quotation marks. The following table provides valid parameters for `[h, w]`.

Parameter Name	Default Value	Description
NFFT	512	Number of FFT points to use.
NormalizedFrequency	true	Indicate whether to use normalized frequency or linear frequency. Values are true (use normalized frequency), or false (use linear frequency). When you specify false, you must supply the sampling frequency Fs.
Fs	normalized	Specify the sampling frequency when NormalizedFrequency is false. No default value. You must set NormalizedFrequency to false before setting a value for Fs.
SpectrumRange	half	Specify the spectrum range to be used as whole or half (default).
CenterDC	false	Specify whether to set the center of the spectrum to the DC value in the output plot. If you select true, both the negative and positive values appear in the plot. If you select false, DC appears at the origin of the axes.
Arithmetic (only for filter System objects)	ARITH	Analyze the filter System object, based on the arithmetic specified in the ARITH input. ARITH can be set to double, single, or fixed. The analysis tool assumes a double-precision

Parameter Name	Default Value	Description
		filter when the arithmetic input is not specified and the filter System object is in an unlocked state.

If *H* is a filter System object, `freqrespest` requires knowledge of the input data type. Analysis cannot be performed if the input data type is not available. If you do not specify the Arithmetic parameter, i.e., use the syntax `[h,w] = freqrespest(H)`, then the following rules apply for this method:

- The System object state is Unlocked — `freqrespest` performs double precision analysis.
- The System object state is Locked — `freqrespest` performs analysis based on the locked input data type.

When you do specify the Arithmetic parameter, i.e., use the syntax `[h,w] = freqrespest(H, 'Arithmetic', ARITH)`, review the following rules for this method. Which rule applies depends on the value you set for the Arithmetic parameter.

Value	System Object State	Rule
ARITH = 'double'	Unlocked	<code>freqrespest</code> performs double-precision analysis.
	Locked	<code>freqrespest</code> performs double-precision analysis.

# freqrespest

Value	System Object State	Rule
ARITH = `single`	Unlocked	freqrespest performs single-precision analysis.
	Locked	freqrespest performs single-precision analysis.
ARITH = `fixed`	Unlocked	freqrespest produces an error because the fixed-point input data type is unknown.
	Locked	If the input data type is double or single, then freqrespest produces an error because the fixed-point input data type is unknown.
		When the input data is of fixed-point type, freqrespest performs analysis based on the locked input data type.

freqrespest supports only the following filter System objects:

- dsp.FIRFilter
- dsp.IIRFilter
- dsp.AllpoleFilter

- `dsp.BiquadFilter`

Regardless of whether `H` is a `dfilt` object or a filter System object, `[h,w] = freqrespest(H,L,opts)` uses an object, `opts`, to specify the optional input parameters. This specification is not done directly by specifying PV pairs as input arguments. Create `opts` with

```
opts = freqrespest(H);
```

Because `opts` is an object, you use `set` to change the parameter values in `opts` before you use it with `freqrespest`. For example, you could specify a new sample rate with

```
set(opts,'fs',48e3); % Same as opts.fs=48e3
```

Regardless of whether `H` is a `dfilt` object or a filter System object, `freqrespest(H,...)` with no output argument launches FVTool.

`freqrespest` can also compute the frequency response of double-precision floating filters. Such filters cannot be converted to transfer-function form without introducing significant round off errors which affect the `freqz` frequency response computation. Examples of these kinds of filters include state-space or lattice filters, especially if they are high-order filters.

## Examples

These examples demonstrate some uses for `freqrespest`.

### Example 1

Start by estimating the frequency response of a fixed-point FIR filter that has filter internals set to full precision.

```
hd = design(fdesign.lowpass(.4,.5,1,60),'equiripple');
hd.arithmetic = 'fixed';
[h,w] = freqrespest(hd); % This should be about the same as freqz.
```


Continuing with filter `hd`, change the value of the `filterinternals` property to `specifyprecision` and then specify the word lengths and precision (the fraction lengths) applied to the output from internal addition and multiplication operations. After you set the word and

# freqrespest

---

fraction lengths, use `freqrespest` to compute the frequency response estimate for the fixed-point filter.

```
hd.filterinternals = 'specifyprecision';
hd.outputwordlength=16;
hd.outputfraclength=15;
hd.productwordlength=16;
hd.productfraclength=15;
hd.accumwordlength=16;
hd.accumfraclength=15;
[h,w] = freqrespest(hd,2);
[h2,w2] = freqz(hd,512);
plot(w/pi,20*log10(abs([h,h2])))
legend('Frequency response estimated by filtering',...
'Freq. response computed by quantizing coefficients only');
xlabel('Normalized Frequency (\times\pi rad/sample)')
ylabel('Magnitude (dB)')
```



## Example 2

freqrespest works with state-space filters as well. This example estimates the frequency response of a state-space filter.

```

fs = 315000;
wp = [320 3800]/(fs/2);
ws = [50 19000]/(fs/2);
rp=0.15; rs=60;
[n,wn]=cheb1ord(wp,ws,rp,rs);
[a,b,c,d] = cheby1(n,rp,wn);
hd = dfilt.statespace(a,b,c,d);
% Compare the following to freqz(hd,8192)
freqrespest(hd,1,'nfft',8192);

```

# freqrespest

---

## See Also

`dfilt` | `freqrespopts` | `freqz` | `limitcycle` | `noisepsd` | `scale`

**Purpose** Options for filter frequency response analysis

**Syntax** `opts = freqrespopts(H)`

**Description** `opts = freqrespopts(H)` uses the settings in the `dfilt` object or the filter System object, `H`, to create an object, `opts`. This object contains parameters and values for estimating the filter frequency response. You pass `opts` as an input argument to `freqrespest` to specify values for the input parameters.

`freqrespopts` allows you to use the same settings for `freqrespest` with multiple filters without specifying all of the parameters as input arguments to `freqrespest`.

`freqrespopts` supports only the following filter System objects:

- `dsp.FIRFilter`
- `dsp.IIRFilter`
- `dsp.AllpoleFilter`
- `dsp.BiquadFilter`

**Examples** This example shows `freqrespopts` in use for setting options for `freqrespest`. `hd` and `hd2` are bandpass filters that use different design methods. The `opts` object makes it easier to set the same conditions for the frequency response estimate in `freqrespest`.

```
d=fdesign.bandpass('fst1,fp1,fp2,fst2,ast1,ap,ast2',...
0.25,0.3,0.45,0.5,60,0.1,60);
```

```
hd=design(d,'butter');
hd.arithmetic='fixed';
hd2=design(d,'cheby2');
hd2.arithmetic='fixed';
opts=freqrespopts(hd)
```

```
opts =
```

# freqrespopts

---

```
                NFFT: 512
NormalizedFrequency: true
                Fs: 'Normalized'
SpectrumRange: 'Half'
                CenterDC: false

opts.NFFT=256; % Same as set(opts,'nfft',256).
opts.NormalizedFrequency=false;
opts.fs=1.5e3;
opts.CenterDC=true

opts =

                NFFT: 256
NormalizedFrequency: false
                Fs: 1500
SpectrumRange: 'Whole'
                CenterDC: true
```

With `opts` configured as needed, use it as an input argument for `freqrespest`.

```
[h2,w2]=freqrespest(hd2,20,opts);
[h1,w1]=freqrespest(hd,20,opts);
```

## See Also

`freqrespest` | `noisepsd` | `noisepsdopts` | `norm` | `scale`

**Purpose** Real or complex frequency-sampled FIR filter from specification object

**Syntax**

```
hd = design(d,'freqsamp')
hd = design(...,'filterstructure',structure)
hd = design(...,'window',window)
```

**Description**

`hd = design(d,'freqsamp')` designs a frequency-sampled filter specified by the filter specifications object `d`.

`hd = design(...,'filterstructure',structure)` returns a filter with the filter structure you specify by the `structure` input argument. `structure` is `dffir` by default and can be any one of the following filter structures.

Structure String	Description of Resulting Filter Structure
<code>dffir</code>	Direct-form FIR filter
<code>dffirt</code>	Transposed direct-form FIR filter
<code>dfsymfir</code>	Symmetrical direct-form FIR filter
<code>dfasymfir</code>	Asymmetrical direct-form FIR filter
<code>fftfir</code>	Fast Fourier transform FIR filter

`hd = design(...,'window',window)` designs filters using the window specified by the string in `window`. Provide the input argument `window` as

- A string for the window type. For example, use `'bartlett'`, or `'hamming'`. See `window` for the full list of windows available or refer to `window` in the *Signal Processing Toolbox User's Guide*.
- A function handle that references the window function. When the window function requires more than one input, use a cell array to hold the required arguments. The first example shows a cell array input argument.
- The window vector itself.


## Examples

These examples design FIR filters that have arbitrary magnitude responses. In the first filter, the response has three distinct sections and the resulting filter is real.

The second example creates a complex filter.

```
b1 = 0:0.01:0.18;
b2 = [.2 .38 .4 .55 .562 .585 .6 .78];
b3 = [0.79:0.01:1];
a1 = .5+sin(2*pi*7.5*b1)/4; % Sinusoidal response section.
a2 = [.5 2.3 1 1 -.2 -.2 1 1]; % Piecewise linear response section.
a3 = .2+18*(1-b3).^2; % Quadratic response section.
f = [b1 b2 b3];
a = [a1 a2 a3];
n = 300;
d = fdesign.arbmag('n,f,a',n,f,a); % First specifications object.
hd = design(d,'freqsamp','window',{@kaiser,.5}); % Filter.
fvtool(hd)
```

The plot from FVTool shows the response for hd.




Now design the arbitrary-magnitude complex FIR filter. Recall that vector  $f$  contains frequency locations and vector  $a$  contains the desired filter response values at the locations specified in  $f$ .

```
f = [-1 -.93443 -.86885 -.80328 -.7377 -.67213 -.60656 -.54098 ...
    -.47541,-.40984 -.34426 -.27869 -.21311 -.14754 -.081967 ...
    -.016393 .04918 .11475,.18033 .2459 .31148 .37705 .44262 ...
    .5082 .57377 .63934 .70492 .77049,.83607 .90164 1];
a = [.0095848 .021972 .047249 .099869 .23119 .57569 .94032 ...
    .98084 .99707,.99565 .9958 .99899 .99402 .99978 .99995 .99733 ...
    .99731 .96979 .94936,.8196 .28502 .065469 .0044517 .018164 ...
    .023305 .02397 .023141 .021341,.019364 .017379 .016061];
n = 48;
d = fdesign.arbmag('n,f,a',n,f,a); % Second spec. object.
hdc = design(d,'freqsamp','window','rectwin'); % Filter.
fvtool(hdc)
```

# freqsamp

---

FVTool shows you the response for `hdc` from -1 to 1 in normalized frequency. `design(d,...)` returns a complex filter for `hdc` because the frequency vector includes negative frequency values.



## See Also

[design](#) | [designmethods](#) | [fdesign.arbmag](#) | [help](#) | [window](#)

**Purpose**

Frequency response of filter

**Syntax**

```
[h,w] = freqz(hfilt)
[h,w] = freqz(hfilt,n)
freqz(hfilt)
[h,w] = freqz(hs)
[h,w] = freqz(hs,n)
[h,w] = freqz(hs,Name,Value)
freqz(hs)
```

**Description**

`freqz` returns the frequency response based on the current filter coefficients. This section describes common `freqz` operation with adaptive filters, discrete-time filters, multirate filters, and filter System objects. For more input options, refer to `freqz` in Signal Processing Toolbox documentation.

`[h,w] = freqz(hfilt)` returns the frequency response `h` and the corresponding frequencies `w` at which the filter response of `hfilt` is computed. The frequency response is evaluated at 8192 points equally spaced around the upper half of the unit circle.

`[h,w] = freqz(hfilt,n)` returns the frequency response `h` and corresponding frequencies `w` for the filter or vector of filters `hfilt`. The frequency response is evaluated at `n` points equally spaced around the upper half of the unit circle. `freqz` uses the transfer function associated with the filter to calculate the frequency response of the filter with the current coefficient values.

`freqz(hfilt)` uses `FVTool` to plot the magnitude and unwrapped phase of the frequency response of the filter `hfilt`. If `hfilt` is a vector of filters, `freqz` plots the magnitude response and phase for each filter in the vector.

`[h,w] = freqz(hs)` returns a frequency response for the filter System object `hs` using 8192 samples.

`[h,w] = freqz(hs,n)` returns a frequency response for the filter System object `hs` using `n` samples.

`[h,w] = freqz(hs,Name,Value)` returns a frequency response with additional options specified by one or more `Name,Value` pair arguments.

`freqz(hs)` uses FVTool to plot the magnitude and unwrapped phase of the frequency response of the filter System object `hs`.

## Input Arguments

### **hfilt**

`hfiltr` is either:

- An adaptive `adaptfilt`, discrete-time `dfilt`, or multirate `mfilt` filter object
- A vector of adaptive, discrete-time, or multirate filter objects

### **hs**

Filter System object. The function supports the following filter structures.

- `dsp.FIRFilter`
- `dsp.BiquadFilter`
- `dsp.FIRInterpolator`
- `dsp.CICInterpolator`
- `dsp.FIRDecimator`
- `dsp.CICDecimator`
- `dsp.FIRRateConverter`

### **n**

Number of samples. For an FIR filter where `n` is a power of two, the computation is done faster using FFTs.

**Default:** 8192

## Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments, where `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes ( `' '`). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

### Arithmetic

`'double'` | `'single'` | `'fixed'`

For filter System object inputs only, specify the arithmetic used during analysis. When you specify `'double'` or `'single'`, the function performs double- or single-precision analysis. When you specify `'fixed'`, the arithmetic changes depending on the setting of the `CoefficientDataType` property and whether the System object is locked or unlocked.

### Details for Fixed-Point Arithmetic

System Object State	Coefficient Data Type	Rule
Unlocked	'Same as input'	The function assumes that the coefficient data type is signed, 16 bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Unlocked	'Custom'	The function performs fixed-point analysis based on the setting of the <code>CustomCoefficientsDataType</code> property.

System Object State	Coefficient Data Type	Rule
Locked	'Same as input'	When the input data type is 'double' or 'fixed', the function assumes that the coefficient data type is signed, 16-bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Locked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.

When you do not specify the arithmetic for non-CIC structures, the function uses double-precision arithmetic if the filter System object is in an unlocked state. If the System object is locked, the function performs analysis based on the locked input data type. CIC structures only support fixed-point arithmetic.

## Output Arguments

### h

Complex, n-element frequency response vector. If `hfilt` is a vector of filters, `h` is a complex, `length(hfilt)`-by-`n` matrix of frequency response vectors corresponding to each filter in `hfilt`. If `n` is not specified, the function uses a default value of 8192.

For adaptive filters, `h` is the instantaneous frequency response.

### w

Frequency vector of length  $n$ , in radians/sample.  $w$  consists of  $n$  points equally spaced around the upper half of the unit circle (from 0 to  $\pi$  radians/sample). If  $n$  is not specified, the function uses a default value of 8192.

## Tips

There are several ways of analyzing the frequency response of filters. `freqz` accounts for quantization effects in the filter coefficients, but does not account for quantization effects in filtering arithmetic. To account for the quantization effects in filtering arithmetic, refer to function `noisepsd`.


## Algorithms

`freqz` calculates the frequency response for a filter from the filter transfer function  $Hq(z)$ . The complex-valued frequency response is calculated by evaluating  $Hq(e^{j\omega})$  at discrete values of  $\omega$  specified by the syntax you use. The integer input argument  $n$  determines the number of equally-spaced points around the upper half of the unit circle at which `freqz` evaluates the frequency response. The frequency ranges from 0 to  $\pi$  radians per sample when you do not supply a sampling frequency as an input argument. When you supply the scalar sampling frequency `fs` as an input argument to `freqz`, the frequency ranges from 0 to `fs/2` Hz.

## Examples


Plot the estimated frequency response of a filter. This example uses discrete-time filters, but `hd` can be any `adaptfilt` object, `dfilt` object, `mfilt` object, or filter System object. First plot the results for one filter.

```
b = fir1(80,0.5,kaiser(81,8));  
hd = dfilt.dffir(b);  
freqz(hd);
```



If you have more than one filter, you can plot them on the same figure using a vector of filters.

```
b = fir1(40,0.5,kaiser(41,6));  
hd2 = dfilt.dffir(b);  
h = [hd hd2];  
freqz(h);
```

**See Also**`adaptfilt | dfilt | mfilt | fvtool`

# gain

---

**Purpose** CIC filter gain

**Syntax**  
`gain(hm)`  
`gain(hm,j)`  
`gain(hs)`

**Description** `gain(hm)` returns the gain of `hm`, the CIC decimation or interpolation filter.

When `hm` is a decimator, `gain` returns the gain for the overall CIC decimator.

When `hm` is an interpolator, the CIC interpolator inserts zeros into the input data stream, reducing the filter overall gain by  $1/R$ , where  $R$  is the interpolation factor, to account for the added zero valued samples. Therefore, the gain of a CIC interpolator is  $(RM)^N/R$ , where  $N$  is the number of filter sections and  $M$  is the filter differential delay. `gain(hm)` returns this value. The next example presents this case.

`gain(hm,j)` returns the gain of the  $j$ th section of a CIC interpolation filter. When you omit  $j$ , `gain` assumes that  $j$  is  $2*N$ , where  $N$  is the number of sections, and returns the gain of the last section of the filter. This syntax does not apply when `hm` is a decimator.

`gain(hs)` returns the gain of the filter System object `hs`. The function supports the `dsp.CICDecimator` and `dsp.CICInterpolator` filter structures.

## Examples

To compare the performance of two interpolators, one a CIC filter and the other an FIR filter, use `gain` to adjust the CIC filter output amplitude to match the FIR filter output amplitude. Start by creating an input data set—a sinusoidal signal `x`.

```
fs = 1000;           % Input sampling frequency.  
t = 0:1/fs:1.5;     % Signal length = 1501 samples.  
x = sin(2*pi*10*t); % Amplitude = 1 sinusoid.
```

```
l = 4; % Interpolation factor for FIR filter.  
d = fdesign.interpolator(l);
```

```
hm = design(d,'multistage');
ym = filter(hm,x);

r = 4; % Interpolation factor for the CIC filter.
d = fdesign.interpolator(r,'cic');
hcic = design(d,'multisection');
ycic = filter(hcic,x);
gaincic = gain(hcic);
subplot(211);
plot(1:length(ym),[ym; double(ycic)]);
subplot(212)
plot(1:length(ym),[ym; double(ycic)/gain(hcic)]);
```

After correcting for the gain induced by the CIC interpolator, the figure shows the filters provide nearly identical interpolation.

**See Also**

scale

# grpdelay

---

**Purpose** Filter group delay

**Syntax**

```
[gd,w]=grpdelay(hfilt)
[gd,w]=grpdelay(hfilt,n)
grpdelay(hfilt)
[gd,w] = grpdelay(hs)
[gd,w] = grpdelay(hs,n)
[gd,w] = grpdelay(hs,Name,Value)
grpdelay(hs)
```

**Description** `grpdelay` returns the group delay based on the current filter coefficients. This section describes common `grpdelay` operation with adaptive filters, discrete-time filters, multirate filters, and filter System objects. For more input options, refer to `grpdelay` in Signal Processing Toolbox documentation.

`[gd,w]=grpdelay(hfilt)` returns the phase response  $\phi$  of the filter `hfilt` and the corresponding frequencies  $w$  at which the function evaluates the group delay. Group delay is

$$-\frac{d}{dw}(\text{angle}(w))$$

The group delay is evaluated at 8192 points equally spaced around the upper half of the unit circle.

`[gd,w]=grpdelay(hfilt,n)` returns the group delay  $\phi$  of the filter `hfilt` and the corresponding frequencies  $w$  at which the function evaluates the group delay. The group delay is evaluated at  $n$  points equally spaced around the upper half of the unit circle.

`grpdelay(hfilt)` displays the group delay of `hfilt` in the Filter Visualization Tool (FVTool).

`[gd,w] = grpdelay(hs)` returns the group delay for the filter System object `hs` using 8192 samples.

`[gd,w] = grpdelay(hs,n)` returns the group delay for the filter System object `hs` using  $n$  samples.

`[gd,w] = grpdelay(hs,Name,Value)` returns the group delay with additional options specified by one or more `Name,Value` pair arguments.

`grpdelay(hs)` uses FVTool to plot the group delay of the filter System object `hs`.

## Input Arguments

### **hfilter**

`hfilter` is either:

- An adaptive `adaptfilt`, discrete-time `dfilt`, or multirate `mfilt` filter object
- A vector of adaptive, discrete-time, or multirate filter objects

### **hs**

Filter System object. The function supports the following filter structures.

- `dsp.FIRFilter`
- `dsp.BiquadFilter`
- `dsp.FIRInterpolator`
- `dsp.CICInterpolator`
- `dsp.FIRDecimator`
- `dsp.CICDecimator`
- `dsp.FIRRateConverter`

### **n**

Number of samples. For an FIR filter where `n` is a power of two, the computation is done faster using FFTs.

**Default:** 8192

## Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments, where `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes ( ' '). You can specify several name and value pair arguments in any order as `Name1,Value1,...,NameN,ValueN`.

## Arithmetic

`'double' | 'single' | 'fixed'`

For filter System object inputs only, specify the arithmetic used during analysis. When you specify `'double'` or `'single'`, the function performs double- or single-precision analysis. When you specify `'fixed'`, the arithmetic changes depending on the setting of the `CoefficientDataType` property and whether the System object is locked or unlocked.

## Details for Fixed-Point Arithmetic

System Object State	Coefficient Data Type	Rule
Unlocked	'Same as input'	The function assumes that the coefficient data type is signed, 16 bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Unlocked	'Custom'	The function performs fixed-point analysis based on the setting of the <code>CustomCoefficientsDataType</code> property.

System Object State	Coefficient Data Type	Rule
Locked	'Same as input'	When the input data type is 'double' or 'fixed', the function assumes that the coefficient data type is signed, 16-bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Locked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.

When you do not specify the arithmetic for non-CIC structures, the function uses double-precision arithmetic if the filter System object is in an unlocked state. If the System object is locked, the function performs analysis based on the locked input data type. CIC structures only support fixed-point arithmetic.

## Output Arguments

### gd

Complex, n-element group-delay vector. If `hfilt` is a vector of filters, `gd` is a complex, `length(hfilt)`-by-`n` matrix of group-delay vectors whose columns correspond to each filter in `hfilt`. If `n` is not specified, the function uses a default value of 8192.

For adaptive filters, `gd` is the instantaneous group delay.

### w

# grpdelay

---

Frequency vector of length  $n$ , in radians/sample.  $w$  consists of  $n$  points equally spaced around the upper half of the unit circle (from 0 to  $\pi$  radians/sample). If `hfilt` is a vector of filters,  $w$  is a complex, `length(hfilt)`-by- $n$  matrix of group-delay vectors whose columns correspond to each filter in `hfilt`. If  $n$  is not specified, the function uses a default value of 8192.

## See Also

`phasez` | `zerophase`

<b>Purpose</b>	Help for design method with filter specification
<b>Syntax</b>	<code>help(d, 'designmethod')</code>
<b>Description</b>	<code>help(d, 'designmethod')</code> displays help in the Command Window for the design algorithm <code>designmethod</code> for the current specifications of the filter specification object <code>d</code> . The string you enter for <code>designmethod</code> must be one of the strings returned by <code>designmethods</code> for <code>d</code> , the design object.
<b>Examples</b>	<p>Get specific help for designing lowpass Butterworth filters. The first lowpass filter uses the default specification string 'Fp,Fst,Ap,Ast' and returns help text specific to the specification string.</p> <pre>d = fdesign.lowpass; designmethods(d)</pre> <p>Design Methods for class <code>fdesign.lowpass (Fp,Fst,Ap,Ast)</code>:</p> <pre>butter cheby1 cheby2 ellip equiripple ifir kaiserwin multistage</pre> <pre>help(d, 'butter')</pre> <p>DESIGN Design a Butterworth IIR filter. HD = DESIGN(D, 'butter') designs a Butterworth filter specified by the FDESIGN object D.</p> <p>HD = DESIGN(..., 'FilterStructure', STRUCTURE) returns a filter with the structure STRUCTURE. STRUCTURE is 'df2sos' by default and can be any of the following.</p>

```
'df1sos'  
'df2sos'  
'df1tsos'  
'df2tsos'
```

HD = DESIGN(..., 'MatchExactly', MATCH) designs a Butterworth filter and matches the frequency and magnitude specification for the band MATCH exactly. The other band will exceed the specification. MATCH can be 'stopband' or 'passband' and is 'stopband' by default.

```
% Example #1 - Compare passband and stopband MatchExactly.  
h = fdesign.lowpass('Fp,Fst,Ap,Ast', .1, .3, 1, 60);  
Hd = design(h, 'butter', 'MatchExactly', 'passband');  
Hd(2) = design(h, 'butter', 'MatchExactly', 'stopband');
```

```
% Compare the passband edges in FVTool.  
fvtool(Hd);  
axis([.09 .11 -2 0]);
```

Note the discussion of the MatchExactly input option. When you use a design object that uses a different specification string, such as 'N,F3dB', the help content for the butter design method changes.

In this case, the MatchExactly option does not appear in the help because it is not an available input argument for the specification string 'N,F3dB'.

```
d=fdesign.lowpass('N,F3dB')
```

```
d =  
           Response: 'Lowpass'  
    Specification: 'N,F3dB'  
    Description: {'Filter Order';'3dB Frequency'}  
NormalizedFrequency: true  
      FilterOrder: 10  
           F3dB: 0.5
```

```
designmethods(d)
```

```
Design Methods for class fdesign.lowpass (N,F3dB):
```

```
butter
```

```
help(d,'butter
```

```
DESIGN Design a Butterworth IIR filter.
```

```
HD = DESIGN(D, 'butter') designs a Butterworth filter  
specified by the FDESIGN object D.
```

```
HD = DESIGN(..., 'FilterStructure', STRUCTURE) returns a  
filter with the structure STRUCTURE. STRUCTURE is 'df2sos'  
by default and can be any of the following.
```

```
'df1sos'
```

```
'df2sos'
```

```
'df1tsos'
```

```
'df2tsos'
```

```
% Example #1 - Design a lowpass Butterworth filter in the  
DF2TSOS structure.
```

```
h = fdesign.lowpass('N,F3dB');
```

```
Hd = design(h, 'butter', 'FilterStructure', 'df2tsos');
```

## See Also

```
fdesign | design | designmethods | designopts
```

**Purpose** Interpolated FIR filter from filter specification

**Syntax** `hd = ifir(d)`  
`hd = design(d, 'ifir', designoption, value, designoption, ...`  
`value, ...)`

**Description** `hd = ifir(d)` designs an FIR filter from design object `d`, using the interpolated FIR method. `ifir` returns `hd` as a cascade of two filters that act together to meet the specifications in `d`. The resulting filter is particularly efficient, having a low number of multipliers. However, if `ifir` determines that a single-stage filter would be more efficient than the default two-stage design, it returns `hd` as a single-stage filter. `ifir` only creates linear phase filters. Generally, `ifir` uses an advanced optimization algorithm to create highly efficient FIR filters.

`ifir` returns `hd` as either a single-rate `dfilt` object or a multirate `mfilt` object (when you have DSP System Toolbox software installed), based on the specifications you provide in `d`, the filter specification object.

specifications supplied in the object `h`.

`hd = design(d, 'ifir', designoption, value, designoption, ...`  
`value, ...)` returns an interpolated FIR filter where you specify design options as input arguments.

To determine the available design options, use `designopts` with the specification object and the design method as input arguments as shown.

```
designopts(d, 'method')
```

For complete help about using `ifir`, refer to the command line help system. For example, to get specific information about using `ifir` with `d`, the specification object, enter the following at the MATLAB prompt.

```
help(d, 'ifir')
```

---

**Note** For help about how you use `ifir` to design filters without using design objects, enter

```
help ifir
```


at the MATLAB prompt.

---

## Examples

Use `fdesign.lowpass` and `fdesign.highpass` to design a lowpass filter and a wideband highpass filter. After designing the filters, use `FVTool` to plot the response curves for both.

```
fpass = 0.2;  
fstop = 0.24;  
d1 = fdesign.lowpass(fpass, fstop);  
hd1 = design(d1, 'ifir');  
fstop = 0.2;  
fpass = 0.25;  
astop = 40;  
apass = 1;  
d2 = fdesign.highpass(fstop, fpass, astop, apass);  
hd2 = design(d2, 'ifir');  
fvtool(hd1, hd2)
```



**See Also**

`fdesign` | `firgr` | `fir1` | `firls` | `firpm`

<b>Purpose</b>	Transform IIR complex bandpass filter to IIR complex bandpass filter with different characteristics
<b>Syntax</b>	<code>[Num,Den,AllpassNum,AllpassDen] = iirbpc2bpc(B,A,Wo,Wt)</code>
<b>Description</b>	<p><code>[Num,Den,AllpassNum,AllpassDen] = iirbpc2bpc(B,A,Wo,Wt)</code> returns the numerator and denominator vectors, Num and Den respectively, of the target filter transformed from the complex bandpass prototype by applying a first-order complex bandpass to complex bandpass frequency transformation.</p> <p>It also returns the numerator, AllpassNum, and the denominator, AllpassDen, of the allpass mapping filter. The prototype lowpass filter is given with the numerator specified by B and the denominator specified by A.</p> <p>This transformation effectively places two features of an original filter, located at frequencies <math>W_{o1}</math> and <math>W_{o2}</math>, at the required target frequency locations, <math>W_{t1}</math>, and <math>W_{t2}</math> respectively. It is assumed that <math>W_{t2}</math> is greater than <math>W_{t1}</math>. In most of the cases the features selected for the transformation are the band edges of the filter passbands. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones.</p> <p>Relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter, <math>F_1</math> and <math>F_2</math>, with <math>F_1</math> preceding <math>F_2</math>. Feature <math>F_1</math> will still precede <math>F_2</math> after the transformation. However, the distance between <math>F_1</math> and <math>F_2</math> will not be the same before and after the transformation.</p> <p>This transformation can also be used for transforming other types of filters; e.g., complex notch filters or resonators can be repositioned at two distinct desired frequencies at any place around the unit circle; e.g., in the adaptive system.</p>
<b>Examples</b>	<p>Design a prototype real IIR halfband filter using a standard elliptic approach:</p> <pre>[b, a] = ellip(3, 0.1, 30, 0.409);</pre>

# iirbpc2bpc


Create a complex passband from 0.25 to 0.75:

```
[b, a] = iirlp2bpc (b, a, 0.5, [0.25,0.75]);  
[num, den] = iirbpc2bpc(b, a, [0.25, 0.75], [-0.5, 0.5]);
```

Verify the result by comparing the prototype filter with the target filter:

```
fvtool(b, a, num, den);
```

Using FVTool to plot the filters shows you the comparison, presented in this figure.



**Arguments**

<b>Variable</b>	<b>Description</b>
<i>B</i>	Numerator of the prototype lowpass filter
<i>A</i>	Denominator of the prototype lowpass filter
<i>Wo</i>	Frequency values to be transformed from the prototype filter
<i>Wt</i>	Desired frequency locations in the transformed target filter
<i>Num</i>	Numerator of the target filter
<i>Den</i>	Denominator of the target filter
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

Frequencies must be normalized to be between -1 and 1, with 1 corresponding to half the sample rate.

**See Also**

`iirftransf` | `allpassbpc2bpc` | `zpkbpc2bpc`

# iircomb

---

**Purpose** IIR comb notch or peak filter

**Syntax**  
`[num,den] = iircomb(n,bw)`  
`[num,den] = iircomb(n,bw,ab)`  
`[num,den] = iircomb(...,'type')`

**Description** `[num,den] = iircomb(n,bw)` returns a digital notching filter with order  $n$  and with the width of the filter notch at -3 dB set to  $bw$ , the filter bandwidth. The filter order must be a positive integer.  $n$  also defines the number of notches in the filter across the frequency range from 0 to  $2\pi$  — the number of notches equals  $n+1$ .

For the notching filter, the transfer function takes the form

$$H(z) = b \frac{1 - z^{-n}}{1 - \alpha z^{-n}}$$

where  $\alpha$  and  $b$  are the positive scalars and  $n$  is the filter order or the number of notches in the filter minus 1.

The quality factor (Q factor)  $q$  for the filter is related to the filter bandwidth by  $q = \omega_0/bw$  where  $\omega_0$  is the frequency to remove from the signal.

`[num,den] = iircomb(n,bw,ab)` returns a digital notching filter whose bandwidth,  $bw$ , is specified at a level of  $-ab$  decibels. Including the optional input argument  $ab$  lets you specify the magnitude response bandwidth at a level that is not the default -3 dB point, such as -6 dB or 0 dB.

`[num,den] = iircomb(...,'type')` returns a digital filter of the specified type. The input argument `type` can be either

- 'notch' to design an IIR notch filter. Notch filters attenuate the response at the specified frequencies. This is the default type. When you omit the `type` input argument, `iircomb` returns a notch filter.
- 'peak' to design an IIR peaking filter. Peaking filters boost the signal at the specified frequencies.

The transfer function for peaking filters is


$$H(z) = b \frac{1 - z^{-n}}{1 + az^{-n}}$$

## Examples

Design and plot an IIR notch filter with 11 notches (equal to filter order plus 1) that removes a 60 Hz tone (f0) from a signal at 600 Hz (fs). For this example, set the Q factor for the filter to 35 and use it to specify the filter bandwidth.

```
fs = 600; fo = 60; q = 35; bw = (fo/(fs/2))/q;  
[b,a] = iircomb(fs/fo,bw,'notch'); % Note type flag 'notch'  
fvtool(b,a);
```

Using the Filter Visualization Tool (FVTool) generates the following plot showing the filter notches. Note the notches are evenly spaced and one falls at exactly 60 Hz.




**See Also** [firgr](#) | [iirnotch](#) | [iirpeak](#)

---

<b>Purpose</b>	IIR frequency transformation of filter
<b>Syntax</b>	<code>[OutNum,OutDen] = iirftransf(OrigNum,OrigDen,FTFNum,FTFDen)</code>
<b>Description</b>	<code>[OutNum,OutDen] = iirftransf(OrigNum,OrigDen,FTFNum,FTFDen)</code> returns the numerator and denominator vectors, <code>OutNum</code> and <code>OutDen</code> , of the target filter, which is the result of transforming the prototype filter specified by the numerator, <code>OrigNum</code> , and denominator, <code>OrigDen</code> , with the mapping filter given by the numerator, <code>FTFNum</code> , and the denominator, <code>FTFDen</code> . If the allpass mapping filter is not specified, then the function returns an original filter.
<b>Examples</b>	<p>Design a prototype real IIR halfband filter using a standard elliptic approach:</p> <pre>[b, a] = ellip(3, 0.1, 30, 0.409); [AlpNum, AlpDen] = allpasslp2lp(0.5, 0.25); [num, den] = iirftransf(b, a, AlpNum, AlpDen);</pre> <p>Verify the result by comparing the prototype filter with the target filter:</p> <pre>fvtool(b, a, num, den);</pre> <p>Here's the comparison between the filters.</p>

# iirtransf



## Arguments

Variable	Description
<i>OrigNum</i>	Numerator of the prototype lowpass filter
<i>OrigDen</i>	Denominator of the prototype lowpass filter
<i>FTFNum</i>	Numerator of the mapping filter
<i>FTFDen</i>	Denominator of the mapping filter
<i>OutNum</i>	Numerator of the target filter
<i>OutDen</i>	Denominator of the target filter

## See Also

`zpkftransf`

**Purpose**

Optimal IIR filter with prescribed group-delay

**Syntax**

```
[num,den] = iirgrpdelay(n,f,edges,a)
[num,den] = iirgrpdelay(n,f,edges,a,w)
[num,den] = iirgrpdelay(n,f,edges,a,w,radius)
[num,den] = iirgrpdelay(n,f,edges,a,w,radius,p)
[num,den] = iirgrpdelay(n,f,edges,a,w,radius,p,dens)
[num,den] = iirgrpdelay(n,f,edges,a,w,radius,p,dens,initden)
[num,den] = iirgrpdelay(n,f,edges,a,w,radius,p,dens,initden,
    tau)
[num,den,tau] = iirgrpdelay(n,f,edges,a,w)
```

**Description**

`[num,den] = iirgrpdelay(n,f,edges,a)` returns an allpass IIR filter of order  $n$  ( $n$  must be even) which is the best approximation to the relative group-delay response described by  $f$  and  $a$  in the least-pth sense.  $f$  is a vector of frequencies between 0 and 1 and  $a$  is specified in samples. The vector  $edges$  specifies the band-edge frequencies for multi-band designs. `iirgrpdelay` uses a constrained Newton-type algorithm. Always check your resulting filter using `grpdelay` or `freqz`.

`[num,den] = iirgrpdelay(n,f,edges,a,w)` uses the weights in  $w$  to weight the error.  $w$  has one entry per frequency point and must be the same length as  $f$  and  $a$ ). Entries in  $w$  tell `iirgrpdelay` how much emphasis to put on minimizing the error in the vicinity of each specified frequency point relative to the other points.

$f$  and  $a$  must have the same number of elements.  $f$  and  $a$  can contain more elements than the vector  $edges$  contains. This lets you use  $f$  and  $a$  to specify a filter that has any group-delay contour within each band.

`[num,den] = iirgrpdelay(n,f,edges,a,w,radius)` returns a filter having a maximum pole radius equal to  $radius$ , where  $0 < radius < 1$ .  $radius$  defaults to 0.999999. Filters whose pole radius you constrain to be less than 1.0 can better retain transfer function accuracy after quantization.

`[num,den] = iirgrpdelay(n,f,edges,a,w,radius,p)`, where  $p$  is a two-element vector  $[pmin \ pmax]$ , lets you determine the minimum and maximum values of  $p$  used in the least-pth algorithm.  $p$  defaults to  $[2$

128] which yields filters very similar to the L-infinity, or Chebyshev, norm. `pmin` and `pmax` should be even. If `p` is the string 'inspect', no optimization occurs. You might use this feature to inspect the initial pole/zero placement.

`[num,den] = iirgrpdelay(n,f,edges,a,w,radius,p,dens)` specifies the grid density `dens` used in the optimization process. The number of grid points is  $(dens*(n+1))$ . The default is 20. `dens` can be specified as a single-element cell array. The grid is not equally spaced.

`[num,den] = iirgrpdelay(n,f,edges,a,w,radius,p,dens,initden)` allows you to specify the initial estimate of the denominator coefficients in vector `initden`. This can be useful for difficult optimization problems. The pole-zero editor in Signal Processing Toolbox software can be used for generating `initden`.

`[num,den] = iirgrpdelay(n,f,edges,a,w,radius,p,dens,initden,tau)` allows the initial estimate of the group delay offset to be specified by the value of `tau`, in samples.

`[num,den,tau] = iirgrpdelay(n,f,edges,a,w)` returns the resulting group delay offset. In all cases, the resulting filter has a group delay that approximates  $[a + \tau]$ . Allpass filters can have only positive group delay and a non-zero value of `tau` accounts for any additional group delay that is needed to meet the shape of the contour specified by  $(f,a)$ . The default for `tau` is `max(a)`.

Hint: If the zeros or poles cluster together, your filter order may be too low or the pole radius may be too small (overly constrained). Try increasing `n` or `radius`.

For group-delay equalization of an IIR filter, compute `a` by subtracting the filter's group delay from its maximum group delay. For example,

```
[be,ae] = ellip(4,1,40,0.2);  
f = 0:0.001:0.2;  
g = grpdelay(be,ae,f,2); % Equalize only the passband.  
a = max(g)-g;
```

```
[num,den]=iirgrpdelay(8, f, [0 0.2], a);
```

## References

Antoniou, A., *Digital Filters: Analysis, Design, and Applications*, Second Edition, McGraw-Hill, Inc. 1993.

## See Also

freqz | filter | grpdelay | iirlpnorm | iirlpnormc | zplane

# iirlinphase

---

**Purpose** Quasi-linear phase IIR filter from halfband filter specification

**Syntax**  
`hd = design(d, 'iirlinphase')`  
`hd = design(..., 'filterstructure', structure)`

**Description** `hd = design(d, 'iirlinphase')` designs a quasi-linear phase filter `hd` specified by the filter specification object `d`.

`hd = design(..., 'filterstructure', structure)` returns a filter with the structure specified by `structure`. By default, the filter structure is `df2sos` (direct-form II with second-order sections). You can substitute one of the following strings for `structure` to specify the structure of `hd`.


Structure String	Filter Structure
<code>df1sos</code>	Direct-form I IIR filter with second-order sections
<code>df2sos</code>	Direct-form II IIR filter with second-order sections
<code>df1tsos</code>	Transposed direct-form I IIR filter with second-order sections
<code>df2tsos</code>	Transposed direct-form II IIR filter with second-order sections

**Examples** Design a quasi-linear phase, minimum-order halfband IIR filter with transition width of 0.36 and stopband attenuation of at least 80 dB.

```
tw = 0.36;  
ast = 80;  
d = fdesign.halfband('tw,ast',tw,ast); % Transition width,  
                                     % stopband attenuation.  
hd = design(d, 'iirlinphase');  
fvtool(hd)
```

Notice the characteristic halfband nature of the ripple in the stopband. If you measure the resulting filter, you see it meets the specifications.

measure (hd)



**See Also**

`fdesign.halfband`

**Purpose** Transform IIR lowpass filter to IIR bandpass filter

**Syntax**  $[Num, Den, AllpassNum, AllpassDen] = iirlp2bp(B, A, Wo, Wt)$   
 $[G, AllpassNum, AllpassDen] = iirlp2bp(Hd, Wo, Wt)$   
where Hd is a `dfilt` object

**Description**  $[Num, Den, AllpassNum, AllpassDen] = iirlp2bp(B, A, Wo, Wt)$  returns the numerator and denominator vectors, Num and Den respectively, of the target filter transformed from the real lowpass prototype by applying a second-order real lowpass to real bandpass frequency mapping.

It also returns the numerator, AllpassNum, and the denominator AllpassDen, of the allpass mapping filter. The prototype lowpass filter is given with a numerator specified by B and a denominator specified by A.

This transformation effectively places one feature of an original filter, located at frequency  $-W_o$ , at the required target frequency location,  $W_{t1}$ , and the second feature, originally at  $+W_o$ , at the new location,  $W_{t2}$ . It is assumed that  $W_{t2}$  is greater than  $W_{t1}$ . This transformation implements the “DC Mobility,” meaning that the Nyquist feature stays at Nyquist, but the DC feature moves to a location dependent on the selection of  $W_t$ s.

Relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter,  $F_1$  and  $F_2$ , with  $F_1$  preceding  $F_2$ . Feature  $F_1$  will still precede  $F_2$  after the transformation. However, the distance between  $F_1$  and  $F_2$  will not be the same before and after the transformation.

Choice of the feature subject to the lowpass to bandpass transformation is not restricted only to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature: the stopband edge, the DC, the deep minimum in the stopband, or other ones.

Real lowpass to bandpass transformation can also be used for transforming other types of filters; e.g., real notch filters or resonators can be doubled and positioned at two distinct desired frequencies.

`[G,AllpassNum,AllpassDen] = iir1p2bp(Hd,Wo,Wt)` returns transformed `dfilt` object `G` with a real bandpass magnitude response. The coefficients `AllpassNum` and `AllpassDen` represent the allpass mapping filter for mapping the prototype filter frequency `Wo` and target frequencies vector `Wt`. Note that in this syntax `Hd` is a `dfilt` object with a lowpass magnitude response.

## Examples

Design a prototype real IIR halfband filter using a standard elliptic approach:

```
[b,a] = ellip(3, 0.1, 30, 0.409);
```


Create the real bandpass filter by placing the cutoff frequencies of the prototype filter at the band edge frequencies  $W_{t1}=0.25$  and  $W_{t2}=0.75$ :

```
[num,den] = iir1p2bp(b,a,0.5,[0.25,0.75]);
```

Verify the result by comparing the prototype filter with the target filter:

```
fvtool(b,a,num,den);
```

You can compare the results in this figure to verify the transformation.



## Arguments

Variable	Description
$B$	Numerator of the prototype lowpass filter
$A$	Denominator of the prototype lowpass filter
$W_0$	Frequency value to be transformed from the prototype filter
$W_t$	Desired frequency locations in the transformed target filter
$Num$	Numerator of the target filter
$Den$	Denominator of the target filter
$AllpassNum$	Numerator of the mapping filter
$AllpassDen$	Denominator of the mapping filter

---

Frequencies must be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.

## References

Constantinides, A.G., "Spectral transformations for digital filters," *IEEE Proceedings*, vol. 117, no. 8, pp. 1585-1590, August 1970.

Nowrouzian, B. and A.G. Constantinides, "Prototype reference transfer function parameters in the discrete-time frequency transformations," *Proceedings 33rd Midwest Symposium on Circuits and Systems*, Calgary, Canada, vol. 2, pp. 1078-1082, August 1990.

Nowrouzian, B. and L.T. Bruton, "Closed-form solutions for discrete-time elliptic transfer functions," *Proceedings of the 35th Midwest Symposium on Circuits and Systems*, vol. 2, pp. 784-787, 1992.

Constantinides, A.G., "Design of bandpass digital filters," *IEEE Proceedings*, vol. 1, pp. 1129-1231, June 1969.

## See Also

iirftransf | allpass1p2bp | zpklp2bp

<b>Purpose</b>	IIR lowpass to complex bandpass transformation
<b>Syntax</b>	<pre>[Num,Den,AllpassNum,AllpassDen] = iirlp2bpc(B,A,Wo,Wt) [G,AllpassNum,AllpassDen] = iirlp2bpc(Hd,Wo,Wt)</pre> where Hd is a <code>dfilt</code> object
<b>Description</b>	<p><code>[Num,Den,AllpassNum,AllpassDen] = iirlp2bpc(B,A,Wo,Wt)</code> returns the numerator and denominator vectors, Num and Den respectively, of the target filter transformed from the real lowpass prototype by applying a first-order real lowpass to complex bandpass frequency transformation.</p> <p>It also returns the numerator, AllpassNum, and the denominator, AllpassDen, of the allpass mapping filter. The prototype lowpass filter is given with a numerator specified by B and a denominator specified by A.</p> <p>This transformation effectively places one feature of an original filter, located at frequency <math>-W_o</math>, at the required target frequency location, <math>W_{t1}</math>, and the second feature, originally at <math>+W_o</math>, at the new location, <math>W_{t2}</math>. It is assumed that <math>W_{t2}</math> is greater than <math>W_{t1}</math>.</p> <p>Relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter, <math>F_1</math> and <math>F_2</math>, with <math>F_1</math> preceding <math>F_2</math>. Feature <math>F_1</math> will still precede <math>F_2</math> after the transformation. However, the distance between <math>F_1</math> and <math>F_2</math> will not be the same before and after the transformation.</p> <p>Choice of the feature subject to the lowpass to bandpass transformation is not restricted only to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones.</p> <p>Lowpass to bandpass transformation can also be used for transforming other types of filters; for example real notch filters or resonators can be doubled and positioned at two distinct desired frequencies at any place around the unit circle forming a pair of complex notches/resonators. This transformation can be used for designing bandpass filters for radio receivers from the high-quality prototype lowpass filter.</p>

`[G,AllpassNum,AllpassDen] = iirlp2bpc(Hd,Wo,Wt)` returns transformed `dfilt` object `G` with a bandpass magnitude response. The coefficients `AllpassNum` and `AllpassDen` represent the allpass mapping filter for mapping the prototype filter frequency `Wo` and the target frequencies vector `Wt`. Note that in this syntax `Hd` is a `dfilt` object with a lowpass magnitude response.

## Examples

Design a prototype real IIR halfband filter using a standard elliptic approach:

```
[b, a] = ellip(3, 0.1, 30, 0.409);
```


Move the cutoffs of the prototype filter to the new locations  $W_{t1}=0.25$  and  $W_{t2}=0.75$  creating a complex bandpass filter:

```
[num, den] = iirlp2bpc(b, a, 0.5, [0.25, 0.75]);
```

Verify the result by comparing the prototype filter with the target filter:

```
fvtool(b, a, num, den);
```

Plotting the prototype and target filters together in FVTool lets you compare the filters.



## Arguments

Variable	Description
$B$	Numerator of the prototype lowpass filter
$A$	Denominator of the prototype lowpass filter
$W_0$	Frequency value to be transformed from the prototype filter. It should be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.
$W_t$	Desired frequency locations in the transformed target filter. They should be normalized to be between -1 and 1, with 1 corresponding to half the sample rate.
$Num$	Numerator of the target filter

<b>Variable</b>	<b>Description</b>
<i>Den</i>	Denominator of the target filter
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

## See Also

`iirftransf` | `allpasslp2bpc` | `zpklp2bpc`

**Purpose**

Transform IIR lowpass filter to IIR bandstop filter

**Syntax**

```
[Num,Den,AllpassNum,AllpassDen] = iirlp2bs(B,A,Wo,Wt)
[G,AllpassNum,AllpassDen] = iirlp2bs(Hd,Wo,Wt)
```

where Hd is a `dfilt` object

**Description**

`[Num,Den,AllpassNum,AllpassDen] = iirlp2bs(B,A,Wo,Wt)` returns the numerator and denominator vectors, Num and Den respectively, of the target filter transformed from the real lowpass prototype by applying a second-order real lowpass to real bandstop frequency mapping.

It also returns the numerator, AllpassNum, and the denominator, AllpassDen, of the allpass mapping filter. The prototype lowpass filter is given with a numerator specified by B and a denominator specified by A.

This transformation effectively places one feature of an original filter, located at frequency  $-W_o$ , at the required target frequency location,  $W_{t1}$ , and the second feature, originally at  $+W_o$ , at the new location,  $W_{t2}$ . It is assumed that  $W_{t2}$  is greater than  $W_{t1}$ . This transformation implements the "Nyquist Mobility," which means that the DC feature stays at DC, but the Nyquist feature moves to a location dependent on the selection of  $W_o$  and  $W_t$ s.

Relative positions of other features of an original filter change in the target filter. This means that it is possible to select two features of an original filter,  $F_1$  and  $F_2$ , with  $F_1$  preceding  $F_2$ . After the transformation feature  $F_2$  will precede  $F_1$  in the target filter. However, the distance between  $F_1$  and  $F_2$  will not be the same before and after the transformation.

Choice of the feature subject to the lowpass to bandstop transformation is not restricted only to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones.

`[G,AllpassNum,AllpassDen] = iirlp2bs(Hd,Wo,Wt)` returns transformed `dfilt` object G with a bandstop magnitude response. The coefficients AllpassNum and AllpassDen represent the allpass mapping

filter for mapping the prototype filter frequency  $\omega_0$  and the target frequencies vector  $\omega_t$ . Note that in this syntax `Hd` is a `dfilt` object with a lowpass magnitude response.

## Examples

Design a prototype real IIR halfband filter using a standard elliptic approach:


```
[b, a] = ellip(3, 0.1, 30, 0.409);
```

Create the real bandstop filter by placing the cutoff frequencies of the prototype filter at the band edge frequencies  $\omega_{t1}=0.25$  and  $\omega_{t2}=0.75$ :

```
[num, den] = iirlp2bs(b, a, 0.5, [0.25, 0.75]);
```

Verify the result by comparing the prototype filter with the target filter:

```
fvtool(b, a, num, den);
```



With both filters plotted in the figure, you see clearly the results of the transformation.

## Arguments

Variable	Description
$B$	Numerator of the prototype lowpass filter
$A$	Denominator of the prototype lowpass filter
$W_o$	Frequency value to be transformed from the prototype filter
$W_t$	Desired frequency locations in the transformed target filter
$Num$	Numerator of the target filter
$Den$	Denominator of the target filter
$AllpassNum$	Numerator of the mapping filter
$AllpassDen$	Denominator of the mapping filter

Frequencies must be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.

## References

Constantinides, A.G., "Spectral transformations for digital filters," *IEEE Proceedings*, vol. 117, no. 8, pp. 1585-1590, August 1970.

Nowrouzian, B. and A.G. Constantinides, "Prototype reference transfer function parameters in the discrete-time frequency transformations," *Proceedings 33rd Midwest Symposium on Circuits and Systems*, Calgary, Canada, vol. 2, pp. 1078-1082, August 1990.

Nowrouzian, B. and L.T. Bruton, "Closed-form solutions for discrete-time elliptic transfer functions," *Proceedings of the 35th Midwest Symposium on Circuits and Systems*, vol. 2, pp. 784-787, 1992.

Constantinides, A.G., "Design of bandpass digital filters," *IEEE Proceedings*, vol. 1, pp. 1129-1231, June 1969.

**See Also**     [iirftransf](#) | [allpasslp2bs](#) | [zpk1p2bs](#)

**Purpose** Transform IIR lowpass filter to IIR complex bandstop filter

**Syntax** `[Num,Den,AllpassNum,AllpassDen] = iirlp2bsc(B,A,Wo,Wt)`  
`[G,AllpassNum,AllpassDen] = iirlp2bsc(Hd,Wo,Wt)`  
where Hd is a `dfilt` object

**Description** `[Num,Den,AllpassNum,AllpassDen] = iirlp2bsc(B,A,Wo,Wt)` returns the numerator and denominator vectors, Num and Den respectively, of the target filter transformed from the real lowpass prototype by applying a first-order real lowpass to complex bandstop frequency transformation.

It also returns the numerator, AllpassNum, and the denominator, AllpassDen, of the allpass mapping filter. The prototype lowpass filter is given with a numerator specified by B and the denominator specified by A.

This transformation effectively places one feature of an original filter, located at frequency  $-W_o$ , at the required target frequency location,  $W_{t1}$ , and the second feature, originally at  $+W_o$ , at the new location,  $W_{t2}$ . It is assumed that  $W_{t2}$  is greater than  $W_{t1}$ . Additionally the transformation swaps passbands with stopbands in the target filter.

Relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter,  $F_1$  and  $F_2$ , with  $F_1$  preceding  $F_2$ . Feature  $F_1$  will still precede  $F_2$  after the transformation. However, the distance between  $F_1$  and  $F_2$  will not be the same before and after the transformation.

Choice of the feature subject to the lowpass to bandstop transformation is not restricted only to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones.

Lowpass to bandpass transformation can also be used for transforming other types of filters; e.g., real notch filters or resonators can be doubled and positioned at two distinct desired frequencies at any place around the unit circle forming a pair of complex notches/resonators. This transformation can be used for designing bandstop filters for band

attenuation or frequency equalizers, from the high-quality prototype lowpass filter.

`[G,AllpassNum,AllpassDen] = iirlp2bsc(Hd,Wo,Wt)` returns transformed `dfilt` object `G` with a bandstop magnitude response. The coefficients `AllpassNum` and `AllpassDen` represent the allpass mapping filter for mapping the prototype filter frequency `Wo` and the target frequencies vector `Wt`. Note that in this syntax `Hd` is a `dfilt` object with a lowpass magnitude response.

## Examples

Design a prototype real IIR halfband filter using a standard elliptic approach:

```
[b, a] = ellip(3, 0.1, 30, 0.409);
```


Move the cutoffs of the prototype filter to the new locations  $W_{t1}=0.25$  and  $W_{t2}=0.75$  creating a complex bandstop filter:

```
[num, den] = iirlp2bsc(b, a, 0.5, [0.25, 0.75]);
```

Verify the result by comparing the prototype filter with the target filter:

```
fvtool(b, a, num, den);
```

The last command in the example plots both filters in the same window so you can compare the results.



## Arguments

Variable	Description
$B$	Numerator of the prototype lowpass filter
$A$	Denominator of the prototype lowpass filter
$W_0$	Frequency value to be transformed from the prototype filter. It should be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.
$W_t$	Desired frequency locations in the transformed target filter. They should be normalized to be between -1 and 1, with 1 corresponding to half the sample rate.

<b>Variable</b>	<b>Description</b>
<i>Num</i>	Numerator of the target filter
<i>Den</i>	Denominator of the target filter
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

**See Also**

`iirftransf` | `allpasslp2bsc` | `zpklp2bsc`

# iirlp2hp

---

**Purpose** Transform lowpass IIR filter to highpass filter

**Syntax** `[num,den] = iirlp2hp(b,a,wc,wd)`  
`[G,AllpassNum,AllpassDen] = iirlp2hp(Hd,Wo,Wt)`  
where Hd is a `dfilt` object

**Description** `[num,den] = iirlp2hp(b,a,wc,wd)` with input arguments `b` and `a`, the numerator and denominator coefficients (zeros and poles) for a lowpass IIR filter, `iirlp2hp` transforms the magnitude response from lowpass to highpass. `num` and `den` return the coefficients for the transformed highpass filter. For `wc`, enter a selected frequency from your lowpass filter. You use the chosen frequency to define the magnitude response value you want in the highpass filter. Enter one frequency for the highpass filter — the value that defines the location of the transformed point — in `wd`. Note that all frequencies are normalized between zero and one. Notice also that the filter order does not change when you transform to a highpass filter.

When you select `wc` and designate `wd`, the transformation algorithm sets the magnitude response at the `wd` values of your bandstop filter to be the same as the magnitude response of your lowpass filter at `wc`. Filter performance between the values in `wd` is not specified, except that the stopband retains the ripple nature of your original lowpass filter and the magnitude response in the stopband is equal to the peak response of your lowpass filter. To accurately specify the filter magnitude response across the stopband of your bandpass filter, use a frequency value from within the stopband of your lowpass filter as `wc`. Then your bandstop filter response is the same magnitude and ripple as your lowpass filter stopband magnitude and ripple.

The fact that the transformation retains the shape of the original filter is what makes this function useful. If you have a lowpass filter whose characteristics, such as rolloff or passband ripple, particularly meet your needs, the transformation function lets you create a new filter with the same characteristic performance features, but in a highpass version. Without designing the highpass filter from the beginning.


In some cases transforming your filter may cause numerical problems, resulting in incorrect conversion to the highpass filter. Use `fvtool` to verify the response of your converted filter.

`[G,AllpassNum,AllpassDen] = iirlp2hp(Hd,Wo,Wt)` returns transformed `dfilt` object `G` with a highpass magnitude response. The coefficients `AllpassNum` and `AllpassDen` represent the allpass mapping filter for mapping the prototype filter frequency `Wo` and the target frequencies vector `Wt`. Note that in this syntax `Hd` is a `dfilt` object with a lowpass magnitude response.

## Examples

This example transforms an IIR filter from lowpass to high pass by moving the magnitude response at one frequency in the source filter to a new location in the transformed filter. To generate a highpass filter whose passband flattens out at 0.4, select the frequency in the lowpass filter where the passband starts to rolloff (`wc = 0.0175`) and move it to the new location at `wd = 0.4`.

```
[b,a] = iirlpnorm(10,6,[0 0.0175 0.02 0.0215 0.025 1],...  
[0 0.0175 0.02 0.0215 0.025 1],[1 1 0 0 0 0],...  
[1 1 1 1 10 10]);  
wc = 0.0175;  
wd = 0.4;  
[num,den] = iirlp2hp(b,a,wc,wd);  
fvtool(b,a,num,den);
```



In the figure showing the magnitude responses for the two filters, the transition band for the highpass filter is essentially the mirror image of the transition for the lowpass filter from 0.0175 to 0.025, stretched out over a wider frequency range. In the passbands, the filter share common ripple characteristics and magnitude.

## References

Mitra, Sanjit K., *Digital Signal Processing. A Computer-Based Approach*, Second Edition, McGraw-Hill, 2001.

## See Also

[iirlp2bp](#) | [iirlp2bs](#) | [iirlp2lp](#) | [fir1p2lp](#) | [fir1p2hp](#)

**Purpose** Transform lowpass IIR filter to different lowpass filter

**Syntax** `[num,den] = iirlp2hp(b,a,wc,wd)`  
`[G,AllpassNum,AllpassDen] = iirlp2lp(Hd,Wo,Wt)`  
where Hd is a `dfilt` object

**Description** `[num,den] = iirlp2hp(b,a,wc,wd)` with input arguments `b` and `a`, the numerator and denominator coefficients (zeros and poles) for a lowpass IIR filter, `iirlp2hp` transforms the magnitude response from lowpass to highpass. `num` and `den` return the coefficients for the transformed highpass filter. For `wc`, enter a selected frequency from your lowpass filter. You use the chosen frequency to define the magnitude response value you want in the highpass filter. Enter one frequency for the highpass filter — the value that defines the location of the transformed point — in `wd`. Note that all frequencies are normalized between zero and one. Notice also that the filter order does not change when you transform to a highpass filter.

When you select `wc` and designate `wd`, the transformation algorithm sets the magnitude response at the `wd` values of your bandstop filter to be the same as the magnitude response of your lowpass filter at `wc`. Filter performance between the values in `wd` is not specified, except that the stopband retains the ripple nature of your original lowpass filter and the magnitude response in the stopband is equal to the peak response of your lowpass filter. To accurately specify the filter magnitude response across the stopband of your bandpass filter, use a frequency value from within the stopband of your lowpass filter as `wc`. Then your bandstop filter response is the same magnitude and ripple as your lowpass filter stopband magnitude and ripple.

The fact that the transformation retains the shape of the original filter is what makes this function useful. If you have a lowpass filter whose characteristics, such as rolloff or passband ripple, particularly meet your needs, the transformation function lets you create a new filter with the same characteristic performance features, but in a highpass version. Without designing the highpass filter from the beginning.

In some cases transforming your filter may cause numerical problems, resulting in incorrect conversion to the highpass filter. Use `fvtool` to verify the response of your converted filter.


`[G,AllpassNum,AllpassDen] = iirlp2lp(Hd,Wo,Wt)` returns transformed `dfilt` object `G` with a lowpass magnitude response. The coefficients `AllpassNum` and `AllpassDen` represent the allpass mapping filter for mapping the prototype filter frequency `Wo` and the target frequencies vector `Wt`. Note that in this syntax `Hd` is a `dfilt` object with a lowpass magnitude response.

## Examples

This example transforms an IIR filter from lowpass to high pass by moving the magnitude response at one frequency in the source filter to a new location in the transformed filter. To generate a lowpass filter whose passband extends out to 0.2, select the frequency in the lowpass filter where the passband starts to rolloff (`wc = 0.0175`) and move it to the new location at `wd = 0.2`.

```
[b,a] = iirlpnorm(10,6,[0 0.0175 0.02 0.0215 0.025 1],...
[0 0.0175 0.02 0.0215 0.025 1],[1 1 0 0 0 0],...
[1 1 1 1 10 10]);
wc = 0.0175;
wd = 0.2;
[num,den] = iirlp2lp(b,a,wc,wd);
fvtool(b,a,num,den);
```

Moving the edge of the passband from 0.0175 to 0.2 results in a new lowpass filter whose peak response in-band is the same as the original filter: same ripple, same absolute magnitude.



The rolloff is slightly less steep and the stopband profiles are the same for both filters; the new filter stopband is a “stretched” version of the original, as is the passband of the new filter.

## References

Mitra, Sanjit K, *Digital Signal Processing. A Computer-Based Approach*, Second Edition, McGraw-Hill, 2001.

## See Also

[iirlp2bp](#) | [iirlp2bs](#) | [iirlp2hp](#) | [firlp2lp](#) | [firlp2hp](#)

# iirlp2mb

---

**Purpose** Transform IIR lowpass filter to IIR M-band filter

**Syntax**

```
[Num,Den,AllpassNum,AllpassDen] = iirlp2mb(B,A,Wo,Wt)
[Num,Den,AllpassNum,AllpassDen]=iirlp2mb(B,A,Wo,Wt,Pass)
[G,AllpassNum,AllpassDen] = iirlp2mb(Hd,Wo,Wt)
[G,AllpassNum,AllpassDen] = iirlp2mb(...,Pass)
```

**Description** [Num,Den,AllpassNum,AllpassDen] = iirlp2mb(B,A,Wo,Wt) returns the numerator and denominator vectors, Num and Den respectively, of the target filter transformed from the real lowpass prototype by applying an Mth-order real lowpass to real multiple bandpass frequency mapping. By default the DC feature is kept at its original location.

[Num,Den,AllpassNum,AllpassDen]=iirlp2mb(B,A,Wo,Wt,Pass) allows you to specify an additional parameter, Pass, which chooses between using the “DC Mobility” and the “Nyquist Mobility.” In the first case the Nyquist feature stays at its original location and the DC feature is free to move. In the second case the DC feature is kept at an original frequency and the Nyquist feature is movable.

It also returns the numerator, AllpassNum, and the denominator, AllpassDen, of the allpass mapping filter. The prototype lowpass filter is given with a numerator specified by B and a denominator specified by A.

This transformation effectively places one feature of an original filter, located at frequency  $W_o$ , at the required target frequency locations,  $W_{t1}, \dots, W_{tM}$ .

Relative positions of other features of an original filter do not change in the target filter. It is possible to select two features of an original filter,  $F_1$  and  $F_2$ , with  $F_1$  preceding  $F_2$ . Feature  $F_1$  will still precede  $F_2$  after the transformation. However, the distance between  $F_1$  and  $F_2$  will not be the same before and after the transformation.

Choice of the feature subject to this transformation is not restricted to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones.

This transformation can also be used for transforming other types of filters; e.g., notch filters or resonators can be easily replicated at a number of required frequency locations. A good application would be an adaptive tone cancellation circuit reacting to the changing number and location of tones.

`[G,AllpassNum,AllpassDen] = iirlp2mb(Hd,Wo,Wt)` returns transformed `dfilt` object `G` with an IIR real `M`-band filter frequency response. The coefficients `AllpassNum` and `AllpassDen` represent the allpass mapping filter for mapping the prototype filter frequency `Wo` and the target frequencies vector `Wt`. Note that in this syntax `Hd` is a `dfilt` object with a lowpass magnitude response.

`[G,AllpassNum,AllpassDen] = iirlp2mb(...,Pass)` returns transformed `dfilt` object `G` with an IIR real `M`-band filter frequency response. This syntax allows you to specify an additional parameter, `Pass`, which chooses between using the “DC Mobility” and the “Nyquist Mobility.” In the first case the Nyquist feature stays at its original location and the DC feature is free to move. In the second case the DC feature is kept at an original frequency and the Nyquist feature is allowed to move.

The coefficients `AllpassNum` and `AllpassDen` represent the allpass mapping filter for mapping the prototype filter frequency `Wo` and the target frequencies vector `Wt`. Note that in this syntax `Hd` is a `dfilt` object with a lowpass magnitude response.

## Examples

Design a prototype real IIR halfband filter using a standard elliptic approach:

```
[b, a] = ellip(3, 0.1, 30, 0.409);
```

### Example 1

Create the real multiband filter with two passbands:

```
[num1, den1] = iirlp2mb(b, a, 0.5, [2 4 6 8]/10);
[num2, den2] = iirlp2mb(b, a, 0.5, [2 4 6 8]/10, 'pass');
```

The second code snippet uses the `pass` option to select the Nyquist mobility option. In this case the resulting filter is the same.

## Example 2


Create the real multiband filter with two stopbands:

```
[num3, den3] = iirlp2mb(b, a, 0.5, [2 4 6 8]/10, 'stop');
```

Verify the result by comparing the prototype filter with target filters:

```
fvtool(b, a, num1, den1, num2, den2, num3, den3);
```

Combining all of the filters, prototypes and targets, on one figure makes comparing them straightforward. Passbands for the filters in example 1 appear separately in the figure, although they overlap to a degree that makes them hard to identify — they have identical coefficients.



## Arguments

Variable	Description
$B$	Numerator of the prototype lowpass filter
$A$	Denominator of the prototype lowpass filter
$\omega_0$	Frequency value to be transformed from the prototype filter
$\omega_t$	Desired frequency locations in the transformed target filter
$Pass$	Choice ('pass' / 'stop') of passband/stopband at DC, 'pass' being the default
$Num$	Numerator of the target filter

Variable	Description
<i>Den</i>	Denominator of the target filter
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

Frequencies must be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.

## References

Franchitti, J.C., "All-pass filter interpolation and frequency transformation problems," *MSc Thesis*, Dept. of Electrical and Computer Engineering, University of Colorado, 1985.

Feyh, G., J.C. Franchitti and C.T. Mullis, "All-pass filter interpolation and frequency transformation problem," *Proceedings 20th Asilomar Conference on Signals, Systems and Computers*, Pacific Grove, California, pp. 164-168, November 1986.

Mullis, C.T. and R. A. Roberts, *Digital Signal Processing*, section 6.7, Reading, Mass., Addison-Wesley, 1987.

Feyh, G., W.B. Jones and C.T. Mullis, "An extension of the Schur Algorithm for frequency transformations," *Linear Circuits, Systems and Signal Processing: Theory and Application*, C. J. Byrnes et al Eds, Amsterdam: Elsevier, 1988.

## See Also

`iirftransf` | `allpasslp2mb` | `zpklp2mb`

**Purpose**

Transform IIR lowpass filter to IIR complex M-band filter

**Syntax**

```
[Num,Den,AllpassNum,AllpassDen] = iirlp2mbc(B,A,Wo,Wc)
[G,AllpassNum,AllpassDen] = iirlp2mbc(Hd,Wo,Wt)
```

where Hd is a `dfilt` object

**Description**

`[Num,Den,AllpassNum,AllpassDen] = iirlp2mbc(B,A,Wo,Wc)` returns the numerator and denominator vectors, `Num` and `Den` respectively, of the target filter transformed from the real lowpass prototype by applying an `M`th-order real lowpass to complex multibandpass frequency transformation.

It also returns the numerator, `AllpassNum`, and the denominator, `AllpassDen`, of the allpass mapping filter. The prototype lowpass filter is given with a numerator specified by `B` and a denominator specified by `A`.

This transformation effectively places one feature of an original filter, located at frequency  $W_o$ , at the required target frequency locations,  $W_{t1}, \dots, W_{tM}$ .

Relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter,  $F_1$  and  $F_2$ , with  $F_1$  preceding  $F_2$ . Feature  $F_1$  will still precede  $F_2$  after the transformation. However, the distance between  $F_1$  and  $F_2$  will not be the same before and after the transformation.

Choice of the feature subject to this transformation is not restricted to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones.

This transformation can also be used for transforming other types of filters; e.g., notch filters or resonators can be easily replicated at a number of required frequency locations. A good application would be an adaptive tone cancellation circuit reacting to the changing number and location of tones.

`[G,AllpassNum,AllpassDen] = iirlp2mbc(Hd,Wo,Wt)` returns transformed `dfilt` object `G` with an IIR complex `M`-band filter frequency response. The coefficients `AllpassNum` and `AllpassDen` represent the allpass mapping filter for mapping the prototype filter frequency `Wo` and the target frequencies vector `Wt`. Note that in this syntax `Hd` is a `dfilt` object with a lowpass magnitude response.

## Examples

Design a prototype real IIR halfband filter using a standard elliptic approach:


```
[b, a] = ellip(3, 0.1, 30, 0.409);
```

Now create a complex multiband filter with two passbands:

```
[num1, den1] = iirlp2mbc(b, a, 0.5, [2 4 6 8]/10);
```

Verify the result by comparing the prototype filter with the target filter:

```
fvtool(b, a, num1, den1);
```



You see in the figure that `iirlp2mbc` replicates the desired feature at 0.5 in the lowpass filter at four locations in the multiband filter.

## Arguments

Variable	Description
<i>B</i>	Numerator of the prototype lowpass filter.
<i>A</i>	Denominator of the prototype lowpass filter.
<i>W0</i>	Frequency value to be transformed from the prototype filter. It should be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.
<i>Wc</i>	Desired frequency locations in the transformed target filter. They should be normalized to be between -1 and 1, with 1 corresponding to half the sample rate.
<i>Num</i>	Numerator of the target filter.

# iirlp2mbc

---

<b>Variable</b>	<b>Description</b>
<i>Den</i>	Denominator of the target filter.
<i>AllpassNum</i>	Numerator of the mapping filter.
<i>AllpassDen</i>	Denominator of the mapping filter.

## See Also

iirftransf | allpasslp2mbc | zpklp2mbc

**Purpose**

Transform IIR lowpass filter to IIR complex N-point filter

**Syntax**

```
[Num,Den,AllpassNum,AllpassDen] = iirlp2xc(B,A,Wo,Wt)
[G,AllpassNum,AllpassDen] = iirlp2xc(Hd,Wo,Wt)
```

where Hd is a `dfilt` object

**Description**

`[Num,Den,AllpassNum,AllpassDen] = iirlp2xc(B,A,Wo,Wt)` returns the numerator and denominator vectors, Num and Den respectively, of the target filter transformed from the real lowpass prototype by applying an Nth-order real lowpass to complex multipoint frequency transformation.

It also returns the numerator, AllpassNum, and the denominator, AllpassDen, of the allpass mapping filter. The prototype lowpass filter is given with a numerator specified by B and a denominator specified by A.

Parameter N also specifies the number of replicas of the prototype filter created around the unit circle after the transformation. This transformation effectively places N features of an original filter, located at frequencies  $W_{o1}, \dots, W_{oN}$ , at the required target frequency locations,  $W_{t1}, \dots, W_{tM}$ .

Relative positions of other features of an original filter are the same in the target filter for the Nyquist mobility and are reversed for the DC mobility. For the Nyquist mobility this means that it is possible to select two features of an original filter,  $F_1$  and  $F_2$ , with  $F_1$  preceding  $F_2$ . Feature  $F_1$  will still precede  $F_2$  after the transformation. However, the distance between  $F_1$  and  $F_2$  will not be the same before and after the transformation. For DC mobility feature  $F_2$  will precede  $F_1$  after the transformation.

Choice of the feature subject to this transformation is not restricted to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., a stopband edge, DC, the deep minimum in the stopband, or other ones. The only condition is that the features must be selected in such a way that when creating N bands around the unit circle, there will be no band overlap.

This transformation can also be used for transforming other types of filters; e.g., notch filters or resonators can be easily replicated at a number of required frequency locations. A good application would be an adaptive tone cancellation circuit reacting to the changing number and location of tones.

`[G,AllpassNum,AllpassDen] = iirlp2xc(Hd,Wo,Wt)` returns transformed `dfilt` object `G` with an IIR complex `N`-point filter frequency response. The coefficients `AllpassNum` and `AllpassDen` represent the allpass mapping filter for mapping the prototype filter frequency `Wo` and the target frequencies vector `Wt`. Note that in this syntax `Hd` is a `dfilt` object with a lowpass magnitude response.

## Examples

Design a prototype real IIR halfband filter using a standard elliptic approach:

```
[b, a] = ellip(3, 0.1, 30, 0.409);
```


Create the complex bandpass filter from the real lowpass filter:

```
[num, den] = iirlp2xc(b, a, [-0.5 0.5], [-0.25 0.25]);
```

Verify the result by comparing the prototype filter with the target filter:

```
fvtool(b, a, num, den);
```

Reviewing the coefficients and the figure produced by the example shows that the target filter has complex coefficients and is indeed a bandpass filter as expected.



## Arguments

Variable	Description
$B$	Numerator of the prototype lowpass filter.
$A$	Denominator of the prototype lowpass filter.
$W_o$	Frequency values to be transformed from the prototype filter. They should be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.
$W_t$	Desired frequency locations in the transformed target filter. They should be normalized to be between -1 and 1, with 1 corresponding to half the sample rate.
$Num$	Numerator of the target filter.

# iirlp2xc

---

<b>Variable</b>	<b>Description</b>
<i>Den</i>	Denominator of the target filter.
<i>AllpassNum</i>	Numerator of the mapping filter.
<i>AllpassDen</i>	Denominator of the mapping filter.

## See Also

iirftransf | allpasslp2xc | zpklp2xc

<b>Purpose</b>	Transform IIR lowpass filter to IIR real N-point filter
<b>Syntax</b>	<pre>[Num,Den,AllpassNum,AllpassDen] = iirlp2xn(B,A,Wo,Wt) [Num,Den,AllpassNum,AllpassDen] = iirlp2xn(B,A,Wo,Wt,Pass) [G,AllpassNum,AllpassDen] = iirlp2bpc(Hd,Wo,Wt), where Hd is a dfilt object [G,AllpassNum,AllpassDen] = iirlp2bpc(...,Pass)</pre>
<b>Description</b>	<p><code>[Num,Den,AllpassNum,AllpassDen] = iirlp2xn(B,A,Wo,Wt)</code> returns the numerator and denominator vectors, <code>Num</code> and <code>Den</code> respectively, of the target filter transformed from the real lowpass prototype by applying an Nth-order real lowpass to real multipoint frequency transformation, where N is the number of features being mapped. By default the DC feature is kept at its original location.</p> <p><code>[Num,Den,AllpassNum,AllpassDen]= iirlp2xn(B,A,Wo,Wt,Pass)</code> allows you to specify an additional parameter, <code>Pass</code>, which chooses between using the "DC Mobility" and the "Nyquist Mobility." In the first case the Nyquist feature stays at its original location and the DC feature is free to move. In the second case the DC feature is kept at an original frequency and the Nyquist feature is allowed to move.</p> <p>It also returns the numerator, <code>AllpassNum</code>, and the denominator, <code>AllpassDen</code>, of the allpass mapping filter. The prototype lowpass filter is given with the numerator specified by <code>B</code> and the denominator specified by <code>A</code>.</p> <p>Parameter N also specifies the number of replicas of the prototype filter created around the unit circle after the transformation. This transformation effectively places N features of an original filter, located at frequencies <math>W_{o1}, \dots, W_{oN}</math>, at the required target frequency locations, <math>W_{t1}, \dots, W_{tM}</math>.</p> <p>Relative positions of other features of an original filter are the same in the target filter for the Nyquist mobility and are reversed for the DC mobility. For the Nyquist mobility this means that it is possible to select two features of an original filter, <math>F_1</math> and <math>F_2</math>, with <math>F_1</math> preceding <math>F_2</math>. Feature <math>F_1</math> will still precede <math>F_2</math> after the transformation. However, the distance between <math>F_1</math> and <math>F_2</math> will not be the same before and after</p>

the transformation. For DC mobility feature  $F_2$  will precede  $F_1$  after the transformation.

Choice of the feature subject to this transformation is not restricted to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones. The only condition is that the features must be selected in such a way that when creating  $N$  bands around the unit circle, there will be no band overlap.

This transformation can also be used for transforming other types of filters; e.g., notch filters or resonators can be easily replicated at a number of required frequency locations. A good application would be an adaptive tone cancellation circuit reacting to the changing number and location of tones.

`[G,AllpassNum,AllpassDen] = iirlp2xn(Hd,Wo,Wt)` returns transformed `dfilt` object `G` with an IIR real  $N$ -point filter frequency response. The coefficients `AllpassNum` and `AllpassDen` represent the allpass mapping filter for mapping the prototype filter frequency `Wo` and the target frequencies vector `Wt`. Note that in this syntax `Hd` is a `dfilt` object with a lowpass magnitude response.

`[G,AllpassNum,AllpassDen] = iirlp2xn(...,Pass)` returns transformed `dfilt` object `G` with an IIR real  $N$ -point filter frequency response. This syntax allows you to specify an additional parameter, `Pass`, which chooses between using the "DC Mobility" and the "Nyquist Mobility." In the first case the Nyquist feature stays at its original location and the DC feature is free to move. In the second case the DC feature is kept at an original frequency and the Nyquist feature is allowed to move.

The coefficients `AllpassNum` and `AllpassDen` represent the allpass mapping filter for mapping the prototype filter frequency `Wo` and the target frequencies vector `Wt`. Note that in this syntax `Hd` is a `dfilt` object with a lowpass magnitude response.

**Examples**

Design a prototype real IIR halfband filter using a standard elliptic approach:

```
[b, a] = ellip(3, 0.1, 30, 0.409);
```


Move the cutoffs of the prototype filter to the new locations  $W_{t1}=0.25$  and  $W_{t2}=0.75$  creating a real bandpass filter:

```
[num, den] = iir1p2xn(b, a, [-0.5 0.5], [0.25 0.75], ...  
pass');
```

Verify the result by comparing the prototype filter with the target filter:

```
fvtool(b, a, num, den);
```

`iir1p2xn` has created the desired bandpass filter with the cutoff locations specified in the command.



## Arguments

Variable	Description
<i>B</i>	Numerator of the prototype lowpass filter
<i>A</i>	Denominator of the prototype lowpass filter
<i>Wo</i>	Frequency values to be transformed from the prototype filter
<i>Wt</i>	Desired frequency locations in the transformed target filter
<i>Pass</i>	Choice ('pass' / 'stop') of passband/stopband at DC, 'pass' being the default
<i>Num</i>	Numerator of the target filter

Variable	Description
<i>Den</i>	Denominator of the target filter
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

Frequencies must be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.

## References

Cain, G.D., A. Krukowski and I. Kale, "High Order Transformations for Flexible IIR Filter Design," *VII European Signal Processing Conference (EUSIPCO'94)*, vol. 3, pp. 1582-1585, Edinburgh, United Kingdom, September 1994.

Krukowski, A., G.D. Cain and I. Kale, "Custom designed high-order frequency transformations for IIR filters," *38th Midwest Symposium on Circuits and Systems (MWSCAS'95)*, Rio de Janeiro, Brazil, August 1995.

## See Also

`iirftransf` | `allpass1p2xn` | `zpk1p2xn`

# iirlpnorm

---

**Purpose** Least P-norm optimal IIR filter

**Syntax**

```
[num,den] = iirlpnorm(n,d,f,edges,a)
[num,den] = iirlpnorm(n,d,f,edges,a,w)
[num,den] = iirlpnorm(n,d,f,edges,a,w,p)
[num,den] = iirlpnorm(n,d,f,edges,a,w,p,dens)
[num,den] = iirlpnorm(n,d,f,edges,a,w,p,dens,initnum,initden)
```

**Description** `[num,den] = iirlpnorm(n,d,f,edges,a)` returns a filter having a numerator order `n` and denominator order `d` which is the best approximation to the desired frequency response described by `f` and `a` in the least-`p`th sense. The vector `edges` specifies the band-edge frequencies for multi-band designs. An unconstrained quasi-Newton algorithm is employed and any poles or zeros that lie outside of the unit circle are reflected back inside. `n` and `d` should be chosen so that the zeros and poles are used effectively. See the “Hints” on page 7-917 section. Always use `freqz` to check the resulting filter.

`[num,den] = iirlpnorm(n,d,f,edges,a,w)` uses the weights in `w` to weight the error. `w` has one entry per frequency point (the same length as `f` and `a`) which tells `iirlpnorm` how much emphasis to put on minimizing the error in the vicinity of each frequency point relative to the other points. `f` and `a` must have the same number of elements, which may exceed the number of elements in `edges`. This allows for the specification of filters having any gain contour within each band. The frequencies specified in `edges` must also appear in the vector `f`. For example,

```
[num,den] = iirlpnorm(5,12,[0 .15 .4 .5 1],[0 .4 .5 1],...
[1 1.6 1 0 0],[1 1 1 10 10])
```

is a lowpass filter with a peak of 1.6 within the passband.

`[num,den] = iirlpnorm(n,d,f,edges,a,w,p)` where `p` is a two-element vector `[pmin pmax]` allows for the specification of the minimum and maximum values of `p` used in the least-`p`th algorithm. Default is `[2 128]` which essentially yields the L-infinity, or Chebyshev, norm. `pmin` and `pmax` should be even. If `p` is the string `'inspect'`, no

optimization will occur. This can be used to inspect the initial pole/zero placement.

`[num,den] = iirlpnorm(n,d,f,edges,a,w,p,dens)` specifies the grid density `dens` used in the optimization. The number of grid points is  $(dens*(n+d+1))$ . The default is 20. `dens` can be specified as a single-element cell array. The grid is not equally spaced.

`[num,den] = iirlpnorm(n,d,f,edges,a,w,p,dens,initnum,initden)` allows for the specification of the initial estimate of the filter numerator and denominator coefficients in vectors `initnum` and `initden`. This may be useful for difficult optimization problems. The pole-zero editor in Signal Processing Toolbox software can be used for generating `initnum` and `initden`.

## Hints

- This is a weighted least-pth optimization.
- Check the radii and locations of the poles and zeros for your filter. If the zeros are on the unit circle and the poles are well inside the unit circle, try increasing the order of the numerator or reducing the error weighting in the stopband.
- Similarly, if several poles have a large radii and the zeros are well inside of the unit circle, try increasing the order of the denominator or reducing the error weighting in the passband.

## References

Antoniou, A., *Digital Filters: Analysis, Design, and Applications*, Second Edition, McGraw-Hill, Inc. 1993.

## See Also

`iirlpnormc` | `filter` | `freqz` | `iingrpdelay` | `zplane`

**Purpose** Constrained least Pth-norm optimal IIR filter

**Syntax**

```
[num,den] = iirlpnormc(n,d,f,edges,a)
[num,den] = iirlpnormc(n,d,f,edges,a,w)
[num,den] = iirlpnormc(n,d,f,edges,a,w,radius)
[num,den] = iirlpnormc(n,d,f,edges,a,w,radius,p)
[num,den] = iirlpnormc(n,d,f,edges,a,w,radius,p,dens)
[num,den] = iirlpnormc(n,d,f,edges,a,w,radius,p,dens,...
initnum,initden)
[num,den,err] = iirlpnormc(...)
[num,den,err,sos,g] = iirlpnormc(...)
```

**Description** `[num,den] = iirlpnormc(n,d,f,edges,a)` returns a filter having numerator order `n` and denominator order `d` which is the best approximation to the desired frequency response described by `f` and `a` in the least-pth sense. The vector `edges` specifies the band-edge frequencies for multi-band designs. A constrained Newton-type algorithm is employed. `n` and `d` should be chosen so that the zeros and poles are used effectively. See the Hints section. Always check the resulting filter using `fvtool`.

`[num,den] = iirlpnormc(n,d,f,edges,a,w)` uses the weights in `w` to weight the error. `w` has one entry per frequency point (the same length as `f` and `a`) which tells `iirlpnormc` how much emphasis to put on minimizing the error in the vicinity of each frequency point relative to the other points. `f` and `a` must have the same number of elements, which can exceed the number of elements in `edges`. This allows for the specification of filters having any gain contour within each band. The frequencies specified in `edges` must also appear in the vector `f`. For example,

```
[num,den] = iirlpnormc(5,5,[0 .15 .4 .5 1],[0 .4 .5 1],...
[1 1.6 1 0 0],[1 1 1 10 10])
```

designs a lowpass filter with a peak of 1.6 within the passband.

`[num,den] = iirlpnormc(n,d,f,edges,a,w,radius)` returns a filter having a maximum pole radius of `radius` where  $0 < \text{radius} < 1$ . `radius`

defaults to 0.999999. Filters that have a reduced pole radius may retain better transfer function accuracy after you quantize them.

`[num,den] = iirlpnormc(n,d,f,edges,a,w,radius,p)` where `p` is a two-element vector `[pmin pmax]` allows for the specification of the minimum and maximum values of `p` used in the least-pth algorithm. Default is `[2 128]` which essentially yields the L-infinity, or Chebyshev, norm. `pmin` and `pmax` should be even. If `p` is the string 'inspect', no optimization will occur. This can be used to inspect the initial pole/zero placement.

`[num,den] = iirlpnormc(n,d,f,edges,a,w,radius,p,dens)` specifies the grid density `dens` used in the optimization. The number of grid points is `(dens*(n+d+1))`. The default is 20. `dens` can be specified as a single-element cell array. The grid is not equally spaced.

`[num,den] = iirlpnormc(n,d,f,edges,a,w,radius,p,dens,...,initnum,initden)` allows for the specification of the initial estimate of the filter numerator and denominator coefficients in vectors `initnum` and `initden`. This may be useful for difficult optimization problems. The pole-zero editor in Signal Processing Toolbox software can be used for generating `initnum` and `initden`.

`[num,den,err] = iirlpnormc(...)` returns the least-Pth approximation error `err`.

`[num,den,err,sos,g] = iirlpnormc(...)` returns the second-order section representation in the matrix `SOS` and gain `G`. For numerical reasons you may find `SOS` and `G` beneficial in some cases.

## Hints

- This is a weighted least-pth optimization.
- Check the radii and location of the resulting poles and zeros.
- If the zeros are all on the unit circle and the poles are well inside of the unit circle, try increasing the order of the numerator or reducing the error weighting in the stopband.

- Similarly, if several poles have a large radius and the zeros are well inside of the unit circle, try increasing the order of the denominator or reducing the error weight in the passband.
- If you reduce the pole radius, you might need to increase the order of the denominator.

The message

```
Poorly conditioned matrix. See the "help" file.
```

indicates that `iirlpnormc` cannot accurately compute the optimization because either:



- 1 The approximation error is extremely small (try reducing the number of poles or zeros — refer to the hints above).
- 2 The filter specifications have huge variation, such as `a=[1 1e9 0 0]`.

## Examples

This example returns a lowpass filter whose pole radius is constrained to 0.8

```
[b,a,err,s,g] = iirlpnormc(6,6,[0 .4 .5 1],[0 .4 .5 1],...  
[1 1 0 0],[1 1 1 1],.8);  
hd = dfilt.df1sos(s,g); % Construct second-order sections filter.  
fvtool(hd); % View filter's magnitude response
```

From the magnitude response shown here you see the lowpass nature of the filter. The pole/zero plot following shows that the poles are constrained to 0.8 as specified in the command.



# iirlpnormc

---

## References

Antoniou, A., *Digital Filters: Analysis, Design, and Applications*, Second Edition, McGraw-Hill, Inc. 1993.

## See Also

`freqz` | `filter` | `iirgrpdelay` | `iirlpnorm` | `zplane`

---

<b>Purpose</b>	RLS IIR filter from specification object
<b>Syntax</b>	<pre>hd = design(d,'iirls') hd = design(d,'iirls',designoption,value,designoption,value, ...)</pre>
<b>Description</b>	<code>hd = design(d,'iirls')</code> designs a least-squares filter specified by the filter specification object <code>d</code> .

---

**Note** The `iirls` algorithm might not be well behaved in all cases. Experience is your best guide to determining if the resulting filter meets your needs. When you use `iirls` to design a filter, review the filter carefully to ensure that it is appropriate for your use.

---

`hd = design(d,'iirls',designoption,value,designoption,value,...)` returns a least-squares IIR filter where you specify design options as input arguments.

To determine the available design options, use `designopts` with the specification object and the design method as input arguments as shown.

```
designopts(d,'method')
```

For complete help about using `iirls`, refer to the command line help system. For example, to get specific information about using `iirls` with `d`, the specification object, enter the following at the MATLAB prompt.

```
help(d,'iirls')
```


## Examples

Starting from an arbitrary magnitude and phase design object `d`, generate a complex bandpass filter of order = 5. To make the example a little easier to do, use the default values for `F`, and `H`, the frequency vector and the complex desired frequency response.

```
d = fdesign.arbmagnphase('N,F,H',5);  
d =  
  
    Response: 'Arbitrary Magnitude and Phase'  
    Specification: 'N,F,H'  
    Description: {'Filter Order';'Frequency Vector';'  
                Complex Desired Frequency Response'  
    NormalizedFrequency: true  
    FilterOrder: 5  
    Frequencies: [1x655 double]  
    FreqResponse: [1x655 double]
```

```
design(d,'iirls'); % Opens FVTool to show the filter.
```

Displaying both the phase and magnitude response in FVTool shows you the filter.



**See Also**

fdesign.arbmag | fdesign.arbmagnphase | fir1s

# iirnotch

---

**Purpose** Second-order IIR notch filter

**Syntax**  
`[num,den] = iirnotch(w0,bw)`  
`[num,den] = iirnotch(w0,bw,ab)`

**Description** `[num,den] = iirnotch(w0,bw)` turns a digital notching filter with the notch located at  $w_0$ , and with the bandwidth at the -3 dB point set to `bw`. To design the filter,  $w_0$  must meet the condition  $0.0 < w_0 < 1.0$ , where 1.0 corresponds to  $\pi$  radians per sample in the frequency range.


The quality factor (Q factor)  $q$  for the filter is related to the filter bandwidth by  $q = w_0/bw$  where  $\omega_0$  is  $w_0$ , the frequency to remove from the signal.

`[num,den] = iirnotch(w0,bw,ab)` returns a digital notching filter whose bandwidth, `bw`, is specified at a level of `-ab` decibels. Including the optional input argument `ab` lets you specify the magnitude response bandwidth at a level that is not the default -3 dB point, such as -6 dB or 0 dB.

**Examples** Design and plot an IIR notch filter that removes a 60 Hz tone ( $f_0$ ) from a signal at 300 Hz ( $f_s$ ). For this example, set the Q factor for the filter to 35 and use it to specify the filter bandwidth:

```
wo = 60/(300/2);  bw = wo/35;  
[b,a] = iirnotch(wo,bw);  
fvtool(b,a);
```

Shown in the next plot, the notch filter has the desired bandwidth with the notch located at 60 Hz, or  $0.4\pi$  radians per sample. Compare this plot to the comb filter plot shown on the reference page for `iircomb`.



**See Also** [firgr](#) | [iircomb](#) | [iirpeak](#)

# iirpeak

---

**Purpose** Second-order IIR peak or resonator filter

**Syntax** `[num,den] = iirpeak(w0,bw)`  
`[num,den] = iirpeak(w0,bw,ab)`

**Description** `[num,den] = iirpeak(w0,bw)` turns a second-order digital peaking filter with the peak located at  $w_0$ , and with the bandwidth at the +3 dB point set to  $bw$ . To design the filter,  $w_0$  must meet the condition  $0.0 < w_0 < 1.0$ , where 1.0 corresponds to  $\pi$  radians per sample in the frequency range.


The quality factor (Q factor)  $q$  for the filter is related to the filter bandwidth by  $q = w_0/bw$  where  $\omega_0$  is  $w_0$  the signal frequency to boost.

`[num,den] = iirpeak(w0,bw,ab)` returns a digital peaking filter whose bandwidth,  $bw$ , is specified at a level of  $+ab$  decibels. Including the optional input argument  $ab$  lets you specify the magnitude response bandwidth at a level that is not the default +3 dB point, such as +6 dB or 0 dB.

**Examples** Design and plot an IIR peaking filter that boosts the frequency at 1.75 Khz in a signal and has bandwidth of 500 Hz at the -3 dB point:

```
fs = 10000; wo = 1750/(fs/2); bw = 500/(fs/2);  
[b,a] = iirpeak(wo,bw);  
fvtool(b,a);
```

Shown in the next plot, the peak filter has the desired gain and bandwidth at 1.75 KHz.



**See Also** [firgr](#) | [iircomb](#) | [iirnotch](#)

# iirpowcomp

---

**Purpose** Power complementary IIR filter

**Syntax**  
`[bp,ap] = iirpowcomp(b,a)`  
`[bp,ap,c] = iirpowcomp(b,a)`

**Description** `[bp,ap] = iirpowcomp(b,a)` returns the coefficients of the power complementary IIR filter  $g(z) = bp(z)/ap(z)$  in vectors `bp` and `ap`, given the coefficients of the IIR filter  $h(z) = b(z)/a(z)$  in vectors `b` and `a`. `b` must be symmetric (Hermitian) or antisymmetric (antihermitian) and of the same length as `a`. The two power complementary filters satisfy the relation

$$|H(w)|^2 + |G(w)|^2 = 1.$$

`[bp,ap,c] = iirpowcomp(b,a)` where `c` is a complex scalar of magnitude = 1, forces `bp` to satisfy the generalized hermitian property `conj(bp(end:-1:1)) = c*bp`.

When `c` is omitted, it is chosen as follows:


- When `b` is real, chooses `C` as 1 or -1, whichever yields `bp` real
- When `b` is complex, `C` defaults to 1

`ap` is always equal to `a`.

## Examples

```
[b,a]=cheby1(10,.5,.4);  
[bp,ap]=iirpowcomp(b,a);  
Hd1 = dfilt.df2(b,a);  
Hd2 = dfilt.df2(bp,ap);  
hfvf = fvtool([Hd1,Hd2], 'MagnitudeDisplay', 'Magnitude');  
legend(hfvf, 'Original Filter', 'Power Complementary Version');
```

The next figure presents the results of applying `iirpowcomp` to the Chebyshev filter — the power complementary version of the original filter.



**See Also**

[tf2ca](#) | [tf2c1](#) | [ca2tf](#) | [c12tf](#)

# iirrateup

---

**Purpose** Upsample IIR filter by integer factor

**Syntax** `[Num,Den,AllpassNum,AllpassDen] = iirrateup(B,A,N)`

**Description** `[Num,Den,AllpassNum,AllpassDen] = iirrateup(B,A,N)` returns the numerator and denominator vectors, Num and Den respectively, of the target filter being transformed from any prototype by applying an Nth-order rateup frequency transformation, where N is the upsample ratio. Transformation creates N equal replicas of the prototype filter frequency response.

It also returns the numerator, AllpassNum, and the denominator, AllpassDen, of the allpass mapping filter. The prototype lowpass filter is given with a numerator specified by B and a denominator specified by A.

The relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter,  $F_1$  and  $F_2$ , with  $F_1$  preceding  $F_2$ . Feature  $F_1$  will still precede  $F_2$  after the transformation. However, the distance between  $F_1$  and  $F_2$  will not be the same before and after the transformation.


**Examples** Design a prototype real IIR halfband filter using a standard elliptic approach:

```
[b, a] = ellip(3, 0.1, 30, 0.409);  
[num, den] = iirrateup(b, a, 4);
```

Verify the result by comparing the prototype filter with the target filter:

```
fvtool(b, a, num, den);
```

As shown in the figure produced by FVTool, the transformed filter appears as expected.



## Arguments

Variable	Description
<i>B</i>	Numerator of the prototype lowpass filter
<i>A</i>	Denominator of the prototype lowpass filter
<i>N</i>	Frequency multiplication ratio
<i>Num</i>	Numerator of the target filter
<i>Den</i>	Denominator of the target filter
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

# iirateup

---

## **See Also**

iirftransf | allpassrateup | zpkrateup

**Purpose**

Shift frequency response of IIR filter

**Syntax**

```
[Num,Den,AllpassNum,AllpassDen] = iirshift(B,A,Wo,Wt)
```

**Description**

`[Num,Den,AllpassNum,AllpassDen] = iirshift(B,A,Wo,Wt)` returns the numerator and denominator vectors, `Num` and `Den` respectively, of the target filter transformed from the real lowpass prototype by applying a second-order real shift frequency mapping.

It also returns the numerator, `AllpassNum`, and the denominator of the allpass mapping filter, `AllpassDen`. The prototype lowpass filter is given with the numerator specified by `B` and the denominator specified by `A`.

This transformation places one selected feature of an original filter located at frequency  $W_o$  to the required target frequency location,  $W_t$ . This transformation implements the "DC Mobility," which means that the Nyquist feature stays at Nyquist, but the DC feature moves to a location dependent on the selection of  $W_o$  and  $W_t$ .

Relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter,  $F_1$  and  $F_2$ , with  $F_1$  preceding  $F_2$ . Feature  $F_1$  will still precede  $F_2$  after the transformation. However, the distance between  $F_1$  and  $F_2$  will not be the same before and after the transformation.

Choice of the feature subject to the real shift transformation is not restricted to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones.

This transformation can also be used for transforming other types of filters; e.g., notch filters or resonators can change their position in a simple way without designing them from the beginning.

**Examples**

Design a prototype real IIR halfband filter using a standard elliptic approach:

```
[b, a] = ellip(3, 0.1, 30, 0.409);
```


Perform the real frequency shift by defining where the selected feature of the prototype filter, originally at  $W_0=0.5$ , should be placed in the target filter,  $W_t=0.75$ :

```
Wo = 0.5; Wt = 0.75;  
[num, den] = iirshift(b, a, Wo, Wt);
```

Verify the result by comparing the prototype filter with the target filter:

```
fvtool(b, a, num, den);
```

Shifting the specified feature from the prototype to the target generates the response shown in the figure.



**Arguments**

<b>Variable</b>	<b>Description</b>
<i>B</i>	Numerator of the prototype lowpass filter
<i>A</i>	Denominator of the prototype lowpass filter
<i>Wo</i>	Frequency value to be transformed from the prototype filter
<i>Wt</i>	Desired frequency location in the transformed target filter
<i>Num</i>	Numerator of the target filter
<i>Den</i>	Denominator of the target filter
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

Frequencies must be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.

**See Also**

`iirftansf` | `allpassshift` | `zpkshift`

# iirshiftc

---

**Purpose** Shift frequency response of IIR complex filter

**Syntax**

```
[Num,Den,AllpassNum,AllpassDen] = iirshiftc(B,A,Wo,Wc)
[Num,Den,AllpassNum,AllpassDen] = iirshiftc(B,A,0,0.5)
[Num,Den,AllpassNum,AllpassDen] = iirshiftc(B,A,0,-0.5)
```

**Description** [Num,Den,AllpassNum,AllpassDen] = iirshiftc(B,A,Wo,Wc) returns the numerator and denominator vectors, Num and Den respectively, of the target filter transformed from the real lowpass prototype by applying a first-order complex frequency shift transformation. This transformation rotates all the features of an original filter by the same amount specified by the location of the selected feature of the prototype filter, originally at  $W_o$ , placed at  $W_t$  in the target filter.

It also returns the numerator, AllpassNum, and the denominator, AllpassDen, of the allpass mapping filter. The prototype lowpass filter is given with the numerator specified by B and the denominator specified by A.

[Num,Den,AllpassNum,AllpassDen] = iirshiftc(B,A,0,0.5) calculates the allpass filter for doing the Hilbert transformation, i.e. a 90 degree counterclockwise rotation of an original filter in the frequency domain.

[Num,Den,AllpassNum,AllpassDen] = iirshiftc(B,A,0,-0.5) calculates the allpass filter for doing an inverse Hilbert transformation, i.e. a 90 degree clockwise rotation of an original filter in the frequency domain.

**Examples** Design a prototype real IIR halfband filter using a standard elliptic approach:

```
[b, a] = ellip(3, 0.1, 30, 0.409);
```


Rotate all features of the prototype filter in the frequency domain by the same amount by specifying where the selected feature of an original filter,  $W_o = 0.5$ , should appear in the target filter,  $W_t = 0.25$ :

```
[num, den] = iirshiftc(b, a, 0.5, 0.25);
```

Verify the result by comparing the prototype filter with the target filter:

```
fvtool(b, a, num, den);
```

After applying the shift, the selected feature from the original filter is just where it should be, at  $W_t = 0.25$ .



## Arguments

Variable	Description
$B$	Numerator of the prototype lowpass filter
$A$	Denominator of the prototype lowpass filter

Variable	Description
<i>Wo</i>	Frequency value to be transformed from the prototype filter
<i>Wt</i>	Desired frequency location in the transformed target filter
<i>Num</i>	Numerator of the target filter
<i>Den</i>	Denominator of the target filter
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

Frequencies must be normalized to be between -1 and 1, with 1 corresponding to half the sample rate.

## References

Oppenheim, A.V., R.W. Schafer and J.R. Buck, *Discrete-Time Signal Processing*, Prentice-Hall International Inc., 1989.

Dutta-Roy, S.C. and B. Kumar, "On digital differentiators, Hilbert transformers, and half-band low-pass filters," *IEEE Transactions on Education*, vol. 32, pp. 314-318, August 1989.

## See Also

`iirftransf` | `allpassshiftc` | `zpkshiftc`

**Purpose**

Filter impulse response

**Syntax**

```
[h,t] = impz(hfilt)
[h,t] = impz(hfilt,n)
[h,t] = impz(hfilt,n,fs)
[h,t] = impz(hfilt,[],fs)
impz(hfilt)
[h,t] = impz(hs)
[h,t] = impz(hs,Name,Value)
impz(hs)
```

**Description**

`impz` returns the impulse response based on the current filter coefficients. This section describes common `impz` operation with adaptive filters, discrete-time filters, multirate filters, and filter System objects. For more input options, refer to `impz` in Signal Processing Toolbox documentation.

`[h,t] = impz(hfilt)` returns the impulse response `h` and the corresponding time points `w` at which the impulse response of `hfilt` is computed. The impulse response is evaluated at 10 1-second intervals—`(0:9)'`.

`[h,t] = impz(hfilt,n)` returns the impulse response evaluated at `floor(n)` 1-second intervals—`(0:floor(n)-1)'`.

`[h,t] = impz(hfilt,n,fs)` returns the impulse response evaluated at `floor(n) 1/fs`-second intervals—`(0:floor(n)-1)'/fs`.

`[h,t] = impz(hfilt,[],fs)` returns the impulse response evaluated at 10 `1/fs`-second intervals—`(0:9)'/fs`.

`impz(hfilt)` uses `FVTool` to plot the impulse response of the filter. You can also provide the optional input arguments `n` and `fs` with this syntax.

`[h,t] = impz(hs)` returns the impulse response for the filter System object `hs`. The impulse response is evaluated at 10 1-second intervals—`(0:9)'`. You can also provide the optional input arguments `n` and `fs` with this syntax.

`[h,t] = impz(hs,Name,Value)` returns an impulse response with additional options specified by one or more `Name,Value` pair arguments.

`impz(hs)` uses FVTool to plot the impulse response of the filter System object `hs`.

---

**Note** You can use `impz` for both real and complex filters. When you omit the output arguments, `impz` plots only the real part of the impulse response.

---

## Input Arguments

### `hfiltr`

`hfiltr` is either:

- An adaptive `adaptfilt`, discrete-time `dfilt`, or multirate `mfilt` filter object
- A vector of adaptive, discrete-time, or multirate filter objects

The multirate filter impulse response is computed relative to the rate at which the filter is running. When you specify `fs` (the sampling rate) as an input argument, `impz` assumes the filter is running at that rate.

For multistage cascades, `impz` forms a single-stage multirate filter that is equivalent to the cascade. It then computes the response relative to the rate at which the equivalent filter is running. `impz` does not support all multistage cascades. The function analyzes only those cascades for which there exists an equivalent single-stage filter.

As an example, consider a 2-stage interpolator where the first stage has an interpolation factor of 2 and the second stage has an interpolation factor of 4. In this case, an equivalent single-stage filter exists with an overall interpolation factor of 8. `impz` uses this equivalent filter for the analysis. If a sampling frequency `fs` is specified as an input argument to `impz`, the function interprets `fs` as the rate at which the equivalent filter is running.

**hs**

Filter System object. The function supports the following filter structures.

- `dsp.FIRFilter`
- `dsp.BiquadFilter`
- `dsp.FIRInterpolator`
- `dsp.CICInterpolator`
- `dsp.FIRDecimator`
- `dsp.CICDecimator`
- `dsp.FIRRateConverter`

**n**

Number of samples.

**Default:** 10

**fs**

Sampling frequency.

**Default:** 1

**Name-Value Pair Arguments**

Specify optional comma-separated pairs of `Name, Value` arguments, where `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes ( ' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

**Arithmetic**

`'double' | 'single' | 'fixed'`

For filter System object inputs only, specify the arithmetic used during analysis. When you specify 'double' or 'single', the function performs double- or single-precision analysis. When you specify 'fixed', the arithmetic changes depending on the setting of the CoefficientDataType property and whether the System object is locked or unlocked.

**Details for Fixed-Point Arithmetic**

<b>System Object State</b>	<b>Coefficient Data Type</b>	<b>Rule</b>
Unlocked	'Same as input'	The function assumes that the coefficient data type is signed, 16 bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Unlocked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.

System Object State	Coefficient Data Type	Rule
Locked	'Same as input'	When the input data type is 'double' or 'fixed', the function assumes that the coefficient data type is signed, 16-bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Locked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.

When you do not specify the arithmetic for non-CIC structures, the function uses double-precision arithmetic if the filter System object is in an unlocked state. If the System object is locked, the function performs analysis based on the locked input data type. CIC structures only support fixed-point arithmetic.

**Output Arguments**

**h**

Complex, n-element impulse response vector. If `hfilt` is a vector of filters, `h` is a complex, `length(hfilt)`-by-`n` matrix of impulse response vectors corresponding to each filter in `hfilt`. If `n` is not specified, the function uses a default value of 8192.

For adaptive filters, `h` is the instantaneous impulse response.

**t**

Time vector of length  $n$ , in seconds.  $t$  consists of  $n$  points equally spaced from 0 to  $\text{floor}(n)/fs$ . If  $n$  is not specified, the function uses a default value of 10. If  $fs$  is not specified, the function uses a default value of 1.

## Examples

Create a discrete-time filter for a fourth-order, lowpass elliptic filter with a cutoff frequency of 0.4 times the Nyquist frequency. Use a second-order sections structure to resist quantization errors. Plot the first 50 samples of the impulse response, along with the reference impulse response.


```
d = fdesign.lowpass(.4,.5,1,80);  
% Create a design object for the prototype filter.
```

Use `ellip` to design a minimum order discrete-time filter in second-order section form.

```
hd=design(d,'ellip');
```

Convert `hd` to fixed-point, and plot the impulse response:

```
impz(hd);  
axis([1 75 -0.2 0.35])
```



**See Also** `filter` | `stepz`

**Purpose** Information about filter

**Syntax**

```
info(h)
info(h, 'short')
info(h, 'long')
s = info(h)
```

**Description** `info(h)` returns very basic information about the filter. The particulars depend on the filter type and structure.

`info(h, 'short')` returns the same information as `info(h)`.

`info(h, 'long')` returns the following information about the filter:

- Specifications such as the filter structure and filter order
- Information about the design method and options
- Performance measurements for the filter response, such as the passband cutoff or stopband attenuation, included in the `measure` method
- Cost of implementing the filter in terms of operations required to apply the filter to data, included in the `cost` method

When the filter uses fixed-point arithmetic, the function returns additional information about the filter, including the arithmetic setting and details about the filter internals.

`s = info(h)` returns filter information in the variable `s`. You can also provide the optional arguments `'short'` and `'long'` with this syntax.

**Input Arguments**

**h**

One of the following types of filter object or filter System object:

- Discrete-time filter (`dfilt`) object
- Multirate filter (`mfilt`) object
- Adaptive filter (`adaptfilt`) object
- Filter System object. The function supports the following structures:

- dsp.FIRFilter
- dsp.BiquadFilter
- dsp.FIRInterpolator
- dsp.CICInterpolator
- dsp.FIRDecimator
- dsp.CICDecimator
- dsp.FIRRateConverter

**'short'**

Input string that instructs the function to return basic information about the filter.

**'long'**

Input string that instructs the function to return in-depth information about the filter.

**Output Arguments****s**

Variable for storing filter information.

**Examples**

Obtain short-format and long-format information about a filter.

```
>> d = fdesign.lowpass;
>> f = design(d);
>> info(f)
Discrete-Time FIR Filter (real)
-----
Filter Structure : Direct-Form FIR
Filter Length   : 43
Stable          : Yes
Linear Phase    : Yes (Type 1)

>> info (f)
```

```
Discrete-Time FIR Filter (real)
-----
Filter Structure : Direct-Form FIR
Filter Length   : 43
Stable          : Yes
Linear Phase    : Yes (Type 1)

>> info(f,'long')
Discrete-Time FIR Filter (real)
-----
Filter Structure : Direct-Form FIR
Filter Length   : 43
Stable          : Yes
Linear Phase    : Yes (Type 1)

Design Method Information
Design Algorithm : equiripple

Design Options
DensityFactor : 16
MinOrder      : any
MinPhase      : false
StopbandDecay : 0
StopbandShape : flat

Design Specifications
Sampling Frequency : N/A (normalized frequency)
Response           : Lowpass
Specification      : Fp,Fst,Ap,Ast
Passband Edge     : 0.45
Stopband Edge     : 0.55
Passband Ripple   : 1 dB
Stopband Atten.   : 60 dB

Measurements
Sampling Frequency : N/A (normalized frequency)
Passband Edge     : 0.45
```

---

3-dB Point	: 0.46956
6-dB Point	: 0.48313
Stopband Edge	: 0.55
Passband Ripple	: 0.8919 dB
Stopband Atten.	: 60.9681 dB
Transition Width	: 0.1

Implementation Cost	
Number of Multipliers	: 43
Number of Adders	: 42
Number of States	: 42
MultPerInputSample	: 43
AddPerInputSample	: 42

**See Also**

`coeffs` | `isfir` | `isstable` | `islinphase` | `dfilt`

# int

---

**Purpose** States from CIC filter

**Syntax** `integerstates = int(hm.states)`

**Description** `integerstates = int(hm.states)` returns the states of a CIC filter in matrix form, rather than as the native `filtstates` object. An important point about `int` is that it quantizes the state values to the smallest number of bits possible while maintaining the values accurately.

**Examples** For many users, the states of multirate filters are most useful as a matrix, but the CIC filters store the states as objects. Here is how you get the states from you CIC filter as a matrix.

```
hm = mfilt.cicdecim;
hs = hm.states; % Returns a FILTSTATES.CIC object hs.
states = int(hs); % Convert object hs to a signed integer matrix.
```

After using `int` to convert the states object to a matrix, here is what you get.

Before converting:

```
hm.states

ans =

    Integrator: [2x1 States]
      Comb: [2x1 States]
```

After the conversion and assigning the states to `states`:

```
states

states =

     0     0
     0     0
```

**See Also**`filtstates.cic | mfilt.cicdecim | mfilt.cicinterp`

**Purpose** Determine whether filter is allpass

**Syntax**

```
isallpass(hd)
isallpass(hd,tolerance)
isallpass(hs,...)
isallpass(hs,'Arithmetic',arithtype)
```

**Description** `isallpass(hd)` determines whether the filter object `hd` is an allpass filter, returning 1 if true and 0 if false.

`isallpass(hd,tolerance)` uses input argument `tolerance` to determine whether the numerator and denominator transfer functions for the filter are close enough in value to be considered equal, and thus allpass. The function returns 1 if true (the difference between the numbers is less than `tolerance`) and 0 if not.

Given an allpass filter with this transfer function

$$H(z) = \frac{\alpha_n + \dots + \alpha_1 z^{-(n-1)} + z^{-n}}{1 + \alpha_1 z^{-1} + \dots + \alpha_n z^{-n}}$$

if the numerator and denominator transfer functions are equal, the filter is allpass. The `tolerance` input argument lets you determine how closely the transfer functions have to match to be considered equal. This approach may be most helpful in fixed-point allpass filters.

Lattice coupled allpass filters always have allpass sections, this function always returns 1 for filters whose structure is `latticeca`.

`isallpass(hs,...)` determines whether the filter System object `hs` is an allpass filter, returning 1 if true and 0 if false.

`isallpass(hs,'Arithmetic',arithtype)` analyzes the filter System object `hs` based on the specified `arithtype`. `arithtype` can be 'double', 'single', or 'fixed'. When you specify 'double' or 'single', the function performs double- or single-precision analysis. When you specify 'fixed', the arithmetic changes depending on the setting of

the `CoefficientDataType` property and whether the System object is locked or unlocked.

### Details for Fixed-Point Arithmetic

System Object State	Coefficient Data Type	Rule
Unlocked	'Same as input'	The function assumes that the coefficient data type is signed, 16 bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Unlocked	'Custom'	The function performs fixed-point analysis based on the setting of the <code>CustomCoefficientsDataType</code> property.
Locked	'Same as input'	When the input data type is 'double' or 'fixed', the function assumes that the coefficient data type is signed, 16-bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Locked	'Custom'	The function performs fixed-point analysis based on

# isallpass

---

System Object State	Coefficient Data Type	Rule
		the setting of the CustomCoefficientsDataType property.

When you do not specify the arithmetic for non-CIC structures, the function uses double-precision arithmetic if the filter System object is in an unlocked state. If the System object is locked, the function performs analysis based on the locked input data type. CIC structures only support fixed-point arithmetic.

## Examples

Use `dfilt.allpass` to construct an allpass filter. Then, use `isallpass` to test whether the filter is allpass.

```
c=[.8,1.5,0.4, 0.7]; % Allpass coefficients.  
hd=dfilt.allpass(c);  
AllPass = isallpass(hd);  
% Returns a 1 indicated hd is all pass.
```

## See Also

`isfir` | `islinphase` | `ismaxphase` | `isminphase` | `isreal` | `issos`  
| `isstable`

**Purpose**

Determine whether filter is FIR

**Syntax**

```
isfir(h)
isfir(hs)
```

**Description**

`isfir(h)` determines whether filter `h` is an FIR filter, returning 1 when the filter is an FIR filter, and 0 when it is IIR. `isfir` applies to `dfilt`, `mfilt`, and `adaptfilt` objects.

To determine whether `h` is an FIR filter, `isfir(h)` inspects filter `h` and determines whether the filter, in transfer function form, has a scalar denominator. If it does, it is an FIR filter.

`isfir(hs)` determines whether the filter System object `hs` is an FIR filter, returning 1 if true and 0 if false.

**Examples**

```
d = fdesign.lowpass;
h = design(d);
isfir(h)
ans =
```

```
1
```

returns 1 for the status of filter `h`. The filter is an FIR structure with denominator reference coefficient equal to 1.

For multirate filters, `isfir` works the same way.

```
d = fdesign.interpolator(5); % Interpolate by 5.
h = design(d); % Use the default design method.
isfir(h)
```

```
ans =
```

```
1
```

Use `isfir` with adaptive filters as well.

# isfir

---

## **See Also**

isallpass | islinphase | ismaxphase | isminphase | isreal |  
issos | isstable

**Purpose** Determine whether filter is linear phase

**Syntax**

```
islinphase(h)  
islinphase(h,tolerance)  
islinphase(hs,...)  
islinphase(hs,'Arithmetic',arithtype)
```

**Description** `islinphase(h)` determines if the filter object `h` is linear phase, and returns 1 if true and 0 if false. `adapfilt`, `dfilt`, and `mfilt` objects work with `islinphase`.

`islinphase(h,tolerance)` uses input argument `tolerance` to determine whether the filter coefficients are close enough in value to be considered symmetric or antisymmetric, returning 1 if true (the difference between the values is less than `tolerance`) and 0 if not.

The phase determination is based on the reference coefficients. A filter has linear phase if it is FIR and its transfer function coefficients are symmetric or antisymmetric. If it is IIR, has poles on or outside the unit circle, and both numerator and denominator are symmetric or antisymmetric, it is linear phase also.

`islinphase(hs,...)` determines whether the filter System object `hs` is linear phase, returning 1 if true and 0 if false.

`islinphase(hs,'Arithmetic',arithtype)` analyzes the filter System object `hs` based on the specified *arithtype*. *arithtype* can be 'double', 'single', or 'fixed'. When you specify 'double' or 'single', the function performs double- or single-precision analysis. When you specify 'fixed', the arithmetic changes depending on the setting of the `CoefficientDataType` property and whether the System object is locked or unlocked.

## Details for Fixed-Point Arithmetic

System Object State	Coefficient Data Type	Rule
Unlocked	'Same as input'	The function assumes that the coefficient data type is signed, 16 bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Unlocked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.
Locked	'Same as input'	When the input data type is 'double' or 'fixed', the function assumes that the coefficient data type is signed, 16-bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Locked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.

When you do not specify the arithmetic for non-CIC structures, the function uses double-precision arithmetic if the filter System object is in an unlocked state. If the System object is locked, the function performs analysis based on the locked input data type. CIC structures only support fixed-point arithmetic.

## Examples

This IIR filter has linear phase.

```
d = fdesign.lowpass('n,fc',10,0.55);  
h = design(d,'window');  
islinphase(h)
```

Using the specification `nb,na,fp,fst` results in an IIR filter that is not linear phase in this design.

```
nb=15  
na=10  
d=fdesign.lowpass('nb,na,fp,fst',nb,na,0.45,0.55)  
h=design(d) % Use the default design method iirlpnorm.  
islinphase(h)
```

## See Also

[isallpass](#) | [isfir](#) | [ismaxphase](#) | [isminphase](#) | [isreal](#) | [issos](#) | [isstable](#)

# ismaxphase

---

**Purpose** Determine whether filter is maximum phase

**Syntax**

```
ismaxphase(h)  
ismaxphase(h,tolerance)  
ismaxphase(hs,...)  
ismaxphase(hs,'Arithmetic',arithtype)
```

**Description** `ismaxphase(h)` determines if the filter object `h` is maximum phase, and returns 1 if true and 0 if false. `adapfilt`, `dfilt`, and `mfilt` objects work with `ismaxphase`.

`ismaxphase(h,tolerance)` uses input argument `tolerance` to determine whether the zeros of the filter transfer function have values that are close enough to 1 to be considered 1 or greater. Such values are on or outside the unit circle. The function returns 1 if true (the difference between the coefficient value and 1 is less than `tolerance`) and 0 if not.

The phase determination is based on the reference coefficients. A filter is maximum phase when the zeros of its transfer function are on or outside the unit circle, or when the numerator is a scalar.

`ismaxphase(hs,...)` determines whether the filter System object `hs` is maximum phase, returning 1 if true and 0 if false.

`ismaxphase(hs,'Arithmetic',arithtype)` analyzes the filter System object `hs` based on the specified `arithtype`. `arithtype` can be 'double', 'single', or 'fixed'. When you specify 'double' or 'single', the function performs double- or single-precision analysis. When you specify 'fixed', the arithmetic changes depending on the setting of the `CoefficientDataType` property and whether the System object is locked or unlocked.

**Details for Fixed-Point Arithmetic**

<b>System Object State</b>	<b>Coefficient Data Type</b>	<b>Rule</b>
Unlocked	'Same as input'	The function assumes that the coefficient data type is signed, 16 bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Unlocked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.
Locked	'Same as input'	When the input data type is 'double' or 'fixed', the function assumes that the coefficient data type is signed, 16-bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Locked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.

When you do not specify the arithmetic for non-CIC structures, the function uses double-precision arithmetic if the filter System object is in an unlocked state. If the System object is locked, the function performs analysis based on the locked input data type. CIC structures only support fixed-point arithmetic.

## Examples

Use `ismaxphase` to determine whether the following filters are maximum phase. The first is a discrete-time `dfilt` object and the second an adaptive filter.

```
fp = 100;
fst= 120;
fs = 800;
ap = 1;
ast= 60;
d = fdesign.lowpass('fp,fst,ap,ast',fp,fst,ap,ast,fs);
h = design(d,'equiripple','maxphase',true);
ismaxphase(h)
```

To make this a minimum phase filter, use `fliplr` to change the coefficient order. Reordering the coefficients this way changes the phase from maximum to minimum.

```
h.numerator=fliplr(h.numerator);
isminphase(h)
```

returns 1, so this filter is minimum phase.

For the adaptive filter example, try the following code:

```
x = randn(1,500);    % Input to the filter
b = fir1(31,0.5);    % FIR system to be identified
n = 0.1*randn(1,500); % Observation noise signal
d = filter(b,1,x)+n; % Desired signal
mu = 1;              % NLMS step size
offset = 50;         % NLMS offset
ha = adaptfilt.nlms(32,mu,1,offset);
[y,e] = filter(ha,x,d);
```

After adapting, `ha` is an FIR filter that does not exhibit maximum phase.

```
ismaxphase(ha)
```

## See Also

```
isallpass | isfir | islinphase | isminphase | isreal | issos |  
isstable
```

# isminphase

---

**Purpose** Determine whether filter is minimum phase

**Syntax**

```
isminphase(h)
isminphase(h,tolerance)
isminphase(hs,...)
isminphase(hs,'Arithmetic',arithtype)
```

**Description**

`isminphase(h)` determines if the filter object `h` is minimum phase, and returns 1 if true and 0 if false. `isminphase` works with `adapfilt`, `dfilt`, and `mfilt` objects.

`isminphase(h,tolerance)` uses the input argument `tolerance` to determine whether the filter transfer function zeros are outside the unit circle by more than `tolerance`. If the zeros do not lie outside the unit circle by more than `tolerance`, `isminphase` returns a 1. If any zeros are more than `tolerance` outside the unit circle, `isminphase` returns a 0.

A filter is *minimum phase* when all the zeros of its transfer function are on or inside the unit circle, or the numerator is a scalar. An equivalent definition for a minimum phase filter is a causal and stable system with a causal and stable inverse.

`isminphase(hs,...)` determines whether the filter System object `hs` is minimum phase, returning 1 if true and 0 if false.

`isminphase(hs,'Arithmetic',arithtype)` analyzes the filter System object `hs` based on the specified *arithtype*. *arithtype* can be 'double', 'single', or 'fixed'. When you specify 'double' or 'single', the function performs double- or single-precision analysis. When you specify 'fixed', the arithmetic changes depending on the setting of the `CoefficientDataType` property and whether the System object is locked or unlocked.

## Details for Fixed-Point Arithmetic

System Object State	Coefficient Data Type	Rule
Unlocked	'Same as input'	The function assumes that the coefficient data type is signed, 16 bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Unlocked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.
Locked	'Same as input'	When the input data type is 'double' or 'fixed', the function assumes that the coefficient data type is signed, 16-bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Locked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.

# isminphase


---

When you do not specify the arithmetic for non-CIC structures, the function uses double-precision arithmetic if the filter System object is in an unlocked state. If the System object is locked, the function performs analysis based on the locked input data type. CIC structures only support fixed-point arithmetic.

## Examples

Create a minimum-phase filter.

```
fp = 200;  
fst= 230;  
fs = 900;  
ap = 1;  
ast= 60;  
d = fdesign.lowpass('fp,fst,ap,ast',fp,fst,ap,ast,fs);  
h = design(d,'equiripple','minphase',true);  
isminphase(h)  
% Returns a 1  
fvtool(h,'analysis','polezero')
```




The zeros of the FIR filter are all on or inside the unit circle.

To illustrate the effect of coefficient quantization, make  $h$  a fixed-point filter. The quantization process results in the filter no longer being minimum phase. However, if the tolerance is increased to 0.01, the quantized design satisfies the definition of a minimum phase filter.

```
h.arithmetic='fixed';
isminphase(h)
% Returns a 0
fvtool(h,'analysis','polezero');
isminphase(h,0.01)
% Returns a 1
```

# ismminphase



## See Also

`isallpass` | `isfir` | `islinphase` | `ismaxphase` | `isreal` | `issos` | `isstable`

---

<b>Purpose</b>	Determine whether filter uses real coefficients
<b>Syntax</b>	<code>isreal(hd)</code> <code>isreal(hs)</code>
<b>Description</b>	<p><code>isreal(hd)</code> returns 1 (or true) if all filter coefficients for the filter <code>hd</code> are real, and returns 0 (or false) otherwise. Complex filters have one or more coefficients with nonzero imaginary parts.</p> <p><code>isreal(hs)</code> determines whether the filter coefficients of the filter System object <code>hs</code> are real, returning 1 if true and 0 if false.</p>

---

**Note** Quantizing a filter cannot make a real filter into a complex filter.

---

**Examples** Create a double-precision filter and a fixed-point filter. Then, test the coefficients of the fixed-point filter to see if they are strictly real.

```
d=fdesign.lowpass('n,fp,ap,ast',5,0.4,0.5,20);
hd=design(d,'ellip');
hd.arithmetic='fixed';
IsReal =isreal(hd);
% Returns a 1
```

**See Also** `isfir` | `islinphase` | `ismaxphase` | `isminphase` | `issos` | `isstable` | `isallpass`

**Purpose** Determine whether filter is SOS form

**Syntax** `issos(hd)`  
`issoss(hs)`

**Description** `issos(hd)` determines whether quantized filter `hq` consists of second-order sections. Returns 1 if all sections of quantized filter `hq` have order less than or equal to two, and 0 otherwise.

`issoss(hs)` determines whether the filter System object `hs` consists of second-order sections, returning 1 if true and 0 if false.

**Examples** By default, `fdesign` and `design` return SOS filters when possible. This example designs a lowpass SOS filter that uses fixed-point arithmetic.

```
d=fdesign.lowpass('n,fp,ap,ast',40,0.55,0.1,60);  
hd=design(d,'ellip');  
hd.arithmetic='fixed';  
IsSOS=issos(hd);
```

The fixed-point filter `hd` is in second-order section form, as is the double-precision version.

**See Also** `isallpass` | `isfir` | `islinphase` | `ismaxphase` | `isminphase` | `isreal` | `isstable`

**Purpose** Determine whether filter is stable

**Syntax**

```
isstable(hq)
isstable(hs)
isstable(hs, 'Arithmetic', arithtype)
```

**Description** `isstable(hq)` tests quantized filter `hq` to determine whether its poles are inside the unit circle. If the poles lie on or outside the circle, `isstable` returns 0. If the poles are inside the circle, `isstable` returns 1.

To determine the filter stability, `isstable` checks the filter coefficients. When the poles lie on or inside the unit circle, the filter is stable. FIR filters are stable by design because the defining transfer functions do not have denominator polynomials, thus no feedback to cause instability.

`isstable(hs)` determines whether the filter System object `hs` is stable, returning 1 if true and 0 if false.

`isstable(hs, 'Arithmetic', arithtype)` analyzes the filter System object `hs` based on the specified *arithtype*. *arithtype* can be 'double', 'single', or 'fixed'. When you specify 'double' or 'single', the function performs double- or single-precision analysis. When you specify 'fixed', the arithmetic changes depending on the setting of the `CoefficientDataType` property and whether the System object is locked or unlocked.

#### Details for Fixed-Point Arithmetic

System Object State	Coefficient Data Type	Rule
Unlocked	'Same as input'	The function assumes that the coefficient data type is signed, 16 bit, and autoscaled. The function performs fixed-point

# isstable

System Object State	Coefficient Data Type	Rule
		analysis based on this assumption.
Unlocked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.
Locked	'Same as input'	When the input data type is 'double' or 'fixed', the function assumes that the coefficient data type is signed, 16-bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Locked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.

When you do not specify the arithmetic for non-CIC structures, the function uses double-precision arithmetic if the filter System object is in an unlocked state. If the System object is locked, the function performs analysis based on the locked input data type. CIC structures only support fixed-point arithmetic.

**Examples**

Because filter stability is very important in your design process, use `isstable` to determine whether your double-precision or fixed-point IIR filter is stable.

```
d=fdesign.nyquist(2,'n,tw',24,0.1);  
hd=design(d,'iirlinphase')  
isstable(hd)  
hd2=design(d,'equiripple');  
isstable(hd2)
```

**See Also**

`isallpass` | `isfir` | `islinphase` | `ismaxphase` | `isminphase` |  
`isreal` | `issos` | `zplane`

# kaiserwin

---

## Purpose

Kaiser window filter from specification object

## Syntax

```
h = design(d, 'kaiserwin')  
h = design(d, 'kaiserwin', designoption, value, designoption, ...  
value, ...)
```

## Description

`h = design(d, 'kaiserwin')` designs a digital filter `hd`, or a multirate filter `hm` that uses a Kaiser window. For `kaiserwin` to work properly, the filter order in the specifications object must be even. In addition, higher order filters (filter order greater than 120) tend to be more accurate for smaller transition widths. `kaiserwin` returns a warning when your filter order may be too low to design your filter accurately.

```
h =  
design(d, 'kaiserwin', designoption, value, designoption, ...  
value, ...) returns a filter where you specify design options as input  
arguments and the design process uses the Kaiser window technique.
```

To determine the available design options, use `designopts` with the specification object and the design method as input arguments as shown.

```
designopts(d, 'method')
```

For complete help about using `kaiserwin`, refer to the command line help system. For example, to get specific information about using `kaiserwin` with `d`, the specification object, enter the following at the MATLAB prompt.

```
help(d, 'kaiserwin')
```

## Examples

This example designs a direct form FIR filter from a halfband filter specification object.

```
d=fdesign.halfband('n,tw',200,0.01)  
hd= design(d,'kaiserwin','filterstructure','dffir')
```

In this example, `kaiserwin` uses an interpolating filter specification object:

```
d=fdesign.interpolator(4,'lowpass');  
h = design(d,'kaiserwin');
```

## See Also

[equiripple](#) | [firls](#)

# lagrange

---

**Purpose** Fractional delay filter from `fdesign.fracdelay` specification object

**Syntax**  
`Hd = design(d, 'lagrange')`  
`hd = design(d, 'lagrange', FilterStructure, structure)`

**Description**  
`Hd = design(d, 'lagrange')` designs a fractional delay filter using the Lagrange method based on the specifications in `d`.  
`hd = design(d, 'lagrange', FilterStructure, structure)` specifies the Lagrange design method and the *structure* filter structure for `hd`. The sole valid filter structure string for `structure` is `fd`, describing the fractional delay structure.

**Examples**  
This example uses a fractional delay of 0.30 samples. The `help` and `designopts` commands provide the details about designing fractional delay filters.

```
d=fdesign.fracdelay(.30)

d =

    Response: 'Fractional Delay'
  Specification: 'N'
  Description: {'Filter Order'}
    FracDelay: 0.3
  NormalizedFrequency: true
    FilterOrder: 3

designmethods(d)

Design Methods for class fdesign.fracdelay (N):

lagrange

help(d, 'lagrange')
```

DESIGN Design a Lagrange fractional delay filter.  
HD = DESIGN(D, 'lagrange') designs a Lagrange filter specified by the FDESIGN object D.

HD = DESIGN(..., 'FilterStructure', STRUCTURE) returns a filter with the structure STRUCTURE. STRUCTURE is 'fd' by default and can be any of the following:

'fd'

```
% Example #1 - Design a linear Lagrange fractional
% delay filter of 0.2 samples.
h = fdesign.fracdelay(0.2,'N',2);
Hd = design(h, 'lagrange', 'FilterStructure', 'fd')
```

```
% Example #2 - Design a cubic Lagrange fractional
% delay filter.
Fs = 8000;          % Sampling frequency of 8kHz
fdelay = 50e-6;    % Fractional delay of 50 microseconds.
h = fdesign.fracdelay(fdelay,'N',3,Fs);
Hd = design(h, 'lagrange', 'FilterStructure', 'fd');
```

This example designs a linear Lagrange fractional delay filter where you set the delay to 0.2 seconds and the filter order N to 2.

```
h = fdesign.fracdelay(0.2,'N',2);
hd = design(h,'lagrange','FilterStructure','fd')
```

Design a cubic Lagrange fractional delay filter with filter order equal to 3..

```
Fs = 8000;          % Sampling frequency of 8 kHz.
fdelay = 50e-6;    % Fractional delay of 50 microseconds.
h = fdesign.fracdelay(fdelay,'N',3,Fs);
hd = design(h,'lagrange','FilterStructure','fd');
```

## References

Laakso, T. I., V. Välimäki, M. Karjalainen, and Unto K. Laine, "Splitting the Unit Delay - Tools for Fractional Delay Filter Design," *IEEE Signal Processing Magazine*, Vol. 13, No. 1, pp. 30-60, January 1996.

## See Also

`design` | `designmethods` | `designopts` | `fdesign` |  
`fdesign.fracdelay`

**Purpose** Check model for blocks from specific DSP System Toolbox libraries

**Syntax**

```
liblinks(lib)
liblinks(lib,sys)
liblinks(lib,sys,c)
```

**Description** `liblinks(lib)` returns a cell array of strings that lists the blocks in the current model that are linked to the specified libraries. The input `lib` provides a cell array of strings with the library names. Use the library name visible in the title bar when you open a library model.

`liblinks(lib,sys)` acts on the named model `sys`.

`liblinks(lib,sys,c)` changes the foreground color of the returned blocks to the color `c`. Possible values of `c` are 'blue', 'green', 'red', 'cyan', 'magenta', 'yellow', or 'black'.

**Examples** Check for blocks from the Sources library in the specified model:

```
rlsdemo
liblinks('dspsrcs4',gcs)
```

**See Also** `dsp_links`

# limitcycle

---

**Purpose** Response of single-rate, fixed-point IIR filter

**Syntax**  
`report = limitcycle(hd)`  
`report = limitcycle(hd,ntrials,inputlengthfactor,stopcriterion)`

**Description** `report = limitcycle(hd)` returns the structure `report` that contains information about how filter `hd` responds to a zero-valued input vector. By default, the input vector has length equal to twice the impulse response length of the filter.

`limitcycle` returns a structure whose elements contain the details about the limit cycle testing. As shown in this table, the `report` includes the following details.

Output Object Property	Description
LimitCycleType	Contains one of the following results: <ul style="list-style-type: none"><li>• <b>Granular</b> — indicates that a granular overflow occurred.</li><li>• <b>Overflow</b> — indicates that an overflow limit cycle occurred.</li><li>• <b>None</b> — indicates that the test did not find any limit cycles.</li></ul>
Zi	Contains the initial condition value(s) that caused the detected limit cycle to occur.
Output	Contains the output of the filter in the steady state.
Trial	Returns the number of the Monte Carlo trial on which the limit cycle testing stopped. For example, <code>Trial = 10</code> indicates that testing stopped on the tenth Monte Carlo trial.

Using an input vector longer than the filter impulse response ensures that the filter is in steady-state operation during the limit cycle testing. `limitcycle` ignores output that occurs before the filter reaches the steady state. For example, if the filter impulse length is 500 samples, `limitcycle` ignores the filter output from the first 500 input samples.

To perform limit cycle testing on your IIR filter, you must set the filter Arithmetic property to `fixed` and `hd` must be a fixed-point IIR filter of one of the following forms:

- `df1` — direct-form I
- `df1t` — direct-form I transposed
- `df1sos` — direct-form I with second-order sections
- `df1tsos` — direct-form I transposed with second-order sections
- `df2` — direct-form II
- `df2t` — direct-form II transposed
- `df2sos` — direct-form II with second-order sections
- `df2tsos` — direct-form II transposed with second-order sections

When you use `limitcycle` without optional input arguments, the default settings are

- Run 20 Monte Carlo trials
- Use an input vector twice the length of the filter impulse response
- Stop testing if the simulation process encounters either a granular or overflow limit cycle

To determine the length of the filter impulse response, use `impzlength`:

```
impzlength(hd)
```

During limit cycle testing, if the simulation runs reveal both overflow and granular limit cycles, the overflow limit cycle takes precedence and is the limit cycle that appears in the report.

# limitcycle

---

Each time you run `limitcycle`, it uses a different sequence of random initial conditions, so the results can differ from run to run.

Each Monte Carlo trial uses a new set of randomly determined initial states for the filter. Test processing stops when `limitcycle` detects a zero-input limit cycle in filter `hd`. `report = limitcycle(hd, ntrials, inputlengthfactor, stopcriterion)` lets you set the following optional input arguments:

- `ntrials` — Number of Monte Carlo trials (default is 20).
- `inputlengthfactor` — integer factor used to calculate the length of the input vector. The length of the input vector comes from  $(\text{impzlength}(\text{hd}) * \text{inputlengthfactor})$ , where `inputlengthfactor = 2` is the default value.
- `stopcriterion` — the criterion for stopping the Monte Carlo trial processing. `stopcriterion` can be set to **either** (the default), **granular**, **overflow**. This table describes the results of each stop criterion.

<b>stopcriterion Setting</b>	<b>Description</b>
<b>either</b>	Stop the Monte Carlo trials when <code>limitcycle</code> detects either a granular or overflow limit cycle.
<b>granular</b>	Stop the Monte Carlo trials when <code>limitcycle</code> detects a granular limit cycle.
<b>overflow</b>	Stop the Monte Carlo trials when <code>limitcycle</code> detects an overflow limit cycle.

---

**Note** An important feature is that if you specify a specific limit cycle stop criterion, such as `overflow`, the Monte Carlo trials do not stop when testing encounters a granular limit cycle. You receive a warning that no `overflow` limit cycle occurred, but consider that a granular limit cycle might have occurred.

---

## Examples

In this example, there is a region of initial conditions in which no limit cycles occur and a region where they do. If no limit cycles are detected before the Monte Carlo trials are over, the state sequence converges to zero. When a limit cycle is found, the states do not end at zero. Each time you run this example, it uses a different sequence of random initial conditions, so the plot you get can differ from the one displayed in the following figure.

```
s = [1 0 0 1 0.9606 0.9849];
hd = dfilt.df2sos(s);
hd.arithmetic = 'fixed';
greport = limitcycle(hd,20,2,'granular')
oreport = limitcycle(hd,20,2,'overflow')
figure,
subplot(211),plot(greport.Output(1:20)), title('Granular Limit Cycle');
subplot(212),plot(oreport.Output(1:20)), title('Overflow Limit Cycle');

greport =

    LimitCycle: 'granular'
             Zi: [2x1 double]
             Output: [1303x1 embedded.fi]
             Trial: 1


oreport =

    LimitCycle: 'overflow'
             Zi: [2x1 double]
             Output: [1303x1 embedded.fi]
```

# limitcycle

Trial: 2

The plots shown in this figure present both limit cycle types — the first displays the small amplitude granular limit cycle, the second the larger amplitude overflow limit cycle.



As you see from the plots, and as is generally true, overflow limit cycles are much greater magnitude than granular limit cycles. This is why `limitcycle` favors overflow limit cycle detection and reporting.

## See Also

`freqz` | `noisepsd`

<b>Purpose</b>	Maxflat FIR filter
<b>Syntax</b>	<pre>hd = design(d,'maxflat') hd = design(d,'maxflat','FilterStructure',structure)</pre>
<b>Description</b>	<p><code>hd = design(d,'maxflat')</code> designs a maximally flat filter, <code>hd</code>, from a filter specification object, <code>d</code>.</p> <p><code>hd = design(d,'maxflat','FilterStructure',structure)</code> designs a maximally flat filter where <code>structure</code> is one of the following:</p> <ul style="list-style-type: none"><li>• <code>'dffir'</code>, a discrete-time, direct-form FIR filter (the default value)</li><li>• <code>'dffirt'</code>, a discrete-time, direct-form FIR transposed filter</li><li>• <code>'dfsymfir'</code>, a discrete-time, direct-form symmetric FIR filter</li><li>• <code>'fftfir'</code>, a discrete-time, overlap-add, FIR filter</li></ul>
<b>Examples</b>	<p>Example 1: Design a lowpass filter with a maximally flat FIR structure.</p> <pre>d = fdesign.lowpass('N,F3dB', 50, 0.3); Hd = design(d, 'maxflat');</pre> <p>Example 2: Design a highpass filter with a maximally flat overlap-add FIR structure.</p> <pre>d = fdesign.highpass('N,F3dB', 50, 0.7); Hd=design(d,'maxflat','FilterStructure','fftfir');</pre>

# maximizestopband

---

**Purpose** Maximize stopband attenuation of fixed-point filter

**Syntax** `Hq = maximizestopband(Hd,Wordlength)`  
`Hq = maximizestopband(Hd,Wordlength,'Ntrials',N)`


**Description** `Hq = maximizestopband(Hd,Wordlength)` quantizes the single-stage or multistage FIR filter `Hd` and returns the fixed-point filter `Hq` with wordlength `wordlength` that maximizes the stopband attenuation. `Hd` must be generated using `fdesign` and `design`. For multistage filters, `wordlength` can either be a scalar or vector. If `wordlength` is a scalar, the same wordlength is used for all stages. If `wordlength` is a vector, each stage uses the corresponding element in the vector. The vector length must equal the number of stages. `maximizestopband` uses a stochastic noise-shaping procedure by default to minimize the wordlength. To obtain repeatable results on successive function calls, initialize the uniform random number generator `rand`

`Hq = maximizestopband(Hd,Wordlength,'Ntrials',N)` specifies the number of Monte Carlo trials to use in the maximization. `Hq` is the fixed-point filter with the largest stopband attenuation among the trials. The number of Monte Carlo trials `N` defaults to 1.

You must have the Fixed-Point Toolbox software installed to use this function.

**Examples** Maximize stopband attenuation for 16-bit fixed-point filter.

```
Hf = fdesign.lowpass('Fp,Fst,Ap,Ast',0.4,0.45,0.5,60);
Hd = design(Hf,'equiripple');
WL = 16; % use 16 bits to represent coefficients
Hq = maximizestopband(Hd,WL);
% Compare stopband attenuation
md = measure(Hd);
mq = measure(Hq);
hfvtool(Hd,Hq,'showreference','off');
legend(hfvtool,'Floating-point Filter','Fixed-point Filter');
```



## See Also

`constraincoeffwl` | `design` | `fdesign` | `minimizecoeffwl` | `measure` | `rand`

## Tutorials

- “Fixed-Point Data Types”

# maxstep

---

**Purpose** Maximum step size for adaptive filter convergence

**Syntax**  
`mumax = maxstep(ha,x)`  
`[mumax,mumaxmse] = maxstep(ha,x)`

**Description** `mumax = maxstep(ha,x)` predicts a bound on the step size to provide convergence of the mean values of the adaptive filter coefficients. The columns of the matrix `x` contain individual input signal sequences. The signal set is assumed to have zero mean or nearly so.

`[mumax,mumaxmse] = maxstep(ha,x)` predicts a bound on the adaptive filter step size to provide convergence of the LMS adaptive filter coefficients in the mean-square sense. `maxstep` issues a warning when `ha.stepsize` is outside of the range  $0 < \text{ha.stepsize} < \text{mumaxmse}/2$ .

`maxstep` is available for the following adaptive filter objects:

- `adaptfilt.blms`
- `adaptfilt.blmsfft`
- `adaptfilt.lms`
- `adaptfilt.nlms` (uses a different syntax. Refer to the text below.)
- `adaptfilt.se`

---

**Note** With `adaptfilt.nlms` filter objects, `maxstep` uses the following slightly different syntax:

`mumax = maxstep(ha)`  
`[mumax,mumaxmse] = maxstep(ha)`

The maximum step size for convergence is fully defined by the filter object `ha`. Matrix `x` is not necessary. If you include an `x` input matrix, MATLAB returns an error.

---

**Examples**

Analyze and simulate a 32-coefficient (31st-order) LMS adaptive filter object. To demonstrate the adaptation process, run 2000 iterations and 50 trials.

```
% Specify [numiterations,numexamples] = size(x);
x = zeros(2000,50);
d = x;
obj = fdesign.lowpass('n,fc',31,0.5);
hd = design(obj,'window'); % FIR filter to identified.
coef = cell2mat(hd.coefficients); % Convert cell array to matrix.

for k=1:size(x,2); % Create input and desired response signal
    % matrices.
% Set the (k)th input to the filter.
    x(:,k) = filter(sqrt(0.75),[1 -0.5],sign(randn(size(x,1),1)));
    n = 0.1*randn(size(x,1),1); % (k)th observation noise signal.
    d(:,k) = filter(coef,1,x(:,k))+n; % (k)th desired signal end.
end
mu = 0.1; % LMS step size.
ha = adaptfilt.lms(32,mu);
[mumax,mumaxmse] = maxstep(ha,x);
```

Warning: Step size is not in the range  $0 < \mu < \text{mumaxmse}/2$ :  
Erratic behavior might result.

mumax

mumax =

0.0623

mumaxmse

mumaxmse =

0.0530

# maxstep

---

## See Also

`msepred` | `msexim` | `filter`

**Purpose** Measure filter magnitude response

**Syntax**

```
measure(hd)
measure(hm)
measure(hs)
measure(hs)
```

**Description** `measure(hd)` returns measured values for specific points in the magnitude response curve for filter object `hd`. When you use a design object `d` to create a filter (by using `fdesign.type` to create `d`), you specify one or more values that define your desired filter response. `measure(hd)` tests the filter to determine the actual values in the magnitude response of the filter, such as the stopband attenuation or the passband ripple. Comparing the results returned by `measure` to the specifications you provided in the design object helps you assess whether the filter meets your design criteria.

---

**Note** To use `measure`, `hd`, `hm`, or `hs` must result from using a filter design method with a filter specifications object. `measure` works with multirate filters and discrete-time filters. The function does not support adaptive filters because you cannot use `fdesign.type` to construct adaptive filter specifications objects.

---

`measure(hd)` returns measurements for the discrete-time filter `hd`. The function determines the relevant specifications based on the response type of the design object you use to create the filter. For example, for single-rate lowpass filters made from design objects, `measure(hd)` returns the following filter specifications.

Lowpass Filter Specification	Description
Sampling Frequency	Filter sampling frequency.
Passband Edge	Location of the edge of the passband as it enters transition.

## measure

---

<b>Lowpass Filter Specification</b>	<b>Description</b>
3-dB Point	Location of the $-3$ dB point on the response curve.
6-dB Point	Location of the $-6$ dB point on the response curve.
Stopband Edge	Location of the edge of the transition band as it enters the stopband.
Passband Ripple	Ripple in the passband.
Stopband Atten.	Attenuation in the stopband.
Transition Width	Width of the transition between the passband and stopband, in normalized frequency or absolute frequency. Measured between $F_{\text{pass}}$ and $F_{\text{stop}}$ .

In contrast, when you use a bandstop design object, `measure(hd)` returns these specifications for the resulting bandstop filter.

<b>Bandstop Filter Specification</b>	<b>Description</b>
Sampling Frequency	Filter sampling frequency.
First Passband Edge	Location of the edge of the first passband.
First 3-dB Point	Location of the edge of the $-3$ dB point in the first transition band.
First 6-dB Point	Location of the edge of the $-6$ dB point in the first transition band.
First Stopband Edge	Location of the start of the stopband.
Second Stopband Edge	Location of the end of the stopband.

<b>Bandstop Filter Specification</b>	<b>Description</b>
Second 6-dB Point	Location of the edge of the $-6$ dB point in the second transition band.
Second 3-dB Point	Location of the edge of the $-3$ dB point in the second transition band.
Second Passband Edge	Location of the start of the second passband.
First Passband Ripple	Ripple in the first passband.
Stopband Atten.	Attenuation in the stopband.
Second Passband Edge	Ripple in the second passband.
First Transition Width	Width of the first transition region. Measured between the $-3$ and $-6$ dB points.
Second Transition Width	Width of the second transition region. Measured between the $-6$ and $-3$ dB points.

`measure(hm)` returns measurements for the multirate filter `hm`. The set of filter specifications that `measure` returns for multirate filters might be different from those for discrete-time filters.

The set of response measurements that `measure` returns depends on the response you use to design the filter. For example, when `hm` is an FIR lowpass interpolator (whose response is lowpass), `measure(hm)` returns the following set of measurements.

<b>Interpolator Filter Specification</b>	<b>Description</b>
First Passband Edge	Location of the edge of the passband as it enters transition.
3-dB Point	Location of the $-3$ dB point on the response curve.

Interpolator Filter Specification	Description
6-dB Point	Location of the $-6$ dB point on the response curve.
Stopband Edge	Location of the edge of the transition band as it enters the stopband.
Passband Ripple	Ripple in the passband.
Stopband Atten.	Attenuation in the stopband.
Transition Width	Width of the transition between the passband and stopband, in normalized frequency or absolute frequency. Measured between $F_{\text{pass}}$ and $F_{\text{stop}}$ .

For reference, the specification object `d` created the interpolator specifications shown in the preceding table:

```
d=fdesign.interpolator(6, 'lowpass')
```

```
d =
```

```
    MultirateType: 'Interpolator'  
InterpolationFactor: 6  
    Response: 'Lowpass'  
    Specification: 'Fp,Fst,Ap,Ast'  
    Description: {4x1 cell}  
NormalizedFrequency: true  
    Fpass: 0.1333333333333333  
    Fstop: 0.1666666666666667  
    Apass: 1  
    Astop: 60
```

`measure(hs)` returns measurements for the filter System object `hs`. You must construct `hs` using `design` with the optional name-value pair argument `'SystemObject',true`.

`measure(hs)` returns measurements for the filter System object `hs` with additional options specified by one or more **Name, Value** pair arguments.

## Tips

For designs that do not specify some of the frequency constraints, the function may not be able to determine corresponding magnitude measurements. In these cases, a constraint can be passed in to `measure` to determine such measurements. For example:

```
f = fdesign.lowpass('N,F3dB,Ast',8,0.5,80);
H = design(f,'cheby2','SystemObject',true);
measure(H)
```

returns values of `Unknown` for the passband edge, passband ripple, and transition width measurements, but

```
f = fdesign.lowpass('N,F3dB,Ast',8,0.5,80);
H = design(f,'cheby2','SystemObject',true);
measure(H,'Fpass',0.4)
```

provides measurements for all returned values.

## Input Arguments

### **hd**

Discrete-time `dfilt` filter object.

### **hm**

Multirate `mfilt` filter object.

### **hs**

Filter System object. The function supports the following filter structures.

- `dsp.FIRFilter`
- `dsp.BiquadFilter`
- `dsp.FIRInterpolator`

- dsp.CICInterpolator
- dsp.FIRDecimator
- dsp.CICDecimator
- dsp.FIRRateConverter

## Name-Value Pair Arguments

Specify optional comma-separated pairs of **Name**, **Value** arguments, where **Name** is the argument name and **Value** is the corresponding value. **Name** must appear inside single quotes ( ' '). You can specify several name and value pair arguments in any order as **Name1**, **Value1**, ..., **NameN**, **ValueN**.

## Arithmetic

`'double' | 'single' | 'fixed'`

For filter System object inputs only, specify the arithmetic used during analysis. When you specify 'double' or 'single', the function performs double- or single-precision analysis. When you specify 'fixed', the arithmetic changes depending on the setting of the **CoefficientDataType** property and whether the System object is locked or unlocked.

## Details for Fixed-Point Arithmetic

System Object State	Coefficient Data Type	Rule
Unlocked	'Same as input'	The function assumes that the coefficient data type is signed, 16 bit, and autoscaled. The function performs fixed-point

System Object State	Coefficient Data Type	Rule
		analysis based on this assumption.
Unlocked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.
Locked	'Same as input'	When the input data type is 'double' or 'fixed', the function assumes that the coefficient data type is signed, 16-bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Locked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.

When you do not specify the arithmetic for non-CIC structures, the function uses double-precision arithmetic if the filter System object is in an unlocked state. If the System object is locked, the function performs analysis based on the locked input data type. CIC structures only support fixed-point arithmetic.

## Examples

For the first example, create a lowpass filter and check whether the actual filter meets the specifications. For this case, use normalized frequency for  $F_s$ , the default setting.

```
d2=fdesign.lowpass('Fp,Fst,Ap,Ast',0.45,0.55,0.1,80)
```

```
d2 =
```

```
        Response: 'Lowpass'  
    Specification: 'Fp,Fst,Ap,Ast'  
    Description: {4x1 cell}  
NormalizedFrequency: true  
          Fpass: 0.45  
          Fstop: 0.55  
          Apass: 0.1  
          Astop: 80
```

```
designmethods(d2)
```

```
Design Methods for class fdesign.lowpass (Fp,Fst,Ap,Ast):
```

```
butter  
cheby1  
cheby2  
ellip  
equiripple  
ifir  
kaiserwin  
multistage
```

```
hd2=design(d2) % Use the default equiripple design method.
```

```
hd2 =
```

```
    FilterStructure: 'Direct-Form FIR'
```

```
Arithmetic: 'double'  
Numerator: [1x68 double]  
PersistentMemory: false
```

```
measure(hd2)
```

```
ans =
```

```
Sampling Frequency : N/A (normalized frequency)  
Passband Edge      : 0.45  
3-dB Point         : 0.47794  
6-dB Point         : 0.48909  
Stopband Edge      : 0.55  
Passband Ripple    : 0.09615 dB  
Stopband Atten.    : 80.2907 dB  
Transition Width   : 0.1
```

Stopband Edge, Passband Edge, Passband Ripple, and Stopband Atten. all meet the specifications.

Now, using  $F_s$  in linear frequency, create a bandpass filter, and measure the magnitude response characteristics.

```
d=fdesign.bandpass
```

```
d =
```

```
Response: 'Bandpass'  
Specification: 'Fst1,Fp1,Fp2,Fst2,Ast1,Ap,Ast2'  
Description: {7x1 cell}  
NormalizedFrequency: true  
Fstop1: 0.35  
Fpass1: 0.45  
Fpass2: 0.55  
Fstop2: 0.65  
Astop1: 60  
Apass: 1  
Astop2: 60
```

## measure

---

```
normalizefreq(d,false,1.5e3) % Convert to linear freq.
```

```
hd=design(d,'cheby2');
```

```
measure(hd)
```

```
ans =
```

```
Sampling Frequency      : 1.5 kHz  
First Stopband Edge    : 0.2625 kHz  
First 6-dB Point       : 0.31996 kHz  
First 3-dB Point       : 0.32497 kHz  
First Passband Edge    : 0.3375 kHz  
Second Passband Edge   : 0.4125 kHz  
Second 3-dB Point      : 0.42503 kHz  
Second 6-dB Point      : 0.43004 kHz  
Second Stopband Edge   : 0.4875 kHz  
First Stopband Atten.  : 60 dB  
Passband Ripple        : 0.17985 dB  
Second Stopband Atten. : 60 dB  
First Transition Width  : 0.075 kHz  
Second Transition Width : 0.075 kHz
```

`measure(hd)` returns the actual response values, in the units you chose. In this example, all frequencies appear in kilohertz because the sampling frequency is in kilohertz.

### See Also

`design` | `fdesign` | `normalizefreq`

**Purpose** Multirate filter

**Syntax** `hm = mfilt.structure(input1,input2,...)`

**Description** `hm = mfilt.structure(input1,input2,...)` returns the object `hm` of type *structure*. As with `dfilt` and `adaptfilt` objects, you must include the *structure* string to construct a multirate filter object. You can, however, construct a default multirate filter object of a given structure by not including input arguments in your calling syntax.

Multirate filters include decimators and interpolators, and fractional decimators and fractional interpolators where the resulting interpolation or decimation factor is not an integer.

### Structures

Each of the following multirate filter structures has a reference page of its own.

Filter Structure String	Description of Resulting Multirate Filter	Coefficient Mapping Support in <code>realizemdl</code> and <code>block</code>
<code>mfilt.cascade</code>	Cascade multirate filters to form another filter	Supported
<code>mfilt.cicdecim</code>	Cascaded integrator-comb decimator	Not supported
<code>mfilt.cicinterp</code>	Cascaded integrator-comb interpolator	Not supported
<code>mfilt.farrowsrc</code>	Multirate Farrow filter	Supported.

<b>Filter Structure String</b>	<b>Description of Resulting Multirate Filter</b>	<b>Coefficient Mapping Support in <code>realizemd1</code> and <code>block</code></b>
<code>mfilt.fftfirinterp</code>	Overlap-add FIR polyphase interpolator	Not supported
<code>mfilt.firdecim</code>	Direct-form FIR polyphase decimator	Supported
<code>mfilt.firinterp</code>	Direct-form FIR polyphase interpolator	Supported
<code>mfilt.firsrc</code>	Direct-form FIR polyphase sample rate converter	Supported
<code>mfilt.firtdecim</code>	Direct-form transposed FIR polyphase decimator	Supported
<code>mfilt.holdinterp</code>	FIR hold interpolator	Not supported
<code>mfilt.iirdecim</code>	IIR decimator	Supported
<code>mfilt.iirinterp</code>	IIR interpolator	Supported
<code>mfilt.linearinterp</code>	FIR Linear interpolator	Supported
<code>mfilt.iirwdfdecim</code>	IIR wave digital filter decimator	Supported
<code>mfilt.iirwdfinterp</code>	IIR wave digital filter interpolator	Supported

## Copying `mfilt` Objects

To create a copy of an `mfilt` object, use the `copy` method.

```
h2 = copy(hd)
```

---

**Note** The syntax `hd2 = hd` copies only the object handle. It does not create a new object. `hd2` and `hd` are not independent. If you change the property value for one of the two, such as `hd2`, you are changing the property for both.

---

## Examples

Decimation by a factor of two. Convert input sampled at 48 kHz to 24 kHz:

```

Fs = 4.8e4;
t =0:1/Fs:1-(1/Fs);
x = cos(2*pi*4000*t);
Hm=mfilt.firdecim(2);
% Note cutoff frequency of 1/2 normalized frequency
fvtool(Hm);
% Note the group delay of 34 samples
fvtool(Hm,'analysis','grpdelay');
y = filter(Hm,x);
% Note delay in output is consistent with 36/2
stem(y(1:48),'markerfacecolor',[0 0 1]);

```

Using existing coefficients to decimate a signal by a factor of two:

```

M = 2; % Decimation factor
b = firhalfband('minorder',.45,0.0001);
Hm = mfilt.firdecim(M,b);
% Decimate a signal which consists of the sum of 2 sinusoids.
N = 160;
x = sin(2*pi*.05*[0:N-1]+pi/3)+cos(2*pi*.03*[0:N-1]+pi/3);
y = filter(Hm,x);

```

---

**Note** Multirate filters can also have complex coefficients. For example, you can specify complex coefficients in the argument `num` passed to the filter structure. This works for all multirate filter structures.

```
m = 2;
num = [0.5 0.5+1j*0.2];
Hm = mfilt.firdecim(m, num);
y = filter(Hm, [1:10]);
```

---

## See Also


[mfilt.firinterp](#) | [mfilt.firsrc](#) | [mfilt.firtdecim](#)

**Purpose** Cascade filter objects

**Syntax** `hm = cascade(hm1, hm2, ..., hmn)`

**Description** `hm = cascade(hm1, hm2, ..., hmn)` creates filter object `hm` by cascading (connecting in series) the individual filter objects `hm1`, `hm2`, and so on to `hmn`.

In block diagram form, the cascade looks like this, with `x` as the input to the filter `hm` and `y` the output from the cascade filter `hm`:



`mfilt.cascade` accepts any combination of `mfilt` and `dfilt` objects (discrete time filters) to cascade, as well as Farrow filter objects.

**Examples** Create a variety of `mfilt` objects and cascade them together.

```

hm(1) = mfilt.firdecim(12);
hm(2) = mfilt.firdecim(4);
h1 = mfilt.cascade(hm(1),hm(2));
hm(3) = mfilt.firinterp(4);
hm(4) = mfilt.firinterp(12);
h2 = mfilt.cascade(hm(3),hm(4));
% Cascade h1 and h2 together
h3 = mfilt.cascade(h1,h2,9600);
  
```

**See Also** `dfilt.cascade`

# mfilt.cicdecim

---

**Purpose** Fixed-point CIC decimator

**Syntax** `hm = mfilt.cicdecim(r,m,n,iwl,owl,wlps)`

**Description** `hm = mfilt.cicdecim(r,m,n,iwl,owl,wlps)` returns a cascaded integrator-comb (CIC) decimation filter object.

All of the input arguments are optional. To enter any optional value, you must include all optional values to the left of your desired value.

When you omit one or more input options, the omitted option applies the default values shown in the table below.

The following table describes the input arguments for creating `hm`.

Input Arguments	Description
<code>r</code>	Decimation factor applied to the input signal. Sharpens the response curve to let you change the shape of the response. <code>r</code> must be an integer value greater than or equal to 1. The default value is 2.
<code>m</code>	Differential delay. Changes the shape, number, and location of nulls in the filter response. Increasing <code>m</code> increases the sharpness of the nulls and the response between nulls. In practice, differential delay values of 1 or 2 are the most common. <code>m</code> must be an integer value greater than or equal to 1. The default value is 1.
<code>n</code>	Number of sections. Deepens the nulls in the response curve. Note that this is the number of either comb or integrator sections, not the total section count. 2 is the default value.
<code>iwl</code>	Word length of the input signal. Use any integer number of bits. The default value is 16 bits.

Input Arguments	Description
owl	Word length of the output signal. It can be any positive integer number of bits. By default, owl is 16 bits.
wlps	<p>Defines the number of bits per word in each filter section while accumulating the data in the integrator sections or while subtracting the data during the comb sections (using 'wrap' arithmetic). Enter wlps as a scalar or vector of length <math>2*n</math>, where <math>n</math> is the number of sections. When wlps is a scalar, the scalar value is applied to each filter section. The default is 16 for each section in the decimator.</p> <p>When you elect to specify wlps as an input argument, the FilterInternals property automatically switches from the default value of 'FullPrecision' to 'SpecifyWordLengths'.</p>

### Constraints and Word Length Considerations

CIC decimators have the following constraint — the word lengths of the filter section must be monotonically decreasing. The word length of each filter section must be the same size as, or smaller than, the word length of the previous filter section.

The formula for  $B_{max}$ , the most significant bit at the filter output, is given in the Hogenauer paper in the References below.

$$B_{max} = (N \log_2 RM + B_{in} - 1)$$

where  $B_{in}$  is the number of bits of the input.

The cast operations shown in the diagram in “Algorithms” on page 7-1023 perform the changes between the word lengths of each section. When you specify word lengths that do not follow the constraints above, the constructor returns an error.

When you specify the word lengths correctly, the most significant bit  $B_{max}$  stays the same throughout the filter, while the word length of each section either decreases or stays the same. This can cause the fraction length to change throughout the filter as least significant bits are truncated to decrease the word length, as shown in “Algorithms” on page 7-1023.

## Properties of the Object

Objects have properties that control the way the object behaves. This table lists all the properties for the filter, with a description of each.

Name	Values	Default	Description
Arithmetic	fixed	fixed	Reports the kind of arithmetic the filter uses. CIC decimators are always fixed-point filters.
DecimationFactor	Any positive integer	2	Amount to reduce the input sampling rate.
DifferentialDelay	Any positive integer	1	Sets the differential delay for the filter. Usually a value of one or two is appropriate.
FilterStructure	mfilt structure string	None	Reports the type of filter object. You cannot set this property — it is always read only and results from your choice of mfilt objects.
FilterInternals	FullPrecision, MinWordLengths, SpecifyPrecision, SpecifyWordLengths	FullPrecision	Set the usage mode for the filter. Refer to “Usage Modes” on page 7-1015 below for details.

<b>Name</b>	<b>Values</b>	<b>Default</b>	<b>Description</b>
InputFracLength	Any positive integer	15	The number of bits applied to the fraction length to interpret the input data to the filter.
InputOffset	Integers in the range $0 \leq \text{InputOffset} \leq r-1$	0	<p>Contains a value derived from the number of input samples and the decimation factor — <math>\text{InputOffset} = \text{mod}(\text{length}(nx), m)</math> where <math>nx</math> is the number of input samples that have been processed so far and <math>m</math> is the decimation factor.</p> <p>The <code>InputOffset</code> property applies only when you set the <code>PersistentMemory</code> property to true. See “<code>InputOffset</code>” on page 8-125 for more information.</p>
InputWordLength	Any positive integer	16	The number of bits applied to the word length to interpret the input data to the filter.

# mfilt.cicdecim

Name	Values	Default	Description
NumberOfSections	Any positive integer	2	Number of sections used in the decimator. Generally called n. Reflects either the number of decimator or comb sections, not the total number of sections in the filter.
OutputFracLength	Any positive integer	15	The number of bits applied to the fraction length to interpret the output data from the filter. Read-only.
OutputWordLength	Any positive integer	16	The number of bits applied to the word length to interpret the output data from the filter.
PersistentMemory	false or true	false	Determines whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter if you have not changed the filter since you constructed it. PersistentMemory returns to zero any state that the filter changes during processing. States

Name	Values	Default	Description
			that the filter does not change are not affected. When <code>PersistentMemory</code> is false, you cannot access the filter states. Setting <code>PersistentMemory</code> to true reveals the <code>States</code> property so you can modify the filter states.

Name	Values	Default	Description
SectionWordLengths	Any integer or a vector of length $2*n$ .	16	Defines the bits per section used while accumulating the data in the integrator sections or while subtracting the data during the comb sections (using 'wrap' arithmetic). Enter <code>SectionWordLengths</code> as a scalar or vector of length $2*n$ , where $n$ is the number of sections. When <code>SectionWordLengths</code> is a scalar, the scalar value is applied to each filter section. When <code>SectionWordLengths</code> is a vector of values,

# mfilt.cicdecim

Name	Values	Default	Description
			the values apply to the sections in order. The default is 16 for each section in the decimator. Available when FilterInternals is 'SpecifyWordLengths'.
States	filtstates.cic object	m+1-by-n matrix of zeros, after you call function int.	Stored conditions for the filter, including values for the integrator and comb sections before and after filtering. m is the differential delay of the comb section and n is the number of sections in the filter. The integrator states are stored in the first matrix row. States for the comb section fill the remaining rows in the matrix. Available for modification when PersistentMemory is true. Refer to the filtstates object in Signal Processing Toolbox documentation for more general information about the filtstates object.

## Usage Modes

There are four modes of usage for this which are set using the `FilterInternals` property

- `FullPrecision` — All word and fraction lengths set to  $B_{max} + 1$ , called  $B_{accum}$  by Fred Harris in [3]. Full Precision is the default setting.
- `MinWordLengths` — Automatically set the sections for minimum word lengths.
- `SpecifyWordLengths` — Specify the word lengths for each section.
- `SpecifyPrecision` — Specify precision by providing values for the word and fraction lengths for each section.

### Full Precision

In full precision mode, the word lengths of all sections and the output are set to  $B_{accum}$  as defined by

$$B_{accum} = \text{ceil}(N_{secs}(\text{Log}_2(D \times M)) + \text{InputWordLength})$$

where  $N_{secs}$  is the number of filter sections.

Section fraction lengths and the fraction length of the output are set to the input fraction length.

Here is the display for this mode:

```
FilterStructure: 'Cascaded Integrator-Comb Decimator'
Arithmetic: 'fixed'
DifferentialDelay: 1
NumberOfSections: 2
DecimationFactor: 4
PersistentMemory: false

InputWordLength: 16
InputFracLength: 15

FilterInternals: 'FullPrecision'
```

## Minimum Wordlengths

In minimum word length mode, you control the output word length explicitly. When the output word length is less than  $B_{accum}$ , roundoff noise is introduced at the output of the filter. Hogenauer's bit pruning theory (refer to [1]) states that one valid design criterion is to make the word lengths of the different sections of the filter smaller than  $B_{accum}$  as well, so that the roundoff noise introduced by all sections does not exceed the roundoff noise introduced at the output.

In this mode, the design calculates the word lengths of each section to meet the Hogenauer criterion. The algorithm subtracts the number of bits computed using eq. 21 in Hogenauer's paper from  $B_{accum}$  to determine the word length each section.

To compute the fraction lengths of the different sections, the algorithm notes that the bits thrown out for this word length criterion are least significant bits (LSB), therefore each bit thrown out at a particular section decrements the fraction length of that section by one bit compared to the input fraction length. Setting the output wordlength for the filter automatically sets the output fraction length as well.

Here is the display for this mode:

```
FilterStructure: 'Cascaded Integrator-Comb Decimator'  
Arithmetic: 'fixed'  
DifferentialDelay: 1  
NumberOfSections: 2  
DecimationFactor: 4  
PersistentMemory: false
```

```
InputWordLength: 16  
InputFracLength: 15
```

```
FilterInternals: 'MinWordLengths'
```

```
OutputWordLength: 16
```

```
Specify word lengths
```

In this mode, the design algorithm discards the LSBs, adjusting the fraction length so that unrecoverable overflow does not occur, always producing a reasonable output.

You can specify the word lengths for all sections and the output, but you cannot control the fraction lengths for those quantities.

To specify the word lengths, you enter a vector of length  $2 * (\text{NumberOfSections})$ , where each vector element represents the word length for a section. If you specify a scalar, such as  $B_{accum}$ , the full-precision output word length, the algorithm expands that scalar to a vector of the appropriate size, applying the scalar value to each section.

The CIC design does not check that the specified word lengths are monotonically decreasing. There are some cases where the word lengths are not necessarily monotonically decreasing, for example

```
hcic=mfilt.cicdecim;  
hcic.FilterInternals='minwordlengths';  
hcic.Outputwordlength=14;
```

which are valid CIC filters but the word lengths do not decrease monotonically across the sections.

Here is the display for the SpecifyWordLengths mode.

```
FilterStructure: 'Cascaded Integrator-Comb Decimator'  
Arithmetic: 'fixed'  
DifferentialDelay: 1  
NumberOfSections: 2  
DecimationFactor: 4  
PersistentMemory: false
```

```
InputWordLength: 16  
InputFracLength: 15
```

```
FilterInternals: 'SpecifyWordLengths'
```

```
SectionWordLengths: [19 18 18 17]
```

OutputWordLength: 16

Specify precision

In this mode, you have full control over the word length and fraction lengths of all sections and the filter output.

When you elect the SpecifyPrecision mode, you must enter a vector of length  $2*(NumberOfSections)$  with elements that represent the word length for each section. When you enter a scalar such as  $B_{accum}$ , `mfilt.cicdecim` expands that scalar to a vector of the appropriate size and applies the scalar value to each section and the output. The design does not check that this vector is monotonically decreasing.

Also, you must enter a vector of length  $2*(NumberOfSections)$  with elements that represent the fraction length for each section as well. When you enter a scalar such as  $B_{accum}$ , `mfilt.cicdecim` applies scalar expansion as done for the word lengths.

Here is the SpecifyPrecision display.

```
FilterStructure: 'Cascaded Integrator-Comb Decimator'  
Arithmetic: 'fixed'  
DifferentialDelay: 1  
NumberOfSections: 2  
DecimationFactor: 4  
PersistentMemory: false
```

```
InputWordLength: 16  
InputFracLength: 15
```

```
FilterInternals: 'SpecifyPrecision'
```

```
SectionWordLengths: [19 18 18 17]  
SectionFracLengths: [14 13 13 12]
```

```
OutputWordLength: 16  
OutputFracLength: 11
```

## About the States of the Filter

In the `states` property you find the states for both the integrator and comb portions of the filter. `states` is a matrix of dimensions  $m + 1$ -by- $n$ , with the states apportioned as follows:

- States for the integrator portion of the filter are stored in the first row of the state matrix.
- States for the comb portion fill the remaining rows in the state matrix..

To review the states of a CIC filter, use `int` to assign the states to a variable in MATLAB. As an example, here are the states for a CIC decimator `hm` before and after filtering a data set.

```
x = fi(ones(1,10),true,16,0); % Fixed-point input data.
hm = mfilt.cicdecim(2,1,2,16,16,16);
sts=int(hm.states)
set(hm,'InputFracLength',0); % Integer input specified.
y=filter(hm,x);
sts=int(hm.states)
```

STS is an integer matrix that `int` returns from the contents of the `filtstates.cic` object in `hm`.

## Design Considerations

When you design your CIC decimation filter, remember the following general points:

- The filter output spectrum has nulls at  $\omega = k * 2\pi/rm$  radians,  $k = 1,2,3\dots$
- Aliasing and imaging occur in the vicinity of the nulls.
- $n$ , the number of sections in the filter, determines the passband attenuation. Increasing  $n$  improves the filter ability to reject aliasing and imaging, but it also increases the droop (or rolloff) in the filter passband. Using an appropriate FIR filter in series after the CIC decimation filter can help you compensate for the induced droop.


- The DC gain for the filter is a function of the decimation factor. Raising the decimation factor increases the DC gain.

## Examples

This example applies a decimation factor  $r$  equal to 8 to a 160-point impulse signal. The signal output from the filter has  $160/r$ , or 20, points or samples. Choosing 10 bits for the word length represents a fairly common setting for analog to digital converters. The plot shown after the code presents the stem plot of the decimated signal, with 20 samples remaining after decimation:

```
m = 2; % Differential delays in the filter.
n = 4; % Filter sections
r = 8; % Decimation factor
x = int16(zeros(160,1)); x(1) = 1; % Create a 160-point
                                   % impulse signal.
hm = mfilt.cicdecim(r,m,n); % Expects 16-bit input
                               % by default.


y = filter(hm,x);
stem(double(y)); % Plot output as a stem plot.
xlabel('Samples'); ylabel('Amplitude');
title('Decimated Signal');
```



The next example demonstrates one way to compute the filter frequency response, using a 4-section decimation filter with the decimation factor set to 7:

```
hm = mfilt.cicdecim(7,1,4);  
fvtool(hm)
```

FVTool provides ways for you to change the title and x labels to match the figure shown. Here's the frequency response plot for the filter. For details about the transfer function used to produce the frequency response, refer to [1] in the References section.



This final example demonstrates the decimator for converting from 44.1 kHz audio to 22.05 kHz — decimation by two. To overlay the before and after signals, scale the output and plot the signals on a stem plot.

```

r = 2;                % Decimation factor.
hm = mfilt.cicdecim(r); % Use default NumberOfSections &
                       % DifferentialDelay property values.
fs = 44.1e3;         % Original sampling frequency: 44.1kHz.
n = 0:10239;        % 10240 samples, 0.232 second long signal.
x = sin(2*pi*1e3/fs*n); % Original signal, sinusoid at 1kHz.

y_fi = filter(hm,x); % 5120 samples, still 0.232 seconds.


% Scale the output to overlay the stem plots.
x = double(x);
y = double(y_fi);

```

```

y = y/max(abs(y));
stem(n(1:44)/fs,x(2:45)); hold on; % Plot original signal
                                % sampled at 44.1kHz.
stem(n(1:22)/(fs/r),y(3:24),'r','filled'); % Plot decimated
                                % signal (22.05kHz)
                                % in red.
xlabel('Time (seconds)');ylabel('Signal Value');

```




## Algorithms

To show how the CIC decimation filter is constructed, the following figure presents a block diagram of the filter structure for a two-section CIC decimation filter ( $n = 2$ ).  $fs$  is the high sampling rate, the input to the decimation process.

For details about the bits that are removed in the Comb section, refer to [1] in References.

# mfilt.cicdecim



mfilt.cicdecim calculates the fraction length at each section of the decimator to avoid overflows at the output of the filter.

## References

- [1] Hogenauer, E. B., "An Economical Class of Digital Filters for Decimation and Interpolation," *IEEE Transactions on Acoustics, Speech, and Signal Processing*, ASSP-29(2): pp. 155-162, 1981
- [2] Meyer-Baese, Uwe, "Hogenauer CIC Filters," in *Digital Signal Processing with Field Programmable Gate Arrays*, Springer, 2001, pp. 155-172
- [3] Harris, Fredric J, *Multirate Signal Processing for Communication Systems*, Prentice-Hall PTR, 2004 , pp. 343

## See Also

mfilt | mfilt.cicinterp

**Purpose** Fixed-point CIC interpolator

**Syntax**

```
hm = mfilt.cicinterp(R,M,N,ILW,OWL,WLPS)
hm = mfilt.cicinterp
hm = mfilt.cicinterp(R,...)
```

**Description** `hm = mfilt.cicinterp(R,M,N,ILW,OWL,WLPS)` constructs a cascaded integrator-comb (CIC) interpolation filter object that uses fixed-point arithmetic.

All of the input arguments are optional. To enter any optional value, you must include all optional values to the left of your desired value.

When you omit one or more input options, the omitted option applies the default values shown in the table below.

The following table describes the input arguments for creating `hm`.

Input Arguments	Description
R	Interpolation factor applied to the input signal. Sharpens the response curve to let you change the shape of the response. R must be an integer value greater than or equal to 1. The default value is 2.
M	Differential delay. Changes the shape, number, and location of nulls in the filter response. Increasing M increases the sharpness of the nulls and the response between nulls. In practice, differential delay values of 1 or 2 are the most common. M must be an integer value greater than or equal to 1. The default value is 1.
N	Number of sections. Deepens the nulls in the response curve. Note that this is the number of either comb or integrator sections, not the total section count. By default, the filter has two sections.

Input Arguments	Description
IWL	Word length of the input signal. Use any integer number of bits. The default value is 16 bits.
OWL	Word length of the output signal. It can be any positive integer number of bits. By default, OWL is 16 bits.
WLPS	<p>Defines the number of bits per word in each filter section while accumulating the data in the integrator sections or while subtracting the data during the comb sections (using 'wrap' arithmetic). Enter WLPS as a scalar or vector of length <math>2*N</math>, where <math>N</math> is the number of sections. When WLPS is a scalar, the scalar value is applied to each filter section. The default is 16 for each section in the integrator.</p> <p>When you elect to specify <code>wlps</code> as an input argument, the <code>FilterInternals</code> property automatically switches from the default value of 'FullPrecision' to 'SpecifyWordLengths'.</p>

`hm = mfilt.cicinterp` constructs the CIC interpolator using the default values for the optional input arguments.

`hm = mfilt.cicinterp(R,...)` constructs the CIC interpolator applying the values you provide for `R` and any other values you specify as input arguments.

## Constraints and Conversions

In Hogenauer [1], the author describes the constraints on CIC interpolator filters. `mfilt.cicinterp` enforces a constraint—the word lengths of the filter sections must be non-decreasing. That is, the word length of each filter section must be the same size as, or greater than, the word length of the previous filter section.

The formula for  $W_j$ , the minimum register width, is derived in [1]. The formula for  $W_j$  is given by

$$W_j = \text{ceil}(B_{in} + \log_2 G_j)$$

where  $G_j$ , the maximum register growth up to the  $j$ th section, is given by

$$G_j = \begin{cases} 2^j, & j = 1, 2, \dots, N \\ \frac{2^{2N-j} (RM)^{j-N}}{R}, & j = N + 1, \dots, 2N \end{cases}$$

When the differential delay,  $M$ , is 1, there is also a special condition for the register width of the last comb,  $W_N$ , that is given by

$$W_N = B_{in} + N - 1 \quad \text{if } M = 1$$

The conversions denoted by the cast blocks in the integrator diagrams in “Algorithms” on page 7-1035 perform the changes between the word lengths of each section. When you specify word lengths that do not follow the constraints described in this section, `mfilt.cicinterp` returns an error.

The fraction lengths and scalings of the filter sections do not change. At each section the word length is either staying the same or increasing. The signal scaling can change at the output after the final filter section if you choose the output word length to be less than the word length of the final filter section.

## Properties of the Object

The following table lists the properties for the filter with a description of each.

Name	Values	Default	Description
Arithmetic	fixed	fixed	Reports the kind of arithmetic the filter uses. CIC interpolators are always fixed-point filters.
InterpolationFactor	Any positive integer	2	Amount to increase the input sampling rate.
DifferentialDelay	Any positive integer	1	Sets the differential delay for the filter. Usually a value of one or two is appropriate.
FilterStructure	mfilt structure string	None	Reports the type of filter object, such as a interpolator or fractional integrator. You cannot set this property — it is always read only and results from your choice of mfilt objects.
FilterInternals	FullPrecision, MinWordLengths, SpecifyWordLengths, SpecifyPrecision	FullPrecision	Set the usage mode for the filter. Refer to “Usage Modes” on page 7-1031 below for details.
InputFracLength	Any positive integer	16	The number of bits applied as the fraction length to interpret the input data to the filter.

<b>Name</b>	<b>Values</b>	<b>Default</b>	<b>Description</b>
InputWordLength	Any positive integer	16	The number of bits applied to the word length to interpret the input data to the filter.
NumberOfSections	Any positive integer	2	Number of sections used in the interpolator. Generally called n. Reflects either the number of interpolator or comb sections, not the total number of sections in the filter.
OutputFracLength	Any positive integer	15	The number of bits applied to the fraction length to interpret the output data from the filter. Read-only.
OutputWordLength	Any positive integer	16	The number of bits applied to the word length to interpret the output data from the filter.
PersistentMemory	false or true	false	Determines whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter if you have not changed the filter since you constructed it. PersistentMemory returns to zero any state that the filter changes during processing.

# mfilt.cicinterp

Name	Values	Default	Description
			States that the filter does not change are not affected. When <code>PersistentMemory</code> is <code>false</code> , you cannot access the filter states. Setting <code>PersistentMemory</code> to <code>true</code> reveals the <code>States</code> property so you can modify the filter states.
<code>SectionWordLengths</code>	<p>Any integer or a vector of length <math>2^N</math>, where <math>N</math> is a positive integer.</p> <p>This property only applies when the <code>FilterInternals</code> is <code>SpecifyWordLengths</code>.</p>	16	Defines the bits per section used while accumulating the data in the integrator sections or while subtracting the data during the comb sections (using 'wrap' arithmetic). Enter <code>SectionWordLengths</code> as a scalar or vector of length $2*n$ , where $n$ is the number of sections. When <code>SectionWordLengths</code> is a scalar, the scalar value is applied to each filter section. When <code>SectionWordLengths</code> is a vector of values, the values apply to the sections in order. The default is 16 for each section in the interpolator. Available

Name	Values	Default	Description
			when <code>FilterInternals</code> is 'SpecifyWordLengths'.
States	<code>filtstates.cic</code> object	$m+1$ -by- $n$ matrix of zeros, after you call function <code>int</code> .	Stored conditions for the filter, including values for the integrator and comb sections before and after filtering. $m$ is the differential delay of the comb section and $n$ is the number of sections in the filter. The integrator states are stored in the first matrix row. States for the comb section fill the remaining rows in the matrix. Available for modification when <code>PersistentMemory</code> is true. Refer to the <code>filtstates</code> object in Signal Processing Toolbox documentation for more general information about the <code>filtstates</code> object.

### Usage Modes

There are usage modes which are set using the `FilterInternals` property:

- **FullPrecision** — In this mode, the word and fraction lengths of the filter sections and outputs are automatically selected for you. The output and last section word lengths are set to:

$$\text{wordlength} = \text{ceil}(\log_2((RM)^N / R)) + I,$$

where  $R$  is the interpolation factor,  $M$  is the differential delay,  $N$  is the number of filter sections, and  $I$  denotes the input word length.

- **MinWordLengths** — In this mode, you specify the word length of the filter output in the `OutputWordLength` property. The word lengths of the filter sections are automatically set in the same way as in the `FullPrecision` mode. The section fraction lengths are set to the input fraction length. The output fraction length is set to the input fraction length minus the difference between the last section and output word lengths.
- **SpecifyWordLengths** — In this mode, you specify the word lengths of the filter sections and output in the `SectionWordLengths` and `OutputWordLength` properties. The fraction lengths of the filter sections are set such that the spread between word length and fraction length is the same as in full-precision mode. The output fraction length is set to the input fraction length minus the difference between the last section and output word lengths.
- **SpecifyPrecision** — In this mode, you specify the word and fraction lengths of the filter sections and output in the `SectionWordLengths`, `SectionFracLengths`, `OutputWordLength`, and `OutputFracLength` properties.

## About the States of the Filter

In the `states` property you find the states for both the integrator and comb portions of the filter. `states` is a matrix of dimensions  $m+1$ -by- $n$ , with the states apportioned as follows:

- States for the integrator portion of the filter are stored in the first row of the state matrix.
- States for the comb portion fill the remaining rows in the state matrix.

To review the states of a CIC filter, use the `int` method to assign the states. As an example, here are the states for a CIC interpolator before and after filtering data:

```
x = fi(cos(pi/4*[0:99]),true,16,0); % Fixed-point input data
```

```

hm = mfilt.cicinterp(2,1,2,16,16,16);
% get initial states-all zero
sts=int(hm.states)
set(hm,'InputFracLength',0); % Integer input specified
y=filter(hm,x);
sts=int(hm.states)
%sts =
%
%      -1      -1
%      -1      -1

```

### Design Considerations

When you design your CIC interpolation filter, remember the following general points:

- The filter output spectrum has nulls at  $\omega = k * 2\pi/rm$  radians,  $k = 1,2,3,\dots$
- Aliasing and imaging occur in the vicinity of the nulls.
- $n$ , the number of sections in the filter, determines the passband attenuation. Increasing  $n$  improves the filter ability to reject aliasing and imaging, but it also increases the droop or rolloff in the filter passband. Using an appropriate FIR filter in series after the CIC interpolation filter can help you compensate for the induced droop.
- The DC gain for the filter is a function of the interpolation factor. Raising the interpolation factor increases the DC gain.

### Examples

Demonstrate interpolation by a factor of two, in this case from 22.05 kHz to 44.1 kHz. Note the scaling required to see the results in the stem plot and to use the full range of the int16 data type.

```


R = 2; % Interpolation factor.
hm = mfilt.cicinterp(R); % Use default NumberOfSections and
% DifferentialDelay property values.
fs = 22.05e3; % Original sample frequency:22.05 kHz.
n = 0:5119; % 5120 samples, .232 second long signal.
x = sin(2*pi*1e3/fs*n); % Original signal, sinusoid at 1 kHz.

```

# mfilt.cicinterp

```
y_fi = filter(hm,x); % 5120 samples, still 0.232 seconds.  
  
% Scale the output to overlay stem plots correctly.  
x = double(x);  
y = double(y_fi);  
y = y/max(abs(y));  
stem(n(1:22)/fs,x(1:22),'filled'); % Plot original signal sampled  
% at 22.05 kHz.  
  
hold on;  
stem(n(1:44)/(fs*R),y(4:47),'r'); % Plot interpolated signal  
% (44.1 kHz) in red.  
  
xlabel('Time (sec)');ylabel('Signal Value');
```

As you expect, the plot shows that the interpolated signal matches the input sine shape, with additional samples between each original sample.




Use the filter visualization tool (FVTool) to plot the response of the interpolator object. For example, to plot the response of an interpolator with an interpolation factor of 7, 4 sections, and 1 differential delay, do something like the following:

```
hm = mfilt.cicinterp(7,1,4)
fvtool(hm)
```

## Algorithms

To show how the CIC interpolation filter is constructed, the following figure presents a block diagram of the filter structure for a two-section CIC interpolation filter ( $n = 2$ ).  $f_s$  is the high sampling rate, the output from the interpolation process.

For details about the bits that are removed in the integrator section, refer to [1] in References.



When you select `MinWordLengths`, the filter section word lengths are automatically set to the minimum number of bits possible in a valid CIC interpolator. `mfilt.cicinterp` computes the wordlength for each section so the roundoff noise introduced by all sections is less than the roundoff noise introduced by the quantization at the output.

## References

[1] Hogenauer, E. B., "An Economical Class of Digital Filters for Decimation and Interpolation," *IEEE Transactions on Acoustics, Speech, and Signal Processing*, ASSP-29(2): pp. 155-162, 1981

[2] Meyer-Baese, Uwe, "Hogenauer CIC Filters," in *Digital Signal Processing with Field Programmable Gate Arrays*, Springer, 2001, pp. 155-172

[3] Harris, Fredric J., *Multirate Signal Processing for Communication Systems*, Prentice-Hall PTR, 2004 , pp. 343

**Purpose** Sample rate converter with arbitrary conversion factor

**Syntax**

```
hm = mfilt.farrowsrc(L,M,C)
hm = mfilt.farrowsrc
hm = mfilt.farrowsrc(1,...)
```

**Description** `hm = mfilt.farrowsrc(L,M,C)` returns a filter object that is a natural extension of `dfilt.farrowfd` with a time-varying fractional delay. It provides a economical implementation of a sample rate converter with an arbitrary conversion factor. This filter works well in the interpolation case, but may exhibit poor anti-aliasing properties in the decimation case.

**Note** You can use the `realizemdl` method to create a Simulink block of a filter created using `mfilt.farrowsrc`.

### Input Arguments

The following table describes the input arguments for creating `hm`.

Input Argument	Description
l	Interpolation factor for the filter. l specifies the amount to increase the input sampling rate. The default value of l is 3.
m	Decimation factor for the filter. m specifies the amount to decrease the input sampling rate. The default value for m is 2.
c	Coefficients for the filter. When no input arguments are specified, the default coefficients are $[-1 \ 1; 1, \ 0]$

`hm = mfilt.farrowsrc` constructs the filter using the default values for l, m, and c.

# **mfilt.farrowsrc**

---

`hm = mfilt.farrowsrc(1,...)` constructs the filter using the input arguments you provide and defaults for the argument you omit.

## **mfilt.farrowsrc Object Properties**

Every multirate filter object has properties that govern the way it behaves when you use it. Note that many of the properties are also input arguments for creating `mfilt.farrowsrc` objects. The next table describes each property for an `mfilt.farrowsrc` filter object.

<b>Name</b>	<b>Values</b>	<b>Description</b>
FilterStructure	String	Reports the type of filter object. You cannot set this property — it is always read only and results from your choice of <code>mfilt</code> object.
Arithmetic	String	Reports the arithmetic precision used by the filter.
Coefficients	Vector	Vector containing the coefficients of the FIR lowpass filter
InterpolationFactor	Integer	Interpolation factor for the filter. It specifies the amount to increase the input sampling rate.


<b>Name</b>	<b>Values</b>	<b>Description</b>
DecimationFactor	Integer	Decimation factor for the filter. It specifies the amount to increase the input sampling rate.
PersistentMemory	false or true	Determines whether the filter states are restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter if you have not changed the filter since you constructed it. PersistentMemory returns to zero any state that the filter changes during processing. States that the filter does not change are not affected.

## Examples

Interpolation by a factor of 8. This object removes the spectral replicas in the signal after interpolation.

```
[L,M] = rat(48/44.1);
Hm = mfilt.farrowsrc(L,M);           % We use the default filter
Fs = 44.1e3;                         % Original sampling frequency
n = 0:9407;                           % 9408 samples, 0.213 seconds long
x = sin(2*pi*1e3/Fs*n);               % Original signal, sinusoid at 1kHz
y = filter(Hm,x);                     % 10241 samples, still 0.213 seconds
stem(n(1:45)/Fs,x(1:45))              % Plot original sampled at 44.1kHz
hold on
% Plot fractionally interpolated signal (48kHz) in red
stem((n(2:50)-1)/(Fs*L/M),y(2:50),'r','filled')
xlabel('Time (sec)');ylabel('Signal value')
legend('44.1 kHz sample rate','48kHz sample rate')
```

The results of the example are shown in the following figure:



**Purpose**                      Overlap-add FIR polyphase interpolator

**Syntax**                      hm = mfilt.fftfirinterp(l,num,b1)  
                                   hm = mfilt.fftfirinterp  
                                   hm = mfilt.fftfirinterp(l,...)

**Description**               hm = mfilt.fftfirinterp(l,num,b1) returns a discrete-time FIR filter object that uses the overlap-add method for filtering input data.

The input arguments are optional. To enter any optional value, you must include all optional values to the left of your desired value.

When you omit one or more input options, the omitted option applies the default values shown in the table below.

The number of FFT points is given by  $[b1 + \text{ceil}(\text{length}(\text{num})/l) - 1]$ . It is to your advantage to choose *b1* such that the number of FFT points is a power of two—using powers of two can improve the efficiency of the FFT and the associated interpolation process.

**Input Arguments**

The following table describes the input arguments for creating *hm*.

Input Argument	Description
l	Interpolation factor for the filter. l specifies the amount to increase the input sampling rate. It must be an integer. When you do not specify a value for l it defaults to 2.
num	Vector containing the coefficients of the FIR lowpass filter used for interpolation. When num is not provided as an input, <code>fftfirinterp</code> uses a lowpass Nyquist filter with gain equal to 1 and cutoff frequency equal to $\pi/l$ by default.
b1	Length of each block of input data used in the filtering. b1 must be an integer. When you omit input b1, it defaults to 100

# mfilt.fftfirinterp

---

`hm = mfilt.fftfirinterp` constructs the filter using the default values for `l`, `num`, and `bl`.

`hm = mfilt.fftfirinterp(l,...)` constructs the filter using the input arguments you provide and defaults for the argument you omit.

## mfilt.fftfirinterp Object Properties

Every multirate filter object has properties that govern the way it behaves when you use it. Note that many of the properties are also input arguments for creating `mfilt.fftfirinterp` objects. The next table describes each property for an `mfilt.fftfirinterp` filter object.

Name	Values	Description
FilterStructure		Reports the type of filter object. You cannot set this property — it is always read only and results from your choice of <code>mfilt</code> object.
Numerator		Vector containing the coefficients of the FIR lowpass filter used for interpolation.
InterpolationFactor		Interpolation factor for the filter. It specifies the amount to increase the input sampling rate. It must be an integer.
BlockLength		Length of each block of input data used in the filtering.

<b>Name</b>	<b>Values</b>	<b>Description</b>
PersistentMemory	false or true	Determines whether the filter states are restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter if you have not changed the filter since you constructed it. PersistentMemory returns to zero any state that the filter changes during processing. States that the filter does not change are not affected.
States		Stored conditions for the filter, including values for the interpolator states.

## Examples

Interpolation by a factor of 8. This object removes the spectral replicas in the signal after interpolation.

```

l = 8; % Interpolation factor
hm = mfilt.fftfirinterp(l); % We use the default filter
n = 8192; % Number of points
hm.blocklength = n; % Set block length to number of points
fs = 44.1e3; % Original sample freq: 44.1 kHz.
n = 0:n-1; % 0.1858 secs of data
x = sin(2*pi*n*22e3/fs); % Original signal, sinusoid at 22 kHz
y = filter(hm,x); % Interpolated sinusoid
xu = l*upsample(x,8); % Upsample to compare--the spectrum
% does not change


[px,f]=periodogram(xu,[],65536,l*fs);% Power spectrum of original
% signal
[py,f]=periodogram(y,[],65536,l*fs); % Power spectrum of
% interpolated signal

```

# mfilt.fftfirinterp

```
plot(f,10*log10([fs*px,1*fs*py]))  
legend('22 kHz sinusoid sampled at 44.1 kHz',...  
'22 kHz sinusoid sampled at 352.8 kHz')  
xlabel('Frequency (Hz)'); ylabel('Power Spectrum');
```

To see the results of the example, look at this figure.



## See Also

[mfilt.firinterp](#) | [mfilt.holdinterp](#) | [mfilt.linearinterp](#) |  
[mfilt.firsrc](#) | [mfilt.cicinterp](#)

**Purpose** Direct-form FIR polyphase decimator

**Syntax**  
`hm = mfilt.firdecim(m)`  
`hm = mfilt.firdecim(m,num)`

**Description** `hm = mfilt.firdecim(m)` returns a direct-form FIR polyphase decimator object `hm` with a decimation factor of  $m$ . A lowpass Nyquist filter of gain 1 and cutoff frequency of  $\pi/m$  is designed by default. This filter allows some aliasing in the transition band but it very efficient because the first polyphase component is a pure delay.

`hm = mfilt.firdecim(m,num)` uses the coefficients specified by `num` for the decimation filter. This lets you specify more completely the FIR filter to use for the decimator.

Make this filter a fixed-point or single-precision filter by changing the value of the `Arithmetic` property for the filter `hm` as follows:

- To change to single-precision filtering, enter

```
set(hm,'arithmetic','single');
```

- To change to fixed-point filtering, enter

```
set(hm,'arithmetic','fixed');
```

## Input Arguments

The following table describes the input arguments for creating `hm`.

# mfilt.firdecim

Input Argument	Description
m	Decimation factor for the filter. m specifies the amount to reduce the sampling rate of the input signal. It must be an integer. When you do not specify a value for m it defaults to 2.
num	Vector containing the coefficients of the FIR lowpass filter used for decimation. When num is not provided as an input, mfilt.firdecim constructs a lowpass Nyquist filter with gain of 1 and cutoff frequency equal to $\pi/m$ by default. The default length for the Nyquist filter is $24*m$ . Therefore, each polyphase filter component has length 24.

## Object Properties

This section describes the properties for both floating-point filters (double-precision and single-precision) and fixed-point filters.

### Floating-Point Filter Properties

Every multirate filter object has properties that govern the way it behaves when you use it. Note that many of the properties are also input arguments for creating mfilt.firdecim objects. The next table describes each property for an mfilt.firdecim filter object.

Name	Values	Description
Arithmetic	Double, single, fixed	Defines the arithmetic the filter uses. Gives you the options double, single, and fixed. In short, this property defines the operation mode for your filter.
DecimationFactor	Integer	Decimation factor for the filter. m specifies the amount to reduce the sampling rate of

Name	Values	Description
		the input signal. It must be an integer.
FilterStructure	String	Reports the type of filter object. You cannot set this property — it is always read only and results from your choice of <code>mfilt</code> object. Describes the signal flow for the filter object.
InputOffset	Integers	Contains a value derived from the number of input samples and the decimation factor — $\text{InputOffset} = \text{mod}(\text{length}(nx), m)$ where $nx$ is the number of input samples that have been processed so far and $m$ is the decimation factor.
Numerator	Vector	Vector containing the coefficients of the FIR lowpass filter used for decimation.
PersistentMemory	false, true	Determines whether the filter states get restored to zeros for each filtering operation. The starting values are the values in place when you create the filter if you have not changed the filter since you constructed it. <code>PersistentMemory</code> set to <code>false</code> returns filter states to the default values after filtering. States that the filter does not change are not affected. Setting this to

Name	Values	Description
		true allows you to modify the States, InputOffset, and PolyphaseAccum properties.
PolyphaseAccum	0 in double, single, or fixed for the different filter arithmetic settings.	Differentiates between the adders in the filter that work in full precision at all times (PolyphaseAccum) and the adders in the filter that the user controls and that may introduce quantization effects when FilterInternals is set to SpecifyPrecision.
States	Double, single, or fi matching the filter arithmetic setting.	This property contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions. Double is the default setting for floating-point filters in double arithmetic.

## Fixed-Point Filter Properties

This table shows the properties associated with the fixed-point implementation of the filter. You see one or more of these properties when you set Arithmetic to fixed. Some of the properties have different default values when they refer fixed point filters. One example is the property PolyphaseAccum which stores data as doubles when you use your filter in double-precision mode, but stores a fi object in fixed-point mode.

**Note** The table lists all of the properties that a fixed-point filter can have. Many of the properties listed are dynamic, meaning they exist only in response to the settings of other properties. To view all of the characteristics for a filter at any time, use `info(hm)` where `hm` is a filter.

For further information about the properties of this filter or any `mfilt` object, refer to “Multirate Filter Properties” on page 8-115.

<b>Name</b>	<b>Values</b>	<b>Description</b>
AccumFracLength	Any positive or negative integer number of bits [32]	Specifies the fraction length used to interpret data output by the accumulator. This is a property of FIR filters.
AccumWordLength	Any integer number of bits [39]	Sets the word length used to store data in the accumulator.
Arithmetic	fixed for fixed-point filters	Setting this to <code>fixed</code> allows you to modify other filter properties to customize your fixed-point filter.
CoeffAutoScale	[true], false	Specifies whether the filter automatically chooses the proper fraction length to represent filter coefficients without overflowing. Turning this off by setting the value to <code>false</code> enables you to change the <code>NumFracLength</code> property value to specify the precision used.
CoeffWordLength	Any integer number of bits [16]	Specifies the word length to apply to filter coefficients.

## mfilt.firdecim

---

Name	Values	Description
FilterInternals	[FullPrecision], SpecifyPrecision	Controls whether the filter automatically sets the output word and fraction lengths, product word and fraction lengths, and the accumulator word and fraction lengths to maintain the best precision results during filtering. The default value, FullPrecision, sets automatic word and fraction length determination by the filter. SpecifyPrecision makes the output and accumulator-related properties available so you can set your own word and fraction lengths for them.
InputFracLength	Any positive or negative integer number of bits [15]	Specifies the fraction length the filter uses to interpret input data.
InputWordLength	Any integer number of bits [16]	Specifies the word length applied to interpret input data.
OutputFracLength	Any positive or negative integer number of bits [32]	Determines how the filter interprets the filter output data. You can change the value of OutputFracLength when you set FilterInternals to SpecifyPrecision.
OutputWordLength	Any integer number of bits [39]	Determines the word length used for the output data. You make this property editable by setting FilterInternals to SpecifyPrecision.

Name	Values	Description
OverflowMode	saturate, [wrap]	<p>Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either <code>saturate</code> (limit the output to the largest positive or negative representable value) or <code>wrap</code> (set overflowing values to the nearest representable value using modular arithmetic.) The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow — they maintain full precision.</p>
RoundMode	[convergent], ceil, fix, floor, nearest, round	<p>Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths).</p> <ul style="list-style-type: none"> <li>• <code>ceil</code> - Round toward positive infinity.</li> <li>• <code>convergent</code> - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.</li> <li>• <code>fix</code> - Round toward zero.</li> <li>• <code>floor</code> - Round toward negative infinity.</li> <li>• <code>nearest</code> - Round toward nearest. Ties round toward positive infinity.</li> <li>• <code>round</code> - Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.</li> </ul>


# mfilt.firdecim

Name	Values	Description
		The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always round. Finally, products never overflow — they maintain full precision.
Signed	[true], false	Specifies whether the filter uses signed or unsigned fixed-point coefficients. Only coefficients reflect this property setting.
States	fi object	This property contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions. The states use fi objects, with the associated properties from those objects. For details, refer to fixed-point objects in Fixed-Point Toolbox documentation. For information about the ordering of the states, refer to the filter structure section.

## Filter Structure

To provide decimation, `mfilt.firdecim` uses the following structure. At the input you see a commutator that operates counterclockwise, moving from position 0 to position 2, position 1, and back to position 0 as input samples enter the filter.

The following figure details the signal flow for the direct form FIR filter implemented by `mfilt.firdecim`.



Notice the order of the states in the filter flow diagram. States 1 through 9 appear in the diagram above each delay element. State 1 applies to the first delay element in phase 2. State 2 applies to the first delay element in phase 1. State 3 applies to the first delay element in phase 0. State 4 applies to the second delay in phase 2, and so on. When you provide the states for the filter as a vector to the States property, the above description explains how the filter assigns the states you specify.

In property value form, the states for a filter `hm` are

```
hm.states=[1:9];
```


## Examples

Convert an input signal from 44.1 kHz to 22.05 kHz using decimation by a factor of 2. In the figure that appears after the example code, you see the results of the decimation.

```
m = 2; % Decimation factor.
hm = mfilter.firdecim(m); % Use the default filter.
fs = 44.1e3; % Original sample freq: 44.1kHz.
n = 0:10239; % 10240 samples, 0.232 second long
% signal.
x = sin(2*pi*1e3/fs*n); % Original signal--sinusoid at 1kHz.
```

# mfilt.firdecim

```
y = filter(hm,x);           % 5120 samples, 0.232 seconds.  
stem(n(1:44)/fs,x(1:44))   % Plot original sampled at 44.1 kHz.  
hold on                    % Plot decimated signal (22.05 kHz)  
                           % in red.  
stem(n(1:22)/(fs/m),y(13:34),'r','filled')  
xlabel('Time (sec)');ylabel('Signal Value')
```



## See Also

[mfilt.firtdecim](#) | [mfilt.firsrc](#) | [mfilt.cicdecim](#)

**Purpose** Direct-form FIR polyphase fractional decimator

**Syntax** `hm = mfilt.firfracdecim(1,m,num)`

**Description** `mfilt.firfracdecim` will be removed in a future release. Use `mfilt.firsrc` instead.

`hm = mfilt.firfracdecim(1,m,num)` returns a direct-form FIR polyphase fractional decimator. Input argument `1` is the interpolation factor. `1` must be an integer. When you omit `1` in the calling syntax, it defaults to `2`. `m` is the decimation factor. It must be an integer. If not specified, it defaults to `l+1`.

`num` is a vector containing the coefficients of the FIR lowpass filter used for decimation. If you omit `num`, a lowpass Nyquist filter of gain `1` and cutoff frequency of  $\pi/\max(1,m)$  is used by default.

By specifying both a decimation factor and an interpolation factor, you can decimate your input signal by noninteger amounts. The fractional decimator first interpolates the input, then decimates to result in an output signal whose sample rate is  $1/m$  of the input rate. By default, the resulting decimation factor is  $2/3$  when you do not provide `1` and `m` in the calling syntax. Specify `1` smaller than `m` for proper decimation.

## Input Arguments

The following table describes the input arguments for creating `hm`.

Input Argument	Description
<code>1</code>	Interpolation factor for the filter. It must be an integer. When you do not specify a value for <code>1</code> it defaults to <code>2</code> .
<code>num</code>	Vector containing the coefficients of the FIR lowpass filter used for decimation. When <code>num</code> is not provided as an input, <code>firfracdecim</code> uses a lowpass Nyquist

## **mfilt.firfracdecim (Obsolete)**

---

<b>Input Argument</b>	<b>Description</b>
	filter with gain equal to 1 and cutoff frequency equal to $\pi/\max(1,m)$ by default.
<code>m</code>	Decimation factor for the filter. <code>m</code> specifies the amount to reduce the sampling rate of the input signal. It must be an integer. When you do not specify a value for <code>m</code> it defaults to <code>1 + 1</code> .

### **mfilt.firfracdecim Object Properties**

Every multirate filter object has properties that govern the way it behaves when you use it. Note that many of the properties are also input arguments for creating `mfilt.firfracdecim` objects. The next table describes each property for an `mfilt.firfracdecim` filter object.

<b>Name</b>	<b>Values</b>	<b>Description</b>
<code>FilterStructure</code>	String	Reports the type of filter object, such as a decimator or fractional decimator. You cannot set this property — it is always read only and results from your choice of <code>mfilt</code> object.
<code>InputOffset</code>	Integers	Contains the number of input data samples processed without generating an output sample. The default value is 0.
<code>Numerator</code>	Vector	Vector containing the coefficients of the FIR lowpass filter used for interpolation.

## mfilt.firfracdecim (Obsolete)

Name	Values	Description
RateChangeFactors	[1,m]	Reports the decimation (m) and interpolation (l) factors for the filter object. Combining these factors results in the final rate change for the signal.
PersistentMemory	false or true	Determines whether the filter states are restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter if you have not changed the filter since you constructed it. PersistentMemory returns to zero any state that the filter changes during processing. States that the filter does not change are not affected.
States	Matrix	Stored conditions for the delays between each interpolator phase, the filter states, and the states at the output of each phase in the filter.  The number of states is $(lh-1)*m+(l-1)*(lo+mo)$ where lh is the length of each subfilter, and l and m are the interpolation and decimation factors. lo and mo, the input and output delays between each interpolation phase, are integers from Euclid's theorem such that $lo*l-mo*m = -1$ (refer to the reference for more details). Use euclidfactors to get lo and mo for an mfilter.firfracdecim object


# mfilt.firfracdecim (Obsolete)

## Examples

To demonstrate `firfracdecim`, perform a fractional decimation by a factor of  $2/3$ . This is one way to downsample a 48 kHz signal to 32 kHz, commonly done in audio processing.

```
l = 2; m = 3; % Interpolation/decimation factors.
hm = mfilter.firfracdecim(l,m); % We use the default
fs = 48e3; % Original sample freq: 48 kHz.
n = 0:10239; % 10240 samples, 0.213 second long
% signal
x = sin(2*pi*1e3/fs*n); % Original signal, sinusoid at 1 kHz
y = filter(hm,x); % 9408 samples, still 0.213 seconds
stem(n(1:49)/fs,x(1:49)); hold on; % Plot original signal sampled
% at 48 kHz
stem(n(1:32)/(fs*l/m),y(13:44),'r','filled') % Plot decimated
% signal at 32 kHz
xlabel('Time (sec)');
```

As shown, the plot clearly demonstrates the reduced sampling frequency of 32 kHz.



## **References**

Fliege, N.J., *Multirate Digital Signal Processing*, John Wiley & Sons, Ltd., 1994

## **See Also**

`mfilt.firsrc` | `mfilt.firinterp` | `mfilt.firdecim`

# **mfilt.firfracinterp (Obsolete)**

---

**Purpose** Direct-form FIR polyphase fractional interpolator

**Syntax** `hm = mfilt.firfracinterp(1,m,num)`

**Description** `mfilt.firfracinterp` will be removed in a future release. Use `mfilt.firsrc` instead.

`hm = mfilt.firfracinterp(1,m,num)` returns a direct-form FIR polyphase fractional interpolator `mfilt` object. `1` is the interpolation factor. It must be an integer. If not specified, `1` defaults to `3`.

`m` is the decimation factor. Like `1`, it must be an integer. If you do not specify `m` in the calling syntax, it defaults to `1`. If you also do not specify a value for `1`, `m` defaults to `2`.

`num` is a vector containing the coefficients of the FIR lowpass filter used for interpolation. If omitted, a lowpass Nyquist filter of gain `1` and cutoff frequency of  $n/\max(1,m)$  is used by default.

By specifying both a decimation factor and an interpolation factor, you can interpolate your input signal by noninteger amounts. The fractional interpolator first interpolates the input, then decimates to result in an output signal whose sample rate is  $1/m$  of the input rate. For proper interpolation, you specify `1` to be greater than `m`. By default, the resulting interpolation factor is  $3/2$  when you do not provide `1` and `m` in the calling syntax.

## **Input Arguments**

The following table describes the input arguments for creating `hm`.

## mfilt.firfracinterp (Obsolete)

Input Argument	Description
l	Interpolation factor for the filter. l specifies the amount to increase the input sampling rate. It must be an integer. When you do not specify a value for l it defaults to 3.
num	Vector containing the coefficients of the FIR lowpass filter used for interpolation. When num is not provided as an input, firfracinterp uses a lowpass Nyquist filter with gain equal to 1 and cutoff frequency equal to $\pi/\max(1,m)$ by default.
m	Decimation factor for the filter. m specifies the amount to reduce the sampling rate of the input signal. It must be an integer. When you do not specify a value for m it defaults to 1. When you do not specify l as well, m defaults to 2.

### mfilt.firfracinterp Object Properties

Every multirate filter object has properties that govern the way it behaves when you use it. Note that many of the properties are also input arguments for creating `mfilt.firfracinterp` objects. The next table describes each property for an `mfilt.firfracinterp` filter object.

Name	Values	Description
FilterStructure		Reports the type of filter object. You cannot set this property — it is always read only and results from your choice of <code>mfilt</code> object.
Numerator		Vector containing the coefficients of the FIR lowpass filter used for interpolation.

# **mfilt.firfracinterp (Obsolete)**

<b>Name</b>	<b>Values</b>	<b>Description</b>
RateChangeFactors	[1,m]	Reports the decimation (m) and interpolation (l) factors for the filter object. Combining these factors results in the final rate change for the signal.
PersistentMemory	false or true	Determines whether the filter states are restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter if you have not changed the filter since you constructed it. PersistentMemory returns to the default values any state that the filter changes during processing. States that the filter does not change are not affected.
States	Matrix	Stored conditions for the filter, including values for the interpolator and comb states.

## **Examples**


To convert a signal from 32 kHz to 48 kHz requires fractional interpolation. This example uses the `mfilt.firfracinterp` object to upsample an input signal. Setting `l = 3` and `m = 2` returns the same `mfilt` object as the default `mfilt.firfracinterp` object.

```
l = 3; m = 2; % Interpolation/decimation factors.
hm = mfilt.firfracinterp(l,m); % We use the default filter
fs = 32e3; % Original sample freq: 32 kHz.
n = 0:6799; % 6800 samples, 0.212 second long signal
x = sin(2*pi*1e3/fs*n); % Original signal, sinusoid at 1 kHz
```

```
y = filter(hm,x);           % 10200 samples, still 0.212 seconds
stem(n(1:32)/fs,x(1:32),'filled') % Plot original sampled at
                                % 32 kHz

hold on;
% Plot fractionally interpolated signal (48 kHz) in red
stem(n(1:48)/(fs*l/m),y(20:67),'r')
xlabel('Time (sec)');ylabel('Signal Value')
```

The ability to interpolate by fractional amounts lets you raise the sampling rate from 32 to 48 kHz, something you cannot do with integral interpolators. Both signals appear in the following figure.



## See Also

[mfilt.firsrc](#) | [mfilt.firinterp](#) | [mfilt.firdecim](#)

# mfilt.firinterp

---

**Purpose** FIR filter-based interpolator

**Syntax**  
`Hm = mfilt.firinterp(L)`  
`Hm = mfilt.firinterp(L,num)`

**Description** `Hm = mfilt.firinterp(L)` returns a FIR polyphase interpolator object `Hm` with an interpolation factor of `L` and gain equal to `L`. `L` defaults to 2 if unspecified.

`Hm = mfilt.firinterp(L,num)` uses the values in the vector `num` as the coefficients of the interpolation filter.

Make this filter a fixed-point or single-precision filter by changing the value of the `Arithmetic` property for the filter `Hm` as follows:

- To change to single-precision filtering, enter

```
set(hm,'arithmetic','single');
```

- To change to fixed-point filtering, enter

```
set(hm,'arithmetic','fixed');
```

## Input Arguments

The following table describes the input arguments for creating `hm`.

Input Argument	Description
1	Interpolation factor for the filter. 1 specifies the amount to increase the input sampling rate. It must be an integer. When you do not specify a value for 1 it defaults to 2.
num	Vector containing the coefficients of the FIR lowpass filter used for interpolation. When <code>num</code> is not provided as an input, <code>firinterp</code> uses a lowpass Nyquist filter with gain equal to 1 and cutoff frequency equal to $\pi/1$ by default. The default length for the Nyquist filter is $24 \times 1$ . Therefore, each polyphase filter component has length 24.

**Object Properties**

This section describes the properties for both floating-point filters (double-precision and single-precision) and fixed-point filters.

**Floating-Point Filter Properties**

Every multirate filter object has properties that govern the way it behaves when you use it. Note that many of the properties are also input arguments for creating `mfilt.firinterp` objects. The next table describes each property for an `mfilt.firinterp` filter object.

<b>Name</b>	<b>Values</b>	<b>Description</b>
Arithmetic	Double, single, fixed	Defines the arithmetic the filter uses. Gives you the options <code>double</code> , <code>single</code> , and <code>fixed</code> . In short, this property defines the operation mode for your filter.
FilterStructure	String	Reports the type of filter object. You cannot set this property — it is always read only and results from your choice of <code>mfilt</code> object. Describes the signal flow for the filter object.
InterpolationFactor	Integer	Interpolation factor for the filter. 1 specifies the amount to increase the sampling rate of the input signal. It must be an integer.
Numerator	Vector	Vector containing the coefficients of the FIR lowpass filter used for decimation.

# mfilt.firinterp

---

Name	Values	Description
PersistentMemory	[false], true	Determines whether the filter states get restored to zeros for each filtering operation. The starting values are the values in place when you create the filter if you have not changed the filter since you constructed it. <code>PersistentMemory</code> set to <code>false</code> returns filter states to the default values after filtering. States that the filter does not change are not affected. Setting this to <code>true</code> allows you to modify the <code>States</code> property.
States	Double, single, matching the filter arithmetic setting.	Contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions.

## Fixed-Point Filter Properties

This table shows the properties associated with the fixed-point implementation of the `mfilt.firinterp` filter.

---

**Note** The table lists all of the properties that a fixed-point filter can have. Many of the properties listed are dynamic, meaning they exist only in response to the settings of other properties. To view all of the characteristics for a filter at any time, use

`info(hm)`

where `hm` is a filter.

---

For further information about the properties of this filter or any `mfilt` object, refer to “Multirate Filter Properties” on page 8-115.

<b>Name</b>	<b>Values</b>	<b>Description</b>
AccumFracLength	Any positive or negative integer number of bits. [32]	Specifies the fraction length used to interpret data output by the accumulator. This is a property of FIR filters and lattice filters. IIR filters have two similar properties — DenAccumFracLength and NumAccumFracLength — that let you set the precision for numerator and denominator operations separately.
AccumWordLength	Any integer number of bits[39]	Sets the word length used to store data in the accumulator.
Arithmetic	fixed for fixed-point filters	Setting this to fixed allows you to modify other filter properties to customize your fixed-point filter.
CoeffAutoScale	[true], false	Specifies whether the filter automatically chooses the proper fraction length to represent filter coefficients without overflowing. Turning this off by setting the value to false enables you to change the NumFracLength property value to specify the precision used.
CoeffWordLength	Any integer number of bits [16]	Specifies the word length to apply to filter coefficients.

## mfilt.firinterp

Name	Values	Description
FilterInternals	[FullPrecision], SpecifyPrecision	Controls whether the filter automatically sets the output word and fraction lengths, product word and fraction lengths, and the accumulator word and fraction lengths to maintain the best precision results during filtering. The default value, FullPrecision, sets automatic word and fraction length determination by the filter. SpecifyPrecision makes the output and accumulator-related properties available so you can set your own word and fraction lengths for them.
InputFracLength	Any positive or negative integer number of bits [15]	Specifies the fraction length the filter uses to interpret input data.
InputWordLength	Any integer number of bits [16]	Specifies the word length applied to interpret input data.
NumFracLength	Any positive or negative integer number of bits [14]	Sets the fraction length used to interpret the numerator coefficients.
OutputFracLength	Any positive or negative integer number of bits [32]	Determines how the filter interprets the filter output data. You can change the value of OutputFracLength when you set FilterInternals to SpecifyPrecision.
OutputWordLength	Any integer number of bits [39]	Determines the word length used for the output data. You make this property editable by setting FilterInternals to SpecifyPrecision.

Name	Values	Description
OverflowMode	saturate, [wrap]	<p>Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either <code>saturate</code> (limit the output to the largest positive or negative representable value) or <code>wrap</code> (set overflowing values to the nearest representable value using modular arithmetic.) The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow — they maintain full precision.</p>
RoundMode	[convergent], <code>ceil</code> , <code>fix</code> , <code>floor</code> , <code>nearest</code> , <code>round</code>	<p>Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths).</p> <ul style="list-style-type: none"> <li>• <code>ceil</code> - Round toward positive infinity.</li> <li>• <code>convergent</code> - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.</li> <li>• <code>fix</code> - Round toward zero.</li> <li>• <code>floor</code> - Round toward negative infinity.</li> <li>• <code>nearest</code> - Round toward nearest. Ties round toward positive infinity.</li> <li>• <code>round</code> - Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.</li> </ul>


# mfilt.firinterp

Name	Values	Description
		The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always round. Finally, products never overflow — they maintain full precision.
Signed	[true], false	Specifies whether the filter uses signed or unsigned fixed-point coefficients. Only coefficients reflect this property setting.
States	fi object to match the filter arithmetic setting.	Contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions. The states use fi objects, with the associated properties from those objects. For details, refer to fixed-point objects in Fixed-Point Toolbox documentation.

## Filter Structure

To provide interpolation, `mfilt.firinterp` uses the following structure.

The following figure details the signal flow for the direct form FIR filter implemented by `mfilt.firinterp`. In the figure, the delay line updates happen at the lower input rate. The remainder of the filter — the sums and coefficients — operate at the higher output rate.



## Examples

This example uses `mfilt.firinterp` to double the sample rate of a 22.05 kHz input signal. The output signal ends up at 44.1 kHz. Although `l` is set explicitly to 2, this represents the default interpolation value for `mfilt.firinterp` objects.

```
L = 2; % Interpolation factor.
Hm = mfilt.firinterp(L); % Use the default filter.
fs = 22.05e3; % Original sample freq: 22.05 kHz.
n = 0:5119; % 5120 samples, 0.232s long signal.
x = sin(2*pi*1e3/fs*n); % Original signal, sinusoid at 1 kHz.
y = filter(Hm,x); % 10240 samples, still 0.232s.
stem(n(1:22)/fs,x(1:22),'filled') % Plot original sampled at
% 22.05 kHz.


hold on;

% Plot interpolated signal (44.1 kHz) in red
stem(n(1:44)/(fs*L),y(25:68),'r')
xlabel('Time (sec)');ylabel('Signal Value')
```

# mfilt.firinterp

```
legend('Original Signal','Interpolated Signal');
```

With interpolation by 2, the resulting signal perfectly matches the original, but with twice as many samples — one between each original sample, as shown in the following figure.



## See Also

[mfilt.holdinterp](#) | [mfilt.linearinterp](#) | [mfilt.fftfirinterp](#) | [mfilt.firsrc](#) | [mfilt.cicinterp](#)

**Purpose**

Direct-form FIR polyphase sample rate converter

**Syntax**

```
hm = mfilt.firsrc(l,m,num)
```

**Description**

`hm = mfilt.firsrc(l,m,num)` returns a direct-form FIR polyphase sample rate converter. `l` specifies the interpolation factor. It must be an integer and when omitted in the calling syntax, it defaults to 2.

`m` is the decimation factor. It must be an integer. If not specified, `m` defaults to 1. If `l` is also not specified, `m` defaults to 3 and the overall rate change factor is  $2/3$ .

You specify the coefficients of the FIR lowpass filter used for sample rate conversion in `num`. If omitted, a lowpass Nyquist filter with gain 1 and cutoff frequency of  $\pi/\max(l,m)$  is the default.

Combining an interpolation factor and a decimation factor lets you use `mfilt.firsrc` to perform fractional interpolation or decimation on an input signal. Using an `mfilt.firsrc` object applies a rate change factor defined by  $l/m$  to the input signal. For proper rate changing to occur, `l` and `m` must be relatively prime — meaning the ratio  $l/m$  cannot be reduced to a ratio of smaller integers.

When you are doing sample-rate conversion with large values of `l` or `m`, such as `l` or `m` greater than 20, using the `mfilt.firsrc` structure is the most effective approach.

Make this filter a fixed-point or single-precision filter by changing the value of the `Arithmetic` property for the filter `hm` as follows:

- To change to single-precision filtering, enter

```
set(hm,'arithmetic','single');
```

- To change to fixed-point filtering, enter

```
set(hm,'arithmetic','fixed');
```

---

**Note** You can use the `realizemdl` method to create a Simulink block of a filter created using `mfilt.firsrc`.

---

## Input Arguments

The following table describes the input arguments for creating `hm`.

Input Argument	Description
1	Interpolation factor for the filter. 1 specifies the amount to increase the input sampling rate. It must be an integer. When you do not specify a value for 1, it defaults to 2.
num	Vector containing the coefficients of the FIR lowpass filter used for interpolation. When num is not provided as an input, <code>mfilt.firsrc</code> uses a lowpass Nyquist filter with gain equal to 1 and cutoff frequency equal to $\pi/\max(1,m)$ by default. The default length for the Nyquist filter is $24*m$ . Therefore, each polyphase filter component has length 24.
m	Decimation factor for the filter. m specifies the amount to reduce the sampling rate of the input signal. It must be an integer. When you do not specify a value for m, it defaults to 1. When 1 is unspecified as well, m defaults to 3.

## Object Properties

This section describes the properties for both floating-point filters (double-precision and single-precision) and fixed-point filters.

### Floating-Point Filter Properties

Every multirate filter object has properties that govern the way it behaves when you use it. Note that many of the properties are also

input arguments for creating `mfilt.firsrc` objects. The next table describes each property for an `mfilt.firsrc` filter object.

<b>Name</b>	<b>Values</b>	<b>Description</b>
Arithmetic	[Double], single, fixed	Defines the arithmetic the filter uses. Gives you the options <code>double</code> , <code>single</code> , and <code>fixed</code> . In short, this property defines the operation mode for your filter.
FilterStructure	String	Reports the type of filter object. You cannot set this property — it is always read only and results from your choice of <code>mfilt</code> object. Describes the signal flow for the filter object.
InputOffset	Integers	Contains a value derived from the number of input samples and the decimation factor — $\text{InputOffset} = \text{mod}(\text{length}(nx), m)$ where $nx$ is the number of input samples and $m$ is the decimation factor.
Numerator	Vector	Vector containing the coefficients of the FIR lowpass filter used for decimation.
PersistentMemory	false, true	Determines whether the filter states get restored to zeros for each filtering operation. The starting values are the values in place when you create the filter if you have not changed the filter since you constructed it. <code>PersistentMemory</code> set to <code>false</code> returns filter states to the default values after filtering. States that the filter does not change are not affected. Setting this to <code>true</code> allows you to modify the <code>States</code> , <code>InputOffset</code> , and <code>PolyphaseAccum</code> properties.

Name	Values	Description
RateChangeFactors	Positive integers. [2 3]	Specifies the interpolation and decimation factors [1 m] (the rate change factors ) for changing the input sample rate by nonintegral amounts.
States	Double, single, matching the filter arithmetic setting.	Contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions.

## Fixed-Point Filter Properties

This table shows the properties associated with the fixed-point implementation of the `mfilt.firsrc` filter.

---

**Note** The table lists all of the properties that a fixed-point filter can have. Many of the properties listed are dynamic, meaning they exist only in response to the settings of other properties. To view all of the characteristics for a filter at any time, use

`info(hm)`

where `hm` is a filter.

---

For further information about the properties of this filter or any `mfilt` object, refer to “Multirate Filter Properties” on page 8-115.

Name	Values	Description
AccumFracLength	Any positive or negative integer number of bits. [32]	Specifies the fraction length used to interpret data output by the accumulator. This is a property of FIR filters.
AccumWordLength	Any integer number of bits [39]	Sets the word length used to store data in the accumulator.

Name	Values	Description
Arithmetic	fixed for fixed-point filters	Setting this to <code>fixed</code> allows you to modify other filter properties to customize your fixed-point filter.
CoeffAutoScale	[true], false	Specifies whether the filter automatically chooses the proper fraction length to represent filter coefficients without overflowing. Turning this off by setting the value to <code>false</code> enables you to change the <code>NumFracLength</code> property value to specify the precision used.
CoeffWordLength	Any integer number of bits [16]	Specifies the word length to apply to filter coefficients.
FilterInternals	[FullPrecision], SpecifyPrecision	Controls whether the filter automatically sets the output word and fraction lengths, product word and fraction lengths, and the accumulator word and fraction lengths to maintain the best precision results during filtering. The default value, <code>FullPrecision</code> , sets automatic word and fraction length determination by the filter. <code>SpecifyPrecision</code> makes the output and accumulator-related properties available so you can set your own word and fraction lengths for them.
InputFracLength	Any positive or negative integer number of bits [15]	Specifies the fraction length the filter uses to interpret input data.
InputWordLength	Any integer number of bits [16]	Specifies the word length applied to interpret input data.

Name	Values	Description
NumFracLength	Any positive or negative integer number of bits [14]	Sets the fraction length used to interpret the numerator coefficients.
OutputFracLength	Any positive or negative integer number of bits [32]	Determines how the filter interprets the filter output data. You can change the value of OutputFracLength when you set FilterInternals to SpecifyPrecision.
OutputWordLength	Any integer number of bits [39]	Determines the word length used for the output data. You make this property editable by setting FilterInternals to SpecifyPrecision.
OverflowMode	saturate, [wrap]	Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either saturate (limit the output to the largest positive or negative representable value) or wrap (set overflowing values to the nearest representable value using modular arithmetic.) The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow — they maintain full precision.
RateChangeFactors	Positive integers [2 3]	Specifies the interpolation and decimation factors [1 m] (the rate change factors) for changing the input sample rate by nonintegral amounts.

Name	Values	Description
RoundMode	[convergent], ceil, fix, floor, nearest, round	<p>Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths).</p> <ul style="list-style-type: none"><li>• <code>ceil</code> - Round toward positive infinity.</li><li>• <code>convergent</code> - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.</li><li>• <code>fix</code> - Round toward zero.</li><li>• <code>floor</code> - Round toward negative infinity.</li><li>• <code>nearest</code> - Round toward nearest. Ties round toward positive infinity.</li><li>• <code>round</code> - Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.</li></ul> <p>The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always round. Finally, products never overflow — they maintain full precision.</p>

Name	Values	Description
Signed	[true], false	Specifies whether the filter uses signed or unsigned fixed-point coefficients. Only coefficients reflect this property setting.
States	fi object	Contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions. The states use fi objects, with the associated properties from those objects. For details, refer to fixed-point objects in Fixed-Point Toolbox documentation. For information about the ordering of the states, refer to the filter structure section.

## Examples

This is an example of a common audio rate change process — changing the sample rate of a high end audio (48 kHz) signal to the compact disc sample rate (44.1 kHz). This conversion requires a rate change factor of 0.91875, or  $l = 147$  and  $m = 160$ .

```


l = 147; m = 160;           % Interpolation/decimation factors.
hm = mfilt.firsrc(l,m);    % Use the default FIR filter.
fs = 48e3;                 % Original sample freq: 48 kHz.
n = 0:10239;               % 10240 samples, 0.213 seconds long.
x = sin(2*pi*1e3/fs*n);    % Original signal, sinusoid at 1 kHz.
y = filter(hm,x);          % 9408 samples, still 0.213 seconds.
stem(n(1:49)/fs,x(1:49))   % Plot original sampled at 48 kHz.
hold on

% Plot fractionally decimated signal (44.1 kHz) in red
stem(n(1:45)/(fs*l/m),y(13:57),'r','filled')
xlabel('Time (sec)');ylabel('Signal Value')

```

Fractional decimation provides you the flexibility to pick and choose the sample rates you want by carefully selecting  $l$  and  $m$ , the interpolation and decimation factors, that result in the final fractional decimation.

The following figure shows the signal after applying the rate change filter `hm` to the original signal.



## See Also

`mfilt.firsrc` | `mfilt.firinterp` | `mfilt.firdecim`

# mfilt.firtdecim

---

**Purpose** Direct-form transposed FIR filter

**Syntax**  
`hm = mfilt.firtdecim(m)`  
`hm = mfilt.firtdecim(m,num)`

**Description** `hm = mfilt.firtdecim(m)` returns a polyphase decimator `mfilt` object `hm` based on a direct-form transposed FIR structure with a decimation factor of  $m$ . A lowpass Nyquist filter of gain 1 and cutoff frequency of  $\pi/m$  is the default.

`hm = mfilt.firtdecim(m,num)` uses the coefficients specified by `num` for the decimation filter. `num` is a vector containing the coefficients of the transposed FIR lowpass filter used for decimation. If omitted, a lowpass Nyquist filter with gain of 1 and cutoff frequency of  $\pi/m$  is the default.

Make this filter a fixed-point or single-precision filter by changing the value of the Arithmetic property for the filter `hm` as follows:

- To change to single-precision filtering, enter

```
set(hm,'arithmetic','single');
```

- To change to fixed-point filtering, enter

```
set(hm,'arithmetic','fixed');
```

## Input Arguments

The following table describes the input arguments for creating `hm`.

<b>Input Argument</b>	<b>Description</b>
num	Vector containing the coefficients of the FIR lowpass filter used for interpolation. When num is not provided as an input, <code>firtdecim</code> uses a lowpass Nyquist filter with gain equal to 1 and cutoff frequency equal to $\pi/m$ by default. The default length for the Nyquist filter is $24*m$ . Therefore, each polyphase filter component has length 24.
m	Decimation factor for the filter. <code>m</code> specifies the amount to reduce the sampling rate of the input signal. It must be an integer. When you do not specify a value for <code>m</code> it defaults to 2.

## **Object Properties**

This section describes the properties for both floating-point filters (double-precision and single-precision) and fixed-point filters.

### **Floating-Point Filter Properties**

Every multirate filter object has properties that govern the way it behaves when you use it. Note that many of the properties are also input arguments for creating `mfilt.firtdecim` objects. The next table describes each property for an `mfilt.firtdecim` filter object.

<b>Name</b>	<b>Values</b>	<b>Description</b>
Arithmetic	Double, single, fixed	Specifies the arithmetic the filter uses to process data while filtering.
DecimationFactor	Integer	Decimation factor for the filter. <code>m</code> specifies the amount to reduce the sampling rate of the input signal. It must be an integer.

## mfilt.firtdecim

---

Name	Values	Description
FilterStructure	String	Reports the type of filter object. You cannot set this property — it is always read only and results from your choice of <code>mfilt</code> object. Also describes the signal flow for the filter object.
InputOffset	Integers	Contains a value derived from the number of input samples and the decimation factor — $\text{InputOffset} = \text{mod}(\text{length}(nx), m)$ where $nx$ is the number of input samples that have been processed so far and $m$ is the decimation factor.
Numerator	Vector	Vector containing the coefficients of the FIR lowpass filter used for decimation.
PersistentMemory	[false], true	Determines whether the filter states get restored to zeros for each filtering operation. The starting values are the values in place when you create the filter if you have not changed the filter since you constructed it. <code>PersistentMemory</code> set to <code>false</code> returns filter states to the default values after filtering. States that the filter does not change are not affected. Setting this to <code>true</code> allows you to modify the <code>States</code> , <code>InputOffset</code> , and <code>PolyphaseAccum</code> properties.

Name	Values	Description
PolyphaseAccum	Double, single [0]	The idea behind having both PolyphaseAccum and Accum is to differentiate between the adders in the filter that work in full precision at all times (PolyphaseAccum) from the adders in the filter that the user controls and that may introduce quantization effects when FilterInternals is set to SpecifyPrecision.
States	Double, single matching the filter arithmetic setting.	Contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions.

### Fixed-Point Filter Properties

This table shows the properties associated with the fixed-point implementation of the `mfilt.firtdecim` filter.

---

**Note** The table lists all of the properties that a fixed-point filter can have. Many of the properties listed are dynamic, meaning they exist only in response to the settings of other properties. To view all of the characteristics for a filter at any time, use

`info(hm)`

where `hm` is a filter.

---

For further information about the properties of this filter or any `mfilt` object, refer to “Multirate Filter Properties” on page 8-115.

## mfilt.firtdecim

---

Name	Values	Description
AccumFracLength	Any positive or negative integer number of bits. [32]	Specifies the fraction length used to interpret data output by the accumulator. This is a property of FIR filters and lattice filters. IIR filters have two similar properties — DenAccumFracLength and NumAccumFracLength — that let you set the precision for numerator and denominator operations separately.
AccumWordLength	Any integer number of bits [39]	Sets the word length used to store data in the accumulator.
Arithmetic	fixed for fixed-point filters	Setting this to fixed allows you to modify other filter properties to customize your fixed-point filter.
CoeffAutoScale	[true], false	Specifies whether the filter automatically chooses the proper fraction length to represent filter coefficients without overflowing. Turning this off by setting the value to false enables you to change the NumFracLength property value to specify the precision used.
CoeffWordLength	Any integer number of bits [16]	Specifies the word length to apply to filter coefficients.

<b>Name</b>	<b>Values</b>	<b>Description</b>
FilterInternals	[FullPrecision], SpecifyPrecision	Controls whether the filter automatically sets the output word and fraction lengths, product word and fraction lengths, and the accumulator word and fraction lengths to maintain the best precision results during filtering. The default value, FullPrecision, sets automatic word and fraction length determination by the filter. SpecifyPrecision makes the output and accumulator-related properties available so you can set your own word and fraction lengths for them.
InputFracLength	Any positive or negative integer number of bits [15]	Specifies the fraction length the filter uses to interpret input data.
InputWordLength	Any integer number of bits [16]	Specifies the word length applied to interpret input data.
NumFracLength	Any positive or negative integer number of bits [14]	Sets the fraction length used to interpret the numerator coefficients.
OutputFracLength	Any positive or negative integer number of bits [32]	Determines how the filter interprets the filter output data. You can change the value of OutputFracLength when you set FilterInternals to SpecifyPrecision.
OutputWordLength	Any integer number of bits [39]	Determines the word length used for the output data. You make this property editable by setting FilterInternals to SpecifyPrecision.

# mfilt.firtdecim

Name	Values	Description
OverflowMode	saturate, [wrap]	Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either <code>saturate</code> (limit the output to the largest positive or negative representable value) or <code>wrap</code> (set overflowing values to the nearest representable value using modular arithmetic.) The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow — they maintain full precision.
PolyphaseAccum	fi object with zeros to start	Differentiates between the adders in the filter that work in full precision at all times ( <code>PolyphaseAccum</code> ) and the adders in the filter that the user controls and that may introduce quantization effects when <code>FilterInternals</code> is set to <code>SpecifyPrecision</code> .
RoundMode	[convergent], ceil, fix, floor, nearest, round	Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths). <ul style="list-style-type: none"><li>• <code>ceil</code> - Round toward positive infinity.</li><li>• <code>convergent</code> - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.</li><li>• <code>fix</code> - Round toward zero.</li><li>• <code>floor</code> - Round toward negative infinity.</li><li>• <code>nearest</code> - Round toward nearest. Ties round toward positive infinity.</li></ul>


Name	Values	Description
		<ul style="list-style-type: none"> <li>• round - Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.</li> </ul> <p>The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always round. Finally, products never overflow — they maintain full precision.</p>
Signed	[true], false	Specifies whether the filter uses signed or unsigned fixed-point coefficients. Only coefficients reflect this property setting.
States	fi object	Contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions. The states use fi objects, with the associated properties from those objects. For details, refer to fixed-point objects in Fixed-Point Toolbox documentation. For information about the ordering of the states, refer to the filter structure section.

**Filter Structure**

To provide sample rate changes, `mfilt.firtdecim` uses the following structure. At the input you see a commutator that operates counterclockwise, moving from position 0 to position 2, position 1, and back to position 0 as input samples enter the filter. To keep track of the position of the commutator, the `mfilt` object uses the property `InputOffset` which reports the current position of the commutator in the filter.

The following figure details the signal flow for the direct form FIR filter implemented by `mfilt.firtdecim`.

# mfilt.firtdecim



Notice the order of the states in the filter flow diagram. States 1 through 3 appear in the following diagram at each delay element. State 1 applies to the third delay element in phase 2. State 2 applies to the second delay element in phase 2. State 3 applies to the first delay element in phase 2. When you provide the states for the filter as a vector to the `States` property, the above description explains how the filter assigns the states you specify.

In property value form, the states for a filter `hm` are


```
hm.states=[1:3];
```

## Examples

Demonstrate decimating an input signal by a factor of 2, in this case converting from 44.1 kHz down to 22.05 kHz. In the figure shown following the code, you see the results of decimating the signal.

```
m = 2; % Decimation factor.
hm = mfilt.firtdecim(m); % Use the default filter coeffs.
fs = 44.1e3; % Original sample freq: 44.1 kHz.
n = 0:10239; % 10240 samples, 0.232 second long signal
x = sin(2*pi*1e3/fs*n); % Original signal--sinusoid at 1 kHz.
y = filter(hm,x); % 5120 samples, 0.232 seconds.
```

```
stem(n(1:44)/fs,x(1:44)) % Plot original sampled at 44.1 kHz.  
axis([0 0.001 -1.2 1.2]);  
hold on % Plot decimated signal (22.05 kHz) in red  
stem(n(1:22)/(fs/m),y(13:34),'r','filled')  
xlabel('Time (sec)');ylabel('Signal Value');  
legend('Original signal','Decimated signal','location','best');
```



## See Also

[mfilt.firdecim](#) | [mfilt.firsrc](#) | [mfilt.cicdecim](#)

# mfilt.holdinterp

---

**Purpose** FIR hold interpolator

**Syntax** `hm = mfilt.holdinterp(1)`

**Description** `hm = mfilt.holdinterp(1)` returns the object `hm` that represents a hold interpolator with the interpolation factor `1`. To work, `1` must be an integer. When you do not include `1` in the calling syntax, it defaults to `2`. To perform interpolation by noninteger amounts, use one of the fractional interpolator objects, such as `mfilt.firsrc`.

When you use this hold interpolator, each sample added to the input signal between existing samples has the value of the most recent sample from the original signal. Thus you see something like a staircase profile where the interpolated samples form a plateau between the previous and next original samples. The example demonstrates this profile clearly. Compare this to the interpolation process for other interpolators in the toolbox, such as `mfilt.linearinterp`.

Make this filter a fixed-point or single-precision filter by changing the value of the `Arithmetic` property for the filter `hm` as follows:

- To change to single-precision filtering, enter

```
set(hm,'arithmetic','single');
```

- To change to fixed-point filtering, enter

```
set(hm,'arithmetic','fixed');
```

## Input Arguments

The following table describes the input arguments for creating `hm`.

Input Argument	Description
1	Interpolation factor for the filter. 1 specifies the amount to increase the input sampling rate. It must be an integer. When you do not specify a value for 1 it defaults to 2.

## Object Properties

This section describes the properties for both floating-point filters (double-precision and single-precision) and fixed-point filters.

### Floating-Point Filter Properties

Every multirate filter object has properties that govern the way it behaves when you use it. Note that many of the properties are also input arguments for creating `mfilt.holdinterp` objects. The next table describes each property for an `mfilt.interp` filter object.

Name	Values	Description
Arithmetic	Double, single, fixed	Specifies the arithmetic the filter uses to process data while filtering.
FilterStructure	String	Reports the type of filter object. You cannot set this property — it is always read only and results from your choice of <code>mfilt</code> object.
Interpolation-Factor	Integer	Interpolation factor for the filter. 1 specifies the amount to increase the input sampling rate. It must be an integer.

# mfilt.holdinterp

---

Name	Values	Description
PersistentMemory	'false' or 'true'	Determines whether the filter states are restored to zero for each filtering operation.
States	Double or single array	Filter states. <code>states</code> defaults to a vector of zeros that has length equal to <code>nstates</code> ( <code>hm</code> ). Always available, but visible in the display only when <code>PersistentMemory</code> is true.

## Fixed-Point Filter Properties

This table shows the properties associated with the fixed-point implementation of the `mfilt.holdinterp` filter.

---

**Note** The table lists all of the properties that a fixed-point filter can have. Many of the properties listed are dynamic, meaning they exist only in response to the settings of other properties. To view all of the characteristics for a filter at any time, use

`info(hm)`

where `hm` is a filter.

---

For further information about the properties of this filter or any `mfilt` object, refer to “Multirate Filter Properties” on page 8-115.

Name	Values	Description
Arithmetic	Double, single, fixed	Specifies the arithmetic the filter uses to process data while filtering.
FilterStructure	String	Reports the type of filter object. You cannot set this property — it is always read only and results from your choice of <code>mfilt</code> object.
InputFracLength	Any positive or negative integer number of bits [15]	Specifies the fraction length the filter uses to interpret input data.
InputWordLength	Any integer number of bits [16]	Specifies the word length applied to interpret input data.
Interpolation-Factor	Integer	Interpolation factor for the filter. 1 specifies the amount to increase the input sampling rate. It must be an integer.
PersistentMemory	'false' or 'true'	Determine whether the filter states get restored to zero for each filtering operation
States	fi object	Contains the filter states before, during, and after filter operations. For hold interpolators, the states are always empty — hold interpolators do not have states. The states use <code>fi</code> objects, with the

# mfilt.holdinterp

Name	Values	Description
		associated properties from those objects. For details, refer to fixed-point objects in Fixed-Point Toolbox documentation.

## Filter Structure


Hold interpolators do not have filter coefficients and their filter structure is trivial.

## Examples

To see the effects of hold-based interpolation, interpolate an input sine wave from 22.05 to 44.1 kHz. Note that each added sample retains the value of the most recent original sample.

```
l = 2; % Interpolation factor
hm = mfilt.holdinterp(l);
fs = 22.05e3; % Original sample freq: 22.05 kHz.
n = 0:5119; % 5120 samples, 0.232 second long signal
x = sin(2*pi*1e3/fs*n); % Original signal, sinusoid at 1 kHz
y = filter(hm,x); % 10240 samples, still 0.232 seconds
stem(n(1:22)/fs,x(1:22),'filled') % Plot original sampled at
% 22.05 kHz
hold on % Plot interpolated signal (44.1 kHz)
stem(n(1:44)/(fs*l),y(1:44),'r')
legend('Original Signal','Interpolated Signal','Location','best');
xlabel('Time (sec)');ylabel('Signal Value')
```

The following figure shows clearly the step nature of the signal that comes from interpolating the signal using the hold algorithm approach. Compare the output to the linear interpolation used in `mfilt.linearinterp`.



## See Also

`mfilt.linearinterp` | `mfilt.firinterp` | `mfilt.firsrc` |  
`mfilt.cicinterp`

# mfilt.iirdecim

---

**Purpose** IIR decimator

**Syntax** `hm = mfilt.iirdecim(c1,c2,...)`

**Description** `hm = mfilt.iirdecim(c1,c2,...)` constructs an IIR decimator filter given the coefficients specified in the cell arrays `c1`, `c2`, and so on. The resulting IIR decimator is a polyphase IIR filter where each phase is a cascade allpass IIR filter.

Each cell array `ci` contains a set of vectors representing a cascade of allpass sections. Each element in one cell array is one section. For more information about the contents of each cell array, refer to `dfilt.cascadeallpass`. The contents of the cell arrays are the same for both filter constructors and `mfilt.iirdecim` interprets them same way as `mfilt.cascadeallpass`.

The following exception applies to interpreting the contents of a cell array — if one of the cell arrays `ci` contains only one vector, and that vector comprises a series of 0s and one element equal to 1, that cell array represents a `dfilt.delay` section with latency equal to the number of zeros, rather than a `dfilt.cascadeallpass` section. This exception case occurs with quasi-linear phase IIR decimators.

Although the first example shows how to construct an IIR decimators explicitly, one usually constructs an IIR decimators filter as a result of designing an decimators, as shown in the subsequent examples.

## Examples

When the coefficients are known, you can construct the IIR decimator directly using `mfilt.iirdecim`. For example, if the filter's coefficients are `[0.6 0.5]` for the first phase in the first stage, `0.7` for the second phase in the first stage and `0.8` for the third phase in the first stage; as well as `0.5` for the first phase in the second stage and `0.4` for the second phase in the second stage, construct the filter as shown here.

```
Hm = mfilt.iirdecim({[0.6 0.5] 0.7 0.8},{0.5 0.4})
```

Also refer to the “Quasi-Linear Phase Halfband and Dyadic Halfband Designs” section of the “IIR Polyphase Filter Design” example, `iirallpassdemo` example.

When the coefficients are not known, use the approach given by the following set of examples. Start by designing an elliptic halfband decimator with a decimation factor of 2. The example specifies the optional sampling frequency argument.

```
tw = 100; % Transition width of filter.
ast = 80; % Stopband attenuation of filter.
fs = 2000; % Sampling frequency of signal to filter.
m = 2; % Decimation factor.
hm = fdesign.decimator(m,'halfband','tw,ast',tw,ast,fs);
```

`hm` contains the specifications for a decimator defined by `tw`, `ast`, `m`, and `fs`.

Use the specification object `hm` to design a `mfilt.iirdecim` filter object.

```
d = design(hm,'ellip','filterstructure','iirdecim');
% Note that realizemdl requires Simulink
realizemdl(d) % Build model of the filter.
```

Designing a linear phase decimator is similar to the previous example. In this case, design a halfband linear phase decimator with decimation factor of 2.

```
tw = 100; % Transition width of filter.
ast = 60; % Stopband attenuation of filter.
fs = 2000; % Sampling frequency of signal to filter.
m = 2; % Decimation factor.
```

Create a specification object for the decimator.

```
hm = fdesign.decimator(m,'halfband','tw,ast',tw,ast,fs);
```

Finally, design the filter `d`.

```
d = design(hm,'iirlinphase','filterstructure','iirdecim');
```

# mfilt.iirdecim


---

```
% Note that realizemdl requires Simulink
realizemdl(d) % Build model of the filter.
```


The filter implementation appears in this model, generated by realizemdl and Simulink.

Given the design specifications shown here

the first phase is a delay section with 0s and a 1 for coefficients and the second phase is a linear phase decimator, shown in the next models.




**Phase 1 model**



**Phase 2 model**

# mfilt.iirdecim



## Overall model

For more information about Multirate Filter Constructors see the “Getting Started with Multirate Filter (MFILT) Objects” example, `mfiltgettingstarteddemo`.

## See Also

`dfilt.cascadeallpass` | `mfilt` | `mfilt.iirinterp` | `mfilt.iirwdfdecim`

**Purpose** IIR interpolator

**Syntax** `hm = mfilt.iirinterp(c1,c2,...)`

**Description** `hm = mfilt.iirinterp(c1,c2,...)` constructs an IIR interpolator filter given the coefficients specified in the cell arrays C1, C2, etc.

The IIR interpolator is a polyphase IIR filter where each phase is a cascade allpass IIR filter.

Each cell array `ci` contains a set of vectors representing a cascade of allpass sections. Each element in one cell array is one section. For more information about the contents of each cell array, refer to `dfilt.cascadeallpass`. The contents of the cell arrays are the same for both filter constructors and `mfilt.iirdecim` interprets them same way as `mfilt.cascadeallpass`.

The following exception applies to interpreting the contents of a cell array—if one of the cell arrays `ci` contains only one vector, and that vector comprises a series of 0s and a unique element equal to 1, that cell array represents a `dfilt.delay` section with latency equal to the number of zeros, rather than a `dfilt.cascadeallpass` section. This exception case occurs with quasi-linear phase IIR interpolators.

Although the first example shows how to construct an IIR interpolator explicitly, one usually constructs an IIR interpolator filter as a result of designing an interpolator, as shown in the subsequent examples.

**Examples** When the coefficients are known, you can construct the IIR interpolator directly using `mfilt.iirinterp`. In the following example, a cascaded polyphase IIR interpolator filter is constructed using 2 phases for each of three stages. The coefficients are given below:

```
Phase1Sect1=0.0603;Phase1Sect2=0.4126; Phase1Sect3=0.7727;
Phase2Sect1=0.2160; Phase2Sect2=0.6044; Phase2Sect3=0.9239;
```

Next the filter is implemented by passing the above coefficients to `mfilt.iirinterp` as cell arrays, where each cell array represents a different phase.

```
Hm = mfilt.iirinterp({Phase1Sect1,Phase1Sect2,Phase1Sect3},...  
{Phase2Sect1,Phase2Sect2,Phase2Sect3})
```

```
Hm =
```

```
FilterStructure: 'IIR Polyphase Interpolator'  
Polyphase: Phase1: Section1: 0.0603  
                Section2: 0.4126  
                Section3: 0.7727  
Phase2: Section1: 0.216  
                Section2: 0.6044  
                Section3: 0.9239  
InterpolationFactor: 2  
PersistentMemory: false
```

Also refer to the “Quasi-Linear Phase Halfband and Dyadic Halfband Designs” section of the “IIR Polyphase Filter Design” example, `iirallpassdemo` example.

When the coefficients are not known, use the approach given by the following set of examples. Start by designing an elliptic halfband interpolator with a interpolation factor of 2.

```
tw = 100; % Transition width of filter.  
ast = 80; % Stopband attenuation of filter.  
fs = 2000; % Sampling frequency of filter.  
l = 2; % Interpolation factor.  
d = fdesign.interpolator(l,'halfband','tw,ast',tw,ast,fs);
```

Specification object `d` stores the interpolator design specifics. With the details in `d`, design the filter, returning `hm`, an `mfilt.iirinterp` object. Use `hm` to realize the filter if you have Simulink installed.

```
hm = design(d,'ellip','filterstructure','iirinterp');
```

```
% Note that realizemdl requires Simulink
realizemdl(hm) % Build model of the filter.
```

Designing a linear phase halfband interpolator follows the same pattern.


```
tw = 100; % Transition width of filter.
ast= 60; % Stopband attenuation of filter.
fs = 2000; % Sampling frequency of filter.
l = 2; % Interpolation factor.
d = fdesign.interpolator(l,'halfband','tw,ast',tw,ast,fs);
```

fdesign.interpolator returns a specification object that stores the design features for an interpolator.

Now perform the actual design that results in an mfilt.iirinterp filter, hm.

```
hm = design(d,'iirlinphase','filterstructure','iirinterp');
% Note that realizemdl requires Simulink
realizemdl(hm) % Build model of the filter.
```

The toolbox creates a Simulink model for hm, shown here. Phase1, Phase2, and InterpCommutator are all subsystem blocks.



## **mfilt.iirinterp**

---

For more information about Multirate Filter Constructors see the “Getting Started with Multirate Filter (MFILT) Objects” example, `mfiltgettingstarteddemo`.

### **See Also**

`dfilt.cascadeallpass` | `mfilt` | `mfilt.iirdecim` |  
`mfilt.iirwdfinterp`

## Purpose

IIR wave digital filter decimator

## Syntax

```
hm = mfilter.iirwdfdecim(c1,c2,...)
```

## Description

`hm = mfilter.iirwdfdecim(c1,c2,...)` constructs an IIR wave digital decimator given the coefficients specified in the cell arrays `c1`, `c2`, and so on. The IIR decimator `hm` is a polyphase IIR filter where each phase is a cascade wave digital allpass IIR filter.

Each cell array `ci` contains a set of vectors representing a cascade of allpass sections. Each element in one cell array is one section. For more information about the contents of each cell array, refer to `dfilter.cascadewdfallpass`. The contents of the cell arrays are the same for both filter constructors and `mfilter.iirwdfdecim` interprets them same way as `mfilter.cascadewdfallpass`.

The following exception applies to interpreting the contents of a cell array — if one of the cell arrays `ci` contains only one vector, and that vector comprises a series of 0s and one element equal to 1, that cell array represents a `dfilter.delay` section with latency equal to the number of zeros, rather than a `dfilter.cascadewdfallpass` section. This exception occurs with quasi-linear phase IIR decimators.

Usually you do not construct IIR wave digital filter decimators explicitly. Instead, you obtain an IIR wave digital filter decimator as a result of designing a halfband decimator. The first example in the following section illustrates this case.

## Examples

Design an elliptic halfband decimator with a decimation factor equal to 2. Both examples use the `iirwdfdecim` filter structure (an input argument to the `design` method) to design the final decimator.

The first portion of this example generates a filter specification object `d` that stores the specifications for the decimator.

```
tw = 100; % Transition width of filter to design, 100 Hz.  
ast = 80; % Stopband attenuation of filter 80 dB.  
fs = 2000; % Sampling frequency of the input signal.  
m = 2; % Decimation factor.
```

## **mfilt.iirwdfdecim**

---

```
d = fdesign.decimator(m, 'halfband', 'tw,ast',tw,ast,fs);
```

Now perform the actual design using d. Filter object hm is an `mfilt.iirwdfdecim` filter.

```
Hm = design(d, 'ellip', 'FilterStructure', 'iirwdfdecim');  
% Note that realizemdl requires Simulink  
realizemdl(hm)      % Build model of the filter.
```



Design a linear phase halfband decimator for decimating a signal by a factor of 2.

```
tw = 100; % Transition width of filter, 100 Hz.  
ast = 60; % Filter stopband attenuation = 80 dB  
fs = 2000; % Input signal sampling frequency.  
m = 2; % Decimation factor.  
d = fdesign.decimator(m, 'halfband', 'tw,ast',tw,ast,fs);
```

Use d to design the final filter hm, an `mfilt.iirwdfdecim` object.


```
hm = design(d, 'iirlinphase', 'filterstructure', ...  
 'iirwdfdecim');  
% Note that realizemdl requires Simulink  
realizemdl(hm)      % Build model of the filter.
```

The models that `realizemd1` returns for each example appear below. At this level, the realizations of the filters are identical. The differences appear in the subsystem blocks Phase1 and Phase2.




# mfilt.iirwdfdecim

This is the Phase1 subsystem from the halfband model.



Phase1 subsystem from the linear phase model is less revealing—an allpass filter.



## See Also

`dfilt.cascadewdfallpass` | `mfilt` | `mfilt.iirdecim` |  
`mfilt.iirwdfinterp`

# mfilt.iirwdfinterp

---

**Purpose** IIR wave digital filter interpolator

**Syntax** `hm = mfilt.iirwdfinterp(c1,c2,...)`

**Description** `hm = mfilt.iirwdfinterp(c1,c2,...)` constructs an IIR wave digital interpolator given the coefficients specified in the cell arrays `c1`, `c2`, and so on. The IIR interpolator `hm` is a polyphase IIR filter where each phase is a cascade wave digital allpass IIR filter.

Each cell array `ci` contains a set of vectors representing a cascade of allpass sections. Each element in one cell array is one section. For more information about the contents of each cell array, refer to `dfilt.cascadewdfallpass`. The contents of the cell arrays are the same for both filter constructors and `mfilt.iirwdfinterp` interprets them same way as `mfilt.cascadewdfallpass`.

The following exception applies to interpreting the contents of a cell array — if one of the cell arrays `ci` contains only one vector, and that vector comprises a series of 0s and one element equal to 1, that cell array represents a `dfilt.delay` section with latency equal to the number of zeros, rather than a `dfilt.cascadewdfallpass` section. This exception occurs with quasi-linear phase IIR interpolators.

Usually you do not construct IIR wave digital filter interpolators explicitly. Rather, you obtain an IIR wave digital interpolator as a result of designing a halfband interpolator. The first example in the following section illustrates this case.

## Examples

Design an elliptic halfband interpolator with interpolation factor equal to 2. At the end of the design process, `hm` is an IIR wave digital filter interpolator.

```
tw = 100; % Transition width of filter, 100 Hz.
ast = 80; % Stopband attenuation of filter, 80 dB.
fs = 2000; % Sampling frequency after interpolation.
l = 2; % Interpolation factor.
d = fdesign.interpolator(l,'halfband','tw,ast',tw,ast,fs);
```

The specification object `d` stores the interpolator design requirements. Now use `d` to design the actual filter `hm`.

```
hm = design(d,'ellip','filterstructure','iirwdfinterp');
```

If you have Simulink installed, you can realize your filter as a model built from DSP System Toolbox blocks.

```
% Note that realizemdl requires Simulink
realizemdl(hm) % Build model of the filter.
```

For variety, design a linear phase halfband interpolator with an interpolation factor of 2.

```
tw = 100; % Transition width of filter, 100 Hz.
ast = 80; % Stopband attenuation of filter, 80 dB.
fs = 2000; % Sampling frequency after interpolation.
l = 2; % Interpolation factor.
d = fdesign.interpolator(l,'halfband','tw,ast',tw,ast,fs);
```

Now perform the actual design process with `d`. Filter `hm` is an IIR wave digital filter interpolator. As in the previous example, `realizemdl` returns a Simulink model of the filter if you have Simulink installed.

```
hm = design(d,'iirlinphase','filterstructure',...
'iirwdfinterp');
% Note that realizemdl requires Simulink
realizemdl(hm) % Build model of the filter.
```

## See Also

[dfilt.cascadewdfallpass](#) | [mfilt.iirinterp](#) | [mfilt.iirwdfdecim](#)

# mfilt.linearinterp

---

**Purpose** Linear interpolator

**Syntax** `hm = mfilt.linearinterp(1)`

**Description** `hm = mfilt.linearinterp(1)` returns an FIR linear interpolator `hm` with an integer interpolation factor `1`. Provide `1` as a positive integer. The default value for the interpolation factor is `2` when you do not include the input argument `1`.

When you use this linear interpolator, the samples added to the input signal have values between the values of adjacent samples in the original signal. Thus you see something like a smooth profile where the interpolated samples continue a line between the previous and next original samples. The example demonstrates this smooth profile clearly. Compare this to the interpolation process for `mfilt.holdinterp`, which creates a stairstep profile.

Make this filter a fixed-point or single-precision filter by changing the value of the Arithmetic property for the filter `hm` as follows:

- To change to single-precision filtering, enter

```
set(hm,'arithmetic','single');
```

- To change to fixed-point filtering, enter

```
set(hm,'arithmetic','fixed');
```

## Input Arguments

The following table describes the input argument for `mfilt.linearinterp`.

Input Argument	Description
1	Interpolation factor for the filter. 1 specifies the amount to increase the input sampling rate. It must be an integer. When you do not specify a value for 1 it defaults to 2.

## Object Properties

This section describes the properties for both floating-point filters (double-precision and single-precision) and fixed-point filters.

### Floating-Point Filter Properties

Every multirate filter object has properties that govern the way it behaves when you use it. Note that many of the properties are also input arguments for creating `mfilt.linearinterp` objects. The next table describes each property for an `mfilt.linearinterp` filter object.

Name	Values	Description
Arithmetic	Double, single, fixed	Specifies the arithmetic the filter uses to process data while filtering.
FilterStructure	String	Reports the type of filter object. You cannot set this property — it is always read only and results from your choice of <code>mfilt</code> object.
InterpolationFactor	Integer	Interpolation factor for the filter. 1 specifies the amount to increase the input sampling rate. It must be an integer.
PersistentMemory	'false' or 'true'	Determine whether the filter states get restored to zero for each filtering operation
States	Double or single array	Filter states. <code>states</code> defaults to a vector of zeros that has length equal to <code>nstates(hm)</code> . Always available, but visible in the display only when <code>PersistentMemory</code> is true.

## Fixed-Point Filter Properties

This table shows the properties associated with the fixed-point implementation of the `mfilt.holdinterp` filter.

---

**Note** The table lists all of the properties that a fixed-point filter can have. Many of the properties listed are dynamic, meaning they exist only in response to the settings of other properties. To view all of the characteristics for a filter at any time, use

`info(hm)`

where `hm` is a filter.

---

For further information about the properties of this filter or any `mfilt` object, refer to “Multirate Filter Properties” on page 8-115.

Name	Values	Description
AccumFracLength	Any positive or negative integer number of bits. Depends on L. [29 when L=2]	Specifies the fraction length used to interpret data output by the accumulator.
AccumWordLength	Any integer number of bits [33]	Sets the word length used to store data in the accumulator.
Arithmetic	fixed for fixed-point filters	Setting this to <code>fixed</code> allows you to modify other filter properties to customize your fixed-point filter.

Name	Values	Description
CoeffAutoScale	[true], false	Specifies whether the filter automatically chooses the proper fraction length to represent filter coefficients without overflowing. Turning this off by setting the value to <code>false</code> enables you to change the <code>NumFracLength</code> property value to specify the precision used.
CoeffWordLength	Any integer number of bits [16]	Specifies the word length to apply to filter coefficients.
FilterInternals	[FullPrecision], SpecifyPrecision	Controls whether the filter automatically sets the output word and fraction lengths, product word and fraction lengths, and the accumulator word and fraction lengths to maintain the best precision results during filtering. The default value, <code>FullPrecision</code> , sets automatic word and fraction length determination by the filter. <code>SpecifyPrecision</code> makes the output and accumulator-related properties available so you can set your own word and fraction lengths for them.
InputFracLength	Any positive or negative integer number of bits [15]	Specifies the fraction length the filter uses to interpret input data.
InputWordLength	Any integer number of bits [16]	Specifies the word length applied to interpret input data.
NumFracLength	Any positive or negative integer number of bits [14]	Sets the fraction length used to interpret the numerator coefficients.

## mfilt.linearinterp

---

Name	Values	Description
OutputFracLength	Any positive or negative integer number of bits [29]	Determines how the filter interprets the filter output data. You can change the value of <code>OutputFracLength</code> when you set <code>FilterInternals</code> to <code>SpecifyPrecision</code> .
OutputWordLength	Any integer number of bits [33]	Determines the word length used for the output data. You make this property editable by setting <code>FilterInternals</code> to <code>SpecifyPrecision</code> .
OverflowMode	saturate, [wrap]	Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either <code>saturate</code> (limit the output to the largest positive or negative representable value) or <code>wrap</code> (set overflowing values to the nearest representable value using modular arithmetic.) The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow — they maintain full precision.

Name	Values	Description
RoundMode	[convergent], ceil, fix, floor, nearest, round	<p>Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths).</p> <ul style="list-style-type: none"> <li>• <b>ceil</b> - Round toward positive infinity.</li> <li>• <b>convergent</b> - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.</li> <li>• <b>fix</b> - Round toward zero.</li> <li>• <b>floor</b> - Round toward negative infinity.</li> <li>• <b>nearest</b> - Round toward nearest. Ties round toward positive infinity.</li> <li>• <b>round</b> - Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.</li> </ul> <p>The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always round. Finally, products never overflow — they maintain full precision.</p>


## mfilt.linearinterp

---

Name	Values	Description
Signed	[true], false	Specifies whether the filter uses signed or unsigned fixed-point coefficients. Only coefficients reflect this property setting.
States	fi object	Contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions. The states use fi objects, with the associated properties from those objects. For details, refer to fixed-point objects in Fixed-Point Toolbox documentation. For information about the ordering of the states, refer to the filter structure in the following section.

## Filter Structure

Linear interpolator structures depend on the FIR filter you use to implement the filter. By default, the structure is direct-form FIR.



## Examples

Interpolation by a factor of 2 (used to convert the input signal sampling rate from 22.05 kHz to 44.1 kHz).


```

l = 2; % Interpolation factor
hm = mfilt.linearinterp(l);
fs = 22.05e3; % Original sample freq: 22.05 kHz.
n = 0:5119; % 5120 samples, 0.232 second long signal
x = sin(2*pi*1e3/fs*n); % Original signal, sinusoid at 1 kHz
y = filter(hm,x); % 10240 samples, still 0.232 seconds
stem(n(1:22)/fs,x(1:22),'filled') % Plot original sampled at
% 22.05 kHz
hold on % Plot interpolated signal (44.1
% kHz) in red
    
```

# mfilt.linearinterp

```
stem(n(1:44)/(fs*1),y(2:45),'r')  
xlabel('Time (s)');ylabel('Signal Value')
```

Using linear interpolation, as compared to the hold approach of `mfilt.holdinterp`, provides greater fidelity to the original signal.



## See Also

`mfilt.holdinterp` | `mfilt.firinterp` | `mfilt.firsrc` |  
`mfilt.cicinterp`

## Purpose

Minimum wordlength fixed-point filter

## Syntax

```
Hq = minimizecoeffwl(Hd)
Hq = minimizecoeffwl(Hd,...,'NoiseShaping',NSFlag)
Hq = minimizecoeffwl(Hd,...,'NTrials',N)
Hq = minimizecoeffwl(Hd,...,'Apasstol',Apasstol)
Hq = minimizecoeffwl(Hd,...,'Astoptol',Astoptol)
Hq = minimizecoeffwl(Hd,...,'MatchrefFilter',RefFiltFlag)
```

## Description

`Hq = minimizecoeffwl(Hd)` returns the minimum wordlength fixed-point filter object `Hq` that meets the design specifications of the single-stage or multistage FIR filter object `Hd`. `Hd` must be generated using `fdesign` and `design`. If `Hd` is a multistage filter object, the procedure minimizes the wordlength for each stage separately. `minimizecoeffwl` uses a stochastic noise-shaping procedure by default to minimize the wordlength. To obtain repeatable results on successive function calls, initialize the uniform random number generator `rand`.

`Hq = minimizecoeffwl(Hd,...,'NoiseShaping',NSFlag)` enables or disables the stochastic noise-shaping procedure in the minimization of the wordlength. By default `NSFlag` is true. Setting `NSFlag` to false minimizes the wordlength without using noise-shaping.

`Hq = minimizecoeffwl(Hd,...,'NTrials',N)` specifies the number of Monte Carlo trials to use in the minimization. `Hq` is the filter with the minimum wordlength among the `N` trials that meets the specifications in `Hd`. `'NTrials'` defaults to one.

`Hq = minimizecoeffwl(Hd,...,'Apasstol',Apasstol)` specifies the passband ripple tolerance in dB. `'Apasstol'` defaults to  $1e-4$ .

`Hq = minimizecoeffwl(Hd,...,'Astoptol',Astoptol)` specifies the stopband tolerance in dB. `'Astoptol'` defaults to  $1e-2$ .

`Hq = minimizecoeffwl(Hd,...,'MatchrefFilter',RefFiltFlag)` determines whether the fixed-point filter matches the filter order and transition width of the floating-point design. Setting `'MatchRefFilter'` to true returns a fixed-point filter with the same order and transition width as `Hd`. The `'MatchRefFilter'` property defaults to false and the

# minimizcoeffwl

---


resulting fixed-point filter may have a different order and transition width than the floating-point design Hd.

You must have the Fixed-Point Toolbox software installed to use this function.

## Examples

Minimize wordlength for lowpass FIR equiripple filter:

```
f=fdesign.lowpass('Fp,Fst,Ap,Ast',0.2,0.3,1,60);
% Design filter with double-precision floating point
Hd=design(f,'equiripple');
% Find minimum wordlength fixed-point filter
% with 0.15 dB stopband tolerance
Hq=minimizcoeffwl(Hd,'MatchRefFilter',true,'Astoptol',0.15);
Hq1=minimizcoeffwl(Hd,'Astoptol',0.15);
% Hq.coeffwordlength is 14 bits.
% Hq1.coeffwordlength is 11 bits
hfvf=fvtool(Hd,Hq,Hq1,'showreference','off');
legend(hfvf,'44 coefficients floating-point',...
'44 coefficients 14 bits','48 coefficients 11 bits');
```



## See Also

`constraincoeffwl` | `design` | `fdesign` | `maximizestopband` | `measure` | `rand`

## Tutorials

- “Fixed-Point Data Types”

**Purpose** Predicted mean-squared error for adaptive filter

**Syntax**

```
[mmse,emse] = msepred(ha,x,d)
[mmse,emse,meanw,mse,tracek] = msepred(ha,x,d)
[mmse,emse,meanw,mse,tracek] = msepred(ha,x,d,m)
```

**Description** [mmse,emse] = msepred(ha,x,d) predicts the steady-state values at convergence of the minimum mean-squared error (mmse) and the excess mean-squared error (emse) given the input and desired response signal sequences in x and d and the property values in the adaptfilt object ha.

[mmse,emse,meanw,mse,tracek] = msepred(ha,x,d) calculates three sequences corresponding to the analytical behavior of the LMS adaptive filter defined by ha:

- **meanw** — contains the sequence of coefficient vector means. The columns of matrix meanw contain predictions of the mean values of the LMS adaptive filter coefficients at each time instant. The dimensions of meanw are (size(x,1))-by-(ha.length).
- **mse** — contains the sequence of mean-square errors. This column vector contains predictions of the mean-square error of the LMS adaptive filter at each time instant. The length of mse is equal to size(x,1).
- **tracek** — contains the sequence of total coefficient error powers. This column vector contains predictions of the total coefficient error power of the LMS adaptive filter at each time instant. The length of tracek is equal to size(x,1).

[mmse,emse,meanw,mse,tracek] = msepred(ha,x,d,m) specifies an optional input argument m that is the decimation factor for computing meanw, mse, and tracek. When m > 1, msepred saves every mth predicted value of each of these sequences. When you omit the optional argument m, it defaults to one.

---

**Note** msepred is available for the following adaptive filters only:  
 — adaptfilt.blms — adaptfilt.blmsfft — adaptfilt.lms —  
 adaptfilt.nlms — adaptfilt.se Using msepred is the same for any  
 adaptfilt object constructed by the supported filters.

---

## Examples


Analyze and simulate a 32-coefficient adaptive filter using 25 trials of 2000 iterations each.

```
x = zeros(2000,25); d = x;      % Initialize variables
ha = fir1(31,0.5);             % FIR system to be identified
x = filter(sqrt(0.75),[1 -0.5],sign(randn(size(x)))));
n = 0.1*randn(size(x));        % observation noise signal
d = filter(ha,1,x)+n;          % desired signal
l = 32;                         % Filter length
mu = 0.008;                    % LMS step size.
m = 5;                          % Decimation factor for analysis
                                % and simulation results

ha = adaptfilt.lms(l,mu);
[mmse,emse,meanW,mse,traceK] = msepred(ha,x,d,m);
[simmse,meanWsim,Wsim,traceKsim] = msesim(ha,x,d,m);
nn = m:m:size(x,1);
subplot(2,1,1);
plot(nn,meanWsim(:,12),'b',nn,meanW(:,12),'r',nn,...
meanWsim(:,13:15),'b',nn,meanW(:,13:15),'r');
PlotTitle ={'Average Coefficient Trajectories for';...
            'W(12), W(13), W(14), and W(15)'};
title(PlotTitle);
legend('Simulation','Theory');
xlabel('Time Index'); ylabel('Coefficient Value');
subplot(2,2,3);
semilogy(nn,simmse,[0 size(x,1)],[(emse+mmse)...
(emse+mmse)],nn,mse,[0 size(x,1)],[mmse mmse]);
title('Mean-Square Error Performance');
axis([0 size(x,1) 0.001 10]);
legend('MSE (Sim.)','Final MSE','MSE','Min. MSE');
```

```
xlabel('Time Index'); ylabel('Squared Error Value');  
subplot(2,2,4);  
semilogy(nn,traceKsim,nn,traceK,'r');  
title('Sum-of-Squared Coefficient Errors'); axis([0 size(x,1)...  
0.0001 1]);  
legend('Simulation','Theory');  
xlabel('Time Index'); ylabel('Squared Error Value');
```

Viewing the plots in this figure you see the various error values plotted in both simulation and theory. Each subplot reveals more information about the results as the simulation converges with the theoretical performance.



**See Also**

`filter` | `maxstep` | `msesim`

**Purpose**

Measured mean-squared error for adaptive filter

**Syntax**

```
mse = msesim(ha,x,d)
[mse,meanw,w,tracek] = msesim(ha,x,d)
[mse,meanw,w,tracek] = msesim(ha,x,d,m)
```

**Description**

`mse = msesim(ha,x,d)` returns the sequence of mean-square errors in column vector `mse`. The vector contains estimates of the mean-square error of the adaptive filter at each time instant during adaptation. The length of `mse` is equal to `size(x,1)`. The columns of matrix `x` contain individual input signal sequences, and the columns of the matrix `d` contain corresponding desired response signal sequences.

`[mse,meanw,w,tracek] = msesim(ha,x,d)` calculates three parameters that correspond to the simulated behavior of the adaptive filter defined by `ha`:

- `meanw` — sequence of coefficient vector means. The columns of this matrix contain estimates of the mean values of the LMS adaptive filter coefficients at each time instant. The dimensions of `meanw` are `(size(x,1))-by-(ha.length)`.
- `w` — estimate of the final values of the adaptive filter coefficients for the algorithm corresponding to `ha`.
- `tracek` — sequence of total coefficient error powers. This column vector contains estimates of the total coefficient error power of the LMS adaptive filter at each time instant. The length of `tracek` is equal to `size(X,1)`.

`[mse,meanw,w,tracek] = msesim(ha,x,d,m)` specifies an optional input argument `m` that is the decimation factor for computing `meanw`, `mse`, and `tracek`. When `m > 1`, `msepsim` saves every `m`th predicted value of each of these sequences. When you omit the optional argument `m`, it defaults to one.


**Examples**

Simulation of a 32-coefficient FIR filter using 25 trials, each trial having 2000 iterations of the adaptation process.

```
x = zeros(2000,25); d = x;           % Initialize variables
ha = fir1(31,0.5);                   % FIR system to be identified
x = filter(sqrt(0.75),[1 -0.5],sign(randn(size(x))));
n = 0.1*randn(size(x));              % Observation noise signal
d = filter(ha,1,x)+n;                % Desired signal
l = 32;                               % Filter length
mu = 0.008;                          % LMS Step size.
m = 5;                                % Decimation factor for analysis
                                     % and simulation results

ha = adaptfilt.lms(l,mu);
[simmse,meanWsim,Wsim,traceKsim] = msesim(ha,x,d,m);
nn = m:m:size(x,1);
subplot(2,1,1);
plot(nn,meanWsim(:,12), 'b',nn,meanWsim(:,13:15), 'b');
PlotTitle = {'Average Coefficient Trajectories for';...
            'W(12), W(13), W(14), and W(15)'};
title(PlotTitle);
xlabel('Time Index'); ylabel('Coefficient Value');
subplot(2,2,3);
semilogy(nn,simmse);
title('Mean-Square Error Performance'); axis([0 size(x,1) 0.001...
10]);
legend('Measured MSE');
xlabel('Time Index'); ylabel('Squared Error Value');
subplot(2,2,4);
semilogy(nn,traceKsim);
title('Sum-of-Squared Coefficient Errors'); axis([0 size(x,1)...
0.0001 1]);
xlabel('Time Index'); ylabel('Squared Error Value');
```

Calculating the mean squared error for an adaptive filter is one measure of the performance of the adapting algorithm. In this figure, you see a variety of measures of the filter, including the error values.



**See Also** `filter` | `msepred`

# multistage

---

**Purpose** Multistage filter from specification object

**Syntax**

```
hd = design(d, 'multistage')
hd = design(..., 'filterstructure', structure)
hd = design(..., 'nstages', nstages)
hd = design(..., 'usehalfbands', hb)
```

**Description** `hd = design(d, 'multistage')` designs a multistage filter whose response you specified by the filter specification object `d`.

`hd = design(..., 'filterstructure', structure)` returns a filter with the structure specified by `structure`. Input argument `structure` is `dffir` by default and can also be one of the following strings.

structure String	Valid with These Responses
<code>firdecim</code>	Lowpass or Nyquist response
<code>firtdecim</code>	Lowpass or Nyquist response
<code>firinterp</code>	Lowpass or Nyquist response
<code>lowpass</code>	Default lowpass only

Multistage design applies to the default lowpass filter specification object and to decimators and interpolators that use either lowpass or Nyquist responses.

`hd = design(..., 'nstages', nstages)` specifies `nstages`, the number of stages to be used in the design. `nstages` must be an integer or the string `auto`. To allow the design algorithm to use the optimal number of stages while minimizing the cost of using the resulting filter, `nstages` is `auto` by default. When you specify an integer for `nstages`, the design algorithm minimizes the cost for the number of stages you specify.


`hd = design(..., 'usehalfbands', hb)` uses halfband filters when you set `hb` to `true`. The default value for `hb` is `false`.

**Note** To see a list of the design methods available for your filter, use `designmethods(hd)`.

## Examples

Design a minimum-order, multistage Nyquist interpolator.

```
l = 15; % Interpolation factor. Also the Nyquist band.
tw = 0.05; % Normalized transition width
ast = 40; % Minimum stopband attenuation in dB
d = fdesign.interpolator(l,'nyquist',l,'tw,ast',tw,ast);
hm = design(d,'multistage');
fvtool(hm);
```




Design a multistage lowpass interpolator with an interpolation factor of 8.

```
m = 8; % Interpolation factor;
```

# multistage

```
d = fdesign.interpolator(m,'lowpass');  
% Use halfband filters if possible.  
hm = design(d,'multistage','Usehalfbands',true);  
fvtool(hm);
```

This figure shows the response for hm.



**See Also**

[design](#) | [designopts](#)

**Purpose**

Power spectral density of filter output due to roundoff noise

**Syntax**

```
hpsd = noisepsd(H,L)
hpsd = noisepsd(H,L,param1,value1,param2,value2,...)
hpsd = noisepsd(H,L,opts)
noisepsd(H,...)
```

**Description**

`hpsd = noisepsd(H,L)` computes the power spectral density (PSD) at the output of `dfilt` object or filter System object, `H`, occurring because of roundoff noise. This noise is produced by quantization errors within the filter. `L` is the number of trials used to compute the average. The PSD is computed from the average over the `L` trials. The more trials you specify, the better the estimate, but at the expense of longer computation time. When you do not explicitly specify `L`, the default is 10 trials.

`hpsd` is a psd data object. To extract the PSD vector (the data from the PSD) from `hpsd`, enter

```
get(hpsd,'data')
```

at the prompt. Plot the PSD data with `plot(hpsd)`. The average power of the output noise (the integral of the PSD) can be computed with `avgpower`, a method of `dspdata` objects:

```
avgpwr = avgpower(hpsd).
```

`hpsd = noisepsd(H,L,param1,value1,param2,value2,...)` where `H` can be either a `dfilt` object or a filter System object, specifies optional parameters via `propertyname/propertyvalue` pairs. Valid psd object property values are:

# noisepsd

Property Name	Default Value	Description and Valid Entries
Nfft	512	Specify the number of FFT points to use to calculate the PSD.
NormalizedFrequency	true	Determine whether to use normalized frequency. Enter a logical value of true or false. Because this property is a logical value, and not a string, do not enclose the single quotation marks.
Fs	normalized	Specify the sampling frequency to use when you set NormalizedFrequency to false. Use any integer value greater than 1. Enter the value in Hz.
SpectrumType	onesided	<p>Specify how noisepsd should generate the PSD. Options are onesided or twosided. If you choose a two-sided computation, you can also choose CenterDC = true. Otherwise, CenterDC must be false.</p> <ul style="list-style-type: none"><li>• onesided converts the type to a spectrum that is calculated over half the Nyquist interval. All properties affected by the new frequency range are adjusted automatically.</li><li>• twosided converts the type to a spectrum that is calculated over the whole Nyquist interval. All properties affected by the new frequency range are adjusted automatically.</li></ul>

Property Name	Default Value	Description and Valid Entries
CenterDC	false	<p>Shift the zero-frequency component to the center of a two-sided spectrum.</p> <ul style="list-style-type: none"> <li>• When you set <code>SpectrumType</code> to <code>onesided</code>, it is changed to <code>twosided</code> and the data is converted to a two-sided spectrum.</li> <li>• Setting <code>CenterDC</code> to <code>false</code> shifts the data and the frequency values in the object so that DC is in the left edge of the spectrum. This operation does not affect the <code>SpectrumType</code> property setting.</li> </ul>
Arithmetic (only for filter System objects)	ARITH	Analyze the filter System object, based on the arithmetic specified in the ARITH input. ARITH can be set to <code>double</code> , <code>single</code> , or <code>fixed</code> . The analysis tool assumes a double-precision filter when the arithmetic input is not specified and the filter System object is in an unlocked state.

---

**Note** If the spectrum data you specify is calculated over half the Nyquist interval and you do not specify a corresponding frequency vector, the default frequency vector assumes that the number of points in the whole FFT was even. Also, the plot option to convert to a whole or two-sided spectrum assumes the original whole FFT length is even.

---

If `H` is a filter System object, `noisepsd` requires knowledge of the input data type. Analysis cannot be performed if the input data type is not available. If you do not specify the `Arithmetic` parameter, i.e., use the syntax `[h,w] = noisepsd(H)`, then the following rules apply to this method:

- The System object state is Unlocked — noisepsd performs double-precision analysis.
- The System object state is Locked — noisepsd performs analysis based on the locked input data type.

If you do specify the Arithmetic parameter, i.e., use the syntax `[h,w] = noisepsd(H, 'Arithmetic', ARITH)`, review the following rules for this method. Which rule applies depends on the value you set for the Arithmetic parameter.

Value	System Object State	Rule
ARITH = 'double'	Unlocked	noisepsd performs double-precision analysis.
	Locked	noisepsd performs double-precision analysis.
ARITH = 'single'	Unlocked	noisepsd performs single-precision analysis.
	Locked	noisepsd performs single-precision analysis.

Value	System Object State	Rule
ARITH = `fixed`	Unlocked	noisepsd produces an error because the fixed-point input data type is unknown.
	Locked	When the input data type is double or single, then noisepsd produces an error because since the fixed-point input data type is unknown.
		When the input data is of fixed-point type, noisepsd performs analysis based on the locked input data type.

noisepsd supports only the following filter System objects:

- dsp.FIRFilter
- dsp.IIRFilter
- dsp.AllpoleFilter
- dsp.BiquadFilter

Regardless of whether H is a dfilt object or a filter System object, hpsd = noisepsd(H,L,opts) uses an options object, opts, to specify the optional input arguments. This specification is not made using property-value pairs in the command. Use opts = noisepsopts(H) to create the object. opts then has the noisepsd settings from H. After creating opts, you change the property values before calling noisepsd:

```
set(opts,'fs',48e3); % Set Fs to 48 kHz.
```


Regardless of whether  $H$  is a `dfilt` object or a filter System object, `noisepsd(H, ...)` with no output argument launches FVTool.

## Examples

Compute the PSD of the output noise caused by the quantization processes in a fixed-point, direct form FIR filter.

```
b = firgr(27,[0 .4 .6 1],[1 1 0 0]);  
h = dfilt.dffir(b); % Create the filter object.  
% Quantize the filter to fixed-point.  
h.arithmetic = 'fixed';  
hpsd = noisepsd(h);  
plot(hpsd)
```

`hpsd` looks similar to the following figure—the data resulting from the noise PSD calculation. You can review the data in `hpsd.data`.



## References

McClellan, et al., *Computer-Based Exercises for Signal Processing Using MATLAB 5*. Upper Saddle River, N.J.: Prentice-Hall, 1998.

**See Also**     `filter` | `noisepsdopts` | `norm` | `reorder` | `scale` | `spectrum.welch`

# noisepsdopts

---

**Purpose** Options for running filter output noise PSD

**Syntax** `opts = noisepsdopts(H)`

**Description** `opts = noisepsdopts(H)` uses the current settings in the `dfilt` object or the filter System object, `H`, to create an options object, `opts`, that contains specified options for computing the output noise PSD. You can pass `opts` to the `scale` method as an input argument to apply scaling settings to a second-order filter.

`noisepsdopts` returns the options object, `opts`, with which you can set the following properties for `noisepsd`:

Property Name	Default Value	Description and Valid Entries
<code>Nfft</code>	512	Specify the number of FFT points to use to calculate the PSD.
<code>NormalizedFrequency</code>	<code>true</code>	Determine whether to use normalized frequency. Enter a logical value of the logical <code>true</code> or <code>false</code> . Because this property is a logical value, and not a string, do not enclose with single quotation marks.
<code>Fs</code>	<code>normalized</code>	Specify the sampling frequency to use when you set <code>NormalizedFrequency</code> to <code>false</code> . Use any integer value greater than 1. Enter the value in Hz.

Property Name	Default Value	Description and Valid Entries
SpectrumType	onesided	<p>Specify how noisepsd should generate the PSD. Options are onesided or twosided. If you choose a two-sided computation, you can also choose centerdc = true. Otherwise, centerdc must be false.</p> <ul style="list-style-type: none"> <li>• onesided converts the type to a spectrum that is calculated over half the Nyquist interval. All properties affected by the new frequency range are adjusted automatically.</li> <li>• twosided converts the type to a spectrum that is calculated over the whole Nyquist interval. All properties affected by the new frequency range are adjusted automatically.</li> </ul>
CenterDC	false	<p>Shift the zero-frequency component to the center of a two-sided spectrum.</p> <ul style="list-style-type: none"> <li>• When you set SpectrumType to onesided, it is changed to twosided and the data is converted to a two-sided spectrum.</li> <li>• Setting CenterDC to false shifts the data and the frequency values in the object so that DC is in the left edge of the spectrum.</li> </ul>

# noisepsdopts

---

Property Name	Default Value	Description and Valid Entries
		This operation does not effect the SpectrumType property setting.
Arithmetic (only for filter System objects)	ARITH	Analyze the filter System object, based on the arithmetic specified in the ARITH input. ARITH can be set to double, single, or fixed. The analysis tool assumes a double-precision filter when the arithmetic input is not specified and the filter System object is in an unlocked state.

**See Also**      noisepsd

**Purpose**

P-norm of filter

**Syntax**

```
l = norm(ha)
l = norm(ha, pnorm)
l = norm(hd)
l = norm(hd, pnorm)
l = norm(hm)
l = norm(hm, pnorm)
```

**Description**

All of the variants of `norm` return the filter p-norm for the object in the syntax, either an adaptive filter, a digital filter, or a multirate filter. When you omit the `pnorm` argument, `norm` returns the L2-norm for the object.

Note that by Parseval's theorem, the L2-norm of a filter is equal to the l2 norm. This equality is not true for the other norm variants.

**For adaptfilt Objects**

`l = norm(ha)` returns the L2-norm of an adaptive filter. `l = norm(ha, pnorm)` adds the input argument `pnorm` to let you specify the norm returned. `pnorm` can be either

- Frequency-domain norms specified by one of `L1`, `L2`, or `Linf`
- Discrete-time domain norms specified by one of `l1`, `l2`, or `linf`

**For dfilt Objects**

`l = norm(hd)` returns the L2-norm of a discrete-time filter.

`l = norm(hd, pnorm)` includes input argument `pnorm` that lets you specify the norm returned. `pnorm` can be either

- Frequency-domain norms specified by one of `L1`, `L2`, or `Linf`
- Discrete-time domain norms specified by one of `l1`, `l2`, or `linf`

By Parseval's theorem, the L2-norm of a filter is equal to the l2 norm. This equality is not true for the other norm variants.

IIR filters respond slightly differently to `norm`. When you compute the l2, `linf`, `L1`, and `L2` norms for an IIR filter, `norm(..., L2, tol)` lets you

specify the tolerance for the accuracy in the computation. For `l1`, `l2`, `L2`, and `linf`, `norm` uses the tolerance to truncate the infinite impulse response that it uses to calculate the norm. For `L1`, `norm` passes the tolerance to the numerical integration algorithm. Refer to Examples to see this in use. You cannot specify `Linf` for the norm and include the `tol` option.

## For mfilt Objects

`l = norm(hm)` returns the L2-norm of a multirate filter.

`l = norm(hm, pnorm)` includes argument `pnorm` to let you specify the norm returned. `pnorm` can be either

- Frequency-domain norms specified by one of `L1`, `L2`, or `Linf`
- Discrete-time domain norms specified by one of `l1`, `l2`, or `linf`

Note that, by Parseval's theorem, the L2-norm of a filter is equal to the `l2` norm. This equality is not true for the other norm variants.

## Examples

### Adaptfilt Objects

For the adaptive filter example, compute the 2-norm of an `adaptfilt` object, here an LMS-based adaptive filter.

```
Ha = adaptfilt.lms; % norm(ha) is zero because all coeffs are zero
% Create some data to filter to generate filter coeffs
x = randn(100,1);
d = x + randn(100,1);
[y,e] = filter(Ha,x,d);
L2 = norm(Ha); % Now norm(ha) is nonzero
```

### Dfilt Objects

To demonstrate the tolerance option used with an IIR filter (`dfilt` object), compute the 2-norm of filter `hd` with a tolerance of `1e-10`.

```
H = fdesign.lowpass('n,fc',5,0.4);
Hd = butter(H);
L2=norm(Hd,'l2',1e-10);
```

### **Mfilt Objects**

In this example, compute the infinity norm of an FIR polyphase interpolator, which is an `mfilt` object.

```
Hm = mfilt.firinterp;  
Linf = norm(Hm,'linf');
```

### **See Also**

[reorder](#) | [scale](#) | [scalecheck](#)

# normalize

---

**Purpose** Normalize filter numerator or feed-forward coefficients

**Syntax** `normalize(hq)`  
`g = normalize(hd)`

**Description** `normalize(hq)` normalizes the filter numerator coefficients for a quantized filter to have values between -1 and 1. The coefficients of `hq` change — `normalize` does not copy `hq` and return the copy. To restore the coefficients of `hq` to the original values, use `denormalize`.

Note that for lattice filters, the feed-forward coefficients stored in the property `lattice` are normalized.

`g = normalize(hd)` normalizes the numerator coefficients for the filter `hq` to between -1 and 1 and returns the gain `g` due to the normalization operation. Calling `normalize` again does not change the coefficients. `g` always returns the gain returned by the first call to `normalize` the filter.

**Examples** Create a direct form II quantized filter that uses second-order sections. Then use `normalize` to maximize the use of the range of representable coefficients.

```
d=fdesign.lowpass('n,fp,ap,ast',8,.5,2,40);  
hd=design(d,'ellip');  
hd.arithmetic='fixed';
```

Check the filter coefficients. Note that `InitialSOSMatrix(3,2)>1`

```
InitialSOSMatrix = hd.sosMatrix;
```

Use `normalize` to modify the coefficients into the range between -1 and 1. The output `g` contains the gains applied to each section of the SOS filter.

```
g = normalize(hd);
```

None of the numerator coefficients exceed -1 or 1.

## See Also

denormalize

# normalizefreq

---

**Purpose** Switch filter specification between normalized frequency and absolute frequency

**Syntax** `normalizefreq(d)`  
`normalizefreq(d, flag)`  
`normalizefreq(d, false, fs)`

**Description** `normalizefreq(d)` normalizes the frequency specifications in filter specifications object `d`. By default, the `NormalizedFrequency` property is set to `true` when you create a design object. You provide the design specifications in normalized frequency units. `normalizefreq` does not affect filters that already use normalized frequency.

If you use this syntax when `d` does not use normalized frequency specifications, all of the frequency specifications are normalized by  $fs/2$  so they lie between 0 and 1, where `fs` is specified in the object. Included in the normalization are the filter properties that define the filter pass and stopband edge locations by frequency:

- `F3 dB` — Used by IIR filter specifications objects to describe the passband cutoff frequency
- `Fcutoff` — Used by FIR filter specifications objects to describe the passband cutoff frequency
- `Fpass` — Describes the passband edges
- `Fstop` — Describes the stopband edges

In this syntax, `normalizefreq(d)` assumes you specified `fs` when you created `d` or changed `d` to use absolute frequency specifications.

`normalizefreq(d, flag)` where `flag` is either `true` or `false`, specifies whether the `NormalizedFrequency` property value is `true` or `false` and therefore whether the filter normalizes the sampling frequency `fs` and other related frequency specifications. `fs` defaults to 1 for this syntax.

When you do not provide the input argument `flag`, it defaults to `true`. If you set `flag` to `false`, affected frequency specifications are multiplied by  $fs/2$  to remove the normalization. Use this syntax to switch your

filter between using normalized frequency specifications and not using normalized frequency specifications.

`normalizefreq(d, false, fs)` lets you specify a new sampling frequency `fs` when you set the `NormalizedFrequency` property to `false`.

## Examples

These examples demonstrate using `normalizefreq` in both of the major syntax applications—setting the design object frequency specifications to use absolute frequency (`normalizefreq(hd, false, fs)`) and resetting a design object to using normalized frequencies (`normalizefreq(d)`).

Construct a highpass filter specifications object by specifying the passband and stopband edges and the desired attenuations in the bands. By default, provide the frequency specifications in normalized values between 0 and 1.

```
d=fdesign.highpass(0.35, 0.45, 60, 40);
```

`Fstop` and `Fpass` are in normalized form, and the property `NormalizedFrequency` is `true`.

Now use `normalizedfreq` to convert to absolute frequency specifications, with a sampling frequency of 1000 Hz.

```
normalizefreq(d, false, 1e3);
```

Both of the attenuation specifications remain the same. The passband and stopband edge definitions now appear in Hz, where the new value represents the normalized values multiplied by  $F_s/2$ , or 500 Hz.

Converting to using normalized frequencies consists of using `normalizefreq` with the design object `d`.

```
normalizefreq(d)
```

For `bandstop`, `bandpass`, and `multiple band` filter specifications objects, `normalizefreq` works the same way for all band edge definitions. When you do not provide the sampling frequency  $F_s$  as an input argument and you are converting to absolute frequency specifications, `normalizefreq` sets  $F_s$  to 1, as shown in this example.

# normalizefreq

---

```
d=fdesign.bandstop(0.25,0.35,0.55,0.65,50,60);  
normalizefreq(d,false)
```

## See Also

```
fdesign.lowpass | fdesign.halfband | fdesign.highpass |  
fdesign.interpolator
```

**Purpose** Number of filter states

**Syntax** `n = nstates(hd)`  
`n = nstates(hm)`

**Description** **Discrete-Time Filters**

`n = nstates(hd)` returns the number of states `n` in the discrete-time filter `hd`. The number of states depends on the filter structure and the coefficients.

**Multirate Filters**

`n = nstates(hm)` returns the number of states `n` in the multirate filter `hm`. The number of states depends on the filter structure and the coefficients.

**Examples** Check the number of states for two different filters, one a direct form FIR filter, the other a multirate filter.

```
h = fir1s(30,[0 .1 .2 .5]*2,[1 1 0 0]);  
hd = dfilt.dffir(h);  
NstateDF = nstates(hd);  
hm = mfilt.firsrc(2,3);  
NstateMR = nstates(hm);
```

**See Also** `mfilt`

# order

---

**Purpose** Order of fixed-point filter

**Syntax** `n = order(hq)`  
`n = order(hs)`

**Description** `n = order(hq)` returns the order `n` of the quantized filter `hq`. When `hq` is a single-section filter, `n` is the number of delays required for a minimum realization of the filter.

When `hq` has more than one section, `n` is the number of delays required for a minimum realization of the overall filter.

`n = order(hs)` returns the order `n` of the filter System object `hs`. The order depends on the filter structure and the reference double-precision floating-point coefficients. `hs` can be one of the following filter structures:

- `dsp.FIRFilter`
- `dsp.BiquadFilter`
- `dsp.FIRInterpolator`
- `dsp.CICInterpolator`
- `dsp.FIRDecimator`
- `dsp.CICDecimator`
- `dsp.FIRRateConverter`

**Examples** Create a discrete-time filter, quantize it, and convert it to second-order section form. Then, use `order` to check the order of the filter.


```
[b,a] = ellip(4,3,20,.6); % Create the reference filter.  
hq = dfilt.df2(b,a);  
% Quantize the filter and convert to second-order sections.  
set(hq,'arithmetic','fixed');  
  
n=order(hq); % Check the order of the overall filter.
```

**Purpose** Multirate parallel filter structure

**Syntax** `hmp = parallel(hm1,hm2,...,hmn)`

**Description** `hmp = parallel(hm1,hm2,...,hmn)` returns a multirate filter `hmp` that is two or more `mfilt` objects `hm1`, `hm2`, and so on connected in a parallel structure. Each filter in the structure is one stage and all stages must have the same rate change factor.

Access the individual filters in the parallel structure by



**See Also** `dfilt.parallel` | `mfilt`

# phasedelay

---

**Purpose** Phase delay of filter

**Syntax**

```
[phi,w]=phasedelay(hfilt)
[phi,w]=phasedelay(hfilt,n)
phasedelay(hfilt)
[phi,w] = phasedelay(hs)
[phi,w] = phasedelay(hs,n)
[phi,w] = phasedelay(hs,Name,Value)
phasedelay(hs)
```

**Description** `phasedelay` returns the phase delay based on the current filter coefficients. This section describes `phasedelay` operation for discrete-time filters and multirate filters. For more information about optional input arguments for `phasedelay`, refer to `phasedelay` in Signal Processing Toolbox documentation.

`[phi,w]=phasedelay(hfilt)` returns the phase response `phi` of the filter `hfilt` and the corresponding frequencies `w` at which the function evaluates the phase delay.

The phase delay is evaluated at 8192 points equally spaced around the upper half of the unit circle.

`[phi,w]=phasedelay(hfilt,n)` returns the phase delay `phi` of the filter `hfilt` and the corresponding frequencies `w` at which the function evaluates the phase delay. The phase delay is evaluated at `n` points equally spaced around the upper half of the unit circle.

`phasedelay(hfilt)` displays the phase delay of `hfilt` in the Filter Visualization Tool (FVTool).

`[phi,w] = phasedelay(hs)` returns the phase delay for the filter System object `hs` using 8192 samples.

`[phi,w] = phasedelay(hs,n)` returns the phase delay for the filter System object `hs` using `n` samples.

`[phi,w] = phasedelay(hs,Name,Value)` returns the phase delay with additional options specified by one or more `Name,Value` pair arguments.

`phasedelay(hs)` uses FVTool to plot the phase delay of the filter System object `hs`.

## Input Arguments

### **hfilt**

`hfilt` is either:

- A discrete-time `dfilt`, or multirate `mfilt` filter object
- A vector of discrete-time, or multirate filter objects

The multirate filter delay response is computed relative to the rate at which the filter is running. When you specify `fs` (the sampling rate) as an input argument, `phasedelay` assumes the filter is running at that rate.

For multistage cascades, `phasedelay` forms a single-stage multirate filter that is equivalent to the cascade. It then computes the response relative to the rate at which the equivalent filter is running. `phasedelay` does not support all multistage cascades. The function analyzes only those cascades for which there exists an equivalent single-stage filter.

As an example, consider a 2-stage interpolator where the first stage has an interpolation factor of 2 and the second stage has an interpolation factor of 4. In this case, an equivalent single-stage filter exists with an overall interpolation factor of 8. `phasedelay` uses this equivalent filter for the analysis. If a sampling frequency `fs` is specified as an input argument to `phasedelay`, the function interprets `fs` as the rate at which the equivalent filter is running.

### **hs**

Filter System object. The function supports the following filter structures.

- `dsp.FIRFilter`
- `dsp.BiquadFilter`
- `dsp.FIRInterpolator`
- `dsp.CICInterpolator`

- `dsp.FIRDecimator`
- `dsp.CICDecimator`
- `dsp.FIRRateConverter`

## **n**

Number of samples. For an FIR filter where `n` is a power of two, the computation is done faster using FFTs.

**Default:** 8192

## **Name-Value Pair Arguments**

Specify optional comma-separated pairs of `Name`, `Value` arguments, where `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes ( `' '`). You can specify several name and value pair arguments in any order as `Name1,Value1,...,NameN,ValueN`.

## **Arithmetic**

`'double' | 'single' | 'fixed'`

For filter System object inputs only, specify the arithmetic used during analysis. When you specify `'double'` or `'single'`, the function performs double- or single-precision analysis. When you specify `'fixed'`, the arithmetic changes depending on the setting of the `CoefficientDataType` property and whether the System object is locked or unlocked.

**Details for Fixed-Point Arithmetic**

<b>System Object State</b>	<b>Coefficient Data Type</b>	<b>Rule</b>
Unlocked	'Same as input'	The function assumes that the coefficient data type is signed, 16 bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Unlocked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.
Locked	'Same as input'	When the input data type is 'double' or 'fixed', the function assumes that the coefficient data type is signed, 16-bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Locked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.

# phasedelay

---

When you do not specify the arithmetic for non-CIC structures, the function uses double-precision arithmetic if the filter System object is in an unlocked state. If the System object is locked, the function performs analysis based on the locked input data type. CIC structures only support fixed-point arithmetic.

## Output Arguments

### **phi**

Complex, n-element phase-delay vector. If `hfilt` is a vector of filters, `phi` is a complex, `length(hfilt)`-by-`n` matrix of phase-delay vectors whose columns correspond to each filter in `hfilt`. If `n` is not specified, the function uses a default value of 8192.

For adaptive filters, `phi` is the instantaneous phase delay.

### **w**

Frequency vector of length `n`, in radians/sample. `w` consists of `n` points equally spaced around the upper half of the unit circle (from 0 to  $\pi$  radians/sample). If `hfilt` is a vector of filters, `w` is a complex, `length(hfilt)`-by-`n` matrix of phase-delay vectors whose columns correspond to each filter in `hfilt`. If `n` is not specified, the function uses a default value of 8192.

## Algorithms

You can provide `fs`, the sampling frequency, as an input as well. `phasedelay` uses `fs` to calculate the delay response and plots the response to `fs/2`.

## See Also

`freqz` | `grpdelay` | `phasez` | `zerophase` | `zplane` | `freqz` | `fvtool` | `phasez` | `zerophase`

**Purpose** Unwrapped phase response for filter

**Syntax**

```
[phi,w]=phasez(hfilt)
[phi,w]=phasez(hfilt,n)
phasez(hfilt)
[phi,w] = phasez(hs)
[phi,w] = phasez(hs,n)
[phi,w] = phasez(hs,Name,Value)
phasez(hs)
```

**Description** `phasez` returns the unwrapped phase response based on the current filter coefficients. This section describes `phasez` operation for adaptive filters, discrete-time filters, multirate filters, and filter System objects. For more information about optional input arguments for `phasez`, refer to `phasez` in Signal Processing Toolbox documentation.

`[phi,w]=phasez(hfilt)` returns the phase response `phi` of the filter `hfilt` and the corresponding frequencies `w` at which the function evaluates the phase response. The phase response is evaluated at 8192 points equally spaced around the upper half of the unit circle.

`[phi,w]=phasez(hfilt,n)` returns the phase response `phi` of the filter `hfilt` and the corresponding frequencies `w` at which the function evaluates the phase response. The phase response is evaluated at `n` points equally spaced around the upper half of the unit circle.

`phasez(hfilt)` displays the phase response of `hfilt` in the Filter Visualization Tool (FVTool).

`[phi,w] = phasez(hs)` returns a phase response for the filter System object `hs` using 8192 samples.

`[phi,w] = phasez(hs,n)` returns a phase response for the filter System object `hs` using `n` samples.

`[phi,w] = phasez(hs,Name,Value)` returns a phase response with additional options specified by one or more `Name,Value` pair arguments.

`phasez(hs)` uses `FVTool` to plot the phase response of the filter System object `hs`.

## Input Arguments

### **hfilter**

`hfilter` is either:

- An adaptive `adaptfilt`, discrete-time `dfilt`, or multirate `mfilt` filter object
- A vector of adaptive, discrete-time, or multirate filter objects

The multirate filter response is computed relative to the rate at which the filter is running. When you specify `fs` (the sampling rate) as an input argument, `phasez` assumes the filter is running at that rate.

For multistage cascades, `phasez` forms a single-stage multirate filter that is equivalent to the cascade. It then computes the response relative to the rate at which the equivalent filter is running. `phasez` does not support all multistage cascades. The function analyzes only those cascades for which there exists an equivalent single-stage filter.

As an example, consider a 2-stage interpolator where the first stage has an interpolation factor of 2 and the second stage has an interpolation factor of 4. In this case, an equivalent single-stage filter exists with an overall interpolation factor of 8. `phasez` uses this equivalent filter for the analysis. If a sampling frequency `fs` is specified as an input argument to `phasez`, the function interprets `fs` as the rate at which the equivalent filter is running.

### **hs**

Filter System object. The function supports the following filter structures.

- `dsp.FIRFilter`
- `dsp.BiquadFilter`
- `dsp.FIRInterpolator`
- `dsp.CICInterpolator`

- `dsp.FIRDecimator`
- `dsp.CICDecimator`
- `dsp.FIRRateConverter`

**n**

Number of samples. For an FIR filter where `n` is a power of two, the computation is done faster using FFTs.

**Default:** 8192

**Name-Value Pair Arguments**

Specify optional comma-separated pairs of `Name, Value` arguments, where `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes ( `' '` ). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

**Arithmetic**

`'double' | 'single' | 'fixed'`

For filter System object inputs only, specify the arithmetic used during analysis. When you specify `'double'` or `'single'`, the function performs double- or single-precision analysis. When you specify `'fixed'`, the arithmetic changes depending on the setting of the `CoefficientDataType` property and whether the System object is locked or unlocked.

**Details for Fixed-Point Arithmetic**

<b>System Object State</b>	<b>Coefficient Data Type</b>	<b>Rule</b>
Unlocked	'Same as input'	The function assumes that the coefficient data type is signed, 16 bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Unlocked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.
Locked	'Same as input'	When the input data type is 'double' or 'fixed', the function assumes that the coefficient data type is signed, 16-bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Locked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.

When you do not specify the arithmetic for non-CIC structures, the function uses double-precision arithmetic if the filter System object is in an unlocked state. If the System object is locked, the function performs analysis based on the locked input data type. CIC structures only support fixed-point arithmetic.

## Output Arguments

### **phi**

Complex, n-element phase response vector. If `hfilt` is a vector of filters, `phi` is a complex, `length(hfilt)`-by-`n` matrix of phase response vectors whose columns correspond to each filter in `hfilt`. If `n` is not specified, the function uses a default value of 8192.

For adaptive filters, `phi` is the instantaneous phase response.

### **w**

Frequency vector of length `n`, in radians/sample. `w` consists of `n` points equally spaced around the upper half of the unit circle (from 0 to  $\pi$  radians/sample). If `hfilt` is a vector of filters, `w` is a complex, `length(hfilt)`-by-`n` matrix of phase response vectors whose columns correspond to each filter in `hfilt`. If `n` is not specified, the function uses a default value of 8192.

## See Also

`freqz` | `grpdelay` | `phasedelay` | `zerophase` | `zplane` | `freqz` | `fvtool` | `phasez`

# polyphase

---

<b>Purpose</b>	Polyphase decomposition of multirate filter
<b>Syntax</b>	<pre>p = polyphase(hm) polyphase(hm) p = polyphase(hs) p = polyphase(hs,Name,Value) polyphase(hs)</pre>
<b>Description</b>	<p><code>p = polyphase(hm)</code> returns the polyphase matrix <code>p</code> of the multirate filter <code>hm</code>.</p> <p><code>polyphase(hm)</code> launches the Filter Visualization Tool (FVTool) with all the polyphase subfilters to allow you to analyze each component subfilter individually.</p> <p><code>p = polyphase(hs)</code> returns the polyphase matrix <code>p</code> of the multirate filter System object <code>hs</code>.</p> <p><code>p = polyphase(hs,Name,Value)</code> returns the polyphase matrix <code>p</code> of the multirate filter System object <code>hs</code>.</p> <p><code>polyphase(hs)</code> launches the Filter Visualization Tool (FVTool) with all the polyphase subfilters to allow you to analyze each component subfilter individually.</p>
<b>Input Arguments</b>	<p><b>hm</b></p> <p>Multirate <code>mfilt</code> filter object. CIC-based filters do not have coefficients, so the function does not support CIC filter structures such as <code>mfilt.cicdecim</code>.</p> <p><b>hs</b></p> <p>Filter System object. The function supports the following filter structures.</p> <ul style="list-style-type: none"><li>• <code>dsp.FIRInterpolator</code></li><li>• <code>dsp.CICInterpolator</code></li><li>• <code>dsp.FIRDecimator</code></li></ul>

- dsp.CICDecimator
- dsp.FIRRateConverter

### Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments, where `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes ( `' '`). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

### Arithmetic

`'double' | 'single' | 'fixed'`

For filter System object inputs only, specify the arithmetic used during analysis. When you specify `'double'` or `'single'`, the function performs double- or single-precision analysis. When you specify `'fixed'`, the arithmetic changes depending on the setting of the `CoefficientDataType` property and whether the System object is locked or unlocked.

### Details for Fixed-Point Arithmetic

System Object State	Coefficient Data Type	Rule
Unlocked	'Same as input'	The function assumes that the coefficient data type is signed, 16 bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Unlocked	'Custom'	The function performs fixed-point analysis based on the setting of the

System Object State	Coefficient Data Type	Rule
		CustomCoefficientsDataType property.
Locked	'Same as input'	When the input data type is 'double' or 'fixed', the function assumes that the coefficient data type is signed, 16-bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Locked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.

When you do not specify the arithmetic for non-CIC structures, the function uses double-precision arithmetic if the filter System object is in an unlocked state. If the System object is locked, the function performs analysis based on the locked input data type. CIC structures only support fixed-point arithmetic.

## Output Arguments

### p

Polyphase matrix  $p$  of the multirate filter. Each row in the matrix represents one subfilter of the multirate filter. The first row of matrix  $p$  represents the first subfilter, the second row the second subfilter, and so on to the last subfilter.

## Examples

When you create a multirate filter that uses polyphase decomposition, polyphase lets you analyze the component filters individually by returning the components as rows in a matrix.

First, create an interpolate-by-eight filter.

```
hm=mfilt.firinterp(8)
```

```
hm =
```

```

      FilterStructure: 'Direct-Form FIR Polyphase Interpolator'
      Numerator: [1x192 double]
      InterpolationFactor: 8
      PersistentMemory: false
      States: [23x1 double]
```

In this syntax, the matrix `p` contains all of the subfilters for `hm`, one filter per matrix row.

```
p=polyphase(hm)
```

```
p =
```

```
Columns 1 through 8
```

```

      0      0      0      0      0      0      0      0
-0.0000  0.0002 -0.0006  0.0013 -0.0026  0.0048 -0.0081  0.0133
-0.0001  0.0004 -0.0012  0.0026 -0.0052  0.0094 -0.0160  0.0261
-0.0001  0.0006 -0.0017  0.0038 -0.0074  0.0132 -0.0223  0.0361
-0.0002  0.0008 -0.0020  0.0045 -0.0086  0.0153 -0.0257  0.0415
-0.0002  0.0008 -0.0021  0.0045 -0.0086  0.0151 -0.0252  0.0406
-0.0002  0.0007 -0.0018  0.0038 -0.0071  0.0124 -0.0205  0.0330
-0.0001  0.0004 -0.0011  0.0022 -0.0041  0.0072 -0.0118  0.0189
```

```
Columns 9 through 16
```

```

      0      0      0      0  1.0000      0      0      0
-0.0212  0.0342 -0.0594  0.1365  0.9741 -0.1048  0.0511 -0.0303
```

# polyphase

---

```
-0.0416  0.0673  -0.1189  0.2958  0.8989  -0.1730  0.0878  -0.0527
-0.0576  0.0938  -0.1691  0.4659  0.7814  -0.2038  0.1071  -0.0648
-0.0661  0.1084  -0.2003  0.6326  0.6326  -0.2003  0.1084  -0.0661
-0.0648  0.1071  -0.2038  0.7814  0.4659  -0.1691  0.0938  -0.0576
-0.0527  0.0878  -0.1730  0.8989  0.2958  -0.1189  0.0673  -0.0416
-0.0303  0.0511  -0.1048  0.9741  0.1365  -0.0594  0.0342  -0.0212
```


Columns 17 through 24

```
0 0 0 0 0 0 0 0
0.0189 -0.0118 0.0072 -0.0041 0.0022 -0.0011 0.0004 -0.0001
0.0330 -0.0205 0.0124 -0.0071 0.0038 -0.0018 0.0007 -0.0002
0.0406 -0.0252 0.0151 -0.0086 0.0045 -0.0021 0.0008 -0.0002
0.0415 -0.0257 0.0153 -0.0086 0.0045 -0.0020 0.0008 -0.0002
0.0361 -0.0223 0.0132 -0.0074 0.0038 -0.0017 0.0006 -0.0001
0.0261 -0.0160 0.0094 -0.0052 0.0026 -0.0012 0.0004 -0.0001
0.0133 -0.0081 0.0048 -0.0026 0.0013 -0.0006 0.0002 -0.0000
```

Finally, using `polyphase` without an output argument opens the Filter Visualization Tool, ready for you to use the analysis capabilities of the tool to investigate the interpolator `hm`.

`polyphase(hm)`

In the following figure, FVTool shows the magnitude responses for the subfilters.



**See Also** `mfilt`

# qreport

---

**Purpose** Most recent fixed-point filtering operation report

**Syntax** `rlog = qreport(h)`

**Description** `rlog = qreport(h)` returns the logging report stored in the filter object `h` in the object `rlog`. The ability to log features of the filtering operation is integrated in the fixed-point filter object and the `filter` method.

Each time you filter a signal with `h`, new log data overwrites the results in the filter from the previous filtering operation. To save the log from a filtering simulation, change the name of the output argument for the operation before subsequent filtering runs.

---

**Note** `qreport` requires Fixed-Point Toolbox software and that filter `h` is a fixed-point filter. Data logging for `fi` operations is a preference you set for each MATLAB session. To learn more about logging, `LoggingMode`, and `fi` object preferences, refer to `fipref` in the Fixed-Point Toolbox documentation.

Also, you cannot use `qreport` to log the filtering operations from a fixed-point Farrow filter.

---

Enable logging during filtering by setting `LoggingMode` to `on` for `fi` objects for your MATLAB session. Trigger logging by setting the `Arithmetic` property for `h` to `fixed`, making `h` a fixed-point filter and filtering an input signal.

## Using Fixed-Point Filtering Logging

Filter operation logging with `qreport` requires some preparation in MATLAB. Complete these steps before you use `qreport`.

- 1 Set the fixed-point object preference for `LoggingMode` to `on` for your MATLAB session. This setting enables data logging.

```
fipref('LoggingMode','on')
```

- 2 Create your fixed-point filter.
- 3 Filter a signal with the filter.
- 4 Use `qreport` to return the filtering information stored in the filter object.

`qreport` provides a way to instrument your fixed-point filters and the resulting data log offers insight into how the filter responds to a particular input data signal.

Report object `rlog` contains a filter-structure-specific list of internal signals for the filter. Each signal contains

- Minimum and maximum values that were recorded during the last simulation. Minimum and maximum values correspond to values before quantization.
- Representable numerical range of the word length and fraction length format
- Number of overflows during filtering for that signal.

## Examples

`qreport` depends on the `LoggingMode` preference for fixed-point objects. This example demonstrates the process for enabling and using `qreport` to log the results of filtering with a fixed-point filter. `hd` is a fixed-point direct-form FIR filter.

```
f = fipref('loggingmode','on');
hd = design(fdesign.lowpass,'equiripple');
hd.arithmetic = 'fixed';
fs = 1000;           % Input sampling frequency.
t = 0:1/fs:1.5;     % Signal length = 1501 samples.
x = sin(2*pi*10*t); % Amplitude = 1 sinusoid.
y = filter(hd,x);
rlog = qreport(hd)
```

View the logging report of a direct-form II, second-order sections IIR filter the same way. While this example sets `loggingmode` to `on`, you

# qreport

---

do that only once for a MATLAB session, unless you reset the mode to off during the session.

```
fipref('loggingmode','on');  
hd = design(fdesign.lowpass,'ellip');  
hd.arithmetic = 'fixed';  
y = filter(hd,rand(100,1));  
rlog = qreport(hd)
```

## See Also

[dfilt](#) | [mfilt](#)

**Purpose** Simulink subsystem block for filter

**Syntax** `realizemdl(hq)`  
`realizemdl(hq,Name,Value)`

**Description** `realizemdl(hq)` generates a model of filter `hq` in a Simulink subsystem block using sum, gain, and delay blocks from Simulink. The properties and values of `hq` define the resulting subsystem block parameters.

`realizemdl` requires Simulink. To accurately realize models of quantized filters, use Simulink Fixed-Point.

`realizemdl(hq,Name,Value)` generates the model for `hq` with additional options specified by one or more `Name,Value` pair arguments. Using name-value pair arguments lets you control more fully the way the block subsystem model gets built. You can specify such details as where the block goes, what the name is, or how to optimize the block structure.

---

**Note** Subsystem filter blocks that you use `realizemdl` to create support sample-based input and output only. You cannot input or output frame-based signals with the block.

---

## Input Arguments

### `hq`

One of the following types of filter object or filter System object:

- Discrete-time filter (`dfilt`) object
- Multirate filter (`mfilt`) object.
- Filter System object. The function supports the following structures:
  - `dsp.FIRFilter`
  - `dsp.BiquadFilter`
  - `dsp.FIRInterpolator`

- dsp.CICInterpolator
- dsp.FIRDecimator
- dsp.CICDecimator
- dsp.FIRRateConverter

## Name-Value Pair Arguments

### Destination

'current' (default) | 'new' | subsystemname

Specify whether to add the block to your current Simulink model or create a new model to contain the block. If you provide the name of a current subsystem in *subsystemname*, `realizemdl` adds the new block to the specified subsystem.

### Blockname

'filter' (default)

Provide the name for the new subsystem block. By default the block is named Filter.

### MapCoeffstoPorts

'off' (default) | 'on'

Specify whether to map the coefficients of the filter to the ports of the block.

### MapStates

'off' (default) | 'on'

Specify whether to apply the current filter states to the realized model. Such specification allows you to save states from a filter object you may have used or configured in a specific way. The default setting of 'off' means the states are not transferred to the model. Setting the property to 'on' preserves the current filter states in the realized model.

### OverwriteBlock

'off' (default) | 'on'

Specify whether to overwrite an existing block with the same name or create a new block.

**OptimizeZeros**

'off' (default) | 'on'

Specify whether to remove zero-gain blocks.

**OptimizeOnes**

'off' (default) | 'on'

Specify whether to replace unity-gain blocks with direct connections.

**OptimizeNegOnes**

'off' (default) | 'on'

Specify whether to replace negative unity-gain blocks with a sign change at the nearest sum block.

**OptimizeDelayChains**

'off' (default) | 'on'

Specify whether to replace delay chains made up of  $n$  unit delays with a single delay by  $n$ .

**CoeffNames**

{ 'Num' } (default FIR) | { 'Num', 'Den' } (default direct form IIR) |  
{ 'Num', 'Den', 'g' } (default IIR SOS) | { 'Num\_1', 'Num\_2', 'Num\_3' ... }  
(default multistage) | { 'K' } (default form lattice)

Specify the coefficient variable names as string variables in a cell array. MapCoeffsToPorts must be set to 'on' for this property to apply.

**InputProcessing**

'columns as channels' (default) | 'elements as channels' |  
'inherited'

Specify sample-based ('elements as channels') or frame-based ('columns as channels') processing.

---

**Note** The `inherited` option will be removed in a future release.

---

## RateOption

'enforce single rate' (default) | 'allow multirate'

Specify how the block adjusts the rate at the output to accommodate the reduced number of samples. This parameter applies only when `InputProcessing` is 'columns as channels'.

## Arithmetic

`double' | 'single' | 'fixed'

For filter System object inputs only, specify the arithmetic used during analysis. When you specify 'double' or 'single', the function performs double- or single-precision analysis. When you specify 'fixed', the arithmetic changes depending on the setting of the `CoefficientDataType` property and whether the System object is locked or unlocked.

## Details for Fixed-Point Arithmetic

System Object State	Coefficient Data Type	Rule
Unlocked	'Same as input'	The function assumes that the coefficient data type is signed, 16 bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Unlocked	'Custom'	The function performs fixed-point analysis based on the setting of the

System Object State	Coefficient Data Type	Rule
		CustomCoefficientsDataType property.
Locked	'Same as input'	When the input data type is 'double' or 'fixed', the function assumes that the coefficient data type is signed, 16-bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Locked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.

When you do not specify the arithmetic for non-CIC structures, the function uses double-precision arithmetic if the filter System object is in an unlocked state. If the System object is locked, the function performs analysis based on the locked input data type. CIC structures only support fixed-point arithmetic.

## Examples


Realize Simulink model of lowpass Butterworth filter:

```
d = fdesign.lowpass('N,F3dB',4,0.25);
Hd = design(d,'butter');
realizemdl(Hd);
```

The realized model is shown in the figure:

# realizemdl

---



Realize Simulink model with coefficients mapped to ports:

```
d = fdesign.lowpass('N,F3dB',4,0.25);  
Hd = design(d,'butter');  
%Realize Simulink model and export coefficients  
realizemdl(Hd,'MapCoeffsToPorts','on');
```

In this case, the filter is an IIR filter with a direct form II second-order sections structure. Setting `MapCoeffstoPorts` to 'on' exports the numerator coefficients, the denominator coefficients, and the gains to the MATLAB workspace using the default variable names `Num`, `Den`, and `g`. Each column of `Num` and `Den` represents one second-order section. You can modify the filter coefficients directly in the MATLAB workspace providing tunability to the realized Simulink model.

## See Also

[design](#) | [fdesign](#)

<b>Purpose</b>	Number of samples of delay introduced by buffering and unbuffering operations
<b>Syntax</b>	<pre>d = rebuffer_delay(f,n,v) d = rebuffer_delay(f,n,v,'mode')</pre>
<b>Description</b>	<p><code>d = rebuffer_delay(f,n,v)</code> returns the delay, in samples, introduced by the Buffer or Unbuffer block in multitasking operations.</p> <p><code>d = rebuffer_delay(f,n,v,'mode')</code> returns the delay, in samples, introduced by the Buffer or Unbuffer block in the specified tasking mode.</p>
<b>Input Arguments</b>	<p><b>f</b> Frame size of the input to the Buffer or Unbuffer block.</p> <p><b>n</b> Size of the output buffer. Specify one of the following:</p> <ul style="list-style-type: none"><li>• The value of the <b>Output buffer size</b> parameter, if you are computing the delay introduced by a Buffer block.</li><li>• 1, if you are computing the delay introduced by an Unbuffer block.</li></ul> <p><b>v</b> Amount of buffer overlap. Specify one of the following:</p> <ul style="list-style-type: none"><li>• The value of the <b>Buffer overlap</b> parameter, if you are computing the delay introduced by a Buffer block.</li><li>• 0, if you are computing the delay introduced by an Unbuffer block.</li></ul> <p><b>'mode'</b> The tasking mode of the model. Specify one of the following options:</p> <ul style="list-style-type: none"><li>• 'singletasking'</li><li>• 'multitasking'</li></ul>

**Default:** 'multitasking'

## **Definitions**      **Multitasking**

When you run a model in `MultiTasking` mode, Simulink processes groups of blocks with the same execution priority through each stage of simulation based on task priority. Multitasking mode helps to create valid models of real-world multitasking systems, where sections of your model represent concurrent tasks. The **Tasking mode for periodic sample times** parameter on the Solver pane of the Configuration Parameters dialog box controls this setting.

## **Singletasking**

When you run a model in `SingleTasking` mode, Simulink processes all blocks through each stage of simulation together. The **Tasking mode for periodic sample times** parameter on the Solver pane of the Configuration Parameters dialog box controls this setting.

## **Examples**

Compute the delay introduced by a Buffer block in a multitasking model:

- 1** Open a model containing a Buffer block. For this example, open the `ex_buffer_tut4` model by typing `ex_buffer_tut4` at the MATLAB command line.
- 2** Double-click the Buffer block to open the block mask. Verify that you have the following settings:
  - **Output buffer size** = 3
  - **Buffer overlap** = 1
  - **Initial conditions** = 0

Based on these settings, two of the required inputs to the `rebuffer_delay` function are as follows:

- `n` = 3
- `v` = 1

**3** To determine the frame size of the input signal to the Buffer block, open the Signal From Workspace block mask. Verify that you have the following settings:

- **Signal** = sp\_examples\_src
- **Sample time** = 1
- **Samples per frame** = 4

Because **Samples per frame** = 4, you know the `f` input to the `rebuffer_delay` function is 4.

**4** After you verify the values of all the inputs to the `rebuffer_delay` function, determine the delay that the Buffer block introduces in this multitasking model. To do so, type the following at the MATLAB command line:

```
d = rebuffer_delay(4,3,1)
```

```
d =  
    8
```

---

Compute the delay introduced by an Unbuffer block in a multitasking model:

- 1** Open a model containing an Unbuffer block. For this example, open the `ex_unbuffer_ref1` model by typing `ex_unbuffer_ref1` at the MATLAB command line.
- 2** To determine the frame size of the input to the Buffer block, open the Signal From Workspace block mask by double-clicking the block in your model. Verify that you have the following settings:
  - **Signal** = sp\_examples\_src
  - **Sample time** = 1
  - **Samples per frame** = 3

# rebuffer\_delay

---

Because **Samples per frame** = 3, you know the  $f$  input to the `rebuffer_delay` function is 3.

- 3 Use the `rebuffer_delay` function to determine the amount of delay that the Unbuffer block introduces in this multitasking model. To compute the delay introduced by the Unbuffer block, use  $f = 3$ ,  $n = 1$  and  $v = 0$ .

```
d = rebuffer_delay(3,1,0)
```

```
d =  
    3
```

## See Also

Buffer | Unbuffer

## How To

- “Buffer Delay and Initial Conditions”

**Purpose**

Reference filter for fixed-point or single-precision filter

**Syntax**

```
href = reffilter(hd)
```

**Description**

`href = reffilter(hd)` returns a new filter `href` that has the same structure as `hd`, but uses the reference coefficients and has its arithmetic property set to `double`. Note that `hd` can be either a fixed-point filter (arithmetic property set to `'fixed'`, or a single-precision floating-point filter whose arithmetic property is `'single'`).

`reffilter(hd)` differs from `double(hd)` in that

- the filter `href` returned by `reffilter` has the reference coefficients of `hd`.
- `double(hd)` returns the quantized coefficients of `hd` represented in double-precision.

To check the performance of your fixed-point filter, use `href = reffilter(hd)` to quickly have the floating-point, double-precision version of `hd` available for comparison.

**Examples**


Compare several fixed-point quantizations of a filter with the same double-precision floating-point version of the filter.

```
h = dfilt.dffir(firceqrip(87,.5,[1e-3,1e-6])); % Lowpass filter.
h1 = copy(h); h2 = copy(h); % Create copies of h.
h.arithmetic = 'fixed'; % Set h to filter using fixed-point...
% arithmetic.
h1.arithmetic = 'fixed'; % Same for h1.
h2.arithmetic = 'fixed'; % Same for h2.
h.CoeffWordLength = 16; % Use 16 bits to represent the...
% coefficients.
h1.CoeffWordLength = 12; % Use 12 bits to represent the...
% coefficients.
h2.CoeffWordLength = 8; % Use 8 bits to represent the...
% coefficients.

href = reffilter(h);
hfvt = fvtool(href,h,h1,h2);
```

```
set(hfvt,'ShowReference','off'); % Reference displayed once  
                                % already.  
legend(hfvt,'Reference filter','16-bits','12-bits','8-bits');
```

The following plot, taken from FVTool, shows href, the reference filter, and the effects of using three different word lengths to represent the coefficients.



As expected, the fidelity of the fixed-point filters suffers as you change the representation of the coefficients. With href available, it is easy to see just how the fixed-point filter compares to the ideal.

## See Also

double

**Purpose**

Rearrange sections in SOS filter

**Syntax**

```
reorder(hd,order)
reorder(hd,numorder,denorder)
reorder(hd,numorder,denorder,svorder)
reorder(hd,filter_type)
reorder(hd,dir_flag)
reorder(hd,dir_flag,sv)
reorder(hs,...)
reorder(hs,...,Name,Value)
```

**Description**

`reorder(hd,order)` rearranges the sections of filter `hd` using the vector of indices provided in `order`.

`reorder(hd,numorder,denorder)` reorders the numerator and denominator separately using the vectors of indices in `numorder` and `denorder`.

`reorder(hd,numorder,denorder,svorder)` specifies that the scale values can be independently reordered.

`reorder(hd,filter_type)` reorders `hd` in a way suitable for the specified filter type. This reordering mode can be especially helpful for fixed-point implementations where the order of the filter sections can significantly affect your filter performance.

`reorder(hd,dir_flag)` specifies rearranges the sections according to proximity to the origin of the poles of the sections.

`reorder(hd,dir_flag,sv)` reorders scale values in addition to rearranging sections according to pole-origin proximity.

`reorder(hs,...)` rearranges the sections of the filter System object `hs` according to any of the preceding input arguments.

`reorder(hs,...,Name,Value)` rearranges the sections of the filter System object `hs` with additional options specified by one or more `Name,Value` pair arguments.

# reorder

---

## Input Arguments

### **hd**

Discrete-time `dfilt.df1sos`, `dfilt.df2tsos`, `dfilt.df2sos`, or `dfilt.df1tsosfilter` object.

### **hs**

`dsp.BiquadFilter` filter System object.

### **order**

Vector of indices used to reorder the filter sections. `order` does not need to contain all of the indices of the filter. Omitting one or more filter section indices removes the omitted sections from the filter. You can use a logical array to remove sections from the filter, but not to reorder it.

### **numorder**

Vector of indices used to reorder the numerator. `numorder` and `denorder` must be the same length.

### **denorder**

Vector of indices used to reorder the denominator. `numorder` and `denorder` must be the same length.

### **svorder**

Independent reordering of scale values. When `svorder` is not specified, the scale values are reordered with the numerator. The output scale value always remains on the end when you use the argument `numorder` to reorder the scale values.

### **filter\_type**

'auto' | 'bandpass' | 'bandstop' | 'highpass' | 'lowpass'

Filter type. The 'auto' option and automatic ordering only apply to filters that you used `fdesign` to create. With the 'auto' option as an input argument, `reorder` automatically rearranges the filter sections depending on the specification response type of the design.

**dir\_flag**`'down' | 'up'`

Pole direction flag. When `dir_flag` is 'up', the first filter section contains the poles closest to the origin, and the last section contains the poles closest to the unit circle. When `ir_flag` is 'down', the sections are ordered in the opposite direction. `reorder` always pairs zeros with the poles closest to them.

**sv**`'poles' | 'zeros'`

Reorder scale values according to poles or zeros. By default the scale values are not reordered when you use the `dir_flag` input argument.

**Name-Value Pair Arguments**

Specify optional comma-separated pairs of `Name,Value` arguments, where `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1,Value1,...,NameN,ValueN`.

**Arithmetic**``double' | 'single' | 'fixed'`

For filter System object inputs only, specify the arithmetic used during analysis. When you specify 'double' or 'single', the function performs double- or single-precision analysis. When you specify 'fixed', the arithmetic changes depending on the setting of the `CoefficientDataType` property and whether the System object is locked or unlocked.

## Details for Fixed-Point Arithmetic

System Object State	Coefficient Data Type	Rule
Unlocked	'Same as input'	The function assumes that the coefficient data type is signed, 16 bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Unlocked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.
Locked	'Same as input'	When the input data type is 'double' or 'fixed', the function assumes that the coefficient data type is signed, 16-bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Locked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.

When you do not specify the arithmetic, the function uses double-precision arithmetic if the filter System object is in an unlocked state. If the System object is locked, the function performs analysis based on the locked input data type.

## Examples

Being able to rearrange the order of the sections in a filter can be a powerful tool for controlling the filter process. This example uses `reorder` to change the sections of a `df2sos` filter. Let `reorder` do the reordering automatically in the first example. In the second, use `reorder` to specify the new order for the sections.

First use the automatic reordering option on a lowpass filter.

```
d = fdesign.lowpass('n,f3db',15,0.75);
hd = design(d,'butter');
hdreorder=reorder(hd,'auto');
```

For another example of using `reorder`, create an SOS filter in the direct form II implementation.

```
[z,p,k] = butter(15,.5);
[sos, g] = zp2sos(z,p,k);
hd = dfilt.df2sos(sos,g);
reorder(hd, [1 3:7 2 8]);
hfvt = fvtool(hd, 'analysis', 'coefficients');
```

Reorder the sections by moving the second section to be between the seventh and eighth sections.

```
reorder(hd, [1 3:7 2 8]);
hfvt = fvtool(hd, 'analysis', 'coefficients');
```

Remove the third, fourth, and seventh sections.

```
hd1 = copy(hd);
reorder(hd1, logical([1 1 0 0 1 1 0 1]));
setfilter(hfvt, hd1);
```

Move the first filter to the end, and remove the eighth section

# reorder

---

```
hd2 = copy(hd);  
reorder(hd2, [2:7 1]);  
setfilter(hfvt, hd2);
```

Move the numerator and denominator independently.

```
hd3 = copy(hd);  
reorder(hd3, [1 3:8 2], [1:8]);  
setfilter(hfvt, hd3);
```

## References

Schlichthärle, Dietrich, *Digital Filters Basics and Design*, Springer-Verlag Berlin Heidelberg, 2000.

## See Also

[cumsec](#) | [scale](#) | [scaleopts](#)

---

<b>Purpose</b>	Reset filter properties to initial conditions
<b>Syntax</b>	<code>reset(ha)</code> <code>reset(hd)</code> <code>reset(hm)</code>
<b>Description</b>	<p><code>reset(ha)</code> resets all the properties of the adaptive filter <code>ha</code> that are updated when filtering to the value specified at construction. If you do not specify a value for any particular property when you construct an adaptive filter, the property value for that property is reset to the default value for the property.</p> <p><code>reset(hd)</code> resets all the properties of the discrete-time filter <code>hd</code> to their factory values that are modified when you run the filter. In particular, the <code>States</code> property is reset to zero.</p> <p><code>reset(hm)</code> resets all the properties of the multirate filter <code>hm</code> to their factory value that are modified when the filter is run. In particular, the <code>States</code> property is reset to zero when <code>hm</code> is a decimator. Additionally, the filter internal properties are also reset to their factory values.</p>
<b>Examples</b>	<p>Denoise a sinusoid and reset the filter after filtering with it.</p> <pre>h = adaptfilt.lms(5,.05,1,[0.5,0.5,0.5,0.5,0.5]); n = filter(1,[1 1/2 1/3],.2*randn(1,2000)); d = sin((0:1999)*2*pi*0.005) + n; % Noisy sinusoid x = n; [y,e]= filter(h,x,d);           % e has denoised signal disp(h) reset(h); % Reset the coefficients and states. disp(h)</pre>
<b>See Also</b>	<code>set</code>

# scale

---

## Purpose

Scale sections of SOS filter

## Syntax

```
scale(hd)
scale(hd,pnorm)
scale(hd,pnorm,Name,Value)
scale(hd,pnorm,opts)
scale(hs)
```

## Description

`scale(hd)` scales the second-order section filter `hd` using peak magnitude response scaling (L-infinity, 'Linf'). This scaling reduces the possibility of overflows when your filter `hd` operates in fixed-point arithmetic mode.

`scale(hd,pnorm)` specifies the norm used to scale the filter.

`scale(hd,pnorm,Name,Value)` scales the SOS filter with additional options specified by one or more `Name,Value` pair arguments.

`scale(hd,pnorm,opts)` uses an input scale options object `opts` to specify the optional scaling parameters instead of specifying parameter-value pairs.

`scale(hs)` scales the filter System object `hs`. You can also use `pnorm`, name-value pair arguments, or scale option objects with this syntax.

## Input Arguments

### hd

Discrete-time `dfilt` filter object.

With the `Arithmetic` property of `hd` set to `double` or `single`, the filter uses the default values for all options that you do not specify explicitly. When you set `Arithmetic` to `fixed`, the values used for the scaling options are set according to the settings in filter `hd`. However, if you specify a scaling option different from the settings in `hd`, the filter uses your explicit option selection for scaling purposes, but does not change the property setting in `hd`.

### hs

`dsp.BiquadFilter` filter System object.

**pnorm**

'l1' | 'l2' | 'linf' | 'L1' | 'L2' | 'Linf' (default)

Discrete-time-domain norm or a frequency-domain norm.

Valid time-domain norm values for `pnorm` are 'l1', 'l2', and 'linf'. Valid frequency-domain norm values are 'L1', 'L2', and 'Linf'. The 'L2' norm is equal to the 'l2' norm (by Parseval's theorem), but this equivalency does not hold for other norms — 'l1' is not the same as 'L1' and 'Linf' is not the same as 'linf'.

Filter norms can be ordered in terms of how stringent they are, as follows from most stringent to least: 'l1', 'Linf', 'l2' ('L2'), 'linf'. Using 'l1', the most stringent scaling, produces a filter that is least likely to overflow, but has the worst signal-to-noise ratio performance. The default scaling 'Linf' is the most commonly used scaling norm.

**opts**

Scale options object. You can create the `opts` object using the `scalects` function.

**Name-Value Pair Arguments**

Specify optional comma-separated pairs of `Name`, `Value` arguments, where `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

**Arithmetic**

'double' | 'single' | 'fixed'

For filter `System` object inputs only, specify the arithmetic used during analysis. When you specify 'double' or 'single', the function performs double- or single-precision analysis. When you specify 'fixed', the arithmetic changes depending on the setting of the `CoefficientDataType` property and whether the `System` object is locked or unlocked.

## Details for Fixed-Point Arithmetic

System Object State	Coefficient Data Type	Rule
Unlocked	'Same as input'	The function assumes that the coefficient data type is signed, 16 bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Unlocked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.
Locked	'Same as input'	When the input data type is 'double' or 'fixed', the function assumes that the coefficient data type is signed, 16-bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Locked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.

When you do not specify the arithmetic, the function uses double-precision arithmetic if the filter System object is in an unlocked state. If the System object is locked, the function performs analysis based on the locked input data type.

**MaxNumerator**

Maximum allowed value for numerator coefficients.

**Default:** 2

**MaxScaleValue**

Maximum allowed scale values. The filter applies the MaxScaleValue limit only when you set ScaleValueConstraint to a value other than unit (the default setting). Setting MaxScaleValue to any numerical value automatically changes the ScaleValueConstraint setting to none.

**Default:** 'Not Used'

**NumeratorConstraint**

'none' (default) | 'normalize' | 'po2' | 'unit'

Specifies whether and how to constrain numerator coefficient values.

**OverflowMode**

satall | saturate | wrap (default)

Sets the way the filter handles arithmetic overflow situations during scaling. If your device does not have guard bits available, and you are using saturation arithmetic for filtering, use 'satall' instead of 'saturate'.

**ScaleValueConstraint**

'none' | 'po2' | 'unit' (default)

Specify whether to constrain the filter scale values, and how to constrain them. Choosing 'unit' for the constraint disables the MaxScaleValue

# scale

---

property setting. 'po2' constrains the scale values to be powers of 2, while 'none' removes any constraint on the scale values.

## **sosReorder**

auto (default) | down | none | up

Reorder filter sections prior to applying scaling.

## **Examples**

Demonstrate the Linf-norm scaling of a lowpass elliptic filter with second-order sections. Start by creating a lowpass elliptical filter in zero, pole, gain (z,p,k) form.

```
[z,p,k] = ellip(5,1,50,.3);  
[sos,g] = zp2sos(z,p,k);  
hd = dfilt.df2sos(sos,g);  
scale(hd,'linf','scalevalueconstraint','none','maxscalevalue',2)
```

## **References**

Dehner, G.F. "Noise Optimized Digital Filter Design: Tutorial and Some New Aspects." *Signal Processing*. Vol. 83, Number 8, 2003, pp. 1565–1582.

## **See Also**

cumsec | norm | reorder | scalecheck | scaleopts

<b>Purpose</b>	Check scaling of SOS filter
<b>Syntax</b>	<pre>s = scalecheck(hd,pnorm) s = scalecheck(hs,pnorm) s = scalecheck(hs,pnorm,Name,Value)</pre>
<b>Description</b>	<p><code>s = scalecheck(hd,pnorm)</code> checks the scaling second-order section (SOS) <code>dfilt</code> filter object <code>hd</code>.</p> <p><code>s = scalecheck(hs,pnorm)</code> checks the scaling of the filter System object <code>hs</code>.</p> <p><code>s = scalecheck(hs,pnorm,Name,Value)</code> checks the scaling of the filter System object <code>hs</code> with additional options specified by one or more <code>Name,Value</code> pair arguments.</p>
<b>Input Arguments</b>	<p><b>hd</b></p> <p>Discrete-time <code>dfilt.df1sos</code>, <code>dfilt.df2tsos</code>, <code>dfilt.df2sos</code>, or <code>dfilt.df1tsosfilter</code> object.</p> <p><b>hs</b></p> <p><code>dsp.BiquadFilter</code> filter System object.</p> <p><b>pnorm</b></p> <p>'l1'   'l2'   'linf'   'L1'   'L2'   'Linf'</p> <p>Discrete-time-domain norm or a frequency-domain norm.</p> <p>Valid time-domain norm values for <code>pnorm</code> are 'l1', 'l2', and 'linf'. Valid frequency-domain norm values are 'L1', 'L2', and 'Linf'. The 'L2' norm is equal to the 'l2' norm (by Parseval's theorem), but this equivalency does not hold for other norms — 'l1' is not the same as 'L1' and 'Linf' is not the same as 'linf'.</p> <p><b>Name-Value Pair Arguments</b></p> <p>Specify optional comma-separated pairs of <code>Name,Value</code> arguments, where <code>Name</code> is the argument name and <code>Value</code> is the corresponding</p>

value. Name must appear inside single quotes ( ' '). You can specify several name and value pair arguments in any order as Name1,Value1,...,NameN,ValueN.

## Arithmetic

`'double' | 'single' | 'fixed'`

For filter System object inputs only, specify the arithmetic used during analysis. When you specify 'double' or 'single', the function performs double- or single-precision analysis. When you specify 'fixed', the arithmetic changes depending on the setting of the CoefficientDataType property and whether the System object is locked or unlocked.

## Details for Fixed-Point Arithmetic

System Object State	Coefficient Data Type	Rule
Unlocked	'Same as input'	The function assumes that the coefficient data type is signed, 16 bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Unlocked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.

System Object State	Coefficient Data Type	Rule
Locked	'Same as input'	When the input data type is 'double' or 'fixed', the function assumes that the coefficient data type is signed, 16-bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Locked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.

When you do not specify the arithmetic, the function uses double-precision arithmetic if the filter System object is in an unlocked state. If the System object is locked, the function performs analysis based on the locked input data type.

## Output Arguments

### s

Filter scaling for a given p-norm. An optimally scaled filter has partial norms equal to one. In such cases, **s** contains all ones.

For direct-form I (`dfilt.df1sos`) and direct-form II transposed (`dfilt.df2tsos`) filters, the function returns the p-norm of the filter computed from the filter input to the output of each second-order section. Therefore, the number of elements in **s** is one less than the number of sections in the filter. This p-norm computation does not include the trailing scale value of the filter, which you can find by entering `hd.scalevalue(end)` at the MATLAB prompt.

For direct-form II (`dfilt.df2sos`) and direct-form I transposed (`dfilt.df1tsos`) filters, the function returns a row vector whose elements contain the p-norm from the filter input to the input of the recursive part of each second-order section. This computation of the p-norm corresponds to the input to the multipliers in these filter structures. These inputs correspond to the locations in the signal flow where overflow should be avoided.

When `hd` has nontrivial scale values, that is, if any scale values are not equal to one, `s` is a two-row matrix, rather than a vector. The first row elements of `s` report the p-norm of the filter computed from the filter input to the output of each second-order section. The elements of the second row of `s` contain the p-norm computed from the input of the filter to the input of each scale value between the sections. For `df2sos` and `df1tsos` filter structures, the last numerator and the trailing scale value for the filter are not included when `scalecheck` checks the scaling.

## Examples

Check the Linf-norm scaling of a filter.

```
% Create filter design specifications
hs = fdesign.lowpass;
object.
hd = ellip(hs);           % Design an elliptic sos filter
scale(hd, 'Linf');
s = scalecheck(hd, 'Linf')
```

In another form:

```
[b,a]=ellip(10,.5,20,0.5);
[s,g]=tf2sos(b,a);
hd=dfilt.df1sos(s,g)
```

```
hd =
```

```
FilterStructure: 'Direct-Form I, Second-Order Sections'
Arithmetic: 'double'
sosMatrix: [5x6 double]
ScaleValues: [6x1 double]
```

```
PersistentMemory: false
      States: [1x1 filtstates.dfiir]

1x1 struct array with no fields.

scalecheck(hd, 'Linf')

ans =

    0.7631    0.9627    0.9952    0.9994    1.0000
```

## See Also

[norm](#) | [reorder](#) | [scale](#) | [scaleopts](#)

# scaleopts

---

**Purpose** Options for scaling SOS filter

**Syntax**

```
opts = scaleopts(hd)
opts = scaleopts(hs)
opts = scaleopts(hs,Name,Value)
```

**Description** `opts = scaleopts(hd)` uses the current settings in the `dfilt` filter `hd` to create an options object `opts` that contains specified scaling options for second-order section scaling. You can pass `opts` as an input to `scale` to apply scaling settings to a second-order filter.

`opts = scaleopts(hs)` creates an options object based on the current settings of the filter System object `hs`.

`opts = scaleopts(hs,Name,Value)` creates an options object with additional options specified by one or more `Name,Value` pair arguments.

## Input Arguments

### **hd**

Discrete-time `dfilt.df1sos`, `dfilt.df2tsos`, `dfilt.df2sos`, or `dfilt.df1tsosfilter` object.

### **hs**

`dsp.BiquadFilter` filter System object.

## **Name-Value Pair Arguments**

Specify optional comma-separated pairs of `Name,Value` arguments, where `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes ( ' '). You can specify several name and value pair arguments in any order as `Name1,Value1,...,NameN,ValueN`.

### **Arithmetic**

`'double'` | `'single'` | `'fixed'`

For filter System object inputs only, specify the arithmetic used during analysis. When you specify `'double'` or `'single'`, the function

performs double- or single-precision analysis. When you specify 'fixed', the arithmetic changes depending on the setting of the CoefficientDataType property and whether the System object is locked or unlocked.

**Details for Fixed-Point Arithmetic**

System Object State	Coefficient Data Type	Rule
Unlocked	'Same as input'	The function assumes that the coefficient data type is signed, 16 bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Unlocked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.
Locked	'Same as input'	When the input data type is 'double' or 'fixed', the function assumes that the coefficient data type is signed, 16-bit, and autoscaled. The function performs fixed-point analysis

# scaleopts

System Object State	Coefficient Data Type	Rule
		based on this assumption.
Locked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.

When you do not specify the arithmetic, the function uses double-precision arithmetic if the filter System object is in an unlocked state. If the System object is locked, the function performs analysis based on the locked input data type.

## Output Arguments

### opts

Scaling object. The following table lists the properties of opts.

Parameter	Default	Description and Valid Value
MaxNumerator	2	Maximum allowed value for numerator coefficients.
MaxScaleValue	No default value	Maximum allowed scale values. The filter applies the MaxScaleValue limit only when you set ScaleValueConstraint to a value other than unit. Setting MaxScaleValue to a numerical value automatically changes the ScaleValueConstraint setting to none.

Parameter	Default	Description and Valid Value
NumeratorConstraint	none	Specifies whether and how to constrain numerator coefficient values. Options are none, normalize, po2, and unit.
OverflowMode	wrap	Sets the way the filter handles arithmetic overflow situations during scaling. Choose one of wrap or saturate or satall.
ScaleValueConstraint	unit	Specify whether to constrain the filter scale values, and how to constrain them. Valid options are none, po2, and unit.

## Examples

From a filter `hd`, you can create an options scaling object that contains the scaling options settings you require.

```
[b,a]=ellip(10,.5,20,0.5);
[s,g]=tf2sos(b,a);
hd=dfilt.df1sos(s,g)
opts=scaleopts(hd)
```

```
opts =
```

```
    MaxNumerator: 2
  NumeratorConstraint: 'none'
    OverflowMode: 'wrap'
  ScaleValueConstraint: 'unit'
```

# scaleopts

---

MaxScaleValue: 'Not used'

## **See Also**

cumsec | norm | reorder | scale | scalecheck

**Purpose** Configure filter for integer filtering

**Syntax**

```
set2int(h)
set2int(h,coeffw1)
set2int(...,inw1)
g = set2int(...)
```

**Description** These sections apply to both discrete-time (`dfilt`) and multirate (`mfilt`) filters.

`set2int(h)` scales the filter coefficients to integer values and sets the filter coefficient and input fraction lengths to zero.

`set2int(h,coeffw1)` uses the number of bits specified by `coeffw1` as the word length it uses to represent the filter coefficients.

`set2int(...,inw1)` uses the number of bits specified by `coeffw1` as the word length it uses to represent the filter coefficients and the number of bits specified by `inw1` as the word length to represent the input data.

`g = set2int(...)` returns the gain `g` introduced into the filter by scaling the filter coefficients to integers. `g` is always calculated to be a power of 2.

---

**Note** `set2int` does not work with CIC decimators or interpolators because they do not have coefficients.

---

**Examples** These examples demonstrate some uses and ideas behind `set2int`.

The second parts of both examples depend on the following — after you filter a set of data, the input data and output data cover the same range of values, unless the filter process introduces gain in the output. Converting your filter object to integer form, and then filtering a set of data, does introduce gain into the system. When the examples refer to resetting the output to the same range as the input, the examples are accounting for this added gain feature.

## Discrete-Time Filter Example

Two parts comprise this example. Part 1 compares the step response of an FIR filter in both the fractional and integer filter modes. Fractional mode filtering is essentially the opposite of integer mode. Integer mode uses a filter which has coefficients represented by integers. Fractional mode filters have coefficients represented in fractional form (nonzero fraction length).

```
b = firrcos(100,.25,.25,2,'rolloff','sqrt');
hd = dfilt.dffir(b);
hd.Arithmetic = 'fixed';
hd.InputFracLength = 0; % Integer inputs.
x = ones(100,1);
yfrac = filter(hd,x); % Fractional mode output.
g = set2int(hd); % Convert to integer coefficients.
yint = filter(hd,x); % Integer mode output.
```

Note that `yint` and `yfrac` are `fi` objects. Later in this example, you use the `fi` object properties `WordLength` and `FractionLength` to work with the output data.

Now use the gain `g` to rescale the output from the integer mode filter operation. Verify that the scaled integer output is equal to the fractional output.

```
yints = double(yint)/g;
MaxDiff=max(abs(yints-double(yfrac)));
```

Verify that the scaled integer output is equal to the fractional output.

```
max(abs(yints-double(yfrac)))
```

In part two, the example reinterprets the output binary data, putting the input and the output on the same scale by weighting the most significant bits in the input and output data equally.

```
WL = yint.WordLength;
FL = yint.Fractionlength + log2(g);
```

```

yints2 = fi(zeros(size(yint)),true,WL,FL);
yints2.bin = yint.bin;
MaxDiff=max(abs(double(yints2)-double(yfrac)));

```

### Multirate Filter Example

This two-part example starts by comparing the step response of a multirate filter in both fractional and integer modes. Fractional mode filtering is essentially the opposite of integer mode. Integer mode uses a filter which has coefficients represented by integers. Fractional mode filters have coefficients in fractional form with nonzero fraction lengths.

```

hm = mfilt.firinterp;
hm.Arithmetic = 'fixed';
hm.InputFracLength = 0; % Integer inputs.
x = ones(100,1);
yfrac = filter(hm,x); % Fractional mode output.
g = set2int(hm); %Convert to integer coefficients.
yint = filter(hm,x); % Integer mode output.

```

Note that `yint` and `yfrac` are `fi` objects. In part 2 of this example, you use the `fi` object properties `WordLength` and `FractionLength` to work with the output data.

Now use the gain `g` to rescale the output from the integer mode filter operation.

```

yints = double(yint)/g;

```

Verify that the scaled integer output is equal to the fractional output.

```

max(abs(yints-double(yfrac)))

```

Part 2 demonstrates reinterpreting the output binary data by using the properties of `yint` to create a scaled version of `yint` named `yints2`. This process puts `yint` and `yints2` on the same scale by weighing the most significant bits of each object equally.

```

w1 = yint.wordlength;
f1 = yint.fractionlength + log2(g);

```

## set2int

---

```
yints2 = fi(zeros(size(yint)),true,wl,f1);  
yints2.bin = yint.bin;  
max(abs(double(yints2)-double(yfrac)))
```

### See Also

`mfilt`

<b>Purpose</b>	Specifications for filter specification object
<b>Syntax</b>	<pre>setspecs(D,specvalue1,specvalue2,...) setspecs(D,Specification,specvalue1,specvalue2,...) setspecs(...Fs) setspecs(...,MAGUNITS)</pre>
<b>Description</b>	<p><code>setspecs(D,specvalue1,specvalue2,...)</code> sets the specifications in filter specification object, <code>D</code>, in the same order they appear in the <code>Specification</code> property.</p> <p><code>setspecs(D,Specification,specvalue1,specvalue2,...)</code> changes the specifications for an existing filter specification object and sets values for the new <code>Specification</code> property.</p> <p><code>setspecs(...Fs)</code> specifies the sampling frequency, <code>Fs</code>, in Hz. The sampling frequency must be a scalar trailing all other specifications. Entering a sampling frequency causes all other frequency specifications to be in Hz.</p> <p><code>setspecs(...,MAGUNITS)</code> specifies the units for any magnitude specifications. <code>MAGUNITS</code> can be one of the following: 'linear', 'dB', or 'squared'. The default is 'dB'. The magnitude specifications are always converted and stored in dB regardless of how the units are specified.</p> <p>Use <code>SET(D,'SPECIFICATION')</code> to get the list of all available specification types for the filter specification object, <code>D</code>.</p>
<b>Examples</b>	<p>Construct a lowpass filter with specifications for the filter order and cutoff frequency (-6 dB). Use <code>setspecs</code> after construction to set the values of the filter order and cutoff frequency. Display the values in the MATLAB command window.</p> <pre>D = fdesign.lowpass('N,Fc'); setspecs(D,10,0.2); D.FilterOrder D.Fcutoff</pre>

## setspecs

---

---

Construct a highpass filter with specifications for the numerator order, denominator order, and 3-dB frequency. Assume the sampling frequency is 1 kHz. Use `setspecs` to set the numerator and denominator orders to 6. Set the 3-dB frequency to 250 Hz. In order to use frequency specifications in Hz, specify the sampling frequency as a trailing scalar.

```
D = fdesign.highpass('Nb,Na,F3dB');  
setspecs(D,6,6,250,1000);
```

### See Also

[design](#) | [designmethods](#) | [designopts](#) | [fdesign](#)

**Purpose**

Convert quantized filter to second-order sections (SOS) form

**Syntax**

```
Hq2 = sos(Hq)
Hq2 = sos(Hq, order)
Hq2 = sos(Hq, order, scale)
```

**Description**

`Hq2 = sos(Hq)` returns a quantized filter `Hq2` that has second-order sections and the `dft2` structure. Use the same optional arguments used in `tf2sos`.

`Hq2 = sos(Hq, order)` specifies the order of the sections in `Hq2`, where `order` is either of the following strings:

- 'down' — to order the sections so the first section of `Hq2` contains the poles closest to the unit circle ( $L_\infty$  norm scaling)
- 'up' — to order the sections so the first section of `Hq2` contains the poles farthest from the unit circle ( $L_2$  norm scaling and the default)

`Hq2 = sos(Hq, order, scale)` also specifies the desired scaling of the gain and numerator coefficients of all second-order sections, where `scale` is one of the following strings:

- 'none' — to apply no scaling (default)
- 'inf' — to apply infinity-norm scaling
- 'two' — to apply 2-norm scaling

Use infinity-norm scaling in conjunction with up-ordering to minimize the probability of overflow in the filter realization. Consider using 2-norm scaling in conjunction with down-ordering to minimize the peak round-off noise.

When `Hq` is a fixed-point filter, the filter coefficients are normalized so that the magnitude of the maximum coefficient in each section is 1. The gain of the filter is applied to the first scale value of `Hq2`.

`sos` uses the direct form II transposed (`dft2`) structure to implement second-order section filters.

## Examples

```
[b,a]=butter(8,.5);
Hq = dfilt.df2t(b,a);
Hq.arithmetic = 'fixed';
Hq1 = sos(Hq)

Hq1 =

    FilterStructure: 'Direct-Form II Transposed, Second-Order Sections'
    Arithmetic: 'double'
    sosMatrix: [4x6 double]
    ScaleValues: [0.00927734375;1;1;1;1]
    OptimizeScaleValues: true
    PersistentMemory: false
```

## See Also

[convert](#) | [dfilt](#) | [tf2sos](#)

**Purpose** Fixed-point scaling modes in direct-form FIR filter

**Syntax**

```
specifyall(hd)
specifyall(hd,false)
specifyall(hd,true)
specifyall(hs)
specifyall(hs,false)
```

**Description** `specifyall` sets all of the autoscale property values of direct-form FIR filters to `false` and all `*modes` of the filters to `SpecifyPrecision`. In this table, you see the results of using `specifyall` with direct-form FIR filters.

Property Name	Default	Setting After Applying <code>specifyall</code>
<code>CoeffAutoScale</code>	<code>true</code>	<code>false</code>
<code>OutputMode</code>	<code>AvoidOverflow</code>	<code>SpecifyPrecision</code>
<code>ProductMode</code>	<code>FullPrecision</code>	<code>SpecifyPrecision</code>
<code>AccumMode</code>	<code>KeepMSB</code>	<code>SpecifyPrecision</code>
<code>RoundMode</code>	<code>convergent</code>	<code>convergent</code>
<code>OverflowMode</code>	<code>wrap</code>	<code>wrap</code>

`specifyall(hd)` gives you maximum control over all settings in a filter `hd` by setting all of the autoscale options that are `true` to `false`, turning off all autoscaling and resetting all modes — `OutputMode`, `ProductMode`, and `AccumMode` — to `SpecifyPrecision`. After you use `specifyall`, you must supply the property values for the mode- and scaling related properties.

`specifyall` provides an alternative to changing all these properties individually. Using `specifyall` changes all of the settings. To set some but not all of the modes, set each property as you require.

`specifyall(hd,false)` performs the opposite operation of `specifyall(hd)` by setting all of the autoscale options to `true`; all

# specifyall

---

of the modes to their default values; and hiding the fraction length properties in the display, meaning you cannot access them to set them or view them.

`specifyall(hd,true)` is equivalent to `specifyall(hd)`.

`specifyall(hs)` sets all the data type fixed-point properties of the filter System object `hs` to 'Custom' so that you can easily specify all the fixed-point settings. If the object has a `FullPrecisionOverride` property, its value is set to `false`. `specifyall` is intended as a shortcut to changing all the fixed-point properties one by one.

`specifyall(hs,false)` sets all fixed-point properties of the filter System object `hs` to their default values and sets the filter to full-precision mode, if possible.

## Examples

This example demonstrates using `specifyall` to provide access to all of the fixed-point settings of an FIR filter implemented with the direct-form structure. Using `specifyall` disables all of the automatic filter scaling and reset the mode values.

```
b = fircband(12,[0 0.4 0.5 1],[1 1 0 0],[1 0.2],{'w' 'c'});
hd = dfilt.dffir(b);
hd.arithmetic = 'fixed'
specifyall(hd)
```

The mode properties `InputMode`, `ProductMode`, and `AccumMode` have the value `SpecifyPrecision` and the fraction length properties appear in the display. Now you use the properties (`InputFracLength`, `ProdFracLength`, `AccumFracLength`) to set the precision the filter applies to the input, product, and accumulator operations. `CoeffAutoScale` switches to `false`, which means that the filter coefficients will not be scaled automatically to prevent overflows. None of the other filter properties change when you apply `specifyall`.

## See Also

`double` | `reffilter`

**Purpose**

Step response for filter

**Syntax**

```
[h,t] = stepz(hfilt)
[h,t] = stepz(hfilt,n)
[h,t] = stepz(hfilt,n,fs)
[h,t] = stepz(hfilt,[],fs)
stepz(hfilt)
[h,t] = stepz(hs)
[h,t] = stepz(hs,Name,Value)
stepz(hs)
```

**Description**

stepz returns the step response based on the current filter coefficients. This section describes common stepz operation with adaptive filters, discrete-time filters, multirate filters, and filter System objects. For more input options, refer to stepz in Signal Processing Toolbox documentation.

[h,t] = stepz(hfilt) returns the impulse response h and the corresponding time points w at which the step response of hfilt is computed. The step response is evaluated at 10 1-second intervals—(0:9) '.

[h,t] = stepz(hfilt,n) returns the step response evaluated at floor(n) 1-second intervals—(0:floor(n)-1) '.

[h,t] = stepz(hfilt,n,fs) returns the step response evaluated at floor(n) 1/fs-second intervals—(0:floor(n)-1) '/fs.

[h,t] = stepz(hfilt,[],fs) returns the step response evaluated at 10 1/fs-second intervals—(0:9) '/fs.

stepz(hfilt) uses FVTool to plot the step response of the filter. You can also provide the optional input arguments n and fs with this syntax.

[h,t] = stepz(hs) returns the step response for the filter System object hs. The impulse response is evaluated at 10 1-second intervals—(0:9) '. You can also provide the optional input arguments n and fs with this syntax.

`[h,t] = stepz(hs,Name,Value)` returns an step response with additional options specified by one or more `Name,Value` pair arguments.

`stepz(hs)` uses FVTool to plot the step response of the filter System object `hs`.

---

**Note** `stepz` works for both real and complex filters. When you omit the output arguments, `stepz` plots only the real part of the step response.

---

## Input Arguments

### `hfilter`

`hfilter` is either:

- An adaptive `adaptfilt`, discrete-time `dfilt`, or multirate `mfilt` filter object
- A vector of adaptive, discrete-time, or multirate filter objects

The multirate filter step response is computed relative to the rate at which the filter is running. When you specify `fs` (the sampling rate) as an input argument, `stepz` assumes the filter is running at that rate.

For multistage cascades, `stepz` forms a single-stage multirate filter that is equivalent to the cascade. It then computes the response relative to the rate at which the equivalent filter is running. `stepz` does not support all multistage cascades. The function analyzes only those cascades for which there exists an equivalent single-stage filter.

As an example, consider a 2-stage interpolator where the first stage has an interpolation factor of 2 and the second stage has an interpolation factor of 4. In this case, an equivalent single-stage filter exists with an overall interpolation factor of 8. `stepz` uses this equivalent filter for the analysis. If a sampling frequency `fs` is specified as an input argument to `stepz`, the function interprets `fs` as the rate at which the equivalent filter is running.

### `hs`

Filter System object. The function supports the following filter structures.

- `dsp.FIRFilter`
- `dsp.BiquadFilter`
- `dsp.FIRInterpolator`
- `dsp.CICInterpolator`
- `dsp.FIRDecimator`
- `dsp.CICDecimator`
- `dsp.FIRRateConverter`

**n**

Number of samples.

**Default:** 10

**fs**

Sampling frequency.

**Default:** 1

### **Name-Value Pair Arguments**

Specify optional comma-separated pairs of `Name, Value` arguments, where `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes ( ' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

### **Arithmetic**

`'double' | 'single' | 'fixed'`

For filter System object inputs only, specify the arithmetic used during analysis. When you specify `'double'` or `'single'`, the function performs double- or single-precision analysis. When you specify

'fixed', the arithmetic changes depending on the setting of the CoefficientDataType property and whether the System object is locked or unlocked.

**Details for Fixed-Point Arithmetic**

<b>System Object State</b>	<b>Coefficient Data Type</b>	<b>Rule</b>
Unlocked	'Same as input'	The function assumes that the coefficient data type is signed, 16 bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Unlocked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.
Locked	'Same as input'	When the input data type is 'double' or 'fixed', the function assumes that the coefficient data type is signed, 16-bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Locked	'Custom'	The function performs fixed-point

System Object State	Coefficient Data Type	Rule
		analysis based on the setting of the CustomCoefficientsDataType property.

When you do not specify the arithmetic for non-CIC structures, the function uses double-precision arithmetic if the filter System object is in an unlocked state. If the System object is locked, the function performs analysis based on the locked input data type. CIC structures only support fixed-point arithmetic.

## Output Arguments

### **h**

Complex,  $n$ -element step response vector. If `hfilt` is a vector of filters, `h` is a complex, `length(hfilt)`-by- $n$  matrix of step response vectors corresponding to each filter in `hfilt`. If  $n$  is not specified, the function uses a default value of 8192.

For adaptive filters, `h` is the instantaneous step response.

### **t**

Time vector of length  $n$ , in seconds. `t` consists of  $n$  points equally spaced from 0 to `floor(n) / fs`. If  $n$  is not specified, the function uses a default value of 10. If `fs` is not specified, the function uses a default value of 1.

## See Also

`freqz` | `impz`

# sysobj

---

**Purpose** Create filter System object from discrete-time filter or multirate filter

**Syntax** `hs = sysobj(hfilt)`

**Description** `hs = sysobj(hfilt)` creates a new filter System object `hs` from the `dfilt` or `mfilt` object, `hfilt`.

The function supports a subset of `dfilt` and `mfilt` objects. The following table lists supported filter structures for `hfilt` and the filter System object that the function creates.

Single-rate or multirate filter	Filter System object
Lattice AR( <code>dfilt.latticear</code> )	<code>dsp.AllpoleFilter</code>
Direct Form I ( <code>dfilt.df1</code> )	<code>dsp.IIRFilter</code>
Direct Form I transposed ( <code>dfilt.df1t</code> )	<code>dsp.IIRFilter</code>
Direct Form II ( <code>dfilt.df2</code> )	<code>dsp.IIRFilter</code>
Direct Form II transposed ( <code>dfilt.df2t</code> )	<code>dsp.IIRFilter</code>
Direct-form FIR ( <code>dfilt.dffir</code> )	<code>dsp.FIRFilter</code>
Direct-form FIR transposed ( <code>dfilt.dffirt</code> )	<code>dsp.FIRFilter</code>
Direct-form symmetric FIR ( <code>dfilt.dfsymfir</code> )	<code>dsp.FIRFilter</code>
Direct-form antisymmetric FIR ( <code>dfilt.dfasymfir</code> )	<code>dsp.FIRFilter</code>
Discrete-time, lattice, moving-average ( <code>dfilt.latticemamin</code> )	<code>dsp.FIRFilter</code>
Discrete-time, second-order section, direct-form I ( <code>dfilt.df1sos</code> )	<code>dsp.BiquadFilter</code>

Single-rate or multirate filter	Filter System object
Discrete-time, second-order section, direct-form I transposed (dfilt.df1tsos)	dsp.BiquadFilter
Discrete-time, second-order section, direct-form II (dfilt.df2sos)	dsp.BiquadFilter
Discrete-time, second-order section, direct-form II transposed (dfilt.df2tsos)	dsp.BiquadFilter
Direct-form FIR polyphase decimator (mfilt.firdecim)	dsp.FIRDecimator
Direct-form transposed FIR polyphase decimator (mfilt.firtdecim)	dsp.FIRDecimator
Fixed-point CIC decimator (mfilt.cicdecim)	dsp.CICDecimator
FIR polyphase interpolator (mfilt.firinterp)	dsp.FIRInterpolator
FIR linear interpolator (mfilt.linearinterp)	dsp.FIRInterpolator
Fixed-point CIC interpolator (mfilt.cicinterp)	dsp.CICInterpolator
Direct-form FIR polyphase sample rate converter (mfilt.firsrc)	dsp.FIRRateConverter

## Input Arguments

### hfilt

Discrete-time filter (dfilt) or multirate filter (mfilt) object. The preceding table lists supported filter structures.

The function interprets the `PersistentMemory` property differently for discrete-time and multirate filters:

- If `hfilt` is a discrete-time filter with the `PersistentMemory` property set to `true`, then the filter states are copied into the initial conditions properties of `hs`. Otherwise, initial conditions are ignored.
- Multirate-filter System objects do not have initial conditions. If `hfilt` is a multirate filter with the `PersistentMemory` property set to `true`, the initial conditions are not copied into `hs`, and the function issues a warning.

The function does not support some properties for SOS filter structures:

- If the `CastBeforeSum` property is set to `false`, the function issues a warning. `dsp.BiquadFilter` System objects always have a cast before a sum.
- If the `Signed` property is `false`, the function issues an error. `dsp.BiquadFilter` System objects do not support unsigned arithmetic.

## Output Arguments

### **hs**

Filter System object. The function maps almost all properties of `hfilt` into the filter System object. However, some properties are not mapped exactly:

- Filter System objects do not have a `CoeffAutoScale` property. The function specifies a word length and a fraction length regardless of whether the `CoeffAutoScale` property of `hfilt` is `true` or `false`.
- `dsp.BiquadFilter` System objects do not have a `FullPrecisionOverride` property. Full-precision values in `hfilt` are mapped to word and fraction lengths in `hs`. These settings correspond to the full-precision setting of the input data type.

## Examples

Convert a discrete-time filter object to a System object:

```
hfilt = dfilt.df1sos; %Direct-form I SOS
hs = sysobj(hfilt); %Biquadratic IIR filter
```

**See Also** block

**Purpose** Transfer function to coupled allpass

**Syntax** [d1,d2] = tf2ca(b,a)  
[d1,d2] = tf2ca(b,a)

**Description** [d1,d2] = tf2ca(b,a) where b is a real, symmetric vector of numerator coefficients and a is a real vector of denominator coefficients, corresponding to a stable digital filter, returns real vectors d1 and d2 containing the denominator coefficients of the allpass filters  $H1(z)$  and  $H2(z)$  such that

$$H(z) = \frac{B(z)}{A(z)} = \frac{1}{2[H1(z) + H2(z)]}$$

representing a coupled allpass decomposition.

[d1,d2] = tf2ca(b,a) where b is a real, antisymmetric vector of numerator coefficients and a is a real vector of denominator coefficients, corresponding to a stable digital filter, returns real vectors d1 and d2 containing the denominator coefficients of the allpass filters  $H1(z)$  and  $H2(z)$  such that

$$H(z) = \frac{B(z)}{A(z)} = \left(\frac{1}{2}\right)[H1(z) - H2(z)]$$

In some cases, the decomposition is not possible with real  $H1(z)$  and  $H2(z)$ . In those cases a generalized coupled allpass decomposition may be possible, whose syntax is

[d1,d2,beta] = tf2ca(b,a)

to return complex vectors d1 and d2 containing the denominator coefficients of the allpass filters  $H1(z)$  and  $H2(z)$ , and a complex scalar beta, satisfying  $|\text{beta}| = 1$ , such that

$$H(z) = \frac{B(z)}{A(z)} = \left(\frac{1}{2}\right)[\bar{\beta} \cdot H1(z) + \beta \cdot H2(z)]$$

representing the generalized allpass decomposition.

In the above equations,  $H1(z)$  and  $H2(z)$  are real or complex allpass IIR filters given by

$$H1(z) = \frac{\text{fliplr}(\overline{D1(z)})}{D1(z)}, H2(z) = \frac{\text{fliplr}(\overline{D2(1/z)})}{D2(1/z)}$$

where  $D1(z)$  and  $D2(z)$  are polynomials whose coefficients are given by  $d1$  and  $d2$ .

---

**Note** A coupled allpass decomposition is not always possible. Nevertheless, Butterworth, Chebyshev, and Elliptic IIR filters, among others, can be factored in this manner. For details, refer to Signal Processing Toolbox User's Guide.

---

## Examples

```
[b,a]=cheby1(9,.5,.4);
[d1,d2]=tf2ca(b,a); % TF2CA returns denominators of the allpass.
num = 0.5*conv(fliplr(d1),d2)+0.5*conv(fliplr(d2),d1);
den = conv(d1,d2); % Reconstruct numerator and denominator.
MaxDiff=max([max(b-num),max(a-den)]); % Compare original and reconstructed
% numerator and denominators.
```

## See Also

ca2tf | c12tf | iirpowcomp | latc2tf | tf2latc

**Purpose** Transfer function to coupled allpass lattice

**Syntax**  
[k1,k2] = tf2cl(b,a)  
[k1,k2] = tf2cl(b,a)

**Description** [k1,k2] = tf2cl(b,a) where b is a real, symmetric vector of numerator coefficients and a is a real vector of denominator coefficients, corresponding to a stable digital filter, will perform the coupled allpass decomposition

$$H(z) = \frac{B(z)}{A(z)} = \frac{1}{2[H1(z) + H2(z)]}$$

of a stable IIR filter  $H(z)$  and convert the allpass transfer functions  $H1(z)$  and  $H2(z)$  to a coupled lattice allpass structure with coefficients given in vectors k1 and k2.

[k1,k2] = tf2cl(b,a) where b is a real, antisymmetric vector of numerator coefficients and a is a real vector of denominator coefficients, corresponding to a stable digital filter, performs the coupled allpass decomposition

$$H(z) = \frac{B(z)}{A(z)} = \left(\frac{1}{2}\right)[H1(z) - H2(z)]$$

of a stable IIR filter  $H(z)$  and converts the allpass transfer functions  $H1(z)$  and  $H2(z)$  to a coupled lattice allpass structure with coefficients given in vectors k1 and k2.

In some cases, the decomposition is not possible with real  $H1(z)$  and  $H2(z)$ . In those cases, a generalized coupled allpass decomposition may be possible, using the command syntax

$$[k1,k2,beta] = tf2cl(b,a)$$

to perform the generalized allpass decomposition of a stable IIR filter  $H(z)$  and convert the complex allpass transfer functions  $H1(z)$  and  $H2(z)$  to corresponding lattice allpass filters

$$H(z) = \frac{B(z)}{A(z)} = \left(\frac{1}{2}\right) [\bar{\beta} \cdot H1(z) + \beta \cdot H2(z)]$$

where  $\beta$  is a complex scalar of magnitude equal to 1.

---

**Note** Coupled allpass decomposition is not always possible. Nevertheless, Butterworth, Chebyshev, and Elliptic IIR filters, among others, can be factored in this manner. For details, refer to Signal Processing Toolbox User's Guide.

---

## Examples

```
[b,a]=cheby1(9,.5,.4);
[k1,k2]=tf2c1(b,a); % Get the reflection coeffs. for the lattices.
[num1,den1]=latc2tf(k1,'allpass'); % Convert each allpass lattice
[num2,den2]=latc2tf(k2,'allpass'); % back to transfer function.
num = 0.5*conv(num1,den2)+0.5*conv(num2,den1);
den = conv(den1,den2); % Reconstruct numerator and denominator.
MaxDiff=max([max(b-num),max(a-den)]); % Compare original and reconstructed
% numerator and denominators.
```

## See Also

ca2tf | cl2tf | iirpowcomp | latc2tf | tf2ca | tf2latc

# validstructures

---

**Purpose** Structures for specification object with design method

**Syntax**

```
filtstruct = validstructures(D)
C = validstructures(D,METHOD)
Cs = validstructures(D,...,'SystemObject',sysobjflag)
```

**Description**

`filtstruct = validstructures(D)` returns a structure array containing all valid filter structures for the filter specification object, `D`, organized by design method. Each design method is a field in the structure array, `filtstruct`. The fields contain a cell array of strings.

`C = validstructures(D,METHOD)` returns the valid structures for the filter specification object, `D`, and the design method, `METHOD`, in a cell array of strings.

`Cs = validstructures(D,...,'SystemObject',sysobjflag)` returns the valid structures for designing a filter System object when `sysobjflag` is true. To use System objects, you must have the DSP System Toolbox product installed. When `sysobjflag` is false, the function returns valid structures for designing `dfilt` and `mfilt` objects, as described previously. Design methods and design options for filter System objects are not necessarily the same as those for `dfilt` and `mfilt` objects.

**Examples**

Design a default lowpass filter specification object. Return all valid design methods and structures in a structure array. Display the fieldnames to see all valid design methods. Display the valid filter structures for the `equiripple` field.

```
D = fdesign.lowpass;
filtstruct = validstructures(D);
fieldnames(filtstruct)
filtstruct.equiripple
```

---

Create a highpass filter of order 50 with a 3-dB frequency of 0.2. Obtain the available structures for a Butterworth design.

```
D = fdesign.highpass('N,F3dB',50,0.2);  
C = validstructures(D,'butter');
```

If you have DSP System Toolbox software installed, use the 'SystemObject', *sysobjflag* syntax to return valid structures for a filter System object:

```
Cs = validstructures(D,'butter','SystemObject',true);
```

## See Also

[design](#) | [designmethods](#) | [designopts](#) | [fdesign](#)

# window

---

**Purpose** FIR filter using windowed impulse response

**Syntax**  
`h = window(d,fcnhd1,fcarg)`  
`h = window(d,win)`

**description** `h = window(d,fcnhd1,fcarg)` designs an FIR filter using the specifications in filter specification object `d`. Depending on the specification type of `d`, the returned filter is either a single-rate digital filter — a `dfilt`, or a multirate digital filter — an `mfilt`.

`fcnhd1` is a handle to a filter design function that returns a window vector, such as the `hamming` or `blackman` functions. `fcarg` is an optional argument that returns a window. You pass the function to `window`. Refer to example 1 in the following section to see the function argument used to design the filter.


`h = window(d,win)` designs a filter using the vector you supply in `win`. The length of vector `win` must be the same as the impulse response of the filter, which is equal to the filter order plus one. Example 2 shows this being done.

**Examples** These examples design filters using the two design techniques of specifying a function handle or passing a window vector as an input argument.

## Example 1

Use a function handle and optional input arguments to design a multirate filter. We use a function handle to `hamming` to provide the window. Since this example creates a decimator filter specifications object, `window` returns a multirate filter.

```
d = fdesign.decimator(4,'lowpass','N,Fc',30,1000,10000);  
% Lowpass decimator with a 6-dB down frequency of 1 kHz  
% Order equal to 30 and sampling frequency 10 kHz  
Hd =window(d,'window',@hamming);  
fvtool(Hd)
```




## Example 2

Use a window vector provided by the kaiser window function to design a Nyquist filter. The window length must be the filter order plus one. .

```
d = fdesign.nyquist(5,'n',150);  
% Kaiser window with beta parameter 2.5  
Hd = window(d,'window',kaiser(151,2.5));  
fvtool(Hd)
```

# window



**See Also** [firls](#) | [kaiserwin](#)

**Purpose**

Zero-phase response for filter

**Syntax**

```
[hr,w] = zerophase(hfilt)
[hr,w] = zerophase(hfilt,n)
zerophase(hfilt)
[hr,w] = zerophase(hs)
[hr,w] = zerophase(hs,n)
[hr,w] = zerophase(hs,Name,Value)
zerophase(hs)
```

**Description**

`zerophase` returns the zero-phase response based on the current filter coefficients. This section describes common `zerophase` operation with adaptive, discrete-time, and multirate filters. For more input options, refer to `zerophase` in Signal Processing Toolbox documentation.

`[hr,w] = zerophase(hfilt)` returns the instantaneous zero-phase response `hr` and the frequencies `w` in radians at which `zerophase` evaluated the response. The zero-phase response is evaluated at 8192 points equally spaced around the upper half of the unit circle.

`[hr,w] = zerophase(hfilt,n)` returns the instantaneous zero-phase response `hr` and the frequencies `w` in radians at which `zerophase` evaluated the response. The zero-phase response is evaluated at `n` points equally spaced around the upper half of the unit circle.

`zerophase(hfilt)` displays the zero-phase response of `ha` in the Filter Visualization Tool (FVTool).

`[hr,w] = zerophase(hs)` returns a zero-phase response for the filter System object `hs` using 8192 samples.

`[hr,w] = zerophase(hs,n)` returns a zero-phase response for the filter System object `hs` using `n` samples.

`[hr,w] = zerophase(hs,Name,Value)` returns a zero-phase response with additional options specified by one or more `Name,Value` pair arguments.

`zerophase(hs)` uses FVTool to plot the zero-phase response of the filter System object `hs`.

## Input Arguments

### **hfilt**

`hfilt` is either:

- An adaptive `adaptfilt`, discrete-time `dfilt`, or multirate `mfilt` filter object
- A vector of adaptive, discrete-time, or multirate filter objects

The multirate filter zero-phase response is computed relative to the rate at which the filter is running. When you specify `fs` (the sampling rate) as an input argument, `zerophase` assumes the filter is running at that rate.

For multistage cascades, `zerophase` forms a single-stage multirate filter that is equivalent to the cascade. It then computes the response relative to the rate at which the equivalent filter is running. `zerophase` does not support all multistage cascades. The function analyzes only those cascades for which there exists an equivalent single-stage filter.

As an example, consider a 2-stage interpolator where the first stage has an interpolation factor of 2 and the second stage has an interpolation factor of 4. In this case, an equivalent single-stage filter exists with an overall interpolation factor of 8. `zerophase` uses this equivalent filter for the analysis. If a sampling frequency `fs` is specified as an input argument to `zerophase`, the function interprets `fs` as the rate at which the equivalent filter is running.

### **hs**

Filter System object. The function supports the following filter structures.

- `dsp.FIRFilter`
- `dsp.BiquadFilter`
- `dsp.FIRInterpolator`
- `dsp.CICInterpolator`
- `dsp.FIRDecimator`

- `dsp.CICDecimator`
- `dsp.FIRRateConverter`

**n**

Number of samples. For an FIR filter where `n` is a power of two, the computation is done faster using FFTs.

**Default:** 8192

**Name-Value Pair Arguments**

Specify optional comma-separated pairs of `Name,Value` arguments, where `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes ( ' '). You can specify several name and value pair arguments in any order as `Name1,Value1,...,NameN,ValueN`.

**Arithmetic**

`'double' | 'single' | 'fixed'`

For filter System object inputs only, specify the arithmetic used during analysis. When you specify `'double'` or `'single'`, the function performs double- or single-precision analysis. When you specify `'fixed'`, the arithmetic changes depending on the setting of the `CoefficientDataType` property and whether the System object is locked or unlocked.

## Details for Fixed-Point Arithmetic

System Object State	Coefficient Data Type	Rule
Unlocked	'Same as input'	The function assumes that the coefficient data type is signed, 16 bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Unlocked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.
Locked	'Same as input'	When the input data type is 'double' or 'fixed', the function assumes that the coefficient data type is signed, 16-bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Locked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.

When you do not specify the arithmetic for non-CIC structures, the function uses double-precision arithmetic if the filter System object is in an unlocked state. If the System object is locked, the function performs analysis based on the locked input data type. CIC structures only support fixed-point arithmetic.

## Output Arguments

### **hr**

Complex, n-element zero-phase response vector. If `hfilt` is a vector of filters, `hr` is a complex, `length(hfilt)`-by-`n` matrix of phase response vectors whose columns correspond to each filter in `hfilt`. If `n` is not specified, the function uses a default value of 8192.

For adaptive filters, `hr` is the instantaneous zero-phase response.

### **w**

Frequency vector of length `n`, in radians/sample. `w` consists of `n` points equally spaced around the upper half of the unit circle (from 0 to  $\pi$  radians/sample). If `hfilt` is a vector of filters, `w` is a complex, `length(hfilt)`-by-`n` matrix of phase response vectors whose columns correspond to each filter in `hfilt`. If `n` is not specified, the function uses a default value of 8192.

## See Also

`freqz` | `fvtool` | `grpdelay` | `impz` | `mfilt` | `phasez` | `zerophase` | `zplane`

# zpkbpc2bpc

---

<b>Purpose</b>	Zero-pole-gain complex bandpass frequency transformation
<b>Syntax</b>	<code>[Z2,P2,K2,AllpassNum,AllpassDen] = zpkbpc2bpc(Z,P,K,Wo,Wt)</code>
<b>Description</b>	<p><code>[Z2,P2,K2,AllpassNum,AllpassDen] = zpkbpc2bpc(Z,P,K,Wo,Wt)</code> returns zeros, <math>Z_2</math>, poles, <math>P_2</math>, and gain factor, <math>K_2</math>, of the target filter transformed from the complex bandpass prototype by applying a first-order complex bandpass to complex bandpass frequency transformation.</p> <p>It also returns the numerator, <code>AllpassNum</code>, and the denominator, <code>AllpassDen</code>, of the allpass mapping filter. The original lowpass filter is given with zeros, <math>Z</math>, poles, <math>P</math>, and gain factor, <math>K</math>.</p> <p>This transformation effectively places two features of an original filter, located at frequencies <math>W_{o1}</math> and <math>W_{o2}</math>, at the required target frequency locations, <math>W_{t1}</math>, and <math>W_{t2}</math> respectively. It is assumed that <math>W_{t2}</math> is greater than <math>W_{t1}</math>. In most of the cases the features selected for the transformation are the band edges of the filter passbands. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones.</p> <p>Relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter, <math>F_1</math> and <math>F_2</math>, with <math>F_1</math> preceding <math>F_2</math>. Feature <math>F_1</math> will still precede <math>F_2</math> after the transformation. However, the distance between <math>F_1</math> and <math>F_2</math> will not be the same before and after the transformation.</p> <p>This transformation can also be used for transforming other types of filters; e.g., complex notch filters or resonators can be repositioned at two distinct desired frequencies at any place around the unit circle; e.g., in the adaptive system.</p>

## Examples

Design a prototype real IIR halfband filter using a standard elliptic approach:

```
[b, a] = ellip(3,0.1,30,0.409);
```


Create a complex passband from 0.25 to 0.75:

```
[b, a] = iirlp2bpc(b,a,0.5,[0.25,0.75]);  
z = roots(b);  
p = roots(a);  
k = b(1);  
[z2,p2,k2] = zpkbpc2bpc(z,p,k,[0.25, 0.75],[-0.75, -0.25]);
```

Verify the result by comparing the prototype filter with the target filter:

```
fvtool(b, a, k2*poly(z2), poly(p2));
```

Comparing the filters in FVTool shows the example results. Use the features in FVTool to check the filter coefficients, or other filter analyses.



# zpkbpc2bpc

---

## Arguments

Variable	Description
<i>Z</i>	Zeros of the prototype lowpass filter
<i>P</i>	Poles of the prototype lowpass filter
<i>K</i>	Gain factor of the prototype lowpass filter
<i>Wo</i>	Frequency value to be transformed from the prototype filter
<i>Wt</i>	Desired frequency location in the transformed target filter
<i>Z2</i>	Zeros of the target filter
<i>P2</i>	Poles of the target filter
<i>K2</i>	Gain factor of the target filter
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

Frequencies must be normalized to be between -1 and 1, with 1 corresponding to half the sample rate.

## See Also

[zpkftransf](#) | [allpassbpc2bpc](#) | [iirbpc2bpc](#)

**Purpose** Zero-pole-gain frequency transformation

**Syntax** `[Z2,P2,K2] = zpkftransf(Z,P,K,AllpassNum,AllpassDen)`

**Description** `[Z2,P2,K2] = zpkftransf(Z,P,K,AllpassNum,AllpassDen)` returns zeros,  $Z_2$ , poles,  $P_2$ , and gain factor,  $K_2$ , of the transformed lowpass digital filter. The prototype lowpass filter is given with zeros,  $Z$ , poles,  $P$ , and gain factor,  $K$ . If `AllpassDen` is not specified it will default to 1. If neither `AllpassNum` nor `AllpassDen` is specified, then the function returns the input filter.

**Examples** Design a prototype real IIR halfband filter using a standard elliptic approach:


```
[b, a] = ellip(3,0.1,30,0.409);  
[AlpNum, AlpDen] = allpasslp2lp(0.5, 0.25);  
[z2, p2, k2] = zpkftransf(roots(b),roots(a),b(1),AlpNum,AlpDen);
```

Verify the result by comparing the prototype filter with the target filter:

```
fvtool(b, a, k2*poly(z2), poly(p2));
```

After transforming the filter, you get the response shown in the figure, where the passband has been shifted towards zero.

# zpkftransf



## Arguments

Variable	Description
$Z$	Zeros of the prototype lowpass filter
$P$	Poles of the prototype lowpass filter
$K$	Gain factor of the prototype lowpass filter
$FTFNum$	Numerator of the mapping filter
$FTFDen$	Denominator of the mapping filter
$Z2$	Zeros of the target filter
$P2$	Poles of the target filter
$K2$	Gain factor of the target filter


## See Also

iirftransf

<b>Purpose</b>	Zero-pole-gain lowpass to bandpass frequency transformation
<b>Syntax</b>	<code>[Z2,P2,K2,AllpassNum,AllpassDen] = zpk1p2bp(Z,P,K,Wo,Wt)</code>
<b>Description</b>	<p><code>[Z2,P2,K2,AllpassNum,AllpassDen] = zpk1p2bp(Z,P,K,Wo,Wt)</code> returns zeros, <math>Z_2</math>, poles, <math>P_2</math>, and gain factor, <math>K_2</math>, of the target filter transformed from the real lowpass prototype by applying a second-order real lowpass to real bandpass frequency mapping.</p> <p>It also returns the numerator, <code>AllpassNum</code>, and the denominator <code>AllpassDen</code>, of the allpass mapping filter. The prototype lowpass filter is given with zeros, <math>Z</math>, poles, <math>P</math>, and gain factor, <math>K</math>.</p> <p>This transformation effectively places one feature of an original filter, located at frequency <math>-W_o</math>, at the required target frequency location, <math>W_{t1}</math>, and the second feature, originally at <math>+W_o</math>, at the new location, <math>W_{t2}</math>. It is assumed that <math>W_{t2}</math> is greater than <math>W_{t1}</math>. This transformation implements the "DC Mobility," which means that the Nyquist feature stays at Nyquist, but the DC feature moves to a location dependent on the selection of <math>W_t</math>.</p> <p>Relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter, <math>F_1</math> and <math>F_2</math>, with <math>F_1</math> preceding <math>F_2</math>. Feature <math>F_1</math> will still precede <math>F_2</math> after the transformation. However, the distance between <math>F_1</math> and <math>F_2</math> will not be the same before and after the transformation.</p> <p>Choice of the feature subject to the lowpass to bandpass transformation is not restricted only to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones.</p> <p>Real lowpass to bandpass transformation can also be used for transforming other types of filters; e.g., real notch filters or resonators can be easily doubled and positioned at two distinct, desired frequencies.</p>
<b>Examples</b>	Design a prototype real IIR halfband filter using a standard elliptic approach:

# zpk1p2bp

```
[B,A] = ellip(3,0.1,30,0.409);  
Z = roots(B);  
P = roots(A);  
K = B(1);  
[Z2,P2,K2] = zpk1p2bp(Z,P,K, 0.5, [0.2 0.3]);  
hfvtool(B,A,K2*poly(Z2),poly(P2));  
legend(hfvtool,'Prototype Lowpass Filter', 'Bandpass Filter');
```



## Arguments

Variable	Description
Z	Zeros of the prototype lowpass filter
P	Poles of the prototype lowpass filter
K	Gain factor of the prototype lowpass filter

Variable	Description
$W_0$	Frequency value to be transformed from the prototype filter
$W_t$	Desired frequency location in the transformed target filter
$Z_2$	Zeros of the target filter
$P_2$	Poles of the target filter
$K_2$	Gain factor of the target filter
$AllpassNum$	Numerator of the mapping filter
$AllpassDen$	Denominator of the mapping filter

Frequencies must be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.

## References

Constantinides, A.G., "Spectral transformations for digital filters," *IEE Proceedings*, vol. 117, no. 8, pp. 1585-1590, August 1970.

Nowrouzian, B. and A.G. Constantinides, "Prototype reference transfer function parameters in the discrete-time frequency transformations," *Proceedings 33rd Midwest Symposium on Circuits and Systems*, Calgary, Canada, vol. 2, pp. 1078-1082, August 1990.

Nowrouzian, B. and L.T. Bruton, "Closed-form solutions for discrete-time elliptic transfer functions," *Proceedings of the 35th Midwest Symposium on Circuits and Systems*, vol. 2, pp. 784-787, 1992.

Constantinides, A.G., "Design of bandpass digital filters," *IEEE Proceedings*, vol. 1, pp. 1129-1231, June 1969.

## See Also

zpkftransf | allpass1p2bp | iir1p2bp

# zpk1p2bpc

---

**Purpose** Zero-pole-gain lowpass to complex bandpass frequency transformation

**Syntax** `[Z2,P2,K2,AllpassNum,AllpassDen] = zpk1p2bpc(Z,P,K,Wo,Wt)`

**Description** `[Z2,P2,K2,AllpassNum,AllpassDen] = zpk1p2bpc(Z,P,K,Wo,Wt)` returns zeros,  $Z_2$ , poles,  $P_2$ , and gain factor,  $K_2$ , of the target filter transformed from the real lowpass prototype by applying a first-order real lowpass to complex bandpass frequency transformation.

It also returns the numerator, `AllpassNum`, and the denominator, `AllpassDen`, of the allpass mapping filter. The prototype lowpass filter is given with zeros,  $Z$ , poles,  $P$ , and gain factor,  $K$ .

This transformation effectively places one feature of an original filter, located at frequency  $-W_o$ , at the required target frequency location,  $W_{t1}$ , and the second feature, originally at  $+W_o$ , at the new location,  $W_{t2}$ . It is assumed that  $W_{t2}$  is greater than  $W_{t1}$ .

Relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter,  $F_1$  and  $F_2$ , with  $F_1$  preceding  $F_2$ . Feature  $F_1$  will still precede  $F_2$  after the transformation. However, the distance between  $F_1$  and  $F_2$  will not be the same before and after the transformation.

Choice of the feature subject to the lowpass to bandpass transformation is not restricted only to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones.

Lowpass to bandpass transformation can also be used for transforming other types of filters; e.g., real notch filters or resonators can be doubled and positioned at two distinct desired frequencies at any place around the unit circle forming a pair of complex notches/resonators. This transformation can be used for designing bandpass filters for radio receivers from the high-quality prototype lowpass filter.

**Examples** Design a prototype real IIR halfband filter using a standard elliptic approach:

```
[b, a] = ellip(3,0.1,30,0.409);
z = roots(b);
p = roots(a);
k = b(1);
[z2,p2,k2] = zpk1p2bpc(z, p, k, 0.5, [0.2 0.3]);
```

Verify the result by comparing the prototype filter with the target filter:

```
fvtool(b, a, k2*poly(z2), poly(p2));
```

## Arguments

Variable	Description
<i>Z</i>	Zeros of the prototype lowpass filter
<i>P</i>	Poles of the prototype lowpass filter
<i>K</i>	Gain factor of the prototype lowpass filter
<i>W0</i>	Frequency value to be transformed from the prototype filter. It should be normalized to be between -1 and 1, with 1 corresponding to half the sample rate.
<i>Wt</i>	Desired frequency locations in the transformed target filter. They should be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.
<i>Z2</i>	Zeros of the target filter
<i>P2</i>	Poles of the target filter
<i>K2</i>	Gain factor of the target filter
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

## See Also

zpkftransf | allpass1p2bpc | iir1p2bpc

# zpk1p2bs

---

<b>Purpose</b>	Zero-pole-gain lowpass to bandstop frequency transformation
<b>Syntax</b>	<code>[Z2,P2,K2,AllpassNum,AllpassDen] = zpk1p2bs(Z,P,K,Wo,Wt)</code>
<b>Description</b>	<p><code>[Z2,P2,K2,AllpassNum,AllpassDen] = zpk1p2bs(Z,P,K,Wo,Wt)</code> returns zeros, <math>Z_2</math>, poles, <math>P_2</math>, and gain factor, <math>K_2</math>, of the target filter transformed from the real lowpass prototype by applying a second-order real lowpass to real bandstop frequency mapping.</p> <p>It also returns the numerator, <code>AllpassNum</code>, and the denominator, <code>AllpassDen</code>, of the allpass mapping filter. The prototype lowpass filter is given with zeros, <math>Z</math>, poles, <math>P</math>, and gain factor, <math>K</math>.</p> <p>This transformation effectively places one feature of an original filter, located at frequency <math>-W_o</math>, at the required target frequency location, <math>W_{t1}</math>, and the second feature, originally at <math>+W_o</math>, at the new location, <math>W_{t2}</math>. It is assumed that <math>W_{t2}</math> is greater than <math>W_{t1}</math>. This transformation implements the "Nyquist Mobility," which means that the DC feature stays at DC, but the Nyquist feature moves to a location dependent on the selection of <math>W_o</math> and <math>W_t</math>s.</p> <p>Relative positions of other features of an original filter change in the target filter. This means that it is possible to select two features of an original filter, <math>F_1</math> and <math>F_2</math>, with <math>F_1</math> preceding <math>F_2</math>. After the transformation feature <math>F_2</math> will precede <math>F_1</math> in the target filter. However, the distance between <math>F_1</math> and <math>F_2</math> will not be the same before and after the transformation.</p> <p>Choice of the feature subject to the lowpass to bandstop transformation is not restricted only to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones.</p>

## Examples

Design a prototype real IIR halfband filter using a standard elliptic approach:

```
[b, a] = ellip(3,0.1,30,0.409);  
z = roots(b);  
p = roots(a);
```

```
k = b(1);
[z2,p2,k2] = zpk1p2bs(z, p, k, 0.5, [0.2 0.3]);
```

Verify the result by comparing the prototype filter with the target filter:

```
fvtool(b, a, k2*poly(z2), poly(p2));
```

## Arguments

Variable	Description
$Z$	Zeros of the prototype lowpass filter
$P$	Poles of the prototype lowpass filter
$K$	Gain factor of the prototype lowpass filter
$W_0$	Frequency value to be transformed from the prototype filter
$W_t$	Desired frequency location in the transformed target filter
$Z_2$	Zeros of the target filter
$P_2$	Poles of the target filter
$K_2$	Gain factor of the target filter
$AllpassNum$	Numerator of the mapping filter
$AllpassDen$	Denominator of the mapping filter

Frequencies must be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.

## References

Constantinides, A.G., "Spectral transformations for digital filters," *IEEE Proceedings*, vol. 117, no. 8, pp. 1585-1590, August 1970.

Nowrouzian, B. and A.G. Constantinides, "Prototype reference transfer function parameters in the discrete-time frequency transformations," *Proceedings 33rd Midwest Symposium on Circuits and Systems*, Calgary, Canada, vol. 2, pp. 1078-1082, August 1990.

Nowrouzian, B. and L.T. Bruton, "Closed-form solutions for discrete-time elliptic transfer functions," *Proceedings of the 35th Midwest Symposium on Circuits and Systems*, vol. 2, pp. 784-787, 1992.

Constantinides, A.G., "Design of bandpass digital filters," *IEEE Proceedings*, vol. 1, pp. 1129-1231, June 1969.

## See Also

[zpkftransf](#) | [allpass1p2bs](#) | [iir1p2bs](#)

<b>Purpose</b>	Zero-pole-gain lowpass to complex bandstop frequency transformation
<b>Syntax</b>	<code>[Z2,P2,K2,AllpassNum,AllpassDen] = zpk1p2bsc(Z,P,K,Wo,Wt)</code>
<b>Description</b>	<p><code>[Z2,P2,K2,AllpassNum,AllpassDen] = zpk1p2bsc(Z,P,K,Wo,Wt)</code> returns zeros, <math>Z_2</math>, poles, <math>P_2</math>, and gain factor, <math>K_2</math>, of the target filter transformed from the real lowpass prototype by applying a first-order real lowpass to complex bandstop frequency transformation.</p> <p>It also returns the numerator, <code>AllpassNum</code>, and the denominator, <code>AllpassDen</code>, of the allpass mapping filter. The prototype lowpass filter is given with zeros, <math>Z</math>, poles, <math>P</math>, and gain factor, <math>K</math>.</p> <p>This transformation effectively places one feature of an original filter, located at frequency <math>-W_o</math>, at the required target frequency location, <math>W_{t1}</math>, and the second feature, originally at <math>+W_o</math>, at the new location, <math>W_{t2}</math>. It is assumed that <math>W_{t2}</math> is greater than <math>W_{t1}</math>. Additionally the transformation swaps passbands with stopbands in the target filter.</p> <p>Relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter, <math>F_1</math> and <math>F_2</math>, with <math>F_1</math> preceding <math>F_2</math>. Feature <math>F_1</math> will still precede <math>F_2</math> after the transformation. However, the distance between <math>F_1</math> and <math>F_2</math> will not be the same before and after the transformation.</p> <p>Choice of the feature subject to the lowpass to bandstop transformation is not restricted only to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones.</p> <p>Lowpass to bandpass transformation can also be used for transforming other types of filters; e.g., real notch filters or resonators can be doubled and positioned at two distinct desired frequencies at any place around the unit circle forming a pair of complex notches/resonators.</p>
<b>Examples</b>	<p>Design a prototype real IIR halfband filter using a standard elliptic approach:</p> <pre>[b, a] = ellip(3,0.1,30,0.409);</pre>

# zpk1p2bsc

```
z = roots(b);  
p = roots(a);  
k = b(1);  
[z2,p2,k2] = zpk1p2bsc(z, p, k, 0.5, [0.2, 0.3]);
```

Verify the result by comparing the prototype filter with the target filter:

```
fvtool(b, a, k2*poly(z2), poly(p2));
```

## Arguments

Variable	Description
<i>Z</i>	Zeros of the prototype lowpass filter
<i>P</i>	Poles of the prototype lowpass filter
<i>K</i>	Gain factor of the prototype lowpass filter
<i>Wo</i>	Frequency value to be transformed from the prototype filter. It should be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.
<i>Wt</i>	Desired frequency locations in the transformed target filter. They should be normalized to be between -1 and 1, with 1 corresponding to half the sample rate.
<i>Z2</i>	Zeros of the target filter
<i>P2</i>	Poles of the target filter
<i>K2</i>	Gain factor of the target filter
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

## See Also

zpkftransf | allpass1p2bsc | iir1p2bsc

<b>Purpose</b>	Zero-pole-gain lowpass to highpass frequency transformation
<b>Syntax</b>	<code>[Z2,P2,K2,AllpassNum,AllpassDen] = zpk1p2hp(Z,P,K,Wo,Wt)</code>
<b>Description</b>	<p><code>[Z2,P2,K2,AllpassNum,AllpassDen] = zpk1p2hp(Z,P,K,Wo,Wt)</code> returns zeros, <math>Z_2</math>, poles, <math>P_2</math>, and gain factor, <math>K_2</math>, of the target filter transformed from the real lowpass prototype by applying a first-order real lowpass to real highpass frequency mapping. This transformation effectively places one feature of an original filter, located at frequency <math>W_o</math>, at the required target frequency location, <math>W_t</math>, at the same time rotating the whole frequency response by half of the sampling frequency. Result is that the DC and Nyquist features swap places.</p> <p>It also returns the numerator, <code>AllpassNum</code>, and the denominator, <code>AllpassDen</code>, of the allpass mapping filter. The prototype lowpass filter is given with zeros, <math>Z</math>, poles, <math>P</math>, and the gain factor, <math>K</math>.</p> <p>Relative positions of other features of an original filter change in the target filter. This means that it is possible to select two features of an original filter, <math>F_1</math> and <math>F_2</math>, with <math>F_1</math> preceding <math>F_2</math>. After the transformation feature <math>F_2</math> will precede <math>F_1</math> in the target filter. However, the distance between <math>F_1</math> and <math>F_2</math> will not be the same before and after the transformation.</p> <p>Choice of the feature subject to the lowpass to highpass transformation is not restricted to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, or the deep minimum in the stopband, or other ones.</p> <p>Lowpass to highpass transformation can also be used for transforming other types of filters; e.g., notch filters or resonators can change their position in a simple way without designing them again.</p>
<b>Examples</b>	<p>Design a prototype real IIR halfband filter using a standard elliptic approach:</p> <pre>[b, a] = ellip(3,0.1,30,0.409); z = roots(b); p = roots(a);</pre>

```
k = b(1);  
[z2,p2,k2] = zpk1p2hp(z, p, k, 0.5, 0.25);
```

Verify the result by comparing the prototype filter with the target filter:

```
fvtool(b, a, k2*poly(z2), poly(p2));
```

## Arguments

Variable	Description
<i>Z</i>	Zeros of the prototype lowpass filter
<i>P</i>	Poles of the prototype lowpass filter
<i>K</i>	Gain factor of the prototype lowpass filter
<i>W<sub>0</sub></i>	Frequency value to be transformed from the prototype filter
<i>W<sub>t</sub></i>	Desired frequency location in the transformed target filter
<i>Z<sub>2</sub></i>	Zeros of the target filter
<i>P<sub>2</sub></i>	Poles of the target filter
<i>K<sub>2</sub></i>	Gain factor of the target filter
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

Frequencies must be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.

## References

Constantinides, A.G., "Spectral transformations for digital filters," *IEE Proceedings*, vol. 117, no. 8, pp. 1585-1590, August 1970.

Nowrouzian, B. and A.G. Constantinides, "Prototype reference transfer function parameters in the discrete-time frequency transformations," *Proceedings 33rd Midwest Symposium on Circuits and Systems*, Calgary, Canada, vol. 2, pp. 1078-1082, August 1990.

Nowrouzian, B. and L.T. Bruton, "Closed-form solutions for discrete-time elliptic transfer functions," *Proceedings of the 35th Midwest Symposium on Circuits and Systems*, vol. 2, pp. 784-787, 1992.

Constantinides, A.G., "Frequency transformations for digital filters," *Electronics Letters*, vol. 3, no. 11, pp. 487-489, November 1967.

## See Also

[zpkftransf](#) | [allpass1p2hp](#) | [iir1p2hp](#)

<b>Purpose</b>	Zero-pole-gain lowpass to lowpass frequency transformation
<b>Syntax</b>	<code>[Z2,P2,K2,AllpassNum,AllpassDen] = zpk1p2lp(Z,P,K,Wo,Wt)</code>
<b>Description</b>	<p><code>[Z2,P2,K2,AllpassNum,AllpassDen] = zpk1p2lp(Z,P,K,Wo,Wt)</code> returns zeros, <math>Z_2</math>, poles, <math>P_2</math>, and gain factor, <math>K_2</math>, of the target filter transformed from the real lowpass prototype by applying a first-order real lowpass to real lowpass frequency mapping. This transformation effectively places one feature of an original filter, located at frequency <math>W_o</math>, at the required target frequency location, <math>W_t</math>.</p> <p>It also returns the numerator, <code>AllpassNum</code>, and the denominator, <code>AllpassDen</code>, of the allpass mapping filter. The prototype lowpass filter is given with zeros, <math>Z</math>, poles, <math>P</math>, and gain factor, <math>K</math>.</p> <p>Relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter, <math>F_1</math> and <math>F_2</math>, with <math>F_1</math> preceding <math>F_2</math>. Feature <math>F_1</math> will still precede <math>F_2</math> after the transformation. However, the distance between <math>F_1</math> and <math>F_2</math> will not be the same before and after the transformation.</p> <p>Choice of the feature subject to the lowpass to lowpass transformation is not restricted to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones.</p> <p>Lowpass to lowpass transformation can also be used for transforming other types of filters; e.g., notch filters or resonators can change their position in a simple way without designing them again.</p>


**Examples** Design a prototype real IIR halfband filter using a standard elliptic approach:

```
[b, a] = ellip(3, 0.1, 30, 0.409);  
z = roots(b);  
p = roots(a);  
k = b(1);  
[z2,p2,k2] = zpk1p2lp(z, p, k, 0.5, 0.25);
```

Verify the result by comparing the prototype filter with the target filter:

```
fvtool(b, a, k2*poly(z2), poly(p2));
```

Using `zpk1p2lp` creates the desired half band IIR filter with the transformed features that you specify in the transformation function. This figure shows the results.



## Arguments

Variable	Description
$Z$	Zeros of the prototype lowpass filter
$P$	Poles of the prototype lowpass filter
$K$	Gain factor of the prototype lowpass filter

Variable	Description
$W_0$	Frequency value to be transformed from the prototype filter
$W_t$	Desired frequency location in the transformed target filter
$Z_2$	Zeros of the target filter
$P_2$	Poles of the target filter
$K_2$	Gain factor of the target filter
$AllpassNum$	Numerator of the mapping filter
$AllpassDen$	Denominator of the mapping filter

Frequencies must be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.

## References

Constantinides, A.G., "Spectral transformations for digital filters," *IEE Proceedings*, vol. 117, no. 8, pp. 1585-1590, August 1970.

Nowrouzian, B. and A.G. Constantinides, "Prototype reference transfer function parameters in the discrete-time frequency transformations," *Proceedings 33rd Midwest Symposium on Circuits and Systems*, Calgary, Canada, vol. 2, pp. 1078-1082, August 1990.

Nowrouzian, B. and L.T. Bruton, "Closed-form solutions for discrete-time elliptic transfer functions," *Proceedings of the 35th Midwest Symposium on Circuits and Systems*, vol. 2, pp. 784-787, 1992.

Constantinides, A.G., "Frequency transformations for digital filters," *Electronics Letters*, vol. 3, no. 11, pp. 487-489, November 1967.

## See Also

zpkftransf | allpasslp2lp | iirlp2lp

<b>Purpose</b>	Zero-pole-gain lowpass to M-band frequency transformation
<b>Syntax</b>	<pre>[Z2,P2,K2,AllpassNum,AllpassDen] = zpk1p2mb(Z,P,K,Wo,Wt) [Z2,P2,K2,AllpassNum,AllpassDen] = zpk1p2mb(Z,P,K,Wo,Wt,Pass)</pre>
<b>Description</b>	<p>[Z2,P2,K2,AllpassNum,AllpassDen] = zpk1p2mb(Z,P,K,Wo,Wt) returns zeros, <math>Z_2</math>, poles, <math>P_2</math>, and gain factor, <math>K_2</math>, of the target filter transformed from the real lowpass prototype by applying an Mth-order real lowpass to real multibandpass frequency mapping. By default the DC feature is kept at its original location.</p> <p>[Z2,P2,K2,AllpassNum,AllpassDen] = zpk1p2mb(Z,P,K,Wo,Wt,Pass) allows you to specify an additional parameter, Pass, which chooses between using the "DC Mobility" and the "Nyquist Mobility". In the first case the Nyquist feature stays at its original location and the DC feature is free to move. In the second case the DC feature is kept at an original frequency and the Nyquist feature is allowed to move.</p> <p>It also returns the numerator, AllpassNum, and the denominator, AllpassDen, of the allpass mapping filter. The prototype lowpass filter is given with zeros, Z, poles, P, and gain factor, K.</p> <p>This transformation effectively places one feature of an original filter, located at frequency <math>W_o</math>, at the required target frequency locations, <math>W_{t1}, \dots, W_{tM}</math>.</p> <p>Relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter, <math>F_1</math> and <math>F_2</math>, with <math>F_1</math> preceding <math>F_2</math>. Feature <math>F_1</math> will still precede <math>F_2</math> after the transformation. However, the distance between <math>F_1</math> and <math>F_2</math> will not be the same before and after the transformation.</p> <p>Choice of the feature subject to this transformation is not restricted to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones.</p> <p>This transformation can also be used for transforming other types of filters; e.g., notch filters or resonators can be easily replicated at a</p>

number of required frequency locations. A good application would be an adaptive tone cancellation circuit reacting to the changing number and location of tones.

## Examples


Design a prototype real IIR halfband filter using a standard elliptic approach:

```
[b, a] = ellip(3,0.1,30,0.409);
z = roots(b);
p = roots(a);
k = b(1);
[z1,p1,k1] = zpk1p2mb(z, p, k, 0.5, [2 4 6 8]/10, 'pass');
[z2,p2,k2] = zpk1p2mb(z, p, k, 0.5, [2 4 6 8]/10, 'stop');
```

Verify the result by comparing the prototype filter with the target filter:

```
fvtool(b, a, k1*poly(z1), poly(p1), k2*poly(z2), poly(p2));
```

The resulting multiband filter that replicates features from the prototype appears in the figure shown. Note the accuracy of the replication process.



## Arguments

Variable	Description
$Z$	Zeros of the prototype lowpass filter
$P$	Poles of the prototype lowpass filter
$K$	Gain factor of the prototype lowpass filter
$W_0$	Frequency value to be transformed from the prototype filter
$W_t$	Desired frequency location in the transformed target filter
$Pass$	Choice ('pass' / 'stop') of passband/stopband at DC, 'pass' being the default
$Z_2$	Zeros of the target filter

Variable	Description
$P2$	Poles of the target filter
$K2$	Gain factor of the target filter
$AllpassNum$	Numerator of the mapping filter
$AllpassDen$	Denominator of the mapping filter

Frequencies must be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.

## References

Franchitti, J.C., "All-pass filter interpolation and frequency transformation problems," *MSc Thesis*, Dept. of Electrical and Computer Engineering, University of Colorado, 1985.

Feyh, G., J.C. Franchitti and C.T. Mullis, "All-pass filter interpolation and frequency transformation problem," *Proceedings 20th Asilomar Conference on Signals, Systems and Computers*, Pacific Grove, California, pp. 164-168, November 1986.

Mullis, C.T. and R.A. Roberts, *Digital Signal Processing*, section 6.7, Reading, Massachusetts, Addison-Wesley, 1987.

Feyh, G., W.B. Jones and C.T. Mullis, *An extension of the Schur Algorithm for frequency transformations*, *Linear Circuits, Systems and Signal Processing: Theory and Application*, C. J. Byrnes et al Eds, Amsterdam: Elsevier, 1988.

## See Also

zpkftransf | allpass1p2mb | iir1p2mb

<b>Purpose</b>	Zero-pole-gain lowpass to complex M-band frequency transformation
<b>Syntax</b>	<code>[Z2,P2,K2,AllpassNum,AllpassDen] = zpk1pmbc(Z,P,K,Wo,Wt)</code>
<b>Description</b>	<p><code>[Z2,P2,K2,AllpassNum,AllpassDen] = zpk1pmbc(Z,P,K,Wo,Wt)</code> returns zeros, <math>Z_2</math>, poles, <math>P_2</math>, and gain factor, <math>K_2</math>, of the target filter transformed from the real lowpass prototype by applying an Mth-order real lowpass to complex multibandpass frequency transformation.</p> <p>It also returns the numerator, <code>AllpassNum</code>, and the denominator, <code>AllpassDen</code>, of the allpass mapping filter. The prototype lowpass filter is given with zeros, <math>Z</math>, poles, <math>P</math>, and gain factor, <math>K</math>.</p> <p>This transformation effectively places one feature of an original filter, located at frequency <math>W_o</math>, at the required target frequency locations, <math>W_{t1}, \dots, W_{tM}</math>.</p> <p>Choice of the feature subject to this transformation is not restricted to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature, for example, the stopband edge, the DC, the deep minimum in the stopband, or other ones.</p> <p>Relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter, <math>F_1</math> and <math>F_2</math>, with <math>F_1</math> preceding <math>F_2</math>. Feature <math>F_1</math> will still precede <math>F_2</math> after the transformation. However, the distance between <math>F_1</math> and <math>F_2</math> will not be the same before and after the transformation.</p> <p>This transformation can also be used for transforming other types of filters; e.g., to replicate notch filters and resonators at any required location.</p>
<b>Examples</b>	<p>Design a prototype real IIR halfband filter using a standard elliptic approach:</p> <pre>[b, a] = ellip(3,0.1,30,0.409); z = roots(b); p = roots(a); k = b(1);</pre>


# zpk1p2mbc

```
[z1,p1,k1] = zpk1p2mbc(z, p, k, 0.5, [2 4 6 8]/10);  
[z2,p2,k2] = zpk1p2mbc(z, p, k, 0.5, [2 4 6 8]/10);
```

Verify the result by comparing the prototype filter with the target filter:

```
fvtool(b, a, k1*poly(z1), poly(p1), k2*poly(z2), poly(p2));
```

You could review the coefficients to compare the filters, but the graphical comparison shown here is quicker and easier.



However, looking at the coefficients in FVTool shows the complex nature desired.

**Arguments**

<b>Variable</b>	<b>Description</b>
<i>Z</i>	Zeros of the prototype lowpass filter
<i>P</i>	Poles of the prototype lowpass filter
<i>K</i>	Gain factor of the prototype lowpass filter
<i>Wo</i>	Frequency value to be transformed from the prototype filter. It should be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.
<i>Wt</i>	Desired frequency locations in the transformed target filter. They should be normalized to be between -1 and 1, with 1 corresponding to half the sample rate.
<i>Z2</i>	Zeros of the target filter
<i>P2</i>	Poles of the target filter
<i>K2</i>	Gain factor of the target filter
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

**See Also**

zpkftransf | allpass1p2mbc | iir1p2mbc

**Purpose** Zero-pole-gain lowpass to complex N-point frequency transformation

**Syntax** [Z2,P2,K2,AllpassNum,AllpassDen] = zpk1p2xc(Z,P,K,Wo,Wt)

**Description** [Z2,P2,K2,AllpassNum,AllpassDen] = zpk1p2xc(Z,P,K,Wo,Wt) returns zeros,  $Z_2$ , poles,  $P_2$ , and gain factor,  $K_2$ , of the target filter transformed from the real lowpass prototype by applying an Nth-order real lowpass to complex multipoint frequency transformation.

It also returns the numerator, AllpassNum, and the denominator, AllpassDen, of the allpass mapping filter. The prototype lowpass filter is given with zeros, Z, poles, P, and gain factor, K.

Parameter N also specifies the number of replicas of the prototype filter created around the unit circle after the transformation. This transformation effectively places N features of an original filter, located at frequencies  $W_{o1}, \dots, W_{oN}$ , at the required target frequency locations,  $W_{t1}, \dots, W_{tM}$ .

Relative positions of other features of an original filter are the same in the target filter for the Nyquist mobility and are reversed for the DC mobility. For the Nyquist mobility this means that it is possible to select two features of an original filter,  $F_1$  and  $F_2$ , with  $F_1$  preceding  $F_2$ . Feature  $F_1$  will still precede  $F_2$  after the transformation. However, the distance between  $F_1$  and  $F_2$  will not be the same before and after the transformation. For DC mobility feature  $F_2$  will precede  $F_1$  after the transformation.

Choice of the feature subject to this transformation is not restricted to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones. The only condition is that the features must be selected in such a way that when creating N bands around the unit circle, there will be no band overlap.

This transformation can also be used for transforming other types of filters; e.g., notch filters or resonators can be easily replicated at a number of required frequency locations. A good application would be

an adaptive tone cancellation circuit reacting to the changing number and location of tones.

## Examples


Design a prototype real IIR halfband filter using a standard elliptic approach:

```
[b, a] = ellip(3,0.1,30,0.409);  
z = roots(b);  
p = roots(a);  
k = b(1);  
[z2,p2,k2] = zpk1p2xc(z, p, k, [-0.5 0.5], [-0.25 0.25]);
```

Verify the result by comparing the prototype filter with the target filter:

```
fvtool(b, a, k2*poly(z2), poly(p2));
```

Plotting the filters on the same axes lets you compare the results graphically, shown here.



# zpk1p2xc

---

## Arguments

Variable	Description
<i>Z</i>	Zeros of the prototype lowpass filter
<i>P</i>	Poles of the prototype lowpass filter
<i>K</i>	Gain factor of the prototype lowpass filter
<i>Wo</i>	Frequency values to be transformed from the prototype filter. They should be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.
<i>Wt</i>	Desired frequency locations in the transformed target filter. They should be normalized to be between -1 and 1, with 1 corresponding to half the sample rate.
<i>Z2</i>	Zeros of the target filter
<i>P2</i>	Poles of the target filter
<i>K2</i>	Gain factor of the target filter
<i>AllpassNum</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

## See Also

zpkftransf | allpass1p2xc | iir1p2xc

<b>Purpose</b>	Zero-pole-gain lowpass to N-point frequency transformation
<b>Syntax</b>	<pre>[ Z2,P2,K2,AllpassNum,AllpassDen] = zpk1p2xn(Z,P,K,Wo,Wt) [ Z2,P2,K2,AllpassNum,AllpassDen] = zpk1p2xn(Z,P,K,Wo,Wt,Pass)</pre>
<b>Description</b>	<p>[ Z2,P2,K2,AllpassNum,AllpassDen] = zpk1p2xn(Z,P,K,Wo,Wt) returns zeros, <math>Z_2</math>, poles, <math>P_2</math>, and gain factor, <math>K_2</math>, of the target filter transformed from the real lowpass prototype by applying an Nth-order real lowpass to real multipoint frequency transformation, where N is the number of features being mapped. By default the DC feature is kept at its original location.</p> <p>[ Z2,P2,K2,AllpassNum,AllpassDen] = zpk1p2xn(Z,P,K,Wo,Wt,Pass) allows you to specify an additional parameter, Pass, which chooses between using the "DC Mobility" and the "Nyquist Mobility". In the first case the Nyquist feature stays at its original location and the DC feature is free to move. In the second case the DC feature is kept at an original frequency and the Nyquist feature is allowed to move.</p> <p>It also returns the numerator, AllpassNum, and the denominator, AllpassDen, of the allpass mapping filter. The prototype lowpass filter is given with zeros, Z, poles, P, and gain factor, K.</p> <p>Parameter N also specifies the number of replicas of the prototype filter created around the unit circle after the transformation. This transformation effectively places N features of an original filter, located at frequencies <math>W_{o1}, \dots, W_{oN}</math>, at the required target frequency locations, <math>W_{t1}, \dots, W_{tM}</math>.</p> <p>Relative positions of other features of an original filter are the same in the target filter for the Nyquist mobility and are reversed for the DC mobility. For the Nyquist mobility this means that it is possible to select two features of an original filter, <math>F_1</math> and <math>F_2</math>, with <math>F_1</math> preceding <math>F_2</math>. Feature <math>F_1</math> will still precede <math>F_2</math> after the transformation. However, the distance between <math>F_1</math> and <math>F_2</math> will not be the same before and after the transformation. For DC mobility feature <math>F_2</math> will precede <math>F_1</math> after the transformation.</p>

Choice of the feature subject to this transformation is not restricted to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones. The only condition is that the features must be selected in such a way that when creating  $N$  bands around the unit circle, there will be no band overlap.

This transformation can also be used for transforming other types of filters; e.g., notch filters or resonators can be easily replicated at a number of required frequency locations. A good application would be an adaptive tone cancellation circuit reacting to the changing number and location of tones.

## Examples

Design a prototype real IIR halfband filter using a standard elliptic approach:

```
[b, a] = ellip(3,0.1,30,0.409);
z = roots(b);
p = roots(a);
k = b(1);
[z2,p2,k2] = zpk1p2xn(z, p, k, [-0.5 0.5], [0 0.25], 'pass');
hfvt = fvtool(b, a, k2*poly(z2), poly(p2));
legend(hfvt,'Original Filter','Half-band Filter');
```

As demonstrated by the figure, the target filter has the desired response shape and values replicated from the prototype.

## Arguments

Variable	Description
$Z$	Zeros of the prototype lowpass filter
$P$	Poles of the prototype lowpass filter
$K$	Gain factor of the prototype lowpass filter
$W_0$	Frequency value to be transformed from the prototype filter

Variable	Description
<i>Wt</i>	Desired frequency location in the transformed target filter
<i>Pass</i>	Choice ('pass' / 'stop') of passband/stopband at DC, 'pass' being the default
<i>Z2</i>	Zeros of the target filter
<i>P2</i>	Poles of the target filter
<i>K2</i>	Gain factor of the target filter
<i>AllpassDen</i>	Numerator of the mapping filter
<i>AllpassDen</i>	Denominator of the mapping filter

Frequencies must be normalized to be between 0 and 1, with 1 corresponding to half the sample rate.

## References

Cain, G.D., A. Krukowski and I. Kale, "High Order Transformations for Flexible IIR Filter Design," *VII European Signal Processing Conference (EUSIPCO'94)*, vol. 3, pp. 1582-1585, Edinburgh, United Kingdom, September 1994.

Krukowski, A., G.D. Cain and I. Kale, "Custom designed high-order frequency transformations for IIR filters," *38th Midwest Symposium on Circuits and Systems (MWSCAS'95)*, Rio de Janeiro, Brazil, August 1995.

## See Also

zpkftransf | allpass1p2xn | iir1p2xn

# zpkrateup

---

**Purpose** Zero-pole-gain complex bandpass frequency transformation

**Syntax** [Z2,P2,K2,AllpassNum,AllpassDen] = zpkrateup(Z,P,K,N)

**Description** [Z2,P2,K2,AllpassNum,AllpassDen] = zpkrateup(Z,P,K,N) returns zeros,  $Z_2$ , poles,  $P_2$ , and gain factor,  $K_2$ , of the target filter being transformed from any prototype by applying an Nth-order rateup frequency transformation, where N is the upsample ratio. Transformation creates N equal replicas of the prototype filter frequency response.

It also returns the numerator, AllpassNum, and the denominator, AllpassDen, of the allpass mapping filter. The original lowpass filter is given with zeros, Z, poles, P, and gain factor, K.

Relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter,  $F_1$  and  $F_2$ , with  $F_1$  preceding  $F_2$ . Feature  $F_1$  will still precede  $F_2$  after the transformation. However, the distance between  $F_1$  and  $F_2$  will not be the same before and after the transformation.

**Examples** Design a prototype real IIR halfband filter using a standard elliptic approach:

```
[b, a] = ellip(3,0.1,30,0.409);  
z = roots(b);  
p = roots(a);  
k = b(1);  
% Upsample the prototype filter 4 times  
[z2,p2,k2] = zpkrateup(z, p, k, 4);  
% Compare prototype filter with target filter  
fvtool(b, a, k2*poly(z2), poly(p2));
```

## Arguments

Variable	Description
Z	Zeros of the prototype lowpass filter
P	Poles of the prototype lowpass filter

Variable	Description
$K$	Gain factor of the prototype lowpass filter
$N$	Integer upsampling ratio
$Z2$	Zeros of the target filter
$P2$	Poles of the target filter
$K2$	Gain factor of the target filter
$AllpassNum$	Numerator of the mapping filter
$AllpassDen$	Denominator of the mapping filter

Frequencies must be normalized to be between -1 and 1, with 1 corresponding to half the sample rate.

**See Also**

zpkrateup | allpassrateup | iirrateup

# zpkshift

---

<b>Purpose</b>	Zero-pole-gain real shift frequency transformation
<b>Syntax</b>	<code>[Z2,P2,K2,AllpassNum,AllpassDen] = zpkshift(Z,P,K,Wo,Wt)</code>
<b>Description</b>	<p><code>[Z2,P2,K2,AllpassNum,AllpassDen] = zpkshift(Z,P,K,Wo,Wt)</code> returns the zeros, <math>Z2</math>, poles, <math>P2</math>, and gain factor, <math>K2</math>, of the target filter transformed from the zeros, poles, and gain factor of real lowpass prototype by applying a second-order real shift frequency mapping. It also returns the numerator, <i>AllpassNum</i>, and the denominator, <i>AllpassDen</i> of the allpass mapping filter.</p> <p>This transformation places one selected feature of an original filter, located at frequency <math>W_o</math>, at the required target frequency location, <math>W_t</math>. This transformation implements the "DC Mobility," which means that the Nyquist feature stays at Nyquist, but the DC feature moves to a location dependent on the selection of <math>W_o</math> and <math>W_t</math>.</p> <p>Relative positions of other features of an original filter do not change in the target filter. This means that it is possible to select two features of an original filter, <math>F_1</math> and <math>F_2</math>, with <math>F_1</math> preceding <math>F_2</math>. Feature <math>F_1</math> will still precede <math>F_2</math> after the transformation. However, the distance between <math>F_1</math> and <math>F_2</math> will not be the same before and after the transformation.</p> <p>Choice of the feature subject to the real shift transformation is not restricted to the cutoff frequency of an original lowpass filter. In general it is possible to select any feature; e.g., the stopband edge, the DC, the deep minimum in the stopband, or other ones.</p> <p>This transformation can also be used for transforming other types of filters; e.g., notch filters or resonators can change their position in a simple way without the need to design them again.</p>

## Examples


Rotate frequency response by  $\pi/2$  radians/sample:

```
[B,A] = ellip(10,0.1,40,0.25);  
% Elliptic lowpass filter with passband frequency 0.25*pi rad/sample  
Z = roots(B); % get roots of numerator polynomial- filter zeros  
P = roots(A); % get roots of denominator polynomial- filter poles  
K = B(1);
```

```

[Z2,P2,K2] = zpkshift(Z,P,K,0.25,0.75); % shift by 0.25*pi rad/sample
Num = poly(Z2);
Den = poly(P2);
hfvtool(B,A,K2*Num,Den);
legend(hfvtool,'Original Filter','Rotate by \pi/2 radians/sample');
axis([0 1 -90 10]);

```



## See Also

[zpkftransf](#) | [allpassshift](#) | [iirshift](#)

# zpkshiftc

---

**Purpose** Zero-pole-gain complex shift frequency transformation

**Syntax**

```
[Z2,P2,K2,AllpassNum,AllpassDen] = zpkshiftc(Z,P,K,Wo,Wt)
[Num,Den,AllpassNum,AllpassDen] = zpkshiftc(Z,P,K,0,0.5)
[Num,Den,AllpassNum,AllpassDen] = zpkshiftc(Z,P,K,0,-0.5)
```

**Description**

`[Z2,P2,K2,AllpassNum,AllpassDen] = zpkshiftc(Z,P,K,Wo,Wt)` returns zeros,  $Z_2$ , poles,  $P_2$ , and gain factor,  $K_2$ , of the target filter transformed from the real lowpass prototype by applying a first-order complex frequency shift transformation. This transformation rotates all the features of an original filter by the same amount specified by the location of the selected feature of the prototype filter, originally at  $W_o$ , placed at  $W_t$  in the target filter.

It also returns the numerator, `AllpassNum`, and the denominator, `AllpassDen`, of the allpass mapping filter. The prototype lowpass filter is given with zeros,  $Z$ , poles,  $P$ , and the gain factor,  $K$ .

`[Num,Den,AllpassNum,AllpassDen] = zpkshiftc(Z,P,K,0,0.5)` performs the Hilbert transformation, i.e. a 90 degree counterclockwise rotation of an original filter in the frequency domain.

`[Num,Den,AllpassNum,AllpassDen] = zpkshiftc(Z,P,K,0,-0.5)` performs the inverse Hilbert transformation, i.e. a 90 degree clockwise rotation of an original filter in the frequency domain.

**Examples**

Design a prototype real IIR halfband filter using a standard elliptic approach:

```
[b, a] = ellip(3,0.1,30,0.409);
z = roots(b);
p = roots(a);
k = b(1);
```

## **Rotation by $\pi/4$ Radians/Sample**

Rotation by -0.25:

```
[z2,p2,k2] = zpkshiftc(z, p, k, 0.5, 0.25);
```

```
hfvt = fvtool(b,a,k2*poly(z2),poly(p2));
```

### Rotation by $\pi/2$ Radians/Sample


```
[z3,p3,k3] = zpkshifto(z, p, k, 0, 0.5);
addfilter(hfvt,k3*poly(z3),poly(p3));
legend(hfvt,'Original Filter','Rotation by  $-\pi/4$  radians/sample',...
        'Rotation by  $\pi/2$  radians/sample');
```

### Rotation by $-\pi/2$ Radians/Sample

```
[z2,p2,k2] = zpkshifto(z, p, k, 0.5, -0.5);
fvtool(b, a, k2*poly(z2), poly(p2));
```


### Result of Example 1

After performing the rotation, the resulting filter shows the features desired.




## Result of Example 2

Similar to the first example, performing the Hilbert transformation generates the desired target filter, shown here.



### Result of Example 3

Finally, using the inverse Hilbert transformation creates yet a third filter, as the figure shows.



### Arguments

Variable	Description
$Z$	Zeros of the prototype lowpass filter
$P$	Poles of the prototype lowpass filter
$K$	Gain factor of the prototype lowpass filter
$W_0$	Frequency value to be transformed from the prototype filter

Variable	Description
$Wt$	Desired frequency location in the transformed target filter
$Z2$	Zeros of the target filter
$P2$	Poles of the target filter
$K2$	Gain factor of the target filter
$AllpassDen$	Numerator of the mapping filter
$AllpassDen$	Denominator of the mapping filter

Frequencies must be normalized to be between -1 and 1, with 1 corresponding to half the sample rate.

## References

Oppenheim, A.V., R.W. Schaffer and J.R. Buck, *Discrete-Time Signal Processing*, Prentice-Hall International Inc., 1989.

Dutta-Roy, S.C. and B. Kumar, "On digital differentiators, Hilbert transformers, and half-band low-pass filters," *IEEE Transactions on Education*, vol. 32, pp. 314-318, August 1989.

## See Also

`zpkftransf` | `allpassshiftc` | `iirshiftc`

**Purpose**

Zero-pole plot for filter

**Syntax**

```
zplane(Hq)
zplane(Hq,plotoption)
zplane(Hq,plotoption,plotoption2)
zplane(Hq,Name,Value)
[zq,pq,kq] = zplane(Hq)
[zq,pq,kq,zr,pr,kr] = zplane(Hq)
```

**Description**

`zplane(Hq)` plots the zeros and poles of a quantized filter `Hq` in the current figure window. The poles and zeros of the quantized and unquantized filters are plotted by default. The symbol `o` represents a zero of the unquantized reference filter, and the symbol `x` represents a pole of that filter. The symbols `□` and `+` are used to plot the zeros and poles of the quantized filter `Hq`. The plot includes the unit circle for reference.

`zplane(Hq,plotoption)` plots the poles and zeros associated with the quantized filter `Hq` according to one specified plot option. The string *plotoption* can be either of the following reference filter display options:

- **'on'** to display the poles and zeros of both the quantized filter and the associated reference filter (default)
- **'off'** to display the poles and zeros of only the quantized filter

`zplane(Hq,plotoption,plotoption2)` plots the poles and zeros associated with the quantized filter `Hq` according to two specified plot options. The string *plotoption* can be selected from the reference filter display options listed in the previous syntax. The string *plotoption2* can be selected from the section-by-section plotting style options described in the following list:

- **'individual'** to display the poles and zeros of each section of the filter in a separate figure window
- **'overlay'** to display the poles and zeros of all sections of the filter on the same plot

# zplane

---

- **'tile'** to display the poles and zeros of each section of the filter in a separate plot in the same figure window

`zplane(Hq,Name,Value)` returns a phase response with additional options specified by one or more `Name,Value` pair arguments. Name-value pair arguments are only available if `Hq` is a filter System object.

`[zq,pq,kq] = zplane(Hq)` returns the vectors of zeros `zq`, poles `pq`, and gains `kq`. If `Hq` has  $n$  sections, `zq`, `pq`, and `kq` are returned as 1-by- $n$  cell arrays. If there are no zeros (or no poles), `zq` (or `pq`) is set to the empty matrix `[]`.

`[zq,pq,kq,zr,pr,kr] = zplane(Hq)` returns the vectors of zeros `zr`, poles `pr`, and gains `kr` of the reference filter associated with the quantized filter `Hq`. It also returns the vectors of zeros `zq`, poles `pq`, and gains `kq` for the quantized filter `Hq`.

## Input Arguments

### `Hq`

`hfilt` is either:

- An adaptive `adaptfilt`, discrete-time `dfilt`, or multirate `mfilt` filter object
- A filter System object. The function supports the following filter structures
  - `dsp.FIRFilter`
  - `dsp.BiquadFilter`
  - `dsp.FIRInterpolator`
  - `dsp.CICInterpolator`
  - `dsp.FIRDecimator`
  - `dsp.CICDecimator`
  - `dsp.FIRRateConverter`

## Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments, where `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes ( `' '`). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

### Arithmetic

`'double' | 'single' | 'fixed'`

For filter System object inputs only, specify the arithmetic used during analysis. When you specify `'double'` or `'single'`, the function performs double- or single-precision analysis. When you specify `'fixed'`, the arithmetic changes depending on the setting of the `CoefficientDataType` property and whether the System object is locked or unlocked.

### Details for Fixed-Point Arithmetic

System Object State	Coefficient Data Type	Rule
Unlocked	'Same as input'	The function assumes that the coefficient data type is signed, 16 bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Unlocked	'Custom'	The function performs fixed-point analysis based on the setting of the <code>CustomCoefficientsDataType</code> property.

System Object State	Coefficient Data Type	Rule
Locked	'Same as input'	When the input data type is 'double' or 'fixed', the function assumes that the coefficient data type is signed, 16-bit, and autoscaled. The function performs fixed-point analysis based on this assumption.
Locked	'Custom'	The function performs fixed-point analysis based on the setting of the CustomCoefficientsDataType property.

When you do not specify the arithmetic for non-CIC structures, the function uses double-precision arithmetic if the filter System object is in an unlocked state. If the System object is locked, the function performs analysis based on the locked input data type. CIC structures only support fixed-point arithmetic.

## Output Arguments

### **zq**

Zeros of quantized filter.

### **pq**

Poles of quantized filter.

### **kq**

Gains of quantized filter.

**zr**

Zeros of reference filter.

**pr**

Poles of reference filter.


**kr**

Gains of reference filter.

## Examples

Create a quantized filter  $H_q$  from a fourth-order digital filter with cutoff frequency of 0.6. Plot the quantized and unquantized poles and zeros associated with this quantized filter.

```
[b,a] = ellip(4,.5,20,.6);  
Hq = dfilt.df2(b, a);  
Hq.arithmetic = 'fixed';  
zplane(Hq);
```



## See Also

[freqz](#) | [impz](#)



# Reference for the Properties of Filter Objects

---

- “Fixed-Point Filter Properties” on page 8-2
- “Adaptive Filter Properties” on page 8-102
- “Multirate Filter Properties” on page 8-115

## Fixed-Point Filter Properties

### In this section...

“Overview of Fixed-Point Filters” on page 8-2

“Fixed-Point Objects and Filters” on page 8-2

“Summary — Fixed-Point Filter Properties” on page 8-5

“Property Details for Fixed-Point Filters” on page 8-18

### Overview of Fixed-Point Filters

There is a distinction between fixed-point filters and quantized filters — quantized filters represent a superset that includes fixed-point filters.

When `dfilt` objects have their `Arithmetic` property set to `single` or `fixed`, they are quantized filters. However, after you set the `Arithmetic` property to `fixed`, the resulting filter is both quantized and fixed-point. Fixed-point filters perform arithmetic operations without allowing the binary point to move in response to the calculation — hence the name fixed-point. You can find out more about fixed-point arithmetic in your Fixed-Point Toolbox documentation or from the Help system.

With the `Arithmetic` property set to `single`, meaning the filter uses single-precision floating-point arithmetic, the filter allows the binary point to move during mathematical operations, such as sums or products. Therefore these filters cannot be considered fixed-point filters. But they are quantized filters.

The following sections present the properties for fixed-point filters, which includes all the properties for double-precision and single-precision floating-point filters as well.

### Fixed-Point Objects and Filters

Fixed-point filters depend in part on fixed-point objects from Fixed-Point Toolbox software. You can see this when you display a fixed-point filter at the command prompt.

```
hd=dfilt.df2t
```

```
hd =  
  
    FilterStructure: 'Direct-Form II Transposed'  
        Arithmetic: 'double'  
        Numerator: 1  
        Denominator: 1  
    PersistentMemory: false  
        States: [0x1 double]  
  
set(hd,'arithmetic','fixed')  
hd  
  
hd =  
  
    FilterStructure: 'Direct-Form II Transposed'  
        Arithmetic: 'fixed'  
        Numerator: 1  
        Denominator: 1  
    PersistentMemory: false  
        States: [1x1 embedded.fi]  
  
    CoeffWordLength: 16  
        CoeffAutoScale: true  
        Signed: true  
  
    InputWordLength: 16  
    InputFracLength: 15  
  
    OutputWordLength: 16  
    OutputFracLength: 15  
  
    StateWordLength: 16  
        StateAutoScale: true  
  
        ProductMode: 'FullPrecision'  
  
    AccumWordLength: 40  
        CastBeforeSum: true
```

```
RoundMode: 'convergent'  
OverflowMode: 'wrap'
```

Look at the States property, shown here

```
States: [1x1 embedded.fi]
```

The notation `embedded.fi` indicates that the states are being represented by fixed-point objects, usually called `fi` objects. If you take a closer look at the property `States`, you see how the properties of the `fi` object represent the values for the filter states.

```
hd.states
```

```
ans =
```

```
[]
```

```
DataType: Fixed  
Scaling: BinaryPoint  
Signed: true  
WordLength: 16  
FractionLength: 15
```

```
RoundMode: round  
OverflowMode: saturate  
ProductMode: FullPrecision  
MaxProductWordLength: 128  
SumMode: FullPrecision  
MaxSumWordLength: 128  
CastBeforeSum: true
```

To learn more about `fi` objects (fixed-point objects) in general, refer to your Fixed-Point Toolbox documentation.

As inputs (data to be filtered), fixed-point filters accept both regular double-precision values and `fi` objects. Which you use depends on your needs. How your filter responds to the input data is determined by the settings of the filter properties, discussed in the next few sections.

## Summary – Fixed-Point Filter Properties

Discrete-time filters in this toolbox use objects that perform the filtering and configuration of the filter. As objects, they include properties and methods that are often referred to as functions — not strictly the same as MATLAB functions but mostly so) to provide filtering capability. In discrete-time filters, or `dfilt` objects, many of the properties are dynamic, meaning they become available depending on the settings of other properties in the `dfilt` object or filter.

### Dynamic Properties

When you use a `dfilt.structure` function to create a filter, MATLAB displays the filter properties in the command window in return (unless you end the command with a semicolon which suppresses the output display). Generally you see six or seven properties, ranging from the property `FilterStructure` to `PersistentMemory`. These first properties are always present in the filter. One of the most important properties is `Arithmetic`. The `Arithmetic` property controls all of the dynamic properties for a filter.

Dynamic properties become available when you change another property in the filter. For example, when you change the `Arithmetic` property value to `fixed`, the display now shows many more properties for the filter, all of them considered dynamic. Here is an example that uses a direct form II filter. First create the default filter:

```
hd=dfilt.df2
```

```
hd =
```

```

    FilterStructure: 'Direct-Form II'
      Arithmetic: 'double'
        Numerator: 1
        Denominator: 1
 PersistentMemory: false
           States: [0x1 double]
```

With the filter `hd` in the workspace, convert the arithmetic to fixed-point. Do this by setting the property `Arithmetic` to `fixed`. Notice the display. Instead of a few properties, the filter now has many more, each one related

to a particular part of the filter and its operation. Each of the now-visible properties is dynamic.

```
hd.arithmetic='fixed'
```

```
hd =
```

```
    FilterStructure: 'Direct-Form II'  
      Arithmetic: 'fixed'  
      Numerator: 1  
      Denominator: 1  
    PersistentMemory: false  
      States: [1x1 embedded.fi]  
  
    CoeffWordLength: 16  
      CoeffAutoScale: true  
      Signed: true  
  
    InputWordLength: 16  
    InputFracLength: 15  
  
    OutputWordLength: 16  
      OutputMode: 'AvoidOverflow'  
  
    StateWordLength: 16  
    StateFracLength: 15  
  
      ProductMode: 'FullPrecision'  
  
    AccumWordLength: 40  
      CastBeforeSum: true  
  
      RoundMode: 'convergent'  
      OverflowMode: 'wrap'
```

Even this list of properties is not yet complete. Changing the value of other properties such as the `ProductMode` or `CoeffAutoScale` properties may reveal even more properties that control how the filter works. Remember this feature about `dfilt` objects and dynamic properties as you review the rest of this section about properties of fixed-point filters.

An important distinction is you cannot change the value of a property unless you see the property listed in the default display for the filter. Entering the filter name at the MATLAB prompt generates the default property display for the named filter. Using `get(filtername)` does not generate the default display — it lists all of the filter properties, both those that you can change and those that are not available yet.

The following table summarizes the properties, static and dynamic, of fixed-point filters and provides a brief description of each. Full descriptions of each property, in alphabetical order, follow the table.

Property Name	Valid Values [Default Value]	Brief Description
AccumFracLength	Any positive or negative integer number of bits [29]	Specifies the fraction length used to interpret data output by the accumulator. This is a property of FIR filters and lattice filters. IIR filters have two similar properties — <code>DenAccumFracLength</code> and <code>NumAccumFracLength</code> — that let you set the precision for numerator and denominator operations separately.
AccumWordLength	Any positive integer number of bits [40]	Sets the word length used to store data in the accumulator/buffer.
Arithmetic	[Double], single, fixed	Defines the arithmetic the filter uses. Gives you the options <code>double</code> , <code>single</code> , and <code>fixed</code> . In short, this property defines the operating mode for your filter.
CastBeforeSum	[True] or false	Specifies whether to cast numeric data to the appropriate accumulator format (as shown in the signal flow diagrams) before performing sum operations.

Property Name	Valid Values [Default Value]	Brief Description
CoeffAutoScale	[True] or false	Specifies whether the filter automatically chooses the proper fraction length to represent filter coefficients without overflowing. Turning this off by setting the value to <code>false</code> enables you to change the <code>NumFracLength</code> and <code>DenFracLength</code> properties to specify the precision used.
CoeffFracLength	Any positive or negative integer number of bits [14]	Set the fraction length the filter uses to interpret coefficients. <code>CoeffFracLength</code> is not available until you set <code>CoeffAutoScale</code> to <code>false</code> . Scalar filters include this property.
CoeffWordLength	Any positive integer number of bits [16]	Specifies the word length to apply to filter coefficients.
DenAccumFracLength	Any positive or negative integer number of bits [29]	Specifies how the filter algorithm interprets the results of addition operations involving denominator coefficients.
DenFracLength	Any positive or negative integer number of bits [14]	Sets the fraction length the filter uses to interpret denominator coefficients. <code>DenFracLength</code> is always available, but it is read-only until you set <code>CoeffAutoScale</code> to <code>false</code> .
Denominator	Any filter coefficient value [1]	Holds the denominator coefficients for IIR filters.
DenProdFracLength	Any positive or negative integer number of bits [29]	Specifies how the filter algorithm interprets the results of product operations involving denominator coefficients. You can change this property value after you set <code>ProductMode</code> to <code>SpecifyPrecision</code> .

<b>Property Name</b>	<b>Valid Values [Default Value]</b>	<b>Brief Description</b>
DenStateFracLength	Any positive or negative integer number of bits [15]	Specifies the fraction length used to interpret the states associated with denominator coefficients in the filter.
FracDelay	Any decimal value between 0 and 1 samples	Specifies the fractional delay provided by the filter, in decimal fractions of a sample.
FDAutoScale	[True] or false	Specifies whether the filter automatically chooses the proper scaling to represent the fractional delay value without overflowing. Turning this off by setting the value to <code>false</code> enables you to change the <code>FDWordLength</code> and <code>FDFracLength</code> properties to specify the data format applied.
FDFracLength	Any positive or negative integer number of bits [5]	Specifies the fraction length to represent the fractional delay.
FDProdFracLength	Any positive or negative integer number of bits [34]	Specifies the fraction length to represent the result of multiplying the coefficients with the fractional delay.
FDProdWordLength	Any positive or negative integer number of bits [39]	Specifies the word length to represent result of multiplying the coefficients with the fractional delay.
FDWordLength	Any positive or negative integer number of bits [6]	Specifies the word length to represent the fractional delay.
DenStateWordLength	Any positive integer number of bits [16]	Specifies the word length used to represent the states associated with denominator coefficients in the filter.

<b>Property Name</b>	<b>Valid Values [Default Value]</b>	<b>Brief Description</b>
FilterInternals	[FullPrecision], SpecifyPrecision	Controls whether the filter sets the output word and fraction lengths, and the accumulator word and fraction lengths automatically to maintain the best precision results during filtering. The default value, FullPrecision, sets automatic word and fraction length determination by the filter. SpecifyPrecision exposes the output and accumulator related properties so you can set your own word and fraction lengths for them.
FilterStructure	Not applicable.	Describes the signal flow for the filter object, including all of the active elements that perform operations during filtering — gains, delays, sums, products, and input/output.
InputFracLength	Any positive or negative integer number of bits [15]	Specifies the fraction length the filter uses to interpret data to be processed by the filter.
InputWordLength	Any positive integer number of bits [16]	Specifies the word length applied to represent input data.
Ladder	Any ladder coefficients in double-precision data type [1]	latticearma filters include this property to store the ladder coefficients.
LadderAccumFracLength	Any positive or negative integer number of bits [29]	latticearma filters use this to define the fraction length applied to values output by the accumulator that stores the results of ladder computations.
LadderFracLength	Any positive or negative integer number of bits [14]	latticearma filters use ladder coefficients in the signal flow. This property determines the fraction length used to interpret the coefficients.

<b>Property Name</b>	<b>Valid Values [Default Value]</b>	<b>Brief Description</b>
Lattice	Any lattice structure coefficients. No default value.	Stores the lattice coefficients for lattice-based filters.
LatticeAccumFracLength	Any positive or negative integer number of bits [29]	Specifies how the accumulator outputs the results of operations on the lattice coefficients.
LatticeFracLength	Any positive or negative integer number of bits [15]	Specifies the fraction length applied to the lattice coefficients.
MultiplicandFracLength	Any positive or negative integer number of bits [15]	Sets the fraction length for values used in product operations in the filter. Direct-form I transposed (df1t) filter structures include this property.
MultiplicandWordLength	Any positive integer number of bits [16]	Sets the word length applied to the values input to a multiply operation (the multiplicands). The filter structure df1t includes this property.
NumAccumFracLength	Any positive or negative integer number of bits [29]	Specifies how the filter algorithm interprets the results of addition operations involving numerator coefficients.
Numerator	Any double-precision filter coefficients [1]	Holds the numerator coefficient values for the filter.
NumFracLength	Any positive or negative integer number of bits [14]	Sets the fraction length used to interpret the numerator coefficients.
NumProdFracLength	Any positive or negative integer number of bits [29]	Specifies how the filter algorithm interprets the results of product operations involving numerator coefficients. You can change the property value after you set ProductMode to SpecifyPrecision.

<b>Property Name</b>	<b>Valid Values [Default Value]</b>	<b>Brief Description</b>
NumStateFracLength	Any positive or negative integer number of bits [15]	For IIR filters, this defines the fraction length applied to the numerator states of the filter. Specifies the fraction length used to interpret the states associated with numerator coefficients in the filter.
NumStateWordLength	Any positive integer number of bits [16]	For IIR filters, this defines the word length applied to the numerator states of the filter. Specifies the word length used to interpret the states associated with numerator coefficients in the filter.
OutputFracLength	Any positive or negative integer number of bits — [15] or [12] bits depending on the filter structure	Determines how the filter interprets the filtered data. You can change the value of OutputFracLength after you set OutputMode to SpecifyPrecision.
OutputMode	[AvoidOverflow], BestPrecision, SpecifyPrecision	<p>Sets the mode the filter uses to scale the filtered input data. You have the following choices:</p> <ul style="list-style-type: none"> <li>• <b>AvoidOverflow</b> — directs the filter to set the output data fraction length to avoid causing the data to overflow.</li> <li>• <b>BestPrecision</b> — directs the filter to set the output data fraction length to maximize the precision in the output data.</li> <li>• <b>SpecifyPrecision</b> — lets you set the fraction length used by the filtered data.</li> </ul>
OutputWordLength	Any positive integer number of bits [16]	Determines the word length used for the filtered data.

Property Name	Valid Values [Default Value]	Brief Description
OverflowMode	Saturate or [wrap]	Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either <b>saturate</b> (limit the output to the largest positive or negative representable value) or <b>wrap</b> (set overflowing values to the nearest representable value using modular arithmetic). The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow — hey maintain full precision.
ProductFracLength	Any positive or negative integer number of bits [29]	For the output from a product operation, this sets the fraction length used to interpret the numeric data. This property becomes writable (you can change the value) after you set <b>ProductMode</b> to <b>SpecifyPrecision</b> .
ProductMode	[FullPrecision], KeepLSB, KeepMSB, SpecifyPrecision	Determines how the filter handles the output of product operations. Choose from full precision ( <b>FullPrecision</b> ), or whether to keep the most significant bit ( <b>KeepMSB</b> ) or least significant bit ( <b>KeepLSB</b> ) in the result when you need to shorten the data words. For you to be able to set the precision (the fraction length) used by the output from the multiplies, you set <b>ProductMode</b> to <b>SpecifyPrecision</b> .

Property Name	Valid Values [Default Value]	Brief Description
ProductWordLength	Any positive number of bits. Default is 16 or 32 depending on the filter structure	Specifies the word length to use for the results of multiplication operations. This property becomes writable (you can change the value) after you set ProductMode to SpecifyPrecision.
PersistentMemory	True or [false]	Specifies whether to reset the filter states and memory before each filtering operation. Lets you decide whether your filter retains states from previous filtering runs. True is the default setting.
RoundMode	[Convergent], ceil, fix, floor, nearest, round	<p>Sets the mode the filter uses to quantize numeric values when the values lie between representable values for the data format (word and fraction lengths).</p> <ul style="list-style-type: none"> <li>• <b>ceil</b> - Round toward positive infinity.</li> <li>• <b>convergent</b> - Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.</li> <li>• <b>fix</b> - Round toward zero.</li> <li>• <b>floor</b> - Round toward negative infinity.</li> <li>• <b>nearest</b> - Round toward nearest. Ties round toward positive infinity.</li> <li>• <b>round</b> - Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.</li> </ul>

Property Name	Valid Values [Default Value]	Brief Description
		The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always round. Finally, products never overflow — they maintain full precision.
ScaleValueFracLength	Any positive or negative integer number of bits [29]	Scale values work with SOS filters. Setting this property controls how your filter interprets the scale values by setting the fraction length. Available only when you disable <code>CoeffAutoScale</code> by setting it to <code>false</code> .
ScaleValues	[2 x 1 double] array with values of 1	Stores the scaling values for sections in SOS filters.
Signed	[True] or false	Specifies whether the filter uses signed or unsigned fixed-point coefficients. Only coefficients reflect this property setting.
sosMatrix	[1 0 0 1 0 0]	Holds the filter coefficients as property values. Displays the matrix in the format [sections x coefficients/section datatype]. A [15x6 double] SOS matrix represents a filter with 6 coefficients per section and 15 sections, using data type <code>double</code> to represent the coefficients.

<b>Property Name</b>	<b>Valid Values [Default Value]</b>	<b>Brief Description</b>
SectionInputAuto Scale	[True] or false	Specifies whether the filter automatically chooses the proper fraction length to prevent overflow by data entering a section of an SOS filter. Setting this property to <b>false</b> enables you to change the SectionInputFracLength property to specify the precision used. Available only for SOS filters.
SectionInputFrac Length	Any positive or negative integer number of bits [29]	Section values work with SOS filters. Setting this property controls how your filter interprets the section values between sections of the filter by setting the fraction length. This applies to data entering a section. Compare to SectionOutputFracLength. Available only when you disable SectionInputAutoScale by setting it to <b>false</b> .
SectionInputWord Length	Any positive or negative integer number of bits [29]	Sets the word length used to represent the data moving into a section of an SOS filter.
SectionOutputAuto Scale	[True] or false	Specifies whether the filter automatically chooses the proper fraction length to prevent overflow by data leaving a section of an SOS filter. Setting this property to <b>false</b> enables you to change the SectionOutputFracLength property to specify the precision used.

<b>Property Name</b>	<b>Valid Values [Default Value]</b>	<b>Brief Description</b>
SectionOutputFracLength	Any positive or negative integer number of bits [29]	Section values work with SOS filters. Setting this property controls how your filter interprets the section values between sections of the filter by setting the fraction length. This applies to data leaving a section. Compare to SectionInputFracLength. Available after you disable SectionOutputAutoScale by setting it to false.
SectionOutputWordLength	Any positive or negative integer number of bits [32]	Sets the word length used to represent the data moving out of one section of an SOS filter.
StateFracLength	Any positive or negative integer number of bits [15]	Lets you set the fraction length applied to interpret the filter states.
States	[1x1 embedded fi]	Contains the filter states before, during, and after filter operations. States act as filter memory between filtering runs or sessions. Notice that the states use fi objects, with the associated properties from those objects. For details, refer to filtstates in your Signal Processing Toolbox documentation or in the Help system.
StateWordLength	Any positive integer number of bits [16]	Sets the word length used to represent the filter states.
TapSumFracLength	Any positive or negative integer number of bits [15]	Sets the fraction length used to represent the filter tap values in addition operations. This is available after you set TapSumMode to false. Symmetric and antisymmetric FIR filters include this property.

Property Name	Valid Values [Default Value]	Brief Description
TapSumMode	FullPrecision, KeepLSB, [KeepMSB], SpecifyPrecision	Determines how the accumulator outputs stored that involve filter tap weights. Choose from full precision (FullPrecision) to prevent overflows, or whether to keep the most significant bits (KeepMSB) or least significant bits (KeepLSB) when outputting results from the accumulator. To let you set the precision (the fraction length) used by the output from the accumulator, set <code>FilterInternals</code> to <code>SpecifyPrecision</code> .  Symmetric and antisymmetric FIR filters include this property.
TapSumWordLength	Any positive number of bits [17]	Sets the word length used to represent the filter tap weights during addition. Symmetric and antisymmetric FIR filters include this property.

## Property Details for Fixed-Point Filters

When you create a fixed-point filter, you are creating a filter object (a `dfilt` object). In this manual, the terms filter, `dfilt` object, and filter object are used interchangeably. To filter data, you apply the filter object to your data set. The output of the operation is the data filtered by the filter and the filter property values.

Filter objects have properties to which you assign property values. You use these property values to assign various characteristics to the filters you create, including

- The type of arithmetic to use in filtering operations
- The structure of the filter used to implement the filter (not a property you can set or change — you select it by the `dfilt.structure` function you choose)

- The locations of quantizations and cast operations in the filter
- The data formats used in quantizing, casting, and filtering operations

Details of the properties associated with fixed-point filters are described in alphabetical order on the following pages.

### **AccumFracLength**

Except for state-space filters, all `dfilt` objects that use fixed arithmetic have this property that defines the fraction length applied to data in the accumulator. Combined with `AccumWordLength`, `AccumFracLength` helps fully specify how the accumulator outputs data after processing addition operations. As with all fraction length properties, `AccumFracLength` can be any integer, including integers larger than `AccumWordLength`, and positive or negative integers.

### **AccumWordLength**

You use `AccumWordLength` to define the data word length used in the accumulator. Set this property to a value that matches your intended hardware. For example, many digital signal processors use 40-bit accumulators, so set `AccumWordLength` to 40 in your fixed-point filter:

```
set(hq,'arithmetic','fixed');
set(hq,'AccumWordLength',40);
```

Note that `AccumWordLength` only applies to filters whose `Arithmetic` property value is `fixed`.

### **Arithmetic**

Perhaps the most important property when you are working with `dfilt` objects, `Arithmetic` determines the type of arithmetic the filter uses, and the properties or quantizers that compose the fixed-point or quantized filter. You use strings to set the `Arithmetic` property value.

The next table shows the valid strings for the `Arithmetic` property. Following the table, each property string appears with more detailed information about what happens when you select the string as the value for `Arithmetic` in your `dfilt`.

<b>Arithmetic Property String</b>	<b>Brief Description of Effect on the Filter</b>
double	All filtering operations and coefficients use double-precision floating-point representations and math. When you use <code>dfilt.structure</code> to create a filter object, <code>double</code> is the default value for the Arithmetic property.
single	All filtering operations and coefficients use single-precision floating-point representations and math.
fixed	This string applies selected default values for the properties in the fixed-point filter object, including such properties as coefficient word lengths, fraction lengths, and various operating modes. Generally, the default values match those you use on many digital signal processors. Allows signed fixed data types only. Fixed-point arithmetic filters are available only when you install Fixed-Point Toolbox software with this toolbox.

**double.** When you use one of the `dfilt.structure` methods to create a filter, the Arithmetic property value is `double` by default. Your filter is identical to the same filter without the Arithmetic property, as you would create if you used Signal Processing Toolbox software.

Double means that the filter uses double-precision floating-point arithmetic in all operations while filtering:

- All input to the filter must be double data type. Any other data type returns an error.
- The states and output are doubles as well.
- All internal calculations are done in double math.

When you use `double` data type filter coefficients, the reference and quantized (fixed-point) filter coefficients are identical. The filter stores the reference coefficients as double data type.

**single.** When your filter should use single-precision floating-point arithmetic, set the `Arithmetic` property to `single` so all arithmetic in the filter processing gets restricted to single-precision data type.

- Input data must be single data type. Other data types return errors.
- The filter states and filter output use single data type.

When you choose `single`, you can provide the filter coefficients in either of two ways:

- Double data type coefficients. With `Arithmetic` set to `single`, the filter casts the double data type coefficients to single data type representation.
- Single data type. These remain unchanged by the filter.

Depending on whether you specified single or double data type coefficients, the reference coefficients for the filter are stored in the data type you provided. If you provide coefficients in double data type, the reference coefficients are double as well. Providing single data type coefficients generates single data type reference coefficients. Note that the arithmetic used by the reference filter is always double.

When you use `refilter` to create a reference filter from the reference coefficients, the resulting filter uses double-precision versions of the reference filter coefficients.

To set the `Arithmetic` property value, create your filter, then use `set` to change the `Arithmetic` setting, as shown in this example using a direct form FIR filter.

```
b=fir1(7,0.45);
```

```
hd=dfilt.dffir(b)
```

```
hd =
```

```

    FilterStructure: 'Direct-Form FIR'
      Arithmetic: 'double'
      Numerator: [1x8 double]
 PersistentMemory: false

```

```
States: [7x1 double]

set(hd,'arithmetic','single')
hd

hd =

    FilterStructure: 'Direct-Form FIR'
    Arithmetic: 'single'
    Numerator: [1x8 double]
    PersistentMemory: false
    States: [7x1 single]
```

**fixed.** Converting your `dfilt` object to use fixed arithmetic results in a filter structure that uses properties and property values to match how the filter would behave on digital signal processing hardware.

---

**Note** The `fixed` option for the property `Arithmetic` is available only when you install Fixed-Point Toolbox software as well as DSP System Toolbox software.

---

After you set `Arithmetic` to `fixed`, you are free to change any property value from the default value to a value that more closely matches your needs. You cannot, however, mix floating-point and fixed-point arithmetic in your filter when you select `fixed` as the `Arithmetic` property value. Choosing `fixed` restricts you to using either fixed-point or floating point throughout the filter (the data type must be homogenous). Also, all data types must be signed. `fixed` does not support unsigned data types except for unsigned coefficients when you set the property `Signed` to `false`. Mixing word and fraction lengths within the fixed object is acceptable. In short, using fixed arithmetic assumes

- fixed word length.
- fixed size and dedicated accumulator and product registers.
- the ability to do either saturation or wrap arithmetic.
- that multiple rounding modes are available.

Making these assumptions simplifies your job of creating fixed-point filters by reducing repetition in the filter construction process, such as only requiring you to enter the accumulator word size once, rather than for each step that uses the accumulator.

Default property values are a starting point in tailoring your filter to common hardware, such as choosing 40-bit word length for the accumulator, or 16-bit words for data and coefficients.

In this `dfilt` object example, `get` returns the default values for `dfilt.df1t` structures.

```
[b,a]=butter(6,0.45);
hd=dfilt.df1(b,a)
```

```
hd =
```

```
    FilterStructure: 'Direct-Form I'
      Arithmetic: 'double'
      Numerator: [1x7 double]
      Denominator: [1x7 double]
 PersistentMemory: false
      States: Numerator: [6x1 double]
            Denominator:[6x1 double]
```

```
set(hd,'arithmetic','fixed')
get(hd)
```

```
 PersistentMemory: false
  FilterStructure: 'Direct-Form I'
      States: [1x1 filtstates.dfiir]
      Numerator: [1x7 double]
      Denominator: [1x7 double]
      Arithmetic: 'fixed'
  CoeffWordLength: 16
  CoeffAutoScale: 1
      Signed: 1
      RoundMode: 'convergent'
  OverflowMode: 'wrap'
  InputWordLength: 16
```

```
    InputFracLength: 15
      ProductMode: 'FullPrecision'
    OutputWordLength: 16
    OutputFracLength: 15
      NumFracLength: 16
      DenFracLength: 14
    ProductWordLength: 32
    NumProdFracLength: 31
    DenProdFracLength: 29
      AccumWordLength: 40
    NumAccumFracLength: 31
    DenAccumFracLength: 29
      CastBeforeSum: 1
```

Here is the default display for `hd`.

```
hd
```

```
hd =
```

```
    FilterStructure: 'Direct-Form I'
      Arithmetic: 'fixed'
      Numerator: [1x7 double]
      Denominator: [1x7 double]
    PersistentMemory: false
      States: Numerator: [6x1 fi]
             Denominator:[6x1 fi]
```

```
    CoeffWordLength: 16
      CoeffAutoScale: true
      Signed: true
```

```
    InputWordLength: 16
    InputFracLength: 15
```

```
    OutputWordLength: 16
    OutputFracLength: 15
```

```
      ProductMode: 'FullPrecision'
```

```

AccumWordLength: 40
CastBeforeSum: true

RoundMode: 'convergent'
OverflowMode: 'wrap'

```

This second example shows the default property values for `dfilt.latticemamax` filter objects, using the coefficients from an `fir1` filter.

```

b=fir1(7,0.45)

hdlat=dfilt.latticemamax(b)

hdlat =

    FilterStructure: [1x45 char]
      Arithmetic: 'double'
      Lattice: [1x8 double]
 PersistentMemory: false
      States: [8x1 double]

hdlat.arithmetic='fixed'

hdlat =

    FilterStructure: [1x45 char]
      Arithmetic: 'fixed'
      Lattice: [1x8 double]
 PersistentMemory: false
      States: [1x1 embedded.fi]

    CoeffWordLength: 16
      CoeffAutoScale: true
      Signed: true

    InputWordLength: 16
    InputFracLength: 15

```

```
OutputWordLength: 16
    OutputMode: 'AvoidOverflow'

StateWordLength: 16
StateFracLength: 15

    ProductMode: 'FullPrecision'

AccumWordLength: 40
    CastBeforeSum: true

    RoundMode: 'convergent'
    OverflowMode: 'wrap'
```

Unlike the `single` or `double` options for `Arithmetic`, `fixed` uses properties to define the word and fraction lengths for each portion of your filter. By changing the property value of any of the properties, you control your filter performance. Every word length and fraction length property is independent — set the one you need and the others remain unchanged, such as setting the input word length with `InputWordLength`, while leaving the fraction length the same.

```
d=fdesign.lowpass('n,fc',6,0.45)
```

```
d =
```

```
    Response: 'Lowpass with cutoff'
    Specification: 'N,Fc'
    Description: {2x1 cell}
    NormalizedFrequency: true
        Fs: 'Normalized'
    FilterOrder: 6
    Fcutoff: 0.4500
```

```
designmethods(d)
```

```
Design Methods for class fdesign.lowpass:
```

```
butter

hd=butter(d)

hd =

    FilterStructure: 'Direct-Form II, Second-Order Sections'
      Arithmetic: 'double'
      sosMatrix: [3x6 double]
      ScaleValues: [4x1 double]
PersistentMemory: false
      States: [2x3 double]

hd.arithmetic='fixed'

hd =

    FilterStructure: 'Direct-Form II, Second-Order Sections'
      Arithmetic: 'fixed'
      sosMatrix: [3x6 double]
      ScaleValues: [4x1 double]
PersistentMemory: false
      States: [1x1 embedded.fi]

    CoeffWordLength: 16
      CoeffAutoScale: true
      Signed: true

    InputWordLength: 16
    InputFracLength: 15

    SectionInputWordLength: 16
    SectionInputAutoScale: true

    SectionOutputWordLength: 16
    Section OutputAutoScale: true

      OutputWordLength: 16
      OutputMode: 'AvoidOverflow'
```

```
StateWordLength: 16
StateFracLength: 15

    ProductMode: 'FullPrecision'

AccumWordLength: 40
CastBeforeSum: true

    RoundMode: 'convergent'
    OverflowMode: 'wrap'

hd.inputWordLength=12

hd =

    FilterStructure: 'Direct-Form II, Second-Order Sections'
    Arithmetic: 'fixed'
    sosMatrix: [3x6 double]
    ScaleValues: [4x1 double]
PersistentMemory: false
    States: [1x1 embedded.fi]

    CoeffWordLength: 16
    CoeffAutoScale: true
    Signed: true

    InputWordLength: 12
    InputFracLength: 15

    SectionInputWordLength: 16
    SectionInputAutoScale: true

    SectionOutputWordLength: 16
    SectionOutputAutoScale: true

    OutputWordLength: 16
    OutputMode: 'AvoidOverflow'

    StateWordLength: 16
```

```
StateFracLength: 15

    ProductMode: 'FullPrecision'

AccumWordLength: 40
CastBeforeSum: true

    RoundMode: 'convergent'
    OverflowMode: 'wrap'
```

Notice that the properties for the lattice filter `hdlat` and direct-form II filter `hd` are different, as befits their differing filter structures. Also, some properties are common to both objects, such as `RoundMode` and `PersistentMemory` and behave the same way in both objects.

**Notes About Fraction Length, Word Length, and Precision.** Word length and fraction length combine to make the format for a fixed-point number, where word length is the number of bits used to represent the value and fraction length specifies, in bits, the location of the binary point in the fixed-point representation. Therein lies a problem — fraction length, which you specify in bits, can be larger than the word length, or a negative number of bits. This section explains how that idea works and how you might use it.

Unfortunately fraction length is somewhat misnamed (although it continues to be used in this User's Guide and elsewhere for historical reasons).

Fraction length defined as the number of fractional bits (bits to the right of the binary point) is true only when the fraction length is positive and less than or equal to the word length. In MATLAB format notation you can use `[word length fraction length]`. For example, for the format `[16 16]`, the second 16 (the fraction length) is the number of fractional bits or bits to the right of the binary point. In this example, all 16 bits are to the right of the binary point.

But it is also possible to have fixed-point formats of `[16 18]` or `[16 -45]`. In these cases the fraction length can no longer be the number of bits to the right of the binary point since the format says the word length is 16 — there cannot be 18 fraction length bits on the right. And how can there be a negative number of bits for the fraction length, such as `[16 -45]`?

A better way to think about fixed-point format [word length fraction length] and what it means is that the representation of a fixed-point number is a weighted sum of powers of two driven by the fraction length, or the two's complement representation of the fixed-point number.

Consider the format [B L], where the fraction length L can be positive, negative, 0, greater than B (the word length) or less than B. (B and L are always integers and B is always positive.)

Given a binary string  $b(1) b(2) b(3) \dots b(B)$ , to determine the two's-complement value of the string in the format described by [B L], use the value of the individual bits in the binary string in the following formula, where  $b(1)$  is the first binary bit (and most significant bit, MSB),  $b(2)$  is the second, and on up to  $b(B)$ .

The decimal numeric value that those bits represent is given by

$$\text{value} = -b(1) * 2^{(B-L-1)} + b(2) * 2^{(B-L-2)} + b(3) * 2^{(B-L-3)} + \dots + b(B) * 2^{(-L)}$$

L, the fraction length, represents the negative of the weight of the last, or least significant bit (LSB). L is also the step size or the precision provided by a given fraction length.

**Precision.** Here is how precision works.

When all of the bits of a binary string are zero except for the LSB (which is therefore equal to one), the value represented by the bit string is given by  $2^{(-L)}$ . If L is negative, for example  $L=-16$ , the value is  $2^{16}$ . The smallest step between numbers that can be represented in a format where  $L=-16$  is given by  $1 \times 2^{16}$  (the rightmost term in the formula above), which is 65536. Note the precision does not depend on the word length.

Take a look at another example. When the word length set to 8 bits, the decimal value 12 is represented in binary by 00001100. That 12 is the decimal equivalent of 00001100 tells you that you are using [8 0] data format representation — the word length is 8 bits and fraction length 0 bits, and the step size or precision (the smallest difference between two adjacent values in the format [8,0], is  $2^0=1$ .

Suppose you plan to keep only the upper 5 bits and discard the other three. The resulting precision after removing the right-most three bits comes from the weight of the lowest remaining bit, the fifth bit from the left, which is  $2^3=8$ , so the format would be [5,-3].

Note that in this format the step size is 8, I cannot represent numbers that are between multiples of 8.

In MATLAB, with Fixed-Point Toolbox software installed:

```
x=8;
q=quantizer([8,0]); % Word length = 8, fraction length = 0
xq=quantize(q,x);
binxq=num2bin(q,xq);
q1=quantizer([5 -3]); % Word length = 5, fraction length = -3
xq1 = quantize(q1,xq);
binxq1=num2bin(q1,xq1);
binxq
```

binxq =

00001000

binxq1

binxq1 =

00001

But notice that in [5,-3] format, 00001 is the two's complement representation for 8, not for 1;  $q = \text{quantizer}([8 \ 0])$  and  $q1 = \text{quantizer}([5 \ -3])$  are not the same. They cover the about the same range —  $\text{range}(q) > \text{range}(q1)$  — but their quantization step is different —  $\text{eps}(q) = 8$ , and  $\text{eps}(q1) = 1$ .

Look at one more example. When you construct a quantizer  $q$

```
q = quantizer([a,b])
```

the first element in  $[a,b]$  is  $a$ , the word length used for quantization. The second element in the expression,  $b$ , is related to the quantization step — the numerical difference between the two closest values that the quantizer

can represent. This is also related to the weight given to the LSB. Note that  $2^{-b} = \text{eps}(q)$ .

Now construct two quantizers, `q1` and `q2`. Let `q1` use the format `[32,0]` and let `q2` use the format `[16, -16]`.

```
q1 = quantizer([32,0])
q2 = quantizer([16, -16])
```

Quantizers `q1` and `q2` cover the same range, but `q2` has less precision. It covers the range in steps of  $2^{16}$ , while `q1` covers the range in steps of 1.

This lost precision is due to (or can be used to model) throwing out 16 least-significant bits.

An important point to understand is that in `dfilt` objects and filtering you control which bits are carried from the sum and product operations in the filter to the filter output by setting the format for the output from the sum or product operation.

For instance, if you use `[16 0]` as the output format for a 32-bit result from a sum operation when the original format is `[32 0]`, you take the lower 16 bits from the result. If you use `[16 -16]`, you take the higher 16 bits of the original 32 bits. You could even take 16 bits somewhere in between the 32 bits by choosing something like `[16 -8]`, but you probably do not want to do that.

Filter scaling is directly implicated in the format and precision for a filter. When you know the filter input and output formats, as well as the filter internal formats, you can scale the inputs or outputs to stay within the format ranges. For more information about scaling filters, refer to “Floating-Point to Fixed-Point Filter Conversion”.

Notice that overflows or saturation might occur at the filter input, filter output, or within the filter itself, such as during add or multiply or accumulate operations. Improper scaling at any point in the filter can result in numerical errors that dramatically change the performance of your fixed-point filter implementation.

## CastBeforeSum

Setting the `CastBeforeSum` property determines how the filter handles the input values to sum operations in the filter. After you set your filter `Arithmetic` property value to `fixed`, you have the option of using `CastBeforeSum` to control the data type of some inputs (addends) to summations in your filter. To determine which addends reflect the `CastBeforeSum` property setting, refer to the reference page for the signal flow diagram for the filter structure.

`CastBeforeSum` specifies whether to cast selected addends to summations in the filter to the output format from the addition operation before performing the addition. When you specify `true` for the property value, the results of the affected sum operations match most closely the results found on most digital signal processors. Performing the cast operation before the summation adds one or two additional quantization operations that can add error sources to your filter results.


Specifying `CastBeforeSum` to be `false` prevents the addends from being cast to the output format before the addition operation. Choose this setting to get the most accurate results from summations without considering the hardware your filter might use.

Notice that the output format for every sum operation reflects the value of the output property specified in the filter structure diagram. Which input property is referenced by `CastBeforeSum` depends on the structure.

Property Value	Description
<code>false</code>	Configures filter summation operations to retain the addends in the format carried from the previous operation.
<code>true</code>	Configures filter summation operations to convert the input format of the addends to match the summation output format before performing the summation operation. Usually this generates results from the summation that more closely match those found from digital signal processors


Another point — with `CastBeforeSum` set to `false`, the filter realization process inserts an intermediate data type format to hold temporarily the full precision sum of the inputs. A separate Convert block performs the process of casting the addition result to the accumulator format. This intermediate data format occurs because the Sum block in Simulink always casts input (addends) to the output data type.

**Diagrams of `CastBeforeSum` Settings.** When `CastBeforeSum` is `false`, sum elements in filter signal flow diagrams look like this:



showing that the input data to the sum operations (the addends) retain their format word length and fraction length from previous operations. The addition process uses the existing input formats and then casts the output to the format defined by `AccumFormat`. Thus the output data has the word length and fraction length defined by `AccumWordLength` and `AccumFracLength`.

When `CastBeforeSum` is `true`, sum elements in filter signal flow diagrams look like this:



showing that the input data gets recast to the accumulator format word length and fraction length (`AccumFormat`) before the sum operation occurs. The data output by the addition operation has the word length and fraction length defined by `AccumWordLength` and `AccumFracLength`.

## CoeffAutoScale

How the filter represents the filter coefficients depends on the property value of `CoeffAutoScale`. When you create a `dfilt` object, you use coefficients in double-precision format. Converting the `dfilt` object to fixed-point arithmetic forces the coefficients into a fixed-point representation. The representation the filter uses depends on whether the value of `CoeffAutoScale` is `true` or `false`.

- `CoeffAutoScale = true` means the filter chooses the fraction length to maintain the value of the coefficients as close to the double-precision values as possible. When you change the word length applied to the coefficients, the filter object changes the fraction length to try to accommodate the change. `true` is the default setting.
- `CoeffAutoScale = false` removes the automatic scaling of the fraction length for the coefficients and exposes the property that controls the coefficient fraction length so you can change it. For example, if the filter is a direct form FIR filter, setting `CoeffAutoScale = false` exposes the `NumFracLength` property that specifies the fraction length applied to numerator coefficients. If the filter is an IIR filter, setting `CoeffAutoScale = false` exposes both the `NumFracLength` and `DenFracLength` properties.

Here is an example of using `CoeffAutoScale` with a direct form filter.

```
hd2=dfilt.dffir([0.3 0.6 0.3])
```

```
hd2 =
```

```

    FilterStructure: 'Direct-Form FIR'
      Arithmetic: 'double'
      Numerator: [0.3000 0.6000 0.3000]
 PersistentMemory: false
      States: [2x1 double]
```

```
hd2.arithmetic='fixed'

hd2 =

    FilterStructure: 'Direct-Form FIR'
      Arithmetic: 'fixed'
      Numerator: [0.3000 0.6000 0.3000]
    PersistentMemory: false
      States: [1x1 embedded.fi]

    CoeffWordLength: 16
      CoeffAutoScale: true
      Signed: true

    InputWordLength: 16
    InputFracLength: 15

    OutputWordLength: 16
      OutputMode: 'AvoidOverflow'

      ProductMode: 'FullPrecision'

    AccumWordLength: 40
      CastBeforeSum: true

      RoundMode: 'convergent'
      OverflowMode: 'wrap'
```

To this point, the filter coefficients retain the original values from when you created the filter as shown in the Numerator property. Now change the CoeffAutoScale property value from true to false.

```
hd2.coeffautoScale=false

hd2 =

    FilterStructure: 'Direct-Form FIR'
      Arithmetic: 'fixed'
      Numerator: [0.3000 0.6000 0.3000]
    PersistentMemory: false
```

```

        States: [1x1 embedded.fi]

    CoeffWordLength: 16
    CoeffAutoScale: false
    NumFracLength: 15
    Signed: true

    InputWordLength: 16
    InputFracLength: 15

    OutputWordLength: 16
    OutputMode: 'AvoidOverflow'

    ProductMode: 'FullPrecision'

    AccumWordLength: 40
    CastBeforeSum: true

    RoundMode: 'convergent'
    OverflowMode: 'wrap'

```

With the NumFracLength property now available, change the word length to 5 bits.

Notice the coefficient values. Setting CoeffAutoScale to false removes the automatic fraction length adjustment and the filter coefficients cannot be represented by the current format of [5 15] — a word length of 5 bits, fraction length of 15 bits.

```
hd2.coeffwordlength=5
```

```
hd2 =
```

```

    FilterStructure: 'Direct-Form FIR'
    Arithmetic: 'fixed'
    Numerator: [4.5776e-004 4.5776e-004 4.5776e-004]
    PersistentMemory: false
    States: [1x1 embedded.fi]

    CoeffWordLength: 5

```

```
    CoeffAutoScale: false
      NumFracLength: 15
        Signed: true

    InputWordLength: 16
    InputFracLength: 15

    OutputWordLength: 16
      OutputMode: 'AvoidOverflow'

      ProductMode: 'FullPrecision'

    AccumWordLength: 40
      CastBeforeSum: true

      RoundMode: 'convergent'
      OverflowMode: 'wrap'
```

Restoring `CoeffAutoScale` to `true` goes some way to fixing the coefficient values. Automatically scaling the coefficient fraction length results in setting the fraction length to 4 bits. You can check this with `get(hd2)` as shown below.

```
hd2.coeffautoScale=true
```

```
hd2 =
```

```
    FilterStructure: 'Direct-Form FIR'
      Arithmetic: 'fixed'
        Numerator: [0.3125 0.6250 0.3125]
    PersistentMemory: false
      States: [1x1 embedded.fi]

    CoeffWordLength: 5
      CoeffAutoScale: true
        Signed: true

    InputWordLength: 16
    InputFracLength: 15
```

```
OutputWordLength: 16
  OutputMode: 'AvoidOverflow'

  ProductMode: 'FullPrecision'

AccumWordLength: 40
  CastBeforeSum: true

  RoundMode: 'convergent'
  OverflowMode: 'wrap'

get(hd2)
  PersistentMemory: false
FilterStructure: 'Direct-Form FIR'
  States: [1x1 embedded.fi]
  Numerator: [0.3125 0.6250 0.3125]
  Arithmetic: 'fixed'
  CoeffWordLength: 5
  CoeffAutoScale: 1
  Signed: 1
  RoundMode: 'convergent'
  OverflowMode: 'wrap'
  InputWordLength: 16
  InputFracLength: 15
  OutputWordLength: 16
  OutputMode: 'AvoidOverflow'
  ProductMode: 'FullPrecision'
  NumFracLength: 4
  OutputFracLength: 12
  ProductWordLength: 21
  ProductFracLength: 19
  AccumWordLength: 40
  AccumFracLength: 19
  CastBeforeSum: 1
```

Clearly five bits is not enough to represent the coefficients accurately.

### **CoeffFracLength**

Fixed-point scalar filters that you create using `dfilt.scalar` use this property to define the fraction length applied to the scalar filter coefficients. Like the coefficient-fraction-length-related properties for the FIR, lattice, and IIR filters, `CoeffFracLength` is not displayed for scalar filters until you set `CoeffAutoScale` to `false`. Once you change the automatic scaling you can set the fraction length for the coefficients to any value you require.

As with all fraction length properties, the value you enter here can be any negative or positive integer, or zero. Fraction length can be larger than the associated word length, as well. By default, the value is 14 bits, with the `CoeffWordLength` of 16 bits.

### **CoeffWordLength**

One primary consideration in developing filters for hardware is the length of a data word. `CoeffWordLength` defines the word length for these data storage and arithmetic locations:

- Numerator and denominator filter coefficients
- Tap sum in `dfilt.dfsymfir` and `dfilt.dfasymfir` filter objects
- Section input, multiplicand, and state values in direct-form SOS filter objects such as `dfilt.df1t` and `dfilt.df2`
- Scale values in second-order filters
- Lattice and ladder coefficients in lattice filter objects, such as `dfilt.latticearma` and `dfilt.latticemamax`
- Gain in `dfilt.scalar`

Setting this property value controls the word length for the data listed. In most cases, the data words in this list have separate fraction length properties to define the associated fraction lengths.

Any positive, integer word length works here, limited by the machine you use to develop your filter and the hardware you use to deploy your filter.

## DenAccumFracLength

Filter structures `df1`, `df1t`, `df2`, and `df2t` that use fixed arithmetic have this property that defines the fraction length applied to denominator coefficients in the accumulator. In combination with `AccumWordLength`, the properties fully specify how the accumulator outputs data stored there.

As with all fraction length properties, `DenAccumFracLength` can be any integer, including integers larger than `AccumWordLength`, and positive or negative integers. To be able to change the property value for this property, you set `FilterInternals` to `SpecifyPrecision`.

## DenFracLength

Property `DenFracLength` contains the value that specifies the fraction length for the denominator coefficients for your filter. `DenFracLength` specifies the fraction length used to interpret the data stored in `C`. Used in combination with `CoeffWordLength`, these two properties define the interpretation of the coefficients stored in the vector that contains the denominator coefficients.

As with all fraction length properties, the value you enter here can be any negative or positive integer, or zero. Fraction length can be larger than the associated word length, as well. By default, the value is 15 bits, with the `CoeffWordLength` of 16 bits.

## Denominator

The denominator coefficients for your IIR filter, taken from the prototype you start with, are stored in this property. Generally this is a 1-by-`N` array of data in double format, where `N` is the length of the filter.

All IIR filter objects include `Denominator`, except the lattice-based filters which store their coefficients in the `Lattice` property, and second-order section filters, such as `dfilt.df1tsos`, which use the `SosMatrix` property to hold the coefficients for the sections.

## DenProdFracLength

A property of all of the direct form IIR `dfilt` objects, except the ones that implement second-order sections, `DenProdFracLength` specifies the fraction

length applied to data output from product operations that the filter performs on denominator coefficients.

Looking at the signal flow diagram for the `dfilt.df1t` filter, for example, you see that denominators and numerators are handled separately. When you set `ProductMode` to `SpecifyPrecision`, you can change the `DenProdFracLength` setting manually. Otherwise, for multiplication operations that use the denominator coefficients, the filter sets the fraction length as defined by the `ProductMode` setting.

### **DenStateFracLength**

When you look at the flow diagram for the `dfilt.df1sos` filter object, the states associated with denominator coefficient operations take the fraction length from this property. In combination with the `DenStateWordLength` property, these properties fully specify how the filter interprets the states.

As with all fraction length properties, the value you enter here can be any negative or positive integer, or zero. Fraction length can be larger than the associated word length, as well. By default, the value is 15 bits, with the `DenStateWordLength` of 16 bits.

### **DenStateWordLength**

When you look at the flow diagram for the `dfilt.df1sos` filter object, the states associated with the denominator coefficient operations take the data format from this property and the `DenStateFracLength` property. In combination, these properties fully specify how the filter interprets the state it uses.

By default, the value is 16 bits, with the `DenStateFracLength` of 15 bits.

### **FilterInternals**

Similar to the `FilterInternals` pane in `FDATool`, this property controls whether the filter sets the output word and fraction lengths automatically, and the accumulator word and fraction lengths automatically as well, to maintain the best precision results during filtering. The default value, `FullPrecision`, sets automatic word and fraction length determination by the filter. Setting `FilterInternals` to `SpecifyPrecision` exposes the output

and accumulator related properties so you can set your own word and fraction lengths for them. Note that

## FilterStructure

Every `dfilt` object has a `FilterStructure` property. This is a read-only property containing a string that declares the structure of the filter object you created.

When you construct filter objects, the `FilterStructure` property value is returned containing one of the strings shown in the following table. Property `FilterStructure` indicates the filter architecture and comes from the constructor you use to create the filter.

After you create a filter object, you cannot change the `FilterStructure` property value. To make filters that use different structures, you construct new filters using the appropriate methods, or use `convert` to switch to a new structure.

**Default value.** Since this depends on the constructor you use and the constructor includes the filter structure definition, there is no default value. When you try to create a filter without specifying a structure, MATLAB returns an error.


Filter Constructor Name	FilterStructure Property String and Filter Type
' <code>dfilt.df1</code> '	Direct form I
' <code>dfilt.df1sos</code> '	Direct form I filter implemented using second-order sections
' <code>dfilt.df1t</code> '	Direct form I transposed
' <code>dfilt.df2</code> '	Direct form II
' <code>dfilt.df2sos</code> '	Direct form II filter implemented using second order sections
' <code>dfilt.df2t</code> '	Direct form II transposed
' <code>dfilt.dfasymfir</code> '	Antisymmetric finite impulse response (FIR). Even and odd forms.

Filter Constructor Name	FilterStructure Property String and Filter Type
'dfilt.dffir'	Direct form FIR
'dfilt.dffirt'	Direct form FIR transposed
'dfilt.latticeallpass'	Lattice allpass
'dfilt.latticear'	Lattice autoregressive (AR)
'dfilt.latticemamin'	Lattice moving average (MA) minimum phase
'dfilt.latticemamax'	Lattice moving average (MA) maximum phase
'dfilt.latticearma'	Lattice ARMA
'dfilt.dfsymfir'	Symmetric FIR. Even and odd forms
'dfilt.scalar'	Scalar

**Filter Structures with Quantizations Shown in Place.** To help you understand how and where the quantizations occur in filter structures in this toolbox, the figure below shows the structure for a Direct Form II filter, including the quantizations (fixed-point formats) that compose part of the fixed-point filter. You see that one or more quantization processes, specified by the \*format label, accompany each filter element, such as a delay, product, or summation element. The input to or output from each element reflects the result of applying the associated quantization as defined by the word length and fraction length format. Wherever a particular filter element appears in a filter structure, recall the quantization process that accompanies the element as it appears in this figure. Each filter reference page, such as the `dfilt.df2` reference page, includes the signal flow diagram showing the formatting elements that define the quantizations that occur throughout the filter flow.

For example, a product quantization, either numerator or denominator, follows every product (gain) element and a sum quantization, also either numerator or denominator, follows each sum element. The figure shows the Arithmetic property value set to `fixed`.

df2 IIR Filter Structure Including the Formatting Objects, with Arithmetic Property Value fixed



When your `df2` filter uses the Arithmetic property set to fixed, the filter structure contains the formatting features shown in the diagram. The formats included in the structure are fixed-point objects that include properties to set various word and fraction length formats. For example, the `NumFormat` or `DenFormat` in the fixed-point arithmetic filter set the properties for quantizing numerator or denominator coefficients according to word and fraction length settings.

When the leading denominator coefficient `a(1)` in your filter is not 1, choose it to be a power of two so that a shift replaces the multiply that would otherwise be used.

**Fixed-Point Arithmetic Filter Structures.** You choose among several filter structures when you create fixed-point filters. You can also specify filters with single or multiple cascaded sections of the same type. Because quantization is a nonlinear process, different fixed-point filter structures produce different results.

To specify the filter structure, you select the appropriate `dfilt.structure` method to construct your filter. Refer to the function reference information for `dfilt` and `set` for details on setting property values for quantized filters.

The figures in the following subsections of this section serve as aids to help you determine how to enter your filter coefficients for each filter structure. Each subsection contains an example for constructing a filter of the given structure.

Scale factors for the input and output for the filters do not appear in the block diagrams. The default filter structures do not include, nor assume, the scale factors. For filter scaling information, refer to `scale` in the Help system.


**About the Filter Structure Diagrams.** In the diagrams that accompany the following filter structure descriptions, you see the active operators that define the filter, such as sums and gains, and the formatting features that control the processing in the filter. Notice also that the coefficients are labeled in the figure. This tells you the order in which the filter processes the coefficients.

While the meaning of the block elements is straightforward, the labels for the formats that form part of the filter are less clear. Each figure includes text in the form *labelFormat* that represents the existence of a formatting feature at that point in the structure. The *Format* stands for formatting object and the *label* specifies the data that the formatting object affects.

For example, in the `dfilt.df2` filter shown above, the entries `InputFormat` and `OutputFormat` are the formats applied, that is the word length and fraction length, to the filter input and output data. For example, filter properties like `OutputWordLength` and `InputWordLength` specify values that control filter operations at the input and output points in the structure and are represented by the formatting objects `InputFormat` and `OutputFormat` shown in the filter structure diagrams.

**Direct Form I Filter Structure.** The following figure depicts the *direct form I* filter structure that directly realizes a transfer function with a second-order numerator and denominator. The numerator coefficients are numbered  $b(i)$ ,  $i = 1, 2, 3$ ; the denominator coefficients are numbered  $a(i)$ ,  $i = 1, 2, 3$ ; and the states (used for initial and final state values in filtering) are labeled  $z(i)$ . In the figure, the Arithmetic property is set to `fixed`.






**Example — Specifying a Direct Form I Filter with Second-Order Sections.** You can specify an eighth-order direct form I structure for a quantized filter `hq` with the following code.

```
b = [0.3 0.6 0.3];
a = [1 0 0.2];
hq = dfilt.df1sos(b,a);
```

To create the fixed-point filter, set the `Arithmetic` property to `fixed`, as shown here.

```
set(hq,'arithmetic','fixed');
```

**Direct Form I Transposed Filter Structure.** The next signal flow diagram depicts a *direct form I transposed* filter structure that directly realizes a transfer function with a second-order numerator and denominator. The numerator coefficients are  $b(i)$ ,  $i = 1, 2, 3$ ; the denominator coefficients are  $a(i)$ ,  $i = 1, 2, 3$ ; and the states (used for initial and final state values in filtering) are labeled  $z(i)$ . With the `Arithmetic` property value set to `fixed`, the figure shows the filter with the properties indicated.




**Example – Specifying a Direct Form I Transposed Filter.** You can specify a second-order direct form I transposed filter structure for a quantized filter `hq` with the following code.

```
b = [0.3 0.6 0.3];
a = [1 0 0.2];
hq = dfilt.df1t(b,a);
set(hq,'arithmetic','fixed');
```

**Direct Form II Filter Structure.** The following graphic depicts a *direct form II* filter structure that directly realizes a transfer function with a second-order numerator and denominator. In the figure, the Arithmetic property value is fixed. Numerator coefficients are named  $b(i)$ ; denominator coefficients are named  $a(i)$ ,  $i = 1, 2, 3$ ; and the states (used for initial and final state values in filtering) are named  $z(i)$ .






Use the method `dfilt.df2sos` to construct a quantized filter whose `FilterStructure` property is `Direct-Form II`.

**Example – Specifying a Direct Form II Filter with Second-Order Sections.** You can specify a tenth-order direct form II filter structure that uses second-order sections for a quantized filter `hq` with the following code.

```
b = [0.3 0.6 0.3];
a = [1 0 0.2];
hq = dfilt.df2sos(b,a);
hq.arithmetic = 'fixed'
```

To convert your prototype double-precision filter `hq` to a fixed-point filter, set the `Arithmetic` property to `fixed`, as shown.

**Direct Form II Transposed Filter Structure.** The following figure depicts the *direct form II transposed* filter structure that directly realizes transfer functions with a second-order numerator and denominator. The numerator coefficients are labeled  $b(i)$ , the denominator coefficients are labeled  $a(i)$ ,  $i = 1, 2, 3$ , and the states (used for initial and final state values in filtering) are labeled  $z(i)$ . In the first figure, the `Arithmetic` property value is `fixed`.



Use the constructor `dfilt.df2t` to specify the value of the `FilterStructure` property for a filter with this structure that you can convert to fixed-point filtering.


**Example – Specifying a Direct Form II Transposed Filter.** Specifying or constructing a second-order direct form II transposed filter for a fixed-point filter `hq` starts with the following code to define the coefficients and construct the filter.

```
b = [0.3 0.6 0.3];
a = [1 0 0.2];
hd = dfilt.df2t(b,a);
```

Now create the fixed-point filtering version of the filter from `hd`, which is floating point.

```
hq = set(hd,'arithmetic','fixed');
```

**Direct Form Antisymmetric FIR Filter Structure (Any Order).** The following figure depicts a *direct form antisymmetric FIR* filter structure that directly realizes a second-order antisymmetric FIR filter. The filter coefficients are labeled  $b(i)$ , and the initial and final state values in filtering are labeled  $z(i)$ . This structure reflects the Arithmetic property set to fixed.



Use the method `dfilt.dfasymfir` to construct the filter, and then set the Arithmetic property to fixed to convert to a fixed-point filter with this structure.

**Example – Specifying an Odd-Order Direct Form Antisymmetric FIR Filter.** Specify a fifth-order direct form antisymmetric FIR filter structure for a fixed-point filter `hq` with the following code.

```
b = [-0.008 0.06 -0.44 0.44 -0.06 0.008];
hq = dfilt.dfasymfir(b);
set(hq,'arithmetic','fixed')
```

```
hq
```

```
hq =  
  
    FilterStructure: 'Direct-Form Antisymmetric FIR'  
        Arithmetic: 'fixed'  
            Numerator: [-0.0080 0.0600 -0.4400 0.4400 -0.0600 0.0080]  
PersistentMemory: false  
        States: [1x1 fi object]  
  
    CoeffWordLength: 16  
        CoeffAutoScale: true  
            Signed: true  
  
    InputWordLength: 16  
    InputFracLength: 15  
  
    OutputWordLength: 16  
        OutputMode: 'AvoidOverflow'  
  
        TapSumMode: 'KeepMSB'  
    TapSumWordLength: 17  
  
        ProductMode: 'FullPrecision'  
  
    AccumWordLength: 40  
  
    CastBeforeSum: true  
        RoundMode: 'convergent'  
        OverflowMode: 'wrap'  
  
    InheritSettings: false
```


**Example — Specifying an Even-Order Direct Form Antisymmetric FIR Filter.** You can specify a fourth-order direct form antisymmetric FIR filter structure for a fixed-point filter `hq` with the following code.

```
b = [-0.01 0.1 0.0 -0.1 0.01];  
hq = dfilt.dfasymfir(b);  
hq.arithmetic='fixed'
```

```
hq =
```

```
FilterStructure: 'Direct-Form Antisymmetric FIR'  
  Arithmetic: 'fixed'  
    Numerator: [-0.0100 0.1000 0 -0.1000 0.0100]  
PersistentMemory: false  
  States: [1x1 fi object]  
  
  CoeffWordLength: 16  
    CoeffAutoScale: true  
      Signed: true  
  
  InputWordLength: 16  
    InputFracLength: 15  
  
  OutputWordLength: 16  
    OutputMode: 'AvoidOverflow'  
  
    TapSumMode: 'KeepMSB'  
  TapSumWordLength: 17  
  
    ProductMode: 'FullPrecision'  
  
  AccumWordLength: 40  
  
    CastBeforeSum: true  
      RoundMode: 'convergent'  
        OverflowMode: 'wrap'  
  
  InheritSettings: false
```

**Direct Form Finite Impulse Response (FIR) Filter Structure.** In the next figure, you see the signal flow graph for a *direct form finite impulse response (FIR)* filter structure that directly realizes a second-order FIR filter. The filter coefficients are  $b(i)$ ,  $i = 1, 2, 3$ , and the states (used for initial and final state values in filtering) are  $z(i)$ . To generate the figure, set the `Arithmetic` property to `fixed` after you create your prototype filter in double-precision arithmetic.




Use the `dfilt.dffir` method to generate a filter that uses this structure.

**Example — Specifying a Direct Form FIR Filter.** You can specify a second-order direct form FIR filter structure for a fixed-point filter `hq` with the following code.

```
b = [0.05 0.9 0.05];
hd = dfilt.dffir(b);
hq = set(hd, 'arithmetic', 'fixed');
```

**Direct Form FIR Transposed Filter Structure.** This figure uses the filter coefficients labeled  $b(i)$ ,  $i = 1, 2, 3$ , and states (used for initial and final state values in filtering) are labeled  $z(i)$ . These depict a *direct form finite impulse response (FIR) transposed* filter structure that directly realizes a second-order FIR filter.




With the Arithmetic property set to fixed, your filter matches the figure. Using the method `dfilt.dffirt` returns a double-precision filter that you convert to a fixed-point filter.



**Lattice Moving Average Maximum Phase Filter Structure.** In the next figure you see a *lattice moving average maximum phase* filter structure. This signal flow diagram directly realizes a third-order lattice moving average (MA) filter with the following phase form depending on the initial transfer function:

- When you start with a minimum phase transfer function, the upper branch of the resulting lattice structure returns a minimum phase filter. The lower branch returns a maximum phase filter.
- When your transfer function is neither minimum phase nor maximum phase, the lattice moving average maximum phase structure will not be maximum phase.
- When you start with a maximum phase filter, the resulting lattice filter is maximum phase also.

The filter reflection coefficients are labeled  $k(i)$ ,  $i = 1, 2, 3$ . The states (used for initial and final state values in filtering) are labeled  $z(i)$ . In the figure, we set the Arithmetic property to fixed to reveal the fixed-point arithmetic format features that control such options as word length and fraction length.




**Example — Constructing a Lattice Moving Average Maximum Phase Filter.** Constructing a fourth-order lattice MA maximum phase filter structure for a quantized filter `hq` begins with the following code.

```
k = [.66 .7 .44 .33];
hd=dfilt.latticemamax(k);
```



- When you start with a minimum phase transfer function, the upper branch of the resulting lattice structure returns a minimum phase filter. The lower branch returns a minimum phase filter.
- When your transfer function is neither minimum phase nor maximum phase, the lattice moving average minimum phase structure will not be minimum phase.
- When you start with a minimum phase filter, the resulting lattice filter is minimum phase also.


The filter reflection coefficients are labeled  $k(i)$ ,  $i = 1, 2, 3$ . The states (used for initial and final state values in filtering) are labeled  $z(i)$ . This figure shows the filter structure when the Arithmetic property is set to fixed to reveal the fixed-point arithmetic format features that control such options as word length and fraction length.



**Example — Specifying a Minimum Phase Lattice MA Filter.** You can specify a third-order lattice MA filter structure for minimum phase applications using variations of the following code.

```
k = [.66 .7 .44];
hd=dfilt.latticemamin(k);
set(hq,'arithmetic','fixed');
```


**Lattice Autoregressive Moving Average (ARMA) Filter Structure.** The figure below depicts a *lattice autoregressive moving average (ARMA)* filter structure that directly realizes a fourth-order lattice ARMA filter. The filter reflection coefficients are labeled  $k(i)$ ,  $(i) = 1, \dots, 4$ ; the ladder coefficients are labeled  $v(i)$ ,  $(i) = 1, 2, 3$ ; and the states (used for initial and final state values in filtering) are labeled  $z(i)$ .



**Example – Specifying an Lattice ARMA Filter.** The following code specifies a fourth-order lattice ARMA filter structure for a quantized filter `hq`, starting from `hd`, a floating-point version of the filter.

```
k = [.66 .7 .44 .66];
v = [1 0 0];
hd=dfilt.latticearma(k,v);
hq.arithmetic = 'fixed';
```

**Direct Form Symmetric FIR Filter Structure (Any Order).** Shown in the next figure, you see signal flow that depicts a *direct form symmetric FIR* filter structure that directly realizes a fifth-order direct form symmetric FIR filter. Filter coefficients are labeled  $b(i)$ ,  $i = 1, \dots, n$ , and states (used for initial and final state values in filtering) are labeled  $z(i)$ . Showing the filter structure used when you select fixed for the Arithmetic property value, the first figure details the properties in the filter object.



### Example — Specifying an Odd-Order Direct Form Symmetric FIR

**Filter.** By using the following code in MATLAB, you can specify a fifth-order direct form symmetric FIR filter for a fixed-point filter `hq`:

```
b = [-0.008 0.06 0.44 0.44 0.06 -0.008];
hd=dfilt.dfsymfir(b);
set(hq,'arithmetic','fixed');
```

**Assigning Filter Coefficients.** The syntax you use to assign filter coefficients for your floating-point or fixed-point filter depends on the structure you select for your filter.

**Converting Filters Between Representations.** Filter conversion functions in this toolbox and in Signal Processing Toolbox software let you convert filter transfer functions to other filter forms, and from other filter forms to transfer function form. Relevant conversion functions include the following functions.

<b>Conversion Function</b>	<b>Description</b>
ca2tf	Converts from a coupled allpass filter to a transfer function.
cl2tf	Converts from a lattice coupled allpass filter to a transfer function.
convert	Convert a discrete-time filter from one filter structure to another.
sos	Converts quantized filters to create second-order sections. We recommend this method for converting quantized filters to second-order sections.
tf2ca	Converts from a transfer function to a coupled allpass filter.
tf2cl	Converts from a transfer function to a lattice coupled allpass filter.
tf2latc	Converts from a transfer function to a lattice filter.
tf2sos	Converts from a transfer function to a second-order section form.
tf2ss	Converts from a transfer function to state-space form.
tf2zp	Converts from a rational transfer function to its factored (single section) form (zero-pole-gain form).
zp2sos	Converts a zero-pole-gain form to a second-order section form.
zp2ss	Conversion of zero-pole-gain form to a state-space form.
zp2tf	Conversion of zero-pole-gain form to transfer functions of multiple order sections.

Note that these conversion routines do not apply to `dfilt` objects.

The function `convert` is a special case — when you use `convert` to change the filter structure of a fixed-point filter, you lose all of the filter states and settings. Your new filter has default values for all properties, and it is not fixed-point.

To demonstrate the changes that occur, convert a fixed-point direct form I transposed filter to direct form II structure.

```
hd=dfilt.df1t
```

```
hd =
```

```
    FilterStructure: 'Direct-Form I Transposed'  
      Arithmetic: 'double'  
      Numerator: 1  
      Denominator: 1  
 PersistentMemory: false  
           States: Numerator: [0x0 double]  
                  Denominator:[0x0 double]
```

```
hd.arithmetic='fixed'
```

```
hd =
```

```
    FilterStructure: 'Direct-Form I Transposed'  
      Arithmetic: 'fixed'  
      Numerator: 1  
      Denominator: 1  
 PersistentMemory: false  
           States: Numerator: [0x0 fi]  
                  Denominator:[0x0 fi]
```

```
convert(hd,'df2')
```

```
Warning: Using reference filter for structure conversion.  
Fixed-point attributes will not be converted.
```

```
ans =
```

```
FilterStructure: 'Direct-Form II'  
Arithmetic: 'double'  
Numerator: 1  
Denominator: 1  
PersistentMemory: false  
States: [0x1 double]
```

You can specify a filter with  $L$  sections of arbitrary order by

- 1 Factoring your entire transfer function with `tf2zp`. This converts your transfer function to zero-pole-gain form.
- 2 Using `zp2tf` to compose the transfer function for each section from the selected first-order factors obtained in step 1.

---

**Note** You are not required to normalize the leading coefficients of each section's denominator polynomial when you specify second-order sections, though `tf2sos` does.

---

### Gain

`dfilt.scalar` filters have a gain value stored in the `gain` property. By default the gain value is one — the filter acts as a wire.

### InputFracLength

`InputFracLength` defines the fraction length assigned to the input data for your filter. Used in tandem with `InputWordLength`, the pair defines the data format for input data you provide for filtering.

As with all fraction length properties in `dfilt` objects, the value you enter here can be any negative or positive integer, or zero. Fraction length can be larger than the associated word length, in this case `InputWordLength`, as well.

### InputWordLength

Specifies the number of bits your filter uses to represent your input data. Your word length option is limited by the arithmetic you choose — up to 32 bits for

double, float, and fixed. Setting Arithmetic to single (single-precision floating-point) limits word length to 16 bits. The default value is 16 bits.

### Ladder

Included as a property in `dfilt.latticearma` filter objects, Ladder contains the denominator coefficients that form an IIR lattice filter object. For instance, the following code creates a high pass filter object that uses the lattice ARMA structure.

```
[b,a]=cheby1(5,.5,.5,'high')

b =

    0.0282   -0.1409    0.2817   -0.2817    0.1409   -0.0282

a =

    1.0000    0.9437    1.4400    0.9629    0.5301    0.1620

hd=dfilt.latticearma(b,a)

hd =

    FilterStructure: [1x44 char]
      Arithmetic: 'double'
      Lattice: [1x6 double]
      Ladder: [1 0.9437 1.4400 0.9629 0.5301 0.1620]
 PersistentMemory: false
      States: [6x1 double]

hd.arithmetic='fixed'

hd =

    FilterStructure: [1x44 char]
      Arithmetic: 'fixed'
      Lattice: [1x6 double]
      Ladder: [1 0.9437 1.4400 0.9629 0.5301 0.1620]
```

```
PersistentMemory: false
    States: [1x1 embedded.fi]

    CoeffWordLength: 16
    CoeffAutoScale: true
    Signed: true

    InputWordLength: 16
    InputFracLength: 15

    OutputWordLength: 16
    OutputMode: 'AvoidOverflow'

    StateWordLength: 16
    StateFracLength: 15

    ProductMode: 'FullPrecision'

    AccumWordLength: 40
    CastBeforeSum: true

    RoundMode: 'convergent'
    OverflowMode: 'wrap'
```

### **LadderAccumFracLength**

Autoregressive, moving average lattice filter objects (`latticearma`) use ladder coefficients to define the filter. In combination with `LadderFracLength` and `CoeffWordLength`, these three properties specify or reflect how the accumulator outputs data stored there. As with all fraction length properties, `LadderAccumFracLength` can be any integer, including integers larger than `AccumWordLength`, and positive or negative integers. The default value is 29 bits.

### **LadderFracLength**

To let you control the way your `latticearma` filter interprets the denominator coefficients, `LadderFracLength` sets the fraction length applied to the ladder coefficients for your filter. The default value is 14 bits.

As with all fraction length properties, `LadderFracLength` can be any integer, including integers larger than `AccumWordLength`, and positive or negative integers.

## Lattice

When you create a lattice-based IIR filter, your numerator coefficients (from your IIR prototype filter or the default `dfilt` lattice filter function) get stored in the `Lattice` property of the `dfilt` object. The properties `CoeffWordLength` and `LatticeFracLength` define the data format the object uses to represent the lattice coefficients. By default, lattice coefficients are in double-precision format.

## LatticeAccumFracLength

Lattice filter objects (`latticeallpass`, `latticearma`, `latticeamax`, and `latticeamin`) use lattice coefficients to define the filter. In combination with `LatticeFracLength` and `CoeffWordLength`, these three properties specify how the accumulator outputs lattice coefficient-related data stored there. As with all fraction length properties, `LatticeAccumFracLength` can be any integer, including integers larger than `AccumWordLength`, and positive or negative integers. By default, the property is set to 31 bits.

## LatticeFracLength

To let you control the way your filter interprets the denominator coefficients, `LatticeFracLength` sets the fraction length applied to the lattice coefficients for your lattice filter. When you create the default lattice filter, `LatticeFracLength` is 16 bits.

As with all fraction length properties, `LatticeFracLength` can be any integer, including integers larger than `CoeffWordLength`, and positive or negative integers.

## MultiplicandFracLength

Each input data element for a multiply operation has both word length and fraction length to define its representation. `MultiplicandFracLength` sets the fraction length to use when the filter object performs any multiply operation during filtering. For default filters, this is set to 15 bits.

As with all word and fraction length properties, `MultiplicandFracLength` can be any integer, including integers larger than `CoeffWordLength`, and positive or negative integers.

### **MultiplicandWordLength**

Each input data element for a multiply operation has both word length and fraction length to define its representation. `MultiplicandWordLength` sets the word length to use when the filter performs any multiply operation during filtering. For default filters, this is set to 16 bits. Only the `df1t` and `df1tsos` filter objects include the `MultiplicandFracLength` property.

Only the `df1t` and `df1tsos` filter objects include the `MultiplicandWordLength` property.

### **NumAccumFracLength**

Filter structures `df1`, `df1t`, `df2`, and `df2t` that use fixed arithmetic have this property that defines the fraction length applied to numerator coefficients in output from the accumulator. In combination with `AccumWordLength`, the `NumAccumFracLength` property fully specifies how the accumulator outputs numerator-related data stored there.

As with all fraction length properties, `NumAccumFracLength` can be any integer, including integers larger than `AccumWordLength`, and positive or negative integers. 30 bits is the default value when you create the filter object. To be able to change the value for this property, set `FilterInternals` for the filter to `SpecifyPrecision`.

### **Numerator**

The numerator coefficients for your filter, taken from the prototype you start with or from the default filter, are stored in this property. Generally this is a 1-by-N array of data in double format, where N is the length of the filter.

All of the filter objects include `Numerator`, except the lattice-based and second-order section filters, such as `dfilt.latticema` and `dfilt.df1tsos`.

## NumFracLength

Property `NumFracLength` contains the value that specifies the fraction length for the numerator coefficients for your filter. `NumFracLength` specifies the fraction length used to interpret the numerator coefficients. Used in combination with `CoeffWordLength`, these two properties define the interpretation of the coefficients stored in the vector that contains the numerator coefficients.

As with all fraction length properties, the value you enter here can be any negative or positive integer, or zero. Fraction length can be larger than the associated word length, as well. By default, the value is 15 bits, with the `CoeffWordLength` of 16 bits.

## NumProdFracLength

A property of all of the direct form IIR `dfilt` objects, except the ones that implement second-order sections, `NumProdFracLength` specifies the fraction length applied to data output from product operations the filter performs on numerator coefficients.

Looking at the signal flow diagram for the `dfilt.df1t` filter, for example, you see that denominators and numerators are handled separately. When you set `ProductMode` to `SpecifyPrecision`, you can change the `NumProdFracLength` setting manually. Otherwise, for multiplication operations that use the numerator coefficients, the filter sets the word length as defined by the `ProductMode` setting.

## NumStateFracLength

All the variants of the direct form I structure include the property `NumStateFracLength` to store the fraction length applied to the numerator states for your filter object. By default, this property has the value 15 bits, with the `CoeffWordLength` of 16 bits, which you can change after you create the filter object.

As with all fraction length properties, the value you enter here can be any negative or positive integer, or zero. Fraction length can be larger than the associated word length, as well.

### **NumStateWordLength**

When you look at the flow diagram for the `df1sos` filter object, the states associated with the numerator coefficient operations take the data format from this property and the `NumStateFracLength` property. In combination, these properties fully specify how the filter interprets the state it uses.

As with all fraction length properties, the value you enter here can be any negative or positive integer, or zero. Fraction length can be larger than the associated word length, as well. By default, the value is 16 bits, with the `NumStateFracLength` of 11 bits.

### **OutputFracLength**

To define the output from your filter object, you need both the word and fraction lengths. `OutputFracLength` determines the fraction length applied to interpret the output data. Combining this with `OutputWordLength` fully specifies the format of the output.

Your fraction length can be any negative or positive integer, or zero. In addition, the fraction length you specify can be larger than the associated word length. Generally, the default value is 11 bits.

### **OutputMode**

Sets the mode the filter uses to scale the filtered (output) data. You have the following choices:

- **AvoidOverflow** — directs the filter to set the property that controls the output data fraction length to avoid causing the data to overflow. In a `df2` filter, this would be the `OutputFracLength` property.
- **BestPrecision** — directs the filter to set the property that controls the output data fraction length to maximize the precision in the output data. For `df1t` filters, this is the `OutputFracLength` property. When you change the word length (`OutputWordLength`), the filter adjusts the fraction length to maintain the best precision for the new word size.
- **SpecifyPrecision** — lets you set the fraction length used by the filtered data. When you select this choice, you can set the output fraction length using the `OutputFracLength` property to define the output precision.

All filters include this property except the direct form I filter which takes the output format from the filter states.

Here is an example that changes the mode setting to `bestprecision`, and then adjusts the word length for the output.

```
hd=dfilt.df2
```

```
hd =
```

```
    FilterStructure: 'Direct-Form II'  
      Arithmetic: 'double'  
        Numerator: 1  
        Denominator: 1  
    PersistentMemory: false  
      States: [0x1 double]
```

```
hd.arithmetic='fixed'
```

```
hd =
```

```
    FilterStructure: 'Direct-Form II'  
      Arithmetic: 'fixed'  
        Numerator: 1  
        Denominator: 1  
    PersistentMemory: false  
      States: [1x1 embedded.fi]
```

```
    CoeffWordLength: 16  
      CoeffAutoScale: true  
        Signed: true
```

```
    InputWordLength: 16  
    InputFracLength: 15
```

```
    OutputWordLength: 16  
      OutputMode: 'AvoidOverflow'
```

```
    StateWordLength: 16  
    StateFracLength: 15
```

```

        ProductMode: 'FullPrecision'

        AccumWordLength: 40
        CastBeforeSum: true

        RoundMode: 'convergent'
        OverflowMode: 'wrap'

get(hd)
    PersistentMemory: false
FilterStructure: 'Direct-Form II'
    States: [1x1 embedded.fi]
        Numerator: 1
        Denominator: 1
        Arithmetic: 'fixed'
    CoeffWordLength: 16
    CoeffAutoScale: 1
    Signed: 1
    RoundMode: 'convergent'
    OverflowMode: 'wrap'
    InputWordLength: 16
    InputFracLength: 15
    OutputWordLength: 16
    OutputMode: 'AvoidOverflow'
    ProductMode: 'FullPrecision'
    StateWordLength: 16
    StateFracLength: 15
    NumFracLength: 14
    DenFracLength: 14
    OutputFracLength: 13
    ProductWordLength: 32
    NumProdFracLength: 29
    DenProdFracLength: 29
    AccumWordLength: 40
    NumAccumFracLength: 29
    DenAccumFracLength: 29
    CastBeforeSum: 1

hd.outputMode='bestprecision'

```

```
hd =  
  
    FilterStructure: 'Direct-Form II'  
        Arithmetic: 'fixed'  
        Numerator: 1  
        Denominator: 1  
    PersistentMemory: false  
        States: [1x1 embedded.fi]  
  
    CoeffWordLength: 16  
        CoeffAutoScale: true  
        Signed: true  
  
    InputWordLength: 16  
    InputFracLength: 15  
  
    OutputWordLength: 16  
        OutputMode: 'BestPrecision'  
  
    StateWordLength: 16  
    StateFracLength: 15  
  
        ProductMode: 'FullPrecision'  
  
    AccumWordLength: 40  
        CastBeforeSum: true  
  
        RoundMode: 'convergent'  
        OverflowMode: 'wrap'  
  
hd.outputWordLength=8;  
  
get(hd)  
    PersistentMemory: false  
    FilterStructure: 'Direct-Form II'  
        States: [1x1 embedded.fi]  
        Numerator: 1  
        Denominator: 1  
        Arithmetic: 'fixed'
```

```
CoeffWordLength: 16
  CoeffAutoScale: 1
    Signed: 1
      RoundMode: 'convergent'
        OverflowMode: 'wrap'
          InputWordLength: 16
            InputFracLength: 15
              OutputWordLength: 8
                OutputMode: 'BestPrecision'
                  ProductMode: 'FullPrecision'
                    StateWordLength: 16
                      StateFracLength: 15
                        NumFracLength: 14
                          DenFracLength: 14
                            OutputFracLength: 5
                              ProductWordLength: 32
                                NumProdFracLength: 29
                                  DenProdFracLength: 29
                                    AccumWordLength: 40
                                      NumAccumFracLength: 29
                                        DenAccumFracLength: 29
                                          CastBeforeSum: 1
```

Changing the `OutputWordLength` to 8 bits caused the filter to change the `OutputFracLength` to 5 bits to keep the best precision for the output data.

### **OutputWordLength**

Use the property `OutputWordLength` to set the word length used by the output from your filter. Set this property to a value that matches your intended hardware. For example, some digital signal processors use 32-bit output so you would set `OutputWordLength` to 32.

```
[b,a] = butter(6,.5);
hd=dfilt.df1t(b,a);

set(hd,'arithmetic','fixed')

hd

hd =
```

```
FilterStructure: 'Direct-Form I Transposed'  
  Arithmetic: 'fixed'  
    Numerator: [1x7 double]  
    Denominator: [1 0 0.7777 0 0.1142 0 0.0018]  
PersistentMemory: false  
  States: Numerator: [6x1 fi]  
          Denominator:[6x1 fi]  
  
  CoeffWordLength: 16  
    CoeffAutoScale: true  
      Signed: true  
  
  InputWordLength: 16  
    InputFracLength: 15  
  
  OutputWordLength: 16  
    OutputMode: 'AvoidOverflow'  
  
  MultiplicandWordLength: 16  
  MultiplicandFracLength: 15  
  
  StateWordLength: 16  
    StateAutoScale: true  
  
    ProductMode: 'FullPrecision'  
  
  AccumWordLength: 40  
    CastBeforeSum: true  
  
    RoundMode: 'convergent'  
    OverflowMode: 'wrap'  
  
hd.outputwordLength=32  
  
hd =  
  
  FilterStructure: 'Direct-Form I Transposed'  
    Arithmetic: 'fixed'
```

```
        Numerator: [1x7 double]
        Denominator: [1 0 0.7777 0 0.1142 0 0.0018]
PersistentMemory: false
        States: Numerator: [6x1 fi]
               Denominator:[6x1 fi]

        CoeffWordLength: 16
        CoeffAutoScale: true
        Signed: true

        InputWordLength: 16
        InputFracLength: 15

        OutputWordLength: 32
        OutputMode: 'AvoidOverflow'

MultiplicandWordLength: 16
MultiplicandFracLength: 15

        StateWordLength: 16
        StateAutoScale: true

        ProductMode: 'FullPrecision'

        AccumWordLength: 40
        CastBeforeSum: true

        RoundMode: 'convergent'
        OverflowMode: 'wrap'
```

When you create a filter object, this property starts with the value 16.

### **OverflowMode**

The `OverflowMode` property is specified as one of the following two strings indicating how to respond to overflows in fixed-point arithmetic:

- `'saturate'` — saturate overflows.

When the values of data to be quantized lie outside of the range of the largest and smallest representable numbers (as specified by the applicable word length and fraction length properties), these values are quantized to the value of either the largest or smallest representable value, depending on which is closest. `saturate` is the default value for `OverflowMode`.

- 'wrap' — wrap all overflows to the range of representable values.

When the values of data to be quantized lie outside of the range of the largest and smallest representable numbers (as specified by the data format properties), these values are wrapped back into that range using modular arithmetic relative to the smallest representable number. You can learn more about modular arithmetic in Fixed-Point Toolbox documentation.

These rules apply to the `OverflowMode` property.

- Applies to the accumulator and output data only.
- Does not apply to coefficients or input data. These always saturate the results.
- Does not apply to products. Products maintain full precision at all times. Your filters do not lose precision in the products.

---

**Note** Numbers in floating-point filters that extend beyond the dynamic range overflow to  $\pm\text{inf}$ .

---

## ProductFracLength

After you set `ProductMode` for a fixed-point filter to `SpecifyPrecision`, this property becomes available for you to change. `ProductFracLength` sets the fraction length the filter uses for the results of multiplication operations. Only the FIR filters such as asymmetric FIRs or lattice autoregressive filters include this dynamic property.

Your fraction length can be any negative or positive integer, or zero. In addition, the fraction length you specify can be larger than the associated word length. Generally, the default value is 11 bits.

## **ProductMode**

This property, available when your filter is in fixed-point arithmetic mode, specifies how the filter outputs the results of multiplication operations. All `dfilt` objects include this property when they use fixed-point arithmetic.

When available, you select from one of the following values for `ProductMode`:

- `FullPrecision` — means the filter automatically chooses the word length and fraction length it uses to represent the results of multiplication operations. The setting allow the product to retain the precision provided by the inputs (multiplicands) to the operation.
- `KeepMSB` — means you specify the word length for representing product operation results. The filter sets the fraction length to discard the LSBs, keep the higher order bits in the data, and maintain the precision.
- `KeepLSB` — means you specify the word length for representing the product operation results. The filter sets the fraction length to discard the MSBs, keep the lower order bits, and maintain the precision. Compare to the `KeepMSB` option.
- `SpecifyPrecision` — means you specify the word length and the fraction length to apply to data output from product operations.

When you switch to fixed-point filtering from floating-point, you are most likely going to throw away some data bits after product operations in your filter, perhaps because you have limited resources. When you have to discard some bits, you might choose to discard the least significant bits (LSB) from a result since the resulting quantization error would be small as the LSBs carry less weight. Or you might choose to keep the LSBs because the results have MSBs that are mostly zero, such as when your values are small relative to the range of the format in which they are represented. So the options for `ProductMode` let you choose how to maintain the information you need from the accumulator.

For more information about data formats, word length, and fraction length in fixed-point arithmetic, refer to “Notes About Fraction Length, Word Length, and Precision” on page 8-29.

## ProductWordLength

You use `ProductWordLength` to define the data word length used by the output from multiplication operations. Set this property to a value that matches your intended application. For example, the default value is 32 bits, but you can set any word length.

```
set(hq,'arithmetic','fixed');
set(hq,'ProductWordLength',64);
```

Note that `ProductWordLength` applies only to filters whose `Arithmetic` property value is `fixed`.

## PersistentMemory

Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter object. `PersistentMemory` returns to zero any state that the filter changes during processing. States that the filter does not change are not affected. Defaults to `false` — the filter does not retain memory about filtering operations from one to the next. Maintaining memory (setting `PersistentMemory` to `true`) lets you filter large data sets as collections of smaller subsets and get the same result.

In this example, filter `hd` first filters data `xtot` in one pass. Then you can use `hd` to filter `x` as two separate data sets. The results `ytot` and `ysec` are the same in both cases.

```
xtot=[x,x];
ytot=filter(hd,xtot)
ytot =

    0   -0.0003   0.0005  -0.0014   0.0028  -0.0054   0.0092

reset(hm1); % Clear history of the filter
hm1.PersistentMemory='true';
ysec=[filter(hd,x) filter(hd,x)]

ysec =

    0   -0.0003   0.0005  -0.0014   0.0028  -0.0054   0.0092
```

This test verifies that `ysec` (the signal filtered by sections) is equal to `ytot` (the entire signal filtered at once).

### RoundMode

The `RoundMode` property value specifies the rounding method used for quantizing numerical values. Specify the `RoundMode` property values as one of the following five strings.

RoundMode String	Description of Rounding Algorithm
Ceiling	Round toward positive infinity.
Floor	Round toward negative infinity.
Nearest	Round toward nearest. Ties round toward positive infinity.
Nearest (Convergent)	Round to the closest representable integer. Ties round to the nearest even stored integer. This is the least biased of the methods available in this software.
Round	Round toward nearest. Ties round toward negative infinity for negative numbers, and toward positive infinity for positive numbers.
Zero	Round toward zero.

The choice you make affects only the accumulator and output arithmetic. Coefficient and input arithmetic always round. Finally, products never overflow — they maintain full precision.

### ScaleValueFracLength

Filter structures `df1sos`, `df1tsos`, `df2sos`, and `df2tsos` that use fixed arithmetic have this property that defines the fraction length applied to the scale values the filter uses between sections. In combination with `CoeffWordLength`, these two properties fully specify how the filter interprets and uses the scale values stored in the property `ScaleValues`. As with fraction length properties, `ScaleValueFracLength` can be any integer,

including integers larger than `CoeffWordLength`, and positive or negative integers. 15 bits is the default value when you create the filter.

## ScaleValues

The `ScaleValues` property values are specified as a scalar (or vector) that introduces scaling for inputs (and the outputs from cascaded sections in the vector case) during filtering:

- When you only have a single section in your filter:
  - Specify the `ScaleValues` property value as a scalar if you only want to scale the input to your filter.
  - Specify the `ScaleValues` property as a vector of length 2 if you want to specify scaling to the input (scaled with the first entry in the vector) and the output (scaled with the last entry in the vector).
- When you have  $L$  cascaded sections in your filter:
  - Specify the `ScaleValues` property value as a scalar if you only want to scale the input to your filter.
  - Specify the value for the `ScaleValues` property as a vector of length  $L+1$  if you want to scale the inputs to every section in your filter, along with the output:

The first entry of your vector specifies the input scaling

Each successive entry specifies the scaling at the output of the next section

The final entry specifies the scaling for the filter output.

The default value for `ScaleValues` is 0.

The interpretation of this property is described as follows with diagrams in “Interpreting the `ScaleValues` Property” on page 8-84.

---

**Note** The value of the `ScaleValues` property is not quantized. Data affected by the presence of a scaling factor in the filter is quantized according to the appropriate data format.

---

When you apply `normalize` to a fixed-point filter, the value for the `ScaleValues` property is changed accordingly.


It is good practice to choose values for this property that are either positive or negative powers of two.

**Interpreting the `ScaleValues` Property.** When you specify the values of the `ScaleValues` property of a quantized filter, the values are entered as a vector, the length of which is determined by the number of cascaded sections in your filter:

- When you have only one section, the value of the `ScaleValues` property can be a scalar or a two-element vector.
- When you have  $L$  cascaded sections in your filter, the value of the `ScaleValues` property can be a scalar or an  $L+1$ -element vector.


The following diagram shows how the `ScaleValues` property values are applied to a quantized filter with only one section.

#### Application of `ScaleValues` to a Single Section



The following diagram shows how the `ScaleValues` property values are applied to a quantized filter with two sections.

### Application of ScaleValues to Multiple Sections



### Signed

When you create a `dfilt` object for fixed-point filtering (you set the property `Arithmetic` to `fixed`, the property `Signed` specifies whether the filter interprets coefficients as signed or unsigned. This setting applies only to the coefficients. While the default setting is `true`, meaning that all coefficients are assumed to be signed, you can change the setting to `false` after you create the fixed-point filter.

For example, create a fixed-point direct-form II transposed filter with both negative and positive coefficients, and then change the property value for `Signed` from `true` to `false` to see what happens to the negative coefficient values.

```
hd=dfilt.df2t(-5:5)
```

```
hd =
```

```

    FilterStructure: 'Direct-Form II Transposed'
      Arithmetic: 'double'
      Numerator: [-5 -4 -3 -2 -1 0 1 2 3 4 5]
      Denominator: 1
 PersistentMemory: false
      States: [10x1 double]
```

```
set(hd,'arithmetic','fixed')
hd.numerator
```

```
ans =
```

```

-5   -4   -3   -2   -1    0
```

```

          1      2      3      4      5

set(hd,'signed',false)
hd.numerator

ans =

          0      0      0      0      0      0
          1      2      3      4      5

```

Using unsigned coefficients limits you to using only positive coefficients in your filter. `Signed` is a dynamic property — you cannot set or change it until you switch the setting for the `Arithmetic` property to `fixed`.

### SosMatrix

When you convert a `dfilt` object to second-order section form, or create a second-order section filter, `sosMatrix` holds the filter coefficients as property values. Using the `double` data type by default, the matrix is in [sections coefficients per section] form, displayed as [15-x-6] for filters with 6 coefficients per section and 15 sections, [15 6].

To demonstrate, the following code creates an order 30 filter using second-order sections in the direct-form II transposed configuration. Notice the `sosMatrix` property contains the coefficients for all the sections.

```

d = fdesign.lowpass('n,fc',30,0.5);
hd = butter(d);

hd =

    FilterStructure: 'Direct-Form II, Second-Order Sections'
      Arithmetic: 'double'
      sosMatrix: [15x6 double]
    ScaleValues: [16x1 double]
PersistentMemory: false
      States: [2x15 double]

hd.arithmetic='fixed'

hd =

```

```

FilterStructure: 'Direct-Form II, Second-Order Sections'
  Arithmetic: 'fixed'
    sosMatrix: [15x6 double]
    ScaleValues: [16x1 double]
PersistentMemory: false
  States: [1x1 embedded.fi]

```

```

CoeffWordLength: 16
  CoeffAutoScale: true
    Signed: true

```

```

InputWordLength: 16
InputFracLength: 15

```

```

SectionInputWordLength: 16
  SectionInputAutoScale: true

```

```

SectionOutputWordLength: 16
  SectionOutputAutoScale: true

```

```

  OutputWordLength: 16
    OutputMode: 'AvoidOverflow'

```

```

    StateWordLength: 16
      StateFracLength: 15

```

```

      ProductMode: 'FullPrecision'

```

```

      AccumWordLength: 40
        CastBeforeSum: true

```

```

        RoundMode: 'convergent'
          OverflowMode: 'wrap'

```

```
hd.sosMatrix
```

```
ans =
```

```

    1.0000    2.0000    1.0000    1.0000         0    0.9005

```

1.0000	2.0000	1.0000	1.0000	0	0.7294
1.0000	2.0000	1.0000	1.0000	0	0.5888
1.0000	2.0000	1.0000	1.0000	0	0.4724
1.0000	2.0000	1.0000	1.0000	0	0.3755
1.0000	2.0000	1.0000	1.0000	0	0.2948
1.0000	2.0000	1.0000	1.0000	0	0.2275
1.0000	2.0000	1.0000	1.0000	0	0.1716
1.0000	2.0000	1.0000	1.0000	0	0.1254
1.0000	2.0000	1.0000	1.0000	0	0.0878
1.0000	2.0000	1.0000	1.0000	0	0.0576
1.0000	2.0000	1.0000	1.0000	0	0.0344
1.0000	2.0000	1.0000	1.0000	0	0.0173
1.0000	2.0000	1.0000	1.0000	0	0.0062
1.0000	2.0000	1.0000	1.0000	0	0.0007

The SOS matrix is an M-by-6 matrix, where M is the number of sections in the second-order section filter. Filter `hd` has M equal to 15 as shown above (15 rows). Each row of the SOS matrix contains the numerator and denominator coefficients (b's and a's) and the scale factors of the corresponding section in the filter.

### **SectionInputAutoScale**

Second-order section filters include this property that determines who the filter handles data in the transitions from one section to the next in the filter.

How the filter represents the data passing from one section to the next depends on the property value of `SectionInputAutoScale`. The representation the filter uses between the filter sections depends on whether the value of `SectionInputAutoScale` is `true` or `false`.

- `SectionInputAutoScale = true` means the filter chooses the fraction length to maintain the value of the data between sections as close to the output values from the previous section as possible. `true` is the default setting.
- `SectionInputAutoScale = false` removes the automatic scaling of the fraction length for the intersection data and exposes the property that controls the coefficient fraction length (`SectionInputFracLength`) so you can change it. For example, if the filter is a second-order, direct form FIR filter, setting `SectionInputAutoScale` to `false` exposes the

`SectionInputFracLength` property that specifies the fraction length applied to data between the sections.

### **SectionInputFracLength**



Second-order section filters use quantizers at the input to each section of the filter. The quantizers apply to the input data entering each filter section. Note that the quantizers for each section are the same. To set the fraction length for interpreting the input values, use the property value in `SectionInputFracLength`.

In combination with `CoeffWordLength`, `SectionInputFracLength` fully determines how the filter interprets and uses the state values stored in the property `States`. As with all word and fraction length properties, `SectionInputFracLength` can be any integer, including integers larger than `CoeffWordLength`, and positive or negative integers. 15 bits is the default value when you create the filter object.

### **SectionInputWordLength**

SOS filters are composed of sections, each one a second-order filter. Filtering data input to the filter involves passing the data through each filter section. `SectionInputWordLength` specifies the word length applied to data as it enters one filter section from the previous section. Only second-order implementations of direct-form I transposed and direct-form II transposed filters include this property.

The following diagram shows an SOS filter composed of sections (the bottom part of the diagram) and a possible internal structure of each Section (the top portion of the diagram), in this case — a direct form I transposed second order sections filter structure. Note that the output of each section is fed through a multiplier. If the gain of the multiplier =1, then the last Cast block of the Section is ignored, and the format of the output is NumSumQ.



`SectionInputWordLength` defaults to 16 bits.

### **SectionOutputAutoScale**

Second-order section filters include this property that determines who the filter handles data in the transitions from one section to the next in the filter.

How the filter represents the data passing from one section to the next depends on the property value of `SectionOutputAutoScale`. The representation the filter uses between the filter sections depends on whether the value of `SectionOutputAutoScale` is `true` or `false`.

- `SectionOutputAutoScale = true` means the filter chooses the fraction length to maintain the value of the data between sections as close to the output values from the previous section as possible. `true` is the default setting.
- `SectionOutputAutoScale = false` removes the automatic scaling of the fraction length for the intersection data and exposes the property that controls the coefficient fraction length (`SectionOutputFracLength`) so you can change it. For example, if the filter is a second-order, direct form FIR filter, setting `SectionOutputAutoScale = false` exposes the `SectionOutputFracLength` property that specifies the fraction length applied to data between the sections.

### **SectionOutputFracLength**



Second-order section filters use quantizers at the output from each section of the filter. The quantizers apply to the output data leaving each filter section. Note that the quantizers for each section are the same. To set the fraction length for interpreting the output values, use the property value in `SectionOutputFracLength`.

In combination with `CoeffWordLength`, `SectionOutputFracLength` determines how the filter interprets and uses the state values stored in the property `States`. As with all fraction length properties, `SectionOutputFracLength` can be any integer, including integers larger than `CoeffWordLength`, and positive or negative integers. 15 bits is the default value when you create the filter object.

### **SectionOutputWordLength**

SOS filters are composed of sections, each one a second-order filter. Filtering data input to the filter involves passing the data through each filter section. `SectionOutputWordLength` specifies the word length applied to data as it leaves one filter section to go to the next. Only second-order implementations direct-form I transposed and direct-form II transposed filters include this property.

The following diagram shows an SOS filter composed of sections (the bottom part of the diagram) and a possible internal structure of each Section (the top portion of the diagram), in this case — a direct form I transposed second order sections filter structure. Note that the output of each section is fed through a multiplier. If the gain of the multiplier =1, then the last Cast block of the Section is ignored, and the format of the output is NumSumQ.



SectionOutputWordLength defaults to 16 bits.

### **StateAutoScale**

Although all filters use states, some do not allow you to choose whether the filter automatically scales the state values to prevent overruns or bad arithmetic errors. You select either of the following settings:

- `StateAutoScale = true` means the filter chooses the fraction length to maintain the value of the states as close to the double-precision values as possible. When you change the word length applied to the states (where allowed by the filter structure), the filter object changes the fraction length to try to accommodate the change. `true` is the default setting.
- `StateAutoScale = false` removes the automatic scaling of the fraction length for the states and exposes the property that controls the coefficient fraction length so you can change it. For example, in a direct form I transposed SOS FIR filter, setting `StateAutoScale = false` exposes the `NumStateFracLength` and `DenStateFracLength` properties that specify the fraction length applied to states.

Each of the following filter structures provides the `StateAutoScale` property:

- `df1t`
- `df1tsos`
- `df2t`
- `df2tsos`
- `dffirt`

Other filter structures do not include this property.

### **StateFracLength**

Filter states stored in the property `States` have both word length and fraction length. To set the fraction length for interpreting the stored filter object state values, use the property value in `StateFracLength`.

In combination with `CoeffWordLength`, `StateFracLength` fully determines how the filter interprets and uses the state values stored in the property `States`.

As with all fraction length properties, `StateFracLength` can be any integer, including integers larger than `CoeffWordLength`, and positive or negative integers. 15 bits is the default value when you create the filter object.

## States

Digital filters are dynamic systems. The behavior of dynamic systems (their response) depends on the input (stimulus) to the system and the current or previous *state* of the system. You can say the system has memory or inertia. All fixed- or floating-point digital filters (as well as analog filters) have states.

Filters use the states to compute the filter output for each input sample, as well using them while filtering in loops to maintain the filter state between loop iterations. This toolbox assumes zero-valued initial conditions (the dynamic system is at rest) by default when you filter the first input sample. Assuming the states are zero initially does not mean the states are not used; they are, but arithmetically they do not have any effect.

Filter objects store the state values in the property `States`. The number of stored states depends on the filter implementation, since the states represent the delays in the filter implementation.

When you review the display for a filter object with fixed arithmetic, notice that the states return an embedded `fi` object, as you see here.

```
b = ellip(6,3,50,300/500);
hd=dfilt.dffir(b)

hd =

    FilterStructure: 'Direct-Form FIR'
      Arithmetic: 'double'
      Numerator: [0.0773 0.2938 0.5858 0.7239 0.5858 0.2938 0.0773]
 PersistentMemory: false
           States: [6x1 double]
```

```
hd.arithmetic='fixed'

hd =

    FilterStructure: 'Direct-Form FIR'
      Arithmetic: 'fixed'
      Numerator: [0.0773 0.2938 0.5858 0.7239 0.5858 0.2938 0.0773]
    PersistentMemory: false
      States: [1x1 embedded.fi]

    CoeffWordLength: 16
      CoeffAutoScale: 'on'
      Signed: 'on'

    InputWordLength: 16
    InputFracLength: 15

    OutputWordLength: 16
      OutputMode: 'AvoidOverflow'

      ProductMode: 'FullPrecision'

    AccumWordLength: 40
      CastBeforeSum: 'on'

      RoundMode: 'convergent'
      OverflowMode: 'wrap'

    InheritSettings: 'off'
```

`fi` objects provide fixed-point support for the filters. To learn more about the details about `fi` objects, refer to your Fixed-Point Toolbox documentation.

The property `States` lets you use a `fi` object to define how the filter interprets the filter states. For example, you can create a `fi` object in MATLAB, then assign the object to `States`, as follows:

```
statefi=fi([],16,12)
```

```
statefi =

[]
    DataTypeMode = Fixed-point: binary point scaling
        Signed = true
        Wordlength = 16
    Fractionlength = 12
```

This `fi` object does not have a value associated (notice the `[]` input argument to `fi` for the value), and it has word length of 16 bits and fraction length of 12 bit. Now you can apply `statefi` to the `States` property of the filter `hd`.

```
set(hd,'States',statefi);
Warning: The 'States' property will be reset to the value
specified at construction before filtering.
Set the 'PersistentMemory' flag to 'True'
to avoid changing this property value.
hd

hd =
```

```
    FilterStructure: 'Direct-Form FIR'
        Arithmetic: 'fixed'
            Numerator: [0.0773 0.2938 0.5858 0.7239 0.5858
                0.2938 0.0773]
    PersistentMemory: false
        States: [1x1 embedded.fi]

    CoeffWordLength: 16
        CoeffAutoScale: 'on'
            Signed: 'on'

    InputWordLength: 16
    InputFracLength: 15

    OutputWordLength: 16
        OutputMode: 'AvoidOverflow'

        ProductMode: 'FullPrecision'
    AccumWordLength: 40
```

```
CastBeforeSum: 'on'  
  
    RoundMode: 'convergent'  
    OverflowMode: 'wrap'
```

### **StateWordLength**

While all filters use states, some do not allow you to directly change the state representation — the word length and fraction lengths — independently. For the others, `StateWordLength` specifies the word length, in bits, the filter uses to represent the states. Filters that do not provide direct state word length control include:

- `df1`
- `dfasymfir`
- `dffir`
- `dfsymfir`

For these structures, the filter derives the state format from the input format you choose for the filter — except for the `df1` IIR filter. In this case, the numerator state format comes from the input format and the denominator state format comes from the output format. All other filter structures provide control of the state format directly.

### **TapSumFracLength**

Direct-form FIR filter objects, both symmetric and antisymmetric, use this property. To set the fraction length for output from the sum operations that involve the filter tap weights, use the property value in `TapSumFracLength`. To enable this property, set the `TapSumMode` to `SpecifyPrecision` in your filter.

As you can see in this code example that creates a fixed-point asymmetric FIR filter, the `TapSumFracLength` property becomes available after you change the `TapSumMode` property value.

```
hd=dfilt.dfasymfir  
  
hd =
```

```
        FilterStructure: 'Direct-Form Antisymmetric FIR'
          Arithmetic: 'double'
            Numerator: 1
    PersistentMemory: false
          States: [0x1 double]

set(hd,'arithmetic','fixed');
hd

hd =

        FilterStructure: 'Direct-Form Antisymmetric FIR'
          Arithmetic: 'fixed'
            Numerator: 1
    PersistentMemory: false
          States: [1x1 embedded.fi]

        CoeffWordLength: 16
          CoeffAutoScale: true
            Signed: true

        InputWordLength: 16
          InputFracLength: 15

    OutputWordLength: 16
          OutputMode: 'AvoidOverflow'

          TapSumMode: 'KeepMSB'
    TapSumWordLength: 17

          ProductMode: 'FullPrecision'

    AccumWordLength: 40

        CastBeforeSum: true
          RoundMode: 'convergent'
        OverflowMode: 'wrap'
```

With the filter now in fixed-point mode, you can change the `TapSumMode` property value to `SpecifyPrecision`, which gives you access to the `TapSumFracLength` property.

```
set(hd, 'TapSumMode', 'SpecifyPrecision');  
hd
```

```
hd =  
  
    FilterStructure: 'Direct-Form Antisymmetric FIR'  
      Arithmetic: 'fixed'  
      Numerator: 1  
 PersistentMemory: false  
      States: [1x1 embedded.fi]  
  
    CoeffWordLength: 16  
      CoeffAutoScale: true  
      Signed: true  
  
    InputWordLength: 16  
    InputFracLength: 15  
  
    OutputWordLength: 16  
      OutputMode: 'AvoidOverflow'  
  
      TapSumMode: 'SpecifyPrecision'  
    TapSumWordLength: 17  
    TapSumFracLength: 15  
  
      ProductMode: 'FullPrecision'  
  
    AccumWordLength: 40  
  
    CastBeforeSum: true  
      RoundMode: 'convergent'  
      OverflowMode: 'wrap'
```

In combination with `TapSumWordLength`, `TapSumFracLength` fully determines how the filter interprets and uses the state values stored in the property `States`.

As with all fraction length properties, `TapSumFracLength` can be any integer, including integers larger than `TapSumWordLength`, and positive or negative integers. 15 bits is the default value when you create the filter object.

### **TapSumMode**

This property, available only after your filter is in fixed-point mode, specifies how the filter outputs the results of summation operations that involve the filter tap weights. Only symmetric (`dfilt.dfsymfir`) and antisymmetric (`dfilt.dfasymfir`) FIR filters use this property.

When available, you select from one of the following values:

- **FullPrecision** — means the filter automatically chooses the word length and fraction length to represent the results of the sum operation so they retain all of the precision provided by the inputs (addends).
- **KeepMSB** — means you specify the word length for representing tap sum summation results to keep the higher order bits in the data. The filter sets the fraction length to discard the LSBs from the sum operation. This is the default property value.
- **KeepLSB** — means you specify the word length for representing tap sum summation results to keep the lower order bits in the data. The filter sets the fraction length to discard the MSBs from the sum operation. Compare to the **KeepMSB** option.
- **SpecifyPrecision** — means you specify the word and fraction lengths to apply to data output from the tap sum operations.

### **TapSumWordLength**

Specifies the word length the filter uses to represent the output from tap sum operations. The default value is 17 bits. Only `dfasymfir` and `dfsymfir` filters include this property.

## Adaptive Filter Properties

In this section...
“Property Summaries” on page 8-102
“Property Details for Adaptive Filter Properties” on page 8-107
“References for Adaptive Filters” on page 8-114

### Property Summaries

The following table summarizes the adaptive filter properties and provides a brief description of each. Full descriptions of each property, in alphabetical order, are given in the subsequent section.

Property	Description
Algorithm	Reports the algorithm the object uses for adaptation. When you construct your adaptive filter object, this property is set automatically by the constructor, such as <code>adaptfilt.nlms</code> creating an adaptive filter that uses the normalized LMS algorithm. You cannot change the value — it is read only.
AvgFactor	Averaging factor used to compute the exponentially-windowed estimates of the powers in the transformed signal bins for the coefficient updates. AvgFactor should lie between zero and one. For default filter objects, AvgFactor equals $(1 - \text{step})$ . <code>lambda</code> is the input argument that represents AvgFactor
BkwdPredErrorPower	Returns the minimum mean-squared prediction error. Refer to [3] in the bibliography for details about linear prediction.
BkwdPrediction	Returns the predicted samples generated during adaptation. Refer to [3] in the bibliography for details about linear prediction.

Property	Description
Blocklength	Block length for the coefficient updates. This must be a positive integer such that $(1/\text{blocklength})$ is also an integer. For faster execution, <code>blocklength</code> should be a power of two. <code>blocklength</code> defaults to two.
Coefficients	Vector containing the initial filter coefficients. It must be a length <code>l</code> vector where <code>l</code> is the number of filter coefficients. <code>coeffs</code> defaults to length <code>l</code> vector of zeros when you do not provide the argument for input.
ConversionFactor	Conversion factor defaults to the matrix $[1 \ -1]$ that specifies soft-constrained initialization. This is the <code>gamma</code> input argument for some of the fast transversal algorithms.
Delay	Update delay given in time samples. This scalar should be a positive integer—negative delays do not work. <code>delay</code> defaults to 1 for most algorithms.
DesiredSignalStates	Desired signal states of the adaptive filter. <code>dstates</code> defaults to a zero vector with length equal to $(\text{blocklen} - 1)$ or $(\text{swblocklen} - 1)$ depending on the algorithm.
EpsilonStates	Vector of the epsilon values of the adaptive filter. <code>EpsilonStates</code> defaults to a vector of zeros with $(\text{projectord} - 1)$ elements.
ErrorStates	Vector of the adaptive filter error states. <code>ErrorStates</code> defaults to a zero vector with length equal to $(\text{projectord} - 1)$ .
FFTCoefficients	Stores the discrete Fourier transform of the filter coefficients in <code>coeffs</code> .
FFTStates	Stores the states of the FFT of the filter coefficients during adaptation.
FilteredInputStates	Vector of filtered input states with length equal to $l - 1$ .

Property	Description
FilterLength	Contains the length of the filter. Note that this is not the filter order. Filter length is 1 greater than filter order. Thus a filter with length equal to 10 has filter order equal to 9.
ForgettingFactor	Determines how the RLS adaptive filter uses past data in each iteration. You use the forgetting factor to specify whether old data carries the same weight in the algorithm as more recent data.
FwdPredErrorPower	Returns the minimum mean-squared prediction error in the forward direction. Refer to [3] in the bibliography for details about linear prediction.
FwdPrediction	Contains the predicted values for samples during adaptation. Compare these to the actual samples to get the error and power.
InitFactor	Soft-constrained initialization factor. This scalar should be positive and sufficiently large to prevent an excessive number of Kalman gain rescues. Called <code>delta</code> as an input argument, this defaults to one.
InvCov	Upper-triangular Cholesky (square root) factor of the input covariance matrix. Initialize this matrix with a positive definite upper triangular matrix. Dimensions are 1-by-1, where 1 is the filter length.
KalmanGain	Empty when you construct the object, this gets populated after you run the filter.
KalmanGainStates	Contains the states of the Kalman gain updates during adaptation.

<b>Property</b>	<b>Description</b>
Leakage	Contains the setting for leakage in the adaptive filter algorithm. Using a leakage factor that is not 1 forces the weights to adapt even when they have found the minimum error solution. Forcing the adaptation can improve the numerical performance of the LMS algorithm.
OffsetCov	Contains the offset covariance matrix.
Offset	Specifies an optional offset for the denominator of the step size normalization term. You must specify offset to be a scalar greater than or equal to zero. Nonzero offsets can help avoid a divide-by-near-zero condition that causes errors.
Power	A vector of 2*1 elements, each initialized with the value delta from the input arguments. As you filter data, Power gets updated by the filter process.
ProjectionOrder	Projection order of the affine projection algorithm. <code>projectord</code> defines the size of the input signal covariance matrix and defaults to two.
ReflectionCoeffs	Coefficients determined for the reflection portion of the filter during adaptation.
ReflectionCoeffsStep	Size of the steps used to determine the reflection coefficients.
PersistentMemory	Specifies whether to reset the filter states and memory before each filtering operation. Lets you decide whether your filter retains states and coefficients from previous filtering runs.
SecondaryPathCoeffs	A vector that contains the coefficient values of your secondary path from the output actuator to the error sensor.
SecondaryPathEstimate	An estimate of the secondary path filter model.

Property	Description
SecondaryPathStates	The states of the secondary path filter, the unknown system.
SqrtCov	Upper-triangular Cholesky (square root) factor of the input covariance matrix. Initialize this matrix with a positive definite upper triangular matrix.
SqrtInvCov	Square root of the inverse of the sliding window input signal covariance matrix. This square matrix should be full-ranked.
States	Vector of the adaptive filter states. <code>states</code> defaults to a vector of zeros whose length depends on the chosen algorithm. Usually the length is a function of the filter length <code>l</code> and another input argument to the filter object, such as <code>projectord</code> .
StepSize	Reports the size of the step taken between iterations of the adaptive filter process. Each <code>adaptfilt</code> object has a default value that best meets the needs of the algorithm.
SwBlockLength	Block length of the sliding window. This integer must be at least as large as the filter length. <code>swblocklen</code> defaults to 16.

Like `dfilt` objects, `adaptfilt` objects have properties that govern their behavior and store some of the results of filtering operations. The following pages list, in alphabetical order, the name of every property associated with `adaptfilt` objects. Note that not all `adaptfilt` objects have all of these properties. To view the properties of a particular adaptive filter, such as an `adaptfilt.bap` filter, use `get` with the object handle, like this:

```

ha = adaptfilt.bap(32,0.5,4,1.0);
get(ha)
    PersistentMemory: false
        Algorithm: 'Block Affine Projection FIR Adaptive Filter'
        FilterLength: 32
        Coefficients: [1x32 double]

```

```
States: [35x1 double]
StepSize: 0.5000
ProjectionOrder: 4
OffsetCov: [4x4 double]
```

`get` shows you the properties for `ha` and the values for the properties. Entering the object handle returns the same values and properties without the formatting of the list and the more familiar property names.

## Property Details for Adaptive Filter Properties

### Algorithm

Reports the algorithm the object uses for adaptation. When you construct you adaptive filter object, this property is set automatically. You cannot change the value—it is read only.

### AvgFactor

Averaging factor used to compute the exponentially-windowed estimates of the powers in the transformed signal bins for the coefficient updates. `AvgFactor` should lie between zero and one. For default filter objects, `AvgFactor` equals  $(1 - \text{step})$ . `lambda` is the input argument that represent `AvgFactor`

### BkwdPredErrorPower

Returns the minimum mean-squared prediction error in the backward direction. Refer to [3] in the bibliography for details about linear prediction.

### BkwdPrediction

When you use an adaptive filter that does backward prediction, such as `adaptfilt.ftf`, one property of the filter contains the backward prediction coefficients for the adapted filter. With these coefficient, the forward coefficients, and the system under test, you have the full set of knowledge of how the adaptation occurred. Two values stored in properties compose the `BkwdPrediction` property:

- `Coefficients`, which contains the coefficients of the system under test, as determined using backward predictions process.

- Error, which is the difference between the filter coefficients determined by backward prediction and the actual coefficients of the sample filter. In this example, `adaptfilt.ftf` identifies the coefficients of an unknown FIR system.

```

x = randn(1,500);    % Input to the filter
b = fir1(31,0.5);    % FIR system to be identified
n = 0.1*randn(1,500); % Observation noise signal
d = filter(b,1,x)+n; % Desired signal
N = 31;              % Adaptive filter order
lam = 0.99;          % RLS forgetting factor
del = 0.1;           % Soft-constrained initialization factor
ha = adaptfilt.ftf(32,lam,del);
[y,e] = filter(ha,x,d);

ha

ha =

        Algorithm: 'Fast Transversal Least-Squares Adaptive Filter'
        FilterLength: 32
        Coefficients: [1x32 double]
           States: [31x1 double]
    ForgettingFactor: 0.9900
         InitFactor: 0.1000
      FwdPrediction: [1x1 struct]
      BkwdPrediction: [1x1 struct]
         KalmanGain: [32x1 double]
    ConversionFactor: 0.7338
    KalmanGainStates: [32x1 double]
    PersistentMemory: false

ha.coefficients

ans =

Columns 1 through 8

    -0.0055    0.0048    0.0045    0.0146   -0.0009    0.0002   -0.0019    0.0008

```

```
Columns 9 through 16
-0.0142 -0.0226 0.0234 0.0421 -0.0571 -0.0807 0.1434 0.4620

Columns 17 through 24
0.4564 0.1532 -0.0879 -0.0501 0.0331 0.0361 -0.0266 -0.0220

Columns 25 through 32
0.0231 0.0026 -0.0063 -0.0079 0.0032 0.0082 0.0033 0.0065

ha.bkwdprediction

ans =

Coeffs: [1x32 double]
Error: 82.3394

>> ha.bkwdprediction.coeffs

ans =

Columns 1 through 8
0.0067 0.0186 0.1114 -0.0150 -0.0239 -0.0610 -0.1120 -0.1026

Columns 9 through 16
0.0093 -0.0399 -0.0045 0.0622 0.0997 0.0778 0.0646 -0.0564

Columns 17 through 24
0.0775 0.0814 0.0057 0.0078 0.1271 -0.0576 0.0037 -0.0200

Columns 25 through 32
-0.0246 0.0180 -0.0033 0.1222 0.0302 -0.0197 -0.1162 0.0285
```

**Blocklength**

Block length for the coefficient updates. This must be a positive integer such that  $(1/\text{blocklen})$  is also an integer. For faster execution, `blocklen` should be a power of two. `blocklen` defaults to two.

**Coefficients**

Vector containing the initial filter coefficients. It must be a length `l` vector where `l` is the number of filter coefficients. `coeffs` defaults to length `l` vector of zeros when you do not provide the argument for input.

**ConversionFactor**

Conversion factor defaults to the matrix  $[1 \ -1]$  that specifies soft-constrained initialization. This is the `gamma` input argument for some of the fast transversal algorithms.

**Delay**

Update delay given in time samples. This scalar should be a positive integer — negative delays do not work. `delay` defaults to 1 for most algorithms.

**DesiredSignalStates**

Desired signal states of the adaptive filter. `dstates` defaults to a zero vector with length equal to  $(\text{blocklen} - 1)$  or  $(\text{swblocklen} - 1)$  depending on the algorithm.

**EpsilonStates**

Vector of the epsilon values of the adaptive filter. `EpsilonStates` defaults to a vector of zeros with  $(\text{projectord} - 1)$  elements.

**ErrorStates**

Vector of the adaptive filter error states. `ErrorStates` defaults to a zero vector with length equal to  $(\text{projectord} - 1)$ .

**FFTCoefficients**

Stores the discrete Fourier transform of the filter coefficients in `coeffs`.

**FFTStates**

Stores the states of the FFT of the filter coefficients during adaptation.

**FilteredInputStates**

Vector of filtered input states with length equal to  $1 - 1$ .

**FilterLength**

Contains the length of the filter. Note that this is not the filter order. Filter length is 1 greater than filter order. Thus a filter with length equal to 10 has filter order equal to 9.

**ForgettingFactor**

Determines how the RLS adaptive filter uses past data in each iteration. You use the forgetting factor to specify whether old data carries the same weight in the algorithm as more recent data.

This is a scalar and should lie in the range  $(0, 1]$ . It defaults to 1. Setting `forgetting factor = 1` denotes infinite memory while adapting to find the new filter. Note that this is the `lambda` input argument.

**FwdPredErrorPower**

Returns the minimum mean-squared prediction error in the forward direction. Refer to [3] in the bibliography for details about linear prediction.

**FwdPrediction**

Contains the predicted values for samples during adaptation. Compare these to the actual samples to get the error and power.

**InitFactor**

Returns the soft-constrained initialization factor. This scalar should be positive and sufficiently large to prevent an excessive number of Kalman gain rescues. `delta` defaults to one.

### **InvCov**

Upper-triangular Cholesky (square root) factor of the input covariance matrix. Initialize this matrix with a positive definite upper triangular matrix. Dimensions are 1-by-1, where 1 is the filter length.

### **KalmanGain**

Empty when you construct the object, this gets populated after you run the filter.

### **KalmanGainStates**

Contains the states of the Kalman gain updates during adaptation.

### **Leakage**

Contains the setting for leakage in the adaptive filter algorithm. Using a leakage factor that is not 1 forces the weights to adapt even when they have found the minimum error solution. Forcing the adaptation can improve the numerical performance of the LMS algorithm.

### **OffsetCov**

Contains the offset covariance matrix.

### **Offset**

Specifies an optional offset for the denominator of the step size normalization term. You must specify offset to be a scalar greater than or equal to zero. Nonzero offsets can help avoid a divide-by-near-zero condition that causes errors.

Use this to avoid dividing by zero or by very small numbers when input signal amplitude becomes very small, or dividing by very small numbers when any of the FFT input signal powers become very small. `offset` defaults to one.

### **Power**

A vector of 2\*1 elements, each initialized with the value `delta` from the input arguments. As you filter data, `Power` gets updated by the filter process.

**ProjectionOrder**

Projection order of the affine projection algorithm. `projectord` defines the size of the input signal covariance matrix and defaults to two.

**ReflectionCoeffs**

For adaptive filters that use reflection coefficients, this property stores them.

**ReflectionCoeffsStep**

As the adaptive filter changes coefficient values during adaptation, the step size used between runs is stored here.

**PersistentMemory**

Determines whether the filter states and coefficients get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter.

`PersistentMemory` returns to zero any property value that the filter changes during processing. Property values that the filter does not change are not affected. Defaults to `false`.

**SecondaryPathCoeffs**

A vector that contains the coefficient values of your secondary path from the output actuator to the error sensor.

**SecondaryPathEstimate**

An estimate of the secondary path filter model.

**SecondaryPathStates**

The states of the secondary path filter, the unknown system.

**SqrtCov**

Upper-triangular Cholesky (square root) factor of the input covariance matrix. Initialize this matrix with a positive definite upper triangular matrix.

### **SqrtInvCov**

Square root of the inverse of the sliding window input signal covariance matrix. This square matrix should be full-ranked.

### **States**

Vector of the adaptive filter states. `states` defaults to a vector of zeros whose length depends on the chosen algorithm. Usually the length is a function of the filter length `l` and another input argument to the filter object, such as `projectord`.

### **StepSize**

Reports the size of the step taken between iterations of the adaptive filter process. Each `adaptfilt` object has a default value that best meets the needs of the algorithm.

### **SwBlockLength**

Block length of the sliding window. This integer must be at least as large as the filter length. `swblocklength` defaults to 16.

## **References for Adaptive Filters**

- [1] Griffiths, L.J., *A Continuously Adaptive Filter Implemented as a Lattice Structure*, Proc. IEEE Int. Conf. on Acoustics, Speech, and Signal Processing, Hartford, CT, pp. 683-686, 1977.
- [2] Hayes, M.H., *Statistical Digital Signal Processing and Modeling*, John Wiley and Sons, 1996.
- [3] Haykin, S., *Adaptive Filter Theory*, Third Edition, Prentice-Hall, Inc., 1996.

## Multirate Filter Properties

### In this section...

“Property Summaries” on page 8-115

“Property Details for Multirate Filter Properties” on page 8-120

“References for Multirate Filters” on page 8-130

### Property Summaries

The following table summarizes the multirate filter properties and provides a brief description of each. Full descriptions of each property are given in the subsequent section.

Name	Values	Default	Description
BlockLength	Positive integers	100	Length of each block of data input to the FFT used in the filtering. <code>fftfirinterp</code> multirate filters include this property.
DecimationFactor	Any positive integer	2	Amount to reduce the input sampling rate.
DifferentialDelay	Any integer	1	Sets the differential delay for the filter. Usually a value of one or two is appropriate.

Name	Values	Default	Description
FilterInternals	FullPrecision, MinWordlengths, SpecifyWordLengths, SpecifyPrecision	FullPrecision	Controls whether the filter sets the output word and fraction lengths, and the accumulator word and fraction lengths automatically to maintain the best precision results during filtering. The default value, <code>FullPrecision</code> , sets automatic word and fraction length determination by the filter. <code>SpecifyPrecision</code> exposes the output and accumulator related properties so you can set your own word and fraction lengths for them.
FilterStructure	mfilt structure string	None	Describes the signal flow for the filter object, including all of the active elements that perform operations during filtering — gains, delays, sums, products, and input/output. You cannot set this property — it is always read only and results from your choice of <code>mfilt</code> object.

Name	Values	Default	Description
InputOffset	Integers	0	Contains the number of input data samples processed without generating an output sample. $\text{InputOffset} = \text{mod}(\text{length}(nx), m)$ where $nx$ is the number of input samples that have been processed so far and $m$ is the decimation factor.
InterpolationFactor	Positive integers	2	Interpolation factor for the filter. 1 specifies the amount to increase the input sampling rate.
NumberOfSections	Any positive integer	2	Number of sections used in the decimator, or in the comb and integrator portions of CIC filters.
Numerator	Array of double values	No default values	Vector containing the coefficients of the FIR lowpass filter used for interpolation.
OverflowMode	saturate, [wrap]	wrap	Sets the mode used to respond to overflow conditions in fixed-point arithmetic. Choose from either saturate (limit the output to the largest positive or negative representable value) or wrap (set overflowing values to the nearest representable value using modular arithmetic. The choice you make affects only the accumulator and output

Name	Values	Default	Description
			<p>arithmetic. Coefficient and input arithmetic always saturates. Finally, products never overflow — they maintain full precision.</p>
PolyphaseAccum	<p>Values depend on filter type. Either double, single, or fixed-point object</p>	0	<p>Stores the value remaining in the accumulator after the filter processes the last input sample. The stored value for PolyphaseAccum affects the next output when PersistentMemory is true and InputOffset is not equal to 0. Always provides full precision values. Compare the AccumWordLength and AccumFracLength.</p>
PersistentMemory	false or true	false	<p>Determines whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter if you have not changed the filter since you constructed it. PersistentMemory returns to zero any state that the filter changes during processing. States that the filter does not change are not affected.</p>

Name	Values	Default	Description
RateChangeFactors	[1,m]	[2,3] or [3,2]	Reports the decimation (m) and interpolation (1) factors for the filter object. Combining these factors results in the final rate change for the signal. The default changes depending on whether the filter decimates or interpolates.
States	Any m+1-by-n matrix of double values	2-by-2 matrix, int32	Stored conditions for the filter, including values for the integrator and comb sections. n is the number of filter sections and m is the differential delay. Stored in a <code>filtstates</code> object.
SpecifyWordLengths	Vector of integers	[16 16 16 16] bits	
WordLengthPerSection	Any integer or a vector of length 2*n	16	Defines the word length used in each section while accumulating the data in the integrator sections or while subtracting the data during the comb sections (using 'wrap' arithmetic). Enter <code>WordLengthPerSection</code> as a scalar or vector of length 2*n, where n is the number of sections. When <code>WordLengthPerSection</code> is a scalar, the scalar value is applied to each filter section. The default is 16 for each section in the decimator.

The following sections provide details about the properties that govern the way multirate filter work. Creating any multirate filter object puts in place a number of these properties. The following pages list the `mfilt` object properties in alphabetical order.

## Property Details for Multirate Filter Properties

### **BitsPerSection**

Any integer or a vector of length  $2*n$ .

Defines the bits per section used while accumulating the data in the integrator sections or while subtracting the data during the comb sections (using `wrap` arithmetic). Enter `bps` as a scalar or vector of length  $2*n$ , where  $n$  is the number of sections. When `bps` is a scalar, the scalar value is applied to each filter section. The default is 16 for each section in the decimator.

### **BlockLength**

Length of each block of input data used in the filtering.

`mfilt.fftfirinterp` objects process data in blocks whose length is determined by the value you set for the `BlockLength` property. By default the property value is 100. When you set the `BlockLength` value, try choosing a value so that  $[\text{BlockLength} + \text{length}(\text{filter order})]$  is a power of two.

Larger block lengths generally reduce the computation time.

### **DecimationFactor**

Decimation factor for the filter. `m` specifies the amount to reduce the sampling rate of the input signal. It must be an integer. You can enter any integer value. The default value is 2.

### **DifferentialDelay**

Sets the differential delay for the filter. Usually a value of one or two is appropriate. While you can set any value, the default is one and the maximum is usually two.

## FilterInternals

Similar to the FilterInternals pane in FDATool, this property controls whether the filter sets the output word and fraction lengths automatically, and the accumulator word and fraction lengths automatically as well, to maintain the best precision results during filtering. The default value, FullPrecision, sets automatic word and fraction length determination by the filter. Setting FilterInternals to SpecifyPrecision exposes the output and accumulator related properties so you can set your own word and fraction lengths for them.

**About FilterInternals Mode.** There are four usage modes for this that you set using the FilterInternals property in multirate filters.

- FullPrecision — All word and fraction lengths set to  $B_{max} + 1$ , called  $B_{accum}$  by Fred Harris in [2]. Full precision is the default setting.
- MinWordLengths — Minimum Word Lengths
- SpecifyWordLengths — Specify Word Lengths
- SpecifyPrecision — Specify Precision

### Full Precision

In full precision mode, the word lengths of all sections and the output are set to  $B_{accum}$  as defined by

$$B_{accum} = \text{ceil}(N_{secs}(\text{Log}_2(D \times M)) + \text{InputWordLength})$$

where  $N_{secs}$  is the number of filter sections.

Section fraction lengths and the fraction length of the output are set to the input fraction length.

Here is the display looks for this mode.

```
FilterStructure: 'Cascaded Integrator-Comb Decimator'
Arithmetic: 'fixed'
DifferentialDelay: 1
NumberOfSections: 2
DecimationFactor: 4
PersistentMemory: false
```

```
InputWordLength: 16  
InputFracLength: 15
```

```
FilterInternals: 'FullPrecision'
```

### Minimum Word Lengths

In minimum word length mode, you control the output word length explicitly. When the output word length is less than  $B_{accum}$ , roundoff noise is introduced at the output of the filter. Hogenauer's bit pruning theory (refer to [3] in the following References section) states that one valid design criterion is to make the word lengths of the different sections of the filter smaller than  $B_{accum}$  as well, so that the roundoff noise introduced by all sections does not exceed the roundoff noise introduced at the output.

In this mode, the design calculates the word lengths of each section to meet the Hogenauer criterion. The algorithm subtracts the number of bits computed using eq. 21 in Hogenauer's paper from  $B_{accum}$  to determine the word length each section.

To compute the fraction lengths of the different sections, the algorithm notes that the bits thrown out for this word length criterion are least significant bits (LSB), therefore each bit thrown out at a particular section decrements the fraction length of that section by one bit compared to the input fraction length. Setting the output word length for the filter automatically sets the output fraction length as well.

Here is the display for this mode:

```
FilterStructure: 'Cascaded Integrator-Comb Decimator'  
Arithmetic: 'fixed'  
DifferentialDelay: 1  
NumberOfSections: 2  
DecimationFactor: 4  
PersistentMemory: false
```

```
InputWordLength: 16  
InputFracLength: 15
```

```
FilterInternals: 'MinWordLengths'
```

```
OutputWordLength: 16
```

### Specify Word Lengths

In this mode, the design algorithm discards the LSBs, adjusting the fraction length so that unrecoverable overflow does not occur, always producing a reasonable output.

You can specify the word lengths for all sections and the output, but you cannot control the fraction lengths for those quantities.

To specify the word lengths, you enter a vector of length  $2 \times (\text{NumberOfSections})$ , where each vector element represents the word length for a section. If you specify a scalar, such as  $B_{accum}$ , the full-precision output word length, the algorithm expands that scalar to a vector of the appropriate size, applying the scalar value to each section.

The CIC design does not check that the specified word lengths are monotonically decreasing. There are some cases where the word lengths are not necessarily monotonically decreasing, for example

```
hcic=mfilt.cicdecim;
hcic.FilterInternals='minwordlengths';
hcic.Outputwordlength=14;
```

which are valid CIC filters but the word lengths do not decrease monotonically across the sections.

Here is the display looks like for the SpecifyWordLengths mode.

```
FilterStructure: 'Cascaded Integrator-Comb Decimator'
Arithmetic: 'fixed'
DifferentialDelay: 1
NumberOfSections: 2
DecimationFactor: 4
PersistentMemory: false

InputWordLength: 16
InputFracLength: 15
```

```
FilterInternals: 'SpecifyWordLengths'
```

```
SectionWordLengths: [19 18 18 17]
```

```
OutputWordLength: 16
```

### **Specify Precision**

In this mode, you have full control over the word length and fraction lengths of all sections and the filter output.

When you elect the `SpecifyPrecision` mode, you must enter a vector of length  $2*(\text{NumberOfSections})$  with elements that represent the word length for each section. When you enter a scalar such as  $B_{accum}$ , the CIC algorithm expands that scalar to a vector of the appropriate size and applies the scalar value to each section and the output. The design does not check that this vector is monotonically decreasing.

Also, you must enter a vector of length  $2*(\text{NumberOfSections})$  with elements that represent the fraction length for each section as well. When you enter a calar such as  $B_{accum}$ , the design applies scalar expansion as done for the word lengths.

Here is the `SpecifyPrecision` display.

```
FilterStructure: 'Cascaded Integrator-Comb Decimator'
```

```
Arithmetic: 'fixed'
```

```
DifferentialDelay: 1
```

```
NumberOfSections: 2
```

```
DecimationFactor: 4
```

```
PersistentMemory: false
```

```
InputWordLength: 16
```

```
InputFracLength: 15
```

```
FilterInternals: 'SpecifyPrecision'
```

```
SectionWordLengths: [19 18 18 17]
```

```
SectionFracLengths: [14 13 13 12]
```

```
OutputWordLength: 16
OutputFracLength: 11
```

### FilterStructure

Reports the type of filter object, such as a decimator or fractional integrator. You cannot set this property — it is always read only and results from your choice of `mfilt` object. Because of the length of the names of multirate filters, `FilterStructure` often returns a vector specification for the string. For example, when you use `mfilt.firfracinterp` to design a filter, `FilterStructure` returns as [1x49 char].

```
hm=mfilt.firfracinterp
```

```
hm =
```

```
    FilterStructure: [1x49 char]
           Numerator: [1x72 double]
RateChangeFactors: [3 2]
 PersistentMemory: false
           States: [24x1 double]
```

### InputOffset

When you decimate signals whose length is not a multiple of the decimation factor  $M$ , the last samples —  $(nM + 1)$  to  $[(n+1)(M) - 1]$ , where  $n$  is an integer — are processed and used to track where the filter stopped processing input data and when to expect the next output sample. If you think of the filtering process as generating an output for a block of input data, `InputOffset` contains a count of the number of samples in the last incomplete block of input data.

---

**Note** `InputOffset` applies only when you set `PersistentMemory` to true. Otherwise, `InputOffset` is not available for you to use.

---

Two different cases can arise when you decimate a signal:

- 1 The input signal is a multiple of the filter decimation factor. In this case, the filter processes the input samples and generates output samples for all inputs as determined by the decimation factor. For example, processing 99 input samples with a filter that decimates by three returns 33 output samples.
- 2 The input signal is not a multiple of the decimation factor. When this occurs, the filter processes all of the input samples, generates output samples as determined by the decimation factor, and has one or more input samples that were processed but did not generate an output sample.

For example, when you filter 100 input samples with a filter which has decimation factor of 3, you get 33 output samples, and 1 sample that did not generate an output. In this case, `InputOffset` stores the value 1 after the filter run.

`InputOffset` equal to 1 indicates that, if you divide your input signal into blocks of data with length equal to your filter decimation factor, the filter processed one sample from a new (incomplete) block of data. Subsequent inputs to the filter are concatenated with this single sample to form the next block of length `m`.

One way to define the value stored in `InputOffset` is

```
InputOffset = mod(length(nx),m)
```

where `nx` is the number of input samples in the data set and `m` is the decimation factor.

Storing `InputOffset` in the filter allows you to stop filtering a signal at any point and start over from there, provided that the `PersistentMemory` property is set to `true`. Being able to resume filtering after stopping a signal lets you break large data sets in to smaller pieces for filtering. With `PersistentMemory` set to `true` and the `InputOffset` property in the filter, breaking a signal into sections of arbitrary length and filtering the sections is equivalent to filtering the entire signal at once.

```
xtot=[x,x];  
ytot=filter(hm1,xtot)  
ytot =
```

```

        0   -0.0003   0.0005  -0.0014   0.0028  -0.0054   0.0092
reset(hm1); % Clear history of the filter
hm1.PersistentMemory='true';
ysec=[filter(hm1,x) filter(hm1,x)]

ysec =

        0   -0.0003   0.0005  -0.0014   0.0028  -0.0054   0.0092

```

This test verifies that `ysec` (the signal filtered by sections) is equal to `ytot` (the entire signal filtered at once).

### InterpolationFactor

Amount to increase the sampling rate. Interpolation factor for the filter. It specifies the amount to increase the input sampling rate. It must be an integer. Two is the default value. You may use any positive value.

### NumberOfSections

Number of sections used in the multirate filter. By default multirate filters use two sections, but any positive integer works.

### OverflowMode

The `OverflowMode` property is specified as one of the following two strings indicating how to respond to overflows in fixed-point arithmetic:

- `'saturate'` — saturate overflows.

When the values of data to be quantized lie outside of the range of the largest and smallest representable numbers (as specified by the applicable word length and fraction length properties), these values are quantized to the value of either the largest or smallest representable value, depending on which is closest.

- `'wrap'` — wrap all overflows to the range of representable values.

When the values of data to be quantized lie outside of the range of the largest and smallest representable numbers (as specified by the data format properties), these values are wrapped back into that range using modular

arithmetic relative to the smallest representable number. You can learn more about modular arithmetic in *Fixed-Point Toolbox* documentation.

These rules apply to the `OverflowMode` property.

- Applies to the accumulator and output data only.
- Does not apply to coefficients or input data. These always saturate the results.
- Does not apply to products. Products maintain full precision at all times. Your filters do not lose precision in the products.

**Default value:** 'saturate'

---

**Note** Numbers in floating-point filters that extend beyond the dynamic range overflow to  $\pm\text{inf}$ .

---

### **PolyphaseAccum**

The idea behind `PolyphaseAccum` and `AccumWordLength/AccumFracLength` is to distinguish between the adders that always work in full precision (`PolyphaseAccum`) from the others [the adders that are controlled by the user (through `AccumWordLength` and `AccumFracLength`) and that may introduce quantization effects when you set property `FilterInternals` to `SpecifyPrecision`].

Given a product format determined by the input word and fraction lengths, and the coefficients word and fraction lengths, doing full precision accumulation means allowing enough guard bits to avoid overflows and underflows.

Property `PolyphaseAccum` stores the value that was in the accumulator the last time your filter ran out of input samples to process. The default value for `PolyphaseAccum` affects the next output only if `PersistentMemory` is true and `InputOffset` is not equal to 0.

`PolyphaseAccum` stores data in the format for the filter arithmetic. Double-precision filters store doubles in `PolyphaseAccum`. Single-precision

filter store singles in `PolyphaseAccum`. Fixed-point filters store `fi` objects in `PolyphaseAccum`.

## PersistentMemory

Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter if you have not changed the filter since you constructed it. `PersistentMemory` returns to zero any state that the filter changes during processing. States that the filter does not change are not affected.

Determine whether the filter states get restored to their starting values for each filtering operation. The starting values are the values in place when you create the filter object. `PersistentMemory` returns to zero any state that the filter changes during processing. States that the filter does not change are not affected. Defaults to `true` — the filter retains memory about filtering operations from one to the next. Maintaining memory lets you filter large data sets as collections of smaller subsets and get the same result.

```
xtot=[x,x];
ytot=filter(hm1,xtot)
ytot =

         0   -0.0003    0.0005   -0.0014    0.0028   -0.0054    0.0092
reset(hm1); % Clear history of the filter
hm1.PersistentMemory='true';
ysec=[filter(hm1,x) filter(hm1,x)]

ysec =

         0   -0.0003    0.0005   -0.0014    0.0028   -0.0054    0.0092
```

This test verifies that `ysec` (the signal filtered by sections) is equal to `ytot` (the entire signal filtered at once).

## RateChangeFactors

Reports the decimation (`m`) and interpolation (`l`) factors for the filter object when you create fractional integrators and decimators, although `m` and `l` are used as arguments to both decimators and integrators, applying the

same meaning. Combining these factors as input arguments to the fractional decimator or integrator results in the final rate change for the signal.

For decimating filters, the default is [2,3]. For integrators, [3,2].

### States

Stored conditions for the filter, including values for the integrator and comb sections.  $m$  is the differential delay and  $n$  is the number of sections in the filter.

**About the States of Multirate Filters.** In the `states` property you find the states for both the integrator and comb portions of the filter, stored in a `filtstates` object. `states` is a matrix of dimensions  $m+1$ -by- $n$ , with the states in CIC filters apportioned as follows:

- States for the integrator portion of the filter are stored in the first row of the state matrix.
- States for the comb portion fill the remaining rows in the state matrix.

In the state matrix, state values are specified and stored in `double` format.

`States` stores conditions for the delays between each interpolator phase, the filter states, and the states at the output of each phase in the filter, including values for the interpolator and comb states.

The number of states is  $(l_h-1)*m+(l-1)*(l_0+m_0)$  where  $l_h$  is the length of each subfilter, and  $l$  and  $m$  are the interpolation and decimation factors.  $l_0$  and  $m_0$ , the input and output delays between each interpolation phase, are integers from Euclid's theorem such that  $l_0*l-m_0*m = -1$  (refer to the reference for more details). Use `euclidfactors` to get  $l_0$  and  $m_0$  for an `mfilt.firfracdecim` object.

`States` defaults to a vector of zeros that has length equal to `nstates(hm)`

### References for Multirate Filters

[1] Fliege, N.J., *Multirate Digital Signal Processing*, John Wiley and Sons, 1994.

[2] Harris, Fredric J, *Multirate Signal Processing for Communication Systems*, Prentice Hall PTR, 2004.

[3] Hogenauer, E. B., "An Economical Class of Digital Filters for Decimation and Interpolation," *IEEE Transactions on Acoustics, Speech, and Signal Processing*, Vol. ASSP-29, No. 2, April 1981, pp. 155-162.

[4] Lyons, Richard G., *Understanding Digital Signal Processing*, Prentice Hall PTR, 2004

[5] Mitra, S.K., *Digital Signal Processing*, McGraw-Hill, 1998.

[6] Orfanidis, S.J., *Introduction to Signal Processing*, Prentice-Hall, Inc., 1996.



This glossary defines terms related to fixed-point data types and numbers. These terms may appear in some or all of the documents that describe MathWorks® products that have fixed-point support.

## **arithmetic shift**

Shift of the bits of a binary word for which the sign bit is recycled for each bit shift to the right. A zero is incorporated into the least significant bit of the word for each bit shift to the left. In the absence of overflows, each arithmetic shift to the right is equivalent to a division by 2, and each arithmetic shift to the left is equivalent to a multiplication by 2.

*See also* binary point, binary word, bit, logical shift, most significant bit

## **bias**

Part of the numerical representation used to interpret a fixed-point number. Along with the slope, the bias forms the scaling of the number. Fixed-point numbers can be represented as

$$\text{real-world value} = (\text{slope} \times \text{stored integer}) + \text{bias}$$

where the slope can be expressed as

$$\text{slope} = \text{fractional slope} \times 2^{\text{exponent}}$$

*See also* fixed-point representation, fractional slope, integer, scaling, slope, [Slope Bias]

## **binary number**

Value represented in a system of numbers that has two as its base and that uses 1's and 0's (bits) for its notation.

*See also* bit

**binary point**

Symbol in the shape of a period that separates the integer and fractional parts of a binary number. Bits to the left of the binary point are integer bits and/or sign bits, and bits to the right of the binary point are fractional bits.

*See also* binary number, bit, fraction, integer, radix point

**binary point-only scaling**

Scaling of a binary number that results from shifting the binary point of the number right or left, and which therefore can only occur by powers of two.

*See also* binary number, binary point, scaling

**binary word**

Fixed-length sequence of bits (1's and 0's). In digital hardware, numbers are stored in binary words. The way in which hardware components or software functions interpret this sequence of 1's and 0's is described by a data type.

*See also* bit, data type, word

**bit**

Smallest unit of information in computer software or hardware. A bit can have the value 0 or 1.

**ceiling (round toward)**

Rounding mode that rounds to the closest representable number in the direction of positive infinity. This is equivalent to the `ceil` mode in Fixed-Point Toolbox software.

*See also* convergent rounding, floor (round toward), nearest (round toward), rounding, truncation, zero (round toward)

**contiguous binary point**

Binary point that occurs within the word length of a data type. For example, if a data type has four bits, its contiguous binary point must be understood to occur at one of the following five positions:

.0000

0.000

00.00

000.0

0000.

*See also* data type, noncontiguous binary point, word length

**convergent rounding**

Rounding mode that rounds to the nearest allowable quantized value. Numbers that are exactly halfway between the two nearest allowable quantized values are rounded up only if the least significant bit (after rounding) would be set to 0.

*See also* ceiling (round toward), floor (round toward), nearest (round toward), rounding, truncation, zero (round toward)

**data type**

Set of characteristics that define a group of values. A fixed-point data type is defined by its word length, its fraction length, and whether it is signed or unsigned. A floating-point data type is defined by its word length and whether it is signed or unsigned.

*See also* fixed-point representation, floating-point representation, fraction length, signedness, word length

**data type override**

Parameter in the Fixed-Point Tool that allows you to set the output data type and scaling of fixed-point blocks on a system or subsystem level.

*See also* data type, scaling

**exponent**

Part of the numerical representation used to express a floating-point or fixed-point number.

1. Floating-point numbers are typically represented as

$$\textit{real-world value} = \textit{mantissa} \times 2^{\textit{exponent}}$$

2. Fixed-point numbers can be represented as

$$\textit{real-world value} = (\textit{slope} \times \textit{stored integer}) + \textit{bias}$$

where the slope can be expressed as

$$\textit{slope} = \textit{fractional slope} \times 2^{\textit{exponent}}$$

The exponent of a fixed-point number is equal to the negative of the fraction length:

$$\textit{exponent} = -1 \times \textit{fraction length}$$

*See also* bias, fixed-point representation, floating-point representation, fraction length, fractional slope, integer, mantissa, slope

### **fixed-point representation**

Method for representing numerical values and data types that have a set range and precision.

1. Fixed-point numbers can be represented as

$$\textit{real-world value} = (\textit{slope} \times \textit{stored integer}) + \textit{bias}$$

where the slope can be expressed as

$$\textit{slope} = \textit{fractional slope} \times 2^{\textit{exponent}}$$

The slope and the bias together represent the scaling of the fixed-point number.

2. Fixed-point data types can be defined by their word length, their fraction length, and whether they are signed or unsigned.

*See also* bias, data type, exponent, fraction length, fractional slope, integer, precision, range, scaling, slope, word length

**floating-point representation**

Method for representing numerical values and data types that can have changing range and precision.

1. Floating-point numbers can be represented as

$$\text{real-world value} = \text{mantissa} \times 2^{\text{exponent}}$$

2. Floating-point data types are defined by their word length.

*See also* data type, exponent, mantissa, precision, range, word length

**floor (round toward)**

Rounding mode that rounds to the closest representable number in the direction of negative infinity.

*See also* ceiling (round toward), convergent rounding, nearest (round toward), rounding, truncation, zero (round toward)

**fraction**

Part of a fixed-point number represented by the bits to the right of the binary point. The fraction represents numbers that are less than one.

*See also* binary point, bit, fixed-point representation

**fraction length**

Number of bits to the right of the binary point in a fixed-point representation of a number.

*See also* binary point, bit, fixed-point representation, fraction

**fractional slope**

Part of the numerical representation used to express a fixed-point number. Fixed-point numbers can be represented as

$$\textit{real-world value} = (\textit{slope} \times \textit{stored integer}) + \textit{bias}$$

where the slope can be expressed as

$$\textit{slope} = \textit{fractional slope} \times 2^{\textit{exponent}}$$

The term *slope adjustment* is sometimes used as a synonym for fractional slope.

*See also* bias, exponent, fixed-point representation, integer, slope

**full range**

The broadest range available for a data type. From  $-\infty$  to  $\infty$  for floating-point types. For integer types, the representable range is the range from the smallest to largest integer value (finite) the type can represent. For example, from -128 to 127 for a signed 8-bit integer. Also known as representable range.

**guard bits**

Extra bits in either a hardware register or software simulation that are added to the high end of a binary word to ensure that no information is lost in case of overflow.

*See also* binary word, bit, overflow

**incorrect range**

A range that is too restrictive and does not include values that can actually occur in the model element. A range that is too broad is not considered incorrect because it will not lead to overflow.

*See also* range analysis

**integer**

1. Part of a fixed-point number represented by the bits to the left of the binary point. The integer represents numbers that are greater than or equal to one.

2. Also called the "stored integer." The raw binary number, in which the binary point is assumed to be at the far right of the word. The integer is part of the numerical representation used to express a fixed-point number. Fixed-point numbers can be represented as

$$\text{real-world value} = 2^{-\text{fraction length}} \times \text{stored integer}$$

or

$$\text{real-world value} = (\text{slope} \times \text{stored integer}) + \text{bias}$$

where the slope can be expressed as

$$\text{slope} = \text{fractional slope} \times 2^{\text{exponent}}$$

*See also* bias, fixed-point representation, fractional slope, integer, real-world value, slope

### **integer length**

Number of bits to the left of the binary point in a fixed-point representation of a number.

*See also* binary point, bit, fixed-point representation, fraction length, integer

### **least significant bit (LSB)**

Bit in a binary word that can represent the smallest value. The LSB is the rightmost bit in a big-endian-ordered binary word. The weight of the LSB is related to the fraction length according to

$$\text{weight of LSB} = 2^{-\text{fraction length}}$$

*See also* big-endian, binary word, bit, most significant bit

**logical shift**

Shift of the bits of a binary word, for which a zero is incorporated into the most significant bit for each bit shift to the right and into the least significant bit for each bit shift to the left.

*See also* arithmetic shift, binary point, binary word, bit, most significant bit

**mantissa**

Part of the numerical representation used to express a floating-point number. Floating-point numbers are typically represented as

$$\text{real - world value} = \text{mantissa} \times 2^{\text{exponent}}$$

*See also* exponent, floating-point representation

**model element**

Entities in a model that range analysis software tracks, for example, blocks, signals, parameters, block internal data (such as accumulators, products).

*See also* range analysis

**most significant bit (MSB)**

Bit in a binary word that can represent the largest value. The MSB is the leftmost bit in a big-endian-ordered binary word.

*See also* binary word, bit, least significant bit

**nearest (round toward)**

Rounding mode that rounds to the closest representable number, with the exact midpoint rounded to the closest representable number in the direction of positive infinity. This is equivalent to the nearest mode in Fixed-Point Toolbox software.

*See also* ceiling (round toward), convergent rounding, floor (round toward), rounding, truncation, zero (round toward)

**noncontiguous binary point**

Binary point that is understood to fall outside the word length of a data type. For example, the binary point for the following 4-bit word is understood to occur two bits to the right of the word length,

0000\_\_.

thereby giving the bits of the word the following potential values:

$2^5 2^4 2^3 2^2$  \_\_.

*See also* binary point, data type, word length

**one's complement representation**

Representation of signed fixed-point numbers. Negating a binary number in one's complement requires a bitwise complement. That is, all 0's are flipped to 1's and all 1's are flipped to 0's. In one's complement notation there are two ways to represent zero. A binary word of all 0's represents "positive" zero, while a binary word of all 1's represents "negative" zero.

*See also* binary number, binary word, sign/magnitude representation, signed fixed-point, two's complement representation

**overflow**

Situation that occurs when the magnitude of a calculation result is too large for the range of the data type being used. In many cases you can choose to either saturate or wrap overflows.

*See also* saturation, wrapping

**padding**

Extending the least significant bit of a binary word with one or more zeros.

*See also* least significant bit

**precision**

1. Measure of the smallest numerical interval that a fixed-point data type and scaling can represent, determined by the value of the number's least significant bit. The precision is given by the slope, or the number

of fractional bits. The term *resolution* is sometimes used as a synonym for this definition.

2. Measure of the difference between a real-world numerical value and the value of its quantized representation. This is sometimes called quantization error or quantization noise.

*See also* data type, fraction, least significant bit, quantization, quantization error, range, slope

### **Q format**

Representation used by Texas Instruments™ to encode signed two's complement fixed-point data types. This fixed-point notation takes the form

$$Qm.n$$

where

- $Q$  indicates that the number is in Q format.
- $m$  is the number of bits used to designate the two's complement integer part of the number.
- $n$  is the number of bits used to designate the two's complement fractional part of the number, or the number of bits to the right of the binary point.

In Q format notation, the most significant bit is assumed to be the sign bit.

*See also* binary point, bit, data type, fixed-point representation, fraction, integer, two's complement

### **quantization**

Representation of a value by a data type that has too few bits to represent it exactly.

*See also* bit, data type, quantization error

### **quantization error**

Error introduced when a value is represented by a data type that has too few bits to represent it exactly, or when a value is converted from

one data type to a shorter data type. Quantization error is also called quantization noise.

*See also* bit, data type, quantization

**radix point**

Symbol in the shape of a period that separates the integer and fractional parts of a number in any base system. Bits to the left of the radix point are integer and/or sign bits, and bits to the right of the radix point are fraction bits.

*See also* binary point, bit, fraction, integer, sign bit

**range**

Span of numbers that a certain data type can represent.

*See also* data type, full range, precision, representable range

**range analysis**

Static analysis of model to derive minimum and maximum range values for elements in the model. The software statically analyzes the ranges of the individual computations in the model based on specified design ranges, inputs, and the semantics of the calculation.

**real-world value**

Stored integer value with fixed-point scaling applied. Fixed-point numbers can be represented as

$$\text{real-world value} = 2^{-\text{fraction length}} \times \text{stored integer}$$

or

$$\text{real-world value} = (\text{slope} \times \text{stored integer}) + \text{bias}$$

where the slope can be expressed as

$$\text{slope} = \text{fractional slope} \times 2^{\text{exponent}}$$

*See also* integer

**representable range**

The broadest range available for a data type. From  $-\infty$  to  $\infty$  for floating-point types. For integer types, the representable range is the range from the smallest to largest integer value (finite) the type can represent. For example, from -128 to 127 for a signed 8-bit integer. Also known as full range.

**resolution**

*See* **precision**

**rounding**

Limiting the number of bits required to express a number. One or more least significant bits are dropped, resulting in a loss of precision. Rounding is necessary when a value cannot be expressed exactly by the number of bits designated to represent it.

*See also* bit, ceiling (round toward), convergent rounding, floor (round toward), least significant bit, nearest (round toward), precision, truncation, zero (round toward)

**saturation**

Method of handling numeric overflow that represents positive overflows as the largest positive number in the range of the data type being used, and negative overflows as the largest negative number in the range.

*See also* overflow, wrapping

**scaled double**

A double data type that retains fixed-point scaling information. For example, in Simulink and Fixed-Point Toolbox software you can use data type override to convert your fixed-point data types to scaled doubles. You can then simulate to determine the ideal floating-point behavior of your system. After you gather that information you can turn data type override off to return to fixed-point data types, and your quantities still have their original scaling information because it was held in the scaled double data types.

**scaling**

1. Format used for a fixed-point number of a given word length and signedness. The slope and bias together form the scaling of a fixed-point number.
2. Changing the slope and/or bias of a fixed-point number without changing the stored integer.

*See also* bias, fixed-point representation, integer, slope

**shift**

Movement of the bits of a binary word either toward the most significant bit ("to the left") or toward the least significant bit ("to the right"). Shifts to the right can be either logical, where the spaces emptied at the front of the word with each shift are filled in with zeros, or arithmetic, where the word is sign extended as it is shifted to the right.

*See also* arithmetic shift, logical shift, sign extension

**sign bit**

Bit (or bits) in a signed binary number that indicates whether the number is positive or negative.

*See also* binary number, bit

**sign extension**

Addition of bits that have the value of the most significant bit to the high end of a two's complement number. Sign extension does not change the value of the binary number.

*See also* binary number, guard bits, most significant bit, two's complement representation, word

**sign/magnitude representation**

Representation of signed fixed-point or floating-point numbers. In sign/magnitude representation, one bit of a binary word is always the dedicated sign bit, while the remaining bits of the word encode the magnitude of the number. Negation using sign/magnitude representation consists of flipping the sign bit from 0 (positive) to 1 (negative), or from 1 to 0.

*See also* binary word, bit, fixed-point representation, floating-point representation, one's complement representation, sign bit, signed fixed-point, signedness, two's complement representation

**signed fixed-point**

Fixed-point number or data type that can represent both positive and negative numbers.

*See also* data type, fixed-point representation, signedness, unsigned fixed-point

**signedness**

The signedness of a number or data type can be signed or unsigned. Signed numbers and data types can represent both positive and negative values, whereas unsigned numbers and data types can only represent values that are greater than or equal to zero.

*See also* data type, sign bit, sign/magnitude representation, signed fixed-point, unsigned fixed-point

**slope**

Part of the numerical representation used to express a fixed-point number. Along with the bias, the slope forms the scaling of a fixed-point number. Fixed-point numbers can be represented as

$$\text{real-world value} = (\text{slope} \times \text{stored integer}) + \text{bias}$$

where the slope can be expressed as

$$\text{slope} = \text{fractional slope} \times 2^{\text{exponent}}$$

*See also* bias, fixed-point representation, fractional slope, integer, scaling, [Slope Bias]

**slope adjustment**

*See fractional slope*

**[Slope Bias]**

Representation used to define the scaling of a fixed-point number.

*See also* bias, scaling, slope

**stored integer**

*See integer*

**trivial scaling**

Scaling that results in the real-world value of a number being simply equal to its stored integer value:

$$\textit{real - world value} = \textit{stored integer}$$

In [Slope Bias] representation, fixed-point numbers can be represented as

$$\textit{real-world value} = (\textit{slope} \times \textit{stored integer}) + \textit{bias}$$

In the trivial case, slope = 1 and bias = 0.

In terms of binary point-only scaling, the binary point is to the right of the least significant bit for trivial scaling, meaning that the fraction length is zero:

$$\textit{real - world value} = \textit{stored integer} \times 2^{-\textit{fraction length}} = \textit{stored integer} \times 2^0$$

Scaling is always trivial for pure integers, such as `int8`, and also for the true floating-point types `single` and `double`.

*See also* bias, binary point, binary point-only scaling, fixed-point representation, fraction length, integer, least significant bit, scaling, slope, [Slope Bias]

**truncation**

Rounding mode that drops one or more least significant bits from a number.

*See also* ceiling (round toward), convergent rounding, floor (round toward), nearest (round toward), rounding, zero (round toward)

**two's complement representation**

Common representation of signed fixed-point numbers. Negation using signed two's complement representation consists of a translation into one's complement followed by the binary addition of a one.

*See also* binary word, one's complement representation, sign/magnitude representation, signed fixed-point

**unsigned fixed-point**

Fixed-point number or data type that can only represent numbers greater than or equal to zero.

*See also* data type, fixed-point representation, signed fixed-point, signedness

**word**

Fixed-length sequence of binary digits (1's and 0's). In digital hardware, numbers are stored in words. The way hardware components or software functions interpret this sequence of 1's and 0's is described by a data type.

*See also* binary word, data type

**word length**

Number of bits in a binary word or data type.

*See also* binary word, bit, data type

**wrapping**

Method of handling overflow. Wrapping uses modulo arithmetic to cast a number that falls outside of the representable range the data type being used back into the representable range.

*See also* data type, overflow, range, saturation

**zero (round toward)**

Rounding mode that rounds to the closest representable number in the direction of zero. This is equivalent to the `fix` mode in Fixed-Point Toolbox software.

*See also* ceiling (round toward), convergent rounding, floor (round toward), nearest (round toward), rounding, truncation

## A

- AccumFracLength 8-19
- AccumWordLength 8-19
- acquiring data
  - blocks for 1-18
  - objects for 3-10
- adaptfilt
  - about 7-2
  - copying 7-9
- adaptfilt object properties
  - Algorithm 8-107
  - AvgFactor 8-107
  - BkwdPredErrorPower 8-107
  - BkwdPrediction 8-107
  - Blocklength 8-110
  - Coefficients 8-110
  - ConversionFactor 8-110
  - Delay 8-110
  - DesiredSignalStates 8-110
  - EpsilonStates 8-110
  - ErrorStates 8-110
  - FFTCoefficients 8-110
  - FFTStates 8-111
  - FilteredInputStates 8-111
  - FilterLength 8-111
  - ForgettingFactor 8-111
  - FwdPredErrorPower 8-111
  - FwdPrediction 8-111
  - InitFactor 8-111
  - InvCov 8-112
  - KalmanGain 8-112
  - KalmanGainStates 8-112
  - Offset 8-112
  - OffsetCov 8-112
  - Power 8-112
  - ProjectionOrder 8-113
  - ReflectionCoeffsStep 8-113
  - ResetBeforeFiltering 8-113
  - SecondaryPathCoeffs 8-113
  - SecondaryPathEstimate 8-113
  - SecondaryPathStates 8-113
  - SqrtInvCov 8-114
  - States 8-114
  - StepSize 8-114
  - SwBlockLength 8-114
- adaptive filter designs
  - FIR 2-895
  - Kalman 2-841
  - LMS 2-895
  - RLS 2-1284
- adaptive filter properties
  - SqrtCov 8-113
- addition
  - cumulative 2-356
- addstages method 7-246
- Algorithm 8-107
- Allpole Filter block 2-2
- Analog Filter Design block 2-21
- analytic signal 2-26
- Analytic Signal block 2-26
- antisymmetricfir 8-53
- Arbitrary Response Filter block 2-29
- arithmetic
  - about fixed-point 8-19
- arithmetic property
  - double 8-20
  - fixed 8-22
  - single 8-21
- Array-Vector Add block 2-37
- Array-Vector Divide block 2-46
- Array-Vector Multiply block 2-53
- Array-Vector Subtract block 2-62
- audio
  - From Audio Device block 2-688
  - From Wave Device block 2-705
  - From Wave File block 2-712
  - To Audio Device block 2-1534
  - To Wave Device block 2-1547
  - To Wave File block 2-1556
- Audio Weighting Filter block 2-71

- autocorrelation
  - and Levinson-Durbin recursion 2-879
  - of a real vector 2-78
  - sequence 2-1820
- Autocorrelation block 2-78
- Autocorrelation LPC block 2-88
- autocorrelation method 2-1814
- autoregressive models, using
  - Burg AR Estimator block 2-179
  - Burg Method block 2-184
  - Covariance AR Estimator block 2-332
  - Covariance Method block 2-335
  - Modified Covariance AR Estimator block 2-1079
  - Modified Covariance Method block 2-1082
  - Yule-Walker AR Estimator block 2-1814
  - Yule-Walker Method block 2-1820
- AvgFactor 8-107

## B

- Backward Substitution block 2-93
- Bandpass Filter block 2-102
- bandpass filter designs
  - using Analog Filter Design block 2-21
- Bandstop Filter block 2-114
- bandstop filter designs
  - using Analog Filter Design block 2-21
- Bartlett windows 2-1798
- binary clock signals 2-1087
- bins
  - histogram 2-752
- Biquad Filter block 2-126
- BkwdPredErrorPower 8-107
- BkwdPrediction 8-107
- Blackman windows 2-1798
- Block LMS Filter block 2-161
- block method 7-246
- Blocklength 8-110
- Buffer block 2-168

- buffering
  - blocks for 1-12
  - Buffer block 2-168
  - first input, first output (FIFO) register 2-1242
  - last input, first output (LIFO) register 2-1406
  - Queue block 2-1242
  - Stack block 2-1406
- Burg AR Estimator block 2-179
- Burg Method block 2-184
  - power spectrum estimation 2-184
- Butterworth filter designs
  - using Analog Filter Design block 2-21

## C

- cascade method 7-246
- changing
  - size of frames 2-168
- Chebyshev type I filter designs
  - using Analog Filter Design block 2-21
- Chebyshev type II filter designs
  - using Analog Filter Design block 2-21
- Chebyshev windows 2-1798
- Check Signal Attributes block 2-191
- Chirp block 2-200
- Cholesky Factorization block 2-225
- Cholesky Inverse block 2-229
- Cholesky Solver block 2-232
- CIC Compensator block 2-235
- CIC Decimation block 2-244
- CIC Filter block 2-254
- CIC Interpolation block 2-261
- clocks
  - binary 2-1087
  - multiphase 2-1087
- CoeffAutoScale 8-35
- CoeffFracLength 8-40
- Coefficients 8-110

- coefficients method 7-246
  - CoeffWordLength 8-40
  - Comb Filter block 2-272
  - complex analytic signal 2-26
  - Complex Cepstrum block 2-279
  - Complex Exponential block 2-281
  - complex exponentials 2-281
  - computing
    - frequency distributions 2-752
    - histograms 2-752
  - Constant block 2-282
  - Constant Diagonal Matrix block 2-283
  - Constant Ramp block 2-287
  - constants
    - matrix 2-283
    - ramp 2-287
  - control signals, for
    - Triggered Shift Register block 2-1562
    - Triggered Signal From Workspace block 2-1566
    - Triggered Signal To Workspace block 2-1570
  - controller canonical forms 2-22
  - ConversionFactor 8-110
  - Convert 1-D to 2-D block 2-293
  - Convert 2-D to 1-D block 2-296
  - convert filters 8-65
  - convert method 7-246
  - convolution
    - of two real vectors 2-298
  - Convolution block 2-298
  - correlation
    - of two real vectors 2-309
  - Correlation block 2-309
  - correlation matrices 2-842
  - Counter block 2-319
  - Covariance AR Estimator block 2-332
  - Covariance Method block 2-335
    - spectral analysis 2-335
  - Create Diagonal Matrix block 2-339
  - Cumulative Product block 2-341
  - Cumulative Sum block 2-356
- ## D
- Data Type Conversion block 2-370
  - dB
    - converting to 2-371
  - dB Conversion block 2-371
  - dB Gain block 2-375
  - dBm
    - converting to 2-371
  - DC component of an analytic signal 2-26
  - DCT block 2-378
  - DCTs
    - computing 2-378
  - decimation
    - using FIR Decimation block 2-608
    - using FIR Rate Conversion block 2-652
  - delay 7-270
    - fractional 2-1643
  - Delay 8-110
  - Delay block 2-388
  - Delay Line block 2-404
  - DenAccumFracLength 8-41
  - DenFracLength 8-41
  - Denominator 8-41
  - DenProdFracLength 8-41
  - DenStateFracLength 8-42
  - DenStateWordLength 8-42
  - DesiredSignalStates 8-110
  - Detrend block 2-410
  - df1 8-46
  - df1t 8-48
  - df2 8-49
  - df2t 8-51
  - dfilt 7-6
    - cascade 7-262
    - df1 7-272
    - df1sos 7-281
    - df1t 7-291

- df1tsos 7-301
- df2 7-314
- df2sos 7-323
- df2t 7-334
- df2tsos 7-343
- direct-form antisymmetric FIR 7-354
- direct-form FIR transposed 7-369
- direct-form II transposed (df2t) 7-334
- direct-form IIR 7-362
- direct-form symmetric FIR 7-376
- lattice allpass 7-389
- lattice autoregressive 7-398
- lattice moving-average maximum 7-416
- lattice moving-average minimum 7-425
- parallel 7-434
- scalar 7-435
- See also* Signal Processing Toolbox
  - documentation
- dfilt function 7-241
  - convert structures 7-253
  - copying 7-252
  - delay 7-270
  - FFT FIR 7-387
  - methods 7-245
  - structures 7-241
- dfilt properties
  - arithmetic 8-19
- dfilt.cascade 7-262
- dfilt.delay function 7-270
- dfilt.df1 7-272
- dfilt.df1sos 7-281
- dfilt.df1t 7-291
- dfilt.df1tsos 7-301
- dfilt.df2 7-314
- dfilt.df2sos 7-323
- dfilt.df2t 7-334
- dfilt.df2tsos 7-343
- dfilt.dffir 7-362
- dfilt.dffirt 7-369
- dfilt.dfsymfir 7-376
- dfilt.fftfir function 7-387
- dfilt.latticeallpass 7-389
- dfilt.latticear 7-398
- dfilt.latticemamax 7-416
- dfilt.latticemamin 7-425
- dfilt.parallel 7-434
- dfilt.scalar 7-435
- diagonal matrix constants 2-283
- difference
  - between elements in a vector 2-412
- Difference block 2-412
- Differentiator Filter block 2-422
- Digital Filter block 2-431
- Digital Filter Design block 2-497
- direct-form I 8-47
  - transposed 8-48
- direct-form II 8-49
  - transposed 8-51
- discrete cosine transforms 2-378
- Discrete FIR Filter block 2-629
- Discrete Impulse block 2-518
- discrete wavelet transform 2-538
- Display block 2-523
- display span
  - Vector Scope Block 2-1730
- displaying
  - blocks for 1-17
  - frame-based data 2-1730
  - matrices as images 2-1001
  - objects for 3-9
- double
  - property value 8-20
- Downsample block 2-524
- downsampling
  - Downsample block 2-524
  - FIR Decimation block 2-608
  - FIR Rate Conversion block 2-652
- DSP Constant block 2-533
- DWT block 2-538
- Dyadic Analysis Filter Bank block 2-539

Dyadic Synthesis Filter Bank block 2-550  
dynamic properties 8-5

## E

Edge Detector block 2-562  
elements of a vector  
  selecting 2-1677  
elliptic filter designs  
  using Analog Filter Design block 2-21  
EpsilonStates 8-110  
ErrorStates 8-110  
estimation  
  blocks for 1-2  
  Burg AR Estimator block 2-179  
  Burg Method block 2-184  
  Covariance AR Estimator block 2-332  
  Covariance Method block 2-335  
  Modified Covariance AR Estimator  
    block 2-1079  
  Modified Covariance Method block 2-1082  
  nonparametric with Magnitude FFT  
    block 2-966  
  nonparametric with Short-Time FFT  
    block 2-1338  
  Yule-Walker AR Estimator block 2-1814  
  Yule-Walker Method block 2-1820  
Event-Count Comparator block 2-566  
events, triggering for  
  N-Sample Enable block 2-1097  
  N-Sample Switch block 2-1101  
  Sample and Hold block 2-1299  
  Stack block 2-1407  
  Triggered Shift Register block 2-1562  
  Triggered Signal From Workspace  
    block 2-1566  
  Triggered Signal To Workspace block 2-1570  
exponentials  
  complex 2-281  
exporting

  blocks for 1-17  
  objects for 3-9  
  using Triggered Signal To Workspace  
    block 2-1570

Extract Diagonal block 2-570  
Extract Triangular Matrix block 2-572

## F

Fast Block LMS Filter block 2-576  
fast Fourier transform (FFT) 2-583  
fcfwrite method 7-247  
FDATool  
  in DSP System Toolbox 2-497  
fdesign  
  reference 7-477  
FFT block 2-583  
FFTCoefficients 8-110  
fftcoeffs method 7-247  
FFTs  
  computing 2-583  
  overlap-add filtering 2-1151  
  overlap-save filtering 2-1155  
FFTStates 8-111  
filter  
  initial conditions 7-9  
  states 7-9  
filter conversions 8-66  
filter design  
  multirate 6-10  
filter designs  
  Digital Filter block 2-431  
  Digital Filter Design block 2-497  
  Levinson-Durbin block 2-880  
  using Analog Filter Design block 2-21  
filter method 7-247  
Filter Realization Wizard 2-598  
filter realizations  
  using Filter Realization Wizard 2-598  
filter sections

- specifying 8-66
- filter structures
  - about 8-43
  - all-pass lattice 8-58
  - direct-form antisymmetric FIR 8-53
  - direct-form FIR 8-55
  - direct-form I 8-46
  - direct-form I SOS IIR 8-47
  - direct-form I transposed 8-48
  - direct-form I transposed IIR 8-48
  - direct-form II 8-49
  - direct-form II IIR 8-49
  - direct-form II SOS IIR 8-50
  - direct-form II transposed 8-51
  - direct-form II transposed IIR 8-51
  - direct-form symmetric FIR 8-63
  - direct-form transposed FIR 8-56
  - FIR transposed 8-56
  - fixed-point 8-45
  - lattice allpass 8-58
  - lattice AR 8-60
  - lattice ARMA 8-62
  - lattice autoregressive moving average 8-62
  - lattice moving average maximum phase 8-59
  - lattice moving average minimum phase 8-60
- FilteredInputStates 8-111
- filterinternals
  - fixed-point filter 8-42
  - multirate filter 8-121
- FilterLength 8-111
- filters
  - blocks for 1-4
  - converting 8-65
  - FIR 8-43
  - impulse response 7-941
  - initial conditions using `dfilt` 7-253
  - lattice 8-43
  - objects 7-241
  - objects for 3-4
  - overlap-add method 2-1151
  - overlap-add using `dfilt.fftfir` 7-387
  - overlap-save method 2-1155
  - state-space 8-43
  - states 7-253
- FilterStructure property 8-43
- finite impulse response
  - antisymmetric 8-53
  - symmetric 8-63
- fir 8-55
- FIR
  - interpolation 2-813
  - FIR Decimation block 2-608
  - FIR filter designs
    - using Levinson-Durbin block 2-880
    - with prescribed autocorrelation sequence 2-880
  - FIR filters 8-43
    - least square linear phase 7-818
  - FIR Interpolation block 2-630
  - FIR Rate Conversion block 2-652
- first-input, first-output (FIFO) registers 2-1242
- firt 8-56
- firtype method 7-247
- fixed
  - arithmetic property value 8-22
- fixed-point filter properties
  - AccumFracLength 8-19
  - AccumWordLength 8-19
  - Arithmetic 8-19
  - CastBeforeSum 8-33
  - CoeffAutoScale 8-35
  - CoeffFracLength 8-40
  - CoeffWordLength 8-40
  - DenAccumFracLength 8-41
  - DenFracLength 8-41
  - Denominator 8-41
  - DenProdFracLength 8-41
  - DenStateFracLength 8-42
  - DenStateWordLength 8-42
  - FilterStructure 8-43

- fixed-point filter states 8-95
- fixed-point filter structures 8-45
- fixed-point filters
  - dynamic properties 8-5
- Flip block 2-669
- ForgettingFactor 8-111
- forms
  - controller canonical 2-22
  - state-space 2-22
- Forward Substitution block 2-672
- fraction length
  - about 8-29
  - negative number of bits 8-29
- Frame Conversion 2-682
- Frame Status Conversion block 2-685
- frames
  - changing size of 2-168
  - unbuffering to scalars 2-1615
- frequency distributions 2-752
  - computing 2-752
- frequency response 7-843
- freqz 7-843
- freqz method 7-247
- From Audio Device block 2-688
- From Multimedia File block 2-695
- From Wave Device block 2-705
- From Wave File block 2-712
- FwdPredErrorPower 8-111
- FwdPrediction 8-111

## G

- G.711 Codec block 2-718
- gain
  - applying in dB 2-375
- grpdelay method 7-247

## H

- Halfband Filter block 2-723

- Hamming windows 2-1798
- Hann windows 2-1798
- Highpass Filter block 2-732
- highpass filter designs
  - using Analog Filter Design block 2-21
- Hilbert Filter block 2-744
- Hilbert transformer filter designs 2-26
- Histogram block 2-752
- histograms
  - computing 2-752

## I

- IDCT block 2-764
- IDCTs 2-764
  - computing 2-764
- identity matrices 2-776
- Identity Matrix block 2-776
- IDWT block 2-781
- IFFT block 2-782
- IFFTs
  - computing 2-782
- images
  - displaying matrices as 2-1001
- importing
  - blocks for 1-18
  - objects for 3-10
  - scalars 2-712
  - signals from the workspace 2-1344
  - Triggered Signal From Workspace
    - block 2-1566
  - vectors 2-712
- impz method 7-247
- impzlength method 7-247
- indexing
  - blocks for 1-12
- info method
  - dfilt function 7-247
- Inherit Complexity block 2-800
- InitFactor 8-111

- initial conditions 7-9
    - using `dfilt` states 7-253
  - Integer Delay block 2-803
  - interpolating
    - FIR Interpolation block 2-630
    - FIR Rate Conversion block 2-652
    - procedure 2-630
  - Interpolation block 2-813
  - InvCov 8-112
  - inverse discrete cosine transforms 2-764
  - inverse fast Fourier transform (FFT) 2-782
  - Inverse Short-Time FFT block 2-827
  - Inverse Sinc Filter block 2-831
  - `isallpass` method 7-248
  - `iscascade` method 7-248
  - `isfir` method 7-248
  - `islinphase` method 7-248
  - `ismaxphase` method 7-248
  - `isminphase` method 7-248
  - `isparallel` method 7-248
  - `isreal` method 7-248
  - `isscalar` method 7-248
  - `issos` method 7-248
  - `isstable` method 7-248
- K**
- Kaiser windows 2-1798
  - Kalman Adaptive Filter block 2-841
  - Kalman Filter block 2-846
  - KalmanGain 8-112
  - KalmanGainStates 8-112
- L**
- last-input, first-output (LIFO) registers 2-1406
  - `latcallpass` 8-58
  - lattice filters
    - allpass 8-58
    - AR 8-60
    - ARMA 8-62
    - autoregressive 8-60
    - MA 8-60
    - moving average maximum phase 8-59
    - moving average minimum phase 8-60
  - `latticear` 8-60
  - `latticearma` 8-62
  - `latticeca` 8-59
  - `latticeamax` 8-59
  - `latticeamin` 8-60
  - LDL Factorization block 2-855
  - LDL Inverse block 2-863
  - LDL Solver block 2-866
  - least mean-square algorithm 2-895
  - least squares method FIR 7-818
  - Least Squares Polynomial Fit block 2-875
  - Levinson-Durbin block 2-878
  - linear algebra
    - blocks for 1-7
  - linear phase filters
    - least squares FIR 7-818
  - linear prediction
    - using Autocorrelation LPC block 2-88
  - LMS Adaptive Filter block 2-890
  - LMS algorithm
    - Block LMS Filter block 2-161
    - Fast Block LMS Filter block 2-576
    - LMS Filter block 2-895
  - LMS Filter block 2-895
  - Lowpass Filter block 2-912
  - lowpass filter designs
    - using Analog Filter Design block 2-21
  - LPC to LSP/LSF Conversion block 2-924
  - LPC to/from Cepstral Coefficients block 2-941
  - LPC to/from RC block 2-946
  - LPC/RC to Autocorrelation block 2-951
  - LSF/LSP to LPC Conversion block 2-939
  - LU Factorization block 2-954
  - LU Inverse block 2-962
  - LU Solver block 2-964

**M**

Magnitude FFT block 2-966  
 magnitude response of filters 2-21  
 magnitudes  
     converting to dB 2-371  
 matrices  
     constant diagonal 2-283  
     create diagonal 2-339  
     displaying as images 2-1001  
     extracting diagonal of 2-570  
     extracting triangle from 2-572  
     identity 2-283  
     Identity Matrix block 2-776  
     multiplying 2-980  
     multiplying within 2-981  
     normalizing 2-971  
     overwriting elements of 2-1159  
     permuting 2-1214  
     selecting elements from 2-1430  
     summing 2-993  
     Toeplitz 2-1530  
     transposing 2-1559  
 Matrix 1-Norm block 2-971  
 Matrix Concatenate block 2-977  
 Matrix Exponential block 2-978  
 Matrix Multiply block 2-980  
 matrix operations  
     blocks for 1-7  
 Matrix Product block 2-981  
 Matrix Square block 2-989  
 Matrix Sum block 2-993  
 Matrix Viewer block 2-1001  
 Maximum block 2-1008  
 Mean block 2-1027  
 Median block 2-1044  
`mfilt` object 7-1003  
`mfilt` objects 6-10  
 MIDI Controls block 2-1053  
 Minimum block 2-1060  
 minimum mean-square estimate (MMSE) 2-841

Modified Covariance AR Estimator block 2-1079  
 Modified Covariance Method block 2-1082  
 modifying signal attributes  
     blocks for 1-13  
 Multiphase Clock block 2-1087  
 multiple sections  
     specifying 8-66  
 multiplication  
     cumulative 2-341  
 multiplying  
     by dB gain 2-375  
 Multiport Selector block 2-1092  
 multirate filter functions 6-10  
 multirate filter states 8-130  
 multirate object 7-1003  
     *See also* `mfilt`

**N**

N-Sample Enable block 2-1097  
 N-Sample Switch block 2-1101  
 n-step forward linear predictors 2-88  
 NCO block 2-1106  
 negative fraction length  
     interpret 8-29  
 Normalization block 2-1122  
`nsections` method 7-249  
`nstages` method 7-249  
`nstate` method 7-249  
 Numerically Controlled Oscillator block 2-1106  
 Nyquist Filter block 2-1130

**O**

object  
     `adaptfilt` 7-2  
     changing properties 7-9 7-252  
     filter 7-241  
     `mfilt` 7-1003  
     viewing parameters 7-8

- viewing properties 7-252
- object properties
  - AccumWordLength 8-19
- Octave Filter block 2-1141
- Offset 8-112
- Offset block 2-1147
- OffsetCov 8-112
- ones
  - outputting 2-1097
- order method 7-249
- Overlap-Add FFT Filter block 2-1151
- overlap-add filter 7-387
- overlap-add method 2-1151
- Overlap-Save FFT Filter block 2-1155
- overlap-save method 2-1155
- Overwrite Values block 2-1159

## P

- Pad block 2-1176
- parallel method 7-249
- Parametric Equalizer block 2-1183
- Peak Finder block 2-1193
- Peak-Notch Filter block 2-1201
- Periodogram block 2-1208
- periodograms 2-966
- Permute Matrix block 2-1214
- PersistentMemory 8-113
- phase angles
  - unwrapping 2-1629
- phase unwrap 2-1629
- phasez method 7-249
- plots
  - zero-pole, command for 7-1285
- pole-zero plots 7-1285
- Polynomial Evaluation block 2-1219
- Polynomial Stability Test block 2-1221
- polyphase filter structures
  - FIR Interpolation block 2-630
- polyphase filters 6-10

*See also* multirate filter functions

- Power 8-112
- power spectrum estimation, using
  - Burg method 2-184
  - short-time, fast Fourier transform (ST-FFT) 2-1338
  - Yule-Walker AR method 2-1820
- precision 8-30
- prediction
  - linear 2-88
- predictor algorithm 2-841
- ProjectionOrder 8-113
- properties
  - dynamic 8-5
  - FilterStructure 8-43
  - ScaleValues 8-83
- Pseudoinverse block 2-1223
- Pulse Shaping Filter block 2-1226

## Q

- QR Factorization block 2-1233
- QR Solver block 2-1239
- quantization
  - blocks for 1-11
  - objects for 3-6
- quantized filters
  - architecture 8-43
  - direct-form FIR 8-55
  - direct-form FIR transposed 8-56
  - direct-form symmetric FIR 8-63
  - filtering data 7-640 7-642
  - finite impulse response 8-56
  - frequency response 7-843
  - lattice allpass 8-58
  - lattice AR 8-60
  - lattice ARMA 8-62
  - lattice coupled-allpass 8-58
  - lattice MA maximum phase 8-59
  - lattice MA minimum phase 8-60

- reference filter 8-63
- scaling 8-83
- specifying 8-63
- specifying coefficients for multiple sections 8-66
- structures 8-43
- symmetric FIR 8-53
- zero-pole plots 7-1285
- quantized filters properties
  - ScaleValues 8-83
- Quantizer block 2-1241
- Queue block 2-1242

## R

- ramp signal 2-287
- random signals 2-1253
- Random Source block 2-1253
- random-walk Kalman filter 2-842
- Real Cepstrum block 2-1263
- realizemdl method 7-250
- rebuffering
  - with the Buffer block 2-168
- Reciprocal Condition block 2-1265
- rectangular windows 2-1798
- recursive least-squares (RLS) algorithm 2-1284
- reference coefficients
  - specifying 8-63
- ReflectionCoeffs 8-113
- ReflectionCoeffsStep 8-113
- registers
  - first-input, first-output (FIFO) 2-1242
  - last-input, first-output (LIFO) 2-1406
- Remez exchange algorithm 2-26
- removestage method 7-250
- Repeat block 2-1273
- represent numeric data 8-29
- resampling
  - by inserting zeros 2-1637
  - Downsample block 2-524

- FIR Decimation block 2-608
- FIR Interpolation block 2-630
- FIR Rate Conversion block 2-652
  - procedure 2-652
  - Repeat block 2-1273
- ResetBeforeFiltering (PersistentMemory) 8-113
- RLS Adaptive Filter block 2-1279
- RLS Filter block 2-1284
- RMS block 2-1290
- root-mean-square (RMS)
  - computing 2-1290

## S

- Sample and Hold block 2-1299
- sample rates
  - changing 2-524
- Scalar Quantizer block 2-1302
- Scalar Quantizer Decoder block 2-1312
- Scalar Quantizer Design block 2-1317
- Scalar Quantizer Encoder block 2-1326
- scalars
  - converting to vectors 2-404
  - creating from vectors 2-1615
  - exporting 2-1570
  - importing 2-712
  - importing from the workspace 2-1344
- ScaleValues property 8-83
  - interpreting 8-84
- scaling
  - implementing for quantized filters 8-84
  - quantized filters 8-83
- second-order sections
  - normalizing 8-66
- SecondaryPathCoeffs 8-113
- SecondaryPathEstimate 8-113
- SecondaryPathStates 8-113
- selecting
  - elements of a vector 2-1677

- Selector block 2-1337
  - setstage method 7-250
  - Shift Register block
    - initial state of 2-405
  - Short-Time FFT block 2-1338
  - short-time, fast Fourier transform (ST-FFT)
    - method 2-1338
  - Signal From Workspace block 2-1344
    - compared to Simulink To Workspace block 2-1344
  - signal operations
    - blocks for 1-15
    - objects for 3-8
  - Signal To Workspace block 2-1350
  - signals
    - control 2-1562
    - random 2-1253
    - Triggered Signal From Workspace block 2-1566
  - Sine Wave block 2-1358
  - single
    - property value 8-21
  - Singular Value Decomposition block 2-1371
  - Sort block 2-1374
  - sos method 7-251
  - sound
    - From Audio Device block 2-688
    - From Wave Device block 2-705
    - From Wave File block 2-712
    - To Audio Device block 2-1534
    - To Wave Device block 2-1547
    - To Wave File block 2-1556
  - spectral analysis 2-184
    - Burg method 2-184
    - covariance method 2-335
    - magnitude FFT method 2-966
    - modified covariance method 2-1082
    - short-time FFT method 2-1338
    - Yule-Walker method 2-1820
    - See also* power spectrum estimation
  - Spectrum Scope block 2-1382
  - SqrtCov 8-113
  - SqrtInvCov 8-114
  - ss method 7-251
  - ST-FFT method 2-1338
  - Stack block 2-1406
  - stack events 2-1407
  - standard deviation
    - computing 2-1416
  - Standard Deviation block 2-1416
  - state-space forms 2-22
  - States 8-114
  - states, fixed-point filter 8-95
  - states, multirate filter 8-130
  - statistical operations
    - blocks for 1-19
    - objects for 3-11
  - statistics
    - RMS 2-1290
    - standard deviation 2-1416
    - variance 2-1683
  - StepSize 8-114
  - stepz method 7-251
  - Submatrix block 2-1430
  - SVD Solver block 2-1439
  - SwBlockLength 8-114
  - swept cosine 2-208
  - swept-frequency cosine 2-200
  - switching
    - between two inputs 2-1101
  - symmetricfir 8-63
  - sysobj method 7-251
- ## T
- Taylor windows 2-1799
  - tf method 7-252
  - Time Scope block 2-1442
  - To Audio Device block 2-1534
  - To Multimedia File block 2-1541

To Wave Device block 2-1547  
 To Wave File block 2-1556  
 Toeplitz block 2-1530  
 transforms  
   blocks for 1-20  
   discrete cosine 2-378  
   discrete wavelet 2-538  
   Fourier 2-583  
   inverse Fourier 2-782  
   objects for 3-12  
 Transpose block 2-1559  
 transposing  
   matrices 2-1559  
 trends  
   removing 2-410  
 triangular windows 2-1799  
 Triggered Delay Line block 2-1562  
 Triggered Shift Register block  
   initial state of 2-1563  
 Triggered Signal From Workspace block 2-1566  
 Triggered To Workspace block 2-1570  
 triggering, for  
   N-Sample Enable block 2-1097  
   N-Sample Switch block 2-1101  
   Sample and Hold block 2-1299  
   Triggered Shift Register block 2-1562  
   Triggered Signal From Workspace  
     block 2-1566  
   Triggered Signal To Workspace block 2-1570  
 Two-Channel Analysis Subband Filter  
   block 2-1575  
 Two-Channel Synthesis Subband Filter  
   block 2-1591

## U

UDP Receive block 2-1607  
 UDP Send block 2-1612  
 Unbuffer block 2-1615  
   initial state of 2-1616

unbuffering  
   with the Buffer block 2-168  
 Uniform Decoder block 2-1620  
 Uniform Encoder block 2-1624  
 Unwrap block 2-1629  
 unwrapping radian phase angles 2-1629  
 Upsample block 2-1637  
 upsampling  
   by inserting zeros 2-1637  
   FIR Interpolation block 2-630  
   FIR Rate Conversion block 2-652  
   Repeat block 2-1273

## V

Variable Fractional Delay block 2-1643  
   initial conditions for 2-1644  
 Variable Integer Delay block 2-1665  
   initial conditions for 2-1668  
 Variable Selector block 2-1677  
 variance 2-1683  
   tracking 2-1683  
 Variance block 2-1683  
 Vector Quantizer Decoder block 2-1702  
 Vector Quantizer Design 2-1708  
 Vector Quantizer Encoder block 2-1719  
 Vector Scope block 2-1730  
 vectors  
   converting to scalars 2-1615  
   creating from scalars 2-1562  
   exporting 2-1570  
   importing 2-712  
   importing from the workspace 2-1344

## W

Waterfall block 2-1756  
 Window Function block 2-1796  
 windows  
   applying 2-1796

- Bartlett 2-1798
  - Blackman 2-1798
  - Chebyshev 2-1798
  - Hamming 2-1798
  - Hann 2-1798
  - Kaiser 2-1798
  - rectangular 2-1798
  - Taylor 2-1799
  - triangular 2-1799
  - word length
    - about 8-29
- Y**
- Yule-Walker AR Estimator block 2-1814
  - Yule-Walker Method block 2-1820
- Z**
- Zero Crossing block 2-1825
  - zero-padding
    - Pad block 2-1176
  - zero-pole plots 7-1285
  - zerophase method 7-252
  - zeros
    - Discrete Impulse block 2-518
    - inserting 2-630
    - N-Sample Enable block 2-1097
    - Signal From Workspace block 2-1344
    - Triggered Signal From Workspace block 2-1567
  - zpk method 7-252
  - zplane 7-1285
    - plotting options 7-1285
  - zplane method 7-252