Release Notes for Econometrics Toolbox™

How to Contact MathWorks



www.mathworks.com

comp.soft-sys.matlab

www.mathworks.com/contact TS.html Technical Support

Web

Newsgroup



suggest@mathworks.com bugs@mathworks.com

doc@mathworks.com

service@mathworks.com info@mathworks.com

Product enhancement suggestions

Bug reports

Documentation error reports

Order status, license renewals, passcodes Sales, pricing, and general information



508-647-7000 (Phone)



508-647-7001 (Fax)



The MathWorks, Inc. 3 Apple Hill Drive Natick. MA 01760-2098

For contact information about worldwide offices, see the MathWorks Web site.

Release Notes for Econometrics ToolboxTM

© COPYRIGHT 2005–2012 by The MathWorks, Inc.

The software described in this document is furnished under a license agreement. The software may be used or copied only under the terms of the license agreement. No part of this manual may be photocopied or reproduced in any form without prior written consent from The MathWorks, Inc.

FEDERAL ACQUISITION: This provision applies to all acquisitions of the Program and Documentation by, for, or through the federal government of the United States. By accepting delivery of the Program or Documentation, the government hereby agrees that this software or documentation qualifies as commercial computer software or commercial computer software documentation as such terms are used or defined in FAR 12.212, DFARS Part 227.72, and DFARS 252.227-7014. Accordingly, the terms and conditions of this Agreement and only those rights specified in this Agreement, shall pertain to and govern the use, modification, reproduction, release, performance, display, and disclosure of the Program and Documentation by the federal government (or other entity acquiring for or through the federal government) and shall supersede any conflicting contractual terms or conditions. If this License fails to meet the government's needs or is inconsistent in any respect with federal procurement law, the government agrees to return the Program and Documentation, unused, to The MathWorks, Inc.

Trademarks

MATLAB and Simulink are registered trademarks of The MathWorks, Inc. See www.mathworks.com/trademarks for a list of additional trademarks. Other product or brand names may be trademarks or registered trademarks of their respective holders.

Patents

MathWorks products are protected by one or more U.S. patents. Please see www.mathworks.com/patents for more information.

Contents

	R2012b)
Impulse response (dynamic multipliers) for ARIMA	c	
models	2	1
conditional variance models	3	\$
A series of new examples on time-series regression techniques	4	Į
	_	
	R2012a	Ĺ
New Model Objects and Their Functions	6	;
New Utility Functions		
Demo for Static Time Series Model Specification New Data Sets		
	R2011b	<u>)</u>
Warning and Error ID Changes	12	2
	R2011a	Ī
New Cointegration Functionality	14	Į
Convert Vector Autoregressive Models to and from Vect		
Error-Correction Models		

	R	<u> 2010b</u>
Ade	nctions Being Removed	. 20
	R	2010a
	nctions Being Removed	. 24
	Economy	
-	g Operator Polynomial Objects	
	ybourne-McCabe Test for Stationarity	
	storical Data Sets for Calibrating Economic Models	
Ne	w Organization and Naming Standard for Data Sets w Naming Convention for Demos and Example	
	Functions	. 31
Fin	it Root Tests	. 35
	R	2009a
	pothesis Tests	
	w Demo	
	R2	2008b
Mu	ultivariate VAR, VARX, and VARMA Models	42

Heston Stochastic Volatility Models	•••	43
	R20	08a
Monte Carlo Simulation of Stochastic Differential Equations		46
	R20	07b
Changes to garchsim	•••	48
	R20	07a
No New Features or Changes		
	R20	06b
Data Preprocessing		$\frac{52}{53}$
	R20	06a
User's Guide		56 57
	R14	${ m SP3}$
Changes to garchsim		60

R2012b

Version: 2.2

New Features: Yes Bug Fixes: No

Impulse response (dynamic multipliers) for ARIMA models

The arima model object has a new impulse method for generating and plotting impulse response functions for ARIMA models.

Filter user-specified disturbances through ARIMA and conditional variance models

There are new methods to filter user-specified disturbances through ARIMA and conditional variance models:

- filter for arima model objects to filter disturbances through an ARIMA process.
- filter for garch model objects to filter disturbances through a GARCH process.
- filter for egarch model objects to filter disturbances through an EGARCH process.
- filter for gjr model objects to filter disturbances through a GJR process.

A series of new examples on time-series regression techniques

Eight new examples that illustrate common principles and tasks in time-series regression modeling:

- Time Series Regression I: Linear Models
- Time Series Regression II: Collinearity and Estimator Variance
- Time Series Regression III: Influential Observations
- Time Series Regression IV: Spurious Regression
- Time Series Regression V: Predictor Selection
- Time Series Regression VI: Residual Diagnostics
- Time Series Regression VII: Forecasting
- Time Series Regression VIII: Lagged Variables and OLS Estimator Bias

R2012a

Version: 2.1

New Features: Yes Bug Fixes: No

New Model Objects and Their Functions

Econometrics Toolbox[™] has four new model objects for modeling univariate time series data.

- The arima model object supports ARIMA processes, including AR, MA, ARMA, and seasonal models.
- For modeling conditionally heteroscedastic series, there are new garch, egarch, and gjr model objects, supporting GARCH models and the EGARCH and GJR variants.

Five new functions for each model object simplify the modeling workflow: estimate, infer, forecast, print, and simulate.

New Utility Functions

Four new utility functions assist in time series analysis:

- corrplot plots predictor correlations.
- collintest performs Belsley collinearity diagnostics.
- i10test conducts paired integration and stationarity tests.
- recessionplot adds recession bands to time series plots.

Demo for Static Time Series Model Specification

A new demo, "Specifying Static Time Series Models," steps through the model specification workflow for static multiple linear regression models.

Steps include:

- Detecting multicollinearity
- Identifying influential observations
- Testing for spurious regression due to integrated data
- Selecting predictor subsets using stepwise regression and lasso
- Conducting residual diagnostics
- Forecasting

The demo uses many tools from Econometrics Toolbox, and introduces new utility functions useful for model specification.

To run the demo in the Command Window, use the command ${\tt showdemo}$ ${\tt Demo_StaticModels}.$

New Data Sets

Econometrics Toolbox includes two new data sets:

- Data_CreditDefaults. Historical data on investment-grade corporate bond defaults and four predictors, 1984–2004. Data are those used in: Loeffler, G., and P. N. Posch. *Credit Risk Modeling Using Excel and VBA*. West Sussex, England: Wiley Finance, 2007.
- Data_Recessions. U.S. recession start and end dates from 1857 to 2011. Source: National Bureau of Economic Research. "U.S. Business Cycle Expansions and Contractions." http://www.nber.org/cycles.html.

R2011b

Version: 2.0.1 New Features: Yes Bug Fixes: No

Warning and Error ID Changes Compatibility Considerations: Yes

Many warning and error IDs have changed from their previous versions. These warnings or errors typically appear during a function call.

Compatibility Considerations

If you use warning or error IDs, you might need to change the strings you use. For example, if you turned off a warning for a certain ID, the warning might now appear under a different ID. If you use a try/catch statement in your code, replace the old identifier with the new identifier. There is no definitive list of the differences, or of the IDs that changed.

R2011a

Version: 2.0

New Features: Yes Bug Fixes: No

New Cointegration Functionality

Econometrics Toolbox now offers functions for cointegration testing and modeling. The egcitest function uses Engle-Granger methods to test for individual cointegrating relationships, and estimates their parameters. The jcitest function uses Johansen methods to test for multiple cointegrating relationships, and estimates parameters in corresponding vector error-correction models. The jcontest function tests linear restrictions on both error-correction speeds and the space of cointegrating vectors, and estimates restricted model parameters.

Convert Vector Autoregressive Models to and from Vector Error-Correction Models

The functions vectovar and vartovec allow you to convert between vector autoregressive (VAR) models and vector error-correction (VEC) models.

Data Sets for Calibrating Economic Models

Econometrics Toolbox includes three new data sets:

- Data_Canada. Mackinnon's data on inflation and interest rates in Canada, 1954–1994. Data are those used in: MacKinnon, J. G. "Numerical Distribution Functions for Unit Root and Cointegration Tests." *Journal of Applied Econometrics*. v. 11, 1996, pp. 601–618.
- Data_JDanish, Data_JAustralian. Johansen's data on money and income in Denmark, 1974–1987, and Australia/U.S. purchasing power and interest parity, 1972–1991. Data are those used in: Johansen, Likelihood-Based Inference in Cointegrated Vector Autoregressive Models. Oxford: Oxford University Press, 1995.

R2010b

Version: 1.4

New Features: Yes Bug Fixes: No

Functions Being Removed Compatibility Considerations: Yes

Function Name	What Happens When You Use This Function?	Use This Function Instead	Compatibility Considerations
dfARDTest	Error	adftest	The new function syntax differs. Replace all existing instances of dfARDTest with the correct adftest syntax.
dfARTest	Error	adftest	The new function syntax differs. Replace all existing instances of dfARTest with the correct adftest syntax.
dfTSTest	Error	adftest	The new function syntax differs. Replace all existing instances of dfTSTest with the correct adftest syntax.
ppARDTest	Error	pptest	The new function syntax differs. Replace all existing instances of ppARDTest with the correct pptest syntax.

Function Name	What Happens When You Use This Function?	Use This Function Instead	Compatibility Considerations
ppARTest	Error	pptest	The new function syntax differs. Replace all existing instances of ppARTest with the correct pptest syntax.
ppTSTest	Error	pptest	The new function syntax differs. Replace all existing instances of ppTSTest with the correct pptest syntax.

Additional Syntax Options for archtest and lbqtest

The functions archtest and lbqtest now take name-value pair arguments as inputs. The old syntax of individual arguments will continue to work but will not be documented.

New Data Set for Calibrating Economic Models

The economic data from the paper by Nielsen and Risager, "Stock Returns and Bond Yields in Denmark, 1922–99," (Department of Economics, Copenhagen Business School; Working paper 3-2001, 2001) is now included with Econometrics Toolbox in the file Data Danish.

R2010a

Version: 1.3

New Features: Yes Bug Fixes: No

Functions Being Removed Compatibility Considerations: Yes

Function Name	What Happens When You Use This Function?	Use This Function Instead	Compatibility Considerations
dfARDTest	Error	adftest	The new function syntax differs. Replace all existing instances of dfARDTest with the correct adftest syntax.
dfARTest	Error	adftest	The new function syntax differs. Replace all existing instances of dfARTest with the correct adftest syntax.
dfTSTest	Error	adftest	The new function syntax differs. Replace all existing instances of dfTSTest with the correct adftest syntax.
ppARDTest	Error	pptest	The new function syntax differs. Replace all existing instances of ppARDTest with the correct pptest syntax.

Function Name	What Happens When You Use This Function?	Use This Function Instead	Compatibility Considerations
ppARTest	Error	pptest	The new function syntax differs. Replace all existing instances of ppARTest with the correct pptest syntax.
ppTSTest	Error	pptest	The new function syntax differs. Replace all existing instances of ppTSTest with the correct pptest syntax.

Demo Showing Multivariate Modeling of the U.S. Economy

A new demo, "Modeling the United States Economy," develops a small macroeconomic model. This model is used to examine the impact of various shocks on the United States economy, particularly around the period of the 2008 fiscal crisis. It uses the multiple time series tools from the Econometrics Toolbox.

To run the demo in the command window, use the command echodemo Demo USEconModel.

Lag Operator Polynomial Objects

The new LagOp polynomial class provides methods to create and manipulate lag operator polynomials and filter time series data, as well as methods to perform polynomial algebra including addition, subtraction, multiplication, and division.

Leybourne-McCabe Test for Stationarity

The new Leybourne-McCabe test function 1mctest assesses the null hypothesis that a univariate time series y is a trend-stationary AR(p) process against the alternative that y is a nonstationary ARIMA(p,1,1) process.

Historical Data Sets for Calibrating Economic Models

The new data set Data_SchwertMacro contains original data from G. William Schwert's article "Effects of Model Specification on Tests for Unit Roots in Macroeconomic Data," (*Journal of Monetary Economics*, Vol. 20, 1987, pp. 73–103.). These data are a benchmark for unit root tests. The new data set Data_SchwertStock contains indices of U.S. stock prices as published in G. William Schwert's article "Indexes of U.S. Stock Prices from 1802 to 1987," (*The Journal of Business*, Vol. 63, 1990, pp. 399–42.). The new data set Data_USEconModelcontains the macroeconomic series for the new demo Demo USEconModel.

New Organization and Naming Standard for Data Sets

Compatibility Considerations: Yes

Econometrics Toolbox has a new set of naming conventions for data sets. Data set names are prefixed by Data_.

For full information on the available data sets, demos, and examples, see Data Sets, Demos, and Example Functions or type help econ/econdemos at the command line. For more information on Dataset Array objects, see dataset in the Statistics ToolboxTM documentation.

Compatibility Considerations

Replace any instances of load Old_Data with load and the new file name.

New Naming Convention for Demos and Example Functions

Compatibility Considerations: Yes

All demos and examples in the Econometrics Toolbox have been moved to the folder econ/econdemos and renamed according to the following convention:

- Demos are named Demo DemoName
- Examples are named Example ExampleName

Compatibility Considerations

Replace any instances of example functions with their new names. For full information on the available, demos, and examples, see Data Sets, Demos, and Example Functions or type help econ/econdemos at the command line.

R2009b

Version: 1.2

Unit Root Tests Compatibility Considerations: Yes

There are now four classes of unit root tests. More information on the tests is available in the Unit Root Nonstationarity section of the User's Guide.

Dickey-Fuller and Phillips-Perron Tests

Dickey-Fuller and Phillips-Perron tests now have single interfaces, with new capabilities for multiple testing. Both adftest and pptest test a unit root null hypothesis against autoregressive, autoregressive with drift, or trend-stationary alternatives.

KPSS Test

The new kpsstest function tests a null hypothesis of (trend) stationarity against nonstationary unit root alternatives.

Variance Ratio Test

The new vratiotest function tests a null hypothesis of a random walk against alternatives with innovations that are not independent and identically distributed.

Compatibility Considerations

The ardtest function replaces the dfARDTest, dfARTest, and dfTSTest functions. The pptest function replaces the ppARDTest, ppARTest, and ppTSTest functions. The new function syntax differs from the functions they replace.

Financial Toolbox Required

Econometrics Toolbox requires Financial Toolbox $^{\text{TM}}$ as of this version.

Nelson-Plosser Data

The Nelson and Plosser [50] data set is now available. To access the data, enter load Data_NelsonPlosser at the MATLAB $^{\! (8)}$ command line.

R2009a

Version: 1.1

Hypothesis Tests Compatibility Considerations: Yes

There are two new hypothesis tests for model misspecification:

- Lagrange Multiplier tests, 1mtest
- Wald tests, waldtest

Furthermore, the likelihood ratio test, lratiotest, has been enhanced to be able to "test up" as well as "test down" when performing multiple model comparisons. It now accepts vectors of model parameters for restricted log likelihoods, for unrestricted log likelihoods, or for both.

There is a new demo about these tests; see "New Demo" on page 40.

Compatibility Considerations

1ratiotest error messages and message IDs differ from previous versions.

Structural VAR, VARX, and VARMAX models Compatibility Considerations: Yes

Econometrics Toolbox multiple time series functions now include structural multiple time series. Structural models have the general form

$$A_0Y_t = a + X_tb + \sum_{i=1}^p A_iY_{t-i} + \sum_{j=1}^q B_jW_{t-j} + B_0W_t.$$

Previously, Econometrics Toolbox multiple time series functions addressed models of the form

$$Y_t = a + X_t b + \sum_{i=1}^{p} A_i Y_{t-i} + \sum_{j=1}^{q} B_i W_{t-j} + W_t.$$

The mathematical difference is the inclusion of A_0 and B_0 matrices. These matrices allow practitioners to specify structural dependencies between variables. For more information, see the Multivariate Time Series Models chapter of the Econometrics Toolbox User's Guide.

Compatibility Considerations

Objects created with the Econometrics Toolbox V1.0 vgxset function, and saved in MAT files, do not work with Econometrics Toolbox V1.1 functions. Recreate the objects with the Econometrics Toolbox V1.1 vgxset function.

New Demo

There is a new demo on hypothesis tests. Run the demo at the MATLAB command line by entering showdemo classicalTestsDemo.

R2008b

Version: 1.0

Multivariate VAR, VARX, and VARMA Models

A new suite of functions, listed in the following table, adds support for multivariate VAR, VARX, and VARMA models.

Function	Description
vgxar	Convert VARMA specification into a pure vector autoregressive (VAR) model
vgxcount	Count restricted and unrestricted parameters in VAR or VARX models
vgxdisp	Display VGX model parameters and standard errors in different formats
vgxget	Get multivariate time-series specification parameters
vgxinfer	Infer innovations of a VGX process
vgxloglik	Compute conditional log-likelihoods of VGX process
vgxma	Convert VARMA specification into a pure vector moving average (VMA) model
vgxplot	Plot multivariate time series process
vgxpred	Generate transient response of VGX process during a specified forecast period
vgxproc	Generate a VGX process from an innovations process
vgxqual	Determine if a VGX process is stable and invertible
vgxset	Set or modify multivariate time-series specification parameters
vgxsim	Simulate VGX processes
vgxvarx	Solve VAR or VARX model using maximum likelihood estimation

Heston Stochastic Volatility Models

The new heston function adds support for Heston stochastic volatility models to the SDE engine.

R2008a

Version: 2.4

Monte Carlo Simulation of Stochastic Differential Equations

The GARCH ToolboxTM software now allows you to model dependent financial and economic variables, such as interest rates and equity prices, via Monte Carlo simulation of multivariate diffusion processes. For more information, see Stochastic Differential Equations in the GARCH Toolbox documentation.

R2007b

Version: 2.3.2 New Features: Yes Bug Fixes: No

Changes to garchsim

The garchsim function previously allowed you to specify the State argument as either a scalar or a time series matrix of standardized, independent, identically distributed disturbances to drive the output Innovations in a time series process. The State argument must now be a time series matrix. See the State input argument on the garchsim reference page for more information.

R2007a

Version: 2.3.1 New Features: No Bug Fixes: No

No New Features or Changes

R2006b

Version: 2.3

Data Preprocessing

A new Hodrick-Prescott filter, hpfilter, separates time series into trend and cyclical components

Demos

A new demo uses the hpfilter function to reproduce the results in Hodrick and Prescott's original paper on U.S. business cycles

R2006a

Version: 2.2

User's Guide

A new chapter in the *GARCH Toolbox User's Guide* explains how to conduct Dickey-Fuller and Phillips-Perron unit root tests with the new statistical functions in the toolbox.

Statistical Functions

Version 2.2 of the GARCH Toolbox software has six new functions. All of them support the ability to conduct univariate unit root tests on time series data. Three functions support augmented Dickey-Fuller unit root tests. The remaining three support Phillips-Perron unit root tests.

Dickey-Fuller Unit Root Tests

Function	Purpose
dfARDTest	Augmented Dickey-Fuller unit root test based on AR model with drift.
dfARTest	Augmented Dickey-Fuller unit root test based on zero drift AR model.
dfTSTest	Augmented Dickey-Fuller unit root test based on trend stationary AR model.

Phillips-Perron Unit Root Tests

Function	Purpose
ppARDTest	Phillips-Perron unit root test based on AR(1) model with drift.
ppARTest	Phillips-Perron unit root test based on zero drift $AR(1)$ model.
ppTSTest	Phillips-Perron unit root test based on trend stationary AR(1) model.

R14SP3

Version: 2.1

Changes to garchsim Compatibility Considerations: Yes

A change introduced in V2.1 of the GARCH Toolbox software concerns user-specified noise processes. The garchsim function now allows you to provide a time series matrix of standardized, i.i.d. disturbances to drive the output Innovations in a time series process. In previous versions, you could only provide a state that was used to generate a random noise process. See the State input argument on the garchsim reference page for more information.

Compatibility Considerations

garchsim argument Is renamed. In V2.1, the garchsim argument Seed is renamed to State for consistency with the MATLAB rand and randn functions. The name change, in itself, introduces no backward incompatibilities. The following topic explains a related change.

garchsim defaults to current random number generator state. In V2.0.1 of the GARCH Toolbox software, thegarchsim function used the initial random number generator state, 0, if you did not specify a value for the Seed argument. The Seed argument corresponded to the rand and random state value.

In V2.1, if you do not specify a value for the State (formerly Seed) argument, garchsim uses the current state of rand and randn, rather than the initial state. Use the commands s = rand('state') and s = randn('state') to determine the current state of these random number generators. For more information, see the rand and randn reference pages.