

Release Notes for Simulink[®] Control Design[™]

How to Contact MathWorks



www.mathworks.com Web
comp.soft-sys.matlab Newsgroup
www.mathworks.com/contact_TS.html Technical Support



suggest@mathworks.com Product enhancement suggestions
bugs@mathworks.com Bug reports
doc@mathworks.com Documentation error reports
service@mathworks.com Order status, license renewals, passcodes
info@mathworks.com Sales, pricing, and general information



508-647-7000 (Phone)



508-647-7001 (Fax)



The MathWorks, Inc.
3 Apple Hill Drive
Natick, MA 01760-2098

For contact information about worldwide offices, see the MathWorks Web site.

Release Notes for Simulink® Control Design™

© COPYRIGHT 2004–2012 by The MathWorks, Inc.

The software described in this document is furnished under a license agreement. The software may be used or copied only under the terms of the license agreement. No part of this manual may be photocopied or reproduced in any form without prior written consent from The MathWorks, Inc.

FEDERAL ACQUISITION: This provision applies to all acquisitions of the Program and Documentation by, for, or through the federal government of the United States. By accepting delivery of the Program or Documentation, the government hereby agrees that this software or documentation qualifies as commercial computer software or commercial computer software documentation as such terms are used or defined in FAR 12.212, DFARS Part 227.72, and DFARS 252.227-7014. Accordingly, the terms and conditions of this Agreement and only those rights specified in this Agreement, shall pertain to and govern the use, modification, reproduction, release, performance, display, and disclosure of the Program and Documentation by the federal government (or other entity acquiring for or through the federal government) and shall supersede any conflicting contractual terms or conditions. If this License fails to meet the government's needs or is inconsistent in any respect with federal procurement law, the government agrees to return the Program and Documentation, unused, to The MathWorks, Inc.

Trademarks

MATLAB and Simulink are registered trademarks of The MathWorks, Inc. See www.mathworks.com/trademarks for a list of additional trademarks. Other product or brand names may be trademarks or registered trademarks of their respective holders.

Patents

MathWorks products are protected by one or more U.S. patents. Please see www.mathworks.com/patents for more information.

R2012b

MATLAB code generation from Linear Analysis Tool for batch estimation of model frequency responses	2
Operating point calculation (trimming) from multiple specifications with only one model compilation	3
Export and import operating point specifications in Linear Analysis Tool	4
MATLAB script or function generation from Linear Analysis Tool for repeated or batch linearization	5
Print plots to MATLAB figure in Linear Analysis Tool ...	6
Commands for setting and querying rate conversion methods in tunable blocks	7
“Ignore saturation when linearizing” checked by default in PID Controller and PID Controller (2DOF) blocks	8
showBlockValue renamed to showTunable	9

R2012a

Create Linearization Input/Output Sets in the Linear Analysis Tool	12
Specify Feedback Sign for getLoopTransfer Without Specifying Loop Openings	13

R2011b

Redesigned Graphical Tool for Improved Linear Analysis Workflows	16
Interactive Frequency Response Estimation and Validation of Linearization Results	17
Optimization of Model Parameters to Meet Design Requirements Specified by Model Verification Blocks ..	18
Automatic Tuning of PID Controller Blocks in a Referenced Model	19

Control System Tuning for Simulink Models with looptune or hinfstruct Using slTunable Interface	20
Change in Default Number of Samples in frest.Chirp	21

R2011a

Ability to Select Individual Bus Elements as Linearization Input and Output Points	24
Enhanced LINLFT Command Optionally Returns Linearization of Excluded Blocks	25
Access to Current Linearization of a Simulink Block for Specifying Custom Linearization	26
Enhanced PID Controller Blocks Display Compensator Formula in Block Dialog Box	27

R2010b

New Blocks for Plotting and Verifying Linear System Characteristics of Simulink Models	30
New Tools for Identifying Time-Varying Source Blocks for Frequency Response Estimation	32
Tuning Tools Update Workspace Variables That Define Parameters of Tuned Blocks	33
Enhanced PID Tuner Including New Response Plots	34
New Demo Illustrating Control Design for a Plant That Has Parameter Variations	35

R2010a

New Parallel Computing Support For Frequency Response Estimation	38
New Commands Support Recomputing Frequency Response Estimation Results at Specific Frequencies	39
New frest.simcompare Output Argument Returns Simulation Output Data From Linear System	40

New Options in Simulink Results Viewer GUI for Viewing Frequency Response Estimation Results	41
New Option for Labeling Bus Signal I/O Names in the SISO Design Task	42
Existing Simulink Blocks Now Have Analytic Jacobians ..	43
Change in Format of Time Series in frestimate Output ...	44

R2009b

New GUI for Tuning New PID Controller Blocks	46
New Automated PID Tuning Algorithm	47
Ability to Compute Frequency Response of Simulink Models	48
Ability to Specify the Linearization of Simulink Blocks ...	49
Ability to Design Compensators for Plant Models With Time Delays	50
New Commands to More Efficiently Compute Multiple Linearizations	51
Ability to Set Default Plot Type for Linear Analysis Results from GUI	52

R2009a

Ability to Generate MATLAB Code from the GUI for Creating Operating Points and Linearizing Models	54
Ability to Tune Additional Blocks	55
New Option for Labeling Bus Signal I/O Names in Linearization Results	56

R2008b

New Upsampling Option for Rate Conversion When Linearizing Simulink Models	58
Ability to Specify State Order of Linearized Models from the Command Line	59

Ability to Filter the Linearization Inspector to Show Blocks in the Linearization Path	60
Ability to Disable the Calculation of Linearization Diagnostics and Inspector Data in the GUI	61

R2008a

New Diagnostic Messages Help You Troubleshoot Linearization Results	64
Ability to Find Operating Points for Simscape Models	65
Updated Error and Warning Message System	66

R2007b

Ability to Linearize Models with Model-Reference Blocks by Any Linearization Method	68
Ability to Design Compensators for Models Containing Model-Reference Blocks	69
Ability to Generate Linearized Models with Exact Time-Delay Representations	70
Ability to Linearize Periodic Function-Call Subsystems ..	71

R2007a

Ability to Linearize Using an Operating Point Specified Directly in a Model	74
Ability to Capture Linearization Snapshots in GUI	75
Ability to Perform Control Design at Snapshots in GUI ..	76
Ability to Retrieve Stored Compensator Designs	77

R2006b

R2006a

Compensator Design in Simulink Is Now Supported	82
---	----

R14SP3

Control and Estimation Tools Manager Enhanced	84
Support for Operating Point Search and Linearization of Models with Model Reference Blocks	85

R14SP2

Context-Sensitive Help Added	88
View Linearizations in the Control and Estimation Tools Manager	89
Discretization Methods Added	90
List of Blocks with Preprogrammed Analytic Jacobians Added	91
Block Name Readability Improved	92

R2012b

Version: 3.6
New Features: Yes
Bug Fixes: Yes

MATLAB code generation from Linear Analysis Tool for batch estimation of model frequency responses

You can now generate MATLAB® code for frequency response estimation from the Linear Analysis Tool. You can generate either a MATLAB script or a MATLAB function. Generated MATLAB scripts are useful when you want to programmatically reproduce a result you obtained interactively. A generated MATLAB function allows you to perform multiple estimations with systematic variations in estimation parameters such as operating point (batch estimation).

For more information, see “Generate MATLAB Code for Repeated or Batch Frequency Response Estimation”.

Operating point calculation (trimming) from multiple specifications with only one model compilation

The `findop` command now can find operating points for multiple operating point specifications with a single model compilation. This feature allows you to find multiple trimmed operating points without the overhead of compiling the model for each trimming computation. For an example, see “Batch Compute Operating Points with Single Model Compilation”.

For more information about operating point calculation and operating point specifications, see the `findop` and `operspec` reference pages.

Export and import operating point specifications in Linear Analysis Tool

When you modify an operating point specification in the Linear Analysis Tool, you can now export the specification to the MATLAB workspace. Exported specifications are saved as operating point specifications objects (see `operspec`). Exporting specifications can be useful when you expect to perform multiple trimming operations using the same or a very similar set of specifications. Additionally, you can export interactively-edited operating point specifications when you want to use the `findop` command to perform multiple trimming operations with a single compilation of the model (see “Operating point calculation (trimming) from multiple specifications with only one model compilation” on page 3).

You can also import saved operating point specifications to the Linear Analysis Tool and use them to interactively compute trimmed operating points. Importing a specification can be useful when you want to trim a model to a specification that is similar to one you previously saved. In that case, you can import the specification to the Linear Analysis Tool and interactively change it. You can then export the modified specification, or compute a trimmed operating from it.

For more information, see “Import and Export Specifications For Operating Point Search”.

For more information about operating point specifications, see the `operspec` and `findop` reference pages.

MATLAB script or function generation from Linear Analysis Tool for repeated or batch linearization

When you generate MATLAB code for linearization from the Linear Analysis Tool, you now have a choice of generating a script that uses the current linearization parameters, or a function that takes parameter values as input. Previously, you could only generate a MATLAB function with no input parameters.

Generated MATLAB scripts are useful when you want to programmatically reproduce a result you obtained interactively. A generated MATLAB function allows you to perform multiple linearizations with systematic variations in linearization parameters such as operating point (batch linearization).

For more information, see “Generate MATLAB Code for Repeated or Batch Linearization”.

Print plots to MATLAB figure in Linear Analysis Tool

You can now export a plot from the Linear Analysis Tool to a MATLAB figure window.

For more information, see “Print Plot to MATLAB Figure in Linear Analysis Tool”.

Commands for setting and querying rate conversion methods in tunable blocks

New commands allow you to query and specify the rate conversion method that the `sITunable` interface uses for converting the sampling time of the parametrization of tunable blocks in a Simulink® model.

- `sITunable.getBlockRateConversion` — Query rate conversion method of tunable block
- `sITunable.setBlockRateConversion` — Set rate conversion method of tunable block

These commands are useful, for example, when you use the `sITunable` interface to tune a mixed-rate Simulink model, such as a model having a discrete-time controller and a continuous-time plant. The `sITunable` interface automatically converts the sampling times of tunable blocks where necessary. Using `sITunable.setBlockRateConversion`, you can control the conversion method that the `sITunable` interface uses.

For more information, see:

- “Tuning of a Digital Motion Control System”
- `sITunable.getBlockRateConversion` and `sITunable.setBlockRateConversion` reference pages

“Ignore saturation when linearizing” checked by default in PID Controller and PID Controller (2DOF) blocks

The default linearization behavior of the PID Controller and PID Controller (2DOF) blocks now forces linearization commands to ignore block output limits. Ignoring output limits allows you to linearize a model around an operating point even if that operating point causes the PID Controller block to exceed the output limits.

To cause linearization commands not to ignore block output limits, clear the **Ignore saturation when linearizing** checkbox in the block dialog box, PID Advanced tab.

showBlockValue renamed to showTunable

Compatibility Considerations: Yes

The command `showBlockValue` is now called `showTunable`. Use `showTunable` to obtain the current value of block parametrizations from an `sITunable` interface.

Compatibility Considerations

Replace instances of `showBlockValue` in your code with `showTunable`.

R2012a

Version: 3.5
New Features: Yes
Bug Fixes: Yes

Create Linearization Input/Output Sets in the Linear Analysis Tool

You can now interactively create I/O sets for linearization or frequency response estimation in the Linear Analysis Tool, without adding linearization points to your model. Previously, you had to modify your model to interactively create I/O sets.

For more information, see [Create Linearization I/O Sets In Linear Analysis Tool](#).

For more information about using the Linear Analysis Tool, see [Linearize at Model Operating Point and Estimating Frequency Response](#).

Specify Feedback Sign for getLoopTransfer Without Specifying Loop Openings

An additional syntax for `sITunable.getLoopTransfer` allows you to specify the feedback sign without having to provide an `openings` argument. Use the syntax

```
L = getLoopTransfer(ST,location,sign)
```

to calculate the point-to-point open-loop transfer function at `location` of the Simulink model described by the `sITunable` interface `ST`. The software uses the sign convention specified by `sign` (+1 or -1) to compute `L`.

Previously, to specify a feedback sign, you had to use the syntax

```
L = getLoopTransfer(ST,location,openings,sign)
```

This syntax required you to specify an `openings` argument to specify `sign`. The new syntax allows you to specify `sign` while using the default loop openings.

For more information, see the `sITunable` and `sITunable.getLoopTransfer` reference pages.

R2011b

Version: 3.4
New Features: Yes
Bug Fixes: Yes

Redesigned Graphical Tool for Improved Linear Analysis Workflows

The new interactive Linear Analysis Tool streamlines workflows for linear analysis tasks such as finding steady-state operating points (trimming) and linearization.

To access the Linear Analysis Tool:

- 1** Open a Simulink model.
- 2** In the Simulink model, select **Tools > Control Design > Linear Analysis**.

For more information about using the Linear Analysis Tool for operating-point and linearization workflows, see:

- Steady-State Operating Points
- Linearization

Interactive Frequency Response Estimation and Validation of Linearization Results

The new interactive Linear Analysis Tool provides a graphical interface for frequency response estimation.

To access the Linear Analysis Tool:

- 1** Open a Simulink model.
- 2** In the Simulink model, select **Tools > Control Design > Linear Analysis** to launch the Linear Analysis tool.
- 3** Click the Frequency Response Estimation tab to begin an estimation task.

For more information about using the Linear Analysis Tool for frequency response estimation, see [Frequency Response Estimation](#).

Optimization of Model Parameters to Meet Design Requirements Specified by Model Verification Blocks

If you have Simulink Design Optimization™ software, you can optimize the Simulink model to meet frequency-domain requirements specified in Model Verification blocks. For example, you can optimize the linear system to meet Bode magnitude or gain and phase margin requirements. For more information, see [Design Optimization To Meet Frequency-Domain Requirements \(GUI\)](#).

You can also include time-domain requirements such as step response characteristics for optimization. For more information, see [Design Optimization to Meet Time- and Frequency-Domain Requirements](#).

Automatic Tuning of PID Controller Blocks in a Referenced Model

You can now use the PID Tuner to tune a PID Controller block in a model that is referenced in one or more open models. When you launch the PID Tuner from a block within a model reference, the software prompts you to select which of the open models is the top-level model for analysis and tuning. Previously, the PID Tuner could only use the model containing the PID Controller block as the top-level model.

For more information, see [Tuning a PID Controller Within a Model Reference](#).

Control System Tuning for Simulink Models with looptune or hinfstruct Using sITunable Interface

If you have Robust Control Toolbox™ software, you can use tuning commands, such as `sITunable.looptune` and `hinfstruct`, to tune control systems modeled in Simulink. The `sITunable` object provides an interface between your Simulink model and these commands.

Use `sITunable` to specify information about your control structure and parametrization. `sITunable` also automates tasks such as linearizing the Simulink model, parametrizing the tunable blocks of your system, and applying tuned parameter values to the model. After you create and configure an `sITunable` object for your control architecture, you can tune the control system using `sITunable.looptune` or `hinfstruct`.

For more information, see [Tuning Fixed Control Architectures](#) in the Robust Control Toolbox documentation.

Change in Default Number of Samples in `frest.Chirp`

Compatibility Considerations: Yes

The default number of samples (`NumSamples`) in a `frest.Chirp` input signal for frequency response estimation is now given by the formula:

$$\frac{4\pi}{T_s * \min(\text{FreqRange})}$$

`Ts` is the sampling time of the chirp signal. `FreqRange` is the vector of signal frequencies of the chirp signal.

This formula returns twice the value returned in previous releases.

For example, if you create a default chirp input signal with the command

```
input = frest.Chirp
```

the value of `input.NumSamples` is 10000, instead of the previous value of 5000.

For more information, see the `frest.Chirp` reference page.

Compatibility Considerations

If you have scripts that rely on the default `NumSamples` formula, modify your scripts to account for the new value.

R2011a

Version: 3.3
New Features: Yes
Bug Fixes: Yes

Ability to Select Individual Bus Elements as Linearization Input and Output Points

Instead of selecting an entire bus, you can now select individual elements of the bus signal as linearization inputs or outputs (I/Os). By selecting individual bus elements, you can:

- Obtain the linearization only for the channels of interest.
- Specify multiple I/Os, possibly as different types, in the same bus.

Select individual bus elements as I/Os when you want to:

- Linearize a Simulink model using the GUI or programmatically.
- Visualize time- and frequency-domain response during simulation using the Linear Analysis Plots blocks.
- Verify frequency-domain characteristics using the Model Verification blocks.

For more information, see [Select Individual Bus Elements as Linearization Points](#) and the `linio` reference page.

Enhanced LINLFT Command Optionally Returns Linearization of Excluded Blocks

A new optional output argument to `linlft` returns the linearization of blocks you specify for exclusion from the linearized model.

For more information, see the `linlft` reference page.

Access to Current Linearization of a Simulink Block for Specifying Custom Linearization

When you use a specification function to specify a custom linearization of a Simulink block, you can now access the current linearization in your function. The current linearization is stored in the new `BlockLinearization` field of the `BlockData` structure. The software automatically creates the `BlockData` structure and passes it to your block linearization specification function.

For more information and an example showing how to use the `BlockLinearization` field of `BlockData`, see [Augmenting the Linearization of a Block](#).

Enhanced PID Controller Blocks Display Compensator Formula in Block Dialog Box

The PID Controller and PID Controller (2DOF) blocks now display the current compensator formula in the block dialog box. This display reflects the current settings for controller type, controller form, and time domain.

R2010b

Version: 3.2
New Features: Yes
Bug Fixes: Yes

New Blocks for Plotting and Verifying Linear System Characteristics of Simulink Models

This version of Simulink Control Design™ software provides new blocks for:

- “Plotting Linear System Characteristics of Simulink Models” on page 30.
- “Verifying Linear System Characteristics of Simulink Models” on page 30.

Plotting Linear System Characteristics of Simulink Models

Simulink Control Design software provides six new blocks in the **Linear Analysis Plots** library. Use these blocks to plot the time- and frequency-domain characteristics of a linear system computed from a nonlinear Simulink model. The linear system is computed and plotted during simulation at:

- Simulation snapshot times. The default snapshot time is 0.
- Trigger-based simulation events.

You can also use these blocks to specify bounds on the linear system characteristics, and view the bounds on the plot.

Because these blocks are same as the Model Verification blocks except for the default settings of the bound parameters, you can optionally use the blocks to verify that the bounds are satisfied during simulation.

For more information, see:

- Visualize Bode Response of Simulink Model During Simulation
- Linear Analysis Plots block reference pages
- Plotting Linear System Characteristics of a Chemical Reactor demo

Verifying Linear System Characteristics of Simulink Models

Simulink Control Design software provides six new blocks in the **Model Verification** library. Use these blocks to verify that the time- and frequency-domain characteristics of a linear system, computed from a nonlinear Simulink model, satisfy specified bounds during simulation. For

example, you can verify whether the linearized behavior of your model satisfies upper and lower magnitude bounds on a Bode plot or gain and phase margins.

You can perform the verification during simulation at:

- Simulation snapshot times. The default snapshot time is 0.
- Trigger-based simulation events

Because these blocks are same as the Linear Analysis Plots blocks except for the default settings of the bound parameters, you can use the blocks to view the bounds on time- and frequency-domain plots.

You can also use these blocks with the Simulink Model Verification library blocks to design complex logic for model verification.

If you have Simulink Verification and Validation™ software, you can construct simulation tests for your model using the Verification Manager.

For more information, see:

- Model Verification in the Simulink Control Design documentation.
- Model Verification block reference pages
- Verifying Frequency-Domain Characteristics of an Aircraft demo

New Tools for Identifying Time-Varying Source Blocks for Frequency Response Estimation

When you are performing frequency response estimation, time-varying source blocks in the signal path can skew the results. Previously, to obtain accurate estimation, you manually identified source blocks and inserted open-loop points in your model to disable them.

The new `frest.findSources` command automatically detects time-varying source blocks in the signal path of the output linearization points in your Simulink model. Additionally, a new option to the `frestimate` command, `BlocksToHoldConstant`, allows you to disable these blocks during frequency response estimation.

For more information, see the `frest.findSources` and `frestimateOptions` reference pages.

There is also a new Model Advisor check for detecting time-varying source blocks in your model. For more information about using the Model Advisor, see *Consulting the Model Advisor* in the *Simulink User's Guide*.

Tuning Tools Update Workspace Variables That Define Parameters of Tuned Blocks

When you use Simulink Control Design tools to tune a block with parameters defined as workspace variables, the software now updates the values of the workspace variables. This update occurs when you write the compensator design to your Simulink model. The block remains parametrized by the variables. The software can update variable parameters that represent numerical values or `Simulink.Parameter` objects, whether they reside in the base workspace or the model workspace.

Previously, tuning a block parametrized by workspace variables overwrote the block parameters with numerical values. Thus, such tuning did not change the value of the workspace variables.

Enhanced PID Tuner Including New Response Plots

This release introduces several enhancements to the PID Tuner, including:

- New response plot options let you analyze system responses in either time domain (step plot) or frequency domain (Bode plot). Available responses are reference tracking, input and output disturbance rejection, controller effort, open loop, and plant.
- New options when the plant linearizes to zero at the operating point defined in the Simulink model.

When the plant linearizes to zero on launch of the PID Tuner, the PID Tuner provides an option to linearize at a different operating point. The PID Tuner also lets you import an LTI model of your plant, such as a model obtained by frequency response estimation. Previously, the PID Tuner did not launch when the plant linearized to zero.

For an example illustrating these options, see the new Simulink Control Design demo, *Designing PID Controller in Simulink with Estimated Frequency Response*.

For more information about using the PID Tuner, see *Automatic PID Tuning* in the *Simulink Control Design User's Guide*.

New Demo Illustrating Control Design for a Plant That Has Parameter Variations

The Reference Tracking of a DC Motor with Parameter Variations demo illustrates compensator design for a plant that has parameter variations. The demo shows the following techniques:

- Performing batch linearization to obtain multiple linear models from a single Simulink model
- Using the new SISO Design Tool ability to analyze a control design for multiple models simultaneously

R2010a

Version: 3.1
New Features: Yes
Bug Fixes: Yes

New Parallel Computing Support For Frequency Response Estimation

If you have the Parallel Computing Toolbox™ software installed, you can use parallel computing to speed up frequency response estimation.

For more information, see [Speeding Up Estimation Using Parallel Computing](#) in the Simulink Control Design documentation.

New Commands Support Recomputing Frequency Response Estimation Results at Specific Frequencies

If you use the sinestream input signal for estimation, you can now recompute your frequency response estimation for only those specific frequencies that do not reach steady state. Previously, you had to redo the entire estimation if a few frequencies needed recomputing.

For more information, see [Time Response Not at Steady State](#).

New `frest.simcompare` Output Argument Returns Simulation Output Data From Linear System

This release provides enhanced `frest.simCompare` functionality, which allows the return of simulated output data. If your linear model uses state-space representation, you can also return the state vector.

For more information, see the `frest.simCompare` reference page.

New Options in Simulink Results Viewer GUI for Viewing Frequency Response Estimation Results

The Simulation Results Viewer GUI, which you display using `frest.simView`, now provides additional options for analyzing your frequency response estimation:

- You can now enable phase unwrapping in the frequency response plot. To unwrap phase, right-click the Bode plot, and select **Unwrap Phase**.
- You can also import frequency response estimation results into an open Simulation Results Viewer, which replaces the existing results. Previously, you had to open a new Viewer each time you viewed estimation results. To import results, select **File > Import** in the Simulation Results Viewer.

New Option for Labeling Bus Signal I/O Names in the SISO Design Task

You can now configure the SISO Design Task to automatically label model I/Os using bus signal names. Model I/O labels describe available loops in the Graphical Tuning tab and label response plots in the Analysis Plots tab of the SISO Design Task GUI. Previously, labels for bus signals were based on the block and port path, or the Simulink signal name.

To use this option, select **Tools > Options** in the SISO Design Task GUI, and enable **Use bus signal names to label model I/O**.

Existing Simulink Blocks Now Have Analytic Jacobians

The following Simulink blocks now have Analytic Jacobians, which are optimized for memory consumption in large-scale models:

- Switch
- Multiport Switch
- Math Function (Transpose and Hermitian Transpose)

For more information on each block, see the block reference pages.

Change in Format of Time Series in `frestimate` Output

Compatibility Considerations: Yes

When you use the `simout` output of the `frestimate` command, you obtain a cell array of `Simulink.Timeseries` objects. Previously, the time dimension was always the first dimension of each `Simulink.Timeseries` object.

As of R2010a, the time dimension of each `Simulink.Timeseries` in `simout` is:

- The first dimension, if the time series is 2-D
- The last dimension, if the time series is 3-D or higher

Compatibility Considerations

If you have scripts that run `frestimate` on a model having an output point on a vector or matrix signal and perform operations on the resulting 3-D or higher-dimensional `Simulink.Timeseries` object in `simout`, modify your scripts to reflect the new placement of the time dimension in the time series.

For additional information, see:

- MATLAB Data Analysis Release Notes
- `frestimate` reference page
- `Simulink.Timeseries` reference page

R2009b

Version: 3.0
New Features: Yes
Bug Fixes: Yes

New GUI for Tuning New PID Controller Blocks

You can automatically tune the new Simulink PID Controller blocks in the PID Tuner GUI R2009b introduces. You launch the PID Tuner directly from the PID block dialogs boxes. These blocks are available in the Continuous and Discrete Simulink libraries.

For more information on tuning PID Controller using the PID Tuner, see [Automatic PID Tuning](#).

New Automated PID Tuning Algorithm

You can now tune compensators using a new automated PID tuning algorithm called Robust Response Time, which is available in the SISO Design Task. You specify the open-loop bandwidth and phase margin, and the software computes PID parameters to robustly stabilize your system.

For information on tuning compensators using automated tuning methods, see [Completing the Design](#).

Ability to Compute Frequency Response of Simulink Models

You can now compute the frequency response of a Simulink model using simulation. You use new commands to easily create input signals and simultaneously simulate and estimate the frequency response without changing your model. You can also use this capability to validate the accuracy of exact linearizations.

Ability to Specify the Linearization of Simulink Blocks

You can now specify the linearization of Simulink blocks, subsystems, and model references without having to replace any block in your model. You can specify the linearizations as LTI models or Robust Control Toolbox uncertain models.

Ability to Design Compensators for Plant Models With Time Delays

You can now design compensators for plants with exact time delay representations. Previously, you had to specify a Padé approximation before designing compensators.

For more information on designing compensators for plants with time delays, see [Designing Compensators for Plants with Time Delays](#).

New Commands to More Efficiently Compute Multiple Linearizations

You can now more efficiently compute multiple linearizations for large models when only a few blocks or model references change per linearization. You linearize the fixed portion of the model once using `linlft` and linearize the varying portion multiple times. Then, you combine the results using `linlftfold` to obtain linearizations equal to those you would receive if you linearized the entire model multiple times.

For more information, see the `linlft` and `linlftfold` reference pages.

Ability to Set Default Plot Type for Linear Analysis Results from GUI

You can now set the default plot type for viewing linear analysis results computed in the Control and Estimation Tools Manager. This setting applies to all future Control and Estimation Tools Manager sessions.

To set this option in the Simulink Control Design Preferences, select **File > Preferences** in the Control and Estimation Tools Manager.

R2009a

Version: 2.5
New Features: Yes
Bug Fixes: Yes

Ability to Generate MATLAB Code from the GUI for Creating Operating Points and Linearizing Models

You can now generate MATLAB code reflecting the configuration in the GUI when creating operating points and linearizing models.

Ability to Tune Additional Blocks

You can now tune the following blocks:

- Blocks that you discretized using the Simulink Model Discretizer
- Blocks in the Simulink Extras library that specify initial states or outputs

For information about how to tune these blocks, see [Selecting Blocks to Tune](#) in the Simulink Control Design documentation.

New Option for Labeling Bus Signal I/O Names in Linearization Results

You can now compute linear models that show the bus signal names for linearization I/O points located on buses. You can select this option using the following:

- Linearization Options GUI
- `linoptions` command

R2008b

Version: 2.4
New Features: Yes
Bug Fixes: Yes

New Upsampling Option for Rate Conversion When Linearizing Simulink Models

Version 2.4 includes an upsampling rate conversion method for linearization. This method upsamples discrete-time LTI systems at any sampling rate that is an integer-value-times faster than the sampling rate of the original system. You can select the upsampling rate conversion method in the following ways:

- Using the linearization options GUI
- From the command line using `linoptions`

For more information on the upsampling rate conversion method, see the `linoptions` reference page.

Ability to Specify State Order of Linearized Models from the Command Line

You can now specify the order of the states in your linearized model directly from the command line using the `linearize` command. Previously, you could only specify state order using the GUI.

For more information on specifying state order from the command line, see the `linearize` reference page.

Ability to Filter the Linearization Inspector to Show Blocks in the Linearization Path

You can now filter the list of blocks in the Linearization Inspector to show only the blocks in the linearization path. This filtering makes it easier for you to find blocks in the linearization path that you want to inspect.

Ability to Disable the Calculation of Linearization Diagnostics and Inspector Data in the GUI

You can now disable the calculation of the linearization inspector and diagnostics information when you linearize using the GUI. This capability allow you to choose when you want to calculate diagnostic information.

R2008a

Version: 2.3
New Features: Yes
Bug Fixes: Yes

New Diagnostic Messages Help You Troubleshoot Linearization Results

You can now view diagnostic messages for your linearized model that help you diagnose and troubleshoot linearization results. These messages identify blocks in your model that encounter the following block issues during linearization:

- Blocks that have been marked as not supported for linearization
- Blocks with linearization configuration warning messages
- Blocks without pre-programmed exact Jacobian that linearize using numerical approximation

Ability to Find Operating Points for Simscape Models

You can now find operating points for models that include Simscape™ and SimHydraulics® blocks using the Simulink Control Design `findop` command.

For more information on finding operating point for Simscape Models, see the Simscape documentation.

Updated Error and Warning Message System

The Simulink Control Design error and warning IDs and messages have been updated. If you use error and warning IDs in your code, you must update your code to reflect the new IDs.

R2007b

Version: 2.2
New Features: Yes
Bug Fixes: Yes

Ability to Linearize Models with Model-Reference Blocks by Any Linearization Method

You can now perform any type of linearization for models containing Model blocks that reference other Simulink models.

Previously, you could only perform numerical perturbation linearization for models containing Model blocks. Now, you can also perform block-by-block linearization for such models when you set the simulation mode of the Model blocks to Normal.

Ability to Design Compensators for Models Containing Model-Reference Blocks

You can now design compensators for tunable blocks inside external models referenced by your model. Your model references such external models by using Model blocks. You can also update the tunable blocks in the external model with the new compensator designs.

To view and select tunable blocks for compensator design from the referenced model, set the simulation mode of the Model block to Normal.

For more information about the types of blocks that you can tune, see [Selecting Blocks to Tune in the Simulink Control Design documentation](#).

Ability to Generate Linearized Models with Exact Time-Delay Representations

You can now use the Simulink Control Design software to compute linearized models with exact time-delay representations. Time delays in the original nonlinear model can result from any of the following blocks:

- Transport Delay
- Variable Time Delay
- Variable Transport Delay
- Unit Delay
- Integer Delay

Previously, you could only achieve approximate linearizations of models with continuous time delays using a Padé approximation.

Ability to Linearize Periodic Function-Call Subsystems

You can now linearize periodic function-call subsystems with a constant sample time as discrete subsystems. You must set the sample time of the function-call trigger block to equal the sample time of the function-call generator block.

For more information on function-call subsystems, see [Function-Call Subsystems](#) in the Simulink documentation.

R2007a

Version: 2.1
New Features: Yes
Bug Fixes: Yes

Ability to Linearize Using an Operating Point Specified Directly in a Model

You can use the Simulink Control Design software to linearize around any operating point that you specify directly in a Simulink model. This capability allows you to make changes to a model and then perform a linearization around the newly specified operating point with the click of a single button. Previously, this same task required two steps: creating a new operating point and then linearizing around this operating point.

There are two ways to linearize around an operating point specified directly in the model:

- From the Control and Estimation Tools Manager
- Using `linearize`

Ability to Capture Linearization Snapshots in GUI

You can use the Control and Estimation Tools Manager to linearize at snapshots of your model operating point at the following simulation points:

- Specified simulation times, such as when the simulation reaches a steady state solution
- Events during a specified simulation interval

As in prior releases, you can use `linearize` to perform linearization at snapshots in your model operating point, as described in `linearize` in the reference pages.

Ability to Perform Control Design at Snapshots in GUI

You can use the Control and Estimation Tools Manager to perform control design at snapshots of your model operating point at the following simulation points:

- Specified simulation times, such as when the simulation reaches a steady state solution
- Events during a specified simulation interval

Ability to Retrieve Stored Compensator Designs

When you design a compensator using the SISO design tool, you can store the current design and then continue making changes to this design. A new button called **Retrieve Design** lets you retrieve the stored design at any time by undoing the design changes you made since you last stored the design. For more information on retrieving stored compensator designs, see *Storing and Retrieving Designs* in the Simulink® Control Design™ documentation.

R2006b

Version: 2.0.1
New Features: No
Bug Fixes: Yes

R2006a

Version: 2.0
New Features: Yes
Bug Fixes: Yes

Compensator Design in Simulink Is Now Supported

This release provides new tools to streamline the workflow for designing Single-Input Single-Output (SISO) control loops directly in Simulink. In previous releases, designing a compensator was a multistep process that involved several tools.

The new tools support any linearizable control architecture, such as single loops, multiple loops, and cascaded loops. With the new tools, you simply select the blocks you want to tune. Then, the Simulink Control Design software automatically analyzes your model to identify the relevant control loops and opens a preconfigured session of the SISO Design Tool (in the Control System Toolbox™ software). For more information, see “Designing Compensators” in the Simulink Control Design documentation.

Supported tunable SISO Simulink blocks include Gain, Transfer Function, Zero-Pole-Gain, State-Space, and PID blocks.

In the SISO Design Tool you can

- Graphically tune multiple SISO loops in a single GUI.
- Gain visual insight into loop interactions and coupling effects.
- Focus the analysis on a specific loop in a multiloop design by removing the effect of other feedback loops.
- Generate first-cut compensator designs using systematic design algorithms, such as Ziegler-Nichols PID tuning, IMC design, or LQG design.
- Optimize linear responses to meet time and frequency-based design constraints (requires the Simulink Response Optimization™ software).
- Directly tune Simulink block parameters, such as PID gains, zero-pole-gain representations, and masked blocks.
- Tune continuous or discrete control loops.
- Examine the closed-loop response of any portion of a model.

After a design is completed, you can write the tuned parameter values back to your model for verification with the full nonlinear system.

R14SP3

Version: 1.3
New Features: Yes
Bug Fixes: Yes

Control and Estimation Tools Manager Enhanced

You can copy and edit operating points within the Control and Estimation Tools Manager. .

You can initialize a model for simulation using operating points from within the Control and Estimation Tools Manager.

Support for Operating Point Search and Linearization of Models with Model Reference Blocks

You can linearize and compute operating points for models that reference other models using the Model block. Linearization of model reference models must use the numerical perturbation linearization algorithm. This algorithm accepts state and input perturbation values in the form of an operating point object.

R14SP2

Version: 1.2
New Features: Yes
Bug Fixes: Yes

Context-Sensitive Help Added

Access context-sensitive help for the Linearization, Operating Point Search, and Linearization State Ordering Options window of the Control and Estimation Tools Manager. To access help on a field within the options window, right-click the option's label and select **What's this?** from the context menu. Help for the option will appear in this window.

View Linearizations in the Control and Estimation Tools Manager

You can view state space, transfer function, and zero-pole gain representations of linearized models within the Control and Estimation Tools Manager without exporting to the workspace. These linearized models appear in the linearization summary pane of the Control and Estimation Tools Manager.

Discretization Methods Added

You can select from three different discretization methods for linearization of multirate and hybrid models.

List of Blocks with Preprogrammed Analytic Jacobians Added

You can view a complete list of blocks indicating which blocks have preprogrammed analytic Jacobians for use with the block-by-block analytic linearization algorithm.

Block Name Readability Improved

You can use either truncated block names or full block names in the state space matrices of a linearized model, and within the LTI Viewer, to improve readability.