

Release Notes for MATLAB®

How to Contact MathWorks



www.mathworks.com
[comp.soft-sys.matlab](mailto:comp.soft-sys.matlab@mathworks.com)
www.mathworks.com/contact_TS.html

Web
Newsgroup
Technical Support



suggest@mathworks.com
bugs@mathworks.com
doc@mathworks.com
service@mathworks.com
info@mathworks.com

Product enhancement suggestions
Bug reports
Documentation error reports
Order status, license renewals, passcodes
Sales, pricing, and general information



508-647-7000 (Phone)



508-647-7001 (Fax)



The MathWorks, Inc.
3 Apple Hill Drive
Natick, MA 01760-2098

For contact information about worldwide offices, see the MathWorks Web site.

Release Notes for MATLAB®

© COPYRIGHT 2004–2013 by The MathWorks, Inc.

The software described in this document is furnished under a license agreement. The software may be used or copied only under the terms of the license agreement. No part of this manual may be photocopied or reproduced in any form without prior written consent from The MathWorks, Inc.

FEDERAL ACQUISITION: This provision applies to all acquisitions of the Program and Documentation by, for, or through the federal government of the United States. By accepting delivery of the Program or Documentation, the government hereby agrees that this software or documentation qualifies as commercial computer software or commercial computer software documentation as such terms are used or defined in FAR 12.212, DFARS Part 227.72, and DFARS 252.227-7014. Accordingly, the terms and conditions of this Agreement and only those rights specified in this Agreement, shall pertain to and govern the use, modification, reproduction, release, performance, display, and disclosure of the Program and Documentation by the federal government (or other entity acquiring for or through the federal government) and shall supersede any conflicting contractual terms or conditions. If this License fails to meet the government's needs or is inconsistent in any respect with federal procurement law, the government agrees to return the Program and Documentation, unused, to The MathWorks, Inc.

Trademarks

MATLAB and Simulink are registered trademarks of The MathWorks, Inc. See www.mathworks.com/trademarks for a list of additional trademarks. Other product or brand names may be trademarks or registered trademarks of their respective holders.

Patents

MathWorks products are protected by one or more U.S. patents. Please see www.mathworks.com/patents for more information.

Desktop	2
Option to add separators between controls on the quick access toolbar	3
Additional icon choices, auto-scaled thumbnails, and text-formatting options for customizing descriptions of MATLAB apps	4
Left-aligned table of contents for navigating in the Help browser and online Documentation Center	5
Search term highlighting and content expansion in the Help browser	6
Context menu items in Help and Web browsers for zooming, page navigation, and saving	7
Removal of Handle Graphics support under <code>-nojvm</code> startup option	8
<code>-noFigureWindows</code> startup option suppresses figures on Linux and Mac platforms	9
No default keyboard shortcut for overwrite mode	10
Support requests using prerelease versions	11
 Language and Programming	 12
<code>matlab.unittest</code> package, an xUnit-style testing framework for the MATLAB language that allows writing and running unit tests, and analyzing test results	13
<code>strsplit</code> and <code>strjoin</code> functions for splitting and joining strings	14
Additional <code>validateattributes</code> options for checking array size and shape	15
Help text for enumerations and events	16
Removal of support for <code>.jar</code> documentation files	17
Changes to Microsoft .NET Framework support	18
Changes to compiler support for building MEX-files	19
Changes to subclasses of built-in classes	20
Conversion of error and warning message identifiers	21
No strict-match requirements for month formats when converting date strings	22
Date functions error on out-of-range quarter values	24

String representations of large integers using exponential notation	25
Do not use <code>classpath.txt</code> file to modify Java static path	26
Functionality being removed or changed	27
Mathematics	28
scatteredInterpolant and griddedInterpolant support for extrapolation	29
Syntax for ones, zeros, and other functions for creating arrays that match attributes of an existing variable ...	30
Integer type support for prod, cumsum, cumprod, median, mode, and number theory functions	31
flintmax function for largest consecutive integer in floating-point format	32
Scale option for airy function	33
scatteredInterpolant class that replaces TriScatteredInterp	34
triangulation class to replace TriRep	35
delaunayTriangulation class to replace DelaunayTri ...	37
Set functions behavior change	39
Functionality being removed or changed	41
Graphics	47
gobjects function for preallocating graphics handle array	48
Functionality being removed or changed	49
Data Import and Export	50
Reading and writing indexed and grayscale AVI files with VideoReader and VideoWriter objects	51
Writing MPEG-4 H.264 files on Mac with VideoWriter object	52
Tiff object improvements for reading and writing RGB-class TIFF images	53
Importing non-ASCII encoded files with textscan function	54
Multichannel JP2 support in imread function	55
Previous behavior change of xlsread function output ...	56
Authentication, user name, and password inputs for urlread and urlwrite functions	58
Additional audio and video file reading capabilities using Import Wizard and importdata function	59

sound function nonblocking	60
Functionality being removed or changed	61
Performance	62
fft function performance improvements on computers with new Intel and AMD processors	63
permute function performance improvements for 3-D and higher dimensional arrays	64

R2012b

Desktop	66
Toolstrip that replaces menus and toolbars in MATLAB Desktop	67
Apps gallery that presents apps from the MATLAB product family	69
Single-file application packaging as a MATLAB App Installer file for inclusion in the apps gallery	70
Redesigned Help with improved browsing, searching, and filtering	71
Viewing of multiple documentation pages simultaneously with tabbed browsing	75
Suggested corrections for mistyped functions and variables in the Command Window	76
Full-screen view mode on Mac operating systems	77
Changes to -nojvm startup option on Mac	78
Tabs in MATLAB Web browser	79
Direct access to run configurations from the Run button ..	80
Multiple vector creation from single selection in Variables editor	82
Language and Programming	83
Abstract attribute for declaring MATLAB classes as abstract	84
Diagnostic message improvements when attempting to create an instance of an abstract class	85
Handle and dynamicprops do not support the empty static method	86
Switch uses eq to compare enumerations	87

Cannot specify property attributes multiple times	88
Discontinued compiler support for building MEX-files	89
Jagged array support for .NET	90
Java exceptions accessible to MATLAB code	91
Ability to add jar files to static Java class path	92
Preservation of string functions for backwards compatibility	93
Conversion of Error and Warning Message Identifiers ...	94
Mathematics	95
Performance improvements and multithreading for airy, psi, and Bessel functions	96
ddensd function that solves delay differential equations of neutral type with state-dependent delays	97
Signed integer support for bit-wise operations	98
atan2d function that calculates four-quadrant inverse tangent with result in degrees	99
Complex number support for trigonometry degree functions	100
Functionality being removed or changed	101
Data Import and Export	104
Data import from delimited and fixed-width text files using Import Tool	105
Single-step import of numbers, text, and dates as column vectors from a spreadsheet with Import Tool	106
audioread and audioinfo functions for reading MP3, MPEG-4 AAC, WAVE, and other audio files	107
audiowrite function for writing MPEG-4 AAC, WAVE, and other audio files	108
Reading and writing of BigTIFF image files larger than 4 GB	109
Reading of XLSM, XLTX, and XLTM files on all platforms with xlsread function	110
xlsread function now supporting named ranges on all platforms	111
Multiple delimiter support in textscan function	112
Timeout, user agent, and character encoding inputs for urlread and urlwrite functions	113
Functionality being removed or changed	114

Desktop Tools and Development Environment	116
Transpose and Sort Variables in the Variable Editor	117
MATLAB Dock Menu on Mac Includes New Capabilities ..	118
Improved Rendering in MATLAB Web Browser	120
Technical Support Requests Use Proxy Settings	121
Published Code Can Display Syntax Highlighted Sample Code	122
The <code>publish</code> Function Accepts Name-Value Pairs	123
Internationalization	124
Mathematics	128
New Integral Functions	129
Performance Enhancements	130
griddata Supports 3-D Data and Natural Neighbor Interpolation	131
TriScatteredInterp Accepts Complex Values	132
Set Functions Provide Option to Return Sets in Original Order	133
Set Functions Changing Behavior in a Future Release ...	134
Interpolation and Computational Geometry Functionality Being Removed or Changed	136
Other Functionality Being Removed or Changed	143
Data Analysis	146
Programming	147
xlsread Reads XLSX Files on All Platforms	148
VideoWriter Supports MPEG-4 Files on Windows 7 Systems	149
audioplayer Supports Overlapping Playback	150
importdata Returns Different Output for Some Text Files	151
Exponents Print with Two Digits	153
Conversion of Error and Warning Message Identifiers ...	154
Specify a List of Allowed Subclasses in the Class Definition	155
Specify Which Classes Can Access Class Members	156
Method Declared as Abstract and Private Now Errors ...	157
New Capabilities for Writing Image Data to FITS Files ..	158

Access Data on Remote Servers Using the OPeNDAP Protocol	159
Upgrades to Scientific File Format Libraries	160
Ability to Read NetCDF Files Using HDF4 Functions Removed	161
Functionality Being Removed or Changed	162
Graphics and 3–D Visualization	164
Creating Graphical User Interfaces (GUIs)	165
External Interfaces/API	166
Changes to Compiler Support	167
mxAssert and mxAssertS Functions Throw MATLAB Exception	168
Version Support for COM ProgID Values	169

R2011b

Desktop Tools and Development Environment	172
Command Window	173
Editor	174
Internationalization	175
Mathematics	178
New Functionality for Grid-Based Interpolation	179
Performance Enhancements	180
Permutation Option for randperm	181
Return Permutation Information in Vector for qr	182
Changes to meshgrid and ndgrid	183
Functionality Being Removed or Changed	184
Data Analysis	185
Programming	186
Load and Save Parts of Variables in V7.3 MAT-Files	187
Nonmatching Function Name Warning is Now an Error ..	188

New narginchk Function Replaces nargchk	189
Conversion of Error and Warning Message Identifiers ...	190
New Spreadsheet Import Tool	191
Two Functions Added to netCDF Low-Level Package To Aid Performance	192
Improved Performance for TIFF Input and Output	193
Upgrades to Scientific File Format Libraries	194
VideoReader Supports MPEG-4 and MOV on Windows 7 Systems	195
MATLAB Warns if Listener Defined for Nonobservable Property	196
MATLAB Warns if Property Is Not Member of Class When Defining Listener	197
Built-In disp Works with Empty Objects	198
MATLAB Warns if Class Defines Property as Dependent and Constant	199
Support for Switch/Case Statements with Objects	200
Functionality Being Removed or Changed	201
Graphics and 3-D Visualization	202
Creating Graphical User Interfaces (GUIs)	203
External Interfaces/API	204
Changes to Compiler Support	205
New Object Support for mxGetProperty and mxSetProperty Functions	206
MEX Header File Does Not Define C++ Type char16_t ...	207
New Support for Features in Microsoft .NET Framework ..	208
COM Automation Server Error Message Formatting	210

R2011a

Desktop Tools and Development Environment	212
Desktop	213
Help Browser	214
Managing Files	216
Editing and Debugging MATLAB Code	218
Publishing MATLAB Code	220

MATLAB Notebook Menu Labels	221
Mathematics	222
New Function rng	223
New Function ichol	224
New Option for gammainc	225
Performance Enhancement	226
Changes to qr	227
Functionality Being Removed	228
Programming	229
Regenerate P-code Files Built Before Version 7.5	230
VideoWriter Supports Motion JPEG 2000 Files	231
audioplayer and audiorecorder Support Device Selection on All Platforms	232
New Class Forms the Basis for Heterogeneous Hierarchies	233
New Class Provides the Basis for Customizable Handle Object Copy Method	234
MATLAB Meta-Classes Can Now Form Heterogeneous Arrays	235
New High-Level NetCDF Functions	236
New High-Level HDF5 Functions	237
Two New Functions Added to CDFLIB Package	238
HDF4 Functions Grouped into Packages	239
FITSREAD Function Now Supports Data Subsetting	240
Unrecognized Name Warning Changed to Error	241
Regular Expressions Support Zero-Length Matching	243
Growing Arrays Is Faster	244
Error Checking Improved	245
Functions and Function Elements Being Removed	246
Graphics and 3-D Visualization	247
Plot Catalog with a New Look, More Plots, and Diagnostics	248
Creating Graphical User Interfaces (GUIs)	250
Do not Repopulate Menus on the Mac from Inside Their Callbacks	251
Functions and Function Elements Being Removed	252
External Interfaces/API	253

Changes to Compiler Support	254
Changes to Shared Library Compiler Support	256
New Support for Features in Microsoft .NET Framework ..	257

R2010bSP2

R2010bSP1

R2010b

Desktop Tools and Development Environment	264
Desktop	265
Help Browser	267
Managing Files	268
Editing and Debugging MATLAB Code	270
Mathematics	273
64-Bit Integer Arithmetic	274
New Utility Functions: isrow, iscolumn, ismatrix	275
Output Option for Point Distances in DelaunayTri/nearestNeighbor Method	276
Changes to convhull and delaunay Functions	277
Performance Enhancements	278
Functions Being Removed	279
optimset Errors for Optimization Toolbox Options	280
atan Warning Being Removed	281
Data Analysis	282
Arrays of Time Series Objects Supported	283
Programming	285

arrayfun Accepts Array of Objects	286
Comparing Object Arrays that Contain NaNs	287
Functions isa and islogical Now Consistent for Objects ...	288
New Enumeration Classes	289
New Functionality for Writing Video Files	290
mmreader Renamed VideoReader	291
New HDF4 Functions	292
New HDF5 Low-Level Functions	293
New netCDF Functions	294
Upgrades to Scientific File Format Libraries	295
New Examples in Command Line Help	296
imread and imwrite Can Now Handle N-channel J2C JPEG 2000 Files	297
csvread and csvwrite Will Not Be Removed	298
sprintf and fprintf Print Null Characters in Strings	299
Functions and Function Elements Being Removed	300
MATLAB Did Not Pass struct to loadobj When Property Was Deleted	302
Graphics and 3-D Visualization	303
Print -dmfile and printdmfile Issue Deprecation Warnings	304
The saveas 'mmap' option Issues a Deprecation Warning ..	305
The movie Function is No Longer a Built-in Function	306
Creating Graphical User Interfaces (GUIs)	307
Functions and Function Elements Being Removed	308
External Interfaces/API	310
Changes to Compiler Support	311
-largeArrayDims Option to MEX Will Become Default in Next Release of MATLAB	313
MEX Function -argcheck Option Removed	314
MEX Function -inline Option Removed	315
New Support for Features in Microsoft .NET Framework ..	316
New COM Data Type Support	317

Desktop Tools and Development Environment	320
Desktop New Features Video for R2010a	321
Startup and Shutdown	322
Desktop	323
Help Browser	325
Managing Files	328
Editing and Debugging MATLAB Code	332
Mathematics	333
New Multithreading Capability	334
Performance Improvements	335
Changes To qr	336
Change in Indexing for Sparse Matrix Input	337
Improved Error Checking for Sparse Functions	338
Computational Geometry Functions Being Changed	339
Computational Geometry Functions Being Removed	340
lsqnonneg No Longer Uses Optional Starting Point Input	341
Function erfcore Removed	342
Integer Warning Messages Removed	343
Function intwarning Being Removed	344
atan Warning Being Removed	345
nextpow2 Returns Output the Same Size As Input	346
Math Libraries Not Available to Build MEX-Files with Compaq Visual Fortran	347
Data Analysis	348
Operations on Timeseries Objects Sometimes Warn About the isTimeFirst Property	349
Time Series Time Vectors Can Now Contain Duplicate Sample Times	350
Programming	351
Subscribing Into Function Return Values	352
New Constructor for Map Containers	353
Function Handle Access to Private and Protected Methods	354
Listing Video File Formats Supported by mmreader	355
unzip Preserves Write Attribute of Files	356

New Package Provides Access to low-level CDF API	
Routines	357
Upgrades to Scientific File Format Libraries	358
Tiff Class Enhancements	359
MATLAB Adds Support for Creating JPEG 2000 Files ...	360
Sealed No Longer Listed as meta.property Class	
Property	361
Functions and Function Elements Being Removed	362
Graphics and 3-D Visualization	365
Plot Selector Supports Additional Toolboxes	366
External Interfaces/API	367
Changes to Compiler Support	368
Changes to Libraries on Linux with Debian Systems	370
Math Libraries Not Available to Build MEX-Files with	
Compaq Visual Fortran	371
Cannot Create MEX-Files with DLL File Extension	372
-largeArrayDims Option to MEX Will Become Default in	
Next Release of MATLAB	373

R2009bSP1

R2009b

Desktop Tools and Development Environment	378
Startup and Shutdown	379
Desktop	380
Help Browser	383
Workspace and Variable Editor	388
Managing Files	389
File Exchange Desktop Tool — Find and Get Files Created	
by Other Users	392
Editing and Debugging MATLAB Code Files	394
Publishing MATLAB Code Files to PDF Output Format ..	395

Internationalization	396
Mathematics	397
Computational Geometry Functions Being Changed	398
Computational Geometry Functions Being Removed	399
New Sparse Matrix Functionality In qr and mldivide Functions	400
Support for Large-Sized Dimensions In fft	401
Performance Improvement For Large Data Sets	402
erfc core Being Removed	403
New Multithreading Capability	404
New Test Matrices in gallery Function	405
Data Analysis	406
Improved Plot Selector Makes Graphic Data Exploration Easier	407
Programming	408
Ignore Selected Arguments on Function Calls	409
Internal Packages Make Reserved Functions Easy to Identify	410
Use of lasterror, lasterr, rethrow(errStruct) Not Recommended	411
Use of maxNumCompThreads No Longer Recommended ..	413
Excel Worksheet Selection in the Import Wizard	414
Motion JPEG 2000 Files Supported by mmreader	415
Minimum Sample Rate for audioplayer	416
Documentation Changes: File I/O and Data Import and Export	417
Object Array Property Indexing	418
Equality of Objects Using isequal Now Ignores Numeric Class	419
Class Defining Private/Abstract Property Now Errors	420
Subclasses of Built-in Classes and numel	421
Array Expansion with Indexed Assignment	422
New Tiff Object Enables Writing of Tiled Data and Broader Metadata Support	423
Ambiguity Error Now Reported	424
Graphics and 3-D Visualization	425
Enhanced Plot Selector Simplifies Data Display	426

Certain Print Options and Devices Now Warn When Used	429
The view Function No Longer Supports 4-by-4 Transformation Matrices as Input	430
Creating Graphical User Interfaces (GUIs)	431
Expanded Documentation on Techniques for Programmatic GUI Design	432
Previous Change to How UI Components Set the Figure SelectionType Property	433
External Interfaces/API	434
Changes to Compiler Support	435
Run-Time Libraries Required for Applications Built with Microsoft Visual Studio 2008 Compiler	437
Changes to Building MEX-Files	438
New Features for Interface to Microsoft .NET Framework	439

R2009a

Desktop Tools and Development Environment	442
Desktop New Features Video	443
Startup and Shutdown	444
Desktop	445
Running Functions — Command Window and History ...	447
Help and Related Resources	448
Workspace, Search Path, and File Operations	450
Editing and Debugging MATLAB Code	451
Tuning and Managing MATLAB Code Files	458
Publishing MATLAB Code Files	459
Mathematics	460
Upgrade to Computational Geometry	461
Incomplete Inverse Gamma Function <code>gammaincinv</code> and Incomplete Inverse Beta Function <code>betaincinv</code>	462
Krylov Subspace Methods <code>bicgstabl</code> and <code>tfqmr</code>	463
New Function <code>quad2d</code>	464
Changes To <code>conv</code>	465

Changes To conv2 and convn	466
nextpow2 Changing to Element-By-Element Calculation in a Future Release	467
Function finite Being Removed	468
New Multithreading Capability in MATLAB Functions ..	469
64-bit Support in LAPACK and BLAS	470
Upgrade to ACML 4.1.0	471
Data Analysis	472
Programming Fundamentals	473
Setting the Number of Threads Removed from Preferences Panel	474
Timer Objects Saved in New Format	475
mmreader Supports Linux Platforms	476
Support of Microsoft Excel 2007 File Formats	477
Anonymous Functions Support str2func	478
size and range Implemented for validateattributes	479
isempty Supported for Map Objects	480
Bug Fix for Misinterpreted Variables	481
MATLAB Upgrades Support for HDF5 to Version 1.8.1 ...	482
Indirect Calls to Superclass Constructors Now Errors	483
Graphics and 3-D Visualization	484
Functions Previously Only Available in the Image Processing Toolbox Now Available in MATLAB	485
Creating Graphical User Interfaces (GUIs)	486
New Programmatic GUI Doc Example	487
GUIDE Help Menu Enhanced	488
External Interfaces/API	489
New Interface to Microsoft .NET Framework	490
Expanded Platform Support Added for MATLAB Serial Port	491
Changes To Compiler Support	492
Do Not Use mxFree to Destroy mxArray Arrays	494
Cannot Build MEX-Files Using MATLAB Version 5 API ..	495
MEX-Files Calling BLAS or LAPACK Functions Must Be Updated On 64-Bit Platforms	496
Object .o Files Saved on Macintosh Systems for Debugging	497

Run-Time Libraries Required for Applications Built with Microsoft Visual Studio 2008 Compiler	498
New Features for Shared Library Interface	499
New Java Thread Safety Functions	500
Improved Robustness of Web Services Functions	501

R2008b

Desktop Tools and Development Environment	504
Desktop New Features Video	505
Startup and Shutdown	506
Desktop	510
Running Functions — Command Window and History ...	512
Help and Related Resources	515
Workspace, Search Path, and File Operations	518
Editing and Debugging MATLAB Code	525
Tuning and Managing MATLAB Code Files	529
Publishing MATLAB Code Files	530
Mathematics	531
Upgrade to Random Number Generator	532
Multipoint Boundary-Value Problems with bvp5c	533
Upgrades to lsqnonneg	534
Functions and Properties Being Removed	535
Upgrade to Intel Math Kernel Libraries	536
Data Analysis	537
Specialized Data Tips for the hist Function	538
Programming Fundamentals	539
Fast Key Lookup Provided with New Map Data Structure	540
Tic and Toc Support Multiple Consecutive Timings	542
New Options for MException getReport	543
what Function Returns Package Information	544
addtodate Accepts Hours, Minutes, Seconds, Milliseconds	545
Querying Options Added to pause	546
File Selection Restriction in Import Wizard	547

Function Handle Array Warning Is Now An Error	549
Two Types of issorted Warnings Are Now Errors	550
Possible Conflict with New Keyword: SPMD	551
Do Not Create MEX-Files with DLL File Extensions	552
isequal Is Now Called Explicitly for Contained Objects ...	553
Indexed Assignment with Objects of the Form p(:) = o Now Consistent with MATLAB Language	554
fopen No Longer Supports VAXD, VAXG, and Cray Machine Formats	555
Graphics and 3-D Visualization	556
Certain Printer Formats and Drivers Now Warn When Used	557
Handle Graphics Not Supported Under -nojvm Startup Option	560
Creating Graphical User Interfaces (GUIs)	561
Undocumented Functions Removed	562
Handle Graphics Not Supported Under -nojvm Startup Option	564
New Menu Options to Hide or Show GUIDE Toolbar and Status Bar	565
GUIDE Status Bar Now Shows Tag Property of Selected Object	566
Four New Major GUI Examples	567
External Interfaces/API	568
Do Not Use DLL File Extensions for MEX-Files	569
MEX-Files Must Be Recompiled When -largeArrayDims Becomes Default MEX Option	570
New Compiler Support	571
Compiler Support to Be Phased Out	572
Use mxDestroyArray to Release Memory for mxArray ...	573
New Function Displays Information about MEX Compiler Configurations	574
New Functions to Catch Errors in MEX-Files Replace mexSetTrapFlag	575
“Duplicate dylib” Warning on Macintosh Systems	576
Microsoft Visual Studio "X64 Compilers and Tools" Required for 64-bit Systems	577
Run-Time Libraries Required for Applications Built with Microsoft Visual Studio 2008 Compiler	578

Do Not Use get or set Function to Manage Properties of Java Objects	579
COM Objects Might Display Different Number of Supported Events	580

R2008a

Desktop Tools and Development Environment	582
Desktop New Features Video	583
Startup and Shutdown	584
Desktop	589
Running Functions — Command Window and History ...	592
Help	593
Workspace, Search Path, and File Operations	594
Tuning and Managing M-Files	598
Editing and Debugging M-Files	599
Publishing M-Files	605
Internationalization	616
 Mathematics	 617
Upgrade to BLAS Libraries	618
Upgrade to LAPACK Library	619
More Multithreaded Support For Elementwise Math Functions With Warnings	620
New Algorithms for ldl, logm, and funm Functions	621
Functions and Properties Being Removed	622
 Data Analysis	 623
Data Brushing for Graphs and Linked Variables	624
 Programming	 629
Multithreaded Computations Enabled	630
Enhancements to Object-Oriented Programming Capabilities	631
Packages for Classes and Functions	632
Clear Variables with Exceptions	633
Information on the State of Memory	634
Define Your Own Function Cleanup Tasks	635
New Functions	636

Extended JIT Support	637
Enhancements to Image Information and Writing Functions	638
Compression of -v7.3 MAT-Files	639
Changes to Programming Documentation	640
Graphics and 3-D Visualization	641
New Figure Toolbar Buttons	642
“v6” Plotting Option Update — Affected Functions	643
Creating Graphical User Interfaces (GUIs)	645
New GUI Table Component	646
Event Data Input to GUIDE Callbacks	647
uigetfile and uiputfile Support of ‘,’ ‘.’, and ‘/’	648
hidegui Function Being Obsoleted	649
Changes to How uicontrols Set Figure SelectionType	650
External Interfaces/API	652
Interface to Generic DLLs Supported on 64-bit Platforms	653
Changes to Compiler Support	654
New Version of Perl on Windows Platforms	656
Rebuild MEX-Files Created on Linux Platforms	657
Use mxDestroyArray to Release Memory for mxArray ...	658
Do Not Use get or set Function to Manage Properties of Java Objects	659
New mxArray Functions for Use with MATLAB Class Objects	660
mex.bat File Removed from matlabroot\bin\\${ARCH}	661
Run-time Libraries Required for Applications Built with Microsoft Visual Studio 2008 Compiler	662
Environment Variables Required with Intel Visual Fortran 9.0	663
-largeArrayDims Option to MEX Will Become Default ...	664
Changes to Dynamic Data Exchange (DDE) Documentation	665

Desktop Tools and Development Environment	668
Startup and Shutdown	669
Desktop	671
Running Functions — Command Window and History ...	674
Help	675
Editing and Debugging M-Files	680
Publishing Results	689
Mathematics	691
New Functions	692
finite Function Deprecated	693
dmperm Function Gives Coarse Decomposition	694
ldl Function Supports Real Sparse Symmetric Matrices ..	695
Upgrade to LAPACK Library	696
Upgrade to BLAS Libraries	697
Library for LAPACK and BLAS Symbols Separated	698
Colon Operations on Characters Return Character Type Data	699
Matrix Generating Functions No Longer Accept Complex Inputs	700
Data Analysis	701
Programming	702
Increased Size for Large Arrays	703
Documentation for Multiprocessing in MATLAB	704
Setting Number of Threads Programmatically	705
New Internal Format for P-code	706
New Split String Functionality in regexp	707
Changes Related to Error Handling	708
Results From tempname Are More Unique	711
MATLAB Includes New Input Argument Validation Functions	712
Windows Current Working Directory Corrected	713
New Multimedia Functionality	714
Compressed AVI Video Files in Windows Vista and Windows XP x64	715
mmfileinfo Reads Files on MATLAB Path	716
Changes to imread Support of TIFF Format	717

Removal of freeserial Function	718
Graphics and 3-D Visualization	719
Datatips Are Now Saved to FIG-Files	720
New Options for Displaying Groups of Lines in Legends ..	721
Drawnow Update Option Now Updates Uicontrols Only ..	722
Annotation Textboxes Can Automatically Resize to Fit their Contents	723
Property Inspector Now Has Context-Sensitive Help	725
The “v6” Option for Creating Plot Objects is Obsolete	726
Creating Graphical User Interfaces (GUIs)	728
New Editors for Creating Custom Toolbars within GUIDE	729
Coordinate Readouts in Layout Editor	730
Documentation for Making GUIDE GUIs Interact	731
Functions Being Removed	732
External Interfaces/API	734
Support for 64-bit mxArrayArrays	735
Fortran MEX-Files Will Require mwSize and mwIndex ..	736
Changes to the MATLAB Locale Setting	737
Changes to MEX Error-Handling Functions mexErrMsgTxt and mexErrMsgIdAndTxt	738
Rebuild MEX-Files Created with MATLAB Versions Earlier Than V7 (R14)	739
Changes to Compiler Support	740
Changes to Applications Built with Borland 5.5 or 5.6 C Compilers	742
Environment Variable Required for mex with Microsoft Platform SDK Compiler	743
Environment Variables Required for mex with Intel Visual Fortran 9.0	744
Changes to Handling ActiveX Methods	745
Changes to Dynamic Data Exchange (DDE) Documentation	746

Desktop Tools and Development Environment	750
Startup and Shutdown	751
Desktop	756
Running Functions—Command Window and History	765
Help	767
Workspace, Search Path, and File Operations	769
Editing and Debugging M-Files	771
Tuning and Managing M-Files	775
Publishing Results	776
Mathematics	777
New Functions	778
More Efficient Matrix Multiplication for Sparse Matrices	779
rand Function Uses the Mersenne Twister Algorithm as Default	780
Upgrade to BLAS Libraries	782
mode of Empty Array Now Returns NaN	783
Change to Syntax for Setting BLAS Library Version on Linux	784
Data Analysis	785
Programming	786
New Functions	787
Parse Inputs with Consistently Implemented Mechanism	788
textscan Returns Like Values in Same Cell Array	789
Numbered Arguments for Formatted String Functions ...	790
The dir Function Returns Additional datenum Field	791
Using whos -file on Objects with Overloaded size or class Methods	792
mat2str Returns Correct Output for Strings	793
Warning Generated by try-catch	794
save -regexp Saves to Correct Filename	796
Functions Not Callable If in Directory Under Class Directory	797
Improved Performance on Certain Platforms and Operations	798

Technique to Conserve Memory on Windows Vista	799
ispuma Function Deprecated	800
Graphics and 3-D Visualization	801
Nudging Annotations with Arrow Keys	802
Movies No Longer Play During Loading	803
Ghostscript Printing Software Upgraded	804
Property Inspector Now Categorizes Graphic Object Properties	805
Figure WindowScrollWheelFcn Property Programs Scrollwheel Events	807
Figure KeyReleaseFcn Property Programs Key Release Events	808
Creating Graphical User Interfaces (GUIs)	809
GUIDE No Longer Copies Callbacks When You Duplicate Components	810
GUIDE M-File-Defined handles Structure Fields No Longer Become Permanent	811
UNIX: File Dialog 'Location' Property Is Obsolete	812
Functions Becoming Obsolete	813
External Interfaces/API	814
New File Extensions for MEX-Files	815
MEX-Files Built in MATLAB R11 or Earlier Must Be Rebuilt	816
Changes to Compiler Support	817
New COM Features	822
Changes to Handling Microsoft ActiveX Methods	824

R2006b

Desktop Tools and Development Environment	826
Startup and Shutdown	827
Desktop	829
Help	833
Workspace, Search Path, and File Operations	835
Editing and Debugging M-Files	836
Tuning and Managing M-Files	841

Publishing Results	844
Mathematics	845
New Functions	846
max and min Now Use Magnitudes and Phase Angle for Complex Input	847
Additional Output from lu	848
Upper and Lower Factors for chol and ldl	849
Permutation Vectors with lu, luinc, ldl	850
Two-Element Threshold for lu, spparms	851
Lower Triangular Factors from symbfact	852
Support for New Versions of AMD, COLAMD, CHOLMOD, UMFPACK	853
Sparse Arrays on 64-Bit Systems	855
FFTW Upgraded to Version 3.1.1 in MATLAB	856
Future Obsolete Functions	857
Obsolete Functions	858
max and min No Longer Return Warning Messages for Inputs with Different Data Types	859
Data Analysis	860
Generate M-File Now Supports Basic Fitting and Data Statistics	861
New Options for Working with Time Series Objects	862
Programming	863
Saving to MAT-Files Larger than 2 GB	864
Import Wizard Generates Import M-Code	866
New Dynamic Regular Expression Syntax	867
New Reserved MATLAB Keywords	868
Enhancements to Display Generated by whos	869
unique Function Returns First and Last Indices	870
save Compression and Unicode Options Removed	871
Warning Generated by try-catch	872
Case-Sensitivity Warning Removed	873
fprintf(0,...) Now Throws an Error	874
Assigning Nonscalar Structure Array Fields to a Single Variable	875
Comma Separators Not Required in Function Declaration	876
Improved Performance on Certain Platforms and Operations	877

Graphics and 3-D Visualization	878
Plotting Tools Are Now Modular Desktop Components ...	879
Version 6 Property Editor Has Been Removed	880
New Desktop Printing GUI	881
Zoom Mode Now Supports Mouse Scroll Wheel	882
Data Cursor Text Can Now Be Programmatically Modified	883
Customizing Zoom, Pan, and Rotate3D Data Explore Modes	884
Improvements to MATLAB Graphics Documentation	885
Creating Graphical User Interfaces (GUIs)	886
Functions Are Now Obsolete	887
Colored Buttons on Windows XP	888
Documentation Enhancement	889
External Interfaces/API	890
New Types for Declaring Size and Index Values	891
Sparse Arrays on 64-bit Systems	892
New MAT-File Format Based on HDF5	894
-V5 Option to MEX to Be Removed	895
Location of mex.bat File Changed	896
Changes to Compiler Support	897
Actxcontrol Command Now Validates ProgID	898

R2006a

Desktop Tools and Development Environment	900
Startup and Shutdown	901
Desktop	903
Running Functions — Command Window and Command History	904
Help	905
Workspace, Search Path, and File Operations	906
Editing and Debugging M-Files	907
Tuning and Managing M-Files	914
Publishing Results	917
Source Control Interface	918

Mathematics	919
New Library CHOLMOD for Sparse Cholesky Factorization	920
New Solver for State-Dependent DDEs	921
Upgrade to BLAS Libraries	922
New Function for Integer Division	923
New Input to gallery Function	924
Improved Algorithm for expm	925
More Efficient condst for Sparse Matrices	926
accumarray Accepts Cell Vector Input	927
Data Analysis	928
Data Analysis Collection Revised and Expanded	929
Reference Pages for timeseries and tscollection Objects ...	930
Text Files Can Be Imported In Time Series Tools	931
Linux 64 Platform Fully Enabled for Time Series Tools ..	932
Programming	933
Larger Data Sets with 64-Bit Windows XP	934
Using avifile and movie2avi on Windows XP 64	935
Regular Expressions	937
Setting Environment Variables	938
issorted Support for Cell Arrays	939
XLS Functions Support More Formats	940
Archiving Functions Accept Files on Path and ~/	941
sendmail No Longer Requires ASCII Messages	942
MATLAB Warns on Invalid Input to str2func	943
Changes to Character Encoding in File I/O	944
Graphics and 3-D Visualization	948
Pasting Cut or Copied Graphic Objects Can Create an Axes	949
Inspector Has New Look	950
Creating Graphical User Interfaces (GUIs)	951
Treatment of & in Menu Label Is Changed	952
Major Documentation Revision	953
External Interfaces/API	954
MEX-Files Built with gcc on Linux Must Be Rebuilt	955
MEX-Files in MATLAB for Microsoft Windows x64	956
New Microsoft and Intel Compilers Supported	957

MWPOINTER Macro for Platform-Independent Fortran	
Code	958
Compaq Visual Fortran Engine and MAT Options File	
Renamed	959
Options Files Removed for Unsupported Compilers	960
Obsolete Functions No Longer Documented	961
Support for Licensed ActiveX Controls	966
Support for VT_Date Type	967
Dynamic Linking of External Libraries	968

R14SP3

Desktop Tools and Development Environment	970
Startup and Shutdown	971
Desktop	972
Running Functions — Command Window and Command	
History	976
Help	978
Workspace, Search Path, and File Operations	981
Editing and Debugging M-Files	982
Tuning and Managing M-Files	986
Publishing Results	987
Mathematics	989
New Functions	990
Modified Functions	991
Changes to accumarray	992
Imposing Nonnegativity Constraints on Computed ODE	
Solution	993
Mersenne Twister Support in rand	994
svd Returns Economy Decomposition	995
New Location for LAPACK Libraries	996
Documentation on Data Analysis	997
Data Analysis	998
Data Analysis Documentation	999
Time-Series Analysis	1000
Programming	1001

New Functions	1002
Modified Functions	1003
Evaluation Functions for Arrays, Structures, Cells	1004
Using who and whos with Nested Functions	1005
Date and Time Functions Support Milliseconds	1006
Stack Trace Provided for lasterror	1007
isfield Function Supports Cell Arrays; Results Might Differ from Previous Version	1008
Support for Reading EXIF Data from Image Files	1010
Performance Improvements to the MATLAB JIT/Accelerator on Macintosh	1011
Specifying fread Precision as Number of Bits	1012
Seconds Field Now Truncated; Results Might Differ	1013
Built-in Functions No Longer Use .bi; Impacts Output of which Function	1014
New Warning About Potential Naming Conflict	1015
Graphics and 3-D Visualization	1016
Plot Tools Now Available on Mac Platform	1017
Documentation for Data Analysis Reorganized	1018
Creating Graphical User Interfaces (GUIs)	1019
Plans for Obsolete Functions	1020
External Interfaces/API	1022
mex Switches Now Supported on Microsoft Windows	1023
New COM Programmatic Identifier	1024
New File Extension for MEX-Files on Windows Systems ..	1025
New Preferences Directory and MEX Options	1028
Compiler Support	1029
Import Libraries Moved	1030
MEX Perl Script Moved	1031
Linking to System Libraries	1032
COM Automation Server Now Displays Figure	1033

R14SP2

Desktop Tools and Development Environment	1036
Installation Folder with Spaces	1037

Startup and Shutdown	1038
Desktop	1039
Running Functions — Command Window and History ...	1040
Help	1041
Workspace, Search Path, and File Operations	1042
Editing and Debugging M-Files	1043
Source Control Interface	1044
Publishing Results	1045
Mathematics	1046
New Vendor BLAS Used for Linear Algebra in MATLAB ..	1047
max and min on Complex Integers Not Supported	1048
Programming	1049
Memory-Mapping	1050
textscan Enhancements	1051
xlsread Enhancements	1052
xlsread Imported Date Format Changes	1053
format Options Added	1054
Nonscalar Arrays of Function Handles to Become Invalid	1055
Assigning Nonstructure Variables As Structures Displays Warning	1056
Function Declaration Compatibililty with Pre-R14 M-Files	1059
Graphics and 3-D Visualization	1060
imwrite Now Supports GIF Export	1061
Cannot Dock Figures on Macintosh	1062
Plotting Tools Not Working on Macintosh	1063
Not All Macintosh System Fonts Are Available	1064
XDisplay Property Setable on Motif-Based Systems	1065
Creating Graphical User Interfaces (GUIs)	1066
New Callbacks Chapter	1067
External Interfaces/API	1068
New File Archiving Functions and Functionality	1069

R2013a

Version: 8.1
New Features: Yes
Bug Fixes: Yes

Desktop


Option to add separators between controls on the quick access toolbar


You can now insert and move separator bars on the quick access toolbar. This helps to organize icons into groups. For information on how to customize and organize icons on the quick access toolbar, see “Access Frequently Used Features”.



Additional icon choices, auto-scaled thumbnails, and text-formatting options for customizing descriptions of MATLAB apps

When you package an app by clicking the **Package App** tab on the **Apps** tab, MATLAB® opens the Package app dialog box. In the **Describe your app** section of the dialog box, you can:

- Click the app icon , and then select a new icon from the display to represent your app in the Apps gallery.



- Use formatting options when writing the app description.
Options include: bold, italic, monospace, and hyperlinked text; bulleted and numbered lists; images.

In addition, MATLAB automatically scales the screenshot you provide when packaging. This screenshot appears in the tooltip MATLAB displays when hovering over an app icon in the App gallery. The screenshot is scaled to fit a 300 x 300 area and maintains its original aspect ratio.

For more information, see “Package Apps”.

Left-aligned table of contents for navigating in the Help browser and online Documentation Center

The documentation now includes a table of contents that can remain open and that does not overlap the content. View the table of contents by clicking the Contents icon on the left edge of the window.



Search term highlighting and content expansion in the Help browser

In the Help browser, search terms now appear highlighted when you view pages linked from the search results. If the search term occurs within a collapsed section on the page, the browser automatically expands the content.

For example, the reference page for the `publish` function includes the term `bmp` in collapsed content. When you search the documentation for `bmp`, and then select the `publish` reference page, the Help browser expands the relevant section on the page and highlights all occurrences of the term.

To clear highlights, press the **Esc** key.

Context menu items in Help and Web browsers for zooming, page navigation, and saving

Both the Help browser and the MATLAB Web browser now provide easy access to commonly used features in their context menus. Right-click within the browser to see the available options, which include zooming to change the font size, searching within a page, navigating back or forward, or saving the HTML to a file.

Note These context menu items are not available on Macintosh systems.

Removal of Handle Graphics support under `-nojvm` startup option

Compatibility Considerations: Yes

When you start MATLAB with the `-nojvm` startup option, Handle Graphics[®] functionality is not supported. (The `-nojvm` option is available for UNIX[®] platforms; see background information on the `matlab` (UNIX) reference page.)

Some aspects of MATLAB and related products use Handle Graphics in a way that might not be obvious. This includes anything that is based on or works using figures in MATLAB. Here is a summary of the affected features:

- Creating figures and performing plotting tasks, such as using the `plot`, `axes`, `getframe`, and `gcf` functions.
- Printing figures and using related functions such as `print`, `hgexport`, and `saveas`.
- Creating GUIs in MATLAB using GUI-building functions such as `warndlg`.
- Using Simulink[®] scopes and printing Simulink models.

If you use the `-nojvm` startup option and use Handle Graphics functionality, MATLAB produces an error.

Compatibility Considerations

To avoid the error, start MATLAB without the `-nojvm` startup option:

- If you have been using the `-nojvm` startup option to work in a command line environment or because you do not use the MATLAB desktop, use the `-nodesktop` startup option instead.
- If you have been using the `-nojvm` startup option because of memory or performance benefits, look for other ways to gain those improvements when you start MATLAB without the `-nojvm` option. See topics in “Performance and Memory”.
- If you want to continue to use the `-nojvm` startup option, remove the code that is now producing the warnings.

-noFigureWindows startup option suppresses figures on Linux and Mac platforms

When you start MATLAB with the -noFigureWindows startup option, MATLAB disables the display of figure windows.

No default keyboard shortcut for overwrite mode

Compatibility Considerations: Yes

There is no longer a default keyboard shortcut for Overwrite mode, and **OVR** no longer appears at the bottom right corner of the MATLAB status bar. Previously, the **Insert** key by default toggled between Insert and Overwrite modes in the Command Window and in the MATLAB Editor.

Compatibility Considerations

To enable Overwrite mode, assign a keyboard shortcut to this action. On the **Home** tab, in the **Environment** section, click **Preferences > Keyboard > Shortcuts**. Search or scroll to find the action name, **Toggle Insert/Overwrite Mode**, and assign a keyboard shortcut. Use this shortcut to toggle between Insert and Overwrite modes.

Support requests using prerelease versions

If you have Internet access, you can submit a technical support request to MathWorks® from MATLAB by selecting **Help > Request Support**. Previously, this feature was only available in the final version of each release. Beginning with R2013a, this feature is also available in the prerelease version.

Language and Programming

matlab.unittest package, an xUnit-style testing framework for the MATLAB language that allows writing and running unit tests, and analyzing test results

New MATLAB Unit Testing Framework (9 min, 24 sec)

For information about the matlab.unittest package, see “Unit Testing Framework”.

strsplit and strjoin functions for splitting and joining strings

The `strsplit` function splits a string into a cell array of strings. The `strjoin` function joins strings in a cell array into a single string.

Additional validateattributes options for checking array size and shape

The validateattributes function now checks the following attributes of input arrays.

Attribute	Description
'3d'	Array with three or fewer dimensions
'ndims', N	N-dimensional array
'square'	Square matrix
'diag'	Diagonal matrix

For more information, see the validateattributes reference page.

Help text for enumerations and events

The `help` and `doc` commands now display help text that you define for enumerations and events in custom classes. For more information, see “Create Help for Classes”.

Removal of support for .jar documentation files

The Help system no longer extracts documentation from .jar files. All custom documentation must be in uncompressed HTML files.

For more information, see “Display Custom Documentation”.

Changes to Microsoft .NET Framework support

Compatibility Considerations: Yes

As of R2013a, the MATLAB .NET interface requires the Microsoft® .NET Framework Version 4.0 and above. The interface continues to support assemblies built on Framework 2.0 and above.

Compatibility Considerations

You must have the .NET Framework Version 4.0 or above installed on your system. If you enter any `NET.` or `System.` commands on a machine without Framework 4.0, MATLAB displays a warning. To determine if your system has a supported framework, use the `NET.IsNETSupported` function.

Changes to compiler support for building MEX-files

Compatibility Considerations: Yes

MATLAB supports these new compilers for building MEX-files.

Microsoft Windows® platforms:

- Visual C++® 2012
- Intel® C++ XE 2013
- Intel Visual Fortran XE 2013

Mac OS X platforms:

- Apple Xcode 4.2 and higher with Clang

MATLAB no longer supports the following compiler on Mac OS X platforms:

- Xcode with gcc

Compatibility Considerations

To ensure continued support for building your MEX-files, consider upgrading to another supported compiler. For an up-to-date list of supported compilers, see the [Supported and Compatible Compilers Web page](#).

Changes to subclasses of built-in classes

Compatibility Considerations: Yes

Subclasses of built-in classes no longer inherit the following methods:

- ones
- zeros
- true
- false
- cast

As a result of this change, you cannot call these methods with an object of a built-in subclass. For example, given a class, `mySubclassOfDouble`, that derives from `double`, the following attempt to call `cast` results in an error:

```
a = mySubclassOfDouble(1);    % constructor
b = a.cast('int8');          % ok in R2012b but errors in R2013a
```

However, you can call the corresponding built-in functions with objects of the subclass. Use the function syntax instead of the method dot notation syntax:

```
b = cast(a, 'int8');
```

Compatibility Considerations

Change code that attempts to call these methods to call the built-in function instead. Use function syntax instead of dot notation, as described in the previous section.

Conversion of error and warning message identifiers

Compatibility Considerations: Yes

For R2013a, error and warning message identifiers have changed in MATLAB.

Compatibility Considerations

If you have scripts or functions that use message identifiers that changed, you must update the code to use the new identifiers. Typically, message identifiers are used to turn off specific warning messages, or in code that uses a try/catch statement and performs an action based on a specific error identifier.

For example, the `MATLAB:addtodate:Nargin` identifier has changed to `MATLAB:addtodatemx:Nargin`. If your code checks for `MATLAB:addtodate:Nargin`, you must update it to check for `MATLAB:addtodatemx:Nargin` instead. For a mapping of the new identifiers to the original identifiers, see Technical Support solution 1 - ERAFNC.

No strict-match requirements for month formats when converting date strings

Compatibility Considerations: Yes

When reading date strings, the date functions `datenum`, `datevec`, and `datestr` now treat months expressed as full names, three-letter abbreviations, or numbers in date string inputs interchangeably. In previous releases, the commands fail if a date string input does not match the format input. Using the `datestr` function to write date strings is not affected.

For example, consider the cell array of date strings, where each date string indicates the month in a different format:

```
mydates = {'31-October-2012', '31-Oct-2012', '31-10-2012'};
datevec(mydates, 'dd-mm-yyyy')
```

```
ans =
```

2012	10	31	0	0	0
2012	10	31	0	0	0
2012	10	31	0	0	0

Replacing the date string format input, `'dd-mm-yyyy'`, with `'dd-mmm-yyyy'` or `'dd-mmmm-yyyy'` returns the same output. Previously, the command failed, because the first two date strings include a full month name and a month abbreviation, which are not strict matches to the `mm` month format specified.

Compatibility Considerations

The date functions `datenum`, `datevec`, and `datestr` do not error when month formats are inconsistent across multiple date strings in a cell array of strings. When reading a cell array of date strings, you no longer can rely on using a format that includes a field for month name or abbreviation to catch date strings that specify a month number. You should ensure that all date strings in a cell array have the same format to avoid the possibility of confusing day and month numbers. For example,

```
mydates = {'11-Oct-2012', '11-10-2012'};
datevec(mydates, 'dd-mmm-yyyy')
```

```
ans =
```

```
      2012      10      11      0      0      0
      2012      10      11      0      0      0
```

In R2013a, both dates are silently interpreted as October 11, 2012 although you might have intended '11-10-2012' to be in month-day-year format, representing November 10, 2012.

Date functions error on out-of-range quarter values

Compatibility Considerations: Yes

Valid values for quarter formats are Q1 through Q4 when converting date strings using the `datenum` or `datevec` functions. Values outside this range throw an error. Previously, the date functions accepted values outside the range, such as Q5, but returned incorrect results.

Compatibility Considerations

To prevent errors when parsing quarter values, remove values outside the valid range (Q1 through Q4) from your code.

String representations of large integers using exponential notation

Compatibility Considerations: Yes

The `num2str` function converts any large floating-point number that loses precision due to hardware limitations to a string representation that uses exponential notation. Such floating-point numbers are those greater than `flintmax`. Previously, `num2str` returned a string representation in decimal notation.

This change in behavior affects only the syntax `str = num2str(x)`. The following example compares the output of `num2str` in R2013a to R2012b.

R2013a	R2012b
<pre>num2str(30e+25) ans = 3e+26</pre>	<pre>num2str(30e+25) ans = 30000000000000000000000000000000</pre>

Compatibility Considerations

To obtain a string representation of large integers that uses decimal notation, call `int2str(x)` instead of `num2str(x)`.

Do not use classpath.txt file to modify Java static path

Compatibility Considerations: Yes

As of R2012b, the file `classpath.txt` is no longer used to add custom paths to the static Java® class path. A new MathWorks product installation rewrites the static class path (found in the `classpath.txt` file).

Compatibility Considerations

To modify the Java class path, create `javaclasspath.txt` or `javalibrarypath.txt` files. For more information, see “The Static Path” and “Locating Native Method Libraries”.

Functionality being removed or changed

Compatibility Considerations: Yes

Functionality	What Happens When You Use This	Use This Instead	Compatibility Considerations
createCopy method of inputParser class	Warns	copy	Replace all instances of createCopy with copy.
hostid	Warns		See Solution 1–171PI on the MathWorks website for instructions on obtaining your hostid.

Mathematics

scatteredInterpolant and griddedInterpolant support for extrapolation

Compatibility Considerations: Yes

- `scatteredInterpolant` is a new class for interpolating scattered data, and it returns extrapolated values by default when you evaluate at query points outside the convex hull.
- `griddedInterpolant` now returns extrapolated values by default when you evaluate at query points outside the domain of your sample grid.

Compatibility Considerations

`scatteredInterpolant` supports extrapolation by default. This behavior is different from that of `TriScatteredInterp`, which returns NaN when you evaluate at query points outside the convex hull using the 'linear' or 'natural' methods. To preserve the `TriScatteredInterp` behavior, set the `ExtrapolationMethod` property to 'none'. See the `scatteredInterpolant` reference page for more information.

`griddedInterpolant` previously returned NaN values when you queried points outside the domain of the sample points using the 'linear', 'cubic' or 'nearest' interpolation methods. Now all interpolation methods support extrapolation by default. To preserve the old behavior, set the `ExtrapolationMethod` property to 'none' when the interpolation method is 'linear', 'cubic' or 'nearest'. See the `griddedInterpolant` reference page for more information.

Syntax for ones, zeros, and other functions for creating arrays that match attributes of an existing variable

The functions `ones`, `zeros`, `eye`, `Inf`, `NaN`, `true`, `false`, and `cast` now can return an output that matches the data type, sparsity, and complexity (real or complex) of a variable `p`.

For example:

```
p = uint8([1 2]);  
X = ones(2,3,'like',p);  
class(X)
```

```
ans =
```

```
uint8
```

Integer type support for prod, cumsum, cumprod, median, mode, and number theory functions

The following functions now support inputs of any integer data type: median, mode, prod, cumprod, cumsum, isprime, primes, factor, gcd, lcm, perms, factorial, nextpow2, and nchoosek.

flintmax function for largest consecutive integer in floating-point format

Largest consecutive integer in floating-point format. `flintmax` returns the largest consecutive integer in IEEE® double precision, which is 2^{53} . Above this value, double-precision format does not have integer precision, and not all integers can be represented exactly. `flintmax('single')` returns the largest consecutive integer in IEEE single precision, which is `single(2^24)`.

Scale option for airy function

`scale` is an optional flag you can pass to `airy` to scale the resulting Airy function. See the `airy` reference page for more information.

scatteredInterpolant class that replaces TriScatteredInterp

Compatibility Considerations: Yes

TriScatteredInterp will be removed in a future release. Use the new scatteredInterpolant class instead. The scatteredInterpolant class performs interpolation on 2-D and 3-D scattered data with support for extrapolation outside the convex hull of the sample points. scatteredInterpolant also supports queries in grid vector format to conserve memory.

Compatibility Considerations

- scatteredInterpolant supports extrapolation by default. This behavior is different from that of TriScatteredInterp, which returns NaN when you evaluate at query points outside the convex hull using the 'linear' or 'natural' methods. To preserve the TriScatteredInterp behavior, set the ExtrapolationMethod property to 'none'. See the scatteredInterpolant reference page for more information.
- scatteredInterpolant does not accept input of type DelaunayTri. Use nearestNeighbor or pointLocation to interpolate using a specific Delaunay triangulation. See “Interpolation Using a Specific Delaunay Triangulation” for more information.
- The scatteredInterpolant Points property is the array of sample point coordinates. The corresponding TriScatteredInterp property is called X. Use the Points property to refer to the sample points when you update your code.

triangulation class to replace TriRep

Compatibility Considerations: Yes

TriRep will be removed in a future release. Use the new triangulation class instead. The triangulation class represents 2-D and 3-D triangulations using a similar form and syntax as TriRep.

Compatibility Considerations

The property names and some method names have changed. The tables below map the current TriRep properties and methods to the triangulation replacements. Each replacement property has the same shape and holds the same values as the corresponding TriRep property. Similarly, each replacement method has the same syntax and returns the same result as the corresponding TriRep method.

Replacements for TriRep Properties

TriRep Property	Replacement triangulation Property	Name Change
X	Points	✓
Triangulation	ConnectivityList	✓

Replacements for TriRep Methods

TriRep Method	Replacement triangulation Method	Name Change
baryToCart	barycentricToCartesian	✓
cartToBary	cartesianToBarycentric	✓
circumcenters	circumcenter	✓
edgeAttachments	edgeAttachments	
edges	edges	
faceNormals	faceNormal	✓
featureEdges	featureEdges	

TriRep Method	Replacement triangulation Method	Name Change
freeBoundary	freeBoundary	
incenters	incenter	✓
isEdge	isConnected	✓
neighbors	neighbors	
size	size	
vertexAttachments	vertexAttachments	

deLaunayTriangulation class to replace DelaunayTri **Compatibility Considerations: Yes**

DelaunayTri will be removed in a future release. Use the new deLaunayTriangulation class instead. deLaunayTriangulation represents 2-D and 3-D Delaunay triangulations using a similar form and syntax as DelaunayTri.

Compatibility Considerations

Some of the property and method names have changed. The tables below map the current DelaunayTri properties and methods to the deLaunayTriangulation replacements. Each replacement property has the same shape and holds the same values as the corresponding DelaunayTri property. Similarly, each replacement method has the same syntax and returns the same result as the corresponding DelaunayTri method.

Replacements for DelaunayTri Properties

DelaunayTri Property	Replacement deLaunayTriangulation Property	Name Change
Constraints	Constraints	
X	Points	✓
Triangulation	ConnectivityList	✓

Replacements for DelaunayTri Methods

DelaunayTri Method	Replacement deLaunayTriangulation Method	Name Change
convexHull	convexHull	
inOutStatus	isInterior	✓
nearestNeighbor	nearestNeighbor	

DelaunayTri Method	Replacement delaunayTriangulation Method	Name Change
pointLocation	pointLocation	
voronoiDiagram	voronoiDiagram	

Set functions behavior change

Compatibility Considerations: Yes

The behavior of `unique`, `union`, `intersect`, `setdiff`, `setxor`, and `ismember` has changed.

- If there are repeated elements in the input arrays, the functions `unique`, `union`, `intersect`, `setdiff`, and `setxor` return the index to the first occurrence of the repeated elements (or rows).
- The optional output array, `locb`, returned by `ismember`, contains the lowest absolute indices in `B` for elements (or rows) that are also in `A`.
- All index vectors returned by `unique`, `union`, `intersect`, `setdiff`, or `setxor` are column vectors.
- The shape of the output, `C`, from `intersect`, `setxor`, and `union`, when the `'rows'` and `'legacy'` flags are not specified, is as follows. `C` is column vector unless both `A` and `B` are row vectors, in which case `C` is a row vector.
- The shape of the output, `C`, from `setdiff`, when the `'rows'` and `'legacy'` flags are not specified, is as follows. `C` is a row vector if `A` is a row vector. Otherwise, `C` is a column vector.
- `unique`, `union`, `intersect`, `setdiff`, `setxor`, and `ismember` support objects.
- The input arrays passed to `union`, `intersect`, `setdiff`, `setxor`, and `ismember` must be of the same class with the following exceptions:
 - Logical, `char`, and all numeric classes can combine with double arrays.
 - Cell arrays of strings can combine with `char` arrays.
- `ismember` treats trailing white space in cell arrays of strings as distinct characters. For example, `'word'` is different from `'word '`. If the `'legacy'` flag is specified, `ismember` ignores trailing white space and treats `'word'` the same as `'word '`.

Compatibility Considerations

If the changes adversely affect your code, you can specify `'legacy'` to preserve the behavior from R2012b and prior releases. For example:

```
[C,IA,IC] = unique([9 9 1])
```

```
C =
```

```
    1    9
```

```
IA =
```

```
    3  
    1
```

```
IC =
```

```
    2  
    2  
    1
```

```
[C2,IA2,IC2] = unique([9 9 1], 'legacy')
```

```
C2 =
```

```
    1    9
```

```
IA2 =
```

```
    3    2
```

```
IC2 =
```

```
    2    2    1
```


Functionality being removed or changed

Compatibility Considerations: Yes

Functionality	What Happens When You Use This Functionality	Use This Instead	Compatibility Considerations
quad	Still runs	integral	<p>Replace all instances of quad with integral.</p> <p>For example, replace <code>q = quad('x.*cos(x)',0,1)</code> with <code>q = integral(@(x)x.*cos(x),0,1)</code>.</p> <p>If quad uses an absolute error tolerance, <code>tol</code>, replace all instances of the tolerance argument with the 'AbsTol' or 'RelTol' name-value pair arguments.</p> <p>For example, replace <code>q = quad(fun,a,b,tol)</code> with <code>q = integral(fun, a, b, 'AbsTol', tol, 'RelTol', tol)</code>.</p>
quadl	Still runs	integral	<p>Replace all instances of quadl with integral.</p> <p>For example, replace <code>q = quadl('x.*cos(x)',0,1)</code> with <code>q = integral(@(x)x.*cos(x),0,1)</code>.</p> <p>If quadl uses an absolute error tolerance, <code>tol</code>, replace all instances of the tolerance argument</p>

Functionality	What Happens When You Use This Functionality	Use This Instead	Compatibility Considerations
			<p>with the 'AbsTol' or 'RelTol' name-value pair arguments.</p> <p>For example, replace <code>q = quad1(fun,a,b,tol)</code> with <code>q = integral(fun, a, b, 'AbsTol', tol, 'RelTol', tol)</code>.</p>
quadv	Still runs	integral with the 'ArrayValued', true name-value pair argument	Replace all instances of quadv with integral using the 'ArrayValued', true name-value pair argument.
dblquad	Still runs	integral2	<p>Replace all instances of dblquad with integral2.</p> <p>If there are discontinuities in the interior of the region of integration, replace dblquad with integral2 using the 'method', 'iterated' name-value pair argument.</p>

Functionality	What Happens When You Use This Functionality	Use This Instead	Compatibility Considerations
triplequad	Still runs	integral3	<p>Replace all instances of triplequad with integral3.</p> <p>If there are discontinuities in the interior of the region of integration, replace triplequad with integral3 using the 'method', 'iterated' name-value pair argument.</p>
bitmax	Still runs	flintmax	Replace all instances of bitmax with flintmax.
TriRep	Still runs	triangulation	<p>Replace all instances of TriRep with triangulation. Most of the triangulation properties and methods are the same as those in TriRep, but there are a few exceptions. See “triangulation class to replace TriRep” on page 35 for details.</p>

Functionality	What Happens When You Use This Functionality	Use This Instead	Compatibility Considerations
DelaunayTri	Still runs	delaunayTriangulation	Replace all instances of DelaunayTri with delaunayTriangulation. Most of the delaunayTriangulation properties and methods are the same as those in DelaunayTri, but there are a few exceptions. See “delaunayTriangulation class to replace DelaunayTri” on page 37 for details.
TriScatteredInterp	Still runs	scatteredInterpolant	Replace all instances of TriScatteredInterp with scatteredInterpolant. See “scatteredInterpolant class that replaces TriScatteredInterp” on page 34 for compatibility details.
inline	Still runs	Anonymous function	Replace all instances of inline with an anonymous function. See “Anonymous Functions” for more information. You can use symvar and func2str to convert your existing code.

Functionality	What Happens When You Use This Functionality	Use This Instead	Compatibility Considerations
rand or randn with the 'seed', 'state' or 'twister' inputs.	Still runs	rng	For more information about updating your code and assessing the impact of this change, see “Updating Your Random Number Generator Syntax”.
permute(A,order) where order contains noninteger or complex values.	Warns	Real, positive integer values for order	Replace all instances of noninteger or complex valued inputs with real, positive integer values. You can use round or real for this conversion.
Noninteger valued size inputs for zeros, ones, eye, Inf, NaN, true, false, rand, randi, randn, and cell	Warns	Integer valued size inputs	Replace all instances of noninteger valued size inputs with integer valued size inputs for zeros, ones, eye, Inf, NaN, true, false, rand, randi, randn, and cell. You can use floor for this conversion.
cholinc(X,'inf')	Errors	None	Remove all instances of cholinc(X,'inf') from your code.
All other syntaxes of cholinc except cholinc(X,'inf')	Errors	ichol	Replace these instances of cholinc with ichol.
luinc	Errors	ilu	Replace all instances of luinc with ilu.

Functionality	What Happens When You Use This Functionality	Use This Instead	Compatibility Considerations
<code>sparse(A)</code> <code>sparse(i,j,s,...)</code> where A and s are of type char.	Errors	<code>sparse(double(A))</code> <code>sparse(i,j,double(s),...)</code>	Convert all char inputs to double before calling <code>sparse</code> .
<code>RandnAlg</code> property of <code>RandStream</code> class	Errors	<code>NormalTransform</code> property of <code>RandStream</code> class	Replace all existing instances of <code>RandnAlg</code> with <code>NormalTransform</code> .
<code>setDefaultStream</code> method of <code>RandStream</code> class	Errors	<code>setGlobalStream</code> method of <code>RandStream</code> class	Replace all existing instances of <code>RandStream.setDefaultStream</code> with <code>RandStream.setGlobalStream</code> .
<code>getDefaultStream</code> method of <code>RandStream</code> class	Errors	<code>getGlobalStream</code> method of <code>RandStream</code> class	Replace all existing instances of <code>RandStream.getDefaultStream</code> with <code>RandStream.getGlobalStream</code> .

Graphics

gobjects function for preallocating graphics handle array

The `gobjects` function creates an array of graphics handles. Use this function instead of the `ones` or `zeros` function when preallocating an array to store graphics handles.

Functionality being removed or changed

Compatibility Considerations: Yes

Functionality	What Happens When You Use This	Use This Instead	Compatibility Considerations
Figure DoubleBuffer property	No effect	No replacement needed	On older computer systems, was used to produced flash-free graph animations.
Use of <code>ginput</code> when MATLAB is started with the <code>noFigureWindow</code> or <code>nodisplay</code> flag	Errors	Not applicable	Do not use <code>ginput</code> when you start MATLAB with the <code>noFigureWindows</code> or <code>nodisplay</code> flags.
Use of graphics format extensions <code>ai</code> or <code>ill</code> with <code>saveas</code>	Warns	No replacement	Remove all instances of <code>saveas</code> with the <code>ai</code> or <code>ill</code> extensions.
Use of <code>all</code> option with <code>hgsave</code> or <code>hgload</code>	Warns	No replacement	Remove all instances of passing <code>all</code> to <code>hgsave</code> or <code>hgload</code> .
Use of <code>getframe</code> with second input argument that specifies an area not contained in figure window	Warns	No replacement	If using a second input argument with <code>getframe</code> , then specify an area fully contained in figure window.
Use of <code>-dsetup</code> option with <code>print</code> to display the Windows Print Setup dialog	Warns	No replacement	Remove all instances of <code>-dsetup</code> . For the current figure, click File > Print in the Figure window to display the Print Setup dialog.

Data Import and Export

Reading and writing indexed and grayscale AVI files with VideoReader and VideoWriter objects

Compatibility Considerations: Yes

The `VideoReader.read` method now returns an array of grayscale data when reading grayscale AVI files. The `read` method also reads AVI files with indexed video and a colormap using the new 'native' input argument.

The `VideoWriter.writeVideo` method now writes grayscale AVI files, and AVI files with indexed video and a colormap.

Compatibility Considerations

A `VideoReader` object created from an AVI file with indexed video and a grayscale colormap now has a `VideoFormat` property with the value 'Grayscale'. By default, using the `VideoReader.read` method to read this object returns an `m-by-n-by-1-by-F` array, where `m` is the image frame height, `n` is the image frame width, and `F` is the number of frames read. In R2012b and earlier releases, the value of `VideoFormat` was 'RGB24' and read by default returned an `m-by-n-by-3-by-F` array.

Writing MPEG-4 H.264 files on Mac with VideoWriter object

VideoWriter now writes MPEG-4 H.264 files with the extension `.mp4` or `.m4v` on systems with Mac OS X 10.7 or later.

Tiff object improvements for reading and writing RGB-class TIFF images

The `Tiff.readRGBAImage` method returns RGBA data from an entire RGB-compatible image. The `Tiff.readRGBAStrip` and `Tiff.readRGBATile` methods return RGBA data from a single strip or a single tile in an RGB-compatible image, respectively.

The `JPEGColorMode` property for Tiff objects controls YCbCr/RGB conversion when writing YCbCr images. For more information, see the [Tiff reference page](#).

Importing non-ASCII encoded files with textscan function

The `textscan` function now reads text files with non-ASCII encodings. For a complete list of supported encoding schemes and the syntax for specifying the encoding, see the `fopen` reference page.

Multichannel JP2 support in `imread` function

Compatibility Considerations: Yes

By default, when reading JP2 files, the `imread` function now returns all image channels in the order in which they exist in the codestream. In R2012b and earlier releases, `imread` read up to 3 channels only.

Compatibility Considerations

The default syntax of `imread` no longer reorders the channels of a JP2 image where the channels are out of order. To reorder the channels, call `imread` with the `'V79Compatible'` name-value pair argument.

Previous behavior change of xlsread function output

Compatibility Considerations: Yes

In R2011b and earlier, the `xlsread` function returned columns of empty strings, ' ', in the text data output, where there were leading columns of numeric data preceding text data. As of R2012a, on systems with Excel® for Windows, these columns of empty strings are trimmed from the text data output.

Compatibility Considerations

This change in behavior affects file reading on systems with Excel for Windows, when calling `xlsread` without the 'basic' argument. For example, given a file, `myfile.xls`, where Sheet1 contains the following data:

```
1 1 1 A A
2 2 2 B B
3 3 3 C C
4 4 4 D D
5 5 5 E E
```

Calling `[num,txt] = xlsread('myfile.xls','Sheet1')` on systems with Excel for Windows returns:

```
num =
     1     1     1
     2     2     2
     3     3     3
     4     4     4
     5     5     5

txt =
     'A'     'A'
     'B'     'B'
     'C'     'C'
     'D'     'D'
     'E'     'E'
```

In R2011b and earlier, the command returned:


```
num =
```

```
    1    1    1
    2    2    2
    3    3    3
    4    4    4
    5    5    5
```

```
txt =
```

```
'' '' '' 'A' 'A'
'' '' '' 'B' 'B'
'' '' '' 'C' 'C'
'' '' '' 'D' 'D'
'' '' '' 'E' 'E'
```

When reading XLS files, you can use the 'basic' flag to reproduce the pre-R2012a output:

```
[num,txt] = xlsread('filename.xls',Sheet, '', 'basic');
```

Authentication, user name, and password inputs for `urlread` and `urlwrite` functions

The `urlread` and `urlwrite` functions accept the following optional name-value pair arguments.

Attribute	Value
Authentication	HTTP authentication mechanism. Currently, only basic authentication is supported.
Username	User identifier.
Password	User authentication string.

Additional audio and video file reading capabilities using Import Wizard and importdata function

The Import Wizard and the `importdata` function now import all audio file formats supported by the `audioread` function, including WAV, FLAC, and OGG files on all platforms, and MP3 and MPEG-4 AAC files on Windows 7 (or later), Macintosh, and Linux® platforms.

The Import Wizard and the `importdata` function now import all video file formats supported by the `VideoReader` class.

sound function nonblocking

Compatibility Considerations: Yes

The sound function now returns immediately. In R2012b and earlier releases, sound blocked until all audio played back.

Compatibility Considerations

To play audio with blocking, use `playblocking(audioplayer(y,Fs))` instead of `sound(y,Fs)`.

Functionality being removed or changed

Compatibility Considerations: Yes

Functionality	What Happens When You Use This Functionality?	Use This Instead	Compatibility Considerations
<code>aufinfo</code>	Still runs	<code>audioinfo</code>	Replace all instances of <code>aufinfo</code> with <code>audioinfo</code> .
<code>auread</code>	Still runs	<code>audioread</code>	Replace all instances of <code>auread</code> with <code>audioread</code> .
<code>auwrite</code>	Still runs		Write audio files using <code>audiowrite</code> .
<code>wavfinfo</code>	Still runs	<code>audioinfo</code>	Replace all instances of <code>wavfinfo</code> with <code>audioinfo</code> .
<code>wavread</code>	Still runs	<code>audioread</code>	Replace all instances of <code>wavread</code> with <code>audioread</code> .
<code>wavwrite</code>	Still runs	<code>audiowrite</code>	Replace all instances of <code>wavwrite</code> with <code>audiowrite</code> .
<code>cdfwrite</code>	Still runs		Write Common Data Format (CDF) files using the <code>cdflib</code> low-level functions.
<code>hdftool</code>	Still runs		Read data from HDF files using <code>hdfread</code> or the low-level functions in the <code>matlab.io.hdf4.sd</code> , <code>matlab.io.hdfeos.gd</code> , and <code>matlab.io.hdfeos.sw</code> packages.

Performance

fft function performance improvements on computers with new Intel and AMD processors

The fft function performance improves on computers with Intel and AMD® processors supporting the AVX instruction set.

permute function performance improvements for 3-D and higher dimensional arrays

The permute function performance improves for 3-D and higher dimensional arrays.


R2012b

Version: 8.0
New Features: Yes
Bug Fixes: Yes


Desktop

Toolstrip that replaces menus and toolbars in MATLAB Desktop


New MATLAB Desktop (5 min, 3 sec)



- The Toolstrip contains components that were previously available in menus, toolbars, and the **Start** button. Tabs such as **Home**, **Plots**, **Apps**, **Editor**, and **Variable**, group functionality to support common tasks.
- The **Apps** tab contains a gallery of apps from the MATLAB family of products. You also can install your own apps, which appear in the apps gallery.
- The quick access toolbar contains frequently used options such as cut, copy, paste. The quick access toolbar is customizable; you can add items from tabs or from command shortcuts you create. You can also change the position of the toolbar on the Desktop.



- The current folder toolbar enables you to control the current working directory. The location and the controls available are customizable.



- The **Search Documentation** box enables you to search the documentation for functions and other topics of interest.

Search Documentation 

Apps gallery that presents apps from the MATLAB product family

The MATLAB desktop contains a gallery of apps from the MATLAB family of products. You can also install your own apps, which appear in the apps gallery.

- To access the apps gallery, on the desktop Toolstrip, click the **Apps** tab, and then, on the far right of the **Apps** section, click the arrow ▾.
- To find and install apps written by others, click the **Apps** tab, and in the **File** section, click **Get More Apps**.

Single-file application packaging as a MATLAB App Installer file for inclusion in the apps gallery

Packaging and Installing MATLAB Apps (2 min, 58 sec)

You can package your GUI as a single installer file that contains all of the code and data needed to run your app, as well as a description of your app. Share your app with others by uploading the installer file to File Exchange or sending it as an email attachment. When your app installs, it appears alongside apps from the MathWorks family of products in the apps gallery. For more information, see “Package Apps”.

Redesigned Help with improved browsing, searching, and filtering

Compatibility Considerations: Yes


Redesigned Help (5 min, 43 sec)

Searching and navigation

The R2012b release includes a redesigned documentation system with streamlined product pages, detailed search suggestions, and enhanced filtering of search results.


Each product's documentation is now organized by categories of functionality, such as Graphics or Simulation, rather than by information type, such as Function Reference or User's Guide. Categories include links to related reference pages, examples, and conceptual topics, allowing you to browse from one to another.

Most features of the previous Help browser are available in the new browser, although some functionality has a different appearance or location. For example:

- The table of contents for each product is collapsed by default to maximize the space available for reading topics. Expand the table of contents from any page in the Help browser by clicking the Table of Contents button, .
- Links to alphabetical lists of reference pages, such as functions or blocks, appear at the bottom of each product page.
- Tasks previously performed using menu items in the Help browser, such as setting preferences or viewing page locations, are now accessible via context (right-click) menus, keyboard shortcuts, or toolbar buttons.

Note On Macintosh systems, there are no context menu items for **Evaluate Selection** or **Get Page Address**. You can copy selected code to the Command Window for evaluation by pressing **Shift+F7**. However, in this release, there is no way to identify the page address.

- Demos are now labeled *Examples*, and are accessible from the top of each product page. When you select video examples, they open in your system Web browser.



- All release notes for a product appear on the same page, allowing you to track changes across several releases from a single location.

The new Help browser is used exclusively for the documentation of MathWorks products. As a result:

- The `web` command opens all pages that are not part of the documentation in the MATLAB Web browser, even when you specify the `-helpbrowser` option. Because this is the default behavior of the `web` command, the `-helpbrowser` option has been removed from the documentation.
- When the `doc` command does not find a documentation page, but does find associated help text, it displays the text in the MATLAB Web browser rather than the Help browser.
- Custom documentation and documentation for downloadable or third-party products displays in a separate browser. To access this browser, open the Help browser and navigate to the documentation home page. Then, at the bottom of the page, click **Supplemental Software**.

Font size in Help browser and Web browser

The Help browser and Web browser now allow you to zoom in and out to adjust the font size by pressing **Ctrl** and **+** or **-**.

In-product access to online documentation

From within the product, you can access either the installed documentation or the documentation on the Web. By default, your Help preference is set to

view the installed documentation. If you change the preference to view the Web documentation, then you can choose to view documentation for products that you do not have installed.

Searches using the doc command

In previous releases, if you passed a term to the doc command that did not correspond to the name of a MathWorks reference page or to a file with help text, the doc command issued an error. Now, the doc command searches the documentation for the term, and displays the search results in the Help browser.

Improved rendering in Help browser and Web browser

The new Help browser uses a different rendering engine than the previous Help browser. This engine provides improved legibility, particularly on Microsoft Windows 64-bit systems.

The MATLAB Web browser also uses this rendering engine on all platforms. In previous releases, the Web browser used this engine only on Microsoft Windows systems.

This rendering engine is not fully supported on Red Hat® 5 operating systems, so not all Help features are available on those systems. For example:


- Search suggestions are available from the search bar in the desktop, but not within the Help browser.
- Some components of the search results page are not available, such as filtering.
- The Help browser can display installed product documentation, but not the documentation on the Web.

Compatibility Considerations

- The Help system now requires that custom documentation files reside outside the matlabroot folder (but on the MATLAB search path). To view any installed custom documentation, open the Help browser and navigate to the documentation home page. Then, at the bottom of the page, click **Supplemental Software**.

- The `demo` command no longer supports categories of MATLAB or Simulink examples.
- For some products (primarily third-party toolboxes), the `demo` command requires different input values to specify the product type or name. The `demo` command now identifies each product using its `info.xml` file rather than its `demos.xml` file. For most MathWorks products, the product information is the same in both files.
- In a future release, MathWorks will remove support for `demos.m` files, an old way to include demos in the Help browser. For the recommended method, see “Display Custom Examples”.

Viewing of multiple documentation pages simultaneously with tabbed browsing

The Help browser now allows you to open multiple tabs so that you can view more than one documentation topic at a time. Open a new tab by clicking the New Tab button, , or by right-clicking a link.

Suggested corrections for mistyped functions and variables in the Command Window

Command Window Suggestions for Mistyped Functions and Variables (2 min, 1 sec)

MATLAB can show suggestions in the Command Window for misspelled functions and variable names. If you enter an undefined function or variable name, MATLAB displays:

Did you mean:

followed by a suggested command at the command line. You can press **Enter** to execute that command, or **Esc** to delete the suggestion.


Full-screen view mode on Mac operating systems

MATLAB can operate in full-screen mode on Mac OS X 10.7 Lion.

Changes to `-nojvm` startup option on Mac

When you start MATLAB on a Mac with the `-nojvm` startup option, Handle Graphics functionality is no longer supported. MATLAB will produce an error. Previous to this release, calls to Handle Graphics functionality would work but generate a warning. (For more information about the `-nojvm` option, see the `matlab (UNIX)` reference page.)


Tabs in MATLAB Web browser

The MATLAB Web browser now allows you to open multiple tabs so that you can view multiple reports or Web sites simultaneously. Open a new tab by clicking the New Tab button, .

Direct access to run configurations from the Run button

Compatibility Considerations: Yes

Now you can type commands directly using the **Run** options on the **Editor** tab.



In previous versions, you accessed run configurations by clicking the **Run** button down arrow and selecting **Edit Run Configurations for *filename***.

Compatibility Considerations

MATLAB R2012b does not automatically copy run configurations from versions prior to R2012b. To transfer run configurations from a release prior to the MATLAB R2012b installation:

- 1 Open `prefdir\run_configurations.m`. To identify your preference directory, type `prefdir` in the Command Window.


Run configuration entries appear similar to this example:


```
%% @name foo
% @associatedFile C:\Documents\MATLAB\work\foo.m
% @mostRecentlyActioned true
% @uniqueId 695644b0:1355f0bb372:-7fb0

% Modify expression to add input arguments.
% Example:
%   a = [1 2 3; 4 5 6];
```



```
% foo(a);  
foo(1,2)
```

- 2** Copy the MATLAB command in the run configuration. In the example configuration, the command is `foo(1,2)`.
- 3** Open the MATLAB file associated with the run configuration that you want to keep. In the example configuration, the file is `C:\Documents\MATLAB\work\foo.m`.
- 4** Click  and then the field containing type code to run.
- 5** Paste the MATLAB command.

If the MATLAB expression spans multiple lines, create a script, and copy and paste the code into the script. You can then run the script directly using .

Multiple vector creation from single selection in Variables editor

The Variables editor now allows you to create one or more new row or column vectors from a single selection within an existing variable. The names of the new variables are based on the name of the existing variable. Previously, the Variables editor could only create a new array from a single selection, and new variables were called unnamed, unnamed1, ..., unnamedN.

Language and Programming

Abstract attribute for declaring MATLAB classes as abstract

Declare MATLAB classes as abstract by setting the class `Abstract` attribute. See “Defining Abstract Classes” for more information.

Diagnostic message improvements when attempting to create an instance of an abstract class

Attempting to instantiate an abstract class returns a list of abstract members and their defining classes in the error diagnostic message. The `meta.abstractDetails` function finds abstract members defined or inherited by abstract classes.

Handle and dynamicprops do not support the empty static method

Compatibility Considerations: Yes

For R2012b, the `handle` and `dynamicprops` classes no longer support the empty static method. This change makes these classes consistent with all MATLAB abstract classes.

Compatibility Considerations

MATLAB software issues an error for calls to the empty static method from the `handle` and `dynamicprops` classes:

```
% Will return errors  
handle.empty  
dynamicprops.empty
```

See “Creating Empty Arrays” for information on using `empty`.

Switch uses eq to compare enumerations

Compatibility Considerations: Yes

Switch statements use the enumeration `eq` method to compare the switch expression with the `case` expression (see `switch`). In previous releases, `switch` used a special comparison that required the result of both expressions to belong to the same enumeration class. The result of the comparison is determined by the result of:

```
switch_expression == case_expression
```

The new behavior is consistent with that of other conditional statements, such as `if` statements.

Compatibility Considerations

Code that uses enumerations in `switch` statements can behave differently in release R2012b than in a previous release.

Cannot specify property attributes multiple times

Compatibility Considerations: Yes

Classes can define a property attribute only once in a properties block. Defining the same attribute more than once in a properties block causes an error when the class is instantiated.

Compatibility Considerations

Classes that define the same property attribute multiple times in a properties block will error when attempting to instantiate the class. Previously, MATLAB evaluated property attribute specifications in right to left order.

Discontinued compiler support for building MEX-files

Compatibility Considerations: Yes

MATLAB no longer supports the following compilers on Linux 32-bit platforms:

- GNU® gcc Version 4.4.x
- GNU gfortran 4.3.x

Compatibility Considerations

To ensure continued support for building your MEX-files, consider upgrading to another supported compiler. For an up-to-date list of supported compilers, see the [Supported and Compatible Compilers Web page](#).

Jagged array support for .NET

- To create a .NET jagged array, use the `NET.createArray`.
- To convert a .NET jagged array to a MATLAB array, see “How MATLAB Handles Jagged Arrays”.
- To convert a MATLAB array to a .NET jagged array, see “Pass MATLAB Arrays as Jagged Arrays”.

MATLAB does not support:

- Autoconversion of char or cell arrays to jagged array arguments. For more information, see “Call .NET Method with System.String Jagged Array Arguments”.
- Autoconversion of MATLAB arrays to multidimensional jagged array arguments. For more information, see “Call .NET Method with Multidimensional Jagged Array Arguments”.

Java exceptions accessible to MATLAB code

If you call a Java method from MATLAB, and that code throws an exception, use the `matlab.exception.JavaException` class to handle the exception in MATLAB.

Ability to add jar files to static Java class path

To use third-party Java libraries in MATLAB, you can control the Java class path and native library path by creating `javaclasspath.txt` and `javalibrarypath.txt` files. For more information, see “The Static Path” and “Locating Native Method Libraries”.

Preservation of string functions for backwards compatibility

The R2010a Release Notes originally stated that the `isstr`, `setstr`, `str2mat`, `stread`, `strvcat`, and `textread` functions would be removed in a future release. As of R2012b, there are no plans to remove these functions. However, use of these functions is not recommended.

Function	Recommended Modification
<code>isstr</code>	Replace all existing instances of <code>isstr</code> with <code>ischar</code> .
<code>setstr</code>	Replace all existing instances of <code>setstr</code> with <code>char</code> .
<code>str2mat</code>	Replace all existing instances of <code>str2mat</code> with <code>char</code> .
<code>stread</code>	<p>Replace all existing instances of <code>stread</code> with <code>textscan</code>. For example, replace</p> <pre>[a,b,c] = stread(...)</pre> <p>with</p> <pre>C = textscan(...) [a,b,c] = deal(C{:})</pre> <p>Unlike <code>stread</code>, the <code>textscan</code> function converts numeric values to the specified data type, allowing preservation of integer types.</p>
<code>strvcat</code>	Replace all existing instances of <code>strvcat</code> with <code>char</code> . Unlike <code>strvcat</code> , the <code>char</code> function does <i>not</i> ignore empty strings.
<code>textread</code>	Replace all existing instances of <code>textread</code> with <code>textscan</code> , similar to <code>stread</code> . Open and close files with <code>fopen</code> and <code>fclose</code> .

Conversion of Error and Warning Message Identifiers

Compatibility Considerations: Yes

For R2012b, error and warning message identifiers have changed in MATLAB.

Compatibility Considerations

If you have scripts or functions that use message identifiers that changed, you must update the code to use the new identifiers. Typically, message identifiers are used to turn off specific warning messages, or in code that uses a try/catch statement and performs an action based on a specific error identifier.

For example, the `MATLAB:uitable:InvalidParent` identifier has changed to `MATLAB:uitable:ParentMustBeFigureOrUIContainer`. If your code checks for `MATLAB:uitable:InvalidParent`, you must update it to check for `MATLAB:uitable:ParentMustBeFigureOrUIContainer` instead. For a mapping of the new identifiers to the original identifiers, see Technical Support solution 1-ERAFNC.

Mathematics

Performance improvements and multithreading for airy, psi, and Bessel functions

The following functions show improved performance: `besselh`, `besseli`, `besselj`, `besselk`, `bessely`, `airy`, and `psi`.

ddensd function that solves delay differential equations of neutral type with state-dependent delays

The ddensd function solves neutral delay differential equations that involve both the solution and its first derivative evaluated in the past:

$$y'(t) = f(t, y(t), y(dy_1), \dots, y(dy_j), y'(dyp_1), \dots, y'(dyp_k))$$

The delays, dy and dyp , can be time-dependent, state-dependent, or both.

Signed integer support for bit-wise operations

The `bitand`, `bitor`, `bitxor`, `bitcmp`, `bitshift`, `bitget`, and `bitset`, functions now support signed integers.

An additional input argument, `assumedtype`, is an optional string argument you can pass to any of these functions. Use `assumedtype` to indicate the assumed integer class for input values of type `double`. For example, `bitor(14,240,'uint8')` treats 14 and 240 as unsigned 8-bit integers even though they are passed as integers of type `double`.

`assumedtype` can be one of the following strings: `'int8'`, `'uint8'`, `'int16'`, `'uint16'`, `'int32'`, `'uint32'`, `'int64'`, or `'uint64'`. The default value of `assumedtype` is `'uint64'` for input values of type `double`. If the input values belong to an integer class, `assumedtype` defaults to the class of the input values.

atan2d function that calculates four-quadrant inverse tangent with result in degrees

atan2d calculates the four-quadrant inverse tangent and returns angles in degrees that lie in the closed interval $[-180, 180]$.

Complex number support for trigonometry degree functions

The `sind`, `cosd`, `tand`, `asind`, `acosd`, `atand`, `cscd`, `cotd`, `secd`, `acscd`, `asecd`, and `acotd` functions now support complex values. For example, `sind(10+i)` returns $0.1737 + 0.0172i$. Likewise, `asind(2)` now returns the complex angle $90.0000 - 75.4561i$.

Functionality being removed or changed

Compatibility Considerations: Yes

Functionality	What Happens When You Use This Functionality	Use This Instead	Compatibility Considerations
<code>bitshift(A,k,N)</code>	Still Runs	<code>bitshift(A,k,assumedtype)</code>	Replace all instances of <code>bitshift(A,k,N)</code> with <code>bitshift(A,k,assumedtype)</code> .
<code>bitcmp(A,N)</code>	Still Runs	<code>bitcmp(A,assumedtype)</code>	Replace all instances of <code>bitcmp(A,N)</code> with <code>bitcmp(A,assumedtype)</code> .
<code>bitshift(A,k)</code> where A is of <code>typedouble</code> .	Still runs	Not Applicable	<code>bitshift</code> now interprets double input as <code>uint64</code> instead of 53-bit signed integer by default. For example, <code>bitshift(1,54)</code> now returns <code>1.8014e+16</code> instead of 0.
<code>mimofr</code>	Warns	Not Applicable	Remove all instances of <code>mimofr</code> from your existing code.
Second output argument for <code>besselh</code> , <code>besseli</code> , <code>besselj</code> , <code>besselk</code> , <code>bessely</code> , and <code>airy</code> . For example, <code>[J,ierr] = besselj(nu,Z)</code> .	Errors	Syntax that returns only the solution vector. For example, <code>J = besselj(nu,Z)</code> .	Replace all instances that return two output arguments with the syntax that returns only the solution vector.

Functionality	What Happens When You Use This Functionality	Use This Instead	Compatibility Considerations
<p>Passing mixed-orientation input vectors to <code>besselh</code>, <code>besseli</code>, <code>besselj</code>, <code>besselk</code>, and <code>bessely</code>. For example, passing a row vector followed by a column vector:</p> <pre>J= besselj(rowNu, colZ)</pre> <p>or passing a column vector followed by a row vector:</p> <pre>J= besselj(colNu, rowZ)</pre>	Errors	First construct the inputs with <code>ndgrid</code> or <code>meshgrid</code> . Alternatively, you can pass a function handle and the mixed-orientation vectors to <code>bsxfun</code> .	<p>Modify all instances that pass mixed-orientation vectors. You can modify your code in one of two ways:</p> <ul style="list-style-type: none"> • Call <code>meshgrid</code> or <code>ndgrid</code> to construct the full grid first. <pre>[nu,Z]= meshgrid(rowNu, ColZ); J= besselj(nu, Z);</pre> • Pass a function handle and the mixed-orientation vectors to <code>bsxfun</code>. For example, if your existing code passes a row vector followed by a column vector, make the following change: <pre>J= bsxfun(@besselj, rowNu, colZ);</pre> or, if your code passes a column vector followed by a row vector, make the following change: <pre>J= bsxfun(@besselj, colNu', rowZ.');</pre>

Functionality	What Happens When You Use This Functionality	Use This Instead	Compatibility Considerations
$Y = \text{psi}(k0:k1,X)$	Errors	$Y = \text{psi}(k,X)$ where k is a scalar specifying the k th derivative of ψ at the elements of X .	Replace all instances of $Y = \text{psi}(k0:k1,X)$ with $Y = \text{psi}(k,X)$, where k is a scalar. To modify your code, loop through the values $k0:k1$. For example: <pre>for k=k0:k1 Y(:,k) = psi(k,X); end</pre> In the future, <code>size(Y)</code> will be <code>size(X)</code> . Modify any code that depends on <code>size(Y)</code> .
Passing empty and nonscalar input to <code>besselh</code> , <code>besseli</code> , <code>besselj</code> , <code>besselk</code> , <code>bessely</code> , and <code>airy</code> . For example, <pre>J = besselj([],(1:3))</pre> or <pre>J = besselj((1:3),[])</pre>	Errors	$J = \text{besselj}(\text{nu},[])$ or $J = \text{besselj}([],Z)$ where nu and Z are scalars.	Modify all instances that pass combinations of empty arrays with nonscalar input. The inputs must be the same size or one must be a scalar.

Data Import and Export

Data import from delimited and fixed-width text files using Import Tool

The Import Tool now allows you to preview data in delimited and fixed-width text files and select ranges of data to import. You also can define rules for handling nonnumeric values, and import data as column vectors, a matrix, a cell array, or a dataset array, in a single step. This tool opens instead of the Import Wizard for text files.

For more information, watch this video.

Single-step import of numbers, text, and dates as column vectors from a spreadsheet with Import Tool

The Import Tool now allows you to import columns of numeric data, text, and dates from spreadsheets as multiple column vectors in one step. Previously, this functionality was available for numeric data only.

audioread and audioinfo functions for reading MP3, MPEG-4 AAC, WAVE, and other audio files

The `audioread` and `audioinfo` functions read and provide information about MP3, MPEG-4 AAC, WAVE, OGG, and FLAC files on all platforms.

`audioread` is a drop-in replacement for the most common forms of `wavread` and `auread`. In most cases where you use `wavread` or `auread`, you can rename instances of these functions to `audioread`.

audiowrite function for writing MPEG-4 AAC, WAVE, and other audio files

The `audiowrite` function writes data to WAVE, OGG, and FLAC files on all platforms. `audiowrite` writes data to MPEG-4 AAC files on Windows and Mac platforms.

`audiowrite` is a drop-in replacement for the most common forms of `wavwrite`. In most cases where you use `wavwrite`, you can rename instances of this function to `audiowrite`.

Reading and writing of BigTIFF image files larger than 4 GB

MATLAB now supports BigTIFF image files larger than 4 GB. You can use `imread` or the `Tiff` object.

Reading of XLSM, XLTX, and XLTM files on all platforms with xlsread function

The `xlsread` function now reads data from XLSM, XLTX, and XLTM files on all platforms. Previously, this functionality was available only on Microsoft Windows systems with Excel software.

xlsread function now supporting named ranges on all platforms

The `xlsread` function now supports named ranges as inputs, on all platforms. For example, you can call

```
num = xlsread(filename, sheet, xlRange);
```

where `xlRange` refers to a named range of data in your Excel workbook. Previously, this functionality was available only on Microsoft Windows systems with Excel software.

Multiple delimiter support in textscan function

The `textscan` function recognizes multiple different delimiters within a single file. `textscan` also can treat multiple repeated delimiter characters as a single delimiter.

Timeout, user agent, and character encoding inputs for `urlread` and `urlwrite` functions

The `urlread` and `urlwrite` functions accept the following optional attribute-value pair arguments.

Attribute	Value
Timeout	Timeout duration
UserAgent	Client user agent identification
Charset	Character encoding, determined from the headers of the file

For example, to download Web content from a the MATLAB Central File Exchange while specifying a timeout duration of 5 seconds, type

```
urlread('http://www.mathworks.com/matlabcentral/fileexchange','Timeout',5);
```

Functionality being removed or changed

Compatibility Considerations: Yes

Functionality	What Happens When You Use This	Use This Instead	Compatibility Considerations
avifile	Warns	VideoWriter	Replace all instances of avifile with VideoWriter.
wavplay	Warns	audioplayer and play	Replace all existing instances of wavplay with audioplayer and play.
wavrecord	Warns	audiorecorder and record	Replace all existing instances of wavrecord with audiorecorder and record.
wk1finfo	Errors		Remove all instances of wk1finfo. Get information about Excel spreadsheets with xlsfinfo.
wk1read	Errors		Remove all instances of wk1read. Read Excel spreadsheets with xlsread.
wk1write	Errors		Remove all instances of wk1write. Write to Excel spreadsheets with xlswrite.

R2012a

Version: 7.14
New Features: Yes
Bug Fixes: Yes

Desktop Tools and Development Environment

Transpose and Sort Variables in the Variable Editor


To transpose or sort variables, use the right-click menu options in the Variable Editor. You can sort variables based on single or multiple column selections. The columns you select can be noncontiguous and should always include all the rows. Also, you can create variables from noncontiguous data selections. For more information see the New Variable Editor Features in Release 2012a demo.

MATLAB Dock Menu on Mac Includes New Capabilities

Previously, on a Mac, the Dock menu associated with the MATLAB icon included only the default options, such as **Hide/Show** and **Quit**. Now, consistent with the behavior of most Mac applications, the MATLAB Dock menu lists open windows and documents associated with the running MATLAB application. By choosing on any of the entries in the Dock menu, you can bring that window or document to the front. To view the Dock menu, right-click the MATLAB icon in the Dock or **Ctrl**+click the icon, if you have a one-button mouse.

In addition, the MATLAB Dock menu includes a new option, named **Open Additional Instance of MATLAB**, that is a convenient way to start another instance of MATLAB running on your computer.

The following figure shows the MATLAB Dock menu with a document open in the MATLAB Editor.



Improved Rendering in MATLAB Web Browser

The MATLAB Web browser uses a new HTML rendering engine on Microsoft Windows systems. This new engine provides better rendering, particularly on 64-bit systems. This update impacts the display of HTML from these sources:

- web commands
- Published MATLAB file output
- Folder reports from the Current Folder browser
- Simulink Model Advisor

Technical Support Requests Use Proxy Settings

You can submit Technical Support requests from MATLAB by selecting **Help > Submit a MathWorks Support Request**. In previous releases, if you were connected to the Internet via a proxy server, you had to save the request form to a text file, and then email it to MathWorks. Starting with R2012a, you can submit the request directly from the form.

Published Code Can Display Syntax Highlighted Sample Code

Compatibility Considerations: Yes

When you publish MATLAB code, you can have sample code appear with syntax highlighting. Sample code is code that appears within comments. Previously, only uncommented code appeared with syntax highlighting.

For details, see [Syntax Highlighted Sample Code](#). For a video demo, see [Syntax Highlighting for Commented MATLAB Code in Published Scripts in Release 2012a](#).

Compatibility Considerations

Previously, to publish preformatted text (without syntax highlighting), MATLAB required two or more spaces between the comment character (%) and the first text character in a code cell comment block. Now, to publish such text, there must be two, four, or more spaces in that location. Three spaces results in syntax highlighted sample code.

The publish Function Accepts Name-Value Pairs

You can customize the output from the `publish` function using Name-Value pair arguments. Previously, to customize the output from this function, you had to use a structure. You now can use either a structure or Name-Value pair arguments. For details, see `publish`.

Internationalization

Compatibility Considerations: Yes

Displaying Non-7-Bit ASCII Characters on Mac OS X Platforms

On Apple Mac OS X platforms, you might see garbled text if you try to use non-7-bit ASCII characters. For example, if you create a variable in the MATLAB command window containing these characters, you can type the characters, but if you display the contents of the variable, the characters are corrupted.

Or if you share MATLAB text files with a user on a computer with different locale settings, they might see corrupted text. The characters are rendered in that user's locale, not the language it was written in.

MATLAB text files include scripts and user-defined functions and classes. MATLAB displays characters in a text file using an *encoding scheme*, which is defined in the MathWorks locale database. This encoding scheme supports characters for the language specified by the user locale setting. If you try to use non-7-bit ASCII characters in a text file, you might have to use a different encoding scheme. UTF-8 is often used to handle multilingual characters. Beginning in R2011b, to handle non-7-bit ASCII characters, you can change the default encoding scheme to UTF-8 by switching the MathWorks locale database. Note that changing the default encoding scheme might cause characters other than 7-bit ASCII characters in existing text files to be garbled.

See [How the MATLAB Process Uses Locale Settings](#) for more information.

How to Change MATLAB's Default Encoding to UTF-8

If you have text files containing non-7-bit ASCII characters, you must convert the encoding in the files before changing the default encoding on your computer. For instructions, see “How to Convert Text File Encoding to UTF-8” on page 125.

You can change the default encoding scheme on Mac OS X platforms by using the UTF-8 locale database found in the `matlabroot/bin` folder.

To change the default locale database, type:

```
mldir = fullfile(matlabroot,'bin');
copyfile(fullfile(mldir,'lclata.xml'),...
    fullfile(mldir,'lclata_default.xml'));
copyfile(fullfile(mldir,'lclata_utf8.xml'),...
    fullfile(mldir,'lclata.xml'));
```

Alternatively, you can change the default locale database by setting an environment variable on your computer.

- 1 Set the environment variable, `MWLOCALE_LCDATA_FILENAME`, with the UTF-8 version of the locale database name, `lclata_utf8.xml`, in the environment file, `environment.plist`. Please see this article from the Mac OS X Developer Library, Technical Q&A QA1067 “Setting environment variables for user processes” at http://developer.apple.com/library/mac/#qa/qa1067/_index.html.
- 2 Close MATLAB if it is currently running.
- 3 Start MATLAB by double-clicking the MATLAB icon in the Applications folder.

How to Convert Text File Encoding to UTF-8

Before converting a file, copy the file to a new directory.

Use the Mac OS X TextEdit application to convert the file encoding. For example:

- 1 Open a MATLAB text file with TextEdit.
- 2 Select **File -> Save as...**
- 3 Change the file name.
- 4 Change **Plain Text Encoding:** to Unicode (UTF-8).
- 5 Save the file.

Alternatively, the following MATLAB function, `convert_file_encoding`, creates a new text file with different encoding.

```

function convert_file_encoding(infile,outfile,from_encoding,to_encoding)

if strcmp(infile(end-2:end),'mdl');
    isMDL = 1;
else
    isMDL = 0;
end

fpIn = fopen(infile,'r','n',from_encoding);
fpOut = fopen(outfile,'w','n',to_encoding);

while feof(fpIn) == 0
    lineIn = fgets(fpIn);
    if isMDL && strcmp('SavedCharacterEncoding',strtrim(lineIn),22)
        lineIn = regexprep(lineIn,from_encoding,to_encoding);
    end

    fwrite(fpOut,lineIn,'char');
end

fclose(fpIn);
fclose(fpOut);
end

```

To use this function, you need to know the current encoding, `from_encoding`.

- For MATLAB R2010b or later:

```

ret = feature('locale');
from_encoding = ret.encoding;

```

- For MATLAB R2008a through R2010a:

```

ret = feature('locale');
[t,r] = strtok(ret.ctype, '.');
from_encoding = r(2:end);

```

For example, a file, `myFile.m`, was created with MATLAB encoding set to ISO-8859-1. To convert the file to UTF-8, type:

```
convert_file_encoding('myFile.m','myFileUTF8.m','ISO-8859-1','UTF-8')
```

Compatibility Considerations

In a future release, the UTF-8 version of the MathWorks locale database will be the default on Mac OS X systems. Any text file created in MATLAB that is encoded in the user default encoding and contains characters other than 7-bit ASCII characters must be converted to the UTF-8 encoding scheme. Otherwise, MATLAB and other MathWorks products might not be able to properly load the files.

You must convert the file encoding before changing the default locale database.

Do not convert text files to UTF-8 if you share them with users on Windows platforms.

Mathematics

New Integral Functions

The new functions, `integral`, `integral2`, and `integral3` perform numerical integration with additional support for nonrectangular and unbounded regions of integration. They are the recommended functions for performing quadrature.

Performance Enhancements

The following functions show improved performance:

- Arithmetic and similar basic math functions for double, single, and integer data types.
- The grid-based interpolation functions, `interp2`, `interp3`, and `interpn`.
- Generating random values using either `rng('combRecursive')` or `RandStream('mrg32k3a')`.

griddata Supports 3-D Data and Natural Neighbor Interpolation

`griddata` is now the recommended function for interpolating 2-D and 3-D scattered data. `griddata` also has a new `method` option, `'natural'`, for specifying natural neighbor interpolation.

TriScatteredInterp Accepts Complex Values

You can now use `TriScatteredInterp` to interpolate complex scattered data in a single pass. For example, `F = TriScatteredInterp(X,V)` now accepts a complex vector `V`.

Set Functions Provide Option to Return Sets in Original Order

You now can specify the ordering of the output array returned by the functions `unique`, `union`, `intersect`, `setdiff`, and `setxor`. The new argument, `setOrder`, is one of two strings, `'stable'` or `'sorted'`. Specify `'stable'` if you want the elements in the output array to be in the same order as in the input array. For example:

```
C = unique([9 2 2], 'stable') returns C = [9 2].
```

Specify `'sorted'` if you want the elements in the output array to be in sorted order. For example:

```
C = unique([9 2 2], 'sorted') returns C = [2 9].
```

Set Functions Changing Behavior in a Future Release

Compatibility Considerations: Yes

In a future release, the behavior of `unique`, `union`, `intersect`, `setdiff`, `setxor`, and `ismember` will change.

- If there are repeated elements in the input arrays, the functions `unique`, `union`, `intersect`, `setdiff`, and `setxor` will return the index to the first occurrence of the repeated elements (or rows).
- The optional output array, `locb`, returned by `ismember`, will contain the lowest absolute indices in `B` for elements (or rows) that are also in `A`.
- All index vectors returned by `unique`, `union`, `intersect`, `setdiff`, or `setxor` will be column vectors.
- `unique` and `union` will support objects with methods `sort` (sortrows for the 'rows' option), and `ne`. This includes heterogeneous arrays derived from the same root class.
- `intersect`, `setdiff`, `setxor`, and `ismember` will support objects with methods `sort` (sortrows for the 'rows' option), `ne`, and `eq`. This includes heterogeneous arrays derived from the same root class.
- The input arrays passed to `union`, `intersect`, `setdiff`, `setxor`, and `ismember` must be of the same class with the following exceptions:
 - Logical, char, and all numeric classes can combine with double arrays.
 - Cell arrays of strings can combine with char arrays.

Note The set functions already conform to this behavior when you call them with the new `setOrder` argument.

Compatibility Considerations

The new behavior change is introduced for adoption in R2012a. If you want to assess the impact this change might have on your existing code, specify 'R2012a' as the final input argument to `unique`, `union`, `intersect`, `setdiff`, `setxor`, and `ismember`. For example:

```
[C,IA,IC] = unique([9 9 1], 'R2012a')
```

```
C =
```

```
    1    9
```

```
IA =
```

```
    3  
    1
```

```
IC =
```

```
    2  
    2  
    1
```

If the changes adversely affect your code, you can specify 'legacy' to preserve the current behavior. For example:

```
[C,IA,IC] = unique([9 9 1], 'legacy')
```

```
C =
```

```
    1    9
```

```
IA =
```

```
    3    2
```

```
IC =
```

```
    2    2    1
```

Interpolation and Computational Geometry Functionality Being Removed or Changed

Compatibility Considerations: Yes

Functionality	What Happens When You Use This Functionality	Use This Instead	Compatibility Considerations
<code>interp1q</code>	Still Runs	<code>interp1</code>	Replace all instances of <code>interp1q</code> with <code>interp1</code> .
<code>interp1(..., 'cubic')</code>	Still Runs	<code>interp1(..., 'pchip')</code>	Replace all instances of <code>interp1(..., 'cubic')</code> with <code>interp1(..., 'pchip')</code> .
Passing nonuniformly spaced points or grid to: <code>interp1(..., 'v5cubic')</code> <code>interp2(..., 'cubic')</code> <code>interp3(..., 'cubic')</code> <code>interp4(..., 'cubic')</code>	Warns	<code>interp1(..., 'spline')</code> <code>interp2(..., 'spline')</code> <code>interp3(..., 'spline')</code> <code>interp4(..., 'spline')</code>	In previous releases, <code>interp1</code> , <code>interp2</code> , <code>interp3</code> , and <code>interp4</code> silently changed the <code>'v5cubic'</code> and <code>'cubic'</code> methods to <code>'spline'</code> when the sample data was not uniformly spaced. Now, a warning is issued if the uniformity conditions are not honored. To avoid the warning message, change any instances that call for <code>'v5cubic'</code> or <code>'cubic'</code> to the <code>'spline'</code> method.

Functionality	What Happens When You Use This Functionality	Use This Instead	Compatibility Considerations
Passing the 'pp' flag to interp1. For example: <pre>pp = interp1(x, v, 'linear', 'pp'); vq = ppval(pp, xq);</pre>	Still Runs	Use griddedInterpolant to create an interpolating function that is efficient to evaluate in a repeated manner.	Replace all instances of interp1(..., 'pp') with griddedInterpolant. For example: <pre>F = griddedInterpolant(x, v, 'linear'); vq = F(xq);</pre>
interp1(X, Y, Xq, [], ...) where [] specifies the default interpolation method	Still Runs	interp1(X, Y, Xq, 'linear', ...)	Replace all instances of interp1(X, Y, Xq, [], ...) with interp1(X, Y, Xq, 'linear', ...).
interp1(x,V,...) where x is a vector and V is an array representing multiple value sets. For example: <pre>x = (1:5)'; V = [x, 2*x, 3*x]; xq = (1:0.5:5)'; Vq = interp1(x, V, xq);</pre>	Still Runs	Use griddedInterpolant and loop over each value set, updating and evaluating during each iteration.	Replace all instances of interp1(x,V,...), where x is a vector and V is an array representing multiple value sets. Loop over V, calling griddedInterpolant on each value set. The following example code shows how to set up and interpolate over three value sets in V: <pre>x = (1:5)'; V = [x, 2*x, 3*x]; xq = (1:0.5:5)'; F = griddedInterpolant(x, V(:,1));</pre>

Functionality	What Happens When You Use This Functionality	Use This Instead	Compatibility Considerations
			<pre>for n=1:3 F.Values = V(:, n); Vq(:, n) = F(xq); end</pre> <p>The columns of Vq are the interpolation results for the corresponding columns of V.</p>
<p>Passing mixed orientation vectors to <code>interp2</code>:</p> <pre>Vq = interp2(x, y, V, xq, yq)</pre> <p>Specifically, if one or both of the following are true:</p> <ul style="list-style-type: none"> • One of <code>x</code> and <code>y</code> is a row vector and the other is a column vector. • One of <code>xq</code> and <code>yq</code> is a row vector and the other is a column vector. 	Still Runs	Construct the full grid with <code>meshgrid</code> first. Alternatively, use <code>griddedInterpolant</code> if you have a large data set.	<p>Modify all instances that pass mixed orientation vectors to <code>interp2</code>. You can modify your code in one of two ways:</p> <ul style="list-style-type: none"> • Call <code>meshgrid</code> to construct the full grid first. <pre>[X,Y] = meshgrid(x, y); [Xq,Yq] = meshgrid(xq, yq); Vq = interp2(X, Y, V, Xq, Yq);</pre> • Pass the vectors to <code>griddedInterpolant</code> inside a cell array. <pre>F = griddedInterpolant({x, y}, V.');</pre>

Functionality	What Happens When You Use This Functionality	Use This Instead	Compatibility Considerations
<p>Passing mixed orientation vectors to <code>interp3</code>:</p> <pre>interp3(x, y, z, V, xq, yq, zq)</pre> <p>Specifically, if one or both of the following are true:</p> <ul style="list-style-type: none"> • <code>x</code>, <code>y</code>, and <code>z</code> are a combination of row and column vectors. • <code>xq</code>, <code>yq</code>, and <code>zq</code> are a combination of row and column vectors. 	Still Runs	Construct the full grid with <code>meshgrid</code> first. Alternatively, use <code>griddedInterpolant</code> if you have a large data set.	<p>$V_q = (F(\{x_q, y_q\})) \cdot'$</p> <p>Modify all instances that pass mixed orientation vectors to <code>interp3</code>. You can modify your code in one of two ways:</p> <ul style="list-style-type: none"> • Call <code>meshgrid</code> to construct the full grid first. <pre>[X,Y,Z] = meshgrid(x, y, z); [Xq,Yq,Zq] = meshgrid(xq, yq, zq); Vq = interp3(X, Y, Z, V, Xq, Yq, Zq);</pre> <ul style="list-style-type: none"> • Pass the vectors to <code>griddedInterpolant</code> inside a cell array. <pre>V = permute(V, [2 1 3]); F = griddedInterpolant({x, y, z}, V); Vq = F({xq, yq, zq}); Vq = permute(Vq, [2 1 3]);</pre>

Functionality	What Happens When You Use This Functionality	Use This Instead	Compatibility Considerations
<p>Passing mixed orientation vectors to <code>interp</code>:</p> <pre>interp(x1,x2,...,xn, V, x1q,x2q,...,xnq)</pre> <p>Specifically, if one or both of the following are true:</p> <ul style="list-style-type: none"> • <code>x1,x2,...,xn</code> are a combination of row and column vectors. • <code>x1q,x2q,...,xnq</code> are a combination of row and column vectors. 	Still Runs	Construct the full grid with <code>ndgrid</code> first. Alternatively, use <code>griddedInterpolant</code> if you have a large data set.	<p>Modify all instances that pass mixed orientation vectors to <code>interp</code>. You can modify your code in one of two ways:</p> <ul style="list-style-type: none"> • Call <code>ndgrid</code> to construct the full grid first. <pre>[X1,X2,...,Xn]= ndgrid(x1,x2,...,xn); [X1q,X2q,...,Xnq]= ndgrid(x1q,x2q,...,xnq); Vq= interp(X1,X2,...,Xn, V, X1q,X2q,...,Xnq);</pre> • Pass the vectors to <code>griddedInterpolant</code> inside a cell array. <pre>F= griddedInterpolant({x1, x2,...,xn}, V); Vq= F({x1q, x2q,...,xnq});</pre>

Functionality	What Happens When You Use This Functionality	Use This Instead	Compatibility Considerations
<code>interp1(..., *METHOD)</code> <code>interp2(..., *METHOD)</code> <code>interp3(..., *METHOD)</code> <code>interpN(..., *METHOD)</code>	Still Runs Errors for invalid input data	<code>interp1(..., METHOD)</code> <code>interp2(..., METHOD)</code> <code>interp3(..., METHOD)</code> <code>interpN(..., METHOD)</code>	In previous releases, <code>interp1</code> , <code>interp2</code> , <code>interp3</code> , and <code>interpN</code> provided a <code>*METHOD</code> option that bypassed error checking on the assumption of valid data. These checks are no longer bypassed. Use the <code>griddedInterpolant</code> class to perform repeated interpolation queries on the same data set without penalty of repeated error checks.
<code>vq=griddata(x,y,v,xq,yq)</code> where <code>xq</code> is a row vector and <code>yq</code> is a column vector.	Still Runs	<code>vq=griddata(x,y,v,Xq,Yq)</code> where <code>Xq</code> and <code>Yq</code> are the output arrays returned by <code>meshgrid</code> .	Modify all instances that pass mixed orientation vectors to <code>griddata</code> . To specify a grid of query points, construct a full grid with <code>meshgrid</code> before calling <code>griddata</code> .
<code>griddata3</code>	Errors	<code>griddata</code>	Replace all existing instances of <code>griddata3</code> with <code>griddata</code> .
<code>delaunay3</code>	Errors	<code>delaunay</code>	Replace all existing instances of <code>delaunay3</code> with <code>delaunay</code> .
<code>tsearch</code>	Errors	<code>DelaunayTri/pointLocation</code>	Replace all existing instances of <code>tsearch</code> with <code>DelaunayTri/pointLocation</code> .

Functionality	What Happens When You Use This Functionality	Use This Instead	Compatibility Considerations
dsearch	Errors	DelaunayTri/nearestNeighbor	Replace all existing instances of dsearch with DelaunayTri/nearestNeighbor.
convhull(..., OPTIONS)	Errors	Omit the OPTIONS argument when you call convhull.	Remove the OPTIONS argument from all instances that pass it to convhull.
delaunay(..., OPTIONS)	Errors	Omit the OPTIONS argument when you call delaunay.	Remove the OPTIONS argument from all instances that pass it to delaunay.
griddata(..., OPTIONS)	Errors	Omit the OPTIONS argument when you call griddata.	Remove the OPTIONS argument from all instances that pass it to griddata.
voronoi(..., OPTIONS)	Errors	Omit the OPTIONS argument when you call voronoi.	Remove the OPTIONS argument from all instances that pass it to voronoi.

Other Functionality Being Removed or Changed

Compatibility Considerations: Yes

Functionality	What Happens When You Use This Functionality	Use This Instead	Compatibility Considerations
<code>isequalwithequalnans</code>	Still Runs	<code>isequaln</code>	Replace all instances of <code>isequalwithequalnans</code> with <code>isequaln</code> .
<code>mimofr</code>	Still Runs	Not Applicable	Remove all instances of <code>mimofr</code> from your existing code.
<code>RandnAlg</code> property of <code>RandStream</code> class	Warns	<code>NormalTransform</code> property of <code>RandStream</code> class	Replace all existing instances of <code>RandnAlg</code> with <code>NormalTransform</code> .
<code>setDefaultStream</code> method of <code>RandStream</code> class	Warns	<code>setGlobalStream</code> method of <code>RandStream</code> class	Replace all existing instances of <code>RandStream.setDefaultStream</code> with <code>RandStream.setGlobalStream</code> .
<code>getDefaultStream</code> method of <code>RandStream</code> class	Warns	<code>getGlobalStream</code> method of <code>RandStream</code> class	Replace all existing instances of <code>RandStream.getDefaultStream</code> with <code>RandStream.getGlobalStream</code> .
<code>atan2(y,x)</code> for complex <code>y</code> and <code>x</code> .	Errors	<code>atan2(real(y),real(x))</code> when <code>y</code> and <code>x</code> are complex.	Replace all existing instances of <code>atan2(y,x)</code> with <code>atan2(real(y),real(x))</code> where <code>y</code> and <code>x</code> are complex.

Functionality	What Happens When You Use This Functionality	Use This Instead	Compatibility Considerations
Second output argument for <code>besselh</code> , <code>besseli</code> , <code>besselj</code> , <code>besselk</code> , <code>bessely</code> , and <code>airy</code> . For example, <code>[J,ierr] = besselj(nu,Z)</code> .	Warns	Syntax that returns only the solution vector. For example, <code>J = besselj(nu,Z)</code> .	Replace all instances that return two output arguments with the syntax that returns only the solution vector.
Passing mixed orientation input vectors to <code>besselh</code> , <code>besseli</code> , <code>besselj</code> , <code>besselk</code> , and <code>bessely</code> . For example, passing a row vector followed by a column vector: <code>J= besselj(rowNu, colZ)</code> or passing a column vector followed by a row vector: <code>J= besselj(colNu, rowZ)</code>	Warns	Construct the inputs with <code>ndgrid</code> or <code>meshgrid</code> first. Alternatively, you can pass a function handle and the mixed orientation vectors to <code>bsxfun</code> .	Modify all instances that pass mixed orientation vectors. You can modify your code in one of two ways: <ul style="list-style-type: none"> • Call <code>meshgrid</code> or <code>ndgrid</code> to construct the full grid first. <code>[nu,Z]= meshgrid(rowNu, ColZ);</code> <code>J= besselj(nu, Z);</code> • Pass a function handle and the mixed orientation vectors to <code>bsxfun</code>. For example, if your existing code passes a row vector followed by a column vector, make the following change: <code>J= bsxfun(@besselj, rowNu, colZ);</code> or, if your code passes a column vector followed by a row vector, make

Functionality	What Happens When You Use This Functionality	Use This Instead	Compatibility Considerations
			<p>the following change:</p> <pre>J= bsxfun(@besselj, colNu', rowZ.');</pre>
<p><code>Y = psi(k0:k1,X)</code></p>	<p>Warns</p>	<p><code>Y = psi(k,X)</code> where <code>k</code> is a scalar specifying the kth derivative of ψ at the elements of <code>X</code>.</p>	<p>Replace all instances of <code>Y = psi(k0:k1,X)</code> with <code>Y = psi(k,X)</code>, where <code>k</code> is a scalar. To modify your code, loop through the values <code>k0:k1</code>. For example:</p> <pre>for k=k0:k1 Y(:,k) = psi(k,X); end</pre> <p>In the future, <code>size(Y)</code> will be <code>size(X)</code>. Modify any code that depends on <code>size(Y)</code>.</p>
<p>Passing empty and nonscalar input to <code>besselh</code>, <code>besseli</code>, <code>besselj</code>, <code>besselk</code>, <code>bessely</code>, and <code>airy</code>. For example,</p> <pre>J = besselj([],(1:3))</pre> <p>or</p> <pre>J = besselj((1:3),[])</pre>	<p>Warns</p>	<p><code>J = besselj(nu,[])</code> or <code>J = besselj([],Z)</code> where <code>nu</code> and <code>Z</code> are scalars.</p>	<p>Modify all instances that pass combinations of empty arrays with nonscalar input. The inputs must be the same size or one must be a scalar.</p>

Data Analysis

Programming

xlsread Reads XLSX Files on All Platforms

The `xlsread` function now reads data from XLSX files on all platforms, including support for specifying the range and worksheet number. Previously, this functionality was available only on Microsoft Windows systems with Excel software.

VideoWriter Supports MPEG-4 Files on Windows 7 Systems

VideoWriter now creates MPEG-4 files with the extension .mp4 or .m4v on Windows 7 systems. For more information, see the VideoWriter reference page.

audioplayer Supports Overlapping Playback

In R2011a, changes that allowed `audioplayer` to support device selection also disabled the ability to play overlapping audio samples. With R2012a, overlapping playback is available again.

For example, play a second sample before the first one completes, and hear audio from both:

```
chirpData = load('chirp.mat');
chirpObj = audioplayer(chirpData.y,chirpData.Fs);

gongData = load('gong.mat');
gongObj = audioplayer(gongData.y,gongData.Fs);

play(chirpObj);
play(gongObj);
```

importdata Returns Different Output for Some Text Files

Previously, the `importdata` function recognized comments in text files and did not include them in the output. In addition, `importdata` parsed files that contained numeric values and comma, space, or tab delimiters into a numeric array, even when you specified a delimiter that did not match the contents of the file.

In this release, `importdata` honors the specified delimiter, and includes comments in the output. For example, consider a hypothetical file named `test.txt` with this space-delimited data:

```
% Comment in file
1 2 3
4 5 6
```

In previous releases,

```
t = importdata('test.txt','(',')')
```

returned a numeric array:

```
t =
     1     2     3
     4     5     6
```

In this release, the same code returns a cell array:

```
t =
    '% Comment in file'
    '1 2 3'
    '4 5 6'
```

If you remove the incorrect comma delimiter,

```
t = importdata('test.txt')
```

`importdata` returns a struct array:

```
t =
    data: [2x3 double]
```

```
textdata: {'% Comment in file'}
```


Exponents Print with Two Digits

In previous releases, functions that printed floating-point values with exponents used three digits for the exponent on Windows systems, but two digits on any other system. Now, these functions use two digits for the exponent on all systems.

For example,

```
str = sprintf('%e',pi)
```

always returns

```
str =  
3.141593e+00
```

Conversion of Error and Warning Message Identifiers

Compatibility Considerations: Yes

For R2012a, error and warning message identifiers have changed in MATLAB.

Compatibility Considerations

If you have scripts or functions that use message identifiers that changed, you must update the code to use the new identifiers. Typically, message identifiers are used to turn off specific warning messages, or in code that uses a try/catch statement and performs an action based on a specific error identifier.

For example, the `MATLAB:eigs:NonPosIntSize` identifier has changed to `MATLAB:eigs:RoundNonIntSize`. If your code checks for `MATLAB:eigs:NonPosIntSize`, you must update it to check for `MATLAB:eigs:RoundNonIntSize` instead. For a mapping of the new identifiers to the original identifiers, see Technical Support solution 1 - ERAFNC.

Specify a List of Allowed Subclasses in the Class Definition

You can control which classes are allowed to subclass a class that you define by specifying a list classes in the new class attribute, `AllowedSubclasses`. See [Controlling Allowed Subclasses](#) for more information.

Specify Which Classes Can Access Class Members

Compatibility Considerations: Yes

You can control access to specific class members (properties, methods, and events) by specifying a list of classes to which you want to grant access to these members. See [Controlling Access to Class Members](#) for more information.

Compatibility Considerations

In previous releases, you could assign a value to the following class member access attributes as a value returned by a function:

- Properties – `Access`, `GetAccess`, and `SetAccess`
- Methods – `Access`
- Events – `ListenAccess` and `NotifyAccess`

With this release, you can specify values for these attributes only explicitly as either the appropriate character string or a `meta.class` object returned by the `?` operator, or a cell array of character strings and/or `meta.class` objects. See [Specify Access to Class Members](#) for more information.

Method Declared as Abstract and Private Now Errors

Compatibility Considerations: Yes

In previously releases, declaring a method as both `Abstract` and `Access = private` did not cause an error. With this release, declaring a method both `Abstract` and `private` causes an error.

Compatibility Considerations

If any of your class definitions declare a method as both `Abstract` and `private`, you need to declare the method either as `Abstract`, which make the class abstract and requires subclasses to implement the method with the declared syntax, or declare the method `Access = private`, which means that only methods within the defining class can call the `private` method.

Declaring a method as both `Abstract` and `private` is not supported.

New Capabilities for Writing Image Data to FITS Files

MATLAB now includes a function named `fitswrite` that you can use to write image data to Flexible Image Transport System (FITS) files. You can also display the metadata for all Header-Data Units (HDUs) in a FITS file using the `fitsdisp` function. (MATLAB already supports reading FITS files using the `fitsread` function.)

In addition, MATLAB now includes a new package, called `matlab.io.fits`, containing dozens of functions that provide access to the routines in the CFITSIO library. Using these low-level functions, you can create FITS files, read data from FITS files and write data to the files, using the CFITSIO library, version 3.27.

Access Data on Remote Servers Using the OPeNDAP Protocol

You can read data stored on remote servers using the OPeNDAP protocol capability of the following MATLAB NetCDF functions:

- `ncread`
- `ncreadatt`
- `ncdisp`
- `ncinfo`
- `netcdf.open`

To use these functions to access data on remote servers using OPeNDAP protocol, specify the URL instead of a file name.

Upgrades to Scientific File Format Libraries

The following table lists upgrades to scientific file format libraries used by MATLAB.

Library	Version
NetCDF	4.1.3 (upgraded from 4.1.2)

Ability to Read NetCDF Files Using HDF4 Functions Removed

In past releases, for certain NetCDF files on Linux and Macintosh systems, you could read the files using the HDF4 functions. This capability has been removed. To read NetCDF files, use the high-level NetCDF functions or the low-level NetCDF package.

Functionality Being Removed or Changed

Compatibility Considerations: Yes

Functionality	What Happens When You Use This Functionality?	Use This Instead	Compatibility Considerations
avifile	Still runs	VideoWriter	Replace all instances of avifile with VideoWriter.
fileparts return argument 4 (file version)	Errors — beginning in MATLAB Version 7.13 (R2011b)	No alternative; file versions are unsupported	Call fileparts with three return arguments: [path_name, file_name, file_extension]
helpbrowser	Still runs	doc	Replace all instances of helpbrowser with doc.
helpdesk	Still runs	doc	Replace all instances of helpdesk with doc.
helpwin	Still runs	doc	Replace all instances of helpwin with doc.
info	Warns		Remove all instances of info. Find information about MathWorks at www.mathworks.com/company/aboutus
mmreader	Warns, creates a VideoReader object	VideoReader	Replace all instances of mmreader with VideoReader.
mmreader.isPlatformSupported and VideoReader.isPlatformSupported	Errors		For a platform-specific list of supported video file formats, use getFileFormats.

Functionality	What Happens When You Use This Functionality?	Use This Instead	Compatibility Considerations
support	Warns		Remove all instances of support. Find the MathWorks technical support page at www.mathworks.com/support .
whatsnew	Warns		Remove all instances of whatsnew.

Graphics and 3-D Visualization

Creating Graphical User Interfaces (GUIs)

External Interfaces/API

Changes to Compiler Support

Compatibility Considerations: Yes

New Compiler Support

MATLAB Version 7.14 (R2012a) supports these new compilers for building MEX-files on Linux 64- and 32-bit platforms:

- GNU gcc Version 4.4.6

MATLAB supports these new compilers for building MEX-files on Windows 64- and 32-bit platforms:

- Intel Visual Fortran Composer XE 2011 SP1 (12.1)

Discontinued Compiler Support

MATLAB no longer supports the following compilers:

Windows 64-Bit Platforms

- Microsoft Visual Studio® 2010 (10.0) Express

Windows 32-Bit Platforms

- Microsoft Visual Studio 2010 (10.0) Express
- Visual C++ 6.0

Linux (64- and 32-Bit) Platforms

- GNU gcc Version 4.3.x

Compatibility Considerations

To ensure continued support for building your MEX-files, consider upgrading to another supported compiler. For an up-to-date list of supported compilers, see the [Supported and Compatible Compilers Web page](#).

mxAssert and mxAssertS Functions Throw MATLAB Exception

The `mxAssert` and `mxAssertS` functions now throw the MATLAB exception `MATLAB:mex:assertion` and terminate the MEX-file instead of aborting MATLAB.

Version Support for COM ProgID Values

You can specify version-specific Programmatic Identifiers (ProgID) for MATLAB Version 7.14 (R2012a) and later.

- `MATLAB.Desktop.Application`
- `MATLAB.Application`
- `MATLAB.Application.Single`, to specify a dedicated server.

R2011b

Version: 7.13
New Features: Yes
Bug Fixes: Yes

Desktop Tools and Development Environment

Command Window

Error Messages Reformatted for Improved Readability and Navigation

Error messages in the Command Window no longer appear with question marks or arrows. In addition, error messages for each function now provide a link to that function's documentation.

The following images show examples of the differences in presentation:

- Built-in functions:
 - MATLAB Version 7.13 (R2011b)

```
>> eig
Error using eig
Not enough input arguments.
```
 - MATLAB Version 7.12 (R2011a) and earlier

```
>> eig
??? Error using ==> eig
Not enough input arguments.
```
- Functions that are not built in:
 - MATLAB Version 7.13 (R2011b)

```
>> num2str
Error using num2str (line 40)
Not enough input arguments.
```
 - MATLAB Version 7.12 (R2011a) and earlier

```
>> num2str
??? Error using ==> num2str at 42
Numeric array is unspecified
```

Editor

New Desktop features and changes introduced in this version are:

Automatically Renaming All Variables and Functions in File

Under certain conditions, as you rename a variable or function, a tooltip opens. The tooltip indicates that MATLAB can rename all instances of the function or variable in the current file. This is helpful in preventing errors that result if you change names manually and overlook or mistype one or more instances of the name. For a video overview, watch this video demo

```
value1 = 0:1:6*pi;
y=sin(val1)
plot(val1,val2)
title('Sine Wave','FontWeight','bold')
xlabel('x')
ylabel('sin(x)')
set(gca,'Color','w')
set(gcf,'MenuBar','none')
```

Press **Shift+Enter** to rename 3 instances of 'val1' to 'value1'

For details, including the circumstances under which MATLAB prompts you, see [Automatically Rename All Functions or Variables in a File](#).

Internationalization

Compatibility Considerations: Yes

Displaying Multilingual Characters on Mac OS X Platforms

On Apple Mac OS X platforms, you might see garbled text if you try to use multilingual characters. Suppose you create a variable in the MATLAB command window containing multilingual characters. You can type the multilingual characters, but if you display the contents of the variable, the characters are corrupted.

MATLAB text files include scripts and user-defined functions and classes. MATLAB displays characters in a text file using an *encoding scheme*, which is defined in the MathWorks locale database. This encoding scheme supports characters for the language specified by the user locale setting. If you try to use multilingual characters in a text file, you may have to use a different encoding scheme. UTF-8 is often used to handle multilingual characters. In R2011b, to handle multilingual characters, you can change the default encoding scheme to UTF-8 by switching the MathWorks locale database. Note that changing the default encoding scheme might cause characters other than 7-bit ASCII characters in existing text files to be garbled.

See [How the MATLAB Process Uses Locale Settings](#) for more information.

How to Change MATLAB's Default Encoding to UTF-8

You can change the default encoding scheme on Mac OS X platforms by using the UTF-8 locale database found in the *matlabroot/bin* folder. If you have text files containing characters other than 7-bit ASCII characters, you must convert the encoding before changing the default encoding. For instructions, see “How to Convert Text File Encoding to UTF-8” on page 176.

To change the default locale database, type:

```
mldir = fullfile(matlabroot,'bin');
copyfile(fullfile(mldir,'lodata.xml'),...
    fullfile(mldir,'lodata_default.xml'));
copyfile(fullfile(mldir,'lodata_utf8.xml'),...
    fullfile(mldir,'lodata.xml'));
```

How to Convert Text File Encoding to UTF-8

Before converting a file, copy the file to a new directory.

Use the Mac OS X TextEdit application to convert the file encoding. For example:

- 1 Open a MATLAB text file with TextEdit.
- 2 Select **File** ->**Save as...**
- 3 Change the file name.
- 4 Change **Plain Text Encoding:** to Unicode (UTF-8).
- 5 Save the file.

Alternatively, the following MATLAB code creates a new text file with the encoding set to UTF-8:

```
function convertencoding(infile, outfile)

fpIn = fopen(infile, 'r', 'n');
fpOut = fopen(outfile, 'w', 'n', 'UTF-8');

while feof(fpIn) == 0
    lineIn = fgets(fpIn);
    fwrite(fpOut, lineIn, 'char');
end

fclose(fpIn);
fclose(fpOut);
end
```

Compatibility Considerations

In a future release, the UTF-8 version of the MathWorks locale database will be the default on Mac OS X systems. Any text file created in MATLAB that is encoded in the user default encoding and contains characters other than 7-bit ASCII characters must be converted to the UTF-8 encoding scheme.

Otherwise, MATLAB and other MathWorks products might not be able to properly load the files.

You must convert the file encoding before changing the default locale database.

Mathematics

New Functionality for Grid-Based Interpolation

MATLAB includes a new class, `griddedInterpolant`, for grid-based interpolation. `griddedInterpolant` works with grids in `ndgrid` format and complements the functionality provided by `interpn` to provide improved performance and memory efficiency.

Performance Enhancements

The following functions show improved performance:

- Some integer math functions
- Some linear algebra functions, including chol and 3-output form of qr
- Trigonometric functions

Permutation Option for randperm

The `randperm` function and the `RandStream.randperm` method now have the option of returning random permutations of k integers selected at random from the integers 1 through n .

Return Permutation Information in Vector for qr

If you use the three-output form of `qr` in noneconomy mode, you can now specify `'vector'` as an input argument. The permutation information will return a vector instead of a matrix.

Changes to meshgrid and ndgrid

The functions `meshgrid` and `ndgrid` have changed behavior under certain calling scenarios:

- When more than one input argument is passed to `meshgrid`, the dimensionality of the output arrays is deduced from the number of inputs. Previously the dimensionality was deduced from the number of outputs. For example, `[x,y] = meshgrid(1:3,1:4,1:5)` will now assume a missing third output argument and return 3-D output arrays `x` and `y`. Previously, the third input was ignored and the function returned 2-D arrays for `x` and `y`.
- When a single argument is passed to `ndgrid`, the dimensionality of the output arrays is dictated by the number of output arguments. `ndgrid` has been revised to maintain consistency in the case of a single input and output. `ndgrid` will now degenerate naturally to support 1-D outputs. For example, `x = ndgrid(1:5)` returns a 5-by-1 output vector `x`. Previously, a 5-by-5 array was returned.

Functionality Being Removed or Changed

Compatibility Considerations: Yes

Functionality	What Happens When You Use This Functionality	Use This Instead	Compatibility Considerations
bessel	Errors	besselj	Replace all instances of bessel with besselj.
ODE solver syntax <code>solver('vdp',t0,tfinal,y0)</code> where <code>solver</code> is one of the ODE solvers <code>ode45</code> , <code>ode23</code> , <code>ode113</code> , <code>ode15s</code> , <code>ode23s</code> , <code>ode23t</code> , or <code>ode23tb</code>	Errors	<code>solver('vdp',[t0 tfinal],y0)</code> or <code>solver(@vdp,[t0 tfinal],y0)</code>	Replace all instances of the syntax <code>t0,tfinal</code> with <code>[t0 tfinal]</code> .
Values on and off for Mass property of <code>odeset</code> and <code>odeget</code>	Errors	Set the Mass property to a constant matrix or a function that evaluates the variable mass matrix.	Update your code to use a constant mass matrix or a function that evaluates the variable mass matrix. For more information, check the supported settings of Mass and MassStateDependency in the <code>odeset</code> properties.
MassConstant property of <code>odeset</code> and <code>odeget</code>	Errors	For a constant mass matrix, set the Mass property to that matrix. For a time-dependent mass matrix, set the Mass property to a function that evaluates the matrix and set the MassStateDependency property to none.	Update your code to use a constant mass matrix or a function that evaluates the variable mass matrix. For more information, check the supported settings of Mass and MassStateDependency in the <code>odeset</code> properties.

Data Analysis

Programming

Load and Save Parts of Variables in V7.3 MAT-Files

The new `matfile` function creates a `matlab.io.MatFile` object that can efficiently load or save to parts of variables in Version 7.3 MAT-Files. Loading part of a variable requires less memory than loading the entire contents of that variable.

For example, these commands create a MAT-file and add data to part of variable `X`:

```
new = matfile('newfile.mat','Writable',true);  
new.X(6:10,6:10) = magic(5);
```

This command loads part of the data into variable `partOfX`:

```
partOfX = new.X(1:8,1:8);
```

Note Syntax such as `size(new.X)` or `new.X(end,end)` temporarily loads the entire contents of variable `X` into memory. To determine the size of a variable without loading, use the `size` method for `matlab.io.MatFile` objects:

```
sizeOfX = size(new,'X');
```

For more information, see the `matfile` reference page or watch this video demo.

Nonmatching Function Name Warning is Now an Error

Compatibility Considerations: Yes

In previous releases of MATLAB, entering a function name that did not match any known function name in the given letter case resulted in a warning. After displaying this warning message, MATLAB attempted to find a function that would match if letter case were ignored. If such a match were found, MATLAB ran this function instead.

In MATLAB R2011b, the MATLAB software generates an error if it can't find an exact-case match. The message displayed by the error may suggest the correct spelling for the function that was entered. The message identifier for this error reads as follows:

```
'MATLAB:dispatcher:InexactCaseMatch'
```

Compatibility Considerations

If you have a program that calls another program with nonmatching letter case, the call to this function now throws an error.

New narginchk Function Replaces nargin

narginchk is a new function that replaces and adds to the functionality of nargin.

The narginchk function differs from nargin in the following ways:

- narginchk accepts only 2 inputs: the minimum and maximum allowable number of arguments one can pass to the currently running function.
- narginchk returns no outputs. Instead, it throws an error if the number of arguments passed to the current function is outside the allowable range

Conversion of Error and Warning Message Identifiers

Compatibility Considerations: Yes

For R2011b, error and warning message identifiers have changed in MATLAB.

Compatibility Considerations

If you have code that uses message identifiers that changed, you must update the code to use the new identifiers. Typically, message identifiers are used to turn off specific warning messages, or in code that uses a try/catch statement and performs an action based on a specific error identifier.

For example, the `MATLAB:eigs:NonPosIntSize` identifier has changed to `MATLAB:eigs:RoundNonIntSize`. If your code checks for `MATLAB:eigs:NonPosIntSize`, you must update it to check for `MATLAB:eigs:RoundNonIntSize` instead. For a mapping of the new identifiers to the original identifiers, see Technical Support solution 1 - ERAFNC.

New Spreadsheet Import Tool

The new Spreadsheet Import Tool allows you to select ranges of data and define rules for handling nonnumeric values. This tool opens instead of the Import Wizard for spreadsheets and comma-separated value (CSV) files. For more information, watch this video demo.

Two Functions Added to netCDF Low-Level Package To Aid Performance

The NetCDF low-level package now includes two functions that you can use to improve performance:

- `netcdf.getChunkCache` – Return default chunk cache settings.
- `netcdf.setChunkCache` – Set the default chunk cache settings.

Improved Performance for TIFF Input and Output

Input and output performance for TIFF files has been improved, when using `imread` and `imwrite`.

Upgrades to Scientific File Format Libraries

The following table lists upgrades to scientific file format libraries used by MATLAB.

Library	Version Upgrade
NetCDF	4.0.1 to 4.1.2
HDF5	1.8.3 to 1.8.6
HDF4	4.2r4 to 4.2.5
HDF-EOS	2.16 to 2.17
TIFF	3.7.1 to 3.9.5

VideoReader Supports MPEG-4 and MOV on Windows 7 Systems

VideoReader now imports MPEG-4 and Apple QuickTime movies, and any other formats supported by Microsoft Media Foundation, on Windows 7 systems. For more information, see the [VideoReader reference page](#).

MATLAB Warns if Listener Defined for Nonobservable Property

Compatibility Considerations: Yes

If you attempt to create a `PreSet` or `PostSet` listener for a property that is not declared as `SetObservable`, MATLAB issues a `MATLAB:class:nonSetObservableProp` warning.

If you attempt to create a `PreGet` or `PostGet` listener for a property that is not declared as `GetObservable`, MATLAB issues a `MATLAB:class:nonGetObservableProp` warning.

In previous releases, MATLAB did not warn in either case, but did not call the listener callback function when a set or get event occurred. In a future release, these warnings will become errors.

Compatibility Considerations

If you use class metadata or the `properties` function to get a list of properties for which you create listeners, add warning/error handling for these conditions. A better approach is to use `findobj` to get the list of observable properties for any given class and assign listeners only for those properties.

MATLAB Warns if Property Is Not Member of Class When Defining Listener

When calling the `event.proplistener` constructor, or calling the `addlistener` method with an array of `meta.property` objects, warning messages alert you if a property is not a member of the correct class.

- **Nonscalar input objects:** if any one of the properties is not a valid member of the class of the object array, MATLAB issues the `MATLAB:class:PropNotMember` warning.
- **Scalar input object:** if any of the properties are not valid dynamic or class properties, MATLAB issues the `MATLAB:class:PropNotMember` or `MATLAB:class:DynPropNotMember` warning.

In previous releases, MATLAB did not warn in either case. In a future release, these warnings will become errors.

Built-In disp Works with Empty Objects

It is now possible to call the built-in `disp` function with empty objects. For example, define the `TestClass` as:

```
classdef TestClass
    properties
        PropertyA = 1;
    end
end
```

Then call the built-in version of `disp`:

```
>> builtin('disp',TestClass.empty)
0x0 empty TestClass
```

```
Properties:
    PropertyA
```

```
Methods
```

In previous releases, calling the built-in `disp` function did not display anything with empty objects.

MATLAB Warns if Class Defines Property as Dependent and Constant

MATLAB now issues a warning if a class defines properties as both Dependent and Constant. In a future release, this warning will become an error.

Support for Switch/Case Statements with Objects

You can construct switch statement blocks using objects as both the switch expression and the case expression. The object's class must define or inherit an `eq (==)` method. See [Using Switch/Case Statements with Objects in Functions Used with Objects](#) for more information.

Functionality Being Removed or Changed

Compatibility Considerations: Yes

Functionality	What Happens When You Use This Functionality?	Use This Instead	Compatibility Considerations
nargchk	Still runs	narginchk	Accepts only min and max inputs, returns no output, generates error.
nargoutchk	Still runs	nargoutchk (see new syntax)	Accepts only min and max inputs, returns no output, generates error.

Graphics and 3-D Visualization

Creating Graphical User Interfaces (GUIs)

External Interfaces/API

Changes to Compiler Support

New Compiler Support

MATLAB Version 7.13 (R2011b) supports these new compilers for building MEX-files on Windows 64- and 32-bit platforms:

- Microsoft Windows Software Development Kit for Windows 7 and .NET Framework 4, Version 7.1
- Intel C++ Composer XE 2011
- Intel Visual Fortran Composer XE 2011

MATLAB Version 7.13 (R2011b) supports the following new compiler for building MEX-files on Mac OS X 64-bit platforms:

- Apple Xcode 4.0.0 with gcc 4.2.x

Compiler Support To Be Phased Out

Support for the following compilers on Windows 64- and 32-bit platforms will be discontinued in a future release, at which time new versions will be supported. For an up-to-date list of supported compilers, see the Supported and Compatible Compilers Web page.

- Intel C++ Version 11.1
- Intel Fortran Version 11.1

New Object Support for mxGetProperty and mxSetProperty Functions

You can read and modify properties of Java and COM objects using the `mxGetProperty` and `mxSetProperty` functions.

MEX Header File Does Not Define C++ Type `char16_t`

Compatibility Considerations: Yes

The `matrix.h` header file, used by the `mex.h` header file for building C/C++ MEX-files, no longer defines the C++ type `char16_t`.

Compatibility Considerations

If your MEX-file uses the `char16_t` type, you must include the appropriate header file for your compiler in order to build the MEX-file. For example, the header file for Microsoft Visual Studio Version 10.0 is `yvals.h`.

New Support for Features in Microsoft .NET Framework

Compatibility Considerations: Yes

- “Support for Cell Arrays” on page 208
- “Support for Auto-Conversion of Multidimensional Arrays” on page 208

Support for Cell Arrays

Creating Cell Arrays from .NET Stings and Objects

Use the MATLAB `cell` function to convert .NET `System.String` and `System.Object` arrays to MATLAB cell arrays. For more information, see [Converting .NET Arrays to Cell Arrays](#).

Passing Cell Arrays to .NET Methods

If an input argument to a .NET property or method is an array of `System.Object` or `System.String`, you can pass a cell array. MATLAB automatically converts a cell array into the appropriate .NET array. For more information, see [Pass Cell Arrays](#).

Support for Auto-Conversion of Multidimensional Arrays

You can pass MATLAB arrays directly to .NET without explicitly converting them into .NET arrays. MATLAB also converts an array of a lower dimensionality to a higher dimensionality .NET array. For more information, see [Pass Arrays](#).

Compatibility Considerations

In most cases, you no longer need to use the `NET.convertArray` function. Review your MATLAB code to update the use of this function. If you continue to use `NET.convertArray`, note the following change of behavior for empty matrices:

- If you call `NET.convertArray` with an N-D empty matrix and try to convert it to 1-D .NET array, MATLAB throws the following error:

Source and destination array dimension sizes do not match.

- Different results for:

```
NET.convertArray(rand(0,1,1))
```

As of R2011a, MATLAB creates a `System.Double[,]`. In R2011b, MATLAB creates a `System.Double[]`.

COM Automation Server Error Message Formatting

Although some MATLAB Command Window messages have been reformatted (see “Error Messages Reformatted for Improved Readability and Navigation” on page 173), error messages from the `Execute` function can still be identified with leading ??? characters.

R2011a

Version: 7.12
New Features: Yes
Bug Fixes: Yes

Desktop Tools and Development Environment

Desktop

New features and changes introduced in Version 7.12 (R2011a) are:

MATLAB Menus Display at the Top of the Apple Mac Screen

Previously when running on Apple Mac, menus displayed at the top of the MATLAB desktop. In addition, if a tool was undocked from the desktop, the menu displayed at the top of that tool. Now, to be consistent with the behavior of most Mac applications, MATLAB menus display at the top of the Mac screen.

Help Browser

- “New Location and Archived Content for Product Documentation” on page 214
- “Submit Support Requests Directly from MATLAB” on page 215


New Location and Archived Content for Product Documentation

The new MathWorks Web site location for product documentation is <http://www.mathworks.com/help/>. Accessing the old URL, <http://www.mathworks.com/access/helpdesk/help/helpdesk.html>, redirects you the new location.

In addition to all current product documentation, the new location provides archived product documentation from all releases going back to R13sp2 (including Japanese, when available). To go to the archive, click the View documentation for other releases link. The archived release documentation is available only at the MathWorks Web site, and not via the Help browser.

To view some documentation you must log on to www.mathworks.com with your MathWorks user name and password. For example, you need to log in to view current PDF files and documentation from prior releases.

The **View > Page Location** dialog box in the Help browser now links to documentation at the MathWorks Web site that accompanies the release you are currently running. For example, when you run R2011a, the dialog box looks like this.



As of R2011a, the Help Browser **View > Page Location** dialog box (shown above) is available on Japanese language systems.

Submit Support Requests Directly from MATLAB

As of this release, if you need assistance from MathWorks product support, you can request it directly from the MATLAB desktop. Selecting the **Submit a MathWorks Support Request** option from the **Help** menu opens a login dialog for you to provide the e-mail address and password for your MathWorks account. After you log in, a form displays for you to create a service request. Select the product for which you want help, explain the issue you are having, give the request a meaningful title, describe the issue you are having, provide reproduction steps, and attach files that enable Technical Support to follow the steps.

If you do not have a MathWorks account, the login form enables you to create one. MathWorks accounts are free and without obligation. You can also use the account login form to obtain a forgotten MathWorks password. You can log out before submitting your request or remain logged in.

If you are not connected to the Internet or if you are connected to the Internet via a proxy server when you attempt to create a help request, you are prompted to save your form to a text file. You can then send the file as e-mail to support@mathworks.com. You can also upload the description and supporting files directly to the MathWorks FTP site.

For an example of submitting a support request, see this video demo. For further details about requesting service requests from MATLAB, see Contact Technical Support.

Managing Files

New features and changes introduced in Version 7.11 (R2011a) are:

- “Renaming Files and Folders in the Current Folder Browser Now Reflected in the Editor” on page 216
- “Options Names Changed for Locating and Opening Files and Folders Outside the MATLAB Desktop” on page 217
- “Comparison and Merging of MAT-file Variables” on page 217
- “Filter Results in Folder Comparisons” on page 217
- “Showing Differences Only in Text Comparisons” on page 217

Renaming Files and Folders in the Current Folder Browser Now Reflected in the Editor

If a file is open in the Editor and you:

- Rename that file in the Current Folder browser, then the file name updates in the Editor
- Rename the folder containing that file in the Current Folder Browser, then MATLAB updates the file specification for all open Editor documents in the renamed folder
- Delete that file from the Current Folder browser, then MATLAB deletes the file from disk and renames the Editor document to `Untitled*`

If more than one unnamed document is open in the Editor, then MATLAB renames the deleted document `Untitledn*`, where `n` is an integer.

However, modifying file and folder names from either of the following does not update names for open documents in the Editor:

- The operating system file manager — such as Windows Explorer
- The MATLAB Command window — using `movefile`, for instance

Options Names Changed for Locating and Opening Files and Folders Outside the MATLAB Desktop

To locate a file or folder in Windows Explorer or Apple Mac Finder, you previously used the Current Folder browser context-menu option, **Locate on Disk**. Now the option is one of the following:

- On Microsoft Windows systems—**Show in Explorer**
- On Macintosh systems—**Show in Finder**

In addition, from the Current Folder browser, you can open the current folder in Explorer or Finder. Right-click in white space, and then select **Open Current Folder in Explorer** or **Open Current Folder in Finder**.

Comparison and Merging of MAT-file Variables

When comparing MAT-files, you now can view details of differences between variables to see which fields of a structure are different and to view differences in individual elements of an array. You can merge changes between files by copying variables from one file to another. For details, see [Comparing MAT-Files](#).

Filter Results in Folder Comparisons

You now can define filters to exclude unimportant differences when comparing folders. For example, you can exclude backup files or files created by a revision control system. Filters can save time when reviewing differences, especially when comparing many subfolders. For details, see [Comparing Folders and Zip Files](#).

Showing Differences Only in Text Comparisons

When comparing text files, you now can specify whether to show only differences. Use the new toolbar button in the Comparison Tool to hide sections of the report that do not include any differences. It can be useful to hide unmodified lines in large text comparison reports. For details, see [Comparing Text Files](#).

Editing and Debugging MATLAB Code


Compatibility Considerations: Yes

New Desktop features and changes introduced in Version 7.11 (R2011a) are:

- “Change to Tooltip and Behavior for M-Lint Messages” on page 218
- “Changed Default Preference for Deleting Autosaved Files” on page 219
- “Shared Scope Color Preferences Apply to Persistent and Global Variables” on page 219

Change to Tooltip and Behavior for M-Lint Messages

Previously, when you hovered the *mouse pointer* over code in the Editor that has an autofixable M-Lint warning message, a tooltip opened that included the phrase, **Press Alt + Enter to fix**, as shown in this image.



Now, this phrase is removed from the M-Lint tooltip. You can still use the keyboard shortcut, **Alt+Enter**, to apply the autofix, but your *cursor* must be within the code to which the autofix will be applied.

Compatibility Considerations

When an M-Lint tooltip is open and you want to apply the autofix for that warning, click the **Fix** button. To apply the same autofix using a keyboard shortcut, move the cursor within the code that generates the warning, and then click **Alt+Enter**.

Changed Default Preference for Deleting Autosaved Files

Previously, the **Automatically delete autosave files** preference for the Editor was disabled by default. Now, it is enabled by default. However, as usual, MATLAB retains settings you set explicitly in a previous release (unless you delete `matlab.prf.`)

For more information, see [Autosaving Files and Where MATLAB Stores Preferences](#).

Shared Scope Color Preferences Apply to Persistent and Global Variables

Previously, the preference for **Variables with shared scope** was labeled **Nonlocal variables** and it affected the color of variables within nested functions only. Now, the Editor also applies this color preference to variables you declare as global or persistent.

This feature makes it easier to find reuses of a variable, which sometimes indicate variable scoping problems. For details, including information on how to disable or change the colors that the Editor uses for variables with shared scope, see [Avoid Variable and Function Scoping Problems](#).

Publishing MATLAB Code

New Desktop features and changes introduced in Version 7.11 (R2011a) are:

- “Change to Menu Option for Including Blocks of LaTeX Code” on page 220
- “Menu Option to Include Inline LaTeX Math in Published MATLAB Code” on page 220

Change to Menu Option for Including Blocks of LaTeX Code

Previously, if you wanted to include blocks of LaTeX code within your MATLAB code intended for publishing, you selected **Cell > Insert Text Markup > LaTeX Equation**. Now you select **Cell > Insert Text Markup > LaTeX Display Math**. The name of the option was changed to better distinguish it from a new publishing option that enables you to include inline LaTeX equations in your published code.

For details see LaTeX Display Math.

Menu Option to Include Inline LaTeX Math in Published MATLAB Code

The Cell menu now provides an option for including inline LaTeX equations. Position the cursor within the comment line where you want the LaTeX equation to appear, and then select **Cell > Insert Text Markup > LaTeX Inline Math**.

For details see Inline LaTeX Math Equations.

MATLAB Notebook Menu Labels

Menu labels for MATLAB Notebook are changed. To ensure your menu options are up to date, and match those presented in the documentation, run the following command:

```
notebook -setup
```

MathWorks recommends you run this command whenever you install a new version of MATLAB.

Mathematics

New Function `rng`

The new `rng` function controls the random number generator used by `rand`, `randi`, and `randn`. For a demonstration, see [this instructional video](#).

`rng` is the recommended alternative to former `rand` and `randn` input syntaxes `'seed'`, `'state'` and `'twister'`. `rng` is a simpler alternative to the `RandStream` class. To use `rng`, see the documentation on [Updating Your Random Number Generator Syntax](#).

New Function `ichol`

The new `ichol` function performs incomplete Cholesky factorization and is the recommended alternative to `cholinc`.

New Option for `gammainc`

The new options `gammainc(X,A, 'scaledlower')` and `gammainc(X,A, 'scaledupper')` now return scaled versions of the incomplete gamma function `gammainc`.

Performance Enhancement

- Matrix transpose
- Element-wise single precision functions
- Sparse matrix indexed assignment
- Many linear algebra functions
- Convolution for long vectors and large matrices with `conv` and `conv2`

Changes to qr

Compatibility Considerations: Yes

In R2010a and R2010b, the upper triangular output R from the full `qr` function was guaranteed to have real and nonnegative diagonal elements. In this release, the behavior reverts to that of R2009b and prior releases. That is, the diagonal of R may contain complex and negative elements, and will affect the unitary output Q correspondingly.

Compatibility Considerations

Since the QR factorization is not unique, these different results are still correct. Ensure that your code does not depend on the values of the elements of the factors Q and R .

Functionality Being Removed

Compatibility Considerations: Yes

Function Name	What Happens When You Use This Function	Use This Function Instead	Compatibility Considerations
bessel	Errors	besselj	Replace all instances of <code>bessel</code> with <code>besselj</code> .
intwarning	Errors	None	Remove all instances of <code>intwarning</code> from your code.
luinc	Warns	ilu	Replace instances of <code>luinc</code> with <code>ilu</code> .
cholinc(X, 'inf')	Warns	None	Remove all instances of <code>cholinc(X, 'inf')</code> from your code.
All other syntaxes of <code>cholinc</code> except <code>cholinc(X, 'inf')</code>	Warns	ichol	Replace these instances of <code>cholinc</code> with <code>ichol</code> .
RandnAlg property of RandStream class	Still runs	NormalTransform property of RandStream class	Replace all existing instances of <code>RandnAlg</code> with <code>NormalTransform</code> .
setDefaultStream method of RandStream class	Still runs	setGlobalStream method of RandStream class	Replace all existing instances of <code>RandStream.setDefaultStream</code> with <code>RandStream.setGlobalStream</code> .
getDefaultStream method of RandStream class	Still runs	getGlobalStream method of RandStream class	Replace all existing instances of <code>RandStream.getDefaultStream</code> with <code>RandStream.getGlobalStream</code> .
rand or randn with the 'seed', 'state' or 'twister' inputs	Still runs	rng	See Updating Your Random Number Generator Syntax in the MATLAB Mathematics documentation.

Programming

Regenerate P-code Files Built Before Version 7.5

Compatibility Considerations: Yes

To enable the MATLAB software to take advantage of significant performance improvements planned for a future release, MathWorks recommends that you begin to regenerate any P-code files you use that were generated prior to MATLAB 7.5 (release R2007b). P-code files generated in releases earlier than R2007b will not run in this future release with the new performance features enabled.

Compatibility Considerations

Using MATLAB 7.5 or later, rebuild any P-code files that you expect to need in the future.

VideoWriter Supports Motion JPEG 2000 Files

VideoWriter now creates Motion JPEG 2000 (.mj2) files, which support logging data with these features:

- Multi-byte precision, such as 10, 12, or 16 bits
- Signed data values
- Lossless compression

For more information, see the [VideoWriter](#) reference page.

audioplayer and audiorecorder Support Device Selection on All Platforms

Compatibility Considerations: Yes

`audioplayer` and `audiorecorder` now allow you to specify the input or output device on all supported platforms. In previous releases, you could only specify devices on Microsoft Windows systems.

Compatibility Considerations

- `audioplayer`, `audiorecorder`, and `audiodevinfo` now use different technology for enumerating system input and output devices. If your existing code specifies a device ID (other than the default, -1), check whether you need to change the ID. To determine your device IDs, call `audiodevinfo`.
- `audioplayer` does not support overlapping playback. For example, in this code, the second call to `play` returns an error:

```
chirpData = load('chirp.mat');
chirpObj = audioplayer(chirpData.y, chirpData.Fs);

gongData = load('gong.mat');
gongObj = audioplayer(gongData.y, gongData.Fs);

play(chirpObj);
play(gongObj);
```


New Class Forms the Basis for Heterogeneous Hierarchies

The `matlab.mixin.Heterogeneous` class enables you to form heterogeneous arrays containing instances of classes derived from this class. You can create heterogeneous hierarchies of both handle and value classes.

New Class Provides the Basis for Customizable Handle Object Copy Method

The `matlab.mixin.Copyable` class enables you to define handle classes that inherit a copy method whose behavior you can modify in subclasses.

MATLAB Meta-Classes Can Now Form Heterogeneous Arrays

All MATLAB meta-classes are now defined in a heterogeneous hierarchy, which enables the formation of heterogeneous arrays of meta-class objects. This capability enables functions like `findobj` and `findprop` to return heterogeneous arrays containing instances of meta-classes of different specific types. The hidden class `meta.MetaData` forms the root of the heterogeneous hierarchy.

New High-Level NetCDF Functions

MATLAB now includes several new functions that provide a high-level interface to NetCDF files. These functions let you read and write to NetCDF files, without having to use the programming paradigm required by the low-level functions in the netCDF package. Using these functions, you can create a new NetCDF file based on the schema of an existing file, convert files between NetCDF formats, and create a new NetCDF file by merging together two existing NetCDF files.

- `nccreate` — Create variable in NetCDF file
- `ncdisp` — Display contents of netCDF file
- `ncinfo` — Return information about netCDF file
- `ncread` — Read data and attributes from netCDF file
- `ncreadatt` — Read global attribute or attribute associated with variable from netCDF file.
- `ncwrite` — Write data to netCDF file
- `ncwriteatt` — Write attribute to netCDF file
- `ncwritschema` — Add netCDF schema definitions to a NetCDF file

New High-Level HDF5 Functions

Compatibility Considerations: Yes

MATLAB now includes several new high-level functions for working with HDF5 files. These functions let you read and write to HDF5 files, without having to use the programming paradigm required by the low-level functions in the HDF5 package.

- `h5create` — Create HDF5 data set
- `h5disp` — Display contents of HDF5 file
- `h5info` — Return information about HDF5 file
- `h5read` — Read data from HDF5 data set.
- `h5readatt` — Read attribute from HDF5 group or data set
- `h5write` — Write to HDF5 data set
- `h5writeatt` — Write HDF5 attribute to group or data set

Compatibility Considerations

The new high-level HDF5 functions have the following compatibility considerations with the existing high-level HDF5 functions.

- `hdf5read` is not recommended. Use `h5read` instead.
- `hdf5write` is not recommended. Use `h5write` instead.
- `hdf5info` is not recommended. Use `h5info` instead.

Two New Functions Added to CDFLIB Package

The MATLAB interface to the CDF library now includes the following new functions.

- `cdflib.setFileBackward` — Sets the backward compatibility mode. If the backward mode is set to on, files created can be read by clients using version 2.7 of the library
- `cdflib.getFileBackward` — Return the current backward compatibility mode setting.

HDF4 Functions Grouped into Packages

The MATLAB HDF4 low-level functions and HDF EOS functions are now grouped into three new packages:

- `matlab.io.hdf4.sd` — access to more than 50 functions in the HDF library SD interface
- `matlab.io.hdfeos.gd` — access to more than 50 functions in the HDF-EOS library grid interface
- `matlab.io.hdfeos.sw` — access to more than 50 functions in the HDF-EOS library swath interface

For example, MATLAB previously included one function, `hdfsd`, that you used to call all the routines in the HDF library SD interface. Now, the new package `matlab.io.hdf4.sd` contains many individual functions that correspond to routines in the HDF SD Interface C library.

FITSREAD Function Now Supports Data Subsetting

The MATLAB `fitsread` function now supports data subsetting by using several new options: `PixelRegion`, `TableColumns`, and `TableRows`.

Unrecognized Name Warning Changed to Error

Compatibility Considerations: Yes

In earlier releases of MATLAB, a statement in which an unrecognized (e.g., misspelled) name immediately follows a function name and dot (.) results in a warning instead of an error. Here is the format this type of statement:

```
functionname.unrecognizedname
```

The following example shows such a statement case and part of the resulting warning:

```
simulink.badname
```

```
Warning: Direct access of structure fields returned by a  
function call (e.g., call to simulink) is not allowed. ...
```

In addition to being misleading, handling this case with merely a warning also allows the function (`simulink`, in this case) to execute, regardless of the fact that the name to the right of the dot is invalid.

In MATLAB version 7.12 (R2011a), this type of statement throws an error. The text of the error message is:

```
simulink.badname
```

```
??? Undefined variable "simulink" or function "simulink.badname".
```

Compatibility Considerations

Any such statements in your code that have only generated a warning message in past releases will now throw an error. Any such error that is not caught and handled appropriately will terminate the function in which it occurs. MathWorks recommends that you replace the unrecognized name to the right of the dot with the correct name.

This change also affects the output of the `lasterror` function if you attempt to access any field value (`message`, `identifier`, or `stack`) directly. Earlier versions of MATLAB generate a warning:

```
lasterror.message
```

Warning: Direct access of structure fields returned by a function call (e.g., call to `lasterror`) is not allowed. ...

This and future versions throw an error:

```
lasterror.message  
??? Undefined variable "lasterror" or function "lasterror.message".
```

Regular Expressions Support Zero-Length Matching

Regular expressions in MATLAB now support successful zero-length matching. See the documentation on Empty Match mode in the description of Command Options for the `regexp` function.

Growing Arrays Is Faster

This release improves the performance of growing an array in the trailing dimension if that array has not been preallocated.

Error Checking Improved

Compatibility Considerations: Yes

MATLAB provides more effective error checking and returns new error messages in the following cases.

Nonstatic Method

A reference to a class method using the class name is valid only in cases where the method is static. Therefore, code of the form:

```
ClassName.ordinaryMethod
```

Where `ordinaryMethod` is not a static method of the class `ClassName`, previously returned the error: `MATLAB:class:InvalidStaticMethod`.

This code now returns the error:

```
MATLAB:subscripting:classHasNoPropertyOrMethod
```

Nonexistent Method Name

A reference to a nonexistent method name:

```
obj.badName
```

Where `badName` is not a method defined by the class of `obj`, previously returned the error: `MATLAB:noSuchMethodOrField`.

This code now returns the error:

```
MATLAB:subscripting:classHasNoPropertyOrMethod.
```

Compatibility Considerations

Code that checks for the specific errors previously returned must be updated to check for the new errors.

Functions and Function Elements Being Removed

Compatibility Considerations: Yes

Function or Function Element Name	What Happens When You Use the Function or Element?	Use This Instead	Compatibility Considerations
audioplayer(BufferLength)	No effect (no-op)		Remove all instances of BufferLength.
audioplayer(NumberOfBuffers)	No effect (no-op)		Remove all instances of NumberOfBuffers.
hdf5read	Still runs	h5read	Replace with preferred function.
hdf5write	Still runs	h5write	Replace with preferred function.
hdf5info	Still runs	h5info	Replace with referred function.

Graphics and 3-D Visualization

Plot Catalog with a New Look, More Plots, and Diagnostics

The Plot Catalog GUI now offers a wider variety of plotting options. Its appearance and operation closely resemble the Plot Selector, with short descriptions of each graph type and a search box. It also categorizes graphs by type and by toolbox, and lets you designate personal Favorites (the top menu category). Access the Plot Catalog from the Plotting Tools Figure Palette, the bottom of the Plot Selector menu in the Workspace Browser, the Variable Editor, and various context menus. For a demonstration, see this instructional video.

This table lists the differences and similarities between the Plot Catalog and the Plot Selector.

	Plot Catalog	Plot Selector	Both
Window Characteristics	Opens in its own window, which persists until you close it	Opens in a pop-up window that closes after it loses focus	Show icons for plot types with descriptions and Favorites.
Help for Plot Types	Displays partial help listings from reference pages in a resizable pane within its window	Opens a popup help window with reference information when you hover	Provide the same help content and a More Help hyperlink to the Help Browser.
Plot Creation and Validation	Provides a field in which you can type variable names or expressions to plot	Plots variables you select in the Workspace browser or Variable Editor	Validate input variables and display diagnoses of incorrect or insufficient inputs.
Plot Destination	Current figure or new figure	Current figure	Create figure, if none exists

Previously, the Plot Catalog did not validate input data. If you provided incorrect inputs for a plotting function, it attempted to use them, resulting in an incorrect plot or errors. Now, the Plot Catalog provides the same diagnostics as the Plot Selector. When you type workspace variable names into the Variables box on top, the tool validates variable types, sizes, and ordering. If validation fails, the Plot Selector provides a diagnostic message in its Help pane and does not let you run the plotting function.

In addition to MATLAB plots, the Plot Catalog offers the same set of choices as the Plot Selector. The choices include most types of plots from the following toolboxes (if installed):

- Control System Toolbox™
- Curve Fitting Toolbox™
- DSP System Toolbox™
- Financial Toolbox™
- Image Processing Toolbox™
- Mapping Toolbox™
- Signal Processing Toolbox™
- Statistics Toolbox™
- System Identification Toolbox™

For more information about the Plot Catalog, see [Selecting a Graph from the Plot Catalog](#). For information on the Plot Selector, see [“Enhanced Plot Selector Simplifies Data Display”](#) on page 426.

Creating Graphical User Interfaces (GUIs)

Do not Repopulate Menus on the Mac from Inside Their Callbacks

Compatibility Considerations: Yes

In R2011a, figures display their menus on the Mac screen menubar instead of across the top of figure windows. Prior to R2011a, GUIs could create dynamic menus using callbacks that completely deleted, and then repopulated the contents of menus. But on a Mac, running a GUI with a menu whose callback changes all items in this manner can result in the display of a blank menu (no items). The unexpected behavior only happens when a `uimenu` callback deletes all submenus (child `uimenu` components) and repopulates the menu with a new set of items at the time the menu opens.

In R2011a, on the Mac platform only, `uimenu` callbacks are no longer able to replace all submenus during menu selection. Note that repopulating some (not all) menu items does not create this issue. However, it is not good programming practice to remove and insert menu items within a menu callback routine.

For more information, see “MATLAB Menus Display at the Top of the Apple Mac Screen” on page 213.

Compatibility Considerations

If you have a `uimenu` callback that *repopulates all of its menu items* when you open that menu, you must change that code if you want it to work on a Mac. For example, your code might be able to remove and install submenus from outside of the callback that handles the menu. The callback can also rename, disable, hide, and show submenus instead of deleting them and creating new ones. The Mac is the only platform impacted by this incompatibility. Menus on Microsoft Windows, Unix, and Linux continue to behave as they did in previous releases.

Functions and Function Elements Being Removed

Compatibility Considerations: Yes

Function or Function Element Name	What Happens When You Use the Function or Element?	Use This Instead	Compatibility Considerations
pagesetupdlg	Warns	printpreview	printpreview provides all functionality and more, except for some unit choices. Update any GUIs that call pagesetupdlg to do page setup.

External Interfaces/API

Changes to Compiler Support

Compatibility Considerations: Yes

New Compiler Support

MATLAB Version 7.12 (R2011a) supports these new compilers for building MEX-files:

Linux (64- and 32-Bit) Platforms

- GNU gfortran 4.3.x

Apple Mac 64-Bit Platforms

- Apple Xcode 3.2 with gcc 4.2.x

Compiler Support To Be Phased Out

Support for the following compilers will be discontinued in a future release, at which time new versions will be supported. For an up-to-date list of supported compilers, see the Supported and Compatible Compilers Web page.

Microsoft Windows 32-Bit Platforms

- Microsoft Visual Studio 2005 SP1
- Visual C++ 6.0

Windows 64-Bit Platforms

- Microsoft Visual Studio 2005 SP1

Discontinued Compiler Support

MATLAB no longer supports the following compilers:

Windows (64- and 32-Bit) Platforms

- Microsoft Visual Studio 2008 (9.0) Express
- Intel Visual Fortran Version 10.1

Linux (64- and 32-Bit) Platforms

- GNU g95 0.90

Mac 64-Bit Platforms

- Xcode 3.1 with gcc 4.0.1

Compatibility Considerations

To ensure continued support for building your MEX-files, consider upgrading to another supported compiler. For an up-to-date list of supported compilers, see the Supported and Compatible Compilers Web page.

Changes to Shared Library Compiler Support

Compatibility Considerations: Yes

In MATLAB Version 7.12 (R2011a), you can use the `loadlibrary` command with any supported compiler. For an up-to-date list of supported compilers, see the [Supported and Compatible Compilers Web page](#).

Compatibility Considerations

You must run `mex -setup` before using the `loadlibrary` command. For information about selecting a compiler, see [Selecting a Compiler on Windows Platforms](#) or [Selecting a Compiler on UNIX Platforms](#).

New Support for Features in Microsoft .NET Framework

Compatibility Considerations: Yes

Support for .NET System.Enum Objects

MATLAB exposes .NET enumerations as native .NET classes:

- Support for non-Int32 underlying types
- Support for bit-wise `bitand`, `bitnot`, `bitor`, and `bitxor` operators
- Support for invocation of `System.Enum` methods, such as the `HasFlag` method in Framework Version 4.0
- Support for comparison and binary operators `eq`, `ne`, `ge`, `gt`, `le`, and `lt` on enumeration types

See .NET Enumerations in MATLAB.

Compatibility Considerations

MATLAB displays an error when you use the enumeration command to return arrays of .NET enumeration objects. To read enumeration members into MATLAB arrays, see [Refer to a .NET Enumeration Member](#).

MATLAB enumerations no longer inherit from the MATLAB `int32` class.

You cannot create arrays of .NET enumeration objects. For example, if you type:

```
a = [EnumTest.Colors.Red EnumTest.Colors.Blue]
```

MATLAB displays:

```
??? Array formation and indexing are not allowed on .NET objects.
```

To combine members of an enumeration into a MATLAB variable, see [Combining Enumerations into a Single MATLAB Variable](#).

Support for Asynchronous .NET Delegate Callback Handling

You can use delegates to call a synchronous method asynchronously. See [Calling a .NET Method Asynchronously](#).

R2010bSP2

Version: 7.11.2
New Features: No
Bug Fixes: Yes

R2010bSP1

Version: 7.11.1
New Features: No
Bug Fixes: Yes

R2010b

Version: 7.11
New Features: Yes
Bug Fixes: Yes

Desktop Tools and Development Environment


Desktop

New desktop features and changes introduced in Version 7.11 (R2010b) are:

- “Ability to Customize the Date Format ” on page 265
- “Keyboard Shortcuts Preferences Integrated with File Exchange” on page 266
- “MATLAB Provides Enumeration Template” on page 266

Ability to Customize the Date Format

You can now customize the date format that the Current Folder browser and the Command History window use to display dates, such as the dates indicated here:



Previously, the date format in both of these tools was M/d/yy (for instance, 6/4/90 for June 4, 1990) and you could not change it. Now, both tools use the operating system short date format. For details, see [Customizing the Column Display](#).

Keyboard Shortcuts Preferences Integrated with File Exchange

MATLAB now integrates keyboard shortcuts preferences with File Exchange. You can access File Exchange directly from the Keyboard Shortcuts Preferences panel and find:

- MATLAB keyboard shortcuts available in Version 7.9 (R2009a) and earlier releases
- Keyboard shortcuts sets created by other MATLAB users

For details, see [Download Keyboard Shortcut Settings Files from File Exchange](#) .

MATLAB Provides Enumeration Template

MATLAB provides a template for classes that define enumerations. Enumeration classes enable you to define a fixed set of names representing a particular type of value. Choose **File > New > Enumeration**. For more information, see [Enumerations](#).

Help Browser

- “New Language Preference for Help Browser” on page 267
- “Accessing Product Documentation in Japanese” on page 267

New Language Preference for Help Browser

If your system displays documentation in Japanese, you can use the **Language** panel in the Help Preferences dialog to instruct the Help browser to display documentation in English instead of Japanese. You can toggle between languages with the preference panel, enabling you to revert to Japanese at any time. The option changes the language used in the Help Browser and for GUI context-sensitive help, but it does *not* affect the language appearing in menus or elsewhere in products.

For example, the `help` command still provides help in Japanese after you switch the Help browser to English. The **Language** preference is available only when the system locale is Japanese and the Japanese documentation is installed. If the documentation for a product is not translated, the Help Browser displays the English documentation for it no matter how you set the preference.

Accessing Product Documentation in Japanese

MathWorks usually provides Japanese translations of product documentation about 2 months after new versions of products first ship. When you install the new version of a product, the *previous version* of translated documentation is installed in most cases.

To read the most current documentation for your release, switch the Help browser to English. After the translations of the latest documentation are available, you can download and install them in your products. At that time, you can find a link to download the latest translated documentation on the Japanese documentation start page.

Managing Files

New features and changes introduced in Version 7.11 (R2010b) are:

- “Ability to View Zip File Contents in Current Folder Browser” on page 268
- “Details Panel of Current Folder Provides Preview of Graphic Files” on page 268
- “Current Folder Browser Indicates Whether File Is Modified in Editor” on page 268
- “Compare Zip Files and Folders” on page 269
- “Enhanced Comparison Tool” on page 269

Ability to View Zip File Contents in Current Folder Browser

Using the Current Folder browser, you can now view the files in a zip file without having to extract them. This feature enables you to:

- Confirm the contents of a newly created zip file
- Selectively open items from a zip file
- Add or remove files from the zip file

For details, see [Creating and Managing Zip File Archives](#) or watch the [Zip File Browsing video demo](#).

Details Panel of Current Folder Provides Preview of Graphic Files

Now, when you select a JPEG, JPG, BMP, WBMP, PNG, or GIF image in the Current Folder browser, the Details panel displays a thumbnail of the image and lists its width and height in pixels. For more information, see [Viewing File Details Without Opening Files](#) or watch the [File Preview Enhancements video demo](#).

Current Folder Browser Indicates Whether File Is Modified in Editor

Now, if you modify a file in the Editor, but have not yet saved the changes, the Current Folder browser indicates the file state. An asterisk (*) appears

next to the name of such a file in the Current Folder browser. In addition, when you select such a file in the Current Folder browser, the detail panel reflects the modified file, not the file saved on disk. This feature is useful when you are creating zip files and want to be sure that all files included in the archive are saved and up-to-date. For details see, [Viewing File Details Without Opening Files](#) or watch the [File Preview Enhancements](#) video demo.

Compare Zip Files and Folders

You can now compare any combinations of zip files, folders, and Simulink Manifests with the Comparison Tool. Right-click files or folders in the Current Folder browser and choose **Compare Selected Files/Folders**, or **Compare Against > Choose**.

For details, see [Comparing Folders and Zip Files](#).

Enhanced Comparison Tool

The Comparison Tool now provides the following capabilities:

- Select what type of comparison to run from a list of possible comparison options, e.g., text, binary or XML comparison.
- Enhanced MAT-file comparisons now include size, data type and change summary.
- New option to ignore whitespace changes in text comparisons.

For details, see [Comparing Files and Folders](#).

Editing and Debugging MATLAB Code

New Desktop features and changes introduced in Version 7.11 (R2010b) are:

- “Ability to Save File to Backup Without Closing That File” on page 270
- “Enhanced Comment Wrapping” on page 270
- “Variable and Function Highlighting” on page 271
- “Options for Setting Current Folder and Search Path Available from Editor Context Menu” on page 271
- “Open As Text Option” on page 272

Ability to Save File to Backup Without Closing That File

You now can save a file that is open in the Editor to a backup file. Select **File > Save Backup**, and then specify a backup file name. The file that is active in the Editor when you perform the save operation remains active. If changes to the active file prove problematic, you can use the backup file to return to a known state or to compare with the active file. This comparison can help you determine where errors exist.

For information on other save options, see Save Files.

Enhanced Comment Wrapping

The enhanced ability to wrap MATLAB comments includes:

- Wrapping an entire block of comments by selecting **File > Wrap Comments**.

There is no need to select the block of comments first. For details see Wrap Comments Manually.

- Specifying where you want column counting to begin.

For example, if you indent comments, you can specify that you want the maximum width of comments to be 75 columns from the start of a comment, rather than from the start of a line. To set **Comment formatting** preferences, select **File > Preferences > Editor/Debugger > Language**.

Variable and Function Highlighting

The Editor now presents variables that are not local variables in a teal blue color, by default. Also by default, when you click a function or local variable, the Editor highlights it and all other references to it in a sky blue color. As demonstrated in the Variable and Subfunction Highlighting video demo, this feature makes it easier to:

- Find unintentional reuses of a variable within a nested function
For details, see Avoid Variable and Function Scoping Problems.
- Navigate through a file from function to function reference or variable to variable reference
For details, see Navigate to a Specific Location.
- Search a file for a particular function or variable name
For details, see Find and Replace Functions or Variables in the Current File.

To disable or change the colors that the Editor uses for variable and function highlighting, see Use Automatic Function and Variable Highlighting.

Options for Setting Current Folder and Search Path Available from Editor Context Menu

When multiple documents are open and docked in the Editor, you can right-click the document tab, and then from the context menu choose:

- **Change Current Folder to *folder-name***
- **Add *folder-name* to Search Path or Remove *folder-name* from Search Path**, respectively
- **Locate on Disk**

This option locates the document in your operating system file browser. It is not available on Linux platforms.

- **Copy Full Path to Clipboard**

Open As Text Option

You can use the **File > Open as Text** option to open a file in the Editor as a text file, even if the file type is associated with another application or tool. This feature is useful, for example, if you import a tab-delimited data file (.dat) into the workspace, and then you find you want to add a data point. For details, see [Open Existing Files](#).

Mathematics

64-Bit Integer Arithmetic

Core MATLAB arithmetic functions now support `int64` and `uint64` classes natively. Functions added are `plus (+)`, `minus (-)`, `uminus (-)`, `times (.*)`, `rdivide ./`, `ldivide (.\)`, `power (.^)`, `rem`, `mod`, `bitcmp`, `any`, `all`, `sum`, `diff`, `colon (:)`, `sign`, `accumarray`, and `bsxfun`.

New Utility Functions: `isrow`, `iscolumn`, `ismatrix`

New functions `isrow`, `iscolumn`, and `ismatrix` provide basic information about inputs.

Output Option for Point Distances in DelaunayTri/nearestNeighbor Method

The two-output form of `DelaunayTri/nearestNeighbor` returns the corresponding Euclidean distances between the query points and their nearest neighbors.

Changes to convhull and delaunay Functions

The functions `convhull` and `delaunay` now support 3-D input in either multiple vector or multicolumn matrix format. In addition, the `simplify` option for `convhull` provides the option of removing vertices that do not contribute to the area or volume of the convex hull.

Performance Enhancements

- Three-Output Form of `svd`

The three-output form of `svd` displays significantly enhanced performance.

- Sparse Column Assignment

The assignment of elements into multiple columns of a MATLAB sparse matrix displays significantly enhanced performance.

- Trigonometric Functions

All degree-based trigonometric functions (`sind`, `cosd`, `tand`, `cotd`, `secd`, `cscd`) and their inverses (`asind`, `acosd`, `atand`, `acotd`, `asecd`, `acscd`) display significantly enhanced performance.

Functions Being Removed

Compatibility Considerations: Yes

Function Name	What Happens When You Use This Function	Use This Function Instead	Compatibility Considerations
bessel	Warns	besselj	Replace all instances of <code>bessel</code> with <code>besselj</code> .
erfcov	Errors	erf, erfc, erfcx, erfcinv, or erfcinv	See the function reference pages for the individual functions.
intwarning	Errors	None	Remove all instances of <code>intwarning</code> from your code.

optimset Errors for Optimization Toolbox Options

Compatibility Considerations: Yes

If you do not have an Optimization Toolbox™ license, and you set an `optimset` option for a solver that is only available in Optimization Toolbox, `optimset` errors. Previously, `optimset` would warn, not error, and ignore the option.

Compatibility Considerations

Change your code to set only those options that apply to your solver: `fminbnd`, `fminsearch`, `fzero`, or `lsqnonneg`.

atan Warning Being Removed

Compatibility Considerations: Yes

When you use `atan(1i)` and `atan(-1i)` you no longer get a warning.

Compatibility Considerations

Remove instances of the warning ID `MATLAB:atan:singularity` from your code.

Data Analysis

Arrays of Time Series Objects Supported

Compatibility Considerations: Yes

MATLAB now enables you to create arrays of `timeseries` objects. In Version 7.10 (R2010a) and before, `timeseries` objects behaved as arrays, but some array behavior was overridden.

Compatibility Considerations

Note It is likely that this change is important to you *only* if you write code that uses `timeseries` objects.

In Version 7.11 (R2010b), all of the overridden behaviors for the functions listed in the table that follows are removed. The behavior of these functions on `timeseries` objects is the built-in behavior for arrays of objects. Think of a `timeseries` object as a single object that you can concatenate into an array of objects. Do not think of each `timeseries` itself as an array.

Functions Being Modified

Function or Function Element Name	What Happens When You Use the Function or Element?	Use This Instead	Compatibility Considerations
<code>horzcat</code>	No error or warning	Not applicable	You can now use <code>horzcat</code> with <code>timeseries</code> objects.
<code>isempty</code> (<code>timeseries</code>)	No error or warning	<code>timeseries.Length==0</code>	Replace code such as: <code>isempty(ts)</code> with: <code>ts.Length == 0</code>
<code>length</code> (<code>timeseries</code>)	No error or warning	<code>timeseries.Length</code> property	Replace code such as: <code>length(ts)</code> with: <code>ts.Length</code>

Function or Function Element Name	What Happens When You Use the Function or Element?	Use This Instead	Compatibility Considerations
size (timeseries)	No error or warning	[timeseries.Length 1]	Replace code such as: size(ts) with: [ts.Length 1]
subsref	No error or warning	getsamples	Replace code such as: t3 = t1(1:3); with: getsamples(t1,1:3);
vertcat (timeseries)	May return Index exceeds matrix dimension error	append	Replace code such as: t3 = [t1;t2]; with t3 = append(t1,t2);

Example of timeseries Object Concatenation

Suppose you concatenate the following two `timeseries` objects:

```
t1 = timeseries(ones(5,1),0:4);
t2 = timeseries(zeros(5,1),5:9);
```

In R2010a, the following syntax created a single `timeseries` object, `t3`, with 10 samples spanning the time range 0-9. The first 5 samples derived from `t1` and the last 5 samples derived from `t2`. The size of the `timeseries`, `t3`, was [10 1] and its length was 10, because `t3` has 10 samples.

```
t3 = [t1;t2]
t3 = vertcat(t1,t2)
```

Now, the same syntax creates a 2x1 array comprising the two `timeseries` objects `t1` and `t2`. Its size is [2 1], and its length is 2 because the array has two rows, each a single `timeseries`.

Programming

arrayfun Accepts Array of Objects

The `arrayfun` function now accepts an array of objects as an input. The output can also be a scalar object, as long as the `UniformOutput` flag is set to `false`.

Comparing Object Arrays that Contain NaNs

Compatibility Considerations: Yes

In previous versions of MATLAB, calling `isequalwithequalnans` to compare identical arrays of objects that contain one or more NaN (Not a Number) values incorrectly returned `false`. Similarly, calling `isequal` to compare identical arrays of objects that contain NaNs incorrectly returned `true`.

In MATLAB version 7.11, these functions return the expected values (`true` for `isequalwithequalnans`, and `false` for `isequal`) when used to compare object arrays.

Compatibility Considerations

Program code that compares object arrays that may contain NaNs should be examined to ensure correct behavior.

Functions `isa` and `islogical` Now Consistent for Objects

Compatibility Considerations: Yes

In earlier releases of MATLAB, the following statements returned different results for objects with a base class of `logical`:

```
isa(obj, 'logical')  
islogical(obj)
```

In MATLAB version 7.11, both of these statements return `true` if the class of `obj` is derived from `logical`, and `false` otherwise.

Compatibility Considerations

If you have program code that calls either `isa` or `islogical` on objects with a base class of `logical`, it is advisable to verify that this new behavior does not adversely affect the execution of the program.

New Enumeration Classes

MATLAB provides support for classes that define enumerations. Enumeration classes enable you to define a fixed set of names representing a particular type of value. See [Enumerations](#) for more information.

Use this link to watch a video that introduces enumerations: [Play demo](#)

New Functionality for Writing Video Files

The new `VideoWriter` function allows you to create AVI files on all platforms. As an improvement over the `avifile` function, `VideoWriter` can create files larger than 2 GB. For more information, watch this video demo or see the `VideoWriter` reference page.

mmreader Renamed VideoReader

Compatibility Considerations: Yes

For consistency with the new VideoWriter class, the mmreader class is now called VideoReader. A new function, VideoReader, replaces the mmreader function. VideoReader and mmreader return identical VideoReader objects for the same input file.

Compatibility Considerations

Replace all instances of mmreader with VideoReader. The two functions use identical syntax. When requesting help or documentation for methods from the command line, or calling a static method such as getFileFormats, use the new VideoReader class name (such as doc VideoReader/read). You do not need to change any calls to the read, get, or set methods.

Previously, the R2010a Release Notes recommended replacing instances of aviinfo with mmreader and get, and instances of aviread with mmreader and read. Instead, replace aviinfo with VideoReader and get, and replace aviread with VideoReader and read.

New HDF4 Functions

The MATLAB interface to the grid functions in the HDF-EOS C library, `hdfgd`, now includes three new syntaxes. These syntaxes convert grid coordinates to longitude and latitude values.

- `ij2ll`
- `ll2ij`
- `rs2ll`

To view the help for these functions, use the `help` command at the MATLAB prompt, as in the following example:

```
help hdfgd
```

New HDF5 Low-Level Functions

The MATLAB interfaces to the HDF5 C library now include the following new functions.

- `H5A.open_by_idx`
- `H5A.open_by_name`
- `H5D.get_access_plist`
- `H5I.is_valid`
- `H5L.copy`
- `H5L.get_name_by_idx`
- `H5P.set_chunk_cache`
- `H5P.get_chunk_cache`
- `H5P.set_copy_object`
- `H5P.get_copy_object`

To view the help for these functions, use the `help` command at the MATLAB prompt, as in the following example:

```
help H5P.get_copy_object
```

New netCDF Functions

The MATLAB interface to the netCDF C library now includes the following new functions.

- `netcdf.inqFormat`
- `netcdf.inqUnlimDims`
- `netcdf.defGrp`
- `netcdf.inqNcid`
- `netcdf.inqGrps`
- `netcdf.inqVarIDs`
- `netcdf.inqDimIDs`
- `netcdf.inqGrpName`
- `netcdf.inqGrpNameFull`
- `netcdf.inqGrpParent`
- `netcdf.defVarChunking`
- `netcdf.defVarDeflate`
- `netcdf.defVarFill`
- `netcdf.defVarFletcher32`
- `netcdf.inqVarChunking`
- `netcdf.inqVarDeflate`
- `netcdf.inqVarFill`
- `netcdf.inqVarFletcher32`

To view the help for these functions, use the `help` command at the MATLAB prompt, as in the following example:

```
help netcdf.inqVarFletcher32
```

Upgrades to Scientific File Format Libraries

The following table lists upgrades to scientific file format libraries used by MATLAB.

Library	Version Upgrade
netCDF	3.6.2 to 4.0.1

New Examples in Command Line Help

The MATLAB command line help for the HDF5, netCDF, and CDF low-level functions now includes hundreds of new examples.

imread and imwrite Can Now Handle N-channel J2C JPEG 2000 Files

You can now use the `imread` and `imwrite` functions with n-channel J2C JPEG 2000 files.

J2C files are raw JPEG2000 codestreams that usually have the file extension `.j2c` or `.j2k`. J2C files don't contain color space, color palette, capture resolution, display resolution and vendor specific information.

In previous releases, if you use `imread` to read a 4-channel J2C file, you receive a warning that some channels may be ignored and `imread` returns a 3-channel image. Now, `imread` returns a 4-channel image and does not issue a warning.

If you try to write a 4-channel J2C file in previous releases, `imwrite` issues an error. In this release, `imwrite` creates the 4-channel J2C file.

csvread and csvwrite Will Not Be Removed

The R2010a Release Notes originally stated that `csvread` and `csvwrite` would be removed in a future release. As of R2010b, there are no plans to remove these functions.

sprintf and fprintf Print Null Characters in Strings

Compatibility Considerations: Yes

In previous releases, calls to `sprintf` or `fprintf` that printed strings using the `%s` qualifier prematurely terminated strings that contained null characters. For example, this code

```
sprintf('%s', ['foo' 0 'bar'])
```

returned

```
ans =  
foo
```

The same code now returns

```
ans =  
foo bar
```

Compatibility Considerations

If you do not want to print the entire contents of strings that contain null characters, test the string for these characters (for example, using the `isstrprop` function).

Functions and Function Elements Being Removed

Compatibility Considerations: Yes

Function or Function Element Name	What Happens When You Use the Function or Element?	Use This Instead	Compatibility Considerations
fileparts return argument 4 (file version)	Warns, returns empty fourth argument	No alternative; file versions are unsupported	Call fileparts with three return arguments: [path_name file_name file_extension]
mmreader	Still runs, creates a VideoReader object	VideoReader	Replace all existing instances of mmreader with VideoReader.
wavplay	Still runs	audioplayer and play	Replace all existing instances of wavplay with audioplayer and play.
wavrecord	Still runs	audiorecorder and record	Replace all existing instances of wavrecord with audiorecorder and record.
wk1finfo	Warns		Remove all instances of wk1finfo. Get information about Excel spreadsheets with xlsfinfo.

Function or Function Element Name	What Happens When You Use the Function or Element?	Use This Instead	Compatibility Considerations
wk1read	Warns		Remove all instances of wk1read. Read Excel spreadsheets with xlsread.
wk1write	Warns		Remove all instances of wk1write. Write to Excel spreadsheets with xlswrite.

MATLAB Did Not Pass struct to loadobj When Property Was Deleted

Compatibility Considerations: Yes

If you save an object having a property value equal to the property's default value, and then that property is removed from the class definition, MATLAB did not detect the fact that the property was missing. In this case, MATLAB did not build a struct to pass to `loadobj`. MATLAB now returns a struct in this case.

Compatibility Considerations

If you rely on the following situation *not* returning a struct to `loadobj`, you need to update your code:

- You saved an object using the `save` command
- This object had a property that was set to the default value defined by the class at the time of saving
- The property set to its default value at save time is subsequently removed from the class definition
- You load the property and expect the load operation to return an object (it should return a struct because the class definition has changed in a way the load cannot create the object).
- Your `loadobj` method is not prepared to use the returned struct to create an object

You must implement a `loadobj` method to recreate the object using the current class definition.

See [Saving and Loading Objects](#) for more information.

Graphics and 3-D Visualization

Print `-dmfile` and `printdmfile` Issue Deprecation Warnings

Compatibility Considerations: Yes

The `dmfile` print command option and the `printdmfile` function now issue a deprecation warning. Both option and function will be removed in a subsequent release. The `dmfile` option and the `printdmfile` function were used by GUIDE.

Compatibility Considerations

Remove any use of `print dmfile` or `printdmfile` from your code.

The saveas 'mmat' option Issues a Deprecation Warning

Compatibility Considerations: Yes

The saveas function now issues a deprecation warning if you use the 'mmat' format option. This option will be removed in a subsequent release. This option was used with GUIDE.

Compatibility Considerations

Remove any use of the mmat option with saveas from your code.

The movie Function is No Longer a Built-in Function

Compatibility Considerations: Yes

The `movie` function is no longer a built-in function. Therefore, you cannot call `movie` from the `builtin` function. `movie` syntax remains the same.

Compatibility Considerations

Remove any use of the `builtin` function to call the `movie` function from your code.

Creating Graphical User Interfaces (GUIs)

Functions and Function Elements Being Removed

Compatibility Considerations: Yes

The `uitabgroup` and `uitab` GUI components are undocumented features that provide tabbed panels to GUIs that you create programmatically. The current method of calling these functions and some of their properties will change in a future release. MathWorks has never supported their use. However, if your MATLAB code includes these functions, read the following information:

Function or Function Element Name	What Happens When You Use the Function or Element?	Use This Instead	Compatibility Considerations
<code>uitabgroup('v0',...)</code> <code>uitab('v0',...)</code>	Warns	<code>uitabgroup(...)</code> <code>uitab(...)</code>	Using the 'v0' argument generates a warning, but the object is created.
<code>uitabgroup</code> property <code>SelectionChangeFcn</code>	Not recommended	<code>SelectionChangeCallback</code>	Event data for the callback is still a struct with fields <code>OldValue</code> and <code>NewValue</code> but those values are now <code>uitab</code> handles, not <code>uitab</code> indexes.
<code>uitabgroup</code> property <code>SelectedIndex</code>	Not recommended	<code>SelectedTab</code>	Both properties still exist, but replace instances of <code>SelectedIndex</code> (an integer tab index) with <code>SelectedTab</code> (a handle to a <code>uitab</code> object).
<code>uitabgroup</code> property <code>BackgroundColor</code>	Not recommended	no replacement	<code>uitabgroup</code> now uses the default <code>uicontrol</code> background color.
<code>uitabgroup</code> event <code>SelectionChanged</code>	Errors	<code>SelectionChange</code> event	Event name changed to be consistent with other components. Event data is still a struct with fields <code>OldValue</code> and <code>NewValue</code> but those values are now <code>uitab</code> handles, not <code>uitab</code> indexes.

You should update any code that you maintain which uses the undocumented `uitabgroup` and `uitab` functions to conform to the new standards, as described in the `uitab` and `uitabgroup` Migration Document. Existing code for these functions is unlikely to work in R2010b going forward.

External Interfaces/API

Changes to Compiler Support

Compatibility Considerations: Yes

New Compiler Support

MATLAB Version 7.11 (R2010b) supports these new compilers for building MEX-files:

Microsoft Windows (64- and 32-Bit) Platforms

- Microsoft Visual Studio 2010 (10.0) Professional
- Microsoft Visual Studio 2010 (10.0) Express

Linux (64- and 32-Bit) Platforms

- GNU gcc Version 4.3.x

Compiler Support to Be Phased Out

Support for the following compilers will be discontinued in a future release, at which time new versions will be supported. For an up-to-date list of supported compilers, see the Supported and Compatible Compilers Web page.

Windows (64- and 32-Bit) Platforms

- Intel Visual Fortran Version 10.1
- Microsoft Visual Studio 2005 SP1

Discontinued Compiler Support

MATLAB no longer supports the following compilers:

Windows (64- and 32-Bit) Platforms

- Intel C++ Version 9.1

Linux (64- and 32-Bit) Platforms

- GNU gcc Version 4.2.3

Apple Macintosh (32-Bit) Platforms

- Apple Xcode 3.1 (gcc / g++ Version 4.0.1)
- GNU gfortran Version 4.2.2

Compatibility Considerations

To ensure continued support for building your MEX-files, consider upgrading to another supported compiler. For an up-to-date list of supported compilers, see the [Supported and Compatible Compilers Web page](#).

-largeArrayDims Option to MEX Will Become Default in Next Release of MATLAB

Compatibility Considerations: Yes

In the next release of MATLAB, the `mex` command will change to use the large-array-handling API by default. This means the `-largeArrayDims` option will become the default.

You do not need to make changes to build and run MEX-files with MATLAB Version 7.11 (R2010b).

Compatibility Considerations

Source for MEX-files built on 64-bit platforms must be updated in order to successfully build and run with the next release of MATLAB. Review your source MEX-files and `mex` build scripts. For information about migrating your MEX-files to use the large-array-handling API, see [Upgrading MEX-Files to Use 64-Bit API](#).

MEX Function -argcheck Option Removed

Compatibility Considerations: Yes

Function Option Name	What Happens When you use the Option?	Compatibility Considerations
mex -argcheck option	Errors	Remove all existing instances of -argcheck in build scripts.

The -argcheck option was a strategy for identifying memory corruption caused by a MEX-file. When you understand the likely causes of memory corruption, you can take preventative measures in your code or use your debugger to identify the source of errors.

If a binary MEX-file causes a segmentation violation or assertion, it means the MEX-file attempted to access protected, read-only, or unallocated memory.

These types of programming errors are sometimes difficult to track down. Segmentation violations do not always occur at the same point as the logical errors that cause them. If a program writes data to an unintended section of memory, an error might not occur until the program reads and interprets the corrupted data. Consequently, a segmentation violation can occur after the MEX-file finishes executing.

One cause of memory corruption is to pass a null pointer to a function. To check for this condition, add code in your MEX-file to check for invalid arguments to MEX Library and MX Matrix Library API functions.

To troubleshoot problems of this nature, run MATLAB within a debugging environment. For more information, see [Debugging C/C++ Language MEX-Files](#) or [Debugging Fortran Source MEX-Files](#).

MEX Function -inline Option Removed

Compatibility Considerations: Yes

Function Option Name	What Happens When you use the Option?	Compatibility Considerations
mex -inline option	Errors	Remove all existing instances of -inline in build scripts.

New Support for Features in Microsoft .NET Framework

MATLAB supports:

- Using .NET Delegates in MATLAB.
- Accessing Microsoft Office Applications with .NET.
- Using `System.Nullable`, described in [How MATLAB Handles System.Nullable](#).
- Calling constructors or `NET.invokeGenericMethod` with ref or out type arguments.
- Calling methods with default arguments
(`System.Reflection.Missing.Value` is supported.)

New COM Data Type Support

Support for the following COM data type has been added. See [Handling COM Data in MATLAB Software](#) for a description of supported data types.

- VT_I8 — signed int64
- VT_UI8 — unsigned int64
- Unsigned integer

R2010a

Version: 7.10
New Features: Yes
Bug Fixes: Yes

Desktop Tools and Development Environment

Desktop New Features Video for R2010a

For an overview of the major new features in the MATLAB Desktop Tools and Development Environment area, watch this video demo.

Startup and Shutdown

AUTOMOUNT_MAP Environment Variable No Longer Used by MATLAB

On UNIX systems, MATLAB no longer uses the `AUTOMOUNT_MAP` environment variable, the path prefix map for automounting. Previously, MATLAB set the value of the variable in `.matlab7.rc`, but you could override this setting using the `AUTOMOUNT_MAP` environment variable.

Desktop

Compatibility Considerations: Yes

New Desktop features and changes introduced in Version 7.10 (R2010a) are:

- “Enhancements for Managing Keyboard Shortcuts” on page 323
- “Method for Accessing M-Lint Preferences and the M-Lint Report” on page 323
- “Preference for Java Heap Memory” on page 324

Enhancements for Managing Keyboard Shortcuts

Keyboard shortcuts now provide the following:

- “Ability to List a Set of Keyboard Shortcuts in a Text Editor” on page 323
- “Ability to Remove Keyboard Shortcuts Sets” on page 323
- “Ability to Compare Sets of Keyboard Shortcuts” on page 323

Ability to List a Set of Keyboard Shortcuts in a Text Editor

You can now list all of the keyboard shortcuts for a given set in a text editor. For details, see [List All Keyboard Shortcuts in a Set](#).

Ability to Remove Keyboard Shortcuts Sets


You can now remove keyboard shortcut sets that you created or imported. For details, see [Delete a Set of Keyboard Shortcuts](#).

Ability to Compare Sets of Keyboard Shortcuts

You can now compare one set of keyboard shortcuts to another. This enables you, for example, to see what is different between the current Windows default keyboard shortcuts and those that were the defaults in MATLAB Version 7.8 (R2009a) and earlier. For details, see [Compare Sets of Keyboard Shortcuts](#).

Method for Accessing M-Lint Preferences and the M-Lint Report

The **M-Lint Preferences** is now renamed the **Code Analyzer Preference**. Therefore, to set preferences for analyzing MATLAB code, select

File > Preferences > Code Analyzer. Similarly, the M-Lint Report is now renamed the Code Analyzer Report. To access this report, click the Actions button  in the Current Folder browser, and then select **Reports > Code Analyzer Report**. The names of the `mlint` and `mlintrpt` functions are unchanged.

Preference for Java Heap Memory

A new preference setting allows you to adjust the amount of memory that MATLAB allocates for storing Java objects. Insufficient memory for these objects results in `OutOfMemory` errors. For more information, see [Java Heap Memory Preferences](#).

Compatibility Considerations

Technical Solution 1-18I2C specifies a procedure for creating a text file named `java.opts` to set the Java heap size. Do not use both the new MATLAB preference and a `java.opts` file to adjust the heap size.

Help Browser

Compatibility Considerations: Yes

- “Improved Instructions and Examples for Adding Help and Demos to the Help Browser” on page 325
- “New Search Hints” on page 326
- “Search History Persists Between Sessions” on page 326
- “Hide Search Results Previews” on page 327
- “docopt Function Removed” on page 327

For a demonstration of previous enhancements to the Help browser, watch the Help Browser Enhancements video.

Improved Instructions and Examples for Adding Help and Demos to the Help Browser

The MATLAB documentation now includes more details about how to display your own HTML help and demos. In particular, the documentation clarifies procedures for setting up files and folders and provides three new XML file templates that you can inspect, copy, and modify.

The documentation also adds a new complete working example, called the Upslope Area Toolbox. Documentation for the toolbox includes a getting started guide, user guide, function reference pages, and release notes. The documentation set is generated entirely from MATLAB script files (also provided), using the `publish` command. The example folder includes all program files for the toolbox. However, certain routines require Image Processing Toolbox for full functionality.

You can also find the Upslope Area Toolbox on the MATLAB Central File Exchange. For more information about techniques and algorithms the toolbox uses, see the set of articles about it on this MATLAB Central blog: <http://blogs.mathworks.com/steve/category/upslope-area>.

Find the updated documentation in Create Help and Demos. For details, XML templates, and examples, see these subsections:


- Add Documentation to the Help Browser

- Add Demos to the Help Browser

You can view the Upslope Toolbox documentation example in the Help browser now by clicking here, which places its folder on the search path.


New Search Hints

The Help Browser now provides suggestions for search terms as you type in the search field. These hints save you time and can suggest words and phrases you might not have thought of but that can be useful in making a search. The hints display as a drop-down menu that changes its contents as you type. The following illustration shows the appearance of the menu.



Search History Persists Between Sessions

The Help browser can now recall searches you have made across MATLAB sessions. Your search history and search hints display as separate lists in a drop-down pane as you type in the search field. Select **Show Search History** from the pop-up menu to the right of the search field, or press the down arrow key in the search field when it is empty. The following illustration shows search history and search hints as they appear when you enter search terms.



Hide Search Results Previews

You can now choose not to see the one-line descriptions of search results called *previews*. To toggle all previews off, right-click in the Search Results pane of the Help Navigator and choose **Hide Previews**. The search results listing is smaller so you can scan it quickly when you hide previews. To see previews again, right-click in the Search Results pane, and choose **Show Previews**.

doopt Function Removed

This release obsoletes the `doopt` function, which specified which system Web browser to use on UNIX platforms. This function has been removed. You can instead specify a default system browser in your preferences. For more information, see “New System Browser Preference Instead of `doopt.m` for MATLAB on UNIX Platforms” on page 445.

Compatibility Considerations

If you call `doopt` in your startup file or some other program file, remove the call to avoid receiving an error.

Managing Files


- “Create and Expand Zipped Archives from Current Folder Browser” on page 328
- “Visual Aids for Identifying Files Inaccessible to MATLAB” on page 328
- “Ability to Remove Folders and Subfolders from the Path Using the Current Folder Browser” on page 329
- “Enhancements for File and Folder Comparisons” on page 330

Create and Expand Zipped Archives from Current Folder Browser

Effective this release, the capability to create and expand, and archive .zip files has been added to the Current Folder browser. Select files and folders in the Current Folder browser, then right click, and choose **Create Zip File** to create an archive. The archive appears in the current folder. You can expand an archive in the same way. For details, see *Creating and Managing Zip File Archives*.

Visual Aids for Identifying Files Inaccessible to MATLAB

This release changes the default behavior of the Current Folder browser. The Current Folder browser now dims files that are inaccessible to MATLAB to indicate their unavailability. A tooltip provides an explanation.



You can also customize or disable this feature. For more information, see Preferences for the Current Folder Browser and Viewing Files and Folders on the Search Path.

Ability to Remove Folders and Subfolders from the Path Using the Current Folder Browser

You can now remove folders from the MATLAB path as follows:


- 1 In the Current Folder browser, right-click the folder you want to remove from the path.
- 2 From the context menu, select **Remove from Path**, and then select **Selected Folders** or **Selected Folder and Subfolders**.

If the default preferences for the Current Folder **Path indication** option are set, the folders you removed now appear dimmed in the Current Folder browser. For more information, see Preferences for the Current Folder Browser and Removing Folders from the Search Path.

Enhancements for File and Folder Comparisons

This release enhances the File and Folder Comparisons tool to improve the usability of comparisons between text files and folders.

File comparisons now highlight changes within lines and provide new toolbar buttons for stepping through differences, as the following figure shows.



Folder comparisons now provides results that are sortable by name, type, size, timestamp, or change summary. Click column headers to sort the table. Click **compare** links to explore differences between files and folders. The following example shows results sorted by **Type**.

Comparing folder curvefitting vs. folder curvefitting2

Left file list	Contents of folder C:\Work\comp\curvefitting
Right file list	Contents of folder C:\Work\comp\curvefitting2

Click on a column header to sort the table

		In left list (folder curvefitting)		In right list (folder curvefitting2)		
Type ▾	File Name	Size (bytes)	Last Modified Date	Size (bytes)	Last Modified Date	Change Summary
ASV file	lengthofline.asv (open)	(not in this list)		2403	2009-11-16 15:24:45	added
HTML file	manifest_report.html (open)	2410	2008-11-27 14:24:50	(not in this list)		removed
MAT file	splinetool.mat (open)	1720	2001-08-20 18:14:12	(not in this list)		removed
M file	csapidem.m (open)	(not in this list)		15038	2009-01-08 13:56:28	added
M file	lengthofline.m (open ; left ; right)	2405	2009-11-12 16:56:52	2408	2009-11-16 15:25:14	contents changed (compare)
TXT file	kdm.txt (open)	(not in this list)		1367	2008-10-03 11:13:37	added
XML file	report.xml (open)	(not in this list)		4868	2008-09-11 17:53:32	added
folder	curvefit	-	2009-11-16 15:18:38	-	2009-11-16 15:20:08	contents changed (compare)
folder	cftoolgui	-	2009-11-16 15:18:38	-	2009-11-16 15:20:04	contents changed (compare)
folder	demosearch	-	2009-11-16 15:19:13	-	2009-11-16 15:19:44	identical

When you compare subfolders with many files, now the tool continues analysis in the background, reporting progress. You can now skip items or cancel as you review this analysis.

For more information, see [Comparing Files and Folders](#).

Editing and Debugging MATLAB Code



New features and changes introduced in Version 7.10 (R2010a) are:

- “Tab Completion for Local Variables and Functions” on page 332
- “Toolbar Buttons for Stepping Through Code Cells Without Evaluating Code” on page 332

Tab Completion for Local Variables and Functions

The MATLAB Editor now supports tab completion for local variable and subfunction names within MATLAB program files. For more information, see [Complete Names in the Editor Using the Tab Key](#).

Toolbar Buttons for Stepping Through Code Cells Without Evaluating Code

This release provides two New Cell Mode toolbar buttons, Next Cell  and Previous Cell . You can use these buttons to step through cells in the Editor without evaluating the code within the cells. By default, these buttons do not appear on the Cell Mode toolbar.

For more information, see [Navigate Among Code Cells in a File](#).

Mathematics

New Multithreading Capability

MATLAB's new multithreading capability now includes:

- `fft` for long vectors
- The two-input form of `conv2`
- Integer conversion and arithmetic

Performance Improvements

MATLAB features significant performance improvements for:

- Sparse matrix indexed assignment and deletion
- `bvp4c` and `bvp5c` for sparse problems
- `sortrows`
- `mrdivide (/)`
- `convn`
- `histc`

Changes To qr

Compatibility Considerations: Yes

The factorization routine in `qr` produces an upper triangular matrix, `R`. Now this matrix always contains real and nonnegative diagonal elements. In previous releases, the diagonal of `R` could contain complex and negative elements.

Compatibility Considerations

`R` now contains only real, nonnegative diagonal elements. The QR factorization is not unique, so the answer is still correct.

Change in Indexing for Sparse Matrix Input

Compatibility Considerations: Yes

Now subscripted reference into a sparse matrix always returns a sparse matrix. In previous versions of MATLAB, using a double scalar to index into a sparse matrix resulted in full scalar output.

Compatibility Considerations

Scalars extricated from sparse matrices are no longer full. If you previously used the output with a function that does not support sparse input, you now need to update your code. For a list of the functions that do not support sparse matrices, see [Functions That Do Not Support Sparse Matrices](#) in the MATLAB Mathematics documentation.

Improved Error Checking for Sparse Functions

Functions that erroneously accepted N-D arrays and returned reshaped sparse 2-D outputs no longer accept full N-D inputs and now return an error. The functions affected are:

- `spones`, `spfun`, `sprand`, `sprandn`, and `sprandsym`
- `cat`, `horzcat`, and `vertcat`

Also, binary functions that formerly accepted both full N-D inputs along with sparse 2-D inputs and warned about the reshape, now return an error. For example, `ones(2,2,2).*sparse(3)` formerly returned a sparse 2-by-4 matrix along with a warning about the reshape. This code now returns an error.

Computational Geometry Functions Being Changed

Compatibility Considerations: Yes

The computational geometry functions `delaunay`, `convhull`, `griddata`, `voronoi`, `delaunay3`, `griddata3` no longer use the `options` arguments.

Compatibility Considerations

Use of the `options` arguments to `delaunay`, `convhull`, `griddata`, and `voronoi` now throws a warning.

Computational Geometry Functions Being Removed

Compatibility Considerations: Yes

The functions `griddata3`, `delaunay3`, `dsearch`, `tsearch` will be removed in a future release. Use of these functions now throws a warning.

Function Name	Use This Method Instead
<code>griddata3</code>	<code>TriScatteredInterp</code>
<code>dsearch</code>	<code>DelaunayTri/nearestNeighbor</code>
<code>tsearch</code>	<code>DelaunayTri/pointLocation</code>
<code>delaunay3</code>	<code>DelaunayTri</code>

Compatibility Considerations

Update your code to use the `DelaunayTri` and `TriScatteredInterp` computational geometry classes .

lsqnonneg No Longer Uses Optional Starting Point Input

Compatibility Considerations: Yes

The `lsqnonneg` solver no longer uses the optional input `x0` as a starting point.

Compatibility Considerations

If you give a starting point `x0`, MATLAB issues a warning. Also, `lsqnonneg` ignores `x0`, and instead uses a starting point of a vector of zeros.

Function erfc0re Removed

Compatibility Considerations: Yes

Support for the `erfc0re` function has been removed. Use of `erfc0re` now results in the following error message:

ERFCORE will be removed in a future release.
Use `ERF`, `ERFC`, `ERFCX`, `ERFINV`, or `ERFCINV` instead.

Compatibility Considerations

Replace `erfc0re` with `erf`, `erfc`, `erfcx`, `erfinv`, or `erfcinv`. See the function reference pages for the individual error functions.

Integer Warning Messages Removed

Compatibility Considerations: Yes

These warning messages for integer math and conversion have been removed:

- `MATLAB:intConvertNaN`
- `MATLAB:intConvertNonIntVal`
- `MATLAB:intConvertOverflow`
- `MATLAB:intMathOverflow`

Compatibility Considerations

The warning messages for integer math and conversion are no longer available. Remove these warning IDs from your code.

Function intwarning Being Removed

Compatibility Considerations: Yes

The intwarning function will be removed in a future release. Use of intwarning now throws a warning:

Warning: All four integer warnings are removed.
INTWARNING will be removed in a future release.

Compatibility Considerations

The warnings previously thrown when you used intwarning on are now removed. Remove all instances of intwarning from your code.

atan Warning Being Removed

Compatibility Considerations: Yes

The warning thrown when you use `atan(i)` and `atan(-i)` will be removed. Currently, the warning message is:

```
Warning: Singularity in ATAN. This warning will be
removed in a future release.Consider using DBSTOP
IF NANINF when debugging.
```

Compatibility Considerations

Remove instances of the warning ID `MATLAB:atan:singularity` from your code.

nextpow2 Returns Output the Same Size As Input

Compatibility Considerations: Yes

In previous releases, `nextpow2` with a vector input `v` returned `nextpow2(length(v))`. Now `nextpow2(v)` returns a vector the same size as the input.

Compatibility Considerations

If you require the old behavior, replace instances of `nextpow2` with `nextpow2(length(v))`.

Math Libraries Not Available to Build MEX-Files with Compaq Visual Fortran

Compatibility Considerations: Yes

MATLAB no longer provides the `libdflapack.dll` and `libdfblas.dll` math libraries for building Fortran MEX-files with a Compaq® Visual Fortran compiler.

Compatibility Considerations

If you distribute MEX-files that call BLAS or LAPACK functions built on a Compaq Visual Fortran compiler, you must also distribute the `libdflapack.dll` and `libdfblas.dll` library files.

If MATLAB displays errors when loading a MEX-file and the Dependency Walker indicates missing `libdflapack.dll` and/or `libdfblas.dll` libraries, contact the MEX-file vendor for copies of the libraries. The third-party product, Dependency Walker, is available from the Web site <http://www.dependencywalker.com/>.

Data Analysis

Operations on Timeseries Objects Sometimes Warn About the isTimeFirst Property

Compatibility Considerations: Yes

In a future release, the `timeseries` Boolean property `isTimeFirst` will behave differently. If the value is `true`, this property indicates that the time vector is the *first* dimension of a time series. If the value is `false`, the time vector is the *last* dimension of a time series. In this release, you receive a warning that certain settings of `isTimeFirst` will not be valid in a future release. The warning indicates that for 3-D or N-D data, time must be the *last* dimension, while 2-D time series data can have time as the first dimension.

Compatibility Considerations

You can receive a warning when:

- Constructing a time series object with three or more dimensions without specifying a time vector. In a future release, MATLAB will calculate a value of the `isTimeFirst` property that can differ from the value it currently calculates.
- Changing the data of a time series to data of a different dimensionality. In a future release MATLAB will calculate a value of the `isTimeFirst` property that differs from the value it currently calculates.
- Directly setting the `isTimeFirst` property for a time series to a value that will be invalid in a future release.

The warning does not affect how you can use time series data in this release. It is intended to inform you that the behavior of `isTimeFirst` will change in a future release. If you receive a warning about `isTimeFirst`, you can use the `timeseries` method `migrateistimefirst` to correct the problem. For information type

```
help timeseries/migrateistimefirst
```

in the Command Window.

Time Series Time Vectors Can Now Contain Duplicate Sample Times

Starting with this release, a vector containing sample times can have duplicate times in contiguous positions. Previously, time vectors needed to increase monotonically and duplicated time values generated errors. This condition is now relaxed, such that time vectors must be *nondecreasing*. Interpolation of time series can produce duplicated times if the input to the interpolation method contained duplicate time samples. For more information, see the `timeseries` reference documentation.

Programming

Subscribing Into Function Return Values

Compatibility Considerations: Yes

If you have a function, such as the following, that returns a struct array:

```
function structOut = getStruct
structOut = struct('fieldA', 5, 'fieldB', 10);
```

it is no longer valid to access fields of the structure by directly dot indexing the function's return value, as shown here:

```
getStruct.fieldA
```

Instead, you should first assign the returned structure to a variable, and then dot index the variable:

```
s = getStruct;
s.fieldA
ans =
     5
```

This type of field access has never been allowed within function code, and this change causes scripts and command line statements to be in agreement with function rules.

Compatibility Considerations

If you have scripts that employ this type of dot indexing, they will now throw an error. Replace this unsupported style of dot indexing with the style shown above.

New Constructor for Map Containers

The following command constructs an empty `containers.Map` object that uses a key type of `kType`, and a value type of `vType`:

```
M = containers.Map('KeyType', kType, 'ValueType', vType)
```

See the `containers.Map` function reference page for more information.

Function Handle Access to Private and Protected Methods

When creating a function handle inside a method of a class, the function is resolved using the permissions of that method. When MATLAB invokes the function handle, it does so using the permissions of the class. This gives MATLAB the same access as the locations where the function handle was created, including access to private and protected methods accessible to that class.

See [Obtaining Permissions from Class Methods](#) for more information.

Listing Video File Formats Supported by mmreader

The new `mmreader.getFileFormats` method returns a list of the formats that `mmreader` supports. The list of formats is static for Windows and UNIX systems, but dynamic on Macintosh systems. For more information, see the `getFileFormats` reference page.

unzip Preserves Write Attribute of Files

In previous releases, for files archived using WinZip® software, the unzip function set the file write attribute of extracted files to read only. Starting with R2010a, unzip preserves the original attribute.

New Package Provides Access to low-level CDF API Routines

MATLAB has included high-level routines for accessing Common Data Format (CDF) files: `cdfread`, `cdfwrite`, and `cdfinfo`. However, the CDF API is so large, these functions cannot satisfy every need. To solve this, MATLAB now includes a new package, called `CDFlib`, that provides access to dozens of the functions in the CDF API. Using these low-level functions, you can create CDF files and populate them with variables and attributes using the CDF library, version 3.3.0.

Upgrades to Scientific File Format Libraries

The following table lists upgrades to several scientific file format libraries used by MATLAB.

Library	Version Upgrade
CDF	3.2.1 to 3.3.0
HDF5	1.8.1 to 1.8.3
HDF4	4.2.r1 to 4.2.r4
HDF-EOS2	2.8 to 2.16
PNG	1.2.8 to 1.2.39

Tiff Class Enhancements

Compatibility Considerations: Yes

The Tiff class includes the following enhancements.

Tiff Class Now Excludes Reading OJPEG Format Image Data

You can no longer read YCbCr OJPEG ("old-style" JPEG compression) TIFF images. The Tiff object was not intended to work with OJPEG data but some TIFF files contain data in this format. Reading this data could cause LibTIFF to terminate.

Compatibility Considerations

To read OJPEG image data, use the `imread` function. Note that the `imread` function transforms the image data into the RGB colorspace.

Additional Reading and Writing Capabilities

The Tiff class includes the following additional capabilities:

- Writing image data that use 16-bit colormaps (palettes)
- Reading and writing LogL and LogLUV High Dynamic Range (HDR) images. To write a LogL or LogLUV image, you must use the new `SGILogDataFmt` property.

MATLAB Adds Support for Creating JPEG 2000 Files

You can now use the `imwrite` function to create a JPEG 2000 file and write data to the file. The `imwrite` function supports format-specific parameters that let you specify the mode, compression ratio, and other characteristics.

Sealed No Longer Listed as meta.property Class Property

While class properties do not have a Sealed attribute, the meta.property class listed Sealed as a property. Sealed is no longer listed as a meta.property class property.

Functions and Function Elements Being Removed

Compatibility Considerations: Yes

Function or Function Element Name	What Happens When You Use the Function or Element?	Use This Instead	Compatibility Considerations
aviread	Warns	mmreader and read	Replace all existing instances of aviread with mmreader and read.
aviinfo	Warns	mmreader and get	Replace all existing instances of aviinfo with mmreader and get.
exifread	Warns	imfinfo	Replace all existing instances of exifread with imfinfo
fileparts	Still runs, <i>versn</i> output is always empty ('')		Remove all references to a fourth output (<i>versn</i>) from fileparts.
intwarning	Warns	warning	If you use intwarning, you can implement the same warnings using the warning function.
isstr	Still runs	ischar	Replace all existing instances of isstr with ischar.
mmreader.isPlatformSupported	Warns, always returns true		For a platform-specific list of supported video file formats, use getFileFormats.
setstr	Still runs	char	Replace all existing instances of setstr with char.

Function or Function Element Name	What Happens When You Use the Function or Element?	Use This Instead	Compatibility Considerations
str2mat	Still runs	char	Replace all existing instances of str2mat with char.
stread	Still runs	textscan	Replace all existing instances of stread with textscan. For example, replace <pre>[a,b,c] = stread(...)</pre> with <pre>C = textscan(...)</pre> <pre>[a,b,c] = deal(C{:})</pre> Unlike stread, the textscan function converts numeric values to the specified data type, allowing preservation of integer types.
strvcat	Still runs	char	Replace all existing instances of strvcat with char. Unlike strvcat, the char function does <i>not</i> ignore empty strings.
textread	Still runs	textscan	Replace all existing instances of textread with textscan, similar to stread. Open and close files with fopen and fclose.

Function or Function Element Name	What Happens When You Use the Function or Element?	Use This Instead	Compatibility Considerations
wk1info	Still runs		Remove all instances of wk1info. Get information about Excel spreadsheets with xlsfinfo.
wk1read	Still runs		Remove all instances of wk1read. Read Excel spreadsheets with xlsread.
wk1write	Still runs		Remove all instances of wk1write. Write to Excel spreadsheets with xlswrite.

Graphics and 3-D Visualization

Plot Selector Supports Additional Toolboxes

The Plot Selector, which was upgraded in Version 7.9 (R2009b), now also generates plots for display functions in the following toolboxes:

- Curve Fitting Toolbox
- DSP System Toolbox
- Image Processing Toolbox
- Signal Processing Toolbox

The Plot Selector continues to support display functions for Control System Toolbox, Financial Toolbox, and Statistics Toolbox. You must have installed a toolbox to display data using its plotting functions. For more information about the Plot Selector, see “Enhanced Plot Selector Simplifies Data Display” on page 426.

External Interfaces/API

Changes to Compiler Support

Compatibility Considerations: Yes

New Compiler Support

MATLAB Version 7.10 (R2010a) supports these new compilers for building MEX-files:

Windows (32-Bit) Platforms

- Intel C++ Version 11.1
- Intel Visual Fortran Compiler Professional Edition for Windows Version 11.1, installed with Microsoft Visual Studio 2008 Shell. This product is bundled.
- Intel Visual Fortran Compiler Professional Edition for Windows Version 11.1 and Microsoft Visual Studio 2008 SP1 Professional Edition. Separate products.
- Open Watcom Version 1.8

Windows (64-Bit) Platforms

- Intel C++ Version 11.1
- Intel Visual Fortran Compiler Professional Edition for Windows Version 11.1, installed with Microsoft Visual Studio 2008 Shell. This product is bundled.
- Intel Visual Fortran Compiler Professional Edition for Windows Version 11.1 and Microsoft Visual Studio 2008 SP1 Professional Edition. Separate products.

Compiler Support to Be Phased Out

Support for the following compilers will be discontinued in a future release, at which time new versions will be supported. For an up-to-date list of supported compilers, see the Supported and Compatible Compilers Web page.

Windows (32-Bit) Platforms

- Intel Visual Fortran Version 10.1
- Intel C++ Version 9.1

Windows (64-Bit) Platforms

- Intel Visual Fortran Version 10.1
- Intel C++ Version 9.1

Discontinued Compiler Support

MATLAB no longer supports the following compilers:

Windows (32-Bit) Platforms

- Open Watcom Version 1.7
- Microsoft Visual Studio .NET 2003 Version 7.1

Solaris SPARC (64-Bit) Platforms

- Sun™ Studio 11 cc / CC Version 5.8
- Sun Studio 11 f90 Version 8.2

Compatibility Considerations

To ensure continued support for building your MEX-files, consider upgrading to another supported compiler. For an up-to-date list of supported compilers, see the [Supported and Compatible Compilers Web page](#).

Changes to Libraries on Linux with Debian Systems

Compatibility Considerations: Yes

If you run MATLAB Version 7.10 (R2010a) on a Linux with Debian® system, you must use Debian 5, as indicated on the Platforms & Requirements Web page.

MEX-files created with MATLAB Version 7.2 (R2006a) or earlier depend on the `libstdc++.so.5` library. Debian 5 does not include this library. MATLAB running on Linux platforms with Debian 5 cannot load these pre-R2006a MEX-files.

Compatibility Considerations

You cannot run MEX-files created with MATLAB R2006a or earlier on Linux with Debian 5. Recompile these files on a system with Debian 5.

Math Libraries Not Available to Build MEX-Files with Compaq Visual Fortran

Compatibility Considerations: Yes

MATLAB no longer provides the `libdflapack.dll` and `libdfblas.dll` math libraries for building Fortran MEX-files with a Compaq Visual Fortran compiler.

Compatibility Considerations

If you distribute MEX-files that call BLAS or LAPACK functions built on a Compaq Visual Fortran compiler, you must also distribute the `libdflapack.dll` and `libdfblas.dll` library files.

If MATLAB displays errors when loading a MEX-file and the Dependency Walker indicates missing `libdflapack.dll` and/or `libdfblas.dll` libraries, contact the MEX-file vendor for copies of the libraries. The third-party product, Dependency Walker, is available from the Web site <http://www.dependencywalker.com/>.

Cannot Create MEX-Files with DLL File Extension

Compatibility Considerations: Yes

On Windows 32-bit platforms, support for MEX-files with a `.dll` file extension is being phased out. Use the `.mexw32` extension instead.

MATLAB Version 7.10 will continue to execute `.dll` MEX-files, but future versions of MATLAB will not support the `.dll` extension. You can no longer use the `mex` function `-output` switch to create MEX-files with a `.dll` extension. If you enter a command such as:

```
mex myfile.c -output newfile.dll
```

MATLAB creates the MEX-file `newfile.mexw32` and displays a warning message.

For more information about MEX-files with `.dll` extensions, see [Running MEX-Files with .DLL File Extensions on Windows 32-bit Platforms](#).

Compatibility Considerations

Recompile MEX-files with `.dll` file extensions. Update MATLAB scripts or `makefiles` that explicitly specify `.dll` extensions for compiled MEX-files.

If you use MEX-files with a `.dll` extension from a third-party source, contact that vendor to get a recompiled version, referring to these release notes.

-largeArrayDims Option to MEX Will Become Default in Next Release of MATLAB

Compatibility Considerations: Yes

In the next release of MATLAB, the default `mex` command will change to use the large-array-handling API. This means the `-largeArrayDims` option will become the default.

You do not need to make changes to build and run MEX-files with MATLAB Version 7.10 (R2010a).

Compatibility Considerations

Source for MEX-files built on 64-bit platforms must be updated in order to successfully build and run with the next release of MATLAB. Review your source MEX-files and `mex` build scripts. For information about migrating your MEX-files to use the large-array-handling API, [Upgrading MEX-Files to Use 64-Bit API](#).

R2009bSP1

Version: 7.9.1
New Features: No
Bug Fixes: Yes

New features and changes introduced in this version are as follows:

The version number of the MATLAB Compiler™ Runtime (MCR) in release R2009bSP1 is different from the MCR version number in release R2009b. For details about MCR version numbers and corresponding MATLAB releases, see <http://www.mathworks.com/support/solutions/en/data/1-4GSNCF/?solution=1-4GS>

R2009b

Version: 7.9
New Features: Yes
Bug Fixes: Yes

Desktop Tools and Development Environment

Startup and Shutdown

Changes to `-nodisplay` and `-noFigureWindows` Startup Options

When you start MATLAB using `-nodisplay` (UNIX) or `-noFigureWindows` (Microsoft Windows) startup options, running a built-in GUI (predefined dialog boxes) generates this warning:

```
This functionality is no longer supported under
the nodisplay and -noFigureWindows startup options.
```

If the GUI is modal, MATLAB execution suspends, and you need to type **Ctrl+C** for the Command Window prompt to reappear.

This change affects predefined dialog boxes, such as `dialog`, `msgbox`, `printpreview`, `uigetfile`, `uisetcolor`, `waitfor`, `waitbar`, and more. For a list of predefined dialog boxes, see [Predefined Dialog Boxes](#). For more information on startup options, see the `matlab` (UNIX) and `matlab` (Windows) reference pages, respectively.

In a future release, instead of a warning, MATLAB will generate an error when you use such a dialog box under the `-nodisplay` or `-noFigureWindows` options.

Compatibility Considerations

To avoid generating the warning, start MATLAB without the `-nodisplay` or `-noFigureWindows` startup options. To avoid warnings while continuing to use these startup options, remove the code that is now producing the warnings.

Changes to Memory Manager Startup Options

Version 7.9 removes support for the `-memmgr` and `-check_malloc` command line arguments and the `MATLAB_MEM_MGR` environment variable.

Compatibility Considerations

MATLAB ignores any memory manager options.

Desktop

Compatibility Considerations: Yes

New features and changes introduced in Version 7.9 (R2009b) are:

- “Ability to Customize Keyboard Shortcuts” on page 380
- “Ability to Set Fonts Preferences for Extended M-Lint Messages and Function Browser” on page 381
- “Save Files from MATLAB Web Browser” on page 382

Ability to Customize Keyboard Shortcuts

MATLAB supports customizing keyboard shortcuts for desktop tools. Press combinations of keyboard keys to perform a desktop action, instead of using the mouse to select items from menus. For example, press **Ctrl+N** to open a blank file in the Editor.

The ability to customize keyboard shortcuts enables you to:

- Modify keyboard shortcuts across desktop tools on an action-by-action basis.
- Modify keyboard shortcuts to match other applications you use or to match your personal preferences.
- Share your keyboard shortcuts with others, or use shortcuts created by someone else.
- Create keyboard shortcuts for some actions that currently have no shortcut.
- Use your preferred keyboard shortcuts when you use MATLAB on a different system than you typically use.

To customize keyboard shortcuts, choose **File > Preferences > Keyboard > Shortcuts**.

MATLAB does not support customizing keyboard shortcuts for Figure Windows, dialog boxes, or toolboxes. For details, see [Customize Keyboard Shortcuts](#). For a video demo, see [Customizable Keyboard Shortcuts](#).


Compatibility Considerations

- The method for specifying keyboard shortcuts differs from previous versions.

In previous versions, you chose **File > Preferences > Keyboard**, and then chose a set of key bindings. MATLAB no longer limits your choices to either platform-specific settings or Emacs settings.

- Some default keyboard shortcuts differ from the previous defaults.

Defaults changed in Version 7.9 (R2009b) to be more consistent across the MATLAB desktop. Previously, you could specify keyboard shortcut preferences for the Command Window and Editor/Debugger only. For instance, on Windows, default keyboard shortcut preferences appeared as follows:



To restore keyboard shortcuts that were the default before Version 7.9 (R2009b):

- 1 Choose **File > Preferences > Keyboard > Shortcuts**.
- 2 From the **Active settings** drop-down menu, choose **R2009a Windows Default Set**, **R2009a Macintosh Default Set**, or **R2009a UNIX Default Set**, depending on the platform on which MATLAB is installed.

Ability to Set Fonts Preferences for Extended M-Lint Messages and Function Browser

MATLAB now supports setting the font size and type for extended M-Lint messages and the function browser. In previous releases, changes to **HTML Proportional Text** affected only the display in the MATLAB Web browser, the Profiler, and Help topics. To set font preferences:

- 1 Choose **File > Preferences > Fonts > Custom**.
- 2 Under **Desktop tools**, select **HTML Proportional Text**, and then specify the font size and type you want to use.

For more information, see Fonts.

Save Files from MATLAB Web Browser

To save a file being displayed in the MATLAB Web Browser, select **File > Save As**.

Help Browser

Compatibility Considerations: Yes

For a demonstration of enhancements to the Help browser, watch the Help Browser Enhancements video.


Improved Contents Listing

When you expand a product in the **Contents** pane, you now can view the following:

- Function and block names with brief descriptions — Expand **Functions** or **Blocks**, and then expand a category to see the list and descriptions. Select a function or block to view its reference page.

If you provide your own HTML help files for use in the Help browser, you now can include **Functions** and **Blocks** entries for your toolbox.

- Demos — Expand **Demos**, and then select a demo from the list to view or run it.



Enhanced Presentation of Search Results


Each search result includes:

- A preview of where the search words were found within the page.
- An icon representing the type of document, such as a reference page or demo.

Use new sorting and grouping features to arrange results:


- Sort results by **Relevance**, in addition to sorting by **Type** and **Product**, which were available in previous versions.
- After sorting by **Type** or **Product**, you now can collapse and expand results for each type or product. To expand or collapse all groups, right-click in the results pane and select the option you want from the context menu.


The following example of **Search Results** in the Help browser illustrates grouping, previews, and the block reference page icon.




Viewing Pages

- To see where the current page is located within the documentation, use the navigation bar at the top of the display pane. To go to another topic in the documentation, select an entry from the navigation bar.



- Use the new Actions button  on the display pane toolbar to access features such as Refresh, which clears the search results highlighting for the current page.

- Get links to reference pages for overloaded functions. When you run `doc foo`, if `foo` is an overloaded function, a message appears at the top of the display pane that provides links to the other `foo` reference pages.
- To use the Help browser alongside other tools, dock it in the desktop. When docked in a narrow area of the desktop, the pane for **Contents** and **Search Results** moves above the display pane.



Compatibility Considerations

The **Index** and **Demos** tabs are no longer in the Help browser:

- To find terms that were in the **Index**, use the search feature instead.
- To access demos for a product, go to the **Contents** pane and expand the **Demos** entry for the product.

The Actions button on the toolbar provides access to features for the displayed page. Previously, some of these features were available on individual toolbar buttons. To add individual toolbar buttons, right-click the toolbar and select **Customize**.


If you provide your own files for use in the Help browser:

- Remove the `helpindex.xml` entry from the `info.xml` file for your toolbox. MATLAB no longer supports the **Index**.
- Demos you add now appear in the **Contents** pane under **Other Demos**, which is after the entries for all MathWorks products.

For more information about the new Help browser features, see [Help and Product Information](#).

Workspace and Variable Editor

Improved Workspace Plotting Tool

The Plot Selector button on  the Workspace Browser and Variable Editor toolbars has a new look and added capabilities, options, and help. The tool now displays larger icons, includes many more graphing functions, summarizes each function, and displays pop-up windows with syntax descriptions (function hints). You can customize the tool by rearranging and categorizing functions, and by creating a list of “favorites”.

For further details, see this video demo and the release note “Enhanced Plot Selector Simplifies Data Display” on page 426.






Managing Files

Compatibility Considerations: Yes


Enhanced Current Folder (Directory) Browser

The Current Directory browser is now the Current Folder browser.

For an overview of the enhancements, watch this video, Current Folder Browser Enhancements, or review the following summary:

- Use the expandable tree structure to view the contents of the current folder. Double-click a subfolder to make it the current folder.
- Display the file type in a column.
- Distinguish types of MATLAB program files using new icons:
 -  class
 -  function
 -  script
- View file descriptions below file names. To show or hide descriptions, select **View > Show > Description**.
- Display hidden files a new way:
 - On Windows platforms, MATLAB follows your Windows preference for hidden files.
 - On other platforms, MATLAB uses the new setting in Current Folder preferences.
- Find files and folders within the current folder and its subfolders:
 - To access the search feature, click the Search button  on the address bar, and then enter the string you want to find.
 - To clear the results and display all files and folders in the current folder, click the Clear button .

The following illustration shows the new Current Folder browser, including the tree view, new icons for program files, and the search button.



Compatibility Considerations

- With the new tree structure, you now see all files, including those in subfolders. You might not be able to run the files you see in the subfolders. To run a file from a subfolder, the subfolder must be on the search path or the subfolder must become the current folder. In previous versions, you could only see files in the current folder, so you could run every file you could see.

- You now search for files by clicking the search button in the address bar. In previous versions, the search feature, referred to as the filter field, appeared if your preference was set to display it.
- File descriptions now appear below the file name. In previous versions, they displayed in a column.

For more information about the new features, see [Managing Files in MATLAB](#).

File Exchange Desktop Tool – Find and Get Files Created by Other Users

Watch this video, MATLAB File Exchange Access, or review the following summary of what you can do with the new File Exchange desktop tool:







- Access user-created files from the File Exchange repository. The files are at MATLAB Central, the community area of the MathWorks Web site.
- Use the files in your own work to save time and get new ideas.
- Work with the file repository from within the MATLAB desktop.
- Use features like those found in the Web site interface to the File Exchange repository.

The File Exchange desktop tool offers these main features:


- Find files by searching and by selecting tags (keywords associated with files).
- Sort results. For example, show the most highly rated or the most recent files first.
- View details about a file.
- Download files to use in MATLAB.
- Provide feedback about files.

To open the File Exchange tool, select **Desktop > File Exchange**.

The screenshot shows the File Exchange Desktop Tool interface. At the top, there is a menu bar with 'File', 'Desktop', 'Window', and 'Help'. Below the menu bar, the user is logged in as 'fx2'. There are links for 'Download History', 'Log Out', and a help icon. A search bar is present with the text 'Search the File Exchange'. To the right of the search bar is a 'Tag View' button. Below the search bar, there are several tags: 'data export', 'data import', 'example', 'graphics', 'gui', 'image processing', 'mathematics', 'optimization', 'probability', 'statistics', and 'utilities'. A 'View tags as:' dropdown is set to 'List', and there is a 'Cloud' option. Below the tags, there is a table of files.

Submitted	File Summary	Tags	Rating	Downlo...	
Today	 flattin/merging ... {{a}, b, {c,{d;e}}... Author: Oleg Kom...	cell matrix nested cells	★ ★ ★ ★ ☆ 3.0 1 ratings	20	
Today	 xml_io_tools Read XML files int... Author: Jaroslaw ...	base64 data data export ...	★ ★ ★ ★ ★ 4.8 20 ratings	190	
Today	 Reaminging time ... Returns a string w... Author: Reaming...	process remaining time	none	42	

1 - 10 of 3,901 results.

If you have questions while you work, access the File Exchange FAQ by clicking the Help button . For full documentation, see File Exchange — Finding and Getting Files Created by Other Users.

Editing and Debugging MATLAB Code Files

New features and changes introduced in Version 7.9 (R2009b) are:

- “Syntax Highlighting for VHDL and Verilog Code” on page 394
- “File and Folders Comparison Tool Enhanced” on page 394


Syntax Highlighting for VHDL and Verilog Code

The MATLAB Editor now supports syntax highlighting for VHDL and Verilog code. For details see, [Highlight Syntax to Help Ensure Correct Entries in the Editor](#).

File and Folders Comparison Tool Enhanced

When you use the File and Folders Comparisons tool to compare folders, it now includes the following information about each file in each folder:

- The file size, in bytes
- The date the file was last modified

In addition, the File and Folders Comparisons tool enables you to reload the information by clicking the refresh button  or selecting **File > Refresh**. For details see, [Comparing Files and Folders](#).

Publishing MATLAB Code Files to PDF Output Format

MATLAB now supports PDF as the output format for publishing MATLAB code files. For instructions on how to publish to .pdf files, watch the Publishing Features video demo. For details, see Steps for Publishing sine_wave_f.m to PDF.

Internationalization

How MATLAB Reads Customized Locale Settings on Macintosh OS X Platforms

If you use the **Customize** option to modify the locale setting, MATLAB ignores the customized portion. For example, if you select the euro currency symbol for a locale set to the United Kingdom, the locale name is:

```
en_GB@currency=EUR
```

MATLAB uses the locale name:

```
en_GB
```

Mathematics

Computational Geometry Functions Being Changed

Compatibility Considerations: Yes

2- and 3-D computational geometry functions (`delaunay`, `convhull`, `griddata`, `voronoi`, `delaunay3`, `griddata3`) no longer use QHULL or the QHULL options arguments. The N-D functions `gridatan`, `delaunayn`, `convhulln`, and `voronoin` still use QHULL.

Compatibility Considerations

The QHULL options arguments to `delaunay`, `convhull`, `griddata`, and `voronoi` are no longer required and are currently ignored. Support for these options will be removed in a future release.

Computational Geometry Functions Being Removed

Compatibility Considerations: Yes

A future release will remove the `griddata3`, `dsearch`, `tsearch`, and `delaunay3` functions. See the table below for alternatives.

Function Name	Use This Method Instead
<code>griddata3</code>	<code>TriScatteredInterp</code>
<code>dsearch</code>	<code>DelaunayTri/nearestNeighbor</code>
<code>tsearch</code>	<code>DelaunayTri/pointLocation</code>
<code>delaunay3</code>	<code>DelaunayTri</code>

Compatibility Considerations

Update your old code to use the new computational geometry classes `DelaunayTri` and `TriScatteredInterp`.

New Sparse Matrix Functionality In `qr` and `mldivide` Functions

`mldivide` supports complex rectangular sparse input matrices. `qr` supports complex sparse input matrices. `qr` for sparse matrix input now supports a third output argument that contains a fill-reducing permutation.

Support for Large-Sized Dimensions In `fft`

MATLAB functions `fft`, `fft2`, and `fftn` (and their inverses `ifft`, `ifft2`, and `ifftn`) can now handle input arrays with a size in 1 dimension greater than $2^{31} - 1$ on 64-bit platforms.

Performance Improvement For Large Data Sets

- MATLAB includes improved sparse matrix performance for indexing, basic math, binary and relational operators, and exponential functions.
- There are significant performance improvements to `conv2`.

erfc core Being Removed

Compatibility Considerations: Yes

Use of erfc core will produce a warning:

ERFCORE will be removed in a future release.
Use ERF, ERFC, ERFCX, ERFINV, or ERFCINV instead.

Compatibility Considerations

Replace all instances of erfc core with erf, erfc, erfcx, erfinv, or erfcinv.

New Multithreading Capability

Many MATLAB functions are now multithreaded:


- `sort`
- `bsxfun`
- `mldivide` for sparse rectangular matrix input
- `qr` for sparse matrix input
- `filter` for matrices and higher-dimensional arrays
- `gamma`, `gammaln`
- `erf`, `erfc`, `erfcx`, `erfinv`, `erfcinv`

New Test Matrices in gallery Function

The gallery suite of test matrices includes new options `integerdata`, `normaldata`, and `uniformdata`.

Data Analysis

Improved Plot Selector Makes Graphic Data Exploration Easier

The Plot Selector button on the Workspace Browser and Variable Editor toolbars has a new look and added capabilities, options, and help. Now the Plot Selector button  changes its appearance to reflect the variable or variables you select. Now it suggests a plot type and indicates its calling argument sequence. You can also make the Plot Selector list the types of graphs you use most often at the top of its drop-down menu. The tool provides descriptions and hints to help you discover data graphing functions and learn to use them more effectively.

For further details, see this video demo and the release note “Enhanced Plot Selector Simplifies Data Display” on page 426.

Programming

Ignore Selected Arguments on Function Calls

This version of MATLAB introduces a new usage for the tilde (~) operator. As in earlier releases, tilde signifies a logical NOT. In the 9b release, you can also use the tilde operator to specify unused outputs in a function call, or unused inputs in a function definition. See Ignore Function Inputs in the Programming Fundamentals documentation for more information on this feature.

Replacing Output Variables with Tilde

This feature enables you to replace this type of function call:

```
[val1, ignoreThisOutput, val3] = myTestFun;
```

with the following:

```
[val1, ~, val3] = myTestFun;
```

MATLAB ignores any values returned by a function that have a corresponding tilde in the output list. This new syntax can help you avoid confusion in your program code and unnecessary clutter in your workspace. It also avoids wasting memory to store unused outputs returned from the called function.

Replacing Input Arguments with Tilde

You can also use the tilde operator to specify unused inputs when you are creating a function. You can replace this type of function definition:

```
function myTestFun(arg1, ignoreThisInput, arg3)
```

with the following

```
function myTestFun(arg1, ~, arg)
```

Whenever this function is called, MATLAB ignores any inputs passed to the function that have a tilde in the corresponding position in the input argument list. You are likely to find the tilde operator most useful when writing callback functions and subclass methods that must match a predefined function interface.

Internal Packages Make Reserved Functions Easy to Identify

The MathWorks® reserves the use of packages named `internal` for utility functions used by internal MATLAB code. Functions that belong to an `internal` package are intended for The MathWorks use only. Using functions that belong to an `internal` package is strongly discouraged. These functions are not guaranteed to work in a consistent manner from one release to the next. In fact, any of these functions and classes may be removed from the MATLAB software in any subsequent release without notice and without documentation in the product release notes.

See [Internal Utility Functions in the Programming Fundamentals documentation](#) for more information.

Use of `lasterror`, `lasterr`, `rethrow(errStruct)` Not Recommended

Compatibility Considerations: Yes

In version 7.5, The MathWorks introduced a new class called `MException` for use in error handling. Prior to this change, the `lasterr` and, more recently, `lasterror` functions kept track of only the one most recently thrown error. The state of any errors thrown before that was overwritten by newer errors. Also, this error state was globally accessible, which means that it could be unintentionally modified or destroyed either during an interactive session or by another function.

When using the newer, object-based error mechanism, every error generated by a MATLAB function stores information about what caused the error in a separate `MException` object. This enables MATLAB to store information about multiple errors, adds the capacity to store new fields of information including links to related errors, and also resolves the problem of being globally accessible.

The MathWorks now discourages the use of the `lasterr` and `lasterror` functions because the information they return is global and thus has the potential to be corrupted. You should replace the use of these two functions with the new style of `try-catch` statement that captures an `MException` object to represent the error. When entering commands at the MATLAB command line, you can also use the static method `MException.last` to retrieve information on the most recent error. For more information on this method of error handling, see [The MException Class](#).

This change also affects which form of the `rethrow` function to use when reissuing an exception. The original `rethrow` function, in use since before version 7.5, accepts only a structure as input. Because this structure is typically obtained using the `lasterror` function, this form of `rethrow` should be avoided. The later form of `rethrow(MException)`, introduced in version 7.5, accepts an `MException` object as input, and is the recommended form.

Compatibility Considerations

It is strongly recommended that you discontinue the use of `lasterror` and `lasterr`, and that you replace the use of these functions in your program code with the `MException`-based style of error handling described above.

Use of maxNumCompThreads No Longer Recommended

Compatibility Considerations: Yes

Invoking the function `maxNumCompThreads` now returns the following warning:

Warning: `maxNumCompThreads` will be removed in a future release. Please remove any instances of this function from your code.

`maxNumCompThreads` continues to operate the same in this release of MATLAB. However, the function will be discontinued in a future release of the product.

Compatibility Considerations

It is recommended that you discontinue the use of `maxNumCompThreads`. However, if you do have any program code that invokes this function, you should make sure that such programs are not affected by this new warning.

Excel Worksheet Selection in the Import Wizard

In previous releases, the Import Wizard imported only the first populated worksheet in an Excel file. The Import Wizard now allows you to specify the worksheet to import. To start the Import Wizard, use one of the following methods:

- Select **File > Import Data**.
- Call `uiimport`.
- Double-click a file name in the Current Folder browser.

Motion JPEG 2000 Files Supported by mmreader

Compatibility Considerations: Yes

mmreader now imports Motion JPEG 2000 (.mj2) files on Windows, Macintosh, and Linux platforms.

Compatibility Considerations

Because mmreader imports Motion JPEG 2000 files, the function `mmreader.isPlatformSupported` always returns true on Windows, Macintosh, and Linux platforms. For a list of file formats that mmreader supports, and the requirements to read these formats on each platform, see the mmreader reference page.

Minimum Sample Rate for audioplayer

Compatibility Considerations: Yes

If you specify a sample rate less than 80 samples per second, `audioplayer` generates an error with the following ID:

```
MATLAB:audioplayer:positivesamplerate
```

Compatibility Considerations

In previous releases, the error ID on Windows platforms for low sample rates was:

```
MATLAB:audioplayer:negativesamplerate
```

Change any references to this identifier to:

```
MATLAB:audioplayer:positivesamplerate
```


Documentation Changes: File I/O and Data Import and Export

The function category “File I/O” is renamed “Data Import and Export.” It appears immediately below the category “Desktop Tools and Development Environment.”

In the MATLAB User Guide, Data Import and Export content previously appeared in the Programming Fundamentals documentation. The User Guide now includes a stand-alone topic for Data Import and Export.

Object Array Property Indexing

Object array indexing operations on properties now return an error for improper array references. Before MATLAB 7.9, an expression such as:

```
obj.Prop(n) % for non-scalar obj is invalid if Prop is a property
```

did not return an error. MATLAB 7.9, you can reference or assign properties from scalar objects only by entering:

```
obj(int).Prop(n)
```

where `int` is a positive integer.

Equality of Objects Using `isequal` Now Ignores Numeric Class

Before MATLAB 7.9, an expression such as:

```
isequal(a,b)
```

returned false in cases where `a` and `b` are objects of the same class that have properties set to numeric values which are mathematically equivalent, but of different classes (for example, `double` and `single`),

The behavior of `isequal` in MATLAB 7.9 is consistent with the documented behavior (see `isequal`). `isequal` does not consider class when comparing numeric values.

Class Defining Private/Abstract Property Now Errors

MATLAB 7.9 returns an error when it loads a class that defines a property as both `Abstract` and `Private`.

Subclasses of Built-in Classes and numel

Before MATLAB 7.9, the `numel` function did not return the same results for built-in classes and subclasses of built-in classes. In MATLAB 7.9, the behavior of `numel` is consistent with built-in classes and subclasses of built-in classes. See [Understanding size and numel](#) for a discussion of the current behavior.

Array Expansion with Indexed Assignment

Before MATLAB 7.9, initializing a handle object array by specifying the last element in the array to create it:

```
obj(10) = MyClass;
```

resulted in the same handle being assigned from the second to the penultimate elements of the array. With MATLAB 7.9, all elements in the handle object array have unique handles. See [Creating Object Arrays](#) for more information on the current behavior.

New Tiff Object Enables Writing of Tiled Data and Broader Metadata Support

Using the new `Tiff` object, you can now write portions of a TIFF file and update the values of individual metadata tags in an image. MATLAB has long offered the capability of reading and writing TIFF files, using the `imread` and `imwrite` functions. However, if you wanted to update any part of the image, you had to write the entire image to the file. Similarly, if you just wanted to update a tag, you had to write the entire image. By providing access to functions in the LibTIFF library, the `Tiff` object offers more flexibility in creating and editing TIFF images. You can write data to specific tiles in an image and update individual tags in a file, without having to write the entire image.

Ambiguity Error Now Reported

Compatibility Considerations: Yes

Due to a bug, versions of MATLAB prior to Version 7.9 did not report an error in functions such as the following, even though it cannot be determined in the last line whether `U` is a variable or a function:

```
function r = testMfile1(A)
A = 1;
eval('U = 1;');
r = A(logical(end), U(end));
```

However, if you replace the last line with

```
r = A(U(end));
```

MATLAB reports an ambiguity error and has done so since Version 7.0. Starting in Version 7.9, MATLAB reports an ambiguity error for either statement.

Compatibility Considerations


In certain circumstances, it is possible that you will see ambiguity errors generated in code that did not report this error in previous releases. If you do get such an error, examine your code and resolve the ambiguous statements.

Graphics and 3-D Visualization



Enhanced Plot Selector Simplifies Data Display




Compatibility Considerations: Yes

The Plot Selector workspace tool creates graphs of workspace variables. As this video demo shows, the tool lets you access more types of data display functions and provides help about each one. It also categorizes display functions and lets you organize them within its drop-down menu. The following illustration shows the old and new versions of the Plot Selector and calls out new features.




Use the Plot Selector tool to instantly generate graphs of workspace variables. You can choose from more than 40 two-dimensional, three-dimensional, and volumetric MATLAB data display types. It also constructs graphs using Control System Toolbox, Financial Toolbox, and Statistics Toolbox functions if your installation includes those products.

The Plot Selector button  displays a graph icon and the names of selected variables in the Workspace browser or the Variable Editor. Until you select one or more variables, the button reads **Select to plot** . The graphing function for one or two data vectors still defaults to `plot`, but the tool now gives you additional options and information, including the following:


- The grouping of menu items into categories of graph types, such as **Stem and Stair Plots**, **3-D Surface Plots**, and **Analytic Plots**. You can rearrange categories and items within a category by dragging them.
- A **Favorites** category at the top of the menu, where you can collect the types of graphs you use most often. Your collection of favorites persists across MATLAB sessions.
- A star-shaped button  on menu items that adds a graph type to or removes one from your Favorites collection.
- Two tabs   for toggling the scope of the menu:
 - **Plots for <variable names>** — The set of graphs you can generate with the currently selected variables
 - **All plots** — A master list of graphing functions available on your system

On the **All plots** tab, graphing functions that are not compatible with the selected variables display in gray and do not plot. Incompatible plot types do not appear on the first-tab menu.

- A button  to interchange the axes positions of two selected variables
- Pop-up descriptions of function syntax when your mouse pointer lingers over a menu item
- Direct access to your Favorites from context menus in the Workspace Browser and the Variable Editor

For more information, see [Creating Plots from the Workspace Browser](#).

Compatibility Considerations

- In previous versions, the Plot Selector automatically assigned variables named `t` and `time` to the x -axis. Now, the variable you select first always plots on the x - axis. Use the switch variable input order button  to interchange the x and y variables before plotting them.
- In previous versions, clicking **Plot Selector > More Plots** opened the Plot Catalog tool. Now, you click **Catalog** at the bottom of the Plot Selector GUI to open the Plot Catalog tool. The Plot Catalog has not changed.

Certain Print Options and Devices Now Warn When Used

Compatibility Considerations: Yes

The following print command option and device now throw warnings when used and will be removed in a future release:

Option/ Device	Warning ID	Warning Text
'-adobecset' print option	'MATLAB:print: adobecset:DeprecatedOption'	The -adobecset option will be removed in a future release.
'-dill' print device (native support for Adobe Illustrator)	'MATLAB:print: Illustrator:DeprecatedDevice'	The '-dill' print device will be removed in a future release. Use Encapsulated PostScript ('-depsec') instead.

If you wish to prevent these warnings from displaying, use the warning command.

- To disable the warning generated by using the `adobecset` print option:

```
warning('off', 'MATLAB:print:adobecset:DeprecatedOption');
```

- To disable the warning generated by using the `dill` print device:

```
warning('off', 'MATLAB:print:Illustrator:DeprecatedDevice');
```

Compatibility Considerations

If you have developed code that uses the previous option or device, in the future you must remove such calls or replace them with other code.

The view Function No Longer Supports 4-by-4 Transformation Matrices as Input

Compatibility Considerations: Yes

The `view` function no longer supports 4-by-4 transformation matrices as input arguments. Previously, you could create a 4-by-4 transformation matrix and use it with `view`.

Compatibility Considerations

If you have code that calls `view(T)`, explore using `view([az e1])` instead.

Creating Graphical User Interfaces (GUIs)

Expanded Documentation on Techniques for Programmatic GUI Design

The section Lay Out a Programmatic GUI of the Creating Graphic User Interfaces documentation has been expanded. The updated section, formerly called “Aligning Components,” now has the title Compose and Code GUIs with Interactive Tools.

The renamed section describes techniques, functions, and predefined dialog boxes you can use to accelerate programmatic construction of GUIs (that is, those you create without using GUIDE).

The section includes examples of setting component positions, colors, and font properties interactively. Also included is an example function that generates a `set` statement for a specified property of any GUI component. By running this function and pasting its output into your GUI code file, you can save time and avoid making typographical errors.

Previous Change to How UI Components Set the Figure SelectionType Property

The MATLAB `SelectionType` figure property had an undocumented change in V. 7.6 (R2008a). That change modified how the property is set in response to single-clicking and double-clicking objects, particularly `uicontrols`, with and without key modifiers.

For information about this change, including potential incompatibilities, see “Changes to How `uicontrols` Set Figure `SelectionType`” on page 650. The table in that release note specifies the `SelectionType` setting resulting from clicking a UI component in both enabled and disabled states.

External Interfaces/API

Changes to Compiler Support

Compatibility Considerations: Yes

Support for Apple Macintosh (64-bit) Platforms

MATLAB Version 7.9 (R2009b) supports these new compilers for building MEX-files:

- Apple Xcode 3.1 (gcc / g++ Version 4.0.1)
- GNU gfortran Version 4.3

Compiler Support to Be Phased Out

MATLAB Version 7.9 (R2009b) supports the following compilers but will not support them in a future version.

Windows (32-bit) Platforms

- Intel Visual Fortran Version 10.1
- Intel C/C++ Version 9.1
- Microsoft Visual Studio .NET Version 7.1

Windows (64-bit) Platforms

- Intel Visual Fortran Version 10.1
- Intel C/C++ Version 9.1

Solaris SPARC (64-bit) Platforms

- Sun Studio 11 cc / CC Version 5.8
- Sun Studio 11 f90 Version 8.2

Discontinued Support for Intel Visual Fortran Version 9.1

MATLAB no longer supports the Intel Visual Fortran Version 9.1 compiler on the following platforms:

- Windows 32-bit
- Windows 64-bit

Compatibility Considerations

To ensure continued support for building your Fortran programs, consider upgrading to another supported compiler. For an up-to-date list of supported compilers, see the Supported and Compatible Compilers Web page.

Run-Time Libraries Required for Applications Built with Microsoft Visual Studio 2008 Compiler

You must provide the Visual C++ run-time libraries if you distribute any of the following:

- MEX-file
- Engine application
- MAT-file application built with the Visual Studio 2008 compiler

You need these files to run applications developed with Visual C++ on a computer that does not have Visual C++ 2008 installed. For information on locating the Microsoft Visual C++ 2008 Redistributable Package (x86), containing `vc redistrib_x86.exe` and `vc redistrib_x64.exe`, consult your Microsoft documentation.

Changes to Building MEX-Files

INLINE Option to MEX Function Deprecated

The use of the `-inline` switch has been deprecated and will not be available in future versions of the `mex` function.

MEX Function No Longer Automatically Includes `mexversion.c` When Building MEX-Files

The `mex` function no longer automatically compiles and links its own copy of `mexversion.c` when generating MEX-files.

New Features for Interface to Microsoft .NET Framework

This release includes several changes that affect your use of the Microsoft .NET framework:

- The `NET.addAssembly` function returns information about the assembly in the `NET.Assembly` class. You can also add an assembly using an instance of the `System.Reflection.AssemblyName` class.
- You can access elements of a .NET array using MATLAB one-based indexing, as described in [Accessing .NET Array Elements in MATLAB](#).
- To call a generic method, use the `NET.invokeGenericMethod` function.
- You can change a static property or field name using the `NET.setStaticProperty` function.
- You can use overloaded operators, such as `+` and `*`. For a complete list of supported operators, see [How MATLAB Represents .NET Operators](#).

R2009a

Version: 7.8
New Features: Yes
Bug Fixes: Yes

Desktop Tools and Development Environment

Desktop New Features Video

For an overview of the major new features in the MATLAB Desktop Tools and Development Environment area, watch this video demo. Another way to access the demo is by selecting the **Demos** tab in the Help browser, and then selecting **MATLAB > New Features in Version 7.8**.

Startup and Shutdown

The `matlab` command to start MATLAB now supports the `-singleCompThread` option on all platforms. When you specify this option, you limit MATLAB to a single computational thread. By default, if you do not specify this option, MATLAB makes use of the multithreading capabilities of the computer on which it is running.

Desktop

Compatibility Considerations: Yes

New features and changes introduced in Version 7.8 (R2009a) are:

- “New System Browser Preference Instead of `docopt.m` for MATLAB on UNIX Platforms” on page 445
- “Test Proxy Settings for Accessing the Internet from MATLAB” on page 446

New System Browser Preference Instead of `docopt.m` for MATLAB on UNIX Platforms

On UNIX platforms (except Apple Macintosh), MATLAB now uses the Mozilla® Firefox® browser by default to display documents or Web sites in a system browser. If you want MATLAB to use a different system browser, use the new **System Web browser** setting in Web preferences to specify it. In addition, the `web` function with the `browser` option now determines the system browser to use from the preference. For more information, click the **Help** button in the Web preference pane, or see Web Preferences.

Compatibility Considerations

In previous versions, the default system browser on UNIX platforms was Netscape Navigator®; it is now Firefox. If you do not have Firefox on your system, when MATLAB tries to use a system browser, it produces a warning. To correct the problem, use Web preferences to specify a system browser that is installed.

In previous versions, if you wanted to use a different browser, you specified it in the `docopt.m` file. Starting in R2009a, MATLAB ignores the browser specified in `docopt.m`. If you have code that relies on `docopt.m`, your code still runs, but it produces a warning. Remove the calls from your code. In future versions, the code will not run and will produce an error.

If you have your own `docopt.m` file, delete it and either use the new default, Firefox, or specify a different system browser using Web preferences.

Test Proxy Settings for Accessing the Internet from MATLAB

If you want to access the Internet from MATLAB, and your network uses a firewall or another means of protection that restricts Internet access, you now can ensure your proxy server settings are working correctly. Click the new **Test Connection** button in Web preferences, and MATLAB will use the proxy settings you specified in Web preferences to attempt to access the Internet. For more information about the proxy server features, click the **Help** button in the Web preferences pane, or see Web Preferences.

Running Functions – Command Window and History

Tab Completion for Class Directories and File Names

The Command Window and Editor now support tab completion for class directories. In addition, the Command Window supports tab completion for class file names. For details, see Complete Names in the Command Window Using the Tab Key.

Help and Related Resources

Compatibility Considerations: Yes

New features and changes introduced in Version 7.8 (R2009a) are:

- “Help Browser No Longer Reopens at Startup” on page 448
- “docsearch Accepts Multiple Words Without Parentheses” on page 448
- “View Your Platform (32-bit or 64-bit) and Architecture in the About Dialog Box” on page 449

Help Browser No Longer Reopens at Startup

When you start MATLAB, the Help browser no longer automatically opens if you had it open when you last quit MATLAB.

Compatibility Considerations

In previous versions, the Help browser opened at MATLAB startup if it had been open when you last quit MATLAB. If you want the Help browser to automatically open at startup, use a startup option. For example, you can include a `helpbrowser` statement in your `startup.m` file. For more information, see Startup Options.

If you include a statement in a `finish.m` file that closes the Help browser automatically whenever you quit MATLAB, you now can remove that statement because MATLAB now performs the action by default.

docsearch Accepts Multiple Words Without Parentheses

The `docsearch` function, which you can use to search the documentation, now accepts multiple words as input, without requiring the function form of the syntax. For example, in previous versions, you used `docsearch('word1 word2')`, but now you can use `docsearch word1 word2`. With the new form of the syntax, you can use all options for `docsearch`, such as wildcards (for example, `docsearch wor*`) and exact phrases (for example, `docsearch "word1 word2"`).

View Your Platform (32-bit or 64-bit) and Architecture in the About Dialog Box

To find out if you are currently running a 32-bit or 64-bit version of MATLAB, select **Help > About MATLAB**, and view the value in the resulting About MATLAB dialog box. You might need to know the version if you want to take advantage of the benefits of 64-bit MATLAB, or if you want to use files that depend on the version, such as MEX-files.

The About MATLAB dialog box also shows the architecture value, for example, (win32) or (win64). You use this value for the arch option of the mex function.

For more information, see [Information About your Installation](#).

Workspace, Search Path, and File Operations

Enhancements to Current Directory Browser

These are the enhancements to the Current Directory browser:

- You can use the new **View** menu to choose the columns to display, to specify the sort order for a column, and to apply grouping for any attribute. In the previous version, you performed these actions using the column header and its context menus, which you can still do (but only on Microsoft Windows platforms). For more information, see [Sorting and Grouping Files and Folders](#).
- A new **Description** column displays the brief description for files and directories in the current directory. To show the column, use **View > Choose Columns**. Descriptions include the first help line in a MATLAB program file, and a model file's description, which is useful because you do not need to start the Simulink software to view it. The description is the same one that appears with the details for a selected file. For more information, see [Viewing Help for a MATLAB Program File](#).
- If you try to rename a MATLAB program file in the Current Directory browser to an invalid name, such as `*myfile.m`, a warning appears, notifying you about the name problem. If you want to run the file, change the file name to a valid one. For more information about what a MATLAB file name requires to be valid so you can run it, see [Naming Functions](#).
- When you right-click a FIG-file in the Current Directory browser, there is a new option to open the figure in GUIDE.

Editing and Debugging MATLAB Code


Compatibility Considerations: Yes

New features and changes introduced in Version 7.8 (R2009a) are:


- “Many M-Lint Messages Now Extend to Provide an Explanation and Suggested Action” on page 451
- “M-Lint Messages Now Searchable in Preferences” on page 453
- “Block Indenting Option No Longer Provided” on page 456
- “Integrated Text Editor Option Removed from Editor/Debugger Preferences Panel” on page 456
- “New Navigation Aids in File and Directory Comparisons Tool” on page 456
- “Wrap Around Option for Find and Replace Now On By Default” on page 456

Many M-Lint Messages Now Extend to Provide an Explanation and Suggested Action

When you create a file with integrated M-Lint warning and error messages enabled, you can get additional information about many of the messages. When you hover the pointer over an M-Lint indicator that has an extended message, the message appears as a link:



When you click the link, the message window expands to display an explanation and suggested action.



When you click a link within the extended message, the Help browser opens to provide more information.


M-Lint Messages Now Searchable in Preferences

You can now filter the list of M-Lint messages in the preferences panel (**File > Preferences > M-Lint**), to find a message of interest.

For example, you can search for a message:

- Containing a string
- Corresponding to a particular message ID
- Within a given category
- With a setting different from the default

Filtering the list of messages can help you see, for example, why certain messages are suppressed, and which messages are disabled. It can be helpful when you want to see the explanation and suggested action for a message, as described in “Many M-Lint Messages Now Extend to Provide an Explanation and Suggested Action” on page 451.



Block Indenting Option No Longer Provided

The **Block Indent** option is no longer available. Previously, this option was available for MATLAB, Java, and C/C++ programming languages, when you selected **File > Preferences > Editor/Debugger > Language**.

Note Do not confuse the **Block Indent** option with the **Smart indenting** option, which is still provided.

Compatibility Considerations

To attain the effect of block indenting, you can use the **No indent** option and indent lines manually using the **Tab** and **space** keys.

Integrated Text Editor Option Removed from Editor/Debugger Preferences Panel

The MATLAB Editor no longer supports EmacsLink. In previous releases, you could choose **File > Preferences > Editor/Debugger**, and then (if you correctly registered EmacsLink with MATLAB) you could select **Integrated text editor**. This option is no longer available.

New Navigation Aids in File and Directory Comparisons Tool

The File and Directory Comparisons Tool now provides links to help you quickly navigate to the areas of differences. This is useful for large files that have too many lines to fit on the screen. At the top of the page is a link to the first difference. In addition, each set of differences has an up arrow that you click to go to the previous set of differences, and a down arrow you click to go to the next set of differences. For details, see [Stepping Through Differences](#).

Wrap Around Option for Find and Replace Now On By Default

When the **Find Next** operation for searching files in the Editor reaches the end of a file, it automatically wraps around to search from the beginning of the file for the text you specified. In previous releases, the **Wrap around** option was off by default. This meant that if you were in the middle of a file

and the text you were searching for appeared before your current position, **Find Next** would not find that text.

Because it is more convenient to have this option on, it is now selected by default. To access this option, select **Edit > Find and Replace**.

For more information, see Find and Replace Text in Files.

Tuning and Managing MATLAB Code Files

Profile Summary Report Includes Information on Excluded Profiling Overhead

The bottom of the Profile Summary Report now indicates the amount of time spent in profiling overhead, when possible. For details, see Profile Summary Report.

Publishing MATLAB Code Files

New features and changes introduced in Version 7.8 (R2009a) are:

- “New Options for Capturing Figures in Published Documents” on page 459
- “Dynamic Links in Published Documents” on page 459

New Options for Capturing Figures in Published Documents

Two new options are available to specify how you want figures captured for published documents: `entireGUIWindow` and `entireFigureWindow`. The `entireGUIWindow` option is appropriate for most publishing purposes and is now the default. The `entireFigureWindow` option is appropriate when you want to capture all the details, including the title bar and other window decorations in your published document. Use this option, for example, if you are creating a tutorial on using MATLAB software. In the GUI, you can select these options from the **Figure capture method** setting in the Edit M-file Configuration dialog box. In the `publish` function, you can specify these options with `figureSnapMethod`.

For more information, see [Figure capture method](#) and the [publish](#) reference page.

Dynamic Links in Published Documents

When you publish a document to HTML, you can include dynamic links. Dynamic links are links to files on the MATLAB path. They are called dynamic links because MATLAB evaluates them when the reader of your document clicks on one. To use a dynamic link, the reader must open the HTML file in the MATLAB Web browser.

For more information, see [Dynamic Hyperlinks](#).

Mathematics

Upgrade to Computational Geometry

MATLAB includes a new object-oriented suite of computational geometry tools, together with a new underlying library called CGAL. The new library provides improved robustness, performance, and memory efficiency. The new tools are presented in three classes:

- New class `TriRep` provides topological and geometric queries for triangulations in 2-D and 3-D space.
- New class `DelaunayTri` provides increased functionality for Delaunay triangulation including topological and geometric queries, incremental modification, and edge constraints.
- New class `TriScatteredInterp` provides fast robust scattered data interpolation and a new natural-neighbor interpolation technique.

Incomplete Inverse Gamma Function `gammaincinv` and Incomplete Inverse Beta Function `betaincinv`

MATLAB has new functions for incomplete inverse gamma and incomplete inverse beta functions. These functions, `gammaincinv` and `betaincinv`, provide the Statistics Toolbox functionality of the inverse incomplete gamma and beta functions to MATLAB.

Krylov Subspace Methods `bicgstabl` and `tfqmr`

MATLAB has new iterative methods for solving systems of linear equations. `bicgstabl` provides the stabilized biconjugate gradients method. `tfqmr` provides a transpose-free implementation of the quasi-minimal residual method.

New Function quad2d

The `quad2d` function provides additional quadrature functionality for nonrectangular areas of integration.

Changes To conv

The conv function now accepts the shape parameter as input.

Changes To conv2 and convn

Compatibility Considerations: Yes

Use of the conv2 and convn functions with one empty input now returns the matrix of the correct size as described by the shape input.

Compatibility Considerations

Use of the conv2 and convn functions with one empty input no longer returns an empty matrix. Instead, it returns the matrix of size specified by the shape input. For information on how to use the shape input, see the reference pages for the conv and conv2 functions.

nextpow2 Changing to Element-By-Element Calculation in a Future Release

Compatibility Considerations: Yes

Compatibility Considerations

nextpow2 with a nonscalar produces a warning:

Warning: NEXTPOW2(X) where X is non-scalar will change behavior in future versions: it will operate on each element of X. To retain current behavior, use NEXTPOW2(LENGTH(X)) instead.

This behavior will change in a future release. Replace instances of nextpow2 with nonscalar input X to nextpow2(length(X)) to maintain the current behavior.

Function `finite` Being Removed

Compatibility Considerations: Yes

The `finite` function is obsolete. Use of the `finite` function now causes an error in MATLAB.

Compatibility Considerations

Replace all instances of `finite` with `isfinite`.

New Multithreading Capability in MATLAB Functions

The MATLAB functions for Fourier transforms `fft`, `fft2`, and `fftn`, and their inverses `ifft`, `ifft2`, and `ifftn` are now multithreaded. In addition, the MATLAB functions `prod`, `sum`, `max`, and `min` are multithreaded.

64-bit Support in LAPACK and BLAS

Compatibility Considerations: Yes

MATLAB supports 64-bit integers for matrix dimensions in LAPACK, and BLAS. Linear algebra operations can now handle matrices of dimensions greater than $2^{31} - 1$.

Compatibility Considerations

MEX files that call BLAS or LAPACK need to be updated. All integer variables passed into BLAS or LAPACK need to be of type `mwSignedIndex`. MEX files compiled in previous versions of MATLAB that call BLAS or LAPACK could lead to undefined behaviors. If you have existing code that generates MEX files that pass variables to BLAS or LAPACK you need to update the code to use the proper data types and recompile.

Upgrade to ACML 4.1.0

AMD Core Math Library (ACML) is upgraded to version 4.1.0.

Data Analysis

Programming Fundamentals

Setting the Number of Threads Removed from Preferences Panel

Compatibility Considerations: Yes

The capability to adjust the number of computational threads in a single MATLAB session is no longer available as of this release. This change removes from the MATLAB preferences panel the ability to set the maximum number of computational threads. The primary reason for this change is that products that MATLAB is dependent upon have the ability to spawn threads from the currently-executing thread. This makes it infeasible to monitor and/or limit the number of computational threads at any given time in a MATLAB process.

MATLAB versions 7.8 and later require that you decide between threading and no threading at the time you launch your MATLAB session. Multithreading is enabled by default. To disable this feature, start MATLAB using the new `singleCompThread` option.

Compatibility Considerations

If you currently use the preferences panel to enable or disable multithreading or to adjust the number of computational threads, you need to be aware that this capability is no longer available. See the Startup Options section in the Desktop Tools and Development Environment documentation to find out how to enable or disable multithreading when launching a new MATLAB session.

Timer Objects Saved in New Format

Compatibility Considerations: Yes

The format in which MATLAB saves Timer objects has changed in MATLAB version 7.8. Any Timer objects that you create and save while running MATLAB 7.8 cannot be loaded into an earlier version of MATLAB.

Compatibility Considerations

If you need to use a Timer object that you have constructed using MATLAB 7.8, you will have to reconstruct and save the object in an earlier version of MATLAB.

mmreader Supports Linux Platforms

The `mmreader` object now supports Linux platforms. For more information about using `mmreader`, see the `mmreader` reference page.

Support of Microsoft Excel 2007 File Formats

If you have installed Excel 2007 (or Excel 2003 with the Compatibility Pack) on your Windows system, the `xlswrite` function exports data to XLSX, XLSB, and XLSM formats.

To write data to an Excel file, specify the name and extension of the output file in the call to `xlswrite`. If the file already exists, `xlswrite` writes data in the existent file format. If the file does not exist, `xlswrite` creates a new file, using the format that corresponds to the file extension you specify. If you do not specify a file extension, `xlswrite` applies the XLS extension, and writes a new file in the XLS format.

The `xlsread` function imports any file format recognized by your version of Excel, including XLS, XLSX, XLSB, XLSM, and HTML-based formats. The `importdata` function imports XLS, XLSX, XLSB, and XLSM formats. The Import Wizard imports XLS and XLSX formats.

Note Large files in XLSX format might load very slowly. For better import and export performance, Microsoft recommends that you use the XLSB format.

Anonymous Functions Support `str2func`

The `str2func` which, prior to this release, converted a function name to a function handle, now also converts an anonymous function definition to a function handle. See the function reference page for `str2func` for more information.

```
N = 5;   NthPower = str2func(['@(x)x.^', num2str(N)]);  
NthPower(8)  
ans =  
    32768
```

size and range Implemented for validateattributes

The `validateattributes` function now enables you to check the size and range of the input value. The following commands validate the size and range of the values of `x` and `y` respectively:

```
x = rand(4,2,6);  
y = uint8(50:10:200);  
  
validateattributes(x, {'numeric'}, {'size', [4,2,6]});  
validateattributes(y, {'uint8'}, {'>=' , 50, '<=' , 200})
```

isempty Supported for Map Objects

MATLAB now supports the `isempty` function for `containers.Map` objects. This example creates a 0-by-1 Map object and runs `isempty` on it:

```
mapObj = containers.Map;  
size(mapObj)  
ans =  
     0     1  
  
isempty(mapObj)  
ans =  
     1
```


Bug Fix for Misinterpreted Variables

The example below describes a bug in the MATLAB software that has been fixed in version 7.8. The bug was caused by misinterpretation of an unassigned variable. For certain names, MATLAB mistakenly interpreted the variable as a stem in dot indexing.

The following example illustrates the problem. The example is a bit artificial (which is why the bug went undiscovered for so long).

Suppose you have a function that is intended to perform two levels of dot-indexing:

```
function y = dotindextwice_A(j)
    y = j.lang.String;
```

Calling this function with no arguments results in an error in all versions of MATLAB, as it should.

Now modify the function slightly so that the input variable is named `java` and run it on a version of MATLAB prior to Version 7.8:

```
function y = dotindextwice_B(java)
y = java.lang.String;
```

Now when you run the function without arguments, MATLAB misinterprets the word `java`, treating it as if it were the stem of a Java class name:

```
x = dotindextwice_B;    % Deliberately called with no arguments
```

Prior to Version 7.8, this function did not throw an error. In fact, it returned an instance of the `java.lang.String` class:

```
class(x)
ans =
    java.lang.String
```

This violates the rule that variables in functions are supposed to hide all other uses of the name. Beginning in Version 7.8, calling function `dotindextwice_B` without arguments results in an error, just as calling `dotindextwice_A` does.

MATLAB Upgrades Support for HDF5 to Version 1.8.1

Compatibility Considerations: Yes

The R2009a release of MATLAB uses version 1.8.1 of the HDF5 library. The HDF Group has deprecated two of the HDF5 library functions, `H5Pget_cache` and `H5Pset_cache`. Their M-file counterparts, `H5P.get_config` and `H5P.set_config`, may not work as they did in prior releases of MATLAB. To replace these deprecated functions in your code, consider these four new HDF5 functions: `H5P.get_mdc_config`, `H5P.set_mdc_config`, `H5F.get_mdc_config`, and `H5F.set_mdc_config`.

Compatibility Considerations

If your code uses `H5P.get_cache` or `H5P.set_cache`, your program will produce a warning message.

Indirect Calls to Superclass Constructors Now Errors

Compatibility Considerations: Yes

You can no longer call an indirect superclass constructor from a subclass constructor. For example, suppose class B is derived from class A, and class C is derived from class B. The constructor for class C should not call the constructor for class A to initialize properties. The call to initialize class A properties should be made from class B.

Compatibility Considerations

If you define classes in which subclass constructors call indirect superclass constructors, MATLAB now issues an error when you attempt to create an instance of the subclass. Call `Only Direct Superclass from Constructor` for information on how to correctly code subclass constructors.

Graphics and 3-D Visualization

Functions Previously Only Available in the Image Processing Toolbox Now Available in MATLAB

Compatibility Considerations: Yes

The following functions have been added to MATLAB from the Image Processing Toolbox:

- `rgb2ind`: Convert RGB image to indexed image.
- `dither`: Convert image using dithering.
- `cmunique`: Eliminate unneeded colors in colormap of indexed image.
- `cmpermute`: Rearrange colors in colormap.
- `imapprox`: Approximate indexed image by one with fewer colors.

Compatibility Considerations

- The `dither` and `imapprox` functions no longer display their output as an image via a call to `imshow` when called with no output arguments. Instead, the first output argument appears in the Command Window if no semicolon ends the line.
- Function `rgb2ind` errors when called with syntax `rgb2ind(rgb)`.
- Function `imapprox` errors when called with syntax `imapprox(x,map)`.

Creating Graphical User Interfaces (GUIs)

New Programmatic GUI Doc Example

A new example in the documentation teaches you how to code a GUI that manages multiple lists, such as to-do and shopping lists, contact information, music or video catalogs, or any set of itemizations. Among other things, it illustrates how to write MATLAB code to:

- Share callbacks among uicontrols.
- Obtain component handles from their tags.
- Create a new version of an existing GUI.
- Import and export list data.
- Edit, add, delete, and reorder list items.
- Save a list in the GUI itself.
- Concurrently run multiple GUIs containing different data that call back to the same function.

This example does not use GUIDE. To read about and run it, see [A GUI That Manages List Data](#) in the documentation for [Creating Graphical User Interfaces](#).

GUIDE Help Menu Enhanced

The Help menu in GUIDE now links to more topics in the documentation than previously. It also links to a set of video tutorials on the MATLAB Central Web site. For details, see [Getting Help in GUIDE](#) in the [Opening GUIDE](#) section of the [Creating Graphical User Interfaces](#) documentation.

External Interfaces/API

New Interface to Microsoft .NET Framework

The interface to .NET allows you to bring .NET assemblies into the MATLAB environment, to construct objects from classes contained in the assemblies, and to call methods on these objects. For complete documentation of this feature, see [Using .NET Libraries from MATLAB](#). For an overview of the .NET interface, watch this [video demo](#).

Expanded Platform Support Added for MATLAB Serial Port

MATLAB Serial Port is now supported on the following platforms:

- Microsoft Windows 64-bit
- Apple Macintosh OS X
- Macintosh OS X 64-bit
- Linux
- Linux 64-bit
- Sun Solaris™ 64-bit

Changes To Compiler Support

Compatibility Considerations: Yes

New Compiler Support

MATLAB Version 7.8 (R2009a) supports these new compilers for building MEX-files:

Microsoft Windows (64- and 32-bit) Platforms

- Microsoft Visual Studio 2008 SP1

Linux (64- and 32-bit) Platforms

- gcc Version 4.2.3

Apple Macintosh (32-bit) Platforms

- GNU gfortran Version 4.2.2

Compiler Support To Be Phased Out

The following compilers are supported in Version 7.8 (R2009a), but will not be supported in a future version of MATLAB:

Windows (32-bit) Platforms

- Intel Visual Fortran Version 9.1
- Intel Visual Fortran Version 10.1
- Intel C/C++ Version 9.1
- Microsoft Visual Studio .NET Version 7.1

Windows (64-bit) Platforms

- Intel Visual Fortran Version 9.1

- Intel Visual Fortran Version 10.1
- Intel C/C++ Version 9.1

Solaris SPARC (64-bit) Platforms

- Sun Studio 11 cc / CC Version 5.8
- Sun Studio 11 f90 Version 8.2

Discontinued Compiler Support

MATLAB no longer supports the following compilers:

Windows (32-bit) Platforms

- Open Watcom Version 1.3
- Microsoft Visual Studio 2005 Express Edition

Windows (64-bit) Platforms

- Microsoft Platform SDK

Apple Macintosh (32-bit) Platforms

- g95 Version 0.90

Compatibility Considerations

To ensure continued support for building your C/C++ programs, consider upgrading to another supported compiler. For an up-to-date list of supported compilers, see the Supported and Compatible Compilers Web page.

Do Not Use `mxFree` to Destroy `mxArrays`

Compatibility Considerations: Yes

It is improper to call `mxFree` on an `mxArray`. Previously, to remedy misleading statements in older documentation, under limited circumstances, MATLAB issued a warning in code that made this error. MATLAB no longer issues the warning.

Compatibility Considerations

The correct function to use to release memory for an `mxArray` is `mxDestroyArray`. Calling `mxFree` on an `mxArray` could cause memory corruption, which might result in a segmentation violation.

Cannot Build MEX-Files Using MATLAB Version 5 API

Compatibility Considerations: Yes

MATLAB does not support the `-V5` option to the `mex` function.

Compatibility Considerations

You are no longer able to build a MEX-file using the MATLAB Version 5 API. If you use any of the functions shown in the “Obsolete Functions: MX Array Manipulation” on page 962 table, you must replace them with functions from the Replacement column, if available. These obsolete functions were deprecated when MATLAB Version 6 was released over 5 years ago.

MEX-Files Calling BLAS or LAPACK Functions Must Be Updated On 64-Bit Platforms

Compatibility Considerations: Yes

You must update any MEX-file that calls functions in the BLAS or LAPACK math packages on 64-bit platforms. The change occurs as a result of updated support, described in “64-bit Support in LAPACK and BLAS” on page 470. Existing MEX-files generated in previous versions of MATLAB will result in undefined behavior (likely crashes), if run in R2009a. The previous versions pass 32-bit integer arguments, but the math routines now read and write to 64 bits of memory. The results you see depend on what is stored in the subsequent 32 bits of memory.

Compatibility Considerations

On 64-bit platforms, you must use 64-bit integers for all input and output variables when calling LAPACK and BLAS routines in C and Fortran source MEX-files. Use the `mwSignedIndex` type for platform-independent code.

Object .o Files Saved on Macintosh Systems for Debugging

MATLAB saves object .o files when compiling MEX-files on Apple Mac OS Version 10.5 systems so that you can use source-level debugging.

Run-Time Libraries Required for Applications Built with Microsoft Visual Studio 2008 Compiler

If you distribute a MEX-file, an engine application, or a MAT-file application built with the Visual Studio 2008 compiler, you must provide the Visual C++ run-time libraries. These files are required to run applications developed with Visual C++ on a computer that does not have Visual C++ 2008 installed. For information on locating the Microsoft Visual C++ 2008 Redistributable Package (x86), containing `vcredist_x86.exe` and `vcredist_x64.exe`, consult your Microsoft documentation.

New Features for Shared Library Interface

- It is now possible to use the `char**` return value and to increment the resulting pointer to retrieve all values. See [Passing an Array of Strings](#).
- Added support for accessing values exported by a library.
- All fully and partly sized arrays should now work.

New Java Thread Safety Functions

Use the following new functions to work with Sun Java objects on the Event Dispatch Thread (EDT).

Function	Description
javaObjectEDT	Construct Java object on EDT
javaMethodEDT	Call Java method from EDT

Improved Robustness of Web Services Functions

Compatibility Considerations: Yes

The underlying technology used in the `createClassFromWsd1` and `parseSoapResponse` functions was modified to better ensure support for WSDL and SOAP standards.

Compatibility Considerations

There was no intended change to functionality or results of the `createClassFromWsd1` and `parseSoapResponse` functions, which MathWorks verified through testing. There are many variations among WSDL files and Web services and they cannot all be tested. Therefore, it is possible that your results using the `createClassFromWsd1` and `parseSoapResponse` functions in this version could differ from a previous version.

Ensure that your results using `createClassFromWsd1` and `parseSoapResponse` functions are as expected.

R2008b

Version: 7.7
New Features: Yes
Bug Fixes: Yes

Desktop Tools and Development Environment

Desktop New Features Video

For an overview of the major new features in the MATLAB Desktop Tools and Development Environment area, watch this video demo. Another way to access this and other video demos is to select the **Demos** tab in the Help browser, and then select **MATLAB > New Features in Version 7.7**.

Startup and Shutdown

New features and changes introduced in Version 7.7 (R2008b) are:

- “Macintosh Startup and Root Directory Enhancements and Changes” on page 506
- “Updated Version of JVM Software” on page 508
- “Specifying Address Space Protection During Startup on Windows Platforms” on page 508
- “Changes to -nojvm Startup Option” on page 508
- “Changes to matlab Memory Manager Startup Options” on page 509

Macintosh Startup and Root Directory Enhancements and Changes

MATLAB for Apple Macintosh platforms is now installed like many other applications for Macintosh platforms, as a Macintosh .app bundle. This has resulted in some enhancements and changes to starting and using MATLAB on Macintosh platforms.

Startup Location

To start MATLAB on the Macintosh platform, double-click the MATLAB_R2008b icon in the Applications folder. This differs from R2008a (V7.6), where you started MATLAB by double-clicking the MATLAB 7.6 icon in the Applications/MATLAB_R2008a folder; there was an additional folder level in R2008a.

Starting MATLAB from a File

You can now start MATLAB by double-clicking a file with a file extension that has been associated with MATLAB, such as a file with a .m extension. Similarly, you can drag a file onto the MATLAB_R2008b icon in the Applications folder or in the dock. These actions start MATLAB and open the file.

Contents of MATLAB Root Directory

When you use file browser GUIs to navigate in the MATLAB root directory, `/Applications/MATLAB_R2008b`, (known as the *matlabroot* directory), you cannot directly view or access its contents. For example, when you select **File > Open** and navigate to `Applications/MATLAB_R2008b`, no contents display. To access the contents, press **Command+Shift+G**, and enter the path to the MATLAB root directory in the resulting Go To Folder dialog box, for example, `/Applications/MATLAB_R2008b.app`.

Similarly, when you select `MATLAB_R2008b` in the Applications folder using the Finder, you do not see the contents. To access the contents, right-click (or **Ctrl+click**) `MATLAB_R2008b`, and from the context menu, select **Show Package Contents**. For more information, see Navigating Within the MATLAB Root Folder on Macintosh Platforms.

Startup Options and the Start MATLAB Settings Dialog Box

You can no longer set startup options using the Start MATLAB Settings dialog box and you can no longer start MATLAB from any `.smat` files you saved using Start MATLAB Settings. The dialog box is now used only for diagnostics and only appears if MATLAB experiences a problem during startup.

To set the startup directory in MATLAB, use the `userpath` function. To instruct MATLAB to run a specified statement upon startup, start MATLAB using the `matlab` command from a shell, as you would to start MATLAB on any UNIX platform. For more information, see Startup Options.

Starting MATLAB in a Shell

In R2008b (V7.7), to start MATLAB from a shell, enter the path to the executable, `/Applications/MATLAB_R2008b.app/bin/matlab`. This differs from R2008a (V7.6), in which the path was `/Applications/MATLAB_R2008a/bin/matlab`.

Compatibility Considerations

The compatibility considerations are described along with the above changes.

Updated Version of JVM Software

MATLAB is now using Sun Microsystems™ JVM™ Version 6 Update 4 software on all platforms, except the Apple Macintosh platform. If you specify a version of Java software to use with MATLAB, this change might impact your work.

Specifying Address Space Protection During Startup on Windows Platforms

When you start MATLAB on Microsoft Windows 32-bit platforms, you can set a startup option to help ensure the largest available contiguous block of memory after startup, which is useful if you run memory-intensive operations, such as processing large data sets. You can use the new `-shield` startup option to specify different levels of protection of the address space during the MATLAB startup process. This can also help resolve problems if MATLAB fails to start. For more information, see the `matlab` (Windows) reference page.

Changes to `-nojvm` Startup Option

When you start MATLAB with the `-nojvm` startup option, Handle Graphics functionality will no longer be supported. (The `-nojvm` option is available for UNIX platforms; see background information at the `matlab` (UNIX) reference page.)

Some aspects of MATLAB and related products use Handle Graphics in a way that might not be obvious. This includes anything that is based on or works using figures in MATLAB. Here is a summary of the affected features:

- Creating figures and performing plotting tasks, such as using the `plot`, `axes`, `getframe`, and `gcf` functions.
- Printing figures and using related functions such as `print`, `hgexport`, and `saveas`.
- Creating GUIs in MATLAB using GUI-building functions such as `warndlg`.
- Using Simulink scopes and printing Simulink models.

In MATLAB Version 7.7 (R2008b), if you use the `-nojvm` startup option and use Handle Graphics functionality, MATLAB produces this warning:

This functionality is no longer supported under the `-nojvm` startup option.

In a future release, instead of a warning, MATLAB will produce an error when you start with the `-nojvm` option and use Handle Graphics functionality.

Compatibility Considerations

To avoid the warning, start MATLAB without the `-nojvm` startup option:

- If you have been using the `-nojvm` startup option to work in a command line environment or because you do not use the MATLAB desktop, use the `-nodesktop` startup option instead.
- If you have been using the `-nojvm` startup option because of memory or performance benefits, look for other ways to gain those improvements when you start MATLAB without the `-nojvm` option. See the Performance and Memory Usage topics in the MATLAB Programming Fundamentals documentation.
- If you want to continue to use the `-nojvm` startup option, remove the code that is now producing the warnings.

Changes to matlab Memory Manager Startup Options

The `matlab` command line arguments `-memmgr` and `-check_malloc` are deprecated and will be removed in a future release. The environment variable `MATLAB_MEM_MGR` is also deprecated and will be removed. For information about these options, see `matlab` (Windows) or `matlab` (UNIX).

Compatibility Considerations

If you use these options, MATLAB generates a warning message.

Desktop

New features and changes introduced in Version 7.7 (R2008b) are:

- “New Default Layout for Desktop” on page 510
- “Closing Document Windows Using Middle Mouse Button” on page 510
- “Preferences Opens to Last Pane Used” on page 510
- “Changes to Desktop Text Font” on page 510
- “Provide Authentication Settings for Proxy Server when Accessing the Internet from MATLAB” on page 511

New Default Layout for Desktop

There is a new desktop layout when you select **Desktop > Desktop Layout > Default**. It includes the same components as the previous default desktop layout, however, they are arranged differently. If you prefer the previous default layout, arrange your desktop in that way and save the layout. You then can reuse the saved layout at any time.

Closing Document Windows Using Middle Mouse Button

If you have multiple documents open, you can now close a document by clicking the middle mouse button when the pointer is in the document's button on the document bar.

Preferences Opens to Last Pane Used

When you open the Preferences dialog box, it displays the last preference pane you viewed in the current session. In prior versions, the Preferences dialog box displayed the pane associated with the tool from which you accessed it.

Changes to Desktop Text Font

You now can specify that the desktop text font use the system default font. To do this, select **File > Preferences > Fonts**. Then, for **Desktop text font**, select **Use system font**. For more information, click the **Help** button in the Fonts Preferences dialog box.

The default settings for the desktop text font and the HTML Proportional Text font have changed. This only affects existing users who choose to use a new preferences file (`matlab.prf`) in R2008b.

Provide Authentication Settings for Proxy Server when Accessing the Internet from MATLAB


If you want to access the Internet from MATLAB and your network uses a firewall or another means of protection that restricts Internet access and requires you to provide a username and password, use the new proxy server authentication settings in Web preferences to specify the values. For more information, click the **Help** button in the Web preferences pane, or see Web Preferences.

Running Functions – Command Window and History

- “Find Function Names and Get Help Using the New Function Browser” on page 512
- “View Syntax Hints While Entering Statements” on page 513

Find Function Names and Get Help Using the New Function Browser

While you work, you can find the names of functions and get help for them using the new Function Browser. The Function Browser is useful if you want to find a function whose name you cannot remember, determine if there are functions that do what you want, or view the reference page for a function. The Function Browser uses a subset of the information found in the function reference pages in the Help browser for quick access while you work.


To access the Function Browser, press **Shift+F1**, or if you are in the Command Window or Editor, click the Function Browser button . The Function Browser opens. You can specify the products to look in, browse categories of functions, and search for words that appear in function reference pages. For more information, see Find Functions Using the Function Browser.

1. To open the Function Browser, click its button or press **Shift+F1**.

4. Select a function to view quick help for it in a pop-up window.

2. Find categories and functions whose help contains words you specify.

3. Click to change the scope of product documentation to look in.



5. To use a function, drag it from the Function Browser to a tool, such as the Command Window.


View Syntax Hints While Entering Statements

While you enter statements in the Command Window and Editor, you can view the allowable input argument syntax for a function in a pop-up window. This feature is called *function hints*. To use function hints:

- 1 Type the function name, followed by the left parenthesis, (, and pause. The syntax for input arguments automatically displays in a pop-up window near the statement you are entering.

- 2 The arguments you can enter appear in bold. Enter your first argument and type a comma (,) after it. The syntax options in the pop-up window then change, based on the argument you just entered.
- 3 Continue entering arguments, using the hints as needed. You can dismiss the function hints pop-up window at any time by pressing **Esc**. When you type the closing parenthesis,), or when there are no more arguments to enter, the pop-up window automatically closes.

The following illustration shows function hints for the `plot` function.



To turn off the function hints feature so the pop-up menu does *not* automatically display the syntax reminders when you type an opening parenthesis, use Keyboard preferences; for **Function Hints**, clear the check box that enables them.

For more information, see View Function Syntax Hints While Entering a Statement.

Help and Related Resources

- “New Help Features — Function Browser and Function Hints” on page 515
- “Viewing an HTML Version of Help for Classes You Create” on page 515
- “Finding Text In Small Help Windows” on page 517
- “Changes to Search Field in Help Browser” on page 517

New Help Features — Function Browser and Function Hints


There are two new features that provide help while you work:

- Use the new Function Browser to find function names while you work. It is most useful in the Command Window and Editor, but you can access it from any tool. For more information, see “Find Function Names and Get Help Using the New Function Browser” on page 512.
- Use function hints to help you complete syntax for statements in the Command Window or Editor. For more information, see “View Syntax Hints While Entering Statements” on page 513.

Viewing an HTML Version of Help for Classes You Create


If you create your own class definition files in MATLAB and you provide help in the `classdef` file for the class, properties, and methods, you can conveniently view the help in the Help browser by running `doc classname`. For more information, see Help for Classes You Create. The following example shows class information in the Help browser for the user-created class, `sads`, displayed by running

```
doc sads
```



Finding Text In Small Help Windows

The Find dialog box is now available from the small help windows used for the Help on Selection feature and for context-sensitive help. The find feature is useful when you want to search for a specific word or phrase within one of these help windows. To access the Find dialog box:

- In a window used for the Help on Selection feature, press **Ctrl+F** on Windows and UNIX platforms or **Cmd+F** on Macintosh platforms. You can also click the **Find text**  button
- In a context-sensitive help window, press **Ctrl+F** on Windows and UNIX platforms, and **Cmd+F** on Macintosh platforms

Changes to Search Field in Help Browser

You can quickly access the Product Filter from the search field by selecting the down arrow at the right side of the search field and from it, selecting **Filter by Product**. The Help pane of the Preferences dialog box opens. For more information about the product filter, click the **Help** button in the dialog box.

As you enter a term in the search field, a history of terms you previously entered in the current session appears. To view the full history, select the down arrow at the right side of the search field and from it, select **Show Search History**. You can select an item in the search history to rerun the search.

To execute a search, enter the search terms and press **Enter**. There is no longer a Go button.


Workspace, Search Path, and File Operations

New features and changes introduced in Version 7.7 (R2008b) are:

- “Current Directory Browser Enhanced, Including New Navigation and Grouping Features” on page 518
- “Structure Results of dir for Nonexistent Files Now Include Empty Matrices” on page 522
- “Workspace Browser Toolbar Is Now Configurable” on page 524
- “Semicolon (;) Path Separator Character Now Used on UNIX Platforms” on page 524

Current Directory Browser Enhanced, Including New Navigation and Grouping Features

The Current Directory browser includes new ways to navigate and to view the directory contents. There are also new ways to find files, including a new filter field.

- Use the new address bar to view the current directory and to view and navigate to subdirectories within the current directory path.
- Access common features from the Actions button  on the toolbar.
- Add and remove buttons from the toolbar by right-clicking the toolbar and selecting **Customize**.
- List only files whose names contain a specified string by using the new filter field. To show the filter field, use **File > Preferences > Current Directory**.
- In the **Details** pane at the bottom of the tool, view a list of elements in the selected file, such as subfunctions in a MATLAB program file. Double-click an element to open the file at the location of the element.
- For a MAT-file, drag selected variables from the **Details** pane to the Workspace browser to load them into MATLAB. Similarly, save workspace variables to a MAT-file by dragging them from the Workspace browser to the Current Directory browser.


- Group items in the current directory, that is, view related items together. From the Actions button, select **Group By** and select the attribute you want to group by.

Some of the major changes are highlighted in the following illustrations.


Type a string in the filter field to view only file names containing that string in the current directory. Use preferences to show the filter field.

Right-click the toolbar and select **Customize** to add and remove buttons.

View subdirectories and change the current directory using the address bar.



To group files by type, select **Group By** from the Actions button. Use the - or + button to hide or show files within a group. Here, files are grouped by type, and files for all types except those with a .m extension are hidden.



For more information, see [Managing Files in MATLAB](#).

Compatibility Considerations

The following aspects of using the Current Directory browser are different in Version 7.7 (R2008b) than in the previous version. Following is a table of what changed and the way to perform the same action in Version 7.7.

Change	What To Do Instead In Version 7.7 (R2008b)
The toolbar no longer includes the buttons it previously included.	<p>You can now specify which buttons to include on the toolbar. You can include the toolbar buttons included in previous versions, or use these alternatives:</p> <ul style="list-style-type: none"> • Go up one level button — Instead, select a directory one level up by using the address bar. • Find files button — Instead, select Find Files from the Actions button on the toolbar, or use Ctrl+F. • New folder button — Instead, select New Folder from the Actions button on the toolbar. • Directory reports — Instead, select Reports from the Actions button on the toolbar.
The string display of the full path for the current directory has been replaced by the address bar view.	You can still access the string display, which can be useful if you want to copy it or edit it directly. To access the string, click the blank area to the right of the last subdirectory in the address bar. To return to the address bar view, press the Escape key.
You do not select attributes (columns) to display using Current Directory Preferences (Browser display options).	Right-click any column header to select or clear the columns to display, such as file size. You can only do this on Microsoft Windows platforms.
The file description no longer appears in a column.	View the description for a selected file in the detail pane.

Change	What To Do Instead In Version 7.7 (R2008b)
The full help for a MATLAB program file no longer appears in the detail pane.	Press F1 to view the reference page for the selected file.
You do not elect to show details using Current Directory Preferences (Browser display options).	Use the arrow on the right side of the detail pane separator to show or hide the details.
The File Filter options, accessible from the context menu and the View menu, have been removed.	Use the new filter field (use Preferences for the Current Directory browser to show the filter field), or sort by file type (click the document icon header), or group by file type using the new grouping feature (available from the Actions button).
The View menu was removed.	Use the new filter field (previously described) to filter the view. For Directory Reports, select Reports from the Actions button on the toolbar.
When you look for items in the current directory by typing the initial letters in the name, a pop-up window no longer appears showing the letters that you typed.	As before, the first entry whose name begins with the letters you typed is selected. If you want to see what you type when finding items in the current directory, instead use the filter field.

Structure Results of dir for Nonexistent Files Now Include Empty Matrices

When you run `dir` with an output argument and the results include a nonexistent file or a file that `dir` cannot query for some other reason, `dir` now returns empty matrices for the `date`, `bytes`, and `datenum` fields. The most common occurrence is on UNIX platforms when `dir` queries a file that is a symbolic link and the symbolic link points to a nonexistent target. A nonexistent target is when a target has been moved, removed, or renamed.

For example, if `my_file` in `my_dir` is a symbolic link to another file that has been deleted, then running

```
r = dir('my_dir')
```

includes this result for `my_file`:

```
r(n) =  
  name: 'my_file'  
  date: ''  
  bytes: []  
  isdir: 0  
  datenum: []
```

where n is the index for `my_file`, found by searching `r` by the `name` field.

With empty matrices returned, code you write to use the results of `dir` can be simpler and more robust. For more information, see the reference page for the `dir` function.

Compatibility Considerations

In previous versions, `dir` returned inappropriate values for files that could not be queried:

```
r(n) =  
  name: 'my_file'  
  date: '18-Jan-2038 22:14:07'  
  bytes: 0  
  isdir: 0  
  datenum: 7.4438e+05
```

If you have existing files that rely on the results of `dir` for a file that could not be queried, your code might not produce the result it used to. If you write new code that depends on the new results for `dir` and run it in a previous version of MATLAB, it might not produce the results you expect. In either case, there will probably not be a warning or error.

Workspace Browser Toolbar Is Now Configurable

Rearrange, add, or remove buttons and other controls from the Workspace Browser toolbar using **File > Preferences > Toolbars**. Alternatively, right-click the toolbar and select **Customize** from the context menu. By default, the Print button is not on the toolbar.

For more information on customizing the toolbar, see [Toolbar Customization](#).

Semicolon (;) Path Separator Character Now Used on UNIX Platforms

On UNIX platforms, MATLAB now uses a semicolon (;) as the character that separates directories in the search path file, `pathdef.m`, which is the character used on Windows platforms. This is beneficial if you work with the contents of the `pathdef.m` file programmatically on both Windows and UNIX platforms. In versions prior to Version 7.7 (R2008b), MATLAB used the colon (:) character as the path separator on UNIX platforms.

Compatibility Considerations

MATLAB will continue to accept the colon (:) character as a valid path separator on UNIX platforms, so any existing code you have that relies on it will still work.

You will experience a problem if you have any directories that contain a semicolon in their name. You will need to rename the directories to include them on the search path.

Editing and Debugging MATLAB Code

New features and changes introduced in Version 7.7 (R2008b) are:

- “Create New Function and Class Files Using Templates” on page 525
- “View Syntax Hints, Find Function Names, and Get Quick Help” on page 525
- “Set Color and Width of Right-Hand Text Limit” on page 526
- “Set Cursor to First Nonwhite Character on Line” on page 526
- “Suppress a Specific M-Lint Message Throughout a File” on page 526
- “New M-Lint Message for Suppressed Messages” on page 526
- “View M-Lint Message in ToolTip Using the Keyboard” on page 527
- “Apply M-Lint Autofix Using the Keyboard” on page 527
- “Code Fold Single Program, Multiple Data (spmd) Blocks” on page 527
- “File and Directory Comparisons Tool: Highlight Changes” on page 527
- “Block Indenting Will Not Be Included in Next Version” on page 528
- “Accessing Contents of MATLAB Root Directory on Macintosh Platforms” on page 528

Create New Function and Class Files Using Templates

When you create new functions and class definition files (`classdef`), you can start with a template that reminds you to include standard information. Select **File > New > Function M-File**, or **File > New > Class M-File**. A new file containing template information opens in the Editor.

View Syntax Hints, Find Function Names, and Get Quick Help

While you enter statements in the Editor or Command Window, you can display the syntax for a function in a temporary pop-up window. For more information, see “View Syntax Hints While Entering Statements” on page 513.

You also can find the names of and get help for functions using the new Function Browser—for more information, see “Find Function Names and Get Help Using the New Function Browser” on page 512.

Set Color and Width of Right-Hand Text Limit

In the Editor, where you can enable a vertical line to indicate a right-hand text limit, you now can set the width and color of the line. Note that the default color for the line is now gray, instead of light red.

Set preferences for the line by selecting **File > Preferences > Editor/Debugger > Display**, which opens the Preferences dialog box.

Click **Help** in the Preferences dialog box for more information.

Set Cursor to First Nonwhite Character on Line

When you press the **Home** key, the cursor goes to the first nonwhite character on the current line. When you press the **Home** key twice, the cursor goes to the beginning of the line.

Compatibility Considerations

In versions prior to Version 7.7 (R2008b), the **Home** key always moved the cursor to the first column of the current line.

Suppress a Specific M-Lint Message Throughout a File

You can now suppress a specific M-Lint message throughout a file by right-clicking on an M-Lint indicator that elicits the message, and then from the context menu, selecting **Suppress All Instances in this File**.

For details, see **Suppress All Instances of a Message in the Current File** in the MATLAB Desktop Tools and Development Environment documentation. For information on manually inserting the string that tells M-Lint to suppress the message throughout the file, see the documentation for the `mlint` function.

New M-Lint Message for Suppressed Messages

An M-Lint message now appears if you previously suppressed a message using the `%#ok` directive, and that message no longer appears. This can result if the message is already suppressed using preferences (**File > Preferences > M-Lint**), and the code has changed such that the

message is no longer generated, or if the rules M-Lint follows for generating the message have changed. The new message is:

An M-Lint message was suppressed here, but the message no longer appears. Use the context menu to fix.

For an example, see the *Suppressing All Messages on a Line with mlint* example in the `mlint` function documentation.

View M-Lint Message in ToolTip Using the Keyboard

To open an M-Lint Message ToolTip using the keyboard, place the cursor over the marked code and press **Ctrl + M**. This feature is offered in addition to the identical behavior available when you use the mouse pointer to hover over code that is marked by M-Lint. For an example of viewing an M-Lint message in a ToolTip, see Check Code for Errors and Warnings in the MATLAB Desktop Tools and Development Environment documentation.

Apply M-Lint Autofix Using the Keyboard

To fix a problem marked by M-Lint as having an automatic fix available, place the cursor over the marked code, and then press **Alt + Enter**. This feature is offered in addition to the identical behavior available when you use the context menu. For an example of using the M-Lint autofix feature, see Check Code for Errors and Warnings in the MATLAB Desktop Tools and Development Environment documentation.

Code Fold Single Program, Multiple Data (spmd) Blocks

By default, the Editor now supports code folding for single program, multiple data (spmd) blocks. For more information on code folding, see Code Folding — Expand and Collapse Code Constructs in the MATLAB Desktop Tools and Development Environment documentation.

File and Directory Comparisons Tool: Highlight Changes

The File and Directory Comparisons Tool now uses shades of colors to mark differences in the contents of two directories being compared. Light colors indicate files that differ and dark colors indicate subdirectories that differ. For details and an example, see Comparing Folders and Zip Files in the MATLAB Desktop Tools and Development Environment documentation.

Compatibility Considerations

In releases prior to Version 7.7 (R2008b), the same color intensity highlighted differences in both files and directories.

Block Indenting Will Not Be Included in Next Version

The **Block Indent** option will no longer be provided, starting in the next version of MATLAB. Currently, this option is available for M, Java, and C/C++ programming languages, when you select **File > Preferences > Editor/Debugger > Language**. To attain the effect of block indenting, you can use the **No indent** option and indent lines manually using the **Tab** and **space** keys.

If you have concerns about the pending removal of the **Block Indent** option, please e-mail Technical Support at support@mathworks.com.


Accessing Contents of MATLAB Root Directory on Macintosh Platforms

Starting in MATLAB 7.7 (R2008b), on Macintosh platforms, you cannot use file browser GUIs to directly access contents of the MATLAB root directory. For example, when you use **File > Open** from the Editor, you cannot directly select a file located within *matlabroot*. For more information, see “Contents of MATLAB Root Directory” on page 507.


Tuning and Managing MATLAB Code Files

Compatibility Considerations: Yes

Access Directory Reports

You now access Directory Reports by navigating to the directory containing the MATLAB program files for which you want to produce reports. Then, on the Current Directory browser toolbar, click the **Actions** down arrow  and select the type of report you want to run for all of the MATLAB program files in the current directory. Note that these reports are now referred to as Reports, rather than Directory Reports.

Compatibility Considerations

In versions prior to Version 7.7 (R2008b), you navigated to the directory containing the MATLAB program files for which you wanted to produce reports. Then, you clicked the **Directory Reports** down arrow  on the Current Directory browser toolbar.

Publishing MATLAB Code Files

Compatibility Considerations: Yes

New features and changes introduced in Version 7.7 (R2008b) are:

- “Include Figure Window Details in Published Documents” on page 530
- “Inline Math Supported in Published Documents” on page 530
- “Publish Setting: Cascading Style Sheet Is Now XSL File” on page 530


Include Figure Window Details in Published Documents

In versions prior to Version 7.7 (R2008b), when you published a file that included a figure window, only the graph or figure was included in the published document. Using the `figureSnapMethod` option, you can now specify that you want the window details included in the published document. For details, see the `publish` reference page.

Inline Math Supported in Published Documents

In versions prior to Version 7.7 (R2008b), you could publish LaTeX code in a published document as a code block, separate from the rest of your comments, if any. Now, you can publish LaTeX math symbols inline with the rest of your comments. For details, see [Inline LaTeX Math Equations](#).

Publish Setting: Cascading Style Sheet Is Now XSL File

In versions prior to Version 7.7 (R2008b), there was a **Cascading Style Sheet** setting on the Publish Configurations dialog box (which you access by clicking the Publish down-arrow button ). This setting is now called **XSL File**, to more accurately reflect the setting.

Compatibility Considerations

The **Cascading Style Sheet** setting on the Publish Configurations dialog box is now **XSL File**.

Mathematics

Upgrade to Random Number Generator

Compatibility Considerations: Yes

- The `randn` function uses a new longer period random number algorithm as its default.
- The new function `randi` returns random integers from a uniform discrete distribution.
- The `@RandStream` class allows you to construct a random number stream object and set its properties. For more information, see [Random Numbers](#) in the MATLAB Mathematics documentation.

Compatibility Considerations

The `randn` function now produces different results than in previous releases. Because the values returned by `randn` are intended to be random, this change should not affect most code.

`rand` and `randn` now draw from the same random number stream. In prior releases, `rand` and `randn` had separate independent underlying random number streams. Since `rand` and `randn` now access the same stream, using `randn` will affect subsequent values produced by `rand` and vice-versa. See [Creating and Controlling a Random Number Stream](#) in the MATLAB Mathematics documentation for more information.

Multipoint Boundary-Value Problems with `bvp5c`

The solver `bvp5c` will take multipoint boundary-value problems.

Upgrades to lsqnonneg

lsqnonneg now runs more efficiently. It accepts sparse matrices as inputs and maintains sparsity throughout its internal iterations.

Functions and Properties Being Removed

Compatibility Considerations: Yes

Function or Property Name	What Happens When You Use Function or Property?	Use This Instead	Compatibility Considerations
betacore	Fails	betainc	Replace all existing instances of betacore with betainc.
colmmd	Fails	colamd	Replace all existing instances of colmmd with colamd.
symmmd	Fails	symamd	Replace all existing instances of symmmd with symamd.
flops	Fails	None	Remove all instances of flops. With the incorporation of LAPACK in MATLAB Version 6, counting floating-point operations is no longer practical.

Upgrade to Intel Math Kernel Libraries

For Windows, Intel Mac, and Linux platforms, MATLAB software supports the Intel Math Kernel Library (MKL) version 10.0.3.

Data Analysis

Specialized Data Tips for the `hist` Function

Compatibility Considerations: Yes

When you create a histogram display using `hist` and place data tips in the plot in data cursor mode, they now snap to the top center of the bin you attach them to. The data tip contents have changed as well, and now consist of:

- Number of observations falling into the selected bin
- The x -value of the bin's center
- The lower and upper x -values for the bin

For details, see [Using Data Cursors with Histograms](#) in the MATLAB Graphics documentation.

Compatibility Considerations

Data tips for histograms no longer display the x and y coordinates of their locations and no longer snap to the four corners of the bins, as they do for `bar` plots. The data tips are also larger, to accommodate the extra information.

Programming Fundamentals

Fast Key Lookup Provided with New Map Data Structure

This release introduces a new MATLAB class called a *Map*. An object of the *Map* class is an array of any MATLAB data type that supports lookup table functionality. Unlike most arrays in MATLAB that only allow access to the elements by means of integer indices, indices for *Map* containers can be nearly any scalar numeric value or a character string.

The following example creates a *Map* object that is an array of strings. It is very much like any other string array except that with each *value* of this array there is also a lookup *key* associated with it. This particular *Map* contains the names of capital cities in the United States. These are the values of the *Map* object. Associated with each capital city value is the US state that it resides in. These are the keys of the *Map* object. You look up values in the *Map* using key indices. Call the `containers.Map` constructor to create an array of six capital cities indexed by six US states. (The capital of Alaska has purposely been entered incorrectly):

```
US_Capitals = containers.Map( ...
{'Arizona', 'Nebraska', 'Nevada', ...      % 6 States
 'New York', 'Georgia', 'Alaska'}, ...
{'Phoenix', 'Lincoln', 'Carson City', ...  % 6 Capitals
 'Albany', 'Atlanta', 'Fairbanks'});
```

Show the capitals of three of the states by looking them up in the *Map* using the string indices 'Nevada', 'Alaska' and 'Georgia':

```
values(US_Capitals, {'Nevada', 'Alaska', 'Georgia'})
ans =
    'Carson City'    'Fairbanks'    'Atlanta'
```

Correct the capital city of Alaska by overwriting the entry at string index 'Alaska':

```
US_Capitals('Alaska') = 'Juneau';

US_Capitals('Alaska')
ans =
    Juneau
```

The term `containers.Map` refers to a `Map` class that is part of a MATLAB package called `containers`. For more information, see `Map Containers` in the `Programming Fundamentals` documentation.

Tic and Toc Support Multiple Consecutive Timings

The `tic` and `toc` timing functions now support multiple consecutive timings. Call `tic` with an output `t0` to save the current time as the starting time for some operation. When the operation completes, call `toc` with the same `t0` as its input and MATLAB displays the time between that particular `tic` and `toc`.

In the following example, MATLAB measures the time used by each function call and, at the same time, measures the time required for the overall operation:

```
t0 = tic;
    t1 = tic;   W = myfun1(A,B);           toc(t1)
    t2 = tic;   [X,Y] = myfun2(C,W);      toc(t2)
    t3 = tic;   Z = myfun3(A,C,Y);        toc(t3)
toc(t0)
```

You can still call `tic` and `toc` without any arguments. In this case, `toc` just measures the time since the most recent `tic`.

See the function reference page for `tic` or `toc` for more information.

New Options for MException getReport

The MException `getReport` method has several new options available in this release. You select these options when you call `getReport`. They give you more control over the content and format of the information displayed or returned by `getReport`.

See the function reference page for `getReport` for more information.

what Function Returns Package Information

The `what` function now includes package information in its output display and a `package` field in the structure array that it returns.

List the packages used in the MathWorks Communications System Toolbox™:

```
s = what('comm');
```

```
s.packages
ans =
    'crc'
    'commdevice'
    'commsrc'
    'commgui'
    'commscope'
    'commutils'
```

You can also call `what` on a specific package name to see what types of directories and files are in the package directory.

See the function reference page for `what` for more information.

addtodate Accepts Hours, Minutes, Seconds, Milliseconds

In previous releases, the `addtodate` function supported modifying a date number by a specified number of years, months, or days. In this release, you can also modify the date by a specified number of hours, minutes, seconds, or milliseconds.

Add 2 hours, 45 minutes, and 17 seconds to the current time:

```
d1 = now;
datestr(d1)
ans =
    12-Jun-2008 16:15:38

d2 = addtodate(d1, 2, 'hour');
d2 = addtodate(d2, 45, 'minute');
d2 = addtodate(d2, 17, 'second');
d2 = addtodate(d2, 3000, 'millisecond');

datestr(d2)
ans =
    12-Jun-2008 19:00:58
```

See the function reference page for `addtodate` for more information.

Querying Options Added to pause

There are new syntaxes for the pause function:

- To see whether pausing is enabled or not, use one of the following commands:

```
pause query  
state = pause('query')
```

- To return the previous pause state when enabling or disabling pausing, use one of the following:

```
oldstate = pause('on')  
oldstate = pause('off')
```

See the function reference page for `pause` for more information.

File Selection Restriction in Import Wizard


Compatibility Considerations: Yes

This release introduces a change in how you select the source to import using the Import Wizard. In previous releases, you could select and view the contents of any number of files within the wizard before choosing the one to import. As of this release, if you need to import from a different source (a specific file or the system clipboard) than the one you had originally selected, you must exit and restart the Import Wizard. This change gives the Import Wizard increased flexibility in handling different types of files, removes redundancy in the import process, and also removes a potential source of unexpected behavior from the product.

Compatibility Considerations

The user interface to the Import Wizard is very much the same as in previous versions of MATLAB. However, you should take note of the following changes:

- The panel named **Select Data Source**, that appears at the top of the Import Wizard preview dialog box in earlier releases, is no longer available. As before, you select the source file to import, or the clipboard, at the time you activate the Import Wizard. This applies whether you use **File > Import Data** from the MATLAB Command Window menu or the `uiimport` function at the command prompt. To make a new file or clipboard selection, click the **Cancel** button in any of the dialog boxes, and then restart the Wizard.
- Calling `uiimport` without a file name displays the following new dialog box. Choosing **File** opens the **Import Data** dialog box. Selecting **Clipboard** opens the wizard with the contents of the clipboard in the preview panel.



- To import from the clipboard using the MATLAB menus, use **Edit > Paste to Workspace** instead of using **File > Import Data** , and then change the source to **Clipboard**. This method is preferred because it is more direct. The capability of switching from file to clipboard within the wizard is no longer supported.

Function Handle Array Warning Is Now An Error

Compatibility Considerations: Yes

The only way to make an array of function handles is to use a cell array. Attempting to create any other type of array of function handles is invalid. For the past several releases, MATLAB has issued a warning if you should attempt to put function handles into any type of array other than a cell array. As of this release, MATLAB throws an error instead of a warning when this is attempted.

Replace

```
A = [@sin @cos @tan];  
??? Error using ==> horzcat  
Nonscalar arrays of function handles are not allowed; use cell arrays instead
```

with

```
A = {@sin @cos @tan};
```

Compatibility Considerations

If any of your program code attempts to create a regular array of function handles, this code will now generate an error.

Two Types of issorted Warnings Are Now Errors

Compatibility Considerations: Yes

In previous versions, the `issorted` function generated a warning for the following two cases:

- `issorted(x)`, where `x` is a complex integer, and
- `issorted(x, 'rows')`, where `x` is an ND array

Using `issorted` on a Complex Integer

In this case, a statement such as the following

```
issorted(int8(complex(1,2)))
```

now issues the error message

```
??? Error using ==> issorted
ISSORTED on complex inputs with integer class is obsolete.
Please use ISSORTED(DOUBLE(X)) or ISSORTED(SINGLE(X)) instead.
```

Using `issorted` on an N-D Array

In this case, a statement such as

```
issorted(ones(3,3,3), 'rows')
```

now issues the error message

```
??? Error using ==> issorted
X must be a 2-D matrix.
```

Compatibility Considerations

If any of your program code attempts to use either of these types of statements, this code will now generate an error.

Possible Conflict with New Keyword: SPMD

Compatibility Considerations: Yes

This release introduces a new keyword, `spmd`, that, although used solely by the Parallel Computing Toolbox (PCT), may cause conflicts with MATLAB users as well. See `spmd` Construct in the PCT release notes for more information on this keyword.

Compatibility Considerations

Because `spmd` is a new keyword, it will conflict with any user-defined functions or variables of the same name. If you have any code with functions or variables named `spmd`, you must rename them.

Do Not Create MEX-Files with DLL File Extensions

In the future, on 32-bit Windows® systems, MATLAB will not support MEX-files with a .dll file extension. See release note “Do Not Use DLL File Extensions for MEX-Files” on page 569 for information on how this might affect you.

isequal Is Now Called Explicitly for Contained Objects

Compatibility Considerations: Yes

When you pass two MATLAB objects to `isequal`, MATLAB dispatches to the `isequal` method of the dominant object (see [Object Precedence in Expressions Using Operators](#)). If the dominant object does not overload `isequal`, then MATLAB uses the built-in version.

Compatibility Considerations

What is different with this release, is that MATLAB now calls `isequal` explicitly for each contained object. This means that, if any contained object overloads `isequal`, MATLAB calls the overloaded version for that object.

Previously, MATLAB compared contained objects using the built-in `isequal` functionality without regard to any special behavior programmed into overloaded `isequal` methods. The effect of this change is that, for objects that contain other objects and those contained objects overload `isequal`, the overloaded behavior establishes the basis with which MATLAB determines equality for those contained objects.

Indexed Assignment with Objects of the Form p(:) = o Now Consistent with MATLAB Language

Compatibility Considerations: Yes

The behavior of indexed assignment with MATLAB objects is consistent with the behavior of all MATLAB intrinsic types and V5 MATLAB objects. For example, attempting the following assignment, where `d` does not previously exist, gives an error:

```
>> d(:) = 5;  
??? In an assignment A(:) = B, the number of elements in A and B  
must be the same.
```

MATLAB objects behave in the same way:

```
ts_obj = timeseries;  
t(:) = ts_obj;  
??? In an assignment A(:) = B, the number of elements in A and B  
must be the same.
```

Compatibility Considerations

In MATLAB Version 7.6 Release 2008a, indexed assignment of the form `p(:) = object` did not result in an error.

fopen No Longer Supports VAXD, VAXG, and Cray Machine Formats

Compatibility Considerations: Yes

Calls to `fopen` with any of the following values for machine format return an error:

- 'vaxd' or 'd'
- 'vaxg' or 'g'
- 'cray' or 'c'

Compatibility Considerations

In previous releases, calls to `fopen` with machine format values associated with VAXD, VAXG, and Cray did not result in an error.

To read files in VAXD and VAXG formats, consider the workaround available on the MATLAB Central File Exchange, file ID #22675.

Graphics and 3-D Visualization

Certain Printer Formats and Drivers Now Warn When Used

Compatibility Considerations: Yes

Going forward, MathWorks is planning to leverage existing operating system (OS) support for printer drivers and devices. As a result, the ability to specify certain print devices using the `print -d` command, and certain graphics formats using the `print -d` command and/or the `saveas` command, will be removed in a future release.

Graphic Format Drivers		
-pkm	-pkmraw	-tiff1zw

Printer Driver	print Command Option String
Canon® BubbleJet BJ10e	-dbj10e
Canon BubbleJet BJ200 color	-dbj200
Canon Color BubbleJet BJC-70/BJC-600/BJC-4000	-dbjc600
Canon Color BubbleJet BJC-800	-dbjc800
Epson® and compatible 9- or 24-pin dot matrix print drivers	-depson
Epson and compatible 9-pin with interleaved lines (triple resolution)	-deps9high
Epson LQ-2550 and compatible; color (not supported on HP®-700)	-depsonc
Fujitsu® 3400/2400/1200	-depsonc
HP DesignJet 650C color (not supported on Windows OS)	-ddnj650c
HP DeskJet 500	-ddjet500
HP DeskJet 500C (creates black and white output)	-dcdjmono

Printer Driver	print Command Option String
HP DeskJet 500C (with 24 bit/pixel color and high-quality Floyd-Steinberg color dithering) (not supported on Windows OS)	-dcdjcolor
HP DeskJet 500C/540C color (not supported on Windows OS)	-dcdj500
HP Deskjet 550C color (not supported on Windows OS)	-dcdj550
HP DeskJet and DeskJet Plus	-ddeskjet
HP LaserJet	-dlaserjet
HP LaserJet+	-dljetplus
HP LaserJet IIP	-dljet2p
HP LaserJet III	-dljet3
HP LaserJet 4.5L and 5P	-dljet4
HP LaserJet 5 and 6	-dpxlmono
HP PaintJet color	-dpaintjet
HP PaintJet XL color	-dpjx1
HP PaintJet XL color	-dpjetx1
HP PaintJet XL300 color (not supported on Windows OS)	-dpjx1300
HP-GL® for HP 7475A and other compatible plotters. (Renderer cannot be set to Z-buffer.)	-dhpgl
IBM® 9-pin Proprinter	-dibmpro

Compatibility Considerations

The following Web site provides more detailed information on the file types that will issue warnings and how to suppress the warnings if desired, as well as a form to provide feedback to MathWorks about your use of these options:

http://www.mathworks.com/support/contact_us/dev/obsoleteprintdevices.html

Handle Graphics Not Supported Under -nojvm Startup Option

Compatibility Considerations: Yes

If you start MATLAB with `matlab -nojvm` (which disables Java) you will receive a warning when you attempt to create or load figures, open GUIs, print or capture figures using `getframe`.

Compatibility Considerations

For information, see “Changes to -nojvm Startup Option” on page 508 in the Desktop Tools and Development Environment release notes.

Creating Graphical User Interfaces (GUIs)

Undocumented Functions Removed

Compatibility Considerations: Yes

The following set of deprecated functions, all of which were previously undocumented, have been removed. Alternatives to most of them exist, which are described.

- `axlimdlg` — No alternative
- `cbedit` — No alternative
- `clruprop` — Use `rmappdata` instead
- `ctlpanel` — No alternative
- `edtext` — Set text object's `Editing` property
- `extent` — Get text object's `Extent` property
- `getuprop` — Use `getappdata` instead
- `hidegui` — Set figure's `HandleVisibility` property
- `hthelp` — Use `web` instead
- `layout` — No alternative
- `matq2ws` — Combine `save + load` or `uisave + uiload`
- `matqdlg` — Combine `save + load` or `uisave + uiload`
- `matqparse` — Combine `save + load` or `uisave + uiload`
- `matqueue` — Combine `save + load` or `uisave + uiload`
- `menubar` — The string 'none'
- `menuedit` — No alternative
- `pagedlg` — Use `pagesetupdlg` instead
- `setuprop` — Use `setappdata` instead
- `umtoggle` — Set `uimenu`'s `Checked` property
- `wizard` — Use `guide` instead
- `ws2matq` — Combine `save + load` or `uisave + uiload`

Compatibility Considerations

If you have developed MATLAB code that uses any of the above undocumented functions, you must remove such calls or replace them with other code, as suggested within the above bullets.

Handle Graphics Not Supported Under -nojvm Startup Option

If you start MATLAB with `matlab -nojvm` (which disables Java) you will receive a warning when you attempt to create or load figures, open GUIs, print, or capture figures using `getframe`. For more information, see “Changes to -nojvm Startup Option” on page 508 in the Desktop Tools and Development Environment release notes.

New Menu Options to Hide or Show GUIDE Toolbar and Status Bar

Compatibility Considerations: Yes

Two new menu options in GUIDE let you hide/show the GUIDE toolbar and status bar. By default both are visible, but you can deselect **Show Toolbar**, **Show Status Bar**, or both from the **View** menu to make the layout area larger.

Compatibility Considerations

The GUIDE Preferences option **Show Toolbar** is no longer available. Use **Show Toolbar** from the GUIDE **View** menu instead.

GUIDE Status Bar Now Shows Tag Property of Selected Object

The GUIDE Layout Editor now shows the Tag property of any object you select, in the left corner of the status bar that runs along its bottom. This display saves you from having to open the Property Inspector to read Tag names. Information in the status bar is read-only; you still need to use the Property Inspector to change a component's Tag.

Four New Major GUI Examples

The Creating Graphical User Interface documentation has four new extensive examples of building GUIs with GUIDE and programmatically. All of them feature uitable, a feature introduced in R2008a, and all the GUIs plot data. The new examples are:

- A Working GUI with Many Components (GUIDE)
- GUI for Animating a 3-D View (GUIDE) (GUIDE)
- GUI to Interactively Explore Data in a Table (GUIDE) (GUIDE)
- GUI that Displays and Graphs Tabular Data (programmatic)

This release includes FIG- and code files for all these examples. The documentation discusses many of their callbacks and includes hyperlinks to code in the code files.

External Interfaces/API

Do Not Use DLL File Extensions for MEX-Files

Compatibility Considerations: Yes

In the future, on 32-bit Microsoft Windows systems, MATLAB will not support MEX-files with a `.dll` file extension. In MATLAB Version 7.7 (R2008b), if you run a MEX-file with a `.dll` file extension, MATLAB displays a warning.

Additionally, if you use the `mex` function with the `-output` switch to create a MEX-file with a `.dll` extension, MATLAB displays a warning. If you use the `-output` switch to name a MEX-file, you do not need to provide a file extension. MATLAB automatically appends the appropriate extension. For example, the following command creates a MEX-file named `newtest.mexw32`:

```
mex mytest.c -output newtest
```

Compatibility Considerations

You must recompile MEX-files with a `.mexw32` file extension. This is the default of the `mex` command.

MEX-Files Must Be Recompiled When -largeArrayDims Becomes Default MEX Option

Compatibility Considerations: Yes

In a future version of MATLAB, the default mex command will change to use the large-array-handling API. This means the `-largeArrayDims` option will be the default. For information about migrating your MEX-files to use the large-array-handling API, see the Technical Support solution 1-5C27B9.

Compatibility Considerations

In the near future you will be required to update your code to use the new API and to recompile your MEX-files. You should review your source MEX-files and mex build scripts.

New Compiler Support

MATLAB Version 7.7 (R2008b) supports these new compilers for building MEX-files:

Microsoft Windows 64-bit and 32-bit Platforms

- Microsoft Visual Studio 2008 Express Edition

Compiler Support to Be Phased Out

The following compilers are supported in Version 7.7 (R2008b), but will not be supported in a future version of MATLAB.

Windows (32-bit) platform

- Intel Visual Fortran Version 9.1
- Microsoft Visual Studio .NET Version 7.1
- Open Watcom Version 1.3

Windows (64-bit) platforms

- Intel Visual Fortran Version 9.1

Solaris SPARC (64-bit) platform

- Sun Studio 11 cc / CC Version 5.8
- Sun Studio 11 f90 Version 8.2

Use mxDestroyArray to Release Memory for mxArray

Compatibility Considerations: Yes

The documentation for the `mxSetCell`, `mxSetField`, and `mxSetFieldByNumber` functions in the MATLAB C and Fortran API incorrectly instructs customers to use `mxFree` to release memory for any mxArray returned by `mxGetCell`, `mxGetField`, or `mxGetFieldByNumber`.

Compatibility Considerations

The correct function to use to release memory for an mxArray is `mxDestroyArray`. Calling `mxFree` on an mxArray only frees the array header, but does not actually free the data itself and can result in a memory leak.

To help diagnose this problem, MATLAB issues a warning if calling `mxFree` on an mxArray could cause memory corruption. In future versions of MATLAB, this condition might result in a segmentation violation.

New Function Displays Information about MEX Compiler Configurations

The `mex.getCompilerConfigurations` function displays information about the selected compiler and associated switches and options that MATLAB uses to build a MEX-file. The selected compiler is the one you choose when you run the `mex -setup` command. For more information, see [Building MEX-Files](#).

New Functions to Catch Errors in MEX-Files Replace mexSetTrapFlag

Compatibility Considerations: Yes

Two new MEX library functions have been added to the MATLAB C and Fortran API.

The `mexCallMATLABWithTrap` function, like `mexCallMATLAB`, lets you call MATLAB functions from within a MEX-file. In addition, `mexCallMATLABWithTrap` lets you catch, or trap, errors. Using this function for exception handling is more flexible than using `mexCallMATLAB` with the `mexSetTrapFlag` function.

Likewise, the `mexEvalStringWithTrap` function adds error handling to the `mexEvalString` function.

Compatibility Considerations

In the near future you will be required to update your MEX-files to remove use of the `mexSetTrapFlag` function.

“Duplicate dylib” Warning on Macintosh Systems

When compiling MEX-files on an Apple Mac OS Version 10.5 system you can ignore a warning about a duplicate library `libz.1.dylib`. The MEX-file builds properly and runs as expected. The warning message contains the following information:

```
ld: warning, duplicate dylib
```


Microsoft Visual Studio "X64 Compilers and Tools" Required for 64-bit Systems

If you use Microsoft Visual Studio with MATLAB on 64-bit systems, you must choose "X64 Compilers and Tools" when you install the following products:

- Visual Studio 2008 Express Edition
- Visual Studio 2008 Professional Edition
- Visual Studio 2005 Professional Edition

Run-Time Libraries Required for Applications Built with Microsoft Visual Studio 2008 Compiler

If you distribute a MEX-file, an engine application, or a MAT-file application built with the Visual Studio 2008 compiler, you must provide the Visual C++ run-time libraries. These files are required to run applications developed with Visual C++ on a computer that does not have Visual C++ 2008 installed. For information on locating the Microsoft Visual C++ 2008 Redistributable Package (x86), containing `vcredist_x86.exe` and `vcredist_x64.exe`, consult your Microsoft documentation.

Do Not Use get or set Function to Manage Properties of Java Objects

Compatibility Considerations: Yes

If you want to read or update a property of a Sun Java object created in MATLAB using the Java class constructor, do *not* use the MATLAB `get` or `set` functions on the property. For example, if you create a Java object called `javaObject` that has a property called `PropertyName`, the following commands might cause memory leaks and will be deprecated in a future version of MATLAB:

```
propertyValue = get(javaObject, 'PropertyName');  
set(javaObject, 'PropertyName', newValue);
```

Compatibility Considerations

In future versions of MATLAB, using `get` or `set` on Java objects to manage the properties will generate an error. The correct commands to use are:

```
propertyValue = javaObject.getPropertyName;  
javaObject.setPropertyName(newValue);
```

COM Objects Might Display Different Number of Supported Events

Compatibility Considerations: Yes

If you use events from COM servers implementing event interface versioning, COM objects created with MATLAB Version 7.4 (R2007a), Version 7.5 (R2007b), or Version 7.6 (R2008a) might have a different number of supported events than COM objects created with MATLAB Version 7.7 (R2008b) or any version prior to 7.4.

Compatibility Considerations

Calling the `events (COM)` function on affected types of COM server components returns a list of events for the latest [default] interface version which might be different from the list of events displayed by MATLAB Version 7.4, Version 7.5, or Version 7.6.

If an event in an older COM event interface version is no longer supported or renamed in the newer interface version, the `registerevent` function generates an error when such an event is used in an `.m` file.

R2008a

Version: 7.6
New Features: Yes
Bug Fixes: Yes

Desktop Tools and Development Environment

Desktop New Features Video

For an overview of the major new features in the MATLAB Desktop Tools and Development Environment area, watch this video demo. You can also access this and other video demos by selecting the **Demos** tab in the Help browser, and then selecting **MATLAB > New Features in Version 7.6**.

Startup and Shutdown

New features and changes introduced in Version 7.6 (R2008a) are:

- “Windows Platforms — Startup Changes, Including Use of My Documents/MATLAB or Documents/MATLAB Directory” on page 584
- “UNIX Platforms — Startup Changes” on page 585
- “Macintosh Platforms — Startup Changes” on page 585
- “Macintosh Platforms — Define Startup Options Using New Dialog Box” on page 586
- “Macintosh Platforms — Run Startup Diagnostics” on page 587
- “Updated Version of JVM Software on Solaris Platform” on page 587
- “Changes to Abnormal Termination Process” on page 588

Windows Platforms — Startup Changes, Including Use of My Documents/MATLAB or Documents/MATLAB Directory

On Microsoft Windows platforms, when MATLAB starts, it automatically adds the My Documents/MATLAB directory (or Documents/MATLAB on Windows Vista™) to the top of the MATLAB search path. This directory is known as the `userpath`. If you remove the My Documents/MATLAB (or Documents/MATLAB) directory from the search path and save the changes, either using the Set Path dialog box or using the `rmpath` and `savepath` functions, the MATLAB search path will not include the `userpath` directory at the next startup. On Windows platforms, the `userpath` is also the default startup directory.

Use the new function, `userpath`, to view the current value, clear the value so the directory is *not* on the search path and is *not* the startup directory, specify a different value, or reset the value to the default. For more information, see Default Startup Directory (Folder) on Windows Platforms and the `userpath` reference page.

Compatibility Considerations

In previous versions, MATLAB automatically added the My Documents/MATLAB directory (or Documents/MATLAB on Windows Vista

platforms) to the search path upon startup, even if you had removed it from the path and saved your changes during the previous session.

UNIX Platforms – Startup Changes

On UNIX platforms, when MATLAB starts, it automatically adds the *userhome/Documents/MATLAB* directory to the top of the MATLAB search path. This directory is known as the *userpath*. Use the new function, *userpath*, to view the current value, clear the value so the directory is *not* on the search path, specify a different value, or reset the value to the default. You can also specify that *userpath* be the MATLAB startup directory by setting the value for the environment variable `MATLAB_USE_USERWORK` to 1 prior to startup. For more information, see *Startup Directory on UNIX Platforms* and the *userpath* reference page.

Compatibility Considerations

In previous versions, no directories were added to the search path upon startup.

Macintosh Platforms – Startup Changes

On Apple Macintosh platforms, when MATLAB starts, it automatically adds the *userhome/Documents/MATLAB* directory to the top of the MATLAB search path. This directory is known as the *userpath*. Use the new function, *userpath*, to view the current value, clear the value so the directory is *not* on the search path, specify a different value, or reset the value to the default. If you start MATLAB from a shell, you can also specify that *userpath* be the MATLAB startup directory by setting the value for the environment variable `MATLAB_USE_USERWORK` to 1.

For more information, see *Startup Directory on <trademark Macintosh Platforms* and the *userpath* reference page.

Compatibility Considerations

In previous versions, no directories were added to the search path upon startup.


Macintosh Platforms – Define Startup Options Using New Dialog Box

On Apple Macintosh platforms, you can specify startup options using the new Start MATLAB Settings dialog box. The first time you start MATLAB Version 7.6 (R2008a), the Start MATLAB Settings dialog box opens automatically. It does not open automatically on subsequent startups; to open the dialog box, double-click `Start MATLAB Settings`, located in the same directory as the MATLAB application.

You can set these options and others:

- How you will interact with MATLAB (desktop or specified shell)
- The startup directory; the default is `userhome/Documents/MATLAB`
- Statement MATLAB runs upon startup

You can create and save multiple startup options files, each with different settings. For more information, see [Startup Options](#).



Macintosh Platforms – Run Startup Diagnostics

Upon startup on Macintosh platforms, MATLAB automatically runs diagnostics to ensure your system has the required X11 and Sun Microsystems Java applications. If there are no problems, MATLAB starts as expected. If there is a problem, MATLAB displays a dialog box informing you of the problem and how to address it. You can run these diagnostics manually from the Start MATLAB Settings dialog box, using items in the **Diagnostics** menu.

Updated Version of JVM Software on Solaris Platform

MATLAB is now using Sun Microsystems JVM Version 6 on the Sun Microsystems Solaris platform.

Compatibility Considerations

If you use a specific version of Sun Microsystems Java with MATLAB on the Solaris platform, this change might impact your work.

Changes to Abnormal Termination Process

When MATLAB encounters a serious problem, such as a segmentation violation, a dialog box opens to notify you about the problem. From the dialog box, you can close MATLAB, or try to save your work in progress before closing.

If you try to save your work in progress, be aware that MATLAB is in an unreliable state and you should exit MATLAB as soon as you finish saving your work. The Command Window displays the message `Please exit and restart MATLAB` to the left of the prompt, which reminds you to discontinue use. For more information, see [Abnormal Termination](#).

Compatibility Considerations

In previous versions, when MATLAB encountered a serious problem, an error message appeared in the Command Window that instructed you to close MATLAB.

With multithreaded computation enabled, a platform-specific dialog box appeared, from which you immediately closed MATLAB.


Desktop

New features and changes introduced in Version 7.6 (R2008a) are:

- “Customize the MATLAB Desktop and Editor Toolbars” on page 589
- “Clear a Browser with New Method” on page 591
- “Manage Your License” on page 591
- “Check for Updates Feature Enhanced” on page 591



Customize the MATLAB Desktop and Editor Toolbars



Rearrange, add, or remove buttons and other controls from the MATLAB desktop or Editor toolbars using **File > Preferences > Toolbars**. Alternatively, right-click a toolbar and select **Customize** from the context menu.



For more information, see [Toolbar Customization](#).


There are new buttons you can add to the MATLAB desktop toolbar:

- Preferences, , which displays the Preferences dialog box, open to the pane last used
- Demos, , which displays the listing of Demos in the Help browser

You can also add Save All  and Save As  buttons to the Editor toolbar.

You can change the position of the toolbars within a tool, for example, putting both the Editor and Editor cell mode toolbars next to each other instead of stacked. To move a toolbar, grab the anchor for a toolbar, then drag the toolbar to the new location.

Drag the toolbar anchor to move the toolbar to a different position.



Clear a Browser with New Method

Clear an open browser in MATLAB with a new close method. For example, open a browser to display the MathWorks Web site by running `[stat,h1]=web('http://www.mathworks.com')`. Then `close(h1)` clears `mathworks.com` from that browser window. For more information, see the reference page for the `web` function.

Manage Your License

You can use new licensing features to perform license management activities, such as activating your license, deactivating your license, or updating your license. You can also visit the License Center at the MathWorks Web site to perform other license-related activities. Access the features by selecting **Help > Licensing**.

Check for Updates Feature Enhanced

When you select **Help > Check for Updates**, the dialog box now allows you to see the latest versions for all MathWorks products, or just those you install. You can also access release notes for each product from the dialog box. For more information, see [Check for Software Updates](#).

Running Functions – Command Window and History

Compatibility Considerations: Yes

Command History Preference – Default Value Changed

The default value for the Command History preference, **Save after n commands**, is now 1. This allows you to more easily rebuild your state in MATLAB if MATLAB terminates abnormally, such as after a power failure. For more information about this preference, see Command History Preferences.

Compatibility Considerations

Previously, the default value for the **Save after n commands** preference was 5.

Help

Preferences for Help on Selection

When you click a function name in the Command Window or Editor, and then press **F1** or select **Help on Selection** from the context menu, the help appears in a pop-up window by default. Now, you can specify that the help appear in the Help browser rather than in a pop-up window via the new **Help on Selection** preference. For more information, see Help Preferences.

Slight Reordering of Products in Help Browser

In the Help browser, the order of some documentation names in the **Contents** pane and the Product Filter preference dialog box has changed slightly. Documentation now appears in this order:

- Release Notes (general)
- Installation
- MATLAB
- Toolboxes and other products based on MATLAB, arranged alphabetically
- Simulink
- Blocksets and other products based on Simulink, arranged alphabetically
- Link and target products, arranged alphabetically

Workspace, Search Path, and File Operations

New features and changes introduced in Version 7.6 (R2008a) are:

- “Array Editor Renamed to Variable Editor; Offers Enhanced Support for Structures and Classes” on page 594
- “Search Path — Changes to User Portion” on page 595
- “New Context Menu Options in Current Directory Browser” on page 596
- “File and Directory Comparisons Tool” on page 596

Array Editor Renamed to Variable Editor; Offers Enhanced Support for Structures and Classes


The Array Editor has been renamed to the Variable Editor, which better reflects its support for non-array data such as structures and properties.


The Variable Editor now reports, just below the toolbar, the class and size of the selected variable. For many classes, there is also a link to help for the class. To view a structure in the Variable Editor, double-click one of its elements. The resulting display is much like the display of that element in the Workspace browser, showing the Class, Value, Size, Min, Max, and other information. For more information about the Variable Editor, see Viewing and Editing Workspace Variables with the Variable Editor.

The class for the selected element is shown (struct in this example), and includes a link to help for that class.

Double-click an element in a structure in the Variable Editor (S(1,1) in this example).

The element opens in its own tab, displaying information about the data, as is done in the Workspace browser.




Use the data brushing button on the Variable Editor toolbar  to mark observations on graphs and then remove or save them to new variables. For more information, see “Data Brushing for Graphs and Linked Variables” on page 624.

The Variable Editor supports the new MATLAB class system. Double-click an object in the Workspace browser, and it opens in the Variable Editor. The Variable Editor displays the object, the class, and the properties of the object.

Double-click an object in the Workspace browser and it displays the object's properties in the Variable Editor.

Object and class. →

Properties. ↙ ↘



Compatibility Considerations

In previous versions, the Variable Editor was called the Array Editor. Starting in R2008a, MATLAB Version 7.6, the tool will be referred to as the Variable Editor.

Search Path – Changes to User Portion

By default, MATLAB adds a directory to the top of the search path upon startup, known as the `userpath` directory. By default, its value is `Documents/MATLAB` on Windows platforms, or `My Documents/MATLAB` on Windows Vista platforms. On UNIX and Macintosh platforms, the default directory is `userhome/Documents/MATLAB`. Use the new function, `userpath`, to specify a different directory, clear the `userpath` value, or reset it to the default value. On UNIX and Macintosh platforms, you can specify additional

directories for MATLAB to add to the top of the search path upon startup using the MATLABPATH environment variable. When you remove the `userpath` portion of the search path, it clears the value for `userpath` and might impact the startup directory. For related information, see “Startup and Shutdown” on page 584. For details see Locations for Storing Your Files and the `userpath` reference page.

Compatibility Considerations

In previous versions, on Windows platforms, MATLAB added the default directory to the search path upon startup, even if you removed it and saved the changes to the path. On UNIX and Macintosh platforms, MATLAB did not add a directory to the search path on startup.

New Context Menu Options in Current Directory Browser

The context menu, which you access by right-clicking anywhere within the Current Directory browser, provides these three new options for creating M-files in the current directory:

- **New > Blank M-File**
Creates an empty M-file
- **New > Function M-File**
Creates an M-file with a template for writing an M-file function
- **New > Class M-File**
Creates an M-file with a template for writing an M-file class definition

Compatibility Considerations

The **New > M-File** option is replaced by the **New > Function M-File** option, which has the same effect.

File and Directory Comparisons Tool

The File Comparisons tool is now called the File and Directory Comparisons Tool. In addition to enabling you to compare lines in two text files, it now enables you to:

- Compare variables in two MAT files
- Determine whether the contents of two binary files are the same
- Compare two directories to determine which file names are unique to each directory
- Compare two directories to determine if files with the same name in each directory have the same content

See `Comparing Files and Folders` for details.

Tuning and Managing M-Files

Profiling – Setting Intel Multi-Core Processors

If your system uses Intel multi-core chips, and you plan to profile using CPU time, set the number of active CPUs to 1 before you start profiling. See Intel Multi-Core Processors — Setting for Most Accurate Profiling on Windows Systems for details.

Editing and Debugging M-Files

New features and changes introduced in Version 7.6 (R2008a) are:

- “Stand-Alone Editor No Longer Provided” on page 599
- “Run/Continue Button Now Two Separate Buttons” on page 599
- “Evaluate Entire File Button Off Toolbar by Default” on page 600
- “TLC and XML Syntax Highlighting Supported” on page 600
- “Code Folding Enhanced to Support More Language Constructs” on page 600
- “mlint Function Uses Preference Settings when Java Software is Available” on page 601
- “New M-Lint Warning Related to the MException Class” on page 602
- “dbstop and dbclear Functions — Option to Specify File Not on Path” on page 603
- “edit Function Can Create New File in Existing Subdirectory” on page 604
- “Nest Cells for Rapid Code Iteration; Includes Changes to Cell Highlighting” on page 604

Stand-Alone Editor No Longer Provided


The MATLAB stand-alone Editor (`meditor.exe`) is no longer provided. Instead of the stand-alone Editor, you can use the MATLAB Editor.

Compatibility Considerations

Some users have preferred the stand-alone Editor to the MATLAB Editor because of slightly better startup performance and because it does not require a MATLAB software license. For those situations, you can use any text editor you have, such as UltraEdit or Emacs.

Run/Continue Button Now Two Separate Buttons


The Continue button is now separate from the Run button. Previously, the Run button served as both the Run and Continue button.



Compatibility Considerations

You now use the Run button to execute a run configuration and the Continue button to continue execution of an M-file after a breakpoint during debugging. See [Run MATLAB Files in the Editor and Step Through a File](#) for details.

Evaluate Entire File Button Off Toolbar by Default

The Evaluate Entire File button, , is no longer on the Editor Cell Mode toolbar by default.

Compatibility Considerations

Previously, the Evaluate Entire File button was on the Editor Cell Mode toolbar by default. You can put the Evaluate Entire File button back on the toolbar by customizing it. See [“Customize the MATLAB Desktop and Editor Toolbars”](#) on page 589 for more information.

TLC and XML Syntax Highlighting Supported

You can specify preferences for TLC and XML syntax highlighting in the Editor/Debugger Language Preferences panel by selecting **File > Preferences > Editor > Language** and then, in the **Language** drop-down menu choosing **TLC** or **XML/HTML**.

Click **Help** in the Preferences dialog box for more information.

Code Folding Enhanced to Support More Language Constructs

You can enable code folding for all these programming constructs:

- Blocks of comments
- Cells used for rapid code iteration and publishing
- Class code
- Class enumeration blocks
- Class event blocks
- Class method blocks
- Class properties blocks
- For and parfor blocks
- Function and class help
- Function code
- If/else blocks
- Switch/case blocks
- Try/catch blocks
- While blocks

Prior to MATLAB Version 7.6 (R2008a), code folding was supported for function code and function help only.

See Code Folding — Expand and Collapse Code Constructs for details.

mlint Function Uses Preference Settings when Java Software is Available

When Sun Microsystems Java software is available, the `mlint` function honors the M-lint preferences that you specify using the M-Lint Preferences dialog box (**File > Preferences > M-Lint**).

In addition, the `' config=settings.txt'` option to the `mlint` function enables you to override the current default M-Lint preferences settings with a settings file that you previously created and saved using the M-Lint Preferences dialog box. If you use the `' config=settings.txt'` option, you must specify the full path to the file. If you prefer that `m-lint` ignore all

M-Lint preferences and use the factory default settings instead, specify the ' config=factory' flag. See `m-lint` for details.

Compatibility Considerations

Previously, the `mlint` function always used the factory default settings, regardless of the M-Lint preferences that you set. To restore that behavior, use the ' config=factory' flag on the `mlint` function.

New M-Lint Warning Related to the MException Class

MATLAB Version 7.6 (R2008a) adds a new M-Lint warning related to the `MException` class. This warning, along with two M-Lint warnings added in MATLAB Version 7.5 (R2007b), intentionally make it difficult for you to completely ignore an error without receiving an M-Lint warning. It is a best practice to check error information even when an error is expected or frequent, so that you can rule out unexpected situations.

The three messages are as follows—the first is the one added in MATLAB Version 7.6 (R2008a):

- `LASTERR` and `LASTERROR` are better replaced by an identifier on the `CATCH` block. See `doc CATCH`.
- The value assigned here to variable 'x' might never be used.
This message appears when the code contains a `catch` statement that is never used.
- `TRY` statement without a `CATCH`.

For example, suppose you want to read options from a file, `options.txt`, but it is acceptable if that file is not present. You might write the following code, expecting the `read_options` program to throw an error if the file is not present:

```
options = {};  
try  
    options = read_options( 'options.txt' );  
end
```

The problem with the preceding code is that the file might be present, but its permissions may prevent the program from reading it. The program ignores the file, and potentially confuses the user, who knows the file is there. Better code for accomplishing the task is as follows, which assigns a structure value to the variable `err` if an error is thrown in the `try` block. The structure value contains information about the error that was thrown.

```
try
    options = read_options( 'options.txt' );
catch err
    if strcmp( err.identifier, 'Program:ReadOptions:NoOptionsFile' )
        options = {};
    else
        rethrow( err );
    end
end
```

Using this code, if a problem other than the “file is missing” error occurs, MATLAB reports the error to the user. For instance, MATLAB reports an error if the file format is incorrect, or if the file has the wrong permissions.

If you feel comfortable ignoring the errors completely, it is probably best to use the `try` statement with no `catch` statement, and suppress the M-Lint warnings that result. You can suppress the warnings through the M-Lint preferences or by placing the `%#ok` pragma at the end of the line that triggers the message. However, The MathWorks suggests that if you suppress an M-Lint message, you include a comment in your code indicating why you think it is appropriate to ignore the message.

For more information about the `MException` class, see the Error Handling section in the MATLAB Programming Fundamentals documentation.

dbstop and dbclear Functions – Option to Specify File Not on Path

The `completenames` option to the `dbstop` and `dbclear` functions enables you to set and clear breakpoints, respectively, for M-files that are not on the search path in MATLAB. See `dbstop` and `dbclear` for details.

edit Function Can Create New File in Existing Subdirectory

The edit function now allows you to specify a file that is not in the current directory. If the file does not exist, the edit function creates it in the directory you specify. However, the directory, must exist; the edit function will not create a directory for you. See `edit` for details.

Nest Cells for Rapid Code Iteration; Includes Changes to Cell Highlighting

You can nest cells in an M-file, including within functions and control statements, such as `for` loops and `if-then` blocks. This gives you greater control over how a published document appears. This nesting ability also enables you to evaluate subsections of code on a finer grain. See “Nest Cells for Finer Control” on page 607 for details.

Compatibility Considerations

With the introduction of nested cells, cells definitions result in cell highlighting that looks different from previous releases. See `Define Code Cells` for details.

Publishing M-Files

New features and changes introduced in Version 7.6 (R2008a) are:


- “Publish Functions and Scripts Using Publish Configurations; Includes Replacement of Publishing Preferences” on page 605
- “Nest Cells for Finer Control” on page 607
- “Publish Button Moved” on page 614
- “Publish Trademark Symbols” on page 614
- “Specifying Code for MATLAB Software to Evaluate with the publish Function” on page 614
- “stopOnError Option No Longer Available with publish Function” on page 614
- “Include Snapshot of M-file Output in Published Document” on page 615

Publish Functions and Scripts Using Publish Configurations; Includes Replacement of Publishing Preferences

In the Editor, you can now do the following when publishing M-file code:

- Specify code that you want MATLAB to evaluate before publishing the code, including input arguments for functions
- Specify publishing settings, such as an output directory and file format, that you can save and reuse as a group

To create a publish configuration, first open an M-file in the Editor. Then, select **File > Publish Configurations for *filename* > Edit Publish Configurations for *filename***. In the resulting Edit M-File Configurations dialog box, modify the **MATLAB expression**, specify **Publish settings**, and name the publish configuration. For more information, see [Creating a Publish Configuration for a MATLAB File](#).



Compatibility Considerations

Previously, preferences for publishing and publishing images were available on the Preferences dialog box, which you accessed by selecting **File > Preferences > Editor/Debugger** and then choosing the **Publishing** or **Publishing Images** node. Now you set these preferences when you create or update a publish configuration by using the **Publish settings** options on the Edit M-file Configurations dialog box.


The Edit M-file Configurations dialog box continues to provide support for creating configurations that enable you to run an M-file. These are now called run configurations to differentiate them from publish configurations.

Nest Cells for Finer Control

You can nest cells in an M-file, including within functions and control statements, such as for loops and if-then blocks. This gives you greater control over how a published document appears. This nesting ability also enables you to evaluate subsections of code on a finer grain when using rapid code iteration.

You can insert white space before the double percent (%%) characters that specify a cell break (which is also referred to as a cell divider). This helps to improve readability of the M-file when the cell break is within indented code. In prior releases, the %% characters had to be in the first column of the code.

The following image shows a simple example of an M-file with nested cells.




The screenshot shows the MATLAB Editor window titled "Editor - I:\my_matlab_files\my_mfiles\plot_example.m". The menu bar includes File, Edit, Text, Go, Cell, Tools, Debug, Desktop, Window, and Help. The toolbar contains various icons for file operations, editing, and execution. Below the toolbar is a numeric keypad with values 1.0 and 1.1, and mathematical symbols for addition, subtraction, multiplication, and division. The main editor area displays the following code:


```
1      %% Plot x as i Increases
2
3      x = 0:.1:2*pi;
4      clf
5      hold on
6      for i = 1:3
7          %%
8          plot(x, i*sin(i), ...
9              'bp', 'MarkerSize', 4.5)
10     end
11
```

The code is displayed with line numbers on the left. A yellow cell is highlighted, containing lines 7 through 9. The cell is defined by a double percent sign (%%) at the start of line 7 and is indented under the 'for' loop. The status bar at the bottom shows "script", "Ln 9", "Col 36", and "OVR".

If you publish the file to HTML (reducing the size of the images), the cell break nested within the `for` loop causes MATLAB to publish each iteration of the `for` loop as it evaluates the code in the loop:



Similarly, the cell break within the for loop enables you to run the M-file and experiment with the marker size value without the need to save the file between adjustments:



For more information see [Mark Up MATLAB Code for Publishing and Evaluate Subsections of Files Using Code Cells](#).

Compatibility Considerations

In prior releases, the cell break characters (%%) had to be in the first column of the code for the Editor to recognize the characters as a cell break. This is no longer true, the Editor now recognizes these characters as a cell break regardless of the amount of white space that precedes them.


Furthermore, with the introduction of nested cells, inserting cell breaks in this release has different effects than in the previous release. In the previous release, if you inserted a cell break before a subfunction declaration, MATLAB

created two cells; one above the cell break and one below it. Now, if you insert a cell break, MATLAB also inserts implicit cell breaks.

In the example shown, it inserts two implicit cell breaks in the subfunction where you inserted the explicit cell break; one on the first line of the subfunction and one on the last line of the subfunction. This results in three cells: one containing the entire file, one containing the `collatzplot_new` function, and one containing just the Collatz Problem cell title.

Nested cells are introduced to support function publishing.

Version 7.5 (R2007b)



Editor - I:\my_matlab_files\my_mfiles\collatzplot_new.m

File Edit Text Go Cell Tools Debug Desktop Window >> >>

```
1 function collatzplot_new(m)
2     clf
3     set(gcf,'DoubleBuffer','on')
4     set(gca,'XScale','linear')
5
6     for N = 1:m
7         plot_seq = collatz(N);
8         seq_length(N) = length(plot_seq);
9         line(N,seq_length(N),'Marker','.',':');
10        drawnow
11    end
12    %% Collatz Problem
13    function sequence=collatzz(n)
14        sequence = n;
15        next_value = n;
16        while next_value > 1
17            if rem(next_value,2)==0
18                next_value = next_value/2;
19            else
20                next_value = 3*next_value+1;
21            end
22            sequence = [sequence, next_value];
23        end
24    end
```

Explicit cell break

collatzplot_new Ln 12 Col 19 OVR

Version 7.6 (R2008a)

The screenshot shows the MATLAB Editor window titled "Editor - I:\my_matlab_files\my_mfiles\collatzplot_new.m". The script content is as follows:

```
1 function collatzplot_new(m)
2     clf
3     set(gcf,'DoubleBuffer','on')
4     set(gca,'XScale','linear')
5
6     for N = 1:m
7         plot_seq = collatz(N);
8         seq_length(N) = length(plot_seq);
9         line(N,seq_length(N),'Marker','.', 'M
10        drawnow
11    end
12    %% Collatz Problem
13    function sequence=collatz(n)
14        sequence = n;
15        next_value = n;
16        while next_value > 1
17            if rem(next_value,2)==0
18                next_value = next_value/2;
19            else
20                next_value = 3*next_value+1;
21            end
22            sequence = [sequence, next_value];
23        end
24
```

Annotations on the left side of the editor:

- "Implicit cell break" points to the end of line 11.
- "Explicit cell break" points to the end of line 11.
- "Implicit cell break" points to the end of line 23.

The status bar at the bottom indicates "collatzplot_new", "Ln 12", "Col 19", and "OVR".

See Nested Code Cells for details.

Publish Button Moved

The Publish button, , is now located on the Editor toolbar.

Compatibility Considerations

Previously, the Publish button was located on the Editor Cell Mode toolbar. Now you find it on the Editor toolbar.

Publish Trademark Symbols

If the comments in your M-file include trademarked terms, you can format the comment to produce a trademark symbol (™) or registered trademark symbol (®) in the published output. See Trademark Symbols for details.

Specifying Code for MATLAB Software to Evaluate with the publish Function

Use the `codetoEvaluate` option to the `publish` function to specify code that you want MATLAB software to evaluate when it publishes an M-file. By default, this is the code in the M-file. However, if you want, you can use this option to specify additional code or alternative code for MATLAB to evaluate. For example, you might want MATLAB to evaluate code that calls the M-file that you are publishing.

stopOnError Option No Longer Available with publish Function

The `stopOnError` option is no longer available for the `publish` function. MATLAB software will always stop when an error occurs, unless you add code to handle the error.


Compatibility Considerations

To have MATLAB continue processing code when an error occurs, handle the error using a try-catch statement. For more information, see The try-catch Statement.

Include Snapshot of M-file Output in Published Document

You can include snapshots of output that an M-file generates within a published document. Select **Cell > Insert Text Markup > Force Snapshot**. This menu option inserts the `snapnow` function into your M-file code. This is particularly useful when you have code that generates numerous images that you want to include in the published document. See *Force a Snapshot of Output* for details.

The following image, for example, shows a published document that uses this feature (with the size of the images reduced). Notice that the published images appear after the `for` loop that generates them.



Internationalization

Locale Information Added to MATLAB Documentation

Information about using locale in MATLAB can be found in Internationalization in the Desktop Tools and Development Environment documentation.

Changes to Locale Database

Windows Platform Changes

On Microsoft Windows systems, users can select the Pashto language with the Afghanistan country code. This locale setting is `ps_AF.1256`.

Macintosh OS X Platform Changes

On Apple Macintosh OS X systems, for users selecting the Chinese language and the China country code, the locale setting is `zh_CN.gb2312`. The previous setting was `zh_CN.GBK`.

Mathematics

Upgrade to BLAS Libraries

MATLAB software now uses new versions of the Basic Linear Algebra Subroutine (BLAS) libraries. For Windows, Intel Mac, and Linux platforms, MATLAB software supports the Intel Math Kernel Library (MKL) version 9.1. For the Solaris platform, MATLAB software uses the Sun Performance Library from Sun Studio 12.

Upgrade to LAPACK Library

MATLAB software now uses Version 3.1.1 of the Linear Algebra Package (LAPACK) library.

More Multithreaded Support For Elementwise Math Functions With Warnings

Multithreaded support has been added to elementwise math functions that may generate warnings: `rdivide`, `ldivide`, `log`, `log2`, and `rem`.

New Algorithms for `ldl`, `logm`, and `funm` Functions

The `ldl`, `logm`, and `funm` functions include new algorithms based on recent numerical methods research.

Functions and Properties Being Removed

Compatibility Considerations: Yes

Function or Property Name	What Happens When You Use Function or Property?	Use This Instead	Compatibility Considerations
betacore	Errors	betainc	Replace all existing instances of betacore with betainc.
colmmd	Errors	colamd	Replace all existing instances of colmmd with colamd.
flops	Errors	None	Remove all existing instances of flops. With the incorporation of LAPACK in MATLAB version 6, counting floating-point operations is no longer practical.
symmmd	Errors	symamd	Replace all existing instances of symmmd with symamd.
quad8	Errors	quad1	Replace all existing instances of quad8 with quad1.
table1	Errors	interp1 or interp1q	Replace all existing instances of table1 with interp1 or interp1q.
table2	Errors	interp2	Replace all existing instances of table2 with interp2.
bessela	Errors	besselj	Replace all existing instances of bessela with besselj.
beta using three input arguments	Errors	betainc using three input arguments	Replace all existing instances of beta using three input arguments with betainc using three input arguments.

Data Analysis

Data Brushing for Graphs and Linked Variables

Compatibility Considerations: Yes

- “Data Brushing Tool” on page 625
- “Data Brushing API” on page 626
- “Data Linking Tool” on page 626
- “Data Linking API” on page 628

This release introduces two new interactive tools for data exploration:

- **Data brushing** — For marking observations on graphs, allowing you to remove or save them to new variables
- **Data linking** — For connecting graphs with data sources (workspace variables) to automatically and interactively update them

In addition, figure windows have a new banner, called the *linking and brushing message bar*. By default, when you plot data into a figure (i.e., add axes), an informational banner appears across top of the figure that looks like this.



In the figure’s message bar, click the first two links to read about these new tools. Click the **Play video** link to open a nine-minute video tutorial about the tools in a browser window (the video also describes new GUI-building features.) To dismiss the banner, click the **X**. Once you do, the banner only reappears on subsequent plots if you select **Show linking and brushing message bar** in the MATLAB Preferences Confirmation Dialogs panel.

Note The linking and brushing message bar can obscure a plot’s title. Also, if you do not dismiss the message bar, it is visible in images of figures captured with `getframe`, but it does not print. See for details.

Use data brushing when you want to isolate observations in a 2-D or 3-D graph for separate analysis, or to remove outliers or noisy data points. Data

brushing can be applied to most graphs (some plot types do not support brushing). Data brushing is an exclusive, persistent mode. That is, when using it, you cannot use other figure tools, but the results of brushing data persist when you select a different tool or no tool.

Use data linking to make plots dynamically respond to changes in the variables they plot. Data linking applies to most graphs with identifiable data sources and operates at the figure level. Data linking is not modal and persists until you toggle it off or the connection between a plot and its data sources is broken.

The two tools work smoothly together and with the Variable Editor to visually highlight brushed observations and the data values they represent:

- Brushing data-linked observations on a graph highlights them on other graphs that display them.
- Brushing highlights values in the Variable Editor when a brushed variable is displayed there.
- Using the Brush tool in the Variable Editor highlights values you brush that appear in linked plots.
- Changing values of variables causes linked graphs displaying them to update with the changes.
- Clearing variables disconnects them from all linked figures displaying graphs of them

You can modify variables from the command line, the Variable Editor, or with M-files. When used within functions, data linking operates in the function's workspace, not the base workspace. This is also the case when debugging.



Data Brushing Tool

All figure windows that contain axes now include a data brushing tool (the



Brush/Select data icon) that lets you enter and exit brushing mode and select a color with which to brush observations. The tool draws selection rectangles (in 2-D plots) or prisms (in 3-D plots) and permits you to select discontinuous regions and negate previously brushed observations. Undo is also supported.

The Brush/Select data tool is a “split button” control with a brush icon on the left and a drop-down color palette on the right. When you depress the brush icon, you are in brushing mode; all data observations you select are highlighted with the current brush color. The figures below illustrate these operations.




If you leave data brushing mode to zoom, pan, or edit the plot, all brushed observations remain highlighted. You can then reenter brushing mode and pick up where you left off. Brush marks are not preserved when you save a figure and reopen it from the FIG-file, however.

Data Brushing API


Use the brush function to turn brushing on and off, and to select a color for brushing graphs. You can change brush colors on the fly with either the API or with the Brush tool.


Data Linking Tool


All figure windows that contain axes now include a data linking tool (the

Linked Plots button ) to toggle linked mode on and off (the default). When you toggle it on, an information bar appears underneath the lowest

toolbar on the figure, as shown below. It displays what variables are linked to each series (data sources for x -, y -, and z - data in the graphs).



On the left side of the information bar is a drop-down menu  that displays the symbolism and identifies the data source for each series currently linked. On the right side is an **Edit** button that opens the Data Source Properties dialog box in which you can set display names and data sources. Usually it is possible to unambiguously determine what data sources a graph has, but sometimes you need to indicate what data source to use, for example, when you plot a subrange of a data array. The information bar explains that you need to do this as soon as you turn on data linking; then, you can open the Data Source Properties dialog box to identify your data source(s).



Data Linking API

Use the `linkdata` function to turn data linking on or off for the current figure or for a figure for which you supply a handle.

Compatibility Considerations

If you capture figure windows with the `getframe` function, their images will include the message bar if the figures being captured possess them. To prevent this from happening, click the **X** on the right side of the message bar to dismiss it before calling `getframe`. Subsequent figures will not display a message bar. If you want to restore the message bar at a later time, select **Show linking and brushing message bar** in the MATLAB Preferences Confirmation Dialogs panel.

If the figure has a title, its Linked Plots/Data Brushing message bar can obscure it. This is the case for figures at the default size. Remove the message bar if you want a title to display.

Programming

Multithreaded Computations Enabled

Compatibility Considerations: Yes

Multithreaded computations, introduced in R2007a, are now on by default.

Compatibility Considerations

To disable multithreaded computations, open the Preferences dialog, choose Multithreading, and then disable it explicitly.

Enhancements to Object-Oriented Programming Capabilities

Major enhancements to object oriented programming capabilities enables easier development and maintenance of large applications and data structures.

New features include:

- The new `classdef` keyword enables you to define properties, methods, and events in a class definition file. See [User-Defined Classes](#).
- A new `handle` class with reference behavior enables you to create more sophisticated data structures, such as linked lists and to manage external resources, such as files. See [Comparing Handle and Value Classes](#).
- Events and listeners enable you to monitoring object property changes and other actions. See [Events — Sending and Responding to Messages](#).
- Packages enable scoping of classes and functions. See [Create a Namespace with Packages](#).
- Meta-classes provide support for class introspection. See [Information from Class Metadata](#).
- JIT/Accelerator support provides significantly improved performance over the previous object oriented-programming system.

For a full description of object-oriented features, see [Object-Oriented Programming](#).

Packages for Classes and Functions

This release provides the capability to manage name space by placing classes and functions in packages.

Clear Variables with Exceptions

With the new `clearvars` function, you can specify which variables you do not want cleared from memory.

Information on the State of Memory

Compatibility Considerations: Yes

The new `memory` function provides memory usage information such as largest block available, allowing you to diagnose memory problems on Microsoft Windows platforms.

Compatibility Considerations

The `memory` function existed in previous versions of MATLAB, but its purpose has changed. Previously, `memory` provided help text on how to free additional memory space for your MATLAB application. The function now returns information on the current state of memory use and availability in your system.

Define Your Own Function Cleanup Tasks

With the new `onCleanup` function, you can specify one or more tasks for MATLAB to perform just before exiting the current function.

New Functions

Name	Description
clearvars	Clear variables from memory
memory	Display memory information
onCleanup	Cleanup tasks at function completion

Extended JIT Support

JIT/Accelerator support now extends to statements executed at the MATLAB Command Line and in cell mode in the MATLAB Editor. This provides improved performance in these environments.

Enhancements to Image Information and Writing Functions

The image information and writing functions have the following enhancements:

- `imfinfo` can now return Exif data for JPEG or TIFF format image files. Information specific to the digital camera can be found in the 'DigitalCamera' field, while any global positioning system information can be found in the 'GPSInfo' field.
- `imwrite` now supports the 'RowsPerStrip' parameter that you can use to specify how many image rows to include in a strip when writing TIFF files. By default, `imwrite` limits the number of rows included in a strip so that the size of the strip does not exceed 8 KB. Now you can specify strips of larger size.

Compression of -v7.3 MAT-Files

You can store data items that are over 2 gigabytes in size in a MAT-file using the `-v7.3` option for the `save` function. This option was introduced in MATLAB R2006b. With MATLAB R2008a, `save` now compresses these MAT-files.

Changes to Programming Documentation

Some of the chapters in the MATLAB Programming documentation have been moved or renamed in this release. Also the title of the Programming documentation has been changed to Programming Fundamentals in order to differentiate this part of the MATLAB help from the new documentation on Developing MATLAB Classes.

Graphics and 3-D Visualization

New Figure Toolbar Buttons

Two new toolbar buttons and an information bar have been added in this release that control the new *Data Brushing* and *Data Linking* tools. Brushing and linking let you interactively explore and analyze data.

By default, now when you create axes or plot something into a blank figure, an informational banner appears across top of the figure with links to documentation for data brushing and linking capabilities. You can dismiss it by clicking the **X** button on right-hand side of the message bar. Once you dismiss it, subsequent figures will not display the banner unless you select **Show linking and brushing message bar** in the MATLAB Preferences Confirmation Dialogs panel.

For more information, see “Data Brushing for Graphs and Linked Variables” on page 624 in the Data Analysis release notes and Interactive Data Exploration in the Data Analysis documentation. Also view the video tutorial that describes these and other new features.

"v6" Plotting Option Update — Affected Functions

Compatibility Considerations: Yes

The Version 7.5 (R2007b) release note "The "v6" Option for Creating Plot Objects is Obsolete" on page 726 identified plotting functions that accept the v6 option, which is now obsolete and will be removed in a future version of MATLAB. There is no change to the status of these functions in R2008a. However, the list of affected functions in the R2007b release note had errors and omissions. Below is the correct list of functions that support the option in their syntax and now warn when it is used:

- area
- bar
- barh
- colorbar
- contour
- contourf
- errorbar
- legend
- loglog
- mesh
- plot
- plot3
- quiver
- quiver3
- scatter
- scatter3
- semilogx
- semilogy
- stairs

- stem
- stem3
- subplot
- surf

Note that the updated list adds functions `plot3` and `quiver3`.

In the earlier release note, the following functions were incorrectly identified as accepting the `v6` option:

- meshc
- meshz
- surfc

These functions do not call `v6` code and are not affected by it becoming obsolete.

Compatibility Considerations

Specifying the `v6` flag to any plotting function now results in a warning that the option is being removed, but the option still functions. To generate a FIG-file for a plot created with the `v6` option, you still need to use the `-v6` option to the `hgsave` command in order to save it in a form that a previous version of MATLAB can read. Figures containing annotations (such as textboxes, arrows, ovals, and rectangles) that are saved this way open in previous versions, but the annotations do not display because different objects are used to contain them in Version 7 than before. That is, the annotation objects have never been backward compatible.

Creating Graphical User Interfaces (GUIs)

New GUI Table Component

The new `uitable` component allows you to show data in a table. This component replaces the undocumented MATLAB `uitable` implementation. If you are using the old `uitable` component, please refer to the `uitable` Migration Document for help migrating to the supported `uitable` component.

Event Data Input to GUIDE Callbacks

Auto-generated callbacks of GUIDE GUIs can now access event data for Handle Graphics callbacks. The following Handle Graphics callbacks provide event data when triggered:

- `KeyPressFcn` in `uicontrol` and `figure`
- `KeyReleaseFcn` in `figure`
- `SelectionChangeFcn` in `uibuttonGroup`
- `WindowKeyPressFcn` in `figure`
- `WindowKeyReleaseFcn` in `figure`
- `WindowScrollWheelFcn` in `figure`
- `CellEditCallback` in `uitable`
- `CellSelectionCallback` in `uitable`

For example, the event data for `keypress` provides information on the key that is pressed. See the [Callback Templates](#) documentation for more information.

uigetfile and uiputfile Support of '.', '..', and '/'

Starting in R2007b, the `uigetfile` and `uiputfile` functions interpret '.', '..', and '/' the same way as does the `cd` command. '.' is interpreted as the current directory, '..' is the directory above the current directory, and '/' is the top level directory. When specifying a directory rather than a filename for either the `Filterspec` or `DefaultName` argument, you no longer need to end the string with a '/'. However, such strings ending with a '/' are interpreted as they were in previous releases.

hidegui Function Being Obsoleted

The `hidegui` function is being obsoleted and will be removed in a future version. Instead of this function use the `set` function to set the figure handle's `handlevisibility` property to `on` or `off`:

```
set(figurehandle, 'handlevisibility', 'on')
```

Changes to How uicontrols Set Figure SelectionType

Compatibility Considerations: Yes

SelectionType is a figure property that user interface components set when you click them. It is a read-only property that describes the gesture used when clicking the most recently selected object. For single mouse clicks, components no longer set the figure SelectionType property to anything but 'normal' when they are enabled. By default, all components are enabled (their Enable property is 'on'). Previously, enabled components responded to modifier keys (**Ctrl**, **Alt**, **Shift**, and **Cmd**) by setting SelectionType to 'alt' or 'extend'. Now all key modifiers set SelectionType to 'normal' for UI components.

Disabled components (those with their Enable property set to 'off') set SelectionType to 'alt' or 'extend' in response to modifier keys.

When Enable is 'on', the control is active and your Callback responds to clicks. When Enable is 'off', the control is not active, and your ButtonDownFcn responds to clicks. You can provide components with a ButtonDownFcn to detect changes in SelectionType.

An additional change affects how *list box* uicontrol components respond to double-clicking. The second of two successive clicks sets the SelectionType property of an enabled list box to 'open'. Other types of uicontrols set their SelectionType to 'normal' after both the first and the second clicks unless key modifiers were used.

The following table describes the click responses for uicontrol components.

Enable Status	Mouse Button Pressed	Key Modifier Pressed	SelectionType on First Click	SelectionType on Second Click
on	left		'normal'	'normal' *
on	right		'alt'	'open'
on	left	Ctrl	'normal'	'normal' *
on	right	Ctrl	'alt'	'open'
on	left	Shift	'normal'	'normal' *
on	right	Shift	'extend'	'open'

Enable Status	Mouse Button Pressed	Key Modifier Pressed	SelectionType on First Click	SelectionType on Second Click
off	left		'normal'	'open'
off	right		'alt'	'open'
off	left	Ctrl	'alt'	'open'
off	right	Ctrl	'alt'	'open'
off	left	Shift	'extend'	'open'
off	right	Shift	'extend'	'open'

* Double-click result is 'open' for list boxes.

For a two-button mouse, pressing the left and right buttons together (without key modifiers) can set `SelectionType` to either 'normal' or 'extend'; the results are unpredictable, possibly depending on which button you actually depressed first.

`uipushtool` and `uitoggletool` toolbar buttons do not set `SelectionType` at all, no matter what keys or mouse buttons you press. When they are disabled, `uipushtool` and `uitoggletool` controls do not execute their `ClickedCallback` (or `OnCallback/OffCallback`), nor does using them trigger a `WindowButtonDownFcn` callback.

Compatibility Considerations

If your callback code depends on the value for `SelectionType`, be aware that for the left mouse button, pressing **Ctrl** no longer sets it to 'alt' and that **Shift**-clicking no longer sets it to 'extend'.

The `SelectionType` behavior for the right mouse button has not changed.

External Interfaces/API

Interface to Generic DLLs Supported on 64-bit Platforms

Compatibility Considerations: Yes

The ability to load a generic DLL on 64-bit platforms using `loadlibrary` is available in MATLAB Version 7.6 (R2008a).

Compatibility Considerations

You must install a C compiler and Perl to use this feature. For a list of supported compilers and how to install them, see [Using loadlibrary on 64-Bit Platforms](#).

Changes to Compiler Support

Compatibility Considerations: Yes

The set of compilers that MATLAB supports has changed in MATLAB Version 7.6 (R2008a). For an up-to-date list of supported compilers, see the Supported and Compatible Compilers Web page.

- “New Compiler Support” on page 654
- “Discontinued Compiler Support” on page 655
- “Compiler Support to Be Phased Out” on page 655

New Compiler Support

MATLAB Version 7.6 (R2008a) supports new compilers for building MEX-files.

Microsoft Windows (64-bit) platform

- Microsoft Visual Studio 2008
- Windows SDK for Vista
- Intel Visual Fortran 10.1

Windows (32-bit) platform

- Microsoft Visual Studio 2008
- Open Watcom Version 1.7
- Intel Visual Fortran 10.1

Sun Solaris SPARC (64-bit) platform

- Sun Studio 12 cc / CC Version 5.9

Macintosh (Intel-based 32-bit) platforms

- Apple Xcode 3.0 (gcc / g++ Version 4.0.1)

Discontinued Compiler Support

The following compilers are no longer supported.

Windows platforms

- Intel C++ Version 7.1
- Intel Visual Fortran Version 9.0
- Borland® C++Builder® 6 Version 5.6
- Borland C++Builder 5 Version 5.5
- Borland C++ Compiler Version 5.5
- Compaq Visual Fortran Version 6.1
- Compaq Visual Fortran Version 6.6

Compatibility Considerations

To ensure continued support for building your C/C++ programs, consider upgrading to another supported compiler. For an up-to-date list of supported compilers, see the Supported and Compatible Compilers Web page.

Compiler Support to Be Phased Out

The following compilers are supported in Version 7.6 (R2008a), but will not be supported in a future version of MATLAB.

Windows (32-bit) platform

- Open Watcom Version 1.3

Solaris SPARC (64-bit) platform

- Sun Studio 11 cc / CC Version 5.8

New Version of Perl on Windows Platforms

Compatibility Considerations: Yes

MATLAB Version 7.6 (R2008a) includes Perl on Windows Version 5.8.8.

Compatibility Considerations

Prior to this release, MATLAB contained Perl Version 5.005. Consult your Perl documentation for details on the changes between Perl versions.

Rebuild MEX-Files Created on Linux Platforms

Compatibility Considerations: Yes

MATLAB V7.6 (R2008a) on Linux platforms is built with a compiler that utilizes glibc Version 2.3.6.

Compatibility Considerations

To work with MATLAB V7.6 (R2008a), MEX-files compiled on a Linux platform must be rebuilt.

Use mxDestroyArray to Release Memory for mxArray

Compatibility Considerations: Yes

The documentation for the `mxSetCell`, `mxSetField`, and `mxSetFieldByNumber` functions in the MATLAB C and Fortran API incorrectly instructs customers to use `mxFree` to release memory for any `mxArray` returned by `mxGetCell`, `mxGetField`, or `mxGetFieldByNumber`.

Compatibility Considerations

The correct function to use is `mxDestroyArray`. Calling `mxFree` on an `mxArray` only frees the array header, but does not actually free the data itself and can result in a memory leak.

To help diagnose this problem, MATLAB issues a warning if calling `mxFree` on an `mxArray` could cause memory corruption. In future versions of MATLAB, this condition may result in a segmentation violation.

Do Not Use get or set Function to Manage Properties of Java Objects

Compatibility Considerations: Yes

If you want to read or update a property of a Sun Java object created in MATLAB using the Java class constructor, do not use the MATLAB `get` or `set` functions on the property. For example, if you create a Java object called `javaObject` that has a property called `PropertyName`, the following commands may cause memory leaks and will be deprecated in a future version of MATLAB:

```
propertyValue = get(javaObject, 'PropertyName');  
set(javaObject, 'PropertyName', newValue);
```

Compatibility Considerations

The correct commands to use are:

```
propertyValue = javaObject.getPropertyName;  
javaObject.setPropertyName(newValue);
```

In future versions of MATLAB, using `get` or `set` on Java objects to manage the properties will generate an error.

New mxArray Functions for Use with MATLAB Class Objects

You can read and modify properties of MATLAB class objects using the `mxGetProperty` and `mxSetProperty` functions.

mex.bat File Removed from matlabroot\bin\\${ARCH}

Compatibility Considerations: Yes

Beginning with MATLAB Version 7.3 (R2006b), the Windows script `mex.bat` is located in the directory `matlabroot\bin`. Copies of this file were also in the directory `matlabroot\bin\${ARCH}`. In MATLAB Version 7.6 (R2008a), `mex.bat` is only located in `matlabroot\bin`.

Compatibility Considerations

If you did not make the updates described in “Location of mex.bat File Changed” on page 896, you may need to make changes now.

Run-time Libraries Required for Applications Built with Microsoft Visual Studio 2008 Compiler

If you distribute a MEX-file, an engine application, or a MAT-file application built with the Visual Studio 2008 compiler, you must provide the Visual C++ run-time libraries. These files are required to run applications developed with Visual C++ on a computer that does not have Visual C++ 2008 installed. For information on locating the Microsoft Visual C++ 2008 Redistributable Package (x86), containing `vcredist_x86.exe` and `vcredist_x64.exe`, consult your Microsoft documentation.

Environment Variables Required with Intel Visual Fortran 9.0

When you build a MEX-file, an engine application, or a MAT application using Intel Visual Fortran 9.0, MATLAB requires that you define an environment variable for the Windows platform you are using.

Windows (32-bit) platform

Define the environment variable `VS71COMNTOOLS`. The value of this environment variable is the path to the `Common7\Tools` directory of the Microsoft Visual Studio .NET 2002 or 2003 installation directory. (Intel Visual Fortran requires Visual Studio .NET 2002 or 2003 on 32-bit Windows platforms.) The Visual Studio .NET 2003 installation program commonly defines this environment variable. For example, you might set the environment variable as follows:

```
C:\Program Files\Microsoft Visual Studio .NET 2003\Common7\Tools
```

Windows x64 platform

Define the environment variable `MSSdk`. The value of this environment variable is the path to the installation directory for Microsoft Platform SDK for Windows Server® 2003. (Intel Visual Fortran requires Microsoft Platform SDK for Windows Server 2003 on Windows x64 platforms.) The Microsoft Platform SDK installation program does not commonly define this environment variable. For example, the environment variable might have the value

```
C:\Program Files\Microsoft Platform SDK
```

-largeArrayDims Option to MEX Will Become Default

Compatibility Considerations: Yes

In a future version of MATLAB, the default `mex` command will change to use the large-array-handling API. This means the `-largeArrayDims` option will be the default. For information about migrating your MEX-files to use the large-array-handling API, see the Technical Support solution 1-5C27B9.

Compatibility Considerations

In the near future you will be required to update your code to utilize the new API. You should review your source MEX-files and `mex` build scripts.

Changes to Dynamic Data Exchange (DDE) Documentation

Compatibility Considerations: Yes

In MATLAB Version 5.1, all development work for the Dynamic Data Exchange (DDE) server and client was stopped. MathWorks provides, instead, a MATLAB interface to COM technology that is documented in Using COM Objects from MATLAB .

Obsolete Functionality No Longer Documented

Documentation for the following functions no longer included in External Interfaces.

Obsolete Functions
ddeadv
ddeexec
ddeinit
ddepoke
ddereq
ddeterm
ddeunadv

The following syntax for `enableservice` no longer included in External Interfaces.

```
enableservice('DDEServer',enable)
```

Compatibility Considerations

If you must support this obsolete functionality, we suggest you print and keep a copy of the relevant MATLAB function reference pages from V7.5 (R2007b) or earlier.

R2007b

Version: 7.5
New Features: Yes
Bug Fixes: Yes

Desktop Tools and Development Environment

Startup and Shutdown

Compatibility Considerations: Yes

Windows Platforms Startup Changes

You can now change the MATLAB startup directory on Microsoft Windows platforms using the standard shortcut **Start in** field. The My Documents\MATLAB subfolder (or Documents\MATLAB on the Microsoft Windows Vista platform) is the default startup directory. Upon startup, MATLAB automatically creates a My Documents\MATLAB subfolder (or Documents\MATLAB on the Windows Vista platform) if it does not exist, and adds it to the top of the MATLAB search path. To change the startup directory:

- 1** Right-click the MATLAB shortcut icon and select **Properties** from the context menu. The MATLAB Properties dialog box opens to the **Shortcut** pane.
- 2** In the **Start in** field, specify the directory in which you want MATLAB to start, for example, C:\My MATLAB Place.

You can specify the directory via a UNC path (that is, the path can begin with \\).

The **Target** field specifies the full path to the file to start MATLAB, `matlab.exe`, located in the `bin` folder (for example, `C:\Program Files\MATLAB\R2007b\bin\matlab.exe`). Use the `bin\matlab.exe` to start MATLAB instead of `matlab.bat` or `matlab.exe` located in a platform directory such as `bin\win32`. The `bin\matlab.exe` detects the Windows platform and ensures required run-time files are installed.

Compatibility Considerations

The **Target** field no longer contains the `-sd $documents` startup option. In MATLAB Version 7.4 (R2007a), the startup directory was specified via the `-sd` startup option in the **Target** field. You had to specify the directory via a mapped drive. Any value in the **Start in** field was ignored.

The file to start MATLAB, as specified in the **Target** field, was `matlab.bat`.

Change any scripts you use to start MATLAB to specify the full path to `bin\matlab.exe`. If you use `matlab.bat` in R2007b, MATLAB issues a warning message instructing you to use `matlab.exe` instead.

If scripts include the `-sd` startup option to specify the startup directory, that will be the startup directory, even if a directory is specified in the **Start in** field.

Desktop

Compatibility Considerations: Yes

New features and changes introduced in Version 7.5 (R2007b) are:

- “Minimizing Tools in the Desktop Now Supported on Macintosh Platforms” on page 671
- “Double-Click to Maximize or Restore Minimized Tools in Desktop” on page 671
- “New Desktop Layout — All but Command Window Minimized” on page 672
- “Start Button Now Includes New Category for Links and Targets” on page 673
- “Start Button — View Source Files Renamed” on page 673
- “Changes to Look of Buttons in Desktop and Other Tools” on page 673
- “Antialiasing Option No Longer Necessary on Windows and Macintosh Platforms” on page 673

Minimizing Tools in the Desktop Now Supported on Macintosh Platforms

You can now minimize tools in the desktop on Apple Macintosh platforms. It was introduced for other platforms in a previous version.

Double-Click to Maximize or Restore Minimized Tools in Desktop

After you minimize a tool within the desktop, you can now:


- Restore the tool to its former position by double-clicking the button.
- Drag a button to move its position—drag it to another edge of the desktop or to a new position within the edge where it’s currently located.
- Restore the tool by dragging the button to a location within the desktop, or outside the desktop to undock the tool.

Similarly, you can double-click a tool's title bar to maximize the tool in the desktop; then double-click the title bar again to restore it to its former position. (The capability was introduced in R2007a, MATLAB Version 7.4).

For more information, see [Open and Rearrange Desktop Tools and Documents](#).

New Desktop Layout – All but Command Window Minimized

Select **Desktop > Desktop Layout > All but Command Window Minimized** to arrange the desktop as shown here. The Command Window is open in the desktop, and all other desktop tools are open, but minimized.



Start Button Now Includes New Category for Links and Targets

In the Start button, there is a new category for Link and Target products. Select **Start > Links and Targets**, and then select one of the products. In previous versions, you accessed these products from the Toolboxes or Simulink software categories.

You also use this new category when running demos, or accessing **Demos** or **Contents** in the Help browser. For more information, see “Demos and Help Browser Contents Now Include New Category for Links and Targets” on page 675.

Start Button – View Source Files Renamed

To add your own toolboxes to the **Start** button, select **Start > Desktop Tools > View Start Button Configuration Files**. In previous versions, this menu item was **View Source Files**. There has been no change in functionality or features.

Changes to Look of Buttons in Desktop and Other Tools

Some icons on toolbar buttons have changed slightly. In addition, standard desktop icon image files are no longer provided in the *matlabroot/toolbox/matlab/icons* directory.

Compatibility Considerations

If your code relied on icon files in the *matlabroot/toolbox/matlab/icons* directory (for example, for adding your entries to the **Start** button or the Help browser), you might need to use other image files.

Antialiasing Option No Longer Necessary on Windows and Macintosh Platforms

MATLAB now follows the operating system’s font settings on Microsoft and Macintosh platforms. This provides smooth fonts without the need for antialiasing within MATLAB.

Running Functions – Command Window and History

New features and changes introduced in Version 7.5 (R2007b) are:

- “Command History — Find Entry by Letter Now Looks in Collapsed Sessions” on page 674
- “Pop-Up Help for a Function in the Command Window” on page 674

Command History – Find Entry by Letter Now Looks in Collapsed Sessions

When you type letters in the Command History, it finds and selects the next entry that begins with the letters you typed. Now, if the entry is in a session that was collapsed, MATLAB automatically expands the session and selects the matching entry in it. In previous versions, MATLAB did not find matching entries in collapsed sessions.

If you do *not* want to find entries in collapsed sessions (the previous behavior), you can instead select **Edit > Find**, which finds text in the Command History, but not in collapsed sessions. For more information, see Quick Search for Entries Beginning with Specified Letters or Numbers.

Pop-Up Help for a Function in the Command Window

For more information, see “Help on Selection Enhanced in Command Window and Editor” on page 677.

Help

New features and changes introduced in Version 7.5 (R2007b) are:

- “Minor Visual Changes to Help Browser” on page 675
- “Demos and Help Browser Contents Now Include New Category for Links and Targets” on page 675
- “Help on Selection Enhanced in Command Window and Editor” on page 677

Minor Visual Changes to Help Browser

- To open the Help browser from a tool’s **Help** menu, select **Product Help**. In previous versions you selected **Full Product Family Help**.
- When the Help browser first opens, it displays help for MATLAB. In previous versions, it displayed a Begin Here page. The information previously available on the Begin Here page has been incorporated into the MATLAB roadmap page.
- When you close and reopen the Help browser, it maintains the list of pages you previously viewed, but does not open to the page you last viewed. In previous versions, upon reopening, the Help browser displayed the page you last viewed.


Demos and Help Browser Contents Now Include New Category for Links and Targets


When you run the demo function or access **Demos** or **Contents** in the Help browser, there is a new category for Link and Target products.


To use the `demo` function to access a demo that is now in the Links and Targets category, you specify the new subtopic 'links and targets', followed by the category. For example

```
demo('links and targets', 'link for modelsim')
```

displays the **Demos** pane, and expands the Link for ModelSim® demos listing.

In the Help **Demos**, Link and Target products appear together in their own category, and are identifiable by the new Links and Targets icon, .

In the Help **Contents**, Link and Target products appear together after any installed Simulink and blockset products, and are identifiable by the new Links and Targets green book icon, .



This new category is also used in the **Start** button in the MATLAB desktop—for more information, see “Start Button Now Includes New Category for Links and Targets” on page 673.

If you add help or demos to the Help browser for your own toolbox or list your own toolbox in the **Start** button and you want to take advantage of the new Links and Targets category, use the new type, `links_targets`, in the `info.xml` file for your toolbox.

Compatibility Considerations


In previous versions, when you used the `demo` function to access a demo that is now in the Links and Targets category, you specified a different subtopic and category. If you have any code that relies on the `demo` function for accessing Links and Targets demos, you will need to replace the subtopic and category in the code.

In previous versions, you accessed the products in the Help browser **Demos** from the Toolbox or Simulink software categories.

In previous versions, you accessed the products in the Help browser **Contents** from within the list of toolbox products (orange book icon) or Simulink products (blue book icon).

Help on Selection Enhanced in Command Window and Editor

To get help for a function in the Command Window or the Editor, click the pointer in the function name and press **F1**. The reference page for that function appears in a small help window. To close the window, press **Escape**. You can also access the feature by choosing **Help on Selection** from the context menu. To change the window in which this help appears, select **File > Preferences > Help**, and adjust the option for **Help on Selection and More Help**.



Compatibility Considerations

In the previous version, you could select the function name, right-click, and select **Help on Selection**. The documentation appeared in the Help browser. Now if you want to see the documentation for the function in the Help browser, first access the pop-up help, and then click the **Open Help Browser** link.


Editing and Debugging M-Files


New features and changes introduced in Version 7.5 (R2007b) are:

- “Run Your Function M-Files in the Editor/Debugger Using Configurations” on page 680
- “Run/Continue Button Changes” on page 681
- “Code Folding Feature for Collapsing and Expanding Code” on page 682
- “Quick Help for a Function in the Editor” on page 684
- “Line Endings Removed in Files Provided with MATLAB Software for Windows Platforms; Impacts Viewing in Notepad Application” on page 684
- “Stand-Alone Editor Will Not Be Included in Next Version” on page 687
- “Determine the McCabe (Cyclomatic) Complexity of an M-File” on page 688

Run Your Function M-Files in the Editor/Debugger Using Configurations

In the Editor/Debugger, you can provide values for a function’s input arguments using a configuration, and then run that configuration to use the assigned values. Use a configuration as an alternative to running the function in the Command Window. You can associate multiple configurations with an M-file, each for different input values. MATLAB saves the configurations between sessions.


To create a configuration, first open an M-file in the Editor/Debugger. Then, from the down arrow on the Run button in the toolbar  select **Edit Configurations for *filename***. In the resulting Edit M-File Configurations dialog box, add statements and name the configuration. For more information, see Run Files with Input Arguments in the Editor.




Run/Continue Button Changes

The Run/Continue button has a new look and new location on the Editor/Debugger toolbar.

New look and position of Run/Continue button



Run/Continue button in previous versions




Compatibility Considerations

The button performs the same as it did in previous versions, but you need to access it in the new position.

Code Folding Feature for Collapsing and Expanding Code

To improve the readability of files containing several subfunctions, the Editor includes a code folding feature, which is enabled by default. Using this feature you can collapse and expand subfunctions and their associated help. The following figure shows the `collatzplot_new` function collapsed, such that only the function definition is displayed. The figure shows the `collatz` function expanded, revealing both the help code and the function code. If you collapse just the help code, only the H1 help line displays.



- To expand code that is collapsed, click the plus sign (+) to the left of the code you want to expand.
- To collapse code that is expanded, click the minus sign (-) to the left of the code you want to collapse.
- To expand or collapse all of the code in an M-file, place your cursor anywhere within the M-file, right-click, and then select **Code Folding > Expand All** or **Code Folding > Collapse All** from the context menu.

For more information, see [Code Folding—Expanding and Collapsing M-File Constructs](#)

Quick Help for a Function in the Editor

For more information, see “[Help on Selection Enhanced in Command Window and Editor](#)” on page 677.

Line Endings Removed in Files Provided with MATLAB Software for Windows Platforms; Impacts Viewing in Notepad Application

In previous versions, text files provided with MATLAB for Windows platforms included a carriage return and line feed at the end of each line. Starting in R2007b, the text files MATLAB provides do not include a carriage return and line feed at the end of each line.

File types affected are:

- .asc
- .bat
- .c
- .cc
- .cdr
- .cpp
- .def
- .for

- `gs.rights`
- `.h`
- `.ini`
- `.m`
- `.mdl`
- `.pl`
- `readme`
- `.tlc`
- `.tmf`
- `.txt`

There is no impact if you view the files in MATLAB and other common text editors, with the known exception of the Microsoft Notepad application.

Compatibility Considerations


If you use the Notepad application to view files provided with MATLAB, you see carriage return and line feed symbols `␣%` instead of line endings. This makes the files less readable in the Notepad application. Other text editors might display the symbols instead of line endings, but of the common text editors tested, none have been found that do so.

As an alternative to the Notepad application, use the Microsoft WordPad application, provided with Windows platforms, or another text editor to view the files.

If your Windows file associations are set to associate any of the listed file types with Notepad, change the associations to use WordPad or another text editor.

The following illustration shows how the `ver` M-file included with MATLAB Version 7.5 looks when opened in the Notepad application.

M-file from MATLAB Version 7.5 when opened in Notepad shows symbols instead of line endings.




The screenshot shows a Notepad window titled 'ver.m - Notepad'. The menu bar includes 'File', 'Edit', 'Format', 'View', and 'Help'. The text content is as follows:

```
function varargout=ver(arg)%VER MATLAB, Simulink and toolbox
version information.% VER displays the current MATLAB, Simulink
and toolbox version information.% VER(TOOLBOX_DIR) displays the
current version information for the% toolbox specified by the
string TOOLBOX_DIR.% A = VER displays the general MATLAB version
header and return in A the% sorted struct array of version
information on all toolboxes on the% MATLAB path.% The
definition of struct A is:% A.Name : toolbox name%
A.Version : toolbox version number%
A.Release : toolbox release string% A.Date :
toolbox release date% For example,% ver control%
displays the version info for the Control System Toolbox, sorted %
alphabetically.% A = ver('control');% returns in A
the version information for the Control System Toolbox, %
sorted alphabetically.%% For tips on how to get VER to display
version information about% your toolbox, type at the MATLAB
prompt% more on% type ver.m% and then type 'more
off' when the display of ver.m has finished.%% See also HOSTID,
INFO, LICENSE, verLessThan, VERSION, WHATSNEW.% Tips on how to
```

The following illustration shows how the ver M-file included with MATLAB Version 7.5 looks when opened in the WordPad application.

M-file from MATLAB Version 7.5 when opened in WordPad shows line endings.



The screenshot shows a WordPad window titled 'ver.m - WordPad'. The menu bar includes File, Edit, View, Insert, Format, and Help. The toolbar contains icons for file operations and editing. The text area displays the following code with visible line endings (carriage returns):

```
function varargout=ver(arg)
%VER MATLAB, Simulink and toolbox version information.
% VER displays the current MATLAB, Simulink and toolbox version information.
% VER(TOOLBOX_DIR) displays the current version information for the
% toolbox specified by the string TOOLBOX_DIR.
% A = VER displays the general MATLAB version header and returns a
% sorted struct array of version information on all toolboxes on the
% MATLAB path.
% The definition of struct A is:
%     A.Name       : toolbox name
%     A.Version    : toolbox version number
%     A.Release    : toolbox release string
%     A.Date       : toolbox release date
```

At the bottom of the window, it says 'For Help, press F1' and there is a 'NUM' button.

There are no problems with files you create or edit in the Notepad application, and then view or edit in MATLAB. The files have line endings in the MATLAB Editor, and continue to have line endings when you open them in the Notepad application.

(Microsoft product screen shot(s) reprinted with permission from Microsoft Corporation.)

Stand-Alone Editor Will Not Be Included in Next Version

The MATLAB stand-alone Editor (`meditor.exe`) will no longer be provided, starting in the next version of MATLAB. Instead of the stand-alone Editor, you can use the MATLAB Editor/Debugger. It provides all the features of the stand-alone Editor, plus the following:

- Tab completion

- Debugging M-files
- Evaluating selections
- Accessing source control features
- Docking the tool in the MATLAB desktop
- Using cell features for rapid code iteration or publishing

Compatibility Considerations

Some users have preferred the stand-alone Editor to the MATLAB Editor/Debugger because of slightly better startup performance and because it does not require a MATLAB license. For those situations, you can use any text editor you have, such as the UltraEdit® application from IDM Computer Solutions, or the GNU Emacs software.

Determine the McCabe (Cyclomatic) Complexity of an M-File

The `cyc` option to the `mlint` function enables you to determine the McCabe complexity (also referred to as the cyclomatic complexity) of an M-file. Higher McCabe complexity values indicate higher complexity, and there is some evidence to suggest that programs with higher complexity values are more likely to contain errors. Frequently, you can lower the complexity of a function by dividing it into smaller, simpler functions. In general, smaller complexity values indicate programs that are easier to understand and modify. Some people advocate splitting up programs that have a complexity rating over 10. See `mlint` for syntax and an example.

Publishing Results

New features and changes introduced in Version 7.5 (R2007b) are:

- “Notebook and Word for Office 2007” on page 689
- “Text Markup in Cells for Publishing” on page 689
- “Preference to Restrict Lines of Output” on page 690

Notebook and Word for Office 2007

Notebook now supports Microsoft Word for Office 2007. For details, see [Creating a MATLAB Notebook to Publish to Microsoft Word](#).

Text Markup in Cells for Publishing

The following Editor/Debugger menu items are added to assist you in marking up cells in the Editor/Debugger for publishing. Access the menu items presented in the following list from **Cell > Insert Text Markup**. When you select the menu item, the Editor inserts code to assist you in adding the text markup for the specified item.

- **Document Title and Introduction**
- **Section Title with Cell Break**
- **Hyperlinked Text**
- **Image**
- **Numbered List**
- **HTML Markup**
- **LaTeX Markup**

The first two list items are provided instead of the **Cell Title** and **Descriptive Text** menu items that were offered in Version 7.4 (R2007a).

As an alternative to using the Cell menu items, you can manually insert code to mark up cells in your M-file for publishing. For details on the Cell menu items and the resulting code see [Marking Up Text in Cells for Publishing](#)

Preference to Restrict Lines of Output

You can now specify options to restrict the number of lines included in the output of a published M-file. To access this option from the Editor/Debugger, follow these steps:

- 1** Select **File > Preferences > Editor/Debugger > Publishing**
- 2** In the Editor/Debugger Publishing Preferences pane, select the **Evaluate code** and **Restrict output to** options.
- 3** Specify the maximum number of lines that you want to include in the output.

Mathematics

New Functions

Function	Description
quadgk	Numerically evaluates the integral, adaptive Gauss-Kronrod quadrature
bvp5c	Solves boundary value problems for ordinary differential equations, notably useful for small error tolerances
maxNumCompThreads	Gets and sets the maximum number of computational threads

finite Function Deprecated

Compatibility Considerations: Yes

In this release, the `finite` function displays a warning message that the function is now deprecated. Support for `finite` will be removed in a future release of MATLAB software.

Compatibility Considerations

It is recommended that you replace all calls to `finite` with the `isfinite` function.

dmperm Function Gives Coarse Decomposition

The `dmperm` function now provides two additional output arguments for the indices of the Dulmage-Mendelsohn coarse decomposition.

ldl Function Supports Real Sparse Symmetric Matrices

The `ldl` function now provides factorization and solving for an additional output argument, the scaling matrix, when the input matrix is real sparse and symmetric.

Upgrade to LAPACK Library

MATLAB software now uses Version 3.1 of the Linear Algebra Package (LAPACK) library.

Upgrade to BLAS Libraries

For AMD processors, MATLAB software now uses Version 3.6 of the AMD Core Math Library (ACML™) for the Basic Linear Algebra Subroutine (BLAS) libraries.

Library for LAPACK and BLAS Symbols Separated

Compatibility Considerations: Yes

The binder library, `libmwapack.lib`, containing both LAPACK and BLAS symbols is now two separate library files: `libmwapack.lib` for LAPACK symbols and `libmwblas.lib` for BLAS symbols.

Compatibility Considerations

If you previously linked to the `libmwapack.lib` library to use the BLAS symbols, you will need to update your code to link to the `libmwblas.lib` library.

Colon Operations on Characters Return Character Type Data

Compatibility Considerations: Yes

Using a colon with characters to iterate a for-loop now returns data of type character. For example,

```
for x='a':'b',x,end
```

results in

```
x =  
  a  
x =  
  b
```

Compatibility Considerations

Previously, colon operations with characters iterating a for-loop returned data of type double. In previous releases the above example returned:

```
for x='a':'b',x,end
```

```
x =  
  97  
x =  
  98
```

Existing program code that relies on the colon operations of character arrays returning a double, needs to be updated to expect a character data type.

Matrix Generating Functions No Longer Accept Complex Inputs

Compatibility Considerations: Yes

Calling matrix generating functions, such as ones, zeros, rand, randn, true, and false, with a complex number as dimensions input now returns the error:

```
true([1 i])  
??? Error using ==> true  
Size vector must be a row vector with real elements.
```

Compatibility Considerations

In previous releases, if you supplied a complex number as a dimension input, MATLAB software returned:

```
true([1 i])  
Warning: Size vector should be a row vector with integer elements.  
         Complex inputs will cause an error in a future release.  
  
ans =  
  
     Empty matrix: 1-by-0
```

Existing program code that relies on entering complex numbers as dimension input to a matrix generating function should be modified.

Data Analysis

Programming

Increased Size for Large Arrays

On 64-bit platforms, MATLAB arrays are no longer limited to 2^{31} elements. The limit in MATLAB 7.5 is $2^{48}-1$. For example, given sufficient memory, many numeric and low-level file I/O functions now support real double arrays greater than 16 GB.

Documentation for Multiprocessing in MATLAB

Documentation for “Multiprocessing in MATLAB” has moved from Desktop Tools and Development Environment to the “Improving Performance and Memory Usage” section of MATLAB Programming.

Setting Number of Threads Programmatically

In this release, MATLAB provides a way to set or retrieve the maximum number of computational threads from within an M-file program. With the `maxNumCompThreads` function, you can either set the maximum number of computational threads to a specific number, or indicate that you want the setting to be done automatically by MATLAB

New Internal Format for P-code

Compatibility Considerations: Yes

P-code files have a new internal format in MATLAB Version 7.5. The new P-code files are smaller and more secure than those built with MATLAB 7.4 and earlier, and provide a more robust solution to protect your intellectual property.

Any P-code files that were built using MATLAB 7.4 or earlier also work in 7.5. However, support for these older files will at some point be removed from MATLAB.

P-code files built with MATLAB 7.5 only work on 7.5 or later. They cannot be used with MATLAB 7.4 or earlier versions.

Compatibility Considerations

Rebuild any P-code files using MATLAB 7.5 that you expect to need in the future.

New Split String Functionality in regexp

Using the regular expressions function `regexp`, you can now split an input string into sections by specifying the new `'split'` option when calling `regexp`:

```
s1 = ['Use REGEXP to split ^this string into ' ...  
      'several ^individual pieces'];  
  
s2 = regexp(s1, '\^', 'split');  
  
s2(:)  
ans =  
      'Use REGEXP to split '  
      'this string into several '  
      'individual pieces'
```

The `split` option returns those parts of the input string that are delimited by those substrings returned when using the `regexp` `'match'` option.

Changes Related to Error Handling

New Error Handling Mechanism

MATLAB extends its error-handling capabilities with the new `MException` class to provide you with a more secure and extensible system for throwing and responding to errors. Read about this new feature in the Error Handling section of the MATLAB Programming documentation and in related function reference pages such as `MException`.

This feature *extends* the error-handling capabilities available in earlier releases, but does not replace that functionality. Your M-file programs will continue to function the same when using Version 7.5.

New Syntax for catch Function

As part of new error-handling mechanism, the `catch` function has a new, optional syntax as shown here in a try-catch statement:

```
try
    % Try to execute this block of code. Go to 'catch' on error
    - code that may error -
catch ME
    % Deal with the error captured in MException object, ME
    - code to handle the error -
end
```

`ME` is an object of the `MException` class. This command gives you access to the `MException` object that represents the error (i.e., exception) being caught.

Warning and Error Messages Now Wrap

In previous versions of MATLAB, warning and error messages that were longer than the width of your terminal screen extended beyond the visible portion of your screen. These messages now wrap onto succeeding lines so that the entire text of the warning or error is visible.

Change to Error Message from Anonymous Function

The error message and M-file line number that MATLAB displays when encountering an error in an anonymous function defined within a script

file or at the MATLAB Command Line has changed in this release. In MATLAB Version 7.4, the error message included the line number (set to 1 for anonymous functions), and the stack information returned by the `lasterror` function also showed the line number as 1. In MATLAB 7.5, the line number is not displayed in the error message and is set to 0 in the returned stack information.

For example, when you enter the following two lines at the command line, MATLAB generates an error from the anonymous function:

```
X = @() error('* Error *');
X()
```

This example shows the difference between MATLAB Versions 7.4 and 7.5:

```
e = lasterror;

e.message
ans =
Error using ==> @()error('Error') at 1      % V7.4 response
Error using ==> @()error('Error')          % V7.5 response
* Error *

e.stack
ans =
    file: ''
    name: '@()error('* Error *')'
    line: 1                                % V7.4 response
    line: 0                                % V7.5 response
```

Compatibility Considerations

If you have programs that rely on the line number returned in response to an error in an anonymous function, these programs may not work as expected. Remove dependencies on the returned error message and line number, or update your program code to use the new string and value.

New Message In Response to Ctrl+C

MATLAB now displays a more user-friendly message when you press **Ctrl+C**. The previous response to **Ctrl+C** was

```
Error in ==> testctrlc>waitawhile at 5  
pause(100);
```

```
Error in ==> testctrlc at 2  
waitawhile
```

In this and future releases, pressing **Ctrl+C** still halts program execution, but now displays the response

```
??? Operation terminated by user during ==> testctrlc>  
waitawhile at 5
```

```
In ==> testctrlc at 2  
waitawhile
```

Compatibility Considerations

You only need to be aware that the change in the text of this message is intentional and does not signify any error on your part.

hdfread Errors Instead of Warns on I/O Failures

In previous releases, `hdfread` issued a warning when a requested I/O operation failed. In addition, `hdfread` created an empty variable in the workspace. In this release, `hdfread` now errors when a requested I/O operation fails and does not create an empty variable in the workspace.

Compatibility Considerations

If you call `hdfread` in a script to perform an I/O operation and that operation fails, your script will now terminate. Previously, because `hdfread` only warned when an I/O operation failed, your script would continue processing.

Results From tempname Are More Unique

Compatibility Considerations: Yes

The tempname function now produces a string such as

```
C:\Temp\tpe51f2ba3_9ad3_490f_8142_58359c98f4a5
```

when Java is present, or a string like

```
C:\Temp\tp346976948758473
```

when nojvm is selected. Underscores are included in the name so you can use the filename portion of it as a valid M-function name. If a string row vector is passed in as an argument, that string is used instead of tempdir as the root.

Compatibility Considerations

Because the new string generated by tempname is generally longer than the string constructed in earlier versions, there is a possibility of exceeding length restrictions, especially if your program code passes a string to the tempname function. If you consider this to be a potential problem, verify that the strings you pass to tempname will not result in an overly long string being returned.

MATLAB Includes New Input Argument Validation Functions

MATLAB now includes two new functions that validate the input arguments passed to functions. For example, you can use these functions to make sure that an input argument is numeric and nonempty. The following table lists these functions with a brief description.

Function	Description
<code>validateattributes</code>	Check validity of array
<code>validatestring</code>	Check validity of text string

Windows Current Working Directory Corrected

Compatibility Considerations: Yes

On Windows, you can define a current working directory, `cwd`, for each drive letter. For example, entering the command `cd D:\work` at the DOS prompt defines your D current working directory as `D:\work`. All references to `D:` are then relative to this directory.

The term . . .	Represents the directory . . .
<code>D:</code>	<code>D:\work</code>
<code>D:matlab</code>	<code>D:\work\matlab</code>
<code>D:\matlab</code>	<code>D:\matlab</code>

(Note the difference between `D:\` and `D:`, where the former is the drive D, and the latter is a user-defined working directory that may or may not be equal to `D:\`.)

Previous versions of MATLAB have been inconsistent in the way that volume-relative path specification is handled. For example, in MATLAB 7.4 and earlier, if `D:` were defined as the directory `D:\work`, the following commands on the left and right returned identical results:

```
dir D:                                dir D:\
dir D:matlab                          dir D:\work\matlab
fileparts('D:myfile.m')              fileparts('D:\myfile.m')
```

This has been fixed in MATLAB 7.5 so that the following are now equivalent:

```
dir D:                                dir D:\work
dir D:matlab                          dir D:\work\matlab
fileparts('D:myfile.m')              fileparts('D:\work\myfile.m')
```

Compatibility Considerations

Some MATLAB commands may fail or return unexpected results if you use Windows current working directories on MATLAB. You might have to update hard-coded paths if you have been relying on the incorrect behavior exhibited in earlier versions.

New Multimedia Functionality

A new `mmreader` video file reader object for Windows platforms supports formats such as AVI, MPEG, and WMV, and adds the ability to read additional video codecs that `aviread` does not support. For more information, see the `mmreader` and `read` reference pages.

Compressed AVI Video Files in Windows Vista and Windows XP x64

Compatibility Considerations: Yes

Because Windows Vista, Windows Vista 64-bit, and Windows XP x64 operating systems do not ship with the Indeo® 5 codec, which is the default codec used by MATLAB Audio-Video functions for file compression, the functions `movie2avi` and `avifile` now generate uncompressed AVI files on these platforms. Also, `aviread` on these platforms cannot read files that were compressed using the Indeo 5 codec.

Compatibility Considerations

If you have upgraded your Windows operating system to Windows Vista, Windows Vista 64-bit, or Windows XP x64, you need to install the Indeo 5 codec to read or create Indeo 5 compressed AVI files with `aviread`, `avifile`, or `movie2avi`. You can learn more about downloading the Indeo 5 codec from the Ligos Corporation Web site at <http://ligos.com/index.php/home/products/indeo/>

mmfileinfo Reads Files on MATLAB Path

Compatibility Considerations: Yes

The `mmfileinfo` function now reads files on the MATLAB path, not only those in the current directory. The `mmfileinfo` output struct contains a field called `Path`, which indicates the directory where the file exists.

Compatibility Considerations

The `Filename` field of the output struct from `mmfileinfo` now contains only the filename itself without any path information, while the path information is contained in the `Path` field. In previous releases, the `Filename` field contained both path and filename information.

Changes to imread Support of TIFF Format

The `imread` function includes several updates to its TIFF support:

- `imread` reads TIFF files that use JPEG, LZW, and Deflate compression.
- `imread` reads image data from TIFF files in any arbitrary samples-per-pixel and bits-per-sample combination.
- `imread` provides increased performance when reading large images, when used with the 'PixelRegion' parameter.

Removal of freeserial Function

Compatibility Considerations: Yes

The `freeserial` function is now obsolete. Use `fclose` to release the serial port.

Compatibility Considerations

If your program code still makes use of the `freeserial` function, replace each instance with the `fclose` function instead.

Graphics and 3-D Visualization

Datatypes Are Now Saved to FIG-Files

Compatibility Considerations: Yes

When you save a figure, all datatypes existing in it are saved along with other annotations. When you open the FIG-file, the datatypes are displayed and can be manipulated or deleted in the same ways they could in the original figure.

Compatibility Considerations

If you open a FIG-file containing datatypes while using a previous MATLAB version (V7.4 or earlier), no error results, but the datatypes do not display.

New Options for Displaying Groups of Lines in Legends

You can now customize how legends for figures display groups of lines, such as contours. Previously, legends displayed groups of lines such as contourgroups with a glyph that represented the entire group; now users have the flexibility to designate a single legend entry, a legend entry for each child of the group, or no legend entries for the group.

By default, a legend entry for an hggroup now consists of the `DisplayName` of its first child and a glyph representing it (previously, no glyph appeared, only the `DisplayName`). This is what you now see after clicking the legend tool icon in the figure's toolbar. However, you can set the new `Annotation` property of hggroups to control how the group is represented in a legend. For details and examples of its use in customizing legends, see [Controlling Legends](#) in the Graphics documentation.

Drawnow Update Option Now Updates Uicontrols Only

The drawnow command can now selectively update the display of UI components. The update option enables you to update only uicontrol objects without allowing callbacks to execute or processing other events in the queue.

Annotation Textboxes Can Automatically Resize to Fit their Contents

In previous releases, textboxes had fixed sizes that users needed to adjust to fit the size of their contents. Now, if you create a textbox annotation using a GUI or the annotation function, it can grow or shrink to just fit the text you type into it. This behavior is controlled by the Annotation Textbox object's `FitBoxToText` property, which can be 'on' or 'off'. When you create a textbox with the Annotation toolbar (using the **T** tool), this property is set to 'on' if you create a textbox without dragging; however, if you drag to make the new textbox have a certain size, the property is initially 'off'. When you create a textbox with the annotation function, for example,


```
htb = annotation('textbox')
```

without specifying a position and size, the textbox is created with `FitBoxToText` set to 'on'. If you specify a position vector in the command, for example,

```
htb = annotation('textbox', [.1 .8 .4 .1])
```

the textbox is created with `FitBoxToText` set to 'off'.

Similarly, if you resize a textbox in plot edit mode or change the width or height of its `position` property directly, its `FitBoxToText` property is set to 'off'. You can toggle this property with `set`, with the Property Inspector, or more conveniently, via the object's context menu, as the illustration below shows.



If you edit a textbox that has `FitBoxToText` set to 'on', the textbox resizes to accommodate the number of characters and lines in the text as you type. You can reposition the textbox without changing the `FitBoxToText` property, but as soon as you resize it, the property becomes (or remains) 'off'.

Property Inspector Now Has Context-Sensitive Help

When you use the Property Inspector (the `inspect` command), you can now ask for a description of any property it shows. The descriptions come from the property reference page for the type of object being inspected (e.g., axes, lineseries, annotations, uicontrols, etc.). To get a description of a property, right-click its name in the left-hand column of the Property Inspector and select **What's This?** from the context menu that appears. A mini-help window opens to show the property's description from the object's property reference page. If you need an overview of all properties pertaining to particular kinds of objects and how these objects relate, scroll through the entries in the mini-help window or open the Handle Graphics Property Browser from the Help Browser.

The “v6” Option for Creating Plot Objects is Obsolete

Compatibility Considerations: Yes

Prior to MATLAB Version 7, handles returned by high-level plotting functions referenced graphic primitives, such as lines and patches. In Version 7, MATLAB began bundling the primitives into “series” objects, for example, lineseries, barseries, and contourgroups. At that time, the v6 option was added to plotting functions to enable users of MATLAB Version 7.x to create FIG-files that previous versions can open. The v6 option is now obsolete. It will be removed in a future MATLAB release. The following functions include the option in their syntax and now warn when it is used:

- area
- bar
- barh
- colorbar
- contour
- contourf
- errorbar
- legend
- loglog
- mesh
- meshc
- meshz
- plot
- quiver
- scatter
- scatter3
- semilogx
- semilogy
- stairs

- stem
- stem3
- subplot
- surf
- surfc

Compatibility Considerations

Specifying the v6 flag to any plotting function now results in a warning that the option is being removed, but the option still functions. To generate a FIG-file for a plot created with the v6 option, you still need to use the -v6 option to the hgsave command in order to save it in a form that a previous version of MATLAB can read. Figures containing annotations (such as textboxes, arrows, ovals, and rectangles) that are saved this way open in previous versions, but the annotations do not display because different objects are used to contain them in Version 7 than before. That is, the annotation objects have never been backward compatible.

Creating Graphical User Interfaces (GUIs)

New Editors for Creating Custom Toolbars within GUIDE

In previous releases, adding toolbars to a GUI had to be done programmatically, by writing code for the `uitoolbar`, `uipushtool` and `uitoggletool` functions. GUIDE now has a Toolbar Editor and an associated Icon Editor that allow you to lay out a toolbar for a GUI and populate it with standard predefined tools for printing, saving, panning, zooming, annotating, etc. or with custom tools that you design yourself. You can draw or modify an icon for any tool on your toolbar with the Icon Editor or import one from an image file.

The Toolbar Editor

When you run GUIDE to create a new GUI or edit an existing one, click the Toolbar Editor icon in the Layout Editor Toolbar or choose **Toolbar Editor** from the **Tools** menu to open the Toolbar Editor. To add tools to the toolbar of your GUI, you drag standard or custom tool icons to the toolbar layout area at the top. You can modify a tool's properties using the Toolbar Editor and Property Inspector. You can also create and customize icons for tools using the new Icon Editor, described next. You control the behavior of a tool in your toolbar with its `ClickedCallback` (and for toggle tools, their `OnCallback` and `OffCallback`) in the GUI's associated M-file. If you use an existing tool, such as Print or Save, you do not need to modify its callback; it is predefined as `%default`.

The Icon Editor

The Icon Editor lets you customize the icons for existing tools or create entirely new icons. Icons are stored as `CData` for each tool, and can also be read from and saved to `.icn` files. The Icon Editor also includes a Color Editor, a palette you can use for picking predefined colors and defining new ones.

Coordinate Readouts in Layout Editor

The GUIDE Layout Editor now has two fields in its lower left corner that continuously provide numeric feedback for:

- **Current Point** — The cursor location within the layout window
- **Position** — The Position property of the currently selected object(s) in the layout window

Both measurements are given in pixels, regardless of the current Units settings for GUI objects. When multiple objects are selected, any elements of their Position properties that are not identical are read out as MULTI. The readouts help you to precisely size and align GUI components.

Documentation for Making GUIDE GUIs Interact

A new documentation section, Making Multiple GUIs Work Together, has been added to illustrate how multiple GUIDE GUIs can work together by sharing data to create a more complicated GUI. It first summarizes the techniques that GUIDE GUIs can use to share data with one another. It then steps through two examples, accompanied by their M-files and FIG-files, to show how to use those techniques for specific tasks.

Functions Being Removed

Compatibility Considerations: Yes

Function Name	What Happens When You Run the Function?	Use This Function Instead	Compatibility Considerations
axlimdlg	Errors	None	No replacement
cbedit	Errors	guide	Use the guide command instead
clruprop	Errors	rmappdata	Replace existing instances of clruprop with rmappdata
ctlpanel	Errors	guide	Use the guide command instead
edtext	Errors	Set the editing property on the text object	No replacement
extent	Errors	Get the extent property of the text object	No replacement
getuprop	Errors	getappdata	Replace existing instances of getuprop with getappdata
hthelp	Errors	web	Replace existing instances of hthelp with web
layout	Errors	None	No replacement
matq2ws	Errors	None	No replacement
matqdlg	Errors	None	No replacement

Function Name	What Happens When You Run the Function?	Use This Function Instead	Compatibility Considerations
matqparse	Errors	None	No replacement
matqueue	Errors	None	No replacement
menubar	Errors	Set the menubar property of the figure to none	No differences
menuedit	Errors	guide	Use the guide command instead
pagedlg	Errors	pagesetupdlg	Replace existing instances of pagedlg with pagesetupdlg
setupprop	Errors	setappdata	Replace existing instances of setupprop with setappdata
umtoggle	Errors	Set the Checked property of uimenu objects	No differences
wizard	Errors	guide	Use the guide command instead
ws2matq	Errors	None	No replacement

External Interfaces/API

Support for 64-bit mxArray

Compatibility Considerations: Yes

MATLAB Version 7.5 (R2007b) supports 64-bit mxArray. This change allows C/C++ and Fortran files built on 64-bit platforms to handle large data arrays.

In earlier versions of MATLAB, mxArray are limited to $2^{31}-1$ elements. In Version 7.5 (R2007b) your mxArray can have up to $2^{48}-1$ elements.

The mex command option, `-largeArrayDims`, uses the large-array-handling mxArray API. Use `mwSize` to represents size values, such as array dimensions and number of elements. Use `mwIndex` to represent index values, such as indices into arrays.

Compatibility Considerations

MEX-files that built properly in previous versions of MATLAB continue to build in Version 7.5 (R2007b).

The default option for mex is `-compatibleArrayDims`. If you use this option, mex builds the files using the 32-bit array-handling API.

To work with 64-bit mxArray, your C, C++ and Fortran source code must comply with the 64-bit array-handling API. To use the API to create C/C++ MEX-files, see [Handling Large mxArray](#) . To use the API to create Fortran MEX-files, see [Handling Large mxArray](#) .

Fortran MEX-Files Will Require mwSize and mwIndex

Compatibility Considerations: Yes

In a future version of MATLAB, the default `mex` command option will change to `-largeArrayDims`. Fortran MEX-files will be required to use the `mwSize` and `mwIndex` preprocessor macros

Compatibility Considerations

To make your Fortran MEX-file compatible with the `-largeArrayDims` option, and to create platform-independent code, you need to include the `fintrf.h` header file in your Fortran source files, and you need to name your source files with an uppercase `.F` file extension. For information on creating MEX-files, see the Gateway Routine in the Fortran MEX-Files topic.

Changes to the MATLAB Locale Setting

Retrieving and using the proper locale setting is a mandatory operation in creating and using applications for international audiences. In R2007b, MATLAB Version 7.5 standardizes the way it initializes the locale setting across platforms. As a result, on Microsoft Windows platforms, MEX-files that use C/C++ locale-dependent standard library functions should note that MATLAB now sets the locale using the `setlocale` function.

Because of changes to Microsoft Visual Studio, MEX-Files created on Windows with dMicrosoft Visual Studio 2003 will not have the same locale setting as MATLAB Version 7.5 (R2007b).

Note C/C++ users must not change the locale setting using the `setlocale` function. This is true for all versions of MATLAB on all platforms.

Changes to MEX Error-Handling Functions `mexErrMsgTxt` and `mexErrMsgIdAndTxt`

In MATLAB Version 7.5 (R2007b), the `mexErrMsgTxt` and `mexErrMsgIdAndTxt` functions determine where the error occurred, and display the function name. In previous versions, these functions only display the error message.

For example, if an error occurs in the function `foo`, `mexErrMsgTxt` and `mexErrMsgIdAndTxt` display the following information before the error message:

```
??? Error using ==> foo
```

Rebuild MEX-Files Created with MATLAB Versions Earlier Than V7 (R14)

To work with MATLAB V7.5 (R2007b), MEX-files compiled on any platform with MATLAB versions earlier than V7 (R14) no longer load correctly and must be rebuilt.

Changes to Compiler Support

Compatibility Considerations: Yes

The set of compilers that MATLAB supports has changed in MATLAB Version 7.5 (R2007b). For an up-to-date list of supported compilers, see the Supported and Compatible Compilers Web page.

- “New Compiler Support” on page 740
- “Discontinued Compiler Support” on page 740
- “Compiler Support to Be Phased Out” on page 741

New Compiler Support

MATLAB V7.5 (R2007b) supports new compilers for building MEX-files.

Windows platforms

- Microsoft Visual Studio 2005 SP1

Sun Solaris SPARC (64-bit) platform

- gcc / g++ Version 4.1.2

Discontinued Compiler Support

The following compilers are no longer supported.

Windows platforms

- Microsoft Visual Studio 2005 without SP1

Solaris SPARC (64-bit) platform

- gcc / g++ Version 3.2.3

Compatibility Considerations

To ensure continued support for building your C/C++ programs, consider upgrading to another supported compiler. For an up-to-date list of supported compilers, see the Supported and Compatible Compilers Web page.

Compiler Support to Be Phased Out

The following compilers are supported in Version 7.5 (R2007b), but will not be supported in a future version of MATLAB.

Windows (32-bit) platform

- Intel Visual Fortran Version 9.0
- Compaq Visual Fortran Version 6.6
- Intel C++ Version 7.1
- Borland C++Builder 6 Version 5.6
- Borland C++Builder 5 Version 5.5
- Borland C++ Compiler Version 5.5
- Compaq Visual Fortran Version 6.1

Changes to Applications Built with Borland 5.5 or 5.6 C Compilers

Compatibility Considerations: Yes

MATLAB applications built with Borland Version 5.5 or 5.6 C compilers have changed in MATLAB Version 7.5 (R2007b). MATLAB applications that run under Windows are now implemented as console applications, not Windows applications.

Compatibility Considerations

If you have customized the build process based on one of the `bcc*engmatopts.bat` options files, you must edit this file making changes to the appropriate `LINKFLAGS` statement, as described in the `.bat` file comments.

Environment Variable Required for mex with Microsoft Platform SDK Compiler

When you build a MEX-file, an engine application, or a MAT application on a Windows 64-bit platform using the Microsoft Platform SDK compiler, MATLAB requires that you define the environment variable `MSSdk`. The value of this environment variable is the path to the installation directory for Microsoft Platform SDK. The Microsoft Platform SDK installation program does not commonly define this environment variable. For example, you might set the environment variable as follows:

```
C:\Program Files\Microsoft Platform SDK
```

Environment Variables Required for mex with Intel Visual Fortran 9.0

When you build a MEX-file, an engine application, or a MAT application using Intel Visual Fortran 9.0, MATLAB requires that you define an environment variable for the Windows platform you are using.

Windows (32-bit) platform

Define the environment variable `VS71COMNTOOLS`. The value of this environment variable is the path to the `Common7\Tools` directory of the Visual Studio .NET 2002 or 2003 installation directory. (Intel Visual Fortran requires Visual Studio .NET 2002 or 2003 on 32-bit Windows platforms.) The Visual Studio .NET 2003 installation program commonly defines this environment variable. For example, you might set the environment variable as follows:

```
C:\Program Files\Microsoft Visual Studio .NET 2003\Common7\Tools
```

Windows x64 platform

Define the environment variable `MSSdk`. The value of this environment variable is the path to the installation directory for Microsoft Platform SDK for Windows Server 2003. (Intel Visual Fortran requires Microsoft Platform SDK for Windows Server 2003 on Windows x64 platforms.) The Microsoft Platform SDK installation program does not commonly define this environment variable. For example, the environment variable might have the value

```
C:\Program Files\Microsoft Platform SDK
```


Changes to Handling ActiveX Methods

In MATLAB Version 7.4 (R2007a), a change was made to Microsoft ActiveX® methods which was not documented in the release notes. This change is described in “Changes to Handling Microsoft® ActiveX® Methods” on page 824 in the MATLAB Release Notes, Version 7.4 (R2007a).

Changes to Dynamic Data Exchange (DDE) Documentation

In MATLAB V5.1, all development work for the Dynamic Data Exchange (DDE) server and client was stopped. This functionality is no longer documented in V7.5 (R2007b). MathWorks provides, instead, a MATLAB interface to COM technology that is documented in Using COM Objects from MATLAB .

Obsolete Functionality No Longer Documented

Documentation for Dynamic Data Exchange (DDE) is no longer included in External Interfaces.

Compatibility Considerations

If you must support this obsolete functionality, we suggest you print a copy of the External Interfaces chapter “COM and DDE Support (Windows Only)” from MATLAB V7.4 (R2007a) or earlier.

Documentation for Obsolete Functions To Be Phased Out

Documentation for the following functions is included in the MATLAB Function Reference documentation for MATLAB V7.5 (R2007b), but will not be included in a future version of MATLAB.

Obsolete Functions
ddeadv
ddeexec
ddeinit
ddepoke
ddereq
ddeterm
ddeunadv

The following syntax for `enableservice`, included in the MATLAB Function Reference documentation for MATLAB V7.5 (R2007b), will be removed from the documentation.

```
enableservice('DDEServer',enable)
```

Compatibility Considerations

If you must support this obsolete functionality, we suggest you print and keep a copy of the relevant MATLAB function reference pages from V7.5 (R2007b) or earlier.

R2007a

Version: 7.4
New Features: Yes
Bug Fixes: Yes

Desktop Tools and Development Environment

Startup and Shutdown

New features and changes introduced in Version 7.4 (R2007a) are

- “Double-Clicking Associated File Type in Explorer Now Opens File in Existing Session of MATLAB Software” on page 751
- “Changes to Startup Directory (Folder) and Startup Options for MATLAB Application on Windows” on page 752
- “JVM for Windows Updated” on page 755
- “New Version of Java Access Bridge Software” on page 755
- “Confirm Exit Preference to be Enabled by Default in Future Version” on page 755

Double-Clicking Associated File Type in Explorer Now Opens File in Existing Session of MATLAB Software

When you open a file from Microsoft Windows Explorer whose type is associated with the MATLAB application, the file opens in the appropriate tool in the existing session of MATLAB, if MATLAB is already running, or if not, starts MATLAB. This assumes you associated the file types with MATLAB by accepting the defaults while installing MATLAB, or by changing the associations. For example, in Explorer, double-click an M-file to open the file in the MATLAB Editor/Debugger, or double-click a MAT-file to open the Import Wizard and load the data into the workspace in MATLAB. For details, including how to change file associations, see *Associating Files with MATLAB on Windows Platforms*.

Compatibility Considerations

In previous versions, when you double-clicked a file in Explorer whose type was associated with MATLAB, the file opened in a new session of MATLAB. The change made in MATLAB Version 7.4 (R2007a) to open the file in an existing session was based on many user requests.

In previous versions, double-clicking a MAT-file associated with MATLAB in Explorer opened a new session of MATLAB and loaded the data into the workspace. When clicked in the Apple Macintosh Finder, the data loaded into

the existing session of MATLAB. Now on Microsoft Windows and Macintosh platforms, the Import Wizard opens in the existing session of MATLAB, and you use it to load the data into the workspace.


By default, in previous versions, double-clicking an M-file in Explorer opened it in the MATLAB stand-alone Editor. For more information about that change, see “Stand-Alone Editor No Longer Opens By Default; To Be Removed in a Future Version” on page 771.

Changes to Startup Directory (Folder) and Startup Options for MATLAB Application on Windows

The default startup directory for MATLAB on Microsoft Windows platforms is now `My Documents\MATLAB`, or `Documents\MATLAB` on the Microsoft Windows Vista platform. Upon startup, MATLAB automatically locates this MATLAB folder (creating it if it does not exist), and adds it to the top of the search path. This utilizes standard folders on Windows and Windows Vista platforms to provide a unique startup directory for each user. As such, the folder is part of the Windows (or Windows Vista) user’s profile, and will be accessible when the user runs MATLAB from other machines, when the profile is set up to roam.

In the Properties dialog box of the shortcut icon for MATLAB, the **Target** field includes a new startup option `-sd` (for startup *directory*), followed by `$documents\MATLAB`, where MATLAB interprets `$documents` as the `My Documents` folder for the current user (or `Documents` for the Windows Vista platform). If the path for `$documents` is specified in the configuration of the Windows environment via UNC pathname, MATLAB automatically assigns it a mapped drive, creating one if necessary. The `-sd` startup option overrides anything in the **Start in** field, which is now empty by default.

For more information, see [Changing the Startup Directory](#).



Compatibility Considerations

In previous releases, the default startup directory was `\Work`, located in the directory in which MATLAB was installed. For example, in R2006b, if you

installed MATLAB in C:\Program Files, the default startup directory was C:\Program Files\MATLAB\R2006b\Work.

Windows Vista User Account Control (UAC) security features restrict access to Program Files. To accommodate this enhanced security model, the default startup directory in MATLAB has been moved outside of Program Files.

These are the differences between the startup directory for R2007a and previous releases:

- In previous releases, upon installation, the default startup directory was specified in the **Start in** field of the Properties dialog box for the shortcut icon for MATLAB. You could change the startup directory by replacing the pathname in that field. In R2007a, if you want to specify the startup directory using the **Start in** field, you must also remove from the **Target** field the -sd startup option and the pathname that follows it.
- The default startup directory is no longer specific to a release. When you upgrade from R2007a to a future release, files you created and saved in My Documents\MATLAB (or Documents\MATLAB on Vista) will automatically be in the startup directory for the new release. Previously, you had to move files you created and saved in the Work folder for a release, for example, R2006a\Work, to the default startup directory for the new release, for example, R2006b\Work.
- In previous releases, the default startup directory, Work, was shared by all users running that installation of MATLAB. The default startup directory in R2007a, My Documents\MATLAB (or Documents\MATLAB on Vista), provides each user with a unique startup directory.
- In previous releases, MATLAB added the default startup directory, Work, to the bottom of the search path. In R2007a, MATLAB adds the default startup directory, My Documents\MATLAB (or Documents\MATLAB on the Windows Vista platform), to the top of the search path. In R2007a, for consistency with previous releases, MATLAB adds . . . \MATLAB\R2007a\Work to the bottom of the search path. However, we encourage you to stop using the Work folder because support for it might be removed in a future release.

JVM for Windows Updated

MATLAB is now using Sun Microsystems Java (JVM) version 1.5.0_07 on Windows platforms. Java is supplied with MATLAB for Windows platforms, so this change requires no action on your part.

Compatibility Considerations

If you use a specific version of Java with MATLAB on Windows platforms, this change might impact you.

New Version of Java Access Bridge Software

MATLAB now installs Java Access Bridge 2.0, which is used by Freedom Scientific BLV Group JAWS® software for accessibility support.

Confirm Exit Preference to be Enabled by Default in Future Version

When you exit from MATLAB, MATLAB terminates without displaying a confirmation dialog box that asks if you are sure you want to quit. This is the default behavior but you can set a preference to display a confirmation dialog box. In a future version, the confirmation dialog box will appear by default when you quit MATLAB.

Compatibility Considerations

When the confirmation dialog appears by default, you will be able to disable it using preferences. If you have files that include exit statements, you might need to ensure the preference for the confirmation dialog box is disabled.

Desktop

Compatibility Considerations: Yes


New features and changes introduced in Version 7.4 (R2007a) are

- “Minimize, Temporarily Display, and Restore Tools in the Desktop” on page 756
- “Maximize Tools in the Desktop” on page 760
- “Tabs for Tools Replaced by Title Bars” on page 762
- “Multithreaded Computation Support Added; Enable Via New Preference” on page 764


Minimize, Temporarily Display, and Restore Tools in the Desktop

On Windows and UNIX platforms, you can minimize any tool in the desktop. Minimizing a tool creates a button for it along the specified edge. When you want to view the tool, hover over or click the button to temporarily show it in the desktop. Right-click the button and select **Restore *toolname*** to return the tool to the desktop. Perform these tasks for the selected tool using items in the **Desktop** menu, equivalent mnemonics (for example **Alt+D, N** to minimize), or buttons on the tool’s titlebar.


The following illustrations show how to use these features, using the example of the Command History window in the default desktop layout.




When minimized, a tool, such as the Command Window in this example, is represented by a button on the desktop border.



Hover over or click the button for a minimized tool to temporarily view the tool. The tool is temporarily displayed until you select another tool. Then the tool becomes minimized again.




On the button for a minimized tool, right-click, and from the context menu, select **Restore**. The tool resumes the size and position it had in the desktop before it was minimized.




Maximize Tools in the Desktop

On Windows and UNIX platforms, you can maximize a tool so it occupies the entire desktop tool area in MATLAB, then restore it to return it to its previous location. Perform these tasks for the selected tool using items in the **Desktop** menu, equivalent mnemonics (for example **Alt+D, X** to maximize), or buttons on the tool's titlebar.

Default desktop layout.
Maximize a tool, for example, the Command Window
so it occupies the full MATLAB desktop area.



Maximized, the Command Window now occupies the full desktop area. Restoring the Command Window returns it to its original size and location in the desktop.




Tabs for Tools Replaced by Title Bars

In the desktop, when you tab tools together, that is, arrange them so they occupy the same position, the tools' title bars share the title bar area. To make a tool active, select its name in the title bar.

The Current Directory browser and Workspace browser are "tabbed together".

The name of the tool in the title bar serves as the tab. To make a tool active, click its name in the title bar. For example, click Workspace in the title bar to make the Workspace browser active.



Compatibility Considerations

In previous versions, tools tabbed together each had a tab at the bottom of the area they occupied. The tabs have been removed in favor of tools sharing the titlebar area.

Multithreaded Computation Support Added; Enable Via New Preference

If you run MATLAB on a multiple-CPU system (multiprocessor or multicore), use a new preference to enable multithreaded computation. This can increase performance in MATLAB for element-wise and BLAS library computations.

By default the preference is not set, so you must set it to enable multithreaded computation. With the preference enabled, MATLAB automatically specifies the recommended number of computational threads, although you can change that value. On AMD platforms running the Linux operating system, MATLAB supports multithreaded computation, but requires an extra step to change the default BLAS.

If you are using a multiple-CPU system, you can run the Multithreaded Computation demo to see the performance impact. For more information, see “Enabling Multithreaded Computation” in the MATLAB Desktop documentation.

Running Functions—Command Window and History

Compatibility Considerations: Yes

New features and changes introduced in Version 7.4 (R2007a) are

- “Startup Message Bar Replaces Startup Message in Command Window” on page 765
- “Command History Searching Enhanced” on page 765
- “Macintosh Platforms—Some Key Bindings in Command Window Changed” on page 765

Startup Message Bar Replaces Startup Message in Command Window

When you start MATLAB, a getting started message bar appears at the top of the Command Window, that provides links to information that is helpful for new users. You can dismiss the message bar by using the close box in it. Use Command Window preferences to specify whether or not the message bar should appear.

Command History Searching Enhanced

You can now find entries in the Command History window by typing the first few letters of an entry; the previous entry that begins with those letters is selected. Then use up and down arrow keys to extend the find to the next and previous instances. Use the **Ctrl** key with an arrow key to select the current as well as next or previous instances. Use **Ctrl+A** to find and highlight all instances at once. The search does not look at entries in sessions that are collapsed. For more information about this search feature, see Quick Search for Entries Beginning with Specified Letters or Numbers.

Macintosh Platforms—Some Key Bindings in Command Window Changed

On Macintosh platforms, some key bindings were changed to make them more consistent with Mac OS X/Mac OS X standard behaviors.

Compatibility Considerations

Key bindings you have been used to in the Command Window might have changed.

Help

New features and changes introduced in Version 7.4 (R2007a) are

- “Demos Now Included in Search Results and Product Filtering” on page 767
- “Get URL of Displayed Page for Viewing on Web” on page 767
- “Include Search Database for Your Own Help Files” on page 767
- “Video Tutorials Now Accessed Via Web Site” on page 768

Demos Now Included in Search Results and Product Filtering

When you perform a search in the Help browser, the results now include code and text found in **Demos**. Also, the **Demos** listing in the Help Navigator pane now synchronizes with the demo currently open when you have the synchronization preference for the Help browser selected. For more information, see Search Syntax and Tips.

When you select **File > Preferences > Help** and enable the Product Filter, only demos for selected products are shown in the **Demos** pane, and searched via the **Search for** field.

Get URL of Displayed Page for Viewing on Web

When viewing a page in the Help browser, select **View > Page Locations**. A window appears providing the location of the current Help page you are viewing. The window provides the page location on both your local system and the MathWorks Web site. Use this feature to

- Send the URL to someone else who wants to view that information and might not have MATLAB or the same version of MATLAB, for example, a colleague or technical support.
- More easily see if this same documentation page has been updated for the latest product version.

Include Search Database for Your Own Help Files

If you create your own HTML help files for use with the MATLAB Help browser, the Help browser can now search the content of your files. Create

a search database for your help files using the new `builddocsearchdb` function. The function creates a `helpsearch` directory that contains the search database files. For information on this process, see [Making Your HTML Help Files Searchable](#).

Compatibility Considerations

In previous versions of MATLAB, some users created help search databases for their own help files via assistance from MathWorks Technical Support. If you created a help search database for use with R2006b, it might work in R2007a, but it is recommended that you recreate it for R2007a, even if no content has changed. If you created a help search database prior to R2006b, you must recreate it for R2007a.

Help search databases in prior releases were built from a help jar file rather than html files. The `builddocsearchdb` function only supports html files. However, it is expected to support jar files in a future release. If you used a jar file for a prior version and want to use a jar file in R2007a, build your R2007a help search database using the same technique you used in R2006b.

Video Tutorials Now Accessed Via Web Site

Previously video tutorials were installed when you installed MATLAB. Now the tutorials are on the MathWorks Web site.

Compatibility Considerations

You can still link to and play video tutorials from within the Help browser Demos listings or other links to them in the product and documentation, however this now requires an active Internet connection.

Workspace, Search Path, and File Operations

Compatibility Considerations: Yes

New features and changes introduced in Version 7.4 (R2007a) are described here.

Current Directory Browser Enhancements

- When you double-click a Windows shortcut in the Current Directory browser, it runs the shortcut.
- When you double-click a prj file in the Current Directory browser, it opens in the Deployment Tool.
- You can now find entries in the Current Directory browser by typing the first few letters of an entry; the entry that begins with those letters is selected.

Workspace Browser

When you double-click an object, it opens in the Property Inspector.

Array Editor Enhancements

You can now undo and redo the last operation you performed in the Array Editor. This applies to cut, paste, insert, delete, and clear contents features.

Search Path Changes

On Windows platforms, MATLAB now adds the default startup directory, My Documents\MATLAB (or Documents\MATLAB on Windows Vista), to the top of the search path upon startup.

Compatibility Considerations

In previous releases, MATLAB added the default startup directory, Work, to the bottom of the search path on Windows platforms. For example, in R2006b, it added `... \MATLAB\R2006b\Work` to the bottom of the search path. In R2007a, for consistency with previous releases, MATLAB adds `... \MATLAB\R2007a\Work` to the bottom of the search path. However, we

encourage you to stop using the `Work` folder because support for it might be removed in a future release. For more information, see “Changes to Startup Directory (Folder) and Startup Options for MATLAB Application on Windows” on page 752.

Editing and Debugging M-Files

New features and changes introduced in Version 7.4 (R2007a) are

- “Stand-Alone Editor No Longer Opens By Default; To Be Removed in a Future Version” on page 771
- “Delimiter Matching Extended to Include Language Keyword Pairs” on page 772
- “M-Lint Automatic Correction Feature” on page 772
- “M-Lint Detection of Missing End-of-Line Semicolons Enhanced” on page 773
- “Macintosh Platforms—Some Key Bindings in Editor/Debugger Changed” on page 774
- “Other Changes in the Editor/Debugger” on page 774

Stand-Alone Editor No Longer Opens By Default; To Be Removed in a Future Version

Starting in this release, by default, double-clicking an M-file in Windows Explorer opens the file in the MATLAB Editor/Debugger rather than in the MATLAB stand-alone Editor. In a future version, the stand-alone Editor will not be provided with MATLAB.

Compatibility Considerations

The change to open M-files in the MATLAB Editor/Debugger rather than the stand-alone Editor was made based on many user requests. You can still use the MATLAB stand-alone Editor in this release by starting the application located at: `matlabroot\bin\win##\meditor.exe`.

Starting MATLAB by double-clicking an M-file requires a MATLAB license, while starting the stand-alone Editor does not require a MATLAB license.

If you want to associate M-files so that when you double-click them they open in the MATLAB stand-alone Editor rather than in the MATLAB Editor/Debugger, follow the instructions in *Associating Files with MATLAB*

on Windows Platforms; rather than specifying the executable for MATLAB, `matlab.exe`, specify `meditor.exe`, which is in the same folder.

Instead of the stand-alone Editor, you can use the MATLAB Editor/Debugger. It provides all the features of the stand-alone Editor plus some not found in the stand-alone Editor, such as debugging and tab completion; for a full list, see “Stand-Alone Editor Will Not Be Included in Next Version” on page 687.


Some users have preferred the stand-alone Editor to the MATLAB Editor/Debugger because of slightly better startup performance and because it does not require a license for MATLAB. For those situations, you can use any text editor you have, such as UltraEdit or Emacs. If you have concerns about the pending removal of the stand-alone Editor, please contact us at editor-feedback@mathworks.com, so we can plan to minimize transition issues.

Delimiter Matching Extended to Include Language Keyword Pairs

You can now see the match to language keyword pairs using delimiter matching features that previously existed for parentheses and brackets. For example, when you type `end`, the Editor/Debugger highlights the matching `if`. To set delimiter matching preferences, select **File > Preferences > Keyboard > Delimiter Matching**; click **Help** for more information.

M-Lint Automatic Correction Feature

For some types of warnings or errors, M-Lint can apply an automatic fix to the code. Code that can be automatically corrected appears with a different background color. To perform the fix, right-click the code that is highlighted (for a single single-button mouse, use **Ctrl+click**); from the resulting context menu, select the auto-fix action.



For more information, see step 8 in the example at [Automatically Check Code in the Editor — Code Analyzer](#).

M-Lint Detection of Missing End-of-Line Semicolons Enhanced

In previous versions, there was a single output message generated by a line with a missing terminating semicolon:

Terminate statement with semicolon to suppress output.

However, M-Lint suppressed displaying the message for files with three or more cells (a cell being indicated by a line with an initial %). This was done based on the assumption that such files were demo programs, and therefore display of the output was intentional.

In MATLAB Version 7.4 (R2007a), M-Lint no longer makes a distinction for files with three or more cells. Instead, M-Lint displays one message for scripts and a different message for functions:

Terminate statement with semicolon to suppress output (in functions).

Terminate statement with semicolon to suppress output (in scripts).

The corresponding M-Lint tags to suppress display of such messages within a line are `%#ok<NOPRT>` for functions, and `%#ok<NOPTS>` for scripts.

By default, both of the messages are initially selected in Preferences.

Compatibility Considerations

In MATLAB Version 7.3 (R2006b), `%#ok<NOPRT>` was the only tag used to suppress the missing terminating semicolon. The tag will remain valid for function files, but will not be valid for script files. If you added any `%#ok<NOPRT>` tags in script files in R2006b, change those tags to the new tag `%#ok<NOPTS>`.

Macintosh Platforms—Some Key Bindings in Editor/Debugger Changed

On Macintosh platforms, some key bindings were changed to make them more consistent with standard behaviors for Mac OS X.

Compatibility Considerations

Key bindings you have been used to in the Editor/Debugger might have changed.

Other Changes in the Editor/Debugger

- There is a new confirmation preference for displaying a warning about exiting debug mode in order to save a file.

Tuning and Managing M-Files

Compatibility Considerations: Yes

There was a minor change in M-Lint behavior—for details, see “M-Lint Detection of Missing End-of-Line Semicolons Enhanced” on page 773.

Compatibility Considerations

See the compatibility considerations associated with “M-Lint Detection of Missing End-of-Line Semicolons Enhanced” on page 773.

Publishing Results

New features and changes introduced in Version 7.4 (R2007a) are

- “Publishing Function M-Files Now Supported” on page 776
- “Specify Maximum Number of Output Lines in Published File” on page 776
- “New Publishing Options” on page 776

Publishing Function M-Files Now Supported

You can now publish an M-file function. When publishing an M-file function, you cannot evaluate the code. This feature effectively allows you to save M-file functions to output formats such as HTML or Microsoft Word documents, with formatting. To publish an M-file function, first clear the **Evaluate code** preference in **Editor/Debugger Publishing Preferences**, or run the publish function with the `evalCode` option set to `false`.

Specify Maximum Number of Output Lines in Published File

Using the `publish` function, you can specify the maximum number of lines in a published file. Set the new `maxOutputLines` field to a nonnegative value. The default value is `Inf`.

New Publishing Options

New publishing options provide increased flexibility and control over the appearance of the published document. The added options are for adding inline links, inline links with link text, graphics, and HTML markup. See *Mark Up MATLAB Comments for Publishing* for more information.

Mathematics

New Functions

Function	Description
bsxfun	Applies an element-by-element binary operation to two full arrays with singleton expansion enabled
ilu	Performs the sparse incomplete LU factorization

More Efficient Matrix Multiplication for Sparse Matrices

Matrix multiplication for $A^T * b$ now handles sparse matrices more efficiently.

rand Function Uses the Mersenne Twister Algorithm as Default

Compatibility Considerations: Yes

The rand function now uses the Mersenne Twister algorithm as default generator algorithm. This method generates double precision values in the closed interval $[2^{-53}, 1-2^{-53}]$, with a period of $(2^{19937}-1)/2$. Prior to this release, MATLAB used an algorithm known as the Subtract-with-Borrow (SWB) algorithm.

The rand function now produces different results than in previous releases. However, the results returned are still pseudorandom values drawn from a standard uniform distribution. Because the values returned by rand are intended to be random, this change should not affect your code.

Compatibility Considerations

There are several things to keep in mind regarding this change:

- If your code requires the exact values returned by rand in previous releases, you should use the statement

```
rand('state',0);
```

to reset rand to use the SWB algorithm. The new default algorithm's internal state at startup is equivalent to using the statement

```
rand('twister',5489);
```

Note that the 'state' keyword corresponds specifically to the SWB algorithm; it cannot be used generally to refer to the internal state of the currently active algorithm.

- Existing code that uses the 'state' keyword to reinitialize rand in a statement such as

```
rand('state',sum(100*clock))
```

causes rand to switch to using the SWB algorithm. You may want to use the 'twister' keyword, which resets rand but does not switch algorithms.

- Existing code that uses the 'state' keyword to save and restore the internal state of rand in statements such as

```
savedState = rand('state');  
... % code that uses rand  
rand('state',savedState);
```

may no longer work as intended. Specifically, the first line of code saves the state of the SWB generator algorithm (see the rand documentation for details). If the default Mersenne Twister algorithm was the active one at that time, then using the saved state in the last line does not restore the rand internal state to its original conditions. Instead, it switches the rand algorithm to SWB. To save and restore the internal state of the Mersenne Twister algorithm, use the 'twister' keyword.

Upgrade to BLAS Libraries

MATLAB now uses new versions of the Basic Linear Algebra Subroutine (BLAS) libraries. For Windows, Intel Mac, and Intel processors on Linux platforms, MATLAB supports the Intel Math Kernel Library (MKL) version 9.0. For AMD processors on Linux platforms, MATLAB uses the AMD Core Math Library (ACML) version 3.5. For the Solaris platform, MATLAB uses the Sun Performance Library from Sun Studio 11.

mode of Empty Array Now Returns NaN

Compatibility Considerations: Yes

The mode function, when operating on an empty array (`[]`), returns a 1-by-0 array in previous releases, while related functions `mean`, `median`, `std`, and `var` return NaN when given the same input. In this release, mode returns NaN for an empty array input.

Compatibility Considerations

Existing program code that relies on mode of an empty array to return an empty array should be modified.

Change to Syntax for Setting BLAS Library Version on Linux

Compatibility Considerations: Yes

If you change the BLAS library used by MATLAB on Linux platforms, MATLAB now loads libraries in the left-to-right order specified in the syntax. For example, to load the Intel MKL BLAS, from a system prompt, run

```
setenv BLAS_VERSION mkl.so:mklcompat.so
```

MATLAB loads `mkl.so` first, and then loads `mklcompat.so`.

This also applies if you edit `bin\$(ARCH)\blas.spec` directly.

Compatibility Considerations

This syntax differs from that used for Linux platforms in prior versions.

Data Analysis

Programming

New Functions

New Functions in this release are

Function	Description
<code>assert</code>	Generates an error when a specified condition is violated. Displays either the default error message or one that you have written.
<code>ismac</code>	Returns <code>true</code> if you are currently running one of the Mac OS X versions of MATLAB.
<code>verLessThan</code>	Compares the specified version number and toolbox name with the version of that same toolbox that is currently running. Use <code>verLessThan</code> in your functions when you want to write code that can run across multiple versions of MATLAB.

Parse Inputs with Consistently Implemented Mechanism

The new `inputParser` class provides a consistent mechanism for parsing and validating input arguments in the M-file functions you write. Using `inputParser` methods in the body of your function, you build a schema that represents each valid input argument to the function. In the schema, you can specify whether arguments are required or optional, and if they are to be passed as single values or as parameter-value pairs. The schema also provides a means of validating each incoming argument. The properties of the `inputParser` class give you additional information about arguments that are passed to the function.

For more information, see [Parse Function Inputs in the MATLAB Programming documentation](#).

textscan Returns Like Values in Same Cell Array

In previous versions of MATLAB, the `textscan` function always returned each output value in a separate cell array, even if those values were of the same data type. In this release, if you call `textscan` with the new `CollectOutput` switch, MATLAB returns all consecutive data that is of the same type in the same cell array. This can save you the extra task of sorting through the output and merging like data types together in your own code.

For more information, see the `textscan` function reference page.

Numbered Arguments for Formatted String Functions

Using numbered argument specification with MATLAB functions that employ format specifiers such as `%d` or `%s` (e.g., `sprintf`, `error`), you can pass the numeric and character string values that correspond to these format specifiers in a varying order. This can be useful when translating format strings in a different sentence structure.

In addition to identifying the values, you can also use numbered arguments to specify the field width and precision of the format specifiers. In the following example, the first format specifier in the `sprintf` command is `%1$*4$f` (quite different from the usual `%f` specifier). The `1$` tells MATLAB that the value that is to replace this format specifier is in the first argument following the format string; that is, `123.45678`. The `*4$` indicates that the field width for this specifier is being passed in the fourth argument following the format string: `15`.

In the second and third arguments (`%2$.*5$f` and `%3$*6$.*7$f`), the symbols `2$` and `3$` represent the values, `*5$` and `*7$` represent precisions, and `*6$` represents field width:

```
sprintf('%1$*4$f   %2$.*5$f   %3$*6$.*7$f', ...  
123.45678, 16.42837, pi, 15, 3, 6, 4)
```

```
ans =  
    123.456780    16.428    3.1416
```

For more information, see [Formatting Strings in the MATLAB Programming documentation](#).

The dir Function Returns Additional datenum Field

The `dir` function now returns the date the file or directory was last modified in two formats: string and numeric. The numeric date value is not specific to any particular locale, and thus is compatible for international use:

```
fileinfo = dir('myfile.txt')

fileinfo =
    name: 'myfile.txt'
    date: '16-Mar-2006 13:34:01'
    bytes: 251
    isdir: 0
    datenum: 7.3275e+005
```

This new output is also returned when running `dir` on an FTP server.

Using whos -file on Objects with Overloaded size or class Methods

Compatibility Considerations: Yes

MATLAB is unable to determine the true size of an object stored in a MAT-file if the class of this object overloads the MATLAB `size` function. Likewise, MATLAB cannot determine the true class name of an object if it overloads the MATLAB `class` function. For these reasons, in previous versions of MATLAB, the command `whos -file` does not return or display object size and class accurately if the class of that object overloads these methods, but instead always returns `1x1` for the size and a default name for the class.

In this release, `whos -file` returns the empty matrix (`[]`) or displays a hyphen (-) for objects that overload `size`, and returns and displays `unknown` for objects that overload `class`.

Compatibility Considerations

If you use `whos -file` on objects in any of your programs, and if any of these objects overloads the `size` function, then you need to be aware that MATLAB now returns `[]` instead of a 2–element vector of ones in the `size` field of the output structure.

mat2str Returns Correct Output for Strings

Compatibility Considerations: Yes

The documentation for the `mat2str` function states that the `str` output of this function “is suitable for input to the `eval` function such that `eval(str)` produces the original matrix to within 15 digits of precision.” The behavior of `mat2str` when given a character array as input, however, did not abide by this rule. This inconsistency has been fixed in this release.

In MATLAB Version 7.3, the `eval` command below generated an error.

```
s = mat2str('MATLAB')
s =
    'MATLAB'
```

```
eval(s)
ans =
    MATLAB
```

Compatibility Considerations

You might have to modify M-file programs that expect the previous behavior from `mat2str`.

Warning Generated by try-catch

Compatibility Considerations: Yes

To accommodate future changes in the MATLAB error-handling capabilities, there is a new restriction to the syntax of the try-catch block. When the first MATLAB statement that follows the try keyword consists of just a single term (e.g., A as opposed to A+B) occurring on the same line as the try, then that statement and the try keyword should be separated by a comma. For example, the line

```
try A
```

should be written as either

```
try, A
```

or on two lines as

```
try
  A
```

This affects only single-term statements. For example, the following statement continues to be valid:

```
try A+B
```

The same holds true for the catch keyword and a single-term statement following the keyword on the same line. A valid try-catch statement of this type should be composed as follows:

```
try, A, catch, B, end
```

If you omit the commas following try and/or catch, your code will continue to operate correctly. However, MATLAB will issue a warning:

```
try statements, catch statements, end
```

Warning: This try-catch syntax will continue to work in R2007a, but may be illegal or may mean something different in future releases of MATLAB.

As with previous releases, the recommended syntax for a try-catch block is as follows:

```
try
  try_statements
catch
  catch_statements
end
```

Note Due to a bug in the R2007a release, the warning for a catch followed immediately by a single term is thrown as an error, even though the text of the message says that it is a warning.

Compatibility Considerations

Your M-file programs may generate the warning shown above if the correct syntax for try and catch is not used.

save -regexp Saves to Correct Filename

In previous releases, the following command mistook the `-regexp` argument (`[ab]` in the case shown below) to be the name of the file to save to:

```
save -regexp [ab]
```

In this release, the filename is correctly understood to be the default `save` filename, `matlab.mat`, and any arguments that follow the `-regexp` flag and precede the next flag are interpreted as patterns to be matched.

Functions Not Callable If in Directory Under Class Directory

Compatibility Considerations: Yes

M-files placed in a directory that is one or more levels beneath a MATLAB class directory are not callable from that same directory. A MATLAB class directory contains methods of a class and has a filename that begins with the @ character.

In the following example, function myfun1 is not callable if the current working directory is set to dir1. The same holds true for myfun2 if the current working directory is set to dir2.

```
\home\matlab\@myobj\dir1\myfun1.m  
\home\matlab\@myobj\dir1\dir2\myfun2.m
```

This behavior existed in the R2006b release, as well as in this release.

Compatibility Considerations

You will no longer be able to call a file that is one or more levels beneath a MATLAB class directory if your current working directory is set to that same directory.

Improved Performance on Certain Platforms and Operations

As of release R2006b, MATLAB offers improved performance in the following areas:

- Improved performance on 64-bit Windows XP and Linux platforms. This is independent of the size of data set in use.
- Faster scalar indexing into cell arrays.
- Faster assignment of cell array data to variables.

Technique to Conserve Memory on Windows Vista

To conserve memory on machines running Windows Vista, you can reduce the amount of virtual memory space reserved by the operating system by using the command:

```
BCDEdit /set increaseuserva 3072
```

More documentation on this option can be found at the following URL:

<http://msdn2.microsoft.com/en-us/library/aa906211.aspx>

ispuma Function Deprecated

Compatibility Considerations: Yes

Because MATLAB no longer supports OSX 10.1, the `ispuma` function always returns `false` in this release, and also displays a warning message that the function is now deprecated. Support for `ispuma` will be removed in a future release of MATLAB.

Compatibility Considerations

It is recommended that you remove calls to `ispuma` from your M-file functions.

Graphics and 3-D Visualization

Nudging Annotations with Arrow Keys

In plot edit mode, annotations such as textboxes, lines, arrows, doublearrows, and text now respond to pressing directional arrow keys. Each keypress will move the selected annotation(s) one or more pixels in the indicated direction. If you select multiple objects, they all move together in response to arrow key strokes. Normally, selected objects move one pixel with each press of an arrow key. If you have selected **Snap to Layout Grid** from the **Tools** menu, each keypress makes objects move to the next grid position.

Movies No Longer Play During Loading

Compatibility Considerations: Yes

The `movie` function no longer plays each frame one extra time. Previously, it would show frames as they were loaded into memory to speed up display. This behavior is no longer required and has been eliminated.

Compatibility Considerations

If you have code that calls `movie` in a loop a certain number of times and want that number to remain the same, you need to add one iteration to the loop.

Ghostscript Printing Software Upgraded

Compatibility Considerations: Yes

The Ghostscript software used by some print devices has been upgraded from an older version to Version 8.54. Starting in this release, MathWorks is no longer shipping a separate, standalone Ghostscript executable program.

Compatibility Considerations


If you have written M-code based on undocumented functions that called the old version of Ghostscript, your code will no longer work.

As a consequence of this upgrade, support for printing on DEC LN03 printers (`print -dln03`) has been removed from MATLAB.

Property Inspector Now Categorizes Graphic Object Properties

Compatibility Considerations: Yes

The Property Inspector (accessed via the Property Editor, GUIDE, and the `inspect` function) now provides tree views of groups of graphic object properties as well as an alphabetical list of all properties. You can switch between views via the two buttons at the top of the window, as shown in the following picture of the tree view of the Printing category:



In addition, the type of object currently being inspected is now shown in the title bar of the Property Inspector window. Formerly it was shown in the gray area below the title bar, which now contains the view manipulation buttons.

To change view, click a button without the blue background (the collapse and expand buttons at right are disabled in alphabetic list view). When you change views, the selected property stays the same. To inspect properties of graphic objects in the tree view, click the + icon next to a category of interest. Do the same to open properties within a category that have multiple elements. Note that only Handle Graphics objects have categories; annotation and most other MATLAB objects can be displayed only in alphabetic list view.

The functionality of the Property Inspector has not changed; only its GUI has. As previously, if you select a set or array of objects and inspect them, the Property Inspector only displays those properties that all the objects share.

For details on using the Property Inspector, see [Accessing Object Properties with the Property Inspector](#) in the MATLAB Graphics documentation and the [inspect](#) reference page.

Compatibility Considerations

Text that you type or delete after clicking a text field that has a text widget icon (for example, `XTickLabel`), will not persist unless you press **Return** before clicking elsewhere. This mimics the behavior of clicking the text widget icon to open a text entry dialog box, typing into it, and accepting the result by clicking **OK**. This behavior differs from that which existed prior to R2006b (MATLAB V. 7.3).

Figure WindowScrollWheelFcn Property Programs Scrollwheel Events

The new figure property `WindowScrollWheelFcn` enables you to write a callback function that handles mouse wheel scrolling events while the figure has focus. See the documentation for the figure `WindowScrollWheelFcn` for more information.

Figure KeyReleaseFcn Property Programs Key Release Events

The new figure property `KeyReleaseFcn` enables you to write a callback function that handles key release events (analogous to `KeyPressFcn`). See the documentation for the figure `KeyReleaseFcn` for more information.

Creating Graphical User Interfaces (GUIs)

GUIDE No Longer Copies Callbacks When You Duplicate Components

Compatibility Considerations: Yes

In GUIDE, when you copy a component for which one or more of its callback properties are defined, the callback properties of the newly created component are now set to their default values, the ones you get when adding a component directly from the Component Palette. Previously, their values were copied from the corresponding callback properties of the original component. New callback subfunctions can be generated in the GUI M-file for the new component in the same way as for any component in the GUIDE layout.

Compatibility Considerations

If you have relied on the old behavior, in which the callbacks properties of the new component point to the callbacks of the original component, you will now have to explicitly change the callback properties, using the Property Inspector, to do that.

GUIDE M-File-Defined handles Structure Fields No Longer Become Permanent

Compatibility Considerations: Yes

The `handles` structure that is provided to every GUIDE generated callback subfunction in the GUI M-file is constructed at runtime every time the GUI runs. When the GUI is fully initialized, the `handles` structure contains only handles to all the components in the GUI and custom data added in any `CreatedFcn` callbacks and/or the `OpeningFcn`. Previously, fields that the M-file had added to the `handles` structure could sometimes become a permanent part of the structure.

Compatibility Considerations

If your GUI runs well but displays error messages about missing fields in the `handles` structure when starting up, you may have to update the code in the GUI M-file where those fields are accessed. You may need to initialize those `handles` fields properly in a `CreateFcn` callback and/or in the `OpeningFcn`.

UNIX: File Dialog 'Location' Property Is Obsolete

Compatibility Considerations: Yes

For UNIX platforms, the `Location` property of `uigetfile` and `uiputfile` is obsolete. Previously, for UNIX platforms only, you could use the `Location` property to specify the screen location at which the dialog box would originally be displayed.

Compatibility Considerations

Since the UNIX `uigetfile` and `uiputfile` `Location` property is now obsolete, MATLAB ignores any occurrences in existing code of the `Location` property

```
uigetfile(...,'Location',[X Y])
```

or the older use of `X` and `Y` arguments to specify location

```
uigetfile(...,X,Y)
```

A warning is displayed for either syntax, on all platforms.

Functions Becoming Obsolete

Compatibility Considerations: Yes

The following functions are either obsolete or grandfathered in MATLAB 7.4 (R2007a): `cshelp`, `figflag`, `getstatus`, `menulabel`, `popupstr`, `setstatus`, `hidegui`, `uigettoolbar`.

Compatibility Considerations

The functions shown in the following table will continue to work but their use may generate a warning message. As soon as possible, replace any occurrences you may have of these functions with the function(s) shown in the following table, if any, or with other suitable code.

Function	Replacement
<code>cshelp</code> , <code>figflag</code> , <code>getstatus</code> , <code>menulabel</code> , <code>popupstr</code> , <code>setstatus</code>	Grandfathered. There are no replacements. No enhancements will be made and only critical bugs will be fixed. No warnings will be displayed. These functions may become obsolete if replacements become available.
<code>hidegui</code>	Obsoleted. Now issues warnings. Set the figure <code>HandleVisibility</code> property instead.
<code>uigettoolbar</code>	Obsoleted. No warnings will be displayed until a replacement is available in a future release.

External Interfaces/API

New File Extensions for MEX-Files

MEX-Files in MATLAB for Apple Macintosh (Intel)

With the introduction of MATLAB for Macintosh (Intel), the MEX-files you build have the extension `.mexmaci`. The `mexext` command in MATLAB returns `mexmaci` for Macintosh (Intel).

Compatibility Considerations

MEX-files built using MATLAB for Macintosh PowerPC®, which have `.mexmac` extensions, cannot be used in MATLAB for Macintosh (Intel).

Note All MEX-files on Macintosh platforms need to be recompiled for R2007a.

MEX-Files in MATLAB for 64-bit Sun Solaris SPARC

With the introduction of MATLAB for 64-bit Solaris SPARC®, you can now build 64-bit MEX-files for the Solaris platform. These MEX-files have the extension `.mexs64`. The `mexext` command in MATLAB returns `mexs64` for Solaris SPARC.

Compatibility Considerations

MEX-files built using MATLAB for Solaris 32, which have `.mexsol` extensions, cannot be used in MATLAB for Solaris SPARC.

Note All MEX-files on Solaris 64 platforms need to be recompiled for R2007a.

MEX-Files Built in MATLAB R11 or Earlier Must Be Rebuilt

In order to work with MATLAB V7.4 (R2007a), MEX-files compiled on Microsoft Windows (32-bit) platforms with MATLAB R11 or earlier will no longer load correctly and must be recompiled.

Compatibility Considerations

Recompile these MEX-files with MATLAB R12 or later.

Changes to Compiler Support

Compatibility Considerations: Yes

The set of compilers that MATLAB supports has changed in MATLAB Version 7.4 (R2007a). For an up-to-date list of supported compilers, see the Supported and Compatible Compilers Web page.

- “New Compiler Support” on page 817
- “Fortran Compatibility Considerations” on page 819
- “Discontinued Compiler Support” on page 819
- “Compiler Support To Be Phased Out” on page 820
- “Additional Linker Support for Intel Fortran” on page 820

New Compiler Support

MATLAB V7.4 (R2007a) supports new compilers for building MEX-files.

Windows (64-bit) platform

- Intel C++ version 9.1
- Intel Visual Fortran version 9.1

Windows (32-bit) platform

- Intel C++ version 9.1
- Intel Visual Fortran version 9.1
- Microsoft Visual C++ 2005 version 8.0 Express Edition

Note If you use the `mex -f matlabroot/bin/$ARCH/mexopts/msvc80freeopts.bat` switch to build a MEX-file using Microsoft Visual C++ 2005 Express Edition, the environment variable `MSSdk` must be defined. The value of this environment variable is the path to the installation directory for Microsoft Platform SDK for Windows Server 2003. (Microsoft Visual C++ 2005 Express Edition requires Microsoft Platform SDK for Windows Server 2003.)

Macintosh PowerPC and Macintosh (Intel) platforms

- Apple Xcode 2.4.1 (gcc / g++ version 4.0.1)
- g95 version 0.90

Note All MEX-files on Macintosh platforms need to be recompiled for R2007a.

Linux (64-bit) platform

- gcc / g++ version 4.1.1
- g95 version 0.90

Linux (32-bit) platform

- gcc / g++ version 4.1.1
- g95 version 0.90

Note All Fortran MEX-files compiled on Linux platforms need to be recompiled for R2007a.

Solaris SPARC (64-bit) platform

- cc / CC version 5.8
- gcc / g++ version 3.2.3
- f90 version 8.2

Fortran Compatibility Considerations

In R2007a we have added support for a new Fortran compiler g95 on the Linux and Macintosh platforms. This compiler implements the Fortran 95 language standard. It replaces previously supported Fortran compilers which implemented a previous language standard.

This may cause incompatibilities in your Fortran source code for MEX-files.

Compatibility Considerations

Refer to the IBM XL Fortran V10.1 for Linux Language standards Web site <http://publib.boulder.ibm.com/infocenter/lnxpcomp/v8v101/index.jsp?topic=/com.ibm.xlf1011.doc/xlf1r/languagestandards.htm> for information about incompatibilities between language standards.

Discontinued Compiler Support

The following compilers are no longer supported.

Linux (64-bit) platform

- gcc / g++ version 3.4.5
- g77 version 3.4.5

Linux (32-bit) platform

- gcc / g++ version 3.4.5
- g77 version 3.4.5

Macintosh PowerPC platform

- gcc / g++ version 3.3
- Absoft f77 / f90 version 8.2a

Compatibility Considerations

To ensure continued support for building your C/C++ programs, consider upgrading to another supported compiler. For an up-to-date list of supported compilers, see the Supported and Compatible Compilers Web page.

Compiler Support To Be Phased Out

The following compilers are supported in Version 7.4 (R2007a) but will not be supported in a future version of MATLAB.

Windows (32-bit) platform

- Intel C++ version 7.1
- Intel Visual Fortran 9.0
- Borland C++Builder 6 version 5.6
- Borland C++Builder 5 version 5.5
- Borland C++ Compiler version 5.5
- Compaq Visual Fortran version 6.6
- Compaq Visual Fortran version 6.1

Additional Linker Support for Intel Fortran

MATLAB V7.4 (R2007a) supports new linkers for building MEX-files with Intel Visual Fortran 9.0.

Windows (32-bit) platform

- Microsoft Visual Studio .NET 2003

- Microsoft Visual Studio 2005

Windows (64-bit) platform

- Microsoft Visual Studio 2005
- Microsoft Platform SDK for Windows Server 2003 (Build 1289 or later)

New COM Features

Programmatically Connect to Instances of a COM Automation Server

MATLAB can now programmatically connect to an instance of a COM Automation server using the new `actxGetRunningServer` function.

Improve the Custom Interface API

Changes to the `actxserver` function allow you to create a COM Automation server using a custom interface.

New COM Data Type Support

Additional COM data type support has been added. See *Handling COM Data in MATLAB Software* for a description of supported data types.

Enhanced Support for COM Interface Events

MATLAB users can take full advantage of event interfaces provided by COM Automation servers. This change is implemented in the `events`, `eventlisteners`, `isevent`, `registerevent`, `unregisterevent`, and `unregisterallevnts` functions.

For an example of this feature, see *Responding to Interface Events from an Automation Server*.

Get the Status of a MATLAB Automation Server

Using the `enableservice` function you can learn the current state of a MATLAB Automation server. The function returns a logical value, where logical 1 (true) means MATLAB is an Automation server and logical 0 (false) means MATLAB is not an Automation server.

For example, if you type

```
enableservice('AutomationServer')
```

and MATLAB displays

```
ans =
```

```
1
```

then MATLAB is currently an Automation server.

Changes to MATLAB Version-Specific ProgID

A programmatic identifier, or ProgID, is used to create a COM component. MATLAB's version-specific ProgID `Matlab.Application.N.M` now lets you specify both a major and minor version number.

For example, to specify MATLAB version 7.4, use the ProgID `Matlab.Application.7.4`.

Changes to Handling Microsoft ActiveX Methods

Beginning in MATLAB Version 7.4 (R2007a), an ActiveX method with the same name as a class is treated as a constructor and cannot be called in the same way as an ordinary method.

In the following example:

```
myApp = actxserver('Excel.Application');
op = invoke(myApp.Workbooks, 'open', 'MyFile.xls');
Sheets = myApp.ActiveWorkBook.Sheets;
target_sheet = get(Sheets, 'item', 'Sheet1');
invoke(target_sheet, 'Activate');
Activesheet = myApp.Activesheet;
cellname = 'B2';
Range = Activesheet.cells.Range(cellname, cellname);
```

the term `Range` is both a function on the MATLAB path and a constructor of the class `Range`. MATLAB tries to execute the function `range`, which generates the error:

```
??? Error using ==> range
Too many input arguments.
```

```
Error in ==> MyScript at 8
Range = Activesheet.cells.Range(cellname, cellname);
```

To get the property value, use the `get` function.

For example:

```
Range = get(Activesheet.cells, 'Range', cellname, cellname);
```


R2006b

Version: 7.3
New Features: Yes
Bug Fixes: Yes

Desktop Tools and Development Environment

Startup and Shutdown

Compatibility Considerations: Yes

New features and changes introduced in Version 7.3 (R2006b) are described here.

Associate Files from MATLAB Program with Windows Operating System Using New Utility

You can run a utility from the Help browser to associate `.m`, `.mat`, `.fig`, `.p`, and `.mdl` files with the MATLAB program in the Microsoft Windows operating system. After running the utility, you will be able to start MATLAB by double-clicking any of those file types in Windows Explorer. You can still use Windows Explorer Folder Options to perform these file associations, but the utility makes the task more convenient. For details, see *Associating Files with MATLAB on Windows Platforms*.

Redirect Output on UNIX Now Sends Errors to Shell

When you start MATLAB on platforms running The Open Group UNIX operating system using the `-nodesktop` startup option, and you redirect output, for example to a file, MATLAB now sends any errors to the shell, while normal output goes to the redirect target. This change was made so that redirection with MATLAB follows standard behavior for the UNIX operating system.

For example:

```
matlab -nodesktop -"r magic(3), magi(5)" > test.txt
```

starts MATLAB in `nodesktop` mode, runs the statement `magic(3)` and writes the output to `test.txt`. When MATLAB runs `magi(5)`, execution fails and MATLAB displays the error message in the shell.

Compatibility Considerations

In previous versions, MATLAB redirected both output and error messages, so in the above example, MATLAB wrote the output of `magic(3)` as well as the error message from `magi(5)` to `test.txt`.

If you have shell scripts that use `>` to redirect output, and you rely on errors appearing in the output target, you need to modify the `matlab` startup statements in those scripts.

To achieve the former behavior, that is, to redirect both output and errors to the specified target, use that specific redirect syntax for your shell. For example, in `tcsh`, use `>&`, as in


```
matlab -nodesktop -"r magic(3), magi(5)" >& test.txt
```

Desktop

New features and changes introduced in Version 7.3 (R2006b) are described here.

M-Lint Preferences Added and Now Appear on M-Lint Panel

M-Lint preferences now appear on a new M-Lint panel. There are new M-Lint preferences to disable specific messages or categories of messages, as well as to save the settings for use in a later session. In addition, you can choose to show or hide messages for the MATLAB Compiler product if the MATLAB Compiler product is installed. These new M-Lint preferences apply to the M-Lint code analyzer operating automatically in the Editor/Debugger as well as to the M-Lint Code Check Report you run via the Current Directory browser Directory Reports or **Tools > M-Lint > Show M-Lint Report**.



Compatibility Considerations

M-Lint preferences were previously accessed via the Editor/Debugger Language settings for M.

Close All Documents and Close Selected Documents Feature Added

When you have multiple documents open within a tool, such as M-files in the Editor/Debugger, select **File > Close** to readily close selected files in that tool. Alternatively, right-click the document bar to close all open documents or all open documents except the selected document in that tool.

Accessibility Documentation Included

Accessibility features and assistive technologies are now part of the Desktop documentation. In prior versions, they were documented in the general Release Notes.

New Look and Feel on Linux and Solaris Platforms

MATLAB has a new look and feel on the Linux operating system from Linus Torvalds and the Sun Microsystems Solaris operating system that affects windows, decorations, color schemes, and responsiveness of the interface in MATLAB.

Compatibility Considerations

All of the changes are cosmetic, except for file dialog boxes, like Open file. The new file dialog boxes are more conventional and easier to use than in previous versions, and there is no loss in functionality.

Invalid info.xml File on Path Now Generates an Error

When MATLAB finds an `info.xml` file on the search path or in the current directory, it assumes the file is intended to add information to the **Start** button or the Help browser, and automatically validates the file against the supported schema. If there is an invalid construct in the `info.xml` file, MATLAB displays an error in the Command Window. The error is typically of the form

```
XML-file failed validation against schema located in
...
XML-file name: full path to...\info.xml
```

and might appear when you start MATLAB, press the **Start** button, or in other situations. For more information about the error and how to eliminate it, see [Add Your Own Toolboxes to the Start Button](#).

Compatibility Considerations

In previous versions, MATLAB displayed a warning when it encountered an invalid `info.xml` file.

Help

Compatibility Considerations: Yes

New features and changes introduced in Version 7.3 (R2006b) are described here.

Exact Phrase and Wildcard Searching Added; Change to Search Database

These improvements were made to the Help browser search feature. Note that they are not supported on Japanese systems.

- Search Field Always Shown — The **Search for** field is now always in view when the Help browser is open. The list of pages found appears in the **Search Results** tab.
- Exact Phrase Searches for More Relevant Results — Find an exact phrase by typing quotation marks around the search term. For example, "plot tools" finds only pages that include plot tools together, but does not find pages that include plot in one part of the page and tools in another part of the page. You can specify more than one exact phrase in a search term, such as "plot tools" "figure palette".
- Wildcards (*) in Search Terms for Variations of a Word (Partial Word Search) — Use the wildcard character (*) in place of letters or digits in your search terms. For example, plot* finds various forms of the word plot, such as plot, plots, and plotting, while p*t find those variations as well as variations of print and part, among others. You can use multiple wildcards in a word or search term.
- Boolean Operator Evaluation Order Changed — Boolean NOT operators in search terms are now evaluated first, followed by ORs, and then ANDs. In prior versions, Boolean operators were evaluated in left to right order.

Compatibility Considerations

The search enhancements were facilitated by changing to a new type of database. As a result, any existing Help search databases for non-Mathworks products will not work in R2006b and beyond. The documentation still displays in the Help browser, but it is not included in searches.

If you use Help browser documentation for non-MathWorks products with a pre-R2006b search database, a message will display in the Help browser to notify you that the documentation will not be included in searches. If you want search to work for that documentation, contact the product provider to request an R2006b-compatible search database.


If you provide documentation for the Help browser and want the documentation to be included in the searches, you need to update the `helpsearch.db` entry in the `info.xml` file to the `helpsearch` directory, and prepare an R2006b-compatible help search database. This process is much easier than in the past. For instructions, contact Technical Support.

Workspace, Search Path, and File Operations

New features and changes introduced in Version 7.3 (R2006b) are described here.

Statistical Results in Workspace Browser

The Workspace browser includes new columns that automatically display results of common statistical calculations: Minimum, Maximum, Range, Mean, Median, Mode, Variance, and Standard Deviation. Use **View > Choose Columns** to specify the columns to show.



The screenshot shows the MATLAB Workspace browser window. The title bar reads "Workspace". The menu bar includes "File", "Edit", "View", "Graphics", "Debug", "Desktop", "Window", and "Help". The toolbar contains icons for file operations and a "Stack" dropdown menu set to "Base". Below the toolbar is a table with the following data:

Name	Value	Min	Max	Range	Mean	Median	Mode	Var	Std
p	[0;10;100]	0	100	100	36.6667	10	0	3033.3333	55.0757

See also **File > Preferences > Workspace** for associated preferences.

Open Larger Arrays in Array Editor

You can open larger arrays in the Array Editor. In previous versions, large arrays would fail to open in the Array Editor.

Editing and Debugging M-Files


Compatibility Considerations: Yes

New features and changes introduced in Version 7.3 (R2006b) are

- “File Comparisons Tool Added” on page 836
- “M-Lint Enhancements for Suppressing Messages, and Showing Messages for the MATLAB® Compiler™ Product” on page 838
- “Restore Breakpoints Using New dbstop Feature” on page 839
- “End Debugging Completely Using New dbquit('all') Option” on page 839

File Comparisons Tool Added

Use the new File Comparisons tool to highlight the differences between two files. Open a file, select **Tools > Compare Against**, and then browse to select the second file or drag it into the tool from the Current Directory browser or Windows Explorer. The two files appear aligned in a window with highlights and indicators for any lines that differ, as shown in this example. For more information, see Comparing Files and Folders.



Use elements in the toolbar to exchange the left-right positions of the two files and to specify the number of columns shown.

You can also run the File Comparisons tool from the desktop by selecting **Desktop > File Comparisons**. Drag a file from the Current Directory browser or Windows Explorer into the tool. Then drag the second file into the tool.

M-Lint Enhancements for Suppressing Messages, and Showing Messages for the MATLAB Compiler Product

These are the new features and changes to M-Lint:

- “General Enhancements—Japanese Messages, and Line Number in Indicator Bar” on page 838
- “Suppressing M-Lint Messages” on page 838
- “Deployment Messages in M-Lint” on page 839

General Enhancements—Japanese Messages, and Line Number in Indicator Bar

- On Japanese systems, messages now appear in Japanese.
- The messages that appear at the indicator bar now includes the line number.

Suppressing M-Lint Messages

The M-Lint automatic code analyzer in the Editor/Debugger now provides a few ways for you to suppress specific messages and categories of messages:

- **Ignore Specific Instance** — Right-click at the underline for an M-Lint message, and from the context menu, suppress just that instance. M-Lint adds `%#0k` and a new message ID tag to the end of the line, which is the syntax in MATLAB for suppressing an M-Lint message.
- **Disable All Instances** — Right-click at the underline for an M-Lint message, and from the context menu, disable all instances of that message in all files. This changes the preference setting for that message.
- **Use Preferences to Disable All Instances** — Select **File > Preferences > M-Lint**, and disable specific messages or categories of messages, which applies to all instances in all files. You can save the

settings to an M-Lint preference file. From the Editor/Debugger, you can select the M-Lint preference file from the **Tools > M-Lint** menu.

The M-Lint Code Check report also uses the preferences and suppresses the display of specific messages and categories of messages, per the preference settings.

Deployment Messages in M-Lint

M-Lint now displays deployment messages for the MATLAB Compiler product, such as *MCC* does not permit the `CD` function, which appear if the MATLAB Compiler product is installed and you select the M-Lint preference to **Show MATLAB Compiler deployment messages**. You can also disable or enable all deployment messages via the Editor/Debugger **Tools > M-Lint** menu. You can suppress specific messages using the same methods as for other M-Lint messages.

Compatibility Considerations

M-Lint preferences were previously accessed via the Editor/Debugger Language settings for M. See also “mlint Message IDs Changed and %#ok Syntax Enhanced” on page 841

Restore Breakpoints Using New `dbstop` Feature

You can save the status of breakpoints to a MAT-file using `s=dbstatus` and restore the breakpoint status at a later time by loading the MAT-file using the new `dbstop(s)` option. For example, set breakpoints in `collatz`. Run `s=dbstatus` to assign the breakpoint status to `s`; use the `'completenames'` option to save absolute pathnames and breakpoint function nesting sequence. Save `s` to a MAT-file by running, for example, `save mydebugsession s`. At a later time, run `load mydebugsession` to restore `s`, and then run `dbstop(s)` to restore the breakpoints.

End Debugging Completely Using New `dbquit('all')` Option

If you debug multiple files at once, you can exit debug mode for all files by running `dbquit('all')`. If you debug `file1` and step into `file2`, running `dbquit` terminates debugging for both files. However, if you debug `file3` and also debug `file4`, running `dbquit` terminates debugging for `file4`, but `file3`

remains in debug mode until you run `dbquit` again. The new `dbquit('all')` option ends debugging for both `file3` and `file4`, and as `dbquit` does, ends debugging for `file1` and `file2`.

Tuning and Managing M-Files

New features and changes introduced in Version 7.3 (R2006b) are described here.

File Comparison Directory Report Removed; Replaced by File Comparison Tool

The File Comparison Report, one of the directory reports available in the Current Directory browser, was removed.

Compatibility Considerations

The new File Comparisons tool replaces the File Comparison Report. The tool provides the same functionality as the report did, and adds new features. For details, see “File Comparisons Tool Added” on page 836.

M-Lint Code Check Report Enhancements and Changes

You can indicate specific messages or categories of messages you want M-Lint to report. For details, see “M-Lint Enhancements for Suppressing Messages, and Showing Messages for the MATLAB® Compiler™ Product” on page 838.

Compatibility Considerations

In previous versions, the M-Lint Code Check report showed all messages except those suppressed via a `%#ok` at the end of a line. Now, the M-Lint Code Check report will show only the messages that are enabled via M-Lint preferences.

mlint Message IDs Changed and %#ok Syntax Enhanced

The `mlint` function with the `-id` option returns message IDs using a new form. For example, when you run

```
mlint('filename.m', '-id')
```

MATLAB Version 7.2 (R2006a) returns

```
L 22 (C 1-9) 2:AssignmentNotUsed : The value ...
```

whereas MATLAB Version 7.3 (R2006b) returns

```
L 22 (C 1-9): NASGU: The value ...
```

The `%#ok` syntax used in M-files to suppress the display of M-Lint messages for a line has been enhanced to support multiple messages per line. For example, given this line in an M-file,

```
data{nd} = getfield(flds,fdata{nd});
```

two M-Lint messages result:

```
34: 'data' might be growing inside a loop; ...  
    consider preallocating for speed.
```

```
34: Use dynamic fieldnames with structures instead of GETFIELD...  
    Type 'doc struct' for more information.
```

In MATLAB Version 7.2 (R2006a), M-Lint messages could only be suppressed for the entire line:

```
data{nd} = getfield(flds,fdata{nd}); %#ok
```

In MATLAB Version 7.3 (R2006b), you can still use `%#ok` to suppress all messages for the line, or you can add an ID tag to indicate the exact messages to suppress. For example, this suppresses only the first message about data growing inside a loop:

```
data{nd} = getfield(flds,fdata{nd}); %#ok<GFLD>
```

To suppress more than one message per line, separate the ID tags with a comma. For example, this suppresses both messages:

```
data{nd} = getfield(flds,fdata{nd}); %#ok<GFLD,AGROW>
```

Compatibility Considerations

In previous versions, the message IDs returned from `mlint` with the `-id` option, were of a form that included a numeric identifier, followed by the category. If you rely on the exact ID values, you will need to make modifications to use the new form.

If you use M-Lint in MATLAB Version 7.3 (R2006b) and then run those files a previous version, M-Lint in the previous version ignores the tag and IDs that follow the `%#ok`, and therefore suppresses all messages for that line, which is the expected behavior for the previous version.

mlintrpt Option Added to Use Preference Settings File

The `mlintrpt` function now accepts a new option that applies the preferences saved to an M-Lint settings file. It works with the `file` or `dir` syntax:


```
mlintrpt('fullpath_to_file', 'file', 'fullpath_to_configfile.txt')
mlintrpt('fullpath_to_dir', 'dir', 'fullpath_to_configfile.txt')
```

For example, create the file `NoSemiSetting.txt` by saving settings in **File > Preferences > M-Lint**. Later, use the settings via preferences or M-Lint in the Editor/Debugger, or via `mlintrpt` as in this example:

```
mlintrpt('lengthofline.m', 'file', 'I:\MATLABFiles\NoSemiSettings.txt')
```

which displays an M-Lint report in the MATLAB Web browser for the `lengthofline` file in the current directory using the M-Lint settings in `I:\MATLABFiles\NoSemiSettings.txt`.

Toolbar Refresh Button Removed

The Profiler included a refresh button  on the toolbar. This button has been removed. It performed an action similar to the **Refresh** button that appears in many of the Profiler reports, so use that button instead.

Publishing Results

Compatibility Considerations: Yes

notebook Setup Arguments Removed

In MATLAB 7.1 (R14SP3), the notebook function was enhanced to automatically detect the version of the Microsoft Word application and other required information. This feature changed the `notebook -setup` syntax—arguments to specify the version of the Microsoft Word application (`wordversion`, `wordlocation`, `templatelocation`) were no longer supported. If you used those arguments, MATLAB ignored them and issued a warning. Now in MATLAB 7.3 (R2006b), if you use those arguments, MATLAB errors.

Compatibility Considerations

If you use `notebook` with the `wordversion`, `wordlocation`, and `templatelocation` arguments in any of your files (for example, `startup.m`), remove them to prevent errors.

Mathematics

New Functions

Function	Description
amd	Interface to the amd algorithm. This interface is similar to that used in symamd, but is typically faster than symamd.
bvpextend	Forms a guess structure for extending the boundary value problem solution
ldl	Full ldl factorization and solving for Hermitian matrices

max and min Now Use Magnitudes and Phase Angle for Complex Input

Compatibility Considerations: Yes

For complex input, `min` and `max` are computed using the magnitude, `min(abs(x))` and `max(abs(x))` respectively. In the case of equal magnitude elements, the phase angle, `min(angle(x))` and `max(angle(x))`, is now used.

Compatibility Considerations

In previous versions, `min` and `max` were computed using the magnitude, and in the case of equal magnitude elements, the first element was used. This behavior was indeterministic and not consistent with the `sort` function.

Code in previous releases that relied on the output of this functionality for the case described above should be updated.

Additional Output from lu

The `lu` function returns an additional output that helps improve numerical stability of sparse `lu` factorization.

Upper and Lower Factors for chol and ld1

Upper and lower triangular factors for chol and ld1 improve performance for sparse chol. Referencing the lower triangle and returning the lower triangular factor is more memory efficient in the case of sparse chol.

Permutation Vectors with `lu`, `luinc`, `ldl`

Permutation vectors for `lu`, `luinc`, and `ldl` provide memory savings and, for large data, a noticeable performance improvement. You can now store permutation information in a single 1-by-N vector instead of an n-by-n matrix,

Two-Element Threshold for lu, spparms

A new two-element threshold for lu and spparms gives you more control over sparse lu and sparse \ behavior.

Lower Triangular Factors from `symbfact`

Extra arguments exported for `symbfact` allow the return of the lower triangular symbolic factor.

Support for New Versions of AMD, COLAMD, CHOLMOD, UMFPACK

MATLAB 7.3 supports new versions of the following libraries:

Library Name	Version Supported in MATLAB 7.3
AMD	2.0
COLAMD	2.5
CHOLMOD	1.1
UMFPACK	5.0

Sparse Arrays on 64-Bit Systems

Compatibility Considerations: Yes

The internal storage of sparse arrays on 64-bit systems has changed in the R2006b release. This change should be invisible to most MATLAB users. However, MEX-file programs that run on a 64-bit system and access sparse arrays must be modified and recompiled in order to run on MATLAB Version 7.3. This applies to existing MEX-files and to any new MEX-files that you write.

If you are affected by this change, you will need to take the following steps to make your code compatible with the new sparse array format:

- Modify all sparse array declaration statements in MEX-files that are to run on a 64-bit system so that they now use the `mwSize` and `mwIndex` types instead of more specific type declarations such as `int` or `INTEGER*4`.
- Change any MEX code that assigns a negative value to a variable used to hold a sparse array index or size. An example of this would be code that temporarily uses an array index as a flag, assigning a `-1` to it to mark the index as unset. Do not try to cast negative `int` values to `mwSize` or `mwIndex`. Instead, change your code to avoid using negative values.
- Recompile these MEX-files using the `-largeArrayDims` option

For a full description of what you will need to do, please read the section “Sparse Arrays on 64-bit Systems” on page 892 in the MATLAB External Interfaces release notes.

Compatibility Considerations

Existing MEX-files that run on 64-bit systems and access sparse arrays in MATLAB will not operate correctly in MATLAB 7.3 unless the required changes outlined above are made and the files are recompiled with the `-largeArrayDims` option. New MEX-files that you create must also adhere to these guidelines.

FFTW Upgraded to Version 3.1.1 in MATLAB

Compatibility Considerations: Yes

The version of FFTW used in MATLAB has been upgraded from 3.0.2 to 3.1.1. Please read the section, below.

Other changes in MATLAB FFTW support are:

- The default planner method is now `estimate`. Previously, `hybrid` was the default.
- There are new syntaxes for importing from and exporting to the library's internal single- and double-precision wisdom databases. These are as follows and are documented in the reference page for the MATLAB `fftw` function:
 - `str = fftw('dwisdom')`
 - `str = fftw('swisdom')`
 - `fftw('dwisdom', str)`
 - `fftw('swisdom', str)`

Compatibility Considerations

FFTW version 3.1.1 does not support wisdom produced by previous versions of the FFTW library. For this reason, FFTW wisdom that has been exported from a previous version of MATLAB cannot be imported successfully in MATLAB R2006b. Trying to import “old” wisdom results in a warning.

Future Obsolete Functions

Compatibility Considerations: Yes

The `betacore` function generates a warning message in R2006b but completes successfully. This function will be made obsolete in a future release.

Compatibility Considerations

You should remove all instances of the `betacore` function from your M-file program code. This function will not be supported in a future release of MATLAB.

Obsolete Functions

Compatibility Considerations: Yes

The following uses of MATLAB functions are obsolete as of this release. Attempts to use this functionality in the R2006a release generate a warning message but complete successfully. In R2006b, these operations fail and generate an error message.

- The following functions in their entirety: `bvpval`, `quad8`, `table1`, `table8`, `bessela`
- The `sort` function, when used with complex integer inputs
- The `gt`, `ge`, `lt`, and `le` functions, when used with complex integer inputs
- The `beta` function, when used with 3 inputs
- The `gamma` function, when used with 2 inputs
- The `opts.cheb` and `opts.stagtol` fields in the options structure of `eigs`

Compatibility Considerations

You will need to remove all instances that reference these functions at this time. These functions are no longer supported in MATLAB.

max and min No Longer Return Warning Messages for Inputs with Different Data Types

Compatibility Considerations: Yes

In MATLAB version 7.0 (Release 14), the functions `max` and `min` were changed to return results of a different data type than in previous releases. This behavior is described in `max` and `min` Now Have Restrictions on Inputs of Different Data Types. This change in behavior produced warning messages to assist you with diagnosing any resulting issues. In R2006b, these warning messages no longer exist.

Compatibility Considerations

The warning messages for mixed-type inputs to the functions `max` and `min` are no longer produced. Turning warning messages on will no longer display messages for this behavior, and you will no longer be able to depend on the messages for the diagnosis of problems.

Data Analysis

Generate M-File Now Supports Basic Fitting and Data Statistics

The **Generate M-File** option on the **File** menu of MATLAB figure windows now generates code that reproduces plot objects created with the Basic Fitting Tool or the Data Statistics Tool. The generated M-file function accepts new data as input and creates plot objects with the same graphics properties as those in the generating figure. In addition, the M-file recomputes fits and statistics for the new data. The code shows you how to program what you do interactively with the Basic Fitting Tool or the Data Statistics Tool.

New Options for Working with Time Series Objects

- Time Series Tools are now easier to find. From the MATLAB **Start** button, select **MATLAB > Time Series Tools**.
- Time series objects are now fully supported by the Array Editor. When you open a `timeseries` object (using `open` or the Workspace browser), the editor from Time Series Tools appears in the Array Editor.
- Time series objects can now be opened directly in Time Series Tools. Select a `timeseries` object in the Workspace browser, right click, and choose **Open in Time Series Tools** from the context menu.
- In Time Series Tools, you can now change subplot indices interactively. Click on a plotted line in a time series view and drag and drop it from one subplot to another. To create a new subplot, drag and drop the plotted line below the bottom axes.

Programming

Saving to MAT-Files Larger than 2 GB

Compatibility Considerations: Yes

With MATLAB R2006b, you can save data items that are over 2 gigabytes in size. This capability is implemented in MATLAB using a new HDF5-based format for MAT-files.

To save to a MAT-file in this format, specify the new `-v7.3` option with the `save` function:

```
save -v7.3 myfile v1 v2
```

Note MATLAB Version 7.3 does not write MAT-files in HDF5 format by default in this release; you must explicitly specify the `-v7.3` switch.

In this release,

- The default MAT-file format employed by `save` is the standard MAT-file format used in the R14, R14SP, and R2006a releases. You can explicitly specify this format with the command `save -v7`.
- To write an HDF5-based MAT-file, you must use `save -v7.3`.
- HDF5-based MAT-files are *not* compressed.

In a future release,

- The default MAT-file format will be the HDF5-based format. You can explicitly specify the HDF5-based format with the command `save -v7.3`.
- To write the standard MAT-file format, you must use `save -v7`.
- As of release R2008a, HDF5-based MAT files are compressed.

Here is a summary of the version options that you can use with `save`:

save Option	Description	Available In	Is the Default In
save -v4	Save to a MAT-file you can open in MATLAB version 4	V5 and later	V4, V5
save -v6	Save to a MAT-file you can open in MATLAB versions 5 or 6	V7 and later	V6
save -v7	Save to a MAT-file you can open in MATLAB version 7	V7.3 and later	V7.3
save -v7.3	Save to a MAT-file that supports data items ≥ 2 GB	V7.3 and later	post V7.3

Compatibility Considerations

If you are running MATLAB on a 64-bit computer system and you attempt to save a variable that is too large for a version 7 (or earlier) MAT-file, that is, you save without using the -v7.3 option, MATLAB skips that variable during the save operation and issues a warning message to that effect.

If you are running MATLAB on a 32-bit computer system and attempt to load a variable from a -v7.3 MAT-file that is too large to fit in 32-bit address space, MATLAB skips that variable and issues a warning message to that effect.

Import Wizard Generates Import M-Code

The Import Wizard now includes an automated M-code generation option. Click the Generate M-code button located in the lower right of the Import Wizard window and MATLAB generates an M-file that you can use to import additional files that are similar in type to the file you are currently importing. This simplifies the process of importing multiple files into MATLAB.

New Dynamic Regular Expression Syntax

The new (?@cmd) operator specifies a MATLAB command that `regexp` or `regexpi` is to run while parsing the overall match expression. Unlike the other dynamic expressions in MATLAB, this operator does not alter the contents of the expression it is used in. Instead, you can use this functionality to get MATLAB to report just what steps it's taking as it parses the contents of one of your regular expressions. This can be helpful in debugging regular expressions, for example.

New Reserved MATLAB Keywords

Compatibility Considerations: Yes

Two new reserved keywords have been added to the MATLAB language in this release:

- `parfor` – designates a for loop in the Distributing Computing Toolbox
- `classdef` – signals the beginning of a MATLAB class definition

The `iskeyword` function returns `true` for each of these functions, thus identifying them as reserved keywords in MATLAB:

Compatibility Considerations

MATLAB keywords are reserved for use internal to MATLAB, and should not be used in your own program code as identifiers or function names. If your code uses either of these two new keywords in this manner, you should modify your code and use words that are not reserved.

Enhancements to Display Generated by whos

Compatibility Considerations: Yes

The visual output of the information returned by `whos` looks slightly different in R2006b than in previous releases. Changes are as follows:

- There is a new column in the output called `Attributes` that identifies values that are `sparse`, `complex`, `global`, or `persistent`.
- The words “array” and “object” have been dropped from items under the `Class` heading. Items formerly listed as `double array` or `timer object`, for example, are now displayed as `double`, and `timer`.
- MATLAB no longer includes summary information showing the “Grand total” of elements and bytes at the bottom of the `whos` output display.
- There is an additional field in the structure returned by `whos`. This new field is `'persistent'` and is set to logical 1 for those variables that are persistent, or logical 0 otherwise.

Here is an example of the information displayed by `whos` in MATLAB 7.3:

```
whos
  Name           Size           Bytes  Class           Attributes

vCell           5x7             2380  cell
vComplex        6x2             192   double          complex
vDouble         6x5x9          2160  double
vFuncHdl        1x1             16    function_handle
vGlobal         0x0             0     double          global
vObject         1x1            248   timer
vPersist        0x0             0     double          persistent
vSparse         15x15          244   double          sparse
vStruct         1x3            804   struct
```

Compatibility Considerations

If any of your programs depend on the displayed output of `whos`, specifically in relation to the changes listed above, you might have to modify your program code. Also, if your code relies on a specific number of fields for the output structure, you should be aware that this release adds a new field: `persistent`.

unique Function Returns First and Last Indices

Using the new `first` option with the `unique` function returns a vector with elements that represent the *lowest* indices of unique elements in the input vector.

Given the following vector A

```
A = [16 7 5 41 2 16 8 2 6 3 16 6 2 5 2 5];
```

Get a sorted vector of the unique elements of A:

```
v = unique(A)
v =
     2     3     5     6     7     8    16    41
```

Use the `first` and `last` options to get indices of the first and last elements in A that make up the sorted vector v:

```
[v, m1] = unique(A, 'first');
m1
m1 =
     5    10     3     9     2     7     1     4
```

```
[v, m2] = unique(A, 'last');
m2
m2 =
    15    10    16    12     2     7    11     4
```

save Compression and Unicode Options Removed

Compatibility Considerations: Yes

In MATLAB Versions 7.0 through 7.2, you could use the switches `compress`, `nocompress`, `unicode`, and `nounicode` with the `save` function to enable or disable compression and Unicode character encoding in the MAT-file being generated. In MATLAB Version 7.3, the `save` function no longer supports these switches. Instead, `save` now creates a MAT-file with compression and Unicode character encoding by default, or with the following command:

```
save -v7 filename
```

You can still save to a MAT-file without using compression or Unicode encoding. In fact, you will have to do this in order to create MAT-files that you can load into a MATLAB Version 6 or earlier. To save to a MAT-file without compression or Unicode encoding, type

```
save -v6 filename
```

To disable compression and Unicode encoding for all `save` operations in a MATLAB session, open the MATLAB **Preferences** dialog, select **General** and then **MAT-Files**, and then click the button labelled **Ensure backward compatibility (-v6)**.

Compatibility Considerations

If you have code that uses any of these option switches with the `save` function, you will need to modify that code to use the `v6` option instead.

Warning Generated by try-catch

Compatibility Considerations: Yes

To accommodate future changes in the MATLAB error handling capabilities, MathWorks has added a new restriction to the single-line syntax of the try-catch block. In this release, the following syntax operates as it did in previous releases, but now it also generates the following warning message:

```
try try_statements, catch catch_statements, end
```

Warning: This try-catch syntax will continue to work in R2006b, but may be illegal or may mean something different in future releases of MATLAB.

To make this single-line try-catch work without warning in R2006b, you must insert a separator character (comma, semicolon, or newline) immediately after the word catch

```
try try_statements, catch, catch_statements, end
```

As with previous releases, the recommended syntax for a try-catch block is as follows:

```
try
    try_statements
catch
    catch_statements
end
```

Compatibility Considerations

Your M-file programs may generate this warning if correct syntax for try and catch is not used.

Case-Sensitivity Warning Removed

Compatibility Considerations: Yes

The following warning has been removed from MATLAB in release R2006b:

```
"Function call foo invokes /somewhere/on/the/path/foo.m,
however, function /somewhere/ahead/on/the/path/FOO.m that
differs only in case precedes it on the path."
```

In previous versions of MATLAB, this warning message was triggered when you called a function such as `foo`, and all of the following were true:

- There was more than one MATLAB file of this name on the MATLAB path
- The names of these files differed only in letter case, and
- A MATLAB file of this name but with different case (e.g., `FOO.m`) preceded a file of matching case (e.g., `foo.m`) on the path

Earlier versions of MATLAB displayed this warning for the purpose of helping users cope with newly-introduced case sensitive dispatching changes. The warning is being removed at this time under the assumption that users are now sufficiently well-acquainted with the way MATLAB handles case sensitivity in function calls.

Compatibility Considerations

The dispatching behavior regarding to the case sensitivity is NOT changed with the removal of this warning message. If both an exact match and inexact match are present on the path, the exact match is always the one to be invoked.

fprintf(0,...) Now Throws an Error

Compatibility Considerations: Yes

Commands such as `fprintf(0, ...)` and `fwrite(0, ...)`, in which the file identifier is zero (the same as `stdin`) now result in an error being thrown. In previous releases, MATLAB did not throw an error in response to these commands, even though printing or writing to `stdin` is clearly not a valid option.

Compatibility Considerations

If any of your programs use lower-level MATLAB file I/O functions that send output to `stdin`, because these functions no longer ignore this type of operation, your code will now generate an error. You should modify your program code to use a file identifier other than zero.

Assigning Nonscalar Structure Array Fields to a Single Variable

Compatibility Considerations: Yes

In the R14 and R14 service pack releases of MATLAB, assigning a nonscalar structure array field to a single variable incorrectly resulted in an error. For example, in the following code, you should be able to assign `S.A` to one, two, three, or four output variables. However, if you assign to just a single variable, MATLAB throws an error:

```
% Create a 1-by-4 structure array S with field A.
S(1).A = 1;   S(2).A = 2;   S(3).A = 3;   S(4).A = 4;

% Assigning S(1).A and S(2).A works as expected.
[x y] = S.A
x =
     1
y =
     2

% Assigning only S(1).A should work, but does not.
x = S.A;
??? Illegal right hand side in assignment. Too many elements.
```

This has been fixed in MATLAB 7.3.

Compatibility Considerations

If any of your programs rely on this error being thrown, you will need to modify those programs.

Comma Separators Not Required in Function Declaration

Compatibility Considerations: Yes

As of Release 14, the function definition line in a function M-file no longer requires commas separating output variables. This now makes the function definition syntax the same as the syntax used when calling an M-file function:

```
function [A B C] = myfun(x, y)
```

Compatibility Considerations

This new syntax is not valid in MATLAB versions earlier than Release 14. When writing an M-file that you expect to run on versions both earlier and later than R14, be sure to separate any output variables in the function definition line with commas:

```
function [A, B, C] = myfun(x, y)
```

Improved Performance on Certain Platforms and Operations

In this release, MATLAB offers improved performance in the following areas:

- Improved performance on 64-bit Windows XP and Linux platforms. This is independent of the size of data set in use.
- Faster scalar indexing into cell arrays.
- Faster assignment of cell array data to variables.

Graphics and 3-D Visualization

Plotting Tools Are Now Modular Desktop Components

The three MATLAB plotting tools (Figure Palette, Property Editor, and Plot Browser) now function as desktop components like the Workspace Browser and the Array Editor. They dock, however, not to the MATLAB desktop but to a Figures window. Figures windows contain one or more figures, each of which is accessible by a tab. Turning on any plotting tool changes your figure group into a mini-desktop. You can undock, rearrange, tab, and resize the plot tools within the mini-desktop, and their state will persist across MATLAB invocations. There are just one set of plot tools for all your figures, but they only operate on figures contained in the group; undocked figures are free of the plotting tools until you redock them.

For more information see [Plotting Tools – Interactive Plotting in the MATLAB Graphics documentation](#).

Version 6 Property Editor Has Been Removed

Compatibility Considerations: Yes

The MATLAB Version 6 Property Editor, one of the Plotting Tools, is no longer available. This means that the 'v6' switch for the `propedit` function now produces an error instead of starting the version 6 property editor. The error message is

```
??? Error using ==> propedit
The Version 6 property editor is no longer available. Sorry!
```

Compatibility Considerations

If you have code that calls the version 6 property editor, you will need to modify it to use the modular plotting tools described above in “Plotting Tools Are Now Modular Desktop Components” on page 879. The `propedit` function remain otherwise the same.

New Desktop Printing GUI

Compatibility Considerations: Yes

Printing MATLAB figures has become easier as a result of combining the **Page Setup**, **Print Setup**, and **Print Preview** dialogs into one tabbed **Print Preview** dialog. You can now specify paper size, plot size and layout, color and line weight, header text, rendering, and other printing characteristics in this new dialog. The **Page Setup** and **Print Setup** dialogs still exist, and the **Print** dialog that you call from **File** → **Print** remains the same. The **Page Setup** dialog is available on all platforms.

For more information, see Using Print Preview in the MATLAB Graphics documentation and `printpreview` in the MATLAB function reference documentation.

Compatibility Considerations

The **Page Setup** dialog no longer is available from the figure window **File** menu. However, it does continue to exist; you can raise it using the `pagesetupdlg` command. The old **Print Preview** dialog has been removed, however. The old **Print Setup** dialog can be raised using the command

```
print -dsetup
```

When you dismiss the **Print Setup** dialog with **OK**, the settings you made with it are saved, but nothing is printed at that time.

Zoom Mode Now Supports Mouse Scroll Wheel

If your mouse has a center scroll wheel, you can use it to zoom in and out of axes, as well as by clicking and/or dragging.

You can zoom in by positioning the mouse cursor where you want the center of the plot to be and either press the mouse button or rotate the mouse scroll wheel away from you (upward). Zoom out by positioning the mouse cursor where you want the center of the plot to be and either simultaneously press **Shift** and the mouse button, or rotate the mouse scroll wheel toward you (downward). Each mouse click or scroll wheel click zooms in or out by a factor of 2.

Data Cursor Text Can Now Be Programmatically Modified

You can now easily customize the text of datatips. The `datacursormode` function lets you specify the contents and formatting of text displayed by the data cursor tool. When the data cursor tool is active, you can use its context (right-click) menu to edit or specify the text update function that MATLAB executes to display datatips. For more information, see [Data Cursor — Displaying Data Values Interactively](#) in the MATLAB Graphics documentation and `datacursormode` in the MATLAB Function Reference documentation.

Customizing Zoom, Pan, and Rotate3D Data Explore Modes

Compatibility Considerations: Yes

You can now customize the behavior of data explore modes by modifying the zoom, pan and rotate3d objects that are dereferenced as follows:

```
h = pan(figure_handle)
h = rotate3d(figure_handle)
h = zoom(figure_handle)
```

These syntaxes create *mode objects* that you can use to control the behaviors of the explore tools. Among the effects you can achieve using these explore mode objects are

- Allow, change, or inhibit a mode for a specified axes
- Create callbacks for pre- and post-buttonDown events
- Change callbacks dynamically

See `pan`, `rotate3d`, and `zoom` in the MATLAB Function Reference documentation for details and examples.

Compatibility Considerations

Using mode objects can cause a forward incompatibility. In prior releases, explore modes did not return an argument. Therefore, code such as the above examples that you write to take advantage of the new API will not run in MATLAB versions prior to R2006b. `zoom`, `pan`, and `rotate3d` code written for previous MATLAB versions, however, will run as before (there is no backward incompatibility).

Improvements to MATLAB Graphics Documentation

A new section in the Graphics User Guide, *Types of MATLAB Plots*, now includes a gallery of graphs that catalogs the kinds of plots that you can create using MATLAB graphics functions. There are two tables containing labeled icons, one for Two-Dimensional Plotting Functions, and one for Three-Dimensional Plotting Functions, classified by plot type. Clicking the function name above any thumbnail plot in the gallery opens the reference documentation for that function.

Reference pages for functions that create, edit, annotate, and save plots have been enhanced in several ways:

- Thumbnail figures at the top of plotting functions and related GUI reference pages illustrate what you see when you invoke these functions.
- *GUI Alternatives* sections above syntax descriptions describe how to invoke a function (or similar capability) from a GUI, and provide links to relevant topics in the Graphics and Desktop Tools User Guides.
- Revised printing documentation in user guides and reference pages (see “New Desktop Printing GUI” on page 881, above)
- Numerous corrections and clarifications of details in user guides and reference pages

Creating Graphical User Interfaces (GUIs)

Functions Are Now Obsolete

Compatibility Considerations: Yes

The following functions are obsolete in MATLAB 7.3 (R2006b): `axlimdgl`, `edtext`, `menubar`, `pagedlg`, `umtoggle`.

Compatibility Considerations

The functions shown in the following table will continue to work but their use will generate a warning message. As soon as possible, replace any occurrences you may have of these functions with the function(s) shown in the following table, if any, or with other suitable code.

Function	Replacement
<code>axlimdgl</code>	None
<code>edtext</code>	Set the <code>Editing</code> property of the <code>text</code> object.
<code>menubar</code>	Set the <code>MenuBar</code> property of the figure to <code>none</code> .
<code>pagedlg</code>	<code>pagesetupdlg</code>
<code>umtoggle</code>	Set the <code>Checked</code> property of the <code>uimenu</code> object.

Colored Buttons on Windows XP

Compatibility Considerations: Yes

Setting the background color of user interface control (uicontrol) push buttons and toggle buttons on Windows XP now results in flat, colored buttons.

Compatibility Considerations

Prior to this release, if you set the background color of a push button or toggle button to any color other than the factory color on Windows XP, the color displayed only as a border around the button. With this release, any such buttons will display as flat, colored buttons with a simple border.

Documentation Enhancement

The Creating GUIs Programmatically section of the documentation now contains information commensurate with information in the Creating GUIs with GUIDE section. It adds, in workflow order, information and many basic examples about:

- Adding components, menus, and toolbars to your GUI. Placing and aligning components.
- Designing for cross-platform compatibility.
- Initializing the GUI and creating callbacks.
- Callback examples for the different components.

External Interfaces/API

New Types for Declaring Size and Index Values

Version 7.3 (R2006b) defines two new types for API arguments and return values. These are

- `mwSize` — represents size values, such as array dimensions and number of elements.
- `mwIndex` — represents index values, such as indices into arrays.

Using these types in array declarations replaces more specific type declarations such as `int` or `INTEGER*4`. In general, using these types consistently in your C or Fortran source files can insulate your code from changes in the API implementation that might take place between different versions of MATLAB.

The `mwSize` and `mwIndex` types are required when working with functions that access sparse arrays on a 64-bit system. This is described in the release note on “Sparse Arrays on 64-bit Systems” on page 892, below.

Note In Fortran, `mwSize` and `mwIndex` are implemented as preprocessor macros. To use these types in Fortran code, add the declaration `#include "fintf.h"` in your source file and build your MEX-files using the Fortran preprocessor.

Sparse Arrays on 64-bit Systems

Compatibility Considerations: Yes

The internal storage of sparse arrays on 64-bit systems has changed in the R2006b release. Due to this change, you will need to

- Change declaration statements in your source code so that you use the new types `mwSize` and `mwIndex` in place of specific type declarations such as `int` or `INTEGER*4`. This is described in the section “New Types for Declaring Size and Index Values” on page 891, above.
- Recompile all MEX-files that interact with sparse arrays using the new `-largeArrayDims` switch. For more information about the `-largeArrayDims` switch, see the section “New MEX Switch” on page 892, below.

See the section on to find out if you will need to make any modifications to your existing MEX code to accommodate these changes.

Sparse API Functions Affected By This Change

You will need to recompile any MEX-files that use the following sparse functions on a 64-bit system:

- `mxGetIr`
- `mxGetJc`
- `mxSetIr`
- `mxSetJc`

New MEX Switch

In order to build MEX-files that use any of the sparse array functions listed above, you need to compile these files with the `-largeArrayDims` switch, as shown here:

```
mex -largeArrayDims filename
```

Also, any existing MEX-files that interact with sparse arrays in MATLAB Version 7.3 must be recompiled using the `-largeArrayDims` switch.

Note The `-largeArrayDims` option is likely to become the default in a future version of MATLAB.

Compatibility Considerations

If you are using any of the functions listed above, then you should be aware of the following potential compatibility issues if your MEX code uses sparse arrays on a 64-bit system:

- In release R2006b, you must rebuild all MEX-files that use sparse arrays using the new `-largeArrayDims` switch.
- Before building your MEX-files, change your C or Fortran sources to use the `mwSize` or `mwIndex` types introduced in this release. See the `mxArray` reference pages for the types to use for each function.
- MEX-files that compiled properly in Version 7.2 (R2006a) and do not use sparse arrays should build and execute correctly in Version 7.3 (R2006b) without changes.
- For more information on how the sparse API is affected, see the [Sparse Arrays on 64-Bit Systems](#) section in the MATLAB Mathematics release notes.

New MAT-File Format Based on HDF5

Compatibility Considerations: Yes

In Version 7.3 (R2006b), you can save MAT-files in a format based on HDF5. Unlike earlier MAT-file formats, the HDF5-based format is capable of saving variables that occupy more than 2 GB of storage, including large arrays created on 64-bit systems.

To save a MAT-file in the HDF5-based format, use the `-v7.3` option to the MATLAB `save` function or the `"w7.3"` mode argument to the C or Fortran `matOpen` function. The default MAT-file format is the same as that in Version 7.2 (R2006a).

Compatibility Considerations

Earlier versions of MATLAB cannot read MAT-files written in the HDF5-based format.

MAT-files written with MATLAB Version 7.3 (R2006b) on a 64-bit system can be read back into MATLAB 7.3 on a 32-bit system, provided that none of the values stored in the MAT-file require more than 32 bits to store.

-V5 Option to MEX to Be Removed

Compatibility Considerations: Yes

The -V5 option to mex is not supported in this and future versions of MATLAB.

Compatibility Considerations

You will no longer be able to build a MEX-file that is compatible with MATLAB Version 5.

Location of mex.bat File Changed

Compatibility Considerations: Yes

In MATLAB Version 7.3, the Microsoft Windows script `mex.bat` is located in the directory `$MATLAB\bin`.

Compatibility Considerations

You may need to change any scripts or environment variables that relied on the previous location of `mex.bat`.

Changes to Compiler Support

Compatibility Considerations: Yes

Compaq Visual Fortran version 6.1 is supported in Version 7.3 (R2006b) but will not be supported in a future version of MATLAB.

Compatibility Considerations

To ensure continued support for building your Fortran programs, consider upgrading to another supported compiler. For an up-to-date list of supported compilers, see the [Supported and Compatible Compilers Web page](#).

Actxcontrol Command Now Validates ProgID

Compatibility Considerations: Yes

Attempting to insert a COM server into a MATLAB figure can result in unpredictable behaviors. To prevent this condition, the `actxcontrol` command now checks the ProgID by looking at the registry's HKR/CLSID/Control keyword and throws an error if the ProgID does not belong to a Microsoft ActiveX control.

Compatibility Considerations

Before the validation check was added, some server ProgIDs worked with `actxcontrol`, probably because there are cases where Microsoft software points the server GUID to a control GUID underneath. An example of a ProgID that might not work with `actxcontrol` is the Windows Media® Player server ProgID `Mediaplayer.mediaplayer.1`. Therefore, depending on how Microsoft software registers the control, the following command might now return an error:

```
h = actxcontrol('Mediaplayer.mediaplayer.1'); % Returns an error
```

The correct ProgID to use for `Mediaplayer` is the ActiveX control ProgID:

```
h = actxcontrol('WMPlayer.OCX.7'); % Use control ProgID
```

Note that methods and properties to open and play files are different when using the control ProgID.

You can disable the validation check with the following command:

```
feature('COM_ActxProgIdCheck',0)
```

Or reenable it with:

```
feature('COM_ActxProgIdCheck',1)
```

By default, ProgID checking is on.

R2006a

Version: 7.2
New Features: Yes
Bug Fixes: No

Desktop Tools and Development Environment

Startup and Shutdown

Compatibility Considerations: Yes

New features and changes introduced in Version 7.2 (R2006a) are described here.

Installation Directory Structure on Windows Platforms

The installation directory structure on Microsoft Windows platforms is slightly different than in previous versions. By default, the structure now includes a general MATLAB top level directory, with a subdirectory for R2006a. The root directory for the MATLAB software returned by the `matlabroot` function, is now of the form in this example:

```
D:\Applications\MATLAB\R2006a
```

In previous versions, the top-level directory included the version number, so the root directory for MATLAB, as returned by the `matlabroot` function, was of the form in this example:

```
D:\Applications\MATLAB 7.1
```

Compatibility Considerations

If you relied on the explicit root directory structure for MATLAB in your code, change it to reflect the new structure including the top-level MATLAB directory. The `matlabroot` function might be useful.

Error Log Reporting

If MATLAB experiences a segmentation violation, it generates an error log. Upon the next startup, MATLAB prompts you to e-mail the error log to The MathWorks. The MathWorks uses the log to work on resolving the problem. When you send a log, you receive a confirmation e-mail and will only receive further e-mails if The MathWorks develops a fix or workaround for the problem.

There are some situations where the Error Log Reporter does not open, for example, when you start MATLAB with a `-r` option or run in deployed mode. If you experience segmentation violations but do not see the Error Log

Reporter on subsequent startups, you can instead e-mail logs by following the instructions at the end of the segmentation violation message in the Command Window.

JVM Software Updated for 64-Bit Linux Platforms

The Sun Microsystems JVM software version that MATLAB uses is now version 1.5.0_04 for 64-bit platforms running the Linux operating system from Linus Torvalds.

Desktop

Compatibility Considerations: Yes

New features and changes introduced in Version 7.2 (R2006a) are described here.

Preferences Reorganized and New Keyboard Pane Added to Support Command Window and Editor/Debugger

Preferences includes a new pane, **Keyboard**, for setting key bindings, tab completion, and delimiter-matching preferences for the Command Window and Editor/Debugger. Most of these preferences were previously located in the preference panes for the Command Window or Editor/Debugger.

Compatibility Considerations

You no longer access keyboard and indenting preferences for the Command Window and Editor/Debugger from the component preferences, but rather from the new **Keyboard** preferences. In addition, some preferences that were set separately for these components are now shared. For details about the changes, see “Keyboard and Indenting Command Window Preferences Reorganized” on page 904, and “Keyboard and Indenting Editor/Debugger Preferences Reorganized” on page 909.

Open All Desktop Tools from Desktop Menu

You can now open (and close) all desktop tools from the **Desktop** menu. In previous versions, you could not access document-based tools from the **Desktop** menu. The document-based desktop tools are: Editor/Debugger, Figures, Array Editor, and Web Browser.

Access Login Renamed to MathWorks Account

Use **Help > Web Resources > MathWorks Account** menu items to go to your MathWorks Account if you are registered, or to register online. MathWorks Account was previously called Access Login.

Running Functions – Command Window and Command History

New features and changes introduced in Version 7.2 (R2006a) are described here.

Keyboard and Indenting Command Window Preferences Reorganized

The Command Window Keyboard and Indenting preferences pane was removed. The tab size preference is now on the Command Window preferences pane. The tab completion, keybinding, and parentheses matching preferences were moved to the new Keyboard preferences pane. The parentheses-matching preferences are now called delimiter-matching preferences and are shared with the Editor/Debugger.

Help

New features and changes introduced in Version 7.2 (R2006a) are described here.

help for Model Files

You can now use the `help` function to get the complete description for MDL-files. For example, run

```
help f14_dap.mdl
```

MATLAB displays the description of the F-14 Digital Autopilot High Angle of Attack Mode model in the Simulink software, as defined in its **Model Properties > Description:**

```
Multirate digital pitch loop control for F-14 control design demonstration.
```

Workspace, Search Path, and File Operations

New features and changes introduced in Version 7.2 (R2006a) are described here.

toolboxdir function added

The `toolboxdir` function returns the absolute pathname to the specified toolbox. It is particularly useful with the MATLAB Compiler product because the toolbox root directory is different than in MATLAB.

Visual Directory View Removed

The Visual Directory view was removed from the Current Directory browser. Most of the features it provided are accessible from the Current Directory browser standard view.

Editing and Debugging M-Files

New features and changes introduced in Version 7.2 (R2006a) are

- “Tab Completion — Tab Now Completes Function and Variable Names” on page 907
- “Go Menu Added; Bookmark and Go To Items Moved from Edit Menu to Go Menu” on page 908
- “Navigate Back and Forward in Files” on page 909
- “Keyboard and Indenting Editor/Debugger Preferences Reorganized” on page 909
- “M-Lint Automatic Code Analyzer Checks for Problems and Suggests Improvements” on page 909
- “Debugging Changes” on page 910
- “Cell Mode On by Default — Shows Cell Toolbar and Possibly Horizontal Lines and Yellow Highlighting; Cell Information Bar and Button Added” on page 911
- “Lines Between Cells” on page 913
- “Cell Titles in Bold Preference Removed” on page 913

Tab Completion — Tab Now Completes Function and Variable Names

You can now use tab completion in the Editor/Debugger to complete function names and variable names that are in the current workspace. When you type the first few characters of a function or variable name and press the **Tab** key, the Editor/Debugger displays a list of all function and variable names that begin with those letters, from which you choose one.

It operates essentially the same way as the existing tab completion feature in the Command Window, with the exception that Editor/Debugger tab completion does not support completion of file and path names.

To enable tab completion in the Editor/Debugger, select **File > Preferences > Keyboard**, and then under **Tab completion**, select **Tab key narrows completions**. By default, the preference is selected.

With tab completion enabled in the Editor/Debugger, you can still include tab spacing, for example, to include a comment at the end of a line. To add tab spacing, include a space after the last character you type and then press **Tab**. Instead of showing possible completions, the Editor/Debugger moves the cursor to the right where you can continue typing.

Compatibility Considerations

If you press the **Tab** key to add spacing within your statements, you might instead get a completion for a function or see a list of possible completions. For example, if the preference for tab completion is on and you want to create this statement

```
if a=mate    %test input value
```

where you press **Tab** after `mate` to achieve the spacing, the following happens instead

```
if a=material
```

This is because the tab completion preference completes `mate`, automatically supplying the `material` function.

To achieve the spacing with **Tab** (as in previous versions), either add a space after `mate` and then press **Tab**, or turn off the preference **Tab key narrows completions** in Keyboard Preferences.

Go Menu Added; Bookmark and Go To Items Moved from Edit Menu to Go Menu

- To set, clear, and navigate to bookmarks, use the menu items in the new **Go** menu, which were previously located in the **Edit** menu.
- The **Go To** feature for navigating to line numbers, functions in M-files, and cells has moved to the new **Go** menu. It was previously located in the **Edit** menu.

Compatibility Considerations

Use the new **Go** menu items instead of **Edit > Bookmark** features and **Edit > Go To**.

Navigate Back and Forward in Files

Use **Go > Back** (and **Go > Forward**) to go to lines you previously edited or navigated to in a file, in the sequence you accessed them. The main benefit of this feature is going directly to lines of interest. As an alternative to the menu items, use the Back and Forward buttons on the toolbar.


Keyboard and Indenting Editor/Debugger Preferences Reorganized

The Editor/Debugger **Keyboard and Indenting** preferences pane was renamed to **Tab** preferences, and keybinding and parentheses-matching preferences were moved to the new **Keyboard** preferences pane. The parentheses-matching preferences are now called delimiter-matching preferences and are shared with the Command Window.

M-Lint Automatic Code Analyzer Checks for Problems and Suggests Improvements

The M-Lint code analyzer, now built into the Editor/Debugger, continuously checks your code for problems and recommends modifications to maximize performance and maintainability. It performs the same analysis as the existing M-Lint Code Check report, but also provides these features:

- Indicates the problem lines and associated M-Lint messages directly in the M-file rather than in a separate report.
- Identifies (underlines) code fragments within a line that result in M-Lint messages.
- Distinguishes messages that report errors (red) from warnings and suggestions (orange).
- Continually analyzes and updates messages as your work so you can see the effect of your changes without having to save the M-file or rerun an M-Lint report.




To use or turn off M-Lint in the Editor/Debugger, select **File > Preferences > Editor/Debugger > Language**, and for **Language**, select **M**. Under **Syntax**, select **Enable M-Lint messages**, or clear the check box to turn it off. Use the associated drop-down list to specify the types of code fragments that you want M-Lint to underline, for example, **Underline warnings and errors**.

Debugging Changes

- The `dbstop` function now allows you to stop at, (not in), a non M-file, allowing you to view code and variables near it in your M-file. For example, if you want to stop at the point in your M-file `myfile.m` where the built-in `clear` function is called, run `dbstop in clear; myfile`. Use this feature with caution because the debugger stops in M-files it uses for running and debugging if they contain the non M-file, and then some debugging features do not operate as expected, such as typing `help functionname` at the `K>>` prompt.

Cell Mode On by Default – Shows Cell Toolbar and Possibly Horizontal Lines and Yellow Highlighting; Cell Information Bar and Button Added

Cell mode, a useful feature in the Editor/Debugger for publishing results and rapid code iteration, is now enabled by default. An M-file cell is denoted by a %% at the start of a line. Any M-file that contains %% at the start of a line is interpreted as including cells. The Editor/Debugger reflects the cell toolbar state and the cell display preferences, such as yellow highlighting of the current cell and gray horizontal lines between cells.

For quick access to information about using cells in M-files, use the new information  button on the cell toolbar.

%% at the start of a line denotes a cell, used for publishing or rapid code iteration. The current cell is highlighted in yellow.

```


1  %% Simple Sine Wave Plot
2
3  %% Part One: Calculate Sine Wave
4  % Define the range |x|.
5  % Calculate the sine |y| over that range.
6  x = 0:.01:6*pi;
7  y = sin(x);
8
9  %% Part Two: Plot Sine Wave
10 % Graph the result.

```

Example of M-file with cells published to HTML.

Includes source code and output.

Supported formats are: HTML, Word, PowerPoint, LaTeX, and XML.



If you do not want cell mode enabled, select **Cell > Disable Cell Mode**.

MATLAB remembers the cell mode between sessions. If cell mode is disabled when you quit MATLAB, it will be disabled the next time you start MATLAB, and the converse is true.

In MATLAB Version 7.2, the first time you open an M-file in the Editor/Debugger, the cell toolbar appears. If the M-file contains a line beginning with `%`, an information bar appears below the cell toolbar, providing links for details about cell mode. To dismiss the information bar, click the close box on the right side of the bar. To hide the cell toolbar, right-click the toolbar and select **Cell Toolbar** from the context menu.

Compatibility Considerations

In previous versions, cell mode was off by default. The cell toolbar and yellow highlighting or horizontal rules in M-files that contain `%%` at the start of a line might be unexpected. If you used the `%%` symbols at the start of a line in M-files for a purpose other than denoting M-file cells, consider replacing the `%%` symbols with a different indicator, or keep cell mode disabled.

Lines Between Cells

You can set an Editor/Debugger display preference, **Show lines between cells**, to add a faint gray rule above each cell in an M-file. The line does not print or appear in the published M-file.

Cell Titles in Bold Preference Removed

Previous versions included an Editor/Debugger display preference to **Show bold cell titles**. When cleared, cell titles appeared in plain text, rather than bold text. This is no longer a preference you can set — all cell titles now appear in bold text.

Tuning and Managing M-Files

New features and changes introduced in Version 7.2 (R2006a) are

- “M-Lint and mlint Enhancements and Changes” on page 914
- “Profiling Enhancements” on page 915
- “Visual Directory View Removed from Current Directory Browser” on page 916

M-Lint and mlint Enhancements and Changes

The M-Lint code analyzer is now built into the Editor/Debugger where it continuously checks your code for problems and recommends modifications to maximize performance and maintainability. For details, see “M-Lint Automatic Code Analyzer Checks for Problems and Suggests Improvements” on page 909.

Compatibility Considerations

The `mlint` function has changed slightly to support its use in the Editor/Debugger. Specifically, the results returned from `mlint` with the `-id` option are of a different form than for previous versions. If you rely on the exact values, you need to make modifications.

For example, this is the form of a message returned in R2006a: `L 22 (C 1-9) 2:AssignmentNotUsed : The value assigned here to variable 'nohandle' might never be used.`

This is the form of the message from R14SP3: `22 (C 1-9) InefficientUsage:AssignmentNotUsed : The value assigned here to variable 'nohandle' might never be used.`

There is now a numeric identifier, followed by the category, for example:
`2:AssignmentNotUsed`

If you do rely on the exact values, note that there have been very few changes to the message text itself. For example, both R14SP3 and R2006a use the

same text: The value assigned here to variable 'nohandle' might never be used.

Because of improvements being made to `mlint`, the values returned using the `-id` option are expected to change in the next version as well, particularly the numeric identifier and category form. Do not rely on the exact values returned using `mlint` with the `-id` option or you will probably need to make modifications.

Profiling Enhancements

nohistory Option Added to profile Function

Use the new `profile -nohistory` option after having previously set the `-history` option to disable further recording of history (exact sequence of function calls). All other profiling statistics continue to accumulate.

Accuracy Improved

The Profiler provides more accurate accounting. The total time you see with the Profiler GUI now matches total wall clock time from when you started profiling until you stopped profiling. Overhead associated with the Profiler itself is now applied evenly.

Statistics for Recursive Functions

The `profile` function now gathers and reports time for recursive functions in the `FunctionTable`'s `TotalTime` for the function. In previous versions, `profile` attempted to break out `TotalRecursiveTime`, which was not always accounted for accurately. The value for `TotalRecursiveTime` in `FunctionTable` is no longer used.

This change is also reflected in the Profiler GUI reports.

PartialData Reported in Results, AcceleratorMessages Removed

The `FunctionTable` now includes the `PartialData` value. A value of 1 indicates the function was modified during profiling, for example, by being edited or cleared, so data was only collected up until the point it was modified.

In previous versions, `FunctionTable` included `AcceleratorMessages` although it was not used. `AcceleratorMessages` is no longer included.

Visual Directory View Removed from Current Directory Browser

The Visual Directory view was removed from the Current Directory browser.

Compatibility Considerations

Most of the features it provided are accessible from the Current Directory browser standard view.

Publishing Results

New features and changes introduced in Version 7.2 (R2006a) are described here.

Insert Italic Text Markup

You can now make designated text comments in cells appear italicized in the published output. Use **Cell > Insert Text Markup > Italic Text**, or use the equivalent markup symbols, underscores, as in `_SAMPLE ITALIC TEXT_`.

publish Function has New catchError Option

The `publish` function has a new `catchError` option that allows you to continue or stop publishing if the M-file contains an error.

Source Control Interface

Compatibility Considerations: Yes

New features and changes introduced in Version 7.2 (R2006a) are described here.

PVCS Source Control System Name Change

The PVCS[®] source control system (from Merant) now has a new name, ChangeMan[®] (from Serena[®]), and the source control interface in MATLAB on UNIX platforms reflects this change.

If you use the ChangeMan software on UNIX platforms, the `cmopts` value returned for it is `pvcs`. If you use PVCS software, select `ChangeMan` in the Source Control Preferences pane.

Compatibility Considerations

PVCS software users on UNIX platforms formerly selected `PVCS` in the Source Control Preferences pane. Now, PVCS software users select `ChangeMan` instead.

Mathematics

New Library CHOLMOD for Sparse Cholesky Factorization

For sparse matrices, MATLAB now uses CHOLMOD version 1.0 to compute the Cholesky factor. CHOLMOD is a set of routines offering improved performance in factorizing sparse symmetric positive definite matrices. See the function reference pages for `chol`, `spparms`, and `mldivide` for more information on how CHOLMOD is used by MATLAB.

New Solver for State-Dependent DDEs

In this release, MATLAB provides a second solver function, `ddesd`, in addition to the existing `dde23` function, for delay differential equations (DDEs). This new solver is for use on equations that have *general* delays. You supply a function in the input argument list that returns the vector of delays to be used by the solver. See the function reference page for `ddesd`, and Delay Differential Equations in the MATLAB Mathematics documentation for more information.

Upgrade to BLAS Libraries

MATLAB now uses new versions of the Basic Linear Algebra Subroutine (BLAS) libraries. For Intel processors on Windows and Linux platforms, MATLAB supports the Math Kernel Library (MKL) version 8.0.1. For AMD processors on Linux platforms, MATLAB uses the AMD Core Math Library (ACML) version 2.7.

New Function for Integer Division

The new `idivide` function provides division similar to `A./B` on integers except that fractional quotients are rounded to integers according to a specified rounding mode.

New Input to gallery Function

The gallery function has a new, optional input argument called `classname`. The `classname` input is a quoted string that must be either `'single'` or `'double'`. When you specify a `classname` argument in the call to gallery, MATLAB produces a matrix of that class.

Improved Algorithm for `expm`

The `expm` function now uses an improved algorithm to compute a matrix exponential. This algorithm often requires fewer matrix multiplications.

More Efficient `condst` for Sparse Matrices

The `condst` function handles sparse matrices more efficiently when estimating a 1-norm condition number.

accumarray Accepts Cell Vector Input

The `accumarray` function now accepts a cell vector as the `subs` input. This vector can have one or more elements, each element a vector of positive integers. All the vectors must have the same length. In this case, `subs` is treated as if the vectors formed columns of an index matrix.

Data Analysis

Data Analysis Collection Revised and Expanded

In this release, the MATLAB Data Analysis collection has been thoroughly revised to improve content organization and flow. In addition, most examples have been updated and streamlined.

Reference Pages for timeseries and tscollection Objects

Detailed reference pages are now available for `timeseries` and `tscollection` objects, properties, and methods. You can access these reference pages in the Help contents, under Data Analysis in the MATLAB Function Reference.

Text Files Can Be Imported In Time Series Tools

In Time Series Tools, you can now use the Import Wizard to import data from text files, such as .csv, .dat, and .txt.

Linux 64 Platform Fully Enabled for Time Series Tools

Compatibility Considerations: Yes

Time Series Tools is now fully enabled on the Linux 64 platform.

Compatibility Considerations

On the Linux 64 platform, you no longer need to manually enable the Time Series Tools feature before starting Time Series Tools (as in MATLAB 7.1).

Programming

Larger Data Sets with 64-Bit Windows XP

MATLAB support for Windows XP 64-bit edition enables you to handle much larger data sets. To learn more about memory allocation for arrays, see [Memory Allocation](#).

Using avifile and movie2avi on Windows XP 64

Compatibility Considerations: Yes

Note You must change the compression setting if you use the `avifile` or `movie2avi` function on Windows XP 64.

MATLAB currently defaults to using Indeo codecs to compress video frames when using `avifile/addframe` or `movie2avi`. If you attempt to use `avifile` and `addframe`, or `movie2avi` on a Windows XP 64-bit platform without specifying the compression type, an error message appears indicating the codec was not found. Nondefault settings must be explicitly passed in when using these functions on Windows XP 64 because Microsoft does not provide Indeo codecs on this platform.

This issue does not affect 32-bit Windows XP installations.

Compatibility Considerations

To work around this issue, do the following:

- 1 Explicitly specify no compression when creating the `avifile` object or when calling `movie2avi`. Two examples of this are

```
aviobj = avifile('myvideo.avi', 'compression', 'none');  
movie2avi(mov, 'myvideo.avi', 'compression', 'none');
```

- 2 Specify a codec for a compression that is installed. The ones that are included with Windows XP 64 are

- IYUV — Intel YUV codec (c:\winnt\system32\iyuv_32.dll)
- MRLE — Microsoft RLE codec (c:\winnt\system32\msrle32.dll)
- MSVC — Microsoft Video 1 codec (c:\winnt\system32\msvidc32.dll)

For example, to use the Intel YUV codec, use the four-CC code:

```
aviobj = avifile('myvideo.avi', 'compression', 'IYUV');
```

Other codecs can be found at <http://fourcc.org>.

Note there are restrictions with some codecs. For example, some codecs can only be used with grayscale images.

Regular Expressions

Compatibility Considerations: Yes

MATLAB 7.2 introduces the following new features for regular expressions in MATLAB. For more information on these features, see Regular Expressions in the MATLAB Programming documentation.

New Features

- Dynamic regular expressions — You can now insert MATLAB expressions or commands into regular expressions or replacement strings. The dynamic part of the expression is then evaluated at runtime.
- Generating literals in expressions — Use the new `regexprtranslate` function when you want any of the MATLAB regular expression functions to interpret a string containing metacharacters or wildcard characters literally.
- New parsing modes — Four matching modes (case-sensitive, single-line, multiline, and freespacing) extend the parsing capabilities of the MATLAB regular expression functions.
- Warnings display — Use the new `'warnings'` option with the regular expression functions to enable the display of warnings that are otherwise hidden.

Compatibility Considerations

Calling `regexp` or `regexp` with the `'tokenExtents'` and `'once'` options specified now returns a double array instead of a cell array. You may need to change your code to accommodate the new return type.

Setting Environment Variables

Use the new `setenv` function to set the value of an environment variable belonging to the underlying operating system.

issorted Support for Cell Arrays

You can now use the `issorted` function on a cell array of strings.

XLS Functions Support More Formats

`xlsread` now supports Excel files having formats other than XLS (e.g., HTML) as long as the COM server is available. Also, `xlsfinfo` now returns this file format information.

Archiving Functions Accept Files on Path and ~/

Files specified as arguments to `gzip`, `gunzip`, `tar`, and `zip` can now be specified as partial path names. On UNIX machines, directories can start with `~/` or `~username/`, which expands to the current user's home directory or the specified user's home directory, respectively. The wildcard character `*` can be used when specifying files or directories, except when relying on the MATLAB path to resolve a filename or partial pathname.

sendmail No Longer Requires ASCII Messages

E-mail messages that you send using `sendmail` are no longer restricted to ASCII character encoding schemes.

MATLAB Warns on Invalid Input to str2func

Compatibility Considerations: Yes

Due to a bug introduced in MATLAB R14, the `str2func` function failed to issue a warning or error when called with an invalid function name or a function name that includes a path specification. In the R2006a release, `str2func` now generates a warning under these conditions. In a future version of MATLAB, `str2func` will generate an error under these conditions.

Compatibility Considerations

Any existing code that calls `str2func` with an invalid function name or a function name that includes the path now generates a warning message from MATLAB. In a future version, this will cause an error. You should note any such warnings when using R2006a, and fix the input strings to `str2func` so that they specify a valid function name.

Changes to Character Encoding in File I/O

Compatibility Considerations: Yes

The `fopen` function has a new optional argument, a string that specifies a name or alias for the character encoding scheme associated with the file. If this argument is omitted or is the empty string (`''`), the MATLAB default encoding scheme is used. Given a file identifier as the only argument, `fopen` now returns an additional output value, a string that identifies the character encoding scheme associated with the file.

Low-level file I/O functions that read data from files, including `fread`, `fscanf`, `fgetl`, and `fgets`, read characters using the encoding scheme associated with the file during the call to `fopen`. Low-level file I/O functions that write data, including `fwrite` and `fprintf`, write characters using the encoding scheme associated with the file during the call to `fopen`.

Support for character encoding schemes has these limitations:

- Surrogate pairs are not supported. Each surrogate pair is read as a replacement character, the equivalent of `char(26)`.
- Stateful character encoding schemes are not supported.
- Byte order marks are not interpreted in any special way. Your code must skip them if necessary.
- Scanning numbers, using `fscanf`, is supported only for character encoding schemes that are supersets of ASCII. (Most popular character encoding schemes, with the exception of UTF-16, are such supersets.)

Compatibility Considerations

In V7.1 (R14SP3), low-level file I/O functions that read and write data treated characters as unsigned bytes. Programs using such functions as `fread` may have called `native2unicode` to convert input to MATLAB characters using a particular encoding scheme. Programs using such functions as `fwrite` may have called `unicode2native` to convert output from MATLAB characters using a particular encoding scheme.

For example, on a Japanese Windows platform, where the default character encoding scheme is Shift-JIS, a program may have used `native2unicode` and `unicode2native` to read and write Japanese text in this way:

```
fid = fopen(file);
data = fread(fid, '*char')';
fclose(fid);
dataU = native2unicode(data);
% operate on data
outData = unicode2native(dataU);
fid = fopen(file, 'w');
fwrite(fid, outData, 'char');
fclose(fid);
```

Such a program would produce different and possibly incorrect results in V7.2 (R2006a). The calls to `native2unicode` and `unicode2native` are no longer necessary, because the `fread` and `fwrite` functions now convert data to and from MATLAB characters using the character encoding scheme specified in the calls to `fopen`. In V7.2 (R2006a), the example code can be simplified to produce correct results:

```
fid = fopen(file);
dataU = fread(fid, '*char')';
fclose(fid);
% operate on data
fid = fopen(file, 'w');
fwrite(fid, dataU, 'char');
fclose(fid);
```

Changes to code using `fread`, `fgets`, `fgetl`, and `fscanf`

If your code calls `native2unicode` to convert input to MATLAB characters using a specified (or default) encoding scheme, you can, but do not have to, remove the calls to `native2unicode`.

This applies to reading from an encoded file using any of the following:

- `fread` with precision set to `'*char'` or `'char=>char'`
- `fgets` or `fgetl`
- `fscanf` with the format specifier set to either `'%s'` or `'%c'`

When you remove a call to `native2unicode`, be sure that the call to `fopen` supplies the same encoding argument (if any) as the call to `native2unicode`.

You may have used code like these examples in V7.1 (R14SP3):

```
indata = native2unicode(fread(fid, '*char'))';
indata = native2unicode(fread(fid, 'char=>char'))';
indata = native2unicode(fgets(fid));
indata = native2unicode(fgetl(fid));
indata = native2unicode(fscanf(fid, '%s'));
indata = native2unicode(fscanf(fid, '%c'));
```

You can, but do not have to, remove the calls to `native2unicode` in V7.2 (R2006a):

```
indata = fread(fid, '*char')';
indata = fread(fid, 'char=>char')';
indata = fgets(fid);
indata = fgetl(fid);
indata = fscanf(fid, '%s');
indata = fscanf(fid, '%c');
```

Changes to code using `fwrite`

If your code calls `unicode2native` to convert output from MATLAB characters using a specified (or default) encoding scheme, in most cases you must remove the calls to `unicode2native`. This is especially important if the encoding represents multibyte characters.

This applies to writing an encoded file using `fwrite` with precision set to either `'char'` or `'char*1'`.

When you remove a call to `unicode2native`, be sure that the call to `fopen` supplies the same encoding argument (if any) as the call to `unicode2native`.

You may have used code like these examples in V7.1 (R14SP3):

```
fwrite(fid, unicode2native(outbuff), 'char');
fwrite(fid, unicode2native(outbuff), 'char*1');
```

You must remove the calls to `unicode2native` in V7.2 (R2006a):

```
fwrite(fid, outbuff, 'char');  
fwrite(fid, outbuff, 'char*1');
```

Graphics and 3-D Visualization


Pasting Cut or Copied Graphic Objects Can Create an Axes

The way in which MATLAB handles copying (or cutting) and pasting children of axes such as lineseries, barseries, or contourgroup objects has changed slightly. In previous releases, if no destination axes was selected prior to pasting one or more such objects, they would be pasted into the current axes (returned by the `gca` function). MATLAB no longer makes this assumption; if no axes is currently selected when you paste graphic objects, a new axes is created in the destination figure to contain them.

To avoid creating a new axes where you do not want to do so, you should be in plot edit mode and have selected a destination axes before using **Edit** -> **Paste** or typing **CTRL-V**. You can use the Plot Browser to conveniently select objects to copy and to paste into.

Inspector Has New Look

The Property Inspector (the GUI summoned by the MATLAB `inspect` command) has a new look, but no changed functionality. The inspector enables you to view and change the most commonly used object properties. The figure below compares the previous version (7.1, left) of the Property Inspector with the new version (7.2, right):



Note that in addition to having a smaller font and wider line spacing, the new inspector locates pop-up menus at the right margin instead of between the two columns. Also, some icons have been redesigned.

Creating Graphical User Interfaces (GUIs)

Treatment of & in Menu Label Is Changed

Compatibility Considerations: Yes

The use of '&' (ampersand) in the uimenu 'Label' property string is changed for cases that use the constructs 'A& B' and 'A&&B'. The changes bring these constructs in line with the way '&' is used in other 'Label' constructs. See “Compatibility Considerations” below for specific information.

Compatibility Considerations

Interpretation of 'Label' property strings that use the following constructs is changed:

- The string 'A& B' now produces the menu label **A& B** with no underlined mnemonic. Previously, 'A& B' produced the label **A_B**, in which the space is a mnemonic.
- The string 'A&&B' now produces the menu label **A & B** with no underlined mnemonic. Previously, 'A&&B' produced the label **A&B** with no mnemonic.

If you use either construct, 'A& B' or 'A&&B', in your menu labels, verify that the new resulting label is acceptable or change the 'Label' property to a new string.

Major Documentation Revision

The MATLAB document *Creating Graphical User Interfaces* is reorganized and rewritten. It now consists of three sections:

- **Getting Started**—Leads you through the steps needed to create a simple GUI, both programmatically and using GUIDE.
- **Creating GUIs with GUIDE**—Contains the information, previously included in *Creating Graphical User Interfaces*, that you need to create a GUI using GUIDE. This section is organized in workflow order with many small examples of the various steps. A final chapter provides advanced examples.
- **Creating GUIs Programmatically**—For now, this section contains a summary of the available functions and complete code examples for three GUIs.

One GUI uses a variety of user interface controls to enable a user to calculate the mass of an object after specifying the object's density and volume.

Two other GUIs work together as an icon editor. One GUI, a color palette, is embedded in the other GUI, an icon editor. The color palette passes data to the icon editor whenever the GUI user selects a new color.

Note Following the release of MATLAB version 7.2, *Creating Graphical User Interfaces* will be further updated and expanded. The PDF and HTML versions of this document will be updated on The MathWorks Web site some time after the release. Check the top page of the HTML document and the title page of the PDF to determine if they have been updated.

External Interfaces/API

MEX-Files Built with gcc on Linux Must Be Rebuilt

Compatibility Considerations: Yes

In MATLAB V7.2 (R2006a) on Linux and Linux x86-64 platforms, MEX-files built with gcc must be recompiled and relinked using gcc version 3.4 or later. Rebuilding is required because MATLAB V7.2 (R2006a) on Linux and Linux x86-64 platforms is built with gcc version 3.4.

Compatibility Considerations

Changes in gcc version 3.4 have caused incompatibilities between MATLAB V7.2 (R2006a) and MEX-files built with gcc versions earlier than 3.4.

On Linux and Linux x86-64 platforms, MEX-files built with gcc versions earlier than 3.4 cannot be used in MATLAB V7.2 (R2006a).

On Linux and Linux x86-64 platforms, MEX-files built with gcc version 3.4 or later cannot be used in versions of MATLAB earlier than V7.2 (R2006a).

MEX-Files in MATLAB for Microsoft Windows x64

Compatibility Considerations: Yes

With the introduction of MATLAB for Windows x64, you can now build 64-bit MEX-files. These MEX-files have the extension `.mexw64`. The `mexext` command returns `mexw64` in MATLAB for Windows x64.

Compatibility Considerations

MEX-files built using MATLAB for Windows (32-bit), which have `.mexw32` extensions by default, cannot be used in MATLAB for Windows x64.

By default, when MATLAB for Windows x64 is installed, the `mex.pl` and `mex.bat` scripts build MEX-files for a Windows x64 platform (with `.mexw64` extensions).

New Microsoft and Intel Compilers Supported

MATLAB V7.2 (R2006a) supports new compilers for building MEX-files on Windows and Windows x64 platforms:

- Microsoft Visual C++ 2005, also informally called Visual C++ 8.0, part of Microsoft Visual Studio 2005
- Intel Visual Fortran 9.0

Environment Variables Needed for Intel Visual Fortran

When you build a MEX-file or an Engine or MAT application using Intel Visual Fortran 9.0, MATLAB requires an environment variable to be defined, depending on whether you are building in MATLAB for Windows (32-bit) or MATLAB for Windows x64:

- MATLAB for Windows (32-bit): The environment variable VS71COMNTOOLS must be defined. The value of this environment variable is the path to the Common7\Tools directory of the Visual Studio .NET 2002 or 2003 installation directory. (Intel Visual Fortran requires Visual Studio .NET 2002 or 2003 on 32-bit Windows platforms.) This environment variable is commonly defined by the Visual Studio .NET 2003 installation program.
- MATLAB for Windows x64: The environment variable MSSdk must be defined. The value of this environment variable is the path to the installation directory for Microsoft Platform SDK for Windows Server 2003. (Intel Visual Fortran requires Microsoft Platform SDK for Windows Server 2003 on Windows x64 platforms.) This environment variable is *not* commonly defined by the Microsoft Platform SDK installation program.

MWPOINTER Macro for Platform-Independent Fortran Code

MATLAB provides a preprocessor macro, `mwPointer`, that declares the appropriate Fortran type representing a pointer to an `mxArray` or to other data that is not of a native Fortran type, such as memory allocated by `mxMalloc`. On 32-bit platforms, the Fortran type that represents a pointer is `INTEGER*4`; on 64-bit platforms, it is `INTEGER*8`. The Fortran preprocessor translates `MWPOINTER` to the Fortran declaration that is appropriate for the platform on which you compile your file.

Compaq Visual Fortran Engine and MAT Options File Renamed

Compatibility Considerations: Yes

MATLAB V7.1 (R14SP3) included a Windows Engine and MAT options file named `df66engmatopts.bat`. This file contained options for Compaq Visual Fortran version 6.6 for use in building Fortran engine or MAT stand-alone programs. The file name `df66engmatopts.bat` originated with an earlier version of the Fortran compiler, named Digital Fortran.

In V7.2 (R2006a), this file has been renamed `cvf66engmatopts.bat` to match the Compaq Visual Fortran product name.

Compatibility Considerations

You may need to change any scripts that depend on the earlier name for the options file.

Options Files Removed for Unsupported Compilers

Compatibility Considerations: Yes

MATLAB V7.1 (R14SP3) included MEX, Engine, and MAT options files for a number of Windows C and Fortran compilers that were untested. These options files are not included in V7.2 (R2006a). The unsupported compilers, and the supported compilers that replace them, are:

Unsupported Compiler	Supported Replacement
Borland 5.0, 5.2, 5.3, 5.4	Borland 5.5, Borland 5.5 Free, Borland 5.6
Digital Visual Fortran 5.0, 6.0	Compaq Visual Fortran 6.1, Compaq Visual Fortran 6.6, Intel Visual Fortran 9.0
Microsoft Visual C++ 5.0, Visual C++ .NET 2002 (7.0)	Microsoft Visual C++ 6.0, Visual C++ .NET 2003 (7.1), Visual C++ 2005 (8.0)
Watcom 10.6, 11	Open Watcom 1.3

Compatibility Considerations

If you were using an untested compiler with a previous version of MATLAB, replace it with a supported compiler. You may need to recompile your MEX-files or applications.

Obsolete Functions No Longer Documented

Compatibility Considerations: Yes

In V7.1 (R14SP3), many MAT-file access, MX array manipulation, MEX-files, and MATLAB engine functions were declared obsolete in the External Interfaces Reference documentation. These functions are no longer documented in V7.2 (R2006a).

This section lists the obsolete functions removed from the documentation, along with replacement functions, if any.

Obsolete Functions: MAT-File Access

Obsolete Function	Replacement
matDeleteArray (C and Fortran)	matDeleteVariable
matDeleteMatrix (C and Fortran)	matDeleteVariable
matGetArray (C and Fortran)	matGetVariable
matGetArrayHeader (C and Fortran)	matGetVariableInfo
matGetFull (C and Fortran)	matGetVariable followed by mxGetM, mxGetN, mxGetPr, mxGetPi
matGetMatrix (C and Fortran)	matGetVariable
matGetNextArray (C and Fortran)	matGetNextVariable
matGetNextArrayHeader (C and Fortran)	matGetNextVariableInfo
matGetNextMatrix (C and Fortran)	matGetNextVariable
matGetString (C and Fortran)	matGetVariable followed by mxGetString

Obsolete Function	Replacement
matPutArray (C and Fortran)	matPutVariable
matPutArrayAsGlobal (C and Fortran)	matPutVariableAsGlobal
matPutFull (C and Fortran)	mxCreateDoubleMatrix followed by mxSetPr, mxSetPi, matPutVariable
matPutMatrix (C and Fortran)	matPutVariable
matPutString (C and Fortran)	mxCreateString followed by matPutVariable

Obsolete Functions: MX Array Manipulation

Obsolete Function	Replacement
mxClearLogical (C and Fortran)	None
mxCreateFull (C and Fortran)	mxCreateDoubleMatrix
mxCreateScalarDouble (C and Fortran)	mxCreateDoubleScalar
mxFreeMatrix (C and Fortran)	mxDestroyArray
mxGetName (C and Fortran)	None
mxIsFull (C and Fortran)	mxIsSparse
mxIsString (C and Fortran)	mxIsChar
mxSetLogical (C and Fortran)	None
mxSetName (C and Fortran)	None

Obsolete Functions: MEX-Files

Obsolete Function	Replacement
mexAddFlops (C)	None
mexGetArray (C and Fortran)	mexGetVariable
mexGetArrayPtr (C and Fortran)	mexGetVariablePtr
mexGetEps (C and Fortran)	mxGetEps
mexGetFull (C and Fortran)	mexGetVariable followed by mxGetM, mxGetN, mxGetPr, mxGetPi
mexGetGlobal (C and Fortran)	mexGetVariablePtr
mexGetInf (C and Fortran)	mxGetInf
mexGetMatrix (C and Fortran)	mexGetVariable
mexGetMatrixPtr (C and Fortran)	mexGetVariablePtr
mexGetNaN (C and Fortran)	mxGetNaN
mexIsFinite (C and Fortran)	mxIsFinite
mexIsInf (C and Fortran)	mxIsInf
mexIsNaN (C and Fortran)	mxIsNaN
mexPutArray (C and Fortran)	mexPutVariable

Obsolete Function	Replacement
mexPutFull (C and Fortran)	mxCreateDoubleMatrix followed by mxSetPr, mxSetPi, mexPutVariable
mexPutMatrix (C and Fortran)	mexPutVariable

Obsolete Functions: MATLAB Engine

Obsolete Function	Replacement
engGetArray (C and Fortran)	engGetVariable
engGetFull (C and Fortran)	engGetVariable followed by mxGetM, mxGetN, mxGetPr, mxGetPi
engGetMatrix (C and Fortran)	engGetVariable
engPutArray (C and Fortran)	engPutVariable
engPutFull (C and Fortran)	mxCreateDoubleMatrix followed by mxSetPr, mxSetPi, engPutVariable
engPutMatrix (C and Fortran)	engPutVariable
engSetEvalCallback (C)	None
engSetEvalTimeout (C)	None
engWinInit (C)	None

Compatibility Considerations

Most of the functions listed as obsolete in this section are unsupported in V6.5 (R13) and later versions. Some obsolete functions are unsupported in earlier versions.

If this section lists a replacement for an obsolete function, change any code that refers to the obsolete function to use the replacement instead.

If you must use an obsolete function in a MEX-file or application, use the `-v5` option to `mex` when you build the file.

Support for Licensed ActiveX Controls

MATLAB supports the use of Microsoft ActiveX controls that require licensing at both design time and runtime.

See the `actxcontrol` function for information on how to specify a design-time license key.

See [Deploying ActiveX Controls Requiring Run-Time Licenses](#) for information on how to use ActiveX Controls that require runtime licenses in your MATLAB application.

Support for VT_Date Type

MATLAB defines a data type to be used with controls requiring input defined as type VT_DATE. See Using Date Data Type for more information.

Dynamic Linking of External Libraries

MATLAB supports dynamic linking of external libraries only on 32-bit Windows systems and 32-bit Linux systems. See [Calling C Shared Library Functions from MATLAB](#) for more information.

R14SP3

Version: 7.1
New Features: Yes
Bug Fixes: No

Desktop Tools and Development Environment

Startup and Shutdown

Compatibility Considerations: Yes

New features and changes introduced in this version are described here.

Startup Option, `-nodesktop`, on Windows Platforms No Longer has Menu Bar and Toolbar; Use Function Equivalents Instead

The behavior of MATLAB software when started on Microsoft Windows platforms with the `-nodesktop` option has changed. The MATLAB Command Window no longer displays a menu bar or toolbar. This change resolves a number of problems that occurred in previous versions when running MATLAB in `-nodesktop` mode on Windows platforms.

Compatibility Considerations

Use equivalent functions instead of the menu and toolbar.

Instead of using the **File > Preferences** menu to modify the font or colors used in the Command Window, run `preferences -nodesktop`. For more information, see “preferences Function Now Supports `-nodesktop` Option” on page 975.

Desktop

New features and changes introduced in this version are organized by these topics:

- “Arranging Windows and Documents” on page 972
- “Preferences Directory Added for R14SP3; Supplements R14 Directory” on page 973
- “Preferences Changes for Fonts, Hyperlinks, and -nodesktop” on page 974
- “info.xml File Automatic Validation; Shows Warnings for Invalid Constructs” on page 975
- “Other Desktop Changes” on page 975

Arranging Windows and Documents

Figure Windows Now Dockable on Macintosh Platforms

On Apple Macintosh platforms, figure windows are now dockable.

Resize Multiple Tools at Once

You can now position the pointer at the intersection of three or four tools or documents to resize all of them at once.

Resize and Move Desktop Tools Using the Keyboard

There are now menu items you can select to move and resize the active tool in the desktop. Use the menu item mnemonics to perform those action with the keyboard. For example, if the Command Window is in the desktop along with other tools, press **Ctrl+0** (or click in it) to make the Command Window the active tool. Then press **Alt+D, V**, which is the mnemonic equivalent for selecting **Desktop > Move Command Window**. The pointer becomes an arrow. Use the arrow keys to move an outline of the Command Window to a new dockable location. Press **Enter** to dock it there, or press **Esc** to return the Command Window to its original position.

Resize Names in the Document Bar

You can now adjust the width of a name in the document bar when the bar is at the top or bottom of the window.

Positioning Document Bar Menu Item Name Changed

In previous versions, selecting **Desktop > Document Bar** displayed only menu items for positioning the document bar. Now, there are additional menu items. The same change was made to the context menu for the document bar. To access the menu items for positioning the document bar, select **Desktop > Document Bar > Bar Position**.

Keyboard Access Added for Document Bar Options

The **Desktop > Document Bar** now includes these items: **Alphabetize**, **Width**, and **Move documentname On Bar**. With their inclusion in the menu, you can use the keyboard to access these features via mnemonics. For example, on Windows platforms, press **Alt+D, M, A** as a shortcut to for **Desktop > Document Bar > Alphabetize**.

Left/Right and Top/Bottom Split for Document Arrangements Name Changed

When arranging documents in desktop tools, you can choose **Window > Left/Right Split** or **Window > Top/Bottom Split** to show two documents at once in the tool. Those menu items are now called **Left/Right Tile** and **Top/Bottom Tile**. This change was made to avoid any confusion with the Editor/Debugger's new split screen feature.

Preferences Directory Added for R14SP3; Supplements R14 Directory

There is a new preferences directory, R14SP3. This is the directory name returned when you run the `prefdir` function. When you install R14SP3, MATLAB migrates files from your existing preference directory, R14, to the new directory, R14SP3. Changes made to files in the directory when you run R14SP3 are not used when you run previous R14 releases.

This represents a change in the preference directory MATLAB uses for a minor release, and was done to prevent serious backwards compatibility

problems. It is primarily relevant if you use R14SP3 and previous R14 releases. If you only run R14SP3, or run R14SP3 with R13 or R12 releases, you will not be affected by this change.

In the past, minor releases and the associated major release used the same preferences directory. For example, R13 and R13SP1 shared the R13 preferences directory. That continues to be true for all previous releases, but is not true for R14SP3 and beyond. The R14 preferences directory will be shared by the R14 through R14SP2 releases, but the new R14SP3 preferences directory is only used by R14SP3. This means that changes made to files in the directory while running R14SP3 are not used when you run a previous R14 release, and the reverse is true. For example, statements added to the Command History when you run R14SP3 are not in the Command History when you run R14SP2.

For more information, see the reference page for `prefdir`.

Compatibility Considerations

This change was made to prevent major backwards compatibility problems. Use the R14SP3 preferences directory instead of the R14 directory. If you use the `prefdir` function and have code that relies on the result being R14, you will need to modify that code.

Preferences Changes for Fonts, Hyperlinks, and -nodesktop

Font Antialiasing Preference Added

In **Preferences > Fonts**, select the new antialiasing preference to provide a smoother appearance to desktop fonts.

Hyperlink Color Preference Changed

There is a new **Colors** preference for specifying the color of hyperlinks in the Command Window and the Help browser **Index** pane. In previous releases, this preference only applied to the Command Window hyperlinks and was accessed via Command Window preferences.

preferences Function Now Supports -nodesktop Option

Run `preferences -nodesktop` after starting MATLAB on Windows platforms with the `-nodesktop` option to change Command Window font and colors via a special **Preferences** dialog box.

To set other available preferences for the Command Window after starting MATLAB with the `-nodesktop` option, run `preferences` and use the resulting **Preferences** dialog box for all tools and products. Note that changes you make to font and color preferences in this dialog box do not apply to the Command Window.

info.xml File Automatic Validation; Shows Warnings for Invalid Constructs

If you add your own toolbox to the **Start** button, you can use the schema file for its `info.xml` file, `matlabroot/sys/namespace/info/v1/info.xsd`. MATLAB now automatically validates your `info.xml` file against this schema when you click the **Start** button after updating and refreshing your `info.xml` file.

Compatibility Considerations

If your `info.xml` contains invalid constructs, you will see warnings in the Command Window until you correct the problems.

Other Desktop Changes

Paste Special Menu Item Renamed

In the **Edit** menu, the name of the **Paste Special** item has been replaced by **Paste to Workspace**, but the functionality remains the same. It opens the Import Wizard so you can paste the clipboard contents to the workspace in MATLAB.

Rename Shortcut Categories

You can now rename shortcut categories.

Running Functions – Command Window and Command History

Compatibility Considerations: Yes

New features and changes introduced in this version are

- “Tab Completion Preference Added” on page 976
- “Tab Completion No Longer Shows Entries Twice” on page 976
- “Incremental Search Now Supports Removing Characters” on page 976
- “Hyperlink Color Preference Moved” on page 976

Tab Completion Preference Added

There is a new Command Window preference, **Tab key narrows completion**. When selected, with a list of possible completions in view, type another character and press **Tab** to further narrow the list shown. Repeat to continue narrowing the list. This behavior is similar to tab completion behavior in releases prior to R14.

Tab Completion No Longer Shows Entries Twice

In previous versions, when completing filenames or function names, a name sometimes appeared twice in the completion list, once with the file extension and once without. Now the entry appears only once.

Incremental Search Now Supports Removing Characters

In incremental search, use **Ctrl+G** to remove characters back to the previous successful string of characters found. For example, when searching for the term `plode`, the text is not found and `Failing` appears in the incremental search field. **Ctrl+G** automatically removes the `de` from the search term because `pl0` does exist in the file.

Hyperlink Color Preference Moved

The preference for specifying the hyperlink color has moved from the Command Window preferences pane to the **Colors** preferences pane. The hyperlink color now also applies to links in the Help browser **Index** pane.

Compatibility Considerations

Use the **Colors** preference pane to specify the hyperlink color, and be aware that it also impacts the Help browser Index pane color.

Help

New features and changes introduced in this version are

- “Hyperlink Color in the Index Pane Preference Added” on page 978
- “New Look for Demos, Including Thumbnails and Categories” on page 978
- “Demos Run in Command Window as Scripts and Their Variables Now Created in Base Workspace” on page 978
- “echodemo Function Added to Replace playshow function” on page 979
- “Add Demos to Favorites” on page 979
- “Adding Your Own Demos Type Tag Now Supported” on page 980
- “Bug Reporting System Introduced” on page 980

Hyperlink Color in the Index Pane Preference Added

You can now specify the color for links in the Help browser **Index** pane using the **Colors** preferences pane. The hyperlink color also applies to links in the Command Window, so changes you make to the preference apply to both tools.

New Look for Demos, Including Thumbnails and Categories

Stylistic changes were made to the Demos interface in the Help browser. On the summary page for a product, each demo appears with a thumbnail image that provides an indication of the type of output it creates, as well as an icon representing the type of demo (M-file, M-GUI, model, or video).

Demos Run in Command Window as Scripts and Their Variables Now Created in Base Workspace

In this release, all M-file demos include the **Run in the Command Window** link, which executes the demo via echodemo.

In previous releases, some M-file demos provided a **Run** hyperlink in the display pane. When you clicked **Run**, the M-file demo executed in a GUI via the `playshow` function. An example of this type of demo is the MATLAB Mathematics Basic Matrix Operations demo, `intro.m`. In this release, the **Run** hyperlink for these M-file demos has been replaced by **Run in the**

Command Window. It executes the demo step by step in the Command Window via the `echodemo` function. Double-clicking this type of M-file demo in the Navigator pane no longer runs the M-file demo, but opens the M-file in the Editor/Debugger where you can run it step by step using **Cell > Evaluate Current Cell and Advance**.

Compatibility Considerations

The new **Run in Command Window** hyperlink represent a change in the way demos run.

The `echodemo` function MATLAB uses to run M-file demos in the Command Window runs the demos as scripts. The `playshow` function MATLAB used to run M-file demos in previous releases ran the demos as a function. This means that now the demo's variables are created in the base workspace. If you have variables in the base workspace when you run an M-file demo, and the demo uses an identical variable name, there could be problems with variable name conflicts. For example, your variable could be overwritten. The demo's variables remain in the base workspace after the demo finishes running until you clear them or quit MATLAB. Another change is that figures are not automatically closed when you end the demo.

echodemo Function Added to Replace playshow function

There is a new `echodemo` function that replaces `playshow`. The Demos browser uses `echodemo` to execute M-file demos when you click the **Run in the Command Window** link.

Compatibility Considerations

The `playshow` function is deprecated in favor of the `echodemo` function. In a future release, the `playshow` function will be removed. In practice, both `echodemo` and `playshow` are helper functions for running demos. It is unlikely you would ever call either `playshow` or `echodemo` directly, and especially not in M-files.

Add Demos to Favorites

You now can add published M-file demos to favorites.

Adding Your Own Demos Type Tag Now Supported

If you add demos for your own toolbox, you can use the new `<type>` tag for a `<demoitem>` to identify the type of demo in your toolbox's `demos.xml` file.

Bug Reporting System Introduced

You now can view bugs fixed with this release, as well as any known bugs using the Bug Reports database in the Support section of the MathWorks Web site. The MathWorks continuously updates the database to add any newly found bugs and compatibility issues, as well as any new workarounds and solutions. The system includes bugs found and fixed in R14SP2 and later releases.

Workspace, Search Path, and File Operations


Compatibility Considerations: Yes

New features and changes introduced in this version are described here.

Find Files Offers Additional Filtering

The Find Files tool has been enhanced. It now allows you to search all file types except those specified. It also lets you ignore files larger than a specified size. Along with enhancements to the Find Files tool, some minor feature changes were made, including the removal of the **Restore Defaults** button.

Visual Directory View to be Removed

In the next release, the Current Directory browser will no longer support the Visual Directory view (accessed using the  toolbar button).

Compatibility Considerations

Some features currently available using the Visual Directory view will not be available in the next release when the feature is removed.

Editing and Debugging M-Files

Compatibility Considerations: Yes

New features and changes introduced in this version are

- “Split Screen Display Added” on page 982
- “Highlight Current Line Added” on page 983
- “Comment Lines in Java, C, or C++ Program Files Now Supported” on page 984
- “HTML File Indenting Feature Added as the Default” on page 984
- “Incremental Search Now Supports Removing Characters” on page 985
- “Emacs Key Binding for Select All” on page 985
- “Change Case Added to Menu” on page 985
- “Nested Function Name No Longer in Status Bar” on page 985

Split Screen Display Added

The Editor/Debugger now supports a horizontal or vertical split screen for displaying two different parts of the same document at once. To split the screen, select **Window > Split Screen** and the splitting action you want, for example, **Top/Bottom**. Alternatively, drag the splitter bar that appears above the vertical scroll bar or to the left of the horizontal scroll bar. To remove the splitter, drag it to an edge of the window.

Document with top/bottom split.

```


Editor - H:\Documents\MATLABFiles\myfiles\collatzall.m
File Edit Text Cell Tools Debug Desktop Window Help
1 function collatzall(n)
2 % Compute and plot length of sequence for Collatz pro
3 % Prepare figure
4 clf
5 set(gcf,'DoubleBuffer','on')
6 set(gca,'XScale','linear')
6 set(gca,'XScale','linear')
7 %
8 % Determine and plot sequence and sequence length
9
10 seq_length=zeros(100,1);
11 for m = 1:n
12     plot_seq = collatz(m);
collatzall Ln 7 Col 3 OVR

```

Highlight Current Line Added

You can set a preference to highlight the current line, that is, the line with the caret (also called the blinking cursor). This is useful, for example, to help you see where copied text will be inserted when you paste. To highlight the current line, select **Preferences > Editor/Debugger > Display** and under **General Display Options**, select the check box for **Show caret row highlighting**. You can also specify the color used to highlight the line.

Current line (line with the caret/blinking cursor) is highlighted.



Comment Lines in Java, C, or C++ Program Files Now Supported

You can now use the **Text > Comment** feature to comment selected lines in Sun Microsystems Java, ANSI® C, and C++ program files. This adds the // symbols at the start of the selected lines. Similarly, **Text > Uncomment** removes the // symbols from the front of selected lines in Java, C, and C++ program files.

HTML File Indenting Feature Added as the Default

There is a new Editor/Debugger language preference for HTML files to specify block indenting. By default, the preference is selected so block indenting applies when typing text in HTML files.

In addition, you now can select **Text > Smart Indent** to apply smart indenting to selected text in HTML files.

Compatibility Considerations

When typing text in HTML files, you will automatically see block indenting because the preference is selected by default.

Incremental Search Now Supports Removing Characters

In incremental search, use **Ctrl+G** to remove characters back to the previous successful string of characters found. For example, when searching for the term `plode`, the text is not found and `Failing` appears in the incremental search field. **Ctrl+G** automatically removes the `de` from the search term because `plo` does exist in the file.

Emacs Key Binding for Select All

With the Emacs key bindings preference selected, use **Ctrl+X, H** to select all.

Change Case Added to Menu

Use new items in the **Text** menu to change the case of selected text. You can also use the keyboard equivalents for changing case that existed in previous versions—these are shown in the menu next to each item.

Nested Function Name No Longer in Status Bar

The Editor/Debugger no longer displays the current nested function name in the status bar. Look in the M-file to view the current nested function name.

Tuning and Managing M-Files

New features and changes introduced in this version are described here.

Directory Reports Uses New Run Buttons

With Directory Reports displayed in the Web browser, you can use these two new buttons:

- **Rerun This Report** — This updates the currently displayed report after you have made changes to the report options or to any files in the current directory.
- **Run Report on Current Directory** — Use this after changing the current directory to run the same type of report for the new current directory.

These new buttons replace the **Refresh** button.

Override `%#ok` with the New `mlint -notok` Option

There is a new option for the `mlint` function, `'-notok'` you can use to override any statements that include `%#ok` (the symbol you add to the end of a line instructing `mlint` to ignore the line). That is, `mlint` will run for all lines in the file and will not ignore any statements.

Hyperlink Now Part of Messages Displayed by `mlint`

When you run the `mlint` function, the line number in the messages displayed is a hyperlink that when clicked, opens the file in the Editor/Debugger scrolled to that line number.

Profiler Button Added to Toolbar

There is now a button  on the MATLAB desktop toolbar to open the Profiler.

Publishing Results

New features and changes introduced in this version are described here.

Notebook Setup Changes; Some Arguments Removed

The notebook function setup behavior and syntax have changed.

When you run `notebook(' -setup')`, MATLAB automatically obtains all the information about your Microsoft Word application from the system registry for your Windows environment and you are no longer prompted to supply the information.

In previous versions, when you configured Notebook, you ran

```
notebook (' -setup')
```

Notebook then prompted you to specify the version of Word you were using, and if needed, the location of Word and its template directory. You could supply the information using optional arguments to the notebook function:

```
notebook(' -setup', wordversion, wordlocation, templatelocation)
```

Now, when you run `notebook(' -setup')`, MATLAB automatically obtains all the Word information from the registry for your Windows environment.

Compatibility Considerations

If you use notebook with the `wordversion`, `wordlocation`, and `templatelocation` arguments in any of your files (for example, `startup.m`), remove those arguments in your files. If you specify the optional arguments, the notebook function runs and issues a warning, but ignores the values. In a future release, MATLAB will issue an error when it encounters notebook with these arguments.

Versions of Microsoft Word Application Supported by Notebook; Microsoft Word 97 No Longer Supported

MATLAB Notebook supports the Microsoft Word version 2000 application. Notebook also supports the Microsoft Word 2002 application and Microsoft Word 2003 application, both for the Microsoft Windows XP platform.

Compatibility Considerations

As of MATLAB 7.1 (R14SP3), Notebook no longer supports the Microsoft Word 97 application.

Mathematics

New Functions

Compatibility Considerations: Yes

The following functions are new in R14SP3:

Function	Description
hypot	Square root of sum of squares
mode	Finds most frequent values in sample

Compatibility Considerations

A new function name can potentially introduce a backward incompatibility since it can, under certain circumstances, override a variable with the same name as the new function. This is especially true for names that are commonly used as variable names in program code.

An example of such a function name is the `mode` function, introduced in this release. If you have M-file programs that use `mode` as a variable name, it is possible under certain conditions for MATLAB to interpret these variable names as function names by mistake. Read the section Variable Names in the MATLAB Programming documentation to find out how to avoid having these variables misinterpreted.

If your program code uses a user-written function named `mode`, you may find that MATLAB calls the new MATLAB `mode` function instead of your own `mode` function. To correct this, modify your MATLAB path by placing the location of your own `mode` function closer to the beginning of the path string than the location of the MATLAB `mode.m` file. The help for the `addpath` and `rmpath` functions explains how to modify your MATLAB path.

Modified Functions

The following functions have been modified in MATLAB 7.1:

Function	Modified Behavior
accumarray	Allows more flexibility for input/output classes and functions to be called
odeset	New NonNegative integration property to impose nonnegativity constraints on an ODE solution
rand	Supports the Mersenne Twister algorithm in generating random numbers
svd	Returns economy decomposition

Changes to `accumarray`

MATLAB Version 7.1 adds the following new features to the `accumarray` function:

- The data type for the `val` input can be any numeric type, or logical, or character.
- The data type for the `subs` input can be any numeric type.
- You can use a cell array of separate index vectors for the `subs` input.
- When you specify a function input argument, the value returned by `accumarray` is given the same class as the values returned by that function.
- You can control the sparsity of the value returned by `accumarray` by specifying the new input argument `issparse`.

Imposing Nonnegativity Constraints on Computed ODE Solution

There is a new integration property called `NonNegative` that you can use when applying ODE initial value problem solvers. If you need to solve a problem in which certain components of the solution must be nonnegative, use the `NonNegative` property to impose nonnegativity constraints on the computed solutions.

See `Nonnegative Solutions` under `Calculus` in the `MATLAB Mathematics` documentation for more information on this feature.

Mersenne Twister Support in rand

The rand function now supports a method of random number generation called the Mersenne Twister. The algorithm used by this method, developed by Nishimura and Matsumoto, generates double precision values in the closed interval $[2^{-53}, 1-2^{-53}]$, with a period of $(2^{19937}-1)/2$.

For a full description of the Mersenne twister algorithm, see <http://www.math.sci.hiroshima-u.ac.jp/~m-mat/MT/emt.html>.

svd Returns Economy Decomposition

The following feature was released in MATLAB 7.0, but was undocumented until this release.

The command `svd(A, 'econ')` returns economy decomposition on matrices having few rows and many columns as well as those with many rows and few columns. `svd(A,0)` continues to behave as it always has, namely to only return economy-sized decomposition on matrices having many rows and few columns.

Note that this does not carry over to the `qr` function as there is no valid way of cutting out any of the information returned by `qr` to make an economy-sized decomposition of matrices having few rows and many columns.

New Location for LAPACK Libraries

The location of the LAPACK libraries has been changed. These libraries are now located in

```
extern/lib/win32/microsoft/libdflapack.lib  
extern/lib/win32/microsoft/libmwapack.lib
```

This change impacts you only if you build MEX-files that call LAPACK and BLAS functions.

Documentation on Data Analysis

The section of the MATLAB Mathematics documentation on “Data Analysis and Statistics” has been moved to a new MATLAB Data Analysis book. This book documents MATLAB functions and tools that support basic data analysis, including plotting, descriptive statistics, correlation, interpolation, filtering, and Fourier analysis. It also documents the new object-oriented command-line API for analyzing time-series data.

Data Analysis

Data Analysis Documentation

The MATLAB 7.1 documentation includes a new Data Analysis book that describes how to use MATLAB functions and tools for common data-analysis tasks:

- Plotting
- Filtering
- Interpolation
- Descriptive statistics
- Correlation
- Data fitting using linear regression
- Fourier analysis
- Time-series analysis

Some of the content in Data Analysis is incorporated from the Mathematics and Graphics books, such as data plotting, descriptive statistics, data fitting, and Fourier analysis. All information about time-series analysis is new.

Time-Series Analysis

You can analyze time-series data using the new `timeseries` and `tscollection` objects and methods, as well as the Time Series Tools graphical user interface. This new functionality supports the following:

- Representation for univariate or multivariate MATLAB time series and Simulink logged-signals data
- Built-in management of time units
- Removal or interpolation of missing data
- Resampling of data
- Arithmetic operations for `timeseries` objects
- Synchronization of time series

Note Due to reported instabilities on the Linux 64 platform, you must manually enable the Time Series Tools feature before starting Time Series Tools.

To manually enable Time Series Tools on the LinuxLinux 64 platform, type the following at the MATLAB prompt:

```
rehash toolboxcache
feature('TimeSeriesTools',1)
```


Programming

New Functions

Compatibility Considerations: Yes

This version introduces the following new functions:

Function	Description
arrayfun	Applies a given function to each element of an array. This is especially useful for arrays of structures.
exifread	Reads EXIF information from JPEG and TIFF image files
structfun	Applies a given function to each field of a structure
swapbytes	Swaps byte ordering
typecast	Converts data types without changing underlying data

Compatibility Considerations

A new function name can potentially introduce a backward incompatibility since it can, under certain circumstances, override a variable with the same name as the new function. This is especially true for names that are commonly used as variable names in program code. Read the section Variable Names in the MATLAB Programming documentation to find out how to avoid having these variables misinterpreted.

Modified Functions

Compatibility Considerations: Yes

The following functions were modified in this version:

Function	Modified Behavior
cellfun	Applies a given function to each cell of a cell array
datestr	Seconds field truncates instead of rounding
error	Saves stack information that you can retrieve using <code>lasterror</code>
isfield	Supports cell array input
lasterror	Returns stack information on last error
rethrow	Accepts stack information as input
who, whos	Displays information separately for nested functions

Compatibility Considerations

The following functions might, under certain circumstances, return a different value than what was returned in MATLAB 7.0.4 (R14SP2):

- `datestr`: Output might differ by 1 second from what was returned in a previous version.
- `isfield`: Output might differ if you used this feature in a release in which it was not officially supported.

Evaluation Functions for Arrays, Structures, Cells

MATLAB offers the capability to apply a given function to each element of an array, each field of a structure, or each cell of a cell array. See the help on `arrayfun`, `structfun`, and `cellfun` for more information.

Using `who` and `whos` with Nested Functions

When you use `who` or `whos` inside of a nested function, MATLAB returns or displays all variables in the workspace of that function, and in the workspaces of all functions in which that function is nested. This applies whether you include calls to `who` or `whos` in your M-file code or if you call `who` or `whos` from the MATLAB debugger. See the `thewho` reference page for more information.

Date and Time Functions Support Milliseconds

The `datestr`, `datetime`, and `datevec` functions now support time specification in milliseconds. Use the symbol `.FFF` to represent milliseconds in any of these three functions. See the table labeled Free-Form Date Format Specifiers on the `datestr` reference page for more information.

Stack Trace Provided for lasterror

The `lasterror` function now returns an additional field in the structure that it returns. The new `stack` field contains information from the stack on the M-file, function, and line in which the error occurred.

You can use this stack information to track down the source of an error, or as an input to the `rethrow` function. When used with `rethrow`, MATLAB sets the stack of the rethrown error to the value contained in the `stack` input.

isfield Function Supports Cell Arrays; Results Might Differ from Previous Version

Compatibility Considerations: Yes

The `isfield` function now supports cell array input as shown in this example. Check structure `S` for any of four possible field names. In this case, only the first is found, so the first element of the return value is set to true:

```
S = struct('one', 1, 'two', 2);

fields = isfield(S, {'two', 'pi', 'One', 3.14})
fields =
     1     0     0     0
```

Compatibility Considerations

There might be backward compatibility issues associated with this change if you used `isfield` with cell array input in a previous release. In previous releases, although `isfield` might have worked with this type of input in certain cases, it was not officially a supported feature. If you used this previously unsupported syntax in previous releases, you may see a change in the content and/or size of the return values in this release.

For example, create a structure `s` with three fields `a`, `b`, and `c` created in that order. In MATLAB 7.0.4, `isfield` called with a cell array input returns true if any of the elements of the cell array matches a field name, and if that element is in the same position in the cell array as the field is in the structure. This is true for `'c'`:

```
isfield(s, {'b'; 'a'; 'c'})
ans =
     1
```

In MATLAB 7.1, `isfield` returns true for each element in the cell array that matches a field name, regardless of where the string is positioned in the cell array. This is true for `'a'`, `'b'`, and `'c'`:

```
isfield(s, {'b'; 'a'; 'c'})
ans =
     1
```


1
1

Support for Reading EXIF Data from Image Files

You can now read EXIF (Exchangeable Image File Format) data from JPEG and TIFF graphics files using the new `exifread` function. EXIF is a standard used by digital camera manufacturers to store information in the image file, such as the make and model of a camera, the time the picture was taken and digitized, the resolution of the image, exposure time, and focal length.

Performance Improvements to the MATLAB JIT/Accelerator on Macintosh

The JIT/Accelerator for MATLAB, introduced in MATLAB Version 6.5 for Windows and UNIX, is now also supported on Macintosh systems. The JIT/Accelerator affects the performance of MATLAB and can give you a substantial performance increase over earlier MATLAB versions for many MATLAB applications.

Specifying fread Precision as Number of Bits

The following information on the `fread` function applies to MATLAB 7.1 and also to earlier versions.

MATLAB provides the following method of specifying a precision argument in a call to `fread`:

```
input_format=>output_format
```

For example, to read 50 8-bit unsigned integers from a file and convert them to characters, you can use

```
c = fread(fid, 50, 'uint8=>char')
```

If the input format and output format are the same, you can abbreviate the precision specifier by using

```
*input_format
```

For example, you can replace

```
c = fread(fid, 50, 'uint8=>uint8')
```

with

```
c = fread(fid, 50, '*uint8')
```

You can also use this notation with an input stream that is specified as a number of bits (e.g., `bit4` or `ubit18`). MATLAB translates this into an output type that is a signed or unsigned integer (depending on the input type), and which is large enough to hold all of the bits in the source format. For example, `*ubit18` does not translate to `ubit18=>ubit18`, but instead to `ubit18=>uint32`.

Seconds Field Now Truncated; Results Might Differ

Compatibility Considerations: Yes

When handling time data, MATLAB now truncates the seconds field instead of rounding it. This is consistent with the way that MATLAB handles hours and minutes.

For example, using MATLAB 7.0.4 (R14SP2), `datestr` returns

```
t = datestr('11:30:01.666')
t =
    01-Jan-2005 11:30:02
```

while MATLAB 7.1 (R14SP3) returns

```
t = datestr('11:30:01.666')
t =
    01-Jan-2005 11:30:01
```

Compatibility Considerations

If your M-files relied on the previous behavior, you might get different results.

Built-in Functions No Longer Use .bi; Impacts Output of which Function

Compatibility Considerations: Yes

In previous releases, MATLAB function dispatching located built-in functions by means of special files having a `.bi` file extension. MATLAB no longer uses this mechanism to locate built-in functions. All `.bi` files have been removed in MATLAB 7.1.

Compatibility Considerations

If you have M-files that relied on built-in files having a `.bi` extension, your files need to accommodate this change.

There are changes in how MATLAB displays built-in functions using `which`:

In MATLAB 7.0.4 (R14SP2),

```
which -all int32
\\matlab\toolbox\symbolic\@sym\int32.m           % sym method
\\matlab\toolbox\matlab\datatypes\int32.bi      % Shadowed
\\matlab\toolbox\matlab\datatypes\int32.m      % Shadowed
```

In MATLAB 7.1 (R14SP3),

```
which -all int32
built-in (\\matlab\toolbox\matlab\datatypes\int32)
\\matlab\toolbox\symbolic\@sym\int32.m         % sym method
```

New Warning About Potential Naming Conflict

Compatibility Considerations: Yes

If you change directories (`cd`) or add a new directory to your current MATLAB path, and the new directory contains an M-file having the same name as a MATLAB built-in function, MATLAB now displays a warning alerting you to the potential naming conflict. For example,

```
Warning: Function D:\test\matlab\disp.m has the same name as a
MATLAB builtin. We suggest you rename the function to avoid a
potential name conflict.
```

In general, any file system event that leads to path refreshing in MATLAB can trigger this warning if the directory involved in this event has such a user function under it.

Compatibility Considerations

MATLAB might generate warnings about naming conflicts that did not appear in previous versions. To avoid this warning, renaming your M-files that have name conflicts with built-in functions.

Graphics and 3-D Visualization

Plot Tools Now Available on Mac Platform

As a consequence of enabling Java figures on Macintosh, the Plot Tools user interface is now available to Mac users, enabling them to interactively add data to plots, change plot symbology, and otherwise customize their data plots.

Documentation for Data Analysis Reorganized

Documentation explaining techniques for analyzing graphical data has been shifted from the Graphics book of the MATLAB documentation to a new book called Data Analysis.

Creating Graphical User Interfaces (GUIs)

Plans for Obsolete Functions

Compatibility Considerations: Yes

The table below indicates functions that were designated as obsolete prior to R14SP3 and that will be removed in a future version.

Compatibility Considerations

If you use these functions, you should use replacement functions instead.

Obsolete Function	Removed from Version	Replacement
clrprop	Future version	rmappdata
ctlpanel	Future version	guide
extent	Future version	get(txtobj, 'extent')
figflag	Future version	findobj to determine if figure exists. figure(fighandle) to bring figure to front and give it focus.
getuprop	Future version	getappdata
hthelp	Future version	web
layout	Future version	None provided
matq2ws	Future version	None provided
matqdlg	Future version	None provided
matqparse	Future version	None provided
matqueue	Future version	None provided
menuedit	Future version	guide
menulabel	Future version	Use '&' to specify mnemonics and 'Accelerator' property to define accelerator keys.
setuprop	Future version	setappdata

Obsolete Function	Removed from Version	Replacement
wizard	Future version	None provided
ws2matq	Future version	None provided

External Interfaces/API

mex Switches Now Supported on Microsoft Windows

MATLAB now supports the `-l` and `-L` options to the `mex` command on Windows operating systems. In previous releases of MATLAB, these options were supported only on UNIX systems.

Switch	Description
<code>-l</code>	<p>Specifies additional libraries to link against.</p> <hr/> <p>Note On Windows operating systems, the <code>-l</code> option can specify libraries of two forms. For example, specifying <code>-l name</code> matches either <code>name.lib</code> or <code>libname.lib</code>, whereas on UNIX it matches only <code>libname.lib</code>.</p> <hr/>
<code>-L</code>	<p>Specifies a path to use when MATLAB searches for library files specified with the <code>-l</code> option. The <code>-L</code> option must precede the <code>-l</code> option.</p>

For the switches you can use with the `mex` command, see the MEX Script Switches table in the Custom Building MEX-Files section of Creating C/C++ and Fortran Programs to be Callable from MATLAB (MEX-Files) in the MATLAB External Interfaces documentation.

New COM Programmatic Identifier

There is now a ProgID that enables you to use the full desktop version of MATLAB as an automation server.

`Matlab.Desktop.Application` starts an automation server using the most recent version of MATLAB that is installed on your system.

New File Extension for MEX-Files on Windows Systems

Compatibility Considerations: Yes

MATLAB now uses the extension `.mexw32` for MEX-files on 32-bit versions of Windows systems. In previous versions, MATLAB used the extension `.dll`.

MathWorks recommends that you recompile all MEX-files after installing MATLAB 7.1. MEX-files compiled in MATLAB 7.0.4 with `.dll` extensions should still work in MATLAB 7.1.

There may be two MEX-files with the same name, except that one has a `.mexw32` extension and the other has a `.dll` extension. When these files are both on the MATLAB search path:

- If the two files are in the same directory, MATLAB uses the `.mexw32` file.
- If the two files are in different directories, MATLAB uses the file in the directory that is higher on the search path.

If you want one of these two files to take precedence over the other, ensure that the directory that contains the file you want MATLAB to use is higher on the search path than the directory that contains the file you do not want MATLAB to use.

Compatibility Considerations

Previous versions of MATLAB do not recognize MEX-files compiled in MATLAB 7.1 with `.mexw32` extensions. However, you can use the `mex -output` option in MATLAB 7.1 to build a MEX-file with a `.dll` extension that earlier versions of MATLAB can recognize.

You may need to update any MATLAB scripts or makefiles that explicitly expect `.dll` extensions for compiled MEX-files. You can use the `mexext` function in MATLAB to obtain the extension for the platform and version you are working on. A new `mexext` script obtains the appropriate extension when executed from outside MATLAB, as in a makefile.

On Windows systems, MATLAB issues warnings at MEX setup time, compile time, and run-time to notify you of possible incompatibilities resulting from the change in MEX-file extension from `.dll` to `.mexw32`.

New mex-output Behavior for Compatibility

The `-output` option to `mex` specifies the filename of the compiled MEX-file. In general, `mex` ignores any filename extension supplied in the `-output` argument and uses the extension for the compiled file that is appropriate for the architecture. However, on Windows systems, if the `-output` argument specifies a `.dll` extension, the compiled file has this extension instead of `.mexw32`. Previous versions of MATLAB can recognize the resulting compiled file.

Conflicting MEX-Files Renamed Automatically

If two files with the same name but with `.mexw32` and `.dll` extensions exist in the same directory, MATLAB uses the `.mexw32` file. To avoid unintended shadowing, MATLAB automatically renames compiled MEX-files under the following circumstances:

- When you build a MEX-file with a `.mexw32` extension and the directory contains an existing file with the same name, but with a `.dll` extension, the extension of the `.dll` file is changed to `.dll.old`.
- When you build a MEX-file with a `.dll` extension (using the `mex -output` option) and the directory contains an existing file with the same name, but with a `.mexw32` extension, the extension of the `.mexw32` file is changed to `.mexw32.old`.

New Return Value for mexext on Windows Systems

On 32-bit Windows platforms, the `mexext` function now returns `mexw32`. In MATLAB 7.0.4 it returned `dll`.

New mexext Script to Obtain MEX-File Extension in Makefiles

A new script displays the MEX-file extension in the current version of MATLAB that corresponds to the platform on which the script is executed. It is intended to be used outside MATLAB, in makefiles or scripts, to obtain

the appropriate filename extension for compiled MEX-files. Use this script instead of explicitly specifying the MEX-file extension in a makefile.

The script is named `mexext.bat` on Windows platforms and `mexext.sh` on UNIX platforms. It is located in the directory `$matlab/bin`, where `$matlab` represents the string returned from the `matlabroot` command.

The script displays the MEX-file extension without a leading period. For example, on 32-bit Windows platforms, it returns `mexw32`.

Following is a fragment of a GNU makefile that uses the `mexext` script to obtain the MEX-file extension:

```
ext = $(shell mexext)

yprime.$(ext) : yprime.c
    mex yprime.c
```

New Preferences Directory and MEX Options

Compatibility Considerations: Yes

The MATLAB preferences directory has changed. In MATLAB 7.1, the preferences directory is named R14SP3. In previous R14 releases, the preferences directory was named R14. For more information, see the documentation for `prefdir`, which returns the preferences directory.

Compatibility Considerations

When you install MATLAB 7.1, MATLAB migrates some files from any existing R14 preferences directory to the new R14SP3 directory. However, MATLAB does not migrate the MEX options file, `mexopts.bat`. If you want to preserve any MEX options that you have customized in an earlier R14 release, you need to migrate your options to the new R14SP3 preferences directory.

You can migrate your MEX options in either of two ways:

- If you have customized only a few options: Invoke `mex` with the `-setup` option to create a new `mexopts.bat` file in the R14SP3 preferences directory. Edit the new `mexopts.bat` file to customize the MEX options there.
- If you have customized many options: Copy your customized `mexopts.bat` file from the old R14 preferences directory to the new R14SP3 directory. Edit at least the settings of the `LIBLOC` and `NAME_OUTPUT` linker parameters in the `mexopts.bat` file. These lines should look as follows on Windows systems when using a Microsoft compiler:

```
set LIBLOC=%MATLAB%\extern\lib\win32\microsoft
set NAME_OUTPUT=/out:"%OUTDIR%%MEX_NAME%%MEX_EXT%"
```

The `LIBLOC` parameter has changed because import libraries have moved; see “Import Libraries Moved” on page 1030. The value of this parameter depends on the platform you are running MATLAB on and the vendor of the compiler you are using.

The `NAME_OUTPUT` parameter has changed because the extension for compiled MEX-Files has changed on Windows systems; see “New File Extension for MEX-Files on Windows Systems” on page 1025.

Compiler Support

Compatibility Considerations: Yes

The set of compilers that MATLAB supports has changed in MATLAB 7.1. For an up-to-date list of supported compilers, see the Supported and Compatible Compilers Web page.

Compatibility Considerations

You may need to recompile code compiled with an earlier compiler that is no longer supported.

Import Libraries Moved

Compatibility Considerations: Yes

The import libraries (.lib files) for the MATLAB dll files have been moved up a directory level and are no longer specific to the compiler version. The new location for these files is

```
$matlab/extern/lib/$arch/$vendor
```

where the terms \$matlab, \$arch, and \$vendor respectively represent the string returned from the matlabroot command, the platform you are running MATLAB on, and the vendor of the compiler you are using.

Compatibility Considerations

You may need to change any code that depends on the previous library locations.

MEX Perl Script Moved

The MEX Perl script used in building MEX-files is now located in `$matlab/bin`, rather than `$matlab/bin/win32`. (The term `$matlab` represents the string returned by the `matlabroot` function.) You should not notice any difference, however, as a batch file located in `$matlab/bin/win32` provides backward compatibility.

Linking to System Libraries

MATLAB now links with the system libraries by default. You no longer need to specify them explicitly.

COM Automation Server Now Displays Figure

When using MATLAB as an Automation server, executing MATLAB commands that create figures now displays the figure window.

Previous releases of MATLAB created the figure in the background. To duplicate the old behavior, create a figure with its `Visible` property set to `off`, then set the property to `on` when you want the figure to be visible:

```
h = actxserver('matlab.application');  
h.Execute('figure visible off');  
h.Execute('plot(1:10)');  
h.Execute('set(gcf, 'visible', 'on')');
```


R14SP2

Version: 7.0.4
New Features: Yes
Bug Fixes: No

Desktop Tools and Development Environment

Installation Folder with Spaces

In MATLAB 7.0.4 (R14SP2) software, the following two changes have been made to the MathWorks Installer on Microsoft Windows platforms:

- The Installer now allows a folder name with spaces in the installation path.
- The Installer honors the default installation folder for Windows software, which on most machines is Program Files.

These changes were made in response to many customer requests and the desire to conform to a widely established industry practice for the PC platform.

Note MathWorks products are used and integrated into many software environments. If you use MathWorks products in conjunction with other third party applications (compilers, other numerical analysis packages, etc.) you might want to continue installing into a folder that does not have spaces in the path until you have tested that those applications work with MathWorks products.

Startup and Shutdown

Compatibility Considerations: Yes

Confirmation Dialog Box for Quitting Added

When quitting MATLAB, a confirmation dialog box appears if you set a new preference for that purpose. By default, the confirm quitting preference is not set, so the dialog box will not appear. To change the preference, see the instructions for Confirmation Dialogs Preferences in the desktop documentation.

JVM Software Updated

MATLAB is now using version 1.5 of Sun Microsystems Java JVM software on Windows, Linus Torvalds Linux (32-bit), and Sun Microsystems Solaris platforms. Java software is supplied with MATLAB, so this change requires no action on your part.

Compatibility Considerations

If you use a specific version of Java with MATLAB on Windows, Linux 32-bit, or Solaris platforms, this change might affect you.

Desktop

Confirmation Dialog Boxes Preference Introduced

There are new preferences for displaying or not displaying confirmation dialog boxes for desktop tools. In previous versions, some of these preferences existed but were located with other preferences for the associated desktop tool. They are now organized in one preference panel for all desktop tools. Access them by selecting **File > Preferences > General > Confirmation Dialogs**. These preferences work in conjunction with the **Do not show this prompt again** check boxes that appears on various desktop confirmation dialog boxes. For more information, see Confirmation Dialogs Preferences in the desktop documentation.

Running Functions – Command Window and History

Overwrite Mode Now Supported

The Command Window now supports overwrite mode. Press the **Insert** key to enter text in overwrite mode. Press the **Insert** key again to return to entering text in insert mode. View the current state at the far right end of the status bar of the Command Window when it is undocked, or in the desktop when the Command Window is docked and has focus. In insert mode, **OVR** in the status bar is gray and the cursor has a wide block shape.

Hyperlink Color Preference Added

Set the color of hyperlinks that display in the Command Window. Select **File > Preferences > Command Window**, and under **Display**, select **Hyperlink color**.

Help

Compatibility Considerations: Yes

Subfunction Help Syntax Changed

To get help for a subfunction, use

```
help functionname>subfunctionname
```

Compatibility Considerations

In previous versions, the syntax was `help functionname/subfunctionname`. This change was introduced in R14 (MATLAB 7.0) but was not documented.

Bug Fixes and Known Problems Now on Web; No Longer Found Via Help Search

The Release Notes sections “Major Bug Fixes” and “Known Software and Documentation Problems” no longer include the content in the installed help files. Instead, the sections provide links to these lists on the MathWorks Web site. The lists on the Web site can be updated after the release date to reflect the latest information.

Compatibility Considerations

As a result of this change, the Help browser **Search** feature will not find search terms that are in the content of those reports. Use the MathWorks Web site search features to look for search terms in those reports.

Workspace, Search Path, and File Operations

Formatting Decimal Separator when Copying From the Array Editor

You can now specify how you want decimal numbers to be formatted when you cut or copy cells from the Array Editor and paste them into text files or other applications. You can specify a separator for this purpose in the Array Editor panel of the **Preferences** dialog. The **Decimal separator to use when copying** edit field is by default "." (period). If you are working in or providing data to a locale that uses a different character to delimit decimals, type that character in this edit field and click **OK** or **Apply**.

Workspace Browser Preference Panel Removed

The Workspace browser preferences panel was removed. The entry on that panel was for confirming deletion of variables. That preference is now part of **General > Confirmation Dialogs** preferences.

Compatibility Considerations

Use **File > Preferences > General > Confirmation Dialogs** instead of **File > Preferences > Workspace Browser**.

Current Directory Browser Preferences Added

There are new Current Directory browser preferences you can access by selecting **File > Preferences > Current Directory Browser, Browser display options**:

- View the file size by selecting the **Show file sizes** check box. (This is selected by default.)
- For models created with Simulink software, view brief descriptions in the **Description** column when **Show M and MDL file descriptions** is selected.
- For models created with Simulink, view the complete descriptions in the lower pane when the preference for **Show M, MDL and MAT file contents** is selected. This allows you to view information about a model without running Simulink.

Editing and Debugging M-Files

Compatibility Considerations: Yes

Go To Subfunction or Nested Function

Go directly to a subfunction or nested function within an M-file using the enhanced **Go To** dialog box. Access the dialog box by selected **Edit > Go To**. Click the **Name** column header to arrange the list of functions alphabetically, or click the **Line** column header to arrange the list by the position of the functions in the file.

Help Browser Now Accessible from MATLAB Stand-Alone Editor

You can now access the MATLAB Help browser from the MATLAB stand-alone Editor. This provides you with documentation for MATLAB, including using Editor features and MATLAB functions.

Preference for Editor/Debugger Dialog Moved

The **Show dialog prompt** preference has been moved to **Preferences > General > Confirmation Dialogs**. For more information, see Confirmation Dialogs Preferences in the desktop documentation.

Compatibility Considerations

Use **File > Preferences > General > Confirmation Dialogs** instead of **File > Preferences > Editor/Debugger** to set this preference.

Dragging Text Maintains Font and Highlighting

Now, when you drag text from the Editor/Debugger to another application, it maintains the syntax highlighting and font characteristics.

Source Control Interface

Compatibility Considerations: Yes

Register Project Feature Added; Add to Source Control Behavior Changed

There is a new source control interface feature for Windows platforms, **Register Project with MATLAB**. Use this to associate all files in a directory with a source control project. You perform this for any file in a directory, which registers the directory and all files in that directory. You only perform this once in a directory, and must perform it before you perform any other source control actions for files in that directory.

Access the feature in the Current Directory browser by right-clicking a file and selecting **Source Control > Register Your Source Control System Project with MATLAB** from the context menu. You can also access it from the Editor/Debugger **File** menu. To access the feature for files created with Simulink or Stateflow[®] software, use the Current Directory browser.

For a summary of the process, see the topic Source Control Interface on Microsoft Windows in the desktop documentation.

Compatibility Considerations

In previous releases, this feature was part of the **Add to Source Control** feature. You still need to add each file to source control, but you do this after first registering the directory that contains the file.

Project Name Exact Match No Longer Required

The name of the project in the source control system is no longer required to exactly match the name of the directory on disk containing the files.

Publishing Results

Compatibility Considerations: Yes

Cell Publishing: File Extension Changes

The files created when publishing using cells now have more natural extensions. JPEG files now have a .jpg instead of a .jpeg extension, and EPSC2 files now have an .eps instead of an .epsc2 extension.

Compatibility Considerations

If you relied on the formerly used file extensions, you need to accommodate the changes.

Cell Publishing: LaTeX Image File Type Changes

Publishing to LaTeX now respects the image file type you specify in preferences rather than always using EPSC2 files.

Cell Publishing: Image Options More Restrictive

The **Publish image options** in Editor/Debugger preferences for **Publishing Images** have changed slightly. The changes prevent you from choosing invalid formats.

Notebook Support for Microsoft Word 97 Application to be Discontinued

Notebook will no longer support the Microsoft Word 97 application starting in the next release of MATLAB.

Compatibility Considerations

If you use Word 97 with Notebook, you will need to migrate to a more recent version.

Mathematics

New Vendor BLAS Used for Linear Algebra in MATLAB

MATLAB uses Basic Linear Algebra Subprograms (BLAS) for its vector inner product, matrix-vector product, matrix-matrix product, and triangular solvers in `\`. MATLAB also uses BLAS behind its core numerical linear algebra routines from Linear Algebra Package (LAPACK), which are used in functions like `chol`, `lu`, `qr`, and within the linear system solver `\`.

Starting in this release

- On Macintosh, MATLAB now uses the Accelerate framework.
- On 64-bit Linux, MATLAB uses Intel Math Kernel Library (MKL) 7.0.1 on Intel chips, and AMD Core Math Library (ACML) 2.0 on AMD chips.

max and min on Complex Integers Not Supported

Compatibility Considerations: Yes

Using the `max` and `min` functions on complex integer inputs (as shown in the example below) is no longer supported. This operation had been supported from release R11 through R14SP1, but now returns an error.

```
max(int8([3-4i 3+4i]))
```

Compatibility Considerations

Any code that calls `max` or `min` on complex integers should be removed from your program files.

Programming

Memory-Mapping

Memory-mapping is a mechanism that maps a portion of a file, or an entire file, on disk to a range of addresses within an application's address space. The application can then access files on disk in the same way it accesses dynamic memory. This makes file reads and writes faster in comparison with using functions such as `fread` and `fwrite`.

Another advantage of using memory-mapping in MATLAB is that it enables you to access file data using standard MATLAB indexing operations. Once you have mapped a file to memory, you can read the contents of that file using the same type of MATLAB statements used to read variables from the MATLAB workspace. The contents of the mapped file appear as if they were an array in the currently active workspace. You simply index into this array to read or write the desired data from the file.

Memory-mapped files also provide a mechanism for sharing data between applications. This is achieved by having each application map sections of the same file. This feature can be used to transfer large data sets between MATLAB and other applications.

textscan Enhancements

The `textscan` function originally read data only from files. As of this release, you can use `textscan` to read from strings as well.

xlsread Enhancements

In this release, you can write a function and pass a handle to this function to `xlsread`. When `xlsread` executes, it reads from the spreadsheet, executes your function on the data read from the spreadsheet, and returns the final results to you.

You can use either of the following syntaxes:

```
num = xlsread('filename', ..., functionhandle)
[num, txt, raw, X] = xlsread('filename', ..., functionhandle)
```

For an example, see the `xlsread` reference page.

xlsread Imported Date Format Changes

Compatibility Considerations: Yes

In MATLAB versions prior to R14, date values read into MATLAB from an Excel spreadsheet using `xlsread` were always imported as numeric date values. The R14 and later releases of MATLAB import dates in the format in which they were stored in the Excel file. Dates stored in string or date format are now imported as strings by `xlsread`. Dates stored in numeric format are imported as numeric date values.

Compatibility Considerations

Because of a difference in the way Excel and MATLAB compute numeric date values, any numeric dates imported from Excel into MATLAB must be converted to the MATLAB format before being used in the MATLAB application. For more information, see [When to Convert Dates from Excel Files](#).

format Options Added

You can display MATLAB output using two new formats: `short eng` and `long eng`. See the `format` reference page for more information.

- `short eng` — Displays output in an engineering format that has at least 5 digits and a power that is a multiple of three.
- `long eng` — Displays output in an engineering format that has exactly 16 significant digits and a power that is a multiple of three.

```
format short eng
pi
ans =
    3.1416e+000
```

```
format long eng
pi
ans =
    3.14159265358979e+000
```

Nonscalar Arrays of Function Handles to Become Invalid

Compatibility Considerations: Yes

Creation of nonscalar arrays of function handles by `str2func` may be invalid or may return different results in future versions of MATLAB, but will continue to work in R14.

Compatibility Considerations

To avoid this warning and prepare for this change, convert the cell array of strings to a cell array of function handles.

For more information, type `help function_handle` and see the section entitled Note on Backward Compatibility.

Assigning Nonstructure Variables As Structures Displays Warning

Compatibility Considerations: Yes

Assigning to a nonstructure variable as if it were a structure is not recommended in MATLAB. For example, if variable `x` holds a double (as shown below), then attempting to add a fieldname to it, thus converting `x` to a structure, is not good programming practice and should generate an error.

```
x = 10;  
x.name = magic(3);
```

Note that if `x` were empty (i.e., `x == []`), then assigning a field to it as if it were already a structure is acceptable.

Behavior Prior to Release R14

Because of a bug in releases of MATLAB prior to R14, you can assign a field to a nonempty, nonstructure variable in those releases without MATLAB generating a warning message or error. The result is that MATLAB quietly converts the variable to a structure:

```
x = 10;  
class(x)  
ans =  
    double  
  
x.name = magic(3);    % Invalid expression completes  
                    %   without warning or error.  
  
class(x)  
ans =  
    struct
```

Behavior In R14 and Later

In the MATLAB R14 and R14 service pack releases, you can still perform this type of operation, but MATLAB now displays a warning message:

```
x = 10;  
x.name = magic(3);
```


Warning: Struct field assignment overwrites a value with class "double".

In a future release of MATLAB, attempting this type of operation will throw an error instead of just displaying a warning message.

Compatibility Considerations

You are encouraged to modify any code that generates this warning. The section “Making a Valid Assignment” on page 1057 gives instructions on how to do this.

Another Case – Extending the Depth of a Structure

The same rules apply when extending the depth of a structure by adding additional, lower-level fields. The first line of the example shown below creates a structure named `handle` and assigns to it a field of type `double` named `output`. The line after that treats this `double` as if it were a structure by attempting to assign a field named `time` to it. The second line is an invalid expression:

```
handle.output = 5;  
handle.output.time = 13;
```

As in the case discussed earlier, this assignment does not generate a warning or error in MATLAB releases prior to R14. In the R14 and R14 service pack releases of MATLAB, you get the warning shown in the previous example. Beginning in a future release of MATLAB, this assignment will throw an error.

Making a Valid Assignment

To avoid this warning and future errors, first make `x` an empty structure or empty array as shown here. Once a variable is established as a structure or empty array, you can assign fields to it without getting an error:

```
x = struct;      or      x = [];  
x.name = magic(3);
```

In the case of extending the depth of an existing structure, you can perform this type of assignment without generating a warning or error using the `struct` function as shown here:

```
handle.output = struct('time', 13);
```

Function Declaration Compatibility with Pre-R14 M-Files

Compatibility Considerations: Yes

As of Release 14, the function definition line in a function M-file no longer requires commas separating output variables. However, because this syntax is not compatible with earlier releases, you should always include the comma separators when writing an M-file function that you intend to run on releases both earlier and later than Release 14.

Compatibility Considerations

See Comma Separators Not Required in Function Declaration in the Release 14 release notes.

Graphics and 3-D Visualization

imwrite Now Supports GIF Export

The `imwrite` function now supports exporting image data in Graphics Interchange Format (GIF).

Cannot Dock Figures on Macintosh

You cannot dock figures in the Desktop, because MATLAB uses native figure windows on the Macintosh platform.

Compatibility Considerations

You cannot dock figure in the Desktop on the Macintosh

Plotting Tools Not Working on Macintosh

The plotting tools are not supported on the Macintosh platform. This means the Figure Palette, Plot Browser, and Property Editor do not work these platforms. To use the MATLAB 6 Property Editor, see the `propedit` command.

Compatibility Considerations

You cannot use plotting tools on the Macintosh.

Not All Macintosh System Fonts Are Available

MATLAB figures do not support the same fonts as native Macintosh applications. Use the `uifont` functions to see which fonts are available in the MATLAB environment.

Compatibility Considerations

Some Macintosh fonts are not available in MATLAB

XDisplay Property Setable on Motif-Based Systems

You can specify the value of the figure XDisplay property only on systems using Motif-Based figure windows.

Compatibility Considerations

The figure XDisplay property is supported only on systems using Motif.

Creating Graphical User Interfaces (GUIs)

New Callbacks Chapter

The Creating Graphical User Interfaces documentation offers a new chapter, in draft form, that attempts to bring information regarding callbacks into one place. It introduces the concepts and mechanisms with which you work, and explains some basic techniques for programming your GUI's behavior. This chapter is not yet complete, but you may find it useful, even in its current state, particularly if you are new to creating GUIs.

Temporarily, this new chapter appears as Appendix A, “Working with Callbacks (Draft).” It contains some new information, but also duplicates information that can be found in various places throughout the rest of the book. In cases where information has not yet been included in the new chapter, links take you to the main part of the book.

External Interfaces/API

New File Archiving Functions and Functionality

In addition to being able to `zip` and `unzip` compressed file archives, MATLAB software now supports the following archiving functions:

- `gzip/gunzip` — Compress/uncompress files in gzip format.
`gunzip` reads archives from both file systems and URLs.
- `tar/untar` — Compress/extract files in a tar-file.
`untar` reads archives from both file systems and URLs.
- The `unzip` function can now also open a zip archive from a URL.