

Global Optimization Toolbox Release Notes

How to Contact MathWorks



www.mathworks.com Web
comp.soft-sys.matlab Newsgroup
www.mathworks.com/contact_TS.html Technical Support



suggest@mathworks.com Product enhancement suggestions
bugs@mathworks.com Bug reports
doc@mathworks.com Documentation error reports
service@mathworks.com Order status, license renewals, passcodes
info@mathworks.com Sales, pricing, and general information



508-647-7000 (Phone)



508-647-7001 (Fax)



The MathWorks, Inc.
3 Apple Hill Drive
Natick, MA 01760-2098

For contact information about worldwide offices, see the MathWorks Web site.

Global Optimization Toolbox Release Notes

© COPYRIGHT 2005–2013 by The MathWorks, Inc.

The software described in this document is furnished under a license agreement. The software may be used or copied only under the terms of the license agreement. No part of this manual may be photocopied or reproduced in any form without prior written consent from The MathWorks, Inc.

FEDERAL ACQUISITION: This provision applies to all acquisitions of the Program and Documentation by, for, or through the federal government of the United States. By accepting delivery of the Program or Documentation, the government hereby agrees that this software or documentation qualifies as commercial computer software or commercial computer software documentation as such terms are used or defined in FAR 12.212, DFARS Part 227.72, and DFARS 252.227-7014. Accordingly, the terms and conditions of this Agreement and only those rights specified in this Agreement, shall pertain to and govern the use, modification, reproduction, release, performance, display, and disclosure of the Program and Documentation by the federal government (or other entity acquiring for or through the federal government) and shall supersede any conflicting contractual terms or conditions. If this License fails to meet the government's needs or is inconsistent in any respect with federal procurement law, the government agrees to return the Program and Documentation, unused, to The MathWorks, Inc.

Trademarks

MATLAB and Simulink are registered trademarks of The MathWorks, Inc. See www.mathworks.com/trademarks for a list of additional trademarks. Other product or brand names may be trademarks or registered trademarks of their respective holders.

Patents

MathWorks products are protected by one or more U.S. patents. Please see www.mathworks.com/patents for more information.

R2013b

No New Features or Changes

R2013a

Vectorized scalar patternsearch assumes row
orientation 4

R2012b

Example of mixed integer programming using ga 6

R2012a

No New Features or Changes

R2011b

Mixed Integer Nonlinear Programming in Genetic
Algorithm Solver 10
New Demo 10
Conversion of Error and Warning Message Identifiers ... 10

R2011a

“History to New Window” Output Functions Removed ...	14
--	----

R2010b

Output Functions and Plot Functions for GlobalSearch and MultiStart	16
Demo Removed	16

R2010a

Toolbox Renamed and Expanded	18
New GlobalSearch and MultiStart Solver Objects	18
New patternsearch Poll Method	19
New Demo	19
threshacceptbnd Function Removed	19

R2009b

threshacceptbnd Function Deprecated	22
---	----

R2009a

New Demo	24
----------------	----

R2008b

Optimization Tool Enables Parallel Functionality	26
--	----

R2008a

Parallel Computing Toolbox Support	28
Genetic Algorithm Tool and Pattern Search Tool Combined Into Optimization Tool	28
New Optimization Tool Support for gamultiobj, simulannealbnd, and threshacceptbnd	28
New Automatic Population Generation in ga and gamultiobj	28
New Default StallTimeLimit Option = Inf in Genetic Algorithm	29

R2007b

Multiobjective Optimization with Genetic Algorithm	32
Multiobjective Optimization with Genetic Algorithm and Custom Data Types	32
Hybrid Multiobjective Optimization Combining Genetic Algorithm with Optimization Toolbox	32
Vectorized Function Inputs with Nonlinear Constraints ..	32
New Demos	32

R2007a

New Functions for Simulated Annealing and Threshold Acceptance	36
ga Output Argument exitflag Returns Numeric Value	36

R2006b

New Syntax for Search Method Option in Pattern Search Algorithm Improves Speed and Memory	40
--	----

Bug Fixes

Both the Genetic Algorithm and the Pattern Search Algorithm Now Accept Nonlinear Constraints	44
Direct Search Now Implements Two Algorithms — Generalized Pattern Search Algorithm (GPS) and Mesh Adaptive Search Algorithm (MADS)	44
New Options Available in the Genetic Algorithm	44
New Options Available in the Pattern Search Algorithm . .	45
New Demos	45

R2013b

Version: 3.2.4

New Features: No

Bug Fixes: No

No New Features or Changes

R2013a

Version: 3.2.3

New Features: No

Bug Fixes: Yes

Vectorized scalar patternsearch assumes row orientation

Compatibility Considerations: Yes

When x_0 is a scalar, `patternsearch` now expects your objective function to output a column vector of values. In addition, any nonlinear constraint functions need to output column vectors as well.

Compatibility Considerations

Previously, `patternsearch` assumed that scalar problems were in column form, so expected a vectorized objective function to output a row vector.

R2012b

Version: 3.2.2

New Features: No

Bug Fixes: Yes

Example of mixed integer programming using ga

There is an updated example of mixed integer programming using `ga`. View the example [here](#). To run the example at the MATLAB® command line:

```
echodemo steppedCantileverExample
```

This example replaces a similar example, `weldedBeamDemo`.

R2012a

Version: 3.2.1

New Features: No

Bug Fixes: No

No New Features or Changes

R2011b

Version: 3.2

New Features: Yes

Bug Fixes: No

Mixed Integer Nonlinear Programming in Genetic Algorithm Solver

The `ga` function now allows you to specify that certain variables are integer valued. When you include integer constraints, you can have any objective function, bounds, and inequality constraints, but you cannot directly include equality constraints. To try to circumvent this limitation, see [No Equality Constraints](#).

For details on mixed-integer programming, see the `ga` function reference page or [Mixed Integer Optimization](#).

New Demo

There is a new demo of `ga` for mixed integer programming. Run the demo at the MATLAB command line by entering `echodemo weldedBeamDemo`.

Conversion of Error and Warning Message Identifiers

Compatibility Considerations: Yes

For R2011b, error and warning message identifiers have changed in Global Optimization Toolbox.

Compatibility Considerations

If you have scripts or functions that use message identifiers that changed, you must update the code to use the new identifiers. Typically, message identifiers are used to turn off specific warning messages, or in code that uses a `try/catch` statement and performs an action based on a specific error identifier.

For example, the `'globaloptim:EQNSOLV:sparseToFull'` identifier has changed to `'globaloptim:eqnsolv:eqSparseToFull'`. If your code checks for `'globaloptim:EQNSOLV:sparseToFull'`, you must update it to check for `'globaloptim:eqnsolv:eqSparseToFull'` instead.

To determine the identifier for a warning, run the following command just after you see the warning:


```
[MSG,MSGID] = lastwarn;
```

This command saves the message identifier to the variable MSGID.

To determine the identifier for an error, run the following command just after you see the error:

```
exception = MException.last;  
MSGID = exception.identifier;
```

Tip Warning messages indicate a potential issue with your code. While you can turn off a warning, a suggested alternative is to change your code so it runs warning free.

R2011a

Version: 3.1.1

New Features: Yes

Bug Fixes: Yes

“History to New Window” Output Functions Removed

The patternsearch and ga **History to new window** output functions (@psoutputhistory and @gaoutputgen) have been removed. Obtain the same functionality by setting one of the following:

- Display option to 'iter' with psoptimset or gaoptimset
- **Level of display** to iterative in the **Display to command window** part of the Optimization Tool **Options** pane

R2010b

Version: 3.1

New Features: Yes

Bug Fixes: Yes

Output Functions and Plot Functions for GlobalSearch and MultiStart

Compatibility Considerations: Yes

Use output functions or plot functions with `GlobalSearch` and `MultiStart` to report and plot information on algorithm progress during runs. You can also stop the solvers according to criteria you set. For more information, see [Output Functions for GlobalSearch and MultiStart](#) and [Plot Functions for GlobalSearch and MultiStart](#).

Compatibility Considerations

In order to make exit flags have more uniform meaning across solvers, two `GlobalSearch` and `MultiStart` exit flags have different meanings than in R2010a:

Exit Flag	Meaning
-1	<code>GlobalSearch</code> or <code>MultiStart</code> stopped by an output function or plot function (regardless of local solver exit flag)
-8	No solution found; all local solver runs had exit flag -1 or smaller

Demo Removed

The demo titled “Using the Genetic Algorithm with the Parallel Computing Toolbox™” was removed from the toolbox. The demo used more complex parallelization techniques than those in the `Optimization Toolbox™` demo titled “Minimizing an Expensive Optimization Problem Using Parallel Computing Toolbox.”

R2010a

Version: 3.0

New Features: Yes

Bug Fixes: Yes

Toolbox Renamed and Expanded

Compatibility Considerations: Yes

Former Genetic Algorithm and Direct Search Toolbox™ functions are now part of Global Optimization Toolbox software.

Compatibility Considerations

Error and warning IDs now use the `globaloptim` name instead of the `gads` name. For example, to turn off the `sahybrid:unconstrainedHybridFcn` warning, instead of

```
warning('off','gads:sahybrid:unconstrainedHybridFcn')
```

use the statement

```
warning('off','globaloptim:sahybrid:unconstrainedHybridFcn')
```

New GlobalSearch and MultiStart Solver Objects

`GlobalSearch` and `MultiStart` run a local solver (such as `fmincon`) from a variety of start points. The goal is to find a global minimum, or multiple local minima. The chief differences between the solver objects are:

- `GlobalSearch` uses a scatter-search mechanism for generating start points. `MultiStart` uses uniformly distributed start points within bounds, or user-supplied start points.
- `GlobalSearch` analyzes start points and rejects those that are unlikely to improve the best local minimum found so far. `MultiStart` runs all start points.
- `MultiStart` gives a choice of local solver: `fmincon`, `fminunc`, `lsqcurvefit`, or `lsqnonlin`. `GlobalSearch` uses `fmincon`.
- `MultiStart` can be run in parallel, distributing start points to multiple processors. `GlobalSearch` does not run in parallel.

These solver objects come with a variety of new objects, functions, and methods:

- `createOptimProblem` — Function for creating optimization problem structure
- `CustomStartPointSet` and `RandomStartPointSet` — Objects for `MultiStart` multiple start points
- `GlobalOptimSolution` — Object for holding results of multiple runs of local solver
- `list` — Method for obtaining start points from a `CustomStartPointSet` or `RandomStartPointSet`
- `run` — Method for running `GlobalSearch` or `MultiStart` objects with optimization problem structures

For more information, see `Using GlobalSearch` and `MultiStart` in the `Global Optimization Toolbox User's Guide`.

New patternsearch Poll Method

A new poll method generates search directions faster and more reliably in `patternsearch` for linearly constrained problems. Use this poll method at the command line by setting the `PollMethod` option to `'GSSPositiveBasis2N'` or `'GSSPositiveBasisNp1'` with `psoptimset`. With the Optimization Tool, set **Options > Poll > Poll method** to `GSS Positive basis 2N` or `GSS Positive basis Np1`.

For more information, see `Poll Options` in the `Global Optimization Toolbox User's Guide`.

New Demo

There is a new demo showing how to use `GlobalSearch` and `MultiStart` to find a global optimum or several local optima. Run the demo at the MATLAB command line by entering `echodemo opticalInterferenceDemo`.

threshacceptbnd Function Removed

Compatibility Considerations: Yes

The `threshacceptbnd` function has been removed.

Compatibility Considerations

Use `simulannealbnd` for similar functionality. To obtain results using a threshold acceptance algorithm, write a custom acceptance function for `simulannealbnd`—see `AcceptanceFcn` in Algorithm Settings.

R2009b

Version: 2.4.2

New Features: Yes

Bug Fixes: No

threshacceptbnd Function Deprecated

Compatibility Considerations: Yes

The `threshacceptbnd` function will be removed in a future release.

Compatibility Considerations

The `threshacceptbnd` function now warns that it will be removed in a future release. Use `simulannealbnd` for similar functionality. To obtain results using a threshold acceptance algorithm, write a custom acceptance function for `simulannealbnd`—see `AcceptanceFcn` in Algorithm Settings.

R2009a

Version: 2.4.1

New Features: Yes

Bug Fixes: Yes

New Demo

There is a new demo showing graphically how `patternsearch` works. To see the demo, enter `echodemo mtwashdemo` at the MATLAB command line.

R2008b

Version: 2.4

New Features: Yes

Bug Fixes: No

Optimization Tool Enables Parallel Functionality

You can now access built-in parallel functionality in Optimization Tool for relevant Genetic Algorithm and Direct Search Toolbox solvers. The option is available when you have a license for Parallel Computing Toolbox functions.

R2008a

Version: 2.3

New Features: Yes

Bug Fixes: No

Parallel Computing Toolbox Support

The functions `ga`, `gamultiobj`, and `patternsearch` can take advantage of parallel computing. Furthermore, applicable hybrid functions can use parallel computing. For more information, see the Parallel Processing chapter in the User's Guide.

Genetic Algorithm Tool and Pattern Search Tool Combined Into Optimization Tool

Compatibility Considerations: Yes

The Genetic Algorithm Tool and Pattern Search Tool GUIs have been combined into the Optimization Toolbox Optimization Tool GUI. To access these GUIs, enter `optimtool` at the command line and choose the appropriate solver.

Compatibility Considerations

The functions `gatool` and `psearchtool` continue to work, calling `optimtool` with the appropriate solver selected (`ga` or `patternsearch`). However, the functions `gatool` and `psearchtool` are no longer listed in the documentation.

New Optimization Tool Support for `gamultiobj`, `simulannealbnd`, and `threshacceptbnd`

The Optimization Tool GUI now includes the functions `gamultiobj`, `simulannealbnd`, and `threshacceptbnd`. Therefore, all Genetic Algorithm and Direct Search Toolbox solvers are supported in Optimization Tool. To access these GUIs, enter `optimtool` at the command line and choose the appropriate solver.

New Automatic Population Generation in `ga` and `gamultiobj`

Compatibility Considerations: Yes

`ga` and `gamultiobj` can now create populations satisfying bounds and linear constraints, with well-dispersed populations, using the function `gacreationlinearfeasible`.

Compatibility Considerations

The previous creation function, `gacreationuniform`, is accessible by using `gaoptimset` to set `CreationFcn` to `@gacreationuniform`. The new default behavior is to use `gacreationlinearfeasible` when there are linear constraints, and `gacreationuniform` when there are bounds or no constraints.

New Default StallTimeLimit Option = Inf in Genetic Algorithm

Compatibility Considerations: Yes

The default value of `StallTimeLimit` in `ga` used to be 20. It was changed to `Inf` in order to avoid time-outs when using computationally intensive fitness functions.

Compatibility Considerations

Change `StallTimeLimit` to 20 using `gaoptimset` to get the previous behavior.

R2007b

Version: 2.2

New Features: Yes

Bug Fixes: Yes

Multiobjective Optimization with Genetic Algorithm

Multiobjective optimization, with linear and bound constraints, is now available through the new function `gamultiobj`. This function determines optimal Pareto fronts from specified criteria, including Pareto fronts that are nonconvex, disconnected, or both.

Optimization Toolbox also contains multiobjective functionality, but cannot reliably generate optimal Pareto fronts if these are nonconvex or disconnected.

Two new demos illustrate this feature. See “New Demos” on page 32.

Multiobjective Optimization with Genetic Algorithm and Custom Data Types

The new function `gamultiobj` also supports multiobjective optimization with custom data types, including binary.

Hybrid Multiobjective Optimization Combining Genetic Algorithm with Optimization Toolbox

To determine multiobjective optimizations more accurately, you can now combine the new function `gamultiobj` with the existing function `fgoalattain` from Optimization Toolbox.

Vectorized Function Inputs with Nonlinear Constraints

The functions `ga` and `patternsearch` now accept vectorized function inputs with nonlinear constraints. The new function `gamultiobj` does as well.

New Demos

Two accompanying demos illustrate the use of the new multiobjective genetic algorithm function `gamultiobj`:

- `gamultiobjfitness` uses `gamultiobj` to solve a simple problem with one decision variable and two objectives.
- `gamultiobjoptionsdemo` shows how to set options for multiobjective optimization with a simple genetic algorithm problem.

R2007a

Version: 2.1

New Features: Yes

Bug Fixes: Yes

New Functions for Simulated Annealing and Threshold Acceptance

The following functions have been added for simulated annealing and threshold acceptance:

<code>simulannealbnd</code>	Perform unconstrained or bound-constrained minimization of a function of several variables using simulated annealing. The default algorithm uses adaptive annealing, but options can be changed to use Boltzmann annealing, fast annealing, and other variants.
<code>threshacceptbnd</code>	Perform unconstrained or bound-constrained minimization of a function of several variables using threshold acceptance.
<code>saoptimset</code>	Create or modify optimization options for <code>simulannealbnd</code> or <code>threshacceptbnd</code> .
<code>saoptimget</code>	Access options for <code>simulannealbnd</code> or <code>threshacceptbnd</code> .

If you are viewing this documentation in the Help browser, the following demos are available:

- [Minimization Using Simulated Annealing And Threshold Acceptance Algorithms](#)
- [Simulated Annealing and Threshold Acceptance Options](#)
- [Custom Data Type Optimization Using Simulated Annealing](#)

ga Output Argument `exitflag` Returns Numeric Value **Compatibility Considerations: Yes**

The third output argument returned by the `ga` function is now a numeric value. This change is consistent with other optimization solvers in MATLAB and makes it easier to programmatically determine the reason the solver

stopped. As in previous versions, the fourth output argument is a structure with the field `message` containing a string that indicates the reason the solver stopped.

The new syntax is as follows:

```
[x,fval,exitflag,output] = ga(fitnessfcn, ...)
```

For more information, including a description of the messages that correspond to the numeric values for each `exitflag` value, see the `ga` function reference page in the Genetic Algorithm and Direct Search Toolbox User's Guide for more information.

Compatibility Considerations

In previous versions, the third output argument returned by `ga` is a string describing the reason the solver stopped.

```
[x,fval,reason] = ga(fitnessfcn, ...)
```

If you used the third output argument of the `ga` function programmatically in a previous release, for example, to compare the value to a string, this code will now produce an error.

R2006b

Version: 2.0.2

New Features: Yes

Bug Fixes: Yes

New Syntax for Search Method Option in Pattern Search Algorithm Improves Speed and Memory

Compatibility Considerations: Yes

The new syntax is more efficient both with speed and memory. This is done by changing the way linear and bound constraints are stored and passed to a search function. The following describes the new calling syntax:

```
function [successSearch,xBest,fBest,funccount] =  
searchfcn_template(fun,x,A,b,Aeq,beq,lb,ub, ...  
    optimValues,options)
```

For more information on how to use the new search function syntax, see *Structure of the Search Function in the Genetic Algorithm and Direct Search Toolbox User's Guide*. To see a template that you can view and edit, type

```
edit searchfcn_template
```

at the Command Window.

Compatibility Considerations

In previous versions, a search function required the following calling syntax:

```
function [successSearch,nextIterate,optimState] =  
searchfcn_template(fun,iterate,tol,A,L,U, ...  
    funeval,maxfun,searchoptions,objfcnarg, ...  
    iterlimit,factors)
```

If you have a search function written for use in a previous release, the function performs correctly in Version 2.0.2 but returns a warning. Custom search functions written in a previous version need to be updated with the new syntax. In later versions, this syntax may cause a warning or error.

The `searchConversion` utility function is provided to convert your search functions from previous releases to the new syntax of Version 2.0.2. For more information on obtaining and using the conversion function, see this technical support solution.

R2006a

Version: 2.0.1

New Features: No

Bug Fixes: Yes

R14SP3

Version: 2.0

New Features: Yes

Bug Fixes: Yes

Both the Genetic Algorithm and the Pattern Search Algorithm Now Accept Nonlinear Constraints

Previously, the genetic algorithm solver only solved unconstrained optimization problems, and the pattern search solver solved unconstrained optimization problems as well as those with linear constraints and bounds. Now, both solvers have the ability to solve general nonlinear optimization problems with linear constraints, bounds, and nonlinear constraints by accepting a nonlinear constraint function. The M-file for the nonlinear constraint function is accepted as an input argument at the command line for both the `ga` and `patternsearch` functions, as well as in the **Constraints** panel of `psearchtool` and `gatool`.

Direct Search Now Implements Two Algorithms – Generalized Pattern Search Algorithm (GPS) and Mesh Adaptive Search Algorithm (MADS)

The GPS algorithm is the pattern search algorithm implemented in previous versions of the toolbox. The MADS algorithm is a modification of the GPS algorithm. The algorithms differ in how the set of points forming the mesh is computed. The GPS algorithm uses fixed direction vectors, whereas the new MADS algorithm uses a random selection of vectors to define the mesh.

New Options Available in the Genetic Algorithm

The following options are available in the `gatool` and when using the `ga` function at the command prompt:

- The new **Constraints** panel has a **Nonlinear constraint function** field in addition to fields for linear constraints and bounds for solving constrained optimization problems
- New **Max constraint** (`@gaplotmaxconstr`) option in the **Plot** pane to plot the maximum nonlinear constraint violation at each generation
- New crossover function, **Arithmetic** (`@crossoverarithmetic`), available in the **Crossover** panel that creates children that are the weighted arithmetic mean of two parents

- New mutation function, **Adaptive Feasible** (`mutationadaptfeasible`), available in the **Crossover** panel that randomly generates directions that are adaptive with respect to the last successful or unsuccessful generation. This function is the default for constrained problems
- New **Algorithm settings** panel for selecting algorithm specific parameters, such as the penalty parameters, **Initial penalty** and **Penalty factor**, for a nonlinear constraint algorithm
- New **Hybrid function**, `fmincon`, for constrained problems
- New **Nonlinear constraint tolerance** parameter in **Stopping criteria**

New Options Available in the Pattern Search Algorithm

The following options are available in the `psearchtool` and when using the `patternsearch` function at the command prompt:

- **Constraints** now has a **Nonlinear constraint function** option to solve for constrained optimization problems
- New **Max constraint** (`@psplotmaxconstr`) option in the **Plot** pane to plot the maximum nonlinear constraint violation at each generation
- Updated **Poll method** and **Search method** options for selecting the GPS or MADS algorithms
- New **Algorithm settings** panel for selecting algorithm specific parameters, such as the penalty parameters, **Initial penalty** and **Penalty factor**, for a nonlinear constraint algorithm
- New **Time limit** and **Nonlinear constraint tolerance** parameters in **Stopping criteria**

New Demos

The Genetic Algorithm and Direct Search Toolbox contains the following new demos for Version 2.0:

- Optimization of Non-smooth Objective Function
- Constrained Minimization Using the Genetic Algorithm

- Constrained Minimization Using the Pattern Search
- Optimization of Stochastic Objective Function
- Using the Genetic Algorithm and Direct Search Toolbox