


Image Processing Toolbox™

Reference



MATLAB®

R2016a

 MathWorks®

How to Contact MathWorks



Latest news: www.mathworks.com
Sales and services: www.mathworks.com/sales_and_services
User community: www.mathworks.com/matlabcentral
Technical support: www.mathworks.com/support/contact_us



Phone: 508-647-7000



The MathWorks, Inc.
3 Apple Hill Drive
Natick, MA 01760-2098

Image Processing Toolbox™ Reference

© COPYRIGHT 1993–2016 by The MathWorks, Inc.

The software described in this document is furnished under a license agreement. The software may be used or copied only under the terms of the license agreement. No part of this manual may be photocopied or reproduced in any form without prior written consent from The MathWorks, Inc.

FEDERAL ACQUISITION: This provision applies to all acquisitions of the Program and Documentation by, for, or through the federal government of the United States. By accepting delivery of the Program or Documentation, the government hereby agrees that this software or documentation qualifies as commercial computer software or commercial computer software documentation as such terms are used or defined in FAR 12.212, DFARS Part 227.72, and DFARS 252.227-7014. Accordingly, the terms and conditions of this Agreement and only those rights specified in this Agreement, shall pertain to and govern the use, modification, reproduction, release, performance, display, and disclosure of the Program and Documentation by the federal government (or other entity acquiring for or through the federal government) and shall supersede any conflicting contractual terms or conditions. If this License fails to meet the government's needs or is inconsistent in any respect with federal procurement law, the government agrees to return the Program and Documentation, unused, to The MathWorks, Inc.

Trademarks

MATLAB and Simulink are registered trademarks of The MathWorks, Inc. See www.mathworks.com/trademarks for a list of additional trademarks. Other product or brand names may be trademarks or registered trademarks of their respective holders.

Patents

MathWorks products are protected by one or more U.S. patents. Please see www.mathworks.com/patents for more information.

Revision History

August 1993	First printing	Version 1
May 1997	Second printing	Version 2
April 2001	Third printing	Revised for Version 3.0
June 2001	Online only	Revised for Version 3.1 (Release 12.1)
July 2002	Online only	Revised for Version 3.2 (Release 13)
May 2003	Fourth printing	Revised for Version 4.0 (Release 13.0.1)
September 2003	Online only	Revised for Version 4.1 (Release 13.SP1)
June 2004	Online only	Revised for Version 4.2 (Release 14)
August 2004	Online only	Revised for Version 5.0 (Release 14+)
October 2004	Fifth printing	Revised for Version 5.0.1 (Release 14SP1)
March 2005	Online only	Revised for Version 5.0.2 (Release 14SP2)
September 2005	Online only	Revised for Version 5.1 (Release 14SP3)
March 2006	Online only	Revised for Version 5.2 (Release 2006a)
September 2006	Online only	Revised for Version 5.3 (Release 2006b)
March 2007	Online only	Revised for Version 5.4 (Release 2007a)
September 2007	Online only	Revised for Version 6.0 (Release 2007b)
March 2008	Online only	Revised for Version 6.1 (Release 2008a)
October 2008	Online only	Revised for Version 6.2 (Release 2008b)
March 2009	Online only	Revised for Version 6.3 (Release 2009a)
September 2009	Online only	Revised for Version 6.4 (Release 2009b)
March 2010	Online only	Revised for Version 7.0 (Release 2010a)
September 2010	Online only	Revised for Version 7.1 (Release 2010b)
April 2011	Online only	Revised for Version 7.2 (Release 2011a)
September 2011	Online only	Revised for Version 7.3 (Release 2011b)
March 2012	Online only	Revised for Version 8.0 (Release 2012a)
September 2012	Online only	Revised for Version 8.1 (Release 2012b)
March 2013	Online only	Revised for Version 8.2 (Release 2013a)
September 2013	Online only	Revised for Version 8.3 (Release 2013b)
March 2014	Online only	Revised for Version 9.0 (Release 2014a)
October 2014	Online only	Revised for Version 9.1 (Release 2014b)
March 2015	Online only	Revised for Version 9.2 (Release 2015a)
September 2015	Online only	Revised for Version 9.3 (Release 2015b)
March 2016	Online only	Revised for Version 9.4 (Release 2016a)

1	Functions — Alphabetical List
----------	--------------------------------------

Functions — Alphabetical List

Image Batch Processor

Process folder of images

Description

The Image Batch Processor app lets you process a folder of images using a function you specify. The function must have the following signature: `out = fcn(in)`. The app creates an output folder containing the processed images, using the same name and subfolder structure as the input folder.

Open the Image Batch Processor App

- MATLAB® Toolstrip: Open the Apps tab, under **Image Processing and Computer Vision**, click the app icon.
- MATLAB command prompt: Enter `imageBatchProcessor`.

Examples

- “Batch Processing Using the Image Batch Processor App”

Programmatic Use

`imageBatchProcessor` opens the Image Batch Processor app, which enables you to process a folder of images.

`imageBatchProcessor close` closes all open instances of the Image Batch Processor app.

See Also

Functions

`imread` | `imwrite`

Introduced in R2015a

Color Thresholder

Threshold color image

Description

The **Color Thresholder** app lets you threshold color images by manipulating the color components of these images, based on different color spaces. Using this app, you can create a segmentation mask for a color image.

Open the Color Thresholder App

- MATLAB Toolstrip: Open the Apps tab, under **Image Processing and Computer Vision**, click the app icon.
- MATLAB command prompt: Enter `colorThresholder`.

Examples

- “Image Segmentation Using the Color Thresholder App”

Programmatic Use

`colorThresholder` opens the Color Thresholder app, which enables you to create a segmentation mask of a color image based on the exploration of different color spaces.

`colorThresholder(I)` opens the Color Thresholder app, loading the image `I` into the app.

`colorThresholder close` closes all open instances of the Color Thresholder app.

See Also

Apps

Image Segmenter

Functions

`imcontrast`

Introduced in R2014a

Image Segmenter

Segment image using active contours algorithm

Description

The Image Segmenter app lets you segment an image using the active contours algorithm. Using this app, you first create an initial segmentation that defines seed locations and then segment the image iteratively.

Open the Image Segmenter App

- MATLAB Toolstrip: Open the Apps tab, under **Image Processing and Computer Vision**, click the app icon.
- MATLAB command prompt: Enter `imageSegmenter`.

Examples

- “Image Segmentation Using the Image Segmenter App”

Programmatic Use

`imageSegmenter` opens the Image Segmenter app, which enables you to create a segmentation mask of an image by using active contours.

`imageSegmenter(I)` opens the Image Segmenter app, loading the image `I` into the app.

`imageSegmenter close` closes all open instances of the Image Segmenter app.

See Also

Functions

`activecontour`

Introduced in R2014b

Image Region Analyzer

Explore and filter regions in binary image

Description

The Image Region Analyzer app measures a set of properties for each connected component (also called an object or region) in a binary image and displays this information in a table. You can also use this app to create other binary images by filtering the image on region properties.

Open the Image Region Analyzer App

- MATLAB Toolstrip: Open the Apps tab, under **Image Processing and Computer Vision**, click the app icon.
- MATLAB command prompt: Enter `imageRegionAnalyzer`

Examples

- “Calculate Region Properties Using Image Region Analyzer”
- “Filter Images on Region Properties Using Image Region Analyzer App”

Programmatic Use

`imageRegionAnalyzer` opens the Image Region Analyzer app, which enables you to create other binary images and get information about the regions within binary images.

`imageRegionAnalyzer(I)` opens the Image Region Analyzer app, loading the image `I` into the app.

`imageRegionAnalyzer close` closes all open instances of the Image Region Analyzer app.

See Also

Functions

`bwareafilt` | `bwpropfilt` | `regionprops`

Introduced in R2014b

Image Viewer

View and explore images

Description

The Image Viewer app provides image display capabilities as well as access to several tools for navigating and exploring images, and performing some common image processing tasks.

Open the Image Viewer App

- MATLAB Toolstrip: Open the Apps tab, under **Image Processing and Computer Vision**, click the app icon.
- MATLAB command prompt: Enter `imtool`.

Examples

- “Explore Images with the Image Viewer App”

Programmatic Use

```
imtool
```

See Also

Apps

Video Viewer

Functions

`imshow`

Introduced in R2014b

Video Viewer

View videos and image sequences

Description

The Video Viewer app plays movies, videos, or image sequences. Using Video Viewer you can select the movie or image sequence that you want to play, jump to a specific frame in the sequence, change the frame rate of the display, or perform other viewing activities.

Open the Video Viewer App

- MATLAB Toolstrip: Open the Apps tab, under **Image Processing and Computer Vision**, click the app icon.
- MATLAB command prompt: Enter `implay`.

Examples

- “View Image Sequences in Video Viewer App”

Programmatic Use

```
implay
```

See Also

Apps

Image Viewer

Functions

```
implay
```

Introduced in R2014b

activecontour

Segment image into foreground and background using active contour

Syntax

```
bw = activecontour(A,mask)
bw = activecontour(A,mask,n)
bw = activecontour(A,mask,method)
bw = activecontour(A,mask,n,method)
bw = activecontour( ____,Name,Value)
```

Description

`bw = activecontour(A,mask)` segments the 2-D grayscale image `A` into foreground (object) and background regions using active contour based segmentation. The output image `bw` is a binary image where the foreground is white (logical true) and the background is black (logical false). `mask` is a binary image that specifies the initial state of the active contour. The boundaries of the object region(s) (white) in `mask` define the initial contour position used for contour evolution to segment the image. To obtain faster and more accurate segmentation results, specify an initial contour position that is close to the desired object boundaries.

`bw = activecontour(A,mask,n)` segments the image by evolving the contour for a maximum of `n` iterations.

`bw = activecontour(A,mask,method)` specifies the active contour method used for segmentation, either 'Chan-Vese' or 'edge'.

`bw = activecontour(A,mask,n,method)` segments the image by evolving the contour for a maximum of `n` iterations using the specified `method`.


`bw = activecontour(____,Name,Value)` specifies parameters that control various aspects of the segmentation. Parameter names can be abbreviated, and case does not matter.

Examples

Segment an Image Specifying the Mask


Read image and display it.

```
I = imread('coins.png');  
imshow(I)  
title('Original Image');
```



Specify initial contour and display it.


```
mask = zeros(size(I));  
mask(25:end-25,25:end-25) = 1;  
  
figure, imshow(mask);  
title('Initial Contour Location');
```



Segment the image using the default method and 300 iterations.

```
bw = activecontour(I,mask,300);
```

```
figure, imshow(bw);  
title('Segmented Image');
```



Segment Image Overlaying Mask and Contour on Original Image

Read image and display it.

```
I = imread('toyobjects.png');  
imshow(I)  
hold on  
title('Original Image');
```

Original Image




Specify initial contour location close to the object that is to be segmented.

```
mask = false(size(I));  
mask(50:150,40:170) = true;
```

Display the initial contour on the original image in blue.

```
visboundaries(mask, 'Color', 'b');
```

Original Image



Segment the image using the 'edge' method and 200 iterations.

```
bw = activecontour(I, mask, 200, 'edge');
```

Display the final contour on the original image in red.


```
visboundaries(bw, 'Color', 'r');  
title('Initial contour (blue) and final contour (red)');
```

Initial contour (blue) and final contour (red)



Display segmented image.

```
figure, imshow(bw)
title('Segmented Image');
```

Segmented Image


Segment an Image Specifying a Polygonal Mask Created Interactively

Read image and display it, along with instructions to specify initial contour location.

```
I = imread('toyobjects.png');  
imshow(I)
```


```
str = 'Click to select initial contour location. Double-click to confirm and proceed.'  
title(str, 'Color', 'b', 'FontSize', 12);  
disp(sprintf('\nNote: Click close to object boundaries for more accurate result.'))
```

Click to select initial contour location. Double-click to confirm and proceed.




Specify initial contour interactively.

```
mask = roipoly;  
  
figure, imshow(mask)  
title('Initial MASK');
```

Segment the image, specifying 200 iterations.

```
maxIterations = 200;  
bw = activecontour(I, mask, maxIterations, 'Chan-Vese');  
  
% Display segmented image  
figure, imshow(bw)  
title('Segmented Image');
```



Input Arguments

A — Image to be segmented

grayscale image

Image to segmented, specified as a grayscale image. Must be non-sparse.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

mask — Initial contour at which the evolution of the segmentation begins

binary image

Initial contour at which the evolution of the segmentation begins, specified as a binary image the same size as `A`.

Data Types: `logical`

n — Maximum number of iterations to perform in evolution of the segmentation

100 (default) | numeric scalar.

Maximum number of iterations to perform in evolution of the segmentation, specified as a numeric scalar. `activecontour` stops the evolution of the active contour if the contour position in the current iteration is the same as one of the contour positions from the most recent five iterations, or if the maximum number of iterations is reached.

You might need to specify higher values of `n` to achieve desired segmentation results if the initial contour position (specified by the region boundaries in `mask`) is far from the desired object boundaries.

Data Types: `double`

method — Active contour method used for segmentation

'Chan-Vese' (default) | 'edge'

Active contour method used for segmentation, specified as the character string 'Chan-Vese' or 'edge'. The Chan and Vese's region-based energy model is described in [1]. The edge-based model, similar to Geodesic Active Contour, is described in [2].

Data Types: `char`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

Example: `bw = activecontour(I, mask, 200, 'edge', 'SmoothFactor', 1.5);`

'SmoothFactor' — Degree of smoothness or regularity of the boundaries of the segmented regions

0, for 'Chan-Vese'; 1 for 'edge' (default) | positive numeric scalar

Degree of smoothness or regularity of the boundaries of the segmented regions, specified as a positive numeric scalar. Higher values produce smoother region boundaries but can

also smooth out finer details. Lower values produce more irregularities (less smoothing) in the region boundaries but allow finer details to be captured. The default smoothness value depends on the method chosen.

```
Example: bw = activecontour(I, mask, 200, 'edge', 'SmoothFactor', 1.5);
```

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

'ContractionBias' — Tendency of the contour to grow outwards or shrink inwards

0, for 'Chan-Vese'; 0.3 for 'edge' (default) | scalar

Tendency of the contour to grow outwards or shrink inwards, specified as a scalar. Positive values bias the contour to shrink inwards (contract). Negative values bias the contour to grow outwards (expand). Note that this parameter does not guarantee that the contour will contract (or expand) strictly. It is possible that even with a positive value for this parameter, the contour could actually expand (or vice-versa). However, since you specified a bias, the expansion will be slower than an unbiased contour.

```
Example: bw = activecontour(I, mask, 200,  
'edge', 'ContractionBias', 0.4);
```

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

Output Arguments

bw — Segmented image

binary image the same size as the input image A.

Segmented image, returned as a binary image the same size as the input image A. The foreground is white (logical true) and the background is black (logical false).

More About

Tips

- `activecontour` uses the boundaries of the regions in `mask` as the initial state of the contour from where the evolution starts. If `mask` has regions with holes, unpredictable results may be seen. Use `imfill` to fill any holes in the regions in `mask`.
- The regions in `mask` should not touch the image borders. If a region touches the image border(s), `activecontour` removes a single-pixel layer from the region so that the region does not touch the image border before further processing.

- To get faster and more accurate results, specify an initial contour position that is close to the desired object boundaries. This is especially true for the 'edge' method.
- For the 'edge' method, the active contour is naturally biased towards shrinking inwards (collapsing) by default, i.e. in absence of any image gradient, the active contour shrinks on its own. This is unlike the 'Chan-Vese' method where, by default, the contour is unbiased, i.e. free to either shrink or expand based on the image features.
- To achieve an accurate segmentation result with the 'edge' method, the initial contour (specified by region boundaries in `mask`) should lie outside the boundaries of the object to be segmented, because the active contour is biased to shrink by default.
- The 'Chan-Vese' method [1] may not segment all objects in the image, if the various object regions are of significantly different grayscale intensities. For example, if the image has some objects that are brighter than the background and some that are darker, the 'Chan-Vese' method typically segments out either the dark or the bright objects only.

Algorithms

`activecontour` uses the Sparse-Field level-set method, similar to the method described in [3], for implementing active contour evolution.

`activecontour` stops the evolution of the active contour if the contour position in the current iteration is the same as one of the contour positions from the most recent five iterations, or if the maximum number of iterations has been reached.

References

- [1] T. F. Chan, L. A. Vese, *Active contours without edges*. IEEE Transactions on Image Processing, Volume 10, Issue 2, pp. 266-277, 2001
- [2] V. Caselles, R. Kimmel, G. Sapiro, *Geodesic active contours*. International Journal of Computer Vision, Volume 22, Issue 1, pp. 61-79, 1997.
- [3] R. T. Whitaker, *A level-set approach to 3d reconstruction from range data*. International Journal of Computer Vision, Volume 29, Issue 3, pp.203-231, 1998.

See Also

`imellipse` | `imfreehand` | `multithresh` | `poly2mask` | `roipoly`

Introduced in R2013a

adaphisteq

Contrast-limited adaptive histogram equalization (CLAHE)

Syntax

```
J = adaphisteq(I)
J = adaphisteq(I,param1,val1,param2,val2...)
```

Description

`J = adaphisteq(I)` enhances the contrast of the grayscale image `I` by transforming the values using contrast-limited adaptive histogram equalization (CLAHE).

CLAHE operates on small regions in the image, called *tiles*, rather than the entire image. Each tile's contrast is enhanced, so that the histogram of the output region approximately matches the histogram specified by the 'Distribution' parameter. The neighboring tiles are then combined using bilinear interpolation to eliminate artificially induced boundaries. The contrast, especially in homogeneous areas, can be limited to avoid amplifying any noise that might be present in the image.

`J = adaphisteq(I,param1,val1,param2,val2...)` specifies any of the additional parameter/value pairs listed in the following table. Parameter names can be abbreviated, and case does not matter.

Parameter	Value
'NumTiles'	Two-element vector of positive integers specifying the number of tiles by row and column, [M N]. Both M and N must be at least 2. The total number of tiles is equal to M*N. Default: [8 8]
'ClipLimit'	Real scalar in the range [0 1] that specifies a contrast enhancement limit. Higher numbers result in more contrast. Default: 0.01

Parameter	Value
'NBins'	<p>Positive integer scalar specifying the number of bins for the histogram used in building a contrast enhancing transformation. Higher values result in greater dynamic range at the cost of slower processing speed.</p> <p>Default: 256</p>
'Range'	<p>String specifying the range of the output image data.</p> <p>'original' — Range is limited to the range of the original image, $[\min(I(:)) \max(I(:))]$.</p> <p>'full' — Full range of the output image class is used. For example, for <code>uint8</code> data, range is <code>[0 255]</code>.</p> <p>Default: 'full'</p>
'Distribution'	<p>String specifying the desired histogram shape for the image tiles.</p> <p>'uniform' — Flat histogram</p> <p>'rayleigh' — Bell-shaped histogram</p> <p>'exponential' — Curved histogram</p> <p>Default: 'uniform'</p>
'Alpha'	<p>Nonnegative real scalar specifying a distribution parameter.</p> <p>Default: 0.4</p> <hr/> <p>Note: Only used when 'Distribution' is set to either 'rayleigh' or 'exponential'.</p>

Class Support

Grayscale image *I* can be of class `uint8`, `uint16`, `int16`, `single`, or `double`. The output image *J* has the same class as *I*.

Examples

Apply Contrast-limited Adaptive Histogram Equalization (CLAHE)

Apply Contrast-limited Adaptive Histogram Equalization (CLAHE) to an image and display the results.

```
I = imread('tire.tif');  
A = adapthisteq(I, 'clipLimit', 0.02, 'Distribution', 'rayleigh');  
figure, imshow(I);  
figure, imshow(A);
```





Apply CLAHE to a color image

Read the color image into the workspace.

```
[X MAP] = imread('shadow.tif');
```

Convert the indexed image into a truecolor (RGB) image.

```
RGB = ind2rgb(X,MAP);
```

Convert the RGB image into the L*a*b* color space.

```
cform2lab = makecform('srgb2lab');  
LAB = applycform(RGB, cform2lab);
```

Scale values to range from 0 to 1.

```
L = LAB(:,:,1)/100;
```

Perform CLAHE.

```
LAB(:,:,1) = adapthisteq(L, 'NumTiles', ...
```

```
[8 8], 'ClipLimit', 0.005)*100;
```

Convert the resultant image back into the RGB color space.

```
cform2srgb = makecform('lab2srgb');  
J = applycform(LAB, cform2srgb);
```

Display the original image and result.

```
figure, imshow(IMG);  
figure, imshow(J);
```





More About

Tips

- 'NumTiles' specifies the number of rectangular contextual regions (tiles) into which `adapthisteq` divides the image. `adapthisteq` calculates the contrast transform function for each of these regions individually. The optimal number of tiles depends on the type of the input image, and it is best determined through experimentation.
- 'ClipLimit' is a contrast factor that prevents over-saturation of the image specifically in homogeneous areas. These areas are characterized by a high peak in the histogram of the particular image tile due to many pixels falling inside the same gray level range. Without the clip limit, the adaptive histogram equalization technique could produce results that, in some cases, are worse than the original image.
- 'Distribution' specifies the distribution that `adapthisteq` uses as the basis for creating the contrast transform function. The distribution you select should depend on

the type of the input image. For example, underwater imagery appears to look more natural when the Rayleigh distribution is used.

References

- [1] Zuiderveld, Karel. “Contrast Limited Adaptive Histogram Equalization.” *Graphic Gems IV*. San Diego: Academic Press Professional, 1994. 474–485.

See Also

histeq

Introduced before R2006a

adaptthresh

Adaptive image threshold using local first-order statistics

Syntax

```
T = adaptthresh(I)
T = adaptthresh(I,sensitivity)
T = adaptthresh( ____,Name,Value)
```

Description

`T = adaptthresh(I)` computes a locally adaptive threshold that can be used with the `imbinarize` function to convert an intensity image to a binary image. The result, `T`, is a matrix the same size as `I` containing normalized intensity values in the range `[0, 1]`. `adaptthresh` chooses the threshold based on the local mean intensity (first-order statistics) in the neighborhood of each pixel.

`T = adaptthresh(I,sensitivity)` computes a locally adaptive threshold with sensitivity factor specified by `sensitivity`. `sensitivity` is a scalar in the range `[0 1]` that indicates sensitivity towards thresholding more pixels as foreground.

`T = adaptthresh(____,Name,Value)` computes a locally adaptive threshold using name-value pairs to control aspects of the thresholding.

“Code Generation” on page 1-37 support: Yes.

“MATLAB Function Block” on page 1-37 support: Yes.

Examples

Find Threshold and Segment Bright Rice Grains from Dark Background

Read image into the workspace.

```
I = imread('rice.png');
```

Use `adapthresh` to determine threshold to use in binarization operation.


```
T = adapthresh(I, 0.4);
```

Convert image to binary image, specifying the threshold value.

```
BW = imbinarize(I,T);
```

Display the original image with the binary version, side-by-side.

```
figure  
imshowpair(I, BW, 'montage')
```



Find Threshold and Segment Dark Text from Bright Background

Read image into the workspace.

```
I = imread('printedtext.png');
```

Using `adapthresh` compute adaptive threshold and display the local threshold image. This represents an estimate of average background illumination.

```
T = adapttthresh(I,0.4,'ForegroundPolarity','dark');  
figure  
imshow(T)
```



Binarize image using locally adaptive threshold

```
BW = imbinarize(I,T);  
figure  
imshow(BW)
```


What Is Image Filtering in the Spatial Domain?

Filtering is a technique for modifying or enhancing an image. For example, you can filter an image to emphasize certain features or remove other features. Image processing operations implemented with filtering include smoothing, sharpening, and edge enhancement.

Filtering is a *neighborhood operation*, in which the value of any given pixel in the output image is determined by applying some algorithm to the values of the pixels in the neighborhood of the corresponding input pixel. A pixel's neighborhood is some set of pixels, defined by their locations relative to that pixel. (See Neighborhood or Block Processing: An Overview for a general discussion of neighborhood operations.) *Linear filtering* is filtering in which the value of an output pixel is a linear combination of the values of the pixels in the input pixel's neighborhood.

Convolution

Linear filtering of an image is accomplished through an operation called *convolution*. Convolution is a neighborhood operation in which each output pixel is the weighted sum of neighboring input pixels. The matrix of weights is called the *convolution kernel*, also known as the *filter*. A convolution kernel is a correlation kernel that has been rotated 180 degrees.

For example, suppose the image is

```
A = [17 24  1  8 15
      23  5  7 14 16
        4  6 13 20 22
       10 12 19 21  3
       11 10  7  5  4]
```

Input Arguments

I — Input intensity image

real, nonsparse 2-D matrix

Input intensity image, specified as a real, nonsparse, 2-D matrix. If the image contains Infs or NaNs, the behavior of `adapthresh` is undefined. Propagation of Infs or NaNs may not be localized to the neighborhood around Inf or NaN pixels.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

sensitivity — Determine which pixels get thresholded as foreground pixels

0.5 (default) | real, nonnegative numeric scalar in the range [0 1]

Determine which pixels get thresholded as foreground pixels, specified as a real, nonnegative numeric scalar in the range [0 1]. High sensitivity values lead to thresholding more pixels as foreground, at the risk of including some background pixels.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

Example: `T = adaptthresh(I,0.4,'ForegroundPolarity','dark');`

'**NeighborhoodSize**' — Size of neighborhood used to compute local statistic around each pixel

`2*floor(size(I)/16)+1` (default) | real, numeric scalar or two-element vector of positive odd integers

Size of neighborhood used to compute local statistic around each pixel, specified as a real, numeric, scalar or two-element vector of positive odd integers.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

'**ForegroundPolarity**' — Determine which pixels are considered foreground pixels

'bright' (default) | 'dark'

Determine which pixels are considered foreground pixels, specified using either of the following strings.

String	Meaning
'bright'	The foreground is brighter than the background. This is the default.
'dark'	The foreground is darker than the background

Data Types: `char`

'**Statistic**' — Statistic used to compute local threshold at each pixel

'mean' (default) | 'median' | 'gaussian'

Statistic used to compute local threshold at each pixel, specified as one of the following strings.

String	Meaning
'mean'	The local mean intensity in the neighborhood. This is the default. This technique is also called Bradley's method.
'median'	The local median in the neighborhood. Computation of this statistic can be slow. Consider using a smaller neighborhood size to obtain faster results.
'gaussian'	The Gaussian weighted mean in the neighborhood.

Data Types: char

Output Arguments

T — Normalized intensity values

double matrix

Normalized intensity values, returned as a **double** matrix the same size as I.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder™. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, note the following:

- The **ForegroundPolarity** and **Statistic** arguments must be compile-time constants

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

When using the MATLAB Function Block, note the following:

- The parameter `NeighborhoodSize` must be a compile-time constant.

See Also

`graythresh` | `imbinarize` | `otsuthresh`

Introduced in R2016a

affine2d class

2-D Affine Geometric Transformation

Description

An `affine2d` object encapsulates a 2-D affine geometric transformation.

“Code Generation” on page 1-43 support: Yes.

“MATLAB Function Block” on page 1-43 support: Yes.

Construction

`tform = affine2d()` creates an `affine2d` object with default property settings that correspond to the identity transformation.

`tform = affine2d(A)` creates an `affine2d` object given an input 3-by-3 matrix `A` that specifies a valid affine transformation.

Input Arguments

A

3-by-3 matrix that specifies a valid affine transformation of the form:

```
A = [a b 0;  
     c d 0;  
     e f 1];
```

Default: Identity transformation

Properties

T

3-by-3 double-precision, floating point matrix that defines the 2-D forward affine transformation

The matrix T uses the convention:

$$[x \ y \ 1] = [u \ v \ 1] * T$$

where T has the form:

$$\begin{bmatrix} a & b & 0; \\ c & d & 0; \\ e & f & 1 \end{bmatrix};$$

Dimensionality

Describes the dimensionality of the geometric transformation for both input and output points

Methods

invert	Invert geometric transformation
outputLimits	Find output spatial limits given input spatial limits
transformPointsForward	Apply forward geometric transformation
transformPointsInverse	Apply inverse geometric transformation
isRigid	Determine if transformation is rigid transformation
isTranslation	Determine if transformation is pure translation
isSimilarity	Determine if transformation is similarity transformation

Copy Semantics

Value. To learn how value classes affect copy operations, see Copying Objects in the MATLAB documentation.

Examples

Define 10-Degree Rotation in the Counter-Clockwise Direction

Create an `affine2d` object that defines the transformation.

```
theta = 10;
tform = affine2d([cosd(theta) -sind(theta) 0; sind(theta) cosd(theta) 0; 0 0 1])
tform =
    affine2d with properties:
        T: [3x3 double]
        Dimensionality: 2
```

Apply forward geometric transformation to an input (U,V) point (5,10).

```
[X,Y] = transformPointsForward(tform,5,10)
```

```
X =
    6.6605
```

```
Y =
    8.9798
```

Apply inverse geometric transformation to output (X,Y) point from the previous step to recover the original points from the inverse transformation.

```
[U,V] = transformPointsInverse(tform,X,Y)
```

```
U =
    5.0000
```

```
V =
```

10

Apply 10-Degree Counter-Clockwise rotation to Image Using `imwarp` Function

Read image.

```
A = imread('pout.tif');
```

Create an `affine2d` object that defines the transformation.

```
theta = 10;
```

```
tform = affine2d([cosd(theta) -sind(theta) 0; sind(theta) cosd(theta) 0; 0 0 1])
```


```
tform =
```

```
affine2d with properties:
```

```
          T: [3x3 double]  
Dimensionality: 2
```

Apply geometric transformation to image.

```
outputImage = imwarp(A,tform);  
figure, imshow(outputImage);
```

Additional Capabilities

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, you can only specify singular objects—arrays of objects are not supported.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`affine3d` | `projective2d` | `imwarp`

invert

Class: `affine2d`

Invert geometric transformation

Syntax

```
invtfom = invert(tform)
```

Description

`invtfom = invert(tform)` returns the inverse of the geometric transformation `tform`.

Input Arguments

tform

Geometric transformation, specified as an `affine2d` geometric transformation object.

Output Arguments

invtfom

Inverse of the geometric transformation, returned as an `affine2d` geometric transformation object

Examples

Invert Geometric Transformation Object

Create an `affine2d` object that defines a rotation of 10 degrees counter-clockwise.

```
theta = 10;  
tform = affine2d([cosd(theta) -sind(theta) 0; sind(theta) cosd(theta) 0; 0 0 1]);
```

```
tform =
```

```
    affine2d with properties:
```

```
                T: [3x3 double]  
    Dimensionality: 2
```

Invert the geometric transformation.

```
invtform = invert(tform)
```

```
invtform =
```

```
    affine2d with properties:
```

```
                T: [3x3 double]  
    Dimensionality: 2
```

outputLimits

Class: affine2d

Find output spatial limits given input spatial limits

Syntax

```
[xLimitsOut,yLimitsOut] = outputLimits(tform,xLimitsIn,yLimitsIn)
```

Description

`[xLimitsOut,yLimitsOut] = outputLimits(tform,xLimitsIn,yLimitsIn)` estimates the output spatial limits corresponding to a given geometric transformation, `tform`, and a set of input spatial limits, `xLimitsIn` and `yLimitsIn`.

Input Arguments

tform

Geometric transformation, specified as an `affine2d` geometric transformation object.

xLimitsIn

Input spatial limits in X dimension, specified as a two-element vector of doubles.

yLimitsIn

Input spatial limits in Y dimension, specified as a two-element vector of doubles.

Output Arguments

xLimitsOut

Output spatial limits in X dimension, returned as a two-element vector of doubles.

yLimitsOut

Output spatial limits in Y dimension, returned as a two-element vector of **doubles**.

Examples

Estimate the Output Limits for a Geometric Transformation

Create an `affine2d` object that defines a rotation of 10 degrees counter-clockwise.

```
theta = 10;  
tform = affine2d([cosd(theta) -sind(theta) 0; sind(theta) cosd(theta) 0; 0 0 1]);  
tform =
```

```
    affine2d with properties:
```

```
          T: [3x3 double]  
    Dimensionality: 2
```

Estimate the output spatial limits, given the geometric transformation.

```
[xlim ylim] = outputLimits(tform,[1 240],[1 291])
```

```
xlim =
```

```
    1.1585    286.8855
```

```
ylim =
```

```
   -40.6908    286.4054
```

transformPointsForward

Class: affine2d

Apply forward geometric transformation

Syntax

```
[x,y] = transformPointsForward(tform,u,v)  
X = transformPointsForward(tform,U)
```

Description

`[x,y] = transformPointsForward(tform,u,v)` applies the forward geometric transformation of `tform` to the input 2-D point arrays `u` and `v` and outputs the point arrays `x` and `y`. The input point arrays `u` and `v` must be of the same size.

`X = transformPointsForward(tform,U)` applies the forward geometric transformation of `tform` to the input n -by-2 point matrix `U` and outputs the n -by-2 point matrix `X`. `transformPointsForward` maps the point `U(k, :)` to the point `X(k, :)`.

Input Arguments

tform

Geometric transformation, specified as an `affine2d` geometric transformation object.

u

Coordinates in X dimension of points to be transformed, specified as an array.

v

Coordinates in Y dimension of points to be transformed, specified as an array.

U

X and Y coordinates of points to be transformed, specified as an n -by-2 matrix

Output Arguments

x

Transformed coordinates in X dimension, returned as a array.

y

Transformed coordinates in Y dimension, returned as a array.

X

Transformed points in X and Y dimensions, returned as an n -by-2 point matrix

Examples

Apply Forward Geometric Transformation

Create an `affine2d` object that defines the transformation.

```
theta = 10;
```

```
tform = affine2d([cosd(theta) -sind(theta) 0; sind(theta) cosd(theta) 0; 0 0 1])
```

```
tform =
```

```
    affine2d with properties:
```

```
                T: [3x3 double]
    Dimensionality: 2
```

Apply forward geometric transformation to an input (U,V) point.

```
[X,Y] = transformPointsForward(tform,5,10)
```

```
X =
```

```
    6.6605
```

```
Y =
```


8.9798

transformPointsInverse

Class: affine2d

Apply inverse geometric transformation

Syntax

```
[u,v] = transformPointsInverse(tform,x,y)  
U = transformPointsInverse(tform,X)
```

Description

`[u,v] = transformPointsInverse(tform,x,y)` applies the inverse geometric transformation of `tform` to the input 2-D point arrays `x` and `y` and outputs the point arrays `u` and `v`. The input point arrays `x` and `y` must be of the same size.

`U = transformPointsInverse(tform,X)` applies the inverse geometric transformation of `tform` to the input n -by-2 point matrix `X` and outputs the n -by-2 point matrix `U`. `transformPointsInverse` maps the point `X(k, :)` to the point `U(k, :)`.

Input Arguments

tform

Geometric transformation, specified as an `affine2d` geometric transformation object.

Default:

x

Coordinates in X dimension of points to be transformed, specified as a array.

y

Coordinates in Y dimension of points to be transformed, specified as a array.

X

X and Y coordinates of points to be transformed, specified as an n -by-2 matrix

Output Arguments

u

Transformed coordinates in X dimension, returned as an array.

v

Transformed coordinates in Y dimension, returned as an array.

U

Transformed X and Y coordinates, returned as an n -by-2 matrix

Examples

Apply Inverse Geometric Transformation

Create an `affine2d` object that defines the transformation.

```
theta = 10;
```

```
tform = affine2d([cosd(theta) -sind(theta) 0; sind(theta) cosd(theta) 0; 0 0 1])
```

```
tform =
```

```
    affine2d with properties:
```

```
                T: [3x3 double]
    Dimensionality: 2
```

Apply forward geometric transformation to an input point.

```
[X,Y] = transformPointsForward(tform,5,10)
```

```
X =
```

6.6605

Y =

8.9798

Apply inverse geometric transformation to output point from the previous step to recover the original coordinates.

```
[U,V] = transformPointsInverse(tform,X,Y)
```

U =

5.0000

V =

10

isRigid

Class: affine2d

Determine if transformation is rigid transformation

Syntax

```
TF = isRigid(tform)
```

Description

`TF = isRigid(tform)` determines whether or not the affine transformation specified by `tform` is a rigid transformation. `TF` is a scalar boolean that is true when `tform` is a rigid transformation. A `tform` is a rigid transformation when `tform.T` defines only rotation and translation.

Input Arguments

tform

Geometric transformation, specified as an `affine2d` geometric transformation object.

Output Arguments

TF

Scalar boolean, returned as `true` when the `tform` is a rigid transformation.

Examples

Check if transformation is rigid

Create an `affine2d` object that defines a pure translation.

```
A = [ 1  0  0  
      0  1  0  
      40 40  1 ];
```

```
tform = affine2d(A)
```

```
tform =
```

```
    affine2d with properties:
```

```
                T: [3x3 double]  
    Dimensionality: 2
```

Test if it is a rigid transformation.

```
tf = isRigid(tform)
```

```
tf =
```

```
    1
```

isTranslation

Class: affine2d

Determine if transformation is pure translation

Syntax

```
TF = isTranslation(tform)
```

Description

`TF = isTranslation(tform)` determines whether the affine transformation specified in `tform` is a pure translation transformation. `TF` is a scalar boolean that is true when `tform` defines only translation.

Input Arguments

tform

Geometric transformation, specified as an `affine2d` geometric transformation object.

Output Arguments

TF

Scalar boolean, returned as `true` when the `tform` is a pure translation.

Examples

Check if transformation is a pure translation

Create an `affine2d` object that defines a pure translation.

```
A = [ 1  0  0
      0  1  0
      40 40  1 ];
```

```
tform = affine2d(A)
```

```
tform =
```

```
    affine2d with properties:
```

```
                T: [3x3 double]
    Dimensionality: 2
```

Check if transformation is a pure translation.

```
tf = isTranslation(tform)
```

```
tf =
```

```
    1
```


isSimilarity

Class: affine2d

Determine if transformation is similarity transformation

Syntax

```
TF = isSimilarity(tform)
```

Description

`TF = isSimilarity(tform)` determines whether or not the affine transformation specified by `tform` is a similarity transformation. `TF` is a scalar boolean that is true when `tform` is a similarity transformation. A `tform` is a similarity transformation when it defines only homogeneous scale, rotation, and translation.

Input Arguments

tform

Geometric transformation, specified as an `affine2d` geometric transformation object.

Output Arguments

TF

Scalar boolean, returned as `true` when the `tform` is a similarity transformation.

Examples

Check if transformation is a similarity transformation

Create an `affine2d` object that defines a pure translation.

```
A = [ 1  0  0
      0  1  0
      40 40  1 ];
```

```
tform = affine2d(A)
```

```
tform =
```

```
    affine2d with properties:
```

```
                T: [3x3 double]
    Dimensionality: 2
```

Check if transformation is a similarity transformation.

```
tf = isSimilarity(tform)
```

```
tf =
```

```
    1
```

affine3d class

3-D Affine Geometric Transformation

Description

An `affine3d` object encapsulates a 3-D affine geometric transformation.

Construction

`tform = affine3d()` creates an `affine3d` object with default property settings that correspond to the identity transformation.

`tform = affine3d(A)` constructs an `affine3d` object given an input 4-by-4 matrix `A` that specifies a valid 4-by-4 affine transformation matrix.

Input Arguments

A

A 4-by-4 matrix that specifies a valid affine transformation of the form

$$A = \begin{bmatrix} a & b & c & 0; \\ d & e & f & 0; \\ g & h & i & 0; \\ j & k & l & 1 \end{bmatrix};$$

Default: Identity transformation

Properties

T

4-by-4 double-precision floating point matrix that defines the 3-D forward transformation.

The matrix `T` uses the convention:

$$[x \ y \ z \ 1] = [u \ v \ w \ 1] * T$$

where T has the form:

$$\begin{bmatrix} a & b & c & 0; \\ d & e & f & 0; \\ g & h & i & 0; \\ j & k & l & 1 \end{bmatrix};$$

Default: Identity transformation

Dimensionality

Describes the dimensionality of the geometric transformation for both input and output points.

Methods

invert	Invert geometric transformation
outputLimits	Find output spatial limits given input spatial limits
transformPointsForward	Apply forward geometric transformation
transformPointsInverse	Apply inverse 3-D geometric transformation to points
isRigid	Determine if transformation is rigid transformation
isTranslation	Determine if transformation is pure translation
isSimilarity	Determine if transformation is similarity transformation

Copy Semantics

Value. To learn how value classes affect copy operations, see Copying Objects in the MATLAB documentation.

Examples

Define a Different Scale Factor in Each Dimension

Create an `affine3d` object that defines a different scale factor in each dimension.

```
Sx = 1.2;  
Sy = 1.6;  
Sz = 2.4;  
tform = affine3d([Sx 0 0 0; 0 Sy 0 0; 0 0 Sz 0; 0 0 0 1]);
```

```
tform =
```

```
    affine3d with properties:
```

```
        T: [4x4 double]  
    Dimensionality: 3
```

Apply forward geometric transformation to an input point.

```
[X,Y,Z] = transformPointsForward(tform,1,1,1)
```

```
X =
```

```
    1.2000
```

```
Y =
```

```
    1.6000
```

```
Z =
```

```
    2.4000
```

Apply inverse geometric transformation to output points from the previous step to recover the original points from the inverse transformation.

```
[U,V,W] = transformPointsInverse(tform,X,Y,Z)
```

```
U =
```

```
1  
  
V =  
  
1  
  
W =  
  
1
```

Apply Scale Transformation to an MRI Volume Using `imwarp` Function

Load MRI images.

```
A = load('mri');  
A = squeeze(A.D);
```

Create an `affine3d` object that defines a different scale factor in each dimension.

```
Sx = 1.2;  
Sy = 1.6;  
Sz = 2.4;  
tform = affine3d([Sx 0 0 0; 0 Sy 0 0; 0 0 Sz 0; 0 0 0 1]);
```


```
tform =
```

```
affine3d with properties:
```

```
          T: [4x4 double]  
Dimensionality: 3
```

Apply geometric transformation to image using `imwarp` and visualize axial slice through center of transformed volume to see effect of scale transformation.

```
outputImage = imwarp(A,tform);  
figure, imshowpair(A(:,:,14),outputImage(:,:,27));
```



See Also

[affine2d](#) | [projective2d](#) | [imwarp](#)

invert

Class: `affine3d`

Invert geometric transformation

Syntax

```
invtfom = invert(tform)
```

Description

`invtfom = invert(tform)` returns the inverse of the geometric transformation `tform`.

Input Arguments

tform

Geometric transformation, specified as an `affine3d` geometric transformation object.

Output Arguments

invtfom

Inverse of the geometric transformation, returned as an `affine3d` geometric transformation object

Examples

Invert Geometric Transformation Object

Create an `affine3d` object that defines a different scale factor in each dimension.


```
Sx = 1.2;  
Sy = 1.6;  
Sz = 2.4;  
tform = affine3d([Sx 0 0 0; 0 Sy 0 0; 0 0 Sz 0; 0 0 0 1]);
```

```
tform =
```

```
    affine3d with properties:
```

```
                T: [4x4 double]  
    Dimensionality: 3
```

Invert the geometric transformation.

```
invtform = invert(tform)
```

```
invtform =
```

```
    affine3d with properties:
```

```
                T: [4x4 double]  
    Dimensionality: 3
```

outputLimits

Class: affine3d

Find output spatial limits given input spatial limits

Syntax

```
[xLimitsOut,yLimitsOut,zLimitsOut] =  
outputLimits(tform,xLimitsIn,yLimitsIn,zLimitsIn)
```

Description

`[xLimitsOut,yLimitsOut,zLimitsOut] = outputLimits(tform,xLimitsIn,yLimitsIn,zLimitsIn)` estimates the output spatial limits corresponding to a given geometric transformation and a set of input spatial limits.

Input Arguments

tform

Geometric transformation, specified as an `affine3d` geometric transformation object.

xLimitsIn

Input spatial limits in X dimension, specified as a two-element vector of doubles.

yLimitsIn

Input spatial limits in Y dimension, specified as a two-element vector of doubles.

zLimitsIn

Input spatial limits in Z dimension, specified as a two-element vector of doubles.

Output Arguments

xLimitsOut

Output spatial limits in X dimension, returned as a two-element vector of doubles.

yLimitsOut

Output spatial limits in Y dimension, returned as a two-element vector of doubles.

zLimitsOut

Output spatial limits in Z dimension, returned as a two-element vector of doubles.

Examples

Estimate the Output Limits for a Geometric Transformation

Create an `affine3d` object that defines a different scale factor in each dimension.

```
Sx = 1.2;
Sy = 1.6;
Sz = 2.4;
tform = affine3d([Sx 0 0 0; 0 Sy 0 0; 0 0 Sz 0; 0 0 0 1]);
```

```
tform =
```

```
    affine3d with properties:
```

```
          T: [4x4 double]
    Dimensionality: 3
```

Estimate the output spatial limits, given the geometric transformation.

```
[xlim ylim zlim] = outputLimits(tform,[1 128],[1 128],[1 27])
```

```
xlim =
```

```
    1.2000  153.6000
```

```
ylim =
```

1.6000 204.8000

zlim =

2.4000 64.8000

transformPointsForward

Class: affine3d

Apply forward geometric transformation

Syntax

```
[x,y,z] = transformPointsForward(tform,u,v,w)  
X = transformPointsForward(tform,U)
```

Description

`[x,y,z] = transformPointsForward(tform,u,v,w)` applies the forward transformation of `tform` to the input 3-D point arrays `u,v`, and `w` and outputs the point arrays `x,y`, and `z`. The input point arrays `u,v`, and `w` must be of the same size.

`X = transformPointsForward(tform,U)` applies the forward transformation of `tform` to the input n -by-2 point matrix `U` and outputs the n -by-2 point matrix `X`. `transformPointsForward` maps the point `U(k, :)` to the point `X(k, :)`.

Input Arguments

tform

Geometric transformation, specified as an `affine3` geometric transformation object.

u

Coordinates in X dimension of points to be transformed, specified as an array.

v

Coordinates in Y dimension of points to be transformed, specified as an array.

w

Coordinates in Z dimension of points to be transformed, specified as an array.

u

n -by-2 point matrix

Output Arguments

x

Transformed coordinates in X dimension, returned as a array.

y

Transformed coordinates in Y dimension, returned as a array.

z

Transformed coordinates in Z dimension, returned as a array.

X

Transformed points, returned as an n -by-2 point matrix.

Examples

Apply Forward Geometric Transformation

Create an `affine3d` object that defines a different scale factor in each dimension.

```
Sx = 1.2;  
Sy = 1.6;  
Sz = 2.4;  
tform = affine3d([Sx 0 0 0; 0 Sy 0 0; 0 0 Sz 0; 0 0 0 1]);
```

```
tform =
```

```
    affine3d with properties:
```

```
          T: [4x4 double]  
    Dimensionality: 3
```

Apply forward geometric transformation to an input points.

```
[X,Y,Z] = transformPointsForward(tform,5,10,3)
```

```
X =
```

```
6
```

```
Y =
```

```
16
```

```
Z =
```

```
7.2000
```

transformPointsInverse

Class: affine3d

Apply inverse 3-D geometric transformation to points

Syntax

```
[u,v,w] = transformPointsInverse(tform,x,y,z)  
U = transformPointsInverse(tform,X)
```

Description

`[u,v,w] = transformPointsInverse(tform,x,y,z)` applies the inverse transformation of `tform` to the input 3-D point arrays `x`, `y`, and `z` and outputs the point arrays `u`, `v`, and `w`. The input point arrays `x`, `y`, and `z` must be of the same size.

`U = transformPointsInverse(tform,X)` applies the inverse transformation of `tform` to the input n -by-2 point matrix `X` and outputs the n -by-2 point matrix `U`. `transformPointsInverse` maps the point `X(k, :)` to the point `U(k, :)`.

Input Arguments

tform

Geometric transformation `tform`

Default:

x

Coordinates in X dimension of points to be transformed, specified as a array.

y

Coordinates in Y dimension of points to be transformed, specified as a array.

Z

Coordinates in Z dimension of points to be transformed, specified as a array.

X

Coordinates of points to be transformed, specified as an n -by-2 matrix

Output Arguments

u

Transformed coordinates in X dimension, returned as an array.

v

Transformed coordinates in Y dimension, returned as an array.

w

Transformed coordinates in Z dimension, returned as an array.

U

Transformed coordinates, returned as an n -by-2 matrix

Examples

Apply Inverse Geometric Transformation

Create an `affine3d` object that defines a different scale factor in each dimension.

```
Sx = 1.2;  
Sy = 1.6;  
Sz = 2.4;  
tform = affine3d([Sx 0 0 0; 0 Sy 0 0; 0 0 Sz 0; 0 0 0 1]);
```

```
tform =
```

```
    affine3d with properties:
```

```
T: [4x4 double]
Dimensionality: 3
```

Apply forward geometric transformation to an input points.

```
[X,Y,Z] = transformPointsForward(tform,5,10,3)
```

```
X =
```

```
6
```

```
Y =
```

```
16
```

```
Z =
```

```
7.2000
```

Apply inverse geometric transformation to output (X,Y,Z) point from the previous step to recover the original coordinates.

```
[U,V,W] = transformPointsInverse(tform,X,Y,Z)
```

```
U =
```

```
5
```

```
V =
```

```
10
```

```
W =
```

```
3
```

isRigid

Class: affine3d

Determine if transformation is rigid transformation

Syntax

```
TF = isRigid(tform)
```

Description

`TF = isRigid(tform)` determines whether or not the affine transformation specified by `tform` is a rigid transformation. `TF` is a scalar boolean that is true when `tform` is a rigid transformation. A `tform` is a rigid transformation when `tform.T` defines only rotation and translation.

Input Arguments

tform

Geometric transformation, specified as an `affine3d` geometric transformation object.

Output Arguments

TF

Scalar boolean, returned as `true` when the `tform` is a rigid transformation.

Examples

Check if transformation is rigid

Create an `affine3d` object that defines a different scale factor in each dimension.

```
Sx = 1.2;  
Sy = 1.6;  
Sz = 2.4;  
tform = affine3d([Sx 0 0 0; 0 Sy 0 0; 0 0 Sz 0; 0 0 0 1])
```

```
tform =
```

```
    affine3d with properties:
```

```
                T: [4x4 double]  
    Dimensionality: 3
```

Check if the transformation is rigid.

```
TF = isRigid(tform)
```

```
TF =
```

```
    0
```

isTranslation

Class: affine3d

Determine if transformation is pure translation

Syntax

```
TF = isTranslation(tform)
```

Description

`TF = isTranslation(tform)` determines whether affine transformation specified in `tform` is a pure translation transformation. `TF` is a scalar boolean that is true when `tform` defines only translation.

Input Arguments

tform

Geometric transformation, specified as an `affine3d` geometric transformation object.

Output Arguments

TF

Scalar boolean, returned as `true` when the `tform` is a translation.

Examples

Check if transformation is translation

Create an `affine3d` object that defines a different scale factor in each dimension.

```
Sx = 1.2;  
Sy = 1.6;  
Sz = 2.4;  
tform = affine3d([Sx 0 0 0; 0 Sy 0 0; 0 0 Sz 0; 0 0 0 1]);
```

```
tf =
```

```
    affine3d with properties:
```

```
        T: [4x4 double]  
    Dimensionality: 3
```

Check if transformation is a translation.

```
tf = isTranslation(tform)
```

```
tf =
```

```
    0
```

isSimilarity

Class: affine3d

Determine if transformation is similarity transformation

Syntax

```
TF = isSimilarity(tform)
```

Description

`TF = isSimilarity(tform)` determines whether or not the affine transformation specified by `tform` is a similarity transformation. `TF` is a scalar boolean that is true when `tform` is a similarity transformation. A `tform` is a similarity transformation when it defines only homogeneous scale, rotation, and translation.

Input Arguments

tform

Geometric transformation, specified as an `affine3d` geometric transformation object.

Output Arguments

TF

Scalar boolean, returned as `true` when the `tform` is a similarity transformation.

Examples

Check if transformation is a similarity transformation

Create an `affine3d` object that defines a different scale factor in each dimension.

```
Sx = 1.2;  
Sy = 1.6;  
Sz = 2.4;  
tform = affine3d([Sx 0 0 0; 0 Sy 0 0; 0 0 Sz 0; 0 0 0 1])
```

```
tform =
```

```
    affine3d with properties:
```

```
                T: [4x4 double]  
    Dimensionality: 3
```

Check if the transformation is a similarity transformation.

```
TF = isSimilarity(tform)
```

```
TF =
```

```
    0
```


analyze75info

Read metadata from header file of Analyze 7.5 data set

Syntax

```
info = analyze75info(filename)
info = analyze75info(filename, 'ByteOrder', endian)
```

Description

`info = analyze75info(filename)` reads the header file of the Analyze 7.5 data set specified by the string `filename`. The function returns `info`, a structure whose fields contain information about the data set.

Analyze 7.5 is a 3-D biomedical image visualization and analysis product developed by the Biomedical Imaging Resource of the Mayo Clinic. An Analyze 7.5 data set is made of two files, a header file and an image file. The files have the same name with different file extensions. The header file has the file extension `.hdr` and the image file has the file extension `.img`.

`info = analyze75info(filename, 'ByteOrder', endian)` reads the Analyze 7.5 header file using the byte ordering specified by *endian*, where *endian* can have either of the following values:

Value	Meaning
'ieee-le'	Byte ordering is Little Endian
'ieee-be'	Byte ordering is Big Endian

If the specified *endian* value results in a read error, `analyze75info` issues a warning message and attempts to read the header file with the opposite `ByteOrder` format.

Examples

Read an Analyze 7.5 header file.

```
info = analyze75info('brainMRI.hdr');
```

Specify the byte ordering of the data set.

```
info = analyze75info('brainMRI', 'ByteOrder', 'ieee-le');
```

See Also

`analyze75read`

Introduced before R2006a

analyze75read

Read image data from image file of Analyze 7.5 data set

Syntax

```
X = analyze75read(filename)
X = analyze75read(info)
```

Description

`X = analyze75read(filename)` reads the image data from the image file of an Analyze 7.5 format data set specified by the string `filename`. The function returns the image data in `X`. For single-frame, grayscale images, `X` is an m -by- n array. `analyze75read` uses a data type for `X` that is consistent with the data type specified in the data set header file.

Analyze 7.5 is a 3-D biomedical image visualization and analysis product developed by the Biomedical Imaging Resource of the Mayo Clinic. An Analyze 7.5 data set is made of two files, a header file and an image file. The files have the same name with different file extensions. The header file has the file extension `.hdr` and the image file has the file extension `.img`.

`X = analyze75read(info)` reads the image data from the image file specified in the metadata structure `info`. `info` must be a valid metadata structure returned by the `analyze75info` function.

Note `analyze75read` returns image data in radiological orientation (LAS). This is the default used by the Analyze 7.5 format.

Examples

Example 1

Read image data from an Analyze 7.5 image file.

```
X = analyze75read('brainMRI');
```

Because Analyze 7.5 format uses radiological orientation (LAS), flip the data for correct image display in MATLAB.

```
X = flipdim(X,1);
```

Select frames 12 to 17 and use `reshape` to create an array for montage.

```
Y = reshape(X(:,:,12:17),[size(X,1) size(X,2) 1 6]);  
montage(Y);
```

Example 2

Call `analyze75read` with the metadata obtained from the header file using `analyze75info`.

```
info = analyze75info('brainMRI.hdr');  
X = analyze75read(info);
```

Class Support

`X` can be `logical`, `uint8`, `int16`, `int32`, `single`, or `double`. Complex and RGB data types are not supported.

See Also

`analyze75info`

Introduced before R2006a

applycform

Apply device-independent color space transformation

Syntax

```
B = applycform(A,C)
```

Description

`B = applycform(A,C)` converts the color values in `A` to the color space specified in the color transformation structure `C`. The color transformation structure specifies various parameters of the transformation. See `makecform` for details.

If `A` is two-dimensional, each row is interpreted as a color unless the color transformation structure contains a grayscale ICC profile. (See Note for this case.) `A` can have 1 or more columns, depending on the input color space. `B` has the same number of rows and 1 or more columns, depending on the output color space. (The ICC spec currently supports up to 15-channel device spaces.)

If `A` is three-dimensional, each row-column location is interpreted as a color, and `size(A,3)` is typically 1 or more, depending on the input color space. `B` has the same number of rows and columns as `A`, and `size(B,3)` is 1 or more, depending on the output color space.

Class Support

`A` is a real, nonsparse array of class `uint8`, `uint16`, or `double` or a string. `A` is only a string if `C` was created with the following syntax:

```
C = makecform('named', profile, space)
```

The output array `B` has the same class as `A`, unless the output space is `XYZ`. If the input is `XYZ` data of class `uint8`, the output is of class `uint16`, because there is no standard 8-bit encoding defined for `XYZ` color values.

Note: If the color transformation structure **C** contains a grayscale ICC profile, `applycform` interprets each pixel in **A** as a color. **A** can have any number of columns. **B** has the same size as **A**.

Examples

Read in a color image that uses the sRGB color space.

```
rgb = imread('peppers.png');
```

Create a color transformation structure that defines an sRGB to $L^*a^*b^*$ conversion.

```
C = makecform('srgb2lab');
```

Perform the transformation with `applycform`.

```
lab = applycform(rgb,C);
```

More About

- “Understanding Color Spaces and Color Space Conversion”

See Also

`lab2double` | `lab2uint8` | `lab2uint16` | `makecform` | `whitepoint` | `xyz2double`
| `xyz2uint16`

Introduced before R2006a

applylut

Neighborhood operations on binary images using lookup tables

Compatibility

`applylut` is not recommended. Use `bwlookup` instead.

Syntax

```
A = applylut(BW,LUT)
```

Description

`A = applylut(BW,LUT)` performs a 2-by-2 or 3-by-3 neighborhood operation on binary image `BW` by using a lookup table (`LUT`). `LUT` is either a 16-element or 512-element vector returned by `makelut`. The vector consists of the output values for all possible 2-by-2 or 3-by-3 neighborhoods.

Class Support

`BW` can be numeric or logical, and it must be real, two-dimensional, and nonsparse. `LUT` can be numeric or logical, and it must be a real vector with 16 or 512 elements. If all the elements of `LUT` are 0 or 1, then `A` is logical. If all the elements of `LUT` are integers between 0 and 255, then `A` is `uint8`. For all other cases, `A` is `double`.

Examples

Perform Erosion Using a 2-by-2 Neighborhood

Create the `LUT`.


```
lutfun = @(x)(sum(x(:))==4);  
lut    = makelut(lutfun,2);
```


Read image into the workspace and then apply the LUT to the image. An output pixel is on only if all four of the input pixel's neighborhood pixels are on .

```
BW1    = imread('text.png');  
BW2    = applylut(BW1,lut);
```

Show the original image and the eroded image.

```
figure, imshow(BW1);  
figure, imshow(BW2);
```





More About

Algorithms

`applylut` performs a neighborhood operation on a binary image by producing a matrix of indices into `lut`, and then replacing the indices with the actual values in `lut`. The specific algorithm used depends on whether you use 2-by-2 or 3-by-3 neighborhoods.

2-by-2 Neighborhoods

For 2-by-2 neighborhoods, `length(lut)` is 16. There are four pixels in each neighborhood, and two possible states for each pixel, so the total number of permutations is $2^4 = 16$.

To produce the matrix of indices, `applylut` convolves the binary image `BW` with this matrix.

```
8     2
4     1
```

The resulting convolution contains integer values in the range [0,15]. `applylut` uses the central part of the convolution, of the same size as `BW`, and adds 1 to each value to shift the range to [1,16]. It then constructs `A` by replacing the values in the cells of the index matrix with the values in `lut` that the indices point to.

3-by-3 Neighborhoods

For 3-by-3 neighborhoods, `length(lut)` is 512. There are nine pixels in each neighborhood, and two possible states for each pixel, so the total number of permutations is $2^9 = 512$.

To produce the matrix of indices, `applylut` convolves the binary image `BW` with this matrix.

```
256   32   4
128   16   2
 64    8   1
```

The resulting convolution contains integer values in the range [0,511]. `applylut` uses the central part of the convolution, of the same size as `BW`, and adds 1 to each value to shift the range to [1,512]. It then constructs `A` by replacing the values in the cells of the index matrix with the values in `lut` that the indices point to.

See Also

`makelut`

Introduced before R2006a

axes2pix

Convert axes coordinates to pixel coordinates

Syntax

```
pixelx = axes2pix(dim, XDATA, AXESX)
```

Description

`pixelx = axes2pix(dim, XDATA, AXESX)` converts an axes coordinate into an intrinsic (“pixel”) coordinate. For example, if `pt = get(gca, 'CurrentPoint')` then `AXESX` could be `pt(1,1)` or `pt(1,2)`. `AXESX` must be in intrinsic coordinates. `XDATA` is a two-element vector returned by `get(image_handle, 'XData')` or `get(image_handle, 'YData')`. `dim` is the number of image columns for the x coordinate, or the number of image rows for the y coordinate.

Class Support

`dim`, `XDATA`, and `AXESX` can be `double`. The output is `double`.

Note

`axes2pix` performs minimal checking on the validity of `AXESX`, `DIM`, or `XDATA`. For example, `axes2pix` returns a negative coordinate if `AXESX` is less than `XDATA(1)`. The function calling `axes2pix` bears responsibility for error checking.

Examples

Example with default `XData` and `YData`.

```
h = imshow('pout.tif');  
[nrows,ncols] = size(get(h,'CData'));
```

```
xdata = get(h,'XData')
ydata = get(h,'YData')
px = axes2pix(ncols,xdata,30)
py = axes2pix(nrows,ydata,30)
```

Example with non-default XData and YData.

```
xdata = [10 100]
ydata = [20 90]
px = axes2pix(ncols,xdata,30)
py = axes2pix(nrows,ydata,30)
```

See Also

[impixelinfo](#) | [imfill](#) | [bwselect](#) | [impixel](#) | [improfile](#) | [roipoly](#)

Introduced before R2006a

bestblk

Determine optimal block size for block processing

Syntax

```
siz = bestblk([m n],k)
[mb,nb] = bestblk([m n],k)
```

Description

`siz = bestblk([m n],k)` returns, for an m -by- n image, the optimal block size for block processing. The optimal block size is the size required along the outer partial blocks. k is a scalar specifying the maximum row and column dimensions for the block. If you omit this argument, the default is 100. The return value `siz` is a 1-by-2 vector containing the row and column dimensions for the block.

`[mb,nb] = bestblk([m n],k)` returns the row and column dimensions for the block in `mb` and `nb`, respectively.

Examples

Determine Optimal Block Size

```
siz = bestblk([640 800],72)
```

```
siz =
```

```
    64    50
```

More About

Algorithms

`bestblk` returns the optimal block size given m , n , and k . The algorithm for determining `siz` is

- If m is less than or equal to k , return m .
- If m is greater than k , consider all values between $\min(m/10, k/2)$ and k . Return the value that minimizes the padding required.

The same algorithm is then repeated for n .

See Also

blockproc

Introduced before R2006a

blockproc

Distinct block processing for image

Syntax

```
B = blockproc(A, blockSize, fun)
B = blockproc(src_filename, blockSize, fun)
B = blockproc(adapter, blockSize, fun)
blockproc( ___, Name, Value, ...)
```

Description

`B = blockproc(A, blockSize, fun)` processes the image `A` by applying the function `fun` to each distinct block of `A` and concatenating the results into `B`, the output matrix. `blockSize` is a two-element vector, `[rows cols]`, that specifies the size of the block. `fun` is a handle to a function that accepts a *block struct* as input and returns a matrix, vector, or scalar `Y`. For example, `Y = fun(block_struct)`. (For more information about a *block struct*, see the Definition section below.) For each block of data in the input image, `A`, `blockproc` passes the block in a *block struct* to the user function, `fun`, to produce `Y`, the corresponding block in the output image. If `Y` is empty, `blockproc` does not generate any output and returns empty after processing all blocks. Choosing an appropriate block size can significantly improve performance. For more information, see “Choosing Block Size”. For more information about function handles, see “Create Function Handle”.

`B = blockproc(src_filename, blockSize, fun)` processes the image `src_filename`, reading and processing one block at a time. This syntax is useful for processing very large images since only one block of the image is read into memory at a time. If the output matrix `B` is too large to fit into memory, omit the output argument and instead use the 'Destination' parameter/value pair to write the output to a file.

`B = blockproc(adapter, blockSize, fun)` processes the source image specified by `adapter`, an `ImageAdapter` object. An `ImageAdapter` is a user-defined class that provides `blockproc` with a common API for reading and writing to a particular image file format. For more information, see “Read and Write Data in Unsupported Formats Using `blockproc`” in the Image Processing Toolbox™ documentation.

`blockproc(____, Name, Value, ...)` processes the input image, specifying parameters and corresponding values that control various aspects of the block behavior. Parameter names are not case sensitive.

Input Arguments

A

Input image.

blockSize

Size of the block, specified as a two-element vector, `[rows cols]`.

fun

Function handle to a function that accepts a *block struct* as input and returns a matrix, vector, or scalar.

src_filename

Input image.

adapter

A user-defined class that provides `blockproc` with a common API for reading and writing to a particular image file format.

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name, Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (`' '`). You can specify several name and value pair arguments in any order as `Name1, Value1, ... , NameN, ValueN`.

'BorderSize'

A two-element vector, `[V H]`, specifying the amount of border pixels to add to each block. The function adds `V` rows above and below each block and `H` columns left and right of each block. The size of each resulting block will be:

`[M + 2*V, N + 2*H]`

By default, the function automatically removes the border from the result of `fun`. See the `'TrimBorder'` parameter for more information. The function pads blocks with borders extending beyond the image edges with zeros.

Default: `[0 0]` (no border)

'Destination'

The destination for the output of `blockproc`. When you specify the `'Destination'` parameter, `blockproc` does not return the processed image as an output argument, but instead writes the output to the `'Destination'`. (You cannot request an output argument when the `'Destination'` parameter is specified.)

Valid `'Destination'` parameters are:

- **TIFF filename:** A string filename ending with `'.tif'`. If a file with this name already exists, it will be overwritten.
- **ImageAdapter object:** An instance of an `ImageAdapter` class. `ImageAdapters` provide an interface for reading and writing to arbitrary image file formats.

The `'Destination'` parameter is useful when you expect your output to be too large to practically fit into memory. It provides a workflow for file-to-file image processing for arbitrarily large images.

'PadPartialBlocks'

A logical scalar. When set to `true`, `blockproc` pads partial blocks to make them full-sized (`M-by-N`) blocks. Partial blocks arise when the image size is not exactly divisible by the block size. If they exist, partial blocks lie along the right and bottom edge of the image. The default is `false`, meaning that the function does not pad the partial blocks, but processes them as-is. `blockproc` uses zeros to pad partial blocks when necessary.

Default: `false`

'PadMethod'

The `'PadMethod'` determines how `blockproc` will pad the image boundary. Options are:

- **X:** Pads the image with a scalar (`X`) pad value. By default `X == 0`.
- **'replicate':** Repeats border elements of image `A`.
- **'symmetric':** Pads image `A` with mirror reflections of itself.

'TrimBorder'

A logical scalar. When set to `true`, the `blockproc` function trims off border pixels from the output of the user function, `fun`. The function removes `V` rows from the top and bottom of the output of `fun`, and `H` columns from the left and right edges. The `'BorderSize'` parameter defines `V` and `H`. The default is `true`, meaning that the `blockproc` function automatically removes borders from the `fun` output.

Default: `true`

'UseParallel'

A logical scalar. Enabling this mode of image processing requires the Parallel Computing Toolbox™. When set to `true`, `blockproc` will attempt to run in parallel mode, distributing the processing across multiple workers (MATLAB sessions) in an open MATLAB pool. In parallel mode, the input image cannot be an `ImageAdapter` object. See the documentation for `parpool` for information on configuring your parallel environment.

Default: `false`

'DisplayWaitbar'

A logical scalar. When set to `true`, `blockproc` displays a waitbar to indicate progress for long-running operations. To prevent `blockproc` from displaying a waitbar, set `DisplayWaitbar` to `false`.

Default: `true`

File Format Support: Input and output files for `blockproc` (as specified by `src_filename` and the `'Destination'` parameter) must have one of the following file types and must be named with one of the listed file extensions:

- Read/Write File Formats: TIFF (*.tif, *.tiff), JPEG2000 (*.jp2, *.j2c, *.j2k)
- Read-Only File Formats: JPEG2000 (*.jpf, *.jpx)

Output Arguments

B

Output matrix.

Definitions

A *block struct* is a MATLAB structure that contains the block data as well as other information about the block. Fields in the *block struct* are:

- `block_struct.border`: A two-element vector, `[V H]`, that specifies the size of the vertical and horizontal padding around the block of data. (See the 'BorderSize' parameter in the Inputs section.)
- `block_struct.blockSize`: A two-element vector, `[rows cols]`, that specifies the size of the block data. If a border has been specified, the size does not include the border pixels.
- `block_struct.data`: M-by-N or M-by-N-by-P matrix of block data
- `block_struct.imageSize`: A two-element vector, `[rows cols]`, that specifies the full size of the input image.
- `block_struct.location`: A two-element vector, `[row col]`, that specifies the position of the first pixel (minimum-row, minimum-column) of the block data in the input image. If a border has been specified, the location refers to the first pixel of the discrete block data, not the added border pixels.

Examples

Generate an image thumbnail:

```
fun = @(block_struct) imresize(block_struct.data,0.15);  
I = imread('pears.png');  
I2 = blockproc(I,[100 100],fun);  
figure;  
imshow(I);  
figure;  
imshow(I2);
```



Set the pixels in each 32-by-32 block to the standard deviation of the elements in that block:

```
fun = @(block_struct) ...
    std2(block_struct.data) * ones(size(block_struct.data));
I2 = blockproc('moon.tif',[32 32],fun);
figure;
imshow('moon.tif');
figure;
imshow(I2,[]);
```



Original Image



Standard Deviation Image

Switch the red and green bands of an RGB image and write the results to a new TIFF file:

```
I = imread('peppers.png');
fun = @(block_struct) block_struct.data(:,:, [2 1 3]);
blockproc(I,[200 200],fun,'Destination','grb_peppers.tif');
figure;
imshow('peppers.png');
figure;
imshow('grb_peppers.tif');
```



Original Image of Peppers



Recolored Image of Peppers

Convert a TIFF image into a new JPEG2000 image. Replace 'largeImage.tif' in the example below with the name of your file:

```
fun = @(block_struct) block_struct.data;  
blockproc('largeImage.tif',[1024 1024],fun,...  
    'Destination','New.jp2');
```

More About

- “Anonymous Functions”
- “Parameterizing Functions”
- “Distinct Block Processing”

See Also

`colfilt` | `ImageAdapter` | `nlfilter`

Introduced in R2009b

boundarymask

Find region boundaries of segmentation

Syntax

```
mask = boundarymask(L)
mask = boundarymask(BW)
mask = boundarymask( ____, conn)
```

Description

`mask = boundarymask(L)` computes a mask that represents the region boundaries for the input label matrix `L`. The output, `mask`, is a logical image that is `true` at boundary locations and `false` at non-boundary locations.

`mask = boundarymask(BW)` computes the region boundaries for the input binary image `BW`.

`mask = boundarymask(____, conn)` computes the region boundaries using a connectivity specified by `conn`.

“Code Generation” on page 1-107 support: Yes.

“MATLAB Function Block” on page 1-108 support: Yes.

Examples

Create Rasterized Grid of Region Boundaries

Read image into the workspace.

```
A = imread('kobi.png');
```

Create a superpixel representation of the image, returned as a label matrix.


```
L = superpixels(A,100);
```

Create the rasterized grid of the regions in the label matrix.

```
mask = boundarymask(L);
```

Display the boundary mask binary image.

```
figure  
imshow(mask, 'InitialMagnification', 67)
```



Input Arguments

L — Input label matrix

finite, nonnegative, nonsparse, 2-D numeric or logical array

Input label matrix, specified as a finite, nonnegative, nonsparse, 2-D numeric or logical array.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32` | `logical`

BW — Input binary image

numeric or logical array

Input binary image, specified as a numeric or logical array the same size as `L`.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `logical`

conn — Connectivity

8 (default) | 4

Connectivity, specified as the numeric scalar 4 or 8. For a given pixel P in the input image, the corresponding output `mask(P)` is `true` if any of the pixels in the 4-connected or 8-connected neighborhood of P have a value different than P .

Value	Meaning
4	4-connected neighborhood
8	8-connected neighborhood

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

Output Arguments

mask — Rasterized grid of region boundaries

2-D logical matrix

Rasterized grid of region boundaries, specified as a 2-D logical matrix the same size as the input image.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic MATLAB Host Computer target platform, the function generates

code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, the input argument `conn` must be a compile-time constant.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`imoverlay` | `label2idx` | `superpixels`

Introduced in R2016a

bwarea

Area of objects in binary image

Syntax

```
total = bwarea(BW)
```

Description

`total = bwarea(BW)` estimates the area of the objects in binary image `BW`. `total` is a scalar whose value corresponds roughly to the total number of `on` pixels in the image, but might not be exactly the same because different patterns of pixels are weighted differently.

Class Support


`BW` can be numeric or logical. For numeric input, any nonzero pixels are considered to be `on`. The return value `total` is of class `double`.

Examples

Calculate the Area of Objects in a Binary Image

Read the image and display it.

```
BW = imread('circles.png');  
imshow(BW);
```



Calculate the area of objects in the image.

```
bwarea(BW)
```

```
ans =
```

```
1.4187e+04
```

More About

Algorithms

`bwarea` estimates the area of all of the on pixels in an image by summing the areas of each pixel in the image. The area of an individual pixel is determined by looking at its 2-by-2 neighborhood. There are six different patterns, each representing a different area:

- Patterns with zero on pixels (area = 0)
- Patterns with one on pixel (area = 1/4)
- Patterns with two adjacent on pixels (area = 1/2)
- Patterns with two diagonal on pixels (area = 3/4)
- Patterns with three on pixels (area = 7/8)
- Patterns with all four on pixels (area = 1)

Keep in mind that each pixel is part of four different 2-by-2 neighborhoods. This means, for example, that a single on pixel surrounded by off pixels has a total area of 1.

References

- [1] Pratt, William K., *Digital Image Processing*, New York, John Wiley & Sons, Inc., 1991, p. 634.

See Also

bweuler | bwperim

Introduced before R2006a

bwareafilt

Extract objects from binary image by size

Syntax

```
BW2 = bwareafilt(BW,range)
BW2 = bwareafilt(BW,n)
BW2 = bwareafilt(BW,n,keep)
```

Description

`BW2 = bwareafilt(BW,range)` extracts all connected components (objects) from the binary image `BW`, where the area of the objects is in `range`, producing another binary image `BW2`. `range` is a 2-by-1 vector of minimum and maximum sizes (inclusive). `bwareafilt` removes objects that do not meet the criterion. The default connectivity is 8.

`BW2 = bwareafilt(BW,n)` keeps the `n` largest objects. In the event of a tie for `n`-th place, only the first `n` objects are included in `BW2`.

`BW2 = bwareafilt(BW,n,keep)` retains the `n` largest objects if `keep` is 'largest' (the default) or the `n` smallest if `keep` is 'smallest'.

Examples

Filter Binary Image by Area of Objects

Read image.


```
BW = imread('text.png');
```

Filter image, retaining only those objects with areas between 40 and 50.

```
BW2 = bwareafilt(BW,[40 50]);
```

Display the original image and filtered image side by side.

```
imshowpair(BW,BW2, 'montage')
```



Filter Binary Image by Size of Objects

Read image.

```
BW = imread('text.png');
```

Filter image, retaining only the 5 objects with the largest areas.

```
BW2 = bwareafilt(BW,5);
```

Display the original image and the filtered image side by side.

```
imshowpair(BW,BW2, 'montage')
```



- “Filter Images on Region Properties Using Image Region Analyzer App”

Input Arguments

BW — Image to be filtered

binary image

Image to be filtered, specified as a binary image.

Example: `BW = imread('text.png');`

Data Types: `logical`

range — Minimum and maximum values of property inclusive

2-by-1 numeric vector

Minimum and maximum values of the property inclusive, specified as a 2-by-1 numeric vector of the form `[low high]`.

Example: `BW2 = bwareafilt(BW,[40 50]);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

n — Number of objects to include when filtering image objects by size

scalar double

Number of objects to include when filtering image objects by size, specified as a scalar double.

Example: `BW2 = bwareafilt(BW,5);`

Data Types: `double`

keep — Size of objects to include in the output image

'largest' (default) | 'smallest'

Size of objects to include in the output image, specified as the text string 'largest' or 'smallest'. In the event of a tie for n-th place, `bwareafilt` includes only the first n objects.

Example: `BW2 = bwareafilt(BW,5,'smallest');`

Data Types: `char`

Output Arguments

BW2 — Filtered image

binary image

Filtered image, returned as a binary image, the same size and class as the input image `BW`.

See Also

`bwpropfilt` | `conndef` | `regionprops`

Introduced in R2014b

bwareaopen

Remove small objects from binary image

Syntax

```
BW2 = bwareaopen(BW,P)
BW2 = bwareaopen(BW,P,conn)
```

Description

`BW2 = bwareaopen(BW,P)` removes all connected components (objects) that have fewer than `P` pixels from the binary image `BW`, producing another binary image, `BW2`. The default connectivity is 8 for two dimensions, 26 for three dimensions, and `conndef(ndims(BW), 'maximal')` for higher dimensions. This operation is known as an *area opening*.

`BW2 = bwareaopen(BW,P,conn)` removes all connected components, where `conn` specifies the desired connectivity.

“Code Generation” on page 1-118 support: Yes.

MATLAB Function Block support: No.

Examples

Remove Objects in Image Containing Fewer Than 50 Pixels

Read binary image.


```
BW = imread('text.png');
```

Remove objects containing fewer than 50 pixels using `bwareaopen` function.

```
BW2 = bwareaopen(BW, 50);
```

Display original image next to morphologically opened image.

```
imshowpair(BW,BW2,'montage')
```



Input Arguments

BW — Binary image

real, nonsparse, logical or numeric array of any dimension

Binary image, specified as a nonsparse, logical or numeric array of any dimension.

Example: `BW2 = bwareaopen(BW, 50);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

P — Maximum number of pixels in objects

nonnegative, integer-valued, numeric scalar

Maximum number of pixels in objects, specified as a nonnegative, integer-valued, numeric scalar.

Example: `BW2 = bwareaopen(BW, 50);`

Data Types: `double`

conn — Connectivity

8 (2-D), 26 (3-D) or calculated using `conndef(ndims(BW), 'maximal')` for higher dimensions (default) | 4 | 8 | 6 | 18 | 26 | 3-by-3-by-...-by-3 matrix of 0s and 1s.

Connectivity, specified as one of the following numeric scalars:

Value	Meaning
Two-dimensional connectivities	
4	4-connected neighborhood
8	8-connected neighborhood
Three-dimensional connectivities	
6	6-connected neighborhood
18	18-connected neighborhood
26	26-connected neighborhood

Connectivity can also be defined in a more general way for any dimension by specifying a 3-by-3-by-...-by-3 matrix of 0s and 1s. The 1-valued elements define neighborhood locations relative to the central element of `conn`. Note that `conn` must be symmetric about its central element.

Example: `BW2 = bwareaopen(BW, 50, 4);`

Data Types: `double` | `logical`

Output Arguments

BW2 — Image that has been morphologically opened

nonsparse, logical array of any dimension

Image that has been morphologically opened, specified as a nonsparse, logical array the same size as `BW`.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, note the following:

- `BW` must be a 2-D binary image. N-D arrays are not supported.
- `conn` can only be one of the two-dimensional connectivities (4 or 8) or a 3-by-3 matrix. The 3-D connectivities (6, 18, and 26) are not supported. Matrices of size 3-by-3-by-...-by-3 are not supported.
- `conn` must be a compile-time constant.

Algorithms

The basic steps are

- 1 Determine the connected components:

```
CC = bwconncomp(BW, conn);
```

- 2 Compute the area of each component:

```
S = regionprops(CC, 'Area');
```

- 3 Remove small objects:

```
L = labelmatrix(CC);  
BW2 = ismember(L, find([S.Area] >= P));
```

See Also

`bwconncomp` | `conndef`

Introduced before R2006a

bwboundaries

Trace region boundaries in binary image

Syntax

```
B = bwboundaries(BW)
B = bwboundaries(BW,conn)
B = bwboundaries(BW,conn,options)
[B,L]= bwboundaries( ___ )
[B,L,N,A] = bwboundaries( ___ )
```

Description

`B = bwboundaries(BW)` traces the exterior boundaries of objects, as well as boundaries of holes inside these objects, in the binary image `BW`. `bwboundaries` also descends into the outermost objects (parents) and traces their children (objects completely enclosed by the parents). Returns `B`, a cell array of boundary pixel locations.

`B = bwboundaries(BW,conn)` traces the exterior boundaries of objects, where `conn` specifies the connectivity to use when tracing parent and child boundaries.

`B = bwboundaries(BW,conn,options)` traces the exterior boundaries of objects, where `options` is either the string `'holes'` or `'noholes'`, specifying whether you want to include the boundaries of holes inside other objects.

`[B,L]= bwboundaries(___)` returns a label matrix `L` where objects and holes are labeled.

`[B,L,N,A] = bwboundaries(___)` returns `N`, the number of objects found, and `A`, an adjacency matrix.

“Code Generation” on page 1-129 support: Yes.

MATLAB Function Block support: No.

Examples

Overlay Region Boundaries on Image

Read grayscale image into the workspace.


```
I = imread('rice.png');
```

Convert grayscale image to binary image using local adaptive thresholding.

```
BW = imbinarize(I);
```

Calculate boundaries of regions in image and overlay the boundaries on the image.

```
[B,L] = bwboundaries(BW,'noholes');  
imshow(label2rgb(L, @jet, [.5 .5 .5]))  
hold on  
for k = 1:length(B)  
    boundary = B{k};  
    plot(boundary(:,2), boundary(:,1), 'w', 'LineWidth', 2)  
end
```



Overlay Region Boundaries on Image and Annotate with Region Numbers

Read binary image into the workspace.

```
BW = imread('blobs.png');
```

Calculate boundaries of regions in the image.

```
[B,L,N,A] = bwboundaries(BW);
```

Display the image with the boundaries overlaid. Add the region number next to every boundary (based on the label matrix). Use the zoom tool to read individual labels.

```
imshow(BW); hold on;  
colors=['b' 'g' 'r' 'c' 'm' 'y'];  
for k=1:length(B),  
    boundary = B{k};  
    cidx = mod(k,length(colors))+1;
```




```

plot(boundary(:,2), boundary(:,1),...
     colors(cidx), 'LineWidth',2);

%randomize text position for better visibility
rndRow = ceil(length(boundary)/(mod(rand*k,7)+1));
col = boundary(rndRow,2); row = boundary(rndRow,1);
h = text(col+1, row-1, num2str(L(row,col)));
set(h, 'Color', colors(cidx), 'FontSize', 14, 'FontWeight', 'bold');
end

```




Display the adjacency matrix using the `spy` function.

```

figure
spy(A);

```



Display Object Boundaries in Red and Hole Boundaries in Green

Read binary image into workspace.

```
BW = imread('blobs.png');
```

Calculate boundaries.

```
[B,L,N] = bwboundaries(BW);
```


Display object boundaries in red and hole boundaries in green.

```
imshow(BW); hold on;  
for k=1:length(B),  
    boundary = B{k};
```

```

if(k > N)
    plot(boundary(:,2), boundary(:,1), 'g','LineWidth',2);
else
    plot(boundary(:,2), boundary(:,1), 'r','LineWidth',2);
end
end
end

```



Display Parent Boundaries in Red and Holes in Green

Read image into workspace.

```
BW = imread('blobs.png');
```


Display parent boundaries in red and their holes in green.

```

[B,L,N,A] = bwboundaries(BW);
figure; imshow(BW); hold on;
% Loop through object boundaries
for k = 1:N

```

```
% Boundary k is the parent of a hole if the k-th column
% of the adjacency matrix A contains a non-zero element
if (nnz(A(:,k)) > 0)
    boundary = B{k};
    plot(boundary(:,2),...
         boundary(:,1), 'r', 'LineWidth',2);
    % Loop through the children of boundary k
    for l = find(A(:,k))'
        boundary = B{l};
        plot(boundary(:,2),...
             boundary(:,1), 'g', 'LineWidth',2);
    end
end
end
```




Input Arguments

BW — Input binary image

real, nonsparse, 2-D logical or numeric array

Binary input image, specified as a real, nonsparse, 2-D logical or numeric array. **BW** must be a binary image where nonzero pixels belong to an object and 0 pixels constitute the background. The following figure illustrates these components.



Example: `B = bwboundaries(BW);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

conn — Connectivity

8 (default) | 4

Connectivity, specified as either of the following scalar values:

Value	Meaning
4	4-connected neighborhood
8	8-connected neighborhood. This is the default.

Example: `B = bwboundaries(BW,4);`

Data Types: `double`

options — Determine whether to search for both parent and child boundaries

'holes' (default) | 'noholes'

Determine whether to search for both parent and child boundaries, specified as either of the following strings:

String	Meaning
'holes'	Search for both object and hole boundaries. This is the default.
'noholes'	Search only for object (parent and child) boundaries. This can provide better performance.

Example: `B = bwboundaries(BW,'noholes',4);`

Data Types: `char`

Output Arguments

B — Row and column coordinates of boundary pixels

P-by-1 cell array

Row and column coordinates of boundary pixels, returned as a *P*-by-1 cell array, where *P* is the number of objects and holes. Each cell in the cell array contains a *Q*-by-2 matrix. Each row in the matrix contains the row and column coordinates of a boundary pixel. *Q* is the number of boundary pixels for the corresponding region.

L — Label matrix of contiguous regions

2-D array of nonnegative integers

Label matrix of contiguous regions, returned as a 2-D array of nonnegative integers of class `double`. The *k*th region includes all elements in **L** that have value *k*. The number of objects and holes represented by **L** is equal to $\max(\mathbf{L}(:))$. The zero-valued elements of **L** make up the background.

N — Number of objects found

numeric scalar

Number of objects found, returned as a numeric scalar of class `double`.

A — Parent-child dependencies between boundaries and holes

square, sparse, logical matrix

Parent-child dependencies between boundaries and holes, returned as a square, sparse, logical matrix of class `double` with side of length $\max(\mathbf{L}(:))$. The rows and columns of **A** correspond to the positions of boundaries stored in **B**. The first *N* cells in **B** are object boundaries. $\mathbf{A}(i, j) = 1$ means that object *i* is a child of object *j*. The boundaries that enclose or are enclosed by the *k*-th boundary can be found using **A** as follows:

```
enclosing_boundary = find(A(m,:));  
enclosed_boundaries = find(A(:,m));
```

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic MATLAB Host Computer target platform, the function generates

code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, note the following:

- The parameter `conn` must be a compile-time constant.
- The parameter `options` must be a compile-time constant.
- The return value `A` can only be a full matrix, not a sparse matrix.

Algorithms

The `bwboundaries` function implements the Moore-Neighbor tracing algorithm modified by Jacob's stopping criteria. This function is based on the `boundaries` function presented in the first edition of *Digital Image Processing Using MATLAB*, by Gonzalez, R. C., R. E. Woods, and S. L. Eddins, New Jersey, Pearson Prentice Hall, 2004.

References

- [1] Gonzalez, R. C., R. E. Woods, and S. L. Eddins, *Digital Image Processing Using MATLAB*, New Jersey, Pearson Prentice Hall, 2004.

See Also

`bwlabel` | `bwlabeln` | `bwperim` | `bwtraceboundary`

Introduced before R2006a

bwconncomp

Find connected components in binary image

Syntax

```
CC = bwconncomp(BW)
CC = bwconncomp(BW,conn)
```

Description

`CC = bwconncomp(BW)` returns the connected components `CC` found in the binary image `BW`. `bwconncomp` uses a default connectivity of 8 for two dimensions, 26 for three dimensions, and `conndef(ndims(BW), 'maximal')` for higher dimensions.

`CC = bwconncomp(BW,conn)` returns the connected components where `conn` specifies the desired connectivity for the connected components.

“Code Generation” on page 1-136 support: Yes.

MATLAB Function Block support: No.

Examples

Calculate Centroids of 3-D Objects

Create a small sample 3-D array.

```
BW = cat(3, [1 1 0; 0 0 0; 1 0 0], ...
            [0 1 0; 0 0 0; 0 1 0], ...
            [0 1 1; 0 0 0; 0 0 1]);
```

Find the connected components in the array.

```
CC = bwconncomp(BW)
```

```
CC =  
  
    Connectivity: 26  
    ImageSize: [3 3 3]  
    NumObjects: 2  
    PixelIdxList: {[5x1 double] [3x1 double]}
```

Calculate centroids of the objects in the array.


```
S = regionprops(CC, 'Centroid')
```

```
S =  
  
2x1 struct array with fields:  
  
    Centroid
```

Erase Largest Component from Image

Read image into the workspace and display it.

```
BW = imread('text.png');  
imshow(BW)
```



Find the number of connected components in the image.

```
CC = bwconncomp(BW)
```

```
CC =
```


```
Connectivity: 8
ImageSize: [256 256]
NumObjects: 88
PixelIdxList: {1x88 cell}
```

Determine which is the largest component in the image and erase it (set all the pixels to 0).

```
numPixels = cellfun(@numel,CC.PixelIdxList);
[biggest,idx] = max(numPixels);
BW(CC.PixelIdxList{idx}) = 0;
```

Display the image, noting that the largest component happens to be the two consecutive f's in the word different.

```
figure  
imshow(BW)
```



Input Arguments

BW — Input binary image

real, nonsparse, numeric or logical array of any dimension

Input binary image, specified as a real, nonsparse, numeric or logical array of any dimension.

Example: `BW = imread('text.png');` `CC = bwconncomp(BW);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

conn — Connectivity for the connected components

8 for two dimensions; 26 for three dimensions (default) | 4 | 8 | 6 | 18 | 26

Connectivity for the connected components, specified as one of the following scalar values.

Value	Meaning
Two-dimensional connectivities	
4	4-connected neighborhood
8	8-connected neighborhood
Three-dimensional connectivities	
6	6-connected neighborhood
18	18-connected neighborhood
26	26-connected neighborhood

To calculate the default connectivity for higher dimensions, `bwconncomp` uses `conndef(ndims(BW), 'maximal')`.

Connectivity can be defined in a more general way for any dimension using a 3-by-3-by-...-by-3 matrix of 0s and 1s. `conn` must be symmetric about its center element. The 1-valued elements define neighborhood locations relative to `conn`.

Example: `BW = imread('text.png');` `CC = bwconncomp(BW,4);`

Data Types: `double` | `logical`

Output Arguments

CC — Connected components

struct

Connected components, returned as a structure with four fields.

Field	Description
Connectivity	Connectivity of the connected components (objects)
ImageSize	Size of BW

Field	Description
NumObjects	Number of connected components (objects) in BW
PixelIdxList	1-by-NumObjects cell array where the k -th element in the cell array is a vector containing the linear indices of the pixels in the k -th object.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, note the following:

- `bwconncomp` only supports 2-D inputs.
- The `conn` arguments must be a compile-time constant and the only connectivities supported are 4 or 8. You can also specify connectivity as a 3-by-3 matrix, but it can only be `[0 1 0;1 1 1;0 1 0]` or `ones(3)`
- The `PixelIdxList` field in the `CC` struct return value is not supported.

Tips

- The functions `bwlabel`, `bwlabeln`, and `bwconncomp` all compute connected components for binary images. `bwconncomp` replaces the use of `bwlabel` and `bwlabeln`. It uses significantly less memory and is sometimes faster than the other functions.

Function	Input Dimension	Output Form	Memory Use	Connectivity
<code>bwlabel</code>	2-D	Label matrix with double-precision	High	4 or 8
<code>bwlabeln</code>	N-D	Double-precision label matrix	High	Any
<code>bwconncomp</code>	N-D	CC struct	Low	Any

- To extract features from a binary image using `regionprops` with default connectivity, just pass `BW` directly into `regionprops` (i.e., `regionprops(BW)`).

- To compute a label matrix having more memory-efficient data type (e.g., `uint8` versus `double`), use the `labelmatrix` function on the output of `bwconncomp`. See the documentation for each function for more information.

Algorithms

The basic steps in finding the connected components are:

- 1 Search for the next unlabeled pixel, `p`.
- 2 Use a flood-fill algorithm to label all the pixels in the connected component containing `p`.
- 3 Repeat steps 1 and 2 until all the pixels are labelled.

See Also

`bwlabel` | `bwlabeln` | `labelmatrix` | `regionprops`

Introduced in R2009a

bwconvhull

Generate convex hull image from binary image

Syntax

```
CH = bwconvhull(BW)
CH = bwconvhull(BW, method)
CH = bwconvhull(BW, 'objects', conn)
```

Description

`CH = bwconvhull(BW)` computes the convex hull of all objects in `BW` and returns `CH`, a binary convex hull image.

`CH = bwconvhull(BW, method)` specifies the desired method for computing the convex hull image.

`CH = bwconvhull(BW, 'objects', conn)` specifies the desired connectivity used when defining individual foreground objects. The `conn` parameter is only valid when the method is `'objects'`.

Input Arguments

BW

A logical 2-D image

Default:

method

A string that can have the following values:

- `'union'`: Compute the convex hull of all foreground objects, treating them as a single object.

- `'objects'`: Compute the convex hull of each connected component of `BW` individually. `CH` contains the convex hulls of each connected component.

Default: `'union'`

conn

Connectivity. Can have the following scalar values:

- 4: Two-dimensional, four-connected neighborhood.
- 8: Two-dimensional, eight-connected neighborhood.

Additionally, `conn` may be defined in a more general way, using a 3-by-3 matrix of 0s and 1s. The 1-valued elements define neighborhood locations relative to `conn`'s center element. `conn` must be symmetric about its center element.

Default: 8

Output Arguments

CH

A logical, convex hull image, containing the binary mask of the convex hull of all foreground objects in `BW`.

Examples

Display the binary convex hull of an image:


```
subplot(2,2,1);  
I = imread('coins.png');  
imshow(I);  
title('Original');  
  
subplot(2,2,2);  
BW = I > 100;  
imshow(BW);  
title('Binary');  
  
subplot(2,2,3);
```

```
CH = bwconvhull(BW);  
imshow(CH);  
title('Union Convex Hull');  
  
subplot(2,2,4);  
CH_objects = bwconvhull(BW,'objects');  
imshow(CH_objects);  
title('Objects Convex Hull');
```

Original



Binary



Union Convex Hull



Objects Convex Hull



See Also

[bwconncomp](#) | [bwlabel](#) | [labelmatrix](#) | [regionprops](#)

Introduced in R2011a

bwdist

Distance transform of binary image

Syntax

```
D = bwdist(BW)
[D,IDX] = bwdist(BW)
[D,IDX] = bwdist(BW,method)
[gpuarrayD, gpuarrayIDX]= bwdist(gpuarrayBW)
```

Description

`D = bwdist(BW)` computes the Euclidean distance transform of the binary image `BW`. For each pixel in `BW`, the distance transform assigns a number that is the distance between that pixel and the nearest nonzero pixel of `BW`. `bwdist` uses the Euclidean distance metric by default. `BW` can have any dimension. `D` is the same size as `BW`.

`[D,IDX] = bwdist(BW)` also computes the closest-pixel map in the form of an index array, `IDX`. (The closest-pixel map is also called the feature map, feature transform, or nearest-neighbor transform.) `IDX` has the same size as `BW` and `D`. Each element of `IDX` contains the linear index of the nearest nonzero pixel of `BW`.

`[D,IDX] = bwdist(BW,method)` computes the distance transform, where `method` specifies an alternate distance metric. `method` can take any of the following values. The `method` string can be abbreviated.

Method	Description
'chessboard'	In 2-D, the chessboard distance between (x_1,y_1) and (x_2,y_2) is $\max(x_1 - x_2 , y_1 - y_2)$.
'cityblock'	In 2-D, the cityblock distance between (x_1,y_1) and (x_2,y_2) is $ x_1 - x_2 + y_1 - y_2 $.
'euclidean'	In 2-D, the Euclidean distance between (x_1,y_1) and (x_2,y_2) is $\sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2}$.

Method	Description
	This is the default method.
'quasi-euclidean'	In 2-D, the quasi-Euclidean distance between (x_1, y_1) and (x_2, y_2) is $ x_1 - x_2 + (\sqrt{2} - 1) y_1 - y_2 , x_1 - x_2 > y_1 - y_2 $ $(\sqrt{2} - 1) x_1 - x_2 + y_1 - y_2 , \text{ otherwise.}$

`[gpuarrayD, gpuarrayIDX]= bwdist(gpuarrayBW)` computes the Euclidean distance transform of the binary image `gpuarrayBW`, performing the operation on a GPU. The images must be 2-D and have less than 2^{32-1} elements. In addition, you can only compute the Euclidean distance metric. This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-146 support: Yes.

“MATLAB Function Block” on page 1-147 support: Yes.

Class Support

`BW` can be numeric or logical, and it must be nonsparse. `D` is a single matrix with the same size as `BW`. The class of `IDX` depends on the number of elements in the input image, and is determined using the following table.

Class	Range
'uint32'	<code>numel(BW) <= 2³² - 1</code>
'uint64'	<code>numel(BW) >= 2³²</code>

`gpuarrayBW` can be a 2-D `gpuArray` of type `uint8`, `uint16`, `uint32`, `int8`, `int16`, `int32`, `single`, `double` or `logical`. `gpuarrayD` is a `gpuArray` with the same size as `gpuarrayBW` and underlying class `single`. `gpuarrayIDX` is a `gpuArray` with the same size as `gpuarrayBW` and underlying class `uint32`.

Examples

Compute the Euclidean distance transform

Create an image.

```
bw = zeros(5,5);
bw(2,2) = 1;
bw(4,4) = 1
```

```
bw =
    0     0     0     0     0
    0     1     0     0     0
    0     0     0     0     0
    0     0     0     1     0
    0     0     0     0     0
```

Calculate the distance transform.

```
[D,IDX] = bwdist(bw)
```

```
D =
    1.4142    1.0000    1.4142    2.2361    3.1623
    1.0000         0    1.0000    2.0000    2.2361
    1.4142    1.0000    1.4142    1.0000    1.4142
    2.2361    2.0000    1.0000         0    1.0000
    3.1623    2.2361    1.4142    1.0000    1.4142
```

```
IDX =
     7     7     7     7     7
     7     7     7     7    19
     7     7     7    19    19
     7     7    19    19    19
     7    19    19    19    19
```

In the nearest-neighbor matrix `IDX` the values `7` and `19` represent the position of the nonzero elements using linear matrix indexing. If a pixel contains a `7`, its closest nonzero neighbor is at linear position `7`.

Compute the Euclidean distance transform on a GPU

Create an image.

```
bw = gpuArray.zeros(5,5);  
bw(2,2) = 1;  
bw(4,4) = 1;
```


Calculate the distance transform.

```
[D,IDX] = bwdist(bw)
```

Compare 2-D Distance Transforms for Supported Distance Methods

This example shows how to compare the 2-D distance transforms for supported distance methods. In the figure, note how the quasi-Euclidean distance transform best approximates the circular shape achieved by the Euclidean distance method.

```
bw = zeros(200,200); bw(50,50) = 1; bw(50,150) = 1;  
bw(150,100) = 1;  
D1 = bwdist(bw, 'euclidean');  
D2 = bwdist(bw, 'cityblock');  
D3 = bwdist(bw, 'chessboard');  
D4 = bwdist(bw, 'quasi-euclidean');  
figure  
subplot(2,2,1), subimage(mat2gray(D1)), title('Euclidean')  
hold on, imcontour(D1)  
subplot(2,2,2), subimage(mat2gray(D2)), title('City block')  
hold on, imcontour(D2)  
subplot(2,2,3), subimage(mat2gray(D3)), title('Chessboard')  
hold on, imcontour(D3)  
subplot(2,2,4), subimage(mat2gray(D4)), title('Quasi-Euclidean')  
hold on, imcontour(D4)
```



Compare Isosurface Plots for Distance Transforms of 3-D Image





This example shows how to compare isosurface plots for the distance transforms of a 3-D image containing a single nonzero pixel in the center.

```

bw = zeros(50,50,50); bw(25,25,25) = 1;
D1 = bwdist(bw);
D2 = bwdist(bw, 'cityblock');
D3 = bwdist(bw, 'chessboard');
D4 = bwdist(bw, 'quasi-euclidean');
figure
subplot(2,2,1), isosurface(D1,15), axis equal, view(3)
camlight, lighting gouraud, title('Euclidean')
subplot(2,2,2), isosurface(D2,15), axis equal, view(3)

```

```
camlight, lighting gouraud, title('City block')
subplot(2,2,3), isosurface(D3,15), axis equal, view(3)
camlight, lighting gouraud, title('Chessboard')
subplot(2,2,4), isosurface(D4,15), axis equal, view(3)
camlight, lighting gouraud, title('Quasi-Euclidean')
```

Euclidean**City block****Chessboard****Quasi-Euclidean**

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. The code generated for this function uses a precompiled, platform-specific shared library. Use of

a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, the optional second input argument, `method`, must be a compile-time constant. Input images must have fewer than 2^{32} pixels.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

Tips

- `bwdist` uses fast algorithms to compute the true Euclidean distance transform, especially in the 2-D case. The other methods are provided primarily for pedagogical reasons. However, the alternative distance transforms are sometimes significantly faster for multidimensional input images, particularly those that have many nonzero elements.
- The function `bwdist` changed in version 6.4 (R2009b). Previous versions of the Image Processing Toolbox used different algorithms for computing the Euclidean distance transform and the associated label matrix. If you need the same results produced by the previous implementation, use the function `bwdist_old`.

Algorithms

For Euclidean distance transforms, `bwdist` uses the fast algorithm described in

[1] Maurer, Calvin, Rensheng Qi, and Vijay Raghavan, "A Linear Time Algorithm for Computing Exact Euclidean Distance Transforms of Binary Images in Arbitrary Dimensions," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, Vol. 25, No. 2, February 2003, pp. 265-270.

For cityblock, chessboard, and quasi-Euclidean distance transforms, `bwdist` uses the two-pass, sequential scanning algorithm described in

[2] Rosenfeld, Azriel and John Pfaltz, "Sequential operations in digital picture processing," *Journal of the Association for Computing Machinery*, Vol. 13, No. 4, 1966, pp. 471-494.

The different distance measures are achieved by using different sets of weights in the scans, as described in

[3] Paglieroni, David, "Distance Transforms: Properties and Machine Vision Applications," *Computer Vision, Graphics, and Image Processing: Graphical Models and Image Processing*, Vol. 54, No. 1, January 1992, pp. 57-58.

- “Distance Transform”

See Also

bwulterode | watershed

Introduced before R2006a

bwdistgeodesic

Geodesic distance transform of binary image

Syntax

```
D = bwdistgeodesic(BW,mask)
D = bwdistgeodesic(BW,C,R)
D = bwdistgeodesic(BW,ind)
D = bwdistgeodesic(...,method)
```

Description

`D = bwdistgeodesic(BW,mask)` computes the geodesic distance transform, given the binary image `BW` and the seed locations specified by `mask`. Regions where `BW` is `true` represent valid regions that can be traversed in the computation of the distance transform. Regions where `BW` is `false` represent constrained regions that cannot be traversed in the distance computation. For each `true` pixel in `BW`, the geodesic distance transform assigns a number that is the constrained distance between that pixel and the nearest `true` pixel in `mask`. Output matrix `D` contains geodesic distances.

`D = bwdistgeodesic(BW,C,R)` computes the geodesic distance transform of the binary image `BW`. Vectors `C` and `R` contain the column and row coordinates of the seed locations.

`D = bwdistgeodesic(BW,ind)` computes the geodesic distance transform of the binary image `BW`. `ind` is a vector of linear indices of seed locations.

`D = bwdistgeodesic(...,method)` specifies an alternate distance metric.

Input Arguments

BW

Binary image.

mask

Logical image the same size as `BW` that specifies seed locations.

C, R

Numeric vectors that contain the positive integer column and row coordinates of the seed locations. Coordinate values are valid C,R subscripts in BW.

ind

Numeric vector of positive integer, linear indices of seed locations.

method

Type of distance metric. `method` can have any of these values.

Method	Description
'cityblock'	In 2-D, the cityblock distance between (x_1, y_1) and (x_2, y_2) is $ x_1 - x_2 + y_1 - y_2 $.
'chessboard'	The chessboard distance is $\max(x_1 - x_2 , y_1 - y_2)$.
'quasi-euclidean'	The quasi-Euclidean distance is $ x_1 - x_2 + (\sqrt{2} - 1) y_1 - y_2 $, $ x_1 - x_2 > y_1 - y_2 $ $(\sqrt{2} - 1) x_1 - x_2 + y_1 - y_2 $, otherwise.

Default: 'chessboard'

Output Arguments

D

Numeric array of class `single`, with the same size as input BW, that contains geodesic distances.

Class Support

BW is a logical matrix. C, R, and ind are numeric vectors that contain positive integer values. D is a numeric array of class `single` that has the same size as the input BW.

Examples

Compute the geodesic distance transformation of **BW** based on the seed locations specified by vectors **C** and **R**. Output pixels for which **BW** is false have undefined geodesic distance and contain NaN values. Because there is no connected path from the seed locations to element **BW(10,5)**, the output **D(10,5)** has a value of **Inf**.

```
BW = [1 1 1 1 1 1 1 1 1 1;...
      1 1 1 1 1 1 0 0 1 1;...
      1 1 1 1 1 1 0 0 1 1;...
      1 1 1 1 1 1 0 0 1 1;...
      0 0 0 0 0 1 0 0 1 0;...
      0 0 0 0 1 1 0 1 1 0;...
      0 1 0 0 1 1 0 0 0 0;...
      0 1 1 1 1 1 1 0 1 0;...
      0 1 1 0 0 0 1 1 1 0;...
      0 0 0 0 1 0 0 0 0 0];
```

```
BW = logical(BW);
```

```
C = [1 2 3 3 3];
```

```
R = [3 3 3 1 2];
```

```
D = bwdistgeodesic(BW,C,R);
```

More About

Algorithms

`bwdistgeodesic` uses the geodesic distance algorithm described in Soille, P., *Morphological Image Analysis: Principles and Applications, 2nd Edition*, Secaucus, NJ, Springer-Verlag, 2003, pp. 219–221.

See Also

`bwdist` | `graydist`

Introduced in R2011b

bweuler

Euler number of binary image

Syntax

```
eu1 = bweuler(BW,n)
```

Description

`eu1 = bweuler(BW,n)` returns the Euler number for the binary image `BW`. The Euler number is the total number of objects in the image minus the total number of holes in those objects. `n` specifies the connectivity. Objects are connected sets of `on` pixels, that is, pixels having a value of 1.

“Code Generation” on page 1-154 support: Yes.


“MATLAB Function Block” on page 1-155 support: Yes.

Examples

Calculate Euler Number for Binary Image

Read binary image into workspace, and display it.

```
BW = imread('circles.png');  
imshow(BW)
```



Calculate the Euler number. In this example, all the circles touch so they create one object. The object contains four "holes", which are the black areas created by the touching circles. Thus the Euler number is 1 minus 4, or -3.

```
bweuler(BW)
```

```
ans =
```

```
-3
```

Input Arguments

BW — Input binary image

logical or numeric matrix that must be 2-D, real, and nonsparse

Input binary image, specified as a logical or numeric matrix that must be 2-D, real, and nonsparse.

Example: `BW = imread('circles.png'); eu1 = bweuler(BW,4);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

n — Connectivity

8 (default) | 4

Connectivity, specified as either the value 4 or 8.

Value	Description
4	4-connected objects
8	8-connected objects

Example: `BW2 = bweuler(BW,4);`

Data Types: `double`

Output Arguments

eu1 — Euler number

numeric scalar value

Euler number, returned as a numeric scalar value of class `double`.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic `MATLAB Host Computer` target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

Algorithms

`bweuler` computes the Euler number by considering patterns of convexity and concavity in local 2-by-2 neighborhoods. See [2] for a discussion of the algorithm used.

References

- [1] Horn, Berthold P. K., *Robot Vision*, New York, McGraw-Hill, 1986, pp. 73-77.
- [2] Pratt, William K., *Digital Image Processing*, New York, John Wiley & Sons, Inc., 1991, p. 633.

See Also

`bwmorph` | `bwperim`

Introduced before R2006a

bwhitmiss

Binary hit-miss operation

Syntax

```
BW2 = bwhitmiss(BW1,SE1,SE2)
BW2 = bwhitmiss(BW1,INTERVAL)
```

Description

`BW2 = bwhitmiss(BW1,SE1,SE2)` performs the hit-miss operation defined by the structuring elements `SE1` and `SE2`. The hit-miss operation preserves pixels whose neighborhoods match the shape of `SE1` and don't match the shape of `SE2`. `SE1` and `SE2` can be flat structuring element objects, created by `strel`, or neighborhood arrays. The neighborhoods of `SE1` and `SE2` should not have any overlapping elements. The syntax `bwhitmiss(BW1,SE1,SE2)` is equivalent to `imerode(BW1,SE1) & imerode(~BW1,SE2)`.

`BW2 = bwhitmiss(BW1,INTERVAL)` performs the hit-miss operation defined in terms of a single array, called an *interval*. An interval is an array whose elements can contain 1, 0, or -1. The 1-valued elements make up the domain of `SE1`, the -1-valued elements make up the domain of `SE2`, and the 0-valued elements are ignored. The syntax `bwhitmiss(BW1,INTERVAL)` is equivalent to `bwhitmiss(BW1,INTERVAL == 1, INTERVAL == -1)`.

Class Support

`BW1` can be a logical or numeric array of any dimension, and it must be nonsparse. `BW2` is always a logical array the same size as `BW1`. `SE1` and `SE2` must be flat STREL objects or they must be logical or numeric arrays containing 1's and 0's. `INTERVAL` must be an array containing 1's, 0's, and -1's.

Examples

Perform the hit-miss operation on a binary image using an interval.

```
bw = [0 0 0 0 0 0
      0 0 1 1 0 0
      0 1 1 1 1 0
      0 1 1 1 1 0
      0 0 1 1 0 0
      0 0 1 0 0 0]

interval = [0 -1 -1
           1  1 -1
           0  1  0];

bw2 = bwhitmiss(bw,interval)

bw2 =

     0     0     0     0     0     0
     0     0     0     1     0     0
     0     0     0     0     1     0
     0     0     0     0     0     0
     0     0     0     0     0     0
     0     0     0     0     0     0
```

See Also

[imdilate](#) | [imerode](#) | [strel](#) | [offsetstrel](#)

Introduced before R2006a

bwlabel

Label connected components in 2-D binary image

Syntax

```
L = bwlabel(BW)
L = bwlabel(BW,n)
[L,num] = bwlabel( ___ )
[gpuarrayL,num] = bwlabel(gpuarrayBW,n)
```

Description

`L = bwlabel(BW)` returns the label matrix `L` that contains labels for the 8-connected objects found in `BW`. The label matrix, `L`, is the same size as `BW`.

`L = bwlabel(BW,n)` returns a label matrix, where the variable `n` specifies the connectivity.

`[L,num] = bwlabel(___)` also returns `num`, the number of connected objects found in `BW`.

`[gpuarrayL,num] = bwlabel(gpuarrayBW,n)` performs the labeling operation on a GPU. The input image and output image are `gpuArrays`. The variable `n` can be a numeric array or a `gpuArray`. This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-161 support: Yes.

MATLAB Function Block support: No.

Examples

Label Components Using 4-connected Objects

Create a small binary image.

```
BW = logical ([1 1 1 0 0 0 0 0
```

```

    1   1   1   0   1   1   0   0
    1   1   1   0   1   1   0   0
    1   1   1   0   0   0   1   0
    1   1   1   0   0   0   1   0
    1   1   1   0   0   0   1   0
    1   1   1   0   0   0   0   0
    1   1   1   0   0   0   0   0]);

```

Create the label matrix using 4-connected objects.

```
L = bwlabel(BW,4)
```

L =

```

    1   1   1   0   0   0   0   0
    1   1   1   0   2   2   0   0
    1   1   1   0   2   2   0   0
    1   1   1   0   0   0   3   0
    1   1   1   0   0   0   3   0
    1   1   1   0   0   0   3   0
    1   1   1   0   0   3   3   0
    1   1   1   0   0   0   0   0

```

Use the `find` command to get the row and column coordinates of the object labeled "2".

```
[r, c] = find(L==2);
rc = [r c]
```

rc =

```

    2   5
    3   5
    2   6
    3   6

```

Label Components Using 4-connected Objects on a GPU

Create a small binary image and create a `gpuArray` object to contain it.

```
BW = gpuArray(logical([1 1 1 0 0 0 0 0
                      1 1 1 0 1 1 0 0

```

```

1 1 1 0 1 1 0 0
1 1 1 0 0 0 1 0
1 1 1 0 0 0 1 0
1 1 1 0 0 0 1 0
1 1 1 0 0 1 1 0
1 1 1 0 0 0 0 0]);

```

Create the label matrix using 4-connected objects.

```
L = bwlabel(BW,4)
```

Use the `find` command to get the row and column coordinates of the object labeled "2".

```
[r,c] = find(L == 2)
```

Input Arguments

BW — Input binary image

2-D, real, nonsparse, numeric or logical array

Input binary image, specified as a 2-D, real, nonsparse, numeric or logical array.

```
Example: BW = imread('text.png'); L = bwlabel(BW);
```

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

n — Connectivity

8 (default) | 4

Connectivity, specified as the values **4**, for 4-connected objects, or **8**, for 8-connected objects.

```
Example: BW = imread('text.png'); L = bwlabel(BW,4);
```

Data Types: `double`

gpuarrayBW — Input binary image for processing on GPU

`gpuArray`

Input binary image for processing on GPU, specified as a `gpuArray`.

```
Example: BW = gpuArray(imread('text.png')); L = bwlabel(BW);
```

Output Arguments

L – Label matrix

array class double

Label matrix, returned as an array of class `double`, the same size as the input image.

num – Number of connected objects found

array class double

Label matrix, returned as an array of class `double`.

gpuarrayL – Label matrix

gpuArray

Label matrix, returned as a `gpuArray` when processed on a GPU.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, the parameter `n` must be a compile-time constant.

Tips

- The functions `bwlabel`, `bwlabeln`, and `bwconncomp` all compute connected components for binary images. `bwconncomp` replaces the use of `bwlabel` and `bwlabeln`. It uses significantly less memory and is sometimes faster than the other functions.

	Input Dimension	Output Form	Memory Use	Connectivity
<code>bwlabel</code>	2-D	Double-precision label matrix	High	4 or 8
<code>bwlabeln</code>	N-D	Double-precision label matrix	High	Any
<code>bwconncomp</code>	N-D	CC struct	Low	Any

- You can use the MATLAB `find` function in conjunction with `bwlabel` to return vectors of indices for the pixels that make up a specific object. For example, to return the coordinates for the pixels in object 2, enter the following:

```
[r, c] = find(bwlabel(BW)==2)
```

You can display the output matrix as a pseudocolor indexed image. Each object appears in a different color, so the objects are easier to distinguish than in the original image. For more information, see `label2rgb`.

- To compute a label matrix having a more memory-efficient data type (e.g., `uint8` versus `double`), use the `labelmatrix` function on the output of `bwconncomp`. For more information, see the reference page for each function.
- To extract features from a binary image using `regionprops` with default connectivity, just pass `BW` directly into `regionprops`, i.e., `regionprops(BW)`.
- The `bwlabel` function can take advantage of hardware optimization for data types `logical`, `uint8`, and `single` to run faster. Hardware optimization requires `marker` and `mask` to be 2-D images and `conn` to be either 4 or 8.

Algorithms

`bwlabel` uses the general procedure outlined in reference [1], pp. 40-48:

- 1 Run-length encode the input image.
- 2 Scan the runs, assigning preliminary labels and recording label equivalences in a local equivalence table.
- 3 Resolve the equivalence classes.
- 4 Relabel the runs based on the resolved equivalence classes.

References

- [1] Haralick, Robert M., and Linda G. Shapiro, *Computer and Robot Vision, Volume I*, Addison-Wesley, 1992, pp. 28-48.

See Also

`bwconncomp` | `bwlabeln` | `bwselect` | `label2rgb` | `labelmatrix` | `regionprops`

Introduced before R2006a

bwlabeln

Label connected components in binary image

Syntax

```
L = bwlabeln(BW)
[L, NUM] = bwlabeln(BW)
[L, NUM] = bwlabeln(BW, conn)
```

Description

`L = bwlabeln(BW)` returns a label matrix, `L`, containing labels for the connected components in `BW`. The input image `BW` can have any dimension; `L` is the same size as `BW`. The elements of `L` are integer values greater than or equal to 0. The pixels labeled 0 are the background. The pixels labeled 1 make up one object; the pixels labeled 2 make up a second object; and so on. The default connectivity is 8 for two dimensions, 26 for three dimensions, and `conndef(ndims(BW), 'maximal')` for higher dimensions.

`[L, NUM] = bwlabeln(BW)` returns in `NUM` the number of connected objects found in `BW`.

`[L, NUM] = bwlabeln(BW, conn)` specifies the desired connectivity. `conn` can have any of the following scalar values.

Value	Meaning
Two-dimensional connectivities	
4	4-connected neighborhood
8	8-connected neighborhood
Three-dimensional connectivities	
6	6-connected neighborhood
18	18-connected neighborhood
26	26-connected neighborhood

Connectivity can also be defined in a more general way for any dimension by using for `conn` a 3-by-3-by-...-by-3 matrix of 0s and 1s. The 1-valued elements define neighborhood locations relative to the central element of `conn`. Note that `conn` must be symmetric about its central element.

The functions `bwlabel`, `bwlabeln`, and `bwconncomp` all compute connected components for binary images. `bwconncomp` replaces the use of `bwlabel` and `bwlabeln`. It uses significantly less memory and is sometimes faster than the older functions.

Function	Input Dimension	Output Form	Memory Use	Connectivity
<code>bwlabel</code>	2-D	Double-precision label matrix	High	4 or 8
<code>bwlabeln</code>	N-D	Double-precision label matrix	High	Any
<code>bwconncomp</code>	N-D	CC struct	Low	Any

Class Support

BW can be numeric or logical, and it must be real and nonsparse. L is of class `double`.

Examples

Calculate the centroids of the 3-D objects.

```
BW = cat(3, [1 1 0; 0 0 0; 1 0 0],...
           [0 1 0; 0 0 0; 0 1 0],...
           [0 1 1; 0 0 0; 0 0 1])
```

```
bwlabeln(BW)
```

```
ans(:,:,1) =
```

```
    1    1    0
    0    0    0
    2    0    0
```

```
ans(:,:,2) =
```

```
0    1    0
0    0    0
0    2    0
```

```
ans(:,:,3) =
```

```
0    1    1
0    0    0
0    0    2
```

More About

Tips

To extract features from a binary image using `regionprops` with default connectivity, just pass `BW` directly into `regionprops`, i.e., `regionprops(BW)`.

To compute a label matrix having a more memory-efficient data type (e.g., `uint8` versus `double`), use the `labelmatrix` function on the output of `bwconncomp`:

```
C = bwconncomp(BW);
L = labelmatrix(CC);
```

```
CC = bwconncomp(BW, conn);
S = regionprops(CC);
```

Algorithms

`bwlabeln` uses the following general procedure:

- 1 Scan all image pixels, assigning preliminary labels to nonzero pixels and recording label equivalences in a union-find table.
- 2 Resolve the equivalence classes using the union-find algorithm [1].
- 3 Relabel the pixels based on the resolved equivalence classes.

References

[1] Sedgewick, Robert, *Algorithms in C*, 3rd Ed., Addison-Wesley, 1998, pp. 11-20.

See Also

`bwconncomp` | `bwlabel` | `labelmatrix` | `label2rgb` | `regionprops`

Introduced before R2006a

bwlookup

Nonlinear filtering using lookup tables

Syntax

```
A = bwlookup(BW,lut)
gpuarrayA = bwlookup(gpuarrayBW,lut)
```

Description

`A = bwlookup(BW,lut)` performs a 2-by-2 or 3-by-3 nonlinear neighborhood filtering operation on binary or grayscale image `BW` and returns the results in output image `A`. The neighborhood processing determines an integer index value used to access values in lookup table `lut`. The fetched `lut` value becomes the pixel value in output image `A` at the targeted position.

- `A` is the same size as `BW`
- `A` is the same data type as `lut`

`gpuarrayA = bwlookup(gpuarrayBW,lut)` performs the filtering operation on a GPU. The input image and output image are `gpuArrays`. `lut` can be a numeric or `gpuArray` vector. This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-171 support: Yes.

“MATLAB Function Block” on page 1-171 support: Yes.

Examples

2-by-2 Neighborhood Erosion of Binary Image

Perform an erosion along the edges of a binary image using a 2-by-2 neighborhood. Vector `lut` is constructed such that the filtering operation places a 1 at the targeted pixel


```
set(h2, 'Ylim', [.5 64.5]); set(h2, 'Xlim', [.5 64.5]);
```



2-by-2 Neighborhood Erosion of Binary Image Using GPU

Perform an erosion along the edges of a binary image using a 2-by-2 neighborhood, running the code on a graphics processing unit (GPU).

Construct lut so it is true only when all four 2-by-2 locations equal 1

```
lut = makeLut('sum(x(:))==4',2);
```

Load binary image.

```
BW1 = imread('text.png');
```

Perform 2-by-2 neighborhood processing with 16-element vector LUT. To run the code on a GPU, create a gpuArray to contain the image.

```
BW2 = bwlookup(gpuArray(BW1),lut);
```

Show zoomed before and after images.

```
figure;
h1 = subplot(1,2,1); imshow(BW1), axis off; title('BW1')
h2 = subplot(1,2,2); imshow(BW2); axis off; title('BW2')
```

```
% 16X zoom to see effects of erosion on text
set(h1, 'Ylim', [.5 64.5]); set(h1, 'Xlim', [.5 64.5]);
```

```
set(h2, 'Ylim', [.5 64.5]); set(h2, 'Xlim', [.5 64.5]);
```

Input Arguments

BW — Input image

binary image | grayscale image

Input image transformed by nonlinear neighborhood filtering operation, specified as either a grayscale or binary (logical) image. In the case of numeric values, non-zero pixels are considered `true` which is equivalent to logical 1.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

gpuarrayBW — Input image for processing on a GPU

A `gpuArray` containing a binary image

Input image for processing on a GPU, specified as a `gpuArray` containing a binary image.

lut — Lookup table of output pixel values

16- or 512-element vector

Lookup table of output pixel values, specified as a 16- or 512-element vector. The size of `lut` determines which of the two neighborhood operations is performed.

- If `lut` contains 16 data elements, then the neighborhood matrix is 2-by-2.
- If `lut` contains 512 data elements, then the neighborhood matrix is 3-by-3.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

Output Arguments

A — Output image

binary image | grayscale image

Output image, returned as a grayscale or binary image whose size matches `BW`, and whose distribution of pixel values are determined by the content of `lut`.

- A is the same size as BW
- A is the same data type as lut

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

gpuarrayA — Output image

gpuArray containing a grayscale or binary image

Output image, returned as `agpuArray` containing a grayscale or binary image.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic MATLAB Host Computer target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, specify an input image of class `logical`.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.


Algorithms

The first step in each iteration of the filtering operation performed by `bwlookup` entails computing the `index` into vector `lut` based on the binary pixel pattern of the neighborhood matrix on image `BW`. The value in `lut` accessed at `index`, `lut(index)`, is inserted into output image `A` at the targeted pixel location. This results in image `A` being the same data type as vector `lut`.

Since there is a 1-to-1 correspondence in targeted pixel locations, image `A` is the same size as image `BW`. If the targeted pixel location is on an edge of image `BW` and if any part of the 2-by-2 or 3-by-3 neighborhood matrix extends beyond the image edge, then these non-image locations are padded with 0 in order to perform the filtering operation.

The following figures show the mapping from binary 0 and 1 patterns in the neighborhood matrices to its binary representation. Adding 1 to the binary representation yields `index` which is used to access `lut`.

For 2-by-2 neighborhoods, `length(lut)` is 16. There are four pixels in each neighborhood, and two possible states for each pixel, so the total number of permutations is $2^4 = 16$.



To illustrate, this example shows how the pixel pattern in a 2-by-2 matrix determines which entry in lut is placed in the targeted pixel location.

- 1 Create random 16-element lut vector containing `uint8` data.

```
scurr = rng;    % save current random number generator seed state
rng('default') % always generate same set of random numbers
lut = uint8( round( 255*rand(16,1) ) ) % generate lut
rng(scurr);    % restore
```

```
lut =
```

```
208
231
 32
233
161
 25
 71
139
244
246
 40
248
244
124
204
 36
```

- 2 Create a 2-by-2 image and assume for this example that the targeted pixel location is location `BW(1,1)`.

```
BW = [1 0; 0 1]
```

```
BW =
```

```
 1    0
 0    1
```

- 3 By referring to the color coded mapping figure above, the binary representation for this 2-by-2 neighborhood can be computed as shown in the code snippet below. The logical 1 at `BW(1,1)` corresponds to blue in the figure which maps to the Least Significant Bit (LSB) at position 0 in the 4-bit binary representation ($2^0=1$). The logical 1 at `BW(2,2)` is red which maps to the Most Significant Bit (MSB) at position 3 in the 4-bit binary representation ($2^3=8$).

```

% BW(1,1): blue square; sets bit position 0 on right
% BW(2,2): red square; sets bit position 3 on left
binNot = '1 0 0 1'; % binary representation of 2x2 neighborhood matrix

X = bin2dec( binNot ); % convert from binary to decimal
index = X + 1 % add 1 to compute index value for uint8 vector lut
A11 = lut(index) % value at A(1,1)

index =

    10

A11 =

    246

```

- 4 The above calculation predicts that output image A should contain the value 246 at targeted position A(1,1).

```

A = bwlookup(BW,lut) % perform filtering

A =

    246    32
    161   231

```

A(1,1) does in fact equal 246.

Note: For a more robust way to perform image erosion, see function `imerode`.

For 3-by-3 neighborhoods, `length(lut)` is 512. There are nine pixels in each neighborhood, and two possible states for each pixel, so the total number of permutations is $2^9 = 512$.

The process for computing the binary representation of 3-by-3 neighborhood processing is the same as shown above for 2-by-2 neighborhoods.




Figure 1: Color coded mapping from Pixel Patterns to Binary Representation for 3x3 Matrix

See Also

make1ut

Introduced in R2012b

bwmorph

Morphological operations on binary images

Syntax

```
BW2 = bwmorph(BW,operation)
BW2 = bwmorph(BW,operation,n)
gpuarrayBW2 = bwmorph(gpuarrayBW, ___ )
```

Description

`BW2 = bwmorph(BW,operation)` applies a specific morphological operation to the binary image `BW`.

`BW2 = bwmorph(BW,operation,n)` applies the operation `n` times. `n` can be `Inf`, in which case the operation is repeated until the image no longer changes.

`gpuarrayBW2 = bwmorph(gpuarrayBW, ___)` performs the morphological operation on a GPU. The input image and output image are `gpuArrays`. This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-185 support: Yes.


MATLAB Function Block support: No.

Examples

Perform Morphological Operations on Binary Image


Read binary image and display it.

```
BW = imread('circles.png');
imshow(BW);
```


Remove interior pixels to leave an outline of the shapes.

```
BW2 = bwmorph(BW, 'remove');  
figure  
imshow(BW2)
```



Get the image skeleton.

```
BW3 = bwmorph(BW, 'skel', Inf);  
figure  
imshow(BW3)
```



Perform Morphological Operations on a GPU

This example performs the same operations as the previous example but performs them on a GPU. The example starts by reading the image into a `gpuArray`.

```
BW1 = gpuArray(imread('circles.png'));  
figure  
imshow(BW1)
```

```
BW2 = bwmorph(BW1, 'remove');  
figure  
imshow(BW2)
```

```
BW3 = bwmorph(BW1, 'skel', Inf);  
figure  
imshow(BW3)
```

Input Arguments

BW — Input image

binary image

Input image, specified as a binary image. The input image can be numeric or logical, but must be 2-D, real and nonsparse.

Example: `BW = imread('circles.png');`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

operation — Morphological operation to perform

character string

Morphological operation to perform, specified as one of the following character strings.

Operation	Description
'bothat'	Performs the morphological “bottom hat” operation, returning the image minus the morphological closing of the image (dilation followed by erosion).
'branchpoints'	Find branch points of skeleton. For example: <pre> 0 0 1 0 0 0 0 0 0 0 0 0 1 0 0 becomes 0 0 0 0 0 1 1 1 1 1 0 0 1 0 0 0 0 1 0 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 </pre> <p>Note: To find branch points, the image must be skeletonized. To create a skeletonized image, use <code>bwmorph(BW, 'skel')</code>.</p>
'bridge'	Bridges unconnected pixels, that is, sets 0-valued pixels to 1 if they have two nonzero neighbors that are not connected. For example: <pre> 1 0 0 1 1 0 1 0 1 becomes 1 1 1 0 0 1 0 1 1 </pre>
'clean'	Removes isolated pixels (individual 1s that are surrounded by 0s), such as the center pixel in this pattern.

Operation	Description
	<pre>0 0 0 0 1 0 0 0 0</pre>
'close'	Performs morphological closing (dilation followed by erosion).
'diag'	<p>Uses diagonal fill to eliminate 8-connectivity of the background. For example:</p> <pre>0 1 0 0 1 0 1 0 0 becomes 1 1 0 0 0 0 0 0 0</pre>
'endpoints'	<p>Finds end points of skeleton. For example:</p> <pre>1 0 0 0 1 0 0 0 0 1 0 0 becomes 0 0 0 0 0 0 1 0 0 0 1 0 0 0 0 0 0 0 0 0</pre> <p>Note: To find end points, the image must be skeletonized. To create a skeletonized image, use <code>bwmorph(BW, 'skel')</code>.</p>
'fill'	<p>Fills isolated interior pixels (individual 0s that are surrounded by 1s), such as the center pixel in this pattern.</p> <pre>1 1 1 1 0 1 1 1 1</pre>
'hbreak'	<p>Removes H-connected pixels. For example:</p> <pre>1 1 1 1 1 1 0 1 0 becomes 0 0 0 1 1 1 1 1 1</pre>
'majority'	<p>Sets a pixel to 1 if five or more pixels in its 3-by-3 neighborhood are 1s; otherwise, it sets the pixel to 0.</p>
'open'	Performs morphological opening (erosion followed by dilation).
'remove'	<p>Removes interior pixels. This option sets a pixel to 0 if all its 4-connected neighbors are 1, thus leaving only the boundary pixels on.</p>

Operation	Description
'shrink'	With $n = \text{Inf}$, shrinks objects to points. It removes pixels so that objects without holes shrink to a point, and objects with holes shrink to a connected ring halfway between each hole and the outer boundary. This option preserves the Euler number.
'skel'	With $n = \text{Inf}$, removes pixels on the boundaries of objects but does not allow objects to break apart. The pixels remaining make up the image skeleton. This option preserves the Euler number.
'spur'	Removes spur pixels. For example: <pre> 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 1 0 becomes 0 0 0 0 0 1 0 0 0 1 0 0 1 1 0 0 1 1 0 0 </pre>
'thicken'	With $n = \text{Inf}$, thickens objects by adding pixels to the exterior of objects until doing so would result in previously unconnected objects being 8-connected. This option preserves the Euler number.
'thin'	With $n = \text{Inf}$, thins objects to lines. It removes pixels so that an object without holes shrinks to a minimally connected stroke, and an object with holes shrinks to a connected ring halfway between each hole and the outer boundary. This option preserves the Euler number. See “Algorithms” on page 1-186 for more detail.
'tophat'	Performs morphological "top hat" operation, returning the image minus the morphological opening of the image (erosion followed by dilation).

Example: `BW3 = bwmorph(BW, 'skel');`

Data Types: char

n — Number of times to perform the operation

numeric value

Number of times to perform the operation, specified as a numeric value. n can be `Inf`, in which case `bwmorph` repeats the operation until the image no longer changes.

Example: `BW3 = bwmorph(BW, 'skel', 100);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

gpuarrayBW — Input image

binary image in a `gpuArray`

Input image, specified as a binary image of class `logical` in a `gpuArray`. The input image can be numeric or logical, but must be 2-D, real and nonsparse.

Example: `BW = imread('circles.png');`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

Output Arguments

BW2 — Output image

binary image

Output image returned as a binary image of class `logical`.

gpuarrayBW2 — Output image

binary image in a `gpuArray`

Output image returned as a binary image of class `logical` in a `gpuArray`.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic MATLAB Host Computer target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, the text string specifying the operation must be a compile-time constant and, for best results, the input image must be of class `logical`.

Tips

- To perform erosion or dilation, use the `imerode` or `imdilate` functions. If you want to duplicate the dilation or erosion performed by `bwmorph`, specify the structuring element `ones(3)` with these functions.

Algorithms

When used with the 'thin' option, `bwmorph` uses the following algorithm (References [3]):

- 1 In the first subiteration, delete pixel p if and only if the conditions G_1 , G_2 , and G_3 are all satisfied.
- 2 In the second subiteration, delete pixel p if and only if the conditions G_1 , G_2 , and G_3' are all satisfied.

Condition G1:

$$X_H(p) = 1$$

where

$$X_H(p) = \sum_{i=1}^4 b_i$$

$$b_i = \begin{cases} 1, & \text{if } x_{2i-1} = 0 \text{ and } (x_{2i} = 1 \text{ or } x_{2i+1} = 1) \\ 0, & \text{otherwise} \end{cases}$$

x_1, x_2, \dots, x_8 are the values of the eight neighbors of p , starting with the east neighbor and numbered in counter-clockwise order.

Condition G2:

$$2 \leq \min\{n_1(p), n_2(p)\} \leq 3$$

where

$$n_1(p) = \sum_{k=1}^4 x_{2k-1} \vee x_{2k}$$

$$n_2(p) = \sum_{k=1}^4 x_{2k} \vee x_{2k+1}$$

Condition G3:

$$(x_2 \vee x_3 \vee \bar{x}_8) \wedge x_1 = 0$$

Condition G3':

$$(x_6 \vee x_7 \vee \bar{x}_4) \wedge x_5 = 0$$

The two subiterations together make up one iteration of the thinning algorithm. When the user specifies an infinite number of iterations (`n=Inf`), the iterations are repeated until the image stops changing. The conditions are all tested using `applylut` with precomputed lookup tables.

References

- [1] Haralick, Robert M., and Linda G. Shapiro, *Computer and Robot Vision*, Vol. 1, Addison-Wesley, 1992.
- [2] Kong, T. Yung and Azriel Rosenfeld, *Topological Algorithms for Digital Image Processing*, Elsevier Science, Inc., 1996.
- [3] Lam, L., Seong-Whan Lee, and Ching Y. Suen, "Thinning Methodologies-A Comprehensive Survey," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, Vol 14, No. 9, September 1992, page 879, bottom of first column through top of second column.
- [4] Pratt, William K., *Digital Image Processing*, John Wiley & Sons, Inc., 1991.

See Also

`bweuler` | `bwperim` | `gpuArray` | `imdilate` | `imerode`

Introduced before R2006a

bwpack

Pack binary image


Syntax

```
BWP = bwpack(BW)
```

Description

`BWP = bwpack(BW)` packs the `uint8` binary image `BW` into the `uint32` array `BWP`, which is known as a *packed binary image*. Because each 8-bit pixel value in the binary image has only two possible values, 1 and 0, `bwpack` can map each pixel to a single bit in the packed output image.

`bwpack` processes the image pixels by column, mapping groups of 32 pixels into the bits of a `uint32` value. The first pixel in the first row corresponds to the least significant bit of the first `uint32` element of the output array. The first pixel in the 32nd input row corresponds to the most significant bit of this same element. The first pixel of the 33rd row corresponds to the least significant bit of the second output element, and so on. If `BW` is `M`-by-`N`, then `BWP` is `ceil(M/32)`-by-`N`. This figure illustrates how `bwpack` maps the pixels in a binary image to the bits in a packed binary image.



Binary image packing is used to accelerate some binary morphological operations, such as dilation and erosion. If the input to `imdilate` or `imerode` is a packed binary image, the functions use a specialized routine to perform the operation faster.

Use `bwunpack` to unpack packed binary images.

“Code Generation” on page 1-191 support: Yes.

“MATLAB Function Block” on page 1-191 support: Yes.

Class Support

`BW` can be logical or numeric, and it must be 2-D, real, and nonsparse. `BWP` is of class `uint32`.

Examples

Pack, dilate, and unpack a binary image:

```
BW = imread('text.png');  
BWp = bwpack(BW);  
BWp_dilated = imdilate(BWp,ones(3,3),'ispacked');  
BW_dilated = bwunpack(BWp_dilated, size(BW,1));
```

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. The code generated for this function uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`bwunpack` | `imdilate` | `imerode`

Introduced before R2006a

bwperim

Find perimeter of objects in binary image

Syntax

```
BW2 = bwperim(BW)
BW2 = bwperim(BW,conn)
```

Description

`BW2 = bwperim(BW)` returns a binary image that contains only the perimeter pixels of objects in the input image `BW`. A pixel is part of the perimeter if it is nonzero and it is connected to at least one zero-valued pixel. The default connectivity is 4 for two dimensions, 6 for three dimensions, and `conndef(ndims(BW), 'minimal')` for higher dimensions. If you do not specify a return value, `bwperim` displays the result in a figure window.

`BW2 = bwperim(BW,conn)` where `conn` specifies the desired connectivity.

“Code Generation” on page 1-194 support: Yes.

“MATLAB Function Block” on page 1-195 support: Yes.

Examples

Find Perimeter of Objects in Binary Image

Read binary image into workspace.


```
BW = imread('circles.png');
```

Calculate the perimeters of objects in the image.

```
BW2 = bwperim(BW,8);
```

Display the original image and the perimeters side-by-side.

```
imshowpair(BW,BW2,'montage')
```



Input Arguments

BW — Input binary image

logical or numeric matrix that must be 2-D, real, and nonsparse

Input binary image, specified as a logical or numeric matrix that must be 2-D, real, and nonsparse.

Example: `BW = imread('circles.png');` `BW2 = bwperim(BW);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

conn — Connectivity

4 for 2-D (default) | 6 | 8 | 18 | 26 | 3-by-3-by-...-by-3 array of zeroes and ones

Connectivity, specified as one of the values in this table or a 3-by-3-by-...-by-3 array of 0s and 1s. The 1-valued elements define neighborhood locations relative to the center element of `conn`. Note that `conn` must be symmetric around its center element.

Value	Meaning
Two-dimensional connectivities	
4	4-connected neighborhood
8	8-connected neighborhood
Three-dimensional connectivities	
6	6-connected neighborhood
18	18-connected neighborhood
26	26-connected neighborhood

Example: `BW2 = bwperim(BW,8);`

Data Types: `double` | `logical`

Output Arguments

BW2 — Output binary image containing only perimeter pixels of objects

logical array

Output image containing only perimeter pixels of objects, returned as a logical array.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic `MATLAB Host Computer` target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, note the following:

- `bwperim` supports only 2-D images.
- `bwperim` does not support a no-output-argument syntax.

- The connectivity matrix input argument, `conn`, must be a constant

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`bwarea` | `bwboundaries` | `bweuler` | `bwtraceboundary` | `conndef` | `imfill`

Introduced before R2006a

bwpropfilt

Extract objects from binary image using properties

Syntax

```
BW2 = bwpropfilt(BW,attrib,range)
BW2 = bwpropfilt(BW,attrib,n)
BW2 = bwpropfilt(BW,attrib,n,keep)
BW2 = bwpropfilt(BW,I,attrib,___)
BW2 = bwpropfilt(BW,___, conn)
```

Description

`BW2 = bwpropfilt(BW,attrib,range)` extracts all connected components (objects) from a binary image `BW` that meet the criteria specified by `attrib` and `range`. `attrib` is a text string that identifies a particular property of the objects, such as their area. `range` is a 1-by-2 row vector that specifies the range of values (low and high) of the property. `bwpropfilt` returns a binary image `BW2` containing only those objects that meet the criteria.

`BW2 = bwpropfilt(BW,attrib,n)` sorts the objects based on the value of the specified property, `attrib`, returning a binary image that contains only the top `n` largest objects. In the event of a tie for `n`-th place, `bwpropfilt` keeps only the first `n` objects in `BW2`.

`BW2 = bwpropfilt(BW,attrib,n,keep)` sorts the objects based on `attrib` values, keeping the `n` largest values if `keep` is 'largest' (the default) and the `n` smallest if `keep` is 'smallest'.

`BW2 = bwpropfilt(BW,I,attrib,___)` sorts objects based on the intensity values in the grayscale image `I` and the property `attrib`.

`BW2 = bwpropfilt(BW,___, conn)` specifies the desired connectivity. Connectivity can be either 4, 8, or a 3-by-3 matrix of 0s and 1. The 1-valued elements define neighborhood locations relative to the center element of `conn` and `conn` must be symmetric about its center element.


Examples

Find Regions Without Holes

Read image and display it.

```
BW = imread('text.png');  
figure  
imshow(BW)  
title('Original Image')
```


Original Image



Use filtering to create a second image that contains only those regions in the original image that do not have holes. For these regions, the Euler number property is equal to 1. Display filtered image.

```
BW2 = bwpropfilt(BW, 'EulerNumber', [1 1]);  
figure
```

```
imshow(BW2)
title('Regions with Euler Number == 1')
```



Find Which Ten Objects Have Largest Perimeters


Read image.

```
BW = imread('text.png');
```

Find the ten objects in the image with the largest perimeters and display filtered image.

```
BW2 = bwpropfilt(BW, 'perimeter', 10);
figure;
imshow(BW2)
title('Objects with the Largest Perimeters')
```

Objects with the Largest Perimeters



- “Filter Images on Region Properties Using Image Region Analyzer App”

Input Arguments

BW — Image to be filtered

binary image

Image to be filtered, specified as a binary image.

Example: `BW = imread('text.png');`

Data Types: `logical`

attrib — Name of attribute on which to filter

string

Name of attribute on which to filter, specified as one of the following strings. For detailed information about these attributes, see `regionprops`.

Area	EulerNumber	MinorAxisLength
ConvexArea	Extent	Orientation
Eccentricity	FilledArea	Perimeter
EquivDiameter	MajorAxisLength	Solidity

If you specify a grayscale image, `attrib` can have one of these additional values.

MaxIntensity	MeanIntensity	MinIntensity
--------------	---------------	--------------

Example: `BW2 = bwpropfilt(BW, 'EulerNumber', [1 1]);`

Data Types: char

range — Minimum and maximum values of the property inclusive

1-by-2 numeric row vector

Minimum and maximum values of the property inclusive, specified as a 1-by-2 numeric vector of the form `[low high]`.

Example: `BW2 = bwpropfilt(BW, 'EulerNumber', [1 1]);`

Data Types: single | double | int8 | int16 | int32 | int64 | uint8 | uint16 | uint32 | uint64

conn — Connectivity of objects

3-by-3 matrix of 0s and 1s (default) | 4 | 8

Connectivity of objects in the image, specified as the scalar values 4 or 8, or a 3-by-3 matrix of 0s and 1s. 1-valued elements define neighborhood locations relative to the center element of `conn`, which must be symmetric about its center element.

Example:

Data Types: double | logical

n — Number of objects to return

scalar double

Number of object to return, specified as a scalar double.

Example: `BW2 = bwpropfilt(BW, 'Perimeter', 5);`

Data Types: double

keep — Objects to retain

'largest' (default) | 'smallest'

Objects to retain, specified as the text string 'largest' or 'smallest'.

Example: `BW2 = bwpropfilt(BW, 'Perimeter', 5, 'smallest');`

Data Types: char

I — Marker image

grayscale image

Marker image, specified as a grayscale image, the same size as the input binary image. Intensity values in the grayscale image define regions in the input binary image.

Data Types: single | double | int8 | int16 | int32 | int64 | uint8 | uint16 | uint32 | uint64

Output Arguments

BW2 — Filtered image

binary image

Filtered image, returned as a binary image the same size as BW.

See Also

`bwareafilt` | `bwareaopen` | `bwconncomp` | `conndef` | `regionprops`

Introduced in R2014b

bwselect

Select objects in binary image

Syntax

```
BW2 = bwselect(BW,c,r,n)
BW2 = bwselect(BW,n)
[BW2, idx] = bwselect( ___ )
BW2 = bwselect(x,y,BW,xi,yi,n)
[x,y,BW2,idx,xi,yi] = bwselect( ___ )
```

Description

`BW2 = bwselect(BW,c,r,n)` returns a binary image containing the objects that overlap the pixel (r,c) , where n specifies the connectivity. Objects are connected sets of on pixels, that is, pixels having a value of 1. By default, `bwselect` looks for 4-connected objects.

`BW2 = bwselect(BW,n)` displays the image `BW` on the screen and lets you select the (r,c) coordinates using the mouse. If you omit `BW`, `bwselect` operates on the image in the current axes. Use normal button clicks to add points. Press **Backspace** or **Delete** to remove the previously selected point. A shift-click, right-click, or double-click selects the final point; press **Return** to finish the selection without adding a point.

`[BW2, idx] = bwselect(___)` returns the linear indices of the pixels belonging to the selected objects.

`BW2 = bwselect(x,y,BW,xi,yi,n)` uses the vectors `x` and `y` to establish a nondefault spatial coordinate system for `BW`. The arguments `xi` and `yi` are scalars or equal-length vectors that specify locations in this coordinate system.

`[x,y,BW2,idx,xi,yi] = bwselect(___)` returns the `XData` and `YData` in `x` and `y`, the output image in `BW2`, linear indices of all the pixels belonging to the selected objects in `idx`, and the specified spatial coordinates in `xi` and `yi`.

“Code Generation” on page 1-207 support: Yes.

“MATLAB Function Block” on page 1-207 support: Yes.

Examples

Select Objects in Binary Image

Select objects in a binary image and create a new image containing only those objects.

Read binary image into the workspace.

```
BW = imread('text.png');
```

Specify the locations of objects in the image using row and column indices.


```
c = [43 185 212];  
r = [38 68 181];
```

Create a new binary image containing only the selected objects. This example specifies 4-connected objects.

```
BW2 = bwselect(BW,c,r,4);
```

Display the original image and the new image side-by-side.

```
imshowpair(BW,BW2,'montage');
```



Input Arguments

BW — Input binary image

2-D, nonsparse, logical or numeric matrix

Input binary image, specified as a 2-D, nonsparse, logical or numeric matrix. If you do not specify an output argument, `bwselect` displays the output image in a new figure.

Example: `BW = imread('text.png');`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

c — Column index

numeric scalar or vector

Column index, specified as a numeric scalar or vector. If `c` and `r` are equal-length vectors, `BW2` contains the sets of objects overlapping with any of the pixels $(r(k), c(k))$.

Example: `c = [43 185 212];`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

r — Row index

numeric scalar or vector

Row index, specified as a numeric scalar or vector. If `r` and `c` are equal-length vectors, `BW2` contains the sets of objects overlapping with any of the pixels $(r(k), c(k))$.

Example: `r = [38 68 181];`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

n — Connectivity

8 (default) | 4

Connectivity, specified as either the value 4 or 8.

Value	Description
4	4-connected objects
8	8-connected objects

Example: `BW2 = bwselect(BW,c,r,4);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

x — x coordinates of nondefault coordinate system

numeric scalar or vector

`x` coordinates of nondefault coordinate system, specified as a numeric scalar or vector.

Example: `x = [19.5 23.5];`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

y — y coordinates of nondefault coordinate system

numeric scalar or vector

`y` coordinates of nondefault coordinate system, specified as a numeric scalar or vector.

Example: `y = [8.0 12.0];`

Data Types: `single | double | int8 | int16 | int32 | int64 | uint8 | uint16 | uint32 | uint64`

`xi` — `x` coordinates of locations in nondefault coordinate system

numeric scalar or vector

`x` coordinates of locations in nondefault coordinate system, specified as a numeric scalar or vector.

Example: `x = [19.5 23.5];`

Data Types: `single | double | int8 | int16 | int32 | int64 | uint8 | uint16 | uint32 | uint64`

`yi` — `y` coordinates of locations in nondefault coordinate system

numeric scalar or vector

`y` coordinates of locations in nondefault coordinate system, specified as a numeric scalar or vector.

Example: `y = [8.0 12.0];`

Data Types: `single | double | int8 | int16 | int32 | int64 | uint8 | uint16 | uint32 | uint64`

Output Arguments

`BW2` — Binary image containing objects that overlap the specified pixels

logical array

Binary image containing objects that overlap the specified pixels, returned as a logical array.

If you do not specify an output argument, `bwselect` displays the output image in a new figure.

`idx` — Linear indices of the pixels belonging to the selected objects

numeric vector

Linear indices of the pixels belonging to the selected objects, returned as a numeric vector.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, `bwselect` only supports the following syntaxes:

- `BW2 = bwselect(BW, c, r)`
- `[BW2, idx] = bwselect(BW, c, r)`
- `BW2 = bwselect(BW, c, r, n)`
- `[BW2, idx] = bwselect(BW, c, r, n)`

In addition, the optional fourth input argument, `n`, must be a compile-time constant. .

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`bwlabel` | `imfill` | `impixel` | `regionfill` | `roipoly`

Introduced before R2006a

bwtraceboundary

Trace object in binary image


Syntax

```
B = bwtraceboundary(BW,P,fstep)
B = bwtraceboundary(bw,P,fstep,conn)
B = bwtraceboundary(bw,P,fstep,conn,n,dir)
```

Description

`B = bwtraceboundary(BW,P,fstep)` traces the outline of an object in binary image `bw`. Nonzero pixels belong to an object and 0 pixels constitute the background. `P` is a two-element vector specifying the row and column coordinates of the point on the object boundary where you want the tracing to begin.

`fstep` is a string specifying the initial search direction for the next object pixel connected to `P`. You use strings such as 'N' for north, 'NE' for northeast, to specify the direction. The following figure illustrates all the possible values for `fstep`.



`bwtraceboundary` returns `B`, a `Q`-by-2 matrix, where `Q` is the number of boundary pixels for the region. `B` holds the row and column coordinates of the boundary pixels.

`B = bwtraceboundary(bw,P,fstep,conn)` specifies the connectivity to use when tracing the boundary. `conn` can have either of the following scalar values.

Value	Meaning
4	4-connected neighborhood Note: With this connectivity, <code>fstep</code> is limited to the following values: 'N', 'E', 'S', and 'W'.
8	8-connected neighborhood. This is the default.

`B = bwtraceboundary(bw,P,fstep,conn,n,dir)` specifies `n`, the maximum number of boundary pixels to extract, and `dir`, the direction in which to trace the boundary. When `n` is set to `Inf`, the default value, the algorithm identifies all the pixels on the boundary. `dir` can have either of the following values:

Value	Meaning
'clockwise'	Search in a clockwise direction. This is the default.
'counterclockwise'	Search in counterclockwise direction.

“Code Generation” on page 1-211 support: Yes.

MATLAB Function Block support: No.

Class Support


`BW` can be logical or numeric and it must be real, 2-D, and nonsparse. `B`, `P`, `conn`, and `N` are of class `double`. `dir` and `fstep` are strings.

Examples

Trace Boundary and Visualize Contours

Read image and display it.

```
BW = imread('blobs.png');
imshow(BW,[]);
```




Pick an object in the image and trace the boundary. To select an object, specify a pixel on its boundary. This example uses the coordinates of a pixel on the boundary of the thick white circle, obtained through visual inspection using `impixelinfo`. The example specifies the initial search direction, the connectivity, how many boundary pixels should be returned, and the direction in which to perform the search.

```
r = 163;  
c = 37;  
contour = bwtraceboundary(BW,[r c], 'W',8,Inf, 'counterclockwise');
```

Plot the contour on the image.

```
hold on;  
plot(contour(:,2),contour(:,1), 'g', 'LineWidth',2);
```

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic `MATLAB Host Computer` target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, the `dir`, `fstep`, and `conn` arguments must be compile-time constants.

See Also

`bwboundaries` | `bwperim`

Introduced before R2006a

bwulterode

Ultimate erosion

Syntax

```
BW2 = bwulterode(BW)
BW2 = bwulterode(BW,method,conn)
```

Description

`BW2 = bwulterode(BW)` computes the ultimate erosion of the binary image `BW`. The ultimate erosion of `BW` consists of the regional maxima of the Euclidean distance transform of the complement of `BW`. The default connectivity for computing the regional maxima is 8 for two dimensions, 26 for three dimensions, and `conndef(ndims(BW), 'maximal')` for higher dimensions.

`BW2 = bwulterode(BW,method,conn)` specifies the distance transform method and the regional maxima connectivity. *method* can be one of the strings 'euclidean', 'cityblock', 'chessboard', and 'quasi-euclidean'.

`conn` can have any of the following scalar values.

Value	Meaning
Two-dimensional connectivities	
4	4-connected neighborhood
8	8-connected neighborhood
Three-dimensional connectivities	
6	6-connected neighborhood
18	18-connected neighborhood
26	26-connected neighborhood

Connectivity can be defined in a more general way for any dimension by using for `conn` a 3-by-3-by... - by-3 matrix of 0's and 1's. The 1-valued elements define neighborhood

locations relative to the center element of `conn`. Note that `conn` must be symmetric about its center element.

Class Support

BW can be numeric or logical and it must be nonsparse. It can have any dimension. The return value BW2 is always a logical array.

Examples

```
originalBW = imread('circles.png');  
imshow(originalBW)  
ultimateErosion = bwulterode(originalBW);  
figure, imshow(ultimateErosion)
```

See Also

[bwdist](#) | [conndef](#) | [imregionalmax](#)

Introduced before R2006a

bwunpack

Unpack binary image

Syntax

```
BW = bwunpack(BWP,m)
```

Description

`BW = bwunpack(BWP,m)` unpacks the packed binary image `BWP`. `BWP` is a `uint32` array. When it unpacks `BWP`, `bwunpack` maps the least significant bit of the first row of `BWP` to the first pixel in the first row of `BW`. The most significant bit of the first element of `BWP` maps to the first pixel in the 32nd row of `BW`, and so on. `BW` is `M`-by-`N`, where `N` is the number of columns of `BWP`. If `m` is omitted, its default value is `32*size(BWP,1)`.

Binary image packing is used to accelerate some binary morphological operations, such as dilation and erosion. If the input to `imdilate` or `imerode` is a packed binary image, the functions use a specialized routine to perform the operation faster.

`bwpack` is used to create packed binary images.

“Code Generation” on page 1-216 support: Yes.

“MATLAB Function Block” on page 1-216 support: Yes.

Class Support

`BWP` is of class `uint32` and must be real, 2-D, and nonsparse. The return value `BW` is of class `uint8`.

Examples

Pack, dilate, and unpack a binary image.

```
bw = imread('text.png');
```

```
bwp = bwpack(bw);  
bwp_dilated = imdilate(bwp,ones(3,3),'ispacked');  
bw_dilated = bwunpack(bwp_dilated, size(bw,1));
```

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, all input arguments must be compile-time constants.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

The input argument `m` must be compile-time constants.

Tips

- This function supports the generation of C code using MATLAB Coder. The code generated for this function uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, all input arguments must be compile-time constants.

See Also

`bwpack` | `imdilate` | `imerode`

Introduced before R2006a

checkerboard

Create checkerboard image

Syntax

I = checkerboard
I = checkerboard(n)
I = checkerboard(n,p,q)

Description

I = checkerboard creates an 8-by-8 square checkerboard image that has four identifiable corners. Each square has 10 pixels per side. The light squares on the left half of the checkerboard are white. The light squares on the right half of the checkerboard are gray.

I = checkerboard(n) creates a checkerboard image where each square has n pixels per side.

I = checkerboard(n,p,q) creates a rectangular checkerboard where p specifies the number of rows and q specifies the number of columns. If you omit q, it defaults to p and the checkerboard is square.

Each row and column is made up of tiles. Each tile contains four squares, n pixels per side, defined as

TILE = [DARK LIGHT; LIGHT DARK]




The light squares on the left half of the checkerboard are white. The light squares on the right half of the checkerboard are gray.

Examples


Create a checkerboard where the side of every square is 20 pixels in length.

```
I = checkerboard(20); imshow(I)
```




Create a rectangular checkerboard that is 2 tiles in height and 3 tiles wide.

```
J = checkerboard(10,2,3);  
figure, imshow(J)
```



Create a black and white checkerboard.

```
K = (checkerboard > 0.5);  
figure, imshow(K)
```



See Also

[cp2tform](#) | [imtransform](#) | [maketform](#)

Introduced before R2006a

col2im

Rearrange matrix columns into blocks

Syntax

```
A = col2im(B,[m n],[mm nn],'distinct')
A = col2im(B,[m n],[mm nn],'sliding')
```

Description

`A = col2im(B,[m n],[mm nn],'distinct')` rearranges each column of `B` into a distinct `m`-by-`n` block to create the matrix `A` of size `mm`-by-`nn`. If `B = [A11(:) A21(:) A12(:) A22(:)]`, where each column has length `m*n`, then `A = [A11 A12; A21 A22]` where each `Aij` is `m`-by-`n`.

`A = col2im(B,[m n],[mm nn],'sliding')` rearranges the row vector `B` into a matrix of size `(mm-m+1)`-by-`(nn-n+1)`. `B` must be a vector of size `1`-by-`(mm-m+1)*(nn-n+1)`. `B` is usually the result of processing the output of `im2col(...,'sliding')` using a column compression function (such as `sum`).

`col2im(B,[m n],[mm nn])` is the same as `col2im(B,[m n],[mm nn],'sliding')`.

Class Support

`B` can be logical or numeric. The return value `A` is of the same class as `B`.

Examples

```
B = reshape(uint8(1:25),[5 5])'
C = im2col(B,[1 5])
A = col2im(C,[1 5],[5 5],'distinct')
```

See Also

`blockproc` | `im2col` | `colfilt` | `nlfilter`

Introduced before R2006a

colfilt

Columnwise neighborhood operations

Syntax

```
B = colfilt(A,[m n],block_type,fun)
B = colfilt(A,[m n],[mblock nblock],block_type,fun)
B = colfilt(A,'indexed',...)
```

Description

`B = colfilt(A,[m n],block_type,fun)` processes the image `A` by rearranging each `m`-by-`n` block of `A` into a column of a temporary matrix, and then applying the function `fun` to this matrix. `fun` must be a function handle. The function `colfilt` zero-pads `A`, if necessary.

Before calling `fun`, `colfilt` calls `im2col` to create the temporary matrix. After calling `fun`, `colfilt` rearranges the columns of the matrix back into `m`-by-`n` blocks using `col2im`.

`block_type` is a string that can have one of the values listed in this table.

Note: `colfilt` can perform operations similar to `blockproc` and `nlfilter`, but often executes much faster.

Value	Description
'distinct'	Rearranges each <code>m</code> -by- <code>n</code> distinct block of <code>A</code> into a column in a temporary matrix, and then applies the function <code>fun</code> to this matrix. <code>fun</code> must return a matrix the same size as the temporary matrix. <code>colfilt</code> then rearranges the columns of the matrix returned by <code>fun</code> into <code>m</code> -by- <code>n</code> distinct blocks.
'sliding'	Rearranges each <code>m</code> -by- <code>n</code> sliding neighborhood of <code>A</code> into a column in a temporary matrix, and then applies the function <code>fun</code> to this matrix.

Value	Description
	<code>fun</code> must return a row vector containing a single value for each column in the temporary matrix. (Column compression functions such as <code>sum</code> return the appropriate type of output.) <code>colfilt</code> then rearranges the vector returned by <code>fun</code> into a matrix the same size as <code>A</code> .

`B = colfilt(A,[m n],[mblock nblock],block_type,fun)` processes the matrix `A` as above, but in blocks of size `mblock`-by-`nblock` to save memory. Note that using the `[mblock nblock]` argument does not change the result of the operation.

`B = colfilt(A,'indexed',...)` processes `A` as an indexed image, padding with 0's if the class of `A` is `uint8` or `uint16`, or 1's if the class of `A` is `double` or `single`.

Note To save memory, the `colfilt` function might divide `A` into subimages and process one subimage at a time. This implies that `fun` may be called multiple times, and that the first argument to `fun` may have a different number of columns each time.

Class Support

The input image `A` can be of any class supported by `fun`. The class of `B` depends on the class of the output from `fun`.

Examples

Set each output pixel to the mean value of the input pixel's 5-by-5 neighborhood.

```
I = imread('tire.tif');
I2 = uint8(colfilt(I,[5 5],'sliding',@mean));
figure
subplot(1,2,1), imshow(I), title('Original Image')
subplot(1,2,2), imshow(I2), title('Filtered Image')
```

Original Image



Filtered Image



More About

- “Anonymous Functions”
- “Parameterizing Functions”
- “Create Function Handle”

See Also

`blockproc` | `col2im` | `im2col` | `nlfilter`

Introduced before R2006a

conndef

Create connectivity array

Syntax

```
conn = conndef(num_dims,type)
```

Description

`conn = conndef(num_dims,type)` returns the connectivity array defined by `type` for `num_dims` dimensions. Several Image Processing Toolbox functions use `conndef` to create the default connectivity input argument.

“Code Generation” on page 1-226 support: Yes.

“MATLAB Function Block” on page 1-226 support: Yes.

Examples

Create 2-D Connectivity Array with Minimal Connectivity

Create a 2-D connectivity array.

```
conn = conndef(2,'minimal')
```

```
conn =
```

```
    0     1     0
    1     1     1
    0     1     0
```

Create 2-D Connectivity Array with Maximal Connectivity

Create a 2-D connectivity array.

```
conn = conndef(2,'maximal')
```

```
conn =
```

```
    1    1    1
    1    1    1
    1    1    1
```

Create 3-D Connectivity Array with Minimal Connectivity

Create a 3-D connectivity array.

```
conndef(3, 'minimal')
```

```
ans(:,:,1) =
```

```
    0    0    0
    0    1    0
    0    0    0
```

```
ans(:,:,2) =
```

```
    0    1    0
    1    1    1
    0    1    0
```

```
ans(:,:,3) =
```

```
    0    0    0
    0    1    0
    0    0    0
```

Input Arguments

num_dims — Number of dimensions

numeric scalar

Number of dimensions, specified as a numeric scalar.

Example: `conn1 = conndef(2, 'minimal')`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

type — Type of neighborhood connectivity

'minimal' | 'maximal'

Type of neighborhood connectivity, specified as the string 'minimal' or 'maximal'

Value	Description
'minimal'	Defines a neighborhood whose neighbors are touching the central element on an (N-1)-dimensional surface, for the N-dimensional case.
'maximal'	Defines a neighborhood including neighbors that touch the central element in any way; it is <code>ones(repmat(3,1,NUM_DIMS))</code> .

Example: `conn1 = conndef(2,'minimal')`

Data Types: `char`

Output Arguments

conn — Connectivity matrix

3-by-3-by...-3 logical array

Connectivity matrix, returned as a 3-by-3-...-by-3 logical array.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, the `num_dims` and `type` arguments must be compile-time constants.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

Introduced before R2006a

convmtx2

2-D convolution matrix

Syntax

```
T = convmtx2(H,m,n)
T = convmtx2(H,[m n])
```

Description

`T = convmtx2(H,m,n)` returns the convolution matrix `T` for the matrix `H`. If `X` is an `m`-by-`n` matrix, then `reshape(T*X(:),size(H)+[m n]-1)` is the same as `conv2(X,H)`.

`T = convmtx2(H,[m n])` returns the convolution matrix, where the dimensions `m` and `n` are a two-element vector.

Class Support

The inputs are all of class `double`. The output matrix `T` is of class `sparse`. The number of nonzero elements in `T` is no larger than `prod(size(H))*m*n`.

See Also

`conv2` | `convmtx`

Introduced before R2006a

corner

Find corner points in image

Compatibility

`corner` is not recommended. Use `detectHarrisFeatures` or `detectMinEigenFeatures` in Computer Vision System Toolbox™ instead.

Syntax

```
C = corner(I)
C = corner(I,method)
C = corner(I,N)
C = corner(I,method,N)
C = corner( ____,Name,Value,...)
```

Description

`C = corner(I)` detects corners in image `I` and returns them in matrix `C`.

`C = corner(I,method)` detects corners in image `I` using the specified `method`.

`C = corner(I,N)` detects corners in image `I` and returns a maximum of `N` corners.

`C = corner(I,method,N)` detects corners using the specified `method` and maximum number of corners.

`C = corner(____,Name,Value,...)` specifies parameters and corresponding values that control various aspects of the corner detection algorithm.

Input Arguments

I

A grayscale or binary image.

method

The algorithm used to detect corners. Supported methods are:

- 'Harris': The Harris corner detector.
- 'MinimumEigenvalue': Shi & Tomasi's minimum eigenvalue method.

Default: 'Harris'

N

The maximum number of corners the `corner` function can return.

Default: 200

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

'FilterCoefficients'

A vector, `V`, of filter coefficients for the separable smoothing filter. The outer product, `V*V'`, gives the full filter kernel. The length of the vector must be odd and at least 3.

Default: `fspecial('gaussian',[5 1],1.5)`

'QualityLevel'

A scalar value, `Q`, where $0 < Q < 1$, specifying the minimum accepted quality of corners. When candidate corners have corner metric values less than $Q * \max(\text{corner metric})$, the toolbox rejects them. Use larger values of `Q` to remove erroneous corners.

Default: 0.01

'SensitivityFactor'

A scalar value, `K`, where $0 < K < 0.25$, specifying the sensitivity factor used in the Harris detection algorithm. The smaller the value of `K`, the more likely the algorithm is to detect sharp corners. Use this parameter with the 'Harris' method only.

Default: 0.04

Output Arguments

C

An M -by-2 matrix containing the X and Y coordinates of the corner points detected in **I**.


Class Support

I is a nonsparse numeric array. **C** is a matrix of class `double`.

Examples

Find and plot corner points in a checkerboard image.

```
I = checkerboard(50,2,2);  
C = corner(I);  
imshow(I);  
hold on  
plot(C(:,1), C(:,2), 'r*');
```



More About

Tips

The `corner` and `cornermetric` functions both detect corners in images. For most applications, use the streamlined `corner` function to find corners in one step. If you want greater control over corner selection, use the `cornermetric` function to compute a corner metric matrix and then write your own algorithm to find peak values.

Algorithms

The `corner` function performs nonmaxima suppression on candidate corners, and corners are at least two pixels apart.

•

Introduced in R2010b

cornermetric

Create corner metric matrix from image

Compatibility

cornermetric is not recommended. Use detectHarrisFeatures or detectMinEigenFeatures and the cornerPoints class in Computer Vision System Toolbox instead.

Description

`C = cornermetric(I)` generates a corner metric matrix for the grayscale or logical image `I`. The corner metric, `C`, is used to detect corner features in `I` and is the same size as `I`. Larger values in `C` correspond to pixels in `I` with a higher likelihood of being a corner feature.

`C = cornermetric(I, method)` generates a corner metric matrix for the grayscale or logical image `I` using the specified `method`. Valid values for `method` are:

Value	Description
'Harris'	The Harris corner detector. This is the default method.
'MinimumEigenvalue'	Shi and Tomasi's minimum eigenvalue method.

`C = cornermetric(..., param1, val1, param2, val2, ...)` generates a corner metric matrix for `I`, specifying parameters and corresponding values that control various aspects of the corner metric calculation algorithm. Parameters include:

Parameter	Description
'FilterCoefficients'	A vector, <code>V</code> , of filter coefficients for the separable smoothing filter. This parameter is valid with the 'Harris' and 'MinimumEigenvalue' methods.

Parameter	Description
	The outer product, $V*V'$, gives the full filter kernel. The length of the vector must be odd and at least 3. The default is <code>fspecial('gaussian',[5 1],1.5)</code> .
'SensitivityFactor'	A scalar k , $0 < k < 0.25$, specifying the sensitivity factor used in the Harris detection algorithm. For smaller values of k , the algorithm is more likely to detect sharper corners. This parameter is only valid with the 'Harris' method. Default value: 0.04

Class Support

`I` is a nonsparse numeric array. `C` is a matrix of class `double`.

Examples

Find Corner Features in Grayscale Image

Read image and use part of it for processing.

```
I = imread('pout.tif');  
I = I(1:150,1:120);  
subplot(1,3,1);  
imshow(I);  
title('Original Image');
```


Original Image



Generate a corner metric matrix.

```
C = cornermetric(I);
```

Adjust the corner metric for viewing.

```
C_adjusted = imadjust(C);  
subplot(1,3,2);  
imshow(C_adjusted);  
title('Corner Metric');
```

Original Image




Corner Metric



Find and display corner features.

```
corner_peaks = imregionalmax(C);  
corner_idx = find(corner_peaks == true);  
[r g b] = deal(I);  
r(corner_idx) = 255;  
g(corner_idx) = 255;  
b(corner_idx) = 0;  
RGB = cat(3,r,g,b);  
subplot(1,3,3);  
imshow(RGB);  
title('Corner Points');
```



More About

Tips

The `corner` and `cornermetric` functions both detect corners in images. For most applications, use the streamlined `corner` function to find corners in one step. If you want greater control over corner selection, use the `cornermetric` function to compute a corner metric matrix and then write your own algorithm to find peak values.

See Also

| | [edge](#)

Introduced in R2008b

corr2

2-D correlation coefficient

Syntax

```
r = corr2(A,B)
r = corr2(gpuarrayA,gpuarrayB)
```

Description

`r = corr2(A,B)` returns the correlation coefficient `r` between `A` and `B`, where `A` and `B` are matrices or vectors of the same size. `r` is a scalar **double**.

`r = corr2(gpuarrayA,gpuarrayB)` performs the operation on a GPU. The input images are 2-D `gpuArrays` of the same size. `r` is a scalar **double** `gpuArray`. This syntax requires the Parallel Computing Toolbox.

Class Support

`A` and `B` can be numeric or logical. The return value `r` is a scalar **double**.

`gpuarrayA` and `gpuarrayB` must be real, 2-D `gpuArrays`. If either `A` or `B` is not a `gpuArray`, it must be numeric or logical and nonsparse. `corr2` moves any data not already on the GPU to the GPU. `R` is a scalar **double** `gpuArray`.

Examples

Compute the correlation coefficient

Compute the correlation coefficient between an image and the same image processed with a median filter.

```
I = imread('pout.tif');
J = medfilt2(I);
```

```
R = corr2(I,J)
```

```
R =
```

```
0.9959
```

Compute the Correlation Coefficient on a GPU

Compute the correlation coefficient on a GPU between an image and the same image processed using standard deviation filtering.

```
I = gpuArray(imread('pout.tif'));  
J = stdfilt(I);  
R = corr2(I,J)
```

```
R =
```

```
0.2762
```

More About

Algorithms

`corr2` computes the correlation coefficient using

$$r = \frac{\sum_m \sum_n (A_{mn} - \bar{A})(B_{mn} - \bar{B})}{\sqrt{\left(\sum_m \sum_n (A_{mn} - \bar{A})^2\right)\left(\sum_m \sum_n (B_{mn} - \bar{B})^2\right)}}$$

where $\bar{A} = \text{mean2}(A)$, and $\bar{B} = \text{mean2}(B)$.

See Also

`std2` | `gpuArray` | `corrcoef`

Introduced before R2006a

cp2tform

Infer spatial transformation from control point pairs

Compatibility

cp2tform is not recommended. Use `fitgeotrans` instead.

Syntax

```

TFORM = cp2tform(movingPoints, fixedPoints, transformtype)
TFORM = cp2tform(CPSTRUCT, transformtype)
[TFORM, movingPoints, fixedPoints] = cp2tform(CPSTRUCT, ...)
TFORM = cp2tform(movingPoints, fixedPoints, 'polynomial', order)
TFORM = cp2tform(CPSTRUCT, 'polynomial', order)
TFORM = cp2tform(movingPoints, fixedPoints, 'piecewise linear')
TFORM = cp2tform(CPSTRUCT, 'piecewise linear')
TFORM = cp2tform(movingPoints, fixedPoints, 'lwm', N)
TFORM = cp2tform(CPSTRUCT, 'lwm', N)
[TFORM, movingPoints, fixedPoints, movingPoints_bad,
fixedPoints_bad] = cp2tform(movingPoints, fixedPoints, 'piecewise
linear')
[TFORM, movingPoints, fixedPoints, movingPoints_bad,
fixedPoints_bad] = cp2tform(CPSTRUCT, 'piecewise linear')

```

Description

`TFORM = cp2tform(movingPoints, fixedPoints, transformtype)` infers a spatial transformation from control point pairs and returns this transformation as a `TFORM` structure.

`TFORM = cp2tform(CPSTRUCT, transformtype)` works on a `CPSTRUCT` structure that contains the control point matrices for the input and base images. The Control Point Selection Tool, `cpselect`, creates the `CPSTRUCT`.

[TFORM, movingPoints, fixedPoints] = cp2tform(CPSTRUCT, ...) returns the control points that were used in movingPoints and fixedPoints. Unmatched and predicted points are not used. See cpstruct2pairs.

TFORM = cp2tform(movingPoints, fixedPoints, 'polynomial', order) lets you specify the order of the polynomials to use.

TFORM = cp2tform(CPSTRUCT, 'polynomial', order) works on a CPSTRUCT structure.

TFORM = cp2tform(movingPoints, fixedPoints, 'piecewise linear') creates a Delaunay triangulation of the base control points, and maps corresponding input control points to the base control points. The mapping is linear (affine) for each triangle and continuous across the control points but not continuously differentiable as each triangle has its own mapping.

TFORM = cp2tform(CPSTRUCT, 'piecewise linear') works on a CPSTRUCT structure.

TFORM = cp2tform(movingPoints, fixedPoints, 'lwm', N) creates a mapping by inferring a polynomial at each control point using neighboring control points. The mapping at any location depends on a weighted average of these polynomials. You can optionally specify the number of points, N, used to infer each polynomial. The N closest points are used to infer a polynomial of order 2 for each control point pair. If you omit N, it defaults to 12. N can be as small as 6, but making N small risks generating ill-conditioned polynomials.

TFORM = cp2tform(CPSTRUCT, 'lwm', N) works on a CPSTRUCT structure.

[TFORM, movingPoints, fixedPoints, movingPoints_bad, fixedPoints_bad] = cp2tform(movingPoints, fixedPoints, 'piecewise linear') returns the control points that were used in movingPoints and fixedPoints and the control points that were eliminated because they were middle vertices of degenerate fold-over triangles in movingPoints_bad and fixedPoints_bad.

[TFORM, movingPoints, fixedPoints, movingPoints_bad, fixedPoints_bad] = cp2tform(CPSTRUCT, 'piecewise linear') works on a CPSTRUCT structure.

Input Arguments

movingPoints

m-by-2, **double** matrix containing the *x*- and *y*-coordinates of control points in the image you want to transform.




fixedPoints





m-by-2, **double** matrix containing the *x*- and *y*-coordinates of control points in the base image.

transformtype

Specifies the type of spatial transformation to infer. The `cp2tform` function requires a minimum number of control point pairs to infer a structure of each transform type. The following table lists all the transformation types supported by `cp2tform` in order of complexity. The `'lwm'` and `'polynomial'` transform types can each take an optional, additional parameter.

Transformation Types

Transformation Type	Description	Minimum Number of Control Point Pairs	Example
'nonreflective similarity'	Use this transformation when shapes in the input image are unchanged, but the image is distorted by some combination of translation, rotation, and scaling. Straight lines remain straight, and parallel lines are still parallel.	2	
'similarity'	Same as 'nonreflective similarity' with the addition of optional reflection.	3	
'affine'	Use this transformation when shapes in the input image exhibit shearing. Straight lines remain straight, and parallel lines remain parallel, but rectangles become parallelograms.	3	

Transformation Type	Description	Minimum Number of Control Point Pairs	Example
'projective'	Use this transformation when the scene appears tilted. Straight lines remain straight, but parallel lines converge toward vanishing points that might or might not fall within the image.	4	
'polynomial'	Use this transformation when objects in the image are curved. The higher the order of the polynomial, the better the fit, but the result can contain more curves than the base image.	6 (order 2) 10 (order 3) 15 (order 4)	
'piecewise linear'	Use this transformation when parts of the image appear distorted differently.	4	
'lwm'	Use this transformation (local weighted mean), when the distortion varies locally and piecewise linear is not sufficient.	6 (12 recommended)	

CPSTRUCT

Structure containing control point matrices for the input and base images. Use the Control Point Selection Tool (`cpselect`) to create the **CPSTRUCT**.

'polynomial', order

Specifies the order of polynomials to use. `order` can be 2, 3, or 4.

Default: 3

'piecewise linear'

Linear for each piece and continuous, not continuously differentiable.

'lwm'

Local weighted mean.

N

Number of points.

Output Arguments

TFORM

Structure containing the spatial transformation.

movingPoints

Input control points that were used to infer the spatial transformation. Unmatched and predicted points are not used.

fixedPoints

Base control points that were used to infer the spatial transformation. Unmatched and predicted points are not used.

movingPoints_bad

Input control points that were eliminated because they were determined to be outliers.

fixedPoints_bad

Base control points that were eliminated because they were determined to be outliers.

Examples

Transform an image, use the `cp2tform` function to return the transformation, and compare the angle and scale of the `TFORM` to the angle and scale of the original transformation:

```
I = checkerboard;
J = imrotate(I,30);
fixedPoints = [11 11; 41 71];
movingPoints = [14 44; 70 81];
cpselect(J,I,movingPoints,fixedPoints);

t = cp2tform(movingPoints,fixedPoints,'nonreflective similarity');

% Recover angle and scale by checking how a unit vector
% parallel to the x-axis is rotated and stretched.
u = [0 1];
v = [0 0];
```

```
[x, y] = tformfwd(t, u, v);  
dx = x(2) - x(1);  
dy = y(2) - y(1);  
angle = (180/pi) * atan2(dy, dx)  
scale = 1 / sqrt(dx^2 + dy^2)
```

More About

Tips

- When `transformtype` is 'nonreflective similarity', 'similarity', 'affine', 'projective', or 'polynomial', and `movingPoints` and `fixedPoints` (or `CPSTRUCT`) have the minimum number of control points needed for a particular transformation, `cp2tform` finds the coefficients exactly.
- If `movingPoints` and `fixedPoints` have more than the minimum number of control points, a least-squares solution is found. See `mldivide`.
- When either `movingPoints` or `fixedPoints` has a large offset with respect to their origin (relative to range of values that it spans), `cp2tform` shifts the points to center their bounding box on the origin before fitting a `TFORM` structure. This enhances numerical stability and is handled transparently by wrapping the origin-centered `TFORM` within a custom `TFORM` that automatically applies and undoes the coordinate shift as needed. As a result, `fields(T)` can give different results for different coordinate inputs, even for the same transformation type.

Algorithms

`cp2tform` uses the following general procedure:

- 1 Use valid pairs of control points to infer a spatial transformation or an inverse mapping from output space (x,y) to input space (x,y) according to `transformtype`.
- 2 Return the `TFORM` structure containing spatial transformation.

The procedure varies depending on the `transformtype`.

Nonreflective Similarity

Nonreflective similarity transformations can include a rotation, a scaling, and a translation. Shapes and angles are preserved. Parallel lines remain parallel. Straight lines remain straight.

Let

```
sc = scale*cos(angle)
```

```
ss = scale*sin(angle)
```

$$[u \ v] = [x \ y \ 1] * \begin{bmatrix} sc & -ss \\ ss & sc \\ tx & ty \end{bmatrix}$$

Solve for `sc`, `ss`, `tx`, and `ty`.

Similarity

Similarity transformations can include rotation, scaling, translation, and reflection. Shapes and angles are preserved. Parallel lines remain parallel. Straight lines remain straight.

Let

```
sc = s*cos(theta)
```

```
ss = s*sin(theta)
```

$$[u \ v] = [x \ y \ 1] * \begin{bmatrix} sc & -a*ss \\ ss & a*sc \\ tx & ty \end{bmatrix}$$

Solve for `sc`, `ss`, `tx`, `ty`, and `a`. If `a = -1`, reflection is included in the transformation. If `a = 1`, reflection is not included in the transformation.

Affine

In an affine transformation, the x and y dimensions can be scaled or sheared independently and there can be a translation. Parallel lines remain parallel. Straight lines remain straight. Nonreflective similarity transformations are a subset of affine transformations.

For an affine transformation,

$$[u \ v] = [x \ y \ 1] * T_{inv}$$

`Tinv` is a 3-by-2 matrix. Solve for the six elements of `Tinv`:

```
t_affine = cp2tform(movingPoints, fixedPoints, 'affine');
```

The coefficients of the inverse mapping are stored in `t_affine.tdata.Tinv`.

At least three control-point pairs are needed to solve for the six unknown coefficients.

Projective

In a projective transformation, quadrilaterals map to quadrilaterals. Straight lines remain straight. Affine transformations are a subset of projective transformations.

For a projective transformation,

$$[u\ v\ w] = [x\ y\ z] * Tinv$$

where

$$u = up/wp$$

$$v = vp/wp$$

`Tinv` is a 3-by-3 matrix.

Assuming

$$Tinv = \begin{bmatrix} A & D & G; \\ B & E & H; \\ C & F & I \end{bmatrix};$$
$$u = (Ax + By + C)/(Gx + Hy + I)$$
$$v = (Dx + Ey + F)/(Gx + Hy + I)$$

Solve for the nine elements of `Tinv`:

```
t_proj = cp2tform(movingPoints, fixedPoints, 'projective');
```

The coefficients of the inverse mapping are stored in `t_proj.tdata.Tinv`.

At least four control-point pairs are needed to solve for the nine unknown coefficients.

Note: An affine or projective transformation can also be expressed like this, for a 3-by-2 `Tinv`:

$$[u\ v]' = Tinv' * [x\ y\ 1]'$$

Or, like this, for a 3-by-3 `Tinv`:

$$[u\ v\ 1]' = Tinv' * [x\ y\ 1]'$$

Polynomial

In a polynomial transformation, polynomial functions of x and y determine the mapping.

Second-Order Polynomials

For a second-order polynomial transformation,

$$[u \ v] = [1 \ x \ y \ x*y \ x^2 \ y^2] * T_{inv}$$

Both u and v are second-order polynomials of x and y . Each second-order polynomial has six terms. To specify all coefficients, T_{inv} has size 6-by-2.

```
t_poly_ord2 = cp2tform(movingPoints, fixedPoints, 'polynomial');
```

The coefficients of the inverse mapping are stored in `t_poly_ord2.tdata`.

At least six control-point pairs are needed to solve for the 12 unknown coefficients.

Third-Order Polynomials

For a third-order polynomial transformation:

$$[u \ v] = [1 \ x \ y \ x*y \ x^2 \ y^2 \ y*x^2 \ x*y^2 \ x^3 \ y^3] * T_{inv}$$

Both u and v are third-order polynomials of x and y . Each third-order polynomial has 10 terms. To specify all coefficients, T_{inv} has size 10-by-2.

```
t_poly_ord3 = cp2tform(movingPoints, fixedPoints, 'polynomial',3);
```

The coefficients of the inverse mapping are stored in `t_poly_ord3.tdata`.

At least ten control-point pairs are needed to solve for the 20 unknown coefficients.

Fourth-Order Polynomials

For a fourth-order polynomial transformation:

$$[u \ v] = [1 \ x \ y \ x*y \ x^2 \ y^2 \ y*x^2 \ x*y^2 \ x^3 \ y^3 \ x^3*y \ x^2*y^2 \ x*y^3 \ x^4 \ y^4] * T_{inv}$$

Both u and v are fourth-order polynomials of x and y . Each fourth-order polynomial has 15 terms. To specify all coefficients, T_{inv} has size 15-by-2.

```
t_poly_ord4 = cp2tform(movingPoints, fixedPoints, 'polynomial',4);
```

Fourth-Order Polynomials

The coefficients of the inverse mapping are stored in `t_poly_ord4.tdata`.

At least 15 control-point pairs are needed to solve for the 30 unknown coefficients.

Piecewise Linear

In a piecewise linear transformation, linear (affine) transformations are applied separately to each triangular region of the image[1].

- 1 Find a Delaunay triangulation of the base control points.
- 2 Using the three vertices of each triangle, infer an affine mapping from base to input coordinates.

Note At least four control-point pairs are needed. Four pairs result in two triangles with distinct mappings.

Local Weighted Mean

For each control point in `fixedPoints`:

- 1 Find the N closest control points.
- 2 Use these N points and their corresponding points in `movingPoints` to infer a second-order polynomial.
- 3 Calculate the radius of influence of this polynomial as the distance from the center control point to the farthest point used to infer the polynomial (using `fixedPoints`)[2].

Note At least six control-point pairs are needed to solve for the second-order polynomial. Ill-conditioned polynomials might result if too few pairs are used.

References

- [1] Goshtasby, Ardeshir, "Piecewise linear mapping functions for image registration," *Pattern Recognition*, Vol. 19, 1986, pp. 459-466.

[2] Goshtasby, Ardeshir, "Image registration by local approximation methods," *Image and Vision Computing*, Vol. 6, 1988, pp. 255-261.

See Also

`cpcorr` | `cpselect` | `cpstruct2pairs` | `imtransform` | `tformfwd` | `tforminv`

Introduced before R2006a

cpcorr

Tune control-point locations using cross correlation

Syntax

```
movingPointsAdjusted = cpcorr(movingPoints, fixedPoints, moving, fixed)
```

Description

`movingPointsAdjusted = cpcorr(movingPoints, fixedPoints, moving, fixed)` uses normalized cross correlation to adjust each pair of control points specified in `movingPoints` and `fixedPoints`. `moving` and `fixed` are images. `cpcorr` returns the adjusted control points in `movingPointsAdjusted`.

Note: The `moving` and `fixed` images must have the same scale for `cpcorr` to be effective. If `cpcorr` cannot correlate a pairs of control points, `movingPointsAdjusted` will contain the same coordinates as `movingPoints` for that pair.

Examples

Adjust control points using cross correlation

Use `cpcorr` to fine-tune control points selected in an image. Note the difference in the values of the `movingPoints` matrix and the `movingPointsAdjusted` matrix.

Read two images.

```
moving = imread('onion.png');  
fixed = imread('peppers.png');
```

Define sets of control points for both images.

```
movingPoints = [127 93; 74 59];
```

```
fixedPoints = [323 195; 269 161];
```

Adjust the control points using cross correlation.

```
movingPointsAdjusted = cpcorr(movingPoints, fixedPoints, ...
                             moving(:, :, 1), fixed(:, :, 1))
```

```
movingPointsAdjusted =
```

```
    127    93
     72    60
```

Input Arguments

movingPoints — Coordinates of control points in the image to be transformed

M-by-2 double matrix

Coordinates of control points in the image to be transformed, specified as an *M*-by-2 double matrix.

Example: `movingPoints = [127 93; 74 59];`

Data Types: double

fixedPoints — Coordinates of control points in the reference image

M-by-2 double matrix

Coordinates of control points in the reference image, specified as an *M*-by-2 double matrix.

Example: `fixedPoints = [323 195; 269 161];`

Data Types: double

moving — Image to be registered

numeric array of finite values

Image to be registered, specified as a numeric array of finite values.

fixed — Reference image in the target orientation

numeric array of finite values

Reference image in the target orientation, specified as a numeric array of finite values.

Output Arguments

movingPointsAdjusted — Adjusted coordinates of control points in the image to be transformed

double matrix the same size as `movingPoints`

Adjusted coordinates of control points in the image to be transformed, returned as a double matrix the same size as `movingPoints`.

More About

Tips

`cpcorr` cannot adjust a point if any of the following occur:

- points are too near the edge of either image
- regions of images around points contain `Inf` or `NaN`
- region around a point in moving image has zero standard deviation
- regions of images around points are poorly correlated

Algorithms

`cpcorr` will only move the position of a control point by up to four pixels. Adjusted coordinates are accurate up to one tenth of a pixel. `cpcorr` is designed to get subpixel accuracy from the image content and coarse control-point selection.

See Also

`cpselect` | `fitgeotrans` | `imwarp` | `normxcorr2`

Introduced before R2006a

cpselect

Control Point Selection Tool

Syntax

```
cpselect(moving, fixed)
cpselect(moving, fixed, CPSTRUCT_IN)
cpselect(moving, fixed, movingPoints, fixedPoints)
h = cpselect(moving, fixed, ___ )
cpselect( ___ , param1, val1, ___ )
```

Description

`cpselect(moving, fixed)` starts the Control Point Selection Tool, a graphical user interface that enables you to select control points in two related images. `moving` is the image that needs to be warped to bring it into the coordinate system of the `fixed` image. `moving` and `fixed` can be either variables that contain grayscale, truecolor, or binary images, or strings that identify files containing these images. The Control Point Selection Tool returns the control points in a `CPSTRUCT` structure. (For more information, see “Control Point Selection Procedure”.)

`cpselect(moving, fixed, CPSTRUCT_IN)` starts `cpselect` with an initial set of control points that are stored in `CPSTRUCT_IN`. This syntax allows you to restart `cpselect` with the state of control points previously saved in `CPSTRUCT_IN`.

`cpselect(moving, fixed, movingPoints, fixedPoints)` starts `cpselect` with a set of initial pairs of control points. `movingPoints` and `fixedPoints` are m -by-2 matrices that store the `moving` and `fixed` coordinates, respectively.

`h = cpselect(moving, fixed, ___)` returns a handle `h` to the tool. You can use the `close(h)` syntax to close the tool from the command line.

`cpselect(___ , param1, val1, ___)` starts `cpselect`, specifying parameters and corresponding values that control various aspects of the tool. Parameter names can be abbreviated, and case does not matter. Parameters include:

Parameter	Description
'Wait'	<p>Logical scalar that controls whether <code>cpselect</code> waits for the user to finish the task of selecting points. If set to <code>false</code> (the default), you can run <code>cpselect</code> at the same time as you run other programs in MATLAB. If set to <code>true</code>, you must finish the task of selecting points before doing anything else in MATLAB.</p> <p>The value affects the output arguments:</p> <p><code>h = cpselect(...,'Wait',false)</code> returns a handle <code>h</code> to the tool. <code>close(h)</code> closes the tool.</p> <p><code>[moving_out,fixed_out] = cpselect(...,'Wait',true)</code> returns the selected pairs of points. <code>moving_out</code> and <code>fixed_out</code> are P-by-2 matrices that store the moving and fixed image coordinates, respectively.</p>

Class Support

The images can be grayscale, truecolor, or binary. A grayscale image can be `uint8`, `uint16`, `int16`, `single`, or `double`. A truecolor image can be `uint8`, `uint16`, `single`, or `double`. A binary image is of class `logical`.

Examples

Start Control Point Selection tool with saved images.

```
cpselect('westconcordaerial.png','westconcordorthophoto.png')
```

Start Control Point Selection tool with images and control points stored in variables in the workspace.

```
I = checkerboard;  
J = imrotate(I,30);  
fixedPoints = [11 11; 41 71];  
movingPoints = [14 44; 70 81];  
cpselect(J,I,movingPoints,fixedPoints);
```

Register an aerial photo to an orthophoto. Specify the 'wait' parameter to block until control point selection is complete.

```
aerial = imread('westconcordaerial.png');
figure, imshow(aerial)
ortho = imread('westconcordorthophoto.png');
figure, imshow(ortho)
load westconcordpoints % load some points that were already picked

% Ask cpselect to wait for you to pick some more points
[aerial_points,ortho_points] = ...
    cpselect(aerial,'westconcordorthophoto.png',...
            movingPoints,fixedPoints,...
            'Wait',true);

t_concord = fitgeotrans(aerial_points,ortho_points,'projective');
Rortho = imref2d(size(ortho));
aerial_registered = imwarp(aerial,t_concord,'OutputView',Rortho);
figure, imshowpair(aerial_registered,ortho,'blend')
```

More About

Algorithms

cpselect uses the following general procedure for control-point prediction.

- 1 Find all valid pairs of control points.
- 2 Infer a spatial transformation between **moving** and **fixed** control points using method that depends on the number of valid pairs, as follows:

2 pairs	Nonreflective similarity
3 pairs	Affine
4 or more pairs	Projective
- 3 Apply spatial transformation to the new point to generate the predicted point.
- 4 Display predicted point.

See Also

cpcorr | fitgeotrans | imwarp | imtool | cpstruct2pairs

Introduced before R2006a

cpstruct2pairs

Convert CPSTRUCT to valid pairs of control points

Syntax

```
[movingPoints, fixedPoints] = cpstruct2pairs(CPSTRUCT)
```

Description

[movingPoints, fixedPoints] = cpstruct2pairs(CPSTRUCT) takes a CPSTRUCT (produced by cpselect) and returns the arrays of coordinates of valid control point pairs in movingPoints and fixedPoints. cpstruct2pairs eliminates unmatched points and predicted points.

Examples

Start the Control Point Selection Tool, cpselect.

```
aerial = imread('westconcordaerial.png');  
cpselect(aerial(:,:,1), 'westconcordorthophoto.png')
```

Using cpselect, pick control points in the images. Select **Export Points to Workspace** from the **File** menu to save the points to the workspace. On the **Export Points to Workspace** dialog box, check the **Structure with all points** check box and clear **Input points of valid pairs** and **Base points of valid pairs**. Click **OK**. Use cpstruct2pairs to extract the input and base points from the CPSTRUCT.

```
[movingPoints, fixedPoints] = cpstruct2pairs(cpstruct);
```

See Also

cp2tform | cpselect | imtransform

Introduced before R2006a

dct2

2-D discrete cosine transform

Syntax

```
B = dct2(A)
B = dct2(A,m,n)
B = dct2(A,[m n])
```

Description

`B = dct2(A)` returns the two-dimensional discrete cosine transform of `A`. The matrix `B` is the same size as `A` and contains the discrete cosine transform coefficients $B(k_1, k_2)$.

`B = dct2(A,m,n)` pads the matrix `A` with 0's to size `m`-by-`n` before transforming. If `m` or `n` is smaller than the corresponding dimension of `A`, `dct2` truncates `A`.

`B = dct2(A,[m n])` same as above.


Class Support

`A` can be numeric or logical. The returned matrix `B` is of class `double`.

Examples

The commands below compute the discrete cosine transform for the `autumn` image. Notice that most of the energy is in the upper left corner.

```
RGB = imread('autumn.tif');
I = rgb2gray(RGB);
J = dct2(I);
imshow(log(abs(J)),[]), colormap(jet(64)), colorbar
```



Now set values less than magnitude 10 in the DCT matrix to zero, and then reconstruct the image using the inverse DCT function `idct2`.

```
J(abs(J) < 10) = 0;  
K = idct2(J);  
imshow(I)  
figure, imshow(K,[0 255])
```



More About

Algorithms

The discrete cosine transform (DCT) is closely related to the discrete Fourier transform. It is a separable linear transformation; that is, the two-dimensional transform is equivalent to a one-dimensional DCT performed along a single dimension followed by a one-dimensional DCT in the other dimension. The definition of the two-dimensional DCT for an input image A and output image B is

$$B_{pq} = \alpha_p \alpha_q \sum_{m=0}^{M-1} \sum_{n=0}^{N-1} A_{mn} \cos \frac{\pi(2m+1)p}{2M} \cos \frac{\pi(2n+1)q}{2N}, \quad \begin{matrix} 0 \leq p \leq M-1 \\ 0 \leq q \leq N-1 \end{matrix}$$

where

$$\alpha_p = \begin{cases} \frac{1}{\sqrt{M}}, & p = 0 \\ \sqrt{\frac{2}{M}}, & 1 \leq p \leq M-1 \end{cases}$$

and

$$\alpha_q = \begin{cases} \frac{1}{\sqrt{N}}, & q = 0 \\ \sqrt{\frac{2}{N}}, & 1 \leq q \leq N-1 \end{cases}$$

M and N are the row and column size of A , respectively. If you apply the DCT to real data, the result is also real. The DCT tends to concentrate information, making it useful for image compression applications.

This transform can be inverted using `idct2`.

References

- [1] Jain, Anil K., *Fundamentals of Digital Image Processing*, Englewood Cliffs, NJ, Prentice Hall, 1989, pp. 150-153.

[2] Pennebaker, William B., and Joan L. Mitchell, *JPEG: Still Image Data Compression Standard*, Van Nostrand Reinhold, 1993.

See Also

fft2 | idct2 | ifft2

Introduced before R2006a

dctmtx

Discrete cosine transform matrix

Syntax

```
D = dctmtx(n)
```

Description

`D = dctmtx(n)` returns the n -by- n DCT (discrete cosine transform) matrix. $D*A$ is the DCT of the columns of A and $D'*A$ is the inverse DCT of the columns of A (when A is n -by- n).

Class Support

n is an integer scalar of class `double`. D is returned as a matrix of class `double`.

Examples

```
A = im2double(imread('rice.png'));  
D = dctmtx(size(A,1));  
dct = D*A*D';  
figure, imshow(dct)
```

More About

Tips

If A is square, the two-dimensional DCT of A can be computed as $D*A*D'$. This computation is sometimes faster than using `dct2`, especially if you are computing a large number of small DCTs, because D needs to be determined only once.

For example, in JPEG compression, the DCT of each 8-by-8 block is computed. To perform this computation, use `dctmtx` to determine D , and then calculate each DCT

using D^*A^*D' (where A is each 8-by-8 block). This is faster than calling `dct2` for each individual block.

See Also

`dct2`

Introduced before R2006a

deconvblind

Deblur image using blind deconvolution

Syntax

```
[J,PSF] = deconvblind(I, INITPSF)
[J,PSF] = deconvblind(I, INITPSF, NUMIT)
[J,PSF] = deconvblind(I, INITPSF, NUMIT, DAMPAR)
[J,PSF] = deconvblind(I, INITPSF, NUMIT, DAMPAR, WEIGHT)
[J,PSF] = deconvblind(I, INITPSF, NUMIT, DAMPAR, WEIGHT, READOUT)
[J,PSF] = deconvblind(..., FUN, P1, P2,...,PN)
```

Description

`[J,PSF] = deconvblind(I, INITPSF)` deconvolves image `I` using the maximum likelihood algorithm, returning both the deblurred image `J` and a restored point-spread function `PSF`. The restored `PSF` is a positive array that is the same size as `INITPSF`, normalized so its sum adds up to 1. The `PSF` restoration is affected strongly by the size of the initial guess `INITPSF` and less by the values it contains. For this reason, specify an array of 1's as your `INITPSF`.

`I` can be an `N`-dimensional array.

To improve the restoration, `deconvblind` supports several optional parameters, described below. Use `[]` as a placeholder if you do not specify an intermediate parameter.

`[J,PSF] = deconvblind(I, INITPSF, NUMIT)` specifies the number of iterations (default is 10).

`[J,PSF] = deconvblind(I, INITPSF, NUMIT, DAMPAR)` specifies the threshold deviation of the resulting image from the input image `I` (in terms of the standard deviation of Poisson noise) below which damping occurs. The iterations are suppressed for the pixels that deviate within the `DAMPAR` value from their original value. This suppresses the noise generation in such pixels, preserving necessary image details elsewhere. The default value is 0 (no damping).

[J,PSF] = deconvblind(I, INITPSF, NUMIT, DAMPAR, WEIGHT) specifies which pixels in the input image I are considered in the restoration. By default, WEIGHT is a unit array, the same size as the input image. You can assign a value between 0.0 and 1.0 to elements in the WEIGHT array. The value of an element in the WEIGHT array determines how much the pixel at the corresponding position in the input image is considered. For example, to exclude a pixel from consideration, assign it a value of 0 in the WEIGHT array. You can adjust the weight value assigned to each pixel according to the amount of flat-field correction.

[J,PSF] = deconvblind(I, INITPSF, NUMIT, DAMPAR, WEIGHT, READOUT), where READOUT is an array (or a value) corresponding to the additive noise (e.g., background, foreground noise) and the variance of the read-out camera noise. READOUT has to be in the units of the image. The default value is 0.

[J,PSF] = deconvblind(..., FUN, P1, P2, ..., PN), where FUN is a function describing additional constraints on the PSF. FUN must be a function handle.

FUN is called at the end of each iteration. FUN must accept the PSF as its first argument and can accept additional parameters P1, P2, ..., PN. The FUN function should return one argument, PSF, that is the same size as the original PSF and that satisfies the positivity and normalization constraints. The function colfilt zero-pads A, if necessary.

Note The output image J could exhibit ringing introduced by the discrete Fourier transform used in the algorithm. To reduce the ringing, use I = edgetaper(I,PSF) before calling deconvblind.

Resuming Deconvolution

You can use deconvblind to perform a deconvolution that starts where a previous deconvolution stopped. To use this feature, pass the input image I and the initial guess at the PSF, INITPSF, as cell arrays: {I} and {INITPSF}. When you do, the deconvblind function returns the output image J and the restored point-spread function, PSF, as cell arrays, which can then be passed as the input arrays into the next deconvblind call. The output cell array J contains four elements:

J{1} contains I, the original image.

J{2} contains the result of the last iteration.

$J\{3\}$ contains the result of the next-to-last iteration.

$J\{4\}$ is an array generated by the iterative algorithm.

Class Support

I and `INITPSF` can be `uint8`, `uint16`, `int16`, `single`, or `double`. `DAMPAR` and `READOUT` must have the same class as the input image. Other inputs have to be `double`. The output image J (or the first array of the output cell) has the same class as the input image I . The output `PSF` is `double`.

Examples

Deblur an Image Using Blind Deconvolution

Create a sample image with noise.

```
% Set the random number generator back to its default settings for
% consistency in results.
rng default;
```

```
I = checkerboard(8);
PSF = fspecial('gaussian',7,10);
V = .0001;
BlurredNoisy = imnoise(imfilter(I,PSF),'gaussian',0,V);
```

Create a weight array to specify which pixels are included in processing.

```
WT = zeros(size(I));
WT(5:end-4,5:end-4) = 1;
INITPSF = ones(size(PSF));
```





Perform blind deconvolution.

```
[J P] = deconvblind(BlurredNoisy,INITPSF,20,10*sqrt(V),WT);
```

Display the results.

```
subplot(221);imshow(BlurredNoisy);
title('A = Blurred and Noisy');
```

```
subplot(222);imshow(PSF,[]);  
title('True PSF');  
subplot(223);imshow(J);  
title('Deblurred Image');  
subplot(224);imshow(P,[]);  
title('Recovered PSF');
```

A = Blurred and Noisy**True PSF****Deblurred Image****Recovered PSF**

More About

- “Anonymous Functions”
- “Parameterizing Functions”
- “Create Function Handle”

See Also

deconvlucy | deconvreg | deconvwnr | edgetaper | imnoise | otf2psf |
padarray | psf2otf

Introduced before R2006a

deconvlucy

Deblur image using Lucy-Richardson method

Syntax

```
J = deconvlucy(I, PSF)
J = deconvlucy(I, PSF, NUMIT)
J = deconvlucy(I, PSF, NUMIT, DAMPAR)
J = deconvlucy(I, PSF, NUMIT, DAMPAR, WEIGHT)
J = deconvlucy(I, PSF, NUMIT, DAMPAR, WEIGHT, READOUT)
J = deconvlucy(I, PSF, NUMIT, DAMPAR, WEIGHT, READOUT, SUBSMPL)
```

Description

`J = deconvlucy(I, PSF)` restores image `I` that was degraded by convolution with a point-spread function `PSF` and possibly by additive noise. The algorithm is based on maximizing the likelihood of the resulting image `J`'s being an instance of the original image `I` under Poisson statistics.

`I` can be a N-dimensional array.

To improve the restoration, `deconvlucy` supports several optional parameters. Use `[]` as a placeholder if you do not specify an intermediate parameter.

`J = deconvlucy(I, PSF, NUMIT)` specifies the number of iterations the `deconvlucy` function performs. If this value is not specified, the default is 10.

`J = deconvlucy(I, PSF, NUMIT, DAMPAR)` specifies the threshold deviation of the resulting image from the image `I` (in terms of the standard deviation of Poisson noise) below which damping occurs. Iterations are suppressed for pixels that deviate beyond the `DAMPAR` value from their original value. This suppresses the noise generation in such pixels, preserving necessary image details elsewhere. The default value is 0 (no damping).

`J = deconvlucy(I, PSF, NUMIT, DAMPAR, WEIGHT)` specifies the weight to be assigned to each pixel to reflect its recording quality in the camera. A bad pixel is excluded from the solution by assigning it zero weight value. Instead of giving a weight

of unity for good pixels, you can adjust their weight according to the amount of flat-field correction. The default is a unit array of the same size as input image *I*.

`J = deconvlucy(I, PSF, NUMIT, DAMPAR, WEIGHT, READOUT)` specifies a value corresponding to the additive noise (e.g., background, foreground noise) and the variance of the readout camera noise. `READOUT` has to be in the units of the image. The default value is 0.

`J = deconvlucy(I, PSF, NUMIT, DAMPAR, WEIGHT, READOUT, SUBSMPL)`, where `SUBSMPL` denotes subsampling and is used when the `PSF` is given on a grid that is `SUBSMPL` times finer than the image. The default value is 1.

Note The output image *J* could exhibit ringing introduced by the discrete Fourier transform used in the algorithm. To reduce the ringing, use `I = edgetaper(I, PSF)` before calling `deconvlucy`.

Resuming Deconvolution

If *I* is a cell array, it can contain a single numerical array (the blurred image) or it can be the output from a previous run of `deconvlucy`.

When you pass a cell array to `deconvlucy` as input, it returns a 1-by-4 cell array *J*, where

J{1} contains *I*, the original image.

J{2} contains the result of the last iteration.

J{3} contains the result of the next-to-last iteration.

J{4} is an array generated by the iterative algorithm.

Class Support

I and *PSF* can be `uint8`, `uint16`, `int16`, `double`, or `single`. `DAMPAR` and `READOUT` must have the same class as the input image. Other inputs have to be `double`. The output image *J* (or the first array of the output cell) has the same class as the input image *I*.

Examples

```
I = checkerboard(8);
PSF = fspecial('gaussian',7,10);
V = .0001;
BlurredNoisy = imnoise(imfilter(I,PSF),'gaussian',0,V);
WT = zeros(size(I));
WT(5:end-4,5:end-4) = 1;
J1 = deconvlucy(BlurredNoisy,PSF);
J2 = deconvlucy(BlurredNoisy,PSF,20,sqrt(V));
J3 = deconvlucy(BlurredNoisy,PSF,20,sqrt(V),WT);

subplot(221);imshow(BlurredNoisy);
title('A = Blurred and Noisy');
subplot(222);imshow(J1);
title('deconvlucy(A,PSF)');
subplot(223);imshow(J2);
title('deconvlucy(A,PSF,NI,DP)');
subplot(224);imshow(J3);
title('deconvlucy(A,PSF,NI,DP,WT)');
```

References

- [1] Biggs, D.S.C. “Acceleration of Iterative Image Restoration Algorithms.” *Applied Optics*. Vol. 36. Number 8, 1997, pp. 1766–1775.
- [2] Hanisch, R.J., R.L. White, and R.L. Gilliland. “Deconvolution of Hubble Space Telescope Images and Spectra.” *Deconvolution of Images and Spectra* (P.A. Jansson, ed.). Boston, MA: Academic Press, 1997, pp. 310–356.

See Also

deconvblind | deconvreg | deconvwnr | otf2psf | padarray | psf2otf

Introduced before R2006a

deconvreg

Deblur image using regularized filter

Syntax

```
J = deconvreg(I, PSF)
J = deconvreg(I, PSF, NOISEPOWER)
J = deconvreg(I, PSF, NOISEPOWER, LRANGE)
J = deconvreg(I, PSF, NOISEPOWER, LRANGE, REGOP)
[J, LAGRA] = deconvreg(I, PSF, ...)
```

Description

`J = deconvreg(I, PSF)` deconvolves image `I` using the regularized filter algorithm, returning deblurred image `J`. The assumption is that the image `I` was created by convolving a true image with a point-spread function `PSF` and possibly by adding noise. The algorithm is a constrained optimum in the sense of least square error between the estimated and the true images under requirement of preserving image smoothness.

`I` can be a `N`-dimensional array.

`J = deconvreg(I, PSF, NOISEPOWER)` where `NOISEPOWER` is the additive noise power. The default value is 0.

`J = deconvreg(I, PSF, NOISEPOWER, LRANGE)` where `LRANGE` is a vector specifying range where the search for the optimal solution is performed. The algorithm finds an optimal Lagrange multiplier `LAGRA` within the `LRANGE` range. If `LRANGE` is a scalar, the algorithm assumes that `LAGRA` is given and equal to `LRANGE`; the `NP` value is then ignored. The default range is between [1e-9 and 1e9].

`J = deconvreg(I, PSF, NOISEPOWER, LRANGE, REGOP)` where `REGOP` is the regularization operator to constrain the deconvolution. The default regularization operator is the Laplacian operator, to retain the image smoothness. The `REGOP` array dimensions must not exceed the image dimensions; any nonsingleton dimensions must correspond to the nonsingleton dimensions of `PSF`.

`[J, LAGRA] = deconvreg(I, PSF, ...)` outputs the value of the Lagrange multiplier `LAGRA` in addition to the restored image `J`.

Note The output image `J` could exhibit ringing introduced by the discrete Fourier transform used in the algorithm. To reduce the ringing, process the image with the `edgetaper` function prior to calling the `deconvreg` function. For example, `I = edgetaper(I,PSF)`.

Class Support

`I` can be of class `uint8`, `uint16`, `int16`, `single`, or `double`. Other inputs have to be of class `double`. `J` has the same class as `I`.

Examples

```
I = checkerboard(8);
PSF = fspecial('gaussian',7,10);
V = .01;
BlurredNoisy = imnoise(imfilter(I,PSF),'gaussian',0,V);
NOISEPOWER = V*prod(size(I));
[J LAGRA] = deconvreg(BlurredNoisy,PSF,NOISEPOWER);

subplot(221); imshow(BlurredNoisy);
title('A = Blurred and Noisy');
subplot(222); imshow(J);
title('[J LAGRA] = deconvreg(A,PSF,NP)');
subplot(223); imshow(deconvreg(BlurredNoisy,PSF,[],LAGRA/10));
title('deconvreg(A,PSF,[],0.1*LAGRA)');
subplot(224); imshow(deconvreg(BlurredNoisy,PSF,[],LAGRA*10));
title('deconvreg(A,PSF,[],10*LAGRA)');
```

See Also

`deconvblind` | `deconvlucy` | `deconvwnr` | `otf2psf` | `padarray` | `psf2otf`

Introduced before R2006a

deconvwnr

Deblur image using Wiener filter

Syntax

```
J = deconvwnr(I,PSF,NSR)
J = deconvwnr(I,PSF,NCORR,ICORR)
```

Description

`J = deconvwnr(I,PSF,NSR)` deconvolves image `I` using the Wiener filter algorithm, returning deblurred image `J`. Image `I` can be an N-dimensional array. `PSF` is the point-spread function with which `I` was convolved. `NSR` is the noise-to-signal power ratio of the additive noise. `NSR` can be a scalar or a spectral-domain array of the same size as `I`. Specifying 0 for the `NSR` is equivalent to creating an ideal inverse filter.

The algorithm is optimal in a sense of least mean square error between the estimated and the true images.

`J = deconvwnr(I,PSF,NCORR,ICORR)` deconvolves image `I`, where `NCORR` is the autocorrelation function of the noise and `ICORR` is the autocorrelation function of the original image. `NCORR` and `ICORR` can be of any size or dimension, not exceeding the original image. If `NCORR` or `ICORR` are N-dimensional arrays, the values correspond to the autocorrelation within each dimension. If `NCORR` or `ICORR` are vectors, and `PSF` is also a vector, the values represent the autocorrelation function in the first dimension. If `PSF` is an array, the 1-D autocorrelation function is extrapolated by symmetry to all non-singleton dimensions of `PSF`. If `NCORR` or `ICORR` is a scalar, this value represents the power of the noise of the image.

Note The output image `J` could exhibit ringing introduced by the discrete Fourier transform used in the algorithm. To reduce the ringing, use

```
I = edgetaper(I,PSF)
prior to calling deconvwnr.
```

Class Support

I can be of class `uint8`, `uint16`, `int16`, `single`, or `double`. Other inputs have to be of class `double`. J has the same class as I.

Examples

Use `deconvwnr` to Restore an Image

Create a noisy, blurry image and then apply the `deconvwnr` filter to deblur it.

Display the original image.

```
I = im2double(imread('cameraman.tif'));  
imshow(I);  
title('Original Image (courtesy of MIT)');
```




Simulate a motion blur.

```
LEN = 21;
```

```
THETA = 11;  
PSF = fspecial('motion', LEN, THETA);  
blurred = imfilter(I, PSF, 'conv', 'circular');  
figure, imshow(blurred)
```


Simulate additive noise.

```
noise_mean = 0;  
noise_var = 0.0001;  
blurred_noisy = imnoise(blurred, 'gaussian', ...  
                        noise_mean, noise_var);  
figure, imshow(blurred_noisy)  
title('Simulate Blur and Noise')
```




Try restoration assuming no noise.

```
estimated_nsr = 0;  
wnr2 = deconvwnr(blurred_noisy, PSF, estimated_nsr);  
figure, imshow(wnr2)  
title('Restoration of Blurred, Noisy Image Using NSR = 0')
```



Try restoration using a better estimate of the noise-to-signal-power ratio.

```
estimated_nsr = noise_var / var(I(:));  
wnr3 = deconvwnr(blurred_noisy, PSF, estimated_nsr);  
figure, imshow(wnr3)  
title('Restoration of Blurred, Noisy Image Using Estimated NSR');
```



References

"Digital Image Processing", R. C. Gonzalez & R. E. Woods, Addison-Wesley Publishing Company, Inc., 1992.

See Also

[deconvblind](#) | [deconvlucy](#) | [deconvreg](#) | [edgetaper](#) | [otf2psf](#) | [padarray](#) | [psf2otf](#)

Introduced before R2006a

decorrstretch

Apply decorrelation stretch to multichannel image

Syntax

```
S = decorrstretch(A)
S = decorrstretch(A,name,value...)
```

Description

`S = decorrstretch(A)` applies a decorrelation stretch to an `m-by-n-by-nBands` image `A` and returns the result in `S`. `S` has the same size and class as `A`, and the mean and variance in each band are the same as in `A`. `A` can be an RGB image (`nBands = 3`) or can have any number of spectral bands.

The primary purpose of decorrelation stretch is visual enhancement. Decorrelation stretching is a way to enhance the color differences in an image.


`S = decorrstretch(A,name,value...)` applies a decorrelation stretch to the image `A`, subject to optional control parameters.

Examples

Highlight color differences in forest scene

Use decorrelation stretching to highlight elements in a forest image by exaggerating the color differences.

```
[X, map] = imread('forest.tif');
S = decorrstretch(ind2rgb(X,map), 'tol', 0.01);
figure
subplot(1,2,1), imshow(X,map), title('Original Image')
subplot(1,2,2), imshow(S), title('Enhanced Image')
```



Input Arguments

A — Image to be enhanced

nonsparse, real, N-D array

Image to be stretched, specified as a nonsparse, real, N-D array. The image **A** is a multichannel image, such as, an RGB image (`nBands = 3`) or an image with any number of spectral bands.

Example:

Data Types: `single` | `double` | `int16` | `uint8` | `uint16`

Name-Value Pair Arguments

Specify optional comma-separated pairs of **Name**, **Value** arguments. **Name** is the argument name and **Value** is the corresponding value. **Name** must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

Example: `'Mode', 'covariance'`

'Mode' — Decorrelation method

`'correlation'` (default) | `'correlation'` or `'covariance'`

Decorrelation method, specified as the text string 'correlation' or 'covariance'. 'correlation' uses the eigen decomposition of the band-to-band correlation matrix. 'covariance' uses the eigen decomposition of the band-to-band covariance matrix.

Data Types: char

'TargetMean' — Values that the band-means of the output image must match

1-by-nBands vector containing the sample mean of each band (preserving the band-wise means) (default) | real scalar or vector of class double and of length nBands.

Values that the band-means of the output image must match, specified as a real scalar or vector of class double and of length nBands. If values need to be clamped to the standard range of the input/output image class, it can impact the results.

targetmean must be of class double, but uses the same values as the pixels in the input image. For example, if A is class uint8, then 127.5 would be reasonable value.

Data Types: double

'TargetSigma' — Values that the standard deviations of the individual bands of the output image must match

1-by-nBands vector containing the standard deviation of each band (preserving the band-wise variances) (default) | real, positive scalar or vector of class double and of length nBands

Values that the standard deviations of the individual bands of the output image must match, specified as a real, positive scalar or vector of class double and of length nBands. If values need to be clamped to the standard range of the input/output image class, it can impact the results. Ignored for uniform (zero-variance) bands.

targetsigma must be class double, but uses the same values and the pixels in the input image. For example, if A is of class uint8, then and 50.0 would be reasonable value.

Data Types: double

'To1' — Linear contrast stretch to be applied following the decorrelation stretch

one- or two-element real vector of class double

Linear contrast stretch to be applied following the decorrelation stretch, specified as a one- or two-element real vector of class double. Overrides use of TargetMean or TargetSigma. TOL has the same meaning as in stretchlim, where TOL = [LOW_FRACT HIGH_FRACT] specifies the fraction of the image to saturate at low and

high intensities. If you specify `TOL` as a scalar value, then `LOW_FRACT = TOL` and `HIGH_FRACT = 1 - TOL`, saturating equal fractions at low and high intensities. If you do not specify a value for `TOL`, `decorrstretch` omits the linear contrast stretch.

Small adjustments to `TOL` can strongly affect the visual appearance of the output.

Data Types: `double`

'SampleSubs' — **Subset of A used to compute the band-means, covariance, and correlation**
cell array containing two arrays of pixel subscripts `{rowsubs, colsubs}`

Subset of `A` used to compute the band-means, covariance, and correlation, specified as a cell array containing two arrays of pixel subscripts `{rowsubs, colsubs}`. `rowsubs` and `colsubs` are vectors or matrices of matching size that contain row and column subscripts, respectively.

Use this option to reduce the amount of computation, to keep invalid or non-representative pixels from affecting the transformation, or both. For example, you can use `rowsubs` and `colsubs` to exclude areas of cloud cover. If not specified, `decorrstretch` uses all the pixels in `A`.

Data Types: `double`

Output Arguments

S — **Output image**
nonsparse, real, N-D array

`S` has the same size and class as `A`. The mean and variance in each band in `S` are the same as in `A`.

More About

Tips

- The results of a straight decorrelation (without the contrast stretch option) may include values that fall outside the numerical range supported by the class `uint8` or `uint16` (negative values, or values exceeding $2^8 - 1$ or $2^{16} - 1$, respectively). In these cases, `decorrstretch` clamps its output to the supported range.

- For class `double`, `decorrstretch` clamps the output only when you provide a value for `TOL`, specifying a linear contrast stretch followed by clamping to the interval `[0 1]`.
- The optional parameters do not interact, except that a linear stretch usually alters both the band-wise means and band-wise standard deviations. Thus, while you can specify `targetmean` and `targetsigma` along with `TOL`, their effects will be modified.

Algorithms

A decorrelation stretch is a linear, pixel-wise operation in which the specific parameters depend on the values of actual and desired (target) image statistics. The vector `a` containing the value of a given pixel in each band of the input image `A` is transformed into the corresponding pixel `b` in output image `B` as follows:

$$\mathbf{b} = \mathbf{T} * (\mathbf{a} - \mathbf{m}) + \mathbf{m_target}.$$

`a` and `b` are `nBands`-by-1 vectors, `T` is an `nBands`-by-`nBands` matrix, and `m` and `m_target` are `nBands`-by-1 vectors such that

- `m` contains the mean of each band in the image, or in a subset of image pixels that you specify
- `m_target` contains the desired output mean in each band. The default choice is `m_target = m`.

The linear transformation matrix `T` depends on the following:

- The band-to-band sample covariance of the image, or of a subset of the image that you specify (the same subset as used for `m`), represented by matrix `COV`
- A desired output standard deviation in each band. This is conveniently represented by a diagonal matrix, `SIGMA_target`. The default choice is `SIGMA_target = SIGMA`, where `SIGMA` is the diagonal matrix containing the sample standard deviation of each band. `SIGMA` should be computed from the same pixels that were used for `m` and `Cov`, which means simply that:

$$\text{SIGMA}(k,k) = \text{sqrt}(\text{Cov}(k,k)), \quad k = 1, \dots, n\text{Bands}.$$

`Cov`, `SIGMA`, and `SIGMA_target` are `nBands`-by-`nBands`, as are the matrices `Corr`, `LAMBDA`, and `V`, defined below.

The first step in computing `T` is to perform an eigen-decomposition of either the covariance matrix `COV` or the correlation matrix

$\text{Corr} = \text{inv}(\text{SIGMA}) * \text{Cov} * \text{inv}(\text{SIGMA})$.

- In the correlation-based method, Corr is decomposed: $\text{Corr} = V \text{ LAMBDA } V'$.
- In the covariance-based method, Cov is decomposed: $\text{Cov} = V \text{ LAMBDA } V'$.

LAMBDA is a diagonal matrix of eigenvalues and V is the orthogonal matrix that transforms either Corr or Cov to LAMBDA .

The next step is to compute a stretch factor for each band, which is the inverse square root of the corresponding eigenvalue. It is convenient to define a diagonal matrix S containing the stretch factors, such that:

$S(k,k) = 1 / \text{sqrt}(\text{LAMBDA}(k,k))$.

Finally, matrix T is computed from either

$T = \text{SIGMA_target } V \text{ S } V' \text{ inv}(\text{SIGMA})$ (correlation-based method)

or

$T = \text{SIGMA_target } V \text{ S } V'$ (covariance-based method).

The two methods yield identical results if the band variances are uniform.

Substituting T into the expression for b :

$b = m_target + \text{SIGMA_target } V \text{ S } V' \text{ inv}(\text{SIGMA}) * (a - m)$

or

$b = m_target + \text{SIGMA_target } V \text{ S } V' * (a - m)$

and reading from right to left, you can see that the decorrelation stretch:

- 1 Removes a mean from each band
- 2 Normalizes each band by its standard deviation (correlation-based method only)
- 3 Rotates the bands into the eigenspace of Corr or Cov
- 4 Applies a stretch S in the eigenspace, leaving the image decorrelated and normalized in the eigenspace
- 5 Rotates back to the original band-space, where the bands remain decorrelated and normalized

- 6 Rescales each band according to SIGMA_target
- 7 Restores a mean in each band.

See Also

imadjust | stretchlim

Introduced before R2006a

demosaic

Convert Bayer pattern encoded image to truecolor image

Syntax

```
RGB = demosaic(I,sensorAlignment)
```

Description

`RGB = demosaic(I,sensorAlignment)` converts the Bayer pattern encoded image, `I`, to the truecolor image, `RGB`, using gradient-corrected linear interpolation. `sensorAlignment` specifies the Bayer pattern.

A Bayer filter mosaic, or color filter array, refers to the arrangement of color filters that let each sensor in a single-sensor digital camera record only red, green, or blue data. The patterns emphasize the number of green sensors to mimic the human eye's greater sensitivity to green light. The `demosaic` function uses interpolation to convert the two-dimensional Bayer-encoded image into the truecolor image.

“Code Generation” on page 1-292 support: Yes.

“MATLAB Function Block” on page 1-292 support: Yes.

Examples

Convert a Bayer Pattern Encoded Image To an RGB Image

Convert a Bayer pattern encoded image that was photographed by a camera with a sensor alignment of `'bggr'`.

```
I = imread('mandi.tif');  
J = demosaic(I,'bggr');  
imshow(I);  
figure, imshow(J);
```





Input Arguments

I — Bayer-pattern encoded image
M-by-*N* array of intensity values

Bayer-pattern encoded image, specified as an *M*-by-*N* array of intensity values. I must have at least 5 rows and 5 columns.

Data Types: uint8 | uint16 | uint32

sensorAlignment — Bayer pattern
(default) | string

Bayer pattern, specified as one of the strings in the following table. Each string represents the order of the red, green, and blue sensors by describing the four pixels in the upper-left corner of the image (left-to-right, top-to-bottom).

String	2-by-2 Sensor Alignment				
'gbrg'	<table border="1"><tr><td>Green</td><td>Blue</td></tr><tr><td>Red</td><td>Green</td></tr></table>	Green	Blue	Red	Green
Green	Blue				
Red	Green				
'grbg'	<table border="1"><tr><td>Green</td><td>Red</td></tr><tr><td>Blue</td><td>Green</td></tr></table>	Green	Red	Blue	Green
Green	Red				
Blue	Green				
'bggr'	<table border="1"><tr><td>Blue</td><td>Green</td></tr><tr><td>Green</td><td>Red</td></tr></table>	Blue	Green	Green	Red
Blue	Green				
Green	Red				
'rggb'	<table border="1"><tr><td>Red</td><td>Green</td></tr><tr><td>Green</td><td>Blue</td></tr></table>	Red	Green	Green	Blue
Red	Green				
Green	Blue				

Data Types: char

Output Arguments

RGB — RGB image

M-by-*N*-by-3 numeric array

RGB image, returned as an *M*-by-*N*-by-3 numeric array the same class as **I**.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, note the following:

- `sensorAlignment` must be a compile-time constant.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

References

- [1] Malvar, H.S., L. He, and R. Cutler, *High quality linear interpolation for demosaicing of Bayer-patterned color images*. ICASPP, Volume 34, Issue 11, pp. 2274-2282, May 2004.

Introduced in R2007b

dicomanon

Anonymize DICOM file

Syntax

```
dicomanon(file_in, file_out)
dicomanon(..., 'keep', FIELDS)
dicomanon(..., 'update', ATTRS)
dicomanon(..., 'WritePrivate', TF)
dicomanon(..., 'UseVRHeuristic', TF)
```

Description

`dicomanon(file_in, file_out)` removes confidential medical information from the DICOM file `file_in` and creates a new file `file_out` with the modified values. Image data and other attributes are unmodified.

`dicomanon(..., 'keep', FIELDS)` modifies all of the confidential data except for those listed in `FIELDS`, which is a cell array of field names. This syntax is useful for keeping metadata that does not uniquely identify the patient but is useful for diagnostic purposes (e.g., `PatientAge`, `PatientSex`, etc.).

Note Keeping certain fields might compromise patient confidentiality.

`dicomanon(..., 'update', ATTRS)` modifies the confidential data and updates particular confidential data. `ATTRS` is a structure whose fields are the names of the attributes to preserve. The structure values are the attribute values. Use this syntax to preserve the Study/Series/Image hierarchy or to replace a specific value with a more generic property (e.g., remove `PatientBirthDate` but keep a computed `PatientAge`).

`dicomanon(..., 'WritePrivate', TF)` specifies whether `dicomanon` should write nonstandard attributes to the anonymized file. If `TF` is true, `dicomanon` includes private extensions in the file, which could compromise patient confidentiality. The default value is `false`.

`dicomanon(..., 'UseVRHeuristic', TF)` instructs the parser to use a heuristic to help read certain noncompliant files which switch value representation (VR) modes incorrectly. `dicomanon` displays a warning if the heuristic is employed. When `TF` is true (the default), a small number of compliant files will not be read correctly. Set `TF` to false to read these compliant files. Compliant files are always written.

For information about the fields that will be modified or removed, see DICOM Supplement 55 from <http://medical.nema.org/>.

Examples

Remove all confidential metadata from a file.

```
dicomanon('patient.dcm', 'anonymized.dcm')
```

Create a training file.

```
dicomanon('tumor.dcm', 'tumor_anon.dcm', 'keep', ...  
          {'PatientAge', 'PatientSex', 'StudyDescription'})
```

Anonymize a series of images, keeping the hierarchy.

```
values.StudyInstanceUID = dicomuid;  
values.SeriesInstanceUID = dicomuid;  
  
d = dir('*.dcm');  
for p = 1:numel(d)  
    dicomanon(d(p).name, sprintf('anon%d.dcm', p), ...  
              'update', values)  
end
```

See Also

`dicominfo` | `dicomdict` | `dicomdisp` | `dicomwrite` | `dicomlookup` | `dicomread` | `dicomuid`

Introduced before R2006a

dicomdict

Get or set active DICOM data dictionary

Syntax

```
dicomdict('set',dictionary)
dictionary = dicomdict('get')
dicomdict('factory')
```

Description

`dicomdict('set',dictionary)` sets the Digital Imaging and Communications in Medicine (DICOM) data dictionary to the value stored in `dictionary`, a string containing the filename of the dictionary. DICOM-related functions use this dictionary by default, unless a different dictionary is provided at the command line.

`dictionary = dicomdict('get')` returns a string containing the filename of the stored DICOM data dictionary.

`dicomdict('factory')` resets the DICOM data dictionary to its default startup value.

Note The default data dictionary is a MAT-file, `dicom-dict.mat`. The toolbox also includes a text version of this default data dictionary, `dicom-dict.txt`. If you want to create your own DICOM data dictionary, open the `dicom-dict.txt` file in a text editor, modify it, and save it under another name.

Examples

```
dictionary = dicomdict('get')

dictionary =

dicom-dict.mat
```

See Also

dicomanon | dicominfo | dicomdisp | dicomwrite | dicomlookup | dicomread |
dicomuid

Introduced before R2006a

dicomdisp

Display DICOM file structure

Syntax

```
dicomdisp(filename)
dicomdisp( ____,Name,Value)
```

Description

`dicomdisp(filename)` reads the metadata from the compliant DICOM file specified in the string `filename` and displays the metadata at the command prompt. `dicomdisp` can be helpful when debugging issues with DICOM files.

`dicomdisp(____,Name,Value)` reads the metadata using name-value pairs to control aspects of the operation.

Examples

View Metadata from DICOM File

Read the metadata from DICOM file.

```
dicomdisp('CT-MON02-16-ankle.dcm');
```

```
File: B:\matlab\toolbox\images\imdata\CT-MON02-16-ankle.dcm (525436 bytes)
```

```
Read on an IEEE little-endian machine.
```

```
File begins with group 0002 metadata at byte 132.
```

```
Transfer syntax: 1.2.840.10008.1.2 (Implicit VR Little Endian).
```

```
DICOM Information object: 1.2.840.10008.5.1.4.1.1.7 (Secondary Capture Image Storage).
```

Location	Level	Tag	VR	Size	Name	Data
0000132	0	(0002,0000)	UL	4 bytes	- FileMetaInformationGroupLength	*Bin
0000144	0	(0002,0001)	OB	2 bytes	- FileMetaInformationVersion	*Bin
0000158	0	(0002,0002)	UI	26 bytes	- MediaStorageSOPClassUID	[1.2
0000192	0	(0002,0003)	UI	50 bytes	- MediaStorageSOPInstanceUID	[1.2
0000250	0	(0002,0010)	UI	18 bytes	- TransferSyntaxUID	[1.2
0000276	0	(0002,0012)	UI	18 bytes	- ImplementationClassUID	[1.2

0000302	0	(0002,0013)	SH	6 bytes	- ImplementationVersionName	[1_2
0000316	0	(0002,0016)	AE	12 bytes	- SourceApplicationEntityTitle	[CTN
0000336	0	(0008,0000)	UL	4 bytes	- IdentifyingGroupLength	*Bina
0000348	0	(0008,0008)	CS	20 bytes	- ImageType	[DER
0000376	0	(0008,0016)	UI	26 bytes	- SOPClassUID	[1.2
0000410	0	(0008,0018)	UI	50 bytes	- SOPInstanceUID	[1.2
0000468	0	(0008,0020)	DA	10 bytes	- StudyDate	[199
0000486	0	(0008,0021)	DA	10 bytes	- SeriesDate	[199
0000504	0	(0008,0023)	DA	10 bytes	- ContentDate	[199
0000522	0	(0008,0030)	TM	8 bytes	- StudyTime	[11:2
0000538	0	(0008,0031)	TM	8 bytes	- SeriesTime	[11:2
0000554	0	(0008,0033)	TM	8 bytes	- ContentTime	[11:2
0000570	0	(0008,0060)	CS	2 bytes	- Modality	[CT]
0000580	0	(0008,0064)	CS	4 bytes	- ConversionType	[WSD
0000592	0	(0008,0070)	LO	18 bytes	- Manufacturer	[GE M
0000618	0	(0008,0080)	LO	18 bytes	- InstitutionName	[JFK
0000644	0	(0008,0090)	PN	10 bytes	- ReferringPhysicianName	[Anon
0000662	0	(0008,1010)	SH	8 bytes	- StationName	[CTO
0000678	0	(0008,1030)	LO	8 bytes	- StudyDescription	[RT A
0000694	0	(0008,1060)	PN	10 bytes	- PhysicianReadingStudy	[Anon
0000712	0	(0008,1070)	PN	10 bytes	- OperatorName	[Anon
0000730	0	(0008,1090)	LO	12 bytes	- ManufacturerModelName	[GENE
0000750	0	(0010,0000)	UL	4 bytes	- PatientGroupLength	*Bina
0000762	0	(0010,0010)	PN	10 bytes	- PatientName	[Anon
0000780	0	(0018,0000)	UL	4 bytes	- AcquisitionGroupLength	*Bina
0000792	0	(0018,1020)	LO	2 bytes	- SoftwareVersion	[03]
0000802	0	(0020,0000)	UL	4 bytes	- RelationshipGroupLength	*Bina
0000814	0	(0020,000D)	UI	48 bytes	- StudyInstanceUID	[1.2
0000870	0	(0020,000E)	UI	48 bytes	- SeriesInstanceUID	[1.2
0000926	0	(0020,0011)	IS	4 bytes	- SeriesNumber	[365
0000938	0	(0020,0013)	IS	2 bytes	- InstanceNumber	[1]
0000948	0	(0028,0000)	UL	4 bytes	- ImagePresentationGroupLength	*Bina
0000960	0	(0028,0002)	US	2 bytes	- SamplesPerPixel	*Bina
0000970	0	(0028,0004)	CS	12 bytes	- PhotometricInterpretation	[MONO
0000990	0	(0028,0010)	US	2 bytes	- Rows	*Bina
0001000	0	(0028,0011)	US	2 bytes	- Columns	*Bina
0001010	0	(0028,0100)	US	2 bytes	- BitsAllocated	*Bina
0001020	0	(0028,0101)	US	2 bytes	- BitsStored	*Bina
0001030	0	(0028,0102)	US	2 bytes	- HighBit	*Bina
0001040	0	(0028,0103)	US	2 bytes	- PixelRepresentation	*Bina
0001050	0	(0028,0106)	US	2 bytes	- SmallestImagePixelValue	*Bina
0001060	0	(0028,0120)	US	2 bytes	- PixelPaddingValue	*Bina
0001070	0	(0028,1050)	DS	4 bytes	- WindowCenter	[102
0001082	0	(0028,1051)	DS	4 bytes	- WindowWidth	[409

0001094	0	(0028,1052)	DS	6 bytes	- RescaleIntercept	[-1024,1024]
0001108	0	(0028,1053)	DS	2 bytes	- RescaleSlope	[1,1]
0001118	0	(0028,1054)	LO	2 bytes	- RescaleType	[US]
0001128	0	(7FE0,0000)	UL	4 bytes	- PixelDataGroupLength	*Binary
0001140	0	(7FE0,0010)	OW	524288 bytes	- PixelData	[]

Input Arguments

filename — Name of DICOM file

string

Name of DICOM file, specified as a string.

Data Types: char

Name-Value Pair Arguments

Specify optional comma-separated pairs of **Name**, **Value** arguments. **Name** is the argument name and **Value** is the corresponding value. **Name** must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as **Name1**, **Value1**, . . . , **NameN**, **ValueN**.

Example: `dicomdisp('CT-MONO2-16-ankle.dcm','UseVRHeuristic',false)`

'dictionary' — Name of DICOM data dictionary

dicom-dict.txt (default) | string

Name of DICOM data dictionary, specified as a string. When specified, `dicomdisp` uses the data dictionary to read the DICOM file. The file must be on the MATLAB search path.

Data Types: char

'UseVRHeuristic' — Read noncompliant DICOM files that switch VR modes incorrectly

true (default) | false

Read noncompliant DICOM files that switch value representation (VR) modes incorrectly, specified as the Boolean value `true` or `false`. When set to `true`, `dicomdisp` uses a heuristic to help read certain noncompliant DICOM files which switch value representation (VR) modes incorrectly. When `dicomdisp` uses this heuristic, it displays a warning. When set to `true` (the default), `dicomdisp` might not read some compliant DICOM files correctly. To read these compliant files, set `UseVRHeuristic` to `false`.

Data Types: `logical`

More About

- “Explicit Versus Implicit VR Attributes”

See Also

`dicomanon` | `dicomdict` | `dicominfo` | `dicomlookup` | `dicomread` | `dicomuid` | `dicomwrite`

Introduced in R2015a

dicominfo

Read metadata from DICOM message

Syntax

```
info = dicominfo(filename)
info = dicominfo(filename, 'dictionary', D)
info = dicominfo( ____, 'UseVRHeuristic', TF)
info = dicominfo( ____, 'UseDictionaryVR', TF)
```

Description

`info = dicominfo(filename)` reads the metadata from the compliant Digital Imaging and Communications in Medicine (DICOM) file specified in the string `filename`.

`info = dicominfo(filename, 'dictionary', D)` uses the data dictionary file given in the string `D` to read the DICOM message. The file in `D` must be on the MATLAB search path. The default file is `dicom-dict.mat`.

`info = dicominfo(____, 'UseVRHeuristic', TF)` instructs the parser to use a heuristic to help read certain noncompliant files which switch value representation (VR) modes incorrectly. `dicominfo` displays a warning if the heuristic is used. When `TF` is `true` (the default), a small number of compliant files will not be read correctly. Set `TF` to `false` to read these compliant files.

`info = dicominfo(____, 'UseDictionaryVR', TF)` specifies whether the data types in `INFO` should conform to the data dictionary, regardless of what information is present in the file. The default value is `false`, which uses the file's VR codes even if they differ from the data dictionary. Most of the time it is unnecessary to set this field, since file contents and the data dictionary almost always agree. When `TF` is `false` (the default), `dicominfo` issues a warning when they do not agree. Set `TF` to `true` when the warning is issued and providing `info` to `dicomwrite` causes errors.

Examples

```
info = dicominfo('CT-MONO2-16-ankle.dcm')
```

info =

```
        Filename: [1x62 char]
        FileModDate: '18-Dec-2000 11:06:43'
        FileSize: 525436
        Format: 'DICOM'
    FormatVersion: 3
        Width: 512
        Height: 512
        BitDepth: 16
        ColorType: 'grayscale'
    SelectedFrames: []
        FileStruct: [1x1 struct]
    StartOfPixelData: 1140
FileMetaInformationGroupLength: 192
    FileMetaInformationVersion: [2x1 uint8]
        MediaStorageSOPClassUID: '1.2.840.10008.5.1.4.1.1.7'
        .
        .
        .
```

See Also

dicomanon | dicomdict | dicomdisp | dicomwrite | dicomlookup | dicomread |
dicomuid

Introduced before R2006a

dicomlookup

Find attribute in DICOM data dictionary

Syntax

```
name = dicomlookup(group, element)
[group, element] = dicomlookup(name)
```

Description

`name = dicomlookup(group, element)` looks into the current DICOM data dictionary for the attribute with the specified `group` and `element` tag and returns a string containing the `name` of the attribute. `group` and `element` can contain either a decimal value or hexadecimal string.

`[group, element] = dicomlookup(name)` looks into the current DICOM data dictionary for the attribute specified by `name` and returns the `group` and `element` tags associated with the attribute. The values are returned as decimal values.

Examples

Find the names of DICOM attributes using their tags.

```
name1 = dicomlookup('7FE0', '0010')
name2 = dicomlookup(40, 4)
```

Look up a DICOM attribute's tag (GROUP and ELEMENT) using its name.

```
[group, element] = dicomlookup('TransferSyntaxUID')
```

Examine the metadata of a DICOM file. This returns the same value even if the data dictionary changes.

```
metadata = dicominfo('CT-MON02-16-ankle.dcm');
metadata.(dicomlookup('0028', '0004'))
```

See Also

dicomanon | dicomdict | dicomdisp | dicominfo | dicomwrite | dicomread |
dicomuid

Introduced in R2006b

dicomread

Read DICOM image

Syntax

```
X = dicomread(filename)
X = dicomread(info)
[X,map] = dicomread(...)
[X,map,alpha] = dicomread(...)
[X,map,alpha,overlays] = dicomread(...)
[...] = dicomread(filename, 'frames', v)
[...] = dicomread( ____, 'UseVRHeuristic',TF)
```

Description

`X = dicomread(filename)` reads the image data from the compliant Digital Imaging and Communications in Medicine (DICOM) file `filename`. For single-frame grayscale images, `X` is an M-by-N array. For single-frame true-color images, `X` is an M-by-N-by-3 array. Multiframe images are always 4-D arrays.

`X = dicomread(info)` reads the image data from the message referenced in the DICOM metadata structure `info`. The `info` structure is produced by the `dicominfo` function.

`[X,map] = dicomread(...)` returns the image `X` and the colormap `map`. If `X` is a grayscale or true-color image, `map` is empty.

`[X,map,alpha] = dicomread(...)` returns the image `X`, the colormap `map`, and an alpha channel matrix for `X`. The values of `alpha` are 0 if the pixel is opaque; otherwise they are row indices into `map`. The RGB value in `map` should be substituted for the value in `X` to use `alpha`. `alpha` has the same height and width as `X` and is 4-D for a multiframe image.

`[X,map,alpha,overlays] = dicomread(...)` returns the image `X`, the colormap `map`, an alpha channel matrix for `X`, and any overlays from the DICOM file. Each overlay is a 1-bit black and white image with the same height and width as `X`. If multiple

overlays are present in the file, `overlays` is a 4-D multiframe image. If no overlays are in the file, `overlays` is empty.

`[...] = dicomread(filename, 'frames', v)` reads only the frames in the vector `v` from the image. `v` must be an integer scalar, a vector of integers, or the string `'all'`. The default value is `'all'`.

`[...] = dicomread(____, 'UseVRHeuristic', TF)` instructs the parser to use a heuristic to help read certain noncompliant files which switch value representation (VR) modes incorrectly. `dicomread` displays a warning if the heuristic is used. When `TF` is true (the default), a small number of compliant files will not be read correctly. Set `TF` to false to read these compliant files.

Class Support

`X` can be `uint8`, `int8`, `uint16`, or `int16`. `map` must be `double`. `alpha` has the same size and type as `X`. `overlays` is a logical array.

Examples

Use `dicomread` to retrieve the data array, `X`, and colormap matrix, `map`, needed to create a montage.

```
[X, map] = dicomread('US-PAL-8-10x-echo.dcm');  
montage(X, map, 'Size', [2 5]);
```

Call `dicomread` with the information retrieved from the DICOM file using `dicominfo` and display the image using `imshow`. Adjust the contrast of the image using `imcontrast`.

```
info = dicominfo('CT-MON02-16-ankle.dcm');  
Y = dicomread(info);  
figure, imshow(Y);  
imcontrast;
```

More About

Tips

- This function reads imagery from files with one of these pixel formats:

- Little-endian, implicit VR, uncompressed
- Little-endian, explicit VR, uncompressed
- Big-endian, explicit VR, uncompressed
- JPEG (lossy or lossless)
- JPEG2000 (lossy or lossless)
- Run-length Encoding (RLE)
- GE implicit VR, LE with uncompressed BE pixels (1.2.840.113619.5.2)

See Also

dicomanon | dicomdict | dicomdisp | dicominfo | dicomlookup | dicomwrite |
dicomuid

Introduced before R2006a

dicomuid

Generate DICOM unique identifier

Syntax

```
UID = dicomuid
```

Description

`UID = dicomuid` creates a string `UID` containing a new DICOM unique identifier.

Multiple calls to `dicomuid` produce globally unique values. Two calls to `dicomuid` always return different values.

See Also

`dicomanon` | `dicomdict` | `dicomdisp` | `dicominfo` | `dicomlookup` | `dicomread` | `dicomwrite`

Introduced before R2006a

dicomwrite

Write images as DICOM files

Syntax

```
dicomwrite(X, filename)
dicomwrite(X, map, filename)
dicomwrite(..., param1, value1, param2, value2, ...)
dicomwrite(..., 'ObjectType', IOD,...)
dicomwrite(..., 'SOPClassUID', UID,...)
dicomwrite(..., meta_struct,...)
dicomwrite(..., info,...)
status = dicomwrite(...)
```

Description

`dicomwrite(X, filename)` writes the binary, grayscale, or truecolor image `X` to the file `filename`, where `filename` is a string specifying the name of the Digital Imaging and Communications in Medicine (DICOM) file to create.

`dicomwrite(X, map, filename)` writes the indexed image `X` with colormap `map`.

`dicomwrite(..., param1, value1, param2, value2, ...)` specifies optional metadata to write to the DICOM file or parameters that affect how the file is written. `param1` is a string containing the metadata attribute name or a `dicomwrite`-specific option. `value1` is the corresponding value for the attribute or option.

To find a list of the DICOM attributes that you can specify, see the data dictionary file, `dicom-dict.txt`, included with the Image Processing Toolbox software. The following table lists the options that you can specify, in alphabetical order. Default values are enclosed in braces (`{}`).

Option Name	Description
'CompressionMode'	String specifying the type of compression to use when storing the image. Possible values: { 'None' }

Option Name	Description
	'JPEG lossless' 'JPEG lossy' 'JPEG2000 lossy' 'JPEG2000 lossless' 'RLE'
'CreateMode'	Specifies the method used for creating the data to put in the new file. Possible values: {'Create'} — Verify input values and generate missing data values. 'Copy' — Copy all values from the input and do not generate missing values.
'Dictionary'	String specifying the name of a DICOM data dictionary.
'Endian'	String specifying the byte ordering of the file. 'Big' {'Little'} <hr/> Note: If VR is set to 'Explicit', 'Endian' must be 'Big'. <code>dicomwrite</code> ignores this value if 'CompressionMode' or 'TransferSyntax' is set.
'MultiframeSingleFile'	Logical value indicating whether multiframe imagery should be written to one file. When <code>true</code> (default), one file is created regardless of how many frames <code>X</code> contains. When <code>false</code> , one file is written for each frame in the image.

Option Name	Description
'TransferSyntax'	<p>A DICOM UID specifying the 'Endian', 'VR', and 'CompressionMode' options.</p> <hr/> <p>Note: If specified, <code>dicomwrite</code> ignores any values specified for the 'Endian', 'VR', and 'CompressionMode' options. The <code>TransferSyntax</code> value encodes values for these options.</p>
'UseMetadataBitDepths'	<p>Logical value that indicates whether to preserve the metadata values 'BitStored', 'BitsAllocated', and 'HighBit'. When <code>true</code>, <code>dicomwrite</code> preserves existing values. When <code>false</code> (default), <code>dicomwrite</code> computes these values based on the datatype of the pixel data. When 'CreateMode' is 'Create', <code>dicomwrite</code> ignores this field.</p>
'VR'	<p>String specifying whether the two-letter value representation (VR) code should be written to the file.</p> <p>'explicit' — Write VR to file.</p> <p>{'implicit'} — Infer from data dictionary.</p> <hr/> <p>Note: If you specify the 'Endian' value 'Big', you must specify 'Explicit'.</p>
'WritePrivate'	<p>Logical value indicating whether private data should be written to the file. Possible values: <code>true</code> — Write private data to file.</p> <p>{false} — Do not write private data.</p>

`dicomwrite(..., 'ObjectType', IOD, ...)` writes a file containing the necessary metadata for a particular type of DICOM Information Object (IOD). Supported IODs are

- 'Secondary Capture Image Storage' (default)
- 'CT Image Storage'
- 'MR Image Storage'

`dicomwrite(..., 'SOPClassUID', UID, ...)` provides an alternate method for specifying the IOD to create. `UID` is the DICOM unique identifier corresponding to one of the IODs listed above.

`dicomwrite(..., meta_struct, ...)` specifies optional metadata or file options in structure `meta_struct`. The names of fields in `meta_struct` must be the names of DICOM file attributes or options. The value of a field is the value you want to assign to the attribute or option.

`dicomwrite(..., info, ...)` specifies metadata in the metadata structure `info`, which is produced by the `dicominfo` function. For more information about this structure, see `dicominfo`.

`status = dicomwrite(...)` returns information about the metadata and the descriptions used to generate the DICOM file. This syntax can be useful when you specify an `info` structure that was created by `dicominfo` to the `dicomwrite` function. An `info` structure can contain many fields. If no metadata was specified, `dicomwrite` returns an empty matrix (`[]`).

The structure returned by `dicomwrite` contains these fields:

Field	Description
'BadAttribute'	The attribute's internal description is bad. It might be missing from the data dictionary or have incorrect data in its description.
'MissingCondition'	The attribute is conditional but no condition has been provided for when to use it.
'MissingData'	No data was provided for an attribute that must appear in the file.
'SuspectAttribute'	Data in the attribute does not match a list of enumerated values in the DICOM specification.

Examples

Read a CT image from the sample DICOM file included with the toolbox and then write the CT image to a file, creating a secondary capture image.

```
X = dicomread('CT-MONO2-16-ankle.dcm');
```

```
dicomwrite(X, 'sc_file.dcm');
```

Write the CT image, `X`, to a DICOM file along with its metadata. Use the `dicominfo` function to retrieve metadata from a DICOM file.

```
metadata = dicominfo('CT-MONO2-16-ankle.dcm');  
dicomwrite(X, 'ct_file.dcm', metadata);
```

Copy all metadata from one file to another. In this mode, `dicomwrite` does not verify the metadata written to the file.

```
dicomwrite(X, 'ct_copy.dcm', metadata, 'CreateMode', 'copy');
```

More About

Tips

The DICOM format specification lists several Information Object Definitions (IODs) that can be created. These IODs correspond to images and metadata produced by different real-world modalities (e.g., MR, X-ray, Ultrasound, etc.). For each type of IOD, the DICOM specification defines the set of metadata that must be present and possible values for other metadata.

`dicomwrite` fully implements a limited number of these IODs, listed above in the `ObjectType` syntax. For these IODs, `dicomwrite` verifies that all required metadata attributes are present, creates missing attributes if necessary, and specifies default values where possible. Using these supported IODs is the best way to ensure that the files you create conform to the DICOM specification. This is `dicomwrite` default behavior and corresponds to the `CreateMode` option value of `'Create'`.

To write DICOM files for IODs that `dicomwrite` doesn't implement, use the `'Copy'` value for the `CreateMode` option. In this mode, `dicomwrite` writes the image data to a file including the metadata that you specify as a parameter, shown above in the `info` syntax. The purpose of this option is to take metadata from an existing file of the same modality or IOD and use it to create a new DICOM file with different image pixel data.

Note Because `dicomwrite` copies metadata to the file without verification in `'copy'` mode, it is possible to create a DICOM file that does not conform to the DICOM standard. For example, the file may be missing required metadata, contain superfluous metadata, or the metadata may no longer correspond to the modality settings used to generate the

original image. When using 'Copy' mode, make sure that the metadata you use is from the same modality and IOD. If the copy you make is unrelated to the original image, use `dicomuid` to create new unique identifiers for series and study metadata. See the IOD descriptions in Part 3 of the DICOM specification for more information on appropriate IOD values.

See Also

`dicomanon` | `dicomdict` | `dicomdisp` | `dicominfo` | `dicomlookup` | `dicomread` | `dicomuid`

Introduced before R2006a

dpxinfo

Read metadata from DPX file

Syntax

```
metadata = dpxinfo(filename)
```

Description

`metadata = dpxinfo(filename)` reads information about the image contained in the DPX file specified by `filename`. `metadata` is a structure containing the file details.

Digital Picture Exchange (DPX) is an ANSI standard file format commonly used for still-frame storage in digital intermediate post-production facilities and film labs.

Examples

Read Metadata from DPX File

Read metadata from DPX file into the workspace.

```
m = dpxinfo('peppers.dpx')
```

```
m =
```

```
    Filename: 'B:\matlab\toolbox\images\imdata\peppers.dpx'  
    FileModDate: '16-Mar-2015 09:57:26'  
    FileSize: 892828  
    Format: 'DPX'  
    FormatVersion: '2.0'  
    Width: 512  
    Height: 384  
    BitDepth: 36  
    ColorType: 'R,G,B'  
    FormatSignature: [88 80 68 83]  
    ByteOrder: 'Little-endian'
```

```
        Orientation: 'Left-to-right, Top-to-bottom'  
    NumberOfImageElements: 1  
        DataSign: {'Unsigned'}  
    AmplitudeTransferFunction: {'ITU-R 709-4'}  
        Colorimetry: {'ITU-R 709-4'}  
    ChannelBitDepths: 12  
    PackingMethod: 0  
        Encoding: {'None'}
```

Input Arguments

filename — Name of the DPX file

string

Name of a DPX file, specified as a string. **filename** can contain the absolute path to the file, the name of a file on the MATLAB path, or a relative path.

Example: `m = dpxinfo('peppers.dpx');`

Data Types: char

Output Arguments

metadata — Information about the DPX image data

structure

Information about the DPX image data, returned as a structure.

See Also

`dpxread`

Introduced in R2015b

dpxread

Read DPX image

Syntax

```
X = dpxread(filename)
```

Description

`X = dpxread(filename)` reads image data from the DPX file specified by `filename`, returning the image `X`.

Digital Picture Exchange (DPX) is an ANSI standard file format commonly used for still-frame storage in digital intermediate post-production facilities and film labs.

Examples

Read and Visualize 12-bit RGB Image

Read image from DPX file into the workspace.

```
RGB = dpxread('peppers.dpx');
```

Create a scale factor based on the data range of the image data. The image needs to be scaled to span the 16-bit data range expected by `imshow`.

```
maxOfDataRange = 2^12 - 1;  
scaleFactor = intmax('uint16') / maxOfDataRange;
```

Display the image.

```
figure  
imshow(RGB * scaleFactor)
```



Input Arguments

filename — Name of the DPX file
string

Name of a DPX file, specified as a string. **filename** can contain the absolute path to the file, the name of a file on the MATLAB path, or a relative path.

Example: `RGB = dpxread('peppers.dpx');`

Data Types: char

Output Arguments

X — Image data from DPX file

real, nonsparse numeric array

Image data from DPX file, returned as a real, nonsparse numeric array of class `uint8` or `uint16`, depending on the bit depth of the pixels in `filename`.

See Also

`dpxinfo`

Introduced in R2015b

edge

Find edges in intensity image

Syntax

```
BW = edge(I)
BW = edge(I,method)
BW = edge(I,method,threshold)
BW = edge(I,method,threshold,direction)
BW = edge(I,method,threshold,direction,'nothinning')
BW = edge(I,method,threshold,direction,sigma)
[BW,threshOut] = edge( ___ )
[gpuarrayBW,threshOut] = edge(gpuarrayI, ___ )
```

Description

`BW = edge(I)` returns a binary image `BW` containing 1s where the function finds edges in the input image `I` and 0s elsewhere. By default, `edge` uses the Sobel edge detection method.

This function supports code generation (see “Tips” on page 1-327).

`BW = edge(I,method)` detects edges in image `I`, where `method` specifies the edge detection method used.

`BW = edge(I,method,threshold)` detects edges in image `I`, where `threshold` specifies the sensitivity threshold. `edge` ignores all edges that are not stronger than `threshold`.

`BW = edge(I,method,threshold,direction)` detects edges in image `I`, where `direction` specifies the direction in which the function looks for edges in the image: horizontally, vertically, or in both directions. Used only with the Sobel and Prewitt methods.

`BW = edge(I,method,threshold,direction,'nothinning')` detects edges in image `I`, where ‘nothinning’ speeds up the operation of the algorithm by skipping

the additional edge-thinning stage. By default, the algorithm applies edge thinning. Used only with the Sobel, Prewitt, and Roberts methods.

`BW = edge(I,method,threshold,direction,sigma)` detects edges in image `I`, where `sigma` specifies the standard deviation of the filter. Used only with the Laplacian of Gaussian and Canny methods.

`[BW,threshOut] = edge(___)` returns the threshold value.

`[gpuarrayBW,threshOut] = edge(gpuarrayI, ___)` performs the edge detection operation on a GPU. The input image and the output image are `gpuArrays`. This syntax requires Parallel Computing Toolbox.

“Code Generation” on page 1-326 support: Yes.


“MATLAB Function Block” on page 1-326 support: Yes.

Examples

Compare Edge Detection Using Canny and Prewitt Methods

Read a grayscale image into the workspace and display it.

```
I = imread('circuit.tif');  
imshow(I)
```



Find edges using the Canny method.

```
BW1 = edge(I, 'Canny');
```

Find edges using the Prewitt method.

```
BW2 = edge(I, 'Prewitt');
```

Display both results side-by-side.

```
imshowpair(BW1,BW2, 'montage')
```




Find Edges Using Prewitt Method on a GPU

Read grayscale image, creating a `gpuArray`.

```
I = gpuArray(imread('circuit.tif'));
```

Find edges using the Prewitt method.

```
BW = edge(I, 'prewitt');
```

Display results.

```
figure, imshow(BW)
```

Input Arguments

I — Input intensity or binary image

2-D, real, nonsparse numeric or logical array

Input intensity or binary image, specified as a 2-D, real, nonsparse, numeric, or logical array.

Data Types: `single` | `double` | `int16` | `uint8` | `uint16` | `logical`

method — Edge detection method

'Sobel' (default) | string

Edge detection method, specified as one of the following strings.

Method	Description
'Canny'	Finds edges by looking for local maxima of the gradient of I . The edge function calculates the gradient using the derivative of a Gaussian filter. This method uses two thresholds to detect strong and weak edges, including weak edges in the output if they are connected to strong edges. By using two thresholds, the Canny method is less likely than the other methods to be fooled by noise, and more likely to detect true weak edges. Not supported on a GPU.
'log' (Laplacian of Gaussian)	Finds edges by looking for zero-crossings after filtering I with a Laplacian of Gaussian filter.
'Prewitt'	Finds edges using the Prewitt approximation to the derivative. It returns edges at those points where the gradient of I is maximum.
'Roberts'	Finds edges using the Roberts approximation to the derivative. It returns edges at those points where the gradient of I is maximum.
'Sobel'	Finds edges using the Sobel approximation to the derivative. It returns edges at those points where the gradient of I is maximum.
'zerocross'	Finds edges by looking for zero-crossings after filtering I with a filter that you specify.

Data Types: `char`

threshold — Sensitivity threshold

scalar | two-element vector (Canny method only)

Sensitivity threshold, specified as a numeric scalar or, for the Canny method only, a two-element vector. `edge` ignores all edges that are not stronger than `threshold`. If you do not specify `threshold`, or if you specify an empty array (`[]`), `edge` chooses the value automatically. For information about this parameter, see “Tips” on page 1-327.

For the ‘`log`’ (Laplacian of Gaussian) and ‘`zerocross`’ methods, if you specify the threshold value `0`, the output image has closed contours because it includes all of the zero-crossings in the input image.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

direction — Direction of detection

‘`both`’ (default) | ‘`horizontal`’ | ‘`vertical`’

Direction of detection, specified as the string ‘`horizontal`’, ‘`vertical`’, or ‘`both`’. Supported only by the Sobel and Prewitt methods.

Data Types: `char`

sigma — Standard deviation of the filter

`2` (default) | `scalar`

Standard deviation of the filter, specified as a scalar. The following table describes this option for each method that supports it.

Method	Description
Canny	Scalar value that specifies the standard deviation of the Gaussian filter. The default <code>sigma</code> is <code>sqrt(2)</code> ; the size of the filter is chosen automatically, based on <code>sigma</code> .
Laplacian of Gaussian (log)	Scalar value that specifies the standard deviation of the Laplacian of Gaussian filter. The default <code>sigma</code> is <code>2</code> . The size of the filter is <code>n</code> -by- <code>n</code> , where <code>n = ceil(sigma*3)*2+1</code> .

Scalar value that specifies the standard deviation of the Gaussian filter. The default `sigma` is `sqrt(2)`. The size of the filter is chosen automatically, based on `sigma`.

Data Types: `double`

gpuarrayI — Input image

`gpuArray`

Input image, specified as a `gpuArray`.

Output Arguments

BW — Output binary image

logical array

Output binary image, returned as a logical array, the same size as **I**, with 1s where the function finds edges in **I** and 0s elsewhere.

threshOut — Threshold value used in the computation

numeric scalar

Threshold value used in the computation, returned as a numeric scalar.

gpuarrayBW — Output binary image when run on a GPU

gpuArray

Output binary image when run on a GPU, returned as a gpuArray.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, note the following:

- The **method**, **direction**, and **sigma** arguments must be compile-time constants.
- Nonprogrammatic syntaxes are not supported. For example, if you do not specify a return value, **edge** displays an image. This syntax is not supported.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

The **thresh** and **sigma** arguments must be compile-time constants.

Tips

- Notes about the `threshold` parameter:
 - For the gradient-magnitude edge detection methods (Sobel, Prewitt, Roberts), `edge` uses `threshold` to threshold the calculated gradient magnitude. For the zero-crossing methods, including Laplacian of Gaussian, `edge` uses `threshold` as a threshold for the zero-crossings. In other words, a large jump across zero is an edge, while a small jump isn't.
 - The Canny method applies two thresholds to the gradient: a high threshold for low edge sensitivity and a low threshold for high edge sensitivity. `edge` starts with the low sensitivity result and then grows it to include connected edge pixels from the high sensitivity result. This helps fill in gaps in the detected edges.
 - In all cases, `edge` chooses the default threshold heuristically, depending on the input data. The best way to vary the threshold is to run `edge` once, capturing the calculated threshold as the second output argument. Then, starting from the value calculated by `edge`, adjust the threshold higher (fewer edge pixels) or lower (more edge pixels).
- The function `edge` changed in Version 7.2 (R2011a). Previous versions of the Image Processing Toolbox used a different algorithm for computing the Canny method. If you need the same results produced by the previous implementation, use the following syntax:

```
BW = edge(I, 'canny_old', ...)
```

- The syntax `BW = edge(..., K)` has been removed. Use the `BW = edge(..., direction)` syntax instead.
- The syntax `edge(I, 'marr-hildreth', ...)` has been removed. Use the `edge(I, 'log', ...)` syntax instead.

References

- [1] Canny, John, "A Computational Approach to Edge Detection," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, Vol. PAMI-8, No. 6, 1986, pp. 679-698.
- [2] Lim, Jae S., *Two-Dimensional Signal and Image Processing*, Englewood Cliffs, NJ, Prentice Hall, 1990, pp. 478-488.
- [3] Parker, James R., *Algorithms for Image Processing and Computer Vision*, New York, John Wiley & Sons, Inc., 1997, pp. 23-29.

See Also

`fspecial` | `gpuArray` | `imgradient` | `imgradientxy`

Introduced before R2006a

edgetaper

Taper discontinuities along image edges

Syntax

```
J = edgetaper(I,PSF)
```

Description

`J = edgetaper(I,PSF)` blurs the edges of the input image `I` using the point spread function `PSF`. The size of the `PSF` cannot exceed half of the image size in any dimension.

The output image `J` is the weighted sum of the original image `I` and its blurred version. The weighting array, determined by the autocorrelation function of `PSF`, makes `J` equal to `I` in its central region, and equal to the blurred version of `I` near the edges.

The `edgetaper` function reduces the ringing effect in image deblurring methods that use the discrete Fourier transform, such as `deconvwnr`, `deconvreg`, and `deconvlucy`.

Class Support

`I` and `PSF` can be of class `uint8`, `uint16`, `int16`, `single`, or `double`. `J` is of the same class as `I`.

Examples

Blur the Edges of an Image

```
original = imread('cameraman.tif');  
PSF = fspecial('gaussian',60,10);  
edgesTapered = edgetaper(original,PSF);  
figure, imshow(original,[]);  
figure, imshow(edgesTapered,[]);
```





See Also

[deconvlucy](#) | [deconvreg](#) | [deconvwnr](#) | [otf2psf](#) | [padarray](#) | [psf2otf](#)

Introduced before R2006a

entropy

Entropy of grayscale image

Syntax

`E = entropy(I)`

Description

`E = entropy(I)` returns `E`, a scalar value representing the entropy of grayscale image `I`. Entropy is a statistical measure of randomness that can be used to characterize the texture of the input image. Entropy is defined as

$$-\text{sum}(p.\text{*log2}(p))$$

where `p` contains the histogram counts returned from `imhist`. By default, `entropy` uses two bins for logical arrays and 256 bins for `uint8`, `uint16`, or `double` arrays.

`I` can be a multidimensional image. If `I` has more than two dimensions, the `entropy` function treats it as a multidimensional grayscale image and not as an RGB image.

Class Support

`I` can be `logical`, `uint8`, `uint16`, or `double` and must be real, nonempty, and nonsparse. `E` is `double`.

Notes

`entropy` converts any class other than `logical` to `uint8` for the histogram count calculation so that the pixel values are discrete and directly correspond to a bin value.

Examples

```
I = imread('circuit.tif');
```

`J = entropy(I)`

References

- [1] Gonzalez, R.C., R.E. Woods, S.L. Eddins, *Digital Image Processing Using MATLAB*, New Jersey, Prentice Hall, 2003, Chapter 11.

See Also

`imhist` | `entropyfilt`

Introduced before R2006a

entropyfilt

Local entropy of grayscale image

Syntax

```
J = entropyfilt(I)
J = entropyfilt(I,NHOOD)
```

Description

`J = entropyfilt(I)` returns the array `J`, where each output pixel contains the entropy value of the 9-by-9 neighborhood around the corresponding pixel in the input image `I`. `I` can have any dimension. If `I` has more than two dimensions, `entropyfilt` treats it as a multidimensional grayscale image and not as a truecolor (RGB) image. The output image `J` is the same size as the input image `I`.

For pixels on the borders of `I`, `entropyfilt` uses symmetric padding. In symmetric padding, the values of padding pixels are a mirror reflection of the border pixels in `I`.

`J = entropyfilt(I,NHOOD)` performs entropy filtering of the input image `I` where you specify the neighborhood in `NHOOD`. `NHOOD` is a multidimensional array of zeros and ones where the nonzero elements specify the neighbors. `NHOOD`'s size must be odd in each dimension.

By default, `entropyfilt` uses the neighborhood `true(9)`. `entropyfilt` determines the center element of the neighborhood by `floor((size(NHOOD) + 1)/2)`. To specify neighborhoods of various shapes, such as a disk, use the `strel` function to create a structuring element object and then use the `getnhood` function to extract the neighborhood from the structuring element object.

Class Support

`I` can be `logical`, `uint8`, `uint16`, or `double`, and must be real and nonsparse. `NHOOD` can be `logical` or numeric and must contain zeros or ones. The output array `J` is of class `double`.

entropyfilt converts any class other than logical to uint8 for the histogram count calculation so that the pixel values are discrete and directly correspond to a bin value.

Examples

```
I = imread('circuit.tif');  
J = entropyfilt(I);  
imshow(I), figure, imshow(J,[]);
```

References

- [1] Gonzalez, R.C., R.E. Woods, S.L. Eddins, *Digital Image Processing Using MATLAB*, New Jersey, Prentice Hall, 2003, Chapter 11.

See Also

entropy | imhist | rangefilt | stdfilt

Introduced before R2006a

fan2para

Convert fan-beam projections to parallel-beam

Syntax

```
P = fan2para(F,D)
```

```
P = fan2para(..., param1, val1, param2, val2,...)
```

```
[P ,parallel_locations, parallel_rotation_angles] = fan2para(...)
```

Description

`P = fan2para(F,D)` converts the fan-beam data `F` to the parallel-beam data `P`. `D` is the distance in pixels from the fan-beam vertex to the center of rotation that was used to obtain the projections.

`P = fan2para(..., param1, val1, param2, val2,...)` specifies parameters that control various aspects of the `fan2para` conversion, listed in the following table. Parameter names can be abbreviated, and case does not matter.

Parameter	Description
'FanCoverage'	String specifying the range through which the beams are rotated. 'cycle' — Rotate through the full range [0,360). This is the default. 'minimal' — Rotate the minimum range necessary to represent the object.
'FanRotationIncrement'	Positive real scalar specifying the increment of the rotation angle of the fan-beam projections, measured in degrees. Default value is 1.
'FanSensorGeometry'	String specifying how sensors are positioned. 'arc' — Sensors are spaced equally along a circular arc at distance <code>D</code> from the center of rotation. Default value is 'arc'

Parameter	Description
	<p>'line' — Sensors are spaced equally along a line, the closest point of which is distance D from the center of rotation.</p> <p>See <code>fanbeam</code> for details.</p>
'FanSensorSpacing'	<p>Positive real scalar specifying the spacing of the fan-beam sensors. Interpretation of the value depends on the setting of 'FanSensorGeometry'.</p> <p>If 'FanSensorGeometry' is set to 'arc' (the default), the value defines the angular spacing in degrees. Default value is 1.</p> <p>If 'FanSensorGeometry' is 'line', the value specifies the linear spacing. Default value is 1. See <code>fanbeam</code> for details.</p> <hr/> <p>Note: This linear spacing is measured on the x' axis. The x' axis for each column, <code>COL</code>, of <code>F</code> is oriented at <code>fan_rotation_angles(COL)</code> degrees counterclockwise from the x-axis. The origin of both axes is the center pixel of the image.</p>
'Interpolation'	<p>Text string specifying the type of interpolation used between the parallel-beam and fan-beam data.</p> <p>'nearest' — Nearest-neighbor</p> <p>{'linear'} — Linear</p> <p>'spline' — Piecewise cubic spline</p> <p>'pchip' — Piecewise cubic Hermite (PCHIP)</p> <p>'v5cubic' — The cubic interpolation from MATLAB 5</p>

Parameter	Description
'ParallelCoverage'	Text string specifying the range of rotation. 'cycle' — Parallel data covers 360 degrees { 'halfcycle' } — Parallel data covers 180 degrees
'ParallelRotationIncrement'	Positive real scalar specifying the parallel-beam rotation angle increment, measured in degrees. Parallel beam angles are calculated to cover [0,180) degrees with increment PAR_ROT_INC, where PAR_ROT_INC is the value of 'ParallelRotationIncrement'. 180/PAR_ROT_INC must be an integer. If 'ParallelRotationIncrement' is not specified, the increment is assumed to be the same as the increment of the fan-beam rotation angles.
'ParallelSensorSpacing'	Positive real scalar specifying the spacing of the parallel-beam sensors in pixels. The range of sensor locations is implied by the range of fan angles and is given by [D*sin(min(FAN_ANGLES)), ... D*sin(max(FAN_ANGLES))] If 'ParallelSensorSpacing' is not specified, the spacing is assumed to be uniform and is set to the minimum spacing implied by the fan angles and sampled over the range implied by the fan angles.

[P ,parallel_locations, parallel_rotation_angles] = fan2para(...)
returns the parallel-beam sensor locations in parallel_locations and rotation angles in parallel_rotation_angles.

Class Support

The input arguments, F and D, can be double or single, and they must be nonsparse. All other numeric inputs are double. The output P is double.

Examples

Create synthetic parallel-beam data, derive fan-beam data, and then use the fan-beam data to recover the parallel-beam data.

```
ph = phantom(128);
theta = 0:179;
[Psynthetic, xp] = radon(ph, theta);
imshow(Psynthetic, [], ...
        'XData', theta, 'YData', xp, 'InitialMagnification', 'fit')
axis normal
title('Synthetic Parallel-Beam Data')
xlabel('\theta (degrees)')
ylabel('x''')
colormap(hot), colorbar
Fsynthetic = para2fan(Psynthetic, 100, 'FanSensorSpacing', 1);
```

Recover original parallel-beam data.

```
[Precovered, Ploc, Pangles] = fan2para(Fsynthetic, 100, ...
        'FanSensorSpacing', 1, ...
        'ParallelSensorSpacing', 1);
figure
imshow(Precovered, [], 'XData', Pangles, ...
        'YData', Ploc, 'InitialMagnification', 'fit')
axis normal
title('Recovered Parallel-Beam Data')
xlabel('Rotation Angles (degrees)')
ylabel('Parallel Sensor Locations (pixels)')
colormap(hot), colorbar
```

See Also

fanbeam | iradon | ifanbeam | para2fan | phantom | radon

Introduced before R2006a

fanbeam

Fan-beam transform


Syntax

```
F = fanbeam(I,D)
F = fanbeam(..., param1, val1, param1, val2,...)
[F, fan_sensor_positions, fan_rotation_angles] = fanbeam(...)
```

Description

$F = \text{fanbeam}(I, D)$ computes the fan-beam projection data (sinogram) F from the image I .

D is the distance in pixels from the fan-beam vertex to the center of rotation. The center of rotation is the center pixel of the image, defined as $\text{floor}((\text{size}(I)+1)/2)$. D must be large enough to ensure that the fan-beam vertex is outside of the image at all rotation angles. See “Tips” on page 1-344 for guidelines on specifying D . The following figure illustrates D in relation to the fan-beam vertex for one fan-beam geometry. See the `FanSensorGeometry` parameter for more information.



Each column of F contains the fan-beam sensor samples at one rotation angle. The number of columns in F is determined by the fan rotation increment. By default, the fan rotation increment is 1 degree so F has 360 columns.


The number of rows in F is determined by the number of sensors. `fanbeam` determines the number of sensors by calculating how many beams are required to cover the entire image for any rotation angle.

For information about how to specify the rotation increment and sensor spacing, see the documentation for the `FanRotationIncrement` and `FanSensorSpacing` parameters, below.


`F = fanbeam(..., param1, val1, param1, val2, ...)` specifies parameters, listed below, that control various aspects of the fan-beam projections. Parameter names can be abbreviated, and case does not matter.

'`FanRotationIncrement`' - - Positive real scalar specifying the increment of the rotation angle of the fan-beam projections. Measured in degrees. Default value is 1.

'`FanSensorGeometry`' - - Text string specifying how sensors are positioned. Valid values are '`arc`' or '`line`'. In the '`arc`' geometry, sensors are spaced equally along a circular arc, as shown below. This is the default value.



In '`line`' geometry, sensors are spaced equally along a line, as shown below.



'FanSensorSpacing' -- Positive real scalar specifying the spacing of the fan-beam sensors. Interpretation of the value depends on the setting of 'FanSensorGeometry'. If 'FanSensorGeometry' is set to 'arc' (the default), the value defines the angular spacing in degrees. Default value is 1. If 'FanSensorGeometry' is 'line', the value specifies the linear spacing. Default value is 1.

Note This linear spacing is measured on the x' axis. The x' axis for each column, `col`, of `F` is oriented at `fan_rotation_angles(col)` degrees counterclockwise from the x -axis. The origin of both axes is the center pixel of the image.

`[F, fan_sensor_positions, fan_rotation_angles] = fanbeam(...)` returns the location of fan-beam sensors in `fan_sensor_positions` and the rotation angles where the fan-beam projections are calculated in `fan_rotation_angles`.

If 'FanSensorGeometry' is 'arc' (the default), `fan_sensor_positions` contains the fan-beam spread angles. If 'FanSensorGeometry' is 'line', `fan_sensor_positions` contains the fan-beam sensor positions along the x' axis. See 'FanSensorSpacing' for more information.

Class Support

`I` can be logical or numeric. All other numeric inputs and outputs can be double. None of the inputs can be sparse.

Examples

The following example computes the fan-beam projections for rotation angles that cover the entire image.

```
iptsetpref('ImshowAxesVisible','on')
ph = phantom(128);
imshow(ph)
[F,Fpos,Fangles] = fanbeam(ph,250);
figure
imshow(F,[],'XData',Fangles,'YData',Fpos,...
        'InitialMagnification','fit')
axis normal
xlabel('Rotation Angles (degrees)')
ylabel('Sensor Positions (degrees)')
colormap(hot), colorbar
```

The following example computes the Radon and fan-beam projections and compares the results at a particular rotation angle.

```
I = ones(100);
D = 200;
dtheta = 45;

% Compute fan-beam projections for 'arc' geometry
[Farc,FposArcDeg,Fangles] = fanbeam(I,D,...
        'FanSensorGeometry','arc',...
        'FanRotationIncrement',dtheta);
% Convert angular positions to linear distance
% along x-prime axis
FposArc = D*tan(FposArcDeg*pi/180);

% Compute fan-beam projections for 'line' geometry
[Fline,FposLine] = fanbeam(I,D,...
        'FanSensorGeometry','line',...
        'FanRotationIncrement',dtheta);

% Compute the corresponding Radon transform
[R,Rpos]=radon(I,Fangles);

% Display the three projections at one particular rotation
% angle. Note the three are very similar. Differences are
% due to the geometry of the sampling, and the numerical
% approximations used in the calculations.
```

```
figure
idx = find(Fangles==45);
plot(Rpos,R(:,idx),...
      FposArc,Farc(:,idx),...
      FposLine,Fline(:,idx))
legend('Radon','Arc','Line')
```

More About

Tips

As a guideline, try making *D* a few pixels larger than half the image diagonal dimension, calculated as follows

```
sqrt(size(I,1)^2 + size(I,2)^2)
```

The values returned in *F* are a numerical approximation of the fan-beam projections. The algorithm depends on the Radon transform, interpolated to the fan-beam geometry. The results vary depending on the parameters used. You can expect more accurate results when the image is larger, *D* is larger, and for points closer to the middle of the image, away from the edges.

References

[1] Kak, A.C., & Slaney, M., *Principles of Computerized Tomographic Imaging*, IEEE Press, NY, 1988, pp. 92-93.

See Also

fan2para | iradon | ifanbeam | para2fan | phantom | radon

Introduced before R2006a

findbounds

Find output bounds for spatial transformation

Syntax

```
outbounds = findbounds(TFORM,inbounds)
```

Description

`outbounds = findbounds(TFORM,inbounds)` estimates the output bounds corresponding to a given spatial transformation and a set of input bounds. `TFORM`, as returned by `maketform`, is a spatial transformation structure. `inbounds` is a 2-by-`num_dims` matrix. The first row of `inbounds` specifies the lower bounds for each dimension, and the second row specifies the upper bounds. `num_dims` has to be consistent with the `ndims_in` field of `TFORM`.

`outbounds` has the same form as `inbounds`. It is an estimate of the smallest rectangular region completely containing the transformed rectangle represented by the input bounds. Since `outbounds` is only an estimate, it might not completely contain the transformed input rectangle.

More About

Tips

`findbounds` gets called by `imtransform` if 'XData' and 'YData', the parameters that control the output-space bounding box in `imtransform`, are not specified. `findbounds` computes the output-space bounding box.

Algorithms


- 1 `findbounds` first creates a grid of input-space points. These points are located at the center, corners, and middle of each edge in the image.

```
I = imread('rice.png');
```

```

h = imshow(I);
set(h,'AlphaData',0.3);
axis on, grid on
in_points = [ ...
    0.5000  0.5000
    0.5000 256.5000
    256.5000 0.5000
    256.5000 256.5000
    0.5000 128.5000
    128.5000 0.5000
    128.5000 128.5000
    128.5000 256.5000
    256.5000 128.5000];
hold on
plot(in_points(:,1),in_points(:,2),'.','MarkerSize',18)
hold off

```



Grid of Input-Space Points

- Next, `findbounds` transforms the grid of input-space points to output space. If `tform` contains a forward transformation (a nonempty `forward_fcn` field), then `findbounds` transforms the input-space points using `tformfwd`. For example:

```

tform = maketform('affine', ...
    [1.1067 -0.2341 0; 0.5872 1.1769 0; 1000 -300 1]);
out_points = tformfwd(tform, in_points)

```

The output appears below:


```
out_points =  
1.0e+003 *  
1.0008 -0.2995  
1.1512  0.0018  
1.2842 -0.3595  
1.4345 -0.0582  
1.0760 -0.1489  
1.1425 -0.3295  
1.2177 -0.1789  
1.2928 -0.0282  
1.3593 -0.2088
```

If TFORM does not contain a forward transformation, then `findbounds` estimates the output bounds using the Nelder-Mead optimization function `fminsearch`.

- 3 Finally, `findbounds` computes the bounding box of the transformed grid of points.

See Also

`cp2tform` | `imtransform` | `maketform` | `tformarray` | `tformfwd` | `tforminv`

Introduced before R2006a

fitgeotrans

Fit geometric transformation to control point pairs

Syntax

```
tform = fitgeotrans(movingPoints, fixedPoints, transformationType)
tform = fitgeotrans(movingPoints, fixedPoints, 'polynomial', degree)
tform = fitgeotrans(movingPoints, fixedPoints, 'pwl')
tform = fitgeotrans(movingPoints, fixedPoints, 'lwm', n)
```

Description

`tform = fitgeotrans(movingPoints, fixedPoints, transformationType)` takes the pairs of control points, `movingPoints` and `fixedPoints`, and uses them to infer the geometric transformation, specified by `transformationType`.

`tform = fitgeotrans(movingPoints, fixedPoints, 'polynomial', degree)` fits an `images.geotrans.PolynomialTransformation2D` object to control point pairs `movingPoints` and `fixedPoints`. Specify the degree of the polynomial transformation `degree`, which can be 2, 3, or 4.

`tform = fitgeotrans(movingPoints, fixedPoints, 'pwl')` fits an `images.geotrans.PiecewiseLinearTransformation2D` object to control point pairs `movingPoints` and `fixedPoints`. This transformation maps control points by breaking up the plane into local piecewise-linear regions in which a different affine transformation maps control points in each local region.

`tform = fitgeotrans(movingPoints, fixedPoints, 'lwm', n)` fits an `images.geotrans.LocalWeightedMeanTransformation2D` object to control point pairs `movingPoints` and `fixedPoints`. The local weighted mean transformation creates a mapping, by inferring a polynomial at each control point using neighboring control points. The mapping at any location depends on a weighted average of these polynomials. The `n` closest points are used to infer a second degree polynomial transformation for each control point pair.

“Code Generation” on page 1-353 support: Yes.

“MATLAB Function Block” on page 1-353 support: Yes.


Examples

Create Geometric Transformation for Image Alignment

This example shows how to create a geometric transformation that can be used to align two images.

Create a checkerboard image and rotate it to create a misaligned image.

```
I = checkerboard;  
J = imrotate(I,30);  
imshowpair(I,J,'montage')
```



Define some control points on the fixed image (the checkerboard) and moving image (the rotated checkerboard). You can define points interactively using the Control Point Selection tool.

```
fixedPoints = [11 11; 41 71];  
movingPoints = [14 44; 70 81];
```

Create a geometric transformation that can be used to align the two images, returned as an `affine2d` geometric transformation object.

```
tform = fitgeotrans(movingPoints, fixedPoints, 'NonreflectiveSimilarity')
```


```
tform =
```

affine2d with properties:

```
T: [3x3 double]
Dimensionality: 2
```

Use the `tform` estimate to resample the rotated image to register it with the fixed image. The regions of color (green and magenta) in the false color overlay image indicate error in the registration due to lack of precise correspondence in the control points.

```
Jregistered = imwarp(J,tform,'OutputView',imref2d(size(I)));
falsecolorOverlay = imfuse(I,Jregistered);
figure
imshow(falsecolorOverlay,'InitialMagnification','fit');
```



Recover angle and scale of the transformation by checking how a unit vector parallel to the x-axis is rotated and stretched.

```
u = [0 1];
v = [0 0];
[x, y] = transformPointsForward(tform, u, v);
dx = x(2) - x(1);
dy = y(2) - y(1);
angle = (180/pi) * atan2(dy, dx)
scale = 1 / sqrt(dx^2 + dy^2)
```

```
angle =
    29.9816
```

```
scale =
    1.0006
```

Input Arguments

movingPoints — **X and Y coordinates of control points in the image you want to transform**
m-by-2 double matrix

X and *Y* coordinates of control points in the image you want to transform, specified as an *m*-by-2 double matrix.

Example: `fixedPoints = [11 11; 41 71];`

Data Types: double

fixedPoints — **X and Y coordinates of control points in the base image**
m-by-2 double matrix

X and *Y* coordinates of control points in the base image, specified as an *m*-by-2 double matrix.

Example: `movingPoints = [14 44; 70 81];`

Data Types: double

transformationType — Type of transformation

'nonreflectivesimilarity' | 'similarity' | 'affine' | 'projective'

Type of transformation, specified as one of the following text strings.

Type	Description
'affine'	Affine transformation
'nonreflectivesimilar'	Nonreflective similarity
'projective'	Projective transformation
'similarity'	Similarity

Example: `tform = fitgeotrans(movingPoints, fixedPoints, 'nonreflectivesimilarity');`

Data Types: char

degree — Degree of the polynomial

2 | 3 | 4

Degree of the polynomial, specified as the integer 2, 3, or 4.

Data Types: double

n — Number of points to use in local weighted mean calculation

numeric value

Number of points to use in local weighted mean calculation, specified as a numeric value. n can be as small as 6, but making n small risks generating ill-conditioned polynomials

Data Types: double

Output Arguments

tform — Transformation

transformation object

Transformation, specified as a transformation object. The type of object depends on the transformation type. For example, if you specify the transformation type 'affine', tform is an `affine2d` object. If you specify 'pwl', tform is an `image.geotrans.PiecewiseLinearTransformation2d` object.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, the `transformationType` argument must be a compile-time constant and only the following transformation types are supported: 'nonreflectivesimilarity', 'similarity', 'affine', and 'projective'.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

References

- [1] Goshtasby, Ardeshir, "Piecewise linear mapping functions for image registration," *Pattern Recognition*, Vol. 19, 1986, pp. 459-466.
- [2] Goshtasby, Ardeshir, "Image registration by local approximation methods," *Image and Vision Computing*, Vol. 6, 1988, pp. 255-261.

See Also

`affine2d` | `projective2d` | `images.geotrans.PiecewiseLinearTransformation2d`
| `images.geotrans.PolynomialTransformation2d` |
`images.geotrans.LocalWeightedMeanTransformation2d` | `cpselect` | `imwarp`

Introduced in R2013b

fliptform

Flip input and output roles of TFORM structure

Syntax

```
TFLIP = fliptform(T)
```

Description

`TFLIP = fliptform(T)` creates a new spatial transformation structure, a TFORM struct, by flipping the roles of the inputs and outputs in an existing TFORM struct.

Examples

```
T = maketform('affine', [.5 0 0; .5 2 0; 0 0 1]);  
T2 = fliptform(T)
```

The following are equivalent:

```
x = tformfwd([-3 7],T)  
x = tforminv([-3 7],T2)
```

See Also

`maketform` | `tformfwd` | `tforminv`

Introduced before R2006a

freqz2

2-D frequency response

Syntax

```
[H, f1, f2] = freqz2(h, n1, n2)
[H, f1, f2] = freqz2(h, [n2 n1])
[H, f1, f2] = freqz2(h)
[H, f1, f2] = freqz2(h, f1, f2)
[...] = freqz2(h, ..., [dx dy])
[...] = freqz2(h, ..., dx)
freqz2(...)
```

Description

`[H, f1, f2] = freqz2(h, n1, n2)` returns `H`, the `n2`-by-`n1` frequency response of `h`, and the frequency vectors `f1` (of length `n1`) and `f2` (of length `n2`). `h` is a two-dimensional FIR filter, in the form of a computational molecule. `f1` and `f2` are returned as normalized frequencies in the range -1.0 to 1.0, where 1.0 corresponds to half the sampling frequency, or π radians.

`[H, f1, f2] = freqz2(h, [n2 n1])` returns the same result returned by `[H, f1, f2] = freqz2(h, n1, n2)`.

`[H, f1, f2] = freqz2(h)` uses `[n2 n1] = [64 64]`.

`[H, f1, f2] = freqz2(h, f1, f2)` returns the frequency response for the FIR filter `h` at frequency values in `f1` and `f2`. These frequency values must be in the range -1.0 to 1.0, where 1.0 corresponds to half the sampling frequency, or π radians.

`[...] = freqz2(h, ..., [dx dy])` uses `[dx dy]` to override the intersample spacing in `h`. `dx` determines the spacing for the `x` dimension and `dy` determines the spacing for the `y` dimension. The default spacing is 0.5, which corresponds to a sampling frequency of 2.0.

`[...] = freqz2(h, ..., dx)` uses `dx` to determine the intersample spacing in both dimensions.

`freqz2(...)` produces a mesh plot of the two-dimensional magnitude frequency response when no output arguments are specified.


Class Support

The input matrix `h` can be of class `double` or of any integer class. All other inputs to `freqz2` must be of class `double`. All outputs are of class `double`.

Examples

Use the window method to create a 16-by-16 filter, then view its frequency response using `freqz2`.

```
Hd = zeros(16,16);  
Hd(5:12,5:12) = 1;  
Hd(7:10,7:10) = 0;  
h = fwind1(Hd,bartlett(16));  
colormap(jet(64))  
freqz2(h,[32 32]); axis ([-1 1 -1 1 0 1])
```



See Also

freqz

Introduced before R2006a

fsamp2

2-D FIR filter using frequency sampling

Syntax

```
h = fsamp2(Hd)
h = fsamp2(f1, f2, Hd, [m n])
```

Description

`h = fsamp2(Hd)` designs a two-dimensional FIR filter with frequency response `Hd`, and returns the filter coefficients in matrix `h`. (`fsamp2` returns `h` as a computational molecule, which is the appropriate form to use with `filter2`.) The filter `h` has a frequency response that passes through points in `Hd`. If `Hd` is `m`-by-`n`, then `h` is also `m`-by-`n`.

`fsamp2` designs two-dimensional FIR filters based on a desired two-dimensional frequency response sampled at points on the Cartesian plane. `Hd` is a matrix containing the desired frequency response sampled at equally spaced points between -1.0 and 1.0 along the x and y frequency axes, where 1.0 corresponds to half the sampling frequency, or π radians.

$$H_d(f_1, f_2) = H_d(\omega_1, \omega_2) \Big|_{\omega_1 = \pi f_1, \omega_2 = \pi f_2}$$

For accurate results, use frequency points returned by `freqspace` to create `Hd`.

`h = fsamp2(f1, f2, Hd, [m n])` produces an `m`-by-`n` FIR filter by matching the filter response at the points in the vectors `f1` and `f2`. The frequency vectors `f1` and `f2` are in normalized frequency, where 1.0 corresponds to half the sampling frequency, or π radians. The resulting filter fits the desired response as closely as possible in the least squares sense. For best results, there must be at least `m*n` desired frequency points. `fsamp2` issues a warning if you specify fewer than `m*n` points.

Class Support


The input matrix `Hd` can be of class `double` or of any integer class. All other inputs to `fsamp2` must be of class `double`. All outputs are of class `double`.

Examples

Use `fsamp2` to design an approximately symmetric two-dimensional bandpass filter with passband between 0.1 and 0.5 (normalized frequency, where 1.0 corresponds to half the sampling frequency, or π radians):


- 1 Create a matrix `Hd` that contains the desired bandpass response. Use `freqspace` to create the frequency range vectors `f1` and `f2`.

```
[f1,f2] = freqspace(21,'meshgrid');
Hd = ones(21);
r = sqrt(f1.^2 + f2.^2);
Hd((r<0.1)|(r>0.5)) = 0;
colormap(jet(64))
mesh(f1,f2,Hd)
```



2 Design the filter that passes through this response.

```
h = fsamp2(Hd);  
freqz2(h)
```



More About

Algorithms

`fsamp2` computes the filter `h` by taking the inverse discrete Fourier transform of the desired frequency response. If the desired frequency response is real and symmetric (zero phase), the resulting filter is also zero phase.

References

- [1] Lim, Jae S., *Two-Dimensional Signal and Image Processing*, Englewood Cliffs, NJ, Prentice Hall, 1990, pp. 213-217.

See Also

conv2 | filter2 | freqspace | ftrans2 | fwind1 | fwind2

Introduced before R2006a

fspecial

Create predefined 2-D filter

Syntax

```
h = fspecial(type)
h = fspecial(type, parameters)
```

Description

`h = fspecial(type)` creates a two-dimensional filter `h` of the specified `type`. `fspecial` returns `h` as a correlation kernel, which is the appropriate form to use with `imfilter`. `type` is a string having one of these values.

Value	Description
average	Averaging filter
disk	Circular averaging filter (pillbox)
gaussian	Gaussian lowpass filter
laplacian	Approximates the two-dimensional Laplacian operator
log	Laplacian of Gaussian filter
motion	Approximates the linear motion of a camera
prewitt	Prewitt horizontal edge-emphasizing filter
sobel	Sobel horizontal edge-emphasizing filter

`h = fspecial(type, parameters)` accepts the filter specified by `type` plus additional modifying `parameters` particular to the type of filter chosen. If you omit these arguments, `fspecial` uses default values for the `parameters`.

The following list shows the syntax for each filter type. Where applicable, additional parameters are also shown.

- `h = fspecial('average', hsize)` returns an averaging filter `h` of size `hsize`. The argument `hsize` can be a vector specifying the number of rows and columns in `h`,

or it can be a scalar, in which case `h` is a square matrix. The default value for `hsize` is `[3 3]`.

- `h = fspecial('disk', radius)` returns a circular averaging filter (pillbox) within the square matrix of size `2*radius+1`. The default `radius` is 5.
- `h = fspecial('gaussian', hsize, sigma)` returns a rotationally symmetric Gaussian lowpass filter of size `hsize` with standard deviation `sigma` (positive). `hsize` can be a vector specifying the number of rows and columns in `h`, or it can be a scalar, in which case `h` is a square matrix. The default value for `hsize` is `[3 3]`; the default value for `sigma` is 0.5. Not recommended. Use `imgaussfilt` or `imgaussfilt3` instead.
- `h = fspecial('laplacian', alpha)` returns a 3-by-3 filter approximating the shape of the two-dimensional Laplacian operator. The parameter `alpha` controls the shape of the Laplacian and must be in the range 0.0 to 1.0. The default value for `alpha` is 0.2.
- `h = fspecial('log', hsize, sigma)` returns a rotationally symmetric Laplacian of Gaussian filter of size `hsize` with standard deviation `sigma` (positive). `hsize` can be a vector specifying the number of rows and columns in `h`, or it can be a scalar, in which case `h` is a square matrix. The default value for `hsize` is `[5 5]` and 0.5 for `sigma`.
- `h = fspecial('motion', len, theta)` returns a filter to approximate, once convolved with an image, the linear motion of a camera by `len` pixels, with an angle of `theta` degrees in a counterclockwise direction. The filter becomes a vector for horizontal and vertical motions. The default `len` is 9 and the default `theta` is 0, which corresponds to a horizontal motion of nine pixels.

To compute the filter coefficients, `h`, for 'motion':

- 1 Construct an ideal line segment with the desired length and angle, centered at the center coefficient of `h`.
 - 2 For each coefficient location `(i, j)`, compute the nearest distance between that location and the ideal line segment.
 - 3 `h = max(1 - nearest_distance, 0);`
 - 4 Normalize `h`: `h = h / (sum(h(:)))`
- `h = fspecial('prewitt')` returns the 3-by-3 filter `h` (shown below) that emphasizes horizontal edges by approximating a vertical gradient. If you need to emphasize vertical edges, transpose the filter `h'`.

```
[ 1  1  1
```

```
0 0 0
-1 -1 -1 ]
```

To find vertical edges, or for x -derivatives, use h' .

- `h = fspecial('sobel')` returns a 3-by-3 filter h (shown below) that emphasizes horizontal edges using the smoothing effect by approximating a vertical gradient. If you need to emphasize vertical edges, transpose the filter h' .

```
[ 1 2 1
  0 0 0
 -1 -2 -1 ]
```

“Code Generation” on page 1-367 support: Yes.

“MATLAB Function Block” on page 1-367 support: Yes.

Class Support

`h` is of class `double`.

Examples

Create Various Filters and Filter an Image

Read image and display it.

```
I = imread('cameraman.tif');
imshow(I);
```



Create a motion filter and use it to blur the image. Display the blurred image.

```
H = fspecial('motion',20,45);  
MotionBlur = imfilter(I,H,'replicate');  
imshow(MotionBlur);
```



Create a disk filter and use it to blur the image. Display the blurred image.

```
H = fspecial('disk',10);  
blurred = imfilter(I,H,'replicate');  
imshow(blurred);
```



More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, all inputs must be constants at compilation time.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

When generating code, all inputs must be constants at compilation time.

Algorithms

`fspecial` creates Gaussian filters using

$$h_g(n_1, n_2) = e^{-\frac{(n_1^2 + n_2^2)}{2\sigma^2}}$$

$$h(n_1, n_2) = \frac{h_g(n_1, n_2)}{\sum_{n_1} \sum_{n_2} h_g}$$

`fspecial` creates Laplacian filters using

$$\nabla^2 = \frac{\partial^2}{\partial x^2} + \frac{\partial^2}{\partial y^2}$$

$$\nabla^2 = \frac{4}{(\alpha + 1)} \begin{bmatrix} \frac{\alpha}{4} & \frac{1-\alpha}{4} & \frac{\alpha}{4} \\ \frac{1-\alpha}{4} & -1 & \frac{1-\alpha}{4} \\ \frac{\alpha}{4} & \frac{1-\alpha}{4} & \frac{\alpha}{4} \end{bmatrix}$$

`fspecial` creates Laplacian of Gaussian (LoG) filters using

$$h_g(n_1, n_2) = e^{-\frac{(n_1^2 + n_2^2)}{2\sigma^2}}$$

$$h(n_1, n_2) = \frac{(n_1^2 + n_2^2 - 2\sigma^2)h_g(n_1, n_2)}{2\pi\sigma^6 \sum_{n_1} \sum_{n_2} h_g}$$

`fspecial` creates averaging filters using

`ones(n(1), n(2)) / (n(1) * n(2))`

See Also

`conv2` | `edge` | `filter2` | `fsamp2` | `fwind1` | `fwind2` | `imfilter` | `imsharpen` | `del2`

Introduced before R2006a

ftrans2

2-D FIR filter using frequency transformation

Syntax

```
h = ftrans2(b, t)
h = ftrans2(b)
```

Description

`h = ftrans2(b, t)` produces the two-dimensional FIR filter `h` that corresponds to the one-dimensional FIR filter `b` using the transform `t`. (`ftrans2` returns `h` as a computational molecule, which is the appropriate form to use with `filter2`.) `b` must be a one-dimensional, Type I (even symmetric, odd-length) filter such as can be returned by `fir1`, `fir2`, or `remez` in the Signal Processing Toolbox software. The transform matrix `t` contains coefficients that define the frequency transformation to use. If `t` is `m`-by-`n` and `b` has length `Q`, then `h` is size $((m-1)*(Q-1)/2+1)$ -by- $((n-1)*(Q-1)/2+1)$.

`h = ftrans2(b)` uses the McClellan transform matrix `t`.

```
t = [1 2 1; 2 -4 2; 1 2 1]/8;
```

All inputs and outputs should be of class `double`.

Examples


Use `ftrans2` to design an approximately circularly symmetric two-dimensional bandpass filter with passband between 0.1 and 0.6 (normalized frequency, where 1.0 corresponds to half the sampling frequency, or π radians):

- 1 Since `ftrans2` transforms a one-dimensional FIR filter to create a two-dimensional filter, first design a one-dimensional FIR bandpass filter using the Signal Processing Toolbox function `remez`.

```
colormap(jet(64))
```




```
b = remez(10,[0 0.05 0.15 0.55 0.65 1],[0 0 1 1 0 0]);  
[H,w] = freqz(b,1,128,'whole');  
plot(w/pi-1,fftshift(abs(H)))
```



- 2** Use `ftrans2` with the default McClellan transformation to create the desired approximately circularly symmetric filter.

```
h = ftrans2(b);  
freqz2(h)
```



More About

Tips

The transformation below defines the frequency response of the two-dimensional filter returned by `ftrans2`.

$$H_{(\omega_1, \omega_2)} = B(\omega) \Big|_{\cos \omega = T(\omega_1, \omega_2)},$$

where $B(\omega)$ is the Fourier transform of the one-dimensional filter \mathbf{b} :

$$B(\omega) = \sum_{n=-N}^N b(n)e^{-j\omega n}$$

and $T(\omega_1, \omega_2)$ is the Fourier transform of the transformation matrix \mathbf{t} :

$$T(\omega_1, \omega_2) = \sum_{n_2} \sum_{n_1} t(n_1, n_2) e^{-j\omega_1 n_1} e^{-j\omega_2 n_2}.$$

The returned filter h is the inverse Fourier transform of $H(\omega_1, \omega_2)$:

$$h(n_1, n_2) = \frac{1}{(2\pi)^2} \int_{-\pi}^{\pi} \int_{-\pi}^{\pi} H(\omega_1, \omega_2) e^{j\omega_1 n_1} e^{j\omega_2 n_2} d\omega_1 d\omega_2.$$

References

- [1] Lim, Jae S., *Two-Dimensional Signal and Image Processing*, Englewood Cliffs, NJ, Prentice Hall, 1990, pp. 218-237.

See Also

conv2 | filter2 | fsamp2 | fwind1 | fwind2

Introduced before R2006a

fwind1

2-D FIR filter using 1-D window method

Syntax

```
h = fwind1(Hd, win)
h = fwind1(Hd, win1, win2)
h = fwind1(f1, f2, Hd, ...)
```

Description

`fwind1` designs two-dimensional FIR filters using the window method. `fwind1` uses a one-dimensional window specification to design a two-dimensional FIR filter based on the desired frequency response `Hd`. `fwind1` works with one-dimensional windows only; use `fwind2` to work with two-dimensional windows.

`h = fwind1(Hd, win)` designs a two-dimensional FIR filter `h` with frequency response `Hd`. (`fwind1` returns `h` as a computational molecule, which is the appropriate form to use with `filter2`.) `fwind1` uses the one-dimensional window `win` to form an approximately circularly symmetric two-dimensional window using Huang's method. You can specify `win` using windows from the Signal Processing Toolbox software, such as `boxcar`, `hamming`, `hanning`, `bartlett`, `blackman`, `kaiser`, or `chebwin`. If `length(win)` is `n`, then `h` is `n`-by-`n`.

`Hd` is a matrix containing the desired frequency response sampled at equally spaced points between `-1.0` and `1.0` (in normalized frequency, where `1.0` corresponds to half the sampling frequency, or π radians) along the *x* and *y* frequency axes. For accurate results, use frequency points returned by `freqspace` to create `Hd`. (See the entry for `freqspace` for more information.)

`h = fwind1(Hd, win1, win2)` uses the two one-dimensional windows `win1` and `win2` to create a separable two-dimensional window. If `length(win1)` is `n` and `length(win2)` is `m`, then `h` is `m`-by-`n`.

`h = fwind1(f1, f2, Hd, ...)` lets you specify the desired frequency response `Hd` at arbitrary frequencies (`f1` and `f2`) along the *x*- and *y*-axes. The frequency vectors `f1`

and `f2` should be in the range -1.0 to 1.0, where 1.0 corresponds to half the sampling frequency, or π radians. The length of the windows controls the size of the resulting filter, as above.

Class Support


The input matrix `Hd` can be of class `double` or of any integer class. All other inputs to `fwind1` must be of class `double`. All outputs are of class `double`.

Examples

Use `fwind1` to design an approximately circularly symmetric two-dimensional bandpass filter with passband between 0.1 and 0.5 (normalized frequency, where 1.0 corresponds to half the sampling frequency, or π radians):


- 1 Create a matrix `Hd` that contains the desired bandpass response. Use `freqspace` to create the frequency range vectors `f1` and `f2`.

```
[f1,f2] = freqspace(21,'meshgrid');
Hd = ones(21);
r = sqrt(f1.^2 + f2.^2);
Hd((r<0.1)|(r>0.5)) = 0;
colormap(jet(64))
mesh(f1,f2,Hd)
```



2 Design the filter using a one-dimensional Hamming window.

```
h = fwind1(Hd,hamming(21));  
freqz2(h)
```



More About

Algorithms

fwind1 takes a one-dimensional window specification and forms an approximately circularly symmetric two-dimensional window using Huang's method,

$$w(n_1, n_2) = w(t) \Big|_{t=\sqrt{n_1^2+n_2^2}},$$

where $w(t)$ is the one-dimensional window and $w(n_1, n_2)$ is the resulting two-dimensional window.

Given two windows, fwind1 forms a separable two-dimensional window:

$$w(n_1, n_2) = w_1(n_1)w_2(n_2).$$

fwind1 calls fwind2 with Hd and the two-dimensional window. fwind2 computes h using an inverse Fourier transform and multiplication by the two-dimensional window:

$$h_d(n_1, n_2) = \frac{1}{(2\pi)^2} \int_{-\pi}^{\pi} \int_{-\pi}^{\pi} H_d(\omega_1, \omega_2) e^{j\omega_1 n_1} e^{j\omega_2 n_2} d\omega_1 d\omega_2$$

$$h(n_1, n_2) = h_d(n_1, n_2)w(n_2, n_2).$$

References

- [1] Lim, Jae S., *Two-Dimensional Signal and Image Processing*, Englewood Cliffs, NJ, Prentice Hall, 1990.

See Also

`conv2` | `filter2` | `fsamp2` | `freqspace` | `ftrans2` | `fwind2`

Introduced before R2006a

fwind2

2-D FIR filter using 2-D window method

Syntax

```
h = fwind2(Hd, win)
h = fwind2(f1, f2, Hd, win)
```

Description

Use `fwind2` to design two-dimensional FIR filters using the window method. `fwind2` uses a two-dimensional window specification to design a two-dimensional FIR filter based on the desired frequency response `Hd`. `fwind2` works with two-dimensional windows; use `fwind1` to work with one-dimensional windows.

`h = fwind2(Hd, win)` produces the two-dimensional FIR filter `h` using an inverse Fourier transform of the desired frequency response `Hd` and multiplication by the window `win`. `Hd` is a matrix containing the desired frequency response at equally spaced points in the Cartesian plane. `fwind2` returns `h` as a computational molecule, which is the appropriate form to use with `filter2`. `h` is the same size as `win`.

For accurate results, use frequency points returned by `freqspace` to create `Hd`. (See the entry for `freqspace` for more information.)

`h = fwind2(f1, f2, Hd, win)` lets you specify the desired frequency response `Hd` at arbitrary frequencies (`f1` and `f2`) along the x - and y -axes. The frequency vectors `f1` and `f2` should be in the range -1.0 to 1.0 , where 1.0 corresponds to half the sampling frequency, or π radians. `h` is the same size as `win`.

Class Support


The input matrix `Hd` can be of class `double` or of any integer class. All other inputs to `fwind2` must be of class `double`. All outputs are of class `double`.

Examples

Use `fwind2` to design an approximately circularly symmetric two-dimensional bandpass filter with passband between 0.1 and 0.5 (normalized frequency, where 1.0 corresponds to half the sampling frequency, or π radians):


- 1 Create a matrix `Hd` that contains the desired bandpass response. Use `freqspace` to create the frequency range vectors `f1` and `f2`.

```
[f1,f2] = freqspace(21,'meshgrid');
Hd = ones(21);
r = sqrt(f1.^2 + f2.^2);
Hd((r<0.1)|(r>0.5)) = 0;
colormap(jet(64))
mesh(f1,f2,Hd)
```




- 2 Create a two-dimensional Gaussian window using `fspecial`.

```
win = fspecial('gaussian',21,2);
win = win ./ max(win(:)); % Make the maximum window value be 1.
mesh(win)
```



3 Design the filter using the window from step 2.

```
h = fwind2(Hd,win);  
freqz2(h)
```



More About

Algorithms

`fwind2` computes `h` using an inverse Fourier transform and multiplication by the two-dimensional window `win`.

$$h_d(n_1, n_2) = \frac{1}{(2\pi)^2} \int_{-\pi}^{\pi} \int_{-\pi}^{\pi} H_d(\omega_1, \omega_2) e^{j\omega_1 n_1} e^{j\omega_2 n_2} d\omega_1 d\omega_2$$

$$h(n_1, n_2) = h_d(n_1, n_2)w(n_1, n_2)$$

References

- [1] Lim, Jae S., *Two-Dimensional Signal and Image Processing*, Englewood Cliffs, NJ, Prentice Hall, 1990, pp. 202-213.

See Also

conv2 | filter2 | fsamp2 | freqspace | ftrans2 | fwind1

Introduced before R2006a

gabor

Create Gabor filter or Gabor filter bank

Syntax

```
g = gabor(wavelength,orientation)
g = gabor(___,Name,Value,___)
```

Description

`g = gabor(wavelength,orientation)` creates a Gabor filter with the specified `wavelength` (in pixels/cycle) and `orientation` (in degrees). If you specify `wavelength` or `orientation` as vectors, `gabor` returns an array of `gabor` objects, called a *filter bank*, that contain all the unique combinations of `wavelength` and `orientation`. For example, if `wavelength` is a vector of length 2 and `orientation` is a vector of length 3, then the output array `g` is a vector of length 6. To apply the Gabor filters to an image, use the `imgaborfilt` function.

`g = gabor(___,Name,Value,___)` creates an array of Gabor filters using name-value pairs to control aspects of Gabor filter design. If you specify a vector of values, the output array `g` contains all the unique combinations of the input values.

Examples

Construct Gabor Filter Array and Apply to Input Image

Create a sample image of a checkerboard.

```
A = checkerboard(20);
```

Create an array of Gabor filters.

```
wavelength = 20;
orientation = [0 45 90 135];
g = gabor(wavelength,orientation);
```


Apply the filters to the checkerboard image.

```
outMag = imgaborfilt(A,g);
```

Display the results.

```
outSize = size(outMag);  
outMag = reshape(outMag,[outSize(1:2),1,outSize(3)]);  
figure, montage(outMag,'DisplayRange',[]);  
title('Montage of gabor magnitude output images.');
```

Montage of gabor magnitude output images.



Construct Gabor Filter Array and Visualize Wavelength and Orientation

Create array of Gabor filters.

```
g = gabor([5 10],[0 90]);
```

Visualize the real part of the spatial convolution kernel of each Gabor filter in the array.


```
figure;
```

```


subplot(2,2,1)
for p = 1:length(g)
    subplot(2,2,p);
    imshow(real(g(p).SpatialKernel),[]);
    lambda = g(p).Wavelength;
    theta = g(p).Orientation;
    title(sprintf('Re[h(x,y)], \\\lambda = %d, \\\theta = %d',lambda,theta));
end

```


Re[h(x,y)], $\lambda = 5, \theta = 0$



Re[h(x,y)], $\lambda = 10, \theta = 0$



Re[h(x,y)], $\lambda = 5, \theta = 90$



Re[h(x,y)], $\lambda = 10, \theta = 90$



Input Arguments

wavelength — Wavelength of sinusoid
 numeric scalar in the range [2, Inf)

Wavelength of sinusoid, specified as a numeric scalar or vector, in pixels/cycle.

Example: `g = gabor(4,90);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

orientation — Orientation of filter in degrees

numeric scalar in the range [0 180]

Orientation of filter in degrees, specified as a numeric scalar in the range [0 180], where the orientation is defined as the normal direction to the sinusoidal plane wave.

Example: `g = gabor(4,90);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

Example: `g = gabor(4,90, 'SpatialFrequencyBandwidth', 1.5);`

'SpatialFrequencyBandwidth' — Define spatial-frequency bandwidth

1.0 (default) | numeric vector

A numeric vector that defines the spatial-frequency bandwidth in units of Octaves. The spatial-frequency bandwidth determines the cutoff of the filter response as frequency content in the input image varies from the preferred frequency, $1/\text{LAMBDA}$. Typical values for spatial-frequency bandwidth are in the range [0.5 2.5].

Example: `g = gabor(4,90, 'SpatialFrequencyBandwidth', 1.5);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

'SpatialAspectRatio' — Aspect ratio of Gaussian in spatial domain

0.5 (default) | numeric scalar

Aspect ratio of Gaussian in spatial domain, specified as a numeric vector that defines the ratio of the semi-major and semi-minor axes of the Gaussian envelope: `semi-minor/`

`semi-major`. This parameter controls the ellipticity of the Gaussian envelope. Typical values for spatial aspect ratio are in the range `[0.23 0.92]`.

Example: `g = gabor(4,90, 'SpatialAspectRatio',0.75);`

Data Types: `single | double | int8 | int16 | int32 | int64 | uint8 | uint16 | uint32 | uint64`

Output Arguments

g — Gabor filter array

Array of `gabor` objects

Gabor filter array, returned as an array of `gabor` objects.

See Also

`imgaborfilt`

Introduced in R2015b

getheight

Height of structuring element

Note: `getheight` will be removed in a future release. See `strel` for the current list of methods.

Syntax

```
H = getheight(SE)
```

Description

`H = getheight(SE)` returns an array the same size as `getnhood(SE)` containing the height associated with each of the structuring element neighbors. `H` is all zeros for a flat structuring element.

Class Support

`SE` is a STREL object. `H` is of class `double`.

Examples

```
se = strel(ones(3,3),magic(3));  
getheight(se)
```

Introduced before R2006a

getimage

Image data from axes

Syntax

```
A = getimage(h)
[x, y, A] = getimage(h)
[... , A, flag] = getimage(h)
[...] = getimage
```

Description

`A = getimage(h)` returns the first image data contained in the Handle Graphics object `h`. `h` can be a figure, axes, or image. `A` is identical to the image `CData`; it contains the same values and is of the same class (`uint8`, `uint16`, `double`, or `logical`) as the image `CData`. If `h` is not an image or does not contain an image, `A` is empty.

`[x, y, A] = getimage(h)` returns the image `XData` in `x` and the `YData` in `y`. `XData` and `YData` are two-element vectors that indicate the range of the x -axis and y -axis.

`[... , A, flag] = getimage(h)` returns an integer `flag` that indicates the type of image `h` contains. This table summarizes the possible values for `flag`.

Flag	Type of Image
0	Not an image; <code>A</code> is returned as an empty matrix
1	Indexed image
2	Intensity image with values in standard range ([0,1] for <code>single</code> and <code>double</code> arrays, [0,255] for <code>uint8</code> arrays, [0,65535] for <code>uint16</code> arrays)
3	Intensity data, but not in standard range
4	RGB image
5	Binary image

`[...] = getimage` returns information for the current axes object. It is equivalent to `[...] = getimage(gca)`.

Class Support

The output array **A** is of the same class as the image **CData**. All other inputs and outputs are of class **double**.

Note

For **int16** and **single** images, the image data returned by **getimage** is of class **double**, not **int16** or **single**. This is because the **getimage** function gets the data from the image object's **CData** property and image objects store **int16** and **single** image data as class **double**.

For example, create an image object of class **int16**. If you retrieve the **CData** from the object and check its class, it returns **double**.

```
h = imshow(ones(10,'int16'));  
class(get(h,'CData'))
```

Therefore, if you get the image data using the **getimage** function, the data it returns is also of class **double**. The **flag** return value is set to **3**.

```
[img,flag] = getimage(h);  
class(img)
```

The same is true for an image of class **single**. Getting the **CData** directly from the image object or by using **getimage**, the class of the returned data is **double**.

```
h = imshow(ones(10,'single'));  
class(get(h,'CData'))  
[img,flag] = getimage(h);  
class(img)
```

For images of class **single**, the **flag** return value is set to **2** because **single** and **double** share the same dynamic range.

Examples

After using **imshow** or **imtool** to display an image directly from a file, use **getimage** to get the image data into the workspace.

```
imshow rice.png  
I = getimage;
```

```
imshow cameraman.tif  
I = getimage(imgca);
```

See Also

[imshow](#) | [imshow](#)

Introduced before R2006a

getimagemodel

Image model object from image object

Syntax

```
imgmodel = getimagemodel(himage)
```

Description

`imgmodel = getimagemodel(himage)` returns the image model object associated with `himage`. `himage` must be a handle to an image object or an array of handles to image objects.

The return value `imgmodel` is an image model object. If `himage` is an array of handles to image objects, `imgmodel` is an array of image models.

If `himage` does not have an associated image model object, `getimagemodel` creates one.

Examples

```
h = imshow('bag.png');  
imgmodel = getimagemodel(h);
```

See Also

`imagemodel`

Introduced before R2006a

getline

Select polyline with mouse

Syntax

```
[x, y] = getline(fig)
[x, y] = getline(ax)
[x, y] = getline
[x, y] = getline(..., 'closed')
```

Description

`[x, y] = getline(fig)` lets you select a polyline in the current axes of figure `fig` using the mouse. Coordinates of the polyline are returned in `X` and `Y`. Use normal button clicks to add points to the polyline. A shift-, right-, or double-click adds a final point and ends the polyline selection. Pressing **Return** or **Enter** ends the polyline selection without adding a final point. Pressing **Backspace** or **Delete** removes the previously selected point from the polyline.

`[x, y] = getline(ax)` lets you select a polyline in the axes specified by the handle `ax`.

`[x, y] = getline` is the same as `[x,y] = getline(gcf)`.

`[x, y] = getline(..., 'closed')` animates and returns a closed polygon.

See Also

getpts | getrect

Introduced before R2006a

getneighbors

Structuring element neighbor locations and heights

Note: `getneighbors` will be removed in a future release. See `strel` for the current list of methods.

Syntax

```
[offsets, heights] = getneighbors(SE)
```

Description

`[offsets, heights] = getneighbors(SE)` returns the relative locations and corresponding heights for each of the neighbors in the structuring element object `SE`.

`offsets` is a P-by-N array where P is the number of neighbors in the structuring element and N is the dimensionality of the structuring element. Each row of `offsets` contains the location of the corresponding neighbor, relative to the center of the structuring element.

`heights` is a P-element column vector containing the height of each structuring element neighbor.

Class Support

`SE` is a STREL object. The return values `offsets` and `heights` are arrays of double-precision values.

Examples

```
se = strel([1 0 1],[5 0 -5])
```

```
[offsets,heights] = getneighbors(se)
se =
Nonflat STREL object containing 2 neighbors.
```

```
Neighborhood:
```

```
  1    0    1
```

```
Height:
```

```
  5    0   -5
```

```
offsets =
```

```
  0   -1
```

```
  0    1
```

```
heights =
```

```
  5   -5
```

Introduced before R2006a

getnhood

Structuring element neighborhood

Note: getnhood will be removed in a future release. See `strel` for the current list of methods.

Syntax

```
NHOOD = getnhood(SE)
```

Description

NHOOD = `getnhood(SE)` returns the neighborhood associated with the structuring element SE.

Class Support

SE is a STREL object. NHOOD is a `logical` array.

Examples

```
se = strel(eye(5));  
NHOOD = getnhood(se)
```

Introduced before R2006a

getpts

Specify points with mouse

Syntax

```
[x, y] = getpts(fig)
[x, y] = getpts(ax)
[x, y] = getpts
```

Description

`[x, y] = getpts(fig)` lets you choose a set of points in the current axes of figure `fig` using the mouse. Coordinates of the selected points are returned in `X` and `Y`.

Use normal button clicks to add points. A shift-, right-, or double-click adds a final point and ends the selection. Pressing **Return** or **Enter** ends the selection without adding a final point. Pressing **Backspace** or **Delete** removes the previously selected point.

`[x, y] = getpts(ax)` lets you choose points in the axes specified by the handle `ax`.

`[x, y] = getpts` is the same as `[x,y] = getpts(gcf)`.

See Also

`getline` | `getrect`

Introduced before R2006a

getrangefromclass

Default display range of image based on its class

Syntax

```
range = getrangefromclass(I)
```

Description

`range = getrangefromclass(I)` returns the default display range of the image `I`, based on its class type. The function returns `range`, a two-element vector specifying the display range in the form `[min max]`.

“Code Generation” on page 1-400 support: Yes.

“MATLAB Function Block” on page 1-400 support: Yes.

Class Support

`I` can be `uint8`, `uint16`, `int16`, `logical`, `single`, or `double`. `range` is of class `double`.

Note

For `single` and `double` data, `getrangefromclass` returns the range `[0 1]` to be consistent with the way `double` and `single` images are interpreted in MATLAB. For integer data, `getrangefromclass` returns the default display range of the class. For example, if the class is `uint8`, the dynamic range is `[0 255]`.

Examples

Read in the 16-bit DICOM image and get the default display range.

```
CT = dicomread('CT-MON02-16-ankle.dcm');  
r = getrangefromclass(CT)  
r =  
  
    -32768    32767
```

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

[intmin](#) | [intmax](#)

Introduced before R2006a

getrect

Specify rectangle with mouse

Syntax

```
rect = getrect
rect = getrect(fig)
rect = getrect(ax)
```

Description

`rect = getrect` lets you select a rectangle in the current axes using the mouse. Use the mouse to click and drag the desired rectangle. `rect` is a four-element vector with the form `[xmin ymin width height]`. To constrain the rectangle to be a square, use a shift- or right-click to begin the drag.

`rect = getrect(fig)` lets you select a rectangle in the current axes of figure `fig` using the mouse.

`rect = getrect(ax)` lets you select a rectangle in the axes specified by the handle `ax`.

Examples

Select a rectangle in an image of the moon:

```
imshow('moon.tif')
rect = getrect
```

See Also

`getline` | `getpts`

Introduced before R2006a

getsequence

Sequence of decomposed structuring elements

Note: `getsequence` will be removed in a future release. See `strel` for the current list of methods.

Syntax

`SEQ = getsequence(SE)`

Description

`SEQ = getsequence(SE)` returns the array of structuring elements `SEQ`, containing the individual structuring elements that form the decomposition of `SE`. `SE` can be an array of structuring elements. `SEQ` is equivalent to `SE`, but the elements of `SEQ` have no decomposition.

Class Support

`SE` and `SEQ` are arrays of `STREL` objects.

Examples

The `strel` function uses decomposition for square structuring elements larger than 3-by-3. Use `getsequence` to extract the decomposed structuring elements.

```
se = strel('square',5)
se =
Flat STREL object containing 25 neighbors.
Decomposition: 2 STREL objects containing a total of 10 neighbors
```

```
Neighborhood:
  1   1   1   1   1
```



```
1  1  1  1  1
1  1  1  1  1
1  1  1  1  1
1  1  1  1  1
```

```
seq = getsequence(se)
seq =
2x1 array of STREL objects
```

Use `imdilate` with the `'full'` option to see that dilating sequentially with the decomposed structuring elements really does form a 5-by-5 square:

```
imdilate(1,seq,'full')
```

Introduced before R2006a

gradientweight

Calculate weights for image pixels based on image gradient

Syntax

```
W = gradientweight(I)
W = gradientweight(I, sigma)
W = gradientweight(___, Name, Value, ...)
```

Description

`W = gradientweight(I)` calculates the pixel weight for each pixel in image `I` based on the gradient magnitude at that pixel, and returns the weight array `W`. The weight of a pixel is inversely related to the gradient values at the pixel location. Pixels with small gradient magnitude (smooth regions) have a large weight and pixels with large gradient magnitude (such as on the edges) have a small weight.

`W = gradientweight(I, sigma)` uses `sigma` as the standard deviation for the Derivative of Gaussian that is used for computing the image gradient.

`W = gradientweight(___, Name, Value, ...)` returns the weight array `W` using name-value pairs to control aspects of weight computation.

Examples

Segment Image Using Weights Derived from Image Gradient

This example segments an image using the Fast Marching Method based on the weights derived from the image gradient.

Read image and display it.

```
I = imread('coins.png');
imshow(I)
title('Original Image')
```

Original Image




Compute weights based on image gradient.

```
sigma = 1.5;  
W = gradientweight(I, sigma, 'RolloffFactor', 3, 'WeightCutoff', 0.25);
```

Select a seed location.


```
R = 70; C = 216;  
hold on;  
plot(C, R, 'r.', 'LineWidth', 1.5, 'MarkerSize', 15);  
title('Original Image with Seed Location')
```

Original Image with Seed Location




Segment the image using the weight array.

```
thresh = 0.1;  
[BW, D] = imsegfmm(W, C, R, thresh);  
figure, imshow(BW)  
title('Segmented Image')  
hold on;  
plot(C, R, 'r.', 'LineWidth', 1.5, 'MarkerSize',15);
```

Segmented Image

Geodesic distance matrix D can be thresholded using different thresholds to get different segmentation results.

```
figure, imshow(D)
title('Geodesic Distances')
hold on;
plot(C, R, 'r.', 'LineWidth', 1.5, 'MarkerSize', 15);
```



Input Arguments

I — Input image

grayscale image

Input image, specified as a grayscale image. Must be nonsparse.

Example: `I = imread('cameraman.tif');`

Data Types: `single` | `double` | `int8` | `uint8` | `int16` | `uint16` | `int32` | `uint32`

sigma — Standard deviation for Derivative of Gaussian

1.5 (default) | positive scalar

Standard deviation for Derivative of Gaussian, specified as a positive scalar of class `double`.

Example: `sigma = 1.0; W = gradientweight(I, sigma)`

Data Types: double

Name-Value Pair Arguments

Specify optional comma-separated pairs of **Name**, **Value** arguments. **Name** is the argument name and **Value** is the corresponding value. **Name** must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as **Name1**, **Value1**, ..., **NameN**, **ValueN**.

Example: `W =`

```
gradientweight(I,1.5,'RolloffFactor',3,'WeightCutoff',0.25);
```

'RolloffFactor' — Output weight roll-off factor

3 (default) | positive scalar

Output weight roll-off factor, specified as a positive scalar of class **double**. Controls how fast weight values fall as a function of gradient magnitude. When viewed as a 2-D plot, pixel intensity values might vary gradually at the edges of regions, creating a gentle slope. In your segmented image, you might want the edge to be more well-defined. Using the roll-off factor, you control the slope of the weight value curve at points where intensity values start to change. If you specify a high value, the output weight values fall off sharply around the edges of smooth regions. If you specify a low value, the output weight has a more gradual fall-off around the edges. The suggested range for this parameter is [0.5 4].

Example: `'RolloffFactor',3`

Data Types: double

'WeightCutoff' — Threshold for weight values

0.25 (default) | positive scale in the range [1e-3 1]

Threshold for weight values, specified as a positive scalar of class **double**. If you use this parameter to set a threshold on weight values, it suppresses any weight values less than the value you specify, setting these pixels to a small constant value (1e-3). This parameter can be useful in improving the accuracy of the output when you use the output weight array **W** as input to Fast Marching Method segmentation function, `imseggmm`.

Example: `'WeightCutoff',0.5`

Data Types: double

Output Arguments

W — Weight array

numeric array

Weight array, returned as a numeric array. The weight array is the same size as the input image, **I**. The weight array is of class **double**, unless **I** is **single**, in which case it is of class **single**.

More About

Tips

- `gradientweight` uses double-precision floating point operations for internal computations for all classes of **I**, except when **I** is of class **single**, in which case `gradientweight` uses single-precision floating point operations internally.

See Also

`graydiffweight` | `imsegfmm`

Introduced in R2014b

gray2ind

Convert grayscale or binary image to indexed image

Syntax

```
[X, map] = gray2ind(I,n)  
[X, map] = gray2ind(BW,n)
```

Description

`[X, map] = gray2ind(I,n)` converts the grayscale image `I` to an indexed image `X`. `n` specifies the size of the colormap, `gray(n)`. `n` must be an integer between 1 and 65536. If `n` is omitted, it defaults to 64.

`[X, map] = gray2ind(BW,n)` converts the binary image `BW` to an indexed image `X`. `n` specifies the size of the colormap, `gray(n)`. If `n` is omitted, it defaults to 2.

`gray2ind` scales and then rounds the intensity image to produce an equivalent indexed image.

Class Support

The input image `I` can be `logical`, `uint8`, `uint16`, `int16`, `single`, or `double` and must be a real and nonsparse. The image `I` can have any dimension. The class of the output image `X` is `uint8` if the colormap length is less than or equal to 256; otherwise it is `uint16`.

Examples

Convert a grayscale image into an indexed image and then view the result.

```
I = imread('cameraman.tif');  
[X, map] = gray2ind(I, 16);  
imshow(X, map);
```

See Also

`grayslice` | `ind2gray` | `mat2gray`

Introduced before R2006a

graycomatrix

Create gray-level co-occurrence matrix from image

Syntax

```
glcms = graycomatrix(I)
glcms = graycomatrix(I,Name,Value,...)
[glcms,SI] = graycomatrix(____)
```

Description

`glcms = graycomatrix(I)` creates a gray-level co-occurrence matrix (GLCM) from image `I`. Another name for a gray-level co-occurrence matrix is a *gray-level spatial dependence matrix*. Also, the word co-occurrence is frequently used in the literature without a hyphen, cooccurrence.

`graycomatrix` creates the GLCM by calculating how often a pixel with gray-level (grayscale intensity) value i occurs horizontally adjacent to a pixel with the value j . (You can specify other pixel spatial relationships using the 'Offsets' parameter.) Each element (i,j) in `glcm` specifies the number of times that the pixel with value i occurred horizontally adjacent to a pixel with value j .

`glcms = graycomatrix(I,Name,Value,...)` returns one or more gray-level co-occurrence matrices, depending on the values of the optional name/value pairs. Parameter names can be abbreviated, and case does not matter.

`[glcms,SI] = graycomatrix(____)` returns the scaled image, `SI`, used to calculate the gray-level co-occurrence matrix. The values in `SI` are between 1 and `NumLevels`.

Examples

Create Gray-Level Co-occurrence Matrix for Grayscale Image

Read a grayscale image into workspace.

```
I = imread('circuit.tif');
```

Calculate the gray-level co-occurrence matrix (GLCM) for the grayscale image. By default, `graycomatrix` calculates the GLCM based on horizontal proximity of the pixels: [0 1]. That is the pixel next to the pixel of interest on the same row. This example specifies a different offset: two rows apart on the same column.

```
glcm = graycomatrix(I, 'Offset', [2 0])
```

```
glcm =
```

```
Columns 1 through 6
```

14205	2107	126	0	0	0
2242	14052	3555	400	0	0
191	3579	7341	1505	37	0
0	683	1446	7184	1368	0
0	7	116	1502	10256	1124
0	0	0	2	1153	1435
0	0	0	0	0	0
0	0	0	0	0	0

```
Columns 7 through 8
```

0	0
0	0
0	0
0	0
0	0
0	0
0	0
0	0

Create Gray-Level Co-occurrence Matrix Returning Scaled Image

Create a simple 3-by-6 sample array.

```
I = [ 1 1 5 6 8 8; 2 3 5 7 0 2; 0 2 3 5 6 7]
```

```
I =
```

1	1	5	6	8	8
2	3	5	7	0	2
0	2	3	5	6	7

Calculate the gray-level co-occurrence matrix (GLCM) and return the scaled image used in the calculation. By specifying empty brackets for the `GrayLimits` parameter, the example uses the minimum and maximum grayscale values in the input image as limits.

```
[glcm, SI] = graycomatrix(I, 'NumLevels',9, 'GrayLimits',[])
```

```
glcm =
```

```

0 0 2 0 0 0 0 0 0
0 1 0 0 0 1 0 0 0
0 0 0 2 0 0 0 0 0
0 0 0 0 0 2 0 0 0
0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 2 1 0
0 0 0 0 0 0 0 1 1
1 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 1
```

```
SI =
```

```

2 2 6 7 9 9
3 4 6 8 1 3
1 3 4 6 7 8
```

Calculate GLCMs using Four Different Offsets

Read grayscale image into the workspace.

```
I = imread('cell.tif');
```

Define four offsets.

```
offsets = [0 1; -1 1; -1 0; -1 -1];
```

Calculate the GLCMs, returning the scaled image as well.

```
[glcms, SI] = graycomatrix(I, 'Offset',offsets);
```

Note how the function returns an array of four GLCMs.

```
whos
```

Name	Size	Bytes	Class	Attributes
I	159x191	30369	uint8	
SI	159x191	242952	double	
glcms	8x8x4	2048	double	
offsets	4x2	64	double	

Calculate Symmetric GLCM for Grayscale Image

Read grayscale image into the workspace.

```
I = imread('circuit.tif');
```

Calculate GLCM using the `Symmetric` option. The GLCM created when you set `Symmetric` to true is symmetric across its diagonal, and is equivalent to the GLCM described by Haralick (1973).

```
glcm = graycomatrix(I, 'Offset', [2 0], 'Symmetric', true)
```

```
glcm =
```

```
Columns 1 through 6
```

```

28410    4349    317         0         0         0
 4349   28104   7134    1083         7         0
 317     7134  14682   2951    153         0
 0       1083   2951  14368   2870         2
 0         7    153   2870  20512    2277
 0         0         0         2    2277    2870
 0         0         0         0         0         0
 0         0         0         0         0         0

```

```
Columns 7 through 8
```

```

0         0
0         0
0         0
0         0
0         0
0         0
0         0
0         0

```

Input Arguments

I — Input image

2-D, real, nonsparse, numeric or logical array

Input image, specified as a 2-D, real, nonsparse, numeric or logical array.

Example:

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1`, `Value1`, ..., `NameN`, `ValueN`.

Example:

'GrayLimits' — Range used scaling input image into gray levels

range specified by class (default) | two-element vector [`low` `high`]

Range used scaling input image into gray levels, specified as a two-element vector [`low` `high`]. If `N` is the number of gray levels (see parameter '`NumLevels`') to use for scaling, the range [`low` `high`] is divided into `N` equal width bins and values in a bin get mapped to a single gray level. Grayscale values less than or equal to `low` are scaled to 1. Grayscale values greater than or equal to `high` are scaled to '`NumLevels`'. If '`GrayLimits`' is set to [], `graycomatrix` uses the minimum and maximum grayscale values in `I` as limits, [`min(I(:))` `max(I(:))`], for example, [`0` `1`] for class `double` and [`-32768` `32767`] for class `int16`.

Example:

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

'NumLevels' — Number of gray levels

8 for numeric, 2 for binary (default) | integer

Number of gray levels, specified as an integer. For example, if `NumLevels` is 8, `graycomatrix` scales the values in `I` so they are integers between 1 and 8. The number of gray-levels determines the size of the gray-level co-occurrence matrix (`glcm`).

Example:

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`


'Offset' — Distance between the pixel of interest and its neighbor

[0 1] (default) | *p*-by-2 array of integers

Distance between the pixel of interest and its neighbor, specified as a *p*-by-2 array of integers. Each row in the array is a two-element vector, [`row_offset`, `col_offset`], that specifies the relationship, or *offset*, of a pair of pixels. `row_offset` is the number of rows between the pixel-of-interest and its neighbor. `col_offset` is the number of columns between the pixel-of-interest and its neighbor. Because the offset is often expressed as an angle, the following table lists the offset values that specify common angles, given the pixel distance *D*.

Angle	Offset
0	[0 D]
45	[-D D]
90	[-D 0]
135	[-D -D]

The figure illustrates the array: `offset = [0 1; -1 1; -1 0; -1 -1]`



Example:

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

'Symmetric' — Consider ordering of values`false (default) | true`

Consider ordering of values, specified as the Boolean value `true` or `false`. For example, when `'Symmetric'` is set to `true`, `graycomatrix` counts both 1,2 and 2,1 pairings when calculating the number of times the value 1 is adjacent to the value 2. When `'Symmetric'` is set to `false`, `graycomatrix` only counts 1,2 or 2,1, depending on the value of `'offset'`.

Example:

Data Types: `logical`

Output Arguments

g1cms — Gray-level co-occurrence matrix (or matrices)`double array`

Gray-level co-occurrence matrix (or matrices), returned as an `NumLevels-by-NumLevels-by-P` array of class `double`, where `P` is the number of offsets in `Offset`.

SI — Scaled image used in calculation of GLCM`double matrix`

Scaled image used in calculation of GLCM, returned as a `double` matrix the same size as the input image.


More About

Algorithms

`graycomatrix` calculates the GLCM from a scaled version of the image. By default, if `I` is a binary image, `graycomatrix` scales the image to two gray-levels. If `I` is an intensity image, `graycomatrix` scales the image to eight gray-levels. You can specify the number of gray-levels `graycomatrix` uses to scale the image by using the `'NumLevels'` parameter, and the way that `graycomatrix` scales the values using the `'GrayLimits'` parameter .

The following figure shows how `graycomatrix` calculates several values in the GLCM of the 4-by-5 image `I`. Element (1,1) in the GLCM contains the value 1 because there

is only one instance in the image where two, horizontally adjacent pixels have the values 1 and 1. Element (1,2) in the GLCM contains the value 2 because there are two instances in the image where two, horizontally adjacent pixels have the values 1 and 2. `graycomatrix` continues this processing to fill in all the values in the GLCM.



`graycomatrix` ignores pixel pairs if either of the pixels contains a NaN, replaces positive `Infs` with the value `NumLevels`, and replaces negative `Infs` with the value 1. `graycomatrix` ignores border pixels, if the corresponding neighbor pixel falls outside the image boundaries.

The GLCM created when `'Symmetric'` is set to `true` is symmetric across its diagonal, and is equivalent to the GLCM described by Haralick (1973). The GLCM produced by the following syntax, with `'Symmetric'` set to `true`

```
graycomatrix(I, 'offset', [0 1], 'Symmetric', true)
```

is equivalent to the sum of the two GLCMs produced by the following statements where `'Symmetric'` is set to `false`.

```
graycomatrix(I, 'offset', [0 1], 'Symmetric', false)
graycomatrix(I, 'offset', [0 -1], 'Symmetric', false)
```

References

- [1] Haralick, R.M., K. Shanmugan, and I. Dinstein, "Textural Features for Image Classification", IEEE Transactions on Systems, Man, and Cybernetics, Vol. SMC-3, 1973, pp. 610-621.

[2] Haralick, R.M., and L.G. Shapiro. Computer and Robot Vision: Vol. 1, Addison-Wesley, 1992, p. 459.

See Also

graycoprops

Introduced before R2006a

grayconnected

Select contiguous image region with similar gray values

Syntax

```
BW = grayconnected(I,row,column)
BW = grayconnected(I,row,column,tolerance)
```

Description

`BW = grayconnected(I,row,column)` finds connected regions of similar intensity in the grayscale image `I`. You specify the intensity value to use as a starting point, the *seed pixel*, by `row` and `column` indices. By default, `grayconnected` includes connected pixels with values in the range `[seedpixel-32,seedpixel+32]` for integer-valued images and within the range `[seedpixel-0.1,seedpixel+0.1]` for floating point images. `grayconnected` returns a binary mask image, `BW`, where all of the foreground pixels are 8-connected to the seed pixel at `(row, column)` by pixels of similar intensity.

`BW = grayconnected(I,row,column,tolerance)` finds connected regions of similar intensity in a grayscale image, where `tolerance` specifies the range of intensity values to include in the mask, as in `[(seedpixel-tolerance),(seedpixel+tolerance)]`.

“Code Generation” on page 1-425 support: Yes.

“MATLAB Function Block” on page 1-425 support: Yes.

Examples

Create Binary Mask from Connected Pixels

Create small sample image.

```
I = uint8([20 22 24 23 25 20 100
           21 10 12 13 12 30 6
           22 11 13 12 13 25 5])
```

```

23 13 13 13 13 20 5
24 13 13 12 12 13 5
25 26 5 28 29 50 6]);

```

Create mask image, specifying the seed location by row and column and the tolerance. Since the seed location specifies the pixel with the value **23** and the tolerance is **3**, the range of grayscale values is **[20,26]**.

```

seedrow = 4
seedcol = 1
tol = 3
BW = grayconnected(I,seedrow,seedcol,tol)

```

```
seedrow =
```

```
4
```

```
seedcol =
```

```
1
```

```
tol =
```

```
3
```

```
BW =
```

```

1 1 1 1 1 1 0
1 0 0 0 0 0 0
1 0 0 0 0 0 0
1 0 0 0 0 0 0
1 0 0 0 0 0 0
1 1 0 0 0 0 0

```

Input Arguments

I — Input grayscale image
real, nonsparse 2-D matrix

Input grayscale image, specified as a real, nonsparse, 2-D matrix.

Example: `BW = grayconnected(I,50,40);`

Data Types: `single | double | int8 | int16 | int32 | uint8 | uint16 | uint32`

row — Row index of seed location

real, positive, scalar integer.

Row index of seed location, specified as a real, positive, scalar integer.

Example: `BW = grayconnected(I,50,40);`

Data Types: `single | double | int8 | int16 | int32 | uint8 | uint16 | uint32`

column — Column index of seed location

real, positive, scalar integer

Column index of seed location, specified as a real, positive, scalar integer.

Example: `BW = grayconnected(I,50,40);`

Data Types: `single | double | int8 | int16 | int32 | uint8 | uint16 | uint32`

tolerance — Range of intensity values to include in the mask

32 for integer valued images, 0.1 for floating point images (default) | numeric scalar

Range of intensity values to include in the mask, specified as a numeric scalar.

The range is defined as $[(\text{seedvalue} - \text{tolerance}), (\text{seedvalue} + \text{tolerance})]$.

By default, `grayconnected` includes connected pixels with values in the range $[\text{seedpixel} - 32, \text{seedpixel} + 32]$ for integer-valued images and within the range $[\text{seedpixel} - 0.1, \text{seedpixel} + 0.1]$ for floating point images.

Example: `BW = grayconnected(I,50,40,5);`

Data Types: `single | double | int8 | int16 | int32 | uint8 | uint16 | uint32`

Output Arguments

BW — Mask binary image

logical array

Mask binary image, returned as a logical array where all of the foreground pixels are 8-connected to the seed pixel at `(row,column)` by pixels of similar intensity.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`bwselect` | `imfill`

Introduced in R2015b

graycoprops

Properties of gray-level co-occurrence matrix

Syntax

```
stats = graycoprops(glcm,properties)
```

Description

`stats = graycoprops(glcm,properties)` calculates the statistics specified in `properties` from the gray-level co-occurrence matrix `glcm`. `glcm` is an *m-by-n-by-p* array of valid gray-level co-occurrence matrices. If `glcm` is an array of GLCMs, `stats` is an array of statistics for each `glcm`.

`graycoprops` normalizes the gray-level co-occurrence matrix (GLCM) so that the sum of its elements is equal to 1. Each element (*r,c*) in the normalized GLCM is the joint probability occurrence of pixel pairs with a defined spatial relationship having gray level values *r* and *c* in the image. `graycoprops` uses the normalized GLCM to calculate `properties`.

Examples

Calculate Statistics from Gray-level Co-occurrence Matrix

Create simple sample GLCM.

```
glcm = [0 1 2 3;1 1 2 3;1 0 2 0;0 0 0 3]
```

```
glcm =
```

```
    0     1     2     3
    1     1     2     3
    1     0     2     0
    0     0     0     3
```

Calculate statistical properties of the GLCM.


```
stats = graycoprops(glcm)
```

```
stats =
```

```
    Contrast: 2.8947
    Correlation: 0.0783
    Energy: 0.1191
    Homogeneity: 0.5658
```

Calculate Contrast and Homogeneity from Multiple GLCMs

Read grayscale image into the workspace.

```
I = imread('circuit.tif');
```

Create two gray-level co-occurrence matrices (GLCM) from the image, specifying different offsets.

```
glcm = graycomatrix(I, 'Offset', [2 0; 0 2])
```

```
glcm(:,:,1) =
```

```
Columns 1 through 6
```

14205	2107	126	0	0	0
2242	14052	3555	400	0	0
191	3579	7341	1505	37	0
0	683	1446	7184	1368	0
0	7	116	1502	10256	1124
0	0	0	2	1153	1435
0	0	0	0	0	0
0	0	0	0	0	0

```
Columns 7 through 8
```

0	0
0	0
0	0
0	0
0	0
0	0
0	0

```
0 0

glcm(:,:,2) =

Columns 1 through 6

    13938    2615    204    4    0    0
    2406    14062    3311    630    23    0
    145    3184    7371    1650    133    0
    2    371    1621    6905    1706    0
    0    0    116    1477    9974    1173
    0    0    0    1    1161    1417
    0    0    0    0    0    0
    0    0    0    0    0    0

Columns 7 through 8

    0    0
    0    0
    0    0
    0    0
    0    0
    0    0
    0    0
    0    0
```

Get statistics on contrast and homogeneity of the image from the GLCMs.

```
stats = graycoprops(glcm,{'contrast','homogeneity'})
```

```
stats =
```

```
Contrast: [0.3420 0.3567]
Homogeneity: [0.8567 0.8513]
```

Input Arguments

glcm — Gray-level Co-occurrence Matrix

real, non-negative array of finite logical or numeric integers

Gray-level Co-occurrence Matrix, specified as a real, non-negative array of finite logical or numeric integers. Use the `graycomatrix` function to create a GLCM.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

properties — Statistical properties of the image derived from GLCM

'all' (default) | comma-separated list of strings | cell array of strings | space-separated string

Statistical properties of the image derived from GLCM, specified as a comma-separated list of strings, a cell array containing strings, the string 'all', or a space-separated string. You can specify any of the property name strings listed in this table. Property names can be abbreviated and are not case sensitive.

Property	Description	Formula
'Contrast'	Returns a measure of the intensity contrast between a pixel and its neighbor over the whole image. Range = $[0 \text{ (size(GLCM,1) - 1)^2}]$ Contrast is 0 for a constant image. The property Contrast is also known as <i>variance</i> and <i>inertia</i> .	$\sum_{i,j} i - j ^2 p(i, j)$
'Correlation'	Returns a measure of how correlated a pixel is to its neighbor over the whole image. Range = $[-1 \ 1]$ Correlation is 1 or -1 for a perfectly positively or negatively correlated image. Correlation is NaN for a constant image.	$\sum_{i,j} \frac{(i - \mu_i)(j - \mu_j)p(i, j)}{\sigma_i \sigma_j}$
'Energy'	Returns the sum of squared elements in the GLCM. Range = $[0 \ 1]$ Energy is 1 for a constant image.	$\sum_{i,j} p(i, j)^2$

Property	Description	Formula
	The property Energy is also known as <i>uniformity</i> , <i>uniformity of energy</i> , and <i>angular second moment</i> .	
'Homogeneity'	Returns a value that measures the closeness of the distribution of elements in the GLCM to the GLCM diagonal. Range = [0 1] Homogeneity is 1 for a diagonal GLCM.	$\sum_{i,j} \frac{p(i,j)}{1+ i-j }$

Data Types: char | cell

Output Arguments

stats — Statistics derived from the GLCM

structure

Statistics derived from the GLCM, returned as a structure with fields that are specified by `properties`. Each field contains a 1-by- p array, where p is the number of gray-level co-occurrence matrices in GLCM. For example, if GLCM is an 8-by-8-by-3 array and `properties` is 'Energy', `stats` is a structure containing the field `Energy`, which contains a 1-by-3 array.

See Also

`graycomatrix`

Introduced before R2006a

graydiffweight

Calculate weights for image pixels based on grayscale intensity difference

Syntax

```
W = graydiffweight(I,refGrayVal)
W = graydiffweight(I,mask)
W = graydiffweight(I,C,R)
W = graydiffweight(___, Name, Value, ...)
```

Description

`W = graydiffweight(I,refGrayVal)` computes the pixel weight for each pixel in the grayscale image `I`. The weight is the absolute value of the difference between the intensity of the pixel and the reference grayscale intensity specified by the scalar `refGrayVal`. Pick a reference grayscale intensity value that is representative of the object you want to segment. The weights are returned in the array `W`, which is the same size as input image `I`.

The weight of a pixel is inversely related to the absolute value of the grayscale intensity difference at the pixel location. For pixels with small difference (regions with intensity close to `refGrayVal`), the weight value is large, and for pixels with large difference (regions with intensity very different from `refGrayVal`), the weight value is small.

`W = graydiffweight(I,mask)` computes the pixel weights for each pixel in the grayscale image `I`, where the reference grayscale intensity value is the average of the intensity values of all the pixels in `I` that are marked as logical true in `mask`. Using the average of several pixels to calculate the reference grayscale intensity value can be more effective than using a single reference intensity value, as in the previous syntax.

`W = graydiffweight(I,C,R)` computes the pixel weights for each pixel in the grayscale image `I`, where the reference grayscale intensity value is the average of the intensity values of the pixel locations specified by `C` and `R`. `C` and `R` are vectors containing the column and row indices of the pixel locations. `C` and `R` must contain values which are valid pixel indices in `I`.

`W = graydiffweight(___, Name, Value, ...)` returns the weight array `W` using name-value pairs to control aspects of weight computation.

Examples

Calculate Grayscale Intensity Difference Weights

This example segments an object in an image using Fast Marching Method using grayscale intensity difference weights calculated from the intensity values at the seed locations.

Read image and display it.

```
I = imread('cameraman.tif');  
imshow(I)  
title('Original Image')
```

Original Image



Specify row and column index of pixels for use a reference grayscale intensity value.

```
seedpointR = 159;  
seedpointC = 67;
```

Calculate the grayscale intensity difference weight array for the image and display it. The example does log-scaling of W for better visualization.

```
W = graydiffweight(I, seedpointC, seedpointR, 'GrayDifferenceCutoff', 25);  
figure, imshow(log(W), [])
```



Segment the image using the grayscale intensity difference weight array. Specify the same seed point vectors you used to create the weight array.

```
thresh = 0.01;  
BW = imsegfmm(W, seedpointC, seedpointR, thresh);  
figure, imshow(BW)  
title('Segmented Image')
```

Segmented Image



Input Arguments

I — Input image

grayscale image

Input image, specified as a grayscale image. Must be nonsparse.

Example: `I = imread('cameraman.tif');`

Data Types: `single` | `double` | `int8` | `uint8` | `int16` | `uint16` | `int32` | `uint32`

refGrayVal — Reference grayscale intensity value

scalar

Reference grayscale intensity value, specified as a scalar.

Example: `110`

Data Types: `double`

mask — Reference grayscale intensity mask

logical array

Reference grayscale intensity mask, specified as a logical array, the same size as `I`.

Example: `mask = false(size(I)); mask(170,70) = true;`

Data Types: `logical`

C — Column index of reference pixels

numeric vector

Column index of reference pixels, specified as a numeric (integer-valued) vector.

Example: `C = [50,70];`

Data Types: `double`

R — Row index of reference pixel

numeric vector

Row index of reference pixel, specified as a numeric (integer-valued) vector.

Example: `R = [50,90];`

Data Types: `double`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

Example: `W = graydiffweight(I, seedpointC, seedpointR, 'GrayDifferenceCutoff', 25);`

'RolloffFactor' — Output weight roll-off factor

0.5 (default) | positive scalar

Output weight roll-off factor, specified as a positive scalar of class `double`. Controls how fast the output weight falls as the function of the absolute difference between an intensity value and the reference grayscale intensity. When viewed as a 2-D plot, pixel

intensity values might vary gradually at the edges of regions, creating a gentle slope. In your segmented image, you might want the edge to be more well-defined. Using the roll-off factor, you control the slope of the weight value curve at points where intensity values start to change. If you specify a high value, the output weight values fall off sharply around the regions of change intensity. If you specify a low value, the output weight has a more gradual fall-off around the regions of changing intensity. The suggested range for this parameter is [0.5 4].

Example: 'RolloffFactor',3

Data Types: double

'GrayDifferenceCutoff' — Threshold for absolute grayscale intensity difference values

Inf (default) | nonnegative scalar

Threshold for absolute grayscale intensity difference values, specified as a nonnegative scalar of class **double**. This parameter puts a hard threshold on the absolute grayscale intensity difference values, and strongly suppresses the output weight value for any pixel whose absolute grayscale intensity difference from the reference grayscale intensity is greater than the cutoff by assigning them the smallest weight value. When the output weight array **W** is used for Fast Marching Method based segmentation (as input to `imsegfmm`), this parameter can be useful in improving the accuracy of the segmentation output. Default value of this parameter is `Inf`, which means that there is no hard cutoff.

Example: 'GrayDifferenceCutoff',25

Data Types: double

Output Arguments

W — Weight array

numeric array

Weight array, specified as numeric array the same size as **I**. **W** is of class **double**, unless **I** is of class **single**, in which case **W** is of class **single**.

See Also

`gradientweight` | `imsegfmm`

Introduced in R2014b

graydist

Gray-weighted distance transform of grayscale image

Syntax

```
T = graydist(A,mask)
T = graydist(A,C,R)
T = graydist(A,ind)
T = graydist(...,method)
```

Description

`T = graydist(A,mask)` computes the gray-weighted distance transform of the grayscale image `A`. Locations where `mask` is `true` are seed locations.

`T = graydist(A,C,R)` uses vectors `C` and `R` to specify the row and column coordinates of seed locations.

`T = graydist(A,ind)` specifies the linear indices of seed locations using the vector `ind`.

`T = graydist(...,method)` specifies an alternate distance metric. `method` determines the chamfer weights that are assigned to the local neighborhood during outward propagation. Each pixel's contribution to the geodesic time is based on the chamfer weight in a particular direction multiplied by the pixel intensity.

Input Arguments

A

Grayscale image.

mask

Logical image the same size as `A` that specifies seed locations.

C,R

Numeric vectors that contain the positive integer row and column coordinates of the seed locations. Coordinate values are valid C,R subscripts in A.

ind

Numeric vector of positive integer, linear indices of seed locations.

method

Type of distance metric. `method` can have any of these values.

Method	Description
'cityblock'	In 2-D, the cityblock distance between (x_1, y_1) and (x_2, y_2) is $ x_1 - x_2 + y_1 - y_2 $.
'chessboard'	The chessboard distance is $\max(x_1 - x_2 , y_1 - y_2)$.
'quasi-euclidean'	The quasi-Euclidean distance is $ x_1 - x_2 + (\sqrt{2} - 1) y_1 - y_2 $, $ x_1 - x_2 > y_1 - y_2 $ $(\sqrt{2} - 1) x_1 - x_2 + y_1 - y_2 $, otherwise.

Default: 'chessboard'

Output Arguments

T

Array the same size as A that specifies the gray-weighted distance transform. If the input numeric type of A is `double`, the output numeric type of T is `double`. If the input is any other numeric type, the output T is single.

Class Support

A can be numeric or logical, and it must be nonsparse. `mask` is a logical array of the same size as A. C, R, and `ind` are numeric vectors that contain positive integer values.

The output `T` is an array of the same size as `A`. If the input numeric type of `A` is `double`, the output `T` is `double`. If the input is any other numeric type, the output `T` is `single`.

Examples

Matrices generated by the `magic` function have equal row, column and diagonal sums. The minimum path between the upper left and lower right corner is along the diagonal. The following example demonstrates how the `graydist` function computes this path:

```
A = magic(3)
T1 = graydist(A,1,1);
T2 = graydist(A,3,3);
T = T1 + T2
```

A =

```
    8    1    6
    3    5    7
    4    9    2
```

T =

```
   10   11   17
   13   10   13
   17   17   10
```

As expected, there is a constant-value minimum path along the diagonal.

More About

Algorithms

`graydist` uses the geodesic time algorithm described in Soille, P., *Generalized geodesy via geodesic time*, Pattern Recognition Letters, vol.15, December 1994; pp. 1235–1240

The basic equation for geodesic time along a path is:

$$\tau_f(P) = \frac{f(p_o)}{2} + \frac{f(p_l)}{2} + \sum_{i=1}^{l-1} f(p_i)$$

See Also

`bwdist` | `bwdistgeodesic` | `watershed`

Introduced in R2011b

grayscale

Convert grayscale image to indexed image using multilevel thresholding

Syntax

```
X = grayscale(I, n)
```

Description

`X = grayscale(I, n)` thresholds the intensity image `I` returning an indexed image in `X`. `grayscale` uses the threshold values:

$$\frac{1}{n}, \frac{2}{n}, \dots, \frac{n-1}{n}$$

`X = grayscale(I, v)` thresholds the intensity image `I` using the values of `v`, where `v` is a vector of values between 0 and 1, returning an indexed image in `X`.

You can view the thresholded image using `imshow(X, map)` with a colormap of appropriate length.


Class Support

The input image `I` can be of class `uint8`, `uint16`, `int16`, `single`, or `double`, and must be nonsparse. Note that the threshold values are always between 0 and 1, even if `I` is of class `uint8` or `uint16`. In this case, each threshold value is multiplied by 255 or 65535 to determine the actual threshold to use.

The class of the output image `X` depends on the number of threshold values, as specified by `n` or `length(v)`. If the number of threshold values is less than 256, then `X` is of class `uint8`, and the values in `X` range from 0 to `n` or `length(v)`. If the number of threshold values is 256 or greater, `X` is of class `double`, and the values in `X` range from 1 to `n+1` or `length(v)+1`.

Examples

```
I = imread('snowflakes.png');  
X = grayslice(I,16);  
imshow(I)  
figure, imshow(X,jet(16))
```



See Also

[gray2ind](#)

Introduced before R2006a

graythresh

Global image threshold using Otsu's method

Syntax

```
level = graythresh(I)  
[level EM] = graythresh(I)
```

Description

`level = graythresh(I)` computes a global threshold (`level`) that can be used to convert an intensity image to a binary image with `im2bw`. `level` is a normalized intensity value that lies in the range `[0, 1]`.

The `graythresh` function uses Otsu's method, which chooses the threshold to minimize the intraclass variance of the black and white pixels.

Multidimensional arrays are converted automatically to 2-D arrays using `reshape`. The `graythresh` function ignores any nonzero imaginary part of `I`.

`[level EM] = graythresh(I)` returns the effectiveness metric, `EM`, as the second output argument. The effectiveness metric is a value in the range `[0 1]` that indicates the effectiveness of the thresholding of the input image. The lower bound is attainable only by images having a single gray level, and the upper bound is attainable only by two-valued images.

Class Support

The input image `I` can be of class `uint8`, `uint16`, `int16`, `single`, or `double` and it must be nonsparse. The return value `level` is a double scalar. The effectiveness metric `EM` is a double scalar.

Examples

```
I = imread('coins.png');
```

```
level = graythresh(I);  
BW = im2bw(I,level);  
imshow(BW)
```

References

- [1] Otsu, N., "A Threshold Selection Method from Gray-Level Histograms," *IEEE Transactions on Systems, Man, and Cybernetics*, Vol. 9, No. 1, 1979, pp. 62-66.

See Also

[im2bw](#) | [imquantize](#) | [multithresh](#) | [rgb2ind](#)

Introduced before R2006a

hdrread

Read high dynamic range (HDR) image

Syntax

```
hdr = hdrread(filename)
```

Description

`hdr = hdrread(filename)` reads the high dynamic range (HDR) image from the file specified by `filename`. `hdr` is an m-by-n-by-3 RGB array in the range `[0, inf)` of type `single`. For scene-referred data sets, these values usually are scene illumination in radiance units. To display these images, use an appropriate tone-mapping operator.

Class Support

The output image `hdr` is an m-by-n-by-3 image of type `single`.

Examples

```
hdr = hdrread('office.hdr');  
rgb = tonemap(hdr);  
imshow(rgb);
```

References

- [1] Larson, Greg W. "Radiance File Formats"<http://radsite.lbl.gov/radiance/refer/filefmts.pdf>

See Also

`hdrwrite` | `makehdr` | `tonemap`

Introduced in R2007b

hdrwrite

Write Radiance high dynamic range (HDR) image file

Syntax

```
hdrwrite(hdr, filename)
```

Description

`hdrwrite(hdr, filename)` creates a Radiance high dynamic range (HDR) image file from HDR, a single- or double-precision high dynamic range RGB image. The HDR file with the name `filename` uses run-length encoding to minimize file size.

See Also

`hdrread` | `makehdr` | `tonemap`

Introduced in R2008a

histeq

Enhance contrast using histogram equalization

Syntax

```
J = histeq(I,hgram)
J = histeq(I,n)
[J, T] = histeq(I)
[gpuarrayJ, gpuarrayT] = histeq(gpuarrayI, ___)
newmap = histeq(X, map, hgram)
newmap = histeq(X, map)
[newmap, T] = histeq(X, ___)
```

Description

`J = histeq(I,hgram)` transforms the intensity image `I` so that the histogram of the output intensity image `J` with `length(hgram)` bins approximately matches `hgram`. The vector `hgram` should contain integer counts for equally spaced bins with intensity values in the appropriate range: `[0, 1]` for images of class `double`, `[0, 255]` for images of class `uint8`, and `[0, 65535]` for images of class `uint16`. `histeq` automatically scales `hgram` so that `sum(hgram) = prod(size(I))`. The histogram of `J` will better match `hgram` when `length(hgram)` is much smaller than the number of discrete levels in `I`.

`J = histeq(I,n)` transforms the intensity image `I`, returning in `J` an intensity image with `n` discrete gray levels. A roughly equal number of pixels is mapped to each of the `n` levels in `J`, so that the histogram of `J` is approximately flat. (The histogram of `J` is flatter when `n` is much smaller than the number of discrete levels in `I`.) The default value for `n` is 64.

`[J, T] = histeq(I)` returns the grayscale transformation that maps gray levels in the image `I` to gray levels in `J`.

`[gpuarrayJ, gpuarrayT] = histeq(gpuarrayI, ___)` performs the histogram equalization on a GPU. The input image and the output image are `gpuArrays`. This syntax requires the Parallel Computing Toolbox.

`newmap = histeq(X, map, hgram)` transforms the colormap associated with the indexed image `X` so that the histogram of the gray component of the indexed image `(X, newmap)` approximately matches `hgram`. The `histeq` function returns the transformed colormap in `newmap`. `length(hgram)` must be the same as `size(map, 1)`.

`newmap = histeq(X, map)` transforms the values in the colormap so that the histogram of the gray component of the indexed image `X` is approximately flat. It returns the transformed colormap in `newmap`.

`[newmap, T] = histeq(X, ___)` returns the grayscale transformation `T` that maps the gray component of `map` to the gray component of `newmap`.

“Code Generation” on page 1-451 support: Yes.

“MATLAB Function Block” on page 1-452 support: Yes.

Class Support

`I` can be of class `uint8`, `uint16`, `int16`, `single`, or `double`. The output image `J` has the same class as `I`. The optional output `T` is always of class `double`.

`gpuarrayI` is a `gpuArray` of class `uint8`, `uint16`, `int16`, `single`, or `double`. The output image `gpuarrayJ` has the same class as `gpuarrayI`. The optional output `gpuarrayT` is always a `gpuArray` of class `double`.

`X` can be of class `uint8`, `single`, or `double`. The output colormap `newmap` is always of class `double`.

Examples


Enhance the contrast of an intensity image using histogram equalization.

```
I = imread('tire.tif');  
J = histeq(I);  
imshow(I)  
figure, imshow(J)
```




Display a histogram of the original image.

```
figure; imhist(I,64)
```



Compare it to a histogram of the processed image.

```
figure; imhist(J,64)
```

This example performs the same histogram equalization on the GPU.

```
I = gpuArray(imread('tire.tif'));
J = histeq(I);
figure
imshow(I), figure, imshow(J)
```

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic MATLAB Host Computer target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, `histeq` does not support indexed images.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

When using `histeq` in the MATLAB Function Block, the input argument `N` must be a compile-time constant.

Algorithms

When you supply a desired histogram `hgram`, `histeq` chooses the grayscale transformation T to minimize

$$|c_1(T(k)) - c_0(k)|,$$

where c_0 is the cumulative histogram of `A`, c_1 is the cumulative sum of `hgram` for all intensities k . This minimization is subject to the constraints that T must be monotonic and $c_1(T(a))$ cannot overshoot $c_0(a)$ by more than half the distance between the histogram counts at a . `histeq` uses the transformation $b = T(a)$ to map the gray levels in `X` (or the colormap) to their new values.

If you do not specify `hgram`, `histeq` creates a flat `hgram`,

```
hgram = ones(1,n)*prod(size(A))/n;
```

and then applies the previous algorithm.

See Also

`brighten` | `imhist` | `imadjust` | `gpuArray`

Introduced before R2006a

hough

Hough transform

Syntax

```
[H,theta,rho] = hough(BW)  
[H,theta,rho] = hough(BW,Name,Value,...)
```

Description

`[H,theta,rho] = hough(BW)` computes the Standard Hough Transform (SHT) of the binary image `BW`. The `hough` function is designed to detect lines. The function uses the parametric representation of a line: $\rho = x \cdot \cos(\theta) + y \cdot \sin(\theta)$. The function returns `rho`, the distance from the origin to the line along a vector perpendicular to the line, and `theta`, the angle in degrees between the x -axis and this vector. The function also returns the Standard Hough Transform, `H`, which is a parameter space matrix whose rows and columns correspond to `rho` and `theta` values respectively. For more information, see “Algorithms” on page 1-458.

`[H,theta,rho] = hough(BW,Name,Value,...)` computes the Standard Hough Transform (SHT) of the binary image `BW`, where named parameters affect the computation.

“Code Generation” on page 1-458 support: Yes.

“MATLAB Function Block” on page 1-458 support: Yes.

Examples

Compute and Display Hough Transform

Read image and convert to intensity image.

```
RGB = imread('gantrycrane.png');
```

```
I = rgb2gray( RGB );
```

Extract edges.

```
BW = edge( I, 'canny' );
```

Calculate Hough transform.

```
[H,T,R] = hough( BW, 'RhoResolution', 0.5, 'ThetaResolution', 0.5 );
```


Display the original image and the Hough matrix.

```
subplot( 2, 1, 1 );  
imshow( RGB );  
title( 'gantrycrane.png' );  
subplot( 2, 1, 2 );  
imshow( imadjust( mat2gray( H ), 'XData', T, 'YData', R, ...  
    'InitialMagnification', 'fit' ) );  
title( 'Hough transform of gantrycrane.png' );  
xlabel( '\theta' ), ylabel( '\rho' );  
axis on, axis normal, hold on;  
colormap( hot );
```

gantrycrane.png



Hough transform of gantrycrane.png



Compute Hough Transform Over Limited Theta Range

Read image and convert it to grayscale.

```
RGB = imread('gantrycrane.png');  
I = rgb2gray(RGB);
```

Extract edges.


```
BW = edge(I, 'canny');
```

Calculate the Hough transform.

```
[H,T,R] = hough(BW, 'Theta', 44:0.5:46);
```

Display the Hough transform.

```
figure
imshow(imadjust(mat2gray(H)), 'XData',T, 'YData',R, ...
       'InitialMagnification','fit');
title('Limited Theta Range Hough Transform of Gantrycrane Image');
xlabel('\theta'), ylabel('\rho');
axis on, axis normal;
colormap(hot)
```



- “Detect Lines in Images Using Hough”

Input Arguments

BW — Binary image

real, 2-D, nonsparse logical or numeric array

Binary image, specified as a real, 2-D, nonsparse logical or numeric array.

Example: `[H,T,R] = hough(BW);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1,Value1,...,NameN,ValueN`.

Example: `[H,T,R] = hough(BW, 'RhoResolution',0.5, 'ThetaResolution',0.5);`

'RhoResolution' — Spacing of Hough transform bins along the *rho* axis

1 (default) | real, numeric scalar between 0 and `norm(size(BW))`, exclusive

Spacing of Hough transform bins along the *rho* axis, specified as a real, numeric scalar between 0 and `norm(size(BW))`, exclusive.

Example: `[H,T,R] = hough(BW, 'RhoResolution',0.5);`

Data Types: `double`

'Theta' — *Theta* value for the corresponding column of the output matrix H

-90:89 (default) | real, numeric vector

Theta value for the corresponding column of the output matrix H, specified as a real, numeric vector within the range [-90, 90).

Example: `[H,T,R] = hough(BW, 'ThetaResolution',0.5);`

Data Types: `double`

Output Arguments

H — Hough transform matrix

numeric array

Hough transform matrix, returned as a numeric array, *nrho*-by-*ntheta* in size. The rows and columns correspond to `rho` and `theta` values. For more information, see “Algorithms” on page 1-458.

theta — Angle in degrees between the *x*-axis and the *rho* vector

numeric array

Angle in degrees between the *x*-axis and the *rho* vector, returned as a numeric array of class `double`. For more information, see “Algorithms” on page 1-458.

rho — Distance from the origin to the line along a vector perpendicular to the line

numeric array

Distance from the origin to the line along a vector perpendicular to the line, returned as a numeric array of class `double`. For more information, see “Algorithms” on page 1-458.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, note the following:

- The optional parameters '`Theta`' and '`RhoResolution`' must be compile-time string constants.
- The optional `Theta` vector must have a bounded size.

MATLAB Function Block


You can use this function in the MATLAB Function Block in Simulink.

Algorithms

The Standard Hough Transform (SHT) uses the parametric representation of a line:

$$\rho = x \cdot \cos(\theta) + y \cdot \sin(\theta)$$

The variable ρ is the distance from the origin to the line along a vector perpendicular to the line. θ is the angle of the perpendicular projection from the origin to the line measured in degrees clockwise from the positive x -axis. The range of θ is $-90^\circ \leq \theta < 90^\circ$. The angle of the line itself is $\theta + 90^\circ$, also measured clockwise with respect to the positive x -axis.



The SHT is a parameter space matrix whose rows and columns correspond to ρ and θ values respectively. The elements in the SHT represent accumulator cells. Initially, the value in each cell is zero. Then, for every non-background point in the image, ρ is calculated for every θ . ρ is rounded off to the nearest allowed row in SHT. That accumulator cell is incremented. At the end of this procedure, a value of Q in $SHT(\rho, \theta)$ means that Q points in the xy -plane lie on the line specified by $\theta(\theta)$ and $\rho(\rho)$. Peak values in the SHT represent potential lines in the input image.

The Hough transform matrix, H , is $n\rho$ -by- $n\theta$ where:

$$n\rho = 2 * (\text{ceil}(D/\text{RhoResolution})) + 1, \text{ and}$$

$$D = \text{sqrt}((\text{numRowsInBW} - 1)^2 + (\text{numColsInBW} - 1)^2).$$

rho values range from `-diagonal` to `diagonal`, where
`diagonal = RhoResolution*ceil(D/RhoResolution)`.

`ntheta = length(theta)`

See Also

`houghlines` | `houghpeaks`

Introduced before R2006a

houghlines

Extract line segments based on Hough transform

Syntax

```
lines = houghlines(BW,theta,rho,peaks)
lines = houghlines( ___,Name,Value,...)
```

Description

`lines = houghlines(BW,theta,rho,peaks)` extracts line segments in the image `BW` associated with particular bins in a Hough transform. `theta` and `rho` are vectors returned by function `hough`. `peaks` is a matrix returned by the `houghpeaks` function that contains the row and column coordinates of the Hough transform bins to use in searching for line segments. The return value `lines` is a structure array whose length equals the number of merged line segments found.

`lines = houghlines(___,Name,Value,...)` extracts line segments in the image `BW`, where named parameters affect the operation.

“Code Generation” on page 1-467 support: Yes.

MATLAB Function Block support: No.

Examples

Find Line Segments and Highlight longest segment

Read image into workspace.

```
I = imread('circuit.tif');
```

Rotate the image.


```
rotI = imrotate(I,33,'crop');
```

Create a binary image.

```
BW = edge(rotI, 'canny');
```


Create the Hough transform using the binary image.

```
[H,T,R] = hough(BW);
imshow(H,[], 'XData',T, 'YData',R,...
        'InitialMagnification','fit');
xlabel('\theta'), ylabel('\rho');
axis on, axis normal, hold on;
```



Find peaks in the Hough transform of the image.

```
P = houghpeaks(H,5, 'threshold',ceil(0.3*max(H(:))));
x = T(P(:,2)); y = R(P(:,1));
plot(x,y, 's', 'color', 'white');
```




Find lines and plot them.

```
lines = houghlines(BW,T,R,P,'FillGap',5,'MinLength',7);
figure, imshow(rotI), hold on
max_len = 0;
for k = 1:length(lines)
    xy = [lines(k).point1; lines(k).point2];
    plot(xy(:,1),xy(:,2),'LineWidth',2,'Color','green');

    % Plot beginnings and ends of lines
    plot(xy(1,1),xy(1,2),'x','LineWidth',2,'Color','yellow');
    plot(xy(2,1),xy(2,2),'x','LineWidth',2,'Color','red');


    % Determine the endpoints of the longest line segment
```

```
len = norm(lines(k).point1 - lines(k).point2);  
if ( len > max_len)  
    max_len = len;  
    xy_long = xy;  
end  
end
```



Highlight the longest line segment by coloring it cyan.

```
plot(xy_long(:,1),xy_long(:,2), 'LineWidth',2,'Color','cyan');
```



Input Arguments

BW — Binary image

real, 2-D, nonsparse logical or numeric array

Binary image, specified as a real, 2-D, nonsparse logical or numeric array.

Example: `lines = houghlines(BW,T,R,P);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

theta — Line rotation angle in radians

real, 2-D, nonsparse numeric array

Line rotation angle in radians, specified as a real, 2-D, nonsparse logical or numeric array.

Example: `lines = houghlines(BW,T,R,P);`

Data Types: double

rho — Distance from the coordinate origin

real, 2-D, nonsparse logical or numeric array

Distance from the coordinate origin, specified as a real, 2-D, nonsparse logical or numeric array. The coordinate origin is the top-left corner of the image (0,0).

Example: `lines = houghlines(BW,T,R,P);`

Data Types: double

peaks — Row and column coordinates of Hough transform bins

real, nonsparse numeric matrix

Row and column coordinates of Hough transform bins, specified as a real, nonsparse numeric array.

Example: `lines = houghlines(BW,T,R,P);`

Data Types: double

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1,Value1,...,NameN,ValueN`.

Example: `lines = houghlines(BW,T,R,P,'FillGap',5,'MinLength',7);`

'FillGap' — Distance between two line segments associated with the same Hough transform bin

20 (default) | positive real scalar

Distance between two line segments associated with the same Hough transform bin, specified as a positive real scalar. When the distance between the line segments is less than the value specified, the `houghlines` function merges the line segments into a single line segment.

Example: `lines = houghlines(BW,T,R,P,'FillGap',5);`

Data Types: double

'MinLength' – Minimum line length

40 (default) | positive real scalar

Minimum line length, specified as a positive real scalar. `houghlines` discards lines that are shorter than the value specified.

Example: `lines = houghlines(BW,T,R,P,'MinLength',7);`

Data Types: double

Output Arguments

lines – Lines found

structure array

Lines found, returned as a structure array whose length equals the number of merged line segments found. Each element of the structure array has these fields:

Field	Description
<code>point1</code>	Two element vector [X Y] specifying the coordinates of the end-point of the line segment
<code>point2</code>	Two element vector [X Y] specifying the coordinates of the end-point of the line segment
<code>theta</code>	Angle in degrees of the Hough transform bin
<code>rho</code>	rho axis position of the Hough transform bin

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

The optional parameter names `'FillGap'` and `'MinLength'` must be compile-time string constants. Their associated values need not be compile-time constants.

See Also

hough | houghpeaks

Introduced before R2006a

houghpeaks

Identify peaks in Hough transform

Syntax

```
peaks = houghpeaks(H,numpeaks)
peaks = houghpeaks( ___,Name,Value,...)
```

Description

`peaks = houghpeaks(H,numpeaks)` locates peaks in the Hough transform matrix, `H`, generated by the `hough` function. `numpeaks` specifies the maximum number of peaks to identify. The function returns `peaks` a matrix that holds the row and column coordinates of the peaks.

`peaks = houghpeaks(___,Name,Value,...)` locates peaks in the Hough transform matrix, where named parameters control aspects of the operation.

“Code Generation” on page 1-472 support: Yes.

“MATLAB Function Block” on page 1-472 support: Yes.

Examples

Locate and Display Peaks in Hough Transform of Rotated Image

Read image into workspace.

```
I = imread('circuit.tif');
```

Create binary image.


```
BW = edge(imrotate(I,50,'crop'),'canny');
```

Create Hough transform of image.

```
[H,T,R] = hough(BW);
```

Find peaks in the Hough transform of the image and plot them.

```
P = houghpeaks(H,2);  
imshow(H,[],'XData',T,'YData',R,'InitialMagnification','fit');  
xlabel('\theta'), ylabel('\rho');  
axis on, axis normal, hold on;  
plot(T(P(:,2)),R(P(:,1)),'s','color','white');
```



Input Arguments

H — Hough transform matrix
numeric array

Hough transform matrix, specified as a numeric array of class `double`. The rows and columns correspond to `rho` and `theta` values. Use the `hough` function to create a Hough transform matrix.

Data Types: `double`

numpeaks — Maximum number of peaks to identify

1 (default) | positive integer scalar

Maximum number of peaks to identify, specified as a numeric scalar.

Data Types: `double`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

Example: `P = houghpeaks(H,2, 'Threshold',15);`

'Threshold' — Minimum value to be considered a peak

$0.5 * \max(H(:))$ (default) | nonnegative numeric scalar

Minimum value to be considered a peak, specified as a nonnegative numeric scalar. The value can be any value between 0 and `Inf`.

Data Types: `double`

'NHoodSize' — Size of suppression neighborhood

smallest odd values greater than or equal to $\text{size}(H)/50$ (default) | two-element vector of positive odd integers

Size of suppression neighborhood, specified as a two-element vector of positive odd integers. The *suppression neighborhood* is the neighborhood around each peak that is set to zero after the peak is identified.

Data Types: `double`

Output Arguments

peaks — Row and column coordinates of peaks found

Q -by-2 matrix

Row and column coordinates of peaks found, returned as a Q -by-2 matrix, where the value Q can range from 0 to `numpeaks`.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

The optional parameter names 'Threshold' and 'NHoodSize' must be compile-time string constants. Their associated values need not be compile-time constants.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`hough` | `houghlines`

Introduced before R2006a

iccfind

Search for ICC profiles

Syntax

```
P = iccfind(directory)
[P, descriptions] = iccfind(directory)
[...] = iccfind(directory, pattern)
```

Description

`P = iccfind(directory)` searches for all of the ICC profiles in the directory specified by `directory`. The function returns `P`, a cell array of structures containing profile information.

`[P, descriptions] = iccfind(directory)` searches for all of the ICC profiles in the specified directory and returns `P`, a cell array of structures containing profile information, and `descriptions`, a cell array of text strings, where each string describes the corresponding profile in `P`. Each text string is the value of the `Description.String` field in the profile information structure.

`[...] = iccfind(directory, pattern)` returns all of the ICC profiles in the specified directory with the given `pattern` in their `Description.String` fields. `iccfind` performs case-insensitive pattern matching.

Note To improve performance, `iccfind` caches copies of the ICC profiles in memory. Adding or modifying profiles might not change the results of `iccfind`. To clear the cache, use the `clear functions` command.

Examples

Get all the ICC profiles in the default system directory where profiles are stored.

```
profiles = iccfind(iccroot);
```

Get a listing of all the ICC profiles with text strings that describe each profile.

```
[profiles, descriptions ] = iccfind(iccroot);
```

Find the profiles whose descriptions contain the text string **RGB**.

```
[profiles, descriptions] = iccfind(iccroot, 'rgb');
```

See Also

`iccread` | `iccroot` | `iccwrite`

Introduced before R2006a

iccread

Read ICC profile

Syntax

`P = iccread(filename)`

Description

`P = iccread(filename)` reads the International Color Consortium (ICC) color profile information from the file specified by `filename`. The file can be either an ICC profile file or a TIFF file containing an embedded ICC profile. To determine if a TIFF file contains an embedded ICC profile, use the `imfinfo` function to get information about the file and look for the `ICCProfileOffset` field. `iccread` looks for the file in the current directory, a directory on the MATLAB path, or in the directory returned by `iccroot`, in that order.

`iccread` returns the profile information in the structure `P`, a 1-by-1 structure array whose fields contain the data structures (called tags) defined in the ICC specification. `iccread` can read profiles that conform with either Version 2 (ICC.1:2001-04) or Version 4 (ICC.1:2001-12) of the ICC specification. For more information about ICC profiles, visit the ICC web site, www.color.org.

ICC profiles provide color management systems with the information necessary to convert color data between native device color spaces and device independent color spaces, called the Profile Connection Space (PCS). You can use the profile as the source or destination profile with the `makecform` function to compute color space transformations.

The number of fields in `P` depends on the profile class and the choices made by the profile creator. `iccread` returns all the tags for a given profile, both public and private. Private tags and certain public tags are left as encoded `uint8` data. The following table lists fields that are found in any profile structure generated by `iccread`, in the order they appear in the structure.

Field	Data Type	Description
Header	1-by-1 struct array	Profile header fields

Field	Data Type	Description
TagTable	n-by-3 cell array	Profile tag table
Copyright	Text string	Profile copyright notice
Description	1-by-1 struct array	The <code>String</code> field in this structure contains a text string describing the profile.
MediaWhitepoint	double array	XYZ tristimulus values of the device's media white point
PrivateTags	m-by-2 cell array	Contents of all the private tags or tags not defined in the ICC specifications. The tag signatures are in the first column, and the contents of the tags are in the second column. Note that <code>iccread</code> leaves the contents of these tags in unsigned 8-bit encoding.
Filename	Text string	Name of the file containing the profile

Additionally, `P` might contain one or more of the following transforms:

- Three-component, matrix-based transform: A simple transform that is often used to transform between the RGB and XYZ color spaces. If this transform is present, `P` contains a field called `MatTRC`.
- N-component LUT-based transform: A transform that is used for transforming between color spaces that have a more complex relationship. This type of transform is found in any of the following fields in `P`:

<code>AToB0</code>	<code>BToA0</code>	<code>Preview0</code>
<code>AToB1</code>	<code>BToA1</code>	<code>Preview1</code>
<code>AToB2</code>	<code>BToA2</code>	<code>Preview2</code>
<code>AToB3</code>	<code>BToA3</code>	<code>Gamut</code>

Examples

The example reads the ICC profile that describes a typical PC computer monitor.

```
P = iccread('sRGB.icm')
```

P =

```

    Header: [1x1 struct]
    TagTable: {17x3 cell}
    Copyright: 'Copyright (c) 1999 Hewlett-Packard Company'
    Description: [1x1 struct]
    MediaWhitePoint: [0.9505 1 1.0891]
    MediaBlackPoint: [0 0 0]
    DeviceMfgDesc: [1x1 struct]
    DeviceModelDesc: [1x1 struct]
    ViewingCondDesc: [1x1 struct]
    ViewingConditions: [1x1 struct]
        Luminance: [76.0365 80 87.1246]
    Measurement: [1x36 uint8]
    Technology: [115 105 103 32 0 0 0 0 67 82 84 32]
    MatTRC: [1x1 struct]
    PrivateTags: {}
    Filename: 'sRGB.icm'

```

The profile header provides general information about the profile, such as its class, color space, and PCS. For example, to determine the source color space, view the `ColorSpace` field in the `Header` structure.

`P.Header.ColorSpace`

ans =

RGB

See Also

`applycform` | `iccfind` | `iccroot` | `iccwrite` | `isicc` | `makecform`

Introduced before R2006a

iccroot

Find system default ICC profile repository

Syntax

```
rootdir = iccroot
```

Description

`rootdir = iccroot` returns the system directory containing ICC profiles. Additional profiles can be stored in other directories, but this is the default location used by the color management system.

Note Only Windows and Mac OS X platforms are supported.

Examples

Return information on all the profiles in the root directory.

```
iccfind(iccroot)
```

See Also

```
iccfind | iccread | iccwrite
```

Introduced before R2006a

iccwrite

Write ICC color profile to disk file

Syntax

```
P_new = iccwrite(P, filename)
```

Description

`P_new = iccwrite(P, filename)` writes the International Color Consortium (ICC) color profile data in structure `P` to the file specified by `filename`.

`P` is a structure representing an ICC profile in the data format returned by `iccread` and used by `makecform` and `applycform` to compute color-space transformations. `P` must contain all the tags and fields required by the ICC profile specification. Some fields may be inconsistent, however, because of interactive changes to the structure. For instance, the tag table may not be correct because tags may have been added, deleted, or modified since the tag table was constructed. `iccwrite` makes any necessary corrections to the profile structure before writing it to the file and returns this corrected structure in `P_new`.

Note Because some applications use the profile description string in the ICC profile to present choices to users, the ICC recommends modifying the profile description string in the ICC profile data before writing the data to a file. Each profile should have a unique description string. For more information, see the example.

`iccwrite` can write the color profile data using either Version 2 (ICC.1:2001-04) or Version 4 (ICC.1:2001-12) of the ICC specification, depending on the value of the `Version` field in the file profile header. If any required fields are missing, `iccwrite` errors. For more information about ICC profiles, visit the ICC web site, www.color.org.

Note `iccwrite` does not perform automatic conversions from one version of the ICC specification to another. Such conversions have to be done manually, by adding fields or modifying fields. Use `isicc` to validate a profile.

Examples

Read a profile into the MATLAB workspace and export the profile data to a new file. The example changes the profile description string in the profile data before writing the data to a file.

```
P = iccread('monitor.icm');  
  
P.Description.String  
  
ans =  
  
sgC4_050102_d50.pf  
  
P.Description.String = 'my new description';  
  
pmon = iccwrite(P, 'monitor2.icm');
```

See Also

[applycform](#) | [isicc](#) | [iccread](#) | [makecform](#)

Introduced before R2006a

idct2

2-D inverse discrete cosine transform

Syntax

```
B = idct2(A)
B = idct2(A,m,n)
B = idct2(A,[m n])
```

Description

`B = idct2(A)` returns the two-dimensional inverse discrete cosine transform (DCT) of `A`.

`B = idct2(A,m,n)` pads `A` with 0's to size `m`-by-`n` before transforming. If `[m n] < size(A)`, `idct2` crops `A` before transforming.

`B = idct2(A,[m n])` same as above.

For any `A`, `idct2(dct2(A))` equals `A` to within roundoff error.

Class Support

The input matrix `A` can be of class `double` or of any numeric class. The output matrix `B` is of class `double`.

Examples

Create a DCT matrix.

```
RGB = imread('autumn.tif');
I = rgb2gray(RGB);
J = dct2(I);
imshow(log(abs(J)),[]), colormap(jet), colorbar
```

Set values less than magnitude 10 in the DCT matrix to zero, then reconstruct the image using the inverse DCT function `idct2`.

```
J(abs(J)<10) = 0;
K = idct2(J);
figure, imshow(I)
figure, imshow(K,[0 255])
```

More About

Algorithms

`idct2` computes the two-dimensional inverse DCT using:

$$A_{mn} = \sum_{p=0}^{M-1} \sum_{q=0}^{N-1} \alpha_p \alpha_q B_{pq} \cos \frac{\pi(2m+1)p}{2M} \cos \frac{\pi(2n+1)q}{2N}, \quad \begin{matrix} 0 \leq m \leq M-1 \\ 0 \leq n \leq N-1 \end{matrix}$$

where

$$\alpha_p = \begin{cases} \frac{1}{\sqrt{M}}, & p=0 \\ \sqrt{\frac{2}{M}}, & 1 \leq p \leq M-1 \end{cases}$$

and

$$\alpha_q = \begin{cases} \frac{1}{\sqrt{N}}, & q=0 \\ \sqrt{\frac{2}{N}}, & 1 \leq q \leq N-1 \end{cases}.$$

References

- [1] Jain, A. K., *Fundamentals of Digital Image Processing*, Englewood Cliffs, NJ, Prentice Hall, 1989, pp. 150-153.

[2] Pennebaker, W. B., and J. L. Mitchell, *JPEG: Still Image Data Compression Standard*, New York, Van Nostrand Reinhold, 1993.

See Also

dct2 | dctmtx | fft2 | ifft2

Introduced before R2006a

ifanbeam

Inverse fan-beam transform

Syntax

```
I = ifanbeam(F,D)
I = ifanbeam(...,param1,val1,param2,val2,...)
[I,H] = ifanbeam(...)
```

Description

`I = ifanbeam(F,D)` reconstructs the image `I` from projection data in the two-dimensional array `F`. Each column of `F` contains fan-beam projection data at one rotation angle. `ifanbeam` assumes that the center of rotation is the center point of the projections, which is defined as `ceil(size(F,1)/2)`.

The fan-beam spread angles are assumed to be the same increments as the input rotation angles split equally on either side of zero. The input rotation angles are assumed to be stepped in equal increments to cover `[0:359]` degrees.

`D` is the distance from the fan-beam vertex to the center of rotation.

`I = ifanbeam(...,param1,val1,param2,val2,...)` specifies parameters that control various aspects of the `ifanbeam` reconstruction, described in the following table. Parameter names can be abbreviated, and case does not matter. Default values are in braces (`{}`).

Parameter	Description
'FanCoverage'	String specifying the range through which the beams are rotated. { 'cycle' } — Rotate through the full range <code>[0,360)</code> . 'minimal' — Rotate the minimum range necessary to represent the object.

Parameter	Description
'FanRotationIncrement'	Positive real scalar specifying the increment of the rotation angle of the fan-beam projections, measured in degrees. See <code>fanbeam</code> for details.
'FanSensorGeometry'	String specifying how sensors are positioned. 'arc' — Sensors are spaced equally along a circular arc at distance <i>D</i> from the center of rotation. Default value is 'arc' 'line' — Sensors are spaced equally along a line, the closest point of which is distance <i>D</i> from the center of rotation. See <code>fanbeam</code> for details.
'FanSensorSpacing'	Positive real scalar specifying the spacing of the fan-beam sensors. Interpretation of the value depends on the setting of 'FanSensorGeometry'. If 'FanSensorGeometry' is set to 'arc' (the default), the value defines the angular spacing in degrees. Default value is 1. If 'FanSensorGeometry' is 'line', the value specifies the linear spacing. Default value is 1. See <code>fanbeam</code> for details.
'Filter'	String specifying the name of a filter. See <code>iradon</code> for details.
'FrequencyScaling'	Scalar in the range (0,1] that modifies the filter by rescaling its frequency axis. See <code>iradon</code> for details.

Parameter	Description
'Interpolation'	<p>Text string specifying the type of interpolation used between the parallel-beam and fan-beam data.</p> <p>'nearest' — Nearest-neighbor</p> <p>{ 'linear' } — Linear</p> <p>'spline' — Piecewise cubic spline</p> <p>'pchip' — Piecewise cubic Hermite (PCHIP)</p> <p>'v5cubic' — The cubic interpolation from MATLAB 5</p>
'OutputSize'	<p>Positive scalar specifying the number of rows and columns in the reconstructed image.</p> <p>If 'OutputSize' is not specified, <code>ifanbeam</code> determines the size automatically.</p> <p>If you specify 'OutputSize', <code>ifanbeam</code> reconstructs a smaller or larger portion of the image, but does not change the scaling of the data.</p> <hr/> <p>Note: If the projections were calculated with the <code>fanbeam</code> function, the reconstructed image might not be the same size as the original image.</p>

`[I,H] = ifanbeam(...)` returns the frequency response of the filter in the vector H.

Notes

`ifanbeam` converts the fan-beam data to parallel beam projections and then uses the filtered back projection algorithm to perform the inverse Radon transform. The filter is designed directly in the frequency domain and then multiplied by the FFT of the projections. The projections are zero-padded to a power of 2 before filtering to prevent spatial domain aliasing and to speed up the FFT.

Class Support

The input arguments, `F` and `D`, can be `double` or `single`. All other numeric input arguments must be `double`. The output arguments are `double`.

Examples

Example 1

This example creates a fan-beam transformation of the phantom head image and then calls the `ifanbeam` function to recreate the phantom image from the fan-beam transformation.

```
ph = phantom(128);
d = 100;
F = fanbeam(ph,d);
I = ifanbeam(F,d);
imshow(ph), figure, imshow(I);
```

Example 2

This example illustrates use of the `ifanbeam` function with the `'fancoverage'` option set to `'minimal'`.

```
ph = phantom(128);
P = radon(ph);
[F,obeta,otheta] = para2fan(P,100,...
    'FanSensorSpacing',0.5,...
    'FanCoverage','minimal',...
    'FanRotationIncrement',1);
phReconstructed = ifanbeam(F,100,...
    'FanSensorSpacing',0.5,...
    'Filter','Shepp-Logan',...
    'OutputSize',128,...
    'FanCoverage','minimal',...
    'FanRotationIncrement',1);
imshow(ph), figure, imshow(phReconstructed)
```

References

- [1] Kak, A. C., and M. Slaney, *Principles of Computerized Tomographic Imaging*, New York, NY, IEEE Press, 1988.

See Also

fan2para | iradon | fanbeam | para2fan | phantom | radon

Introduced before R2006a

im2bw

Convert image to binary image, based on threshold

Syntax

```
BW = im2bw(I, level)
BW = im2bw(X, map, level)
BW = im2bw(RGB, level)
```

Description

`BW = im2bw(I, level)` converts the grayscale image `I` to a binary image. The output image `BW` replaces all pixels in the input image with luminance greater than `level` with the value 1 (white) and replaces all other pixels with the value 0 (black). Specify `level` in the range [0,1]. This range is relative to the signal levels possible for the image's class. Therefore, a `level` value of 0.5 is midway between black and white, regardless of class. To compute the `level` argument, you can use the function `graythresh`. If you do not specify `level`, `im2bw` uses the value 0.5.

`BW = im2bw(X, map, level)` converts the indexed image `X` with colormap `map` to a binary image.

`BW = im2bw(RGB, level)` converts the truecolor image `RGB` to a binary image.

If the input image is not a grayscale image, `im2bw` converts the input image to grayscale, and then converts this grayscale image to binary by thresholding.


Class Support

The input image can be of class `uint8`, `uint16`, `single`, `int16`, or `double`, and must be nonsparse. The output image `BW` is of class `logical`. `I` and `X` must be 2-D. RGB images are M-by-N-by-3.

Examples

Convert an Indexed Image To a Binary Image

```
load trees
BW = im2bw(X,map,0.4);
imshow(X,map), figure, imshow(BW)
```





See Also

`graythresh` | `ind2gray` | `rgb2gray`

Introduced before R2006a

im2col

Rearrange image blocks into columns

Syntax

```
B = im2col(A,[m n],block_type)
B = im2col(A,'indexed',...)
```

Description

`B = im2col(A,[m n],block_type)` rearranges image blocks into columns. `block_type` is a string that can have one of these values. The default value is enclosed in braces (`{}`).

Value	Description
'distinct'	Rearranges each <i>distinct</i> m -by- n block in the image A into a column of B . <code>im2col</code> pads A with 0's, if necessary, so its size is an integer multiple of m -by- n . If $A = [A_{11} \ A_{12}; \ A_{21} \ A_{22}]$, where each A_{ij} is m -by- n , then $B = [A_{11}(:) \ A_{12}(:) \ A_{21}(:) \ A_{22}(:)]$.
{'sliding'}	Converts each <i>sliding</i> m -by- n block of A into a column of B , with no zero padding. B has $m*n$ rows and contains as many columns as there are m -by- n neighborhoods of A . If the size of A is $[mm \ nn]$, then the size of B is $(m*n)$ -by- $((mm-m+1)*(nn-n+1))$.

For the sliding block case, each column of B contains the neighborhoods of A reshaped as `NHOOD(:)` where `NHOOD` is a matrix containing an m -by- n neighborhood of A . `im2col` orders the columns of B so that they can be reshaped to form a matrix in the normal way. For Examples, suppose you use a function, such as `sum(B)`, that returns a scalar for each column of B . You can directly store the result in a matrix of size $(mm-m+1)$ -by- $(nn-n+1)$, using these calls.

```
B = im2col(A,[m n],'sliding');
C = reshape(sum(B),mm-m+1,nn-n+1);
```

`B = im2col(A,'indexed',...)` processes A as an indexed image, padding with 0's if the class of A is `uint8` or `uint16`, or 1's if the class of A is `double`.

Class Support

The input image **A** can be numeric or logical. The output matrix **B** is of the same class as the input image.

Examples

Calculate the local mean using a [2 2] neighborhood with zero padding:

```
A = reshape(linspace(0,1,16),[4 4])'  
B = im2col(A,[2 2])  
M = mean(B)  
newA = col2im(M,[1 1],[3 3])
```

The output appears like this:

```
newA =  
  
    0.1667    0.2333    0.3000  
    0.4333    0.5000    0.5667  
    0.7000    0.7667    0.8333
```

See Also

[blockproc](#) | [col2im](#) | [colfilt](#) | [nlfilter](#)

Introduced before R2006a

im2int16

Convert image to 16-bit signed integers

Syntax

```
I2 = im2int16(I)
RGB2 = im2int16(RGB)
I = im2int16(BW)
gpuarrayB = im2int16(gpuarrayA, ___ )
```

Description

`I2 = im2int16(I)` converts the intensity image `I` to `int16`, rescaling the data if necessary. If the input image is of class `int16`, the output image is identical to it.

`RGB2 = im2int16(RGB)` converts the truecolor image `RGB` to `int16`, rescaling the data if necessary.

`I = im2int16(BW)` converts the binary image `BW` to an `int16` intensity image, changing false-valued elements to `-32768` and true-valued elements to `32767`.

`gpuarrayB = im2int16(gpuarrayA, ___)` performs the conversion on a GPU. The input image and output image are `gpuArrays`. This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-495 support: Yes.

“MATLAB Function Block” on page 1-495 support: Yes.

Class Support

Intensity and truecolor images can be `uint8`, `uint16`, `int16`, `single`, `double`, or `logical`. Binary images must be `logical`. The output image is `int16`.

Intensity and truecolor `gpuArray` images can be `uint8`, `uint16`, `int16`, `logical`, `single`, or `double`. Binary `gpuArray` images must be `logical`. The output `gpuArray` image is `int16`.

Examples

Convert array to `int16`.

```
I = reshape(linspace(0,1,20),[5 4])
I2 = im2int16(I)
```

I1 =

```

      0      0.2632      0.5263      0.7895
0.0526      0.3158      0.5789      0.8421
0.1053      0.3684      0.6316      0.8947
0.1579      0.4211      0.6842      0.9474
0.2105      0.4737      0.7368      1.0000
```

I2 =

```

-32768 -15522  1724  18970
-29319 -12073  5173  22419
-25870  -8624  8623  25869
-22420  -5174 12072  29318
-18971  -1725 15521  32767
```

Convert array to `int16` on a GPU.

```
I1 = gpuArray(reshape(linspace(0,1,20),[5 4]))
I2 = im2int16(I1)
```

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

[im2double](#) | [im2single](#) | [im2uint8](#) | [im2uint16](#) | [int16](#) | [gpuArray](#)

Introduced before R2006a

im2java2d

Convert image to Java buffered image

Syntax

```
jimage = im2java2d(I)  
jimage = im2java2d(X,MAP)
```

Description

`jimage = im2java2d(I)` converts the image `I` to an instance of the Java image class `java.awt.image.BufferedImage`. The image `I` can be an intensity (grayscale), RGB, or binary image.

`jimage = im2java2d(X,MAP)` converts the indexed image `X` with colormap `MAP` to an instance of the Java class `java.awt.image.BufferedImage`.

Note The `im2java2d` function works with the Java 2D API. The `im2java` function works with the Java Abstract Windowing Toolkit (AWT).

Class Support

Intensity, indexed, and RGB input images can be of class `uint8`, `uint16`, or `double`. Binary input images must be of class `logical`.

Examples

Read an image into the MATLAB workspace and then use `im2java2d` to convert it into an instance of the Java class `java.awt.image.BufferedImage`.

```
I = imread('moon.tif');  
javaImage = im2java2d(I);  
frame = javax.swing.JFrame;
```

```
icon = javax.swing.ImageIcon(javaImage);  
label = javax.swing.JLabel(icon);  
frame.getContentPane().add(label);  
frame.pack  
frame.show
```

Introduced before R2006a

im2single

Convert image to single precision

Syntax

```
I2 = im2single(I)
RGB2 = im2single(RGB)
I = im2single(BW)
X2 = im2single(X, 'indexed')
gpuarrayB = im2single(gpuarrayA, ___)
```

Description

`I2 = im2single(I)` converts the intensity image `I` to single, rescaling the data if necessary. If the input image is of class `single`, the output image is identical to it.

`RGB2 = im2single(RGB)` converts the truecolor image `RGB` to single, rescaling the data if necessary.

`I = im2single(BW)` converts the binary image `BW` to a single-precision intensity image.

`X2 = im2single(X, 'indexed')` converts the indexed image `X` to single precision, offsetting the data if necessary.

`gpuarrayB = im2single(gpuarrayA, ___)` performs the conversion on a GPU. The input image and the output image are `gpuArrays`. This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-501 support: Yes.

“MATLAB Function Block” on page 1-501 support: Yes.

Class Support

Intensity and truecolor images can be `uint8`, `uint16`, `int16`, `logical`, `single`, or `double`. Indexed images can be `uint8`, `uint16`, `double` or `logical`. Binary input images must be `logical`. The output image is `single`.

If input `gpuArray gpuarrayA` is an intensity and truecolor image, it can be `uint8`, `uint16`, `int16`, `logical`, `single`, or `double`. If `gpuarrayA` is an indexed image, it can be `uint8`, `uint16`, `double` or `logical`. If `gpuarrayA` is a binary image, it must be `logical`. The output `gpuArray` image is `single`.

Examples

Convert Array to Class Single

This example shows how to convert an array of class `uint8` into class `single` .

Create a numeric array of class `uint8` .

```
I = reshape(uint8(linspace(1,255,25)),[5 5])
```

I =

```
    1    54    107    160    213
   12    65    117    170    223
   22    75    128    181    234
   33    86    139    192    244
   43    96    149    202    255
```

Convert the array to class `single` .

```
I2 = im2single(I)
```

I2 =

```
    0.0039    0.2118    0.4196    0.6275    0.8353
    0.0471    0.2549    0.4588    0.6667    0.8745
    0.0863    0.2941    0.5020    0.7098    0.9176
    0.1294    0.3373    0.5451    0.7529    0.9569
    0.1686    0.3765    0.5843    0.7922    1.0000
```

Convert Array to Class Single on GPU

Create an array of class `uint8` on the GPU by creating a `gpuArray` object.

```
I = gpuArray(reshape(uint8(linspace(1,255,25)),[5 5]))
```

```
I =
```

```
    1    54   107   160   213
   12    65   117   170   223
   22    75   128   181   234
   33    86   139   192   244
   43    96   149   202   255
```

Convert the array from class `uint8` to class `single` on the GPU. You can pass `im2single` a `gpuArray` object.

```
I2 = im2single(I)
```

```
I2 =
```

```
    0.0039    0.2118    0.4196    0.6275    0.8353
    0.0471    0.2549    0.4588    0.6667    0.8745
    0.0863    0.2941    0.5020    0.7098    0.9176
    0.1294    0.3373    0.5451    0.7529    0.9569
    0.1686    0.3765    0.5843    0.7922    1.0000
```

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`im2double` | `im2int16` | `im2uint8` | `im2uint16` | `single` | `gpuArray`

Introduced before R2006a

im2uint16

Convert image to 16-bit unsigned integers

Syntax

```
I2 = im2uint16(I)
RGB2 = im2uint16(RGB)
I = im2uint16(BW)
X2 = im2uint16(X,'indexed')
gpuarrayB = im2uint16(gpuarrayA, ___ )
```

Description

`I2 = im2uint16(I)` converts the intensity image `I` to `uint16`, rescaling the data if necessary. If the input image is of class `uint16`, the output image is identical to it.

`RGB2 = im2uint16(RGB)` converts the truecolor image `RGB` to `uint16`, rescaling the data if necessary.

`I = im2uint16(BW)` converts the binary image `BW` to a `uint16` intensity image, changing 1-valued elements to 65535.

`X2 = im2uint16(X,'indexed')` converts the indexed image `X` to `uint16`, offsetting the data if necessary. If `X` is of class `double`, `max(X(:))` must be 65536 or less.

`gpuarrayB = im2uint16(gpuarrayA, ___)` performs the conversion on a GPU. The input image and the output image are `gpuArrays`. This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-504 support: Yes

“MATLAB Function Block” on page 1-504 support: Yes

Class Support

Intensity and truecolor images can be `uint8`, `uint16`, `double`, `logical`, `single`, or `int16`. Indexed images can be `uint8`, `uint16`, `double`, or `logical`. Binary input images must be `logical`. The output image is `uint16`.

If the input `gpuArray` `gpuarrayA` is an intensity or truecolor image, it can be `uint8`, `uint16`, `int16`, `logical`, `single`, or `double`. If `gpuarrayA` is an indexed image, it can be `uint8`, `uint16`, `double` or `logical`. If `gpuarrayA` is a binary image, it must be `logical`. The output `gpuArray` image is `uint16`.

Examples

Convert array to `uint16`.

```
I1 = reshape(linspace(0,1,20),[5 4])
I2 = im2uint16(I1)
```

I1 =

	0	0.2632	0.5263	0.7895
	0.0526	0.3158	0.5789	0.8421
	0.1053	0.3684	0.6316	0.8947
	0.1579	0.4211	0.6842	0.9474
	0.2105	0.4737	0.7368	1.0000

I2 =

	0	17246	34492	51738
	3449	20695	37941	55187
	6898	24144	41391	58637
	10348	27594	44840	62086
	13797	31043	48289	65535

Convert array to `uint16` on a GPU.

```
I1 = gpuArray(reshape(linspace(0,1,20),[5 4]))
I2 = im2uint16(I1)
```

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`im2uint8` | `uint8` | `uint16` | `double` | `im2double` | `imapprox` | `gpuArray`

Introduced before R2006a

im2uint8

Convert image to 8-bit unsigned integers

Syntax

```
I2 = im2uint8(I)
RGB2 = im2uint8(RGB)
I = im2uint8(BW)
X2 = im2uint8(X,'indexed')
gpuarrayB = im2uint8(gpuarrayA, ___ )
```

Description

`I2 = im2uint8(I)` converts the grayscale image `I` to `uint8`. If the input image is of class `uint8`, the output image is identical to the input image. If the input image is not `uint8`, `im2uint8` returns the equivalent image of class `uint8`, rescaling or offsetting the data as necessary.

`RGB2 = im2uint8(RGB)` converts the truecolor image `RGB` to `uint8`, rescaling the data if necessary.

`I = im2uint8(BW)` converts the binary image `BW` to a `uint8` grayscale image, changing 1-valued elements to 255.

`X2 = im2uint8(X,'indexed')` converts the indexed image `X` to `uint8`, offsetting the data if necessary. Note that it is not always possible to convert an indexed image to `uint8`. If `X` is of class `double`, the maximum value of `X` must be 256 or less. If `X` is of class `uint16`, the maximum value of `X` must be 255 or less.

`gpuarrayB = im2uint8(gpuarrayA, ___)` performs the conversion on a GPU. The input image, `gpuarrayA`, can be a grayscale, truecolor, binary, or indexed `gpuArray` image. The output image is a `gpuArray`. This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-508 support: Yes.

“MATLAB Function Block” on page 1-508 support: Yes.

Examples

Convert uint16 Array to uint8 Array

Create an array of class `uint16`.

```
I = reshape(uint16(linspace(0,65535,25)),[5 5])
```

I =

```
     0  13653  27306  40959  54613
    2731  16384  30037  43690  57343
    5461  19114  32768  46421  60074
    8192  21845  35498  49151  62804
   10923  24576  38229  51882  65535
```

Convert the array to class `uint8`.

```
I2 = im2uint8(I)
```

I2 =

```
     0   53  106  159  213
    11   64  117  170  223
    21   74  128  181  234
    32   85  138  191  244
    43   96  149  202  255
```

Convert uint16 Array to uint8 on a GPU

Create array of class `uint16`.

```
I1 = gpuArray(reshape(uint16(linspace(0,65535,25)),[5 5]))
```

Convert array to `uint8`.


```
I2 = im2uint8(I1);
```

Input Arguments

I — Input grayscale image

real, nonsparse, numeric array

Input grayscale image, specified as a real, nonsparse, numeric array.

Example: `I = imread('cameraman.tif');`

Data Types: `single` | `double` | `int16` | `uint8`

RGB — Input truecolor image

real, nonsparse, numeric array

Truecolor image, specified as a real, nonsparse, numeric array.

Example: `RGB = imread('peppers.png');`

Data Types: `single` | `double` | `int16` | `uint8`

BW — Binary image

real, nonsparse, logical array

Binary image, specified as a real, nonsparse, logical array.

Example: `BW = imread('text.png');`

Data Types: `logical`

X — Indexed image

real, nonsparse, numeric array

Indexed image, specified as a real, nonsparse, numeric array.

Example: `[X,map] = imread('trees.tif');`

Data Types: `double` | `uint8` | `uint16`

gpuarrayA — Input image

`gpuArray`

Input image, specified as a `gpuArray`.

```
Example: I = gpuArray(imread('cameraman.tif'));
```

Output Arguments

I2 — Grayscale image

`uint8` array

Grayscale image, returned as a `uint8` array.

RGB2 — Truecolor image

numeric array

Truecolor image, returned as a `uint8` array.

X2 — Output indexed image

numeric array

Output indexed image, returned as a `uint8` numeric array.

gpuarrayB — Output image

`gpuArray`

Output image, returned as a `gpuArray`.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic `MATLAB Host Computer` target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

[gpuArray](#) | [im2double](#) | [im2int16](#) | [im2single](#) | [im2uint16](#) | [uint8](#)

Introduced before R2006a

imabsdiff

Absolute difference of two images

Syntax

```
Z = imabsdiff(X,Y)
gpuarrayZ = imabsdiff(gpuarrayX,gpuarrayY)
```

Description

`Z = imabsdiff(X,Y)` subtracts each element in array `Y` from the corresponding element in array `X` and returns the absolute difference in the corresponding element of the output array `Z`.

`gpuarrayZ = imabsdiff(gpuarrayX,gpuarrayY)` performs the computation on a GPU, if at least one of the inputs is a `gpuArray`. The output image is a `gpuArray`. This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-513 support: Yes.

“MATLAB Function Block” on page 1-513 support: Yes.

Examples

Display Absolute Difference between Filtered image and Original

Read image into workspace.

```
I = imread('cameraman.tif');
```

Filter the image.

```
J = uint8(filter2(fspecial('gaussian'), I));
```

Calculate the absolute difference of the two images.

```
K = imabsdiff(I,J);
```

Display the absolute difference image.

```
figure  
imshow(K, [])
```



Display Absolute Difference Between Filtered Image and Original on GPU

Read image and convert it to a GPUArray.

```
I = gpuArray(imread('cameraman.tif'));
```

Filter the image, performing the operation on a GPU.

```
J = imfilter(I, fspecial('gaussian'));
```

Calculate the absolute difference between the filtered image and original image.

```
K = imabsdiff(I, J);
```

Display the absolute difference image.

```
figure  
imshow(K, [])
```

Input Arguments

X — Input image

real, nonsparse numeric array

Input image, specified as a real, nonsparse numeric array. *X* must be the same size and class as *Y*.

If *X* is of class `double`, use the expression `abs(X-Y)` instead of this function. If *X* is of class `logical`, use the expression `XOR(X,Y)` instead of this function.

Example: `Z = imabsdiff(X,Y);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32` | `logical`

Y — Input image

real, nonsparse numeric array

Input image, specified as a real, nonsparse numeric array. *Y* must be the same size and class as *X*.

If *Y* is of class `double`, use the expression `abs(X-Y)` instead of this function. If *Y* is of class `logical`, use the expression `XOR(X,Y)` instead of this function.

Example: `Z = imabsdiff(X,Y);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32` | `logical`

gpuarrayX — Input image

GPUarray

Input image, specified as a GPUarray.

Example: `gpuarrayZ = imabsdiff(gpuarrayX,gpuarrayY);`

gpuarrayY — Input image

GPUarray

Input image, specified as a GPUArray.

Example: `gpuarrayZ = imabsdiff(gpuarrayX,gpuarrayY);`

Output Arguments

Z — Difference image

real, nonsparse, numeric array

Difference image, returned as a real, nonsparse, numeric array. Z has the same class and size as X and Y. If X and Y are integer arrays, `imabsdiff` truncates elements in the output that exceed the range of the integer type.

gpuarrayZ — Difference image

gpuArray

Difference image, returned as a `gpuArray`. `gpuarrayZ` has the same class and size as `gpuarrayX` and `gpuarrayY`.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

Tips

- When X and Y are of class `uint8`, `int16`, or `single`, `imabsdiff` might take advantage of hardware optimization to run faster.

See Also

`gpuArray` | `imadd` | `imcomplement` | `imdivide` | `imlincomb` | `immultiply` | `imsubtract`

Introduced before R2006a

imadd

Add two images or add constant to image

Syntax

```
Z = imadd(X,Y)
```

Description

`Z = imadd(X,Y)` adds each element in array `X` with the corresponding element in array `Y` and returns the sum in the corresponding element of the output array `Z`. `X` and `Y` are real, nonsparse numeric arrays with the same size and class, or `Y` is a scalar double. `Z` has the same size and class as `X`, unless `X` is logical, in which case `Z` is double.

If `X` and `Y` are integer arrays, elements in the output that exceed the range of the integer type are truncated, and fractional values are rounded.

Examples

Add two `uint8` arrays. Note the truncation that occurs when the values exceed 255.

```
X = uint8([ 255 0 75; 44 225 100]);  
Y = uint8([ 50 50 50; 50 50 50 ]);  
Z = imadd(X,Y)  
Z =
```

```
    255     50    125  
     94    255    150
```

Add two images together and specify an output class.

```
I = imread('rice.png');  
J = imread('cameraman.tif');  
K = imadd(I,J,'uint16');  
imshow(K,[])
```

Add a constant to an image.

```
I = imread('rice.png');  
J = imadd(I,50);  
subplot(1,2,1), imshow(I)  
subplot(1,2,2), imshow(J)
```

See Also

[imabsdiff](#) | [imcomplement](#) | [imdivide](#) | [imlincomb](#) | [immultiply](#) | [imsubtract](#)

Introduced before R2006a

imadjust

Adjust image intensity values or colormap

Syntax

```
J = imadjust(I)
J = imadjust(I,[low_in; high_in],[low_out; high_out])
J = imadjust(I,[low_in; high_in],[low_out; high_out],gamma)
newmap = imadjust(map,[low_in; high_in],[low_out; high_out],gamma)
RGB2 = imadjust(RGB1, ___ )
gpuarrayB = imadjust(gpuarrayA, ___ )
```

Description

`J = imadjust(I)` maps the intensity values in grayscale image `I` to new values in `J` such that 1% of data is saturated at low and high intensities of `I`. This increases the contrast of the output image `J`. This syntax is equivalent to `imadjust(I,stretchlim(I))`.

`J = imadjust(I,[low_in; high_in],[low_out; high_out])` maps the values in `I` to new values in `J` such that values between `low_in` and `high_in` map to values between `low_out` and `high_out`.

Note If `high_out` is less than `low_out`, `imadjust` reverses the output image, as in a photographic negative.

`J = imadjust(I,[low_in; high_in],[low_out; high_out],gamma)` maps the values in `I` to new values in `J`, where `gamma` specifies the shape of the curve describing the relationship between the values in `I` and `J`.

`newmap = imadjust(map,[low_in; high_in],[low_out; high_out],gamma)` transforms the m -by-3 array colormap associated with an indexed image. `low_in`, `high_in`, `low_out`, and `high_out` must be 1-by-3 vectors. `gamma` can be a 1-by-3 vector that specifies a unique gamma value for each channel or a scalar that specifies the value used for all three channels. The rescaled colormap `newmap` is the same size as `map`.

`RGB2 = imadjust(RGB1, ___)` performs the adjustment on each plane (red, green, and blue) of the RGB image `RGB1`. If `low_in`, `high_in`, `low_out`, `high_out`, and `gamma` are scalars, `imadjust` applies the same mapping to the red, green, and blue components of the image. To specify unique mappings for each color component of the image, specify `low_in`, `high_in`, `low_out`, `high_out`, and `gamma` as 1-by-3 vectors.

`gpuarrayB = imadjust(gpuarrayA, ___)` performs the contrast adjustment on a GPU. The input GPUArray `gpuarrayA` is an intensity image, RGB image, or a colormap. The output GPUArray `gpuarrayB` is the same as the input image. This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-527 support: Yes.

“MATLAB Function Block” on page 1-527 support: Yes.

Examples

Adjust Contrast of Grayscale Image

Read a low-contrast grayscale image into the workspace and display it.

```
I = imread('pout.tif');  
imshow(I);
```



Adjust the contrast of the image so that 1% of the data is saturated at low and high intensities, and display it.

```
J = imadjust(I);  
figure  
imshow(J)
```



Adjust Contrast of Grayscale Image on GPU

Read an image into a `gpuArray` and then pass the `gpuArray` to `imadjust`.

```
I = gpuArray(imread('pout.tif'));  
figure  
imshow(I)
```

```
J = imadjust(I);  
figure  
imshow(J)
```

Adjust Contrast of Grayscale Image Specifying Contrast Limits

Read a low-contrast grayscale image into the workspace and display it.

```
I = imread('pout.tif');
```

```
imshow(I);
```



Adjust the contrast of the image, specifying contrast limits.

```
K = imadjust(I,[0.3 0.7],[1]);  
figure  
imshow(K)
```



Adjust Contrast of Grayscale Image Specifying Contrast Limits on GPU

Read an image into a `gpuArray` and then pass the `gpuArray` to `imadjust`.

```
I = gpuArray(imread('pout.tif'));  
figure  
imshow(I)
```

```
K = imadjust(I,[0.3 0.7],[1]);  
figure  
imshow(K)
```

Adjust Contrast of RGB Image

Read an RGB image into the workspace and display it.

```
RGB = imread('football.jpg');
```



```
imshow(RGB)
```



Adjust the contrast of the RGB image, specifying contrast limits.

```
RGB2 = imadjust(RGB,[.2 .3 0; .6 .7 1],[,]);  
figure  
imshow(RGB2)
```



Adjust Contrast of RGB Image on GPU

Read an RGB image into a `gpuArray` and then pass the `gpuArray` to `imadjust`, specifying contrast limits for the input image.

```
RGB = gpuArray(imread('football.jpg'));  
RGB2 = imadjust(RGB,[.2 .3 0; .6 .7 1],[1]);  
figure  
imshow(RGB)  
figure  
imshow(RGB2)
```

Input Arguments

I — Image to be adjusted

grayscale image

Image to be adjusted, specified as a grayscale image.

Example:

Data Types: `single` | `double` | `int16` | `uint8` | `uint16` | `uint32`

[low_in; high_in] — Contrast limits for the input image

`[0 1]` (default) | two-element numeric vector with values between 0 and 1 | 1-by-3 element vector

Contrast limits for input image, specified as a two-element numeric vector with values between 0 and 1. Values below `low_in` and above `high_in` are clipped; that is, values below `low_in` map to `low_out`, and those above `high_in` map to `high_out`. If you specify an empty matrix (`[]`), `imadjust` uses the default limits `[0 1]`.

If the input image is a colormap, must be 1-by-3 vectors.

Example: `K = imadjust(I,[0.3 0.7],[]);`

Data Types: `single` | `double`

[low_out; high_out] — Contrast limits for the output image

`[0 1]` (default) | two-element numeric vector with values between 0 and 1

Contrast limits for the output image, specified as a two-element numeric vector with values between 0 and 1. Values below `low_in` and above `high_in` are clipped; that is, values below `low_in` map to `low_out`, and those above `high_in` map to `high_out`. If you specify an empty matrix (`[]`), `imadjust` uses the default limits `[0 1]`.

Example: `K = imadjust(I,[0.3 0.7],[0.3 0.7]);`

Data Types: `single` | `double`

gamma — Shape of the curve describing relationship of input and output values

1 (default) | numeric value of class `double`

Shape of curve describing relationship of input and output values, specified as a numeric value. If `gamma` is less than 1, `imadjust` weights the mapping toward higher (brighter) output values. If `gamma` is greater than 1, `imadjust` weights the mapping toward lower (darker) output values. If you omit the argument, `gamma` defaults to 1 (linear mapping).

Example:

Data Types: `double`

map — Colormap to be adjusted

m-by-3 array

Colormap to be adjusted, specified as an m -by-3 array.

Example:

Data Types: `single` | `double` | `int16` | `uint8` | `uint16` | `uint32`

RGB1 — Color image to be adjusted

RGB image

Color image to be adjusted, specified as an RGB image.

Example:

Data Types: `single` | `double` | `int16` | `uint8` | `uint16` | `uint32`

gpuarrayA — Image to be adjusted on a GPU

`gpuArray`

Image to be adjusted on a GPU, specified as an `gpuArray` containing a grayscale image, an RGB image, or a colormap.

Example: `I = gpuArray(imread('pout.tif'));`

Data Types: `single` | `double` | `int16` | `uint8` | `uint16` | `uint32`

Output Arguments

J — Adjusted image

grayscale image

Adjusted image, returned as a grayscale image. `J` has the same class as the input image.

Data Types: `single` | `double` | `int16` | `uint8` | `uint16` | `uint32`

newmap — Adjusted colormap

m -by-3 array

Adjusted colormap, returned as an m -by-3 array, of the same class as the input colormap.

Data Types: `single` | `double`

RGB2 — Adjusted color image

RGB image

Adjusted color image, returned as an RGB image. RGB2 has the same class as the input image.

Data Types: `single` | `double` | `int16` | `uint8` | `uint16` | `uint32`

gpuarrayB — Adjusted image or colormap on a GPU

`gpuArray`

Adjusted image or colormap on a GPU, returned as a `gpuArray`. The `gpuArray` contains a grayscale or an RGB image, or a colormap.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic MATLAB Host Computer target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, `imadjust` does not support indexed images.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`brighten` | `gpuArray` | `histeq` | `stretchlim`

Introduced before R2006a

ImageAdapter class

Interface for image I/O

Description

`ImageAdapter`, an abstract class, specifies the Image Processing Toolbox interface for region-based reading and writing of image files. You can use classes that inherit from the `ImageAdapter` interface with the `blockproc` function for file-based processing of arbitrary image file formats.

Construction

`adapter = ClassName(...)` handles object initialization, manages file opening or creation, and sets the initial values of class properties. The class constructor can take any number of arguments.

Properties

Colormap

Specifies a colormap. Use the `Colormap` property when working with indexed images.

Data Type: 2-D, real, M-by-3 matrix

Default: Empty (`[]`), indicating either a grayscale, logical, or truecolor image

ImageSize

Holds the size of the entire image. When you construct a new class that inherits from `ImageAdapter`, set the `ImageSize` property in your class constructor.

Data Type: 2- or 3-element vector specified as `[rows cols]` or `[rows cols bands]`, where `rows` indicates height and `cols` indicates width

Methods

Classes that inherit from `ImageAdapter` must implement the `readRegion` and `close` methods to support basic region-based reading of images. The `writeRegion` method allows for incremental, region-based writing of images and is optional. Image Adapter classes that do not implement the `writeRegion` method are read-only.

<code>close</code>	Close <code>ImageAdapter</code> object
<code>readRegion</code>	Read region of image
<code>writeRegion</code>	Write block of data to region of image

See Also

`blockproc`

Tutorials

- [Computing Statistics for Large Images](#)

How To

- [“Abstract Classes”](#)
- [“Read and Write Data in Unsupported Formats Using `blockproc`”](#)

close

Class: ImageAdapter

Close ImageAdapter object

Syntax

```
adapter.close
```

Description

`adapter.close` closes the `ImageAdapter` object and performs any necessary clean-up, such as closing file handles. When you construct a class that inherits from the `ImageAdapter` class, implement this method.

readRegion

Class: ImageAdapter

Read region of image

Syntax

```
data = adapter.readRegion(region_start, region_size)
```

Description

`data = adapter.readRegion(region_start, region_size)` reads a region of the image. `region_start` and `region_size` define a rectangular region in the image. `region_start`, a two-element vector, specifies the [row col] of the first pixel (minimum-row, minimum-column) of the region. `region_size`, a two-element vector, specifies the size of the requested region in [rows cols]. When you construct a class that inherits from the `ImageAdapter` class, implement this method.

writeRegion

Class: ImageAdapter

Write block of data to region of image

Syntax

```
adapter.writeRegion(region_start, region_data)
```

Description

`adapter.writeRegion(region_start, region_data)` writes a contiguous block of data to a region of the image. The method writes the block of data specified by the `region_data` argument. The two-element vector, `region_start`, specifies the [row col] location of the first pixel (minimum-row, minimum-column) of the target region in the image. When you construct a class that inherits from the `ImageAdapter` class, implement this method if you need to write data.

imageinfo

Image Information tool

Syntax

```
imageinfo
imageinfo(h)
imageinfo(filename)
imageinfo(info)
imageinfo(himage, filename)
imageinfo(himage, info)
hfig = imageinfo(...)
```

Description

`imageinfo` creates an Image Information tool associated with the image in the current figure. The tool displays information about the basic attributes of the target image in a separate figure. `imageinfo` gets information about image attributes by querying the image object's `CData`.

The following table lists the basic image information included in the Image Information tool display. Note that the tool contains either four or six fields, depending on the type of image.

Attribute Name	Value
Width (columns)	Number of columns in the image
Height (rows)	Number of rows in the image
Class	Data type used by the image, such as <code>uint8</code> .
	Note: For <code>single</code> or <code>int16</code> images, <code>imageinfo</code> returns a class value of <code>double</code> , because image objects convert the <code>CData</code> of these images to <code>double</code> .

Attribute Name	Value
Image type	One of the image types identified by the Image Processing Toolbox software: 'intensity' 'truecolor', 'binary', or 'indexed'.
Minimum intensity or index	For grayscale images, this value represents the lowest intensity value of any pixel. For indexed images, this value represents the lowest index value into a color map. Not included for 'binary' or 'truecolor' images.
Maximum intensity or index	For grayscale images, this value represents the highest intensity value of any pixel. For indexed images, this value represents the highest index value into a color map. Not included for 'binary' or 'truecolor' images.

`imageinfo(h)` creates an Image Information tool associated with `h`, where `h` is a handle to a figure, axes, or image object.

`imageinfo(filename)` creates an Image Information tool containing image metadata from the graphics file `filename`. The image does not have to be displayed in a figure window. `filename` can be any file type that has been registered with an information function in the file formats registry, `imformats`, so its information can be read by `imfinfo`. `filename` can also be a DICOM, NITF, Interfile, or Analyze file.

`imageinfo(info)` creates an Image Information tool containing the image metadata in the structure `info`. `info` is a structure returned by the functions `imfinfo`, `dicominfo`, `nitfinfo` `interfileinfo`, or `analyze75info`. `info` can also be a user-created structure.

`imageinfo(himage, filename)` creates an Image Information tool containing information about the basic attributes of the image specified by the handle `himage` and the image metadata from the graphics file `filename`.

`imageinfo(himage, info)` creates an Image Information tool containing information about the basic attributes of the image specified by the handle `himage` and the image metadata in the structure `info`.

`hfig = imageinfo(...)` returns a handle to the Image Information tool figure.

Examples

```
imageinfo('peppers.png')  
  
h = imshow('bag.png');  
info = imfinfo('bag.png');  
imageinfo(h,info);  
  
imshow('canoe.tif');  
imageinfo;
```

See Also

[analyze75info](#) | [dicominfo](#) | [imattributes](#) | [imfinfo](#) | [imformats](#) | [imtool](#) | [interfileinfo](#) | [nitfinfo](#)

Introduced before R2006a

imagemodel

Image Model object

Syntax

```
imgmodel = imagemodel(himage)
```

Description

`imgmodel = imagemodel(himage)` creates an image model object associated with a target image. The target image `himage` is a handle to an image object or an array of handles to image objects. `imagemodel` returns an image model object or, if `himage` is an array of image objects, an array of image model objects. `imagemodel` works by querying the image object's `CData`.

API Functions

An image model object stores information about an image such as class, type, display range, width, height, minimum intensity value, and maximum intensity value.

The image model object supports methods that you can use to access this information, get information about the pixels in an image, and perform special text formatting. Brief descriptions of these methods follow.

Methods

`imagemodel` supports the following methods. Type `methods imagemodel` to see a list of methods, or type `help imagemodel/methodname` for more information about a specific method.

getClassType — Return class of image

`imageclass = getClassType(imgmodel)` returns the class associated with the `imagemodel`, `imgmodel`. The return value, `imageclass` is a string, such as `'uint8'`,

specifying the class of the image object's CData. `imagemodel` is expected to contain only one `imagemodel` object.

getDisplayRange — Return display range of intensity image

`disp_range = getDisplayRange(imgmodel)`, where `imgmodel` is a valid image model and `disp_range` is an array of doubles such as `[0 255]`, returns a double array containing the minimum and maximum values of the display range for an intensity image. For image types other than intensity, the value returned is an empty array.

getImageHeight — Return number of rows

`height = getImageHeight(imgmodel)`, where `imgmodel` is a valid image model and `height` is a double scalar, returns a double scalar containing the number of rows.

getImageType — Return image type

`str = getImageType(imgmodel)`, where `imgmodel` is a valid image model and `str` is one of the text strings ('intensity', 'truecolor', 'binary', or 'indexed'), returns a text string indicating the image type.

getImageWidth — Return number of columns

`width = getImageWidth(imgmodel)`, where `imgmodel` is a valid image model and `width` is a double scalar, returns a double scalar containing the number of columns.

getMinIntensity — Return minimum value in image

`minval = getMinIntensity(imgmodel)`, where `imgmodel` is a valid image model and `minval` is a numeric value, returns the minimum value in the image calculated as `min(Image(:))`. For an intensity image, the value returned is the minimum intensity. For an indexed image, the value returned is the minimum index. For any other image type, the value returned is an empty array. The class of `minval` depends on the class of the target image.

getMaxIntensity — Return maximum value in image

`maxval = getMaxIntensity(imgmodel)`, where `imgmodel` is a valid image model and `maxval` is a numeric value, returns the maximum value in the image calculated as `max(Image(:))`. For an intensity image, the value returned is the maximum intensity. For an indexed image, the value returned is the maximum index. For any other image

type, the value returned is an empty array. The class of `maxval` depends on the class of the target image.

getNumberFormatFcn — Return handle to function that converts numeric value into string

`fun = getNumberFormatFcn(imgmodel)`, where `imgmodel` is a valid image model, returns the handle to a function that converts a numeric value into a string.

For example, `str = fun(getPixelValue(imgmodel, 100, 100))` converts the numeric return value of the `getPixelValue` method into a text string.

getPixelInfoString — Return value of specific pixel as text string

`str = getPixelInfoString(imgmodel, row, column)`, where `str` is a character array, `imgmodel` is a valid image model, and `row` and `column` are numeric scalar values, returns a text string containing the value of the pixel at the location specified by `row` and `column`. For example, for an RGB image, the method returns a text string such as `'[66 35 60]'`.

getPixelRegionFormatFcn — Return handle to function that formats value of pixel into text string

`fun = getPixelRegionFormatFcn(imgmodel)`, takes a valid image model, `imgmodel`, and returns `fun`, a handle to a function that accepts the location (`row`, `column`) of a pixel in the target image and returns the value of the pixel as a specially formatted text string. For example, when used with an RGB image, this function returns a text string of the form `'R:000 G:000 B:000'` where 000 is the actual pixel value.

```
str = fun(100,100)
```

getPixelValue — Return value of specific pixel as numeric array

`val = getPixelValue(imgmodel, row, column)`, where `imgmodel` is a valid image model and `row` and `column` are numeric scalar values, returns the value of the pixel at the location specified by `row` and `column` as a numeric array. The class of `val` depends on the class of the target image.

getDefaultPixelInfoString — Return pixel information type as text string

`str = getDefaultPixelInfoString(imgmodel)`, where `imgmodel` is a valid image model, returns a text string indicating the pixel information type. This string can be used

in place of actual pixel information values. Depending on the image type, `str` can be the text string 'Intensity', '[R G B]', 'BW', or '<Index> [R G B]'.

getDefaultPixelRegionString — Return type of information displayed in Pixel Region tool

`str = getDefaultPixelRegionString(imgmodel)`, where `imgmodel` is a valid image model, returns a text string indicating the type of information displayed in the Pixel Region tool for each image type. This string can be used in place of actual pixel values. Depending on the image type, `str` can be the text string '000', 'R:000 G:000 B:000]', '0', or '<000> R:0.00 G:0.00 B:0.00'.

getScreenPixelRGBValue — Return screen display value of specific pixel

`val = getScreenPixelRGBValue(imgmodel, row, col)` returns the screen display value of the pixel at the location specified by `row` and `col` as a double array. `imgmodel` is a valid image model, `row` and `col` are numeric scalar values, and `val` is an array of doubles, such as [0.2 0.5 0.3].

Examples

Create an image model.

```
h = imshow('peppers.png');
im = imagemodel(h);

figure, subplot(1,2,1)
h1 = imshow('hestain.png');
subplot(1,2,2)
h2 = imshow('coins.png');
im = imagemodel([h1 h2]);
```

See Also

`getimagemodel`

Introduced before R2006a

imapplymatrix

Linear combination of color channels

Syntax

```
Y = imapplymatrix(M,X)
Y = imapplymatrix(M,X,C)
Y = imapplymatrix(..., output_type)
```

Description

`Y = imapplymatrix(M,X)` computes the linear combination of the rows of `M` with the color channels of `X`. The output data type is the same as the type of `X`.

`Y = imapplymatrix(M,X,C)` computes the linear combination of the rows of `M` with the color channels of `X`, adding the corresponding constant value from `C` to each combination. The output data type is the same as the type of `X`.

`Y = imapplymatrix(..., output_type)` returns the result of the linear combination in an array of type `output_type`.

Input Arguments

M

Matrix that contains the coefficients of the weighting matrix. If `X` is *m-by-n-by-p*, `M` must be *q-by-p*, where `q` is in the range `[1,p]`.

X

An image.

C

A vector with the same number of elements as the number of rows in `M`, or a scalar applied to every channel.

output_type

A string that describes the output type. Possible values include `uint8`, `int8`, `uint16`, `int16`, `uint32`, `int32`, `single`, or `double`.

Output Arguments

Y

Array that contains the linear combination of the rows of `M` with the color channels of `X`.

Examples


Convert RGB values to grayscale:

```
RGB = imread('peppers.png');  
M = [0.30, 0.59, 0.11];  
gray = imapplymatrix(M, RGB);  
figure  
subplot(1,2,1), imshow(RGB), title('Original RGB')  
subplot(1,2,2), imshow(gray), title('Grayscale Conversion')
```

Original RGB



Grayscale Conversion



See Also

`imlincomb` | `immultiply`

Introduced in R2011b

imattributes

Information about image attributes

Syntax

```
attrs = imattributes
attrs = imattributes(himage)
attrs = imattributes(imgmodel)
```

Description

`attrs = imattributes` returns information about an image in the current figure. If the current figure does not contain an image, `imattributes` returns an empty array.

`attrs = imattributes(himage)` returns information about the image specified by `himage`, a handle to an image object. `imattributes` gets the image attributes by querying the image object's `CData`.

`imattributes` returns image attribute information in `attrs`, a 4-by-2 or 6-by-2 cell array, depending on the image type. The first column of the cell array contains the name of the attribute as a text string. The second column contains the value of the attribute, also represented as a text string. The following table lists these attributes in the order they appear in the cell array.

Attribute Name	Value
Width (columns)	Number of columns in the image
Height (rows)	Number of rows in the image
Class	Data type used by the image, such as <code>uint8</code> . Note: For <code>single</code> or <code>int16</code> images, <code>imageinfo</code> returns a class value of <code>double</code> , because image objects convert <code>CData</code> of these classes to <code>double</code> .
Image type	One of the image types identified by the Image Processing Toolbox software: <code>'intensity'</code> , <code>'truecolor'</code> , <code>'binary'</code> , or <code>'indexed'</code> .

Attribute Name	Value
Minimum intensity	<p>For intensity images, this value represents the lowest intensity value of any pixel.</p> <p>For indexed images, this value represents the lowest index value into a color map.</p> <p>Not included for 'binary' or 'truecolor' images.</p>
Maximum intensity	<p>For intensity images, this value represents the highest intensity value of any pixel.</p> <p>For indexed images, this value represents the highest index value into a color map.</p> <p>Not included for 'binary' or 'truecolor' images.</p>

`attrs = imattributes(imgmodel)` returns information about the image represented by the image model object, `imgmodel`.

Examples

Retrieve the attributes of a grayscale image.

```
h = imshow('liftingbody.png');
attrs = imattributes(h)
attrs =

    'Width (columns)'      '512'
    'Height (rows)'       '512'
    'Class'                'uint8'
    'Image type'          'intensity'
    'Minimum intensity'    '0'
    'Maximum intensity'    '255'
```

Retrieve the attributes of a truecolor image.

```
h = imshow('gantrycrane.png');
im = imagemodel(h);
attrs = imattributes(im)
attrs =
```

'Width (columns)'	'400'
'Height (rows)'	'264'
'Class'	'uint8'
'Image type'	'truecolor'

See Also

imagemodel

Introduced before R2006a

imbinarize

Binarize image by thresholding

Syntax

```
BW = imbinarize(I)
BW = imbinarize(I,method)
BW = imbinarize(I,T)
BW = imbinarize(I,'adaptive',Name,Value)
```

Description

`BW = imbinarize(I)` creates a binary image from image `I` by replacing all values above a globally determined threshold with 1s and setting all other values to 0s. By default, `imbinarize` uses Otsu's method, which chooses the threshold value to minimize the intraclass variance of the thresholded black and white pixels. `imbinarize` uses a 256-bin image histogram to compute Otsu's threshold. To use a different histogram, see `otsuthresh`. `BW` is the output binary image.

`BW = imbinarize(I,method)` creates a binary image from image `I` using the thresholding method specified by `method`.

`BW = imbinarize(I,T)` creates a binary image from image `I` using the threshold value `T`.

`BW = imbinarize(I,'adaptive',Name,Value)` creates a binary image from image `I` using name-value pairs to control aspects of adaptive thresholding.

“Code Generation” on page 1-552 support: Yes.

“MATLAB Function Block” on page 1-552 support: Yes.

Examples

Binarize Image Using Global Threshold

Read grayscale image into the workspace.



```
I = imread('coins.png');
```

Convert the image into a binary image.

```
BW = imbinarize(I);
```

Display the original image next to the binary version.

```
figure  
imshowpair(I,BW,'montage')
```



Binarize Image Using Locally Adaptive Thresholding

Read grayscale image into workspace.


```
I = imread('rice.png');
```

Convert grayscale image to binary image.

```
BW = imbinarize(I, 'adaptive');
```

Display original image along side binary version.

```
figure  
imshowpair(I,BW,'montage')
```




Binarize Images with Darker Foreground Than Background.

Read a grayscale image into the workspace and display it.

```
I = imread('printedtext.png');  
figure  
imshow(I)  
title('Original Image')
```

Original Image



Convert the image to a binary image using adaptive thresholding. Use the `ForegroundPolarity` parameter to indicate that the foreground is darker than the background.

```
BW = imbinarize(I, 'adaptive', 'ForegroundPolarity', 'dark', 'Sensitivity', 0.4);
```

Display the binary version of the image.

```
figure
imshow(BW)
title('Binary Version of Image')
```

Binary Version of Image

What Is Image Filtering in the Spatial Domain?

Filtering is a technique for modifying or enhancing an image. For example, you can filter an image to emphasize certain features or remove other features. Image processing operations implemented with filtering include smoothing, sharpening, and edge enhancement.

Filtering is a *neighborhood operation*, in which the value of any given pixel in the output image is determined by applying some algorithm to the values of the pixels in the neighborhood of the corresponding input pixel. A pixel's neighborhood is some set of pixels, defined by their locations relative to that pixel. (See *Neighborhood* or *Block Processing: An Overview for a general discussion of neighborhood operations*.) *Linear filtering* is filtering in which the value of an output pixel is a linear combination of the values of the pixels in the input pixel's neighborhood.

Convolution

Linear filtering of an image is accomplished through an operation called *convolution*. Convolution is a neighborhood operation in which each output pixel is the weighted sum of neighboring input pixels. The matrix of weights is called the *convolution kernel*, also known as the *filter*. A convolution kernel is a correlation kernel that has been rotated 180 degrees.

For example, suppose the image is

```
A = [17 24  1  8 15
      23  5  7 14 16
        4  6 13 20 22
       10 12 19 21  3
       11 10  7  5  3]
```

Input Arguments

I — Input image

real, nonsparse, 2-D matrix

Input image, specified as a real, nonsparse, 2-D matrix.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32` | `uint64`

method — Method used to binarize image

'global' (default) | 'adaptive'

Method used to binarize image, specified as one of the strings in the following table (names can be abbreviated).

String	Meaning
'global'	Calculate global image threshold using Otsu's method. See <code>graythresh</code> for more information about Otsu's method.
'adaptive'	Calculate locally adaptive image threshold chosen using local first-order image statistics around each pixel. See <code>adaptthresh</code> for details. If the image contains <code>Infs</code> or <code>NaNs</code> , the behavior of <code>imbinarize</code> for the 'adaptive' method is undefined. Propagation of <code>Infs</code> or <code>NaNs</code> may not be localized to the neighborhood around <code>Inf</code> and <code>NaN</code> pixels.

Data Types: char

T — Threshold

scalar luminance value or matrix of luminance values

Threshold, specified as a scalar luminance value or as a matrix of luminance values. If `T` is a scalar luminance value, `imbinarize` interprets it as a global image threshold. If `T` is a matrix of luminance values, `imbinarize` interprets it as a locally adaptive threshold. `T` must have a value between 0 and 1. If `T` is a matrix, it must be of the same size as `I`. Use the functions `graythresh`, `otsuthresh`, or `adaptthresh` to compute `T`.

Data Types: single | double | int8 | int16 | int32 | uint8 | uint16 | uint32 | uint64

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

Example: `BW = imbinarize(I, 'adaptive', 'Sensitivity', 0.4);`

'Sensitivity' — Sensitivity factor for adaptive thresholding

0.50 (default) | value in the range [0 1]

Sensitivity factor for adaptive thresholding, specified as a value in the range [0 1]. A high sensitivity value leads to thresholding more pixels as foreground, at the risk of including some background pixels.

Data Types: single | double | int8 | int16 | int32 | int64 | uint8 | uint16 | uint32 | uint64

'ForegroundPolarity' — Determine which pixels are considered foreground pixels
 'bright' (default) | 'dark'

Determine which pixels are considered foreground pixels, specified as either of the following strings:

String	Meaning
'bright'	The foreground is brighter than the background. This is the default.
'dark'	The foreground is darker than the background

Data Types: char

Output Arguments

BW — Output binary image

logical matrix

Output binary image, returned as a logical matrix the same size as I.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, all string input arguments must be compile-time constants.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

Tips

- To produce a binary image from an indexed image, first convert the image to a grayscale intensity image using `ind2gray`.

- To produce a binary image from an RGB image, first convert the image to a grayscale intensity image using `rgb2gray`.

Algorithms

The 'adaptive' method binarizes the image using a locally adaptive threshold. `imbinarize` computes a threshold for each pixel using the local mean intensity around the neighborhood of the pixel. (This technique is also called Bradley's method.) The 'adaptive' method also uses a neighborhood size of approximately 1/8th of the size of the image (computed as $2 * \text{floor}(\text{size}(I) / 16) + 1$). To use a different first order local statistic or a different neighborhood size, see `adaptthresh`.

See Also

`adaptthresh` | `graythresh` | `otsuthresh`

Introduced in R2016a

imbothat

Bottom-hat filtering

Syntax

```
IM2 = imbothat(IM,SE)
IM2 = imbothat(IM,NHOOD)
gpuarrayIM2 = imbothat(gpuarrayIM, ___ )
```

Description

`IM2 = imbothat(IM,SE)` performs morphological bottom-hat filtering on the grayscale or binary input image, `IM`, returning the filtered image, `IM2`. `SE` is a structuring element returned by the `strel` function. `SE` must be a single structuring element object, not an array containing multiple structuring element objects.

`IM2 = imbothat(IM,NHOOD)` performs morphological bottom-hat filtering where `NHOOD` is an array of 0's and 1's that specifies the size and shape of the structuring element. This is equivalent to `imbothat(IM,strel(NHOOD))`.

`gpuarrayIM2 = imbothat(gpuarrayIM, ___)` performs operation on a graphics processing unit (GPU), where `gpuarrayIM` is a `gpuArray` of class `uint8` or `logical`. This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-557 support: Yes.

“MATLAB Function Block” on page 1-557 support: Yes.

Class Support

`IM` can be numeric or logical and must be nonsparse. If the input is binary (logical), then the structuring element must be flat.

`gpuarrayIM` must be a `gpuArray` of type `uint8` or `logical`. When used with a `gpuarray`, the structuring element must be flat and two-dimensional.

The output has the same class as the input.

Examples

Enhance Contrast Using Bottom-hat and Top-hat Filtering

Read image into the workspace and display it.

```
I = imread('pout.tif');  
imshow(I)
```



Create a disk-shaped structuring element.

```
se = strel('disk',3);
```

Add the original image *I* to the top-hat filtered image, and then subtract the bottom-hat filtered image.

```
J = imsubtract(imadd(I,imtophat(I,se)),imbothat(I,se));  
figure  
imshow(J)
```



Enhance Contrast using Bottom Hat Filtering on a GPU

Read the image into a `gpuArray`.

```
original = gpuArray(imread('pout.tif'));
```

Create a disk-shaped structuring element, needed for morphological processing.

```
se = strel('disk',3);
```

Add the original image *I* to the top-hat filtered image, and then subtract the bottom-hat filtered image.

```
contrastFiltered = ...  
    (original+imtophat(original,se))-imbothat(original,se);
```

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, the input image, *IM*, must be 2-D or 3-D and the structuring element argument *SE* must be a single element—arrays of structuring elements are not supported. To obtain the same result as that obtained using an array of structuring elements, call the function sequentially.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

[imtophat](#) | [strel](#) | [offsetstrel](#) | [gpuArray](#)

Introduced before R2006a

imboxfilt

2-D box filtering of images

Syntax

```
B = imboxfilt(A)
B = imboxfilt(A,filterSize)
B = imboxfilt( ____,Name,Value)
```

Description

`B = imboxfilt(A)` filters image `A` with a 2-D, 3-by-3 box filter. A box filter is also called a mean filter.

`B = imboxfilt(A,filterSize)` filters image `A` with a 2-D box filter with size specified by `filterSize`.

`B = imboxfilt(____,Name,Value)` filters image `A` with a 2-D box filter where Name-Value pairs control aspects of the filtering.

“Code Generation” on page 1-562 support: Yes.

“MATLAB Function Block” on page 1-562 support: Yes.

Examples

Compute Mean Filter Over Specified Neighborhood

Read image into the workspace.

```
A = imread('cameraman.tif');
```

Perform the mean filtering using an 11-by-11 filter.

```
localMean = imboxfilt(A,11);
```

Display the original image and the filtered image, side-by-side.

```
imshowpair(A,localMean,'montage')
```



Compute Local Area Sums Over Specified Neighborhood

Read image into the workspace.

```
A = imread('cameraman.tif');
```

Change the data type of the image to `double` to avoid integer overflow.

```
A = double(A);
```

Filter image, calculating local area sums, using a 15-by-15 box filter. To calculate local area sums, rather than the mean, set the `NormalizationFactor` parameter to 1.

```
localSums = imboxfilt(A, 15, 'NormalizationFactor',1);
```

Display the original image and the filtered image, side-by-side.

```
imshowpair(A,localSums,'montage')
```



Input Arguments

A — Image to be filtered

real, nonsparse array of any dimension

Image to be filtered, specified as a real, nonsparse array of any dimension.

If **A** contains `Inf`s or `NaN`s, the behavior of `imboxfilt` is undefined. This can happen when integral image based filtering is used. To restrict the propagation of `Inf`s and `NaN`s in the output, consider using `imfilter` instead.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

filterSize — Size of box filter

3 -by-3 (default) | scalar or 2-element vector of positive, odd integers

Size of box filter, specified as a scalar or 2-element vector of positive, odd integers. If `filterSize` is scalar, the box filter is square.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1,Value1,...,NameN,ValueN`.

```
Example: A = imread('cameraman.tif'); B =
imboxfilt(A,5,'Padding','circular');
```

'Padding' — Padding pattern

'replicate' (default) | 'circular' | 'symmetric' | numeric scalar

Padding pattern, specified as one of the following strings or a numeric scalar. If you specify a scalar value, input image pixels outside the bounds of the image are implicitly assumed to have the scalar value.

String	Description
'circular'	Input image values outside the bounds of the image are computed by implicitly assuming the input image is periodic.
'replicate'	Input image values outside the bounds of the image are assumed equal to the nearest image border value.
'symmetric'	Input image values outside the bounds of the image are computed by mirror-reflecting the array across the array border.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `char`

'NormalizationFactor' — Normalization factor applied to box filter

$1/\text{filterSize}.^2$, if scalar, and $1/\text{prod}(\text{filterSize})$, if vector (default) | numeric scalar

Normalization factor applied to box filter, specified as a numeric scalar.

The default 'NormalizationFactor' has the effect of a mean filter—the pixels in the output image are the local means of the image over the neighborhood determined by `filterSize`. To get local area sums, set 'NormalizationFactor' to 1. To avoid

overflow in such circumstances, consider using double precision images by converting the input image to class `double`.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

Output Arguments

B — Filtered image

real, nonsparse matrix

Filtered image, returned as a real, nonsparse matrix, the same size as the input image.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic `MATLAB Host Computer` target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, all string input arguments must be compile-time constants.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

Algorithms

`imboxfilt` performs filtering using either convolution-based filtering or integral image filtering, using an internal heuristic to determine which filtering approach to use.

See Also

`imboxfilt3` | `imfilter` | `integralBoxFilter`

Introduced in R2015b

imboxfilt3

3-D box filtering of 3-D images

Syntax

```
B = imboxfilt3(A)
B = imboxfilt3(A,filterSize)
B = imboxfilt3( ____,Name,Value)
```

Description

`B = imboxfilt3(A)` filters the 3-D image `A` with a 3-D box filter, 3-by-3-by-3 in size.

`B = imboxfilt3(A,filterSize)` filters 3-D image `A` with a 3-D box filter with size specified by `filterSize`.

`B = imboxfilt3(____,Name,Value)` filters 3-D image `A` where Name-Value pairs control aspects of the filtering.

Examples

Compute Mean Filter in MRI Volume

Load 3-D image data into the workspace.

```
volData = load('mri');
vol = squeeze(volData.D);
```

Filter the image with a 3-D box filter.

```
localMean = imboxfilt3(vol,[5 5 3]);
```

Input Arguments

A — Image to be filtered

real, nonsparse 3-D array

Image to be filtered, specified as a real, nonsparse 3-D array.

If *A* contains `Infs` or `NaNs`, the behavior of `imboxfilt3` is undefined. This can happen when integral image based filtering is used. To restrict the propagation of `Infs` and `NaNs` in the output, consider using `imfilter` instead.

Example: `B = imboxfilt3(A);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

filterSize — Size of box filter

(default) | scalar or 3-element vector of positive, odd integers

Size of box filter, specified as a scalar or 3-element vector of positive, odd integers. If `filterSize` is scalar, the filter is a cube.

Example: `B = imboxfilt3(A,5);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

Example: `B = imboxfilt3(A,5,'padding','circular');`

'Padding' — Padding pattern

'replicate' (default) | 'circular' | 'symmetric' | numeric scalar

Padding pattern, specified as one of the following strings or a numeric scalar. If you specify a scalar value, input image pixels outside the bounds of the image are implicitly assumed to have the scalar value.

String	Description
'circular'	Input image values outside the bounds of the image are computed by implicitly assuming the input image is periodic.
'replicate'	Input image values outside the bounds of the image are assumed equal to the nearest image border value.

String	Description
'symmetric'	Input image values outside the bounds of the image are computed by mirror-reflecting the array across the array border.

Example: `B = imboxfilt3(A,5,'padding','circular');`

Data Types: `single | double | int8 | int16 | int32 | int64 | uint8 | uint16 | uint32 | uint64`

'NormalizationFactor' — Normalization factor applied to box filter

`1/filterSize.^3`, if scalar, and `1/prod(filterSize)`, if vector (default) | numeric scalar

Normalization factor applied to box filter, specified as a numeric scalar.

The default 'NormalizationFactor' has the effect of a mean filter—the pixels in the output image are the local means of the image. To get local area sums, set 'NormalizationFactor' to 1. To avoid overflow in such circumstances, consider using double precision images by converting the input image to class `double`.

Example: `B = imboxfilt3(A,5,'NormalizationFactor',1);`

Data Types: `single | double | int8 | int16 | int32 | int64 | uint8 | uint16 | uint32 | uint64`

Output Arguments

B — Filtered image

real, nonsparse 3-D array

Filtered image, returned as a real, nonsparse 3-D array.

More About

Algorithms

`imboxfilt` performs filtering using either convolution-based filtering or integral image filtering, using an internal heuristic to determine which filtering approach to use.

See Also

`imboxfilt` | `imfilter` | `integralBoxFilter3`

Introduced in R2015b

imclearborder

Suppress light structures connected to image border

Syntax

```
IM2 = imclearborder(IM)
IM2 = imclearborder(IM,conn)
```

Description

`IM2 = imclearborder(IM)` suppresses structures that are lighter than their surroundings and that are connected to the image border. Use this function to clear the image border. `IM` can be a grayscale or binary image. For grayscale images, `imclearborder` tends to reduce the overall intensity level in addition to suppressing border structures. The output image, `IM2`, is grayscale or binary, depending on the input. The default connectivity is 8 for two dimensions, 26 for three dimensions, and `conndef(ndims(BW), 'maximal')` for higher dimensions.

`IM2 = imclearborder(IM,conn)` specifies the desired connectivity.

“Code Generation” on page 1-570 support: Yes.

“MATLAB Function Block” on page 1-570 support: Yes.

Examples

Impact of Connectivity on Clearing the Border

Create a simple binary image.

```
BW = [0    0    0    0    0    0    0    0    0
       0    0    0    0    0    0    0    0    0
       0    0    0    0    0    0    0    0    0
       1    0    0    1    1    1    0    0    0]
```

```

0   1   0   1   1   1   0   0   0
0   0   0   1   1   1   0   0   0
0   0   0   0   0   0   0   0   0
0   0   0   0   0   0   0   0   0
0   0   0   0   0   0   0   0   0];

```

Clear pixels on the border of the image using 4-connectivity. Note that `imclearborder` does not clear the pixel at (5,2) because, with 4-connectivity, it is not considered connected to the border pixel at (4,1).

```
BWc1 = imclearborder(BW,4)
```

```
BWc1 =
```

```

0   0   0   0   0   0   0   0   0
0   0   0   0   0   0   0   0   0
0   0   0   0   0   0   0   0   0
0   0   0   1   1   1   0   0   0
0   1   0   1   1   1   0   0   0
0   0   0   1   1   1   0   0   0
0   0   0   0   0   0   0   0   0
0   0   0   0   0   0   0   0   0
0   0   0   0   0   0   0   0   0

```

Now clear pixels on the border of the image using 8-connectivity. `imclearborder` clears the pixel at (5,2) because, with 8-connectivity, it is considered connected to the border pixel (4,1).

```
BWc2 = imclearborder(BW,8)
```

```
BWc2 =
```

```

0   0   0   0   0   0   0   0   0
0   0   0   0   0   0   0   0   0
0   0   0   0   0   0   0   0   0
0   0   0   1   1   1   0   0   0
0   0   0   1   1   1   0   0   0
0   0   0   1   1   1   0   0   0
0   0   0   0   0   0   0   0   0
0   0   0   0   0   0   0   0   0
0   0   0   0   0   0   0   0   0

```

Input Arguments

IM — Grayscale or binary image

real, nonsparse, numeric or logical array

Grayscale or binary image, specified as a real, nonsparse, numeric or logical array.

Example: `I = imread('pout.tif');` `I2 = imclearborder(I);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32` | `logical`

conn — Connectivity

8 (for 2-D) (default) | 4 | 6 | 18 | 26 | 3-by-3-by- ... -by-3 matrix

Connectivity, specified as one of the values in this table.

Value	Meaning
Two-dimensional connectivities	
4	4-connected neighborhood
8	8-connected neighborhood
Three-dimensional connectivities	
6	6-connected neighborhood
18	18-connected neighborhood
26	26-connected neighborhood

Connectivity can also be defined in a more general way for any dimension by using for `conn` a 3-by-3-by- ... -by-3 matrix of 0s and 1s. The 1-valued elements define neighborhood locations relative to the center element of `conn`. Note that `conn` must be symmetric around its center element.

Note A pixel on the edge of the input image might not be considered to be a border pixel if you specify a nondefault connectivity. For example, if `conn = [0 0 0; 1 1 1; 0 0 0]`, elements on the first and last row are not considered to be border pixels because,

according to that connectivity definition, they are not connected to the region outside the image.

Example: `I2 = imclearborder(I,4);`

Data Types: `double` | `logical`

Output Arguments

IM2 — Grayscale or binary image

real, nonsparse, numeric or logical array

Grayscale or binary image, returned as a real, nonsparse, numeric or logical array, depending on the input image you specify.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, note:

- Supports only up to 3-D inputs.
- The optional second input argument, `conn`, must be a compile-time constant.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

Algorithms

`imclearborder` uses morphological reconstruction where:

- Mask image is the input image.
- Marker image is zero everywhere except along the border, where it equals the mask image.

References

- [1] Soille, P., *Morphological Image Analysis: Principles and Applications*, Springer, 1999, pp. 164-165.

See Also

conndef

Introduced before R2006a

imclose

Morphologically close image

Syntax

```
IM2 = imclose(IM,SE)
IM2 = imclose(IM,NHOOD)
gpuarrayIM2 = imclose(gpuarrayIM, ___ )
```

Description

`IM2 = imclose(IM,SE)` performs morphological closing on the grayscale or binary image `IM`, returning the closed image, `IM2`. The structuring element, `SE`, must be a single structuring element object, as opposed to an array of objects. The morphological close operation is a dilation followed by an erosion, using the same structuring element for both operations.

`IM2 = imclose(IM,NHOOD)` performs closing with the structuring element `strel(NHOOD)`, where `NHOOD` is an array of 0's and 1's that specifies the structuring element neighborhood.

`gpuarrayIM2 = imclose(gpuarrayIM, ___)` performs the operation on a graphics processing unit (GPU), where `gpuarrayIM` is a `gpuArray` containing the grayscale or binary image. `gpuarrayIM2` is a `gpuArray` of the same class as the input image. This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-575 support: Yes.

“MATLAB Function Block” on page 1-575 support: Yes.

Class Support

`IM` can be any numeric or logical class and any dimension, and must be nonsparse. If `IM` is logical, then `SE` must be flat.

`gpuarrayIM` must be a `gpuArray` of type `uint8` or `logical`. When used with a `gpuarray`, the structuring element must be flat and two-dimensional.


The output has the same class as the input.

Examples

Use Morphological Closing to Fill Gaps in an Image

Read a binary image into the workspace and display it.

```
originalBW = imread('circles.png');  
imshow(originalBW);
```



Create a disk-shaped structuring element. Use a disk structuring element to preserve the circular nature of the object. Specify a radius of 10 pixels so that the largest gap gets filled.

```
se = strel('disk',10);
```

Perform a morphological close operation on the image.

```
closeBW = imclose(originalBW,se);  
figure, imshow(closeBW)
```



Use Morphological Closing to Fill Gaps in an Image on a GPU

Use morphological closing to join the circles in an image together by filling in the gaps between them and by smoothing their outer edges.

Read the image into the MATLAB workspace and view it.

```
originalBW = imread('circles.png');  
imshow(originalBW);
```

Create a disk-shaped structuring element. Use a disk structuring element to preserve the circular nature of the object. Specify a radius of 10 pixels so that the largest gap gets filled.

```
se = strel('disk',10);
```

Perform a morphological close operation on the image on a GPU.

```
closeBW = imclose(gpuArray(originalBW),se);  
figure, imshow(closeBW)
```

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, the input image, **IM**, must be 2-D or 3-D and the structuring element argument **SE** must be a single element—arrays of structuring elements are not supported. To obtain the same result as that obtained using an array of structuring elements, call the function sequentially.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`imdilate` | `imopen` | `imerode` | `gpuArray` | `strel` | `offsetstrel`

Introduced before R2006a

imcolormaptool

Choose Colormap tool

Syntax

```
imcolormaptool  
imcolormaptool(hclientfig)  
hfig = imcolormaptool(...)
```

Description

The Choose Colormap tool is an interactive colormap selection tool that allows you to change the colormap of the target (current) figure by selecting a colormap from a list of MATLAB colormap functions or workspace variables, or by entering a custom MATLAB expression.


`imcolormaptool` launches the Choose Colormap tool in a separate figure, which is associated with the target figure.

`imcolormaptool(hclientfig)` launches the Choose Colormap tool using `hclientfig` as the target figure. `hclientfig` must contain either a grayscale or an indexed image.

`hfig = imcolormaptool(...)` returns a handle to the Choose Colormap tool, `hfig`.

Examples

```
h = figure;  
imshow('cameraman.tif');  
imcolormaptool(h);
```



Choose Colormap Tool

See Also

[colormap](#) | [imshow](#) | [imtool](#)

Introduced in R2009a

imcomplement

Complement image

Syntax

```
IM2 = imcomplement(IM)  
gpuarrayIM2 = imcomplement(gpuarrayIM)
```

Description

`IM2 = imcomplement(IM)` computes the complement of the image `IM`. `IM` can be a binary, grayscale, or RGB image. `IM2` has the same class and size as `IM`.

In the complement of a binary image, zeros become ones and ones become zeros; black and white are reversed. In the complement of an intensity or RGB image, each pixel value is subtracted from the maximum pixel value supported by the class (or 1.0 for double-precision images) and the difference is used as the pixel value in the output image. In the output image, dark areas become lighter and light areas become darker.

`gpuarrayIM2 = imcomplement(gpuarrayIM)` computes the complement of the image on a GPU. The input image `gpuarrayIM` and the return values are `gpuArrays`. `gpuarrayIM2` is a `gpuArray` with the same underlying class and size as `gpuarrayIM`. This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-579 support: Yes.

“MATLAB Function Block” on page 1-580 support: Yes.

Examples

Create the complement of a `uint8` array

```
X = uint8([ 255 10 75; 44 225 100]);  
X2 = imcomplement(X)  
X2 =
```




```
0 245 180
211 30 155
```

Reverse black and white in a binary image


```
bw = imread('text.png');
bw2 = imcomplement(bw);
subplot(1,2,1),imshow(bw)
subplot(1,2,2),imshow(bw2)
```

Create the complement of an intensity image

```
I = imread('glass.png');
J = imcomplement(I);
imshow(I), figure, imshow(J)
```



Original Image



Complement Image

Create the complement of an intensity image on a GPU

```
I = gpuArray(imread('glass.png'));
J = imcomplement(I);
figure, imshow(I), figure, imshow(J)
```

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

`imcomplement` does not support `int64` and `uint64` data types

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

Tips

- If `IM` is a grayscale or RGB image of class `double`, you can use the expression `1 - IM` instead of this function. If `IM` is a binary image, you can use the expression `~IM` instead of this function.

See Also

`imabsdiff` | `imadd` | `imdivide` | `imlincomb` | `immultiply` | `imsubtract`

Introduced before R2006a

imcontour

Create contour plot of image data

Syntax

```
imcontour(I)  
imcontour(I,n)  
imcontour(I,v)  
imcontour(x,y,...)  
imcontour(...,LineStyle)  
[C,handle] = imcontour(...)
```

Description

`imcontour(I)` draws a contour plot of the grayscale image `I`, automatically setting up the axes so their orientation and aspect ratio match the image.

`imcontour(I,n)` draws a contour plot of the grayscale image `I`, automatically setting up the axes so their orientation and aspect ratio match the image. `n` is the number of equally spaced contour levels in the plot; if you omit the argument, the number of levels and the values of the levels are chosen automatically.

`imcontour(I,v)` draws a contour plot of `I` with contour lines at the data values specified in vector `v`. The number of contour levels is equal to `length(v)`.

`imcontour(x,y,...)` uses the vectors `x` and `y` to specify the *x*- and *y*-axis limits.

`imcontour(...,LineStyle)` draws the contours using the line type and color specified by `LineStyle`. Marker symbols are ignored.


`[C,handle] = imcontour(...)` returns the contour matrix `C` and a handle to an `hggroup` object.

Class Support

The input image can be of class `uint8`, `uint16`, `int16`, `single`, `double`, or `logical`.

Examples

```
I = imread('circuit.tif');  
imcontour(I,3)
```



See Also

[clabel](#) | [contour](#) | [LineStyle](#)

Introduced before R2006a

imcontrast


Adjust Contrast tool

Syntax

```
imcontrast
imcontrast(h)
hfigure = imcontrast(...)
```

Description

`imcontrast` creates an Adjust Contrast tool in a separate figure that is associated with the grayscale image in the current figure, called the target image. The Adjust Contrast tool is an interactive contrast and brightness adjustment tool, shown in the following figure, that you can use to adjust the black-to-white mapping used to display the image. When you use the tool, `imcontrast` adjusts the contrast of the displayed image by modifying the axes `CLim` property. To modify the actual pixel values in the target image, click the **Adjust Data** button. (This button is unavailable until you make a change to the contrast of the image.) For more information about using the tool, see “Tips” on page 1-584.



Note The Adjust Contrast tool can handle grayscale images of class `double` and `single` with data ranges beyond the default display range, which is `[0 1]`. For these images, `imcontrast` sets the histogram limits to fit the image data range, with padding at the upper and lower bounds.

`imcontrast(h)` creates the Adjust Contrast tool associated with the image specified by the handle `h`. `h` can be a handle to a figure, axes, uipanel, or image object. If `h` is an axes or figure handle, `imcontrast` uses the first image returned by `findobj(H, 'Type', 'image')`.

`hfigure = imcontrast(...)` returns a handle to the Adjust Contrast tool figure.

Examples

```
imshow('pout.tif')
imcontrast(gca)
```

More About

Tips

The Adjust Contrast tool presents a scaled histogram of pixel values (overly represented pixel values are truncated for clarity). Dragging on the left red bar in the histogram display changes the minimum value. The minimum value (and any value less than the minimum) displays as black. Dragging on the right red bar in the histogram changes the maximum value. The maximum value (and any value greater than the maximum) displays as white. Values in between the red bars display as intermediate shades of gray.

Together the minimum and maximum values create a "window". Stretching the window reduces contrast. Shrinking the window increases contrast. Changing the center of the window changes the brightness of the image. It is possible to manually enter the minimum, maximum, width, and center values for the window. Changing one value automatically updates the other values and the image.

For more information about using the Adjust Contrast tool, see “Adjust Image Contrast In Image Viewer App”.

Window/Level Interactivity

Clicking and dragging the mouse within the target image interactively changes the image's window values. Dragging the mouse horizontally from left to right changes the window width (i.e., contrast). Dragging the mouse vertically up and down changes the window center (i.e., brightness). Holding down the **Ctrl** key before clicking and dragging the mouse accelerates the rate of change; holding down the **Shift** key before clicking and dragging the mouse slows the rate of change. Keys must be pressed before clicking and dragging.

See Also

`imadjust` | `imtool` | `stretchlim`

Introduced before R2006a

imcrop

Crop image

Syntax

```
I2 = imcrop
I2 = imcrop(I)
X2 = imcrop(X,map)
___ = imcrop(h)

I2 = imcrop(I,rect)
X2 = imcrop(X,map,rect)
___ = imcrop(XData,YData,___)
[___,rect2] = imcrop(___)
[XData2,YData2,___] = imcrop(___)
```

Description

`I2 = imcrop` creates an interactive image cropping tool associated with the image displayed in the current figure, called the target image. The Crop Image tool is a moveable, resizable rectangle that you can position over the image and perform the crop operation interactively using the mouse. For more information about using the Crop Image tool, see “Interactive Behavior” on page 1-595. `imcrop` returns the cropped image, `I2`. With this syntax and the other interactive syntaxes, the Crop Image tool blocks the MATLAB command line until you complete the operation.

`I2 = imcrop(I)` displays the image `I` in a figure window and creates a cropping tool associated with that image. `I` can be a grayscale image, a truecolor image, or a logical array. `imcrop` returns the cropped image, `I2`.

`X2 = imcrop(X,map)` displays the indexed image `X` in a figure using the colormap `map`, and creates a cropping tool associated with that image. After you crop the image, `imcrop` returns the cropped indexed image, `X2`.

`___ = imcrop(h)` creates a cropping tool associated with the image specified by handle `h`. `h` may be an image, axes, uipanel, or figure handle. If `h` is an axes, uipanel, or figure handle, the cropping tool acts on the first image found in the container object.

`I2 = imcrop(I,rect)` crops the image `I`. `rect` is a four-element position vector of the form `[xmin ymin width height]` that specifies the size and position of the crop rectangle. `imcrop` returns the cropped image, `I2`.

`X2 = imcrop(X,map,rect)` crops the indexed image `X`. `map` specifies the colormap used with `X`. `rect` is a four-element position vector `[xmin ymin width height]` that specifies the size and position of the cropping rectangle. `imcrop` returns the cropped indexed image, `X2`.

`___ = imcrop(XData,YData, ___)` specifies a nondefault spatial coordinate system for the target image.

`[___ ,rect2] = imcrop(___)` returns the cropping rectangle in `rect2`, a four-element position vector, in addition to the cropped image.

`[XData2,YData2, ___] = imcrop(___)` returns two-element vectors that specify the `XData` and `YData` of the target image.

“Code Generation” on page 1-597 support: Yes.

“MATLAB Function Block” on page 1-597 support: Yes.

Examples


Crop Image Using Crop Image Interactive Tool

Read image into the workspace.

```
I = imread('cameraman.tif');
```


Open Crop Image tool associated with this image. Specify a variable in which to store the cropped image. The example includes the optional return value `rect` in which `imcrop` returns the four-element position vector of the rectangle you draw.

```
[I2, rect] = imcrop(I);
```


When you move the cursor over the image, it changes to a cross-hairs . The Crop Image tool blocks the MATLAB command line until you complete the operation.

Using the mouse, draw a rectangle over the portion of the image that you want to crop.

Draw crop rectangle.



Perform the crop operation by double-clicking in the crop rectangle or selecting Crop Image on the context menu.



The Crop Image tool returns the cropped area in the return variable, `I2`. The variable `rect` is the four-element position vector describing the crop rectangle you specified.

`whos`

Name	Size	Bytes	Class	Attributes
<code>I</code>	256x256	65536	uint8	
<code>I2</code>	121x126	15246	uint8	

rect 1x4 32 double

Crop Image By Specifying Crop Rectangle

Read image into the workspace.


```
I = imread('circuit.tif');
```

Crop image, specifying crop rectangle.

```
I2 = imcrop(I,[75 68 130 112]);
```

Display original image and cropped image.

```
subplot(1,2,1)
imshow(I)
title('Original Image')
subplot(1,2,2)
imshow(I2)
title('Cropped Image')
```



Crop Indexed Image Specifying Crop Rectangle

Load indexed image with its associated map into the workspace.

```
load trees
```


Crop indexed image, specifying crop rectangle.

```
X2 = imcrop(X,map,[30 30 50 75]);
```

Display original image and cropped image.

```
subplot(1,2,1)  
imshow(X,map)  
title('Original Image')
```

```
subplot(1,2,2)
imshow(X2,map)
title('Cropped Image')
```



Input Arguments

I — Image to be cropped

real, nonsparse, numeric array

Image to be cropped, specified as a real, nonsparse, numeric array. With the syntaxes where you specify `rect` as an input argument, the input image can be logical or numeric, and must be real and nonsparse. With the other syntaxes, `imcrop` calls `imshow` and

accepts whatever image classes `imshow` accepts. `I` can be `logical`, `uint8`, `uint16`, `int16`, `single`, or `double`. A truecolor image can be `uint8`, `int16`, `uint16`, `single`, or `double`.

Example: `I = imread('cameraman.tif'); I2 = imcrop(I);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

X — Indexed image to be cropped

real, nonsparse numeric array

Indexed image to be cropped, specified as a real, nonsparse numeric array. With the syntaxes where you specify `rect` as an input argument, the input image can be `logical` or numeric, and must be real and nonsparse. With the other syntaxes, `imcrop` calls `imshow` and accepts any image class that `imshow` accepts. For an indexed image, `X` can be `logical`, `uint8`, `uint16`, `single`, or `double`.

Example: `load trees; X2 = imcrop(X,map);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

map — Color map associated with indexed image

m-by-3 numeric array

Color map associated with indexed image, specified as an *m*-by-3 numeric array.

Example: `load trees; X2 = imcrop(X,map);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

rect — Size and position of the crop rectangle

four-element position vector

Size and position of the crop rectangle, specified as a four-element position vector of the form `[xmin ymin width height]`.

Example: `I2 = imcrop(I,[20 20 40 90]);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

h — Handle to image to be cropped

handle to an image, axes, `uipanel`, or `figure`

Handle to image to be cropped, specified as a handle to an image, axes, uipanel, or figure.

```
Example: I = imread('cameraman.tif'); h = imshow(I); I2 = imcrop(h);
```

Data Types: double

XData — X limits of nondefault coordinate system

two-element vector

X limits of nondefault coordinate system, specified as a two-element vector.

```
Example: I2 = imcrop([10 256],[20 256],I);
```

Data Types: single | double | int8 | int16 | int32 | int64 | uint8 | uint16 | uint32 | uint64

YData — Y limits of nondefault coordinate system

two-element vector

Y limits of nondefault coordinate system, specified as a two-element vector.

```
Example: I2 = imcrop([10 256],[20 256],I);
```

Data Types: single | double | int8 | int16 | int32 | int64 | uint8 | uint16 | uint32 | uint64

Output Arguments

I2 — Cropped image

real, nonsparse, numeric array

Cropped image, returned as a real, nonsparse, numeric array.

If you specify an input image, the output image has the same class as the input image.

If you don't specify an input image, i.e., you call `imcrop` with no input arguments or a handle, the output image has the same class as the input image except for `int16` or `single`. If the input image is `int16` or `single`, the output image is `double`.

X2 — Cropped indexed image

real, nonsparse, numeric array

Cropped image, returned as a real, nonsparse, numeric array.

If you specified an input image, the output image has the same class as the input image. If you don't specify an image as an input argument, i.e., you call `imcrop` with no input arguments or a handle, the output image has the same class as the input image except for `int16` or `single`. If the input image is `int16` or `single`, the output image is `double`.

XData2 — X limits of nondefault coordinate system

two-element vector

X limits of nondefault coordinate system, returned as a two-element vector.

YData2 — Y limits of nondefault coordinate system

two-element vector

Y limits of nondefault coordinate system, returned as a two-element vector.


rect2 — Size and position of the crop rectangle


four-element position vector



Size and position of the crop rectangle, returned as a four-element position vector of the form `[xmin ymin width height]`.

More About

Interactive Behavior

When the Crop Image tool is active in a figure, the pointer changes to cross hairs  when you move it over the target image. Using the mouse, you specify the crop rectangle by clicking and dragging the mouse. You can move or resize the crop rectangle using the mouse. When you are finished sizing and positioning the crop rectangle, create the cropped image by double-clicking the left mouse button or by choosing **Crop Image** from the context menu. `imcrop` returns the cropped image, `I2`. The following figure illustrates the Crop Image tool with the context menu displayed. For more information about the interactive capabilities of the tool, see the table that follows.



Interactive Behavior	Description
Deleting the Crop Image tool.	Press Backspace , Escape or Delete , or right-click inside the crop rectangle and select Cancel from the context menu. Note: If you delete the ROI, the function returns empty values.
Resizing the Crop Image tool.	Select any of the resize handles on the crop rectangle. The pointer changes to a double-headed arrow  . Click and drag the mouse to resize the crop rectangle.
Moving the Crop Image tool.	Move the pointer inside the boundary of the crop rectangle. The pointer changes to a fleur shape  . Click and drag the mouse to move the rectangle over the image.
Changing the color used to display the crop rectangle.	Right-click inside the boundary of the crop rectangle and select Set Color from the context menu.

Interactive Behavior	Description
Cropping the image.	Double-click the left mouse button or right-click inside the boundary of the crop rectangle and select Crop Image from the context menu.
Retrieving the coordinates of the crop rectangle.	Right-click inside the boundary of the crop rectangle and select Copy Position from the context menu. <code>imcrop</code> copies a four-element position vector (<code>[xmin ymin width height]</code>) to the clipboard.

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, note the following:

- The interactive syntaxes are not supported, including:
 - `I2 = imcrop`
 - `I2 = imcrop(I)`
 - `X2 = imcrop(X,map)`
 - `I2 = imcrop(h)`
- Indexed image are not supported, including the noninteractive syntax `X2 = imcrop(X,map,rect)`;

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

Tips

- Because `rect` is specified in terms of spatial coordinates, the `width` and `height` elements of `rect` do not always correspond exactly with the size of the output image. For example, suppose `rect` is `[20 20 40 30]`, using the default spatial coordinate system. The upper-left corner of the specified rectangle is the center of the pixel (20,20) and the lower-right corner is the center of the pixel (50,60). The resulting output image is 31-by-41, not 30-by-40, because the output image includes all pixels in the input image that are completely *or partially* enclosed by the rectangle.

See Also

imrect | zoom

Introduced before R2006a

imdilate

Dilate image

Syntax

```
IM2 = imdilate(IM,SE)
IM2 = imdilate(IM,NHOOD)
IM2 = imdilate( ____,PACKOPT)
IM2 = imdilate( ____,SHAPE)
gpuarrayIM2 = imdilate(gpuarrayIM, ____)
```

Description

`IM2 = imdilate(IM,SE)` dilates the grayscale, binary, or packed binary image `IM`, returning the dilated image, `IM2`. The argument `SE` is a structuring element object, or array of structuring element objects, returned by the `strel` or `offsetstrel` function.

If `IM` is logical, the structuring element must be flat and `imdilate` performs binary dilation. Otherwise, `imdilate` performs grayscale dilation. If `SE` is an array of structuring element objects, `imdilate` performs multiple dilations of the input image, using each structuring element in succession.

`IM2 = imdilate(IM,NHOOD)` dilates the image `IM`, where `NHOOD` is a matrix of 0's and 1's that specifies the structuring element neighborhood. This is equivalent to the syntax `imdilate(IM,strel(NHOOD))`. The `imdilate` function determines the center element of the neighborhood by `floor((size(NHOOD)+1)/2)`.

`IM2 = imdilate(____,PACKOPT)` specifies whether `IM` is a packed binary image. `PACKOPT` can have either of the following values. Default value is enclosed in braces (`{}`).

Value	Description
'ispacked'	<code>IM</code> is treated as a packed binary image as produced by <code>bwpack</code> . <code>IM</code> must be a 2-D <code>uint32</code> array and <code>SE</code> must be a flat 2-D structuring element. If the value of <code>PACKOPT</code> is 'ispacked', <code>PADOPT</code> must be 'same'.

Value	Description
{ 'notpacked' }	IM is treated as a normal array.

IM2 = imdilate(____, SHAPE) specifies the size of the output image. SHAPE can have either of the following values. Default value is enclosed in braces ({}).

Value	Description
{ 'same' }	Make the output image the same size as the input image. If the value of PACKOPT is 'ispacked', SHAPE must be 'same'.
'full'	Compute the full dilation.

gpuarrayIM2 = imdilate(gpuarrayIM, ____) performs the operation on a graphics processing unit (GPU), where gpuarrayIM is a gpuArray that contains a grayscale or binary image. gpuarrayIM2 is a gpuArray of the same class as the input image. Note that the PACKOPT syntax is not supported on a GPU. This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-608 support: Yes.

“MATLAB Function Block” on page 1-608 support: Yes.

Class Support

IM can be logical or numeric and must be real and nonsparse. It can have any dimension. If IM is logical, SE must be flat. The output has the same class as the input. If the input is packed binary, then the output is also packed binary.

gpuarrayIM must be a gpuArray of type uint8 or logical. When used with a gpuarray, the structuring element must be flat and two-dimensional. The output has the same class as the input.

Examples

Dilate Image with Vertical Line Structuring Element

Read a binary image into the workspace.

```
BW = imread('text.png');
```


Create a vertical line shaped structuring element.

```
se = strel('line',11,90);
```

Dilate the image with a vertical line structuring element and compare the results.

```
BW2 = imdilate(BW,se);  
imshow(BW), title('Original')  
figure, imshow(BW2), title('Dilated')
```

Original





Dilate Grayscale Image with Rolling Ball

Read grayscale image into the workspace.

```
originalI = imread('cameraman.tif');
```

Create a nonflat ball-shaped structuring element.

```
se = offsetstrel('ball',5,5);
```

Dilate the image.

```
dilatedI = imdilate(originalI,se);
```

Display the original image and the dilated image.

```
figure  
imshow(originalI)
```



```
figure  
imshow(dilatedI)
```





Determine Domain of Composition of Structuring Elements

Create two flat, line-shaped structuring elements, one at 0 degrees and the other at 90 degrees.

```
se1 = strel('line',3,0)
se2 = strel('line',3,90)
```

```
se1 =
```

```
strel is a line shaped structuring element with properties:
```

```
    Neighborhood: [1 1 1]
    Dimensionality: 2
```

```
se2 =
```

strel is a line shaped structuring element with properties:

```
Neighborhood: [3x1 logical]
Dimensionality: 2
```

Dilate the scalar value 1 with both structuring elements in sequence, using the 'full' option.

```
composition = imdilate(1,[se1 se2], 'full')
```

```
composition =
```

```
  1   1   1
  1   1   1
  1   1   1
```

Dilate Points in 3D Space Using Spherical Structuring Elements

Create a logical 3D volume with two points.


```
BW = false(100,100,100);
BW(25,25,25) = true;
BW(75,75,75) = true;
```

Dilate the 3D volume using a spherical structuring element.

```
se = strel('sphere',25);
dilatedBW = imdilate(BW,se);
```

Visualize the dilated image volume.

```
figure
isosurface(dilatedBW)
```



Dilate a Binary Image with a Vertical Line Structuring Element on a GPU

Read a binary image.

```
originalBW = imread('text.png');
```

Create a structuring element.

```
se = strel('line',11,90);
```

Dilate the image with a vertical line structuring element and compare the results. Note how the example passes the image to the `gpuArray` function as it passes it to `imdilate`.

```
dilatedBW = imdilate(gpuArray(originalBW),se);
```

```
figure, imshow(originalBW), figure, imshow(dilatedBW)
```

Dilate a Grayscale Image with a Disk Structuring Element on a GPU

Read a grayscale image.

```
originalI = imread('cameraman.tif');
```

Create a structuring element.

```
se = strel('disk',5);
```

Dilate a grayscale image with a rolling ball structuring element.

```
dilatedI = imdilate(gpuArray(originalI),se);
figure, imshow(originalI), figure, imshow(dilatedI)
```

Definitions

The *binary dilation* of A by B , denoted $A \oplus B$, is defined as the set operation:

$$A \oplus B = \left\{ z \mid \left(\hat{B} \right)_z \cap A \neq \emptyset \right\},$$

where \hat{B} is the reflection of the structuring element B . In other words, it is the set of pixel locations z , where the reflected structuring element overlaps with foreground pixels in A when translated to z . Note that some people use a definition of dilation in which the structuring element is not reflected.

In the general form of *gray-scale dilation*, the structuring element has a height. The gray-scale dilation of $A(x,y)$ by $B(x,y)$ is defined as:

$$(A \oplus B)(x,y) = \max \left\{ A(x-x',y-y') + B(x',y') \mid (x',y') \in D_B \right\},$$

where D_B is the domain of the structuring element B and $A(x,y)$ is assumed to be $-\infty$ outside the domain of the image. To create a structuring element with nonzero height

values, use the syntax `strel(nhood,height)`, where `height` gives the height values and `nhood` corresponds to the structuring element domain, D_B .

Most commonly, gray-scale dilation is performed with a flat structuring element ($B(x,y) = 0$). Gray-scale dilation using such a structuring element is equivalent to a local-maximum operator:

$$(A \oplus B)(x,y) = \max \{A(x-x',y-y') \mid (x',y') \in D_B\}.$$

All of the `strel` syntaxes except for `strel(nhood,height)`, `strel('arbitrary',nhood,height)`, and `strel('ball',...)` produce flat structuring elements.

For more information about binary dilation, see [1].

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, note the following:

- The input image, `IM`, must be 2-D or 3-D.
- The structuring element argument `SE` must be a single element—arrays of structuring elements are not supported. To obtain the same result as that obtained using an array of structuring elements, call the function sequentially.
- When the target is **MATLAB Host Computer**, the `PACKOPT` and `SHAPE` arguments must be compile-time constants. When the target is any other platform, the `PACKOPT` syntax is not supported.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

Algorithms

`imdilate` automatically takes advantage of the decomposition of a structuring element object (if it exists). Also, when performing binary dilation with a structuring element object that has a decomposition, `imdilate` automatically uses binary image packing to speed up the dilation.

Dilation using bit packing is described in [3].

References

- [1] Gonzalez, R. C., R. E. Woods, and S. L. Eddins, *Digital Image Processing Using MATLAB*, Gatesmark Publishing, 2009.
- [2] Haralick, R. M., and L. G. Shapiro, *Computer and Robot Vision*, Vol. I, Addison-Wesley, 1992, pp. 158-205.
- [3] van den Boomgard, R, and R. van Balen, "Methods for Fast Morphological Image Transforms Using Bitmapped Images," *Computer Vision, Graphics, and Image Processing: Graphical Models and Image Processing*, Vol. 54, Number 3, pp. 254-258, May 1992.

See Also

`bwpack` | `bwunpack` | `conv2` | `filter2` | `imclose` | `imerode` | `imopen` | `strel` | `offsetstrel` | `gpuArray`

Introduced before R2006a

imshow

Display Range tool


Syntax

```
imshow  
imshow(h)  
imshow(hparent,himage)  
hpanel = imshow(...)
```

Description

`imshow` creates a Display Range tool in the current figure. The Display Range tool shows the display range of the intensity image or images in the figure.

The tool is a uipanel object, positioned in the lower-right corner of the figure. It contains the text string `Display range:` followed by the display range values for the image, as shown in the following figure.



For an indexed, truecolor, or binary image, the display range is not applicable and is set to empty (`[]`).

`imshow(h)` creates a Display Range tool in the figure specified by the handle `h`, where `h` is a handle to an image, axes, uipanel, or figure object. Axes, uipanel, or figure objects must contain at least one image object.

`imshow(hparent,himage)` creates a Display Range tool in `hparent` that shows the display range of `himage`. `himage` is a handle to an image or an array of image handles. `hparent` is a handle to the figure or uipanel object that contains the display range tool.

`hpanel = imshow(...)` returns a handle to the Display Range tool uipanel.

Note

The Display Range tool can work with multiple images in a figure. When the pointer is not in an image in a figure, the Display Range tool displays the text string [black white].

Examples

Display an image and include the Display Range tool.

```
imshow('bag.png');  
imshow_range;
```

Import a 16-bit DICOM image and display it with its default range and scaled range in the same figure.

```
dcm = dicomread('CT-MONO2-16-ankle.dcm');  
subplot(1,2,1), imshow(dcm);  
subplot(1,2,2), imshow(dcm,[]);  
imshow_range;
```

See also

`imshow`

Introduced before R2006a

imdistline

Distance tool


Syntax


```
h = imdistline
h = imdistline(hparent)
h = imdistline(..., x, y)
```


Description

`h = imdistline` creates a Distance tool on the current axes. The function returns `h`, a handle to an `imdistline` object.

The Distance tool is a draggable, resizable line, superimposed on an axes, that measures the distance between the two endpoints of the line. The Distance tool displays the distance in a text label superimposed over the line. The tools specifies the distance in data units determined by the `XData` and `YData` properties, which is pixels, by default. The following figure shows a Distance tool on an axes.



To move the Distance tool, position the pointer over the line, the shape changes to the fleur, . Click and drag the line using the mouse. To resize the Distance tool, move the pointer over either of the endpoints of the line, the shape changes to the pointing

finger, . Click and drag the endpoint of the line using the mouse. The line also supports a context menu that allows you to control various aspects of its functioning and appearance. See Context Menu for more information. Right-click the line to access the context menu.

`h = imdistline(hparent)` creates a draggable Distance tool on the object specified by `hparent`. `hparent` specifies the Distance tool's parent, which is typically an axes object, but can also be any other object that can be the parent of an `hgroup` object.

`h = imdistline(..., x, y)` creates a Distance tool with endpoints located at the locations specified by the vectors `x` and `y`, where `x = [x1 x2]` and `y = [y1 y2]`.

Context Menu

Distance Tool Behavior	Context Menu Item
Export endpoint and distance data to the workspace	Select Export to Workspace from the context menu.
Toggle the distance label on/off.	Select Show Distance Label from the context menu.
Specify horizontal and vertical drag constraints	Select Constrain Drag from the context menu.
Change the color used to display the line.	Select Set Color from the context menu.
Delete the Distance tool object	Select Delete from the context menu.

API Functions

The Distance tool contains a structure of function handles, called an API, that can be used to retrieve distance information and control other aspects of Distance tool behavior. To retrieve this structure from the Distance tool, use the `iptgetapi` function, where `h` is a handle to the Distance tool.

```
api = iptgetapi(h)
```

The following table lists the functions in the API, with their syntax and brief descriptions.

Function	Description
getDistance	Returns the distance between the endpoints of the Distance tool. <code>dist = getDistance()</code> The value returned is in data units determined by the <code>XData</code> and <code>YData</code> properties, which is pixels, by default.
getAngleFromHorizontal	Returns the angle in degrees between the line defined by the Distance tool and the horizontal axis. The angle returned is between 0 and 180 degrees. (For information about how this angle is calculated, see “Tips” on page 1-618.) <code>angle = getAngleFromHorizontal()</code>
setLabelTextFormatter	Sets the format string used in displaying the distance label. <code>setLabelTextFormatter(str)</code> <code>str</code> is a character array specifying a format string in the form expected by <code>sprintf</code> .
getLabelTextFormatter	Returns a character array specifying the format string used to display the distance label. <code>str = getLabelTextFormatter()</code> <code>str</code> is a character array specifying a format string in the form expected by <code>sprintf</code> .
setLabelVisible	Sets visibility of Distance tool text label. <code>setLabelVisible(h,TF)</code> <code>h</code> is the Distance tool. <code>TF</code> is a logical scalar. When the distance label is visible, <code>TF</code> is true. When the distance label is invisible, <code>TF</code> is false.
getLabelVisible	Gets visibility of Distance tool text label. <code>TF = getLabelVisible(h)</code>

Function	Description
	h is the Distance tool. TF is a logical scalar. When TF is true, the distance label is visible. When TF is false, the distance label is invisible.
setPosition	Sets the endpoint positions of the Distance tool. setPosition(X,Y) setPosition([X1 Y1; X2 Y2])
getPosition	Returns the endpoint positions of the Distance tool. pos = getPosition() pos is a 2-by-2 array [X1 Y1; X2 Y2].
delete	Deletes the Distance tool associated with the API. delete()
setColor	Sets the color used to draw the Distance tool. setColor(new_color) new_color can be a three-element vector specifying an RGB triplet, or a text string specifying the long or short names of a predefined color, such as 'white' or 'w'. For a complete list of these predefined colors and their short names, see ColorSpec.
getColor	Gets the color used to draw the ROI object h. color = getColor(h) color is a three-element vector that specifies an RGB triplet.

Function	Description
<p><code>addNewPositionCallback</code></p>	<p>Adds the function handle <code>fcn</code> to the list of new-position callback functions.</p> <pre>id = addNewPositionCallback(fcn)</pre> <p>Whenever the Distance tool changes its position, each function in the list is called with the following syntax.</p> <pre>fcn(pos)</pre> <p><code>pos</code> is a 2-by-2 array [X1 Y1; X2 Y2].</p> <p>The return value, <code>id</code>, is used only with <code>removeNewPositionCallback</code>.</p>
<p><code>removeNewPositionCallback</code></p>	<p>Removes the corresponding function from the new-position callback list.</p> <pre>removeNewPositionCallback(id)</pre> <p><code>id</code> is the identifier returned by <code>addNewPositionCallback</code>.</p>
<p><code>setPositionConstraintFcn</code></p>	<p>Sets the position constraint function to be the specified function handle, <code>fcn</code>. Use this function to control where the Distance tool can be moved and resized.</p> <pre>setPositionConstraintFcn(fcn)</pre> <p>Whenever the Distance tool is moved or resized because of a mouse drag, the constraint function is called using the following syntax.</p> <pre>constrained_position = fcn(new_position)</pre> <p><code>new_position</code> is a 2-by-2 array [X1 Y1; X2 Y2].</p>
<p><code>getPositionConstraintFcn</code></p>	<p>Returns the function handle of the current drag constraint function.</p> <pre>fcn = getDragConstraintFcn()</pre>

Examples

Example 1

Insert a Distance tool into an image. Use `makeConstrainToRectFcn` to specify a drag constraint function that prevents the Distance tool from being dragged outside the extent of the image. Right-click the Distance tool and explore the context menu options.

```
figure, imshow('pout.tif');
h = imdistline(gca);
api = iptgetapi(h);
fcn = makeConstrainToRectFcn('imline',...
    get(gca,'XLim'),get(gca,'YLim'));
api.setDragConstraintFcn(fcn);
```

Example 2

Position endpoints of the Distance tool at the specified locations.

```
close all, imshow('pout.tif');
h = imdistline(gca,[10 100],[10 100]);
```

Delete the Distance tool.

```
api = iptgetapi(h);
api.delete();
```

Example 3

Use the Distance tool with `XData` and `YData` of associated image in non-pixel units. This example requires the `boston.tif` image from the Mapping Toolbox software, which includes material copyrighted by GeoEye™, all rights reserved.

```
start_row = 1478;
end_row = 2246;
meters_per_pixel = 1;
rows = [start_row meters_per_pixel end_row];
start_col = 349;
end_col = 1117;
cols = [start_col meters_per_pixel end_col];
img = imread('boston.tif','PixelRegion',{rows,cols});
figure;
hImg = imshow(img);
title('1 meter per pixel');

% Specify initial position of distance tool on Harvard Bridge.
```

```
hline = imdistline(gca,[271 471],[108 650]);
api = iptgetapi(hline);
api.setLabelTextFormatter('%02.0f meters');

% Repeat process but work with a 2 meter per pixel sampled image. Verify
% that the same distance is obtained.
meters_per_pixel = 2;
rows = [start_row meters_per_pixel end_row];
cols = [start_col meters_per_pixel end_col];
img = imread('boston.tif','PixelRegion',{rows,cols});
figure;
hImg = imshow(img);
title('2 meters per pixel');

% Convert XData and YData to meters using conversion factor.
XDataInMeters = get(hImg,'XData')*meters_per_pixel;
YDataInMeters = get(hImg,'YData')*meters_per_pixel;

% Set XData and YData of image to reflect desired units.
set(hImg,'XData',XDataInMeters,'YData',YDataInMeters);
set(gca,'XLim',XDataInMeters,'YLim',YDataInMeters);

% Specify initial position of distance tool on Harvard Bridge.
hline = imdistline(gca,[271 471],[108 650]);
api = iptgetapi(hline);
api.setLabelTextFormatter('%02.0f meters');
```

More About

Tips

If you use `imdistline` with an axes that contains an image object, and do not specify a drag constraint function, users can drag the line outside the extent of the image. When used with an axes created by the `plot` function, the axes limits automatically expand to accommodate the movement of the line.

To understand how `imdistline` calculates the angle returned by `getAngleToHorizontal`, draw an imaginary horizontal vector from the bottom endpoint of the distance line, extending to the right. The value returned by `getAngleToHorizontal` is the angle from this horizontal vector to the distance line, which can range from 0 to 180 degrees.

See Also

`iptgetapi` | `makeConstrainToRectFcn`

Introduced before R2006a

imdivide

Divide one image into another or divide image by constant

Syntax

```
Z = imdivide(X,Y)
```

Description

`Z = imdivide(X,Y)` divides each element in the array `X` by the corresponding element in array `Y` and returns the result in the corresponding element of the output array `Z`. `X` and `Y` are real, nonsparse numeric arrays with the same size and class, or `Y` can be a scalar `double`. `Z` has the same size and class as `X` and `Y`, unless `X` is logical, in which case `Z` is `double`.

If `X` is an integer array, elements in the output that exceed the range of integer type are truncated, and fractional values are rounded.

If `X` and `Y` are numeric arrays of the same size and class, you can use the expression `X./Y` instead of `imdivide`.

Examples

Divide two `uint8` arrays. Note that fractional values greater than or equal to 0.5 are rounded up to the nearest integer.

```
X = uint8([ 255 10 75; 44 225 100]);  
Y = uint8([ 50 20 50; 50 50 50 ]);  
Z = imdivide(X,Y)  
Z =
```

```
    5     1     2  
    1     5     2
```

Estimate and divide out the background of the rice image.

```
I = imread('rice.png');
```

```
background = imopen(I,strel('disk',15));  
Ip = imdivide(I,background);  
imshow(Ip,[])
```

Divide an image by a constant factor.

```
I = imread('rice.png');  
J = imdivide(I,2);  
subplot(1,2,1), imshow(I)  
subplot(1,2,2), imshow(J)
```

See Also

[imabsdiff](#) | [imadd](#) | [incomplement](#) | [imlincomb](#) | [immultiply](#) | [imsubtract](#)

Introduced before R2006a

imellipse

Create draggable ellipse

Syntax

```
h = imellipse
h = imellipse(hparent)
h = imellipse(hparent, position)
h = imellipse(...,param1, val1, ...)
```

Description

`h = imellipse` begins interactive placement of an ellipse on the current axes. The function returns `h`, a handle to an `imellipse` object. The ellipse has a context menu associated with it that controls aspects of its appearance and behavior—see “Interactive Behavior” on page 1-622. Right-click on the line to access this context menu.


`h = imellipse(hparent)` begins interactive placement of an ellipse on the object specified by `hparent`. `hparent` specifies the HG parent of the ellipse graphics, which is typically an axes but can also be any other object that can be the parent of an `hggroup`.


`h = imellipse(hparent, position)` creates a draggable ellipse on the object specified by `hparent`. `position` is a four-element vector that specifies the initial location of the ellipse in terms of a bounding rectangle. `position` has the form `[xmin ymin width height]`.

`h = imellipse(...,param1, val1, ...)` creates a draggable ellipse, specifying parameters and corresponding values that control the behavior of the ellipse. The following table lists the parameter available. Parameter names can be abbreviated, and case does not matter.


Parameter	Value
'PositionConstraintFcn'	Function handle that is called whenever the mouse is dragged. You can use this to control where the ellipse may be dragged. See the help for the <code>setPositionConstraintFcn</code> method for information about valid function handles.


Interactive Behavior

When you call `imellipse` with an interactive syntax, the pointer changes to a cross hairs  when over an image. Click and drag the mouse to specify the size and position of the ellipse. The ellipse also supports a context menu that you can use to control aspects of its appearance and behavior. The following figure illustrates the ellipse with its context menu.



The following table lists the interactive behavior supported by `imellipse`.

Interactive Behavior	Description
Moving the entire ellipse.	Move the pointer inside the ellipse. The pointer changes to a fleur shape  . Click and drag the mouse to move the ellipse.

Interactive Behavior	Description
Resizing the ellipse.	Move the pointer over a resizing handle on the ellipse. The pointer changes to a double-ended arrow shape  . Click and drag the mouse to resize the ellipse.
Changing the color used to display the ellipse.	Move the pointer inside the ellipse. Right-click and select Set Color from the context menu.
Retrieving the current position of the ellipse.	Move the pointer inside the ellipse. Right-click and select Copy Position from the context menu. <code>imellipse</code> copies a four-element position vector [xmin ymin width height] to the clipboard.
Preserving the current aspect ratio of the ellipse during resizing.	Move the pointer inside the ellipse. Right-click and select Fix Aspect Ratio from the context menu.
Deleting the ellipse	Move the pointer inside the ellipse. Right-click and select Delete from the context menu. To remove this option from the context menu, set the <code>Deletable</code> property to false: <code>h = imellipse(); h.Deletable = false;</code>

Methods

Each `imellipse` object supports a number of methods. Type `methods imellipse` to see a complete list.

addNewPositionCallback — Add new-position callback to ROI object

See `imroi` for information.

createMask — Create mask within image

See `imroi` for information.

delete — Delete ROI object

See `imroi` for information.

getColor — Get color used to draw ROI object

See `imroi` for information.

getPosition — Return current position of ellipse

See `imrect` for information.

getPositionConstraintFcn — Return function handle to current position constraint function

See `imroi` for information.

getVertices — Return vertices on perimeter of ellipse

`vert = getVertices(h)` returns a set of vertices which lie along the perimeter of the ellipse `h`. `vert` is a N-by-2 array.

removeNewPositionCallback — Remove new-position callback from ROI object.

See `imroi` for information.

resume — Resume execution of MATLAB command line

See `imroi` for information.

setColor — Set color used to draw ROI object

See `imroi` for information.

setConstrainedPosition — Set ROI object to new position

See `imroi` for information.

setFixedAspectRatioMode — Control whether aspect ratio preserved during resize

See `imrect` for information.

setPosition — Set ellipse to new position

See `imrect` for information.

setPositionConstraintFcn — Set position constraint function of ROI object.

See `imroi` for information.

setResizable — Set resize behavior of ellipse

See `imrect` for information.

wait — Block MATLAB command line until ROI creation is finished

`vert = wait(h)` blocks execution of the MATLAB command line until you finish positioning the ROI object `h`. You indicate completion by double-clicking on the ROI object. The returned vertices, `vert`, is of the form returned by the `getVertices` method.

Examples

Example 1

Create an ellipse, using callbacks to display the updated position in the title of the figure. The example illustrates using the `makeConstrainToRectFcn` to keep the ellipse inside the original `xlim` and `ylim` ranges.

```
figure, imshow('cameraman.tif');
h = imellipse(gca, [10 10 100 100]);
addNewPositionCallback(h,@(p) title(mat2str(p,3)));
fcn = makeConstrainToRectFcn('imellipse',get(gca,'XLim'),get(gca,'YLim'));
setPositionConstraintFcn(h,fcn);
```

Example 2

Interactively place an ellipse by clicking and dragging. Use `wait` to block the MATLAB command line. Double-click on the ellipse to resume execution of the MATLAB command line.

```
figure, imshow('pout.tif');
h = imellipse;
position = wait(h);
```

More About

Tips

If you use `imellipse` with an axes that contains an image object, and do not specify a position constraint function, users can drag the ellipse outside the extent of the image and lose the ellipse. When used with an axes created by the `plot` function, the axes limits automatically expand to accommodate the movement of the ellipse.

See Also

`imfreehand` | `impoly` | `imrect` | `imroi` | `imline` | `impoint` | `iptgetapi` |
`makeConstrainToRectFcn`

Introduced in R2007b

imerode

Erode image

Syntax

```
IM2 = imerode(IM,SE)
IM2 = imerode(IM,NHOOD)
IM2 = imerode( ____,PACKOPT,M)
IM2 = imerode( ____,SHAPE)
gpuarrayIM2 = imerode(gpuarrayIM, ____)
```

Description

`IM2 = imerode(IM,SE)` erodes the grayscale, binary, or packed binary image `IM`, returning the eroded image `IM2`. The argument `SE` is a structuring element object or array of structuring element objects returned by the `strel` or `offsetstrel` functions.

If `IM` is logical and the structuring element is flat, `imerode` performs binary erosion; otherwise it performs grayscale erosion. If `SE` is an array of structuring element objects, `imerode` performs multiple erosions of the input image, using each structuring element in `SE` in succession.

`IM2 = imerode(IM,NHOOD)` erodes the image `IM`, where `NHOOD` is an array of 0's and 1's that specifies the structuring element neighborhood. This is equivalent to the syntax `imerode(IM,strel(NHOOD))`. The `imerode` function determines the center element of the neighborhood by `floor((size(NHOOD)+1)/2)`.

`IM2 = imerode(____,PACKOPT,M)` specifies whether `IM` is a packed binary image and, if it is, provides the row dimension `M` of the original unpacked image. `PACKOPT` can have either of the following values. Default value is enclosed in braces (`{}`).

Value	Description
'ispacked'	<code>IM</code> is treated as a packed binary image as produced by <code>bwpack</code> . <code>IM</code> must be a 2-D <code>uint32</code> array and <code>SE</code> must be a flat 2-D structuring element.
{'notpacked'}	<code>IM</code> is treated as a normal array.

If `PACKOPT` is `'ispacked'`, you must specify a value for `M`.

`IM2 = imerode(____, SHAPE)` specifies the size of the output image. `SHAPE` can have either of the following values. Default value is enclosed in braces (`{}`).

Value	Description
<code>{ 'same' }</code>	Make the output image the same size as the input image. If the value of <code>PACKOPT</code> is <code>'ispacked'</code> , <code>SHAPE</code> must be <code>'same'</code> .
<code>'full'</code>	Compute the full erosion.

`gpuarrayIM2 = imerode(gpuarrayIM, ____,)` performs the operation on a graphics processing unit (GPU). `gpuarrayIM` is a `gpuArray` that contains a grayscale or binary image. `gpuarrayIM2` is a `gpuArray` of the same class as the input image. Note that the `PACKOPT` syntax is not supported on a GPU. This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-634 support: Yes.

“MATLAB Function Block” on page 1-635 support: Yes.

Class Support

`IM` can be numeric or logical and it can be of any dimension. If `IM` is logical and the structuring element is flat, the output image is logical; otherwise the output image has the same class as the input. If the input is packed binary, then the output is also packed binary.

`gpuarrayIM` must be a `gpuArray` of type `uint8` or `logical`. When used with a `gpuarray`, the structuring element must be flat and two-dimensional. The output has the same class as the input.

Examples

Erode Binary Image with Line Structuring Element

Read binary image into the workspace.

```
originalBW = imread('text.png');
```

Create a flat, line-shaped structuring element.


```
se = strel('line',11,90);
```


Erode the image with the structuring element.

```
erodedBW = imerode(originalBW,se);
```

View the original image and the eroded image.

```
figure  
imshow(originalBW)  
figure  
imshow(erodedBW)
```





Erode Grayscale Image with Rolling Ball

Read grayscale image into the workspace.

```
originalI = imread('cameraman.tif');
```

Create a nonflat offsetstrel object.

```
se = offsetstrel('ball',5,5);
```

Erode the image.

```
erodedI = imerode(originalI,se);
```

Display original image and eroded image.

```
figure  
imshow(originalI)
```

```
figure  
imshow(erodedI)
```





Erode Binary Image on GPU

Read binary image into the workspace.

```
originalBW = imread('text.png');
```

Create a structuring element.

```
se = strel('line',11,90);  
erodedBW = imerode(gpuArray(originalBW),se);  
figure, imshow(originalBW), figure, imshow(erodedBW)
```

Erode the image, creating a GPUarray.

```
erodedBW = imerode(gpuArray(originalBW),se);
```

Display the original image and the eroded image.

```
figure, imshow(originalBW), figure, imshow(erodedBW)
```

Erode Grayscale Image on GPU

Read grayscale image into the workspace.

```
originalI = imread('cameraman.tif');
```

Create a structuring element.

```
se = strel('disk',5);
```

Erode the image, creating a GPUarray.

```
erodedI = imerode(gpuArray(originalI),se);
```

Display the original image and the eroded image.

```
figure
imshow(originalI)
figure
imshow(erodedI)
```

Erode MRI Stack Volume Using Cubic Structuring Element

Create a binary volume.

```
load mrystack
BW = mrystack < 100;
```

Create a cubic structuring element.

```
se = strel('cube',3)
```

```
se =
```

```
strel is a cube shaped structuring element with properties:
```

```
    Neighborhood: [3x3x3 logical]
    Dimensionality: 3
```

Erode the volume with a cubic structuring element.

```
erodedBW = imerode(BW, se);
```

Definitions

The *binary erosion* of A by B , denoted $A \ominus B$, is defined as the set operation $A \ominus B = \{z \mid (B_z \subseteq A)\}$. In other words, it is the set of pixel locations z , where the structuring element translated to location z overlaps only with foreground pixels in A .

In the general form of *gray-scale erosion*, the structuring element has a height. The gray-scale erosion of $A(x, y)$ by $B(x, y)$ is defined as:

$$(A \ominus B)(x, y) = \min \{A(x + x', y + y') - B(x', y') \mid (x', y') \in D_B\},$$

where D_B is the domain of the structuring element B and $A(x, y)$ is assumed to be $+\infty$ outside the domain of the image. To create a structuring element with nonzero height values, use the syntax `strel(nhood, height)`, where `height` gives the height values and `nhood` corresponds to the structuring element domain, D_B .

Most commonly, gray-scale erosion is performed with a flat structuring element ($B(x, y) = 0$). Gray-scale erosion using such a structuring element is equivalent to a local-minimum operator:

$$(A \ominus B)(x, y) = \min \{A(x + x', y + y') \mid (x', y') \in D_B\}.$$

All of the `strel` syntaxes except for `strel(nhood, height)`, `strel('arbitrary', nhood, height)`, and `strel('ball', ...)` produce flat structuring elements.

For more information on binary erosion, see [1].

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic `MATLAB Host Computer` target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can

be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, note the following:

- The input image, `IM`, must be 2-D or 3-D.
- The structuring element argument `SE` must be a single element—arrays of structuring elements are not supported. To obtain the same result as that obtained using an array of structuring elements, call the function sequentially.
- When the target is `MATLAB Host Computer`, the `PACKOPT` and `SHAPE` arguments must be compile-time constants. When the target is any other platform, the `PACKOPT` syntax is not supported.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

Algorithms

`imerode` automatically takes advantage of the decomposition of a structuring element object (if a decomposition exists). Also, when performing binary dilation with a structuring element object that has a decomposition, `imerode` automatically uses binary image packing to speed up the dilation.

Erosion using bit packing is described in [3].

References

- [1] Gonzalez, R. C., R. E. Woods, and S. L. Eddins, *Digital Image Processing Using MATLAB*, Gatesmark Publishing, 2009.
- [2] Haralick, Robert M., and Linda G. Shapiro, *Computer and Robot Vision*, Vol. I, Addison-Wesley, 1992, pp. 158-205.
- [3] van den Boomgard, R, and R. van Balen, "Methods for Fast Morphological Image Transforms Using Bitmapped Images," *Computer Vision, Graphics, and Image Processing: Graphical Models and Image Processing*, Vol. 54, Number 3, pp. 254-258, May 1992.

See Also

[bwpack](#) | [bwunpack](#) | [conv2](#) | [filter2](#) | [imclose](#) | [imdilate](#) | [imopen](#) | [strel](#) | [offsetstrel](#) | [gpuArray](#)

Introduced before R2006a

imextendedmax

Extended-maxima transform

Syntax

```
BW = imextendedmax(I,H)  
BW = imextendedmax(I,H,conn)
```

Description

`BW = imextendedmax(I,H)` returns the extended-maxima transform for `I`, which is the regional maxima of the `H`-maxima transform. Regional maxima are connected components of pixels with a constant intensity value, and whose external boundary pixels all have a lower value. `H` is a nonnegative scalar. By default, `imextendedmax` uses 8-connected neighborhoods for 2-D images and 26-connected neighborhoods for 3-D images. For higher dimensions, `imextendedmax` uses `conndef(numel(size(I)), 'maximal')`.

`BW = imextendedmax(I,H,conn)` computes the extended-maxima transform, where `conn` specifies the connectivity.

“Code Generation” on page 1-639 support: Yes.

“MATLAB Function Block” on page 1-640 support: Yes.

Examples

Perform Extended-Maxima transform

Read image into workspace.


```
I = imread('glass.png');
```

Calculate the extended-maxima transform.

```
BW = imextendedmax(I,80);
```

Display original image and transformed image side-by-side.

```
imshowpair(I,BW,'montage')
```



Input Arguments

I — Input image

real, nonsparse numeric array of any dimension

Input image, specified as a real, nonsparse numeric array of any dimension.

Example: `I = imread('glass.png');` `BW = imextendedmax(I,80);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

H — H-maxima transform

real, nonnegative scalar

H-maxima transform, specified as a real, nonnegative scalar.

Example: `BW = imextendedmax(I,80);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

conn — Connectivity

8 (default) | 4 | 6 | 18 | 26 | 3-by-3-by- ...-by-3 matrix of zeroes and ones

Connectivity, specified as a one of the scalar values in the following table. By default, `imextendedmax` uses 8-connected neighborhoods for 2-D images and 26-connected neighborhoods for 3-D images. For higher dimensions, `imextendedmax` uses `conndef(numel(size(I)), 'maximal')`. Connectivity can be defined in a more general way for any dimension by using for `conn` a 3-by-3-by-...-by-3 matrix of 0s and 1s. The 1-valued elements define neighborhood locations relative to the center element of `conn`. Note that `conn` must be symmetric around its center element.

Value	Meaning
Two-dimensional connectivities	
4	4-connected neighborhood
8	8-connected neighborhood
Three-dimensional connectivities	
6	6-connected neighborhood
18	18-connected neighborhood
26	26-connected neighborhood

Example: `BW = imextendedmax(I, 80, 4);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

Output Arguments

BW — Transformed image

logical array

Transformed image, returned as a logical array the same size as `I`.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic MATLAB Host Computer target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library

preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, the optional third input argument, `conn`, must be a compile-time constant.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

References

- [1] Soille, P., *Morphological Image Analysis: Principles and Applications*, Springer-Verlag, 1999, pp. 170-171.

See Also

`conndef` | `imextendedmin` | `imhmax` | `imreconstruct` | `imregionalmax`

Introduced before R2006a

imextendedmin

Extended-minima transform

Syntax

```
BW = imextendedmin(I,h)
BW = imextendedmin(I,h,conn)
```

Description

`BW = imextendedmin(I,h)` computes the extended-minima transform, which is the regional minima of the H-minima transform. Regional minima are connected components of pixels with a constant intensity value, and whose external boundary pixels all have a higher value. `h` is a nonnegative scalar. By default, `imextendedmin` uses 8-connected neighborhoods for 2-D images and 26-connected neighborhoods for 3-D images. For higher dimensions, `imextendedmin` uses `conndef(numel(size(I)), 'maximal')`.

`BW = imextendedmin(I,h,conn)` computes the extended-minima transform, which is the regional minima of the H-minima transform. `h` is a nonnegative scalar.

“Code Generation” on page 1-643 support: Yes.

“MATLAB Function Block” on page 1-644 support: Yes.

Examples

Perform Extended-Minima transform

Read image into the workspace.


```
I = imread('glass.png');
```

Calculate the extended-minima transform.

```
BW = imextendedmin(I,50);
```

Display the original image and the transformation side-by-side.

```
imshowpair(I,BW,'montage');
```



Input Arguments

I — Input image

nonsparse numeric array of any dimension

Input array, specified as a nonsparse numeric array of any dimension.

Example: `I = imread('glass.png');` `BW = imextendedmax(I,80);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

h — h-maxima transform

(default) | nonnegative scalar

h-maxima transform, specified as a nonnegative scalar.

Example: `BW = imextendedmin(I,80);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

conn — Connectivity

8 (default) | 4 | 6 | 18 | 26 | 3-by-3-by- ...-by-3 matrix of zeroes and ones

Connectivity, specified as a one of the scalar values in the following table. By default, `imextendedmin` uses 8-connected neighborhoods for 2-D images and 26-connected neighborhoods for 3-D images. For higher dimensions, `imextendedmin` uses `conndef(numel(size(I)), 'maximal')`. Connectivity can be defined in a more general way for any dimension by using for `conn` a 3-by-3-by- ...-by-3 matrix of 0s and 1s. The 1-valued elements define neighborhood locations relative to the center element of `conn`. Note that `conn` must be symmetric around its center element.

Value	Meaning
Two-dimensional connectivities	
4	4-connected neighborhood
8	8-connected neighborhood
Three-dimensional connectivities	
6	6-connected neighborhood
18	18-connected neighborhood
26	26-connected neighborhood

Example: `BW = imextendedmin(I,80,4);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

Output Arguments

BW — Transformed image

logical array

Transformed image, returned as a logical array the same size as `I`.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic MATLAB Host Computer target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library

preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, the optional third input argument, `conn`, must be a compile-time constant.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

References

- [1] Soille, P., *Morphological Image Analysis: Principles and Applications*, Springer-Verlag, 1999, pp. 170-171.

See Also

`conndef` | `imextendedmax` | `imhmin` | `imreconstruct` | `imregionalmin`

Introduced before R2006a

imfill

Fill image regions and holes

Syntax

```
BW2= imfill(BW,locations)
BW2= imfill(BW,'holes')
I2= imfill(I)

BW2 = imfill(BW)
BW2 = imfill(BW,0,conn)
[BW2,locations_out] = imfill(BW)

BW2= imfill(BW,locations,conn)
BW2= imfill(BW,conn,'holes')
I2= imfill(I,conn)

gpuarrayB = imfill(gpuarrayA, ___ )
```

Description

`BW2= imfill(BW,locations)` performs a flood-fill operation on background pixels of the input binary image `BW`, starting from the points specified in `locations`. If `locations` is a P -by-1 vector, it contains the linear indices of the starting locations. If `locations` is a P -by-`ndims(BW)` matrix, each row contains the array indices of one of the starting locations.

`BW2= imfill(BW,'holes')` fills holes in the input binary image `BW`. In this syntax, a hole is a set of background pixels that cannot be reached by filling in the background from the edge of the image.

`I2= imfill(I)` fills holes in the grayscale image `I`. In this syntax, a hole is defined as an area of dark pixels surrounded by lighter pixels.

`BW2 = imfill(BW)` displays the binary image `BW` on the screen and lets you define the region to fill by selecting points interactively with the mouse. To use this syntax, `BW` must

be a 2-D image. Press **Backspace** or **Delete** to remove the previously selected point. Shift-click, right-click, or double-click to select a final point and start the fill operation. Press **Return** to finish the selection without adding a point.

`BW2 = imfill(BW,0,conn)` lets you override the default connectivity as you interactively specify locations.

`[BW2,locations_out] = imfill(BW)` returns the locations of points selected interactively in `locations_out`. The return value `locations_out` is a vector of linear indices into the input image. To use this syntax, `BW` must be a 2-D image.

`BW2= imfill(BW,locations,conn)` fills the area defined by `locations`, where `conn` specifies the connectivity.

`BW2= imfill(BW,conn, 'holes ')` fills holes in the binary image `BW`, where `conn` specifies the connectivity.

`I2= imfill(I,conn)` fills holes in the grayscale image `I`, where `conn` specifies the connectivity.

`gpuarrayB = imfill(gpuarrayA, ___)` performs the fill operation on a GPU. The input image and the return image are 2-D `gpuArrays`. Use of this syntax requires Parallel Computing Toolbox. When run on a GPU, `imfill` does not support interactive syntaxes, where you select locations using the mouse.

“Code Generation” on page 1-655 support: Yes.

“MATLAB Function Block” on page 1-656 support: Yes.

Examples

Fill Image from Specified Starting Point

```
BW1 = logical([1 0 0 0 0 0 0 0
               1 1 1 1 1 0 0 0
               1 0 0 0 1 0 1 0
               1 0 0 0 1 1 1 0
               1 1 1 1 0 1 1 1
               1 0 0 1 1 0 1 0
               1 0 0 0 1 0 1 0])
```

```
        1 0 0 0 1 1 1 0]);  
BW2 = imfill(BW1,[3 3],8)  
  
BW2 =  
  
     1     0     0     0     0     0     0     0  
     1     1     1     1     1     0     0     0  
     1     1     1     1     1     0     1     0  
     1     1     1     1     1     1     1     0  
     1     1     1     1     1     1     1     1  
     1     0     0     1     1     1     1     0  
     1     0     0     0     1     1     1     0  
     1     0     0     0     1     1     1     0
```

Fill Holes in a Binary Image

Read image into workspace.

```
I = imread('coins.png');  
figure  
imshow(I)  
title('Original Image')
```


Original Image



Convert image to binary image.

```
BW = imbinarize(I);  
figure  
imshow(BW)  
title('Original Image Converted to Binary Image')
```


Original Image Converted to Binary Image



Fill holes in the binary image and display the result.

```
BW2 = imfill(BW, 'holes');  
figure  
imshow(BW2)  
title('Filled Image')
```


Filled Image



Fill Holes in a Grayscale Image

```
I = imread('tire.tif');  
I2 = imfill(I);  
figure, imshow(I), figure, imshow(I2)
```



Fill Operation on a GPU

Create a simple sample binary image.

```
BW1 = logical([1 0 0 0 0 0 0 0  
              1 1 1 1 1 0 0 0  
              1 0 0 0 1 0 1 0  
              1 0 0 0 1 1 1 0  
              1 1 1 1 0 1 1 1  
              1 0 0 1 1 0 1 0  
              1 0 0 0 1 0 1 0  
              1 0 0 0 1 1 1 0])
```

BW1 =

```
1 0 0 0 0 0 0 0  
1 1 1 1 1 0 0 0  
1 0 0 0 1 0 1 0  
1 0 0 0 1 1 1 0  
1 1 1 1 0 1 1 1  
1 0 0 1 1 0 1 0  
1 0 0 0 1 0 1 0  
1 0 0 0 1 1 1 0
```

```

1   0   0   0   1   1   1   0

```

Create a `gpuArray`.

```
BW1 = gpuArray(BW1);
```

Fill in the background of the image from a specified starting location.

```
BW2 = imfill(BW1,[3 3],8)
```

BW2 =

```

1   0   0   0   0   0   0   0
1   1   1   1   1   0   0   0
1   1   1   1   1   0   1   0
1   1   1   1   1   1   1   0
1   1   1   1   1   1   1   1
1   0   0   1   1   1   1   0
1   0   0   0   1   1   1   0
1   0   0   0   1   1   1   0

```

Input Arguments

BW — Input binary image

real, nonsparse, numeric or logical array

Input binary image, specified as a real, nonsparse, numeric or logical array of any dimension.

Example: `BW = imread('text.png');`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

locations — Linear indices identifying pixel locations

2-D, real, numeric vector or matrix of positive integers

Linear indices identifying pixel locations, specified as a 2-D, real, numeric vector or matrix of positive integers.

Example: `BW2 = imfill(BW,[3 3],8);`

Data Types: `double`

I — Input grayscale image

real, nonsparse numeric array

Input grayscale image, specified as a real, nonsparse, numeric array of any dimension.

Example: `I = imread('cameraman.tif');``I2 = imfill(I);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

conn — Connectivity

4 (default) | 8 | 6 | 18 | 26 | 3-by-3-by- ...-by-3 matrix of zeroes and ones

Connectivity, specified as a one of the scalar values in the following table. By default, `imfill` uses 4-connected neighborhoods for 2-D images and 6-connected neighborhoods for 3-D inputs. For higher dimensions, `imfill` uses `conndef(ndims(I), 'minimal')`. Connectivity can be defined in a more general way for any dimension by using for `conn` a 3-by-3-by- ...-by-3 matrix of 0s and 1s. The 1-valued elements define neighborhood locations relative to the center element of `conn`. Note that `conn` must be symmetric around its center element.

Value	Meaning
Two-dimensional connectivities	
4	4-connected neighborhood
8	8-connected neighborhood
Three-dimensional connectivities	
6	6-connected neighborhood
18	18-connected neighborhood
26	26-connected neighborhood

Example:

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

gpuarrayA — Input image

`gpuArray`

Input image, specified as a `gpuArray`.

Output Arguments

BW2 — Filled image

logical array

Filled image, returned as an array the same class as the input image.

locations_out — Linear indices of pixel locations

numeric vector or matrix

Linear indices of pixel locations, returned as a numeric vector or matrix.

I2 — Filled grayscale image

numeric array

Filled grayscale image, returned as a numeric array.

gpuarrayB — Output image

gpuArray

Output image, returned as a gpuArray.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, note the following:

- The optional input arguments, **conn** and **'holes'** must be a compile-time constants.
- **imfill** supports up to 3-D inputs only. (No N-D support.)
- The interactive syntax to select points, **imfill(BW,0,CONN)** is not supported.

- With the `locations` input argument, once you select a format at compile time, you cannot change it at run time. However, the number of points in `locations` can be varied at run time.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

Algorithms

`imfill` uses an algorithm based on morphological reconstruction [1].

References

- [1] Soille, P., *Morphological Image Analysis: Principles and Applications*, Springer-Verlag, 1999, pp. 173-174.

See Also

`bwselect` | `conndef` | `imreconstruct` | `regionfill`

Introduced before R2006a

imfilter

N-D filtering of multidimensional images

Syntax

```
B = imfilter(A,h)
gpuarrayB = imfilter(gpuArrayA,h)
___ = imfilter( ___,options,...)
```

Description

`B = imfilter(A,h)` filters the multidimensional array `A` with the multidimensional filter `h`. The array `A` can be **logical** or a nonsparse numeric array of any class and dimension. The result `B` has the same size and class as `A`.

`imfilter` computes each element of the output, `B`, using double-precision floating point. If `A` is an integer or logical array, `imfilter` truncates output elements that exceed the range of the given type, and rounds fractional values.

`gpuarrayB = imfilter(gpuArrayA,h)` performs the operation on a GPU. `gpuArrayA` is a `gpuArray` that contains a **logical** or a nonsparse numeric array of any class and dimension. When used with a `gpuArray`, `H` must be a vector or 2-D matrix. This syntax requires the Parallel Computing Toolbox.

`___ = imfilter(___,options,...)` performs multidimensional filtering according to the specified options.

“Code Generation” on page 1-665 support: Yes.

“MATLAB Function Block” on page 1-665 support: Yes.

Examples

Create Filter and Apply It

Read a color image into the workspace and display it.

```
originalRGB = imread('peppers.png');  
imshow(originalRGB)
```



Create a motion-blur filter using the `fspecial` function.

```
h = fspecial('motion', 50, 45);
```

Apply the filter to the original image to create an image with motion blur. Note that `imfilter` is more memory efficient than some other filtering functions in that it outputs an array of the same data type as the input image array. In this example, the output is an array of `uint8`.

```
filteredRGB = imfilter(originalRGB, h);
```



```
figure, imshow(filteredRGB)
```



Filter the image again, this time specifying the replicate boundary option.

```
boundaryReplicateRGB = imfilter(originalRGB, h, 'replicate');  
figure, imshow(boundaryReplicateRGB)
```



Create a Filter and Apply it on a GPU

Read a color image into the workspace as a `gpuArray` and view it.

```
originalRGB = gpuArray(imread('peppers.png'));  
imshow(originalRGB)
```



Original Image

Create a filter, `h`, that can be used to approximate linear camera motion.

```
h = fspecial('motion', 50, 45);
```

Apply the filter, using `imfilter`, to the image `originalRGB` to create a new image, `filteredRGB`. The image is returned as a `gpuArray`.

```
filteredRGB = imfilter(originalRGB, h);  
figure, imshow(filteredRGB)
```



Filtered Image

Note that `imfilter` is more memory efficient than some other filtering operations in that it outputs an array of the same data type as the input image array. In this example, the output is an array of `uint8`.

`whos`

Name	Size	Bytes	Class	Attributes
<code>filteredRGB</code>	384x512x3	108	<code>gpuArray</code>	
<code>h</code>	37x37	10952	<code>double</code>	
<code>originalRGB</code>	384x512x3	108	<code>gpuArray</code>	

Try the filtering operation again, this time specifying the `replicate` boundary option.

```
boundaryReplicateRGB = imfilter(originalRGB, h, 'replicate');  
figure, imshow(boundaryReplicateRGB)
```




Image with Replicate Boundary

Input Arguments

A — Image to be filtered

nonsparse, numeric array of any class and dimension

Image to be filtered, specified as a nonsparse, numeric array of any class and dimension

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

h — Multidimensional filter

N-D array of doubles

Multidimensional filter, specified as an N-D array of doubles.

Data Types: `double`

gpuArrayA — Image to be filtered

gpuArray object

Image to be filtered, specified as a `gpuArray` object. When used with a `gpuArray`, `imfilter` computes `gpuarrayB`, using either single- or double-precision floating point,

depending on the data type of `gpuArrayA`. When `gpuArrayA` contains double-precision or `uint32` values, `imfilter` uses double-precision values. For all other data types, `imfilter` uses single-precision. If `gpuarrayA` is an integer or logical array, `imfilter` truncates output elements that exceed the range of the given type, and rounds off fractional values.

options — Options that control the filtering operation

character string | numeric value

Options that control the filtering operation, specified as a character string or numeric value. The following table lists all supported options.

Boundary Options

Option	Description
Boundary Options	
X	Input array values outside the bounds of the array are implicitly assumed to have the value X. When no boundary option is specified, the default is 0.
'symmetric'	Input array values outside the bounds of the array are computed by mirror-reflecting the array across the array border.
'replicate'	Input array values outside the bounds of the array are assumed to equal the nearest array border value.
'circular'	Input array values outside the bounds of the array are computed by implicitly assuming the input array is periodic.
Output Size	
'same'	The output array is the same size as the input array. This is the default behavior when no output size options are specified.
'full'	The output array is the full filtered result, and so is larger than the input array.
Correlation and Convolution Options	
'corr'	<code>imfilter</code> performs multidimensional filtering using correlation, which is the same way that <code>filter2</code> performs filtering. When no correlation or convolution option is specified, <code>imfilter</code> uses correlation.
'conv'	<code>imfilter</code> performs multidimensional filtering using convolution.

Output Arguments

B — Filtered image

numeric array the same size and class as input image

Filtered image, returned as an array the same size and class as the input image.

gpuarrayB — Filtered image

gpuArray

Filtered image, returned as a gpuArray, the same size and class as gpuarrayA

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, the input image, **A**, must be 2-D or 3-D. The value of the input argument, **options**, must be a compile-time constant.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

Tips

- This function may take advantage of hardware optimization for data types `uint8`, `uint16`, `int16`, `single`, and `double` to run faster.

See Also

`conv2` | `convn` | `filter2` | `fspecial` | `gpuArray`

Introduced before R2006a

imfindcircles

Find circles using circular Hough transform

Syntax

```
centers = imfindcircles(A,radius)
[centers,radii] = imfindcircles(A,radiusRange)
[centers,radii,metric] = imfindcircles(A,radiusRange)
[centers,radii,metric] = imfindcircles( ____,Name,Value)
```

Description

`centers = imfindcircles(A,radius)` finds the circles in image `A` whose radii are approximately equal to `radius`. The output, `centers`, is a two-column matrix containing the x,y coordinates of the circles centers in the image.

`[centers,radii] = imfindcircles(A,radiusRange)` finds circles with radii in the range specified by `radiusRange`. The additional output argument, `radii`, contains the estimated radii corresponding to each circle center in `centers`.

`[centers,radii,metric] = imfindcircles(A,radiusRange)` also returns a column vector, `metric`, containing the magnitudes of the accumulator array peaks for each circle (in descending order). The rows of `centers` and `radii` correspond to the rows of `metric`.

`[centers,radii,metric] = imfindcircles(____,Name,Value)` specifies additional options with one or more `Name,Value` pair arguments, using any of the previous syntaxes.

“Code Generation” on page 1-1204 support: Yes.

MATLAB Function Block support: No.

Examples

Detection of Five Strongest Circles in an Image

Read the image into the workspace and display it.

```
A = imread('coins.png');  
imshow(A)
```



Find all the circles with radius r such that $15 \leq r \leq 30$.


```
[centers, radii, metric] = imfindcircles(A,[15 30]);
```

Retain the five strongest circles according to the metric values.

```
centersStrong5 = centers(1:5,:);  
radiiStrong5 = radii(1:5);  
metricStrong5 = metric(1:5);
```

Draw the five strongest circle perimeters.


```
viscircles(centersStrong5, radiiStrong5, 'EdgeColor', 'b');
```



Detection of Bright and Dark Circles in an Image

Read the image into the workspace and display it.

```
A = imread('circlesBrightDark.png');  
imshow(A)
```



Define the radius range.

```
Rmin = 30;  
Rmax = 65;
```

Find all the bright circles in the image within the radius range.


```
[centersBright, radiiBright] = imfindcircles(A,[Rmin Rmax], 'ObjectPolarity', 'bright');
```

Find all the dark circles in the image within the radius range.

```
[centersDark, radiiDark] = imfindcircles(A,[Rmin Rmax], 'ObjectPolarity', 'dark');
```


Plot bright circles in blue.

```
viscircles(centersBright, radiiBright, 'EdgeColor', 'b');
```



Plot dark circles in dashed red boundaries.

```
viscircles(centersDark, radiiDark, 'LineStyle', '--');
```



Input Arguments

A — Input image

grayscale image | truecolor image | binary image

Input image is the image in which to detect circular objects, specified as a grayscale, truecolor, or binary image.

Data Types: `single` | `double` | `int16` | `uint8` | `uint16` | `logical`

radius — Circle radius

scalar numeric

Circle radius is the approximate radius of the circular objects you want to detect, specified as a scalar of any numeric type.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

radiusRange — Range of radii

two-element vector of integers

Range of radii for the circular objects you want to detect, specified as a two-element vector, [`rmin` `rmax`], of integers of any numeric type.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

Name-Value Pair Arguments

Specify optional comma-separated pairs of **Name**, **Value** arguments. **Name** is the argument name and **Value** is the corresponding value. **Name** must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

Example: `'ObjectPolarity', 'bright'` specifies bright circular objects on a dark background.

'ObjectPolarity' — Object polarity

`'bright'` (default) | `'dark'`

Object polarity indicates whether the circular objects are brighter or darker than the background, specified as the comma-separated pair consisting of `'ObjectPolarity'` and either of the text strings in the following table.

<code>'bright'</code>	The circular objects are brighter than the background.
<code>'dark'</code>	The circular objects are darker than the background.

Example: `'ObjectPolarity', 'bright'` specifies bright circular objects on a dark background.

'Method' — Computation method

`'PhaseCode'` (default) | `'TwoStage'`

Computation method is the technique used to compute the accumulator array, specified as the comma-separated pair consisting of `'Method'` and either of the text strings in the following table.

'PhaseCode'	Atherton and Kerbyson's [1] phase coding method . This is the default.
'TwoStage'	The method used in two-stage circular Hough transform [2], [3].

Example: 'Method', 'PhaseCode' specifies the Atherton and Kerbyson's phase coding method.

'Sensitivity' — Sensitivity factor

0.85 (default) | nonnegative scalar between 0 and 1

Sensitivity factor is the sensitivity for the circular Hough transform accumulator array, specified as the comma-separated pair consisting of 'Sensitivity' and a nonnegative scalar value in the range [0, 1]. As you increase the sensitivity factor, `imfindcircles` detects more circular objects, including weak and partially obscured circles. Higher sensitivity values also increase the risk of false detection.

Example: 'Sensitivity', 0.3 sets the sensitivity factor to 0.3.

'EdgeThreshold' — Edge gradient threshold

nonnegative scalar between 0 and 1

Edge gradient threshold sets the gradient threshold for determining edge pixels in the image, specified as the comma-separated pair consisting of 'EdgeThreshold' and a nonnegative scalar value in the range [0, 1]. Specify 0 to set the threshold to zero-gradient magnitude. Specify 1 to set the threshold to the maximum gradient magnitude. `imfindcircles` detects more circular objects (with both weak and strong edges) when you set the threshold to a lower value. It detects fewer circles with weak edges as you increase the value of the threshold. By default, `imfindcircles` chooses the edge gradient threshold automatically using the function `graythresh`.

Example: 'EdgeThreshold', 0.5 sets the edge gradient threshold to 0.5.

Output Arguments

centers — Coordinates of circle centers

two-column matrix

Coordinates of the circle centers, returned as a P-by-2 matrix containing the x -coordinates of the circle centers in the first column and the y -coordinates in the second

column. The number of rows, P , is the number of circles detected. `centers` is sorted based on the strength of the circles.

radii — Estimated radii

column vector

The estimated radii for the circle centers, returned as a column vector. The radius value at `radii(j)` corresponds to the circle centered at `centers(j,:)`.

metric — Circle strengths

column vector

Circle strengths is the relative strengths for the circle centers, returned as a vector. The value at `metric(j)` corresponds to the circle with radius `radii(j)` centered at `centers(j,:)`.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic `MATLAB Host Computer` target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, all string input parameters and values must be a compile-time constant.

Tips

- Specify a relatively small `radiusRange` for better accuracy. A good rule of thumb is to choose `radiusRange` such that $r_{\max} < 3 \cdot r_{\min}$ and $(r_{\max} - r_{\min}) < 100$.
- The accuracy of `imfindcircles` is limited when the value of `radius` (or `rmin`) is less than 10.
- The radius estimation step is typically faster if you use the (default) `'PhaseCode'` method instead of `'TwoStage'`.

- Both computation methods, 'PhaseCode' and 'TwoStage' are limited in their ability to detect concentric circles. The results for concentric circles can vary depending on the input image.
- `imfindcircles` does not find circles with centers outside the domain of the image.
- `imfindcircles` preprocesses binary (logical) images to improve the accuracy of the result. It converts truecolor images to grayscale using the function `rgb2gray` before processing them.

Algorithms

Function `imfindcircles` uses a Circular Hough Transform (CHT) based algorithm for finding circles in images. This approach is used because of its robustness in the presence of noise, occlusion and varying illumination.

The CHT is not a rigorously specified algorithm, rather there are a number of different approaches that can be taken in its implementation. However, by and large, there are three essential steps which are common to all.

1 Accumulator Array Computation.

Foreground pixels of high gradient are designated as being candidate pixels and are allowed to cast 'votes' in the accumulator array. In a classical CHT implementation, the candidate pixels vote in pattern around them that forms a full circle of a fixed radius. Figure 1a shows an example of a candidate pixel lying on an actual circle (solid circle) and the classical CHT voting pattern (dashed circles) for the candidate pixel.




Figure 1: classical CHT voting pattern

2 Center Estimation

The votes of candidate pixels belonging to an image circle tend to accumulate at the accumulator array bin corresponding to the circle's center. Therefore, the circle centers are estimated by detecting the peaks in the accumulator array. Figure 1b shows an example of the candidate pixels (solid dots) lying on an actual circle (solid circle), and their voting patterns (dashed circles) which coincide at the center of the actual circle.

3 Radius Estimation

If the same accumulator array is used for more than one radius value, as is commonly done in CHT algorithms, radii of the detected circles have to be estimated as a separate step.

Function `imfindcircles` provides two algorithms for finding circles in images: Phase-Coding (default) and Two-Stage. Both share some common computational steps, but each has its own unique aspects as well.

The common computational features shared by both algorithms are as follow:

- Use of 2-D Accumulator Array:

The classical Hough Transform requires a 3-D array for storing votes for multiple radii, which results in large storage requirements and long processing times. Both the Phase-Coding and Two-Stage methods solve this problem by using a single 2-D accumulator array for all the radii. Although this approach requires an additional step of radius estimation, the overall computational load is typically lower, especially when working over large radius range. This is a widely adopted practice in modern CHT implementations.

- Use of Edge Pixels

Overall memory requirements and speed is strongly governed by the number of candidate pixels. To limit their number, the gradient magnitude of the input image is threshold so that only pixels of high gradient are included in tallying votes.

- Use of Edge Orientation Information:

Another way to optimize performance is to restrict the number of bins available to candidate pixels. This is accomplished by utilizing locally available edge information to only permit voting in a limited interval along direction of the gradient (Figure 2).




Figure 2: Voting mode: multiple radii, along direction of the gradient

r_{\min}	Minimum search radius
r_{\max}	Maximum search radius
r_{actual}	Radius of the circle that the candidate pixel belongs to
c_{\min}	Center of the circle of radius r_{\min}
c_{\max}	Center of the circle of radius r_{\max}
c_{actual}	Center of the circle of radius r_{actual}

The two CHT methods employed by function `imfindcircles` fundamentally differ in the manner by which the circle radii are computed.

- Two-Stage

Radii are explicitly estimated utilizing the estimated circle centers along with image information. The technique is based on computing radial histograms; see references 1 & 2 for a detailed explanation.

- Phase-Coding

The key idea in Phase Coding is the use of complex values in the accumulator array with the radius information encoded in the phase of the array entries. The votes cast by the edge pixels contain information not only about the possible center locations but also about the radius of the circle associated with the center location. Unlike the Two-Stage method where radius has to be estimated explicitly using radial histograms, in Phase Coding the radius can be estimated by simply decoding the phase information from the estimated center location in the accumulator array. (see reference 3).

References

- [1] T.J Atherton, D.J. Kerbyson. "Size invariant circle detection." *Image and Vision Computing*. Volume 17, Number 11, 1999, pp. 795-803.
- [2] H.K Yuen, .J. Princen, J. Illingworth, and J. Kittler. "Comparative study of Hough transform methods for circle finding." *Image and Vision Computing*. Volume 8, Number 1, 1990, pp. 71–77.
- [3] E.R. Davies, *Machine Vision: Theory, Algorithms, Practicalities*. Chapter 10. 3rd Edition. Morgan Kauffman Publishers, 2005,

See Also

[hough](#) | [houghlines](#) | [houghpeaks](#) | [viscircles](#)

Introduced in R2012a

imfreehand

Create draggable freehand region

Syntax

```
h = imfreehand
h = imfreehand(hparent)
h = imfreehand(...,param1, val1,...)
```

Description

`h = imfreehand` begins interactive placement of a freehand region of interest on the current axes. The function returns `h`, a handle to an `imfreehand` object. A freehand region of interest can be dragged interactively using the mouse and supports a context menu that controls aspects of its appearance and behavior. See “Interactive Behavior” on page 1-681.


`h = imfreehand(hparent)` begins interactive placement of a freehand region of interest on the object specified by `hparent`. `hparent` specifies the HG parent of the freehand region graphics, which is typically an axes, but can also be any other object that can be the parent of an `hggroup`.


`h = imfreehand(...,param1, val1,...)` creates a freehand ROI, specifying parameters and corresponding values that control the behavior of the tool. The following table lists the parameters available. Parameter names can be abbreviated, and case does not matter.

Parameter	Description
'Closed'	Scalar logical that controls whether the freehand region is closed. When set to <code>true</code> (the default), <code>imfreehand</code> draws a straight line to connect the endpoints of the freehand line to create a closed region. If set to <code>false</code> , <code>imfreehand</code> leaves the region open.
'PositionConstraintFcn'	Function handle specifying the function that is called whenever the freehand region is dragged using the


Parameter	Description
	mouse. Use this parameter to control where the freehand region can be dragged. See the help for the setPositionConstraintFcn method for information about valid function handles.

Interactive Behavior

When you call `imfreehand` with an interactive syntax, the pointer changes to a cross hairs  when positioned over an image. Click and drag the mouse to draw the freehand region. By default, `imfreehand` draws a straight line connecting the last point you drew with the first point, but you can control this behavior using the 'Closed' parameter. The following figure illustrates a freehand region with its context menu.



The following table lists the interactive features supported by `imfreehand`.

Interactive Behavior	Description
Moving the region.	Move the pointer inside the freehand region. The pointer changes to a fleur shape  . Click and hold the left mouse button to move the region.
Changing the color used to draw the region.	Move the pointer inside the freehand region. Right-click and select Set Color from the context menu.
Retrieving the current position of the freehand region.	Move the pointer inside the freehand region. Right-click and select Copy Position from the context menu. <code>imfreehand</code> copies an <i>n</i> -by-2 array of coordinates on the boundary of the ROI to the clipboard.
Deleting the region	Move the pointer inside the region. Right-click and select Delete from the context menu. To remove this option from the context menu, set the <code>Deletable</code> property to false: <code>h = imfreehand(); h.Deletable = false;</code>

Methods

The `imfreehand` object supports the following methods. Type methods `imfreehand` to see a complete list of all methods.

addNewPositionCallback — Add new-position callback to ROI object

See `imroi` for information.

createMask — Create mask within image

See `imroi` for information.

delete — Delete ROI object

See `imroi` for information.

getColor — Get color used to draw ROI object

See `imroi` for information.

getPosition — Return current position of freehand region

`pos = getPosition(h)` returns the current position of the freehand region `h`. The returned position, `pos`, is an *N*-by-2 array `[X1 Y1; ...; XN YN]`.

getPositionConstraintFcn — Return function handle to current position constraint function

See `imroi` for information.

removeNewPositionCallback — Remove new-position callback from ROI object.

See `imroi` for information.

resume — Resume execution of MATLAB command line

See `imroi` for information.

setClosed — Set geometry of freehand region

`setClosed(h,TF)` sets the geometry of the freehand region `h`. `TF` is a logical scalar. `True` means that the freehand region is closed. `False` means that the freehand region is open.

setColor — Set color used to draw ROI object

See `imroi` for information.

setConstrainedPosition — Set ROI object to new position

See `imroi` for information.

setPositionConstraintFcn — Set position constraint function of ROI object.

See `imroi` for information.

wait — Block MATLAB command line until ROI creation is finished

See `imroi` for information.

Examples

Interactively place a closed freehand region of interest by clicking and dragging over an image.

```
figure, imshow('pout.tif');  
h = imfreehand(gca);
```

Interactively place a freehand region by clicking and dragging. Use the `wait` method to block the MATLAB command line. Double-click on the freehand region to resume execution of the MATLAB command line.

```
figure, imshow('pout.tif');  
h = imfreehand;  
position = wait(h);
```

More About

Tips

If you use `imfreehand` with an axes that contains an image object, and do not specify a position constraint function, users can drag the freehand region outside the extent of the image and lose the freehand region. When used with an axes created by the `plot` function, the axes limits automatically expand to accommodate the movement of the freehand region.

See Also

`imellipse` | `impoly` | `imrect` | `imline` | `impoint` | `iptgetapi` | `makeConstrainToRectFcn`

Introduced in R2007b

imfuse

Composite of two images

Syntax

```
C = imfuse(A,B)
[C RC] = imfuse(A,RA,B,RB)
C = imfuse( ____,method)
C = imfuse( ____,Name,Value)
```

Description

`C = imfuse(A,B)` creates a composite image from two images, `A` and `B`. If `A` and `B` are different sizes, `imfuse` pads the smaller dimensions with zeros so that both images are the same size before creating the composite. The output, `C`, is a numeric matrix containing a fused version of images `A` and `B`.

`[C RC] = imfuse(A,RA,B,RB)` creates a composite image from two images, `A` and `B`, using the spatial referencing information provided in `RA` and `RB`. The output `RC` defines the spatial referencing information for the output fused image `C`.

`C = imfuse(____,method)` uses the algorithm specified by `method`.

`C = imfuse(____,Name,Value)` specifies additional options with one or more `Name,Value` pair arguments, using any of the previous syntaxes.

Examples

Create Overlay Image of Two Images

Load an image into the workspace. Create a copy and apply a rotation offset.

```
A = imread('cameraman.tif');
B = imrotate(A,5,'bicubic','crop');
```

Create blended overlay image, scaling the intensities of A and B jointly as a single data set.

```
C = imfuse(A,B,'blend','Scaling','joint');
```

Save the resulting image as a .png file and view the fused image.

```
imwrite(C,'my_blend_overlay.png');  
imshow(C);
```



Create Overlay Image Using Color to Distinguish the Areas of Similar Intensity.

Load an image into the workspace. Create a copy and apply a rotation offset.

```
A = imread('cameraman.tif');  
B = imrotate(A,5,'bicubic','crop');
```

Create blended overlay image, using red for one image, green for image B, and yellow for areas of similar intensity between the two images.

```
C = imfuse(A,B,'falsecolor','Scaling','joint','ColorChannels',[1 2 0]);
```

Save the resulting image as a .png file and view the fused image.

```
imwrite(C,'my_blend_red-green.png');  
imshow(C)
```



Create Fused Image of Two Spatially Referenced Images

Load an image into the workspace and create a spatial referencing object associated with it.

```
A = dicomread('knee1.dcm');  
RA = imref2d(size(A));
```

Create a second image by resizing image A and create a spatial referencing object associated with that image.

```
B = imresize(A,2);  
RB = imref2d(size(B));
```


Set referencing object parameters to specify the limits of the coordinates in world coordinates.

```
RB.XWorldLimits = RA.XWorldLimits;  
RB.YWorldLimits = RA.YWorldLimits;
```

Create a blended overlay image and view it, using color to indicate areas of similar intensity. This example uses red for image A, green for image B, and yellow for areas of similar intensity between the two images. Note how the images do not appear to share any areas of similar intensity.


```
C = imfuse(A,B,'falsecolor','Scaling','joint','ColorChannels',[1 2 0]);
```

`imshow(C)`



Create a new fused image, this time using the spatial referencing information in RA and RB, and view it. In this version, the image appears yellow, because the images A and B have the same extent in the world coordinate system. The images actually are aligned, even though B is twice the size of A.

```
[C,RC] = imfuse(A,RA,B,RB,'ColorChannels',[1 2 0]);
```



grayscale image | truecolor image | binary image

Image to be combined into a composite image, specified as a grayscale, truecolor, or binary image.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

B — Image to be combined into a composite image

grayscale image | truecolor image | binary image

Image to be combined into a composite image, specified as a grayscale, truecolor, or binary image.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

RA — Spatial referencing information associated with the input image A

spatial referencing object

Spatial referencing information associated with the input image A, specified as a spatial referencing object of class `imref2d`.

RB — Spatial referencing information associated with the input image B

spatial referencing object

Spatial referencing information associated with the input image B, specified as a spatial referencing object of class `imref2d`.

method — Algorithm used to combine images

'falsecolor' (default) | 'blend' | 'diff' | 'montage'

Algorithm used to combine images, specified as one of the text strings in the following table.

Method	Description
'falsecolor'	Creates a composite RGB image showing A and B overlaid in different color bands. Gray regions in the composite image show where the two images have the same intensities. Magenta and green regions show where the intensities are different. This is the default method.
'blend'	Overlays A and B using alpha blending.
'diff'	Creates a difference image from A and B.
'montage'	Puts A and B next to each other in the same image.

Example: `C = imfuse(A,B, 'montage')` places A and B next to each other in the output image.

Name-Value Pair Arguments

Specify optional comma-separated pairs of **Name**, **Value** arguments. **Name** is the argument name and **Value** is the corresponding value. **Name** must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

Example: `'Scaling', 'joint'` scales the intensity values of A and B together as a single data set.

'Scaling' — Intensity scaling option

`'independent'` (default) | `'joint'` | `'none'`

Intensity scaling option, specified as one of the following character strings:

<code>'independent'</code>	Scales the intensity values of A and B independently when C is created.
<code>'joint'</code>	Scales the intensity values in the images jointly as if they were together in the same image. This option is useful when you want to visualize registrations of monomodal images, where one image contains fill values that are outside the dynamic range of the other image.
<code>'none'</code>	No additional scaling.

'ColorChannels' — Output color channel for each input image

`'green-magenta'` (default) | `[R G B]` | `'red-cyan'`

Output color channel for each input image, specified as one of the following character strings:

<code>[R G B]</code>	A three element vector that specifies which image to assign to the red, green, and blue channels. The R, G, and B values must be 1 (for the first input image), 2 (for the second input image), and 0 (for neither image).
<code>'red-cyan'</code>	A shortcut for the vector <code>[1 2 2]</code> , which is suitable for red/cyan stereo anaglyphs

'green-magenta'

A shortcut for the vector [2 1 2], which is a high contrast option, ideal for people with many kinds of color blindness

Output Arguments

C — Fused image that is a composite of the input images

grayscale image | truecolor image | binary image

Fused image that is a composite of the input images, returned as a grayscale, truecolor, or binary image.

Data Types: `uint8`

RC — Spatial referencing information associated with the output image

spatial referencing object

Spatial referencing information, returned as a spatial referencing object.

More About

Tips

- Use `imfuse` to create composite visualizations that you can save to a file. Use `imshowpair` to display composite visualizations to the screen.

See Also

`imregister` | `imshowpair` | `imtransform`

Introduced in R2012a

imgaborfilt

Apply Gabor filter or set of filters to 2-D image

Syntax

```
[mag,phase] = imgaborfilt(A,wavelength,orientation)
[mag,phase] = imgaborfilt(A,gaborbank)
[mag,phase] = imgaborfilt(A,wavelength,orientation,name,value,...)
```

Description

`[mag,phase] = imgaborfilt(A,wavelength,orientation)` computes the magnitude and phase response of a Gabor filter for the input grayscale image `A`. `wavelength` describes the wavelength in pixels/cycle of the sinusoidal carrier. `orientation` is the orientation of the filter in degrees. The output `mag` and `phase` are the magnitude and phase responses of the Gabor filter.

`[mag,phase] = imgaborfilt(A,gaborbank)` applies the array of Gabor filters, `gaborbank`, to the input image `A`. `gaborbank` is a 1-by- P array of Gabor objects, called a *filter bank*. `mag` and `phase` are image stacks where each plane in the stack corresponds to one of the outputs of the filter bank. For inputs of size `A`, the outputs `mag` and `phase` contain the magnitude and phase response for each filter in `gaborbank` and are of size M -by- N -by- P . Each plane in the magnitude and phase responses, `mag(:,:,ind)`, `phase(:,:,ind)`, is the result of applying the Gabor filter of the same index, `gaborBank(ind)`.

`[mag,phase] = imgaborfilt(A,wavelength,orientation,name,value,...)` applies a single Gabor filter using name-value pairs to control various aspects of filtering.

“Code Generation” on page 1-700 support: Yes.

MATLAB Function Block support: No.

Examples

Apply Single Gabor Filter to Input Image

Read image into the workspace.

```
I = imread('board.tif');
```

Convert image to grayscale.


```
I = rgb2gray(I);
```

Apply Gabor filter to image.

```
wavelength = 4;  
orientation = 90;  
[mag,phase] = imgaborfilt(I,wavelength,orientation);
```

Display original image with plots of the magnitude and phase calculated by the Gabor filter.

```
figure  
subplot(1,3,1);  
imshow(I);  
title('Original Image');  
subplot(1,3,2);  
imshow(mag,[])  
title('Gabor magnitude');  
subplot(1,3,3);  
imshow(phase,[]);  
title('Gabor phase');
```



Apply Array of Gabor Filters to Input Image

Read image into the workspace.

```
I = imread('cameraman.tif');
```

Create array of Gabor filters, called a *filter bank*. This filter bank contains two orientations and two wavelengths.

```
gaborArray = gabor([4 8],[0 90]);
```

Apply filters to input image.

```
gaborMag = imgaborfilt(I,gaborArray);
```


Display results. The figure shows the magnitude response for each filter.

```
figure
subplot(2,2,1);
for p = 1:4
    subplot(2,2,p)
    imshow(gaborMag(:,:,p),[]);
    theta = gaborArray(p).Orientation;
    lambda = gaborArray(p).Wavelength;
    title(sprintf('Orientation=%d, Wavelength=%d',theta,lambda));
end
```


Orientation=0, Wavelength=4




Orientation=0, Wavelength=8



Orientation=90, Wavelength=4



Orientation=90, Wavelength=8



Input Arguments

A — **Input grayscale image**
real, nonsparse 2-D matrix

Input grayscale image, specified as a real, nonsparse 2-D matrix.

If the image contains `Infs` or `NaNs`, the behavior of `imgaborfilt` is undefined because Gabor filtering is performed in the frequency domain.

For all input data types other than `single`, `imgaborfilt` performs the computation in `double`. Input images of type `single` are filtered in type `single`. Performance

optimizations may result from casting the input image to `single` prior to calling `imgaborfilt`.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

wavelength — Wavelength of the sinusoidal carrier

numeric scalar in the range `[2, Inf)`

Wavelength of the sinusoidal carrier, specified as a numeric scalar in the range `[2, Inf)`, in pixels/cycle.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

orientation — Orientation of filter in degrees

numeric scalar in the range `[0 360]`

Orientation of filter in degrees, specified as a numeric scalar in the range `[0 360]`, where the orientation is defined as the normal direction to the sinusoidal plane wave.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

gaborbank — Array of Gabor filters

`gabor` object

Array of Gabor filters, specified as a `gabor` object. You must use the `gabor` function to create an array of Gabor filters.

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

Example: `[mag, phase] = imgaborfilt(I, 4, 90, 'SpatialFrequencyBandwidth', 2);`

'SpatialFrequencyBandwidth' — Spatial frequency bandwidth

1.0 (default) | numeric scalar

Spatial frequency bandwidth, specified as a numeric scalar in units of octaves. The spatial frequency bandwidth determines the cutoff of the filter response as frequency content in the input image varies from the preferred frequency, $1/\lambda$. Typical values for spatial-frequency bandwidth are in the range [0.5 2.5].

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

'SpatialAspectRatio' — Ratio of semi-major and semi-minor axes of Gaussian envelope
0.5 (default) | numeric scalar

Ratio of semi-major and semi-minor axes of Gaussian envelope (semi-minor/semi-major), specified as a numeric scalar. This parameter controls the ellipticity of the Gaussian envelope. Typical values for spatial aspect ratio are in the range [0.23 0.92].

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

Output Arguments

mag — Magnitude response for the Gabor filter
numeric array of class `double`

Magnitude response for the Gabor filter, returned as a numeric array of class `double`.

phase — Phase response for the Gabor filter
numeric array of class `double`

Phase response for the Gabor filter, returned as a numeric array of class `double`.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, note the following:

- The filter bank syntax is not supported.

See Also

gabor

Introduced in R2015b

imgaussfilt

2-D Gaussian filtering of images

Syntax

```
B = imgaussfilt(A)
B = imgaussfilt(A,sigma)
B = imgaussfilt(___,Name,Value,...)
gpuarrayB = imgaussfilt(gpuarrayA, ___)
```

Description

`B = imgaussfilt(A)` filters image `A` with a 2-D Gaussian smoothing kernel with standard deviation of 0.5. Returns `B`, the filtered image.

`B = imgaussfilt(A,sigma)` filters image `A` with a 2-D Gaussian smoothing kernel with standard deviation specified by `sigma`.

`B = imgaussfilt(___,Name,Value,...)` filters image `A` with Name-Value pairs used to control aspects of the filtering.

`gpuarrayB = imgaussfilt(gpuarrayA, ___)` performs the filtering operation on a GPU. The input image must be a `gpuArray`. The function returns a `gpuArray`. This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-706 support: Yes.

“MATLAB Function Block” on page 1-706 support: Yes.

Examples

Smooth image with Gaussian filter

Read image to be filtered.

```
I = imread('cameraman.tif');
```

Filter the image with a Gaussian filter with standard deviation of 2.

```
Iblur = imgaussfilt(I, 2);
```

Display all results for comparison.

```
subplot(1,2,1)
imshow(I)
title('Original Image');
subplot(1,2,2)
imshow(Iblur)
title('Gaussian filtered image, \sigma = 2')
```

Original Image



Gaussian filtered image, $\sigma = 2$



Smooth Image with Gaussian Filter on a GPU

This example shows how to perform a Gaussian smoothing operation on a GPU.

Read image to be filtered into a `gpuArray`.

```
I = gpuArray(imread('cameraman.tif'));
```

Perform Gaussian smoothing.

```
Iblur = imgaussfilt(I, 2);
```

Display all the results for comparison.

```
subplot(1,2,1), imshow(I), title('Original Image');
```

```
subplot(1,2,2), imshow(Iblur)  
title('Gaussian filtered image, \sigma = 2')
```

Input Arguments

A — Image to be filtered

real, nonsparse matrix of any dimension

Image to be filtered, specified as a real, nonsparse matrix of any dimension.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

sigma — Standard deviation of the Gaussian distribution

0.5 (default) | scalar or 2-element vector of positive values

Standard deviation of the Gaussian distribution, specified as a scalar or 2-element vector of positive values. If you specify a scalar, the Gaussian kernel is square.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

gpuarrayA — Input image for GPU

`gpuArray`

Input image for GPU, specified as a `gpuArray`.

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single

quotes (' '). You can specify several name and value pair arguments in any order as Name1,Value1,...,NameN,ValueN.

Example: `B = imgaussfilt(A,'FilterSize',3);`

'FilterSize' — Size of the Gaussian filter

`2*ceil(2*SIGMA)+1` (default) | scalar or 2-element vector of positive, odd integers

Size of the Gaussian filter, specified as a scalar or 2-element vector of positive, odd integers. If you specify a scalar, the filter is a square.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

'Padding' — Type of padding to be used on image before filtering

'replicate' (default) | numeric scalar | 'circular' | 'symmetric'

Padding to be used on image before filtering, specified as a string or numeric scalar. If you specify a scalar (X), input image values outside the bounds of the image are implicitly assumed to have the value X. You can also specify any of the following strings:

String	Description
'circular'	Pad with circular repetition of elements within the dimension.
'replicate'	Pad by repeating border elements of array.
'symmetric'	Pad image with mirror reflections of itself.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical` | `char`

'FilterDomain' — Domain in which to perform filtering

'auto' (default) | 'spatial' | 'frequency'

Domain in which to perform filtering, specified as one of the following strings:

String	Description
'auto'	Perform convolution in the spatial or frequency domain, based on internal heuristics.
'frequency'	Perform convolution in the frequency domain.
'spatial'	Perform convolution in the spatial domain.

Data Types: char

Output Arguments

B — Filtered image

real, nonsparse matrix

Filtered image, returned as a real, nonsparse matrix, the same size and class as the input image.

gpuarrayB — Filtered image

gpuArray

Filtered image, returned as a gpuArray.

More About

Code Generation

If you set the `FilterDomain` parameter to `'frequency'`, this function supports the generation of C code using MATLAB Coder. If you set the `FilterDomain` parameter to `'spatial'` and you choose the generic MATLAB Host Computer target platform, generated code uses a precompiled, platform-specific shared library. For more information, see “Code Generation for Image Processing”.

When generating code, all string input arguments must be compile-time constants.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

Tips

- If image `A` contains `Infs` or `NaNs`, the behavior of `imgaussfilt` for frequency domain filtering is undefined. This can happen if you set the `'FilterDomain'` parameter to `'frequency'` or if you set it to `'auto'` and `imgaussfilt` uses frequency domain filtering. To restrict the propagation of `Infs` and `NaNs` in the output in a manner similar to `imfilter`, consider setting the `'FilterDomain'` parameter to `'spatial'`.

- When you set the `'FilterDomain'` parameter to `'auto'`, `imgaussfilt` uses an internal heuristic to determine whether spatial or frequency domain filtering is faster. This heuristic is machine dependent and may vary for different configurations. For optimal performance, try both options, `'spatial'` and `'frequency'`, to determine the best filtering domain for your image and kernel size.
- If you do not specify the `'Padding'` parameter, `imgaussfilt` uses `'replicate'` padding by default, which is different from the default used by `imfilter`.

See Also

`fspecial` | `imfilter` | `imgaussfilt3`

Introduced in R2015a

imgaussfilt3

3-D Gaussian filtering of 3-D images

Syntax

```
B = imgaussfilt3(A)
B = imgaussfilt3(A,sigma)
B = imgaussfilt3( ___,Name,Value,...)
gpuarrayB= imgaussfilt3(gpuarrayA, ___)
```

Description

`B = imgaussfilt3(A)` filters 3-D image `A` with a 3-D Gaussian smoothing kernel with standard deviation of 0.5.

`B = imgaussfilt3(A,sigma)` filters 3-D image `A` with a 3-D Gaussian smoothing kernel with standard deviation specified by `sigma`.

`B = imgaussfilt3(___,Name,Value,...)` filters 3-D image `A` with a 3-D Gaussian smoothing kernel with Name-Value pairs used to control aspects of the filtering.

`gpuarrayB= imgaussfilt3(gpuarrayA, ___)` performs the filtering operation on a GPU. The input image must be a `gpuArray`. The function returns a `gpuArray`. This syntax requires Parallel Computing Toolbox.


Examples

Smooth MRI volume with 3-D Gaussian filter

Load MRI data and display it.

```
vol = load('mri');
figure
montage(vol.D)
title('Original image volume')
```

Original image volume




Smooth the image with a 3-D Gaussian filter.

```
siz = vol.siz;  
vol = squeeze(vol.D);  
sigma = 2;
```

```
volSmooth = imgaussfilt3(vol, sigma);
```

```
figure  
montage(reshape(volSmooth,siz(1),siz(2),1,siz(3)))
```

```
title('Gaussian filtered image volume')
```



Smooth MRI Volume with 3-D Gaussian Filter on a GPU

This example shows how to perform a 3-D Gaussian smoothing operation on a GPU.

Load MRI data to be filtered.

```
vol = load('mri');  
figure, montage(vol.D), title('Original image volume')
```

Create a `gpuArray` containing the volume data and perform Gaussian smoothing.

```
siz = vol.siz;
vol = gpuArray(squeeze(vol.D));
sigma = 2;

volSmooth = imgaussfilt3(vol, sigma);
```

Collect the smoothed data from the GPU (using the `gather` function) and display all the results for comparison.

```
figure, montage(reshape(gather(volSmooth),siz(1),siz(2),1,siz(3)))
title('Gaussian filtered image volume')
```

Input Arguments

A — Image to be filtered

3-D, real, nonsparse array

Image to be filtered, specified as a 3-D, real, nonsparse array.

Example: `volSmooth = imgaussfilt3(vol,2);`

Data Types: `single` | `double` | `int8` | `uint8` | `int16` | `uint16` | `int32` | `uint32`

sigma — Standard deviation of the Gaussian distribution

0.5 (default) | numeric, real, positive scalar or a 3-element vector

Standard deviation of the Gaussian distribution, specified as a numeric, real, positive scalar or a 3-element vector. If `sigma` is a scalar, `imgaussfilt3` uses a cubic Gaussian kernel.

Example: `volSmooth = imgaussfilt3(vol, 2);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

gpuarrayA — Input image for GPU

`gpuArray`

Input image for GPU, specified as a `gpuArray`.

Example: `gpuarrayA = gpuArray(imread('cameraman.tif')); gpuarrayB = imgaussfilt3(gpuarrayA);`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (`' '`). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

Example: `Smooth = imgaussfilt3(vol, sigma, 'padding', 'circular');`

'FilterSize' — Size of the Gaussian filter

`2*ceil(2*sigma)+1` (default) | real, positive, odd, integer scalar or 3-element vector

Size of the Gaussian filter, specified as a scalar or 3-element vector of real, positive, odd, integers. If you specify a scalar `Q`, `imgaussfilt3` uses a cubic Gaussian filter of size `[Q Q Q]`.

Example: `volSmooth = imgaussfilt3(vol, sigma, 'FilterSize', 5);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

'Padding' — Type of padding to be used on image before filtering

`'replicate'` (default) | `'circular'` | `'symmetric'` | real, numeric, or logical scalar

Type of padding to be used on image before filtering, specified as one of the strings in the following table or a numeric scalar. If you specify a scalar, `imgaussfilt3` uses that value for input image pixels that fall outside the bounds of the image.

Padding Type String	Description
<code>'circular'</code>	Pad with circular repetition of elements within the dimension.
<code>'replicate'</code>	Pad by repeating border elements of array.
<code>'symmetric'</code>	Pad array with mirror reflections of itself.

Example: `volSmooth = imgaussfilt3(vol, sigma, 'padding', 'circular');`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical` | `char`

'FilterDomain' — Domain in which to perform filtering

`'auto'` (default) | `'frequency'` | `'spatial'`

Domain in which to perform filtering, specified as one of the following strings.

Filter Domain String	Description
'auto'	Perform convolution in the spatial or frequency domain, based on internal heuristics.
'frequency'	Perform convolution in the frequency domain.
'spatial'	Perform convolution in the spatial domain.

Example: `Smooth = imgaussfilt3(vol,sigma,'FilterDomain','frequency');`

Data Types: char

Output Arguments

B — Filtered image

numeric array

Filtered image, returned as a numeric array, the same class and size as input image.

gpuarrayB — Filtered image

gpuArray

Filtered image, returned as a gpuArray.

More About

Tips

- If image **A** contains `Inf`s or `NaN`s, the behavior of `imgaussfilt3` for frequency domain filtering is undefined. This can happen if you set the `'FilterDomain'` parameter to `'frequency'` or if you set it to `'auto'` and `imgaussfilt3` uses frequency domain filtering. To restrict the propagation of `Inf`s and `NaN`s in the output in a manner similar to `imfilter`, consider setting the `'FilterDomain'` parameter to `'spatial'`.
- When you set the `'FilterDomain'` parameter to `'auto'`, `imgaussfilt3` uses an internal heuristic to determine whether spatial or frequency domain filtering is faster. This heuristic is machine-dependent and may vary for different configurations. For

optimal performance, try both options, 'spatial' and 'frequency', to determine the best filtering domain for your image and kernel size.

- If you do not specify the 'Padding' parameter, `imgaussfilt3` uses 'replicate' padding by default, which is different from the default used by `imfilter`.

See Also

`imfilter` | `imgaussfilt`

Introduced in R2015a

imgca

Get handle to current axes containing image

Syntax

```
h = imgca
h = imgca(hfig)
```

Description

`h = imgca` returns the handle of the current axes that contains an image. The current axes can be in a regular figure window or in an Image Tool window.

If no figure contains an axes that contains an image, `imgca` creates a new axes.

`h = imgca(hfig)` returns the handle to the current axes that contains an image in the specified figure. (It need not be the current figure.)

Note

`imgca` can be useful in returning the handle to the Image Tool axes. Because the Image Tool turns graphics object handle visibility off, you cannot retrieve a handle to the tool figure using `gca`.

Examples


Compute the centroid of each coin, and superimpose its location on the image. View the results using `imtool` and `imgca`:

```
I = imread('coins.png');
figure, imshow(I)
```



Original Image

```
bw = im2bw(I, graythresh(getimage));  
figure, imshow(bw)
```




Binary Image

```
bw2 = imfill(bw, 'holes');  
s = regionprops(bw2, 'centroid');  
centroids = cat(1, s.Centroid);
```

Display original image I and superimpose centroids:

```
imshow(I)  
hold(imgca, 'on')  
plot(imgca, centroids(:,1), centroids(:,2), 'r*')  
hold(imgca, 'off')
```



Centroids of Coins

See also

`gca`, `gcf`, `imgcf`, `imhandles`

Introduced before R2006a

imgcf

Get handle to current figure containing image

Syntax

```
hfig = imgcf
```

Description

`hfig = imgcf` returns the handle of the current figure that contains an image. The figure may be a regular figure window that contains at least one image or an Image Tool window.

If none of the figures currently open contains an image, `imgcf` creates a new figure.

Note

`imgcf` can be useful in getting the handle to the Image Tool figure window. Because the Image Tool turns graphics object handle visibility off, you cannot retrieve a handle to the tool figure using `gcf`.

Examples

```
imtool rice.png  
cmap = copper(256);  
set(imgcf, 'Colormap', cmap)
```

See also

`gca`, `gcf`, `imgca`, `imhandles`

Introduced before R2006a

imgetfile

Open Image dialog box

Syntax

```
[filename, user_canceled] = imgetfile
```

Description

`[filename, user_canceled] = imgetfile` displays the Open Image dialog box. You can use this dialog box in imaging applications to get the name of the image file a user wants to open. The Open Image dialog box includes only files using supported image file formats (listed in `imformats`) and DICOM files. When the user selects a file and clicks **Open**, `imgetfile` returns the full path of the file in the return value `filename` and sets the `user_canceled` return value to `FALSE`. If the user clicks **Cancel**, `imgetfile` returns an empty string in `filename` and sets the `user_canceled` return value to `TRUE`.

Note: The Open Image dialog box is modal; it blocks the MATLAB command line until the user responds.

See Also

`imformats` | `imtool` | `uigetfile`

Introduced before R2006a

imgradient

Gradient magnitude and direction of an image

Syntax

```
[Gmag,Gdir] = imgradient(I)
[Gmag,Gdir] = imgradient(I,method)
[gpuarrayGmag,gpuarrayGdir] = imgradient(gpuarrayI, ___ )
[Gmag,Gdir] = imgradient(GxGy)
[gpuarrayGmag,gpuarrayGdir] = imgradient(gpuarrayGx,gpuarrayGy)
```

Description

`[Gmag,Gdir] = imgradient(I)` returns the gradient magnitude, `Gmag`, and the gradient direction, `Gdir`, for the grayscale or binary image `I`.

`[Gmag,Gdir] = imgradient(I,method)` returns the gradient magnitude and direction using specified `method`.

`[gpuarrayGmag,gpuarrayGdir] = imgradient(gpuarrayI, ___)` performs the operation on a GPU. The input image and the return values are `gpuArrays`. This syntax requires the Parallel Computing Toolbox.

`[Gmag,Gdir] = imgradient(GxGy)` returns the gradient magnitude and direction using directional gradients along the x -axis, `Gx`, and the y -axis, `Gy`, such as that returned by `imgradientxy`. The x -axis points in the direction of increasing column subscripts and the y -axis points in the direction of increasing row subscripts.

`[gpuarrayGmag,gpuarrayGdir] = imgradient(gpuarrayGx,gpuarrayGy)` performs the operation on a GPU. The input x and y gradients and the return values are `gpuArrays`. This syntax requires the Parallel Computing Toolbox.

Examples

Calculate Gradient Magnitude and Gradient Direction

Read image into workspace.

```

I = imread('coins.png');


Calculate gradients and display.

[Gmag, Gdir] = imgradient(I,'prewitt');

figure; imshowpair(Gmag, Gdir, 'montage');
title('Gradient Magnitude, Gmag (left), and Gradient Direction, Gdir (right), using Prewitt method');
axis off;

```

Gradient Magnitude, Gmag (left), and Gradient Direction, Gdir (right), using Prewitt method



Calculate gradient magnitude and gradient direction on a GPU

Read image and compute gradient magnitude and gradient direction using Prewitt's gradient operator.

Read image.

```

I = gpuArray(imread('coins.png'));
imshow(I)

```

Calculate gradients and display.

```

[Gmag, Gdir] = imgradient(I,'prewitt');

```

```
figure, imshow(Gmag, []), title('Gradient magnitude')  
figure, imshow(Gdir, []), title('Gradient direction')
```

Calculate Directional Gradients

Read image into workspace.


```
I = imread('coins.png');
```


Calculate gradients and display them.

```
[Gx, Gy] = imgradientxy(I);  
[Gmag, Gdir] = imgradient(Gx, Gy);
```

```
figure, imshow(Gmag, []), title('Gradient magnitude')  
figure, imshow(Gdir, []), title('Gradient direction')  
title('Gradient Magnitude and Gradient Direction')  
figure; imshowpair(Gx, Gy, 'montage'); axis off;  
title('Directional Gradients, Gx and Gy')
```

Gradient magnitude



Gradient Magnitude and Gradient Direction



Calculate directional gradients in addition to gradient magnitude and direction on a GPU

Read image and return directional gradients, G_x and G_y , as well as gradient magnitude and direction, G_{mag} and G_{dir} , utilizing default Sobel gradient operator.

Read image.

```
I = gpuArray(imread('coins.png'))
```

Calculate gradients and display them. Note that when you specify a `gpuArray` to `imgradientxy`, it returns G_x and G_y as `gpuArrays`. The results are the same as the previous example.

```
[Gx, Gy] = imgradientxy(I);  
[Gmag, Gdir] = imgradient(Gx, Gy);  
  
figure, imshow(Gmag, []), title('Gradient magnitude')  
figure, imshow(Gdir, []), title('Gradient direction')  
figure, imshow(Gx, []), title('Directional gradient: X axis')
```

```
figure, imshow(Gy, []), title('Directional gradient: Y axis')
```

Input Arguments

I — Input image

grayscale image | binary image

Input image, specified as a grayscale or binary image, that is, a numeric or logical 2-D matrix that must be nonsparse.

Data Types: single | double | int8 | int32 | uint8 | uint16 | uint32 | logical

gpuarrayI — Input image

gpuArray

Input image, specified as a 2-D grayscale or binary gpuArray image.

Data Types: single | double | int8 | int32 | uint8 | uint16 | uint32 | logical

method — Gradient operator

'sobel' (default) | 'prewitt' | 'central' | 'intermediate' | 'roberts'

Gradient operator, specified as one of the text strings in the following table.

Method	Description
'sobel'	Sobel gradient operator (default)
'prewitt'	Prewitt gradient operator
'central',	Central difference gradient: $dI/dx = (I(x+1) - I(x-1))/2$
'intermediate'	Intermediate difference gradient: $dI/dx = I(x+1) - I(x)$
'roberts'	Roberts gradient operator

Data Types: char

Gx — Directional gradients along x-axis (horizontal)

matrix

Directional gradient along x-axis (horizontal), specified as non-sparse matrix equal in size to image I, typically returned by `imgradientxy`.

Data Types: `single` | `double` | `int8` | `int32` | `uint8` | `uint16` | `uint32`

Gy — Directional gradients along the *y*-axis (vertical)

`matrix`

Directional gradient along *y*-axis (vertical), specified as non-sparse matrix equal in size to image **I**, typically returned by `imgradientxy`.

Data Types: `single` | `double` | `int8` | `int32` | `uint8` | `uint16` | `uint32`

gpuarrayGx — Directional gradients along *x*-axis

`gpuArray`

Directional gradient along *x*-axis, specified as a `gpuArray`, typically returned by `imgradientxy`.

Data Types: `single` | `double` | `int8` | `int32` | `uint8` | `uint16` | `uint32`

gpuarrayGy — Directional gradients along the *y*-axis

`gpuArray`

Directional gradient along *y*-axis, specified as a `gpuArray`, typically returned by `imgradientxy`.

Data Types: `single` | `double` | `int8` | `int32` | `uint8` | `uint16` | `uint32`

Output Arguments

Gmag — Gradient magnitude

`matrix`

Gradient magnitude, returned as a non-sparse matrix the same size as image **I**. **Gmag** is of class `double`, unless the input image **I** is of class `single`, in which case it is of class `single`.

Data Types: `double` | `single`

gpuarrayGmag — Gradient magnitude

`gpuArray`

Gradient magnitude, returned as a non-sparse `gpuArray` the same size as image **I**. **Gmag** is of class `double`, unless the input image **I** is of class `single`, in which case it is of class `single`.

Data Types: `double` | `single`

Gdir — Gradient direction

`matrix` | `gpuArray`

Gradient direction, returned as a nonsparse matrix the same size as image `I`. `Gdir` contains angles in degrees within the range `[-180 180]` measured counterclockwise from the positive x -axis. (The x -axis points in the direction of increasing column subscripts.) `Gdir` is of class `double`, unless the input image `I` is of class `single`, in which case it is of class `single`.

When `I` or `Gx` and `Gy` are `gpuArrays`, `Gdir` is a `gpuArray`.

Data Types: `double` | `single`

gpuarrayGdir — Gradient direction

`gpuArray`

Gradient direction, returned as a nonsparse `gpuArray` the same size as image `I`. `Gdir` contains angles in degrees within the range `[-180 180]` measured counterclockwise from the positive x -axis. (The x -axis points in the direction of increasing column subscripts.) `Gdir` is of class `double`, unless the input image `I` is of class `single`, in which case it is of class `single`.

Data Types: `double` | `single`

More About

Tips

- When applying the gradient operator at the boundaries of the image, values outside the bounds of the image are assumed to equal the nearest image border value. This is similar to the `'replicate'` boundary option in `imfilter`.

Algorithms

The algorithmic approach taken in `imgradient` for each of the listed gradient methods is to first compute directional gradients, `Gx` and `Gy`, with respect to the x -axis and y -axis. The x -axis is defined along the columns going right and the y -axis is defined along the rows going down. The gradient magnitude and direction are then computed from their orthogonal components `Gx` and `Gy`.

See Also

`edge` | `fspecial` | `gpuArray` | `gpuArray` | `imgradient3` | `imgradientxy` | `imgradientxyz`

Introduced in R2012b

imgradient3

Find 3-D gradient magnitude and direction of images

Syntax

```
[Gmag,Gazimuth,Gelevation] = imgradient3(I)
[Gmag,Gazimuth,Gelevation] = imgradient3(I,method)
[Gmag,Gazimuth,Gelevation] = imgradient3(Gx,Gy,Gz)
```

Description

`[Gmag,Gazimuth,Gelevation] = imgradient3(I)` returns the gradient magnitude, `Gmag`, gradient direction, `Gazimuth`, and gradient elevation `Gelevation` for the grayscale or binary 3-D image `I`.

`[Gmag,Gazimuth,Gelevation] = imgradient3(I,method)` calculates the gradient magnitude and direction using the specified `method`.

`[Gmag,Gazimuth,Gelevation] = imgradient3(Gx,Gy,Gz)` calculates the gradient magnitude and direction from the directional gradients along the *X*-axis, `Gx`, *Y*-axis, `Gy` and *Z*-axis, `Gz`.

“Code Generation” on page 1-735 support: Yes.

“MATLAB Function Block” on page 1-735 support: Yes.

Examples

Compute 3-D Gradient Magnitude and Direction Using Sobel Method

Read 3-D data into the workspace and prepare it for processing.

```
volData = load('mri');
sz = volData.size;
```

```
vol = squeeze(volData.D);
```


Calculate the gradients.

```
[Gmag, Gaz, Gelev] = imgradient3(vol);
```

Visualize the gradient magnitude as a montage.

```
figure,  
montage(reshape(Gmag,sz(1),sz(2),1,sz(3)), 'DisplayRange', [])  
title('Gradient magnitude')
```


Gradient magnitude



Input Arguments

I — Input image

nonsparse, numeric or logical, 3-D matrix

Input image, specified as a nonsparse, numeric or logical, 3-D matrix

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

method — Gradient operator

`'sobel'` (default) | `'prewitt'` | `'central'` | `'intermediate'`

Gradient operator, specified as one of the text strings in the following table.

Value	Meaning
<code>'sobel'</code>	Sobel gradient operator (default)
<code>'prewitt'</code>	Prewitt gradient operator
<code>'central'</code>	Central difference gradient. $dI/dx = (I(x+1) - I(x-1)) / 2$
<code>'intermedia</code>	Intermediate difference gradient. $dI/dx = I(x+1) - I(x)$

When applying the gradient operator at the boundaries of the image, `imgradient3` assumes values outside the bounds of the image equal the nearest image border value. This behavior is similar to the `'replicate'` boundary option in `imfilter`.

Data Types: `char`

Gx — Directional gradients along x-axis (horizontal)

nonsparse, numeric or logical, 3-D matrix

Directional gradient along *x*-axis (horizontal), specified as a nonsparse, numeric or logical, 3-D matrix. The *X*-axis points in the direction of increasing column subscripts. The matrix must be equal in size to `Gy` and `Gz`. `imgradientxyz` returns `Gx`.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

Gy — Directional gradients along the y-axis (vertical)

nonsparse, numeric or logical, 3-D matrix

Directional gradient along *y*-axis (vertical), specified as a nonsparse, numeric or logical, 3-D matrix. The *Y*-axis points in the direction of increasing row subscripts. The matrix must be equal in size to `Gx` and `Gz`. `imgradientxyz` returns `Gy`.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

Gz — Directional gradients along the z-axis

nonsparse, numeric or logical, 3-D matrix

Directional gradient along z -axis, specified as a nonsparse, numeric or logical, 3-D matrix. The matrix must be equal in size to G_x and G_y . `imgradientxyz` returns G_z .

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

Output Arguments

Gmag — Magnitude of the gradient vector

nonsparse matrix

Magnitude of the gradient vector, returned as a nonsparse matrix the same size as image I .


G_{mag} is of class `double`, unless the input image I or any of the directional gradients G_x , G_y , or G_z are of class `single`. In this case, G_{mag} is of class `single`.

Gazimuth — Azimuthal angle

nonsparse matrix

Azimuthal angle, returned as a nonsparse matrix the same size as image I . $G_{azimuth}$ contains angles in degrees within the range $[-180\ 180]$ measured between positive X -axis and the projection of the point on the X - Y plane.

$G_{azimuth}$ is of class `double`, unless the input image I or any of the directional gradients G_x , G_y , or G_z are of class `single`. In this case, $G_{azimuth}$ is of class `single`.



Gazimuth and Gelevation

Gelevation — Gradient elevation

nonsparse matrix

Gradient elevation, returned as a nonsparse matrix the same size as image I. Gelevation contains angles in degrees within the range $[-90\ 90]$ measured between the Z-axis and the radial line.

`Gelevation` is of class `double`, unless the input image `I` or any of the directional gradients `Gx`, `Gy`, or `Gz` are of class `single`. In this case, `Gelevation` is of class `single`.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, the input argument `method` must be a compile-time constant.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`imgradient` | `imgradientxy` | `imgradientxyz`

Introduced in R2016a

imgradientxy

Directional gradients of an image

Syntax

```
[Gx,Gy] = imgradientxy(I)
[Gx,Gy] = imgradientxy(I,method)
[gpuarrayGx,gpuarrayGy] = imgradientxy(gpuarrayI, ___)
```

Description

`[Gx,Gy] = imgradientxy(I)` returns the directional gradients, `Gx` and `Gy`, the same size as the input image `I`.

When applying the gradient operator at the boundaries of the image, values outside the bounds of the image are assumed to equal the nearest image border value.

`[Gx,Gy] = imgradientxy(I,method)` returns the directional gradients using the specified `method`.

`[gpuarrayGx,gpuarrayGy] = imgradientxy(gpuarrayI, ___)` performs the operation on a GPU. The input image and the return values are `gpuArrays`. This syntax requires the Parallel Computing Toolbox

Examples

Calculate Directional Gradients

Read image into workspace.


```
I = imread('coins.png');
```

Calculate gradient magnitude and gradient direction using Prewitt gradient operator.

```
[Gx, Gy] = imgradientxy(I,'prewitt');
```

```
figure; imshowpair(Gx, Gy, 'montage');
title('Directional Gradients: x-direction, Gx (left), y-direction, Gy (right), using Prewitt method');
axis off;
```

Directional Gradients: x-direction, Gx (left), y-direction, Gy (right), using Prewitt method



Calculate directional gradients on a GPU

Read image into a gpuArray.

```
I = gpuArray(imread('coins.png'));
imshow(I)
```

Calculate gradient magnitude and gradient direction using Prewitt's gradient operator and display images.

```
[Gx, Gy] = imgradientxy(I, 'prewitt');

figure, imshow(Gx, []), title('Directional gradient: X axis')
figure, imshow(Gy, []), title('Directional gradient: Y axis')
```

Calculate Directional Gradients and Then Magnitude and Direction


Read image into workspace.


```
I = imread('coins.png');
```

Calculate x and y directional gradients and then gradient magnitude and direction.

```
[Gx, Gy] = imgradientxy(I);  
[Gmag, Gdir] = imgradient(Gx, Gy);  
figure; imshowpair(Gmag, Gdir, 'montage'); axis off;  
title('Gradient Magnitude, Gmag (left), and Gradient Direction, Gdir (right), using Sobel method');  
figure; imshowpair(Gx, Gy, 'montage'); axis off;  
title('Directional Gradients, Gx and Gy, using Sobel method');
```

Gradient Magnitude, Gmag (left), and Gradient Direction, Gdir (right), using Sobel method



Directional Gradients, Gx and Gy, using Sobel method**Calculate gradient magnitude and direction in addition to directional gradients on a GPU**

Read image and return directional gradients, G_x and G_y , as well as gradient magnitude and direction, G_{mag} and G_{dir} , utilizing default Sobel gradient operator.

Read image into a `gpuArray`.

```
I = gpuArray(imread('coins.png'));  
imshow(I)
```

Calculate gradient and display images.

```
[Gx, Gy] = imgradientxy(I);  
[Gmag, Gdir] = imgradient(Gx, Gy);  
  
figure, imshow(Gmag, []), title('Gradient magnitude')  
figure, imshow(Gdir, []), title('Gradient direction')  
figure, imshow(Gx, []), title('Directional gradient: X axis')
```

```
figure, imshow(Gy, []), title('Directional gradient: Y axis')
```

Input Arguments

I — Input image

grayscale image | binary image

Input image, specified as a grayscale or binary image, that is, a numeric or logical 2-D matrix that must be nonsparse, or a `gpuArray`.

Data Types: `single` | `double` | `int8` | `int32` | `uint8` | `uint16` | `uint32` | `logical`

gpuarrayI — Input image

`gpuArray`

Input image, specified as a 2-D grayscale or binary `gpuArray` image.

Data Types: `single` | `double` | `int8` | `int32` | `uint8` | `uint16` | `uint32` | `logical`

method — Gradient operator

'sobel' (default) | 'prewitt' | 'central' | 'intermediate'

Gradient operator, specified as one of the text strings in the following table.

Method	Description
'sobel'	Sobel gradient operator (default)
'prewitt'	Prewitt gradient operator
'central',	Central difference gradient: $dI/dx = (I(x+1) - I(x-1))/2$
'intermediate'	Intermediate difference gradient: $dI/dx = I(x+1) - I(x)$

Data Types: `char`

Output Arguments

Gx — Directional gradients along x-axis

matrix

Directional gradient along the x -axis, returned as non-sparse matrix equal in size to image **I**. The x -axis points in the direction of increasing column subscripts. The output matrices are of class **double**, unless the input image is of class **single**, in which case they are of class **single**.

When the input image **I** is a **gpuArray**, **Gx** is a **gpuArray**.

Data Types: **single** | **double**

gpuarrayGx — Directional gradients along x -axis

gpuArray

Directional gradient along the x -axis, returned as non-sparse **gpuArray** equal in size to image **I**. The x -axis points in the direction of increasing column subscripts. The output matrices are of class **double**, unless the input image is of class **single**, in which case they are of class **single**.

Data Types: **single** | **double**

Gy — Directional gradient along y -axis

matrix

Directional gradients along the y -axis, returned as non-sparse matrix equal in size to image **I**. The y -axis points in the direction of increasing row subscripts. The output matrices are of class **double**, unless the input image is of class **single**, in which case they are of class **single**.

Data Types: **single** | **double**

gpuarrayGy — Directional gradient along y -axis

gpuArray

Directional gradients along the y -axis, returned as non-sparse **gpuArray** equal in size to image **I**. The y -axis points in the direction of increasing row subscripts. The output matrices are of class **double**, unless the input image is of class **single**, in which case they are of class **single**.

Data Types: **single** | **double**

More About

Tips

- When applying the gradient operator at the boundaries of the image, values outside the bounds of the image are assumed to equal the nearest image border value.

Algorithms

The algorithmic approach is to compute directional gradients with respect to the x -axis and y -axis. The x -axis is defined along the columns going right and the y -axis is defined along the rows going down.

See Also

`edge` | `fspecial` | `gpuArray` | `imgradient` | `imgradient3` | `imgradientxyz`

Introduced in R2012b

imgradientxyz

Find the directional gradients of a 3-D image

Syntax

```
[Gx,Gy,Gz] = imgradientxyz(I)  
[Gx,Gy,Gz] = imgradientxyz(I,method)
```

Description

`[Gx,Gy,Gz] = imgradientxyz(I)` returns the gradient along the *X*-axis, *Gx*, the *Y*-axis, *Gy* and the *Z*-axis, *Gz*, for the grayscale or binary 3-D image *I*.

`[Gx,Gy,Gz] = imgradientxyz(I,method)` calculates the directional gradients using the specified method.

“Code Generation” on page 1-748 support: Yes.

“MATLAB Function Block” on page 1-748 support: Yes.

Examples

Compute 3-D Directional Image Gradients Using Sobel Method

Read 3-D data and prepare it for processing.

```
volData = load('mri');  
sz = volData.size;  
vol = squeeze(volData.D);
```

Calculate the directional gradients.


```
[Gx, Gy, Gz] = imgradientxyz(vol);
```

Visualize the directional gradients as a montage.


```
figure, montage(reshape(Gx,sz(1),sz(2),1,sz(3)), 'DisplayRange', [])  
title('Gradient magnitude along X')
```

```
figure, montage(reshape(Gy,sz(1),sz(2),1,sz(3)), 'DisplayRange', [])  
title('Gradient magnitude along Y')
```


```
figure, montage(reshape(Gz,sz(1),sz(2),1,sz(3)), 'DisplayRange', [])  
title('Gradient magnitude along Z')
```



Gradient magnitude along Y



Gradient magnitude along Z



Input Arguments

I — Input image

nonsparse, numeric or logical, 3-D matrix

Input image, specified as a nonsparse, numeric or logical, 3-D matrix

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

method — Gradient operator

'sobel' (default) | 'prewitt' | 'central' | 'intermediate'

Gradient operator, specified as one of the text strings in the following table.

Value	Meaning
'sobel'	Sobel gradient operator (default)
'prewitt'	Prewitt gradient operator
'central'	Central difference gradient. $dI/dx = (I(x+1) - I(x-1)) / 2$
'intermedia'	Intermediate difference gradient. $dI/dx = I(x+1) - I(x)$

When applying the gradient operator at the boundaries of the image, `imgradientxyz` assumes values outside the bounds of the image are equal to the nearest image border value. This behavior is similar to the 'replicate' boundary option in `imfilter`.

Data Types: `char`

Output Arguments

Gx — Directional gradients along x-axis (horizontal)

nonsparse matrix

Directional gradient along *x*-axis (horizontal), returned as nonsparse matrix equal in size to image *I*. The *X*-axis points in the direction of increasing column subscripts. **Gx** is of class `double`, unless the input image *I* is of class `single`, in which case **Gx** is of class `single`.

Gy — Directional gradients along the y-axis (vertical)

nonsparse matrix

Directional gradient along *y*-axis (vertical), returned as non-sparse matrix equal in size to image *I*. *Y*-axis points in the direction of increasing row subscripts. **Gy** is of class `double`, unless the input image *I* is of class `single`, in which case **Gy** is of class `single`.

Gz — Directional gradients along the z-axis

nonsparse matrix

Directional gradient along z -axis, returned as nonsparse matrix equal in size to image `I`. The Z -axis points in the direction of increasing third dimension subscripts. `GZ` is of class `double`, unless the input image `I` is of class `single`, in which case `GZ` is of class `single`.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, the input argument `method` must be a compile-time constant.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`imgradient` | `imgradient3` | `imgradientxy`

Introduced in R2016a

imguiddfilter

Guided filtering of images

Syntax

```
B = imguiddfilter(A,G)
B = imguiddfilter(A)
B = imguiddfilter(__,Name,Value,...)
```

Description

`B = imguiddfilter(A,G)` filters binary, grayscale, or RGB image `A` using the guided filter, where the filtering process is guided by image `G`. `G` can be a binary, grayscale or RGB image and must have the same number of rows and columns as `A`.

`B = imguiddfilter(A)` filters input image `A` under self-guidance, using `A` itself as the guidance image. This can be used for edge-preserving smoothing of image `A`.

`B = imguiddfilter(__,Name,Value,...)` filters the image `A` using name-value pairs to control aspects of guided filtering. Parameter names can be abbreviated.

Examples

Perform Edge-Preserving Smoothing Using Guided Filtering

This example shows how to perform edge-preserving smoothing using a guide filter.

Read an image into the workspace.

```
A = imread('pout.tif');
```

Smooth the image using `imguiddfilter`. In this syntax, `imguiddfilter` uses the image itself as the guidance image.

```
Ismooth = imguiddfilter(A);
```

Display the original image and the smoothed image side-by-side.

```
imshowpair(A,Ismooth, 'montage');
```



- “Perform Flash/No-flash Denoising with Guided Filter”

Input Arguments

A — Image to be filtered

binary image | grayscale image | RGB image

Image to be filtered, specified as a nonsparse, binary, grayscale, or RGB image.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32` | `logical`

G — Image to use as a guide during filtering

binary image | grayscale image | RGB image

Image to use as a guide during filtering, specified as a nonsparse, binary, grayscale, or RGB image.

Data Types: single | double | int8 | int16 | int32 | uint8 | uint16 | uint32 | logical

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1`, `Value1`, ..., `NameN`, `ValueN`.

Example: `Ismooth = imguiddfilter(A,'NeighborhoodSize',[4 4]);`

'NeighborhoodSize' — Size of the rectangular neighborhood around each pixel used in guided filtering

[5 5] (default) | scalar or two-element vector of positive integers

Size of the rectangular neighborhood around each pixel used in guided filtering, specified as a scalar or a two-element vector, [M N], of positive integers. If you specify a scalar value, such as Q, the neighborhood is a square of size [Q Q].

Example: `Ismooth = imguiddfilter(A,'NeighborhoodSize',[4 4]);`

Data Types: single | double | int8 | int16 | int32 | int64 | uint8 | uint16 | uint32 | uint64

'DegreeOfSmoothing' — Amount of smoothing in the output image

0.01*diff(getrangefromclass(G)).^2 (default) | positive scalar

Amount of smoothing in the output image, specified as a positive scalar. If you specify a small value, only neighborhoods with small variance (uniform areas) will get smoothed and neighborhoods with larger variance (such as around edges) will not be smoothed. If you specify a larger value, high variance neighborhoods, such as stronger edges, will get smoothed in addition to the relatively uniform neighborhoods. Start with the default value, check the results, and adjust the default up or down to achieve the effect you desire.

Data Types: single | double | int8 | int16 | int32 | int64 | uint8 | uint16 | uint32 | uint64

Output Arguments

B — Filtered image

array the same size and type as A

Filtered image, returned as an array of the same size and type as A

More About

Tips

- The parameter `DegreeOfSmoothing` specifies a soft threshold on variance for the given neighborhood. If a pixel's neighborhood has variance much lower than the threshold, it will see some amount of smoothing. If a pixel's neighborhood has variance much higher than the threshold it will have little to no smoothing.
- Input images `A` and `G` can be of different classes. If either `A` or `G` is of class `integer` or `logical`, `imguiddfilter` converts them to floating-point precision for internal computation.
- Input images `A` and `G` can have different number of channels.
 - If `A` is an RGB image and `G` is a grayscale or binary image, `imguiddfilter` uses `G` for guidance for all the channels of `A` independently.
 - If both `A` and `G` are RGB images, `imguiddfilter` uses each channel of `G` for guidance for the corresponding channel of `A`, i.e. plane-by-plane behavior.
 - If `A` is a grayscale or binary image and `G` is an RGB image, `imguiddfilter` uses all the three channels of `G` for guidance (color statistics) for filtering `A`.
- “What is Guided Image Filtering?”

References

- [1] Kaiming He, Jian Sun, Xiaou Tang, *Guided Image Filtering*. IEEE Transactions on Pattern Analysis and Machine Intelligence, Volume 35, Issue 6, pp. 1397-1409, June 2013

See Also

`edge` | `imfilter` | `imsharpen`

imhandles

Get all image handles

Syntax

```
himage = imhandles(h)
```

Description

`himage = imhandles(h)` takes a graphics handle `h` as an input and returns all of the image handles whose ancestor is `h`. `h` can be an array of valid figure, axes, image, or uipanel handles.

`himage` is an array of image handles.

`imhandles` ignores colorbars in `h` and does not include its handle in `himage`.

Note

`imhandles` errors if the image objects in `himage` do not have the same figure as their parent.

Examples

Return the handle to the image object in the current axes.

```
figure, imshow('moon.tif');  
himage = imhandles(gca)
```

Display two images in a figure and uses `imhandles` to get handles to both of the image objects in the figure.

```
subplot(1,2,1), imshow('autumn.tif');  
subplot(1,2,2), imshow('glass.png');  
himages = imhandles(gcf)
```

See Also

imgca | imgcf

Introduced before R2006a

imhist

Histogram of image data

Syntax

```
imhist(I)
imhist(I,n)
imhist(X,map)
[counts,binLocations] = imhist(I)
[counts,binLocations] = imhist(gpuarrayI, ___ )
```

Description

`imhist(I)` calculates the histogram for the intensity image `I` and displays a plot of the histogram. The number of bins in the histogram is determined by the image type.

`imhist(I,n)` calculates the histogram, where `n` specifies the number of bins used in the histogram. `n` also specifies the length of the colorbar displayed at the bottom of the histogram plot.

`imhist(X,map)` displays a histogram for the indexed image `X`. This histogram shows the distribution of pixel values above a colorbar of the colormap `map`. The colormap must be at least as long as the largest index in `X`. The histogram has one bin for each entry in the colormap.

`[counts,binLocations] = imhist(I)` returns the histogram counts in `counts` and the bin locations in `binLocations` so that `stem(binLocations,counts)` shows the histogram. For indexed images, `imhist` returns the histogram counts for each colormap entry. The length of `counts` is the same as the length of the colormap.

`[counts,binLocations] = imhist(gpuarrayI, ___)` performs the histogram calculation on a GPU. The input image and the return values are `gpuArrays`. This syntax requires the Parallel Computing Toolbox. When the input image is a `gpuArray`, `imhist` does not automatically display the histogram. To display the histogram, use `stem(binLocations,counts)`.


“Code Generation” on page 1-758 support: Yes.

“MATLAB Function Block” on page 1-759 support: Yes.

Examples

Calculate Histogram

```
I = imread('pout.tif');  
imhist(I)
```



Calculate Histogram on a GPU

Create array of class `uint16`.

```
I = gpuArray(imread('pout.tif'));
```

Calculate histogram. Because `imhist` does not automatically display the plot of the histogram when run on a GPU, this example uses `stem` to plot the histogram.

```
[counts,x] = imhist(I);  
stem(x,counts);
```

Input Arguments

I — Input intensity image

numeric array

Input intensity image, specified as a numeric array.

Example: `I = imread('cameraman.tif');`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32` | `logical`

n — Number of bins

256 (for grayscale images) (default) | numeric scalar

Number of bins, specified as a numeric scalar. If `I` is a grayscale image, `imhist` uses a default value of 256 bins. If `I` is a binary image, `imhist` uses two bins.

Example: `[counts,x] = imhist(I,50);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

X — Input indexed image

numeric array

Input indexed image, specified as a numeric array.

Example: `[X,map] = imread('trees.tif');`

Data Types: `single` | `double` | `uint8` | `uint16` | `logical`

map — Colormap associated with indexed image

p-by-3 array

Colormap associated with indexed image, specified as a p-by-3 array.

Example: `[X,map] = imread('trees.tif');`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32` | `logical`

gpuarrayI — Input image

`gpuArray`

Input image, specified as a `gpuArray`.

Example: `gpuarrayI = gpuArray(imread('cameraman.tif'));`

Output Arguments

counts — histogram counts

numeric array

Histogram counts, returned as a numeric array.

binLocations — Bin locations

numeric array

Bin locations, returned as a numeric array.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic `MATLAB Host Computer` target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, note the following:

- If the first input is a binary image, then `n` must be a scalar constant of value 2 at compile time.

- Nonprogrammatic syntaxes are not supported. For example, the syntax `imhist(I)`, where `imhist` displays the histogram, is not supported.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

The input argument `n` must be a compile-time constant.

Tips

- For intensity images, the `n` bins of the histogram are each half-open intervals of width $A/(n-1)$. In particular, for intensity images that are not `int16`, the p th bin is the half-open interval

$$\frac{A(p-1.5)}{(n-1)} \leq x < \frac{A(p-0.5)}{(n-1)},$$

where x is the intensity value. For `int16` intensity images, the p th bin is the half-open interval

$$\frac{A(p-1.5)}{(n-1)} - 32768 \leq x < \frac{A(p-0.5)}{(n-1)} - 32768,$$

where x is the intensity value. The scale factor A depends on the image class. If the intensity image is `double` or `single`, A is 1. If the intensity image is `uint8`, A is 255. If the intensity image is `uint16` or `int16`, A is 65535.

See Also

`gpuArray` | `histeq` | `histogram`

Introduced before R2006a

imhistmatch

Adjust histogram of image to match N-bin histogram of reference image

Syntax

```
B = imhistmatch(A,ref)
B = imhistmatch(A,ref,N)
[B,hgram] = imhistmatch( ___ )
```

Description

`B = imhistmatch(A,ref)` transforms the grayscale or truecolor image `A` returning output image `B` whose histogram approximately matches the histogram of the reference image `ref`, when the same number of bins are used for both histograms.

- If both `A` and `ref` are truecolor RGB images, `imhistmatch` matches each color channel of `A` independently to the corresponding color channel of `ref`.
- If `A` is a truecolor RGB image and `ref` is a grayscale image, `imhistmatch` matches each channel of `A` against the single histogram derived from `ref`.
- If `A` is a grayscale image, `ref` must also be a grayscale image.
-

Images `A` and `ref` can be any of the permissible data types and need not be equal in size.

`B = imhistmatch(A,ref,N)` uses `N` equally spaced bins within the appropriate range for the given image data type. The returned image `B` has no more than `N` discrete levels. The default value for `N` is 64.

- If the data type of the image is either `single` or `double`, the histogram range is `[0, 1]`.
- If the data type of the image is `uint8`, the histogram range is `[0, 255]`
- If the data type of the image is `uint16`, the histogram range is `[0, 65535]`
- If the data type of the image is `int16`, the histogram range is `[-32768, 32767]`

`[B,hgram] = imhistmatch(___)` returns the histogram of the reference image `ref` used for matching in `hgram`. `hgram` is a 1-by-N (when `ref` is grayscale) or a 3-by-N (when `ref` is truecolor) matrix, where N is the number of histogram bins. Each row in `hgram` stores the histogram of a single color channel of `ref`.

Examples

Histogram Matching of Aerial Images

These aerial images, taken at different times, represent overlapping views of the same terrain in Concord, Massachusetts. This example demonstrates that input images `A` and `Ref` can be of different sizes and image types.

Load both images.

```
A = imread('concordaerial.png');
Ref = imread('concordorthophoto.png');
```

Get the size of image `A`.

```
size(A)

ans =

    2036    3060     3
```

Get the size of the reference image `Ref`.

```
size(Ref)

ans =

    2215    2956
```

Note that image `A` and image `Ref` are different in size and type. Image `A` is a truecolor RGB image, while image `Ref` is a grayscale image. Both images are of data type `uint8`.

Generate the histogram matched output image. The example matches each channel of `A` against the single histogram of `ref` built with 64 (default value) equally spaced bins. Output image `B` takes on the characteristics of image `A`—it is an RGB image whose size

and data type is the same as image A. The number of distinct levels present in each RGB channel of image B is determined by the number of bins in the single aim histogram built from grayscale image Ref which in this case is 64.

```
B = imhistmatch(A,Ref);
```

RGB image with color cast



Reference grayscale image



Histogram matched RGB image




Multiple N Values Applied to RGB Images

In this example, you will see the effect on output image B of varying N, the number of equally spaced bins in the aim histogram of image Ref, from its default value 64 to the maximum value of 256 for `uint8` pixel data.

The following images were taken with a digital camera and represent two different exposures of the same scene.

```
A = imread('office_2.jpg'); % Dark Image
Ref = imread('office_4.jpg'); % Reference image
```

Image A, being the darker image, has a preponderance of its pixels in the lower bins. The reference image, Ref, is a properly exposed image and fully populates all of the available bins values in all three RGB channels: as shown in the table below, all three channels have 256 unique levels for 8-bit pixel values.




The unique 8-bit level values for the red channel is 205 for A and 256 for ref. The unique 8-bit level values for the green channel is 193 for A and 256 for ref. The unique 8-bit level values for the blue channel is 224 for A and 256 for ref.

The example generates the output image B using three different values of N: 64, 128 and 256. The objective of function `imhistmatch` is to transform image A such that the histogram of output image B is a match to the histogram of Ref built with N equally


spaced bins. As a result, N represents the upper limit of the number of discrete data levels present in image B.

```
[B64, hgram] = imhistmatch(A, Ref, 64);
[B128, hgram] = imhistmatch(A, Ref, 128);
[B256, hgram] = imhistmatch(A, Ref, 256);
```


Output Image B64




Output Image B128




Output Image B256










RGB Histograms: 64 bins



RGB Histograms: 128 bins



RGB Histograms: 256 bins



The unique 8-bit level values for the red channel for $N=[64 \ 128 \ 256]$ are 57 for output image B64, 101 for output image B128, and 134 for output image B256. The unique 8-bit level values for the green channel for $N=[64 \ 128 \ 256]$ are 57 for output image B64, 101 for output image B128, and 134 for output image B256. The unique 8-bit level values for the blue channel for $N=[64 \ 128 \ 256]$ are 57 for output image B64, 101 for output image B128, and 134 for output image B256. Note that as N increases, the number of levels in each RGB channel of output image B also increases.

Histogram Matching a 16-bit grayscale MRI image

Load a 16-bit grayscale MRI image, darken it for use in this example, and then perform histogram matching at two values of N .

Load a 16-bit DICOM image of a knee imaged via MRI.

```
K = dicomread('knee1.dcm'); % read in original 16-bit image
LevelsK = unique(K(:)); % determine number of unique code values
disp(['image K: # levels: ' num2str(length(LevelsK))]);
disp(['max level = ' num2str( max(LevelsK) )]);
disp(['min level = ' num2str( min(LevelsK) )]);

image K: # levels = 448
max level = 473
min level = 0
```

Since it appears that all 448 discrete values are at low code values (darker), scale the image data to span the entire 16-bit range of [0 65535]

```
% Scale it to full 16-bit range
Kdouble = double(K); % cast uint16 to double
kmult = 65535/(max(max(Kdouble(:)))); % full range multiplier
Ref = uint16(kmult*Kdouble); % full range 16-bit reference image
```

Darken the reference image to create an image (A) that can be used in the histogram matching operation.

```
% build concave bow-shaped curve for darkening Reference image
ramp = [0:65535]/65535;
ppconcave = spline([0 .1 .50 .72 .87 1],[0 .025 .25 .5 .75 1]);
Ybuf = ppval( ppconcave, ramp);
Lut16bit = uint16( round( 65535*Ybuf ) );


% pass image Ref through LUT to darken image
```

```
A = intlut(Ref,Lut16bit);
```


View the two images and note that they have the same number of discrete code values, but differ in overall brightness.

```
subplot(1,2,1), imshow(A)
title('A: Darkened Image');
subplot(1,2,2), imshow(Ref)
title('Ref: Reference Image')
```

A: Darkened Image



Ref: Reference Image




Generate histogram-matched output images at two values of N. The first is the default value of 64, the second is the number of values present in image A of 448.

```
B16bit64 = imhistmatch(A(:,:,1),Ref(:,:,1)); % default # bins: N = 64
N = length(LevelsK); % number of unique 16-bit code values in image A
B16bitUniq = imhistmatch(A(:,:,1),Ref(:,:,1),N);
```


View the results of the two histogram matching operations.

```
figure;
subplot(1,2,1), imshow(B16bit64)
title('B16bit64: N = 64');
subplot(1,2,2), imshow(Ref)
title('B16bitUniq: N = 448')
```


B16bit64: N = 64



B16bitUniq: N = 448



The following figure shows the 16 bit histograms of all four images; the y-axis scaling is the same for plots.



The unique 16-bit code values in output B images are Levels=63 and N=64, for B16bit64 and Levels=222 and N=448 for B16bitUniq. N also represents the upper limit of discrete levels in the output image which is shown above; the number of levels increases from 63 to 222 when the number of histogram bins increases from 64 to 448. But note, in the above histogram plots, there are rapid fluctuations in adjacent histogram bins for the B image containing 222 levels, especially in the upper portion of the histogram range. By comparison, the 63 level B histogram has a relatively smooth and continuous progression of peaks in this region.

Input Arguments

A — Input image

truecolor image | grayscale image

Input image to be transformed, specified as a truecolor or grayscale image. The returned image will take the data type class of the input image.

Data Types: single | double | int16 | uint8 | uint16

ref — Reference image whose histogram is the reference histogram

truecolor image | grayscale image

Reference image whose histogram is the reference histogram, specified as truecolor or grayscale image. The reference image provides the equally spaced N bin reference histogram which output image B is trying to match.

Data Types: single | double | int16 | uint8 | uint16

N — Number of equally spaced bins in reference histogram

64 (default) | scalar

Number of equally spaced bins in reference histogram, specified as a scalar value. In addition to specifying the number of equally spaced bins in the histogram for image ref, N also represents the upper limit of the number of discrete data levels present in output image B.

Data Types: double

Output Arguments

B — Output image

truecolor RGB image | grayscale image

Output image, returned as a truecolor or grayscale image. The output image is derived from image **A** whose histogram is an approximate match to the histogram of input image **Ref** built with **N** equally spaced bins. Image **B** is of the same size and data type as input image **A**. Input argument **N** represents the upper limit of the number of discrete levels contained in image **B**.

Data Types: `single` | `double` | `int16` | `uint8` | `uint16`

hgram — Histogram counts derived from reference image **Ref**

vector | matrix

Histogram counts derived from reference image **Ref**, specified as a vector or matrix. When **ref** is a truecolor image, **hgram** is a 3×**N** matrix. When **ref** is a grayscale image, **hgram** is a 1×**N** vector.


Data Types: `double`

More About

Algorithms

The objective of `imhistmatch` is to transform image **A** such that the histogram of image **B** matches the histogram derived from image **Ref**. It consists of **N** equally spaced bins which span the full range of the image data type. A consequence of matching histograms in this way is that **N** also represents the upper limit of the number of discrete data levels present in image **B**.

An important behavioral aspect of this algorithm to note is that as **N** increases in value, the degree of rapid fluctuations between adjacent populated peaks in the histogram of image **B** tends to increase. This can be seen in the following histogram plots taken from the 16-bit grayscale MRI example.



An optimal value for N represents a trade-off between more output levels (larger values of N) while minimizing peak fluctuations in the histogram (smaller values of N).

See Also

histeq | imadjust | imhist

imhmax

H-maxima transform

Syntax

```
I2 = imhmax(I,h)
I2 = imhmax(I,h,conn)
```

Description

`I2 = imhmax(I,h)` suppresses all maxima in the intensity image `I` whose height is less than `h`, where `h` is a scalar. Regional maxima are connected components of pixels with a constant intensity value, and whose external boundary pixels all have a lower value. By default, `imhmax` uses 8-connected neighborhoods for 2-D images, and 26-connected neighborhoods for 3-D images. For higher dimensions, `imhmax` uses `conndef(ndims(I),'maximal')`.

`I2 = imhmax(I,h,conn)` computes the H-maxima transform, where `conn` specifies the connectivity.

“Code Generation” on page 1-775 support: Yes.

“MATLAB Function Block” on page 1-775 support: Yes.

Examples

Create H-Maxima Transform

Create simple sample array of zeros with several maxima.

```
a = zeros(10,10);
a(2:4,2:4) = 3;
a(6:8,6:8) = 8
```

```
a =
```

```

0  0  0  0  0  0  0  0  0  0
0  3  3  3  0  0  0  0  0  0
0  3  3  3  0  0  0  0  0  0
0  3  3  3  0  0  0  0  0  0
0  0  0  0  0  0  0  0  0  0
0  0  0  0  0  8  8  8  0  0
0  0  0  0  0  8  8  8  0  0
0  0  0  0  0  8  8  8  0  0
0  0  0  0  0  0  0  0  0  0
0  0  0  0  0  0  0  0  0  0

```

Calculate the maxima equal to 4 or more. Note how the area of the image set to 3 is not included.

```
b = imhmax(a,4)
```

```
b =
```

```

0  0  0  0  0  0  0  0  0  0
0  0  0  0  0  0  0  0  0  0
0  0  0  0  0  0  0  0  0  0
0  0  0  0  0  0  0  0  0  0
0  0  0  0  0  4  4  4  0  0
0  0  0  0  0  4  4  4  0  0
0  0  0  0  0  4  4  4  0  0
0  0  0  0  0  0  0  0  0  0
0  0  0  0  0  0  0  0  0  0

```

Input Arguments

I — Input image

nonsparse numeric array of any dimension

Input array, specified as a nonsparse numeric array of any dimension.

```
Example: I = imread('glass.png'); BW = imhmax(I,80);
```

Data Types: single | double | int8 | int16 | int32 | int64 | uint8 | uint16 | uint32 | uint64 | logical

h — h-maxima transform

nonnegative scalar

h-maxima transform, specified as a nonnegative scalar.

Example: `b = imhmax(a,4);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

conn — Connectivity

8 (default) | 4 | 6 | 18 | 26 | 3-by-3-by- ...-by-3 matrix of zeroes and ones

Connectivity, specified as a one of the scalar values in the following table.

By default, `imhmax` uses 8-connected neighborhoods for 2-D images and 26-connected neighborhoods for 3-D images. For higher dimensions, `imhmax` uses `conndef(numel(size(I)), 'maximal')`. Connectivity can be defined in a more general way for any dimension by using for `conn` a 3-by-3-by- ...-by-3 matrix of 0s and 1s. The 1-valued elements define neighborhood locations relative to the center element of `conn`. Note that `conn` must be symmetric around its center element.

Value	Meaning
Two-dimensional connectivities	
4	4-connected neighborhood
8	8-connected neighborhood
Three-dimensional connectivities	
6	6-connected neighborhood
18	18-connected neighborhood
26	26-connected neighborhood

Example: `b = imhmax(a,4,4);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

Output Arguments

I2 — Transformed image

nonsparse numeric array of any class

Transformed image, returned as a nonsparse numeric array of any class, the same size as I.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, the optional third input argument, `conn`, must be a compile-time constant.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

References

[1] Soille, P., *Morphological Image Analysis: Principles and Applications*, Springer-Verlag, 1999, pp. 170-171.

See Also

`conndef` | `imextendedmax` | `imhmin` | `imreconstruct` | `imregionalmax`

Introduced before R2006a

imhmin

H-minima transform

Syntax

```
I2 = imhmin(I,h)
I2 = imhmin(I,h,conn)
```

Description

`I2 = imhmin(I,h)` suppresses all minima in the intensity image `I` whose depth is less than `h`, where `h` is a scalar. Regional minima are connected components of pixels with a constant intensity value, t , whose external boundary pixels all have a value greater than t . By default, `imhmin` uses 8-connected neighborhoods for 2-D images, and 26-connected neighborhoods for 3-D images. For higher dimensions, `imhmin` uses `conndef(ndims(I), 'maximal')`.

`I2 = imhmin(I,h,conn)` computes the H-minima transform, where `conn` specifies the connectivity.

“Code Generation” on page 1-779 support: Yes.

“MATLAB Function Block” on page 1-779 support: Yes.

Examples

Calculate H-Minima Transform

Create a sample image with two regional minima.

```
a = 10*ones(10,10);
a(2:4,2:4) = 7;
a(6:8,6:8) = 2
```

```
a =
```

```

10  10  10  10  10  10  10  10  10  10
10   7   7   7   7  10  10  10  10  10
10   7   7   7   7  10  10  10  10  10
10   7   7   7   7  10  10  10  10  10
10  10  10  10  10  10  10  10  10  10
10  10  10  10  10   2   2   2  10  10
10  10  10  10  10   2   2   2  10  10
10  10  10  10  10   2   2   2  10  10
10  10  10  10  10  10  10  10  10  10
10  10  10  10  10  10  10  10  10  10

```

Suppress all minima below a specified value. Note how the region with pixels valued 7 disappears in the transformed image because its depth is less than the specified h value.

```
b = imhmin(a,4)
```

```
b =
```

```

10  10  10  10  10  10  10  10  10  10
10  10  10  10  10  10  10  10  10  10
10  10  10  10  10  10  10  10  10  10
10  10  10  10  10  10  10  10  10  10
10  10  10  10  10   6   6   6  10  10
10  10  10  10  10   6   6   6  10  10
10  10  10  10  10   6   6   6  10  10
10  10  10  10  10  10  10  10  10  10
10  10  10  10  10  10  10  10  10  10

```

Input Arguments

I — Input image

nonsparse numeric array of any dimension

Input array, specified as a nonsparse numeric array of any dimension.

```
Example: I = imread('glass.png'); BW = imhmin(I,80);
```

Data Types: single | double | int8 | int16 | int32 | int64 | uint8 | uint16 | uint32 | uint64 | logical

h — h-minima transform

nonnegative scalar

h-minima transform, specified as a nonnegative scalar.

Example: `b = imhmin(a,4)`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

conn — Connectivity

8 (default) | 4 | 6 | 18 | 26 | 3-by-3-by- ...-by-3 matrix of zeroes and ones

Connectivity, specified as a one of the scalar values in the following table.

By default, `imhmin` uses 8-connected neighborhoods for 2-D images and 26-connected neighborhoods for 3-D images. For higher dimensions, `imhmin` uses `conndef(numel(size(I)), 'maximal')`. Connectivity can be defined in a more general way for any dimension by using for `conn` a 3-by-3-by- ...-by-3 matrix of 0s and 1s. The 1-valued elements define neighborhood locations relative to the center element of `conn`. Note that `conn` must be symmetric around its center element.

Value	Meaning
Two-dimensional connectivities	
4	4-connected neighborhood
8	8-connected neighborhood
Three-dimensional connectivities	
6	6-connected neighborhood
18	18-connected neighborhood
26	26-connected neighborhood

Example: `b = imhmin(a,4,4)`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

Output Arguments

I2 — Transformed image

nonsparse numeric array of any class

Transformed image, returned as a nonsparse numeric array of any class, the same size as I.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, the optional third input argument, `conn`, must be a compile-time constant.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

References

[1] Soille, P., *Morphological Image Analysis: Principles and Applications*, Springer-Verlag, 1999, pp. 170-171.

See Also

`conndef` | `imextendedmin` | `imhmax` | `imreconstruct` | `imregionalmin`

Introduced before R2006a

imimposemin

Impose minima

Syntax

```
I2 = imimposemin(I,BW)
I2 = imimposemin(I,BW,conn)
```

Description

`I2 = imimposemin(I,BW)` modifies the intensity image `I` using morphological reconstruction so it only has regional minima wherever `BW` is nonzero. `BW` is a binary image the same size as `I`.

By default, `imimposemin` uses 8-connected neighborhoods for 2-D images and 26-connected neighborhoods for 3-D images. For higher dimensions, `imimposemin` uses `conndef(ndims(I), 'minimum')`.

`I2 = imimposemin(I,BW,conn)` specifies the connectivity, where `conn` can have any of the following scalar values.

Value	Meaning
Two-dimensional connectivities	
4	4-connected neighborhood
8	8-connected neighborhood
Three-dimensional connectivities	
6	6-connected neighborhood
18	18-connected neighborhood
26	26-connected neighborhood

Connectivity can also be defined in a more general way for any dimension by using for `conn` a 3-by-3-by-...-by-3 matrix of 0's and 1's. The 1-valued elements define

neighborhood locations relative to the center element of `conn`. Note that `conn` must be symmetric about its center element.

Class Support


`I` can be of any nonsparse numeric class and any dimension. `BW` must be a nonsparse numeric array with the same size as `I`. `I2` has the same size and class as `I`.

Examples

Modify an image so that it only has regional minima at one location.

- 1 Read an image and display it. This image is called the *mask* image.

```
mask = imread('glass.png');  
imshow(mask)
```




- 2 Create the marker image that will be used to process the mask image.

The example creates a binary image that is the same size as the mask image and sets a small area of the binary image to 1. These pixels define the location in the mask image where a regional minimum will be imposed.

```
marker = false(size(mask));  
marker(65:70,65:70) = true;
```

To show where these pixels of interest fall on the original image, this code superimposes the marker over the mask. The small white square marks the spot. This code is not essential to the impose minima operation.


```
J = mask;  
J(marker) = 255;  
figure, imshow(J); title('Marker Image Superimposed on Mask');
```



- 3** Impose the regional minimum on the input image using the `imimposemin` function.

The `imimposemin` function uses morphological reconstruction of the mask image with the marker image to impose the minima at the specified location. Note how all the dark areas of the original image, except the marked area, are lighter.


```
K = imimposemin(mask,marker);  
figure, imshow(K);
```




- 4** To illustrate how this operation removes all minima in the original image except the imposed minimum, compare the regional minima in the original image with the regional minimum in the processed image. These calls to `imregionalmin` return binary images that specify the locations of all the regional minima in both images.

```
BW = imregionalmin(mask);  
figure, imshow(BW);  
title('Regional Minima in Original Image');  
BW2 = imregionalmin(K);  
figure, imshow(BW2);
```

```
title('Regional Minima After Processing');
```



Regional Minima in Original Image



Regional Minima After Processing

More About

Algorithms

`imimposemin` uses a technique based on morphological reconstruction.

See Also

`conndef` | `imreconstruct` | `imregionalmin`

Introduced before R2006a

imlincomb

Linear combination of images

Syntax

```
Z = imlincomb(K1,A1,K2,A2,...,Kn,An)
Z = imlincomb(K1,A1,K2,A2,...,Kn,An,K)
Z = imlincomb( ____,output_class)
gpuarrayZ = imlincomb(gpuarrayK,gpuarrayA, ____,output_class)
```

Description

`Z = imlincomb(K1,A1,K2,A2,...,Kn,An)` computes

$$K1*A1 + K2*A2 + \dots + Kn*An$$

where `K1`, `K2`, through `Kn` are real, double scalars and `A1`, `A2`, through `An` are real, nonsparse, numeric arrays with the same class and size. `Z` has the same class and size as `A1` unless `A1` is logical, in which case `Z` is double.

`Z = imlincomb(K1,A1,K2,A2,...,Kn,An,K)` computes

$$K1*A1 + K2*A2 + \dots + Kn*An + K$$

where `imlincomb` adds `K`, a real, double scalar, to the sum of the products of `K1` through `Kn` and `A1` through `An`.

`Z = imlincomb(____,output_class)` lets you specify the class of `Z`. `output_class` is a string containing the name of a numeric class.

`gpuarrayZ = imlincomb(gpuarrayK,gpuarrayA, ____,output_class)` performs the operation on a GPU, where the input values, `gpuarrayK` and `gpuarrayA`, are `gpuArrays` and the output value, `gpuarrayZ` is a `gpuArray`. This syntax requires the Parallel Computing Toolbox

When performing a series of arithmetic operations on a pair of images, you can achieve more accurate results if you use `imlincomb` to combine the operations, rather than

nesting calls to the individual arithmetic functions, such as `imadd`. When you nest calls to the arithmetic functions, and the input arrays are of an integer class, each function truncates and rounds the result before passing it to the next function, thus losing accuracy in the final result. `imlincomb` computes each element of the output `Z` individually, in double-precision floating point. If `Z` is an integer array, `imlincomb` truncates elements of `Z` that exceed the range of the integer type and rounds off fractional values.

“Code Generation” on page 1-787 support: Yes.

“MATLAB Function Block” on page 1-787 support: Yes.

Examples

Example 1

Scale an image by a factor of 2.

```
I = imread('cameraman.tif');
J = imlincomb(2,I);
imshow(J)
```

Example 1 on a GPU

Scale an image by a factor of 2, performing the operation on a GPU.

```
I = gpuArray(imread('cameraman.tif'));
J = imlincomb(2,I);
imshow(J)
```

Example 2

Form a difference image with the zero value shifted to 128.

```
I = imread('cameraman.tif');
J = uint8(filter2(fspecial('gaussian'), I));
K = imlincomb(1,I,-1,J,128); % K(r,c) = I(r,c) - J(r,c) + 128
figure, imshow(K)
```

Example 2 on a GPU

Form a difference image with the zero value shifted to 128, performing the operation on a GPU.

```
I = gpuArray(imread('cameraman.tif'));
J = uint8(filter2(fspecial('gaussian'), I));
K = imlincomb(1,I,-1,J,128); % K(r,c) = I(r,c) - J(r,c) + 128
figure, imshow(K)
```

Example 3

Add two images with a specified output class.

```
I = imread('rice.png');
J = imread('cameraman.tif');
K = imlincomb(1,I,1,J,'uint16');
figure, imshow(K,[])
```

Example 3 on a GPU

Add two images with a specified output class.

```
I = gpuArray(imread('rice.png'));
J = gpuArray(imread('cameraman.tif'));
K = imlincomb(1,I,1,J,'uint16');
figure, imshow(K,[])
```

Example 4

To illustrate how `imlincomb` performs all the arithmetic operations before truncating the result, compare the results of calculating the average of two arrays, `X` and `Y`, using nested arithmetic functions and then using `imlincomb`.

In the version that uses nested arithmetic functions, `imadd` adds 255 and 50 and truncates the result to 255 before passing it to `imdivide`. The average returned in `Z(1,1)` is 128.

```
X = uint8([ 255 10 75; 44 225 100]);
Y = uint8([ 50 20 50; 50 50 50 ]);
Z = imdivide(imadd(X,Y),2)
```



```
Z =  
    128    15    63  
     47   128    75
```

`imlincomb` performs the addition and division in double precision and only truncates the final result. The average returned in `Z2(1,1)` is 153.

```
Z2 = imlincomb(.5,X,.5,Y)  
Z2 =  
    153    15    63  
     47   138    75
```

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, note the following:

- You can specify up to 4 input image arguments.
- The `output_class` argument must be a compile-time constant.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`imadd` | `imcomplement` | `imdivide` | `immultiply` | `imsubtract` | `gpuArray`

Introduced before R2006a

imline

Create draggable, resizable line

Syntax

```
h = imline
h = imline(hparent)
h = imline(hparent, position)
h = imline(hparent, x, y)
h = imline(..., param1, val1,...)
```

Description

`h = imline` begins interactive placement of a line on the current axes. The function returns `h`, a handle to an `imline` object. The line has a context menu associated with it that controls aspects of its appearance and behavior—see “Interactive Behavior” on page 1-789. Right-click on the line to access this context menu.

`h = imline(hparent)` begins interactive placement of a line on the object specified by `hparent`. `hparent` specifies the HG parent of the line graphics, which is typically an axes but can also be any other object that can be the parent of an `hggroup`

`h = imline(hparent, position)` creates a draggable, resizable line on the object specified by `hparent`. `position` is a 2-by-2 array that specifies the initial endpoint positions of the line in the form `[X1 Y1; X2 Y2]`.

`h = imline(hparent, x, y)` creates a line on the object specified by `hparent`. `x` and `y` are two-element vectors that specify the initial endpoint positions of the line in the form `x = [X1 X2]`, `y = [Y1 Y2]`.

`h = imline(..., param1, val1, ...)` creates a draggable, resizable line, specifying parameters and corresponding values that control the behavior of the line. The following table lists the parameter available. Parameter names can be abbreviated, and case does not matter.


Parameter	Description
'PositionConstraintFcn'	Function handle <code>fcn</code> that is called whenever the object is dragged using the mouse. You can use this



Parameter	Description
	function to control where the line can be dragged. See the help for the setPositionConstraintFcn method for information about valid function handles.

Interactive Behavior

When you call `imline` with an interactive syntax, the pointer changes to a cross hairs

⊕ when over the image. Click and drag the mouse to specify the position and length of the line. The line supports a context menu that you can use to control aspects of its appearance and behavior. For more information about these interactive features, see the following table.



Interactive Behavior	Description
Moving the line.	Move the pointer over the line. The pointer changes to a fleur shape  . Click and drag the mouse to move the line.
Moving the endpoints of the line.	Move the pointer over either end of the line. The pointer changes to the pointing finger,  . Click and drag the mouse to resize the line.
Changing the color used to display the line.	Move the pointer over the line. Right-click and select Set Color from the context menu.
Retrieving the coordinates of the endpoints of the line.	Move the pointer over the line. Right-click and select Copy Position from the context menu. <code>imline</code> copies a 2-by-2 array to the clipboard specifying the coordinates of the endpoints of the line in the form [X1 Y1; X2 Y2].
Deleting the line	Move the pointer on top of the line. Right-click and select Delete from the context menu. To remove this option from the context menu, set the <code>Deletable</code> property to false: <code>h = imline(); h.Deletable = false;</code>

Methods

Each `imline` object supports a number of methods. Type `methods imline` to see a list of the methods.

addNewPositionCallback — Add new-position callback to ROI object

See `imroi` for information.

delete — Delete ROI object

See `imroi` for information.

getColor — Get color used to draw ROI object.

See `imroi` for information.

getPosition — Return current position of line

Returns the endpoint positions of the line.

```
pos = api.getPosition()
```

pos is a 2-by-2 array [X1 Y1; X2 Y2].

getPositionConstraintFcn — Return function handle to current position constraint function

See imroi for information.

removeNewPositionCallback — Remove new-position callback from ROI object.

See imroi for information.

resume — Resume execution of MATLAB command line

See imroi for information.

setColor — Set color used to draw ROI object

See imroi for information.

setConstrainedPosition — Set ROI object to new position

See imroi for information.

setPosition — Set line to new position

setPosition(h, pos) sets the line h to a new position. The new position, pos, has the form, [X1 Y1; X2 Y2].

setPosition(h, x, y) sets the line h to a new position. x and y specify the endpoint positions of the line in the form x = [x1 x2], y = [y1 y2].

setPositionConstraintFcn — Set position constraint function of ROI object.

See imroi for information.

wait — Block MATLAB command line until ROI creation is finished

See imroi for information.

Examples

Example 1

Use a custom color for displaying the line. Use `addNewPositionCallback` method. Move the line, note that the 2-by-2 position vector of the line is displayed in the title above the image. Explore the context menu of the line by right clicking on the line.

```
figure, imshow('pout.tif');  
h = imline(gca,[10 100], [100 100]);  
setColor(h,[0 1 0]);  
id = addNewPositionCallback(h,@(pos) title(mat2str(pos,3)));
```

```
% After observing the callback behavior, remove the callback.  
% using the removeNewPositionCallback API function.  
removeNewPositionCallback(h,id);
```

Example 2

Interactively place a line by clicking and dragging. Use `wait` to block the MATLAB command line. Double-click on the line to resume execution of the MATLAB command line

```
figure, imshow('pout.tif');  
h = imline;  
position = wait(h);
```

More About

Tips

If you use `imline` with an axes that contains an image object, and do not specify a position constraint function, users can drag the line outside the extent of the image and lose the line. When used with an axes created by the `plot` function, the axis limits automatically expand to accommodate the movement of the line.

See Also

`imellipse` | `imfreehand` | `impoint` | `impoly` | `imrect` | `imroi` | `makeConstrainToRectFcn`

Introduced before R2006a

immagbox

Magnification box for scroll panel

Syntax

```
hbox = immagbox(hparent,himage)
```

Description

`hbox = immagbox(hparent,himage)` creates a Magnification box for the image displayed in a scroll panel created by `imscrollpanel`. `hparent` is a handle to the figure or `uipanel` object that will contain the Magnification box. `himage` is a handle to the target image (the image in the scroll panel). `immagbox` returns `hbox`, which is a handle to the Magnification box `uicontrol` object

A Magnification box is an editable text box `uicontrol` that contains the current magnification of the target image. When you enter a new value in the magnification box, the magnification of the target image changes. When the magnification of the target image changes for any reason, the magnification box updates the magnification value.

API Functions

A Magnification box contains a structure of function handles, called an API. You can use the functions in this API to manipulate magnification box. To retrieve this structure, use the `iptgetapi` function.

```
api = iptgetapi(hbox)
```

The API for the Magnification box includes the following function.

Function	Description
<code>setMagnification</code>	Sets the magnification in units of screen pixels per image pixel. <code>setMagnification(new_mag)</code>

Function	Description
	where <code>new_mag</code> is a scalar magnification factor. Multiply <code>new_mag</code> by 100 to get percent magnification. For example if you call <code>setMagnification(2)</code> , the magnification box will show the string '200%'.

Examples

Add a magnification box to a scrollable image. Because the toolbox scrollable navigation is incompatible with standard MATLAB figure window navigation tools, the example suppresses the toolbar and menu bar in the figure window. The example positions the scroll panel in the figure window to allow room for the magnification box.

```

hFig = figure('Toolbar','none',...
             'Menubar','none');
hIm = imshow('pears.png');
hSP = imscrollpanel(hFig,hIm);
set(hSP,'Units','normalized',...
     'Position',[0 .1 1 .9])

hMagBox = immagbox(hFig,hIm);
pos = get(hMagBox,'Position');
set(hMagBox,'Position',[0 0 pos(3) pos(4)])
    
```

Change the magnification of the image in the scroll panel, using the scroll panel API function `setMagnification`. Notice how the magnification box updates.

```

apiSP = iptgetapi(hSP);
apiSP.setMagnification(2)
    
```

See also

`imscrollpanel`, `iptgetapi`

Introduced before R2006a

immovie

Make movie from multiframe image

Note: `immovie(D,size)` is an obsolete syntax and is no longer supported. Use `immovie(X,map)` instead.

Syntax

```
mov = immovie(X,map)
mov = immovie(RGB)
```

Description

`mov = immovie(X,map)` returns the movie structure array `MOV` from the images in the multiframe indexed image `X` with the colormap `map`. For details about the movie structure array, see the reference page for `getframe`. To play the movie, call `implay`.

`X` comprises multiple indexed images, all having the same size and all using the colormap `map`. `X` is an `m-by-n-by-1-by-k` array, where `k` is the number of images.

`mov = immovie(RGB)` returns the movie structure array `MOV` from the images in the multiframe, truecolor image `RGB`.

`RGB` comprises multiple truecolor images, all having the same size. `RGB` is an `m-by-n-by-3-by-k` array, where `k` is the number of images.

Class Support

An indexed image can be `uint8`, `uint16`, `single`, `double`, or `logical`. A truecolor image can be `uint8`, `uint16`, `single`, or `double`. `mov` is a MATLAB movie structure.

Examples

```
load mri
mov = imovie(D,map);
imshow(mov)
```

More About

Tips

To create a movie that can be played outside the MATLAB environment, use the `VideoWriter` class.

See Also

`getframe` | `montage` | `movie` | `VideoWriter`

Introduced before R2006a

immse

Mean-squared error

Syntax

```
err = immse(X,Y)
```

Description

`err = immse(X,Y)` calculates the mean-squared error (MSE) between the arrays `X` and `Y`. `X` and `Y` can be arrays of any dimension, but must be of the same size and class.

“Code Generation” on page 1-801 support: Yes.

“MATLAB Function Block” on page 1-801 support: Yes.

Examples

Calculate Mean-Squared Error in Noisy Image

Read image and display it.

```
ref = imread('pout.tif');  
imshow(ref)
```



Create another image by adding noise to a copy of the reference image.

```
A = imnoise(ref, 'salt & pepper', 0.02);  
imshow(A)
```



Calculate mean-squared error between the two images.

```
err = immse(A, ref);  
fprintf('\n The mean-squared error is %0.4f\n', err);
```

```
The mean-squared error is 353.7631
```

Input Arguments

X — Input array

numeric array

Input array, specified as a nonsparse, numeric array.

Example: `err = immse(I,I2);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

Y — Input array

nonsparse, numeric array

Input arrays, specified as a nonsparse, numeric array.

Example: `err = immse(I,I2);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

Output Arguments

err — Mean-squared error

`double` | `single`

Mean-squared error, returned as a scalar of class `double`. If the input arguments are of class `single`, `err` is of class `single`.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`mean` | `median` | `psnr` | `ssim` | `sum` | `var`

Introduced in R2014b

immultiply

Multiply two images or multiply image by constant

Syntax

```
Z = immultiply(X,Y)
```

Description

`Z = immultiply(X,Y)` multiplies each element in array `X` by the corresponding element in array `Y` and returns the product in the corresponding element of the output array `Z`.

If `X` and `Y` are real numeric arrays with the same size and class, then `Z` has the same size and class as `X`. If `X` is a numeric array and `Y` is a scalar double, then `Z` has the same size and class as `X`.

If `X` is logical and `Y` is numeric, then `Z` has the same size and class as `Y`. If `X` is numeric and `Y` is logical, then `Z` has the same size and class as `X`.

`immultiply` computes each element of `Z` individually in double-precision floating point. If `X` is an integer array, then elements of `Z` exceeding the range of the integer type are truncated, and fractional values are rounded.

If `X` and `Y` are numeric arrays of the same size and class, you can use the expression `X.*Y` instead of `immultiply`.

Examples

Multiply an image by itself. Note how the example converts the class of the image from `uint8` to `uint16` before performing the multiplication to avoid truncating the results.

```
I = imread('moon.tif');  
I16 = uint16(I);  
J = immultiply(I16,I16);  
imshow(I), figure, imshow(J)
```


Scale an image by a constant factor:

```
I = imread('moon.tif');  
J = immultiply(I,0.5);  
subplot(1,2,1), imshow(I)  
subplot(1,2,2), imshow(J)
```

See Also

[imabsdiff](#) | [imadd](#) | [imcomplement](#) | [imdivide](#) | [imlincomb](#) | [imsubtract](#)

Introduced before R2006a

imnoise

Add noise to image

Syntax

```
J = imnoise(I,type)
J = imnoise(I,type,parameters)
J = imnoise(I,'gaussian',M,V)
J = imnoise(I,'localvar',V)
J = imnoise(I,'localvar',image_intensity,var)
J = imnoise(I,'poisson')
J = imnoise(I,'salt & pepper',d)
J = imnoise(I,'speckle',v)
gpuarrayJ = imnoise(gpuarrayI, ___ )
```

Description

`J = imnoise(I,type)` adds noise of a given type to the intensity image `I`. `type` is a string that specifies any of the following types of noise. Note that certain types of noise support additional parameters. See the related syntax.

Value	Description
'gaussian'	Gaussian white noise with constant mean and variance
'localvar'	Zero-mean Gaussian white noise with an intensity-dependent variance
'poisson'	Poisson noise
'salt & pepper'	On and off pixels
'speckle'	Multiplicative noise

`J = imnoise(I,type,parameters)` Depending on `type`, you can specify additional parameters to `imnoise`. All numerical parameters are normalized— they correspond to operations with images with intensities ranging from 0 to 1.

`J = imnoise(I,'gaussian',M,V)` adds Gaussian white noise of mean `m` and variance `v` to the image `I`. The default is zero mean noise with 0.01 variance.

`J = imnoise(I, 'localvar', V)` adds zero-mean, Gaussian white noise of local variance `V` to the image `I`. `V` is an array of the same size as `I`.

`J = imnoise(I, 'localvar', image_intensity, var)` adds zero-mean, Gaussian noise to an image `I`, where the local variance of the noise, `var`, is a function of the image intensity values in `I`. The `image_intensity` and `var` arguments are vectors of the same size, and `plot(image_intensity, var)` plots the functional relationship between noise variance and image intensity. The `image_intensity` vector must contain normalized intensity values ranging from 0 to 1.

`J = imnoise(I, 'poisson')` generates Poisson noise from the data instead of adding artificial noise to the data. If `I` is double precision, then input pixel values are interpreted as means of Poisson distributions scaled up by `1e12`. For example, if an input pixel has the value `5.5e-12`, then the corresponding output pixel will be generated from a Poisson distribution with mean of 5.5 and then scaled back down by `1e12`. If `I` is single precision, the scale factor used is `1e6`. If `I` is `uint8` or `uint16`, then input pixel values are used directly without scaling. For example, if a pixel in a `uint8` input has the value 10, then the corresponding output pixel will be generated from a Poisson distribution with mean 10.

`J = imnoise(I, 'salt & pepper', d)` adds salt and pepper noise to the image `I`, where `d` is the noise density. This affects approximately `d*numel(I)` pixels. The default for `d` is 0.05.

`J = imnoise(I, 'speckle', v)` adds multiplicative noise to the image `I`, using the equation $J = I + n * I$, where `n` is uniformly distributed random noise with mean 0 and variance `v`. The default for `v` is 0.04.

Note The mean and variance parameters for 'gaussian', 'localvar', and 'speckle' noise types are always specified as if the image were of class `double` in the range [0, 1]. If the input image is of class `uint8` or `uint16`, the `imnoise` function converts the image to `double`, adds noise according to the specified type and parameters, and then converts the noisy image back to the same class as the input.

`gpuarrayJ = imnoise(gpuarrayI, ___)` adds noise to the `gpuArray` intensity image `gpuarrayI`, performing the operation on a GPU. Returns a `gpuArray` image `J` of the same class. This syntax requires the Parallel Computing Toolbox.

Class Support

For most noise types, the input image **I** can be of class `uint8`, `uint16`, `int16`, `single`, or `double`. For Poisson noise, `int16` is not allowed. The output image **J** is of the same class as **I**. If **I** has more than two dimensions it is treated as a multidimensional intensity image and not as an RGB image.

An input `gpuArray` image **I** can be of class `uint8`, `uint16`, `int16`, `single`, or `double`. For Poisson noise, `int16` is not allowed. The output `gpuArray` image **J** is of the same class as **I**. If **I** has more than two dimensions it is treated as a multidimensional intensity image and not as an RGB `gpuArray` image.

Examples

Add noise to an image.

Add noise to an image.

```
I = imread('eight.tif');  
J = imnoise(I,'salt & pepper',0.02);  
figure, imshow(I)  
figure, imshow(J)
```





Add Noise to an Image Performing Operation on a GPU

```
I = gpuArray(imread('eight.tif'));  
J = imnoise(I,'salt & pepper', 0.02);
```

```
figure, imshow(I);  
figure, imshow(J);
```

See Also

rand | randn | gpuArray

Introduced before R2006a

imopen

Morphologically open image

Syntax

```
IM2 = imopen(IM,SE)
IM2 = imopen(IM,NHOOD)
gpuarrayIM2 = imopen(gpuarrayIM, ___ )
```

Description

`IM2 = imopen(IM,SE)` performs morphological opening on the grayscale or binary image `IM` with the structuring element `SE`. The argument `SE` must be a single structuring element object, as opposed to an array of objects. The morphological open operation is an erosion followed by a dilation, using the same structuring element for both operations.

`IM2 = imopen(IM,NHOOD)` performs opening with the structuring element `strel(NHOOD)`, where `NHOOD` is an array of 0's and 1's that specifies the structuring element neighborhood.

`gpuarrayIM2 = imopen(gpuarrayIM, ___)` performs the operation on a graphics processing unit (GPU) with the structuring element `strel(NHOOD)`, if `NHOOD` is an array of 0s and 1s that specifies the structuring element neighborhood, or `strel(gather(NHOOD))` if `NHOOD` is a `gpuArray` object that specifies the structuring element neighborhood. This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-811 support: Yes.

“MATLAB Function Block” on page 1-811 support: Yes.

Class Support

`IM` can be any numeric or logical class and any dimension, and must be nonsparse. If `IM` is logical, then `SE` must be flat.

`gpuarrayIM` must be a `gpuArray` of type `uint8` or `logical`. When used with a `gpuarray`, the structuring element must be flat and two-dimensional.


The output has the same class as the input.

Examples

Morphologically Open Image with a Disk-shaped Structuring Element

Read the image into the MATLAB workspace and display it.

```
original = imread('snowflakes.png');  
figure, imshow(original);
```



Create a disk-shaped structuring element with a radius of 5 pixels.

```
se = strel('disk',5);
```

Remove snowflakes having a radius less than 5 pixels by opening it with the disk-shaped structuring element.

```
afterOpening = imopen(original,se);  
figure, imshow(afterOpening,[]);
```



Morphologically Open Image with Disk-shaped Structuring Element on a GPU

Read an image.


```
original = imread('snowflakes.png');
```

Create a disk-shaped structuring element.

```
se = strel('disk',5);
```

Morphologically open the image on a GPU, using a `gpuArray` object, and display the images.

```
afterOpening = imopen(gpuArray(original),se);  
figure, imshow(original), figure, imshow(afterOpening,[])
```

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, the image input argument, **IM**, must be 2-D or 3-D and the structuring element input argument, **SE**, must be a compile-time constant.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`imclose` | `imdilate` | `imerode` | `strel` | `offsetstrel` | `gpuArray`

Introduced before R2006a

imoverlay

Burn binary mask into 2-D image

Syntax

```
B = imoverlay(A,BW)
B = imoverlay( ____,color)
```

Description

`B = imoverlay(A,BW)` fills the grayscale or RGB input image, `A`, with a solid color where the input binary mask, `BW`, is `true`.

`B = imoverlay(____,color)` lets you specify the color that `imoverlay` uses to fill the image. `color` is a valid MATLAB color specification.

“Code Generation” on page 1-814 support: Yes.

“MATLAB Function Block” on page 1-814 support: Yes.

Examples

Burn Binary Image into Grayscale Image

Read grayscale image into the workspace.

```
A = imread('cameraman.tif');
```

Read binary image into the workspace.

```
BW = imread('text.png');
```

Burn the binary image into the grayscale image, choosing the color to be used.

```
B = imoverlay(A,BW,'yellow');
```

Display the result.

```
figure  
imshow(B)
```



Input Arguments

A — Input image

real, nonsparse 2-D matrix

Input image, specified as a real, nonsparse 2-D matrix.

Data Types: `single` | `double` | `int16` | `uint8` | `uint16` | `logical`

BW — Mask image

2-D logical matrix

Mask image, specified 2-D logical matrix the same size as **A**.

Data Types: `single` | `double` | `int16` | `uint8` | `uint16` | `logical`

color — Color used for the overlay

MATLAB color specification

Color used for the overlay, specified as a MATLAB color specification. For example, if you want to specify the color red, you could use any of the following specifications: 'red', 'r', or [1 0 0].

Output Arguments

B — Output image

2-D matrix

Output image, returned as a 2-D matrix of class `uint8`.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, if you specify `color` as a string, the string must be a compile-time constant.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`boundarymask` | `superpixels`

Introduced in R2016a

imoverview

Overview tool for image displayed in scroll panel

Syntax


```
imoverview(himage)  
hfig = imoverview(...)
```

Description

`imoverview(himage)` creates an Overview tool associated with the image specified by the handle `himage`, called the target image. The target image must be contained in a scroll panel created by `imscrollpanel`.

The Overview tool is a navigation aid for images displayed in a scroll panel. `imoverview` creates the tool in a separate figure window that displays the target image in its entirety, scaled to fit. Over this scaled version of the image, the tool draws a rectangle, called the detail rectangle, that shows the portion of the target image that is currently visible in the scroll panel. To view portions of the image that are not currently visible in the scroll panel, move the detail rectangle in the Overview tool.

The following figure shows the Image Tool with the Overview tool.



`hfig = imoverview(...)` returns a handle to the Overview tool figure.

Note

To create an Overview tool that can be embedded in an existing figure or uipanel object, use `imoverviewpanel`.

Examples

Create a figure, disabling the toolbar and menubar, because the toolbox navigation tools are not compatible with the standard MATLAB zoom and pan tools. Then create a scroll panel in the figure and use scroll panel API functions to set the magnification.

```
hFig = figure('Toolbar','none',...
    'Menubar','none');
hIm = imshow('tape.png');
```

```
hSP = imscrollpanel(hFig,hIm);  
api = iptgetapi(hSP);  
api.setMagnification(2) % 2X = 200%  
imoverview(hIm)
```

See Also

[imoverviewpanel](#) | [imscrollpanel](#)

Introduced before R2006a

imoverviewpanel

Overview tool panel for image displayed in scroll panel

Syntax

```
hpanel = imoverviewpanel(hparent,himage)
```

Description

`hpanel = imoverviewpanel(hparent,himage)` creates an Overview tool panel associated with the image specified by the handle `himage`, called the target image. `himage` must be contained in a scroll panel created by `imscrollpanel`. `hparent` is a handle to the figure or `uipanel` object that will contain the Overview tool panel. `imoverviewpanel` returns `hpanel`, a handle to the Overview tool `uipanel` object.

The Overview tool is a navigation aid for images displayed in a scroll panel. `imoverviewpanel` creates the tool in a `uipanel` object that can be embedded in a figure or `uipanel` object. The tool displays the target image in its entirety, scaled to fit. Over this scaled version of image, the tool draws a rectangle, called the detail rectangle, that shows the portion of the target image that is currently visible in the scroll panel. To view portions of the image that are not currently visible in the scroll panel, move the detail rectangle in the Overview tool.

Note

To create an Overview tool in a separate figure, use `imoverview`. When created using `imoverview`, the Overview tool includes zoom-in and zoom-out buttons.

Examples

Create an Overview tool that is embedded in the same figure that contains the target image.

```
hFig = figure('Toolbar','none','Menubar','none');
```



```
hIm = imshow('tissue.png');  
hSP = imscrollpanel(hFig,hIm);  
set(hSP,'Units','normalized','Position',[0 .5 1 .5])  
hOvPanel = imoverviewpanel(hFig,hIm);  
set(hOvPanel,'Units','Normalized',...  
'Position',[0 0 1 .5])
```

See Also

[imoverview](#) | [imscrollpanel](#)

Introduced before R2006a

impixel

Pixel color values

Syntax

```
impixel(I)
P = impixel(I,c,r)
P = impixel(X,map)
P = impixel(X,map,c,r)
[c,r,P] = impixel(____)
P = impixel(x,y,I,xi,yi)
[xi,yi,P] = impixel(x,y,I,xi,yi)
```

Description

`impixel(I)` returns the value of pixels in the specified image `I`, where `I` can be a grayscale, binary, or RGB image. `impixel` displays the image specified and waits for you to select the pixels in the image using the mouse. If you omit the input arguments, `impixel` operates on the image in the current axes.

Use normal button clicks to select pixels. Press **Backspace** or **Delete** to remove the previously selected pixel. To finish selecting pixels, adding a final pixel, press shift-click, right-click, or double-click. To finish selecting pixels without adding a final pixel, press **Return**.

When you finish selecting pixels, `impixel` returns an `m`-by-3 matrix of RGB values in the supplied output argument. If you do not supply an output argument, `impixel` returns the matrix in `ans`. `impixel` always returns pixel values as RGB triplets, regardless of the image type:

- For an RGB image, `impixel` returns the actual data for the pixel. The values are either `uint8` integers or `double` floating-point numbers, depending on the class of the image array.
- For an indexed image, `impixel` returns the RGB triplet stored in the row of the colormap that the pixel value points to. The values are `double` floating-point numbers.

- For grayscale images, `impixel` returns the intensity value as an RGB triplet, where $R=G=B$. The values are either `uint8` integers or `double` floating-point numbers, depending on the class of the image array.
- For binary images, `impixel` returns the intensity value as an RGB triplet, where $R=G=B$. The values are `double` floating-point numbers.

`P = impixel(I,c,r)` returns the values of pixels specified by the row and column vectors `r` and `c`. `r` and `c` must be equal-length vectors. The k th row of `P` contains the RGB values for the pixel $(r(k),c(k))$.

`P = impixel(X,map)` returns the value of pixels in the specified indexed image `I` with corresponding colormap, `map`.

`P = impixel(X,map,c,r)` returns the value of pixels specified by the row and column vectors `r` and `c`.

`[c,r,P] = impixel(___)` returns the coordinates of the selected pixels.

`P = impixel(x,y,I,xi,yi)` returns the values of pixels in the specified image, `I`, where `x` and `y` are two-element vectors specifying the image `XData` and `YData`. `xi` and `yi` are equal-length vectors specifying the spatial coordinates of the pixels whose values are returned in `P`

`[xi,yi,P] = impixel(x,y,I,xi,yi)` returns the coordinates of the selected pixels.

Class Support

The input image can be of class `uint8`, `uint16`, `int16`, `single`, `double`, or `logical`. All other inputs are of class `double`.

If the input is `double`, the output `P` is `double`. For all other input classes the output is `single`. The rest of the outputs are `double`.

Examples

```
RGB = imread('peppers.png');  
c = [12 146 410];  
r = [104 156 129];
```

```
pixels = impixel( RGB, c, r )
```

```
pixels =
```

```
    62    34    63  
   166    54    60  
    59    28    47
```

See Also

`improfile`

Introduced before R2006a

impixelinfo

Pixel Information tool

Syntax

```
impixelinfo
impixelinfo(h)
impixelinfo(hparent,himage)
hpanel = impixelinfo(...)
```


Description

`impixelinfo` creates a Pixel Information tool in the current figure. The Pixel Information tool displays information about the pixel in an image that the pointer is positioned over. The tool can display pixel information for all the images in a figure.

The Pixel Information tool is a uipanel object, positioned in the lower-left corner of the figure. The tool contains the text string `Pixel info:` followed by the pixel information. Before you move the pointer over the image, the tool contains the default pixel information text string `(X,Y) Pixel Value`. Once you move the pointer over the image, the information displayed varies by image type, as shown in the following table. If you move the pointer off the image, the pixel information tool displays the default pixel information string for that image type.

Image Type	Pixel Information	Example
Intensity	(X,Y) Intensity	(13,30) 82
Indexed	(X,Y) <index> [R G B]	(2,6) <4> [0.29 0.05 0.32]
Binary	(X,Y) BW	(12,1) 0
Truecolor	(X,Y) [R G B]	(19,10) [15 255 10]
Floating point image with <code>CDataMapping</code> property set to <code>direct</code>	(X,Y) value <index> [R G B]	(19,10) 82 <4> [15 255 10]

For example, for grayscale (intensity) images, the pixel information tool displays the x and y coordinates of the pixel and its value, as shown in the following figure.



If you want to display the pixel information without the “Pixel Info” label, use the `impixelinfoval` function.

`impixelinfo(h)` creates a Pixel Information tool in the figure specified by `h`, where `h` is a handle to an image, axes, uipanel, or figure object. Axes, uipanel, or figure objects must contain at least one image object.

`impixelinfo(hparent,himage)` creates a Pixel Information tool in `hparent` that provides information about the pixels in `himage`. `himage` is a handle to an image or an array of image handles. `hparent` is a handle to the figure or uipanel object that contains the pixel information tool.

`hpanel = impixelinfo(...)` returns a handle to the Pixel Information tool uipanel.

Note

To copy the pixel information string to the clipboard, right-click while the pointer is positioned over a pixel. In the context menu displayed, choose **Copy pixel info**.

Examples

Display an image and add a Pixel Information tool to the figure. The example shows how you can change the position of the tool in the figure using properties of the tool uipanel object.

```
h = imshow('hestain.png');
hp = impixelinfo;
set(hp,'Position',[5 1 300 20]);
```

Use the Pixel Information tool in a figure containing multiple images of different types.

```
figure
subplot(1,2,1), imshow('liftingbody.png');
subplot(1,2,2), imshow('autumn.tif');
```

`impixelinfo;`

See Also

`impixelinfoval` | `imtool`

Introduced before R2006a

impixelinfoval

Pixel Information tool without text label

Syntax

```
hcontrol = impixelinfoval(hparent,himage)
```

Description

`hcontrol = impixelinfoval(hparent,himage)` creates a Pixel Information tool in `hparent` that provides information about the pixels in the image specified by `himage`. `hparent` is a handle to a figure or uipanel object. `himage` can be a handle to an image or an array of image handles.

The Pixel Information tool displays information about the pixel in an image that the pointer is positioned over. The tool displays pixel information for all the images in a figure.

When created with `impixelinfo`, the tool is a uipanel object, positioned in the lower-left corner of the figure, that contains the text label **Pixel Info:** followed by the *x*- and *y*-coordinates of the pixel and its value. When created with `impixelinfoval`, the tool is a uicontrol object positioned in the lower-left corner of the figure, that displays the pixel information without the text label, as shown in the following figure.

X and Y coordinates	Pixel Value
(167, 251)	114

The information displayed depends on the image type. See `impixelinfo` for details.

To copy the pixel value string to the Clipboard, right-click while the pointer is positioned over a pixel. In the context menu displayed, choose **Copy pixel info**.

Examples

Add a Pixel Information tool to a figure. Note how you can change the style and size of the font used to display the value in the tool using standard Handle Graphics commands.

```
ankle = dicomread('CT-MON02-16-ankle.dcm');  
h = imshow(ankle,[]);  
hText = impixelinfoval(gcf,h);  
set(hText,'FontWeight','bold')  
set(hText,'FontSize',10)
```

See also

`impixelinfo`

Introduced before R2006a

impixelregion


Pixel Region tool

Syntax

```
impixelregion  
impixelregion(h)  
hfig = impixelregion(...)
```

Description

`impixelregion` creates a Pixel Region tool associated with the image displayed in the current figure, called the target image. The Pixel Region tool opens a separate figure window containing an extreme close-up view of a small region of pixels in the target image, as shown in the following figure.



The Pixel Region rectangle defines the area of the target image that is displayed in the Pixel Region tool. You can move this rectangle over the target image using the mouse to view different regions. To get a closer view of the pixels displayed in the tool, use the zoom buttons on the Pixel Region tool toolbar or change the size of the Pixel Region rectangle using the mouse. You can also resize the Pixel Region tool itself to view more or fewer pixels. If the size of the pixels allows, the tool superimposes the numeric value of the pixel over each pixel.

To get the current position of the Pixel Region rectangle, right-click on the rectangle and select **Copy Position** from the context menu. The Pixel Region tool copies a four-element position vector to the clipboard. To change the color of the Pixel Region rectangle, right-click and select **Set Color**.

`impixelregion(h)` creates a Pixel Region tool associated with the object specified by the handle `h`. `h` can be a handle to a figure, axes, uipanel, or image object. If `h` is a handle to an axes or figure, `impixelregion` associates the tool with the first image found in the axes or figure.

`hfig = impixelregion(...)` returns `hfig`, a handle of the Pixel Region tool figure.

Note

To create a Pixel Region tool that can be embedded in an existing figure window or uipanel, use `impixelregionpanel`.

Examples

Display an image and then create a Pixel Region tool associated with the image.

```
imshow peppers.png
impixelregion
```

See Also

`impixelinfo` | `imtool` | `impixelregionpanel`

Introduced before R2006a

impixelregionpanel

Pixel Region tool panel

Syntax

```
hpanel = impixelregionpanel(hparent,himage)
```

Description

`hpanel = impixelregionpanel(hparent,himage)` creates a Pixel Region tool panel associated with the image specified by the handle `himage`, called the target image. This is the image whose pixels are to be displayed. `hparent` is the handle to the figure or `uipanel` object that will contain the Pixel Region tool panel. `hpanel` is the handle to the Pixel Region tool scroll panel.

The Pixel Region tool is a `uipanel` object that contains an extreme close-up view of a small region of pixels in the target image. If the size of the pixels allows, the tool superimposes the numeric value of the pixel over each pixel. To define the region being examined, the tool overlays a rectangle on the target image, called the pixel region rectangle. To view pixels in a different region, click and drag the rectangle over the target image. See `impixelregion` for more information.

Note

To create a Pixel Region tool in a separate figure window, use `impixelregion`.

Examples

```
himage = imshow('peppers.png');  
hfigure = figure;  
hpanel = impixelregionpanel(hfigure, himage);
```

Set the panel's position to the lower-left quadrant of the figure.

```
set(hpanel, 'Position', [0 0 .5 .5])
```

See Also

`impixelregion` | `imrect` | `imscrollpanel`

Introduced before R2006a

implay

Play movies, videos, or image sequences


Syntax

```
implay  
implay(filename)  
implay(I)  
implay(..., FPS)
```

Description

`implay` opens the Video Viewer app. You can use Video Viewer to show MATLAB movies, videos, or image sequences (also called image stacks). To select the movie or image sequence that you want to play, use the Video Viewer **File** menu. To play the movie, jump to a specific frame in the image sequence, or change the frame rate of the display use the Video Viewer toolbar buttons or menu options. You can open multiple Video Viewers to view different movies simultaneously.

The following figure shows the Video Viewer app containing an image sequence.



`imshow(filename)` opens the Video Viewer app, displaying the content of the file specified by `filename`. The file can be an Audio Video Interleaved (AVI) file. The Video Viewer reads one frame at a time, conserving memory during playback. The Video Viewer does not play audio tracks.

`imshow(I)` opens the Video Viewer app, displaying the first frame in the multiframe image array specified by `I`. `I` can be a MATLAB movie structure, or a sequence of binary, grayscale, or truecolor images. A binary or grayscale image sequence can be an M -by- N -by-1-by- K array or an M -by- N -by- K array. A truecolor image sequence must be an M -by- N -by-3-by- K array.

`implay(..., FPS)` specifies the rate at which you want to view the movie or image sequence. The frame rate is specified as frames-per-second. If omitted, the Video Viewer uses the frame rate specified in the file or the default value 20.

Class Support

I can be numeric but `uint8` is preferred. The actual data type used to display pixels may differ from the source data type.

Examples

Animate a sequence of images.

```
load cellsequence
implay(cellsequence,10);
```

Visually explore a stack of MRI images.

```
load mrystack
implay(mrystack);
```

Play an AVI file.

```
implay('rhinos.avi');
```

More About

Tips

- You can also open the Video Viewer app through the Apps tab. Navigate to the Image Processing and Computer Vision group and click Video Viewer.

Introduced in R2007b

impoint

Create draggable point

Syntax

```
h = impoint
h = impoint(hparent)
h = impoint(hparent,position)
h = impoint(hparent,x, y)
h = impoint(..., param,val)
```

Description

`h = impoint` begins interactive placement of a draggable point on the current axes. The function returns `h`, a handle to an `impoint` object. The point has a context menu associated with it that controls aspects of its appearance and behavior—see “Interactive Behavior” on page 1-837. Right-click on the point to access this context menu.

`h = impoint(hparent)` begins interactive placement of a point on the object specified by `hparent`. `hparent` specifies the HG parent of the point graphics, which is typically an axes but can also be any other object that can be the parent of an `hggroup`.

`h = impoint(hparent,position)` creates a draggable point on the object specified by `hparent`. `position` is a 1-by-2 array of the form `[x y]` that specifies the initial position of the point.

`h = impoint(hparent,x, y)` creates a draggable point on the object specified by `hparent`. `x` and `y` are both scalars that together specify the initial position of the point.


`h = impoint(..., param,val)` creates a draggable point, specifying parameters and corresponding values that control the behavior of the point. The following table lists the parameter available. Parameter names can be abbreviated, and case does not matter.

Parameter	Description
'PositionConstraintFcn'	Function handle <code>fcn</code> that is called whenever the point is dragged using the mouse. You can use this


Parameter	Description
	function to control where the point can be dragged. See the help for the <code>setPositionConstraintFcn</code> method for information about valid function handles.

Interactive Behavior

When you call `impoint` with an interactive syntax, the pointer changes to a cross

hairs  when over the image. Click and drag the mouse to specify the position of the point. The point supports a context menu that you can use to control aspects of its appearance and behavior. The following table describes the interactive behavior of the point, including the right-click context menu options.



Interactive Behavior	Description
Moving the point.	Move the mouse pointer over the point. The mouse pointer changes to a fleur shape  . Click and drag the mouse to move the point.
Changing the color used to display the point.	Move the mouse pointer over the point. Right-click and select Set Color from the context menu and specify the color you want to use.
Retrieving the coordinates of the point.	Move the mouse pointer over the point. Right-click and select Copy Position from the context menu to copy a 1-by-2 array to the clipboard specifying the coordinates of the point [X Y].
Deleting the point	Move the pointer on top of the point. Right-click and select Delete from the context menu. To remove this option from the context menu, set the <code>Deletable</code> property to false: <code>h = impoint(); h.Deletable = false;</code>

Methods

The following lists the methods supported by the `impoint` object. Type `methods impoint` to see a complete list of all the methods.

addNewPositionCallback — Add new-position callback to ROI object

See `imroi` for information.

delete — Delete ROI object

See `imroi` for information.

getColor — Get color used to draw ROI object

See `imroi` for information.

getPosition — Return current position of point

`pos = getPosition(h)` returns the current position of the point `h`. The returned position, `pos`, is a two-element vector [x y].

getPositionConstraintFcn — Return function handle to current position constraint function

See `imroi` for information.

removeNewPositionCallback — Remove new-position callback from ROI object.

See `imroi` for information.

resume — Resume execution of MATLAB command line

See `imroi` for information.

setColor — Set color used to draw ROI object

See `imroi` for information.

setConstrainedPosition — Set ROI object to new position

See `imroi` for information.

setPosition — Set point to new position

`setPosition(h, pos)` sets the point `h` to a new position. The new position, `pos`, has the form, `[x y]`.

`setPosition(h, new_x, new_y)` sets the point `h` to a new position. `new_x` and `new_y` are both scalars that together specify the position of the point.

setPositionConstraintFcn — Set position constraint function of ROI object.

See `imroi` for information.

setString — Set text label for point

`setString(h, s)` sets a text label for the point `h`. The string, `s`, is placed to the lower right of the point.

wait — Block MATLAB command line until ROI creation is finished

See `imroi` for information.

Examples

Example 1

Use `impoint` methods to set custom color, set a label, enforce a boundary constraint, and update position in title as point moves.

```
figure, imshow rice.png
h = impoint(gca,100,200);
% Update position in title using newPositionCallback
addNewPositionCallback(h,@(h) title(sprintf('%1.0f,%1.0f',h(1),h(2))));
% Construct boundary constraint function
fcn = makeConstrainToRectFcn('impoint',get(gca,'XLim'),get(gca,'YLim'));
% Enforce boundary constraint function using setPositionConstraintFcn
setPositionConstraintFcn(h,fcn);
setColor(h,'r');
setString(h,'Point label');
```

Example 2

Interactively place a point. Use `wait` to block the MATLAB command line. Double-click on the point to resume execution of the MATLAB command line.

```
figure, imshow('pout.tif');
h = impoint(gca,[]);
position = wait(h);
```

More About

Tips

If you use `impoint` with an axes that contains an image object, and do not specify a drag constraint function, users can drag the point outside the extent of the image and lose the point. When used with an axes created by the `plot` function, the axes limits automatically expand to accommodate the movement of the point.

See Also

`imellipse` | `imline` | `impoly` | `imrect` | `imroi` | `imfreehand` | `makeConstrainToRectFcn`

Introduced before R2006a

impoly

Create draggable, resizable polygon

Syntax

```
h = impoly
h = impoly(hparent)
h = impoly(hparent, position)
h = impoly(..., param1, val1, ...)
```

Description

`h = impoly` begins interactive placement of a polygon on the current axes. The function returns `h`, a handle to an `impoly` object. The polygon has a context menu associated with it that controls aspects of its appearance and behavior—see “Interactive Behavior” on page 1-842. Right-click on the polygon to access this context menu.

`h = impoly(hparent)` begins interactive placement of a polygon on the object specified by `hparent`. `hparent` specifies the HG parent of the polygon graphics, which is typically an axes but can also be any other object that can be the parent of an `hggroup`.


`h = impoly(hparent, position)` creates a draggable, resizable polygon on the object specified by `hparent`. `position` is an n -by-2 array that specifies the initial position of the vertices of the polygon. `position` has the form `[X1,Y1;...;XN,YN]`.


`h = impoly(..., param1, val1, ...)` creates a draggable, resizable polygon, specifying parameters and corresponding values that control the behavior of the polygon. The following table lists available parameters. Parameter names can be abbreviated, and case does not matter.

Parameter	Description
'Closed'	Scalar logical that controls whether the polygon is closed. When set to <code>true</code> (the default), <code>impoly</code> creates a closed polygon, that is, it draws a straight


Parameter	Description
	line between the last vertex specified and the first vertex specified to create a closed region. When <code>Closed</code> is <code>false</code> , <code>impoly</code> does not connect the last vertex with the first vertex, creating an open polygon (or polyline).
'PositionConstraintFcn'	Function handle <code>fcn</code> that is called whenever the object is dragged using the mouse. You can use this function to control where the line can be dragged. See the help for the <code>setPositionConstraintFcn</code> method for information about valid function handles.





Interactive Behavior

When you call `impoly` with an interactive syntax, the pointer changes to a cross hairs  when over the image. Click and drag the mouse to define the vertices of the polygon and adjust the size, shape, and position of the polygon. The polygon also supports a context menu that you can use to control aspects of its appearance and behavior. The choices in the context menu vary whether you position the pointer on an edge of the polygon (or anywhere inside the region) or on one of the vertices. The following figure shows the context menu when the pointer is on the polygon, not on a vertex.



The following table lists the interactive behaviors supported by `impoly`.

Interactive Behavior	Description
Closing the polygon.	<p>Use any of the following mechanisms:</p> <ul style="list-style-type: none"> • Move the pointer over the initial vertex of the polygon that you selected. The pointer changes to a circle . Click either mouse button. • Double-click the left mouse button. This action creates a vertex at the point under the mouse and draws a straight line connecting this vertex with the initial vertex. • Click the right mouse button. This action draws a line connecting the last vertex selected with the initial vertex; it does not create a new vertex.

Interactive Behavior	Description
Adding a new vertex.	Move the pointer over an edge of the polygon and press the A key. The shape of the pointer changes  . Click the left mouse button to create a new vertex at that position on the line.
Moving a vertex. (Reshaping the polygon.)	Move the pointer over a vertex. The pointer changes to a circle  . Click and drag the vertex to its new position.
Deleting a vertex.	Move the pointer over a vertex. The shape changes to a circle  . Right-click and select Delete Vertex from the vertex context menu. This action deletes the vertex and adjusts the shape of the polygon, drawing a new straight line between the two vertices that were neighbors of the deleted vertex.
Deleting the polygon	Move the pointer inside the polygon or on one of the lines that define the polygon, not on a vertex. Right-click and select Delete from the context menu. To remove this option from the context menu, set the Deletable property to false: <code>h = impoly(); h.Deletable = false;</code>
Moving the polygon.	Move the pointer inside the polygon. The pointer changes to a fleur shape  . Click and drag the mouse to move the polygon.
Changing the color of the polygon	Move the pointer inside the polygon. Right-click and select Set Color from the context menu.
Retrieving the coordinates of the vertices	Move the pointer inside the polygon. Right-click and select Copy Position from the context menu. <code>impoly</code> copies an <i>n</i> -by-2 array containing the <i>x</i> - and <i>y</i> -coordinates of each vertex to the clipboard. <i>n</i> is the number of vertices you specified.

Methods

Each `impoly` object supports a number of methods, listed below. Methods inherited from the base class are links to that class.

addNewPositionCallback — Add new-position callback to ROI object

See `imroi` for information.

createMask — Create mask within image

See `imroi` for information.

delete — Delete ROI object

See `imroi` for information.

getColor — Get color used to draw ROI object

See `imroi` for information.

getPosition — Return current position of polygon

`pos = getPosition(h)` returns the current position of the polygon `h`. The returned position, `pos`, is an N-by-2 array [`X1 Y1; . . . ; XN YN`].

getPositionConstraintFcn — Return function handle to current position constraint function

See `imroi` for information.

removeNewPositionCallback — Remove new-position callback from ROI object.

See `imroi` for information.

resume — Resume execution of MATLAB command line

See `imroi` for information.

setClosed — Set geometry of polygon

`setClosed(TF)` sets the geometry of the polygon. `TF` is a logical scalar. `true` means that the polygon is closed. `false` means that the polygon is an open polyline.

setColor — Set color used to draw ROI object

See `imroi` for information.

setPosition — Set ROI object to new position

See `imroi` for information.

setPosition — Set polygon to new position

`setPosition(h, pos)` sets the polygon `h` to a new position. The new position, `pos`, is an n -by-2 array, `[x1 y1; ..; xn yn]` where each row specifies the position of a vertex of the polygon.

setPositionConstraintFcn — Set position constraint function of ROI object.

See `imroi` for information.

setVerticesDraggable — Control whether vertices may be dragged

`setVerticesDraggable(h, TF)` sets the interactive behavior of the vertices of the polygon `h`. `TF` is a logical scalar. `True` means that the vertices of the polygon are draggable. `False` means that the vertices of the polygon are not draggable.

wait — Block MATLAB command line until ROI creation is finished

See `imroi` for information.


Examples

Draw Polygon on Image and Specify Position Constraint Function

Draw a polygon on an image and specify a position constraint function using `makeConstrainToRectFcn` to keep the polygon inside the original `xlim` and `ylim` ranges. Display updated position of the polygon in the title.


Display image.

```
figure
imshow('gantrycrane.png');
```



Draw polygon on the image, specifying location of vertices.

```
h = impoly(gca, [188,30; 189,142; 93,141; 13,41; 14,29]);
```




Get the API associated with the polygon so that you can modify properties of the polygon.

```
api = iptgetapi(h);
```

Set the color of the polygon to yellow.

```
api.setColor('yellow');
```


Color of polygon changed to yellow



Define a function for the new position callback. This function displays the current position of the polygon whenever it is moved.

```
api.addNewPositionCallback(@(p) title(mat2str(p,3)));
```


Title with current position of polygon



Create the function that constrains the movement of the polygon, specifying the boundary of the image as the limits, and then set the value of the `setPositionConstraintFcn` property.

```
fcn = makeConstrainToRectFcn('impoly',get(gca,'XLim'),get(gca,'YLim'));
api.setPositionConstraintFcn(fcn);
```



Can't move polygon past image border



Interactively Create a Polygon by Clicking to Specify Vertex Locations

Display image.


```
figure  
imshow('gantrycrane.png');
```



Create a polygon, specifying several vertices, but leave it unfinished so that you can finish it interactively. The example sets `Closed` to `false` so that the polygon is left open. When you move the cursor over one of the endpoints of the polygon, the cursor shape changes to a circle.


```
h = impoly(gca,[203,30; 202,142; 294,142], 'Closed',false);
```

Cursor changes to circle.



Complete the polygon. Grab one of the ends of the existing lines. Extend the line by dragging it to another corner of the shape you want to create. Then, while positioning the cursor over the line, press the **A** key to add a vertex to the line. Once you create the vertex you can drag it anywhere you want to create the shape you want. Continue dragging the line and adding vertices as you want. For more information, see “Interactive Behavior” on page 1-842.

Press and hold the A key to get the add vertex cursor. Then drag the new vertex where desired.



See also

`imellipse`, `imfreehand`, `imline`, `impoint`, `imrect`, `imroi`,
`makeConstrainToRectFcn`

More About

Tips

If you use `impoly` with an axes that contains an image object, and do not specify a position constraint function, users can drag the polygon outside the extent of the image and lose the polygon. When used with an axes created by the `plot` function, the axes limits automatically expand when the polygon is dragged outside the extent of the axes.

Introduced in R2007b

impositionrect

Create draggable position rectangle

Syntax

```
H = impositionrect(hparent,position)
```

Note This function is obsolete and may be removed in future versions. Use `imrect` instead.

Description

`H = impositionrect(hparent,position)` creates a position rectangle on the object specified by `hparent`. The function returns `H`, a handle to the position rectangle, which is an `hggroup` object. `hparent` specifies the `hggroup`'s parent, which is typically an axes object, but can also be any other object that can be the parent of an `hggroup`. `position` is a four-element position vector that specifies the initial location of the rectangle. `position` has the form `[XMIN YMIN WIDTH HEIGHT]`.

All measurements are in units specified by the `Units` property axes object. When you do not specify the `position` argument, `impositionrect` uses `[0 0 1 1]` as the default value.

API Function Syntaxes

A position rectangle contains a structure of function handles, called an API, that can be used to manipulate it. To retrieve this structure from the position rectangle, use the `iptgetapi` function.

```
API = iptgetapi(H)
```

The following lists the functions in the position rectangle API in the order they appear in the API structure.

Function	Description
setPosition	<p>Sets the position rectangle to a new position.</p> <pre>api.setPosition(new_position)</pre> <p>where <code>new_position</code> is a four-element position vector.</p>
getPosition	<p>Returns the current position of the position rectangle.</p> <pre>position = api.getPosition()</pre> <p><code>position</code> is a four-element position vector.</p>
delete	<p>Deletes the position rectangle associated with the API.</p> <pre>api.delete()</pre>
setColor	<p>Sets the color used to draw the position rectangle.</p> <pre>api.setColor(new_color)</pre> <p>where <code>new_color</code> can be a three-element vector specifying an RGB triplet, or a text string specifying the long or short names of a predefined color, such as 'white' or 'w'. For a complete list of these predefined colors and their short names, see ColorSpec.</p>
addNewPositionCallback	<p>Adds the function handle <code>fun</code> to the list of new-position callback functions.</p> <pre>id = api.addNewPositionCallback(fun)</pre> <p>Whenever the position rectangle changes its position, each function in the list is called with the syntax:</p> <pre>fun(position)</pre> <p>The return value, <code>id</code>, is used only with <code>removeNewPositionCallback</code>.</p>

Function	Description
<code>removeNewPositionCallback</code>	<p>Removes the corresponding function from the new-position callback list.</p> <pre>api.removeNewPositionCallback(id)</pre> <p>where <code>id</code> is the identifier returned by <code>api.addNewPositionCallback</code></p>
<code>setDragConstraintCallback</code>	<p>Sets the drag constraint function to be the specified function handle, <code>fcn</code>.</p> <pre>api.setDragConstraintCallback(fcn)</pre> <p>Whenever the position rectangle is moved because of a mouse drag, the constraint function is called using the syntax:</p> <pre>constrained_position = fcn(new_position)</pre> <p>where <code>new_position</code> is a four-element position vector. This allows a client, for example, to control where the position rectangle may be dragged.</p>

Examples

Display in the command window the updated position of the position rectangle as it moves in the axes.

```
close all, plot(1:10)
h = impositionrect(gca, [4 4 2 2]);
api = iptgetapi(h);
api.addNewPositionCallback(@(p) disp(p));
```

Constrain the position rectangle to move only up and down.

```
close all, plot(1:10)
h = impositionrect(gca, [4 4 2 2]);
api = getappdata(h, 'API');
api.setDragConstraintCallback(@(p) [4 p(2:4)]);
```

Specify the color of the position rectangle.

```
close all, plot(1:10)
```



```
h = impositionrect(gca, [4 4 2 2]);  
api = iptgetapi(h, 'API');  
api.setColor([1 0 0]);
```

When the position rectangle occupies only a few pixels on the screen, the rectangle is drawn in a different style to increase its visibility.

```
close all, imshow cameraman.tif  
h = impositionrect(gca, [100 100 10 10]);
```

More About

Tips

A position rectangle can be dragged interactively using the mouse. When the position rectangle occupies a small number of screen pixels, its appearance changes to aid visibility.

The position rectangle has a context menu associated with it that you can use to copy the current position to the clipboard and change the color used to display the rectangle.

See Also

`iptgetapi`

Introduced before R2006a

improfile

Pixel-value cross-sections along line segments

Syntax

```
improfile
improfile(n)
improfile(I,xi,yi)
improfile(I,xi,yi,n)
c = improfile( ___ )
[ cx,cy,c ] = improfile(I,xi,yi,n)
[ cx,cy,c,xi,yi ] = improfile(I,xi,yi,n)
[ ___ ] = improfile(x,y,I,xi,yi)
[ ___ ] = improfile(x,y,I,xi,yi,n)
[ ___ ] = improfile( ___,method)
```

Description

`improfile` retrieves the intensity values of pixels along a line or a multiline path in the grayscale, binary, or RGB image in the current axes and displays a plot of the intensity values. If the specified path consists of a single line segment, `improfile` creates a two-dimensional plot of intensity values versus the distance along the line segment. If the path consists of two or more line segments, `improfile` creates a three-dimensional plot of the intensity values versus their x - and y -coordinates.

With this syntax, you specify the line or path using the mouse, by clicking points in the image. Press **Backspace** or **Delete** to remove the previously selected point. To finish selecting points, adding a final point, press shift-click, right-click, or double-click. To finish selecting points without adding a final point, press **Return**.

`improfile(n)` retrieves the intensity values, where n specifies the number of points to include. If you do not provide this argument, `improfile` chooses a value for n , roughly equal to the number of pixels the path traverses.

`improfile(I,xi,yi)` retrieves pixel intensity values, where I specifies an image, and xi and yi are equal-length vectors specifying the spatial coordinates of the endpoints of the line segments.

`improfile(I,xi,yi,n)` returns pixel intensity values, where `n` specifies the number of points to include.

`c = improfile(____)` returns the intensity values in `c`, an `n`-by-1 vector, if the input is a grayscale intensity image, or an `n`-by-1-by-3 array if the input is an RGB image.

`[cx,cy,c] = improfile(I,xi,yi,n)` additionally returns the spatial coordinates of the pixels, `cx` and `cy`, of length `n`.

`[cx,cy,c,xi,yi] = improfile(I,xi,yi,n)` additionally returns two equal-length vectors specifying the spatial coordinates of the endpoints of the line segments. `xi` and `yi`.

`[____] = improfile(x,y,I,xi,yi)` enables the definition of a nondefault spatial coordinate system by specifying two, 2-element vector, `x` and `y`, containing the image `XData` and `YData`.

`[____] = improfile(x,y,I,xi,yi,n)` defines a nondefault spatial coordinate system and specifies the number of points to include, `n`.

`[____] = improfile(____,method)` specifies the interpolation method:

- 'nearest' — Nearest-neighbor interpolation (the default)
- 'bilinear' — Bilinear interpolation
- 'bicubic' — Bicubic interpolation

Class Support

The input image can be `uint8`, `uint16`, `int16`, `single`, `double`, or `logical`. All other inputs and outputs must be `double`.

Examples

Plot Multisegment Line from Image

Read image.


```
I = imread('liftingbody.png');
```

Specify x - and y -coordinates that define line segments.

```
x = [19 427 416 77];  
y = [96 462 37 33];
```

Display 3-D plot of the pixel values of these line segments.

```
improfile(I,x,y),grid on;
```



See Also

[improfile](#) | [interp2](#)

Introduced before R2006a

imputfile


Display Save Image dialog box

Syntax

```
[filename, ext, user_canceled] = imputfile
```

Description

[filename, ext, user_canceled] = imputfile displays the Save Image dialog box (shown below) which you can use to specify the full path and format of a file. Using the dialog box, you can navigate to folders in a file system and select a particular file or specify the name of a new file. imputfile limits the types of files displayed in the dialog box to the image file format selected in the Files of Type menu.



When you click **Save**, `imputfile` returns the full path to the file in `filename` and the file type selected from the Files of Type menu in `ext`. `imputfile` does not automatically add a file name extension (such as `.jpg`) to the file name.

If the user clicks **Cancel** or closes the Save Image dialog box, `imputfile` returns, setting `user_canceled` to `True` (1), and setting `filename` and `ext` to empty strings; otherwise, `user_canceled` is `False` (0).

Note: The Save Image dialog box is modal; it blocks the MATLAB command line until you click **Save** or cancel the operation.

See Also

`imformats` | `imsave` | `imtool` | `imgetfile`

Introduced in R2007b

impyramid

Image pyramid reduction and expansion

Syntax

```
B = impyramid(A,direction)
```

Description

`B = impyramid(A,direction)` computes a Gaussian pyramid reduction or expansion of `A` by one level, where `direction` determines whether it's a reduction or an expansion.

“Code Generation” on page 1-868 support: Yes.

“MATLAB Function Block” on page 1-868 support: Yes.

Examples

Compute Four-level Multiresolution Pyramid of Image

Read image into the workspace.

```
I = imread('cameraman.tif');
```

Perform a series of reductions. The first call reduces the original image. The other calls to `impyramid` use the previously reduced image.

```
I1 = impyramid(I, 'reduce');  
I2 = impyramid(I1, 'reduce');  
I3 = impyramid(I2, 'reduce');
```

View the original image and the reduced versions.

```
figure, imshow(I)  
figure, imshow(I1)  
figure, imshow(I2)
```

figure, imshow(I3)





Input Arguments

A — Image to reduced or expanded

numeric or logical array

Image to reduced or expanded, specified as a numeric or logical array.

Example: `I = imread('cameraman.tif'); I1 = impyramid(I,'reduce');`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32` | `logical`

direction — Reduction or expansion

'reduce' | 'expand'

Reduction or expansion, specified as one of the following strings.

String	Description
'reduce'	Return an image, smaller than the original image.

String	Description
'expand'	Return an image that is larger than the original image.

Example: `I = imread('cameraman.tif'); I1 = impyramid(I,'reduce');`

Data Types: char

Output Arguments

B — Reduced or expanded image

numeric or logical array

Reduced or expanded image, returned as a numeric or logical array, the same class as A.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, note the following:

- `direction` must be a compile-time constant.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

Algorithms

If A is m -by- n and `direction` is 'reduce', the size of B is $\text{ceil}(M/2)$ -by- $\text{ceil}(N/2)$. If `direction` is 'expand', the size of B is $(2*M-1)$ -by- $(2*N-1)$.

Reduction and expansion take place only in the first two dimensions. For example, if A is 100-by-100-by-3 and `direction` is 'reduce', then B is 50-by-50-by-3.

Note that `impyramid` uses the kernel specified on page 533 of the Burt and Adelson paper cited below:

$w = \left[\frac{1}{4} - \frac{\alpha}{2}, \frac{1}{4}, \alpha, \frac{1}{4}, \frac{1}{4} - \frac{\alpha}{2} \right]$, where $\alpha = 0.375$. The parameter α is chosen to be 0.375 so that the equivalent weighting function is close to a Gaussian shape and the weights can be readily applied using fixed-point arithmetic.

References

- [1] Burt and Adelson, "The Laplacian Pyramid as a Compact Image Code," IEEE Transactions on Communications, vol. COM-31, no. 4, April 1983, pp. 532-540.
- [2] Burt, "Fast Filter Transforms for Image Processing," Computer Graphics and Image Processing, vol. 16, 1981, pp. 20-51

See Also

`imresize`

Introduced in R2007b

imquantize

Quantize image using specified quantization levels and output values

Syntax

```
quant_A = imquantize(A,levels)
quant_A = imquantize( ____,values)
[quant_A,index] = imquantize( ____ )
```

Description

`quant_A = imquantize(A,levels)` quantizes image `A` using specified quantization values contained in the `N` element vector `levels`. Output image `quant_A` is the same size as `A` and contains `N + 1` discrete integer values in the range 1 to `N + 1` which are determined by the following criteria:

- If $A(k) \leq \text{levels}(1)$, then $\text{quant_A}(k) = 1$.
- If $\text{levels}(m-1) < A(k) \leq \text{levels}(m)$, then $\text{quant_A}(k) = m$.
- If $A(k) > \text{levels}(N)$, then $\text{quant_A}(k) = N + 1$.

Note that `imquantize` assigns values to the two implicitly defined end intervals:

- $A(k) \leq \text{levels}(1)$
- $A(k) > \text{levels}(N)$

`quant_A = imquantize(____,values)` adds the `N + 1` element vector `values` where `N = length(levels)`. Each of the `N + 1` elements of `values` specify the quantization value for one of the `N + 1` discrete pixel values in `quant_A`.

- If $A(k) \leq \text{levels}(1)$, then $\text{quant_A}(k) = \text{values}(1)$.
- If $\text{levels}(m-1) < A(k) \leq \text{levels}(m)$, then $\text{quant_A}(k) = \text{values}(m)$.
- If $A(k) > \text{levels}(N)$, then $\text{quant_A}(k) = \text{values}(N + 1)$.

`[quant_A,index] = imquantize(____)` returns an array `index` such that:

```
quant_A = values(index)
```

“Code Generation” on page 1-880 support: Yes.

“MATLAB Function Block” on page 1-881 support: Yes.


Examples

Segment Image into Three Levels Using Two Thresholds

Read image and display it.

```
I = imread('circlesBrightDark.png');  
imshow(I)  
axis off  
title('Original Image')
```

Original Image



Calculate two threshold levels.

```
thresh = multithresh(I,2);
```


Segment the image into three levels using `imquantize` .

```
seg_I = imquantize(I,thresh);
```

Convert segmented image into color image using `label2rgb` and display it.

```
RGB = label2rgb(seg_I);  
figure;  
imshow(RGB)  
axis off  
title('RGB Segmented Image')
```

RGB Segmented Image



Compare Thresholding Entire Image Versus Plane-by-Plane Thresholding

Read truecolor (RGB) image and display it.

```
I = imread('peppers.png');
```



```
imshow(I)
axis off
title('RGB Image');
```

RGB Image



Generate thresholds for seven levels from the entire RGB image.

```
threshRGB = multithresh(I,7);
```

Generate thresholds for each plane of the RGB image.

```
threshForPlanes = zeros(3,7);
```

```
for i = 1:3
```

```

    threshForPlanes(i,:) = multithresh(I(:,:,i),7);
end

```

Process the entire image with the set of threshold values computed from entire image.

```

value = [0 threshRGB(2:end) 255];
quantRGB = imquantize(I, threshRGB, value);

```

Process each RGB plane separately using the threshold vector computed from the given plane. Quantize each RGB plane using threshold vector generated for that plane.

```

quantPlane = zeros( size(I) );

for i = 1:3
    value = [0 threshForPlanes(i,2:end) 255];
    quantPlane(:,:,i) = imquantize(I(:,:,i),threshForPlanes(i,:),value);
end

```

```

quantPlane = uint8(quantPlane);


```

Display both posterized images and note the visual differences in the two thresholding schemes.

```

imshowpair(quantRGB,quantPlane,'montage')
axis off
title('Full RGB Image Quantization          Plane-by-Plane Quantization')

```



To compare the results, calculate the number of unique RGB pixel vectors in each output image. Note that the plane-by-plane thresholding scheme yields about 23% more colors than the full RGB image scheme.

```
dim = size( quantRGB );
quantRGBmx3 = reshape(quantRGB, prod(dim(1:2)), 3);
quantPlanemx3 = reshape(quantPlane, prod(dim(1:2)), 3);

colorsRGB = unique(quantRGBmx3, 'rows' );
colorsPlane = unique(quantPlanemx3, 'rows' );

disp(['Unique colors in RGB image : ' int2str(length(colorsRGB))]);
disp(['Unique colors in Plane-by-Plane image : ' int2str(length(colorsPlane))]);

Unique colors in RGB image : 188
Unique colors in Plane-by-Plane image : 231
```

Threshold grayscale image from 256 to 8 levels

Reduce the number of discrete levels in an image from 256 to 8. This example uses two different methods for assigning values to each of the eight output levels.

Read image and display it.

```
I = imread('coins.png');
imshow(I)
axis off
title('Grayscale Image')
```

Grayscale Image



Split the image into eight levels by obtaining seven thresholds from `multithresh`.

```
thresh = multithresh(I,7);
```

Construct the `valuesMax` vector such that the maximum value in each quantization interval is assigned to the eight levels of the output image.

```
valuesMax = [thresh max(I(:))]  
[quant8_I_max, index] = imquantize(I,thresh,valuesMax);
```

```
valuesMax =
```

```
65  88  119  149  169  189  215  255
```

Similarly, construct the `valuesMin` vector such that the minimum value in each quantization interval is assigned to the eight levels of the output image. Instead of calling `imquantize` again with the vector `valuesMin`, use the output argument `index` to assign those values to the output image.


```
valuesMin = [min(I(:)) thresh]
quant8_I_min = valuesMin(index);
```

```
valuesMin =
```

```
    23    65    88   119   149   169   189   215
```

Display both eight-level output images side by side.

```
imshowpair(quant8_I_min,quant8_I_max,'montage')
title('Minimum Interval Value           Maximum Interval Value')
```



Input Arguments

A — Input image

image

Input image, specified as a numeric array of any dimension.

Data Types: single | double | int8 | int16 | int32 | int64 | uint8 | uint16 | uint32 | uint64

levels — Quantization levels

vector

Quantization levels, specified as an N element vector. Values of the discrete quantization levels must be in monotonically increasing order.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

values — Quantization values

vector

Quantization values, specified as an $N + 1$ element vector.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

Output Arguments

quant_A — Quantized output image

image

Quantized output image, returned as a numeric array the same size as A . If input argument *values* is specified, then *quant_A* is the same data type as *values*. If *values* is not specified, then *quant_A* is of class `double`.

index — Mapping array

array

Mapping array, returned as an array the same size as input image A . It contains integer indices which access *values* to construct the output image: `quant_A = values(index)`. If input argument *values* is not defined, then `index = quant_A`.

Data Types: `double`

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`label2rgb` | `multithresh` | `rgb2ind`

Introduced in R2012b

imreconstruct

Morphological reconstruction

Syntax

```
IM = imreconstruct(marker,mask)
IM = imreconstruct(marker,mask,conn)
IM = imreconstruct(gpuarrayMarker,gpuarrayMask)
```

Description

`IM = imreconstruct(marker,mask)` performs morphological reconstruction of the image `marker` under the image `mask`. The arguments `marker` and `mask` can be intensity images or binary images with the same size. The returned image `IM` is the same as the input image. Elements of `marker` must be less than or equal to the corresponding elements of `mask`. If values in `marker` are greater than corresponding elements in `mask`, `imreconstruct` clips the values to the `mask` level. Both input images must be 2-D. The optional connectivity argument (`conn`) can be 4 or 8. If not specified, `imreconstruct` uses a 4-connected neighborhood.

`IM = imreconstruct(marker,mask,conn)` performs morphological reconstruction with the specified connectivity.

`IM = imreconstruct(gpuarrayMarker,gpuarrayMask)` performs morphological reconstruction on a GPU. The input marker image and mask image must be `gpuArrays`. This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-888 support: Yes.


“MATLAB Function Block” on page 1-889 support: Yes.

Examples

Perform Opening-by-Reconstruction to Identify High Intensity Objects


Read a grayscale image and display it.


```
I = imread('snowflakes.png');  
figure  
imshow(I)
```



Adjust the contrast of the image to create the mask image and display results.


```
mask = adapthisteq(I);  
figure  
imshow(mask)
```



Create a marker image that identifies high-intensity objects in the image using morphological erosion and display results.


```
se = strel('disk',5);
```

```
marker = imerode(mask,se);  
imshow(marker)
```



Perform morphological opening on the mask image, using the marker image to identify high-intensity objects in the mask. Display results.


```
obr = imreconstruct(marker,mask);  
figure  
imshow(obr, [])
```



Use Reconstruction to Segment an Image

Read a logical image into workspace and display it. This is the mask image.

```
mask = imread('text.png');  
figure  
imshow(mask)
```




Create a marker image that identifies the object in the image you want to extract through segmentation. For this example, identify the "w" in the word "watershed".

```
marker = false(size(mask));  
marker(13,94) = true;
```

Perform segmentation of the mask image using the marker image.

```
im = imreconstruct(marker,mask);  
figure  
imshow(im)
```



Use Reconstruction to Segment an Image on a GPU

Read mask image and create gpuArray.

```
mask = gpuArray(imread('text.png'));  
figure, imshow(mask),
```

Create marker image gpuArray.

```
marker = gpuArray.false(size(mask));  
marker(13,94) = true;
```

Perform the segmentation and display the result.

```
im = imreconstruct(marker,mask);
```

```
figure, imshow(im)
```

Input Arguments

marker — Input image

nonsparse numeric or logical array

Input image, specified as a nonsparse numeric or logical array.

Example: `se = strel('disk',5); marker = imerode(mask,se);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

mask — Mask image

nonsparse numeric or logical array

Mask image, specified as a nonsparse numeric or logical array.

Example: `mask = imread('text.png');`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

conn — Connectivity

8 (for 2-D images) (default) | 4 | 6 | 18 | 26 | 3-by-3-by- ... -by-3 matrix

Connectivity, specified as one of the values in this table.

Value	Meaning
Two-dimensional connectivities	
4	4-connected neighborhood
8	8-connected neighborhood
Three-dimensional connectivities	
6	6-connected neighborhood
18	18-connected neighborhood
26	26-connected neighborhood

Connectivity can also be defined in a more general way for any dimension by using for `conn` a 3-by-3-by- ... -by-3 matrix of 0s and 1s. The 1-valued elements define

neighborhood locations relative to the center element of `conn`. Note that `conn` must be symmetric about its center element.

Example: `obr = imreconstruct(marker,mask,4);`

Data Types: `double` | `logical`

gpuarrayMarker — Input image on a GPU

`gpuArray`

Input image on a GPU, specified as a `gpuArray`.

Example: `marker = gpuArray(imread('text.png'));`

gpuarrayMask — Mask image on a GPU

`gpuArray`

Mask image on a GPU, specified as a `gpuArray`.

Example: `mask = gpuArray(imread('text.png'));`

Output Arguments

IM — Reconstructed image

numeric or logical array

Reconstructed image, returned as a numeric or logical array, depending on the input image, that is the same size as the input image.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic `MATLAB Host Computer` target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, the optional third input argument, `conn`, must be a compile-time constant, and can only take the value `4` or `8`.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

Tips

- Morphological reconstruction is the algorithmic basis for several other Image Processing Toolbox functions, including `imclearborder`, `imextendedmax`, `imextendedmin`, `imfill`, `imhmax`, `imhmin`, and `imimposemin`.
- **Performance note:** This function may take advantage of hardware optimization for data types `logical`, `uint8`, and `single` to run faster. Hardware optimization requires `marker` and `mask` to be 2-D images and `conn` to be either 4 or 8.

Algorithms

`imreconstruct` uses the fast hybrid grayscale reconstruction algorithm described in [1].

- “Understanding Morphological Reconstruction”

References

- [1] Vincent, L., "Morphological Grayscale Reconstruction in Image Analysis: Applications and Efficient Algorithms," *IEEE Transactions on Image Processing*, Vol. 2, No. 2, April, 1993, pp. 176-201.

See Also

`imclearborder` | `imextendedmax` | `imextendedmin` | `imfill` | `imhmax` | `imhmin` | `imimposemin`

Introduced before R2006a

imrect

Create draggable rectangle

Syntax

```
h = imrect
h = imrect(hparent)
h = imrect(hparent, position)
h = imrect(..., param1, val1,...)
```

Description

`h = imrect` begins interactive placement of a rectangle on the current axes. The function returns `h`, a handle to an `imrect` object. The rectangle has a context menu associated with it that controls aspects of its appearance and behavior—see “Interactive Behavior” on page 1-891. Right-click on the rectangle to access this context menu.


`h = imrect(hparent)` begins interactive placement of a rectangle on the object specified by `hparent`. `hparent` specifies the HG parent of the rectangle graphics, which is typically an axes but can also be any other object that can be the parent of an `hggroup`.


`h = imrect(hparent, position)` creates a draggable rectangle on the object specified by `hparent`. `position` is a four-element vector that specifies the initial size and location of the rectangle. `position` has the form `[xmin ymin width height]`.

`h = imrect(..., param1, val1,...)` creates a draggable rectangle, specifying parameters and corresponding values that control the behavior of the rectangle. The following table lists the parameter available. Parameter names can be abbreviated, and case does not matter.


Parameter	Description
'PositionConstraintFcn'	Function handle <code>fcn</code> that is called whenever the mouse is dragged. You can use this function to control where the rectangle can be dragged. See the help for the <code>setPositionConstraintFcn</code> method for information about valid function handles.


Interactive Behavior

When you call `imrect` with an interactive syntax, the pointer changes to a cross hairs  when over the image. You can create the rectangle and adjust its size and position using the mouse. The rectangle also supports a context menu that you can use to control aspects of its appearance and behavior. The following figure shows the rectangle.



The following table lists the interactive behaviors supported by `imrect`.

Interactive Behavior	Description
Moving the rectangle.	Move the pointer inside the rectangle. The pointer changes to a fleur shape  . Click and drag the mouse to move the rectangle.

Interactive Behavior	Description
Resizing the rectangle.	Move the pointer over any of the edges or corners of the rectangle, the shape changes to a double-ended arrow,  . Click and drag the edge or corner using the mouse.
Changing the color of the rectangle.	Move the pointer inside the rectangle. Right-click and select Set Color from the context menu.
Retrieving the coordinates of the current position	Move the pointer inside the polygon. Right-click and select Copy Position from the context menu. <code>imrect</code> copies a four-element position vector to the clipboard.
Preserve the current aspect ratio of the rectangle during interactive resizing.	Move the pointer inside the rectangle. Right-click and select Fix Aspect Ratio from the context menu.
Deleting the rectangle	Move the pointer inside the rectangle or on an edge of the rectangle. Right-click and select Delete from the context menu. To remove this option from the context menu, set the <code>Deletable</code> property to false: <code>h = imrect(); h.Deletable = false;</code>

Methods

Each `imrect` object supports a number of methods, listed below. Type methods `imrect` to see a list of the methods.

addNewPositionCallback — Add new-position callback to ROI object

See `imroi` for information.

createMask — Create mask within image

See `imroi` for information.

delete — Delete ROI object

See `imroi` for information.

getColor — Get color used to draw ROI object

See `imroi` for information.

getPosition — Return current position of rectangle

`pos = getPosition(h)` returns the current position of the rectangle `h`. The returned position, `pos`, is a 1-by-4 array [`xmin` `ymin` `width` `height`].

getPositionConstraintFcn — Return function handle to current position constraint function

See `imroi` for information.

removeNewPositionCallback — Remove new-position callback from ROI object.

See `imroi` for information.

resume — Resume execution of MATLAB command line

See `imroi` for information.

setColor — Set color used to draw ROI object

See `imroi` for information.

setConstrainedPosition — Set ROI object to new position

See `imroi` for information.

setFixedAspectRatioMode — Control whether aspect ratio preserved during resize

`setFixedAspectRatioMode(h,TF)` sets the interactive resize behavior of the rectangle `h`. `TF` is a logical scalar. `True` means that the current aspect ratio is preserved during interactive resizing. `False` means that interactive resizing is not constrained.

setPosition — Set rectangle to new position

`setPosition(h,pos)` sets the rectangle `h` to a new position. The new position, `pos`, has the form [`xmin` `ymin` `width` `height`].

setPositionConstraintFcn — Set position constraint function of ROI object

See `imroi` for information.

setResizable — Set resize behavior of rectangle

`setResizable(h,TF)` sets whether the rectangle `h` may be resized interactively. `TF` is a logical scalar.

wait — Block MATLAB command line until ROI creation is finished

See `imroi` for information.

Examples

Example 1

Display updated position in the title. Specify a position constraint function using `makeConstrainToRectFcn` to keep the rectangle inside the original `Xlim` and `Ylim` ranges.

```
figure, imshow('cameraman.tif');  
h = imrect(gca, [10 10 100 100]);  
addNewPositionCallback(h,@(p) title(mat2str(p,3)));  
fcn = makeConstrainToRectFcn('imrect',get(gca,'XLim'),get(gca,'YLim'));  
setPositionConstraintFcn(h,fcn);
```

Now drag the rectangle using the mouse.

Example 2

Interactively place a rectangle by clicking and dragging. Use `wait` to block the MATLAB command line. Double-click on the rectangle to resume execution of the MATLAB command line.

```
figure, imshow('pout.tif');  
h = imrect;  
position = wait(h);
```

More About

Tips

If you use `imrect` with an axes that contains an image object, and do not specify a position constraint function, users can drag the rectangle outside the extent of the image. When used with an axes created by the `plot` function, the axes limits automatically expand to accommodate the movement of the rectangle.

When the API function `setResizable` is used to make the rectangle non-resizable, the **Fix Aspect Ratio** context menu item is not provided.

See Also

`imellipse` | `imline` | `imfreehand` | `impoint` | `impoly` | `imroi` | `makeConstrainToRectFcn`

Introduced before R2006a

imref2d class

Reference 2-D image to world coordinates

Description

An `imref2d` object encapsulates the relationship between the intrinsic coordinates anchored to the rows and columns of a 2-D image and the spatial location of the same row and column locations in a world coordinate system. The image is sampled regularly in the planar world- X and world- Y coordinate system such that intrinsic- X values align with world- X values, and intrinsic- Y values align with world- Y values. The pixel spacing from row to row need not equal the pixel spacing from column to column.

The intrinsic coordinate values (x,y) of the center point of any pixel are identical to the values of the column and row subscripts for that pixel. For example, the center point of the pixel in row 5, column 3 has intrinsic coordinates $x = 3.0$, $y = 5.0$. Be aware, however, that the order of coordinate specification $(3.0,5.0)$ is reversed in intrinsic coordinates relative to pixel subscripts $(5,3)$. Intrinsic coordinates are defined on a continuous plane while the subscript locations are discrete locations with integer values.

“Code Generation” on page 1-901 support: Yes.

“MATLAB Function Block” on page 1-901 support: Yes.

Construction

`R = imref2d()` creates an `imref2d` object with default property settings.

`R = imref2d(imageSize)` creates an `imref2d` object given an image size. This syntax constructs a spatial referencing object for the default case in which the world coordinate system is co-aligned with the intrinsic coordinate system.

`R = imref2d(imageSize,pixelExtentInWorldX,pixelExtentInWorldY)` creates an `imref2d` object given an image size and the resolution in each dimension, specified by `pixelExtentInWorldX` and `pixelExtentInWorldY`.

`R = imref2d(imageSize,xWorldLimits,yWorldLimits)` creates an `imref2d` object given an image size and the world coordinate limits in each dimension, specified by `xWorldLimits` and `yWorldLimits`.

Input Arguments

imageSize

Size of the image associated with the object, specified as a row vector of class `double`, such as `[256 256]`, as returned by the `size` function.

pixelExtentInWorldX

Size of a single pixel in *X* dimension measured in the world coordinate system, specified as a `double`.

pixelExtentInWorldY

Size of a single pixel in *Y* dimension measured in the world coordinate system, specified as a `double`.

xWorldLimits

Minimum and maximum coordinate values in *X* dimension in world coordinate system, specified as a two-element numeric vector, such as `[0.5 256.5]`.

yWorldLimits

Minimum and maximum coordinate values in *Y* in world coordinate system, specified as a two-element numeric vector, such as `[0.5 256.5]`.

Properties

ImageExtentInWorldX

Span of image in *X* dimension in the world coordinate system, specified as a numeric scalar. The `imref2d` object calculates this value as `PixelExtentInX * ImageSize(2)`.

ImageExtentInWorldY

Span of image in Y dimension in the world coordinate system, specified as a numeric scalar. The `imref2d` object calculates this value as `PixelExtentInY * ImageSize(1)`.

ImageSize

Number of elements in each spatial dimension, specified as a two-element vector, in the same form as that returned by the `size` function.

PixelExtentInWorldX

Size of a single pixel in X dimension measured in the world coordinate system, specified as a `double`.

PixelExtentInWorldY

Size of a single pixel in Y dimension measured in the world coordinate system, specified as a `double`.

XWorldLimits

Limits of image in world X dimension, specified as a two-element row vector [`xMin` `xMax`].

YWorldLimits

Limits of image in world Y dimension, specified as a two-element row vector [`yMin` `yMax`].

XIntrinsicLimits

Limits of image in intrinsic units in X dimension, specified as a two-element row vector [`xMin` `xMax`]. For an M -by- N image (or an M -by- N -by- P image) it equals [`0.5`, $N + 0.5$].

YIntrinsicLimits

Limits of image in intrinsic units in Y dimension, specified as a two-element row vector [`yMin` `yMax`]. For an M -by- N image (or an M -by- N -by- P image) it equals [`0.5`, $M + 0.5$].

Methods

<code>contains</code>	True if image contains points in world coordinate system
<code>intrinsicToWorld</code>	Convert from intrinsic to world coordinates
<code>sizesMatch</code>	True if object and image are size-compatible
<code>worldToIntrinsic</code>	Convert from world to intrinsic coordinates
<code>worldToSubscript</code>	Convert world coordinates to row and column subscripts

Copy Semantics

Value. To learn how value classes affect copy operations, see [Copying Objects in the MATLAB documentation](#).

Examples

Create `imref2d` Object Given Knowledge of Image Size and World Limits

Read image.


```
A = imread('pout.tif');
```

Create an `imref2d` object, specifying the size and world limits of the image with which you want to associate the object.

```
xWorldLimits = [2 5];
yWorldLimits = [3 6];
RA = imref2d(size(A),xWorldLimits,yWorldLimits);
```

Display the image, specifying the spatial referencing object. Note how the axes coordinates reflect the world coordinates.

```
figure, imshow(A,RA);
```



Create `imref2d` Object Given Knowledge of Image Size and Resolution

Read image.

```
m = dicominfo('knee1.dcm');  
A = dicomread(m);
```

Create an `imref2d` object associated with the image, specifying the size of the pixels. The DICOM file contains a metadata field `PixelSpacing` that specifies the image resolution in each dimension in millimeters/pixel.

```
RA = imref2d(size(A),m.PixelSpacing(2),m.PixelSpacing(1))
```

```
RA =
```

```
imref2d with properties:
```

```
    XWorldLimits: [0.1563 160.1563]  
    YWorldLimits: [0.1563 160.1563]  
    ImageSize: [512 512]  
PixelExtentInWorldX: 0.3125  
PixelExtentInWorldY: 0.3125
```

```
ImageExtentInWorldX: 160
ImageExtentInWorldY: 160
  XIntrinsicLimits: [0.5000 512.5000]
  YIntrinsicLimits: [0.5000 512.5000]
```

Examine the extent of the image in each dimension in millimeters.

```
RA.ImageExtentInWorldX
RA.ImageExtentInWorldY
```

```
ans =
```

```
    160
```

```
ans =
```

```
    160
```

Additional Capabilities

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, you can only specify singular objects—arrays of objects are not supported.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

[imref3d](#) | [imshow](#) | [imwarp](#)

contains

Class: `imref2d`

True if image contains points in world coordinate system

Syntax

`TF = contains(R,xWorld,yWorld)`

Description

`TF = contains(R,xWorld,yWorld)` returns a logical array `TF` having the same size as `xWorld`, `yWorld`, such that `TF(k)` is true if and only if the point `(xWorld(k),yWorld(k))` falls within the bounds of the image associated with spatial referencing object `R`.

Input Arguments

R

Spatial referencing object, `imref2d`, associated with an image.

xWorld

Coordinates along the *X* dimension in world system, specified as a numeric scalar or vector

yWorld

Coordinates along the *Y* dimension in world system, specified as a numeric scalar or vector

Output Arguments

TF

Logical scalar or vector, the same size as the input values.

Examples

Check if Image Contains Specified World Coordinates

Read an image.

```
I = imread('cameraman.tif');
```

Create an `imref2d` object and associate it with the image.

```
R = imref2d(size(I))
```

```
R =
```

```
imref2d
```

```
Properties:
```

```
    XWorldLimits: [0.5000 256.5000]
    YWorldLimits: [0.5000 256.5000]
    ImageSize: [256 256]
PixelExtentInWorldX: 1
PixelExtentInWorldY: 1
ImageExtentInWorldX: 256
ImageExtentInWorldY: 256
    XIntrinsicLimits: [0.5000 256.5000]
    YIntrinsicLimits: [0.5000 256.5000]
```

Test to see if certain world coordinates are in the image.

```
res = contains(R,[5 8],[5 10])
```

```
res =
```

```
    1    1
```

Try some coordinates that are deliberately outside the image.

```
res = contains(R,[5 8],[5 257])
```

```
res =
```

```
    1    0
```

intrinsicToWorld

Class: `imref2d`

Convert from intrinsic to world coordinates

Syntax

```
[xWorld,yWorld] = intrinsicToWorld(R,xIntrinsic,yIntrinsic)
```

Description

`[xWorld,yWorld] = intrinsicToWorld(R,xIntrinsic,yIntrinsic)` maps point locations from the intrinsic system (`xIntrinsic`, `yIntrinsic`) to the world system (`xWorld`, `yWorld`) based on the relationship defined by the spatial referencing object `R`. If the input includes values that fall outside the limits of the image in the intrinsic system, the `intrinsicToWorld` method extrapolates `worldX` and `worldY` outside the bounds of the image in the world system.

Input Arguments

R

Spatial referencing object, `imref2d`, associated with an image.

xIntrinsic

Coordinate in *X* dimension in intrinsic system, specified as a numeric scalar or vector

yIntrinsic

Coordinate in *Y* dimension in intrinsic system, specified as a numeric scalar or vector

Output Arguments

xWorld

Coordinates along the X dimension in world system, specified as a numeric scalar or vector

yWorld

Coordinates along the Y dimension in world system, specified as a numeric scalar or vector

Examples

Convert Intrinsic Coordinates to World Coordinates

Read an image.

```
I = imread('cameraman.tif');
```

Create an `imref2d` object and associate it with the image.

```
R = imref2d(size(I))
```

```
R =
```

```
imref2d
```

```
Properties:
```

```
    XWorldLimits: [0.5000 256.5000]
    YWorldLimits: [0.5000 256.5000]
      ImageSize: [256 256]
PixelExtentInWorldX: 1
PixelExtentInWorldY: 1
ImageExtentInWorldX: 256
ImageExtentInWorldY: 256
    XIntrinsicLimits: [0.5000 256.5000]
    YIntrinsicLimits: [0.5000 256.5000]
```

Convert intrinsic coordinates to world coordinates. In this example, intrinsic coordinates align with world coordinates.

```
[val1 val2] = intrinsicToWorld(R,5,5)
```

val1 =

5

val2 =

5

sizesMatch

Class: `imref2d`

True if object and image are size-compatible

Syntax

`TF = sizesMatch(R,A)`

Description

`TF = sizesMatch(R,A)` returns `true` if the size of the image `A` is consistent with the `ImageSize` property of the spatial referencing object `R`. That is, `R.ImageSize == [size(A,1) size(A,2)]`.

Input Arguments

R

Spatial referencing object, `imref2d`, associated with an image.

A

Input image

Output Arguments

TF

Logical array. True if the size of the image `A` is consistent with the referencing object `R`.

Examples

Check Image Size with Spatial Referencing Object

Read an image.

```
I = imread('cameraman.tif');
```

Create an `imref2d` object.

```
R = imref2d(size(I))
```

```
R =
```

```
imref2d
```

```
Properties:
```

```
    XWorldLimits: [0.5000 256.5000]
    YWorldLimits: [0.5000 256.5000]
      ImageSize: [256 256]
PixelExtentInWorldX: 1
PixelExtentInWorldY: 1
ImageExtentInWorldX: 256
ImageExtentInWorldY: 256
    XIntrinsicLimits: [0.5000 256.5000]
    YIntrinsicLimits: [0.5000 256.5000]
```

See if the size of the image matches the size in the object.

```
res = sizesMatch(R,I)
```

```
res =
```

```
    1
```

Read another image that is a different size.

```
I2 = imread('coins.png');
```

Check if the size of this image matches the size in the object. It should return `false`.

```
res2 = sizesMatch(R,I2)
```

```
res2 =
```

```
    0
```

worldToIntrinsic

Class: `imref2d`

Convert from world to intrinsic coordinates

Syntax

```
[xIntrinsic,yIntrinsic] = worldToIntrinsic(R,xWorld,yWorld)
```

Description

`[xIntrinsic,yIntrinsic] = worldToIntrinsic(R,xWorld,yWorld)` maps point locations from the world system (`xWorld`, `yWorld`) to the intrinsic system (`xIntrinsic`, `yIntrinsic`) based on the relationship defined by the spatial referencing object `R`. If the input includes values that fall outside the limits of the image in the world system, the `worldToIntrinsic` method extrapolates `xWorld` and `yWorld` outside the bounds of the image in the intrinsic system.

Input Arguments

R

Spatial referencing object, `imref2d`, associated with an image.

xWorld

Coordinates in *X* dimension in world system, specified as a numeric scalar or vector.

yWorld

Coordinate in *Y* dimension in world system, specified as a numeric scalar or vector.

Output Arguments

xIntrinsic

Coordinates in *X* dimension in intrinsic system, returned as a numeric scalar or vector.

yIntrinsic

Coordinates in *Y* dimension in intrinsic system, returned as a numeric scalar or vector.

Examples

Convert World Coordinates to Intrinsic

Read an image.

```
I = imread('cameraman.tif');
```

Create an `imref2d` object.

```
R = imref2d(size(I))
```

```
R =
```

```
imref2d
```

```
Properties:
```

```
    XWorldLimits: [0.5000 256.5000]
    YWorldLimits: [0.5000 256.5000]
      ImageSize: [256 256]
PixelExtentInWorldX: 1
PixelExtentInWorldY: 1
ImageExtentInWorldX: 256
ImageExtentInWorldY: 256
  XIntrinsicLimits: [0.5000 256.5000]
  YIntrinsicLimits: [0.5000 256.5000]
```

Convert coordinates from world to intrinsic. In this example, world coordinates align with intrinsic coordinates.

```
[xi yi] = worldToIntrinsic(R,5,5)
```

```
xi =
```

```
5
```

```
yi =
```


worldToSubscript

Class: `imref2d`

Convert world coordinates to row and column subscripts

Syntax

`[I,J] = worldToSubscript(R,xWorld,yWorld)`

Description

`[I,J] = worldToSubscript(R,xWorld,yWorld)` maps point locations from the world system (`xWorld,yWorld`) to subscript arrays `I` and `J` based on the relationship defined by the spatial referencing object `R`. `I` and `J` are the row and column subscripts of the image pixels identified by their world coordinates (`xWorld, yWorld`). `xWorld` and `yWorld` must have the same size. `I` and `J` have the same size as `xWorld` and `yWorld`.

For an m -by- n image, $1 \leq I \leq m$ and $1 \leq J \leq n$. If a point `xWorld(k)`, `yWorld(k)` falls outside the image, as defined by `contains(R,xWorld,yWorld)`, `worldToSubscript` sets the returned subscripts, `I(k)` and `J(k)`, to `NaN`.

Input Arguments

R

Spatial referencing object, `imref2d`, associated with an image.

xWorld

Coordinates along the X dimension in world system, specified as a numeric scalar or vector

yWorld

Coordinates along the Y dimension in world system, specified as a numeric scalar or vector

Output Arguments

I

Row coordinates, returned as a numeric scalar or vector the same size as `yWorld`.

J

Column coordinates, returned as a numeric scalar or vector, the same size as `xWorld`.

Examples

Convert World Coordinates to Subscripts

Read an image.

```
I = imread('cameraman.tif');
```

Create an `imref2d` object and associate it with the image.

```
R = imref2d(size(I))
```

```
R =
```

```
imref2d
```

```
Properties:
```

```

    XWorldLimits: [0.5000 256.5000]
    YWorldLimits: [0.5000 256.5000]
    ImageSize: [256 256]
PixelExtentInWorldX: 1
PixelExtentInWorldY: 1
ImageExtentInWorldX: 256
ImageExtentInWorldY: 256
    XIntrinsicLimits: [0.5000 256.5000]
    YIntrinsicLimits: [0.5000 256.5000]
```

Convert the world coordinates to subscripts. Note that, when expressed as subscripts, the order of the coordinates is reversed.

```
[m n] = worldToSubscript(R,100,200)
```

```
m =
```

200

n =

100

imref3d class

Reference 3-D image to world coordinates

Description

An `imref3d` object encapsulates the relationship between the intrinsic coordinates anchored to the columns, rows, and planes of a 3-D image and the spatial location of the same column, row, and plane locations in a world coordinate system. The image is sampled regularly in the planar world- X , world- Y , and world- Z coordinates of the coordinate system such that intrinsic- X values align with world- X values, intrinsic- Y values align with world- Y values, and intrinsic- Z values align with world- Z values. The pixel spacing in each dimension may be different.

The intrinsic coordinate values (x,y,z) of the center point of any pixel are identical to the values of the column, row, and plane subscripts for that pixel. For example, the center point of the pixel in row 5, column 3, plane 4 has intrinsic coordinates $x = 3.0$, $y = 5.0$, $z = 4.0$. Be aware, however, that the order of the coordinate specification (3.0,5.0,4.0) is reversed in intrinsic coordinates relative to pixel subscripts (5,3,4). Intrinsic coordinates are defined on a continuous plane while the subscript locations are discrete locations with integer values.

“Code Generation” on page 1-919 support: Yes.

“MATLAB Function Block” on page 1-919 support: Yes.

Construction

`R = imref3d()` creates an `imref3d` object with default property settings.

`R = imref3d(imageSize)` creates an `imref3d` object given an image size. This syntax constructs a spatial referencing object for the default case in which the world coordinate system is co-aligned with the intrinsic coordinate system.

`R =`

`imref3d(imageSize,pixelExtentInWorldX,pixelExtentInWorldY,pixelExtentInWorldZ)`
creates an `imref3d` object given an image size and the resolution in each

dimension, specified by `pixelExtentInWorldX`, `pixelExtentInWorldY`, and `pixelExtentInWorldZ`.

`R = imref3d(imageSize,xWorldLimits,yWorldLimits,zWorldLimits)` creates an `imref3d` object given an image size and the world limits in each dimension, specified by `xWorldLimits`, `yWorldLimits` and `zWorldLimits`.

Input Arguments

imageSize

Size of the image associated with the object, specified as a three-element row vector of class `double`, such as `[128 128 27]`, as returned by the `size` function.

PixelExtentInWorldX

Size of a single pixel in X dimension measured in the world coordinate system, specified as a `double`.

PixelExtentInWorldY

Size of a single pixel in Y dimension measured in the world coordinate system, specified as a `double`.

PixelExtentInWorldZ

Size of a single pixel in Z dimension measured in the world coordinate system, specified as a `double`.

xWorldLimits

Minimum and maximum coordinate values in X dimension in world coordinate system, specified as a two-element numeric vector of class `double`, such as `[0.5 256.5]`.

yWorldLimits

Minimum and maximum coordinate values in Y in world coordinate system, specified as a two-element numeric vector of class `double`, such as `[0.5 256.5]`.

zWorldLimits

Minimum and maximum coordinate values in Z in world coordinate system, specified as a two-element numeric vector of class `double`, such as `[0.5 256.5]`.

Properties

ImageExtentInWorldX

Span of image in X dimension in the world coordinate system, specified as a numeric scalar. The `imref3d` object calculates this value as `PixelExtentInX * ImageSize(2)`.

ImageExtentInWorldY

Span of image in Y dimension in the world coordinate system, specified as a numeric scalar. The `imref3d` object calculates this value as `PixelExtentInY * ImageSize(1)`.

ImageExtentInWorldZ

Span of image in Z dimension in the world coordinate system, specified as a numeric scalar. The `imref3d` object calculates this value as `PixelExtentInZ * ImageSize(3)`.

ImageSize

Number of elements in each spatial dimension, specified as a three-element vector, in the same form as that returned by the `size` function.

PixelExtentInWorldX

Size of a single pixel in X dimension measured in the world coordinate system, specified as a `double`.

PixelExtentInWorldY

Size of a single pixel in Y dimension measured in the world coordinate system, specified as a `double`.

PixelExtentInWorldZ

Size of a single pixel in Z dimension measured in the world coordinate system, specified as a `double`.

XWorldLimits

Limits of image in world X , specified as a two-element row vector, [`xMin` `xMax`].

YWorldLimits

Limits of image in world Y , specified as a two-element row vector, `[yMin yMax]`.

ZWorldLimits

Limits of image in world Z , specified as a two-element row vector, `[zMin zMax]`.

XIntrinsicLimits

Limits of image in intrinsic units in X dimension, specified as a two-element row vector `[xMin xMax]`. For an M -by- N -by- P image, it equals `[0.5, N + 0.5]`.

YIntrinsicLimits

Limits of image in intrinsic units in Y dimension, specified as a two-element row vector `[yMin yMax]`. For an M -by- N -by- P image, it equals `[0.5, M + 0.5]`.

ZIntrinsicLimits

Limits of image in intrinsic units in Z dimension, specified as a two-element row vector `[zMin zMax]`. For an M -by- N -by- P image, it equals `[0.5, P + 0.5]`.

Methods

<code>contains</code>	True if image contains points in world coordinate system
<code>intrinsicToWorld</code>	Convert from intrinsic to world coordinates
<code>sizesMatch</code>	True if object and image are size-compatible
<code>worldToIntrinsic</code>	Convert from world to intrinsic coordinates
<code>worldToSubscript</code>	World coordinates to row and column subscripts

Additional Capabilities

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, you can only specify singular objects—arrays of objects are not supported.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

Copy Semantics

Value. To learn how value classes affect copy operations, see Copying Objects in the MATLAB documentation.

Examples

Create `imref3d` Object Given Knowledge of Image Size and Resolution in each Dimension

Read image.

```
m = analyze75info('brainMRI.hdr');  
A = analyze75read(m);
```

Create an `imref3d` object associated with the image, specifying the size of the pixels. The `PixelDimensions` field of the metadata of the file specifies the resolution in each dimension in millimeters/pixel.

```
RA = imref3d(size(A),m.PixelDimensions(2),m.PixelDimensions(1),m.PixelDimensions(3));
```

```
RA =
```

```
imref3d with properties:
```

```
XWorldLimits: [0.5000 128.5000]
YWorldLimits: [0.5000 128.5000]
ZWorldLimits: [0.5000 27.5000]
    ImageSize: [128 128 27]
PixelExtentInWorldX: 1
PixelExtentInWorldY: 1
PixelExtentInWorldZ: 1
ImageExtentInWorldX: 128
ImageExtentInWorldY: 128
ImageExtentInWorldZ: 27
    XIntrinsicLimits: [0.5000 128.5000]
    YIntrinsicLimits: [0.5000 128.5000]
    ZIntrinsicLimits: [0.5000 27.5000]
```

Examine the extent of the image in each dimension in millimeters.

```
RA.ImageExtentInWorldX
RA.ImageExtentInWorldY
RA.ImageExtentInWorldZ
```

```
ans =
```

```
    128
```

```
ans =
```

```
    128
```

```
ans =
```

```
    27
```

See Also

[imref2d](#)

contains

Class: `imref3d`

True if image contains points in world coordinate system

Syntax

`TF = contains(R,xWorld,yWorld,zWorld)`

Description

`TF = contains(R,xWorld,yWorld,zWorld)` returns a logical array `TF` having the same size as `xWorld`, `yWorld`, and `zWorld` such that `TF(k)` is true if and only if the point `(xWorld(k), yWorld(k), zWorld(k))` falls within the bounds of the image associated with spatial referencing object `R`.

Input Arguments

R

Spatial referencing object, `imref3d`, associated with an image.

xWorld

Coordinate in the *X* dimension, specified as a numeric scalar or vector.

yWorld

Coordinate in the *Y* dimension, specified as a numeric scalar or vector.

zWorld

Coordinate in the *Z* dimension, specified as a numeric scalar or vector.

Default:

Output Arguments

TF

Logical scalar or vector, the same size as the input values.

Examples

Check if Image Contains Specified World Coordinates

Read an image.

```
I = imread('cameraman.tif');
```

Create an `imref3d` object and associate it with the image.

```
R3d = imref3d(size(I))
```

R =

```
imref3d
```

Properties:

```
    XWorldLimits: [0.5000 512.5000]
    YWorldLimits: [0.5000 384.5000]
    ZWorldLimits: [0.5000 3.5000]
    ImageSize: [384 512 3]
PixelExtentInWorldX: 1
PixelExtentInWorldY: 1
PixelExtentInWorldZ: 1
ImageExtentInWorldX: 512
ImageExtentInWorldY: 384
ImageExtentInWorldZ: 3
    XIntrinsicLimits: [0.5000 512.5000]
    YIntrinsicLimits: [0.5000 384.5000]
    ZIntrinsicLimits: [0.5000 3.5000]
```

Test to see if certain world coordinates are in the image.

```
res = contains(R,5,5,1)
```

```
res =
```


1

Try a point that is deliberately outside the image.

```
res = contains(R,513,5,1)
```

```
res =
```

0

intrinsicToWorld

Class: `imref3d`

Convert from intrinsic to world coordinates

Syntax

```
[xWorld, yWorld, zWorld] =  
intrinsicToWorld(R,xIntrinsic,yIntrinsic,zIntrinsic)
```

Description

```
[xWorld, yWorld, zWorld] =  
intrinsicToWorld(R,xIntrinsic,yIntrinsic,zIntrinsic)
```

 maps point locations from the intrinsic system (`xIntrinsic`, `yIntrinsic`, `zIntrinsic`) to the world system (`xWorld`, `yWorld`, `zWorld`) based on the relationship defined by the spatial referencing object `R`. If the input includes values that fall outside the limits of the image in the intrinsic system, the `intrinsicToWorld` method extrapolates `worldX`, `worldY`, and `worldZ` outside the bounds of the image in the world system.

Input Arguments

R

Spatial referencing object, `imref3d`, associated with an image.

xIntrinsic

Coordinate in *X* dimension in intrinsic system, specified as a numeric scalar or vector

yIntrinsic

Coordinate in *Y* dimension in intrinsic system, specified as a numeric scalar or vector

zIntrinsic

Coordinate in *Z* dimension in intrinsic system, specified as a numeric scalar or vector

Output Arguments

xWorld

Coordinates along the *X* dimension in world system, returned as a numeric scalar or vector the same size as `xIntrinsic`.

yWorld

Coordinates along the *Y* dimension in world system, returned as a numeric scalar or vector the same size as `xIntrinsic`.

zWorld

Coordinates along the *Z* dimension in world system, returned as a numeric scalar or vector the same size as `xIntrinsic`.

Examples

Convert Intrinsic Coordinates to World Coordinates

Read an image.

```
I = imread('peppers.png');
```

Create an `imref3d` object and associate it with the image.

```
R = imref3d(size(I))
```

```
R =
```

```
imref3d
```

```
Properties:
```

```
    XWorldLimits: [0.5000 512.5000]  
    YWorldLimits: [0.5000 384.5000]  
    ZWorldLimits: [0.5000 3.5000]  
      ImageSize: [384 512 3]  
PixelExtentInWorldX: 1  
PixelExtentInWorldY: 1  
PixelExtentInWorldZ: 1  
ImageExtentInWorldX: 512
```

```
ImageExtentInWorldY: 384
ImageExtentInWorldZ: 3
  XIntrinsicLimits: [0.5000 512.5000]
  YIntrinsicLimits: [0.5000 384.5000]
  ZIntrinsicLimits: [0.5000 3.5000]
```

Convert intrinsic coordinates to world coordinates. In this example, intrinsic coordinates align with world coordinates.

```
[x y z] = intrinsicToWorld(R,5,5,3)
```

```
x =
```

```
5
```

```
y =
```

```
5
```

```
z =
```

```
3
```

sizesMatch

Class: `imref3d`

True if object and image are size-compatible

Syntax

`TF = sizesMatch(R,A)`

Description

`TF = sizesMatch(R,A)` returns true if the size of the image `A` is consistent with the `ImageSize` property of the spatial referencing object `R`. That is, `R.ImageSize == [size(A,1) size(A,2) size(A,3)]`.

Input Arguments

R

Spatial referencing object, `imref3d`, associated with an image.

A

Input image

Output Arguments

TF

Logical scalar

Examples

Check if Image and Spatial Referencing Object Are Size-Compatible

Read an image.

```
I = imread('peppers.png');
```

Create an `imref3d` object and associate it with the image.

```
R = imref3d(size(I))
```

```
R =
```

```
imref3d
```

```
Properties:
```

```
    XWorldLimits: [0.5000 512.5000]
    YWorldLimits: [0.5000 384.5000]
    ZWorldLimits: [0.5000 3.5000]
    ImageSize: [384 512 3]
PixelExtentInWorldX: 1
PixelExtentInWorldY: 1
PixelExtentInWorldZ: 1
ImageExtentInWorldX: 512
ImageExtentInWorldY: 384
ImageExtentInWorldZ: 3
    XIntrinsicLimits: [0.5000 512.5000]
    YIntrinsicLimits: [0.5000 384.5000]
    ZIntrinsicLimits: [0.5000 3.5000]
```

Check if the size of the image matches the size in the object.

```
tf = sizesMatch(R,I)
```

```
tf =
```

```
    1
```

Read another image that is a different size.

```
I2 = imread('coins.png');
```

Check if the size of this image matches the size in the object. It should return `false`.

```
tf = sizesMatch(R,I2)
```

```
tf =
```

```
    0
```

worldToIntrinsic

Class: `imref3d`

Convert from world to intrinsic coordinates

Syntax

```
[xIntrinsic,yIntrinsic,zIntrinsic] =  
worldToIntrinsic(R,xWorld,yWorld,zWorld)
```

Description

```
[xIntrinsic,yIntrinsic,zIntrinsic] =  
worldToIntrinsic(R,xWorld,yWorld,zWorld)
```

 maps point locations from the world system (`xWorld`, `yWorld`, `zWorld`) to the intrinsic system (`xIntrinsic`, `yIntrinsic`, `zIntrinsic`) based on the relationship defined by the spatial referencing object `R`. If the input includes values that fall outside the limits of the image in the world system, the `worldToIntrinsic` method extrapolates `worldX`, `worldY`, and `worldZ` outside the bounds of the image in the intrinsic system.

Input Arguments

R

Spatial referencing object, `imref3d`, associated with an image.

xWorld

Coordinates along the *X* dimension in world system, specified as a numeric scalar or vector

yWorld

Coordinates along the *Y* dimension in world system, specified as a numeric scalar or vector

zWorld

Coordinates along the Z dimension in world system, specified as a numeric scalar or vector

Output Arguments

xIntrinsic

Coordinates in X dimension in intrinsic system, returned as a numeric scalar or vector.

yIntrinsic

Coordinates in Y dimension in intrinsic system, returned as a numeric scalar or vector.

zIntrinsic

Coordinates in Z dimension in intrinsic system, returned as a numeric scalar or vector.

Examples

Illustrate the world to intrinsic method

Read an image.

```
I = imread('peppers.png');
```

Create an `imref3d` object associated with the image.

```
R = imref3d(size(I))
```

```
R =
```

```
imref3d
```

```
Properties:
```

```
    XWorldLimits: [0.5000 512.5000]
```

```
    YWorldLimits: [0.5000 384.5000]
```

```
    ZWorldLimits: [0.5000 3.5000]
```

```
    ImageSize: [384 512 3]
```

```
PixelExtentInWorldX: 1
```



```
PixelExtentInWorldY: 1
PixelExtentInWorldZ: 1
ImageExtentInWorldX: 512
ImageExtentInWorldY: 384
ImageExtentInWorldZ: 3
  XIntrinsicLimits: [0.5000 512.5000]
  YIntrinsicLimits: [0.5000 384.5000]
  ZIntrinsicLimits: [0.5000 3.5000]
```

Convert coordinates from world to intrinsic. In this example, world coordinates align with intrinsic coordinates.

```
[x y z] = worldToIntrinsic(R,5,5,3)
```

```
x =
```

```
    5
```

```
y =
```

```
    5
```

```
z =
```

```
    3
```

worldToSubscript

Class: `imref3d`

World coordinates to row and column subscripts

Syntax

```
[I,J,K] = worldToSubscript(R,xWorld,yWorld,zWorld)
```

Description

`[I,J,K] = worldToSubscript(R,xWorld,yWorld,zWorld)` maps point locations from the world system (`xWorld,yWorld,zWorld`) to subscript arrays `I`, `J`, and `K`, based on the relationship defined by the spatial referencing object `R`. `I`, `J`, and `K` are the row, column, and plane subscripts of the image voxels identified by their world coordinates (`xWorld`, `yWorld`, `zWorld`). `xWorld`, `yWorld`, and `zWorld` must have the same size. `I`, `J`, and `K` have the same size as `xWorld`, `yWorld`, and `zWorld`. For an m -by- n -by- p image, $1 \leq I \leq M$, $1 \leq J \leq N$, and $1 \leq K \leq P$. If a point `xWorld(k)`, `yWorld(k)`, `zWorld(k)` falls outside the image, as defined by `contains(R,xWorld, yWorld, zWorld)`, `worldToSubscript` sets the returned subscripts, `I(k)`, `J(k)`, and `K(k)` to `NaN`.

Input Arguments

R

Spatial referencing object, `imref3d`, associated with an image.

xWorld

Coordinates along the X dimension in world system, specified as a numeric scalar or vector

yWorld

Coordinates along the Y dimension in world system, specified as a numeric scalar or vector

zWorld

Coordinates along the Z dimension in world system, specified as a numeric scalar or vector

Output Arguments

I

Row coordinates, returned as a numeric scalar or vector the same size as `yWorld`.

J

Column coordinates, returned as a numeric scalar or vector the same size as `xWorld`.

K

Plane coordinates, returned as a numeric scalar or vector the same size as `zWorld`.

Examples

Convert World Coordinates to Subscripts

Read an image.

```
I = imread('peppers.png');
```

Create an `imref3d` object and associate it with the image.

```
R = imref3d(size(I))
```

```
R =
```

```
imref3d
```

```
Properties:
```

```
  XWorldLimits: [0.5000 512.5000]
```

```
  YWorldLimits: [0.5000 384.5000]
```

```
  ZWorldLimits: [0.5000 3.5000]
```

```
    ImageSize: [384 512 3]
```

```
PixelExtentInWorldX: 1
```

```
PixelExtentInWorldY: 1
PixelExtentInWorldZ: 1
ImageExtentInWorldX: 512
ImageExtentInWorldY: 384
ImageExtentInWorldZ: 3
  XIntrinsicLimits: [0.5000 512.5000]
  YIntrinsicLimits: [0.5000 384.5000]
  ZIntrinsicLimits: [0.5000 3.5000]
```

Convert the world coordinates to subscripts.

```
[m n p] = worldToSubscript(R,30,50,3)
```

```
m =
```

```
50
```

```
n =
```

```
30
```

```
p =
```

```
3
```

imregionalmax

Regional maxima

Syntax

```
BW = imregionalmax(I)
BW = imregionalmax(I,conn)
gpuarrayBW = imregionalmax(gpuarrayI, ___ )
```

Description

`BW = imregionalmax(I)` returns the binary image `BW` that identifies the regional maxima in `I`. Regional maxima are connected components of pixels with a constant intensity value, t , whose external boundary pixels all have a value less than t . In `BW`, pixels that are set to 1 identify regional maxima; all other pixels are set to 0.

`BW = imregionalmax(I,conn)` computes the regional maxima, where `conn` specifies the connectivity. By default, `imregionalmax` uses 8-connected neighborhoods for 2-D images and 26-connected neighborhoods for 3-D images.

`gpuarrayBW = imregionalmax(gpuarrayI, ___)` performs the operation on a GPU. The input image must be a `gpuArray`. The function returns a `gpuArray`. This syntax requires Parallel Computing Toolbox.

“Code Generation” on page 1-939 support: Yes.

“MATLAB Function Block” on page 1-939 support: Yes.

Examples

Find Regional Maxima in Simple Sample Image

Create a simple sample image with several regional maxima.

```
A = 10*ones(10,10);
```

```
A(2:4,2:4) = 22;
A(6:8,6:8) = 33;
A(2,7) = 44;
A(3,8) = 45;
A(4,9) = 44
```

```
A =
```

```

10  10  10  10  10  10  10  10  10  10
10  22  22  22  10  10  44  10  10  10
10  22  22  22  10  10  10  45  10  10
10  22  22  22  10  10  10  10  44  10
10  10  10  10  10  10  10  10  10  10
10  10  10  10  10  33  33  33  10  10
10  10  10  10  10  33  33  33  10  10
10  10  10  10  10  33  33  33  10  10
10  10  10  10  10  10  10  10  10  10
10  10  10  10  10  10  10  10  10  10
```

Find the regional maxima. Note that the result includes the regional maxima at (3,8).

```
regmax = imregionalmax(A)
```

```
regmax =
```

```

0  0  0  0  0  0  0  0  0  0
0  1  1  1  0  0  0  0  0  0
0  1  1  1  0  0  0  1  0  0
0  1  1  1  0  0  0  0  0  0
0  0  0  0  0  0  0  0  0  0
0  0  0  0  0  1  1  1  0  0
0  0  0  0  0  1  1  1  0  0
0  0  0  0  0  1  1  1  0  0
0  0  0  0  0  0  0  0  0  0
0  0  0  0  0  0  0  0  0  0
```

Find Regional Maxima in Simple Sample Image on a GPU

Create a 10-by-10 pixel sample image that contains two regional maxima.

```
A = 10*gpuArray.ones(10,10);
```

```

A(2:4,2:4) = 22;    % maxima 12 higher than surrounding pixels
A(6:8,6:8) = 33;    % maxima 23 higher than surrounding pixels
A(2,7) = 44;
A(3,8) = 45;        % maxima 1 higher than surrounding pixels
A(4,9) = 44

```

```
A =
```

```

10  10  10  10  10  10  10  10  10  10
10  22  22  22  10  10  44  10  10  10
10  22  22  22  10  10  10  45  10  10
10  22  22  22  10  10  10  10  44  10
10  10  10  10  10  10  10  10  10  10
10  10  10  10  10  33  33  33  10  10
10  10  10  10  10  33  33  33  10  10
10  10  10  10  10  33  33  33  10  10
10  10  10  10  10  10  10  10  10  10
10  10  10  10  10  10  10  10  10  10

```

Pass the sample image `A` to `imregionalmax`. The function returns a binary image, the same size as `A`, in which pixels with the value 1 represent the regional maxima in `A`. `imregionalmax` sets all other pixels in to 0.

```
regmax = imregionalmax(A)
```

```
regmax =
```

```

0  0  0  0  0  0  0  0  0  0
0  1  1  1  0  0  0  0  0  0
0  1  1  1  0  0  0  1  0  0
0  1  1  1  0  0  0  0  0  0
0  0  0  0  0  0  0  0  0  0
0  0  0  0  0  1  1  1  0  0
0  0  0  0  0  1  1  1  0  0
0  0  0  0  0  1  1  1  0  0
0  0  0  0  0  0  0  0  0  0
0  0  0  0  0  0  0  0  0  0

```

Input Arguments

I — Input image

nonsparse numeric array of any dimension

Input array, specified as a nonsparse numeric array of any dimension.

Example: `I = imread('glass.png'); BW = imregionalmax(I);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

conn — Connectivity

8 (default) | 4 | 6 | 18 | 26 | 3-by-3-by- ...-by-3 matrix of zeroes and ones

Connectivity, specified as a one of the scalar values in the following table. By default, `imregionalmax` uses 8-connected neighborhoods for 2-D images and 26-connected neighborhoods for 3-D images. For higher dimensions, `imregionalmax` uses `conndef(ndims(I), 'maximal')`. Connectivity can be defined in a more general way for any dimension by using for `conn` a 3-by-3-by- ...-by-3 matrix of 0s and 1s. The 1-valued elements define neighborhood locations relative to the center element of `conn`. Note that `conn` must be symmetric around its center element.

Value	Meaning
Two-dimensional connectivities	
4	4-connected neighborhood
8	8-connected neighborhood
Three-dimensional connectivities	
6	6-connected neighborhood
18	18-connected neighborhood
26	26-connected neighborhood

Example: `regmax = imregionalmax(A,4);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

gpuarrayI — Input image for GPU

`gpuArray`

Input image for GPU, specified as a `gpuArray`.

Example: `gpuarrayI = gpuArray(imread('cameraman.tif')); gpuarrayBW = imregionalmax(gpuarrayI);`

Output Arguments

BW — Transformed image

logical array

Transformed image, returned as a logical array the same size as I.

gpuarrayBW — Transformed image

gpuArray

Transformed image, returned as a gpuArray.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, the optional second input argument, `conn`, must be a compile-time constant.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`conndef` | `imextendedmax` | `imhmax` | `imreconstruct` | `imregionalmin`

Introduced before R2006a

imregionalmin

Regional minima

Syntax

```
BW = imregionalmin(I)
BW = imregionalmin(I,conn)
gpuarrayBW = imregionalmin(gpuarrayI, ___ )
```

Description

`BW = imregionalmin(I)` returns the binary image `BW` that identifies the regional minima in `I`. Regional minima are connected components of pixels with a constant intensity value, and whose external boundary pixels all have a higher value. In `BW`, pixels that are set to 1 identify regional minima; all other pixels are set to 0.

`BW = imregionalmin(I,conn)` computes the regional minima, where `conn` specifies the desired connectivity. By default, `imregionalmin` uses 8-connected neighborhoods for 2-D images and 26-connected neighborhoods for 3-D images

`gpuarrayBW = imregionalmin(gpuarrayI, ___)` performs the operation on a GPU. The input image must be a `gpuArray`. The function returns a `gpuArray`. This syntax requires Parallel Computing Toolbox.

“Code Generation” on page 1-944 support: Yes.

“MATLAB Function Block” on page 1-944 support: Yes.

Examples

Find Regional Minima in Simple Sample Image

Create a simple sample array with several regional minima.

```
A = 10*ones(10,10);
A(2:4,2:4) = 3;
A(6:8,6:8) = 8
```

A =

```

10  10  10  10  10  10  10  10  10  10
10  3   3   3   10  10  10  10  10  10
10  3   3   3   10  10  10  10  10  10
10  3   3   3   10  10  10  10  10  10
10  10  10  10  10  10  10  10  10  10
10  10  10  10  10  8   8   8  10  10
10  10  10  10  10  8   8   8  10  10
10  10  10  10  10  8   8   8  10  10
10  10  10  10  10  10  10  10  10  10
10  10  10  10  10  10  10  10  10  10

```

Calculate the regional minima. The function returns a binary image, the same size as the input image, in which pixels with the value 1 represent the regional minima. `imregionalmin` sets all other pixels in to 0.

```
regmin = imregionalmin(A)
```

regmin =

```

0   0   0   0   0   0   0   0   0   0
0   1   1   1   0   0   0   0   0   0
0   1   1   1   0   0   0   0   0   0
0   1   1   1   0   0   0   0   0   0
0   0   0   0   0   0   0   0   0   0
0   0   0   0   0   1   1   1   0   0
0   0   0   0   0   1   1   1   0   0
0   0   0   0   0   1   1   1   0   0
0   0   0   0   0   0   0   0   0   0
0   0   0   0   0   0   0   0   0   0

```

Find Regional Minima in Simple Sample Image on a GPU

Create a 10-by-10 pixel sample image that contains two regional minima.

```

A = 10*gpuArray.ones(10,10);
A(2:4,2:4) = 3;           % minima 3 lower than surround
A(6:8,6:8) = 8           % minima 8 lower than surroundA(6:8,6:8) = 7;

```

A =

```
10  10  10  10  10  10  10  10  10  10
10  3   3   3   3   10  10  10  10  10
10  3   3   3   3   10  10  10  10  10
10  3   3   3   3   10  10  10  10  10
10  10  10  10  10  10  10  10  10  10
10  10  10  10  10  8   8   8   10  10
10  10  10  10  10  8   8   8   10  10
10  10  10  10  10  8   8   8   10  10
10  10  10  10  10  10  10  10  10  10
10  10  10  10  10  10  10  10  10  10
10  10  10  10  10  10  10  10  10  10
```

Pass the sample image `A` to `imregionalmin`. The function returns a binary image, the same size as `A`, in which pixels with the value `1` represent the regional minima in `A`. `imregionalmin` sets all other pixels in to `0`.

```
regmin = imregionalmin(A)
```

```
regmin =
```

```
0   0   0   0   0   0   0   0   0   0
0   1   1   1   0   0   0   0   0   0
0   1   1   1   0   0   0   0   0   0
0   1   1   1   0   0   0   0   0   0
0   0   0   0   0   0   0   0   0   0
0   0   0   0   0   1   1   1   0   0
0   0   0   0   0   1   1   1   0   0
0   0   0   0   0   1   1   1   0   0
0   0   0   0   0   0   0   0   0   0
0   0   0   0   0   0   0   0   0   0
```

Input Arguments

I — Input image

nonsparse numeric array of any dimension

Input array, specified as a nonsparse numeric array of any dimension.

```
Example: I = imread('glass.png'); BW = imregionalmin(I);
```

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

conn — Connectivity

8 (default) | 4 | 6 | 18 | 26 | 3-by-3-by- ...-by-3 matrix of zeroes and ones

Connectivity, specified as a one of the scalar values in the following table. By default, `imregionalmin` uses 8-connected neighborhoods for 2-D images and 26-connected neighborhoods for 3-D images. For higher dimensions, `imregionalmin` uses `conndef(ndims(I), 'maximal')`. Connectivity can be defined in a more general way for any dimension by using for `conn` a 3-by-3-by- ...-by-3 matrix of 0s and 1s. The 1-valued elements define neighborhood locations relative to the center element of `conn`. Note that `conn` must be symmetric about its center element.

Value	Meaning
Two-dimensional connectivities	
4	4-connected neighborhood
8	8-connected neighborhood
Three-dimensional connectivities	
6	6-connected neighborhood
18	18-connected neighborhood
26	26-connected neighborhood

Example: `B = imregionalmin(A,4);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

gpuarrayI — Input image for GPU

`gpuArray`

Input image for GPU, specified as a `gpuArray`.

Example: `gpuarrayI = gpuArray(imread('cameraman.tif')); gpuarrayBW = imregionalmin(gpuarrayI);`

Output Arguments

BW — Transformed image

logical array

Transformed image, returned as a logical array the same size as I.

gpuarrayBW — Transformed image

`gpuArray`

Transformed image, returned as a `gpuArray`.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, the optional second input argument, `conn`, must be a compile-time constant.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`conndef` | `imextendedmin` | `imhmin` | `imimposemin` | `imreconstruct` | `imregionalmax`

Introduced before R2006a

imregconfig

Configurations for intensity-based registration

Syntax

```
[optimizer,metric] = imregconfig(modality)
```

Description

`[optimizer,metric] = imregconfig(modality)` creates `optimizer` and `metric` configurations that you pass to `imregister` to perform intensity-based image registration. `imregconfig` returns `optimizer` and `metric` with default settings to provide a basic registration configuration.

Examples

Create Optimizer and Metric Configurations to Register Images Captured on the Same Device

Load the images into the workspace and display them.

```
fixed = imread('pout.tif');  
moving = imrotate(fixed, 5, 'bilinear', 'crop');  
imshowpair(fixed, moving, 'Scaling', 'joint');
```



Create the optimizer and metric. The two images in this example were captured on the same device, so we'll set the modality to 'monomodal'.

```
[optimizer, metric] = imregconfig('monomodal')  
  
optimizer =  
  
    registration.optimizer.RegularStepGradientDescent  
  
Properties:  
    GradientMagnitudeTolerance: 1.000000e-04  
    MinimumStepLength: 1.000000e-05  
    MaximumStepLength: 6.250000e-02  
    MaximumIterations: 100  
    RelaxationFactor: 5.000000e-01  
  
metric =  
  
    registration.metric.MeanSquares  
  
This class has no properties.
```

Pass `optimizer` and `metric` to `imregister` to perform the registration.


```
movingRegistered = imregister(moving, fixed, 'rigid', optimizer, metric);
```

View the registered images

```
figure  
imshowpair(fixed, movingRegistered, 'Scaling', 'joint');
```



Input Arguments

modality — Image capture modality

'monomodal' | 'multimodal'

Image capture modality describes how your images have been captured, specified as either 'monomodal' (captured on the same device) or 'multimodal' (captured on different devices).

Output Arguments

optimizer — Optimization configuration

optimizer object

Optimization configuration describes the method for optimizing the similarity metric, returned as one of the `optimizer` objects, `registration.optimizer.RegularStepGradientDescent` or `registration.optimizer.OnePlusOneEvolutionary`

metric — Metric configuration

metric object

Metric configuration describes the image similarity metric to be optimized during registration, returned as one of the `metric` objects, `registration.metric.MeanSquares` or `registration.metric.MattesMutualInformation`.

More About

Monomodal

Images captured on the same device. Monomodal images have similar brightness ranges.

Multimodal

Images captured on different devices. Multimodal images usually have different brightness ranges.

Tips

- Your registration results can improve if you adjust the `optimizer` or `metric` settings. For example, if you increase the number of iterations in the optimizer, reduce the optimizer step size, or change the number of samples in a stochastic metric, the registration improves to a point, at the expense of performance.
- “Intensity-Based Automatic Image Registration”

See Also

`registration.metric.MattesMutualInformation` | `registration.metric.MeanSquares`
| `registration.optimizer.RegularStepGradientDescent` |
`registration.optimizer.OnePlusOneEvolutionary` | `imregister` | `imshowpair`

Introduced in R2012a

imregcorr

Estimates geometric transformation that aligns two 2-D images using phase correlation

Syntax

```
tform = imregcorr(moving, fixed)
tform = imregcorr(moving, fixed, transformtype)
tform = imregcorr(moving, Rmoving, fixed, Rfixed, ___)
tform = imregcorr( ___, Name, Value, ___)
```

Description

`tform = imregcorr(moving, fixed)` estimates the geometric transformation that aligns an image, `moving`, with a reference image, `fixed`. The function returns a geometric transformation object, `tform`, that maps pixels in `moving` to pixels in `fixed`.

`tform = imregcorr(moving, fixed, transformtype)` estimates the geometric transformation, where `transformtype` is a text string that specifies the type of transformation.

`tform = imregcorr(moving, Rmoving, fixed, Rfixed, ___)` estimates the geometric transformation that aligns an image, `moving`, with a reference image, `fixed`. `Rmoving` and `Rfixed` are spatial referencing objects that contain spatial information about the `moving` and `fixed` images, respectively. The transformation object returned, `tform`, defines the point mapping in the world coordinate system.

`tform = imregcorr(___, Name, Value, ___)` registers the moving image to the fixed image using name-value pairs to control various aspects of the registration algorithm.

Examples

Register an image using phase correlation


Solve a registration problem in which an image is synthetically scaled and rotated.

Prepare the sample fixed and moving images.

```
fixed = imread('cameraman.tif');

theta = 20;
S = 2.3;
tform = affine2d([S.*cosd(theta) -S.*sind(theta) 0; S.*sind(theta) S.*cosd(theta) 0; 0 0 1]);
moving = imwarp(fixed,tform);
moving = moving + uint8(10*rand(size(moving)));

figure, imshowpair(fixed,moving,'montage');
```



Estimate the transformation needed to align the images using `imregcorr`.

```
tformEstimate = imregcorr(moving,fixed);
```

Apply estimated geometric transform to the image you want to align (`moving`). The example uses the `'OutputView'` parameter to obtain a registered image the same size and with the same world limits as the reference image. The example first views the original image and the registered image side-by-side to check the registration. The example then views the registered image overlaid on the original using the `'falsecolor'` option to highlight any areas where the images differ.

```
Rfixed = imref2d(size(fixed));  
movingReg = imwarp(moving,tformEstimate,'OutputView',Rfixed);  
  
figure, imshowpair(fixed,movingReg,'montage');  
figure, imshowpair(fixed,movingReg,'falsecolor');
```





Input Arguments

moving — Image to be registered

grayscale image | binary image | RGB image

Image to be registered, specified as a grayscale, binary, or RGB image. If you specify an RGB image, `imregcorr` converts it to a grayscale image, using `rgb2gray`, before processing.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

fixed — Reference image in the target orientation

grayscale image | binary image | RGB image

Reference image in the target orientation, specified as a grayscale, binary, or RGB image. If you specify an RGB image, `imregcorr` converts it to a grayscale image, using `rgb2gray`, before processing.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

transformtype — Type of transformation to estimate

'similarity' (default) | 'rigid' | 'translation'

Type of transformation to estimate, specified as one of the text strings in this table.

Transformation Type	Description
'translation'	Translation
'rigid'	Translation and rotation
'similarity'	Translation, rotation, and scaling. When using the 'similarity' option, the phase correlation algorithm is only scale invariant within some range of scale difference between the fixed and moving images. <code>imregcorr</code> limits the search space to scale differences within the range (1/4,4). Scale differences less than 1/4 or greater than 4 cannot be detected by <code>imregcorr</code> .

Data Types: char

Moving — Spatial referencing information associated with the image to be registered

spatial referencing object

Spatial referencing information associated with the image to be registered, specified as a spatial referencing object of type `imref2d`.

Fixed — Spatial referencing information associated with the reference (fixed) image

spatial referencing object

Spatial referencing information associated with the reference (fixed) image, specified as a spatial referencing object of type `imref2d`.

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

Example: `tformEstimate = imregcorr(moving, fixed, 'Window', true);`

'Window' — Logical flag to control use of windowing to suppress spectral leakage effects in frequency domain

true (default) | scalar logical

Logical flag to control use of windowing to suppress spectral leakage effects in frequency domain, specified as a logical scalar. When set to `true`, `imregcorr` uses a Blackman

window to increase the stability of registration results. If the common features you are trying to align in your images are oriented along the edges, setting 'Window' to **false** can sometimes provide superior registration results.

```
Example: tformEstimate = imregcorr(moving, fixed, 'Window', true);
```

Data Types: `logical`

Output Arguments

tform — Geometric transformation

geometric transformation object

Geometric transformation, specified as a geometric transformation object of type `affine2d`.

More About

Tips

- If your image is of type `double`, you can achieve performance improvements by casting the image to `single` with `im2single` before registration. Input images of type `double` cause the algorithm to compute FFTs in `double`.

References

- [1] Reddy, B. S. and Chatterji, B. N., *An FFT-Based Technique for Translation, Rotation, and Scale-Invariant Image Registration*, IEEE Transactions on Image Processing, Vol. 5, No. 8, August 1996

See Also

`imregister` | `imregtform` | `imshowpair` | `imwarp`

Introduced in R2014a

imregdemons

Estimate displacement field that aligns two 2-D or 3-D images

Syntax

```
[D,moving_reg] = imregdemons(moving,fixed)
[___] = imregdemons(moving,fixed,N)
[gpuarrayD,gpuarrayMoving_reg] = imregdemons(gpuarrayMoving,
gpuarrayFixed,N)
[___] = imregdemons(____,Name,Value,...)
```

Description

`[D,moving_reg] = imregdemons(moving,fixed)` estimates the displacement field `D` that aligns the image to be registered, `moving`, with the reference image, `fixed`. `moving` and `fixed` can be 2-D or 3-D intensity images.

The displacement vectors at each pixel location map locations from the `fixed` image grid to a corresponding location in the `moving` image. `moving_reg` is a warped version of the `moving` image that is warped according to the displacement field `D` and resampled using linear interpolation.

`[___] = imregdemons(moving,fixed,N)` specifies the number of iterations to be computed. This function does not use a convergence criterion and therefore is always guaranteed to run for the specified or default number of iterations.

`[gpuarrayD,gpuarrayMoving_reg] = imregdemons(gpuarrayMoving,gpuarrayFixed,N)` performs the estimation on a GPU.

Note: The GPU version does not support 3-D input images.

`[___] = imregdemons(____,Name,Value,...)` registers the moving image using name-value pairs to control aspects of weight computation.

Examples

Register Two Images with Local Distortions

This example shows how to solve a registration problem in which the same hand has been photographed in two different poses. The misalignment of the images varies locally throughout each image. This is therefore a non-rigid registration problem.

Read the two images into the workspace.

```
fixed = imread('hands1.jpg');  
moving = imread('hands2.jpg');
```


Convert the images to grayscale for processing.

```
fixed = rgb2gray(fixed);  
moving = rgb2gray(moving);
```

Observe the initial misalignment. Fingers are in different poses. In the second figure, the two images are overlaid over each other to make it easy to see where the images differ. The differences are highlighted in green.

```
figure  
imshowpair(fixed,moving,'montage')  
figure  
imshowpair(fixed,moving)
```





Correct illumination differences between the `moving` and `fixed` images using histogram matching. This is a common pre-processing step.

```
moving = imhistmatch(moving, fixed);
```


Estimate the transformation needed to bring the two images into alignment.

```
[~, movingReg] = imregdemons(moving, fixed, [500 400 200], ...  
    'AccumulatedFieldSmoothing', 1.3);
```

Display the results of the registration. In the first figure, the images are overlaid to show the alignment.

```
figure  
imshowpair(fixed, movingReg)  
figure  
imshowpair(fixed, movingReg, 'montage')
```





Register two images with local distortions on a GPU

Perform a nonrigid registration on a GPU.

Read images into the workspace.

```
fixed = imread('hands1.jpg');  
moving = imread('hands2.jpg');
```

Observe the initial misalignment. (Fingers are in different positions.)

```
figure  
imshowpair(fixed,moving,'montage')  
figure  
imshowpair(fixed,moving)
```

Create `gpuArrays` and convert the images to grayscale.

```
fixedGPU = gpuArray(fixed);  
movingGPU = gpuArray(moving);  
  
fixedGPU = rgb2gray(fixedGPU);  
movingGPU = rgb2gray(movingGPU);
```

Use histogram matching to correct illumination differences between the moving and fixed images. This is a common preprocessing step.

```
fixedHist = imhist(fixedGPU);  
movingGPU = histeq(movingGPU, fixedHist);
```

Perform the registration.

```
[~, movingReg] = imregdemons(movingGPU, fixedGPU, [500 400 200], 'AccumulatedFieldSmoothing');
```

Bring the registered image back to the CPU.

```
movingReg = gather(movingReg);
```

View the results.

```
figure  
imshowpair(fixed, movingReg)  
figure  
imshowpair(fixed, movingReg, 'montage')
```

Input Arguments

moving — Image to be registered

2-D or 3-D grayscale image

Image to be registered, specified as a 2-D or 3-D grayscale image.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

fixed — Reference image in the target orientation

2-D or 3-D grayscale image

Reference image in the target orientation, specified as a 2-D or 3-D grayscale image.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

N — Number of iterations

100 (default) | positive integer scalar or vector

Number of iterations, specified as a positive integer scalar or vector.

When you specify a vector, **N** is the number of iterations per pyramid level (resolution level). For example, if there are 3 pyramid levels, you can specify the vector `[100, 50, 25]`, where `imregdemons` performs 100 iterations at the lowest resolution level, 50 iterations at the next pyramid level, and 25 iterations at the next iteration level.

—the level with full resolution. Because it takes less time to process the lower resolution levels, running more iterations at low resolution and fewer iterations at the higher resolutions of the pyramid can help performance.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

gpuarrayMoving — Input image for processing on a GPU

gpuArray containing a 2-D grayscale image

Input image for processing on a GPU, specified as a 2-D grayscale image. 3-D images are not supported on the GPU.

gpuarrayFixed — Reference image for processing on a GPU

gpuArray containing a 2-D grayscale image

Reference image for processing on a GPU, specified as a gpuArray containing 2-D grayscale image. 3-D images are not supported on the GPU.

Name-Value Pair Arguments

Specify optional comma-separated pairs of **Name**, **Value** arguments. **Name** is the argument name and **Value** is the corresponding value. **Name** must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as **Name1**, **Value1**, ..., **NameN**, **ValueN**.

Example: `[~,movingReg] = imregdemons(moving,fixed,[500 400 200],'AccumulatedFieldSmoothing',1.5);`

'AccumulatedFieldSmoothing' — Smoothing applied at each iteration

1.0 (default) | positive scalar

Smoothing applied at each iteration, specified as a numeric value. This parameter controls the amount of diffusion-like regularization. `imregdemons` applies the standard deviation of the Gaussian smoothing to regularize the accumulated field at each iteration. Larger values result in smoother output displacement fields. Smaller values result in more localized deformation in the output displacement field. Values typically are in the range `[0.5, 3.0]`. When you specify multiple `PyramidLevels`, the standard deviation used in the Gaussian smoothing remains the same at each pyramid level.

Data Types: `double`

'PyramidLevels' — Number of multi-resolution image pyramid levels to use

3 (default) | positive scalar

Number of multi-resolution image pyramid levels to use, specified as a positive value.

Note: The 'PyramidLevels' parameter is not supported on a GPU.

Data Types: `double`

'DisplayWaitbar' — Display waitbar to indicate progress

`true` (default) | `false`

When set to `true`, `imregdemons` displays a waitbar to indicate progress for long-running operations. To prevent `imregdemons` from displaying a waitbar, set `DisplayWaitbar` to `false`.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

Output Arguments

D — Displacement field

matrix of class `double`

Displacement field, specified as a matrix of class `double`. If `fixed` is m -by- n , the displacement field matrix is m -by- n -by-2, in which `D(:, :, 1)` contains displacements along the x -axis and `D(:, :, 2)` contains displacements along the y -axis. If `fixed` is m -by- n -by- P , the displacement field is of size m -by- n -by- P -by-3, in which `D(:, :, :, 1)` contains displacements along the x -axis, `D(:, :, :, 2)` contains displacements along the y -axis, and `D(:, :, :, 3)` contains displacements along the z -axis, in units of pixels.

moving_reg — Aligned image

2-D or 3-D grayscale image

Registered image, returned as a 2-D or 3-D grayscale image, warped according to the displacement field `D` and resampled using linear interpolation.

gpuarrayD — Displacement field

`gpuArray` containing a matrix of class `double`

Displacement field, specified as a `gpuArray` containing a matrix of class `double`.

gpuarrayMoving_reg — Aligned image

gpuArray containing a 2-D grayscale image

Registered image, returned as a `gpuArray` containing a 2-D grayscale image, warped according to the displacement field `gpuarrayD` and resampled using linear interpolation. 3-D images are not supported on the GPU.

See Also

`imregcorr` | `imregister` | `imregtform` | `imshowpair` | `imwarp`

Introduced in R2014b

imregister

Intensity-based image registration

Syntax

```
moving_reg = imregister(moving, fixed, transformType, optimizer, metric)
[moving_reg, R_reg] = imregister(moving, Rmoving, fixed, Rfixed,
transformType, optimizer, metric)
___ = imregister( ___, Name, Value)
```

Description

`moving_reg = imregister(moving, fixed, transformType, optimizer, metric)` transforms the 2-D or 3-D image, `moving`, so that it is registered with the reference image, `fixed`. Both `moving` and `fixed` images must be of the same dimensionality, either 2-D or 3-D. `transformType` is a character string that defines the type of transformation to perform. `optimizer` is an object that describes the method for optimizing the metric and `metric` is an object that defines the quantitative measure of similarity between the images to optimize. Returns the aligned image, `moving_reg`.

`[moving_reg, R_reg] = imregister(moving, Rmoving, fixed, Rfixed, transformType, optimizer, metric)` transforms the spatially referenced image `moving` so that it is registered with the spatially referenced image `fixed`. `Rmoving` and `Rfixed` are spatial referencing objects that describe the world coordinate limits and resolution of `moving` and `fixed`.

`___ = imregister(___, Name, Value)` specifies additional options with one or more `Name, Value` pair arguments.


Examples

Register Two MRI Images Obtained Using Different Protocols

Read the MRI images.

```
fixed = dicomread('knee1.dcm');
```

```
moving = dicomread('knee2.dcm');  
View the misaligned images.  
imshowpair(fixed, moving, 'Scaling', 'joint');
```



Create a configuration suitable for registering images from the different sensors.

```
[optimizer, metric] = imregconfig('multimodal')
```

```
optimizer =
```

```
    registration.optimizer.OnePlusOneEvolutionary
```

```
    Properties:
```

```
        GrowthFactor: 1.050000e+00
```

```
        Epsilon: 1.500000e-06
```

```
        InitialRadius: 6.250000e-03
```

```
        MaximumIterations: 100
```

```
metric =
```

```
    registration.metric.MattesMutualInformation
```

```
    Properties:
```

```
        NumberOfSpatialSamples: 500
```

```
        NumberOfHistogramBins: 50
```

```
        UseAllPixels: 1
```

Tune the properties of the optimizer to get the problem to converge on a global maxima and to allow for more iterations.

```
optimizer.InitialRadius = 0.009;
```

```
optimizer.Epsilon = 1.5e-4;
```

```
optimizer.GrowthFactor = 1.01;
```

```
optimizer.MaximumIterations = 300;
```


Perform the registration.

```
movingRegistered = imregister(moving, fixed, 'affine', optimizer, metric);
```

View registered images.

```
figure
```

```
imshowpair(fixed, movingRegistered, 'Scaling', 'joint');
```



Input Arguments

moving — Image to be registered
grayscale image

Image to be registered, specified as a 2-D or 3-D grayscale image.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

Rmoving — Spatial referencing information associated with the image to be registered

spatial referencing object

Spatial referencing information associated with image to be registered, specified as a spatial referencing object.

fixed — Reference image in the target orientation

grayscale image

Reference image in the target orientation, specified as a grayscale image.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

Rfixed — Spatial referencing information associated with the reference image

spatial referencing object

Spatial referencing information associated with the reference image, specified as a spatial referencing object.

transformType — Geometric transformation to be applied to the image to be registered

'translation' | 'rigid' | 'similarity' | 'affine'

Geometric transformation to be applied to the moving image, specified as one of the text strings listed in this table.

Transform Type	Description
'translation'	(<i>x,y</i>) translation.
'rigid'	Rigid transformation consisting of translation and rotation.
'similarity'	Nonreflective similarity transformation consisting of translation, rotation, and scale.
'affine'	Affine transformation consisting of translation, rotation, scale, and shear.

The 'similarity' and 'affine' transformation types always involve nonreflective transformations.

optimizer — Method for optimizing the similarity metric

optimizer object

Method for optimizing the similarity metric, specified as an optimizer object. Use `imregconfig` to create the optimizer objects `registration.optimizer.RegularStepGradientDescent` or `registration.optimizer.OnePlusOneEvolutionary`.

metric — Image similarity metric to be optimized during registration

metric object

Image similarity metric to be optimized during registration, specified as a metric object. Use `imregconfig` to create the metric objects `registration.metric.MeanSquares` or `registration.metric.MattesMutualInformation`.

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1,Value1,...,NameN,ValueN`.

Example: `'DisplayOptimization',1` enables the verbose optimization mode.

'DisplayOptimization' — Verbose optimization flag

false (default) | true

Verbose optimization flag, specified as a logical value, either `true` or `false`. Controls whether `imregister` displays optimization information in the command window during the registration process.

Data Types: `logical`

'InitialTransformation' — Spatial transformation to start at

`affine2d` or `affine3d` spatial transformation object

Spatial transformation to start at, specified as an `affine2d` or `affine3d` geometric transformation object.

'PyramidLevels' — Number of pyramid levels used during registration process

3 (default) | positive integer

Number of pyramid levels used during the registration process, specified as a positive integer.

Example: `'PyramidLevels',4` sets the number of pyramid levels to 4.

Data Types: `double`

Output Arguments

`moving_reg` — Transformed image

numeric matrix

Transformed image, returned as a matrix. Any fill pixels introduced that do not correspond to locations in the original image are 0.

`R_reg` — Spatial referencing information associated with output image

spatial referencing object

Spatial referencing information associated with output image, specified as a spatial referencing object.

More About

Tips

- Create `optimizer` and `metric` with the `imregconfig` function before calling `imregister`. Getting good results from optimization-based image registration usually requires modifying optimizer or metric settings for the pair of images being registered. The `imregconfig` function provides a default configuration that should only be considered a starting point. For example, if you increase the number of iterations in the optimizer, reduce the optimizer step size, or change the number of samples in a stochastic metric, the registration improves to a point, at the expense of performance. See the output of `imregconfig` for more information on the different parameters that you can modify.
- If the spatial scaling of your images differs by more than 10%, you should resize them with `imresize` before registering them.
- Use `imshowpair` or `imfuse` to visualize the results of registration.
- You can use `imregister` in an automated workflow to register several images.
- When you have spatial referencing information about the image to be registered, specify the information to `imregister` using spatial referencing objects. This helps `imregister` converge to better results more quickly because scale differences can be taken into account.

- “Intensity-Based Automatic Image Registration”

See Also

`affine2d` | `affine3d` | `imref2d` | `imref3d` | `imfuse` | `imregconfig` | `imregtform` | `imshowpair` | `imwarp`

Introduced in R2012a

imregtform

Estimate geometric transformation that aligns two 2-D or 3-D images

Syntax

```
tform = imregtform(moving, fixed, transformType, optimizer, metric)
tform = imregtform(moving, Rmoving, fixed, Rfixed, transformType,
optimizer, metric)
tform = imregtform( ____, Name, Value)
```

Description

`tform = imregtform(moving, fixed, transformType, optimizer, metric)` estimates the geometric transformation that aligns the moving image `moving` with the fixed image `fixed`. `transformType` is a string that defines the type of transformation to estimate. `optimizer` is an object that describes the method for optimizing the metric. `metric` is an object that defines the quantitative measure of similarity between the images to optimize. The output `tform` is a geometric transformation object that maps `moving` to `fixed`.

`tform = imregtform(moving, Rmoving, fixed, Rfixed, transformType, optimizer, metric)` estimates the geometric transformation where `Rmoving` and `Rfixed` specify the spatial referencing objects associated with the `moving` and `fixed` images. The output `tform` is a geometric transformation object in units defined by the spatial referencing objects `Rmoving` and `Rfixed`.


`tform = imregtform(____, Name, Value)` estimates the geometric transformation using name-value pairs to control aspects of the operation.

Examples

Estimate Transformation Needed to Register Two Misaligned Images

Read two slightly misaligned magnetic resonance images of a knee obtained using different protocols and view the images overlaid on each other.

```
fixed = dicomread('knee1.dcm');  
moving = dicomread('knee2.dcm');  
  
imshowpair(fixed, moving, 'Scaling', 'joint');
```



Get default optimizer and metric configurations suitable for registering images from different sensors ('multimodal'). Then tune the properties of the optimizer to get the problem to converge on a global maxima and to allow for more iterations.

```
[optimizer, metric] = imregconfig('multimodal')

optimizer.InitialRadius = 0.009;
optimizer.Epsilon = 1.5e-4;
optimizer.GrowthFactor = 1.01;
optimizer.MaximumIterations = 300;
```

Find the geometric transformation that maps the image to be registered (moving) to the reference image (fixed).

```
tform = imregtform(moving, fixed, 'affine', optimizer, metric)
```

```
tform =
```

```
    affine2d with properties:
```


```
                T: [3x3 double]
    Dimensionality: 2
```

Apply the transformation to the image being registered (moving) using the `imwarp` function. The example uses the 'OutputView' parameter to preserve world limits and resolution of the fixed image when forming the transformed image.

```
movingRegistered = imwarp(moving,tform,'OutputView',imref2d(size(fixed)));
```

View registered images

```
figure
imshowpair(fixed, movingRegistered,'Scaling','joint');
```



Input Arguments

moving — Image to be registered
2-D or 3-D grayscale image

Image to be registered, specified as a 2-D or 3-D grayscale image.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

Rmoving — Spatial referencing information associated with the image to be registered

spatial referencing object

Spatial referencing information associated with the image to be registered, specified as a spatial referencing object of type `imref2d` or `imref3d`.

fixed — Reference image in the target orientation

2-D or 3-D grayscale image

Reference image in the target orientation, specified as a 2-D or 3-D grayscale image.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

Rfixed — Spatial referencing information associated with the reference (fixed) image

spatial referencing object of type `imref2d` or `imref3d`

Spatial referencing information associated with the reference (fixed) image, specified as a spatial referencing object of type `imref2d` or `imref3d`.

transformType — Geometric transformation to be applied to the image to be registered

'translation' | 'rigid' | 'similarity' | 'affine'

Geometric transformation to be applied to the image to be registered, specified as one of the text strings listed in this table.

Transform Type	Description
'translation'	(<i>x,y</i>) translation.
'rigid'	Rigid transformation consisting of translation and rotation.
'similarity'	Nonreflective similarity transformation consisting of translation, rotation, and scale.
'affine'	Affine transformation consisting of translation, rotation, scale, and shear.

The 'similarity' and 'affine' transformation types always involve nonreflective transformations.

optimizer — Method for optimizing the similarity metric

optimizer object

Method for optimizing the similarity metric, specified as an optimizer object. Use `imregconfig` to create the optimizer objects `registration.optimizer.RegularStepGradientDescent` or `registration.optimizer.OnePlusOneEvolutionary`.

metric — Image similarity metric to be optimized during registration

metric object

Image similarity metric to be optimized during registration, specified as a metric object. Use `imregconfig` to create the metric objects `registration.metric.MeanSquares` or `registration.metric.MattesMutualInformation`.

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

Example: `'DisplayOptimization', 1` enables verbose optimization mode.

'DisplayOptimization' — Verbose optimization flag

false (default) | true

Verbose optimization flag, specified as a logical value, either `true` or `false`. Controls whether `imregister` displays optimization information in the command window during the registration process.

Data Types: logical

'InitialTransformation' — Spatial transformation to start at

affine2d or affine3d spatial transformation object

Spatial transformation to start at, specified as an `affine2d` or `affine3d` geometric transformation object.

'PyramidLevels' — Number of multi-level image pyramid levels used during the registration process

3 (default) | positive integer

Number of pyramid levels used during the registration process, specified as a positive integer.

Example: 'PyramidLevels', 4 sets the number of pyramid levels to 4.

Output Arguments

tform — Geometric transformation

geometric transformation object `affine2d` or `affine3d`

Geometric transformation, specified as a geometric transformation object, `affine2d` or `affine3d`. If the input matrices are 3-D, `imregtform` returns an `affine3d` object.

More About

Tips

- When you have spatial referencing information available, it is important to provide this information to `imregtform`, using spatial referencing objects. This information helps `imregtform` converge to better results more quickly because scale differences can be taken into account.
- Both `imregtform` and `imregister` use the same underlying registration algorithm. `imregister` performs the additional step of resampling `moving` to produce the registered output image from the geometric transformation estimate calculated by `imregtform`. Use `imregtform` when you want access to the geometric transformation that relates `moving` to `fixed`. Use `imregister` when you want a registered output image.
- Getting good results from optimization-based image registration usually requires modifying optimizer and/or metric settings for the pair of images being registered. The `imregconfig` function provides a default configuration that should only be considered a starting point. See the output of the `imregconfig` for more information on the different parameters that can be modified.

See Also

`affine2d` | `affine3d` | `imref2d` | `imref3d` | `imregconfig` | `imregister` | `imshowpair` | `imwarp`

Introduced in R2013a

imresize

Resize image

Syntax

```
B = imresize(A, scale)
B = imresize(A, outputSize)
[Y, newmap] = imresize(X, map, ___)
___ = imresize( ___, method)
___ = imresize( ___, Name, Value, ...)
gpuarrayB = imresize(gpuarrayA, scale)
```

Description

`B = imresize(A, scale)` returns image **B** that is **scale** times the size of **A**. The input image **A** can be a grayscale, RGB, or binary image. If **scale** is from 0 through 1.0, **B** is smaller than **A**. If **scale** is greater than 1.0, **B** is larger than **A**. By default, **imresize** uses bicubic interpolation.

`B = imresize(A, outputSize)` returns image **B** that has the number of rows and columns specified by **outputSize**, a two-element vector of the form `[numrows numcols]`.

`[Y, newmap] = imresize(X, map, ___)` resizes the indexed image **X** where **map** is the colormap associated with the image. By default, **imresize** returns a new, optimized colormap (**newmap**) with the resized image. To return a colormap that is the same as the original colormap, use the `'Colormap'` parameter.

`___ = imresize(___, method)` specifies the interpolation method used.

`___ = imresize(___, Name, Value, ...)` you can control various aspects of the resizing operation by specifying parameter/value pairs with any of the previous syntaxes.

`gpuarrayB = imresize(gpuarrayA, scale)` performs the resize operation on a GPU. The input image and the output image are `gpuArrays`. When used with `gpuArrays`,

`imresize` only supports cubic interpolation and always performs antialiasing. For cubic interpolation, the output image might have some values slightly outside the range of pixel values in the input image. This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-993 support: Yes

“MATLAB Function Block” on page 1-993 support: Yes

Examples

Resize Image Specifying Scale Factor

Read image into the workspace.

```
I = imread('rice.png');
```


Resize the image, specifying scale factor and using default interpolation method and antialiasing.


```
J = imresize(I, 0.5);
```

Display the original and the resized image.

```
figure
imshow(I)
title('Original Image')
figure
imshow(J)
title('Resized Image')
```

Original Image





Resize Image on GPU

Read image into the workspace in a `gpuArray`.

```
I = im2double(gpuArray(imread('rice.png')));
```

Resize the image, performing the operation on a GPU.

```
J = imresize(I, 0.5);
```

Display the original image and the resized image.

```
figure  
imshow(I)  
title('Original')  
figure  
imshow(J)  
title('Resized Image')
```

Resize Image Specifying Scale Factor and Interpolation Method

Read image into the workspace.

```
I = imread('rice.png');
```


Resize the image, specifying scale factor and the interpolation method.

```
J = imresize(I, 0.5, 'nearest');
```


Display the original and the resized image.

```
figure
imshow(I)
title('Original Image')
figure
imshow(J)
title('Resized Image Using Nearest-Neighbor')
```

Original Image



Resized Image Using Nearest-Neighbor



Resize Indexed Image

Read image into the workspace.

```
[X, map] = imread('trees.tif');
```


Resize the image, specifying a scale factor. By default, `imresize` returns an optimized color map with the resized indexed image.

```
[Y, newmap] = imresize(X, map, 0.5);
```

Display the original image and the resized image.

```
figure  
imshow(X, map)  
title('Original Image')  
figure  
imshow(Y, newmap)  
title('Resized Image')
```

Original Image



Resized Image



Resize RGB Image Specifying Size of Output Image

Read image into the workspace.

```
RGB = imread('peppers.png');
```

Resize the image, specifying that the output image have 64 rows. Let `imresize` calculate the number of columns necessary to preserve the aspect ratio.

```
RGB2 = imresize(RGB, [64 NaN]);
```

Display the original image and the resized image.

```
figure
imshow(RGB)
title('Original Image')
figure
imshow(RGB2)
title('Resized Image')
```


Original Image



Resized Image



Resize RGB Image on GPU

Read image into the workspace in a `gpuArray`.

```
RGB = gpuArray(im2single(imread('peppers.png')));
```

Resize the image, performing the operation on a GPU.

```
RGB2 = imresize(RGB, 0.5);
```

Display the original image and the resized image.

```
figure
imshow(RGB)
title('Original')
figure
imshow(RGB2)
title('Resized Image')
```

Input Arguments

A — Image to be resized

real, nonsparse numeric or logical array

Image to be resized, specified as a real, nonsparse numeric array.

Example: `I2 = imresize(I,0.5);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32` | `logical`

scale — Resize factor

real, numeric scalar

Resize factor, specified as a real, numeric scalar.

Example: `I2 = imresize(I,0.5);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

outputSize — Row and column dimensions of output image

two-element numeric vector

Row and column dimensions of output image, specified as a two-element vector of the form `[numrows numcols]`. Either `numrows` or `numcols` can be `NaN`, in which case `imresize` computes the number of rows or columns automatically to preserve the image aspect ratio.

Example: `I2 = imresize(I,[50 NaN]);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

X — Indexed image to be resized

real, nonsparse numeric array

Indexed image to be resized, specified as a real, nonsparse numeric array.

Example: `[X2, newmap] = imresize(X,map,0.75);`

Data Types: `double` | `uint8` | `uint16`

map — Colormap associated with indexed image

m-by-3 numeric array

Colormap associated with indexed image, *m*-by-3 numeric array.

Example:

Data Types: `double`

method — Interpolation method

'bicubic' (default) | string | two-element cell array

Interpolation method, specified as a string that identifies a general method or a named interpolation kernel, listed in the following table. Method can also be a two-element cell

array, of the form $\{f, w\}$, that specifies a custom interpolation kernel. In this cell array, f is a function handle for a custom interpolation kernel and w is the width of the custom kernel. $f(x)$ must be zero outside the interval $-w/2 \leq x < w/2$. The function handle f can be called with a scalar or a vector input.

Method	Description
'nearest'	Nearest-neighbor interpolation; the output pixel is assigned the value of the pixel that the point falls within. No other pixels are considered.
'bilinear'	Bilinear interpolation; the output pixel value is a weighted average of pixels in the nearest 2-by-2 neighborhood
'bicubic'	Bicubic interpolation (the default); the output pixel value is a weighted average of pixels in the nearest 4-by-4 neighborhood
Interpolation Kernel	Description
'box'	Box-shaped kernel
'triangle'	Triangular kernel (equivalent to 'bilinear')
'cubic'	Cubic kernel (equivalent to 'bicubic')
'lanczos2'	Lanczos-2 kernel
'lanczos3'	Lanczos-3 kernel

Example: `I2 = imresize(I,0.5,'bilinear');`

Data Types: `char` | `cell`

gpuarrayA — Image to be resized on a GPU

gpuArray

Image to be resized on a GPU, specified as a gpuArray.

Example: `gpuarrayB = imresize(gpuarrayA,0.5);`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

```
Example: I2 = imresize(I,0.5,'Antialiasing',false);
```

'Antialiasing' — Perform antialiasing when shrinking an image

true | false

Perform antialiasing when shrinking an image, specified as the logical Boolean value **true** or **false**. The default value depends on the interpolation method. If the method is nearest-neighbor ('nearest'), the default is **false**. For all other interpolation methods, the default is **true**.

```
Example: I2 = imresize(I,0.5,'Antialiasing',false);
```

Data Types: logical

'Colormap' — Return optimized colormap

'optimized' (default) | 'original'

Return optimized colormap, specified as the string 'optimized' or 'original'. (Indexed images only). If set to 'original', the output colormap (**newmap**) is the same as the input colormap (**map**). If set to 'optimized', **imresize** returns a new optimized colormap.

```
Example: [X2, map2] = imresize(X,map,0.75,'Colormap','original');
```

Data Types: char

'Dither' — Perform color dithering

true (default) | false

Perform color dithering, specified as the logical Boolean value **true** or **false**. (Indexed images only).

```
Example: [X2, newmap] = imresize(X,map,0.75,'Dither',false);
```

Data Types: logical

'Method' — Interpolation method

'bicubic' (default) | string | cell array

Interpolation method, specified as a text string or two-element cell array. For details, see **method**.

```
Example: I2 = imresize(I,0.5,'Method','nearest');
```

Data Types: char | cell

'OutputSize' — Size of output image

two-element numeric vector

Size of the output image, specified as a two-element vector of the form [numrows numcols].

Example: [X2, newmap] = imresize(X,map,'OutputSize',[150 150]);

Data Types: single | double | int8 | int16 | int32 | int64 | uint8 | uint16 | uint32 | uint64

'Scale' — Resize scale factor

numeric scalar or two-element vector of positive values

Resize scale factor, specified as a numeric scalar or two-element vector of positive values.

Example: [X2, newmap] = imresize(X,map,'scale',1.25);

Data Types: single | double | int8 | int16 | int32 | int64 | uint8 | uint16 | uint32 | uint64

Output Arguments

B — Resized image

real, nonsparse numeric array

Resized image, returned as a real, nonsparse numeric array, the same class as the input image.

Y — Resized indexed image

real, nonsparse numeric array

Resized indexed image, returned as a real, nonsparse numeric array, the same class as the input image.

newmap — Optimized colormap

m-by-3 numeric array

Optimized colormap, returned as an *m*-by-3 numeric array.

gpuarrayB — Resized image

gpuArray

Resized image, returned as a `gpuArray`.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, note the following:

- Indexed input images are not supported. This includes the `imresize(X,map,...)` syntaxes and the parameters `'Colormap'` and `'Dither'`.
- Custom interpolation kernels are not supported.
- All parameter-value pairs must be compile-time constants.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

When using this function with the MATLAB Function Block, note the following:

- `Scale` and `Method` input argument values must be compile-time constants.
- The `numrows` and `numcols` values of the `OutputSize` parameter must be compile-time constants.

Tips

- The function `imresize` changed in version 5.4 (R2007a). Previous versions of the Image Processing Toolbox used a different algorithm by default. If you need the same results produced by the previous implementation, use the function `imresize_old`.
- For bicubic interpolation and user-specified interpolation kernels, the output image may have some values slightly outside the range of pixel values in the input image.

See Also

`gpuArray` | `imrotate` | `imtransform` | `interp2` | `tformarray`

Introduced before R2006a

imroi

Region-of-interest (ROI) base class

Description

Because the `imroi` class is abstract, creating an instance of the `imroi` class is not allowed.

Methods

`imroi` supports the following methods. Type `methods imroi` to see a complete list.

addNewPositionCallback — Add new-position callback to ROI object

`id = addNewPositionCallback(h, fcn)` adds the function handle `fcn` to the list of new-position callback functions of the ROI object `h`. Whenever the ROI object changes its position each function in the list is called with the syntax:

```
fcn(pos)
```

where `pos` is of the form returned by the object's `getPosition` method.

The return value, `id`, is used only with `removeNewPositionCallback`.

createMask — Create mask within image

`BW = createMask(h)` returns a mask, or binary image, that is the same size as the input image with 1s inside the ROI object `h` and 0s everywhere else. The input image must be contained within the same axes as the ROI.

`BW = createMask(h, h_im)` returns a mask the same size as the image `h_im` with 1s inside the ROI object `h` and 0s outside. This syntax is required when the axes that contain the ROI hold more than one image.

delete — Delete ROI object

`delete(h)` deletes the ROI object `h`

getColor — Get color used to draw ROI object.

`color = getColor(h)` gets the color used to draw the ROI object `h`. The three-element vector `color` specifies an RGB triplet.

getPosition — Return current position of ROI object

`pos = getPosition(h)` returns current position of the ROI object `h`.

getPositionConstraintFcn — Return function handle to current position constraint function

`fcn = getPositionConstraintFcn(h)` returns a function handle `fcn` to the current position constraint function of the ROI object `h`.

removeNewPositionCallback — Remove new-position callback from ROI object

`removeNewPositionCallback(h, id)` removes the corresponding function from the new-position callback list of the ROI object `h`. `id` is the identifier returned by the `addNewPositionCallback` method.

resume — Resume execution of MATLAB command line

`resume(h)` resumes execution of the MATLAB command line. When called after a call to `wait`, `resume` causes `wait` to return an accepted position. The `resume` method is useful when you need to exit `wait` from a callback function.

setColor — Set color used to draw ROI object.

`setColor(h, new_color)` sets the color used to draw the ROI object `h`. `new_color` can be a three-element vector specifying an RGB triplet, or a text string specifying the long or short name of a predefined color, such as 'white' or 'w'. See `ColorSpec` for a list of predefined colors.

setConstrainedPosition — Set ROI object to new position

`setConstrainedPosition(h, candidate_position)` sets the ROI object `h` to a new position. The candidate position is subject to the position constraint function. `candidate_position` is of the form expected by the `setPosition` method.

setPositionConstraintFcn — Set position constraint function of ROI object

`setPositionConstraintFcn(h, fcn)` sets the position constraint function of the ROI object `h` to be the specified function handle, `fcn`. Whenever the object is moved because of a mouse drag, the constraint function is called using the syntax:

```
constrained_position = fcn(new_position)
```

where `new_position` is of the form returned by the `getPosition` method. You can use the `makeConstrainToRectFcn` to create this function.

wait — Block MATLAB command line until ROI creation is finished

`accepted_pos = wait(h)` blocks execution of the MATLAB command line until you finish positioning the ROI object `h`. You indicate completion by double-clicking on the ROI object. The returned position, `accepted_pos`, is of the form returned by the object's `getPosition` method.

See Also

`makeConstrainToRectFcn`

Introduced in R2008a

imrotate

Rotate image

Syntax

```
B = imrotate(A,angle)
B = imrotate(A,angle,method)
B = imrotate(A,angle,method,bbox)
gpuarrayB = imrotate(gpuarrayA,method)
```

Description

`B = imrotate(A,angle)` rotates image `A` by `angle` degrees in a counterclockwise direction around its center point. To rotate the image clockwise, specify a negative value for `angle`. `imrotate` makes the output image `B` large enough to contain the entire rotated image. `imrotate` uses nearest neighbor interpolation, setting the values of pixels in `B` that are outside the rotated image to 0 (zero).

`B = imrotate(A,angle,method)` rotates image `A`, using the interpolation method specified by `method`.

`B = imrotate(A,angle,method,bbox)` rotates image `A`, where `bbox` specifies the size of the returned image. `bbox` is a text string that can have one of the following values.

`gpuarrayB = imrotate(gpuarrayA,method)` perform operation on a graphics processing unit (GPU), where `gpuarrayA` is a `gpuArray` object that contains a grayscale or binary image, and the output image is a `gpuArray` object. This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-1001 support: Yes.

“MATLAB Function Block” on page 1-1001 support: Yes

Examples

Rotate Image Clockwise for Better Horizontal Alignment

Read image into the workspace.

```
I = fitsread('solarspectra.fts');
```

Convert to grayscale.

```
I = mat2gray(I);
```


Rotate the image 1 degree clockwise to bring it into better horizontal alignment. The example specified bilinear interpolation and requests that the result be cropped to be the same size as the original image.


```
J = imrotate(I,-1,'bilinear','crop');
```

Display the original image and the rotated image.

```
figure  
imshow(I)  
title('Original Image')  
figure  
imshow(J)  
title('Rotated Image')
```

Original Image



Rotated Image

Rotate Image on GPU

Read image into a `gpuArray` object.

```
X = gpuArray(imread('pout.tif'));
```

Rotate the image, performing the operation on the graphics processing unit (GPU).

```
Y = imrotate(X, 37, 'loose', 'bilinear');
```

Display the rotated image.

```
figure; imshow(Y)
```

Input Arguments

A — Image to be rotated

real, nonsparse, numeric or logical array

Image to be rotated, specified as a real, nonsparse, numeric, or logical array.

```
Example: J = imrotate(I, -1);
```

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

angle — Amount of rotation in degrees

numeric scalar

Amount of rotation in degrees, specified as a numeric scalar.

Example: `J = imrotate(I, -1);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

method — Interpolation method

'nearest-neighbor' (default) | string

Interpolation method, specified as one of the following strings.

Value	Description
'nearest'	Nearest-neighbor interpolation
'bilinear'	Bilinear interpolation
'bicubic'	Bicubic interpolation
	Note: Bicubic interpolation can produce pixel values outside the original range.

Example: `J = imrotate(I, -1, 'bilinear');`

Data Types: `char`

bbox — Bounding box defining size of output image

'loose' (default) | 'crop'

Bounding box that defines the size of output image, specified as either of the following text strings.

Value	Description
'crop'	Make output image B the same size as the input image A, cropping the rotated image to fit
{ 'loose' }	Make output image B large enough to contain the entire rotated image. B is larger than A.

Example: `J = imrotate(I, -1, 'bilinear', 'crop');`

Data Types: char

gpuarrayA — Image to be rotated

gpuArray

Image to be rotated, specified as a gpuArray.

```
Example: X = gpuArray(imread('pout.tif')); Y = imrotate(X, 37,  
'loose', 'bilinear');
```

Output Arguments

B — Rotated image

real, nonsparse, numeric or logical array

Rotated image, returned as a real, nonsparse, numeric or logical array.

gpuarrayB — Rotated image

gpuArray

Rotated image, returned as a gpuArray

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic MATLAB Host Computer target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, note the following:

- The `method` and `bbox` arguments must be compile-time constants.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

When using this function with the MATLAB Function Block, the input argument `angle` must be a compile-time constant.

Tips

- This function changed in version 9.3 (R2015b). Previous versions of the Image Processing Toolbox use different spatial conventions. If you need the same results produced by the previous implementation, use the function `imrotate_old`.
- This function might take advantage of hardware optimization for data types `uint8`, `uint16`, and `single` to run faster.

See Also

`gpuArray` | `imcrop` | `imresize` | `imtransform` | `tformarray`

Introduced before R2006a

imsave


Save Image Tool

Syntax

```
imsave  
imsave(h)  
[filename, user_canceled] = imsave(...)
```

Description

`imsave` creates a Save Image tool in a separate figure that is associated with the image in the current figure, called the target image. The Save Image tool displays an interactive file chooser dialog box (shown below) in which you can specify a path and filename. When you click **Save**, the Save Image tool writes the target image to a file using the image file format you select in the Files of Type menu. `imsave` uses `imwrite` to save the image, using default options.



Select image file format. →

If you specify a filename that already exists, `imsave` displays a warning message. Select **Yes** to use the filename or **No** to return to the dialog to select another filename. If you select **Yes**, the Save Image tool attempts to overwrite the target file.

Note: The Save Image tool is modal; it blocks the MATLAB command line until you respond.

`imsave(h)` creates a Save Image tool associated with the image specified by the handle `h`. `h` can be an image, axes, uipanel, or figure handle. If `h` is an axes or figure handle, `imsave` uses the first image returned by `findobj(h, 'Type', 'image')`.

`[filename, user_canceled] = imsave(...)` returns the full path to the file selected in `filename`. If you press the **Cancel** button, `imsave` sets `user_canceled` to `true` (1); otherwise, `false` (0).

Remarks

In contrast to the **Save as** option in the figure **File** menu, the Save Image tool saves only the image displayed in the figure. The **Save as** option in the figure window File menu saves the entire figure window, not just the image.

Examples

```
imshow peppers.png  
save
```

See Also

```
imformats | imgetfile | imputfile | imwrite
```

Introduced in R2007b

imscrollpanel

Scroll panel for interactive image navigation

Syntax

```
hpanel = imscrollpanel(hparent, himage)
```

Description

`hpanel = imscrollpanel(hparent, himage)` creates a scroll panel containing the target image (the image to be navigated). `himage` is a handle to the target image. `hparent` is a handle to the figure or `uipanel` that will contain the new scroll panel. The function returns `hpanel`, a handle to the scroll panel, which is a `uipanel` object.

A scroll panel makes an image scrollable. If the size or magnification makes an image too large to display in a figure on the screen, the scroll panel displays a portion of the image at 100% magnification (one screen pixel represents one image pixel). The scroll panel adds horizontal and vertical scroll bars to enable navigation around the image.

`imscrollpanel` changes the object hierarchy of the target image. Instead of the familiar figure->axes->image object hierarchy, `imscrollpanel` inserts several `uipanel` and `uicontrol` objects between the figure and the axes object.

API Functions

A scroll panel contains a structure of function handles, called an API. You can use the functions in this API to manipulate the scroll panel. To retrieve this structure, use the `iptgetapi` function, as in the following example.

```
api = iptgetapi(hpanel)
```

This table lists the scroll panel API functions, in the order they appear in the structure.

Function	Description
<code>setMagnification</code>	Sets the magnification of the target image in units of screen pixels per image pixel.

Function	Description
	<pre>mag = api.setMagnification(new_mag)</pre> <p>where <code>new_mag</code> is a scalar magnification factor.</p>
<code>getMagnification</code>	<p>Returns the current magnification factor of the target image in units of screen pixels per image pixel.</p> <pre>mag = api.getMagnification()</pre> <p>Multiply <code>mag</code> by 100 to convert to percentage. For example if <code>mag=2</code>, the magnification is 200%.</p>
<code>setMagnificationAndCenter</code>	<p>Changes the magnification and makes the point <code>cx, cy</code> in the target image appear in the center of the scroll panel. This operation is equivalent to a simultaneous zoom and recenter.</p> <pre>api.setMagnificationAndCenter(mag, cx, cy)</pre>
<code>findFitMag</code>	<p>Returns the magnification factor that would make the target image just fit in the scroll panel.</p> <pre>mag = api.findFitMag()</pre>
<code>setVisibleLocation</code>	<p>Moves the target image so that the specified location is visible. Scrollbars update.</p> <pre>api.setVisibleLocation(xmin, ymin) api.setVisibleLocation([xmin ymin])</pre>
<code>getVisibleLocation</code>	<p>Returns the location of the currently visible portion of the target image.</p> <pre>loc = api.getVisibleLocation()</pre> <p>where <code>loc</code> is a vector <code>[xmin ymin]</code>.</p>
<code>getVisibleImageRect</code>	<p>Returns the current visible portion of the image.</p> <pre>r = api.getVisibleImageRect()</pre> <p>where <code>r</code> is a rectangle <code>[xmin ymin width height]</code>.</p>

Function	Description
<p><code>addNewMagnificationCallback</code></p>	<p>Adds the function handle <code>fcn</code> to the list of new-magnification callback functions.</p> <pre>id = api.addNewMagnificationCallback(fcn)</pre> <p>Whenever the scroll panel magnification changes, each function in the list is called with the syntax:</p> <pre>fcn(mag)</pre> <p>where <code>mag</code> is a scalar magnification factor.</p> <p>The return value, <code>id</code>, is used only with <code>removeNewMagnificationCallback</code>.</p>
<p><code>removeNewMagnificationCallback</code></p>	<p>Removes the corresponding function from the new-magnification callback list.</p> <pre>api.removeNewMagnificationCallback(id)</pre> <p>where <code>id</code> is the identifier returned by <code>addNewMagnificationCallback</code>.</p>
<p><code>addNewLocationCallback</code></p>	<p>Adds the function handle <code>fcn</code> to the list of new-location callback functions.</p> <pre>id = api.addNewLocationCallback(fcn)</pre> <p>Whenever the scroll panel location changes, each function in the list is called with the syntax:</p> <pre>fcn(loc)</pre> <p>where <code>loc</code> is <code>[xmin ymin]</code>.</p> <p>The return value, <code>id</code>, is used only with <code>removeNewLocationCallback</code>.</p>

Function	Description
removeNewLocationCallback	<p>Removes the corresponding function from the new-location callback list.</p> <pre>api.removeNewLocationCallback(id)</pre> <p>where <code>id</code> is the identifier returned by <code>addNewLocationCallback</code>.</p>
replaceImage	<pre>api.replaceImage(...,PARAM1,VAL1,PARAM2,VAL2,...)</pre> <p>replaces the image displayed in the scroll panel.</p> <pre>api.replaceImage(I) api.replaceImage(BW) api.replaceImage(RGB) api.replaceImage(I,MAP) api.replaceImage(filename)</pre> <p>By default, the new image data is displayed centered, at 100% magnification. The image handle is unchanged.</p> <p>The parameters you can specify include many of the parameters supported by <code>imshow</code>, including <code>'Colormap'</code>, <code>'DisplayRange'</code>, and <code>'InitialMagnification'</code>. In addition, you can use the <code>'PreserveView'</code> parameter to preserve the current magnification and centering of the image during replacement. Specify the logical scalar <code>True</code> to preserve current centering and magnification. Parameter names can be abbreviated, and case does not matter.</p>

Note

Scrollbar navigation as provided by `imscrollpanel` is incompatible with the default MATLAB figure navigation buttons (pan, zoom in, zoom out). The corresponding menu items and toolbar buttons should be removed in a custom GUI that includes a scrollable uipanel created by `imscrollpanel`.

When you run `imscrollpanel`, it appears to take over the entire figure because, by default, an `hpanel` object has `'Units'` set to `'normalized'` and `'Position'` set to `[0 0 1 1]`. If you want to see other children of `hparent` while using your new scroll panel, you must manually set the `'Position'` property of `hpanel`.

Examples

Create Scroll Panel with Magnification Box and Overview Tool


Display an image in a figure. The example suppresses the standard toolbar and menubar in the figure window because these do not work with the scroll panel.

```
hFig = figure('Toolbar','none',...  
             'Menubar','none');  
hIm = imshow('saturn.png');
```

Create a scroll panel to contain the image.


```
hSP = imscrollpanel(hFig,hIm);  
set(hSP,'Units','normalized',...  
      'Position',[0 .1 1 .9])
```


Note addition of scroll bars.



Add a Magnification Box and an Overview tool to the figure.

```
hMagBox = immagbox(hFig,hIm);  
pos = get(hMagBox,'Position');  
set(hMagBox,'Position',[0 0 pos(3) pos(4)])  
imoverview(hIm)
```



Get the scroll panel API so that you can control the view programmatically.

```
api = iptgetapi(hSP);
```

Get the current magnification and position.

```
mag = api.getMagnification()  
r = api.getVisibleImageRect()
```

```
mag =
```


```
1
```

```
r =
```

```
125.0072 201.5646 716.0000 709.0000
```

Use the scroll panel object API function `setVisibleLocation` to view the top left corner of the image.


```
api.setVisibleLocation(0.5,0.5)
```



Change the magnification of the image so that the image fits entirely in the scroll panel. In the following figure, note that the scroll bars are no longer visible.


```
api.setMagnification(api.findFitMag())
```

Magnification changed to fit image completely in the figure.



Zoom in to 1600% on the dark spot.

```
api.setMagnificationAndCenter(16,306,800)
```

More About

- "Adding Navigation Aids to a GUT"

See Also

`immagbox` | `imoverview` | `imoverviewpanel` | `imtool` | `iptgetapi`

Introduced before R2006a

imsegfmm

Binary image segmentation using Fast Marching Method

Syntax

```
BW = imsegfmm(W,mask,thresh)
BW = imsegfmm(W,C,R,thresh)
[BW,D] = imsegfmm( ___ )
```

Description

`BW = imsegfmm(W,mask,thresh)` returns a segmented image `BW`, which is computed using the Fast Marching Method. The array `W` specifies weights for each pixel. `mask` is a logical array that specifies seed locations. `thresh` is a non-negative scalar in the range `[0 1]` which specifies the level at which `imsegfmm` thresholds the output of the Fast Marching Method to obtain the output binary image `BW`.

`BW = imsegfmm(W,C,R,thresh)` returns a segmented image, with seed locations specified by the vectors `C` and `R`, which contain column and row indices. `C` and `R` must contain values which are valid pixel indices in `W`.

`[BW,D] = imsegfmm(___)` returns the normalized geodesic distance map `D` computed using the Fast Marching Method. `BW` is a thresholded version of `D`, where all the pixels that have normalized geodesic distance values less than `thresh` are considered foreground pixels and set to `true`. `D` can be thresholded at different levels to obtain different segmentation results.

Examples

Segment Image Using Fast Marching Method Algorithm

This example shows how to segment an object in an image using Fast Marching Method based on differences in grayscale intensity as compared to the seed locations.

Read image.

```
I = imread('cameraman.tif');  
imshow(I)  
title('Original Image')
```

Original Image



Create mask and specify seed location. You can also use `roipoly` to create the mask interactively.

```
mask = false(size(I));  
mask(170,70) = true;
```

Compute the weight array based on grayscale intensity differences.

```
W = graydiffweight(I, mask, 'GrayDifferenceCutoff', 25);
```

Segment the image using the weights.

```
thresh = 0.01;  
[BW, D] = imsefmm(W, mask, thresh);
```

```
figure
imshow(BW)
title('Segmented Image')
```



You can threshold the geodesic distance matrix D using different thresholds to get different segmentation results.

```
figure
imshow(D)
title('Geodesic Distances')
```

Geodesic Distances



Input Arguments

W — Weight array

nonsparse, nonnegative numeric array

Weight array, specified as a nonsparse, nonnegative numeric array. Use the `graydiffweight` or `gradientweight` functions to compute this weight array. `W` must have nonnegative values. Ideally, `W` should have high values in the region which is to be segmented as the foreground (object) and low values elsewhere.

Example: `W = graydiffweight(I, mask, 'GrayDifferenceCutoff', 25);`

Data Types: `single` | `double` | `uint8` | `int8` | `int16` | `uint16` | `int32` | `uint32`

mask — Seed locations mask

logical array

Seed locations mask, specified as a logical array, the same size as *W*. Locations where *mask* is true are seed locations. If you used `graydiffweight` to create the weight matrix *W*, it is recommended that you use the same value of *mask* with `imseghmm` that you used with `graydiffweight`.

Example: `mask = false(size(I)); mask(170,70) = true;`

Data Types: `logical`

thresh — Threshold level used to obtain the binary image

non-negative scalar in the range [0 1]

Threshold level used to obtain the binary image, specified as a non-negative scalar in the range [0 1]. Low values typically result in large foreground regions (logical true) in *BW*, and high values produce small foreground regions.

Example: 0.5

Data Types: `double`

C — Column index of reference pixels

numeric vector

Column index of reference pixels, specified as a numeric vector.

Example: [50 75 93]

Data Types: `double`

R — Row index of reference pixels

numeric vector

Row index of reference pixels, specified as a numeric vector.

Example: [48 71 89]

Data Types: `double`

Output Arguments

BW — Segmented image

logical array

Segmented image, returned as a logical array of the same size as *W*.

Example:

Data Types: `logical`

D — Normalized geodesic distance map

`double` | `single`

Normalized geodesic distance map, returned as an array of `double` the same size as `W`. If `W` is of class `single`, `D` is of class `single`.

More About

Tips

- `imsegfmm` uses double-precision floating point operations for internal computations for all classes of `W`, except when `W` is of class `single`, in which case `imsegfmm` uses single-precision floating point operations internally.
- Pixels with 0 or NaN weight values will have the geodesic distance value of `Inf` in the corresponding location in `D`, and will be part of the background (logical false) in the segmented image `BW`.

References

- [1] Sethian, J. A. Level Set Methods and Fast Marching Methods: Evolving Interfaces in Computational Geometry, Fluid Mechanics, Computer Vision, and Materials Science, Cambridge University Press, 2nd Edition, 1999.

See Also

`gradientweight` | `graydiffweight`

Introduced in R2014b

imseggeodesic

Segment image into two or three regions using geodesic distance-based color segmentation

Syntax

```
L = imseggeodesic(RGB,BW1,BW2)
L = imseggeodesic(RGB,BW1,BW2,BW3)
[L,P] = imseggeodesic(____)
[L, P] = imseggeodesic(____,Name,Value,...)
```

Description

`L = imseggeodesic(RGB,BW1,BW2)` segments the input image `RGB`, which must be a valid RGB image, returning a segmented binary image with segment labels specified by label matrix `L`. `BW1` and `BW2` are binary images that specify the location of the initial seed regions, called *scribbles*, for the two regions (foreground and background). `imseggeodesic` uses the scribbles specified in `BW1` and `BW2` as representative samples for computing the statistics for their respective regions, which it then uses in segmentation. The scribbles specified by `BW1` and `BW2` (regions that are logical true) should not overlap. The underlying algorithm uses the statistics estimated over the regions marked by the scribbles for segmentation. The greater the number of pixels marked by scribbles, the more accurate the estimation of the region statistics, which typically leads to more accurate segmentation. Therefore, it is a good practice to provide as many scribbles as possible. Typically, provide at least a few hundred pixels as scribbles for each region.

`L = imseggeodesic(RGB,BW1,BW2,BW3)` segments the input image `RGB`, returning a segmented image with three segments (ternary segmentation) with the region labels specified by label matrix `L`. `BW1`, `BW2`, and `BW3` are binary images that specify the location of the initial seed regions or scribbles for the three regions. The scribbles specified by `BW1`, `BW2`, and `BW3` (regions that are logical true) should not overlap.

`[L,P] = imseggeodesic(____)` returns the probability for each pixel belonging to each of the labels in matrix `P`.

`[L, P] = imseggeodesic(___,Name,Value,...)` segments the image using name-value pairs to control aspects of segmentation. Parameter names can be abbreviated.

Examples

Segment Image into Two Regions Using Color Information

Read image into workspace and display it.

```
RGB = imread('yellowlily.jpg');  
imshow(RGB, 'InitialMagnification',50)  
hold on
```



Specify the initial seed regions or "scribbles" for the foreground object, in the form [left_topR left_topC bottom_rightR bottom_rightC].


```
bbox1 = [700 350 820 775];  
BW1 = false(size(IMG,1),size(IMG,2));  
BW1(bbox1(1):bbox1(3),bbox1(2):bbox1(4)) = true;
```

Specify the initial seed regions or "scribbles" for the background.

```
bbox2 = [1230 90 1420 1000];  
BW2 = false(size(IMG,1),size(IMG,2));  
BW2(bbox2(1):bbox2(3),bbox2(2):bbox2(4)) = true;
```

Display seed regions. The foreground is in red and the background is blue.

```
visboundaries(BW1,'Color','r');  
visboundaries(BW2,'Color','b');
```



Segment the image.


```
[L,P] = imseggeodesic( RGB, BW1, BW2 );
```

Display results.


```
figure
imshow(label2rgb(L), 'InitialMagnification', 50)
title('Segmented image')

figure
imshow(P(:,:,1), 'InitialMagnification', 50)
title('Probability that a pixel belongs to the foreground')
```

Segmented image



Probability that a pixel belongs to the foreground



Segment Image into Three Regions Using Color Information


```
RGB = imread('yellowlily.jpg');  
imshow(RGB, 'InitialMagnification', 50)  
hold on
```



Creates scribbles for three regions. Note that you can specify the scribbles interactively using tools such as `roipoly`, `imfreehand`, `imrect`, `impoly`, and `imellipse`. Region 1 is the yellow flower. Region 2 is the green leaves. Region 3 is the background.


```
region1 = [350 700 425 120]; % [x y w h] format
BW1 = false(size(RGB,1),size(RGB,2));
BW1(region1(2):region1(2)+region1(4),region1(1):region1(1)+region1(3)) = true;

region2 = [800 1124 120 230];
BW2 = false(size(RGB,1),size(RGB,2));
BW2(region2(2):region2(2)+region2(4),region2(1):region2(1)+region2(3)) = true;

region3 = [20 1320 480 200; 1010 290 180 240];
BW3 = false(size(RGB,1),size(RGB,2));
BW3(region3(1,2):region3(1,2)+region3(1,4),region3(1,1):region3(1,1)+region3(1,3)) = true;
BW3(region3(2,2):region3(2,2)+region3(2,4),region3(2,1):region3(2,1)+region3(2,3)) = true;
```

Display the seed regions.

```
visboundaries(BW1,'Color','r');
visboundaries(BW2,'Color','g');
visboundaries(BW3,'Color','b');
```



Segment the image.

```
[L,P] = imseggeodesic(RGB,BW1,BW2,BW3, 'AdaptiveChannelWeighting', true);
```

Display results.

```
figure
imshow(label2rgb(L),'InitialMagnification', 50)
title('Segmented image with three regions')

figure
imshow(P(:,:,2),'InitialMagnification', 50)
title('Probability that a pixel belongs to region/label 2')
```

Segmented image with three regions



Probability that a pixel belongs to region/label 2



RGB image

Input Arguments

Image to be segmented, specified as a valid RGB image. `imseggeodesic` converts the input RGB image to the YCbCr color space before performing the segmentation.

```
Example: RGB = imread('peppers.png');
```

Data Types: `double` | `uint8` | `uint16`

BW1 — Scribble image for first region

logical matrix

Scribble image, specified as a logical matrix. **BW1** must have the same number of rows and columns as the input image `RGB`. To specify the scribbles interactively, use `roipoly`, `imfreehand`, `imrect`, `impoly`, or `imellipse`.

```
Example: bbox1 = [700 350 820 775]; BW1 =  
false(size(RGB,1),size(RGB,2));  
BW1(bbox1(1):bbox1(3),bbox1(2):bbox1(4)) = true;
```

Data Types: `logical`

BW2 — Scribble image for second region

logical matrix

Scribble image, specified as a logical matrix. **BW2** must have the same number of rows and columns as the input image `RGB`. To specify the scribbles interactively, use `roipoly`, `imfreehand`, `imrect`, `impoly`, or `imellipse`.

```
Example: bbox2 = [1230 90 1420 1000];  
BW2 = false(size(RGB,1),size(RGB,2));  
BW2(bbox2(1):bbox2(3),bbox2(2):bbox2(4)) = true;
```

Data Types: `logical`

BW3 — Scribble image for third region

logical matrix

Scribble image, specified as a logical matrix. **BW3** must have the same number of rows and columns as the input image `RGB`. To specify the scribbles interactively, use `roipoly`, `imfreehand`, `imrect`, `impoly`, or `imellipse`.

```
Example: bbox3 = [20 1320 480 200; 1010 290 180  
240]; BW3 = false(size(RGB,1),size(RGB,2));  
BW3(bbox3(1,2):bbox3(1,2)+bbox3(1,4),bbox3(1,1):bbox3(1,1)+bbox3(1,3))  
= true;
```


Data Types: `logical`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1,Value1,...,NameN,ValueN`.

```
Example: [L,P] = imseggeodesic( RGB, BW1, BW2, BW3,
    'AdaptiveChannelWeighting', true);
```

'AdaptiveChannelWeighting' — Use adaptive channel weighting

`false` (default) | `true`

Use adaptive channel weighting, specified as a logical scalar. When `true`, `imseggeodesic` weights the channels proportional to the amount of discriminatory information they have that is useful for segmentation (based on the scribbles provided as input). When `false` (the default), `imseggeodesic` weights all the channels equally.

```
Example: [L,P] = imseggeodesic( RGB, BW1, BW2, BW3,
    'AdaptiveChannelWeighting', true);
```

Data Types: `logical`

Output Arguments

L — Label matrix

double matrix

Label matrix, returned as a `double` matrix where the elements are integer values greater than or equal to 0. Pixels labeled 0 are the background and pixels labeled 1 identify a segmented region. Pixels labeled 2 identify another segmented region in trinary segmentation.

P — Probability a pixel belongs to a labeled region

M-by-*N*-by-2 double matrix (binary segmentation) | *M*-by-*N*-by-3 double matrix (trinary segmentation)

Probability a pixel belongs to a labeled region, specified as an *M*-by-*N*-by-2 matrix for binary segmentation or an *M*-by-*N*-by-3 matrix for trinary segmentation. *M* and *N* are

the number of rows and columns in the input image. $P(i, j, k)$ specifies the probability of pixel at location (i, j) belonging to label k . P is of class `double`.

More About

Tips

- The scribbles for the two (or three) regions should not overlap each other. Each scribble matrix (`BW1`, `BW2`, and `BW3`) should be nonempty, that is, there should be at least one pixel (although the more the better) marked as logical true in each of the scribbles.

Algorithms

`imseggeodesic` uses a geodesic distance-based color segmentation algorithm (similar to [1]).

References

- [1] A. Protiere and G. Sapiro, *Interactive Image Segmentation via Adaptive Weighted Distances*, IEEE Transactions on Image Processing, Volume 16, Issue 4, 2007.

See Also

`activecontour` | `Color Thresholder` | `imsegfmm` | `visboundaries`

Introduced in R2015a

imsharpen

Sharpen image using unsharp masking

Syntax

```
B = imsharpen(A)
B = imsharpen(A,Name,Value,...)
```

Description

`B = imsharpen(A)` returns an enhanced version of the grayscale or truecolor (RGB) input image `A`, where the image features, such as edges, have been sharpened using the unsharp masking method.

`B = imsharpen(A,Name,Value,...)` sharpens the image using name-value pairs to control aspects of unsharp masking. Parameter names can be abbreviated.


Examples

Sharpen Image

Read an image into the workspace and display it.

```
a = imread('hestain.png');
imshow(a)
title('Original Image');
```


Original Image



Sharpen the image using the `imsharpen` function and display it.

```
b = imsharpen(a);  
figure, imshow(b)  
title('Sharpened Image');
```

Sharpened Image




Control the Amount of Sharpening at the Edges

Read an image into the workspace and display it.


```
a = imread('rice.png');  
imshow(a), title('Original Image');
```

Original Image



Sharpen image, specifying the radius and amount parameters.

```
b = imsharpen(a, 'Radius', 2, 'Amount', 1);  
figure, imshow(b)  
title('Sharpened Image');
```

Sharpened Image

Input Arguments

A — Grayscale or truecolor (RGB) image to be enhanced

nonsparse numeric array

Grayscale or truecolor (RGB) image to be enhanced, specified as a nonsparse, numeric array.

If **A** is a truecolor (RGB) image, `imsharpen` converts the image to the $L^*a^*b^*$ colorspace, applies sharpening to the L^* channel only, and then converts the image back to the RGB colorspace before returning it as the output image **B**.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

Example: `'Radius', 1.5`

'Radius' — Standard deviation of the Gaussian lowpass filter

1 (default) | numeric

Standard deviation of the Gaussian lowpass filter, specified as a numeric value. This value controls the size of the region around the edge pixels that is affected by sharpening. A large value sharpens wider regions around the edges, whereas a small value sharpens narrower regions around edges.

Example: `'Radius', 1.5`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

'Amount' — Strength of the sharpening effect

0.8 (default) | numeric

Strength of the sharpening effect, specified as a numeric value. A higher value leads to larger increase in the contrast of the sharpened pixels. Typical values for this parameter are within the range [0 2], although values greater than 2 are allowed. Very large values for this parameter may create undesirable effects in the output image.

Example: `'Amount', 1.2`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

'Threshold' — Minimum contrast required for a pixel to be considered an edge pixel

0 (default) | scalar in the range [0 1]

Minimum contrast required for a pixel to be considered an edge pixel, specified as a scalar in the range [0 1]. Higher values (closer to 1) allow sharpening only in high-contrast regions, such as strong edges, while leaving low-contrast regions unaffected. Lower values (closer to 0) additionally allow sharpening in relatively smoother regions of the image. This parameter is useful in avoiding sharpening noise in the output image.

Example: 'Threshold', 0.7

Data Types: single | double | int8 | int16 | int32 | int64 | uint8 | uint16 | uint32 | uint64

Output Arguments

B — Sharpened image

nonsparse array the same size and class as the input image.

Image that has been sharpened, returned as a nonsparse array the same size and class as the input image.

More About

sharpening

Sharpness is actually the contrast between different colors. A quick transition from black to white looks sharp. A gradual transition from black to gray to white looks blurry. Sharpening images increases the contrast along the edges where different colors meet.

Unsharp masking

The unsharp masking technique comes from a publishing industry process in which an image is sharpened by subtracting a blurred (unsharp) version of the image from itself. Do not be confused by the name of this filter: an unsharp filter is an operator used to sharpen an image.

See Also

`fspecial` | `imadjust` | `imcontrast`

Introduced in R2013a

imshow

Display image

Syntax

```
imshow(I)
imshow(I,RI)

imshow(X,map)
imshow(X,RX,map)

imshow(filename)

imshow( ____,Name,Value... )

imshow(gpuarrayIM, ____)

imshow(I,[low high])
imshow( ____,Name,Value,... )

himage = imshow( ____)
```

Description

`imshow(I)` displays the image `I` in a Handle Graphics[®] figure, where `I` is a grayscale, RGB (truecolor), or binary image. For binary images, `imshow` displays pixels with the value 0 (zero) as black and 1 as white.

`imshow(I,RI)` displays the image `I` with associated 2-D spatial referencing object `RI`.

`imshow(X,map)` displays the indexed image `X` with the colormap `map`. A color map matrix may have any number of rows, but it must have exactly 3 columns. Each row is interpreted as a color, with the first element specifying the intensity of red light, the second green, and the third blue. Color intensity can be specified on the interval 0.0 to 1.0.

`imshow(X,RX,map)` displays the indexed image `X` with associated 2-D spatial referencing object `RX` and colormap `MAP`.

`imshow(filename)` displays the image stored in the graphics file specified by the text string `filename`.

`imshow(____, Name, Value, ...)` displays the image, specifying additional options with one or more `Name, Value` pair arguments, using any of the previous syntaxes.

`imshow(gpuarrayIM, ____)` displays the image contained in a `gpuArray`. This syntax requires the Parallel Computing Toolbox.

`imshow(I, [low high])` displays the grayscale image `I`, specifying the display range as a two-element vector, `[low high]`. For more information, see the `DisplayRange` parameter.

`imshow(____, Name, Value, ...)` displays an image, using name-value pairs to control aspects of the operation.

`himage = imshow(____)` returns the handle to the image object created by `imshow`.

Examples

Display image from file

Specify image file.

```
imshow('board.tif')
```

Display indexed image

Read indexed image and associated color map from file and display it.

```
[X,map] = imread('trees.tif');  
imshow(X,map)
```

Display grayscale image

Read grayscale image from file and display it.

```
I = imread('cameraman.tif');  
imshow(I)
```

Display grayscale image, adjusting display range

Read grayscale image and specify display range.

```
I = imread('cameraman.tif');  
h = imshow(I,[0 80]);
```

Display grayscale image using associated spatial referencing object

Read image into workspace.

```
I = imread('pout.tif');
```

Create a spatial referencing object associated with the image. Then specify *X* and *Y* limits in a world coordinate system.

```
RI = imref2d(size(I));  
RI.XWorldLimits = [0 3];  
RI.YWorldLimits = [2 5];
```

Display the image, specifying the spatial referencing object.

```
imshow(I,RI);
```

Display Image on a GPU

Read image into a `gpuArray`.

```
X = gpuArray(imread('pout.tif'));
```

Display it.

```
figure; imshow(X)
```

Input Arguments

I — Input image

grayscale image | RGB image | binary image

Input image, specified as a grayscale, RGB, or binary image.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

X — Indexed image

2-D array of real numeric values.

Indexed image, specified as a 2-D array of real numeric values. The values in *X* are an index into `Map`, an *n*-by-3 array of RGB values.

Data Types: `single` | `double` | `uint8` | `logical`

map — Colormap

n-by-3 array

Colormap, specified as an *n*-by-3 array. Each row specified an RGB color value.

Data Types: `single` | `double` | `uint8` | `logical`

filename — Name of file containing an image

text string

Name of file containing an image, specified as a text string. The image must be readable by `imread` or by `dicomread`. `imshow` displays the image but does not store the image data in the MATLAB workspace. If the file contains multiple images, `imshow` displays the first image in the file.

Data Types: `char`

RI — 2-D spatial referencing object associated with the input image

`imref2d` object

2-D spatial referencing object associated with input image, specified as an `imref2d` object.

RX — 2-D spatial referencing object associated with an indexed image

`imref2d` object

2-D spatial referencing object associated with an indexed image, specified as a `imref2d` object.

gpuarrayIM — Image to be processed on a graphics processing unit (GPU)

`gpuArray` object

Image to be processed on a graphics processing unit (GPU), specified as a `gpuArray`.

[low high] — Display range of the image

two-element vector

Display range of the image, specified as a two-element vector.

Example: `[50 250]`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

Example: 'Border', 'tight'

'Border' — Control whether figure window includes a border

value returned by `iptgetpref('ImshowBorder')` (default) | 'tight' or 'loose'

Controls whether `imshow` includes a border around the image displayed in the figure window. 'tight' or 'loose' There can still be a border if the image is very small, or if there are other objects besides the image and its axes in the figure.

Example:

Data Types: char

'Colormap' — Value of figure's colormap property

(default) | 2-D, real, *m*-by-3 matrix

`imshow` uses this to set the figure's `colormap` property. Use this parameter to view grayscale images in false color. If you specify an empty colormap (`[]`), `imshow` ignores this parameter.

Example:

Data Types: double

'DisplayRange' — Display range of grayscale image

`[min(I(:)) max(I(:))]` (default) | two-element vector

Display range of a grayscale image, specified as a two-element vector `[LOW HIGH]`. `imshow` displays the value `low` (and any value less than `low`) as black, and the value `high` (and any value greater than `high`) as white. Values in between are displayed as intermediate shades of gray, using the default number of gray levels. If you specify an empty matrix (`[]`), `imshow` uses `[min(I(:)) max(I(:))]`; that is, use the minimum value in `I` as black, and the maximum value as white.

Note: Including the parameter name is optional, except when the image is specified by a filename. The syntax `imshow(I, [LOW HIGH])` is equivalent to

`imshow(I, 'DisplayRange', [LOW HIGH])`. When calling `imshow` with a filename, you must specify the `'DisplayRange'` parameter.

Example: `h = imshow(I, 'DisplayRange', [0 80]);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

'InitialMagnification' — Initial magnification used to display image

value returned by `iptgetpref('ImshowInitialMagnification')` (default) | numeric scalar value | text string `'fit'`

Initial magnification used to display an image, specified as the numeric value or the text string `'fit'`.

When set to 100, `imshow` displays the image at 100% magnification (one screen pixel for each image pixel). When set to `'fit'`, `imshow` scales the entire image to fit in the window.

On initial display, `imshow` always displays the entire image. If the magnification value is large enough that the image would be too big to display on the screen, `imshow` warns and displays the image at the largest magnification that fits on the screen.

If the image is displayed in a figure with its `'WindowStyle'` property set to `'docked'`, `imshow` warns and displays the image at the largest magnification that fits in the figure.

Note: If you specify the axes position (using `subplot` or `axes`), `imshow` ignores any initial magnification you might have specified and defaults to the `'fit'` behavior.

When used with the `'Reduce'` parameter, only `'fit'` is allowed as an initial magnification.

Example:

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `char`

'Parent' — Axes that is the parent of the image object

axes object

Axes that is the parent of the image object, specified as an axes object. Created by `imshow`.

Note: If you are building a GUI where you want to control the figure and axes properties, be sure to use the `imshow(..., 'Parent', ax)` syntax.

Data Types: `function_handle`

'Reduce' — Subsample image in filename

logical value

Subsample image in `filename`, specified as a logical value. Only valid for TIFF images. Use this parameter to display overviews of very large images.

Data Types: `logical`

'Xdata' — Limits along X axis of a nondefault spatial coordinate system

two-element vector

Limits along X axis of a nondefault spatial coordinate system, specified as a two-element vector. Establishes a nondefault spatial coordinate system by specifying the image XData. The value can have more than two elements, but only the first and last elements are actually used.

Example: `[100 200]`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

'YData' — Limits along Y axis of a nondefault spatial coordinate system

two-element vector

Limits along Y axis of a nondefault spatial coordinate system, specified as a two-element vector. The value can have more than two elements, but only the first and last elements are actually used.

Example: `[100 200]`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

Output Arguments

himage — Image object created by `imshow`

handle

Image object created by `imshow`, specified as a handle.

Alternative Functionality


App

`imshow` is the toolbox's fundamental image display function, optimizing figure, axes, and image object property settings for image display. `imshow_tool` provides all the image display capabilities of `imshow` but also provides access to several other tools for navigating and exploring images, such as the Pixel Region tool, Image Information tool, and the Adjust Contrast tool. `imshow_tool` presents an integrated environment for displaying images and performing some common image processing tasks.

The `imshow` function is not supported when MATLAB is started with the `-nojvm` option.

You can access `imshow` through the Plot Selector workspace tool, which is represented by

this icon: . In your workspace, select the data you want

to display. The Plot Selector icon changes to look like this: . Scroll down to **Image Processing Toolbox Plots**. Select **imshow(I)**.

More About

Tips

- You can use the `iptsetpref` function to set several toolbox preferences that modify the behavior of `imshow`.
 - `'ImshowBorder'` controls whether `imshow` displays the image with a border around it.
 - `'ImshowAxesVisible'` controls whether `imshow` displays the image with the axes box and tick labels.
 - `'ImshowInitialMagnification'` controls the initial magnification for image display, unless you override it in a particular call by specifying `imshow(..., 'InitialMagnification', initial_mag)`.

For more information about these preferences, see `iptprefs`.

See Also

`gpuArray` | `image` | `imagesc` | `imread` | `imtool` | `iptprefs` | `subimage` |
`trueSize` | `warp`

Introduced before R2006a

imshowpair

Compare differences between images

Syntax

```
h = imshowpair(A,B)
h = imshowpair(A,RA,B,RB)
h = imshowpair( ____,method)
h = imshowpair( ____,Name,Value)
```

Description

`h = imshowpair(A,B)` creates a visualization of the differences between images A and B. If A and B are different sizes, `imshowpair` pads the smaller dimensions with zeros on the bottom and right edges so that the two images are the same size. `h` is a handle to the HG image object created by `imshowpair`.

`h = imshowpair(A,RA,B,RB)` displays the differences between images A and B, using the spatial referencing information provided in RA and RB. RA and RB are spatial referencing objects.

`h = imshowpair(____,method)` uses the visualization method specified by `method`.

`h = imshowpair(____,Name,Value)` specifies additional options with one or more Name,Value pair arguments, using any of the previous syntaxes.

Examples

Display Two Images That Differ by Rotation Offset

Display a pair of grayscale images with two different visualization methods, 'diff' and 'blend'.

Load an image into the workspace. Create a copy with a rotation offset applied.

```
A = imread('cameraman.tif');  
B = imrotate(A,5,'bicubic','crop');
```

Display the difference of A and B.

```
imshowpair(A,B,'diff');
```



Display a blended overlay A and B.

```
figure;  
imshowpair(A,B,'blend','Scaling','joint');
```



Display Two Spatially Referenced Images with Different Brightness Ranges

Read an image. Create a copy and apply rotation and a brightness adjustment.


```
A = dicomread('CT-MONO2-16-ankle.dcm');  
B = imrotate(A,10,'bicubic','crop');  
B = B * 0.2;
```

In this case, we know that the resolution of images A and B is 0.2mm. Provide this information using two spatial referencing objects.

```
RA = imref2d(size(A),0.2,0.2);  
RB = imref2d(size(B),0.2,0.2);
```

Display the images with the default method ('falsecolor') and apply brightness scaling independently to each image. Specify the axes that will be the parent of the image object created by `imshowpair`.

```
figure;  
hAx = axes;  
imshowpair(A,RA,B,RB,'Scaling','independent','Parent',hAx);
```



Input Arguments

A — Image to be displayed

grayscale image | truecolor image | binary image

Image to be displayed, specified as a grayscale, truecolor, or binary image.

B — Image to be displayed

grayscale image | truecolor image | binary image

Image to be displayed, specified as a grayscale, truecolor, or binary image.

RA — Spatial referencing information about an input image

spatial referencing object

Spatial referencing information about an input image, specified as spatial referencing object, of class `imref2d`.

RB — Spatial referencing information about an input image

spatial referencing object

Spatial referencing information about an input image, specified as spatial referencing object, of class `imref2d`.

method — Visualization method to display combined images

'falsecolor' (default) | 'blend' | 'diff' | 'montage'

Visualization method to display combined images, specified as one of the text strings in the following table.

Method	Description
'falsecolor'	Creates a composite RGB image showing A and B overlaid in different color bands. Gray regions in the composite image show where the two images have the same intensities. Magenta and green regions show where the intensities are different. This is the default method.
'blend'	Overlays A and B using alpha blending.
'diff'	Creates a difference image from A and B.
'montage'	Places A and B next to each other in the same image.

Example: `imshowpair(A,B,'montage')` displays A and B next to each other.

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name,Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single

quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

Example: `'Scaling', 'joint'` scales the intensity values of A and B together as a single data set.

'ColorChannels' — Output color channel for each input image

`'green-magenta'` (default) | `[R G B]` | `'red-cyan'`

Output color channel for each input image, specified as one of the following character strings:

<code>[R G B]</code>	A three element vector that specifies which image to assign to the red, green, and blue channels. The R, G, and B values must be 1 (for the first input image), 2 (for the second input image), and 0 (for neither image).
<code>'red-cyan'</code>	A shortcut for the vector <code>[1 2 2]</code> , which is suitable for red/cyan stereo anaglyphs.
<code>'green-magenta'</code>	A shortcut for the vector <code>[2 1 2]</code> , which is a high contrast option, ideal for people with many kinds of color blindness.

'Parent' — Parent of image object created by `imshowpair`

handle to an HG axes object

Parent of image object created by `imshowpair`, specified as a handle to an HG axes that is the parent of the image object created by `imshowpair`.

'Scaling' — Intensity scaling option

`'independent'` (default) | `'joint'` | `'none'`

Intensity scaling option, specified as one of the character strings in the following table.

<code>'independent'</code>	Scales the intensity values of A and B independently from each other.
<code>'joint'</code>	Scales the intensity values in the images jointly as if they were together in the same image. This option is useful when you want to visualize registrations of monomodal images, where one image contains fill values that are outside the dynamic range of the other image.

'none'

No additional scaling.

Output Arguments

h — Image object

handle to Handle Graphics image object

Image object, returned as a handle to the Handle Graphics image object created by `imshowpair`.

More About

Tips

- Use `imfuse` to create composite visualizations that you can save to a file. Use `imshowpair` to display composite visualizations to the screen.

See Also

`imfuse` | `imregister` | `imshow` | `imtransform`

Introduced in R2012a

imsubtract

Subtract one image from another or subtract constant from image

Syntax

```
Z = imsubtract(X,Y)
```

Description

`Z = imsubtract(X,Y)` subtracts each element in array `Y` from the corresponding element in array `X` and returns the difference in the corresponding element of the output array `Z`. `X` and `Y` are real, nonsparse numeric arrays of the same size and class, or `Y` is a double scalar. The array returned, `Z`, has the same size and class as `X` unless `X` is logical, in which case `Z` is double.

If `X` is an integer array, elements of the output that exceed the range of the integer type are truncated, and fractional values are rounded.

Examples

Subtract two `uint8` arrays. Note that negative results are rounded to 0.

```
X = uint8([ 255 10 75; 44 225 100]);  
Y = uint8([ 50 50 50; 50 50 50 ]);  
Z = imsubtract(X,Y)  
Z =
```

```
    205     0    25  
     0    175    50
```

Estimate and subtract the background of an image:

```
I = imread('rice.png');  
background = imopen(I,strel('disk',15));  
Ip = imsubtract(I,background);  
imshow(Ip,[])
```

Subtract a constant value from an image:

```
I = imread('rice.png');  
Iq = imsubtract(I,50);  
figure, imshow(I), figure, imshow(Iq)
```

See Also

[imabsdiff](#) | [imadd](#) | [imcomplement](#) | [imdivide](#) | [imlincomb](#) | [immultiply](#)

Introduced before R2006a

imtool

Image Viewer app

Syntax

```
imtool
imtool(I)
imtool(I,[low high])
imtool(RGB)
imtool(BW)
imtool(X,map)
imtool(filename)
hfigure = imtool(...)
imtool close all
imtool(...,param1,val1,param2,val2,...)
```

Description

`imtool` opens the Image Viewer app in an empty state. Use the **File** menu options **Open** or **Import from Workspace** to choose an image for display.

`imtool(I)` displays the grayscale image `I` in the Image Viewer.

`imtool(I,[low high])` displays the grayscale image `I` in the Image Viewer, specifying the display range for `I` in the vector `[low high]`. The value `low` (and any value less than `low`) is displayed as black, the value `high` (and any value greater than `high`) is displayed as white. Values in between are displayed as intermediate shades of gray. The Image Viewer uses the default number of gray levels. If you use an empty matrix (`[]`) for `[low high]`, the Image Viewer uses `[min(I(:)) max(I(:))]`; the minimum value in `I` is displayed as black, and the maximum value is displayed as white.

`imtool(RGB)` displays the truecolor image `RGB` in the Image Viewer.

`imtool(BW)` displays the binary image `BW` in the Image Viewer. Pixel values of 0 display as black; pixel values of 1 display as white.

`imtool(X,map)` displays the indexed image `X` with colormap `map` in the Image Viewer.

`imtool(filename)` displays the image contained in the graphics file `filename` in the Image Viewer. The file must contain an image that can be read by `imread` or `dicomread` or a reduced resolution dataset (R-Set) created by `rsetwrite`. If the file contains multiple images, the first one is displayed. The file must be in the current directory or on the MATLAB path.

`hfigure = imtool(...)` returns `hfigure`, a handle to the figure created by the Image Viewer. `close(hfigure)` closes the Image Viewer.

`imtool close all` closes all open Image Viewers.

`imtool(...,param1,val1,param2,val2,...)` displays the image, specifying parameters and corresponding values that control various aspects of the image display. The following table lists all `imshow` parameters. Parameter names can be abbreviated, and case does not matter.

Parameter	Value
'Colormap'	2-D, real, m -by-3 matrix specifying the colormap to use for the figure's <code>colormap</code> property. Use this parameter to view grayscale images in false color. If you specify an empty colormap (<code>[]</code>), <code>imtool</code> ignores this parameter.
'DisplayRange'	Two-element vector [<code>LOW HIGH</code>] that controls the display range of a grayscale image. See the <code>imtool(I,[low high])</code> syntax for more details about how to set this parameter. Note: Including the parameter name is optional, except when the image is specified by a filename. The syntax <code>imtool(I,[LOW HIGH])</code> is equivalent to <code>imtool(I,'DisplayRange',[LOW HIGH])</code> . However, the 'DisplayRange' parameter must be specified when calling <code>imtool</code> with a filename, as in the syntax <code>imtool(filename,'DisplayRange',[LOW HIGH])</code> .
'InitialMagnification'	One of two text strings: 'adaptive' or 'fit' or a numeric scalar value that specifies the initial magnification used to display the image. When set to 'adaptive', the entire image is visible on initial display. If the image is too large to display on the screen, the Image Viewer displays the image at the largest magnification that fits on the screen.

Parameter	Value
	<p>When set to 'fit', the Image Viewer scales the entire image to fit in the window.</p> <p>When set to a numeric value, the value specifies the magnification as a percentage. For example, if you specify 100, the Image Viewer displays the image at 100% magnification (one screen pixel for each image pixel).</p> <hr/> <p>Note: When the image aspect ratio is such that less than one pixel would be displayed in either dimension at the requested magnification, the Image Viewer issues a warning and displays the image at 100%.</p> <hr/> <p>By default, the initial magnification parameter is set to the value returned by <code>iptgetpref('ImtoolInitialMagnification')</code>.</p>

Class Support

A truecolor image can be `uint8`, `uint16`, `single`, or `double`. An indexed image can be `logical`, `uint8`, `single`, or `double`. A grayscale image can be `uint8`, `uint16`, `int16`, `single`, or `double`. A binary image must be `logical`. A binary image is of class `logical`.

For all grayscale images having integer types, the default display range is `[intmin(class(I)) intmax(class(I))]`.

For grayscale images of class `single` or `double`, the default display range is `[0 1]`. If the data range of a `single` or `double` image is much larger or smaller than the default display range, you might need to experiment with setting the display range to see features in the image that would not be visible using the default display range.

Large Data Support

To view very large TIFF or NITF images that will not fit into memory, you can use `rsetwrite` to create a reduced resolution dataset (R-Set) viewable in the Image Viewer.

R-Sets can also improve performance of the Image Viewer for large images that fit in memory.

The following tools can be used with an R-Set: Overview, Zoom, Pan, Image Information, and Distance. Other tools, however, will not work with an R-Set. You cannot use the Pixel Region, Adjust Contrast, Crop Image, and Window/Level tools. Please note that the Pixel Information tool displays only the x and y coordinates of a pixel and not the associated intensity, index, or [R G B] values.

Related Toolbox Preferences

You can use the Image Processing Preferences dialog box to set toolbox preferences that modify the behavior of the Image Viewer. To access the dialog, select **File > Preferences** in the MATLAB desktop or Image Viewer menu. Also, you can set preferences programmatically with `iptsetpref`. The Image Viewer preferences include:

- `'ImtoolInitialMagnification'` controls the initial magnification for image display. To override this toolbox preference, specify the `'InitialMagnification'` parameter when you call `imtool`, as follows:

```
imtool(...,'InitialMagnification',initial_mag).
```

- `'ImtoolStartWithOverview'` controls whether the Overview tool opens automatically when you open an image using the Image Viewer. Possible values:

`true`— Overview tool opens when you open an image.

`{false}`— Overview tool does not open when you open an image. This is the default behavior.

For more information about these preferences, see `iptprefs`.

Examples

Display an image from a file.

```
imtool('board.tif')
```

Display an indexed image.

```
[X,map] = imread('trees.tif');
```

```
imshow(X,map)
```

Display a grayscale image.

```
I = imread('cameraman.tif');  
imshow(I)
```

Display a grayscale image, adjusting the display range.

```
h = imshow(I,[0 80]);  
close(h)
```

More About

Tips

`imshow` is the toolbox's fundamental image display function, optimizing figure, axes, and image object property settings for image display. The Image Viewer provides all the image display capabilities of `imshow` but also provides access to several other tools for navigating and exploring images, such as the Pixel Region tool, Image Information tool, and the Adjust Contrast tool. The Image Viewer presents an integrated environment for displaying images and performing some common image processing tasks.

You can access the Image Viewer through the Apps tab. Navigate to the Image Processing and Computer Vision group and select Image Viewer.

See Also

`imageinfo` | `imcontrast` | `imoverview` | `impixelregion` | `imread` | `imshow` | `iptprefs` | `rsetwrite`

Introduced before R2006a

imtophat

Top-hat filtering

Syntax

```
IM2 = imtophat(IM,SE)
IM2 = imtophat(IM,NHOOD)
gpuarrayIM2 = imtophat(gpuarrayIM, ___ )
```

Description

`IM2 = imtophat(IM,SE)` performs morphological top-hat filtering on the grayscale or binary input image `IM`. Top-hat filtering computes the morphological opening of the image (using `imopen`) and then subtracts the result from the original image. `imtophat` uses the structuring element `SE`, where `SE` is returned by `strel`. `SE` must be a single structuring element object, not an array containing multiple structuring element objects.

`IM2 = imtophat(IM,NHOOD)` where `NHOOD` is an array of 0s and 1s that specifies the size and shape of the structuring element, is the same as `imtophat(IM,strel(NHOOD))`.

`gpuarrayIM2 = imtophat(gpuarrayIM, ___)` performs the operation on a GPU. `NHOOD` is the structuring element specified by `strel(NHOOD)`, if `NHOOD` is an array of 0s and 1s that specifies the structuring element neighborhood. If `NHOOD` is a `gpuArray`, `strel(gather(NHOOD))` specifies the structuring element neighborhood.

“Code Generation” on page 1-1078 support: Yes.

“MATLAB Function Block” on page 1-1078 support: Yes.

Class Support

`IM` can be numeric or logical and must be nonsparse. The output image `IM2` has the same class as the input image. If the input is binary (`logical`), the structuring element must be flat.

`gpuarrayIM` must be a `gpuArray` of type `uint8` or `logical`. When used with a `gpuArray`, the structuring element must be flat and two-dimensional.

The output has the same class as the input.


Examples

Use Top-hat Filtering to Correct Uneven Illumination

You can use top-hat filtering to correct uneven illumination when the background is dark. This example uses top-hat filtering with a disk-shaped structuring element to remove the uneven background illumination from an image.

Read an image and display it.

```
original = imread('rice.png');  
figure, imshow(original)
```




Create the structuring element.

```
se = strel('disk',12);
```

Perform the top-hat filtering and display the image.

```
tophatFiltered = imtophat(original,se);  
figure, imshow(tophatFiltered)
```



Use `imadjust` to improve the visibility of the result.

```
contrastAdjusted = imadjust(tophatFiltered);  
figure, imshow(contrastAdjusted)
```



Use Top-hat Filtering to Correct Uneven Illumination on the GPU

You can use top-hat filtering to correct uneven illumination when the background is dark. This example uses top-hat filtering with a disk-shaped structuring element to remove the uneven background illumination from an image.

Read an image and display it.

```
original = imread('rice.png');  
figure, imshow(original)
```

Create the structuring element.

```
se = strel('disk',12);
```

Perform the top-hat filtering and display the image. Note how the example passes the image to the `gpuArray` function before passing it to the `imtophat` function.

```
tophatFiltered = imtophat(gpuArray(original),se);  
figure, imshow(tophatFiltered)
```

Use `imadjust` to improve the visibility of the result. The `gather` function is used to retrieve the contents of the `gpuArray` from the GPU.

```
contrastAdjusted = imadjust(gather(tophatFiltered));  
figure, imshow(contrastAdjusted)
```

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, the image input argument, **IM**, must be 2-D or 3-D and the structuring element input argument, **SE**, must be a compile-time constant.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`imbothat` | `strel` | `offsetstrel` | `gpuArray`

Introduced before R2006a

imtransform

Apply 2-D spatial transformation to image

Compatibility

`imtransform` is not recommended. Use `imwarp` instead.

Syntax

```
B = imtransform(A,tform)
B = imtransform(A,tform,interp)
[B,xdata,ydata] = imtransform(...)
[B,xdata,ydata] = imtransform(...,Name,Value)
```

Description

`B = imtransform(A,tform)` transforms the image `A` according to the 2-D spatial transformation defined by `tform`. If `ndims(A) > 2`, such as for an RGB image, then `imtransform` applies the same 2-D transformation to all 2-D planes along the higher dimensions.

`B = imtransform(A,tform,interp)` specifies the form of interpolation to use.

`[B,xdata,ydata] = imtransform(...)` returns the location of the output image `B` in the output X-Y space. By default, `imtransform` calculates `xdata` and `ydata` automatically so that `B` contains the entire transformed image `A`. However, you can override this automatic calculation by specifying values for the 'XData' and 'YData' arguments.

`[B,xdata,ydata] = imtransform(...,Name,Value)` transforms the image with additional options for controlling various aspects of the spatial transformation specified by one or more `Name,Value` pair arguments.

Input Arguments

A

An image of any nonsparse numeric class (real or complex) or of class `logical`.

`tform`

A spatial transformation structure returned by `maketform` or `cp2tform`. `imtransform` assumes spatial-coordinate conventions for the transformation `tform`. Specifically, the first dimension of the transformation is the horizontal or x -coordinate, and the second dimension is the vertical or y -coordinate. This convention is the reverse of the array subscripting convention in MATLAB.

`interp`

A string that specifies the form of interpolation to use. *interp* can be one of the following strings: `'bicubic'`, `'bilinear'`, or `'nearest'` (nearest-neighbor). Alternatively, `interp` can be a `resampler` structure returned by `makeresampler`. This option allows more control over how `imtransform` performs resampling.

Default: `'bilinear'`

Name-Value Pair Arguments

Optional comma-separated pairs of `Name`, `Value` arguments, where `Name` is the argument name and `Value` is the corresponding value. `Name` must appear within single quotes (`' '`) and is not case sensitive. You can specify several name and value pair arguments in any order as `Name1`, `Value1`, ..., `NameN`, `ValueN`.

`'UData'`

A two-element, real vector that, when combined with `'VData'`, specifies the spatial location of image `A` in the 2-D input space U-V. The two elements of `'UData'` give the u -coordinates (horizontal) of the first and last columns of `A`, respectively.

Default: `[1 size(A,2)]`

`'VData'`

A two-element, real vector that, when combined with `'UData'`, specifies the spatial location of image `A` in the 2-D input space U-V. The two elements of `'VData'` give the v -coordinates (vertical) of the first and last rows of `A`, respectively.

Default: `[1 size(A,1)]`

'XData'

A two-element, real vector that, when combined with `'YData'`, specifies the spatial location of the output image **B** in the 2-D output space X-Y. The two elements of `'XData'` give the *x*-coordinates (horizontal) of the first and last columns of **B**, respectively.

Default: If you do not specify `'XData'` and `'YData'`, `imtransform` estimates values that contain the entire transformed output image. To determine these values, `imtransform` uses the `findbounds` function.

'YData'

A two-element real vector that, when combined with `'XData'`, specifies the spatial location of the output image **B** in the 2-D output space X-Y. The two elements of `'YData'` give the *y*-coordinates (vertical) of the first and last rows of **B**, respectively.

Default: If you do not specify `'XData'` and `'YData'`, `imtransform` estimates values that contain the entire transformed output image. To determine these values, `imtransform` uses the `findbounds` function.

'XYScale'

A one- or two-element real vector. The first element of `'XYScale'` specifies the width of each output pixel in X-Y space. The second element (if present) specifies the height of each output pixel. If `'XYScale'` has only one element, then the same value specifies both width and height.

Default: If you do not specify `'XYScale'` but you do specify `'Size'`, then `imtransform` calculates `'XYScale'` from `'Size'`, `'XData'`, and `'YData'`. If you do not provide `'XYScale'` or `'Size'`, then `imtransform` uses the scale of the input pixels for `'XYScale'`, except in cases where an excessively large output image would result.

Note: In cases where preserving the scale of the input image would result in an excessively large output image, the `imtransform` function automatically increases the `'XYScale'`. To ensure that the output pixel scale matches the input pixel scale, specify the `'XYScale'` parameter. For example, call `imtransform` as shown in the following syntax:

```
B = imtransform(A,T,'XYScale',1)
```

'Size'

A two-element vector of nonnegative integers that specifies the number of rows and columns of the output image **B**. For higher dimensions, `imtransform` takes the size of **B** directly from the size of **A**. Thus, `size(B,k)` equals `size(A,k)` for $k > 2$.

Default: If you do not specify `'Size'`, `imtransform` derives this value from `'XData'`, `'YData'`, and `'XYScale'`.

'FillValues'

An array containing one or several fill values. The `imtransform` function uses fill values for output pixels when the corresponding transformed location in the input image is completely outside the input image boundaries. If **A** is 2-D, `'FillValues'` requires a scalar. However, if **A**'s dimension is greater than two, then you can specify `'FillValues'` as an array whose size satisfies the following constraint: `size(fill_values,k)` must equal either `size(A,k+2)` or 1.

For example, if **A** is a `uint8` RGB image that is 200-by-200-by-3, then possibilities for `'FillValues'` include the following values.

Value	Fill
0	Fill with black
[0;0;0]	Fill with black
255	Fill with white
[255;255;255]	Fill with white
[0;0;255]	Fill with blue
[255;255;0]	Fill with yellow

If **A** is 4-D with size 200-by-200-by-3-by-10, then you can specify `'FillValues'` as a scalar, 1-by-10, 3-by-1, or 3-by-10.

Output Arguments

B

Output image of any nonsparse numeric class (real or complex) or of class `logical`.

xdata

Two-element vector that specifies the x -coordinates of the first and last columns of **B**.

Note: Sometimes the output values **xdata** and **ydata** do not exactly equal the input 'XData' and 'YData' arguments. The values differ either because of the need for an integer number of rows and columns, or because you specify values for 'XData', 'YData', 'XYScale', and 'Size' that are not entirely consistent. In either case, the first element of **xdata** and **ydata** always equals the first element of 'XData' and 'YData', respectively. Only the second elements of **xdata** and **ydata** can be different.

ydata

Two-element vector that specifies the y -coordinates of the first and last rows of **B**.

Examples

Simple Transformation. Apply a horizontal shear to an intensity image:

```
I = imread('cameraman.tif');  
tform = maketform('affine',[1 0 0; .5 1 0; 0 0 1]);  
J = imtransform(I,tform);  
imshow(I), figure, imshow(J)
```



Horizontal Shear

Projective Transformation. Map a square to a quadrilateral with a projective transformation:

```
% Set up an input coordinate system so that the input image
% fills the unit square with vertices (0 0),(1 0),(1 1),(0 1).
I = imread('cameraman.tif');
udata = [0 1]; vdata = [0 1];

% Transform to a quadrilateral with vertices (-4 2),(-8 3),
% (-3 -5),(6 3).
tform = maketform('projective',[ 0 0; 1 0; 1 1; 0 1],...
                  [-4 2; -8 -3; -3 -5; 6 3]);

% Fill with gray and use bicubic interpolation.
% Make the output size the same as the input size.

[B,xdata,ydata] = imtransform(I, tform, 'bicubic', ...
                              'udata', udata,...
                              'vdata', vdata,...
                              'size', size(I),...
                              'fill', 128);
subplot(1,2,1), imshow(I,'XData',udata,'YData',vdata), ...
    axis on
subplot(1,2,2), imshow(B,'XData',xdata,'YData',ydata), ...
    axis on
```



Projective Transformation

Image Registration. Register an aerial photo to an orthophoto.

Read an aerial photo into the MATLAB workspace and view it.

```
unregistered = imread('westconcordaerial.png');  
figure, imshow(unregistered)
```



Aerial Photo

Read an orthophoto into the MATLAB workspace and view it.

```
figure, imshow('westconcordorthophoto.png')
```



Orthophoto

Load control points that were previously picked.

```
load westconcordpoints
```

Create a transformation structure for a projective transformation using the points.

```
t_concord = cp2tform(movingPoints,fixedPoints,'projective');
```

Get the width and height of the orthophoto, perform the transformation, and view the result.

```
info = imfinfo('westconcordorthophoto.png');
```

```
registered = imtransform(unregistered,t_concord,...  
    'XData',[1 info.Width], 'YData',[1 info.Height]);  
figure, imshow(registered)
```



Transformed Image

More About

Tips

- **Image Registration.** The `imtransform` function automatically shifts the origin of your output image to make as much of the transformed image visible as possible. If you use `imtransform` to do image registration, the syntax `B =`

`imtransform(A,tform)` can produce unexpected results. To control the spatial location of the output image, set `'XData'` and `'YData'` explicitly.

- **Pure Translation.** Calling the `imtransform` function with a purely translational transformation, results in an output image that is exactly like the input image unless you specify `'XData'` and `'YData'` values in your call to `imtransform`. For example, if you want the output to be the same size as the input revealing the translation relative to the input image, call `imtransform` as shown in the following syntax:

```
B = imtransform(A,T,'XData',[1 size(A,2)],...  
    'YData',[1 size(A,1)])
```

For more information about this topic, see “Perform Simple 2-D Translation Transformation”.

- **Transformation Speed.** When you do not specify the output-space location for `B` using `'XData'` and `'YData'`, `imtransform` estimates the location automatically using the function `findbounds`. You can use `findbounds` as a quick forward-mapping option for some commonly used transformations, such as affine or projective. For transformations that do not have a forward mapping, such as the polynomial ones computed by `fitgeotrans`, `findbounds` can take much longer. If you can specify `'XData'` and `'YData'` directly for such transformations, `imtransform` may run noticeably faster.
- **Clipping.** The automatic estimate of `'XData'` and `'YData'` using `findbounds` sometimes clips the output image. To avoid clipping, set `'XData'` and `'YData'` directly.
- **Arbitrary Dimensional Transformations.** Use a 2-D transformation for `tform` when using `imtransform`. For arbitrary-dimensional array transformations, see `tformarray`.

See Also

`checkerboard` | `cp2tform` | `imresize` | `imrotate` | `maketform` | `makeresampler` | `tformarray`

Introduced before R2006a

imtranslate

Translate image

Syntax

```
B = imtranslate(A,translation)
[B,RB] = imtranslate(A,RA,translation)
___ = imtranslate(___ ,method)
___ = imtranslate(___ ,Name,Value)
```

Description

`B = imtranslate(A,translation)` translates image **A** according to the translation specified by the translation vector `translation`. The function returns **B**, the translated image. If **A** has more than two dimensions and `translation` is a two-element vector, `imtranslate` applies a 2-D translation to **A**, one plane at a time.

`[B,RB] = imtranslate(A,RA,translation)` translates the spatially referenced image **A** with its associated spatial referencing object **RA**. The translation vector, `translation`, is in the world coordinate system. The function returns the translated spatially referenced image **B**, with its associated spatially referencing object, **RB**.

`___ = imtranslate(___ ,method)` specifies the interpolation method to use.

`___ = imtranslate(___ ,Name,Value)` translates the input image using name-value pairs to control various aspects of the translation.

“Code Generation” on page 1-1097 support: Yes.

“MATLAB Function Block” on page 1-1097 support: Yes.

Examples

Translate 2-D Image

Read image into the workspace.


```
I = imread('pout.tif');
```


Translate the image.

```
J = imtranslate(I,[25.3, -10.1],'FillValues',255);
```

Display the original image and the translated image.

```
figure  
imshow(I);  
title('Original Image');  
set(gca,'Visible','on');  
figure  
imshow(J);  
title('Translated Image');  
set(gca,'Visible','on');
```





Translate 2-D Image and View Entire Translated Image

Read image into the workspace.

```
I = imread('pout.tif');
```

Translate the image. Use the `OutputView` parameter to specify that you want the entire translated image to be visible.


```
J = imtranslate(I,[25.3, -10.1],'FillValues',255,'OutputView','full');
```


Display the original image and the translated image.

```
figure  
imshow(I);  
title('Original Image');
```



```
set(gca, 'Visible', 'on');  
figure  
imshow(J);  
title('Full Translated Image');  
set(gca, 'Visible', 'on');
```






Translate 3-D MRI Dataset

Load MRI data into the workspace and display it.

```
s = load('mri');  
mriVolume = squeeze(s.D);  
sizeIn = size(mriVolume);  
hFigOriginal = figure;  
hAxOriginal = axes;  
slice(double(mriVolume),sizeIn(2)/2,sizeIn(1)/2,sizeIn(3)/2);  
grid on, shading interp, colormap gray
```




Apply a translation in the X,Y direction.

```
mriVolumeTranslated = imtranslate(mriVolume,[40,30,0], 'OutputView', 'full');
```

Visualize axial slice plane taken through center of volume.

```
sliceIndex = round(sizeIn(3)/2);
axialSliceOriginal = mriVolume(:,:,sliceIndex);
axialSliceTranslated = mriVolumeTranslated(:,:,sliceIndex);
imshowpair(axialSliceOriginal,axialSliceTranslated, 'montage');
set(gca, 'Visible', 'on')
```



- “Translate an Image”

Input Arguments

A — Image to be transformed

nonsparse, numeric array | logical array

Image to be transformed, specified as a nonsparse, numeric array of any class, except `uint64` and `int64`, or a logical array.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32` | `logical`

RA — Spatial referencing information associated with the input image A

spatial referencing object

Spatial referencing information associated with the input image A, specified as a spatial referencing object, `imref2d` or `imref3d`.

translation — Translation vector

2-element or 3-element, nonsparse, real-valued numeric vector

Translation vector, specified as a 2-element or 3-element, nonsparse, real-valued numeric vector, such as [Tx Ty], for 2-D inputs, and [Tx Ty Tz], for 3-D inputs. Values can be fractional.

Example: `J = imtranslate(I,[5.3, -10.1],'FillValues',255);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

method — Interpolation method

`'linear'` (default) | `'nearest'` | `'cubic'`

Interpolation method, specified by one of the following text strings:

Method	Description
<code>'cubic'</code>	Cubic interpolation. Note: This method can produce pixel values outside the original range.
<code>'linear'</code>	Linear interpolation
<code>'nearest'</code>	Nearest neighbor interpolation

Example: `J = imtranslate(I,[5.3, -10.1],'nearest','FillValues',255);`

Data Types: `char`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (`' '`). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

Example: `mriVolumeTranslated = imtranslate(mriVolume, [40,30,0], 'OutputView', 'full');`

'OutputView' — Output world limits

`'same'` (default) | `'full'`

Output world limits, specified as one of the following text strings.

Text String	Description
<code>'same'</code>	Output world limits are the same as the input image.

Text String	Description
'full'	Output world limits are the bounding rectangle that includes both the input image and the translated output image.

Example: `mriVolumeTranslated = imtranslate(mriVolume, [40,30,0], 'OutputView', 'full');`

Data Types: char

'FillValues' — Fill values used for output pixels outside the input image

0 (default) | numeric array

Fill values used for output pixels outside the input image, specified as a numeric array containing one or several fill values. `imtranslate` uses fill values for output pixels when the corresponding inverse transformed location in the input image is completely outside the input image boundaries.

- If A is 2-D, `FillValues` must be a scalar.
- If A is 3-D and `translation` is a 3-element vector, `FillValues` must be a scalar.
- If A is N-D and `translation` is a 2-element vector, `FillValues` can be either scalar or an array whose size matches dimensions 3-to-N of A. For example, if A is a `uint8` RGB image that is 200-by-200-by-3, `FillValues` can be a scalar or a 3-by-1 array.
- If A is 4-D with size 200-by-200-by-3-by-10, `FillValues` can be a scalar or a 3-by-10 array.

Some example fill values:

Fill Value	Description
0	Fill with black
[0;0;0]	Fill with black
255	Fill with white
[255;255;255]	Fill with white
[0;0;255]	Fill with blue
[255;255;0]	Fill with yellow

Example: `J = imtranslate(I,[5.3, -10.1], 'FillValues',255);`

Data Types: single | double | int8 | int16 | int32 | uint8 | uint16 | uint32

Output Arguments

B — Transformed image

nonsparse, real-valued, numeric array | logical array

Transformed image, returned as a nonsparse, real-valued, numeric array or logical array. The class of **B** is the same as the class of **A**.

RB — Spatial referencing information associated with the output image

spatial referencing object

Spatial referencing information associated with the output image, returned as a spatial referencing object, `imref2d` or `imref3d`.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic `MATLAB Host Computer` target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, note the following:

- The function supports only 2-D translation vectors, `translation`. 3-D translations are not supported.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

When using this function with the MATLAB Function Block, the `translation` input argument must be a compile-time constant.

Tips

- `imtranslate` is optimized for integrally valued `translation` vectors.

- When 'OutputView' is 'full' and `translation` is a fractional number of pixels, the world limits of the output spatial referencing object `RB` are expanded to the nearest full pixel increment such that `RB` contains both the original and translated images at the same resolution as the input image `A`. The additional image extent in each is added on one side of the image, in the direction that the translation vector points. For example, when `translation` is fractional and positive in both `X` and `Y`, then the maximum of `XWorldLimits` and `YWorldLimits` is expanded to enclose the 'full' bounding rectangle at the resolution of the input image.

See Also

`imresize` | `imrotate` | `imwarp`

Introduced in R2014a

imview

Display image in image tool

Note: `imview` has been removed. Use `imtool` instead.

Introduced before R2006a

imwarp

Apply geometric transformation to image

Syntax

```
B = imwarp(A,tform)
B = imwarp(A,D)
[B,RB] = imwarp(A,RA,tform)
B = imwarp( ____,Interp)
[B,RB] = imwarp( ____,Name,Value)
```

Description

`B = imwarp(A,tform)` transforms the image `A` according to the geometric transformation defined by `tform`, which is a geometric transformation object. `B` is the transformed image.

`B = imwarp(A,D)` transforms the input image `A` according to the displacement field defined by `D`.

`[B,RB] = imwarp(A,RA,tform)` transforms the spatially referenced image, specified by the image data `A` and the associated spatial referencing object `RA`. The output is a spatially referenced image specified by the image data `B` and the associated spatial referencing object `RB`.

`B = imwarp(____,Interp)` specifies the form of interpolation to use

`[B,RB] = imwarp(____,Name,Value)` specifies parameters that control various aspects of the geometric transformation. Parameter names can be abbreviated, and case does not matter.

“Code Generation” on page 1-1113 support: Yes.

“MATLAB Function Block” on page 1-1113 support: Yes.

Examples

Apply Horizontal Shear to Image

Read grayscale image into workspace and display it.

```
I = imread('cameraman.tif');  
imshow(I)
```



Create a 2-D geometric transformation object.

```
tform = affine2d([1 0 0; .5 1 0; 0 0 1])
```

```
tform =
```

```
    affine2d with properties:
```

```
        T: [3x3 double]
```

Dimensionality: 2

Apply the transformation to the image.


```
J = imwarp(I,tform);  
figure  
imshow(J)
```



Apply Rotation Transformation to 3-D MRI Dataset

Read MRI data into the workspace and visualize it.

```
s = load('mri');  
mriVolume = squeeze(s.D);  
sizeIn = size(mriVolume);  
hFigOriginal = figure;  
hAxOriginal = axes;  
slice(double(mriVolume),sizeIn(2)/2,sizeIn(1)/2,sizeIn(3)/2);  
grid on, shading interp, colormap gray
```



Create a 3-D geometric transformation object. First create a transformation matrix that rotates the image around the *Y* axis. Then pass the matrix to the `affine3d` function.

```
theta = pi/8;  
t = [cos(theta) 0 -sin(theta) 0  
     0 1 0 0  
     sin(theta) 0 cos(theta) 0  
     0 0 0 1]  
  
tform = affine3d(t)  
  
t =
```

```
0.9239      0   -0.3827      0
      0   1.0000      0      0
0.3827      0   0.9239      0
      0      0      0   1.0000
```

```
tform =
```

```
affine3d with properties:
```


```
          T: [4x4 double]
Dimensionality: 3
```

Apply the transformation to the image.

```
mriVolumeRotated = imwarp(mriVolume,tform);
```


Visualize three slice planes through the center of the transformed volumes.


```
sizeOut = size(mriVolumeRotated);
hFigRotated = figure;
hAxRotated = axes;
slice(double(mriVolumeRotated),sizeOut(2)/2,sizeOut(1)/2,sizeOut(3)/2);
grid on, shading interp, colormap gray
```



Link views of both axes together.


```
linkprop([hAxOriginal,hAxRotated],'View');
```






Set view to see effect of rotation.

```
set(hAxRotated, 'View', [-3.5 20.0])
```





Input Arguments

A — Image to be transformed

nonsparse, real-valued array of any numeric class or logical

Image to be transformed, specified as a nonsparse, real-valued array of any numeric class or logical.

tform — 2-D or 3-D geometric transformation to perform

geometric transformation object

2-D or 3-D geometric transformation to perform, specified as a geometric transformation object.

- If `tform` is 2-D and `ndims(A) > 2`, such as for an RGB image, `imwarp` applies the same 2-D transformation to all 2-D planes along the higher dimensions.
- If `tform` is 3-D, `A` must be a 3-D image volume.

D — Displacement field

nonsparse numeric matrix

Displacement field, specified as nonsparse numeric matrix.

When `A` is 2-D, `D` is an m -by- n -by-2 numeric array. The first plane of the displacement field, `D(:, :, 1)` describes the X component of additive displacement that is added to column and row locations in `D` to produce remapped locations in `A`. Similarly, `D(:, :, 2)` describes the Y component of additive displacement values.

When `A` is 3-D, `D` is an m -by- n -by- p -by-3 numeric array. In the 3-D case, `D(:, :, :, 1)` contains displacements along the x -axis, `D(:, :, :, 2)` contains displacements along the y -axis, and `D(:, :, :, 3)` contains displacements along the z -axis. The unit of displacement values in `D` is pixels. When `A` is m -by- n -by- p and `D` is m -by- n -by-2, `imwarp` applies the displacement field to one plane at a time. `imwarp` assumes that `D` is referenced to the default intrinsic coordinate system.

RA — Spatial referencing information associated with the image to be transformed

spatial referencing object

Spatial referencing information associated with the image to be transformed, specified as a spatial referencing object.

- If `tform` is a 2-D geometric transformation, `RA` must be a 2-D spatial referencing object (`imref2d`).
- If `tform` is a 3-D geometric transformation, `RA` must be a 3-D spatial referencing object (`imref3d`).

Interp — Form of interpolation used

'linear' (default) | 'nearest' | 'cubic'

Form of interpolation used, specified as one of the following character strings:

Interpolation Method	Description
'linear'	Linear interpolation

Interpolation Method	Description
'nearest'	Nearest-neighbor interpolation—the output pixel is assigned the value of the pixel that the point falls within. No other pixels are considered.
'cubic'	Cubic interpolation

Data Types: char

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

Example: `J = imwarp(I, tform, 'FillValues', 255)` uses white pixels as fill values.

'OutputView' — Size and location of output image in world coordinate system

`imref2d` or `imref3d` spatial referencing object

Size and location of output image in world coordinate system, specified as the comma-separated pair consisting of 'OutputView' and an `imref2d` or `imref3d` spatial referencing object. The `ImageSize`, `XWorldLimits`, and `YWorldLimits` properties of the specified spatial referencing object define the size of the output image and the location of the output image in the world coordinate system. The use of 'OutputView' is not available when applying displacement fields.

'FillValues' — Value used for output pixels outside image boundaries

numeric scalar or array

Value used for output pixels outside the input image boundaries, specified as the comma-separated pair consisting of 'FillValues' and a numeric array. Fill values are used for output pixels when the corresponding inverse transformed location in the input image is completely outside the input image boundaries.

- If the input image is 2-D, `FillValues` must be a scalar.
- If the input image is 3-D and the geometric transformation is 3-D, `FillValues` must be a scalar.
- If the input image is N-D and the geometric transformation is 2-D, `FillValues` may be either scalar or an array whose size matches dimensions 3 to N of the input image.

For example, if the input image is a `uint8` RGB image that is 200-by-200-by-3, `FillValues` can be a scalar or a 3-by-1 array. In this RGB image example, possibilities for `FillValues` include:

FillValue	Effect
0	Fill with black
[0;0;0]	Fill with black
255	Fill with white
[255;255;255]	Fill with white
[0;0;255]	Fill with blue
[255;255;0]	Fill with yellow

- If the input image is 4-D with size 200-by-200-by-3-by-10, `FillValues` can be a scalar or a 3-by-10 array.

'SmoothEdges' — Pad image to create smooth edges

false (default) | true

Pad image to create smooth edges, specified as the logical value `true` or `false`. When set to `true`, `imwarp` pads the input image (with values specified by `FillValues`) to create a smoother edge in the output image. When set to `false`, `imwarp` does not pad the image. Not padding the input image results in a sharper edge in the output image, which can be useful to minimize seam distortions when registering two images side by side.

Output Arguments

B — Transformed image

nonsparse real-valued array of any numeric class or logical

Transformed image, returned as a nonsparse real-valued array of any numeric class or logical.

RB — Spatial referencing information associated with the transformed image

spatial referencing object

Spatial referencing information associated with the transformed image, returned as a spatial referencing object.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, note:

- The geometric transformation object input, `tform`, must be either an `affine2d` or `projective2d` object.
- The interpolation method and optional parameter names must be string constants.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

The `TFORM` input argument must be a compile-time constant.

See Also

`affine2d` | `affine3d` | `projective2d` | `imref2d` | `imref3d` | `imregtform` | `imtranslate`

Introduced in R2013a

ind2gray

Convert indexed image to grayscale image

Syntax

```
I = ind2gray(X,map)
```

Description

`I = ind2gray(X,map)` converts the image `X` with colormap `map` to a grayscale image `I`. `ind2gray` removes the hue and saturation information from the input image while retaining the luminance.

Note: A grayscale image is also called a gray-scale, gray scale, or gray-level image.

Class Support

`X` can be of class `uint8`, `uint16`, `single`, or `double`. `map` is `double`. `I` is of the same class as `X`.

Examples

```
load trees
I = ind2gray(X,map);
imshow(X,map)
figure,imshow(I)
```





Image Courtesy of Susan Cohen

More About

Algorithms

`ind2gray` converts the colormap to NTSC coordinates using `rgb2ntsc`, and sets the hue and saturation components (I and Q) to zero, creating a gray colormap. `ind2gray` then replaces the indices in the image X with the corresponding grayscale intensity values in the gray colormap.

See Also

`gray2ind` | `imshow` | `imtool` | `mat2gray` | `rgb2gray` | `rgb2ntsc`

Introduced before R2006a

ind2rgb

Convert indexed image to RGB image

Syntax

```
RGB = ind2rgb(X,map)
```

Description

`RGB = ind2rgb(X,map)` converts the matrix `X` and corresponding colormap `map` to RGB (truecolor) format.

Class Support

`X` can be of class `uint8`, `uint16`, or `double`. `RGB` is an `m-by-n-by-3` array of class `double`.

See Also

`ind2gray` | `rgb2ind`

Introduced before R2006a

integralBoxFilter

2-D box filtering of integral images

Syntax

```
B = integralBoxFilter(intA)
B = integralBoxFilter(intA,filterSize)
B = integralBoxFilter( ____,Name,Value)
```

Description

`B = integralBoxFilter(intA)` filters the integral image `intA` with a 3-by-3 box filter. Returns the filtered image, `B`.

`B = integralBoxFilter(intA,filterSize)` filters the integral image `intA` with a 2-D box filter with size specified by `filterSize`.

`B = integralBoxFilter(____,Name,Value)` filters integral image `intA` with Name-Value pairs to control various aspects of the filtering.

“Code Generation” on page 1-1125 support: Yes.

“MATLAB Function Block” on page 1-1125 support: Yes.

Examples

Filter Integral Image

Read image into the workspace.

```
A = imread('cameraman.tif');
```

Pad the image by the radius of the filter neighborhood. This example uses an 11-by-11 filter.

```
filterSize = [11 11];
```

```
padSize = (filterSize-1)/2;  
Apad = padarray(A, padSize, 'replicate', 'both');
```

Compute the integral image of the padded input image.

```
intA = integralImage(Apad);
```

Filter the integral image.

```
B = integralBoxFilter(intA, filterSize);
```

Display original image and filtered image.

```
figure  
imshow(A)  
title('Original Image')  
figure  
imshow(B,[])  
title('Filtered Image')
```

Original Image



Filtered Image

Filter Image with Horizontal and Vertical Motion Blur

Read image into the workspace.

```
A = imread('cameraman.tif');
```

Pad the image by radius of the filter neighborhood, calculated $(11 - 1) / 2$.

```
padSize = [5 5];  
Apad = padarray(A, padSize, 'replicate', 'both');
```

Calculate the integral image of the padded input.

```
intA = integralImage(Apad);
```

Filter the integral image with a vertical $[11\ 1]$ filter.

```
Bvert = integralBoxFilter(intA, [11 1]);
```

Crop the output to retain input image size and display it.

```
Bvert = Bvert(:,6:end-5);
```

Filter the integral image with a horizontal [1 11] filter.

```
Bhorz = integralBoxFilter(intA, [1 11]);
```

Crop the output to retain input image size.

```
Bhorz = Bhorz(6:end-5,:);
```

Display the original image and the filtered images.

```
figure,  
imshow(A)  
title('Original Image')  
figure,  
imshow(Bvert,[])  
title('Filtered with Vertical Filter')  
figure,  
imshow(Bhorz,[])  
title('Filtered with Horizontal Filter')
```

Original Image



Filtered with Vertical Filter



Filtered with Horizontal Filter

Input Arguments

intA — Integral image to be filtered

real, nonsparse double matrix of any dimension

Integral image to be filtered, specified as a real, nonsparse matrix of any dimension. The integral image must be upright—`integralBoxFilter` does not support rotated integral images. The first row and column of the integral image is assumed to be zero-padded, as returned by `integralImage`.

Example: `B = integralBoxFilter(A);`

Data Types: double

filterSize — Size of box filter

3-by-3 box filter (default) | scalar or 2-element vector of positive, odd integers

Size of box filter, specified as a scalar or 2-element vector of positive, odd integers. If `filterSize` is scalar, `integralBoxFilter` uses a square box filter.

Example: `B = integralBoxFilter(A,5);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

Example: `B = integralBoxFilter(A,5,'NormalizationFactor',1);`

'NormalizationFactor' — Normalization factor applied to box filter

$1/\text{filterSize}.^2$, if scalar, and $1/\text{prod}(\text{filterSize})$, if vector (default) | numeric scalar

Normalization factor applied to box filter, specified as a numeric scalar or vector.

The default 'NormalizationFactor' has the effect of a mean filter—the pixels in the output image are the local means of the image. To get local area sums, set 'NormalizationFactor' to 1. To avoid overflow in such circumstances, consider using double precision images by converting the input image to class `double`.

Example: `B = integralBoxFilter(A,5,'NormalizationFactor',1);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

Output Arguments

B — Filtered image

real, nonsparse `double` matrix

Filtered image, returned as a real, nonsparse matrix of class `double`.

`integralBoxFilter` returns only the parts of the filtering that are computed without padding.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, note the following:

- The 'NormalizationFactor' parameter must be a compile-time constant.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

When using this function with the MATLAB function block, note the following:

- The FilterSize argument must be a compile-time constant.
- “Integral Image”

See Also

`imboxfilt` | `integralImage`

Introduced in R2015b

integralBoxFilter3

3-D box filtering of 3-D integral images

Syntax

```
B = integralBoxFilter3(intA)
B = integralBoxFilter3(intA,filterSize)
B = integralBoxFilter3( ____,Name,Value)
```

Description

`B = integralBoxFilter3(intA)` filters integral image `intA` with a 3-by-3-by-3 box filter. `B` is a 3-D image of class `double` containing the filtered output.

`B = integralBoxFilter3(intA,filterSize)` filters integral image `intA` with a 3-D box filter with size specified by `filterSize`.

`B = integralBoxFilter3(____,Name,Value)` filters integral image `intA` with a 3-D box filter with `Name-Value` pairs to control various aspects of the filtering.

Examples

Filter 3-D MRI Volume with Box Filter

Load 3-D MRI data.

```
volData = load('mri');
vol = squeeze(volData.D);
```

Pad the image volume by the radius of the filter neighborhood.

```
filterSize = [5 5 3];
padSize = (filterSize-1)/2;
volPad = padarray(vol, padSize, 'replicate', 'both');
```

Calculate the 3-D integral image of the padded input.

```
intVol = integralImage3(volPad);
```

Filter the 3-D integral image with a [5 5 3] filter.

```
volFilt = integralBoxFilter3(intVol, filterSize);
```

Input Arguments

intA — Integral image to be filtered

real, non-sparse 3-D double array

Integral image to be filtered, specified as a real, non-sparse 3-D array of class **double**.

`integralBoxFilter3` expects the input integral image, `intA`, to be an upright integral image computed using `integralImage3`. `integralBoxFilter3` does not support rotated integral images. The first row, column and page of the integral image is assumed to be padded, as returned by `integralImage3`.

Example: `B = integralBoxFilter3(A);`

Data Types: `double`

filterSize — Size of box filter

3-by-3-by-3 box filter (default) | scalar or 3-element vector of positive, odd integers

Size of box filter, specified as a scalar or 3-element vector of positive, odd integers. If `filterSize` is scalar, `integralBoxFilter3` uses a cube box filter.

Example: `B = integralBoxFilter3(A,5);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

Example: `B = integralBoxFilter3(A,5,'NormalizationFactor',1);`

'NormalizationFactor' — Normalization factor applied to box filter

`1/filterSize.^3`, if scalar, and `1/prod(filterSize)`, if vector (default) | numeric scalar

Normalization factor applied to box filter, specified as a numeric scalar.

The default 'NormalizationFactor' has the effect of a mean filter—the pixels in the output image are the local means of the image. To get local area sums, set 'NormalizationFactor' to 1. To avoid overflow in such circumstances, consider using double precision images by converting the input image to class `double`.

Example: `B = integralBoxFilter3(A,5,'NormalizationFactor',1);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

Output Arguments

B — Filtered image

real, nonsparse 3-D array

Filtered image, returned as a real, nonsparse 3-D array of class `double`.

`integralBoxFilter3` returns only the parts of the filtering that are computed without padding.

More About

- “Integral Image”

See Also

`imboxfilt3` | `integralimage3`

Introduced in R2015b

integrallImage

Calculate integral image

Syntax

```
J = integrallImage(I)
J = integrallImage(I,orientation)
```

Description

`J = integrallImage(I)` calculates the “Integral Image” on page 1-1132 , J, from the intensity image, I.

`J = integrallImage(I,orientation)` calculates the integral image with the orientation specified by `orientation`.

Examples

Use Integral Image to Compute Region Sums

Create a simple sample image. For this example, sum the 2-by-2 rectangular region starting at row 1, column 3 (value 1) and extending to row 2, column 4 (value 14). In this trivial example, it's easy to calculate the sum of the pixels in the region: $1 + 7 + 8 + 14 = 30$.

```
I = magic(5)
```

```
I =
```

```
17    24     1     8    15
23     5     7    14    16
 4     6    13    20    22
10    12    19    21     3
11    18    25     2     9
```

Create an integral image of the sample image. The value of each pixel in the integral image is the sum of the pixel above it and the pixel to its left. Note how `integralImage` adds a padding row to the top and left sides of the image.

```
J = integralImage(I)
```

```
J =
```

```

0     0     0     0     0     0
0    17    41    42    50    65
0    40    69    77    99   130
0    44    79   100   142   195
0    54   101   141   204   260
0    65   130   195   260   325
```

Sum the rectangular region in the integral image. In this calculation, you extend the rectangular region you sum. The coordinates of the four corners are: (startRow,startCol), (startRow,endCol+1),(endRow,startCol), and (endRow+1,endCol+1)

```
regionSum = (J(1,3) + J(3,5)) - (J(1,5) + J(3,3))
```

```
regionSum =
```

```
30
```

Compute Integral Image with Rotated Orientation

Create sample image.

```

I = magic(5)
% Define rotated rectangular region as [x, y, width, height] where x, y
% denote the indices of the top corner of the rectangle. Width and height
% are along 45 degree lines from the top corner.
[x, y, w, h] = deal(3, 1, 3, 2);
```

```
I =
```

```

17    24     1     8    15
23     5     7    14    16
 4     6    13    20    22
```



```

10  12  19  21  3
11  18  25  2  9

```

Create integral image.

```
J = integralImage(I, 'rotated');
```

Compute the sum over the region using the integral image.

```
regionSum = J(y+w+h,x+w-h+1) + J(y,x+1) - J(y+h,x-h+1) - J(y+w,x+w+1);
```

Input Arguments

I — Input grayscale image

real, nonsparse 2-D matrix

Input grayscale image, specified as a real, nonsparse 2-D matrix.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

orientation — Image orientation

'upright' (default) | 'rotated'

Image orientation, specified as the string 'upright' or 'rotated'. If you set the orientation to 'rotated', `integralImage` returns the integral image for computing sums over rectangles rotated by 45 degrees. To facilitate computation of pixel sums along all image boundaries, the `integralImage` pads the output integral images as follows:

Integral Image	Description
Upright integral image	Zero-padded on top and left, resulting in <code>size(J) = size(I)+1</code>
Rotated integral image	Zero-padded at the top, left, and right, resulting in <code>size(J) = size(I)+[1 2]</code>

If the input image has more than two dimensions (`ndims(I)>2`), such as for an RGB image, the `integralImage` function computes the integral image for all 2-D planes along the higher dimensions.

Data Types: `char`

Output Arguments

J — Integral image

real, nonsparse matrix of class `double`

Integral image, returned as a real, nonsparse matrix of class `double`. The function zero-pads the top and left side of the integral image so the size of the output integral image is the size as the input image, plus 1, `size(J) = size(I)+1`. Such sizing facilitates easy computation of pixel sums along all image boundaries. The integral image, `J`, is essentially a padded version of the value `cumsum(cumsum(I,2))`.

More About

Integral Image

In an *integral image*, every pixel is the summation of the pixels above and to the left of it. Using an integral image, you can rapidly calculate summations over image subregions. Use of integral images was popularized by the Viola-Jones algorithm. Integral images facilitate summation of pixels and can be performed in constant time, regardless of the neighborhood size.

- “Integral Image”

References

- [1] Viola, Paul and Michael J. Jones, “Rapid Object Detection using a Boosted Cascade of Simple Features”, *Proceedings of the 2001 IEEE Computer Society Conference on Computer Vision and Pattern Recognition*, 2001. Volume: 1, pp.511–518.

See Also

`cumsum` | `integralBoxFilter`

Introduced in R2015b

integralImage3

Calculate 3-D integral image

Syntax

```
J = integralImage3(I)
```

Description

`J = integralImage3(I)` calculates the integral image, `J`, from the input intensity image, `I`.

Examples

Compute Integral Image of 3-D Input Image

Create a 3-D input image.

```
I = reshape(1:125,5,5,5);
```

Define a 3-by-3-by-3 sub-volume as [`startRow`, `startCol`, `startPlane`, `endRow`, `endCol`, `endPlane`].

```
[sR, sC, sP, eR, eC, eP] = deal(2, 2, 2, 4, 4, 4);
```

Create an integral image from the input image and compute the sum over a 3-by-3-by-3 sub-volume of `I`.

```
J = integralImage3(I);
regionSum = J(eR+1,eC+1,eP+1) - J(eR+1,eC+1,sP) - J(eR+1,sC,eP+1) ...
            - J(sR,eC+1,eP+1) + J(sR,sC,eP+1) + J(sR,eC+1,sP) ...
            + J(eR+1,sC,sP) - J(sR,sC,sP)
```

```
regionSum =
```

```
1701
```

Verify that the sum of pixels is accurate.

```
sum(sum(sum(I(sR:eR, sC:eC, sP:eP))))
```

```
ans =
```

```
1701
```

Input Arguments

I — Input intensity image

real, nonsparse 3-D array

Input intensity image, specified as a real, nonsparse 3-D array of any numeric class.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

Output Arguments

J — Integral image

real, nonsparse matrix of class `double`

Integral image, returned as a real, nonsparse matrix of class `double`. The function zero-pads the top, left and along the first plane, resulting in `size(J) = size(I) + 1`. side of the integral image. The class of the output is `double`. The resulting size of the output integral image equals: `size(J) = size(I) + 1`. Such sizing facilitates easy computation of pixel sums along all image boundaries. The integral image, `J`, is essentially a padded version of the value `cumsum(cumsum(cumsum(I),2),3)`.

See Also

`integralBoxFilter3` | `integralImage`

Introduced in R2015b

interfileinfo

Read metadata from Interfile file

Syntax

```
info = interfileinfo(filename)
```

Description

`info = interfileinfo(filename)` returns a structure whose fields contain information about an image in a Interfile file. `filename` is a string that specifies the name of the file. The file must be in the current directory or in a directory on the MATLAB path.

The Interfile file format was developed for the exchange of nuclear medicine data. In Interfile 3.3, metadata is stored in a header file, separate from the image data. The two files have the same name with different file extensions. The header file has the file extension `.hdr` and the image file has the file extension `.img`.

Examples

Read metadata from an Interfile file.

```
info = interfileinfo('MyFile.hdr');
```

For more information about this file format, visit the [Interfile Archive](#), maintained by the Department of Medical Physics and Bioengineering, University College, London, UK.

See Also

`interfileread`

Introduced before R2006a

interfileread

Read images in Interfile format

Syntax

```
A = interfileread(filename)
A = interfileread(filename, window)
```

Description

`A = interfileread(filename)` reads the images in the first energy window of `filename` into `A`, where `A` is an `M`-by-`N` array for a single image and an `M`-by-`N`-by-`P` array for multiple images. The file must be in the current directory or in a directory on the MATLAB path.

`A = interfileread(filename, window)` reads the images in the energy window specified by `window` of `filename` into `A`.

The images in the energy window must be of the same size.

Examples

Read image data from an Interfile file.

```
img = interfileread('MyFile.hdr');
```

For more information about this file format, visit the [Interfile Archive](#), maintained by the Department of Medical Physics and Bioengineering, University College, London, UK.

See also

`interfileinfo`

Introduced before R2006a

intlut

Convert integer values using lookup table

Syntax

```
B = intlut(A, LUT)
```

Description

`B = intlut(A, LUT)` converts values in array `A` based on lookup table `LUT` and returns these new values in array `B`. For example, if `A` is a vector whose k th element is equal to `alpha`, then `B(k)` is equal to the `LUT` value corresponding to `alpha`, i.e., `LUT(alpha+1)`.

“Code Generation” on page 1-1137support: Yes.

“MATLAB Function Block” on page 1-1138 support: Yes.

Class Support

`A` can be `uint8`, `uint16`, or `int16`. If `A` is `uint8`, `LUT` must be a `uint8` vector with 256 elements. If `A` is `uint16` or `int16`, `LUT` must be a vector with 65536 elements that has the same class as `A`. `B` has the same size and class as `A`.

Examples

```
A = uint8([1 2 3 4; 5 6 7 8; 9 10 11 12])
LUT = repmat(uint8([0 150 200 255]),1,64);
B = intlut(A, LUT)
```

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic MATLAB Host Computer target platform, the function generates

code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`ind2gray` | `rgb2ind`

Introduced before R2006a

iptaddcallback

Add function handle to callback list

Syntax

```
ID = iptaddcallback(h,callback,func_handle)
```

Description

`ID = iptaddcallback(h,callback,func_handle)` adds the function handle `func_handle` to the list of functions to be called when the callback specified by `callback` executes. `callback` is a string specifying the name of a callback property of the Handle Graphics object specified by the handle `h`.

`iptaddcallback` returns a unique callback identifier, `ID`, that can be used with `iptremovecallback` to remove the function from the callback list.

`iptaddcallback` can be useful when you need to notify more than one tool about the same callback event for a single object.

Note

Callback functions that have already been added to an object using the `set` command continue to work after you call `iptaddcallback`. The first time you call `iptaddcallback` for a given object and `callback`, the function checks to see if a different callback function is already installed. If a callback is already installed, `iptaddcallback` replaces that callback function with the `iptaddcallback` callback processor, and then adds the preexisting callback function to the `iptaddcallback` list.

Examples

Create a figure and register two callback functions. Whenever MATLAB detects mouse motion over the figure, function handles `f1` and `f2` are called in the order in which they were added to the list.

```
h = figure;  
f1 = @(varargin) disp('Callback 1');  
f2 = @(varargin) disp('Callback 2');  
iptaddcallback(h, 'WindowButtonMotionFcn', f1);  
iptaddcallback(h, 'WindowButtonMotionFcn', f2);
```

See Also

`iptremovecallback`

Introduced before R2006a

iptcheckconn

Check validity of connectivity argument

Syntax

```
iptcheckconn(conn, func_name, var_name, arg_pos)
```

Description

`iptcheckconn(conn, func_name, var_name, arg_pos)` checks whether `conn` is a valid connectivity argument. If it is invalid, the function issues a formatted error message.

A connectivity argument can be one of the following scalar values: 1, 4, 6, 8, 18, or 26. A connectivity argument can also be a 3-by-3-by- ... -by-3 array of 0's and 1s. The central element of a connectivity array must be nonzero and the array must be symmetric about its center.

`func_name` is a string that specifies the name used in the formatted error message to identify the function checking the connectivity argument.

`var_name` is a string that specifies the name used in the formatted error message to identify the argument being checked.

`arg_pos` is a positive integer that indicates the position of the argument being checked in the function argument list. `iptcheckconn` includes this information in the formatted error message.

“Code Generation” on page 1-1142 support: Yes.

“MATLAB Function Block” on page 1-1142 support: Yes.

Class Support

`conn` must be of class `double` or `logical` and must be real and nonsparse.

Examples

Create a 4-by-4 array and pass it as the connectivity argument.

```
iptcheckconn(eye(4), 'func_name', 'var_name', 2)
```

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, all input arguments must be compile-time constants.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

Introduced before R2006a

iptcheckhandle

Check validity of handle

Syntax

```
iptcheckhandle(H, valid_types, func_name, var_name, arg_pos)
```

Description

`iptcheckhandle(H, valid_types, func_name, var_name, arg_pos)` checks the validity of the handle `H` and issues a formatted error message if the handle is invalid. `H` must be a handle to a single figure, uipanel, hggroup, axes, or image object.

`valid_types` is a cell array of strings specifying the set of Handle Graphics object types to which `H` is expected to belong. For example, if you specify `valid_types` as `{'uipanel', 'figure'}`, `H` can be a handle to either a uipanel object or a figure object.

`func_name` is a string that specifies the name used in the formatted error message to identify the function checking the handle.

`var_name` is a string that specifies the name used in the formatted error message to identify the argument being checked.

`arg_pos` is a positive integer that indicates the position of the argument being checked in the function argument list. `iptcheckhandle` converts this value to an ordinal number and includes this information in the formatted error message.

Examples

To trigger the error message, create a figure that does not contain an axes object and then check for a valid axes handle.

```
fig = figure; % create figure without an axes
iptcheckhandle(fig,{'axes'},'my_function','my_variable',2)
```

The following shows the format of the error message and indicates which parts you can customize using `iptcheckhandle` arguments.

func_name arg_pos var_name
 ↓ ↓ ↓
Function MY_FUNCTION expected its second input argument, my_variable,
to be a handle of one of these types:

axes ←————— valid_types

Instead, its type was: figure.

See Also

iptcheckinput | iptcheckmap | iptchecknargin | iptcheckstrs |
iptnum2ordinal

Introduced before R2006a

iptcheckinput

Check validity of array

Compatibility

iptcheckinput will be removed in a future release. Use `validateattributes` instead.

Syntax

```
iptcheckinput(A, classes, attributes, func_name, var_name, arg_pos)
```

Description

iptcheckinput(A, classes, attributes, func_name, var_name, arg_pos) checks the validity of the array A and issues a formatted error message if it is invalid.

classes is a cell array of strings specifying the set of classes to which A is expected to belong. For example, if you specify classes as {'logical' 'cell'}, A is required to be either a logical array or a cell array. The string 'numeric' is interpreted as an abbreviation for the classes uint8, uint16, uint32, int8, int16, int32, single, and double.

attributes is a cell array of strings specifying the set of attributes that A must satisfy. For example, if attributes is {'real' 'nonempty' 'finite'}, A must be real and nonempty, and it must contain only finite values. The following table lists the supported attributes in alphabetical order.

2d	nonempty	odd	twod
column	nonnan	positive	vector
even	nonnegative	real	
finite	nonsparse	row	
integer	nonzero	scalar	

`func_name` is a string that specifies the name used in the formatted error message to identify the function checking the input.

`var_name` is a string that specifies the name used in the formatted error message to identify the argument being checked.

`arg_pos` is a positive integer that indicates the position of the argument being checked in the function argument list. `iptcheckinput` converts this value to an ordinal number and includes this information in the formatted error message.

Examples

To trigger this error message, create a three-dimensional array and then check for the attribute '2d'.

```
A = [ 1 2 3; 4 5 6 ];
B = [ 7 8 9; 10 11 12];
C = cat(3,A,B);
iptcheckinput(C,{'numeric'},{'2d'},'func_name','var_name',2)
```

The following shows the format of the error message and indicates which parts you can customize using `iptcheckinput` arguments.

```
      func_name          arg_pos          var_name
      ↓                 ↓                 ↓
Function FUNC_NAME expected its second input, var_name, to be
two-dimensional.
      ↑
attributes
```

See Also

`iptcheckhandle` | `iptcheckmap` | `iptchecknargin` | `iptcheckstrs` | `iptnum2ordinal`

Introduced before R2006a

iptcheckmap

Check validity of colormap

Syntax

```
iptcheckmap(map, func_name, var_name, arg_pos)
```

Description

`iptcheckmap(map, func_name, var_name, arg_pos)` checks the validity of the MATLAB colormap and issues a formatted error message if it is invalid.

`func_name` is a string that specifies the name used in the formatted error message to identify the function checking the colormap.

`var_name` is a string that specifies the name used in the formatted error message to identify the argument being checked.

`arg_pos` is a positive integer that indicates the position of the argument being checked in the function argument list. `iptcheckmap` includes this information in the formatted error message.

“Code Generation” on page 1-1148 support: Yes.

“MATLAB Function Block” on page 1-1148 support: Yes.

Examples

```
bad_map = ones(10);  
iptcheckmap(bad_map, 'func_name', 'var_name', 2)
```

The following shows the format of the error message and indicates which parts you can customize using `iptcheckmap` arguments.

func_name



arg_pos



var_name



Function FUNC_NAME expected input number 2, var_name, to be a valid colormap.
Valid colormaps must be nonempty, double, 2-D matrices with 3 columns.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

[iptcheckhandle](#) | [iptcheckinput](#) | [iptchecknargin](#) | [iptcheckstrs](#)

Introduced before R2006a

iptchecknargin

Check number of input arguments

Compatibility

`iptchecknargin` will be removed in a future release. Use `narginchk` instead.

Syntax

```
iptchecknargin(low, high, num_inputs, func_name)
```

Description

`iptchecknargin(low, high, num_inputs, func_name)` checks whether `num_inputs` is in the range indicated by `low` and `high`. If not, `iptchecknargin` issues a formatted error message.

`low` should be a scalar nonnegative integer.

`high` should be a scalar nonnegative integer or `Inf`.

`func_name` is a string that specifies the name used in the formatted error message to identify the function checking the handle.

Examples

Create a function and use `iptchecknargin` to check that the number of arguments passed to the function is within the expected range.

```
function test_function(varargin)
    iptchecknargin(1,3,nargin,mfilename);
```

Trigger the error message by executing the function at the MATLAB command line, specifying more than the expected number of arguments.

```
test_function(1,2,3,4)
```

See Also

```
iptcheckhandle | iptcheckinput | iptcheckmap | iptcheckstrs |  
iptnum2ordinal
```

Introduced before R2006a

iptcheckstrs

Check validity of option string

Compatibility

iptcheckstrs will be removed in a future release. Use `validatestring` instead.

Syntax

```
out = iptcheckstrs(in, valid_strs, func_name, var_name, arg_pos)
```

Description

`out = iptcheckstrs(in, valid_strs, func_name, var_name, arg_pos)` checks the validity of the option string `in`. It returns the matching string in `valid_strs` in `out`. `iptcheckstrs` looks for a case-insensitive, nonambiguous match between `in` and the strings in `valid_strs`.

`valid_strs` is a cell array containing strings.

`func_name` is a string that specifies the name used in the formatted error message to identify the function checking the strings.

`var_name` is a string that specifies the name used in the formatted error message to identify the argument being checked.

`arg_pos` is a positive integer that indicates the position of the argument being checked in the function argument list. `iptcheckstrs` converts this value to an ordinal number and includes this information in the formatted error message.

Examples

To trigger this error message, define a cell array of some text strings and pass in another string that isn't in the cell array.

```
iptcheckstrs('option3',{ 'option1','option2'},...  
            'func_name','var_name',2)
```

The following shows the format of the error message and indicates which parts you can customize using `iptcheckhandle` arguments.

```
      func_name          arg_pos          var_name  
      ↓                ↓                ↓  
Function FUNC_NAME expected its second input argument, var_name,  
to match one of these strings:  
  
  option1, option2 ← valid_strs
```

The input, 'option3', did not match any of the valid strings.

See Also

`iptcheckhandle` | `iptcheckinput` | `iptcheckmap` | `iptchecknargin` | `iptnum2ordinal`

Introduced before R2006a

iptdemos

Index of Image Processing Toolbox examples

Syntax

iptdemos

Description

iptdemos displays the HTML page that lists all the Image Processing examples.

iptdemos displays the page in the MATLAB Help browser.

Introduced before R2006a

iptgetapi

Get Application Programmer Interface (API) for handle

Syntax

```
API = iptgetapi(h)
```

Description

`API = iptgetapi(h)` returns the API structure associated with handle `h` if there is one. Otherwise, `iptgetapi` returns an empty array.

To view functions that use this type of API, see `immagbox`, `imdistline`, or `imscrollpanel`.

Examples

```
hFig = figure('Toolbar','none',...  
             'Menubar','none');  
hIm = imshow('tape.png');  
hSP = imscrollpanel(hFig,hIm);  
api = iptgetapi(hSP);  
api.setMagnification(2) % 2X = 200%
```

See Also

`immagbox` | `imdistline` | `imscrollpanel`

Introduced before R2006a

iptGetPointerBehavior

Retrieve pointer behavior from HG object

Syntax

```
pointerBehavior = iptGetPointerBehavior(h)
```

Description

`pointerBehavior = iptGetPointerBehavior(h)` returns the pointer behavior structure associated with the Handle Graphics object `h`. A pointer behavior structure contains function handles that interact with a figure's pointer manager (see `iptPointerManager`) to control what happens when the figure's mouse pointer moves over and then exits the object. See `iptSetPointerBehavior` for details.

If `h` does not contain a pointer behavior structure, `iptGetPointerBehavior` returns `[]`.

See Also

`iptPointerManager` | `iptSetPointerBehavior`

Introduced in R2006a

iptgetpref

Get values of Image Processing Toolbox preferences

Syntax

```
prefs = iptgetpref  
value = iptgetpref(prefname)
```

Description

`prefs = iptgetpref` returns a structure containing all the Image Processing Toolbox preferences with their current values. Each field in the structure has the name of an Image Processing Toolbox preference.

`value = iptgetpref(prefname)` returns the value of the Image Processing Toolbox preference specified by the string `prefname`. See `iptprefs` for a complete list of valid preference names or access the Image Processing preferences dialog box from the **File** menu in the MATLAB desktop. Preference names are not case sensitive and can be abbreviated.

Examples

```
value = iptgetpref('ImshowAxesVisible')
```

```
value =
```

```
off
```

See Also

`imshow` | `iptprefs` | `iptsetpref`

Introduced before R2006a

ipticondir

Directories containing IPT and MATLAB icons

Syntax

```
[D1, D2] = ipticondir
```

Description

[D1, D2] = `ipticondir` returns the names of the directories containing the Image Processing Toolbox icons (D1) and the MATLAB icons (D2).

Examples

```
[iptdir, MATLABdir] = ipticondir  
dir(iptdir)
```

See Also

`imtool`

Introduced before R2006a

iptnum2ordinal

Convert positive integer to ordinal string

Syntax

```
string = iptnum2ordinal(number)
```

Description

`string = iptnum2ordinal(number)` converts the positive integer `number` to the ordinal text string `string`.

Examples

The following example returns the string 'fourth'.

```
str = iptnum2ordinal(4)
```

The following example returns the string '23rd'.

```
str = iptnum2ordinal(23)
```

Introduced before R2006a

iptPointerManager

Create pointer manager in figure

Syntax

```
iptPointerManager(hFigure)
iptPointerManager(hFigure, 'disable')
iptPointerManager(hFigure, 'enable')
```

Description

`iptPointerManager(hFigure)` creates a pointer manager in the specified figure. The pointer manager controls pointer behavior for any Handle Graphics objects in the figure that contain pointer behavior structures. Use `iptSetPointerBehavior` to associate a pointer behavior structure with a particular object to define specific actions that occur when the mouse pointer moves over and then leaves the object. See `iptSetPointerBehavior` for more information.

`iptPointerManager(hFigure, 'disable')` disables the figure's pointer manager.

`iptPointerManager(hFigure, 'enable')` enables and updates the figure's pointer manager.

Note: If the figure already contains a pointer manager, `iptPointerManager(hFigure)` does not create a new one. It has the same effect as `iptPointerManager(hFigure, 'enable')`.

Examples

Plot a line. Create a pointer manager in the figure. Then, associate a pointer behavior structure with the line object in the figure that changes the mouse pointer into a fleur whenever the pointer is over it.

```
h = plot(1:10);
```

```
iptPointerManager(gcf);  
enterFcn = @(hFigure, currentPoint)...  
            set(hFigure, 'Pointer', 'fleur');  
iptSetPointerBehavior(h, enterFcn);
```

More About

Tips

`iptPointerManager` considers not just the object the pointer is over, but all objects in the figure. `iptPointerManager` searches the HG hierarchy to find the first object that contains a pointer behavior structure. The `iptPointerManager` then executes that object's pointer behavior function. For example, you could set the pointer to be a fleur and associate that pointer with the axes. Then, when you slide the pointer into the figure window, it will initially be the default pointer, then change to a fleur when you cross into the axes, and remain a fleur when you slide over the objects parented to the axes.

See Also

`iptGetPointerBehavior` | `iptSetPointerBehavior`

Introduced in R2006a

iptprefs

Display Image Processing Toolbox Preferences dialog box

Syntax

`iptprefs`

Description

`iptprefs` opens the Image Processing Toolbox Preferences dialog box, part of the MATLAB Preferences dialog box. You can also open this dialog box by clicking **Preferences** on the Home tab, in the Environment section.

The Image Processing Toolbox Preferences dialog box contains display preferences for `imtool` and `imshow`, and provides an option for enabling hardware optimizations. You can set all preferences at the command line with the `iptsetpref` function. The following figure shows how the preferences relate to options in the Preferences dialog box.




Image Processing Toolbox Preferences Dialog Box

The following table details the available preferences and their syntaxes. Note that preference names are case insensitive and you can abbreviate them. The default value appears enclosed in braces ({}).

Available Image Processing Toolbox Preferences

Preference Name	Description
'ImtoolStartWithOverview'	Controls whether the Overview tool opens automatically when you open an image using the Image Tool (<code>imtool</code>). Possible values:

Preference Name	Description
	<p><code>true</code>— Overview tool opens when you open an image.</p> <p><code>{false}</code>— Overview tool does not open when you open an image. This is the default behavior.</p>
'ImtoolInitialMagnification'	<p>Controls the initial magnification of the image displayed by <code>imtool</code>. Possible values:</p> <p><code>{ 'adaptive' }</code> — Display the entire image. If the image is too large to display on the screen at 100% magnification, display the image at the largest magnification that fits on the screen. This is the default.</p> <p>Any numeric value — Specify the magnification as a percentage. A magnification of 100% means that there should be one screen pixel for every image pixel.</p> <p><code>'fit'</code> — Scale the image so that it fits into the window in its entirety.</p> <p>You can override this preference by specifying the <code>'InitialMagnification'</code> parameter when you call <code>imtool</code>.</p>
'ImshowAxesVisible'	<p>Controls whether <code>imshow</code> displays images with the axes box and tick labels. Possible values:</p> <p><code>'on'</code> — Include axes box and tick labels.</p> <p><code>{ 'off' }</code> — Do not include axes box and tick labels.</p>
'ImshowBorder'	<p>Controls whether <code>imshow</code> includes a border around the image in the figure window. Possible values:</p>

Preference Name	Description
	<p>{ 'loose ' } — Include a border between the image and the edges of the figure window, thus leaving room for axes labels, titles, etc.</p> <p>' tight ' — Adjust the figure size so that the image entirely fills the figure.</p> <hr/> <p>Note: There still can be a border if the image is very small, or if there are other objects besides the image and its axes in the figure.</p> <hr/> <p>You can override this preference by specifying the 'Border' parameter when you call <code>imshow</code>.</p>
'ImshowInitialMagnification'	<p>Controls the initial magnification of the image displayed by <code>imshow</code>. Possible values:</p> <p>Any numeric value — <code>imshow</code> interprets numeric values as a percentage. The default value is 100. A magnification of 100% means that there should be one screen pixel for every image pixel.</p> <p>' fit ' — Scale the image so that it fits into the window in its entirety.</p> <p>You can override this preference by specifying the 'InitialMagnification' parameter when you call <code>imshow</code>, or by calling the <code>truesize</code> function manually after displaying the image.</p>
'UseIPPL'	<p>Controls whether some toolbox functions use hardware optimization or not. Possible values:</p> <p>{true} — Enable hardware optimization</p> <p>false — Disable hardware optimization</p>

Preference Name	Description
	Note: Setting this preference value clears all loaded MEX-files.

See Also

imshow | imtool | iptgetpref | iptsetpref

Introduced in R2009a

iptremovecallback

Delete function handle from callback list

Syntax

```
iptremovecallback(h,callback,ID)
```

Description

`iptremovecallback(h,callback,ID)` deletes a callback from the list of callbacks created by `imaddcallback` for the object with handle `h` and the associated callback string `callback`. `ID` is the identifier of the callback to be deleted. This `ID` is returned by `iptaddcallback` when you add the function handle to the callback list.

Examples

Register three callbacks and try them interactively.

```
h = figure;  
f1 = @(varargin) disp('Callback 1');  
f2 = @(varargin) disp('Callback 2');  
f3 = @(varargin) disp('Callback 3');  
id1 = iptaddcallback(h, 'WindowButtonMotionFcn', f1);  
id2 = iptaddcallback(h, 'WindowButtonMotionFcn', f2);  
id3 = iptaddcallback(h, 'WindowButtonMotionFcn', f3);
```

Remove one of the callbacks and then move the mouse over the figure again. Whenever MATLAB detects mouse motion over the figure, function handles `f1` and `f3` are called in that order.

```
iptremovecallback(h, 'WindowButtonMotionFcn', id2);
```

See Also

`iptaddcallback`

Introduced before R2006a

iptSetPointerBehavior

Store pointer behavior structure in Handle Graphics object

Syntax

```
iptSetPointerBehavior(h, pointerBehavior)
iptSetPointerBehavior(h, [])
iptSetPointerBehavior(h, enterFcn)
```

Description

`iptSetPointerBehavior(h, pointerBehavior)` stores the specified pointer behavior structure in the specified Handle Graphics object, `h`. If `h` is an array of objects, `iptSetPointerBehavior` stores the same structure in each object.

When used with a figure's pointer manager (see `iptPointerManager`), a pointer behavior structure controls what happens when the figure's mouse pointer moves over and then exits an object in the figure. For details about this structure, see "Pointer Behavior Structure" on page 1-1167.

`iptSetPointerBehavior(h, [])` clears the pointer behavior from the Handle Graphics object or objects.

`iptSetPointerBehavior(h, enterFcn)` creates a pointer behavior structure, setting the `enterFcn` field to the function handle specified, and setting the `traverseFcn` and `exitFcn` fields to `[]`. See "Pointer Behavior Structure" on page 1-1167 for details about these fields. This syntax is provided as a convenience because, for most common uses, only the `enterFcn` is necessary.

Pointer Behavior Structure

A pointer behavior structure contains three fields: `enterFcn`, `traverseFcn`, and `exitFcn`. You set the value of these fields to function handles and use the `iptSetPointerBehavior` function to associate this structure with an HG object in a figure. If the figure has a pointer manager installed, the pointer manager calls these functions when the following events occur. If you set a field to `[]`, no action is taken.

Function Handle	When Called
<code>enterFcn</code>	Called when the mouse pointer moves over the object.
<code>traverseFcn</code>	Called once when the mouse pointer moves over the object, and called again each time the mouse moves within the object.
<code>exitFcn</code>	Called when the mouse pointer leaves the object.

When the pointer manager calls the functions you create, it passes two arguments: a handle to the figure and the current position of the pointer.

Examples

Example 1

Change the mouse pointer to a fleur whenever it is over a specific object and restore the original pointer when the mouse pointer moves off the object. The example creates a patch object and associates a pointer behavior structure with the object. Because this scenario requires only an `enterFcn`, the example uses the `iptSetPointerBehavior(n, enterFcn)` syntax. The example then creates a pointer manager in the figure. Note that the pointer manager takes care of restoring the original figure pointer.

```
hPatch = patch([.25 .75 .75 .25 .25],...  
              [.25 .25 .75 .75 .25], 'r');  
xlim([0 1]);  
ylim([0 1]);  
  
enterFcn = @(figHandle, currentPoint)...  
           set(figHandle, 'Pointer', 'fleur');  
iptSetPointerBehavior(hPatch, enterFcn);  
iptPointerManager(gcf);
```

Example 2

Change the appearance of the mouse pointer, depending on where it is within the object. This example sets up the pointer behavior structure, setting the `enterFcn` and `exitFcn` fields to `[]`, and setting `traverseFcn` to a function named `overMe` that handles the position-specific behavior. `overMe` is an example function (in `\toolbox\images`

\imdemos) that varies the mouse pointer depending on the location of the mouse within the object. For more information, edit `overMe`.

```
hPatch = patch([.25 .75 .75 .25 .25],...
               [.25 .25 .75 .75 .25], 'r');
xlim([0 1])
ylim([0 1])

pointerBehavior.enterFcn = [];
pointerBehavior.exitFcn = [];
pointerBehavior.traverseFcn = @overMe;

iptSetPointerBehavior(hPatch, pointerBehavior);
iptPointerManager(gcf);
```

Example 3

Change the figure's title when the mouse pointer is over the object. In this scenario, `enterFcn` and `exitFcn` are used to achieve the desired side effect, and `traverseFcn` is `[]`.

```
hPatch = patch([.25 .75 .75 .25 .25],...
               [.25 .25 .75 .75 .25], 'r');
xlim([0 1])
ylim([0 1])

pointerBehavior.enterFcn = ...
    @(figHandle, currentPoint)...
    set(figHandle, 'Name', 'Over patch');
pointerBehavior.exitFcn = ...
    @(figHandle, currentPoint) set(figHandle, 'Name', '');
pointerBehavior.traverseFcn = [];

iptSetPointerBehavior(hPatch, pointerBehavior);
iptPointerManager(gcf)
```

See Also

`iptGetPointerBehavior` | `iptPointerManager`

Introduced in R2006a

iptsetpref

Set Image Processing Toolbox preferences or display valid values

Syntax

```
iptsetpref(prefname)  
iptsetpref(prefname,value)
```

Description

`iptsetpref(prefname)` displays the valid values for the Image Processing Toolbox preference specified by `prefname`.

`iptsetpref(prefname,value)` sets the Image Processing Toolbox preference specified by the string `prefname` to the value specified by `value`. The setting persists until you change it. You can also use the Image Processing Preferences dialog box to set the preferences. To access the dialog, select **Preferences** from the **File** menu in the MATLAB desktop. For more information about available preferences, see `iptprefs`.

Examples

```
iptsetpref('ImshowBorder','tight')
```

See Also

`imshow` | `imtool` | `iptgetpref` | `iptprefs`

Introduced before R2006a

iptwindowalign

Align figure windows


Syntax

```
iptwindowalign(fixed_fig, fixed_fig_edge, moving_fig,  
moving_fig_edge)
```

Description

`iptwindowalign(fixed_fig, fixed_fig_edge, moving_fig, moving_fig_edge)` moves the figure `moving_fig` to align it with the figure `fixed_fig`. `moving_fig` and `fixed_fig` are handles to figure objects.

`fixed_fig_edge` and `moving_fig_edge` describe the alignment of the figures in relation to their edges and can take any of the following values: 'left', 'right', 'hcenter', 'top', 'bottom', or 'vcenter'. 'hcenter' means center horizontally and 'vcenter' means center vertically. The following figure shows these alignments.



Notes

The two specified locations must be consistent in terms of their direction. For example, you cannot specify 'left' for `fixed_fig_edge` and 'bottom' for `moving_fig_edge`.

`iptwindowalign` constrains the position adjustment of `moving_fig` to keep it entirely visible on the screen.

`iptwindowalign` has no effect if either figure window is docked.


Examples

To illustrate some possible figure window alignments, first create two figures: `fig1` and `fig2`. Initially, `fig2` overlays `fig1` on the screen.

```
fig1 = figure;  
fig2 = figure;
```


Use `iptwindowalign` to move `fig2` so its left edge is aligned with the right edge of `fig1`.

```
iptwindowalign(fig1, 'right', fig2, 'left');
```




Now move `fig2` so its top edge is aligned with the bottom edge of `fig1`.

```
iptwindowalign(fig1, 'bottom', fig2, 'top');
```



Now move `fig2` so the two figures are centered horizontally.

```
iptwindowalign(fig1, 'hcenter', fig2, 'hcenter');
```



See Also

`imtool`

Introduced before R2006a

iradon

Inverse Radon transform

Syntax

```
I = iradon(R, theta)
I = iradon(R, theta, interp, filter, frequency_scaling, output_size)
[I, H] = iradon(...)
[ ___ ] = iradon(gpuarrayR, ___)
```

Description

`I = iradon(R, theta)` reconstructs the image `I` from projection data in the two-dimensional array `R`. The columns of `R` are parallel beam projection data. `iradon` assumes that the center of rotation is the center point of the projections, which is defined as `ceil(size(R,1)/2)`.

`theta` describes the angles (in degrees) at which the projections were taken. It can be either a vector containing the angles or a scalar specifying `D_theta`, the incremental angle between projections. If `theta` is a vector, it must contain angles with equal spacing between them. If `theta` is a scalar specifying `D_theta`, the projections were taken at angles `theta = m*D_theta`, where `m = 0, 1, 2, ..., size(R,2) - 1`. If the input is the empty matrix (`[]`), `D_theta` defaults to `180/size(R,2)`.

`iradon` uses the filtered back-projection algorithm to perform the inverse Radon transform. The filter is designed directly in the frequency domain and then multiplied by the FFT of the projections. The projections are zero-padded to a power of 2 before filtering to prevent spatial domain aliasing and to speed up the FFT.

`I = iradon(R, theta, interp, filter, frequency_scaling, output_size)` specifies parameters to use in the inverse Radon transform. You can specify any combination of the last four arguments. `iradon` uses default values for any of these arguments that you omit.

`interp` specifies the type of interpolation to use in the back projection. The available options are listed in order of increasing accuracy and computational complexity.

Value	Description
'nearest'	Nearest-neighbor interpolation
'linear'	Linear interpolation (the default)
'spline'	Spline interpolation
'pchip'	Shape-preserving piecewise cubic interpolation
'v5cubic'	Cubic interpolation from MATLAB 5. This method does not extrapolate, and it issues a warning and uses 'spline' if X is not equally spaced.

`filter` specifies the filter to use for frequency domain filtering. `filter` can be any of the strings that specify standard filters.

Value	Description
'Ram-Lak'	Cropped Ram-Lak or ramp filter. This is the default. The frequency response of this filter is $ f $. Because this filter is sensitive to noise in the projections, one of the filters listed below might be preferable. These filters multiply the Ram-Lak filter by a window that deemphasizes high frequencies.
'Shepp-Logan'	Multiplies the Ram-Lak filter by a <code>sinc</code> function
'Cosine'	Multiplies the Ram-Lak filter by a <code>cosine</code> function
'Hamming'	Multiplies the Ram-Lak filter by a Hamming window
'Hann'	Multiplies the Ram-Lak filter by a Hann window
'None'	No filtering. When you specify this value, <code>iradon</code> returns unfiltered backprojection data.

`frequency_scaling` is a scalar in the range (0,1] that modifies the filter by rescaling its frequency axis. The default is 1. If `frequency_scaling` is less than 1, the filter is compressed to fit into the frequency range $[0, \text{frequency_scaling}]$, in normalized frequencies; all frequencies above `frequency_scaling` are set to 0.

`output_size` is a scalar that specifies the number of rows and columns in the reconstructed image. If `output_size` is not specified, the size is determined from the length of the projections.

```
output_size = 2*floor(size(R,1)/(2*sqrt(2)))
```

If you specify `output_size`, `iradon` reconstructs a smaller or larger portion of the image but does not change the scaling of the data. If the projections were calculated with the `radon` function, the reconstructed image might not be the same size as the original image.

`[I,H] = iradon(...)` returns the frequency response of the filter in the vector `H`.

`[___]= iradon(gpuarrayR, ___)` reconstructs the image `gpuarrayI` from projection data in the `gpuArray` `R`. The input image and the return values are 2-D `gpuArrays`. All other numeric arguments must be a `double` or a `gpuArray` of underlying class `double`. This syntax requires the Parallel Computing Toolbox.

Note: The GPU implementation of this function supports only nearest-neighbor and linear interpolation methods for the back projection.

Class Support

`R` can be `double` or `single`. All other numeric input arguments must be of class `double`. `I` has the same class as `R`. `H` is `double`.

`R` can be a `gpuArray` of underlying class `double` or `single`. All other numeric input arguments must be `double` or `gpuArray` of underlying class `double`. `I` has the same class as `R`. `H` is a `gpuArray` of underlying class `double`.

Examples

Calculate the inverse Radon Transform comparing filtered and unfiltered backprojection

Calculate the inverse Radon transform and compare filtered and unfiltered back projection.

```
P = phantom(128);
R = radon(P,0:179);
I1 = iradon(R,0:179);
I2 = iradon(R,0:179,'linear','none');
subplot(1,3,1), imshow(P), title('Original')
subplot(1,3,2), imshow(I1), title('Filtered backprojection')
subplot(1,3,3), imshow(I2,[]), title('Unfiltered backprojection')
```



Compute the backprojection of a single projection vector. The `iradon` syntax does not allow you to do this directly, because if `theta` is a scalar it is treated as an increment. You can accomplish the task by passing in two copies of the projection vector and then dividing the result by 2.

```
P = phantom(128);
R = radon(P,0:179);
r45 = R(:,46);
I = iradon([r45 r45], [45 45])/2;
imshow(I, [])
title('Backprojection from the 45-degree projection')
```

Calculate the inverse Radon transform on a GPU

Calculate the inverse Radon transform on a GPU.

```
P = gpuArray(phantom(128));
R = radon(P,0:179);
I1 = iradon(R,0:179);
I2 = iradon(R,0:179,'linear','none');
subplot(1,3,1), imshow(P), title('Original')
subplot(1,3,2), imshow(I1), title('Filtered backprojection')
subplot(1,3,3), imshow(I2,[]), title('Unfiltered backprojection')
```

More About

Algorithms

`iradon` uses the filtered back projection algorithm to perform the inverse Radon transform. The filter is designed directly in the frequency domain and then multiplied

by the FFT of the projections. The projections are zero-padded to a power of 2 before filtering to prevent spatial domain aliasing and to speed up the FFT.

References

- [1] Kak, A. C., and M. Slaney, *Principles of Computerized Tomographic Imaging*, New York, NY, IEEE Press, 1988.

See Also

fan2para | fanbeam | ifanbeam | para2fan | phantom | radon

Introduced before R2006a

isbw

True for binary image

Syntax

```
flag = isbw(A)
```

Note: `isbw` has been removed.

Description

`flag = isbw(A)` returns 1 if `A` is a binary image and 0 otherwise.

The input image `A` is considered to be a binary image if it is a nonsparse logical array.

Class Support

The input image `A` can be any MATLAB array.

See Also

`isind` | `isgray` | `isrgb`

Introduced before R2006a

isflat

True for flat structuring element

Note: `isflat` will be removed in a future release. See `strel` for the current list of methods.

Syntax

TF = `isflat`(SE)

Description

TF = `isflat`(SE) returns true (1) if the structuring element SE is flat; otherwise it returns false (0). If SE is an array of STREL objects, then TF is the same size as SE.

Class Support

SE is a STREL object. TF is a double-precision value.

Introduced before R2006a

isgray

True for grayscale image

Syntax

```
flag = isgray(A)
```

Note: `isgray` has been removed.

Description

`flag = isgray(A)` returns 1 if `A` is a grayscale intensity image and 0 otherwise.

`isgray` uses these criteria to decide whether `A` is an intensity image:

- If `A` is of class `double`, all values must be in the range `[0,1]`, and the number of dimensions of `A` must be 2.
- If `A` is of class `uint16` or `uint8`, the number of dimensions of `A` must be 2.

Note A four-dimensional array that contains multiple grayscale images returns 0, not 1.

Class Support

The input image `A` can be of class `logical`, `uint8`, `uint16`, or `double`.

See Also

`isbw` | `isind` | `isrgb`

Introduced before R2006a

isicc

True for valid ICC color profile

Syntax

```
TF = isicc(P)
```

Description

`TF = isicc(P)` returns `True` if structure `P` is a valid ICC color profile; otherwise `False`.

`isicc` checks if `P` has a complete set of the tags required for an ICC profile. `P` must contain a `Header` field, which in turn must contain a `Version` field and a `DeviceClass` field. These fields, and others, are used to determine the set of required tags according to the ICC Profile Specification, either Version 2 (ICC.1:2001-04) or Version 4 (ICC.1:2001-12), which are available at www.color.org. The set of required tags is given in Section 6.3 in either version.

Examples

Read in an ICC profile and `isicc` returns `True`.

```
P = iccread('sRGB.icm');
```

```
TF = isicc(P)
```

```
TF =
```

```
1
```

This example creates a MATLAB structure and uses `isicc` to test if it's a valid ICC profile. `isicc` returns `False`.

```
S.name = 'Any Student';  
S.score = 83;
```

```
S.grade = 'B+'
```

```
TF = isicc(S)
```

```
TF =
```

```
    0
```

See Also

`applycform` | `iccread` | `iccwrite` | `makecform`

Introduced before R2006a

isind

True for indexed image

Syntax

```
flag = isind(A)
```

Note: `isind` has been removed.

Description

`flag = isind(A)` returns 1 if `A` is an indexed image and 0 otherwise.

`isind` uses these criteria to determine if `A` is an indexed image:

- If `A` is of class `double`, all values in `A` must be integers greater than or equal to 1, and the number of dimensions of `A` must be 2.
- If `A` is of class `uint8` or `uint16`, the number of dimensions of `A` must be 2.

Note A four-dimensional array that contains multiple indexed images returns 0, not 1.

Class Support

`A` can be of class `logical`, `uint8`, `uint16`, or `double`.

See Also

`isbw` | `isgray` | `isrgb`

Introduced before R2006a

isnif

Check if file is National Imagery Transmission Format (NITF) file

Syntax

```
[tf, NITF_version] = isnif(filename)
```

Description

`[tf, NITF_version] = isnif(filename)` returns **True** (1) if the file specified by `filename` is a National Imagery Transmission Format (NITF) file, otherwise **False** (0). If the file is a NITF file, `isnif` returns a text string identifying the NITF version in `NITF_version`, such as '2.1'. If the file is not a NITF file, `NITF_version` contains the text string 'UNK'.

See Also

`nitfinfo` | `nitfread`

Introduced in R2007b

isrgb

True for RGB image

Syntax

```
flag = isrgb(A)
```

Note: `isrgb` has been removed.

Description

`flag = isrgb(A)` returns 1 if `A` is an RGB truecolor image and 0 otherwise.

`isrgb` uses these criteria to determine whether `A` is an RGB image:

- If `A` is of class `double`, all values must be in the range `[0,1]`, and `A` must be `m-by-n-by-3`.
- If `A` is of class `uint16` or `uint8`, `A` must be `m-by-n-by-3`.

Note A four-dimensional array that contains multiple RGB images returns 0, not 1.

Class Support

`A` can be of class `logical`, `uint8`, `uint16`, or `double`.

See Also

`isbw` | `isgray` | `isind`

Introduced before R2006a

isrset

Check if file is R-Set

Syntax

```
[tf, supported] = isrset(filename)
```

Description

`[tf, supported] = isrset(filename)` sets `tf` to true if the file `filename` is a reduced resolution dataset (R-Set) created by `rsetwrite` and false if it is not. The value of `supported` is true if the R-Set file is compatible with the R-Set tools (such as `imtool`) in the version of the Image Processing Toolbox you are using. If `supported` is false, the R-Set file was probably created by a newer version of `rsetwrite` than the one in the version of the Image Processing Toolbox you are using.

See Also

`rsetwrite`

Introduced in R2009a

lab2double

Convert $L^*a^*b^*$ data to double

Syntax

```
labd = lab2double(lab)
```

Description

`labd = lab2double(lab)` converts an M-by-3 or M-by-N-by-3 array of $L^*a^*b^*$ color values to class `double`. The output array `labd` has the same size as `lab`.

The Image Processing Toolbox software follows the convention that double-precision $L^*a^*b^*$ arrays contain 1976 CIE $L^*a^*b^*$ values. $L^*a^*b^*$ arrays that are `uint8` or `uint16` follow the convention in the ICC profile specification (ICC.1:2001-4, www.color.org) for representing $L^*a^*b^*$ values as unsigned 8-bit or 16-bit integers. The ICC encoding convention is illustrated by these tables.

Value (L^*)	uint8 Value	uint16 Value
0.0	0	0
100.0	255	65280
$100.0 + (25500/65280)$	None	65535

Value (a^* or b^*)	uint8 Value	uint16 Value
-128.0	0	0
0.0	128	32768
127.0	255	65280
$127.0 + (255/256)$	None	65535

Class Support

`lab` is a `uint8`, `uint16`, or `double` array that must be real and nonsparse. `labd` is `double`.

Examples

Convert full intensity neutral color (white) from `uint8` to `double`.

```
lab2double(uint8([255 128 128]))  
ans =
```

```
    100     0     0
```

See Also

`applycform` | `lab2uint8` | `lab2uint16` | `makecform` | `whitepoint` | `xyz2double`
| `xyz2uint16`

Introduced before R2006a

lab2rgb

Convert CIE 1976 L*a*b* to RGB

Syntax

```
rgb = lab2rgb(lab)
rgb = lab2rgb(lab,Name,Value)
```

Description

`rgb = lab2rgb(lab)` converts CIE 1976 L*a*b* values to RGB values.

`rgb = lab2rgb(lab,Name,Value)` specifies additional options with one or more Name,Value pair arguments.

“Code Generation” on page 1-1194 support: Yes.

“MATLAB Function Block” on page 1-1194 support: Yes.

Examples

Convert L*a*b* color to RGB

```
lab2rgb([70 5 10])
ans =
    0.7358    0.6566    0.6010
```

Convert L*a*b* color to Adobe RGB (1998)

```
lab2rgb([70 5 10], 'ColorSpace', 'adobe-rgb-1998')
ans =
```

```
0.7086    0.6507    0.5978
```

Convert L*a*b* color to sRGB using D50 as reference white

```
lab2rgb([70 5 10], 'WhitePoint', 'd50')
```

```
ans =
```

```
0.7281    0.6574    0.6007
```

Convert L*a*b* color to 8-bit-encoded RGB color

```
lab2rgb([70 5 10], 'OutputType', 'uint8')
```

```
ans =
```

```
188 167 153
```

Input Arguments

lab — Color values to convert

P-by-3 matrix | M-by-N-by-3 image array | M-by-N-by-3-by-F image stack

Color values to convert, specified as a P-by-3 matrix of color values (one color per row), an M-by-N-by-3 image array, or an M-by-N-by-3-by-F image stack.

Example: `lab2rgb([70 5 10])`

Data Types: `single` | `double`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1`, `Value1`, ..., `NameN`, `ValueN`.

Example: `lab2rgb([70 5 10], 'WhitePoint', 'd50')`

'ColorSpace' — Color space of the input RGB values

'srgb' (default) | 'adobe-rgb-1998'

Color space of the input RGB values, specified as the text string 'srgb' or 'adobe-rgb-1998'.

Example: `lab2rgb([70 5 10], 'ColorSpace', 'adobe-rgb-1998')`

Data Types: char

'WhitePoint' — Reference white point

'd65' (default) | 'd50' | 'a' | 'c' | 'icc' | 'e' | 1-by-3 vector

Reference white point, specified as a 1-by-3 vector or one of the CIE standard illuminants, listed in the following table.

String Value	White Point
'a'	CIE standard illuminant A, [1.0985, 1.0000, 0.3558]. Simulates typical, domestic, tungsten-filament lighting.
'c'	CIE standard illuminant C, [0.9807, 1.0000, 1.1822]. Simulates daylight with correlated color temperature of 4874 K. Deprecated by CIE.
'd50'	CIE standard illuminant D50, [0.9642, 1.0000, 0.8251]. Simulates daylight with correlated color temperature of 5003 K.
'd65'	CIE standard illuminant D65, [0.9504, 1.0000, 1.0888]. Simulates daylight with correlated color temperature of 6504 K.
'icc'	Profile Connection Space (PCS) illuminant used in ICC profiles. Approximation of [0.962, 1.000, 0.8249] using fixed-point, signed, 32-bit numbers with 16 fractional bits. Actual value: [31595, 32768, 27030] / 32768.
'e'	Equal-energy radiator. Useful as a theoretical reference. [1.000, 1.000, 1.000].

Example: `lab2rgb([70 5 10], 'WhitePoint', 'd50')`

Data Types: single | double | char

'OutputType' — Data type of returned RGB values

'double' | 'single' | 'uint8' | 'uint16'

Data type of returned RGB values, specified as one of the following text strings: 'double', 'single', 'uint8', or 'uint16'. If you do not specify `OutputType`, the output type is the same type as the input.

Example: `lab2rgb([70 5 10], 'OutputType', 'uint8')`

Data Types: char

Output Arguments

rgb — Converted color values

array the same shape as the input

Converted color values, returned as an array the same shape as the input. The output type is the same as the input class unless you specify the type using the 'OutputType' parameter.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, all string input arguments must be compile-time constants.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

lab2xyz | rgb2lab | rgb2xyz | xyz2lab | xyz2rgb

Introduced in R2014b

lab2uint16

Convert $L^*a^*b^*$ data to uint16

Syntax

```
lab16 = lab2uint16(lab)
```

Description

`lab16 = lab2uint16(lab)` converts an M-by-3 or M-by-N-by-3 array of $L^*a^*b^*$ color values to `uint16`. `lab16` has the same size as `lab`.

The Image Processing Toolbox software follows the convention that double-precision $L^*a^*b^*$ arrays contain 1976 CIE $L^*a^*b^*$ values. $L^*a^*b^*$ arrays that are `uint8` or `uint16` follow the convention in the ICC profile specification (ICC.1:2001-4, www.color.org) for representing $L^*a^*b^*$ values as unsigned 8-bit or 16-bit integers. The ICC encoding convention is illustrated by these tables.

Value (L^*)	uint8 Value	uint16 Value
0.0	0	0
100.0	255	65280
100.0 + (25500/65280)	None	65535

Value (a^* or b^*)	uint8 Value	uint16 Value
-128.0	0	0
0.0	128	32768
127.0	255	65280
127.0 + (255/256)	None	65535

Class Support

`lab` can be a `uint8`, `uint16`, or `double` array that must be real and nonsparse. `lab16` is of class `uint16`.

Examples

Convert full intensity neutral color (white) from `double` to `uint16`.

```
lab2uint16(100 0 0)
ans =
```

```
65280 32768 32768
```

See Also

`applycform` | `lab2double` | `lab2uint8` | `makecform` | `whitepoint` | `xyz2double`
| `xyz2uint16`

Introduced before R2006a

lab2uint8

Convert $L^*a^*b^*$ data to uint8

Syntax

```
lab8 = lab2uint8(lab)
```

Description

`lab8 = lab2uint8(lab)` converts an M-by-3 or M-by-N-by-3 array of $L^*a^*b^*$ color values to uint8. `lab8` has the same size as `lab`.

The Image Processing Toolbox software follows the convention that double-precision $L^*a^*b^*$ arrays contain 1976 CIE $L^*a^*b^*$ values. $L^*a^*b^*$ arrays that are uint8 or uint16 follow the convention in the ICC profile specification (ICC.1:2001-4, www.color.org) for representing $L^*a^*b^*$ values as unsigned 8-bit or 16-bit integers. The ICC encoding convention is illustrated by these tables.

Value (L^*)	uint8 Value	uint16 Value
0.0	0	0
100.0	255	65280
$100.0 + (25500/65280)$	None	65535

Value (a^* or b^*)	uint8 Value	uint16 Value
-128.0	0	0
0.0	128	32768
127.0	255	65280
$127.0 + (255/256)$	None	65535

Class Support

`lab` is a uint8, uint16, or double array that must be real and nonsparse. `lab8` is uint8.

Examples

Convert full intensity neutral color (white) from `double` to `uint8`.

```
lab2uint8([100 0 0])  
ans =
```

```
    255    128    128
```

See Also

[applycform](#) | [lab2double](#) | [lab2uint16](#) | [makecform](#) | [whitepoint](#) | [xyz2double](#)
| [xyz2uint16](#)

Introduced before R2006a

lab2xyz

Convert CIE 1976 L*a*b* to CIE 1931 XYZ

Syntax

```
xyz = lab2xyz(lab)
xyz = lab2xyz(lab,Name,Value)
```

Description

`xyz = lab2xyz(lab)` converts CIE 1976 L*a*b* values to CIE 1931 XYZ values.

`xyz = lab2xyz(lab,Name,Value)` specifies additional options with one or more Name,Value pair arguments.

Examples

Convert L*a*b* color to XYZ

```
lab2xyz([50 10 -5])
ans =
```

```
    0.1942    0.1842    0.2282
```

Convert L*a*b* color to XYZ using d50 as reference white

```
lab2xyz([50 10 -5], 'WhitePoint', 'd50')
ans =
```

```
    0.1970    0.1842    0.1729
```

Input Arguments

lab — Color values to convert

P-by-3 matrix | M-by-N-by-3 image array | M-by-N-by-3-by-F image stack

Color values to convert, specified as a P-by-3 matrix of color values (one color per row), an M-by-N-by-3 image array, or an M-by-N-by-3-by-F image stack.

Example: `lab2xyz([0.25 0.40 0.10])`

Data Types: `single` | `double`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1`, `Value1`, ..., `NameN`, `ValueN`.

Example: `lab2xyz([0.25 0.40 0.10], 'WhitePoint', 'd50')`

'WhitePoint' — Reference white point

'd65' (default) | 'a' | 'c' | 'd50' | 'icc' | 'e' | 1-by-3 vector

Reference white point, specified as a 1-by-3 vector or one of the CIE standard illuminants, listed in the following table.

String Value	White Point
'a'	CIE standard illuminant A, [1.0985, 1.0000, 0.3558]. Simulates typical, domestic, tungsten-filament lighting.
'c'	CIE standard illuminant C, [0.9807, 1.0000, 1.1822]. Simulates daylight with correlated color temperature of 4874 K. Deprecated by CIE.
'd50'	CIE standard illuminant D50, [0.9642, 1.0000, 0.8251]. Simulates daylight with correlated color temperature of 5003 K.
'd65'	CIE standard illuminant D65, [0.9504, 1.0000, 1.0888]. Simulates daylight with correlated color temperature of 6504 K.
'icc'	Profile Connection Space (PCS) illuminant used in ICC profiles. Approximation of [0.962, 1.000, 0.8249] using fixed-point, signed, 32-bit numbers with 16 fractional bits. Actual value: [31595, 32768, 27030]/32768.
'e'	Equal-energy radiator. Useful as a theoretical reference. [1.000, 1.000, 1.000].

Example: `lab2xyz([0.25 0.40 0.10], 'WhitePoint', 'd50')`

Data Types: `single` | `double` | `char`

Output Arguments

xyz — Converted color values

array the same shape and type as the input

Converted color values, returned as an array the same shape and type as the input.

See Also

`rgb2lab` | `rgb2xyz` | `xyz2lab` | `xyz2rgb`

Introduced in R2014b

label2idx

Convert label matrix to cell array of linear indices

Syntax

```
pixelIndexList = label2idx(L)
```

Description

`pixelIndexList = label2idx(L)` converts the regions described by the label matrix `L` into the 1-by- N cell array of linear indices `pixelIndexList`.

“Code Generation” on page 1-1204 support: Yes.

MATLAB Function Block support: No.

Examples

Calculate Pixel Index List for Small Label Matrix

Create a small sample matrix containing three regions.

```
BW = logical([1 1 1 0 0 0 0 0  
             1 1 1 0 1 1 0 0  
             1 1 1 0 1 1 0 0  
             1 1 1 0 0 0 0 0  
             1 1 1 0 0 0 1 0  
             1 1 1 0 0 0 1 0  
             1 1 1 0 0 1 1 0  
             1 1 1 0 0 0 0 0]);
```

Create a label matrix from this sample image.

```
L = bwlabel(BW)
```

```
L =
```



```

1    1    1    0    0    0    0    0
1    1    1    0    2    2    0    0
1    1    1    0    2    2    0    0
1    1    1    0    0    0    0    0
1    1    1    0    0    0    3    0
1    1    1    0    0    0    3    0
1    1    1    0    0    3    3    0
1    1    1    0    0    0    0    0

```

Get a linear index list of all the pixels in each region. The function returns a cell array with an element for each region it finds in the label matrix.

```
pixelIndexList = label2idx(L)
```

```
pixelIndexList =
```

```
    [24x1 double]    [4x1 double]    [4x1 double]
```

Examine one of the pixel index lists returned. For example, look at the second cell in the returned cell array. It contains the linear indices for all the pixels in the region labeled "2". The upper left corner of the region is pixel BW(2,5), which is the 34th pixel in linear indexing.

```
pixelIndexList{2}
```

```
ans =
```

```

34
35
42
43

```

Input Arguments

L — Label matrix

real, nonsparse, nonnegative, finite numeric N-D matrix

Label matrix, specified as a real, nonsparse, nonnegative, finite numeric N-D matrix.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

Output Arguments

pixelIndexList — Linear indices of pixels in regions

1-by- N cell array

Linear indices of pixels in regions, returned as a 1-by- N cell array. Each element of the output, `pixelIndexList{N}`, is a vector that contains all the linear indices in L where L is equal to N .

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

See Also

`labelmatrix` | `superpixels`

Introduced in R2016a

label2rgb

Convert label matrix into RGB image

Syntax

```

RGB = label2rgb(L)
RGB = label2rgb(L, map)
RGB = label2rgb(L, map, zerocolor)
RGB = label2rgb(L, map, zerocolor, order)

```

Description

`RGB = label2rgb(L)` converts a label matrix, `L`, such as those returned by `labelmatrix`, `bwlabel`, `bwlabeln`, or `watershed`, into an RGB color image for the purpose of visualizing the labeled regions. The `label2rgb` function determines the color to assign to each object based on the number of objects in the label matrix and range of colors in the colormap. The `label2rgb` function picks colors from the entire range.

`RGB = label2rgb(L, map)` defines the colormap `map` to be used in the RGB image. `map` can have any of the following values:

- n -by-3 colormap matrix
- String containing the name of a MATLAB colormap function, such as `'jet'` or `'gray'` (See `colormap` for a list of supported colormaps.)
- Function handle of a colormap function, such as `@jet` or `@gray`

If you do not specify `map`, the default value is `'jet'`.

`RGB = label2rgb(L, map, zerocolor)` defines the RGB color of the elements labeled 0 (zero) in the input label matrix `L`. As the value of `zerocolor`, specify an RGB triple or one of the strings listed in this table.

Value	Color
'b'	Blue

Value	Color
'c'	Cyan
'g'	Green
'k'	Black
'm'	Magenta
'r'	Red
'w'	White
'y'	Yellow

If you do not specify `zerocolor`, the default value for zero-labeled elements is `[1 1 1]` (white).

`RGB = label2rgb(L, map, zerocolor, order)` controls how `label2rgb` assigns colormap colors to regions in the label matrix. If `order` is `'noshuffle'` (the default), `label2rgb` assigns colormap colors to label matrix regions in numerical order. If `order` is `'shuffle'`, `label2rgb` assigns colormap colors pseudorandomly.

“Code Generation” on page 1-1209 support: Yes.

“MATLAB Function Block” on page 1-1210 support: Yes.

Class Support


The input label matrix `L` can have any numeric class. It must contain finite, nonnegative integers. The output of `label2rgb` is of class `uint8`.

Examples

Use Color to Highlight Elements in a Label Matrix

Read an image and display it.

```
I = imread('rice.png');  
figure, imshow(I)
```



Create a label matrix from the image.

```
BW = im2bw(I, graythresh(I));  
CC = bwconncomp(BW);  
L = labelmatrix(CC);
```


Convert the label matrix into RGB image, using default settings.

```
RGB = label2rgb(L);  
figure, imshow(RGB)
```



Convert label matrix into RGB image, specifying optional parameters.

```
RGB2 = label2rgb(L, 'spring', 'c', 'shuffle');  
figure, imshow(RGB2)
```



More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, for best results when using the standard syntax `RGB = label2rgb(L, map, zerocolor, order)`:

- Submit at least two input arguments: the label matrix, `L`, and the colormap matrix, `map`.
- `map` must be an `n-by-3, double`, colormap matrix. You cannot use a string containing the name of a MATLAB colormap function or a function handle of a colormap function.

- If you set the boundary color `zerocolor` to the same color as one of the regions, `label2rgb` will not issue a warning.
- If you supply a value for `order`, it must be `'noshuffle'`.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`bwconncomp` | `bwlabel` | `colormap` | `ismember` | `labelmatrix` | `watershed`

Introduced before R2006a

labelmatrix

Create label matrix from `bwconncomp` structure

Syntax

```
L = labelmatrix(CC)
```

Description

`L = labelmatrix(CC)` creates a label matrix from the connected components structure `CC` returned by `bwconncomp`. The size of `L` is `CC.ImageSize`. The elements of `L` are integer values greater than or equal to 0. The pixels labeled 0 are the background. The pixels labeled 1 make up one object; the pixels labeled 2 make up a second object; and so on. The class of `L` depends on `CC.NumObjects`, as shown in the following table.

Class	Range
'uint8'	$CC.NumObjects \leq 255$
'uint16'	$256 \leq CC.NumObjects \leq 65535$
'uint32'	$65536 \leq CC.NumObjects \leq 2^{32} - 1$
'double'	$CC.NumObjects \geq 2^{32}$

`labelmatrix` is more memory efficient than `bwlabel` and `bwlabeln` because it returns its label matrix in the smallest numeric class necessary for the number of objects.

Class Support

`CC` is a structure returned by `bwconncomp`. The label matrix `L` is `uint8`, `uint16`, `uint32`, or `double`.

Examples

Calculate connected components and display results

Read binary image into the workspace.

```
BW = imread('text.png');
```

Calculate the connected components, using `bwconncomp`.

```
CC = bwconncomp(BW);
```

Create a label matrix, using `labelmatrix`.

```
L = labelmatrix(CC);
```

For comparison, create a second label matrix, using `bwlabel`.

```
L2 = bwlabel(BW);
```

View both label matrices in the workspace. Note that `labelmatrix` is more memory efficient than `bwlabel`, using the smallest numeric class necessary for the number of objects.

```
whos L L2
```

Name	Size	Bytes	Class	Attributes
L	256x256	65536	uint8	
L2	256x256	524288	double	

Display the label matrix as an RGB image, using `label2rgb`.

```
figure  
imshow(label2rgb(L));
```

The term **watershed**
refers to a ridge **that ...**

**... divides areas
drained by different
river systems.**

See Also

`bwconncomp` | `bwlabel` | `bwlabeln` | `label2rgb` | `regionprops`

Introduced in R2009a

images.geotrans.LocalWeightedMeanTransformation2D class

Package: images.geotrans

2-D Local Weighted Mean Geometric Transformation

Description

An `images.geotrans.LocalWeightedMeanTransformation2D` object encapsulates a 2-D local weighted mean geometric transformation.

Construction

`tform = images.geotrans.LocalWeightedMeanTransformation2D(movingPoints, fixedPoints, n)` constructs an `images.geotrans.LocalWeightedMeanTransformation2D` object given m -by-2 matrices `movingPoints` and `fixedPoints`, which define matched control points in the moving and fixed images, respectively. The local weighted mean transformation creates a mapping, by inferring a polynomial at each control point using neighboring control points. The mapping at any location depends on a weighted average of these polynomials. The n closest points are used to infer a second degree polynomial transformation for each control point pair. `n` can be as small as 6, but making it small risks generating ill-conditioned polynomials.

Properties

Dimensionality

Dimensionality of geometric transformation

Describes the dimensionality of the geometric transformation for both input and output points.

Methods

<code>transformPointsInverse</code>	Apply inverse geometric transformation
<code>outputLimits</code>	Find output limits of geometric transformation

Copy Semantics

Value. To learn how value classes affect copy operations, see [Copying Objects in the MATLAB documentation](#).

Examples

Fit set of fixed and moving control points using second degree polynomial

Fit a local weighted mean transformation to a set of fixed and moving control points that are actually related by a global second degree polynomial transformation across the entire plane.

Set up variables.

```
x = [10, 12, 17, 14, 7, 10];
y = [8, 2, 6, 10, 20, 4];
```

```
a = [1 2 3 4 5 6];
b = [2.3 3 4 5 6 7.5];
```

```
u = a(1) + a(2).*x + a(3).*y + a(4) .*x.*y + a(5).*x.^2 + a(6).*y.^2;
v = b(1) + b(2).*x + b(3).*y + b(4) .*x.*y + b(5).*x.^2 + b(6).*y.^2;
```

```
movingPoints = [u',v'];
fixedPoints = [x',y'];
```

Fit local weighted mean transformation to points.

```
tformLocalWeightedMean = images.geotrans.LocalWeightedMeanTransformation2D(movingPoints, fixedPoints);
```

Verify the fit of our `LocalWeightedMeanTransformation2D` object at the control points.

```
movingPointsComputed = transformPointsInverse(tformLocalWeightedMean, fixedPoints);  
errorInFit = hypot(movingPointsComputed(:,1)-movingPoints(:,1), ...  
                  movingPointsComputed(:,2)-movingPoints(:,2))
```

See Also

[affine2d](#) | [fitgeotrans](#) | [imwarp](#)

images.geotrans.LocalWeightedMeanTransformation2d.trans

Apply inverse geometric transformation

Syntax

```
[u,v] = transformPointsInverse(tform,x,y)  
U = transformPointsInverse(tform,X)
```

Description

`[u,v] = transformPointsInverse(tform,x,y)` applies the inverse transformation of `tform` to the input 2-D point arrays `x` and `y` and outputs the point arrays `u` and `v`. The input point arrays `x` and `y` must be of the same size.

`U = transformPointsInverse(tform,X)` applies the inverse transformation of `tform` to the input n -by-2 point matrix `X` and outputs the n -by-2 point matrix `U`. `transformPointsFoward` maps the point `X(k, :)` to the point `U(k, :)`.

Input Arguments

tform

Geometric transformation, specified as a `images.geotrans.LocalWeightedMeanTransformation2D` object.

x

Coordinates in X dimension of points to be transformed, specified as a array.

y

Coordinates in Y dimension of points to be transformed, specified as a array.

X

X and Y coordinates of points to be transformed, specified as an n -by-2 matrix

Output Arguments

u

Transformed coordinates in X dimension, returned as an array.

v

Transformed coordinates in Y dimension, returned as an array.

U

Transformed X and Y coordinates, returned as an n -by-2 matrix

images.geotrans.LocalWeightedMeanTransformation2d.outp

Find output limits of geometric transformation

Syntax

```
[xLimitsOut,yLimitsOut] = outputLimits(tform,xLimitsIn,yLimitsIn)
[xLimitsOut,yLimitsOut,zLimitsOut] =
outputLimits(tform,xLimitsIn,yLimitsIn,zLimitsIn)
```

Description

`[xLimitsOut,yLimitsOut] = outputLimits(tform,xLimitsIn,yLimitsIn)` estimates the output spatial limits corresponding to a given 2D geometric transformation and a set of input spatial limits.

`[xLimitsOut,yLimitsOut,zLimitsOut] = outputLimits(tform,xLimitsIn,yLimitsIn,zLimitsIn)` estimates the output spatial limits corresponding to a given 3D geometric transformation and a set of input spatial limits.

Input Arguments

tform

Geometric transformation, specified as an `images.geotrans.LocalWeightedMeanTransformation2D` object.

xLimitsIn

Limits along the *X* axes, specified as a two-element vector, such as `[]`.

yLimitsIn

Limits along the *Y* axes, specified as a two-element vector, such as `[]`.

zLimitsIn

Limits along the Z axes, specified as a two-element vector, such as [].

Output Arguments

xLimitsOut

Actual limits along the X dimension, returned as an array.

yLimitsOut

Actual limits along the Y dimension, returned as an array.

zLimitsOut

Actual limits along the Z dimension, returned as an array.

makeform

Create color transformation structure

Syntax

```

C = makeform(type)
C = makeform(type, 'WhitePoint', WP)
C = makeform(type, 'AdaptedWhitePoint', WP)
C = makeform('srgb2cmyk', 'RenderingIntent', intent)
C = makeform('cmyk2srgb', 'RenderingIntent', intent)
C = makeform('adapt', 'WhiteStart', WPS, 'WhiteEnd', WPE,
'AdaptModel', modelName)
C = makeform('icc', src_profile, dest_profile)
C = makeform('icc', src_profile, dest_profile,
'SourceRenderingIntent', src_intent, 'DestRenderingIntent',
dest_intent)
C = makeform('clut', profile, LUTtype)
C = makeform('mattrc', MatTrc, 'Direction', direction)
C = makeform('mattrc', profile, 'Direction', direction)
C = makeform('mattrc', profile, 'Direction', direction,
'RenderingIntent', intent)
C = makeform('graytrc', profile, 'Direction', direction)
C = makeform('graytrc', profile, 'Direction', direction,
'RenderingIntent', intent)
C = makeform('named', profile, space)

```

Description

`C = makeform(type)` creates the color transformation structure `C` that defines the color space conversion specified by *type*. To perform the transformation, pass the color transformation structure as an argument to the `applycform` function.

The *type* argument specifies one of the conversions listed in the following table. `makeform` supports conversions between members of the family of device-independent color spaces defined by the CIE, *Commission Internationale de l'Éclairage* (International Commission on Illumination). In addition, `makeform` also supports conversions to

and from the *sRGB* and *CMYK* color spaces. For a list of the abbreviations used by the Image Processing Toolbox software for each color space, see the Remarks section of this reference page.

Type	Description
'cmyk2srgb'	Convert from the <i>CMYK</i> color space to the <i>sRGB</i> color space.
'lab2lch'	Convert from the $L^*a^*b^*$ to the L^*ch color space.
'lab2srgb'	Use <code>lab2rgb</code> instead.
'lab2xyz'	Use <code>lab2xyz</code> instead.
'lch2lab'	Convert from the L^*ch to the $L^*a^*b^*$ color space.
'srgb2cmyk'	Convert from the <i>sRGB</i> to the <i>CMYK</i> color space.
'srgb2lab'	Use <code>rgb2lab</code> instead.
'srgb2xyz'	Use <code>rgb2xyz</code> instead.
'upvp12xyz'	Convert from the u^*v^*L to the <i>XYZ</i> color space.
'uvl2xyz'	Convert from the uvL to the <i>XYZ</i> color space.
'xyz12xyz'	Convert from the xyY to the <i>XYZ</i> color space.
'xyz2lab'	Use <code>xyz2lab</code> instead.
'xyz2srgb'	Use <code>xyz2rgb</code> instead.
'xyz2upvp1'	Convert from the <i>XYZ</i> to the u^*v^*L color space.
'xyz2uvl'	Convert from the <i>XYZ</i> to the uvL color space.
'xyz2xy1'	Convert from the <i>XYZ</i> to the xyY color space.

`C = makecform(type, 'WhitePoint', WP)` specifies the value of the reference white point. *type* can be either 'xyz2lab' or 'lab2xyz'. *WP* is a 1-by-3 vector of *XYZ* values scaled so that $Y = 1$. The default is `whitepoint('ICC')`. Use the `whitepoint` function to create the *WP* vector.

`C = makecform(type, 'AdaptedWhitePoint', WP)` specifies the adapted white point. *type* can be either 'srgb2lab', 'lab2srgb', 'srgb2xyz', or 'xyz2srgb'. As above, *WP* is a row vector of *XYZ* values scaled so that $Y = 1$. If not specified, the default adapted white point is `whitepoint('ICC')`. To get answers consistent with some published *sRGB* equations, specify `whitepoint('D65')` for the adapted white point.

`C = makecform('srgb2cmyk', 'RenderingIntent', intent)` and

`C = makecform('cmyk2srgb', 'RenderingIntent', intent)` specify the rendering intent for transforms of type `srgb2cmyk` and `cmyk2srgb`. These transforms convert data between *sRGB* IEC61966-2.1 and "Specifications for Web Offset Publications" (SWOP) *CMYK*. *intent* must be one of these strings: 'AbsoluteColorimetric', 'Perceptual', 'RelativeColorimetric', or 'Saturation'. For more information, see the table Rendering Intent.

`C = makecform('adapt', 'WhiteStart', WPS, 'WhiteEnd', WPE, 'AdaptModel', modelName)` creates a linear chromatic-adaptation transform. WPS and WPE are row vectors of XYZ values, scaled so that $Y = 1$, specifying the starting and ending white points. *modelName* is either 'vonKries' or 'Bradford' and specifies the type of chromatic-adaptation model to be employed. If 'AdaptModel' is not specified, it defaults to 'Bradford'.

`C = makecform('icc', src_profile, dest_profile)` creates a color transform based on two ICC profiles. `src_profile` and `dest_profile` are ICC profile structures returned by `iccread`.

`C = makecform('icc', src_profile, dest_profile, 'SourceRenderingIntent', src_intent, 'DestRenderingIntent', dest_intent)` creates a color transform based on two ICC color profiles, `src_profile` and `dest_profile`, specifying rendering intent arguments for the source, *src_intent*, and the destination, *dest_intent*, profiles.

Rendering intents specify the style of reproduction that should be used when these profiles are combined. For most devices, the range of reproducible colors is much smaller than the range of colors represented by the PCS. Rendering intents define gamut mapping techniques. Possible values for these rendering intents are listed below. Each rendering intent has distinct aesthetic and color-accuracy trade-offs.

Rendering Intent

Value	Description
'AbsoluteColorimetric'	Maps all out-of-gamut colors to the nearest gamut surface while maintaining the relationship of all in-gamut colors. This absolute rendering contains color data that is relative to a perfectly reflecting diffuser.
'Perceptual' (default)	Employs vendor-specific gamut mapping techniques for optimizing the range of producible colors of a given device. The objective is to provide the most aesthetically pleasing result even though the relationship of the in-gamut colors

Value	Description
	might not be maintained. This media-relative rendering contains color data that is relative to the device's white point.
'RelativeColorimetric'	Maps all out-of-gamut colors to the nearest gamut surface while maintaining the relationship of all in-gamut colors. This media-relative rendering contains color data that is relative to the device's white point.
'Saturation'	Employs vendor-specific gamut mapping techniques for maximizing the saturation of device colors. This rendering is generally used for simple business graphics such as bar graphs and pie charts. This media-relative rendering contains color data that is relative to the device's white point.

`C = makecform('clut', profile, LUTtype)` creates the color transformation structure `C` based on a color lookup table (CLUT) contained in an ICC color profile. `profile` is an ICC profile structure returned by `iccread`. `LUTtype` specifies which `clut` in the `profile` structure is to be used. Each `LUTtype` listed in the table below contains the components of an 8-bit or 16-bit LUTtag that performs a transformation between device colors and PCS colors using a particular rendering. For more information about 'clut' transformations, see Section 6.5.7 of the International Color Consortium specification ICC.1:2001-04 (Version 2) or Section 6.5.9 of ICC.1:2001-12 (Version 4), available at www.color.org.

LUT Type	Description
'AToB0' (default)	Device to PCS: perceptual rendering intent
'AToB1'	Device to PCS: media-relative colorimetric rendering intent
'AToB2'	Device to PCS: saturation rendering intent
'AToB3'	Device to PCS: ICC-absolute rendering intent
'BToA0'	PCS to device: perceptual rendering intent
'BToA1'	PCS to device: media-relative colorimetric rendering intent
'BToA2'	PCS to device: saturation rendering intent
'BToA3'	PCS to device: ICC-absolute rendering intent
'Gamut'	Determines which PCS colors are out of gamut for a given device

LUT Type	Description
'Preview0'	PCS colors to the PCS colors available for soft proofing using the perceptual rendering
'Preview1'	PCS colors available for soft proofing using the media-relative colorimetric rendering.
'Preview2'	PCS colors to the PCS colors available for soft proofing using the saturation rendering.

`C = makecform('mattrc', MatTrc, 'Direction', direction)` creates the color transformation structure `C` based on a Matrix/Tone Reproduction Curve (MatTRC) model, containing an *RGB*-to-*XYZ* matrix and *RGB* Tone Reproduction Curves. `MatTRC` is typically the 'MatTRC' field of an ICC profile structure returned by `iccread`, based on tags contained in an ICC color profile. `direction` can be either 'forward' or 'inverse' and specifies whether the `MatTRC` is to be applied in the forward (*RGB* to *XYZ*) or inverse (*XYZ* to *RGB*) direction. For more information, see section 6.3.1.2 of the International Color Consortium specification ICC.1:2001-04 or ICC.1:2001-12, available at www.color.org.

`C = makecform('mattrc', profile, 'Direction', direction)` creates a color transform based on the `MatTRC` field of the given ICC profile structure `profile`. `direction` is either 'forward' or 'inverse' and specifies whether the `MatTRC` is applied in the forward (*RGB* to *XYZ*) or inverse (*XYZ* to *RGB*) direction.

`C = makecform('mattrc', profile, 'Direction', direction, 'RenderingIntent', intent)` is similar, but adds the option of specifying the rendering intent. `intent` must be either 'RelativeColorimetric' (the default) or 'AbsoluteColorimetric'. When 'AbsoluteColorimetric' is specified, the colorimetry is referenced to a perfect diffuser, rather than to the Media White Point of the profile.

`C = makecform('graytrc', profile, 'Direction', direction)` creates the color transformation structure `C` that specifies a monochrome transform based on a single-channel Tone Reproduction Curve (GrayTRC) contained in an ICC color profile. `direction` can be either 'forward' or 'inverse' and specifies whether the `grayTRC` transform is to be applied in the forward (device to PCS) or inverse (PCS to device) direction. ("Device" here refers to the grayscale signal communicating with the monochrome device. "PCS" is the Profile Connection Space of the ICC profile and can be either *XYZ* or *L*a*b**, depending on the 'ConnectionSpace' field in `profile.Header`.)

`C = makecform('graytrc', profile, 'Direction', direction, 'RenderingIntent', intent)` is similar but adds the option of specifying the rendering intent. *intent* must be either 'RelativeColorimetric' (the default) or 'AbsoluteColorimetric'. When 'AbsoluteColorimetric' is specified, the colorimetry is referenced to a perfect diffuser, rather than to the Media White Point of the profile.

`C = makecform('named', profile, space)` creates the color transformation structure `C` that specifies the transformation from color names to color-space coordinates. *profile* must be a profile structure for a Named Color profile (with a `NamedColor2` field). *space* is either 'PCS' or 'Device'. The 'PCS' option is always available and will return $L^*a^*b^*$ or XYZ coordinates, depending on the 'ConnectionSpace' field in `profile.Header`, in 'double' format. The 'Device' option, when active, returns device coordinates, the dimension depending on the 'ColorSpace' field in `profile.Header`, also in 'double' format.

Examples

Convert RGB image to $L^*a^*b^*$, assuming input image is *sRGB*.

```
rgb = imread('peppers.png');
cform = makecform('srgb2lab');
lab = applycform(rgb,cform);
```

Convert from a non-standard RGB color profile to the device-independent XYZ profile connection space. Note that the ICC input profile must include a MatTRC value.

```
InputProfile = iccread('myRGB.icc');
C = makecform('mattc',InputProfile.MatTRC, ...
             'direction', 'forward');
```

More About

Tips

The Image Processing Toolbox software uses the following abbreviations to represent color spaces.

Abbreviation	Description
xyz	1931 CIE XYZ tristimulus values (2° observer)

Abbreviation	Description
xy1	1931 CIE xyY chromaticity values (2° observer), where x and y refer to the xy -coordinates of the associated CIE chromaticity diagram, and 1 refers to Y (luminance).
uv1	1960 CIE uvY values, where u and v refer to the uv -coordinates, and 1 refers to Y (luminance).
upvp1	1976 CIE $u'v'Y$ values, where up and vp refer to the $u'v'$ -coordinates and 1 refers to Y (luminance).
lab	1976 CIE $L^*a^*b^*$ values Note: 1 or L refers to L^* (CIE 1976 psychometric lightness) rather than luminance (Y).
lch	Polar transformation of CIE $L^*a^*b^*$ values, where c = chroma and h = hue
cmyk	Standard values used by printers
srgb	Standard computer monitor RGB values, (IEC 61966-2-1)

See Also

lab2rgb | lab2xyz | rgb2lab | rgb2xyz | xyz2lab | xyz2rgb | applycform
 | iccread | iccwrite | isicc | lab2double | lab2uint8 | lab2uint16 |
 whitepoint | xyz2double | xyz2uint16

Introduced before R2006a

makeConstrainToRectFcn

Create rectangularly bounded drag constraint function

Syntax

```
fcn = makeConstrainToRectFcn(type, xlim, ylim)
```

Description

`fcn = makeConstrainToRectFcn(type, xlim, ylim)` creates a position constraint function for draggable tools of a given type, where `type` is one of the following strings: 'imellipse', 'imfreehand', 'imline', 'impoint', 'impoly', or 'imrect'. The rectangular boundaries of the position constraint function are described by the vectors `xlim` and `ylim` where `xlim = [xmin xmax]` and `ylim = [ymin ymax]`.

Examples

Constrain drag of `impoint` within axes limits.

```
figure, plot(1:10);  
h = impoint(gca,2,6);  
api = iptgetapi(h);  
fcn = makeConstrainToRectFcn('impoint',get(gca,'XLim'),...  
    get(gca,'YLim'));  
api.setPositionConstraintFcn(fcn);
```

See Also

`imdistline` | `imellipse` | `imfreehand` | `imline` | `impoint` | `impoly` | `imrect`

Introduced in R2006a

makehdr

Create high dynamic range image

Syntax

```
HDR = makehdr(files)
HDR = makehdr(files, param1, val1, ...)
```

Description

`HDR = makehdr(files)` creates the single-precision, high dynamic range image from the set of spatially registered low dynamic range images listed in the `files` cell array. `makehdr` uses the middle exposure between the brightest and darkest images as the base exposure for the high dynamic range calculations. (This value does not need to appear in any particular file. For more information about calculating this middle exposure value, see “Algorithm” on page 1-1231.)

Note: When you call `makehdr` with this syntax, the low dynamic range image files must contain `exif` exposure metadata.

`HDR = makehdr(files, param1, val1, ...)` creates a high dynamic range image from the low dynamic range images in `files`, specifying parameters and corresponding values that control various aspects of the image creation. Parameter names can be abbreviated and case does not matter.

Note: Only one of the `BaseFile`, `ExposureValues`, and `RelativeExposure` parameters may be used at a time.

Parameter	Description
'BaseFile'	Character array containing the name of the file to use as the base exposure.

Parameter	Description
'ExposureValues'	Vector of exposure values, with one element for each low dynamic range image in the cell array <code>files</code> . An increase in one exposure value (EV) corresponds to a doubling of exposure, while a decrease in one EV corresponds to a halving of exposure. Any positive value is allowed. This parameter overrides EXIF exposure metadata.
'RelativeExposure'	Vector of relative exposure values, with one element for each low dynamic range image in the cell array <code>files</code> . An image with a relative exposure (RE) of 0.5 has half as much exposure as an image with an RE of 1. An RE value of 3 has three times the exposure of an image with an RE of 1. This parameter overrides EXIF exposure metadata.
'MinimumLimit'	Numeric scalar value in the range [0 255] that specifies the minimum correctly exposed value. For each low dynamic range image, pixels with smaller values are considered underexposed and will not contribute to the final high dynamic range image.
'MaximumLimit'	Numeric scalar value in the range [0 255] that specifies the maximum correctly exposed value. For each low dynamic range image, pixels with larger values are considered overexposed and will not contribute to the final high dynamic range image.

Examples

Make a high dynamic range image from a series of six low dynamic range images that share the same *f*/stop number and have different exposure times. Use `tonemap` to visualize the HDR image.

```
files = {'office_1.jpg', 'office_2.jpg', 'office_3.jpg', ...
        'office_4.jpg', 'office_5.jpg', 'office_6.jpg'};
expTimes = [0.0333, 0.1000, 0.3333, 0.6250, 1.3000, 4.0000];

hdr = makehdr(files, 'RelativeExposure', expTimes ./ expTimes(1));
rgb = tonemap(hdr);
figure; imshow(rgb)
```

More About

Algorithms

The `makehdr` function calculates the middle exposure by computing the exposure values (EV) for each image, based on the aperture and shutter speed metadata stored in the files or specified using the `'Exposurevalues'` parameter. The EV of a middle image (hypothetical or actual) is used as the base exposure. Thus, the middle exposure is an average of the highest and lowest EV, not of actual brightness (because of the nonlinear, geometric nature of EV).

References

[1] Reinhard, et al. "High Dynamic Range Imaging." 2006. Ch. 4.

See Also

`hdrread` | `tonemap`

Introduced in R2008a

makelut

Create lookup table for use with `bwlookup`

Syntax

```
lut = makelut(fun,n)
```

Description

`lut = makelut(fun,n)` returns a lookup table for use with `bwlookup`. `fun` is a function that accepts an n -by- n matrix of 1's and 0's as input and return a scalar. `n` can be either 2 or 3. `makelut` creates `lut` by passing all possible 2-by-2 or 3-by-3 neighborhoods to `fun`, one at a time, and constructing either a 16-element vector (for 2-by-2 neighborhoods) or a 512-element vector (for 3-by-3 neighborhoods). The vector consists of the output from `fun` for each possible neighborhood. `fun` must be a function handle. Parameterizing Functions, in the MATLAB Mathematics documentation, explains how to provide additional parameters to the function `fun`.

Class Support

`lut` is returned as a vector of class `double`.

Examples

Construct a lookup table for 2-by-2 neighborhoods. In this example, the function passed to `makelut` returns `TRUE` if the number of 1's in the neighborhood is 2 or greater, and returns `FALSE` otherwise.

```
f = @(x) (sum(x(:)) >= 2);  
lut = makelut(f,2)  
lut =  
    0  
    0  
    0
```

1
0
1
1
1
0
1
1
1
1
1
1
1
1

More About

- “Anonymous Functions”
- “Parameterizing Functions”

See Also

`bwlookup`

Introduced before R2006a

makeresampler

Create resampling structure

Syntax

```
R = makeresampler(interpolant, padmethod)
```

Description

`R = makeresampler(interpolant, padmethod)` creates a separable resampler structure for use with `tformarray` and `imtransform`.

The `interpolant` argument specifies the interpolating kernel that the separable resampler uses. In its simplest form, `interpolant` can have any of the following strings as a value.

Interpolant	Description
'cubic'	Cubic interpolation
'linear'	Linear interpolation
'nearest'	Nearest-neighbor interpolation

If you are using a custom interpolating kernel, you can specify `interpolant` as a cell array in either of these forms:

{half_width, positive_half}	<code>half_width</code> is a positive scalar designating the half width of a symmetric interpolating kernel. <code>positive_half</code> is a vector of values regularly sampling the kernel on the closed interval <code>[0 positive_half]</code> .
{half_width, interp_fcn}	<code>interp_fcn</code> is a function handle that returns interpolating kernel values, given an array of input values in the interval <code>[0 positive_half]</code> .

To specify the interpolation method independently along each dimension, you can combine both types of `interpolant` specifications. The number of elements in the cell array

must equal the number of transform dimensions. For example, if you specify this value for `interpolant`

```
{'nearest', 'linear', {2 KERNEL_TABLE}}
```

the resampler uses nearest-neighbor interpolation along the first transform dimension, linear interpolation along the second dimension, and a custom table-based interpolation along the third.

The `padmethod` argument controls how the resampler interpolates or assigns values to output elements that map close to or outside the edge of the input array. The following table lists all the possible values of `padmethod`.

Pad Method	Description
'bound'	Assigns values from the fill value array to points that map outside the array and repeats border elements of the array for points that map inside the array (same as 'replicate'). When <code>interpolant</code> is 'nearest', this pad method produces the same results as 'fill'. 'bound' is like 'fill', but avoids mixing fill values and input image values.
'circular'	Pads array with circular repetition of elements within the dimension. Same as <code>padarray</code> .
'fill'	Generates an output array with smooth-looking edges (except when using nearest-neighbor interpolation). For output points that map near the edge of the input array (either inside or outside), it combines input image and fill values. When <code>interpolant</code> is 'nearest', this pad method produces the same results as 'bound'.
'replicate'	Pads array by repeating border elements of array. Same as <code>padarray</code> .
'symmetric'	Pads array with mirror reflections of itself. Same as <code>padarray</code> .

In the case of 'fill', 'replicate', 'circular', or 'symmetric', the resampling performed by `tformarray` or `imtransform` occurs in two logical steps:

- 1 Pad the array `A` infinitely to fill the entire input transform space.
- 2 Evaluate the convolution of the padded `A` with the resampling kernel at the output points specified by the geometric map.

Each nontransform dimension is handled separately. The padding is virtual, (accomplished by remapping array subscripts) for performance and memory efficiency. If you implement a custom resampler, you can implement these behaviors.

Custom Resamplers

The syntaxes described above construct a resampler structure that uses the separable resampler function that ships with the Image Processing Toolbox software. It is also possible to create a resampler structure that uses a user-written resampler by using this syntax:

```
R = makesampler(PropertyName,PropertyValue,...)
```

The makesampler function supports the following properties.

Property	Description
'Type'	Can have the value 'separable' or 'custom' and must always be supplied. If 'Type' is 'separable', the only other properties that can be specified are 'Interpolant' and 'PadMethod', and the result is equivalent to using the makesampler(interpolant,padmethod) syntax. If 'Type' is 'custom', you must specify the 'NDims' and 'ResampleFcn' properties and, optionally, the 'CustomData' property.
'PadMethod'	See the padmethod argument for more information.
'Interpolant'	See the interpolant argument for more information.
'NDims'	Positive integer indicating the dimensionality the custom resampler can handle. Use a value of Inf to indicate that the custom resampler can handle any dimension. If 'Type' is 'custom', NDims is required.
'ResampleFcn'	Handle to a function that performs the resampling. The function is called with the following interface. $B = \text{resample_fcn}(A,M,TDIMS_A,TDIMS_B,FSIZE_A,FSIZE_B,F,R)$ <p>See the help for tformarray for information about the inputs A, TDIMS_A, TDIMS_B, and F. The argument M is an array that maps the transform subscript space of B to the transform subscript space of A. If A has N transform dimensions ($N = \text{length}(TDIMS_A)$) and B has P transform dimensions ($P = \text{length}(TDIMS_B)$), then $\text{ndims}(M) = P + 1$, if $N > 1$ and P if $N == 1$, and $\text{size}(M,P + 1) = N$.</p>

Property	Description
	The first P dimensions of M correspond to the output transform space, permuted according to the order in which the output transform dimensions are listed in <code>TDIMS_B</code> . (In general <code>TDIMS_A</code> and <code>TDIMS_B</code> need not be sorted in ascending order, although such a limitation might be imposed by specific resamplers.) Thus, the first P elements of <code>size(M)</code> determine the sizes of the transform dimensions of B . The input transform coordinates to which each point is mapped are arrayed across the final dimension of M , following the order given in <code>TDIMS_A</code> . M must be <code>double</code> . <code>FSIZE_A</code> and <code>FSIZE_B</code> are the full sizes of A and B , padded with 1's as necessary to be consistent with <code>TDIMS_A</code> , <code>TDIMS_B</code> , and <code>size(A)</code> .
'CustomData'	User-defined.

Examples

Stretch an image in the y -direction using a separable resampler that applies cubic interpolation in the y -direction and nearest-neighbor interpolation in the x -direction. (This is equivalent to, but faster than, applying bicubic interpolation.)

```
A = imread('moon.tif');
resamp = makesampler({'nearest','cubic'},'fill');
stretch = maketform('affine',[1 0; 0 1.3; 0 0]);
B = imtransform(A,stretch,resamp);
```

See Also

`imtransform` | `tformarray`

Introduced before R2006a

maketform

Create spatial transformation structure (TFORM)

Compatibility

`maketform` is not recommended. Use `fitgeotrans`, `affine2d`, `affine3d`, or `projective2d` instead.

Syntax

```
T = maketform(transformtype, ...)
T = maketform('affine',A)
T = maketform('affine',U,X)
T = maketform('projective',A)
T = maketform('projective',U,X)
T = maketform('custom', NDIMS_IN, NDIMS_OUT, FORWARD_FCN,
INVERSE_FCN, TDATA)
T = maketform('box',tsize,LOW,HIGH)
T = maketform('box',INBOUNDS, OUTBOUNDS)
T = maketform('composite',T1,T2,...,TL)
T = maketform('composite', [T1 T2 ... TL])
```

Description

`T = maketform(transformtype, ...)` creates a multidimensional spatial transformation structure (called a TFORM struct) that can be used with the `tformfwd`, `tforminv`, `fliptform`, `imtransform`, or `tformarray` functions.

`transformtype` can be any of the following spatial transformation types. `maketform` supports a special syntax for each transformation type. See the following sections for information about these syntax.

Transform Type	Description
'affine'	Affine transformation in 2-D or N-D

Transform Type	Description
'projective'	Projective transformation in 2-D or N-D
'custom'	User-defined transformation that can be N-D to M-D
'box'	Independent affine transformation (scale and shift) in each dimension
'composite'	Composition of an arbitrary number of more basic transformations

Transform Types

Affine

`T = maketform('affine',A)` builds a TFORM struct `T` for an `N`-dimensional affine transformation. `A` is a nonsingular real $(N+1)$ -by- $(N+1)$ or $(N+1)$ -by- N matrix. If `A` is $(N+1)$ -by- $(N+1)$, the last column of `A` must be `[zeros(N,1);1]`. Otherwise, `A` is augmented automatically, such that its last column is `[zeros(N,1);1]`. The matrix `A` defines a forward transformation such that `tformfwd(U,T)`, where `U` is a 1-by-`N` vector, returns a 1-by-`N` vector `X`, such that $X = U * A(1:N,1:N) + A(N+1,1:N)$. `T` has both forward and inverse transformations.

`T = maketform('affine',U,X)` builds a TFORM struct `T` for a two-dimensional affine transformation that maps each row of `U` to the corresponding row of `X`. The `U` and `X` arguments are each 3-by-2 and define the corners of input and output triangles. The corners cannot be collinear.

Projective

`T = maketform('projective',A)` builds a TFORM struct for an `N`-dimensional projective transformation. `A` is a nonsingular real $(N+1)$ -by- $(N+1)$ matrix. $A(N+1,N+1)$ cannot be 0. The matrix `A` defines a forward transformation such that `tformfwd(U,T)`, where `U` is a 1-by-`N` vector, returns a 1-by-`N` vector `X`, such that $X = W(1:N)/W(N+1)$, where $W = [U \ 1] * A$. The transformation structure `T` has both forward and inverse transformations.

`T = maketform('projective',U,X)` builds a TFORM struct `T` for a two-dimensional projective transformation that maps each row of `U` to the corresponding row of `X`. The `U` and `X` arguments are each 4-by-2 and define the corners of input and output quadrilaterals. No three corners can be collinear.

Note: An affine or projective transformation can also be expressed like this, for a 3-by-2 A:

$$[X \ Y]' = A' * [U \ V \ 1]'$$

Or, like this, for a 3-by-3 A:

$$[X \ Y \ 1]' = A' * [U \ V \ 1]'$$

Custom

`T = maketform('custom', NDIMS_IN, NDIMS_OUT, FORWARD_FCN, INVERSE_FCN, TDATA)` builds a custom TFORM struct `T` based on user-provided function handles and parameters. `NDIMS_IN` and `NDIMS_OUT` are the numbers of input and output dimensions. `FORWARD_FCN` and `INVERSE_FCN` are function handles to forward and inverse functions. Those functions must support the following syntax:

Forward function: $X = \text{FORWARD_FCN}(U, T)$

Inverse function: $U = \text{INVERSE_FCN}(X, T)$

where `U` is a `P`-by-`NDIMS_IN` matrix whose rows are points in the transformation's input space, and `X` is a `P`-by-`NDIMS_OUT` matrix whose rows are points in the transformation's output space. The `TDATA` argument can be any MATLAB array and is typically used to store parameters of the custom transformation. It is accessible to `FORWARD_FCN` and `INVERSE_FCN` via the `tdata` field of `T`. Either `FORWARD_FCN` or `INVERSE_FCN` can be empty, although at least `INVERSE_FCN` must be defined to use `T` with `tformarray` or `imtransform`.

Box

`T = maketform('box', tsize, LOW, HIGH)` or

`T = maketform('box', INBOUNDS, OUTBOUNDS)` builds an `N`-dimensional affine TFORM struct `T`. The `tsize` argument is an `N`-element vector of positive integers. `LOW` and `HIGH` are also `N`-element vectors. The transformation maps an input box defined by the opposite corners `ones(1, N)` and `tsize` or, alternatively, by corners `INBOUNDS(1, :)` and `INBOUND(2, :)` to an output box defined by the opposite corners `LOW` and `HIGH` or `OUTBOUNDS(1, :)` and `OUTBOUNDS(2, :)`. `LOW(K)` and `HIGH(K)` must be different unless `tsize(K)` is 1, in which case the affine scale factor along the `K`th dimension is assumed to be 1.0. Similarly, `INBOUNDS(1, K)` and `INBOUNDS(2, K)` must

be different unless `OUTBOUNDS(1,K)` and `OUTBOUNDS(2,K)` are the same, and vice versa. The 'box' TFORM is typically used to register the row and column subscripts of an image or array to some world coordinate system.

Composite

`T = maketform('composite',T1,T2,...,TL)` or
`T = maketform('composite', [T1 T2 ... TL])` builds a TFORM struct `T` whose forward and inverse functions are the functional compositions of the forward and inverse functions of `T1`, `T2`, ..., `TL`.

Note that the inputs `T1`, `T2`, ..., `TL` are ordered just as they would be when using the standard notation for function composition: $T = T1 \circ T2 \circ \dots \circ TL$ and note also that composition is associative, but not commutative. This means that in order to apply `T` to the input `U`, one must apply `TL` first and `T1` last. Thus if `L = 3`, for example, then `tformfwd(U,T)` is the same as `tformfwd(tformfwd(tformfwd(U,T3),T2),T1)`. The components `T1` through `TL` must be compatible in terms of the numbers of input and output dimensions. `T` has a defined forward transform function only if all the component transforms have defined forward transform functions. `T` has a defined inverse transform function only if all the component functions have defined inverse transform functions.

Examples

Make and apply an affine transformation.

```
T = maketform('affine',[.5 0 0; .5 2 0; 0 0 1]);
tformfwd([10 20],T)
I = imread('cameraman.tif');
I2 = imtransform(I,T);
imshow(I), figure, imshow(I2)
```

See Also

`tformfwd` | `tforminv` | `fliptform` | `imtransform` | `tformarray`

Introduced before R2006a

mat2gray

Convert matrix to grayscale image

Syntax

```
I = mat2gray(A, [amin amax])  
I = mat2gray(A)  
gpuarrayI = mat2gray(gpuarrayA, ___ )
```

Description

`I = mat2gray(A, [amin amax])` converts the matrix `A` to the intensity image `I`. The returned matrix `I` contains values in the range 0.0 (black) to 1.0 (full intensity or white). `amin` and `amax` are the values in `A` that correspond to 0.0 and 1.0 in `I`. Values less than `amin` become 0.0, and values greater than `amax` become 1.0.

`I = mat2gray(A)` sets the values of `amin` and `amax` to the minimum and maximum values in `A`.

`gpuarrayI = mat2gray(gpuarrayA, ___)` performs the operation on a GPU. This syntax requires the Parallel Computing Toolbox.

Class Support

The input array `A` can be `logical` or numeric. The output image `I` is `double`.

The input gpuArray `gpuarrayA` can be `logical` or numeric. The output gpuArray image `gpuarrayI` is `double`.

Examples

Convert a Matrix into an Image

Read an image and, for this example, turn it into a numeric matrix.



```
I = imread('rice.png');  
J = filter2(fspecial('sobel'),I);
```


Convert the matrix into an image.

```
K = mat2gray(J);
```

Display the original image and the result of the conversion.

```
imshow(I), figure, imshow(K)
```





See Also

`gray2ind` | `ind2gray` | `rgb2gray` | `gpuArray`

Introduced before R2006a

mean2

Average or mean of matrix elements

Syntax

```
B = mean2(A)
gpuarrayB = mean2(gpuarrayA)
```

Description

`B = mean2(A)` computes the mean of the values in `A`.

`gpuarrayB = mean2(gpuarrayA)` computes the mean of the values in `gpuarrayA`, performing the operation on a GPU. This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-1246 support: Yes.

“MATLAB Function Block” on page 1-1246 support: Yes.

Class Support

The input image `A` can be `numeric` or `logical`. The output image `B` is a scalar of class `double`.

The input image `gpuarrayA` is a `gpuArray` whose underlying class is `numeric` or `logical`. The output image `gpuarrayB` is a `gpuArray` scalar with the underlying class `double`.

Examples

Compute Mean of an Image

Read an image into the workspace.

```
I = imread('liftingbody.png');
```

Compute the mean.

```
meanval = mean2(I)
```

```
meanval =
```

```
140.2991
```

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

Algorithms

`mean2` computes the mean of an array `A` using `mean(A(:))`.

See Also

`std2` | `mean` | `std`

Introduced before R2006a

medfilt2

2-D median filtering

Syntax

```
B = medfilt2(A)
B = medfilt2(A, [m n])
B = medfilt2( ____,padopt)
gpuarrayB = medfilt2(gpuarrayA, ____)
```

Description

`B = medfilt2(A)` performs median filtering of the matrix `A` in two dimensions. Each output pixel contains the median value in a 3-by-3 neighborhood around the corresponding pixel in the input image. `medfilt2` pads the image with 0's on the edges, so the median values for points within one-half the width of the neighborhood ($[m\ n]/2$) of the edges might appear distorted.

`B = medfilt2(A, [m n])` performs median filtering, where each output pixel contains the median value in the `m`-by-`n` neighborhood around the corresponding pixel in the input image.

`B = medfilt2(____,padopt)` controls how `medfilt2` pads the matrix boundaries.

`gpuarrayB = medfilt2(gpuarrayA, ____)` performs the median filtering operation on a GPU. The input image and the output image are `gpuArrays`. When working with `gpuArrays`, `medfilt2` only supports square neighborhoods with odd-length sides between 3 and 15. This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-1251 support: Yes.

“MATLAB Function Block” on page 1-1251 support: Yes.

Examples

Remove Salt and Pepper Noise from Image

Read image into workspace and display it.

```
I = imread('eight.tif');  
figure, imshow(I)
```



Add salt and pepper noise.

```
J = imnoise(I,'salt & pepper',0.02);
```

Use a median filter to filter out the noise.

```
K = medfilt2(J);
```

Display results, side-by-side.

```
imshowpair(J,K,'montage')
```



Remove Salt and Pepper Noise from Image Using a GPU

Read the image into a gpuArray.

```
I = gpuArray(imread('eight.tif'));
```

Read the image into a gpuArray.

```
J = imnoise(I,'salt & pepper',0.02);  
K = medfilt2(J);  
figure, imshow(J), figure, imshow(K)
```

Input Arguments

A — Input matrix

2-D, real, nonsparse, numeric or logical matrix

Input matrix, specified as a 2-D, real, nonsparse, numeric or logical matrix.

Example: `I = imread('eight.tif');` `J = medfilt2(I);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32` | `logical`

[m n] — Neighborhood size

3-by-3 (default) | two-element numeric vector

Neighborhood size, specified as a two-element numeric vector, [m n], of real positive integers.

Example: `J = medfilt2(gpuarrayI,[5 5]);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

gpuarrayA — Input matrix when run on a GPU

`gpuArray`

Input matrix when run on a GPU, specified as a `gpuArray`.

Example: `gpuarrayI = gpuArray(imread('your_image_file.tif')); J = medfilt2(gpuarrayI);`

padopt — Padding option

'zeros' (default) | 'symmetric' | 'indexed'

Padding option, specified as one of the following strings.

Value	Description
'zeros'	Padded with 0s. This is the default.
'symmetric'	Symmetrically extended at the boundaries.
'indexed'	Padded with 1s, if the class of A is <code>double</code> ; otherwise, padded with 0s.

Example: `K = medfilt2(J,'symmetric');`

Data Types: `char`

Output Arguments

B — Output image

2-D array

Output image, returned as a 2-D array of the same class as the input image A.

gpuarrayB — Output image when run on a GPU

gpuArray

Output image when run on a GPU, returned as a gpuArray.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic MATLAB Host Computer target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, the `padopt` argument must be a compile-time constant.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

The `[m n]` input argument must be a compile-time constant.

Tips

- Median filtering is a nonlinear operation often used in image processing to reduce "salt and pepper" noise. A median filter is more effective than convolution when the goal is to simultaneously reduce noise and preserve edges. For information about performance considerations, see `ordfilt2`.
- If the input image A is of an integer class, all the output values are returned as integers. If the number of pixels in the neighborhood (i.e., $m*n$) is even, some of the median values might not be integers. In these cases, the fractional parts are discarded. Logical input is treated similarly. For example, the true median for the following 2-by-2 neighborhood in a `uint8` array is 4.5, but `medfilt2` discards the fractional part and returns 4.

4 8

Algorithms

On the CPU, `medfilt2` uses `ordfilt2` to perform the filtering.

References

[1] Lim, Jae S., *Two-Dimensional Signal and Image Processing*, Englewood Cliffs, NJ, Prentice Hall, 1990, pp. 469-476.

See Also

`filter2` | `gpuArray` | `ordfilt2` | `wiener2`

Introduced before R2006a

montage

Display multiple image frames as rectangular montage

Syntax

```
montage(filenamees)
montage(I)
montage(X, map)
montage(..., param1, value1, param2, value2, ...)
h = montage(...)
```

Description

`montage(filenamees)` displays a montage of the images specified in `filenamees`. `filenamees` is an N -by-1 or 1-by- N cell array of filenames. If the files are not in the current directory or in a directory on the MATLAB path, you must specify the full pathname. See the `imread` command for more information. If one or more of the image files contains an indexed image, `montage` uses the colormap from the first indexed image file. `montage` arranges the frames so that they roughly form a square.

`montage(I)` displays all the frames of a multiframe image array `I` in a single image object. `I` can be a sequence of binary, grayscale, or truecolor images. A binary or grayscale image sequence must be an M -by- N -by-1-by- K array. A truecolor image sequence must be an M -by- N -by-3-by- K array.

`montage(X, map)` displays all the frames of the indexed image array `X`, using the colormap `map` for all frames. `X` is an M -by- N -by-1-by- K array.

`montage(..., param1, value1, param2, value2, ...)` returns a customized display of an image montage, depending on the values of the optional parameter/value pairs. See “Parameters” on page 1-1254 for a list of available parameters.

`h = montage(...)` returns the handle to the single image object which contains all the frames displayed.

Parameters

The following table lists the parameters available, alphabetically by name. Parameter names can be abbreviated, and case does not matter.

Parameter	Value
'DisplayRange'	1-by-2 vector, [LOW HIGH] that controls the display range of each image in a grayscale sequence. The value LOW (and any value less than LOW) displays as black; the value HIGH (and any value greater than HIGH) displays as white. If you specify an empty matrix ([]), <code>montage</code> uses the minimum and maximum values of the images to be displayed in the montage as specified by 'Indices'. For example, if 'Indices' is 1:K and the 'DisplayRange' is set to [], the minimum value in <code>I (min(I(:)))</code> is displayed as black, and the maximum value (<code>max(I(:))</code>) is displayed as white. Default: Range of the data type of I.
'Indices'	Numeric array specifying which frames to display in the montage. <code>montage</code> interprets the values as indices into array I or cell array filenames. For example, to create a montage of the first four frames in I, enter <code>montage(I, 'Indices', 1:4);</code> . You can use this parameter to specify individual frames or skip frames. For example, the value 1:2:20 displays every other frame. Default: 1:K, where K is the total number of frames or image files.
'Parent'	Handle of an axes that specifies the parent of the image object created by <code>montage</code> .
'Size'	Two-element vector, [NROWS NCOLS], specifying the number of rows and number of columns in the montage. Use NaNs in the size vector to indicate that <code>montage</code> should calculate size in a particular dimension in a way that includes all the images in the montage. For example, if 'Size' is [2 NaN], the montage will have two rows, and the number of columns will be computed automatically to include all of the images in the montage. <code>montage</code> displays the images horizontally across columns. Default: Calculated so the images in the montage roughly form a square. <code>montage</code> considers the aspect ratio when calculating the number of images to display horizontally and vertically.

Class Support

A grayscale image array can be `logical`, `uint8`, `uint16`, `int16`, `single`, or `double`. An indexed image can be `logical`, `uint8`, `uint16`, `single`, or `double`. The colormap must be `double`. A truecolor image can be `uint8`, `uint16`, `single`, or `double`. The output is a handle to the image object produced by `montage`.

Examples

Create Montage from Series of Files

Create a list of filenames.


```
fileFolder = fullfile(matlabroot, 'toolbox', 'images', 'imdata');  
dirOutput = dir(fullfile(fileFolder, 'AT3_1m4_*.tif'));  
fileNames = {dirOutput.name}'
```

```
fileNames =
```

```
'AT3_1m4_01.tif'  
'AT3_1m4_02.tif'  
'AT3_1m4_03.tif'  
'AT3_1m4_04.tif'  
'AT3_1m4_05.tif'  
'AT3_1m4_06.tif'  
'AT3_1m4_07.tif'  
'AT3_1m4_08.tif'  
'AT3_1m4_09.tif'  
'AT3_1m4_10.tif'
```

Display the sequence of images.

```
montage(fileNames, 'Size', [2 5]);
```



Use DisplayRange Parameter to Highlight Image Structures

Create a list of file names.


```
fileFolder = fullfile(matlabroot, 'toolbox', 'images', 'imdata');  
dirOutput = dir(fullfile(fileFolder, 'AT3_1m4_*.tif'));  
fileNames = {dirOutput.name}'
```

```
fileNames =
```

```
 'AT3_1m4_01.tif'  
 'AT3_1m4_02.tif'  
 'AT3_1m4_03.tif'  
 'AT3_1m4_04.tif'  
 'AT3_1m4_05.tif'  
 'AT3_1m4_06.tif'  
 'AT3_1m4_07.tif'  
 'AT3_1m4_08.tif'  
 'AT3_1m4_09.tif'  
 'AT3_1m4_10.tif'
```

Display the sequence of images as a montage, using the `DisplayRange` parameter to highlight structures in the images.

```
montage(fileNames, 'Size', [2 5], 'DisplayRange', [75 200]);
```




Customize Number of Images in Montage

Load images.

```
load mri
```


Display as montage.

```
montage(D,map)
```



Create new montage containing only the first nine images.

```
figure  
montage(D, map, 'Indices', 1:9);
```

See Also

`immovie` | `imshow` | `imshowarray`

Introduced before R2006a

multithresh

Multilevel image thresholds using Otsu's method

Syntax

```
thresh = multithresh(A)
thresh = multithresh(A,N)
[thresh,metric] = multithresh( ___ )
```

Description

`thresh = multithresh(A)` returns the single threshold value `thresh` computed for image `A` using Otsu's method. You can use `thresh` as an input argument to `imquantize` to convert an image into a two-level image.

`thresh = multithresh(A,N)` returns `thresh` a 1-by-`N` vector containing `N` threshold values using Otsu's method. You can use `thresh` as an input argument to `imquantize` to convert image `A` into an image with `N + 1` discrete levels.

`[thresh,metric] = multithresh(___)` returns `metric`, a measure of the effectiveness of the computed thresholds. `metric` is in the range `[0 1]` and a higher value indicates greater effectiveness of the thresholds in separating the input image into `N + 1` regions based on Otsu's objective criterion.

“Code Generation” on page 1-1271 support: Yes.

“MATLAB Function Block” on page 1-1272 support: Yes.

Examples

Segment Image Into Two Regions

Read image and display it.

```
I = imread('coins.png');
```

```
imshow(I)
```




Calculate a single threshold value for the image.

```
level = multithresh(I);
```

Segment the image into two regions using `imquantize`, specifying the threshold level returned by `multithresh`.

```
seg_I = imquantize(I,level);  
figure  
imshow(seg_I,[])
```




Segment Image into Three Levels Using Two Thresholds

Read image and display it.

```
I = imread('circlesBrightDark.png');  
imshow(I)  
axis off  
title('Original Image')
```

Original Image



Calculate two threshold levels.

```
thresh = multithresh(I,2);
```


Segment the image into three levels using `imquantize` .

```
seg_I = imquantize(I,thresh);
```

Convert segmented image into color image using `label2rgb` and display it.

```
RGB = label2rgb(seg_I);  
figure;  
imshow(RGB)  
axis off  
title('RGB Segmented Image')
```

RGB Segmented Image



Compare Thresholding Entire Image Versus Plane-by-Plane Thresholding

Read truecolor (RGB) image and display it.

```
I = imread('peppers.png');
```

```
imshow(I)
axis off
title('RGB Image');
```

RGB Image



Generate thresholds for seven levels from the entire RGB image.

```
threshRGB = multithresh(I,7);
```

Generate thresholds for each plane of the RGB image.

```
threshForPlanes = zeros(3,7);
```

```
for i = 1:3
```



```

    threshForPlanes(i,:) = multithresh(I(:,:,i),7);
end

```

Process the entire image with the set of threshold values computed from entire image.

```

value = [0 threshRGB(2:end) 255];
quantRGB = imquantize(I, threshRGB, value);

```

Process each RGB plane separately using the threshold vector computed from the given plane. Quantize each RGB plane using threshold vector generated for that plane.

```

quantPlane = zeros( size(I) );

for i = 1:3
    value = [0 threshForPlanes(i,2:end) 255];
    quantPlane(:,:,i) = imquantize(I(:,:,i),threshForPlanes(i,:),value);
end

```

```

quantPlane = uint8(quantPlane);


```

Display both posterized images and note the visual differences in the two thresholding schemes.

```

imshowpair(quantRGB,quantPlane,'montage')
axis off
title('Full RGB Image Quantization          Plane-by-Plane Quantization')

```



To compare the results, calculate the number of unique RGB pixel vectors in each output image. Note that the plane-by-plane thresholding scheme yields about 23% more colors than the full RGB image scheme.

```
dim = size( quantRGB );
quantRGBmx3 = reshape(quantRGB, prod(dim(1:2)), 3);
quantPlanemx3 = reshape(quantPlane, prod(dim(1:2)), 3);

colorsRGB = unique(quantRGBmx3, 'rows' );
colorsPlane = unique(quantPlanemx3, 'rows' );

disp(['Unique colors in RGB image : ' int2str(length(colorsRGB))]);
disp(['Unique colors in Plane-by-Plane image : ' int2str(length(colorsPlane))]);

Unique colors in RGB image : 188
Unique colors in Plane-by-Plane image : 231
```

Check Results Using the Metric Output Argument

Read image.

```
I = imread('circlesBrightDark.png');
```

Find all unique grayscale values in image.

```
uniqLevels = unique(I(:));

disp(['Number of unique levels = ' int2str( length(uniqLevels) )]);

Number of unique levels = 148
```

Compute a series of thresholds at monotonically increasing values of N.

```
Nvals = [1 2 4 8];
for i = 1:length(Nvals)
    [thresh, metric] = multithresh(I, Nvals(i) );
    disp(['N = ' int2str(Nvals(i)) ' | metric = ' num2str(metric)]);
end

N = 1 | metric = 0.54767
N = 2 | metric = 0.98715
N = 4 | metric = 0.99648
N = 8 | metric = 0.99902
```

Apply the set of 8 threshold values to obtain a 9-level segmentation using `imquantize`.

```
seg_Neq8 = imquantize(I,thresh);
```

```
uniqLevels = unique( seg_Neq8(:) )
```

```
uniqLevels =
```

```

1
2
3
4
5
6
7
8
9
```

Threshold the image using `seg_Neq8` as an input to `multithresh`. Set `N` equal to 8, which is 1 less than the number of levels in this segmented image. `multithresh` returns a `metric` value of 1.

```
[thresh, metric] = multithresh(seg_Neq8,8)
```

```
thresh =
```

```
Columns 1 through 7
```

```
1.8784    2.7882    3.6667    4.5451    5.4549    6.3333    7.2118
```

```
Column 8
```

```
8.1216
```

```
metric =
```

```
1
```

Threshold the image again, this time increasing the value of `N` by 1. This value now equals the number of levels in the image. Note how the input is degenerate because the number of levels in the image is too few for the number of requested thresholds. Hence, `multithresh` returns a `metric` value of 0.

```
[thresh, metric] = multithresh(seg_Neq8,9)
```

```
Warning: No solution exists because the number of unique levels in the image are too few to find 9 thresholds. Returning an arbitrarily chosen solution.
```

```
thresh =  
      1      2      3      4      5      6      7      8      9  
  
metric =  
      0
```

Input Arguments

A — Image to be thresholded

real, nonsparse numeric array of any dimension

Image to be thresholded, specified as a real, nonsparse numeric array of any dimension. `multithresh` finds the thresholds based on the aggregate histogram of the entire array. `multithresh` considers an RGB image as a 3-D numeric array and computes the thresholds for the combined data from all three color planes.

`multithresh` uses the range of the input image `A`, `[min(A(:)) max(A(:))]`, as the limits for computing the histogram used in subsequent computations. `multithresh` ignores any NaNs in computation. Any `Inf`s and `-Inf`s are counted in the first and last bin of the histogram, respectively.

For degenerate inputs where the number of unique values in `A` is less than or equal to `N`, there is no viable solution using Otsu's method. For such inputs, the return value `thresh` contains all the unique values from `A` and possibly some extra values that are chosen arbitrarily.

```
Example: I = imread('cameraman.tif'); thresh = multithresh(I);
```

Data Types: `single` | `double` | `int16` | `uint8` | `uint16`

N — Number of threshold values

1 (default) | positive integer scalar

Number of threshold values, specified as a positive integer scalar value. For `N > 2`, `multithresh` uses search-based optimization of Otsu's criterion to find the thresholds.

The search-based optimization guarantees only locally optimal results. Since the chance of converging to local optimum increases with N , it is preferable to use smaller values of N , typically $N < 10$. The maximum allowed value for N is 20.

Example: `thresh = multithresh(I,4);`

Data Types: `single | double | int8 | int16 | int32 | int64 | uint8 | uint16 | uint32 | uint64`

Output Arguments

thresh — Set of threshold values used to quantize an image

1×N vector

Set of threshold values used to quantize an image, returned as a 1-by- N vector, whose data type is the same as image A .

These thresholds are in the same range as the input image A , unlike the `graythresh` function, which returns a normalized threshold in the range $[0, 1]$.

metric — Measure of the effectiveness of the thresholds

scalar

Measure of the effectiveness of the thresholds, returned as a scalar value. Higher values indicates greater effectiveness of the thresholds in separating the input image into $N+1$ classes based on Otsu's objective criterion. For degenerate inputs where the number of unique values in A is less than or equal to N , `metric` equals 0.

Data Types: `double`

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic MATLAB Host Computer target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

The input argument `N` must be a compile-time constant.

References

- [1] Otsu, N., "A Threshold Selection Method from Gray-Level Histograms," *IEEE Transactions on Systems, Man, and Cybernetics*, Vol. 9, No. 1, 1979, pp. 62-66.

See Also

`graythresh` | `im2bw` | `imquantize` | `rgb2ind`

Introduced in R2012b

nitfinfo

Read metadata from National Imagery Transmission Format (NITF) file

Syntax

```
metadata = nitfinfo(filename)
```

Description

`metadata = nitfinfo(filename)` returns a structure whose fields contain file-level metadata about the images, annotations, and graphics in a National Imagery Transmission Format (NITF) file. NITF is an image format used by the U.S. government and military for transmitting documents. A NITF file can contain multiple images and include text and graphic layers. *filename* is a character array that specifies the name of the NITF file, which must be in the current directory, in a directory on the MATLAB path, or contain the full path to the file.

`nitfinfo` supports version 2.0 and 2.1 NITF files, at all Joint Interoperability Test Command (JITC) compliance levels, as well as the NATO Secondary Image Format (NSIF) 1.0. `nitfinfo` does not support NITF 1.1 files.

See Also

`isnitf` | `nitfread`

Introduced in R2007b

nitfread

Read image from NITF file

Syntax

```
X = nitfread(filename)
X = nitfread(filename,idx)
X = nitfread(...,'PixelRegion',{rows,cols})
```

Description

`X = nitfread(filename)` reads the first image from the National Imagery Transmission Format (NITF) file specified by the character array `filename`. The `filename` array must be in the current directory or in a directory on the MATLAB path, or it must contain the full path to the file.

`X = nitfread(filename,idx)` reads the image with index number `idx` from a NITF file that contains multiple images.

`X = nitfread(...,'PixelRegion',{rows,cols})` reads a region of pixels from a NITF image. `rows` and `cols` are two or three element vectors, where the first value is the starting location, and the last value is the ending location. In the three value syntax, the second value is the increment.

This function supports version 2.0 and 2.1 NITF files, as well as NSIF 1.0. Compressed images, image submasks, and NITF 1.1 files are not supported.

See Also

`isnitf` | `nitfinfo`

Introduced in R2007b

nlfiter

General sliding-neighborhood operations

Syntax

```
B = nlfiter(A, [m n], fun)
B = nlfiter(A, 'indexed',...)
```

Description

`B = nlfiter(A, [m n], fun)` applies the function `fun` to each `m`-by-`n` sliding block of the grayscale image `A`. `fun` is a function that accepts an `m`-by-`n` matrix as input and returns a scalar result.

```
c = fun(x)
```

`fun` must be a function handle.

`c` is the output value for the center pixel in the `m`-by-`n` block `x`. `nlfiter` calls `fun` for each pixel in `A`. `nlfiter` zero-pads the `m`-by-`n` block at the edges, if necessary.

`B = nlfiter(A, 'indexed',...)` processes `A` as an indexed image, padding with 1's if `A` is of class `single` or `double` and 0's if `A` is of class `logical`, `uint8`, or `uint16`.

Class Support

The input image `A` can be of any class supported by `fun`. The class of `B` depends on the class of the output from `fun`. When `A` is grayscale, it can be any numeric type or `logical`. When `A` is indexed, it can be `logical`, `uint8`, `uint16`, `single`, or `double`.

Examples

Apply median filter to image

This example shows how apply a median filter to an image using `nlfiter`. This example produces the same result as calling `medfilt2` with a 3-by-3 neighborhood.

```
A = imread('cameraman.tif');  
A = im2double(A);  
fun = @(x) median(x(:));  
B = nlfilter(A,[3 3],fun);  
imshow(A), figure, imshow(B)
```





More About

Tips

`nlfiler` can take a long time to process large images. In some cases, the `colfilt` function can perform the same operation much faster.

- “Anonymous Functions”
- “Parameterizing Functions”
- “Create Function Handle”

See Also

`blockproc` | `colfilt`

Introduced before R2006a

normxcorr2

Normalized 2-D cross-correlation

Syntax

```
C = normxcorr2(template, A)
gpuarrayC = normxcorr2(gpuarrayTemplate, gpuarrayA)
```

Description

`C = normxcorr2(template, A)` computes the normalized cross-correlation of the matrices `template` and `A`. The matrix `A` must be larger than the matrix `template` for the normalization to be meaningful. The values of `template` cannot all be the same. The resulting matrix `C` contains the correlation coefficients, which can range in value from -1.0 to 1.0.

`gpuarrayC = normxcorr2(gpuarrayTemplate, gpuarrayA)` performs the normalized cross-correlation operation on a GPU.

Class Support

The input matrices `template` and `A` can be numeric. The output matrix `C` is `double`.


The input matrices `gpuarrayTemplate` and `gpuarrayA` are `gpuArrays` whose underlying type must be numeric. The output matrix `gpuarrayC` is a `gpuArray` whose underlying class must be `double`.

Examples

Use Cross-Correlation to Find Template in Image


Read images into the workspace and display them side-by-side.

```
onion = rgb2gray(imread('onion.png'));  
peppers = rgb2gray(imread('peppers.png'));  
imshowpair(peppers,onion,'montage')
```



Perform cross-correlation and display result as surface.

```
c = normxcorr2(onion,peppers);  
figure, surf(c), shading flat
```



Find peak in cross-correlation.

```
[ypeak, xpeak] = find(c==max(c(:)));
```


Account for the padding that `normxcorr2` adds.

```
yoffSet = ypeak-size(onion,1);  
xoffSet = xpeak-size(onion,2);
```

Display matched area.

```
hFig = figure;  
hAx = axes;  
imshow(peppers, 'Parent', hAx);
```

```
imrect(hAx, [xoffSet+1, yoffSet+1, size(onion,2), size(onion,1)]);
```



Use cross-correlation to find template in image on a GPU

Read images into `gpuArrays`.


```
onion    = gpuArray(imread('onion.png'));  
peppers = gpuArray(imread('peppers.png'));
```

Convert the color images to 2-D. The `rgb2gray` function accepts `gpuArrays`.

```
onion    = rgb2gray(onion);  
peppers = rgb2gray(peppers);
```

Perform cross-correlation and display result as surface.

```
c = normxcorr2(onion,peppers);  
figure, surf(c), shading flat
```



Find peak in cross-correlation.

```
[ypeak, xpeak] = find(c==max(c(:)));
```

Account for the padding that `normxcorr2` adds.

```
yoffset = ypeak-size(onion,1);  
xoffset = xpeak-size(onion,2);
```

Move data back to CPU for display.


```
yoffSet = gather(ypeak-size(onion,1));
xoffSet = gather(xpeak-size(onion,2));
```

Display matched area.

```
hFig = figure;
hAx = axes;
imshow(peppers, 'Parent', hAx);
imrect(hAx, [xoffSet, yoffSet, size(onion,2), size(onion,1)]);
```

More About

Tips

Normalized cross-correlation is an undefined operation in regions where **A** has zero variance over the full extent of the template. In these regions, we assign correlation coefficients of zero to the output **C**.

Algorithms

normxcorr2 uses the following general procedure [1], [2]:

- 1 Calculate cross-correlation in the spatial or the frequency domain, depending on size of images.
- 2 Calculate local sums by precomputing running sums. [1]
- 3 Use local sums to normalize the cross-correlation to get correlation coefficients.

The implementation closely follows following formula from [1]:

$$\gamma(u,v) = \frac{\sum_{x,y} [f(x,y) - \bar{f}_{u,v}] [t(x-u, y-v) - \bar{t}]}{\left\{ \sum_{x,y} [f(x,y) - \bar{f}_{u,v}]^2 \sum_{x,y} [t(x-u, y-v) - \bar{t}]^2 \right\}^{0.5}}$$

where

- f is the image.
- \bar{t} is the mean of the template

- $\bar{f}_{u,v}$ is the mean of $f(x,y)$ in the region under the template.

References

- [1] Lewis, J. P., "Fast Normalized Cross-Correlation," *Industrial Light & Magic*
- [2] Haralick, Robert M., and Linda G. Shapiro, *Computer and Robot Vision*, Volume II, Addison-Wesley, 1992, pp. 316-317.

See Also

corrcoef

Introduced before R2006a

ntsc2rgb

Convert NTSC values to RGB color space

Syntax

```
rgbmap = ntsc2rgb(yiqmap)  
RGB = ntsc2rgb(YIQ)
```

Description

`rgbmap = ntsc2rgb(yiqmap)` converts the m -by-3 NTSC (television) color values in `yiqmap` to RGB color space. If `yiqmap` is m -by-3 and contains the NTSC luminance (Y) and chrominance (I and Q) color components as columns, then `rgbmap` is an m -by-3 matrix that contains the red, green, and blue values equivalent to those colors. Both `rgbmap` and `yiqmap` contain intensities in the range 0 to 1.0. The intensity 0 corresponds to the absence of the component, while the intensity 1.0 corresponds to full saturation of the component.

`RGB = ntsc2rgb(YIQ)` converts the NTSC image `YIQ` to the equivalent truecolor image `RGB`.

`ntsc2rgb` computes the RGB values from the NTSC components using

$$\begin{bmatrix} R \\ G \\ B \end{bmatrix} = \begin{bmatrix} 1.000 & 0.956 & 0.621 \\ 1.000 & -0.272 & -0.647 \\ 1.000 & -1.106 & 1.703 \end{bmatrix} \begin{bmatrix} Y \\ I \\ Q \end{bmatrix}.$$

Class Support

The input image or colormap must be of class `double`. The output is of class `double`.

Examples

Convert RGB image to NTSC and back.

```
RGB = imread('board.tif');  
NTSC = rgb2ntsc(RGB);  
RGB2 = ntsc2rgb(NTSC);
```

See Also

[rgb2ntsc](#) | [rgb2ind](#) | [ind2rgb](#) | [ind2gray](#)

Introduced before R2006a

offsetstrel class

Morphological offset structuring element

Description

An `offsetstrel` object represents a nonflat morphological *structuring element*, which is an essential part of morphological dilation and erosion operations. (To create a flat structuring element, use `strel`.)

A nonflat structuring element is a matrix of type `double` that identifies the pixel in the image being processed and defines the neighborhood used in the processing of that pixel. A nonflat structuring element contains finite values used as additive offsets in the morphological computation. The center pixel of the matrix, called the *origin*, identifies the pixel in the image that is being processed. Pixels in the neighborhood with the value `-Inf` are not used in the computation.

You can only use `offsetstrel` objects with grayscale images.

Construction

`SE = offsetstrel('ball',R,H)` creates a nonflat, ball-shaped structuring element whose radius in the X-Y plane is `R` and whose maximum offset height is `H`. For improved performance, `offsetstrel` approximates this shape by a sequence of eight nonflat line-shaped structuring elements.

`SE = offsetstrel('ball',R,H,N)` creates a nonflat ball-shaped structuring element, where `N` specifies the number of nonflat, line-shaped structuring elements that `offsetstrel` uses to approximate the shape. Morphological operations using ball approximations run much faster when you specify a value for `N` greater than 0.

`SE = offsetstrel(offset)` creates a nonflat structuring element with the additive offset specified in the matrix `offset`.

“Code Generation” on page 1-1289 support: Yes.

“MATLAB Function Block” on page 1-1290 support: Yes.

Input Arguments

R — Radius of the ball-shaped structuring element

nonnegative integer

Radius of the ball-shaped structuring element in the X-Y plane, specified as a nonnegative integer.

Data Types: double

H — Maximum offset height

real scalar

Maximum offset height, specified as a real scalar.

Data Types: double

N — Number of nonflat line-shaped structuring elements used to approximate the shape

8 (default) | even number

Number of nonflat line-shaped structuring elements used to approximate the shape, specified as a nonnegative integer.

Value of N	Behavior
N > 0	<code>offsetstrel</code> uses a sequence of N nonflat, line-shaped structuring elements to approximate the shape. N must be an even number.
N = 0	<code>offsetstrel</code> does not use any approximation. The structuring element members comprise all pixels whose centers are no greater than R away from the origin. The corresponding height values are determined from the formula of the ellipsoid specified by R and H.

Data Types: double

offset — Values to be added to each pixel location in the neighborhood

matrix

Values to be added to each pixel location in the neighborhood when performing the morphological operation, specified as a matrix. Values that are `-Inf` are not considered in the computation.

Data Types: `double`

Properties

Offset — Structuring element neighborhood with offsets

`double` matrix

Structuring element neighborhood with offsets, specified as a `double` matrix.

Data Types: `logical`

Dimensionality — Dimensions of structuring element

nonnegative scalar

Dimensions of structuring element, specified as a nonnegative scalar of class `double`.

Data Types: `double`

Methods

<code>decompose</code>	Return sequence of decomposed structuring elements
<code>reflect</code>	Reflect offset structuring element
<code>translate</code>	Translate structuring element

Additional Capabilities

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, note the following:

- The `'ball'` input argument and all other input arguments must be compile-time constants.

- The methods associated with `offsetstrel` objects are not supported in code generation.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

Examples

Create Ball-shaped Structuring Element

Create a ball-shaped structuring element.

```
SE = offsetstrel('ball',5, 6)
```

```
SE =
```

```
offsetstrel is a ball shaped offset structuring element with properties:
```

```
    Offset: [11x11 double]  
Dimensionality: 2
```

View the structuring element.

```
SE.Offset
```

```
ans =
```

```
Columns 1 through 7
```

```
    -Inf    -Inf         0    0.7498    1.4996    2.2494    1.4996  
    -Inf    0.7498    1.4996    2.2494    2.9992    2.9992    2.9992  
         0    1.4996    2.2494    2.9992    3.7491    3.7491    3.7491  
    0.7498    2.2494    2.9992    3.7491    4.4989    4.4989    4.4989  
    1.4996    2.9992    3.7491    4.4989    5.2487    5.2487    5.2487  
    2.2494    2.9992    3.7491    4.4989    5.2487    5.9985    5.2487  
    1.4996    2.9992    3.7491    4.4989    5.2487    5.2487    5.2487  
    0.7498    2.2494    2.9992    3.7491    4.4989    4.4989    4.4989  
         0    1.4996    2.2494    2.9992    3.7491    3.7491    3.7491
```


-Inf	0.7498	1.4996	2.2494	2.9992	2.9992	2.9992
-Inf	-Inf	0	0.7498	1.4996	2.2494	1.4996

Columns 8 through 11

0.7498	0	-Inf	-Inf
2.2494	1.4996	0.7498	-Inf
2.9992	2.2494	1.4996	0
3.7491	2.9992	2.2494	0.7498
4.4989	3.7491	2.9992	1.4996
4.4989	3.7491	2.9992	2.2494
4.4989	3.7491	2.9992	1.4996
3.7491	2.9992	2.2494	0.7498
2.9992	2.2494	1.4996	0
2.2494	1.4996	0.7498	-Inf
0.7498	0	-Inf	-Inf

See Also

strel

More About

- “Structuring Elements”
- Property Attributes

Introduced in R2016a

decompose

Class: `offsetstrel`

Return sequence of decomposed structuring elements

Syntax

`SEQ = decompose(SE)`

Description

`SEQ = decompose(SE)` returns an array of structuring elements, `SEQ`, that are the decomposition of the input structuring element `SE`. `SEQ` is equivalent to `SE`, but the elements of `SEQ` cannot be decomposed further.

Input Arguments

SE — Offset structuring element

`offsetstrel` object

Offset structuring element, specified as an `offsetstrel` object.

Output Arguments

SEQ — Sequence of structuring elements that approximate an `offsetstrel` object

array of `offsetstrel` objects

Sequence of structuring elements that approximate an offset structuring element, returned as an array of `offsetstrel` objects.

Examples

Extract Decomposition of Structuring Element

Create a ball-shaped structuring element.

```
se = offsetstrel('ball',5, 6.5)
```

```
se =
```

offsetstrel is a ball shaped offset structuring element with properties:

```
    Offset: [11x11 double]  
Dimensionality: 2
```

Obtain the decomposition of the structuring element.

```
seq = decompose(se)
```

```
seq =
```

1x8 offsetstrel array with properties:

```
    Offset  
Dimensionality
```

Introduced in R2016a

reflect

Class: `offsetstrel`

Reflect offset structuring element

Syntax

`SE2 = reflect(SE)`

Description

`SE2 = reflect(SE)` reflects the structuring element (or structuring elements) specified by `SE`. This method reflects the structuring element through its center. The effect is the same as if you rotated the structuring element's domain 180 degrees around its center (for a 2-D structuring element).

Input Arguments

SE — Offset structuring element

`offsetstrel` object or array of objects

Offset structuring element, specified as an `offsetstrel` object or array of objects. If `SE` is an array of structuring element objects, then `reflect(SE)` reflects each element of `SE`, and `SE2` has the same size as `SE`.

Output Arguments

SE2 — Reflected structuring element or structuring elements

`offsetstrel` object or array of `offsetstrel` objects

Reflected structuring element or structuring elements, returned as an `offsetstrel` object or array of `offsetstrel` objects.

Examples

Reflect Offset Structuring Element

Create offset strel structuring element.

```
se = offsetstrel('ball', 5, 6.5)
```

```
se =
```

offsetstrel is a ball shaped offset structuring element with properties:

```
        Offset: [11x11 double]
Dimensionality: 2
```

Reflect the structuring element.

```
se2 = se.reflect()
```

```
se2 =
```

offsetstrel is a ball shaped offset structuring element with properties:

```
        Offset: [11x11 double]
Dimensionality: 2
```

Introduced in R2016a

translate

Class: `offsetstrel`

Translate structuring element

Syntax

`SE2 = translate(SE, V)`

Description

`SE2 = translate(SE, V)` translates an offset structuring element `SE` in N-D space. `V` is an N-element vector containing the offsets of the desired translation in each dimension.

Input Arguments

SE — Offset structuring element

`offsetstrel` object

Offset structuring element, specified as an `offsetstrel` object.

V — Translation offsets

numeric vector

Translation offsets, specified as a numeric vector.

Output Arguments

SE2 — Translated structuring element

`offsetstrel` object

Translated structuring element, returned as an `offsetstrel` object.

Examples

Translate Offset Structuring Element

Create an offset structuring element.

```
SE = offsetstrel('ball', 5, 6.5)
SE.Offset
```

```
SE =
```

offsetstrel is a ball shaped offset structuring element with properties:

```
    Offset: [11x11 double]
 Dimensionality: 2
```

```
ans =
```

```
Columns 1 through 7
```

```

-Inf      -Inf          0      0.8123      1.6246      2.4369      1.6246
-Inf      0.8123      1.6246      2.4369      3.2492      3.2492      3.2492
  0      1.6246      2.4369      3.2492      4.0615      4.0615      4.0615
0.8123      2.4369      3.2492      4.0615      4.8738      4.8738      4.8738
1.6246      3.2492      4.0615      4.8738      5.6861      5.6861      5.6861
2.4369      3.2492      4.0615      4.8738      5.6861      6.4984      5.6861
1.6246      3.2492      4.0615      4.8738      5.6861      5.6861      5.6861
0.8123      2.4369      3.2492      4.0615      4.8738      4.8738      4.8738
  0      1.6246      2.4369      3.2492      4.0615      4.0615      4.0615
-Inf      0.8123      1.6246      2.4369      3.2492      3.2492      3.2492
-Inf      -Inf          0      0.8123      1.6246      2.4369      1.6246
```

```
Columns 8 through 11
```

```

0.8123          0      -Inf      -Inf
2.4369      1.6246      0.8123      -Inf
3.2492      2.4369      1.6246          0
4.0615      3.2492      2.4369      0.8123
4.8738      4.0615      3.2492      1.6246
4.8738      4.0615      3.2492      2.4369
4.8738      4.0615      3.2492      1.6246
4.0615      3.2492      2.4369      0.8123
```

```

3.2492    2.4369    1.6246    0
2.4369    1.6246    0.8123   -Inf
0.8123    0          -Inf     -Inf

```

Translate the structuring element.

```

V = [2 2];
SE2 = translate(SE,V)
SE2.Offset

```

```
SE2 =
```

offsetstrel is a ball shaped offset structuring element with properties:

```

    Offset: [15x15 double]
Dimensionality: 2

```

```
ans =
```

```
Columns 1 through 7
```

```

-Inf    -Inf    -Inf    -Inf    -Inf    -Inf    -Inf
-Inf    -Inf    -Inf    -Inf    -Inf    -Inf    -Inf
-Inf    -Inf    -Inf    -Inf    -Inf    -Inf    -Inf
-Inf    -Inf    -Inf    -Inf    -Inf    -Inf    -Inf
-Inf    -Inf    -Inf    -Inf    -Inf    -Inf    0
-Inf    -Inf    -Inf    -Inf    -Inf    0.8123  1.6246
-Inf    -Inf    -Inf    -Inf    0        1.6246  2.4369
-Inf    -Inf    -Inf    -Inf    0.8123  2.4369  3.2492
-Inf    -Inf    -Inf    -Inf    1.6246  3.2492  4.0615
-Inf    -Inf    -Inf    -Inf    2.4369  3.2492  4.0615
-Inf    -Inf    -Inf    -Inf    1.6246  3.2492  4.0615
-Inf    -Inf    -Inf    -Inf    0.8123  2.4369  3.2492
-Inf    -Inf    -Inf    -Inf    0        1.6246  2.4369
-Inf    -Inf    -Inf    -Inf    -Inf     0.8123  1.6246
-Inf    -Inf    -Inf    -Inf    -Inf     -Inf     0

```

```
Columns 8 through 14
```

```

-Inf    -Inf    -Inf    -Inf    -Inf    -Inf    -Inf
-Inf    -Inf    -Inf    -Inf    -Inf    -Inf    -Inf
-Inf    -Inf    -Inf    -Inf    -Inf    -Inf    -Inf

```


-Inf	-Inf	-Inf	-Inf	-Inf	-Inf	-Inf
0.8123	1.6246	2.4369	1.6246	0.8123	0	-Inf
2.4369	3.2492	3.2492	3.2492	2.4369	1.6246	0.8123
3.2492	4.0615	4.0615	4.0615	3.2492	2.4369	1.6246
4.0615	4.8738	4.8738	4.8738	4.0615	3.2492	2.4369
4.8738	5.6861	5.6861	5.6861	4.8738	4.0615	3.2492
4.8738	5.6861	6.4984	5.6861	4.8738	4.0615	3.2492
4.8738	5.6861	5.6861	5.6861	4.8738	4.0615	3.2492
4.0615	4.8738	4.8738	4.8738	4.0615	3.2492	2.4369
3.2492	4.0615	4.0615	4.0615	3.2492	2.4369	1.6246
2.4369	3.2492	3.2492	3.2492	2.4369	1.6246	0.8123
0.8123	1.6246	2.4369	1.6246	0.8123	0	-Inf

Column 15

```
-Inf
-Inf
-Inf
-Inf
-Inf
-Inf
0
0.8123
1.6246
2.4369
1.6246
0.8123
0
-Inf
-Inf
```

Introduced in R2016a

openrset

Open R-Set file

Syntax

```
openrset(filename)
```

Description

`openrset(filename)` opens the reduced resolution dataset (R-Set) specified by *filename* for viewing.

See Also

`imtool` | `rsetwrite`

Introduced in R2010a

ordfilt2

2-D order-statistic filtering

Syntax

```
B = ordfilt2(A,order,domain)
B = ordfilt2(A,order,domain,S)
B = ordfilt2( ____,padopt)
```

Description

`B = ordfilt2(A,order,domain)` replaces each element in `A` by the `order`th element in the sorted set of neighbors specified by the nonzero elements in `domain`.

`B = ordfilt2(A,order,domain,S)` filters `A`, where `ordfilt2` uses the values of `S` corresponding to the nonzero values of `domain` as additive offsets. You can use this syntax to implement grayscale morphological operations, including grayscale dilation and erosion.

`B = ordfilt2(____,padopt)` filters `A`, where `padopt` specifies how `ordfilt2` pads the matrix boundaries.

“Code Generation” on page 1-1305 support: Yes.

“MATLAB Function Block” on page 1-1305 support: Yes.


Examples

Filter Image with Maximum Filter

Read image into workspace and display it.


```
A = imread('snowflakes.png');
figure
```

```
imshow(A)
```



Filter the image and display the result.

```
B = ordfilt2(A,25,true(5));  
figure  
imshow(B)
```



Input Arguments

A — Input matrix

2-D, real, nonsparse, numeric or logical matrix

Input matrix, specified as a 2-D, real, nonsparse, numeric or logical array.

Example: `A = imread('snowflakes.png');`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32` | `logical`

order — Element to replace the target pixel

real scalar integer

Element to replace the target pixel, specified as a real scalar integer of class `double`.




Example: `B = ordfilt2(A,25,true(5));`

Data Types: `double`

domain — Neighborhood

numeric or logical matrix

Neighborhood, specified as a numeric or logical matrix, containing 1's and 0's. `domain` is equivalent to the structuring element used for binary image operations. The 1-valued elements define the neighborhood for the filtering operation. The following table gives examples of some common filters.

Type of Filtering Operation	MATLAB code	Neighborhood
Median filter	<code>B = ordfilt2(A,5,ones(3,3))</code>	
Minimum filter	<code>B = ordfilt2(A,1,ones(3,3))</code>	
Maximum filter	<code>B = ordfilt2(A,9,ones(3,3))</code>	

Type of Filtering Operation	MATLAB code	Neighborhood									
Minimum of north, east, south, and west neighbors	<code>B = ordfilt2(A,1,[0 1 0; 1 0 1; 0 1 0])</code>	<table border="1"> <tr> <td>0</td> <td>1</td> <td>0</td> </tr> <tr> <td>1</td> <td>0</td> <td>1</td> </tr> <tr> <td>0</td> <td>1</td> <td>0</td> </tr> </table>	0	1	0	1	0	1	0	1	0
0	1	0									
1	0	1									
0	1	0									

Example: `B = ordfilt2(A,25,true(5));`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

S — Additive offsets

matrix

Additive offsets, specified as a matrix the same size as `domain`.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

padopt — Padding option

'zeros' (default) | 'symmetric'

Padding option, specified as either of the strings in this table. 'zeros' or 'symmetric'.

Option	Description
'zeros'	Pad array boundaries with 0's.
'symmetric'	Pad array with mirror reflections of itself.

Data Types: `char`

Output Arguments

B — Output image

2-D array

Output image, returned as a 2-D array of the same class as the input image `A`.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, the `padopt` argument must be a compile-time constant.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

Tips

- When working with large domain matrices that do not contain any zero-valued elements, `ordfilt2` can achieve higher performance if **A** is in an integer data format (`uint8`, `int8`, `uint16`, `int16`). The gain in speed is larger for `uint8` and `int8` than for the 16-bit data types. For 8-bit data formats, the domain matrix must contain seven or more rows. For 16-bit data formats, the domain matrix must contain three or more rows and 520 or more elements.

References

- [1] Haralick, Robert M., and Linda G. Shapiro, *Computer and Robot Vision*, Volume I, Addison-Wesley, 1992.
- [2] Huang, T.S., G.J.Yang, and G.Y.Tang. "A fast two-dimensional median filtering algorithm.", *IEEE transactions on Acoustics, Speech and Signal Processing*, Vol ASSP 27, No. 1, February 1979

See Also

`medfilt2`

Introduced before R2006a

otf2psf

Convert optical transfer function to point-spread function

Syntax

```
PSF = otf2psf(OTF)
PSF = otf2psf(OTF, OUTSIZE)
```

Description

`PSF = otf2psf(OTF)` computes the inverse Fast Fourier Transform (IFFT) of the optical transfer function (OTF) array and creates a point-spread function (PSF), centered at the origin. By default, the PSF is the same size as the OTF.

`PSF = otf2psf(OTF, OUTSIZE)` converts the OTF array into a PSF array, where `OUTSIZE` specifies the size of the output point-spread function. The size of the output array must not exceed the size of the OTF array in any dimension.

To center the PSF at the origin, `otf2psf` circularly shifts the values of the output array down (or to the right) until the (1,1) element reaches the central position, then it crops the result to match dimensions specified by `OUTSIZE`.

Note that this function is used in image convolution/deconvolution when the operations involve the FFT.

Class Support

OTF can be any nonsparse, numeric array. PSF is of class `double`.

Examples

```
PSF = fspecial('gaussian',13,1);
OTF = psf2otf(PSF,[31 31]); % PSF --> OTF
PSF2 = otf2psf(OTF,size(PSF)); % OTF --> PSF2
```



```
subplot(1,2,1); surf(abs(OTF)); title('|OTF|');  
axis square; axis tight  
subplot(1,2,2); surf(PSF2); title('Corresponding PSF');  
axis square; axis tight
```

See Also

psf2otf | circshift | padarray

Introduced before R2006a

otsuthresh

Global histogram threshold using Otsu's method

Syntax

```
T = otsuthresh(counts)
[T EM] = otsuthresh(counts)
```

Description

`T = otsuthresh(counts)` computes a global threshold `T` from histogram counts, `counts`, using Otsu's method. `T` is a normalized intensity value that lies in the range `[0, 1]` that can be used with `imbinarize` to convert an intensity image to a binary image. Otsu's method chooses a threshold that minimizes the intraclass variance of the thresholded black and white pixels.

`[T EM] = otsuthresh(counts)` returns the effectiveness metric, `EM`, which indicates the effectiveness of the thresholding. `EM` is in the range `[0, 1]`.

“Code Generation” on page 1-1311 support: Yes.

“MATLAB Function Block” on page 1-1311 support: Yes.

Examples


Compute Threshold from Image Histogram and Binarize Image

Read image into the workspace.

```
I = imread('coins.png');
```

Calculate a 16-bin histogram for the image.

```
[counts,x] = imhist(I,16);
stem(x,counts)
```




Compute a global threshold using the histogram counts.

```
T = otsuthresh(counts);
```

Create a binary image using the computed threshold and display the image.

```
BW = imbinarize(I,T);  
figure  
imshow(BW)
```



Input Arguments

counts — Histogram counts

real, nonsparse numeric vector of nonnegative values

Histogram counts, specified as a real, nonsparse numeric vector of nonnegative values.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

Output Arguments

T — Global threshold value

numeric scalar

Global threshold value, returned as a numeric scalar of class `double` in the range `[0, 1]`.

EM — Effectiveness metric

numeric scalar

Effectiveness metric, returned as a numeric scalar of class `double` in the range `[0, 1]`. The lower bound is attainable only by histogram counts with all data in a single non-zero bin. The upper bound is attainable only by histogram counts with two non-zero bins.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`adaptthresh` | `graythresh` | `imbinarize`

Introduced in R2016a

padarray

Pad array

Syntax

```
B = padarray(A,padsizel)
B = padarray(A,padsizel,padval)
B = padarray(A,padsizel,padval,direction)
gpuarrayB = padarray(gpuarrayA, ___ )
```

Description

`B = padarray(A,padsizel)` pads array `A` with 0's (zeros). `padsizel` is a vector of nonnegative integers that specifies both the amount of padding to add and the dimension along which to add it. The value of an element in the vector specifies the amount of padding to add. The order of the element in the vector specifies the dimension along which to add the padding.

For example, a `padsizel` value of `[2 3]` means add 2 elements of padding along the first dimension and 3 elements of padding along the second dimension. By default, `padarray` adds padding before the first element and after the last element along the specified dimension.

`B = padarray(A,padsizel,padval)` pads array `A` where `padval` specifies the value to use as the pad value. `padarray` uses the value 0 (zero) as the default. `padval` can be a scalar that specifies the pad value directly or one of the following text strings that specifies the method `padarray` uses to determine the values of the elements added as padding.

Value	Meaning
'circular'	Pad with circular repetition of elements within the dimension.
'replicate'	Pad by repeating border elements of array.
'symmetric'	Pad array with mirror reflections of itself.

`B = padarray(A,padsize,padval,direction)` pads `A` in the direction specified by the string `direction`. `direction` can be one of the following strings. The default value is enclosed in braces (`{}`).

Value	Meaning
<code>{ 'both' }</code>	Pads before the first element and after the last array element along each dimension. This is the default.
<code>'post'</code>	Pad after the last array element along each dimension.
<code>'pre'</code>	Pad before the first array element along each dimension.

`gpuarrayB = padarray(gpuarrayA, ___)` performs the padding operation on a GPU, where `gpuarrayA` is a `gpuArray` object that contains the image `A`. The return value `gpuarrayB` is also a `gpuArray`. This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-1316 support: Yes.

“MATLAB Function Block” on page 1-1316 support: Yes.

Class Support

When padding with a constant value, `A` can be numeric or logical. When padding using the `'circular'`, `'replicate'`, or `'symmetric'` methods, `A` can be of any class. `B` is of the same class as `A`.

Examples

Example 1

Add three elements of padding to the beginning of a vector. The padding elements, indicated by the gray shading, contain mirror copies of the array elements.

```
a = [ 1 2 3 4 ];
b = padarray(a,[0 3],'symmetric','pre')
b ==
```

3	2	1	1	2	3	4
---	---	---	---	---	---	---

Example 2

Add three elements of padding to the end of the first dimension of the array and two elements of padding to the end of the second dimension. The example uses the value of the last array element as the padding value.

```
A = [1 2; 3 4];  
B = padarray(A,[3 2],'replicate','post')
```

```
    1     2     2     2  
    3     4     4     4  
    3     4     4     4  
    3     4     4     4  
    3     4     4     4  
B =
```

Example 3

Add three elements of padding to the vertical and horizontal dimensions of a three-dimensional array. Use default values for the pad value and direction.

```
A = [ 1 2; 3 4];  
B = [ 5 6; 7 8];  
C = cat(3,A,B)  
C(:,:,1) =
```

```
    1     2  
    3     4
```

```
C(:,:,2) =
```

```
    5     6  
    7     8
```

```
D = padarray(C,[3 3])
```



```

    0  0  0  0  0  0  0  0
    0  0  0  0  0  0  0  0
    0  0  0  0  0  0  0  0
    0  0  0  1  2  0  0  0
    0  0  0  3  4  0  0  0
    0  0  0  0  0  0  0  0
    0  0  0  0  0  0  0  0
    0  0  0  0  0  0  0  0
D(:,:,1) ==
    0  0  0  0  0  0  0  0
    0  0  0  0  0  0  0  0
    0  0  0  0  0  0  0  0
    0  0  0  5  6  0  0  0
    0  0  0  7  8  0  0  0
    0  0  0  0  0  0  0  0
    0  0  0  0  0  0  0  0
    0  0  0  0  0  0  0  0
D(:,:,2) ==

```

Perform Padding on a GPU

Add padding on all sides of an image.

```

gcam = gpuArray(imread('cameraman.tif'));
padcam = padarray(gcam,[50 50],'both');
imshow(padcam)

```



More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, `padarray` supports only up to 3-D inputs, and the input arguments, `padval` and `direction` must be compile-time constants.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

When generating code, `padsizes` must be a compile-time constant.

See Also

`circshift` | `gpuArray` | `imfilter`

Introduced before R2006a

para2fan

Convert parallel-beam projections to fan-beam

Syntax

```
F = para2fan(P, D)
I = para2fan(..., param1, val1, param2, val2, ...)
[F, fan_positions, fan_rotation_angles] = fan2para(...)
```

Description

`F = para2fan(P, D)` converts the parallel-beam data `P` to the fan-beam data `F`. Each column of `P` contains the parallel-beam sensor samples at one rotation angle. `D` is the distance in pixels from the fan-beam vertex to the center of rotation that was used to obtain the projections.

The sensors are assumed to have a one-pixel spacing. The parallel-beam rotation angles are assumed to be spaced equally to cover $[0,180]$ degrees. The calculated fan-beam rotation angles cover $[0,360)$ with the same spacing as the parallel-beam rotation angles. The calculated fan-beam angles are equally spaced with the spacing set to the smallest angle implied by the sensor spacing.

`I = para2fan(..., param1, val1, param2, val2, ...)` specifies parameters that control various aspects of the `para2fan` conversion. Parameter names can be abbreviated, and case does not matter. Default values are enclosed in braces like this: `{default}`. Parameters include

Parameter	Description
'FanCoverage'	String specifying the range of rotation angles used to calculate the projection data <code>F</code> . Possible values: <code>{'cycle'}</code> or <code>'minimal'</code> See <code>ifanbeam</code> for details.
'FanRotationIncrement'	Positive real scalar specifying the rotation angle increment of the fan-beam projections in degrees.

Parameter	Description
	<p>If 'FanCoverage' is 'cycle', 'FanRotationIncrement' must be a factor of 360.</p> <p>If 'FanRotationIncrement' is not specified, then it is set to the same spacing as the parallel-beam rotation angles.</p>
'FanSensorGeometry'	<p>String specifying how sensors are positioned.</p> <p>Possible values: { 'arc ' } or 'line '</p> <p>See fanbeam for details.</p>
'FanSensorSpacing'	<p>Positive real scalar specifying the spacing of the fan beams. Interpretation of the value depends on the setting of 'FanSensorGeometry':</p> <p>If 'FanSensorGeometry' is 'arc ', the value defines the angular spacing in degrees. Default value is 1.</p> <p>If 'FanSensorGeometry' is 'line ', the value defines the linear spacing in pixels.</p> <p>If 'FanSensorSpacing' is not specified, the default is the smallest value implied by 'ParallelSensorSpacing' such that</p> <p>If 'FanSensorGeometry' is 'arc ', 'FanSensorSpacing' is</p> $180/PI*ASIN(PSPACE/D)$ <p>where PSPACE is the value of 'ParallelSensorSpacing'.</p> <p>If 'FanSensorGeometry' is 'line ', 'FanSensorSpacing' is</p> $D*ASIN(PSPACE/D)$

Parameter	Description
'Interpolation'	Text string specifying the type of interpolation used between the parallel-beam and fan-beam data. 'nearest' — Nearest-neighbor { 'linear' } — Linear 'spline' — Piecewise cubic spline 'pchip' — Piecewise cubic Hermite (PCHIP) 'v5cubic' — The cubic interpolation from MATLAB 5
'ParallelCoverage'	Text string specifying the range of rotation. 'cycle' -- Parallel data covers 360 degrees { 'halfcycle' } — Parallel data covers 180 degrees
'ParallelSensorSpacing'	Positive real scalar specifying the spacing of the parallel-beam sensors in pixels. The range of sensor locations is implied by the range of fan angles and is given by $[D*\sin(\min(\text{FAN_ANGLES})), D*\sin(\max(\text{FAN_ANGLES}))]$ If 'ParallelSensorSpacing' is not specified, the spacing is assumed to be uniform and is set to the minimum spacing implied by the fan angles and sampled over the range implied by the fan angles.

`[F, fan_positions, fan_rotation_angles] = fan2para(...)` returns the fan-beam sensor measurement *angles* in `fan_positions`, if 'FanSensorGeometry' is 'arc'. If 'FanSensorGeometry' is 'line', `fan_positions` contains the fan-beam sensor *positions* along the line of sensors. `fan_rotation_angles` contains rotation angles.

Class Support

P and D can be `double` or `single`, and must be nonsparse. The other numeric input arguments must be `double`. The output arguments are `double`.

Examples

Generate parallel-beam projections

```
ph = phantom(128);
theta = 0:180;
[P, xp] = radon(ph, theta);
imshow(theta, xp, P, [], 'n'), axis normal
title('Parallel-Beam Projections')
xlabel('\theta (degrees)')
ylabel('x''')
colormap(hot), colorbar
```

Convert to fan-beam projections

```
[F, Fpos, Fangles] = para2fan(P, 100);
figure, imshow(Fangles, Fpos, F, [], 'n'), axis normal
title('Fan-Beam Projections')
xlabel('\theta (degrees)')
ylabel('Sensor Locations (degrees)')
colormap(hot), colorbar
```

See Also

fan2para | iradon | fanbeam | ifanbeam | phantom | radon

Introduced before R2006a

phantom

Create head phantom image

Syntax

```
P = phantom(def, n)
P = phantom(E, n)
[P, E] = phantom(...)
```

Description

`P = phantom(def, n)` generates an image of a head phantom that can be used to test the numerical accuracy of `radon` and `iradon` or other two-dimensional reconstruction algorithms. `P` is a grayscale intensity image that consists of one large ellipse (representing the brain) containing several smaller ellipses (representing features in the brain).

`def` is a string that specifies the type of head phantom to generate. Valid values are

- 'Shepp-Logan' — Test image used widely by researchers in tomography
- 'Modified Shepp-Logan' (default) — Variant of the Shepp-Logan phantom in which the contrast is improved for better visual perception

`n` is a scalar that specifies the number of rows and columns in `P`. If you omit the argument, `n` defaults to 256.

`P = phantom(E, n)` generates a user-defined phantom, where each row of the matrix `E` specifies an ellipse in the image. `E` has six columns, with each column containing a different parameter for the ellipses. This table describes the columns of the matrix.

Column	Parameter	Meaning
Column 1	A	Additive intensity value of the ellipse
Column 2	a	Length of the horizontal semiaxis of the ellipse
Column 3	b	Length of the vertical semiaxis of the ellipse
Column 4	x0	<i>x</i> -coordinate of the center of the ellipse
Column 5	y0	<i>y</i> -coordinate of the center of the ellipse

Column	Parameter	Meaning
Column 6	phi	Angle (in degrees) between the horizontal semiaxis of the ellipse and the x -axis of the image

For purposes of generating the phantom, the domains for the x - and y -axes span $[-1,1]$. Columns 2 through 5 must be specified in terms of this range.

`[P, E] = phantom(...)` returns the matrix **E** used to generate the phantom.

Class Support

All inputs and all outputs must be of class `double`.

Examples

```
P = phantom('Modified Shepp-Logan',200);
imshow(P)
```



More About

Tips

For any given pixel in the output image, the pixel's value is equal to the sum of the additive intensity values of all ellipses that the pixel is a part of. If a pixel is not part of any ellipse, its value is 0.

The additive intensity value A for an ellipse can be positive or negative; if it is negative, the ellipse will be darker than the surrounding pixels. Note that, depending on the values of A , some pixels can have values outside the range $[0,1]$.

References

- [1] Jain, Anil K., *Fundamentals of Digital Image Processing*, Englewood Cliffs, NJ, Prentice Hall, 1989, p. 439.

See Also

radon | iradon

Introduced before R2006a

images.geotrans.PiecewiseLinearTransformation2D class

Package: images.geotrans

2-D piecewise linear geometric transformation

Description

An `images.geotrans.PiecewiseLinearTransformation2D` object encapsulates a 2-D piecewise linear geometric transformation.

Construction

`tform = images.geotrans.PiecewiseLinearTransformation2D(movingPoints, fixedPoints)` creates an `images.geotrans.PiecewiseLinearTransformation2D` object given m -by-2 matrices `movingPoints` and `fixedPoints`, which define matched control points in the moving and fixed images, respectively.

Properties

Dimensionality

Dimensionality of geometric transformation

Describes the dimensionality of the geometric transformation for both input and output points.

Methods

`transformPointsInverse`
`outputLimits`

Apply inverse geometric transformation
Find output limits of geometric transformation

Copy Semantics

Value. To learn how value classes affect copy operations, see [Copying Objects in the MATLAB documentation](#).

Examples

Fit set of control points related by affine transformation

Fit a piecewise linear transformation to a set of fixed and moving control points that are actually related by a single global `affine2d` transformation across the domain.

Create a 2D affine transformation.

```
theta = 10;
tformAffine = affine2d([cosd(theta) -sind(theta) 0; sind(theta) cosd(theta) 0; 0 0 1])
tformAffine =
```

```
    affine2d with properties:
```

```
                T: [3x3 double]
    Dimensionality: 2
```

Arbitrarily choose 6 pairs of control points.

```
fixedPoints = [10 20; 10 5; 2 3; 0 5; -5 3; -10 -20];
```

Apply forward geometric transformation to map fixed points to obtain effect of fixed and moving points that are related by some geometric transformation.

```
movingPoints = transformPointsForward(tformAffine, fixedPoints)
```

```
movingPoints =

    13.3210    17.9597
    10.7163     3.1876
     2.4906     2.6071
     0.8682     4.9240
    -4.4031     3.8227
   -13.3210   -17.9597
```

Estimate piecewise linear transformation that maps `movingPoints` to `fixedPoints`.

```
tformPiecewiseLinear = images.geotrans.PiecewiseLinearTransformation2D(movingPoints, fixedPoints)
```

```
tformPiecewiseLinear =
```

```
    PiecewiseLinearTransformation2D with properties:
```

```
        Dimensionality: 2
```

Verify the fit of our `PiecewiseLinearTransformation2D` object at the control points.

```
movingPointsComputed = transformPointsInverse(tformPiecewiseLinear, fixedPoints);
```

```
errorInFit = hypot(movingPointsComputed(:,1)-movingPoints(:,1), ...  
                  movingPointsComputed(:,2)-movingPoints(:,2))
```

```
errorInFit =
```

```
    1.0e-15 *
```

```
    0
```

```
    0
```

```
    0.4441
```

```
    0
```

```
    0
```

```
    0
```

See Also

`images.geotrans.PolynomialTransformation2D` | `fitgeotrans` | `imwarp`

images.geotrans.PiecewiseLinearTransformation2D.transform

Class: images.geotrans.PiecewiseLinearTransformation2D

Package: images.geotrans

Apply inverse geometric transformation

Syntax

```
[u,v] = transformPointsInverse(tform,x,y)
```

```
U = transformPointsInverse(tform,X)
```

Description

`[u,v] = transformPointsInverse(tform,x,y)` applies the inverse transformation of `tform` to the input 2-D point arrays `x` and `y` and outputs the point arrays `u` and `v`. The input point arrays `x` and `y` must be of the same size.

`U = transformPointsInverse(tform,X)` applies the inverse transformation of `tform` to the input n -by-2 point matrix `X` and outputs the n -by-2 point matrix `U`. `transformPointsForward` maps the point `X(k, :)` to the point `U(k, :)`.

Input Arguments

tform

Geometric transformation, specified as an `images.geotrans.PiecewiseLinearTransformation2D` object.

x

Coordinates in X dimension of points to be transformed, specified as a array.

y

Coordinates in Y dimension of points to be transformed, specified as a array.

X

X and Y coordinates of points to be transformed, specified as an n -by-2 matrix

Output Arguments

u

Transformed coordinates in X dimension, returned as an array.

v

Transformed coordinates in Y dimension, returned as an array.

U

Transformed X and Y coordinates, returned as an n -by-2 matrix

images.geotrans.PiecewiseLinearTransformation2D.outputLimits

Class: images.geotrans.PiecewiseLinearTransformation2D

Package: images.geotrans

Find output limits of geometric transformation

Syntax

```
[xLimitsOut,yLimitsOut] = outputLimits(tform,xLimitsIn,yLimitsIn)
[xLimitsOut,yLimitsOut,zLimitsOut] =
outputLimits(tform,xLimitsIn,yLimitsIn,zLimitsIn)
```

Description

[xLimitsOut,yLimitsOut] = outputLimits(tform,xLimitsIn,yLimitsIn) estimates the output spatial limits corresponding to a given 2D geometric transformation and a set of input spatial limits.

[xLimitsOut,yLimitsOut,zLimitsOut] = outputLimits(tform,xLimitsIn,yLimitsIn,zLimitsIn) estimates the output spatial limits corresponding to a given 3D geometric transformation and a set of input spatial limits.

Input Arguments

tform

Geometric transformation, specified as an `images.geotrans.PiecewiseLinearTransformation2D` object.

xLimitsIn

Limits along the *X* axes, specified as a two-element vector, such as [].

yLimitsIn

Limits along the *Y* axes, specified as a two-element vector, such as [].

zLimitsIn

Limits along the Z axes, specified as a two-element vector, such as [].

Output Arguments

xLimitsOut

Actual limits along the X dimension, returned as an array.

yLimitsOut

Actual limits along the Y dimension, returned as an array.

zLimitsOut

Actual limits along the Z dimension, returned as an array.

poly2mask

Convert region of interest (ROI) polygon to region mask

Syntax

```
BW = poly2mask(x, y, m, n)
```

Description

`BW = poly2mask(x, y, m, n)` computes a binary region of interest (ROI) mask, `BW`, from an ROI polygon, represented by the vectors `x` and `y`. The size of `BW` is `m`-by-`n`. `poly2mask` sets pixels in `BW` that are inside the polygon (`X, Y`) to 1 and sets pixels outside the polygon to 0.

`poly2mask` closes the polygon automatically if it isn't already closed.

Note on Rectangular Polygons

When the input polygon goes through the middle of a pixel, sometimes the pixel is determined to be inside the polygon and sometimes it is determined to be outside (see Algorithm for details). To specify a polygon that includes a given rectangular set of pixels, make the edges of the polygon lie along the outside edges of the bounding pixels, instead of the center of the pixels.

For example, to include pixels in columns 4 through 10 and rows 4 through 10, you might specify the polygon vertices like this:

```
x = [4 10 10 4 4];  
y = [4 4 10 10 4];  
mask = poly2mask(x,y,12,12)
```

mask =

```
0 0 0 0 0 0 0 0 0 0 0 0  
0 0 0 0 0 0 0 0 0 0 0 0  
0 0 0 0 0 0 0 0 0 0 0 0  
0 0 0 0 0 0 0 0 0 0 0 0  
0 0 0 0 1 1 1 1 1 1 0 0
```

```

0  0  0  0  1  1  1  1  1  1  0  0
0  0  0  0  1  1  1  1  1  1  0  0
0  0  0  0  1  1  1  1  1  1  0  0
0  0  0  0  1  1  1  1  1  1  0  0
0  0  0  0  1  1  1  1  1  1  0  0
0  0  0  0  0  0  0  0  0  0  0  0
0  0  0  0  0  0  0  0  0  0  0  0

```

In this example, the polygon goes through the center of the bounding pixels, with the result that only some of the desired bounding pixels are determined to be inside the polygon (the pixels in row 4 and column 4 and not in the polygon). To include these elements in the polygon, use fractional values to specify the outside edge of the 4th row (3.5) and the 10th row (10.5), and the outside edge of the 4th column (3.5) and the outside edge of the 10th column (10.5) as vertices, as in the following example:

```

x = [3.5 10.5 10.5 3.5 3.5];
y = [3.5 3.5 10.5 10.5 3.5];
mask = poly2mask(x,y,12,12)

```

mask =

```

0  0  0  0  0  0  0  0  0  0  0  0
0  0  0  0  0  0  0  0  0  0  0  0
0  0  0  0  0  0  0  0  0  0  0  0
0  0  0  1  1  1  1  1  1  1  0  0
0  0  0  1  1  1  1  1  1  1  0  0
0  0  0  1  1  1  1  1  1  1  0  0
0  0  0  1  1  1  1  1  1  1  0  0
0  0  0  1  1  1  1  1  1  1  0  0
0  0  0  1  1  1  1  1  1  1  0  0
0  0  0  0  0  0  0  0  0  0  0  0
0  0  0  0  0  0  0  0  0  0  0  0

```

Class Support

The class of BW is `logical`

Examples

```

x = [63 186 54 190 63];
y = [60 60 209 204 60];
bw = poly2mask(x,y,256,256);
imshow(bw)
hold on

```

```
plot(x,y,'b','LineWidth',2)
hold off
```


Create a mask using random points.

```
x = 256*rand(1,4);
y = 256*rand(1,4);
x(end+1) = x(1);
y(end+1) = y(1);
bw = poly2mask(x,y,256,256);
imshow(bw)
hold on
plot(x,y,'b','LineWidth',2)
hold off
```

More About

Algorithms

When creating a region of interest (ROI) mask, `poly2mask` must determine which pixels are included in the region. This determination can be difficult when pixels on the edge of a region are only partially covered by the border line. The following figure illustrates a triangular region of interest, examining in close-up one of the vertices of the ROI. The figure shows how pixels can be partially covered by the border of a region-of-interest.




Pixels on the Edge of an ROI Are Only Partially Covered by Border

To determine which pixels are in the region, `poly2mask` uses the following algorithm:

- 1** Divide each pixel (unit square) into a 5-by-5 grid. See “Dividing Pixels into a 5-by-5 Subpixel Grid” on page 1-1336 for an illustration.
- 2** Adjust the position of the vertices to be on the intersections of the subpixel grid. See “Adjusting the Vertices to the Subpixel Grid” on page 1-1336 for an illustration.
- 3** Draw a path from each adjusted vertex to the next, following the edges of the subpixel grid. See “Drawing a Path Between the Adjusted Vertices” on page 1-1337 for an illustration.
- 4** Determine which border pixels are inside the polygon using this rule: if a pixel's central subpixel is inside the boundaries defined by the path between adjusted vertices, the pixel is considered inside the polygon. See “Determining Which Pixels Are in the Region” on page 1-1337 for an illustration.


Dividing Pixels into a 5-by-5 Subpixel Grid

The following figure shows the pixel that contains the vertex of the ROI shown previously with this 5-by-5 subpixel grid.




Adjusting the Vertices to the Subpixel Grid

`poly2mask` adjusts each vertex of the polygon so that the vertex lies on the subpixel grid. Note how `poly2mask` rounds up x and y coordinates to find the nearest grid corner. This creates a second, modified polygon, slightly smaller, in this case, than the original ROI. A portion is shown in the following figure.



Drawing a Path Between the Adjusted Vertices


poly2mask forms a path from each adjusted vertex to the next, following the edges of the subpixel grid. In the following figure, a portion of this modified polygon is shown by the thick dark lines.



Determining Which Pixels Are in the Region

poly2mask uses the following rule to determine which border pixels are inside the polygon: if the pixel's central subpixel is inside the modified polygon, the pixel is inside the region.

In the following figure, the central subpixels of pixels on the ROI border are shaded a dark gray color. Pixels inside the polygon are shaded a lighter gray. Note that the pixel containing the vertex is not part of the ROI because its center pixel is not inside the modified polygon.



See Also

roipoly

Introduced before R2006a

images.geotrans.PolynomialTransformation2D class

Package: images.geotrans

2-D Polynomial Geometric Transformation

Description

An `images.geotrans.PolynomialTransformation2D` object encapsulates a 2-D polynomial geometric transformation.

Construction

`tform = images.geotrans.PolynomialTransformation2D(movingPoints, fixedPoints, degree)` creates an `images.geotrans.PolynomialTransformation2D` object given m -by-2 matrices `movingPoints`, and `fixedPoints` which define matched control points in the moving and fixed images, respectively. `Degree` is a scalar with value 2, 3, or 4 that specifies the degree of the polynomial that is fit to the control points.

`tform = images.geotrans.PolynomialTransformation2D(A,B)` creates an `images.geotrans.PolynomialTransformation2D` object given polynomial coefficient vectors `A` and `B`. `A` is a vector of polynomial coefficients of length N that is used to determine U in the inverse transformation. `B` is a vector of polynomial coefficients of length N that is used to determine V in the inverse transformation. For polynomials of degree 2, 3, and 4, N is 6, 10, and 15, respectively.

Input Arguments

movingPoints — X and Y coordinates of control points in the image you want to transform
 m -by-2 double matrix

X and Y coordinates of control points in the image you want to transform, specified as an m -by-2 double matrix.

Example: `fixedPoints = [11 11; 41 71];`

Data Types: double

fixedPoints — *X* and *Y* coordinates of control points in the base image

m-by-2 double matrix

X and *Y* coordinates of control points in the base image, specified as an *m*-by-2 double matrix.

Example: `movingPoints = [14 44; 70 81];`

Data Types: double

A — Polynomial coefficients used to determine *U* in the inverse transformation

double vector

Polynomial coefficients used to determine *U* in inverse transformation, specified as a double vector of length *N*. For polynomials of degree 2, 3, and 4, *N* is 6, 10, and 15, respectively. The polynomial coefficient vector *A* is ordered as follows:

$$U = A(1) + A(2) \cdot X + A(3) \cdot Y + A(4) \cdot X \cdot Y + A(5) \cdot X.^2 + A(6) \cdot Y.^2 + \dots$$

B — Polynomial coefficients used to determine *V* in inverse transformation

double vector

Polynomial coefficients used to determine *V* in the inverse transformation, specified as a double vector of length *N*. For polynomials of degree 2, 3, and 4, *N* is 6, 10, and 15, respectively. The polynomial coefficient vector *B* is ordered as follows:

$$V = B(1) + B(2) \cdot X + B(3) \cdot Y + B(4) \cdot X \cdot Y + B(5) \cdot X.^2 + B(6) \cdot Y.^2 + \dots$$

Degree — Degree of the polynomial transformation

2 | 3 | 4

Degree of the polynomial transformation, specified as the scalar values 2, 3, or 4.

Properties

Dimensionality

Dimensionality of geometric transformation

Describes the dimensionality of the geometric transformation for both input and output points.

Methods

<code>transformPointsInverse</code>	Apply inverse 2-D geometric transformation to points
<code>outputLimits</code>	Apply inverse 2-D geometric transformation to points

Copy Semantics

Value. To learn how value classes affect copy operations, see Copying Objects in the MATLAB documentation.

Examples

Fit a second degree polynomial transformation to a set of fixed and moving control points

Fit a second degree polynomial transformation to a set of fixed and moving control points that are actually related by an 2D affine transformation.

Create 2D affine transformation.

```
theta = 10;
tformAffine = affine2d([cosd(theta) -sind(theta) 0; sind(theta) cosd(theta) 0; 0 0 1]);
```

Arbitrarily choose six pairs of control points. A second degree polynomial requires six pairs of control points.

```
fixedPoints = [10 20; 10 5; 2 3; 0 5; -5 3; -10 -20];
```

Apply forward geometric transformation to map fixed points to obtain effect of fixed and moving points that are related by some geometric transformation.

```
movingPoints = transformPointsForward(tformAffine, fixedPoints);
```

Estimate second degree `PolynomialTransformation2D` transformation that fits `fixedPoints` and `movingPoints`.

```
tformPolynomial = images.geotrans.PolynomialTransformation2D(movingPoints, fixedPoints, 2);
```

Verify the fit of our `PolynomialTransformation2D` transformation at the control points.

```
movingPointsEstimated = transformPointsInverse(tformPolynomial, fixedPoints);  
errorInFit = hypot(movingPointsEstimated(:,1)-movingPoints(:,1), ...  
                  movingPointsEstimated(:,2)-movingPoints(:,2))
```

See Also

`images.geotrans.PiecewiseLinearTransformation2D` | `fitgeotrans` | `imwarp`

images.geotrans.PolynomialTransformation2d.transformPointsInverse

Apply inverse 2-D geometric transformation to points

Syntax

```
[u,v] = transformPointsInverse(tform,x,y)
U = transformPointsInverse(tform,X)
```

Description

`[u,v] = transformPointsInverse(tform,x,y)` applies the inverse transformation of `tform` to the input 2-D point arrays `x` and `y` and outputs the point arrays `u` and `v`. The input point arrays `x` and `y` must be of the same size.

`U = transformPointsInverse(tform,X)` applies the inverse transformation of `tform` to the input n -by-2 point matrix `X` and outputs the n -by-2 point matrix `U`. `transformPointsInverse` maps the point `X(k, :)` to the point `U(k, :)`.

Input Arguments

tform

Geometric transformation, specified as an `projective2d` geometric transformation object.

x

Coordinates in X dimension of points to be transformed, specified as a array.

y

Coordinates in Y dimension of points to be transformed, specified as a array.

X

X and Y coordinates of points to be transformed, specified as an n -by-2 matrix

Output Arguments

u

Transformed coordinates in X dimension, returned as an array.

v

Transformed coordinates in Y dimension, returned as an array.

U

Transformed X and Y coordinates, returned as an n -by-2 matrix

images.geotrans.PolynomialTransformation2d.outputLimits

Apply inverse 2-D geometric transformation to points

Syntax

```
[xLimitsOut,yLimitsOut] = outputLimits(tform,xLimitsIn,yLimitsIn)
[xLimitsOut,yLimitsOut,zLimitsOut] =
outputLimits(tform,xLimitsIn,yLimitsIn,zLimitsIn)
```

Description

`[xLimitsOut,yLimitsOut] = outputLimits(tform,xLimitsIn,yLimitsIn)` estimates the output spatial limits corresponding to a given 2D geometric transformation and a set of input spatial limits.

`[xLimitsOut,yLimitsOut,zLimitsOut] = outputLimits(tform,xLimitsIn,yLimitsIn,zLimitsIn)` estimates the output spatial limits corresponding to a given 3D geometric transformation and a set of input spatial limits.

Input Arguments

tform

Geometric transformation, specified as an `images.geotrans.PolynomialTransformation2D` object.

xLimitsIn

Limits along the *X* axes, specified as a two-element vector, such as `[]`.

yLimitsIn

Limits along the *Y* axes, specified as a two-element vector, such as `[]`.

zLimitsIn

Limits along the Z axes, specified as a two-element vector, such as `[]`.

Output Arguments

xLimitsOut

Actual limits along the X dimension, returned as an array.

yLimitsOut

Actual limits along the Y dimension, returned as an array.

zLimitsOut

Actual limits along the Z dimension, returned as an array.

projective2d class

2-D Projective Geometric Transformation

Description

A `projective2d` object encapsulates a 2-D projective geometric transformation.

“Code Generation” on page 1-1350 support: Yes.

“MATLAB Function Block” on page 1-1350 support: Yes.

Construction

`tform = projective2d()` creates a `projective2d` object with default property settings that correspond to the identity transformation.

`tform = projective2d(A)` creates a `projective2d` object given an input 3-by-3 matrix `A` that specifies a valid projective transformation.

Input Arguments

A

3-by-3 matrix that specifies a valid projective transformation of the form:

$$A = \begin{bmatrix} a & b & c; \\ d & e & f; \\ g & h & i \end{bmatrix}$$

Default: Identity transformation

Properties

T

3-by-3 double-precision, floating point matrix that defines the 2-D forward projective transformation.

The matrix T uses the convention:

$$[x \ y \ 1] = [u \ v \ 1] * T$$

where T has the form:

```
[a b c;...  
 d e f;...  
 g h i];
```

Dimensionality

Describes the dimensionality of the geometric transformation for both input and output points.

Methods

invert	Invert geometric transformation
outputLimits	Find output spatial limits given input spatial limits
transformPointsForward	Apply forward geometric transformation
transformPointsInverse	Apply inverse 2-D geometric transformation to points

Copy Semantics

Value. To learn how value classes affect copy operations, see [Copying Objects in the MATLAB documentation](#).

Examples

Create a Projective2d Object

Create a projective2d object that defines the transformation.

```
theta = 10;  
tform = projective2d([cosd(theta) -sind(theta) 0.001; sind(theta) cosd(theta) 0.01; 0 0 1]);  
tform =
```

```
projective2d with properties:
```

```
          T: [3x3 double]  
Dimensionality: 2
```

Apply forward geometric transformation to an input point.

```
[X,Y] = transformPointsForward(tform,5,10)
```

```
X =
```

```
6.0276
```

```
Y =
```

```
8.1265
```

Apply inverse geometric transformation to output point from previous step to recover the point we started with.

```
[U,V] = transformPointsInverse(tform,X,Y)
```

```
U =
```

```
5.0000
```

```
V =
```

```
10
```

Apply Projective Transformation to Image Using the `imwarp` Function

Read image.

```
A = imread('pout.tif');
```


Create geometric transformation object.

```
theta = 10;
```

```
tform = projective2d([cosd(theta) -sind(theta) 0.001; sind(theta) cosd(theta) 0.01; 0 0 1]);
```

Apply transformation and view image.

```
outputImage = imwarp(A,tform);  
figure, imshow(outputImage);
```



Additional Capabilities

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, you can only specify singular objects—arrays of objects are not supported.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

invert

Class: projective2d

Invert geometric transformation

Syntax

```
invtfom = invert(tform)
```

Description

`invtfom = invert(tform)` inverts the geometric transformation `tform` and returns the inverse geometric transform.

Input Arguments

tform

Geometric transformation, specified as an `projective2d` geometric transformation object.

Output Arguments

invtfom

Inverse of the geometric transformation, returned as an `projective2d` geometric transformation object

Examples

Invert Geometric Transformation Object

Create a `projective2d` object that defines a transformation.

```
theta = 10;  
tform = projective2d([cosd(theta) -sind(theta) 0.001; sind(theta) cosd(theta) 0.01; 0 0 1]);  
invtform =
```

```
projective2d with properties:  
          T: [3x3 double]  
Dimensionality: 2
```

Invert the geometric transformation.

```
invtform = invert(tform)  
invtform =  
projective2d with properties:  
          T: [3x3 double]  
Dimensionality: 2
```

outputLimits

Class: projective2d

Find output spatial limits given input spatial limits

Syntax

```
[xLimitsOut,yLimitsOut] = outputLimits(tform,xLimitsIn,yLimitsIn)
```

Description

```
[xLimitsOut,yLimitsOut] = outputLimits(tform,xLimitsIn,yLimitsIn)
```

estimates the output spatial limits corresponding to a given geometric transformation, `tform`, and a set of input spatial limits.

Input Arguments

tform

Geometric transformation, specified as an `projective2d` geometric transformation object.

xLimitsIn

Input spatial limits in X dimension, specified as a two-element vector of doubles.

yLimitsIn

Input spatial limits in Y dimension, specified as a two-element vector of doubles.

Output Arguments

xLimitsOut

Output spatial limits in X dimension, returned as a two-element vector of doubles.

yLimitsOut

Output spatial limits in Y dimension, returned as a two-element vector of **doubles**.

Examples

Estimate the Output Limits for a Geometric Transformation

Create an `projective2d` object that defines a transformation.

```
theta = 10;  
tform = affine2d([cosd(theta) -sind(theta) 0; sind(theta) cosd(theta) 0; 0 0 1]);  
tform =
```

```
    affine2d with properties:
```

```
                T: [3x3 double]  
    Dimensionality: 2
```

Estimate the output spatial limits, given the geometric transformation.

```
[xlim ylim] = outputLimits(tform,[1 240],[1 291])
```

```
xlim =
```

```
    1.1459    189.2220
```

```
ylim =
```

```
   -32.5526    73.2307
```


transformPointsForward

Class: projective2d

Apply forward geometric transformation

Syntax

```
[x,y] = transformPointsForward(tform,u,v)  
X = transformPointsForward(tform,U)
```

Description

`[x,y] = transformPointsForward(tform,u,v)` applies the forward transformation of `tform` to the input 2-D point arrays `u` and `v` and returns the point arrays `x` and `y`. The input point arrays `u` and `v` must be of the same size.

`X = transformPointsForward(tform,U)` applies the forward transformation of `tform` to the input n -by-2 point matrix `U` and outputs the n -by-2 point matrix `X`. `transformPointsForward` maps the point `U(k,:)` to the point `X(k,:)`.

Input Arguments

tform

Geometric transformation, specified as an `projective2d` geometric transformation object.

u

Coordinates in X dimension of points to be transformed, specified as an array.

v

Coordinates in Y dimension of points to be transformed, specified as an array.

U

X and Y coordinates of points to be transformed, specified as an n -by-2 matrix

Output Arguments

x

Transformed coordinates in X dimension, returned as a array.

y

Transformed coordinates in Y dimension, returned as a array.

X

Transformed points in X and Y dimensions, returned as an n -by-2 point matrix

Examples

Apply Forward Geometric Transformation

Create an `projective2d` object that defines the transformation.

```
theta = 10;  
tform = projective2d([cosd(theta) -sind(theta) 0.001; sind(theta) cosd(theta) 0.01; 0 0 1]);  
tform =
```

```
projective2d with properties:
```

```
          T: [3x3 double]  
Dimensionality: 2
```

Apply forward geometric transformation to an input point.

```
[X,Y] = transformPointsForward(tform,5,10)
```

```
X =
```

```
6.0276
```

Y =

8.1265

transformPointsInverse

Class: projective2d

Apply inverse 2-D geometric transformation to points

Syntax

```
[u,v] = transformPointsInverse(tform,x,y)  
U = transformPointsInverse(tform,X)
```

Description

`[u,v] = transformPointsInverse(tform,x,y)` applies the inverse transformation of `tform` to the input 2-D point arrays `x` and `y` and outputs the point arrays `u` and `v`. The input point arrays `x` and `y` must be of the same size.

`U = transformPointsInverse(tform,X)` applies the inverse transformation of `tform` to the input n -by-2 point matrix `X` and outputs the n -by-2 point matrix `U`. `transformPointsFoward` maps the point `X(k, :)` to the point `U(k, :)`.

Input Arguments

tform

Geometric transformation, specified as an `projective2d` geometric transformation object.

x

Coordinates in X dimension of points to be transformed, specified as a array.

y

Coordinates in Y dimension of points to be transformed, specified as a array.

X

X and Y coordinates of points to be transformed, specified as an n -by-2 matrix

Output Arguments

u

Transformed coordinates in X dimension, returned as an array.

v

Transformed coordinates in Y dimension, returned as an array.

U

Transformed X and Y coordinates, returned as an n -by-2 matrix

Examples

Apply Inverse Geometric Transformation

Create an `projective2d` object that defines the transformation.

```
theta = 10;
tform = projective2d([cosd(theta) -sind(theta) 0.001; sind(theta) cosd(theta) 0.01; 0 0 1]);
tform =
```

```
projective2d with properties:
```

```
          T: [3x3 double]
Dimensionality: 2
```

Apply forward geometric transformation to an input point.

```
[X,Y] = transformPointsForward(tform,5,10)
```

```
X =
```

```
    6.0276
```

Y =

8.1265

Apply inverse geometric transformation to output point from the previous step to recover the original coordinates.

```
[U,V] = transformPointsInverse(tform,X,Y)
```

U =

5.0000

V =

10

psf2otf

Convert point-spread function to optical transfer function

Syntax

```
OTF = psf2otf(PSF)
OTF = psf2otf(PSF,OUTSIZE)
```

Description

`OTF = psf2otf(PSF)` computes the fast Fourier transform (FFT) of the point-spread function (PSF) array and creates the optical transfer function array, `OTF`, that is not influenced by the PSF off-centering. By default, the `OTF` array is the same size as the `PSF` array.

`OTF = psf2otf(PSF,OUTSIZE)` converts the `PSF` array into an `OTF` array, where `OUTSIZE` specifies the size of the `OTF` array. `OUTSIZE` cannot be smaller than the `PSF` array size in any dimension.

To ensure that the `OTF` is not altered because of `PSF` off-centering, `psf2otf` postpads the `PSF` array (down or to the right) with 0's to match dimensions specified in `OUTSIZE`, then circularly shifts the values of the `PSF` array up (or to the left) until the central pixel reaches (1,1) position.

Note that this function is used in image convolution/deconvolution when the operations involve the FFT.

Class Support

`PSF` can be any nonsparse, numeric array. `OTF` is of class `double`.

Examples

```
PSF = fspecial('gaussian',13,1);
```

```
OTF = psf2otf(PSF,[31 31]); % PSF --> OTF
subplot(1,2,1); surf(PSF); title('PSF');
axis square; axis tight
subplot(1,2,2); surf(abs(OTF)); title('Corresponding |OTF|');
axis square; axis tight
```

See Also

[otf2psf](#) | [circshift](#) | [padarray](#)

Introduced before R2006a

psnr

Peak Signal-to-Noise Ratio (PSNR)

Syntax

```
peaksnr = psnr(A,ref)
peaksnr = psnr(A,ref,peakval)
[peaksnr,snr] = psnr( ___ )
```

Description

`peaksnr = psnr(A,ref)` calculates the peak signal-to-noise ratio for the image `A`, with the image `ref` as the reference. `A` and `ref` must be of the same size and class.

`peaksnr = psnr(A,ref,peakval)` uses `peakval` as the peak signal value for calculating the peak signal-to-noise ratio for image `A`.

`[peaksnr,snr] = psnr(___)` returns the simple signal-to-noise ratio, `snr`, in addition to the peak signal-to-noise ratio.

“Code Generation” on page 1-1365 support: Yes.

“MATLAB Function Block” on page 1-1365 support: Yes.

Examples

Calculate PSNR for Noisy Image Given Original Image as Reference

Read image and create a copy with added noise. The original image is the reference image.

```
ref = imread('pout.tif');
A = imnoise(ref,'salt & pepper', 0.02);
```

Calculate the PSNR.

```
[peaksnr, snr] = psnr(A, ref);  
  
fprintf('\n The Peak-SNR value is %0.4f', peaksnr);  
fprintf('\n The SNR value is %0.4f \n', snr);
```

```
The Peak-SNR value is 22.6437  
The SNR value is 15.5524
```

Input Arguments

A — Image to be analyzed

N-D numeric matrix

Image to be analyzed, specified as an N-D numeric matrix.

Data Types: `single` | `double` | `int16` | `uint8` | `uint16`

ref — Reference image

N-D numeric matrix

Reference image, specified as an N-D numeric matrix.

Data Types: `single` | `double` | `int16` | `uint8` | `uint16`

peakval — Peak signal level

scalar of any numeric class

Peak signal level, specified as a scalar of any numeric class. If not specified, the default value for `peakval` depends on the class of `A` and `ref`. If the images are of floating point types, `peakval` is 1, assuming that the data is in the range `[0 1]`. If the images are of integer data types, `peakval` is the largest value allowed by the range of the class. For `uint8`, the default value is 255. For `uint16` or `int16`, the default is 65535.

Data Types: `single` | `double` | `int16` | `uint8` | `uint16`

Output Arguments

peaksnr — Peak signal-to-noise ratio

scalar

Peak signal-to-noise ratio in decibels, returned as a scalar of type `double`, except if `A` and `ref` are of class `single`, in which case `peaksnr` is of class `single`.

Data Types: `single` | `double`

snr — Signal-to-noise ratio

scalar

Signal-to-noise ratio in decibels, returned as a scalar of type `double`, except if `A` and `ref` are of class `single`, in which case `peaksnr` is of class `single`.

Data Types: `single` | `double`

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

Algorithms

The `psnr` function implements the following equation to calculate the Peak Signal-to-Noise Ratio (PSNR):

$$PSNR = 10 \log_{10} \left(\frac{peakval^2}{MSE} \right)$$

where *peakval* is either specified by the user or taken from the range of the image datatype (e.g. for `uint8` image it is 255). *MSE* is the mean square error, i.e. *MSE* between `A` and `ref`.

- “Image Quality Metrics”

See Also

`immse` | `mean` | `median` | `ssim` | `sum` | `var`

Introduced in R2014a

qtdecomp

Quadtree decomposition

Syntax

```
S = qtdecomp(I)
S = qtdecomp(I, threshold)
S = qtdecomp(I, threshold, mindim)
S = qtdecomp(I, threshold, [mindim maxdim])
S = qtdecomp(I, fun)
```

Description

`qtdecomp` divides a square image into four equal-sized square blocks, and then tests each block to see if it meets some criterion of homogeneity. If a block meets the criterion, it is not divided any further. If it does not meet the criterion, it is subdivided again into four blocks, and the test criterion is applied to those blocks. This process is repeated iteratively until each block meets the criterion. The result can have blocks of several different sizes.

`S = qtdecomp(I)` performs a quadtree decomposition on the intensity image `I` and returns the quadtree structure in the sparse matrix `S`. If `S(k,m)` is nonzero, then `(k,m)` is the upper left corner of a block in the decomposition, and the size of the block is given by `S(k,m)`. By default, `qtdecomp` splits a block unless all elements in the block are equal.

`S = qtdecomp(I, threshold)` splits a block if the maximum value of the block elements minus the minimum value of the block elements is greater than `threshold`. `threshold` is specified as a value between 0 and 1, even if `I` is of class `uint8` or `uint16`. If `I` is `uint8`, the threshold value you supply is multiplied by 255 to determine the actual threshold to use; if `I` is `uint16`, the threshold value you supply is multiplied by 65535.

`S = qtdecomp(I, threshold, mindim)` will not produce blocks smaller than `mindim`, even if the resulting blocks do not meet the threshold condition.

`S = qtdecomp(I, threshold, [mindim maxdim])` will not produce blocks smaller than `mindim` or larger than `maxdim`. Blocks larger than `maxdim` are split even if they meet the threshold condition. `maxdim/mindim` must be a power of 2.

`S = qtdecomp(I, fun)` uses the function `fun` to determine whether to split a block. `qtdecomp` calls `fun` with all the current blocks of size `m`-by-`m` stacked into an `m`-by-`m`-by-`k` array, where `k` is the number of `m`-by-`m` blocks. `fun` returns a logical `k`-element vector, whose values are 1 if the corresponding block should be split, and 0 otherwise. (For example, if `k(3)` is 0, the third `m`-by-`m` block should not be split.) `fun` must be a function handle.

Class Support

For the syntaxes that do not include a function, the input image can be of class `logical`, `uint8`, `uint16`, `int16`, `single`, or `double`. For the syntaxes that include a function, the input image can be of any class supported by the function. The output matrix is always of class `sparse`.

Examples

```
I = uint8([1 1 1 1 2 3 6 6;...
          1 1 2 1 4 5 6 8;...
          1 1 1 1 7 7 7 7;...
          1 1 1 1 6 6 5 5;...
          20 22 20 22 1 2 3 4;...
          20 22 22 20 5 4 7 8;...
          20 22 20 20 9 12 40 12;...
          20 22 20 20 13 14 15 16]);
```

```
S = qtdecomp(I, .05);
disp(full(S));
```

View the block representation of quadtree decomposition.

```
I = imread('liftingbody.png');
S = qtdecomp(I, .27);
blocks = repmat(uint8(0), size(S));

for dim = [512 256 128 64 32 16 8 4 2 1];
    numblocks = length(find(S==dim));
    if (numblocks > 0)
        values = repmat(uint8(1), [dim dim numblocks]);
        values(2:dim, 2:dim, :) = 0;
        blocks = qtsetblk(blocks, S, dim, values);
    end
end
```

```
end
end

blocks(end,1:end) = 1;
blocks(1:end,end) = 1;

imshow(I), figure, imshow(blocks,[])
```

The following figure shows the original image and a representation of the quadtree decomposition of the image.




Image courtesy of NASA

More About

Tips

`qtdecomp` is appropriate primarily for square images whose dimensions are a power of 2, such as 128-by-128 or 512-by-512. These images can be divided until the blocks are as small as 1-by-1. If you use `qtdecomp` with an image whose dimensions are not a power of 2, at some point the blocks cannot be divided further. For example, if an image is 96-by-96, it can be divided into blocks of size 48-by-48, then 24-by-24, 12-by-12, 6-by-6, and finally 3-by-3. No further division beyond 3-by-3 is possible. To process this image,

you must set `mindim` to 3 (or to 3 times a power of 2); if you are using the syntax that includes a function, the function must return 0 at the point when the block cannot be divided further.

- “Anonymous Functions”
- “Parameterizing Functions”
- “Create Function Handle”

See Also

`qtgetblk` | `qtsetblk`

Introduced before R2006a

qtgetblk

Block values in quadtree decomposition

Syntax

```
[vals, r, c] = qtgetblk(I, S, dim)
[vals, idx] = qtgetblk(I, S, dim)
```

Description

`[vals, r, c] = qtgetblk(I, S, dim)` returns in `vals` an array containing the `dim`-by-`dim` blocks in the quadtree decomposition of `I`. `S` is the sparse matrix returned by `qtdecomp`; it contains the quadtree structure. `vals` is a `dim`-by-`dim`-by-`k` array, where `k` is the number of `dim`-by-`dim` blocks in the quadtree decomposition; if there are no blocks of the specified size, all outputs are returned as empty matrices. `r` and `c` are vectors containing the row and column coordinates of the upper left corners of the blocks.

`[vals, idx] = qtgetblk(I, S, dim)` returns in `idx` a vector containing the linear indices of the upper left corners of the blocks.

Class Support

`I` can be of class `logical`, `uint8`, `uint16`, `int16`, `single`, or `double`. `S` is of class `sparse`.

Examples

```
I = [1  1  1  1  2  3  6  6
      1  1  2  1  4  5  6  8
      1  1  1  1 10 15  7  7
      1  1  1  1 20 25  7  7
     20 22 20 22  1  2  3  4
     20 22 22 20  5  6  7  8
     20 22 20 20  9 10 11 12]
```

```
    22    22    20    20    13    14    15    16];  
S = qtdecomp(I,5);  
[vals,r,c] = qtgetblk(I,S,4)
```

More About

Tips

The ordering of the blocks in `vals` matches the columnwise order of the blocks in `I`. For example, if `vals` is 4-by-4-by-2, `vals(:, :, 1)` contains the values from the first 4-by-4 block in `I`, and `vals(:, :, 2)` contains the values from the second 4-by-4 block.

See Also

`qtdecomp` | `qtsetblk`

Introduced before R2006a

qtsetblk

Set block values in quadtree decomposition

Syntax

```
J = qtsetblk(I, S, dim, vals)
```

Description

`J = qtsetblk(I, S, dim, vals)` replaces each `dim-by-dim` block in the quadtree decomposition of `I` with the corresponding `dim-by-dim` block in `vals`. `S` is the sparse matrix returned by `qtdecomp`; it contains the quadtree structure. `vals` is a `dim-by-dim-by-k` array, where `k` is the number of `dim-by-dim` blocks in the quadtree decomposition.

Class Support

`I` can be of class `logical`, `uint8`, `uint16`, `int16`, `single`, or `double`. `S` is of class `sparse`.

Examples

```
I = [1    1    1    1    2    3    6    6
      1    1    2    1    4    5    6    8
      1    1    1    1   10   15    7    7
      1    1    1    1   20   25    7    7
     20   22   20   22    1    2    3    4
     20   22   22   20    5    6    7    8
     20   22   20   20    9   10   11   12
     22   22   20   20   13   14   15   16];
```

```
S = qtdecomp(I,5);
```

```
newvals = cat(3,zeros(4),ones(4));
J = qtsetblk(I,S,4,newvals)
```

More About

Tips

The ordering of the blocks in `vals` must match the columnwise order of the blocks in `I`. For example, if `vals` is 4-by-4-by-2, `vals(:, :, 1)` contains the values used to replace the first 4-by-4 block in `I`, and `vals(:, :, 2)` contains the values for the second 4-by-4 block.

See Also

`qtdecomp` | `qtgetblk`

Introduced before R2006a

radon

Radon transform

Syntax

```
R = radon(I, theta)
[R, xp] = radon(...)
[ ___ ]= radon(gpuarrayI, theta)
```

Description

`R = radon(I, theta)` returns the Radon transform **R** of the intensity image **I** for the angle **theta** degrees.

The Radon transform is the projection of the image intensity along a radial line oriented at a specific angle. If **theta** is a scalar, **R** is a column vector containing the Radon transform for **theta** degrees. If **theta** is a vector, **R** is a matrix in which each column is the Radon transform for one of the angles in **theta**. If you omit **theta**, it defaults to 0:179.

`[R, xp] = radon(...)` returns a vector **xp** containing the radial coordinates corresponding to each row of **R**.

The radial coordinates returned in **xp** are the values along the x' -axis, which is oriented at **theta** degrees counterclockwise from the x -axis. The origin of both axes is the center pixel of the image, which is defined as

```
floor((size(I)+1)/2)
```

For example, in a 20-by-30 image, the center pixel is (10,15).

`[___]= radon(gpuarrayI, theta)` performs the Radon transform on a GPU. The input image and the return values are 2-D `gpuArrays`. **theta** can be a `double` or `gpuArray` of underlying class `double`. This syntax requires the Parallel Computing Toolbox.

Class Support

I can be of class `double`, `logical`, or any integer class. All other inputs and outputs are of class `double`. Neither of the inputs can be sparse.


`gpuarrayI` is a `gpuArray` with underlying class `uint8`, `uint16`, `uint32`, `int8`, `int16`, `int32`, `logical`, `single` or `double` and must be two-dimensional. `theta` is a `double` vector or `gpuArray` vector of underlying class `double`.

Examples

Calculate Radon Transform

Calculate Radon transform and visualize it.

```
iptsetpref('ImshowAxesVisible','on')
I = zeros(100,100);
I(25:75, 25:75) = 1;
theta = 0:180;
[R,xp] = radon(I,theta);
imshow(R,[],'Xdata',theta,'Ydata',xp,...
        'InitialMagnification','fit')
xlabel('\theta (degrees)')
ylabel('x')
colormap(hot), colorbar
iptsetpref('ImshowAxesVisible','off')
```



Calculate Radon transform on a GPU

Calculate Radon transform on a GPU and visualize it.

```

iptsetpref('ImshowAxesVisible','on')
I = zeros(100,100);
I(25:75, 25:75) = 1;
theta = 0:180;
[R,xp] = radon(gpuArray(I),theta);
imshow(R,[],'Xdata',theta,'Ydata',xp,...
        'InitialMagnification','fit')
xlabel('\theta (degrees)')
ylabel('x')
colormap(hot), colorbar
iptsetpref('ImshowAxesVisible','off')


```

More About

Algorithms

The Radon transform of an image is the sum of the Radon transforms of each individual pixel.

The algorithm first divides pixels in the image into four subpixels and projects each subpixel separately, as shown in the following figure.



Each subpixel's contribution is proportionally split into the two nearest bins, according to the distance between the projected location and the bin centers. If the subpixel projection hits the center point of a bin, the bin on the axes gets the full value of the subpixel, or one-fourth the value of the pixel. If the subpixel projection hits the border between two bins, the subpixel value is split evenly between the bins.

References

Bracewell, Ronald N., *Two-Dimensional Imaging*, Englewood Cliffs, NJ, Prentice Hall, 1995, pp. 505-537.

Lim, Jae S., *Two-Dimensional Signal and Image Processing*, Englewood Cliffs, NJ, Prentice Hall, 1990, pp. 42-45.

See Also

fan2para | fanbeam | ifanbeam | iradon | para2fan | phantom

Introduced before R2006a

rangefilt

Local range of image

Syntax

```
J = rangefilt(I)
J = rangefilt(I, NHOOD)
```

Description

`J = rangefilt(I)` returns the array `J`, where each output pixel contains the range value (maximum value – minimum value) of the 3-by-3 neighborhood around the corresponding pixel in the input image `I`. The image `I` can have any dimension. The output image `J` is the same size as the input image `I`.

`J = rangefilt(I, NHOOD)` performs range filtering of the input image `I` where you specify the neighborhood in `NHOOD`. `NHOOD` is a multidimensional array of zeros and ones where the nonzero elements specify the neighborhood for the range filtering operation. `NHOOD`'s size must be odd in each dimension.

By default, `rangefilt` uses the neighborhood `true(3)`. `rangefilt` determines the center element of the neighborhood by `floor((size(NHOOD) + 1)/2)`. For information about specifying neighborhoods, see Notes.

Class Support

`I` can be logical or numeric and must be real and nonsparse. `NHOOD` can be logical or numeric and must contain zeros or ones.

The output image `J` is the same class as `I`, except for signed integer data types. The output class for signed data types is the corresponding unsigned integer data type. For example, if the class of `I` is `int8`, then the class of `J` is `uint8`.

Notes


`rangefilt` uses the morphological functions `imdilate` and `imerode` to determine the maximum and minimum values in the specified neighborhood. Consequently, `rangefilt` uses the padding behavior of these morphological functions.


In addition, to specify neighborhoods of various shapes, such as a disk, use the `strel` function to create a structuring element object and then extract the neighborhood from the structuring element object's `neighborhood` property.

Examples

Identify Objects in 2-D Image

```
I = imread('liftingbody.png');  
J = rangefilt(I);  
imshow(I), figure, imshow(J);
```





Quantify Land Cover Changes in an RGB (3-D) Image

Read an image and convert color space from RGB to LAB.

```
I = imread('autumn.tif');  
cform = makecform('srgb2lab');
```

```
LAB = applycform(I, cform);
```



Perform the range filtering on the LAB image.


```
rLAB = rangefilt(LAB);
```

Display the images.

```
imshow(I);  
figure, imshow(rLAB(:,:,1),[]);  
figure, imshow(rLAB(:,:,2),[]);  
figure, imshow(rLAB(:,:,3),[]);
```







See Also

`entropyfilt` | `getnhood` | `imdilate` | `imerode` | `stdfilt` | `strel` | `offsetstrel`

Introduced before R2006a

regionfill

Fill in specified regions in image using inward interpolation

Syntax

```
J = regionfill(I,mask)
J = regionfill(I,x,y)
```

Description

`J = regionfill(I,mask)` fills the regions in image `I` specified by `mask`. Non-zero pixels in `mask` designate the pixels of image `I` to fill. You can use `regionfill` to remove objects in an image or to replace invalid pixel values using their neighbors.

`J = regionfill(I,x,y)` fills the region in image `I` corresponding to the polygon with vertices specified by `x` and `y`.

Examples

Fill Region in Grayscale Image

Read grayscale image into the workspace.

```
I = imread('eight.tif');
```

Specify a polygon that completely surrounds one of the coins in the image. This example uses the x-coordinates and y-coordinates (columns and rows) of the polygon vertices to specify the region.


```
x = [222 272 300 270 221 194];
y = [21 21 75 121 121 75];
```

Fill the polygon, using the `regionfill` function.

```
J = regionfill(I,x,y);
```

Display the original image and the filled image side-by-side.

```
figure
subplot(1,2,1)
imshow(I)
title('Original image')
subplot(1,2,2)
imshow(J)
title('Image with one less coin')
```



Fill Regions Using Mask Image

Read grayscale image into the workspace.

```
I = imread('eight.tif');
```

Create a mask image that covers all the coins.

```
mask = I < 200;
```

Fill holes in the mask image.

```
mask = imfill(mask,'holes');
```

Remove noise in the mask image.


```
mask = imerode(mask,strel('disk',10));  
mask = imdilate(mask,strel('disk',20));
```

Fill the regions in the input image using the mask image.

```
J = regionfill(I,mask);
```

Display the original image next to the mask image and the filled image.

```
figure  
subplot(1,3,1)  
imshow(I)  
title('Original image')  
subplot(1,3,2)  
imshow(mask)  
title('Mask of pixels to fill')  
subplot(1,3,3)  
imshow(J)  
title('Resulting image')
```



Input Arguments

I — Input grayscale image

2-D numeric array, nonsparse and real

Input grayscale image, specified as a 2-D numeric array, nonsparse and real. **I** must be greater than or equal to a 3-by-3 array.

Example: `I = imread('eight.tif');`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

mask — Mask binary image

nonsparse logical array

Mask binary image, specified as a nonsparse logical array the same size as `I`.

Data Types: `logical`

x — X-coordinates of polygon vertices

numeric vector

X-coordinates of polygon vertices, specified as a numeric vector of class `double`. Must be the same length as `y`.

Example: `x = [222 272 300 270 221 194];`

Data Types: `double`

y — Y-coordinates of polygon vertices

numeric vector

Y-coordinates of polygon vertices, specified as a numeric vector of class `double`. Must be the same length as `x`.

Example: `y = [21 21 75 121 121 75];`

Data Types: `double`

Output Arguments

J — Filled grayscale image

2-D numeric array, nonsparse and real

Filled grayscale image, returned as a 2-D numeric array, nonsparse, and real. `J` has the same size and class as `I`.

More About

Tips

- `regionfill` does not support the interactive syntax that `roifill` supports to specify a region of interest (ROI). To define an ROI interactively, use `roipoly` with `regionfill`.

Algorithms

`regionfill` smoothly interpolates inward from the pixel values on the outer boundary of the regions. `regionfill` computes the discrete Laplacian over the regions and solves the Dirichlet boundary value problem.

See Also

`imfill` | `impoly` | `poly2mask` | `roifilt2` | `roipoly`

Introduced in R2015a

regionprops

Measure properties of image regions

Syntax

```
stats = regionprops(BW,properties)
stats = regionprops(CC,properties)
stats = regionprops(L,properties)
stats = regionprops( ____,I,properties)
stats = regionprops(output, ____)
stats = regionprops(gpuarrayImg, ____)
```

Description

`stats = regionprops(BW,properties)` returns measurements for the set of properties specified by `properties` for each connected component (object) in the binary image, `BW`. `stats` is struct array containing a struct for each object in the image. You can use `regionprops` on contiguous regions and discontinuous regions (see “Algorithms” on page 1-1410).

`stats = regionprops(CC,properties)` returns measurements for the set of properties specified by `properties` for each connected component (object) in `CC`. `CC` is a structure returned by `bwconncomp`.

`stats = regionprops(L,properties)` returns measurements for the set of properties specified by `properties` for each labeled region in the label matrix `L`.

`stats = regionprops(____,I,properties)` returns measurements for the set of properties specified by `properties` for each labeled region in the image `I`. The first input to `regionprops` (`BW`, `CC`, or `L`) identifies the regions in `I`. The size of the first input must match the size of the image, that is, `size(I)` must equal `size(BW)`, `CC.ImageSize`, or `size(L)`.

`stats = regionprops(output, ____)` returns measurements for a set of properties, where `output` specifies the type of return value. `regionprops` can return these values in a `struct` or a `table`.

`stats = regionprops(gpuarrayImg, ___)` performs the measurements on a GPU. `gpuarrayImg` can be a 2-D binary image (logical `gpuArray`) or a `gpuArray` label matrix. The connected component structure (CC) returned by `bwconncomp` is not supported on the GPU.

When run on a GPU, `regionprops` does not support the following properties: 'ConvexArea', 'ConvexHull', 'ConvexImage', 'EulerNumber', 'FilledArea', 'FilledImage', and 'Solidity'.

“Code Generation” on page 1-1408 support: Yes.

MATLAB Function Block support: No.

Examples

Calculate Centroids and Superimpose Locations on Image

Read binary image into workspace.

```
BW = imread('text.png');
```

Calculate centroids for connected components in the image using `regionprops`.


```
s = regionprops(BW, 'centroid');
```

Concatenate structure array containing centroids into a single matrix.

```
centroids = cat(1, s.Centroid);
```

Display binary image with centroid locations superimposed.

```
imshow(BW)
hold on
plot(centroids(:,1),centroids(:,2), 'b*')
hold off
```

Calculate Centroids and Superimpose Locations on Image on a GPU

Read binary image into a gpuArray.

```
BW = gpuArray(imread('text.png'));
```

Calculate the centroids of objects in the image.

```
s = regionprops(BW, 'centroid');
```

Plot the centroids on the image.

```
centroids = cat(1, s.Centroid);  
imshow(BW)  
hold on  
plot(centroids(:,1), centroids(:,2), 'b*')
```

```
hold off
```

Estimate Center and Radii of Circular Objects and Plot Circles

Estimate the center and radii of circular objects in an image and use this information to plot circles on the image. In this example, `regionprops` returns the information it calculates in a table.


Read an image into workspace.

```
a = imread('circlesBrightDark.png');
```

Turn the input image into a binary image.

```
bw = a < 100;  
imshow(bw)  
title('Image with Circles')
```

Image with Circles



Calculate properties of regions in the image and return the data in a table.

```
stats = regionprops('table',bw,'Centroid',...  
    'MajorAxisLength','MinorAxisLength')
```

```
stats =
```

Centroid		MajorAxisLength	MinorAxisLength
_____		_____	_____
256.5	256.5	834.46	834.46
300	120	81.759	81.759
330.47	369.83	111.78	110.36
450	240	101.72	101.72


Get centers and radii of the circles.

```
centers = stats.Centroid;  
diameters = mean([stats.MajorAxisLength stats.MinorAxisLength],2);  
radii = diameters/2;
```

Plot the circles.

```
hold on  
viscircles(centers,radii);  
hold off
```

Image with Circles



Input Arguments

BW — Input binary image
logical array of any dimension

Input binary image, specified as a logical array of any dimension.

Example: `BW = imread('text.png'); s = regionprops(BW,'basic');`

Data Types: `logical`

properties — Type of measurement


`string` | comma-separated list of strings | cell array of strings | `'all'` | `'basic'`

Type of measurement, specified as a string, comma-separated list of strings, cell array of strings, or the string `'all'` or `'basic'`. Property name strings are case-insensitive and can be abbreviated. When used with code generation, `regionprops` does not support cell arrays of strings.



The following tables list all the properties that provide shape measurements. The properties listed in the Pixel Value Measurements table are only valid when you specify a grayscale image. If you specify `'all'`, `regionprops` computes all the shape measurements and, if you specified a grayscale image, the pixel value measurements. If you specify the string `'basic'`, or do not specify the `properties` argument, `regionprops` computes only the `'Area'`, `'Centroid'`, and `'BoundingBox'` measurements. You can calculate the following properties on N-D inputs: `'Area'`, `'BoundingBox'`, `'Centroid'`, `'FilledArea'`, `'FilledImage'`, `'Image'`, `'PixelIdxList'`, `'PixelList'`, and `'SubarrayIdx'`.

Shape Measurements


Property Name String	Description	N-D Support	GPU Support	Code Generation
<code>'Area'</code>	Returns a scalar that specifies the actual number of pixels in the region. (This value might differ slightly from the value returned by <code>bwarea</code> , which weights different patterns of pixels differently.)	Yes	Yes	Yes
<code>'BoundingBox'</code>	Returns the smallest rectangle containing the region, specified as a 1-by-Q*2 vector, where Q is the number of image dimensions, for example, <code>[ul_corner width]</code> . <code>ul_corner</code> specifies the upper-left corner of the bounding box in the form <code>[x y z ...]</code> . <code>width</code> specifies the width of the bounding box along each dimension in the form <code>[x_width y_width ...]</code> . <code>regionprops</code> uses <code>ndims</code> to get the dimensions of	Yes	Yes	Yes


Property Name String	Description	N-D Support	GPU Support	Code Generation
	label matrix or binary image, <code>ndims(L)</code> , and <code>numel</code> to get the dimensions of connected components, <code>numel(CC.ImageSize)</code> .			
'Centroid'	Returns a 1-by- <i>Q</i> vector that specifies the center of mass of the region. The first element of Centroid is the horizontal coordinate (or <i>x</i> -coordinate) of the center of mass, and the second element is the vertical coordinate (or <i>y</i> -coordinate). All other elements of Centroid are in order of dimension. This figure illustrates the centroid and bounding box for a discontinuous region. The region consists of the white pixels; the green box is the bounding box, and the red dot is the centroid. 	Yes	Yes	Yes
'ConvexArea'	Returns a scalar that specifies the number of pixels in 'ConvexImage'.	2-D only	No	No
'ConvexHull'	Returns a <i>p</i> -by-2 matrix that specifies the smallest convex polygon that can contain the region. Each row of the matrix contains the <i>x</i> - and <i>y</i> -coordinates of one vertex of the polygon.	2-D only	No	No
'ConvexImage'	Returns a binary image (logical) that specifies the convex hull, with all pixels within the hull filled in (set to on). The image is the size of the bounding box of the region. (For pixels that the boundary of the hull passes through, regionprops uses the same logic as roipoly to determine whether the pixel is inside or outside the hull.)	2-D only	No	No
'Eccentricity'	Returns a scalar that specifies the eccentricity of the ellipse that has the same second-moments as the region. The eccentricity is the ratio of the distance	2-D only	Yes	Yes

Property Name String	Description	N-D Support	GPU Support	Code Generation
	between the foci of the ellipse and its major axis length. The value is between 0 and 1. (0 and 1 are degenerate cases. An ellipse whose eccentricity is 0 is actually a circle, while an ellipse whose eccentricity is 1 is a line segment.)			
'EquivDia'	Returns a scalar that specifies the diameter of a circle with the same area as the region. Computed as $\sqrt{4 \cdot \text{Area} / \pi}$.	2-D only	Yes	Yes
'EulerNum'	Returns a scalar that specifies the number of objects in the region minus the number of holes in those objects. This property is supported only for 2-D label matrices. <code>regionprops</code> uses 8-connectivity to compute the Euler number measurement. To learn more about connectivity, see “Pixel Connectivity”.	Yes	No	Yes
'Extent'	Returns a scalar that specifies the ratio of pixels in the region to pixels in the total bounding box. Computed as the <code>Area</code> divided by the area of the bounding box.	2-D only	Yes	Yes
'Extrema'	Returns an 8-by-2 matrix that specifies the extrema points in the region. Each row of the matrix contains the x - and y -coordinates of one of the points. The format of the vector is [top-left top-right right-top right-bottom bottom-right bottom-left left-bottom left-top]. This figure illustrates the extrema of two different regions. In the region on the left, each extrema point is distinct. In the region on the right, certain	2-D only	Yes	Yes

Property Name String	Description	N-D Support	GPU Support	Code Generation
	<p>extrema points (e.g., top-left and left-top) are identical.</p> 			
'FilledArea'	Returns a scalar that specifies the number of on pixels in FilledImage.	Yes	No	Yes
'FilledImage'	<p>Returns a binary image (logical) of the same size as the bounding box of the region. The on pixels correspond to the region, with all holes filled in, as shown in this figure.</p>  <p>Original Image, Containing a Single Region</p>	Yes	No	Yes

Property Name String	Description	N-D Support	GPU Support	Code Generation
'Image'	Returns a binary image (logical) of the same size as the bounding box of the region. The on pixels correspond to the region, and all other pixels are off .	Yes	Yes	Yes
'MajorAxis'	Returns a scalar that specifies the length (in pixels) of the major axis of the ellipse that has the same normalized second central moments as the region.	2-D only	Yes	Yes
'MinorAxis'	Returns a scalar that specifies the length (in pixels) of the minor axis of the ellipse that has the same normalized second central moments as the region.	2-D only	Yes	Yes
'Orientation'	Returns a scalar that specifies the angle between the x -axis and the major axis of the ellipse that has the same second-moments as the region. The value is in degrees, ranging from -90 to 90 degrees. This figure illustrates the axes and orientation of the ellipse. The left side of the figure shows an image region and its corresponding ellipse. The right side shows the same ellipse with the solid blue lines representing the axes, the red dots are the foci, and the orientation is the angle between the horizontal dotted line and the major axis.	2-D only	Yes	Yes
'Perimeter'	Returns a scalar that specifies the distance around the boundary of the region. regionprops computes the perimeter by calculating the distance between each adjoining pair of pixels around the border of the region. If the image contains discontinuous regions, regionprops returns unexpected results. This figure illustrates the	2-D only	Yes	v



Property Name String	Description	N-D Support	GPU Support	Code Generation
	<p>pixels included in the perimeter calculation for this object.</p> 			
'PixelIdxList'	Returns a p -element vector that contains the linear indices of the pixels in the region.	Yes	Yes	Yes
'PixelList'	Returns a p -by- Q matrix that specifies the locations of pixels in the region. Each row of the matrix has the form $[x \ y \ z \ \dots]$ and specifies the coordinates of one pixel in the region.	Yes	Yes	Yes
'Solidity'	Returns a scalar specifying the proportion of the pixels in the convex hull that are also in the region. Computed as $\text{Area}/\text{ConvexArea}$.	2-D only	No	No
'Subarray'	Returns a cell array that contains indices such that $L(\text{idx}\{\ : \})$ extracts the elements of L inside the object bounding box.	Yes	Yes	No

The pixel value measurement properties in the following table are valid only when you specify a grayscale image, I .

Pixel Value Measurements

Property Name String	Description	N-D Support	GPU Support	Code Generation
'MaxInten	Returns a scalar that specifies the value of the pixel with the greatest intensity in the region.	No	Yes	Yes
'MeanInte	Returns a scalar that specifies the mean of all the intensity values in the region.	No	Yes	Yes
'MinInten	Returns a scalar that specifies the value of the pixel with the lowest intensity in the region.	No	Yes	Yes
'PixelVal	Returns a p -by-1 vector, where p is the number of pixels in the region. Each element in the vector contains the value of a pixel in the region.	No	Yes	Yes
'Weighted	Returns a p -by- Q vector of coordinates specifying the center of the region based on location and intensity value. The first element of <code>WeightedCentroid</code> is the horizontal coordinate (or x -coordinate) of the weighted centroid. The second element is the vertical coordinate (or y -coordinate). All other elements of <code>WeightedCentroid</code> are in order of dimension.	No	Yes	Yes

Data Types: char

CC — Connected components

structure

Connected components, specified as a structure returned by `bwconncomp`.

```
Example: BW = imread('text.png'); CC = bwconncomp(BW); s = regionprops(CC, 'basic');
```

Data Types: struct

L — Labeled regions

label matrix

Labeled regions, specified as a label matrix. `L` can have any numeric class and any dimension. `regionprops` treats negative-valued pixels as background and rounds down input pixels that are not integers. Positive integer elements of `L` correspond to different regions. For example, the set of elements of `L` equal to 1 corresponds to region 1; the set of elements of `L` equal to 2 corresponds to region 2; and so on.

Example: `BW = imread('text.png'); L = bwlabel(BW); s = regionprops(L, 'basic');`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

I — Image to be measured

grayscale image

Image to be measured, specified as a grayscale image.

Example: `I = imread('cameraman.tif'); s = regionprops(L,I,'basic');`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32`

output — Return type

'struct' (default) | 'table'

Return type, specified as either of these strings.

String	Description
'struct'	Returns an array of structures with length equal to the number of objects in <code>BW</code> , <code>CC.NumObjects</code> , or <code>max(L(:))</code> . The fields of the structure array denote different properties for each region, as specified by <code>properties</code> . If you do not specify this argument, <code>regionprops</code> returns a struct by default.
'table'	Returns a MATLAB table with height (number of rows) equal to the number of objects in <code>BW</code> , <code>CC.NumObjects</code> , or <code>max(L(:))</code> . The variables (columns) denote different properties for each region, as specified by <code>properties</code> . To learn more about MATLAB tables, see <code>table</code> . Not supported on a GPU.

Example: `s = regionprops('table',BW,'basic');`

Data Types: `char`

gpuarrayImg — Input image

2D logical `gpuArray` | label matrix `gpuArray`

Input image, specified as a 2-D logical `gpuArray` or label matrix `gpuArray`.

```
Example: gpuarrayBW = gpuArray(imread('text.png')); s =  
regionprops(gpuarrayBW, 'basic');
```

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

Output Arguments

stats — Measurement values

`struct array (default)` | `table`

Measurement values, returned as an array of structs or a table. The number of structs in the array, or the number of rows in the table, corresponds to the number of objects in `BW`, `CC.NumObjects`, or `max(L(:))`. The fields of each struct, or the variables in each row, denote the properties calculated for each region, as specified by `properties`.

When run on a GPU, `regionprops` can only return struct arrays.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic `MATLAB Host Computer` target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, `regionprops` has the following limitations.

- Supports only 2-D input images or label matrices.
- Specifying the output type `'table'` is not supported.
- Passing a cell array of properties is not supported. Use a comma-separated list instead.
- All properties are supported except `'ConvexArea'`, `'ConvexHull'`, `'ConvexImage'`, `'Solidity'`, and `'SubarrayIdx'`.

Tips

- The function `ismember` is useful in conjunction with `regionprops`, `bwconncomp`, and `labelmatrix` for creating a binary image containing only objects or regions that meet certain criteria. For example, these commands create a binary image containing only the regions whose area is greater than 80 and whose eccentricity is less than 0.8.

```
cc = bwconncomp(BW);
stats = regionprops(cc, 'Area', 'Eccentricity');
idx = find([stats.Area] > 80 & [stats.Eccentricity] < 0.8);
BW2 = ismember(labelmatrix(cc), idx);
```

- The comma-separated list syntax for structure arrays is very useful when you work with the output of `regionprops`. For example, for a field that contains a scalar, you can use this syntax to create a vector containing the value of this field for each region in the image. For instance, if `stats` is a structure array with field `Area`, then the following expression:

```
stats(1).Area, stats(2).Area, ..., stats(end).Area
```

is equivalent to:

```
stats.Area
```

Therefore, you can use these calls to create a vector containing the area of each region in the image. `allArea` is a vector of the same length as the structure array `stats`.

```
stats = regionprops(L, 'Area');
allArea = [stats.Area];
```

- The functions `bwlabel`, `bwlabeln`, and `bwconncomp` all compute connected components for binary images. `bwconncomp` replaces the use of `bwlabel` and `bwlabeln`. It uses significantly less memory and is sometimes faster than the other functions.

Function	Input Dimension	Output Form	Memory Use	Connectivity
<code>bwlabel</code>	2-D	Label matrix with double-precision	High	4 or 8
<code>bwlabeln</code>	N-D	Double-precision label matrix	High	Any
<code>bwconncomp</code>	N-D	CC struct	Low	Any

The output of `bwlabel` and `bwlabeln` is a double-precision label matrix. To compute a label matrix using a more memory-efficient data type, use the `labelmatrix` function on the output of `bwconncomp`:

```
CC = bwconncomp(BW);  
L = labelmatrix(CC);
```

If you are measuring components in a binary image with default connectivity, it is no longer necessary to call `bwlabel` or `bwlabeln` first. You can pass the binary image directly to `regionprops`, which then uses the memory-efficient `bwconncomp` function to compute the connected components automatically. If you need to specify nondefault connectivity, call `bwconncomp` and then pass the result to `regionprops`.

```
CC = bwconncomp(BW, CONN);  
S = regionprops(CC);
```

- Most of the measurements take very little time to compute. However, these measurements can take significantly longer, depending on the number of regions in `L`:
 - 'ConvexHull'
 - 'ConvexImage'
 - 'ConvexArea'
 - 'FilledImage'
- Computing certain groups of measurements takes about the same amount of time as computing just one of them because `regionprops` takes advantage of intermediate computations used in both computations. Therefore, it is fastest to compute all the desired measurements in a single call to `regionprops`.

Algorithms

Contiguous regions are also called "objects," "connected components," or "blobs." A label matrix containing contiguous regions might look like this:

```
1 1 0 2 2 0 3 3  
1 1 0 2 2 0 3 3
```

Elements of `L` equal to 1 belong to the first contiguous region or connected component; elements of `L` equal to 2 belong to the second connected component; and so on.

Discontiguous regions are regions that might contain multiple connected components. A label matrix containing discontiguous regions might look like this:


```
1 1 0 1 1 0 2 2
1 1 0 1 1 0 2 2
```

Elements of `L` equal to 1 belong to the first region, which is discontinuous and contains two connected components. Elements of `L` equal to 2 belong to the second region, which is a single connected component.

See Also

`bwconncomp` | `bwlabel` | `bwlabeln` | `ismember` | `labelmatrix` | `watershed`

Introduced before R2006a

registration.metric.MattesMutualInformation class

Package: registration.metric

Mattes mutual information metric configuration object

Description

A `MattesMutualInformation` object describes a mutual information metric configuration that you pass to the function `imregister` to solve image registration problems.

Construction

`metric = registration.metric.MattesMutualInformation()` constructs a `MattesMutualInformation` object.

Properties

NumberOfSpatialSamples

Number of spatial samples used to compute the metric.

`NumberOfSpatialSamples` is a positive scalar integer value that defines the number of random pixels `imregister` uses to compute the metric. Your registration results are more reproducible (at the cost of performance) as you increase this value. `imregister` only uses `NumberOfSpatialSamples` when `UseAllPixels = 0` (false). The default value for `NumberOfSpatialSamples` is 500.

NumberOfHistogramBins

Number of histogram bins used to compute the metric.

`NumberOfHistogramBins` is a positive scalar integer value that defines the number of bins `imregister` uses to compute the joint distribution histogram. The default value is 50, and the minimum value is 5.

UseAllPixels

Logical scalar that specifies whether `imregister` should use all pixels in the overlap region of the images to compute the metric.

You can achieve significantly better performance if you set this property to `0` (false). When `UseAllPixels = 0`, the `NumberOfSpatialSamples` property controls the number of random pixel locations that `imregister` uses to compute the metric. The results of your registration might not be reproducible when `UseAllPixels = 0`. This is because `imregister` selects a random subset of pixels from the images to compute the metric. The default value for `UseAllPixels` is `1` (true).

Definitions

Mutual Information Metric

Metric used to maximize the number of coincident pixels with the same relative brightness value. This metric is best suited for images with different brightness ranges.

Copy Semantics

Value. To learn how value classes affect copy operations, see [Copying Objects in the MATLAB documentation](#).

Tips

- Larger values of mutual information correspond to better registration results. You can examine the computed values of Mattes mutual information if you enable `'DisplayOptimization'` when you call `imregister`, for example:

```
movingRegistered = imregister(moving, fixed, 'rigid', optimizer, metric, 'DisplayOptimization', true);
```

Examples

Register MRI Images with MattesMutualInformation Metric


Register two MRI images of a knee that were obtained using different protocols.

Read the images into the workspace.

```
fixed = dicomread('knee1.dcm');  
moving = dicomread('knee2.dcm');
```

View the misaligned images.

```
imshowpair(fixed, moving, 'Scaling', 'joint');
```



Create the optimizer configuration object suitable for registering images from different sensors.

```
optimizer = registration.optimizer.OnePlusOneEvolutionary;
```

Create the MattesMutualInformation metric configuration object.

```
metric = registration.metric.MattesMutualInformation
```

```
metric =
```

```
registration.metric.MattesMutualInformation
```

```
Properties:
```

```
NumberOfSpatialSamples: 500
```

```
NumberOfHistogramBins: 50
```

```
UseAllPixels: 1
```

Tune the properties of the optimizer so that the problem will converge on a global maxima. Increase the number of iterations the optimizer will use to solve the problem.


```
optimizer.InitialRadius = 0.009;  
optimizer.Epsilon = 1.5e-4;  
optimizer.GrowthFactor = 1.01;  
optimizer.MaximumIterations = 300;
```

Register the moving and fixed images.

```
movingRegistered = imregister(moving, fixed, 'affine', optimizer, metric);
```

View the registered images.

```
figure;  
imshowpair(fixed, movingRegistered, 'Scaling', 'joint');
```



Algorithms

The `imregister` function uses an iterative process to register images. The metric you pass to `imregister` defines the image similarity metric for evaluating the accuracy of the registration. An image similarity metric takes two images and returns a scalar value that describes how similar the images are. The optimizer you pass to `imregister` defines the methodology for minimizing or maximizing the similarity metric.

Mutual information metrics are information theoretic techniques for measuring how related two variables are. These algorithms use the joint probability distribution of a sampling of pixels from two images to measure the certainty that the values of one set of pixels map to similar values in the other image. This information is a quantitative measure of how similar the images are. High mutual information implies a large reduction in the uncertainty (entropy) between the two distributions, signaling that the images are likely better aligned.

The Mattes mutual information algorithm uses a single set of pixel locations for the duration of the optimization, instead of drawing a new set at each iteration. The number of samples used to compute the probability density estimates and the number of bins used to compute the entropy are both user selectable. The marginal and joint probability density function is evaluated at the uniformly spaced bins using the samples. Entropy values are computed by summing over the bins. Zero-order and third-order B-spline kernels are used to compute the probability density functions of the fixed and moving images, respectively.[1]

References

- [1] Rahunathan, Smriti, D. Stredney, P. Schmalbrock, and B.D. Clymer. Image Registration Using Rigid Registration and Maximization of Mutual Information. Poster presented at: MMVR13. The 13th Annual Medicine Meets Virtual Reality Conference; 2005 January 26–29; Long Beach, CA.
- [2] D. Mattes, D.R. Haynor, H. Vesselle, T. Lewellen, and W. Eubank. "Non-rigid multimodality image registration." (Proceedings paper).*Medical Imaging 2001: Image Processing*. SPIE Publications, 3 July 2001. pp. 1609–1620.

Alternatives

Use `imregconfig` to construct a metric configuration for typical image registration scenarios.

See Also

`registration.metric.MeanSquares` | `imregister`

More About

- [Class Attributes](#)
- [Property Attributes](#)

registration.metric.MeanSquares class

Package: registration.metric

Mean square error metric configuration object

Description

A `MeanSquares` object describes a mean square error metric configuration that you pass to the function `imregister` to solve image registration problems.

Construction

`metric = registration.metric.MeanSquares()` constructs a `MeanSquares` object.

Copy Semantics

Value. To learn how value classes affect copy operations, see [Copying Objects in the MATLAB documentation](#).

Tips

- This metric is an element-wise difference between two input images. The ideal value is zero. You can examine the computed values of mean square error if you enable `'DisplayOptimization'` when you call `imregister`. For example, `movingRegistered = imregister(moving, fixed, 'rigid', optimizer, metric, 'DisplayOptimization')`

Examples

Register Remote Sensing Images with MeanSquares Metric

Create a `MeanSquares` object and use it to register two images captured with different sensors.

In general, `imregister` doesn't support perspective transformations. However it returns good results for this problem, which uses a similarity transformation.

Read the images into the workspace.

```
fixed = imread('westconcordorthophoto.png');  
moving = rgb2gray(imread('westconcordaerial.png'));
```

View the misaligned images.

```
imshowpair(fixed, moving, 'Scaling', 'joint');
```



Create the optimizer configuration object suitable for registering images from different sensors.

```
optimizer = registration.optimizer.OnePlusOneEvolutionary;
```

Create the `MeanSquares` metric configuration object. Even though the images came from different sensors, they have an intensity relationship similar enough to use mean square error as the similarity metric.

```
metric = registration.metric.MeanSquares
```

```
metric =
```

```
    registration.metric.MeanSquares
```

```
    This class has no properties.
```

Increase `MaximumIterations` property of the optimizer to allow for more iterations.

```
optimizer.MaximumIterations = 1000;
```

Register the moving and fixed images.

```
movingRegistered = imregister(moving, fixed, 'similarity', optimizer, metric);
```

View the registered images.

```
figure;
```

```
imshowpair(fixed, movingRegistered, 'Scaling', 'joint');
```



Algorithms

The `imregister` function uses an iterative process to register images. The metric you pass to `imregister` defines the image similarity metric for evaluating the accuracy of the registration. An image similarity metric takes two images and returns a scalar value that describes how similar the images are. The optimizer you pass to `imregister` defines the methodology for minimizing or maximizing the similarity metric.

The mean squares image similarity metric is computed by squaring the difference of corresponding pixels in each image and taking the mean of the those squared differences.

Use `imregconfig` to construct a metric configuration for typical image registration scenarios.

See Also

registration.metric.MattesMutualInformation | `imregister`

registration.optimizer.OnePlusOneEvolutionary class

Package: registration.optimizer

One-plus-one evolutionary optimizer configuration object

Description

A `OnePlusOneEvolutionary` object describes a one-plus-one evolutionary optimization configuration that you pass to the function `imregister` to solve image registration problems.

Construction

`optimizer = registration.optimizer.OnePlusOneEvolutionary()` Constructs a `OnePlusOneEvolutionary` object.

Properties

GrowthFactor

Growth factor of the search radius.

`GrowthFactor` is a positive scalar value that the optimizer uses to control the rate at which the search radius grows in parameter space. If you set `GrowthFactor` to a large value, the optimization is fast, but it might result in finding only the metric's local extrema. If you set `GrowthFactor` to a small value, the optimization is slower, but it is likely to converge on a better solution. The default value of `GrowthFactor` is `1.05`.

Epsilon

Minimum size of the search radius.

`Epsilon` is a positive scalar value that controls the accuracy of convergence by adjusting the minimum size of the search radius. If you set `Epsilon` to a small value, the optimization of the metric is more accurate, but the computation takes longer. If you set

Epsilon to a large value, the computation time decreases at the expense of accuracy. The default value of `Epsilon` is `1.5e-6`.

InitialRadius

Initial size of search radius.

`InitialRadius` is a positive scalar value that controls the initial search radius of the optimizer. If you set `InitialRadius` to a large value, the computation time decreases. However, overly large values of `InitialRadius` might result in an optimization that fails to converge. The default value of `InitialRadius` is `6.25e-3`.

MaximumIterations

Maximum number of optimizer iterations.

`MaximumIterations` is a positive scalar integer value that determines the maximum number of iterations the optimizer performs at any given pyramid level. The registration could converge before the optimizer reaches the maximum number of iterations. The default value of `MaximumIterations` is `100`.

Copy Semantics

Value. To learn how value classes affect copy operations, see [Copying Objects in the MATLAB documentation](#).

Examples

Register MRI Images with OnePlusOneEvolutionary Optimizer


Register two MRI images of a knee that were obtained using different protocols.

Read the images into the workspace.

```
fixed = dicomread('knee1.dcm');  
moving = dicomread('knee2.dcm');
```

View the misaligned images.

```
imshowpair(fixed, moving, 'Scaling', 'joint');
```



Create the optimizer configuration object suitable for registering images from different sensors.

```
optimizer = registration.optimizer.OnePlusOneEvolutionary
```

```
optimizer =
```

```
    registration.optimizer.OnePlusOneEvolutionary
```

```
    Properties:
```

```
        GrowthFactor: 1.050000e+00
```

```
        Epsilon: 1.500000e-06
```

```
        InitialRadius: 6.250000e-03
```

```
        MaximumIterations: 100
```

Create the MattesMutualInformation metric configuration object.

```
metric = registration.metric.MattesMutualInformation;
```

Tune the properties of the optimizer so that the problem will converge on a global maxima. Increase the number of iterations the optimizer will use to solve the problem.


```
optimizer.InitialRadius = 0.009;  
optimizer.Epsilon = 1.5e-4;  
optimizer.GrowthFactor = 1.01;  
optimizer.MaximumIterations = 300;
```

Register the moving and fixed images.

```
movingRegistered = imregister(moving, fixed, 'affine', optimizer, metric);
```

View the registered images.

```
figure  
imshowpair(fixed, movingRegistered, 'Scaling', 'joint');
```

Algorithms

The `imregister` function uses an iterative process to register images. The metric you pass to `imregister` defines the image similarity metric for evaluating the accuracy of the registration. An image similarity metric takes two images and returns a scalar value that describes how similar the images are. The optimizer you pass to `imregister` defines the methodology for minimizing or maximizing the similarity metric.

An evolutionary algorithm iterates to find a set of parameters that produce the best possible registration result. It does this by perturbing, or mutating, the parameters from the last iteration (the parent). If the new (child) parameters yield a better result, then the child becomes the new parent whose parameters are perturbed, perhaps more aggressively. If the parent yields a better result, it remains the parent and the next perturbation is less aggressive.

References

- [1] Styner, M., C. Brechbuehler, G. Székely, and G. Gerig. "Parametric estimate of intensity inhomogeneities applied to MRI." *IEEE Transactions on Medical Imaging*. Vol. 19, Number 3, 2000, pp. 153-165.

Alternatives

Use `imregconfig` to construct an optimizer configuration for typical image registration scenarios.

See Also

`registration.optimizer.RegularStepGradientDescent` | `imregister`

More About

- Class Attributes
- Property Attributes

registration.optimizer.RegularStepGradientDescent class

Package: registration.optimizer

Regular step gradient descent optimizer configuration object

Description

A `RegularStepGradientDescent` object describes a regular step gradient descent optimization configuration that you pass to the function `imregister` to solve image registration problems.

Construction

`optimizer = registration.optimizer.RegularStepGradientDescent()` constructs a `RegularStepGradientDescent` object.

Properties

GradientMagnitudeTolerance

Gradient magnitude tolerance.

`GradientMagnitudeTolerance` is a positive scalar value that controls the optimization process. When the value of the gradient is smaller than `GradientMagnitudeTolerance`, it is an indication that the optimizer might have reached a plateau. The default value of `GradientMagnitudeTolerance` is $1e-4$.

MinimumStepLength

Tolerance for convergence.

`MinimumStepLength` is a positive scalar value that controls the accuracy of convergence. If you set `MinimumStepLength` to a small value, the optimization takes longer to compute, but it is likely to converge on a more accurate metric value. The default value of `MinimumStepLength` is $1e-5$.

MaximumStepLength

Initial step length.

`MaximumStepLength` is a positive scalar value that controls the initial step length used in optimization. If you set `MaximumStepLength` to a large value, the computation time decreases. However, the optimizer might fail to converge if you set `MaximumStepLength` to an overly large value. The default value of `MaximumStepLength` is `0.0625`.

MaximumIterations

Maximum number of iterations.

`MaximumIterations` is a positive scalar integer value that determines the maximum number of iterations the optimizer performs at any given pyramid level. The registration could converge before the optimizer reaches the maximum number of iterations. The default value of `MaximumIterations` is `100`.

RelaxationFactor

Step length reduction factor.

`RelaxationFactor` is a scalar value between 0 and 1 that defines the rate at which the optimizer reduces step size during convergence. Whenever the optimizer determines that the direction of the gradient changed, it reduces the size of the step length. If your metric is noisy, you can set `RelaxationFactor` to a larger value. This leads to a more stable convergence at the expense of computation time. The default value of `RelaxationFactor` is `0.5`.

Copy Semantics

Value. To learn how value classes affect copy operations, see [Copying Objects in the MATLAB documentation](#).

Examples

Register Images with RegularStepGradientDescent Optimizer

Create a `RegularStepGradientDescent` object and use it to register two images captured with the same device.

Read the reference image and create an unregistered copy.

```
fixed = imread('pout.tif');  
moving = imrotate(fixed, 5, 'bilinear', 'crop');
```

View the misaligned images.

```
imshowpair(fixed, moving, 'Scaling', 'joint');
```



Create the optimizer configuration object suitable for registering images from the same device.

```
optimizer = registration.optimizer.RegularStepGradientDescent
```

Create the metric configuration object.

```
metric = registration.metric.MeanSquares;
```

Now modify the optimizer configuration to get more precision.

```
optimizer.MaximumIterations = 300;  
optimizer.MinimumStepLength = 5e-4;
```

Perform the registration.

```
movingRegistered = imregister(moving, fixed, 'rigid', optimizer, metric);
```

View registered images.

```
figure  
imshowpair(fixed, movingRegistered, 'Scaling', 'joint');
```



Algorithms

The `imregister` function uses an iterative process to register images. The metric you pass to `imregister` defines the image similarity metric for evaluating the accuracy of the registration. An image similarity metric takes two images and returns a scalar value that describes how similar the images are. The optimizer you pass to `imregister` defines the methodology for minimizing or maximizing the similarity metric.

The regular step gradient descent optimization adjusts the transformation parameters so that the optimization follows the gradient of the image similarity metric in the direction of the extrema. It uses constant length steps along the gradient between computations until the gradient changes direction, at which point the step length is halved.

Use `imregconfig` to construct an optimizer configuration for typical image registration scenarios.

See Also

`registration.optimizer.OnePlusOneEvolutionary` | `imregister`

More About

- [Class Attributes](#)
- [Property Attributes](#)

rgb2lab

Convert RGB to CIE 1976 L*a*b*

Syntax

```
lab = rgb2lab(rgb)
lab = rgb2lab(rgb,Name,Value)
```

Description

`lab = rgb2lab(rgb)` converts RGB values to CIE 1976 L*a*b* values.

`lab = rgb2lab(rgb,Name,Value)` specifies additional options with one or more Name,Value pair arguments.

“Code Generation” on page 1-1438 support: Yes.

“MATLAB Function Block” on page 1-1438 support: Yes.

Examples

Convert RGB White to L*a*b*

Use `rgb2lab` to convert the RGB white value to L*a*b*.

```
rgb2lab([1 1 1])
```

```
ans =
```

```
    100     0     0
```

Convert Color Value to L*a*b* Specifying Color Space

Convert an Adobe RGB (1998) color value to L*a*b* using the `ColorSpace` parameter.


```
rgb2lab([.2 .3 .4], 'ColorSpace', 'adobe-rgb-1998')
```

```
ans =
```

```
30.1783 -5.6902 -20.8223
```

Convert RGB color to L*a*b* Specifying Reference White

Use `rgb2lab` to convert an RGB color to L*a*b* using the D50 reference white.

```
rgb2lab([.2 .3 .4], 'WhitePoint', 'd50')
```

```
ans =
```

```
31.3294 -4.0732 -18.1750
```

Convert RGB Image to L*a*b* and Display L* Component

Read RGB image into the workspace.


```
rgb = imread('peppers.png');
```

Convert the RGB image to the L*a*b* color space.

```
lab = rgb2lab(rgb);
```

Display the L* component of the L*a*b* image.

```
imshow(lab(:,:,1), [0 100])
```



Input Arguments

rgb — Color values to convert

P-by-3 matrix | M-by-N-by-3 image array | M-by-N-by-3-by-F image stack

Color values to convert, specified as a P-by-3 matrix of color values (one color per row), an M-by-N-by-3 image array, or an M-by-N-by-3-by-F image stack.

Data Types: `single` | `double` | `uint8` | `uint16`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, . . . , NameN, ValueN`.

Example: `rgb2lab([0.25 0.40 0.10], 'WhitePoint', 'd50')`

'ColorSpace' — Color space of the input RGB values

'srgb' (default) | 'adobe-rgb-1998'

Color space of the input RGB values, specified as the text string 'srgb' or 'adobe-rgb-1998'.

Data Types: char

'WhitePoint' — Reference white point

'd65' (default) | 'a' | 'c' | 'd50' | 'icc' | 'e' | 1-by-3 vector

Reference white point, specified as a 1-by-3 vector or one of the CIE standard illuminants, listed in the following table.

String Value	White Point
'a'	CIE standard illuminant A, [1.0985, 1.0000, 0.3558]. Simulates typical, domestic, tungsten-filament lighting.
'c'	CIE standard illuminant C, [0.9807, 1.0000, 1.1822]. Simulates daylight with correlated color temperature of 4874 K. Deprecated by CIE.
'd50'	CIE standard illuminant D50, [0.9642, 1.0000, 0.8251]. Simulates daylight with correlated color temperature of 5003 K.
'd65'	CIE standard illuminant D65, [0.9504, 1.0000, 1.0888]. Simulates daylight with correlated color temperature of 6504 K.
'icc'	Profile Connection Space (PCS) illuminant used in ICC profiles. Approximation of [0.962, 1.000, 0.8249] using fixed-point, signed, 32-bit numbers with 16 fractional bits. Actual value: [31595, 32768, 27030] / 32768.
'e'	Equal-energy radiator. Useful as a theoretical reference. [1.000, 1.000, 1.000].

Data Types: `single` | `double` | `char`

Output Arguments

lab — Converted color values

numeric array

Converted color values, returned as an array the same shape as the input. The output type is `double` unless the input type is `single`, in which case the output type is also `single`.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, all string input arguments must be compile-time constants.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

`lab2rgb` | `lab2xyz` | `rgb2xyz` | `xyz2lab` | `xyz2rgb`

Introduced in R2014b

rgb2ntsc

Convert RGB color values to NTSC color space

Syntax

```
yiqmap = rgb2ntsc(rgbmap)  
YIQ = rgb2ntsc(RGB)
```

Description

`yiqmap = rgb2ntsc(rgbmap)` converts the m -by-3 RGB values in `rgbmap` to NTSC color space. `yiqmap` is an m -by-3 matrix that contains the NTSC luminance (Y) and chrominance (I and Q) color components as columns that are equivalent to the colors in the RGB colormap.

`YIQ = rgb2ntsc(RGB)` converts the truecolor image `RGB` to the equivalent NTSC image `YIQ`.

Class Support

`RGB` can be of class `uint8`, `uint16`, `int16`, `single`, or `double`. `RGBMAP` can be `double`. The output is `double`.

More About

Tips

In the NTSC color space, the luminance is the grayscale signal used to display pictures on monochrome (black and white) televisions. The other components carry the hue and saturation information.

`rgb2ntsc` defines the NTSC components using

$$\begin{bmatrix} Y \\ I \\ Q \end{bmatrix} = \begin{bmatrix} 0.299 & 0.587 & 0.114 \\ 0.596 & -0.274 & -0.322 \\ 0.211 & -0.523 & 0.312 \end{bmatrix} \begin{bmatrix} R \\ G \\ B \end{bmatrix}$$

See Also

[ntsc2rgb](#) | [rgb2ind](#) | [ind2rgb](#) | [ind2gray](#)

Introduced before R2006a

rgb2xyz

Convert RGB to CIE 1931 XYZ

Syntax

```
xyz = rgb2xyz(rgb)
xyz = rgb2xyz(rgb,Name,Value)
```

Description

`xyz = rgb2xyz(rgb)` converts RGB values to CIE 1931 XYZ values.

`xyz = rgb2xyz(rgb,Name,Value)` specifies additional options with one or more Name,Value pair arguments.

Examples

Convert RGB image to XYZ

```
rgb = imread('peppers.png');
xyz = rgb2xyz(rgb);
```

Convert RGB white to XYZ

```
rgb2xyz([1 1 1])
ans =
    0.9505    1.0000    1.0890
```

Convert RGB color to XYZ using D50 as reference white

```
rgb2xyz([.2 .3 .4], 'WhitePoint', 'd50')
ans =
```

```
0.0617    0.0679    0.1025
```

Convert Adobe RGB (1998) color value to XYZ

```
rgb2xyz([.2 .3 .4], 'ColorSpace', 'adobe-rgb-1998')
```

```
ans =
```

```
0.0550    0.0631    0.1379
```

Input Arguments

rgb — Color values to convert

P-by-3 matrix | M-by-N-by-3 image array | M-by-N-by-3-by-F image stack

Color values to convert, specified as a P-by-3 matrix of color values (one color per row), an M-by-N-by-3 image array, or an M-by-N-by-3-by-F image stack.

Example: `rgb2xyz([1 1 1])`

Data Types: `single` | `double` | `uint8` | `uint16`

Name-Value Pair Arguments

Specify optional comma-separated pairs of **Name**, **Value** arguments. **Name** is the argument name and **Value** is the corresponding value. **Name** must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as **Name1**, **Value1**, ..., **NameN**, **ValueN**.

Example: `rgb2xyz([.2 .3 .4], 'WhitePoint', 'd50')`

'ColorSpace' — Color space of the input RGB values

'srgb' (default) | 'adobe-rgb-1998'

Color space of the input RGB values, specified as the text string 'srgb' or 'adobe-rgb-1998'.

Example: `rgb2xyz([.2 .3 .4], 'ColorSpace', 'adobe-rgb-1998')`

Data Types: `char`

'WhitePoint' — Reference white point

'd65' (default) | 'a' | 'c' | 'd50' | 'icc' | 'e' | 1-by-3 vector

Reference white point, specified as a 1-by-3 vector or one of the CIE standard illuminants, identified by the following text strings: 'a', 'c', 'd50', 'd65', 'e', or the ICC standard profile connection space illuminant, 'icc'.

Example: `rgb2xyz([.2 .3 .4], 'WhitePoint', 'd50')`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `char`

Output Arguments

xyz — Converted color values

array the same shape as the input

Converted color values, returned as an array the same shape as the input. The output type is class `double` unless the input type is `single`, in which case the output type is also `single`.

See Also

`lab2rgb` | `lab2xyz` | `rgb2lab` | `xyz2lab` | `xyz2rgb`

Introduced in R2014b

rgb2ycbcr

Convert RGB color values to YCbCr color space

Syntax

```
ycbcrmap = rgb2ycbcr(map)
YCBCR = rgb2ycbcr(RGB)
gpuarrayB = rgb2ycbcr(gpuarrayA)
```

Description

`ycbcrmap = rgb2ycbcr(map)` converts the RGB values in `map` to the YCbCr color space. `map` must be an M-by-3 array. `ycbcrmap` is an M-by-3 matrix that contains the YCbCr luminance (*Y*) and chrominance (*Cb* and *Cr*) color values as columns. Each row in `ycbcrmap` represents the equivalent color to the corresponding row in the RGB colormap, `map`.

`YCBCR = rgb2ycbcr(RGB)` converts the truecolor image `RGB` to the equivalent image in the YCbCr color space. `RGB` must be a M-by-N-by-3 array.

`gpuarrayB = rgb2ycbcr(gpuarrayA)` performs the conversion on a GPU. The input image, `gpuarrayA`, can be an RGB `gpuArray` colormap or an RGB `gpuArray` image. The output is an YCbCr `gpuArray` colormap or an YCbCr `gpuArray` image, depending on the input type. This syntax requires the Parallel Computing Toolbox.

- If the input is `uint8`, `YCBCR` is `uint8`, where *Y* is in the range [16 235], and *Cb* and *Cr* are in the range [16 240].
- If the input is a `double`, *Y* is in the range [16/255 235/255] and *Cb* and *Cr* are in the range [16/255 240/255].
- If the input is `uint16`, *Y* is in the range [4112 60395] and *Cb* and *Cr* are in the range [4112 61680].

“Code Generation” on page 1-1445 support: Yes.

“MATLAB Function Block” on page 1-1446 support: Yes.

Class Support

If the input is an RGB image, it can be of class `uint8`, `uint16`, or `double`. If the input is a colormap, it must be `double`. The output is of the same class as the input image.

If the input `gpuArray` is an RGB image, it can be of class `uint8`, `uint16`, `single`, or `double`. If the input `gpuArray` is a colormap, it must be `single` or `double`. The output `gpuArray` is of the same class as the input image.

Examples

Convert RGB image to YCbCr.

```
RGB = imread('board.tif');  
YCBCR = rgb2ycbcr(RGB);
```

Convert RGB color space to YCbCr.

```
map = jet(256);  
newmap = rgb2ycbcr(map);
```

Convert RGB image to YCbCr on a GPU.

```
RGB = imread('board.tif');  
YCBCR = rgb2ycbcr(gpuArray(RGB));
```

Convert RGB color space to YCbCr on a GPU.

```
map = jet(256);  
newmap = rgb2ycbcr(gpuArray(map));
```

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can

be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

References

- [1] Poynton, C. A. *A Technical Introduction to Digital Video*, John Wiley & Sons, Inc., 1996, p. 175.
- [2] Rec. ITU-R BT.601-5, *Studio Encoding Parameters of Digital Television for Standard 4:3 and Wide-screen 16:9 Aspect Ratios*, (1982-1986-1990-1992-1994-1995), Section 3.5.

See Also

[ntsc2rgb](#) | [rgb2ntsc](#) | [ycbcr2rgb](#) | [gpuArray](#)

Introduced before R2006a

roicolor

Select region of interest (ROI) based on color

Syntax

```
BW = roicolor(A,low,high)
BW = roicolor(A,v)
```

Description

`roicolor` selects a region of interest (ROI) within an indexed or intensity image and returns a binary image. (You can use the returned image as a mask for masked filtering using `roifilt2`.)

`BW = roicolor(A,low,high)` returns an ROI selected as those pixels that lie within the colormap range [`low high`].

```
BW = (A >= low) & (A <= high)
```

`BW` is a binary image with 0's outside the region of interest and 1's inside.

`BW = roicolor(A,v)` returns an ROI selected as those pixels in `A` that match the values in vector `v`. `BW` is a binary image with 1's where the values of `A` match the values of `v`.

Class Support

The input image `A` must be numeric. The output image `BW` is of class `logical`.

Examples

```
load clown
BW = roicolor(X,10,20);
imshow(X,map)
figure,imshow(BW)
```



See Also

roifilt2 | roipoly

Introduced before R2006a

roifill

Fill in specified region of interest (ROI) polygon in grayscale image

Compatibility

`roifill` is not recommended. Use `regionfill` instead.

Syntax

```
J = roifill
J = roifill(I)
J = roifill(I, c, r)
J = roifill(I, BW)
[J,BW] = roifill(...)
J = roifill(x, y, I, xi, yi)
[x, y, J, BW, xi, yi] = roifill(...)
```

Description

Use `roifill` to fill in a specified region of interest (ROI) polygon in a grayscale image. `roifill` smoothly interpolates inward from the pixel values on the boundary of the polygon by solving Laplace's equation. The boundary pixels are not modified. `roifill` can be used, for example, to erase objects in an image.

`J = roifill` creates an interactive polygon tool, associated with the image displayed in the current figure, called the target image. You use the mouse to define the ROI – see “Interactive Behavior” on page 1-1450. When you are finished defining the ROI, fill in the area specified by the ROI by double-clicking inside the region or by right-clicking anywhere inside the region and selecting **Fill Area** from the context menu. `roifill` returns the image, `J`, which is the same size as `I` with the region filled in (see “Examples” on page 1-1452).

Note: If you do not specify an output argument, `roifill` displays the filled image in a new figure.

`J = roifill(I)` displays the image `I` and creates an interactive polygon tool associated with the image.

`J = roifill(I, c, r)` fills in the polygon specified by `c` and `r`, which are equal-length vectors containing the row-column coordinates of the pixels on vertices of the polygon. The k th vertex is the pixel $(r(k), c(k))$.


`J = roifill(I, BW)` uses `BW` (a binary image the same size as `I`) as a mask. `roifill` fills in the regions in `I` corresponding to the nonzero pixels in `BW`. If there are multiple regions, `roifill` performs the interpolation on each region independently.


`[J,BW] = roifill(...)` returns the binary mask used to determine which pixels in `I` get filled. `BW` is a binary image the same size as `I` with 1's for pixels corresponding to the interpolated region of `I` and 0's elsewhere.



`J = roifill(x, y, I, xi, yi)` uses the vectors `x` and `y` to establish a nondefault spatial coordinate system. `xi` and `yi` are equal-length vectors that specify polygon vertices as locations in this coordinate system.




`[x, y, J, BW, xi, yi] = roifill(...)` returns the `XData` and `YData` in `x` and `y`, the output image in `J`, the mask image in `BW`, and the polygon coordinates in `xi` and `yi`. `xi` and `yi` are empty if the `roifill(I,BW)` form is used.

Interactive Behavior

When you call `roifill` with an interactive syntax, the pointer changes to a cross hairs shape  when you move it over the target image. Using the mouse, you specify a region-of-interest by selecting vertices of a polygon. You can change the size or shape of the polygon using the mouse. The following figure illustrates a polygon defined by multiple vertices. For more information about all the interactive capabilities of `roifill`, see the table that follows.



Interactive Behavior	Description
Closing the polygon. (Completing the region-of-interest.)	Use any of the following mechanisms: <ul style="list-style-type: none"> • Move the pointer over the initial vertex of the polygon that you selected. The shape changes to a circle . Click either mouse button. • Double-click the left mouse button. This action creates a vertex at the point under the mouse and draws a straight line connecting this vertex with the initial vertex. • Click the right mouse button. This action draws a line connecting the last vertex selected with the initial vertex; it does not create a new vertex.
Deleting the polygon	Press Backspace , Escape or Delete , or right-click inside the region and select Cancel from the context menu. Note: If you delete the ROI, the function returns empty values.
Moving the polygon	Move the pointer inside the region. The pointer changes to a fleur  . Click and drag the mouse to move the polygon.

Interactive Behavior	Description
Changing the color of the polygon	Move the pointer inside the region. Right-click and select Set color from the context menu.
Adding a new vertex.	Move the pointer over an edge of the polygon and press the A key. The shape of the pointer changes  . Click the left mouse button to create a new vertex at that position on the line.
Moving a vertex. (Reshaping the region-of-interest.)	Move the pointer over a vertex. The pointer changes to a circle  . Click and drag the vertex to its new position.
Deleting a vertex.	Move the pointer over a vertex. The pointer changes to a circle  . Right-click and select Delete Vertex from the context menu. This action deletes the vertex and adjusts the shape of the polygon, drawing a new straight line between the two vertices that were neighbors of the deleted vertex.
Retrieving the coordinates of the vertices	Move the pointer inside the region. Right-click and select Copy position from the context menu to copy the current position to the Clipboard. Position is an n -by-2 array containing the x - and y -coordinates of each vertex, where n is the number of vertices you selected.

Class Support

The input image **I** can be of class `uint8`, `uint16`, `int16`, `single`, or `double`. The input binary mask **BW** can be any numeric class or `logical`. The output binary mask **BW** is always `logical`. The output image **J** is of the same class as **I**. All other inputs and outputs are of class `double`.

Examples

This example uses `roifill` to fill a region in the input image, **I**. For more examples, especially of the interactive syntaxes, see “Fill Region of Interest in an Image”.

```
I = imread('eight.tif');
```

```
c = [222 272 300 270 221 194];  
r = [21 21 75 121 121 75];  
J = roifill(I,c,r);  
imshow(I)  
figure, imshow(J)
```



See Also

[impoly](#) | [roifilt2](#) | [roipoly](#)

Introduced before R2006a

roifilt2

Filter region of interest (ROI) in image

Syntax

```
J = roifilt2(h, I, BW)
J = roifilt2(I, BW, fun)
```

Description

`J = roifilt2(h, I, BW)` filters the data in `I` with the two-dimensional linear filter `h`. `BW` is a binary image the same size as `I` that defines an ROI used as a mask for filtering. `roifilt2` returns an image that consists of filtered values for pixels in locations where `BW` contains 1's, and unfiltered values for pixels in locations where `BW` contains 0's. For this syntax, `roifilt2` calls `filter2` to implement the filter.

`J = roifilt2(I, BW, fun)` processes the data in `I` using the function `fun`. The result `J` contains computed values for pixels in locations where `BW` contains 1's, and the actual values in `I` for pixels in locations where `BW` contains 0's. `fun` must be a function handle. Parameterizing Functions, in the MATLAB Mathematics documentation, explains how to provide additional parameters to the function `fun`.

Class Support

For the syntax that includes a filter `h`, the input image can be logical or numeric, and the output array `J` has the same class as the input image. For the syntax that includes a function, `I` can be of any class supported by `fun`, and the class of `J` depends on the class of the output from `fun`.

Examples

This example continues the `roipoly` example, filtering the region of the image `I` specified by the mask `BW`. The `roifilt2` function returns the filtered image `J`, shown in the following figure.

```
I = imread('eight.tif');  
c = [222 272 300 270 221 194];  
r = [21 21 75 121 121 75];  
BW = roipoly(I,c,r);  
H = fspecial('unsharp');  
J = roifilt2(H,I,BW);  
figure, imshow(I), figure, imshow(J)
```



More About

- “Anonymous Functions”
- “Parameterizing Functions”
- “Create Function Handle”

See Also

[filter2](#) | [imfilter](#) | [roipoly](#)

Introduced before R2006a

roipoly

Specify polygonal region of interest (ROI)


Syntax


```
BW = roipoly
BW = roipoly(I)
BW = roipoly(I, c, r)
BW = roipoly(x, y, I, xi, yi)
[BW, xi, yi] = roipoly(...)
[x, y, BW, xi, yi] = roipoly(...)
```

Description



Use `roipoly` to specify a polygonal region of interest (ROI) within an image. `roipoly` returns a binary image that you can use as a mask for masked filtering.




`BW = roipoly` creates an interactive polygon tool, associated with the image displayed in the current figure, called the target image. With the polygon tool active, the pointer

changes to cross hairs  when you move the pointer over the image in the figure. Using the mouse, you specify the region by selecting vertices of the polygon. You can move or resize the polygon using the mouse. The following figure illustrates a polygon defined by multiple vertices. The following table describes all the interactive behavior of the polygon tool.



When you are finished positioning and sizing the polygon, create the mask by double-clicking, or by right-clicking inside the region and selecting **Create mask** from the context menu. `roipoly` returns the mask as a binary image, `BW`, the same size as `I`. In the mask image, `roipoly` sets pixels inside the region to 1 and pixels outside the region to 0.

Interactive Behavior	Description
Closing the polygon. (Completing the region-of-interest.)	Use any of the following mechanisms: <ul style="list-style-type: none"> • Move the pointer over the initial vertex of the polygon that you selected. The pointer changes to a circle . Click either mouse button. • Double-click the left mouse button. This action creates a vertex at the point under the mouse pointer and draws a straight line connecting this vertex with the initial vertex. • Right-click the mouse. This draws a line connecting the last vertex selected with the initial vertex; it does not create a new vertex at the point under the mouse.
Moving the entire polygon	Move the pointer inside the region. The pointer changes to a fleur shape  . Click and drag the polygon over the image.

Interactive Behavior	Description
Deleting the polygon	<p>Press Backspace, Escape or Delete, or right-click inside the region and select Cancel from the context menu.</p> <p>Note: If you delete the ROI, the function returns empty values.</p>
Moving a vertex. (Reshaping the region-of-interest.)	<p>Move the pointer over a vertex. The pointer changes to a circle . Click and drag the vertex to its new position.</p>
Adding a new vertex.	<p>Move the pointer over an edge of the polygon and press the A key. The pointer changes shape to . Click the left mouse button to create a new vertex at that point on the edge.</p>
Deleting a vertex. (Reshaping the region-of-interest.)	<p>Move the pointer over the vertex. The pointer changes to a circle . Right-click and select Delete vertex from the context menu. <code>roipoly</code> draws a new straight line between the two vertices that were neighbors of the deleted vertex.</p>
Changing the color of the polygon	<p>Move the pointer anywhere inside the boundary of the region and click the right mouse button. Select Set color from the context menu.</p>
Retrieving the coordinates of the vertices	<p>Move the pointer inside the region. Right-click and select Copy position from the context menu to copy the current position to the Clipboard. The position is an n-by-2 array containing the x- and y-coordinates of each vertex, where n is the number of vertices.</p>

Note: If you call `roipoly` without specifying any output arguments, `roipoly` displays the resulting mask image in a new figure window.

`BW = roipoly(I)` displays the image `I` and creates an interactive polygon tool associated with that image.

`BW = roipoly(I, c, r)` returns the ROI specified by the polygon described by vectors `c` and `r`, which specify the column and row indices of each vertex, respectively. `c` and `r` must be the same size.

`BW = roipoly(x, y, I, xi, yi)` uses the vectors `x` and `y` to establish a nondefault spatial coordinate system. `xi` and `yi` are equal-length vectors that specify polygon vertices as locations in this coordinate system.

`[BW, xi, yi] = roipoly(...)` returns the x - and y -coordinates of the polygon vertices in `xi` and `yi`.

Note: `roipoly` always produces a closed polygon. If the points specified describe a closed polygon (i.e., if the last pair of coordinates is identical to the first pair), the length of `xi` and `yi` is equal to the number of points specified. If the points specified do not describe a closed polygon, `roipoly` adds a final point having the same coordinates as the first point. (In this case the length of `xi` and `yi` is one greater than the number of points specified.)

`[x, y, BW, xi, yi] = roipoly(...)` returns the `XData` and `YData` in `x` and `y`, the mask image in `BW`, and the polygon coordinates in `xi` and `yi`.


Class Support

The input image `I` can be of class `uint8`, `uint16`, `int16`, `single`, or `double`. The output image `BW` is of class `logical`. All other inputs and outputs are of class `double`.

Examples

Use `roipoly` to create a mask image, `BW`, the same size as the input image, `I`. The example in `roifilt2` continues this example, filtering the specified region in the image. To see another example of using `roipoly`, especially of the interactive syntaxes, see “Fill Region of Interest in an Image”.

```
I = imread('eight.tif');
c = [222 272 300 270 221 194];
r = [21 21 75 121 121 75];
BW = roipoly(I,c,r);
figure, imshow(I)
figure, imshow(BW)
```



More About

Tips

For any of the `roipoly` syntaxes, you can replace the input image `I` with two arguments, `m` and `n`, that specify the row and column dimensions of an arbitrary image. For example, these commands create a 100-by-200 binary mask.

```
c = [112 112 79 79];  
r = [37 66 66 37];  
BW = roipoly(100,200,c,r);
```

If you specify `m` and `n` with an interactive form of `roipoly`, an `m`-by-`n` black image is displayed, and you use the mouse to specify a polygon within this image.

See Also

`impoly` | `poly2mask` | `roifilt2` | `roicolor` | `regionfill`

Introduced before R2006a

rsetwrite

Create reduced resolution data set from image file

Syntax

```
rsetfile = rsetwrite(File_Name)
rsetfile = rsetwrite(File_Name, output_filename)
rsetfile = rsetwrite(adapter, output_filename)
```

Description

`rsetfile = rsetwrite(File_Name)`, where `File_Name` is a TIFF or NITF image file, creates a reduced resolution data set (R-Set) from the specified file. The R-Set file is written to the current working directory with a name based on the input file name. For example, if `File_Name` is `'VeryLargeImage.tiff'`, `rsetfile` will be `'VeryLargeImage.rset'`. If an image file contains multiple images, only the first one is used.

`rsetfile = rsetwrite(File_Name, output_filename)` creates an R-Set from the specified image file, using `output_filename` as the name of the new file. In this case, `rsetfile` and `output_filename` contain the same string.

`rsetfile = rsetwrite(adapter, output_filename)` creates an R-Set from the specified Image Adapter object, `adapter`. Image Adapters are user-defined classes that provide `rsetwrite` a common API for reading a particular image file format. See the documentation for `ImageAdapter` for more details.

Examples

Example 1: Create an R-Set File

Visualize a very large image by using an R-Set. Replace `'MyReallyBigImage.tif'` in the example below with the name of your file:

```
big_file = 'MyReallyBigImage.tif';
rset_file = rsetwrite(big_file);
```

```
imtool(rset_file)
```

Example 2: Convert TIFF Files to R-Set Files

Create R-Set files for every TIFF in a directory containing very large images. Put the R-Set files into a temporary directory:

```
d = dir('*.tif*');
image_dir = pwd;
cd(tempdir)
for p = 1:numel(d)
    big_file = fullfile(image_dir, d(p).name);
    rsetwrite(big_file);
end
```

More About

Tips

`rsetwrite` creates an R-Set file by dividing an image into spatial tiles and resampling the image at different resolution levels. When you open the R-Set file in the Image Tool and zoom in, you view tiles at a higher resolution. When you zoom out, you view tiles at a lower resolution. In this way, clarity of the image and memory usage are balanced for optimal performance. The R-Set file contains a compressed copy of the full-resolution data.

Because R-Set creation can be time consuming, a progress bar shows the status of the operation. If you cancel the operation, processing stops, no file is written, and the `rsetfile` variable will be empty.

`rsetwrite` supports NITF image files that are uncompressed and Version 2.0 or higher. It does not support NITF files with more than three bands or with floating point data. Images with more than one data band are OK if they contain unsigned integer data.

While it is possible to create an R-Set from an image where the dimensions are smaller than the size of a single R-Set tile, the resulting R-set file will likely be larger and take longer to load than the original file. The current size of an R-Set tile is 512 x 512 pixels.

See Also

`imread` | `imtool`

Introduced in R2009a

ssim

Structural Similarity Index (SSIM) for measuring image quality

Syntax

```
ssimval = ssim(A,ref)
[ssimval,ssimmap] = ssim(A,ref)
___ = ssim(__,Name,Value,...)
```

Description

`ssimval = ssim(A,ref)` computes the Structural Similarity Index (SSIM) value for image `A` using `ref` as the reference image.

`[ssimval,ssimmap] = ssim(A,ref)` returns the local SSIM value for each pixel in `A`.

`___ = ssim(__,Name,Value,...)` computes the SSIM, using name-value pairs to control aspects of the computation. Parameter names can be abbreviated.

Examples

Calculate Structural Similarity Index (SSIM)

Read an image into the workspace. Create another version of the image, applying a blurring filter. Display both images.

```
ref = imread('pout.tif');
H = fspecial('Gaussian',[11 11],1.5);
A = imfilter(ref,H,'replicate');

subplot(1,2,1); imshow(ref); title('Reference Image');
subplot(1,2,2); imshow(A); title('Blurred Image');
```


Reference Image**Blurred Image**

Calculate the global SSIM value for the image and local SSIM values for each pixel. Return the global SSIM value and display the local SSIM value map.

```
[ssimval, ssimmap] = ssim(A,ref);  
fprintf('The SSIM value is %0.4f.\n',ssimval);  
figure, imshow(ssimmap,[]);  
title(sprintf('ssim Index Map - Mean ssim Value is %0.4f',ssimval));
```

The SSIM value is 0.9407.

ssim Index Map - Mean ssim Value is 0.9407



- “Compare Image Quality at Various Compression Levels”

Input Arguments

A — Image whose quality is to be measured

2-D grayscale image | 3-D volume image

Image whose quality is to be measured, specified as a 2-D grayscale image or 3-D volume image. Must be the same size and class as `ref`

Data Types: `single` | `double` | `int16` | `uint8` | `uint16`

ref — Reference image against which quality is measured

2-D grayscale image | 3-D volume image

Reference image against which quality is measured, specified as a 2-D grayscale image or 3-D volume image. Must be the same size and class as A

Data Types: `single` | `double` | `int16` | `uint8` | `uint16`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

Example:

'DynamicRange' — Dynamic range of the input image

`diff(getrangefromclass(A))` (default) | positive scalar

Dynamic range of the input image, specified as a positive scalar. By default, this value is chosen based on the class of the input image A, as `diff(getrangefromclass(A))`. When class of A is `single` or `double`, this value is 1, by default.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

'Exponents' — Exponents for the luminance, contrast, and structural terms respectively

`[1 1 1]` (default) | three-element vector of nonnegative real numbers, [`alpha beta gamma`]

Exponents for the luminance, contrast, and structural terms, specified as a three-element vector of nonnegative real numbers, [`alpha beta gamma`].

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

'Radius' — Standard deviation of isotropic Gaussian function

1.5 (default) | positive scalar

Standard deviation of isotropic Gaussian function, specified as a positive scalar. This value is used for weighting the neighborhood pixels around a pixel for estimating local statistics. This weighting is used to avoid blocking artifacts in estimating local statistics.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

'RegularizationConstants' — Regularization constants for the luminance, contrast, and structural terms

three-element vector of nonnegative real numbers, [`C1 C2 C3`]

Regularization constants for the luminance, contrast, and structural terms, specified as a three-element vector of nonnegative real numbers. `ssim` uses these regularization constants to avoid instability for image regions where the local mean or standard deviation is close to zero. Therefore, small non-zero values should be used for these constants.

By default,

- $C1 = (0.01 * L)^2$, where L is the specified `DynamicRange` value.
- $C2 = (0.03 * L)^2$, where L is the specified `DynamicRange` value.
- $C3 = C2 / 2$

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

Output Arguments

ssimval — Structural Similarity (SSIM) Index

scalar

Structural Similarity (SSIM) Index, returned as a scalar `double`, except when `A` and `ref` are of class `single`, in which case `ssimval` is of class `single`.

ssimmap — Local values of Structural Similarity (SSIM) Index

numeric array

Local values of Structural Similarity (SSIM) Index, returned as a numeric array of class `double` except when `A` and `ref` are of class `single`, in which case `ssimmap` is of class `single`. `ssimmap` is an array of the same size as input image `A`.

More About

Structural Similarity Index

An image quality metric that assesses the visual impact of three characteristics of an image: luminance, contrast and structure.

Algorithms

The Structural Similarity (SSIM) Index quality assessment index is based on the computation of three terms, namely the luminance term, the contrast term and the structural term. The overall index is a multiplicative combination of the three terms.

$$SSIM(x, y) = [l(x, y)]^\alpha \cdot [c(x, y)]^\beta \cdot [s(x, y)]^\gamma$$

where

$$l(x, y) = \frac{2\mu_x\mu_y + C_1}{\mu_x^2 + \mu_y^2 + C_1},$$

$$c(x, y) = \frac{2\sigma_x\sigma_y + C_2}{\sigma_x^2 + \sigma_y^2 + C_2},$$

$$s(x, y) = \frac{\sigma_{xy} + C_3}{\sigma_x\sigma_y + C_3}$$

where μ_x , μ_y , σ_x , σ_y , and σ_{xy} are the local means, standard deviations, and cross-covariance for images x , y . If $\alpha = \beta = \gamma = 1$ (the default for Exponents), and $C_3 = C_2/2$ (default selection of C_3) the index simplifies to:

$$SSIM(x, y) = \frac{(2\mu_x\mu_y + C_1)(2\sigma_{xy} + C_2)}{(\mu_x^2 + \mu_y^2 + C_1)(\sigma_x^2 + \sigma_y^2 + C_2)}$$

References

- [1] Wang Zhou, Bovik, Alan C., Sheikh, Hamid R., and Simoncelli, Eero P. *Image Quality Assessment: From Error Visibility to Structural Similarity*. IEEE Transactions on Image Processing, Volume 13, Issue 4, pp. 600–612, April 2004

See Also

immse | mean | median | psnr | sum | var

Introduced in R2014a

std2

Standard deviation of matrix elements

Syntax

```
B = std2(A)
gpuarrayB = std2(gpuarrayA)
```

Description

`B = std2(A)` returns the scalar `B`, the standard deviation of the values in `A`.

`gpuarrayB = std2(gpuarrayA)` performs the operation on a GPU. The input image is a `gpuArray` image. The output is a `gpuArray` scalar. This syntax requires the Parallel Computing Toolbox.

Class Support

`A` can be numeric or `logical`. `B` is a scalar of class `double`.

`gpuarrayA` is a numeric or `logical` `gpuArray`. `gpuarrayB` is a scalar `double` `gpuArray`.

Examples

Calculate the standard deviation.

```
I = imread('liftingbody.png');
val = std2(I);

val =

    31.6897
```

Calculate the standard deviation on a GPU.

```
I = gpuArray(imread('liftingbody.png'));  
val = std2(I)
```

More About

Algorithms

std2 computes the standard deviation of the array A using `std(A(:))`.

See Also

[corr2](#) | [mean2](#) | [std](#) | [mean](#) | [gpuArray](#)

Introduced before R2006a

stdfilt

Local standard deviation of image

Syntax

```
J = stdfilt(I)
J = stdfilt(I, NHOOD)
gpuarrayJ = stdfilt(gpuarrayI, ___)
```

Description

`J = stdfilt(I)` returns the array `J`, where each output pixel contains the standard deviation of the 3-by-3 neighborhood around the corresponding pixel in the input image `I`. `I` can have any dimension. The output image `J` is the same size as the input image `I`.

For pixels on the borders of `I`, `stdfilt` uses symmetric padding. In symmetric padding, the values of padding pixels are a mirror reflection of the border pixels in `I`.

`J = stdfilt(I, NHOOD)` calculates the local standard deviation of the input image `I`, where you specify the neighborhood in `NHOOD`. `NHOOD` is a multidimensional array of zeros and ones where the nonzero elements specify the neighbors. `NHOOD`'s size must be odd in each dimension. By default, `stdfilt` uses the neighborhood `ones(3)`. `stdfilt` determines the center element of the neighborhood by `floor((size(NHOOD) + 1)/2)`.

`gpuarrayJ = stdfilt(gpuarrayI, ___)` performs the conversion on a GPU. The input image and the output image are `gpuArrays`. This syntax requires the Parallel Computing Toolbox.

Class Support

`I` can be logical or numeric and must be real and nonsparse. `NHOOD` can be logical or numeric and must contain zeros and/or ones. `J` is of class `double`.

The `gpuArray` `gpuarrayI` can be logical or numeric and must be real and nonsparse. The `gpuArray` returned `gpuarrayJ` is of class `double`.

Notes

To specify neighborhoods of various shapes, such as a disk, use the `strel` function to create a structuring element object and then extract the neighborhood from the structuring element object's `neighborhood` property.

Examples

Perform standard deviation filtering.

```
I = imread('circuit.tif');  
J = stdfilt(I);  
imshow(I);  
figure, imshow(J,[]);
```

Perform standard deviation filtering on a GPU.

```
I = gpuArray(imread('circuit.tif'));  
J = stdfilt(I);  
imshow(I);  
figure, imshow(J,[]);
```

See Also

[entropyfilt](#) | [getnhood](#) | [rangefilt](#) | [std2](#) | [strel](#) | [offsetstrel](#) | [gpuArray](#)

Introduced before R2006a

strel class

Morphological structuring element

Note: To create the following nonflat structuring element shapes, use `offsetstrel` instead.

- `SE = strel('arbitrary',NHOOD,HEIGHT)`
- `SE = strel('ball',R,H,N)`


The following syntaxes still work, but are not recommended for use.

- `SE = strel('pair',OFFSET)`
 - `SE = strel('periodicline',P,V)`
-

Description

A `strel` object represents a flat morphological *structuring element*, which is an essential part of morphological dilation and erosion operations. (To create a nonflat structuring element, use `offsetstrel`.)

A flat structuring element is a binary valued neighborhood, either 2-D or multidimensional, in which the true pixels are included in the morphological computation, and the false pixels are not. The center pixel of the structuring element, called the *origin*, identifies the pixel in the image being processed. Use the `strel` function to create a flat structuring element. You can use flat structuring elements with both binary and grayscale images. The following figure illustrates a flat structuring element.



Construction

`SE = strel('diamond',R)` creates a diamond-shaped structuring element, where `R` specifies the distance from the structuring element origin to the points of the diamond.

`SE = strel('disk',R,N)` creates a disk-shaped structuring element, where `R` specifies the radius. `N` specifies the number of line structuring elements used to approximate the disk shape. Morphological operations using disk approximations run much faster when the structuring element uses approximations.

`SE = strel('line',len,deg)` creates a linear structuring element that is symmetric with respect to the neighborhood center. `deg` specifies the angle (in degrees) of the line as measured in a counterclockwise direction from the horizontal axis. `len` is approximately the distance between the centers of the structuring element members at opposite ends of the line.

`SE = strel('octagon',R)` creates an octagonal structuring element, where `R` specifies the distance from the structuring element origin to the sides of the octagon, as measured along the horizontal and vertical axes. `R` must be a nonnegative multiple of 3.

`SE = strel('rectangle',MN)` creates a rectangular structuring element, where `MN` specifies the size.

`SE = strel('square',W)` creates a square structuring element whose width is `W` pixels.

`SE = strel('cube',W)` creates a cubic structuring element whose width is `W` pixels. `W` must be a nonnegative integer scalar.

`SE = strel('cuboid',XYZ)` creates a cuboidal structuring element of size `XYZ`.

`SE = strel('sphere',R)` creates a spherical structuring element whose radius is `R` pixels.

`SE = strel('arbitrary',nhood)` creates a structuring element, where `NHOOD` is a matrix of 1s and 0s that specifies the neighborhood. You can omit the `'arbitrary'` string and specify `strel(nhood)`.

“Code Generation” on page 1-1481 support: Yes.

“MATLAB Function Block” on page 1-1481 support: Yes.

Input Arguments

R — Radius of the structuring element in the X-Y plane

nonnegative integer

Radius of the structuring element in the X-Y plane, specified as a nonnegative integer.

For the disk shape, R is the distance from the origin to the edge of the disk.

For the diamond shape, R is the distance from the structuring element origin to the points of the diamond.

Data Types: double

N — Number of periodic line structuring elements used to approximate shape

4 (default) | 0 | 6 | 8

Number of periodic line structuring elements used to approximate shape, specified as the scalar value 0, 4, 6, or 8. When N is greater than 0, the disk-shaped structuring element is approximated by a sequence of N periodic-line structuring elements. When N is 0, `strel` does no approximation, and the structuring element members comprise all pixels whose centers are no greater than R away from the origin. Morphological operations using disk approximations run much faster when the structuring element uses approximations ($N > 0$). Sometimes it is necessary for `strel` to use two extra line structuring elements in the approximation, in which case the number of decomposed structuring elements used is $N + 2$.

Value of N	Behavior
$N > 0$	<code>strel</code> uses a sequence of N (or sometimes $N+2$) periodic line-shaped structuring elements to approximate the shape.
$N = 0$	<code>strel</code> does not use any approximation. The structuring element members comprise all pixels whose centers are no greater than R away from the origin and the corresponding height values are determined from the formula of the ellipsoid specified by R and H.

Data Types: double

MN — Size of rectangle-shaped structuring element

two-element vector of nonnegative integers

Size of rectangle-shaped structuring element, specified as a two-element vector of nonnegative integers. The first element of MN is the number of rows in the structuring element neighborhood and the second element is the number of columns.

Data Types: double

W — Width of square-shaped or cube-shaped structuring element

nonnegative integer scalar

Width of square-shaped or cube-shaped structuring element, specified as a nonnegative integer scalar.

Data Types: double

XYZ — Dimensions of cuboidal-shaped structuring element

three-element vector

Dimensions of cuboidal-shaped structuring element, specified as a three-element vector of nonnegative integers, of the form $[X \ Y \ Z]$. X is the number of rows, Y is the number of columns, and Z is the number of planes in the third dimension.

Data Types: double

nhood — Neighborhood

matrix

Neighborhood, specified as a matrix containing 1's and 0's. The location of the 1's defines the neighborhood for the morphological operation. The center (or origin) of nhood is its center element, given by $\text{floor}((\text{size}(\text{nhood}) + 1)/2)$.

Data Types: double

Properties

Neighborhood — Structuring element neighborhood

logical matrix

Structuring element neighborhood, specified as a matrix of class `logical`.

Data Types: logical

Dimensionality — Dimensions of structuring element

nonnegative scalar

Dimensions of structuring element, specified as a nonnegative scalar of class `double`.

Data Types: `double`

Examples

Create Square Structuring Element

Create an 11-by-11 square structuring element.

```
SE = strel('square', 11)
```

```
SE =
```

`strel` is a square shaped structuring element with properties:

```
    Neighborhood: [11x11 logical]
    Dimensionality: 2
```

Create Line-Shaped Structuring Element

Create a line-shaped structuring element with a length of 10 at an angle of 45 degrees.

```
SE = strel('line', 10, 45)
```

```
SE =
```

`strel` is a line shaped structuring element with properties:

```
    Neighborhood: [7x7 logical]
    Dimensionality: 2
```

View the structuring element.

```
SE.Neighborhood
```

```
ans =
```

```
    0    0    0    0    0    0    1
    0    0    0    0    0    1    0
    0    0    0    0    1    0    0
```

```

0   0   0   1   0   0   0
0   0   1   0   0   0   0
0   1   0   0   0   0   0
1   0   0   0   0   0   0

```

Create Disk-Shaped Structuring Element

Create a disk-shaped structuring element with a radius of 15.

```
SE3 = strel('disk', 15)
```

```
SE3 =
```

```
strel is a disk shaped structuring element with properties:
```

```

    Neighborhood: [29x29 logical]
    Dimensionality: 2

```

Display the disk-shaped structuring element.

```
figure
imshow(SE3.Neighborhood)
```



Create 3-D Sphere-shaped Structuring Element

Create a 3-D sphere-shaped structuring element with a radius of 15.

```
SE = strel('sphere', 15)
```


```
SE =
```

```
strel is a sphere shaped structuring element with properties:
```

```
Neighborhood: [31x31x31 logical]  
Dimensionality: 3
```

Display the structuring element.

```
figure  
isosurface(SE.Neighborhood)
```



Tips

- Structuring elements that do not use approximations ($N = 0$) are not suitable for computing granulometries.

Additional Capabilities

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, note the following:

- All input arguments must be compile-time constants.
- The methods associated with `strel` objects are not supported in code generation.
- Arrays of `strel` objects are not supported.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

Algorithms

For all shapes except 'arbitrary', structuring elements are constructed using a family of techniques known collectively as *structuring element decomposition*. The principle is that dilation by some large structuring elements can be computed faster by dilation with a sequence of smaller structuring elements. For example, dilation by an 11-by-11 square structuring element can be accomplished by dilating first with a 1-by-11 structuring element and then with an 11-by-1 structuring element. This results in a theoretical performance improvement of a factor of 5.5, although in practice the actual performance improvement is somewhat less. Structuring element decompositions used for the 'disk' shape is an approximations—all other decompositions are exact.

Methods

decompose	Return sequence of decomposed structuring elements
reflect	Reflect structuring element
translate	Translate structuring element

References

- [1] van den Boomgard, R, and R. van Balen, "Methods for Fast Morphological Image Transforms Using Bitmapped Images," *Computer Vision, Graphics, and Image Processing: Graphical Models and Image Processing*, Vol. 54, Number 3, pp. 252–254, May 1992.
- [2] Adams, R., "Radial Decomposition of Discs and Spheres," *Computer Vision, Graphics, and Image Processing: Graphical Models and Image Processing*, Vol. 55, Number 5, pp. 325–332, September 1993.
- [3] Jones, R., and P. Soille, "Periodic lines: Definition, cascades, and application to granulometrie," *Pattern Recognition Letters*, Vol. 17, pp. 1057–1063, 1996.

See Also

offsetstrel

More About

- “Structuring Elements”
- Property Attributes

Introduced before R2006a

decompose

Class: `strel`

Return sequence of decomposed structuring elements

Syntax

`SEQ = decompose(SE)`

Description

`SEQ = decompose(SE)` returns an array of structuring elements `SEQ` that are the decomposition of the input structuring element `SE`. `SEQ` is equivalent to `SE`, but the elements of `SEQ` cannot be decomposed further.

`strel` uses decomposition by default for square structuring elements larger than 3-by-3, and disk-shaped structuring elements.

Input Arguments

SE — Structuring element

`strel` object

Structuring element, specified as a `strel` object.

Output Arguments

SEQ — Sequence of structuring elements that approximate the desired shape

array of `strel` objects

Sequence of structuring elements that approximate the desired shape, returned as an array of `strel` objects.

Examples

View Decomposition of Structuring Element

Create a disk-shaped structuring element.

```
se = strel('square',5)
```

```
se =
```

```
strel is a square shaped structuring element with properties:
```

```
    Neighborhood: [5x5 logical]  
    Dimensionality: 2
```

Extract the decomposition of the structuring element.

```
seq = decompose(se)
```

```
seq =
```

```
    2x1 strel array with properties:
```

```
    Neighborhood  
    Dimensionality
```

To see that dilating sequentially with the decomposed structuring elements really does form a 5-by-5 square, use `imdilate` with the full option.

```
imdilate(1,seq,'full')
```

```
ans =
```

```
    1    1    1    1    1  
    1    1    1    1    1  
    1    1    1    1    1  
    1    1    1    1    1  
    1    1    1    1    1
```

Introduced before R2006a

reflect

Class: strel

Reflect structuring element

Syntax

```
se2 = reflect(se)
```

Description

`se2 = reflect(se)` reflects the structuring element (or array of structuring elements) specified by `se`. The method reflects the structuring element through its center. The effect is the same as if you rotated the structuring element's domain 180 degrees around its center (for a 2-D structuring element).

Input Arguments

se — Structuring element or structuring elements

strel object or array of strel objects.

Structuring element or structuring elements, specified as a strel object or array of strel objects. If `se` is an array of structuring element objects, then `reflect(se)` reflects each element of `se`, and `se2` has the same size as `se`.

Output Arguments

se2 — Reflected structuring element or structuring elements

strel object or array of strel objects

Reflected structuring element, returned as a strel object or array of structuring elements.

Examples

Reflect a Structuring Element

Create a structuring element.

```
se = strel([0 0 1; 0 0 0; 0 0 0])
```

```
se =
```

strel is a arbitrary shaped structuring element with properties:

```
    Neighborhood: [3x3 logical]
    Dimensionality: 2
```

Look at the neighborhood.

```
se.Neighborhood
```

```
ans =
```

```
    0    0    1
    0    0    0
    0    0    0
```

Reflect it.

```
se2 = reflect(se)
```

```
se2 =
```

strel is a arbitrary shaped structuring element with properties:

```
    Neighborhood: [3x3 logical]
    Dimensionality: 2
```

Look at the reflected neighborhood.

```
se2.Neighborhood
```

ans =

0	0	0
0	0	0
1	0	0

Introduced before R2006a

translate

Class: `strel`

Translate structuring element

Syntax

`SE2 = translate(SE,V)`

Description

`SE2 = translate(SE,V)` translates the structuring element `SE` in N-D space. `V` is an N-element vector containing the offsets of the desired translation in each dimension.

Input Arguments

SE — Structuring element

`strel` object

Structuring element, specified as a `strel` object.

V — Translation offsets

`strel` object

Translation offsets, specified as a numeric vector.

Output Arguments

SE2 — Translated structuring element

`strel` object

Translated structuring element, returned as a `strel` object.

Examples

Translate Structuring Element

Read an image into the workspace.

```
I = imread('cameraman.tif');
```

Create a structuring element and translate it down and to the right by 25 pixels.

```
se = translate(strel(1), [25 25]);
```

Dilate the image using the translated structuring element.

```
J = imdilate(I,se);
```

Display the original image and the translated image.

```
figure  
imshow(I), title('Original')  
figure  
imshow(J), title('Translated');
```


Original



Translated



Introduced before R2006a

stretchlim

Find limits to contrast stretch image

Syntax

```
Low_High = stretchlim(I)
Low_High = stretchlim(I,Tol)
Low_High = stretchlim(RGB,Tol)
Low_High = stretchlim(gpuarrayI, ___ )
```

Description

`Low_High = stretchlim(I)` returns `Low_High`, a two-element vector of pixel values that specify lower and upper limits that can be used for contrast stretching image `I`. By default, values in `Low_High` specify the bottom 1% and the top 1% of all pixel values. The gray values returned can be used by the `imadjust` function to increase the contrast of an image.

`Low_High = stretchlim(I,Tol)` returns `Low_High`, a two-element vector of pixel values that specify lower and upper limits that can be used for contrast stretching image `I`. where `Tol` specifies the fraction of the image to saturate at low and high pixel values.

`Low_High = stretchlim(RGB,Tol)` returns `Low_High`, a two-element vector of pixel values that specify lower and upper limits that can be used for contrast stretching truecolor image `RGB`.

`Low_High = stretchlim(gpuarrayI, ___)` performs the operation on a GPU. . This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-1497 support: Yes.

“MATLAB Function Block” on page 1-1497 support: Yes.

Examples

Find Limits to Stretch Contrast in Grayscale Image

Read grayscale image into the workspace and display it.

```
I = imread('pout.tif');  
figure  
imshow(I)
```



Adjust the contrast in the image using `stretchlim` to set the limits, and display the result. The example uses the default limits `[0.01 0.99]`, saturating the upper 1% and the lower 1%.

```
J = imadjust(I,stretchlim(I),[]);  
figure  
imshow(J)
```



Find Limits to Stretch Contrast in Grayscale Image on a GPU

Read grayscale image, creating a `gpuArray`.

```
gpuarrayI = gpuArray(imread('pout.tif'));  
figure, imshow(gpuarrayI)
```

Adjust the contrast in the image using `stretchlim` to set the limits. Display the result.

```
gpuarrayJ = imadjust(gpuarrayI,stretchlim(I),[]);  
figure, imshow(gpuarrayJ)
```

Input Arguments

I — Grayscale image

real, nonsparse, numeric array

Grayscale image, specified as a real, nonsparse, numeric array.

Example: `I = imread('pout.tif'); lohi = stretchlim(I);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

Tol — Fraction of the image to saturate

[0.01 0.99] (default) | numeric scalar or two-element vector in the range [0 1]

Fraction of the image to saturate, specified as a numeric scalar or two-element vector [Low_Fract High_Fract] in the range [0 1].

Value	Description
Scalar	If Tol is a scalar, Low_Fract = Tol, and High_Fract = 1 - Low_Fract, which saturates equal fractions at low and high pixel values.
0	If Tol = 0, Low_High = [min(I(:)); max(I(:))].
Default	If you omit the Tol argument, [Low_Fract High_Fract] defaults to [0.01 0.99], saturating 2%.
Too big	If Tol is too big, such that no pixels would be left after saturating low and high pixel values, stretchlim returns [0 1]

Example: `lohi = stretchlim(I,[.02 .80]);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

RGB — Truecolor image

real, nonsparse, numeric array

Truecolor image, specified as a numeric array.

Example: `RGB = imread('peppers.png'); lohi = stretchlim(RGB);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `uint8` | `uint16` | `uint32`

gpuarrayI — Input image

gpuArray

Input image, specified as a gpuArray.

Output Arguments

Low_High — Lower and upper limits for contrast stretching

two-element vector of pixel values

Lower and upper limits for contrast stretching, returned as a two-element vector of pixel values

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

See Also

brighten | decorrstretch | gpuArray | histeq | imadjust

Introduced before R2006a

subimage

Display multiple images in single figure

Syntax

```
subimage(X, map)
subimage(I)
subimage(BW)
subimage(RGB)
subimage(x, y...)
h = subimage(...)
```

Description

You can use `subimage` in conjunction with `subplot` to create figures with multiple images, even if the images have different colormaps. `subimage` works by converting images to truecolor for display purposes, thus avoiding colormap conflicts.

`subimage(X, map)` displays the indexed image `X` with colormap `map` in the current axes.

`subimage(I)` displays the intensity image `I` in the current axes.

`subimage(BW)` displays the binary image `BW` in the current axes.

`subimage(RGB)` displays the truecolor image `RGB` in the current axes.

`subimage(x, y...)` displays an image using a nondefault spatial coordinate system.

`h = subimage(...)` returns a handle to an image object.

Class Support

The input image can be of class `logical`, `uint8`, `uint16`, or `double`.

Examples

```
load trees
[X2,map2] = imread('forest.tif');
subplot(1,2,1), subimage(X,map)
subplot(1,2,2), subimage(X2,map2)
```

See Also

[imshow](#) | [subplot](#)

Introduced before R2006a

superpixels

2-D superpixel oversegmentation of images

Syntax

```
[L,NumLabels] = superpixels(A,N)
[L,NumLabels] = superpixels( ___,Name,Value,...)
```

Description

`[L,NumLabels] = superpixels(A,N)` computes superpixels of the 2-D grayscale or RGB image `A`. `N` specifies the number of superpixels you want to create. The function returns `L`, a label matrix of type `double`, and `NumLabels`, the actual number of superpixels that were computed.

The `superpixels` function uses the simple linear iterative clustering (SLIC) algorithm. This algorithm groups pixels into regions with similar values. Using these regions in image processing operations, such as segmentation, can reduce the complexity of these operations.

`[L,NumLabels] = superpixels(___,Name,Value,...)` computes superpixels of image `A` using with `Name-Value` pairs used to control aspects of the segmentation.

“Code Generation” on page 1-1505 support: Yes.

MATLAB Function Block support: No.

Examples

Compute Superpixels of Input RGB Image

Read image into the workspace.


```
A = imread('kobi.png');
```

Calculate superpixels of the image.

```
[L,N] = superpixels(A,500);
```

Display the superpixel boundaries overlaid on the original image.

```
figure
BW = boundarymask(L);
imshow(imoverlay(A,BW,'cyan'),'InitialMagnification',67)
```



Set the color of each pixel in the output image to the mean RGB color of the superpixel region.

```
outputImage = zeros(size(A),'like',A);
idx = label2idx(L);
numRows = size(A,1);
numCols = size(A,2);
```

```
for labelVal = 1:N
    redIdx = idx{labelVal};
    greenIdx = idx{labelVal}+numRows*numCols;
    blueIdx = idx{labelVal}+2*numRows*numCols;
    outputImage(redIdx) = mean(A(redIdx));
    outputImage(greenIdx) = mean(A(greenIdx));
    outputImage(blueIdx) = mean(A(blueIdx));
end

figure
imshow(outputImage, 'InitialMagnification', 67)
```



- “Plot Land Classification with Color Features and Superpixels”

Input Arguments

A — Input image

real, nonsparse matrix

Input image, specified as a real, nonsparse matrix. **A** can be a 2-D grayscale or 2-D RGB image. When the parameter `isInputLab` is true, the input image must be `single` or `double`.

Data Types: `single` | `double` | `uint8` | `uint16`

N — Desired number of superpixels

numeric scalar

Desired number of superpixels, specified as a numeric scalar.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

Name-Value Pair Arguments

Specify optional comma-separated pairs of **Name**, **Value** arguments. **Name** is the argument name and **Value** is the corresponding value. **Name** must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

Example: `B = superpixels(A,100,'NumIterations', 20);`

'Compactness' — Shape of superpixels

10 (default) | numeric scalar

Shape of superpixels, specified as the comma-separated pair consisting of 'Compactness' and a numeric scalar. The compactness parameter of the SLIC algorithm controls the shape of superpixels. A higher value makes superpixels more regularly shaped, that is, a square. A lower value makes superpixels adhere to boundaries better, making them irregularly shaped. The allowed range is `[0 Inf)`. Typical values for compactness are in the range `[1, 20]`.

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

'IsInputLab' — Input image data is in the *L*a*b** colorspace

false (default) | true

Input image data is in the $L*a*b*$ colorspace, specified as the comma-separated pair consisting of 'IsInputLab' and the logical scalar true or false.

Data Types: single | double | int8 | int16 | int32 | int64 | uint8 | uint16 | uint32 | uint64 | logical

'Method' — Algorithm used to compute superpixels

'slic0' (default) | 'slic'

Algorithm used to compute superpixels, specified as the comma-separated pair consisting of 'Method' and one of the following strings. The `superpixels` function uses two variations of the simple linear iterative clustering (SLIC) algorithm.

String	Meaning
'slic0'	superpixels uses the SLIC0 algorithm to refine 'Compactness' adaptively after the first iteration. This is the default.
'slic'	'Compactness' is constant during clustering.

Data Types: char

'NumIterations' — Number of iterations used in the clustering phase of the algorithm

10 (default) | numeric scalar

Number of iterations used in the clustering phase of the algorithm, specified as the comma-separated pair consisting of 'NumIterations' and a numeric scalar. For most problems it is not necessary to adjust this parameter.

Data Types: single | double | int8 | int16 | int32 | int64 | uint8 | uint16 | uint32 | uint64

Output Arguments

L — Label matrix

numeric array

Label matrix, returned as a numeric array of positive integers, where 1 indicates the first region, 2 the second region, and so on for each superpixel region in the image.

NumLabels — Number of superpixels computed

numeric scalar

Number of superpixels computed, returned as a numeric scalar of type double.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. For more information, see “Code Generation for Image Processing”.

When generating code, note the following:

- All string inputs must be compile-time constants.
- The value of 'IsInputLab' (true or false) must be a compile-time constant.

.

References

- [1] Radhakrishna Achanta, Appu Shaji, Kevin Smith, Aurelien Lucchi, Pascal Fua, and Sabine Susstrunk, *SLIC Superpixels Compared to State-of-the-art Superpixel Methods*. IEEE Transactions on Pattern Analysis and Machine Intelligence, Volume 34, Issue 11, pp. 2274-2282, May 2012
- [2] Radhakrishna Achanta, Appu Shaji, Kevin Smith, Aurelien Lucchi, Pascal Fua, and Sabine Susstrunk, *SLIC Superpixels*. EPFL Technical Report, no. 149300, June 2010.

See Also

boundarymask | imoverlay | label2idx | label2rgb

Introduced in R2016a

tformarray

Apply spatial transformation to N-D array

Syntax

```
B = tformarray(A, T, R, TDIMS_A, TDIMS_B, TSIZE_B, TMAP_B, F)
```

Description

`B = tformarray(A, T, R, TDIMS_A, TDIMS_B, TSIZE_B, TMAP_B, F)` applies a spatial transformation to array `A` to produce array `B`. The `tformarray` function is like `imtransform`, but is intended for problems involving higher-dimensioned arrays or mixed input/output dimensionality, or requiring greater user control or customization. (Anything that can be accomplished with `imtransform` can be accomplished with a combination of `maketform`, `makeresampler`, `findbounds`, and `tformarray`; but for many tasks involving 2-D images, `imtransform` is simpler.)

This table provides a brief description of all the input arguments. See the following section for more detail about each argument. (Click an argument in the table to move to the appropriate section.)

Argument	Description
A	Input array or image
T	Spatial transformation structure, called a <code>TFORM</code> , typically created with <code>maketform</code>
R	Resampler structure, typically created with <code>makeresampler</code>
TDIMS_A	Row vector listing the input transform dimensions
TDIMS_B	Row vector listing the output transform dimensions
TSIZE_B	Output array size in the transform dimensions
TMAP_B	Array of point locations in output space; can be used as an alternative way to specify a spatial transformation
F	Array of fill values

A can be any nonsparse numeric array, and can be real or complex.

T is a **TFORM** structure that defines a particular spatial transformation. For each location in the output transform subscript space (as defined by **TDIMS_B** and **TSIZE_B**), **tformarray** uses **T** and the function **tforminv** to compute the corresponding location in the input transform subscript space (as defined by **TDIMS_A** and **size(A)**).

If **T** is empty, **tformarray** operates as a direct resampling function, applying the resampler defined in **R** to compute values at each transform space location defined in **TMAP_B** (if **TMAP_B** is nonempty), or at each location in the output transform subscript grid.

R is a structure that defines how to interpolate values of the input array at specified locations. **R** is usually created with **makeresampler**, which allows fine control over how to interpolate along each dimension, as well as what input array values to use when interpolating close to the edge of the array.

TDIMS_A and **TDIMS_B** indicate which dimensions of the input and output arrays are involved in the spatial transformation. Each element must be unique, and must be a positive integer. The entries need not be listed in increasing order, but the order matters. It specifies the precise correspondence between dimensions of arrays **A** and **B** and the input and output spaces of the transformer **T**. **length(TDIMS_A)** must equal **T.ndims_in**, and **length(TDIMS_B)** must equal **T.ndims_out**.

For example, if **T** is a 2-D transformation, **TDIMS_A** = [2 1], and **TDIMS_B** = [1 2], then the column dimension and row dimension of **A** correspond to the first and second transformation input-space dimensions, respectively. The row and column dimensions of **B** correspond to the first and second output-space dimensions, respectively.

TSIZE_B specifies the size of the array **B** along the output-space transform dimensions. Note that the size of **B** along nontransform dimensions is taken directly from the size of **A** along those dimensions. If, for example, **T** is a 2-D transformation, **size(A)** = [480 640 3 10], **TDIMS_B** is [2 1], and **TSIZE_B** is [300 200], then **size(B)** is [200 300 3].

TMAP_B is an optional array that provides an alternative way of specifying the correspondence between the position of elements of **B** and the location in output transform space. **TMAP_B** can be used, for example, to compute the result of an image warp at a set of arbitrary locations in output space. If **TMAP_B** is not empty, then the size of **TMAP_B** takes the form

```
[D1 D2 D3 ... DN L]
```

where N equals `length(TDIMS_B)`. The vector `[D1 D2 ... DN]` is used in place of `TSIZE_B`. If `TMAP_B` is not empty, then `TSIZE_B` should be `[]`.

The value of L depends on whether or not `T` is empty. If `T` is not empty, then L is `T.ndims_out`, and each L -dimension point in `TMAP_B` is transformed to an input-space location using `T`. If `T` is empty, then L is `length(TDIMS_A)`, and each L -dimensional point in `TMAP_B` is used directly as a location in input space.

`F` is a double-precision array containing fill values. The fill values in `F` can be used in three situations:

- When a separable resampler is created with `makeresampler` and its `padmethod` is set to either `'fill'` or `'bound'`.
- When a custom resampler is used that supports the `'fill'` or `'bound'` pad methods (with behavior that is specific to the customization).
- When the map from the transform dimensions of `B` to the transform dimensions of `A` is deliberately undefined for some points. Such points are encoded in the input transform space by NaNs in either `TMAP_B` or in the output of `TFORMINV`.

In the first two cases, fill values are used to compute values for output locations that map outside or near the edges of the input array. Fill values are copied into `B` when output locations map well outside the input array. See `makeresampler` for more information about `'fill'` and `'bound'`.

`F` can be a scalar (including NaN), in which case its value is replicated across all the nontransform dimensions. `F` can also be a nonscalar, whose size depends on `size(A)` in the nontransform dimensions. Specifically, if K is the J th nontransform dimension of `A`, then `size(F,J)` must be either `size(A,K)` or 1. As a convenience to the user, `tformarray` replicates `F` across any dimensions with unit size such that after the replication `size(F,J)` equals `size(A,K)`.

For example, suppose `A` represents 10 RGB images and has size 200-by-200-by-3-by-10, `T` is a 2-D transformation, and `TDIMS_A` and `TDIMS_B` are both `[1 2]`. In other words, `tformarray` will apply the same 2-D transform to each color plane of each of the 10 RGB images. In this situation you have several options for `F`:

- `F` can be a scalar, in which case the same fill value is used for each color plane of all 10 images.
- `F` can be a 3-by-1 vector, `[R G B]'`. Then `R`, `G`, and `B` are used as the fill values for the corresponding color planes of each of the 10 images. This can be interpreted as specifying an RGB fill color, with the same color used for all 10 images.

- `F` can be a 1-by-10 vector. This can be interpreted as specifying a different fill value for each of 10 images, with that fill value being used for all three color planes.
- `F` can be a 3-by-10 matrix, which can be interpreted as supplying a different RGB fill color for each of the 10 images.

Class Support

`A` can be any nonsparse numeric array, and can be real or complex. It can also be of class `logical`.

Examples

Create a 2-by-2 checkerboard image where each square is 20 pixels wide, then transform it with a projective transformation. Use a `pad` method of `'circular'` when creating a resampler, so that the output appears to be a perspective view of an infinite checkerboard. Swap the output dimensions. Specify a 100-by-100 output image. Leave `TMAP_B` empty, since `TSIZE_B` is specified. Leave the fill value empty, since it won't be needed.

```
I = checkerboard(20,1,1);
figure; imshow(I)
T = maketform('projective',[1 1; 41 1; 41 41; 1 41],...
             [5 5; 40 5; 35 30; -10 30]);
R = makesampler('cubic','circular');
J = tformarray(I,T,R,[1 2],[2 1],[100 100],[],[]);
figure; imshow(J)
```

See Also

`findbounds` | `imtransform` | `makesampler` | `maketform`

Introduced before R2006a

tformfwd

Apply forward spatial transformation

Syntax

```
[X, Y] = tformfwd(T, U, V)
[X1, X2, X3, ...] = tformfwd(T, U1, U2, U3, ...)
X = tformfwd(T, U)
X = tformfwd(T, U)
[X1, X2, X3, ...] = tformfwd(T, U)
X = tformfwd(T, U1, U2, U3, ...)
X = tformfwd(U, T)
```

Description

`[X, Y] = tformfwd(T, U, V)` applies the 2D-to-2D spatial transformation defined in `T` to coordinate arrays `U` and `V`, mapping the point `[U(k) V(k)]` to the point `[X(k) Y(k)]`.

`T` is a `TFORM` struct created with `maketform`, `fliptform`, or `cp2tform`. Both `T.ndim_in` and `T.ndim_out` must equal 2. `U` and `V` are typically column vectors matching in length. In general, `U` and `V` can have any dimensionality, but must have the same size. In any case, `X` and `Y` will have the same size as `U` and `V`.

`[X1, X2, X3, ...] = tformfwd(T, U1, U2, U3, ...)` applies the `ndims_in`-to-`ndims_out` spatial transformation defined in `TFORM` structure `T` to the coordinate arrays `U1, U2, ..., UNDIM_IN` (where `NDIM_IN = T.ndim_in` and `NDIM_OUT = T.ndim_out`). The number of output arguments must equal `NDIM_OUT`. The transformation maps the point

```
[U1(k) U2(k) ... UNDIM_IN(k)]
```

to the point

```
[X1(k) X2(k) ... XNDIM_OUT(k)].
```

`U1, U2, U3, ...` can have any dimensionality, but must be the same size.

X_1, X_2, X_3, \dots must have this size also.

$X = \text{tformfwd}(T, U)$ applies the `ndims_in`-to-`ndims_out` spatial transformation defined in TFORM structure `T` to each row of `U`, where `U` is an `M`-by-`NDIMS_IN` matrix. It maps the point $U(k, :)$ to the point $X(k, :)$. `X` is an `M`-by-`NDIMS_OUT` matrix.

$X = \text{tformfwd}(T, U)$, where `U` is an $(N+1)$ -dimensional array, maps the point $U(k_1, k_2, \dots, k_N, :)$ to the point $X(k_1, k_2, \dots, k_N, :)$. `size(U, N+1)` must equal `NDIMS_IN`. `X` is an $(N+1)$ -dimensional array, with `size(X, I)` equal to `size(U, I)` for $I = 1, \dots, N$ and `size(X, N+1)` equal to `NDIMS_OUT`.

$[X_1, X_2, X_3, \dots] = \text{tformfwd}(T, U)$ maps an $(N+1)$ -dimensional array to `NDIMS_OUT` equally sized N -dimensional arrays.

$X = \text{tformfwd}(T, U_1, U_2, U_3, \dots)$ maps `NDIMS_IN` N -dimensional arrays to one $(N+1)$ -dimensional array.

Note

$X = \text{tformfwd}(U, T)$ is an older form of the two-argument syntax that remains supported for backward compatibility.

Examples

Create an affine transformation that maps the triangle with vertices $(0,0)$, $(6,3)$, $(-2,5)$ to the triangle with vertices $(-1,-1)$, $(0,-10)$, $(4,4)$.

```
u = [ 0  6 -2]';
v = [ 0  3  5]';
x = [-1  0  4]';
y = [-1 -10  4]';
tform = maketform('affine',[u v],[x y]);
```

Validate the mapping by applying `tformfwd`. Results should equal `[x, y]`

```
[xm, ym] = tformfwd(tform, u, v)
```

See Also

`cp2tform` | `fliptform` | `maketform` | `tforminv`

Introduced before R2006a

tforminv

Apply inverse spatial transformation

Syntax

```
[U,V] = tforminv(T,X,Y)
[U1,U2,U3,...] = tforminv(T,X1,X2,X3,...)
U = tforminv(T,X)
[U1,U2,U3,...] = tforminv(T,X)
U = tforminv(T,X1,X2,X3,...)
```

Description

`[U,V] = tforminv(T,X,Y)` applies the 2D-to-2D inverse transformation defined in TFORM structure `T` to coordinate arrays `X` and `Y`, mapping the point `[X(k) Y(k)]` to the point `[U(k) V(k)]`. Both `T.ndims_in` and `T.ndims_out` must equal 2. `X` and `Y` are typically column vectors matching in length. In general, `X` and `Y` can have any dimensionality, but must have the same size. In any case, `U` and `V` will have the same size as `X` and `Y`.

`[U1,U2,U3,...] = tforminv(T,X1,X2,X3,...)` applies the `NDIMS_OUT`-to-`NDIMS_IN` inverse transformation defined in TFORM structure `T` to the coordinate arrays `X1,X2,...,XNDIMS_OUT` (where `NDIMS_IN = T.ndims_in` and `NDIMS_OUT = T.ndims_out`). The number of output arguments must equal `NDIMS_IN`. The transformation maps the point

$$[X1(k) \ X2(k) \ \dots \ XNDIMS_OUT(k)]$$

to the point

$$[U1(k) \ U2(k) \ \dots \ UNDIMS_IN(k)].$$

`X1,X2,X3,...` can have any dimensionality, but must be the same size.

`U1,U2,U3,...` have this size also.

`U = tforminv(T,X)` applies the `NDIMS_OUT`-to-`NDIMS_IN` inverse transformation defined in TFORM structure `T` to each row of `X`, where `X` is an `M`-by-`NDIMS_OUT` matrix. It maps the point `X(k,:)` to the point `U(k,:)`. `U` is an `M`-by-`NDIMS_IN` matrix.

`U = tforminv(T,X)`, where `X` is an $(N+1)$ -dimensional array, maps the point `X(k1,k2,...,kN,:)` to the point `U(k1,k2,...,kN,:)`. `size(X,N+1)` must equal `NDIMS_OUT`. `U` is an $(N+1)$ -dimensional array, with `size(U,I)` equal to `size(X,I)` for $I = 1, \dots, N$ and `size(U,N+1)` equal to `NDIMS_IN`.

`[U1,U2,U3,...] = tforminv(T,X)` maps an $(N+1)$ -dimensional array to `NDIMS_IN` equally-sized N -dimensional arrays.

`U = tforminv(T,X1,X2,X3,...)` maps `NDIMS_OUT` N -dimensional arrays to one $(N+1)$ -dimensional array.

Note

`U = tforminv(X,T)` is an older form of the two-argument syntax that remains supported for backward compatibility.

Examples

Create an affine transformation that maps the triangle with vertices $(0,0)$, $(6,3)$, $(-2,5)$ to the triangle with vertices $(-1,-1)$, $(0,-10)$, $(4,4)$.

```
u = [ 0  6 -2]';  
v = [ 0  3  5]';  
x = [-1  0  4]';  
y = [-1 -10  4]';  
tform = maketform('affine',[u v],[x y]);
```

Validate the mapping by applying `tforminv`. Results should equal `[u, v]`.

```
[um, vm] = tforminv(tform, x, y)
```

See Also

`cp2tform` | `tformfwd` | `maketform` | `fliptform`

Introduced before R2006a

tonemap

Render high dynamic range image for viewing

Syntax

```
RGB = tonemap(HDR)
RGB = tonemap(HDR, param1, val1, ...)
```

Description

`RGB = tonemap(HDR)` converts the high dynamic range image `HDR` to a lower dynamic range image, `RGB`, suitable for display, using a process called tone mapping. Tone mapping is a technique used to approximate the appearance of high dynamic range images on a display with a more limited dynamic range.

`RGB = tonemap(HDR, param1, val1, ...)` performs tone mapping where parameters control various aspects of the operation. The following table lists these parameters.

Parameter	Description
'AdjustLightness'	A two-element vector in the form [<code>low high</code>] that specifies the overall lightness of the rendered image. <code>low</code> and <code>high</code> are luminance values of the low dynamic range image, in the range <code>[0, 1]</code> . These values are passed to <code>imadjust</code> .
'AdjustSaturation'	A numeric value that specifies the saturation of colors in the rendered image. When the value is greater than 1, the colors are more saturated. When the value is in the range <code>[0, 1)</code> colors are less saturated.
'NumberOfTiles'	A two-element vector of the form [<code>rows cols</code>] that specifies the number of tiles used during the adaptive histogram equalization part of the tone mapping operation. <code>rows</code> and <code>cols</code> specify the number of tile rows and columns. Both <code>rows</code> and <code>cols</code> must be at least 2. The total number of image tiles is equal to <code>rows * cols</code> . A

Parameter	Description
	larger number of tiles results in an image with greater local contrast. The default for <code>rows</code> and <code>cols</code> is 4.

Class Support

The high dynamic range image HDR must be a m-by-n-by-3 `single` or `double` array. The output image RGB is an m-by-n-by-3 `uint8` image.

Examples

Load a high dynamic range image, convert it to a low dynamic range image while deepening shadows and increasing saturation, and display the results.

```
hdr = hdrread('office.hdr');
imshow(hdr)
rgb = tonemap(hdr, 'AdjustLightness', [0.1 1], ...
               'AdjustSaturation', 1.5);
figure;
imshow(rgb)
```

See Also

`adaptHISTeq` | `hdrread` | `stretchlim`

Introduced in R2007b

truesize

Adjust display size of image

Syntax

```
truesize(fig,[mrows ncols])
```

Description

`truesize(fig,[mrows ncols])` adjusts the display size of an image. `fig` is a figure containing a single image or a single image with a colorbar. `[mrows ncols]` is a 1-by-2 vector that specifies the requested screen area (in pixels) that the image should occupy.

`truesize(fig)` uses the image height and width for `[mrows ncols]`. This results in the display having one screen pixel for each image pixel.

If you do not specify a figure, `truesize` uses the current figure.

Examples

Fit image to figure window.

```
imshow(checkerboard,'InitialMagnification','fit')
```

Resize image and figure to show image at its 80-by-80 pixel size.

```
truesize
```

See Also

`imshow` | `iptsetpref` | `iptgetpref`

Introduced before R2006a

uintlut

Compute new values of **A** based on lookup table (LUT)

Syntax

```
B = uintlut(A,LUT)
```

Note: `uintlut` has been removed. Use `intlut` instead.

Class Support

A must be `uint8` or `uint16`. If **A** is `uint8`, then **LUT** must be a `uint8` vector with 256 elements. If **A** is `uint16`, then **LUT** must be a `uint16` vector with 65536 elements. **B** has the same size and class as **A**.

Examples

```
A = uint8([1 2 3 4; 5 6 7 8;9 10 11 12]);  
LUT = repmat(uint8([0 150 200 255]),1,64);  
B = uintlut(A,LUT);  
imshow(A,[]), figure, imshow(B);
```

See Also

`impixel` | `improfile`

Introduced before R2006a

visboundaries

Plot region boundaries

Syntax

```
visboundaries(BW)
visboundaries(B)
visboundaries(AX, ___)
H = visboundaries(___ )
H = visboundaries(____,Name,Value)
```

Description

`visboundaries(BW)` draws boundaries of regions in the binary image `BW` on the current axes. `BW` is a 2D binary image where pixels that are logical `true` belong to the foreground region and pixels that are logical `false` constitute the background. `visboundaries` uses `bwboundaries` to find the boundary pixel locations in the image.

`visboundaries(B)` draws region boundaries specified by `B`, where `B` is a cell array containing the boundary pixel locations of the regions, similar in structure to the first output from `bwboundaries`. Each cell contains a Q -by-2 matrix, where Q is the number of boundary pixels for the corresponding region. Each row of these Q -by-2 matrices contains the row and column coordinates of a boundary pixel.

`visboundaries(AX, ___)` draws region boundaries on the axes specified by `AX`.

`H = visboundaries(___)` returns a handle to an `hggroup` object for the boundaries. The `hggroup` object, `H`, is the child of the axes object, `AX`.

`H = visboundaries(____,Name,Value)` passes the name-value pair arguments to specify additional properties of the boundaries. Parameter names can be abbreviated.

Examples

Compute Boundaries and Plot on Image

Read image.


```
BW = imread('blobs.png');
```

Compute boundaries.

```
B = bwboundaries(BW);
```

Display image and plot boundaries on image.

```
imshow(BW)  
hold on  
visboundaries(B)
```



Visualize Segmentation Result

Read image and display it.

```
I = imread('toyobjects.png');
```

```
imshow(I)  
hold on
```




Segment the image using active contour. First, specify the initial contour location close to the object that is to be segmented.

```
mask = false(size(I));  
mask(50:150,40:170) = true;
```

Display the initial contour on the original image in blue.

```
visboundaries(mask, 'Color', 'b');
```




Segment the image using the 'edge' method using 200 iterations.

```
bw = activecontour(I, mask, 200, 'edge');
```

Display the final contour on the original image in red.

```
visboundaries(bw, 'Color', 'r');  
title('Blue - Initial Contour, Red - Final Contour');
```


Blue - Initial Contour, Red - Final Contour



Input Arguments

BW — Binary image

logical array

Binary image, specified as a logical array.

Data Types: `logical`

B — Boundary pixel locations

cell array of Q -by-2 matrices containing row and column coordinates

Boundary pixel locations, specified as a cell array of Q -by-2 matrices containing row and column coordinates, where Q is the number of boundary pixels for the corresponding region.

Data Types: `cell`

AX — Image on which to draw boundaries

current axes (default) | handle to an axes object

Image on which to draw boundaries, specified as a handle to an axes object.

Data Types: `double`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1`, `Value1`, ..., `NameN`, `ValueN`.

Example: `visboundaries(bw, 'Color', 'r');`

'Color' — Color of the boundary

MATLAB color spec

Color of the boundary, specified as a MATLAB colorspec.

Example: `visboundaries(bw, 'Color', 'r');`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical` | `char`

Complex Number Support: Yes

'LineStyle' — Style of boundary line

solid line('-') (default) | MATLAB line spec

Style of boundary line, specified as a MATLAB line spec.

Example: `visboundaries(bw, 'LineStyle', '-.');`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `char`

'LineWidth' — Width of the line used for the boundary

2 points (default) | numeric value

Width of the line used for the boundary, specified as a numeric value. Specify this value in points, where one point = 1/72 inch.

Example: `visboundaries(bw, 'LineWidth', 4);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

'EnhanceVisibility' — Augment the drawn boundary with contrasting features`true` (default) | `false`

Augment the drawn boundary with contrasting features to improve visibility on a varying background, specified as the logical flag `true` or `false`.

Example: `visboundaries(bw, 'EnhanceVisibility', true);`

Data Types: `logical`

Output Arguments

H — Handle to the boundary lines`hgroup` handle

Handle to the boundary line, specified as a handle to an `hgroup` object. The `hgroup` object is the child of the axes object, `AX`.

See Also`bwboundaries` | `bwperim` | `bwtraceboundary` | `viscircles`**Introduced in R2015a**

viscircles

Create circle

Syntax

```
viscircles(centers, radii)
viscircles(ax, centers, radii)
h = viscircles(ax, centers, radii)
h = viscircles( ____, Name, Value)
```

Description

`viscircles(centers, radii)` draws circles with specified `centers` and `radii` onto the current axes.

`viscircles(ax, centers, radii)` draws circles onto the axes specified by `ax`.

`h = viscircles(ax, centers, radii)` draws circles and returns a handle to the circles created. This handle is an `hggroup` object that is a child of the `axes` object, `ax`.

`h = viscircles(____, Name, Value)` specifies additional options with one or more `Name, Value` pair arguments, using any of the previous syntaxes. Parameter names can be abbreviated.


Examples

Draw Lines Around Bright and Dark Circles in Image

This example shows how to draw lines around both bright and dark circles in an image.

Read the image into the workspace and display it.

```
A = imread('circlesBrightDark.png');
imshow(A)
```



Define the radius range.

```
Rmin = 30;  
Rmax = 65;
```

Find all the bright circles in the image within the radius range.


```
[centersBright, radiiBright] = imfindcircles(A,[Rmin Rmax], 'ObjectPolarity', 'bright');
```

Find all the dark circles in the image within the radius range.

```
[centersDark, radiiDark] = imfindcircles(A,[Rmin Rmax], 'ObjectPolarity', 'dark');
```


Draw blue lines around the edges of the bright circles.

```
viscircles(centersBright, radiiBright, 'Color', 'b');
```



Draw red dashed lines around the edges of the dark circles.

```
viscircles(centersDark, radiiDark, 'LineStyle', '--');
```



Input Arguments

centers — Coordinates of circle centers
two-column matrix

Coordinates of circle centers, specified as a P-by-2 matrix, such as that obtained from `imfindcircles`. The *x*-coordinates of the circle centers are in the first column and the *y*-coordinates are in the second column. The coordinates can be integers (of any numeric type) or floating-point values (of type `double` or `single`).

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

radii — Circle radii

column vector

Circle radii, specified as a column vector such as that returned by `imfindcircles`. The radius value at `radii(j)` corresponds to the circle with center coordinates `centers(j,:)`. The values of `radii` can be nonnegative integers (of any numeric type) or floating-point values (of type `double` or `single`).

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64`

ax — Axes in which to draw circles

handle

Axes in which to draw circles, specified as a handle object returned by `gca` or `axes`.

Data Types: `double`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1, Value1, ..., NameN, ValueN`.

Example: `'Color', 'b'` specifies blue circle edges, using the short name for blue.

'EnhanceVisibility' — Augment drawn circles with contrasting features to improve visibility

`'true'` (default) | `'false'`

Augment drawn circles with contrasting features to improve visibility, specified as a logical value `true` or `false`. If you set the value to `true`, `viscircles` draws a contrasting circle below the colored circle.

Data Types: `logical`

'Color' — Color of circle edge

'red' (default) | [R G B] | short name | long name

Color of circle edges, specified as a MATLAB `ColorSpec` value.

Example: `'Color', 'b'` specifies blue circle edges.

'LineStyle' — Line style of circle edge

'-' (default) | '- -' | ':'

Line style of circle edge, specified as the comma-separated pair consisting of `'LineStyle'` and any line specifier in the table below.

Specifier	Line Style
' - '	Solid line (default)
' - - '	Dashed line
' : '	Dotted line
' - . '	Dash-dot line
' none '	No line

Example: `'LineStyle', '- -'` specifies a dashed line at each circle edge.

'LineWidth' — Width of circle edge

2 (default) | double

Width of circle edge, specified a positive floating-point `double` value. Line width is expressed in points, where each point equals 1/72 of an inch.

Example: `'LineWidth', 4` specifies a 4-point line width.

Output Arguments

h — Circles drawn

Handle to an `hgroup` object

Circles drawn, returned as a handle to an `hgroup` object. This handle is a child of the axes object, `ax`.

See Also

`imdistline` | `imfindcircles` | `imtool`

Introduced in R2012a

warp

Display image as texture-mapped surface

Syntax

```
warp(X, map)
warp(I, n)
warp(BW)
warp(RGB)
warp(z, ...)
warp(x, y, z...)
h = warp(...)
```

Description

`warp(X, map)` displays the indexed image `X` with colormap `map` as a texture map on a simple rectangular surface.

`warp(I, n)` displays the intensity image `I` with grayscale colormap of length `n` as a texture map on a simple rectangular surface.

`warp(BW)` displays the binary image `BW` as a texture map on a simple rectangular surface.

`warp(RGB)` displays the RGB image in the array `RGB` as a texture map on a simple rectangular surface.

`warp(z, ...)` displays the image on the surface `z`.

`warp(x, y, z...)` displays the image on the surface `(x, y, z)`.

`h = warp(...)` returns a handle to a texture-mapped surface.

Class Support

The input image can be of class `logical`, `uint8`, `uint16`, or `double`.

More About

Tips

Texture-mapped surfaces are generally rendered more slowly than images.

See Also

`imshow` | `image` | `imagesc` | `surf`

Introduced before R2006a

watershed

Watershed transform

Syntax

```
L = watershed(A)
L = watershed(A,conn)
```

Description

`L = watershed(A)` returns a label matrix `L` that identifies the watershed regions of the input matrix `A`, which can have any dimension. The watershed transform finds "catchment basins" or "watershed ridge lines" in an image by treating it as a surface where light pixels represent high elevations and dark pixels represent low elevations. The elements of `L` are integer values greater than or equal to 0. The elements labeled 0 do not belong to a unique watershed region. The elements labeled 1 belong to the first watershed region, the elements labeled 2 belong to the second watershed region, and so on. By default, `watershed` uses 8-connected neighborhoods for 2-D inputs and 26-connected neighborhoods for 3-D inputs. For higher dimensions, `watershed` uses the connectivity given by `conndef(ndims(A), 'maximal')`.

`L = watershed(A,conn)` specifies the connectivity to be used in the watershed computation.

“Code Generation” on page 1-1544 support: Yes.

MATLAB Function Block support: No.


Examples

Compute Watershed Transform and Display Resulting Label Matrix

Compute the watershed transform and display the resulting label matrix as an RGB image. This example works with 2-D images.

Create a binary image containing two overlapping circular objects and display it.


```
center1 = -10;  
center2 = -center1;  
dist = sqrt(2*(2*center1)^2);  
radius = dist/2 * 1.4;  
lims = [floor(center1-1.2*radius) ceil(center2+1.2*radius)];  
[x,y] = meshgrid(lims(1):lims(2));  
bw1 = sqrt((x-center1).^2 + (y-center1).^2) <= radius;  
bw2 = sqrt((x-center2).^2 + (y-center2).^2) <= radius;  
bw = bw1 | bw2;  
figure  
imshow(bw, 'InitialMagnification','fit'), title('bw')
```



Compute the distance transform of the complement of the binary image.

```
D = bwdist(~bw);
```

```
figure
imshow(D,[],'InitialMagnification','fit')
title('Distance transform of ~bw')
```



Complement the distance transform, and force pixels that don't belong to the objects to be at $-\text{Inf}$.


```
D = -D;
D(~bw) = -Inf;
```

Compute the watershed transform and display the resulting label matrix as an RGB image.

```
L = watershed(D);
rgb = label2rgb(L,'jet',[.5 .5 .5]);
```



```
figure
imshow(rgb, 'InitialMagnification', 'fit')
title('Watershed transform of D')
```



Compute Watershed Transform of 3-D Binary Image


Make a 3-D binary image containing two overlapping spheres.

```
center1 = -10;
center2 = -center1;
dist = sqrt(3*(2*center1)^2);
radius = dist/2 * 1.4;
lims = [floor(center1-1.2*radius) ceil(center2+1.2*radius)];
[x,y,z] = meshgrid(lims(1):lims(2));
bw1 = sqrt((x-center1).^2 + (y-center1).^2 + ...
```

```

        (z-center1).^2) <= radius;
bw2 = sqrt((x-center2).^2 + (y-center2).^2 + ...
        (z-center2).^2) <= radius;
bw = bw1 | bw2;
figure, isosurface(x,y,z,bw,0.5), axis equal, title('BW')
xlabel x, ylabel y, zlabel z
xlim(lims), ylim(lims), zlim(lims)
view(3), camlight, lighting gouraud

```



Compute the distance transform.


```

D = bwdist(-bw);
figure, isosurface(x,y,z,D,radius/2), axis equal
title('Isosurface of distance transform')

```

```
xlabel x, ylabel y, zlabel z
xlim(lims), ylim(lims), zlim(lims)
view(3), camlight, lighting gouraud
```

Isosurface of distance transform




Complement the distance transform, force nonobject pixels to be $-\text{Inf}$, and then compute the watershed transform.

```
D = -D;
D(~bw) = -Inf;
L = watershed(D);
figure
isosurface(x,y,z,L==2,0.5)
isosurface(x,y,z,L==3,0.5)
axis equal
```

```
title('Segmented objects')  
xlabel x, ylabel y, zlabel z  
xlim(lims), ylim(lims), zlim(lims)  
view(3), camlight, lighting gouraud
```

Segmented objects



Input Arguments

A — Input image

real, nonsparse, numeric or logical array of any dimension

Input image, specified as a real, nonsparse, numeric, or logical array of any dimension.

Example: `RGB = imread('pears.png');` `I = rgb2gray(RGB);`

Data Types: `single` | `double` | `int8` | `int16` | `int32` | `int64` | `uint8` | `uint16` | `uint32` | `uint64` | `logical`

conn — Connectivity

8 (for 2-D images) (default) | 4 | 6 | 18 | 26 | 3-by-3-by- ... -by-3 matrix

Connectivity, specified as one of the values in this table.

Value	Meaning
Two-dimensional connectivities	
4	4-connected neighborhood
8	8-connected neighborhood
Three-dimensional connectivities	
6	6-connected neighborhood
18	18-connected neighborhood
26	26-connected neighborhood

Connectivity can also be defined in a more general way for any dimension by using for `conn` a 3-by-3-by- ... -by-3 matrix of 0s and 1s. The 1-valued elements define neighborhood locations relative to the center element of `conn`, which must be symmetric around its center element.

Note If you specify a nondefault connectivity, pixels on the edge of the image might not be considered to be border pixels. For example, if `conn = [0 0 0; 1 1 1; 0 0 0]`, elements on the first and last row are not considered to be border pixels because, according to that connectivity definition, they are not connected to the region outside the image.

Example: `L = watershed(I,4);`

Data Types: `double` | `logical`

Output Arguments

L — Label matrix

numeric array of unsigned integers

Label matrix, specified as a numeric array of unsigned integers.

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

When generating code, note:

- Supports only 2-D images
- Supports only 4 or 8 connectivity
- Supports images containing up to 65,535 regions
- Output type is always `uint16`

Tips

- The watershed transform algorithm used by this function changed in version 5.4 (R2007a) of the Image Processing Toolbox software. The previous algorithm occasionally produced labeled watershed basins that were not contiguous. If you need to obtain the same results as the previous algorithm, use the function `watershed_old`.

Algorithms

`watershed` uses the Fernand Meyer algorithm [1].

References

- [1] Meyer, Fernand, "Topographic distance and watershed lines," *Signal Processing*, Vol. 38, July 1994, pp. 113-125.

See Also

`bwdist` | `bwlabel` | `bwlabeln` | `regionprops`

Introduced before R2006a

whitepoint

XYZ color values of standard illuminants

Syntax

```
xyz = whitepoint(string)  
xyz = whitepoint
```

Description

`xyz = whitepoint(string)` returns `xyz`, a three-element row vector of *XYZ* values scaled so that $Y = 1$. `string` specifies the white reference illuminant. The following table lists all the possible values for `string`. The default value is enclosed in braces (`{}`).

Value	Description
'a'	CIE standard illuminant A
'c'	CIE standard illuminant C
'd50'	CIE standard illuminant D50
'd55'	CIE standard illuminant D55
'd65'	CIE standard illuminant D65
{'icc'}	ICC standard profile connection space illuminant; a 16-bit fractional approximation of D50

`xyz = whitepoint` is the same as `xyz = whitepoint('icc')`.

Class Support

`string` is a character array. `xyz` is of class `double`.

Examples

Return the *XYZ* color space representation of the default white reference illuminant 'icc'.


```
wp_icc = whitepoint
```

```
wp_icc =
```

```
    0.9642    1.0000    0.8249
```

See Also

```
applycform | lab2double | lab2uint8 | lab2uint16 | makecform | xyz2double  
| xyz2uint16
```

Introduced before R2006a

wiener2

2-D adaptive noise-removal filtering

Compatibility

The syntax `wiener2(I,[m n],[mblock nblock],noise)` has been removed. Use the `wiener2(I,[m n],noise)` syntax instead.

Syntax

```
J = wiener2(I,[m n],noise)
[J,noise] = wiener2(I,[m n])
```

Description

`wiener2` lowpass-filters a grayscale image that has been degraded by constant power additive noise. `wiener2` uses a pixelwise adaptive Wiener method based on statistics estimated from a local neighborhood of each pixel.

`J = wiener2(I,[m n],noise)` filters the image `I` using pixelwise adaptive Wiener filtering, using neighborhoods of size `m`-by-`n` to estimate the local image mean and standard deviation. If you omit the `[m n]` argument, `m` and `n` default to 3. The additive noise (Gaussian white noise) power is assumed to be `noise`.

`[J,noise] = wiener2(I,[m n])` also estimates the additive noise power before doing the filtering. `wiener2` returns this estimate in `noise`.

Class Support

The input image `I` is a two-dimensional image of class `uint8`, `uint16`, `int16`, `single`, or `double`. The output image `J` is of the same size and class as `I`.

Examples

For an example, see “Remove Noise By Adaptive Filtering”.

More About

Algorithms

`wiener2` estimates the local mean and variance around each pixel.

$$\mu = \frac{1}{NM} \sum_{n_1, n_2 \in \eta} a(n_1, n_2)$$

and

$$\sigma^2 = \frac{1}{NM} \sum_{n_1, n_2 \in \eta} a^2(n_1, n_2) - \mu^2,$$

where η is the N -by- M local neighborhood of each pixel in the image A . `wiener2` then creates a pixelwise Wiener filter using these estimates,

$$b(n_1, n_2) = \mu + \frac{\sigma^2 - v^2}{\sigma^2} (a(n_1, n_2) - \mu),$$

where v^2 is the noise variance. If the noise variance is not given, `wiener2` uses the average of all the local estimated variances.

References

- [1] Lim, Jae S., *Two-Dimensional Signal and Image Processing*, Englewood Cliffs, NJ, Prentice Hall, 1990, p. 548, equations 9.26, 9.27, and 9.29.

See Also

`filter2` | `medfilt2`

Introduced before R2006a

xyz2double

Convert *XYZ* color values to `double`

Syntax

```
xyxd = xyz2double(XYZ)
```

Description

`xyxd = xyz2double(XYZ)` converts an M-by-3 or M-by-N-by-3 array of *XYZ* color values to `double`. `xyxd` has the same size as *XYZ*.

The Image Processing Toolbox software follows the convention that double-precision *XYZ* arrays contain 1931 CIE *XYZ* values. *XYZ* arrays that are `uint16` follow the convention in the ICC profile specification (ICC.1:2001-4, www.color.org) for representing *XYZ* values as unsigned 16-bit integers. There is no standard representation of *XYZ* values as unsigned 8-bit integers. The ICC encoding convention is illustrated by this table.

Value (X, Y, or Z)	uint16 Value
0.0	0
1.0	32768
$1.0 + (32767/32768)$	65535

Class Support

`xyz` is a `uint16` or `double` array that must be real and nonsparse. `xyzd` is of class `double`.

Examples

Convert `uint16`-encoded *XYZ* values to `double`.

```
xyz2double(uint16([100 32768 65535]))
```

ans =

0.0031 1.0000 2.0000

See Also

[applycform](#) | [lab2double](#) | [lab2uint16](#) | [lab2uint8](#) | [makecform](#) | [whitepoint](#)
| [xyz2uint16](#)

Introduced before R2006a

xyz2rgb

Convert CIE 1931 XYZ to RGB

Syntax

```
rgb = xyz2rgb(xyz)
rgb = xyz2rgb(xyz, Name, Value)
```

Description

`rgb = xyz2rgb(xyz)` converts CIE 1931 XYZ values to RGB values.

`rgb = xyz2rgb(xyz, Name, Value)` specifies additional options with one or more Name, Value pair arguments.

Examples

Convert XYZ color to sRGB

Convert a color value in the XYZ color space to the sRGB color space.

```
xyz2rgb([0.25 0.40 0.10])
```

```
ans =
```

```
    0.4174    0.7434    0.2152
```

Convert XYZ Color to Adobe RGB

Convert the color value in XYZ color space to the Adobe RGB (1998) color space.

```
xyz2rgb([0.25 0.40 0.10], 'ColorSpace', 'adobe-rgb-1998')
```

```
ans =
```

```
0.5323 0.7377 0.2730
```

Convert XYZ color to sRGB Specifying Whitepoint

Convert an XYZ color value to sRGB specifying the D50 whitepoint.

```
xyz2rgb([0.25 0.40 0.10], 'WhitePoint', 'd50')
```

```
ans =
```

```
0.3276 0.7517 0.2869
```

Convert XYZ color to 8-bit-encoded RGB Color

Convert an XYZ color value to an 8-bit encoded RGB color value.

```
xyz2rgb([0.25 0.40 0.10], 'OutputType', 'uint8')
```

```
ans =
```

```
106 190 55
```

Input Arguments

xyz — Color values to convert

P-by-3 matrix | M-by-N-by-3 image array | M-by-N-by-3-by-F image stack

Color values to convert, specified as a P-by-3 matrix of color values (one color per row), an M-by-N-by-3 image array, or an M-by-N-by-3-by-F image stack.

Data Types: `single` | `double`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single

quotes (' '). You can specify several name and value pair arguments in any order as Name1, Value1, . . . , NameN, ValueN.

Example: `xyz2rgb([0.25 0.40 0.10], 'ColorSpace', 'adobe-rgb-1998')`

'ColorSpace' — Color space of the input RGB values

'srgb' (default) | 'adobe-rgb-1998'

Color space of the input RGB values, specified as the text string 'srgb' or 'adobe-rgb-1998'.

Data Types: char

'WhitePoint' — Reference white point

'd65' (default) | 'a' | 'c' | 'd50' | 'icc' | 'e' | 1-by-3 vector

Reference white point, specified as a 1-by-3 vector or one of the CIE standard illuminants, listed in the following table.

String Value	White Point
'a'	CIE standard illuminant A, [1.0985, 1.0000, 0.3558]. Simulates typical, domestic, tungsten-filament lighting.
'c'	CIE standard illuminant C, [0.9807, 1.0000, 1.1822]. Simulates daylight with correlated color temperature of 4874 K. Deprecated by CIE.
'd50'	CIE standard illuminant D50, [0.9642, 1.0000, 0.8251]. Simulates daylight with correlated color temperature of 5003 K.
'd65'	CIE standard illuminant D65, [0.9504, 1.0000, 1.0888]. Simulates daylight with correlated color temperature of 6504 K.
'icc'	Profile Connection Space (PCS) illuminant used in ICC profiles. Approximation of [0.962, 1.000, 0.8249] using fixed-point, signed, 32-bit numbers with 16 fractional bits. Actual value: [31595, 32768, 27030] / 32768.
'e'	Equal-energy radiator. Useful as a theoretical reference. [1.000, 1.000, 1.000].

Data Types: single | double | char

'OutputType' — Data type of returned RGB values

'double' | 'single' | 'uint8' | 'uint16'

Data type of returned RGB values, specified as one of the following text strings: 'double', 'single', 'uint8', or 'uint16'. If you do not specify `OutputType`, the output type is the same type as the input.

Data Types: char

Output Arguments

rgb — Converted color values

Array the same shape as the input

Converted color values, returned as an array the same shape as the input. The output type is the same as the input type unless you specify the 'OutputType' parameter.

See Also

rgb2xyz

Introduced in R2014b

xyz2lab

Convert CIE 1931 XYZ to CIE 1976 L*a*b*

Syntax

```
lab = xyz2lab(xyz)
lab = xyz2lab(xyz,Name,Value)
```

Description

`lab = xyz2lab(xyz)` converts CIE 1931 XYZ values to CIE 1976 L*a*b* values.

`lab = xyz2lab(xyz,Name,Value)` specifies additional options with one or more Name,Value pair arguments.

Examples

Convert XYZ color to L*a*b*

```
xyz2lab([0.25 0.40 0.10])
ans =
```

```
    69.4695   -48.0361    57.1279
```

Convert XYZ color to L*a*b* using D50 as reference white

```
xyz2lab([0.25 0.40 0.10], 'WhitePoint', 'd50')
ans =
```

```
    69.4695   -49.5717    48.3864
```

Input Arguments

xyz — Color values to convert

P-by-3 matrix | M-by-N-by-3 image array | M-by-N-by-3-by-F image stack

Color values to convert, specified as a P-by-3 matrix of color values (one color per row), an M-by-N-by-3 image array, or an M-by-N-by-3-by-F image stack.

Example: `xyz2lab([0.25 0.40 0.10])`

Data Types: `single` | `double`

Name-Value Pair Arguments

Specify optional comma-separated pairs of `Name`, `Value` arguments. `Name` is the argument name and `Value` is the corresponding value. `Name` must appear inside single quotes (' '). You can specify several name and value pair arguments in any order as `Name1`, `Value1`, ..., `NameN`, `ValueN`.

Example: `xyz2lab([0.25 0.40 0.10], 'WhitePoint', 'd50')`

'WhitePoint' — Reference white point

'd65' (default) | 'a' | 'c' | 'd50' | 'icc' | 'e' | 1-by-3 vector

Reference white point, specified as a 1-by-3 vector or one of the CIE standard illuminants, listed in the following table.

String Value	White Point
'a'	CIE standard illuminant A, [1.0985, 1.0000, 0.3558]. Simulates typical, domestic, tungsten-filament lighting.
'c'	CIE standard illuminant C, [0.9807, 1.0000, 1.1822]. Simulates daylight with correlated color temperature of 4874 K. Deprecated by CIE.
'd50'	CIE standard illuminant D50, [0.9642, 1.0000, 0.8251]. Simulates daylight with correlated color temperature of 5003 K.
'd65'	CIE standard illuminant D65, [0.9504, 1.0000, 1.0888]. Simulates daylight with correlated color temperature of 6504 K.
'icc'	Profile Connection Space (PCS) illuminant used in ICC profiles. Approximation of [0.962, 1.000, 0.8249] using fixed-point, signed, 32-bit numbers with 16 fractional bits. Actual value: [31595, 32768, 27030]/32768.
'e'	Equal-energy radiator. Useful as a theoretical reference. [1.000, 1.000, 1.000].

Example: `xyz2lab([0.25 0.40 0.10], 'WhitePoint', 'd50')`

Data Types: `single` | `double` | `char`

Output Arguments

1ab — Converted color values

array the same shape and type as the input

Converted color values, returned as an array the same shape and type as the input.

See Also

`rgb2lab` | `rgb2xyz` | `rgb2xyz` | `xyz2rgb`

Introduced in R2014b

xyz2uint16

Convert *XYZ* color values to `uint16`

Syntax

```
xyz16 = xyz2uint16(xyz)
```

Description

`xyz16 = xyz2uint16(xyz)` converts an *M*-by-3 or *M*-by-*N*-by-3 array of *XYZ* color values to `uint16`. `xyz16` has the same size as `xyz`.

The Image Processing Toolbox software follows the convention that double-precision *XYZ* arrays contain 1931 CIE *XYZ* values. *XYZ* arrays that are `uint16` follow the convention in the ICC profile specification (ICC.1:2001-4, www.color.org) for representing *XYZ* values as unsigned 16-bit integers. There is no standard representation of *XYZ* values as unsigned 8-bit integers. The ICC encoding convention is illustrated by this table.

Value (X, Y, or Z)	uint16 Value
0.0	0
1.0	32768
1.0 + (32767/32768)	65535

Class Support

`xyz` is a `uint16` or `double` array that must be real and nonsparse. `xyz16` is `uint8`.

Examples

Convert *XYZ* values to `uint16` encoding.

```
xyz2uint16([0.1 0.5 1.0])
```

ans =

3277 16384 32768

See Also

[applycform](#) | [lab2double](#) | [lab2uint16](#) | [lab2uint8](#) | [makecform](#) | [whitepoint](#)
| [xyz2double](#)

Introduced before R2006a

ybcr2rgb

Convert YCbCr color values to RGB color space

Syntax

```
rgbmap = ybcr2rgb(ybcrmap)
gpuarrayRGBmap = ybcr2rgb(gpuarrayYbcrmap)
RGB = ybcr2rgb(Ybcr)
gpuarrayRGB = ybcr2rgb(gpuarrayYbcr)
```

Description

`rgbmap = ybcr2rgb(ybcrmap)` converts the YCbCr values in the colormap `ybcrmap` to the RGB color space. If `ybcrmap` is M-by-3 and contains the YCbCr luminance (*Y*) and chrominance (*Cb* and *Cr*) color values as columns, `rgbmap` is returned as an M-by-3 matrix that contains the red, green, and blue values equivalent to those colors.

`gpuarrayRGBmap = ybcr2rgb(gpuarrayYbcrmap)` performs the conversion on a GPU. The input image, `gpuarrayYbcrmap`, is a `gpuArray` containing a YCbCr colormap. The output is a `gpuArray` containing an RGB colormap. This syntax requires the Parallel Computing Toolbox.

`RGB = ybcr2rgb(Ybcr)` converts the YCbCr image `Ybcr` to the equivalent truecolor image `RGB`.

`gpuarrayRGB = ybcr2rgb(gpuarrayYbcr)` performs the conversion on a GPU. The input image, `gpuarrayYbcr`, is a `gpuArray` containing a YCbCr image. The output is a `gpuArray` containing an RGB image. This syntax requires the Parallel Computing Toolbox.

“Code Generation” on page 1-1563 support: Yes.

“MATLAB Function Block” on page 1-1563 support: Yes.

Class Support

If the input is a YCbCr image, it can be of class `uint8`, `uint16`, or `double`. The output image is of the same class as the input image. If the input is a colormap, the input and output colormaps are both of class `double`.

If the input is a YCbCr `gpuArray` image, it can contain `uint8`, `uint16`, `single` or `double`. The output `gpuArray` image contains the same class as the input image. If the input is a `gpuArray` colormap, the input and output `gpuArray` colormaps can contain `single` or `double`.

Examples

Convert image from RGB space to YCbCr space and back.

```
rgb = imread('board.tif');  
ycbcr = rgb2ycbcr(rgb);  
rgb2 = ycbcr2rgb(ycbcr);
```

Convert image from RGB space to YCbCr space and back on a GPU.

```
rgb = gpuArray(imread('board.tif'));  
ycbcr = rgb2ycbcr(rgb);  
rgb2 = ycbcr2rgb(ycbcr);
```

More About

Code Generation

This function supports the generation of C code using MATLAB Coder. Note that if you choose the generic **MATLAB Host Computer** target platform, the function generates code that uses a precompiled, platform-specific shared library. Use of a shared library preserves performance optimizations but limits the target platforms for which code can be generated. For more information, see “Understanding Code Generation with Image Processing Toolbox”.

MATLAB Function Block

You can use this function in the MATLAB Function Block in Simulink.

References

[1] Poynton, C. A. *A Technical Introduction to Digital Video*, John Wiley & Sons, Inc., 1996, p. 175.

[2] Rec. ITU-R BT.601-5, *Studio Encoding Parameters of Digital Television for Standard 4:3 and Wide-screen 16:9 Aspect Ratios*, (1982-1986-1990-1992-1994-1995), Section 3.5.

See Also

`ntsc2rgb` | `rgb2ntsc` | `rgb2ycbcr` | `gpuArray`

Introduced before R2006a