


Optimization Toolbox™ Release Notes



MATLAB®

How to Contact MathWorks



Latest news: www.mathworks.com
Sales and services: www.mathworks.com/sales_and_services
User community: www.mathworks.com/matlabcentral
Technical support: www.mathworks.com/support/contact_us



Phone: 508-647-7000



The MathWorks, Inc.
3 Apple Hill Drive
Natick, MA 01760-2098

Optimization Toolbox™ Release Notes

© COPYRIGHT 2005–2018 by The MathWorks, Inc.

The software described in this document is furnished under a license agreement. The software may be used or copied only under the terms of the license agreement. No part of this manual may be photocopied or reproduced in any form without prior written consent from The MathWorks, Inc.

FEDERAL ACQUISITION: This provision applies to all acquisitions of the Program and Documentation by, for, or through the federal government of the United States. By accepting delivery of the Program or Documentation, the government hereby agrees that this software or documentation qualifies as commercial computer software or commercial computer software documentation as such terms are used or defined in FAR 12.212, DFARS Part 227.72, and DFARS 252.227-7014. Accordingly, the terms and conditions of this Agreement and only those rights specified in this Agreement, shall pertain to and govern the use, modification, reproduction, release, performance, display, and disclosure of the Program and Documentation by the federal government (or other entity acquiring for or through the federal government) and shall supersede any conflicting contractual terms or conditions. If this License fails to meet the government's needs or is inconsistent in any respect with federal procurement law, the government agrees to return the Program and Documentation, unused, to The MathWorks, Inc.

Trademarks

MATLAB and Simulink are registered trademarks of The MathWorks, Inc. See www.mathworks.com/trademarks for a list of additional trademarks. Other product or brand names may be trademarks or registered trademarks of their respective holders.

Patents

MathWorks products are protected by one or more U.S. patents. Please see www.mathworks.com/patents for more information.

R2018b

Optimization Modeling: Use variable expressions to represent quadratic objectives	1-2
Optimization Solving: Solve problems with quadratic objectives and linear constraints using an automatically selected solver	1-2
intlinprog Performance: Solve problems faster with enhanced preprocessing and branching	1-2
quadprog and lsqin Options: Choose dense or sparse linear solver explicitly	1-2
Functionality Being Removed or Changed	1-3
solve(prob,solver), solve(prob,options), and solve(prob,solver,options) syntaxes have been removed . . .	1-3
Complex Numbers Disallowed in Nonlinear Least-Squares Problems with Bounds	1-3

R2018a

intlinprog Performance: Solve problems faster with new branching methods	2-2
solve Initial Point: Warm-start branch-and-bound when solving mixed-integer linear programs in the problem-based workflow	2-2

Automatic Code Suggestions and Completions: Specify options and arguments by making selections from a list	2-2
findindex: Find numeric equivalents of named index variables	2-4
Problem-Based Approach: Streamlined problems	2-4
intlinprog Options: Default value changes	2-5
Functionality Being Removed or Changed	2-5

R2017b

Optimization Modeling: Use variable expressions to represent linear or integer constraints and objectives	3-2
Optimization Modeling: Create a collection of constraints with a single statement	3-2
Optimization Solving: Solve linear and mixed-integer linear problems with an automatically selected solver	3-2
Optimization Modeling Examples: Learn how to specify a model with examples from finance, supply chain, energy production, and more	3-3
intlinprog Initial Point: Warm start branch-and-bound	3-3
Functionality Being Removed or Changed	3-3

R2017a

Interior-Point Algorithms: Solve dense quadratic and linear least-squares problems faster	4-2
--	-----

intlinprog Heuristics: Find more integer-feasible points using new, simplified options	4-2
fmincon 'sqp' Algorithm: Use less memory	4-3
fminunc, linprog, and lsqlin: Default algorithm changes	4-3
String Arguments: Solvers accept strings	4-4
Dual-Simplex Algorithm Updates: Increased robustness in intlinprog and linprog	4-4
intlinprog 'RootLPMaxIterations' Option: New default value	4-4
Functionality Being Removed or Changed	4-5

R2016b

fmincon 'sqp' Algorithm: Solve problems more quickly	5-2
intlinprog Heuristics: Select from a larger set of heuristics for finding integer-feasible points	5-2
intlinprog: Revised branch-and-bound algorithm	5-3
quadprog: 'active-set' algorithm removed	5-3
linprog: 'active-set' and 'simplex' algorithms removed, syntax update, and default algorithm will change	5-3
fsolve: 'trust-region-reflective' algorithm renamed 'trust-region'	5-4
lsqlin: 'active-set' algorithm will be removed, default algorithm will change	5-4
fminunc: InitialHessMatrix and InitialHessType options removed	5-5

Featured example update	5-5
--------------------------------------	------------

R2016a

Renamed Options: Use more expressive and consistent names for options	6-2
Parallel Computation: Accelerate fminunc, fsolve, lsqcurvefit, and lsqnonlin functions (using Parallel Computing Toolbox)	6-2
Option Changes: Distinguish between function tolerance and optimality tolerance, specify Hessians differently, more ...	6-3
resetoptions: Restore default option values	6-4
Iterative display changes in linprog and quadprog	6-4
fsolve 'trust-region-dogleg' algorithm: Improved robustness	6-4

R2015b

Additional interior-point linear programming algorithm with improved performance and robustness	7-2
Mathematical Programming System (MPS) file reader for importing linear programming and mixed-integer linear programming problems	7-2
Updated output structure in several solvers	7-2
Optimization app will be removed in a future release	7-3
Linear programming example	7-3

Improved performance and robustness of intlinprog primal-simplex algorithm	8-2
linprog dual-simplex algorithm returns more information ...	8-2
quadprog active-set algorithm will be removed	8-2
fmincon allows problems without constraints	8-2
Least-squares solvers allow equal upper and lower bounds ..	8-3
quadprog allows zero or empty quadratic term	8-3
Changes to algorithm field of output structure	8-3
Mixed-integer quadratic programming example	8-3

Dual-simplex algorithm in linprog linear programming solver	9-2
Interior-point algorithm in lsqin linear least-squares solver	9-2
Plot functions and output functions for monitoring progress of intlinprog solver	9-2
Levenberg-Marquardt InitDamping option	9-2
Changing default algorithm for fminunc	9-3
Mixed-integer linear programming example	9-3
Two linprog algorithms will be removed in the future	9-3

Two fminunc options will be removed in the future	9-3
bintprog removed	9-4
ktrlink removed	9-4

R2014a

Mixed-integer linear programming solver	10-2
New default algorithms in fmincon and quadprog	10-2
Nonlinear least-squares tweaks	10-3
Parallel option change	10-3
ktrlink default math library change	10-3
bintprog will be removed in the future	10-3
ktrlink will be removed in the future	10-4

R2013b

Solvers that check initial point more carefully	11-2
--	-------------

R2013a

optimoptions function for setting options with compact and comprehensive display	12-2
---	-------------

Algorithm option replaces LargeScale option	12-2
ktrlink supports KNITRO 8.1	12-3

R2012b

Changing default algorithms for fmincon and quadprog	13-2
ktrlink supports KNITRO 8	13-2

R2012a

Enhanced Robustness in fminunc	14-2
FinDiffRelStep Option in Optimization Tool	14-2
Levenberg-Marquardt Algorithm Tweak	14-2
fmincon sqp Algorithm Tweak	14-2

R2011b

Derivative Estimate Changes	15-2
Gauss-Newton Algorithm Removed	15-2
DerivativeCheck Changes	15-3
fmincon ScaleProblem Default Changed	15-3

fsolve trust-region-dogleg Algorithm Change	15-4
Conversion of Error and Warning Message Identifiers	15-4

R2011a

New Quadratic Programming Algorithm	16-2
Enhanced Robustness in Nonlinear Solvers	16-3
New Defaults in DiffMinChange and DiffMaxChange Options	16-3
Output Structure Tweak	16-4
ktrlink Compatible with KNITRO 7	16-4
New quadprog Demo	16-4

R2010b

Enhanced fmincon Finite Difference Algorithms Add Robustness	17-2
ktrlink Available for Macintosh 64-Bit Systems	17-2
Output Structure Tweaks	17-2
New Video Demo on Modeling	17-2

R2010a

New fmincon Algorithm	18-2
lsqnonneg No Longer Uses x0	18-2

R2009b

Enhanced Exit Messages in Selected Solvers	19-2
fmincon Interior-Point Algorithm Robust to Certain Errors	19-2
Changes in quadprog	19-2
Changes in linprog	19-2
Multiobjective optimValues Changes	19-3

R2009a

Parallel Gradient Estimation Available in fmincon Interior-Point Algorithm	20-2
Enhanced Exit Messages in Selected Solvers	20-2
Links to More Information Window	20-2
Link for More Detail in Command Window	20-2
New Display Option Values Control Default Detail	20-2
Messages in Output Structure	20-3
Change in linprog Simplex Algorithm	20-3
Change in fminunc Exit Flag	20-3

New demos	20-4
------------------------	-------------

R2008b

fsolve, lsqcurvefit, lsqnonlin Algorithm and Options Changes	21-2
Optimization Tool Enables Parallel Functionality	21-2
Central Finite Differences Available in Selected Solvers	21-2
lsqnonneg Refactored	21-3
Finite Difference Algorithm Tweaked	21-4
DerivativeCheck Tolerance Changed	21-4

R2008a

Parallel Computing Toolbox Support in fmincon, fminimax, and fgoalattain	22-2
Combined and Extended optimtool	22-2
New fmincon Solver, New Option Algorithm for fmincon, Option LargeScale Changed	22-2
External Interface to KNITRO Libraries	22-3
Default PrecondBandWidth = Inf in lsqcurvefit, lsqnonlin, and fsolve	22-3
New Option TolConSQP with Incompatible Default Value ...	22-3
Field constrviolation in Output Structure	22-4

R2007b

Bug Fixes

R2007a

Changes to Outputs of Multiobjective Solvers 24-2

R2006b

New Optimization Tool 25-2

Plot Functions Option Added 25-2

**Output Function Option Enhanced to Accept Multiple
Functions 25-2**

Changes to the Output Function 25-2

R2006a

Bug Fixes

Notify Parameter Added to Display Option for Five Functions	27-2
--	-------------

R2018b

Version: 8.2

New Features

Bug Fixes

Compatibility Considerations

Optimization Modeling: Use variable expressions to represent quadratic objectives

The problem-based approach now applies to problems with quadratic objective functions and linear constraints. Previously, a problem-based objective function could be only linear. See “Problem-Based Optimization Setup”.

For examples using the problem-based approach with quadratic objectives, see “Quadratic Programming” and “Linear Least Squares”.

Optimization Solving: Solve problems with quadratic objectives and linear constraints using an automatically selected solver

`solve` now applies to problems with quadratic objectives and linear constraints. For these problems, `solve` internally calls `quadprog`, or, for linear least-squares problems, `lsqlin` or, if specified in the `solver` option, `lsqnonneg`.

For examples solving quadratic problems using the problem-based approach, see “Quadratic Programming” and “Linear Least Squares”.

intlinprog Performance: Solve problems faster with enhanced preprocessing and branching

The `intlinprog` solver has improved performance due to algorithm changes. These changes include:

- Stronger clique cuts during cut generation (the `CutGeneration` option).
- Inclusion of objective GCD reasoning during branch-and-bound.
- More frequent use of the simple rounding heuristic during branch-and-bound.
- More efficient implementation of `BranchRule` options `'strongpscost'` and `'reliability'`.

quadprog and lsqlin Options: Choose dense or sparse linear solver explicitly

The `'LinearSolver'` option specifies the underlying linear algebra type for the `quadprog` `'interior-point-convex'` algorithm and the `lsqlin` `'interior-point'`

algorithm: 'sparse' or 'dense'. The previous way to choose the linear algebra type was implicitly, by the type of the quadratic matrix (H for `quadprog`, C for `lsqlin`). The default behavior retains this implicit choice as the 'auto' setting. For details, see the options entries on the function reference pages.

The returned output structure for these solvers now has a 'linearsolver' field, with value 'sparse' or 'dense' depending on the linear algebra type used.

Functionality Being Removed or Changed

`solve(prob,solver)`, `solve(prob,options)`, and `solve(prob,solver,options)` syntaxes have been removed

Errors

To choose options or the underlying solver for `solve`, use name-value pairs. For example,

```
sol = solve(prob, 'options', opts, 'solver', 'quadprog');
```

The previous syntaxes were not as flexible, standard, or extensible as name-value pairs.

Complex Numbers Disallowed in Nonlinear Least-Squares Problems with Bounds

Behavior change

For problems containing finite bounds, both `lsqcurvefit` and `lsqnonlin` now disallow steps leading to complex values.

Previously, the solvers would accept complex steps, and could return mysterious errors or spurious solutions. To use both bounds and complex values, split the problem into real and imaginary parts as described in "Fit a Model to Complex-Valued Data".

R2018a

Version: 8.1

New Features

Bug Fixes

Compatibility Considerations

intlinprog Performance: Solve problems faster with new branching methods

`intlinprog` has new branching methods that can lead to faster solutions and faster acquisition of integer-feasible points.

The new branching methods are the `'strongpscost'` and `'reliability'` settings of the `BranchRule` option. See `Branch and Bound`.

Because `solve` internally calls `intlinprog` for integer-constrained problems, it can also use these new branching methods.

solve Initial Point: Warm-start branch-and-bound when solving mixed-integer linear programs in the problem-based workflow

The function `solve` now accepts an optional initial point.


Compatibility Considerations

The syntax of `solve` has changed. Pass the solver and options arguments in name-value pairs. Pass the optional initial point `x0` as the second argument. See the `solve` function reference page.

Automatic Code Suggestions and Completions: Specify options and arguments by making selections from a list

The `optimproblem`, `optimconstr`, `optimexpr`, `resetoptions`, and `optimoptions` functions present you with a list of choices for nonnumeric entries. To get the list at the command line or MATLAB® Editor, enter a single or double quote and some letters, and then press **Tab**.


```
options = optimoptions('fTab
```



```
options = optimoptions('fminunc','DTab
```

```
options = optimoptions('fminunc','Display'
```


The Live Editor presents these choices without requiring you to press **Tab**.



You can also press **Tab** to display a list of options when using dot notation.

```
options = optimoptions('fmincon');  
options.Display = 'Tab
```

```
>> options = optimoptions('fmincon');  
fx >> options.Display = '
```



- final
- final-detailed
- iter
- iter-detailed
- notify
- notify-detailed
- off

findindex: Find numeric equivalents of named index variables

To ease the creation of initial points or the interpretation of solutions when a problem has named index variables, use `findindex`. For details, see [Named Index for Optimization Variables and `findindex`](#).

Problem-Based Approach: Streamlined problems

The infrastructure for generating optimization expressions and constraints has changed. Generally, the resulting optimization objects are now more compact and run slightly faster.

Compatibility Considerations

If you load an expression, constraint, or problem object saved in R2017b format, the loaded object does not inherit the new capabilities. In this case, `solve` runs the problem the same way as in R2017b, which can be slightly slower than if you create the problem in R2018a. To obtain the latest version, recreate the object using the commands that previously created the object.

Generally, you cannot load an optimization expression or problem created in R2018a into MATLAB R2017b.

intlinprog Options: Default value changes

The `intlinprog` `ObjectiveImprovementThreshold` option now has a default value of 0. Previously, the default was $1e-4$.

The `LPMaxIterations` option now has a default value of `'max(30000,10*(numberOfEqualities+numberOfInequalities+numberOfVariables))'`. Previously, the default was 30000.

Compatibility Considerations

Although the change to `ObjectiveImprovementThreshold` can provide a more accurate solution and more integer feasible points, when using the new default value, some problems run slower or do not converge. To solve a problem as before, set the `ObjectiveImprovementThreshold` to $1e-4$ using `optimoptions`.

If your code assumes that the default value of `LPMaxIterations` is numeric, change the code to accept a character vector.

Functionality Being Removed or Changed

The following functionality has changed.

Functionality	Result	Use Instead	Compatibility Considerations
<code>solve(prob,solver)</code> , <code>solve(prob,options)</code> , or <code>solve(prob,solver,options)</code>	Warns	<code>solve(prob,'solver',solver)</code> , <code>solve(prob,'options',options)</code> , or <code>solve(prob,'solver',solver,'options',options)</code>	Replace all instances of the solver and options arguments with corresponding name-value pair arguments.
<code>str2sub</code>	Errors	<code>findindex</code>	Replace all instances of <code>str2sub</code> with <code>findindex</code> .

R2017b

Version: 8.0

New Features

Bug Fixes

Optimization Modeling: Use variable expressions to represent linear or integer constraints and objectives

Solve linear programming problems and mixed-integer linear programming problems using a problem-based, variable approach.

- Create an optimization problem using `optimproblem`.
- Create optimization variables using `optimvar`.
- Specify the objective by creating an optimization expression as a linear combination of optimization variables.
- Create constraints as linear expressions in optimization variables with a comparison operator: `<=`, `==`, or `>=`.
- Solve the problem using `solve`.

For the workflow steps, see Problem-Based Workflow. For details and examples, see Problem-Based Optimization.

Optimization Modeling: Create a collection of constraints with a single statement

For structured constraints, you can create multiple constraints in an optimization problem by using a single vectorized statement. For example, to represent the constraints that each row of a matrix `x` sums to one:

```
rowcons = sum(x,2) == 1;
```

For details, see Expressions for Constraints.

Optimization Solving: Solve linear and mixed-integer linear problems with an automatically selected solver

The `solve` function automatically chooses the appropriate underlying solver, either `linprog` or `intlinprog`, to solve linear problems with or without integer constraints. For details, see the `solve` function reference page.

Optimization Modeling Examples: Learn how to specify a model with examples from finance, supply chain, energy production, and more

The linear programming and mixed-integer linear programming featured examples show the problem-based approach Optimization Toolbox Examples. For examples using the previous solver-based approach, see Solver-Based Optimization.

intlinprog Initial Point: Warm start branch-and-bound

You can specify an integer-feasible initial point for `intlinprog`. Typically, when you specify an integer-feasible point, `intlinprog` runs somewhat faster. For details, see the function reference page.

Compatibility Considerations

For compatibility with previously-accepted syntax, the solver runs as before when you leave out the `x0` argument and include an `options` argument. In other words, the following syntaxes are equivalent when you have no initial point, meaning `x0 = []`:

```
x = intlinprog(f,intcon,A,b,Aeq,beq,lb,ub,x0,options)
% and
x = intlinprog(f,intcon,A,b,Aeq,beq,lb,ub,options)
```

Functionality Being Removed or Changed

The following functions and algorithms have been removed.

Functionality	Result	Use Instead	Compatibility Considerations
color removed	Errors	There is no replacement	To avoid errors,ensure that your code does not call <code>color</code> .

Functionality	Result	Use Instead	Compatibility Considerations
fzmult removed	Errors	There is no replacement	To avoid errors, ensure that your code does not call fzmult.
gangstr removed	Errors	There is no replacement	To avoid errors, ensure that your code does not call gangstr.
linprog 'simplex' and 'active-set' algorithms removed	Errors	'dual-simplex', 'interior-point', or 'interior-point-legacy'	Set the Algorithm option using optimoptions
lsqlin 'active-set' algorithm removed	Errors	'trust-region-reflective' or 'interior-point'	Set the Algorithm option using optimoptions

R2017a

Version: 7.6

New Features

Bug Fixes

Compatibility Considerations

Interior-Point Algorithms: Solve dense quadratic and linear least-squares problems faster

The quadprog 'interior-point-convex' algorithm now has better performance on

problems with a dense quadratic matrix H in the minimization $\min_x \frac{1}{2} x^T H x + f^T x$. For details, see Quadratic Programming Algorithms.

The lsqlin 'interior-point' algorithm internally calls the quadprog 'interior-point-convex' algorithm, as described in Interior-Point Linear Least Squares.

Therefore, the lsqlin 'interior-point' algorithm now has better performance on

problems with a dense matrix C in the minimization $\min_x \frac{1}{2} \|C \cdot x - d\|_2^2$.

lsqlin now uses the StepTolerance option. For both solvers, there are new exit flag values of 2 (step size less than StepTolerance, constraints satisfied) and -2 (step size less than StepTolerance, but constraints are not satisfied). The default value of StepTolerance is 1e-12, which is less than the previous default value of 1e-8 for quadprog.

Compatibility Considerations

If you pass a dense quadratic matrix H to quadprog or a dense matrix C to lsqlin, the solution can be slightly different than before. To get the same solution, pass the matrix in sparse form.

To use the same default quadprog StepTolerance option as before, set StepTolerance to 1e-8 using optimoptions.

intlinprog Heuristics: Find more integer-feasible points using new, simplified options

There are three new intlinprog Heuristics options. These options enable intlinprog to solve some previously-intractable problems, and to solve some problems faster. The new options are:

- 'basic' (default)

- 'intermediate'
- 'advanced'

Select Heuristics using `optimoptions`.

`intlinprog` now uses more diving heuristics For details, see Heuristics for Finding Feasible Solutions.

Compatibility Considerations

The default value of the `Heuristics` option is now 'basic'. To have `intlinprog` use the previous default heuristic, set the `Heuristics` option to 'rss'.

Heuristics that include diving cause `intlinprog` iterations to differ from previous releases. Generally, the new heuristics allow `intlinprog` to solve more problems than before. However, `intlinprog` performance can vary from previous releases.

fmincon 'sqp' Algorithm: Use less memory

The `fmincon` 'sqp' algorithm now uses less memory. The algorithm runs faster on many problems.

fminunc, linprog, and lsqlin: Default algorithm changes

The `fminunc`, `linprog`, and `lsqlin` solvers have new default algorithms:

Solver	New Default Algorithm	Previous Default Algorithm
<code>fminunc</code>	'quasi-newton'	'trust-region'
<code>linprog</code>	'dual-simplex'	'interior-point-legacy'
<code>lsqlin</code>	'interior-point'	'trust-region-reflective'

Compatibility Considerations

If you do not set an algorithm, these solvers run different algorithms than before. Solutions can have slight numerical differences from the previous versions. To use a

previous default algorithm, use `optimoptions` to set the 'Algorithm' option appropriately.

String Arguments: Solvers accept strings

You can use a string wherever you would previously have used a character vector in setting options or passing arguments to solvers. For example,

```
solver = string('fminunc');
name1 = string('SpecifyObjectiveGradient');
value1 = true;
name2 = string('Algorithm');
value2 = string('trust-region');
options = optimoptions(solver,name1,value1,name2,value2);
```

Dual-Simplex Algorithm Updates: Increased robustness in `intlinprog` and `linprog`

The 'dual-simplex' algorithm in `intlinprog` and `linprog` was updated. The algorithm now solves more problems than before.

Compatibility Considerations

The `intlinprog` branch-and-bound iterations now take different steps than before. This change can lead to longer solution times.

`intlinprog` 'RootLPMaxIterations' Option: New default value

The `intlinprog` 'RootLPMaxIterations' option has a new default value of $\max(3e4, 10 * (\text{numberOfEqualities} + \text{numberOfInequalities} + \text{numberOfVariables}))$. In this expression, `numberOfEqualities` means the number of rows of `Aeq`, `numberOfInequalities` means the number of rows of `A`, and `numberOfVariables` means the number of elements of `f`. This new default value enables `intlinprog` to solve more problems than before, when the default value was `3e4`.

Compatibility Considerations

To run `intlinprog` as before, set the `'RootLPMaxIterations'` option to `3e4` using `optimoptions`.

Functionality Being Removed or Changed

The following functions will be removed in a future release.

Functionality	Result	Use Instead	Compatibility Considerations
<code>color</code>	Still runs	There is no replacement	To avoid future errors, ensure that your code does not call <code>color</code> .
<code>fzmult</code>	Still runs	There is no replacement	To avoid future errors, ensure that your code does not call <code>fzmult</code> .
<code>gangstr</code>	Still runs	There is no replacement	To avoid future errors, ensure that your code does not call <code>gangstr</code> .

R2016b

Version: 7.5

New Features

Bug Fixes

Compatibility Considerations

fmincon 'sqp' Algorithm: Solve problems more quickly

The `fmincon` 'sqp' algorithm was rewritten. The new version is generally faster and more memory-efficient than before. Specify the new algorithm by setting the `Algorithm` option to 'sqp', and specify the previous algorithm as 'sqp-legacy'.

Compatibility Considerations

The 'sqp' and 'sqp-legacy' algorithms are similar, but have slight numerical differences that can lead to different results.

If you load a problem that was saved with a MATLAB version prior to R2016b that had the `fmincon` `Algorithm` option set to 'sqp', then MATLAB converts the problem options to the 'sqp-legacy' algorithm.

The Optimization app cannot run or save the 'sqp-legacy' algorithm. It converts any such problem into one that uses the new 'sqp' algorithm.

You cannot choose the 'sqp-legacy' algorithm using `optimset`. Instead, use `optimoptions`.

intlinprog Heuristics: Select from a larger set of heuristics for finding integer-feasible points

There are more options for `intlinprog` Heuristics. The new options generally have `-diving` appended to the previous names, and are:

- 'diving'
- 'round-diving'
- 'rss-diving'
- 'rins-diving'

The new `-diving` options can enable `intlinprog` to solve previously intractable problems. Select Heuristics using `optimoptions`. For details, see Heuristics for Finding Feasible Solutions.

intlinprog: Revised branch-and-bound algorithm

`intlinprog` has a new branch-and-bound implementation. The intent is to have similar or better performance than the previous version, and to be more memory-efficient.

Compatibility Considerations

The new algorithm can take different iterative steps, and can find different integer-feasible points than before.

quadprog: 'active-set' algorithm removed

The `quadprog` 'active-set' algorithm has been removed.

Compatibility Considerations

If you load a problem that was saved with a previous toolbox version, and that has the `Algorithm` option 'active-set', then `optimoptions` changes the option to the default 'interior-point-convex' algorithm.

linprog: 'active-set' and 'simplex' algorithms removed, syntax update, and default algorithm will change

The `linprog` 'active-set' and 'simplex' algorithms have been removed. Additionally, you can no longer choose the `linprog` algorithm using the `LargeScale` option.

Previously, `linprog` accepted an initial point argument `x0` for the 'active-set' algorithm. Now that this algorithm is removed, you no longer need to pass `x0` to `linprog`. This means that the following syntax is valid:

```
x = linprog(f,A,b,Aeq,beq,lb,ub,options)
```

If you do not set an algorithm, `linprog` warns that, in a future release, the default will change from 'interior-point-legacy' to 'dual-simplex'.

Compatibility Considerations

If you load a problem that was saved with a previous toolbox version, and that has the Algorithm option 'active-set' or 'simplex', then `optimoptions` changes the option to the default 'interior-point-legacy' algorithm.

Choose the `linprog` algorithm by using `optimoptions` to set the Algorithm option.

For compatibility, `linprog` accepts the former syntax that includes `x0`, but `linprog` doesn't use `x0`:

```
x = linprog(f,A,b,Aeq,beq,lb,ub,x0,options)
```

fsolve: 'trust-region-reflective' algorithm renamed 'trust-region'

The former `fsolve` 'trust-region-reflective' algorithm is now named 'trust-region'.

Compatibility Considerations

When you set the Algorithm option using `optimoptions`, you can use either the former name 'trust-region-reflective' or the current name 'trust-region'. However, `optimoptions` displays the resulting option name as 'trust-region' in either case.

To set the algorithm using `optimset`, use the former name 'trust-region-reflective'.

If you export options containing the 'trust-region' algorithm from the Optimization app, the exported options cannot be used in toolbox versions prior to R2016a.

lsqlin: 'active-set' algorithm will be removed, default algorithm will change

The `lsqlin` 'active-set' algorithm now warns that it will be removed in a future release.

When you do not set an Algorithm option, `lsqlin` warns that the default algorithm will change to 'interior-point' in a future release.

Compatibility Considerations

To avoid these warnings, use `optimoptions` to set the `Algorithm` option to `'trust-region-reflective'` or `'interior-point'`.

fminunc: InitialHessianMatrix and InitialHessianType options removed

The `fminunc` `InitialHessianMatrix` and `InitialHessianType` options have been removed.

Compatibility Considerations

To avoid errors, remove any reference to these options from your `optimset` or `optimoptions` calls.

Featured example update

The `bandem` function, which used to bring up an app showing how various algorithms perform, has been replaced by an updated example, `Banana Function Minimization`.

R2016a

Version: 7.4

New Features

Bug Fixes

Compatibility Considerations

Renamed Options: Use more expressive and consistent names for options

Many options have new names. The old names continue to work, but do not appear in documented examples. The renaming gives a more consistent set of option names that match those in Global Optimization Toolbox.

All legacy option names continue to work in both `optimoptions` and `optimset`.

For option name change details, see Current and Legacy Option Name Tables.

Compatibility Considerations

`optimset` uses only the legacy option names, while `optimoptions` uses either legacy names or current names. However, `optimoptions` displays only current names, so if you set a legacy name, it displays the equivalent current name. See Current and Legacy Option Name Tables.

`optimoptions` no longer displays some options. See View Options.

Some option values differ when using current names. For example, any previous setting that was 'on' or 'off' is now `true` or `false`.

Parallel Computation: Accelerate `fminunc`, `fsolve`, `lsqcurvefit`, and `lsqnonlin` functions (using Parallel Computing Toolbox)

More nonlinear solvers can estimate gradients or Jacobians by parallel finite differences:

- `fminunc`
- `fsolve`
- `lsqcurvefit`
- `lsqnonlin`

To enable parallel finite differences, set the `UseParallel` option to `true`. For details, see Parallel Computing.

Option Changes: Distinguish between function tolerance and optimality tolerance, specify Hessians differently, more

- Previously, the TolFun tolerance applied to both the change in function value and to the size of the first-order optimality measure. This role is now explicitly split into two new tolerances:
 - FunctionTolerance — Applies to changes in objective function value
 - OptimalityTolerance — Applies to first-order optimality measure
- The way to set Hessians for fminunc and fmincon has changed. For details, see Including Hessians.
- Several solvers gained a SubproblemAlgorithm option for their 'trust-region' or 'trust-region-reflective' algorithm:
 - fminunc
 - fsolve
 - lsqcurvefit
 - lsqnonlin
- The former Jacobian option in fsolve, lsqcurvefit, and lsqnonlin is now the SpecifyObjectiveGradient option.

Compatibility Considerations

The Optimization app imports and exports only one option related to the former TolFun tolerance. It displays this option as **Optimality tolerance**, and uses it as the OptimalityTolerance option. You cannot import, export, or change the FunctionTolerance option in the Optimization app for Optimization Toolbox solvers. When you run problems in the Optimization app, FunctionTolerance has its default value.

However, Global Optimization Toolbox solvers do not have an OptimalityTolerance option. Those solvers can import, export, and set the FunctionTolerance option in the Optimization app.

resetoptions: Restore default option values

The `resetoptions` function resets selected `optimoptions` options to their default values. For details, see the function reference page.

Iterative display changes in `linprog` and `quadprog`

Iterative display has changed for the `linprog` 'dual-simplex' and 'interior-point' algorithms, and for the `quadprog` 'interior-point-convex' algorithm. The changes give clearer and more consistent information. For iterative display details, see `linprog` and `quadprog`.

`fsolve` 'trust-region-dogleg' algorithm: Improved robustness

The default `fsolve` 'trust-region-dogleg' algorithm is now more robust to function evaluation failures during finite difference estimation of the Jacobian.

R2015b

Version: 7.3

New Features

Bug Fixes

Compatibility Considerations

Additional interior-point linear programming algorithm with improved performance and robustness

The `linprog` solver has a new algorithm named `'interior-point'`. The previous algorithm named `'interior-point'` is now named `'interior-point-legacy'`. Usually, the new `'interior-point'` algorithm is faster and more robust than the `'interior-point-legacy'` algorithm.

Compatibility Considerations

The default `linprog` algorithm is now named `'interior-point-legacy'`. If your code explicitly chooses the `'interior-point'` algorithm, `linprog` runs the new interior-point algorithm, and so can have different behavior than before.

Mathematical Programming System (MPS) file reader for importing linear programming and mixed-integer linear programming problems

The `mpsread` function reads files in the MPS format that specify linear programming problems or mixed-integer linear programming problems. For details, see the function reference page.

Updated output structure in several solvers

The `fmincon`, `fsolve`, `lsqcurvefit`, and `lsqnonlin` `'trust-region-reflective'` algorithms now return a `stepsize` field in their output structures. Similarly, the `fminunc` `'trust-region'` algorithm now returns a `stepsize` field in its output structure.

The `fmincon` `'sqp'` algorithm and `fminunc` `'quasi-newton'` algorithm now return a `stepsize` field that contains the size of the final step, and a `lssteplength` field that contains the relative step compared to a line-search prediction.

Compatibility Considerations

The meaning of the `stepsize` field has changed for the output structure of the `fmincon` `'sqp'` algorithm and `fminunc` `'quasi-newton'` algorithm. The former

stepsize field, which measured the relative step compared to a line-search prediction, is now returned in the `lssteplength` field.

Optimization app will be removed in a future release

The Optimization app now warns that it will be removed in a future release.

Compatibility Considerations

Set and examine options using `optimoptions`, which streamlines viewing Optimization Toolbox options.

Linear programming example

There is a new featured example of linear programming, `Maximize Long-Term Investments Using Linear Programming`.

R2015a

Version: 7.2

New Features

Bug Fixes

Compatibility Considerations

Improved performance and robustness of intlinprog primal-simplex algorithm

The 'primal-simplex' algorithm of the `intlinprog` solver can solve more problems than before, and has better performance on large problems. Select the algorithm in the `RootLPAlgorithm` option.

Compatibility Considerations

`intlinprog` iterations can differ from previous versions. This holds even when you select the 'dual-simplex' algorithm, because `intlinprog` uses the 'primal-simplex' algorithm for some calculations in any case.

linprog dual-simplex algorithm returns more information

The `linprog` 'dual-simplex' algorithm now returns a Lagrange multiplier structure and an output structure containing the first-order optimality measure.

quadprog active-set algorithm will be removed

The `quadprog` 'active-set' algorithm now warns that it will be removed in a future release.

Compatibility Considerations

To avoid this warning, use `optimoptions` to set the `Algorithm` option to 'interior-point-convex' or 'trust-region-reflective'. Or simply do not set the `Algorithm` option; `quadprog` defaults to the 'interior-point-convex' algorithm.

fmincon allows problems without constraints

`fmincon` no longer throws an error if you run it on a problem without constraints. This change can make it easier for you to see the effect of constraints by running a problem both with and without constraints.

To run `fmincon` without constraints, you no longer need to set an artificial constraint, such as `lb = -Inf`, but doing so will not matter.

Compatibility Considerations

Any code that checks for this error will have different behavior than before.

Least-squares solvers allow equal upper and lower bounds

The `lsqnonlin` and `lsqcurvefit` solvers now allow you to fix variables by specifying equal upper and lower bounds. For example, lower bound `lb = [0,0]` and upper bound `ub = [Inf,0]` fix the solution `x` to have `x(2) = 0`.

quadprog allows zero or empty quadratic term

Previously, if you gave a zero or empty matrix as the `H` input, the `quadprog` solver would switch to `linprog`. Now `quadprog` solves the problem.

Changes to algorithm field of output structure

The `algorithm` field of the output structure of several solvers has changed. Now, all `output.algorithm` strings are the same as those you set in the `Algorithm` name-value pair. For example, the `output.algorithm` field of the `fmincon` 'active-set' algorithm used to be 'medium-scale: SQP, Quasi-Newton, line-search'. Now it is 'active-set'.

The affected solvers are `fgoalattain`, `fminimax`, `fmincon`, `fseminf`, `fsolve`, `linprog`, `lsqcurvefit`, and `lsqnonlin`.

Compatibility Considerations

Any code that uses the string in `output.algorithm` can have different behavior than before.

Mixed-integer quadratic programming example

There is a new featured example of mixed-integer quadratic programming, Mixed-Integer Quadratic Programming Portfolio Optimization.

R2014b

Version: 7.1

New Features

Bug Fixes

Compatibility Considerations

Dual-simplex algorithm in `linprog` linear programming solver

`linprog` has a new algorithm option named `'dual-simplex'`. The algorithm saves memory when you specify sparse constraint matrices. For details, see the function reference page.

Currently, `'dual-simplex'` returns an empty Lagrange multiplier structure `lambda` and `firstorderopt` field in the output structure.

Interior-point algorithm in `lsqlin` linear least-squares solver

`lsqlin` has a new algorithm option named `'interior-point'`. The algorithm handles all types of constraints and saves memory when you specify sparse constraint matrices. For details, see the function reference page.

Plot functions and output functions for monitoring progress of `intlinprog` solver

`intlinprog` accepts `OutputFcn` and `PlotFcns` options. For details, see `intlinprog` Output Functions and Plot Functions.

There is a built-in output function that collects all integer feasible solutions that `intlinprog` encounters. Choose this output function by using `optimoptions` to set the `OutputFcn` option to `@savemilpsolutions`.

There is a built-in plot function that shows details of the solver iterations. Choose this plot function by using `optimoptions` to set the `PlotFcns` option to `@optimplotmilp`.

Levenberg-Marquardt `InitDamping` option

The `fsolve`, `lsqcurvefit`, and `lsqnonlin` solvers can use the `'levenberg-marquardt'` algorithm. To initialize the Levenberg-Marquardt parameter differently than its default, set the new `InitDamping` option using `optimoptions`.

Compatibility Considerations

Previously, to initialize the Levenberg-Marquardt parameter you would pass a cell array in the `Algorithm` option when using `optimset`, such as

```
options = optimset('Algorithm',{'levenberg-marquardt',0.1});
```

That method still works. But when using `optimoptions`, you cannot set the parameter in the `Algorithm` option, and instead must use the `InitDamping` option, such as

```
options = optimoptions(@fsolve,'Algorithm','levenberg-marquardt','InitDamping',0.1);
```

Changing default algorithm for `fminunc`

The `fminunc` default algorithm will change to `'quasi-newton'` in a future release.

Compatibility Considerations

`fminunc` now warns when you run it in cases where the default behavior will change. For details, see the `fminunc` function reference page or `fminunc Algorithms`.

Mixed-integer linear programming example

There is a new featured example of mixed-integer linear programming, `Optimal Dispatch of Power Generators`.

Two `linprog` algorithms will be removed in the future

The `linprog` `'active-set'` and `'simplex'` algorithms warn that they will be removed in a future release.

Compatibility Considerations

To avoid this warning, choose the `'interior-point'` or `'dual-simplex'` algorithms using `optimoptions`.

Two `fminunc` options will be removed in the future

`fminunc` now warns that the `InitialHessMatrix` and `InitialHessType` options will be removed in a future release.

Compatibility Considerations

To avoid these warnings, do not set values for these options. The Optimization app no longer has these options.

bintprog removed

The `bintprog` function has been removed.

Compatibility Considerations

To update code to use `intlinprog` instead of `bintprog`, see Tips.

ktrlink removed

The `ktrlink` interface to the KNITRO® third-party solver has been removed.

Compatibility Considerations

For a KNITRO interface, contact Ziena Optimization: www.ziena.com.

R2014a

Version: 7.0

New Features

Bug Fixes

Compatibility Considerations

Mixed-integer linear programming solver

The `intlinprog` function solves mixed-integer linear programming problems. For more information, see the reference page and the documentation.

There are several new featured examples of mixed-integer linear programming:

- Factory, Warehouse, Sales Allocation Model
- Travelling Salesman Problem
- Solve Sudoku Puzzles Via Integer Programming

Currently, you cannot run `intlinprog` in the Optimization app.

New default algorithms in `fmincon` and `quadprog`

When you do not specify an algorithm, `fmincon` and `quadprog` default to different algorithms than before. Usually, the new algorithms are faster and more robust than the algorithms they replace.

Solver	Previous Default Algorithm	New Default Algorithm
<code>fmincon</code>	'trust-region-reflective'	'interior-point'
<code>quadprog</code>	'trust-region-reflective'	'interior-point-convex'

Compatibility Considerations

Solvers can produce different results than before. To reproduce previous results, set the `Algorithm` option with `optimoptions`.

```
options = optimoptions('fmincon','Algorithm','trust-region-reflective');  
% or  
options = optimoptions('quadprog','Algorithm','trust-region-reflective');
```

Be sure to pass options in your function call.

```
x = fmincon(fun,x0,A,b,Aeq,beq,lb,ub,nlcon,options)
% or
x = quadprog(H,f,A,b,Aeq,beq,lb,ub,x0,options)
```

Nonlinear least-squares tweaks

The `lsqcurvefit` and `lsqnonlin` solvers have slightly different behavior than before when the internally calculated trust-region radius gets large in the 'trust-region-reflective' algorithm, or the Levenberg-Marquardt parameter gets small in the 'levenberg-marquardt' algorithm. There are no longer any arbitrary limits on these parameters. `fsolve` has the same change to its 'trust-region-reflective' and 'levenberg-marquardt' algorithms.

Parallel option change

The `UseParallel` option now accepts the values `true` and `false`. The option also accepts the former values 'always' and 'never', and scalar values 1 and 0.

The affected solvers are `fmincon`, `fgoalattain`, and `fminimax`.

ktrlink default math library change

The `ktrlink` function uses a different default math library within KNITRO than before. This change can enable `ktrlink` to run on more hardware versions.

Compatibility Considerations

With the new default math library, `ktrlink` runs slower than before. To use the previous math library, set the KNITRO format option `blasoption` to 1. See Setting Options.

bintprog will be removed in the future

`intlinprog` solves more problems than `bintprog`, and has better performance. So `bintprog` will be removed in a future release.

To update your existing `bintprog` code to use `intlinprog`, see Tips.

ktrlink will be removed in the future

ktrlink will be removed in a future release. For an updated KNITRO interface, contact Ziena Optimization: www.ziena.com.

R2013b

Version: 6.4

New Features

Bug Fixes

Compatibility Considerations

Solvers that check initial point more carefully

All nonlinear solvers now check whether derivatives of the objective and nonlinear constraint functions are well defined at the initial point, usually called x_0 . (This is in addition to the existing checks that the functions are well defined at x_0 .) Well defined means the value of each derivative is not NaN, Inf, or complex (nonlinear least-squares solvers allow complex values). Derivatives include both gradients and Jacobians. See Including Derivatives and Writing Vector and Matrix Objective Functions.

When the objective or nonlinear constraint functions do not include a derivative, solvers approximate derivatives by finite differences. This means that the functions must be well defined for points in a small neighborhood of x_0 .

If any derivative is not well defined at x_0 , the solver stops with an error, and does not attempt to find a solution.

In all tested cases, this behavior led to a clearer exit condition.

Compatibility Considerations

It is conceivable that a problem that previously ran to completion will now exit without completion. This can occur in the rare case when a derivative did not exist for a function at the initial point, but the solver was able to step to a point where the derivatives were well defined.

R2013a

Version: 6.3

New Features

Bug Fixes

Compatibility Considerations

optimoptions function for setting options with compact and comprehensive display

The new `optimoptions` function creates and modifies options for all solvers except the base MATLAB solvers `fminbnd`, `fminsearch`, `fzero`, and `lsqnonneg`. Continue to use `optimset` for those functions.

`optimoptions` organizes options by solver, with a more focused and comprehensive display than `optimset`:

- Creates and modifies only the options that apply to a solver
- Shows your option choices and default values for a specific solver/algorithm
- Displays links for more information on solver options and other available solver algorithms

For details, see the `optimoptions` page, or Set Options.

Compatibility Considerations

If you export options or a problem from the Optimization Tool, the options are an object as created by `optimoptions`. Therefore, earlier software versions cannot import the options or problem. This consideration does not apply to the base MATLAB solvers, which continue to encapsulate options as a structure.

Algorithm option replaces LargeScale option

Use the `Algorithm` option to select the algorithm in all solvers that have multiple algorithms. In a future release, solvers will no longer use the `LargeScale` option. The `linprog Simplex` option will also change to the `Algorithm` option.

Compatibility Considerations

Update options as follows.

Solver	Previous Setting	Current Setting
<code>fminunc</code>	<code>'LargeScale' = 'on'</code>	<code>'Algorithm' = 'trust-region'</code>

Solver	Previous Setting	Current Setting
	'LargeScale' = 'off'	'Algorithm' = 'quasi-newton'
linprog	'LargeScale' = 'on'	'Algorithm' = 'interior-point'
	'LargeScale' = 'off', 'Simplex' = 'off' or unset	'Algorithm' = 'active-set'
	'LargeScale' = 'off', 'Simplex' = 'on'	'Algorithm' = 'simplex'
lsqlin	'LargeScale' = 'on'	'Algorithm' = 'trust-region-reflective'
	'LargeScale' = 'off'	'Algorithm' = 'active-set'

ktrlink supports KNITRO 8.1

The `ktrlink` function now supports KNITRO version 8.1. For details, see `ktrlink`: An Interface to KNITRO Libraries.

R2012b

Version: 6.2.1

Bug Fixes

Compatibility Considerations

Changing default algorithms for `fmincon` and `quadprog`

The `fmincon` and `quadprog` default algorithms will change in a future release.

- The default `fmincon` algorithm will become `'interior-point'`.
- The default `quadprog` algorithm will become `'interior-point-convex'`.

Compatibility Considerations

These solvers now warn when you run them in cases where the default behavior will change. For example, they warn when:

- You do not set the `Algorithm` option.
- You set incompatible `LargeScale` and `Algorithm` options.

To avoid these warnings:

- Do not set the `LargeScale` option.
- Set the `Algorithm` option appropriately.

For details, see the `fmincon` and `quadprog` function reference pages or [Choosing the Algorithm](#).

`ktrlink` supports KNITRO 8

The `ktrlink` function now supports KNITRO version 8. For details, see [ktrlink: An Interface to KNITRO Libraries](#).

R2012a

Version: 6.2

New Features

Bug Fixes

Compatibility Considerations

Enhanced Robustness in `fminunc`

The `fminunc` medium-scale algorithm now attempts to recover from failures when evaluating the objective function during iteration steps, or during gradient estimation. Failure means the objective function returns `NaN`, a complex value, or `Inf`. If there is such a failure, the algorithm attempts to take different steps.

As part of robustness, the `fminunc` medium-scale algorithm now uses the `ObjectiveLimit` tolerance.

Compatibility Considerations

When objective function values drop below `ObjectiveLimit` (default value: `-1e20`), iterations end with a `-3` exit flag. Use `optimset` to change the value of `ObjectiveLimit`. Set `ObjectiveLimit` to `-Inf` to disable this tolerance.

`FinDiffRelStep` Option in Optimization Tool

The `FinDiffRelStep` option for choosing relative finite difference step sizes is now available in the Optimization Tool, in the **Approximated derivatives** pane. This option lets you tune the gradient estimation step in most solvers.

Levenberg-Marquardt Algorithm Tweak

The `fsolve`, `lsqcurvefit`, and `lsqnonlin` solvers no longer use the magnitude of the Levenberg-Marquardt regularization parameter as a stopping criterion, so they no longer return an exit flag of `-3` when using the `levenberg-marquardt` algorithm. Instead, they use the `TolX` tolerance in all internal calculations.

Compatibility Considerations

The solvers now stop with exit flag `2` in most situations where previously they stopped with exit flag `-3`.

`fmincon sqp` Algorithm Tweak

The `fmincon sqp` algorithm calculates its Lagrange multiplier estimates somewhat differently than before.

Compatibility Considerations

The `fmincon sqp` algorithm can give slightly different results than before.

R2011b

Version: 6.1

New Features

Bug Fixes

Compatibility Considerations

Derivative Estimate Changes

- The `fsolve`, `lsqcurvefit`, and `lsqnonlin` solvers now accept the `FinDiffType` option. Set `FinDiffType` to 'central' with `optimset` to enable derivative estimation by central finite differences. Central finite differences are more accurate, but take more time than the default 'forward' finite differences.
- `fsolve`, `lsqcurvefit`, and `lsqnonlin` now use the `TypicalX` option when estimating dense Jacobians via finite differences. In previous releases, these solvers used `TypicalX` only when checking derivatives.
- For algorithms that obey bounds, finite difference steps for derivative estimation now stay within any bounds you set for the decision variables. See [Iterations Can Violate Constraints](#).
- The new `FinDiffRelStep` option allows you to set a vector of finite difference step sizes to better handle problems whose components have different scales. Use `FinDiffRelStep` at the command line for any solver that uses finite differences. For details, see `FinDiffRelStep` in [Options Structure](#).

Gauss-Newton Algorithm Removed

The `fsolve`, `lsqcurvefit`, and `lsqnonlin` functions no longer use the Gauss-Newton algorithm.

Compatibility Considerations

The previous way of selecting the Gauss-Newton algorithm was to set the `LargeScale` option to 'off', and in:

- `fsolve` — set the `NonlEqnAlgorithm` option to 'gn'.
- `lsqcurvefit` or `lsqnonlin` — set the `LevenbergMarquardt` option to 'off'.

To select an algorithm, use `optimset` to set the `Algorithm` option:

- `fsolve` — `trust-region-dogleg`, `trust-region-reflective`, or `levenberg-marquardt`
- `lsqcurvefit` or `lsqnonlin` — `trust-region-reflective` or `levenberg-marquardt`

Solvers no longer use the `LevenbergMarquardt`, `LineSearchType`, and `NonLeqnAlgorithm` options, since these options relate only to the Gauss-Newton algorithm.

DerivativeCheck Changes

The `DerivativeCheck` option checks whether a solver's finite-difference approximations match the gradient or Jacobian functions that you supply. When a solver finds a discrepancy between the computed derivatives and their finite-difference approximations, the solver now errors. Solvers used to pause in this situation instead of erroring.

Additionally, solvers now compare derivatives at a point near the initial point x_0 , but not exactly at x_0 . Previously, solvers performed the comparison at x_0 . This change usually gives more reliable `DerivativeCheck` decisions. For details, see [Checking Validity of Gradients or Jacobians](#).

Solvers do not include the computations for `DerivativeCheck` in the function count. See [Iterations and Function Counts](#).

Compatibility Considerations

Solvers compare the derivatives at a different point than before, so can change their decision on whether the derivatives match. Solvers now error instead of pause when they encounter a discrepancy.

fmincon ScaleProblem Default Changed

The `fmincon` interior-point and `sqp` algorithms can use the `ScaleProblem` option. The default value of `ScaleProblem` is now `'none'` instead of `'obj-and-constr'`.

Compatibility Considerations

Because of a bug in previous releases, when you did not provide gradients of the objective and nonlinear constraint functions, `fmincon` did not scale these functions. `fmincon` did scale linear constraints. So, if you do not provide gradients and have no linear constraints, the current `fmincon` behavior is the same as in previous releases. However, the current behavior can differ if you do provide gradients (`GradObj` or `GradConstr` is

'on'). If you provide gradients, have no linear constraints, and want to obtain the previous behavior, set `ScaleProblem` to `'obj-and-constr'` with `optimset`.

fsolve trust-region-dogleg Algorithm Change

The `fsolve trust-region-dogleg` algorithm no longer performs an internal calculation of conditioning. This change usually speeds `fsolve`.

Compatibility Considerations

`fsolve` iterations differ from previous versions. Additionally, the solution and all associated outputs can differ from previous versions. Usually, results are numerically equivalent to previous results.

Conversion of Error and Warning Message Identifiers

For R2011b, error and warning message identifiers have changed in Optimization Toolbox.

Compatibility Considerations

If you have scripts or functions that use message identifiers that changed, you must update the code to use the new identifiers. Typically, message identifiers are used to turn off specific warning messages, or in code that uses a `try/catch` statement and performs an action based on a specific error identifier.

For example, the `'optim:fmincon:ConstrainedProblemsOnly'` identifier has changed to `'optimlib:fmincon:ConstrainedProblemsOnly'`. If your code checks for `'optim:fmincon:ConstrainedProblemsOnly'`, you must update it to check for `'optimlib:fmincon:ConstrainedProblemsOnly'` instead.

To determine the identifier for a warning, run the following command just after you see the warning:

```
[MSG,MSGID] = lastwarn;
```

This command saves the message identifier to the variable `MSGID`.

To determine the identifier for an error, run the following command just after you see the error:

```
exception = MException.last;  
MSGID = exception.identifier;
```

Tip Warning messages indicate a potential issue with your code. While you can turn off a warning, a suggested alternative is to change your code so it runs warning free.

R2011a

Version: 6.0

New Features

Bug Fixes

Compatibility Considerations

New Quadratic Programming Algorithm

quadprog has a new algorithm named 'interior-point-convex'. It has these features:

- The algorithm has fast internal linear algebra.
- The algorithm handles sparse problems.
- There is a new presolve module that can improve speed, numerical stability, and detection of infeasibility.
- The algorithm handles large convex problems, and accepts and uses sparse inputs. See Large-Scale vs. Medium-Scale Algorithms.
- The algorithm optionally gives iterative display.
- The algorithm has enhanced exit messages.

For details on the algorithm, see interior-point-convex quadprog Algorithm. For help choosing the algorithm to use, see Quadratic Programming Algorithms.

Compatibility Considerations

You now choose the quadprog algorithm by using `optimset` to set the `Algorithm` option instead of the `LargeScale` option. If you don't set `Algorithm` or `LargeScale`, quadprog behaves as before.

Algorithm option choices are:

- `trust-region-reflective` (formerly `LargeScale = 'on'`), the default
- `active-set` (formerly `LargeScale = 'off'`)
- `interior-point-convex`

The previous way of choosing the quadprog algorithm at the command line was to set the `LargeScale` option to 'on' or 'off'. quadprog now ignores the `LargeScale` option, except when you set the inconsistent values `LargeScale = 'off'` and `Algorithm = 'trust-region-reflective'`. In this case, to avoid backward incompatibility, quadprog honors the `LargeScale` option, and uses the 'active-set' algorithm.

quadprog now checks whether any inputs are complex, and, if so, it errors. The only exception is the `Hinfo` argument for the `HessMult` option is allowed to be complex.

Enhanced Robustness in Nonlinear Solvers

More solvers now attempt to recover from errors in the evaluation of objective functions and nonlinear constraint functions during iteration steps, or, for some algorithms, during gradient estimation. The errors include results that are NaN or Inf for all solvers, or complex for `fmincon` and `fminunc`. If there is such an error, the algorithms attempt to take different steps. The following solvers are enhanced:

- `fmincon` trust-region-reflective algorithm (the interior-point and sqp algorithms already had this robustness)
- `fminunc` LargeScale algorithm
- `fsolve` trust-region-reflective, trust-region-dogleg, and levenberg-marquardt algorithms
- `lsqcurvefit` trust-region-reflective and levenberg-marquardt algorithms
- `lsqnonlin` trust-region-reflective and levenberg-marquardt algorithms

New Defaults in DiffMinChange and DiffMaxChange Options

The `DiffMinChange` and `DiffMaxChange` options set the minimum and maximum possible step sizes for finite differences in gradient estimation. The defaults are now:

- `DiffMinChange` = 0 (formerly `1e-8`)
- `DiffMaxChange` = Inf (formerly `0.1`)

Solvers have mechanisms that ensure nonzero and non-infinite step sizes, so the new defaults simply mean that the step size adjustment algorithms have fewer constraints.

The new defaults remove the previous arbitrary choices. The previous values can be inappropriate when components are too large or small in magnitude. Tests show these new defaults are good for most situations.

Compatibility Considerations

Some solver iterations can differ from previous ones. To obtain the previous behavior:

```
options = optimset('DiffMinChange',1e-8,'DiffMaxChange',0.1);
```

Output Structure Tweak

For the trust-region-reflective algorithm, the `algorithm` field of the output structure is now `'trust-region-reflective'`. This value differs slightly from the previous values returned by `fmincon`, `fsolve`, `lsqcurvefit`, `lsqnonlin`, and `quadprog`.

Compatibility Considerations

To avoid errors or unexpected results, update any code that depends on the exact value of the `output.algorithm` string.

ktrlink Compatible with KNITRO 7

`ktrlink` is compatible with KNITRO 7. For details, see `ktrlink: An Interface to KNITRO Libraries`, or the Ziena Optimization web site <http://www.ziena.com/>.

New quadprog Demo

A new demo shows how to solve portfolio optimization problems using `quadprog`. View the demo at the command line by entering

```
showdemo portfoptimdemo
```

R2010b

Version: 5.1

New Features

Bug Fixes

Enhanced `fmincon` Finite Difference Algorithms Add Robustness

The `fmincon` `interior-point` and `sqp` algorithms now attempt to recover from errors in the evaluation of objective functions and nonlinear constraint functions during gradient estimation. The errors include results that are NaN, Inf, or complex. If there is such an error, the finite differencing routines attempt to take different steps.

`ktrlink` Available for Macintosh 64-Bit Systems

The `ktrlink` function now works with Macintosh 64-bit systems. Therefore, `ktrlink` works on the same systems as all other Optimization Toolbox functions.

Output Structure Tweaks

All `linprog` and `quadprog` algorithms now create a `firstorderopt` field in the output structure. This field contains the value of the first-order optimality measure at the final point.

All `fmincon` and `quadprog` algorithms now create a `constrviolation` field in the output structure. This field contains the largest value of the constraint functions at the final point: bounds, linear constraints, and nonlinear constraints. (Some algorithms return the larger of the constraint functions and 0.) See [Writing Constraints](#).

New Video Demo on Modeling

There is a new two-part video on modeling and solving optimization problems:

- [Mathematical Modeling with Optimization, Part 1](#)
- [Optimization Modeling 2: Converting to Solver Form](#)

R2010a

Version: 5.0

New Features

Bug Fixes

Compatibility Considerations

New fmincon Algorithm

fmincon has a new algorithm called SQP for Sequential Quadratic Programming. The algorithm has the following features:

- Honors bounds at all iterations
- Attempts a different step if one leads to an objective or constraint function returning a NaN, Inf, or complex result
- Fast internal linear algebra for solving quadratic programs

Choose the algorithm at the command line by setting the `Algorithm` option to `'sqp'` with `optimset`. For more information about the algorithm, see fmincon SQP Algorithm in the Optimization Toolbox documentation.

lsqnonneg No Longer Uses x0

The `lsqnonneg` solver no longer accepts a start point `x0` as an optional input.

Compatibility Considerations

The Optimization Tool no longer has an input region for accepting a start point. If you import or run a problem that contains a start point `x0`, MATLAB issues a warning. Also, the Optimization Tool and `lsqnonneg` ignore `x0`, and instead use a start point of a vector of zeroes. If you export a problem structure from the Optimization Tool, there is no `x0` field.

R2009b

Version: 4.3

New Features

Bug Fixes

Compatibility Considerations

Enhanced Exit Messages in Selected Solvers

Enhanced, clearer exit messages in `fsolve`, `lsqnonlin`, and `lsqcurvefit`, with links for more information. For more information about the enhancements, see [Exit Flags and Exit Messages](#).

Compatibility Considerations

For solvers with enhanced exit messages, the content of `output.message` contains many more characters than before. User code that relies on this field might need to be modified in order to display the larger exit message satisfactorily.

fmincon Interior-Point Algorithm Robust to Certain Errors

The `fmincon` interior-point algorithm attempts to continue when a user-supplied objective or constraint function returns `Inf`, `NaN`, or a complex result. For more information, see [fmincon Interior Point Algorithm](#).

Changes in quadprog

The large-scale `quadprog` algorithm now uses the `TolFun` and `MaxIter` tolerances for deciding when to end iterations when there are only linear equality constraints, instead of the `TolPCG` and `MaxPCGIter` tolerances.

The `quadprog` output structure now contains the `constrviolation` field, which reports the maximum constraint function at the final point.

Compatibility Considerations

For large-scale linear equality constrained problems, the default values of the tolerances are much tighter than before, so `quadprog` can take more iterations, but the resulting solution should be more accurate.

Changes in linprog

The large-scale interior-point algorithm of `linprog` now has a backtracking mechanism for the case of stalling, and performs LDL factorization when there is rank deficiency. For more information, see [Large Scale Linear Programming](#).

The `linprog` output structure now contains the `constrviolation` field, which reports the maximum constraint function at the final point.

Compatibility Considerations

The interior-point algorithm of `linprog` might arrive at different solutions than before, and can solve more problems than before.

Multiobjective `optimValues` Changes

The `optimValues` structure, used by output functions, has two new fields to better reflect the state of multiobjective solvers:

- For `fgoalattain`, the `optimValues.attainfactor` field contains the value of γ , the attainment factor.
- For `fminimax`, the `optimValues.maxfval` field contains the value $\max_i F_i$, where F is the vector of objectives.

Furthermore, the value stored in `optimValues.fval` has changed. Now `optimValues.fval` contains the vector F of objective function values. For a complete description of the current `optimValues` structure, see `Fields in optimValues`.

Compatibility Considerations

User code that uses the `optimValues.fval` field within an output function in `fgoalattain` and `fminimax` might need to be updated to avoid errors

R2009a

Version: 4.2

New Features

Bug Fixes

Compatibility Considerations

Parallel Gradient Estimation Available in fmincon Interior-Point Algorithm

The `fmincon` solver's interior-point algorithm can now compute finite differences in parallel in order to speed the estimation of gradients. For details on how to use this parallel gradient estimation, see the Parallel Computing for Optimization chapter in the User's Guide.

Enhanced Exit Messages in Selected Solvers

Solvers print exit messages by default at the end of their runs. The exit messages are different in R2009a for several solvers, and the messages have been enhanced with new functionality. The following sections describe the new features and changes. There is more information in the Exit Flags and Exit Messages section of the User's Guide.

The following solvers have enhanced exit messages:

- `fgoalattain`
- `fmincon`
- `fminimax`
- `fminunc`
- `fsemif`

Links to More Information Window

The enhanced exit messages include hyperlinks within their exit messages. These hyperlinks bring up a window containing further information about the terms used in the exit messages.

Link for More Detail in Command Window

A `<stopping criteria details>` hyperlink may appear at the end of an exit message, depending on the solver and setting of the `Display` option. This link causes the solver to print more detail about the exit conditions to the MATLAB Command Window.

New Display Option Values Control Default Detail

There are new values of the `Display` option to control whether detailed exit messages appear instead of the default (simpler) messages. The new values are:

-
- 'final-detailed'
 - 'iter-detailed'
 - 'notify-detailed'

These settings have the same effect as the corresponding settings without '-detailed', but give detailed exit messages instead of the default exit messages. For solvers without the new exit messages, the '-detailed' options give the same behavior as without '-detailed'.

Messages in Output Structure

For solvers with enhanced exit messages, the `message` field of the output structure contains both the default (simpler) and the detailed exit messages, separated by a line of text stating `Stopping criteria details:`. The message field does not contain hyperlinks; it contains only text.

Compatibility Considerations

For solvers with enhanced exit messages, the content of `output.message` contains many more characters than before. User code that relies on this field may need to be modified in order to display the larger exit message satisfactorily.

Change in linprog Simplex Algorithm

The simplex algorithm of `linprog` now detects when there is no progress in the solution process. It attempts to continue by performing bound perturbation.

Compatibility Considerations

The simplex algorithm of `linprog` might arrive at different solutions than before, and can solve more problems than before.

Change in fminunc Exit Flag

One exit flag in the `fminunc` medium-scale solver was changed from -2 to 5. This flag appears when the solver predicts a change in function value at the next step in its iterations will be less than the `TolFun` tolerance. This condition can occur at a relative minimum, which should be reported by a positive flag.

Compatibility Considerations

This change might cause users (or code) that examine exit flags to evaluate a result more favorably than previously, since positive exit flags represent normal termination of solvers.

New demos

There are two new demos:

- A demo showing how to use Symbolic Math Toolbox™ functions to help calculate gradients and Hessians. Run the demo at the MATLAB command line by entering `echodemo symbolic_optim_demo`.
- A demo showing how to use `fseminf` for investigating the effect of parameter uncertainty. Run the demo at the MATLAB command line by entering `echodemo airpollution`.

Furthermore, the optimization tutorial demo now shows how to include extra parameters. Run the demo at the MATLAB command line by entering `echodemo tutdemo`.

R2008b

Version: 4.1

New Features

Bug Fixes

Compatibility Considerations

fsolve, lsqcurvefit, lsqnonlin Algorithm and Options Changes

- The Levenberg-Marquardt algorithm was refactored in the solvers `fsolve`, `lsqcurvefit` and `lsqnonlin`. It is now a more standard implementation, that accepts and preserves sparse Jacobians.
- Choose between the algorithms used in `fsolve`, `lsqcurvefit` and `lsqnonlin` using the new `Algorithm` option.
- There is a new `ScaleProblem` option that can sometimes help the Levenberg-Marquardt algorithm converge.
- The default `fsolve` algorithm, `'trust-region-dogleg'`, has been validated to work with sparse Jacobians.

Compatibility Considerations

- The refactored Levenberg-Marquardt algorithm can cause `fsolve`, `lsqcurvefit` and `lsqnonlin` to yield different answers than before.
- The previous way of choosing the algorithm at the command line was to set the `LargeScale` option to `'on'` or `'off'`, and, for all solvers but `fsolve`, to set the `LevenbergMarquardt` option to `'on'` or `'off'`. For `fsolve`, in addition to the `LargeScale` option, you needed to set the `NonLeqAlgorithm` option appropriately. `LargeScale`, `NonLeqAlgorithm`, and `LevenbergMarquardt` are now ignored, except when choosing to use the Gauss-Newton algorithm.
- The Gauss-Newton algorithm warns that soon it may no longer be available.
- The default value of the `MaxFunEvals` option in the refactored Levenberg-Marquardt algorithm is now `200*numberOfVariables`; the previous value was `100*numberOfVariables`.

Optimization Tool Enables Parallel Functionality

You can now access built-in parallel functionality in Optimization Tool for relevant Optimization Toolbox solvers and, if licensed, Global Optimization Toolbox solvers. The option is available when you have a license for Parallel Computing Toolbox™ functions.

Central Finite Differences Available in Selected Solvers

The following solvers can now use central finite differences for gradient estimation:

-
- `fgoalattain`
 - `fmincon`
 - `fminimax`
 - `fminunc`
 - `fseminf`

The `fmincon` active-set algorithm and `fminunc` medium-scale algorithm gained central finite differences this release. The `fmincon` interior-point algorithm already had them, and the trust-region-reflective algorithm for both solvers requires a user-supplied gradient, so does not use finite differences.

To use central finite differences, use `optimset` to set the `FinDiffType` option to `'central'` instead of the default `'forward'`. This causes the solver to estimate gradients by formulae such as

$$\nabla f(x) \approx \left[\frac{f(x + \Delta_1 e_1) - f(x - \Delta_1 e_1)}{2\Delta_1}, \dots, \frac{f(x + \Delta_n e_n) - f(x - \Delta_n e_n)}{2\Delta_n} \right],$$

instead of

$$\nabla f(x) \approx \left[\frac{f(x + \Delta_1 e_1) - f(x)}{\Delta_1}, \frac{f(x + \Delta_2 e_2) - f(x)}{\Delta_2}, \dots, \frac{f(x + \Delta_n e_n) - f(x)}{\Delta_n} \right].$$

Central finite differences take twice as many function evaluations as forward finite differences, but are usually much more accurate.

Central finite differences can work in parallel for gradient estimation in `fgoalattain`, `fmincon` active-set algorithm, and `fminimax`. For details on how to use this parallel gradient estimation, see the Parallel Computing for Optimization chapter in the User's Guide.

lsqnonneg Refactored

`lsqnonneg` was refactored. It can now use sparse matrices, and it preserves sparsity during its execution.

Finite Difference Algorithm Tweaked

A subroutine for gradient estimation by forward finite differences in nonlinear solvers had a bug that affected it when the current point x had a component with the value 0. Forward finite differences are typically calculated with a step size proportional to $\sqrt{\text{eps}}$, which is about 1.5×10^{-8} . When a component of x was 0, the step size would instead be proportional to `DiffMinChange`, which has a default value of 10^{-8} . There is now no difference in step size when x is 0.

Compatibility Considerations

Nonlinear solvers can run slightly differently whenever an iteration causes a component of x to be zero, and gradients are estimated by forward finite differences.

DerivativeCheck Tolerance Changed

The `DerivativeCheck` option enables you to ascertain whether the derivative (gradient) functions that you supply for objective or constraint functions give approximately the same values as those estimated by a solver using finite differences. The meaning of “approximately” has changed. Now it means the relative error of each component of the gradient is less than 10^{-6} , unless the size of an analytically given component is smaller than 1, in which case it means the absolute difference is less than 10^{-6} . Previously, the gradients were considered approximately equal if the maximum absolute error in any component of the gradient was less than $(10^{-6} * \text{norm of analytic gradient}) + 10^{-5}$.

Compatibility Considerations

Some problems will now report violations of the `DerivativeCheck` condition, when previously they would not.

R2008a

Version: 4.0

New Features

Bug Fixes

Compatibility Considerations

Parallel Computing Toolbox Support in `fmincon`, `fminimax`, and `fgoalattain`

`fmincon`, `fminimax`, and `fgoalattain` can take finite differences in parallel in order to speed the estimation of gradients. For details on how to use this parallel gradient estimation, see the Parallel Computing for Optimization chapter in the User's Guide.

Combined and Extended `optimtool`

The Global Optimization Toolbox GUIs `gatool` and `psearchtool` have been combined into the Optimization Tool GUI. To access these GUIs, type `optimtool` at the command line, and choose the appropriate solver.

Furthermore, three new Global Optimization Toolbox solvers were added to Optimization Tool: `gamultiobj`, `simulannealbnd`, and `threshacceptbnd`.

Optimization Tool shows Global Optimization Toolbox solvers only if these solvers are licensed.

New `fmincon` Solver, New Option Algorithm for `fmincon`, Option `LargeScale` Changed

The new interior-point algorithm is a large-scale algorithm that can handle all types of constraints. It has several new options, explained in the `fmincon` function reference pages.

`fmincon` now has three algorithms. Choose between them by setting the new option `Algorithm` to:

- `'trust-region-reflective'` (formerly known as `'large scale'`)
- `'active-set'` (formerly known as `'medium scale'`)
- `'interior-point'`

By default, `Algorithm = 'trust-region-reflective'`.

Compatibility Considerations

The previous way of choosing the algorithm at the command line was to set option `LargeScale` to `'on'` or `'off'`. `LargeScale` is now ignored, except when `LargeScale`

= 'off' and `Algorithm = 'trust-region-reflective'`. In this case, the 'active-set' algorithm is used, to minimize backward incompatibility.

External Interface to KNITRO Libraries

Use the new `ktlink` function to call KNITRO optimization libraries from Ziena Optimization, Inc. KNITRO libraries must be purchased separately. The External Interface chapter of the User's Guide describes the `ktlink` function.

Default PrecondBandWidth = Inf in lsqcurvefit, lsqnonlin, and fsolve

The default value of the `PrecondBandWidth` option changed from 0 to Inf for the `lsqcurvefit`, `lsqnonlin`, and `fsolve` solvers. This change was beneficial in the vast majority of tested problems.

In Optimization Tool, the default in **Algorithm settings > Subproblem algorithm** is now **Cholesky factorization**, instead of **Preconditioned CG = 0**.

Compatibility Considerations

The new default can lead to slower performance for problems with high-dimensional nonlinearities. If this happens, change the default to another value such as 0 (the previous default).

New Option TolConSQP with Incompatible Default Value

The new `TolConSQP` option exposes a parameter that was fixed at `eps` before. The parameter is used in the `fmincon`, `fminimax`, `fgoalattain`, and `fseminf` solvers.

Compatibility Considerations

The new default value is `TolConSQP = 1e-6`. This did not affect a vast majority of tested cases, and was beneficial in some. If you want exactly the same behavior as before, set `TolConSQP = eps` using `optimset`.

Field constrviolation in Output Structure

The `constrviolation` field now exists in the output structure for the `fgoalattain`, `fmincon`, `fminimax`, and `fseminf` functions; it measures the nonlinear constraint violation.

R2007b

Version: 3.1.2

Bug Fixes

R2007a

Version: 3.1.1

New Features

Bug Fixes

Compatibility Considerations

Changes to Outputs of Multiobjective Solvers

- `fminimax` now returns the value of `max(fval)` in the output `maxfval`.
- The iterative display of `fminimax` and `fgoalattain` have changed.

Compatibility Considerations

- The third output argument of the solver `fminimax`, `maxfval`, is described in the documentation as the maximum of the objective functions in the input `fun` evaluated at the solution `x`, that is, `max(fval)`. Before this release, `fminimax` actually returned the maximum of the objective functions in the reformulated minimax problem internally constructed by the algorithm. This value was typically very close to, but not necessarily equal to, `max(fval)`. `fminimax` now returns the exact value of `max(fval)` in the output `maxfval`.
- The iterative display for `fminimax` includes a new column with header `Objective value` that reports the objective function value of the nonlinear programming reformulation of the minimax problem. The column header `Max{F, constraints}` has been changed to `Max constraint`, and the column now contains the maximum violation among all constraints, both internally constructed and user-provided.

The iterative display for `fgoalattain` now shows the value of the attainment factor in the `Attainment factor` column. A new column, `Max constraint`, contains the maximum violation among all constraints, both internally constructed and user-provided.

R2006b

Version: 3.1

New Features

Bug Fixes

Compatibility Considerations

New Optimization Tool

The Optimization Tool is a graphical user interface (GUI) for performing common optimization tasks with the Optimization Toolbox. Using the `optimtool`, you can do the following:

- Select a solver and define your optimization problem.
- Set and inspect optimization options and their default values.
- Run problems and visualize results.
- Import and export problem definitions, algorithm options, and results between the MATLAB workspace and the Optimization Tool.
- Automatically generate M-code to capture, automate, and recreate your problem.
- Access built-in help.

Plot Functions Option Added

You can now specify the `PlotFcns` option in the `optimset` function or using the Optimization Tool for use with an Optimization Toolbox solver. With this option, you can plot various measures of progress while the algorithm executes. You can select from several predefined plots, or you can write your own.

Output Function Option Enhanced to Accept Multiple Functions

You can now specify more than one output function in the `OutputFcn` option.

Changes to the Output Function

The output function input `x` and fields in the `optimValues` structure have the following changes that address bugs in previous releases:

- `residual` now returns the residual vector for `lsqnonlin` and `lsqcurvefit`.
- `resnorm` contains the sum of squares and has been added for `lsqnonlin` and `lsqcurvefit`. The previous field `fval` has been removed for these functions.
- `procedure` has been removed for `lsqnonlin`, `lsqcurvefit`, and `fsolve`.
- `x` now returns the expected shape and size for `fgoalattain` and `fminimax`.

Compatibility Considerations

The above changes to the input `x` and `optimValues` structure have the following compatibility considerations in the output function:

- If you have references to the `residual` in a previous version, note that the value of this field has changed for `lsqnonlin` and `lsqcurvefit`. This fixes the problem addressed by the bug report S-289285.
- Any references to `fval` for `lsqnonlin` and `lsqcurvefit` need to be updated to `resnorm`. This fixes the problem addressed by the bug report S-289285.
- Any references to `procedure` for `lsqnonlin` and `lsqcurvefit` need to be removed. This fixes the problem addressed by the bug report S-291974.
- Previously, for `fgoalattain` and `fminimax`, `x` returned a column vector with an additional last element. If you have references to the values for `x` in a previous version, the extra element must be removed and the output vector may need to be reshaped. This fixes the problem addressed by the bug report S-315658.

R2006a

Version: 3.0.4

Bug Fixes

R14SP3

Version: 3.0.3

New Features

Bug Fixes

Notify Parameter Added to Display Option for Five Functions

You can now set the optimization option `Display` to `'notify'` for the functions `fmincon`, `fminunc`, `fminimax`, `fgoalattain`, and `fseminf`. When `Display` is set to `'notify'`, the output is displayed only if the function does not converge.