

Text Analytics Toolbox™

User's Guide



MATLAB®

R2019a



How to Contact MathWorks



Latest news: www.mathworks.com
Sales and services: www.mathworks.com/sales_and_services
User community: www.mathworks.com/matlabcentral
Technical support: www.mathworks.com/support/contact_us



Phone: 508-647-7000



The MathWorks, Inc.
1 Apple Hill Drive
Natick, MA 01760-2098

Text Analytics Toolbox™ User's Guide

© COPYRIGHT 2017–2019 by The MathWorks, Inc.

The software described in this document is furnished under a license agreement. The software may be used or copied only under the terms of the license agreement. No part of this manual may be photocopied or reproduced in any form without prior written consent from The MathWorks, Inc.

FEDERAL ACQUISITION: This provision applies to all acquisitions of the Program and Documentation by, for, or through the federal government of the United States. By accepting delivery of the Program or Documentation, the government hereby agrees that this software or documentation qualifies as commercial computer software or commercial computer software documentation as such terms are used or defined in FAR 12.212, DFARS Part 227.72, and DFARS 252.227-7014. Accordingly, the terms and conditions of this Agreement and only those rights specified in this Agreement, shall pertain to and govern the use, modification, reproduction, release, performance, display, and disclosure of the Program and Documentation by the federal government (or other entity acquiring for or through the federal government) and shall supersede any conflicting contractual terms or conditions. If this License fails to meet the government's needs or is inconsistent in any respect with federal procurement law, the government agrees to return the Program and Documentation, unused, to The MathWorks, Inc.

Trademarks

MATLAB and Simulink are registered trademarks of The MathWorks, Inc. See www.mathworks.com/trademarks for a list of additional trademarks. Other product or brand names may be trademarks or registered trademarks of their respective holders.

Patents

MathWorks products are protected by one or more U.S. patents. Please see www.mathworks.com/patents for more information.

Revision History

March 2018	Online Only	New for Version 1.1 (Release 2018a)
September 2018	Online Only	Revised for Version 1.2 (Release 2018b)
March 2019	Online Only	Revised for Version 1.3 (Release 2019a)

Text Data Preparation

1

Extract Text Data from Files	1-2
Prepare Text Data for Analysis	1-12
Parse HTML and Extract Text Content	1-22
Correct Spelling Using Edit Distance Searchers	1-28

Modeling and Prediction

2

Create Simple Text Model for Classification	2-2
Analyze Text Data Using Multiword Phrases	2-9
Analyze Text Data Using Topic Models	2-18
Choose Number of Topics for LDA Model	2-25
Compare LDA Solvers	2-30
Analyze Text Data Containing Emojis	2-35
Train a Sentiment Classifier	2-43
Classify Text Data Using Deep Learning	2-53
Classify Text Data Using Convolutional Neural Network	2-76

Classify Out-of-Memory Text Data Using Deep Learning	2-87
Pride and Prejudice and MATLAB	2-94
Word-By-Word Text Generation Using Deep Learning	2-101
Classify Out-of-Memory Text Data Using Custom Mini-Batch Datastore	2-108

Display and Presentation

3

Visualize Text Data Using Word Clouds	3-2
Visualize Word Embeddings Using Text Scatter Plots	3-8

Language Support

4

Language Considerations	4-2
Language-Independent Features	4-4
Japanese Language Support	4-6
Tokenization	4-6
Part of Speech Details	4-6
Named Entity Recognition	4-7
Stop Words	4-9
Lemmatization	4-9
Language-Independent Features	4-10
Analyze Japanese Text Data	4-12
German Language Support	4-26
Tokenization	4-26
Sentence Detection	4-26
Part of Speech Details	4-28
Named Entity Recognition	4-29

Stop Words	4-30
Stemming	4-31
Language-Independent Features	4-31
Analyze German Text Data	4-33
Language-Independent Features	4-47
Word and N-Gram Counting	4-47
Modeling and Prediction	4-47

Glossary

5

Text Analytics Glossary	5-2
Documents and Tokens	5-2
Preprocessing	5-3
Modeling and Prediction	5-4
Visualization	5-7

Text Data Preparation

- “Extract Text Data from Files” on page 1-2
- “Prepare Text Data for Analysis” on page 1-12
- “Parse HTML and Extract Text Content” on page 1-22
- “Correct Spelling Using Edit Distance Searchers” on page 1-28

Extract Text Data from Files

This example shows how to extract the text data from text, HTML, Microsoft® Word, PDF, CSV, and Microsoft Excel® files and import it into MATLAB® for analysis.

Usually, the easiest way to import text data into MATLAB is to use the `extractFileText` function. This function extracts the text data from text, PDF, HTML, and Microsoft Word files. To import text from CSV and Microsoft Excel files, use `readtable`. To extract text from HTML code, use `extractHTMLText`. To read data from PDF forms, use `readPDFFormData`.

Text File

Extract the text from `sonnets.txt` using `extractFileText`. The file `sonnets.txt` contains Shakespeare's sonnets in plain text.

```
filename = "sonnets.txt";  
str = extractFileText(filename);
```

View the first sonnet by extracting the text between the two titles "I" and "II".

```
start = " I" + newline;  
fin = " II";  
sonnet1 = extractBetween(str,start,fin)
```

```
sonnet1 =  
"  
    From fairest creatures we desire increase,  
    That thereby beauty's rose might never die,  
    But as the ripper should by time decease,  
    His tender heir might bear his memory:  
    But thou, contracted to thine own bright eyes,  
    Feed'st thy light's flame with self-substantial fuel,  
    Making a famine where abundance lies,  
    Thy self thy foe, to thy sweet self too cruel:  
    Thou that art now the world's fresh ornament,  
    And only herald to the gaudy spring,  
    Within thine own bud buriest thy content,  
    And tender churl mak'st waste in niggarding:  
    Pity the world, or else this glutton be,  
    To eat the world's due, by the grave and thee.  
"
```


Microsoft Word Document

Extract the text from `sonnets.docx` using `extractFileText`. The file `exampleSonnets.docx` contains Shakespeare's sonnets in a Microsoft Word document.

```
filename = "exampleSonnets.docx";  
str = extractFileText(filename);
```

View the second sonnet by extracting the text between the two titles "II" and "III".

```
start = " II" + newline;  
fin = " III";  
sonnet2 = extractBetween(str,start,fin)
```

```
sonnet2 =  
"
```

```
    When forty winters shall besiege thy brow,  
    And dig deep trenches in thy beauty's field,  
    Thy youth's proud livery so gazed on now,  
    Will be a tatter'd weed of small worth held:  
    Then being asked, where all thy beauty lies,  
    Where all the treasure of thy lusty days;  
    To say, within thine own deep sunken eyes,  
    Were an all-eating shame, and thriftless praise.  
    How much more praise deserv'd thy beauty's use,  
    If thou couldst answer 'This fair child of mine  
    Shall sum my count, and make my old excuse,'  
    Proving his beauty by succession thine!  
        This were to be new made when thou art old,  
        And see thy blood warm when thou feel'st it cold.
```

"

The example Microsoft Word document uses two newline characters between each line. To replace these characters with a single newline character, use the `replace` function.

```
sonnet2 = replace(sonnet2,[newline newline],newline)
```

```
sonnet2 =
```

```
"
```

```
    When forty winters shall besiege thy brow,  
    And dig deep trenches in thy beauty's field,  
    Thy youth's proud livery so gazed on now,  
    Will be a tatter'd weed of small worth held:  
    Then being asked, where all thy beauty lies,  
    Where all the treasure of thy lusty days;  
    To say, within thine own deep sunken eyes,  
    Were an all-eating shame, and thriftless praise.  
    How much more praise deserv'd thy beauty's use,  
    If thou couldst answer 'This fair child of mine  
    Shall sum my count, and make my old excuse,'  
    Proving his beauty by succession thine!  
        This were to be new made when thou art old,  
        And see thy blood warm when thou feel'st it cold.
```

```
"
```

PDF Files

Extract text from PDF documents and data from PDF forms.

PDF Document

Extract the text from `sonnets.pdf` using `extractFileText`. The file `exampleSonnets.pdf` contains Shakespeare's sonnets in a PDF.

```
filename = "exampleSonnets.pdf";  
str = extractFileText(filename);
```

View the third sonnet by extracting the text between the two titles "III" and "IV". This PDF has a space before each newline character.

```
start = " III " + newline;  
fin = "IV";  
sonnet3 = extractBetween(str,start,fin)
```

```
sonnet3 =  
"  
    Look in thy glass and tell the face thou viewest  
    Now is the time that face should form another;  
    Whose fresh repair if now thou not renewest,  
    Thou dost beguile the world, unbless some mother.  
    For where is she so fair whose unear'd womb  
    Disdains the tillage of thy husbandry?  
    Or who is he so fond will be the tomb,  
    Of his self-love to stop posterity?  
    Thou art thy mother's glass and she in thee  
    Calls back the lovely April of her prime;  
    So thou through windows of thine age shalt see,  
    Despite of wrinkles this thy golden time.  
        But if thou live, remember'd not to be,  
        Die single and thine image dies with thee.  
  
"
```

PDF Form

To read text data from PDF forms, use `readPDFFormData`. The function returns a struct containing the data from the PDF form fields.

```
filename = "weatherReportForm1.pdf";  
data = readPDFFormData(filename)  
  
data = struct with fields:  
    event_type: "Thunderstorm Wind"  
    event_narrative: "Large tree down between Plantersville and Nettleton."
```

HTML

Extract text from HTML files, HTML code, and the web.

HTML File

To extract text data from a saved HTML file, use `extractFileText`.

```
filename = "exampleSonnets.html";  
str = extractFileText(filename);
```

View the forth sonnet by extracting the text between the two titles "IV" and "V".

```
start = newline + "IV" + newline;
fin = newline + "V" + newline;
sonnet4 = extractBetween(str,start,fin)

sonnet4 =
"
    Unthrifty loveliness, why dost thou spend
    Upon thy self thy beauty's legacy?
    Nature's bequest gives nothing, but doth lend,
    And being frank she lends to those are free:
    Then, beauteous niggard, why dost thou abuse
    The bounteous largess given thee to give?
    Profitless usurer, why dost thou use
    So great a sum of sums, yet canst not live?
    For having traffic with thy self alone,
    Thou of thy self thy sweet self dost deceive:
    Then how when nature calls thee to be gone,
    What acceptable audit canst thou leave?
    Thy unused beauty must be tombed with thee,
    Which, used, lives th' executor to be.
"
```

HTML Code

To extract text data from a string containing HTML code, use `extractHTMLText`.

```
code = "<html><body><h1>THE SONNETS</h1><p>by William Shakespeare</p></body></html>";
str = extractHTMLText(code)

str =
"THE SONNETS

    by William Shakespeare"
```

From the Web

To extract text data from a web page, first read the HTML code using `webread`, and then use `extractHTMLText`.

```
url = "https://www.mathworks.com/help/textanalytics";
code = webread(url);
str = extractHTMLText(code)
```

```
str =
    'Text Analytics Toolbox™ provides algorithms and visualizations for preprocessing
    Text Analytics Toolbox includes tools for processing raw text from sources such as
    Using machine learning techniques such as LSA, LDA, and word embeddings, you can t
```

Parse HTML Code

To find particular elements of HTML code, parse the code using `htmlTree` and use `findElement`. Parse the HTML code and find all the hyperlinks. The hyperlinks are nodes with element name "A".

```
tree = htmlTree(code);
selector = "A";
subtrees = findElement(tree,selector);
```

View the first 10 subtrees and extract the text using `extractHTMLText`.

```
subtrees(1:10)

ans =
    10×1 htmlTree:

    <A class="svg_link navbar-brand" href="https://www.mathworks.com?s_tid=gn_logo"><I
    <A class="mwa-nav_login" href="https://www.mathworks.com/login?uri=http://www.mathw
    <A href="https://www.mathworks.com/products.html?s_tid=gn_ps">Products</A>
    <A href="https://www.mathworks.com/solutions.html?s_tid=gn_sol">Solutions</A>
    <A href="https://www.mathworks.com/academia.html?s_tid=gn_acad">Academia</A>
    <A href="https://www.mathworks.com/support.html?s_tid=gn_supp">Support</A>
    <A href="https://www.mathworks.com/matlabcentral/?s_tid=gn_mlc">Community</A>
    <A href="https://www.mathworks.com/company/events.html?s_tid=gn_ev">Events</A>
    <A href="https://www.mathworks.com/company/aboutus/contact_us.html?s_tid=gn_cntus">
    <A href="https://www.mathworks.com/store?s_cid=store_top_nav&amp;s_tid=gn_store">H
```

```
str = extractHTMLText(subtrees);
```

View the extracted text of the first 10 hyperlinks.

```
str(1:10)

ans = 10×1 string array
    ""
```

```
"Sign In"  
"Products"  
"Solutions"  
"Academia"  
"Support"  
"Community"  
"Events"  
"Contact Us"  
"How to Buy"
```

To get the link targets, use `getAttributes` and specify the attribute `"href"` (hyperlink reference). Get the link targets of the first 10 subtrees.

```
attr = "href";  
str = getAttribute(subtrees(1:10),attr)  
  
str = 10x1 string array  
"https://www.mathworks.com?s_tid=gn_logo"  
"https://www.mathworks.com/login?uri=http://www.mathworks.com/help/textanalytics/i  
"https://www.mathworks.com/products.html?s_tid=gn_ps"  
"https://www.mathworks.com/solutions.html?s_tid=gn_sol"  
"https://www.mathworks.com/academia.html?s_tid=gn_acad"  
"https://www.mathworks.com/support.html?s_tid=gn_supp"  
"https://www.mathworks.com/matlabcentral/?s_tid=gn_mlc"  
"https://www.mathworks.com/company/events.html?s_tid=gn_ev"  
"https://www.mathworks.com/company/aboutus/contact_us.html?s_tid=gn_cntus"  
"https://www.mathworks.com/store?s_cid=store_top_nav&s_tid=gn_store"
```

CSV and Microsoft Excel Files

To extract text data from CSV and Microsoft Excel files, use `readtable` and extract the text data from the table that it returns.

Extract the table data using the `readtable` function and view the first few rows of the table.

```
T = readtable('weatherReports.csv', 'TextType', 'string');  
head(T)
```

```
ans=8x16 table  
          Time          event_id          state          event_type          da
```

22-Jul-2016 16:10:00	6.4433e+05	"MISSISSIPPI"	"Thunderstorm Wind"
15-Jul-2016 17:15:00	6.5182e+05	"SOUTH CAROLINA"	"Heavy Rain"
15-Jul-2016 17:25:00	6.5183e+05	"SOUTH CAROLINA"	"Thunderstorm Wind"
16-Jul-2016 12:46:00	6.5183e+05	"NORTH CAROLINA"	"Thunderstorm Wind"
15-Jul-2016 14:28:00	6.4332e+05	"MISSOURI"	"Hail"
15-Jul-2016 16:31:00	6.4332e+05	"ARKANSAS"	"Thunderstorm Wind"
15-Jul-2016 16:03:00	6.4343e+05	"TENNESSEE"	"Thunderstorm Wind"
15-Jul-2016 17:27:00	6.4344e+05	"TENNESSEE"	"Hail"

Extract the text data from the `event_narrative` column and view the first few strings.

```
str = T.event_narrative;
str(1:10)
```

```
ans = 10x1 string array
```

```
"Large tree down between Plantersville and Nettleton."
"One to two feet of deep standing water developed on a street on the Winthrop Univ
"NWS Columbia relayed a report of trees blown down along Tom Hall St."
"Media reported two trees blown down along I-40 in the Old Fort area."
""
"A few tree limbs greater than 6 inches down on HWY 18 in Roseland."
"Awning blown off a building on Lamar Avenue. Multiple trees down near the interse
"Quarter size hail near Rosemark."
"Tin roof ripped off house on Old Memphis Road near Billings Drive. Several large
"Powerlines down at Walnut Grove and Cherry Lane roads."
```

Extract Text from Multiple Files

If your text data is contained in multiple files in a folder, then you can import the text data into MATLAB using a file datastore.

Create a file datastore for the example sonnet text files. The examples files are named "exampleSonnetN.txt", where N is the number of the sonnet. Specify the file name using the wildcard "*" to find all file names of this structure. To specify the read function to be `extractFileText`, input this function to `fileDatastore` using a function handle.

```
fds = fileDatastore('exampleSonnet*.txt', 'ReadFcn', @extractFileText)
```

```
fds =
```

```
FileDatastore with properties:
```

```
Files: {
    '...\Documents\MATLAB\examples\textanalytics-ex15735454'
```

```
        ' ...\Documents\MATLAB\examples\textanalytics-ex15735454
        ' ...\Documents\MATLAB\examples\textanalytics-ex15735454
        ... and 1 more
    }
    UniformRead: 0
    ReadFcn: @extractFileText
    AlternateFileSystemRoots: {}
```

Loop over the files in the datastore and read each text file.

```
str = [];
while hasdata(fds)
    textData = read(fds);
    str = [str; textData];
end
```

View the extracted text.

```
str
str = 4x1 string array
" From fairest creatures we desire increase,␣ That thereby beauty's rose might ne
" When forty winters shall besiege thy brow,␣ And dig deep trenches in thy beauty
" Look in thy glass and tell the face thou viewest␣ Now is the time that face sho
" Unthrifty loveliness, why dost thou spend␣ Upon thy self thy beauty's legacy?␣
```

See Also

[extractFileText](#) | [extractHTMLText](#) | [readPDFFormData](#) | [tokenizedDocument](#)

Related Examples

- “Prepare Text Data for Analysis” on page 1-12
- “Create Simple Text Model for Classification” on page 2-2
- “Visualize Text Data Using Word Clouds” on page 3-2
- “Analyze Text Data Containing Emojis” on page 2-35
- “Analyze Text Data Using Topic Models” on page 2-18
- “Analyze Text Data Using Multiword Phrases” on page 2-9

- “Classify Text Data Using Deep Learning” on page 2-53
- “Train a Sentiment Classifier” on page 2-43


Prepare Text Data for Analysis

This example shows how to create a function which cleans and preprocesses text data for analysis.

Text data can be large and can contain lots of noise which negatively affects statistical analysis. For example, text data can contain the following:

- Variations in case, for example "new" and "New"
- Variations in word forms, for example "walk" and "walking"
- Words which add noise, for example stop words such as "the" and "of"
- Punctuation and special characters
- HTML and XML tags

These word clouds illustrate word frequency analysis applied to some raw text data from weather reports, and a preprocessed version of the same text data.



Load and Extract Text Data

Load the example data. The file `weatherReports.csv` contains weather reports, including a text description and categorical labels for each event.

```
filename = "weatherReports.csv";
data = readtable(filename, 'TextType', 'string');
```

Extract the text data from the field `event_narrative`, and the label data from the field `event_type`.

```
textData = data.event_narrative;
labels = data.event_type;
textData(1:10)
```

```
ans = 10x1 string array
    "Large tree down between Plantersville and Nettleton."
    "One to two feet of deep standing water developed on a street on the Winthrop Univer
    "NWS Columbia relayed a report of trees blown down along Tom Hall St."
    "Media reported two trees blown down along I-40 in the Old Fort area."
    ""
    "A few tree limbs greater than 6 inches down on HWY 18 in Roseland."
    "Awning blown off a building on Lamar Avenue. Multiple trees down near the interse
    "Quarter size hail near Rosemark."
    "Tin roof ripped off house on Old Memphis Road near Billings Drive. Several large t
    "Powerlines down at Walnut Grove and Cherry Lane roads."
```

Create Tokenized Documents

Create an array of tokenized documents.

```
cleanedDocuments = tokenizedDocument(textData);
cleanedDocuments(1:10)

ans =
    10x1 tokenizedDocument:

     8 tokens: Large tree down between Plantersville and Nettleton .
    39 tokens: One to two feet of deep standing water developed on a street on the Win
    14 tokens: NWS Columbia relayed a report of trees blown down along Tom Hall St .
    14 tokens: Media reported two trees blown down along I-40 in the Old Fort area .
     0 tokens:
    15 tokens: A few tree limbs greater than 6 inches down on HWY 18 in Roseland .
    20 tokens: Awning blown off a building on Lamar Avenue . Multiple trees down near t
     6 tokens: Quarter size hail near Rosemark .
    21 tokens: Tin roof ripped off house on Old Memphis Road near Billings Drive . Seve
    10 tokens: Powerlines down at Walnut Grove and Cherry Lane roads .
```

Lemmatize the words using `normalizeWords`. To improve lemmatization, first add part of speech details to the documents using `addPartOfSpeechDetails`.

```
cleanedDocuments = addPartOfSpeechDetails(cleanedDocuments);
cleanedDocuments = normalizeWords(cleanedDocuments, 'Style', 'lemma');
cleanedDocuments(1:10)

ans =
    10x1 tokenizedDocument:
```

```

8 tokens: large tree down between plantersville and nettleton .
39 tokens: one to two foot of deep standing water develop on a street on the winthrop
14 tokens: nws columbia relay a report of tree blow down along tom hall st .
14 tokens: medium report two tree blow down along i-40 in the old fort area .
0 tokens:
15 tokens: a few tree limb great than 6 inch down on hwy 18 in roseland .
20 tokens: awning blow off a building on lamar avenue . multiple tree down near the
6 tokens: quarter size hail near rosemark .
21 tokens: tin roof rip off house on old memphis road near billings drive . several
10 tokens: powerlines down at walnut grove and cherry lane road .

```

Erase the punctuation from the documents.

```

cleanedDocuments = erasePunctuation(cleanedDocuments);
cleanedDocuments(1:10)

```

```

ans =
10x1 tokenizedDocument:

7 tokens: large tree down between plantersville and nettleton
37 tokens: one to two foot of deep standing water develop on a street on the winthrop
13 tokens: nws columbia relay a report of tree blow down along tom hall st
13 tokens: medium report two tree blow down along i40 in the old fort area
0 tokens:
14 tokens: a few tree limb great than 6 inch down on hwy 18 in roseland
18 tokens: awning blow off a building on lamar avenue multiple tree down near the
5 tokens: quarter size hail near rosemark
19 tokens: tin roof rip off house on old memphis road near billings drive several
9 tokens: powerlines down at walnut grove and cherry lane road

```

Words like "a", "and", "to", and "the" (known as stop words) can add noise to data. Remove a list of stop words using the `removeStopWords` function.

```

cleanedDocuments = removeStopWords(cleanedDocuments);
cleanedDocuments(1:10)

```

```

ans =
10x1 tokenizedDocument:

5 tokens: large tree down plantersville nettleton
18 tokens: two foot deep standing water develop street winthrop university campus
10 tokens: nws columbia relay report tree blow down tom hall st
10 tokens: medium report two tree blow down i40 old fort area

```

```
0 tokens:
10 tokens: few tree limb great 6 inch down hwy 18 roseland
13 tokens: awning blow off building lamar avenue multiple tree down near intersect
5 tokens: quarter size hail near rosemark
16 tokens: tin roof rip off house old memphis road near billings drive several larg
7 tokens: powerlines down walnut grove cherry lane road
```

Remove words with 2 or fewer characters, and words with 15 or greater characters.

```
cleanedDocuments = removeShortWords(cleanedDocuments,2);
cleanedDocuments = removeLongWords(cleanedDocuments,15);
cleanedDocuments(1:10)
```

```
ans =
  10×1 tokenizedDocument:

    5 tokens: large tree down plantersville nettleton
   18 tokens: two foot deep standing water develop street winthrop university campus
    9 tokens: nws columbia relay report tree blow down tom hall
   10 tokens: medium report two tree blow down i40 old fort area
    0 tokens:
    8 tokens: few tree limb great inch down hwy roseland
   13 tokens: awning blow off building lamar avenue multiple tree down near intersect
    5 tokens: quarter size hail near rosemark
   16 tokens: tin roof rip off house old memphis road near billings drive several larg
    7 tokens: powerlines down walnut grove cherry lane road
```

Create Bag-of-Words Model

Create a bag-of-words model.

```
cleanedBag = bagOfWords(cleanedDocuments)
```

```
cleanedBag =
  bagOfWords with properties:

    Counts: [36176×18469 double]
    Vocabulary: [1×18469 string]
    NumWords: 18469
    NumDocuments: 36176
```

Remove words that do not appear more than two times in the bag-of-words model.

```
cleanedBag = removeInfrequentWords(cleanedBag,2)
```

```
cleanedBag =
  bagOfWords with properties:
      Counts: [36176×6974 double]
      Vocabulary: [1×6974 string]
      NumWords: 6974
      NumDocuments: 36176
```

Some preprocessing steps such as `removeInfrequentWords` leaves empty documents in the bag-of-words model. To ensure that no empty documents remain in the bag-of-words model after preprocessing, use `removeEmptyDocuments` as the last step.

Remove empty documents from the bag-of-words model and the corresponding labels from labels.

```
[cleanedBag,idx] = removeEmptyDocuments(cleanedBag);
labels(idx) = [];
cleanedBag
```

```
cleanedBag =
  bagOfWords with properties:
      Counts: [28137×6974 double]
      Vocabulary: [1×6974 string]
      NumWords: 6974
      NumDocuments: 28137
```

Create a Preprocessing Function

It can be useful to create a function which performs preprocessing so you can prepare different collections of text data in the same way. For example, you can use a function so that you can preprocess new data using the same steps as the training data.

Create a function which tokenizes and preprocesses the text data so it can be used for analysis. The function `preprocessWeatherNarratives`, performs the following steps:

- 1 Tokenize the text using `tokenizedDocument`.
- 2 Lemmatize the words using `normalizeWords`.
- 3 Erase punctuation using `erasePunctuation`.

- 4 Remove a list of stop words (such as "and", "of", and "the") using `removeStopWords`.
- 5 Remove words with 2 or fewer characters using `removeShortWords`.
- 6 Remove words with 15 or more characters using `removeLongWords`.

Use the example preprocessing function `preprocessWeatherNarratives` to prepare the text data.

```
newText = "A tree is downed outside Apple Hill Drive, Natick";  
newDocuments = preprocessWeatherNarratives(newText)
```

```
newDocuments =  
  tokenizedDocument:  
  
  7 tokens: tree down outside apple hill drive natick
```

Compare with Raw Data

Compare the preprocessed data with the raw data.

```
rawDocuments = tokenizedDocument(textData);  
rawBag = bagOfWords(rawDocuments)
```

```
rawBag =  
  bagOfWords with properties:  
  
      Counts: [36176×23302 double]  
  Vocabulary: [1×23302 string]  
      NumWords: 23302  
  NumDocuments: 36176
```

Calculate the reduction in data.


```
numWordsCleaned = cleanedBag.NumWords;  
numWordsRaw = rawBag.NumWords;  
reduction = 1 - numWordsCleaned/numWordsRaw  
  
reduction = 0.7007
```

Compare the raw data and the cleaned data by visualizing the two bag-of-words models using word clouds.

```
figure  
subplot(1,2,1)
```



```
wordcloud(rawBag);
title("Raw Data")
subplot(1,2,2)
wordcloud(cleanedBag);
title("Cleaned Data")
```



Preprocessing Function

The function preprocessWeatherNarratives, performs the following steps in order:

- 1 Tokenize the text using tokenizedDocument.
- 2 Lemmatize the words using normalizeWords.
- 3 Erase punctuation using erasePunctuation.

- 4 Remove a list of stop words (such as "and", "of", and "the") using `removeStopWords`.
- 5 Remove words with 2 or fewer characters using `removeShortWords`.
- 6 Remove words with 15 or more characters using `removeLongWords`.

```
function documents = preprocessWeatherNarratives(textData)

% Tokenize the text.
documents = tokenizedDocument(textData);

% Lemmatize the words. To improve lemmatization, first use
% addPartOfSpeechDetails.
documents = addPartOfSpeechDetails(documents);
documents = normalizeWords(documents, 'Style', 'lemma');

% Erase punctuation.
documents = erasePunctuation(documents);

% Remove a list of stop words.
documents = removeStopWords(documents);

% Remove words with 2 or fewer characters, and words with 15 or more
% characters.
documents = removeShortWords(documents, 2);
documents = removeLongWords(documents, 15);

end
```

See Also

`addPartOfSpeechDetails` | `bagOfWords` | `erasePunctuation` | `normalizeWords` | `removeEmptyDocuments` | `removeInfrequentWords` | `removeLongWords` | `removeShortWords` | `removeStopWords` | `tokenizedDocument` | `wordcloud`

Related Examples

- “Extract Text Data from Files” on page 1-2
- “Create Simple Text Model for Classification” on page 2-2
- “Visualize Text Data Using Word Clouds” on page 3-2
- “Analyze Text Data Containing Emojis” on page 2-35
- “Analyze Text Data Using Topic Models” on page 2-18

- “Analyze Text Data Using Multiword Phrases” on page 2-9
- “Classify Text Data Using Deep Learning” on page 2-53
- “Train a Sentiment Classifier” on page 2-43

Parse HTML and Extract Text Content

This example shows how to parse HTML code and extract the text content from particular elements.

Parse HTML Code

Read HTML code from the URL `https://www.mathworks.com/help/textanalytics` using `webread`.

```
url = "https://www.mathworks.com/help/textanalytics";  
code = webread(url);
```

Parse the HTML code using `htmlTree`.

```
tree = htmlTree(code);
```

View the HTML element name of the tree.

```
tree.Name
```

```
ans =  
"HTML"
```

View the child elements of the tree. The children are subtrees of `tree`.

```
tree.Children
```

```
ans =  
  4×1 htmlTree:  
  
  " "  
  <HEAD><TITLE>Text Analytics Toolbox Documentation</TITLE><META charset="utf-8"/><META  
  " "  
  <BODY id="responsive_offcanvas"><!-- Mobile TopNav: Start --><DIV class="header vis
```

Extract Text from HTML Tree

To extract text directly from the HTML tree, use `extractHTMLText`.

```
str = extractHTMLText(tree)
```

```
str =  
  "Text Analytics Toolbox™ provides algorithms and visualizations for preprocessing,
```

Text Analytics Toolbox includes tools for processing raw text from sources such as

Using machine learning techniques such as LSA, LDA, and word embeddings, you can

Find HTML Elements

To find particular elements of an HTML tree, use `findElement`. Find all the hyperlinks in the HTML tree. In HTML, hyperlinks use the "A" tag.

```
selector = "A";
subtrees = findElement(tree,selector);
```

View the first few subtrees.

```
subtrees(1:20)
```

```
ans =
```

```
20×1 htmlTree:
```

```
<A class="svg_link navbar-brand" href="https://www.mathworks.com?s_tid=gn_logo"><IMG alt="MathWorks logo" data-bbox="194 500 212 518"/>
<A class="mwa-nav_login" href="https://www.mathworks.com/login?uri=http://www.mathworks.com" data-bbox="194 518 212 536">
<A href="https://www.mathworks.com/products.html?s_tid=gn_ps">Products</A>
<A href="https://www.mathworks.com/solutions.html?s_tid=gn_sol">Solutions</A>
<A href="https://www.mathworks.com/academia.html?s_tid=gn_acad">Academia</A>
<A href="https://www.mathworks.com/support.html?s_tid=gn_supp">Support</A>
<A href="https://www.mathworks.com/matlabcentral/?s_tid=gn_mlc">Community</A>
<A href="https://www.mathworks.com/company/events.html?s_tid=gn_ev">Events</A>
<A href="https://www.mathworks.com/company/aboutus/contact_us.html?s_tid=gn_cntus">
<A href="https://www.mathworks.com/store?s_cid=store_top_nav&s_tid=gn_store">Home</A>
<A href="https://www.mathworks.com/company/aboutus/contact_us.html?s_tid=gn_cntus">
<A href="https://www.mathworks.com/store?s_cid=store_top_nav&s_tid=gn_store">Home</A>
<A class="mwa-nav_login" href="https://www.mathworks.com/login?uri=http://www.mathworks.com" data-bbox="194 700 212 718">
<A class="svg_link pull-left" href="https://www.mathworks.com?s_tid=gn_logo"><IMG alt="MathWorks logo" data-bbox="194 718 212 736"/>
<A href="https://www.mathworks.com/products.html?s_tid=gn_ps">Products</A>
<A href="https://www.mathworks.com/solutions.html?s_tid=gn_sol">Solutions</A>
<A href="https://www.mathworks.com/academia.html?s_tid=gn_acad">Academia</A>
<A href="https://www.mathworks.com/support.html?s_tid=gn_supp">Support</A>
<A href="https://www.mathworks.com/matlabcentral/?s_tid=gn_mlc">Community</A>
<A href="https://www.mathworks.com/company/events.html?s_tid=gn_ev">Events</A>
```

Create a word cloud from the text of the hyperlinks.

```
str = extractHTMLText(subtrees);  
figure  
wordcloud(str);  
title("Hyperlinks")
```



Get HTML Attributes

Get the class attributes from the paragraph elements in the HTML tree.

```
subtrees = findElement(tree, 'p');  
attr = "class";  
str = getAttribute(subtrees, attr)  
  
str = 21x1 string array  
    <missing>
```

```
<missing>  
"add_margin_5"  
<missing>  
<missing>  
<missing>  
<missing>  
<missing>  
"category_desc"  
"category_desc"  
"category_desc"  
"category_desc"  
<missing>  
<missing>  
<missing>  
"text-center"  
<missing>  
<missing>  
<missing>  
"copyright"  
<missing>
```

Create a word cloud from the text contained in paragraph elements with class "category_desc".

```
subtrees = findElement(tree, 'p.category_desc');  
str = extractHTMLText(subtrees);  
figure  
wordcloud(str);
```



See Also

`extractHTMLText` | `findElement` | `getAttribute` | `htmlTree` | `tokenizedDocument`

Related Examples

- “Prepare Text Data for Analysis” on page 1-12
- “Create Simple Text Model for Classification” on page 2-2
- “Visualize Text Data Using Word Clouds” on page 3-2
- “Analyze Text Data Using Topic Models” on page 2-18

- “Analyze Text Data Using Multiword Phrases” on page 2-9
- “Classify Text Data Using Deep Learning” on page 2-53
- “Train a Sentiment Classifier” on page 2-43

Correct Spelling Using Edit Distance Searchers

This example shows how to correct spelling using edit distance searchers and a vocabulary of known words.

If you have misspelled words in a collection of text, then you can use edit distance searchers to find the nearest correctly spelled words to a given vocabulary. To correct the spelling of misspelled words in documents, replace them with the nearest neighbors in the vocabulary.

Lemmatization with `normalizeWords` and `word2vec` requires correctly spelled words to work. Use edit distance searchers to find the nearest correctly spelled word to misspelled words according to an edit distance. For example, the number of adjacent grapheme swaps and grapheme insertions, deletions, and substitutions.

Load Data

Create a vocabulary of known words. Download the Spell Checking Oriented Word Lists (SCOWL) from <https://sourceforge.net/projects/wordlist/>. Import the words from the downloaded data using the supporting function `scowlWordList`.

```
folderName = "scowl-2018.04.16";
maxSize = 60;
vocabulary = scowlWordList(folderName, 'english', maxSize);
```

View the number of words in the vocabulary.

```
numWords = numel(vocabulary)

numWords = 98129
```

Create Simple Spelling Corrector

Using the imported vocabulary, create an edit distance searcher with a maximum distance of 2. For better results, allow for adjacent grapheme swaps by setting the `'SwapCost'` option to 1. For large vocabularies, this can take a few minutes.

```
maxDist = 2;
eds = editDistanceSearcher(vocabulary, maxDist, 'SwapCost', 1);
```

This edit distance searcher is case sensitive which means that changing the case of characters contributes to the edit distance. For example, the searcher can find the

neighbor "testing" for the word "tseting" because it has edit distance 1 (one swap), but not of the word "TSeTiNG" because it has edit distance 6.

Correct Spelling

Correct the spelling of misspelled words in an array of tokenized documents by selecting the misspelled words and finding the nearest neighbors in the edit distance searcher.

Create a tokenized document object containing typos and spelling mistakes.

```
str = "An exmaple dccoument with typos and averyunusualword.";
document = tokenizedDocument(str)
```

```
document =
    tokenizedDocument:
```

```
    8 tokens: An exmaple dccoument with typos and averyunusualword .
```

Convert the documents to a string array of words using the string function.

```
words = string(document)
```

```
words = 1×8 string array
    "An"    "exmaple"    "dccoument"    "with"    "typos"    "and"    "averyunusualword"
```

Find the words that need correction. To ignore words that are correctly spelled, find the indices of the words already in the vocabulary. To ignore punctuation and complex tokens such as email addresses, find the indices of the words which do not have the token types "letters" or "other". Get the token details from the document using the `tokenDetails` function.

```
tdetails = tokenDetails(document);
idxVocabularyWords = ismember(tdetails.Token, eds.Vocabulary);
```

```
idxComplexTokens = ...
    ~tdetails.Type ~= "letters" & ...
    ~tdetails.Type ~= "other";
```

```
idxWordsToCheck = ...
    ~idxVocabularyWords & ...
    ~idxComplexTokens
```

```
idxWordsToCheck = 8×1 logical array
```

```
1
1
1
0
0
0
1
0
```

Find the numeric indices of the words and view the corresponding words.

```
idxWordsToCheck = find(idxWordsToCheck)
```

```
idxWordsToCheck = 4×1
```

```
1
2
3
7
```

```
wordsToCheck = words(idxWordsToCheck)
```

```
wordsToCheck = 1×4 string array
    "An"      "exmaple"    "dccoument"  "averyunusualword"
```

Notice that the word "An" is flagged as a word to check. This word is flagged because the vocabulary does not contain the word "An" with an uppercase "A". A later section in the example shows how to create a case insensitive spelling corrector.

Find the nearest words and their distances using the `knnsearch` function with the edit distance searcher.

```
[idxNearestWords,d] = knnsearch(eds,wordsToCheck)
```

```
idxNearestWords = 4×1
```

```
165
1353
1152
NaN
```

```
d = 4×1
    1
    1
    2
    Inf
```

If any of the words are not found in the searcher, then the function returns index NaN with distance Inf. The word "averyunusualword" does not have a match within edit distance 2, so the function returns the index NaN for that word.

Find the indices of the words with positive finite edit distances.

```
idxMatches = ~isnan(idxNearestWords)
idxMatches = 4×1 logical array
    1
    1
    1
    0
```

Get the indices of the words with matches in the searcher and view the corresponding corrected words in the vocabulary.

```
idxCorrectedWords = idxNearestWords(idxMatches)
idxCorrectedWords = 3×1
    165
    1353
    1152
```

```
correctedWords = eds.Vocabulary(idxCorrectedWords)
correctedWords = 1×3 string array
    "an"      "example"    "document"
```

Replace the misspelled words that have matches with the corrected words.

```
idxToCorrect = idxWordsToCheck(idxMatches);
words(idxToCorrect) = correctedWords
```

```
words = 1x8 string array
      "an"      "example"      "document"      "with"      "typos"      "and"      "averyunusualword"
```

To create a tokenized document of these words, use the `tokenizedDocument` function and set `'TokenizedMethod'` to `'none'`.

```
document = tokenizedDocument(words, 'TokenizeMethod', 'none')

document =
    tokenizedDocument:

        8 tokens: an example document with typos and averyunusualword .
```

The next section shows how to correct the spelling of multiple documents at once by creating a custom spelling correction function and using `docfun`.

Create Spelling Correction Function

To correct the spelling in multiple documents at once, create a custom function using the code from the previous section and use this function with the `docfun` function.

Create a function that takes an edit distance searcher, a string array of words, and the corresponding table of token details as inputs and outputs the corrected words. The `correctSpelling` function, listed at the end of the example, corrects the spelling in a string array of words using the corresponding token details and an edit distance searcher.

To use this function with the `docfun` function, create a function handle that takes a string array of words and the corresponding table of token details as the inputs.

```
func = @(words, tdetails) correctSpelling(eds, words, tdetails);
```

Correct the spelling of an array of tokenized documents using `docfun` with the function handle `func`.

```
str = [
    "Here is some really badly writen texct."
    "Some moree mitsakes here too."];
documents = tokenizedDocument(str);
documentsCorrected = docfun(func, documents)

documentsCorrected =
    2x1 tokenizedDocument:
```

```

8 tokens: here is some really badly written text .
6 tokens: come more mistakes here too .

```

Note that uppercase characters can get corrected to different lowercase characters. For example, the word "Some" can get corrected to "come". If multiple words in the edit distance searcher vocabulary have the same edit distance to the input, then the function outputs the first result it found. For example, the words "come" and "some" both have edit distance 1 from the word "Some".

The next section shows how to create a spelling corrector that is case insensitive.

Create Case Insensitive Spelling Corrector

To prevent differences in case clashing with other substitutions, create an edit distance searcher with the vocabulary in lower case and convert the documents to lowercase before using the edit distance searcher.

Convert the vocabulary to lowercase. This operation can introduce duplicate words, remove them by taking the unique values only.

```

vocabularyLower = lower(vocabulary);
vocabularyLower = unique(vocabularyLower);

```

Create an edit distance searcher using the lowercase vocabulary using the same options as before. This can take a few minutes to run.

```

maxDist = 2;
eds = editDistanceSearcher(vocabularyLower,maxDist,'SwapCost',1);

```

Use the edit distance searcher to correct the spelling of the words in tokenized document. To use the case insensitive spelling corrector, convert the documents to lowercase.

```

documentsLower = lower(documents);

```

Correct the spelling using the new edit distance searcher using same steps as before.

```

func = @(words,tetails) correctSpelling(eds,words,tetails);
documentsCorrected = docfun(func,documentsLower)

```

```

documentsCorrected =
    2x1 tokenizedDocument:

```

```
8 tokens: here is some really badly written text .
6 tokens: some more mistakes here too .
```

Here, the word "Some" in the original text is converted to "some" before being input to the spelling corrector. The corresponding word "some" is unaffected by the searcher as the word some occurs in the vocabulary.

Spelling Correction Function

The `correctSpelling` function corrects the spelling in a string array of words using the corresponding token details and an edit distance searcher. You can use this function with `docfun` to correct the spelling of multiple documents at once.

```
function words = correctSpelling(eds,words,tdetails)

% Get indices of misspelled words ignoring complex tokens.
idxVocabularyWords = ismember(tdetails.Token,eds.Vocabulary);

idxComplexTokens = ...
    tdetails.Type ~= "letters" & ...
    tdetails.Type ~= "other";

idxWordsToCheck = ...
    ~idxVocabularyWords & ...
    ~idxComplexTokens;

% Convert to numeric indices.
idxWordsToCheck = find(idxWordsToCheck);

% Find nearest words.
wordsToCheck = words(idxWordsToCheck);
idxNearestWords = knnsearch(eds,wordsToCheck);

% Find words with matches.
idxMatches = ~isnan(idxNearestWords);

% Get corrected words.
idxCorrectedWords = idxNearestWords(idxMatches);
correctedWords = eds.Vocabulary(idxCorrectedWords);

% Correct words.
idxToCorrect = idxWordsToCheck(idxMatches);
words(idxToCorrect) = correctedWords;
```


end

See Also

`docfun` | `editDistance` | `editDistanceSearcher` | `knnsearch` | `tokenDetails` | `tokenizedDocument`

More About

- “Prepare Text Data for Analysis” on page 1-12
- “Create Simple Text Model for Classification” on page 2-2
- “Visualize Text Data Using Word Clouds” on page 3-2
- “Analyze Text Data Using Topic Models” on page 2-18
- “Analyze Text Data Using Multiword Phrases” on page 2-9
- “Classify Text Data Using Deep Learning” on page 2-53
- “Train a Sentiment Classifier” on page 2-43

Modeling and Prediction

- “Create Simple Text Model for Classification” on page 2-2
- “Analyze Text Data Using Multiword Phrases” on page 2-9
- “Analyze Text Data Using Topic Models” on page 2-18
- “Choose Number of Topics for LDA Model” on page 2-25
- “Compare LDA Solvers” on page 2-30
- “Analyze Text Data Containing Emojis” on page 2-35
- “Train a Sentiment Classifier” on page 2-43
- “Classify Text Data Using Deep Learning” on page 2-53
- “Classify Text Data Using Convolutional Neural Network” on page 2-76
- “Classify Out-of-Memory Text Data Using Deep Learning” on page 2-87
- “Pride and Prejudice and MATLAB” on page 2-94
- “Word-By-Word Text Generation Using Deep Learning” on page 2-101
- “Classify Out-of-Memory Text Data Using Custom Mini-Batch Datastore” on page 2-108

Create Simple Text Model for Classification

This example shows how to train a simple text classifier on word frequency counts using a bag-of-words model.

You can create a simple classification model which uses word frequency counts as predictors. This example trains a simple classification model to predict the event type of weather reports using text descriptions.

To reproduce the results of this example, set `rng` to `'default'`.

```
rng('default')
```

Load and Extract Text Data

Load the example data. The file `weatherReports.csv` contains weather reports, including a text description and categorical labels for each event.

```
filename = "weatherReports.csv";
data = readtable(filename, 'TextType', 'string');
head(data)
```

```
ans=8x16 table
           Time          event_id          state          event_type          da
-----
22-Jul-2016 16:10:00  6.4433e+05  "MISSISSIPPI"  "Thunderstorm Wind"
15-Jul-2016 17:15:00  6.5182e+05  "SOUTH CAROLINA"  "Heavy Rain"
15-Jul-2016 17:25:00  6.5183e+05  "SOUTH CAROLINA"  "Thunderstorm Wind"
16-Jul-2016 12:46:00  6.5183e+05  "NORTH CAROLINA"  "Thunderstorm Wind"
15-Jul-2016 14:28:00  6.4332e+05  "MISSOURI"        "Hail"
15-Jul-2016 16:31:00  6.4332e+05  "ARKANSAS"        "Thunderstorm Wind"
15-Jul-2016 16:03:00  6.4343e+05  "TENNESSEE"       "Thunderstorm Wind"
15-Jul-2016 17:27:00  6.4344e+05  "TENNESSEE"       "Hail"
```

Remove rows with empty reports.


```
idx = strlength(data.event_narrative) == 0;
data(idx,:) = [];
```

Convert the labels in the `event_type` column of the table to categorical and view the distribution of the classes in the data using a histogram.

```

data.event_type = categorical(data.event_type);
figure
h = histogram(data.event_type);
xlabel("Class")
ylabel("Frequency")
title("Class Distribution")

```



The classes of the data are imbalanced, with several classes containing few observations. To ensure that you can partition the data so that the partitions contain observations for each class, remove any classes which appear fewer than ten times.

Get the frequency counts of the classes and their names from the histogram.

```
classCounts = h.BinCounts;  
classNames = h.Categories;
```

Find the classes containing fewer than ten observations and remove these infrequent classes from the data.

```
idxLowCounts = classCounts < 10;  
infrequentClasses = classNames(idxLowCounts);  
idxInfrequent = ismember(data.event_type, infrequentClasses);  
data(idxInfrequent, :) = [];
```

Partition the data into a training partition and a held-out test set. Specify the holdout percentage to be 10%.

```
cvp = cvpartition(data.event_type, 'Holdout', 0.1);  
dataTrain = data(cvp.training, :);  
dataTest = data(cvp.test, :);
```

Extract the text data and labels from the tables.

```
textDataTrain = dataTrain.event_narrative;  
textDataTest = dataTest.event_narrative;  
YTrain = dataTrain.event_type;  
YTest = dataTest.event_type;
```

Prepare Text Data for Analysis

Create a function which tokenizes and preprocesses the text data so it can be used for analysis. The function `preprocessWeatherNarratives`, performs the following steps in order:

- 1 Tokenize the text using `tokenizedDocument`.
- 2 Lemmatize the words using `normalizeWords`.
- 3 Erase punctuation using `erasePunctuation`.
- 4 Remove a list of stop words (such as "and", "of", and "the") using `removeStopWords`.
- 5 Remove words with 2 or fewer characters using `removeShortWords`.
- 6 Remove words with 15 or more characters using `removeLongWords`.

Use the example preprocessing function `preprocessWeatherNarratives` to prepare the text data.

```
documents = preprocessWeatherNarratives(textDataTrain);  
documents(1:5)
```

```
ans =
  5x1 tokenizedDocument:

    5 tokens: large tree down plantersville nettleton
   18 tokens: two foot deep standing water develop street winthrop university campus :
    9 tokens: nws columbia relay report tree blow down tom hall
   10 tokens: medium report two tree blow down i40 old fort area
    8 tokens: few tree limb great inch down hwy roseland
```

Create a bag-of-words model from the tokenized documents.

```
bag = bagOfWords(documents)

bag =
  bagOfWords with properties:

    Counts: [25316x17524 double]
  Vocabulary: [1x17524 string]
    NumWords: 17524
  NumDocuments: 25316
```

Remove words from the bag-of-words model that do not appear more than two times in total. Remove any documents containing no words from the bag-of-words model, and remove the corresponding entries in labels.

```
bag = removeInfrequentWords(bag,2);
[bag,idx] = removeEmptyDocuments(bag);
YTrain(idx) = [];
bag

bag =
  bagOfWords with properties:

    Counts: [25315x6534 double]
  Vocabulary: [1x6534 string]
    NumWords: 6534
  NumDocuments: 25315
```

Train Supervised Classifier

Train a supervised classification model using the word frequency counts from the bag-of-words model and the labels.

Train a multiclass linear classification model using `fitcecoc`. Specify the `Counts` property of the bag-of-words model to be the predictors, and the event type labels to be the response. Specify the learners to be linear. These learners support sparse data input.

```
XTrain = bag.Counts;
mdl = fitcecoc(XTrain,YTrain,'Learners','linear')

mdl =
    classreg.learning.classif.CompactClassificationECOC
        ResponseName: 'Y'
        ClassNames: [1×39 categorical]
        ScoreTransform: 'none'
        BinaryLearners: {741×1 cell}
        CodingMatrix: [39×741 double]
```

Properties, Methods

For a better fit, you can try specifying different parameters of the linear learners. For more information on linear classification learner templates, see `templateLinear`.

Test Classifier

Predict the labels of the test data using the trained model and calculate the classification accuracy. The classification accuracy is the proportion of the labels that the model predicts correctly.

Preprocess the test data using the same preprocessing steps as the training data. Encode the resulting test documents as a matrix of word frequency counts according to the bag-of-words model.

```
documentsTest = preprocessWeatherNarratives(textDataTest);
XTest = encode(bag,documentsTest);
```

Predict the labels of the test data using the trained model and calculate the classification accuracy.

```
YPred = predict(mdl,XTest);
acc = sum(YPred == YTest)/numel(YTest)

acc = 0.8808
```


Predict Using New Data

Classify the event type of new weather reports. Create a string array containing the new weather reports.

```
str = [ ...
    "A large tree is downed and blocking traffic outside Apple Hill."
    "Damage to many car windshields in parking lot."
    "Lots of water damage to computer equipment inside the office."];
documentsNew = preprocessWeatherNarratives(str);
XNew = encode(bag,documentsNew);
labelsNew = predict mdl,XNew

labelsNew = 3×1 categorical array
    Thunderstorm Wind
    Thunderstorm Wind
    Flash Flood
```

Example Preprocessing Function

The function `preprocessWeatherNarratives`, performs the following steps in order:

- 1 Tokenize the text using `tokenizedDocument`.
- 2 Lemmatize the words using `normalizeWords`.
- 3 Erase punctuation using `erasePunctuation`.
- 4 Remove a list of stop words (such as "and", "of", and "the") using `removeStopWords`.
- 5 Remove words with 2 or fewer characters using `removeShortWords`.
- 6 Remove words with 15 or more characters using `removeLongWords`.

```
function documents = preprocessWeatherNarratives(textData)

% Tokenize the text.
documents = tokenizedDocument(textData);

% Lemmatize the words. To improve lemmatization, first use
% addPartOfSpeechDetails.
documents = addPartOfSpeechDetails(documents);
documents = normalizeWords(documents,'Style','lemma');

% Erase punctuation.
documents = erasePunctuation(documents);
```

```
% Remove a list of stop words.
documents = removeStopWords(documents);

% Remove words with 2 or fewer characters, and words with 15 or more
% characters.
documents = removeShortWords(documents,2);
documents = removeLongWords(documents,15);

end
```

See Also

[addPartOfSpeechDetails](#) | [bagOfWords](#) | [encode](#) | [erasePunctuation](#) | [normalizeWords](#) | [removeLongWords](#) | [removeShortWords](#) | [removeStopWords](#) | [tokenizedDocument](#) | [wordcloud](#)

Related Examples

- “Analyze Text Data Using Topic Models” on page 2-18
- “Analyze Text Data Using Multiword Phrases” on page 2-9
- “Analyze Text Data Containing Emojis” on page 2-35
- “Train a Sentiment Classifier” on page 2-43
- “Classify Text Data Using Deep Learning” on page 2-53
- “Generate Text Using Deep Learning” (Deep Learning Toolbox)

Analyze Text Data Using Multiword Phrases

This example shows how to analyze text using n-gram frequency counts.

N-Grams

An n-gram is a tuple of n consecutive words. For example, a bigram (the case when $n = 2$) is a pair of consecutive words such as "heavy rainfall". A unigram (the case when $n = 1$) is a single word. A bag-of-n-grams model records the number of times that different n-grams appear in document collections.

Using a bag-of-n-grams model, you can retain more information on word ordering in the original text data. For example, a bag-of-n-grams model is better suited for capturing short phrases which appear in the text, such as "heavy rainfall" and "thunderstorm winds".

To create a bag-of-n-grams model, use `bagOfNgrams`. You can input `bagOfNgrams` objects into other Text Analytics Toolbox functions such as `wordcloud` and `fitlda`.

Load and Extract Text Data

To reproduce the results of this example, set `rng` to 'default'.

```
rng('default')
```

Load the example data. The file `weatherReports.csv` contains weather reports, including a text description and categorical labels for each event. Remove the rows with empty reports.

```
filename = "weatherReports.csv";
data = readtable(filename, 'TextType', 'String');
idx = strlength(data.event_narrative) == 0;
data(idx,:) = [];
```

Extract the text data from the table and view the first few reports.

```
textData = data.event_narrative;
textData(1:5)
```

```
ans = 5x1 string array
    "Large tree down between Plantersville and Nettleton."
    "One to two feet of deep standing water developed on a street on the Winthrop Univer
    "NWS Columbia relayed a report of trees blown down along Tom Hall St."
```

```
"Media reported two trees blown down along I-40 in the Old Fort area."  
"A few tree limbs greater than 6 inches down on HWY 18 in Roseland."
```

Prepare Text Data for Analysis

Create a function which tokenizes and preprocesses the text data so it can be used for analysis. The function `preprocessWeatherNarratives` listed at the end of the example, performs the following steps:

- 1 Convert the text data to lowercase using `lower`.
- 2 Tokenize the text using `tokenizedDocument`.
- 3 Erase punctuation using `erasePunctuation`.
- 4 Remove a list of stop words (such as "and", "of", and "the") using `removeStopWords`.
- 5 Remove words with 2 or fewer characters using `removeShortWords`.
- 6 Remove words with 15 or more characters using `removeLongWords`.
- 7 Lemmatize the words using `normalizeWords`.

Use the example preprocessing function `preprocessWeatherNarratives` to prepare the text data.

```
documents = preprocessWeatherNarratives(textData);  
documents(1:5)
```

```
ans =  
  5×1 tokenizedDocument:  
  
  (1,1)  5 tokens: large tree down plantersville nettleton  
  (2,1) 18 tokens: two foot deep standing water develop street winthrop unive...  
  (3,1)  9 tokens: nws columbia relayed report tree blow down tom hall  
  (4,1) 10 tokens: medium report two tree blow down i40 old fort area  
  (5,1)  8 tokens: few tree limb great inches down hwy roseland
```

Create Word Cloud of Bigrams

Create a word cloud of bigrams by first creating a bag-of-n-grams model using `bagOfNgrams`, and then inputting the model to `wordcloud`.

To count the n-grams of length 2 (bigrams), use `bagOfNgrams` with the default options.


```
bag = bagOfNgrams(documents)
```

```
bag =  
  bagOfNgrams with properties:  
      Counts: [28138×117043 double]  
      Vocabulary: [1×18409 string]  
      Ngrams: [117043×2 string]  
      NgramLengths: 2  
      NumNgrams: 117043  
      NumDocuments: 28138
```

Visualize the bag-of-n-grams model using a word cloud.

```
figure  
wordcloud(bag);  
title("Weather Reports: Preprocessed Bigrams")
```

Weather Reports: Preprocessed Bigrams



Fit Topic Model to Bag-of-N-Grams

A Latent Dirichlet Allocation (LDA) model is a topic model which discovers underlying topics in a collection of documents and infers the word probabilities in topics.

Create an LDA topic model with 10 topics using `fitlda`. The function fits an LDA model by treating the n-grams as single words.

```
mdl = fitlda(bag,10);
```

Initial topic assignments sampled in 0.741989 seconds.


```
=====
```

Iteration	Time per iteration	Relative change in	Training perplexity	Topic concentration	Topic concentration
-----------	--------------------	--------------------	---------------------	---------------------	---------------------

	(seconds)	log(L)			iterations
0	2.81		2.043e+04	2.500	0
1	3.62	6.8345e-02	1.083e+04	2.500	0
2	3.54	1.9129e-03	1.064e+04	2.500	0
3	3.79	2.4671e-04	1.061e+04	2.500	0
4	3.81	8.5912e-05	1.060e+04	2.500	0

Visualize the first four topics as word clouds.

```
figure
for i = 1:4
    subplot(2,2,i)
    wordcloud mdl,i;
    title("LDA Topic " + i)
end
```



The word clouds highlight commonly co-occurring bigrams in the LDA topics. The function plots the bigrams with sizes according to their probabilities for the specified LDA topics.

Analyze Text Using Longer Phrases

To analyze text using longer phrases, specify the 'NGramLengths' option in `bagOfNgrams` to be a larger value.

When working with longer phrases, it can be useful to keep stop words in the model. For example, to detect the phrase "is not happy", keep the stop words "is" and "not" in the model.

Preprocess the text. Erase the punctuation using `erasePunctuation`, and tokenize using `tokenizedDocument`.


```
cleanTextData = erasePunctuation(textData);
documents = tokenizedDocument(cleanTextData);
```


To count the n-grams of length 3 (trigrams), use `bagOfNgrams` and specify 'NGramLengths' to be 3.

```
bag = bagOfNgrams(documents, 'NGramLengths', 3);
```

Visualize the bag-of-n-grams model using a word cloud. The word cloud of trigrams better shows the context of the individual words.

```
figure
wordcloud(bag);
title("Weather Reports: Trigrams")
```

Weather Reports: Trigrams



View the top 10 trigrams and their frequency counts using `topkngrams`.

```
tbl = topkngrams(bag,10)
```

```
tbl=10x3 table
```

Ngram			Count	NgramLength
"inches"	"of"	"snow"	2075	3
"across"	"the"	"county"	1318	3
"were"	"blown"	"down"	1189	3
"wind"	"gust"	"of"	934	3
"A"	"tree"	"was"	860	3
"the"	"intersection"	"of"	812	3
"inches"	"of"	"rain"	739	3
"hail"	"was"	"reported"	648	3
"was"	"blown"	"down"	638	3
"and"	"power"	"lines"	631	3

Example Preprocessing Function

The function `preprocessWeatherNarratives` performs the following steps in order:

- 1 Convert the text data to lowercase using `lower`.
- 2 Tokenize the text using `tokenizedDocument`.
- 3 Erase punctuation using `erasePunctuation`.
- 4 Remove a list of stop words (such as "and", "of", and "the") using `removeStopWords`.
- 5 Remove words with 2 or fewer characters using `removeShortWords`.
- 6 Remove words with 15 or more characters using `removeLongWords`.
- 7 Lemmatize the words using `normalizeWords`.

```
function [documents] = preprocessWeatherNarratives(textData)
```

```
% Convert the text data to lowercase.
```

```
cleanTextData = lower(textData);
```

```
% Tokenize the text.
```

```
documents = tokenizedDocument(cleanTextData);
```

```
% Erase punctuation.
```

```
documents = erasePunctuation(documents);
```

```
% Remove a list of stop words.
documents = removeStopWords(documents);

% Remove words with 2 or fewer characters, and words with 15 or greater
% characters.
documents = removeShortWords(documents,2);
documents = removeLongWords(documents,15);

% Lemmatize the words.
documents = addPartOfSpeechDetails(documents);
documents = normalizeWords(documents,'Style','lemma');
end
```

See Also

[addPartOfSpeechDetails](#) | [bagOfNgrams](#) | [bagOfWords](#) | [erasePunctuation](#) | [fitlda](#) | [ldaModel](#) | [normalizeWords](#) | [removeLongWords](#) | [removeShortWords](#) | [removeStopWords](#) | [tokenizedDocument](#) | [topkngrams](#) | [wordcloud](#)

Related Examples

- “Create Simple Text Model for Classification” on page 2-2
- “Analyze Text Data Containing Emojis” on page 2-35
- “Analyze Text Data Using Topic Models” on page 2-18
- “Train a Sentiment Classifier” on page 2-43
- “Classify Text Data Using Deep Learning” on page 2-53
- “Generate Text Using Deep Learning” (Deep Learning Toolbox)

Analyze Text Data Using Topic Models

This example shows how to use the Latent Dirichlet Allocation (LDA) topic model to analyze text data.

A Latent Dirichlet Allocation (LDA) model is a topic model which discovers underlying topics in a collection of documents and infers the word probabilities in topics.

To reproduce the results of this example, set `rng` to `'default'`.

```
rng('default')
```

Load and Extract Text Data

Load the example data. The file `weatherReports.csv` contains weather reports, including a text description and categorical labels for each event.

```
data = readtable("weatherReports.csv", 'TextType', 'string');
head(data)
```

```
ans=8x16 table
      Time          event_id          state          event_type          da
-----
22-Jul-2016 16:10:00  6.4433e+05  "MISSISSIPPI"  "Thunderstorm Wind"
15-Jul-2016 17:15:00  6.5182e+05  "SOUTH CAROLINA"  "Heavy Rain"
15-Jul-2016 17:25:00  6.5183e+05  "SOUTH CAROLINA"  "Thunderstorm Wind"
16-Jul-2016 12:46:00  6.5183e+05  "NORTH CAROLINA"  "Thunderstorm Wind"
15-Jul-2016 14:28:00  6.4332e+05  "MISSOURI"  "Hail"
15-Jul-2016 16:31:00  6.4332e+05  "ARKANSAS"  "Thunderstorm Wind"
15-Jul-2016 16:03:00  6.4343e+05  "TENNESSEE"  "Thunderstorm Wind"
15-Jul-2016 17:27:00  6.4344e+05  "TENNESSEE"  "Hail"
```

Extract the text data from the field `event_narrative`.

```
textData = data.event_narrative;
textData(1:10)
```

```
ans = 10x1 string array
    "Large tree down between Plantersville and Nettleton."
    "One to two feet of deep standing water developed on a street on the Winthrop Univ
    "NWS Columbia relayed a report of trees blown down along Tom Hall St."
    "Media reported two trees blown down along I-40 in the Old Fort area."
```

```

""
"A few tree limbs greater than 6 inches down on HWY 18 in Roseland."
"Awning blown off a building on Lamar Avenue. Multiple trees down near the intersece
"Quarter size hail near Rosemark."
"Tin roof ripped off house on Old Memphis Road near Billings Drive. Several large t
"Powerlines down at Walnut Grove and Cherry Lane roads."

```

Prepare Text Data for Analysis

Create a function which tokenizes and preprocesses the text data so it can be used for analysis. The function `preprocessText`, listed at the end of the example, performs the following steps in order:

- 1 Tokenize the text using `tokenizedDocument`.
- 2 Lemmatize the words using `normalizeWords`.
- 3 Erase punctuation using `erasePunctuation`.
- 4 Remove a list of stop words (such as "and", "of", and "the") using `removeStopWords`.
- 5 Remove words with 2 or fewer characters using `removeShortWords`.
- 6 Remove words with 15 or more characters using `removeLongWords`.

Use the preprocessing function `preprocessText` to prepare the text data.

```

documents = preprocessText(textData);
documents(1:5)

ans =
    5×1 tokenizedDocument:

    5 tokens: large tree down plantersville nettleton
   18 tokens: two foot deep standing water develop street winthrop university campus
    9 tokens: nws columbia relay report tree blow down tom hall
   10 tokens: medium report two tree blow down i40 old fort area
    0 tokens:

```

Create a bag-of-words model from the tokenized documents.

```

bag = bagOfWords(documents)

bag =
    bagOfWords with properties:

```

```
Counts: [36176×18469 double]
Vocabulary: [1×18469 string]
NumWords: 18469
NumDocuments: 36176
```

Remove words from the bag-of-words model that have do not appear more than two times in total. Remove any documents containing no words from the bag-of-words model.

```
bag = removeInfrequentWords(bag,2);
bag = removeEmptyDocuments(bag)
```

```
bag =
  bagOfWords with properties:

    Counts: [28137×6974 double]
    Vocabulary: [1×6974 string]
    NumWords: 6974
    NumDocuments: 28137
```

Fit LDA Model

Fit an LDA model with 7 topics. For an example showing how to choose the number of topics, see “Choose Number of Topics for LDA Model” on page 2-25. To suppress verbose output, set 'Verbose' to 0.

```
numTopics = 7;
mdl = fitlda(bag,numTopics,'Verbose',0);
```

If you have a large dataset, then the stochastic approximate variational Bayes solver is usually better suited as it can fit a good model in fewer passes of the data. The default solver for `fitlda` (collapsed Gibbs sampling) can be more accurate at the cost of taking longer to run. To use stochastic approximate variational Bayes, set the 'Solver' option to 'savb'. For an example showing how to compare LDA solvers, see “Compare LDA Solvers” on page 2-30.

Visualize Topics Using Word Clouds


You can use word clouds to view the words with the highest probabilities in each topic. Visualize the first four topics using word clouds.

```
figure;
for topicIdx = 1:4
```

```

subplot(2,2,topicIdx)
wordcloud mdl, topicIdx);
title("Topic " + topicIdx)
end

```



View Mixtures of Topics in Documents

Use `transform` to transform the documents into vectors of topic probabilities.

```

newDocument = tokenizedDocument("A tree is downed outside Apple Hill Drive, Natick");
topicMixture = transform(mdl,newDocument);


```

```

figure
bar(topicMixture)

```

```
xlabel("Topic Index")
ylabel("Probability")
title("Document Topic Probabilities")
```




Visualize multiple topic mixtures using stacked bar charts. Visualize the topic mixtures of the first 5 input documents.

```
figure
topicMixtures = transform mdl, documents(1:5);
barh(topicMixtures(1:5,:), 'stacked')
xlim([0 1])
title("Topic Mixtures")
xlabel("Topic Probability")
```



```
ylabel("Document")
legend("Topic " + string(1:numTopics), 'Location', 'northeastoutside')
```



Preprocessing Function

The function `preprocessText`, performs the following steps in order:

- 1 Tokenize the text using `tokenizedDocument`.
- 2 Lemmatize the words using `normalizeWords`.
- 3 Erase punctuation using `erasePunctuation`.
- 4 Remove a list of stop words (such as "and", "of", and "the") using `removeStopWords`.
- 5 Remove words with 2 or fewer characters using `removeShortWords`.

6 Remove words with 15 or more characters using `removeLongWords`.

```
function documents = preprocessText(textData)

% Tokenize the text.
documents = tokenizedDocument(textData);

% Lemmatize the words.
documents = addPartOfSpeechDetails(documents);
documents = normalizeWords(documents, 'Style', 'lemma');

% Erase punctuation.
documents = erasePunctuation(documents);

% Remove a list of stop words.
documents = removeStopWords(documents);

% Remove words with 2 or fewer characters, and words with 15 or greater
% characters.
documents = removeShortWords(documents, 2);
documents = removeLongWords(documents, 15);

end
```

See Also

`addPartOfSpeechDetails` | `bagOfWords` | `fitlda` | `ldaModel` |
`removeEmptyDocuments` | `removeInfrequentWords` | `removeStopWords` |
`tokenizedDocument` | `transform` | `wordcloud`

Related Examples

- “Create Simple Text Model for Classification” on page 2-2
- “Analyze Text Data Containing Emojis” on page 2-35
- “Analyze Text Data Using Multiword Phrases” on page 2-9
- “Train a Sentiment Classifier” on page 2-43
- “Classify Text Data Using Deep Learning” on page 2-53
- “Generate Text Using Deep Learning” (Deep Learning Toolbox)

Choose Number of Topics for LDA Model

This example shows how to decide on a suitable number of topics for a latent Dirichlet allocation (LDA) model.

To decide on a suitable number of topics, you can compare the goodness-of-fit of LDA models fit with varying numbers of topics. You can evaluate the goodness-of-fit of an LDA model by calculating the perplexity of a held-out set of documents. The perplexity indicates how well the model describes a set of documents. A lower perplexity suggests a better fit.

To reproduce the results of this example, set `rng` to `'default'`.

```
rng('default')
```

Extract and Preprocess Text Data

Load the example data. The file `weatherReports.csv` contains weather reports, including a text description and categorical labels for each event. Extract the text data from the field `event_narrative`.

```
filename = "weatherReports.csv";
data = readtable(filename, 'TextType', 'string');
textData = data.event_narrative;
```

Tokenize and preprocess the text data using the function `preprocessWeatherNarratives` which is listed at the end of this example.

```
documents = preprocessWeatherNarratives(textData);
documents(1:5)
```

```
ans =
    5×1 tokenizedDocument:

    (1,1)  5 tokens: large tree down plantersville nettleton
    (2,1) 18 tokens: two foot deep standing water develop street winthrop unive...
    (3,1)  9 tokens: nws columbia relayed report tree blow down tom hall
    (4,1) 10 tokens: medium report two tree blow down i40 old fort area
    (5,1)  0 tokens:
```

Set aside 10% of the documents at random for validation.

```
numDocuments = numel(documents);
cvp = cvpartition(numDocuments, 'HoldOut', 0.1);
```

```
documentsTrain = documents(cvp.training);
documentsValidation = documents(cvp.test);
```

Create a bag-of-words model from the training documents. Remove the words that do not appear more than two times in total. Remove any documents containing no words.

```
bag = bagOfWords(documentsTrain);
bag = removeInfrequentWords(bag,2);
bag = removeEmptyDocuments(bag);
```

Choose Number of Topics

The goal is to choose a number of topics that minimize the perplexity is lowest compared to other numbers of topics. This is not the only consideration: models fit with larger numbers of topics may take longer to converge. To see the effects of the tradeoff, calculate both goodness-of-fit and the fitting time. If the optimal number of topics is high, then you might want to choose a lower value to speed up the fitting process.

Fit some LDA models for a range of values for the number of topics. Compare the fitting time and the perplexity of each model on the held-out set of test documents. The perplexity is the second output to the `logp` function. To obtain the second output without assigning the first output to anything, use the `~` symbol. The fitting time is the `TimeSinceStart` value for the last iteration. This value is in the `History` struct of the `FitInfo` property of the LDA model.

For a quicker fit, specify 'Solver' to be 'savb'. To suppress verbose output, set 'Verbose' to 0. This may take a few minutes to run.

```
numTopicsRange = [5 10 15 20 40];
for i = 1:numel(numTopicsRange)
    numTopics = numTopicsRange(i);

    mdl = fitlda(bag,numTopics, ...
        'Solver','savb', ...
        'Verbose',0);

    [~,validationPerplexity(i)] = logp(mdl,documentsValidation);
    timeElapsed(i) = mdl.FitInfo.History.TimeSinceStart(end);
end
```

Show the perplexity and elapsed time for each number of topics in a plot. Plot the perplexity on the left axis and the time elapsed on the right axis.

```
figure
yyaxis left
```


```

plot(numTopicsRange,validationPerplexity,'+-')
ylabel("Validation Perplexity")

yyaxis right
plot(numTopicsRange,timeElapsed,'o-')
ylabel("Time Elapsed (s)")

legend(["Validation Perplexity" "Time Elapsed (s)"],"Location','southeast')
xlabel("Number of Topics")

```



The plot suggests that fitting a model with 10-20 topics may be a good choice. The perplexity is low compared with the models with different numbers of topics. With this solver, the elapsed time for this many topics is also reasonable. With different solvers, you

may find that increasing the number of topics can lead to a better fit, but fitting the model takes longer to converge.

Example Preprocessing Function

The function `preprocessWeatherNarratives`, performs the following steps in order:

- 1 Convert the text data to lowercase using `lower`.
- 2 Tokenize the text using `tokenizedDocument`.
- 3 Erase punctuation using `erasePunctuation`.
- 4 Remove a list of stop words (such as "and", "of", and "the") using `removeStopWords`.
- 5 Remove words with 2 or fewer characters using `removeShortWords`.
- 6 Remove words with 15 or more characters using `removeLongWords`.
- 7 Lemmatize the words using `normalizeWords`.

```
function [documents] = preprocessWeatherNarratives(textData)
% Convert the text data to lowercase.
cleanTextData = lower(textData);

% Tokenize the text.
documents = tokenizedDocument(cleanTextData);

% Erase punctuation.
documents = erasePunctuation(documents);

% Remove a list of stop words.
documents = removeStopWords(documents);

% Remove words with 2 or fewer characters, and words with 15 or greater
% characters.
documents = removeShortWords(documents,2);
documents = removeLongWords(documents,15);

% Lemmatize the words.
documents = addPartOfSpeechDetails(documents);
documents = normalizeWords(documents,'Style','lemma');
end
```

See Also

`addPartOfSpeechDetails` | `bagOfWords` | `bagOfWords` | `erasePunctuation` | `fitlda` | `ldaModel` | `logp` | `normalizeWords` | `removeEmptyDocuments` |

`removeInfrequentWords | removeLongWords | removeShortWords |
removeStopWords | tokenizedDocument`

Related Examples

- “Analyze Text Data Using Topic Models” on page 2-18
- “Compare LDA Solvers” on page 2-30

Compare LDA Solvers

This example shows how to compare latent Dirichlet allocation (LDA) solvers by comparing the goodness of fit and the time taken to fit the model.

To reproduce the results of this example, set `rng` to `'default'`.

```
rng('default')
```

Extract and Preprocess Text Data

Load the example data. The file `weatherReports.csv` contains weather reports, including a text description and categorical labels for each event. Extract the text data from the field `event_narrative`.

```
filename = "weatherReports.csv";  
data = readtable(filename, 'TextType', 'string');  
textData = data.event_narrative;
```

Set aside 10% of the documents at random for validation.

```
numDocuments = numel(textData);  
cvp = cvpartition(numDocuments, 'HoldOut', 0.1);  
textDataTrain = textData(training(cvp));  
textDataValidation = textData(test(cvp));
```

Tokenize and preprocess the text data using the function `preprocessText` which is listed at the end of this example.

```
documentsTrain = preprocessText(textDataTrain);  
documentsValidation = preprocessText(textDataValidation);
```

Create a bag-of-words model from the training documents. Remove the words that do not appear more than two times in total. Remove any documents containing no words.

```
bag = bagOfWords(documentsTrain);  
bag = removeInfrequentWords(bag, 2);  
bag = removeEmptyDocuments(bag);
```

Fit and Compare Models

For each of the LDA solvers, fit an LDA model with 60 topics. To distinguish the solvers when plotting the results on the same axes, specify different line properties for each solver.


```

numTopics = 60;
solvers = ["cgs" "avb" "cvb0" "savb"];
lineSpecs = ["+-" "*-" "x-" "o-"];

```

For the validation data, create a bag-of-words model from the validation documents.

```
validationData = bagOfWords(documentsValidation);
```

For each of the LDA solvers, fit the model, set the initial topic concentration to 1, and specify not to fit the topic concentration parameter. Using the data in the `FitInfo` property of the fitted LDA models, plot the validation perplexity and the time elapsed. Plot the time elapsed in a logarithmic scale. This can take up to an hour to run.

The code for removing NaNs is necessary because of a quirk of the stochastic solver 'savb'. For this solver, the function evaluates the validation perplexity after each pass of the data. The function does not evaluate the validation perplexity for each iteration (mini-batch) and reports NaNs in the `FitInfo` property. To plot the validation perplexity, remove the NaNs from the reported values.

```

figure
for i = 1:numel(solvers)
    solver = solvers(i);
    lineSpec = lineSpecs(i);

    mdl = fitlda(bag,numTopics, ...
        'Solver',solver, ...
        'InitialTopicConcentration',1, ...
        'FitTopicConcentration',false, ...
        'ValidationData',validationData, ...
        'Verbose',0);

    history = mdl.FitInfo.History;

    timeElapsed = history.TimeSinceStart;
    validationPerplexity = history.ValidationPerplexity;

    % Remove NaNs.
    idx = isnan(validationPerplexity);
    timeElapsed(idx) = [];
    validationPerplexity(idx) = [];


    semilogx(timeElapsed,validationPerplexity,lineSpec)
    hold on
end

```

```

hold off
xlabel("Time Elapsed (s)")
ylabel("Validation Perplexity")
legend(solvers)

```



For the stochastic solver "savb", the function, by default, passes through the training data once. To process more passes of the data, set 'DataPassLimit' to a larger value (the default value is 1). For the batch solvers ("cgs", "avb", and "cvb0"), to reduce the number of iterations used to fit the models, set the 'IterationLimit' option to a lower value (the default value is 100).

A lower validation perplexity suggests a better fit. Usually, the solvers "savb" and "cgs" converge quickly to a good fit. The solver "cvb0" might converge to a better fit, but it can take much longer to converge.

For the `FitInfo` property, the `fitlda` function estimates the validation perplexity from the document probabilities at the maximum likelihood estimates of the per-document topic probabilities. This is usually quicker to compute, but can be less accurate than other methods. Alternatively, calculate the validation perplexity using the `logp` function. This function calculates more accurate values but can take longer to run. For an example showing how to compute the perplexity using `logp`, see “Calculate Document Log-Probabilities from Word Count Matrix”.

Preprocessing Function

The function `preprocessText` performs the following steps:

- 1 Tokenize the text using `tokenizedDocument`.
- 2 Lemmatize the words using `normalizeWords`.
- 3 Erase punctuation using `erasePunctuation`.
- 4 Remove a list of stop words (such as "and", "of", and "the") using `removeStopWords`.
- 5 Remove words with 2 or fewer characters using `removeShortWords`.
- 6 Remove words with 15 or more characters using `removeLongWords`.

```
function documents = preprocessText(textData)

% Tokenize the text.
documents = tokenizedDocument(textData);

% Lemmatize the words.
documents = addPartOfSpeechDetails(documents);
documents = normalizeWords(documents, 'Style', 'lemma');

% Erase punctuation.
documents = erasePunctuation(documents);

% Remove a list of stop words.
documents = removeStopWords(documents);

% Remove words with 2 or fewer characters, and words with 15 or greater
% characters.
documents = removeShortWords(documents, 2);
```

```
documents = removeLongWords(documents,15);  
end
```

See Also

`addPartOfSpeechDetails` | `bagOfWords` | `erasePunctuation` | `fitlda` | `ldaModel` | `logp` | `normalizeWords` | `removeEmptyDocuments` | `removeInfrequentWords` | `removeLongWords` | `removeShortWords` | `removeStopWords` | `tokenizedDocument` | `wordcloud`

Related Examples

- “Analyze Text Data Using Topic Models” on page 2-18
- “Choose Number of Topics for LDA Model” on page 2-25

Analyze Text Data Containing Emojis

This example shows how to analyze text data containing emojis.

Emojis are pictorial symbols that appear inline in text. When writing text on mobile devices such as smartphones and tablets, people use emojis to keep the text short and convey emotion and feelings.

You also can use emojis to analyze text data. For example, use them to identify relevant strings of text or to visualize the sentiment or emotion of the text.

When working with text data, emojis can behave unpredictably. Depending on your system fonts, your system might not display some emojis correctly. Therefore, if an emoji is not displayed correctly, then the data is not necessarily missing. Your system might be unable to display the emoji in the current font.

Composing Emojis

In most cases, you can read emojis from a file (for example, by using `extractFileText`, `extractHTMLText`, or `readtable`) or by copying and pasting them directly into MATLAB®. Otherwise, you must compose the emoji using Unicode UTF16 code units.

Some emojis consist of multiple Unicode UTF16 code units. For example, the "smiling face with sunglasses" emoji (☀️ with code point U+1F60E) is a single glyph but comprises two UTF16 code units "D83D" and "DE0E". Create a string containing this emoji using the `compose` function, and specify the two code units with the prefix `"\x"`.

```
emoji = compose("\xD83D\xDE0E")
```

```
emoji =  
"☀️"
```

First get the Unicode UTF16 code units of an emoji. Use `char` to get the numeric representation of the emoji, and then use `dec2hex` to get the corresponding hex value.

```
codeUnits = dec2hex(char(emoji))
```

```
codeUnits = 2x4 char array  
    'D83D'  
    'DE0E'
```

Reconstruct the composition string using the `strjoin` function with the empty delimiter `""`.

```
formatSpec = strjoin("\x" + codeUnits, "")
```

```
formatSpec =  
"\xD83D\xDE0E"
```

```
emoji = compose(formatSpec)
```

```
emoji =  
"👍"
```

Import Text Data

Extract the text data in the file `weekendUpdates.xlsx` using `readtable`. The file `weekendUpdates.xlsx` contains status updates containing the hashtags `"#weekend"` and `"#vacation"`.

```
filename = "weekendUpdates.xlsx";  
tbl = readtable(filename, 'TextType', 'string');  
head(tbl)
```

```
ans=8x2 table
```

ID	TextData
1	"Happy anniversary! ♥ Next stop: Paris! → #vacation"
2	"Haha, BBQ on the beach, engage smug mode! 🍷♥ 🍷#vacation"
3	"getting ready for Saturday night 🍷#yum #weekend 🍷"
4	"Say it with me - I NEED A #VACATION!!! ☺"
5	"🍷Chilling 🍷at home for the first time in ages...This is the life! 🍷#weekend"
6	"My last #weekend before the exam 🍷🍷"
7	"can't believe my #vacation is over 🍷so unfair"
8	"Can't wait for tennis this #weekend 🍷🍷🍷"

Extract the text data from the field `TextData` and view the first few status updates.

```
textData = tbl.TextData;  
textData(1:5)
```

```
ans = 5x1 string array
```

```
"Happy anniversary! ♥ Next stop: Paris! → #vacation"  
"Haha, BBQ on the beach, engage smug mode! 🍷♥ 🍷#vacation"  
"getting ready for Saturday night 🍷#yum #weekend 🍷"
```


with code U+1F60E). This emoji comprises the two Unicode UTF16 code units "D83D" and "DE0E".

```
emoji = compose("\xD83D\xDE0E");
idx = contains(textData,emoji);
textDataSunglasses = textData(idx);
textDataSunglasses(1:5)

ans = 5x1 string array
    "Haha, BBQ on the beach, engage smug mode! 🍷❤️ 🏖️#vacation"
    "getting ready for Saturday night 🍷#yum #weekend 🍷"
    "🏖️Chilling 🏖️at home for the first time in ages...This is the life! 🏖️#weekend"
    "🏖️Check the out-of-office crew, we are officially ON #VACATION!! 🍷"
    "Who needs a #vacation when the weather is this good * 🍷"
```

Visualize the extracted text data in a word cloud.

```
figure
wordcloud(textDataSunglasses);
```



```

16 tokens: Haha , BBQ on the beach , engage smug mode ! 🍷🍷🍷❤️ 🍷🍷#vacation
9 tokens: getting ready for Saturday night 🍷🍷#yum #weekend 🍷🍷
13 tokens: Say it with me - I NEED A #VACATION ! ! ! ☺️
19 tokens: 🍷🍷Chilling 🍷🍷at home for the first time in ages ... This is the life ! 🍷🍷

```

The `tokenizedDocument` function automatically detects emoji and assigns the token type "emoji". View the first few token details of the documents using the `tokenDetails` function.

```

tdetails = tokenDetails(documents);
head(tdetails)

```

```

ans=8x5 table

```

Token	DocumentNumber	LineNumber	Type	Language
"Happy"	1	1	letters	en
"anniversary"	1	1	letters	en
"!"	1	1	punctuation	en
"❤️"	1	1	emoji	en
"Next"	1	1	letters	en
"stop"	1	1	letters	en
":"	1	1	punctuation	en
"Paris"	1	1	letters	en

Visualize the emojis in a word cloud by extracting the tokens with token type "emoji" and inputting them into the `wordcloud` function.

```

idx = tdetails.Type == "emoji";
tokens = tdetails.Token(idx);
figure
wordcloud(tokens);
title("Emojis")

```


- “Generate Text Using Deep Learning” (Deep Learning Toolbox)

Train a Sentiment Classifier

This example shows how to train a classifier for sentiment analysis using an annotated list of positive and negative sentiment words and a pretrained word embedding.

The pretrained word embedding plays several roles in this workflow. It converts words into numeric vectors and forms the basis for a classifier. You can then use the classifier to predict the sentiment of other words using their vector representation, and use these classifications to calculate the sentiment of a piece of text. There are four steps in training and using the sentiment classifier:

- Load a pretrained word embedding.
- Load an opinion lexicon listing positive and negative words.
- Train a sentiment classifier using the word vectors of the positive and negative words.
- Calculate the mean sentiment scores of the words in a piece of text.

To reproduce the results in this example, set `rng` to `'default'`.

```
rng('default')
```

Load Pretrained Word Embedding

Word embeddings map words in a vocabulary to numeric vectors. These embeddings can capture semantic details of the words so that similar words have similar vectors. They also model relationships between words through vector arithmetic. For example, the relationship *king is to queen as man is to woman* is described by the equation $king - man + woman = queen$.

Load a pretrained word embedding using the `fastTextWordEmbedding` function. This function requires Text Analytics Toolbox™ Model for *fastText English 16 Billion Token Word Embedding* support package. If this support package is not installed, then the function provides a download link.

```
emb = fastTextWordEmbedding;
```

Load Opinion Lexicon

Load the positive and negative words from the opinion lexicon (also known as a sentiment lexicon) from <https://www.cs.uic.edu/~liub/FBS/sentiment-analysis.html>. First, extract the files from the `.rar` file into a folder named `opinion-lexicon-English`, and then import the text.

Load the data using the function `readLexicon` listed at the end of this example. The output `data` is a table with variables `Word` containing the words, and `Label` containing a categorical sentiment label, `Positive` or `Negative`.

```
data = readLexicon;
```

View the first few words labeled as positive.

```
idx = data.Label == "Positive";  
head(data[idx,:])
```

```
ans=8x2 table  
      Word      Label  
-----  
"a+"      Positive  
"abound"   Positive  
"abounds"  Positive  
"abundance" Positive  
"abundant" Positive  
"accessible" Positive  
"accessible" Positive  
"acclaim"  Positive
```

View the first few words labeled as negative.

```
idx = data.Label == "Negative";  
head(data[idx,:])
```

```
ans=8x2 table  
      Word      Label  
-----  
"2-faced"  Negative  
"2-faces"  Negative  
"abnormal" Negative  
"abolish"  Negative  
"abominable" Negative  
"abominably" Negative  
"abominate" Negative  
"abomination" Negative
```

Prepare Data for Training

To train the sentiment classifier, convert the words to word vectors using the pretrained word embedding `emb`. First remove the words that do not appear in the word embedding `emb`.

```
idx = ~isVocabularyWord(emb,data.Word);
data(idx,:) = [];
```

Set aside 10% of the words at random for testing.

```
numWords = size(data,1);
cvp = cvpartition(numWords,'HoldOut',0.1);
dataTrain = data(training(cvp),:);
dataTest = data(test(cvp),:);
```

Convert the words in the training data to word vectors using `word2vec`.

```
wordsTrain = dataTrain.Word;
XTrain = word2vec(emb,wordsTrain);
YTrain = dataTrain.Label;
```

Train Sentiment Classifier

Train a support vector machine (SVM) classifier which classifies word vectors into positive and negative categories.

```
mdl = fitcsvm(XTrain,YTrain);
```

Test Classifier

Convert the words in the test data to word vectors using `word2vec`.


```
wordsTest = dataTest.Word;
XTest = word2vec(emb,wordsTest);
YTest = dataTest.Label;
```

Predict the sentiment labels of the test word vectors.

```
[YPred,scores] = predict(mdl,XTest);
```

Visualize the classification accuracy in a confusion matrix.

```
figure
confusionchart(YTest,YPred);
```



Visualize the classifications in word clouds. Plot the words with positive and negative sentiments in word clouds with word sizes corresponding to the prediction scores.

```
figure
subplot(1,2,1)
idx = YPred == "Positive";
wordcloud(wordsTest(idx), scores(idx,1));
title("Predicted Positive Sentiment")

subplot(1,2,2)
wordcloud(wordsTest(~idx), scores(~idx,2));
title("Predicted Negative Sentiment")
```



```
textData = dataReviews.comments;
textData(1:10)

ans = 10x1 string array
    "Pretty nice, quiet, cozy place to stay. Toiletries, snacks, coffee, WiFi, cable TV
    "The host was extremely welcoming and obliging. The neighborhood is quiet and charm
    "Nice and easy stay - with good accommodations especially the cable TV "
    "The host has been very accommodating and helpful. The description in the ad is acc
    "It's a great quiet stay."
    "Couldn't have been happier. The apartment was well renovated, very clean and conv
    "The apartment is very nice- as described and very convenient. The real superstar o
    "This is a brand new gorgeous place, very clean, bright and welcoming. Estee espec
    "Estee and Josh are great hosts. Very welcoming. Made us feel like we were staying
    "Estee was super sweet and so very accommodating! The apartment was nicely renovate
```

Create a function which tokenizes and preprocesses the text data so it can be used for analysis. The function `preprocessText`, listed at the end of the example, performs the following steps in order:

- 1 Tokenize the text using `tokenizedDocument`.
- 2 Erase punctuation using `erasePunctuation`.
- 3 Remove stop words (such as "and", "of", and "the") using `removeStopWords`.
- 4 Convert to lowercase using `lower`.

Use the preprocessing function `preprocessText` to prepare the text data. This step can take a few minutes to run.

```
documents = preprocessText(textData);
```

Remove the words from the documents that do not appear in the word embedding `emb`.

```
idx = ~isVocabularyWord(emb,documents.Vocabulary);
documents = removeWords(documents,idx);
```

To visualize how well the sentiment classifier generalizes to the reviews, classify the sentiments on the words that occur in the reviews, but not in the training data and visualize them in word clouds. Use the word clouds to manually check that the classifier behaves as expected.

```
words = documents.Vocabulary;
words(ismember(words,wordsTrain)) = [];
```

```

vec = word2vec(emb,words);
[YPred,scores] = predict mdl,vec);

figure
subplot(1,2,1)
idx = YPred == "Positive";
wordcloud(words(idx),scores(idx,1));
title("Predicted Positive Sentiment")

subplot(1,2,2)
wordcloud(words(~idx),scores(~idx,2));
title("Predicted Negative Sentiment")

```

Predicted Positive Sentiment



Predicted Negative Sentiment



To calculate the sentiment of a given piece of text, compute the sentiment score for each word in the text and calculate the mean sentiment score.

For a selection of the documents, calculate the mean sentiment score. For each document, convert the words to word vectors, predict the sentiment score on the word vectors, transform the scores using the score-to-posterior transform function and then calculate the mean sentiment score.

```
idx = [7 34 331 1788 1820 1831 2185 21892 63734 76832 113276 120210];
for i = 1:numel(idx)
    words = string(documents(idx(i)));
    vec = word2vec(emb,words);
    [~,scores] = predict mdl,vec);
    sentimentScore(i) = mean(scores(:,1));
end
```

View the predicted sentiment scores with the text data. Scores greater than 0 correspond to positive sentiment, scores less than 0 correspond to negative sentiment, and scores close to 0 correspond to neutral sentiment.

```
[sentimentScore' textData(idx)]
```

```
ans = 12x2 string array
    "0.85721"      "The apartment is very nice- as described and very convenient. The
    "2.0453"       "Estee was the perfect Airbnb host. The apartment was comfortable, s
    "-0.37918"    "The apartment is not appropriate for 5 people. Is too little and We
    "0.94799"     "Truly a quaint place in Beacon Hill. Comfortable walking distance t
    "-0.077053"   "the neighbourhood is perfect!!!!!! as it is very close to Bowdoin T S
    "0.17846"     "Although we didn't meet JJ, we felt he was very quick to respond. C
    "-0.31603"    "In the apartment it was very dirty .we walked in and there instinc
    "-4.0895"     "Blackmail!"
    "1.658"       "Outstanding stay. The apartment is world-class - very, very nice.
    "1.7102"      "I had an amazing stay at Carney's. The hosts are friendly and very
    "0.67654"     "My husband and I came to Boston for our 1 year anniversary. We're s
    "-0.21651"    "My fiancÃ© and I had just gotten engaged and wanted to stay somewhe
```

Sentiment Lexicon Reading Function

This function reads the positive and negative words from the sentiment lexicon and returns a table. The table contains variables `Word` and `Label`, where `Label` contains categorical values `Positive` and `Negative` corresponding to the sentiment of each word.

```

function data = readLexicon

% Read positive words
fidPositive = fopen(fullfile('opinion-lexicon-English','positive-words.txt'));
C = textscan(fidPositive,'%s','CommentStyle',';');
wordsPositive = string(C{1});

% Read negative words
fidNegative = fopen(fullfile('opinion-lexicon-English','negative-words.txt'));
C = textscan(fidNegative,'%s','CommentStyle',';');
wordsNegative = string(C{1});
fclose all;

% Create table of labeled words
words = [wordsPositive;wordsNegative];
labels = categorical(nan(numel(words),1));
labels(1:numel(wordsPositive)) = "Positive";
labels(numel(wordsPositive)+1:end) = "Negative";

data = table(words,labels,'VariableNames',{'Word','Label'});

end

```

Preprocessing Function

The function preprocessText performs the following steps:

- 1 Tokenize the text using tokenizedDocument.
- 2 Erase punctuation using erasePunctuation.
- 3 Remove stop words (such as "and", "of", and "the") using removeStopWords.
- 4 Convert to lowercase using lower.

```

function documents = preprocessText(textData)

% Tokenize the text.
documents = tokenizedDocument(textData);

% Erase punctuation.
documents = erasePunctuation(documents);

% Remove a list of stop words.
documents = removeStopWords(documents);

```

```
% Convert to lowercase.  
documents = lower(documents);  
  
end
```

See Also

[bagOfWords](#) | [erasePunctuation](#) | [fastTextWordEmbedding](#) | [removeStopWords](#) | [removeWords](#) | [tokenizedDocument](#) | [word2vec](#) | [wordcloud](#)

Related Examples

- “Create Simple Text Model for Classification” on page 2-2
- “Analyze Text Data Containing Emojis” on page 2-35
- “Analyze Text Data Using Topic Models” on page 2-18
- “Analyze Text Data Using Multiword Phrases” on page 2-9
- “Classify Text Data Using Deep Learning” on page 2-53
- “Generate Text Using Deep Learning” (Deep Learning Toolbox)

Classify Text Data Using Deep Learning

This example shows how to classify text descriptions of weather reports using a deep learning long short-term memory (LSTM) network.

Text data is naturally sequential. A piece of text is a sequence of words, which might have dependencies between them. To learn and use long-term dependencies to classify sequence data, use an LSTM neural network. An LSTM network is a type of recurrent neural network (RNN) that can learn long-term dependencies between time steps of sequence data.

To input text to an LSTM network, first convert the text data into numeric sequences. You can achieve this using a word encoding which maps documents to sequences of numeric indices. For better results, also include a word embedding layer in the network. Word embeddings map words in a vocabulary to numeric vectors rather than scalar indices. These embeddings capture semantic details of the words, so that words with similar meanings have similar vectors. They also model relationships between words through vector arithmetic. For example, the relationship "*king is to queen as man is to woman*" is described by the equation $king - man + woman = queen$.

There are four steps in training and using the LSTM network in this example:

- Import and preprocess the data.
- Convert the words to numeric sequences using a word encoding.
- Create and train an LSTM network with a word embedding layer.
- Classify new text data using the trained LSTM network.

Import Data

Import the weather reports data. This data contains labeled textual descriptions of weather events. To import the text data as strings, specify the text type to be 'string'.

```
filename = "weatherReports.csv";
data = readtable(filename, 'TextType', 'string');
head(data)
```

```
ans=8x16 table
      Time          event_id      state      event_type
-----
22-Jul-2016 16:10:00  6.4433e+05  "MISSISSIPPI"  "Thunderstorm Wind"
```

15-Jul-2016	17:15:00	6.5182e+05	"SOUTH CAROLINA"	"Heavy Rain"
15-Jul-2016	17:25:00	6.5183e+05	"SOUTH CAROLINA"	"Thunderstorm Wind"
16-Jul-2016	12:46:00	6.5183e+05	"NORTH CAROLINA"	"Thunderstorm Wind"
15-Jul-2016	14:28:00	6.4332e+05	"MISSOURI"	"Hail"
15-Jul-2016	16:31:00	6.4332e+05	"ARKANSAS"	"Thunderstorm Wind"
15-Jul-2016	16:03:00	6.4343e+05	"TENNESSEE"	"Thunderstorm Wind"
15-Jul-2016	17:27:00	6.4344e+05	"TENNESSEE"	"Hail"

Remove the rows of the table with empty reports.

```
idxEmpty = strlen(data.event_narrative) == 0;
data(idxEmpty,:) = [];
```


The goal of this example is to classify events by the label in the `event_type` column. To divide the data into classes, convert these labels to categorical.

```
data.event_type = categorical(data.event_type);
```

View the distribution of the classes in the data using a histogram. To make the labels easier to read, increase the width of the figure.

```
f = figure;
f.Position(3) = 1.5*f.Position(3);

h = histogram(data.event_type);
xlabel("Class")
ylabel("Frequency")
title("Class Distribution")
```

The classes of the data are imbalanced, with many classes containing few observations. When the classes are imbalanced in this way, the network might converge to a less accurate model. To prevent this problem, remove any classes which appear fewer than ten times.

Get the frequency counts of the classes and the class names from the histogram.

```
classCounts = h.BinCounts;
classNames = h.Categories;
```

Find the classes containing fewer than ten observations.

```
idxLowCounts = classCounts < 10;
infrequentClasses = classNames(idxLowCounts)
```

```
infrequentClasses = 1x8 cell array
    {'Freezing Fog'}    {'Hurricane'}    {'Lakeshore Flood'}    {'Marine Dense Fog'}
```

Remove these infrequent classes from the data. Use `removecats` to remove the unused categories from the categorical data.

```
idxInfrequent = ismember(data.event_type,infrequentClasses);  
data(idxInfrequent,:) = [];  
data.event_type = removecats(data.event_type);
```

Now the data is sorted into classes of reasonable size. The next step is to partition it into sets for training, validation, and testing. Partition the data into a training partition and a held-out partition for validation and testing. Specify the holdout percentage to be 30%.

```
cvp = cvpartition(data.event_type,'Holdout',0.3);  
dataTrain = data(training(cvp),:);  
dataHeldOut = data(test(cvp),:);
```

Partition the held-out set again to get a validation set. Specify the holdout percentage to be 50%. This results in a partitioning of 70% training observations, 15% validation observations, and 15% test observations.

```
cvp = cvpartition(dataHeldOut.event_type,'HoldOut',0.5);  
dataValidation = dataHeldOut(training(cvp),:);  
dataTest = dataHeldOut(test(cvp),:);
```

Extract the text data and labels from the partitioned tables.

```
textDataTrain = dataTrain.event_narrative;  
textDataValidation = dataValidation.event_narrative;  
textDataTest = dataTest.event_narrative;  
YTrain = dataTrain.event_type;  
YValidation = dataValidation.event_type;  
YTest = dataTest.event_type;
```

To check that you have imported the data correctly, visualize the training text data using a word cloud.

```
figure  
wordcloud(textDataTrain);  
title("Training Data")
```


documentsValidation =

4218x1 tokenizedDocument:

5 tokens: quarter size hail near rosemark
7 tokens: large tree down on powerlines in caruthersville
6 tokens: three trees down on hwy 224
7 tokens: heat indices of 110 degrees or higher
9 tokens: numerous trees were reported down in the greenback area
9 tokens: several large tree branches were blown down in osage
12 tokens: a tree fell onto a car four miles west southwest of knoxville
7 tokens: two trees were reported in tellico plains
21 tokens: wind gusts of 40 to 45 mph were common across buffalo county during the
77 tokens: strong southerly gradient winds affected the nashville metro during the
36 tokens: wind gusts of 40 to 50 mph were common across crawford county during the
31 tokens: snowfall amounts between 19 and 32 inches were reported across prince w
16 tokens: wind driven hail resulted in numerous holes in siding on the south side
15 tokens: snowfall amounts were estimated to be between 24 and 36 inches based on
33 tokens: snowfall amounts were reported to be between 18 and 30 inches across so
10 tokens: three to eight inches of snow fell across suffolk county
9 tokens: approximately nine inches of snow fell in bristol county
14 tokens: between 2 and 5 inches of snow were reported over the 12 hour period
13 tokens: trained spotters reported between 02 and 04 inches of ice around the co
23 tokens: the white river at newport remained above flood stage from december and
118 tokens: strong high pressure developed across south central arizona including t
13 tokens: the blackhall mountain snotel site elevation 9820 ft estimated six inch
13 tokens: the battle mountain snotel site elevation 7440 ft estimated 17 inches o
7 tokens: trees were blown down on persimmon road
16 tokens: two to five inches of rain fell across central and eastern portions of
13 tokens: one to two feet of water covered highway 2692 from mitchell to scottsb
13 tokens: the intersection of highway 97 and highway vv was closed due to floodin
7 tokens: quarter size hail was reported at federal
127 tokens: the national weather service baltimore washington weather forecast off:
14 tokens: the east santa barbara channel buoy reported a thunderstorm wind gust o
19 tokens: there was a report via social media of 73 inches of lake enhanced snow
27 tokens: lake enhanced snow totals over an 18hour period included six inches nea
19 tokens: twoday storm total lake effect snow accumulation included 14 inches at
10 tokens: trees were blown down around highway 37 near fort gaines
13 tokens: the webber springs snotel site elevation 9250 ft estimated 15 inches o
10 tokens: just over two inches of rain fell in 24 hours
8 tokens: quarter size hail was reported at fort laramie
12 tokens: between 2 and 4 inches of snow was reported around the county
13 tokens: estimated wind gusts of 60 mph were reported 17 miles westnorthwest of
9 tokens: nickel to quarter size hail was reported at potter
9 tokens: just over two inches of rain fell with thunderstorms

73 tokens: the poteau river near poteau rose above its flood stage of 24 feet at 1
10 tokens: fdk reported reduced visibilities of one quarter mile or less
10 tokens: hwy reported reduced visibilities of one quarter mile or less
11 tokens: heavy rain fell from thunderstorms on the morning hours of 731
20 tokens: total rainfall from thunderstorms was six and three quarter inches with
14 tokens: between 1 and 3 inches of snow were reported over the 12 hour period
9 tokens: between 1 and 4 inches of snow was reported
10 tokens: just under three inches of heavy rain fell from thunderstorms
21 tokens: a large tree was taken down by thunderstorm wind gusts and knocked off
28 tokens: heavy rainfall over the solimar burn scar resulted in a significant mud
40 tokens: northerly winds gusting to near 50 mph combined with existing snow cover
24 tokens: a light glaze of freezing rain caused hazardous travel conditions over
9 tokens: a tree was blown down just south of bonifay
49 tokens: temperatures reaching daytime highs of 95 to 100 after a period of cool
7 tokens: trees were blown down on beechwood drive
10 tokens: nyg reported reduced visibilities of one quarter mile or less
10 tokens: mrb reported reduced visibilities of one quarter mile or less
9 tokens: between 1 and 4 inches of snow was reported
12 tokens: ping pong ball size hail was reported two miles south of cheyenne
5 tokens: heavy rain fell from thunderstorms
13 tokens: trained spotters reported between 02 and 04 inches of ice around the co
36 tokens: a tree was blown down at avery and spring street in st augustine the t
41 tokens: snow amounts reported by spotters were 10 inches at victor and 9 inches
11 tokens: harell road was closed at forbes street due to high water
9 tokens: golf ball size hail was reported southwest of wheatland
9 tokens: between 5 and 8 inches of snow was reported
9 tokens: almost three inches of heavy rain fell with thunderstorms
31 tokens: a lightning strike hit the pulaski county 911 center several of the cor
14 tokens: the east santa barbara channel buoy reported a thunderstorm wind gust o
13 tokens: a 24 hour storm total rainfall of 550 inches was reported near northvie
15 tokens: a tree was blown down onto a residence in the cottondale area damage wa
8 tokens: trees were blown down in the youngstown area
14 tokens: the roof was partially blown off of lighthouse church near sylvester da
9 tokens: a tree was blown down on spring creek road
53 tokens: temperatures reaching daytime highs of 95 to 100 after a period of cool
5 tokens: heavy rain fell from thunderstorms
5 tokens: heavy rain fell from thunderstorms
13 tokens: the blackhall mountain snotel site elevation 9820 ft estimated 15 inche
9 tokens: there was a water rescue reported on cherokee avenue
13 tokens: trained spotters reported between 02 and 04 inches of ice around the co
14 tokens: the wind sensor at the torrington airport measured a peak gust of 63 mp
9 tokens: between 5 and 8 inches of snow was reported
58 tokens: snow began during the evening hours on the 22nd then continued heavy at
10 tokens: quarter size hail was reported seven miles west of carpenter

39 tokens: snowfall of 1 to 4 inches combined with southeast winds gusting around
17 tokens: quarter size hail was reported 4 miles southeast of kentwood the report
8 tokens: golfball size hail was reported in downtown franklinton
17 tokens: a porch roof was blown off a home at louisiana highway 447 and courtney
12 tokens: just under four inches of rain fell in 24 hours from thunderstorms
13 tokens: the webber springs snotel site elevation 9250 ft estimated 17 inches of
7 tokens: trees were blown down on thames street
9 tokens: between 1 and 6 inches of snow was reported
11 tokens: four and a half inches of heavy rain fell from thunderstorms
17 tokens: one quarter to one half of an inch of freezing rain accrual was reported
20 tokens: a tree was blown down on highway 189 about 5 miles outside of elba power
8 tokens: a tree was blown down on highway 162
8 tokens: trees were blown down on harvey mill road
18 tokens: a tree was blown down onto a house near the 3200 block of crawfordville
11 tokens: highway j was flooded and there was a high water rescue
9 tokens: between one and two inches of snow was reported
9 tokens: between one and two inches of snow was reported
23 tokens: meteorologist from the 26th operational weather squadron at barksdale a
40 tokens: westerly winds behind a cold front reach sustained speed of 40 to 45 mph
12 tokens: a wind gust of 60 mph was measured at wunderground site kflpanam37
12 tokens: snowfall amounts of up to 2 inches were observed across the county
24 tokens: heavy rain and snowmelt combined to cause minor flooding on the kennebec
27 tokens: a tenth of an inch of freezing rain was reported in dillon a large tree
13 tokens: the wydot sensor at bordeaux measured a peak wind gust of 61 mph
17 tokens: a spotter reported visibility of 300 yards at el toro rd and aliso cree
44 tokens: lake effect snow showers accumulated to between 2 and 6 inches during t
42 tokens: lake effect snow showers accumulated to between 2 and 5 inches during t
28 tokens: a couple tenths of an inch of freezing rain accrual was reported across
11 tokens: a 59 mph wind gust was measured at the cleveland awos
8 tokens: a tree was blown down on morris road
11 tokens: a tree fell on a home around 2273 highway 15 south
46 tokens: lake effect snow showers accumulated to between 2 and 4 inches during t
14 tokens: a 24 hour storm total rainfall of 381 inches was reported near ash grove
19 tokens: quarter size hail fell at the intersection of north street and highway
14 tokens: flash flooding washed out portions of county road 19 north of carter ca
16 tokens: a tree was blown down onto county road 5 near the intersection with co
13 tokens: several trees uprooted along highway 231 between the cities of cleveland
13 tokens: several trees uprooted and power pole downed causing structural damage
40 tokens: northerly winds gusting to near 50 mph combined with existing snow cover
29 tokens: westerly winds behind a cold front reach sustained speed of 40 to 45 mph
15 tokens: law enforcement reported a funnel cloud near the intersection of us 98
18 tokens: flooding reported in plaza del caribe flood waters reached the doors of
49 tokens: temperatures reaching daytime highs of 95 to 100 after a period of cool
26 tokens: woodland high school lunchroom roof lifted off along with numerous trees

49 tokens: temperatures reaching daytime highs of 95 to 100 after a period of cool
49 tokens: temperatures reaching daytime highs of 95 to 100 after a period of cool
20 tokens: thunderstorm winds caused tree damage including several branches blown
49 tokens: reports of slideoffs and accidents along with school delays were common
49 tokens: reports of slideoffs and accidents along with school delays were common
23 tokens: six utility poles bent on 4000n between 6000e and 8000e and a half doz
13 tokens: a tree was blown down along shell point road and spring creek highway
5 tokens: heavy rain fell from thunderstorms
19 tokens: trees were taken down at the intersection of 202 and route 10 in morris
10 tokens: there were 2 reports of trees down in quitman county
7 tokens: trees were blown down on highway 216
8 tokens: trees were blown down along val del road
15 tokens: a public report indicated pea to penny sized hail near majors field in
49 tokens: reports of slideoffs and accidents along with school delays were common
11 tokens: golf ball size hail was reported six miles west of hemingford
25 tokens: heavy rain and snow melt combined to cause minor flooding on the presur
13 tokens: trees and wires down on western ave in morristown due to thunderstorm v
5 tokens: heavy rain fell from thunderstorms
10 tokens: trees and power lines were blown down on highway 52
23 tokens: downed tree blocking the road along the 500 block of ridgewood road rad
17 tokens: a tree was blown down on county road 58 near the border of franklin and
12 tokens: a tree was blown down at courtney grade road near puckett road
10 tokens: a tree was taken down due to thunderstorm wind gusts
36 tokens: near lake darby 34 inches of snow was measured a social media post from
5 tokens: reported by ew8188 in frederick
13 tokens: the squaw peak raws recorded a gust to 77 mph at 130239 pst
9 tokens: hail from a thunderstorm was estimated at 75 inches
21 tokens: liberty county dispatch reported power lines down at the intersection o
24 tokens: liberty county dispatch reported a tree and a power line down at the in
16 tokens: the juniper creek raws recorded wind chill temperatures ranging from 10
22 tokens: the flynn prairie raws recorded several gusts exceeding 57 mph during t
13 tokens: dutch harbor asos experienced a peak gust to 82 knots during this time
10 tokens: several large trees were taken down due to thunderstorm winds
6 tokens: thunderstorm winds took down numerous trees
19 tokens: three inches of snow was measured 5 miles south of heath a spotter measu
17 tokens: northeast of troy a spotter measured 28 inches of snow southwest of tov
5 tokens: reported by dw3148 falling waters
10 tokens: w99 reported reduced visibilities of one quarter mile or less
17 tokens: the umpqua offshore buoy indicated heavy swell that likely generated h
17 tokens: the port orford buoy indicated heavy swell that likely generated high s
17 tokens: the port orford buoy indicated heavy swell that likely generated high s
15 tokens: offshore buoys indicated heavy swell that likely generated high surf at
16 tokens: a power line was blown down at highway 71 and industrial road monetary
8 tokens: weatherflow measured thunderstorm wind gust of 64 mph

14 tokens: an nws employee measured hail to the size of 125 inches during a thund
16 tokens: in plymouth warren avenue was closed at the entrance to plymouth beach
30 tokens: a coop observer reported 4 inches of snow new snow in waterville wa the
12 tokens: several pictures of golf ball size hail was posted to social media
15 tokens: a measured wind gust of 56 knots occurred with a thunderstorm at a weat
25 tokens: em reported 56 inches of snow in marysville early thursday morning the
100 tokens: isolated thunderstorms developed and moved north across the greater pho
8 tokens: near circleville an inch of snow was measured
7 tokens: trees were blown down east of somerset
8 tokens: three inches of snow was measured near wapakoneta
63 tokens: a coop observer reported 143 inches of new snow from this passing storm
11 tokens: two and a half inches of snow was measured near greenville
14 tokens: a report from east of pickerington showed that 2 inches of snow had fal
23 tokens: heavy snotel amounts were 9 inches at dollarhide 11 inches at galena su
15 tokens: snowfall amounts were estimated to be between 20 and 30 inches based on
9 tokens: just over two inches of rain fell from thunderstorms
11 tokens: there were numerous reports of downed trees in the haysi vicinity
16 tokens: broadcast media reported a tree blown down on a home 2 miles north of n
35 tokens: two weather stations along the south washington coast reported a few ho
14 tokens: a member of the public reported 6 inches of snow in east wenatchee wa
14 tokens: snowfall totaled up to 243 inches near keyser and 235 inches near short
18 tokens: thunderstorm winds caused tree damage including several branches blown
10 tokens: northwest of chillicothe a half inch of snow was measured
13 tokens: spotters in trenton and southeast of oxford both measured 2 inches of s
47 tokens: numerous trees were downed from a storm that would go on to produce a t
11 tokens: snow accumulated 2 to 5 inches including 40 inches near pipestone
21 tokens: snow amounts up to 15 inches were measured across warren county cocoral
9 tokens: trees and wires taken down due to thunderstorm winds
32 tokens: areas of both low visibilities from fog and icy surfaces from freezing
12 tokens: a coop observer reported 71 inches of snow in holden village wa
41 tokens: measurements and estimates of 4 to 8 inches of snow were received acros
32 tokens: areas of both low visibilities from fog and icy surfaces from freezing
32 tokens: areas of both low visibilities from fog and icy surfaces from freezing
12 tokens: several trees and power wires taken down due to thunderstorm wind gusts
18 tokens: snow accumulated 2 to 5 inches over the southeastern part of yankton co
6 tokens: law enforcement reported several trees down
12 tokens: power lines were blown down on the 4100 block of jordan ave
12 tokens: local media reported trees and power lines were down in oakland townsh
10 tokens: five people died in las vegas of heat related causes
10 tokens: a woman died of heat related causes in death valley
7 tokens: eight homes were flooded in dolan springs
18 tokens: over 9 inches of snow was reported in alamo the heavy wet snow resulte
5 tokens: emergency management reported trees down
8 tokens: a trained spotter reported trees and wires down

5 tokens: the public reported trees down
23 tokens: a tree was down on south shore road near old forge in the town of webb
8 tokens: the sacramento wash flooded the oatman topock highway
11 tokens: a wind gust to 65 mph was reported at joplin 3sw
37 tokens: frequent wind gusts of 40 to 50 mph resulted in numerous trees down ac
28 tokens: the stuart airport awos ksua recorded peak wind gusts of 35 knots as a
11 tokens: one to three inches of snowfall with some light ice accretion
6 tokens: emergency management reported numerous trees down
16 tokens: highway 95 was impassable from vidal junction to mile marker 24 due to
35 tokens: usaf wind tower 0300 recorded a peak gust of 41 knots from the southwest
32 tokens: the awos at the new smryna beach airport kevb reported winds up to 38 k
37 tokens: the vero beach airport asos kvrb measured a gust to 34 knots from the s
14 tokens: eight inches of snow was reported in barryton 73 inches was reported in
12 tokens: fourteen inches of snow fell in riverdale ten inches fell in alma
14 tokens: the interstate 80 at grassey sensor reported a peak wind gust of 58 mph
11 tokens: quarter size hail was reported near p highway near rocky point
34 tokens: an estimated 35 inches of rain fell causing water to flow over roadways
14 tokens: thunderstorm winds snapped a one to two foot diameter tree at chaparral
10 tokens: mud and debris were on interstate 15 at exit 64
12 tokens: a wind gust to 74 mph was reported at gallatin gateway 16se
58 tokens: torrential rainfall of 12 to 15 inches caused widespread flash flooding
19 tokens: measured wind gusts of 40 to 45 mph knocked down isolated tree limbs th
15 tokens: a tree was reported down on black hollow road in arlington due to thund
16 tokens: a trained weather spotter observed pennsized hail falling near state r
24 tokens: a foot of snow was reported in comstock park there were numerous report
22 tokens: local emergency management relayed a report of a tree down southwest of
8 tokens: carpet barn road was closed due to flooding
10 tokens: highway e near barker creek was closed due to flooding
6 tokens: flash flooding covered kelso cima road
24 tokens: approximately 10 vehicles were stuck in flood waters at david drive and
20 tokens: a light pole was blown down on the neil street onramp to westbound i74
6 tokens: lightning set fire to a house
13 tokens: street flooding was reported at orange street and market street near ho
10 tokens: a trained spotter measured a wind gust of 70 mph
9 tokens: several large tree limbs were blown down in gainesville
15 tokens: an nws employee reported heavy freezing rain causing very icy condition
39 tokens: frequent wind gusts of 30 to 40 mph resulted in multiple reports of tre
15 tokens: a wind gust to 67 mph was reported at bynum 13w the dellwo mcsn site
57 tokens: a short tornado track was determined along cr53 just north of its inter
19 tokens: numerous trees were blown down in the area along with numerous power ou
14 tokens: a severe thunderstorm producing winds estimated near 60 mph knocked do
13 tokens: wires were reported down on route 41 in sheffield due to thunderstorm v
10 tokens: golf ball size hail fell 1 mile south of alanreed
14 tokens: trees were blown down and roofs and siding were damaged in the laughlin

18 tokens: winds caused isolated damage removing the roof from a trailer home a wa
86 tokens: this was the second tornado to develop in northwest houston county spa
14 tokens: bar pilot dispatcher reported a brief waterspout in the columbia river
12 tokens: public reported thor road flooding near track road just south of pelion
7 tokens: penny size hail was reported via mping
33 tokens: usaf wind tower 1007 recorded a peak wind gust over 35 knots near play
23 tokens: the asos at vero beach airport kvrb recorded peak winds of 38 knots as
11 tokens: estimated wind gust of 60 mph reported north of hazel green
10 tokens: the wind gust was measured by a davis weather system
17 tokens: a few dime to quarter sized hailstones fell along with brief heavy rain
10 tokens: a large tree was downed in dartmouth blocking reed road
16 tokens: a tree was snapped off at its base and the fordville scale house was bl
17 tokens: the grand canyon airport asos measured a peak wind gust of 59 mph at 20
21 tokens: trees were toppled and power lines brought down by wind gusts estimated
93 tokens: weather observers across cumberland county reported snowfall amounts o
11 tokens: local media relayed a report of roof damage to a home
19 tokens: heavy rainfall over southern sections of alexandria produced flooded ro
39 tokens: strong north winds behind a cold front pushed the tide levels to or bet
21 tokens: two to three inches of snow and gusty southeast winds up to 25 mph crea
68 tokens: weather observers across edgar county reported snowfall amounts of 4 to
11 tokens: a picutre of quarter size hail was received through social media
13 tokens: multiple power poles were knocked down along patton road relayed via so
8 tokens: power lines were knocked down on huntsville road
20 tokens: a large tree was knocked down and blocking the road on mt olive drive a
14 tokens: a tree was knocked down along al 277 in stevenson time estimated by rad
7 tokens: funnel cloud reported did not touch down
9 tokens: strong winds hit the grand forks air force base
8 tokens: a tree was knocked down onto a home
21 tokens: a 30 by 40 foot section of metal roofing was blown onto the intersectio
21 tokens: two to three inches of snow and gusty southeast winds up to 25 mph crea
21 tokens: two to three inches of snow and gusty southeast winds up to 25 mph crea
8 tokens: trees were knocked down on paint hollow road
7 tokens: trees were knocked down on bellview road
7 tokens: trees were knocked down on blanche road
12 tokens: large trees were downed by severe storm winds in the spring area
22 tokens: there was street flooding in the town of coldspring there was also wat
8 tokens: trees were blown down across county road 65
22 tokens: a social media post from haydenville showed that 7 inches of snow fell
10 tokens: winds damaged a lightweight tin roof fences and utility poles
42 tokens: polk county fire rescue reported that multiple 911 calls were received
8 tokens: several trees uprooted in the town of vincent
43 tokens: a spotter west of hebron reported 4 inches of snow in that area another
10 tokens: several trees uprooted in and near the cedar bluff community
14 tokens: six large trees were knocked down along cr 23 between red bay and vina

41 tokens: the cocorahs observer southwest of bethel measured 5 inches of snow a s
25 tokens: the airport at kcvg measured a 47 mph gust as did a cwop station in bu
10 tokens: a peak wind of 52 kt 60 mph was reported
25 tokens: the wind sensor at the rawlins airport measured sustained winds of 40 m
13 tokens: several trees uprooted along highway 43 between tierece road and old fa
18 tokens: the observer near new carlisle measured 2 inches of snow another observ
12 tokens: several trees uprooted and power lines downed in the coates bend commun
40 tokens: a public report southeast of washington court house showed that 6 inche
10 tokens: the cooperative observer near alpine measured 38 inches of snow
37 tokens: a nws employee near ogden measured 3 inches of snow another employee no
12 tokens: the odot county garage west of springfield measured an inch of snow
12 tokens: numerous trees uprooted and power lines downed in the city of wetumpka
16 tokens: the nedor sensor at dalton on highway 385 measured sustained winds of 4
17 tokens: the nedor sensor at interstate 80 mile post 50 measured sustained winds
9 tokens: trace amounts of ice were reported around the county
11 tokens: this wind gust was measured at a lavaca bay mesonet site
3 tokens: no damage reported
16 tokens: the public estimated 075 inch hail in wind point and relayed their rep
17 tokens: a home weather station near new port richy measured a wind gust to 48
20 tokens: rainfall totals generally ranged from 5 to 9 inches across the county r
32 tokens: snow melt and around an inch of rainfall produced an ice jam on the ker
21 tokens: blizzard conditions were estimated based on observations nearby snowfa
23 tokens: the patrick air force base awos kcof recorded a peak gust of 34 knots t
16 tokens: flash flooding was reported at stevens and hazelwood in borger barricad
18 tokens: a home weather station located on indian shores beach measured a wind g
15 tokens: a home weather station near belleair measured a wind gust of 38 knots 4
90 tokens: torrential rainfall of 8 to 12 inches caused widespread flash flooding
12 tokens: visibility was estimated to be around onequarter mile based on observat
17 tokens: a usgs rain gauge near lakewood ranch measured 752 inches of rain in a
34 tokens: rainfall totals generally ranged from 3 to 6 inches across the county s
58 tokens: heavy rainfall of 7 to 10 inches caused widespread flash flooding acros
149 tokens: torrential rainfall of 10 to 14 inches caused widespread flash flooding
44 tokens: heavy rainfall of 9 to 12 inches caused widespread flash flooding acros
197 tokens: torrential rainfall of 9 to 12 inches caused widespread flash flooding
21 tokens: the tidal gauge at annapolis indicated moderate flooding water levels t
18 tokens: heavy rainfall of 5 to 6 inches caused widespread flash flooding across
130 tokens: torrential rainfall of 9 to 12 inches caused widespread flash flooding
41 tokens: rainfall totals generally ranged from 5 to 11 inches across the county
27 tokens: rainfall totals generally ranged from 7 to 10 inches across the county
22 tokens: heavy rainfall caused street flooding in rhinelander mainly west of the
28 tokens: rainfall totals generally ranged from 3 to 6 inches across the county r
30 tokens: rainfall totals generally ranged from 1 inch to 3 inches across the cou
12 tokens: rainfall totals generally ranged from 2 to 4 inches across the county
36 tokens: the mount pleasant police department reported longpoint road near needl

9 tokens: trace amounts of ice were reported around the county
11 tokens: severe storm winds caused tree damage in the town of deanville
18 tokens: there were numerous reports of trees and power lines down throughout d
37 tokens: wind chills of 35 to 40 below zero were common across olmsted county o
12 tokens: there were a few trees down in the county including in Grundy
12 tokens: flash flooding was reported along John B Carter Road southeast of Fayette
19 tokens: blizzard conditions were reported at Reagan National Airport snowfall r
5 tokens: thunderstorm winds damaged a fence
10 tokens: just over two inches of rain fell due to thunderstorms
13 tokens: several roads closed due to flash flooding with some debris washed into
11 tokens: a trained spotter estimated 60 mile per hour winds in Bridgeport
20 tokens: a public report of quarter size hail in crossroads was relayed by broad
8 tokens: snowfall totaled up to 225 inches near Dayton
13 tokens: thunderstorm winds caused tree damage including a large tree blown acro
12 tokens: a brief waterspout over northern Sarasota Bay was reported by the publ
15 tokens: thunderstorm winds blew the roof off a mobile home and also blew down p
14 tokens: a wind gust of 58 mph was recorded at the Judith Gap dot site
11 tokens: windows were knocked out at the Tom Steed Reservoir bait shop
10 tokens: a gust of 61 mph was recorded across the area
12 tokens: a wind gust of 59 mph was recorded at the Baker Airport
11 tokens: thunderstorm winds destroyed two grain bins and damaged a light pole
70 tokens: a NWS survey crew found 25 homes that sustained damage mainly to pool
11 tokens: branches were reported down in the northern end of Pocahontas County
9 tokens: the Butler AWOs reported a wind chill of 12
32 tokens: two to six inches of snow fell across the region the larger totals were
27 tokens: less than an inch to two inches of snow fell across the region the larg
13 tokens: the ASOS at Columbia Metro Airport reported a wind gust of 51 mph
9 tokens: almost three inches of heavy rainfall fell with thunderstorms
7 tokens: several trees downed due to thunderstorm winds
60 tokens: between 18 and 30 inches of snow fell near the Sierra Crest and in
18 tokens: nickel to quarter sized hail fell and nearly covered the ground over t
11 tokens: two and a half inches of rain fell due to thunderstorms
7 tokens: over two inches fell due to thunderstorms
8 tokens: several trees taken down due to thunderstorm winds
9 tokens: hail with a thunderstorm was measured at 75 inches
9 tokens: hail was measured at 34 inch from a thunderstorm
28 tokens: snowfall amounts of 6 to 7 inches were measured above the 5000 foot lev
26 tokens: snowfall amounts of 6 to 10 inches were measured across the area wind g
27 tokens: snowfall amounts of 1 to 3 inches were measured across the area wind g
17 tokens: county comms reported multiple trees and power lines blown down near h
31 tokens: heavy rain resulted in flash flooding at a couple of locations in Ashe
14 tokens: two trees were blown down at a residence approximately 4 miles north
8 tokens: one tree was reported down on Morganton Road
24 tokens: four to six inches of snow fell across the region the larger totals were

24 tokens: the wydot sensor at dana ridge measured sustained winds of 40 mph or h
7 tokens: several trees downed due to thunderstorm winds
11 tokens: trees and wires downed on centerville road due to thunderstorm winds
38 tokens: snowfall amounts between 25 and 38 inches were received across frederic
8 tokens: quarter to ping pong ball sized hail fell
7 tokens: flooding was reported on mirror lake drive
12 tokens: lightning struck a tree which fell on a house damaging several rooms
32 tokens: two to six inches of snow fell across the region the larger totals were
10 tokens: several trees taken down due to thunderstorm winds in bridgeton
10 tokens: numerous trees taken down due to thunderstorm winds in fairton
10 tokens: several trees down on straughn mill road near interstate 295
9 tokens: almost three inches of rain was measured with thunderstorms
7 tokens: trees taken down by thunderstorm wind gusts
6 tokens: a house was struck by lightning
10 tokens: a 63 mph wind gust was measured from a thunderstorm
9 tokens: a funnel cloud was observed at 9148 centerville road
13 tokens: public reported heavy rainfall of 211 inches so far beginning time rad
13 tokens: power pole and wires taken down due to thunderstorm winds trees also do
8 tokens: hail was estimated at 1 inch in diameter
37 tokens: the department of highways relayed a report of flash flooding at highwa
8 tokens: trees and wires downed on bunker hill road
12 tokens: a 53 mph thunderstorm wind gust was measured by a weatherflow site
19 tokens: severe thunderstorm wind gusts around 60 mph downed trees along south r
9 tokens: severe thunderstorm wind gusts downed trees along oakley road
12 tokens: numerous wires were reported down at route 27 at davils mill rd
15 tokens: fd reported a tree blown down on a home causing significant damage on t
18 tokens: one shallow rooted oak tree was blown over wind speeds were estimated t
22 tokens: snow accumulated 3 to 6 inches including 60 inches near pukwana the sno
48 tokens: a bow echo producing winds estimated at 80 mph produced a corridor of v
11 tokens: a tree fell and damaged utility equipment off of mcdaniel road
36 tokens: social media reports of at least a couple of dozen trees blown down ac
47 tokens: county comms and highway patrol reported multiple trees blown down acro
39 tokens: westerly winds behind a cold front reach sustained speed of 40 to 45 mp
15 tokens: a few trees were blown down in the cranfield liberty road area south of
9 tokens: public reported quarter size hail on sam dee rd
63 tokens: the stream gauge on potomac river at point of rocks reached flood stage
10 tokens: old charles town road was closed near the opequon creek
17 tokens: spiky hail around ping pong ball size was reported near the intersectio
39 tokens: light snow began around noon on january 17th then continued through the
6 tokens: several roads flooded in the area
20 tokens: dallas center fire department reported hail just under ping pong ball :
39 tokens: westerly winds behind a cold front reach sustained speed of 40 to 45 mp
23 tokens: trees and power lines were blown down in ocilla in addition a house fi
11 tokens: trees damaged an suv and a mobile home damage was estimated

```
10 tokens: spotter reported brief 34 inch hail off old river rd
10 tokens: spotters reported around half of an inch across the county
39 tokens: while lingering light snow after a blizzard produced little additional
12 tokens: a large cedar tree about two feet in diameter was reported down
23 tokens: multiple large trees uprooted and blown onto power lines resulting in t
12 tokens: a large tree was reported down across calhoun st in west baltimore
44 tokens: county comms and public via social media reported multiple trees blown
13 tokens: the wydot sensor at strouss hill measured peak wind gusts of 58 mph
27 tokens: the wydot sensor at interstate 80 mile post 249 measured sustained wind
```

View the first few preprocessed training documents.

```
documentsTrain(1:5)
```

```
ans =
  5×1 tokenizedDocument:

    7 tokens: large tree down between plantersville and nettleton
   37 tokens: one to two feet of deep standing water developed on a street on the win
   13 tokens: nws columbia relayed a report of trees blown down along tom hall st
   13 tokens: media reported two trees blown down along i40 in the old fort area
   14 tokens: a few tree limbs greater than 6 inches down on hwy 18 in roseland
```

Convert Document to Sequences

To input the documents into an LSTM network, use a word encoding to convert the documents into sequences of numeric indices.


To create a word encoding, use the `wordEncoding` function.

```
enc = wordEncoding(documentsTrain);
```

The next conversion step is to pad and truncate documents so they are all the same length. The `trainingOptions` function provides options to pad and truncate input sequences automatically. However, these options are not well suited for sequences of word vectors. Instead, pad and truncate the sequences manually. If you *left-pad* and truncate the sequences of word vectors, then the training might improve.

To pad and truncate the documents, first choose a target length, and then truncate documents that are longer than it and left-pad documents that are shorter than it. For best results, the target length should be short without discarding large amounts of data. To find a suitable target length, view a histogram of the training document lengths.

```
documentLengths = doclength(documentsTrain);  
figure  
histogram(documentLengths)  
title("Document Lengths")  
xlabel("Length")  
ylabel("Number of Documents")
```



Most of the training documents have fewer than 75 tokens. Use this as your target length for truncation and padding.

Convert the documents to sequences of numeric indices using `doc2sequence`. To truncate or left-pad the sequences to have length 75, set the 'Length' option to 75.

```
XTrain = doc2sequence(enc,documentsTrain,'Length',75);  
XTrain(1:5)
```

```
ans = 5x1 cell array  
    {1x75 double}  
    {1x75 double}  
    {1x75 double}  
    {1x75 double}  
    {1x75 double}
```

Convert the validation documents to sequences using the same options.

```
XValidation = doc2sequence(enc,documentsValidation,'Length',75);
```

Create and Train LSTM Network

Define the LSTM network architecture. To input sequence data into the network, include a sequence input layer and set the input size to 1. Next, include a word embedding layer of dimension 100 and the same number of words as the word encoding. Next, include an LSTM layer and set the number of hidden units to 180. To use the LSTM layer for a sequence-to-label classification problem, set the output mode to 'last'. Finally, add a fully connected layer with the same size as the number of classes, a softmax layer, and a classification layer.

```
inputSize = 1;  
embeddingDimension = 100;  
numWords = enc.NumWords;  
numHiddenUnits = 180;  
numClasses = numel(categories(YTrain));
```

```
layers = [ ...  
    sequenceInputLayer(inputSize)  
    wordEmbeddingLayer(embeddingDimension,numWords)  
    lstmLayer(numHiddenUnits,'OutputMode','last')  
    fullyConnectedLayer(numClasses)  
    softmaxLayer  
    classificationLayer]
```

```
layers =  
6x1 Layer array with layers:
```

1	'	Sequence Input	Sequence input with 1 dimensions
2	'	Word Embedding Layer	Word embedding layer with 100 dimensions and 169
3	'	LSTM	LSTM with 180 hidden units


```
4 '' Fully Connected          39 fully connected layer
5 '' Softmax                  softmax
6 '' Classification Output    crossentropyex
```


Specify the training options. Set the solver to 'adam', train for 10 epochs, and set the gradient threshold to 1. Set the initial learn rate to 0.01. To monitor the training progress, set the 'Plots' option to 'training-progress'. Specify the validation data using the 'ValidationData' option. To suppress verbose output, set 'Verbose' to false.

By default, `trainNetwork` uses a GPU if one is available (requires Parallel Computing Toolbox™ and a CUDA® enabled GPU with compute capability 3.0 or higher). Otherwise, it uses the CPU. To specify the execution environment manually, use the 'ExecutionEnvironment' name-value pair argument of `trainingOptions`. Training on a CPU can take significantly longer than training on a GPU.

```
options = trainingOptions('adam', ...
    'MaxEpochs',10, ...
    'GradientThreshold',1, ...
    'InitialLearnRate',0.01, ...
    'ValidationData',{XValidation,YValidation}, ...
    'Plots','training-progress', ...
    'Verbose',false);
```

Train the LSTM network using the `trainNetwork` function.

```
net = trainNetwork(XTrain,YTrain,layers,options);
```



Test LSTM Network

To test the LSTM network, first prepare the test data in the same way as the training data. Then make predictions on the preprocessed test data using the trained LSTM network net.

Preprocess the test data using the same steps as the training documents.

```
textDataTest = lower(textDataTest);
documentsTest = tokenizedDocument(textDataTest);
documentsTest = erasePunctuation(documentsTest);
```

Convert the test documents to sequences using `doc2sequence` with the same options as when creating the training sequences.

```
XTest = doc2sequence(enc, documentsTest, 'Length', 75);
XTest(1:5)
```

```
ans = 5×1 cell array
    {1×75 double}
    {1×75 double}
    {1×75 double}
    {1×75 double}
    {1×75 double}
```

Classify the test documents using the trained LSTM network.

```
YPred = classify(net,XTest);
```

Calculate the classification accuracy. The accuracy is the proportion of labels that the network predicts correctly.

```
accuracy = sum(YPred == YTest)/numel(YPred)
```

```
accuracy = 0.8691
```

Predict Using New Data

Classify the event type of three new weather reports. Create a string array containing the new weather reports.

```
reportsNew = [ ...
    "Lots of water damage to computer equipment inside the office."
    "A large tree is downed and blocking traffic outside Apple Hill."
    "Damage to many car windshields in parking lot."];
```

Preprocess the text data using the preprocessing steps as the training documents.

```
documentsNew = preprocessText(reportsNew);
```

Convert the text data to sequences using `doc2sequence` with the same options as when creating the training sequences.

```
XNew = doc2sequence(enc,documentsNew,'Length',75);
```

Classify the new sequences using the trained LSTM network.

```
[labelsNew,score] = classify(net,XNew);
```

Show the weather reports with their predicted labels.

```
[reportsNew string(labelsNew)]
```

```
ans = 3x2 string array
    "Lots of water damage to computer equipment inside the office."    "Flash Flood"
    "A large tree is downed and blocking traffic outside Apple Hill."  "Thunderstorm"
    "Damage to many car windshields in parking lot."                  "Hail"
```

Preprocessing Function

The function `preprocessText` performs these steps:

- 1 Tokenize the text using `tokenizedDocument`.
- 2 Convert the text to lowercase using `lower`.
- 3 Erase the punctuation using `erasePunctuation`.

```
function documents = preprocessText(textData)

% Tokenize the text.
documents = tokenizedDocument(textData);

% Convert to lowercase.
documents = lower(documents);

% Erase punctuation.
documents = erasePunctuation(documents);

end
```

See Also

`doc2sequence` | `fastTextWordEmbedding` | `lstmLayer` | `sequenceInputLayer` | `tokenizedDocument` | `trainNetwork` | `trainingOptions` | `wordEmbeddingLayer` | `wordcloud`

Related Examples

- “Classify Text Data Using Convolutional Neural Network” on page 2-76
- “Classify Out-of-Memory Text Data Using Deep Learning” on page 2-87
- “Generate Text Using Deep Learning” (Deep Learning Toolbox)
- “Word-By-Word Text Generation Using Deep Learning” on page 2-101
- “Create Simple Text Model for Classification” on page 2-2

- “Analyze Text Data Using Topic Models” on page 2-18
- “Analyze Text Data Using Multiword Phrases” on page 2-9
- “Train a Sentiment Classifier” on page 2-43
- “Sequence Classification Using Deep Learning” (Deep Learning Toolbox)
- “Deep Learning in MATLAB” (Deep Learning Toolbox)

Classify Text Data Using Convolutional Neural Network

This example shows how to classify text data using a convolutional neural network.

To classify text data using convolutions, you must convert the text data into images. To do this, pad or truncate the observations to have constant length S and convert the documents into sequences of word vectors of length C using a word embedding. You can then represent a document as a 1-by- S -by- C image (an image with height 1, width S , and C channels).

To convert text data from a CSV file to images, create a `tabularTextDatastore` object. Then convert the data read from the `tabularTextDatastore` object to images for deep learning by calling `transform` with a custom transformation function. The `transformTextData` function, listed at the end of the example, takes data read from the datastore and a pretrained word embedding, and converts each observation to an array of word vectors.

This example trains a network with 1-D convolutional filters of varying widths. The width of each filter corresponds to the number of words the filter can see (the n-gram length). The network has multiple branches of convolutional layers, so it can use different n-gram lengths.

Load Pretrained Word Embedding

Load the pretrained `fastText` word embedding. This function requires the Text Analytics Toolbox™ Model for *fastText* English 16 Billion Token Word Embedding support package. If this support package is not installed, then the function provides a download link.

```
emb = fastTextWordEmbedding;
```

Load Data

Create a tabular text datastore from the data in `weatherReportsTrain.csv`. Read the data from the "event_narrative" and "event_type" columns only.

```
filenameTrain = "weatherReportsTrain.csv";  
textName = "event_narrative";  
labelName = "event_type";  
ttdsTrain = tabularTextDatastore(filenameTrain, 'SelectedVariableNames', [textName labelName]);
```

Preview the datastore.

```
ttdsTrain.ReadSize = 8;
preview(ttdsTrain)
```

```
ans=8×2 table
```

```
'Large tree down between Plantersville and Nettleton.'
'One to two feet of deep standing water developed on a street on the Winthrop Univer
'NWS Columbia relayed a report of trees blown down along Tom Hall St.'
'Media reported two trees blown down along I-40 in the Old Fort area.'
'A few tree limbs greater than 6 inches down on HWY 18 in Roseland.'
'Awning blown off a building on Lamar Avenue. Multiple trees down near the intersec
'Tin roof ripped off house on Old Memphis Road near Billings Drive. Several large t
'Powerlines down at Walnut Grove and Cherry Lane roads.'
```

Create a custom transform function that converts data read from the datastore to a table containing the predictors and the responses. The `transformTextData` function, listed at the end of the example, takes the data read from a `tabularTextDatastore` object and returns a table of predictors and responses. The predictors are 1-by-`sequenceLength`-by-`C` arrays of word vectors given by the word embedding `emb`, where `C` is the embedding dimension. The responses are categorical labels over the classes in `classNames`.

Read the labels from the training data using the `readLabels` function, listed at the end of the example, and find the unique class names.

```
labels = readLabels(ttdsTrain, labelName);
classNames = unique(labels);
numObservations = numel(labels);
```

Transform the datastore using `transformTextData` function and specify a sequence length of 100.

```
sequenceLength = 100;
tdsTrain = transform(ttdsTrain, @(data) transformTextData(data, sequenceLength, emb, classNames));
```

```
tdsTrain =
TransformedDatastore with properties:
```

```
UnderlyingDatastore: [1×1 matlab.io.datastore.TabularTextDatastore]
Transforms: {@(data)transformTextData(data, sequenceLength, emb, classNames)}
IncludeInfo: 0
```

Preview the transformed datastore. The predictors are 1-by- S -by- C arrays, where S is the sequence length and C is the number of features (the embedding dimension). The responses are the categorical labels.

```
preview(tdsTrain)
```

```
ans=8x2 table
      predictors      responses
-----
[1x100x300 single]  Thunderstorm Wind
[1x100x300 single]  Heavy Rain
[1x100x300 single]  Thunderstorm Wind
[1x100x300 single]  Thunderstorm Wind
[1x100x300 single]  Thunderstorm Wind
[1x100x300 single]  Thunderstorm Wind
[1x100x300 single]  Thunderstorm Wind
[1x100x300 single]  Thunderstorm Wind
```

Create a transformed datastore containing the validation data in `weatherReportsValidation.csv` using the same steps.

```
filenameValidation = "weatherReportsValidation.csv";
ttdsValidation = tabularTextDatastore(filenameValidation, 'SelectedVariableNames', [textl
tdsValidation = transform(ttdsValidation, @(data) transformTextData(data, sequenceLength
tdsValidation =
    TransformedDatastore with properties:
        UnderlyingDatastore: [1x1 matlab.io.datastore.TabularTextDatastore]
        Transforms: {@(data)transformTextData(data, sequenceLength, emb, classNames)}
        IncludeInfo: 0
```

Define Network Architecture

Define the network architecture for the classification task.

The following steps describe the network architecture.

- Specify an input size of 1-by- S -by- C , where S is the sequence length and C is the number of features (the embedding dimension).

- For the n-gram lengths 2, 3, 4, and 5, create blocks of layers containing a convolutional layer, a batch normalization layer, a ReLU layer, a dropout layer, and a max pooling layer.
- For each block, specify 200 convolutional filters of size 1-by- N and pooling regions of size 1-by- S , where N is the n-gram length.
- Connect the input layer to each block and concatenate the outputs of the blocks using a depth concatenation layer.
- To classify the outputs, include a fully connected layer with output size K , a softmax layer, and a classification layer, where K is the number of classes.

First, in a layer array, specify the input layer, the first block for unigrams, the depth concatenation layer, the fully connected layer, the softmax layer, and the classification layer.

```
numFeatures = emb.Dimension;
inputSize = [1 sequenceLength numFeatures];
numFilters = 200;
```

```
ngramLengths = [2 3 4 5];
numBlocks = numel(ngramLengths);
```

```
numClasses = numel(classNames);
```

Create a layer graph containing the input layer. Set the normalization option to 'none' and the layer name to 'input'.

```
layer = imageInputLayer(inputSize, 'Normalization', 'none', 'Name', 'input');
lgraph = layerGraph(layer);
```

For each of the n-gram lengths, create a block of convolution, batch normalization, ReLU, dropout, and max pooling layers. Connect each block to the input layer.

```
for j = 1:numBlocks
    N = ngramLengths(j);

    block = [
        convolution2dLayer([1 N], numFilters, 'Name', "conv"+N, 'Padding', 'same')
        batchNormalizationLayer('Name', "bn"+N)
        reluLayer('Name', "relu"+N)
        dropoutLayer(0.2, 'Name', "drop"+N)
        maxPooling2dLayer([1 sequenceLength], 'Name', "max"+N)];

    lgraph = addLayers(lgraph, block);
```

```

    lgraph = connectLayers(lgraph, 'input', "conv"+N);
end


```

View the network architecture in a plot.

```

figure
plot(lgraph)
title("Network Architecture")

```



Add the depth concatenation layer, the fully connected layer, the softmax layer, and the classification layer.

```

layers = [
    depthConcatenationLayer(numBlocks, 'Name', 'depth')

```

```

fullyConnectedLayer(numClasses, 'Name', 'fc')
softmaxLayer('Name', 'soft')
classificationLayer('Name', 'classification')];


```

```
lgraph = addLayers(lgraph, layers);
```

```

figure
plot(lgraph)
title("Network Architecture")


```



Connect the max pooling layers to the depth concatenation layer and view the final network architecture in a plot.

```
for j = 1:numBlocks
    N = ngramLengths(j);
    lgraph = connectLayers(lgraph,"max"+N,"depth/in"+j);
end

figure
plot(lgraph)
title("Network Architecture")
```



Train Network

Specify the training options:

- Train for 10 epochs with a mini-batch size of 128.


- Validate the network at each epoch by setting the validation frequency to the number of iterations per epoch.
- Display the training progress plot and suppress the verbose output.

```
miniBatchSize = 128;
numIterationsPerEpoch = floor(numObservations/miniBatchSize);
```

```
options = trainingOptions('adam', ...
    'MaxEpochs',10, ...
    'MiniBatchSize',miniBatchSize, ...
    'ValidationData',tdsValidation, ...
    'ValidationFrequency',numIterationsPerEpoch, ...
    'Plots','training-progress', ...
    'Verbose',false);
```

Train the network using the `trainNetwork` function.

```
net = trainNetwork(tdsTrain,lgraph,options);
```



Test Network

Create a transformed datastore containing the held-out test data in `weatherReportsTest.csv`.

```
filenameTest = "weatherReportsTest.csv";
ttdsTest = tabularTextDatastore(filenameTest, 'SelectedVariableNames', [textName labelName]);

tdsTest = transform(ttdsTest, @(data) transformTextData(data, sequenceLength, emb, classNames));

tdsTest =
    TransformedDatastore with properties:
        UnderlyingDatastore: [1x1 matlab.io.datastore.TabularTextDatastore]
        Transforms: {@(data)transformTextData(data, sequenceLength, emb, classNames)}
        IncludeInfo: 0
```

Read the labels from the `tabularTextDatastore`.

```
labelsTest = readLabels(ttdsTest, labelName);
YTest = categorical(labelsTest, classNames);
```

Make predictions on the test data using the trained network.

```
YPred = classify(net, tdsTest);
```

Calculate the classification accuracy on the test data.

```
accuracy = mean(YPred == YTest)
accuracy = 0.8670
```

Functions

The `readLabels` function creates a copy of the `tabularTextDatastore` object `ttds` and reads the labels from the `labelName` column.

```
function labels = readLabels(ttds, labelName)

ttdsNew = copy(ttds);
ttdsNew.SelectedVariableNames = labelName;
tbl = readall(ttdsNew);
labels = tbl.(labelName);

end
```

The `transformTextData` function takes the data read from a `tabularTextDatastore` object and returns a table of predictors and responses. The predictors are 1-by-`sequenceLength`-by-`C` arrays of word vectors given by the word embedding `emb`, where `C` is the embedding dimension. The responses are categorical labels over the classes in `classNames`.

```
function dataTransformed = transformTextData(data,sequenceLength,emb,classNames)

% Preprocess documents.
textData = data{:,1};
textData = lower(textData);
documents = tokenizedDocument(textData);

% Convert documents to embeddingDimension-by-sequenceLength-by-1 images.
predictors = doc2sequence(emb,documents,'Length',sequenceLength);

% Reshape images to be of size 1-by-sequenceLength-embeddingDimension.
predictors = cellfun(@(X) permute(X,[3 2 1]),predictors,'UniformOutput',false);

% Read labels.
labels = data{:,2};
responses = categorical(labels,classNames);

% Convert data to table.
dataTransformed = table(predictors,responses);

end
```

See Also

[batchNormalizationLayer](#) | [convolution2dLayer](#) | [doc2sequence](#) | [fastTextWordEmbedding](#) | [layerGraph](#) | [tokenizedDocument](#) | [trainNetwork](#) | [trainingOptions](#) | [wordEmbedding](#) | [wordcloud](#)

Related Examples

- “Classify Text Data Using Deep Learning” on page 2-53
- “Classify Out-of-Memory Text Data Using Deep Learning” on page 2-87
- “Create Simple Text Model for Classification” on page 2-2
- “Analyze Text Data Using Topic Models” on page 2-18

- “Analyze Text Data Using Multiword Phrases” on page 2-9
- “Train a Sentiment Classifier” on page 2-43
- “Sequence Classification Using Deep Learning” (Deep Learning Toolbox)
- “Deep Learning in MATLAB” (Deep Learning Toolbox)

Classify Out-of-Memory Text Data Using Deep Learning

This example shows how to classify out-of-memory text data with a deep learning network using a transformed datastore.

A transformed datastore transforms or processes data read from an underlying datastore. You can use a transformed datastore as a source of training, validation, test, and prediction data sets for deep learning applications. Use transformed datastores to read out-of-memory data or to perform specific preprocessing operations when reading batches of data.

When training the network, the software creates mini-batches of sequences of the same length by padding, truncating, or splitting the input data. The `trainingOptions` function provides options to pad and truncate input sequences, however, these options are not well suited for sequences of word vectors. Furthermore, this function does not support padding data in a custom datastore. Instead, you must pad and truncate the sequences manually. If you *left-pad* and truncate the sequences of word vectors, then the training might improve.

The “Classify Text Data Using Deep Learning” on page 2-53 example manually truncates and pads all the documents to the same length. This process adds lots of padding to very short documents and discards lots of data from very long documents.

Alternatively, to prevent adding too much padding or discarding too much data, create a transformed datastore that inputs mini-batches into the network. The datastore created in this example converts mini-batches of documents to sequences or word indices and left-pads each mini-batch to the length of the longest document in the mini-batch.

Load Pretrained Word Embedding

The datastore requires a word embedding to convert documents to sequences of vectors. Load a pretrained word embedding using `fastTextWordEmbedding`. This function requires Text Analytics Toolbox™ Model for *fastText English 16 Billion Token Word Embedding* support package. If this support package is not installed, then the function provides a download link.

```
emb = fastTextWordEmbedding;
```

Load Data

Create a tabular text datastore from the data in `weatherReportsTrain.csv`. Specify to read the data from the “event_narrative” and “event_type” columns only.

```
filenameTrain = "weatherReportsTrain.csv";
textName = "event_narrative";
labelName = "event_type";
ttdsTrain = tabularTextDatastore(filenameTrain, 'SelectedVariableNames', [textName labelName]);
```

View a preview of the datastore.

```
preview(ttdsTrain)
```

```
ans=8x2 table
```

```
'Large tree down between Plantersville and Nettleton.'
'One to two feet of deep standing water developed on a street on the Winthrop University campus.'
'NWS Columbia relayed a report of trees blown down along Tom Hall St.'
'Media reported two trees blown down along I-40 in the Old Fort area.'
'A few tree limbs greater than 6 inches down on HWY 18 in Roseland.'
'Awning blown off a building on Lamar Avenue. Multiple trees down near the intersection of Lamar and Old Memphis.'
'Tin roof ripped off house on Old Memphis Road near Billings Drive. Several large trees down near intersection of Old Memphis and Cherry Lane.'
'Powerlines down at Walnut Grove and Cherry Lane roads.'
```

Transform Datastore

Create a custom transform function that converts data read from the datastore to a table containing the predictors and the responses. The `transformTextData` function takes the data read from a `tabularTextDatastore` object and returns a table of predictors and responses. The predictors are C -by- S arrays of word vectors given by the word embedding `emb`, where C is the embedding dimension and S is the sequence length. The responses are categorical labels over the classes.

To get the class names, read the labels from the training data using the `readLabels` function, listed at the end of the example, and find the unique class names.

```
labels = readLabels(ttdsTrain, labelName);
classNames = unique(labels);
numObservations = numel(labels);
```

Because tabular text datastores can read multiple rows of data in a single read, you can process a full mini-batch of data in the transform function. To ensure that the transform function processes a full mini-batch of data, set the read size of the tabular text datastore to the mini-batch size that will be used for training.

```
miniBatchSize = 128;
ttdsTrain.ReadSize = miniBatchSize;
```

To convert the output of the tabular text data to sequences for training, transform the datastore using the transform function.

```
tdsTrain = transform(ttdsTrain, @(data) transformTextData(data,emb,classNames))
tdsTrain =
    TransformedDatastore with properties:
        UnderlyingDatastore: [1x1 matlab.io.datastore.TabularTextDatastore]
        Transforms: {@(data)transformTextData(data,emb,classNames)}
        IncludeInfo: 0
```

Preview of the transformed datastore. The predictors are C -by- S arrays, where S is the sequence length and C is the number of features (the embedding dimension). The responses are the categorical labels.

```
preview(tdsTrain)
ans=8x2 table
    predictors      responses
    _____      _____
    [300x164 single]  Thunderstorm Wind
    [300x164 single]  Heavy Rain
    [300x164 single]  Thunderstorm Wind
    [300x164 single]  Thunderstorm Wind
    [300x164 single]  Thunderstorm Wind
    [300x164 single]  Thunderstorm Wind
    [300x164 single]  Thunderstorm Wind
    [300x164 single]  Thunderstorm Wind
```

Create a transformed datastore containing the validation data in `weatherReportsValidation.csv` using the same steps.

```
filenameValidation = "weatherReportsValidation.csv";
ttdsValidation = tabularTextDatastore(filenameValidation,'SelectedVariableNames',[textl
ttdsValidation.ReadSize = miniBatchSize;
tdsValidation = transform(ttdsValidation, @(data) transformTextData(data,emb,classNames
tdsValidation =
    TransformedDatastore with properties:
```

```
UnderlyingDatastore: [1x1 matlab.io.datastore.TabularTextDatastore]
  Transforms: {@(data)transformTextData(data,emb,classNames)}
  IncludeInfo: 0
```

Create and Train LSTM Network

Define the LSTM network architecture. To input sequence data into the network, include a sequence input layer and set the input size to the embedding dimension. Next, include an LSTM layer with 180 hidden units. To use the LSTM layer for a sequence-to-label classification problem, set the output mode to 'last'. Finally, add a fully connected layer with output size equal to the number of classes, a softmax layer, and a classification layer.

```
numFeatures = emb.Dimension;
numHiddenUnits = 180;
numClasses = numel(classNames);
layers = [ ...
    sequenceInputLayer(numFeatures)
    lstmLayer(numHiddenUnits,'OutputMode','last')
    fullyConnectedLayer(numClasses)
    softmaxLayer
    classificationLayer];
```

Specify the training options. Specify the solver to be 'adam' and the gradient threshold to be 2. The datastore does not support shuffling, so set 'Shuffle', to 'never'. Validate the network once per epoch. To monitor the training progress, set the 'Plots' option to 'training-progress'. To suppress verbose output, set 'Verbose' to false.

By default, `trainNetwork` uses a GPU if one is available (requires Parallel Computing Toolbox™ and a CUDA® enabled GPU with compute capability 3.0 or higher). Otherwise, it uses the CPU. To specify the execution environment manually, use the 'ExecutionEnvironment' name-value pair argument of `trainingOptions`. Training on a CPU can take significantly longer than training on a GPU.


```
numIterationsPerEpoch = floor(numObservations / miniBatchSize);

options = trainingOptions('adam', ...
    'MaxEpochs',15, ...
    'MiniBatchSize',miniBatchSize, ...
    'GradientThreshold',2, ...
    'Shuffle','never', ...
    'ValidationData',tdsValidation, ...
    'ValidationFrequency',numIterationsPerEpoch, ...
```

```
'Plots', 'training-progress', ...
'Verbose', false);
```

Train the LSTM network using the `trainNetwork` function.

```
net = trainNetwork(tdsTrain, layers, options);
```



Test LSTM Network

Create a transformed datastore containing the held-out test data in `weatherReportsTest.csv`.

```
filenameTest = "weatherReportsTest.csv";
ttdsTest = tabularTextDatastore(filenameTest, 'SelectedVariableNames', [textName labelName]);
ttdsTest.ReadSize = miniBatchSize;
tdsTest = transform(ttdsTest, @(data) transformTextData(data, emb, classNames))

tdsTest =
    TransformedDatastore with properties:
```

```
UnderlyingDatastore: [1x1 matlab.io.datastore.TabularTextDatastore]
  Transforms: {@(data)transformTextData(data,emb,classNames)}
  IncludeInfo: 0
```

Read the labels from the `tabularTextDatastore`.

```
labelsTest = readLabels(ttdsTest,labelName);
YTest = categorical(labelsTest,classNames);
```

Make predictions on the test data using the trained network.

```
YPred = classify(net,tdsTest,'MiniBatchSize',miniBatchSize);
```

Calculate the classification accuracy on the test data.

```
accuracy = mean(YPred == YTest)
```

```
accuracy = 0.8293
```

Functions

The `readLabels` function creates a copy of the `tabularTextDatastore` object `ttds` and reads the labels from the `labelName` column.

```
function labels = readLabels(ttds,labelName)
```

```
ttdsNew = copy(ttds);
ttdsNew.SelectedVariableNames = labelName;
tbl = readall(ttdsNew);
labels = tbl.(labelName);
```

```
end
```

The `transformTextData` function takes the data read from a `tabularTextDatastore` object and returns a table of predictors and responses. The predictors are C -by- S arrays of word vectors given by the word embedding `emb`, where C is the embedding dimension and S is the sequence length. The responses are categorical labels over the classes in `classNames`.

```
function dataTransformed = transformTextData(data,emb,classNames)
```

```
% Preprocess documents.
textData = data{:,1};
```

```
textData = lower(textData);
documents = tokenizedDocument(textData);

% Convert to sequences.
predictors = doc2sequence(emb,documents);

% Read labels.
labels = data{:,2};
responses = categorical(labels,classNames);

% Convert data to table.
dataTransformed = table(predictors,responses);

end
```

See Also

[doc2sequence](#) | [fastTextWordEmbedding](#) | [lstmLayer](#) | [sequenceInputLayer](#) | [tokenizedDocument](#) | [trainNetwork](#) | [trainingOptions](#) | [wordEmbeddingLayer](#)

Related Examples

- “Create Simple Text Model for Classification” on page 2-2
- “Analyze Text Data Using Topic Models” on page 2-18
- “Analyze Text Data Using Multiword Phrases” on page 2-9
- “Train a Sentiment Classifier” on page 2-43
- “Sequence Classification Using Deep Learning” (Deep Learning Toolbox)
- “Deep Learning in MATLAB” (Deep Learning Toolbox)

Pride and Prejudice and MATLAB

This example shows how to train a deep learning LSTM network to generate text using character embeddings.

To train a deep learning network for text generation, train a sequence-to-sequence LSTM network to predict the next character in a sequence of characters. To train the network to predict the next character, specify the responses to be the input sequences shifted by one time step.

To use character embeddings, convert each training observation to a sequence of integers, where the integers index into a vocabulary of characters. Include a word embedding layer in the network which learns an embedding of the characters and maps the integers to vectors.

Load Training Data

Read the HTML code from The Project Gutenberg EBook of Pride and Prejudice, by Jane Austen and parse it using `webread` and `htmlTree`.

```
url = "https://www.gutenberg.org/files/1342/1342-h/1342-h.htm";  
code = webread(url);  
tree = htmlTree(code);
```

Extract the paragraphs by finding the `p` elements. Specify to ignore paragraph elements with class "toc" using the CSS selector `' :not(.toc) '`.

```
paragraphs = findElement(tree, 'p:not(.toc)');
```

Extract the text data from the paragraphs using `extractHTMLText`. and remove the empty strings.

```
textData = extractHTMLText(paragraphs);  
textData(textData == "") = [];
```

Remove strings shorter than 20 characters.

```
idx = strlength(textData) < 20;  
textData(idx) = [];
```

Visualize the text data in a word cloud.


```
newlineCharacter = compose("\x00B6");
whitespaceCharacter = compose("\x00B7");
textData = replace(textData,[newline " "],[newlineCharacter whitespaceCharacter]);
```

Loop over the text data and create a sequence of character indices representing the characters of each observation and a categorical sequence of characters for the responses. To denote the end of each observation, include the special character "␣" (end of text, "\x2403").

```
endOfTextCharacter = compose("\x2403");
numDocuments = numel(textData);
for i = 1:numDocuments
    characters = textData{i};
    X = double(characters);

    % Create vector of categorical responses with end of text character.
    charactersShifted = [cellstr(characters(2:end)')' endOfTextCharacter];
    Y = categorical(charactersShifted);

    XTrain{i} = X;
    YTrain{i} = Y;
end
```

During training, by default, the software splits the training data into mini-batches and pads the sequences so that they have the same length. Too much padding can have a negative impact on the network performance.

To prevent the training process from adding too much padding, you can sort the training data by sequence length, and choose a mini-batch size so that sequences in a mini-batch have a similar length.

Get the sequence lengths for each observation.

```
numObservations = numel(XTrain);
for i=1:numObservations
    sequence = XTrain{i};
    sequenceLengths(i) = size(sequence,2);
end
```

Sort the data by sequence length.

```
[~,idx] = sort(sequenceLengths);
XTrain = XTrain(idx);
YTrain = YTrain(idx);
```

Create and Train LSTM Network

Define the LSTM architecture. Specify a sequence-to-sequence LSTM classification network with 400 hidden units. Set the input size to be the feature dimension of the training data. For sequences of character indices, the feature dimension is 1. Specify a word embedding layer with dimension 200 and specify the number of words (which correspond to characters) to be the highest character value in the input data. Set the output size of the fully connected layer to be the number of categories in the responses. To help prevent overfitting, include a dropout layer after the LSTM layer.

The word embedding layer learns an embedding of characters and maps each character to a 200-dimension vector.

```
inputSize = size(XTrain{1},1);
numClasses = numel(categories([YTrain{:}]));
numCharacters = max([textData{:}]);


layers = [
    sequenceInputLayer(inputSize)
    wordEmbeddingLayer(200,numCharacters)
    lstmLayer(400,'OutputMode','sequence')
    dropoutLayer(0.2);
    fullyConnectedLayer(numClasses)
    softmaxLayer
    classificationLayer];
```

Specify the training options. Specify to train with a mini-batch size of 32 and initial learn rate 0.01. To prevent the gradients from exploding, set the gradient threshold to 1. To ensure the data remains sorted, set 'Shuffle' to 'never'. To monitor the training progress, set the 'Plots' option to 'training-progress'. To suppress verbose output, set 'Verbose' to false.

```
options = trainingOptions('adam', ...
    'MiniBatchSize',32,...
    'InitialLearnRate',0.01, ...
    'GradientThreshold',1, ...
    'Shuffle','never', ...
    'Plots','training-progress', ...
    'Verbose',false);
```

Train the network.

```
net = trainNetwork(XTrain,YTrain,layers,options);
```



Generate New Text

Generate the first character of the text by sampling a character from a probability distribution according to the first characters of the text in the training data. Generate the remaining characters by using the trained LSTM network to predict the next sequence using the current sequence of generated text. Keep generating characters one-by-one until the network predicts the "end of text" character.

Sample the first character according to the distribution of the first characters in the training data.

```
initialCharacters = extractBefore(textData,2);
firstCharacter = datasample(initialCharacters,1);
generatedText = firstCharacter;
```

Convert the first character to a numeric index.

```
X = double(char(firstCharacter));
```

For the remaining predictions, sample the next character according to the prediction scores of the network. The prediction scores represent the probability distribution of the next character. Sample the characters from the vocabulary of characters given by the class names of the output layer of the network. Get the vocabulary from the classification layer of the network.

```
vocabulary = string(net.Layers(end).ClassNames);
```

Make predictions character by character using `predictAndUpdateState`. For each prediction, input the index of the previous character. Stop predicting when the network predicts the end of text character or when the generated text is 500 characters long. For large collections of data, long sequences, or large networks, predictions on the GPU are usually faster to compute than predictions on the CPU. Otherwise, predictions on the CPU are usually faster to compute. For single time step predictions, use the CPU. To use the CPU for prediction, set the `'ExecutionEnvironment'` option of `predictAndUpdateState` to `'cpu'`.

```
maxLength = 500;
while strlength(generatedText) < maxLength
    % Predict the next character scores.
    [net,characterScores] = predictAndUpdateState(net,X,'ExecutionEnvironment','cpu');

    % Sample the next character.
    newCharacter = datasample(vocabulary,1,'Weights',characterScores);

    % Stop predicting at the end of text.
    if newCharacter == endOfTextCharacter
        break
    end

    % Add the character to the generated text.
    generatedText = generatedText + newCharacter;

    % Get the numeric index of the character.
    X = double(char(newCharacter));
end
```

Reconstruct the generated text by replacing the special characters with their corresponding whitespace and new line characters.

```
generatedText = replace(generatedText,[newlineCharacter whitespaceCharacter],[newline '
'
generatedText =
"I wish Mr. Darcy, upon latter of my sort sincerely fixed in the regard to relanth. We
```

To generate multiple pieces of text, reset the network state between generations using `resetState`.

```
net = resetState(net);
```

See Also

`doc2sequence` | `extractHTMLText` | `findElement` | `htmlTree` | `lstmLayer` | `sequenceInputLayer` | `tokenizedDocument` | `trainNetwork` | `trainingOptions` | `wordEmbeddingLayer` | `wordcloud`

Related Examples

- “Generate Text Using Deep Learning” (Deep Learning Toolbox)
- “Word-By-Word Text Generation Using Deep Learning” on page 2-101
- “Create Simple Text Model for Classification” on page 2-2
- “Analyze Text Data Using Topic Models” on page 2-18
- “Analyze Text Data Using Multiword Phrases” on page 2-9
- “Train a Sentiment Classifier” on page 2-43
- “Sequence Classification Using Deep Learning” (Deep Learning Toolbox)
- “Deep Learning in MATLAB” (Deep Learning Toolbox)

Word-By-Word Text Generation Using Deep Learning

This example shows how to train a deep learning LSTM network to generate text word-by-word.

To train a deep learning network for word-by-word text generation, train a sequence-to-sequence LSTM network to predict the next word in a sequence of words. To train the network to predict the next word, specify the responses to be the input sequences shifted by one time step.

This example reads text from a website. It reads and parses the HTML code to extract the relevant text, then uses a custom mini-batch datastore `documentGenerationDatastore` to input the documents to the network as mini-batches of sequence data. The datastore converts documents to sequences of numeric word indices. The deep learning network is an LSTM network that contains a word embedding layer.

A mini-batch datastore is an implementation of a datastore with support for reading data in batches. You can use a mini-batch datastore as a source of training, validation, test, and prediction data sets for deep learning applications. Use mini-batch datastores to read out-of-memory data or to perform specific preprocessing operations when reading batches of data.

You can adapt the custom mini-batch datastore `documentGenerationDatastore.m` to your data by customizing the functions. For an example showing how to create your own custom mini-batch datastore, see “Develop Custom Mini-Batch Datastore” (Deep Learning Toolbox).

Load Training Data

Load the training data. Read the HTML code from Alice's Adventures in Wonderland by Lewis Carroll from Project Gutenberg.

```
url = "https://www.gutenberg.org/files/11/11-h/11-h.htm";  
code = webread(url);
```

Parse HTML Code

The HTML code contains the relevant text inside `<p>` (paragraph) elements. Extract the relevant text by parsing the HTML code using `htmlTree` and then finding all the elements with element name `"p"`.

```
tree = htmlTree(code);
selector = "p";
subtrees = findElement(tree,selector);
```

Extract the text data from the HTML subtrees using `extractHTMLText` and view the first 10 paragraphs.

```
textData = extractHTMLText(subtrees);
textData(1:10)
```

```
ans = 10×1 string array
```

```
""
""
""
""
""
""
""
```

```
"Alice was beginning to get very tired of sitting by her sister on the bank, and o
"So she was considering in her own mind (as well as she could, for the hot day made
"There was nothing so very remarkable in that; nor did Alice think it so very much
"In another moment down went Alice after it, never once considering how in the worl
```

Remove the empty paragraphs and view the first 10 remaining paragraphs.

```
textData(textData == "") = [];
textData(1:10)
```

```
ans = 10×1 string array
```

```
"Alice was beginning to get very tired of sitting by her sister on the bank, and o
"So she was considering in her own mind (as well as she could, for the hot day made
"There was nothing so very remarkable in that; nor did Alice think it so very much
"The rabbit-hole went straight on like a tunnel for some way, and then dipped sudde
"Either the well was very deep, or she fell very slowly, for she had plenty of time
"‘Well!’ thought Alice to herself, ‘after such a fall as this, I shall think nothin
"Down, down, down. Would the fall never come to an end! ‘I wonder how many miles I
"Presently she began again. ‘I wonder if I shall fall right through the earth! How
"Down, down, down. There was nothing else to do, so Alice soon began talking again
```

Visualize the text data in a word cloud.

```
figure
wordcloud(textData);
title("Alice's Adventures in Wonderland")
```


Create a document generation datastore using the tokenized documents.

```
ds = documentGenerationDatastore(documents);
```

To reduce the amount of padding added to the sequences, sort the documents in the datastore by sequence length.

```
ds = sort(ds);
```

Create and Train LSTM Network

Define the LSTM network architecture. To input sequence data into the network, include a sequence input layer and set the input size to 1. Next, include a word embedding layer of dimension 100 and the same number of words as the word encoding. Next, include an LSTM layer and specify the hidden size to be 100. Finally, add a fully connected layer with the same size as the number of classes, a softmax layer, and a classification layer. The number of classes is the number of words in the vocabulary plus an extra class for the "end of text" class.

```
inputSize = 1;
embeddingDimension = 100;
numWords = numel(ds.Encoding.Vocabulary);
numClasses = numWords + 1;


layers = [
    sequenceInputLayer(inputSize)
    wordEmbeddingLayer(embeddingDimension,numWords)
    lstmLayer(100)
    dropoutLayer(0.2)
    fullyConnectedLayer(numClasses)
    softmaxLayer
    classificationLayer];
```

Specify the training options. Specify the solver to be 'adam'. Train for 300 epochs with learn rate 0.01. Set the mini-batch size to 32. To keep the data sorted by sequence length, set the 'Shuffle' option to 'never'. To monitor the training progress, set the 'Plots' option to 'training-progress'. To suppress verbose output, set 'Verbose' to false.

```
options = trainingOptions('adam', ...
    'MaxEpochs',300, ...
    'InitialLearnRate',0.01, ...
    'MiniBatchSize',32, ...
    'Shuffle','never', ...
    'Plots','training-progress', ...
    'Verbose',false);
```

Train the network using `trainNetwork`.

```
net = trainNetwork(ds, layers, options);
```



Generate New Text

Generate the first word of the text by sampling a word from a probability distribution according to the first words of the text in the training data. Generate the remaining words by using the trained LSTM network to predict the next time step using the current sequence of generated text. Keep generating words one-by-one until the network predicts the "end of text" word.

To make the first prediction using the network, input the index that represents the "start of text" token. Find the index by using the `word2ind` function with the word encoding used by the document datastore.

```
enc = ds.Encoding;
wordIndex = word2ind(enc, "startOfText")
```

```
wordIndex = 1
```

For the remaining predictions, sample the next word according to the prediction scores of the network. The prediction scores represent the probability distribution of the next word. Sample the words from the vocabulary given by the class names of the output layer of the network.

```
vocabulary = string(net.Layers(end).Classes);
```

Make predictions word by word using `predictAndUpdateState`. For each prediction, input the index of the previous word. Stop predicting when the network predicts the end of text word or when the generated text is 500 characters long. For large collections of data, long sequences, or large networks, predictions on the GPU are usually faster to compute than predictions on the CPU. Otherwise, predictions on the CPU are usually faster to compute. For single time step predictions, use the CPU. To use the CPU for prediction, set the `'ExecutionEnvironment'` option of `predictAndUpdateState` to `'cpu'`.

```
generatedText = "";
maxLength = 500;
while strlength(generatedText) < maxLength
    % Predict the next word scores.
    [net,wordScores] = predictAndUpdateState(net,wordIndex,'ExecutionEnvironment','cpu')

    % Sample the next word.
    newWord = datasample(vocabulary,1,'Weights',wordScores);

    % Stop predicting at the end of text.
    if newWord == "EndOfText"
        break
    end

    % Add the word to the generated text.
    generatedText = generatedText + " " + newWord;

    % Find the word index for the next input.
    wordIndex = word2ind(enc,newWord);
end
```

The generation process introduces whitespace characters between each prediction, which means that some punctuation characters appear with unnecessary spaces before and after. Reconstruct the generated text by replacing removing the spaces before and after the appropriate punctuation characters.

Remove the spaces that appear before the specified punctuation characters.

```
punctuationCharacters = [". " ", " "' " ") " ":" "?" "!"];  
generatedText = replace(generatedText, " " + punctuationCharacters, punctuationCharacters);
```

Remove the spaces that appear after the specified punctuation characters.

```
punctuationCharacters = ["(" "'"];  
generatedText = replace(generatedText, punctuationCharacters + " ", punctuationCharacters);
```

```
generatedText =  
" 'Sure, it's a good Turtle!' said the Queen in a low, weak voice."
```

To generate multiple pieces of text, reset the network state between generations using `resetState`.

```
net = resetState(net);
```

See Also

[doc2sequence](#) | [extractHTMLText](#) | [findElement](#) | [htmlTree](#) | [lstmLayer](#) | [sequenceInputLayer](#) | [tokenizedDocument](#) | [trainNetwork](#) | [trainingOptions](#) | [wordEmbeddingLayer](#) | [wordcloud](#)

Related Examples

- “Generate Text Using Deep Learning” (Deep Learning Toolbox)
- “Create Simple Text Model for Classification” on page 2-2
- “Analyze Text Data Using Topic Models” on page 2-18
- “Analyze Text Data Using Multiword Phrases” on page 2-9
- “Train a Sentiment Classifier” on page 2-43
- “Sequence Classification Using Deep Learning” (Deep Learning Toolbox)
- “Deep Learning in MATLAB” (Deep Learning Toolbox)

Classify Out-of-Memory Text Data Using Custom Mini-Batch Datastore

This example shows how to classify out-of-memory text data with a deep learning network using a custom mini-batch datastore.

A mini-batch datastore is an implementation of a datastore with support for reading data in batches. You can use a mini-batch datastore as a source of training, validation, test, and prediction data sets for deep learning applications. Use mini-batch datastores to read out-of-memory data or to perform specific preprocessing operations when reading batches of data.

When training the network, the software creates mini-batches of sequences of the same length by padding, truncating, or splitting the input data. The `trainingOptions` function provides options to pad and truncate input sequences, however, these options are not well suited for sequences of word vectors. Furthermore, this function does not support padding data in a custom datastore. Instead, you must pad and truncate the sequences manually. If you *left-pad* and truncate the sequences of word vectors, then the training might improve.

The “Classify Text Data Using Deep Learning” on page 2-53 example manually truncates and pads all the documents to the same length. This process adds lots of padding to very short documents and discards lots of data from very long documents.

Alternatively, to prevent adding too much padding or discarding too much data, create a custom mini-batch datastore that inputs mini-batches into the network. The custom mini-batch datastore `textDatastore.m` converts mini-batches of documents to sequences or word indices and left-pads each mini-batch to the length of the longest document in the mini-batch. For sorted data, this datastore can help reduce the amount of padding added to the data since documents are not padded to a fixed length. Similarly, the datastore does not discard any data from the documents.

This example uses the custom mini-batch datastore `textDatastore.m`. You can adapt this datastore to your data by customizing the functions. For an example showing how to create your own custom mini-batch datastore, see “Develop Custom Mini-Batch Datastore” (Deep Learning Toolbox).

Load Pretrained Word Embedding

The datastore `textDatastore` requires a word embedding to convert documents to sequences of vectors. Load a pretrained word embedding using

`fastTextWordEmbedding`. This function requires Text Analytics Toolbox™ Model for *fastText English 16 Billion Token Word Embedding* support package. If this support package is not installed, then the function provides a download link.

```
emb = fastTextWordEmbedding;
```

Create Mini-Batch Datastore of Documents

Create a datastore that contains the data for training. The custom mini-batch datastore `textDatastore` reads predictors and labels from a CSV file. For the predictors, the datastore converts the documents into sequences of word indices and for the responses, the datastore returns a categorical label for each document.

To create the datastore, first save the custom mini-batch datastore `textDatastore.m` to the path. For more information about creating custom mini-batch datastores, see “Develop Custom Mini-Batch Datastore” (Deep Learning Toolbox).

For the training data, specify the CSV file `"weatherReportsTrain.csv"` and that the text and labels are in the columns `"event_narrative"` and `"event_type"` respectively.

```
filenameTrain = "weatherReportsTrain.csv";
textName = "event_narrative";
labelName = "event_type";
dsTrain = textDatastore(filenameTrain, textName, labelName, emb)

dsTrain =
    textDatastore with properties:
        ClassNames: [1×39 string]
        Datastore: [1×1 matlab.io.datastore.TransformedDatastore]
        EmbeddingDimension: 300
        LabelName: "event_type"
        MiniBatchSize: 128
        NumClasses: 39
        NumObservations: 19683
```

Create a datastore containing the validation data from the CSV file `"weatherReportsValidation.csv"` using the same steps.

```
filenameValidation = "weatherReportsValidation.csv";
dsValidation = textDatastore(filenameValidation, textName, labelName, emb)
```

```
dsValidation =
  textDatastore with properties:

      ClassNames: [1×39 string]
      Datastore: [1×1 matlab.io.datastore.TransformedDatastore]
  EmbeddingDimension: 300
      LabelName: "event_type"
      MiniBatchSize: 128
      NumClasses: 39
      NumObservations: 4218
```

Create and Train LSTM Network

Define the LSTM network architecture. To input sequence data into the network, include a sequence input layer and set the input size to the embedding dimension. Next, include an LSTM layer with 180 hidden units. To use the LSTM layer for a sequence-to-label classification problem, set the output mode to `'last'`. Finally, add a fully connected layer with output size equal to the number of classes, a softmax layer, and a classification layer.

```
numFeatures = dsTrain.EmbeddingDimension;
numHiddenUnits = 180;
numClasses = dsTrain.NumClasses;

layers = [ ...
    sequenceInputLayer(numFeatures)
    lstmLayer(numHiddenUnits, 'OutputMode', 'last')
    fullyConnectedLayer(numClasses)
    softmaxLayer
    classificationLayer];
```

Specify the training options. Specify the solver to be `'adam'` and the gradient threshold to be 2. The datastore `textDatastore.m` does not support shuffling, so set `'Shuffle'`, to `'never'`. For an example showing how to implement a datastore with support for shuffling, see “Develop Custom Mini-Batch Datastore” (Deep Learning Toolbox). Validate the network once per epoch. To monitor the training progress, set the `'Plots'` option to `'training-progress'`. To suppress verbose output, set `'Verbose'` to `false`.

By default, `trainNetwork` uses a GPU if one is available (requires Parallel Computing Toolbox™ and a CUDA® enabled GPU with compute capability 3.0 or higher). Otherwise, it uses the CPU. To specify the execution environment manually, use the `'ExecutionEnvironment'` name-value pair argument of `trainingOptions`. Training on a CPU can take significantly longer than training on a GPU.



```

miniBatchSize = 128;
numObservations = dsTrain.NumObservations;
numIterationsPerEpoch = floor(numObservations / miniBatchSize);

options = trainingOptions('adam', ...
    'MaxEpochs',15, ...
    'MiniBatchSize',miniBatchSize, ...
    'GradientThreshold',2, ...
    'Shuffle','never', ...
    'ValidationData',dsValidation, ...
    'ValidationFrequency',numIterationsPerEpoch, ...
    'Plots','training-progress', ...
    'Verbose',false);
    
```

Train the LSTM network using the `trainNetwork` function.

```
net = trainNetwork(dsTrain, layers, options);
```



Test LSTM Network

Create a datastore containing the documents and the labels

```
filenameTest = "weatherReportsTest.csv";
dsTest = textDatastore(filenameTest, textName, labelName, emb)

dsTest =
    textDatastore with properties:

        ClassNames: [1×39 string]
        Datastore: [1×1 matlab.io.datastore.TransformedDatastore]
        EmbeddingDimension: 300
        LabelName: "event_type"
        MiniBatchSize: 128
        NumClasses: 39
        NumObservations: 4217
```

Read the labels from the datastore using the `readLabels` function of the custom datastore.

```
YTest = readLabels(dsTest);
```

Classify the test documents using the trained LSTM network.

```
YPred = classify(net, dsTest);
```

Calculate the classification accuracy. The accuracy is the proportion of labels that the network predicts correctly.

```
accuracy = mean(YPred == YTest)
```

```
accuracy = 0.8084
```

See Also

`doc2sequence` | `extractHTMLText` | `findElement` | `htmlTree` | `lstmLayer` | `sequenceInputLayer` | `tokenizedDocument` | `trainNetwork` | `trainingOptions` | `wordEmbeddingLayer` | `wordcloud`

Related Examples

- “Generate Text Using Deep Learning” (Deep Learning Toolbox)
- “Create Simple Text Model for Classification” on page 2-2
- “Analyze Text Data Using Topic Models” on page 2-18
- “Analyze Text Data Using Multiword Phrases” on page 2-9
- “Train a Sentiment Classifier” on page 2-43
- “Sequence Classification Using Deep Learning” (Deep Learning Toolbox)
- “Deep Learning in MATLAB” (Deep Learning Toolbox)

Display and Presentation

- “Visualize Text Data Using Word Clouds” on page 3-2
- “Visualize Word Embeddings Using Text Scatter Plots” on page 3-8

Visualize Text Data Using Word Clouds

This example shows how to visualize text data using word clouds.

Text Analytics Toolbox extends the functionality of the `wordcloud` (MATLAB) function. It adds support for creating word clouds directly from string arrays and creating word clouds from bag-of-words models and LDA topics.

Load the example data. The file `weatherReports.csv` contains weather reports, including a text description and categorical labels for each event.

```
filename = "weatherReports.csv";  
T = readtable(filename, 'TextType', 'string');
```

Extract the text data from the `event_narrative` column.

```
textData = T.event_narrative;  
textData(1:10)
```

```
ans = 10x1 string array  
"Large tree down between Plantersville and Nettleton."  
"One to two feet of deep standing water developed on a street on the Winthrop Univer  
"NWS Columbia relayed a report of trees blown down along Tom Hall St."  
"Media reported two trees blown down along I-40 in the Old Fort area."  
""  
"A few tree limbs greater than 6 inches down on HWY 18 in Roseland."  
"Awning blown off a building on Lamar Avenue. Multiple trees down near the interse  
"Quarter size hail near Rosemark."  
"Tin roof ripped off house on Old Memphis Road near Billings Drive. Several large t  
"Powerlines down at Walnut Grove and Cherry Lane roads."
```


Create a word cloud from all the weather reports.

```
figure  
wordcloud(textData);  
title("Weather Reports")
```



```
subplot(1,3,2)
idx = state == "KANSAS";
wordcloud(textData(idx), 'Shape', 'rectangle', 'Box', 'on');
title("Kansas")
```


```
subplot(1,3,3)
idx = state == "ALASKA";
wordcloud(textData(idx), 'Shape', 'rectangle', 'Box', 'on');
title("Alaska")
```



Compare the words in the reports with property damage reported in thousands of dollars to the reports with damage reported in millions of dollars. Create word clouds of the reports for each of these amounts with highlight color blue and red respectively.

```
cost = T.damage_property;  
idx = endsWith(cost,"K");  
figure  
wordcloud(textData(idx),'HighlightColor','blue');  
title("Damage Reported in Thousands")
```

Damage Reported in Thousands



```
idx = endsWith(cost,"M");  
figure  
wordcloud(textData(idx),'HighlightColor','red');  
title("Damage Reported in Millions")
```


Visualize Word Embeddings Using Text Scatter Plots

This example shows how to visualize word embeddings using 2-D and 3-D t-SNE and text scatter plots.

Word embeddings map words in a vocabulary to real vectors. The vectors attempt to capture the semantics of the words, so that similar words have similar vectors. Some embeddings also capture relationships between words like "Italy is to France as Rome is to Paris". In vector form, this relationship is $Italy - Rome + Paris = France$.

To reproduce the results in this example, set `rng` to `'default'`.

```
rng('default')
```

Load Pretrained Word Embedding

Load a pretrained word embedding using `fastTextWordEmbedding`. This function requires Text Analytics Toolbox™ Model for *fastText English 16 Billion Token Word Embedding* support package. If this support package is not installed, then the function provides a download link.

```
emb = fastTextWordEmbedding
emb =
  wordEmbedding with properties:
    Dimension: 300
    Vocabulary: [1x999994 string]
```

Explore the word embedding using `word2vec` and `vec2word`. Convert the words *Italy*, *Rome*, and *Paris* to vectors using `word2vec`.

```
italy = word2vec(emb, "Italy");
rome = word2vec(emb, "Rome");
paris = word2vec(emb, "Paris");
```

Compute the vector given by $italy - rome + paris$. This vector encapsulates the semantic meaning of the word *Italy*, without the semantics of the word *Rome*, and also includes the semantics of the word *Paris*.

```
vec = italy - rome + paris
vec = 1x300 single row vector
```

```
0.1606 -0.0690 0.1183 -0.0349 0.0672 0.0907 -0.1820 -0.0080 0.
```

Find the closest words in the embedding to `vec` using `vec2word`.

```
word = vec2word(emb,vec)
```

```
word =  
"France"
```

Create 2-D Text Scatter Plot

Visualize the word embedding by creating a 2-D text scatter plot using `tsne` and `textscatter`.

Convert the first 500 words to vectors using `word2vec`. `V` is a matrix of word vectors of length 300.

```
words = emb.Vocabulary(1:5000);  
V = word2vec(emb,words);  
size(V)
```

```
ans = 1x2
```


```
5000    300
```

Embed the word vectors in two-dimensional space using `tsne`. This function may take a few minutes to run. If you want to display the convergence information, then set the `'Verbose'` name-value pair to 1.

```
XY = tsne(V);
```

Plot the words at the coordinates specified by `XY` in a 2-D text scatter plot. For readability, `textscatter`, by default, does not display all of the input words and displays markers instead.

```
figure  
textscatter(XY,words)  
title("Word Embedding t-SNE Plot")
```



Zoom in on a section of the plot.

```
xlim([-18 -5])  
ylim([11 21])
```



5000 300

Embed the word vectors in a three-dimensional space using `tsne` by specifying the number of dimensions to be three. This function may take a few minutes to run. If you want to display the convergence information, then you can set the `'Verbose'` name-value pair to 1.

```
XYZ = tsne(V, 'NumDimensions', 3);
```


Plot the words at the coordinates specified by `XYZ` in a 3-D text scatter plot.

```
figure  
ts = textscatter3(XYZ, words);  
title("3-D Word Embedding t-SNE Plot")
```

Zoom in on a section of the plot.

```
xlim([12.04 19.48])  
ylim([-2.66 3.40])  
zlim([10.03 14.53])
```



Perform Cluster Analysis

Convert the first 5000 words to vectors using `word2vec`. `V` is a matrix of word vectors of length 300.

```
words = emb.Vocabulary(1:5000);  
V = word2vec(emb, words);  
size(V)
```

```
ans = 1x2
```


```
5000    300
```

Discover 25 clusters using `kmeans`.

```
cidx = kmeans(V,25,'dist','sqeuclidean');
```


Visualize the clusters in a text scatter plot using the 2-D t-SNE data coordinates calculated earlier.

```
figure
textscatter(XY,words,'ColorData',categorical(cidx));
title("Word Embedding t-SNE Plot")
```



Zoom in on a section of the plot.

```
xlim([13 24])
ylim([-47 -35])
```



See Also

`readWordEmbedding` | `textscatter` | `textscatter3` | `tokenizedDocument` | `vec2word` | `word2vec` | `wordEmbedding`

Related Examples

- “Extract Text Data from Files” on page 1-2
- “Prepare Text Data for Analysis” on page 1-12
- “Visualize Text Data Using Word Clouds” on page 3-2
- “Classify Text Data Using Deep Learning” on page 2-53

Language Support

- “Language Considerations” on page 4-2
- “Japanese Language Support” on page 4-6
- “Analyze Japanese Text Data” on page 4-12
- “German Language Support” on page 4-26
- “Analyze German Text Data” on page 4-33
- “Language-Independent Features” on page 4-47

Language Considerations

Text Analytics Toolbox supports the languages English, Japanese, and German. Most Text Analytics Toolbox functions also work with text in other languages. This table summarizes how to use Text Analytics Toolbox features for other languages.

Feature	Language Consideration	Workaround
Tokenization	The <code>tokenizedDocument</code> function has built-in rules for English, Japanese, and German only. For English and German text, the 'unicode' tokenization method of <code>tokenizedDocument</code> detects tokens using rules based on Unicode [®] Standard Annex #29 [1] and the ICU tokenizer [2], modified to better detect complex tokens such as hashtags and URLs. For Japanese text, the 'mecab' tokenization method detects tokens using rules based on the MeCab tokenizer [3].	For other languages, you can still try using <code>tokenizedDocument</code> . If <code>tokenizedDocument</code> does not produce useful results, then try tokenizing the text manually. To create a <code>tokenizedDocument</code> array from manually tokenized text, set the 'TokenizeMethod' option to 'none'. For more information, see <code>tokenizedDocument</code> .
Stop word removal	The <code>stopWords</code> and <code>removeStopWords</code> functions support English, Japanese, and German stop words only.	To remove stop words from other languages, use <code>removeWords</code> and specify your own stop words to remove.

Feature	Language Consideration	Workaround
Sentence detection	The <code>addSentenceDetails</code> function detects sentence boundaries based on punctuation characters and line number information. For English and German text, the function also uses a list of abbreviations passed to the function.	For other languages, you might need to specify your own list of abbreviations for sentence detection. To do this, use the 'Abbreviations' option of <code>addSentenceDetails</code> . For more information, see <code>addSentenceDetails</code> .
Word clouds	For string input, the <code>wordcloud</code> function uses English, Japanese, and German tokenization, stop word removal, and word normalization.	For other languages, you might need to manually preprocess your text data and specify unique words and corresponding sizes in <code>wordcloud</code> . To specify word sizes in <code>wordcloud</code> , input your data as a table or arrays containing the unique words and corresponding sizes. For more information, see <code>wordcloud</code> .

Feature	Language Consideration	Workaround
Word embeddings	File input to the <code>trainWordEmbedding</code> function requires words separated by whitespace.	<p>For files containing non-English text, you might need to input a <code>tokenizedDocument</code> array to <code>trainWordEmbedding</code>.</p> <p>To create a <code>tokenizedDocument</code> array from pretokenized text, use the <code>tokenizedDocument</code> function and set the <code>'TokenizeMethod'</code> option to <code>'none'</code>.</p> <p>For more information, see <code>trainWordEmbedding</code>.</p>

Language-Independent Features

Word and N-Gram Counting

The `bagOfWords` and `bagOfNgrams` functions support `tokenizedDocument` input regardless of language. If you have a `tokenizedDocument` array containing your data, then you can use these functions.

Modeling and Prediction

The `fitlda` and `fitlsa` functions support `bagOfWords` and `bagOfNgrams` input regardless of language. If you have a `bagOfWords` or `bagOfNgrams` object containing your data, then you can use these functions.

The `trainWordEmbedding` function supports `tokenizedDocument` or file input regardless of language. If you have a `tokenizedDocument` array or a file containing your data in the correct format, then you can use this function.

References

[1] *Unicode Text Segmentation*. <https://www.unicode.org/reports/tr29/>

[2] *Boundary Analysis*. <http://userguide.icu-project.org/boundaryanalysis>

[3] *MeCab: Yet Another Part-of-Speech and Morphological Analyzer*. <https://taku910.github.io/mecab/>

See Also

[addLanguageDetails](#) | [addSentenceDetails](#) | [bagOfNgrams](#) | [bagOfWords](#) | [fitlda](#) | [fitlsa](#) | [normalizeWords](#) | [removeWords](#) | [stopWords](#) | [tokenizedDocument](#) | [wordcloud](#)

More About

- “Text Data Preparation”
- “Modeling and Prediction”
- “Display and Presentation”
- “Japanese Language Support” on page 4-6
- “Analyze Japanese Text Data” on page 4-12
- “German Language Support” on page 4-26
- “Analyze German Text Data” on page 4-33

Japanese Language Support

This topic summarizes the Text Analytics Toolbox features that support Japanese text. For an example showing how to analyze Japanese text data, see “Analyze Japanese Text Data” on page 4-12.

Tokenization

The `tokenizedDocument` function automatically detects Japanese input. Alternatively, set the 'Language' option in `tokenizedDocument` to 'ja'. This option specifies the language details of the tokens. To view the language details of the tokens, use `tokenDetails`. These language details determine the behavior of the `removeStopWords`, `addPartOfSpeechDetails`, `normalizeWords`, `addSentenceDetails`, and `addEntityDetails` functions on the tokens.

Tokenize Japanese Text

Tokenize Japanese text using `tokenizedDocument`. The function automatically detects Japanese text.

```
str = [  
    "恋に悩み、苦しむ。"  
    "恋の悩みで苦しむ。"  
    "空に星が輝き、瞬いている。"  
    "空の星が輝きを増している。"];  
documents = tokenizedDocument(str)  
  
documents =  
    4x1 tokenizedDocument:  
  
    6 tokens: 恋 に 悩み 、 苦しむ 。  
    6 tokens: 恋 の 悩み で 苦しむ 。  
    10 tokens: 空 に 星 が 輝き 、 瞬い て い る 。  
    10 tokens: 空 の 星 が 輝き を 増し て い る 。
```

Part of Speech Details

The `tokenDetails` function, by default, includes part of speech details with the token details.

Get Part of Speech Details of Japanese Text

Tokenize Japanese text using `tokenizedDocument`.

```
str = [
    "恋に悩み、苦しむ。"
    "恋の悩みで 苦しむ。"
    "空に星が輝き、瞬いている。"
    "空の星が輝きを増している。"
    "駅までは遠くて、歩けない。"
    "遠くの駅まで歩けない。"
    "すもももももものうち。"];
documents = tokenizedDocument(str);
```

For Japanese text, you can get the part-of-speech details using `tokenDetails`. For English text, you must first use `addPartOfSpeechDetails`.

```
tdetails = tokenDetails(documents);
head(tdetails)
```

ans=8x8 table

Token	DocumentNumber	LineNumber	Type	Language	PartOfSpeech
"恋"	1	1	letters	ja	noun
"に"	1	1	letters	ja	adposition
"悩み"	1	1	letters	ja	verb
"、"	1	1	punctuation	ja	punctuation
"苦しむ"	1	1	letters	ja	verb
"。"	1	1	punctuation	ja	punctuation
"恋"	2	1	letters	ja	noun
"の"	2	1	letters	ja	adposition

Named Entity Recognition

To add entity tags to documents, use the `addEntityDetails` function.

Add Named Entity Tags to Japanese Text

Tokenize Japanese text using `tokenizedDocument`.

```
str = [
    "マリーさんはボストンからニューヨークに引っ越しました。"]
```

```

"駅で鈴木さんに迎えに行きます。"
"東京は大阪より大きいですか?"
"東京に行った時、新宿や渋谷などいろいろな所に訪れたました。"];
documents = tokenizedDocument(str);

```

For Japanese text, the software automatically adds named entity tags, so you do not need to use the `addEntityDetails` function. This software detects person names, locations, organizations, and other named entities. To view the entity details, use the `tokenDetails` function.

```

tdetails = tokenDetails(documents);
head(tdetails)

```

ans=8×8 table

Token	DocumentNumber	LineNumber	Type	Language	PartOfSpeech
"マリー"	1	1	letters	ja	proper-noun
"さん"	1	1	letters	ja	noun
"は"	1	1	letters	ja	adposition
"ボストン"	1	1	letters	ja	proper-noun
"から"	1	1	letters	ja	adposition
"ニューヨーク"	1	1	letters	ja	proper-noun
"に"	1	1	letters	ja	adposition
"引っ越し"	1	1	letters	ja	verb

View the words tagged with entity "person", "location", "organization", or "other". These words are the words not tagged "non-entity".

```

idx = tdetails.Entity ~= "non-entity";
tdetails(idx,:).Token

```

ans = 11×1 string array

```

"マリー"
"さん"
"ボストン"
"ニューヨーク"
"鈴木"
"さん"
"東京"
"大阪"
"東京"
"新宿"

```

"渋谷"

Stop Words

To remove stop words from documents according to the token language details, use `removeStopWords`. For a list of Japanese stop words set the 'Language' option in `stopWords` to 'ja'.

Remove Japanese Stop Words

Tokenize Japanese text using `tokenizedDocument`. The function automatically detects Japanese text.

```
str = [
    "ここは静かなので、とても穏やかです"
    "企業内の顧客データを利用し、今年の売り上げを調べることが出来た。"
    "私は先生です。私は英語を教えています。"];
documents = tokenizedDocument(str);
```

Remove stop words using `removeStopWords`. The function uses the language details from documents to determine which language stop words to remove.

```
documents = removeStopWords(documents)

documents =
    3x1 tokenizedDocument:

    4 tokens: 静か 、 とても 穏やか
    10 tokens: 企業 顧客 データ 利用 、 今年 売り上げ 調べる 出来 。
    5 tokens: 先生 。 英語 教え 。
```

Lemmatization

To lemmatize tokens according to the token language details, use `normalizeWords` and set the 'Style' option to 'lemma'.

Lemmatize Japanese Text

Tokenize Japanese text using the `tokenizedDocument` function. The function automatically detects Japanese text.

```
str = [  
    "空に星が輝き、瞬いている。"  
    "空の星が輝きを増している。"  
    "駅までは遠くて、歩けない。"  
    "遠くの駅まで歩けない。"];  
documents = tokenizedDocument(str);
```

Lemmatize the tokens using `normalizeWords`.

```
documents = normalizeWords(documents)  
  
documents =  
  4x1 tokenizedDocument:  
  
  10 tokens: 空 に 星 が 輝く 、 瞬く て いる 。  
  10 tokens: 空 の 星 が 輝き を 増す て いる 。  
   9 tokens: 駅 ま で は 遠い て 、 歩ける ない 。  
   7 tokens: 遠く の 駅 ま で 歩ける ない 。
```

Language-Independent Features

Word and N-Gram Counting

The `bagOfWords` and `bagOfNgrams` functions support `tokenizedDocument` input regardless of language. If you have a `tokenizedDocument` array containing your data, then you can use these functions.

Modeling and Prediction

The `fitlda` and `fitlsa` functions support `bagOfWords` and `bagOfNgrams` input regardless of language. If you have a `bagOfWords` or `bagOfNgrams` object containing your data, then you can use these functions.

The `trainWordEmbedding` function supports `tokenizedDocument` or file input regardless of language. If you have a `tokenizedDocument` array or a file containing your data in the correct format, then you can use this function.

See Also

`addEntityDetails` | `addLanguageDetails` | `addPartOfSpeechDetails` |
`normalizeWords` | `removeStopWords` | `stopWords` | `tokenDetails` |
`tokenizedDocument`

More About

- “Language Considerations” on page 4-2
- “Analyze Japanese Text Data” on page 4-12

Analyze Japanese Text Data

This example shows how to import, prepare, and analyze Japanese text data using a topic model.

Japanese text data can be large and can contain lots of noise that negatively affects statistical analysis. For example, the text data can contain the following:

- Variations in word forms. For example, "難しい" ("is difficult") and "難しかった" ("was difficult")
- Words that add noise. For example, stop words such as "あそこ" ("over there"), "あたり" ("around"), and "あちら" ("there")
- Punctuation and special characters

These word clouds illustrate word frequency analysis applied to some raw text data from "吾輩は猫である" by 夏目漱石, and a preprocessed version of the same text data.

Import Data

Read the data from "吾輩は猫である" by 夏目漱石 from https://www.aozora.gr.jp/cards/000148/files/789_14547.html using the `webread` function.

Specify the character encoding of the text using the `weboptions` function. To find the correct character encoding for an HTML, look in the header of the HTML code. For this file, specify the character encoding to be "Shift_JIS".

```
url = "https://www.aozora.gr.jp/cards/000148/files/789_14547.html";
options = weboptions('CharacterEncoding', 'Shift_JIS');
code = webread(url, options);
```

View the first few lines of the HTML code.

```
extractBefore(code, "<script")
```

```
ans =
'<?xml version="1.0" encoding="Shift_JIS"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.1//EN"
"http://www.w3.org/TR/xhtml11/DTD/xhtml11.dtd">
<html xml:lang="ja" >
<head>
  <meta http-equiv="Content-Type" content="text/html; charset=Shift_JIS" />
  <meta http-equiv="content-style-type" content="text/css" />
  <link rel="stylesheet" type="text/css" href="../../aozora.css" />
  <title>夏目漱石 吾輩は猫である</title>
'
```

Extract the text data from the HTML using `extractHTMLText`. Split the text by `newline` characters.

```
textData = extractHTMLText(code);
textData = string(split(textData, newline));
textData(1:10)
```

```
ans = 10×1 string array
    "吾輩は猫である"
    ""
    "夏目漱石"
    ""
    ""
    ""
    ""
    ""
```

```
""
" 吾輩は猫である。名前はまだ無い。"
" どこで生れたかとうんと見当がつかぬ。何でも薄暗いじめじめした所でニャーニャー泣いていた事だけは記憶
```


Remove the empty lines of text.

```
idx = textData == "";
textData[idx] = [];
textData(1:10)

ans = 10×1 string array
"吾輩は猫である"
"夏目漱石"
" "
"_"
" 吾輩は猫である。名前はまだ無い。"
" どこで生れたかとうんと見当がつかぬ。何でも薄暗いじめじめした所でニャーニャー泣いていた事だけは記憶
" この書生の掌の裏でしばらくはよい心持に坐っておったが、しばらくすると非常な速力で運転し始めた。書生
" ふと気が付いて見ると書生はいない。たくさんおった兄弟が一疋も見えぬ。肝心の母親さえ姿を隠してしま
" ようやくの思いで笹原を這い出すと向うに大きな池がある。吾輩は池の前に坐ってどうしたらよかろうと考
" 吾輩の主人は滅多に吾輩と顔を合せる事がない。職業は教師だそうだ。学校から帰ると終日書齋に這入った
```

Visualize the text data in a word cloud.

```
figure
wordcloud(textData);
```



Tokenize Documents

Tokenize the text using `tokenizedDocument` and view the first few documents.

```
documents = tokenizedDocument(textData);
documents(1:10)
```

```
ans =
    10×1 tokenizedDocument:

    5 tokens: 吾輩 は 猫 で ある
    2 tokens: 夏目 漱石
    0 tokens:
    1 tokens: 一
```

11 tokens: 吾輩は猫である。名前はまだ無い。
 264 tokens: どこで生れたか とんと見当がつかぬ。何でも薄暗いじめじめした所で
 100 tokens: この書生の掌の裏でしばらくはよい心持に坐っておったが、しばらく
 92 tokens: ふと気が付いて見ると書生はいない。たくさんおった兄弟が一疋も見
 693 tokens: ようやくの思いで笹原を這い出すと向うに大きな池がある。吾輩は池の
 276 tokens: 吾輩の主人は滅多に吾輩と顔を合せる事がない。職業は教師だそうか

Get Part-of-Speech Tags

Get the token details and then view the details of the first few tokens.

```
tdetails = tokenDetails(documents);
head(tdetails)
```

ans=8x8 table

Token	DocumentNumber	LineNumber	Type	Language	PartOfSpeech
"吾輩"	1	1	letters	ja	pronoun
"は"	1	1	letters	ja	adposition
"猫"	1	1	letters	ja	noun
"で"	1	1	letters	ja	auxiliary-verb
"ある"	1	1	letters	ja	auxiliary-verb
"夏目"	2	1	letters	ja	proper-noun
"漱石"	2	1	letters	ja	proper-noun
"一"	4	1	letters	ja	numeral

The PartOfSpeech variable in the table contains the part-of-speech tags of the tokens. Create word clouds of all the nouns and adjectives, respectively.

```
figure
idx = tdetails.PartOfSpeech == "noun";
tokens = tdetails.Token(idx);
subplot(1,2,1)
wordcloud(tokens);
title("Nouns")

idx = tdetails.PartOfSpeech == "adjective";
tokens = tdetails.Token(idx);
subplot(1,2,2)
wordcloud(tokens);
title("Adjectives")
```


6 tokens: 吾輩 猫 。 まだ 無い 。
 117 tokens: 生れ とんと 見当 つか ぬ 。 薄暗い じめじめ ニャーニャー 泣い いた事 記憶 。 吾輩
 43 tokens: 書生 掌 裏 しばらく よい 心持 坐っ おっ、 しばらく 非常 速力 運転 始め 。 書生 動
 46 tokens: ふと 付い 見る 書生 。 おっ 兄弟 一疋 見え ぬ 。 肝心 母親 姿 隠し しまっ 上今 違っ 無
 323 tokens: ようやく 思い 笹原 這い出す 向う 大きな 池 。 吾輩 池 坐っ たら よかる 考え 。 別
 122 tokens: 吾輩 主人 滅多 吾輩 顔 合せる 。 職業 教師 。 学校 帰る 終日 書齋 這入っ ぎりほとん

Erase the punctuation.

```
documents = erasePunctuation(documents);
documents(1:10)
```

```
ans =
  10×1 tokenizedDocument:

    2 tokens: 吾輩 猫
    2 tokens: 夏目 漱石
    0 tokens:
    0 tokens:
    4 tokens: 吾輩 猫 まだ 無い
  102 tokens: 生れ とんと 見当 つか ぬ 薄暗い じめじめ ニャーニャー 泣い いた事 記憶 吾輩 始め
  36 tokens: 書生 掌 裏 しばらく よい 心持 坐っ おっ しばらく 非常 速力 運転 始め 書生 動く 動
  38 tokens: ふと 付い 見る 書生 おっ 兄弟 一疋 見え ぬ 肝心 母親 姿 隠し しまっ 上今 違っ 無
  274 tokens: ようやく 思い 笹原 這い出す 向う 大きな 池 吾輩 池 坐っ たら よかる 考え 別に とい
  101 tokens: 吾輩 主人 滅多 吾輩 顔 合せる 職業 教師 学校 帰る 終日 書齋 這入っ ぎりほとん 出
```

Lemmatize the text using normalizeWords.

```
documents = normalizeWords(documents);
documents(1:10)
```

```
ans =
  10×1 tokenizedDocument:

    2 tokens: 吾輩 猫
    2 tokens: 夏目 漱石
    0 tokens:
    0 tokens:
    4 tokens: 吾輩 猫 まだ 無い
  102 tokens: 生れる とんと 見当 つく ぬ 薄暗い じめじめ ニャーニャー 泣く いた事 記憶 吾輩 始め
  36 tokens: 書生 掌 裏 しばらく よい 心持 坐る おる しばらく 非常 速力 運転 始める 書生 動く 動
  38 tokens: ふと 付く 見る 書生 おる 兄弟 一疋 見える ぬ 肝心 母親 姿 隠す しまっ 上今 違っ 無
  274 tokens: ようやく 思い 笹原 這い出す 向う 大きな 池 吾輩 池 坐る た よい 考える 別に とい
```

101 tokens: 吾輩 主人 滅多 吾輩 顔 合せる 職業 教師 学校 帰る 終日 書齋 這入る ぎりほとんど 出

Some preprocessing steps, such as removing stop words and erasing punctuation, return empty documents. Remove the empty documents using the `removeEmptyDocuments` function.

```
documents = removeEmptyDocuments(documents);
```

Create Preprocessing Function

Creating a function that performs preprocessing can be useful to prepare different collections of text data in the same way. For example, you can use a function to preprocess new data using the same steps as the training data.

Create a function which tokenizes and preprocesses the text data to use for analysis. The function `preprocessJapaneseText`, performs these steps:

- 1 Tokenize the text using `tokenizedDocument`.
- 2 Erase punctuation using `erasePunctuation`.
- 3 Remove a list of stop words (such as "あそこ", "あたり", and "あちら") using `removeStopWords`.
- 4 Lemmatize the words using `normalizeWords`.

Remove the empty documents after preprocessing using the `removeEmptyDocuments` function. Removing documents after using a preprocessing function makes it easier to remove corresponding data such as labels from other sources.

In this example, use the preprocessing function `preprocessJapaneseText`, listed at the end of the example, to prepare the text data.

```
documents = preprocessJapaneseText(textData);  
documents(1:5)
```

```
ans =  
  5×1 tokenizedDocument:  
  
  2 tokens: 吾輩 猫  
  2 tokens: 夏目 漱石  
  0 tokens:  
  0 tokens:  
  4 tokens: 吾輩 猫 まだ 無い
```


Remove the empty documents.

```
documents = removeEmptyDocuments(documents);
```

Fit Topic Model

Fit a latent Dirichlet allocation (LDA) topic model to the data. An LDA model discovers underlying topics in a collection of documents and infers word probabilities in topics.

To fit an LDA model to the data, you first must create a bag-of-words model. A bag-of-words model (also known as a term-frequency counter) records the number of times that words appear in each document of a collection. Create a bag-of-words model using `bagOfWords`.

```
bag = bagOfWords(documents);
```

Remove the empty documents from the bag-of-words model.

```
bag = removeEmptyDocuments(bag);
```

Fit an LDA model with seven topics using `fitlda`. To suppress the verbose output, set 'Verbose' to 0.


```
numTopics = 7;  
mdl = fitlda(bag,numTopics,'Verbose',0);
```

Visualize the first four topics using word clouds.

```
figure  
for i = 1:4  
    subplot(2,2,i)  
    wordcloud(mdl,i);  
    title("Topic " + i)  
end
```


23 tokens: 立つ 月給 上がる いくら 勉強 褒める くれる 郎 君 独 寂寞 中学 時代 覚える 詩 句 細

```
topicMixtures = transform mdl,documents(idx));
figure
barh(topicMixtures(1:5,:), 'stacked')
xlim([0 1])
title("Topic Mixtures")
xlabel("Topic Probability")
ylabel("Document")
legend("Topic " + string(1:numTopics), 'Location', 'northeastoutside')
```



Example Preprocessing Function

The function `preprocessJapaneseText`, performs these steps:

- 1 Tokenize the text using `tokenizedDocument`.
- 2 Erase punctuation using `erasePunctuation`.
- 3 Remove a list of stop words (such as "あそこ", "あたり", and "あちら") using `removeStopWords`.
- 4 Lemmatize the words using `normalizeWords`.

```
function documents = preprocessJapaneseText(textData)

% Tokenize the text.
documents = tokenizedDocument(textData);

% Erase the punctuation.
documents = erasePunctuation(documents);

% Remove a list of stop words.
documents = removeStopWords(documents);

% Lemmatize the words.
documents = normalizeWords(documents, 'Style', 'lemma');
end
```

See Also

[addPartOfSpeechDetails](#) | [normalizeWords](#) | [removeStopWords](#) | [stopWords](#) | [tokenDetails](#) | [tokenizedDocument](#)

More About

- “Language Considerations” on page 4-2
- “Create Simple Text Model for Classification” on page 2-2
- “Analyze Text Data Using Topic Models” on page 2-18
- “Analyze Text Data Using Multiword Phrases” on page 2-9
- “Analyze Text Data Containing Emojis” on page 2-35
- “Train a Sentiment Classifier” on page 2-43
- “Classify Text Data Using Deep Learning” on page 2-53
- “Generate Text Using Deep Learning” (Deep Learning Toolbox)

See Also

German Language Support

This topic summarizes the Text Analytics Toolbox features that support German text. For an example showing how to analyze German text data, see “Analyze German Text Data” on page 4-33.

Tokenization

The `tokenizedDocument` function automatically detects German input. Alternatively, set the 'Language' option in `tokenizedDocument` to 'de'. This option specifies the language details of the tokens. To view the language details of the tokens, use `tokenDetails`. These language details determine the behavior of the `removeStopWords`, `addPartOfSpeechDetails`, `normalizeWords`, `addSentenceDetails`, and `addEntityDetails` functions on the tokens.

Tokenize German Text

Tokenize German text using `tokenizedDocument`. The function automatically detects German text.

```
str = [  
    "Guten Morgen. Wie geht es dir?"  
    "Heute wird ein guter Tag."];  
documents = tokenizedDocument(str)  
  
documents =  
    2x1 tokenizedDocument:  
  
    8 tokens: Guten Morgen . Wie geht es dir ?  
    6 tokens: Heute wird ein guter Tag .
```

Sentence Detection

To detect sentence structure in documents, use the `addSentenceDetails`. You can use the `abbreviations` function to help create custom lists of abbreviations to detect.

Add Sentence Details to German Documents

Tokenize German text using `tokenizedDocument`.

```
str = [
  "Guten Morgen, Dr. Schmidt. Geht es Ihnen wieder besser?"
  "Heute wird ein guter Tag."];
documents = tokenizedDocument(str);
```

Add sentence details to the documents using `addSentenceDetails`. This function adds the sentence numbers to the table returned by `tokenDetails`. View the updated token details of the first few tokens.

```
documents = addSentenceDetails(documents);
tdetails = tokenDetails(documents);
head(tdetails,10)
```

ans=10x6 table

Token	DocumentNumber	SentenceNumber	LineNumber	Type	Language
"Guten"	1	1	1	letters	de
"Morgen"	1	1	1	letters	de
","	1	1	1	punctuation	de
"Dr"	1	1	1	letters	de
."	1	1	1	punctuation	de
"Schmidt"	1	1	1	letters	de
."	1	1	1	punctuation	de
"Geht"	1	2	1	letters	de
"es"	1	2	1	letters	de
"Ihnen"	1	2	1	letters	de

Table of German Abbreviations

View a table of German abbreviations. Use this table to help create custom tables of abbreviations for sentence detection when using `addSentenceDetails`.

```
tbl = abbreviations('Language', 'de');
head(tbl)
```

ans=8x2 table

Abbreviation	Usage
"A.T"	regular
"ABl"	regular
"Abb"	regular

```
"Abdr"      regular
"Abf"      regular
"Abfl"     regular
"Abh"      regular
"Abk"      regular
```

Part of Speech Details

To add German part of speech details to documents, use the `addPartOfSpeechDetails` function.

Get Part of Speech Details of German Text

Tokenize German text using `tokenizedDocument`.

```
str = [
  "Guten Morgen. Wie geht es dir?"
  "Heute wird ein guter Tag."];
documents = tokenizedDocument(str)

documents =
  2x1 tokenizedDocument:

    8 tokens: Guten Morgen . Wie geht es dir ?
    6 tokens: Heute wird ein guter Tag .
```

To get the part of speech details for German text, first use `addPartOfSpeechDetails`.

```
documents = addPartOfSpeechDetails(documents);
```

To view the part of speech details, use the `tokenDetails` function.

```
tdetails = tokenDetails(documents);
head(tdetails)
```

ans=8x7 table

Token	DocumentNumber	SentenceNumber	LineNumber	Type	Language
"Guten"	1	1	1	letters	de
"Morgen"	1	1	1	letters	de

"."	1	1	1	punctuation	de
"Wie"	1	2	1	letters	de
"geht"	1	2	1	letters	de
"es"	1	2	1	letters	de
"dir"	1	2	1	letters	de
"?"	1	2	1	punctuation	de

Named Entity Recognition

To add entity tags to documents, use the `addEntityDetails` function.

Add Named Entity Tags to German Text

Tokenize German text using `tokenizedDocument`.

```
str = [
    "Ernst zog von Frankfurt nach Berlin."
    "Besuchen Sie Volkswagen in Wolfsburg."];
documents = tokenizedDocument(str);
```

To add entity tags to German text, use the `addEntityDetails` function. This function detects person names, locations, organizations, and other named entities.

```
documents = addEntityDetails(documents);
```

To view the entity details, use the `tokenDetails` function.

```
tetails = tokenDetails(documents);
head(tetails)
```

ans=8x8 table

Token	DocumentNumber	SentenceNumber	LineNumber	Type	Language
"Ernst"	1	1	1	letters	de
"zog"	1	1	1	letters	de
"von"	1	1	1	letters	de
"Frankfurt"	1	1	1	letters	de
"nach"	1	1	1	letters	de
"Berlin"	1	1	1	letters	de
"."	1	1	1	punctuation	de
"Besuchen"	2	1	1	letters	de

View the words tagged with entity "person", "location", "organization", or "other". These words are the words not tagged with "non-entity".

```
idx = tdetails.Entity ~= "non-entity";
tdetails(idx,:)
```

```
ans=5x8 table
```

Token	DocumentNumber	SentenceNumber	LineNumber	Type	Language
"Ernst"	1	1	1	letters	de
"Frankfurt"	1	1	1	letters	de
"Berlin"	1	1	1	letters	de
"Volkswagen"	2	1	1	letters	de
"Wolfsburg"	2	1	1	letters	de

Stop Words

To remove stop words from documents according to the token language details, use `removeStopWords`. For a list of German stop words set the 'Language' option in `stopWords` to 'de'.

Remove German Stop Words from Documents

Tokenize German text using `tokenizedDocument`. The function automatically detects German text.

```
str = [
    "Guten Morgen. Wie geht es dir?"
    "Heute wird ein guter Tag."];
documents = tokenizedDocument(str)

documents =
    2x1 tokenizedDocument:

    8 tokens: Guten Morgen . Wie geht es dir ?
    6 tokens: Heute wird ein guter Tag .
```

Remove stop words using the `removeStopWords` function. The function uses the language details from documents to determine which language stop words to remove.

```
documents = removeStopWords(documents)

documents =
  2x1 tokenizedDocument:

    5 tokens: Guten Morgen . geht ?
    5 tokens: Heute wird guter Tag .
```

Stemming

To stem tokens according to the token language details, use `normalizeWords`.

Stem German Text

Tokenize German text using the `tokenizedDocument` function. The function automatically detects German text.

```
str = [
  "Guten Morgen. Wie geht es dir?"
  "Heute wird ein guter Tag."];
documents = tokenizedDocument(str);
```

Stem the tokens using `normalizeWords`.

```
documents = normalizeWords(documents)

documents =
  2x1 tokenizedDocument:

    8 tokens: gut morg . wie geht es dir ?
    6 tokens: heut wird ein gut tag .
```

Language-Independent Features

Word and N-Gram Counting

The `bagOfWords` and `bagOfNgrams` functions support `tokenizedDocument` input regardless of language. If you have a `tokenizedDocument` array containing your data, then you can use these functions.

Modeling and Prediction

The `fitlda` and `fitlsa` functions support `bagOfWords` and `bagOfNgrams` input regardless of language. If you have a `bagOfWords` or `bagOfNgrams` object containing your data, then you can use these functions.

The `trainWordEmbedding` function supports `tokenizedDocument` or file input regardless of language. If you have a `tokenizedDocument` array or a file containing your data in the correct format, then you can use this function.

See Also

`addLanguageDetails` | `addPartOfSpeechDetails` | `normalizeWords` | `removeStopWords` | `stopWords` | `tokenDetails` | `tokenizedDocument`

More About

- “Language Considerations” on page 4-2
- “Analyze German Text Data” on page 4-33


Analyze German Text Data

This example shows how to import, prepare, and analyze German text data using a topic model.

German text data can be large and can contain lots of noise that negatively affects statistical analysis. For example, the text data can contain the following:

- Variations in word forms. For example, „rot“, „rote“, and „roten“.
- Words that add noise. For example, stop words such as „der“, „die“, and „das“.
- Punctuation and special characters.

These word clouds illustrate word frequency analysis applied to some raw text data and a preprocessed version of the same text data.



This example first shows how to import and prepare German text data, and then it shows how to analyze the text data using a Latent Dirichlet Allocation (LDA) model. An LDA model is a topic model that discovers underlying topics in a collection of documents and infers the word probabilities in topics. Use these steps in preparing the text data and fitting the model:

- Import the text data from a CSV file and extract the relevant data.
- Prepare the text data for analysis using standard preprocessing techniques.
- Fit a topic model and visualize the results.

Import Data

Download the data `vorhaben.csv` from <https://opendata.bonn.de/dataset/vorhabenliste-b%C3%BCrgerbeteiligungen-planungen-und-projekte>. This file can change over time, so the results in the example can vary.

Use `detectImportOptions` to determine the format of the CSV file and set the text type to string. Set the 'Encoding' option to 'ISO-8859-15'. Read the data using the `readtable` function and view the first few rows.

```
filename = "vorhaben.csv";
options = detectImportOptions(filename, 'TextType', 'string', 'Encoding', 'ISO-8859-15');
data = readtable(filename, options);
head(data)
```

`ans=8x19 table`

Titel

```
"Bauleitplanverfahren zur Aufstellung des vorhabenbezogenen↵Bebauungsplans Nr. 662
"Bauleitplanverfahren zur Aufstellung des vorhabenbezogenen↵Bebauungsplans Nr. 652
"Bauleitplanverfahren zur Aufstellung des Bebauungsplans↵Nr. 7621-56 ?Sebastianstra
"EPICURO - European Partnership for Innovative Cities within and Urban Resilience (
"Bauleitplanverfahren zur Aufstellung des Bebauungsplanes Nr. 6719-3 "Schwimmbad Wa
"Bürgerbeteiligung an der Konzepterstellung für den Neubau eines Schwimmbades in B
"Integriertes Handlungskonzept Grüne Infrastruktur (InHK GI) zur↵zukünftigen Freira
"Verlängerung des Teufelsbachweges bis zur L 83n"
```

Extract the text data from the variable `InhaltlicheBeschreibungUndZielsetzung` (the description of the content and the goal).

```
textData = data.InhaltlicheBeschreibungUndZielsetzung;
```

Visualize the text data in a word cloud.

```
figure
wordcloud(textData);
```


24 tokens: Schaffung von Planungsrecht für den Bau eines neuen Familien - , Schul
 80 tokens: Für die begleitende Bürgerbeteiligung bei der Konzepterstellung für das
 60 tokens: In der Gebietskulisse des Grünen C sollen die Freiräume auch zukünftig
 51 tokens: Zur Entlastung von Pützchen / Bechlinghoven vor Durchgangsverkehr und
 29 tokens: Für das Areal der ehemaligen Landwirtschaftskammer sowie einer angrenz
 37 tokens: Für das Areal Herbert-Rabius-Straße im Stadtbezirk Beuel , Ortsteil Beu

Get Part-of-Speech Tags

Add the part of speech details using the `addPartOfSpeechDetails` function.

```
documents = addPartOfSpeechDetails(documents);
```

Get the token details and then view the details of the first few tokens.

```
tdetails = tokenDetails(documents);
head(tdetails)
```

```
ans=8x7 table
      Token      DocumentNumber      SentenceNumber      LineNumber      Type
-----
"Für"          1          1          1      letters
"das"          1          1          1      letters
"Gebiet"        1          1          1      letters
"zwischen"      1          1          1      letters
"Reuterstraße" 1          1          1      letters
", "           1          1          1      punctuat.
"Bundeskanzlerplatz" 1          1          1      letters
", "           1          1          1      punctuat.
```

The `PartOfSpeech` variable in the table contains the part-of-speech tags of the tokens. Create word clouds of all the nouns and adjectives, respectively.

```
figure
idx = tdetails.PartOfSpeech == "noun";
tokens = tdetails.Token(idx);
subplot(1,2,1)
wordcloud(tokens);
title("Nouns")

idx = tdetails.PartOfSpeech == "adjective";
tokens = tdetails.Token(idx);
```



```

50 tokens: Für das Gebiet zwischen Reuterstraße , Bundeskanzlerplatz , Willy-Brandt-Allee
46 tokens: Für den vorhabenbezogenen Bebauungsplan Nr . 6522-1 ? Didinkirica ? Bundesstadt Bonn
41 tokens: Für das Gebiet zwischen Alfred-Bucherer-Straße , Sebastianstraße und Fußweg zwischen
134 tokens: In den vergangenen Jahren führte der Klimawandel zu einer Vielzahl von Folgen Umwelt , Wirtschaft
24 tokens: Schaffung von Planungsrecht für den Bau eines neuen Familien - , Schul - Sportschwimmbades
80 tokens: Für die begleitende Bürgerbeteiligung bei der Konzepterstellung für neue Schwimmbad soll für
60 tokens: In der Gebietskulisse des Grünen C sollen die Freiräume auch zukünftig im Sinne Naherholung ,
51 tokens: Zur Entlastung von Pützchen / Bechlinghoven vor Durchgangsverkehr und Verbindung geplant
29 tokens: Für das Areal der ehemaligen Landwirtschaftskammer sowie einer angrenzenden städtischen Fläche
37 tokens: Für das Areal Herbert-Rabius-Straße im Stadtbezirk Beuel , Ortsteil Beuel-Mitte soll

```

Replace common phrases (n-grams) with a single token and remove the stop words.

```

old = ["Bad" "Godesberg"];
new = "Bad Godesberg";
documents = replaceNgrams(documents,old,new);
documents = removeStopWords(documents);
documents(1:10)

```

```

ans =
    10x1 tokenizedDocument:

    35 tokens: Gebiet zwischen Reuterstraße , Bundeskanzlerplatz , Willy-Brandt-Allee
    33 tokens: vorhabenbezogenen Bebauungsplan Nr . 6522-1 ? Didinkirica ? Bundesstadt Bonn
    27 tokens: Gebiet zwischen Alfred-Bucherer-Straße , Sebastianstraße Fußweg zwischen
    81 tokens: vergangenen Jahren führte Klimawandel Vielzahl Folgen Umwelt , Wirtschaft
    15 tokens: Schaffung Planungsrecht Bau neuen Familien - , Schul - Sportschwimmbades
    57 tokens: begleitende Bürgerbeteiligung Konzepterstellung neue Schwimmbad soll für
    40 tokens: Gebietskulisse Grünen C sollen Freiräume zukünftig im Sinne Naherholung ,
    32 tokens: Entlastung Pützchen / Bechlinghoven Durchgangsverkehr Verbindung geplant
    19 tokens: Areal ehemaligen Landwirtschaftskammer sowie angrenzenden städtischen Fläche
    25 tokens: Areal Herbert-Rabius-Straße Stadtbezirk Beuel , Ortsteil Beuel-Mitte soll

```

Normalize the text using the `normalizeWords` function.

```

documents = normalizeWords(documents);
documents(1:10)

```

```

ans =
    10x1 tokenizedDocument:

    35 tokens: gebiet zwisch reuterstrass , bundeskanzlerplatz , willy-brandt-alle ,
    33 tokens: vorhabenbezog bebauungsplan nr . 6522-1 ? didinkirica ? bundesstadt bonn

```

```
27 tokens: gebiet zwisch alfred-bucherer-strass , sebastianstrass fussweg zwisch ro
81 tokens: vergang jahr fuhr klimawandel vielzahl folg umwelt , wirtschaft menschl
15 tokens: schaffung planungsrecht bau neu famili - , schul - sportschwimmbad flach
57 tokens: begleit burgerbeteil konzepterstell neu schwimmbad soll folgend them bet
40 tokens: gebietskuliss grun c soll freiraum zukunft sinn naherhol , landwirtschaft
32 tokens: entlast putzch / bechlinghov durchgangsverkehr verbind geplant anschluss
19 tokens: areal ehemal landwirtschaftskamm sowi angrenz stadtisch flach stadtbezi
25 tokens: areal herbert-rabius-strass stadtbezirk beuel , ortsteil beuel-mitt soll
```

Erase the punctuation using the `erasePunctuation` function.

```
documents = erasePunctuation(documents);
documents(1:10)
```

```
ans =
  10x1 tokenizedDocument:

  27 tokens: gebiet zwisch reuterstrass bundeskanzlerplatz willybrandtalle eduardpflu
  25 tokens: vorhabenbezog bebauungsplan nr 65221 didinkirica bundesstadt bonn stadt
  22 tokens: gebiet zwisch alfredbuchererstrass sebastianstrass fussweg zwisch rocku
  64 tokens: vergang jahr fuhr klimawandel vielzahl folg umwelt wirtschaft menschl
  11 tokens: schaffung planungsrecht bau neu famili schul sportschwimmbad flach nord
  41 tokens: begleit burgerbeteil konzepterstell neu schwimmbad soll folgend them bet
  31 tokens: gebietskuliss grun c soll freiraum zukunft sinn naherhol landwirtschaft
  27 tokens: entlast putzch bechlinghov durchgangsverkehr verbind geplant anschluss
  18 tokens: areal ehemal landwirtschaftskamm sowi angrenz stadtisch flach stadtbezi
  19 tokens: areal herbertrabiusstrass stadtbezirk beuel ortsteil beuelmitt soll vor
```

Visualize the raw and cleaned data in word clouds.

```
figure
subplot(1,2,1)
wordcloud(documentsRaw);
title("Raw Data")

subplot(1,2,2)
wordcloud(documents);
title("Cleaned Data")
```


- 3 Remove a list of stop words (such as „der“, „die“, and „das“) using `removeStopWords`.
- 4 Normalize the words using `normalizeWords`.
- 5 Erase punctuation using `erasePunctuation`.

Remove the empty documents after preprocessing using the `removeEmptyDocuments` function. Removing documents after using a preprocessing function makes it easier to remove corresponding data such as labels from other sources.

In this example, use the preprocessing function `preprocessGermanText`, listed at the end of the example, to prepare the text data.

```
documents = preprocessGermanText(textData);
documents(1:5)
```

```
ans =
    5×1 tokenizedDocument:
```

```
    27 tokens: gebiet zwisch reuterstrass bundeskanzlerplatz willybrandtalle eduardpflu
    25 tokens: vorhabenbezog bebauungsplan nr 65221 didinkirica bundesstadt bonn stadt
    22 tokens: gebiet zwisch alfredbuchererstrass sebastianstrass fussweg zwisch rockun
    64 tokens: vergang jahr fuhr klimawandel vielzahl folg umwelt wirtschaft mensch st
    11 tokens: schaffung planungsrecht bau neu famili schul sportschwimmbad flach nord
```

Remove the empty documents using the `removeEmptyDocuments` function.

```
documents = removeEmptyDocuments(documents);
```

Fit Topic Model

Fit a latent Dirichlet allocation (LDA) topic model to the data. An LDA model discovers underlying topics in a collection of documents and infers word probabilities in topics.

To fit an LDA model to the data, you first must create a bag-of-words model. A bag-of-words model (also known as a term-frequency counter) records the number of times that words appear in each document of a collection. Create a bag-of-words model using `bagOfWords`.

```
bag = bagOfWords(documents);
```

Remove the empty documents from the bag-of-words model.

```
bag = removeEmptyDocuments(bag);
```


Visualize multiple topic mixtures using stacked bar charts. View five input documents at random and visualize the corresponding topic mixtures.


```
numDocuments = numel(documents);
idx = randperm(numDocuments,5);
documents(idx)

ans =
    5×1 tokenizedDocument:

    4 tokens: gastronom Angebot sollt verbessert
   82 tokens: grunflach dietrichglaunerstrass rand dorfplatz entlang fussweg mehlem l
  116 tokens: sportplatz plittersdorf kommt leid regelmass unschon vorfall einsehbar
   64 tokens: mainz strass bereich geschaft kirch uberwieg beidseit zugeparkt unschon
   50 tokens: "1" "bezirksverodnet" "sollt" "kulturburgermeist" "gewahlt" "hatt" "au

topicMixtures = transform mdl,documents(idx));

figure
barh(topicMixtures(1:5,:), 'stacked')
xlim([0 1])
title("Topic Mixtures")
xlabel("Topic Probability")
ylabel("Document")
legend("Topic " + string(1:numTopics), 'Location', 'northeastoutside')
```

Example Preprocessing Function

The function `preprocessGermanText`, performs these steps:

- 1 Tokenize the text using `tokenizedDocument`.
- 2 Replace the multiword phrase `["Bad" "Godesberg"]` with `"Bad Godesberg"`.
- 3 Remove a list of stop words (such as `„der“`, `„die“`, and `„das“`) using `removeStopWords`.
- 4 Normalize the words using `normalizeWords`.
- 5 Erase punctuation using `erasePunctuation`.

```
function documents = preprocessGermanText(textData)
```

```
% Tokenize the text.
documents = tokenizedDocument(textData);

% Replace multiword phrases
old = ["Bad" "Godesberg"];
new = "Bad Godesberg";
documents = replaceNgrams(documents,old,new);

% Remove a list of stop words.
documents = removeStopWords(documents);

% Normalize the words.
documents = normalizeWords(documents);

% Erase the punctuation.
documents = erasePunctuation(documents);

end
```

See Also

[addPartOfSpeechDetails](#) | [normalizeWords](#) | [removeStopWords](#) | [stopWords](#) | [tokenDetails](#) | [tokenizedDocument](#)

More About

- “Language Considerations” on page 4-2
- “Create Simple Text Model for Classification” on page 2-2
- “Analyze Text Data Using Topic Models” on page 2-18
- “Analyze Text Data Using Multiword Phrases” on page 2-9
- “Analyze Text Data Containing Emojis” on page 2-35
- “Train a Sentiment Classifier” on page 2-43
- “Classify Text Data Using Deep Learning” on page 2-53
- “Generate Text Using Deep Learning” (Deep Learning Toolbox)

Language-Independent Features

Word and N-Gram Counting

The `bagOfWords` and `bagOfNgrams` functions support `tokenizedDocument` input regardless of language. If you have a `tokenizedDocument` array containing your data, then you can use these functions.

Modeling and Prediction

The `fitlda` and `fitlsa` functions support `bagOfWords` and `bagOfNgrams` input regardless of language. If you have a `bagOfWords` or `bagOfNgrams` object containing your data, then you can use these functions.

The `trainWordEmbedding` function supports `tokenizedDocument` or file input regardless of language. If you have a `tokenizedDocument` array or a file containing your data in the correct format, then you can use this function.

See Also

`addLanguageDetails` | `addSentenceDetails` | `bagOfNgrams` | `bagOfWords` | `fitlda` | `fitlsa` | `normalizeWords` | `removeWords` | `stopWords` | `tokenizedDocument` | `wordcloud`

More About

- “Text Data Preparation”
- “Modeling and Prediction”
- “Display and Presentation”
- “Japanese Language Support” on page 4-6
- “Analyze Japanese Text Data” on page 4-12
- “German Language Support” on page 4-26
- “Analyze German Text Data” on page 4-33

Glossary

Text Analytics Glossary

This section provides a list of terms used in text analytics.

Documents and Tokens

Term	Definition	More Information
Bigram	Two tokens in succession. For example, ["New" "York"].	bagOfNgrams
Complex token	A token with complex structure. For example, an email address or a hash tag.	tokenDetails
Context	Tokens or characters that surround a given token.	context
Corpus	A collection of documents.	tokenizedDocument
Document	A single observation of text data. For example, a report, a tweet, or an article.	tokenizedDocument
Grapheme	A human readable character. A grapheme can consist of multiple Unicode code points. For example, "a", "□□" or "語".	splitGraphemes
N-gram	<i>N</i> tokens in succession.	bagOfNgrams
Part of speech	Categories of words used in grammatical structure. For example, "noun", "verb", and "adjective".	addPartOfSpeechDetails
Token	A string of characters representing a unit of text data, also known as a "unigram". For example, a word, number, or email address.	tokenizedDocument

Term	Definition	More Information
Token details	Information about the token. For example, type, language, or part-of-speech details.	tokenDetails
Token types	The category of the token. For example, "letters", "punctuation", or "email address".	tokenDetails
Tokenized document	A document split into tokens.	tokenizedDocument
Trigram	Three tokens in succession. For example, ["The" "United" "States"]	bagOfNgrams
Vocabulary	Unique words or tokens in a corpus or model.	tokenizedDocument

Preprocessing

Term	Definition	More Information
Normalize	Reduce words to a root form. For example, reduce the word "walking" to "walk" using stemming or lemmatization.	normalizeWords
Lemmatize	Reduce words to a dictionary word (the lemma form). For example, reduce the words "running" and "ran" to "run".	normalizeWords

Term	Definition	More Information
Stem	Reduce words by removing inflections. The reduced word is not necessarily a real word. For example, the Porter stemmer reduces the words "happy" and "happiest" to "happi".	normalizeWords
Stop words	Words commonly removed before analysis. For example "and", "of", and "the".	removeStopWords

Modeling and Prediction

Bag-of-Words

Term	Definition	More Information
Bag-of-n-grams model	A model that records the number of times that n-grams appear in each document of a corpus.	bagOfNgrams
Bag-of-words model	A model that records the number of times that words appear in each document of a collection.	bagOfWords
Term frequency count matrix	A matrix of the frequency counts of words occurring in a collection of documents corresponding to a given vocabulary. This matrix is the underlying data of a bag-of-words model.	bagOfWords

Term	Definition	More Information
Term Frequency-Inverse Document Frequency (tf-idf) matrix	A statistical measure based on the word frequency counts in documents and the proportion of documents containing the words in the corpus.	tfidf

Latent Dirichlet Allocation

Term	Definition	More Information
Corpus topic probabilities	The probabilities of observing each topic in the corpus used to fit the LDA model.	ldaModel
Document topic probabilities	The probabilities of observing each topic in each document used to fit the LDA model. Equivalently, the topic mixtures of the training documents.	ldaModel
Latent Dirichlet allocation (LDA)	A generative statistical topic model that infers topic probabilities in documents and word probabilities in topics.	fitlda
Perplexity	A statistical measure of how well a model describes the given data. A lower perplexity indicates a better fit.	logp
Topic	A distribution of words, characterized by the "topic word probabilities".	ldaModel

Term	Definition	More Information
Topic concentration	The concentration parameter of the underlying Dirichlet distribution of the corpus topics mixtures.	<code>ldaModel</code>
Topic mixture	The probabilities of topics in a given document.	<code>transform</code>
Topic word probabilities	The probabilities of words in a given topic.	<code>ldaModel</code>
Word concentration	The concentration parameter of the underlying Dirichlet distribution of the topics.	<code>ldaModel</code>

Latent Semantic Analysis

Term	Definition	More Information
Component weights	The singular values of the decomposition, squared.	<code>lsaModel</code>
Document scores	The score vectors in lower dimensional space of the documents used to fit the LSA model.	<code>transform</code>
Latent semantic analysis (LSA)	A dimension reducing technique based on principal component analysis (PCA).	<code>fitlsa</code>
Word scores	The scores of each word in each component of the LSA model.	<code>lsaModel</code>

Word Embeddings

Term	Definition	More Information
Word embedding	A model, popularized by the word2vec, GloVe, and fastText libraries, that maps words in a vocabulary to real vectors.	wordEmbedding
Word embedding layer	A deep learning network layer that learns a word embedding during training.	wordEmbeddingLayer
Word encoding	A model that maps words to numeric indices.	wordEncoding

Visualization

Term	Definition	More Information
Text scatter plot	A scatter plot with words plotted at specified coordinates instead of markers.	textscatter
Word cloud	A chart that displays words with sizes corresponding to numeric data, usually frequency counts.	wordcloud

See Also

addPartOfSpeechDetails | bagOfNgrams | bagOfWords | fitlda |
 normalizeWords | removeStopWords | textscatter | tokenDetails |
 tokenizedDocument | wordEmbedding | wordEmbeddingLayer | wordEncoding |
 wordcloud

More About

- “Try Text Analytics in 10 Lines of Code”

- “Import Text Data into MATLAB”
- “Create Simple Preprocessing Function”
- “Get Started with Topic Modeling”
- “Visualize Text Data Using Word Clouds” on page 3-2